



## INDEX

---

### A

- abbreviating commands [2-3](#)
- AC (command switch) [6-10](#)
- access-class command [31-17](#)
- access control entries
  - See ACEs
- access-denied response, VMPS [13-23](#)
- access groups
  - Layer 3 [31-19](#)
- access groups, applying IPv4 ACLs to interfaces [31-18](#)
- accessing
  - clusters, switch [6-13](#)
  - command switches [6-11](#)
  - member switches [6-13](#)
  - switch clusters [6-13](#)
- accessing stack members [7-21](#)
- access lists
  - See ACLs
- access ports
  - in switch clusters [6-9](#)
- access ports, defined [12-3](#)
- accounting
  - with 802.1x [10-55](#)
  - with IEEE 802.1x [10-17](#)
  - with RADIUS [9-35](#)
  - with TACACS+ [9-11, 9-17](#)
- ACEs
  - and QoS [33-8](#)
  - defined [31-2](#)
  - Ethernet [31-2](#)
  - IP [31-2](#)
- ACLs
  - ACEs [31-2](#)
  - any keyword [31-11](#)
  - applying
    - time ranges to [31-15](#)
    - to an interface [31-18](#)
    - to QoS [33-8](#)
  - classifying traffic for QoS [33-48](#)
  - comments in [31-16](#)
  - compiling [31-20](#)
  - defined [31-1, 31-7](#)
  - examples of [31-20, 33-48](#)
  - extended IP, configuring for QoS classification [33-49](#)
  - extended IPv4
    - creating [31-9](#)
    - matching criteria [31-7](#)
  - hardware and software handling [31-19](#)
  - host keyword [31-11](#)
  - IP
    - creating [31-7](#)
    - fragments and QoS guidelines [33-38](#)
    - implicit deny [31-9, 31-12, 31-14](#)
    - implicit masks [31-9](#)
    - matching criteria [31-7](#)
    - undefined [31-19](#)
  - IPv4
    - applying to interfaces [31-18](#)
    - creating [31-7](#)
    - matching criteria [31-7](#)
    - named [31-13](#)
    - numbers [31-7](#)
    - terminal lines, setting on [31-17](#)
    - unsupported features [31-6](#)

- MAC extended [31-22, 33-50](#)
- matching [31-7, 31-19](#)
- monitoring [31-25](#)
- named, IPv4 [31-13](#)
- number per QoS class map [33-38](#)
- port [31-2](#)
- precedence of [31-2](#)
- QoS [33-8, 33-48](#)
- resequencing entries [31-13](#)
- router [31-2](#)
- standard IP, configuring for QoS classification [33-48](#)
- standard IPv4
  - creating [31-8](#)
  - matching criteria [31-7](#)
- support for [1-10](#)
- support in hardware [31-19](#)
- time ranges [31-15](#)
- types supported [31-2](#)
- unsupported features, IPv4 [31-6](#)
- active link [19-4, 19-5, 19-6](#)
- active links [19-2](#)
- active traffic monitoring, IP SLAs [32-1](#)
- address aliasing [22-2](#)
- addresses
  - displaying the MAC address table [5-30](#)
  - dynamic
    - accelerated aging [16-9](#)
    - changing the aging time [5-22](#)
    - default aging [16-9](#)
    - defined [5-20](#)
    - learning [5-21](#)
    - removing [5-23](#)
  - IPv6 [35-2](#)
  - MAC, discovering [5-31](#)
  - multicast, STP address management [16-9](#)
  - static
    - adding and removing [5-27](#)
    - defined [5-20](#)
- address resolution [5-31](#)
- Address Resolution Protocol
  - See ARP
- advertisements
  - CDP [25-1](#)
  - LLDP [26-2](#)
  - VTP [13-15, 14-3, 14-4](#)
- aggregatable global unicast addresses [35-3](#)
- aggregated ports
  - See EtherChannel
- aggregate policers [33-58](#)
- aggregate policing [1-14](#)
- aging, accelerating [16-9](#)
- aging time
  - accelerated
    - for MSTP [17-25](#)
    - for STP [16-9, 16-23](#)
  - MAC address table [5-22](#)
  - maximum
    - for MSTP [17-26](#)
    - for STP [16-23, 16-24](#)
- alarms, RMON [28-3](#)
- allowed-VLAN list [13-17](#)
- ARP
  - defined [1-6, 5-31](#)
  - table
    - address resolution [5-31](#)
    - managing [5-31](#)
- attributes, RADIUS
  - vendor-proprietary [9-38](#)
  - vendor-specific [9-36](#)
- attribute-value pairs [10-14, 10-17, 10-22, 10-23](#)
- authentication
  - local mode with AAA [9-40](#)
  - NTP associations [5-5](#)
  - open1x [10-33](#)
  - RADIUS
    - key [9-28](#)
    - login [9-30](#)
  - TACACS+

- defined [9-11](#)
- key [9-13](#)
- login [9-14](#)
- See also port-based authentication
- authentication compatibility with Catalyst 6000 switches [10-9](#)
- authentication failed VLAN
  - See restricted VLAN
- authentication manager
  - CLI commands [10-10](#)
  - compatibility with older 802.1x CLI commands [10-10 to ??](#)
  - overview [10-8](#)
- authoritative time source, described [5-3](#)
- authorization
  - with RADIUS [9-34](#)
  - with TACACS+ [9-11, 9-16](#)
- authorized ports with IEEE 802.1x [10-11](#)
- autoconfiguration [3-3](#)
- auto enablement [10-34](#)
- automatic advise (auto-advise) in switch stacks [7-11](#)
- automatic copy (auto-copy) in switch stacks [7-10](#)
- automatic discovery
  - considerations
    - beyond a noncandidate device [6-8](#)
    - brand new switches [6-9](#)
    - connectivity [6-5](#)
    - different VLANs [6-7](#)
    - management VLANs [6-8](#)
    - non-CDP-capable devices [6-7](#)
    - noncluster-capable devices [6-7](#)
  - in switch clusters [6-5](#)
  - See also CDP
- automatic extraction (auto-extract) in switch stacks [7-10](#)
- automatic QoS
  - See QoS
- automatic recovery, clusters [6-10](#)
  - See also HSRP
- automatic upgrades (auto-upgrade) in switch stacks [7-10](#)

- auto-MDIX
  - configuring [12-30](#)
  - described [12-29](#)
- autonegotiation
  - duplex mode [1-4](#)
  - interface configuration guidelines [12-27](#)
  - mismatches [38-12](#)
- Auto-QoS video devices [1-14](#)
- autosensing, port speed [1-4](#)
- auxiliary VLAN
  - See voice VLAN
- availability, features [1-8](#)

---

## B

- BackboneFast
  - described [18-7](#)
  - disabling [18-17](#)
  - enabling [18-17](#)
  - support for [1-8](#)
- backup interfaces
  - See Flex Links
- backup links [19-2](#)
- banners
  - configuring
    - login [5-20](#)
    - message-of-the-day login [5-19](#)
  - default configuration [5-18](#)
  - when displayed [5-18](#)
- Berkeley r-tools replacement [9-52](#)
- binding database
  - DHCP snooping
    - See DHCP snooping binding database
- bindings
  - DHCP snooping database [20-7](#)
  - IP source guard [20-14](#)
- binding table, DHCP snooping
  - See DHCP snooping binding database
- blocking packets [23-7](#)

## booting

- boot loader, function of [3-2](#)
- boot process [3-2](#)
- manually [3-19](#)
- specific image [3-20](#)

## boot loader

- accessing [3-21](#)
- described [3-2](#)
- environment variables [3-21](#)
- prompt [3-21](#)
- trap-door mechanism [3-2](#)

## BPDU

- error-disabled state [18-3](#)
- filtering [18-3](#)
- RSTP format [17-13](#)

## BPDU filtering

- described [18-3](#)
- disabling [18-15](#)
- enabling [18-15](#)
- support for [1-8](#)

## BPDU guard

- described [18-2](#)
- disabling [18-14](#)
- enabling [18-14](#)
- support for [1-8](#)

## bridge protocol data unit

See BPDU

broadcast storm-control command [23-4](#)broadcast storms [23-1](#)


---

**C**
cables, monitoring for unidirectional links [24-1](#)

## candidate switch

- automatic discovery [6-5](#)
- defined [6-4](#)
- requirements [6-4](#)

See also command switch, cluster standby group, and member switch

## Catalyst 6000 switches

- authentication compatibility [10-9](#)

## CA trustpoint

- configuring [9-49](#)
- defined [9-47](#)

## CDP

- and trusted boundary [33-43](#)
- automatic discovery in switch clusters [6-5](#)
- configuring [25-2](#)
- default configuration [25-2](#)
- defined with LLDP [26-1](#)
- described [25-1](#)
- disabling for routing device [25-4](#)
- enabling and disabling
  - on an interface [25-4](#)
  - on a switch [25-4](#)
- monitoring [25-5](#)
- overview [25-1](#)
- power negotiation extensions [12-5](#)
- support for [1-6](#)
- switch stack considerations [25-2](#)
- transmission timer and holdtime, setting [25-3](#)
- updates [25-3](#)

## CGMP

- as IGMP snooping learning method [22-9](#)
- joining multicast group [22-3](#)

CipherSuites [9-48](#)Cisco 7960 IP Phone [15-1](#)

## Cisco Discovery Protocol

See CDP

Cisco intelligent power management [12-5](#)

## Cisco IOS File System

See IFS

Cisco IOS IP Service Level Agreements (SLAs) responder [1-5](#)Cisco IOS IP SLAs [32-2](#)

## Cisco Secure ACS

- attribute-value pairs for downloadable ACLs [10-23](#)
- attribute-value pairs for redirect URL [10-22](#)

- Cisco Secure ACS configuration guide [10-67](#)
- CiscoWorks 2000 [1-5, 30-4](#)
- CISP [10-34](#)
- CIST regional root
  - See MSTP
- CIST root
  - See MSTP
- civic location [26-3](#)
- class maps for QoS
  - configuring [33-51](#)
  - described [33-8](#)
  - displaying [33-79](#)
- class of service
  - See CoS
- clearing interfaces [12-38](#)
- CLI
  - abbreviating commands [2-3](#)
  - command modes [2-1](#)
  - configuration logging [2-4](#)
  - described [1-5](#)
  - editing features
    - enabling and disabling [2-6](#)
    - keystroke editing [2-7](#)
    - wrapped lines [2-8](#)
  - error messages [2-4](#)
  - filtering command output [2-9](#)
  - getting help [2-3](#)
  - history
    - changing the buffer size [2-5](#)
    - described [2-5](#)
    - disabling [2-6](#)
    - recalling commands [2-6](#)
  - managing clusters [6-16](#)
  - no and default forms of commands [2-4](#)
- Client Information Signalling Protocol
  - See CISP
- client mode, VTP [14-3](#)
- clock
  - See system clock
- clusters, switch
  - accessing [6-13](#)
  - automatic discovery [6-5](#)
  - automatic recovery [6-10](#)
  - benefits [1-2](#)
  - compatibility [6-5](#)
  - described [6-1](#)
  - LRE profile considerations [6-16](#)
  - managing
    - through CLI [6-16](#)
    - through SNMP [6-17](#)
  - planning [6-5](#)
  - planning considerations
    - automatic discovery [6-5](#)
    - automatic recovery [6-10](#)
    - CLI [6-16](#)
    - host names [6-13](#)
    - IP addresses [6-13](#)
    - LRE profiles [6-16](#)
    - passwords [6-13](#)
    - RADIUS [6-16](#)
    - SNMP [6-14, 6-17](#)
    - switch stacks [6-14](#)
    - TACACS+ [6-16](#)

See also candidate switch, command switch, cluster standby group, member switch, and standby command switch
- cluster standby group
  - automatic recovery [6-12](#)
  - considerations [6-11](#)
  - defined [6-2](#)
  - requirements [6-3](#)
  - virtual IP address [6-11](#)
  - See also HSRP
- CNS [1-6](#)
- Configuration Engine
  - configID, deviceID, hostname [4-3](#)
  - configuration service [4-2](#)
  - described [4-1](#)

- event service [4-3](#)
- embedded agents
  - described [4-5](#)
  - enabling automated configuration [4-6](#)
  - enabling configuration agent [4-9](#)
  - enabling event agent [4-7](#)
  - management functions [1-6](#)
- CoA Request Commands [9-23](#)
- Coarse Wave Division Multiplexer
  - See CWDM SFPs
- command-line interface
  - See CLI
- command modes [2-1](#)
- commands
  - abbreviating [2-3](#)
  - no and default [2-4](#)
- commands, setting privilege levels [9-8](#)
- command switch
  - accessing [6-11](#)
  - active (AC) [6-10](#)
  - configuration conflicts [38-12](#)
  - defined [6-2](#)
  - passive (PC) [6-10](#)
  - password privilege levels [6-17](#)
  - priority [6-10](#)
  - recovery
    - from command-switch failure [6-10, 38-8](#)
    - from lost member connectivity [38-12](#)
  - redundant [6-10](#)
  - replacing
    - with another switch [38-11](#)
    - with cluster member [38-9](#)
  - requirements [6-3](#)
  - standby (SC) [6-10](#)
  - See also candidate switch, cluster standby group, member switch, and standby command switch
- community strings
  - configuring [6-14, 30-8](#)
  - for cluster switches [30-4](#)
  - in clusters [6-14](#)
  - overview [30-4](#)
  - SNMP [6-14](#)
- compatibility, feature [23-12](#)
- compatibility, software
  - See stacks, switch
- config.text [3-18](#)
- configurable leave timer, IGMP [22-6](#)
- configuration, initial
  - defaults [1-16](#)
  - Express Setup [1-2](#)
- configuration changes, logging [29-11](#)
- configuration conflicts, recovering from lost member connectivity [38-12](#)
- configuration examples, network [1-18](#)
- configuration files
  - archiving [A-20](#)
  - clearing the startup configuration [A-19](#)
  - creating using a text editor [A-10](#)
  - default name [3-18](#)
  - deleting a stored configuration [A-19](#)
  - described [A-8](#)
  - downloading
    - automatically [3-18](#)
    - preparing [A-11, A-13, A-16](#)
    - reasons for [A-9](#)
    - using FTP [A-13](#)
    - using RCP [A-17](#)
    - using TFTP [A-11](#)
  - guidelines for creating and using [A-9](#)
  - guidelines for replacing and rolling back [A-21](#)
  - invalid combinations when copying [A-5](#)
  - limiting TFTP server access [30-16](#)
  - obtaining with DHCP [3-9](#)
  - password recovery disable considerations [9-5](#)
  - replacing a running configuration [A-19, A-20](#)
  - rolling back a running configuration [A-19, A-20](#)
  - specifying the filename [3-18](#)
  - system contact and location information [30-16](#)

- types and location [A-10](#)
  - uploading
    - preparing [A-11, A-13, A-16](#)
    - reasons for [A-9](#)
    - using FTP [A-15](#)
    - using RCP [A-18](#)
    - using TFTP [A-12](#)
  - configuration logger [29-11](#)
  - configuration logging [2-4](#)
  - configuration replacement [A-19](#)
  - configuration rollback [A-19, A-20](#)
  - configuration settings, saving [3-15](#)
  - configure terminal command [12-16](#)
  - configuring 802.1x user distribution [10-63](#)
  - configuring port-based authentication violation modes [10-44](#)
  - configuring small-frame arrival rate [23-5](#)
  - conflicts, configuration [38-12](#)
  - connections, secure remote [9-42](#)
  - connectivity problems [38-14, 38-15, 38-17](#)
  - consistency checks in VTP Version 2 [14-5](#)
  - console port, connecting to [2-10](#)
  - control protocol, IP SLAs [32-4](#)
  - corrupted software, recovery steps with Xmodem [38-2](#)
  - CoS
    - in Layer 2 frames [33-2](#)
    - override priority [15-6](#)
    - trust priority [15-6](#)
  - CoS input queue threshold map for QoS [33-16](#)
  - CoS output queue threshold map for QoS [33-19](#)
  - CoS-to-DSCP map for QoS [33-61](#)
  - counters, clearing interface [12-38](#)
  - CPU utilization, troubleshooting [38-28](#)
  - crashinfo file [38-23](#)
  - critical authentication, IEEE 802.1x [10-60](#)
  - critical VLAN [10-26](#)
  - critical voice VLAN
    - configuring [10-60](#)
  - cross-stack EtherChannel
    - configuration guidelines [37-13](#)
    - described [37-3](#)
    - illustration [37-4](#)
    - support for [1-8](#)
  - cross-stack UplinkFast, STP
    - described [18-5](#)
    - disabling [18-17](#)
    - enabling [18-17](#)
    - fast-convergence events [18-7](#)
    - Fast Uplink Transition Protocol [18-6](#)
    - normal-convergence events [18-7](#)
    - support for [1-8](#)
  - cryptographic software image
    - SSH [9-41](#)
    - SSL [9-46](#)
    - switch stack considerations [7-14](#)
  - customizable web pages, web-based authentication [11-6](#)
  - CWDM SFPs [1-23](#)
- 
- ## D
- DAACL
    - See downloadable ACL
  - daylight saving time [5-14](#)
  - debugging
    - enabling all system diagnostics [38-21](#)
    - enabling for a specific feature [38-20](#)
    - redirecting error message output [38-21](#)
    - using commands [38-20](#)
  - default commands [2-4](#)
  - default configuration
    - 802.1x [10-37](#)
    - auto-QoS [33-22](#)
    - banners [5-18](#)
    - booting [3-18](#)
    - CDP [25-2](#)
    - DHCP [20-9](#)
    - DHCP option 82 [20-9](#)
    - DHCP snooping [20-9](#)

- DHCP snooping binding database [20-9](#)
- DNS [5-17](#)
- dynamic ARP inspection [21-5](#)
- EtherChannel [37-11](#)
- Ethernet interfaces [12-23](#)
- Flex Links [19-8](#)
- IGMP filtering [22-24](#)
- IGMP snooping [22-7, 36-6](#)
- IGMP throttling [22-24](#)
- initial switch information [3-3](#)
- IP SLAs [32-5](#)
- IP source guard [20-16](#)
- IPv6 [35-6](#)
- Layer 2 interfaces [12-23](#)
- LLDP [26-5](#)
- MAC address table [5-22](#)
- MAC address-table move update [19-8](#)
- MSTP [17-16](#)
- MVR [22-19](#)
- NTP [5-5](#)
- optional spanning-tree configuration [18-12](#)
- password and privilege level [9-2](#)
- RADIUS [9-27](#)
- RMON [28-3](#)
- RSPAN [27-11](#)
- SDM template [8-3](#)
- SNMP [30-6](#)
- SPAN [27-11](#)
- SSL [9-48](#)
- standard QoS [33-36](#)
- STP [16-13](#)
- switch stacks [7-17](#)
- system message logging [29-4](#)
- system name and prompt [5-16](#)
- TACACS+ [9-13](#)
- UDLD [24-4](#)
- VLAN, Layer 2 Ethernet interfaces [13-15](#)
- VLANs [13-7](#)
- VMPS [13-24](#)
- voice VLAN [15-3](#)
- VTP [14-9](#)
- default gateway [3-15](#)
- default web-based authentication configuration
  - 802.1X [11-9](#)
- deleting VLANs [13-9](#)
- denial-of-service attack [23-1](#)
- description command [12-34](#)
- designing your network, examples [1-18](#)
- destination addresses
  - in IPv4 ACLs [31-10](#)
- destination-IP address-based forwarding, EtherChannel [37-9](#)
- destination-MAC address forwarding, EtherChannel [37-9](#)
- detecting indirect link failures, STP [18-8](#)
- device [A-23](#)
- device discovery protocol [25-1, 26-1](#)
- device manager
  - benefits [1-2](#)
  - described [1-2, 1-5](#)
  - in-band management [1-7](#)
  - upgrading a switch [A-23](#)
- DHCP
  - enabling
    - relay agent [20-11](#)
- DHCP-based autoconfiguration
  - client request message exchange [3-4](#)
  - configuring
    - client side [3-3](#)
    - DNS [3-8](#)
    - relay device [3-8](#)
    - server side [3-6](#)
    - TFTP server [3-7](#)
  - example [3-10](#)
  - lease options
    - for IP address information [3-6](#)
    - for receiving the configuration file [3-6](#)
  - overview [3-3](#)



- relationship to BOOTP [3-4](#)
- relay support [1-6](#)
- support for [1-6](#)
- DHCP-based autoconfiguration and image update
  - configuring [3-11 to 3-14](#)
  - understanding [3-5 to 3-6](#)
- DHCP binding database
  - See DHCP snooping binding database
- DHCP binding table
  - See DHCP snooping binding database
- DHCP option 82
  - circuit ID suboption [20-5](#)
  - configuration guidelines [20-9](#)
  - default configuration [20-9](#)
  - displaying [20-14](#)
  - overview [20-4](#)
  - packet format, suboption
    - circuit ID [20-5](#)
    - remote ID [20-5](#)
  - remote ID suboption [20-5](#)
- DHCP server port-based address allocation
  - configuration guidelines [20-23](#)
  - default configuration [20-23](#)
  - described [20-22](#)
  - displaying [20-25](#)
  - enabling [20-23](#)
  - reserved addresses [20-23](#)
- DHCP server port-based address assignment
  - support for [1-6](#)
- DHCP snooping
  - accepting untrusted packets form edge switch [20-3, 20-11](#)
  - binding database
    - See DHCP snooping binding database
  - configuration guidelines [20-9](#)
  - default configuration [20-9](#)
  - displaying binding tables [20-14](#)
  - message exchange process [20-4](#)
  - option 82 data insertion [20-4](#)
  - trusted interface [20-3](#)
  - untrusted interface [20-3](#)
  - untrusted messages [20-3](#)
- DHCP snooping binding database
  - adding bindings [20-13](#)
  - binding entries, displaying [20-14](#)
  - binding file
    - format [20-8](#)
    - location [20-7](#)
  - bindings [20-7](#)
  - clearing agent statistics [20-13](#)
  - configuration guidelines [20-10](#)
  - configuring [20-13](#)
  - default configuration [20-9](#)
  - deleting
    - binding file [20-13](#)
    - bindings [20-13](#)
    - database agent [20-13](#)
  - described [20-7](#)
  - displaying [20-14](#)
  - displaying status and statistics [20-14](#)
  - enabling [20-13](#)
  - entry [20-7](#)
  - renewing database [20-13](#)
  - resetting
    - delay value [20-13](#)
    - timeout value [20-13](#)
- DHCP snooping binding table
  - See DHCP snooping binding database
- Differentiated Services architecture, QoS [33-2](#)
- Differentiated Services Code Point [33-2](#)
- directed unicast requests [1-6](#)
- directories
  - changing [A-4](#)
  - creating and removing [A-4](#)
  - displaying the working [A-4](#)
- discovery, clusters
  - See automatic discovery
- DNS

- and DHCP-based autoconfiguration [3-8](#)
  - default configuration [5-17](#)
  - displaying the configuration [5-18](#)
  - in IPv6 [35-3](#)
  - overview [5-16](#)
  - setting up [5-17](#)
  - support for [1-6](#)
- domain names
- DNS [5-16](#)
  - VTP [14-10](#)
- Domain Name System
- See DNS
- downloadable ACL [10-21, 10-23, 10-67](#)
- downloading
- configuration files
    - preparing [A-11, A-13, A-16](#)
    - reasons for [A-9](#)
    - using FTP [A-13](#)
    - using RCP [A-17](#)
    - using TFTP [A-11](#)
  - image files
    - deleting old image [A-27](#)
    - preparing [A-25, A-29, A-33](#)
    - reasons for [A-23](#)
    - using CMS [1-2](#)
    - using FTP [A-30](#)
    - using HTTP [1-2, A-23](#)
    - using RCP [A-34](#)
    - using TFTP [A-26](#)
    - using the device manager or Network Assistant [A-23](#)
- DRP
- support for [1-15](#)
- DSCP [1-13, 33-2](#)
- DSCP input queue threshold map for QoS [33-16](#)
- DSCP output queue threshold map for QoS [33-19](#)
- DSCP-to-CoS map for QoS [33-64](#)
- DSCP-to-DSCP-mutation map for QoS [33-65](#)
- DSCP transparency [33-44](#)
- DTP [1-9, 13-13](#)
- dual-action detection [37-6](#)
- dual IPv4 and IPv6 templates [35-4, 35-5](#)
- dual protocol stacks
  - IPv4 and IPv6 [35-4](#)
  - SDM templates supporting [35-5](#)
- dual-purpose uplinks
  - defined [12-4](#)
  - LEDs [12-5](#)
  - link selection [12-5, 12-25](#)
  - setting the type [12-25](#)
- dynamic access ports
  - characteristics [13-4](#)
  - configuring [13-25](#)
  - defined [12-3](#)
- dynamic addresses
- See addresses
- dynamic ARP inspection
  - ARP cache poisoning [21-1](#)
  - ARP requests, described [21-1](#)
  - ARP spoofing attack [21-1](#)
  - clearing
    - log buffer [21-16](#)
    - statistics [21-16](#)
  - configuration guidelines [21-6](#)
  - configuring
    - ACLs for non-DHCP environments [21-9](#)
    - in DHCP environments [21-7](#)
    - log buffer [21-13](#)
    - rate limit for incoming ARP packets [21-4, 21-11](#)
  - default configuration [21-5](#)
  - denial-of-service attacks, preventing [21-11](#)
  - described [21-1](#)
  - DHCP snooping binding database [21-2](#)
  - displaying
    - ARP ACLs [21-15](#)
    - configuration and operating state [21-15](#)
    - log buffer [21-16](#)
    - statistics [21-16](#)

- trust state and rate limit [21-15](#)
- error-disabled state for exceeding rate limit [21-4](#)
- function of [21-2](#)
- interface trust states [21-3](#)
- log buffer
  - clearing [21-16](#)
  - configuring [21-13](#)
  - displaying [21-16](#)
- logging of dropped packets, described [21-5](#)
- man-in-the middle attack, described [21-2](#)
- network security issues and interface trust states [21-3](#)
- priority of ARP ACLs and DHCP snooping entries [21-4](#)
- rate limiting of ARP packets
  - configuring [21-11](#)
  - described [21-4](#)
  - error-disabled state [21-4](#)
- statistics
  - clearing [21-16](#)
  - displaying [21-16](#)
- validation checks, performing [21-12](#)
- dynamic auto trunking mode [13-14](#)
- dynamic desirable trunking mode [13-14](#)
- Dynamic Host Configuration Protocol
  - See DHCP-based autoconfiguration
- dynamic port VLAN membership
  - described [13-23](#)
  - reconfirming [13-26](#)
  - troubleshooting [13-28](#)
  - types of connections [13-25](#)
- Dynamic Trunking Protocol
  - See DTP

---

## E

- editing features
  - enabling and disabling [2-6](#)
  - keystrokes used [2-7](#)
- wrapped lines [2-8](#)
- elections
  - See stack master
- ELIN location [26-3](#)
- enable password [9-3](#)
- enable secret password [9-3](#)
- encryption, CipherSuite [9-48](#)
- encryption for passwords [9-3](#)
- environment variables, function of [3-21](#)
- error-disabled state, BPDU [18-3](#)
- error messages during command entry [2-4](#)
- EtherChannel
  - automatic creation of [37-5, 37-7](#)
  - channel groups
    - binding physical and logical interfaces [37-4](#)
    - numbering of [37-4](#)
  - configuration guidelines [37-12](#)
  - configuring Layer 2 interfaces [37-13](#)
  - default configuration [37-11](#)
  - described [37-2](#)
  - displaying status [37-20](#)
  - forwarding methods [37-8, 37-15](#)
  - IEEE 802.3ad, described [37-7](#)
  - interaction
    - with STP [37-12](#)
    - with VLANs [37-13](#)
- LACP
  - described [37-7](#)
  - displaying status [37-20](#)
  - hot-standby ports [37-18](#)
  - interaction with other features [37-8](#)
  - modes [37-7](#)
  - port priority [37-19](#)
  - system priority [37-18](#)
- load balancing [37-8, 37-15](#)
- PAgP
  - aggregate-port learners [37-16](#)
  - compatibility with Catalyst 1900 [37-17](#)
  - described [37-5](#)

- displaying status [37-20](#)
  - interaction with other features [37-7](#)
  - interaction with virtual switches [37-6](#)
  - learn method and priority configuration [37-16](#)
  - modes [37-6](#)
  - support for [1-4](#)
  - with dual-action detection [37-6](#)
  - port-channel interfaces
    - described [37-4](#)
    - numbering of [37-4](#)
  - port groups [12-4](#)
  - stack changes, effects of [37-10](#)
  - support for [1-4](#)
  - EtherChannel guard
    - described [18-10](#)
    - disabling [18-18](#)
    - enabling [18-18](#)
  - Ethernet management port
    - active link [12-21](#)
    - and routing [12-21](#)
    - and TFTP [12-22](#)
    - configuring [12-22](#)
    - default setting [12-21](#)
    - described [12-21](#)
    - for network management [12-21](#)
    - specifying [12-22](#)
    - supported features [12-21](#)
    - unsupported features [12-22](#)
  - Ethernet management port, internal
    - and routing [12-21](#)
    - unsupported features [12-22](#)
  - Ethernet VLANs
    - adding [13-8](#)
    - defaults and ranges [13-7](#)
    - modifying [13-8](#)
  - EUI [35-3](#)
  - events, RMON [28-3](#)
  - examples
    - network configuration [1-18](#)
  - expedite queue for QoS [33-78](#)
  - Express Setup [1-2](#)
    - See also getting started guide
  - extended crashinfo file [38-23](#)
  - extended-range VLANs
    - configuration guidelines [13-11](#)
    - configuring [13-10](#)
    - creating [13-11](#)
    - defined [13-1](#)
  - extended system ID
    - MSTP [17-19](#)
    - STP [16-4, 16-16](#)
  - extended universal identifier
    - See EUI
  - Extensible Authentication Protocol over LAN [10-1](#)
- 
- F**
- fa0 interface [1-7](#)
  - Fa0 port
    - See Ethernet management port
  - failover support [1-8](#)
  - Fast Convergence [19-3](#)
  - fastethernet0 port
    - See Ethernet management port
  - Fast Uplink Transition Protocol [18-6](#)
  - features, incompatible [23-12](#)
  - fiber-optic, detecting unidirectional links [24-1](#)
  - files
    - basic crashinfo
      - description [38-23](#)
      - location [38-23](#)
    - copying [A-5](#)
    - crashinfo, description [38-23](#)
    - deleting [A-5](#)
    - displaying the contents of [A-8](#)
    - extended crashinfo
      - description [38-24](#)
      - location [38-24](#)

- tar
  - creating [A-6](#)
  - displaying the contents of [A-7](#)
  - extracting [A-7](#)
  - image file format [A-24](#)
- file system
  - displaying available file systems [A-2](#)
  - displaying file information [A-3](#)
  - local file system names [A-1](#)
  - network file system names [A-5](#)
  - setting the default [A-3](#)
- filtering
  - non-IP traffic [31-22](#)
  - show and more command output [2-9](#)
- filtering show and more command output [2-9](#)
- filters, IP
  - See ACLs, IP
- flash device, number of [A-1](#)
- flexible authentication ordering
  - configuring [10-70](#)
  - overview [10-33](#)
- Flex Link Multicast Fast Convergence [19-3](#)
- Flex Links
  - configuration guidelines [19-8](#)
  - configuring [19-9, 19-10](#)
  - configuring preferred VLAN [19-12](#)
  - configuring VLAN load balancing [19-11](#)
  - default configuration [19-8](#)
  - description [19-2](#)
  - link load balancing [19-3](#)
  - monitoring [19-14](#)
  - VLANs [19-3](#)
- flooded traffic, blocking [23-8](#)
- flow-based packet classification [1-13](#)
- flowcharts
  - QoS classification [33-7](#)
  - QoS egress queueing and scheduling [33-18](#)
  - QoS ingress queueing and scheduling [33-15](#)
  - QoS policing and marking [33-11](#)

- flowcontrol
  - configuring [12-29](#)
  - described [12-28](#)
- forward-delay time
  - MSTP [17-25](#)
  - STP [16-23](#)
- FTP
  - accessing MIB files [B-4](#)
  - configuration files
    - downloading [A-13](#)
    - overview [A-12](#)
    - preparing the server [A-13](#)
    - uploading [A-15](#)
  - image files
    - deleting old image [A-31](#)
    - downloading [A-30](#)
    - preparing the server [A-29](#)
    - uploading [A-32](#)

---

## G

- general query [19-5](#)
- Generating IGMP Reports [19-4](#)
- get-bulk-request operation [30-3](#)
- get-next-request operation [30-3, 30-4](#)
- get-request operation [30-3, 30-4](#)
- get-response operation [30-3](#)
- Gigabit modules
  - See SFPs
- global configuration mode [2-2](#)
- global leave, IGMP [22-13](#)
- guest VLAN and 802.1x [10-24](#)
- guide mode [1-2](#)
- GUIs
  - See device manager and Network Assistant

---

**H**

hello time

    MSTP [17-25](#)

    STP [16-22](#)

help, for the command line [2-3](#)

HFTM space [38-26](#)

history

    changing the buffer size [2-5](#)

    described [2-5](#)

    disabling [2-6](#)

    recalling commands [2-6](#)

history table, level and number of syslog messages [29-10](#)

host names, in clusters [6-13](#)

hosts, limit on dynamic ports [13-28](#)

HP OpenView [1-5](#)

HQATM space [38-26](#)

HSRP

    automatic cluster recovery [6-12](#)

    cluster standby group considerations [6-11](#)

    See also clusters, cluster standby group, and standby command switch

HTTP over SSL

    see HTTPS

HTTPS [9-46](#)

    configuring [9-50](#)

    self-signed certificate [9-47](#)

HTTP secure server [9-46](#)

Hulc Forwarding TCAM Manager

    See HFTM space

Hulc QoS/ACL TCAM Manager

    See HQATM space

---

**I**

ICMP

    IPv6 [35-3](#)

    time-exceeded messages [38-17](#)

    traceroute and [38-17](#)

ICMP ping

    executing [38-14](#)

    overview [38-14](#)

ICMPv6 [35-3](#)

IDS appliances

    and ingress RSPAN [27-21](#)

    and ingress SPAN [27-14](#)

IEEE 802.1D

    See STP

IEEE 802.1p [15-1](#)

IEEE 802.1Q

    and trunk ports [12-3](#)

    configuration limitations [13-14](#)

    encapsulation [13-13](#)

    native VLAN for untagged traffic [13-18](#)

IEEE 802.1s

    See MSTP

IEEE 802.1w

    See RSTP

IEEE 802.1x

    See port-based authentication

IEEE 802.3ad

    See EtherChannel

IEEE 802.3ad, PoE+ [1-15, 12-6](#)

IEEE 802.3af

    See PoE

IEEE 802.3x flow control [12-28](#)

ifIndex values, SNMP [30-5](#)

IFS [1-6](#)

IGMP

    configurable leave timer

        described [22-6](#)

        enabling [22-11](#)

    flooded multicast traffic

        controlling the length of time [22-12](#)

        disabling on an interface [22-13](#)

        global leave [22-13](#)

        query solicitation [22-13](#)

        recovering from flood mode [22-13](#)

- joining multicast group 22-3
- join messages 22-3
- leave processing, enabling 22-10, 36-9
- leaving multicast group 22-5
- queries 22-4
- report suppression
  - described 22-6
  - disabling 22-15, 36-11
- supported versions 22-3
- support for 1-4
- IGMP filtering
  - configuring 22-24
  - default configuration 22-24
  - described 22-23
  - monitoring 22-28
  - support for 1-4
- IGMP groups
  - configuring filtering 22-27
  - setting the maximum number 22-26
- IGMP Immediate Leave
  - configuration guidelines 22-11
  - described 22-5
  - enabling 22-10
- IGMP profile
  - applying 22-25
  - configuration mode 22-24
  - configuring 22-25
- IGMP snooping
  - and address aliasing 22-2
  - and stack changes 22-6
  - configuring 22-7
  - default configuration 22-7, 36-6
  - definition 22-2
  - enabling and disabling 22-7, 36-7
  - global configuration 22-7
  - Immediate Leave 22-5
  - in the switch stack 22-6
  - method 22-8
  - monitoring 22-16, 36-12
  - querier
    - configuration guidelines 22-14
    - configuring 22-14
    - supported versions 22-3
    - support for 1-4
    - VLAN configuration 22-8
- IGMP throttling
  - configuring 22-27
  - default configuration 22-24
  - described 22-24
  - displaying action 22-28
- Immediate Leave, IGMP 22-5
  - enabling 36-9
- inaccessible authentication bypass 10-26
  - support for multiauth ports 10-26
- initial configuration
  - defaults 1-16
  - Express Setup 1-2
- interface
  - number 12-16
  - range macros 12-19
- interface command 12-16 to ??, 12-16
- interface configuration mode 2-2
- interfaces
  - auto-MDIX, configuring 12-29
  - configuration guidelines
    - duplex and speed 12-26
  - configuring
    - procedure 12-16
  - counters, clearing 12-38
  - default configuration 12-23
  - described 12-34
  - descriptive name, adding 12-34
  - displaying information about 12-38
  - flow control 12-28
  - management 1-5
  - monitoring 12-37
  - naming 12-34
  - physical, identifying 12-15, 12-16

- range of [12-17](#)
- restarting [12-39](#)
- shutting down [12-39](#)
- speed and duplex, configuring [12-27](#)
- status [12-37](#)
- supported [12-15](#)
- types of [12-1](#)
- interfaces range macro command [12-19](#)
- interface types [12-16](#)
- Internet Protocol version 6
  - See IPv6
- inter-VLAN routing [34-1](#)
- Intrusion Detection System
  - See IDS appliances
- inventory management TLV [26-3, 26-7](#)
- IP ACLs
  - for QoS classification [33-8](#)
  - implicit deny [31-9, 31-12](#)
  - implicit masks [31-9](#)
  - named [31-13](#)
  - undefined [31-19](#)
- IP addresses
  - 128-bit [35-2](#)
  - candidate or member [6-4, 6-13](#)
  - classes of [34-4](#)
  - cluster access [6-2](#)
  - command switch [6-3, 6-11, 6-13](#)
  - discovering [5-31](#)
  - for IP routing [34-4](#)
  - IPv6 [35-2](#)
  - redundant clusters [6-11](#)
  - standby command switch [6-11, 6-13](#)
  - See also IP information
- ip igmp profile command [22-24](#)
- IP information
  - assigned
    - manually [3-15](#)
    - through DHCP-based autoconfiguration [3-3](#)
  - default configuration [3-3](#)
- IP phones
  - and QoS [15-1](#)
  - automatic classification and queuing [33-21](#)
  - configuring [15-4](#)
  - ensuring port security with QoS [33-43](#)
  - trusted boundary for QoS [33-43](#)
- IP Port Security for Static Hosts
  - on a Layer 2 access port [20-18](#)
- IP precedence [33-2](#)
- IP-precedence-to-DSCP map for QoS [33-62](#)
- IP protocols in ACLs [31-10](#)
- IP routing
  - disabling [34-4](#)
  - enabling [34-4](#)
- IP Service Level Agreements
  - See IP SLAs
- IP service levels, analyzing [32-1](#)
- IP SLAs
  - benefits [32-2](#)
  - configuration guidelines [32-5](#)
  - Control Protocol [32-4](#)
  - default configuration [32-5](#)
  - definition [32-1](#)
  - measuring network performance [32-3](#)
  - monitoring [32-6](#)
  - operation [32-3](#)
  - responder
    - described [32-4](#)
    - enabling [32-6](#)
  - response time [32-4](#)
  - SNMP support [32-2](#)
  - supported metrics [32-2](#)
- IP source guard
  - and 802.1x [20-17](#)
  - and DHCP snooping [20-14](#)
  - and EtherChannels [20-17](#)
  - and port security [20-17](#)
  - and private VLANs [20-17](#)
  - and routed ports [20-16](#)



- and TCAM entries [20-17](#)
- and trunk interfaces [20-16](#)
- and VRF [20-17](#)
- binding configuration
  - automatic [20-14](#)
  - manual [20-14](#)
- binding table [20-14](#)
- configuration guidelines [20-16](#)
- default configuration [20-16](#)
- described [20-14](#)
- disabling [20-18](#)
- displaying
  - active IP or MAC bindings [20-22](#)
  - bindings [20-22](#)
  - configuration [20-22](#)
- enabling [20-17, 20-18](#)
- filtering
  - source IP address [20-15](#)
  - source IP and MAC address [20-15](#)
- on provisioned switches [20-17](#)
- source IP address filtering [20-15](#)
- source IP and MAC address filtering [20-15](#)
- static bindings
  - adding [20-17, 20-18](#)
  - deleting [20-18](#)
- static hosts [20-18](#)

IP traceroute

- executing [38-18](#)
- overview [38-17](#)

IP unicast routing

- assigning IP addresses to Layer 3 interfaces [34-4](#)
- configuring static routes [34-5](#)
- disabling [34-4](#)
- enabling [34-4](#)
- inter-VLAN [34-1](#)
- IP addressing
  - classes [34-4](#)
  - configuring [34-4](#)
- steps to configure [34-3](#)

- subnet mask [34-4](#)
- with SVIs [34-3](#)

IPv4 ACLs

- applying to interfaces [31-18](#)
- extended, creating [31-9](#)
- named [31-13](#)
- standard, creating [31-8](#)

IPv4 and IPv6

- dual protocol stacks [35-4](#)

IPv6

- addresses [35-2](#)
- address formats [35-2](#)
- and switch stacks [35-6](#)
- applications [35-4](#)
- assigning address [35-7](#)
- autoconfiguration [35-4](#)
- configuring static routes [35-10](#)
- default configuration [35-6](#)
- defined [35-1](#)
- forwarding [35-7](#)
- ICMP [35-3](#)
- monitoring [35-11](#)
- neighbor discovery [35-3](#)
- SDM templates [36-1](#)
- stack master functions [35-6](#)
- Stateless Autoconfiguration [35-4](#)
- supported features [35-2](#)

---

## J

- join messages, IGMP [22-3](#)

---

## L

### LACP

- See EtherChannel

- Layer 2 frames, classification with CoS [33-2](#)

- Layer 2 interfaces, default configuration [12-23](#)

- Layer 2 traceroute
    - and ARP [38-16](#)
    - and CDP [38-16](#)
    - broadcast traffic [38-15](#)
    - described [38-15](#)
    - IP addresses and subnets [38-16](#)
    - MAC addresses and VLANs [38-16](#)
    - multicast traffic [38-16](#)
    - multiple devices on a port [38-16](#)
    - unicast traffic [38-15](#)
    - usage guidelines [38-16](#)
  - Layer 3 features [1-15](#)
  - Layer 3 interfaces
    - assigning IP addresses to [34-4](#)
    - assigning IPv6 addresses to [35-7](#)
    - changing from Layer 2 mode [34-4](#)
  - Layer 3 packets, classification methods [33-2](#)
  - LDAP [4-2](#)
  - Leaking IGMP Reports [19-4](#)
  - LEDs, switch
    - See hardware installation guide
  - lightweight directory access protocol
    - See LDAP
  - line configuration mode [2-2](#)
  - Link Aggregation Control Protocol
    - See EtherChannel
  - link failure, detecting unidirectional [17-8](#)
  - Link Layer Discovery Protocol
    - See CDP
  - link local unicast addresses [35-3](#)
  - link redundancy
    - See Flex Links
  - links, unidirectional [24-1](#)
  - link-state tracking
    - configuring [37-23](#)
    - described [37-20](#)
  - LLDP
    - configuring [26-5](#)
    - characteristics [26-6](#)
    - default configuration [26-5](#)
    - enabling [26-6](#)
    - monitoring and maintaining [26-11](#)
    - overview [26-1](#)
    - supported TLVs [26-2](#)
    - switch stack considerations [26-2](#)
    - transmission timer and holdtime, setting [26-6](#)
  - LLDP-MED
    - configuring
      - procedures [26-5](#)
      - TLVs [26-7](#)
    - monitoring and maintaining [26-11](#)
    - overview [26-1, 26-2](#)
    - supported TLVs [26-2](#)
  - LLDP Media Endpoint Discovery
    - See LLDP-MED
  - local SPAN [27-2](#)
  - location TLV [26-3, 26-7](#)
  - login authentication
    - with RADIUS [9-30](#)
    - with TACACS+ [9-14](#)
  - login banners [5-18](#)
  - log messages
    - See system message logging
  - Long-Reach Ethernet (LRE) technology [1-20](#)
  - loop guard
    - described [18-11](#)
    - enabling [18-19](#)
    - support for [1-9](#)
  - LRE profiles, considerations in switch clusters [6-16](#)
- 
- M**
  - MAB
    - See MAC authentication bypass
  - MAB inactivity timer
    - default setting [10-38](#)
    - range [10-40](#)
  - MAC/PHY configuration status TLV [26-2](#)

- MAC addresses
  - aging time [5-22](#)
  - and VLAN association [5-21](#)
  - building the address table [5-21](#)
  - default configuration [5-22](#)
  - disabling learning on a VLAN [5-30](#)
  - discovering [5-31](#)
  - displaying [5-30](#)
  - displaying in the IP source binding table [20-22](#)
  - dynamic
    - learning [5-21](#)
    - removing [5-23](#)
  - in ACLs [31-22](#)
  - static
    - adding [5-27](#)
    - allowing [5-29, 5-30](#)
    - characteristics of [5-27](#)
    - dropping [5-29](#)
    - removing [5-28](#)
- MAC address learning [1-6](#)
- MAC address learning, disabling on a VLAN [5-30](#)
- MAC address notification, support for [1-15](#)
- MAC address-table move update
  - configuration guidelines [19-8](#)
  - configuring [19-12](#)
  - default configuration [19-8](#)
  - description [19-6](#)
  - monitoring [19-14](#)
- MAC address-to-VLAN mapping [13-23](#)
- MAC authentication bypass [10-40](#)
  - configuring [10-63](#)
  - overview [10-18](#)
- MAC extended access lists
  - applying to Layer 2 interfaces [31-24](#)
  - configuring for QoS [33-50](#)
  - creating [31-22](#)
  - defined [31-22](#)
  - for QoS classification [33-5](#)
- magic packet [10-30](#)
- manageability features [1-6](#)
- management access
  - in-band
    - browser session [1-7](#)
    - CLI session [1-7](#)
    - device manager [1-7](#)
    - SNMP [1-7](#)
  - out-of-band console port connection [1-7](#)
- management address TLV [26-2](#)
- management options
  - CLI [2-1](#)
  - clustering [1-3](#)
  - CNS [4-1](#)
  - Network Assistant [1-2](#)
  - overview [1-5](#)
- management VLAN
  - considerations in switch clusters [6-8](#)
  - discovery through different management VLANs [6-8](#)
- mapping tables for QoS
  - configuring
    - CoS-to-DSCP [33-61](#)
    - DSCP [33-61](#)
    - DSCP-to-CoS [33-64](#)
    - DSCP-to-DSCP-mutation [33-65](#)
    - IP-precedence-to-DSCP [33-62](#)
    - policed-DSCP [33-63](#)
  - described [33-11](#)
- marking
  - action with aggregate policers [33-58](#)
  - described [33-4, 33-9](#)
- matching, IPv4 ACLs [31-7](#)
- maximum aging time
  - MSTP [17-26](#)
  - STP [16-23](#)
- maximum hop count, MSTP [17-26](#)
- maximum number of allowed devices, port-based authentication [10-40](#)
- MDA

- configuration guidelines [10-13 to 10-14](#)
- described [1-11, 10-13](#)
- exceptions with authentication process [10-6](#)
- membership mode, VLAN port [13-3](#)
- member switch
  - automatic discovery [6-5](#)
  - defined [6-2](#)
  - managing [6-16](#)
  - passwords [6-13](#)
  - recovering from lost connectivity [38-12](#)
  - requirements [6-4](#)
  - See also candidate switch, cluster standby group, and standby command switch
- memory consistency check errors
  - displaying [38-27](#)
  - example [38-27](#)
- memory consistency check routines [1-5, 38-26](#)
- memory consistency integrity [1-5, 38-26](#)
- messages, to users through banners [5-18](#)
- MIBs
  - accessing files with FTP [B-4](#)
  - location of files [B-4](#)
  - overview [30-1](#)
  - SNMP interaction with [30-4](#)
  - supported [B-1](#)
- mirroring traffic for analysis [27-1](#)
- mismatches, autonegotiation [38-12](#)
- module number [12-16](#)
- monitoring
  - access groups [31-25](#)
  - cables for unidirectional links [24-1](#)
  - CDP [25-5](#)
  - features [1-15](#)
  - Flex Links [19-14](#)
  - IGMP
    - filters [22-28](#)
    - snooping [22-16, 36-12](#)
  - interfaces [12-37](#)
  - IP SLAs operations [32-6](#)
  - IPv4 ACL configuration [31-25](#)
  - IPv6 [35-11](#)
  - MAC address-table move update [19-14](#)
  - multicast router interfaces [22-16, 36-12](#)
  - MVR [22-23](#)
  - network traffic for analysis with probe [27-2](#)
  - port
    - blocking [23-18](#)
    - protection [23-18](#)
  - SFP status [12-38, 38-14](#)
  - speed and duplex mode [12-28](#)
  - traffic flowing among switches [28-1](#)
  - traffic suppression [23-18](#)
  - VLANs [13-13](#)
  - VMPS [13-27](#)
  - VTP [14-18](#)
- mrouter Port [19-3](#)
- mrouter port [19-5](#)
- MSTP
  - boundary ports
    - configuration guidelines [17-17](#)
    - described [17-6](#)
  - BPDU filtering
    - described [18-3](#)
    - enabling [18-15](#)
  - BPDU guard
    - described [18-2](#)
    - enabling [18-14](#)
  - CIST, described [17-3](#)
  - CIST regional root [17-3](#)
  - CIST root [17-5](#)
  - configuration guidelines [17-16, 18-12](#)
  - configuring
    - forward-delay time [17-25](#)
    - hello time [17-25](#)
    - link type for rapid convergence [17-27](#)
    - maximum aging time [17-26](#)
    - maximum hop count [17-26](#)
    - MST region [17-17](#)

- neighbor type [17-27](#)
- path cost [17-23](#)
- port priority [17-21](#)
- root switch [17-19](#)
- secondary root switch [17-20](#)
- switch priority [17-24](#)
- CST
  - defined [17-3](#)
  - operations between regions [17-4](#)
- default configuration [17-16](#)
- default optional feature configuration [18-12](#)
- displaying status [17-28](#)
- enabling the mode [17-17](#)
- EtherChannel guard
  - described [18-10](#)
  - enabling [18-18](#)
- extended system ID
  - effects on root switch [17-19](#)
  - effects on secondary root switch [17-20](#)
  - unexpected behavior [17-19](#)
- IEEE 802.1s
  - implementation [17-7](#)
  - port role naming change [17-7](#)
  - terminology [17-5](#)
- instances supported [16-10](#)
- interface state, blocking to forwarding [18-2](#)
- interoperability and compatibility among modes [16-11](#)
- interoperability with IEEE 802.1D
  - described [17-9](#)
  - restarting migration process [17-28](#)
- IST
  - defined [17-3](#)
  - master [17-3](#)
  - operations within a region [17-3](#)
- loop guard
  - described [18-11](#)
  - enabling [18-19](#)
- mapping VLANs to MST instance [17-18](#)
- MST region
  - CIST [17-3](#)
  - configuring [17-17](#)
  - described [17-2](#)
  - hop-count mechanism [17-6](#)
  - IST [17-3](#)
  - supported spanning-tree instances [17-2](#)
- optional features supported [1-8](#)
- overview [17-2](#)
- Port Fast
  - described [18-2](#)
  - enabling [18-13](#)
- preventing root switch selection [18-10](#)
- root guard
  - described [18-10](#)
  - enabling [18-18](#)
- root switch
  - configuring [17-19](#)
  - effects of extended system ID [17-19](#)
  - unexpected behavior [17-19](#)
- shutdown Port Fast-enabled port [18-2](#)
- stack changes, effects of [17-9](#)
- status, displaying [17-28](#)
- multiauth
  - support for inaccessible authentication bypass [10-26](#)
- multiauth mode
  - See multiple-authentication mode
- multicast groups
  - Immediate Leave [22-5](#)
  - joining [22-3](#)
  - leaving [22-5](#)
  - static joins [22-10, 36-8](#)
- multicast router interfaces, monitoring [22-16, 36-12](#)
- multicast router ports, adding [22-9, 36-8](#)
- multicast storm [23-1](#)
- multicast storm-control command [23-4](#)
- multicast television application [22-18](#)
- multicast VLAN [22-17](#)
- Multicast VLAN Registration

See MVR  
 multidomain authentication

See MDA

multiple authentication [10-15](#)  
 multiple authentication mode  
   configuring [10-48](#)

MVR  
   and address aliasing [22-20](#)  
   and IGMPv3 [22-20](#)  
   configuration guidelines [22-20](#)  
   configuring interfaces [22-21](#)  
   default configuration [22-19](#)  
   described [22-17](#)  
   example application [22-18](#)  
   modes [22-21](#)  
   monitoring [22-23](#)  
   multicast television application [22-18](#)  
   setting global parameters [22-20](#)  
   support for [1-4](#)

## N

### NAC

critical authentication [10-26, 10-60](#)  
 IEEE 802.1x authentication using a RADIUS server [10-65](#)  
 IEEE 802.1x validation using RADIUS server [10-65](#)  
 inaccessible authentication bypass [10-60](#)  
 Layer 2 IEEE 802.1x validation [1-12, 10-32, 10-65](#)

named IPv4 ACLs [31-13](#)

NameSpace Mapper

See NSM

native VLAN

configuring [13-18](#)  
 default [13-18](#)

NEAT

configuring [10-66](#)  
 overview [10-34](#)

neighbor discovery, IPv6 [35-3](#)

Network Admission Control

See NAC

Network Assistant

benefits [1-2](#)  
 described [1-5](#)  
 downloading image files [1-2](#)  
 guide mode [1-2](#)  
 management options [1-2](#)  
 managing switch stacks [7-2, 7-14](#)  
 upgrading a switch [A-23](#)  
 wizards [1-2](#)

network configuration examples

increasing network performance [1-19](#)  
 long-distance, high-bandwidth transport [1-23](#)  
 providing network services [1-19](#)  
 server aggregation and Linux server cluster [1-21](#)  
 small to medium-sized network [1-22](#)

network design

performance [1-19](#)  
 services [1-19](#)

Network Edge Access Topology

See NEAT

network management

CDP [25-1](#)  
 RMON [28-1](#)  
 SNMP [30-1](#)

network performance, measuring with IP SLAs [32-3](#)

network policy TLV [26-2, 26-7](#)

Network Time Protocol

See NTP

no commands [2-4](#)

nonhierarchical policy maps

described [33-10](#)

non-IP traffic filtering [31-22](#)

nontrunking mode [13-14](#)

normal-range VLANs [13-4](#)

configuration guidelines [13-6](#)

configuring [13-4](#)

defined [13-1](#)

NSM [4-3](#)

NTP

associations

    authenticating [5-5](#)

    defined [5-3](#)

    enabling broadcast messages [5-7](#)

    peer [5-6](#)

    server [5-6](#)

default configuration [5-5](#)

displaying the configuration [5-12](#)

overview [5-3](#)

restricting access

    creating an access group [5-9](#)

    disabling NTP services per interface [5-11](#)

source IP address, configuring [5-11](#)

stratum [5-3](#)

support for [1-6](#)

synchronizing devices [5-6](#)

time

    services [5-3](#)

    synchronizing [5-3](#)

## O

OBFL

    configuring [38-25](#)

    described [38-24](#)

    displaying [38-26](#)

offline configuration for switch stacks [7-7](#)

off mode, VTP [14-4](#)

on-board failure logging

    See OBFL

online diagnostics

    overview [39-1](#)

    running tests [39-3](#)

    understanding [39-1](#)

openIx

    configuring [10-71](#)

openIx authentication

    overview [10-33](#)

optimizing system resources [8-1](#)

options, management [1-5](#)

out-of-profile markdown [1-14](#)

## P

packet modification, with QoS [33-20](#)

PAGP

    See EtherChannel

passwords

    default configuration [9-2](#)

    disabling recovery of [9-5](#)

    encrypting [9-3](#)

    for security [1-10](#)

    in clusters [6-13](#)

    overview [9-1](#)

    recovery of [38-3](#)

    setting

        enable [9-3](#)

        enable secret [9-3](#)

        Telnet [9-6](#)

        with usernames [9-7](#)

    VTP domain [14-10](#)

path cost

    MSTP [17-23](#)

    STP [16-20](#)

PC (passive command switch) [6-10](#)

performance, network design [1-19](#)

performance features [1-4](#)

persistent self-signed certificate [9-47](#)

per-user ACLs and Filter-Ids [10-9](#)

per-VLAN spanning-tree plus

    See PVST+

physical ports [12-2](#)

PIM-DVMRP, as snooping method [22-8](#)

ping

    character output description [38-15](#)

    executing [38-14](#)

- overview [38-14](#)
- PoE
  - auto mode [12-7](#)
  - CDP with power consumption, described [12-5](#)
  - CDP with power negotiation, described [12-5](#)
  - Cisco intelligent power management [12-5](#)
  - configuring [12-30](#)
  - cutoff power
    - determining [12-8](#)
  - cutoff-power
    - support for [12-8](#)
  - devices supported [12-5](#)
  - high-power devices operating in low-power mode [12-6](#)
  - IEEE power classification levels [12-6](#)
  - monitoring [12-8](#)
  - monitoring power [12-33](#)
  - policing power consumption [12-33](#)
  - policing power usage [12-8](#)
  - power budgeting [12-31](#)
  - power consumption [12-9, 12-31](#)
  - powered-device detection and initial power allocation [12-6](#)
  - power management modes [12-7](#)
  - power monitoring [12-8](#)
  - power negotiation extensions to CDP [12-5](#)
  - power sensing [12-8](#)
  - standards supported [12-5](#)
  - static mode [12-7](#)
  - total available power [12-10](#)
  - troubleshooting [38-13](#)
- PoE+ [1-15, 12-5, 12-6, 12-30](#)
- policed-DSCP map for QoS [33-63](#)
- policers
  - configuring
    - for each matched traffic class [33-53](#)
    - for more than one traffic class [33-58](#)
  - described [33-4](#)
  - displaying [33-79](#)
  - number of [33-39](#)
  - types of [33-10](#)
- policing
  - described [33-4](#)
  - token-bucket algorithm [33-10](#)
- policy maps for QoS
  - characteristics of [33-53](#)
  - described [33-8](#)
  - displaying [33-80](#)
  - nonhierarchical on physical ports
    - described [33-10](#)
- port ACLs
  - defined [31-2](#)
  - types of [31-3](#)
- Port Aggregation Protocol
  - See EtherChannel
- port-based authentication
  - accounting [10-17](#)
  - authentication server
    - defined [10-3, 11-2](#)
    - RADIUS server [10-3](#)
  - client, defined [10-3, 11-2](#)
  - configuration guidelines [10-38, 11-9](#)
  - configuring
    - 802.1x authentication [10-45](#)
    - guest VLAN [10-57](#)
    - host mode [10-48](#)
    - inaccessible authentication bypass [10-60](#)
    - manual re-authentication of a client [10-50](#)
    - periodic re-authentication [10-49](#)
    - quiet period [10-51](#)
    - RADIUS server [10-47, 11-13](#)
    - RADIUS server parameters on the switch [10-46, 11-11](#)
    - restricted VLAN [10-58](#)
    - switch-to-client frame-retransmission number [10-53, 10-54](#)
    - switch-to-client retransmission time [10-51](#)
    - violation modes [10-44](#)



- default configuration [10-37, 11-9](#)
- described [10-1](#)
- device roles [10-3, 11-2](#)
- displaying statistics [10-73, 11-17](#)
- downloadable ACLs and redirect URLs
  - configuring [10-67 to 10-69, ?? to 10-70](#)
  - overview [10-21 to 10-23](#)
- EAPOL-start frame [10-6](#)
- EAP-request/identity frame [10-6](#)
- EAP-response/identity frame [10-6](#)
- enabling
  - 802.1X authentication [11-11](#)
- encapsulation [10-3](#)
- flexible authentication ordering
  - configuring [10-70](#)
  - overview [10-33](#)
- guest VLAN
  - configuration guidelines [10-24, 10-25](#)
  - described [10-24](#)
- host mode [10-13](#)
- inaccessible authentication bypass
  - configuring [10-60](#)
  - described [10-26](#)
  - guidelines [10-39](#)
- initiation and message exchange [10-6](#)
- magic packet [10-30](#)
- maximum number of allowed devices per port [10-40](#)
- method lists [10-45](#)
- multiple authentication [10-15](#)
- per-user ACLs
  - configuration tasks [10-21](#)
  - described [10-20](#)
  - RADIUS server attributes [10-20](#)
- ports
  - authorization state and dot1x port-control command [10-11](#)
  - authorized and unauthorized [10-11](#)
  - voice VLAN [10-28](#)
- port security
  - and voice VLAN [10-29](#)
  - described [10-29](#)
  - interactions [10-29](#)
  - multiple-hosts mode [10-13](#)
- readiness check
  - configuring [10-40](#)
  - described [10-18, 10-40](#)
- resetting to default values [10-72](#)
- stack changes, effects of [10-12](#)
- statistics, displaying [10-73](#)
- switch
  - as proxy [10-3, 11-2](#)
  - RADIUS client [10-3](#)
- switch supplicant
  - configuring [10-66](#)
  - overview [10-34](#)
- user distribution
  - guidelines [10-32](#)
  - overview [10-31](#)
- VLAN assignment
  - AAA authorization [10-45](#)
  - characteristics [10-19](#)
  - configuration tasks [10-20](#)
  - described [10-19](#)
- voice aware 802.1x security
  - configuring [10-42](#)
  - described [10-33, 10-42](#)
- voice VLAN
  - described [10-28](#)
  - PVID [10-28](#)
  - VVID [10-28](#)
- wake-on-LAN, described [10-30](#)
- with ACLs and RADIUS Filter-Id attribute [10-35](#)
- port-based authentication methods, supported [10-8](#)
- port blocking [1-4, 23-7](#)
- port-channel
  - See EtherChannel
- port description TLV [26-2](#)
- Port Fast

- described [18-2](#)
- enabling [18-13](#)
- mode, spanning tree [13-24](#)
- support for [1-8](#)
- port membership modes, VLAN [13-3](#)
- port priority
  - MSTP [17-21](#)
  - STP [16-18](#)
- ports
  - access [12-3](#)
  - blocking [23-7](#)
  - dual-purpose uplink [12-4](#)
  - dynamic access [13-4](#)
  - protected [23-6](#)
  - secure [23-9](#)
  - static-access [13-3, 13-9](#)
  - switch [12-2](#)
  - trunks [13-3, 13-13](#)
  - VLAN assignments [13-9](#)
- port security
  - aging [23-16](#)
  - and QoS trusted boundary [33-43](#)
  - and stacking [23-18](#)
  - configuring [23-13](#)
  - default configuration [23-11](#)
  - described [23-8](#)
  - displaying [23-18](#)
  - on trunk ports [23-14](#)
  - sticky learning [23-9](#)
  - violations [23-10](#)
  - with other features [23-11](#)
- port-shutdown response, VMPS [13-23](#)
- port VLAN ID TLV [26-2](#)
- power management TLV [26-3, 26-7](#)
- Power over Ethernet
  - See PoE
- preemption, default configuration [19-8](#)
- preemption delay, default configuration [19-8](#)
- preferential treatment of traffic
  - See QoS
- preventing unauthorized access [9-1](#)
- primary links [19-2](#)
- priority
  - overriding CoS [15-6](#)
  - trusting CoS [15-6](#)
- private VLAN edge ports
  - See protected ports
- privileged EXEC mode [2-2](#)
- privilege levels
  - changing the default for lines [9-9](#)
  - command switch [6-17](#)
  - exiting [9-10](#)
  - logging into [9-10](#)
  - mapping on member switches [6-17](#)
  - overview [9-2, 9-8](#)
  - setting a command with [9-8](#)
- protected ports [1-10, 23-6](#)
- provisioned switches and IP source guard [20-17](#)
- provisioning new members for a switch stack [7-7](#)
- proxy reports [19-4](#)
- pruning, VTP
  - disabling
    - in VTP domain [14-16](#)
    - on a port [13-18](#)
  - enabling
    - in VTP domain [14-16](#)
    - on a port [13-18](#)
  - examples [14-7](#)
  - overview [14-6](#)
- pruning-eligible list
  - changing [13-18](#)
  - for VTP pruning [14-6](#)
  - VLANs [14-16](#)
- PVST+
  - described [16-10](#)
  - IEEE 802.1Q trunking interoperability [16-11](#)
  - instances supported [16-10](#)

## Q

### QoS

and MQC commands [33-1](#)

#### auto-QoS

- categorizing traffic [33-22](#)
- configuration and defaults display [33-35](#)
- configuration guidelines [33-32](#)
- described [33-21](#)
- disabling [33-34](#)
- displaying generated commands [33-34](#)
- displaying the initial configuration [33-35](#)
- effects on running configuration [33-32](#)
- list of generated commands [33-25](#)

basic model [33-4](#)

#### classification

- class maps, described [33-8](#)
- defined [33-4](#)
- DSCP transparency, described [33-44](#)
- flowchart [33-7](#)
- forwarding treatment [33-3](#)
- in frames and packets [33-3](#)
- IP ACLs, described [33-6, 33-8](#)
- MAC ACLs, described [33-5, 33-8](#)
- options for IP traffic [33-6](#)
- options for non-IP traffic [33-5](#)
- policy maps, described [33-8](#)
- trust DSCP, described [33-5](#)
- trusted CoS, described [33-5](#)
- trust IP precedence, described [33-5](#)

#### class maps

- configuring [33-51](#)
- displaying [33-79](#)

#### configuration guidelines

- auto-QoS [33-32](#)
- standard QoS [33-38](#)

#### configuring

- aggregate policers [33-58](#)
- auto-QoS [33-21](#)

default port CoS value [33-42](#)

DSCP maps [33-61](#)

DSCP transparency [33-44](#)

DSCP trust states bordering another domain [33-45](#)

egress queue characteristics [33-72](#)

ingress queue characteristics [33-67](#)

IP extended ACLs [33-49](#)

IP standard ACLs [33-48](#)

MAC ACLs [33-50](#)

port trust states within the domain [33-40](#)

trusted boundary [33-43](#)

default auto configuration [33-22](#)

default standard configuration [33-36](#)

displaying statistics [33-79](#)

DSCP transparency [33-44](#)

#### egress queues

- allocating buffer space [33-72](#)
- buffer allocation scheme, described [33-18](#)
- configuring shaped weights for SRR [33-76](#)
- configuring shared weights for SRR [33-77](#)
- described [33-4](#)
- displaying the threshold map [33-75](#)
- flowchart [33-18](#)
- mapping DSCP or CoS values [33-74](#)
- scheduling, described [33-4](#)
- setting WTD thresholds [33-72](#)
- WTD, described [33-19](#)

enabling globally [33-40](#)

#### flowcharts

- classification [33-7](#)
- egress queueing and scheduling [33-18](#)
- ingress queueing and scheduling [33-15](#)
- policing and marking [33-11](#)

implicit deny [33-8](#)

#### ingress queues

- allocating bandwidth [33-70](#)
- allocating buffer space [33-69](#)

- buffer and bandwidth allocation, described 33-16
  - configuring shared weights for SRR 33-70
  - configuring the priority queue 33-71
    - described 33-4
    - displaying the threshold map 33-68
  - flowchart 33-15
  - mapping DSCP or CoS values 33-67
  - priority queue, described 33-17
  - scheduling, described 33-4
  - setting WTD thresholds 33-67
  - WTD, described 33-16
  - IP phones
    - automatic classification and queuing 33-21
    - detection and trusted settings 33-21, 33-43
  - limiting bandwidth on egress interface 33-78
  - mapping tables
    - CoS-to-DSCP 33-61
    - displaying 33-80
    - DSCP-to-CoS 33-64
    - DSCP-to-DSCP-mutation 33-65
    - IP-precedence-to-DSCP 33-62
    - policed-DSCP 33-63
    - types of 33-11
  - marked-down actions 33-56
  - marking, described 33-4, 33-9
  - overview 33-2
  - packet modification 33-20
  - policers
    - configuring 33-56, 33-59
    - described 33-9
    - displaying 33-79
    - number of 33-39
    - types of 33-10
  - policies, attaching to an interface 33-9
  - policing
    - described 33-4, 33-9
    - token bucket algorithm 33-10
  - policy maps
    - characteristics of 33-53
    - displaying 33-80
    - nonhierarchical on physical ports 33-53
  - QoS label, defined 33-4
  - queues
    - configuring egress characteristics 33-72
    - configuring ingress characteristics 33-67
    - high priority (expedite) 33-20, 33-78
    - location of 33-12
    - SRR, described 33-14
    - WTD, described 33-13
  - rewrites 33-20
  - support for 1-13
  - trust states
    - bordering another domain 33-45
    - described 33-5
    - trusted device 33-43
    - within the domain 33-40
  - quality of service
    - See QoS
  - queries, IGMP 22-4
  - query solicitation, IGMP 22-13
- 
- ## R
- ### RADIUS
- attributes
    - vendor-proprietary 9-38
    - vendor-specific 9-36
  - configuring
    - accounting 9-35
    - authentication 9-30
    - authorization 9-34
    - communication, global 9-28, 9-36
    - communication, per-server 9-27, 9-28
    - multiple UDP ports 9-28
  - default configuration 9-27
  - defining AAA server groups 9-32
  - displaying the configuration 9-40

- identifying the server [9-27](#)
- in clusters [6-16](#)
- limiting the services to the user [9-34](#)
- method list, defined [9-27](#)
- operation of [9-20](#)
- overview [9-18](#)
- server load balancing [9-40](#)
- suggested network environments [9-19](#)
- support for [1-12](#)
- tracking services accessed by user [9-35](#)
- RADIUS Change of Authorization [9-20](#)
- range
  - macro [12-19](#)
  - of interfaces [12-17](#)
- rapid convergence [17-11](#)
- rapid per-VLAN spanning-tree plus
  - See rapid PVST+
- rapid PVST+
  - described [16-10](#)
  - IEEE 802.1Q trunking interoperability [16-11](#)
  - instances supported [16-10](#)
- Rapid Spanning Tree Protocol
  - See RSTP
- rcommand command [6-16](#)
- RCP
  - configuration files
    - downloading [A-17](#)
    - overview [A-15](#)
    - preparing the server [A-16](#)
    - uploading [A-18](#)
  - image files
    - deleting old image [A-36](#)
    - downloading [A-34](#)
    - preparing the server [A-33](#)
    - uploading [A-36](#)
- readiness check
  - port-based authentication
    - configuring [10-40](#)
    - described [10-18, 10-40](#)
- reconfirmation interval, VMPS, changing [13-26](#)
- reconfirming dynamic VLAN membership [13-26](#)
- recovery procedures [38-1](#)
- redirect URL [10-21, 10-22, 10-67](#)
- redundancy
  - EtherChannel [37-3](#)
  - STP
    - backbone [16-8](#)
    - multidrop backbone [18-5](#)
    - path cost [13-21](#)
    - port priority [13-19](#)
- redundant links and UplinkFast [18-16](#)
- reloading software [3-22](#)
- Remote Authentication Dial-In User Service
  - See RADIUS
- Remote Copy Protocol
  - See RCP
- Remote Network Monitoring
  - See RMON
- Remote SPAN
  - See RSPAN
- remote SPAN [27-3](#)
- report suppression, IGMP
  - described [22-6](#)
  - disabling [22-15, 36-11](#)
- resequencing ACL entries [31-13](#)
- reserved addresses in DHCP pools [20-23](#)
- resetting a UDLD-shutdown interface [24-6](#)
- responder, IP SLAs
  - described [32-4](#)
  - enabling [32-6](#)
- response time, measuring with IP SLAs [32-4](#)
- restricted VLAN
  - configuring [10-58](#)
  - described [10-25](#)
  - using with IEEE 802.1x [10-25](#)
- restricting access
  - NTP services [5-9](#)
  - overview [9-1](#)

- passwords and privilege levels [9-2](#)
- RADIUS [9-18](#)
- TACACS+ [9-10](#)
- retry count, VMPS, changing [13-27](#)
- RFC
  - 1112, IP multicast and IGMP [22-2](#)
  - 1157, SNMPv1 [30-2](#)
  - 1166, IP addresses [34-4](#)
  - 1305, NTP [5-3](#)
  - 1757, RMON [28-2](#)
  - 1901, SNMPv2C [30-2](#)
  - 1902 to 1907, SNMPv2 [30-2](#)
  - 2236, IP multicast and IGMP [22-2](#)
  - 2273-2275, SNMPv3 [30-2](#)
- RFC 5176 Compliance [9-21](#)
- RMON
  - default configuration [28-3](#)
  - displaying status [28-6](#)
  - enabling alarms and events [28-3](#)
  - groups supported [28-2](#)
  - overview [28-1](#)
  - statistics
    - collecting group Ethernet [28-5](#)
    - collecting group history [28-5](#)
  - support for [1-15](#)
- root guard
  - described [18-10](#)
  - enabling [18-18](#)
  - support for [1-8](#)
- root switch
  - MSTP [17-19](#)
  - STP [16-16](#)
- router ACLs
  - defined [31-2](#)
  - types of [31-4](#)
- RSPAN
  - and stack changes [27-10](#)
  - characteristics [27-9](#)
  - configuration guidelines [27-17](#)
  - default configuration [27-11](#)
  - defined [27-3](#)
  - destination ports [27-8](#)
  - displaying status [27-24](#)
  - in a switch stack [27-3](#)
  - interaction with other features [27-9](#)
  - monitored ports [27-6](#)
  - monitoring ports [27-8](#)
  - overview [1-15, 27-1](#)
  - received traffic [27-5](#)
  - sessions
    - creating [27-18](#)
    - defined [27-4](#)
    - limiting source traffic to specific VLANs [27-23](#)
    - specifying monitored ports [27-18](#)
    - with ingress traffic enabled [27-21](#)
  - source ports [27-6](#)
  - transmitted traffic [27-6](#)
  - VLAN-based [27-7](#)
- RSTP
  - active topology [17-10](#)
  - BPDU
    - format [17-13](#)
    - processing [17-14](#)
  - designated port, defined [17-10](#)
  - designated switch, defined [17-10](#)
  - interoperability with IEEE 802.1D
    - described [17-9](#)
    - restarting migration process [17-28](#)
    - topology changes [17-14](#)
  - overview [17-10](#)
  - port roles
    - described [17-10](#)
    - synchronized [17-12](#)
  - proposal-agreement handshake process [17-11](#)
  - rapid convergence
    - cross-stack rapid convergence [17-11](#)
    - described [17-11](#)
    - edge ports and Port Fast [17-11](#)

- point-to-point links [17-11, 17-27](#)
- root ports [17-11](#)
- root port, defined [17-10](#)
- See also MSTP
- running configuration
  - replacing [A-19, A-20](#)
  - rolling back [A-19, A-20](#)
- running configuration, saving [3-15](#)

---

## S

- SC (standby command switch) [6-10](#)
- scheduled reloads [3-22](#)
- SCP
  - and SSH [9-52](#)
  - configuring [9-53](#)
- SDM
  - templates
    - configuring [8-4](#)
    - number of [8-1](#)
- SDM template
  - configuration guidelines [8-3](#)
  - configuring [8-3](#)
  - types of [8-1](#)
- Secure Copy Protocol
- secure HTTP client
  - configuring [9-51](#)
  - displaying [9-52](#)
- secure HTTP server
  - configuring [9-50](#)
  - displaying [9-52](#)
- secure MAC addresses
  - and switch stacks [23-18](#)
  - deleting [23-15](#)
  - maximum number of [23-10](#)
  - types of [23-9](#)
- secure ports
  - and switch stacks [23-18](#)
- secure ports, configuring [23-9](#)
- secure remote connections [9-42](#)
- Secure Shell
  - See SSH
- Secure Socket Layer
  - See SSL
- security, port [23-8](#)
- security features [1-10](#)
- See SCP
- sequence numbers in log messages [29-8](#)
- server mode, VTP [14-3](#)
- service-provider network, MSTP and RSTP [17-1](#)
- set-request operation [30-4](#)
- setup program
  - failed command switch replacement [38-11](#)
  - replacing failed command switch [38-9](#)
- severity levels, defining in system messages [29-9](#)
- SFPs
  - monitoring status of [12-38, 38-14](#)
  - security and identification [38-13](#)
  - status, displaying [38-14](#)
- shaped round robin
  - See SRR
- show access-lists hw-summary command [31-19](#)
- show and more command output, filtering [2-9](#)
- show cdp traffic command [25-6](#)
- show cluster members command [6-16](#)
- show configuration command [12-34](#)
- show forward command [38-22](#)
- show interfaces command [12-28, 12-34](#)
- show interfaces switchport [19-4](#)
- show lldp traffic command [26-11](#)
- show platform forward command [38-22](#)
- show platform team command [38-26, 38-27](#)
- show running-config command
  - displaying ACLs [31-17, 31-18](#)
  - interface description in [12-34](#)
- shutdown command on interfaces [12-39](#)
- Simple Network Management Protocol
  - See SNMP

small form-factor pluggable modules

See SFPs

small-frame arrival rate, configuring [23-5](#)

SNAP [25-1](#)

SNMP

accessing MIB variables with [30-4](#)

agent

described [30-4](#)

disabling [30-7](#)

and IP SLAs [32-2](#)

authentication level [30-10](#)

community strings

configuring [30-8](#)

for cluster switches [30-4](#)

overview [30-4](#)

configuration examples [30-17](#)

default configuration [30-6](#)

engine ID [30-7](#)

groups [30-7, 30-9](#)

host [30-7](#)

ifIndex values [30-5](#)

in-band management [1-7](#)

in clusters [6-14](#)

informs

and trap keyword [30-12](#)

described [30-5](#)

differences from traps [30-5](#)

disabling [30-15](#)

enabling [30-15](#)

limiting access by TFTP servers [30-16](#)

limiting system log messages to NMS [29-10](#)

manager functions [1-5, 30-3](#)

managing clusters with [6-17](#)

MIBs

location of [B-4](#)

supported [B-1](#)

notifications [30-5](#)

overview [30-1, 30-4](#)

security levels [30-3](#)

setting CPU threshold notification [30-15](#)

status, displaying [30-18](#)

system contact and location [30-16](#)

trap manager, configuring [30-13](#)

traps

described [30-3, 30-5](#)

differences from informs [30-5](#)

disabling [30-15](#)

enabling [30-12](#)

enabling MAC address notification [5-23, 5-25, 5-26](#)

overview [30-1, 30-4](#)

types of [30-12](#)

users [30-7, 30-9](#)

versions supported [30-2](#)

SNMP and Syslog Over IPv6 [35-5](#)

SNMPv1 [30-2](#)

SNMPv2C [30-2](#)

SNMPv3 [30-2](#)

snooping, IGMP [22-2](#)

software compatibility

See stacks, switch

software images

location in flash [A-24](#)

recovery procedures [38-2](#)

scheduling reloads [3-23](#)

tar file format, described [A-24](#)

See also downloading and uploading

source addresses

in IPv4 ACLs [31-10](#)

source-and-destination-IP address based forwarding, EtherChannel [37-9](#)

source-and-destination MAC address forwarding, EtherChannel [37-9](#)

source-IP address based forwarding, EtherChannel [37-9](#)

source-MAC address forwarding, EtherChannel [37-8](#)

SPAN

and stack changes [27-10](#)

configuration guidelines [27-11](#)

default configuration [27-11](#)



- destination ports [27-8](#)
- displaying status [27-24](#)
- interaction with other features [27-9](#)
- monitored ports [27-6](#)
- monitoring ports [27-8](#)
- overview [1-15](#), [27-1](#)
- ports, restrictions [23-12](#)
- received traffic [27-5](#)
- sessions
  - configuring ingress forwarding [27-15](#), [27-22](#)
  - creating [27-12](#)
  - defined [27-4](#)
  - limiting source traffic to specific VLANs [27-16](#)
  - removing destination (monitoring) ports [27-13](#)
  - specifying monitored ports [27-12](#)
  - with ingress traffic enabled [27-14](#)
- source ports [27-6](#)
- transmitted traffic [27-6](#)
- VLAN-based [27-7](#)
- spanning tree and native VLANs [13-14](#)
- Spanning Tree Protocol
  - See STP
- SPAN traffic [27-5](#)
- SRR
  - configuring
    - shaped weights on egress queues [33-76](#)
    - shared weights on egress queues [33-77](#)
    - shared weights on ingress queues [33-70](#)
  - described [33-14](#)
  - shaped mode [33-14](#)
  - shared mode [33-14](#)
  - support for [1-14](#)
- SSH
  - configuring [9-43](#)
  - cryptographic software image [9-41](#)
  - described [1-7](#), [9-42](#)
  - encryption methods [9-42](#)
  - switch stack considerations [7-14](#)
  - user authentication methods, supported [9-42](#)
- SSL
  - configuration guidelines [9-49](#)
  - configuring a secure HTTP client [9-51](#)
  - configuring a secure HTTP server [9-50](#)
  - cryptographic software image [9-46](#)
  - described [9-46](#)
  - monitoring [9-52](#)
- stack, switch
  - MAC address of [7-6](#), [7-17](#)
- stack changes, effects on
  - 802.1x port-based authentication [10-12](#)
  - ACL configuration [31-6](#)
  - CDP [25-2](#)
  - cross-stack EtherChannel [37-13](#)
  - EtherChannel [37-10](#)
  - IGMP snooping [22-6](#)
  - IP routing [34-3](#)
  - MAC address tables [5-22](#)
  - MSTP [17-9](#)
  - MVR [22-17](#)
  - port security [23-18](#)
  - SDM template selection [8-2](#)
  - SNMP [30-1](#)
  - SPAN and RSPAN [27-10](#)
  - STP [16-12](#)
  - switch clusters [6-14](#)
  - system message log [29-2](#)
  - VLANs [13-6](#)
  - VTP [14-8](#)
- stack master
  - bridge ID (MAC address) [7-6](#)
  - defined [7-1](#)
  - election [7-5](#)
  - IPv6 [35-6](#)
  - See also stacks, switch
- stack member
  - accessing CLI of specific member [7-21](#)
  - configuring
    - member number [7-19](#)

- priority value [7-20](#)
- defined [7-1](#)
- displaying information of [7-22](#)
- number [7-6](#)
- priority value [7-7](#)
- provisioning a new member [7-20](#)
- replacing [7-13](#)
- See also stacks, switch
- stack member number [12-16](#)
- stack protocol version [7-9](#)
- stacks, switch
  - accessing CLI of specific member [7-21](#)
  - assigning information
    - member number [7-19](#)
    - priority value [7-20](#)
    - provisioning a new member [7-20](#)
  - auto-advise [7-11](#)
  - auto-copy [7-10](#)
  - auto-extract [7-10](#)
  - auto-upgrade [7-10](#)
  - bridge ID [7-6](#)
  - CDP considerations [25-2](#)
  - compatibility, software [7-9](#)
  - configuration file [7-13](#)
  - configuration scenarios [7-15](#)
  - copying an image file from one member to another [A-37](#)
  - default configuration [7-17](#)
  - description of [7-1](#)
  - displaying information of [7-22](#)
  - enabling persistent MAC address timer [7-17](#)
  - in clusters [6-14](#)
  - incompatible software and image upgrades [7-13](#), [A-37](#)
  - IPv6 on [35-6](#)
  - MAC address considerations [5-22](#)
  - management connectivity [7-14](#)
  - managing [7-1](#)
  - membership [7-3](#)
  - merged [7-3](#)
  - MSTP instances supported [16-10](#)
  - offline configuration
    - described [7-7](#)
    - effects of adding a provisioned switch [7-7](#)
    - effects of removing a provisioned switch [7-9](#)
    - effects of replacing a provisioned switch [7-9](#)
    - provisioned configuration, defined [7-7](#)
    - provisioned switch, defined [7-7](#)
    - provisioning a new member [7-20](#)
  - partitioned [7-3](#), [38-8](#)
  - provisioned switch
    - adding [7-7](#)
    - removing [7-9](#)
    - replacing [7-9](#)
  - replacing a failed member [7-13](#)
  - software compatibility [7-9](#)
  - software image version [7-9](#)
  - stack protocol version [7-9](#)
  - STP
    - bridge ID [16-3](#)
    - instances supported [16-10](#)
    - root port selection [16-3](#)
    - stack root switch election [16-3](#)
  - system messages
    - hostnames in the display [29-1](#)
    - remotely monitoring [29-2](#)
  - system prompt consideration [5-15](#)
  - system-wide configuration considerations [7-13](#)
  - upgrading [A-37](#)
  - version-mismatch (VM) mode
    - automatic upgrades with auto-upgrade [7-10](#)
    - examples [7-11](#)
    - manual upgrades with auto-advise [7-11](#)
    - upgrades with auto-extract [7-10](#)
  - version-mismatch mode
    - described [7-10](#)
  - See also stack master and stack member
- standby command switch

- configuring
- considerations [6-11](#)
- defined [6-2](#)
- priority [6-10](#)
- requirements [6-3](#)
- virtual IP address [6-11](#)
- See also cluster standby group and HSRP
- standby group, cluster
  - See cluster standby group and HSRP
- standby links [19-2](#)
- startup configuration
  - booting
    - manually [3-19](#)
    - specific image [3-20](#)
  - clearing [A-19](#)
  - configuration file
    - automatically downloading [3-18](#)
    - specifying the filename [3-18](#)
  - default boot configuration [3-18](#)
- static access ports
  - assigning to VLAN [13-9](#)
  - defined [12-3, 13-3](#)
- static addresses
  - See addresses
- static MAC addressing [1-10](#)
- static routes
  - configuring [34-5](#)
  - configuring for IPv6 [35-10](#)
- static VLAN membership [13-2](#)
- statistics
  - 802.1X [11-17](#)
  - 802.1x [10-73](#)
  - CDP [25-5](#)
  - interface [12-38](#)
  - LLDP [26-11](#)
  - LLDP-MED [26-11](#)
  - NMSP [26-11](#)
  - QoS ingress and egress [33-79](#)
  - RMON group Ethernet [28-5](#)
  - RMON group history [28-5](#)
  - SNMP input and output [30-18](#)
  - VTP [14-18](#)
- sticky learning [23-9](#)
- storm control
  - configuring [23-3](#)
  - described [23-1](#)
  - disabling [23-5](#)
  - displaying [23-18](#)
  - support for [1-4](#)
  - thresholds [23-2](#)
- STP
  - accelerating root port selection [18-4](#)
  - BackboneFast
    - described [18-7](#)
    - disabling [18-17](#)
    - enabling [18-17](#)
  - BPDU filtering
    - described [18-3](#)
    - disabling [18-15](#)
    - enabling [18-15](#)
  - BPDU guard
    - described [18-2](#)
    - disabling [18-14](#)
    - enabling [18-14](#)
  - BPDU message exchange [16-3](#)
  - configuration guidelines [16-13, 18-12](#)
  - configuring
    - forward-delay time [16-23](#)
    - hello time [16-22](#)
    - maximum aging time [16-23](#)
    - path cost [16-20](#)
    - port priority [16-18](#)
    - root switch [16-16](#)
    - secondary root switch [16-18](#)
    - spanning-tree mode [16-15](#)
    - switch priority [16-21](#)
    - transmit hold-count [16-24](#)
  - counters, clearing [16-24](#)

- cross-stack UplinkFast
  - described [18-5](#)
  - enabling [18-17](#)
- default configuration [16-13](#)
- default optional feature configuration [18-12](#)
- designated port, defined [16-4](#)
- designated switch, defined [16-4](#)
- detecting indirect link failures [18-8](#)
- disabling [16-16](#)
- displaying status [16-24](#)
- EtherChannel guard
  - described [18-10](#)
  - disabling [18-18](#)
  - enabling [18-18](#)
- extended system ID
  - effects on root switch [16-16](#)
  - effects on the secondary root switch [16-18](#)
  - overview [16-4](#)
  - unexpected behavior [16-16](#)
- features supported [1-8](#)
- IEEE 802.1D and bridge ID [16-4](#)
- IEEE 802.1D and multicast addresses [16-9](#)
- IEEE 802.1t and VLAN identifier [16-5](#)
- inferior BPDU [16-3](#)
- instances supported [16-10](#)
- interface state, blocking to forwarding [18-2](#)
- interface states
  - blocking [16-6](#)
  - disabled [16-7](#)
  - forwarding [16-6, 16-7](#)
  - learning [16-7](#)
  - listening [16-7](#)
  - overview [16-5](#)
- interoperability and compatibility among modes [16-11](#)
- limitations with IEEE 802.1Q trunks [16-11](#)
- load sharing
  - overview [13-19](#)
  - using path costs [13-21](#)
  - using port priorities [13-19](#)
- loop guard
  - described [18-11](#)
  - enabling [18-19](#)
- modes supported [16-10](#)
- multicast addresses, effect of [16-9](#)
- optional features supported [1-8](#)
- overview [16-2](#)
- path costs [13-21, 13-22](#)
- Port Fast
  - described [18-2](#)
  - enabling [18-13](#)
- port priorities [13-20](#)
- preventing root switch selection [18-10](#)
- protocols supported [16-10](#)
- redundant connectivity [16-8](#)
- root guard
  - described [18-10](#)
  - enabling [18-18](#)
- root port, defined [16-3](#)
- root port selection on a switch stack [16-3](#)
- root switch
  - configuring [16-16](#)
  - effects of extended system ID [16-4, 16-16](#)
  - election [16-3](#)
  - unexpected behavior [16-16](#)
- shutdown Port Fast-enabled port [18-2](#)
- stack changes, effects of [16-12](#)
- status, displaying [16-24](#)
- superior BPDU [16-3](#)
- timers, described [16-22](#)
- UplinkFast
  - described [18-3](#)
  - enabling [18-16](#)
- stratum, NTP [5-3](#)
- subnet mask [34-4](#)
- success response, VMPS [13-23](#)
- summer time [5-14](#)
- SunNet Manager [1-5](#)

- supported port-based authentication methods [10-8](#)
  - SVIs
    - and IP unicast routing [34-3](#)
    - and router ACLs [31-4](#)
    - connecting VLANs [12-10](#)
    - defined [12-4](#)
  - switch [35-2](#)
  - switch clustering technology [6-1](#)
    - See also clusters, switch
  - switch console port [1-7](#)
  - Switch Database Management
    - See SDM
  - Switched Port Analyzer
    - See SPAN
  - switched ports [12-2](#)
  - switchport backup interface [19-4, 19-5](#)
  - switchport block multicast command [23-8](#)
  - switchport block unicast command [23-8](#)
  - switchport protected command [23-7](#)
  - switch priority
    - MSTP [17-24](#)
    - STP [16-21](#)
  - switch software features [1-1](#)
  - switch virtual interface
    - See SVI
  - syslog
    - See system message logging
  - system capabilities TLV [26-2](#)
  - system clock
    - configuring
      - daylight saving time [5-14](#)
      - manually [5-12](#)
      - summer time [5-14](#)
      - time zones [5-13](#)
    - displaying the time and date [5-13](#)
    - overview [5-2](#)
    - See also NTP
  - system description TLV [26-2](#)
  - system message logging
    - default configuration [29-4](#)
    - defining error message severity levels [29-9](#)
    - disabling [29-4](#)
    - displaying the configuration [29-14](#)
    - enabling [29-5](#)
    - facility keywords, described [29-14](#)
    - level keywords, described [29-10](#)
    - limiting messages [29-10](#)
    - message format [29-2](#)
    - overview [29-1](#)
    - sequence numbers, enabling and disabling [29-8](#)
    - setting the display destination device [29-5](#)
    - stack changes, effects of [29-2](#)
    - synchronizing log messages [29-6](#)
    - syslog facility [1-15](#)
    - time stamps, enabling and disabling [29-8](#)
    - UNIX syslog servers
      - configuring the daemon [29-13](#)
      - configuring the logging facility [29-13](#)
      - facilities supported [29-14](#)
  - system name
    - default configuration [5-16](#)
    - default setting [5-16](#)
    - manual configuration [5-16](#)
    - See also DNS
  - system name TLV [26-2](#)
  - system prompt, default setting [5-15, 5-16](#)
  - system resources, optimizing [8-1](#)
- 
- ## T
- TACACS+
    - accounting, defined [9-11](#)
    - authentication, defined [9-11](#)
    - authorization, defined [9-11](#)
    - configuring
      - accounting [9-17](#)
      - authentication key [9-13](#)
      - authorization [9-16](#)

- login authentication [9-14](#)
  - default configuration [9-13](#)
  - displaying the configuration [9-18](#)
  - identifying the server [9-13](#)
  - in clusters [6-16](#)
  - limiting the services to the user [9-16](#)
  - operation of [9-12](#)
  - overview [9-10](#)
  - support for [1-12](#)
  - tracking services accessed by user [9-17](#)
- tar files
- creating [A-6](#)
  - displaying the contents of [A-7](#)
  - extracting [A-7](#)
  - image file format [A-24](#)
- TCAM
- memory consistency check errors
    - displaying [38-27](#)
    - example [38-27](#)
  - memory consistency check routines [1-5, 38-26](#)
  - memory consistency integrity [1-5, 38-26](#)
  - portions [38-27](#)
  - space
    - HFTM [38-26](#)
    - HQATM [38-26](#)
    - unassigned [38-26](#)
- TDR [1-16](#)
- Telnet
- accessing management interfaces [2-10](#)
  - number of connections [1-7](#)
  - setting a password [9-6](#)
- temporary self-signed certificate [9-47](#)
- Terminal Access Controller Access Control System Plus
- See TACACS+
- terminal lines, setting a password [9-6](#)
- ternary content addressable memory
- See TCAM
- TFTP
- configuration files
    - downloading [A-11](#)
    - preparing the server [A-11](#)
    - uploading [A-12](#)
  - configuration files in base directory [3-7](#)
  - configuring for autoconfiguration [3-7](#)
  - image files
    - deleting [A-27](#)
    - downloading [A-26](#)
    - preparing the server [A-25](#)
    - uploading [A-28](#)
  - limiting access by servers [30-16](#)
- TFTP server [1-6](#)
- threshold, traffic level [23-2](#)
- time
- See NTP and system clock
- Time Domain Reflector
- See TDR
- time-range command [31-15](#)
- time ranges in ACLs [31-15](#)
- time stamps in log messages [29-8](#)
- time zones [5-13](#)
- TLVs
- defined [26-2](#)
  - LLDP [26-2](#)
  - LLDP-MED [26-2](#)
- Token Ring VLANs
- support for [13-5](#)
  - VTP support [14-5](#)
- ToS [1-13](#)
- traceroute, Layer 2
- and ARP [38-16](#)
  - and CDP [38-16](#)
  - broadcast traffic [38-15](#)
  - described [38-15](#)
  - IP addresses and subnets [38-16](#)
  - MAC addresses and VLANs [38-16](#)
  - multicast traffic [38-16](#)
  - multiple devices on a port [38-16](#)
  - unicast traffic [38-15](#)

- usage guidelines [38-16](#)
  - traceroute command [38-18](#)
    - See also IP traceroute
  - traffic
    - blocking flooded [23-8](#)
    - fragmented [31-4](#)
    - unfragmented [31-4](#)
  - traffic policing [1-14](#)
  - traffic suppression [23-2](#)
  - transmit hold-count
    - see STP
  - transparent mode, VTP [14-4](#)
  - trap-door mechanism [3-2](#)
  - traps
    - configuring MAC address notification [5-23, 5-25, 5-26](#)
    - configuring managers [30-12](#)
    - defined [30-3](#)
    - enabling [5-23, 5-25, 5-26, 30-12](#)
    - notification types [30-12](#)
    - overview [30-1, 30-4](#)
  - troubleshooting
    - connectivity problems [38-14, 38-15, 38-17](#)
    - CPU utilization [38-28](#)
    - detecting unidirectional links [24-1](#)
    - displaying crash information [38-23](#)
    - setting packet forwarding [38-22](#)
    - SFP security and identification [38-13](#)
    - show forward command [38-22](#)
    - with CiscoWorks [30-4](#)
    - with debug commands [38-20](#)
    - with ping [38-14](#)
    - with system message logging [29-1](#)
    - with traceroute [38-17](#)
  - trunk failover
    - See link-state tracking
  - trunking encapsulation [1-9](#)
  - trunk ports
    - configuring [13-16](#)
    - defined [12-3, 13-3](#)
  - trunks
    - allowed-VLAN list [13-17](#)
    - load sharing
      - setting STP path costs [13-21](#)
      - using STP port priorities [13-19, 13-20](#)
    - native VLAN for untagged traffic [13-18](#)
    - parallel [13-21](#)
    - pruning-eligible list [13-18](#)
    - to non-DTP device [13-13](#)
  - trusted boundary for QoS [33-43](#)
  - trusted port states
    - between QoS domains [33-45](#)
    - classification options [33-5](#)
    - ensuring port security for IP phones [33-43](#)
    - support for [1-13](#)
    - within a QoS domain [33-40](#)
  - trustpoints, CA [9-46](#)
  - twisted-pair Ethernet, detecting unidirectional links [24-1](#)
  - type of service
    - See ToS
- 
- ## U
- UDLD
    - configuration guidelines [24-4](#)
    - default configuration [24-4](#)
    - disabling
      - globally [24-5](#)
      - on fiber-optic interfaces [24-5](#)
      - per interface [24-6](#)
    - echoing detection mechanism [24-3](#)
    - enabling
      - globally [24-5](#)
      - per interface [24-6](#)
    - link-detection mechanism [24-1](#)
    - neighbor database [24-2](#)
    - overview [24-1](#)
    - resetting an interface [24-6](#)

- status, displaying [24-7](#)
  - support for [1-8](#)
  - unauthorized ports with IEEE 802.1x [10-11](#)
  - unicast MAC address filtering [1-6](#)
    - and adding static addresses [5-28](#)
    - and broadcast MAC addresses [5-28](#)
    - and CPU packets [5-28](#)
    - and multicast addresses [5-28](#)
    - and router MAC addresses [5-28](#)
    - configuration guidelines [5-28](#)
    - described [5-28](#)
  - unicast storm [23-1](#)
  - unicast storm control command [23-4](#)
  - unicast traffic, blocking [23-8](#)
  - UniDirectional Link Detection protocol
    - See UDLD
  - UNIX syslog servers
    - daemon configuration [29-13](#)
    - facilities supported [29-14](#)
    - message logging configuration [29-13](#)
  - unrecognized Type-Length-Value (TLV) support [14-5](#)
  - upgrading a Catalyst 2950 switch
    - configuration compatibility issues [D-1](#)
    - differences in configuration commands [D-1](#)
    - feature behavior incompatibilities [D-5](#)
    - incompatible command messages [D-1](#)
    - recommendations [D-1](#)
  - upgrading software images
    - See downloading
  - UplinkFast
    - described [18-3](#)
    - disabling [18-16](#)
    - enabling [18-16](#)
    - support for [1-8](#)
  - uploading
    - configuration files
      - preparing [A-11, A-13, A-16](#)
      - reasons for [A-9](#)
      - using FTP [A-15](#)
      - using RCP [A-18](#)
      - using TFTP [A-12](#)
    - image files
      - preparing [A-25, A-29, A-33](#)
      - reasons for [A-23](#)
      - using FTP [A-32](#)
      - using RCP [A-36](#)
      - using TFTP [A-28](#)
  - USB mini-Type B console port [12-11](#)
  - USB Type A port [1-8](#)
  - user EXEC mode [2-2](#)
  - username-based authentication [9-7](#)
- 
- ## V
- version-dependent transparent mode [14-5](#)
  - version-mismatch (VM) mode
    - automatic upgrades with auto-upgrade [7-10](#)
    - manual upgrades with auto-advise [7-11](#)
    - upgrades with auto-extract [7-10](#)
  - version-mismatch mode
    - described [7-10](#)
  - virtual IP address
    - cluster standby group [6-11](#)
    - command switch [6-11](#)
  - virtual switches and PAgP [37-6](#)
  - vlan.dat file [13-4](#)
  - VLAN 1, disabling on a trunk port [13-17](#)
  - VLAN 1 minimization [13-17](#)
  - vlan-assignment response, VMPS [13-23](#)
  - VLAN configuration
    - at bootup [13-7](#)
    - saving [13-7](#)
  - VLAN configuration mode [2-2](#)
  - VLAN database
    - and startup configuration file [13-7](#)
    - and VTP [14-1](#)
    - VLAN configuration saved in [13-7](#)
    - VLANs saved in [13-4](#)



- VLAN filtering and SPAN [27-7](#)
- vlan global configuration command [13-6](#)
- VLAN ID, discovering [5-31](#)
- VLAN load balancing on flex links [19-3](#)
  - configuration guidelines [19-8](#)
- VLAN management domain [14-2](#)
- VLAN Management Policy Server
  - See VMPS
- VLAN membership
  - confirming [13-26](#)
  - modes [13-3](#)
- VLAN Query Protocol
  - See VQP
- VLANs
  - adding [13-8](#)
  - adding to VLAN database [13-8](#)
  - aging dynamic addresses [16-9](#)
  - allowed on trunk [13-17](#)
  - and spanning-tree instances [13-3, 13-6, 13-11](#)
  - configuration guidelines, extended-range VLANs [13-11](#)
  - configuration guidelines, normal-range VLANs [13-6](#)
  - configuring [13-1](#)
  - configuring IDs 1006 to 4094 [13-11](#)
  - connecting through SVIs [12-10](#)
  - creating [13-8](#)
  - default configuration [13-7](#)
  - deleting [13-9](#)
  - described [12-2, 13-1](#)
  - displaying [13-13](#)
  - extended-range [13-1, 13-10](#)
  - features [1-9](#)
  - illustrated [13-2](#)
  - in the switch stack [13-6](#)
  - limiting source traffic with RSPAN [27-23](#)
  - limiting source traffic with SPAN [27-16](#)
  - modifying [13-8](#)
  - multicast [22-17](#)
  - native, configuring [13-18](#)
  - normal-range [13-1, 13-4](#)
  - number supported [1-9](#)
  - parameters [13-5](#)
  - port membership modes [13-3](#)
  - static-access ports [13-9](#)
  - STP and IEEE 802.1Q trunks [16-11](#)
  - supported [13-2](#)
  - Token Ring [13-5](#)
  - traffic between [13-2](#)
  - VTP modes [14-3](#)
- VLAN Trunking Protocol
  - See VTP
- VLAN trunks [13-13](#)
- VMPS
  - administering [13-27](#)
  - configuration example [13-28](#)
  - configuration guidelines [13-24](#)
  - default configuration [13-24](#)
  - description [13-22](#)
  - dynamic port membership
    - described [13-23](#)
    - reconfirming [13-26](#)
    - troubleshooting [13-28](#)
  - entering server address [13-25](#)
  - mapping MAC addresses to VLANs [13-23](#)
  - monitoring [13-27](#)
  - reconfirmation interval, changing [13-26](#)
  - reconfirming membership [13-26](#)
  - retry count, changing [13-27](#)
- voice aware 802.1x security
  - port-based authentication
    - configuring [10-42](#)
    - described [10-33, 10-42](#)
- voice-over-IP [15-1](#)
- voice VLAN
  - Cisco 7960 phone, port connections [15-1](#)
  - configuration guidelines [15-3](#)
  - configuring IP phones for data traffic
    - override CoS of incoming frame [15-6](#)

- trust CoS priority of incoming frame [15-6](#)
  - configuring ports for voice traffic in
    - 802.1p priority tagged frames [15-5](#)
    - 802.1Q frames [15-5](#)
  - connecting to an IP phone [15-4](#)
  - default configuration [15-3](#)
  - described [15-1](#)
  - displaying [15-7](#)
  - IP phone data traffic, described [15-2](#)
  - IP phone voice traffic, described [15-2](#)
  - VQP [1-9, 13-22](#)
  - VTP
    - adding a client to a domain [14-17](#)
    - advertisements [13-15, 14-4](#)
    - and extended-range VLANs [13-2, 14-2](#)
    - and normal-range VLANs [13-2, 14-2](#)
    - client mode, configuring [14-13](#)
    - configuration
      - guidelines [14-9](#)
      - requirements [14-11](#)
      - saving [14-9](#)
    - configuration requirements [14-11](#)
    - configuration revision number
      - guideline [14-17](#)
      - resetting [14-17](#)
    - consistency checks [14-5](#)
    - default configuration [14-9](#)
    - described [14-1](#)
    - domain names [14-10](#)
    - domains [14-2](#)
    - modes
      - client [14-3](#)
      - off [14-4](#)
      - server [14-3](#)
      - transitions [14-3](#)
      - transparent [14-4](#)
    - monitoring [14-18](#)
    - passwords [14-10](#)
    - pruning
      - disabling [14-16](#)
      - enabling [14-16](#)
      - examples [14-7](#)
      - overview [14-6](#)
      - support for [1-9](#)
    - pruning-eligible list, changing [13-18](#)
    - server mode, configuring [14-11, 14-14](#)
    - statistics [14-18](#)
    - support for [1-9](#)
    - Token Ring support [14-5](#)
    - transparent mode, configuring [14-12](#)
    - using [14-1](#)
    - Version
      - enabling [14-15](#)
    - version, guidelines [14-10](#)
    - Version 1 [14-5](#)
    - Version 2
      - configuration guidelines [14-10](#)
      - overview [14-5](#)
    - Version 3
      - overview [14-5](#)
- 
- W**
  - web authentication [10-18](#)
    - configuring [11-16 to ??](#)
    - described [1-10](#)
  - web-based authentication
    - customizeable web pages [11-6](#)
    - description [11-1](#)
  - web-based authentication, interactions with other features [11-7](#)
  - weighted tail drop
    - See WTD
  - wired location service
    - configuring [26-9](#)
    - displaying [26-11](#)
    - location TLV [26-3](#)
    - understanding [26-3](#)

wizards [1-2](#)

## WTD

described [33-13](#)

setting thresholds

    egress queue-sets [33-72](#)

    ingress queues [33-67](#)

support for [1-14](#)

---

## X

Xmodem protocol [38-2](#)

