



## INDEX

### ACLs

- applying IPv6 ACLs to a Layer 3 interface [43-16, 43-17](#)

## Numerics

---

- 10/100 autonegotiation feature, forced [7-13](#)
- 10-Gigabit Ethernet or Gigabit Ethernet ports
  - deploy on WS-X4606-10GE-E and Sup 6-E [7-7](#)
- 10-Gigabit Ethernet port
  - deploy with Gigabit Ethernet SFP ports [7-7](#)
- 1400 W DC Power supply
  - special considerations [11-17](#)
- 1400 W DC SP Triple Input power supply
  - special considerations [11-18](#)
- 802.10 SAID (default) [13-5](#)
- 802.1Q
  - trunks [17-6](#)
  - tunneling
    - compatibility with other features [23-5](#)
    - defaults [23-3](#)
    - described [23-2](#)
  - tunnel ports with other features [23-6](#)
- 802.1Q VLANs
  - encapsulation [15-3](#)
  - trunk restrictions [15-5](#)
- 802.1s
  - See MST
- 802.1w
  - See MST
- 802.1X
  - See port-based authentication
- 802.1X authentication
  - for Critical Authentication [37-13](#)
  - for guest VLANs [37-10](#)
  - for MAC Authentication Bypass [37-11](#)
  - for Wake-on-LAN [37-14](#)
  - web-based authentication [37-13](#)
  - with port security [37-17](#)
  - with VLAN assignment [37-9](#)
  - with voice VLAN ports [37-20](#)
- 802.1X Host Mode [37-6](#)
  - multiauthentication mode [37-8](#)
  - multidomain authentication mode [37-7](#)
  - single-host [37-7](#)
- 802.3ad
  - See LACP

## A

---

- AAA [40-1](#)
- AAA (authentication, authorization, and accounting). See also port-based authentication. [38-1](#)
- abbreviating commands [2-5](#)
- access control entries
  - See ACEs
- access control entries and lists [40-1](#)
- access-group mode, configuring on Layer 2 interface [43-31](#)
- access-group mode, using PACL with [43-30](#)
- access list filtering, SPAN enhancement [50-13](#)
- access ports
  - configure port security [39-7, 39-22](#)
  - configuring [15-8](#)
- access VLANs [15-6](#)
- accounting

- with TACACS+ [3-16, 3-21](#)
- ACEs
  - ACLs [43-2](#)
  - IP [43-2](#)
  - Layer 4 operation restrictions [43-9](#)
- ACEs and ACLs [40-1](#)
- ACL assignments, port-based authentication [37-18](#)
- ACL assignments and redirect URLs, configure [37-33](#)
- ACLs
  - ACEs [43-2](#)
  - and SPAN [50-5](#)
  - and TCAM programming for Sup II-Plus thru V-10GE [43-6](#)
  - applying on routed packets [43-27](#)
  - applying on switched packets [43-26](#)
  - compatibility on the same switch [43-3](#)
  - configuring with VLAN maps [43-25](#)
  - CPU impact [43-11](#)
  - downloadable [38-7](#)
  - hardware and software support [43-5](#)
  - IP, matching criteria for port ACLs [43-4](#)
  - MAC extended [43-13](#)
  - matching criteria for router ACLs [43-3](#)
  - port
    - and voice VLAN [43-4](#)
    - defined [43-3](#)
    - limitations [43-5](#)
  - processing [43-11](#)
  - selecting mode of capturing control packets [43-7](#)
  - troubleshooting high CPU [43-6](#)
  - types supported [43-3](#)
  - understanding [43-2](#)
  - VLAN maps [43-5](#)
- ACLs and VLAN maps, examples [43-20](#)
- acronyms, list of [A-1](#)
- action drivers, marking [34-20](#)
- active queue management [34-9](#)
- active queue management via DBL, QoS on Sup 6-E [34-33](#)
- active traffic monitoring, IP SLAs [48-1](#)
- adding members to a community [12-8](#)
- addresses
  - displaying the MAC address table [4-32](#)
  - dynamic
    - changing the aging time [4-23](#)
    - defined [4-21](#)
    - learning [4-21](#)
    - removing [4-24](#)
  - IPv6 [44-2](#)
  - MAC, discovering [4-32](#)
  - See MAC addresses
  - static
    - adding and removing [4-29](#)
    - defined [4-21](#)
- address resolution [4-32](#)
- adjacency tables
  - description [28-2](#)
  - displaying statistics [28-9](#)
- advertisements
  - LLDP [1-4, 24-2](#)
- advertisements, VTP
  - See VTP advertisements
- aggregation switch, enabling DHCP snooping [41-9](#)
- aging time
  - MAC address table [4-23](#)
- All Auth manager sessions, displaying summary [37-69](#)
- All Auth manager sessions on the switch authorized for a specified authentication method [37-69](#)
- applying IPv6 ACLs to a Layer 3 interface [43-16, 43-17](#)
- AQM via DBL, QoS on Sup 6-E [34-33](#)
- ARP
  - defined [4-32](#)
  - table
    - address resolution [4-32](#)
    - managing [4-32](#)
- asymmetrical links, and 802.1Q tunneling [23-3](#)
- authentication
  - NTP associations [4-4](#)

- See also port-based authentication
  - TACACS+
    - defined [3-16](#)
    - key [3-18](#)
    - login [3-19](#)
  - Authentication, Authorization, and Accounting (AAA) [40-1](#)
  - Authentication Failed VLAN assignment
    - configure with 802.1X [37-54](#)
  - Authentication methods registered with the Auth manager, determining [37-69](#)
  - authentication open comand [37-8](#)
  - authentication proxy web pages [38-4](#)
  - authentication server
    - defined [37-3](#)
    - RADIUS server [37-3](#)
  - Auth manager session for an interface, verifying [37-70](#)
  - Auth manager summary, displaying [37-69](#)
  - authoritative time source, described [4-2](#)
  - authorization
    - with TACACS+ [3-16](#), [3-21](#)
  - authorized and unauthorized ports [37-4](#)
  - authorized ports with 802.1X [37-4](#)
  - autoconfiguration [3-2](#)
  - automatic discovery
    - considerations [12-7](#)
  - Auto-MDIX on a port
    - configuring [7-23](#)
    - displaying the configuration [7-24](#)
    - overview [7-22](#)
  - autonegotiation feature
    - forced 10/100Mbps [7-13](#)
  - auto-sync command [5-8](#)
- 
- B**
- Baby Giants
    - interacting with [7-21](#)
  - BackboneFast
    - adding a switch (figure) [18-4](#)
    - and MST [17-23](#)
    - configuring [18-16](#)
    - link failure (figure) [18-14](#), [18-15](#)
    - not supported MST [17-23](#)
    - understanding [18-14](#)
    - See also STP
  - banners
    - configuring
      - login [4-20](#)
      - message-of-the-day login [4-18](#)
    - default configuration [4-18](#)
    - when displayed [4-17](#)
  - b command [56-3](#)
  - BGP [1-11](#)
    - routing session with multi-VRF CE [32-11](#)
  - blocking packets [45-1](#)
  - blocking state (STP)
    - RSTP comparisons (table) [17-24](#)
  - boot bootldr command [3-31](#)
  - boot command [3-28](#)
  - boot commands [56-3](#)
  - boot fields
    - See configuration register boot fields
  - boot system command [3-26](#), [3-31](#)
  - boot system flash command [3-28](#)
  - Border Gateway Protocol
    - See BGP
  - boundary ports
    - description [17-27](#)
  - BPDU Guard
    - and MST [17-23](#)
    - configuring [18-16](#)
    - overview [18-8](#)
  - BPDUs
    - and media speed [17-2](#)
    - pseudobridges and [17-25](#)
    - what they contain [17-3](#)
  - bridge ID

See STP bridge ID  
 bridge priority (STP) [17-16](#)  
 bridge protocol data units  
 See BPDUs  
 Broadcast Storm Control  
 disabling [49-5](#)  
 enabling [49-3](#)

## C

### Call Home

description [1-16, 54-1](#)  
 message format options [54-2](#)  
 messages  
 format options [54-2](#)

### call home [54-1](#)

alert groups [54-6](#)  
 configuring e-mail options [54-9](#)  
 contact information [54-4](#)  
 default settings [54-19](#)  
 destination profiles [54-5](#)  
 displaying information [54-14](#)  
 mail-server priority [54-10](#)  
 pattern matching [54-9](#)  
 periodic notification [54-8](#)  
 rate limit messages [54-9](#)  
 severity threshold [54-8](#)  
 smart call home feature [54-2](#)  
 SMTP server [54-9](#)  
 testing communications [54-11](#)

### call home alert groups

configuring [54-6](#)  
 description [54-6](#)  
 subscribing [54-7](#)

### call home contacts

assigning information [54-4](#)

### call home destination profiles

attributes [54-5](#)  
 configuring [54-5](#)

description [54-5](#)  
 displaying [54-17](#)  
 call home notifications  
 full-txt format for syslog [54-26](#)  
 XML format for syslog [54-35](#)

### candidates

automatic discovery [12-7](#)

### candidate switch, cluster

defined [12-12](#)  
 requirements [12-12](#)

### Capturing control packets

selecting mode [43-7](#)

### cautions

Unicast RPF  
 BGP optional attributes [29-5](#)

### cautions for passwords

encrypting [3-22](#)

### CDP

automatic discovery in communities [12-7](#)  
 configuration [20-2](#)  
 defined with LLDP [24-1](#)  
 displaying configuration [20-3](#)  
 enabling on interfaces [20-3](#)  
 host presence detection [37-8](#)  
 maintaining [20-3](#)  
 monitoring [20-3](#)  
 overview [1-2, 20-1](#)

### cdp enable command [20-3](#)

### CEF

adjacency tables [28-2](#)  
 and NSF with SSO [9-4](#)  
 configuring load balancing [28-7](#)  
 displaying statistics [28-8](#)  
 enabling [28-6, 55-2](#)  
 hardware switching [28-4](#)  
 load balancing [28-6](#)  
 overview [28-2](#)  
 software switching [28-4](#)

### certificate authority (CA) [54-3](#)

## CFM

- clearing [46-30](#)
- configuration guidelines [46-7, 47-4](#)
- configuring crosscheck for VLANs [46-10](#)
- configuring fault alarms [46-15](#)
- configuring port MEP [46-13](#)
- configuring static remote MEP [46-12, 46-13, 46-15, 46-17](#)
- crosscheck [46-5](#)
- defined [46-1](#)
- EtherChannel support [46-7, 47-4](#)
- fault alarms
  - configuring [46-15](#)
- IP SLAs support for [46-5](#)
- IP SLAs with endpoint discovers [46-20](#)
- maintenance domain [46-2](#)
- manually configuring IP SLAs ping or jitter [46-18](#)
- measuring network performance [46-5](#)
- monitoring [46-31, 46-32](#)
- port MEP, configuring [46-13](#)
- remote MEPs [46-5](#)
- static RMEP, configuring [46-12, 46-13, 46-15, 46-17](#)
- static RMEP check [46-5](#)
- Y.1731
  - described [46-26](#)

## CGMP

- overview [21-1](#)

channel-group group command [19-8, 19-10](#)

Cisco 7600 series Internet router

- enabling SNMP [57-4, 57-5](#)

Cisco Discovery Protocol

- See CDP

Cisco Express Forwarding

- See CEF

Cisco Group Management Protocol

- See CGMP

Cisco IOS IP SLAs [48-2](#)

Cisco IOS NSF-aware

- support [9-2](#)

Cisco IOS NSF-capable support [9-2](#)

Cisco IP Phones

- configuring [35-3](#)
- sound quality [35-1](#)

CiscoWorks 2000 [52-4](#)

CIST

- description [17-22](#)

civic location [24-3](#)

class level, configure in a service policy [34-30](#)

class of service

- See CoS

clear cdp counters command [20-4](#)

clear cdp table command [20-3](#)

clear counters command [7-26](#)

clearing

- Ethernet CFM [46-30](#)
- IP multicast table entries [30-26](#)

clear ip eigrp neighbors command [27-18](#)

CLI

- accessing [2-2](#)
- backing out one level [2-5](#)
- getting commands [2-5](#)
- history substitution [2-4](#)
- managing clusters [12-12](#)
- modes [2-5](#)
- monitoring environments [50-1](#)
- ROM monitor [2-7](#)
- software basics [2-4](#)

clients

- in 802.1X authentication [37-3](#)

clock

- See system clock

clustering switches

- command switch characteristics [12-11, 12-12](#)
- and VTY [12-11](#)
- convert to a community [12-9](#)
- managing
  - through CLI [12-12](#)
- overview [12-11](#)
- planning considerations

- CLI [12-12](#)
  - passwords [12-8](#)
- command-line processing [2-3](#)
- command modes [2-5](#)
- commands
  - b [56-3](#)
  - boot [56-3](#)
  - dev [56-3](#)
  - dir device [56-3](#)
  - i [56-3](#)
  - listing [2-5](#)
  - reset [56-3](#)
  - ROM monitor [56-2 to ??](#)
  - SNMP [57-4](#)
- command switch, cluster
  - requirements [12-11](#)
- common and internal spanning tree
  - See CIST
- common spanning tree
  - See CST
- community of switches
  - access modes in Network Assistant [12-8](#)
  - adding devices [12-8](#)
  - candidate characteristics [12-6](#)
  - communication protocols [12-8](#)
  - community name [12-7](#)
  - configuration information [12-8](#)
  - converting from a cluster [12-9](#)
  - host name [12-7](#)
  - passwords [12-8](#)
- community ports [36-3](#)
- community strings
  - configuring [52-7](#)
  - overview [52-4](#)
- community VLANs [36-2, 36-3](#)
  - and SPAN features [36-13](#)
  - configure as a PVLAN [36-15](#)
- compiling MIBs [57-4](#)
- config-register command [3-29](#)
- config terminal command [3-9](#)
- configurable leave timer,IGMP [21-4](#)
- configuration examples
  - SNMP [52-16](#)
- configuration files
  - limiting TFTP server access [52-15](#)
  - obtaining with DHCP [3-6](#)
  - saving [3-10](#)
  - system contact and location information [52-15](#)
- configuration guidelines
  - CFM [46-7, 47-4](#)
  - SNMP [52-6](#)
- configuration register
  - boot fields
    - listing value [3-29](#)
    - modifying [3-28](#)
  - changing from ROM monitor [56-3](#)
  - changing settings [3-28 to 3-29](#)
  - configuring [3-26](#)
  - settings at startup [3-27](#)
- configure class-level queue-limit in a service policy [34-30](#)
- configure terminal command [3-29, 7-2](#)
- configuring access-group mode on Layer 2 interface [43-31](#)
- configuring flow control [7-15](#)
- configuring interface link and trunk status events [7-27](#)
- configuring named IPv6 ACLs [43-15](#)
- configuring named MAC extended ACLs [43-13, 43-14](#)
- configuring unicast MAC address filtering [43-13](#)
- configuring VLAN maps [43-18](#)
- Connectivity Fault Management
  - See CFM
- console configuration mode [2-5](#)
- console port
  - disconnecting user sessions [8-7](#)
  - monitoring user sessions [8-6](#)
- contact information
  - assigning for call home [54-4](#)
- control plane policing

- See CoPP
  - control protocol, IP SLAs [48-4](#)
  - CoPP
    - applying QoS service policy to control plane [40-3](#)
    - configuring
      - ACLs to match traffic [40-3](#)
      - enabling MLS QoS [40-3](#)
      - packet classification criteria [40-3](#)
      - service-policy map [40-3](#)
    - control plane configuration mode
      - entering [40-3](#)
    - displaying
      - dynamic information [40-7](#)
      - number of conforming bytes and packets [40-7](#)
      - rate information [40-7](#)
    - entering control plane configuration mode [40-3](#)
    - monitoring statistics [40-7](#)
    - overview [40-2](#)
  - copy running-config startup-config command [3-10](#)
  - copy system:running-config nvram:startup-config command [3-31](#)
  - CoS
    - definition [34-3](#)
    - figure [34-2](#)
    - overriding on Cisco IP Phones [35-5](#)
    - priority [35-5](#)
  - counters
    - clearing MFIB [30-26](#)
    - clearing on interfaces [7-26](#)
  - CPU, impact of ACL processing [43-11](#)
  - CPU port sniffing [50-10](#)
  - crashinfo
    - kernel file [3-34](#)
    - process core dump file [3-34](#)
    - process file [3-33](#)
  - crashinfo, configuring
    - commands [3-35](#)
    - default [3-35](#)
    - determining the process that crashed [3-39](#)
    - enabling generation of process core dump [3-38](#)
    - saving files to a secondary device [3-39](#)
    - show commands [3-36](#)
  - Critical Authentication
    - configure with 802.1X [37-51](#)
  - crosscheck, CFM [46-5, 46-10](#)
  - CST
    - description [17-25](#)
    - IST and [17-22](#)
    - MST and [17-22](#)
  - customer edge devices [32-2](#)
- 
- ## D
- database agent
    - configuration examples [41-15](#)
    - enabling the DHCP Snooping [41-12](#)
  - daylight saving time [4-13](#)
  - default configuration
    - 802.1X [37-24](#)
    - banners [4-18](#)
    - DNS [4-16](#)
    - IGMP filtering [21-20](#)
    - IGMP snooping [22-5, 22-6](#)
    - IP SLAs [48-7](#)
    - IPv6 [44-7](#)
    - LLDP [24-3](#)
    - MAC address table [4-23](#)
    - multi-VRF CE [32-3](#)
    - NTP [4-4](#)
    - private VLANs [36-12](#)
    - resetting the interface [7-29](#)
    - RMON [53-3](#)
    - SNMP [52-5](#)
    - SPAN and RSPAN [50-6](#)
    - system message logging [51-3](#)
    - TACACS+ [3-18](#)
    - Y.1731 [46-28](#)
  - default gateway

- configuring [3-11](#)
  - verifying configuration [3-11](#)
- default settings, erase command [3-32](#)
- default web-based authentication configuration
  - 802.1X [38-6](#)
- denial-of-service attacks
  - IP address spoofing, mitigating [29-5](#)
  - Unicast RPF, deploying [29-5](#)
- denying access to a server on another VLAN [43-24](#)
- deploying 10-Gigabit Ethernet and a Gigabit Ethernet SFP ports [7-7](#)
- deploying 10-Gigabit Ethernet and a Gigabit Ethernet SFP ports on WS-X4606-10GE-E and Sup 6-E [7-7](#)
- description command [7-15](#)
- detecting unidirectional links [25-1](#)
- dev command [56-3](#)
- device discovery protocol [24-1](#)
- device IDs
  - call home format [54-22](#), [54-23](#)
- DHCP
  - configuring
    - rate limit for incoming packets [41-13](#)
  - denial-of-service attacks, preventing [41-13](#)
  - rate limiting of packets
    - configuring [41-13](#)
- DHCP-based autoconfiguration
  - client request message exchange [3-3](#)
  - configuring
    - client side [3-3](#)
    - DNS [3-5](#)
    - relay device [3-5](#)
    - server-side [3-4](#)
    - TFTP server [3-4](#)
  - example [3-7](#)
  - lease options
    - for IP address information [3-4](#)
    - for receiving the configuration file [3-4](#)
  - overview [3-2](#)
  - relationship to BOOTP [3-3](#)
- DHCP option 82
  - overview [41-3](#)
- DHCP Snooping
  - enabling, and Option 82 [41-10](#)
- DHCP snooping
  - accepting untrusted packets from edge switch [41-10](#)
  - configuring [41-6](#)
  - default configuration [41-7](#)
  - displaying binding tables [41-18](#)
  - displaying configuration [41-19](#)
  - displaying information [41-18](#)
  - enabling [41-7](#)
  - enabling on private VLAN [41-11](#)
  - enabling on the aggregation switch [41-9](#)
  - enabling the database agent [41-12](#)
  - message exchange process [41-4](#)
  - monitoring [41-23](#)
  - option 82 data insertion [41-3](#)
  - overview [41-1](#)
  - Snooping database agent [41-2](#)
- DHCP Snooping Database Agent
  - adding to the database (example) [41-18](#)
  - enabling (example) [41-15](#)
  - overview [41-2](#)
  - reading from a TFTP file (example) [41-16](#)
- Diagnostics
  - online [55-1](#)
    - troubleshooting [55-7](#)
  - Power-On-Self-Test
    - causes of failure [55-18](#)
    - how it works [55-9](#)
    - overview [55-9](#)
  - Power-On-Self-Test for Supervisor Engine V-10GE [55-12](#)
- Differentiated Services Code Point values
  - See DSCP values
- DiffServ architecture, QoS [34-2](#)
- Digital optical monitoring transceiver support [7-11](#)
- Digital Signing [56-6](#)



- dir device command [56-3](#)
  - disabled state
    - RSTP comparisons (table) [17-24](#)
  - disabling
    - broadcast storm control [49-5](#)
  - disabling multicast storm control [49-6](#)
  - disconnect command [8-7](#)
  - discovery, clusters
    - See automatic discovery
  - display dection and removal events [10-7](#)
  - displaying
    - Auth Manager summary for an interface [37-69](#)
    - MAB details [37-71](#)
    - summary of all Auth manager sessions [37-69](#)
    - summary of all Auth manager sessions on the switch authorized for a specified authentication method [37-69](#)
  - displaying EtherChannel to a Virtual Switch System [19-16](#)
  - displaying storm control [49-6](#)
  - display PoE consumed by a module [10-8](#)
  - display PoE detection and removal events [10-7](#)
  - DNS
    - and DHCP-based autoconfiguration [3-5](#)
    - default configuration [4-16](#)
    - displaying the configuration [4-17](#)
    - overview [4-15](#)
    - setting up [4-16](#)
  - domain names
    - DNS [4-15](#)
  - Domain Name System
    - See DNS
  - double-tagged packets
    - 802.1Q tunneling [23-2](#)
  - downloading MIBs [57-2, 57-3, 57-4](#)
  - DSCP values
    - definition [34-4](#)
    - IP precedence [34-2](#)
  - DTP
    - VLAN trunks and [15-3](#)
  - duplex command [7-14](#)
  - duplex mode
    - configuring interface [7-12](#)
  - dynamic ARP inspection
    - ARP cache poisoning [42-2](#)
    - configuring
      - ACLs for non-DHCP environments [42-11](#)
      - in DHCP environments [42-5](#)
      - log buffer [42-14](#)
      - rate limit for incoming ARP packets [42-16](#)
    - denial-of-service attacks, preventing [42-16](#)
    - interface trust state, security coverage [42-3](#)
    - log buffer
      - configuring [42-14](#)
    - logging of dropped packets [42-4](#)
    - overview [42-1](#)
    - port channels, their behavior [42-5](#)
    - priority of static bindings [42-4](#)
    - purpose of [42-2](#)
    - rate limiting of ARP packets [42-4](#)
      - configuring [42-16](#)
      - validation checks, performing [42-19](#)
  - Dynamic Host Configuration Protocol snooping
    - See DHCP snooping
  - dynamic port VLAN membership
    - example [13-29](#)
    - limit on hosts [13-29](#)
    - reconfirming [13-26](#)
    - troubleshooting [13-29](#)
  - Dynamic Trunking Protocol
    - See DTP
- 
- ## E
- EAP frames
    - changing retransmission time [37-65](#)
    - exchanging (figure) [37-4, 37-6, 37-12](#)
    - request/identity [37-3](#)
    - response/identity [37-3](#)

- setting retransmission number [37-66](#)
- EAPOL frames
  - 802.1X authentication and [37-3](#)
  - OTP authentication, example (figure) [37-4, 37-12](#)
  - start [37-4](#)
- edge ports
  - description [17-27](#)
- EGP
  - overview [1-11](#)
- EIGRP
  - configuration examples [27-18](#)
  - monitoring and maintaining [27-18](#)
- EIGRP (Enhanced IGRP)
  - stub routing
    - benefits [27-16](#)
    - configuration tasks [27-17](#)
    - configuring [27-13](#)
    - overview [27-13](#)
    - restrictions [27-17](#)
    - verifying [27-17](#)
- EIGRP (enhanced IGRP)
  - overview [1-11](#)
- eigrp stub command [27-17](#)
- EIGRP stub routing, configuring [27-12](#)
- ELIN location [24-3](#)
- e-mail addresses
  - assigning for call home [54-4](#)
- e-mail notifications
  - Call Home [1-16, 54-1](#)
- Embedded CiscoView
  - displaying information [4-35](#)
  - installing and configuring [4-33](#)
  - overview [4-33](#)
- emergency alarms on Sup Engine 6-E systems [11-3](#)
- enable command [3-9, 3-28](#)
- enable mode [2-5](#)
- enabling SNMP [57-4, 57-5](#)
- encapsulation types [15-3](#)
- Enhanced Interior Gateway Routing Protocol
  - See EIGRP
- Enhanced PoE support on E-series [10-15](#)
- Enhanced PoE support on E-series, configuring Universal PoE [10-16](#)
- environmental monitoring
  - using CLI commands [11-1](#)
- EPM logging [37-72](#)
- errdisable recovery
  - configuring [10-14](#)
- EtherChannel
  - channel-group group command [19-8, 19-10](#)
  - configuration guidelines [19-5](#)
  - configuring [19-6 to 19-15](#)
  - configuring Layer 2 [19-10](#)
  - configuring Layer 3 [19-6](#)
  - displaying to a virtual switch system [19-16](#)
  - interface port-channel command [19-7](#)
  - lACP system-priority
    - command example [19-13](#)
  - modes [19-3](#)
  - overview [19-1](#)
  - PAgP
    - Understanding [19-3](#)
  - physical interface configuration [19-7](#)
  - port-channel interfaces [19-2](#)
  - port-channel load-balance command [19-14](#)
  - removing [19-15](#)
  - removing interfaces [19-15](#)
- EtherChannel guard
  - disabling [18-7](#)
  - enabling [18-6](#)
  - overview [18-6](#)
- Ethernet Remote Defect Indication (ETH-RDI) [46-27](#)
- explicit host tracking
  - enabling [21-11](#)
- extended range VLANs
  - See VLANs
- Extensible Authentication Protocol over LAN [37-2](#)
- Exterior Gateway Protocol

See EGP

## F

### Fallback Authentication

configure with 802.1X [37-58](#)

### FastDrop

overview [30-10](#)

### FIB

description [28-2](#)

See also MFIB

### Filter-ID ACL and Per-User ACL, configureport-based authentication

configure Per-User ACL and Filter-ID ACL [37-39](#)

### filtering

in a VLAN [43-18](#)

non-IP traffic [43-13, 43-14](#)

flags [30-11](#)

### Flash memory

configuring router to boot from [3-31](#)

loading system images from [3-30](#)

security precautions [3-31](#)

### Flexible NetFlow

defined [1-2, 33-1](#)

items to consider [33-1](#)

flooded traffic, blocking [45-2](#)

flowchart, traffic marking procedure [34-20](#)

flow control, configuring [7-15](#)

FNF and supported fields, available options [33-4](#)

For [10-13](#)

forward-delay time (STP)

configuring [17-18](#)

forwarding information base

See FIB

## G

### gateway

See default gateway

get-bulk-request operation [52-3](#)

get-next-request operation [52-3, 52-4](#)

get-request operation [52-3, 52-4](#)

get-response operation [52-3](#)

### Gigabit Ethernet SFP ports

deploy with 10-Gigabit Ethernet [7-7](#)

global configuration mode [2-5](#)

### Guest-VLANs

configure with 802.1X [37-47, 37-56](#)

## H

hardware and software ACL support [43-5](#)

hardware switching [28-5](#)

hello time (STP)

configuring [17-17](#)

high CPU due to ACLs, troubleshooting [43-6](#)

### history

CLI [2-4](#)

history table, level and number of syslog messages [51-9](#)

### hop counts

configuring MST bridges [17-28](#)

### host

limit on dynamic port [13-29](#)

### host ports

kinds of [36-4](#)

host presence CDP message [37-8](#)

### Hot Standby Routing Protocol

See HSRP

### HSRP

description [1-9](#)

### http

[//www.cisco.com/en/US/docs/ios/12\\_4/ip\\_sla/configuration/guide/hsla\\_c.html](http://www.cisco.com/en/US/docs/ios/12_4/ip_sla/configuration/guide/hsla_c.html) [48-1, 48-4](#)

[//www.cisco.com/en/US/docs/ios/fundamentals/command/reference/cf\\_book.html](http://www.cisco.com/en/US/docs/ios/fundamentals/command/reference/cf_book.html) [51-1, 52-1, 53-1](#)

hw-module module num power command [11-18](#)

## I

## ICMP

- enabling [8-12](#)
- ping [8-8](#)
- running IP traceroute [8-9](#)
- time exceeded messages [8-9](#)

## ICMP Echo operation

- configuring [48-12](#)
- IP SLAs [48-11](#)

i command [56-3](#)

## IDS

- using with SPAN and RSPAN [50-3](#)

IEEE 802.1ag [46-1](#)

## IEEE 802.1s

- See MST

## IEEE 802.1w

- See MST

## IEEE 802.3ad

- See LACP

## IGMP

- configurable-leave timer [21-4](#)
- description [30-3](#)
- enabling [30-13](#)
- explicit host tracking [21-4](#)
- immediate-leave processing [21-3](#)
- leave processing, enabling [22-8](#)
- overview [21-1](#)
- report suppression
  - disabling [22-10](#)

## IGMP filtering

- configuring [21-21](#)
- default configuration [21-20](#)
- described [21-20](#)
- monitoring [21-24](#)

## IGMP groups

- setting the maximum number [21-23](#)

## IGMP Immediate Leave

- configuration guidelines [21-9](#)

## IGMP profile

- applying [21-22](#)
- configuration mode [21-21](#)
- configuring [21-21](#)

## IGMP Snooping

- configure
  - leave timer [21-9](#)
- configuring
  - Learning Methods [21-7](#)
  - static connection to a multicast router [21-8](#)
- configuring host statically [21-11](#)
- enabling
  - Immediate-Leave processing
  - explicit host tracking [21-11](#)
  - suppressing multicast flooding [21-12](#)

## IGMP snooping

- configuration guidelines [21-5](#)
- default configuration [22-5, 22-6](#)
- enabling
  - globally [21-6](#)
  - on a VLAN [21-6](#)
- enabling and disabling [22-6](#)
- IP multicast and [30-4](#)
- monitoring [21-14, 22-11](#)
- overview [21-1](#)

## IGMP Snooping, displaying

- group [21-16](#)
- hot membership [21-15](#)
- how to [21-15](#)
- MAC address entries [21-18](#)
- multicast router interfaces [21-17](#)
- on a VLAN interface [21-18](#)
- Querier information [21-19](#)

IGMPSnooping Querier, configuring [21-10](#)

## Immediate Leave, IGMP

- enabling [22-8](#)

## immediate-leave processing

- enabling [21-8](#)

## IGMP

- See fast-leave processing
- ingress packets, SPAN enhancement [50-12](#)
- inline power
  - configuring on Cisco IP phones [35-5](#)
- Intelligent Power Management [10-4](#)
- interacting with Baby Giants [7-21](#)
- interface
  - displaying operational status [10-6](#)
- interface command [3-9, 7-2](#)
- interface link and trunk status events
  - configuring [7-27](#)
- interface port-channel command [19-7](#)
- interface range command [7-5](#)
- interface range macro command [7-6](#)
- interfaces
  - adding descriptive name [7-15](#)
  - clearing counters [7-26](#)
  - configuring [7-2](#)
  - configuring ranges [7-4](#)
  - displaying information about [7-25](#)
  - Layer 2 modes [15-4](#)
  - maintaining [7-25](#)
  - monitoring [7-25](#)
  - naming [7-15](#)
  - numbers [7-2](#)
  - overview [7-2](#)
  - restarting [7-26, 7-27](#)
  - See also Layer 2 interfaces
- Internet Control Message Protocol
  - See ICMP
- Internet Group Management Protocol
  - See IGMP
- Internet Protocol version 6
  - See IPv6
- Inter-Switch Link encapsulation
  - See ISL encapsulation
- Intrusion Detection System
  - See IDS
- inventory management TLV [24-2, 24-7](#)
- IP
  - configuring default gateway [3-11](#)
  - configuring static routes [3-11](#)
  - displaying statistics [28-8](#)
- IP addresses
  - 128-bit [44-2](#)
  - cluster candidate or member [12-12](#)
  - cluster command switch [12-11](#)
  - discovering [4-32](#)
  - IPv6 [44-2](#)
- ip cef command [28-6, 55-2](#)
- IP Enhanced IGRP
  - interfaces, displaying [27-18](#)
- ip icmp rate-limit unreachable command [8-13](#)
- ip igmp profile command [21-21](#)
- ip igmp snooping ten flood command [21-13](#)
- ip igmp snooping ten flood query count command [21-14](#)
- ip igmp snooping ten query solicit command [21-14](#)
- IP information
  - assigned
    - through DHCP-based autoconfiguration [3-2](#)
- ip load-sharing per-destination command [28-7](#)
- ip local policy route-map command [31-8](#)
- ip mask-reply command [8-14](#)
- IP MTU sizes, configuring [27-8](#)
- IP MTU sizes, configuring [27-8](#)
- IP multicast
  - clearing table entries [30-26](#)
  - configuring [30-12](#)
  - default configuration [30-12](#)
  - displaying PIM information [30-21](#)
  - displaying the routing table information [30-22](#)
  - enabling dense-mode PIM [30-14](#)
  - enabling sparse-mode [30-14](#)
  - features not supported [30-12](#)
  - hardware forwarding [30-8](#)
  - IGMP snooping and [21-5, 30-4](#)
  - overview [30-1](#)
  - routing protocols [30-2](#)

- software forwarding [30-8](#)
- See also Auto-RP; IGMP; PIM; RP; RPF
- IP multicast routing
  - enabling [30-13](#)
  - monitoring and maintaining [30-21](#)
- ip multicast-routing command [30-13](#)
- IP phones
  - configuring voice ports [35-3](#)
  - See Cisco IP Phones [35-1](#)
- ip pim command [30-14](#)
- ip pim dense-mode command [30-14](#)
- ip pim sparse-dense-mode command [30-15](#)
- ip policy route-map command [31-7](#)
- ip redirects command [8-13](#)
- IP routing tables
  - deleting entries [30-26](#)
- IP Service Level Agreements
  - See IP SLAs
- IP service levels, analyzing [48-1](#)
- IP SLAs
  - benefits [48-3](#)
  - CFM endpoint discovery [46-20](#)
  - Control Protocol [48-4](#)
  - default configuration [48-7](#)
  - definition [48-1](#)
  - ICMP echo operation [48-11](#)
  - manually configuring CFM ping or jitter [46-18](#)
  - measuring network performance [48-3](#)
  - monitoring [48-13](#)
  - multioperations scheduling [48-6](#)
  - operation [48-4](#)
  - responder
    - described [48-4](#)
    - enabling [48-8](#)
  - response time [48-5](#)
  - scheduling [48-6](#)
  - SNMP support [48-3](#)
  - supported metrics [48-3](#)
  - threshold monitoring [48-6](#)
  - UDP jitter operation [48-9](#)
- IP Source Guard
  - configuring [41-20](#)
  - configuring on private VLANs [41-21](#)
  - displaying [41-22, 41-23](#)
  - overview [41-19](#)
- IP statistics
  - displaying [28-8](#)
- IP traceroute
  - executing [8-9](#)
  - overview [8-9](#)
- IP unicast
  - displaying statistics [28-8](#)
- IP Unnumbered support
  - configuring on a range of Ethernet VLANs [14-6](#)
  - configuring on LAN and VLAN interfaces [14-5](#)
  - configuring with connected host polling [14-7](#)
  - DHCP Option 82 [14-3](#)
  - displaying settings [14-8](#)
  - format of agent remote ID suboptions [14-3](#)
  - troubleshooting [14-9](#)
  - with connected host polling [14-4](#)
  - with DHCP server and Relay agent [14-2](#)
- ip unreachable command [8-12](#)
- IPv6
  - addresses [44-2](#)
  - default configuration [44-7](#)
  - defined [1-13, 44-1](#)
  - Enhanced Interior Gateway Routing Protocol (EIGRP) IPv6 [44-6](#)
    - Router ID [44-6](#)
  - OSPF [44-5](#)
- IPX
  - redistribution of route information with EIGRP [1-11](#)
- ISL
  - encapsulation [15-3](#)
  - trunking with 802.1Q tunneling [23-4](#)
- isolated port [36-4](#)
- isolated VLANs [36-2, 36-3, 36-4](#)

**I**

- ISSU
  - compatibility matrix [6-13](#)
  - compatibility verification using Cisco Feature Navigator [6-14](#)
  - NSF overview [6-3](#)
  - perform the process
    - aborting a software upgrade [6-31](#)
    - configuring the rollback timer as a safeguard [6-32](#)
    - displaying a compatibility matrix [6-34](#)
    - loading the new software on the new standby [6-24](#)
    - stopping the rollback timer [6-23](#)
    - switching to the standby [6-21](#)
    - verify the ISSU state [6-17](#)
    - verify the redundancy mode [6-16](#)
    - verify the software installation [6-15](#)
    - vload the new software on standby [6-18](#)
  - prerequisites [6-2](#)
  - process overview [6-6](#)
  - restrictions [6-2](#)
  - SNMP support [6-14](#)
  - SSO overview [6-3](#)

**IST**

- and MST regions [17-22](#)
- description [17-22](#)
- master [17-27](#)

**ITU-T Y.1731**

- See Y.1731

**J****jumbo frames**

- and ethernet ports [7-19](#)
- configuring MTU sizes for [7-20](#)
- ports and linecards that support [7-18](#)
- understanding MTUs [7-19](#)
- understanding support [7-18](#)
- VLAN interfaces [7-20](#)

**K**

- keyboard shortcuts [2-3](#)

**L**

- labels, definition [34-3](#)
- LACP
  - system ID [19-4](#)
- Layer 2 access ports [15-8](#)
- Layer 2 frames
  - classification with CoS [34-2](#)
- Layer 2 interface, configuring access-mode mode on [43-31](#)
- Layer 2 interfaces
  - assigning VLANs [13-7](#)
  - configuring [15-5](#)
  - configuring as PVLAN host ports [36-18](#)
  - configuring as PVLAN promiscuous ports [36-17](#)
  - configuring as PVLAN trunk ports [36-19](#)
  - defaults [15-5](#)
  - disabling configuration [15-9](#)
  - modes [15-4](#)
  - show interfaces command [15-7](#)
- Layer 2 interface type
  - resetting [36-23](#)
  - setting [36-23](#)
- Layer 2 switching
  - overview [15-1](#)
- Layer 2 Traceroute
  - and ARP [8-11](#)
  - and CDP [8-10](#)
  - host-to-host paths [8-10](#)
  - IP addresses and subnets [8-11](#)
  - MAC addresses and VLANs [8-10](#)
  - multicast traffic [8-10](#)
  - multiple devices on a port [8-11](#)
  - unicast traffic [1-25, 8-10](#)
  - usage guidelines [8-10](#)

- Layer 2 trunks
    - configuring [15-6](#)
    - overview [15-3](#)
  - Layer 3 interface, applying IPv6 ACLs [43-16, 43-17](#)
  - Layer 3 interface counters,configuring [27-10](#)
  - Layer 3 interface counters,understanding [27-3](#)
  - Layer 3 interfaces
    - changing from Layer 2 mode [32-7](#)
    - configuration guidelines [27-5](#)
    - overview [27-1](#)
      - logical [27-2](#)
      - physical [27-2](#)
    - VLANs as interfaces [27-7](#)
  - Layer 3 packets
    - classification methods [34-2](#)
  - Layer 4 port operations
    - configuration guidelines [43-10](#)
    - restrictions [43-9](#)
  - Leave timer, enabling [21-9](#)
  - link and trunk status events
    - configuring interface [7-27](#)
  - Link Layer Discovery Protocol
    - See CDP
  - listening state (STP)
    - RSTP comparisons (table) [17-24](#)
  - LLDP
    - configuring [24-3](#)
      - characteristics [24-4](#)
      - default configuration [24-3](#)
    - disabling and enabling
      - globally [24-5](#)
      - on an interface [24-6](#)
    - monitoring and maintaining [24-10](#)
    - overview [24-1](#)
    - transmission timer and holdtime, setting [24-4](#)
  - LLDP-MED
    - configuring
      - procedures [24-3](#)
      - TLVs [24-7, 24-8](#)
    - monitoring and maintaining [24-10](#)
    - overview [24-1](#)
    - supported TLVs [24-2](#)
  - load balancing
    - configuring for CEF [28-7](#)
    - configuring for EtherChannel [19-14](#)
    - overview [19-5, 28-6](#)
    - per-destination [28-7](#)
  - location service
    - configuring [24-9](#)
  - location TLV [24-3, 24-7](#)
  - logging, EPM [37-72](#)
  - Logical Layer 3 interfaces
    - configuring [27-6](#)
  - login authentication
    - with TACACS+ [3-19](#)
  - login banners [4-17](#)
  - login timer
    - changing [8-6](#)
  - logoutwarning command [8-6](#)
  - loop guard
    - and MST [17-23](#)
    - configuring [18-5](#)
    - overview [18-3](#)
- 
- ## M
- MAC/PHY configuration status TLV [24-2](#)
  - MAC addresses
    - aging time [4-23](#)
    - allocating [17-5](#)
    - and VLAN association [4-22](#)
    - building tables [4-21, 15-2](#)
    - convert dynamic to sticky secure [39-5](#)
    - default configuration [4-23](#)
    - discovering [4-32](#)
    - displaying [4-32, 8-3](#)
    - displaying in DHCP snooping binding table [41-19](#)
    - dynamic



- learning [4-21](#)
  - removing [4-24](#)
- in ACLs [43-13](#)
- static
  - adding [4-30](#)
  - allowing [4-31](#)
  - characteristics of [4-29](#)
  - dropping [4-31](#)
  - removing [4-30](#)
- sticky [39-4](#)
- sticky secure, adding [39-5](#)
- MAC Authentication Bypass
  - configure with 802.1X [37-49](#)
- MAC details, displaying [37-71](#)
- MAC extended access lists [43-13](#)
- macros
  - See Smartports macros
- main-cpu command [5-8](#)
- management address TLV [24-2](#)
- management options
  - SNMP [52-1](#)
- marking
  - hardware capabilities [34-22](#)
- marking action drivers [34-20](#)
- marking network traffic [34-17](#)
- marking support, multi-attribute [34-21](#)
- match ip address command [31-6](#)
- maximum aging time (STP)
  - configuring [17-18](#)
- MDA
  - configuration guidelines [37-21 to 37-22](#)
  - described [37-21](#)
- members
  - automatic discovery [12-7](#)
- member switch
  - managing [12-12](#)
- member switch, cluster
  - defined [12-11](#)
  - requirements [12-12](#)
- messages, to users through banners [4-17](#)
- metro tags [23-2](#)
- MFIB
  - CEF [30-5](#)
  - overview [30-11](#)
- MFIB, IP
  - displaying [30-24](#)
- MIBs
  - compiling [57-4](#)
  - downloading [57-2, 57-3, 57-4](#)
  - overview [52-1](#)
  - SNMP interaction with [52-4](#)
- MLD Done messages and Immediate-leave [22-4](#)
- MLD messages [22-2](#)
- MLD queries [22-3](#)
- MLD reports [22-4](#)
- MLD Snooping
  - MLD Done messages and Immediate-leave [22-4](#)
  - MLD messages [22-2](#)
  - MLD queries [22-3](#)
  - MLD reports [22-4](#)
  - Multicast client aging robustness [22-3](#)
  - Multicast router discovery [22-3](#)
  - overview [22-1](#)
- Mode of capturing control packets, selecting [43-7](#)
- modules
  - checking status [8-2](#)
- monitoring
  - 802.1Q tunneling [23-7](#)
  - ACL information [43-35](#)
  - Ethernet CFM [46-31, 46-32](#)
  - IGMP
    - snooping [22-11](#)
  - IGMP filters [21-24](#)
  - IGMP snooping [21-14](#)
  - IP SLAs operations [48-13](#)
  - Layer 2 protocol tunneling [23-7](#)
  - multicast router interfaces [22-11](#)
  - multi-VRF CE [32-16](#)

- traffic flowing among switches [53-1](#)
- tunneling [23-7](#)
- VLAN filters [43-25](#)
- VLAN maps [43-25](#)
- M-record [17-22](#)
- MST
  - and multiple spanning trees [1-5, 17-22](#)
  - boundary ports [17-27](#)
  - BPDUs [17-22](#)
  - configuration parameters [17-26](#)
  - configuring [17-29](#)
  - displaying configurations [17-33](#)
  - edge ports [17-27](#)
  - enabling [17-29](#)
  - hop count [17-28](#)
  - instances
    - configuring parameters [17-32](#)
    - description [17-22](#)
    - number supported [17-26](#)
  - interoperability with PVST+ [17-23](#)
  - link type [17-28](#)
  - master [17-27](#)
  - message age [17-28](#)
  - regions [17-26](#)
  - restrictions [17-29](#)
  - to-SST interoperability [17-24](#)
- MSTP
  - EtherChannel guard
    - enabling [18-6](#)
  - M-record [17-22](#)
  - M-tree [17-22](#)
- M-tree [17-22](#)
- MTUS
  - understanding [7-19](#)
- MTU size
  - configuring [7-20, 7-21, 7-28](#)
  - default [13-5](#)
- multiauthentication mode [37-8](#)
- multicast
  - See IP multicast
  - Multicast client aging robustness [22-3](#)
  - multicast Ethernet loopback (ETH-LB) [46-28](#)
  - multicast Ethernet loopback, using [46-30](#)
  - multicast groups
    - static joins [22-7](#)
  - multicast packets
    - blocking [45-2](#)
  - Multicast router discovery [22-3](#)
  - multicast router interfaces, displaying [21-17](#)
  - multicast router interfaces, monitoring [22-11](#)
  - multicast router ports, adding [22-7](#)
  - multicast routers
    - flood suppression [21-12](#)
  - multicast router table
    - displaying [30-22](#)
  - Multicast Storm Control
    - enabling [49-4](#)
    - disabling [49-6](#)
  - multidomain authentication
    - See MDA
  - multidomain authentication mode [37-7](#)
  - multioperations scheduling, IP SLAs [48-6](#)
  - Multiple Authentication
    - described [37-21](#)
  - Multiple AuthorizationAuthentication
    - configuring [37-30](#)
  - Multiple Domain Authentication [37-30](#)
  - multiple forwarding paths [1-5, 17-22](#)
  - multiple-hosts mode [37-7](#)
  - Multiple Spanning Tree
    - See MST
  - multiple VPN routing/forwarding
    - See multi-VRF CE
  - multi-VRF CE
    - components [32-3](#)
    - configuration example [32-12](#)
    - default configuration [32-3](#)

- defined [32-1](#)
- displaying [32-16](#)
- monitoring [32-16](#)
- network components [32-3](#)
- packet-forwarding process [32-3](#)

## N

named IPv6 ACLs, configuring

- ACLs
  - configuring named IPv6 ACLs [43-15](#)

named MAC extended ACLs

- ACLs
  - configuring named MAC extended [43-13, 43-14](#)

native VLAN

- and 802.1Q tunneling [23-4](#)
- specifying [15-6](#)

Network Assistant

- and VTY [12-11](#)
- configure
  - enable communication with switch [12-13, 12-17](#)
  - default configuration [12-2](#)
  - overview of CLI commands [12-2](#)

network fault tolerance [1-5, 17-22](#)

network management

- configuring [20-1](#)
- RMON [53-1](#)
- SNMP [52-1](#)

network performance, measuring with IP SLAs [48-3](#)

network policy TLV [24-2, 24-7](#)

Network Time Protocol

- See NTP

network traffic, marking [34-17](#)

New Software Features in Release 7.7

- TDR [8-3](#)

Next Hop Resolution Protocol

- See NHRP

NHRP

- support [1-12](#)

non-IP traffic filtering [43-13, 43-14](#)

non-RPF traffic

- description [30-9](#)
- in redundant configurations (figure) [30-10](#)

Nonstop Forwarding

- See NSF

nonvolatile random-access memory

- See NVRAM

normal-range VLANs

- See VLANs

NSF

- defined [9-1](#)
- guidelines and restrictions [9-7](#)
- operation [9-4](#)

NSF-aware

- support [9-2](#)

NSF-capable

- supervisor engines [9-2](#)
- support [9-2](#)

NSF with SSO supervisor engine redundancy

- and CEF [9-4](#)
- overview [9-3](#)
- SSO operation [9-3](#)

NTP

associations

- authenticating [4-4](#)
- defined [4-2](#)
- enabling broadcast messages [4-7](#)
- peer [4-6](#)
- server [4-6](#)

default configuration [4-4](#)

displaying the configuration [4-11](#)

overview [4-2](#)

restricting access

- creating an access group [4-9](#)
- disabling NTP services per interface [4-10](#)

source IP address, configuring [4-10](#)

stratum [4-2](#)

synchronizing devices [4-6](#)

- time
  - services [4-2](#)
  - synchronizing [4-2](#)

## NVRAM

- saving settings [3-10](#)

## O

### OIR

- overview [7-25](#)

Online Diagnostics [55-1](#)

online insertion and removal

- See OIR

Open Shortest Path First

- See OSPF

operating system images

- See system images

Option 82

- enabling DHCP Snooping [41-10](#)

### OSPF

- area concept [1-13](#)

- description [1-12](#)

- for IPv6 [44-5](#)

## P

Packet Length Map, packet length configured [33-3](#)

packets

- modifying [34-10](#)

packet type filtering

- overview [50-14](#)

- SPAN enhancement [50-14](#)

PACL, using with access-group mode [43-30](#)

PACL with VLAN maps and router ACLs [43-32](#)

PAgP

- understanding [19-3](#)

passwords

- configuring enable password [3-14](#)

- configuring enable secret password [3-14](#)

- encrypting [3-22](#)

- in clusters [12-8](#)

- recovering lost enable password [3-25](#)

- setting line password [3-14](#)

PBR (policy-based routing)

- configuration (example) [31-8](#)

- enabling [31-6](#)

- features [31-2](#)

- overview [31-1](#)

- route-map processing logic [31-3](#)

- route-map processing logic example [31-4](#)

- route maps [31-2](#)

- when to use [31-5](#)

per-port and VLAN Access Control List [41-19](#)

per-port per-VLAN QoS

- enabling [34-35](#)

- overview [34-10](#)

Per-User ACL and Filter-ID ACL, configure [37-39](#)

Per-VLAN Rapid Spanning Tree [17-6](#)

- enabling [17-20](#)

- overview [17-6](#)

PE to CE routing, configuring [32-11](#)

Physical Layer 3 interfaces, configuring [27-11](#)

PIM

- configuring dense mode [30-14](#)

- configuring sparse mode [30-14](#)

- displaying information [30-21](#)

- displaying statistics [30-25](#)

- enabling sparse-dense mode [30-14, 30-15](#)

- overview [30-3](#)

PIM-DM [30-3](#)

PIM on an interface, enabling [30-13](#)

PIM-SM [30-4](#)

PIM-SSM mapping, enabling [30-16](#)

ping

- executing [8-8](#)

- overview [8-8](#)

ping command [8-8, 30-21](#)

PoE [10-7, 10-8](#)

- configuring power consumption, powered devices [10-5](#)
- configuring power consumption for single device [10-5](#), [10-16](#)
- displaying operational status for an interface [10-6](#)
- Enhanced PoE support on E-series [10-15](#)
- policing and monitoring [10-12](#)
- power consumption for powered devices
  - Intelligent Power Management [10-4](#)
- power management modes [10-3](#)
- PoE policing
  - configuring errdisable recovery [10-14](#)
  - configuring on an interface [10-12](#)
  - displaying on an interface [10-14](#)
  - power modes [10-12](#)
- point-to-point
  - in 802.1X authentication (figure) [37-2](#)
- policing
  - how to implement [34-17](#)
  - See QoS policing
- policing, PoE [10-12](#)
- policy associations, QoS on Sup 6-E [34-38](#)
- policy-map command [34-15](#)
- policy map marking action, configuring [34-22](#)
- port ACLs
  - and voice VLAN [43-4](#)
  - defined [43-3](#)
  - limitations [43-5](#)
- Port Aggregation Protocol
  - see PAgP
- port-based authentication
  - 802.1X with voice VLAN [37-20](#)
  - authentication server
    - defined [38-2](#)
  - changing the quiet period [37-64](#)
  - client, defined [37-3](#), [38-2](#)
  - configuration guidelines [37-25](#), [38-6](#)
  - configure ACL assignments and redirect URLs [37-33](#)
  - configure switch-to-RADIUS server communication [37-28](#)
  - configure with Authentication Failed VLAN assignment [37-54](#)
  - configure with Critical Authentication [37-51](#)
  - configure with Guest-VLANs [37-47](#), [37-56](#)
  - configure with MAC Authentication Bypass [37-49](#)
  - configure with Wake-on-LAN [37-53](#)
  - configuring
    - Multiple Domain Authentication and Multiple Authorization [37-30](#)
    - RADIUS server [38-10](#)
    - RADIUS server parameters on the switch [38-9](#)
  - configuring Fallback Authentication [37-58](#)
  - configuring Guest-VLAN [37-28](#)
  - configuring manual re-authentication of a client [37-67](#)
  - controlling authorization state [37-5](#)
  - default configuration [37-24](#), [38-6](#)
  - described [37-1](#)
  - device roles [37-2](#), [38-2](#)
  - displaying statistics [37-68](#), [38-13](#)
  - enabling [37-25](#)
    - 802.1X authentication [38-9](#)
  - enabling multiple hosts [37-63](#)
  - enabling periodic re-authentication [37-62](#)
  - encapsulation [37-3](#)
  - host mode [37-6](#)
  - how 802.1X fails on a port [37-22](#)
  - initiation and message exchange [37-3](#)
  - method lists [37-25](#)
  - modes [37-6](#)
  - multidomain authentication [37-21](#)
  - multiple-hosts mode, described [37-7](#)
  - port security
    - multiple-hosts mode [37-7](#)
  - ports not supported [37-4](#)
  - pre-authentication open access [37-8](#)
  - resetting to default values [37-68](#)
  - setting retransmission number [37-66](#)
  - setting retransmission time [37-65](#)
  - switch

- as proxy [38-2](#)
  - topologies, supported [37-22](#)
  - using with ACL assignments and redirect URLs [37-18](#)
  - using with port security [37-17](#)
  - with Critical Authentication [37-13](#)
  - with Guest VLANs [37-10](#)
  - with MAC Authentication Bypass [37-11](#)
  - with VLAN assignment [37-9](#)
- port-channel interfaces
  - See also EtherChannel
  - creating [19-7](#)
  - overview [19-2](#)
- port-channel load-balance
  - command [19-13](#)
  - command example [19-13](#)
- port-channel load-balance command [19-14](#)
- port cost (STP)
  - configuring [17-15](#)
- port description TLV [24-2](#)
- PortFast
  - and MST [17-23](#)
  - BPDU filter, configuring [18-10](#)
  - configuring or enabling [18-16](#)
  - overview [18-7](#)
- PortFast BPDU filtering
  - and MST [17-23](#)
  - enabling [18-10](#)
  - overview [18-9](#)
- port numbering with TwinGig Convertors [7-7](#)
- port priority
  - configuring MST instances [17-32](#)
  - configuring STP [17-13](#)
- ports
  - blocking [45-1](#)
  - checking status [8-2](#)
  - dynamic VLAN membership
    - example [13-29](#)
    - reconfirming [13-26](#)
  - forwarding, resuming [45-3](#)
  - See also interfaces
- port security
  - aging [39-5](#)
  - configuring [39-7](#)
  - displaying [39-28](#)
  - guidelines and restrictions [39-33](#)
  - on access ports [39-7, 39-22](#)
  - on private VLAN [39-14](#)
    - host [39-14](#)
    - promiscuous [39-16](#)
    - topology [39-15, 39-18, 39-32](#)
  - on trunk port [39-17](#)
    - guidelines and restrictions [39-15, 39-18, 39-21, 39-32](#)
    - port mode changes [39-22](#)
  - on voice ports [39-22](#)
  - sticky learning [39-5](#)
  - using with 802.1X [37-17](#)
  - violations [39-6](#)
  - with 802.1X Authentication [39-32](#)
  - with DHCP and IP Source Guard [39-31](#)
  - with other features [39-33](#)
- port states
  - description [17-5](#)
- port VLAN ID TLV [24-2](#)
- power
  - inline [35-5](#)
- power dc input command [11-17](#)
- powered devices, configuring power consumption [10-5](#)
- power handling for Supervisor Engine II-TS [10-11](#)
- power inline command [10-3](#)
- power inline consumption command [10-5](#)
- power management
  - Catalyst 4500 series [11-5](#)
  - Catalyst 4500 Switch power supplies [11-12](#)
  - configuring combined mode [11-11](#)
  - configuring redundant mode [11-10](#)
  - overview [11-1](#)
  - redundancy [11-5](#)

- power management for Catalyst 4500 Switch
  - combined mode [11-7](#)
  - redundant mode [11-7](#)
- power management limitations in Catalyst 4500 Switch [11-8](#)
- power management mode
  - selecting [11-7](#)
- power management TLV [24-2, 24-7](#)
- power negotiation
  - through LLDP [24-8](#)
- Power-On-Self-Test diagnostics [55-9, 55-18](#)
- Power-On-Self-Test for Supervisor Engine V-10GE [55-12](#)
- power policing, displaying on an interface [10-14](#)
- power redundancy-mode command [11-10](#)
- power supplies
  - available power for Catalyst 4500 Switch [11-12](#)
  - fixed [11-6](#)
  - variable [11-6](#)
- pre-authentication open access [37-8](#)
- pre-authentication open access. See port-based authentication.
- primary VLANs [36-2, 36-4](#)
  - associating with secondary VLANs [36-16](#)
  - configuring as a PVLAN [36-15](#)
- priority
  - overriding CoS of incoming frames [35-5](#)
- priority queuing, QoS on Sup 6-E [34-29](#)
- private VLAN
  - configure port security [39-14, 39-15](#)
  - enabling DHCP Snooping [41-11](#)
- private VLANs
  - across multiple switches [36-5](#)
  - and SVIs [36-10](#)
  - benefits of [36-2](#)
  - community ports [36-3](#)
  - community VLANs [36-2, 36-3](#)
  - default configuration [36-12](#)
  - end station access to [36-3](#)
  - isolated port [36-4](#)
  - isolated VLANs [36-2, 36-3, 36-4](#)
  - ports
    - community [36-3](#)
    - isolated [36-4](#)
    - promiscuous [36-4](#)
  - primary VLANs [36-2, 36-4](#)
  - promiscuous ports [36-4](#)
  - secondary VLANs [36-2](#)
  - subdomains [36-2](#)
  - traffic in [36-9](#)
- privileged EXEC mode [2-5](#)
- privileges
  - changing default [3-23](#)
  - configuring levels [3-23](#)
  - exiting [3-24](#)
  - logging in [3-24](#)
- promiscuous ports
  - configuring PVLAN [36-17](#)
  - defined [36-4](#)
  - setting mode [36-23](#)
- protocol timers [17-4](#)
- provider edge devices [32-2](#)
- pruning, VTP
  - See VTP pruning
- pseudobridges
  - description [17-25](#)
- PVACL [41-19](#)
- PVID (port VLAN ID)
  - and 802.1X with voice VLAN ports [37-20](#)
- PVLAN promiscuous trunk port
  - configuring [36-11, 36-17, 36-21](#)
- PVLANS
  - 802.1q support [36-14](#)
  - across multiple switches [36-5](#)
  - configuration guidelines [36-12](#)
  - configure port security [39-14, 39-16, 39-18](#)
  - configure port security in a wireless setting [39-32](#)
  - configuring [36-11](#)
  - configuring a VLAN [36-15](#)

- configuring promiscuous ports [36-17](#)
- host ports
  - configuring a Layer 2 interface [36-18](#)
  - setting [36-23](#)
- overview [36-1](#)
- permitting routing, example [36-22](#)
- promiscuous mode
  - setting [36-23](#)
- setting
  - interface mode [36-23](#)

---

## Q

### QoS

- classification [34-6 to ??](#)
- definitions [34-3](#)
- enabling per-port per-VLAN [34-35](#)
- overview [34-1](#)
- overview of per-port per-VLAN [34-10](#)
- packet modification [34-10](#)
- traffic shaping [34-9](#)
- See also COS; DSCP values; transmit queues

### QoS active queue management

- tracking queue length [34-9](#)

### QoS labels

- definition [34-3](#)

### QoS marking

- description [34-5](#)

### QoS on Sup 6-E

- Active Queue management via DBL [34-33](#)
- active queue management via DBL [34-26, 34-33](#)
- classification [34-14](#)
- configuring [34-12](#)
- configuring the policy map marking action [34-22](#)
- hardware capabilities for marking [34-22](#)
- how to implement policing [34-17](#)
- marking action drivers [34-20](#)
- marking network traffic [34-17](#)
- MQC-based QoS configuration [34-12](#)

- multi-attribute marking support [34-21](#)
- platform hardware capabilities [34-14](#)
- platform restrictions [34-17](#)
- platform-supported classification criteria and QoS features [34-12, 34-13](#)
- policing [34-16](#)
- policy associations [34-38](#)
- prerequisites for applying a service policy [34-14](#)
- priority queuing [34-29](#)
- queue-limiting [34-30](#)
- restrictions for applying a service policy [34-14](#)
- shaping [34-24](#)
- sharing(bandwidth) [34-26](#)
- sharing(bandwidth), shapring, and priority queuing [34-24](#)
- software QoS [34-39](#)
- traffic marking procedure flowchart [34-20](#)

### QoS policing

- definition [34-5](#)
- described [34-8](#)

### QoS policy

- attaching to interfaces [34-9](#)

### QoS service policy

- prerequisites [34-14](#)
- restrictions for applying [34-14](#)

### QoS transmit queues

- burst [34-9](#)
- maximum rate [34-9](#)
- sharing link bandwidth [34-9](#)

### Quality of service

- See QoS

### queueing [34-9](#)

- queue-limiting, QoS on Sup 6-E [34-30](#)

---

## R

### RADIUS server

- configure to-Switch communication [37-28](#)
- configuring settings [37-30](#)



- parameters on the switch [37-28](#)
- range command [7-5](#)
- range macros
  - defining [7-6](#)
- ranges of interfaces
  - configuring [7-4](#)
- Rapid Spanning Tree
  - See RSTP
- rcommand command [12-12](#)
- re-authentication of a client
  - configuring manual [37-67](#)
  - enabling periodic [37-62](#)
- redirect URLs, port-based authentication [37-18](#)
- reduced MAC address [17-2](#)
- redundancy
  - configuring [5-7](#)
  - guidelines and restrictions [5-6](#)
    - changes made through SNMP [5-11](#)
  - NSF-aware support [9-2](#)
  - NSF-capable support [9-2](#)
  - overview [5-2](#)
  - redundancy command [5-8](#)
  - understanding synchronization [5-5](#)
- redundancy (NSF) [9-1](#)
  - configuring
    - BGP [9-9](#)
    - CEF [9-9](#)
    - EIGRP [9-12](#)
    - OSPF [9-11](#)
  - routing protocols [9-5](#)
- redundancy (RPR)
  - route processor redundancy [5-3](#)
  - synchronization [5-5](#)
- redundancy (SSO)
  - redundancy command [9-8](#)
  - route processor redundancy [5-3](#)
  - synchronization [5-6](#)
- reload command [3-28](#), [3-29](#), [3-40](#)
- Remote Network Monitoring
  - See RMON
- rendevous point, configuring [30-16](#)
- rendevous point, configuring single static [30-19](#)
- replication
  - description [30-8](#)
- report suppression, IGMP
  - disabling [22-10](#)
- reserved-range VLANs
  - See VLANs
- reset command [56-3](#)
- resetting an interface to default configuration [7-29](#)
- resetting a switch to defaults [3-32](#)
- responder, IP SLAs
  - described [48-4](#)
  - enabling [48-8](#)
- response time, measuring with IP SLAs [48-5](#)
- restricting access
  - NTP services [4-8](#)
  - TACACS+ [3-15](#)
- retransmission number
  - setting in 802.1X authentication [37-66](#)
- retransmission time
  - changing in 802.1X authentication [37-65](#)
- RFC
  - 1157, SNMPv1 [52-2](#)
  - 1305, NTP [4-2](#)
  - 1757, RMON [53-2](#)
  - 1901, SNMPv2C [52-2](#)
  - 1902 to 1907, SNMPv2 [52-2](#)
  - 2273-2275, SNMPv3 [52-2](#)
- RIP
  - description [1-13](#)
  - for IPv6 [44-5](#)
- RMON
  - default configuration [53-3](#)
  - displaying status [53-6](#)
  - enabling alarms and events [53-3](#)
  - groups supported [53-2](#)
  - overview [53-1](#)

## ROM monitor

- boot process and [3-26](#)
- CLI [2-7](#)
- commands [56-2 to ??](#)
- exiting [56-5](#)

## root bridge

- configuring [17-9](#)
- selecting in MST [17-22](#)

## root guard

- and MST [17-23](#)
- enabling [18-2](#)
- overview [18-2](#)

## routed packets

- ACLs [43-27](#)

route-map (IP) command [31-6](#)

## route maps

- defining [31-6](#)
- PBR [31-2](#)

## router ACLs

- description [43-3](#)
- using with VLAN maps [43-25](#)

router ACLs, using PACL with VLAN maps [43-32](#)

## route targets

- VPN [32-3](#)

## Routing Information Protocol

- See RIP

## RPF

- <Emphasis>See Unicast RPF

## RSPAN

- configuration guidelines [50-16](#)
- destination ports [50-5](#)
- IDS [50-3](#)
- monitored ports [50-4](#)
- monitoring ports [50-5](#)
- received traffic [50-3](#)
- sessions
  - creating [50-17](#)
  - defined [50-3](#)
  - limiting source traffic to specific VLANs [50-23](#)

- monitoring VLANs [50-22](#)

- removing source (monitored) ports [50-21](#)

- specifying monitored ports [50-17](#)

- source ports [50-4](#)

- transmitted traffic [50-4](#)

- VLAN-based [50-5](#)

## RSTP

- compatibility [17-23](#)

- description [17-22](#)

- port roles [17-23](#)

- port states [17-24](#)

## S

## SAID

- See 802.10 SAID

scheduling [34-9](#)scheduling, IP SLAs operations [48-6](#)secondary root switch [17-12](#)secondary VLANs [36-2](#)

- associating with primary [36-16](#)

- permitting routing [36-22](#)

## security

- configuring [40-1](#)

## Security Association Identifier

- See 802.10 SAID

selecting a power management mode [11-7](#)selecting X2/TwinGig Convertor Mode [7-8](#)sequence numbers in log messages [51-7](#)

## server IDs

- description [54-24](#)

service policy, configure class-level queue-limit [34-30](#)service-policy input command [26-2](#)

## service-provider networks

- and customer VLANs [23-2](#)

set default interface command [31-7](#)set interface command [31-7](#)set ip default next-hop command [31-7](#)set ip next-hop command [31-6](#)

- set-request operation [52-4](#)
- severity levels, defining in system messages [51-8](#)
- shaping, QoS on Sup 6-E [34-24](#)
- sharing(bandwidth), QoS on Sup 6-E [34-26](#)
- show adjacency command [28-9](#)
- show boot command [3-31](#)
- show catalyst4000 chassis-mac-address command [17-3](#)
- show cdp command [20-2, 20-3](#)
- show cdp entry command [20-3](#)
- show cdp interface command [20-3](#)
- show cdp neighbors command [20-4](#)
- show cdp traffic command [20-4](#)
- show ciscoview package command [4-35](#)
- show ciscoview version command [4-35](#)
- show cluster members command [12-12](#)
- show configuration command [7-15](#)
- show debugging command [20-4](#)
- show environment command [11-2](#)
- show history command [2-4](#)
- show interfaces command [7-20, 7-21, 7-26, 7-28](#)
- show interfaces status command [8-2](#)
- show ip cef command [28-8](#)
- show ip eigrp interfaces command [27-18](#)
- show ip eigrp neighbors command [27-18](#)
- show ip eigrp topology command [27-18](#)
- show ip eigrp traffic command [27-18](#)
- show ip interface command [30-21](#)
- show ip local policy command [31-8](#)
- show ip mroute command [30-21](#)
- show ip pim interface command [30-21](#)
- show lldp traffic command [24-10](#)
- show mac-address-table address command [8-3](#)
- show mac-address-table interface command [8-3](#)
- show mls entry command [28-8](#)
- show module command [8-2, 17-5](#)
- show PoE consumed [10-8](#)
- show power inline command [10-6](#)
- show power supplies command [11-10](#)
- show protocols command [7-26](#)
- show running-config command
  - adding description for an interface [7-15](#)
  - checking your settings [3-9](#)
  - displaying ACLs [43-19, 43-22, 43-29, 43-30, 43-31](#)
- show startup-config command [3-10](#)
- show users command [8-7](#)
- show version command [3-29](#)
- shutdown, command [7-27](#)
- shutting down
  - interfaces [7-26](#)
- Simple Network Management Protocol
  - See SNMP
- single-host mode [37-7](#)
- single spanning tree
  - See SST
- single static RP, configuring [30-19](#)
- slot numbers, description [7-2](#)
- smart call home [54-1](#)
  - description [54-2](#)
  - destination profile (note) [54-5](#)
  - registration requirements [54-3](#)
  - service contract requirements [54-3](#)
  - Transport Gateway (TG) aggregation point [54-2](#)
- SMARTnet
  - smart call home registration [54-3](#)
- Smartports macros
  - applying global parameter values [16-8](#)
  - applying macros [16-8](#)
  - applying parameter values [16-8](#)
  - configuration guidelines [16-6](#)
  - configuring [16-2](#)
  - creating [16-7](#)
  - default configuration [16-3](#)
  - defined [16-1](#)
  - displaying [16-12](#)
  - tracing [16-6](#)
- SNMP
  - accessing MIB variables with [52-4](#)
  - agent

- described [52-4](#)
  - disabling [52-7](#)
  - and IP SLAs [48-3](#)
  - authentication level [52-10](#)
  - community strings
    - configuring [52-7](#)
    - overview [52-4](#)
  - configuration examples [52-16](#)
  - configuration guidelines [52-6](#)
  - default configuration [52-5](#)
  - enabling [57-4](#), [57-5](#)
  - engine ID [52-6](#)
  - groups [52-6](#), [52-9](#)
  - host [52-6](#)
  - informs
    - and trap keyword [52-11](#)
    - described [52-5](#)
    - differences from traps [52-5](#)
    - enabling [52-15](#)
  - limiting access by TFTP servers [52-15](#)
  - limiting system log messages to NMS [51-9](#)
  - manager functions [52-3](#)
  - notifications [52-5](#)
  - overview [52-1](#), [52-4](#)
  - status, displaying [52-17](#)
  - system contact and location [52-15](#)
  - trap manager, configuring [52-13](#)
  - traps
    - described [52-3](#), [52-5](#)
    - differences from informs [52-5](#)
    - enabling [52-11](#)
    - enabling MAC address notification [4-24](#)
    - enabling MAC move notification [4-26](#)
    - enabling MAC threshold notification [4-28](#)
    - overview [52-1](#), [52-4](#)
    - types of [52-11](#)
  - users [52-6](#), [52-9](#)
  - versions supported [52-2](#)
- SNMP commands [57-4](#)
- SNMPv1 [52-2](#)
  - SNMPv2C [52-2](#)
  - SNMPv3 [52-2](#)
  - software
    - upgrading [5-13](#)
  - software configuration register [3-26](#)
  - software QoS, on Sup 6-E [34-39](#)
  - software switching
    - description [28-5](#)
    - interfaces [28-6](#)
    - key data structures used [30-7](#)
  - source IDs
    - call home event format [54-23](#)
- SPAN
- and ACLs [50-5](#)
  - configuration guidelines [50-7](#)
  - configuring [50-7 to 50-10](#)
  - destination ports [50-5](#)
  - IDS [50-3](#)
  - monitored port, defined [50-4](#)
  - monitoring port, defined [50-5](#)
  - received traffic [50-3](#)
  - sessions
    - defined [50-3](#)
  - source ports [50-4](#)
  - transmitted traffic [50-4](#)
  - VLAN-based [50-5](#)
- SPAN and RSPAN
- concepts and terminology [50-3](#)
  - default configuration [50-6](#)
  - displaying status [50-24](#)
  - overview [50-2](#)
  - session limits [50-6](#)
- SPAN enhancements
- access list filtering [50-13](#)
  - configuration example [50-15](#)
  - CPU port sniffing [50-10](#)
  - encapsulation configuration [50-12](#)
  - ingress packets [50-12](#)

- packet type filtering [50-14](#)
- spanning-tree backbonefast command [18-16](#)
- spanning-tree cost command [17-15](#)
- spanning-tree guard root command [18-2](#)
- spanning-tree portfast bpdu-guard command [18-9](#)
- spanning-tree portfast command [18-7](#)
- spanning-tree port-priority command [17-13](#)
- spanning-tree uplinkfast command [18-13](#)
- spanning-tree vlan
  - command [17-9](#)
  - command example [17-9](#)
- spanning-tree vlan command [17-8](#)
- spanning-tree vlan cost command [17-15](#)
- spanning-tree vlan forward-time command [17-19](#)
- spanning-tree vlan hello-time command [17-17](#)
- spanning-tree vlan max-age command [17-18](#)
- spanning-tree vlan port-priority command [17-13](#)
- spanning-tree vlan priority command [17-17](#)
- spanning-tree vlan root primary command [17-10](#)
- spanning-tree vlan root secondary command [17-12](#)
- speed
  - configuring interface [7-12](#)
- speed command [7-13](#)
- SSO
  - configuring [9-8](#)
- SSO operation [9-3](#)
- SST
  - description [17-22](#)
  - interoperability [17-24](#)
- static addresses
  - See addresses
- static routes
  - configuring [3-11](#)
  - verifying [3-12](#)
- statistics
  - 802.1X [38-13](#)
  - displaying 802.1X [37-68](#)
  - displaying PIM [30-25](#)
  - LLDP [24-10](#)
  - LLDP-MED [24-10](#)
  - SNMP input and output [52-17](#)
- sticky learning
  - configuration file [39-5](#)
  - defined [39-5](#)
  - disabling [39-5](#)
  - enabling [39-5](#)
  - saving addresses [39-5](#)
- sticky MAC addresses
  - configuring [39-7](#)
  - defined [39-4](#)
- Storm Control
  - displaying [49-6](#)
  - enabling Broadcast [49-3](#)
  - enabling Multicast [49-4](#)
  - hardware-based, implementing [49-2](#)
  - overview [49-1](#)
  - software-based, implementing [49-2](#)
- STP
  - bridge ID [17-2](#)
  - configuring [17-7 to 17-20](#)
  - creating topology [17-4](#)
  - defaults [17-6](#)
  - disabling [17-19](#)
  - enabling [17-7](#)
  - enabling extended system ID [17-8](#)
  - enabling Per-VLAN Rapid Spanning Tree [17-20](#)
  - EtherChannel guard
    - disabling [18-7](#)
  - forward-delay time [17-18](#)
  - hello time [17-17](#)
  - maximum aging time [17-18](#)
  - overview [17-1, 17-3](#)
  - per-VLAN rapid spanning tree [17-6](#)
  - port cost [17-15](#)
  - port priority [17-13](#)
  - root bridge [17-9](#)
- stratum, NTP [4-2](#)
- stub routing (EIGRP)

- benefits [27-16](#)
- configuration tasks [27-17](#)
- configuring [27-13](#)
- overview [27-12, 27-13](#)
- restrictions [27-17](#)
- verifying [27-17](#)
- subdomains, private VLAN [36-2](#)
- summer time [4-13](#)
- supervisor engine
  - accessing the redundant [5-14](#)
  - configuring [3-8 to 3-13](#)
  - copying files to standby [5-14](#)
  - default configuration [3-1](#)
  - default gateways [3-11](#)
  - environmental monitoring [11-1](#)
  - redundancy [9-1](#)
  - ROM monitor [3-26](#)
  - startup configuration [3-25](#)
  - static routes [3-11](#)
  - synchronizing configurations [5-11](#)
- Supervisor Engine II-TS
  - insufficient inline power handling [10-11](#)
- SVI Autostate Exclude
  - understanding [27-3](#)
- SVI Autostate exclude
  - configuring [27-7](#)
- switch [44-2](#)
- switched packets
  - and ACLs [43-26](#)
- Switched Port Analyzer
  - See SPAN
- switchport
  - show interfaces [7-20, 7-21, 7-28](#)
- switchport access vlan command [15-6, 15-8](#)
- switchport block multicast command [45-2](#)
- switchport block unicast command [45-2](#)
- switchport mode access command [15-8](#)
- switchport mode dot1q-tunnel command [23-6](#)
- switchport mode dynamic command [15-6](#)
- switchport mode trunk command [15-6](#)
- switch ports
  - See access ports
- switchport trunk allowed vlan command [15-6](#)
- switchport trunk encapsulation command [15-6](#)
- switchport trunk encapsulation dot1q command [15-3](#)
- switchport trunk encapsulation isl command [15-3](#)
- switchport trunk encapsulation negotiate command [15-3](#)
- switchport trunk native vlan command [15-6](#)
- switchport trunk pruning vlan command [15-7](#)
- switch-to-RADIUS server communication
  - configuring [37-28](#)
- system
  - reviewing configuration [3-10](#)
  - settings at startup [3-27](#)
- system alarms
  - on Sup 2+ to V-10GE [11-4](#)
  - overview [11-4](#)
- system and network statistics, displaying [30-21](#)
- system capabilities TLV [24-2](#)
- system clock
  - configuring
    - daylight saving time [4-13](#)
    - manually [4-11](#)
    - summer time [4-13](#)
    - time zones [4-12](#)
  - displaying the time and date [4-12](#)
  - overview [4-2](#)
  - See also NTP
- system description TLV [24-2](#)
- system images
  - loading from Flash memory [3-30](#)
  - modifying boot field [3-27](#)
  - specifying [3-30](#)
- system message logging
  - default configuration [51-3](#)
  - defining error message severity levels [51-8](#)
  - disabling [51-4](#)
  - displaying the configuration [51-12](#)

- enabling [51-4](#)
  - facility keywords, described [51-12](#)
  - level keywords, described [51-9](#)
  - limiting messages [51-9](#)
  - message format [51-2](#)
  - overview [51-1](#)
  - sequence numbers, enabling and disabling [51-7](#)
  - setting the display destination device [51-5](#)
  - synchronizing log messages [51-6](#)
  - timestamps, enabling and disabling [51-7](#)
  - UNIX syslog servers
    - configuring the daemon [51-10](#)
    - configuring the logging facility [51-11](#)
    - facilities supported [51-12](#)
  - system MTU
    - 802.1Q tunneling [23-5](#)
    - maximums [23-5](#)
  - system name
    - manual configuration [4-15](#)
    - See also DNS
  - system name TLV [24-2](#)
  - system prompt, default setting [4-14](#)
- ## T
- 
- TACACS+ [40-1](#)
    - accounting, defined [3-16](#)
    - authentication, defined [3-16](#)
    - authorization, defined [3-16](#)
    - configuring
      - accounting [3-21](#)
      - authentication key [3-18](#)
      - authorization [3-21](#)
      - login authentication [3-19](#)
    - default configuration [3-18](#)
    - displaying the configuration [3-22](#)
    - identifying the server [3-18](#)
    - limiting the services to the user [3-21](#)
    - operation of [3-17](#)
    - overview [3-15](#)
    - tracking services accessed by user [3-21](#)
  - tagged packets
    - 802.1Q [23-3](#)
  - TCAM programming and ACLs [43-7](#)
    - for Sup II-Plust thru V-10GE [43-6](#)
  - TDR
    - checking cable connectivity [8-3](#)
    - enabling and disabling test [8-3](#)
    - guidelines [8-3](#)
  - Telnet
    - accessing CLI [2-2](#)
    - disconnecting user sessions [8-7](#)
    - executing [8-6](#)
    - monitoring user sessions [8-6](#)
  - telnet command [8-6](#)
  - Terminal Access Controller Access Control System Plus
    - See TACACS+
  - TFTP
    - configuration files in base directory [3-5](#)
    - configuring for autoconfiguration [3-4](#)
    - limiting access by servers [52-15](#)
  - threshold monitoring, IP SLAs [48-6](#)
  - time
    - See NTP and system clock
  - Time Domain Reflectometer
    - See TDR
  - time exceeded messages [8-9](#)
  - timer
    - See login timer
  - timestamps in log messages [51-7](#)
  - time zones [4-12](#)
  - TLV
    - host presence detection [37-8](#)
  - TLVs
    - defined [1-4, 24-2](#)
    - LLDP-MED [24-2](#)
  - Token Ring
    - media not supported (note) [13-5, 13-9](#)

- Topology change notification processing
    - MLD Snooping
      - Topology change notification processing [22-4](#)
  - TOS
    - description [34-4](#)
  - trace command [8-9](#)
  - traceroute
    - See IP traceroute
    - See Layer 2 Traceroute
  - traceroute mac command [8-11](#)
  - traceroute mac ip command [8-11](#)
  - traffic
    - blocking flooded [45-2](#)
  - traffic control
    - using ACLs (figure) [43-4](#)
    - using VLAN maps (figure) [43-5](#)
  - traffic marking procedure flowchart [34-20](#)
  - traffic shaping [34-9](#)
  - translational bridge numbers (defaults) [13-5](#)
  - traps
    - configuring MAC address notification [4-24](#)
    - configuring MAC move notification [4-26](#)
    - configuring MAC threshold notification [4-28](#)
    - configuring managers [52-11](#)
    - defined [52-3](#)
    - enabling [4-24, 4-26, 4-28, 52-11](#)
    - notification types [52-11](#)
    - overview [52-1, 52-4](#)
  - troubleshooting
    - with CiscoWorks [52-4](#)
    - with system message logging [51-1](#)
    - with traceroute [8-9](#)
  - troubleshooting high CPU due to ACLs [43-6](#)
  - trunk ports
    - configure port security [39-17](#)
    - configuring PVLAN [36-19 to 36-20](#)
  - trunks
    - 802.1Q restrictions [15-5](#)
    - configuring [15-6](#)
    - configuring access VLANs [15-6](#)
    - configuring allowed VLANs [15-6](#)
    - default interface configuration [15-6](#)
    - different VTP domains [15-3](#)
    - enabling to non-DTP device [15-4](#)
    - encapsulation [15-3](#)
    - specifying native VLAN [15-6](#)
    - understanding [15-3](#)
  - trustpoint [54-3](#)
  - TTL Map, TTL configured [33-3](#)
  - tunneling
    - defined [23-1](#)
  - tunnel ports
    - 802.1Q, configuring [23-6](#)
    - described [23-2](#)
    - incompatibilities with other features [23-5](#)
  - TwinGig Convertors
    - port numbering [7-7](#)
    - selecting X2/TwinGig Convertor mode [7-8](#)
  - type length value
    - See TLV
  - type of service
    - See TOS
- ## U
- 
- UDLD
    - default configuration [25-2](#)
    - disabling [25-5](#)
    - enabling [25-4](#)
    - overview [25-1](#)
  - UDP jitter, configuring [48-9](#)
  - UDP jitter operation, IP SLAs [48-9](#)
  - unauthorized ports with 802.1X [37-4](#)
  - unicast
    - See IP unicast
  - unicast flood blocking
    - configuring [45-1](#)
  - unicast MAC address filtering



- and adding static addresses [4-31](#)
- and broadcast MAC addresses [4-30](#)
- and CPU packets [4-31](#)
- and multicast addresses [4-30](#)
- and router MAC addresses [4-30](#)
- configuration guidelines [4-30](#)
- described [4-30](#)
- unicast MAC address filtering, configuring
  - ACLs
    - configuring unicast MAC address filtering [43-13](#)
- Unicast RPF (Unicast Reverse Path Forwarding)
  - applying [29-5](#)
  - BGP attributes
    - caution [29-5](#)
  - CEF
    - requirement [29-2](#)
    - tables [29-7](#)
  - configuring [29-9](#)
    - (examples) [?? to 29-12](#)
    - BOOTP [29-8](#)
    - DHCP [29-8](#)
    - enterprise network (figure) [29-6](#)
    - prerequisites [29-9](#)
    - routing table requirements [29-7](#)
    - tasks [29-9](#)
    - verifying [29-10](#)
  - deploying [29-5](#)
  - description [1-15, 29-2](#)
  - disabling [29-11](#)
  - enterprise network (figure) [29-6](#)
  - FIB [29-2](#)
  - implementing [29-4](#)
  - maintaining [29-11](#)
  - monitoring [29-11](#)
  - packets, dropping (figure) [29-4](#)
  - prerequisites [29-9](#)
  - restrictions
    - basic [29-8](#)
    - routing asymmetry [29-7](#)
    - routing asymmetry (figure) [29-8](#)
  - routing table requirements [29-7](#)
  - security policy
    - applying [29-5](#)
    - attacks, mitigating [29-5](#)
    - deploying [29-5](#)
    - tunneling [29-5](#)
  - source addresses, validating [29-3](#)
    - (figure) [29-3, 29-4](#)
    - failure [29-3](#)
  - traffic filtering [29-5](#)
  - tunneling [29-5](#)
  - validation
    - failure [29-3, 29-4](#)
    - packets, dropping [29-3](#)
    - source addresses [29-3](#)
    - verifying [29-10](#)
- unicast traffic
  - blocking [45-2](#)
- unidirectional ethernet
  - enabling [26-2](#)
  - example of setting [26-2](#)
  - overview [26-1](#)
- UniDirectional Link Detection Protocol
  - See UDLD
- Universal PoE, configuring [10-16](#)
- UNIX syslog servers
  - daemon configuration [51-10](#)
  - facilities supported [51-12](#)
  - message logging configuration [51-11](#)
- UplinkFast
  - and MST [17-23](#)
  - enabling [18-16](#)
  - MST and [17-23](#)
  - overview [18-11](#)
- user EXEC mode [2-5](#)
- user sessions
  - disconnecting [8-7](#)
  - monitoring [8-6](#)

using PACL with access-group mode [43-30](#)

## V

### VACLs

Layer 4 port operations [43-9](#)

virtual configuration register [56-3](#)

### virtual LANs

See VLANs

### Virtual Private Network

See VPN

Virtual Switch System(VSS), displaying EtherChannel to [19-16](#)

### VLAN ACLs

See VLAN maps

vlan command [13-6](#)

vlan dot1q tag native command [23-4](#)

VLAN ID, discovering [4-32](#)

### VLAN Management Policy Server

See VMPS

### VLAN maps

applying to a VLAN [43-22](#)

configuration example [43-23](#)

configuration guidelines [43-18](#)

configuring [43-18](#)

creating and deleting entries [43-19](#)

defined [43-3](#)

denying access example [43-24](#)

denying packets [43-20](#)

displaying [43-25](#)

order of entries [43-19](#)

permitting packets [43-20](#)

router ACLs and [43-25](#)

using (figure) [43-5](#)

using in your network [43-22](#)

VLAN maps, PACL and Router ACLs [43-32](#)

### VLANs

allowed on trunk [15-6](#)

configuration guidelines [13-3](#)

configuring [13-5](#)

customer numbering in service-provider networks [23-3](#)

default configuration [13-4](#)

description [1-7](#)

extended range [13-3](#)

IDs (default) [13-5](#)

interface assignment [13-7](#)

limiting source traffic with RSPAN [50-23](#)

monitoring with RSPAN [50-22](#)

name (default) [13-5](#)

normal range [13-3](#)

overview [13-1](#)

reserved range [13-3](#)

See also PVLANS

### VLAN Trunking Protocol

See VTP

### VLAN trunks

overview [15-3](#)

### VMPS

configuration file example [13-32](#)

configuring dynamic access ports on client [13-25](#)

configuring retry interval [13-27](#)

database configuration file [13-32](#)

dynamic port membership

example [13-29](#)

reconfirming [13-26](#)

reconfirming assignments [13-26](#)

reconfirming membership interval [13-26](#)

server overview [13-21](#)

### VMPS client

administering and monitoring [13-28](#)

configure switch

configure reconfirmation interval [13-26](#)

dynamic ports [13-25](#)

entering IP VMPS address [13-24](#)

reconfirmation interval [13-27](#)

reconfirm VLAM membership [13-26](#)

default configuration [13-24](#)

- dynamic VLAN membership overview [13-23](#)
- troubleshooting dynamic port VLAN membership [13-29](#)
- VMPS server
  - fall-back VLAN [13-23](#)
  - illegal VMPS client requests [13-23](#)
  - overview [13-21](#)
  - security modes
    - multiple [13-22](#)
    - open [13-22](#)
    - secure [13-22](#)
- voice interfaces
  - configuring [35-1](#)
- Voice over IP
  - configuring [35-1](#)
- voice ports
  - configuring VVID [35-3](#)
- voice traffic [10-2, 35-5](#)
- voice VLAN
  - IP phone data traffic, described [35-2](#)
  - IP phone voice traffic, described [35-2](#)
- voice VLAN ports
  - using 802.1X [37-20](#)
- VPN
  - configuring routing in [32-11](#)
  - forwarding [32-3](#)
  - in service provider networks [32-1](#)
  - routes [32-2](#)
  - routing and forwarding table
    - See VRF
- VRF
  - defining [32-3](#)
  - tables [32-1](#)
- VRF-aware services
  - ARP [32-6, 32-9](#)
  - configuring [32-6](#)
  - ftp [32-8](#)
  - ping [32-7](#)
  - SNMP [32-7](#)
  - syslog [32-8](#)
  - tftp [32-8](#)
  - traceroute [32-8](#)
  - uRPF [32-7](#)
- VTP
  - client, configuring [13-16](#)
  - configuration guidelines [13-12](#)
  - default configuration [13-13](#)
  - disabling [13-16](#)
  - monitoring [13-19](#)
  - overview [13-8](#)
  - pruning
    - configuring [13-15](#)
  - See also VTP version 2
  - server, configuring [13-16](#)
  - statistics [13-19](#)
  - transparent mode, configuring [13-16](#)
  - version 2
    - enabling [13-15](#)
- VTP advertisements
  - description [13-9](#)
- VTP domains
  - description [13-8](#)
- VTP modes [13-9](#)
- VTP pruning
  - overview [13-11](#)
- VTP versions 2 and 3
  - overview [13-9](#)
  - See also VTP
- VTY and Network Assistant [12-11](#)
- VVID (voice VLAN ID)
  - and 802.1X authentication [37-20](#)
  - configuring [35-3](#)

---

## W

- Wake-on-LAN
  - configure with 802.1X [37-53](#)
- web-based authentication

authentication proxy web pages [38-4](#)

description [1-26, 37-13, 38-1](#)

web-based authentication, interactions with other features [38-4](#)

## Y

---

Y.1731

default configuration [46-28](#)

described [46-26](#)

ETH-AIS

Ethernet Alarm Signal function (ETH-AIS)

[46-27](#)

ETH-RDI [46-27](#)

multicast Ethernet loopback [46-30](#)

multicast ETH-LB [46-28](#)

terminology [46-26](#)