

How to Rerun the Setup Script on the CSS 11000/11500

Document ID: 12642

Introduction
Prerequisites
Requirements
Components Used
Conventions
Information
Related Information

Introduction

This document provides information on rerunning the setup script on the CSS 11000 and 11500 series content services switches.

Prerequisites

Requirements

There are no specific requirements for this document.

Components Used

The information in this document applies to:

- all CSS 11000 and 11500 series content services switches
- Cisco WebNS Software Release 2.06 and later

The information in this document was created from the devices in a specific lab environment. All of the devices used in this document started with a cleared (default) configuration. If your network is live, make sure that you understand the potential impact of any command.

Conventions

For more information on document conventions, refer to the Cisco Technical Tips Conventions.

Information

The setup script runs the first time the CSS is booted. If there is no saved startup-config or archived startup-config, the CSS runs the setup script.

If you would like to rerun the setup script, you can perform *one* of these actions:

- Clear the running config and issue the **script play setup** command.
 - Issue the **clear startup-config** and **clear archive startup-config** commands. Reboot the switch
-

Related Information

- **CSS 11000 Series Content Services Switches Product Support**
 - **CSS 11500 Series Content Services Switches Product Support**
 - **Technical Support – Cisco Systems**
-

[Contacts & Feedback](#) | [Help](#) | [Site Map](#)

© 2009 – 2010 Cisco Systems, Inc. All rights reserved. [Terms & Conditions](#) | [Privacy Statement](#) | [Cookie Policy](#) | [Trademarks of Cisco Systems, Inc.](#)

Updated: Dec 27, 2007

Document ID: 12642
