

How to Measure Frame Relay Circuit Utilization Using SNMP

Document ID: 13500

Introduction

Before You Begin

Conventions

Prerequisites

Components Used

frCircuitSentOctets and **frCircuitReceivedOctets** from RFC 1315 MIB

ifInOctets and **IfOutOctets** from RFC 2233

NetPro Discussion Forums – Featured Conversations

Related Information

Introduction

Tracking Frame Relay data-link connection identifier (DLCI) utilization is similar to tracking the utilization of other types of interfaces in that you track traffic transmitted and received by an interface and compare it with maximum amount possible. However, unlike other interfaces, other factors affect the throughput for a particular Frame Relay circuit. For example, committed information rate (CIR), burst rate, and service provider network congestion can affect your ability to accurately calculate utilization.

This document provides two different methods for calculating Frame Relay circuit utilization:

- Using the **frCircuitSentOctets** and **frCircuitReceivedOctets** from RFC 1315 MIB. This method measures the in and out octets for each circuit (DLCI). As long as you are not using compression over the circuit, the counters are accurate.
- Using the **ifInOctets** and **ifOutOctets** from RFC 2233 for each Frame Relay sub-interface.

Please refer to How To Calculate Bandwidth Utilization Using SNMP for the formulas to use. As an estimate of a maximum throughput of the Frame Relay circuit, you can use the **ifSpeed** of the interface, or, if you have Frame Relay Traffic Policing in place, $(Bc+Be)/Tc$.

Before You Begin

Conventions

For more information on document conventions, see the Cisco Technical Tips Conventions.

Prerequisites

There are no specific prerequisites for this document.

Components Used

The information in this document applies to all devices that support RFC 1315 MIB and RFC 2233.

frCircuitSentOctets and frCircuitReceivedOctets from RFC 1315 MIB

RFC 1315 MIB

```
.1.3.6.1.2.1.10.32.2.1.7
frCircuitSentOctets OBJECT-TYPE
    -- FROM RFC1315-MIB
    SYNTAX          Counter
    MAX-ACCESS      read-only
    STATUS          Mandatory
    DESCRIPTION     "The number of octets sent from this virtual circuit
                    since it was created."
 ::= { iso(1) org(3) dod(6) internet(1) mgmt(2) mib-2(1) transmission(10) frame-relay(32)
       frCircuitTable(2) frCircuitEntry(1) 7 }
```

```
.1.3.6.1.2.1.10.32.2.1.9
frCircuitReceivedOctets OBJECT-TYPE
    -- FROM RFC1315-MIB
    SYNTAX          Counter
    MAX-ACCESS      read-only
    STATUS          Mandatory
    DESCRIPTION     "Number of octets received over this virtual circuit
                    since it was created."
 ::= { ISO(1) org(3) DOD(6) Internet(1) mgmt(2) mib-2(1) transmission(10) frame-relay(32)
       frCircuitTable(2) frCircuitEntry(1) 9 }
```

ifInOctets and IfOutOctets from RFC 2233

The advantage of this method is that these counters take into consideration the compressed data statistics rather than the uncompressed.

```
.1.3.6.1.2.1.2.2.1.10
ifInOctets OBJECT-TYPE
    -- FROM RFC1213-MIB
    SYNTAX          Counter
    MAX-ACCESS      read-only
    STATUS          Current
    DESCRIPTION     "The total number of octets received on the interface, including
                    framing characters. Discontinuities in the value of this counter
                    can occur at re-initialization of the management system, and at other
                    times as indicated by the value of ifCounterDiscontinuityTime."
 ::= { ISO(1) org(3) DOD(6) Internet(1) mgmt(2) mib-2(1) interfaces(2) ifTable(2) ifEntry(1) }
```

```
.1.3.6.1.2.1.2.2.1.16
ifOutOctets OBJECT-TYPE
    -- FROM RFC1213-MIB
    SYNTAX          Counter
    MAX-ACCESS      read-only
    STATUS          Current
    DESCRIPTION     "The total number of octets transmitted out of the interface, including
                    framing characters. Discontinuities in the value of this counter can
                    occur at re-initialization of the management system, and at other
                    times as indicated by the value of ifCounterDiscontinuityTime."
 ::= { ISO(1) org(3) DOD(6) Internet(1) mgmt(2) mib-2(1) interfaces(2) ifTable(2) ifEntry(1) }
```

NetPro Discussion Forums – Featured Conversations

Networking Professionals Connection is a forum for networking professionals to share questions, suggestions, and information about networking solutions, products, and technologies. The featured links are some of the most recent conversations available in this technology.

NetPro Discussion Forums – Featured Conversations for Network Management
Network Infrastructure: Network Management
Virtual Private Networks: Network and Policy Management

Related Information

- [Frame Relay Traffic Policing](#)
- [How To Calculate Bandwidth Utilization Using SNMP](#)
- [Technical Support – Cisco Systems](#)

All contents are Copyright © 2006–2007 Cisco Systems, Inc. All rights reserved. Important Notices and Privacy Statement.

Updated: Oct 26, 2005

Document ID: 13500
