

How to Track When a Power Supply Dies or Redundant Supply Changes State Using SNMP

Document ID: 17434

Introduction

Prerequisites

Requirements

Components Used

Conventions

Tracking Procedure

NetPro Discussion Forums – Featured Conversations

Related Information

Introduction

When devices contain redundant power supplies, you can choose to have the device generate traps when one of the power supplies dies or changes state. Traps exist on both routers and switches, and they notify of a state change or failure, and point to further information as to the nature of the change. This document explains how to track when one of the redundant power supplies dies or changes state using Simple Network Management Protocol (SNMP).

Prerequisites

Requirements

There are no specific requirements for this document.

Components Used

The information in this document is valid for Cisco routers and switches that have redundant power supplies.

The information in this document was created from the devices in a specific lab environment. All of the devices used in this document started with a cleared (default) configuration. If your network is live, make sure that you understand the potential impact of any command.

Conventions

For more information on document conventions, refer to the Cisco Technical Tips Conventions.

Tracking Procedure

For routers, watch for the `ciscoEnvMonRedundantSupplyNotification` trap from the `CISCO-ENVMON-MIB` MIB. The variables `ciscoEnvMonSupplyDescr` and `ciscoEnvMonSupplyState` provide details on the nature of the change. You must configure the `snmp-server enable traps envmon` command to enable traps.

```
.1.3.6.1.4.1.9.9.13.3.0.5
ciscoEnvMonRedundantSupplyNotification OBJECT-TYPE
-- FROM CISCO-ENVMON-MIB TRAP VARBINDS { ciscoEnvMonSupplyStatusDescr, ciscoEnvMonSupplySt
DESCRIPTION "A ciscoEnvMonRedundantSupplyNotification is sent if the redundant power suppl
```

```

        (where extant) fails. Since such a
notification is usually generated before the shutdown state is reached, it can convey more
        and has a better chance of being sent than does the
ciscoEnvMonShutdownNotification."
 ::= { iso(1) org(3) dod(6) internet(1) private(4) enterprises(1) cisco(9) ciscoMgmt(9) ciscoEnvMonMIBNotificationPrefix(3)ciscoEnvMonMIBNotifications(0) 5 }

.1.3.6.1.4.1.9.9.13.1.5.1.2
ciscoEnvMonSupplyStatusDescr OBJECT-TYPE
-- FROM CISCO-ENVMON-MIB
-- TEXTUAL CONVENTION DisplayString
SYNTAX OCTET STRING (0..32) DISPLAY-HINT "255a"
MAX-ACCESS read-only
STATUS Current
DESCRIPTION "Textual description of the power supply being instrumented. This description
        short textual label, suitable as a
human-sensible identification for the rest of the information in the entry."
 ::= { ISO(1) org(3) DOD(6) Internet(1) private(4) enterprises(1) cisco(9) ciscoMgmt(9)
        ciscoEnvMonMIB(13) ciscoEnvMonObjects(1)
ciscoEnvMonSupplyStatusTable(5) ciscoEnvMonSupplyStatusEntry(1) 2 }

.1.3.6.1.4.1.9.9.13.1.5.1.3 ciscoEnvMonSupplyState OBJECT-TYPE
-- FROM CISCO-ENVMON-MIB
-- TEXTUAL CONVENTION CiscoEnvMonState
SYNTAX Integer { normal(1), warning(2), critical(3), shutdown(4), notPresent(5) }
MAX-ACCESS read-only
STATUS Current
DESCRIPTION "The current state of the power supply being instrumented."
 ::= { ISO(1) org(3) DOD(6) Internet(1) private(4) enterprises(1) cisco(9) ciscoMgmt(9)
        ciscoEnvMonMIB(13) ciscoEnvMonObjects(1)
ciscoEnvMonSupplyStatusTable(5) ciscoEnvMonSupplyStatusEntry(1) 3 }

```

For switches, watch for the SNMP trap chassisAlarmOn. The variables chassisTempAlarm, chassisMinorAlarm, and chassisMajorAlarm are included with the trap and are necessary for determining the specific chassis alarm in progress. All these traps are from the CISCO-STACK-MIB.

```

.1.3.6.1.4.1.9.5.0.5 chassisAlarmOn OBJECT-TYPE
-- FROM CISCO-STACK-MIB TRAP VARBINDS { chassisTempAlarm, chassisMinorAlarm, chassisMajorAlarm }
DESCRIPTION "A chassisAlarmOn trap signifies that the agent entity has detected the chassis
        chassisMinorAlarm, or
chassisMajorAlarm object in this MIB has transitioned to the on(2) state. The generation of
        can be controlled by the
sysEnableChassisTraps object in this MIB."
 ::= { ISO(1) org(3) DOD(6) Internet(1) private(4) enterprises(1) cisco(9) workgroup(5)
        ciscoStackNotificationsPrefix(0) 5 }

.1.3.6.1.4.1.9.5.1.2.13 chassisTempAlarm OBJECT-TYPE
-- FROM CISCO-STACK-MIB SYNTAX Integer { off(1), on(2), critical(3) }
MAX-ACCESS read-only
STATUS Current
DESCRIPTION "The chassis temperature alarm status."
 ::= { ISO(1) org(3) DOD(6) Internet(1) private(4) enterprises(1) cisco(9) workgroup(5) ciscoStackNotificationsPrefix(0)
        chassisGrp(2) 13 }

.1.3.6.1.4.1.9.5.1.2.11 chassisMinorAlarm OBJECT-TYPE
-- FROM CISCO-STACK-MIB SYNTAX Integer { off(1), on(2) }
MAX-ACCESS read-only
STATUS Current
DESCRIPTION "The chassis minor alarm status."
 ::= { ISO(1) org(3) DOD(6) Internet(1) private(4) enterprises(1) cisco(9) workgroup(5) ciscoStackNotificationsPrefix(0)
        chassisGrp(2) 11 }

.1.3.6.1.4.1.9.5.1.2.12 chassisMajorAlarm OBJECT-TYPE
-- FROM CISCO-STACK-MIB
SYNTAX Integer { off(1), on(2) }

```

```
MAX-ACCESS read-only
STATUS Current
DESCRIPTION "The chassis major alarm status."
::= { ISO(1) org(3) DOD(6) Internet(1) private(4) enterprises(1) cisco(9) workgroup(5) cisco(9)
      chassisGrp(2) 12 }
```

NetPro Discussion Forums – Featured Conversations

Networking Professionals Connection is a forum for networking professionals to share questions, suggestions, and information about networking solutions, products, and technologies. The featured links are some of the most recent conversations available in this technology.

NetPro Discussion Forums – Featured Conversations for Network Management
Network Infrastructure: Network Management
Virtual Private Networks: Network and Policy Management

Related Information

- [Simple Network Management Protocol Support Resources](#)
- [Technical Support – Cisco Systems](#)

[Contacts & Feedback](#) | [Help](#) | [Site Map](#)

© 2008 – 2009 Cisco Systems, Inc. All rights reserved. [Terms & Conditions](#) | [Privacy Statement](#) | [Cookie Policy](#) | [Trademarks of Cisco Systems, Inc.](#)

Updated: Nov 01, 2005

Document ID: 17434
