

Compatible Systems Tech Notes: Adtran Express 3000 ISDN Chat Script

Document ID: 17668

- Introduction**
- Prerequisites**
 - Requirements
- Affected Products**
- Affected Versions**
- More Information**
- Related Information**

Introduction

This document discusses how to set it up to bring up two Channels – Unconfirmed.

Prerequisites

Requirements

There are no specific requirements for this document.

Affected Products

900i, 1200i, 1220i, 1250i, 1270i, 2600i, 2900i, 2200R, 2220R, 2250R, 2270R, 3500R, 3800R, VSR-2, and VSR-8

Affected Versions

All versions

More Information

This is what is necessary to configure a Chat script for a Compatible router to communicate with an Adtran 3000 ISDN Modem.

```
send ATS27=1

!--- This line sets the link to Multilink PPP.

send ATS54=12

!--- This line sets the PPP Async to Sync Conversion.

send ATS152=2

!--- This line sets it up for 2 B Channels.
```

send ATD 800, 356-0283

!--- This line sends the phone number.

expect CONNECT

!--- This line expects the other end to respond with CONNECT.

!--- This line is sometimes optional.

Related Information

- **Technical Support & Documentation – Cisco Systems**
-

All contents are Copyright © 2006–2007 Cisco Systems, Inc. All rights reserved. Important Notices and Privacy Statement.

Updated: Jun 20, 2007

Document ID: 17668
