

# Default User Name and Password for Cisco Transport Controller

Document ID: 64687

---

## Introduction

### Prerequisites

Requirements

Components Used

Conventions

### Default User Name and Password

ONS 15454 Version 4.1.x and 4.5

ONS 15454 Version 4.6.x and Later

### Problem

### Solution

NetPro Discussion Forums – Featured Conversations

### Related Information

---

## Introduction

This document provides the default user name and password that you can use to log into Cisco Transport Controller (CTC) during the initial setup on Cisco ONS 15454.

## Prerequisites

### Requirements

Cisco recommends that you have knowledge of these topics:

- Cisco ONS 15454
- CTC

### Components Used

The information in this document is based on these software and hardware versions:

- Cisco ONS 15454 version 4.1.x and later

The information in this document was created from the devices in a specific lab environment. All of the devices used in this document started with a cleared (default) configuration. If your network is live, make sure that you understand the potential impact of any command.

### Conventions

Refer to Cisco Technical Tips Conventions for more information on document conventions.

## Default User Name and Password

This section provides the default login values for different versions of ONS 15454.

## ONS 15454 Version 4.1.x and 4.5

Use these default login values to log into CTC for ONS 15454 versions 4.1.x and 4.5:

- User Name = CISCO15
- Password =

CISCO15 is delivered without a password in ONS 15454 version 4.1.x and 4.5.

## ONS 15454 Version 4.6.x and Later

Use these default login values to log into CTC for ONS 15454 version 4.6.x and later:

- User Name = CISCO15
- Password = otbu+1

The default login values are case sensitive in all versions of ONS 15454. The CISCO15 user name has SuperUser privileges. You can use CISCO15 to create other users. You must create another SuperUser before you can delete CISCO15.

## Problem

Although CISCO15 must be delivered without a password in ONS 15454 version 4.1.x and 4.5, a few TCC2 cards delivered with ONS 15454 version 4.1.x or 4.5 are loaded with otbu+1 as the default password. This contradicts the information provided on page 3–27 in the *Cisco ONS 15454 Procedure Guide, R4.1.x and R4.5*.

## Solution

When you log into CTC for initial setup on ONS 15454 version 4.1.x or 4.5.x, use CISCO15 without a password first. If your login fails, use **otbu+1** as password for CISCO15. If you are still unable to log in, please contact Cisco Technical Assistance Center (TAC) for assistance.

## NetPro Discussion Forums – Featured Conversations

Networking Professionals Connection is a forum for networking professionals to share questions, suggestions, and information about networking solutions, products, and technologies. The featured links are some of the most recent conversations available in this technology.

|                                                               |
|---------------------------------------------------------------|
| NetPro Discussion Forums – Featured Conversations for Optical |
| Service Providers: Optical Networking                         |
| Service Providers: Metro                                      |

## Related Information

- [Cisco ONS 15454 Procedure Guide, Release 8.0](#)
- [Technical Support & Documentation – Cisco Systems](#)

