

WebVPN Capture Tool on the Cisco ASA 5500 Series Adaptive Security Appliance

Document ID: 65096

Introduction

Prerequisites

Requirements

Components Used

Conventions

Configure

WebVPN Capture Tool Output Files

Activate the WebVPN Capture Tool

Locate and Upload the WebVPN Capture Tool Output Files

Verify

Troubleshoot

Related Information

Introduction

The Cisco ASA 5500 Series Adaptive Security Appliance includes a WebVPN capture tool that lets you log information about Web sites that do not display properly over a WebVPN connection. You can enable the capture tool from the Command Line Interface (CLI) of the security appliance. The data this tool records can help your Cisco customer support representative troubleshoot problems.

Note: When you enable the WebVPN capture tool, it has an impact on the performance of the security appliance. Be sure to disable the capture tool after you generate the output files.

Prerequisites

Requirements

Ensure that you meet this requirement before you attempt this configuration:

- Use the Command Line Interface (CLI) in order to configure the Cisco ASA 5500 Series Adaptive Security Appliance.

Components Used

The information in this document is based on the Cisco ASA 5500 Series Adaptive Security Appliance that runs version 7.0.

The information in this document was created from the devices in a specific lab environment. All of the devices used in this document started with a cleared (default) configuration. If your network is live, make sure that you understand the potential impact of any command.

Conventions

Refer to Cisco Technical Tips Conventions for more information on document conventions.

Configure

In this section, you are presented with the information to configure the features described in this document.

Note: Use the Command Lookup Tool (registered customers only) to obtain more information on the commands used in this section.

WebVPN Capture Tool Output Files

When the WebVPN capture tool is enabled, the capture tool stores the data from the first URL visited in these files:

- **original.000** Contains the data exchanged between the security appliance and the web server.
- **mangled.000** Contains the data exchanged between the security appliance and the browser.

For each subsequent capture, the capture tool generates additional matching **original.<nnn>** and **mangled.<nnn>** files and increments the file extensions. In this example, the output of the **dir** command displays three sets of files from three URL captures:

```
hostname#dir
Directory of disk0:/
2952      -rw-      10931      10:38:32 Jan 19 2005 config
6         -rw-      5124096    19:43:32 Jan 01 2003 cdisk.bin
3397      -rw-      5157       08:30:56 Feb 14 2005 ORIGINAL.000
3398      -rw-      6396       08:30:56 Feb 14 2005 MANGLED.000
3399      -rw-      4928       08:32:51 Feb 14 2005 ORIGINAL.001
3400      -rw-      6167       08:32:51 Feb 14 2005 MANGLED.001
3401      -rw-      5264       08:35:23 Feb 14 2005 ORIGINAL.002
3402      -rw-      6503       08:35:23 Feb 14 2005 MANGLED.002
hostname#
```

Activate the WebVPN Capture Tool

Note: The Flash File System has limitations when multiple files are opened for writing. The WebVPN capture tool can possibly cause file system corruption when multiple capture files are updated concurrently. If this failure should occur with the capture tool, contact the Cisco Technical Assistance Center (TAC).

In order to activate the WebVPN capture tool, use the **debug menu webvpn 67** command from privileged EXEC mode:

```
debug menu webvpn 67 <cmd> <user> <url>
```

Where:

- **cmd** is 0 or 1. 0 disables capture. 1 enables capture.
- **user** is the username to match for data capture.
- **url** is the URL prefix to match for data capture. Use one of these URL formats:
 - ◆ Use **/http** to capture all data.
 - ◆ Use **/http/0/<server/path>** to capture HTTP traffic to the server identified by **<server/path>**.
 - ◆ Use **/https/0/<server/path>** to capture HTTPS traffic to the server identified by **<server/path>**.

Use the **debug menu webvpn 67 0** command in order to disable capture.

In this example, the WebVPN capture tool is enabled to capture HTTP traffic for user2 visiting Web site `wwwin.abcd.com/hr/people`:

```
hostname#debug menu webvpn 67 1 user2 /http/0/wwwin.abcd.com/hr/people
Mangle Logging: ON
Name: "user2"
URL: "/http/0/wwwin.abcd.com/hr/people"
hostname#
```

In this example, the WebVPN capture tool is disabled:

```
hostname#debug menu webvpn 67 0
Mangle Logging: OFF
Name: "user2"
URL: "/http/0/wwwin.abcd.com/hr/people"
hostname#
```

Locate and Upload the WebVPN Capture Tool Output Files

Use the **dir** command in order to locate the WebVPN capture tool output files. This example shows the output of the **dir** command and includes the ORIGINAL.000 and MANGLED.000 files that were generated:

```
hostname#dir
Directory of disk0:/
2952      -rw-          10931          10:38:32 Jan 19 2005 config
6         -rw-          5124096        19:43:32 Jan 01 2003 cdisk.bin
3397      -rw-          5157           08:30:56 Feb 14 2005 ORIGINAL.000
3398      -rw-          6396           08:30:56 Feb 14 2005 MANGLED.000
hostname#
```

You can upload the WebVPN capture tool output files to another computer using the **copy flash** command. In this example, the ORIGINAL.000 and MANGLED.000 files are uploaded:

```
hostname#copy flash:/original.000 tftp://10.86.194.191/original.000
Source filename [original.000]?
Address or name of remote host [10.86.194.191]?
Destination filename [original.000]?
!!!!!!
21601 bytes copied in 0.370 secs
hostname#copy flash:/mangled.000 tftp://10.86.194.191/mangled.000
Source filename [mangled.000]?
Address or name of remote host [10.86.194.191]?
Destination filename [mangled.000]?
!!!!!!
23526 bytes copied in 0.380 secs
hostname#
```

Note: In order to avoid possible file system corruption, do not allow the original.<nnn> and mangled.<nnn> files from previous captures to be overwritten. When you disable the capture tool, delete the old files in order to prevent corruption of the file system.

Verify

There is currently no verification procedure available for this configuration.

Troubleshoot

There is currently no specific troubleshooting information available for this configuration.

Related Information

- **Cisco ASA 5500 Series Adaptive Security Appliance Configuration Guides**
 - **Technical Support & Documentation – Cisco Systems**
-

[Contacts & Feedback](#) | [Help](#) | [Site Map](#)

© 2008 – 2009 Cisco Systems, Inc. All rights reserved. [Terms & Conditions](#) | [Privacy Statement](#) | [Cookie Policy](#) | [Trademarks of Cisco Systems, Inc.](#)

Updated: Oct 01, 2006

Document ID: 65096
