

CallManager: Intercom Feature Configuration Example

Document ID: 81991

Introduction

Prerequisites

Requirements

Components Used

Conventions

Configure Auto Answer

Verify

NetPro Discussion Forums – Featured Conversations

Related Information

Introduction

The Intercom feature allows you to speak to someone on an intercom line. Cisco CallManager does not have a dedicated Intercom feature. However, with Cisco CallManager, you can configure a phone/directory number to auto answer with speakerphone, which acts like an intercom. The configuration of this option causes the speakerphone to go off hook automatically when an incoming call is received.

Prerequisites

Requirements

There are no specific requirements for this document.

Components Used

The information in this document is based on Cisco CallManager 3.x and later.

The information in this document was created from the devices in a specific lab environment. All of the devices used in this document started with a cleared (default) configuration. If your network is live, make sure that you understand the potential impact of any command.

Conventions

Refer to the Cisco Technical Tips Conventions for more information on document conventions.

Configure Auto Answer

Complete these steps in order to configure the Auto Answer feature:

1. On the Cisco CallManager Administration page, choose **Device > Phones** and select **Extension**.
2. Under the Directory Number Settings, go to **Auto Answer** and choose **Auto Answer with speakerphone**.

This acts like an Intercom feature for the directory number.

Note: The Auto Answer feature is not supported on shared lines. If required, you can use a third party solution called Berbee's InformaCast which provides the capability to simultaneously send an audio stream and a text message to Cisco IP phones (7940 or 7960).

The screenshot shows the Cisco CallManager Administration interface. At the top, there is a navigation menu with links: System, Route Plan, Service, Feature, Device, User, Application, Help. Below this is the Cisco CallManager Administration header with the Cisco Systems logo. The main heading is "Directory Number Configuration" with a sub-link "Configure Device (SEP0007EB26DE79) Dependency Records".

On the left, under "Associated With", it shows a phone icon, "SEP0007EB26DE79", and "7940 (Line 1)".

The main configuration area shows:

- Directory Number:** 1000
- Status:** Ready
- Note:** Any update to this Directory Number automatically resets the associated devices
- Buttons: Update, Remove from Device, Reset Devices
- Directory Number Section:**
 - Directory Number*: 1000
 - Partition: < None >
- Directory Number Settings Section:**
 - Voice Mail Profile: < None > (Choose <None> to use default)
 - Calling Search Space: < None >
 - AAR Group: < None >
 - User Hold Audio Source: < None >
 - Network Hold Audio Source: < None >
 - Auto Answer: **Auto Answer with Speakerphone** (highlighted with a red box)
- Call Forward and Pickup Settings** (Section header)

Verify

For all incoming calls to the configured directory number, verify that the speaker phone automatically goes off hook.

NetPro Discussion Forums – Featured Conversations

Networking Professionals Connection is a forum for networking professionals to share questions, suggestions, and information about networking solutions, products, and technologies. The featured links are some of the most recent conversations available in this technology.

NetPro Discussion Forums – Featured Conversations for Voice
Service Providers: Voice over IP
Voice & Video: Voice over IP
Voice & Video: IP Telephony
Voice & Video: IP Phone Services for End Users
Voice & Video: Unified Communications
Voice & Video: IP Phone Services for Developers
Voice & Video: General

Related Information

- [Assistants – How to Use Cisco IPMA on Your Phone](#)
 - [Voice Technology Support](#)
 - [Voice and Unified Communications Product Support](#)
 - [Recommended Reading: Troubleshooting Cisco IP Telephony](#)
 - [Technical Support & Documentation – Cisco Systems](#)
-

All contents are Copyright © 2006–2007 Cisco Systems, Inc. All rights reserved. Important Notices and Privacy Statement.

Updated: Jul 02, 2007

Document ID: 81991
