

CallManager: Intercom Feature Configuration Example

Document ID: 81991

- Introduction**
- Prerequisites**
 - Requirements
 - Components Used
 - Conventions
- Configure Auto Answer**
- Verify**
- Related Information**

Introduction

The Intercom feature allows you to speak to someone on an intercom line. Cisco CallManager does not have a dedicated Intercom feature. However, with Cisco CallManager, you can configure a phone/directory number to auto answer with speakerphone, which acts like an intercom. The configuration of this option causes the speakerphone to go off hook automatically when an incoming call is received.

Prerequisites

Requirements

There are no specific requirements for this document.

Components Used

The information in this document is based on Cisco CallManager 3.x and later.

The information in this document was created from the devices in a specific lab environment. All of the devices used in this document started with a cleared (default) configuration. If your network is live, make sure that you understand the potential impact of any command.

Conventions

Refer to the Cisco Technical Tips Conventions for more information on document conventions.

Configure Auto Answer

Complete these steps in order to configure the Auto Answer feature:

1. On the Cisco CallManager Administration page, choose **Device > Phones** and select **Extension**.
2. Under the Directory Number Settings, go to **Auto Answer** and choose **Auto Answer with speakerphone**.

This acts like an Intercom feature for the directory number.

Note: The Auto Answer feature is not supported on shared lines. If required, you can use a third party solution called Berbee's InformaCast which provides the capability to simultaneously send an audio stream and a text message to Cisco IP phones (7940 or 7960).

The screenshot shows the Cisco CallManager Administration interface. At the top, there is a navigation menu with links: System, Route Plan, Service, Feature, Device, User, Application, and Help. Below the navigation is the Cisco CallManager Administration logo and the Cisco Systems logo. The main heading is "Directory Number Configuration" with a sub-heading "Configure Device (SEP0007EB26DE79) Dependency Records". On the left, there is a sidebar with "Associated With" showing a phone icon, "SEP0007EB26DE79", and "7940 (Line 1)". The main content area shows "Directory Number: 1000" with a status of "Ready" and a note: "Note: Any update to this Directory Number automatically resets the associated devices". There are three buttons: "Update", "Remove from Device", and "Reset Devices". Below this, there are sections for "Directory Number" (Directory Number*: 1000, Partition: <None>), "Directory Number Settings" (Voice Mail Profile: <None>, Calling Search Space: <None>, AAR Group: <None>, User Hold Audio Source: <None>, Network Hold Audio Source: <None>, Auto Answer: Auto Answer with Speakerphone), and "Call Forward and Pickup Settings".

Verify

For all incoming calls to the configured directory number, verify that the speaker phone automatically goes off hook.

Related Information

- [Assistants – How to Use Cisco IPMA on Your Phone](#)
- [Voice Technology Support](#)
- [Voice and Unified Communications Product Support](#)
- [Recommended Reading: Troubleshooting Cisco IP Telephony](#)
- [Technical Support & Documentation – Cisco Systems](#)

[Contacts & Feedback](#) | [Help](#) | [Site Map](#)

© 2008 – 2009 Cisco Systems, Inc. All rights reserved. [Terms & Conditions](#) | [Privacy Statement](#) | [Cookie Policy](#) | [Trademarks of Cisco Systems, Inc.](#)

Updated: Jul 02, 2007

Document ID: 81991