

E&M Cable Pinouts Connecting Cisco 1750/2600/3600 E&M VIC to Lucent PBX G3R E&M Trunk

Document ID: 8635

- Introduction
- Prerequisites
 - Requirements
 - Components Used
 - Conventions
- Pinout
- Related Information

Introduction

This document describes the E&M Cable Pinouts connecting a Cisco 1750/2600/3600 E&M voice interface card (VIC) to a Lucent PBX G3R E&M Trunk.

Prerequisites

Requirements

There are no specific requirements for this document.

Components Used

This document is not restricted to specific software and hardware versions.

Conventions

For more information on document conventions, see the Cisco Technical Tips Conventions.

Pinout

Note: Lucent G3R PBX ty1–stan and ty5 interoperate with Cisco 1750/2600/3600 E&M VIC.

| Router | Pins | PBX |
|--------|--------|-----|
| | 1 -- | |
| M | 2 -- 6 | M |
| R | 3 -- 4 | TA |
| R1 | 4 -- 1 | RA |
| T1 | 5 -- 2 | RB |
| T | 6 -- 5 | TB |
| E | 7 -- 3 | E |
| | 8 -- | |

Related Information

- **Voice Technology Support**
 - **Voice and Unified Communications Product Support**
 - **Recommended Reading: Troubleshooting Cisco IP Telephony**
 - **Technical Support – Cisco Systems**
-

[Contacts & Feedback](#) | [Help](#) | [Site Map](#)

© 2009 – 2010 Cisco Systems, Inc. All rights reserved. [Terms & Conditions](#) | [Privacy Statement](#) | [Cookie Policy](#) | [Trademarks of Cisco Systems, Inc.](#)

Updated: Feb 02, 2006

Document ID: 8635
