

OMPL2001 Result

Copyright ©1999-2006, Standard Performance Evaluation Corporation

Cisco
C220 M3

SPECompLpeak2001 = 549613

SPECompLbase2001 = 527122

SPEC license #: HPG9019 | Tested by: Cisco | Test date: Feb-2012 | Hardware Avail: Apr-2012 | Software Avail: Dec-2011

Benchmark	Reference Time	Base Runtime	Base Ratio	Runtime	Ratio	
311.wupwise_1	9200	213	690726	210	702597	
313.swim_1	12500	635	315187	579	345357	
315.mgrid_1	13500	528	409202	495	435975	
317.applu_1	13500	824	262158	836	258409	
321.earthquake_1	13000	409	508751	382	544936	
325.apsi_1	10500	249	673358	249	673358	
327.gafort_1	11000	350	502602	315	559136	
329.fma3d_1	23500	893	420977	851	441654	
331.art_1	25000	216	1856053	217	1847476	

Hardware

CPU: Intel(R) Xeon(R) Processor E5-2690
CPU MHz: 2900
FPU: Integrated
CPU(s) enabled: 16 cores, 2 chips, 8 cores/chip, 2 thread/core
CPU(s) orderable: 1,2
Primary Cache: 32KB(I)+32KB(D)/core on chip
Secondary Cache: 256KB/core (I+D) on chip
L3 Cache: 20480KB (I+D) on chip
Other Cache: N/A
Memory: 128 GB (RDIMM 16x8-GB 1600 MHz)
Disk Subsystem: LSI MR9266-8i (scsi) 299GB
Other Hardware:

Software

OpenMP Threads: 32
Parallel: OpenMP
Operating System: Red Hat EL 6.2, 2.6.32-220.el6.x86_64
Compiler: Intel C/C++ Compiler 12.0.2 for Linux
Intel FORTRAN Compiler 12.0.2 for Linux
GNU C Compiler 4.4.6
File System: Linux ext4
System State: Default

Notes/Tuning Information

BIOS settings notes:

Intel Hyper-Threading Technology (SMT): Enabled (default is Enabled)
Intel Turbo Boost Technology (Turbo) : Enabled (default is Enabled)

Extra Flags:

331.art_1: -DINTS_PER_CACHELINE=32 -DDBLS_PER_CACHELINE=16
all: -gcc-name=/usr/bin/gcc

General Notes and Environment variables

```
export KMP_LIBRARY=turnaround
export KMP_STACKSIZE=31M
export KMP_BLOCKTIME=infinite
export OMP_DYNAMIC=FALSE
```

ONESTEP=yes

ulimit -s unlimited

SMT Enabled, Turbo Enabled

For compiler/openmp flags description please refer:

Intel-ic12.0-intel64-linux-flags-file.html

Base optimization flags and environment variables:

Large:

```
OPTIMIZE=-O2 -xAVX -ipo -openmp -no-prec-div
```

```
COPTIMIZE = -ansi_alias
```

```
PORTABILITY = -mcmmodel=medium -shared-intel
```

```
export KMP_AFFINITY=compact,0
```

Peak optimization flags and environment variables:

Large:

```
OPTIMIZE=-O2 -xAVX -ipo -openmp
```

Standard Performance Evaluation Corporation

info@spec.org

http://www.spec.org/

OMPL2001 Result

Copyright ©1999-2006, Standard Performance Evaluation Corporation

Cisco
C220 M3

SPECompLpeak2001 = 549613

SPECompLbase2001 = 527122

SPEC license #: HPG9019 | Tested by: Cisco | Test date: Feb-2012 | Hardware Avail: Apr-2012 | Software Avail: Dec-2011

Notes/Tuning Information (Continued)

```
COPTIMIZE = -ansi_alias
PORTABILITY = -mcmmodel=medium -shared-intel
export KMP_AFFINITY=compact,1
Peak per-benchamrk optimization flags and enviroment variables:

311.wupwise_1
OPTIMIZE=-O3 -xSSE4.2 -ipo -openmp

313.swim_1
srcalt = ompl.32
OPTIMIZE=-O3 -xSSE4.2 -ipo -openmp -opt-streaming-stores always -align
export KMP_AFFINITY=compact,1
export OMP_NUM_THREADS=16

315.mgrid_1
OPTIMIZE=-O3 -xSSE4.2 -ipo -openmp -fno-alias
export KMP_AFFINITY=compact,1
export OMP_NUM_THREADS=16

317.applu_1
OPTIMIZE=-O3 -xSSE4.2 -ipo -openmp -fno-alias
export KMP_AFFINITY=compact,1
export OMP_NUM_THREADS=16

321.equake_1
export KMP_AFFINITY=compact,1
export OMP_NUM_THREADS=16

327.gafort_1
OPTIMIZE=-O3 -xSSE4.2 -ipo -openmp
export KMP_AFFINITY=scatter,0

329.fma3d_1
FOPTIMIZE=-no-prec-sqrt -fp-model fast=2
EXTRA_LIBS=-L$(SPECLIB) -lhoard
export KMP_AFFINITY=compact,1

331.art_1
```