



Open Source Used In kvstore Crafton-3.0

Cisco Systems, Inc.

www.cisco.com

Cisco has more than 200 offices worldwide.
Addresses, phone numbers, and fax numbers
are listed on the Cisco website at
www.cisco.com/go/offices.

Text Part Number: 78EE117C99-2000790951

This document contains licenses and notices for open source software used in this product. With respect to the free/open source software listed in this document, if you have any questions or wish to receive a copy of any source code to which you may be entitled under the applicable free/open source license(s) (such as the GNU Lesser/General Public License), please submit this [form](#).

In your requests please include the following reference number 78EE117C99-2000790951

Contents

1.1 cdebconf 0.213ubuntu1

1.1.1 Available under license

1.2 dash 0.5.8-2.10

1.2.1 Available under license

1.3 debianutils 4.8.4

1.3.1 Available under license

1.4 diffutils 3.6-1

1.4.1 Available under license

1.5 hostname 3.20

1.5.1 Available under license

1.6 libffi 3.2.1-8

1.6.1 Available under license

1.7 sensible-utils 0.0.12

1.7.1 Available under license

1.8 adduser 3.116ubuntu1

1.8.1 Available under license

1.9 attr 2.4.47-2build1

1.9.1 Available under license

1.10 base-passwd 3.5.44

1.10.1 Available under license

1.11 coreutils 8.28-1ubuntu1

1.11.1 Available under license

1.12 findutils 4.6.0+git+20170828-2

1.12.1 Available under license

1.13 libsemanage-common 2.7-2build2

1.13.1 Available under license

- 1.14 lsb 9.20170808ubuntu1**
 - 1.14.1 Available under license
- 1.15 mawk 1.3.3-17ubuntu3**
- 1.16 sysv-init 2.88dsf-59.10ubuntu1**
 - 1.16.1 Available under license
- 1.17 debconf 1.5.66ubuntu1**
- 1.18 libunistring 0.9.9-0ubuntu2**
 - 1.18.1 Available under license
- 1.19 init-system-helpers 1.51**
 - 1.19.1 Available under license
- 1.20 procps 3.3.12-3ubuntu1.2**
 - 1.20.1 Available under license
- 1.21 grep 3.1-2build1**
 - 1.21.1 Available under license
- 1.22 libidn 2.0.4-1.1ubuntu0.2**
 - 1.22.1 Available under license
- 1.23 sed 4.4-2**
 - 1.23.1 Available under license
- 1.24 libcap-ng 0.7.7-3.1**
 - 1.24.1 Available under license
- 1.25 ncurses 6.1-1ubuntu1.18.04**
 - 1.25.1 Available under license
- 1.26 acl 2.2.52-3build1**
 - 1.26.1 Available under license
- 1.27 berkeley-db 5.3.28-13.1ubuntu1.1**
 - 1.27.1 Available under license
- 1.28 bzip2 1.0.6-8.1ubuntu0.2**
 - 1.28.1 Available under license
- 1.29 libgpg-error 1.27-6**
 - 1.29.1 Available under license
- 1.30 libprocps6 2:3.3.12-3ubuntu1.2**
 - 1.30.1 Available under license
- 1.31 attr 1:2.4.47-2build1**
 - 1.31.1 Available under license
- 1.32 diffutils 1:3.6-1**
 - 1.32.1 Available under license
- 1.33 procps 2:3.3.12-3ubuntu1.2**
 - 1.33.1 Available under license
- 1.34 cpp 8.4.0-1ubuntu1~18.04**

- 1.34.1 Available under license
- 1.35 libgcc 1:8.4.0-1ubuntu1~18.04**
 - 1.35.1 Available under license
- 1.36 libstd-c 8.4.0-1ubuntu1~18.04**
 - 1.36.1 Available under license
- 1.37 fdisk 2.31.1**
 - 1.37.1 Available under license
- 1.38 libncursesw 6.1-1ubuntu1.18.04**
 - 1.38.1 Available under license
- 1.39 sysvinit-utils 2.88dsf-59.10ubuntu1**
 - 1.39.1 Available under license
- 1.40 libncurses 6.1-1ubuntu1.18.04**
 - 1.40.1 Available under license
- 1.41 libdebconfclient0 0.213ubuntu1**
 - 1.41.1 Available under license
- 1.42 lsb-base 9.20170808ubuntu1**
 - 1.42.1 Available under license
- 1.43 util-linux 2.31.1-0.4ubuntu3.7**
 - 1.43.1 Available under license
- 1.44 selinux 2.7-2build2**
 - 1.44.1 Available under license
- 1.45 audit 2.8.2-1ubuntu1.1**
 - 1.45.1 Available under license
- 1.46 iconv 2.27**
 - 1.46.1 Available under license
- 1.47 zstd 1.3.3+dfsg-2ubuntu1.2**
 - 1.47.1 Available under license
- 1.48 libpkit 0.23.9-2ubuntu0.1**
 - 1.48.1 Available under license
- 1.49 libtasn 4.13-2**
 - 1.49.1 Available under license
- 1.50 util-linux 1:2.31.1-0.4ubuntu3.7**
 - 1.50.1 Available under license
- 1.51 libmount 2.31.1-0.4ubuntu3.7**
 - 1.51.1 Available under license
- 1.52 libuuid 2.31.1-0.4ubuntu3.7**
 - 1.52.1 Available under license
- 1.53 mount 2.31.1-0.4ubuntu3.7**
 - 1.53.1 Available under license

- 1.54 libaudit 1:2.8.2-1ubuntu1.1**
 - 1.54.1 Available under license
- 1.55 fdisk 2.31.1-0.4ubuntu3.7**
 - 1.55.1 Available under license
- 1.56 libzstd1 1.3.3+dfsg-2ubuntu1.2**
 - 1.56.1 Available under license
- 1.57 audit 1:2.8.2-1ubuntu1.1**
 - 1.57.1 Available under license
- 1.58 lz4 0.0~r131-2ubuntu3.1**
 - 1.58.1 Available under license
- 1.59 ubuntu-keyring 2018.09.18.1~18.04.2**
 - 1.59.1 Available under license
- 1.60 apt 1.6.14**
 - 1.60.1 Available under license
- 1.61 base-files 10.1ubuntu2.11**
 - 1.61.1 Available under license
- 1.62 libgcrypt 1.8.1-4ubuntu1.3**
 - 1.62.1 Available under license
- 1.63 afero 1.0.5**
 - 1.63.1 Available under license
- 1.64 tdb 1.44.1**
 - 1.64.1 Available under license
- 1.65 libseccomp 2.5.1-1ubuntu1~18.04.2**
 - 1.65.1 Available under license
- 1.66 spf13-cobra v1.3.0**
 - 1.66.1 Available under license
- 1.67 cobra 1.3.0**
 - 1.67.1 Available under license
- 1.68 xz 5.2.2-1.3ubuntu0.1**
 - 1.68.1 Available under license
- 1.69 gzip 1.6-5ubuntu1.2**
 - 1.69.1 Available under license
- 1.70 liblzma 5.2.2-1.3ubuntu0.1**
 - 1.70.1 Available under license
- 1.71 bash 4.4.18-2ubuntu1.3**
 - 1.71.1 Available under license
- 1.72 libsepol 2.7-1ubuntu0.1**
 - 1.72.1 Available under license
- 1.73 pcre 8.39-9ubuntu0.1**

- 1.73.1 Available under license
- 1.74 dpkg 1.19.0.5ubuntu2.4**
 - 1.74.1 Available under license
- 1.75 glibc 2.27-3ubuntu1.6**
 - 1.75.1 Available under license
- 1.76 libc 2.27-3ubuntu1.6**
 - 1.76.1 Available under license
- 1.77 e2fsprogs 1.44.1-1ubuntu1.4**
 - 1.77.1 Available under license
- 1.78 libcom-err 1.44.1-1ubuntu1.4**
 - 1.78.1 Available under license
- 1.79 pcre 2:8.39-9ubuntu0.1**
 - 1.79.1 Available under license
- 1.80 libext2fs2 1.44.1-1ubuntu1.4**
 - 1.80.1 Available under license
- 1.81 libcbi 2.27-3ubuntu1.6**
 - 1.81.1 Available under license
- 1.82 libss 1.44.1-1ubuntu1.4**
 - 1.82.1 Available under license
- 1.83 golang 1.18.1**
 - 1.83.1 Available under license
- 1.84 gnupg 2.2.4-1ubuntu1.6**
 - 1.84.1 Available under license
- 1.85 gpgv 2.2.4-1ubuntu1.6**
 - 1.85.1 Available under license
- 1.86 gnutls 3.5.18-1ubuntu1.6**
 - 1.86.1 Available under license
- 1.87 zlib 1.2.11.dfsg-0ubuntu2.2**
 - 1.87.1 Available under license
- 1.88 zlib1g 1:1.2.11.dfsg-0ubuntu2.2**
 - 1.88.1 Available under license
- 1.89 systemd 237-3ubuntu10.56**
 - 1.89.1 Available under license
- 1.90 libsystemd 237-3ubuntu10.56**
 - 1.90.1 Available under license
- 1.91 libudev 237-3ubuntu10.56**
 - 1.91.1 Available under license
- 1.92 gmp 6.1.2+dfsg-2ubuntu0.1**
 - 1.92.1 Available under license

- 1.93 perl 5.26.1-6ubuntu0.6**
 - 1.93.1 Available under license
- 1.94 perl-base 5.26.1-6ubuntu0.6**
 - 1.94.1 Available under license
- 1.95 gmp 2:6.1.2+dfsg-2ubuntu0.1**
 - 1.95.1 Available under license
- 1.96 shadow 4.5-1ubuntu2.5**
 - 1.96.1 Available under license
- 1.97 login 1:4.5-1ubuntu2.5**
 - 1.97.1 Available under license
- 1.98 passwd 1:4.5-1ubuntu2.5**
 - 1.98.1 Available under license
- 1.99 ca-certificates 20211016ubuntu0.18.04.1**
 - 1.99.1 Available under license
- 1.100 sudo 1.8.21p2-3ubuntu1.5**
 - 1.100.1 Available under license
- 1.101 pam 1.1.8-3.6ubuntu2.18.04.6**
 - 1.101.1 Available under license
- 1.102 openssl 1.1.1-1ubuntu2.1~18.04.21**
 - 1.102.1 Available under license
- 1.103 libssl 1.1.1-1ubuntu2.1~18.04.21**
 - 1.103.1 Available under license
- 1.104 libpamg 1.1.8-3.6ubuntu2.18.04.6**
 - 1.104.1 Available under license
- 1.105 libpammodulesbin 1.1.8-3.6ubuntu2.18.04.6**
 - 1.105.1 Available under license
- 1.106 tar 1.29b-2ubuntu0.4**
 - 1.106.1 Available under license
- 1.107 libnettle6 3.4.1-0ubuntu0.18.04.1**
 - 1.107.1 Available under license
- 1.108 githubcompelletiergotoml v1.9.4**
 - 1.108.1 Available under license
- 1.109 spf13-pflag v1.0.5**
 - 1.109.1 Available under license
- 1.110 go-toml 1.9.4**
 - 1.110.1 Available under license
- 1.111 pflag 1.0.5**
 - 1.111.1 Available under license

1.1 cdebconf 0.213ubuntu1

1.1.1 Available under license :

CDebConf was initially written by Randolph Chung <tausq@debian.org>

Other contributors include:

Anthony Towns <ajt@debian.org>

David Whedon <dwhedon@gordian.com>

Dan Jacobowitz <dan@debian.org>

Tollef Fog Heen <tfheen@debian.org>

Attilio Fiandrotti <fiandro@tiscali.it>

Colin Watson <cjwatson@debian.org>

Regis Boudin <regis@debian.org>

CDebConf includes ideas and code from:

debconf - The original, de facto, perl implementation

(c) Joey Hess <joeyh@debian.org>

apt - The Debian Advanced Package Tool

(c) Jason Gunthorpe <jgg@debian.org>

(derived portions are public domain)

CDebConf is copyrighted (c) 2000-2009 by Randolph Chung <tausq@debian.org>, the d-i team (see above), and Canonical Ltd. under the following license:

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

1. Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.
2. Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.

THIS SOFTWARE IS PROVIDED BY THE AUTHORS AND CONTRIBUTORS ``AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE AUTHOR OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

1.2 dash 0.5.8-2.10

1.2.1 Available under license :

This package was debianized by Mark W. Eichin eichin@kitten.gen.ma.us on Mon, 24 Feb 1997 16:00:16 -0500.

This package was re-ported from NetBSD and debianized by Herbert Xu herbert@debian.org on Thu, 19 Jun 1997 19:29:16 +1000.

This package was adopted by Gerrit Pape pape@smarden.org on Fri, 28 May 2004 18:38:18 +0000.

It was downloaded from <http://gondor.apana.org.au/~herbert/dash/files/>

Copyright:

Copyright (c) 1989-1994

The Regents of the University of California. All rights reserved.

Copyright (c) 1997 Christos Zoulas. All rights reserved.

Copyright (c) 1997-2005

Herbert Xu herbert@gondor.apana.org.au. All rights reserved.

This code is derived from software contributed to Berkeley by Kenneth Almquist.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

1. Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.
2. Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.
3. Neither the name of the University nor the names of its contributors may be used to endorse or promote products derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE REGENTS AND CONTRIBUTORS ``AS IS'' AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE REGENTS OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY,

OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

mksignames.c:

This file is not directly linked with dash. However, its output is.

Copyright (C) 1992 Free Software Foundation, Inc.

This file is part of GNU Bash, the Bourne Again SHell.

Bash is free software; you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation; either version 2, or (at your option) any later version.

Bash is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details.

You should have received a copy of the GNU General Public License with your Debian GNU/Linux system, in /usr/share/common-licenses/GPL, or with the Debian GNU/Linux hello source package as the file COPYING. If not, write

to the Free Software Foundation, Inc., 59 Temple Place, Suite 330, Boston, MA 02111 USA.

1.3 debianutils 4.8.4

1.3.1 Available under license :

This is the Debian GNU/Linux package debianutils.

It is an original Debian package. Programs in it were maintained by Guy Maor <maor@debian.org>, and are now maintained by Clint Adams <schizo@debian.org>.

All its programs except savelog, and which may be redistributed under the terms of the GNU GPL, Version 2 or later, found on Debian systems in the file /usr/share/common-licenses/GPL.

which is in the public domain.

savelog may be redistributed under the following terms: (The rest of this file consists of savelog's distribution terms.)

SMAIL GENERAL PUBLIC LICENSE
(Clarified 11 Feb 1988)

Copyright (C) 1988 Landon Curt Noll & Ronald S. Karr
Copyright (C) 1992 Ronald S. Karr
Copyleft (GNU) 1988 Landon Curt Noll & Ronald S. Karr

Everyone is permitted to copy and distribute verbatim copies of this license, but changing it is not allowed. You can also use this wording to make the terms for other programs.

The license agreements of most software companies keep you at the mercy of those companies. By contrast, our general public license is intended to give everyone the right to share SMAIL. To make sure that you get the rights we want you to have, we need to make restrictions that forbid anyone to deny you these rights or to ask you to surrender the rights. Hence this license agreement.

Specifically, we want to make sure that you have the right to give away copies of SMAIL, that you receive source code or else can get it if you want it, that you can change SMAIL or use pieces of it in new free programs, and that you know you can do these things.

To make sure that everyone has such rights, we have to forbid you to deprive anyone else of these rights. For example, if you distribute copies of SMAIL, you must give the recipients all the rights that you have. You must make sure that they, too, receive or can get the source code. And you must tell them their rights.

Also, for our own protection, we must make certain that everyone finds out that there is no warranty for SMAIL. If SMAIL is modified by someone else and passed on, we want its recipients to know that what they have is not what we distributed, so that any problems introduced by others will not reflect on our reputation.

Therefore we (Landon Curt Noll and Ronald S. Karr) make the following terms which say what you must do to be allowed to distribute or change SMAIL.

COPYING POLICIES

1. You may copy and distribute verbatim copies of SMAIL source code as you receive it, in any medium, provided that you conspicuously and

appropriately publish on each copy a valid copyright notice "Copyright (C) 1988 Landon Curt Noll & Ronald S. Karr" (or with whatever year is appropriate); keep intact the notices on all files that refer to this License Agreement and to the absence of any warranty; and give any other recipients of the SMAIL program a copy of this License Agreement along with the program. You may charge a distribution fee for the physical act of transferring a copy.

2. You may modify your copy or copies of SMAIL or any portion of it, and copy and distribute such modifications under the terms of Paragraph 1 above, provided that you also do the following:

a) cause the modified files to carry prominent notices stating that you changed the files and the date of any change; and

b) cause the whole of any work that you distribute or publish, that in whole or in part contains or is a derivative of SMAIL or any part thereof, to be licensed at no charge to all third parties on terms identical to those contained in this License Agreement (except that you may choose to grant more extensive warranty protection to some or all third parties, at your option).

c) You may charge a distribution fee for the physical act of transferring a copy, and you may at your option offer warranty protection in exchange for a fee.

Mere

aggregation of another unrelated program with this program (or its derivative) on a volume of a storage or distribution medium does not bring the other program under the scope of these terms.

3. You may copy and distribute SMAIL (or a portion or derivative of it, under Paragraph 2) in object code or executable form under the terms of Paragraphs 1 and 2 above provided that you also do one of the following:

a) accompany it with the complete corresponding machine-readable source code, which must be distributed under the terms of Paragraphs 1 and 2 above; or,

b) accompany it with a written offer, valid for at least three years, to give any third party free (except for a nominal shipping charge) a complete machine-readable copy of the corresponding source code, to be distributed under the terms of Paragraphs 1 and 2 above; or,

c) accompany it with the information you received as to where the corresponding source code may be obtained. (This

alternative is

allowed only for non-commercial distribution and only if you received the program in object code or executable form alone.)

For an executable file, complete source code means all the source code for all modules it contains; but, as a special exception, it need not include source code for modules which are standard libraries that accompany the operating system on which the executable file runs.

4. You may not copy, sublicense, distribute or transfer SMAIL except as expressly provided under this License Agreement. Any attempt otherwise to copy, sublicense, distribute or transfer SMAIL is void and your rights to use the program under this License agreement shall be automatically terminated. However, parties who have received computer software programs from you with this License Agreement will not have their licenses terminated so long as such parties remain in full compliance.

5. If you wish to incorporate parts of SMAIL into other free programs whose distribution conditions are different, write to Landon Curt Noll & Ronald S. Karr via the Free Software Foundation at 51 Franklin St, Fifth Floor, Boston, MA 02110-1301, USA. We have not yet worked out a simple rule that can be stated here, but we will often permit this. We will be guided by the two goals of preserving the free status of all derivatives of our free software and of promoting the sharing and reuse of software.

Your comments and suggestions about our licensing policies and our software are welcome! This contract was based on the contract made by the Free Software Foundation. Please contact the Free Software Foundation, Inc., 51 Franklin St, Fifth Floor, Boston, MA 02110-1301, USA, or call (617) 542-5942 for details on copylefted material in general.

NO WARRANTY

BECAUSE SMAIL IS LICENSED FREE OF CHARGE, WE PROVIDE ABSOLUTELY NO WARRANTY, TO THE EXTENT PERMITTED BY APPLICABLE STATE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING, LANDON CURT NOLL & RONALD S.

KARR AND/OR

OTHER PARTIES PROVIDE SMAIL "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF SMAIL IS WITH YOU. SHOULD SMAIL PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW WILL LANDON CURT NOLL &

RONALD S. KARR AND/OR ANY OTHER PARTY WHO MAY MODIFY AND REDISTRIBUTE
SMAIL AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY
LOST PROFITS, LOST MONIES, OR OTHER SPECIAL, INCIDENTAL OR
CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE
(INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED
INACCURATE OR LOSSES SUSTAINED BY THIRD PARTIES OR A FAILURE OF THE
PROGRAM TO OPERATE WITH ANY OTHER PROGRAMS) SMAIL, EVEN IF YOU HAVE
BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES, OR FOR ANY CLAIM BY
ANY
OTHER PARTY.

1.4 diffutils 3.6-1

1.4.1 Available under license :

This is the Debian prepackaged version of the GNU diffutils package.
GNU `diff` was written by Mike Haertel, David Hayes, Richard Stallman,
Len Tower, and Paul Eggert. Wayne Davison designed and implemented
the unified output format. GNU `diff3` was written by Randy Smith.
GNU `sdiff` was written by Thomas Lord. GNU `cmp` was written by
Torbjorn Granlund and David MacKenzie.

The source for this release was obtained from

<http://ftp.gnu.org/gnu/diffutils/diffutils-3.6.tar.xz>

Program copyright and license:

=====

Copyright (C) 1988-1996, 1998, 2001-2002, 2004, 2006-2007, 2009-2013, 2015-2017
Free Software Foundation, Inc.

This program is free software: you can redistribute it and/or modify
it under the terms of the GNU General Public License as published by
the Free Software Foundation, either version 3 of the License, or
(at your option) any later version.

This program is distributed in the hope that it will be useful,
but WITHOUT ANY WARRANTY; without
even the implied warranty of
MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
GNU General Public License for more details.

On Debian systems, the complete text of the GNU General Public License
may be found in `/usr/share/common-licenses/GPL'.

Manual copyright and license:

=====
Copyright (C) 1992-1994, 1998, 2001-2002, 2004, 2006, 2009-2017 Free Software Foundation, Inc.

Permission is granted to copy, distribute and/or modify this document under the terms of the GNU Free Documentation License, Version 1.3 or any later version published by the Free Software Foundation; with no Invariant Sections, no Front-Cover Texts, and no Back-Cover Texts.

On Debian systems, the complete text of the GNU Free Documentation License may be found in ``usr/share/common-licenses/GFDL'`.

1.5 hostname 3.20

1.5.1 Available under license :

This package was written by Peter Tobias <tobias@et-inf.fho-emden.de> on Thu, 16 Jan 1997 01:00:34 +0100.

License:

Copyright (C) 2009 Michael Meskes <meskes@debian.org>
Copyright (C) 2004-2005 Graham Wilson <graham@debian.org>
Copyright (C) 1997 Bernd Eckenfels
Copyright (C) 1997 Peter Tobias <tobias@et-inf.fho-emden.de>
Copyright (C) 1996 Free Software Foundation, Inc.

This program is free software; you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation; version 2 of the License.

This program is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details.

You should have received a copy of the GNU General Public License along with this program; if not, write to the Free Software Foundation, Inc., 51 Franklin St, Fifth Floor, Boston, MA 02110-1301 USA

On Debian systems, the complete text of the GNU General Public License can be found in `/usr/share/common-licenses/GPL-2` file.

`hostname --` set the host name or show the host/domain name

Copyright (C) 1994-1997 Peter Tobias <tobias@et-inf.fho-emden.de>
2009- Michael Meskes <meskes@debian.org>

This program is free software; you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation; either version 2, or (at your option) any later version.

This program is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details.

You should have received a copy of the GNU General Public License along with this program; if not, write to the Free Software Foundation, Inc., 675 Mass Ave, Cambridge, MA 02139, USA.

1.6 libffi 3.2.1-8

1.6.1 Available under license :

This package was debianized by Matthias Klose <doko@debian.org> on Mon, 10 Mar 2008 05:46:40 +0000.

It was downloaded from <ftp://sourceware.org/pub/libffi/>

Upstream Authors:

Anthony Green <green@redhat.com>

GCC developers

See the README and below in the list of copyright holders for a more complete list.

Copyright:

Copyright (c) 1996-2011 Red Hat, Inc.

Copyright (C) 1996-2011 Anthony Green

Copyright (C) 1996-2010 Free Software Foundation, Inc

Copyright (c) 2003, 2004, 2006, 2007, 2008 Kaz Kojima

Copyright (c) 2010, 2011, Plausible Labs Cooperative , Inc.

Copyright (c) 2010 CodeSourcery

Copyright (c) 1998 Andreas Schwab

Copyright (c) 2000 Hewlett Packard Company

Copyright (c) 2009 Bradley Smith

Copyright (c) 2008 David Daney

Copyright (c) 2004 Simon Posnjak

Copyright (c) 2005 Axis Communications AB

Copyright (c) 1998 Cygnus Solutions

Copyright (c) 2004 Renesas Technology

Copyright (c) 2002, 2007 Bo Thorsen

<bo@suse.de>

Copyright (c) 2002 Ranjit Mathew
Copyright (c) 2002 Roger Sayle
Copyright (c) 2000, 2007 Software AG
Copyright (c) 2003 Jakub Jelinek
Copyright (c) 2000, 2001 John Hornkvist
Copyright (c) 1998 Geoffrey Keating
Copyright (c) 2008 Bjrn Knig

License:

libffi - Copyright (c) 1996-2010 Red Hat, Inc and others.
See source files for details.

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the ``Software''), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE
IS PROVIDED ``AS IS'', WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT.
IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY
CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT,
TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE
SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

Documentation:

Permission is granted to copy, distribute and/or modify this document under the terms of the GNU General Public License as published by the Free Software Foundation; either version 2, or (at your option) any later version. A copy of the license is included in the section entitled ``GNU General Public License''.

doc/*:

Permission is granted to copy, distribute and/or modify this document under the terms of the GNU General Public License as published by the Free Software Foundation; either version 2, or (at your option) any later version. A copy of the license is included in the section entitled ``GNU General Public License''.

On Debian GNU/Linux systems, the complete text of the GNU General Public License is in `/usr/share/common-licenses/GPL`.

The Debian packaging is (C) 2008, 2011 Matthias Klose <doko@debian.org> and is licensed under the GPL, see `/usr/share/common-licenses/GPL`.

1.7 sensible-utils 0.0.12

1.7.1 Available under license :

Format: <https://www.debian.org/doc/packaging-manuals/copyright-format/1.0/>

Upstream-Name: sensible-utils

Upstream-Contact: Anibal Monsalve Salazar <anibal@debian.org>

Source: <https://alioth.debian.org/projects/collab-maint/sensible-utils.git>

Files: *

Copyright: 2002-2009, Clint Adams <schizo@debian.org>

2010- Anibal Monsalve Salazar <anibal@debian.org>

2012, David Prvot <taffit@debian.org>

2013, Thorsten Glaser

2017, Jrmmy Bobbio

2017, Ximin Luo

2017- Bastien Roucaris <rouca@debian.org>

License: GPL-2+

Files: sensible-editor*

Copyright: 1997, Guy Maor

2002, 2004, 2006, Clint Adams

2010- Anibal Monsalve Salazar <anibal@debian.org>

License: GPL-2+

Files: sensible-pager*

Copyright: 1997, 1998, Guy Maor

2004, Clint Adams

2010- Anibal Monsalve Salazar <anibal@debian.org>

License: GPL-2+

Files: sensible-browser*

Copyright: 2002, Joey Hess

2003, 2007, 2008, Clint Adams

2010- Anibal Monsalve Salazar <anibal@debian.org>

License: GPL-2+

Files: select-editor*

Copyright:

2009, Dustin Kirkland <kirkland@canonical.com>.

2010- Anibal Monsalve Salazar <anibal@debian.org>

License: GPL-2+

Files: man/Makefile.am

man/utf8toman.sed

Copyright: 2012-2017, Guillaume Jover

License: GPL-2+

Comment: Part of this are copied from dpkg

Files: man/po4a/cs*

Copyright: 2012, Michal Simunek

License: GPL-2+

Files: man/po4a/de*

Copyright: 2011, Helge Kreutzmann <debian@helgefjell.de>

License: GPL-2+

Files: man/po4a/fr*

Copyright: Nicolas Francois <nicolas.francois@centraliens.net>

License: GPL-2+

Files: man/po4a/es*

Copyright: 2010-2012, Omar Campagne

License: GPL-2+

Files: man/po4a/it*

Copyright: 2012, Beatrice Torracca

License: GPL-2+

Files: man/po4a/ja*

Copyright: 2010, Kurasawa Nozomu

License: GPL-2+

Files: man/po4a/pl*

Copyright: 2004, 2010, Robert Luberda <robert@debian.org>.

License: GPL-2+

Files: man/po4a/pt*

Copyright: 2014, Amrico Monteiro <a_monteiro@gmx.com>

License: GPL-2+

Files: aclocal.m4

Copyright: 1996-2017, Free Software Foundation,
Inc.

License: All-permissive

Files: *Makefile.in

Copyright: 1994-2017, Free Software Foundation, Inc.

License: All-permissive

Files: configure

Copyright: 1992-1996, 1998-2012, Free Software Foundation, Inc.

License: configure

This configure script is free software; the Free Software Foundation gives unlimited permission to copy, distribute and modify it.

Files: build-aux/missing

Copyright: 1996-2014, Free Software Foundation, Inc.

License: GPL-2+

Files: build-aux/install-sh

Copyright: 1994 X Consortium

License: installsh

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

.

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE X CONSORTIUM BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

.

Except as contained in this notice, the name of the X Consortium shall not be used in advertising or otherwise to promote the sale, use or other dealings in this Software without prior written authorization from the X Consortium.

.

FSF changes to this file are in the public domain.

License: GPL-2+

This program is free software; you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation; either version 2 of the License, or (at your option) any later version.

.

This program is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of

MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details.

You should have received a copy of the GNU General Public License along with this program; if not, write to the Free Software Foundation, Inc., 51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA.

On Debian systems, the full text of the GNU General Public License version 2 can be found in the file `/usr/share/common-licenses/GPL-2`.

License: All-permissive

This file is free software; the Free Software Foundation gives unlimited permission to copy and/or distribute it, with or without modifications, as long as this notice is preserved.

This program is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY, to the extent permitted by law; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.

1.8 adduser 3.116ubuntu1

1.8.1 Available under license :

This package was first put together by Ian Murdock <imurdock@debian.org> and was maintained by Steve Phillips <sjp@cvfn.org> from sources written for the Debian Project by Ian Murdock, Ted Hajek <tedhajek@boombox.micro.umn.edu>, and Sven Rudolph <sr1@inf.tu-dresden.de>.

Since Nov 27 1996, it was maintained by Guy Maor <maor@debian.org>. He rewrote most of it.

Since May 20 2000, it is maintained by Roland Buaerschmidt <rb@debian.org>.

Since March 24 2004, it is maintained by Roland Buaerschmidt <rb@debian.org>, and co-maintained by Marc Haber <mh+debian-packages@zugschlus.de>

Since 23 Oct 2005, it has been maintained by Joerg Hoh <joerg@joerghoh.de>

Since June 2006, it has been maintained by Stephen Gran <sgran@debian.org>

deluser is Copyright (C) 2000 Roland Buaerschmidt <rb@debian.org> and based on the source code of adduser.

adduser is Copyright (C) 1997, 1998, 1999 Guy Maor <maor@debian.org>.
adduser is Copyright (C) 1995 Ted Hajek <tedhajek@boombox.micro.umn.edu>
with portions
Copyright (C) 1994 Debian Association, Inc.

The examples directory has been contributed by John Zaitseff, and is
GPL V2 as well.

This program is free software; you can redistribute it and/or modify
it under the terms of the GNU General Public License as published by
the Free Software Foundation; either version 2 of the License, or
(at your option) any later version.

This program is distributed in the hope that it will be useful,
but WITHOUT ANY WARRANTY; without even the implied warranty of
MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
GNU General Public License for more details.

You should have received a copy of the GNU General Public License
along with this program; if not, write to the
Free Software Foundation, Inc.,
51 Franklin St, Fifth Floor, Boston, MA 02110-1301, USA.

On Debian GNU/Linux systems, the complete text of the GNU General
Public License can be found in ``usr/share/common-licenses/GPL-2'`.

1.9 attr 2.4.47-2build1

1.9.1 Available under license :

This package was debianized by Nathan Scott nathans@debian.org on
Sun, 19 Nov 2000 07:37:09 -0500.

It can be downloaded from <ftp://oss.sgi.com/projects/xfs/download/>

Copyright:

Copyright (C) 2001-2002 Silicon Graphics, Inc. All Rights Reserved.
Copyright (C) 2001 Andreas Gruenbacher.

You are free to distribute this software under Version 2.1
of the GNU Lesser General Public License.
On Debian systems, refer to `/usr/share/common-licenses/LGPL-2.1`
for the complete text of the GNU Lesser General Public License.

Certain components (as annotated in the source) are licensed
under version 2 of the terms of the GNU General Public License.

On Debian systems, the complete text of the GNU General Public License can be found in /usr/share/common-licenses/GPL file. Most components of the "attr" package are licensed under Version 2.1 of the GNU Lesser General Public License (see below). below.

Some components (as annotated in the source) are licensed under Version 2 of the GNU General Public License (see COPYING).

GNU LESSER GENERAL PUBLIC LICENSE

Version 2.1, February 1999

Copyright (C) 1991, 1999 Free Software Foundation, Inc.
51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA
Everyone is permitted to copy and distribute verbatim copies of this license document, but changing it is not allowed.

[This is the first released version of the Lesser GPL. It also counts as the successor of the GNU Library Public License, version 2, hence the version number 2.1.]

Preamble

The licenses for most software are designed to take away your freedom to share and change it. By contrast, the GNU General Public Licenses are intended to guarantee your freedom to share and change free software--to make sure the software is free for all its users.

This license, the Lesser General Public License, applies to some specially designated software packages--typically libraries--of the Free Software Foundation and other authors who decide to use it. You can use it too, but we suggest you first think carefully about whether this license or the ordinary General Public License is the better strategy to use in any particular case, based on the explanations below.

When we speak of free software, we are referring to freedom of use, not price. Our General Public Licenses are designed to make sure that you have the freedom to distribute copies of free software (and charge for this service if you wish); that you receive source code or can get it if you want it; that you can change the software and use pieces of it in new free programs; and that you are informed that you can do these things.

To protect your rights, we need to make restrictions

that forbid distributors to deny you these rights or to ask you to surrender these rights. These restrictions translate to certain responsibilities for you if you distribute copies of the library or if you modify it.

For example, if you distribute copies of the library, whether gratis or for a fee, you must give the recipients all the rights that we gave you. You must make sure that they, too, receive or can get the source code. If you link other code with the library, you must provide complete object files to the recipients, so that they can relink them with the library after making changes to the library and recompiling it. And you must show them these terms so they know their rights.

We protect your rights with a two-step method: (1) we copyright the library, and (2) we offer you this license, which gives you legal permission to copy, distribute and/or modify the library.

To protect each distributor, we want to make it very clear that there is no warranty for the free library. Also, if the library is modified by someone else and passed on, the recipients should know that what they have is not the original version, so that the original author's reputation will not be affected by problems that might be introduced by others.

Finally, software patents pose a constant threat to the existence of any free program. We wish to make sure that a company cannot effectively restrict the users of a free program by obtaining a restrictive license from a patent holder. Therefore, we insist that any patent license obtained for a version of the library must be consistent with the full freedom of use specified in this license.

Most GNU software, including some libraries, is covered by the ordinary GNU General Public License. This license, the GNU Lesser General Public License, applies to certain designated libraries, and is quite different from the ordinary General Public License. We use this license for certain libraries in order to permit linking those libraries into non-free programs.

When a program is linked with a library, whether statically or using a shared library, the combination of the two is legally speaking a combined work, a derivative of the original library. The ordinary General Public License therefore permits such linking only if the entire combination fits its criteria of freedom. The Lesser General Public License permits more lax criteria for linking other code with the library.

We call this license the "Lesser" General Public License because it does Less to protect the user's freedom than the ordinary General Public License. It also provides other free software developers Less of an advantage over competing non-free programs. These disadvantages are the reason we use the ordinary General Public License for many libraries. However, the Lesser license provides advantages in certain special circumstances.

For example, on rare occasions, there may be a special need to encourage the widest possible use of a certain library, so that it becomes a de-facto standard. To achieve this, non-free programs must be allowed to use the library. A more frequent case is that a free library does the same job as widely used non-free libraries. In this case, there is little to gain by limiting the free library to free software only, so we use the Lesser General Public License.

In other cases, permission to use a particular library in non-free programs enables a greater number of people to use a large body of free software. For example, permission to use the GNU C Library in non-free programs enables many more people to use the whole GNU operating system, as well as its variant, the GNU/Linux operating system.

Although the Lesser General Public License is Less protective of the users' freedom, it does ensure that the user of a program that is linked with the Library has the freedom and the wherewithal to run that program using a modified version of the Library.

The precise terms and conditions for copying, distribution and modification follow. Pay close attention to the difference between a "work based on the library" and a "work that uses the library". The former contains code derived from the library, whereas the latter must be combined with the library in order to run.

GNU LESSER GENERAL PUBLIC LICENSE

TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

0. This License Agreement applies to any software library or other program which contains a notice placed by the copyright holder or other authorized party saying it may be distributed under the terms of this Lesser General Public License (also called "this License"). Each licensee is addressed as "you".

A "library" means a collection of software functions and/or data prepared so as to be conveniently linked with application programs (which use some of those functions and data) to form executables.

The "Library", below, refers to any such software library or work which has been distributed under these terms. A "work based on the Library" means either the Library or any derivative work under copyright law: that is to say, a work containing the Library or a portion of it, either verbatim or with modifications and/or translated straightforwardly into another language. (Hereinafter, translation is included without limitation in the term "modification".)

"Source code" for a work means the preferred form of the work for making modifications to it. For a library, complete source code means all the source code for all modules it contains, plus any associated interface definition files, plus the scripts used to control compilation and installation of the library.

Activities other than copying, distribution and modification are not covered by this License; they are outside its scope. The act of running a program using the Library is not restricted, and output from such a program is covered only if its contents constitute a work based on the Library (independent of the use of the Library in a tool for writing it). Whether that is true depends on what the Library does and what the program that uses the Library does.

1. You may copy and distribute verbatim copies of the Library's complete source code as you receive it, in any medium, provided that you conspicuously and appropriately publish on each copy an appropriate copyright notice and disclaimer of warranty; keep intact all the notices that refer to this License and to the absence of any warranty; and distribute a copy of this License along with the Library.

You may charge a fee for the physical act of transferring a copy, and you may at your option offer warranty protection in exchange for a fee.

2. You may modify your copy or copies of the Library or any portion of it, thus forming a work based on the Library, and copy and distribute such modifications or work under the terms of Section 1 above, provided that you also meet all of these conditions:

a) The modified work must itself be a software library.

b) You must cause the files modified to carry prominent notices stating that you changed the files and the date of any change.

c) You must cause the whole of the work to be licensed at no charge to all third parties under the terms of this License.

d) If a facility in the modified Library refers to a function or a table of data to be supplied by an application program that uses the facility, other than as an argument passed when the facility is invoked, then you must make a good faith effort to ensure that, in the event an application does not supply such function or table, the facility still operates, and performs whatever part of its purpose remains meaningful.

(For example, a function in a library to compute square roots has a purpose that is entirely well-defined independent of the application. Therefore, Subsection 2d requires that any application-supplied function or table used by this function must be optional: if the application does not supply it, the square root function must still compute square roots.)

These requirements apply to the modified work as a whole. If identifiable sections of that work are not derived from the Library, and can be reasonably considered independent and separate works in themselves, then this License, and its terms, do not apply to those sections when you distribute them as separate works. But when you distribute the same sections as part of a whole which is a work based on the Library, the distribution of the whole must be on the terms of this License, whose permissions for other licensees extend to the entire whole, and thus to each and every part regardless of who wrote it.

Thus, it is not the intent of this section to claim rights or contest your rights to work written entirely by you; rather, the intent is to exercise the right to control the distribution of derivative or collective works based on the Library.

In addition, mere aggregation of another work not based on the Library with the Library (or with a work based on the Library) on a volume of a storage or distribution medium does not bring the other work under the scope of this License.

3. You may opt to apply the terms of the ordinary GNU General Public License instead of this License to a given copy of the Library. To do this, you must alter all the notices that refer to this License, so that they refer to the ordinary GNU General Public License, version 2, instead of to this License. (If a newer version than version 2 of the ordinary GNU General Public License has appeared, then you can specify that version instead if you wish.) Do not make any other change in

these notices.

Once this change is made in a given copy, it is irreversible for that copy, so the ordinary GNU General Public License applies to all subsequent copies and derivative works made from that copy.

This option is useful when you wish to copy part of the code of the Library into a program that is not a library.

4. You may copy and distribute the Library (or a portion or derivative of it, under Section 2) in object code or executable form under the terms of Sections 1 and 2 above provided that you accompany it with the complete corresponding machine-readable source code, which must be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange.

If distribution of object code is made by offering access to copy from a designated place, then offering equivalent access to copy the source code from the same place satisfies the requirement to distribute the source code, even though third parties are not compelled to copy the source along with the object code.

5. A program that contains no derivative of any portion of the Library, but is designed to work with the Library by being compiled or linked with it, is called a "work that uses the Library". Such a work, in isolation, is not a derivative work of the Library, and therefore falls outside the scope of this License.

However, linking a "work that uses the Library" with the Library creates an executable that is a derivative of the Library (because it contains portions of the Library), rather than a "work that uses the library". The executable is therefore covered by this License. Section 6 states terms for distribution of such executables.

When a "work that uses the Library" uses material from a header file that is part of the Library, the object code for the work may be a derivative work of the Library even though the source code is not. Whether this is true is especially significant if the work can be linked without the Library, or if the work is itself a library. The threshold for this to be true is not precisely defined by law.

If such an object file uses only numerical parameters, data structure layouts and accessors, and small macros and small inline functions (ten lines or less in length), then the use of the object file

is unrestricted, regardless of whether it is legally a derivative work. (Executables containing this object code plus portions of the Library will still fall under Section 6.)

Otherwise, if the work is a derivative of the Library, you may distribute the object code for the work under the terms of Section 6. Any executables containing that work also fall under Section 6, whether or not they are linked directly with the Library itself.

6. As an exception to the Sections above, you may also combine or link a "work that uses the Library" with the Library to produce a work containing portions of the Library, and distribute that work under terms of your choice, provided that the terms permit modification of the work for the customer's own use and reverse engineering for debugging such modifications.

You must give prominent notice with each copy of the work that the Library is used in it and that the Library and its use are covered by this License. You must supply a copy of this License. If the work during execution displays copyright notices, you must include the copyright notice for the Library among them, as well as a reference directing the user to the copy of this License. Also, you must do one of these things:

a) Accompany the work with the complete corresponding machine-readable source code for the Library including whatever changes were used in the work (which must be distributed under Sections 1 and 2 above); and, if the work is an executable linked with the Library, with the complete machine-readable "work that uses the Library", as object code and/or source code, so that the user can modify the Library and then relink to produce a modified executable containing the modified Library. (It is understood that the user who changes the contents of definitions files in the Library will not necessarily be able to recompile the application to use the modified definitions.)

b) Use a suitable shared library mechanism for linking with the Library. A suitable mechanism is one that (1) uses at run time a copy of the library already present on the user's computer system, rather than copying library functions into the executable, and (2) will operate properly with a modified version of the library, if the user installs one, as long as the modified version is interface-compatible with the version that the work was made with.

c) Accompany the work with a written offer, valid for at least three years, to give the same user the materials

specified in Subsection 6a, above, for a charge no more than the cost of performing this distribution.

d) If distribution of the work is made by offering access to copy from a designated place, offer equivalent access to copy the above specified materials from the same place.

e) Verify that the user has already received a copy of these materials or that you have already sent this user a copy.

For an executable, the required form of the "work that uses the Library" must include any data and utility programs needed for reproducing the executable from it. However, as a special exception, the materials to be distributed need not include anything that is normally distributed (in either source or binary form) with the major components (compiler, kernel, and so on) of the operating system on which the executable runs, unless that component itself accompanies the executable.

It may happen that this requirement contradicts the license restrictions of other proprietary libraries that do not normally accompany the operating system. Such a contradiction means you cannot use both them and the Library together in an executable that you distribute.

7. You may place library facilities that are a work based on the Library side-by-side in a single library together with other library facilities not covered by this License, and distribute such a combined library, provided that the separate distribution of the work based on the Library and of the other library facilities is otherwise permitted, and provided that you do these two things:

a) Accompany the combined library with a copy of the same work based on the Library, uncombined with any other library facilities. This must be distributed under the terms of the Sections above.

b) Give prominent notice with the combined library of the fact that part of it is a work based on the Library, and explaining where to find the accompanying uncombined form of the same work.

8. You may not copy, modify, sublicense, link with, or distribute the Library except as expressly provided under this License. Any attempt otherwise to copy, modify, sublicense, link with, or distribute the Library is void, and will automatically terminate your rights under this License. However, parties who have received copies, or rights, from you under this License will not have their licenses

terminated so long as such parties remain in full compliance.

9. You are not required to accept this License, since you have not signed it. However, nothing else grants you permission to modify or distribute the Library or its derivative works. These actions are prohibited by law if you do not accept this License. Therefore, by modifying or distributing the Library (or any work based on the Library), you indicate your acceptance of this License to do so, and all its terms and conditions for copying, distributing or modifying the Library or works based on it.

10. Each time you redistribute the Library (or any work based on the Library), the recipient automatically receives a license from the original licensor to copy, distribute, link with or modify the Library subject to these terms and conditions. You may not impose any further restrictions on the recipients' exercise of the rights granted herein. You are not responsible for enforcing compliance by third parties with this License.

11. If, as a consequence of a court judgment or allegation of patent infringement or for any other reason (not limited to patent issues), conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot distribute so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not distribute the Library at all. For example, if a patent license would not permit royalty-free redistribution of the Library by all those who receive copies directly or indirectly through you, then the only way you could satisfy both it and this License would be to refrain entirely from distribution of the Library.

If any portion of this section is held invalid or unenforceable under any particular circumstance, the balance of the section is intended to apply, and the section as a whole is intended to apply in other circumstances.

It is not the purpose of this section to induce you to infringe any patents or other property right claims or to contest validity of any such claims; this section has the sole purpose of protecting the integrity of the free software distribution system which is implemented by public license practices. Many people have made generous contributions to the wide range of software distributed through that system in reliance on consistent application of that system; it is up to the author/donor to decide if he or she is willing to distribute software through any other system and a licensee cannot

impose that choice.

This section is intended to make thoroughly clear what is believed to be a consequence of the rest of this License.

12. If the distribution and/or use of the Library is restricted in certain countries either by patents or by copyrighted interfaces, the original copyright holder who places the Library under this License may add an explicit geographical distribution limitation excluding those countries, so that distribution is permitted only in or among countries not thus excluded. In such case, this License incorporates the limitation as if written in the body of this License.

13. The Free Software Foundation may publish revised and/or new versions of the Lesser General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Library specifies a version number of this License which applies to it and "any later version", you have the option of following the terms and conditions either of that version or of any later version published by the Free Software Foundation. If the Library does not specify a license version number, you may choose any version ever published by the Free Software Foundation.

14. If you wish to incorporate parts of the Library into other free programs whose distribution conditions are incompatible with these, write to the author to ask for permission. For software which is copyrighted by the Free Software Foundation, write to the Free Software Foundation; we sometimes make exceptions for this. Our decision will be guided by the two goals of preserving the free status of all derivatives of our free software and of promoting the sharing and reuse of software generally.

NO WARRANTY

15. BECAUSE THE LIBRARY IS LICENSED FREE OF CHARGE, THERE IS NO WARRANTY FOR THE LIBRARY, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE LIBRARY "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE LIBRARY IS WITH YOU. SHOULD THE LIBRARY PROVE DEFECTIVE, YOU ASSUME THE

COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

16. IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY AND/OR REDISTRIBUTE THE LIBRARY AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE LIBRARY (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE LIBRARY TO OPERATE WITH ANY OTHER SOFTWARE), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Libraries

If you develop a new library, and you want it to be of the greatest possible use to the public, we recommend making it free software that everyone can redistribute and change. You can do so by permitting redistribution under these terms (or, alternatively, under the terms of the ordinary General Public License).

To apply these terms, attach the following notices to the library. It is safest to attach them to the start of each source file to most effectively convey the exclusion of warranty; and each file should have at least the "copyright" line and a pointer to where the full notice is found.

<one line to give the library's name and a brief idea of what it does.>
Copyright (C) <year> <name of author>

This library is free software; you can redistribute it and/or modify it under the terms of the GNU Lesser General Public License as published by the Free Software Foundation; either version 2.1 of the License, or (at your option) any later version.

This library is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU Lesser General Public License for more details.

You should have received a copy of the GNU Lesser General Public License along with this library; if not, write to the Free Software Foundation, Inc., 51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA

Also add information on how to contact you by electronic and paper mail.

You should also get your employer (if you work as a programmer) or your school, if any, to sign a "copyright disclaimer" for the library, if necessary. Here is a sample; alter the names:

Yoyodyne, Inc., hereby disclaims all copyright interest in the library `Frob' (a library for tweaking knobs) written by James Random Hacker.

<signature of Ty Coon>, 1 April 1990
Ty Coon, President of Vice

That's all there is to it!
Most components of the "attr" package are licensed under Version 2.1 of the GNU Lesser General Public License (see COPYING.LGPL).

Some components (as annotated in the source) are licensed under Version 2 of the GNU General Public License (see below),

GNU GENERAL PUBLIC LICENSE
Version 2, June 1991

Copyright (C) 1989, 1991 Free Software Foundation, Inc.,
51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA
Everyone is permitted to copy and distribute verbatim copies of this license document, but changing it is not allowed.

Preamble

The licenses for most software are designed to take away your freedom to share and change it. By contrast, the GNU General Public License is intended to guarantee your freedom to share and change free software--to make sure the software is free for all its users. This General Public License applies to most of the Free Software Foundation's software and to any other program whose authors commit to using it. (Some other Free Software Foundation software is covered by the GNU Lesser General Public License instead.) You can apply it to your programs, too.

When we speak of free software, we are referring to freedom, not price. Our General Public Licenses are designed to make sure that you have the freedom to distribute copies of free software (and charge for this service if you wish), that you receive source code or can get it if you want it, that you can change the software or use pieces of it in new free programs; and that you know you can do these things.

To protect your rights, we need to make restrictions that forbid anyone to deny you these rights or to ask you to surrender the rights. These restrictions translate to certain responsibilities for you if you distribute copies of the software, or if you modify it.

For example, if you distribute copies of such a program, whether gratis or for a fee, you must give the recipients all the rights that you have. You must make sure that they, too, receive or can get the source code. And you must show them these terms so they know their rights.

We protect your rights with two steps: (1) copyright the software, and (2) offer you this license which gives you legal permission to copy, distribute and/or modify the software.

Also, for each author's protection and ours, we want to make certain that everyone understands that there is no warranty for this free software. If the software is modified by someone else and passed on, we want its recipients to know that what they have is not the original, so that any problems introduced by others will not reflect on the original authors' reputations.

Finally, any free program is threatened constantly by software patents. We wish to avoid the danger that redistributors of a free program will individually obtain patent licenses, in effect making the program proprietary. To prevent this, we have made it clear that any patent must be licensed for everyone's free use or not licensed at all.

The precise terms and conditions for copying, distribution and modification follow.

GNU GENERAL PUBLIC LICENSE TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

0. This License applies to any program or other work which contains a notice placed by the copyright holder saying it may be distributed under the terms of this General Public License. The "Program", below, refers to any such program or work, and a "work based on the Program" means either the Program or any derivative work under copyright law: that is to say, a work containing the Program or a portion of it, either verbatim or with modifications and/or translated into another language. (Hereinafter, translation is included without limitation in the term "modification".) Each licensee is addressed as "you".

Activities other than copying, distribution and modification are not covered by this License; they are outside its

scope. The act of running the Program is not restricted, and the output from the Program is covered only if its contents constitute a work based on the Program (independent of having been made by running the Program). Whether that is true depends on what the Program does.

1. You may copy and distribute verbatim copies of the Program's source code as you receive it, in any medium, provided that you conspicuously and appropriately publish on each copy an appropriate copyright notice and disclaimer of warranty; keep intact all the notices that refer to this License and to the absence of any warranty; and give any other recipients of the Program a copy of this License along with the Program.

You may charge a fee for the physical act of transferring a copy, and you may at your option offer warranty protection in exchange for a fee.

2. You may modify your copy or copies of the Program or any portion of it, thus forming a work based on the Program, and copy and distribute such modifications or work under the terms of Section 1 above, provided that you also meet all of these conditions:

a) You must cause the modified files to carry prominent notices stating that you changed the files and the date of any change.

b) You must cause any work that you distribute or publish, that in whole or in part contains or is derived from the Program or any part thereof, to be licensed as a whole at no charge to all third parties under the terms of this License.

c) If the modified program normally reads commands interactively when run, you must cause it, when started running for such interactive use in the most ordinary way, to print or display an announcement including an appropriate copyright notice and a notice that there is no warranty (or else, saying that you provide a warranty) and that users may redistribute the program under these conditions, and telling the user how to view a copy of this License. (Exception: if the Program itself is interactive but does not normally print such an announcement, your work based on the Program is not required to print an announcement.)

These requirements apply to the modified work as a whole. If identifiable sections of that work are not derived from the Program, and can be reasonably considered independent and separate works in themselves, then this License, and its terms, do not apply to those sections when you distribute them as separate works. But when you

distribute the same sections as part of a whole which is a work based on the Program, the distribution of the whole must be on the terms of this License, whose permissions for other licensees extend to the entire whole, and thus to each and every part regardless of who wrote it.

Thus, it is not the intent of this section to claim rights or contest your rights to work written entirely by you; rather, the intent is to exercise the right to control the distribution of derivative or collective works based on the Program.

In addition, mere aggregation of another work not based on the Program with the Program (or with a work based on the Program) on a volume of a storage or distribution medium does not bring the other work under the scope of this License.

3. You may copy and distribute the Program (or a work based on it, under Section 2) in object code or executable form under the terms of Sections 1 and 2 above provided that you also do one of the following:

a) Accompany it with the complete corresponding machine-readable source code, which must be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange; or,

b) Accompany it with a written offer, valid for at least three years, to give any third party, for a charge no more than your cost of physically performing source distribution, a complete machine-readable copy of the corresponding source code, to be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange; or,

c) Accompany it with the information you received as to the offer to distribute corresponding source code. (This alternative is allowed only for noncommercial distribution and only if you received the program in object code or executable form with such an offer, in accord with Subsection b above.)

The source code for a work means the preferred form of the work for making modifications to it. For an executable work, complete source code means all the source code for all modules it contains, plus any associated interface definition files, plus the scripts used to control compilation and installation of the executable. However, as a special exception, the source code distributed need not include anything that is normally distributed (in either source or binary form) with the major components (compiler, kernel, and so on) of the operating system on which the executable runs, unless that

component
itself accompanies the executable.

If distribution of executable or object code is made by offering access to copy from a designated place, then offering equivalent access to copy the source code from the same place counts as distribution of the source code, even though third parties are not compelled to copy the source along with the object code.

4. You may not copy, modify, sublicense, or distribute the Program except as expressly provided under this License. Any attempt otherwise to copy, modify, sublicense or distribute the Program is void, and will automatically terminate your rights under this License. However, parties who have received copies, or rights, from you under this License will not have their licenses terminated so long as such parties remain in full compliance.

5. You are not required to accept this License, since you have not signed it. However, nothing else grants you permission to modify or distribute the Program or its derivative works. These actions are prohibited by law if you do not accept this License. Therefore, by modifying or distributing the Program (or any work based on the Program), you indicate your acceptance of this License to do so, and all its terms and conditions for copying, distributing or modifying the Program or works based on it.

6. Each time you redistribute the Program (or any work based on the Program), the recipient automatically receives a license from the original licensor to copy, distribute or modify the Program subject to these terms and conditions. You may not impose any further restrictions on the recipients' exercise of the rights granted herein. You are not responsible for enforcing compliance by third parties to this License.

7. If, as a consequence of a court judgment or allegation of patent infringement or for any other reason (not limited to patent issues), conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot distribute so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not distribute the Program at all. For example, if a patent license would not permit royalty-free redistribution of the Program by all those who receive copies directly or indirectly through you, then the only way you could satisfy both it and this License would be to refrain entirely from distribution of the Program.

If any portion of this section is held invalid or unenforceable under any particular circumstance, the balance of the section is intended to apply and the section as a whole is intended to apply in other circumstances.

It is not the purpose of this section to induce you to infringe any patents or other property right claims or to contest validity of any such claims; this section has the sole purpose of protecting the integrity of the free software distribution system, which is implemented by public license practices. Many people have made generous contributions to the wide range of software distributed through that system in reliance on consistent application of that system; it is up to the author/donor to decide if he or she is willing to distribute software through any other system and a licensee cannot impose that choice.

This section is intended to make thoroughly clear what is believed to be a consequence of the rest of this License.

8. If the distribution and/or use of the Program is restricted in certain countries either by patents or by copyrighted interfaces, the original copyright holder who places the Program under this License may add an explicit geographical distribution limitation excluding those countries, so that distribution is permitted only in or among countries not thus excluded. In such case, this License incorporates the limitation as if written in the body of this License.

9. The Free Software Foundation may publish revised and/or new versions of the General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Program specifies a version number of this License which applies to it and "any later version", you have the option of following the terms and conditions either of that version or of any later version published by the Free Software Foundation. If the Program does not specify a version number of this License, you may choose any version ever published by the Free Software Foundation.

10. If you wish to incorporate parts of the Program into other free programs whose distribution conditions are different, write to the author to ask for permission. For software which is copyrighted by the Free Software Foundation, write to the Free Software Foundation; we sometimes make exceptions for this. Our decision

will be guided by the two goals
of preserving the free status of all derivatives of our free software and
of promoting the sharing and reuse of software generally.

NO WARRANTY

11. BECAUSE THE PROGRAM IS LICENSED FREE OF CHARGE, THERE IS NO WARRANTY FOR THE PROGRAM, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE PROGRAM "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE PROGRAM IS WITH YOU. SHOULD THE PROGRAM PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

12. IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY AND/OR REDISTRIBUTE THE PROGRAM AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE PROGRAM (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE PROGRAM TO OPERATE WITH ANY OTHER PROGRAMS), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Programs

If you develop a new program, and you want it to be of the greatest possible use to the public, the best way to achieve this is to make it free software which everyone can redistribute and change under these terms.

To do so, attach the following notices to the program. It is safest to attach them to the start of each source file to most effectively convey the exclusion of warranty; and each file should have at least the "copyright" line and a pointer to where the full notice is found.

<one line to give the program's name and a brief idea of what it does.>

Copyright (C) <year> <name of author>

This program is free software; you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation; either version 2 of the License, or (at your option) any later version.

This program is distributed in the hope that it will be useful,
but WITHOUT ANY WARRANTY; without even the implied warranty of
MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
GNU General Public License for more details.

You should have received a copy of the GNU General Public License along
with this program; if not, write to the Free Software Foundation, Inc.,
51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA.

Also add information on how to contact you by electronic and paper mail.

If the program is interactive, make it output a short notice like this
when it starts
in an interactive mode:

```
Gnomovision version 69, Copyright (C) year name of author  
Gnomovision comes with ABSOLUTELY NO WARRANTY; for details type `show w'.  
This is free software, and you are welcome to redistribute it  
under certain conditions; type `show c' for details.
```

The hypothetical commands ``show w'` and ``show c'` should show the appropriate
parts of the General Public License. Of course, the commands you use may
be called something other than ``show w'` and ``show c'`; they could even be
mouse-clicks or menu items--whatever suits your program.

You should also get your employer (if you work as a programmer) or your
school, if any, to sign a "copyright disclaimer" for the program, if
necessary. Here is a sample; alter the names:

```
Yoyodyne, Inc., hereby disclaims all copyright interest in the program  
'Gnomovision' (which makes passes at compilers) written by James Hacker.
```

```
<signature of Ty Coon>, 1 April 1989  
Ty Coon, President of Vice
```

This General Public License
does not permit incorporating your program into
proprietary programs. If your program is a subroutine library, you may
consider it more useful to permit linking proprietary applications with the
library. If this is what you want to do, use the GNU Lesser General
Public License instead of this License.

1.10 base-passwd 3.5.44

1.10.1 Available under license :

Format-Specification: <http://svn.debian.org/wsvn/dep/web/deps/dep5.mdwn?op=file&rev=135>

Name: base-passwd

Maintainer: Colin Watson <cjwatson@debian.org>

Files: update-passwd.c, man/*

Copyright: Copyright 1999-2002 Wichert Akkerman <wichert@deephackmode.org>

Copyright 2002, 2003, 2004 Colin Watson <cjwatson@debian.org>

License: GPL-2

Files: passwd.master, group.master

License: PD

X-Notes: Originally written by Ian Murdock <imurdock@debian.org> and

Bruce Perens <bruce@pixar.com>.

Files: doc/*

Copyright: Copyright 2001, 2002 Joey Hess

Copyright 2002, 2003, 2004, 2005, 2007 Colin Watson

Copyright 2007 David Mandelberg

License: GPL-2

License: GPL-2

On Debian and Debian-based systems, a copy of the GNU General Public License version 2 is available in /usr/share/common-licenses/GPL-2.

GNU GENERAL PUBLIC LICENSE

Version 2, June 1991

Copyright (C) 1989, 1991 Free Software Foundation, Inc.

51 Franklin St, Fifth Floor, Boston, MA 02110-1301 USA

Everyone is permitted to copy and distribute verbatim copies of this license document, but changing it is not allowed.

Preamble

The licenses for most software are designed to take away your freedom to share and change it. By contrast, the GNU General Public License is intended to guarantee your freedom to share and change free software--to make sure the software is free for all its users. This General Public License applies to most of the Free Software Foundation's software and to any other program whose authors commit to using it. (Some other Free Software Foundation software is covered by the GNU Library General Public License instead.) You can apply it to your programs, too.

When we speak of free software, we are referring to freedom, not price. Our General Public Licenses are designed to make sure that you have the freedom to distribute copies of free software (and charge for

this service if you wish), that you receive source code or can get it if you want it, that you can change the software or use pieces of it in new free programs; and that you know you can do these things.

To protect your rights, we need to make restrictions that forbid anyone to deny you these rights or to ask you to surrender the rights. These restrictions translate to certain responsibilities for you if you distribute copies of the software, or if you modify it.

For example, if you distribute copies of such a program, whether gratis or for a fee, you must give the recipients all the rights that you have. You must make sure that they, too, receive or can get the source code. And you must show them these terms so they know their rights.

We protect your rights with two steps: (1) copyright the software, and (2) offer you this license which gives you legal permission to copy, distribute and/or modify the software.

Also, for each author's protection and ours, we want to make certain that everyone understands that there is no warranty for this free software. If the software is modified by someone else and passed on, we want its recipients to know that what they have is not the original, so that any problems introduced by others will not reflect on the original authors' reputations.

Finally, any free program is threatened constantly by software patents. We wish to avoid the danger that redistributors of a free program will individually obtain patent licenses, in effect making the program proprietary. To prevent this, we have made it clear that any patent must be licensed for everyone's free use or not licensed at all.

The precise terms and conditions for copying, distribution and modification follow.

GNU GENERAL PUBLIC LICENSE TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

0. This License applies to any program or other work which contains a notice placed by the copyright holder saying it may be distributed under the terms of this General Public License. The "Program", below, refers to any such program or work, and a "work based on the Program" means either the Program or any derivative work under copyright law: that is to say, a work containing the Program or a portion of it, either verbatim or with modifications and/or translated into another language. (Hereinafter, translation is included without limitation in

the term "modification".) Each licensee is addressed as "you".

Activities other than copying, distribution and modification are not covered by this License; they are outside its scope. The act of running the Program is not restricted, and the output from the Program is covered only if its contents constitute a work based on the Program (independent of having been made by running the Program). Whether that is true depends on what the Program does.

1. You may copy and distribute verbatim copies of the Program's source code as you receive it, in any medium, provided that you conspicuously and appropriately publish on each copy an appropriate copyright notice and disclaimer of warranty; keep intact all the notices that refer to this License and to the absence of any warranty; and give any other recipients of the Program a copy of this License along with the Program.

You may charge a fee for the physical act of transferring a copy, and you may at your option offer warranty protection in exchange for a fee.

2. You may modify your copy or copies of the Program or any portion of it, thus forming a work based on the Program, and copy and distribute such modifications or work under the terms of Section 1 above, provided that you also meet all of these conditions:

a) You must cause the modified files to carry prominent notices stating that you changed the files and the date of any change.

b) You must cause any work that you distribute or publish, that in whole or in part contains or is derived from the Program or any part thereof, to be licensed as a whole at no charge to all third parties under the terms of this License.

c) If the modified program normally reads commands interactively when run, you must cause it, when started running for such interactive use in the most ordinary way, to print or display an announcement including an appropriate copyright notice and a notice that there is no warranty (or else, saying that you provide a warranty) and that users may redistribute the program under these conditions, and telling the user how to view a copy of this License. (Exception: if the Program itself is interactive but does not normally print such an announcement, your work based on the Program is not required to print an announcement.)

These requirements apply to the modified work as a whole. If identifiable sections of that work are not derived from the Program,

and can

be reasonably considered independent and separate works in themselves, then this License, and its terms, do not apply to those sections when you distribute them as separate works. But when you distribute the same sections as part of a whole which is a work based on the Program, the distribution of the whole must be on the terms of this License, whose permissions for other licensees extend to the entire whole, and thus to each and every part regardless of who wrote it.

Thus, it is not the intent of this section to claim rights or contest your rights to work written entirely by you; rather, the intent is to exercise the right to control the distribution of derivative or collective works based on the Program.

In addition, mere aggregation of another work not based on the Program with the Program (or with a work based on the Program) on a volume of a storage or distribution medium does not bring the other work under the scope of this License.

3. You may copy and distribute the Program (or a work based on it, under Section 2) in object code or executable form under the terms of Sections 1 and 2 above provided that you also do one of the following:

a) Accompany it with the complete corresponding machine-readable source code, which must be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange; or,

b) Accompany it with a written offer, valid for at least three years, to give any third party, for a charge no more than your cost of physically performing source distribution, a complete machine-readable copy of the corresponding source code, to be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange; or,

c) Accompany it with the information you received as to the offer to distribute corresponding source code. (This alternative is allowed only for noncommercial distribution and only if you received the program in object code or executable form with such an offer, in accord with Subsection b above.)

The source code for a work means the preferred form of the work for making modifications to it. For an executable work, complete source code means all the source code for all modules it contains, plus any associated interface definition files, plus the scripts used to control compilation and installation of the executable. However, as a special exception, the source code distributed need not include

anything that is normally distributed (in either source or binary form) with the major components (compiler, kernel, and so on) of the operating system on which the executable runs, unless that component itself accompanies the executable.

If distribution of executable or object code is made by offering access to copy from a designated place, then offering equivalent access to copy the source code from the same place counts as distribution of the source code, even though third parties are not compelled to copy the source along with the object code.

4. You may not copy, modify, sublicense, or distribute the Program except as expressly provided under this License. Any attempt otherwise to copy, modify, sublicense or distribute the Program is void, and will automatically terminate your rights under this License. However, parties who have received copies, or rights, from you under this License will not have their licenses terminated so long as such parties remain in full compliance.

5. You are not required to accept this License, since you have not signed it. However, nothing else grants you permission to modify or distribute the Program or its derivative works. These actions are prohibited by law if you do not accept this License. Therefore, by modifying or distributing the Program (or any work based on the Program), you indicate your acceptance of this License to do so, and all its terms and conditions for copying, distributing or modifying the Program or works based on it.

6. Each time you redistribute the Program (or any work based on the Program), the recipient automatically receives a license from the original licensor to copy, distribute or modify the Program subject to these terms and conditions. You may not impose any further restrictions on the recipients' exercise of the rights granted herein. You are not responsible for enforcing compliance by third parties to this License.

7. If, as a consequence of a court judgment or allegation of patent infringement or for any other reason (not limited to patent issues), conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot distribute so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not distribute the Program at all. For example, if a patent license would not permit

royalty-free redistribution of the Program by all those who receive copies directly or indirectly through you, then the only way you could satisfy both it and this License would be to refrain entirely from distribution of the Program.

If any portion of this section is held invalid or unenforceable under any particular circumstance, the balance of the section is intended to apply and the section as a whole is intended to apply in other circumstances.

It is not the purpose of this section to induce you to infringe any patents or other property right claims or to contest validity of any such claims; this section has the sole purpose of protecting the integrity of the free software distribution system, which is implemented by public license practices. Many people have made generous contributions to the wide range of software distributed through that system in reliance on consistent application of that system; it is up to the author/donor to decide if he or she is willing to distribute software through any other system and a licensee cannot impose that choice.

This section is intended to make thoroughly clear what is believed to be a consequence of the rest of this License.

8. If the distribution and/or use of the Program is restricted in certain countries either by patents or by copyrighted interfaces, the original copyright holder who places the Program under this License may add an explicit geographical distribution limitation excluding those countries, so that distribution is permitted only in or among countries not thus excluded. In such case, this License incorporates the limitation as if written in the body of this License.

9. The Free Software Foundation may publish revised and/or new versions of the General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Program specifies a version number of this License which applies to it and "any later version", you have the option of following the terms and conditions either of that version or of any later version published by the Free Software Foundation. If the Program does not specify a version number of this License, you may choose any version ever published by the Free Software Foundation.

10. If you wish to incorporate parts of the Program into other free

programs whose distribution conditions are different, write to the author to ask for permission. For software which is copyrighted by the Free Software Foundation, write to the Free Software Foundation; we sometimes make exceptions for this. Our decision will be guided by the two goals of preserving the free status of all derivatives of our free software and of promoting the sharing and reuse of software generally.

NO WARRANTY

11. BECAUSE THE PROGRAM IS LICENSED FREE OF CHARGE, THERE IS NO WARRANTY FOR THE PROGRAM, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE PROGRAM "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE PROGRAM IS WITH YOU. SHOULD THE PROGRAM PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

12. IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY AND/OR REDISTRIBUTE THE PROGRAM AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE PROGRAM (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE PROGRAM TO OPERATE WITH ANY OTHER PROGRAMS), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Programs

If you develop a new program, and you want it to be of the greatest possible use to the public, the best way to achieve this is to make it free software which everyone can redistribute and change under these terms.

To do so, attach the following notices to the program. It is safest to attach them to the start of each source file to most effectively convey the exclusion of warranty; and each file should have at least the "copyright" line and a pointer to where the full notice is found.

```
<one line to give the program's name and a brief idea of what it does.>  
Copyright (C) <year> <name of author>
```

This program is free software; you can redistribute it and/or modify

it under the terms of the GNU General Public License as published by the Free Software Foundation; either version 2 of the License, or (at your option) any later version.

This program is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details.

You should have received a copy of the GNU General Public License along with this program; if not, write to the Free Software Foundation, Inc., 51 Franklin St, Fifth Floor, Boston, MA 02110-1301 USA

Also add information on how to contact you by electronic and paper mail.

If the program is interactive, make it output a short notice like this when it starts in an interactive mode:

```
Gnomovision version 69, Copyright (C) year name of author
Gnomovision comes with ABSOLUTELY NO WARRANTY; for details type `show w'.
This is free software, and you are welcome to redistribute it
under certain conditions; type `show c' for details.
```

The hypothetical commands `show w' and `show c' should show the appropriate parts of the General Public License. Of course, the commands you use may be called something other than `show w' and `show c'; they could even be mouse-clicks or menu items--whatever suits your program.

You should also get your employer (if you work as a programmer) or your school, if any, to sign a "copyright disclaimer" for the program, if necessary. Here is a sample; alter the names:

```
Yoyodyne, Inc., hereby disclaims all copyright interest in the program
`Gnomovision' (which makes passes at compilers) written by James Hacker.
```

```
<signature of Ty Coon>, 1 April 1989
Ty Coon, President of Vice
```

This General Public License does not permit incorporating your program into proprietary programs. If your program is a subroutine library, you may consider it more useful to permit linking proprietary applications with the library. If this is what you want to do, use the GNU Library General Public License instead of this License.

1.11 coreutils 8.28-1ubuntu1

1.11.1 Available under license :

The empty package mktemp is created by Michael Stone <mstone@debian.org> and either is in the public domain or too trivial to copyright.

This is the Debian GNU/Linux packaged version of the GNU core utilities.

This package is maintained by Michael Stone <mstone@debian.org> and built from sources obtained from:

<ftp://ftp.gnu.org/gnu/coreutils/coreutils-8.24.tar.xz>

This debian package was first created by Michael Stone <mstone@debian.org>, from coreutils 4.5.1.

Changes:

- * added Debian GNU/Linux package maintenance system files
- * at times, bug fixes awaiting inclusion in the upstream source

Authors

=====

See the file AUTHORS.

Copyright Holders and License

=====

lib/fts.c

Copyright (C) 2004, 2005, 2006, 2007, 2008 Free Software Foundation, Inc.

This program is free software: you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation; either version 3 of the License, or (at your option) any later version.

This program is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details.

You should have received a copy of the GNU General Public License along with this program. If not, see <<http://www.gnu.org/licenses/>>. */

/*_

* Copyright (c) 1990, 1993, 1994

* The Regents of the University of California. All rights reserved.

*

* Redistribution and use in source and binary forms, with or without

* modification, are permitted provided that the following conditions

* are met:

* 1. Redistributions of source code must retain the above copyright

* notice, this list of conditions and the following disclaimer.

* 2. Redistributions in binary form must reproduce the above copyright

* notice, this list of conditions and the following disclaimer in the

* documentation and/or other materials provided with the distribution.

* 4. Neither the name of the University nor the names of its

contributors

* may be used to endorse or promote products derived from this software

* without specific prior written permission.

*

* THIS SOFTWARE IS PROVIDED BY THE REGENTS AND CONTRIBUTORS ``AS IS" AND

* ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE

* IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE

* ARE DISCLAIMED. IN NO EVENT SHALL THE REGENTS OR CONTRIBUTORS BE LIABLE

* FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL

* DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS

* OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION)

* HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT

* LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY

* OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF

* SUCH DAMAGE.

*/

lib/fts_.h

Copyright (C) 2004, 2005, 2006, 2007 Free Software Foundation,
Inc.

This program is free software: you can redistribute it and/or modify
it under the terms of the GNU General Public License as published by
the Free Software Foundation; either version 3 of the License, or
(at your option) any later version.

This program is distributed in the hope that it will be useful,
but WITHOUT ANY WARRANTY; without even the implied warranty of
MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
GNU General Public License for more details.

You should have received a copy of the GNU General Public License along with this program. If not, see <<http://www.gnu.org/licenses/>>. */

/*

* Copyright (c) 1989, 1993

* The Regents of the University of California. All rights reserved.

*

* Redistribution and use in source and binary forms, with or without

* modification, are permitted provided that the following conditions

* are met:

* 1. Redistributions of source code must retain the above copyright

*

notice, this list of conditions and the following disclaimer.

* 2. Redistributions in binary form must reproduce the above copyright

* notice, this list of conditions and the following disclaimer in the

* documentation and/or other materials provided with the distribution.

* 4. Neither the name of the University nor the names of its contributors

* may be used to endorse or promote products derived from this software

* without specific prior written permission.

*

* THIS SOFTWARE IS PROVIDED BY THE REGENTS AND CONTRIBUTORS ``AS IS" AND

* ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE

* IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE

* ARE DISCLAIMED. IN NO EVENT SHALL THE REGENTS OR CONTRIBUTORS BE LIABLE

* FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL

* DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS

* OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS

INTERRUPTION)

* HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT

* LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY

* OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF

* SUCH DAMAGE.

lib/rand-isaac.[ch]

Copyright (C) 1999-2006 Free Software Foundation, Inc.

Copyright (C) 1997, 1998, 1999 Colin Plumb.

This program is free software: you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation, either version 3 of the License, or (at your option) any later version.

This program is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the

GNU General Public License for more details.

You should have received a copy of the GNU General Public License along with this program.

If not, see <<http://www.gnu.org/licenses/>>.

lib/inet_ntop.c

Copyright (C) 2005, 2006 Free Software Foundation, Inc.

This program is free software; you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation; either version 3, or (at your option) any later version.

This program is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details.

You should have received a copy of the GNU General Public License along with this program; if not, write to the Free Software Foundation, Inc., 51 Franklin Street, Fifth Floor, Boston, MA 02110-1301, USA. */

/*

* Copyright (c) 1996-1999 by Internet Software Consortium.

*

* Permission to use, copy, modify, and distribute this software for any purpose

with or without fee is hereby granted, provided that the above

* copyright notice and this permission notice appear in all copies.

*

* THE SOFTWARE IS PROVIDED "AS IS" AND INTERNET SOFTWARE CONSORTIUM DISCLAIMS
* ALL WARRANTIES WITH REGARD TO THIS SOFTWARE INCLUDING ALL IMPLIED WARRANTIES
* OF MERCHANTABILITY AND FITNESS. IN NO EVENT SHALL INTERNET SOFTWARE
* CONSORTIUM BE LIABLE FOR ANY SPECIAL, DIRECT, INDIRECT, OR CONSEQUENTIAL
* DAMAGES OR ANY DAMAGES WHATSOEVER RESULTING FROM LOSS OF USE, DATA OR
* PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE OR OTHER TORTIOUS
* ACTION, ARISING OUT OF OR IN CONNECTION WITH THE USE OR PERFORMANCE OF THIS
* SOFTWARE.

*/

m4/autobuild.m4

dnl Copyright (C) 2004, 2006, 2007 Free Software Foundation, Inc.

dnl This file is free software; the Free Software Foundation
dnl gives unlimited permission to copy and/or distribute it,
dnl with or without modifications, as long as this notice is preserved.

dnl From Simon Josefsson

src/cut.c

Copyright (C) 1997-2007 Free Software Foundation, Inc.

Copyright (C) 1984 David M. Ihnat

This program is free software: you can redistribute it and/or modify
it under the terms of the GNU General Public License as published by
the Free Software Foundation, either version 3 of the License, or
(at your option) any later version.

This program is distributed in the hope that it will be useful,
but WITHOUT ANY WARRANTY; without even the implied warranty of
MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
GNU General Public License for more details.

You should have received a copy of the GNU General Public License
along with this program. If not, see <<http://www.gnu.org/licenses/>>. */

src/dircolors.c

Copyright (C) 1996-2007 Free Software Foundation, Inc.

Copyright (C) 1994, 1995, 1997, 1998, 1999, 2000 H. Peter Anvin

This program is free software: you can redistribute it and/or modify
it under the terms of the GNU General Public License as published by
the Free Software Foundation, either version 3 of the License, or
(at your option) any later version.

This program is distributed in the hope that it will be useful,
but WITHOUT ANY WARRANTY; without even the implied warranty of
MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
GNU General Public License for more details.

You should have received a copy of the GNU General Public License
along with this program. If not, see <<http://www.gnu.org/licenses/>>. */

src/paste.c

Copyright (C) 1997-2005 Free Software Foundation, Inc.
Copyright (C) 1984 David M. Ihnat

This program is free software: you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation, either version 3 of the License, or (at your option) any later version.

This program is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details.

You should have received a copy of the GNU General Public License along with this program. If not, see <<http://www.gnu.org/licenses/>>. */

src/shred.c

Copyright (C) 1999-2007 Free Software Foundation, Inc.
Copyright (C) 1997, 1998, 1999 Colin Plumb.

This program is free software: you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation, either version 3 of the License, or (at your option) any later version.

This program is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details.

You should have received a copy of the GNU General Public License along with this program. If not, see <<http://www.gnu.org/licenses/>>.

doc/coreutils.texi (The GNU Coreutils Manual)

Copyright ©copyright{} 1994-1996, 2000-2008 Free Software Foundation, Inc.

Permission is granted to copy, distribute and/or modify this document under the terms of the GNU Free Documentation License, Version 1.2 or

any later version published by the Free Software Foundation; with no Invariant Sections, with no Front-Cover Texts, and with no Back-Cover Texts. A copy of the license is included in the section entitled ``GNU Free Documentation License''.

all other files

Copyright (C) 1984-2008 Free Software Foundation, Inc.

This program is free software: you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation, either version 3 of the License, or (at your option) any later version.

This program is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details.

You should have received a copy of the GNU General Public License along with this program. If not, see <<http://www.gnu.org/licenses/>>.

On Debian systems, the complete text of the GNU General Public License can be found in `~/usr/share/common-licenses/GPL-3'`. The empty package realpath is created by Michael Stone <mstone@debian.org> and either is in the public domain or too trivial to copyright. Coreutils itself is generally copyrighted under the terms of the GNU General Public License. Specific copyrights can be found in the `coreutils.copyright` file and the `*.copyright` files for other packages included within the coreutils source package. (Generally, these are trivial transitional packages.)

1.12 findutils 4.6.0+git+20170828-2

1.12.1 Available under license :

It was downloaded from <ftp://ftp.gnu.org/gnu/findutils>

Debian maintainer history: The original package was put together by Ian Murdock <imurdock@debian.org>, afterwards Kevin Dalley <kevind@rahul.net> took over. 2003-07 Andreas Metzler <ametzler@debian.org> followed.

Upstream Authors:

* GNU find was written by Eric Decker <cire@cisco.com>, with enhancements by David MacKenzie <djm@gnu.org>.

Jay Plett <jay@silence.princeton.nj.us>,
and Tim Wood <axolotl!tim@toad.com>.
The idea for -print0 and xargs -0 came from
Dan Bernstein <brnstnd@kramden.acf.nyu.edu>.
Improvements have been made by James Youngman <jay@gnu.org>.

* GNU xargs
was originally written by Mike Rendell, with enhancements by David
MacKenzie. Modifications by James Youngman Dmitry V. Levin

* GNU locate and its associated utilities were originally
written by James Woods, with enhancements by David MacKenzie, James Youngman
and Bas van Gompel.

Upstream's AUTHORS lists these major contributors:

Eric B. Decker
Michael Rendell
David
J. MacKenzie
Jim Meyering
Tim Wood
Kevin Dalley <kevind@rahul.net>
Paul Eggert <eggert@cs.ucla.edu>
James Youngman <jay@gnu.org>
Jay Plett
Paul Sheer
Dmitry V. Levin
Bas van Gompel
Eric Blake <ebb9@byu.net>
Andreas Metzler
Kamil Dudka <kdudka@redhat.com>
Bernhard Voelker <mail@bernhard-voelker.de>

Current upstream maintainer is James Youngman <jay@gnu.org>.

Copyright (C) 1990, 1991, 1992, 1993, 1994, 2000, 2003, 2004, 2005,
2007, 2008, 2009, 2010 Free Software Foundation, Inc.

This program is free software: you can redistribute it and/or modify
it under the terms of the GNU General Public License as published by
the Free Software Foundation, either version 3 of the License, or
(at your option) any later version.

This program is distributed in the hope that it will be useful,
but WITHOUT ANY WARRANTY; without even the implied warranty of
MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the

GNU
General Public License for more details.

You should have received a copy of the GNU General Public License
along with this program. If not, see <<http://www.gnu.org/licenses/>>.

On Debian GNU/Linux systems, the complete text of the GNU General
Public License version 3 can be found in ``usr/share/common-licenses/GPL-3'`.

=====
DOCUMENTATION

Copyright (C) 1994, 1996, 1998, 2000, 2001, 2003-2016 Free Software
Foundation, Inc.

Permission is granted to copy, distribute and/or modify this document
under the terms of the GNU Free Documentation License, Version 1.3 or
any later version published by the Free Software Foundation; with no
Invariant Sections, no Front-Cover Texts, and no Back-Cover Texts. A
copy of the license is included in the section entitled "GNU Free
Documentation License".

On Debian GNU/Linux systems, the complete text of the GNU Free Documentation
License,
Version 1.3 can be found in ``usr/share/common-licenses/GFDL-1.3'`.

1.13 libsemanage-common 2.7-2build2

1.13.1 Available under license :

This is the Debian packe for libsemanage, and it is built from sources
obtained from: <http://www.nsa.gov/selinux/code/download5.cfm>.

libsemanage is Copyright 2004-2007 Tresys Technology, LLC
Copyright 2005 Red Hat, Inc.

This library is free software; you can redistribute it and/or
modify it under the terms of the GNU Lesser General Public
License as published by the Free Software Foundation; either
version 2.1 of the License, or (at your option) any later version.

This library is distributed in the hope that it will be useful,
but WITHOUT ANY WARRANTY; without even the implied warranty of
MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU
Lesser General Public License for more details.

You should have received a copy of the GNU Lesser General Public License along with this library; if not, write to the Free Software Foundation, Inc., 51 Franklin St, Fifth Floor, Boston, MA 02110-1

On Debian GNU/Linux systems,
the complete text of the Lesser GNU General
Public License can be found in `~/usr/share/common-licenses/LGPL`.

This package is maintained by Manoj Srivastava <srivasta@debian.org>.

The Debian specific changes are 2005-2009, Manoj Srivastava
<srivasta@debian.org>, and distributed under the terms of the GNU
General Public License, version 2.

On Debian GNU/Linux systems, the complete text of the GNU General
Public License can be found in `~/usr/share/common-licenses/GPL`.

A copy of the GNU General Public License is also available at
<URL:<http://www.gnu.org/copyleft/gpl.html>>. You may also obtain
it by writing to the Free Software Foundation, Inc., 51 Franklin
St, Fifth Floor, Boston, MA 02110-1301, USA.

Manoj Srivastava <srivasta@debian.org>
arch-tag: d4250e44-a0e0-4ee0-adb9-2bd74f6eeb27

1.14 Isb 9.20170808ubuntu1

1.14.1 Available under license :

Format: <http://www.debian.org/doc/packaging-manuals/copyright-format/1.0/>
Upstream-Name: LSB implementation package

Files: *
Copyright: 2002-2010, Chris Lawrence <lawrenc@debian.org>
License: GPL-2

Files: init-functions.d/50-ubuntu-logging
Copyright: 2005-2011, Canonical Ltd.
License: GPL-2

Files: init-functions
Copyright: 2002-2009, Chris Lawrence <lawrenc@debian.org>
License: BSD-3-clause
Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions
are met:

1. Redistributions of source code must retain the above copyright
notice, this list of conditions and the following disclaimer.

2. Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.
3. Neither the name of the author nor the names of other contributors may be used to endorse or promote products derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE REGENTS AND CONTRIBUTORS ``AS IS'' AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE REGENTS OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

License: GPL-2

This program is free software; you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation; version 2 dated June 1991.

This program is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details.

You should have received a copy of the GNU General Public License along with this package; if not, write to the Free Software Foundation, Inc., 51 Franklin St, Fifth Floor, Boston, MA 02110-1301 USA

On Debian systems, the full text of the GNU General Public License version 2 can be found in the file `/usr/share/common-licenses/GPL-2`.

1.15 mawk 1.3.3-17ubuntu3

1.16 sysv-init 2.88dsf-59.10ubuntu1

1.16.1 Available under license :

This package contains the mechanism for executing the right scripts in the right order at bootup/shutdown time, and when changing runlevels. It works through managing symlinks in /etc/rc?.d

This package is built from the `sysvinit' source package. Please consult the copyright file of the sysvinit package for the location of the upstream sources of the sysvinit package. Debian-specific files for sysvinit, such as these initscripts, are maintained by the members of the pkg-sysvinit project at alioth.debian.org.

<http://alioth.debian.org/projects/pkg-sysvinit>

Copyright 1997-2005 Miquel van Smoorenburg <miquels@cistron.nl> and the members pkg-sysvinit project.

This program is free software; you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation; either version 2 of the License, or (at your option) any later version.

This program is distributed in the hope that it will be useful,

but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details.

You should have received a copy of the GNU General Public License along with this program; if not, write to the Free Software Foundation, Inc., 51 Franklin St, Fifth Floor, Boston, MA 02110-1301 USA

On Debian GNU/Linux systems, the complete text of the GNU General Public License can be found in `~/usr/share/common-licenses/GPL-2`. This package contains the scripts that are executed at start and shutdown of Debian systems.

This package is built from the `sysvinit' source package. Please consult the copyright file of the sysvinit package for the location of the upstream sources of the sysvinit package. Debian-specific files for sysvinit, such as these initscripts, are maintained by the members of the pkg-sysvinit project at alioth.debian.org.

<http://alioth.debian.org/projects/pkg-sysvinit>

Copyright 1997-2005 Miquel van Smoorenburg <miquels@cistron.nl> and the members pkg-sysvinit project.

This program is free software; you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation; either version 2 of the License, or (at your option) any later version.

This program is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details.

You should have received a copy of the GNU General Public License along with this program; if not, write to the Free Software Foundation, Inc., 51 Franklin St, Fifth Floor, Boston, MA 02110-1301 USA

On Debian GNU/Linux systems, the complete text of the GNU General Public License can be found in `~/usr/share/common-licenses/GPL-2`. This is the Debian GNU/Linux prepackaged version of System V Init.

Init was written by Miquel van Smoorenburg <miquels@cistron.nl>.

This package was first put together by Bruce Perens <Bruce@Pixar.com> from pre-distribution sources. Ian Murdock <imurdock@debian.org> integrated it into the base system maintained it until the end of 1995. Miquel van Smoorenburg <miquels@cistron.nl> implemented Debian support. In version 2.85 the package was split into three (sysvinit, sysv-rc, and initscripts) in order to make room for alternative rc mechanisms.

The upstream source is available at:

Primary-Site: [ftp.cistron.nl/pub/people/miquels/software](ftp:cistron.nl/pub/people/miquels/software)
92K sysvinit-2.86.tar.gz
Alternate-Site: sunsite.unc.edu/pub/Linux/system/daemons/init
92K sysvinit-2.86.tar.gz

Send patches to sysvinit-devel@nongnu.org.

The sysvinit package in Debian is maintained as an alioth project. The project page is <http://alioth.debian.org/projects/pkg-sysvinit/>.

Copyright 1997-2005 Miquel

van Smoorenburg <miquels@cistron.nl> and
the members pkg-sysvinit project.

This program is free software; you can redistribute it and/or modify
it under the terms of the GNU General Public License as published by
the Free Software Foundation; either version 2 of the License, or
(at your option) any later version.

This program is distributed in the hope that it will be useful,
but WITHOUT ANY WARRANTY; without even the implied warranty of
MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
GNU General Public License for more details.

You should have received a copy of the GNU General Public License
along with this program; if not, write to the Free Software
Foundation, Inc., 51 Franklin St, Fifth Floor, Boston, MA
02110-1301 USA

On Debian GNU/Linux systems, the complete text of the GNU General
Public License can be found in `~/usr/share/common-licenses/GPL-2`.

The of the start-stop-daemon:

- * A rewrite of the original Debian's
start-stop-daemon Perl script
- * in C (faster - it is executed many times during system startup).
- *
- * Written by Marek Michalkiewicz <marekm@i17linuxb.ists.pwr.wroc.pl>,
* public domain.

1.17 debconf 1.5.66ubuntu1

1.18 libunistring 0.9.9-0ubuntu2

1.18.1 Available under license :

@c The GNU Free Documentation License.

@center Version 1.3, 3 November 2008

@c This file is intended to be included within another document,

@c hence no sectioning command or @node.

@display

Copyright @copyright{ } 2000, 2001, 2002, 2007, 2008 Free Software Foundation, Inc.

@uref{http://fsf.org/}

Everyone is permitted to copy and distribute verbatim copies of this license document, but changing it is not allowed.

@end display

@enumerate 0

@item

PREAMBLE

The purpose of this License is to make a manual, textbook, or other functional and useful document @dfn{free} in the sense of freedom: to assure everyone the effective freedom to copy and redistribute it, with or without modifying it, either commercially or noncommercially. Secondly, this License preserves for the author and publisher a way to get credit for their work, while not being considered responsible for modifications made by others.

This License is a kind of ``copyleft'', which means that derivative works of the document must themselves be free in the same sense. It complements the GNU General Public License, which is a copyleft license designed for free software.

We have designed this License in order to use it for manuals for free software, because free software needs free documentation: a free program should come with manuals providing the same freedoms that the software does. But this License is not limited to software manuals; it can be used for any textual work, regardless of subject matter or whether it is published as a printed book. We recommend this License principally for works whose purpose is instruction or reference.

@item

APPLICABILITY AND DEFINITIONS

This License applies to any manual or other work, in any medium, that contains a notice placed by the copyright holder saying it can be distributed under the terms of this License. Such a notice grants a world-wide, royalty-free license, unlimited in duration, to use that work under the conditions stated herein. The ``Document'', below, refers

to any such manual or work. Any member of the public is a licensee, and is addressed as ``you''. You accept the license if you copy, modify or distribute the work in a way requiring permission under copyright law.

A ``Modified Version'' of the Document means any work containing the Document or a portion of it, either copied verbatim, or with modifications and/or translated into another language.

A "Secondary Section" is a named appendix or a front-matter section of the Document that deals exclusively with the relationship of the publishers or authors of the Document to the Document's overall subject (or to related matters) and contains nothing that could fall directly within that overall subject. (Thus, if the Document is in part a textbook of mathematics, a Secondary Section may not explain any mathematics.) The relationship could be a matter of historical connection with the subject or with related matters, or of legal, commercial, philosophical, ethical or political position regarding them.

The "Invariant Sections" are certain Secondary Sections whose titles are designated, as being those of Invariant Sections, in the notice that says that the Document is released under this License. If a section does not fit the above definition of Secondary then it is not allowed to be designated as Invariant. The Document may contain zero Invariant Sections. If the Document does not identify any Invariant Sections then there are none.

The "Cover Texts" are certain short passages of text that are listed, as Front-Cover Texts or Back-Cover Texts, in the notice that says that the Document is released under this License. A Front-Cover Text may be at most 5 words, and a Back-Cover Text may be at most 25 words.

A "Transparent" copy of the Document means a machine-readable copy, represented in a format whose specification is available to the general public, that is suitable for revising the document straightforwardly with generic text editors or (for images composed of pixels) generic paint programs or (for drawings) some widely available drawing editor, and that is suitable for input to text formatters or for automatic translation to a variety of formats suitable for input to text formatters. A copy made in an otherwise Transparent file format whose markup, or absence of markup, has been arranged to thwart or discourage subsequent modification by readers is not Transparent. An image format is not Transparent if used for any substantial amount of text. A copy that is not "Transparent" is called "Opaque".

Examples of suitable formats for Transparent copies include plain `@sc{ascii}` without markup, Texinfo input format, `La@TeX{}` input format, `@acronym{SGML}` or `@acronym{XML}` using a publicly available `@acronym{DTD}`, and standard-conforming simple `@acronym{HTML}`, PostScript or `@acronym{PDF}` designed for human modification. Examples of transparent image formats include `@acronym{PNG}`, `@acronym{XCF}` and `@acronym{JPG}`. Opaque formats include proprietary formats that can be read and edited only by proprietary word processors, `@acronym{SGML}` or

@acronym{XML} for which the @acronym{DTD} and/or processing tools are not generally available, and the machine-generated @acronym{HTML}, PostScript or @acronym{PDF} produced by some word processors for output purposes only.

The ``Title Page'' means, for a printed book, the title page itself, plus such following pages as are needed to hold, legibly, the material this License requires to appear in the title page. For works in formats which do not have any title page as such, ``Title Page'' means the text near the most prominent appearance of the work's title, preceding the beginning of the body of the text.

The ``publisher'' means any person or entity that distributes copies of the Document to the public.

A section ``Entitled XYZ'' means a named subunit of the Document whose title either is precisely XYZ or contains XYZ in parentheses following text that translates XYZ in another language. (Here XYZ stands for a specific section name mentioned below, such as ``Acknowledgements'', ``Dedications'', ``Endorsements'', or ``History''.) To ``Preserve the Title'' of such a section when you modify the Document means that it remains a section ``Entitled XYZ'' according to this definition.

The Document may include Warranty Disclaimers next to the notice which states that this License applies to the Document. These Warranty Disclaimers are considered to be included by reference in this License, but only as regards disclaiming warranties: any other implication that these Warranty Disclaimers may have is void and has no effect on the meaning of this License.

@item

VERBATIM COPYING

You may copy and distribute the Document in any medium, either commercially or noncommercially, provided that this License, the copyright notices, and the license notice saying this License applies to the Document are reproduced in all copies, and that you add no other conditions whatsoever to those of this License. You may not use technical measures to obstruct or control the reading or further copying of the copies you make or distribute. However, you may accept compensation in exchange for copies. If you distribute a large enough number of copies you must also follow the conditions in section 3.

You may also lend copies, under the same conditions stated above, and you may publicly display copies.

@item

COPYING IN QUANTITY

If you publish printed copies (or copies in media that commonly have printed covers) of the Document, numbering more than 100, and the Document's license notice requires Cover Texts, you must enclose the copies in covers that carry, clearly and legibly, all these Cover Texts: Front-Cover Texts on the front cover, and Back-Cover Texts on the back cover. Both covers must also clearly and legibly identify you as the publisher of these copies. The front cover must present the full title with all words of the title equally prominent and visible.

You may add other material on the covers in addition.

Copying with changes limited to the covers, as long as they preserve the title of the Document and satisfy these conditions, can be treated as verbatim copying in other respects.

If the required texts for either cover are too voluminous to fit legibly, you should put the first ones listed (as many as fit reasonably) on the actual cover, and continue the rest onto adjacent pages.

If you publish or distribute Opaque copies of the Document numbering more than 100, you must either include a machine-readable Transparent copy along with each Opaque copy, or state in or with each Opaque copy a computer-network location from which the general network-using public has access to download using public-standard network protocols a complete Transparent copy of the Document, free of added material.

If you use the latter option, you must take reasonably prudent steps, when you begin distribution of Opaque copies in quantity, to ensure that

this Transparent copy will remain thus accessible at the stated location until at least one year after the last time you distribute an Opaque copy (directly or through your agents or retailers) of that edition to the public.

It is requested, but not required, that you contact the authors of the Document well before redistributing any large number of copies, to give them a chance to provide you with an updated version of the Document.

@item

MODIFICATIONS

You may copy and distribute a Modified Version of the Document under the conditions of sections 2 and 3 above, provided that you release the Modified Version under precisely this License, with the Modified Version filling the role of the Document, thus licensing distribution and modification of the Modified Version to whoever possesses a copy

of it. In addition, you must do these things in the Modified Version:

@enumerate A

@item

Use in the Title Page (and on the covers, if any) a title distinct from that of the Document, and from those of previous versions (which should, if there were any, be listed in the History section of the Document). You may use the same title as a previous version if the original publisher of that version gives permission.

@item

List on the Title Page, as authors, one or more persons or entities responsible for authorship of the modifications in the Modified Version, together with at least five of the principal authors of the Document (all of its principal authors, if it has fewer than five), unless they release you from this requirement.

@item

State on the Title page the name of the publisher of the Modified Version, as the publisher.

@item

Preserve all the copyright notices of the Document.

@item

Add an appropriate copyright notice for your modifications adjacent to the other copyright notices.

@item

Include, immediately after the copyright notices, a license notice giving the public permission to use the Modified Version under the terms of this License, in the form shown in the Addendum below.

@item

Preserve in that license notice the full lists of Invariant Sections and required Cover Texts given in the Document's license notice.

@item

Include an unaltered copy of this License.

@item

Preserve the section Entitled ``History'', Preserve its Title, and add to it an item stating at least the title, year, new authors, and publisher of the Modified Version as given on the Title Page. If there is no section Entitled ``History'' in the Document, create one stating the title, year, authors, and publisher of the Document as

given on its Title Page, then add an item describing the Modified Version as stated in the previous sentence.

@item

Preserve the network location, if any, given in the Document for public access to a Transparent copy of the Document, and likewise the network locations given in the Document for previous versions it was based on. These may be placed in the ``History" section. You may omit a network location for a work that was published at least four years before the Document itself, or if the original publisher of the version it refers to gives permission.

@item

For any section Entitled ``Acknowledgements" or ``Dedications", Preserve the Title of the section, and preserve in the section all the substance and tone of each of the contributor acknowledgements and/or dedications given therein.

@item

Preserve all the Invariant Sections of the Document, unaltered in their text and in their titles. Section numbers or the equivalent are not considered part of the section titles.

@item

Delete any section Entitled ``Endorsements". Such a section may not be included in the Modified Version.

@item

Do not retitle any existing section to be Entitled ``Endorsements" or to conflict in title with any Invariant Section.

@item

Preserve any Warranty Disclaimers.
@end enumerate

If the Modified Version includes new front-matter sections or appendices that qualify as Secondary Sections and contain no material copied from the Document,
you may at your option designate some or all of these sections as invariant. To do this, add their titles to the list of Invariant Sections in the Modified Version's license notice. These titles must be distinct from any other section titles.

You may add a section Entitled ``Endorsements", provided it contains nothing but endorsements of your Modified Version by various parties---for example, statements of peer review or that the text has been approved by an organization as the authoritative definition of a

standard.

You may add a passage of up to five words as a Front-Cover Text, and a passage of up to 25 words as a Back-Cover Text, to the end of the list of Cover Texts in the Modified Version. Only one passage of Front-Cover Text and one of Back-Cover Text may be added by (or through arrangements made by) any one entity. If the Document already includes a cover text for the same cover, previously added by you or by arrangement made by the same entity you are acting on behalf of, you may not add another; but you may replace the old one, on explicit permission from the previous publisher that added the old one.

The author(s) and publisher(s) of the Document do not by this License give permission to use their names for publicity for or to assert or imply endorsement of any Modified Version.

@item

COMBINING DOCUMENTS

You may combine the Document with other documents released under this License, under the terms defined in section 4 above for modified versions, provided that you include in the combination all of the Invariant Sections of all of the original documents, unmodified, and list them all as Invariant Sections of your combined work in its license notice, and that you preserve all their Warranty Disclaimers.

The combined work need only contain one copy of this License, and multiple identical Invariant Sections may be replaced with a single copy. If there are multiple Invariant Sections with the same name but different contents, make the title of each such section unique by adding at the end of it, in parentheses, the name of the original author or publisher of that section if known, or else a unique number. Make the same adjustment to the section titles in the list of Invariant Sections in the license notice of the combined work.

In the combination, you must combine any sections Entitled ``History" in the various original documents, forming one section Entitled ``History"; likewise combine any sections Entitled ``Acknowledgements", and any sections Entitled ``Dedications". You must delete all sections Entitled ``Endorsements."

@item

COLLECTIONS OF DOCUMENTS

You may make a collection consisting of the Document and other documents released under this License, and replace the individual copies of this

License in the various documents with a single copy that is included in the collection, provided that you follow the rules of this License for verbatim copying of each of the documents in all other respects.

You may extract

a single document from such a collection, and distribute it individually under this License, provided you insert a copy of this License into the extracted document, and follow this License in all other respects regarding verbatim copying of that document.

@item

AGGREGATION WITH INDEPENDENT WORKS

A compilation of the Document or its derivatives with other separate and independent documents or works, in or on a volume of a storage or distribution medium, is called an "aggregate" if the copyright resulting from the compilation is not used to limit the legal rights of the compilation's users beyond what the individual works permit. When the Document is included in an aggregate, this License does not apply to the other works in the aggregate which are not themselves derivative works of the Document.

If the Cover Text requirement of section 3 is applicable to these copies of the Document, then if the Document is less than one half of the entire aggregate, the Document's Cover Texts may be placed on covers that bracket the Document within the aggregate, or the electronic equivalent of covers if the Document is in electronic form. Otherwise they must appear on printed covers that bracket the whole aggregate.

@item

TRANSLATION

Translation is considered a kind of modification, so you may distribute translations of the Document under the terms of section 4. Replacing Invariant Sections with translations requires special permission from their copyright holders, but you may include translations of some or all Invariant Sections in addition to the original versions of these Invariant Sections. You may include a translation of this License, and all the license notices in the Document, and any Warranty Disclaimers, provided that you also include the original English version of this License and the original versions of those notices and disclaimers. In case of a disagreement between the translation and the original version of this License or a notice or disclaimer, the original version will prevail.

If a section in the Document is Entitled ``Acknowledgements'', ``Dedications'', or ``History'', the requirement (section 4) to Preserve its Title (section 1) will typically require changing the actual title.

@item

TERMINATION

You may not copy, modify, sublicense, or distribute the Document except as expressly provided under this License. Any attempt otherwise to copy, modify, sublicense, or distribute it is void, and will automatically terminate your rights under this License.

However, if you cease all violation of this License, then your license from a particular copyright holder is reinstated (a) provisionally, unless and until the copyright holder explicitly and finally terminates your license, and (b) permanently, if the copyright holder fails to notify you of the violation by some reasonable means prior to 60 days after the cessation.

Moreover, your license from a particular copyright holder is reinstated permanently if the copyright holder notifies you of the violation by some reasonable means, this is the first time you have received notice of violation of this License (for any work) from that copyright holder, and you cure the violation prior to 30 days after your receipt of the notice.

Termination of your rights under this section does not terminate the licenses of parties who have received copies or rights from you under this License. If your rights have been terminated and not permanently reinstated, receipt of a copy of some or all of the same material does not give you any rights to use it.

@item

FUTURE REVISIONS OF THIS LICENSE

The Free Software Foundation may publish new, revised versions of the GNU Free Documentation License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns. See [@uref{http://www.gnu.org/copyleft/}](http://www.gnu.org/copyleft/).

Each version of the License is given a distinguishing version number. If the Document specifies that a particular numbered version of this License ``or any later version'' applies to it, you have the option of following the terms and conditions either of that specified version or

of any later version that has been published (not as a draft) by the Free Software Foundation. If the Document does not specify a version number of this License, you may choose any version ever published (not as a draft) by the Free Software Foundation. If the Document specifies that a proxy can decide which future versions of this License can be used, that proxy's public statement of acceptance of a version permanently authorizes you to choose that version for the Document.

@item

RELICENSING

``Massive Multiauthor Collaboration Site" (or ``MMC Site") means any World Wide Web server that publishes copyrightable works and also provides prominent facilities for anybody to edit those works. A public wiki that anybody can edit is an example of such a server. A ``Massive Multiauthor Collaboration" (or ``MMC") contained in the site means any set of copyrightable works thus published on the MMC site.

``CC-BY-SA" means the Creative Commons Attribution-Share Alike 3.0 license published by Creative Commons Corporation, a not-for-profit corporation with a principal place of business in San Francisco, California, as well as future copyleft versions of that license published by that same organization.

``Incorporate" means to publish or republish a Document, in whole or in part, as part of another Document.

An MMC is ``eligible for relicensing" if it is licensed under this License, and if all works that were first published under this License somewhere other than this MMC, and subsequently incorporated in whole or in part into the MMC, (1) had no cover texts or invariant sections, and (2) were thus incorporated prior to November 1, 2008.

The operator of an MMC Site may republish an MMC contained in the site under CC-BY-SA on the same site at any time before August 1, 2009, provided the MMC is eligible for relicensing.

@end enumerate

@page

@heading ADDENDUM: How to use this License for your documents

To use this License in a document you have written, include a copy of the License in the document and put the following copyright and

license notices just after the title page:

```
@smallexample
@group
Copyright (C) @var{year} @var{your name}.
Permission is granted to copy, distribute and/or modify this document
under the terms of the GNU Free Documentation License, Version 1.3
or any later version published by the Free Software Foundation;
with no Invariant Sections, no Front-Cover Texts, and no Back-Cover
Texts. A copy of the license is included in the section entitled ``GNU
Free Documentation License".
@end group
@end smallexample
```

If you have Invariant Sections, Front-Cover Texts and Back-Cover Texts, replace the ``with@dots{ }Texts." line with this:

```
@smallexample
@group
  with the Invariant Sections being @var{list their titles}, with
  the Front-Cover
  Texts being @var{list}, and with the Back-Cover Texts
  being @var{list}.
@end group
@end smallexample
```

If you have Invariant Sections without Cover Texts, or some other combination of the three, merge those two alternatives to suit the situation.

If your document contains nontrivial examples of program code, we recommend releasing these examples in parallel under your choice of free software license, such as the GNU General Public License, to permit their use in free software.

```
@c Local Variables:
@c ispell-local-pdict: "ispell-dict"
@c End:
      GNU GENERAL PUBLIC LICENSE
      Version 3, 29 June 2007
```

Copyright (C) 2007 Free Software Foundation, Inc. <<http://fsf.org/>>
Everyone is permitted to copy and distribute verbatim copies
of this license document, but changing it is not allowed.

Preamble

The GNU General Public License is a free, copyleft license for

software and other kinds of works.

The licenses for most software and other practical works are designed to take away your freedom to share and change the works. By contrast, the GNU General Public License is intended to guarantee your freedom to share and change all versions of a program--to make sure it remains free software for all its users. We, the Free Software Foundation, use the GNU General Public License for most of our software; it applies also to any other work released this way by its authors. You can apply it to your programs, too.

When we speak of free software, we are referring to freedom, not price. Our General Public Licenses are designed to make sure that you have the freedom to distribute copies of free software (and charge for them if you wish), that you receive source code or can get it if you want it, that you can change the software or use pieces of it in new free programs, and that you know you can do these things.

To protect your rights, we need to prevent others from denying you these rights or asking you to surrender the rights. Therefore, you have certain responsibilities if you distribute copies of the software, or if you modify it: responsibilities to respect the freedom of others.

For example, if you distribute copies of such a program, whether gratis or for a fee, you must pass on to the recipients the same freedoms that you received. You must make sure that they, too, receive or can get the source code. And you must show them these terms so they know their rights.

Developers that use the GNU GPL protect your rights with two steps: (1) assert copyright on the software, and (2) offer you this License giving you legal permission to copy, distribute and/or modify it.

For the developers' and authors' protection, the GPL clearly explains that there is no warranty for this free software. For both users' and authors' sake, the GPL requires that modified versions be marked as changed, so that their problems will not be attributed erroneously to authors of previous versions.

Some devices are designed to deny users access to install or run modified versions of the software inside them, although the manufacturer can do so. This is fundamentally incompatible with the aim of protecting users' freedom to change the software. The systematic pattern of such abuse occurs in the area of products for individuals to use, which is precisely where it is most unacceptable. Therefore, we have designed this version of the GPL to prohibit the practice for those

products. If such problems arise substantially in other domains, we stand ready to extend this provision to those domains in future versions of the GPL, as needed to protect the freedom of users.

Finally, every program is threatened constantly by software patents. States should not allow patents to restrict development and use of software on general-purpose computers, but in those that do, we wish to avoid the special danger that patents applied to a free program could make it effectively proprietary. To prevent this, the GPL assures that patents cannot be used to render the program non-free.

The precise terms and conditions for copying, distribution and modification follow.

TERMS AND CONDITIONS

0. Definitions.

"This License" refers to version 3 of the GNU General Public License.

"Copyright" also means copyright-like laws that apply to other kinds of works, such as semiconductor masks.

"The Program" refers to any copyrightable work licensed under this License. Each licensee is addressed as "you". "Licensees" and "recipients" may be individuals or organizations.

To "modify" a work means to copy from or adapt all or part of the work in a fashion requiring copyright permission, other than the making of an exact copy. The resulting work is called a "modified version" of the earlier work or a work "based on" the earlier work.

A "covered work" means either the unmodified Program or a work based on the Program.

To "propagate" a work means to do anything with it that, without permission, would make you directly or secondarily liable for infringement under applicable copyright law, except executing it on a computer or modifying a private copy. Propagation includes copying, distribution (with or without modification), making available to the public, and in some countries other activities as well.

To "convey" a work means any kind of propagation that enables other parties to make or receive copies. Mere interaction with a user through a computer network, with no transfer of a copy, is

not conveying.

An interactive user interface displays "Appropriate Legal Notices" to the extent that it includes a convenient and prominently visible feature that (1) displays an appropriate copyright notice, and (2) tells the user that there is no warranty for the work (except to the extent that warranties are provided), that licensees may convey the work under this License, and how to view a copy of this License. If the interface presents a list of user commands or options, such as a menu, a prominent item in the list meets this criterion.

1. Source Code.

The "source code" for a work means the preferred form of the work for making modifications to it. "Object code" means any non-source form of a work.

A "Standard Interface" means an interface that either is an official standard defined by a recognized standards body, or, in the case of interfaces specified for a particular programming language, one that is widely used among developers working in that language.

The

"System Libraries" of an executable work include anything, other than the work as a whole, that (a) is included in the normal form of packaging a Major Component, but which is not part of that Major Component, and (b) serves only to enable use of the work with that Major Component, or to implement a Standard Interface for which an implementation is available to the public in source code form. A "Major Component", in this context, means a major essential component (kernel, window system, and so on) of the specific operating system (if any) on which the executable work runs, or a compiler used to produce the work, or an object code interpreter used to run it.

The "Corresponding Source" for a work in object code form means all the source code needed to generate, install, and (for an executable work) run the object code and to modify the work, including scripts to control those activities. However, it does not include the work's System Libraries, or general-purpose tools or generally available free programs which are used unmodified in performing those activities but which are not part of the work. For example, Corresponding Source includes interface definition files associated with source files for the work, and the source code for shared libraries and dynamically linked subprograms that the work is specifically designed to require, such as by intimate data communication or control flow between those subprograms and other parts of the work.

The Corresponding Source need not include anything that users can regenerate automatically from other parts of the Corresponding Source.

The Corresponding Source for a work in source code form is that same work.

2. Basic Permissions.

All rights granted under this License are granted for the term of copyright on the Program, and are irrevocable provided the stated conditions are met. This License explicitly affirms your unlimited permission to run the unmodified Program. The output from running a covered work is covered

by this License only if the output, given its content, constitutes a covered work. This License acknowledges your rights of fair use or other equivalent, as provided by copyright law.

You may make, run and propagate covered works that you do not convey, without conditions so long as your license otherwise remains in force. You may convey covered works to others for the sole purpose of having them make modifications exclusively for you, or provide you with facilities for running those works, provided that you comply with the terms of this License in conveying all material for which you do not control copyright. Those thus making or running the covered works for you must do so exclusively on your behalf, under your direction and control, on terms that prohibit them from making any copies of your copyrighted material outside their relationship with you.

Conveying under any other circumstances is permitted solely under the conditions stated below. Sublicensing is not allowed; section 10 makes it unnecessary.

3. Protecting Users' Legal Rights From Anti-Circumvention Law.

No covered work shall be deemed part of an effective technological measure under any applicable law fulfilling obligations under article 11 of the WIPO copyright treaty adopted on 20 December 1996, or similar laws prohibiting or restricting circumvention of such measures.

When you convey a covered work, you waive any legal power to forbid circumvention of technological measures to the extent such circumvention is effected by exercising rights under this License with respect to the covered work, and you disclaim any intention to limit operation or modification of the work as a means of enforcing, against the work's users, your or third parties' legal rights to forbid circumvention of

technological measures.

4. Conveying Verbatim Copies.

You may convey verbatim copies of the Program's source code as you receive it, in any medium, provided that you conspicuously and appropriately publish on each copy an appropriate copyright notice; keep intact all notices stating that this License and any non-permissive terms added in accord with section 7 apply to the code; keep intact all notices of the absence of any warranty; and give all recipients a copy of this License along with the Program.

You may charge any price or no price for each copy that you convey, and you may offer support or warranty protection for a fee.

5. Conveying Modified Source Versions.

You may convey a work based on the Program, or the modifications to produce it from the Program, in the form of source code under the terms of section 4, provided that you also meet all of these conditions:

- a) The work must carry prominent notices stating that you modified it, and giving a relevant date.
- b) The work must carry prominent notices stating that it is released under this License and any conditions added under section 7. This requirement modifies the requirement in section 4 to "keep intact all notices".
- c) You must license the entire work, as a whole, under this License to anyone who comes into possession of a copy. This License will therefore apply, along with any applicable section 7 additional terms, to the whole of the work, and all its parts, regardless of how they are packaged. This License gives no permission to license the work in any other way, but it does not invalidate such permission if you have separately received it.
- d) If the work has interactive user interfaces, each must display Appropriate Legal Notices; however, if the Program has interactive interfaces that do not display Appropriate Legal Notices, your work need not make them do so.

A compilation of a covered work with other separate and independent works, which are not by their nature extensions of the covered work, and which are not combined with it such as to form a larger program, in or on a volume of a storage or distribution

medium, is called an "aggregate" if the compilation and its resulting copyright are not used to limit the access or legal rights of the compilation's users beyond what the individual works permit. Inclusion of a covered work in an aggregate does not cause this License to apply to the other parts of the aggregate.

6. Conveying Non-Source Forms.

You may convey a covered work in object code form under the terms of sections 4 and 5, provided that you also convey the machine-readable Corresponding Source under the terms of this License, in one of these ways:

- a) Convey the object code in, or embodied in, a physical product (including a physical distribution medium), accompanied by the Corresponding Source fixed on a durable physical medium customarily used for software interchange.
- b) Convey the object code in, or embodied in, a physical product (including a physical distribution medium), accompanied by a written offer, valid for at least three years and valid for as long as you offer spare parts or customer support for that product model, to give anyone who possesses the object code either (1) a copy of the Corresponding Source for all the software in the product that is covered by this License, on a durable physical medium customarily used for software interchange, for a price no more than your reasonable cost of physically performing this conveying of source, or (2) access to copy the Corresponding Source from a network server at no charge.
- c) Convey individual copies of the object code with a copy of the written offer to provide the Corresponding Source. This alternative is allowed only occasionally and noncommercially, and only if you received the object code with such an offer, in accord with subsection 6b.
- d) Convey the object code by offering access from a designated place (gratis or for a charge), and offer equivalent access to the Corresponding Source in the same way through the same place at no further charge. You need not require recipients to copy the Corresponding Source along with the object code. If the place to copy the object code is a network server, the Corresponding Source may be on a different server (operated by you or a third party) that supports equivalent copying facilities, provided you maintain clear directions next to the object code saying where to find the

Corresponding Source. Regardless of what server hosts the Corresponding Source, you remain obligated to ensure that it is available for as long as needed to satisfy these requirements.

e) Convey the object code using peer-to-peer transmission, provided you inform other peers where the object code and Corresponding Source of the work are being offered to the general public at no charge under subsection 6d.

A separable portion of the object code, whose source code is excluded from the Corresponding Source as a System Library, need not be included in conveying the object code work.

A "User Product" is either (1) a "consumer product", which means any tangible personal property which is normally used for personal, family, or household purposes, or (2) anything designed or sold for incorporation into a dwelling. In determining whether a product is a consumer product, doubtful cases shall be resolved in favor of coverage. For a particular product received by a particular user, "normally used" refers to a typical or common use of that class of product, regardless of the status of the particular user or of the way in which the particular user actually uses, or expects or is expected to use, the product. A product is a consumer product regardless of whether the product has substantial commercial, industrial or non-consumer uses, unless such uses represent the only significant mode of use of the product.

"Installation Information" for a User Product means any methods, procedures, authorization keys, or other information required to install and execute modified versions of a covered work in that User Product from a modified version of its Corresponding Source. The information must suffice to ensure that the continued functioning of the modified object code is in no case prevented or interfered with solely because modification has been made.

If you convey an object code work under this section in, or with, or specifically for use in, a User Product, and the conveying occurs as part of a transaction in which the right of possession and use of the User Product is transferred to the recipient in perpetuity or for a fixed term (regardless of how the transaction is characterized), the Corresponding Source conveyed under this section must be accompanied by the Installation Information. But this requirement does not apply if neither you nor any third party retains the ability to install modified object code on the User Product (for example, the work has been installed in ROM).

The requirement to provide Installation Information does not include a requirement to continue to provide support service, warranty, or updates for a work that has been modified or installed by the recipient, or for the User Product in which it has been modified or installed. Access to a network may be denied when the modification itself materially and adversely affects the operation of the network or violates the rules and protocols for communication across the network.

Corresponding Source conveyed, and Installation Information provided, in accord with this section must be in a format that is publicly documented (and with an implementation available to the public in source code form), and must require no special password or key for unpacking, reading or copying.

7. Additional Terms.

"Additional permissions" are terms that supplement the terms of this License by making exceptions from one or more of its conditions. Additional permissions that are applicable to the entire Program shall be treated as though they were included in this License, to the extent that they are valid under applicable law. If additional permissions apply only to part of the Program, that part may be used separately under those permissions, but the entire Program remains governed by this License without regard to the additional permissions.

When you convey a copy of a covered work, you may at your option remove any additional permissions from that copy, or from any part of it. (Additional permissions may be written to require their own removal in certain cases when you modify the work.) You may place additional permissions on material, added by you to a covered work, for which you have or can give appropriate copyright permission.

Notwithstanding any other provision of this License, for material you add to a covered work, you may (if authorized by the copyright holders of that material) supplement the terms of this License with terms:

- a) Disclaiming warranty or limiting liability differently from the terms of sections 15 and 16 of this License; or
- b) Requiring preservation of specified reasonable legal notices or author attributions in that material or in the Appropriate Legal Notices displayed by works containing it; or
- c) Prohibiting misrepresentation of the origin of that material, or requiring that modified versions of such material be marked in reasonable ways as different from the original version; or

- d) Limiting the use for publicity purposes of names of licensors or authors of the material; or
- e) Declining to grant rights under trademark law for use of some trade names, trademarks, or service marks; or
- f) Requiring indemnification of licensors and authors of that material by anyone who conveys the material (or modified versions of it) with contractual assumptions of liability to the recipient, for any liability that these contractual assumptions directly impose on those licensors and authors.

All other non-permissive additional terms are considered "further restrictions" within the meaning of section 10. If the Program as you received it, or any part of it, contains a notice stating that it is governed by this License along with a term that is a further restriction, you may remove that term. If a license document contains a further restriction but permits relicensing or conveying under this License, you may add to a covered work material governed by the terms of that license document, provided that the further restriction does not survive such relicensing or conveying.

If you add terms to a covered work in accord with this section, you must place, in the relevant source files, a statement of the additional terms that apply to those files, or a notice indicating where to find the applicable terms.

Additional terms, permissive or non-permissive, may be stated in the form of a separately written license, or stated as exceptions; the above requirements apply either way.

8. Termination.

You may not propagate or modify a covered work except as expressly provided under this License. Any attempt otherwise to propagate or modify it is void, and will automatically terminate your rights under this License (including any patent licenses granted under the third paragraph of section 11).

However, if you cease all violation of this License, then your license from a particular copyright holder is reinstated (a) provisionally, unless and until the copyright holder explicitly and finally terminates your license, and (b) permanently, if the copyright holder fails to notify you of the violation by some reasonable means prior to 60 days after the cessation.

Moreover, your license from a particular copyright holder is reinstated permanently if the copyright holder notifies you of the violation by some reasonable means, this is the first time you have received notice of violation of this License (for any work) from that copyright holder, and you cure the violation prior to 30 days after your receipt of the notice.

Termination of your rights under this section does not terminate the licenses of parties who have received copies or rights from you under this License. If your rights have been terminated and not permanently reinstated, you do not qualify to receive new licenses for the same material under section 10.

9. Acceptance Not Required for Having Copies.

You are not required to accept this License in order to receive or run a copy of the Program. Ancillary propagation of a covered work occurring solely as a consequence of using peer-to-peer transmission to receive a copy likewise does not require acceptance. However, nothing other than this License grants you permission to propagate or modify any covered work. These actions infringe copyright if you do not accept this License. Therefore, by modifying or propagating a covered work, you indicate your acceptance of this License to do so.

10. Automatic Licensing of Downstream Recipients.

Each time you convey a covered work, the recipient automatically receives a license from the original licensors, to run, modify and propagate that work, subject to this License. You are not responsible for enforcing compliance by third parties with this License.

An "entity transaction" is a transaction transferring control of an organization, or substantially all assets of one, or subdividing an organization, or merging organizations. If propagation of a covered work results from an entity transaction, each party to that transaction who receives a copy of the work also receives whatever licenses to the work the party's predecessor in interest had or could give under the previous paragraph, plus a right to possession of the Corresponding Source of the work from the predecessor in interest, if the predecessor has it or can get it with reasonable efforts.

You may not impose any further restrictions on the exercise of the rights granted or affirmed under this License. For example, you may not impose a license fee, royalty, or other charge for exercise of

rights granted under this License, and you may not initiate litigation (including a cross-claim or counterclaim in a lawsuit) alleging that any patent claim is infringed by making, using, selling, offering for sale, or importing the Program or any portion of it.

11. Patents.

A "contributor" is a copyright holder who authorizes use under this License of the Program or a work on which the Program is based. The work thus licensed is called the contributor's "contributor version".

A contributor's "essential patent claims" are all patent claims owned or controlled by the contributor, whether already acquired or hereafter acquired, that would be infringed by some manner, permitted by this License, of making, using, or selling its contributor version, but do not include claims that would be infringed only as a consequence of further modification of the contributor version. For purposes of this definition, "control" includes the right to grant patent sublicenses in a manner consistent with the requirements of this License.

Each contributor grants you a non-exclusive, worldwide, royalty-free patent license under the contributor's essential patent claims, to make, use, sell, offer for sale, import and otherwise run, modify and propagate the contents of its contributor version.

In the following three paragraphs, a "patent license" is any express agreement or commitment, however denominated, not to enforce a patent (such as an express permission to practice a patent or covenant not to sue for patent infringement). To "grant" such a patent license to a party means to make such an agreement or commitment not to enforce a patent against the party.

If you convey a covered work, knowingly relying on a patent license, and the Corresponding Source of the work is not available for anyone to copy, free of charge and under the terms of this License, through a publicly available network server or other readily accessible means, then you must either (1) cause the Corresponding Source to be so available, or (2) arrange to deprive yourself of the benefit of the patent license for this particular work, or (3) arrange, in a manner consistent with the requirements of this License, to extend the patent license to downstream recipients. "Knowingly relying" means you have actual knowledge that, but for the patent license, your conveying the covered work in a country, or your recipient's use of the covered work in a country, would infringe one or more identifiable patents in that country that you have reason to believe are valid.

If, pursuant to or in connection with a single transaction or arrangement, you convey, or propagate by procuring conveyance of, a covered work, and grant a patent license to some of the parties receiving the covered work authorizing them to use, propagate, modify or convey a specific copy of the covered work, then the patent license you grant is automatically extended to all recipients of the covered work and works based on it.

A patent license is "discriminatory" if it does not include within the scope of its coverage, prohibits the exercise of, or is conditioned on the non-exercise of one or more of the rights that are specifically granted under this License. You may not convey a covered work if you are a party to an arrangement with a third party that is in the business of distributing software, under which you make payment to the third party based on the extent of your activity of conveying the work, and under which the third party grants, to any of the parties who would receive the covered work from you, a discriminatory patent license (a) in connection with copies of the covered work conveyed by you (or copies made from those copies), or (b) primarily for and in connection with specific products or compilations that contain the covered work, unless you entered into that arrangement, or that patent license was granted, prior to 28 March 2007.

Nothing in this License shall be construed as excluding or limiting any implied license or other defenses to infringement that may otherwise be available to you under applicable patent law.

12. No Surrender of Others' Freedom.

If conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot convey a covered work so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not convey it at all. For example, if you agree to terms that obligate you to collect a royalty for further conveying from those to whom you convey the Program, the only way you could satisfy both those terms and this License would be to refrain entirely from conveying the Program.

13. Use with the GNU Affero General Public License.

Notwithstanding any other provision of this License, you have permission to link or combine any covered work with a work licensed under version 3 of the GNU Affero General Public License into a single combined work, and to convey the resulting work. The terms of this

License will continue to apply to the part which is the covered work, but the special requirements of the GNU Affero General Public License, section 13, concerning interaction through a network will apply to the combination as such.

14. Revised Versions of this License.

The Free Software Foundation may publish revised and/or new versions of the GNU General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Program specifies that a certain numbered version of the GNU General Public License "or any later version" applies to it, you have the option of following the terms and conditions either of that numbered version or of any later version published by the Free Software Foundation. If the Program does not specify a version number of the GNU General Public License, you may choose any version ever published by the Free Software Foundation.

If the Program specifies that a proxy can decide which future versions of the GNU General Public License can be used, that proxy's public statement of acceptance of a version permanently authorizes you to choose that version for the Program.

Later license versions may give you additional or different permissions. However, no additional obligations are imposed on any author or copyright holder as a result of your choosing to follow a later version.

15. Disclaimer of Warranty.

THERE IS NO WARRANTY FOR THE PROGRAM, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE PROGRAM "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE PROGRAM IS WITH YOU. SHOULD THE PROGRAM PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

16. Limitation of Liability.

IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MODIFIES AND/OR CONVEYS

THE PROGRAM AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE PROGRAM (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE PROGRAM TO OPERATE WITH ANY OTHER PROGRAMS), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

17.

Interpretation of Sections 15 and 16.

If the disclaimer of warranty and limitation of liability provided above cannot be given local legal effect according to their terms, reviewing courts shall apply local law that most closely approximates an absolute waiver of all civil liability in connection with the Program, unless a warranty or assumption of liability accompanies a copy of the Program in return for a fee.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Programs

If you develop a new program, and you want it to be of the greatest possible use to the public, the best way to achieve this is to make it free software which everyone can redistribute and change under these terms.

To do so, attach the following notices to the program. It is safest to attach them to the start of each source file to most effectively state the exclusion of warranty; and each file should have at least the "copyright" line and a pointer to where the full notice is found.

```
<one line to give the program's name and a brief idea of what it does.>  
Copyright (C) <year> <name of author>
```

This program is free software: you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation, either version 3 of the License, or (at your option) any later version.

This program is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details.

You should have received a copy of the GNU General Public License along with this program. If not, see <http://www.gnu.org/licenses/>.

Also add information on how to contact you by electronic and paper mail.

If the program does terminal interaction, make it output a short notice like this when it starts in an interactive mode:

```
<program> Copyright (C) <year> <name of author>
This program comes with ABSOLUTELY NO WARRANTY; for details type `show w'.
This is free software, and you are welcome to redistribute it
under certain conditions; type `show c' for details.
```

The hypothetical commands `show w' and `show c' should show the appropriate parts of the General Public License. Of course, your program's commands might be different; for a GUI interface, you would use an "about box".

You should also get your employer (if you work as a programmer) or school, if any, to sign a "copyright disclaimer" for the program, if necessary. For more information on this, and how to apply and follow the GNU GPL, see <http://www.gnu.org/licenses/>.

The GNU General Public License does not permit incorporating your program into proprietary programs. If your program is a subroutine library, you may consider it more useful to permit linking proprietary applications with the library. If this is what you want to do, use the GNU Lesser General Public License instead of this License. But first, please read <http://www.gnu.org/philosophy/why-not-lgpl.html>.
@c The GNU General Public License.
@center Version 3, 29 June 2007

@c This file is intended to be included within another document,
@c hence no sectioning command or @node.

@display
Copyright @copyright{ } 2007 Free Software Foundation, Inc. @url{http://fsf.org/}

Everyone is permitted to copy and distribute verbatim copies of this license document, but changing it is not allowed.
@end display

@heading Preamble

The GNU General Public License is a free, copyleft license for software and other kinds of works.

The licenses for most software and other practical works are designed to take away your freedom to share and change the works. By contrast, the GNU General Public License is intended to guarantee your freedom

to share and change all versions of a program---to make sure it remains free software for all its users. We, the Free Software Foundation, use the GNU General Public License for most of our software; it applies also to any other work released this way by its authors. You can apply it to your programs, too.

When we speak of free software, we are referring to freedom, not price. Our General Public Licenses are designed to make sure that you have the freedom to distribute copies of free software (and charge for them if you wish), that you receive source code or can get it if you want it, that you can change the software or use pieces of it in new free programs, and that you know you can do these things.

To protect your rights, we need to prevent others from denying you these rights or asking you to surrender the rights. Therefore, you have certain responsibilities if you distribute copies of the software, or if you modify it: responsibilities to respect the freedom of others.

For example, if you distribute copies of such a program, whether gratis or for a fee, you must pass on to the recipients the same freedoms that you received. You must make sure that they, too, receive or can get the source code. And you must show them these terms so they know their rights.

Developers that use the GNU GPL protect your rights with two steps: (1) assert copyright on the software, and (2) offer you this License giving you legal permission to copy, distribute and/or modify it.

For the developers' and authors' protection, the GPL clearly explains that there is no warranty for this free software. For both users' and authors' sake, the GPL requires that modified versions be marked as changed, so that their problems will not be attributed erroneously to authors of previous versions.

Some devices are designed to deny users access to install or run modified versions of the software inside them, although the manufacturer can do so. This is fundamentally incompatible with the aim of protecting users' freedom to change the software. The systematic pattern of such abuse occurs in the area of products for individuals to use, which is precisely where it is most unacceptable. Therefore, we have designed this version of the GPL to prohibit the practice

for those products. If such problems arise substantially in other domains, we stand ready to extend this provision to those domains in future versions of the GPL, as needed to protect the

freedom of users.

Finally, every program is threatened constantly by software patents. States should not allow patents to restrict development and use of software on general-purpose computers, but in those that do, we wish to avoid the special danger that patents applied to a free program could make it effectively proprietary. To prevent this, the GPL assures that patents cannot be used to render the program non-free.

The precise terms and conditions for copying, distribution and modification follow.

@heading TERMS AND CONDITIONS

@enumerate 0

@item Definitions.

``This License" refers to version 3 of the GNU General Public License.

``Copyright" also means copyright-like laws that apply to other kinds of works, such as semiconductor masks.

``The Program" refers to any copyrightable work licensed under this License. Each licensee is addressed as ``you". ``Licensees" and ``recipients" may be individuals or organizations.

To ``modify" a work means to copy from or adapt all or part of the work in a fashion requiring copyright permission, other than the making of an exact copy. The resulting work is called a ``modified version" of the earlier work or a work ``based on" the earlier work.

A ``covered work" means either the unmodified Program or a work based on the Program.

To ``propagate" a work means to do anything with it that, without permission, would make you directly or secondarily liable for infringement under applicable copyright law, except executing it on a computer or modifying a private copy. Propagation includes copying, distribution (with or without modification), making available to the public, and in some countries other activities as well.

To ``convey" a work means any kind of propagation that enables other parties to make or receive copies. Mere interaction with a user through a computer network, with no transfer of a copy, is not conveying.

An interactive user interface displays "Appropriate Legal Notices" to the extent that it includes a convenient and prominently visible feature that (1) displays an appropriate copyright notice, and (2) tells the user that there is no warranty for the work (except to the extent that warranties are provided), that licensees may convey the work under this License, and how to view a copy of this License. If the interface presents a list of user commands or options, such as a menu, a prominent item in the list meets this criterion.

@item Source Code.

The "source code" for a work means the preferred form of the work for making modifications to it. "Object code" means any non-source form of a work.

A "Standard Interface" means an interface that either is an official standard defined by a recognized standards body, or, in the case of interfaces specified for a particular programming language, one that is widely used among developers working in that language.

The "System Libraries" of an executable work include anything, other than the work as a whole, that (a) is included in the normal form of packaging a Major Component, but which is not part of that Major Component, and (b) serves only to enable use of the work with that Major Component, or to implement a Standard Interface for which an implementation is available to the public in source code form. A "Major Component", in this context, means a major essential component (kernel, window system, and so on) of the specific operating system (if any) on which the executable work runs, or a compiler used to produce the work, or an object code interpreter used to run it.

The "Corresponding Source" for a work in object code form means all the source code needed to generate, install, and (for an executable work) run the object code and to modify the work, including scripts to control those activities. However, it does not include the work's System Libraries, or general-purpose tools or generally available free programs which are used unmodified in performing those activities but which are not part of the work. For example, Corresponding Source includes interface definition files associated with source files for the work, and the source code for shared libraries and dynamically linked subprograms that the work is specifically designed to require, such as by intimate data communication or control flow between those subprograms and other parts of the work.

The Corresponding Source need not include anything that users can regenerate automatically from other parts of the Corresponding Source.

The Corresponding Source for a work in source code form is that same work.

@item Basic Permissions.

All rights granted under this License are granted for the term of copyright on the Program, and are irrevocable provided the stated conditions are met. This License explicitly affirms your unlimited permission

to run the unmodified Program. The output from running a covered work is covered by this License only if the output, given its content, constitutes a covered work. This License acknowledges your rights of fair use or other equivalent, as provided by copyright law.

You may make, run and propagate covered works that you do not convey, without conditions so long as your license otherwise remains in force. You may convey covered works to others for the sole purpose of having them make modifications exclusively for you, or provide you with facilities for running those works, provided that you comply with the terms of this License in conveying all material for which you do not control copyright. Those thus making or running the covered works for you must do so exclusively on your behalf, under your direction and control, on terms that prohibit them from making any copies of your copyrighted material outside their relationship with you.

Conveying under any other circumstances is permitted solely under the conditions stated below. Sublicensing is not allowed; section 10 makes it unnecessary.

@item Protecting Users' Legal Rights From Anti-Circumvention Law.

No covered work shall be deemed part of an effective technological measure under any applicable law fulfilling obligations under article 11 of the WIPO copyright treaty adopted on 20 December 1996, or similar laws prohibiting or restricting circumvention of such measures.

When you convey a covered work, you waive any legal power to forbid circumvention of technological measures to the extent such circumvention is effected by exercising rights under this License with respect to the covered work, and you disclaim any intention to limit operation or modification of the work as a means of enforcing, against the work's users, your or third parties' legal rights to forbid circumvention of technological measures.

@item Conveying Verbatim Copies.

You may convey verbatim copies of the Program's source code as you receive it, in any medium, provided that you conspicuously and appropriately publish on each copy an appropriate copyright notice; keep intact all notices stating that this License and any non-permissive terms added in accord with section 7 apply to the code; keep intact all notices of the absence of any warranty; and give all recipients a copy of this License along with the Program.

You may charge any price or no price for each copy that you convey, and you may offer support or warranty protection for a fee.

@item Conveying Modified Source Versions.

You may convey a work based on the Program, or the modifications to produce it from the Program, in the form of source code under the terms of section 4, provided that you also meet all of these conditions:

@enumerate a

@item

The work must carry prominent notices stating that you modified it, and giving a relevant date.

@item

The work must carry prominent notices stating that it is released under this License and any conditions added under section 7. This requirement modifies the requirement in section 4 to ``keep intact all notices".

@item

You must license the entire work, as a whole, under this License to anyone who comes into possession of a copy. This License will therefore apply, along with any applicable section 7 additional terms, to the whole of the work, and all its parts, regardless of how they are packaged. This License gives no permission to license the work in any other way, but it does not invalidate such permission if you have separately received it.

@item

If the work has interactive user interfaces, each must display Appropriate Legal Notices; however, if the Program has interactive interfaces that do not display Appropriate Legal Notices, your work need not make them do so.

@end enumerate

A compilation of a covered work with other separate and independent works, which are not by their nature extensions of the covered work, and which are not combined with it such as to form a larger program, in

or on a volume of a storage or distribution medium, is called an "aggregate" if the compilation and its resulting copyright are not used to limit the access or legal rights of the compilation's users beyond what the individual works permit. Inclusion of a covered work in an aggregate does not cause this License to apply to the other parts of the aggregate.

@item Conveying Non-Source Forms.

You may convey a covered work in object code form under the terms of sections 4 and 5, provided that you also convey the machine-readable Corresponding Source under the terms of this License, in one of these ways:

@enumerate a

@item

Convey the object code in, or embodied in, a physical product (including a physical distribution medium), accompanied by the Corresponding Source fixed on a durable physical medium customarily used for software interchange.

@item

Convey the object code in, or embodied in, a physical product (including a physical distribution medium), accompanied by a written offer, valid for at least three years and valid for as long as you offer spare parts or customer support for that product model, to give anyone who possesses the object code either (1) a copy of the Corresponding Source for all the software in the product that is covered by this License, on a durable physical medium customarily used for software interchange, for a price no more than your reasonable cost of physically performing this conveying of source, or (2) access to copy the Corresponding Source from a network server at no charge.

@item

Convey individual copies of the object code with a copy of the written offer to provide the Corresponding Source. This alternative is allowed only occasionally and noncommercially, and only if you received the object code with such an offer, in accord with subsection 6b.

@item

Convey the object code by offering access from a designated place (gratis or for a charge), and offer equivalent access to the

Corresponding Source in the same way through the same place at no further charge. You need not require recipients to copy the Corresponding Source along with the object code. If the place to copy the object code is a network server, the Corresponding Source may be on a different server (operated by you or a third party) that supports equivalent copying facilities, provided you maintain clear directions next to the object code saying where to find the Corresponding Source. Regardless of what server hosts the Corresponding Source, you remain obligated to ensure that it is available for as long as needed to satisfy these requirements.

@item

Convey the object code using peer-to-peer transmission, provided you inform other peers where the object code and Corresponding Source of the work are being offered to the general public at no charge under subsection 6d.

@end enumerate

A separable portion of the object code, whose source code is excluded from the Corresponding Source as a System Library, need not be included in conveying the object code work.

A "User Product" is either (1) a "consumer product", which means any tangible personal property which is normally used for personal, family, or household purposes, or (2) anything designed or sold for incorporation into a dwelling. In determining whether a product is a consumer product, doubtful cases shall be resolved in favor of coverage. For a particular product received by a particular user, "normally used" refers to a typical or common use of that class of product, regardless of the status of the particular user or of the way in which the particular user actually uses, or expects or is expected to use, the product. A product is a consumer product regardless of whether the product has substantial commercial, industrial or non-consumer uses, unless such uses represent the only significant mode of use of the product.

"Installation Information" for a User Product means any methods, procedures, authorization keys, or other information required to install and execute modified versions of a covered work in that User Product from a modified version of its Corresponding Source. The information must suffice to ensure that the continued functioning of the modified object code is in no case prevented or interfered with solely because modification has been made.

If you convey an object code work under this section in, or with, or specifically for use in, a User Product, and the conveying occurs as part of a transaction in which the right of possession and use of the User Product is transferred to the recipient in perpetuity or for a fixed term (regardless of how the transaction is characterized), the Corresponding Source conveyed under this section must be accompanied by the Installation Information. But this requirement does not apply if neither you nor any third party retains the ability to install modified object code on the User Product (for example, the work has been installed in ROM).

The requirement to provide Installation Information does not include a requirement to continue to provide support service, warranty, or updates for a work that has been modified or installed by the recipient, or for the User Product in which it has been modified or installed. Access to a network may be denied when the modification itself materially and adversely affects the operation of the network or violates the rules and protocols for communication across the network.

Corresponding Source conveyed, and Installation Information provided, in accord with this section must be in a format that is publicly documented (and with an implementation available to the public in source code form), and must require no special password or key for unpacking, reading or copying.

@item Additional Terms.

``Additional permissions'' are terms that supplement the terms of this License by making exceptions from one or more of its conditions. Additional permissions that are applicable to the entire Program shall be treated as though they were included in this License, to the extent that they are valid under applicable law. If additional permissions apply only to part of the Program, that part may be used separately under those permissions, but the entire Program remains governed by this License without regard to the additional permissions.

When you convey a copy of a covered work, you may at your option remove any additional permissions from that copy, or from any part of it. (Additional permissions may be written to require their own removal in certain cases when you modify the work.) You may place additional permissions on material, added by you to a covered work, for which you have or can give appropriate copyright permission.

Notwithstanding any other provision of this License, for material you add to a covered work, you may (if authorized by the copyright holders

of that material) supplement the terms of this License with terms:

@enumerate a

@item

Disclaiming warranty or limiting liability differently from the terms of

sections 15 and 16 of this License; or

@item

Requiring preservation of specified reasonable legal notices or author attributions in that material or in the Appropriate Legal Notices displayed by works containing it; or

@item

Prohibiting misrepresentation of the origin of that material, or requiring that modified versions of such material be marked in reasonable ways as different from the original version; or

@item

Limiting the use for publicity purposes of names of licensors or authors of the material; or

@item

Declining to grant rights under trademark law for use of some trade names, trademarks, or service marks; or

@item

Requiring indemnification of licensors and authors of that material by anyone who conveys the material (or modified versions of it) with contractual assumptions of liability to the recipient, for any liability that these contractual assumptions directly impose on those licensors and authors.

@end enumerate

All other non-permissive additional terms are considered

``further

restrictions" within the meaning of section 10. If the Program as you received it, or any part of it, contains a notice stating that it is governed by this License along with a term that is a further restriction, you may remove that term. If a license document contains a further restriction but permits relicensing or conveying under this License, you may add to a covered work material governed by the terms of that license document, provided that the further restriction does not survive such relicensing or conveying.

If you add terms to a covered work in accord with this section, you must place, in the relevant source files, a statement of the additional terms that apply to those files, or a notice indicating

where to find the applicable terms.

Additional terms, permissive or non-permissive, may be stated in the form of a separately written license, or stated as exceptions; the above requirements apply either way.

@item Termination.

You may not propagate or modify a covered work except as expressly provided under this License. Any attempt otherwise to propagate or modify it is void, and will automatically terminate your rights under this License (including any patent licenses granted under the third paragraph of section 11).

However, if you cease all violation of this License, then your license from a particular copyright holder is reinstated (a) provisionally, unless and until the copyright holder explicitly and finally terminates your license, and (b) permanently, if the copyright holder fails to notify you of the violation by some reasonable means prior to 60 days after the cessation.

Moreover, your license from a particular copyright holder is reinstated permanently if the copyright holder notifies you of the violation by some reasonable means, this is the first time you have received notice of violation of this License (for any work) from that copyright holder, and you cure the violation prior to 30 days after your receipt of the notice.

Termination

of your rights under this section does not terminate the licenses of parties who have received copies or rights from you under this License. If your rights have been terminated and not permanently reinstated, you do not qualify to receive new licenses for the same material under section 10.

@item Acceptance Not Required for Having Copies.

You are not required to accept this License in order to receive or run a copy of the Program. Ancillary propagation of a covered work occurring solely as a consequence of using peer-to-peer transmission to receive a copy likewise does not require acceptance. However, nothing other than this License grants you permission to propagate or modify any covered work. These actions infringe copyright if you do not accept this License. Therefore, by modifying or propagating a covered work, you indicate your acceptance of this License to do so.

@item Automatic Licensing of Downstream Recipients.

Each time you convey a covered work, the recipient automatically receives a license from the original licensors, to run, modify and propagate that work, subject to this License. You are not responsible for enforcing compliance by third parties with this License.

An "entity transaction" is a transaction transferring control of an organization, or substantially all assets of one, or subdividing an organization, or merging organizations. If propagation of a covered work results from an entity transaction, each party to that transaction who receives a copy of the work also receives whatever licenses to the work the party's predecessor in interest had or could give under the previous paragraph, plus a right to possession of the Corresponding Source of the work from the predecessor in interest, if the predecessor has it or can get it with reasonable efforts.

You may not impose any further restrictions on the exercise of the rights granted or affirmed under this License. For example, you may not impose a license fee, royalty, or other charge for exercise of rights granted under this License, and you may not initiate litigation (including a cross-claim or counterclaim in a lawsuit) alleging that any patent claim is infringed by making, using, selling, offering for sale, or importing the Program or any portion of it.

@item Patents.

A "contributor" is a copyright holder who authorizes use under this License of the Program or a work on which the Program is based. The work thus licensed is called the contributor's "contributor version".

A contributor's "essential patent claims" are all patent claims owned or controlled by the contributor, whether already acquired or hereafter acquired, that would be infringed by some manner, permitted by this License, of making, using, or selling its contributor version, but do not include claims that would be infringed only as a consequence of further modification of the contributor version. For purposes of this definition, "control" includes the right to grant patent sublicenses in a manner consistent with the requirements of this License.

Each contributor grants you a non-exclusive, worldwide, royalty-free patent license under the contributor's essential patent claims, to make, use, sell, offer for sale, import and otherwise run, modify and propagate the contents of its contributor version.

In the following three paragraphs, a "patent license" is any express agreement or commitment, however denominated, not to enforce a patent (such as an express permission to practice a patent or covenant not to sue for patent infringement). To "grant" such a patent license to a party means to make such an agreement or commitment not to enforce a patent against the party.

If you convey a covered work, knowingly relying on a patent license, and the Corresponding Source of the work is not available for anyone to copy, free of charge and under the terms of this License, through a publicly available network server or other readily accessible means, then you

must either (1) cause the Corresponding Source to be so available, or (2) arrange to deprive yourself of the benefit of the patent license for this particular work, or (3) arrange, in a manner consistent with the requirements of this License, to extend the patent license to downstream recipients. "Knowingly relying" means you have actual knowledge that, but for the patent license, your conveying the covered work in a country, or your recipient's use of the covered work in a country, would infringe one or more identifiable patents in that country that you have reason to believe are valid.

If, pursuant to or in connection with a single transaction or arrangement, you convey, or propagate by procuring conveyance of, a covered work, and grant a patent license to some of the parties receiving the covered work authorizing them to use, propagate, modify or convey a specific copy of the covered work, then the patent license you grant is automatically extended to all recipients of the covered work and works based on it.

A patent license is "discriminatory" if it does not include within the scope of its coverage, prohibits the exercise of, or is conditioned on the non-exercise of one or more of the rights that are specifically granted under this License. You may not convey a covered work if you are a party to an arrangement with a third party that is in the business of distributing software, under which you make payment to the third party based on the extent of your activity of conveying the work, and under which the third party grants, to any of the parties who would receive the covered work from you, a discriminatory patent license (a) in connection with copies of the covered work conveyed by you (or copies made from those copies), or (b) primarily for and in connection with specific products or compilations that contain the covered work, unless you entered into that arrangement, or that patent license was granted, prior to 28 March 2007.

Nothing in this License shall

be construed as excluding or limiting any implied license or other defenses to infringement that may otherwise be available to you under applicable patent law.

@item No Surrender of Others' Freedom.

If conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot convey a covered work so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not convey it at all. For example, if you agree to terms that obligate you to collect a royalty for further conveying from those to whom you convey the Program, the only way you could satisfy both those terms and this License would be to refrain entirely from conveying the Program.

@item Use with the GNU Affero General Public License.

Notwithstanding any other provision of this License, you have permission to link or combine any covered work with a work licensed under version 3 of the GNU Affero General Public License into a single combined work, and to convey the resulting work. The terms of this License will continue to apply to the part which is the covered work, but the special requirements of the GNU Affero General Public License, section 13, concerning interaction through a network will apply to the combination as such.

@item Revised Versions of this License.

The Free Software Foundation may publish revised and/or new versions of the GNU General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Program specifies that a certain numbered version of the GNU General Public License "or any later version" applies to it, you have the option of following the terms and conditions either of that numbered version or of any later version published by the Free Software Foundation. If the Program does not specify a version number of the GNU General Public License, you may choose any version ever published by the Free Software Foundation.

If the Program specifies that a proxy can decide which future versions of the GNU General Public License can be used, that proxy's public

statement of acceptance of a version permanently authorizes you to choose that version for the Program.

Later license versions may give you additional or different permissions. However, no additional obligations are imposed on any author or copyright holder as a result of your choosing to follow a later version.

@item Disclaimer of Warranty.

THERE IS NO WARRANTY FOR THE PROGRAM, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE PROGRAM ``AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE PROGRAM IS WITH YOU. SHOULD THE PROGRAM PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

@item Limitation of Liability.

IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MODIFIES AND/OR CONVEYS THE PROGRAM AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE PROGRAM (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE PROGRAM TO OPERATE WITH ANY OTHER PROGRAMS), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

@item Interpretation of Sections 15 and 16.

If the disclaimer of warranty and limitation of liability provided above cannot be given local legal effect according to their terms, reviewing courts shall apply local law that most closely approximates an absolute waiver of all civil liability in connection with the Program, unless a warranty or assumption of liability accompanies a copy of the Program in return for a fee.

@end enumerate

@heading END OF TERMS AND CONDITIONS

@heading How to Apply These Terms to Your New Programs

If you develop a new program, and you want it to be of the greatest possible use to the public, the best way to achieve this is to make it free software which everyone can redistribute and change under these terms.

To do so, attach the following notices to the program. It is safest to attach them to the start of each source file to most effectively state the exclusion of warranty; and each file should have at least the ``copyright" line and a pointer to where the full notice is found.

```
@smallexample
@var{one line to give the program's name and a brief idea of what it does.}
Copyright
(C) @var{year} @var{name of author}
```

This program is free software: you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation, either version 3 of the License, or (at your option) any later version.

This program is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details.

You should have received a copy of the GNU General Public License along with this program. If not, see [@url{http://www.gnu.org/licenses/}](http://www.gnu.org/licenses/).
@end smallexample

Also add information on how to contact you by electronic and paper mail.

If the program does terminal interaction, make it output a short notice like this when it starts in an interactive mode:

```
@smallexample
@var{program} Copyright (C) @var{year} @var{name of author}
This program comes with ABSOLUTELY NO WARRANTY;
for details type @samp{show w}.
This is free software, and you are welcome to redistribute it
under certain conditions; type @samp{show c} for details.
@end smallexample
```

The hypothetical commands @samp{show w} and @samp{show c} should show the appropriate parts of the General Public License. Of course, your program's commands might be different; for a GUI interface, you would use an ``about box".

You should also get your employer (if you work as a programmer) or school, if any, to sign a "copyright disclaimer" for the program, if necessary. For more information on this, and how to apply and follow the GNU GPL, see [@url{http://www.gnu.org/licenses/}](http://www.gnu.org/licenses/).

The GNU General Public License does not permit incorporating your program into proprietary programs. If your program is a subroutine library, you may consider it more useful to permit linking proprietary applications with the library. If this is what you want to do, use the GNU Lesser General Public License instead of this License.

But

first, please read [@url{http://www.gnu.org/philosophy/why-not-lgpl.html}](http://www.gnu.org/philosophy/why-not-lgpl.html).

GNU LESSER GENERAL PUBLIC LICENSE

Version 3, 29 June 2007

Copyright (C) 2007 Free Software Foundation, Inc. <<http://fsf.org/>>
Everyone is permitted to copy and distribute verbatim copies of this license document, but changing it is not allowed.

This version of the GNU Lesser General Public License incorporates the terms and conditions of version 3 of the GNU General Public License, supplemented by the additional permissions listed below.

0. Additional Definitions.

As used herein, "this License" refers to version 3 of the GNU Lesser General Public License, and the "GNU GPL" refers to version 3 of the GNU General Public License.

"The Library" refers to a covered work governed by this License, other than an Application or a Combined Work as defined below.

An "Application" is any work that makes use of an interface provided by the Library, but which is not otherwise based on the Library. Defining a subclass of a class defined by the Library is deemed a mode of using an interface provided by the Library.

A "Combined Work" is a work produced by combining or linking an Application with the Library. The particular version of the Library with which the Combined Work was made is also called the "Linked Version".

The "Minimal Corresponding Source" for a Combined Work means the Corresponding Source for the Combined Work, excluding any source code for portions of the Combined Work that, considered in isolation, are based on the Application, and not on the Linked Version.

The "Corresponding Application Code" for a Combined Work means the object code and/or source code for the Application, including any data and utility programs needed for reproducing the Combined Work from the Application, but excluding the System Libraries of the Combined Work.

1. Exception to Section 3 of the GNU GPL.

You may convey a covered work under sections 3 and 4 of this License without being bound by section 3 of the GNU GPL.

2. Conveying Modified Versions.

If you modify a copy of the Library, and, in your modifications, a facility refers to a function or data to be supplied by an Application that uses the facility (other than as an argument passed when the facility is invoked), then you may convey a copy of the modified version:

- a) under this License, provided that you make a good faith effort to ensure that, in the event an Application does not supply the function or data, the facility still operates, and performs whatever part of its purpose remains meaningful, or
- b) under the GNU GPL, with none of the additional permissions of this License applicable to that copy.

3. Object Code Incorporating Material from Library Header Files.

The object code form of an Application may incorporate material from a header file that is part of the Library. You may convey such object code under terms of your choice, provided that, if the incorporated material is not limited to numerical parameters, data structure layouts and accessors, or small macros, inline functions and templates (ten or fewer lines in length), you do both of the following:

- a) Give prominent notice with each copy of the object code that the Library is used in it and that the Library and its use are covered by this License.
- b) Accompany the object code with a copy of the GNU GPL and this license document.

4. Combined Works.

You may convey a Combined Work under terms of your choice that,

taken together, effectively do not restrict modification of the portions of the Library contained in the Combined Work and reverse engineering for debugging such modifications, if you also do each of the following:

a) Give prominent notice with each copy of the Combined Work that the Library is used in it and that the Library and its use are covered by this License.

b) Accompany the Combined Work with a copy of the GNU GPL and this license document.

c) For a Combined Work that displays copyright notices during execution, include the copyright notice for the Library among these notices, as well as a reference directing the user to the copies of the GNU GPL and this license document.

d) Do one of the following:

0) Convey the Minimal Corresponding Source under the terms of this License, and the Corresponding Application Code in a form suitable for, and under terms that permit, the user to recombine or relink the Application with a modified version of the Linked Version to produce a modified Combined Work, in the manner specified by section 6 of the GNU GPL for conveying Corresponding Source.

1) Use a suitable shared library mechanism for linking with the Library. A suitable mechanism is one that (a) uses at run time a copy of the Library already present on the user's computer system, and (b) will operate properly with a modified version of the Library that is interface-compatible with the Linked Version.

e) Provide Installation Information, but only if you would otherwise be required to provide such information under section 6 of the GNU GPL, and only to the extent that such information is necessary to install and execute a modified version of the Combined Work produced by recombining or relinking the Application with a modified version of the Linked Version. (If you use option 4d0, the Installation Information must accompany the Minimal Corresponding Source and Corresponding Application Code. If you use option 4d1, you must provide the Installation Information in the manner specified by section 6 of the GNU GPL for conveying Corresponding Source.)

5. Combined Libraries.

You may place library facilities that are a work based on the Library side by side in a single library together with other library facilities that are not Applications and are not covered by this License, and convey such a combined library under terms of your choice, if you do both of the following:

- a) Accompany the combined library with a copy of the same work based on the Library, uncombined with any other library facilities, conveyed under the terms of this License.
- b) Give prominent notice with the combined library that part of it is a work based on the Library, and explaining where to find the accompanying uncombined form of the same work.

6. Revised Versions of the GNU Lesser General Public License.

The Free Software Foundation may publish revised and/or new versions of the GNU Lesser General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Library as you received it specifies that a certain numbered version of the GNU Lesser General Public License "or any later version" applies to it, you have the option of following the terms and conditions either of that published version or of any later version published by the Free Software Foundation. If the Library as you received it does not specify a version number of the GNU Lesser General Public License, you may choose any version of the GNU Lesser General Public License ever published by the Free Software Foundation.

If the Library as you received it specifies that a proxy can decide whether future versions of the GNU Lesser General Public License shall apply, that proxy's public statement of acceptance of any version is permanent authorization for you to choose that version for the Library.

1.19 init-system-helpers 1.51

1.19.1 Available under license :

Format: <https://www.debian.org/doc/packaging-manuals/copyright-format/1.0/>

Files: *

Copyright: 2013 Michael Stapelberg

License: BSD-3-clause

Files: debian/*

Copyright: 2013 Michael Stapelberg <stapelberg@debian.org>

License: BSD-3-clause

Files: script/service man8/service.8

Copyright: 2006 Red Hat, Inc

2008 Canonical Ltd

License: GPL-2+

Files: script/invoke-rc.d man8/invoke-rc.d.8

Copyright: 2000,2001 Henrique de Moraes Holschuh <hnh@debian.org>

License: GPL-2+

Files: script/update-rc.d man8/update-rc.d.8

Copyright: 1997-2005 Miquel van Smoorenburg <miquels@cistron.nl>

Members of the pkg-sysvinit project

License: GPL-2+

License: GPL-2+

This program is free software; you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation; either version 2, or (at your option) any later version.

.

This program is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of

MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details.

.

You should have received a copy of the GNU General Public License along with this program; if not, write to the Free Software Foundation, Inc., 51 Franklin Street, Fifth Floor, Boston, MA 02110-1301, USA.

.

On Debian systems, the complete text of the GNU General Public License version 2 can be found in /usr/share/common-licenses/GPL-2.

License: BSD-3-clause

Copyright 2013 Michael Stapelberg

All rights reserved.

.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

.

* Redistributions of source code must retain the above copyright

notice, this list of conditions and the following disclaimer.

* Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation

and/or other materials provided with the distribution.

* Neither the name of Michael Stapelberg nor the names of contributors may be used to endorse or promote products derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY Michael Stapelberg "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL Michael Stapelberg BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

1.20 procps 3.3.12-3ubuntu1.2

1.20.1 Available under license :

Format: <https://www.debian.org/doc/packaging-manuals/copyright-format/1.0/>

Upstream-Name: procps-ng

Source: <https://gitlab.com/procps-ng/procps>

Files: *

Copyright: 1998-2004 Albert Cahalan

1991 Tony Rems <rembo@unisoft.com>

1993 Larry Greenfield

1996 Charles Blake

1999 Mike Coleman <mkc@acm.org>

2004 Nicholas Miell

2003 Chris Rivera

2003 Robert Love <rml@tech9.net>

2008 Morty Abzug

2009 Jarrod Lowe <procps@rrod.net>

1992 Branko Lankester

???? David Engel <david@ods.com>

1992-1998 Michael K. Johnson <johnsonm@sunsite.unc.edu>

2012 Craig Small <csmall@enc.com.au>

1995 Martin Schulze <joey@infodrom.north.de>

License: LGPL-2.1+

Files: top/*

Copyright: 2002-2014 James C. Warner

License: LGPL-2.0+

Files: pgrep.*

Copyright: 2000 Kjetil Torgrim Homme <kjetilho@ifi.uio.no>

2002,2006 Albert Cahalan

2012 Roberto Polli

<rpolli@babel.it>

License: GPL-2.0+

Files: pidof.*

Copyright: 2013 Jaromir Capik <jcapik@redhat.com>

License: GPL-2.0+

Files: free.*

Copyright: 2011 Sami Kerola <kerolasa@iki.fi>

2002-2003 Robert Love <rml@tech9.net>

1992 Brian Edmonds

1992 Rafal Maszkowski

2004 Albert Cahalan

License: GPL-2.0+

Files: sysctl.*

Copyright: 1999 George Staikos

License: GPL-2.0+

Files: debian/*

Copyright: 1997-2015 Craig Small <csmall@debian.org>

1996-1197 Helmut Geyer <Helmut.Geyer@iwr.uni-heidelberg.de>

License: GPL-2.0+

License: GPL-2.0+

This package is free software; you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation; either version 2 of the License, or (at your option) any later version.

.

This package is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details.

.

You should have received a copy of the GNU General Public License along with this program. If not, see <<https://www.gnu.org/licenses/>>

.

On Debian systems, the complete text of the GNU General

Public License version 2 can be found in "/usr/share/common-licenses/GPL-2".

License: LGPL-2.0+

This package is free software; you can redistribute it and/or modify it under the terms of the GNU Lesser General Public License as published by the Free Software Foundation; either version 2 of the License, or (at your option) any later version.

.

This package is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU Lesser General Public License for more details.

.

You should have received a copy of the GNU General Public License along with this program. If not, see <<https://www.gnu.org/licenses/>>.

.

On Debian systems, the complete text of the GNU Lesser General Public License can be found in "/usr/share/common-licenses/LGPL-2".

License: LGPL-2.1+

This package is free software; you can redistribute it and/or modify it under the terms of the GNU Lesser General Public License as published by the Free Software Foundation; either version 2.1 of the License, or (at your option) any later version.

.

This package is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU Lesser General Public License for more details.

.

You should have received a copy of the GNU General Public License along with this program. If not, see <<https://www.gnu.org/licenses/>>.

.

On Debian systems, the complete text of the GNU Lesser General Public License can be found in "/usr/share/common-licenses/LGPL-2.1".

1.21 grep 3.1-2build1

1.21.1 Available under license :

@c The GNU Free Documentation License.

@center Version 1.3, 3 November 2008

@c This file is intended to be included within another document,

@c hence no sectioning command or @node.

@display

Copyright @copyright{} 2000, 2001, 2002, 2007, 2008 Free Software Foundation, Inc.

@uref{http://fsf.org/}

Everyone is permitted to copy and distribute verbatim copies of this license document, but changing it is not allowed.

@end display

@enumerate 0

@item

PREAMBLE

The purpose of this License is to make a manual, textbook, or other functional and useful document @dfn{free} in the sense of freedom: to assure everyone the effective freedom to copy and redistribute it, with or without modifying it, either commercially or noncommercially. Secondly, this License preserves for the author and publisher a way to get credit for their work, while not being considered responsible for modifications made by others.

This License is a kind of ``copyleft'', which means that derivative works of the document must themselves be free in the same sense. It complements the GNU General Public License, which is a copyleft license designed for free software.

We have designed this License in order to use it for manuals for free software, because free software needs free documentation: a free program should come with manuals providing the same freedoms that the software does. But this License is not limited to software manuals; it can be used for any textual work, regardless of subject matter or whether it is published as a printed book. We recommend this License principally for works whose purpose is instruction or reference.

@item

APPLICABILITY AND DEFINITIONS

This License applies to any manual or other work, in any medium, that contains a notice placed by the copyright holder saying it can be distributed under the terms of this License. Such a notice grants a world-wide, royalty-free license, unlimited in duration, to use that work under the conditions stated herein. The ``Document'', below, refers

to any such manual or work. Any member of the public is a licensee, and is addressed as ``you''. You accept the license if you copy, modify or distribute the work in a way requiring permission under copyright law.

A ``Modified Version'' of the Document means any work containing the Document or a portion of it, either copied verbatim, or with

modifications and/or translated into another language.

A "Secondary Section" is a named appendix or a front-matter section of the Document that deals exclusively with the relationship of the publishers or authors of the Document to the Document's overall subject (or to related matters) and contains nothing that could fall directly within that overall subject. (Thus, if the Document is in part a textbook of mathematics, a Secondary Section may not explain any mathematics.) The relationship could be a matter of historical connection with the subject or with related matters, or of legal, commercial, philosophical, ethical or political position regarding them.

The "Invariant Sections" are certain Secondary Sections whose titles are designated, as being those of Invariant Sections, in the notice that says that the Document is released under this License. If a section does not fit the above definition of Secondary then it is not allowed to be designated as Invariant. The Document may contain zero Invariant Sections. If the Document does not identify any Invariant Sections then there are none.

The "Cover Texts" are certain short passages of text that are listed, as Front-Cover Texts or Back-Cover Texts, in the notice that says that the Document is released under this License. A Front-Cover Text may be at most 5 words, and a Back-Cover Text may be at most 25 words.

A "Transparent" copy of the Document means a machine-readable copy, represented in a format whose specification is available to the general public, that is suitable for revising the document straightforwardly with generic text editors or (for images composed of pixels) generic paint programs or (for drawings) some widely available drawing editor, and that is suitable for input to text formatters or for automatic translation to a variety of formats suitable for input to text formatters. A copy made in an otherwise Transparent file format whose markup, or absence of markup, has been arranged to thwart or discourage subsequent modification by readers is not Transparent. An image format is not Transparent if used for any substantial amount of text. A copy that is not "Transparent" is called "Opaque".

Examples of suitable formats for Transparent copies include plain ASCII without markup, Texinfo input format, LaTeX input format, SGML or XML using a publicly available DTD, and standard-conforming simple HTML, PostScript or PDF designed for human modification. Examples of transparent image formats include PNG, XCF and JPG. Opaque formats include proprietary formats that can be

read and edited only by proprietary word processors, SGML or XML for which the DTD and/or processing tools are not generally available, and the machine-generated HTML, PostScript or PDF produced by some word processors for output purposes only.

The "Title Page" means, for a printed book, the title page itself, plus such following pages as are needed to hold, legibly, the material this License requires to appear in the title page. For works in formats which do not have any title page as such, "Title Page" means the text near the most prominent appearance of the work's title, preceding the beginning of the body of the text.

The "publisher" means any person or entity that distributes copies of the Document to the public.

A section "Entitled XYZ" means a named subunit of the Document whose title either is precisely XYZ or contains XYZ in parentheses following text that translates XYZ in another language. (Here XYZ stands for a specific section name mentioned below, such as "Acknowledgements", "Dedications", "Endorsements", or "History".) To "Preserve the Title" of such a section when you modify the Document means that it remains a section "Entitled XYZ" according to this definition.

The Document may include Warranty Disclaimers next to the notice which states that this License applies to the Document. These Warranty Disclaimers are considered to be included by reference in this License, but only as regards disclaiming warranties: any other implication that these Warranty Disclaimers may have is void and has no effect on the meaning of this License.

@item

VERBATIM COPYING

You may copy and distribute the Document in any medium, either commercially or noncommercially, provided that this License, the copyright notices, and the license notice saying this License applies to the Document are reproduced in all copies, and that you add no other conditions whatsoever to those of this License. You may not use technical measures to obstruct or control the reading or further copying of the copies you make or distribute. However, you may accept compensation in exchange for copies. If you distribute a large enough number of copies you must also follow the conditions in section 3.

You may also lend copies, under the same conditions stated above, and

you may publicly display copies.

@item

COPYING IN QUANTITY

If you publish printed copies (or copies in media that commonly have printed covers) of the Document, numbering more than 100, and the Document's license notice requires Cover Texts, you must enclose the copies in covers that carry, clearly and legibly, all these Cover Texts: Front-Cover Texts on the front cover, and Back-Cover Texts on the back cover. Both covers must also clearly and legibly identify you as the publisher of these copies. The front cover must present the full title with all words of the title equally prominent and visible. You may add other material on the covers in addition. Copying with changes limited to the covers, as long as they preserve the title of the Document and satisfy these conditions, can be treated as verbatim copying in other respects.

If the required texts for either cover are too voluminous to fit legibly, you should put the first ones listed (as many as fit reasonably) on the actual cover, and continue the rest onto adjacent pages.

If you publish or distribute Opaque copies of the Document numbering more than 100, you must either include a machine-readable Transparent copy along with each Opaque copy, or state in or with each Opaque copy a computer-network location from which the general network-using public has access to download using public-standard network protocols a complete Transparent copy of the Document, free of added material. If you use the latter option, you must take reasonably prudent steps, when you begin distribution of Opaque copies in quantity, to ensure that this Transparent copy will remain thus accessible at the stated location until at least one year after the last time you distribute an Opaque copy (directly or through your agents or retailers) of that edition to the public.

It is requested, but not required, that you contact the authors of the Document well before redistributing any large number of copies, to give them a chance to provide you with an updated version of the Document.

@item

MODIFICATIONS

You may copy and distribute a Modified Version of the Document under the conditions of sections 2 and 3 above, provided that you release the Modified Version under precisely this License, with the Modified

Version filling the role of the Document, thus licensing distribution and modification of the Modified Version to whoever possesses a copy of it. In addition, you must do these things in the Modified Version:

@enumerate A

@item

Use in the Title Page (and on the covers, if any) a title distinct from that of the Document, and from those of previous versions (which should, if there were any, be listed in the History section of the Document). You may use the same title as a previous version if the original publisher of that version gives permission.

@item

List on the Title Page, as authors, one or more persons or entities responsible for authorship of the modifications in the Modified Version, together with at least five of the principal authors of the Document (all of its principal authors, if it has fewer than five), unless they release you from this requirement.

@item

State on the Title page the name of the publisher of the Modified Version, as the publisher.

@item

Preserve all the copyright notices of the Document.

@item

Add an appropriate copyright notice for your modifications adjacent to the other copyright notices.

@item

Include, immediately after the copyright notices, a license notice giving the public permission to use the Modified Version under the terms of this License, in the form shown in the Addendum below.

@item

Preserve in that license notice the full lists of Invariant Sections and required Cover Texts given in the Document's license notice.

@item

Include an unaltered copy of this License.

@item

Preserve the section Entitled ``History'', Preserve its Title, and add to it an item stating at least the title, year, new authors, and publisher of the Modified Version as given on the Title Page. If

there is no section Entitled ``History" in the Document, create one stating the title, year, authors, and publisher of the Document as given on its Title Page, then add an item describing the Modified Version as stated in the previous sentence.

@item

Preserve the network location, if any, given in the Document for public access to a Transparent copy of the Document, and likewise the network locations given in the Document for previous versions it was based on. These may be placed in the ``History" section. You may omit a network location for a work that was published at least four years before the Document itself, or if the original publisher of the version it refers to gives permission.

@item

For any section Entitled ``Acknowledgements" or ``Dedications", Preserve the Title of the section, and preserve in the section all the substance and tone of each of the contributor acknowledgements and/or dedications given therein.

@item

Preserve all the Invariant Sections of the Document, unaltered in their text and in their titles. Section numbers or the equivalent are not considered part of the section titles.

@item

Delete any section Entitled ``Endorsements". Such a section may not be included in the Modified Version.

@item

Do not retitle any existing section to be Entitled ``Endorsements" or to conflict in title with any Invariant Section.

@item

Preserve any Warranty Disclaimers.

@end enumerate

If the Modified Version includes new front-matter sections or appendices that qualify as Secondary Sections and contain no material copied from the Document, you may at your option designate some or all of these sections as invariant. To do this, add their titles to the list of Invariant

Sections in the Modified Version's license notice.

These titles must be distinct from any other section titles.

You may add a section Entitled ``Endorsements", provided it contains nothing but endorsements of your Modified Version by various

parties---for example, statements of peer review or that the text has been approved by an organization as the authoritative definition of a standard.

You may add a passage of up to five words as a Front-Cover Text, and a passage of up to 25 words as a Back-Cover Text, to the end of the list of Cover Texts in the Modified Version. Only one passage of Front-Cover Text and one of Back-Cover Text may be added by (or through arrangements made by) any one entity. If the Document already includes a cover text for the same cover, previously added by you or by arrangement made by the same entity you are acting on behalf of, you may not add another; but you may replace the old one, on explicit permission from the previous publisher that added the old one.

The author(s) and publisher(s) of the Document do not by this License give permission to use their names for publicity for or to assert or imply endorsement of any Modified Version.

@item

COMBINING DOCUMENTS

You may combine the Document with other documents released under this License, under the terms defined in section 4 above for modified versions, provided that you include in the combination all of the Invariant Sections of all of the original documents, unmodified, and list them all as Invariant Sections of your combined work in its license notice, and that you preserve all their Warranty Disclaimers.

The combined work need only contain one copy of this License, and multiple identical Invariant Sections may be replaced with a single copy. If there are multiple Invariant Sections with the same name but different contents, make the title of each such section unique by adding at the end of it, in parentheses, the name of the original author or publisher of that section if known, or else a unique number.

Make the same adjustment to the section titles in the list of Invariant Sections in the license notice of the combined work.

In the combination, you must combine any sections Entitled ``History" in the various original documents, forming one section Entitled ``History"; likewise combine any sections Entitled ``Acknowledgements", and any sections Entitled ``Dedications". You must delete all sections Entitled ``Endorsements."

@item

COLLECTIONS OF DOCUMENTS

You may make a collection consisting of the Document and other documents released under this License, and replace the individual copies of this License in the various documents with a single copy that is included in the collection, provided that you follow the rules of this License for verbatim copying of each of the documents in all other respects.

You may extract a single document from such a collection, and distribute it individually under this License, provided you insert a copy of this License into the extracted document, and follow this License in all other respects regarding verbatim copying of that document.

@item

AGGREGATION WITH INDEPENDENT WORKS

A compilation of the Document or its derivatives with other separate and independent documents or works, in or on a volume of a storage or distribution medium, is called an "aggregate" if the copyright resulting from the compilation is not used to limit the legal rights of the compilation's users beyond what the individual works permit. When the Document is included in an aggregate, this License does not apply to the other works in the aggregate which are not themselves derivative works of the Document.

If the Cover Text requirement of section 3 is applicable to these copies of the Document, then if the Document is less than one half of the entire aggregate, the Document's Cover Texts may be placed on covers that bracket the Document within the aggregate, or the electronic equivalent of covers if the Document is in electronic form.

Otherwise they must appear on printed covers that bracket the whole aggregate.

@item

TRANSLATION

Translation is considered a kind of modification, so you may distribute translations of the Document under the terms of section 4. Replacing Invariant Sections with translations requires special permission from their copyright holders, but you may include translations of some or all Invariant Sections in addition to the original versions of these Invariant Sections. You may include a translation of this License, and all the license notices in the Document, and any Warranty Disclaimers, provided that you also include the original English version of this License and the original versions of those notices and disclaimers. In case of a disagreement between the translation and the original version of this License or a notice or disclaimer, the original version will prevail.

If a section in the Document is Entitled ``Acknowledgements'', ``Dedications'', or ``History'', the requirement (section 4) to Preserve its Title (section 1) will typically require changing the actual title.

@item

TERMINATION

You may not copy, modify, sublicense, or distribute the Document except as expressly provided under this License. Any attempt otherwise to copy, modify, sublicense, or distribute it is void, and will automatically terminate your rights under this License.

However, if you cease all violation of this License, then your license from a particular copyright holder is reinstated (a) provisionally, unless and until the copyright holder explicitly and finally terminates your license, and (b) permanently, if the copyright holder fails to notify you of the violation by some reasonable means prior to 60 days after the cessation.

Moreover, your license from a particular copyright holder is reinstated permanently if the copyright holder notifies you of the violation by some reasonable means, this is the first time you have received notice of violation of this License (for any work) from that copyright holder, and you cure the violation prior to 30 days after your receipt of the notice.

Termination of your rights under this section does not terminate the licenses of parties who have received copies or rights from you under this License. If your rights have been terminated and not permanently reinstated, receipt of a copy of some or all of the same material does not give you any rights to use it.

@item

FUTURE REVISIONS OF THIS LICENSE

The Free Software Foundation may publish new, revised versions of the GNU Free Documentation License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns. See <http://www.gnu.org/copyleft/>.

Each version of the License is given a distinguishing version number. If the Document specifies that a particular numbered version of this License ``or any later version'' applies to it, you have the option of

following the terms and conditions either of that specified version or of any later version that has been published (not as a draft) by the Free Software Foundation. If the Document does not specify a version number of this License, you may choose any version ever published (not as a draft) by the Free Software Foundation. If the Document specifies that a proxy can decide which future versions of this License can be used, that proxy's public statement of acceptance of a version permanently authorizes you to choose that version for the Document.

@item

RELICENSING

``Massive Multiauthor Collaboration Site" (or ``MMC Site") means any World Wide Web server that publishes copyrightable works and also provides prominent facilities for anybody to edit those works. A public wiki that anybody can edit is an example of such a server. A ``Massive Multiauthor Collaboration" (or ``MMC") contained in the site means any set of copyrightable works thus published on the MMC site.

``CC-BY-SA" means the Creative Commons Attribution-Share Alike 3.0 license published by Creative Commons Corporation, a not-for-profit corporation with a principal place of business in San Francisco, California, as well as future copyleft versions of that license published by that same organization.

``Incorporate" means to publish or republish a Document, in whole or in part, as part of another Document.

An MMC is ``eligible for relicensing" if it is licensed under this License, and if all works that were first published under this License somewhere other than this MMC, and subsequently incorporated in whole or in part into the MMC, (1) had no cover texts or invariant sections, and (2) were thus incorporated prior to November 1, 2008.

The operator of an MMC Site may republish an MMC contained in the site under CC-BY-SA on the same site at any time before August 1, 2009, provided the MMC is eligible for relicensing.

@end enumerate

@page

@heading ADDENDUM: How to use this License for your documents

To use this License

in a document you have written, include a copy of the License in the document and put the following copyright and license notices just after the title page:

```
@smallexample
@group
Copyright (C) @var{year} @var{your name}.
Permission is granted to copy, distribute and/or modify this document
under the terms of the GNU Free Documentation License, Version 1.3
or any later version published by the Free Software Foundation;
with no Invariant Sections, no Front-Cover Texts, and no Back-Cover
Texts. A copy of the license is included in the section entitled ``GNU
Free Documentation License".
@end group
@end smallexample
```

If you have Invariant Sections, Front-Cover Texts and Back-Cover Texts, replace the ``with@dots{ }Texts."@: line with this:

```
@smallexample
@group
with the Invariant Sections being @var{list their titles}, with
the Front-Cover Texts being @var{list}, and with the Back-Cover Texts
being @var{list}.
@end group
@end smallexample
```

If you have Invariant Sections without Cover Texts, or some other combination of the three, merge those two alternatives to suit the situation.

If your document contains nontrivial examples of program code, we recommend releasing these examples in parallel under your choice of free software license, such as the GNU General Public License, to permit their use in free software.

```
@c Local Variables:
@c ispell-local-pdict: "ispell-dict"
@c End:
```

GNU GENERAL PUBLIC LICENSE

Version 3, 29 June 2007

Copyright (C) 2007 Free Software Foundation, Inc. <<http://fsf.org/>>
Everyone is permitted to copy and distribute verbatim copies of this license document, but changing it is not allowed.

Preamble

The GNU General Public License is a free, copyleft license for software and other kinds of works.

The licenses for most software and other practical works are designed to take away your freedom to share and change the works. By contrast, the GNU General Public License is intended to guarantee your freedom to share and change all versions of a program--to make sure it remains free software for all its users. We, the Free Software Foundation, use the GNU General Public License for most of our software; it applies also to any other work released this way by its authors. You can apply it to your programs, too.

When we speak of free software, we are referring to freedom, not price. Our General Public Licenses are designed to make sure that you have the freedom to distribute copies of free software (and charge for them if you wish), that you receive source code or can get it if you want it, that you can change the software or use pieces of it in new free programs, and that you know you can do these things.

To protect your rights, we need to prevent others from denying you these rights or asking you to surrender the rights. Therefore, you have certain responsibilities if you distribute copies of the software, or if you modify it: responsibilities to respect the freedom of others.

For example, if you distribute copies of such a program, whether gratis or for a fee, you must pass on to the recipients the same freedoms that you received. You must make sure that they, too, receive or can get the source code. And you must show them these terms so they know their rights.

Developers that use the GNU GPL protect your rights with two steps:

(1)

assert copyright on the software, and (2) offer you this License giving you legal permission to copy, distribute and/or modify it.

For the developers' and authors' protection, the GPL clearly explains that there is no warranty for this free software. For both users' and authors' sake, the GPL requires that modified versions be marked as changed, so that their problems will not be attributed erroneously to authors of previous versions.

Some devices are designed to deny users access to install or run modified versions of the software inside them, although the manufacturer can do so. This is fundamentally incompatible with the aim of protecting users' freedom to change the software. The systematic

pattern of such abuse occurs in the area of products for individuals to use, which is precisely where it is most unacceptable. Therefore, we have designed this version of the GPL to prohibit the practice for those products. If such problems arise substantially in other domains, we stand

ready to extend this provision to those domains in future versions of the GPL, as needed to protect the freedom of users.

Finally, every program is threatened constantly by software patents. States should not allow patents to restrict development and use of software on general-purpose computers, but in those that do, we wish to avoid the special danger that patents applied to a free program could make it effectively proprietary. To prevent this, the GPL assures that patents cannot be used to render the program non-free.

The precise terms and conditions for copying, distribution and modification follow.

TERMS AND CONDITIONS

0. Definitions.

"This License" refers to version 3 of the GNU General Public License.

"Copyright" also means copyright-like laws that apply to other kinds of works, such as semiconductor masks.

"The Program" refers to any copyrightable work licensed under this License. Each licensee is addressed as "you". "Licensees" and "recipients" may be individuals or organizations.

To "modify" a work means to copy from or adapt all or part of the work in a fashion requiring copyright permission, other than the making of an exact copy. The resulting work is called a "modified version" of the earlier work or a work "based on" the earlier work.

A "covered work" means either the unmodified Program or a work based on the Program.

To "propagate" a work means to do anything with it that, without permission, would make you directly or secondarily liable for infringement under applicable copyright law, except executing it on a computer or modifying a private copy. Propagation includes copying, distribution (with or without modification), making available to the public, and in some countries other activities as well.

To "convey" a work means any kind of propagation that enables other

parties to make or receive copies. Mere interaction with a user through a computer network, with no transfer of a copy, is not conveying.

An interactive user interface displays "Appropriate Legal Notices" to the extent that it includes a convenient and prominently visible feature that (1) displays an appropriate copyright notice, and (2) tells the user that there is no warranty for the work (except to the extent that warranties are provided), that licensees may convey the work under this License, and how to view a copy of this License. If the interface presents a list of user commands or options, such as a menu, a prominent item in the list meets this criterion.

1. Source Code.

The "source code" for a work means the preferred form of the work for making modifications to it. "Object code" means any non-source form of a work.

A "Standard Interface" means an interface that either is an official standard defined by a recognized standards body, or, in the case of interfaces specified for a particular programming language, one that is widely used among developers working in that language.

The "System Libraries" of an executable work include anything, other than the work as a whole, that (a) is included in the normal form of packaging a Major Component, but which is not part of that Major Component, and (b) serves only to enable use of the work with that Major Component, or to implement a Standard Interface for which an implementation is available to the public in source code form. A "Major Component", in this context, means a major essential component (kernel, window system, and so on) of the specific operating system (if any) on which the executable work runs, or a compiler used to produce the work, or an object code interpreter used to run it.

The "Corresponding Source" for a work in object code form means all the source code needed to generate, install, and (for an executable work) run the object code and to modify the work, including scripts to control those activities. However, it does not include the work's System Libraries, or general-purpose tools or generally available free programs which are used unmodified in performing those activities but which are not part of the work. For example, Corresponding Source includes interface definition files associated with source files for the work, and the source code for shared libraries and dynamically linked subprograms that the work is specifically designed to require, such as by intimate data communication or control flow between those

subprograms and other parts of the work.

The Corresponding Source need not include anything that users can regenerate automatically from other parts of the Corresponding Source.

The Corresponding Source for a work in source code form is that same work.

2. Basic Permissions.

All rights granted under this License are granted for the term of copyright on the Program, and are irrevocable provided the stated conditions are met. This License explicitly affirms your unlimited permission to run the unmodified Program. The output from running a covered work is covered by this License only if the output, given its content, constitutes a covered work. This License acknowledges your rights of fair use or other equivalent, as provided by copyright law.

You may make, run and propagate covered works that you do not convey, without conditions so long as your license otherwise remains in force. You may convey covered works to others for the sole purpose of having them make modifications exclusively for you, or provide you with facilities for running those works, provided that you comply with the terms of this License in conveying all material for which you do not control copyright. Those thus making or running the covered works for you must do so exclusively on your behalf, under your direction and control, on terms that prohibit them from making any copies of your copyrighted material outside their relationship with you.

Conveying under any other circumstances is permitted solely under the conditions stated below. Sublicensing is not allowed; section 10 makes it unnecessary.

3. Protecting Users' Legal Rights From Anti-Circumvention Law.

No covered work shall be deemed part of an effective technological measure under any applicable law fulfilling obligations under article 11 of the WIPO copyright treaty adopted on 20 December 1996, or similar laws prohibiting or restricting circumvention of such measures.

When you convey a covered work, you waive any legal power to forbid circumvention of technological measures to the extent such circumvention is effected by exercising rights under this License with respect to the covered work, and you disclaim any intention to limit operation or

modification of the work as a means of enforcing, against the work's users, your or third parties' legal rights to forbid circumvention of technological measures.

4. Conveying Verbatim Copies.

You may convey verbatim copies of the Program's source code as you receive it, in any medium, provided that you conspicuously and appropriately

- publish on each copy an appropriate copyright notice;
- keep intact all notices stating that this License and any non-permissive terms added in accord with section 7 apply to the code;
- keep intact all notices of the absence of any warranty; and give all recipients a copy of this License along with the Program.

You may charge any price or no price for each copy that you convey, and you may offer support or warranty protection for a fee.

5. Conveying Modified Source Versions.

You may convey a work based on the Program, or the modifications to produce it from the Program, in the form of source code under the terms of section 4, provided that you also meet all of these conditions:

- The work must carry prominent notices stating that you modified it, and giving a relevant date.
- The work must carry prominent notices stating that it is released under this License and any conditions added under section 7. This requirement modifies the requirement in section 4 to "keep intact all notices".
- You must license the entire work, as a whole, under this License to anyone who comes into possession of a copy. This License will therefore apply, along with any applicable section 7 additional terms, to the whole of the work, and all its parts, regardless of how they are packaged. This License gives no permission to license the work in any other way, but it does not invalidate such permission if you have separately received it.
- If the work has interactive user interfaces, each must display Appropriate Legal Notices; however, if the Program has interactive interfaces that do not display Appropriate Legal Notices, your work need not make them do so.

A compilation of a covered work with other separate and independent works, which are not by their nature extensions of the covered work,

and which are not combined with it such as to form a larger program, in or on a volume of a storage or distribution medium, is called an "aggregate" if the compilation and its resulting copyright are not used to limit the access or legal rights of the compilation's users beyond what the individual works permit. Inclusion of a covered work in an aggregate does not cause this License to apply to the other parts of the aggregate.

6. Conveying Non-Source Forms.

You may convey a covered work in object code form under the terms of sections 4 and 5, provided that you also convey the machine-readable Corresponding Source under the terms of this License, in one of these ways:

- a) Convey the object code in, or embodied in, a physical product (including a physical distribution medium), accompanied by the Corresponding Source fixed on a durable physical medium customarily used for software interchange.
- b) Convey the object code in, or embodied in, a physical product (including a physical distribution medium), accompanied by a written offer, valid for at least three years and valid for as long as you offer spare parts or customer support for that product model, to give anyone who possesses the object code either (1) a copy of the Corresponding Source for all the software in the product that is covered by this License, on a durable physical medium customarily used for software interchange, for a price no more than your reasonable cost of physically performing this conveying of source, or (2) access to copy the Corresponding Source from a network server at no charge.
- c) Convey individual copies of the object code with a copy of the written offer to provide the Corresponding Source. This alternative is allowed only occasionally and noncommercially, and only if you received the object code with such an offer, in accord with subsection 6b.
- d) Convey the object code by offering access from a designated place (gratis or for a charge), and offer equivalent access to the Corresponding Source in the same way through the same place at no further charge. You need not require recipients to copy the Corresponding Source along with the object code. If the place to copy the object code is a network server, the Corresponding Source may be on a different server (operated by you or a third party)

that supports equivalent copying facilities, provided you maintain clear directions next to the object code saying where to find the Corresponding Source. Regardless of what server hosts the Corresponding Source, you remain obligated to ensure that it is available for as long as needed to satisfy these requirements.

e) Convey the object code using peer-to-peer transmission, provided you inform other peers where the object code and Corresponding Source of the work are being offered to the general public at no charge under subsection 6d.

A separable portion of the object code, whose source code is excluded from the Corresponding Source as a System Library, need not be included in conveying the object code work.

A "User Product" is either (1) a "consumer product", which means any tangible personal property which is normally used for personal, family, or household purposes, or (2) anything designed or sold for incorporation into a dwelling. In determining whether a product is a consumer product, doubtful cases shall be resolved in favor of coverage. For a particular product received by a particular user, "normally used" refers to a typical or common use of that class of product, regardless of the status of the particular user or of the way in which the particular user actually uses, or expects or is expected to use, the product. A product is a consumer product regardless of whether the product has substantial commercial, industrial or non-consumer uses, unless such uses represent the only significant mode of use of the product.

"Installation Information" for a User Product means any methods, procedures, authorization keys, or other information required to install and execute modified versions of a covered work in that User Product from a modified version of its Corresponding Source. The information must suffice to ensure that the continued functioning of the modified object code is in no case prevented or interfered with solely because modification has been made.

If you convey an object code work under this section in, or with, or specifically for use in, a User Product, and the conveying occurs as part of a transaction in which the right of possession and use of the User Product is transferred to the recipient in perpetuity or for a fixed term (regardless of how the transaction is characterized), the Corresponding Source conveyed under this section must be accompanied by the Installation Information. But this requirement does not apply if neither you nor any third party retains the ability to install modified object code on the User Product (for example, the work has been installed in

ROM).

The requirement to provide Installation Information does not include a requirement to continue to provide support service, warranty, or updates for a work that has been modified or installed by the recipient, or for the User Product in which it has been modified or installed. Access to a network may be denied when the modification itself materially and adversely affects the operation of the network or violates the rules and protocols for communication across the network.

Corresponding Source conveyed, and Installation Information provided, in accord with this section must be in a format that is publicly documented (and with an implementation available to the public in source code form), and must require no special password or key for unpacking, reading or copying.

7. Additional Terms.

"Additional permissions" are terms that supplement the terms of this License by making exceptions from one or more of its conditions. Additional permissions that are applicable to the entire Program shall be treated as though they were included in this License, to the extent that they are valid under applicable law. If additional permissions apply only to part of the Program, that part may be used separately under those permissions, but the entire Program remains governed by this License without regard to the additional permissions.

When you convey a copy of a covered work, you may at your option remove any additional permissions from that copy, or from any part of it. (Additional permissions may be written to require their own removal in certain cases when you modify the work.) You may place additional permissions on material, added by you to a covered work, for which you have or can give appropriate copyright permission.

Notwithstanding any other provision of this License, for material you add to a covered work, you may (if authorized by the copyright holders of that material) supplement the terms of this License with terms:

- a) Disclaiming warranty or limiting liability differently from the terms of sections 15 and 16 of this License; or
- b) Requiring preservation of specified reasonable legal notices or author attributions in that material or in the Appropriate Legal Notices displayed by works containing it; or
- c) Prohibiting misrepresentation of the origin of that material, or

requiring that modified versions of such material be marked in reasonable ways as different from the original version; or

d) Limiting the use for publicity purposes of names of licensors or authors of the material; or

e) Declining to grant rights under trademark law for use of some trade names, trademarks, or service marks; or

f) Requiring indemnification of licensors and authors of that material by anyone who conveys the material (or modified versions of it) with contractual assumptions of liability to the recipient, for any liability that these contractual assumptions directly impose on

those licensors and authors.

All other non-permissive additional terms are considered "further restrictions" within the meaning of section 10. If the Program as you received it, or any part of it, contains a notice stating that it is governed by this License along with a term that is a further restriction, you may remove that term. If a license document contains a further restriction but permits relicensing or conveying under this License, you may add to a covered work material governed by the terms of that license document, provided that the further restriction does not survive such relicensing or conveying.

If you add terms to a covered work in accord with this section, you must place, in the relevant source files, a statement of the additional terms that apply to those files, or a notice indicating where to find the applicable terms.

Additional terms, permissive or non-permissive, may be stated in the form of a separately written license, or stated as exceptions; the above requirements apply either way.

8. Termination.

You may not propagate or modify a covered work except as expressly provided under this License. Any attempt otherwise to propagate or modify it is void, and will automatically terminate your rights under this License (including any patent licenses granted under the third paragraph of section 11).

However, if you cease all violation of this License, then your license from a particular copyright holder is reinstated (a) provisionally, unless and until the copyright holder explicitly and finally terminates your license, and (b) permanently, if the copyright

holder fails to notify you of the violation by some reasonable means prior to 60 days after the cessation.

Moreover, your license from a particular copyright holder is reinstated permanently if the copyright holder notifies you of the violation by some reasonable means, this is the first time you have received notice of violation of this License (for any work) from that copyright holder, and you cure the violation prior to 30 days after your receipt of the notice.

Termination of your rights under this section does not terminate the licenses of parties who have received copies or rights from you under this License. If your rights have been terminated and not permanently reinstated, you do not qualify to receive new licenses for the same material under section 10.

9. Acceptance Not Required for Having Copies.

You are not required to accept this License in order to receive or run a copy of the Program. Ancillary propagation of a covered work occurring solely as a consequence of using peer-to-peer transmission to receive a copy likewise does not require acceptance. However, nothing other than this License grants you permission to propagate or modify any covered work. These actions infringe copyright if you do not accept this License. Therefore, by modifying or propagating a covered work, you indicate your acceptance of this License to do so.

10. Automatic Licensing of Downstream Recipients.

Each time you convey a covered work, the recipient automatically receives a license from the original licensors, to run, modify and propagate that work, subject to this License. You are not responsible for enforcing compliance by third parties with this License.

An "entity transaction" is a transaction transferring control of an organization, or substantially all assets of one, or subdividing an organization, or merging organizations. If propagation of a covered work results from an entity transaction, each party to that transaction who receives a copy of the work also receives whatever licenses to the work the party's predecessor in interest had or could give under the previous paragraph, plus a right to possession of the Corresponding Source of the work from the predecessor in interest, if the predecessor has it or can get it with reasonable efforts.

You may not impose any further restrictions on the exercise of the rights

granted or affirmed under this License. For example, you may not impose a license fee, royalty, or other charge for exercise of rights granted under this License, and you may not initiate litigation (including a cross-claim or counterclaim in a lawsuit) alleging that any patent claim is infringed by making, using, selling, offering for sale, or importing the Program or any portion of it.

11. Patents.

A "contributor" is a copyright holder who authorizes use under this License of the Program or a work on which the Program is based. The work thus licensed is called the contributor's "contributor version".

A contributor's "essential patent claims" are all patent claims owned or controlled by the contributor, whether already acquired or hereafter acquired, that would be infringed by some manner, permitted by this License, of making, using, or selling its contributor version, but do not include claims that would be infringed only as a consequence of further modification of the contributor version. For purposes of this definition, "control" includes the right to grant patent sublicenses in a manner consistent with the requirements of this License.

Each contributor grants you a non-exclusive, worldwide, royalty-free patent license under the contributor's essential patent claims, to make, use, sell, offer for sale, import and otherwise run, modify and propagate the contents of its contributor version.

In the following three paragraphs, a "patent license" is any express agreement or commitment, however denominated, not to enforce a patent (such as an express permission to practice a patent or covenant not to sue for patent infringement). To "grant" such a patent license to a party means to make such an agreement or commitment not to enforce a patent against the party.

If you convey a covered work, knowingly relying on a patent license, and the Corresponding Source of the work is not available for anyone to copy, free of charge and under the terms of this License, through a publicly available network server or other readily accessible means, then you must either (1) cause the Corresponding Source to be so available, or (2) arrange to deprive yourself of the benefit of the patent license for this particular work, or (3) arrange, in a manner consistent with the requirements of this License, to extend the patent license to downstream recipients. "Knowingly relying" means you have actual knowledge that, but for the patent license, your conveying the covered work in a country, or your recipient's use of the covered work

in a country, would infringe one or more identifiable patents in that country that you have reason to believe are valid.

If, pursuant to or in connection with a single transaction or arrangement, you convey, or propagate by procuring conveyance of, a covered work, and grant a patent license to some of the parties receiving the covered work authorizing them to use, propagate, modify or convey a specific copy of the covered work, then the patent license you grant is automatically extended to all recipients of the covered work and works based on it.

A patent license is "discriminatory" if it does not include within the scope of its coverage, prohibits the exercise of, or is conditioned on the non-exercise of one or more of the rights that are specifically granted under this License. You may not convey a covered work if you are a party to an arrangement with a third party that is in the business of distributing software, under which you make payment to the third party based on the extent of your activity of conveying the work, and under which the third party grants, to any of the parties who would receive the covered work from you, a discriminatory patent license (a) in connection with copies of the covered work conveyed by you (or copies made from those copies), or (b) primarily for and in connection with specific products or compilations that contain the covered work, unless you entered into that arrangement, or that patent license was granted, prior to 28 March 2007.

Nothing in this License shall be construed as excluding or limiting any implied license or other defenses to infringement that may otherwise be available to you under applicable patent law.

12. No Surrender of Others' Freedom.

If conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot convey a covered work so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not convey it at all. For example, if you agree to terms that obligate you to collect a royalty for further conveying from those to whom you convey the Program, the only way you could satisfy both those terms and this License would be to refrain entirely from conveying the Program.

13. Use with the GNU Affero General Public License.

Notwithstanding any other provision of this License, you have

permission to link or combine any covered work with a work licensed under version 3 of the GNU Affero General Public License into a single combined work, and to convey the resulting work. The terms of this License will continue to apply to the part which is the covered work, but the special requirements of the GNU Affero General Public License, section 13, concerning interaction through a network will apply to the combination as such.

14. Revised Versions of this License.

The Free Software Foundation may publish revised and/or new versions of the GNU General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Program specifies that a certain numbered version of the GNU General Public License "or any later version" applies to it, you have the option of following the terms and conditions either of that numbered version or of any later version published by the Free Software Foundation. If the Program does not specify a version number of the GNU General Public License, you may choose any version ever published by the Free Software Foundation.

If the Program specifies that a proxy can decide which future versions of the GNU General Public License can be used, that proxy's public statement of acceptance of a version permanently authorizes you to choose that version for the Program.

Later license versions may give you additional or different permissions. However, no additional obligations are imposed on any author or copyright holder as a result of your choosing to follow a later version.

15. Disclaimer of Warranty.

THERE IS NO WARRANTY FOR THE PROGRAM, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE PROGRAM "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE PROGRAM IS WITH YOU. SHOULD THE PROGRAM PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

16. Limitation of Liability.

IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MODIFIES AND/OR CONVEYS THE PROGRAM AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE PROGRAM (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE PROGRAM TO OPERATE WITH ANY OTHER PROGRAMS), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

17.

Interpretation of Sections 15 and 16.

If the disclaimer of warranty and limitation of liability provided above cannot be given local legal effect according to their terms, reviewing courts shall apply local law that most closely approximates an absolute waiver of all civil liability in connection with the Program, unless a warranty or assumption of liability accompanies a copy of the Program in return for a fee.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Programs

If you develop a new program, and you want it to be of the greatest possible use to the public, the best way to achieve this is to make it free software which everyone can redistribute and change under these terms.

To do so, attach the following notices to the program. It is safest to attach them to the start of each source file to most effectively state the exclusion of warranty; and each file should have at least the "copyright" line and a pointer to where the full notice is found.

<one line to give the program's name and a brief idea of what it does.>

Copyright (C) <year> <name of author>

This program is free software: you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation, either version 3 of the License, or (at your option) any later version.

This program is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details.

You should have received a copy of the GNU General Public License along with this program. If not, see <http://www.gnu.org/licenses/>.

Also add information on how to contact you by electronic and paper mail.

If the program does terminal interaction, make it output a short notice like this when it starts in an interactive mode:

```
<program> Copyright (C) <year> <name of author>  
This program comes with ABSOLUTELY NO WARRANTY; for details type `show w'.  
This is free software, and you are welcome to redistribute it  
under certain conditions; type `show c' for details.
```

The hypothetical commands `show w' and `show c' should show the appropriate parts of the General Public License. Of course, your program's commands might be different; for a GUI interface, you would use an "about box".

You should also get your employer (if you work as a programmer) or school, if any, to sign a "copyright disclaimer" for the program, if necessary. For more information on this, and how to apply and follow the GNU GPL, see <http://www.gnu.org/licenses/>.

The GNU General Public License does not permit incorporating your program into proprietary programs. If your program is a subroutine library, you may consider it more useful to permit linking proprietary applications with the library. If this is what you want to do, use the GNU Lesser General Public License instead of this License. But first, please read <http://www.gnu.org/philosophy/why-not-lgpl.html>.

1.22 libidn 2.0.4-1.1ubuntu0.2

1.22.1 Available under license :

GNU LESSER GENERAL PUBLIC LICENSE
Version 3, 29 June 2007

Copyright (C) 2007 Free Software Foundation, Inc. <http://fsf.org/>
Everyone is permitted to copy and distribute verbatim copies of this license document, but changing it is not allowed.

This version of the GNU Lesser General Public License incorporates the terms and conditions of version 3 of the GNU General Public License, supplemented by the additional permissions listed below.

0. Additional Definitions.

As used herein, "this License" refers to version 3 of the GNU Lesser General Public License, and the "GNU GPL" refers to version 3 of the GNU General Public License.

"The Library" refers to a covered work governed by this License, other than an Application or a Combined Work as defined below.

An "Application" is any work that makes use of an interface provided by the Library, but which is not otherwise based on the Library.

Defining a subclass of a class defined by the Library is deemed a mode of using an interface provided by the Library.

A "Combined Work" is a work produced by combining or linking an Application with the Library. The particular version of the Library with which the Combined Work was made is also called the "Linked Version".

The "Minimal Corresponding Source" for a Combined Work means the Corresponding Source for the Combined Work, excluding any source code for portions of the Combined Work that, considered in isolation, are based on the Application, and not on the Linked Version.

The "Corresponding Application Code" for a Combined Work means the object code and/or source code for the Application, including any data and utility programs needed for reproducing the Combined Work from the Application, but excluding the System Libraries of the Combined Work.

1. Exception to Section 3 of the GNU GPL.

You may convey a covered work under sections 3 and 4 of this License without being bound by section 3 of the GNU GPL.

2. Conveying Modified Versions.

If you modify a copy of the Library, and, in your modifications, a facility refers to a function or data to be supplied by an Application that uses the facility (other than as an argument passed when the facility is invoked), then you may convey a copy of the modified version:

a) under this License, provided that you make a good faith effort to ensure that, in the event an Application does not supply the function or data, the facility still operates, and performs whatever part of its purpose remains meaningful, or

b) under the GNU GPL, with none of the additional permissions of this License applicable to that copy.

3. Object Code Incorporating Material from Library Header Files.

The object code form of an Application may incorporate material from a header file that is part of the Library. You may convey such object code under terms of your choice, provided that, if the incorporated material is not limited to numerical parameters, data structure layouts and accessors, or small macros, inline functions and templates (ten or fewer lines in length), you do both of the following:

- a) Give prominent notice with each copy of the object code that the Library is used in it and that the Library and its use are covered by this License.
- b) Accompany the object code with a copy of the GNU GPL and this license document.

4. Combined Works.

You may convey a Combined Work under terms of your choice that, taken together, effectively do not restrict modification of the portions of the Library contained in the Combined Work and reverse engineering for debugging such modifications, if you also do each of the following:

- a) Give prominent notice with each copy of the Combined Work that the Library is used in it and that the Library and its use are covered by this License.
- b) Accompany the Combined Work with a copy of the GNU GPL and this license document.
- c) For a Combined Work that displays copyright notices during execution, include the copyright notice for the Library among these notices, as well as a reference directing the user to the copies of the GNU GPL and this license document.

d) Do one of the following:

- 0) Convey the Minimal Corresponding Source under the terms of this License, and the Corresponding Application Code in a form suitable for, and under terms that permit, the user to recombine or relink the Application with a modified version of the Linked Version to produce a modified Combined Work, in the manner specified by section 6 of the GNU GPL for conveying Corresponding Source.

1) Use a suitable shared library mechanism for linking with the Library. A suitable mechanism is one that (a) uses at run time a copy of the Library already present on the user's computer system, and (b) will operate properly with a modified version of the Library that is interface-compatible with the Linked Version.

e) Provide Installation Information, but only if you would otherwise be required to provide such information under section 6 of the GNU GPL, and only to the extent that such information is necessary to install and execute a modified version of the Combined Work produced by recombining or relinking the Application with a modified version of the Linked Version. (If you use option 4d0, the Installation Information must accompany the Minimal Corresponding Source and Corresponding Application Code. If you use option 4d1, you must provide the Installation Information in the manner specified by section 6 of the GNU GPL for conveying Corresponding Source.)

5. Combined Libraries.

You may place library facilities that are a work based on the Library side by side in a single library together with other library facilities that are not Applications and are not covered by this License, and convey such a combined library under terms of your choice, if you do both of the following:

- a) Accompany the combined library with a copy of the same work based on the Library, uncombined with any other library facilities, conveyed under the terms of this License.
- b) Give prominent notice with the combined library that part of it is a work based on the Library, and explaining where to find the accompanying uncombined form of the same work.

6. Revised Versions of the GNU Lesser General Public License.

The Free Software Foundation may publish revised and/or new versions of the GNU Lesser General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Library as you received it specifies that a certain numbered version of the GNU Lesser General Public License "or any later version"

applies to it, you have the option of following the terms and conditions either of that published version or of any later version published by the Free Software Foundation. If the Library as you received it does not specify a version number of the GNU Lesser General Public License, you may choose any version of the GNU Lesser General Public License ever published by the Free Software Foundation.

If the Library as you received it specifies that a proxy can decide whether future versions of the GNU Lesser General Public License shall apply, that proxy's public statement of acceptance of any version is permanent authorization for you to choose that version for the Library.

GNU GENERAL PUBLIC LICENSE

Version 2, June 1991

Copyright (C) 1989, 1991 Free Software Foundation, Inc.,
51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA
Everyone is permitted to copy and distribute verbatim copies
of this license document, but changing it is not allowed.

Preamble

The licenses for most software are designed to take away your freedom to share and change it. By contrast, the GNU General Public License is intended to guarantee your freedom to share and change free software--to make sure the software is free for all its users. This General Public License applies to most of the Free Software Foundation's software and to any other program whose authors commit to using it. (Some other Free Software Foundation software is covered by the GNU Lesser General Public License instead.) You can apply it to your programs, too.

When we speak of free software, we are referring to freedom, not price.

Our General Public Licenses are designed to make sure that you have the freedom to distribute copies of free software (and charge for this service if you wish), that you receive source code or can get it if you want it, that you can change the software or use pieces of it in new free programs; and that you know you can do these things.

To protect your rights, we need to make restrictions that forbid anyone to deny you these rights or to ask you to surrender the rights. These restrictions translate to certain responsibilities for you if you distribute copies of the software, or if you modify it.

For example, if you distribute copies of such a program, whether gratis or for a fee, you must give the recipients all the rights that

you have. You must make sure that they, too, receive or can get the source code. And you must show them these terms so they know their rights.

We protect your rights with two steps: (1) copyright the software, and (2) offer you this license which gives you legal permission to copy, distribute and/or modify the software.

Also, for each author's protection and ours, we want to make certain that everyone understands that there is no warranty for this free software. If the software is modified by someone else and passed on, we want its recipients to know that what they have is not the original, so that any problems introduced by others will not reflect on the original authors' reputations.

Finally, any free program is threatened constantly by software patents. We wish to avoid the danger that redistributors of a free program will individually obtain patent licenses, in effect making the program proprietary. To prevent this, we have made it clear that any patent must be licensed for everyone's free use or not licensed at all.

The precise terms and conditions for copying, distribution and modification follow.

GNU GENERAL PUBLIC LICENSE TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

0. This License applies to any program or other work which contains a notice placed by the copyright holder saying it may be distributed under the terms of this General Public License. The "Program", below, refers to any such program or work, and a "work based on the Program" means either the Program or any derivative work under copyright law: that is to say, a work containing the Program or a portion of it, either verbatim or with modifications and/or translated into another language. (Hereinafter, translation is included without limitation in the term "modification".) Each licensee is addressed as "you".

Activities other than copying, distribution and modification are not covered by this License; they are outside its scope. The act of running the Program is not restricted, and the output from the Program is covered only if its contents constitute a work based on the Program (independent of having been made by running the Program). Whether that is true depends on what the Program does.

1. You may copy and distribute verbatim copies of the Program's source code as you receive it, in any medium, provided that you

conspicuously and appropriately publish on each copy an appropriate copyright notice and disclaimer of warranty; keep intact all the notices that refer to this License and to the absence of any warranty; and give any other recipients of the Program a copy of this License along with the Program.

You may charge a fee for the physical act of transferring a copy, and you may at your option offer warranty protection in exchange for a fee.

2. You may modify your copy or copies of the Program or any portion of it, thus forming a work based on the Program, and copy and distribute such modifications or work under the terms of Section 1 above, provided that you also meet all of these conditions:

a) You must cause the modified files to carry prominent notices stating that you changed the files and the date of any change.

b) You must cause any work that you distribute or publish, that in whole or in part contains or is derived from the Program or any part thereof, to be licensed as a whole at no charge to all third parties under the terms of this License.

c) If the modified program normally reads commands interactively when run, you must cause it, when started running for such interactive use in the most ordinary way, to print or display an announcement including an appropriate copyright notice and a notice that there is no warranty (or else, saying that you provide a warranty) and that users may redistribute the program under these conditions, and telling the user how to view a copy of this License. (Exception: if the Program itself is interactive but does not normally print such an announcement, your work based on the Program is not required to print an announcement.)

These requirements apply to the modified work as a whole. If identifiable sections of that work are not derived from the Program, and can be reasonably considered independent and separate works in themselves, then this License, and its terms, do not apply to those sections when you distribute them as separate works. But when you distribute the same sections as part of a whole which is a work based on the Program, the distribution of the whole must be on the terms of this License, whose permissions for other licensees extend to the entire whole, and thus to each and every part regardless of who wrote it.

Thus, it is not the intent of this section to claim rights or contest your rights to work written entirely by you; rather, the intent is to exercise the right to control the distribution of derivative or

collective works based on the Program.

In addition, mere aggregation of another work not based on the Program with the Program (or with a work based on the Program) on a volume of a storage or distribution medium does not bring the other work under the scope of this License.

3. You may copy and distribute the Program (or a work based on it, under Section 2) in object code or executable form under the terms of Sections 1 and 2 above provided that you also do one of the following:

- a) Accompany it with the complete corresponding machine-readable source code, which must be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange; or,
- b) Accompany it with a written offer, valid for at least three years, to give any third party, for a charge no more than your cost of physically performing source distribution, a complete machine-readable copy of the corresponding source code, to be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange; or,
- c) Accompany it with the information you received as to the offer to distribute corresponding source code. (This alternative is allowed only for noncommercial distribution and only if you received the program in object code or executable form with such an offer, in accord with Subsection b above.)

The source code for a work means the preferred form of the work for making modifications to it. For an executable work, complete source code means all the source code for all modules it contains, plus any associated interface definition files, plus the scripts used to control compilation and installation of the executable. However, as a special exception, the source code distributed need not include anything that is normally distributed (in either source or binary form) with the major components (compiler, kernel, and so on) of the operating system on which the executable runs, unless that component itself accompanies the executable.

If distribution of executable or object code is made by offering access to copy from a designated place, then offering equivalent access to copy the source code from the same place counts as distribution of the source code, even though third parties are not compelled to copy the source along with the object code.

4. You may not copy, modify, sublicense, or distribute the Program

except as expressly provided under this License. Any attempt otherwise to copy, modify, sublicense or distribute the Program is void, and will automatically terminate your rights under this License. However, parties who have received copies, or rights, from you under this License will not have their licenses terminated so long as such parties remain in full compliance.

5. You are not required to accept this License, since you have not signed it. However, nothing else grants you permission to modify or distribute the Program or its derivative works. These actions are prohibited by law if you do not accept this License. Therefore, by modifying or distributing the Program (or any work based on the Program), you indicate your acceptance of this License to do so, and all its terms and conditions for copying, distributing or modifying the Program or works based on it.

6. Each time you redistribute the Program (or any work based on the Program), the recipient automatically receives a license from the original licensor to copy, distribute or modify the Program subject to these terms and conditions. You may not impose any further restrictions on the recipients' exercise of the rights granted herein. You are not responsible for enforcing compliance by third parties to this License.

7. If, as a consequence of a court judgment or allegation of patent infringement or for any other reason (not limited to patent issues), conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot distribute so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not distribute the Program at all. For example, if a patent license would not permit royalty-free redistribution of the Program by all those who receive copies directly or indirectly through you, then the only way you could satisfy both it and this License would be to refrain entirely from distribution of the Program.

If any portion of this section is held invalid or unenforceable under any particular circumstance, the balance of the section is intended to apply and the section as a whole is intended to apply in other circumstances.

It is not the purpose of this section to induce you to infringe any patents or other property right claims or to contest validity of any such claims; this section has the sole purpose of protecting the integrity of the free software distribution system, which is

implemented by public license practices. Many people have made generous contributions to the wide range of software distributed through that system in reliance on consistent application of that system; it is up to the author/donor to decide if he or she is willing to distribute software through any other system and a licensee cannot impose that choice.

This section is intended to make thoroughly clear what is believed to be a consequence of the rest of this License.

8. If the distribution and/or use of the Program is restricted in certain countries either by patents or by copyrighted interfaces, the original copyright holder who places the Program under this License may add an explicit geographical distribution limitation excluding those countries, so that distribution is permitted only in or among countries not thus excluded. In such case, this License incorporates the limitation as if written in the body of this License.

9. The Free Software Foundation may publish revised and/or new versions of the General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Program specifies a version number of this License which applies to it and "any later version", you have the option of following the terms and conditions either of that version or of any later version published by the Free Software Foundation. If the Program does not specify a version number of this License, you may choose any version ever published by the Free Software Foundation.

10. If you wish to incorporate parts of the Program into other free programs whose distribution conditions are different, write to the author to ask for permission. For software which is copyrighted by the Free Software Foundation, write to the Free Software Foundation; we sometimes make exceptions for this. Our decision will be guided by the two goals of preserving the free status of all derivatives of our free software and of promoting the sharing and reuse of software generally.

NO WARRANTY

11. BECAUSE THE PROGRAM IS LICENSED FREE OF CHARGE, THERE IS NO WARRANTY FOR THE PROGRAM, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE PROGRAM "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED

OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE PROGRAM IS WITH YOU. SHOULD THE PROGRAM PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

12. IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY AND/OR REDISTRIBUTE THE PROGRAM AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE PROGRAM (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE PROGRAM TO OPERATE WITH ANY OTHER PROGRAMS), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Programs

If you develop a new program, and you want it to be of the greatest possible use to the public, the best way to achieve this is to make it free software which everyone can redistribute and change under these terms.

To do so, attach the following notices to the program. It is safest to attach them to the start of each source file to most effectively convey the exclusion of warranty; and each file should have at least the "copyright" line and a pointer to where the full notice is found.

<one line to give the program's name and a brief idea of what it does.>
Copyright (C) <year> <name of author>

This program is free software; you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation; either version 2 of the License, or (at your option) any later version.

This program is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details.

You should have received a copy of the GNU General Public License along with this program; if not, write to the Free Software Foundation, Inc., 51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA.

Also add information on how to contact you by electronic and paper mail.

If the program is interactive, make it output a short notice like this when it starts in an interactive mode:

```
Gnomovision version 69, Copyright (C) year name of author
Gnomovision comes with ABSOLUTELY NO WARRANTY; for details type `show w'.
This is free software, and you are welcome to redistribute
it
under certain conditions; type `show c' for details.
```

The hypothetical commands ``show w'` and ``show c'` should show the appropriate parts of the General Public License. Of course, the commands you use may be called something other than ``show w'` and ``show c'`; they could even be mouse-clicks or menu items--whatever suits your program.

You should also get your employer (if you work as a programmer) or your school, if any, to sign a "copyright disclaimer" for the program, if necessary. Here is a sample; alter the names:

```
Yoyodyne, Inc., hereby disclaims all copyright interest in the program
`Gnomovision' (which makes passes at compilers) written by James Hacker.
```

```
<signature of Ty Coon>, 1 April 1989
Ty Coon, President of Vice
```

This General Public License does not permit incorporating your program into proprietary programs. If your program is a subroutine library, you may consider it more useful to permit linking proprietary applications with the library. If this is what you want to do, use the GNU Lesser General Public License instead of this License.

A. Unicode Copyright.

Copyright 1991-2016 Unicode, Inc. All rights reserved.

Certain documents and files on this website contain a legend indicating that "Modification is permitted." Any person is hereby authorized, without fee, to modify such documents and files to create derivative works conforming to the Unicode Standard, subject to Terms and Conditions herein.

Any person is hereby authorized, without fee, to view, use, reproduce, and distribute all documents and files solely for informational purposes and in the creation of products supporting the Unicode Standard, subject to the Terms and Conditions herein.

Further specifications of rights and restrictions pertaining to the use of the particular set of data files known as the "Unicode Character Database" can be found in the License.

Each version of the Unicode Standard has further specifications of rights and restrictions of use. For the book editions (Unicode 5.0 and earlier), these are found on the back of the title page. The online code charts carry specific restrictions. All other files, including online documentation of the core specification for Unicode 6.0 and later, are covered under these general Terms of Use.

No license is granted to "mirror" the Unicode website where a fee is charged for access to the "mirror" site.

Modification is not permitted with respect to this document. All copies of this document must be verbatim.

B. Restricted Rights Legend.

Any technical data or software which is licensed to the United States of America, its agencies and/or instrumentalities under this Agreement is commercial technical data or commercial computer software developed exclusively at private expense as defined in FAR 2.101, or DFARS 252.227-7014 (June 1995), as applicable. For technical data, use, duplication, or disclosure by the Government is subject to restrictions as set forth in DFARS 202.227-7015 Technical Data, Commercial and Items (Nov 1995) and this Agreement. For Software, in accordance with FAR 12-212 or DFARS 227-7202, as applicable, use, duplication or disclosure by the Government is subject to the restrictions set forth in this Agreement.

C. Warranties and Disclaimers.

This publication and/or website may include technical or typographical errors or other inaccuracies. Changes are periodically added to the information herein; these changes will be incorporated in new editions of the publication and/or website. Unicode may make improvements and/or changes in the product(s) and/or program(s) described in this publication and/or website at any time.

If this file has been purchased on magnetic or optical media from Unicode, Inc. the sole and exclusive remedy for any claim will be exchange of the defective media within ninety (90) days of original purchase.

EXCEPT AS PROVIDED IN SECTION C.2, THIS PUBLICATION AND/OR SOFTWARE IS PROVIDED "AS IS" WITHOUT WARRANTY OF ANY KIND EITHER EXPRESS, IMPLIED, OR STATUTORY, INCLUDING, BUT NOT LIMITED TO,

ANY WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR NON-INFRINGEMENT. UNICODE AND ITS LICENSORS ASSUME NO RESPONSIBILITY FOR ERRORS OR OMISSIONS IN THIS PUBLICATION AND/OR SOFTWARE OR OTHER DOCUMENTS WHICH ARE REFERENCED BY OR LINKED TO THIS PUBLICATION OR THE UNICODE WEBSITE.

D. Waiver of Damages.

In no event shall Unicode or its licensors be liable for any special, incidental, indirect or consequential damages of any kind, or any damages whatsoever, whether or not Unicode was advised of the possibility of the damage, including, without limitation, those resulting from the following: loss of use, data or profits, in connection with the use, modification or distribution of this information or its derivatives.

E. Trademarks & Logos.

The Unicode Word Mark and the Unicode Logo are trademarks of Unicode, Inc. The Unicode Consortium and Unicode, Inc. are trade names of Unicode, Inc. Use of the information and materials found on this website indicates your acknowledgement

of Unicode, Inc.'s exclusive worldwide rights in the Unicode Word Mark, the Unicode Logo, and the Unicode trade names.

The Unicode Consortium Name and Trademark Usage Policy (Trademark Policy) are incorporated herein by reference and you agree to abide by the provisions of the Trademark Policy, which may be changed from time to time in the sole discretion of Unicode, Inc.

All third party trademarks referenced herein are the property of their respective owners.

F. Miscellaneous.

Jurisdiction and Venue. This server is operated from a location in the State of California, United States of America. Unicode makes no representation that the materials are appropriate for use in other locations. If you access this server from other locations, you are responsible for compliance with local laws. This Agreement, all use of this site and any claims and damages resulting from use of this site are governed solely by the laws of the State of

California without regard to any principles

which would apply the laws of a different jurisdiction. The user agrees that any disputes regarding this site shall be resolved solely in the courts located in Santa Clara County, California. The user agrees said courts have personal jurisdiction and agree to waive any right to transfer the dispute to any other forum.

Modification by Unicode Unicode shall have the right to modify this Agreement at any time by posting it to this site. The user may not assign any part of this Agreement without Unicodes prior written consent.

Taxes. The user agrees to pay any taxes arising from access to this website or use of the information herein, except for those based on Unicodes net income.

Severability. If any provision of this Agreement is declared invalid or unenforceable, the remaining provisions of this Agreement shall remain in effect.

Entire Agreement. This Agreement constitutes the entire agreement between the parties.

EXHIBIT 1

Unicode Data Files include all data files
under the directories

<http://www.unicode.org/Public/>, <http://www.unicode.org/reports/>,
<http://www.unicode.org/cldr/data/>, <http://source.icu-project.org/repos/icu/>, and
<http://www.unicode.org/utility/trac/browser/>.

Unicode Data Files do not include PDF online code charts under the
directory <http://www.unicode.org/Public/>.

Software includes any source code published in the Unicode Standard
or under the directories

<http://www.unicode.org/Public/>, <http://www.unicode.org/reports/>,
<http://www.unicode.org/cldr/data/>, <http://source.icu-project.org/repos/icu/>, and
<http://www.unicode.org/utility/trac/browser/>.

NOTICE TO USER: Carefully read the following legal agreement.

BY DOWNLOADING, INSTALLING, COPYING OR OTHERWISE USING UNICODE INC.'S
DATA FILES ("DATA FILES"), AND/OR SOFTWARE ("SOFTWARE"),
YOU UNEQUIVOCALLY ACCEPT, AND AGREE TO BE BOUND BY, ALL OF THE
TERMS AND CONDITIONS OF THIS AGREEMENT.
IF YOU DO NOT AGREE, DO NOT DOWNLOAD, INSTALL, COPY, DISTRIBUTE OR USE
THE DATA FILES OR SOFTWARE.

COPYRIGHT

AND PERMISSION NOTICE

Copyright 1991-2016 Unicode, Inc. All rights reserved.

Distributed under the Terms of Use in <http://www.unicode.org/copyright.html>.

Permission is hereby granted, free of charge, to any person obtaining
a copy of the Unicode data files and any associated documentation
(the "Data Files") or Unicode software and any associated documentation
(the "Software") to deal in the Data Files or Software

without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, and/or sell copies of the Data Files or Software, and to permit persons to whom the Data Files or Software are furnished to do so, provided that either

- (a) this copyright and permission notice appear with all copies of the Data Files or Software, or
- (b) this copyright and permission notice appear in associated Documentation.

THE DATA FILES AND SOFTWARE ARE PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT OF THIRD PARTY RIGHTS. IN NO EVENT SHALL THE COPYRIGHT HOLDER OR HOLDERS INCLUDED IN THIS NOTICE BE LIABLE FOR ANY CLAIM, OR ANY SPECIAL INDIRECT OR CONSEQUENTIAL DAMAGES, OR ANY DAMAGES WHATSOEVER RESULTING FROM LOSS OF USE, DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE OR OTHER TORTIOUS ACTION, ARISING OUT OF OR IN CONNECTION WITH THE USE OR PERFORMANCE OF THE DATA FILES OR SOFTWARE.

Except as contained in this notice, the name of a copyright holder shall not be used in advertising or otherwise to promote the sale, use or other dealings in these Data Files or Software without prior written authorization of the copyright holder.

Libidn2 COPYING -- Licensing information. - *- outline - *-
Copyright (C) 2011-2016 Simon Josefsson
See the end for copying conditions.

The source code for the C library (libidn2.a or libidn.so) are licensed under the terms of either the GNU General Public License version 2.0 or later (see the file COPYINGv2) or the GNU Lesser General Public License version 3.0 or later (see the file COPYING.LESSERv3), or both in parallel as here.

The command line tool, self tests, examples, and other auxilliary files, are licensed under the GNU General Public License version 3.0 or later.

The license of the Unicode character data files (which are parsed into static storage in the library) are documented in COPYING.unicode.

Other files are licensed as indicated in each file.

There may be exceptions to these general rules, see each file for precise information.

This file is free software: you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation, either version 3 of the License, or (at your option) any later version.

This file is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details.

You should have received a copy of the GNU General Public License along with this file. If not, see <<http://www.gnu.org/licenses/>>.

1.23 sed 4.4-2

1.23.1 Available under license :

GNU GENERAL PUBLIC LICENSE

Version 3, 29 June 2007

Copyright (C) 2007 Free Software Foundation, Inc. <<http://fsf.org/>>

Everyone is permitted to copy and distribute verbatim copies of this license document, but changing it is not allowed.

Preamble

The GNU General Public License is a free, copyleft license for software and other kinds of works.

The licenses for most software and other practical works are designed to take away your freedom to share and change the works. By contrast, the GNU General Public License is intended to guarantee your freedom to share and change all versions of a program--to make sure it remains free software for all its users. We, the Free Software Foundation, use the GNU General Public License for most of our software; it applies also to any other work released this way by its authors. You can apply it to your programs, too.

When we speak of free software, we are referring to freedom, not price. Our General Public Licenses are designed to make sure that you have the freedom to distribute copies of free software (and charge for them if you wish), that you receive source code or can get it if you want it, that you can change the software or use pieces of it in new free programs, and that you know you can do these things.

To protect your rights, we need to prevent others from denying you

these rights or asking you to surrender the rights. Therefore, you have certain responsibilities if you distribute copies of the software, or if you modify it: responsibilities to respect the freedom of others.

For example, if you distribute copies of such a program, whether gratis or for a fee, you must pass on to the recipients the same freedoms that you received. You must make sure that they, too, receive or can get the source code. And you must show them these terms so they know their rights.

Developers that use the GNU GPL protect your rights with two steps:

(1)

assert copyright on the software, and (2) offer you this License giving you legal permission to copy, distribute and/or modify it.

For the developers' and authors' protection, the GPL clearly explains that there is no warranty for this free software. For both users' and authors' sake, the GPL requires that modified versions be marked as changed, so that their problems will not be attributed erroneously to authors of previous versions.

Some devices are designed to deny users access to install or run modified versions of the software inside them, although the manufacturer can do so. This is fundamentally incompatible with the aim of protecting users' freedom to change the software. The systematic pattern of such abuse occurs in the area of products for individuals to use, which is precisely where it is most unacceptable. Therefore, we have designed this version of the GPL to prohibit the practice for those products. If such problems arise substantially in other domains, we stand

ready to extend this provision to those domains in future versions of the GPL, as needed to protect the freedom of users.

Finally, every program is threatened constantly by software patents. States should not allow patents to restrict development and use of software on general-purpose computers, but in those that do, we wish to avoid the special danger that patents applied to a free program could make it effectively proprietary. To prevent this, the GPL assures that patents cannot be used to render the program non-free.

The precise terms and conditions for copying, distribution and modification follow.

TERMS AND CONDITIONS

0. Definitions.

"This License" refers to version 3 of the GNU General Public License.

"Copyright" also means copyright-like laws that apply to other kinds of works, such as semiconductor masks.

"The Program" refers to any copyrightable work licensed under this License. Each licensee is addressed as "you". "Licensees" and "recipients" may be individuals or organizations.

To "modify" a work means to copy from or adapt all or part of the work in a fashion requiring copyright permission, other than the making of an exact copy. The resulting work is called a "modified version" of the earlier work or a work "based on" the earlier work.

A "covered work" means either the unmodified Program or a work based on the Program.

To "propagate" a work means to do anything with it that, without permission, would make you directly or secondarily liable for infringement under applicable copyright law, except executing it on a computer or modifying a private copy. Propagation includes copying, distribution (with or without modification), making available to the public, and in some countries other activities as well.

To "convey" a work means any kind of propagation that enables other parties to make or receive copies. Mere interaction with a user through a computer network, with no transfer of a copy, is not conveying.

An interactive user interface displays "Appropriate Legal Notices" to the extent that it includes a convenient and prominently visible feature that (1) displays an appropriate copyright notice, and (2) tells the user that there is no warranty for the work (except to the extent that warranties are provided), that licensees may convey the work under this License, and how to view a copy of this License. If the interface presents a list of user commands or options, such as a menu, a prominent item in the list meets this criterion.

1. Source Code.

The "source code" for a work means the preferred form of the work for making modifications to it. "Object code" means any non-source form of a work.

A "Standard Interface" means an interface that either is an official standard defined by a recognized standards body, or, in the case of interfaces specified for a particular programming language, one that is widely used among developers working in that language.

The

"System Libraries" of an executable work include anything, other than the work as a whole, that (a) is included in the normal form of packaging a Major Component, but which is not part of that Major Component, and (b) serves only to enable use of the work with that Major Component, or to implement a Standard Interface for which an implementation is available to the public in source code form. A "Major Component", in this context, means a major essential component (kernel, window system, and so on) of the specific operating system (if any) on which the executable work runs, or a compiler used to produce the work, or an object code interpreter used to run it.

The "Corresponding Source" for a work in object code form means all the source code needed to generate, install, and (for an executable work) run the object code and to modify the work, including scripts to control those activities. However, it does not include the work's System Libraries, or general-purpose tools or generally available free programs which are used unmodified in performing those activities but which are not part of the work. For example, Corresponding Source includes interface definition files associated with source files for the work, and the source code for shared libraries and dynamically linked subprograms that the work is specifically designed to require, such as by intimate data communication or control flow between those subprograms and other parts of the work.

The Corresponding Source need not include anything that users can regenerate automatically from other parts of the Corresponding Source.

The Corresponding Source for a work in source code form is that same work.

2. Basic Permissions.

All rights granted under this License are granted for the term of copyright on the Program, and are irrevocable provided the stated conditions are met. This License explicitly affirms your unlimited permission to run the unmodified Program. The output from running a covered work is covered by this License only if the output, given its content, constitutes a covered work. This License acknowledges your rights of fair use or other equivalent, as provided by copyright law.

You may make, run and propagate covered works that you do not convey, without conditions so long as your license otherwise remains in force. You may convey covered works to others for the sole purpose

of having them make modifications exclusively for you, or provide you with facilities for running those works, provided that you comply with the terms of this License in conveying all material for which you do not control copyright. Those thus making or running the covered works for you must do so exclusively on your behalf, under your direction and control, on terms that prohibit them from making any copies of your copyrighted material outside their relationship with you.

Conveying under any other circumstances is permitted solely under the conditions stated below. Sublicensing is not allowed;

section 10

makes it unnecessary.

3. Protecting Users' Legal Rights From Anti-Circumvention Law.

No covered work shall be deemed part of an effective technological measure under any applicable law fulfilling obligations under article 11 of the WIPO copyright treaty adopted on 20 December 1996, or similar laws prohibiting or restricting circumvention of such measures.

When you convey a covered work, you waive any legal power to forbid circumvention of technological measures to the extent such circumvention is effected by exercising rights under this License with respect to the covered work, and you disclaim any intention to limit operation or modification of the work as a means of enforcing, against the work's users, your or third parties' legal rights to forbid circumvention of technological measures.

4. Conveying Verbatim Copies.

You may convey verbatim copies of the Program's source code as you receive it, in any medium, provided that you conspicuously and appropriately

publish on each copy an appropriate copyright notice;
keep intact all notices stating that this License and any non-permissive terms added in accord with section 7 apply to the code;
keep intact all notices of the absence of any warranty; and give all recipients a copy of this License along with the Program.

You may charge any price or no price for each copy that you convey, and you may offer support or warranty protection for a fee.

5. Conveying Modified Source Versions.

You may convey a work based on the Program, or the modifications to produce it from the Program, in the form of source code under the terms of section 4, provided that you also meet all of these conditions:

- a) The work must carry prominent notices stating that you modified it, and giving a relevant date.

- b) The work must carry prominent notices stating that it is released under this License and any conditions added under section 7. This requirement modifies the requirement in section 4 to "keep intact all notices".

- c) You must license the entire work, as a whole, under this License to anyone who comes into possession of a copy. This License will therefore apply, along with any applicable section 7 additional terms, to the whole of the work, and all its parts, regardless of how they are packaged. This License gives no permission to license the work in any other way, but it does not invalidate such permission if you have separately received it.

- d) If the work has interactive user interfaces, each must display Appropriate Legal Notices; however, if the Program has interactive interfaces that do not display Appropriate Legal Notices, your work need not make them do so.

A compilation of a covered work with other separate and independent works, which are not by their nature extensions of the covered work, and which are not combined with it such as to form a larger program, in or on a volume of a storage or distribution medium, is called an "aggregate" if the compilation and its resulting copyright are not used to limit the access or legal rights of the compilation's users beyond what the individual works permit. Inclusion of a covered work in an aggregate does not cause this License to apply to the other parts of the aggregate.

6. Conveying Non-Source Forms.

You may convey a covered work in object code form under the terms of sections 4 and 5, provided that you also convey the machine-readable Corresponding Source under the terms of this License, in one of these ways:

- a) Convey the object code in, or embodied in, a physical product (including a physical distribution medium), accompanied by the Corresponding Source fixed on a durable physical medium customarily used for software interchange.

- b) Convey the object code in, or embodied in, a physical product (including a physical distribution medium), accompanied by a

written offer, valid for at least three years

and valid for as

long as you offer spare parts or customer support for that product model, to give anyone who possesses the object code either (1) a copy of the Corresponding Source for all the software in the product that is covered by this License, on a durable physical medium customarily used for software interchange, for a price no more than your reasonable cost of physically performing this conveying of source, or (2) access to copy the Corresponding Source from a network server at no charge.

c) Convey individual copies of the object code with a copy of the written offer to provide the Corresponding Source. This alternative is allowed only occasionally and noncommercially, and only if you received the object code with such an offer, in accord with subsection 6b.

d) Convey the object code by offering access from a designated place (gratis or for a charge), and offer equivalent access to the Corresponding Source in the same way through the same place at no further charge. You need not require recipients to copy the Corresponding Source along with the object code. If the place to copy the object code is a network server, the Corresponding Source may be on a different server (operated by you or a third party) that supports equivalent copying facilities, provided you maintain clear directions next to the object code saying where to find the Corresponding Source. Regardless of what server hosts the Corresponding Source, you remain obligated to ensure that it is available for as long as needed to satisfy these requirements.

e) Convey the object code using peer-to-peer transmission, provided you inform other peers where the object code and Corresponding Source of the work are being offered to the general public at no charge under subsection 6d.

A separable portion of the object code, whose source code is excluded from the Corresponding Source as a System Library, need not be included in conveying the object code work.

A "User Product" is either (1) a "consumer product", which means any tangible personal property which is normally used for personal, family, or household purposes, or (2) anything designed or sold for incorporation into a dwelling. In determining whether a product is a consumer product, doubtful cases shall be resolved in favor of coverage. For a particular product received by a particular user, "normally used" refers to a typical or common use of that class of product, regardless of the status

of the particular user or of the way in which the particular user actually uses, or expects or is expected to use, the product. A product is a consumer product regardless of whether the product has substantial commercial, industrial or non-consumer uses, unless such uses represent the only significant mode of use of the product.

"Installation Information" for a User Product means any methods, procedures, authorization keys, or other information required to install and execute modified versions of a covered work in that User Product from a modified version of its Corresponding Source. The information must suffice to ensure that the continued functioning of the modified object code is in no case prevented or interfered with solely because modification has been made.

If you convey an object code work under this section in, or with, or specifically for use in, a User Product, and the conveying occurs as part of a transaction in which the right of possession and use of the User Product is transferred to the recipient in perpetuity or for a fixed term (regardless of how the transaction is characterized), the Corresponding Source conveyed under this section must be accompanied by the Installation Information. But this requirement does not apply if neither you nor any third party retains the ability to install modified object code on the User Product (for example, the work has been installed in ROM).

The requirement to provide Installation Information does not include a requirement to continue to provide support service, warranty, or updates for a work that has been modified or installed by the recipient, or for the User Product in which it has been modified or installed. Access to a network may be denied when the modification itself materially and adversely affects the operation of the network or violates the rules and protocols for communication across the network.

Corresponding Source conveyed, and Installation Information provided, in accord with this section must be in a format that is publicly documented (and with an implementation available to the public in source code form), and must require no special password or key for unpacking, reading or copying.

7. Additional Terms.

"Additional permissions" are terms that supplement the terms of this License by making exceptions from one or more of its conditions. Additional permissions that are applicable to the entire Program shall be treated as though they were included in this License, to the extent

that they are valid under applicable law. If additional permissions apply only to part of the Program, that part may be used separately under those permissions, but the entire Program remains governed by this License without regard to the additional permissions.

When you convey a copy of a covered work, you may at your option remove any additional permissions from that copy, or from any part of it. (Additional permissions may be written to require their own removal in certain cases when you modify the work.) You may place additional permissions on material, added by you to a covered work, for which you have or can give appropriate copyright permission.

Notwithstanding any other provision of this License, for material you add to a covered work, you may (if authorized by the copyright holders of that material) supplement the terms of this License with terms:

- a) Disclaiming warranty or limiting liability differently from the terms of sections 15 and 16 of this License; or
- b) Requiring preservation of specified reasonable legal notices or author attributions in that material or in the Appropriate Legal Notices displayed by works containing it; or
- c) Prohibiting misrepresentation of the origin of that material, or requiring that modified versions of such material be marked in reasonable ways as different from the original version; or
- d) Limiting the use for publicity purposes of names of licensors or authors of the material; or
- e) Declining to grant rights under trademark law for use of some trade names, trademarks, or service marks; or
- f) Requiring indemnification of licensors and authors of that material by anyone who conveys the material (or modified versions of it) with contractual assumptions of liability to the recipient, for any liability that these contractual assumptions directly impose on those licensors and authors.

All other non-permissive additional terms are considered "further restrictions" within the meaning of section 10. If the Program as you received it, or any part of it, contains a notice stating that it is governed by this License along with a term that is a further restriction, you may remove that term. If a license document contains a further restriction but permits relicensing or conveying under this License, you may add to a covered work material governed by the terms

of that license document, provided that the further restriction does not survive such relicensing or conveying.

If you add terms to a covered work in accord with this section, you must place, in the relevant source files, a statement of the additional terms that apply to those files, or a notice indicating where to find the applicable terms.

Additional terms, permissive or non-permissive, may be stated in the form of a separately written license, or stated as exceptions; the above requirements apply either way.

8. Termination.

You may not propagate or modify a covered work except as expressly provided under this License. Any attempt otherwise to propagate or modify it is void, and will automatically terminate your rights under this License (including any patent licenses granted under the third paragraph of section 11).

However, if you cease all violation of this License, then your license from a particular copyright holder is reinstated (a) provisionally, unless and until the copyright holder explicitly and finally terminates your license, and (b) permanently, if the copyright holder fails to notify you of the violation by some reasonable means prior to 60 days after the cessation.

Moreover, your license from a particular copyright holder is reinstated permanently if the copyright holder notifies you of the violation by some reasonable means, this is the first time you have received notice of violation of this License (for any work) from that copyright holder, and you cure the violation prior to 30 days after your receipt of the notice.

Termination of your rights under this section does not terminate the licenses of parties who have received copies or rights from you under this License. If your rights have been terminated and not permanently reinstated, you do not qualify to receive new licenses for the same material under section 10.

9. Acceptance Not Required for Having Copies.

You are not required to accept this License in order to receive or run a copy of the Program. Ancillary propagation of a covered work occurring solely as a consequence of using peer-to-peer transmission to receive a copy likewise does not require acceptance. However,

nothing other than this License grants you permission to propagate or modify any covered work. These actions infringe copyright if you do not accept this License. Therefore, by modifying or propagating a covered work, you indicate your acceptance of this License to do so.

10. Automatic Licensing of Downstream Recipients.

Each time you convey a covered work, the recipient automatically receives a license from the original licensors, to run, modify and propagate that work, subject to this License. You are not responsible for enforcing compliance by third parties with this License.

An "entity transaction" is a transaction transferring control of an organization, or substantially all assets of one, or subdividing an organization, or merging organizations. If propagation of a covered work results from an entity transaction, each party to that transaction who receives a copy of the work also receives whatever licenses to the work the party's predecessor in interest had or could give under the previous paragraph, plus a right to possession of the Corresponding Source of the work from the predecessor in interest, if the predecessor has it or can get it with reasonable efforts.

You may not impose any further restrictions on the exercise of the rights granted or affirmed under this License. For example, you may not impose a license fee, royalty, or other charge for exercise of rights granted under this License, and you may not initiate litigation (including a cross-claim or counterclaim in a lawsuit) alleging that any patent claim is infringed by making, using, selling, offering for sale, or importing the Program or any portion of it.

11. Patents.

A "contributor" is a copyright holder who authorizes use under this License of the Program or a work on which the Program is based. The work thus licensed is called the contributor's "contributor version".

A contributor's "essential patent claims" are all patent claims owned or controlled by the contributor, whether already acquired or hereafter acquired, that would be infringed by some manner, permitted by this License, of making, using, or selling its contributor version, but do not include claims that would be infringed only as a consequence of further modification of the contributor version. For purposes of this definition, "control" includes the right to grant patent sublicenses in a manner consistent with the requirements of this License.

Each contributor grants you a non-exclusive, worldwide, royalty-free patent license under the contributor's essential patent claims, to make, use, sell, offer for sale, import and otherwise run, modify and propagate the contents of its contributor version.

In the following three paragraphs, a "patent license" is any express agreement or commitment, however denominated, not to enforce a patent (such as an express permission to practice a patent or covenant not to sue for patent infringement). To "grant" such a patent license to a party means to make such an agreement or commitment not to enforce a patent against the party.

If you convey a covered work, knowingly relying on a patent license, and the Corresponding Source of the work is not available for anyone to copy, free of charge and under the terms of this

License, through a publicly available network server or other readily accessible means, then you must either (1) cause the Corresponding Source to be so available, or (2) arrange to deprive yourself of the benefit of the patent license for this particular work, or (3) arrange, in a manner consistent with the requirements of this License, to extend the patent license to downstream recipients. "Knowingly relying" means you have actual knowledge that, but for the patent license, your conveying the covered work in a country, or your recipient's use of the covered work in a country, would infringe one or more identifiable patents in that country that you have reason to believe are valid.

If, pursuant to or in connection with a single transaction or arrangement, you convey, or propagate by procuring conveyance of, a covered work, and grant a patent license to some of the parties receiving the covered work authorizing them to use, propagate, modify or convey a specific copy of the covered work, then the patent license you grant is automatically extended to all recipients of the covered work and works based on it.

A patent license is "discriminatory" if it does not include within the scope of its coverage, prohibits the exercise of, or is conditioned on the non-exercise of one or more of the rights that are specifically granted under this License. You may not convey a covered work if you are a party to an arrangement with a third party that is in the business of distributing software, under which you make payment to the third party based on the extent of your activity of conveying the work, and under which the third party grants, to any of the parties who would receive the covered work from you, a discriminatory patent license (a) in connection with copies of the covered work conveyed by you (or copies made from those copies), or (b) primarily

for and in connection with specific products or compilations that contain the covered work, unless you entered into that arrangement, or that patent license was granted, prior to 28 March 2007.

Nothing in this License shall be construed as excluding or limiting any implied license or other defenses to infringement that may otherwise be available to you under applicable patent law.

12. No Surrender of Others' Freedom.

If conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot convey a covered work so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not convey it at all. For example, if you agree to terms that obligate you to collect a royalty for further conveying from those to whom you convey the Program, the only way you could satisfy both those terms and this License would be to refrain entirely from conveying the Program.

13. Use with the GNU Affero General Public License.

Notwithstanding any other provision of this License, you have permission to link or combine any covered work with a work licensed under version 3 of the GNU Affero General Public License into a single combined work, and to convey the resulting work. The terms of this License will continue to apply to the part which is the covered work, but the special requirements of the GNU Affero General Public License, section 13, concerning interaction through a network will apply to the combination as such.

14. Revised Versions of this License.

The Free Software Foundation may publish revised and/or new versions of the GNU General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Program specifies that a certain numbered version of the GNU General Public License "or any later version" applies to it, you have the option of following the terms and conditions either of that numbered version or of any later version published by the Free Software Foundation. If the Program does not specify a version number of the GNU General Public License, you may choose any version ever published by the Free Software Foundation.

If the Program specifies that a proxy can decide which future versions of the GNU General Public License can be used, that proxy's public statement of acceptance of a version permanently authorizes you to choose that version for the Program.

Later license versions may give you additional or different permissions. However, no additional obligations are imposed on any author or copyright holder as a result of your choosing to follow a later version.

15. Disclaimer of Warranty.

THERE IS NO WARRANTY FOR THE PROGRAM, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE PROGRAM "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE PROGRAM IS WITH YOU. SHOULD THE PROGRAM PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

16. Limitation of Liability.

IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MODIFIES AND/OR CONVEYS THE PROGRAM AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE PROGRAM (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE PROGRAM TO OPERATE WITH ANY OTHER PROGRAMS), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

17.

Interpretation of Sections 15 and 16.

If the disclaimer of warranty and limitation of liability provided above cannot be given local legal effect according to their terms, reviewing courts shall apply local law that most closely approximates an absolute waiver of all civil liability in connection with the Program, unless a warranty or assumption of liability accompanies a copy of the Program in return for a fee.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Programs

If you develop a new program, and you want it to be of the greatest possible use to the public, the best way to achieve this is to make it free software which everyone can redistribute and change under these terms.

To do so, attach the following notices to the program. It is safest to attach them to the start of each source file to most effectively state the exclusion of warranty; and each file should have at least the "copyright" line and a pointer to where the full notice is found.

```
<one line to give the program's name and a brief idea of what it does.>  
Copyright (C) <year> <name of author>
```

This program is free software: you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation, either version 3 of the License, or (at your option) any later version.

This program is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details.

You should have received a copy of the GNU General Public License along with this program. If not, see <http://www.gnu.org/licenses/>.

Also add information on how to contact you by electronic and paper mail.

If the program does terminal interaction, make it output a short notice like this when it starts in an interactive mode:

```
<program> Copyright (C) <year> <name of author>  
This program comes with ABSOLUTELY NO WARRANTY; for details type `show w'.  
This is free software, and you are welcome to redistribute it  
under certain conditions; type `show c' for details.
```

The hypothetical commands `show w' and `show c' should show the appropriate parts of the General Public License. Of course, your program's commands might be different; for a GUI interface, you would use an "about box".

You should also get your employer (if you work as a programmer) or school, if any, to sign a "copyright disclaimer" for the program, if necessary. For more information on this, and how to apply and follow the GNU GPL, see <http://www.gnu.org/licenses/>.

The GNU General Public License does not permit incorporating your program

into proprietary programs. If your program is a subroutine library, you may consider it more useful to permit linking proprietary applications with the library. If this is what you want to do, use the GNU Lesser General Public License instead of this License. But first, please read <<http://www.gnu.org/philosophy/why-not-lgpl.html>>. @c The GNU Free Documentation License. @center Version 1.3, 3 November 2008

@c This file is intended to be included within another document, @c hence no sectioning command or @node.

@display
Copyright @copyright{ } 2000, 2001, 2002, 2007, 2008 Free Software Foundation, Inc.
@uref{<http://fsf.org/>}

Everyone is permitted to copy and distribute verbatim copies of this license document, but changing it is not allowed.
@end display

@enumerate 0
@item
PREAMBLE

The purpose of this License is to make a manual, textbook, or other functional and useful document @dfn{free} in the sense of freedom: to assure everyone the effective freedom to copy and redistribute it, with or without modifying it, either commercially or noncommercially. Secondly, this License preserves for the author and publisher a way to get credit for their work, while not being considered responsible for modifications made by others.

This License is a kind of ``copyleft'', which means that derivative works of the document must themselves be free in the same sense. It complements the GNU General Public License, which is a copyleft license designed for free software.

We have designed this License in order to use it for manuals for free software, because free software needs free documentation: a free program should come with manuals providing the same freedoms that the software does. But this License is not limited to software manuals; it can be used for any textual work, regardless of subject matter or whether it is published as a printed book. We recommend this License principally for works whose purpose is instruction or reference.

@item
APPLICABILITY AND DEFINITIONS

This License applies to any manual or other work, in any medium, that contains a notice placed by the copyright holder saying it can be distributed under the terms of this License. Such a notice grants a world-wide, royalty-free license, unlimited in duration, to use that work under the conditions stated herein. The "Document", below, refers

to any such manual or work. Any member of the public is a licensee, and is addressed as "you". You accept the license if you copy, modify or distribute the work in a way requiring permission under copyright law.

A "Modified Version" of the Document means any work containing the Document or a portion of it, either copied verbatim, or with modifications and/or translated into another language.

A "Secondary Section" is a named appendix or a front-matter section of the Document that deals exclusively with the relationship of the publishers or authors of the Document to the Document's overall subject (or to related matters) and contains nothing that could fall directly within that overall subject. (Thus, if the Document is in part a textbook of mathematics, a Secondary Section may not explain any mathematics.) The relationship could be a matter of historical connection with the subject or with related matters, or of legal, commercial, philosophical, ethical or political position regarding them.

The "Invariant Sections" are certain Secondary Sections whose titles are designated, as being those of Invariant Sections, in the notice that says that the Document is released under this License. If a section does not fit the above definition of Secondary then it is not allowed to be designated as Invariant. The Document may contain zero Invariant Sections. If the Document does not identify any Invariant Sections then there are none.

The "Cover Texts" are certain short passages of text that are listed, as Front-Cover Texts or Back-Cover Texts, in the notice that says that the Document is released under this License. A Front-Cover Text may be at most 5 words, and a Back-Cover Text may be at most 25 words.

A "Transparent" copy of the Document means a machine-readable copy, represented in a format whose specification is available to the general public, that is suitable for revising the document straightforwardly with generic text editors or (for images composed of pixels) generic paint programs or (for drawings) some widely available drawing editor, and that is suitable for input to text formatters or

for automatic translation to a variety of formats suitable for input to text formatters. A copy made in an otherwise Transparent file format whose markup, or absence of markup, has been arranged to thwart or discourage subsequent modification by readers is not Transparent. An image format is not Transparent if used for any substantial amount of text. A copy that is not ``Transparent" is called ``Opaque".

Examples of suitable formats for Transparent copies include plain ASCII without markup, Texinfo input format, La@TeX{ } input format, SGML or XML using a publicly available DTD, and standard-conforming simple HTML, PostScript or PDF designed for human modification. Examples of transparent image formats include PNG, XCF and JPG@. Opaque formats include proprietary formats that can be read and edited only by proprietary word processors, SGML or XML for which the DTD and/or processing tools are not generally available, and the machine-generated HTML, PostScript or PDF produced by some word processors for output purposes only.

The ``Title Page" means, for a printed book, the title page itself, plus such following pages as are needed to hold, legibly, the material this License requires to appear in the title page. For works in formats which do not have any title page as such, ``Title Page" means the text near the most prominent appearance of the work's title, preceding the beginning of the body of the text.

The ``publisher" means any person or entity that distributes copies of the Document to the public.

A section ``Entitled XYZ" means a named subunit of the Document whose title either is precisely XYZ or contains XYZ in parentheses following text that translates XYZ in another language. (Here XYZ stands for a specific section name mentioned below, such as ``Acknowledgements", ``Dedications", ``Endorsements", or ``History".) To ``Preserve the Title" of such a section when you modify the Document means that it remains a section ``Entitled XYZ" according to this definition.

The Document may include Warranty Disclaimers next to the notice which states that this License applies to the Document. These Warranty Disclaimers are considered to be included by reference in this License, but only as regards disclaiming warranties: any other implication that these Warranty Disclaimers may have is void and has no effect on the meaning of this License.

@item

VERBATIM COPYING

You may copy and distribute the Document in any medium, either commercially or noncommercially, provided that this License, the copyright notices, and the license notice saying this License applies to the Document are reproduced in all copies, and that you add no other conditions whatsoever to those of this License. You may not use technical measures to obstruct or control the reading or further copying of the copies

you make or distribute. However, you may accept compensation in exchange for copies. If you distribute a large enough number of copies you must also follow the conditions in section 3.

You may also lend copies, under the same conditions stated above, and you may publicly display copies.

@item

COPYING IN QUANTITY

If you publish printed copies (or copies in media that commonly have printed covers) of the Document, numbering more than 100, and the Document's license notice requires Cover Texts, you must enclose the copies in covers that carry, clearly and legibly, all these Cover Texts: Front-Cover Texts on the front cover, and Back-Cover Texts on the back cover. Both covers must also clearly and legibly identify you as the publisher of these copies. The front cover must present the full title with all words of the title equally prominent and visible. You may add other material on the covers in addition.

Copying with changes limited to the covers, as long as they preserve the

title of the Document and satisfy these conditions, can be treated as verbatim copying in other respects.

If the required texts for either cover are too voluminous to fit legibly, you should put the first ones listed (as many as fit reasonably) on the actual cover, and continue the rest onto adjacent pages.

If you publish or distribute Opaque copies of the Document numbering more than 100, you must either include a machine-readable Transparent copy along with each Opaque copy, or state in or with each Opaque copy a computer-network location from which the general network-using public has access to download using public-standard network protocols a complete Transparent copy of the Document, free of added material.

If you use the latter option, you must take reasonably prudent steps, when you begin distribution of Opaque copies in quantity, to ensure that this Transparent copy will remain thus accessible at the stated location until at least one year after the last time you distribute

an

Opaque copy (directly or through your agents or retailers) of that edition to the public.

It is requested, but not required, that you contact the authors of the Document well before redistributing any large number of copies, to give them a chance to provide you with an updated version of the Document.

@item

MODIFICATIONS

You may copy and distribute a Modified Version of the Document under the conditions of sections 2 and 3 above, provided that you release the Modified Version under precisely this License, with the Modified Version filling the role of the Document, thus licensing distribution and modification of the Modified Version to whoever possesses a copy of it. In addition, you must do these things in the Modified Version:

@enumerate A

@item

Use in the Title Page (and on the covers, if any) a title distinct from that of the Document, and from those of previous versions (which should, if there were any, be listed in the History section of the Document). You may use the same title as a previous version if the original publisher of that version gives permission.

@item

List on the Title Page, as authors, one or more persons or entities responsible for authorship of the modifications in the Modified Version, together with at least five of the principal authors of the Document (all of its principal authors, if it has fewer than five), unless they release you from this requirement.

@item

State on the Title page the name of the publisher of the Modified Version, as the publisher.

@item

Preserve all the copyright notices of the Document.

@item

Add an appropriate copyright notice for your modifications adjacent to the other copyright notices.

@item

Include, immediately after the copyright notices, a license notice giving the public permission to use the Modified Version under the

terms of this License, in the form shown in the Addendum below.

@item

Preserve in that license notice the full lists of Invariant Sections and required Cover Texts given in the Document's license notice.

@item

Include an unaltered copy of this License.

@item

Preserve the section Entitled ``History'', Preserve its Title, and add to it an item stating at least the title, year, new authors, and publisher of the Modified Version as given on the Title Page. If there is no section Entitled ``History'' in the Document, create one stating the title, year, authors, and publisher of the Document as given on its Title Page, then add an item describing the Modified Version as stated in the previous sentence.

@item

Preserve the network location, if any, given in the Document for public access to a Transparent copy of the Document, and likewise the network locations given in the Document for previous versions it was based on. These may be placed in the ``History'' section. You may omit a network location for a work that was published at least four years before the Document itself, or if the original publisher of the version it refers to gives permission.

@item

For any section Entitled ``Acknowledgements'' or ``Dedications'', Preserve the Title of the section, and preserve in the section all the substance and tone of each of the contributor acknowledgements and/or dedications given therein.

@item

Preserve all the Invariant Sections of the Document, unaltered in their text and in their titles. Section numbers or the equivalent are not considered part of the section titles.

@item

Delete any section Entitled ``Endorsements''. Such a section may not be included in the Modified Version.

@item

Do not retitle any existing section to be Entitled ``Endorsements'' or to conflict in title with any Invariant Section.

@item

Preserve any Warranty Disclaimers.

@end enumerate

If the Modified Version includes new front-matter sections or appendices that qualify as Secondary Sections and contain no material copied from the Document, you may at your option designate some or all of these sections as invariant. To do this, add their titles to the list of Invariant

Sections in the Modified Version's license notice.

These titles must be distinct from any other section titles.

You may add a section Entitled ``Endorsements'', provided it contains nothing but endorsements of your Modified Version by various parties---for example, statements of peer review or that the text has been approved by an organization as the authoritative definition of a standard.

You may add a passage of up to five words as a Front-Cover Text, and a passage of up to 25 words as a Back-Cover Text, to the end of the list of Cover Texts in the Modified Version. Only one passage of Front-Cover Text and one of Back-Cover Text may be added by (or through arrangements made by) any one entity. If the Document already includes a cover text for the same cover, previously added by you or by arrangement made by the same entity you are acting on behalf of, you may not add another; but you may replace the old one, on explicit permission from the previous publisher that added the old one.

The author(s) and publisher(s) of the Document do not by this License give permission to use their names for publicity for or to assert or imply endorsement of any Modified Version.

@item

COMBINING DOCUMENTS

You may combine the Document with other documents released under this License, under the terms defined in section 4 above for modified versions, provided that you include in the combination all of the Invariant Sections of all of the original documents, unmodified, and list them all as Invariant Sections of your combined work in its license notice, and that you preserve all their Warranty Disclaimers.

The combined work need only contain one copy of this License, and multiple identical Invariant Sections may be replaced with a single copy. If there are multiple Invariant Sections with the same name but different contents, make the title of each such section unique by adding at the end of it, in parentheses, the name of the original

author or publisher of that section if known, or else a unique number. Make the same adjustment to the section titles in the list of Invariant Sections in the license notice of the combined work.

In the combination, you must combine any sections Entitled ``History" in the various original documents, forming one section Entitled ``History"; likewise combine any sections Entitled ``Acknowledgements", and any sections Entitled ``Dedications". You must delete all sections Entitled ``Endorsements."

@item

COLLECTIONS OF DOCUMENTS

You may make a collection consisting of the Document and other documents released under this License, and replace the individual copies of this License in the various documents with a single copy that is included in the collection, provided that you follow the rules of this License for verbatim copying of each of the documents in all other respects.

You may extract a single document from such a collection, and distribute it individually under this License, provided you insert a copy of this License into the extracted document, and follow this License in all other respects regarding verbatim copying of that document.

@item

AGGREGATION WITH INDEPENDENT WORKS

A compilation of the Document or its derivatives with other separate and independent documents or works, in or on a volume of a storage or distribution medium, is called an ``aggregate" if the copyright resulting from the compilation is not used to limit the legal rights of the compilation's users beyond what the individual works permit. When the Document is included in an aggregate, this License does not apply to the other works in the aggregate which are not themselves derivative works of the Document.

If the Cover Text requirement of section 3 is applicable to these copies of the Document, then if the Document is less than one half of the entire aggregate, the Document's Cover Texts may be placed on covers that bracket the Document within the aggregate, or the electronic equivalent of covers if the Document is in electronic form.

Otherwise they must appear on printed covers that bracket the whole aggregate.

@item

TRANSLATION

Translation is considered a kind of modification, so you may distribute translations of the Document under the terms of section 4. Replacing Invariant Sections with translations requires special permission from their copyright holders, but you may include translations of some or all Invariant Sections in addition to the original versions of these Invariant Sections. You may include a translation of this License, and all the license notices in the Document, and any Warranty Disclaimers, provided that you also include the original English version of this License and the original versions of those notices and disclaimers. In case of a disagreement between the translation and the original version of this License or a notice or disclaimer, the original version will prevail.

If a section in the Document is Entitled ``Acknowledgements'', ``Dedications'', or ``History'', the requirement (section 4) to Preserve its Title (section 1) will typically require changing the actual title.

@item

TERMINATION

You may not copy, modify, sublicense, or distribute the Document except as expressly provided under this License. Any attempt otherwise to copy, modify, sublicense, or distribute it is void, and will automatically terminate your rights under this License.

However, if you cease all violation of this License, then your license from a particular copyright holder is reinstated (a) provisionally, unless and until the copyright holder explicitly and finally terminates your license, and (b) permanently, if the copyright holder fails to notify you of the violation by some reasonable means prior to 60 days after the cessation.

Moreover, your license from a particular copyright holder is reinstated permanently if the copyright holder notifies you of the violation by some reasonable means, this is the first time you have received notice of violation of this License (for any work) from that copyright holder, and you cure the violation prior to 30 days after your receipt of the notice.

Termination of your rights under this section does not terminate the licenses of parties who have received copies or rights from you under this License. If your rights have been terminated and not permanently reinstated, receipt of a copy of some or all of the same material does

not give you any rights to use it.

@item

FUTURE REVISIONS OF THIS LICENSE

The Free Software Foundation may publish new, revised versions of the GNU Free Documentation License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns. See <http://www.gnu.org/copyleft/>.

Each version of the License is given a distinguishing version number. If the Document specifies that a particular numbered version of this License "or any later version" applies to it, you have the option of following the terms and conditions either of that specified version or of any later version that has been published (not as a draft) by the Free Software Foundation. If the Document does not specify a version number of this License, you may choose any version ever published (not as a draft) by the Free Software Foundation. If the Document specifies that a proxy can decide which future versions of this License can be used, that proxy's public statement of acceptance of a version permanently authorizes you to choose that version for the Document.

@item

RELICENSING

"Massive Multiauthor Collaboration Site" (or "MMC Site") means any World Wide Web server that publishes copyrightable works and also provides prominent facilities for anybody to edit those works. A public wiki that anybody can edit is an example of such a server. A "Massive Multiauthor Collaboration" (or "MMC") contained in the site means any set of copyrightable works thus published on the MMC site.

"CC-BY-SA" means the Creative Commons Attribution-Share Alike 3.0 license published by Creative Commons Corporation, a not-for-profit corporation with a principal place of business in San Francisco, California, as well as future copyleft versions of that license published by that same organization.

"Incorporate" means to publish or republish a Document, in whole or in part, as part of another Document.

An MMC is "eligible for relicensing" if it is licensed under this License, and if all works that were first published under this License

somewhere other than this MMC, and subsequently incorporated in whole or in part into the MMC, (1) had no cover texts or invariant sections, and (2) were thus incorporated prior to November 1, 2008.

The operator of an MMC Site may republish an MMC contained in the site under CC-BY-SA on the same site at any time before August 1, 2009, provided the MMC is eligible for relicensing.

@end enumerate

@page

@heading ADDENDUM: How to use this License for your documents

To use this License
in a document you have written, include a copy of
the License in the document and put the following copyright and
license notices just after the title page:

@smallexample

@group

Copyright (C) @var{year} @var{your name}.

Permission is granted to copy, distribute and/or modify this document
under the terms of the GNU Free Documentation License, Version 1.3
or any later version published by the Free Software Foundation;
with no Invariant Sections, no Front-Cover Texts, and no Back-Cover
Texts. A copy of the license is included in the section entitled ``GNU
Free Documentation License".

@end group

@end smallexample

If you have Invariant Sections, Front-Cover Texts and Back-Cover Texts,
replace the ``with@dots{ }Texts."@: line with this:

@smallexample

@group

with the Invariant Sections being @var{list their titles}, with
the Front-Cover Texts being @var{list}, and with the Back-Cover Texts
being @var{list}.

@end group

@end smallexample

If you have Invariant
Sections without Cover Texts, or some other
combination of the three, merge those two alternatives to suit the
situation.

If your document contains nontrivial examples of program code, we
recommend releasing these examples in parallel under your choice of

free software license, such as the GNU General Public License, to permit their use in free software.

@c Local Variables:

@c ispell-local-pdict: "ispell-dict"

@c End:

1.24 libcap-ng 0.7.7-3.1

1.24.1 Available under license :

GNU LESSER GENERAL PUBLIC LICENSE

Version 2.1, February 1999

Copyright (C) 1991, 1999 Free Software Foundation, Inc.

51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA

Everyone is permitted to copy and distribute verbatim copies of this license document, but changing it is not allowed.

[This is the first released version of the Lesser GPL. It also counts as the successor of the GNU Library Public License, version 2, hence the version number 2.1.]

Preamble

The licenses for most software are designed to take away your freedom to share and change it. By contrast, the GNU General Public Licenses are intended to guarantee your freedom to share and change free software--to make sure the software is free for all its users.

This license, the Lesser General Public License, applies to some specially designated software packages--typically libraries--of the Free Software Foundation and other authors who decide to use it. You can use it too, but we suggest you first think carefully about whether this license or the ordinary General Public License is the better strategy to use in any particular case, based on the explanations below.

When we speak of free software, we are referring to freedom of use, not price. Our General Public Licenses are designed to make sure that you have the freedom to distribute copies of free software (and charge for this service if you wish); that you receive source code or can get it if you want it; that you can change the software and use pieces of it in new free programs; and that you are informed that you can do these things.

To protect your rights, we need to make restrictions that forbid distributors to deny you these rights or to ask you to surrender these rights. These restrictions translate to certain responsibilities for you if you distribute copies of the library or if you modify it.

For example, if you distribute copies of the library, whether gratis or for a fee, you must give the recipients all the rights that we gave you. You must make sure that they, too, receive or can get the source code. If you link other code with the library, you must provide complete object files to the recipients, so that they can relink them with the library after making changes to the library and recompiling it. And you must show them these terms so they know their rights.

We protect your rights with a two-step method: (1) we copyright the library, and (2) we offer you this license, which gives you legal permission to copy, distribute and/or modify the library.

To protect each distributor, we want to make it very clear that there is no warranty for the free library. Also, if the library is modified by someone else and passed on, the recipients should know that what they have is not the original version, so that the original author's reputation will not be affected by problems that might be introduced by others.

^L

Finally, software patents pose a constant threat to the existence of any free program. We wish to make sure that a company cannot effectively restrict the users of a free program by obtaining a restrictive license from a patent holder. Therefore, we insist that any patent license obtained for a version of the library must be consistent with the full freedom of use specified in this license.

Most GNU software, including some libraries, is covered by the ordinary GNU General Public License. This license, the GNU Lesser General Public License, applies to certain designated libraries, and is quite different from the ordinary General Public License. We use this license for certain libraries in order to permit linking those libraries into non-free programs.

When a program is linked with a library, whether statically or using a shared library, the combination of the two is legally speaking a combined work, a derivative of the original library. The ordinary General Public License therefore permits such linking only if the entire combination fits its criteria of freedom. The Lesser General Public License permits more lax criteria for linking other code with the library.

We call this license the "Lesser" General Public License because it does Less to protect the user's freedom than the ordinary General Public License. It also provides other free software developers Less of an advantage over competing non-free programs. These disadvantages are the reason we use the ordinary General Public License for many libraries. However, the Lesser license provides advantages in certain special circumstances.

For example, on rare occasions, there may be a special need to encourage the widest possible use of a certain library, so that it becomes a de-facto standard. To achieve this, non-free programs must be allowed to use the library. A more frequent case is that a free library does the same job as widely used non-free libraries. In this case, there is little to gain by limiting the free library to free software only, so we use the Lesser General Public License.

In other cases, permission to use a particular library in non-free programs enables a greater number of people to use a large body of free software. For example, permission to use the GNU C Library in non-free programs enables many more people to use the whole GNU operating system, as well as its variant, the GNU/Linux operating system.

Although the Lesser General Public License is Less protective of the users' freedom, it does ensure that the user of a program that is linked with the Library has the freedom and the wherewithal to run that program using a modified version of the Library.

The precise terms and conditions for copying, distribution and modification follow. Pay close attention to the difference between a "work based on the library" and a "work that uses the library". The former contains code derived from the library, whereas the latter must be combined with the library in order to run.

^L

GNU LESSER GENERAL PUBLIC LICENSE TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

0. This License Agreement applies to any software library or other program which contains a notice placed by the copyright holder or other authorized party saying it may be distributed under the terms of this Lesser General Public License (also called "this License"). Each licensee is addressed as "you".

A "library" means a collection of software functions and/or data

prepared so as to be conveniently linked with application programs (which use some of those functions and data) to form executables.

The "Library", below, refers to any such software library or work which has been distributed under these terms. A "work based on the Library" means either the Library or any derivative work under copyright law: that is to say, a work containing the Library or a portion of it, either verbatim or with modifications and/or translated straightforwardly into another language. (Hereinafter, translation is included without limitation in the term "modification".)

"Source code" for a work means the preferred form of the work for making modifications to it. For a library, complete source code means all the source code for all modules it contains, plus any associated interface definition files, plus the scripts used to control compilation and installation of the library.

Activities other than copying, distribution and modification are not covered by this License; they are outside its scope. The act of running a program using the Library is not restricted, and output from such a program is covered only if its contents constitute a work based on the Library (independent of the use of the Library in a tool for writing it). Whether that is true depends on what the Library does and what the program that uses the Library does.

1. You may copy and distribute verbatim copies of the Library's complete source code as you receive it, in any medium, provided that you conspicuously and appropriately publish on each copy an appropriate copyright notice and disclaimer of warranty; keep intact all the notices that refer to this License and to the absence of any warranty; and distribute a copy of this License along with the Library.

You may charge a fee for the physical act of transferring a copy, and you may at your option offer warranty protection in exchange for a fee.

2. You may modify your copy or copies of the Library or any portion of it, thus forming a work based on the Library, and copy and distribute such modifications or work under the terms of Section 1 above, provided that you also meet all of these conditions:

- a) The modified work must itself be a software library.
- b) You must cause the files modified to carry prominent notices

stating that you changed the files and the date of any change.

c) You must cause the whole of the work to be licensed at no charge to all third parties under the terms of this License.

d) If a facility in the modified Library refers to a function or a table of data to be supplied by an application program that uses the facility, other than as an argument passed when the facility is invoked, then you must make a good faith effort to ensure that, in the event an application does not supply such function or table, the facility still operates, and performs whatever part of its purpose remains meaningful.

(For example, a function in a library to compute square roots has a purpose that is entirely well-defined independent of the application. Therefore, Subsection 2d requires that any application-supplied function or table used by this function must be optional: if the application does not supply it, the square root function must still compute square roots.)

These requirements apply to the modified work as a whole. If identifiable sections of that work are not derived from the Library, and can be reasonably considered independent and separate works in themselves, then this License, and its terms, do not apply to those sections when you distribute them as separate works. But when you distribute the same sections as part of a whole which is a work based on the Library, the distribution of the whole must be on the terms of this License, whose permissions for other licensees extend to the entire whole, and thus to each and every part regardless of who wrote it.

Thus, it is not the intent of this section to claim rights or contest your rights to work written entirely by you; rather, the intent is to exercise the right to control the distribution of derivative or collective works based on the Library.

In addition, mere aggregation of another work not based on the Library with the Library (or with a work based on the Library) on a volume of a storage or distribution medium does not bring the other work under the scope of this License.

3. You may opt to apply the terms of the ordinary GNU General Public License instead of this License to a given copy of the Library. To do this, you must alter all the notices that refer to this License, so that they refer to the ordinary GNU General Public License, version 2,

instead of to this License. (If a newer version than version 2 of the ordinary GNU General Public License has appeared, then you can specify that version instead if you wish.) Do not make any other change in these notices.

^L

Once this change is made in a given copy, it is irreversible for that copy, so the ordinary GNU General Public License applies to all subsequent copies and derivative works made from that copy.

This option is useful when you wish to copy part of the code of the Library into a program that is not a library.

4. You may copy and distribute the Library (or a portion or derivative of it, under Section 2) in object code or executable form under the terms of Sections 1 and 2 above provided that you accompany it with the complete corresponding machine-readable source code, which must be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange.

If distribution of object code is made by offering access to copy from a designated place, then offering equivalent access to copy the source code from the same place satisfies the requirement to distribute the source code, even though third parties are not compelled to copy the source along with the object code.

5. A program that contains no derivative of any portion of the Library, but is designed to work with the Library by being compiled or linked with it, is called a "work that uses the Library". Such a work, in isolation, is not a derivative work of the Library, and therefore falls outside the scope of this License.

However, linking a "work that uses the Library" with the Library creates an executable that is a derivative of the Library (because it contains portions of the Library), rather than a "work that uses the library". The executable is therefore covered by this License. Section 6 states terms for distribution of such executables.

When a "work that uses the Library" uses material from a header file that is part of the Library, the object code for the work may be a derivative work of the Library even though the source code is not. Whether this is true is especially significant if the work can be linked without the Library, or if the work is itself a library. The threshold for this to be true is not precisely defined by law.

If such an object file uses only numerical parameters, data structure layouts and accessors, and small macros and small inline

functions (ten lines or less in length), then the use of the object file is unrestricted, regardless of whether it is legally a derivative work. (Executables containing this object code plus portions of the Library will still fall under Section 6.)

Otherwise, if the work is a derivative of the Library, you may distribute

the object code for the work under the terms of Section 6.

Any executables containing that work also fall under Section 6, whether or not they are linked directly with the Library itself.

^L

6. As an exception to the Sections above, you may also combine or link a "work that uses the Library" with the Library to produce a work containing portions of the Library, and distribute that work under terms of your choice, provided that the terms permit modification of the work for the customer's own use and reverse engineering for debugging such modifications.

You must give prominent notice with each copy of the work that the Library is used in it and that the Library and its use are covered by this License. You must supply a copy of this License. If the work during execution displays copyright notices, you must include the copyright notice for the Library among them, as well as a reference directing the user to the copy of this License. Also, you must do one of these things:

a) Accompany the work with the complete corresponding machine-readable source code for the Library including whatever changes were used in the work (which must be distributed under Sections 1 and 2 above); and, if the work is an executable linked with the Library, with the complete machine-readable "work that uses the Library", as object code and/or source code, so that the user can modify the Library and then relink to produce a modified executable containing the modified Library. (It is understood that the user who changes the contents of definitions files in the Library will not necessarily be able to recompile the application to use the modified definitions.)

b) Use a suitable shared library mechanism for linking with the Library. A suitable mechanism is one that (1) uses at run time a copy of the library already present on the user's computer system, rather than copying library functions into the executable, and (2)

will operate properly with a modified version of the library, if the user installs one, as long as the modified version is interface-compatible with the version that the work was made with.

c) Accompany the work with a written offer, valid for at least three years, to give the same user the materials specified in Subsection 6a, above, for a charge no more than the cost of performing this distribution.

d) If distribution of the work is made by offering access to copy from a designated place, offer equivalent access to copy the above specified materials from the same place.

e) Verify that the user has already received a copy of these materials or that you have already sent this user a copy.

For an executable, the required form of the "work that uses the Library" must include any data and utility programs needed for reproducing the executable from it. However, as a special exception, the materials to be distributed need not include anything that is normally distributed (in either source or binary form) with the major components (compiler, kernel, and so on) of the operating system on which the executable runs, unless that component itself accompanies the executable.

It may happen that this requirement contradicts the license restrictions of other proprietary libraries that do not normally accompany the operating system. Such a contradiction means you cannot use both them and the Library together in an executable that you distribute.

^L

7. You may place library facilities that are a work based on the Library side-by-side in a single library together with other library facilities not covered by this License, and distribute such a combined library, provided that the separate distribution of the work based on the Library and of the other library facilities is otherwise permitted, and provided that you do these two things:

a) Accompany the combined library with a copy of the same work based on the Library, uncombined with any other library facilities. This must be distributed under the terms of the Sections above.

b) Give prominent notice with the combined library of the fact that part of it is a work based on the Library, and explaining where to find the accompanying uncombined form of the same work.

8. You may not copy, modify, sublicense, link with, or distribute the Library except as expressly provided under this License. Any attempt otherwise to copy, modify, sublicense, link with, or

distribute the Library is void, and will automatically terminate your rights under this License. However, parties who have received copies, or rights, from you under this License will not have their licenses terminated so long as such parties remain in full compliance.

9. You are not required to accept this License, since you have not signed it. However, nothing else grants you permission to modify or distribute the Library or its derivative works. These actions are prohibited

by law if you do not accept this License. Therefore, by modifying or distributing the Library (or any work based on the Library), you indicate your acceptance of this License to do so, and all its terms and conditions for copying, distributing or modifying the Library or works based on it.

10. Each time you redistribute the Library (or any work based on the Library), the recipient automatically receives a license from the original licensor to copy, distribute, link with or modify the Library subject to these terms and conditions. You may not impose any further restrictions on the recipients' exercise of the rights granted herein. You are not responsible for enforcing compliance by third parties with this License.

^L

11. If, as a consequence of a court judgment or allegation of patent infringement or for any other reason (not limited to patent issues), conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot distribute so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not distribute the Library at all. For example, if a patent license would not permit royalty-free redistribution of the Library by all those who receive copies directly or indirectly through you, then the only way you could satisfy both it and this License would be to refrain entirely from distribution of the Library.

If any portion of this section is held invalid or unenforceable under any particular circumstance, the balance of the section is intended to apply, and the section as a whole is intended to apply in other circumstances.

It is not the purpose of this section to induce you to infringe any patents or other property right claims or to contest validity of any such claims; this section has the sole purpose of protecting the integrity of the free software distribution system which is implemented by public license practices. Many people have made

generous contributions to the wide range of software distributed through that system in reliance on consistent application of that system; it is up to the author/donor to decide if he or she is willing to distribute software through any other system and a licensee cannot impose that choice.

This section is intended to make thoroughly clear what is believed to be a consequence of the rest of this License.

12. If the distribution and/or use of the Library is restricted in certain countries either by patents or by copyrighted interfaces, the original copyright holder who places the Library under this License may add an explicit geographical distribution limitation excluding those countries, so that distribution is permitted only in or among countries not thus excluded. In such case, this License incorporates the limitation as if written in the body of this License.

13. The Free Software Foundation may publish revised and/or new versions of the Lesser General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Library specifies a version number of this License which applies to it and "any later version", you have the option of following the terms and conditions either of that version or of any later version published by the Free Software Foundation. If the Library does not specify a license version number, you may choose any version ever published by the Free Software Foundation.

^L

14. If you wish to incorporate parts of the Library into other free programs whose distribution conditions are incompatible with these, write to the author to ask for permission. For software which is copyrighted by the Free Software Foundation, write to the Free Software Foundation; we sometimes make exceptions for this. Our decision will be guided by the two goals of preserving the free status of all derivatives of our free software and of promoting the sharing and reuse of software generally.

NO WARRANTY

15. BECAUSE THE LIBRARY IS LICENSED FREE OF CHARGE, THERE IS NO WARRANTY FOR THE LIBRARY, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE LIBRARY "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE

IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE LIBRARY IS WITH YOU. SHOULD THE LIBRARY PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

16. IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY AND/OR REDISTRIBUTE THE LIBRARY AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE LIBRARY (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE LIBRARY TO OPERATE WITH ANY OTHER SOFTWARE), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

END OF TERMS AND CONDITIONS

^L

How to Apply These Terms to Your New Libraries

If you develop a new library, and you want it to be of the greatest possible use to the public, we recommend making it free software that everyone can redistribute and change. You can do so by permitting redistribution under these terms (or, alternatively, under the terms of the ordinary General Public License).

To apply these terms, attach the following notices to the library. It is safest to attach them to the start of each source file to most effectively convey the exclusion of warranty; and each file should have at least the "copyright" line and a pointer to where the full notice is found.

<one line to give the library's name and a brief idea of what it does.>

Copyright (C) <year> <name of author>

This library is free software; you can redistribute it and/or modify it under the terms of the GNU Lesser General Public License as published by the Free Software Foundation; either version 2 of the License, or (at your option) any later version.

This library is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU Lesser General Public License for more details.

You should have received a copy of the GNU Lesser General Public License along with this library; if not, write to the Free Software Foundation, Inc., 51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA

Also add information on how to contact you by electronic and paper mail.

You should also get your employer (if you work as a programmer) or your school, if any, to sign a "copyright disclaimer" for the library, if necessary. Here is a sample; alter the names:

Yoyodyne, Inc., hereby disclaims all copyright interest in the library `Frob' (a library for tweaking knobs) written by James Random Hacker.

<signature of Ty Coon>, 1 April 1990
Ty Coon, President of Vice

That's all there is to it!

GNU GENERAL PUBLIC LICENSE
Version 2, June 1991

Copyright (C) 1989, 1991 Free Software Foundation, Inc.
59 Temple Place, Suite 330, Boston, MA 02111-1307 USA
Everyone is permitted to copy and distribute verbatim copies of this license document, but changing it is not allowed.

Preamble

The licenses for most software are designed to take away your freedom to share and change it. By contrast, the GNU General Public License is intended to guarantee your freedom to share and change free software--to make sure the software is free for all its users. This General Public License applies to most of the Free Software Foundation's software and to any other program whose authors commit to using it. (Some other Free Software Foundation software is covered by the GNU Library General Public License instead.) You can apply it to your programs, too.

When we speak of free software, we are referring to freedom, not price. Our General Public Licenses are designed to make sure that you have the freedom to distribute copies of free software (and charge for this service if you wish), that you receive source code or can get it if you want it, that you can change the software or use pieces of it

in new free programs; and that you know you can do these things.

To protect your rights, we need to make restrictions that forbid anyone to deny you these rights or to ask you to surrender the rights. These restrictions translate to certain responsibilities for you if you distribute copies of the software, or if you modify it.

For example, if you distribute copies of such a program, whether gratis or for a fee, you must give the recipients all the rights that you have. You must make sure that they, too, receive or can get the source code. And you must show them these terms so they know their rights.

We protect your rights with two steps: (1) copyright the software, and (2) offer you this license which gives you legal permission to copy, distribute and/or modify the software.

Also, for each author's protection and ours, we want to make certain that everyone understands that there is no warranty for this free software. If the software is modified by someone else and passed on, we want its recipients to know that what they have is not the original, so that any problems introduced by others will not reflect on the original authors' reputations.

Finally, any free program is threatened constantly by software patents. We wish to avoid the danger that redistributors of a free program will individually obtain patent licenses, in effect making the program proprietary. To prevent this, we have made it clear that any patent must be licensed for everyone's free use or not licensed at all.

The precise terms and conditions for copying, distribution and modification follow.

GNU GENERAL PUBLIC LICENSE TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

0. This License applies to any program or other work which contains a notice placed by the copyright holder saying it may be distributed under the terms of this General Public License. The "Program", below, refers to any such program or work, and a "work based on the Program" means either the Program or any derivative work under copyright law: that is to say, a work containing the Program or a portion of it, either verbatim or with modifications and/or translated into another language. (Hereinafter, translation is included without limitation in the term "modification".) Each licensee is addressed as "you".

Activities other than copying, distribution and modification are not covered by this License; they are outside its scope. The act of running the Program is not restricted, and the output from the Program is covered only if its contents constitute a work based on the Program (independent of having been made by running the Program). Whether that is true depends on what the Program does.

1. You may copy and distribute verbatim copies of the Program's source code as you receive it, in any medium, provided that you conspicuously and appropriately publish on each copy an appropriate copyright notice and disclaimer of warranty; keep intact all the notices that refer to this License and to the absence of any warranty; and give any other recipients of the Program a copy of this License along with the Program.

You may charge a fee for the physical act of transferring a copy, and you may at your option offer warranty protection in exchange for a fee.

2. You may modify your copy or copies of the Program or any portion of it, thus forming a work based on the Program, and copy and distribute such modifications or work under the terms of Section 1 above, provided that you also meet all of these conditions:

a) You must cause the modified files to carry prominent notices stating that you changed the files and the date of any change.

b) You must cause any work that you distribute or publish, that in whole or in part contains or is derived from the Program or any part thereof, to be licensed as a whole at no charge to all third parties under the terms of this License.

c) If the modified program normally reads commands interactively when run, you must cause it, when started running for such interactive use in the most ordinary way, to print or display an announcement including an appropriate copyright notice and a notice that there is no warranty (or else, saying that you provide a warranty) and that users may redistribute the program under these conditions, and telling the user how to view a copy of this License. (Exception: if the Program itself is interactive but does not normally print such an announcement, your work based on the Program is not required to print an announcement.)

These requirements apply to the modified work as a whole. If identifiable sections of that work are not derived from the Program, and can be reasonably considered

independent and separate works in themselves, then this License, and its terms, do not apply to those sections when you distribute them as separate works. But when you distribute the same sections as part of a whole which is a work based on the Program, the distribution of the whole must be on the terms of this License, whose permissions for other licensees extend to the entire whole, and thus to each and every part regardless of who wrote it.

Thus, it is not the intent of this section to claim rights or contest your rights to work written entirely by you; rather, the intent is to exercise the right to control the distribution of derivative or collective works based on the Program.

In addition, mere aggregation of another work not based on the Program with the Program (or with a work based on the Program) on a volume of a storage or distribution medium does not bring the other work under the scope of this License.

3. You may copy and distribute the Program (or a work based on it, under Section 2) in object code or executable form under the terms of Sections 1 and 2 above provided that you also do one of the following:

a) Accompany it with the complete corresponding machine-readable source code, which must be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange; or,

b) Accompany it with a written offer, valid for at least three years, to give any third party, for a charge no more than your cost of physically performing source distribution, a complete machine-readable copy of the corresponding source code, to be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange; or,

c) Accompany it with the information you received as to the offer to distribute corresponding source code. (This alternative is allowed only for noncommercial distribution and only if you received the program in object code or executable form with such an offer, in accord with Subsection b above.)

The source code for a work means the preferred form of the work for making modifications to it. For an executable work, complete source code means all the source code for all modules it contains, plus any associated interface definition files, plus the scripts used to control compilation and installation of the executable. However, as a special exception, the source code distributed need not include anything that is normally distributed (in either source or binary

form) with the major components (compiler, kernel, and so on) of the operating system on which the executable runs, unless that component itself accompanies the executable.

If distribution of executable or object code is made by offering access to copy from a designated place, then offering equivalent access to copy the source code from the same place counts as distribution of the source code, even though third parties are not compelled to copy the source along with the object code.

4. You may not copy, modify, sublicense, or distribute the Program except as expressly provided under this License. Any attempt otherwise to copy, modify, sublicense or distribute the Program is void, and will automatically terminate your rights under this License. However, parties who have received copies, or rights, from you under this License will not have their licenses terminated so long as such parties remain in full compliance.

5. You are not required to accept this License, since you have not signed it. However, nothing else grants you permission to modify or distribute the Program or its derivative works. These actions are prohibited by law if you do not accept this License. Therefore, by modifying or distributing the Program (or any work based on the Program), you indicate your acceptance of this License to do so, and all its terms and conditions for copying, distributing or modifying the Program or works based on it.

6. Each time you redistribute the Program (or any work based on the Program), the recipient automatically receives a license from the original licensor to copy, distribute or modify the Program subject to these terms and conditions. You may not impose any further restrictions on the recipients' exercise of the rights granted herein. You are not responsible for enforcing compliance by third parties to this License.

7. If, as a consequence of a court judgment or allegation of patent infringement or for any other reason (not limited to patent issues), conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot distribute so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not distribute the Program at all. For example, if a patent license would not permit royalty-free redistribution of the Program by all those who receive copies directly or indirectly through you, then

the only way you could satisfy both it and this License would be to refrain entirely from distribution of the Program.

If any portion of this section is held invalid or unenforceable under any particular circumstance, the balance of the section is intended to apply and the section as a whole is intended to apply in other circumstances.

It is not the purpose of this section to induce you to infringe any patents or other property right claims or to contest validity of any such claims; this section has the sole purpose of protecting the integrity of the free software distribution system, which is implemented by public license practices. Many people have made generous contributions to the wide range of software distributed through that system in reliance on consistent application of that system; it is up to the author/donor to decide if he or she is willing to distribute software through any other system and a licensee cannot impose that choice.

This section is intended to make thoroughly clear what is believed to be a consequence of the rest of this License.

8. If the distribution and/or use of the Program is restricted in certain countries either by patents or by copyrighted interfaces, the original copyright holder who places the Program under this License may add an explicit geographical distribution limitation excluding those countries, so that distribution is permitted only in or among countries not thus excluded. In such case, this License incorporates the limitation as if written in the body of this License.

9. The Free Software Foundation may publish revised and/or new versions of the General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Program specifies a version number of this License which applies to it and "any later version", you have the option of following the terms and conditions either of that version or of any later version published by the Free Software Foundation. If the Program does not specify a version number of this License, you may choose any version ever published by the Free Software Foundation.

10. If you wish to incorporate parts of the Program into other free programs whose distribution conditions are different, write to the author to ask for permission. For software which is copyrighted by the Free

Software Foundation, write to the Free Software Foundation; we sometimes make exceptions for this. Our decision will be guided by the two goals of preserving the free status of all derivatives of our free software and of promoting the sharing and reuse of software generally.

NO WARRANTY

11. BECAUSE THE PROGRAM IS LICENSED FREE OF CHARGE, THERE IS NO WARRANTY FOR THE PROGRAM, TO THE EXTENT PERMITTED BY APPLICABLE LAW.

EXCEPT WHEN

OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE PROGRAM "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE PROGRAM IS WITH YOU. SHOULD THE PROGRAM PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

12. IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY AND/OR REDISTRIBUTE THE PROGRAM AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE PROGRAM (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE PROGRAM TO OPERATE WITH ANY OTHER PROGRAMS), EVEN

IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Programs

If you develop a new program, and you want it to be of the greatest possible use to the public, the best way to achieve this is to make it free software which everyone can redistribute and change under these terms.

To do so, attach the following notices to the program. It is safest to attach them to the start of each source file to most effectively convey the exclusion of warranty; and each file should have at least the "copyright" line and a pointer to where the full notice is found.

<one line to give the program's name and a brief idea of what it does.>

Copyright (C) <year> <name of author>

This program is free software; you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation; either version 2 of the License,

or

(at your option) any later version.

This program is distributed in the hope that it will be useful,
but WITHOUT ANY WARRANTY; without even the implied warranty of
MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
GNU General Public License for more details.

You should have received a copy of the GNU General Public License
along with this program; if not, write to the Free Software
Foundation, Inc., 59 Temple Place, Suite 330, Boston, MA 02111-1307 USA

Also add information on how to contact you by electronic and paper mail.

If the program is interactive, make it output a short notice like this
when it starts in an interactive mode:

```
Gnomovision version 69, Copyright (C) year name of author
Gnomovision comes with ABSOLUTELY NO WARRANTY; for details type `show w'.
This is free software, and you are welcome to redistribute it
under certain conditions; type `show c' for details.
```

The hypothetical commands `show w' and
`show c' should show the appropriate
parts of the General Public License. Of course, the commands you use may
be called something other than `show w' and `show c'; they could even be
mouse-clicks or menu items--whatever suits your program.

You should also get your employer (if you work as a programmer) or your
school, if any, to sign a "copyright disclaimer" for the program, if
necessary. Here is a sample; alter the names:

```
Yoyodyne, Inc., hereby disclaims all copyright interest in the program
`Gnomovision' (which makes passes at compilers) written by James Hacker.
```

```
<signature of Ty Coon>, 1 April 1989
```

```
Ty Coon, President of Vice
```

This General Public License does not permit incorporating your program into
proprietary programs. If your program is a subroutine library, you may
consider it more useful to permit linking proprietary applications with the
library. If this is what you want to do, use the GNU Library General
Public License instead of this License.

1.25 ncurses 6.1-1ubuntu1.18.04

1.25.1 Available under license :

Upstream source <https://invisible-island.net/ncurses/ncurses-examples.html>

Current ncurses maintainer: Thomas Dickey <dickey@invisible-island.net>

Files: *

Copyright: 1998-2017,2018 Free Software Foundation, Inc.

Licence: X11

Files: aclocal.m4 package

Copyright: 2010-2017,2018 by Thomas E. Dickey

Licence: X11

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, distribute with modifications, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE ABOVE COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

Except as contained in this notice, the name(s) of the above copyright holders shall not be used in advertising or otherwise to promote the sale, use or other dealings in this Software without prior written authorization.

Files: install-sh

Copyright: 1994 X Consortium

Licence: X11

Permission is hereby granted, free of charge, to any person obtaining a copy

of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE X CONSORTIUM BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

Except as contained in this notice, the name of the X Consortium shall not be used in advertising or otherwise to promote the sale, use or other dealings in this Software without prior written authorization from the X Consortium.

FSF changes to this file are in the public domain.

Calling this script `install-sh` is preferred over `install.sh`, to prevent `'make'` implicit rules from creating a file called `install` from it when there is no `Makefile`.

This script is compatible with the BSD `install` script, but was written from scratch. It can only install one file at a time, a restriction shared with many OS's `install` programs.

On Debian systems, the complete text of the GNU General Public License can be found in `'/usr/share/common-licenses/GPL-2'`

-- vile: txtmode file-encoding=utf-8
Upstream source <https://invisible-island.net/ncurses/ncurses.html>
This package is used for testing builds of `ncurses`.

Current `ncurses` maintainer: Thomas Dickey <dickey@invisible-island.net>

Files: *
Copyright: 1998-2017,2018 Free Software Foundation, Inc.
Licence: X11

Files: `aclocal.m4` package

Copyright: 1996-2017,2018 by Thomas E. Dickey

Licence: X11

Files: doc/html/NCURSES-Programming-HOWTO.html

Copyright: 2001 by Pradeep Padala

Licence: X11

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, distribute with modifications, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE ABOVE COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

Except as contained in this notice, the name(s) of the above copyright holders shall not be used in advertising or otherwise to promote the sale, use or other dealings in this Software without prior written authorization.

Files: install-sh

Copyright: 1994

X Consortium

Licence: X11

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE X CONSORTIUM BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

Except as contained in this notice, the name of the X Consortium shall not be used in advertising or otherwise to promote the sale, use or other dealings in this Software without prior written authorization from the X Consortium.

Files: progs/tset.c ncurses/tinfo/read_termcap.c

Copyright: 1980,1991,1992,1993 The Regents of the University of California.

License: BSD

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

1. Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.
2. Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.
3. Neither the name of the University nor the names of its contributors may be used to endorse or promote products derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE REGENTS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE REGENTS OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

-- vile: txtmode file-encoding=utf-8

Upstream source <https://invisible-island.net/ncurses/ncurses-examples.html>

Current ncurses maintainer: Thomas Dickey <dickey@invisible-island.net>

Files: *

Copyright: 1998-2017,2018 Free Software Foundation, Inc.

Licence: X11

Files: aclocal.m4 package

Copyright: 2003-2017,2018 by Thomas E. Dickey

Licence: X11

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, distribute with modifications, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE ABOVE COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

Except as contained in this notice, the name(s) of the above copyright holders shall not be used in advertising or otherwise to promote the sale, use or other dealings in this Software without prior written authorization.

Files: install-sh

Copyright: 1994 X Consortium

Licence: X11

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE X CONSORTIUM BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

Except as contained in this notice, the name of the X Consortium shall not be used in advertising or otherwise to promote the sale, use or other dealings in this Software without prior written authorization from the X Consortium.

FSF changes to this file are in the public domain.

Calling this script `install-sh` is preferred over `install.sh`, to prevent `make` implicit rules from creating a file called `install` from it when there is no `Makefile`.

This script is compatible with the BSD `install` script, but was written from scratch. It can only install one file at a time, a restriction shared with many OS's `install` programs.

On Debian systems, the complete text of the GNU General Public License can be found in `/usr/share/common-licenses/GPL-2`

-- vile: txtmode file-encoding=utf-8

Copyright (c) 1998-2017,2018 Free Software Foundation, Inc.

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, distribute with modifications, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE ABOVE COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR

OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR
THE USE OR OTHER DEALINGS IN THE SOFTWARE.

Except as contained in this notice, the name(s) of the above copyright holders shall not be used in advertising or otherwise to promote the sale, use or other dealings in this Software without prior written authorization.

```
-- vile:txtmode fc=72
-- $Id: COPYING,v 1.6 2018/01/01 12:00:00 tom Exp $
```

This is the Debian prepackaged version of the ncurses library and terminfo utilities. ncurses/terminfo was originally written by Pavel Curtis and Zeyd M. Ben-Halim <zmbenhal@netcom.com>, and is currently held by the Free Software Foundation.

This package was put together by Vaidhyanathan G Mayilrangam <vaidhy@debian.org> and Joel Klecker <espy@debian.org>, using sources obtained from <ftp://ftp.gnu.org/gnu/ncurses/ncurses-5.0.tar.gz>. Current versions of the ncurses sources are found at <ftp://invisible-island.net/ncurses/>.

It is based somewhat on work done by Bruce Perens <Bruce@Pixar.com>, David Engel <david@elo.ods.com>. Michael Alan Dorman <mdorman@debian.org>, Richard Braakman <dark@xs4all.nl>, James Troup <jjttrou@comp.brad.ac.uk>, J.H.M. Dassen (Ray) <jdassen@wi.LeidenUniv.nl>, and Galen Hazelwood <galenh@micron.net> over various years.

Copyright (c) 1998-2018 Free Software Foundation, Inc.
Copyright 2001 by Pradeep Padala

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, distribute with modifications, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT.

IN NO EVENT SHALL THE ABOVE COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

Except

as contained in this notice, the name(s) of the above copyright holders shall not be used in advertising or otherwise to promote the sale, use or other dealings in this Software without prior written authorization.

Copyright (C) 1994 X Consortium

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE X CONSORTIUM BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

Except as contained in this notice, the name of the X Consortium shall not be used in advertising or otherwise to promote the sale, use or other dealings in this Software without prior written authorization from the X Consortium.

Copyright (c) 1980, 1991, 1992, 1993

The Regents of the University of California. All rights reserved.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

1. Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.
2. Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following

disclaimer in the documentation and/or other materials provided with the distribution.

3. Neither the name of the University nor the names of its contributors may be used to endorse or promote products derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE REGENTS AND CONTRIBUTORS ``AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE REGENTS OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

Copyright 1996-2018 by Thomas E. Dickey

All Rights Reserved

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE ABOVE LISTED COPYRIGHT HOLDER(S) BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

Except as contained in this notice, the name(s) of the above copyright holders shall not be used in advertising or otherwise to promote the sale, use or other dealings in this Software without prior written authorization.

1.26 acl 2.2.52-3build1

1.26.1 Available under license :

This package was debianized by Nathan Scott nathans@debian.org on Tue, 26 Feb 2002 13:25:26 +1100

It can be downloaded from <http://mirror.its.uidaho.edu/pub/savannah/acl/>

Copyright:

Copyright (C) 2001 Andreas Gruenbacher.

Copyright (C) 2001-2002 Silicon Graphics, Inc. All Rights Reserved.

You are free to distribute this software under Version 2.1 of the GNU Lesser General Public License.

On Debian systems, refer to `/usr/share/common-licenses/LGPL-2.1` for the complete text of the GNU Lesser General Public License.

Certain components (as annotated in the source) are licensed under the terms of the GNU General Public License.

On Debian systems, the complete text of the GNU General Public License can be found in `/usr/share/common-licenses/GPL` file.

This package was debianized by Nathan Scott nathans@debian.org on Tue, 26 Feb 2002 13:25:26 +1100

It can be downloaded from <ftp://acl.bestbits.at/>

Copyright:

Copyright (C) 2001 Andreas Gruenbacher.

Copyright (C) 2001-2002 Silicon Graphics, Inc. All Rights Reserved.

You are free to distribute this software under Version 2.1 of the GNU Lesser General Public License.

On Debian systems, refer to `/usr/share/common-licenses/LGPL-2.1` for the complete text of the GNU Lesser General Public License.

Certain components (as annotated in the source) are licensed under the terms of the GNU General Public License.

On Debian systems, the complete text of the GNU General Public License can be found in `/usr/share/common-licenses/GPL` file.

Most components of the "acl" package are licensed under Version 2.1 of the GNU Lesser General Public License (see `COPYING.LGPL`).

Some components (as annotated in the source) are licensed under Version 2 of the GNU General Public License (see below),

GNU GENERAL PUBLIC LICENSE

Version 2, June 1991

Copyright (C) 1989, 1991 Free Software Foundation, Inc.,
51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA
Everyone is permitted to copy and distribute verbatim copies
of this license document, but changing it is not allowed.

Preamble

The licenses for most software are designed to take away your freedom to share and change it. By contrast, the GNU General Public License is intended to guarantee your freedom to share and change free software--to make sure the software is free for all its users. This General Public License applies to most of the Free Software Foundation's software and to any other program whose authors commit to using it. (Some other Free Software Foundation software is covered by the GNU Lesser General Public License instead.) You can apply it to your programs, too.

When we speak of free software, we are referring to freedom, not price. Our General Public Licenses are designed to make sure that you have the freedom to distribute copies of free software (and charge for this service if you wish), that you receive source code or can get it if you want it, that you can change the software or use pieces of it in new free programs; and that you know you can do these things.

To protect your rights, we need to make restrictions that forbid anyone to deny you these rights or to ask you to surrender the rights. These restrictions translate to certain responsibilities for you if you distribute copies of the software, or if you modify it.

For example, if you distribute copies of such a program, whether gratis or for a fee, you must give the recipients all the rights that you have. You must make sure that they, too, receive or can get the source code. And you must show them these terms so they know their rights.

We protect your rights with two steps: (1) copyright the software, and (2) offer you this license which gives you legal permission to copy, distribute and/or modify the software.

Also, for each author's protection and ours, we want to make certain

that everyone understands that there is no warranty for this free software. If the software is modified by someone else and passed on, we want its recipients to know that what they have is not the original, so that any problems introduced by others will not reflect on the original authors' reputations.

Finally, any free program is threatened constantly by software patents. We wish to avoid the danger that redistributors of a free program will individually obtain patent licenses, in effect making the program proprietary. To prevent this, we have made it clear that any patent must be licensed for everyone's free use or not licensed at all.

The precise terms and conditions for copying, distribution and modification follow.

GNU GENERAL PUBLIC LICENSE TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

0. This License applies to any program or other work which contains a notice placed by the copyright holder saying it may be distributed under the terms of this General Public License. The "Program", below, refers to any such program or work, and a "work based on the Program" means either the Program or any derivative work under copyright law: that is to say, a work containing the Program or a portion of it, either verbatim or with modifications and/or translated into another language. (Hereinafter, translation is included without limitation in the term "modification".) Each licensee is addressed as "you".

Activities other than copying, distribution and modification are not covered by this License; they are outside its scope. The act of running the Program is not restricted, and the output from the Program is covered only if its contents constitute a work based on the Program (independent of having been made by running the Program). Whether that is true depends on what the Program does.

1. You may copy and distribute verbatim copies of the Program's source code as you receive it, in any medium, provided that you conspicuously and appropriately publish on each copy an appropriate copyright notice and disclaimer of warranty; keep intact all the notices that refer to this License and to the absence of any warranty; and give any other recipients of the Program a copy of this License along with the Program.

You may charge a fee for the physical act of transferring a copy, and you may at your option offer warranty protection in exchange for a fee.

2. You may modify your copy or copies of the Program or any portion of it, thus forming a work based on the Program, and copy and distribute such modifications or work under the terms of Section 1 above, provided that you also meet all of these conditions:

- a) You must cause the modified files to carry prominent notices stating that you changed the files and the date of any change.
- b) You must cause any work that you distribute or publish, that in whole or in part contains or is derived from the Program or any part thereof, to be licensed as a whole at no charge to all third parties under the terms of this License.
- c) If the modified program normally reads commands interactively when run, you must cause it, when started running for such interactive use in the most ordinary way, to print or display an announcement including an appropriate copyright notice and a notice that there is no warranty (or else, saying that you provide a warranty) and that users may redistribute the program under these conditions, and telling the user how to view a copy of this License. (Exception: if the Program itself is interactive but does not normally print such an announcement, your work based on the Program is not required to print an announcement.)

These requirements apply to the modified work as a whole. If identifiable sections of that work are not derived from the Program, and can be reasonably considered independent and separate works in themselves, then this License, and its terms, do not apply to those sections when you distribute them as separate works. But when you distribute the same sections as part of a whole which is a work based on the Program, the distribution of the whole must be on the terms of this License, whose permissions for other licensees extend to the entire whole, and thus to each and every part regardless of who wrote it.

Thus, it is not the intent of this section to claim rights or contest your rights to work written entirely by you; rather, the intent is to exercise the right to control the distribution of derivative or collective works based on the Program.

In addition, mere aggregation of another work not based on the Program with the Program (or with a work based on the Program) on a volume of a storage or distribution medium does not bring the other work under the scope of this License.

3. You may copy and distribute the Program (or a work based on it,

under Section 2) in object code or executable form under the terms of Sections 1 and 2 above provided that you also do one of the following:

- a) Accompany it with the complete corresponding machine-readable source code, which must be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange; or,
- b) Accompany it with a written offer, valid for at least three years, to give any third party, for a charge no more than your cost of physically performing source distribution, a complete machine-readable copy of the corresponding source code, to be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange; or,
- c) Accompany it with the information you received as to the offer to distribute corresponding source code. (This alternative is allowed only for noncommercial distribution and only if you received the program in object code or executable form with such an offer, in accord with Subsection b above.)

The source code for a work means the preferred form of the work for making modifications to it. For an executable work, complete source code means all the source code for all modules it contains, plus any associated interface definition files, plus the scripts used to control compilation and installation of the executable. However, as a special exception, the source code distributed need not include anything that is normally distributed (in either source or binary form) with the major components (compiler, kernel, and so on) of the operating system on which the executable runs, unless that component itself accompanies the executable.

If distribution of executable or object code is made by offering access to copy from a designated place, then offering equivalent access to copy the source code from the same place counts as distribution of the source code, even though third parties are not compelled to copy the source along with the object code.

4. You may not copy, modify, sublicense, or distribute the Program except as expressly provided under this License. Any attempt otherwise to copy, modify, sublicense or distribute the Program is void, and will automatically terminate your rights under this License. However, parties who have received copies, or rights, from you under this License will not have their licenses terminated so long as such parties remain in full compliance.

5. You are not required to accept this License, since you have not

signed it. However, nothing else grants you permission to modify or distribute the Program or its derivative works. These actions are prohibited by law if you do not accept this License. Therefore, by modifying or distributing the Program (or any work based on the Program), you indicate your acceptance of this License to do so, and all its terms and conditions for copying, distributing or modifying the Program or works based on it.

6. Each time you redistribute the Program (or any work based on the Program), the recipient automatically receives a license from the original licensor to copy, distribute or modify the Program subject to these terms and conditions. You may not impose any further restrictions on the recipients' exercise of the rights granted herein. You are not responsible for enforcing compliance by third parties to this License.

7. If, as a consequence of a court judgment or allegation of patent infringement or for any other reason (not limited to patent issues), conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot distribute so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not distribute the Program at all. For example, if a patent license would not permit royalty-free redistribution of the Program by all those who receive copies directly or indirectly through you, then the only way you could satisfy both it and this License would be to refrain entirely from distribution of the Program.

If any portion of this section is held invalid or unenforceable under any particular circumstance, the balance of the section is intended to apply and the section as a whole is intended to apply in other circumstances.

It is not the purpose of this section to induce you to infringe any patents or other property right claims or to contest validity of any such claims; this section has the sole purpose of protecting the integrity of the free software distribution system, which is implemented by public license practices. Many people have made generous contributions to the wide range of software distributed through that system in reliance on consistent application of that system; it is up to the author/donor to decide if he or she is willing to distribute software through any other system and a licensee cannot impose that choice.

This section is intended to make thoroughly clear what is believed to be a consequence of the rest of this License.

8. If the distribution and/or use of the Program is restricted in certain countries either by patents or by copyrighted interfaces, the original copyright holder who places the Program under this License may add an explicit geographical distribution limitation excluding those countries, so that distribution is permitted only in or among countries not thus excluded. In such case, this License incorporates the limitation as if written in the body of this License.

9. The Free Software Foundation may publish revised and/or new versions of the General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Program specifies a version number of this License which applies to it and "any later version", you have the option of following the terms and conditions either of that version or of any later version published by the Free Software Foundation. If the Program does not specify a version number of this License, you may choose any version ever published by the Free Software Foundation.

10. If you wish to incorporate parts of the Program into other free programs whose distribution conditions are different, write to the author to ask for permission. For software which is copyrighted by the Free Software Foundation, write to the Free Software Foundation; we sometimes make exceptions for this. Our decision will be guided by the two goals of preserving the free status of all derivatives of our free software and of promoting the sharing and reuse of software generally.

NO WARRANTY

11. BECAUSE THE PROGRAM IS LICENSED FREE OF CHARGE, THERE IS NO WARRANTY FOR THE PROGRAM, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE PROGRAM "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE PROGRAM IS WITH YOU. SHOULD THE PROGRAM PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

12. IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY AND/OR

REDISTRIBUTE THE PROGRAM AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE PROGRAM (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE PROGRAM TO OPERATE WITH ANY OTHER PROGRAMS), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Programs

If you develop a new program, and you want it to be of the greatest possible use to the public, the best way to achieve this is to make it free software which everyone can redistribute and change under these terms.

To do so, attach the following notices to the program. It is safest to attach them to the start of each source file to most effectively convey the exclusion of warranty; and each file should have at least the "copyright" line and a pointer to where the full notice is found.

```
<one  
line to give the program's name and a brief idea of what it does.>  
Copyright (C) <year> <name of author>
```

This program is free software; you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation; either version 2 of the License, or (at your option) any later version.

This program is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details.

You should have received a copy of the GNU General Public License along with this program; if not, write to the Free Software Foundation, Inc., 51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA.

Also add information on how to contact you by electronic and paper mail.

If the program is interactive, make it output a short notice like this when it starts in an interactive mode:

```
Gnomovision version 69, Copyright (C) year name of author  
Gnomovision comes with ABSOLUTELY NO WARRANTY; for details type `show w'.
```

This is free software, and you are welcome to redistribute it under certain conditions; type `show c' for details.

The hypothetical commands `show w' and `show c' should show the appropriate parts of the General Public License. Of course, the commands you use may be called something other than `show w' and `show c'; they could even be mouse-clicks or menu items--whatever suits your program.

You should also get your employer (if you work as a programmer) or your school, if any, to sign a "copyright disclaimer" for the program, if necessary. Here is a sample; alter the names:

Yoyodyne, Inc., hereby disclaims all copyright interest in the program `Gnomovision' (which makes passes at compilers) written by James Hacker.

<signature of Ty Coon>, 1 April 1989
Ty Coon, President of Vice

This General Public License does not permit incorporating your program into proprietary programs. If your program is a subroutine library, you may consider it more useful to permit linking proprietary applications with the library. If this is what you want to do, use the GNU Lesser General Public License instead of this License. Most components of the "acl" package are licensed under Version 2.1 of the GNU Lesser General Public License (see below). below.

Some components (as annotated in the source) are licensed under Version 2 of the GNU General Public License (see COPYING).

GNU LESSER GENERAL PUBLIC LICENSE

Version 2.1, February 1999

Copyright (C) 1991, 1999 Free Software Foundation, Inc.
51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA
Everyone is permitted to copy and distribute verbatim copies of this license document, but changing it is not allowed.

[This is the first released version of the Lesser GPL. It also counts as the successor of the GNU Library Public License, version 2, hence the version number 2.1.]

Preamble

The licenses for most software are designed to take away your

freedom to share and change it. By contrast, the GNU General Public Licenses are intended to guarantee your freedom to share and change free software--to make sure the software is free for all its users.

This license, the Lesser General Public License, applies to some specially designated software packages--typically libraries--of the Free Software Foundation and other authors who decide to use it. You can use it too, but we suggest you first think carefully about whether this license or the ordinary General Public License is the better strategy to use in any particular case, based on the explanations below.

When we speak of free software, we are referring to freedom of use, not price. Our General Public Licenses are designed to make sure that you have the freedom to distribute copies of free software (and charge for this service if you wish); that you receive source code or can get it if you want it; that you can change the software and use pieces of it in new free programs; and that you are informed that you can do these things.

To protect your rights, we need to make restrictions that forbid distributors to deny you these rights or to ask you to surrender these rights. These restrictions translate to certain responsibilities for you if you distribute copies of the library or if you modify it.

For example, if you distribute copies of the library, whether gratis or for a fee, you must give the recipients all the rights that we gave you. You must make sure that they, too, receive or can get the source code. If you link other code with the library, you must provide complete object files to the recipients, so that they can relink them with the library after making changes to the library and recompiling it. And you must show them these terms so they know their rights.

We protect your rights with a two-step method: (1) we copyright the library, and (2) we offer you this license, which gives you legal permission to copy, distribute and/or modify the library.

To protect each distributor, we want to make it very clear that there is no warranty for the free library. Also, if the library is modified by someone else and passed on, the recipients should know that what they have is not the original version, so that the original author's reputation will not be affected by problems that might be introduced by others.

Finally, software patents pose a constant threat to the existence of any free program. We wish to make sure that a company cannot

effectively restrict the users of a free program by obtaining a restrictive license from a patent holder. Therefore, we insist that any patent license obtained for a version of the library must be consistent with the full freedom of use specified in this license.

Most GNU software, including some libraries, is covered by the ordinary GNU General Public License. This license, the GNU Lesser General Public License, applies to certain designated libraries, and is quite different from the ordinary General Public License. We use this license for certain libraries in order to permit linking those libraries into non-free programs.

When a program is linked with a library, whether statically or using a shared library, the combination of the two is legally speaking a combined work, a derivative of the original library. The ordinary General Public License therefore permits such linking only if the entire combination fits its criteria of freedom. The Lesser General Public License permits more lax criteria for linking other code with the library.

We call this license the "Lesser" General Public License because it does Less to protect the user's freedom than the ordinary General Public License. It also provides other free software developers Less of an advantage over competing non-free programs. These disadvantages are the reason we use the ordinary General Public License for many libraries. However, the Lesser license provides advantages in certain special circumstances.

For example, on rare occasions, there may be a special need to encourage the widest possible use of a certain library, so that it becomes a de-facto standard. To achieve this, non-free programs must be allowed to use the library. A more frequent case is that a free library does the same job as widely used non-free libraries. In this case, there is little to gain by limiting the free library to free software only, so we use the Lesser General Public License.

In other cases, permission to use a particular library in non-free programs enables a greater number of people to use a large body of free software. For example, permission to use the GNU C Library in non-free programs enables many more people to use the whole GNU operating system, as well as its variant, the GNU/Linux operating system.

Although the Lesser General Public License is Less protective of the users' freedom, it does ensure that the user of a program that is linked with the Library has the freedom and the wherewithal to run

that program using a modified version of the Library.

The precise terms and conditions for copying, distribution and modification follow. Pay close attention to the difference between a "work based on the library" and a "work that uses the library". The former contains code derived from the library, whereas the latter must be combined with the library in order to run.

GNU LESSER GENERAL PUBLIC LICENSE TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

0. This License Agreement applies to any software library or other program which contains a notice placed by the copyright holder or other authorized party saying it may be distributed under the terms of this Lesser General Public License (also called "this License"). Each licensee is addressed as "you".

A "library" means a collection of software functions and/or data prepared so as to be conveniently linked with application programs (which use some of those functions and data) to form executables.

The "Library", below, refers to any such software library or work which has been distributed under these terms. A "work based on the Library" means either the Library or any derivative work under copyright law: that is to say, a work containing the Library or a portion of it, either verbatim or with modifications and/or translated straightforwardly into another language. (Hereinafter, translation is included without limitation in the term "modification".)

"Source code" for a work means the preferred form of the work for making modifications to it. For a library, complete source code means all the source code for all modules it contains, plus any associated interface definition files, plus the scripts used to control compilation and installation of the library.

Activities other than copying, distribution and modification are not covered by this License; they are outside its scope. The act of running a program using the Library is not restricted, and output from such a program is covered only if its contents constitute a work based on the Library (independent of the use of the Library in a tool for writing it). Whether that is true depends on what the Library does and what the program that uses the Library does.

1. You may copy and distribute verbatim copies of the Library's complete source code as you receive it, in any medium, provided that

you conspicuously and appropriately publish on each copy an appropriate copyright notice and disclaimer of warranty; keep intact all the notices that refer to this License and to the absence of any warranty; and distribute a copy of this License along with the Library.

You may charge a fee for the physical act of transferring a copy, and you may at your option offer warranty protection in exchange for a fee.

2. You may modify your copy or copies of the Library or any portion of it, thus forming a work based on the Library, and copy and distribute such modifications or work under the terms of Section 1 above, provided that you also meet all of these conditions:

- a) The modified work must itself be a software library.
- b) You must cause the files modified to carry prominent notices stating that you changed the files and the date of any change.
- c) You must cause the whole of the work to be licensed at no charge to all third parties under the terms of this License.
- d) If a facility in the modified Library refers to a function or a table of data to be supplied by an application program that uses the facility, other than as an argument passed when the facility is invoked, then you must make a good faith effort to ensure that, in the event an application does not supply such function or table, the facility still operates, and performs whatever part of its purpose remains meaningful.

(For example, a function in a library to compute square roots has a purpose that is entirely well-defined independent of the application. Therefore, Subsection 2d requires that any application-supplied function or table used by this function must

be optional: if the application does not supply it, the square root function must still compute square roots.)

These requirements apply to the modified work as a whole. If identifiable sections of that work are not derived from the Library, and can be reasonably considered independent and separate works in themselves, then this License, and its terms, do not apply to those sections when you distribute them as separate works. But when you distribute the same sections as part of a whole which is a work based on the Library, the distribution of the whole must be on the terms of this License, whose permissions for other licensees extend to the

entire whole, and thus to each and every part regardless of who wrote it.

Thus, it is not the intent of this section to claim rights or contest your rights to work written entirely by you; rather, the intent is to exercise the right to control the distribution of derivative or collective works based on the Library.

In addition, mere aggregation of another work not based on the Library with the Library (or with a work based on the Library) on a volume of a storage or distribution medium does not bring the other work under the scope of this License.

3. You may opt to apply the terms of the ordinary GNU General Public License instead of this License to a given copy of the Library. To do this, you must alter all the notices that refer to this License, so that they refer to the ordinary GNU General Public License, version 2, instead of to this License. (If a newer version than version 2 of the ordinary GNU General Public License has appeared, then you can specify that version instead if you wish.) Do not make any other change in these notices.

Once this change is made in a given copy, it is irreversible for that copy, so the ordinary GNU General Public License applies to all subsequent copies and derivative works made from that copy.

This option is useful when you wish to copy part of the code of the Library into a program that is not a library.

4. You may copy and distribute the Library (or a portion or derivative of it, under Section 2) in object code or executable form under the terms of Sections 1 and 2 above provided that you accompany it with the complete corresponding machine-readable source code, which must be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange.

If distribution of object code is made by offering access to copy from a designated place, then offering equivalent access to copy the source code from the same place satisfies the requirement to distribute the source code, even though third parties are not compelled to copy the source along with the object code.

5. A program that contains no derivative of any portion of the Library, but is designed to work with the Library by being compiled or linked with it, is called a "work that uses the Library". Such a work, in isolation, is not a derivative work of

the Library, and therefore falls outside the scope of this License.

However, linking a "work that uses the Library" with the Library creates an executable that is a derivative of the Library (because it contains portions of the Library), rather than a "work that uses the library". The executable is therefore covered by this License. Section 6 states terms for distribution of such executables.

When a "work that uses the Library" uses material from a header file that is part of the Library, the object code for the work may be a derivative work of the Library even though the source code is not. Whether this is true is especially significant if the work can be linked without the Library, or if the work is itself a library. The threshold for this to be true is not precisely defined by law.

If such an object file uses only numerical parameters, data structure layouts and accessors, and small macros and small inline functions (ten lines or less in length), then the use of the object file is unrestricted, regardless of whether it is legally a derivative work. (Executables containing this object code plus portions of the Library will still fall under Section 6.)

Otherwise, if the work is a derivative of the Library, you may distribute the object code for the work under the terms of Section 6. Any executables containing that work also fall under Section 6, whether or not they are linked directly with the Library itself.

6. As an exception to the Sections above, you may also combine or link a "work that uses the Library" with the Library to produce a work containing portions of the Library, and distribute that work under terms of your choice, provided that the terms permit modification of the work for the customer's own use and reverse engineering for debugging such modifications.

You must give prominent notice with each copy of the work that the Library is used in it and that the Library and its use are covered by this License. You must supply a copy of this License. If the work during execution displays copyright notices, you must include the copyright notice for the Library among them, as well as a reference directing the user to the copy of this License. Also, you must do one of these things:

- a) Accompany the work with the complete corresponding machine-readable source code for the Library including whatever changes were used in the work (which must be distributed under

Sections 1 and 2 above); and, if the work is an executable linked with the Library, with the complete machine-readable "work that uses the Library", as object code and/or source code, so that the user can modify the Library and then relink to produce a modified executable containing the modified Library. (It is understood that the user who changes the contents of definitions files in the Library will not necessarily be able to recompile the application to use the modified definitions.)

- b) Use a suitable shared library mechanism for linking with the Library. A suitable mechanism is one that (1) uses at run time a copy of the library already present on the user's computer system, rather than copying library functions into the executable, and (2) will operate properly with a modified version of the library, if the user installs one, as long as the modified version is interface-compatible with the version that the work was made with.
- c) Accompany the work with a written offer, valid for at least three years, to give the same user the materials specified in Subsection 6a, above, for a charge no more than the cost of performing this distribution.
- d) If distribution of the work is made by offering access to copy from a designated place, offer equivalent access to copy the above specified materials from the same place.
- e) Verify that the user has already received a copy of these materials or that you have already sent this user a copy.

For an executable, the required form of the "work that uses the Library" must include any data and utility programs needed for reproducing the executable from it. However, as a special exception, the materials to be distributed need not include anything that is normally distributed (in either source or binary form) with the major components (compiler, kernel, and so on) of the operating system on which the executable runs, unless that component itself accompanies the executable.

It may happen that this requirement contradicts the license restrictions of other proprietary libraries that do not normally accompany the operating system. Such a contradiction means you cannot use both them and the Library together in an executable that you distribute.

7. You may place library facilities that are a work based on the Library side-by-side in a single library together with other library

facilities not covered by this License, and distribute such a combined library, provided that the separate distribution of the work based on the Library and of the other library facilities is otherwise permitted, and provided that you do these two things:

- a) Accompany the combined library with a copy of the same work based on the Library, uncombined with any other library facilities. This must be distributed under the terms of the Sections above.
- b) Give prominent notice with the combined library of the fact that part of it is a work based on the Library, and explaining where to find the accompanying uncombined form of the same work.

8. You may not copy, modify, sublicense, link with, or distribute the Library except as expressly provided under this License. Any attempt otherwise to copy, modify, sublicense, link with, or distribute the Library is void, and will automatically terminate your rights under this License. However, parties who have received copies, or rights, from you under this License will not have their licenses terminated so long as such parties remain in full compliance.

9. You are not required to accept this License, since you have not signed it. However, nothing else grants you permission to modify or distribute the Library or its derivative works. These actions are prohibited by law if you do not accept this License. Therefore, by modifying or distributing the Library (or any work based on the Library), you indicate your acceptance of this License to do so, and all its terms and conditions for copying, distributing or modifying the Library or works based on it.

10. Each time you redistribute the Library (or any work based on the Library), the recipient automatically receives a license from the original licensor to copy, distribute, link with or modify the Library subject to these terms and conditions. You may not impose any further restrictions on the recipients' exercise of the rights granted herein. You are not responsible for enforcing compliance by third parties with this License.

11. If, as a consequence of a court judgment or allegation of patent infringement or for any other reason (not limited to patent issues), conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot distribute so as to satisfy simultaneously your obligations under this

License and any other pertinent obligations, then as a consequence you may not distribute the Library at all. For example, if a patent license would not permit royalty-free redistribution of the Library by all those who receive copies directly or indirectly through you, then the only way you could satisfy both it and this License would be to refrain entirely from distribution of the Library.

If any portion of this section is held invalid or unenforceable under any particular circumstance, the balance of the section is intended to apply, and the section as a whole is intended to apply in other circumstances.

It

is not the purpose of this section to induce you to infringe any patents or other property right claims or to contest validity of any such claims; this section has the sole purpose of protecting the integrity of the free software distribution system which is implemented by public license practices. Many people have made generous contributions to the wide range of software distributed through that system in reliance on consistent application of that system; it is up to the author/donor to decide if he or she is willing to distribute software through any other system and a licensee cannot impose that choice.

This section is intended to make thoroughly clear what is believed to be a consequence of the rest of this License.

12. If the distribution and/or use of the Library is restricted in certain countries either by patents or by copyrighted interfaces, the original copyright holder who places the Library under this License may add an explicit geographical distribution limitation excluding those countries, so that distribution is permitted only in or among countries not thus excluded. In such case, this License incorporates the limitation as if written in the body of this License.

13. The Free Software Foundation may publish revised and/or new versions of the Lesser General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Library specifies a version number of this License which applies to it and "any later version", you have the option of following the terms and conditions either of that version or of any later version published by the Free Software Foundation. If the Library does not specify a license version number, you may choose any version ever published by the Free Software Foundation.

14. If you wish to incorporate parts of the Library into other free programs whose distribution conditions are incompatible with these, write to the author to ask for permission. For software which is copyrighted by the Free Software Foundation, write to the Free Software Foundation; we sometimes make exceptions for this. Our decision will be guided by the two goals of preserving the free status of all derivatives of our free software and of promoting the sharing and reuse of software generally.

NO WARRANTY

15. BECAUSE THE LIBRARY IS LICENSED FREE OF CHARGE, THERE IS NO WARRANTY FOR THE LIBRARY, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE LIBRARY "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE LIBRARY IS WITH YOU. SHOULD THE LIBRARY PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

16. IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY AND/OR REDISTRIBUTE THE LIBRARY AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE LIBRARY (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE LIBRARY TO OPERATE WITH ANY OTHER SOFTWARE), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Libraries

If you develop a new library, and you want it to be of the greatest possible use to the public, we recommend making it free software that everyone can redistribute and change. You can do so by permitting redistribution under these terms (or, alternatively, under the terms of the ordinary General Public License).

To apply these terms, attach the following notices to the library. It is safest to attach them to the start of each source file to most effectively convey the exclusion of warranty; and each file should have at least the

"copyright" line and a pointer to where the full notice is found.

<one line to give the library's name and a brief idea of what it does.>

Copyright (C) <year> <name of author>

This library is free software; you can redistribute it and/or modify it under the terms of the GNU Lesser General Public License as published by the Free Software Foundation; either version 2.1 of the License, or (at your option) any later version.

This library is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU Lesser General Public License for more details.

You should have received a copy of the GNU Lesser General Public License along with this library; if not, write to the Free Software Foundation, Inc., 51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA

Also add information on how to contact you by electronic and paper mail.

You should also get your employer (if you work as a programmer) or your school, if any, to sign a "copyright disclaimer" for the library, if necessary. Here is a sample; alter the names:

Yoyodyne, Inc., hereby disclaims all copyright interest in the library `Frob' (a library for tweaking knobs) written by James Random Hacker.

<signature of Ty Coon>, 1 April 1990
Ty Coon, President of Vice

That's all there is to it!

1.27 berkeley-db 5.3.28-13.1ubuntu1.1

1.27.1 Available under license :

Copyright (c) 1996, 2013 Oracle and/or its affiliates. All rights reserved. See the file LICENSE for redistribution information.

This software is copyrighted by Christian Werner <chw@ch-werner.de> and other authors. The following terms apply to all files associated with the software unless explicitly disclaimed in individual files.

The authors hereby grant permission to use, copy, modify, distribute, and license this software and its documentation for any purpose, provided that existing copyright notices are retained in all copies and that this notice is included verbatim in any distributions. No written agreement,

license, or royalty fee is required for any of the authorized uses.
Modifications to this software may be copyrighted by their authors
and need not follow the licensing terms described here, provided that
the new terms are clearly indicated on the first page of each file where
they apply.

IN NO EVENT SHALL THE AUTHORS OR DISTRIBUTORS BE LIABLE TO ANY PARTY
FOR DIRECT, INDIRECT, SPECIAL, INCIDENTAL, OR CONSEQUENTIAL DAMAGES
ARISING OUT OF THE USE OF THIS SOFTWARE, ITS DOCUMENTATION, OR ANY
DERIVATIVES

THEREOF, EVEN IF THE AUTHORS HAVE BEEN ADVISED OF THE
POSSIBILITY OF SUCH DAMAGE.

THE AUTHORS AND DISTRIBUTORS SPECIFICALLY DISCLAIM ANY WARRANTIES,
INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY,
FITNESS FOR A PARTICULAR PURPOSE, AND NON-INFRINGEMENT. THIS SOFTWARE
IS PROVIDED ON AN "AS IS" BASIS, AND THE AUTHORS AND DISTRIBUTORS HAVE
NO OBLIGATION TO PROVIDE MAINTENANCE, SUPPORT, UPDATES, ENHANCEMENTS, OR
MODIFICATIONS.

This software is copyrighted by Christian Werner <chw@ch-werner.de> and others.

The following terms apply to all files associated with the software
unless explicitly disclaimed in individual files.

The authors hereby grant permission to use, copy, modify, distribute,
and license this software and its documentation for any purpose, provided
that existing copyright notices are retained in all copies and that this
notice is included verbatim in any distributions. No written agreement,
license, or royalty fee is required for any of the authorized uses.

Modifications to this software may be copyrighted by their authors
and need not follow the licensing terms described here, provided that
the new terms are clearly indicated on the first page of each file where
they apply.

IN NO EVENT SHALL THE AUTHORS OR DISTRIBUTORS BE LIABLE TO ANY PARTY
FOR DIRECT, INDIRECT, SPECIAL, INCIDENTAL, OR CONSEQUENTIAL DAMAGES
ARISING OUT OF THE USE OF THIS SOFTWARE, ITS DOCUMENTATION, OR ANY
DERIVATIVES THEREOF,

EVEN IF THE AUTHORS HAVE BEEN ADVISED OF THE
POSSIBILITY OF SUCH DAMAGE.

THE AUTHORS AND DISTRIBUTORS SPECIFICALLY DISCLAIM ANY WARRANTIES,
INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY,
FITNESS FOR A PARTICULAR PURPOSE, AND NON-INFRINGEMENT. THIS SOFTWARE
IS PROVIDED ON AN "AS IS" BASIS, AND THE AUTHORS AND DISTRIBUTORS HAVE
NO OBLIGATION TO PROVIDE MAINTENANCE, SUPPORT, UPDATES, ENHANCEMENTS, OR
MODIFICATIONS.

/*-

* \$Id\$

*/

The following is the license that applies to this copy of the Berkeley DB software. For a license to use the Berkeley DB software under conditions other than those described here, or to purchase support for this software, please contact Oracle at berkeleydb-info_us@oracle.com.

/*

* Copyright (c) 1990, 2013 Oracle and/or its affiliates. All rights reserved.

*

* Redistribution and use in source and binary forms, with or without
* modification, are permitted provided that the following conditions
* are met:

* 1. Redistributions of source code must retain the above copyright

* notice, this list of conditions and the following disclaimer.

* 2. Redistributions in binary form must reproduce the above copyright

* notice, this list of conditions and the following disclaimer in the

* documentation and/or other materials provided with the distribution.

* 3. Redistributions in any form must be accompanied by information
on

* how to obtain complete source code for the DB software and any

* accompanying software that uses the DB software. The source code

* must either be included in the distribution or be available for no

* more than the cost of distribution plus a nominal fee, and must be

* freely redistributable under reasonable conditions. For an

* executable file, complete source code means the source code for all

* modules it contains. It does not include source code for modules or

* files that typically accompany the major components of the operating

* system on which the executable file runs.

*

* THIS SOFTWARE IS PROVIDED BY ORACLE ``AS IS" AND ANY EXPRESS OR

* IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED

* WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR

* NON-INFRINGEMENT, ARE DISCLAIMED. IN NO EVENT SHALL ORACLE BE LIABLE

* FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR

* CONSEQUENTIAL

DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF

* SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR

* BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY,

* WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE

* OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN

* IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

*/

/*

* Copyright (c) 1990, 1993, 1994, 1995

* The Regents of the University of California. All rights reserved.

*

- * Redistribution and use in source and binary forms, with or without
- * modification, are permitted provided that the following conditions
- * are met:
- * 1. Redistributions of source code must retain the above copyright
- * notice, this list of conditions and the following disclaimer.
- * 2. Redistributions in binary form must reproduce the above copyright
- * notice, this list of conditions and the following disclaimer in the
- * documentation and/or other materials provided with
- the distribution.
- * 3. Neither the name of the University nor the names of its contributors
- * may be used to endorse or promote products derived from this software
- * without specific prior written permission.
- *

* THIS SOFTWARE IS PROVIDED BY THE REGENTS AND CONTRIBUTORS ``AS IS" AND
 * ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE
 * IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE
 * ARE DISCLAIMED. IN NO EVENT SHALL THE REGENTS OR CONTRIBUTORS BE LIABLE
 * FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL
 * DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS
 * OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION)
 * HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT
 * LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY
 * OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF
 * SUCH DAMAGE.

*/

/*

* Copyright (c) 1995, 1996
 * The President and Fellows of Harvard University. All rights reserved.
 *

- * Redistribution and use in source and binary forms, with or without
- * modification, are permitted provided that the following conditions
- * are met:
- * 1. Redistributions of source code must retain the above copyright
- * notice, this list of conditions and the following disclaimer.
- * 2. Redistributions in binary form must reproduce the above copyright
- * notice, this list of conditions and the following disclaimer in the
- * documentation and/or other materials provided with the distribution.
- * 3. Neither the name of the University nor the names of its contributors
- * may be used to endorse or promote products derived from this software
- * without specific prior written permission.
- *

* THIS SOFTWARE IS PROVIDED BY HARVARD AND ITS CONTRIBUTORS ``AS IS" AND
 * ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE
 * IMPLIED WARRANTIES OF MERCHANTABILITY
 AND FITNESS FOR A PARTICULAR PURPOSE
 * ARE DISCLAIMED. IN NO EVENT SHALL HARVARD OR ITS CONTRIBUTORS BE LIABLE
 * FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL
 * DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS

* OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION)
* HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT
* LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY
* OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF
* SUCH DAMAGE.

*/

/**

* ASM: a very small and fast Java bytecode manipulation framework

* Copyright (c) 2000-2005 INRIA, France Telecom

* All rights reserved.

*

* Redistribution and use in source and binary forms, with or without

* modification, are permitted provided that the following conditions

* are met:

* 1. Redistributions of source code must retain the

above copyright

* notice, this list of conditions and the following disclaimer.

* 2. Redistributions in binary form must reproduce the above copyright

* notice, this list of conditions and the following disclaimer in the

* documentation and/or other materials provided with the distribution.

* 3. Neither the name of the copyright holders nor the names of its

* contributors may be used to endorse or promote products derived from

* this software without specific prior written permission.

*

* THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS"

* AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE

* IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE

* ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER OR CONTRIBUTORS BE

* LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR

* CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF

* SUBSTITUTE GOODS OR SERVICES;

LOSS OF USE, DATA, OR PROFITS; OR BUSINESS

* INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN

* CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE)

* ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF

* THE POSSIBILITY OF SUCH DAMAGE.

*/

NOTE

The license is based on the zlib/libpng license. For more details see
<http://www.opensource.org/licenses/zlib-license.html>. The intent of the
license is to:

- keep the license as simple as possible
- encourage the use of CuTest in both free and commercial applications
and libraries
- keep the source code together

- give credit to the CuTest contributors for their work

If you ship CuTest in source form with your source distribution, the following license document must be included with it in unaltered form. If you find CuTest useful we would like to hear about it.

LICENSE

Copyright (c) 2003 Asim Jalis

This software is provided 'as-is', without any express or implied warranty. In no event will the authors be held liable for any damages arising from the use of this software.

Permission is granted to anyone to use this software for any purpose, including commercial applications, and to alter it and redistribute it freely, subject to the following restrictions:

1. The origin of this software must not be misrepresented; you must not claim that you wrote the original software. If you use this software in a product, an acknowledgment in the product documentation would be appreciated but is not required.
2. Altered source versions must be plainly marked as such, and must not be misrepresented as being the original software.
3. This notice may not be removed or altered from any source distribution.

This package was debianized by Clint Adams <schizo@debian.org> on Wed, 25 Jul 2007 20:37:51 +0700

It was downloaded from
<http://www.oracle.com/technology/software/products/berkeley-db/db/index.html>

Copyright and license:

The following is the license that applies to this copy of the Berkeley DB software. For a license to use the Berkeley DB software under conditions other than those described here, or to purchase support for this software, please contact Oracle at berkeleydb-info_us@oracle.com.

=====
/*

- * Copyright (c) 1990, 2010 Oracle and/or its affiliates. All rights reserved.
- *
- * Redistribution and use in source and binary forms, with or without
- * modification, are permitted provided that the following conditions

* are met:

- * 1. Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.
- * 2. Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.
- * 3. Redistributions in any form must be accompanied by information on how to obtain complete source code for the DB software and any accompanying software that uses the DB software. The source code must either be included in the distribution or be available for no more than the cost of distribution plus a nominal fee, and must be freely redistributable under reasonable conditions. For an executable file, complete source code means the source code for all modules it contains. It does not include source code for modules or files that typically accompany the major components of the operating system on which the executable file runs.

* THIS SOFTWARE IS PROVIDED BY ORACLE ``AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR NON-INFRINGEMENT, ARE DISCLAIMED. IN NO EVENT SHALL ORACLE BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

*/

/*

* Copyright (c) 1990, 1993, 1994, 1995

* The Regents of the University of California. All rights reserved.

*

* Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

- * 1. Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.
- * 2. Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.
- * 3. Neither the name of the University nor the names of its contributors may be used to endorse or promote products derived from this software without specific prior written permission.

* THIS SOFTWARE IS PROVIDED BY THE REGENTS AND CONTRIBUTORS ``AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE

* IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE
* ARE DISCLAIMED. IN NO EVENT SHALL THE REGENTS OR CONTRIBUTORS BE LIABLE
* FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL
* DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS
* OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION)
* HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY,
* WHETHER IN CONTRACT, STRICT
* LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY
* OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF
* SUCH DAMAGE.

*/

/*

* Copyright (c) 1995, 1996

* The President and Fellows of Harvard University. All rights reserved.

*

* Redistribution and use in source and binary forms, with or without
* modification, are permitted provided that the following conditions
* are met:

* 1. Redistributions of source code must retain the above copyright

* notice, this list of conditions and the following disclaimer.

* 2. Redistributions in binary form must reproduce the above copyright

* notice, this list of conditions and the following disclaimer in the

* documentation and/or other materials provided with the distribution.

* 3. Neither the name of the University nor the names of its contributors

* may be used to endorse or promote products derived from this software

* without specific

prior written permission.

*

* THIS SOFTWARE IS PROVIDED BY HARVARD AND ITS CONTRIBUTORS ``AS IS" AND

* ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE

* IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE

* ARE DISCLAIMED. IN NO EVENT SHALL HARVARD OR ITS CONTRIBUTORS BE LIABLE

* FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL

* DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS

* OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION)

* HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT

* LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY

* OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF

* SUCH DAMAGE.

*/

/**

* ASM: a very small and fast Java bytecode manipulation framework

* Copyright (c) 2000-2005 INRIA, France Telecom

* All rights reserved.

*

* Redistribution and use in source and binary forms, with or without

* modification, are permitted provided that the following conditions

* are met:

- * 1. Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.
- * 2. Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.
- * 3. Neither the name of the copyright holders nor the names of its contributors may be used to endorse or promote products derived from this software without specific prior written permission.

*

* THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

*/

This package was debianized by Sam Clegg <samo@debian.org> on Tue, 25 Jul 2006 11:43:45 +0100.

It was downloaded from <<http://www.ch-werner.de/sqliteodbc/>>

Upstream Author: Christian Werner <chw@ch-werner.de>

Copyright: Copyright (c) 2001-2011 Christian Werner <chw@ch-werner.de>
OS/2 Port Copyright (c) 2004 Lorne R. Sunley <lsunley@mb.sympatico.ca>

License:

This software is copyrighted by Christian Werner <chw@ch-werner.de> and other authors. The following terms apply to all files associated with the software unless explicitly disclaimed in individual files.

The authors hereby grant permission to use, copy, modify, distribute, and license this software and its documentation for any purpose, provided that existing copyright notices are retained in all copies and that this notice is included verbatim in any distributions. No written agreement, license, or royalty fee is required for any of the authorized uses.

Modifications to this software may be copyrighted by their authors and

need not follow the licensing terms described here, provided that the new terms are clearly indicated on the first page of each file where

they apply.

IN NO EVENT SHALL THE AUTHORS OR DISTRIBUTORS BE LIABLE TO ANY PARTY FOR DIRECT, INDIRECT, SPECIAL, INCIDENTAL, OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OF THIS SOFTWARE, ITS DOCUMENTATION, OR ANY DERIVATIVES THEREOF, EVEN IF THE AUTHORS HAVE BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

THE AUTHORS AND DISTRIBUTORS SPECIFICALLY DISCLAIM ANY WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, AND NON-INFRINGEMENT. THIS SOFTWARE IS PROVIDED ON AN "AS IS" BASIS, AND THE AUTHORS AND DISTRIBUTORS HAVE NO OBLIGATION TO PROVIDE MAINTENANCE, SUPPORT, UPDATES, ENHANCEMENTS, OR MODIFICATIONS.

The Debian packaging is (C) 2006, Sam Clegg <samo@debian.org> and is licensed under the GPL-3, see `~/usr/share/common-licenses/GPL-3`.

1.28 bzip2 1.0.6-8.1ubuntu0.2

1.28.1 Available under license :

This program, "bzip2", the associated library "libbzip2", and all documentation, are copyright (C) 1996-2010 Julian R Seward. All rights reserved.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

1. Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.
2. The origin of this software must not be misrepresented; you must not claim that you wrote the original software. If you use this software in a product, an acknowledgment in the product documentation would be appreciated but is not required.
3. Altered source versions must be plainly marked as such, and must not be misrepresented as being the original software.
4. The name of the author may not be used to endorse or promote products derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE AUTHOR ``AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE AUTHOR BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

Julian Seward, jseward@bzip.org
bzip2/libbzip2 version 1.0.6 of 6 September 2010

This bzip2 Debian package was created by Philippe Troin <phil@fifi.org>. It is currently maintained by Anibal Monsalve Salazar <anibal@debian.org>. It is Copyright (C) 1999, 2000, 2001, 2002 Philippe Troin <phil@fifi.org> and Copyright (C) 2004-2011 Anibal Monsalve Salazar. It is licensed under the GNU General Public License version 2 which can be found in </usr/share/common-licenses/GPL-2>.

The original tarball was downloaded from
<http://www.bzip.org/downloads.html>

For more information about bzip2, please visit:
<http://www.bzip.org/>

Author:
Julian Seward <jseward@acm.org>

Copyright: (from LICENSE)

This program, "bzip2", the associated library "libbzip2", and all documentation, are copyright (C) 1996-2010 Julian R Seward. All rights reserved.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

1. Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.

2. The origin of this software must not be misrepresented; you must not claim that you wrote the original software. If you use this software in a product, an acknowledgment in the product documentation would be appreciated but is not required.
3. Altered source versions must be plainly marked as such, and must not be misrepresented as being the original software.
4. The name of the author may not be used to endorse or promote products derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE AUTHOR ``AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE AUTHOR BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

Julian Seward, jseward@bzip.org
bzip2/libbzip2 version 1.0.6 of 6 September 2010

1.29 libgpg-error 1.27-6

1.29.1 Available under license :

GNU GENERAL PUBLIC LICENSE

Version 2, June 1991

Copyright (C) 1989, 1991 Free Software Foundation, Inc.

51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA

Everyone is permitted to copy and distribute verbatim copies of this license document, but changing it is not allowed.

Preamble

The licenses for most software are designed to take away your freedom to share and change it. By contrast, the GNU General Public License is intended to guarantee your freedom to share and change free

software--to make sure the software is free for all its users. This General Public License applies to most of the Free Software Foundation's software and to any other program whose authors commit to using it. (Some other Free Software Foundation software is covered by the GNU Library General Public License instead.) You can apply it to your programs, too.

When we speak of free software, we are referring to freedom, not price. Our General Public Licenses are designed to make sure that you have the freedom to distribute copies of free software (and charge for this service if you wish), that you receive source code or can get it if you want it, that you can change the software or use pieces of it in new free programs; and that you know you can do these things.

To protect your rights, we need to make restrictions that forbid anyone to deny you these rights or to ask you to surrender the rights. These restrictions translate to certain responsibilities for you if you distribute copies of the software, or if you modify it.

For example, if you distribute copies of such a program, whether gratis or for a fee, you must give the recipients all the rights that you have. You must make sure that they, too, receive or can get the source code. And you must show them these terms so they know their rights.

We protect your rights with two steps: (1) copyright the software, and (2) offer you this license which gives you legal permission to copy, distribute and/or modify the software.

Also, for each author's protection and ours, we want to make certain that everyone understands that there is no warranty for this free software. If the software is modified by someone else and passed on, we want its recipients to know that what they have is not the original, so that any problems introduced by others will not reflect on the original authors' reputations.

Finally, any free program is threatened constantly by software patents. We wish to avoid the danger that redistributors of a free program will individually obtain patent licenses, in effect making the program proprietary. To prevent this, we have made it clear that any patent must be licensed for everyone's free use or not licensed at all.

The precise terms and conditions for copying, distribution and modification follow.

GNU GENERAL PUBLIC LICENSE

TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

0. This License applies to any program or other work which contains a notice placed by the copyright holder saying it may be distributed under the terms of this General Public License. The "Program", below, refers to any such program or work, and a "work based on the Program" means either the Program or any derivative work under copyright law: that is to say, a work containing the Program or a portion of it, either verbatim or with modifications and/or translated into another language. (Hereinafter, translation is included without limitation in the term "modification".) Each licensee is addressed as "you".

Activities other than copying, distribution and modification are not covered by this License; they are outside its scope. The act of running the Program is not restricted, and the output from the Program is covered only if its contents constitute a work based on the Program (independent of having been made by running the Program). Whether that is true depends on what the Program does.

1. You may copy and distribute verbatim copies of the Program's source code as you receive it, in any medium, provided that you conspicuously and appropriately publish on each copy an appropriate copyright notice and disclaimer of warranty; keep intact all the notices that refer to this License and to the absence of any warranty; and give any other recipients of the Program a copy of this License along with the Program.

You may charge a fee for the physical act of transferring a copy, and you may at your option offer warranty protection in exchange for a fee.

2. You may modify your copy or copies of the Program or any portion of it, thus forming a work based on the Program, and copy and distribute such modifications or work under the terms of Section 1 above, provided that you also meet all of these conditions:

- a) You must cause the modified files to carry prominent notices stating that you changed the files and the date of any change.
- b) You must cause any work that you distribute or publish, that in

whole or in part contains or is derived from the Program or any part thereof, to be licensed as a whole at no charge to all third parties under the terms of this License.

- c) If the modified program normally reads commands interactively when run, you must cause it, when started running for such

interactive use in the most ordinary way, to print or display an announcement including an appropriate copyright notice and a notice that there is no warranty (or else, saying that you provide a warranty) and that users may redistribute the program under these conditions, and telling the user how to view a copy of this License. (Exception: if the Program itself is interactive but does not normally print such an announcement, your work based on the Program is not required to print an announcement.)

These requirements apply to the modified work as a whole. If identifiable sections of that work are not derived from the Program, and can be reasonably considered independent and separate works in themselves, then this License, and its terms, do not apply to those sections when you distribute them as separate works. But when you distribute the same sections as part of a whole which is a work based on the Program, the distribution of the whole must be on the terms of this License, whose permissions for other licensees extend to the entire whole, and thus to each and every part regardless of who wrote it.

Thus, it is not the intent of this section to claim rights or contest your rights to work written entirely by you; rather, the intent is to exercise the right to control the distribution of derivative or collective works based on the Program.

In addition, mere aggregation of another work not based on the Program with the Program (or with a work based on the Program) on a volume of a storage or distribution medium does not bring the other work under the scope of this License.

3. You may copy and distribute the Program (or a work based on it, under Section 2) in object code or executable form under the terms of Sections 1 and 2 above provided that you also do one of the following:

a) Accompany it with the complete corresponding machine-readable source code, which must be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange; or,

b) Accompany it with a written offer, valid for at least three years, to give any third party, for a charge no more than your cost of physically performing source distribution, a complete machine-readable copy of the corresponding source code, to be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange; or,

c) Accompany it with the information you received as to the offer to distribute corresponding source code. (This alternative is

allowed only for noncommercial distribution and only if you received the program in object code or executable form with such an offer, in accord with Subsection b above.)

The source code for a work means the preferred form of the work for making modifications to it. For an executable work, complete source code means all the source code for all modules it contains, plus any associated interface definition files, plus the scripts used to control compilation and installation of the executable. However, as a special exception, the source code distributed need not include anything that is normally distributed (in either source or binary form) with the major components (compiler, kernel, and so on) of the operating system on which the executable runs, unless that component itself accompanies the executable.

If distribution of executable or object code is made by offering access to copy from a designated place, then offering equivalent access to copy the source code from the same place counts as distribution of the source code, even though third parties are not compelled to copy the source along with the object code.

4. You may not copy, modify, sublicense, or distribute the Program except as expressly provided under this License. Any attempt otherwise to copy, modify, sublicense or distribute the Program is void, and will automatically terminate your rights under this License. However, parties who have received copies, or rights, from you under this License will not have their licenses terminated so long as such parties remain in full compliance.

5. You are not required to accept this License, since you have not signed it. However, nothing else grants you permission to modify or distribute the Program or its derivative works. These actions are prohibited by law if you do not accept this License. Therefore, by modifying or distributing the Program (or any work based on the Program), you indicate your acceptance of this License to do so, and all its terms and conditions for copying, distributing or modifying the Program or works based on it.

6.

Each time you redistribute the Program (or any work based on the Program), the recipient automatically receives a license from the original licensor to copy, distribute or modify the Program subject to these terms and conditions. You may not impose any further restrictions on the recipients' exercise of the rights granted herein. You are not responsible for enforcing compliance by third parties to this License.

7. If, as a consequence of a court judgment or allegation of patent infringement or for any other reason (not limited to patent issues), conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot distribute so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not distribute the Program at all. For example, if a patent license would not permit royalty-free redistribution of the Program by all those who receive copies directly or indirectly through you, then the only way you could satisfy both it and this License would be to refrain entirely from distribution of the Program.

If any portion of this section is held invalid or unenforceable under any particular circumstance, the balance of the section is intended to apply and the section as a whole is intended to apply in other circumstances.

It is not the purpose of this section to induce you to infringe any patents or other property right claims or to contest validity of any such claims; this section has the sole purpose of protecting the integrity of the free software distribution system, which is implemented by public license practices. Many people have made generous contributions to the wide range of software distributed through that system in reliance on consistent application of that system; it is up to the author/donor to decide if he or she is willing to distribute software through any other system and a licensee cannot impose that choice.

This section is intended to make thoroughly clear what is believed to be a consequence of the rest of this License.

8. If the distribution and/or use of the Program is restricted in certain countries either by patents or by copyrighted interfaces, the original copyright holder who places the Program under this License may add an explicit geographical distribution limitation excluding those countries, so that distribution is permitted only in or among countries not thus excluded. In such case, this License incorporates the limitation as if written in the body of this License.

9. The Free Software Foundation may publish revised and/or new versions of the General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Program specifies a version number of this License which applies to it and "any later version", you have the option of following the terms and conditions either of that version or of any later version published by the Free Software Foundation. If the Program does not specify a version number of this License, you may choose any version ever published by the Free Software Foundation.

10. If you wish to incorporate parts of the Program into other free programs whose distribution conditions are different, write to the author to ask for permission. For software which is copyrighted by the Free Software Foundation, write to the Free Software Foundation; we sometimes make exceptions for this. Our decision will be guided by the two goals of preserving the free status of all derivatives of our free software and of promoting the sharing and reuse of software generally.

NO WARRANTY

11. BECAUSE THE PROGRAM IS LICENSED FREE OF CHARGE, THERE IS NO WARRANTY FOR THE PROGRAM, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE PROGRAM "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE PROGRAM IS WITH YOU. SHOULD THE PROGRAM PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

12. IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY AND/OR REDISTRIBUTE THE PROGRAM AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE PROGRAM (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE PROGRAM TO OPERATE WITH ANY OTHER PROGRAMS), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Programs

If you develop a new program, and you want it to be of the greatest possible use to the public, the best way to achieve this is to make it free software which everyone can redistribute and change under these terms.

To do so, attach the following notices to the program. It is safest to attach them to the start of each source file to most effectively convey the exclusion of warranty; and each file should have at least the "copyright" line and a pointer to where the full notice is found.

```
<one line to give the program's name and a brief idea of what it does.>  
Copyright (C) <year> <name of author>
```

This program is free software; you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation; either version 2 of the License, or
(at your option) any later version.

This program is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details.

You should have received a copy of the GNU General Public License along with this program; if not, write to the Free Software Foundation, Inc., 51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA

Also add information on how to contact you by electronic and paper mail.

If the program is interactive, make it output a short notice like this when it starts in an interactive mode:

```
Gnomovision version 69, Copyright (C) year name of author  
Gnomovision comes with ABSOLUTELY NO WARRANTY; for details type `show w'.  
This is free software, and you are welcome to redistribute it  
under certain conditions; type `show c' for details.
```

The hypothetical commands
`show w' and `show c' should show the appropriate parts of the General Public License. Of course, the commands you use may be called something other than `show w' and `show c'; they could even be mouse-clicks or menu items--whatever suits your program.

You should also get your employer (if you work as a programmer) or your school, if any, to sign a "copyright disclaimer" for the program, if necessary. Here is a sample; alter the names:

```
Yoyodyne, Inc., hereby disclaims all copyright interest in the program  
'Gnomovision' (which makes passes at compilers) written by James Hacker.
```

<signature of Ty Coon>, 1 April 1989

Ty Coon, President of Vice

This General Public License does not permit incorporating your program into proprietary programs. If your program is a subroutine library, you may consider it more useful to permit linking proprietary applications with the library. If this is what you want to do, use the GNU Library General Public License instead of this License.

GNU LESSER GENERAL PUBLIC LICENSE

Version 2.1, February 1999

Copyright (C) 1991, 1999 Free Software Foundation, Inc.

51 Franklin St, Fifth Floor, Boston, MA 02110-1301 USA

Everyone is permitted to copy and distribute verbatim copies of this license document, but changing it is not allowed.

[This is the first released version of the Lesser GPL. It also counts as the successor of the GNU Library Public License, version 2, hence the version number 2.1.]

Preamble

The licenses for most software are designed to take away your freedom to share and change it. By contrast, the GNU General Public Licenses are intended to guarantee your freedom to share and change free software--to make sure the software is free for all its users.

This license, the Lesser General Public License, applies to some specially designated software packages--typically libraries--of the Free Software Foundation and other authors who decide to use it. You can use it too, but we suggest you first think carefully about whether this license or the ordinary General Public License is the better strategy to use in any particular case, based on the explanations below.

When we speak of free software, we are referring to freedom of use, not price. Our General Public Licenses are designed to make sure that you have the freedom to distribute copies of free software (and charge for this service if you wish); that you receive source code or can get it if you want it; that you can change the software and use pieces of it in new free programs; and that you are informed that you can do these things.

To protect your rights, we need to make restrictions that forbid distributors to deny you these rights or to ask you to surrender these rights. These restrictions translate to certain responsibilities for

you if you distribute copies of the library or if you modify it.

For example, if you distribute copies of the library, whether gratis or for a fee, you must give the recipients all the rights that we gave you. You must make sure that they, too, receive or can get the source code. If you link other code with the library, you must provide complete object files to the recipients, so that they can relink them with the library after making changes to the library and recompiling it. And you must show them these terms so they know their rights.

We protect your rights with a two-step method: (1) we copyright the library, and (2) we offer you this license, which gives you legal permission to copy, distribute and/or modify the library.

To protect each distributor, we want to make it very clear that there is no warranty for the free library. Also, if the library is modified by someone else and passed on, the recipients should know that what they have is not the original version, so that the original author's reputation will not be affected by problems that might be introduced by others.

Finally, software patents pose a constant threat to the existence of any free program. We wish to make sure that a company cannot effectively restrict the users of a free program by obtaining a restrictive license from a patent holder. Therefore, we insist that any patent license obtained for a version of the library must be consistent with the full freedom of use specified in this license.

Most GNU software, including some libraries, is covered by the ordinary GNU General Public License. This license, the GNU Lesser General Public License, applies to certain designated libraries, and is quite different from the ordinary General Public License. We use this license for certain libraries in order to permit linking those libraries into non-free programs.

When a program is linked with a library, whether statically or using a shared library, the combination of the two is legally speaking a combined work, a derivative of the original library. The ordinary General Public License therefore permits such linking only if the entire combination fits its criteria of freedom. The Lesser General Public License permits more lax criteria for linking other code with the library.

We call this license the "Lesser" General Public License because it does Less to protect the user's freedom than the ordinary General

Public License. It also provides other free software developers Less of an advantage over competing non-free programs. These disadvantages are the reason we use the ordinary General Public License for many libraries. However, the Lesser license provides advantages in certain special circumstances.

For example, on rare occasions, there may be a special need to encourage the widest possible use of a certain library, so that it becomes a de-facto standard. To achieve this, non-free programs must be allowed to use the library. A more frequent case is that a free library does the same job as widely used non-free libraries. In this case, there is little to gain by limiting the free library to free software only, so we use the Lesser General Public License.

In other cases, permission to use a particular library in non-free programs enables a greater number of people to use a large body of free software. For example, permission to use the GNU C Library in non-free programs enables many more people to use the whole GNU operating system, as well as its variant, the GNU/Linux operating system.

Although the Lesser General Public License is Less protective of the users' freedom, it does ensure that the user of a program that is linked with the Library has the freedom and the wherewithal to run that program using a modified version of the Library.

The precise terms and conditions for copying, distribution and modification follow. Pay close attention to the difference between a "work based on the library" and a "work that uses the library". The former contains code derived from the library, whereas the latter must be combined with the library in order to run.

GNU LESSER GENERAL PUBLIC LICENSE TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

0. This License Agreement applies to any software library or other program which contains a notice placed by the copyright holder or other authorized party saying it may be distributed under the terms of this Lesser General Public License (also called "this License"). Each licensee is addressed as "you".

A "library" means a collection of software functions and/or data prepared so as to be conveniently linked with application programs (which use some of those functions and data) to form executables.

The "Library", below, refers to any such software library or work

which has been distributed under these terms. A "work based on the Library" means either the Library or any derivative work under copyright law: that is to say, a work containing the Library or a portion of it, either verbatim or with modifications and/or translated straightforwardly into another language. (Hereinafter, translation is included without limitation in the term "modification".)

"Source code" for a work means the preferred form of the work for making modifications to it. For a library, complete source code means all the source code for all modules it contains, plus any associated interface definition files, plus the scripts used to control compilation and installation of the library.

Activities other than copying, distribution and modification are not covered by this License; they are outside its scope. The act of running a program using the Library is not restricted, and output from such a program is covered only if its contents constitute a work based on the Library (independent of the use of the Library in a tool for writing it). Whether that is true depends on what the Library does and what the program that uses the Library does.

1. You may copy and distribute verbatim copies of the Library's complete source code as you receive it, in any medium, provided that you conspicuously and appropriately publish on each copy an appropriate copyright notice and disclaimer of warranty; keep intact all the notices that refer to this License and to the absence of any warranty; and distribute a copy of this License along with the Library.

You may charge a fee for the physical act of transferring a copy, and you may at your option offer warranty protection in exchange for a fee.

2. You may modify your copy or copies of the Library or any portion of it, thus forming a work based on the Library, and copy and distribute such modifications or work under the terms of Section 1 above, provided that you also meet all of these conditions:

- a) The modified work must itself be a software library.
- b) You must cause the files modified to carry prominent notices stating that you changed the files and the date of any change.
- c) You must cause the whole of the work to be licensed at no charge to all third parties under the terms

of this License.

d) If a facility in the modified Library refers to a function or a table of data to be supplied by an application program that uses the facility, other than as an argument passed when the facility is invoked, then you must make a good faith effort to ensure that, in the event an application does not supply such function or table, the facility still operates, and performs whatever part of its purpose remains meaningful.

(For example, a function in a library to compute square roots has a purpose that is entirely well-defined independent of the application. Therefore, Subsection 2d requires that any application-supplied function or table used by this function must be optional: if the application does not supply it, the square root function must still compute square roots.)

These requirements apply to the modified work as a whole. If identifiable sections of that work are not derived from the Library, and can be reasonably considered independent and separate works in themselves, then this License, and its terms, do not apply to those sections when you distribute them as separate works. But when you distribute the same sections as part of a whole which is a work based on the Library, the distribution of the whole must be on the terms of this License, whose permissions for other licensees extend to the entire whole, and thus to each and every part regardless of who wrote it.

Thus, it is not the intent of this section to claim rights or contest your rights to work written entirely by you; rather, the intent is to exercise the right to control the distribution of derivative or collective works based on the Library.

In addition, mere aggregation of another work not based on the Library with the Library (or with a work based on the Library) on a volume of a storage or distribution medium does not bring the other work under the scope of this License.

3. You may opt to apply the terms of the ordinary GNU General Public

License instead of this License to a given copy of the Library. To do this, you must alter all the notices that refer to this License, so that they refer to the ordinary GNU General Public License, version 2, instead of to this License. (If a newer version than version 2 of the ordinary GNU General Public License has appeared, then you can specify that version instead if you wish.) Do not make any other change in these notices.

Once this change is made in a given copy, it is irreversible for that copy, so the ordinary GNU General Public License applies to all subsequent copies and derivative works made from that copy.

This option is useful when you wish to copy part of the code of the Library into a program that is not a library.

4. You may copy and distribute the Library (or a portion or derivative of it, under Section 2) in object code or executable form under the terms of Sections 1 and 2 above provided that you accompany it with the complete corresponding machine-readable source code, which must be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange.

If distribution of object code is made by offering access to copy from a designated place, then offering equivalent access to copy the source code from the same place satisfies the requirement to distribute the source code, even though third parties are not compelled to copy the source along with the object code.

5. A program that contains no derivative of any portion of the Library, but is designed to work with the Library by being compiled or linked with it, is called a "work that uses the Library". Such a work, in isolation, is not a derivative work of the Library, and therefore falls outside the scope of this License.

However, linking a "work that uses the Library" with the Library creates an executable that is a derivative of the Library (because it contains portions of the Library), rather than a "work that uses the library". The executable is therefore covered by this License. Section 6 states terms for distribution of such executables.

When a "work that uses the Library" uses material from a header file that is part of the Library, the object code for the work may be a derivative work of the Library even though the source code is not. Whether this is true is especially significant if the work can be linked without the Library, or if the work is itself a library. The threshold for this to be true is not precisely defined by law.

If such an object file uses only numerical parameters, data structure layouts and accessors, and small macros and small inline functions (ten lines or less in length), then the use of the object file is unrestricted, regardless of whether it is legally a derivative work. (Executables containing this object code plus portions of the Library will still fall under Section 6.)

Otherwise, if the work is a derivative of the Library, you may distribute the object code for the work under the terms of Section 6. Any executables containing that work also fall under Section 6, whether or not they are linked directly with the Library itself.

6. As an exception to the Sections above, you may also combine or link a "work that uses the Library" with the Library to produce a work containing portions of the Library, and distribute that work under terms of your choice, provided that the terms permit modification of the work for the customer's own use and reverse engineering for debugging such modifications.

You must give prominent notice with each copy of the work that the Library is used in it and that the Library and its use are covered by this License. You must supply a copy of this License. If the work during execution displays copyright notices, you must include the copyright notice for the Library among them, as well as a reference directing the user to the copy of this License. Also, you must do one of these things:

a) Accompany the work with the complete corresponding machine-readable source code for the Library including whatever changes were used in the work (which must be distributed under Sections 1 and 2 above); and, if the work is an executable linked with the Library, with the complete machine-readable "work that uses the Library", as object code and/or source code, so that the user can modify the Library and then relink to produce a modified executable containing the modified Library. (It is understood that the user who changes the contents of definitions files in the Library will not necessarily be able to recompile the application to use the modified definitions.)

b) Use a suitable shared library mechanism for linking with the Library. A suitable mechanism is one that (1) uses at run time a copy of the library already present on the user's computer system, rather than copying library functions into the executable, and (2) will operate properly with a modified version of the library, if the user installs one, as long as the modified version is interface-compatible with the version that the work was made with.

c) Accompany the work with a written offer, valid for at least three years, to give the same user the materials specified in Subsection 6a, above, for a charge no more than the cost of performing this distribution.

d) If distribution of the work is made by offering access to copy from a designated place, offer equivalent access to copy the above specified materials from the same place.

e) Verify that the user has already received a copy of these materials or that you have already sent this user a copy.

For an executable, the required form of the "work that uses the Library" must include any data and utility programs needed for reproducing the executable from it. However, as a special exception, the materials to be distributed need not include anything that is normally

distributed (in either source or binary form) with the major components (compiler, kernel, and so on) of the operating system on which the executable runs, unless that component itself accompanies the executable.

It may happen that this requirement contradicts the license restrictions of other proprietary libraries that do not normally accompany the operating system. Such a contradiction means you cannot use both them and the Library together in an executable that you distribute.

7. You may place library facilities that are a work based on the Library side-by-side in a single library together with other library facilities not covered by this License, and distribute such a combined library, provided that the separate distribution of the work based on the Library and of the other library facilities is otherwise permitted, and provided that you do these two things:

a) Accompany the combined library with a copy of the same work based on the Library, uncombined with any other library facilities. This must be distributed under the terms of the Sections above.

b) Give prominent notice with the combined library of the fact that part of it is a work based on the Library, and explaining where to find the accompanying uncombined form of the same work.

8. You may not copy, modify, sublicense, link with, or distribute the Library except as expressly provided under this License. Any attempt otherwise to copy, modify, sublicense, link with, or distribute the Library is void, and will automatically terminate your rights under this License. However, parties who have received copies, or rights, from you under this License will not have their licenses terminated so long as such parties remain in full compliance.

9. You are not required to accept this License, since you have not signed it. However, nothing else grants you permission to modify or distribute the Library or its derivative works. These actions are prohibited by law if you do not accept this License. Therefore, by modifying or distributing the Library (or any work based on the Library), you indicate your acceptance of this License to do so, and all its terms and conditions for copying, distributing or modifying the Library or works based on it.

10. Each time you redistribute the Library (or any work based on the Library), the recipient automatically receives a license from the original licensor to copy, distribute, link with or modify the Library subject to these terms and conditions. You may not impose any further restrictions on the recipients' exercise of the rights granted herein. You are not responsible for enforcing compliance by third parties with this License.

11. If, as a consequence of a court judgment or allegation of patent infringement or for any other reason (not limited to patent issues), conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot distribute so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not distribute the Library at all. For example, if a patent license would not permit royalty-free redistribution of the Library by all those who receive copies directly or indirectly through you, then the only way you could satisfy both it and this License would be to refrain entirely from distribution of the Library.

If any portion of this section is held invalid or unenforceable under any particular circumstance, the balance of the section is intended to apply, and the section as a whole is intended to apply in other circumstances.

It is not the purpose of this section to induce you to infringe any patents or other property right claims or to contest validity of any such claims; this section has the sole purpose of protecting the integrity of the free software distribution system which is implemented by public license practices. Many people have made generous contributions to the wide range of software distributed through that system in reliance on consistent application of that system; it is up to the author/donor to decide if he or she is willing to distribute software through any other system and a licensee cannot

impose that choice.

This section is intended to make thoroughly clear what is believed to be a consequence of the rest of this License.

12. If the distribution and/or use of the Library is restricted in certain countries either by patents or by copyrighted interfaces, the original copyright holder who places the Library under this License may add an explicit geographical distribution limitation excluding those countries, so that distribution is permitted only in or among countries not thus excluded. In such case, this License incorporates the limitation as if written in the body of this License.

13. The Free Software Foundation may publish revised and/or new versions of the Lesser General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Library specifies a version number of this License which applies to it and "any later version", you have the option of following the terms and conditions either of that version or of any later version published by the Free Software Foundation. If the Library does not specify a license version number, you may choose any version ever published by the Free Software Foundation.

14. If you wish to incorporate parts of the Library into other free programs whose distribution conditions are incompatible with these, write to the author to ask for permission. For software which is copyrighted by the Free Software Foundation, write to the Free Software Foundation; we sometimes make exceptions for this. Our decision will be guided by the two goals of preserving the free status of all derivatives of our free software and of promoting the sharing and reuse of software generally.

NO WARRANTY

15. BECAUSE THE LIBRARY IS LICENSED FREE OF CHARGE, THERE IS NO WARRANTY FOR THE LIBRARY, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE LIBRARY "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE LIBRARY IS WITH YOU. SHOULD THE LIBRARY PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

16. IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY AND/OR REDISTRIBUTE THE LIBRARY AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE LIBRARY (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE LIBRARY TO OPERATE WITH ANY OTHER SOFTWARE), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Libraries

If you develop a new library, and you want it to be of the greatest possible use to the public, we recommend making it free software that everyone can redistribute and change. You can do so by permitting redistribution under these terms (or, alternatively, under the terms of the ordinary General Public License).

To apply these terms, attach the following notices to the library. It is safest to attach them to the start of each source file to most effectively convey the exclusion of warranty; and each file should have at least the "copyright" line and a pointer to where the full notice is found.

<one line to give the library's name and a brief idea of what it does.>
Copyright (C) <year> <name of author>

This library is free software; you can redistribute it and/or modify it under the terms of the GNU Lesser General Public License as published by the Free Software Foundation; either version 2.1 of the License, or (at your option) any later version.

This library is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU Lesser General Public License for more details.

You should have received a copy of the GNU Lesser General Public License along with this library; if not, write to the Free Software Foundation, Inc., 51 Franklin St, Fifth Floor, Boston, MA 02110-1301

USA

Also add information on how to contact you by electronic and paper mail.

You should also get your employer (if you work as a programmer) or your school, if any, to sign a "copyright disclaimer" for the library, if necessary. Here is a sample; alter the names:

Yoyodyne, Inc., hereby disclaims all copyright interest in the library `Frob' (a library for tweaking knobs) written by James Random Hacker.

<signature of Ty Coon>, 1 April 1990
Ty Coon, President of Vice

That's all there is to it!

1.30 libprocps6 2:3.3.12-3ubuntu1.2

1.30.1 Available under license :

GNU GENERAL PUBLIC LICENSE
Version 2, June 1991

Copyright (C) 1989, 1991 Free Software Foundation, Inc.,
51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA
Everyone is permitted to copy and distribute verbatim copies
of this license document, but changing it is not allowed.

Preamble

The licenses for most software are designed to take away your freedom to share and change it. By contrast, the GNU General Public License is intended to guarantee your freedom to share and change free software--to make sure the software is free for all its users. This General Public License applies to most of the Free Software Foundation's software and to any other program whose authors commit to using it. (Some other Free Software Foundation software is covered by the GNU Lesser General Public License instead.) You can apply it to your programs, too.

When we speak of free software, we are referring to freedom, not price.

Our General Public Licenses are designed to make sure that you have the freedom to distribute copies of free software (and charge for this service if you wish), that you receive source code or can get it if you want it, that you can change the software or use pieces of it in new free programs; and that you know you can do these things.

To protect your rights, we need to make restrictions that forbid anyone to deny you these rights or to ask you to surrender the rights. These restrictions translate to certain responsibilities for you if you distribute copies of the software, or if you modify it.

For example, if you distribute copies of such a program, whether gratis or for a fee, you must give the recipients all the rights that you have. You must make sure that they, too, receive or can get the source code. And you must show them these terms so they know their rights.

We protect your rights with two steps: (1) copyright the software, and (2) offer you this license which gives you legal permission to copy, distribute and/or modify the software.

Also, for each author's protection and ours, we want to make certain that everyone understands that there is no warranty for this free software. If the software is modified by someone else and passed on, we want its recipients to know that what they have is not the original, so that any problems introduced by others will not reflect on the original authors' reputations.

Finally, any free program is threatened constantly by software patents. We wish to avoid the danger that redistributors of a free program will individually obtain patent licenses, in effect making the program proprietary. To prevent this, we have made it clear that any patent must be licensed for everyone's free use or not licensed at all.

The precise terms and conditions for copying, distribution and modification follow.

GNU GENERAL PUBLIC LICENSE TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

0. This License applies to any program or other work which contains a notice placed by the copyright holder saying it may be distributed under the terms of this General Public License. The "Program", below, refers to any such program or work, and a "work based on the Program" means either the Program or any derivative work under copyright law: that is to say, a work containing the Program or a portion of it, either verbatim or with modifications and/or translated into another language. (Hereinafter, translation is included without limitation in the term "modification".) Each licensee is addressed as "you".

Activities other than copying, distribution and modification are not covered by this License; they are outside its scope. The act of

running the Program is not restricted, and the output from the Program is covered only if its contents constitute a work based on the Program (independent of having been made by running the Program). Whether that is true depends on what the Program does.

1. You may copy and distribute verbatim copies of the Program's source code as you receive it, in any medium, provided that you conspicuously and appropriately publish on each copy an appropriate copyright notice and disclaimer of warranty; keep intact all the notices that refer to this License and to the absence of any warranty; and give any other recipients of the Program a copy of this License along with the Program.

You may charge a fee for the physical act of transferring a copy, and you may at your option offer warranty protection in exchange for a fee.

2. You may modify your copy or copies of the Program or any portion of it, thus forming a work based on the Program, and copy and distribute such modifications or work under the terms of Section 1 above, provided that you also meet all of these conditions:

a) You must cause the modified files to carry prominent notices stating that you changed the files and the date of any change.

b) You must cause any work that you distribute or publish, that in whole or in part contains or is derived from the Program or any part thereof, to be licensed as a whole at no charge to all third parties under the terms of this License.

c) If the modified program normally reads commands interactively when run, you must cause it, when started running for such interactive use in the most ordinary way, to print or display an announcement including an appropriate copyright notice and a notice that there is no warranty (or else, saying that you provide a warranty) and that users may redistribute the program under these conditions, and telling the user how to view a copy of this License. (Exception: if the Program itself is interactive but does not normally print such an announcement, your work based on the Program is not required to print an announcement.)

These requirements apply to the modified work as a whole. If identifiable sections of that work are not derived from the Program, and can be reasonably considered independent and separate works in themselves, then this License, and its terms, do not apply to those sections when you distribute them as separate works. But when you

distribute the same sections as part of a whole which is a work based on the Program, the distribution of the whole must be on the terms of this License, whose permissions for other licensees extend to the entire whole, and thus to each and every part regardless of who wrote it.

Thus, it is not the intent of this section to claim rights or contest your rights to work written entirely by you; rather, the intent is to exercise the right to control the distribution of derivative or collective works based on the Program.

In addition, mere aggregation of another work not based on the Program with the Program (or with a work based on the Program) on a volume of a storage or distribution medium does not bring the other work under the scope of this License.

3. You may copy and distribute the Program (or a work based on it, under Section 2) in object code or executable form under the terms of Sections 1 and 2 above provided that you also do one of the following:

a) Accompany it with the complete corresponding machine-readable source code, which must be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange; or,

b) Accompany it with a written offer, valid for at least three years, to give any third party, for a charge no more than your cost of physically performing source distribution, a complete machine-readable copy of the corresponding source code, to be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange; or,

c) Accompany it with the information you received as to the offer to distribute corresponding source code. (This alternative is allowed only for noncommercial distribution and only if you received the program in object code or executable form with such an offer, in accord with Subsection b above.)

The source code for a work means the preferred form of the work for making modifications to it. For an executable work, complete source code means all the source code for all modules it contains, plus any associated interface definition files, plus the scripts used to control compilation and installation of the executable. However, as a special exception, the source code distributed need not include anything that is normally distributed (in either source or binary form) with the major components (compiler, kernel, and so on) of the operating system on which the executable runs, unless that component itself accompanies the executable.

If distribution of executable or object code is made by offering access to copy from a designated place, then offering equivalent access to copy the source code from the same place counts as distribution of the source code, even though third parties are not compelled to copy the source along with the object code.

4. You may not copy, modify, sublicense, or distribute the Program except as expressly provided under this License. Any attempt otherwise to copy, modify, sublicense or distribute the Program is void, and will automatically terminate your rights under this License. However, parties who have received copies, or rights, from you under this License will not have their licenses terminated so long as such parties remain in full compliance.

5. You are not required to accept this License, since you have not signed it. However, nothing else grants you permission to modify or distribute the Program or its derivative works. These actions are prohibited by law if you do not accept this License. Therefore, by modifying or distributing the Program (or any work based on the Program), you indicate your acceptance of this License to do so, and all its terms and conditions for copying, distributing or modifying the Program or works based on it.

6. Each time you redistribute the Program (or any work based on the Program), the recipient automatically receives a license from the original licensor to copy, distribute or modify the Program subject to these terms and conditions. You may not impose any further restrictions on the recipients' exercise of the rights granted herein. You are not responsible for enforcing compliance by third parties to this License.

7. If, as a consequence of a court judgment or allegation of patent infringement or for any other reason (not limited to patent issues), conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot distribute so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not distribute the Program at all. For example, if a patent license would not permit royalty-free redistribution of the Program by all those who receive copies directly or indirectly through you, then the only way you could satisfy both it and this License would be to refrain entirely from distribution of the Program.

If any portion of this section is held invalid or unenforceable under

any particular circumstance, the balance of the section is intended to apply and the section as a whole is intended to apply in other circumstances.

It is not the purpose of this section to induce you to infringe any patents or other property right claims or to contest validity of any such claims; this section has the sole purpose of protecting the integrity of the free software distribution system, which is implemented by public license practices. Many people have made generous contributions to the wide range of software distributed through that system in reliance on consistent application of that system; it is up to the author/donor to decide if he or she is willing to distribute software through any other system and a licensee cannot impose that choice.

This section is intended to make thoroughly clear what is believed to be a consequence of the rest of this License.

8. If the distribution and/or use of the Program is restricted in certain countries either by patents or by copyrighted interfaces, the original copyright holder who places the Program under this License may add an explicit geographical distribution limitation excluding those countries, so that distribution is permitted only in or among countries not thus excluded. In such case, this License incorporates the limitation as if written in the body of this License.

9. The Free Software Foundation may publish revised and/or new versions of the General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Program specifies a version number of this License which applies to it and "any later version", you have the option of following the terms and conditions either of that version or of any later version published by the Free Software Foundation. If the Program does not specify a version number of this License, you may choose any version ever published by the Free Software Foundation.

10. If you wish to incorporate parts of the Program into other free programs whose distribution conditions are different, write to the author to ask for permission. For software which is copyrighted by the Free Software Foundation, write to the Free Software Foundation; we sometimes make exceptions for this. Our decision will be guided by the two goals of preserving the free status of all derivatives of our free software and of promoting the sharing and reuse of software generally.

NO WARRANTY

11. BECAUSE THE PROGRAM IS LICENSED FREE OF CHARGE, THERE IS NO WARRANTY FOR THE PROGRAM, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE PROGRAM "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE PROGRAM IS WITH YOU. SHOULD THE PROGRAM PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

12. IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY AND/OR REDISTRIBUTE THE PROGRAM AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE PROGRAM (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE PROGRAM TO OPERATE WITH ANY OTHER PROGRAMS), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Programs

If you develop a new program, and you want it to be of the greatest possible use to the public, the best way to achieve this is to make it free software which everyone can redistribute and change under these terms.

To do so, attach the following notices to the program. It is safest to attach them to the start of each source file to most effectively convey the exclusion of warranty; and each file should have at least the "copyright" line and a pointer to where the full notice is found.

<one line to give the program's name and a brief idea of what it does.>
Copyright (C) <year> <name of author>

This program is free software; you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation; either version 2 of the License, or (at your option) any later version.

This program is distributed in the hope that it will be useful,

but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details.

You should have received a copy of the GNU General Public License along with this program; if not, write to the Free Software Foundation, Inc., 51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA.

Also add information on how to contact you by electronic and paper mail.

If the program is interactive, make it output a short notice like this when it starts in an interactive mode:

```
Gnomovision version 69, Copyright (C) year name of author
Gnomovision comes with ABSOLUTELY NO WARRANTY; for details type `show w'.
This is free software, and you are welcome to redistribute
it
under certain conditions; type `show c' for details.
```

The hypothetical commands `show w' and `show c' should show the appropriate parts of the General Public License. Of course, the commands you use may be called something other than `show w' and `show c'; they could even be mouse-clicks or menu items--whatever suits your program.

You should also get your employer (if you work as a programmer) or your school, if any, to sign a "copyright disclaimer" for the program, if necessary. Here is a sample; alter the names:

```
Yoyodyne, Inc., hereby disclaims all copyright interest in the program
`Gnomovision' (which makes passes at compilers) written by James Hacker.
```

```
<signature of Ty Coon>, 1 April 1989
Ty Coon, President of Vice
```

This General Public License does not permit incorporating your program into proprietary programs. If your program is a subroutine library, you may consider it more useful to permit linking proprietary applications with the library. If this is what you want to do, use the GNU Lesser General Public License instead of this License.

GNU LIBRARY GENERAL PUBLIC LICENSE
Version 2, June 1991

Copyright (C) 1991 Free Software Foundation, Inc.
51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA
Everyone is permitted to copy and distribute verbatim copies of this license document, but changing it is not allowed.

[This is the first released version of the library GPL. It is numbered 2 because it goes with version 2 of the ordinary GPL.]

Preamble

The licenses for most software are designed to take away your freedom to share and change it. By contrast, the GNU General Public Licenses are intended to guarantee your freedom to share and change free software--to make sure the software is free for all its users.

This license, the Library General Public License, applies to some specially designated Free Software Foundation software, and to any other libraries whose authors decide to use it. You can use it for your libraries, too.

When

we speak of free software, we are referring to freedom, not price. Our General Public Licenses are designed to make sure that you have the freedom to distribute copies of free software (and charge for this service if you wish), that you receive source code or can get it if you want it, that you can change the software or use pieces of it in new free programs; and that you know you can do these things.

To protect your rights, we need to make restrictions that forbid anyone to deny you these rights or to ask you to surrender the rights. These restrictions translate to certain responsibilities for you if you distribute copies of the library, or if you modify it.

For example, if you distribute copies of the library, whether gratis or for a fee, you must give the recipients all the rights that we gave you. You must make sure that they, too, receive or can get the source code. If you link a program with the library, you must provide complete object files to the recipients so that they can relink them with the library, after making changes to the library and recompiling it. And you must show them these terms so they know their rights.

Our method of protecting your rights has two steps: (1) copyright the library, and (2) offer you this license which gives you legal permission to copy, distribute and/or modify the library.

Also, for each distributor's protection, we want to make certain that everyone understands that there is no warranty for this free library. If the library is modified by someone else and passed on, we want its recipients to know that what they have is not the original version, so that any problems introduced by others will not reflect on the original authors' reputations.

Finally, any free program is threatened constantly by software patents. We wish to avoid the danger that companies distributing free software will individually obtain patent licenses, thus in effect transforming the program into proprietary software. To prevent this, we have made it clear that any patent must be licensed for everyone's free use or not licensed at all.

Most GNU software, including some libraries, is covered by the ordinary GNU General Public License, which was designed for utility programs. This license, the GNU Library General Public License, applies to certain designated libraries. This license is quite different from the ordinary one; be sure to read it in full, and don't assume that anything in it is the same as in the ordinary license.

The reason we have a separate public license for some libraries is that they blur the distinction we usually make between modifying or adding to a program and simply using it. Linking a program with a library, without changing the library, is in some sense simply using the library, and is analogous to running a utility program or application program. However, in a textual and legal sense, the linked executable is a combined work, a derivative of the original library, and the ordinary General Public License treats it as such.

Because of this blurred distinction, using the ordinary General Public License for libraries did not effectively promote software sharing, because most developers did not use the libraries. We concluded that weaker conditions might promote sharing better.

However, unrestricted linking of non-free programs would deprive the users of those programs of all benefit from the free status of the libraries themselves. This Library General Public License is intended to permit developers of non-free programs to use free libraries, while preserving your freedom as a user of such programs to change the free libraries that are incorporated in them. (We have not seen how to achieve this as regards changes in header files, but we have achieved it as regards changes in the actual functions of the Library.) The hope is that this will lead to faster development of free libraries.

The precise terms and conditions for copying, distribution and modification follow. Pay close attention to the difference between a "work based on the library" and a "work that uses the library". The former contains code derived from the library, while the latter only works together with the library.

Note that it is possible for a library to be covered by the ordinary

General Public License rather than by this special one.

GNU LIBRARY GENERAL PUBLIC LICENSE
TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

0. This License Agreement applies to any software library which contains a notice placed by the copyright holder or other authorized party saying it may be distributed under the terms of this Library General Public License (also called "this License"). Each licensee is addressed as "you".

A "library" means a collection of software functions and/or data prepared so as to be conveniently linked with application programs (which use some of those functions and data) to form executables.

The "Library", below, refers to any such software library or work which has been distributed under these terms. A "work based on the Library" means either the Library or any derivative work under copyright law: that is to say, a work containing the Library or a portion of it, either verbatim or with modifications and/or translated straightforwardly into another language. (Hereinafter, translation is included without limitation in the term "modification".)

"Source code" for a work means the preferred form of the work for making modifications to it. For a library, complete source code means all the source code for all modules it contains, plus any associated interface definition files, plus the scripts used to control compilation and installation of the library.

Activities other than copying, distribution and modification are not covered by this License; they are outside its scope. The act of running a program using the Library is not restricted, and output from such a program is covered only if its contents constitute a work based on the Library (independent of the use of the Library in a tool for writing it). Whether that is true depends on what the Library does and what the program that uses the Library does.

1. You may copy and distribute verbatim copies of the Library's complete source code as you receive it, in any medium, provided that you conspicuously and appropriately publish on each copy an appropriate copyright notice and disclaimer of warranty; keep intact all the notices that refer to this License and to the absence of any warranty; and distribute a copy of this License along with the Library.

You may charge a fee for the physical act of transferring a copy,

and you may at your option offer warranty protection in exchange for a fee.

2. You may modify your copy or copies of the Library or any portion of it, thus forming a work based on the Library, and copy and distribute such modifications or work under the terms of Section 1 above, provided that you also meet all of these conditions:

- a) The modified work must itself be a software library.
- b) You must cause the files modified to carry prominent notices stating that you changed the files and the date of any change.
- c) You must cause the whole of the work to be licensed at no charge to all third parties under the terms of this License.
- d) If a facility in the modified Library refers to a function or a table of data to be supplied by an application program that uses the facility, other than as an argument passed when the facility is invoked, then you must make a good faith effort to ensure that, in the event an application does not supply such function or table, the facility still operates, and performs whatever part of its purpose remains meaningful.

(For example, a function in a library to compute square roots has a purpose that is entirely well-defined independent of the application. Therefore, Subsection 2d requires that any application-supplied function or table used by this function must be optional: if the application does not supply it, the square root function must still compute square roots.)

These requirements apply to the modified work as a whole. If identifiable sections of that work are not derived from the Library, and can be reasonably considered independent and separate works in themselves, then this License, and its terms, do not apply to those sections when you distribute them as separate works. But when you distribute the same sections as part of a whole which is a work based on the Library, the distribution of the whole must be on the terms of this License, whose permissions for other licensees extend to the entire whole, and thus to each and every part regardless of who wrote it.

Thus, it is not the intent of this section to claim rights or contest your rights to work written entirely by you; rather, the intent is to exercise the right to control the distribution of

derivative or
collective works based on the Library.

In addition, mere aggregation of another work not based on the Library with the Library (or with a work based on the Library) on a volume of a storage or distribution medium does not bring the other work under the scope of this License.

3. You may opt to apply the terms of the ordinary GNU General Public License instead of this License to a given copy of the Library. To do this, you must alter all the notices that refer to this License, so that they refer to the ordinary GNU General Public License, version 2, instead of to this License. (If a newer version than version 2 of the ordinary GNU General Public License has appeared, then you can specify that version instead if you wish.) Do not make any other change in these notices.

Once this change is made in a given copy, it is irreversible for that copy, so the ordinary GNU General Public License applies to all subsequent copies and derivative works made from that copy.

This option is useful when you wish to copy part of the code of the Library into a program that is not a library.

4. You may copy and distribute the Library (or a portion or derivative of it, under Section 2) in object code or executable form under the terms of Sections 1 and 2 above provided that you accompany it with the complete corresponding machine-readable source code, which must be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange.

If distribution of object code is made by offering access to copy from a designated place, then offering equivalent access to copy the source code from the same place satisfies the requirement to distribute the source code, even though third parties are not compelled to copy the source along with the object code.

5. A program that contains no derivative of any portion of the Library, but is designed to work with the Library by being compiled or linked with it, is called a "work that uses the Library". Such a work, in isolation, is not a derivative work of the Library, and therefore falls outside the scope of this License.

However, linking a "work that uses the Library" with the Library creates an executable that is a derivative of the Library (because it contains portions of the Library), rather than a "work that uses the

library". The executable is therefore covered by this License. Section 6 states terms for distribution of such executables.

When a "work that uses the Library" uses material from a header file that is part of the Library, the object code for the work may be a derivative work of the Library even though the source code is not. Whether this is true is especially significant if the work can be linked without the Library, or if the work is itself a library. The threshold for this to be true is not precisely defined by law.

If such an object file uses only numerical parameters, data structure layouts and accessors, and small macros and small inline functions (ten lines or less in length), then the use of the object file is unrestricted, regardless of whether it is legally a derivative work. (Executables containing this object code plus portions of the Library will still fall under Section 6.)

Otherwise, if the work is a derivative of the Library, you may distribute the object code for the work under the terms of Section 6. Any executables containing that work also fall under Section 6, whether or not they are linked directly with the Library itself.

6. As an exception to the Sections above, you may also compile or link a "work that uses the Library" with the Library to produce a work containing portions of the Library, and distribute that work under terms of your choice, provided that the terms permit modification of the work for the customer's own use and reverse engineering for debugging such modifications.

You must give prominent notice with each copy of the work that the Library is used in it and that the Library and its use are covered by this License. You must supply a copy of this License. If the work during execution displays copyright notices, you must include the copyright notice for the Library among them, as well as a reference directing the user to the copy of this License. Also, you must do one of these things:

- a) Accompany the work with the complete corresponding machine-readable source code for the Library including whatever changes were used in the work (which must be distributed under Sections 1 and 2 above); and, if the work is an executable linked with the Library, with the complete machine-readable "work that uses the Library", as object code and/or source code, so that the user can modify the Library and then relink to produce a modified executable containing the modified Library. (It is understood that the user who changes the contents of definitions files in the

Library will not necessarily be able to recompile the application to use the modified definitions.)

b) Accompany the work with a written offer, valid for at least three years, to give the same user the materials specified in Subsection 6a, above, for a charge no more than the cost of performing this distribution.

c) If distribution of the work is made by offering access to copy from a designated place, offer equivalent access to copy the above specified materials from the same place.

d) Verify that the user has already received a copy of these materials or that you have already sent this user a copy.

For an executable, the required form of the "work that uses the Library" must include any data and utility programs needed for reproducing the executable from it. However, as a special exception, the source code distributed need not include anything that is normally distributed (in either source or binary form) with the major components (compiler, kernel, and so on) of the operating system on which the executable runs, unless that component itself accompanies the executable.

It may happen that this requirement contradicts the license restrictions of other proprietary libraries that do not normally accompany the operating system. Such a contradiction means you cannot use both them and the Library together in an executable that you distribute.

7. You may place library facilities that are a work based on the Library side-by-side in a single library together with other library facilities not covered by this License, and distribute such a combined library, provided that the separate distribution of the work based on the Library and of the other library facilities is otherwise permitted, and provided that you do these two things:

a) Accompany the combined library with a copy of the same work based on the Library, uncombined with any other library facilities. This must be distributed under the terms of the Sections above.

b) Give prominent notice with the combined library of the fact that part of it is a work based on the Library, and explaining where to find the accompanying uncombined form of the same work.

8. You may not copy, modify, sublicense, link with, or distribute the Library except as expressly provided under this License. Any attempt otherwise to copy, modify, sublicense, link with, or distribute the Library is void, and will automatically terminate your rights under this License. However, parties who have received copies, or rights, from you under this License will not have their licenses terminated so long as such parties remain in full compliance.

9. You are not required to accept this License, since you have not signed it. However, nothing else grants you permission to modify or distribute the Library or its derivative works. These actions are prohibited by law if you do not accept this License. Therefore, by modifying or distributing the Library (or any work based on the Library), you indicate your acceptance of this License to do so, and all its terms and conditions for copying, distributing or modifying the Library or works based on it.

10. Each time you redistribute the Library (or any work based on the Library), the recipient automatically receives a license from the original licensor to copy, distribute, link with or modify the Library subject to these terms and conditions. You may not impose any further restrictions on the recipients' exercise of the rights granted herein. You are not responsible for enforcing compliance by third parties to this License.

11. If, as a consequence of a court judgment or allegation of patent infringement or for any other reason (not limited to patent issues), conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot distribute so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not distribute the Library at all. For example, if a patent license would not permit royalty-free redistribution of the Library by all those who receive copies directly or indirectly through you, then the only way you could satisfy both it and this License would be to refrain entirely from distribution of the Library.

If any portion of this section is held invalid or unenforceable under any particular circumstance, the balance of the section is intended to apply, and the section as a whole is intended to apply in other circumstances.

It is not the purpose of this section to induce you to infringe any patents or other property right claims or to contest validity of any such claims; this section has the sole purpose of protecting the integrity of the free software distribution system which is

implemented by public license practices. Many people have made generous contributions to the wide range of software distributed through that system in reliance on consistent application of that system; it is up to the author/donor to decide if he or she is willing to distribute software through any other system and a licensee cannot impose that choice.

This section is intended to make thoroughly clear what is believed to be a consequence of the rest of this License.

12. If the distribution and/or use of the Library is restricted in certain countries either by patents or by copyrighted interfaces, the original copyright holder who places the Library under this License may add an explicit geographical distribution limitation excluding those countries, so that distribution is permitted only in or among countries not thus excluded. In such case, this License incorporates the limitation as if written in the body of this License.

13. The Free Software Foundation may publish revised and/or new versions of the Library General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Library specifies a version number of this License which applies to it and "any later version", you have the option of following the terms and conditions either of that version or of any later version published by the Free Software Foundation. If the Library does not specify a license version number, you may choose any version ever published by the Free Software Foundation.

14. If you wish to incorporate parts of the Library into other free programs whose distribution conditions are incompatible with these, write to the author to ask for permission. For software which is copyrighted by the Free Software Foundation, write to the Free Software Foundation; we sometimes make exceptions for this. Our decision will be guided by the two goals of preserving the free status of all derivatives of our free software and of promoting the sharing and reuse of software generally.

NO WARRANTY

15. BECAUSE THE LIBRARY IS LICENSED FREE OF CHARGE, THERE IS NO WARRANTY FOR THE LIBRARY, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR

OTHER PARTIES PROVIDE THE LIBRARY "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE LIBRARY IS WITH YOU. SHOULD THE LIBRARY PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

16. IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY AND/OR REDISTRIBUTE THE LIBRARY AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE LIBRARY

(INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE LIBRARY TO OPERATE WITH ANY OTHER SOFTWARE), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Libraries

If you develop a new library, and you want it to be of the greatest possible use to the public, we recommend making it free software that everyone can redistribute and change. You can do so by permitting redistribution under these terms (or, alternatively, under the terms of the ordinary General Public License).

To apply these terms, attach the following notices to the library. It is safest to attach them to the start of each source file to most effectively convey the exclusion of warranty; and each file should have at least the "copyright" line and a pointer to where the full notice is found.

<one line to give the library's name and a brief idea of what it does.>

Copyright (C) <year> <name of author>

This library is free software; you can redistribute it and/or modify it under the terms of the GNU Library General Public License as published by the Free Software Foundation; either version 2 of the License, or (at your option) any later version.

This library is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU Library General Public License for more details.

You should have received a copy of the GNU Library General Public License along with this library; if not, write to the Free Software Foundation, Inc., 51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA

Also add information on how to contact you by electronic and paper mail.

You should also get your employer (if you work as a programmer) or your school, if any, to sign a "copyright disclaimer" for the library, if necessary. Here is a sample; alter the names:

Yoyodyne, Inc., hereby disclaims all copyright interest in the library `Frob' (a library for tweaking knobs) written by James Random Hacker.

<signature of Ty Coon>, 1 April 1990
Ty Coon, President of Vice

That's all there is to it!

1.31 attr 1:2.4.47-2build1

1.31.1 Available under license :

This package was debianized by Nathan Scott nathans@debian.org on Sun, 19 Nov 2000 07:37:09 -0500.

It can be downloaded from <ftp://oss.sgi.com/projects/xfs/download/>

Copyright:

Copyright (C) 2001-2002 Silicon Graphics, Inc. All Rights Reserved.
Copyright (C) 2001 Andreas Gruenbacher.

You are free to distribute this software under Version 2.1 of the GNU Lesser General Public License.
On Debian systems, refer to `/usr/share/common-licenses/LGPL-2.1` for the complete text of the GNU Lesser General Public License.

Certain components (as annotated in the source) are licensed under version 2 of the terms of the GNU General Public License.
On Debian systems, the complete text of the GNU General Public License can be found in `/usr/share/common-licenses/GPL` file.
Most components of the "attr" package are licensed under Version 2.1 of the GNU Lesser General Public License (see below).
below.

Some components (as annotated in the source) are licensed under Version 2 of the GNU General Public License (see COPYING).

GNU LESSER GENERAL PUBLIC LICENSE

Version 2.1, February 1999

Copyright (C) 1991, 1999 Free Software Foundation, Inc.
51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA
Everyone is permitted to copy and distribute verbatim copies
of this license document, but changing it is not allowed.

[This is the first released version of the Lesser GPL. It also counts
as the successor of the GNU Library Public License, version 2, hence
the version number 2.1.]

Preamble

The licenses for most software are designed to take away your
freedom to share and change it. By contrast, the GNU General Public
Licenses are intended to guarantee your
freedom to share and change
free software--to make sure the software is free for all its users.

This license, the Lesser General Public License, applies to some
specially designated software packages--typically libraries--of the
Free Software Foundation and other authors who decide to use it. You
can use it too, but we suggest you first think carefully about whether
this license or the ordinary General Public License is the better
strategy to use in any particular case, based on the explanations below.

When we speak of free software, we are referring to freedom of use,
not price. Our General Public Licenses are designed to make sure that
you have the freedom to distribute copies of free software (and charge
for this service if you wish); that you receive source code or can get
it if you want it; that you can change the software and use pieces of
it in new free programs; and that you are informed that you can do
these things.

To protect your rights, we need to make restrictions
that forbid
distributors to deny you these rights or to ask you to surrender these
rights. These restrictions translate to certain responsibilities for
you if you distribute copies of the library or if you modify it.

For example, if you distribute copies of the library, whether gratis
or for a fee, you must give the recipients all the rights that we gave
you. You must make sure that they, too, receive or can get the source
code. If you link other code with the library, you must provide

complete object files to the recipients, so that they can relink them with the library after making changes to the library and recompiling it. And you must show them these terms so they know their rights.

We protect your rights with a two-step method: (1) we copyright the library, and (2) we offer you this license, which gives you legal permission to copy, distribute and/or modify the library.

To protect each distributor, we want to make it very clear that there is no warranty for the free library. Also, if the library is modified by someone else and passed on, the recipients should know that what they have is not the original version, so that the original author's reputation will not be affected by problems that might be introduced by others.

Finally, software patents pose a constant threat to the existence of any free program. We wish to make sure that a company cannot effectively restrict the users of a free program by obtaining a restrictive license from a patent holder. Therefore, we insist that any patent license obtained for a version of the library must be consistent with the full freedom of use specified in this license.

Most GNU software, including some libraries, is covered by the ordinary GNU General Public License. This license, the GNU Lesser General Public License, applies to certain designated libraries, and is quite different from the ordinary General Public License. We use this license for certain libraries in order to permit linking those libraries into non-free programs.

When a program is linked with a library, whether statically or using a shared library, the combination of the two is legally speaking a combined work, a derivative of the original library. The ordinary General Public License therefore permits such linking only if the entire combination fits its criteria of freedom. The Lesser General Public License permits more lax criteria for linking other code with the library.

We call this license the "Lesser" General Public License because it does Less to protect the user's freedom than the ordinary General Public License. It also provides other free software developers Less of an advantage over competing non-free programs. These disadvantages are the reason we use the ordinary General Public License for many libraries. However, the Lesser license provides advantages in certain special circumstances.

For example, on rare occasions, there may be a special need to

encourage the widest possible use of a certain library, so that it becomes a de-facto standard. To achieve this, non-free programs must be allowed to use the library. A more frequent case is that a free library does the same job as widely used non-free libraries. In this case, there is little to gain by limiting the free library to free software only, so we use the Lesser General Public License.

In other cases, permission to use a particular library in non-free programs enables a greater number of people to use a large body of free software. For example, permission to use the GNU C Library in non-free programs enables many more people to use the whole GNU operating system, as well as its variant, the GNU/Linux operating system.

Although the Lesser General Public License is Less protective of the users' freedom, it does ensure that the user of a program that is linked with the Library has the freedom and the wherewithal to run that program using a modified version of the Library.

The precise terms and conditions for copying, distribution and modification follow. Pay close attention to the difference between a "work based on the library" and a "work that uses the library". The former contains code derived from the library, whereas the latter must be combined with the library in order to run.

GNU LESSER GENERAL PUBLIC LICENSE

TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

0. This License Agreement applies to any software library or other program which contains a notice placed by the copyright holder or other authorized party saying it may be distributed under the terms of this Lesser General Public License (also called "this License"). Each licensee is addressed as "you".

A "library" means a collection of software functions and/or data prepared so as to be conveniently linked with application programs (which use some of those functions and data) to form executables.

The "Library", below, refers to any such software library or work which has been distributed under these terms. A "work based on the Library" means either the Library or any derivative work under copyright law: that is to say, a work containing the Library or a portion of it, either verbatim or with modifications and/or translated straightforwardly into another language. (Hereinafter, translation is included without limitation in the term "modification".)

"Source code" for a work means the preferred form of the work for making modifications to it. For a library, complete source code means all the source code for all modules it contains, plus any associated interface definition files, plus the scripts used to control compilation and installation of the library.

Activities other than copying, distribution and modification are not covered by this License; they are outside its scope. The act of running a program using the Library is not restricted, and output from such a program is covered only if its contents constitute a work based on the Library (independent of the use of the Library in a tool for writing it). Whether that is true depends on what the Library does and what the program that uses the Library does.

1. You may copy and distribute verbatim copies of the Library's complete source code as you receive it, in any medium, provided that you conspicuously and appropriately publish on each copy an appropriate copyright notice and disclaimer of warranty; keep intact all the notices that refer to this License and to the absence of any warranty; and distribute a copy of this License along with the Library.

You may charge a fee for the physical act of transferring a copy, and you may at your option offer warranty protection in exchange for a fee.

2. You may modify your copy or copies of the Library or any portion of it, thus forming a work based on the Library, and copy and distribute such modifications or work under the terms of Section 1 above, provided that you also meet all of these conditions:

- a) The modified work must itself be a software library.
- b) You must cause the files modified to carry prominent notices stating that you changed the files and the date of any change.
- c) You must cause the whole of the work to be licensed at no charge to all third parties under the terms of this License.
- d) If a facility in the modified Library refers to a function or a table of data to be supplied by an application program that uses the facility, other than as an argument passed when the facility is invoked, then you must make a good faith effort to ensure that, in the event an application does not supply such function or table, the facility still operates, and performs whatever part of

its purpose remains meaningful.

(For example, a function in a library to compute square roots has a purpose that is entirely well-defined independent of the application. Therefore, Subsection 2d requires that any application-supplied function or table used by this function must be optional: if the application does not supply it, the square root function must still compute square roots.)

These requirements apply to the modified work as a whole. If identifiable sections of that work are not derived from the Library, and can be reasonably considered independent and separate works in themselves, then this License, and its terms, do not apply to those sections when you distribute them as separate works. But when you distribute the same sections as part of a whole which is a work based on the Library, the distribution of the whole must be on the terms of this License, whose permissions for other licensees extend to the entire whole, and thus to each and every part regardless of who wrote it.

Thus, it is not the intent of this section to claim rights or contest your rights to work written entirely by you; rather, the intent is to exercise the right to control the distribution of derivative or collective works based on the Library.

In addition, mere aggregation of another work not based on the Library with the Library (or with a work based on the Library) on a volume of a storage or distribution medium does not bring the other work under the scope of this License.

3. You may opt to apply the terms of the ordinary GNU General Public License instead of this License to a given copy of the Library. To do this, you must alter all the notices that refer to this License, so that they refer to the ordinary GNU General Public License, version 2, instead of to this License. (If a newer version than version 2 of the ordinary GNU General Public License has appeared, then you can specify that version instead if you wish.) Do not make any other change in these notices.

Once this change is made in a given copy, it is irreversible for that copy, so the ordinary GNU General Public License applies to all subsequent copies and derivative works made from that copy.

This option is useful when you wish to copy part of the code of the Library

into a program that is not a library.

4. You may copy and distribute the Library (or a portion or derivative of it, under Section 2) in object code or executable form under the terms of Sections 1 and 2 above provided that you accompany it with the complete corresponding machine-readable source code, which must be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange.

If distribution of object code is made by offering access to copy from a designated place, then offering equivalent access to copy the source code from the same place satisfies the requirement to distribute the source code, even though third parties are not compelled to copy the source along with the object code.

5. A program that contains no derivative of any portion of the Library, but is designed to work with the Library by being compiled or linked with it, is called a "work that uses the Library". Such a work, in isolation, is not a derivative work of the Library, and therefore falls outside the scope of this License.

However, linking a "work that uses the Library" with the Library creates an executable that is a derivative of the Library (because it contains portions of the Library), rather than a "work that uses the library". The executable is therefore covered by this License. Section 6 states terms for distribution of such executables.

When a "work that uses the Library" uses material from a header file that is part of the Library, the object code for the work may be a derivative work of the Library even though the source code is not. Whether this is true is especially significant if the work can be linked without the Library, or if the work is itself a library. The threshold for this to be true is not precisely defined by law.

If such an object file uses only numerical parameters, data structure layouts and accessors, and small macros and small inline functions (ten lines or less in length), then the use of the object file is unrestricted, regardless of whether it is legally a derivative work. (Executables containing this object code plus portions of the Library will still fall under Section 6.)

Otherwise, if the work is a derivative of the Library, you may distribute the object code for the work under the terms of Section 6. Any executables containing that work also fall under Section 6, whether or not they are linked directly with the Library itself.

6. As an exception to the Sections above, you may also combine or link a "work that uses the Library" with the Library to produce a work containing portions of the Library, and distribute that work under terms of your choice, provided that the terms permit modification of the work for the customer's own use and reverse engineering for debugging such modifications.

You must give prominent notice with each copy of the work that the Library is used in it and that the Library and its use are covered by this License. You must supply a copy of this License. If the work during execution displays copyright notices, you must include the copyright notice for the Library among them, as well as a reference directing the user to the copy of this License. Also, you must do one of these things:

a) Accompany the work with the complete corresponding machine-readable source code for the Library including whatever changes were used in the work (which must be distributed under Sections 1 and 2 above); and, if the work is an executable linked with the Library, with the complete machine-readable "work that uses the Library", as object code and/or source code, so that the user can modify the Library and then relink to produce a modified executable containing the modified Library. (It is understood that the user who changes the contents of definitions files in the Library will not necessarily be able to recompile the application to use the modified definitions.)

b) Use a suitable shared library mechanism for linking with the Library. A suitable mechanism is one that (1) uses at run time a copy of the library already present on the user's computer system, rather than copying library functions into the executable, and (2) will operate properly with a modified version of the library, if the user installs one, as long as the modified version is interface-compatible with the version that the work was made with.

c) Accompany the work with a written offer, valid for at least three years, to give the same user the materials specified in Subsection 6a, above, for a charge no more than the cost of performing this distribution.

d) If distribution of the work is made by offering access to copy from a designated place, offer equivalent access to copy the above specified materials from the same place.

e) Verify that the user has already received a copy of these materials or that you have already sent this user a copy.

For an executable, the required form of the "work that uses the Library" must include any data and utility programs needed for reproducing the executable from it. However, as a special exception, the materials to be distributed need not include anything that is normally distributed (in either source or binary form) with the major components (compiler, kernel, and so on) of the operating system on which the executable runs, unless that component itself accompanies the executable.

It may happen that this requirement contradicts the license restrictions of other proprietary libraries that do not normally accompany the operating system. Such a contradiction means you cannot use both them and the Library together in an executable that you distribute.

7. You may place library facilities that are a work based on the Library side-by-side in a single library together with other library facilities not covered by this License, and distribute such a combined library, provided that the separate distribution of the work based on the Library and of the other library facilities is otherwise permitted, and provided that you do these two things:

a) Accompany the combined library with a copy of the same work based on the Library, uncombined with any other library facilities. This must be distributed under the terms of the Sections above.

b) Give prominent notice with the combined library of the fact that part of it is a work based on the Library, and explaining where to find the accompanying uncombined form of the same work.

8. You may not copy, modify, sublicense, link with, or distribute the Library except as expressly provided under this License. Any attempt otherwise to copy, modify, sublicense, link with, or distribute the Library is void, and will automatically terminate your rights under this License. However, parties who have received copies, or rights, from you under this License will not have their licenses terminated so long as such parties remain in full compliance.

9. You are not required to accept this License, since you have not signed it. However, nothing else grants you permission to modify or distribute the Library or its derivative works. These actions are prohibited by law if you do not accept this License. Therefore, by modifying or distributing the Library (or any work based on the Library), you indicate your acceptance of this License to do so, and

all its terms and conditions for copying, distributing or modifying the Library or works based on it.

10. Each time you redistribute the Library (or any work based on the Library), the recipient automatically receives a license from the original licensor to copy, distribute, link with or modify the Library subject to these terms and conditions. You may not impose any further restrictions on the recipients' exercise of the rights granted herein. You are not responsible for enforcing compliance by third parties with this License.

11. If, as a consequence of a court judgment or allegation of patent infringement or for any other reason (not limited to patent issues), conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot distribute so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not distribute the Library at all. For example, if a patent license would not permit royalty-free redistribution of the Library by all those who receive copies directly or indirectly through you, then the only way you could satisfy both it and this License would be to refrain entirely from distribution of the Library.

If any portion of this section is held invalid or unenforceable under any particular circumstance, the balance of the section is intended to apply, and the section as a whole is intended to apply in other circumstances.

It is not the purpose of this section to induce you to infringe any patents or other property right claims or to contest validity of any such claims; this section has the sole purpose of protecting the integrity of the free software distribution system which is implemented by public license practices. Many people have made generous contributions to the wide range of software distributed through that system in reliance on consistent application of that system; it is up to the author/donor to decide if he or she is willing to distribute software through any other system and a licensee cannot impose that choice.

This section is intended to make thoroughly clear what is believed to be a consequence of the rest of this License.

12. If the distribution and/or use of the Library is restricted in certain countries either by patents or by copyrighted interfaces, the original copyright holder who places the Library under this License may add an explicit geographical distribution

limitation excluding those countries,
so that distribution is permitted only in or among countries not thus
excluded. In such case, this License incorporates the limitation as if
written in the body of this License.

13. The Free Software Foundation may publish revised and/or new
versions of the Lesser General Public License from time to time.
Such new versions will be similar in spirit to the present version,
but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Library
specifies a version number of this License which applies to it and
"any later version", you have the option of following the terms and
conditions either of that version or of any later version published by
the Free Software Foundation. If the Library does not specify a
license version number, you may choose any version ever published by
the Free Software Foundation.

14. If you wish to incorporate parts of the Library into other free
programs
whose distribution conditions are incompatible with these,
write to the author to ask for permission. For software which is
copyrighted by the Free Software Foundation, write to the Free
Software Foundation; we sometimes make exceptions for this. Our
decision will be guided by the two goals of preserving the free status
of all derivatives of our free software and of promoting the sharing
and reuse of software generally.

NO WARRANTY

15. BECAUSE THE LIBRARY IS LICENSED FREE OF CHARGE, THERE IS NO
WARRANTY FOR THE LIBRARY, TO THE EXTENT PERMITTED BY APPLICABLE LAW.
EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR
OTHER PARTIES PROVIDE THE LIBRARY "AS IS" WITHOUT WARRANTY OF ANY
KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE
IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR
PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE
LIBRARY IS WITH YOU. SHOULD THE LIBRARY PROVE DEFECTIVE, YOU ASSUME
THE
COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

16. IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN
WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY
AND/OR REDISTRIBUTE THE LIBRARY AS PERMITTED ABOVE, BE LIABLE TO YOU
FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR
CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE
LIBRARY (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING
RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A

FAILURE OF THE LIBRARY TO OPERATE WITH ANY OTHER SOFTWARE), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Libraries

If you develop a new library, and you want it to be of the greatest possible use to the public, we recommend making it free software that everyone can redistribute and change. You can do so by permitting redistribution under these terms (or, alternatively, under the terms of the ordinary General Public License).

To apply these terms, attach the following notices to the library. It is safest to attach them to the start of each source file to most effectively convey the exclusion of warranty; and each file should have at least the "copyright" line and a pointer to where the full notice is found.

```
<one line to give the library's name and a brief idea of what it does.>  
Copyright (C) <year> <name of author>
```

```
This library is free software; you can redistribute it and/or  
modify it under the terms of the GNU Lesser General Public  
License as published by the Free Software Foundation; either  
version 2.1 of the License, or (at your option) any later version.
```

```
This library is distributed in the hope that it will be useful,  
but WITHOUT ANY WARRANTY; without even the implied warranty of  
MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU  
Lesser General Public License  
for more details.
```

```
You should have received a copy of the GNU Lesser General Public  
License along with this library; if not, write to the Free Software  
Foundation, Inc., 51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA
```

Also add information on how to contact you by electronic and paper mail.

You should also get your employer (if you work as a programmer) or your school, if any, to sign a "copyright disclaimer" for the library, if necessary. Here is a sample; alter the names:

```
Yoyodyne, Inc., hereby disclaims all copyright interest in the  
library `Frob' (a library for tweaking knobs) written by James Random Hacker.
```

```
<signature of Ty Coon>, 1 April 1990
```

Ty Coon, President of Vice

That's all there is to it!

Most components of the "attr" package are licensed under
Version 2.1 of the GNU Lesser General Public License (see COPYING.LGPL).

Some components (as annotated in the source) are licensed
under Version 2 of the GNU General Public License (see below),

GNU GENERAL PUBLIC LICENSE

Version 2, June 1991

Copyright (C) 1989, 1991 Free Software Foundation, Inc.,
51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA
Everyone is permitted to copy and distribute verbatim copies
of this license document, but changing it is not allowed.

Preamble

The licenses for most software are designed to take away your
freedom to share and change it. By contrast, the GNU General Public
License is intended to guarantee your freedom to share and change free
software--to make sure the software is free for all its users. This
General Public License applies to most of the Free Software
Foundation's software
and to any other program whose authors commit to
using it. (Some other Free Software Foundation software is covered by
the GNU Lesser General Public License instead.) You can apply it to
your programs, too.

When we speak of free software, we are referring to freedom, not
price. Our General Public Licenses are designed to make sure that you
have the freedom to distribute copies of free software (and charge for
this service if you wish), that you receive source code or can get it
if you want it, that you can change the software or use pieces of it
in new free programs; and that you know you can do these things.

To protect your rights, we need to make restrictions that forbid
anyone to deny you these rights or to ask you to surrender the rights.
These restrictions translate to certain responsibilities for you if you
distribute copies of the software, or if you modify it.

For example, if you distribute copies of such a program, whether
gratis or for a fee, you must give the recipients
all the rights that
you have. You must make sure that they, too, receive or can get the

source code. And you must show them these terms so they know their rights.

We protect your rights with two steps: (1) copyright the software, and (2) offer you this license which gives you legal permission to copy, distribute and/or modify the software.

Also, for each author's protection and ours, we want to make certain that everyone understands that there is no warranty for this free software. If the software is modified by someone else and passed on, we want its recipients to know that what they have is not the original, so that any problems introduced by others will not reflect on the original authors' reputations.

Finally, any free program is threatened constantly by software patents. We wish to avoid the danger that redistributors of a free program will individually obtain patent licenses, in effect making the program proprietary. To prevent this, we have made it clear that any patent must be licensed for everyone's free use or not licensed at all.

The precise terms and conditions for copying, distribution and modification follow.

GNU GENERAL PUBLIC LICENSE TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

0. This License applies to any program or other work which contains a notice placed by the copyright holder saying it may be distributed under the terms of this General Public License. The "Program", below, refers to any such program or work, and a "work based on the Program" means either the Program or any derivative work under copyright law: that is to say, a work containing the Program or a portion of it, either verbatim or with modifications and/or translated into another language. (Hereinafter, translation is included without limitation in the term "modification".) Each licensee is addressed as "you".

Activities other than copying, distribution and modification are not covered by this License; they are outside its scope. The act of running the Program is not restricted, and the output from the Program is covered only if its contents constitute a work based on the Program (independent of having been made by running the Program). Whether that is true depends on what the Program does.

1. You may copy and distribute verbatim copies of the Program's source code as you receive it, in any medium, provided that you conspicuously and appropriately publish on each copy an appropriate

copyright notice and disclaimer of warranty; keep intact all the notices that refer to this License and to the absence of any warranty; and give any other recipients of the Program a copy of this License along with the Program.

You may charge a fee for the physical act of transferring a copy, and you may at your option offer warranty protection in exchange for a fee.

2. You may modify your copy or copies of the Program or any portion of it, thus forming a work based on the Program, and copy and distribute such modifications or work under the terms of Section 1 above, provided that you also meet all of these conditions:

- a) You must cause the modified files to carry prominent notices stating that you changed the files and the date of any change.
- b) You must cause any work that you distribute or publish, that in whole or in part contains or is derived from the Program or any part thereof, to be licensed as a whole at no charge to all third parties under the terms of this License.
- c) If the modified program normally reads commands interactively when run, you must cause it, when started running for such interactive use in the most ordinary way, to print or display an announcement including an appropriate copyright notice and a notice that there is no warranty (or else, saying that you provide a warranty) and that users may redistribute the program under these conditions, and telling the user how to view a copy of this License. (Exception: if the Program itself is interactive but does not normally print such an announcement, your work based on the Program is not required to print an announcement.)

These requirements apply to the modified work as a whole. If identifiable sections of that work are not derived from the Program, and can be reasonably considered independent and separate works in themselves, then this License, and its terms, do not apply to those sections when you distribute them as separate works. But when you distribute the same sections as part of a whole which is a work based on the Program, the distribution of the whole must be on the terms of this License, whose permissions for other licensees extend to the entire whole, and thus to each and every part regardless of who wrote it.

Thus, it is not the intent of this section to claim rights or contest your rights to work written entirely by you; rather, the intent is to exercise the right to control the distribution of derivative or collective works

based on the Program.

In addition, mere aggregation of another work not based on the Program with the Program (or with a work based on the Program) on a volume of a storage or distribution medium does not bring the other work under the scope of this License.

3. You may copy and distribute the Program (or a work based on it, under Section 2) in object code or executable form under the terms of Sections 1 and 2 above provided that you also do one of the following:

a) Accompany it with the complete corresponding machine-readable source code, which must be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange; or,

b) Accompany it with a written offer, valid for at least three years, to give any third party, for a charge no more than your cost of physically performing source distribution, a complete machine-readable copy of the corresponding source code, to be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange; or,

c) Accompany it with the information you received as to the offer to distribute corresponding source code. (This alternative is allowed only for noncommercial distribution and only if you received the program in object code or executable form with such an offer, in accord with Subsection b above.)

The source code for a work means the preferred form of the work for making modifications to it. For an executable work, complete source code means all the source code for all modules it contains, plus any associated interface definition files, plus the scripts used to control compilation and installation of the executable. However, as a special exception, the source code distributed need not include anything that is normally distributed (in either source or binary form) with the major components (compiler, kernel, and so on) of the operating system on which the executable runs, unless that component itself accompanies the executable.

If distribution of executable or object code is made by offering access to copy from a designated place, then offering equivalent access to copy the source code from the same place counts as distribution of the source code, even though third parties are not compelled to copy the source along with the object code.

4. You may not copy, modify, sublicense, or distribute the Program

except as expressly provided under this License. Any attempt otherwise to copy, modify, sublicense or distribute the Program is void, and will automatically terminate your rights under this License. However, parties who have received copies, or rights, from you under this License will not have their licenses terminated so long as such parties remain in full compliance.

5. You are not required to accept this License, since you have not signed it. However, nothing else grants you permission to modify or distribute the Program or its derivative works. These actions are prohibited by law if you do not accept this License. Therefore, by modifying or distributing the Program (or any work based on the Program), you indicate your acceptance of this License to do so, and all its terms and conditions for copying, distributing or modifying the Program or works based on it.

6. Each time you redistribute the Program (or any work based on the Program), the recipient automatically receives a license from the original licensor to copy, distribute or modify the Program subject to these terms and conditions. You may not impose any further restrictions on the recipients' exercise of the rights granted herein. You are not responsible for enforcing compliance by third parties to this License.

7. If, as a consequence of a court judgment or allegation of patent infringement or for any other reason (not limited to patent issues), conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot distribute so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not distribute the Program at all. For example, if a patent license would not permit royalty-free redistribution of the Program by all those who receive copies directly or indirectly through you, then the only way you could satisfy both it and this License would be to refrain entirely from distribution of the Program.

If any portion of this section is held invalid or unenforceable under any particular circumstance, the balance of the section is intended to apply and the section as a whole is intended to apply in other circumstances.

It is not the purpose of this section to induce you to infringe any patents or other property right claims or to contest validity of any such claims; this section has the sole purpose of protecting the integrity of the free software distribution

system, which is implemented by public license practices. Many people have made generous contributions to the wide range of software distributed through that system in reliance on consistent application of that system; it is up to the author/donor to decide if he or she is willing to distribute software through any other system and a licensee cannot impose that choice.

This section is intended to make thoroughly clear what is believed to be a consequence of the rest of this License.

8. If the distribution and/or use of the Program is restricted in certain countries either by patents or by copyrighted interfaces, the original copyright holder who places the Program under this License may add an explicit geographical distribution limitation excluding those countries, so that distribution is permitted only in or among countries not thus excluded. In such case, this License incorporates the limitation as if written in the body of this License.

9. The Free Software Foundation may publish revised and/or new versions of the General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Program specifies a version number of this License which applies to it and "any later version", you have the option of following the terms and conditions either of that version or of any later version published by the Free Software Foundation. If the Program does not specify a version number of this License, you may choose any version ever published by the Free Software Foundation.

10. If you wish to incorporate parts of the Program into other free programs whose distribution conditions are different, write to the author to ask for permission. For software which is copyrighted by the Free Software Foundation, write to the Free Software Foundation; we sometimes make exceptions for this. Our decision will be guided by the two goals of preserving the free status of all derivatives of our free software and of promoting the sharing and reuse of software generally.

NO WARRANTY

11. BECAUSE THE PROGRAM IS LICENSED FREE OF CHARGE, THERE IS NO WARRANTY FOR THE PROGRAM, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE PROGRAM "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED

OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE PROGRAM IS WITH YOU. SHOULD THE PROGRAM PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

12. IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY AND/OR REDISTRIBUTE THE PROGRAM AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE PROGRAM (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE PROGRAM TO OPERATE WITH ANY OTHER PROGRAMS), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Programs

If you develop a new program, and you want it to be of the greatest possible use to the public, the best way to achieve this is to make it free software which everyone can redistribute and change under these terms.

To do so, attach the following notices to the program. It is safest to attach them to the start of each source file to most effectively convey the exclusion of warranty; and each file should have at least the "copyright" line and a pointer to where the full notice is found.

```
<one line to give the program's name and a brief idea of what it does.>  
Copyright (C) <year> <name of author>
```

This program is free software; you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation; either version 2 of the License, or (at your option) any later version.

This program is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details.

You should have received a copy of the GNU General Public License along with this program; if not, write to the Free Software Foundation, Inc., 51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA.

Also add information on how to contact you by electronic and paper mail.

If the program is interactive, make it output a short notice like this when it starts in an interactive mode:

```
Gnomovision version 69, Copyright (C) year name of author
Gnomovision comes with ABSOLUTELY NO WARRANTY; for details type `show w'.
This is free software, and you are welcome to redistribute it
under certain conditions; type `show c' for details.
```

The hypothetical commands ``show w'` and ``show c'` should show the appropriate parts of the General Public License. Of course, the commands you use may be called something other than ``show w'` and ``show c'`; they could even be mouse-clicks or menu items--whatever suits your program.

You should also get your employer (if you work as a programmer) or your school, if any, to sign a "copyright disclaimer" for the program, if necessary. Here is a sample; alter the names:

```
Yoyodyne, Inc., hereby disclaims all copyright interest in the program
`Gnomovision' (which makes passes at compilers) written by James Hacker.
```

```
<signature of Ty Coon>, 1 April 1989
Ty Coon, President of Vice
```

This General Public License does not permit incorporating your program into proprietary programs. If your program is a subroutine library, you may consider it more useful to permit linking proprietary applications with the library. If this is what you want to do, use the GNU Lesser General Public License instead of this License.

1.32 diffutils 1:3.6-1

1.32.1 Available under license :

GNU GENERAL PUBLIC LICENSE
Version 3, 29 June 2007

Copyright (C) 2007 Free Software Foundation, Inc. <<http://fsf.org/>>
Everyone is permitted to copy and distribute verbatim copies of this license document, but changing it is not allowed.

Preamble

The GNU General Public License is a free, copyleft license for software and other kinds of works.

The licenses for most software and other practical works are designed to take away your freedom to share and change the works. By contrast, the GNU General Public License is intended to guarantee your freedom to share and change all versions of a program--to make sure it remains free software for all its users. We, the Free Software Foundation, use the GNU General Public License for most of our software; it applies also to any other work released this way by its authors. You can apply it to your programs, too.

When we speak of free software, we are referring to freedom, not price. Our General Public Licenses are designed to make sure that you have the freedom to distribute copies of free software (and charge for them if you wish), that you receive source code or can get it if you want it, that you can change the software or use pieces of it in new free programs, and that you know you can do these things.

To protect your rights, we need to prevent others from denying you these rights or asking you to surrender the rights. Therefore, you have certain responsibilities if you distribute copies of the software, or if you modify it: responsibilities to respect the freedom of others.

For example, if you distribute copies of such a program, whether gratis or for a fee, you must pass on to the recipients the same freedoms that you received. You must make sure that they, too, receive or can get the source code. And you must show them these terms so they know their rights.

Developers that use the GNU GPL protect your rights with two steps:

- (1) assert copyright on the software, and
- (2) offer you this License giving you legal permission to copy, distribute and/or modify it.

For the developers' and authors' protection, the GPL clearly explains that there is no warranty for this free software. For both users' and authors' sake, the GPL requires that modified versions be marked as changed, so that their problems will not be attributed erroneously to authors of previous versions.

Some devices are designed to deny users access to install or run modified versions of the software inside them, although the manufacturer can do so. This is fundamentally incompatible with the aim of protecting users' freedom to change the software. The systematic pattern of such abuse occurs in the area of products for individuals to use, which is precisely where it is most unacceptable. Therefore, we have designed this version of the GPL to prohibit the practice for those products. If such problems arise substantially in other domains, we

stand

ready to extend this provision to those domains in future versions of the GPL, as needed to protect the freedom of users.

Finally, every program is threatened constantly by software patents. States should not allow patents to restrict development and use of software on general-purpose computers, but in those that do, we wish to avoid the special danger that patents applied to a free program could make it effectively proprietary. To prevent this, the GPL assures that patents cannot be used to render the program non-free.

The precise terms and conditions for copying, distribution and modification follow.

TERMS AND CONDITIONS

0. Definitions.

"This License" refers to version 3 of the GNU General Public License.

"Copyright" also means copyright-like laws that apply to other kinds of works, such as semiconductor masks.

"The Program" refers to any copyrightable work licensed under this License. Each licensee is addressed as "you". "Licensees" and "recipients" may be individuals or organizations.

To "modify" a work means to copy from or adapt all or part of the work in a fashion requiring copyright permission, other than the making of an exact copy. The resulting work is called a "modified version" of the earlier work or a work "based on" the earlier work.

A "covered work" means either the unmodified Program or a work based on the Program.

To "propagate" a work means to do anything with it that, without permission, would make you directly or secondarily liable for infringement under applicable copyright law, except executing it on a computer or modifying a private copy. Propagation includes copying, distribution (with or without modification), making available to the public, and in some countries other activities as well.

To "convey" a work means any kind of propagation that enables other parties to make or receive copies. Mere interaction with a user through a computer network, with no transfer of a copy, is not conveying.

An interactive user interface displays "Appropriate Legal Notices" to the extent that it includes a convenient and prominently visible feature that (1) displays an appropriate copyright notice, and (2) tells the user that there is no warranty for the work (except to the extent that warranties are provided), that licensees may convey the work under this License, and how to view a copy of this License. If the interface presents a list of user commands or options, such as a menu, a prominent item in the list meets this criterion.

1. Source Code.

The "source code" for a work means the preferred form of the work for making modifications to it. "Object code" means any non-source form of a work.

A "Standard Interface" means an interface that either is an official standard defined by a recognized standards body, or, in the case of interfaces specified for a particular programming language, one that is widely used among developers working in that language.

The "System Libraries" of an executable work include anything, other than the work as a whole, that (a) is included in the normal form of packaging a Major Component, but which is not part of that Major Component, and (b) serves only to enable use of the work with that Major Component, or to implement a Standard Interface for which an implementation is available to the public in source code form. A "Major Component", in this context, means a major essential component (kernel, window system, and so on) of the specific operating system (if any) on which the executable work runs, or a compiler used to produce the work, or an object code interpreter used to run it.

The "Corresponding Source" for a work in object code form means all the source code needed to generate, install, and (for an executable work) run the object code and to modify the work, including scripts to control those activities. However, it does not include the work's System Libraries, or general-purpose tools or generally available free programs which are used unmodified in performing those activities but which are not part of the work. For example, Corresponding Source includes interface definition files associated with source files for the work, and the source code for shared libraries and dynamically linked subprograms that the work is specifically designed to require, such as by intimate data communication or control flow between those subprograms and other parts of the work.

The Corresponding Source need not include anything that users can regenerate automatically from other parts of the Corresponding

Source.

The Corresponding Source for a work in source code form is that same work.

2. Basic Permissions.

All rights granted under this License are granted for the term of copyright on the Program, and are irrevocable provided the stated conditions are met. This License explicitly affirms your unlimited permission to run the unmodified Program. The output from running a covered work is covered

by this License only if the output, given its content, constitutes a covered work. This License acknowledges your rights of fair use or other equivalent, as provided by copyright law.

You may make, run and propagate covered works that you do not convey, without conditions so long as your license otherwise remains in force. You may convey covered works to others for the sole purpose of having them make modifications exclusively for you, or provide you with facilities for running those works, provided that you comply with the terms of this License in conveying all material for which you do not control copyright. Those thus making or running the covered works for you must do so exclusively on your behalf, under your direction and control, on terms that prohibit them from making any copies of your copyrighted material outside their relationship with you.

Conveying under any other circumstances is permitted solely under the conditions stated below. Sublicensing is not allowed; section 10 makes it unnecessary.

3. Protecting Users' Legal Rights From Anti-Circumvention Law.

No covered work shall be deemed part of an effective technological measure under any applicable law fulfilling obligations under article 11 of the WIPO copyright treaty adopted on 20 December 1996, or similar laws prohibiting or restricting circumvention of such measures.

When you convey a covered work, you waive any legal power to forbid circumvention of technological measures to the extent such circumvention is effected by exercising rights under this License with respect to the covered work, and you disclaim any intention to limit operation or modification of the work as a means of enforcing, against the work's users, your or third parties' legal rights to forbid circumvention of technological measures.

4. Conveying Verbatim Copies.

You may convey verbatim copies of the Program's source code as you receive it, in any medium, provided that you conspicuously and appropriately
publish on each copy an appropriate copyright notice;
keep intact all notices stating that this License and any non-permissive terms added in accord with section 7 apply to the code;
keep intact all notices of the absence of any warranty; and give all recipients a copy of this License along with the Program.

You may charge any price or no price for each copy that you convey, and you may offer support or warranty protection for a fee.

5. Conveying Modified Source Versions.

You may convey a work based on the Program, or the modifications to produce it from the Program, in the form of source code under the terms of section 4, provided that you also meet all of these conditions:

- a) The work must carry prominent notices stating that you modified it, and giving a relevant date.
- b) The work must carry prominent notices stating that it is released under this License and any conditions added under section 7. This requirement modifies the requirement in section 4 to "keep intact all notices".
- c) You must license the entire work, as a whole, under this License to anyone who comes into possession of a copy. This License will therefore apply, along with any applicable section 7 additional terms, to the whole of the work, and all its parts, regardless of how they are packaged. This License gives no permission to license the work in any other way, but it does not invalidate such permission if you have separately received it.
- d) If the work has interactive user interfaces, each must display Appropriate Legal Notices; however, if the Program has interactive interfaces that do not display Appropriate Legal Notices, your work need not make them do so.

A compilation of a covered work with other separate and independent works, which are not by their nature extensions of the covered work, and which are not combined with it such as to form a larger program, in or on a volume of a storage or distribution medium, is called an "aggregate" if the compilation and its resulting copyright are not

used to limit the access or legal rights of the compilation's users beyond what the individual works permit. Inclusion of a covered work in an aggregate does not cause this License to apply to the other parts of the aggregate.

6. Conveying Non-Source Forms.

You may convey a covered work in object code form under the terms of sections 4 and 5, provided that you also convey the machine-readable Corresponding Source under the terms of this License, in one of these ways:

a) Convey the object code in, or embodied in, a physical product (including a physical distribution medium), accompanied by the Corresponding Source fixed on a durable physical medium customarily used for software interchange.

b) Convey the object code in, or embodied in, a physical product (including a physical distribution medium), accompanied by a written offer, valid for at least three years and valid for as

long as you offer spare parts or customer support for that product model, to give anyone who possesses the object code either (1) a copy of the Corresponding Source for all the software in the product that is covered by this License, on a durable physical medium customarily used for software interchange, for a price no more than your reasonable cost of physically performing this conveying of source, or (2) access to copy the Corresponding Source from a network server at no charge.

c) Convey individual copies of the object code with a copy of the written offer to provide the Corresponding Source. This alternative is allowed only occasionally and noncommercially, and only if you received the object code with such an offer, in accord with subsection 6b.

d) Convey the object code by offering access from a designated place (gratis or for a charge), and offer equivalent access to the Corresponding Source in the same way through the same place at no further charge. You need not require recipients to copy the Corresponding Source along with the object code. If the place to copy the object code is a network server, the Corresponding Source may be on a different server (operated by you or a third party) that supports equivalent copying facilities, provided you maintain clear directions next to the object code saying where to find the Corresponding Source. Regardless of what server hosts the Corresponding Source, you remain obligated to ensure that it is

available for as long as needed to satisfy these requirements.

e) Convey the object code using peer-to-peer transmission, provided you inform other peers where the object code and Corresponding Source of the work are being offered to the general public at no charge under subsection 6d.

A separable portion of the object code, whose source code is excluded from the Corresponding Source as a System Library, need not be included in conveying the object code work.

A "User Product" is either (1) a "consumer product", which means any tangible personal property which is normally used for personal, family, or household purposes, or (2) anything designed or sold for incorporation into a dwelling. In determining whether a product is a consumer product, doubtful cases shall be resolved in favor of coverage. For a particular product received by a particular user, "normally used" refers to a typical or common use of that class of product, regardless of the status of the particular user or of the way in which the particular user actually uses, or expects or is expected to use, the product. A product is a consumer product regardless of whether the product has substantial commercial, industrial or non-consumer uses, unless such uses represent the only significant mode of use of the product.

"Installation Information" for a User Product means any methods, procedures, authorization keys, or other information required to install and execute modified versions of a covered work in that User Product from a modified version of its Corresponding Source. The information must suffice to ensure that the continued functioning of the modified object code is in no case prevented or interfered with solely because modification has been made.

If you convey an object code work under this section in, or with, or specifically for use in, a User Product, and the conveying occurs as part of a transaction in which the right of possession and use of the User Product is transferred to the recipient in perpetuity or for a fixed term (regardless of how the transaction is characterized), the Corresponding Source conveyed under this section must be accompanied by the Installation Information. But this requirement does not apply if neither you nor any third party retains the ability to install modified object code on the User Product (for example, the work has been installed in ROM).

The requirement to provide Installation Information does not include a requirement to continue to provide support service, warranty, or updates

for a work that has been modified or installed by the recipient, or for the User Product in which it has been modified or installed. Access to a network may be denied when the modification itself materially and adversely affects the operation of the network or violates the rules and protocols for communication across the network.

Corresponding Source conveyed, and Installation Information provided, in accord with this section must be in a format that is publicly documented (and with an implementation available to the public in source code form), and must require no special password or key for unpacking, reading or copying.

7. Additional Terms.

"Additional permissions" are terms that supplement the terms of this License by making exceptions from one or more of its conditions. Additional permissions that are applicable to the entire Program shall be treated as though they were included in this License, to the extent that they are valid under applicable law. If additional permissions apply only to part of the Program, that part may be used separately under those permissions, but the entire Program remains governed by this License without regard to the additional permissions.

When you convey a copy of a covered work, you may at your option remove any additional permissions from that copy, or from any part of it. (Additional permissions may be written to require their own removal in certain cases when you modify the work.) You may place additional permissions on material, added by you to a covered work, for which you have or can give appropriate copyright permission.

Notwithstanding any other provision of this License, for material you add to a covered work, you may (if authorized by the copyright holders of that material) supplement the terms of this License with terms:

- a) Disclaiming warranty or limiting liability differently from the terms of sections 15 and 16 of this License; or
- b) Requiring preservation of specified reasonable legal notices or author attributions in that material or in the Appropriate Legal Notices displayed by works containing it; or
- c) Prohibiting misrepresentation of the origin of that material, or requiring that modified versions of such material be marked in reasonable ways as different from the original version; or
- d) Limiting the use for publicity purposes of names of licensors or

authors of the material; or

e) Declining to grant rights under trademark law for use of some trade names, trademarks, or service marks; or

f) Requiring indemnification of licensors and authors of that material by anyone who conveys the material (or modified versions of it) with contractual assumptions of liability to the recipient, for any liability that these contractual assumptions directly impose on

those licensors and authors.

All other non-permissive additional terms are considered "further restrictions" within the meaning of section 10. If the Program as you received it, or any part of it, contains a notice stating that it is governed by this License along with a term that is a further restriction, you may remove that term. If a license document contains a further restriction but permits relicensing or conveying under this License, you may add to a covered work material governed by the terms of that license document, provided that the further restriction does not survive such relicensing or conveying.

If you add terms to a covered work in accord with this section, you must place, in the relevant source files, a statement of the additional terms that apply to those files, or a notice indicating where to find the applicable terms.

Additional terms, permissive or non-permissive, may be stated in the form of a separately written license, or stated as exceptions; the above requirements apply either way.

8. Termination.

You may not propagate or modify a covered work except as expressly provided under this License. Any attempt otherwise to propagate or modify it is void, and will automatically terminate your rights under this License (including any patent licenses granted under the third paragraph of section 11).

However, if you cease all violation of this License, then your license from a particular copyright holder is reinstated (a) provisionally, unless and until the copyright holder explicitly and finally terminates your license, and (b) permanently, if the copyright holder fails to notify you of the violation by some reasonable means prior to 60 days after the cessation.

Moreover, your license from a particular copyright holder is

reinstated permanently if the copyright holder notifies you of the violation by some reasonable means, this is the first time you have received notice of violation of this License (for any work) from that copyright

holder, and you cure the violation prior to 30 days after your receipt of the notice.

Termination of your rights under this section does not terminate the licenses of parties who have received copies or rights from you under this License. If your rights have been terminated and not permanently reinstated, you do not qualify to receive new licenses for the same material under section 10.

9. Acceptance Not Required for Having Copies.

You are not required to accept this License in order to receive or run a copy of the Program. Ancillary propagation of a covered work occurring solely as a consequence of using peer-to-peer transmission to receive a copy likewise does not require acceptance. However, nothing other than this License grants you permission to propagate or modify any covered work. These actions infringe copyright if you do not accept this License. Therefore, by modifying or propagating a covered work, you indicate your acceptance of this License to do so.

10. Automatic Licensing of Downstream Recipients.

Each time you convey a covered work, the recipient automatically receives a license from the original licensors, to run, modify and propagate that work, subject to this License. You are not responsible for enforcing compliance by third parties with this License.

An "entity transaction" is a transaction transferring control of an organization, or substantially all assets of one, or subdividing an organization, or merging organizations. If propagation of a covered work results from an entity transaction, each party to that transaction who receives a copy of the work also receives whatever licenses to the work the party's predecessor in interest had or could give under the previous paragraph, plus a right to possession of the Corresponding Source of the work from the predecessor in interest, if the predecessor has it or can get it with reasonable efforts.

You may not impose any further restrictions on the exercise of the rights

granted or affirmed under this License. For example, you may not impose a license fee, royalty, or other charge for exercise of rights granted under this License, and you may not initiate litigation (including a cross-claim or counterclaim in a lawsuit) alleging that

any patent claim is infringed by making, using, selling, offering for sale, or importing the Program or any portion of it.

11. Patents.

A "contributor" is a copyright holder who authorizes use under this License of the Program or a work on which the Program is based. The work thus licensed is called the contributor's "contributor version".

A contributor's "essential patent claims" are all patent claims owned or controlled by the contributor, whether already acquired or hereafter acquired, that would be infringed by some manner, permitted by this License, of making, using, or selling its contributor version, but do not include claims that would be infringed only as a consequence of further modification of the contributor version. For purposes of this definition, "control" includes the right to grant patent sublicenses in a manner consistent with the requirements of this License.

Each contributor grants you a non-exclusive, worldwide, royalty-free patent license under the contributor's essential patent claims, to make, use, sell, offer for sale, import and otherwise run, modify and propagate the contents of its contributor version.

In the following three paragraphs, a "patent license" is any express agreement or commitment, however denominated, not to enforce a patent (such as an express permission to practice a patent or covenant not to sue for patent infringement). To "grant" such a patent license to a party means to make such an agreement or commitment not to enforce a patent against the party.

If you convey a covered work, knowingly relying on a patent license, and the Corresponding Source of the work is not available for anyone to copy, free of charge and under the terms of this License, through a publicly available network server or other readily accessible means, then you must either (1) cause the Corresponding Source to be so available, or (2) arrange to deprive yourself of the benefit of the patent license for this particular work, or (3) arrange, in a manner consistent with the requirements of this License, to extend the patent license to downstream recipients. "Knowingly relying" means you have actual knowledge that, but for the patent license, your conveying the covered work in a country, or your recipient's use of the covered work in a country, would infringe one or more identifiable patents in that country that you have reason to believe are valid.

If, pursuant to or in connection with a single transaction or

arrangement, you convey, or propagate by procuring conveyance of, a covered work, and grant a patent license to some of the parties receiving the covered work authorizing them to use, propagate, modify or convey a specific copy of the covered work, then the patent license you grant is automatically extended to all recipients of the covered work and works based on it.

A patent license is "discriminatory" if it does not include within the scope of its coverage, prohibits the exercise of, or is conditioned on the non-exercise of one or more of the rights that are specifically granted under this License. You may not convey a covered work if you are a party to an arrangement with a third party that is in the business of distributing software, under which you make payment to the third party based on the extent of your activity of conveying the work, and under which the third party grants, to any of the parties who would receive the covered work from you, a discriminatory patent license (a) in connection with copies of the covered work conveyed by you (or copies made from those copies), or (b) primarily for and in connection with specific products or compilations that contain the covered work, unless you entered into that arrangement, or that patent license was granted, prior to 28 March 2007.

Nothing in this License shall be construed as excluding or limiting any implied license or other defenses to infringement that may otherwise be available to you under applicable patent law.

12. No Surrender of Others' Freedom.

If conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot convey a covered work so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not convey it at all. For example, if you agree to terms that obligate you to collect a royalty for further conveying from those to whom you convey the Program, the only way you could satisfy both those terms and this License would be to refrain entirely from conveying the Program.

13. Use with the GNU Affero General Public License.

Notwithstanding any other provision of this License, you have permission to link or combine any covered work with a work licensed under version 3 of the GNU Affero General Public License into a single combined work, and to convey the resulting work. The terms of this License will continue to apply to the part which is the covered work, but the special requirements of the GNU Affero General Public License,

section 13, concerning interaction through a network will apply to the combination as such.

14. Revised Versions of this License.

The Free Software Foundation may publish revised and/or new versions of the GNU General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Program specifies that a certain numbered version of the GNU General Public License "or any later version" applies to it, you have the option of following the terms and conditions either of that numbered version or of any later version published by the Free Software Foundation. If the Program does not specify a version number of the GNU General Public License, you may choose any version ever published by the Free Software Foundation.

If the Program specifies that a proxy can decide which future versions of the GNU General Public License can be used, that proxy's public statement of acceptance of a version permanently authorizes you to choose that version for the Program.

Later license versions may give you additional or different permissions. However, no additional obligations are imposed on any author or copyright holder as a result of your choosing to follow a later version.

15. Disclaimer of Warranty.

THERE IS NO WARRANTY FOR THE PROGRAM, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE PROGRAM "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE PROGRAM IS WITH YOU. SHOULD THE PROGRAM PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

16. Limitation of Liability.

IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MODIFIES AND/OR CONVEYS THE PROGRAM AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE

USE OR INABILITY TO USE THE PROGRAM (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE PROGRAM TO OPERATE WITH ANY OTHER PROGRAMS), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

17.

Interpretation of Sections 15 and 16.

If the disclaimer of warranty and limitation of liability provided above cannot be given local legal effect according to their terms, reviewing courts shall apply local law that most closely approximates an absolute waiver of all civil liability in connection with the Program, unless a warranty or assumption of liability accompanies a copy of the Program in return for a fee.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Programs

If you develop a new program, and you want it to be of the greatest possible use to the public, the best way to achieve this is to make it free software which everyone can redistribute and change under these terms.

To do so, attach the following notices to the program. It is safest to attach them to the start of each source file to most effectively state the exclusion of warranty; and each file should have at least the "copyright" line and a pointer to where the full notice is found.

<one line to give the program's name and a brief idea of what it does.>

Copyright (C) <year> <name of author>

This program is free software: you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation, either version 3 of the License, or (at your option) any later version.

This program is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details.

You should have received a copy of the GNU General Public License along with this program. If not, see <<http://www.gnu.org/licenses/>>.

Also add information on how to contact you by electronic and paper mail.

If the program does terminal interaction, make it output a short notice like this when it starts in an interactive mode:

```
<program> Copyright (C) <year> <name of author>  
This program comes with ABSOLUTELY NO WARRANTY; for details type `show w'.  
This is free software, and you are welcome to redistribute it  
under certain conditions; type `show c' for details.
```

The hypothetical commands `show w' and `show c' should show the appropriate parts of the General Public License. Of course, your program's commands might be different; for a GUI interface, you would use an "about box".

You should also get your employer (if you work as a programmer) or school, if any, to sign a "copyright disclaimer" for the program, if necessary. For more information on this, and how to apply and follow the GNU GPL, see <http://www.gnu.org/licenses/>.

The GNU General Public License does not permit incorporating your program into proprietary programs. If your program is a subroutine library, you may consider it more useful to permit linking proprietary applications with the library. If this is what you want to do, use the GNU Lesser General Public License instead of this License. But first, please read <http://www.gnu.org/philosophy/why-not-lgpl.html>.
© The GNU Free Documentation License.
@center Version 1.3, 3 November 2008

© This file is intended to be included within another document,
© hence no sectioning command or @node.

@display
Copyright © 2000, 2001, 2002, 2007, 2008 Free Software Foundation, Inc.
@uref{http://fsf.org/}

Everyone is permitted to copy and distribute verbatim copies of this license document, but changing it is not allowed.
@end display

@enumerate 0
@item
PREAMBLE

The purpose of this License is to make a manual, textbook, or other functional and useful document @dfn{free} in the sense of freedom: to assure everyone the effective freedom to copy and redistribute it, with or without modifying it, either commercially or noncommercially. Secondly, this License preserves for the author and publisher a way

to get credit for their work, while not being considered responsible for modifications made by others.

This License is a kind of "copyleft", which means that derivative works of the document must themselves be free in the same sense. It complements the GNU General Public License, which is a copyleft license designed for free software.

We have designed this License in order to use it for manuals for free software, because free software needs free documentation: a free program should come with manuals providing the same freedoms that the software does. But this License is not limited to software manuals; it can be used for any textual work, regardless of subject matter or whether it is published as a printed book. We recommend this License principally for works whose purpose is instruction or reference.

@item

APPLICABILITY AND DEFINITIONS

This License applies to any manual or other work, in any medium, that contains a notice placed by the copyright holder saying it can be distributed under the terms of this License. Such a notice grants a world-wide, royalty-free license, unlimited in duration, to use that work under the conditions stated herein. The "Document", below, refers

to any such manual or work. Any member of the public is a licensee, and is addressed as "you". You accept the license if you copy, modify or distribute the work in a way requiring permission under copyright law.

A "Modified Version" of the Document means any work containing the Document or a portion of it, either copied verbatim, or with modifications and/or translated into another language.

A "Secondary Section" is a named appendix or a front-matter section of the Document that deals exclusively with the relationship of the publishers or authors of the Document to the Document's overall subject (or to related matters) and contains nothing that could fall directly within that overall subject. (Thus, if the Document is in part a textbook of mathematics, a Secondary Section may not explain any mathematics.) The relationship could be a matter of historical connection with the subject or with related matters, or of legal, commercial, philosophical, ethical or political position regarding them.

The "Invariant Sections" are certain Secondary Sections whose titles

are designated, as being those of Invariant Sections, in the notice that says that the Document is released under this License. If a section does not fit the above definition of Secondary then it is not allowed to be designated as Invariant. The Document may contain zero Invariant Sections. If the Document does not identify any Invariant Sections then there are none.

The ``Cover Texts'' are certain short passages of text that are listed, as Front-Cover Texts or Back-Cover Texts, in the notice that says that the Document is released under this License. A Front-Cover Text may be at most 5 words, and a Back-Cover Text may be at most 25 words.

A ``Transparent'' copy of the Document means a machine-readable copy, represented in a format whose specification is available to the general public, that is suitable for revising the document straightforwardly with generic text editors or (for images composed of pixels) generic paint programs or (for drawings) some widely available drawing editor, and that is suitable for input to text formatters or for automatic translation to a variety of formats suitable for input to text formatters. A copy made in an otherwise Transparent file format whose markup, or absence of markup, has been arranged to thwart or discourage subsequent modification by readers is not Transparent. An image format is not Transparent if used for any substantial amount of text. A copy that is not ``Transparent'' is called ``Opaque''.

Examples of suitable formats for Transparent copies include plain ASCII without markup, Texinfo input format, $\text{La@TeX}\{\}$ input format, SGML or XML using a publicly available DTD, and standard-conforming simple HTML, PostScript or PDF designed for human modification. Examples of transparent image formats include PNG, XCF and JPG@. Opaque formats include proprietary formats that can be read and edited only by proprietary word processors, SGML or XML for which the DTD and/or processing tools are not generally available, and the machine-generated HTML, PostScript or PDF produced by some word processors for output purposes only.

The ``Title Page'' means, for a printed book, the title page itself, plus such following pages as are needed to hold, legibly, the material this License requires to appear in the title page. For works in formats which do not have any title page as such, ``Title Page'' means the text near the most prominent appearance of the work's title, preceding the beginning of the body of the text.

The ``publisher'' means any person or entity that distributes copies

of the Document to the public.

A section ``Entitled XYZ" means a named subunit of the Document whose title either is precisely XYZ or contains XYZ in parentheses following text that translates XYZ in another language. (Here XYZ stands for a specific section name mentioned below, such as ``Acknowledgements", ``Dedications", ``Endorsements", or ``History".) To ``Preserve the Title" of such a section when you modify the Document means that it remains a section ``Entitled XYZ" according to this definition.

The Document may include Warranty Disclaimers next to the notice which states that this License applies to the Document. These Warranty Disclaimers are considered to be included by reference in this License, but only as regards disclaiming warranties: any other implication that these Warranty Disclaimers may have is void and has no effect on the meaning of this License.

@item

VERBATIM COPYING

You may copy and distribute the Document in any medium, either commercially or noncommercially, provided that this License, the copyright notices, and the license notice saying this License applies to the Document are reproduced in all copies, and that you add no other conditions whatsoever to those of this License. You may not use technical measures to obstruct or control the reading or further copying of the copies you make or distribute. However, you may accept compensation in exchange for copies. If you distribute a large enough number of copies you must also follow the conditions in section 3.

You may also lend copies, under the same conditions stated above, and you may publicly display copies.

@item

COPYING IN QUANTITY

If you publish printed copies (or copies in media that commonly have printed covers) of the Document, numbering more than 100, and the Document's license notice requires Cover Texts, you must enclose the copies in covers that carry, clearly and legibly, all these Cover Texts: Front-Cover Texts on the front cover, and Back-Cover Texts on the back cover. Both covers must also clearly and legibly identify you as the publisher of these copies. The front cover must present the full title with all words of the title equally prominent and visible. You may add other material on the covers in addition. Copying with changes limited to the covers, as long as they preserve

the
title of the Document and satisfy these conditions, can be treated
as verbatim copying in other respects.

If the required texts for either cover are too voluminous to fit
legibly, you should put the first ones listed (as many as fit
reasonably) on the actual cover, and continue the rest onto adjacent
pages.

If you publish or distribute Opaque copies of the Document numbering
more than 100, you must either include a machine-readable Transparent
copy along with each Opaque copy, or state in or with each Opaque copy
a computer-network location from which the general network-using
public has access to download using public-standard network protocols
a complete Transparent copy of the Document, free of added material.
If you use the latter option, you must take reasonably prudent steps,
when you begin distribution of Opaque copies in quantity, to ensure
that this Transparent copy will remain thus accessible at the stated
location until at least one year after the last time you distribute
an
Opaque copy (directly or through your agents or retailers) of that
edition to the public.

It is requested, but not required, that you contact the authors of the
Document well before redistributing any large number of copies, to give
them a chance to provide you with an updated version of the Document.

@item

MODIFICATIONS

You may copy and distribute a Modified Version of the Document under
the conditions of sections 2 and 3 above, provided that you release
the Modified Version under precisely this License, with the Modified
Version filling the role of the Document, thus licensing distribution
and modification of the Modified Version to whoever possesses a copy
of it. In addition, you must do these things in the Modified Version:

@enumerate A

@item

Use in the Title Page (and on the covers, if any) a title distinct
from that of the Document, and from those of previous versions
(which should, if there were any, be listed in the History section
of the Document). You may use the same
title as a previous version
if the original publisher of that version gives permission.

@item

List on the Title Page, as authors, one or more persons or entities

responsible for authorship of the modifications in the Modified Version, together with at least five of the principal authors of the Document (all of its principal authors, if it has fewer than five), unless they release you from this requirement.

@item

State on the Title page the name of the publisher of the Modified Version, as the publisher.

@item

Preserve all the copyright notices of the Document.

@item

Add an appropriate copyright notice for your modifications adjacent to the other copyright notices.

@item

Include, immediately after the copyright notices, a license notice giving the public permission to use the Modified Version under the terms of this License, in the form shown in the Addendum below.

@item

Preserve in that license notice the full lists of Invariant Sections and required Cover Texts given in the Document's license notice.

@item

Include an unaltered copy of this License.

@item

Preserve the section Entitled ``History'', Preserve its Title, and add to it an item stating at least the title, year, new authors, and publisher of the Modified Version as given on the Title Page. If there is no section Entitled ``History'' in the Document, create one stating the title, year, authors, and publisher of the Document as given on its Title Page, then add an item describing the Modified Version as stated in the previous sentence.

@item

Preserve the network location, if any, given in the Document for public access to a Transparent copy of the Document, and likewise the network locations given in the Document for previous versions it was based on. These may be placed in the ``History'' section. You may omit a network location for a work that was published at least four years before the Document itself, or if the original publisher of the version it refers to gives permission.

@item

For any section Entitled ``Acknowledgements" or ``Dedications", Preserve the Title of the section, and preserve in the section all the substance and tone of each of the contributor acknowledgements and/or dedications given therein.

@item

Preserve all the Invariant Sections of the Document, unaltered in their text and in their titles. Section numbers or the equivalent are not considered part of the section titles.

@item

Delete any section Entitled ``Endorsements". Such a section may not be included in the Modified Version.

@item

Do not retitle any existing section to be Entitled ``Endorsements" or to conflict in title with any Invariant Section.

@item

Preserve any Warranty Disclaimers.

@end enumerate

If the Modified Version includes new front-matter sections or appendices that qualify as Secondary Sections and contain no material copied from the Document, you may at your option designate some or all of these sections as invariant. To do this, add their titles to the list of Invariant

Sections in the Modified Version's license notice.

These titles must be distinct from any other section titles.

You may add a section Entitled ``Endorsements", provided it contains nothing but endorsements of your Modified Version by various parties---for example, statements of peer review or that the text has been approved by an organization as the authoritative definition of a standard.

You may add a passage of up to five words as a Front-Cover Text, and a passage of up to 25 words as a Back-Cover Text, to the end of the list of Cover Texts in the Modified Version. Only one passage of Front-Cover Text and one of Back-Cover Text may be added by (or through arrangements made by) any one entity. If the Document already includes a cover text for the same cover, previously added by you or by arrangement made by the same entity you are acting on behalf of, you may not add another; but you may replace the old one, on explicit permission from the previous publisher that added the old one.

The author(s) and publisher(s) of the Document do not by this License give permission to use their names for publicity for or to assert or imply endorsement of any Modified Version.

@item

COMBINING DOCUMENTS

You may combine the Document with other documents released under this License, under the terms defined in section 4 above for modified versions, provided that you include in the combination all of the Invariant Sections of all of the original documents, unmodified, and list them all as Invariant Sections of your combined work in its license notice, and that you preserve all their Warranty Disclaimers.

The combined work need only contain one copy of this License, and multiple identical Invariant Sections may be replaced with a single copy. If there are multiple Invariant Sections with the same name but different contents, make the title of each such section unique by adding at the end of it, in parentheses, the name of the original author or publisher of that section if known, or else a unique number.

Make the same adjustment to the section titles in the list of Invariant Sections in the license notice of the combined work.

In the combination, you must combine any sections Entitled ``History'' in the various original documents, forming one section Entitled ``History''; likewise combine any sections Entitled ``Acknowledgements'', and any sections Entitled ``Dedications''. You must delete all sections Entitled ``Endorsements''.

@item

COLLECTIONS OF DOCUMENTS

You may make a collection consisting of the Document and other documents released under this License, and replace the individual copies of this License in the various documents with a single copy that is included in the collection, provided that you follow the rules of this License for verbatim copying of each of the documents in all other respects.

You may extract a single document from such a collection, and distribute it individually under this License, provided you insert a copy of this License into the extracted document, and follow this License in all other respects regarding verbatim copying of that document.

@item

AGGREGATION WITH INDEPENDENT WORKS

A compilation of the Document or its derivatives with other separate and independent documents or works, in or on a volume of a storage or distribution medium, is called an "aggregate" if the copyright resulting from the compilation is not used to limit the legal rights of the compilation's users beyond what the individual works permit. When the Document is included in an aggregate, this License does not apply to the other works in the aggregate which are not themselves derivative works of the Document.

If the Cover Text requirement of section 3 is applicable to these copies of the Document, then if the Document is less than one half of the entire aggregate, the Document's Cover Texts may be placed on covers that bracket the Document within the aggregate, or the electronic equivalent of covers if the Document is in electronic form.

Otherwise they must appear on printed covers that bracket the whole aggregate.

@item

TRANSLATION

Translation is considered a kind of modification, so you may distribute translations of the Document under the terms of section 4. Replacing Invariant Sections with translations requires special permission from their copyright holders, but you may include translations of some or all Invariant Sections in addition to the original versions of these Invariant Sections. You may include a translation of this License, and all the license notices in the Document, and any Warranty Disclaimers, provided that you also include the original English version of this License and the original versions of those notices and disclaimers. In case of a disagreement between the translation and the original version of this License or a notice or disclaimer, the original version will prevail.

If a section in the Document is Entitled "Acknowledgements", "Dedications", or "History", the requirement (section 4) to Preserve its Title (section 1) will typically require changing the actual title.

@item

TERMINATION

You may not copy, modify, sublicense, or distribute the Document except as expressly provided under this License. Any attempt otherwise to copy, modify, sublicense, or distribute it is void, and will automatically terminate your rights under this License.

However, if you cease all violation of this License, then your license from a particular copyright holder is reinstated (a) provisionally, unless and until the copyright holder explicitly and finally terminates your license, and (b) permanently, if the copyright holder fails to notify you of the violation by some reasonable means prior to 60 days after the cessation.

Moreover, your license from a particular copyright holder is reinstated permanently if the copyright holder notifies you of the violation by some reasonable means, this is the first time you have received notice of violation of this License (for any work) from that copyright holder, and you cure the violation prior to 30 days after your receipt of the notice.

Termination of your rights under this section does not terminate the licenses of parties who have received copies or rights from you under this License. If your rights have been terminated and not permanently reinstated, receipt of a copy of some or all of the same material does not give you any rights to use it.

@item

FUTURE REVISIONS OF THIS LICENSE

The Free Software Foundation may publish new, revised versions of the GNU Free Documentation License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns. See [@uref{http://www.gnu.org/copyleft/}](http://www.gnu.org/copyleft/).

Each version of the License is given a distinguishing version number. If the Document specifies that a particular numbered version of this License "or any later version" applies to it, you have the option of following the terms and conditions either of that specified version or of any later version that has been published (not as a draft) by the Free Software Foundation. If the Document does not specify a version number of this License, you may choose any version ever published (not as a draft) by the Free Software Foundation. If the Document specifies that a proxy can decide which future versions of this License can be used, that proxy's public statement of acceptance of a version permanently authorizes you to choose that version for the Document.

@item

RELICENSING

"Massive Multiauthor Collaboration Site" (or "MMC Site") means any

World Wide Web server that publishes copyrightable works and also provides prominent facilities for anybody to edit those works. A public wiki that anybody can edit is an example of such a server. A ``Massive Multiauthor Collaboration" (or ``MMC") contained in the site means any set of copyrightable works thus published on the MMC site.

``CC-BY-SA" means the Creative Commons

Attribution-Share Alike 3.0

license published by Creative Commons Corporation, a not-for-profit corporation with a principal place of business in San Francisco, California, as well as future copyleft versions of that license published by that same organization.

``Incorporate" means to publish or republish a Document, in whole or in part, as part of another Document.

An MMC is ``eligible for relicensing" if it is licensed under this License, and if all works that were first published under this License somewhere other than this MMC, and subsequently incorporated in whole or in part into the MMC, (1) had no cover texts or invariant sections, and (2) were thus incorporated prior to November 1, 2008.

The operator of an MMC Site may republish an MMC contained in the site under CC-BY-SA on the same site at any time before August 1, 2009, provided the MMC is eligible for relicensing.

@end enumerate

@page

@heading ADDENDUM: How to use this License for your documents

To use this License
in a document you have written, include a copy of
the License in the document and put the following copyright and
license notices just after the title page:

@smallexample

@group

Copyright (C) @var{year} @var{your name}.

Permission is granted to copy, distribute and/or modify this document under the terms of the GNU Free Documentation License, Version 1.3 or any later version published by the Free Software Foundation; with no Invariant Sections, no Front-Cover Texts, and no Back-Cover Texts. A copy of the license is included in the section entitled ``GNU Free Documentation License".

@end group

@end smallexample

If you have Invariant Sections, Front-Cover Texts and Back-Cover Texts, replace the ``with@dots{ }Texts."@: line with this:

```
@smallexample
@group
  with the Invariant Sections being @var{list their titles}, with
  the Front-Cover Texts being @var{list}, and with the Back-Cover Texts
  being @var{list}.
@end group
@end smallexample
```

If you have Invariant Sections without Cover Texts, or some other combination of the three, merge those two alternatives to suit the situation.

If your document contains nontrivial examples of program code, we recommend releasing these examples in parallel under your choice of free software license, such as the GNU General Public License, to permit their use in free software.

```
@c Local Variables:
@c ispell-local-pdict: "ispell-dict"
@c End:
```

1.33 procps 2:3.3.12-3ubuntu1.2

1.33.1 Available under license :

GNU GENERAL PUBLIC LICENSE
Version 2, June 1991

Copyright (C) 1989, 1991 Free Software Foundation, Inc.,
51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA
Everyone is permitted to copy and distribute verbatim copies
of this license document, but changing it is not allowed.

Preamble

The licenses for most software are designed to take away your freedom to share and change it. By contrast, the GNU General Public License is intended to guarantee your freedom to share and change free software--to make sure the software is free for all its users. This General Public License applies to most of the Free Software Foundation's software and to any other program whose authors commit to using it. (Some other Free Software Foundation software is covered by the GNU Lesser General Public License instead.) You can apply it to

your programs, too.

When we speak of free software, we are referring to freedom, not price.

Our General Public Licenses are designed to make sure that you have the freedom to distribute copies of free software (and charge for this service if you wish), that you receive source code or can get it if you want it, that you can change the software or use pieces of it in new free programs; and that you know you can do these things.

To protect your rights, we need to make restrictions that forbid anyone to deny you these rights or to ask you to surrender the rights. These restrictions translate to certain responsibilities for you if you distribute copies of the software, or if you modify it.

For example, if you distribute copies of such a program, whether gratis or for a fee, you must give the recipients all the rights that you have. You must make sure that they, too, receive or can get the source code. And you must show them these terms so they know their rights.

We protect your rights with two steps: (1) copyright the software, and (2) offer you this license which gives you legal permission to copy, distribute and/or modify the software.

Also, for each author's protection and ours, we want to make certain that everyone understands that there is no warranty for this free software. If the software is modified by someone else and passed on, we want its recipients to know that what they have is not the original, so that any problems introduced by others will not reflect on the original authors' reputations.

Finally, any free program is threatened constantly by software patents. We wish to avoid the danger that redistributors of a free program will individually obtain patent licenses, in effect making the program proprietary. To prevent this, we have made it clear that any patent must be licensed for everyone's free use or not licensed at all.

The precise terms and conditions for copying, distribution and modification follow.

GNU GENERAL PUBLIC LICENSE TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

0. This License applies to any program or other work which contains a notice placed by the copyright holder saying it may be distributed under the terms of this General Public License. The "Program", below,

refers to any such program or work, and a "work based on the Program" means either the Program or any derivative work under copyright law: that is to say, a work containing the Program or a portion of it, either verbatim or with modifications and/or translated into another language. (Hereinafter, translation is included without limitation in the term "modification".) Each licensee is addressed as "you".

Activities other than copying, distribution and modification are not covered by this License; they are outside its scope. The act of running the Program is not restricted, and the output from the Program is covered only if its contents constitute a work based on the Program (independent of having been made by running the Program). Whether that is true depends on what the Program does.

1. You may copy and distribute verbatim copies of the Program's source code as you receive it, in any medium, provided that you conspicuously and appropriately publish on each copy an appropriate copyright notice and disclaimer of warranty; keep intact all the notices that refer to this License and to the absence of any warranty; and give any other recipients of the Program a copy of this License along with the Program.

You may charge a fee for the physical act of transferring a copy, and you may at your option offer warranty protection in exchange for a fee.

2. You may modify your copy or copies of the Program or any portion of it, thus forming a work based on the Program, and copy and distribute such modifications or work under the terms of Section 1 above, provided that you also meet all of these conditions:

a) You must cause the modified files to carry prominent notices stating that you changed the files and the date of any change.

b) You must cause any work that you distribute or publish, that in whole or in part contains or is derived from the Program or any part thereof, to be licensed as a whole at no charge to all third parties under the terms of this License.

c) If the modified program normally reads commands interactively when run, you must cause it, when started running for such interactive use in the most ordinary way, to print or display an announcement including an appropriate copyright notice and a notice that there is no warranty (or else, saying that you provide a warranty) and that users may redistribute the program under these conditions, and telling the user how to view a copy of this License. (Exception: if the Program itself is interactive but

does not normally print such an announcement, your work based on the Program is not required to print an announcement.)

These requirements apply to the modified work as a whole. If identifiable sections of that work are not derived from the Program, and can be reasonably considered independent and separate works in themselves, then this License, and its terms, do not apply to those sections when you distribute them as separate works. But when you distribute the same sections as part of a whole which is a work based on the Program, the distribution of the whole must be on the terms of this License, whose permissions for other licensees extend to the entire whole, and thus to each and every part regardless of who wrote it.

Thus, it is not the intent of this section to claim rights or contest your rights to work written entirely by you; rather, the intent is to exercise the right to control the distribution of derivative or collective works based on the Program.

In addition, mere aggregation of another work not based on the Program with the Program (or with a work based on the Program) on a volume of a storage or distribution medium does not bring the other work under the scope of this License.

3. You may copy and distribute the Program (or a work based on it, under Section 2) in object code or executable form under the terms of Sections 1 and 2 above provided that you also do one of the following:

- a) Accompany it with the complete corresponding machine-readable source code, which must be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange; or,
- b) Accompany it with a written offer, valid for at least three years, to give any third party, for a charge no more than your cost of physically performing source distribution, a complete machine-readable copy of the corresponding source code, to be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange; or,
- c) Accompany it with the information you received as to the offer to distribute corresponding source code. (This alternative is allowed only for noncommercial distribution and only if you received the program in object code or executable form with such an offer, in accord with Subsection b above.)

The source code for a work means the preferred form of the work for making modifications to it. For an executable work, complete source

code means all the source code for all modules it contains, plus any associated interface definition files, plus the scripts used to control compilation and installation of the executable. However, as a special exception, the source code distributed need not include anything that is normally distributed (in either source or binary form) with the major components (compiler, kernel, and so on) of the operating system on which the executable runs, unless that component itself accompanies the executable.

If distribution of executable or object code is made by offering access to copy from a designated place, then offering equivalent access to copy the source code from the same place counts as distribution of the source code, even though third parties are not compelled to copy the source along with the object code.

4. You may not copy, modify, sublicense, or distribute the Program except as expressly provided under this License. Any attempt otherwise to copy, modify, sublicense or distribute the Program is void, and will automatically terminate your rights under this License. However, parties who have received copies, or rights, from you under this License will not have their licenses terminated so long as such parties remain in full compliance.

5. You are not required to accept this License, since you have not signed it. However, nothing else grants you permission to modify or distribute the Program or its derivative works. These actions are prohibited by law if you do not accept this License. Therefore, by modifying or distributing the Program (or any work based on the Program), you indicate your acceptance of this License to do so, and all its terms and conditions for copying, distributing or modifying the Program or works based on it.

6. Each time you redistribute the Program (or any work based on the Program), the recipient automatically receives a license from the original licensor to copy, distribute or modify the Program subject to these terms and conditions. You may not impose any further restrictions on the recipients' exercise of the rights granted herein. You are not responsible for enforcing compliance by third parties to this License.

7. If, as a consequence of a court judgment or allegation of patent infringement or for any other reason (not limited to patent issues), conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot distribute so as to satisfy simultaneously your obligations under this

License and any other pertinent obligations, then as a consequence you may not distribute the Program at all. For example, if a patent license would not permit royalty-free redistribution of the Program by all those who receive copies directly or indirectly through you, then the only way you could satisfy both it and this License would be to refrain entirely from distribution of the Program.

If any portion of this section is held invalid or unenforceable under any particular circumstance, the balance of the section is intended to apply and the section as a whole is intended to apply in other circumstances.

It is not the purpose of this section to induce you to infringe any patents or other property right claims or to contest validity of any such claims; this section has the sole purpose of protecting the integrity of the free software distribution system, which is implemented by public license practices. Many people have made generous contributions to the wide range of software distributed through that system in reliance on consistent application of that system; it is up to the author/donor to decide if he or she is willing to distribute software through any other system and a licensee cannot impose that choice.

This section is intended to make thoroughly clear what is believed to be a consequence of the rest of this License.

8. If the distribution and/or use of the Program is restricted in certain countries either by patents or by copyrighted interfaces, the original copyright holder who places the Program under this License may add an explicit geographical distribution limitation excluding those countries, so that distribution is permitted only in or among countries not thus excluded. In such case, this License incorporates the limitation as if written in the body of this License.

9. The Free Software Foundation may publish revised and/or new versions of the General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Program specifies a version number of this License which applies to it and "any later version", you have the option of following the terms and conditions either of that version or of any later version published by the Free Software Foundation. If the Program does not specify a version number of this License, you may choose any version ever published by the Free Software

Foundation.

10. If you wish to incorporate parts of the Program into other free programs whose distribution conditions are different, write to the author to ask for permission. For software which is copyrighted by the Free Software Foundation, write to the Free Software Foundation; we sometimes make exceptions for this. Our decision will be guided by the two goals of preserving the free status of all derivatives of our free software and of promoting the sharing and reuse of software generally.

NO WARRANTY

11. BECAUSE THE PROGRAM IS LICENSED FREE OF CHARGE, THERE IS NO WARRANTY FOR THE PROGRAM, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE PROGRAM "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE PROGRAM IS WITH YOU. SHOULD THE PROGRAM PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

12. IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY AND/OR REDISTRIBUTE THE PROGRAM AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE PROGRAM (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE PROGRAM TO OPERATE WITH ANY OTHER PROGRAMS), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Programs

If you develop a new program, and you want it to be of the greatest possible use to the public, the best way to achieve this is to make it free software which everyone can redistribute and change under these terms.

To do so, attach the following notices to the program. It is safest to attach them to the start of each source file to most effectively convey the exclusion of warranty; and each file should have at least the "copyright" line and a pointer to where the full notice is found.

<one line to give the program's name and a brief idea of what it does.>

Copyright (C) <year> <name of author>

This program is free software; you can redistribute it and/or modify it under the terms of the GNU

General Public License as published by the Free Software Foundation; either version 2 of the License, or (at your option) any later version.

This program is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details.

You should have received a copy of the GNU General Public License along with this program; if not, write to the Free Software Foundation, Inc., 51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA.

Also add information on how to contact you by electronic and paper mail.

If the program is interactive, make it output a short notice like this when it starts in an interactive mode:

```
Gnomovision version 69, Copyright (C) year name of author
Gnomovision comes with ABSOLUTELY NO WARRANTY; for details type `show w'.
This is free software, and you are welcome to redistribute
it
under certain conditions; type `show c' for details.
```

The hypothetical commands `show w' and `show c' should show the appropriate parts of the General Public License. Of course, the commands you use may be called something other than `show w' and `show c'; they could even be mouse-clicks or menu items--whatever suits your program.

You should also get your employer (if you work as a programmer) or your school, if any, to sign a "copyright disclaimer" for the program, if necessary. Here is a sample; alter the names:

```
Yoyodyne, Inc., hereby disclaims all copyright interest in the program
`Gnomovision' (which makes passes at compilers) written by James Hacker.
```

```
<signature of Ty Coon>, 1 April 1989
Ty Coon, President of Vice
```

This General Public License does not permit incorporating your program into proprietary programs. If your program is a subroutine library, you may consider it more useful to permit linking proprietary applications with the library. If this

is what you want to do, use the GNU Lesser General Public License instead of this License.

GNU LIBRARY GENERAL PUBLIC LICENSE
Version 2, June 1991

Copyright (C) 1991 Free Software Foundation, Inc.
51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA
Everyone is permitted to copy and distribute verbatim copies of this license document, but changing it is not allowed.

[This is the first released version of the library GPL. It is numbered 2 because it goes with version 2 of the ordinary GPL.]

Preamble

The licenses for most software are designed to take away your freedom to share and change it. By contrast, the GNU General Public Licenses are intended to guarantee your freedom to share and change free software--to make sure the software is free for all its users.

This license, the Library General Public License, applies to some specially designated Free Software Foundation software, and to any other libraries whose authors decide to use it. You can use it for your libraries, too.

When

we speak of free software, we are referring to freedom, not price. Our General Public Licenses are designed to make sure that you have the freedom to distribute copies of free software (and charge for this service if you wish), that you receive source code or can get it if you want it, that you can change the software or use pieces of it in new free programs; and that you know you can do these things.

To protect your rights, we need to make restrictions that forbid anyone to deny you these rights or to ask you to surrender the rights. These restrictions translate to certain responsibilities for you if you distribute copies of the library, or if you modify it.

For example, if you distribute copies of the library, whether gratis or for a fee, you must give the recipients all the rights that we gave you. You must make sure that they, too, receive or can get the source code. If you link a program with the library, you must provide complete object files to the recipients so that they can relink them with the library, after making changes to the library and recompiling it. And you must show them these terms so they know their rights.

Our method of protecting your rights has two steps: (1) copyright

the library, and (2) offer you this license which gives you legal permission to copy, distribute and/or modify the library.

Also, for each distributor's protection, we want to make certain that everyone understands that there is no warranty for this free library. If the library is modified by someone else and passed on, we want its recipients to know that what they have is not the original version, so that any problems introduced by others will not reflect on the original authors' reputations.

Finally, any free program is threatened constantly by software patents. We wish to avoid the danger that companies distributing free software will individually obtain patent licenses, thus in effect transforming the program into proprietary software. To prevent this, we have made it clear that any patent must be licensed for everyone's free use or not licensed at all.

Most GNU software, including some libraries, is covered by the ordinary GNU General Public License, which was designed for utility programs. This license, the GNU Library General Public License, applies to certain designated libraries. This license is quite different from the ordinary one; be sure to read it in full, and don't assume that anything in it is the same as in the ordinary license.

The reason we have a separate public license for some libraries is that they blur the distinction we usually make between modifying or adding to a program and simply using it. Linking a program with a library, without changing the library, is in some sense simply using the library, and is analogous to running a utility program or application program. However, in a textual and legal sense, the linked executable is a combined work, a derivative of the original library, and the ordinary General Public License treats it as such.

Because of this blurred distinction, using the ordinary General Public License for libraries did not effectively promote software sharing, because most developers did not use the libraries. We concluded that weaker conditions might promote sharing better.

However, unrestricted linking of non-free programs would deprive the users of those programs of all benefit from the free status of the libraries themselves. This Library General Public License is intended to permit developers of non-free programs to use free libraries, while preserving your freedom as a user of such programs to change the free libraries that are incorporated in them. (We have not seen how to achieve this as regards changes in header files, but we have achieved it as regards changes in the actual functions of the Library.) The hope is that this

will lead to faster development of free libraries.

The precise terms and conditions for copying, distribution and modification follow. Pay close attention to the difference between a "work based on the library" and a "work that uses the library". The former contains code derived from the library, while the latter only works together with the library.

Note that it is possible for a library to be covered by the ordinary General Public License rather than by this special one.

GNU LIBRARY GENERAL PUBLIC LICENSE TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

0. This License Agreement applies to any software library which contains a notice placed by the copyright holder or other authorized party saying it may be distributed under the terms of this Library General Public License (also called "this License"). Each licensee is addressed as "you".

A "library" means a collection of software functions and/or data prepared so as to be conveniently linked with application programs (which use some of those functions and data) to form executables.

The "Library", below, refers to any such software library or work which has been distributed under these terms. A "work based on the Library" means either the Library or any derivative work under copyright law: that is to say, a work containing the Library or a portion of it, either verbatim or with modifications and/or translated straightforwardly into another language. (Hereinafter, translation is included without limitation in the term "modification".)

"Source code" for a work means the preferred form of the work for making modifications to it. For a library, complete source code means all the source code for all modules it contains, plus any associated interface definition files, plus the scripts used to control compilation and installation of the library.

Activities other than copying, distribution and modification are not covered by this License; they are outside its scope. The act of running a program using the Library is not restricted, and output from such a program is covered only if its contents constitute a work based on the Library (independent of the use of the Library in a tool for writing it). Whether that is true depends on what the Library does and what the program that uses the Library does.

1. You may copy and distribute verbatim copies of the Library's complete source code as you receive it, in any medium, provided that you conspicuously and appropriately publish on each copy an appropriate copyright notice and disclaimer of warranty; keep intact all the notices that refer to this License and to the absence of any warranty; and distribute a copy of this License along with the Library.

You may charge a fee for the physical act of transferring a copy, and you may at your option offer warranty protection in exchange for a fee.

2. You may modify your copy or copies of the Library or any portion of it, thus forming a work based on the Library, and copy and distribute such modifications or work under the terms of Section 1 above, provided that you also meet all of these conditions:

- a) The modified work must itself be a software library.
- b) You must cause the files modified to carry prominent notices stating that you changed the files and the date of any change.
- c) You must cause the whole of the work to be licensed at no charge to all third parties under the terms of this License.
- d) If a facility in the modified Library refers to a function or a table of data to be supplied by an application program that uses the facility, other than as an argument passed when the facility is invoked, then you must make a good faith effort to ensure that, in the event an application does not supply such function or table, the facility still operates, and performs whatever part of its purpose remains meaningful.

(For example, a function in a library to compute square roots has a purpose that is entirely well-defined independent of the application. Therefore, Subsection 2d requires that any application-supplied function or table used by this function must be optional: if the application does not supply it, the square root function must still compute square roots.)

These requirements apply to the modified work as a whole. If identifiable sections of that work are not derived from the Library, and can be reasonably considered independent and separate works in themselves, then this License, and its terms, do not apply to those sections when you distribute them as separate works. But when you

distribute the same sections as part of a whole which is a work based on the Library, the distribution of the whole must be on the terms of this License, whose permissions for other licensees extend to the entire whole, and thus to each and every part regardless of who wrote it.

Thus, it is not the intent of this section to claim rights or contest your rights to work written entirely by you; rather, the intent is to exercise the right to control the distribution of derivative or collective works based on the Library.

In addition, mere aggregation of another work not based on the Library with the Library (or with a work based on the Library) on a volume of a storage or distribution medium does not bring the other work under the scope of this License.

3. You may opt to apply the terms of the ordinary GNU General Public License instead of this License to a given copy of the Library. To do this, you must alter all the notices that refer to this License, so that they refer to the ordinary GNU General Public License, version 2, instead of to this License. (If a newer version than version 2 of the ordinary GNU General Public License has appeared, then you can specify that version instead if you wish.) Do not make any other change in these notices.

Once this change is made in a given copy, it is irreversible for that copy, so the ordinary GNU General Public License applies to all subsequent copies and derivative works made from that copy.

This option is useful when you wish to copy part of the code of the Library into a program that is not a library.

4. You may copy and distribute the Library (or a portion or derivative of it, under Section 2) in object code or executable form under the terms of Sections 1 and 2 above provided that you accompany it with the complete corresponding machine-readable source code, which must be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange.

If distribution of object code is made by offering access to copy from a designated place, then offering equivalent access to copy the source code from the same place satisfies the requirement to distribute the source code, even though third parties are not compelled to copy the source along with the object code.

5. A program that contains no derivative of any portion of the

Library, but is designed to work with the Library by being compiled or linked with it, is called a "work that uses the Library". Such a work, in isolation, is not a derivative work of the Library, and therefore falls outside the scope of this License.

However, linking a "work that uses the Library" with the Library creates an executable that is a derivative of the Library (because it contains portions of the Library), rather than a "work that uses the library". The executable is therefore covered by this License. Section 6 states terms for distribution of such executables.

When a "work that uses the Library" uses material from a header file that is part of the Library, the object code for the work may be a derivative work of the Library even though the source code is not. Whether this is true is especially significant if the work can be linked without the Library, or if the work is itself a library. The threshold for this to be true is not precisely defined by law.

If such an object file uses only numerical parameters, data structure layouts and accessors, and small macros and small inline functions (ten lines or less in length), then the use of the object file is unrestricted, regardless of whether it is legally a derivative work. (Executables containing this object code plus portions of the Library will still fall under Section 6.)

Otherwise, if the work is a derivative of the Library, you may distribute the object code for the work under the terms of Section 6. Any executables containing that work also fall under Section 6, whether or not they are linked directly with the Library itself.

6. As an exception to the Sections above, you may also compile or link a "work that uses the Library" with the Library to produce a work containing portions of the Library, and distribute that work under terms of your choice, provided that the terms permit modification of the work for the customer's own use and reverse engineering for debugging such modifications.

You must give prominent notice with each copy of the work that the Library is used in it and that the Library and its use are covered by this License. You must supply a copy of this License. If the work during execution displays copyright notices, you must include the copyright notice for the Library among them, as well as a reference directing the user to the copy of this License. Also, you must do one of these things:

a) Accompany the work with the complete corresponding machine-readable source code for the Library including whatever changes were used in the work (which must be distributed under Sections 1 and 2 above); and, if the work is an executable linked with the Library, with the complete machine-readable "work that uses the Library", as object code and/or source code, so that the user can modify the Library and then relink to produce a modified executable containing the modified Library. (It is understood that the user who changes the contents of definitions files in the Library will not necessarily be able to recompile the application to use the modified definitions.)

b) Accompany the work with a written offer, valid for at least three years, to give the same user the materials specified in Subsection 6a, above, for a charge no more than the cost of performing this distribution.

c) If distribution of the work is made by offering access to copy from a designated place, offer equivalent access to copy the above specified materials from the same place.

d) Verify that the user has already received a copy of these materials or that you have already sent this user a copy.

For an executable, the required form of the "work that uses the Library" must include any data and utility programs needed for reproducing the executable from it. However, as a special exception, the source code distributed need not include anything that is normally distributed (in either source or binary form) with the major components (compiler, kernel, and so on) of the operating system on which the executable runs, unless that component itself accompanies the executable.

It may happen that this requirement contradicts the license restrictions of other proprietary libraries that do not normally accompany the operating system. Such a contradiction means you cannot use both them and the Library together in an executable that you distribute.

7. You may place library facilities that are a work based on the Library side-by-side in a single library together with other library facilities not covered by this License, and distribute such a combined library, provided that the separate distribution of the work based on the Library and of the other library facilities is otherwise permitted, and provided that you do these two things:

a) Accompany the combined library with a copy of the same work

based on the Library, uncombined with any other library facilities. This must be distributed under the terms of the Sections above.

b) Give prominent notice with the combined library of the fact that part of it is a work based on the Library, and explaining where to find the accompanying uncombined form of the same work.

8. You may not copy, modify, sublicense, link with, or distribute the Library except as expressly provided under this License. Any attempt otherwise to copy, modify, sublicense, link with, or distribute the Library is void, and will automatically terminate your rights under this License. However, parties who have received copies, or rights, from you under this License will not have their licenses terminated so long as such parties remain in full compliance.

9. You are not required to accept this License, since you have not signed it. However, nothing else grants you permission to modify or distribute the Library or its derivative works. These actions are prohibited by law if you do not accept this License. Therefore, by modifying or distributing the Library (or any work based on the Library), you indicate your acceptance of this License to do so, and all its terms and conditions for copying, distributing or modifying the Library or works based on it.

10. Each time you redistribute the Library (or any work based on the Library), the recipient automatically receives a license from the original licensor to copy, distribute, link with or modify the Library subject to these terms and conditions. You may not impose any further restrictions on the recipients' exercise of the rights granted herein. You are not responsible for enforcing compliance by third parties to this License.

11. If, as a consequence of a court judgment or allegation of patent infringement or for any other reason (not limited to patent issues), conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot distribute so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not distribute the Library at all. For example, if a patent license would not permit royalty-free redistribution of the Library by all those who receive copies directly or indirectly through you, then the only way you could satisfy both it and this License would be to refrain entirely from distribution of the Library.

If any portion of this section is held invalid or unenforceable under any particular circumstance, the balance of the section is intended to apply, and the section as a whole is intended to apply in other circumstances.

It is not the purpose of this section to induce you to infringe any patents or other property right claims or to contest validity of any such claims; this section has the sole purpose of protecting the integrity of the free software distribution system which is implemented by public license practices. Many people have made generous contributions to the wide range of software distributed through that system in reliance on consistent application of that system; it is up to the author/donor to decide if he or she is willing to distribute software through any other system and a licensee cannot impose that choice.

This section is intended to make thoroughly clear what is believed to be a consequence of the rest of this License.

12. If the distribution and/or use of the Library is restricted in certain countries either by patents or by copyrighted interfaces, the original copyright holder who places the Library under this License may add an explicit geographical distribution limitation excluding those countries, so that distribution is permitted only in or among countries not thus excluded. In such case, this License incorporates the limitation as if written in the body of this License.

13. The Free Software Foundation may publish revised and/or new versions of the Library General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Library specifies a version number of this License which applies to it and "any later version", you have the option of following the terms and conditions either of that version or of any later version published by the Free Software Foundation. If the Library does not specify a license version number, you may choose any version ever published by the Free Software Foundation.

14. If you wish to incorporate parts of the Library into other free programs whose distribution conditions are incompatible with these, write to the author to ask for permission. For software which is copyrighted by the Free Software Foundation, write to the Free Software Foundation; we sometimes make exceptions for this. Our decision will be guided by the two goals of preserving the free status

of all derivatives of our free software and of promoting the sharing and reuse of software generally.

NO WARRANTY

15. BECAUSE THE LIBRARY IS LICENSED FREE OF CHARGE, THERE IS NO WARRANTY FOR THE LIBRARY, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE LIBRARY "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE LIBRARY IS WITH YOU. SHOULD THE LIBRARY PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

16. IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY AND/OR REDISTRIBUTE THE LIBRARY AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE LIBRARY (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE LIBRARY TO OPERATE WITH ANY OTHER SOFTWARE), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Libraries

If you develop a new library, and you want it to be of the greatest possible use to the public, we recommend making it free software that everyone can redistribute and change. You can do so by permitting redistribution under these terms (or, alternatively, under the terms of the ordinary General Public License).

To apply these terms, attach the following notices to the library. It is safest to attach them to the start of each source file to most effectively convey the exclusion of warranty; and each file should have at least the "copyright" line and a pointer to where the full notice is found.

<one line to give the library's name and a brief idea of what it does.>
Copyright (C) <year> <name of author>

This library is free software; you can redistribute it and/or

modify it under the terms of the GNU Library General Public License as published by the Free Software Foundation; either version 2 of the License, or (at your option) any later version.

This library is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU Library General Public License for more details.

You should have received a copy of the GNU Library General Public License along with this library; if not, write to the Free Software Foundation, Inc., 51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA

Also add information on how to contact you by electronic and paper mail.

You should also get your employer (if you work as a programmer) or your school, if any, to sign a "copyright disclaimer" for the library, if necessary. Here is a sample; alter the names:

Yoyodyne, Inc., hereby disclaims all copyright interest in the library `Frob' (a library for tweaking knobs) written by James Random Hacker.

<signature of Ty Coon>, 1 April 1990
Ty Coon, President of Vice

That's all there is to it!

1.34 cpp 8.4.0-1ubuntu1~18.04

1.34.1 Available under license :

GNU GENERAL PUBLIC LICENSE

Version 3, 29 June 2007

Copyright (C) 2007 Free Software Foundation, Inc. <<http://fsf.org/>>

Everyone is permitted to copy and distribute verbatim copies of this license document, but changing it is not allowed.

Preamble

The GNU General Public License is a free, copyleft license for software and other kinds of works.

The licenses for most software and other practical works are designed to take away your freedom to share and change the works. By contrast, the GNU General Public License is intended to guarantee your freedom to share and change all versions of a program--to make sure it remains free

software for all its users. We, the Free Software Foundation, use the GNU General Public License for most of our software; it applies also to any other work released this way by its authors. You can apply it to your programs, too.

When we speak of free software, we are referring to freedom, not price. Our General Public Licenses are designed to make sure that you have the freedom to distribute copies of free software (and charge for them if you wish), that you receive source code or can get it if you want it, that you can change the software or use pieces of it in new free programs, and that you know you can do these things.

To protect your rights, we need to prevent others from denying you these rights or asking you to surrender the rights. Therefore, you have certain responsibilities if you distribute copies of the software, or if you modify it: responsibilities to respect the freedom of others.

For example, if you distribute copies of such a program, whether gratis or for a fee, you must pass on to the recipients the same freedoms that you received. You must make sure that they, too, receive or can get the source code. And you must show them these terms so they know their rights.

Developers that use the GNU GPL protect your rights with two steps:

- (1) assert copyright on the software, and (2) offer you this License giving you legal permission to copy, distribute and/or modify it.

For the developers' and authors' protection, the GPL clearly explains that there is no warranty for this free software. For both users' and authors' sake, the GPL requires that modified versions be marked as changed, so that their problems will not be attributed erroneously to authors of previous versions.

Some devices are designed to deny users access to install or run modified versions of the software inside them, although the manufacturer can do so. This is fundamentally incompatible with the aim of protecting users' freedom to change the software. The systematic pattern of such abuse occurs in the area of products for individuals to use, which is precisely where it is most unacceptable. Therefore, we have designed this version of the GPL to prohibit the practice for those products. If such problems arise substantially in other domains, we stand ready to extend this provision to those domains in future versions of the GPL, as needed to protect the freedom of users.

Finally, every program is threatened constantly by software patents.

States should not allow patents to restrict development and use of software on general-purpose computers, but in those that do, we wish to avoid the special danger that patents applied to a free program could make it effectively proprietary. To prevent this, the GPL assures that patents cannot be used to render the program non-free.

The precise terms and conditions for copying, distribution and modification follow.

TERMS AND CONDITIONS

0. Definitions.

"This License" refers to version 3 of the GNU General Public License.

"Copyright" also means copyright-like laws that apply to other kinds of works, such as semiconductor masks.

"The Program" refers to any copyrightable work licensed under this License. Each licensee is addressed as "you". "Licensees" and "recipients" may be individuals or organizations.

To "modify" a work means to copy from or adapt all or part of the work in a fashion requiring copyright permission, other than the making of an exact copy. The resulting work is called a "modified version" of the earlier work or a work "based on" the earlier work.

A "covered work" means either the unmodified Program or a work based on the Program.

To "propagate" a work means to do anything with it that, without permission, would make you directly or secondarily liable for infringement under applicable copyright law, except executing it on a computer or modifying a private copy. Propagation includes copying, distribution (with or without modification), making available to the public, and in some countries other activities as well.

To "convey" a work means any kind of propagation that enables other parties to make or receive copies. Mere interaction with a user through a computer network, with no transfer of a copy, is not conveying.

An interactive user interface displays "Appropriate Legal Notices" to the extent that it includes a convenient and prominently visible feature that (1) displays an appropriate copyright notice, and (2) tells the user that there is no warranty for the work (except to the extent that warranties are provided), that licensees may convey the

work under this License, and how to view a copy of this License. If the interface presents a list of user commands or options, such as a menu, a prominent item in the list meets this criterion.

1. Source Code.

The "source code" for a work means the preferred form of the work for making modifications to it. "Object code" means any non-source form of a work.

A "Standard Interface" means an interface that either is an official standard defined by a recognized standards body, or, in the case of interfaces specified for a particular programming language, one that is widely used among developers working in that language.

The

"System Libraries" of an executable work include anything, other than the work as a whole, that (a) is included in the normal form of packaging a Major Component, but which is not part of that Major Component, and (b) serves only to enable use of the work with that Major Component, or to implement a Standard Interface for which an implementation is available to the public in source code form. A "Major Component", in this context, means a major essential component (kernel, window system, and so on) of the specific operating system (if any) on which the executable work runs, or a compiler used to produce the work, or an object code interpreter used to run it.

The "Corresponding Source" for a work in object code form means all the source code needed to generate, install, and (for an executable work) run the object code and to modify the work, including scripts to control those activities. However, it does not include the work's System Libraries, or general-purpose tools or generally available free programs which are used unmodified in performing those activities but which are not part of the work. For example, Corresponding Source includes interface definition files associated with source files for the work, and the source code for shared libraries and dynamically linked subprograms that the work is specifically designed to require, such as by intimate data communication or control flow between those subprograms and other parts of the work.

The Corresponding Source need not include anything that users can regenerate automatically from other parts of the Corresponding Source.

The Corresponding Source for a work in source code form is that same work.

2. Basic Permissions.

All rights granted under this License are granted for the term of copyright on the Program, and are irrevocable provided the stated conditions are met. This License explicitly affirms your unlimited permission to run the unmodified Program. The output from running a covered work is covered

by this License only if the output, given its content, constitutes a covered work. This License acknowledges your rights of fair use or other equivalent, as provided by copyright law.

You may make, run and propagate covered works that you do not convey, without conditions so long as your license otherwise remains in force. You may convey covered works to others for the sole purpose of having them make modifications exclusively for you, or provide you with facilities for running those works, provided that you comply with the terms of this License in conveying all material for which you do not control copyright. Those thus making or running the covered works for you must do so exclusively on your behalf, under your direction and control, on terms that prohibit them from making any copies of your copyrighted material outside their relationship with you.

Conveying under any other circumstances is permitted solely under the conditions stated below. Sublicensing is not allowed; section 10 makes it unnecessary.

3. Protecting Users' Legal Rights From Anti-Circumvention Law.

No covered work shall be deemed part of an effective technological measure under any applicable law fulfilling obligations under article 11 of the WIPO copyright treaty adopted on 20 December 1996, or similar laws prohibiting or restricting circumvention of such measures.

When you convey a covered work, you waive any legal power to forbid circumvention of technological measures to the extent such circumvention is effected by exercising rights under this License with respect to the covered work, and you disclaim any intention to limit operation or modification of the work as a means of enforcing, against the work's users, your or third parties' legal rights to forbid circumvention of technological measures.

4. Conveying Verbatim Copies.

You may convey verbatim copies of the Program's source code as you receive it, in any medium, provided that you conspicuously and appropriately

publish on each copy an appropriate copyright notice;
keep intact all notices stating that this License and any
non-permissive terms added in accord with section 7 apply to the code;
keep intact all notices of the absence of any warranty; and give all
recipients a copy of this License along with the Program.

You may charge any price or no price for each copy that you convey,
and you may offer support or warranty protection for a fee.

5. Conveying Modified Source Versions.

You may convey a work based on the Program, or the modifications to
produce it from the Program, in the form of source code under the
terms of section 4, provided that you also meet all of these conditions:

- a) The work must carry prominent notices stating that you modified
it, and giving a relevant date.

- b) The work must carry prominent notices stating that it is
released under this License and any conditions added under section
7. This requirement modifies the requirement in section
4 to
"keep intact all notices".

- c) You must license the entire work, as a whole, under this
License to anyone who comes into possession of a copy. This
License will therefore apply, along with any applicable section 7
additional terms, to the whole of the work, and all its parts,
regardless of how they are packaged. This License gives no
permission to license the work in any other way, but it does not
invalidate such permission if you have separately received it.

- d) If the work has interactive user interfaces, each must display
Appropriate Legal Notices; however, if the Program has interactive
interfaces that do not display Appropriate Legal Notices, your
work need not make them do so.

A compilation of a covered work with other separate and independent
works, which are not by their nature extensions of the covered work,
and which are not combined with it such as to form a larger program,
in or on a volume of a storage or distribution
medium, is called an
"aggregate" if the compilation and its resulting copyright are not
used to limit the access or legal rights of the compilation's users
beyond what the individual works permit. Inclusion of a covered work
in an aggregate does not cause this License to apply to the other
parts of the aggregate.

6. Conveying Non-Source Forms.

You may convey a covered work in object code form under the terms of sections 4 and 5, provided that you also convey the machine-readable Corresponding Source under the terms of this License, in one of these ways:

- a) Convey the object code in, or embodied in, a physical product (including a physical distribution medium), accompanied by the Corresponding Source fixed on a durable physical medium customarily used for software interchange.
- b) Convey the object code in, or embodied in, a physical product (including a physical distribution medium), accompanied by a written offer, valid for at least three years and valid for as long as you offer spare parts or customer support for that product model, to give anyone who possesses the object code either (1) a copy of the Corresponding Source for all the software in the product that is covered by this License, on a durable physical medium customarily used for software interchange, for a price no more than your reasonable cost of physically performing this conveying of source, or (2) access to copy the Corresponding Source from a network server at no charge.
- c) Convey individual copies of the object code with a copy of the written offer to provide the Corresponding Source. This alternative is allowed only occasionally and noncommercially, and only if you received the object code with such an offer, in accord with subsection 6b.
- d) Convey the object code by offering access from a designated place (gratis or for a charge), and offer equivalent access to the Corresponding Source in the same way through the same place at no further charge. You need not require recipients to copy the Corresponding Source along with the object code. If the place to copy the object code is a network server, the Corresponding Source may be on a different server (operated by you or a third party) that supports equivalent copying facilities, provided you maintain clear directions next to the object code saying where to find the Corresponding Source. Regardless of what server hosts the Corresponding Source, you remain obligated to ensure that it is available for as long as needed to satisfy these requirements.
- e) Convey the object code using peer-to-peer transmission, provided you inform other peers where the object code and Corresponding Source of the work are being offered to the general public at no

charge under subsection 6d.

A separable portion of the object code, whose source code is excluded from the Corresponding Source as a System Library, need not be included in conveying the object code work.

A "User Product" is either (1) a "consumer product", which means any tangible personal property which is normally used for personal, family, or household purposes, or (2) anything designed or sold for incorporation into a dwelling. In determining whether a product is a consumer product, doubtful cases shall be resolved in favor of coverage. For a particular product received by a particular user, "normally used" refers to a typical or common use of that class of product, regardless of the status of the particular user or of the way in which the particular user actually uses, or expects or is expected to use, the product. A product is a consumer product regardless of whether the product has substantial commercial, industrial or non-consumer uses, unless such uses represent the only significant mode of use of the product.

"Installation Information" for a User Product means any methods, procedures, authorization keys, or other information required to install and execute modified versions of a covered work in that User Product from a modified version of its Corresponding Source. The information must suffice to ensure that the continued functioning of the modified object code is in no case prevented or interfered with solely because modification has been made.

If you convey an object code work under this section in, or with, or specifically for use in, a User Product, and the conveying occurs as part of a transaction in which the right of possession and use of the User Product is transferred to the recipient in perpetuity or for a fixed term (regardless of how the transaction is characterized), the Corresponding Source conveyed under this section must be accompanied by the Installation Information. But this requirement does not apply if neither you nor any third party retains the ability to install modified object code on the User Product (for example, the work has been installed in ROM).

The requirement to provide Installation Information does not include a requirement to continue to provide support service, warranty, or updates for a work that has been modified or installed by the recipient, or for the User Product in which it has been modified or installed. Access to a network may be denied when the modification itself materially and adversely affects the operation of the network or violates the rules and protocols for communication across the network.

Corresponding Source conveyed, and Installation Information provided, in accord with this section must be in a format that is publicly documented (and with an implementation available to the public in source code form), and must require no special password or key for unpacking, reading or copying.

7. Additional Terms.

"Additional permissions" are terms that supplement the terms of this License by making exceptions from one or more of its conditions. Additional permissions that are applicable to the entire Program shall be treated as though they were included in this License, to the extent that they are valid under applicable law. If additional permissions apply only to part of the Program, that part may be used separately under those permissions, but the entire Program remains governed by this License without regard to the additional permissions.

When you convey a copy of a covered work, you may at your option remove any additional permissions from that copy, or from any part of it. (Additional permissions may be written to require their own removal in certain cases when you modify the work.) You may place additional permissions on material, added by you to a covered work, for which you have or can give appropriate copyright permission.

Notwithstanding any other provision of this License, for material you add to a covered work, you may (if authorized by the copyright holders of that material) supplement the terms of this License with terms:

- a) Disclaiming warranty or limiting liability differently from the terms of sections 15 and 16 of this License; or
- b) Requiring preservation of specified reasonable legal notices or author attributions in that material or in the Appropriate Legal Notices displayed by works containing it; or
- c) Prohibiting misrepresentation of the origin of that material, or requiring that modified versions of such material be marked in reasonable ways as different from the original version; or
- d) Limiting the use for publicity purposes of names of licensors or authors of the material; or
- e) Declining to grant rights under trademark law for use of some trade names, trademarks, or service marks; or

f) Requiring indemnification of licensors and authors of that material by anyone who conveys the material (or modified versions of it) with contractual assumptions of liability to the recipient, for any liability that these contractual assumptions directly impose on

those licensors and authors.

All other non-permissive additional terms are considered "further restrictions" within the meaning of section 10. If the Program as you received it, or any part of it, contains a notice stating that it is governed by this License along with a term that is a further restriction, you may remove that term. If a license document contains a further restriction but permits relicensing or conveying under this License, you may add to a covered work material governed by the terms of that license document, provided that the further restriction does not survive such relicensing or conveying.

If you add terms to a covered work in accord with this section, you must place, in the relevant source files, a statement of the additional terms that apply to those files, or a notice indicating where to find the applicable terms.

Additional terms, permissive or non-permissive, may be stated in the form of a separately written license, or stated as exceptions; the above requirements apply either way.

8. Termination.

You may not propagate or modify a covered work except as expressly provided under this License. Any attempt otherwise to propagate or modify it is void, and will automatically terminate your rights under this License (including any patent licenses granted under the third paragraph of section 11).

However, if you cease all violation of this License, then your license from a particular copyright holder is reinstated (a) provisionally, unless and until the copyright holder explicitly and finally terminates your license, and (b) permanently, if the copyright holder fails to notify you of the violation by some reasonable means prior to 60 days after the cessation.

Moreover, your license from a particular copyright holder is reinstated permanently if the copyright holder notifies you of the violation by some reasonable means, this is the first time you have received notice of violation of this License (for any work) from that copyright

holder, and you cure the violation prior to 30 days after your receipt of the notice.

Termination of your rights under this section does not terminate the licenses of parties who have received copies or rights from you under this License. If your rights have been terminated and not permanently reinstated, you do not qualify to receive new licenses for the same material under section 10.

9. Acceptance Not Required for Having Copies.

You are not required to accept this License in order to receive or run a copy of the Program. Ancillary propagation of a covered work occurring solely as a consequence of using peer-to-peer transmission to receive a copy likewise does not require acceptance. However, nothing other than this License grants you permission to propagate or modify any covered work. These actions infringe copyright if you do not accept this License. Therefore, by modifying or propagating a covered work, you indicate your acceptance of this License to do so.

10. Automatic Licensing of Downstream Recipients.

Each time you convey a covered work, the recipient automatically receives a license from the original licensors, to run, modify and propagate that work, subject to this License. You are not responsible for enforcing compliance by third parties with this License.

An "entity transaction" is a transaction transferring control of an organization, or substantially all assets of one, or subdividing an organization, or merging organizations. If propagation of a covered work results from an entity transaction, each party to that transaction who receives a copy of the work also receives whatever licenses to the work the party's predecessor in interest had or could give under the previous paragraph, plus a right to possession of the Corresponding Source of the work from the predecessor in interest, if the predecessor has it or can get it with reasonable efforts.

You may not impose any further restrictions on the exercise of the rights granted or affirmed under this License. For example, you may not impose a license fee, royalty, or other charge for exercise of rights granted under this License, and you may not initiate litigation (including a cross-claim or counterclaim in a lawsuit) alleging that any patent claim is infringed by making, using, selling, offering for sale, or importing the Program or any portion of it.

11. Patents.

A "contributor" is a copyright holder who authorizes use under this License of the Program or a work on which the Program is based. The work thus licensed is called the contributor's "contributor version".

A contributor's "essential patent claims" are all patent claims owned or controlled by the contributor, whether already acquired or hereafter acquired, that would be infringed by some manner, permitted by this License, of making, using, or selling its contributor version, but do not include claims that would be infringed only as a consequence of further modification of the contributor version. For purposes of this definition, "control" includes the right to grant patent sublicenses in a manner consistent with the requirements of this License.

Each contributor grants you a non-exclusive, worldwide, royalty-free patent license under the contributor's essential patent claims, to make, use, sell, offer for sale, import and otherwise run, modify and propagate the contents of its contributor version.

In the following three paragraphs, a "patent license" is any express agreement or commitment, however denominated, not to enforce a patent (such as an express permission to practice a patent or covenant not to sue for patent infringement). To "grant" such a patent license to a party means to make such an agreement or commitment not to enforce a patent against the party.

If you convey a covered work, knowingly relying on a patent license, and the Corresponding Source of the work is not available for anyone to copy, free of charge and under the terms of this License, through a publicly available network server or other readily accessible means, then you must either (1) cause the Corresponding Source to be so available, or (2) arrange to deprive yourself of the benefit of the patent license for this particular work, or (3) arrange, in a manner consistent with the requirements of this License, to extend the patent license to downstream recipients. "Knowingly relying" means you have actual knowledge that, but for the patent license, your conveying the covered work in a country, or your recipient's use of the covered work in a country, would infringe one or more identifiable patents in that country that you have reason to believe are valid.

If, pursuant to or in connection with a single transaction or arrangement, you convey, or propagate by procuring conveyance of, a covered work, and grant a patent license to some of the parties receiving the covered work authorizing them to use, propagate, modify or convey a specific copy of the covered

work, then the patent license you grant is automatically extended to all recipients of the covered work and works based on it.

A patent license is "discriminatory" if it does not include within the scope of its coverage, prohibits the exercise of, or is conditioned on the non-exercise of one or more of the rights that are specifically granted under this License. You may not convey a covered work if you are a party to an arrangement with a third party that is in the business of distributing software, under which you make payment to the third party based on the extent of your activity of conveying the work, and under which the third party grants, to any of the parties who would receive the covered work from you, a discriminatory patent license (a) in connection with copies of the covered work conveyed by you (or copies made from those copies), or (b) primarily for and in connection with specific products or compilations that contain the covered work, unless you entered into that arrangement, or that patent license was granted, prior to 28 March 2007.

Nothing in this License shall be construed as excluding or limiting any implied license or other defenses to infringement that may otherwise be available to you under applicable patent law.

12. No Surrender of Others' Freedom.

If conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot convey a covered work so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not convey it at all. For example, if you agree to terms that obligate you to collect a royalty for further conveying from those to whom you convey the Program, the only way you could satisfy both those terms and this License would be to refrain entirely from conveying the Program.

13. Use with the GNU Affero General Public License.

Notwithstanding any other provision of this License, you have permission to link or combine any covered work with a work licensed under version 3 of the GNU Affero General Public License into a single combined work, and to convey the resulting work. The terms of this License will continue to apply to the part which is the covered work, but the special requirements of the GNU Affero General Public License, section 13, concerning interaction through a network will apply to the combination as such.

14. Revised Versions of this License.

The Free Software Foundation may publish revised and/or new versions of the GNU General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Program specifies that a certain numbered version of the GNU General Public License "or any later version" applies to it, you have the option of following the terms and conditions either of that numbered version or of any later version published by the Free Software Foundation. If the Program does not specify a version number of the GNU General Public License, you may choose any version ever published by the Free Software Foundation.

If the Program specifies that a proxy can decide which future versions of the GNU General Public License can be used, that proxy's public statement of acceptance of a version permanently authorizes you to choose that version for the Program.

Later license versions may give you additional or different permissions. However, no additional obligations are imposed on any author or copyright holder as a result of your choosing to follow a later version.

15. Disclaimer of Warranty.

THERE IS NO WARRANTY FOR THE PROGRAM, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE PROGRAM "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE PROGRAM IS WITH YOU. SHOULD THE PROGRAM PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

16. Limitation of Liability.

IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MODIFIES AND/OR CONVEYS THE PROGRAM AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE PROGRAM (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE PROGRAM TO OPERATE WITH ANY OTHER PROGRAMS), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF

SUCH DAMAGES.

17.

Interpretation of Sections 15 and 16.

If the disclaimer of warranty and limitation of liability provided above cannot be given local legal effect according to their terms, reviewing courts shall apply local law that most closely approximates an absolute waiver of all civil liability in connection with the Program, unless a warranty or assumption of liability accompanies a copy of the Program in return for a fee.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Programs

If you develop a new program, and you want it to be of the greatest possible use to the public, the best way to achieve this is to make it free software which everyone can redistribute and change under these terms.

To do so, attach the following notices to the program. It is safest to attach them to the start of each source file to most effectively state the exclusion of warranty; and each file should have at least the "copyright" line and a pointer to where the full notice is found.

```
<one line to give the program's name and a brief idea of what it does.>  
Copyright (C) <year> <name of author>
```

```
This program is free software: you can redistribute it and/or modify  
it under the terms of the GNU General Public License as published by  
the Free Software Foundation, either version 3 of the License, or  
(at your option) any later version.
```

```
This program is distributed in the hope that it will be useful,  
but WITHOUT ANY WARRANTY; without even the implied warranty of  
MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the  
GNU General Public License for more details.
```

```
You should have received a copy of the GNU General Public License  
along with this program. If not, see <http://www.gnu.org/licenses/>.
```

Also add information on how to contact you by electronic and paper mail.

If the program does terminal interaction, make it output a short notice like this when it starts in an interactive mode:

<program> Copyright (C) <year> <name of author>

This program comes with ABSOLUTELY NO WARRANTY; for details type 'show w'.

This is free software, and you are welcome to redistribute it under certain conditions; type 'show c' for details.

The hypothetical commands 'show w' and 'show c' should show the appropriate parts of the General Public License. Of course, your program's commands might be different; for a GUI interface, you would use an "about box".

You should also get your employer (if you work as a programmer) or school, if any, to sign a "copyright disclaimer" for the program, if necessary.

For more information on this, and how to apply and follow the GNU GPL, see <<http://www.gnu.org/licenses/>>.

The GNU General Public License does not permit incorporating your program into proprietary programs. If your program is a subroutine library, you may consider it more useful to permit linking proprietary applications with the library. If this is what you want to do, use the GNU Lesser General Public License instead of this License. But first, please read <<http://www.gnu.org/philosophy/why-not-lgpl.html>>.

1.35 libgcc 1:8.4.0-1ubuntu1~18.04

1.35.1 Available under license :

GNU GENERAL PUBLIC LICENSE

Version 2, June 1991

Copyright (C) 1989, 1991 Free Software Foundation, Inc.

51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA

Everyone is permitted to copy and distribute verbatim copies of this license document, but changing it is not allowed.

Preamble

The licenses for most software are designed to take away your freedom to share and change it. By contrast, the GNU General Public License is intended to guarantee your freedom to share and change free software--to make sure the software is free for all its users. This General Public License applies to most of the Free Software Foundation's software and to any other program whose authors commit to using it. (Some other Free Software Foundation software is covered by the GNU Library General Public License instead.) You can apply it to your programs, too.

When we speak of free software, we are referring to freedom, not price. Our General Public Licenses are designed

to make sure that you have the freedom to distribute copies of free software (and charge for this service if you wish), that you receive source code or can get it if you want it, that you can change the software or use pieces of it in new free programs; and that you know you can do these things.

To protect your rights, we need to make restrictions that forbid anyone to deny you these rights or to ask you to surrender the rights. These restrictions translate to certain responsibilities for you if you distribute copies of the software, or if you modify it.

For example, if you distribute copies of such a program, whether gratis or for a fee, you must give the recipients all the rights that you have. You must make sure that they, too, receive or can get the source code. And you must show them these terms so they know their rights.

We protect your rights with two steps: (1) copyright the software, and (2) offer you this license which gives you legal permission to copy, distribute and/or modify the software.

Also, for each author's protection and ours, we want to make certain that everyone understands that there is no warranty for this free software. If the software is modified by someone else and passed on, we want its recipients to know that what they have is not the original, so that any problems introduced by others will not reflect on the original authors' reputations.

Finally, any free program is threatened constantly by software patents. We wish to avoid the danger that redistributors of a free program will individually obtain patent licenses, in effect making the program proprietary. To prevent this, we have made it clear that any patent must be licensed for everyone's free use or not licensed at all.

The precise terms and conditions for copying, distribution and modification follow.

GNU GENERAL PUBLIC LICENSE TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

0. This License applies to any program or other work which contains a notice placed by the copyright holder saying it may be distributed under the terms of this General Public License. The "Program", below, refers to any such program or work, and a "work based on the Program" means either the Program or any derivative work under copyright law: that is to say, a work containing the Program or a portion of it,

either verbatim or with modifications and/or translated into another language. (Hereinafter, translation is included without limitation in the term "modification".) Each licensee is addressed as "you".

Activities other than copying, distribution and modification are not covered by this License; they are outside its scope. The act of running the Program is not restricted, and the output from the Program is covered only if its contents constitute a work based on the Program (independent of having been made by running the Program). Whether that is true depends on what the Program does.

1. You may copy and distribute verbatim copies of the Program's source code as you receive it, in any medium, provided that you conspicuously and appropriately publish on each copy an appropriate copyright notice and disclaimer of warranty; keep intact all the notices that refer to this License and to the absence of any warranty; and give any other recipients of the Program a copy of this License along with the Program.

You may charge a fee for the physical act of transferring a copy, and you may at your option offer warranty protection in exchange for a fee.

2. You may modify your copy or copies of the Program or any portion of it, thus forming a work based on the Program, and copy and distribute such modifications or work under the terms of Section 1 above, provided that you also meet all of these conditions:

- a) You must cause the modified files to carry prominent notices stating that you changed the files and the date of any change.
- b) You must cause any work that you distribute or publish, that in

whole or in part contains or is derived from the Program or any part thereof, to be licensed as a whole at no charge to all third parties under the terms of this License.

- c) If the modified program normally reads commands interactively when run, you must cause it, when started running for such interactive use in the most ordinary way, to print or display an announcement including an appropriate copyright notice and a notice that there is no warranty (or else, saying that you provide a warranty) and that users may redistribute the program under these conditions, and telling the user how to view a copy of this License. (Exception: if the Program itself is interactive but does not normally print such an announcement, your work based on the Program is not required to print an announcement.)

These requirements apply to the modified work as a whole. If identifiable sections of that work are not derived from the Program, and can be reasonably considered independent and separate works in themselves, then this License, and its terms, do not apply to those sections when you distribute them as separate works. But when you distribute the same sections as part of a whole which is a work based on the Program, the distribution of the whole must be on the terms of this License, whose permissions for other licensees extend to the entire whole, and thus to each and every part regardless of who wrote it.

Thus, it is not the intent of this section to claim rights or contest your rights to work written entirely by you; rather, the intent is to exercise the right to control the distribution of derivative or collective works based on the Program.

In addition, mere aggregation of another work not based on the Program with the Program (or with a work based on the Program) on a volume of a storage or distribution medium does not bring the other work under the scope of this License.

3. You may copy and distribute the Program (or a work based on it, under Section 2) in object code or executable form under the terms of Sections 1 and 2 above provided that you also do one of the following:

- a) Accompany it with the complete corresponding machine-readable source code, which must be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange; or,
- b) Accompany it with a written offer, valid for at least three years, to give any third party, for a charge no more than your cost of physically performing source distribution, a complete machine-readable copy of the corresponding source code, to be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange; or,
- c) Accompany it with the information you received as to the offer to distribute corresponding source code. (This alternative is allowed only for noncommercial distribution and only if you received the program in object code or executable form with such an offer, in accord with Subsection b above.)

The source code for a work means the preferred form of the work for making modifications to it. For an executable work, complete source code means all the source code for all modules it contains, plus any associated interface definition files, plus the scripts used to

control compilation and installation of the executable. However, as a special exception, the source code distributed need not include anything that is normally distributed (in either source or binary form) with the major components (compiler, kernel, and so on) of the operating system on which the executable runs, unless that component itself accompanies the executable.

If distribution of executable or object code is made by offering access to copy from a designated place, then offering equivalent access to copy the source code from the same place counts as distribution of the source code, even though third parties are not compelled to copy the source along with the object code.

4. You may not copy, modify, sublicense, or distribute the Program except as expressly provided under this License. Any attempt otherwise to copy, modify, sublicense or distribute the Program is void, and will automatically terminate your rights under this License. However, parties who have received copies, or rights, from you under this License will not have their licenses terminated so long as such parties remain in full compliance.

5. You are not required to accept this License, since you have not signed it. However, nothing else grants you permission to modify or distribute the Program or its derivative works. These actions are prohibited by law if you do not accept this License. Therefore, by modifying or distributing the Program (or any work based on the Program), you indicate your acceptance of this License to do so, and all its terms and conditions for copying, distributing or modifying the Program or works based on it.

6.

Each time you redistribute the Program (or any work based on the Program), the recipient automatically receives a license from the original licensor to copy, distribute or modify the Program subject to these terms and conditions. You may not impose any further restrictions on the recipients' exercise of the rights granted herein. You are not responsible for enforcing compliance by third parties to this License.

7. If, as a consequence of a court judgment or allegation of patent infringement or for any other reason (not limited to patent issues), conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot distribute so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not distribute the Program at all. For example, if a patent

license would not permit royalty-free redistribution of the Program by all those who receive copies directly or indirectly through you, then the only way you could satisfy both it and this License would be to refrain entirely from distribution of the Program.

If any portion of this section is held invalid or unenforceable under any particular circumstance, the balance of the section is intended to apply and the section as a whole is intended to apply in other circumstances.

It is not the purpose of this section to induce you to infringe any patents or other property right claims or to contest validity of any such claims; this section has the sole purpose of protecting the integrity of the free software distribution system, which is implemented by public license practices. Many people have made generous contributions to the wide range of software distributed through that system in reliance on consistent application of that system; it is up to the author/donor to decide if he or she is willing to distribute software through any other system and a licensee cannot impose that choice.

This section is intended to make thoroughly clear what is believed to be a consequence of the rest of this License.

8. If the distribution and/or use of the Program is restricted in certain countries either by patents or by copyrighted interfaces, the original copyright holder who places the Program under this License may add an explicit geographical distribution limitation excluding those countries, so that distribution is permitted only in or among countries not thus excluded. In such case, this License incorporates the limitation as if written in the body of this License.

9. The Free Software Foundation may publish revised and/or new versions of the General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Program specifies a version number of this License which applies to it and "any later version", you have the option of following the terms and conditions either of that version or of any later version published by the Free Software Foundation. If the Program does not specify a version number of this License, you may choose any version ever published by the Free Software Foundation.

10. If you wish to incorporate parts of the Program into other free programs whose distribution conditions are different, write to the author to ask for permission. For software which is copyrighted by the Free Software Foundation, write to the Free Software Foundation; we sometimes make exceptions for this. Our decision will be guided by the two goals of preserving the free status of all derivatives of our free software and of promoting the sharing and reuse of software generally.

NO WARRANTY

11. BECAUSE THE PROGRAM IS LICENSED FREE OF CHARGE, THERE IS NO WARRANTY FOR THE PROGRAM, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE PROGRAM "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE PROGRAM IS WITH YOU. SHOULD THE PROGRAM PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

12. IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY AND/OR REDISTRIBUTE THE PROGRAM AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE PROGRAM (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE PROGRAM TO OPERATE WITH ANY OTHER PROGRAMS), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Programs

If you develop a new program, and you want it to be of the greatest possible use to the public, the best way to achieve this is to make it free software which everyone can redistribute and change under these terms.

To do so, attach the following notices to the program. It is safest to attach them to the start of each source file to most effectively convey the exclusion of warranty; and each file should have at least the "copyright" line and a pointer to where the full notice is found.

<one line to give the program's name and a brief idea of what it does.>
Copyright (C) <year> <name of author>

This program is free software; you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation; either version 2 of the License, or (at your option) any later version.

This program is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details.

You should have received a copy of the GNU General Public License along with this program; if not, write to the Free Software Foundation, Inc., 51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA

Also add information on how to contact you by electronic and paper mail.

If the program is interactive, make it output a short notice like this when it starts in an interactive mode:

```
Gnomovision version 69, Copyright (C) year name of author
Gnomovision comes with ABSOLUTELY NO WARRANTY; for details type `show w'.
This is free software, and you are welcome to redistribute it
under certain conditions; type `show c' for details.
```

The hypothetical commands ``show w'` and ``show c'` should show the appropriate parts of the General Public License. Of course, the commands you use may be called something other than ``show w'` and ``show c'`; they could even be mouse-clicks or menu items--whatever suits your program.

You should also get your employer (if you work as a programmer) or your school, if any, to sign a "copyright disclaimer" for the program, if necessary. Here is a sample; alter the names:

```
Yoyodyne, Inc., hereby disclaims all copyright interest in the program
`Gnomovision' (which makes passes at compilers) written by James Hacker.
```

```
<signature of Ty Coon>, 1 April 1989
Ty Coon, President of Vice
```

This General Public License does not permit incorporating your program into proprietary programs. If your program is a subroutine library, you may consider it more useful to permit linking proprietary applications with the library. If this is what you want to do, use the GNU Library General Public License instead of this License.

This program, "bzip2", the associated library "libbzip2", and all documentation, are copyright (C) 1996-2010 Julian R Seward. All rights reserved.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

1. Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.
2. The origin of this software must not be misrepresented; you must not claim that you wrote the original software. If you use this software in a product, an acknowledgment in the product documentation would be appreciated but is not required.
3. Altered source versions must be plainly marked as such, and must not be misrepresented as being the original software.
4. The name of the author may not be used to endorse or promote products derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE AUTHOR ``AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE AUTHOR BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

Julian Seward, jseward@bzip.org
bzip2/libbzip2 version 1.0.6 of 6 September 2010

The newlib subdirectory is a collection of software from several sources.

Each file may have its own copyright/license that is embedded in the source file. Unless otherwise noted in the body of the source file(s), the following copyright notices will apply to the contents of the newlib subdirectory:

(1) Red Hat Incorporated

Copyright (c) 1994-2009 Red Hat, Inc. All rights reserved.

This copyrighted material is made available to anyone wishing to use, modify, copy, or redistribute it subject to the terms and conditions of the BSD License. This program is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY expressed or implied, including the implied warranties of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. A copy of this license is available at <http://www.opensource.org/licenses>. Any Red Hat trademarks that are incorporated in the source code or documentation are not subject to the BSD License and may only be used or replicated with the express permission of Red Hat, Inc.

(2) University of California, Berkeley

Copyright (c) 1981-2000 The Regents of the University of California. All rights reserved.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

- * Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.
- * Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.
- * Neither the name of the University nor the names of its contributors may be used to endorse or promote products derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED.

IN NO EVENT SHALL THE COPYRIGHT OWNER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT

NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

(3) David M. Gay (AT&T 1991, Lucent 1998)

The author of this software is David M. Gay.

Copyright (c) 1991 by AT&T.

Permission to use, copy, modify, and distribute this software for any purpose without fee is hereby granted, provided that this entire notice is included in all copies of any software which is or includes a copy or modification of this software and in all copies of the supporting documentation for such software.

THIS SOFTWARE IS BEING PROVIDED "AS IS", WITHOUT ANY EXPRESS OR IMPLIED WARRANTY. IN PARTICULAR, NEITHER THE AUTHOR NOR AT&T MAKES ANY REPRESENTATION OR WARRANTY OF ANY KIND CONCERNING THE MERCHANTABILITY OF THIS SOFTWARE OR ITS FITNESS FOR ANY PARTICULAR PURPOSE.

The author of this software is David M. Gay.

Copyright (C) 1998-2001 by Lucent Technologies
All Rights Reserved

Permission to use, copy, modify, and distribute this software and its documentation for any purpose and without fee is hereby granted, provided that the above copyright notice appear in all copies and that both that the copyright notice and this permission notice and warranty disclaimer appear in supporting documentation, and that the name of Lucent or any of its entities not be used in advertising or publicity pertaining to distribution of the software without specific, written prior permission.

LUCENT
DISCLAIMS ALL WARRANTIES WITH REGARD TO THIS SOFTWARE, INCLUDING ALL IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS. IN NO EVENT SHALL LUCENT OR ANY OF ITS ENTITIES BE LIABLE FOR ANY SPECIAL, INDIRECT OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES WHATSOEVER RESULTING FROM LOSS OF USE, DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE OR OTHER TORTIOUS ACTION, ARISING OUT OF OR IN CONNECTION WITH THE USE OR PERFORMANCE OF THIS SOFTWARE.

(4) Advanced Micro Devices

Copyright 1989, 1990 Advanced Micro Devices, Inc.

This software is the property of Advanced Micro Devices, Inc (AMD) which specifically grants the user the right to modify, use and distribute this software provided this notice is not removed or altered. All other rights are reserved by AMD.

AMD MAKES NO WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, WITH REGARD TO THIS SOFTWARE. IN NO EVENT SHALL AMD BE LIABLE FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES IN CONNECTION WITH OR ARISING FROM THE FURNISHING, PERFORMANCE, OR USE OF THIS SOFTWARE.

So that all may benefit from your experience, please report any problems or suggestions about this software to the 29K Technical Support Center at 800-29-29-AMD (800-292-9263) in the USA, or 0800-89-1131 in the UK, or 0031-11-1129 in Japan, toll free. The direct dial number is 512-462-4118.

Advanced Micro Devices, Inc.
29K Support Products
Mail Stop 573
5900 E. Ben White Blvd.
Austin, TX 78741
800-292-9263

(5)

(6)

(7) Sun Microsystems

Copyright (C) 1993 by Sun Microsystems, Inc. All rights reserved.

Developed at SunPro, a Sun Microsystems, Inc. business.
Permission to use, copy, modify, and distribute this software is freely granted, provided that this notice is preserved.

(8) Hewlett Packard

(c) Copyright 1986 HEWLETT-PACKARD COMPANY

To anyone who acknowledges that this file is provided "AS IS" without any express or implied warranty:

permission to use, copy, modify, and distribute this file for any purpose is hereby granted without fee, provided that the above copyright notice and this notice appears in all

copies, and that the name of Hewlett-Packard Company not be used in advertising or publicity pertaining to distribution of the software without specific, written prior permission. Hewlett-Packard Company makes no representations about the suitability of this software for any purpose.

(9) Hans-Peter Nilsson

Copyright (C) 2001 Hans-Peter Nilsson

Permission to use, copy, modify, and distribute this software is freely granted, provided that the above copyright notice, this notice and the following disclaimer are preserved with no changes.

THIS SOFTWARE IS PROVIDED ``AS IS" AND WITHOUT ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, WITHOUT LIMITATION, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE.

(10) Stephane Carrez (m68hc11-elf/m68hc12-elf targets only)

Copyright (C) 1999, 2000, 2001, 2002 Stephane Carrez (stcarrez@nerim.fr)

The authors hereby grant permission to use, copy, modify, distribute, and license this software and its documentation for any purpose, provided that existing copyright notices are retained in all copies and that this notice is included verbatim in any distributions. No written agreement, license, or royalty fee is required for any of the authorized uses. Modifications to this software may be copyrighted by their authors and need not follow the licensing terms described here, provided that the new terms are clearly indicated on the first page of each file where they apply.

(11) Christopher G. Demetriou

Copyright (c) 2001 Christopher G. Demetriou
All rights reserved.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

1. Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.
2. Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.

3. The name of the author may not be used to endorse or promote products derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE AUTHOR ``AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE AUTHOR BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

(12) SuperH, Inc.

Copyright

2002 SuperH, Inc. All rights reserved

This software is the property of SuperH, Inc (SuperH) which specifically grants the user the right to modify, use and distribute this software provided this notice is not removed or altered. All other rights are reserved by SuperH.

SUPERH MAKES NO WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, WITH REGARD TO THIS SOFTWARE. IN NO EVENT SHALL SUPERH BE LIABLE FOR INDIRECT, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES IN CONNECTION WITH OR ARISING FROM THE FURNISHING, PERFORMANCE, OR USE OF THIS SOFTWARE.

So that all may benefit from your experience, please report any problems or suggestions about this software to the SuperH Support Center via e-mail at softwaresupport@superh.com .

SuperH, Inc.

405 River Oaks Parkway

San Jose

CA 95134

USA

(13) Royal Institute of Technology

Copyright (c) 1999 Kungliga Tekniska Hgskolan

(Royal Institute of Technology, Stockholm, Sweden).

All rights reserved.

Redistribution and use in source and binary

forms, with or without

modification, are permitted provided that the following conditions

are met:

1. Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.
2. Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.
3. Neither the name of KTH nor the names of its contributors may be used to endorse or promote products derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY KTH AND ITS CONTRIBUTORS ``AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL KTH OR ITS CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

(14) Alexey Zelkin

Copyright (c) 2000, 2001 Alexey Zelkin <phantom@FreeBSD.org>
All rights reserved.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

1. Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.
2. Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.

THIS SOFTWARE IS PROVIDED BY THE AUTHOR AND CONTRIBUTORS ``AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE AUTHOR OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION)

HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

(15) Andrey A. Chernov

Copyright (C) 1997 by Andrey A. Chernov, Moscow, Russia.
All rights reserved.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

1. Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.
2. Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.

THIS SOFTWARE IS PROVIDED BY THE AUTHOR ``AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE REGENTS OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

(16)

FreeBSD

Copyright (c) 1997-2002 FreeBSD Project.
All rights reserved.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

1. Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.
2. Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.

THIS SOFTWARE IS PROVIDED BY THE AUTHOR AND CONTRIBUTORS ``AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE

IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE AUTHOR OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

(17) S. L. Moshier

Author: S. L. Moshier.

Copyright (c) 1984,2000 S.L. Moshier

Permission to use, copy, modify, and distribute this software for any purpose without fee is hereby granted, provided that this entire notice is included in all copies of any software which is or includes a copy or modification of this software and in all copies of the supporting documentation for such software.

THIS SOFTWARE IS BEING PROVIDED "AS IS", WITHOUT ANY EXPRESS OR IMPLIED WARRANTY. IN PARTICULAR, THE AUTHOR MAKES NO REPRESENTATION OR WARRANTY OF ANY KIND CONCERNING THE MERCHANTABILITY OF THIS SOFTWARE OR ITS FITNESS FOR ANY PARTICULAR PURPOSE.

(18) Citrus Project

Copyright (c)1999 Citrus Project,
All
rights reserved.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

1. Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.
2. Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.

THIS SOFTWARE IS PROVIDED BY THE AUTHOR AND CONTRIBUTORS ``AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE AUTHOR OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL

DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION)

HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

(19) Todd C. Miller

Copyright (c) 1998 Todd C. Miller <Todd.Miller@courtesan.com>

All rights reserved.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

1. Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.
2. Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.
3. The name of the author may not be used to endorse or promote products derived from this software without specific prior written permission.

THIS SOFTWARE

IS PROVIDED ``AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE AUTHOR BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

(20) DJ Delorie (i386 / arm)

Copyright (C) 1991 DJ Delorie

All rights reserved.

Redistribution, modification, and use in source and binary forms is permitted provided that the above copyright notice and following paragraph are duplicated in all such forms.

This file is distributed WITHOUT ANY WARRANTY; without even the implied

warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.

(21) Free Software Foundation LGPL License (*-linux* targets only)

Copyright (C) 1990-1999, 2000, 2001 Free Software Foundation, Inc.
This file is part of the GNU C Library.
Contributed by Mark Kettenis <kettenis@phys.uva.nl>, 1997.

The GNU C Library is free software; you can redistribute it and/or modify it under the terms of the GNU Lesser General Public License as published by the Free Software Foundation; either version 2.1 of the License, or (at your option) any later version.

The GNU C Library is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU Lesser General Public License for more details.

You should have received a copy of the GNU Lesser General Public License along with the GNU C Library; if not, write to the Free Software Foundation, Inc., 51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA.

(22) Xavier Leroy LGPL License (i[3456]86-*-linux* targets only)

Copyright (C) 1996 Xavier Leroy (Xavier.Leroy@inria.fr)

This program is free software; you can redistribute it and/or modify it under the terms of the GNU Library General Public License as published by the Free Software Foundation; either version 2 of the License, or (at your option) any later version.

This program is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU Library General Public License for more details.

(23) Intel (i960)

Copyright (c) 1993 Intel Corporation

Intel hereby grants you permission to copy, modify, and distribute this software and its documentation. Intel grants this permission provided that the above copyright notice appears in all copies and that both the copyright notice and this permission notice appear in supporting documentation. In addition, Intel grants this permission provided that you prominently mark as "not part of the original" any modifications made to this software or documentation, and that the name of Intel

Corporation not be used in advertising or publicity pertaining to distribution of the software or the documentation without specific, written prior permission.

Intel Corporation provides this AS IS, WITHOUT ANY WARRANTY, EXPRESS OR IMPLIED, INCLUDING, WITHOUT LIMITATION, ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Intel makes no guarantee or representations regarding the use of, or the results of the use of, the software and documentation in terms of correctness, accuracy, reliability, currentness, or otherwise; and you rely on the software, documentation and results solely at your own risk.

IN NO EVENT SHALL INTEL BE LIABLE FOR ANY LOSS OF USE, LOSS OF BUSINESS, LOSS OF PROFITS, INDIRECT, INCIDENTAL, SPECIAL OR CONSEQUENTIAL DAMAGES OF ANY KIND. IN NO EVENT SHALL INTEL'S TOTAL LIABILITY EXCEED THE SUM PAID TO INTEL FOR THE PRODUCT LICENSED HEREUNDER.

(24) Hewlett-Packard (hppa targets only)

(c) Copyright 1986 HEWLETT-PACKARD COMPANY

To anyone who acknowledges that this file is provided "AS IS" without any express or implied warranty:

permission to use, copy, modify, and distribute this file for any purpose is hereby granted without fee, provided that the above copyright notice and this notice appears in all copies, and that the name of Hewlett-Packard Company not be used in advertising or publicity pertaining to distribution of the software without specific, written prior permission. Hewlett-Packard Company makes no representations about the suitability of this software for any purpose.

(25) Henry Spencer (only *-linux targets)

Copyright 1992, 1993, 1994 Henry Spencer. All rights reserved. This software is not subject to any license of the American Telephone and Telegraph Company or of the Regents of the University of California.

Permission is granted to anyone to use this software for any purpose on any computer system, and to alter it and redistribute it, subject to the following restrictions:

1. The author is not responsible for the consequences of use of this software, no matter how awful, even if they arise from flaws in it.
2. The origin of this software must not be misrepresented, either by

explicit claim or by omission. Since few users ever read sources, credits must appear in the documentation.

3. Altered versions must be plainly marked as such, and must not be misrepresented as being the original software. Since few users ever read sources, credits must appear in the documentation.
4. This notice may not be removed or altered.

(26) Mike Barcroft

Copyright (c) 2001 Mike Barcroft <mike@FreeBSD.org>
All rights reserved.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

1. Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.
2. Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.

THIS SOFTWARE IS PROVIDED BY THE AUTHOR AND CONTRIBUTORS ``AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE AUTHOR OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

(27) Konstantin Chuguev (--enable-newlib-iconv)

Copyright (c) 1999, 2000
Konstantin Chuguev. All rights reserved.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

1. Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.
2. Redistributions in binary form must reproduce the above copyright

notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.

THIS SOFTWARE IS PROVIDED BY THE AUTHOR AND CONTRIBUTORS ``AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE AUTHOR OR CONTRIBUTORS BE LIABLE FOR

ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

iconv (Charset Conversion Library) v2.0

(28) Artem Bityuckiy (--enable-newlib-iconv)

Copyright (c) 2003, Artem B. Bityuckiy, SoftMine Corporation.
Rights transferred to Franklin Electronic Publishers.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

1. Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.
2. Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.

THIS SOFTWARE IS PROVIDED BY THE AUTHOR AND CONTRIBUTORS ``AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE AUTHOR OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

(29) IBM, Sony, Toshiba (only spu-* targets)

(C) Copyright 2001,2006,
International Business Machines Corporation,

Sony Computer Entertainment, Incorporated,
Toshiba Corporation,

All rights reserved.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

- * Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.
- * Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.
- * Neither the names of the copyright holders nor the names of their contributors may be used to endorse or promote products derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

(30) - Alex Tatmanjants (targets using libc/posix)

Copyright (c) 1995 Alex Tatmanjants <alex@elvisti.kiev.ua>
at Electronni Visti IA, Kiev, Ukraine.
All rights reserved.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

1. Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.
2. Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.

THIS SOFTWARE IS PROVIDED BY THE AUTHOR ``AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE

IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE AUTHOR BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

(31) - M. Warner Losh (targets using libc/posix)

Copyright (c) 1998, M. Warner Losh <imp@freebsd.org>
All rights reserved.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

1. Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.
2. Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.

THIS SOFTWARE IS PROVIDED BY THE AUTHOR AND CONTRIBUTORS ``AS IS'' AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE AUTHOR OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

(32) - Andrey A. Chernov (targets using libc/posix)

Copyright (C) 1996 by Andrey A. Chernov, Moscow, Russia.
All rights reserved.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

1. Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.

2. Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.

THIS SOFTWARE IS PROVIDED BY THE AUTHOR ``AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE REGENTS OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

(33) - Daniel Eischen (targets using libc/posix)

Copyright (c) 2001 Daniel Eischen <deischen@FreeBSD.org>.
All rights reserved.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

1. Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.
2. Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.

THIS SOFTWARE IS PROVIDED BY THE AUTHOR AND CONTRIBUTORS ``AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE REGENTS OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

(34) - Jon Beniston (only lm32-* targets)

Contributed by Jon Beniston <jon@beniston.com>

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

1. Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.
2. Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.

THIS SOFTWARE IS PROVIDED BY THE AUTHOR AND CONTRIBUTORS ``AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED.

IN NO EVENT SHALL THE AUTHOR OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

(35) - Arm Ltd

Copyright (c) 2009-2018 Arm Ltd
All rights reserved.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

1. Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.
2. Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.
3. The name of the company may not be used to endorse or promote products derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY ARM LTD ``AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL ARM LTD BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED

TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

(36) - Xilinx, Inc. (microblaze-* and powerpc-* targets)

Copyright

(c) 2004, 2009 Xilinx, Inc. All rights reserved.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

1. Redistributions source code must retain the above copyright notice, this list of conditions and the following disclaimer.
2. Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.
3. Neither the name of Xilinx nor the names of its contributors may be used to endorse or promote products derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDER AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT HOLDER

OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

(37) Texas Instruments Incorporated (tic6x-*, *-tirtos targets)

Copyright (c) 1996-2010,2014 Texas Instruments Incorporated

<http://www.ti.com/>

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.

Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.

Neither the name of Texas Instruments Incorporated nor the names of its contributors may be used to endorse or promote products derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

(38) National Semiconductor (cr16-* and crx-* targets)

Copyright (c) 2004 National Semiconductor Corporation

The authors hereby grant permission to use, copy, modify, distribute, and license this software and its documentation for any purpose, provided that existing copyright notices are retained in all copies and that this notice is included verbatim in any distributions. No written agreement, license, or royalty fee is required for any of the authorized uses. Modifications to this software may be copyrighted by their authors and need not follow the licensing terms described here, provided that the new terms are clearly indicated on the first page of each file where they apply.

(39) - Adapteva, Inc. (epiphany-* targets)

Copyright (c) 2011, Adapteva, Inc.
All rights reserved.

Redistribution and use in source and binary

forms, with or without

modification, are permitted provided that the following conditions are met:

- * Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.
- * Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.
- * Neither the name of Adapteva nor the names of its contributors may be used to endorse or promote products derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT HOLDER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES

(INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

(40) - Altera Corporation (nios2-* targets)

Copyright (c) 2003 Altera Corporation

All rights reserved.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

- o Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.
- o Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.
- o Neither the name of Altera Corporation nor the names of its contributors may be used to endorse or promote products derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY ALTERA CORPORATION, THE COPYRIGHT HOLDER, AND ITS CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT HOLDER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING,

BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

(41) Ed Schouten - Free
BSD

Copyright (c) 2008 Ed Schouten <ed@FreeBSD.org>
All rights reserved.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

1. Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.
2. Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.

THIS SOFTWARE IS PROVIDED BY THE AUTHOR AND CONTRIBUTORS ``AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE AUTHOR OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

(42) - Rolls-Royce Controls and Data Services Limited (visium-* targets)

Copyright (c) 2015 Rolls-Royce Controls and Data Services Limited.
All rights reserved.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

- * Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.
- * Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.
- * Neither the name of Rolls-Royce Controls

and Data Services Limited nor

the names of its contributors may be used to endorse or promote products derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT HOLDER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

(43) - FTDI (ft32-* targets)

Copyright (C) 2014 FTDI (support@ftdichip.com)

The

authors hereby grant permission to use, copy, modify, distribute, and license this software and its documentation for any purpose, provided that existing copyright notices are retained in all copies and that this notice is included verbatim in any distributions. No written agreement, license, or royalty fee is required for any of the authorized uses. Modifications to this software may be copyrighted by their authors and need not follow the licensing terms described here, provided that the new terms are clearly indicated on the first page of each file where they apply.

(44) - Synopsys Inc (arc-* targets)

Copyright (c) 2015, Synopsys, Inc. All rights reserved.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

1) Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.

2) Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.

3) Neither the name of the Synopsys, Inc., nor the names of its contributors may be used to endorse or promote products derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT HOLDER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

(45) Phoenix Systems - Phoenix-RTOS targets

Copyright (c) 2016 Phoenix Systems
All rights reserved.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

1. Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.
2. Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.

THIS SOFTWARE IS PROVIDED BY THE AUTHOR AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE AUTHOR OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

(46) embedded brains - RTEMS targets

Copyright (c) 2017 embedded brains GmbH
All rights reserved.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions

are met:

1. Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.
2. Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.

THIS SOFTWARE IS PROVIDED BY THE AUTHOR AND CONTRIBUTORS ``AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE AUTHOR OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

(47) John Baldwin - RTEMS targets

Copyright (c) 2015 John Baldwin <jhb@FreeBSD.org>.
All rights reserved.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

1. Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.
2. Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.
3. Neither the name of the author nor the names of its contributors may be used to endorse or promote products derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE REGENTS AND CONTRIBUTORS ``AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE REGENTS OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY

OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

(48) Jeffrey Roberson - RTEMS targets

Copyright (c) 2008, Jeffrey Roberson <jeff@freebsd.org>
All rights reserved.

Copyright (c) 2008 Nokia Corporation
All rights reserved.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

1. Redistributions of source code must retain the above copyright notice unmodified, this list of conditions, and the following disclaimer.
2. Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.

THIS SOFTWARE IS PROVIDED
BY THE AUTHOR ``AS IS" AND ANY EXPRESS OR
IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES
OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED.
IN NO EVENT SHALL THE AUTHOR BE LIABLE FOR ANY DIRECT, INDIRECT,
INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT
NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE,
DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY
THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT
(INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF
THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

(49) - SiFive Inc. (riscv-* targets)

Copyright (c) 2017 SiFive Inc. All rights reserved.

This copyrighted material is made available to anyone wishing to use, modify, copy, or redistribute it subject to the terms and conditions of the FreeBSD License. This program is distributed in the hope that it will be useful,

but WITHOUT ANY WARRANTY expressed or implied, including the implied warranties of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. A copy of this license is available at <http://www.opensource.org/licenses>.

(50) Michael R. Neilly (riscv-* targets)

(c) Copyright 2017 Michael R. Neilly

All rights reserved.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

* Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.

* Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.

* Neither the names of the copyright holders nor the names of their contributors may be used to endorse or promote products derived from this software without specific prior written permission.

THIS SOFTWARE

IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS

"AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

GNU LESSER GENERAL PUBLIC LICENSE

Version 2.1, February 1999

Copyright (C) 1991, 1999 Free Software Foundation, Inc.

51 Franklin St, Fifth Floor, Boston, MA 02110-1301 USA

Everyone is permitted to copy and distribute verbatim copies of this license document, but changing it is not allowed.

[This is the first released version of the Lesser GPL. It also counts as the successor of the GNU Library Public License, version 2, hence the version number 2.1.]

Preamble

The licenses for most software are designed to take away your

freedom to share and change it. By contrast, the GNU General Public Licenses are intended to guarantee your freedom to share and change free software--to make sure the software is free for all its users.

This license, the Lesser General Public License, applies to some specially designated software packages--typically libraries--of the Free Software Foundation and other authors who decide to use it. You can use it too, but we suggest you first think carefully about whether this license or the ordinary General Public License is the better strategy to use in any particular case, based on the explanations below.

When we speak of free software, we are referring to freedom of use, not price. Our General Public Licenses are designed to make sure that you have the freedom to distribute copies of free software (and charge for this service if you wish); that you receive source code or can get it if you want it; that you can change the software and use pieces of it in new free programs; and that you are informed that you can do these things.

To protect your rights, we need to make restrictions that forbid distributors to deny you these rights or to ask you to surrender these rights. These restrictions translate to certain responsibilities for you if you distribute copies of the library or if you modify it.

For example, if you distribute copies of the library, whether gratis or for a fee, you must give the recipients all the rights that we gave you. You must make sure that they, too, receive or can get the source code. If you link other code with the library, you must provide complete object files to the recipients, so that they can relink them with the library after making changes to the library and recompiling it. And you must show them these terms so they know their rights.

We protect your rights with a two-step method: (1) we copyright the library, and (2) we offer you this license, which gives you legal permission to copy, distribute and/or modify the library.

To protect each distributor, we want to make it very clear that there is no warranty for the free library. Also, if the library is modified by someone else and passed on, the recipients should know that what they have is not the original version, so that the original author's reputation will not be affected by problems that might be introduced by others.

Finally, software

patents pose a constant threat to the existence of any free program. We wish to make sure that a company cannot effectively restrict the users of a free program by obtaining a restrictive license from a patent holder. Therefore, we insist that any patent license obtained for a version of the library must be consistent with the full freedom of use specified in this license.

Most GNU software, including some libraries, is covered by the ordinary GNU General Public License. This license, the GNU Lesser General Public License, applies to certain designated libraries, and is quite different from the ordinary General Public License. We use this license for certain libraries in order to permit linking those libraries into non-free programs.

When a program is linked with a library, whether statically or using a shared library, the combination of the two is legally speaking a combined work, a derivative of the original library. The ordinary General Public License therefore permits such linking only if the entire combination fits its criteria of freedom. The Lesser General Public License permits more lax criteria for linking other code with the library.

We call this license the "Lesser" General Public License because it does Less to protect the user's freedom than the ordinary General Public License. It also provides other free software developers Less of an advantage over competing non-free programs. These disadvantages are the reason we use the ordinary General Public License for many libraries. However, the Lesser license provides advantages in certain special circumstances.

For example, on rare occasions, there may be a special need to encourage the widest possible use of a certain library, so that it becomes a de-facto standard. To achieve this, non-free programs must be allowed to use the library. A more frequent case is that a free library does the same job as widely used non-free libraries. In this case, there is little gain by limiting the free library to free software only, so we use the Lesser General Public License.

In other cases, permission to use a particular library in non-free programs enables a greater number of people to use a large body of free software. For example, permission to use the GNU C Library in non-free programs enables many more people to use the whole GNU operating system, as well as its variant, the GNU/Linux operating system.

Although the Lesser General Public License is Less protective of the

users' freedom, it does ensure that the user of a program that is linked with the Library has the freedom and the wherewithal to run that program using a modified version of the Library.

The precise terms and conditions for copying, distribution and modification follow. Pay close attention to the difference between a "work based on the library" and a "work that uses the library". The former contains code derived from the library, whereas the latter must be combined with the library in order to run.

GNU LESSER GENERAL PUBLIC LICENSE TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

0. This License Agreement applies to any software library or other program which contains a notice placed by the copyright holder or other authorized party saying it may be distributed under the terms of this Lesser General Public License (also called "this License"). Each licensee is addressed as "you".

A "library" means a collection of software functions and/or data prepared so as to be conveniently linked with application programs (which use some of those functions and data) to form executables.

The "Library", below, refers to any such software library or work which has been distributed under these terms. A "work based on the Library" means either the Library or any derivative work under copyright law: that is to say, a work containing the Library or a portion of it, either verbatim or with modifications and/or translated straightforwardly into another language. (Hereinafter, translation is included without limitation in the term "modification".)

"Source code" for a work means the preferred form of the work for making modifications to it. For a library, complete source code means all the source code for all modules it contains, plus any associated interface definition files, plus the scripts used to control compilation and installation of the library.

Activities other than copying, distribution and modification are not covered by this License; they are outside its scope. The act of running a program using the Library is not restricted, and output from such a program is covered only if its contents constitute a work based on the Library (independent of the use of the Library in a tool for writing it). Whether that is true depends on what the Library does and what the program that uses the Library does.

1. You may copy and distribute verbatim copies of the Library's

complete source code as you receive it, in any medium, provided that you conspicuously and appropriately publish on each copy an appropriate copyright notice and disclaimer of warranty; keep intact all the notices that refer to this License and to the absence of any warranty; and distribute a copy of this License along with the Library.

You may charge a fee for the physical act of transferring a copy, and you may at your option offer warranty protection in exchange for a fee.

2. You may modify your copy or copies of the Library or any portion of it, thus forming a work based on the Library, and copy and distribute such modifications or work under the terms of Section 1 above, provided that you also meet all of these conditions:

- a) The modified work must itself be a software library.
- b) You must cause the files modified to carry prominent notices stating that you changed the files and the date of any change.
- c) You must cause the whole of the work to be licensed at no charge to all third parties under the terms of this License.
- d) If a facility in the modified Library refers to a function or a table of data to be supplied by an application program that uses the facility, other than as an argument passed when the facility is invoked, then you must make a good faith effort to ensure that, in the event an application does not supply such function or table, the facility still operates, and performs whatever part of its purpose remains meaningful.

(For example, a function in a library to compute square roots has a purpose that is entirely well-defined independent of the application. Therefore, Subsection 2d requires that any application-supplied function or table used by this function must be optional: if the application does not supply it, the square root function must still compute square roots.)

These requirements apply to the modified work as a whole. If identifiable sections of that work are not derived from the Library, and can be reasonably considered independent and separate works in themselves, then this License, and its terms, do not apply to those sections when you distribute them as separate works. But when you distribute the same sections as part of a whole which is a work based

on the Library, the distribution of the whole must be on the terms of this License, whose permissions for other licensees extend to the entire whole, and thus to each and every part regardless of who wrote it.

Thus, it is not the intent of this section to claim rights or contest your rights to work written entirely by you; rather, the intent is to exercise the right to control the distribution of derivative or collective works based on the Library.

In addition, mere aggregation of another work not based on the Library with the Library (or with a work based on the Library) on a volume of a storage or distribution medium does not bring the other work under the scope of this License.

3. You may opt to apply the terms of the ordinary GNU General Public

License instead of this License to a given copy of the Library. To do this, you must alter all the notices that refer to this License, so that they refer to the ordinary GNU General Public License, version 2, instead of to this License. (If a newer version than version 2 of the ordinary GNU General Public License has appeared, then you can specify that version instead if you wish.) Do not make any other change in these notices.

Once this change is made in a given copy, it is irreversible for that copy, so the ordinary GNU General Public License applies to all subsequent copies and derivative works made from that copy.

This option is useful when you wish to copy part of the code of the Library into a program that is not a library.

4. You may copy and distribute the Library (or a portion or derivative of it, under Section 2) in object code or executable form under the terms of Sections 1 and 2 above provided that you accompany it with the complete corresponding machine-readable source code, which must be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange.

If distribution of object code is made by offering access to copy from a designated place, then offering equivalent access to copy the source code from the same place satisfies the requirement to distribute the source code, even though third parties are not compelled to copy the source along with the object code.

5. A program that contains no derivative of any portion of the Library, but is designed to work with the Library by being compiled or

linked with it, is called a "work that uses the Library". Such a work, in isolation, is not a derivative work of the Library, and therefore falls outside the scope of this License.

However, linking a "work that uses the Library" with the Library creates an executable that is a derivative of the Library (because it contains portions of the Library), rather than a "work that uses the library". The executable is therefore covered by this License. Section 6 states terms for distribution of such executables.

When a "work that uses the Library" uses material from a header file that is part of the Library, the object code for the work may be a derivative work of the Library even though the source code is not. Whether this is true is especially significant if the work can be linked without the Library, or if the work is itself a library. The threshold for this to be true is not precisely defined by law.

If such an object file uses only numerical parameters, data structure layouts and accessors, and small macros and small inline functions (ten lines or less in length), then the use of the object file is unrestricted, regardless of whether it is legally a derivative work. (Executables containing this object code plus portions of the Library will still fall under Section 6.)

Otherwise, if the work is a derivative of the Library, you may distribute the object code for the work under the terms of Section 6. Any executables containing that work also fall under Section 6, whether or not they are linked directly with the Library itself.

6. As an exception to the Sections above, you may also combine or link a "work that uses the Library" with the Library to produce a work containing portions of the Library, and distribute that work under terms of your choice, provided that the terms permit modification of the work for the customer's own use and reverse engineering for debugging such modifications.

You must give prominent notice with each copy of the work that the Library is used in it and that the Library and its use are covered by this License. You must supply a copy of this License. If the work during execution displays copyright notices, you must include the copyright notice for the Library among them, as well as a reference directing the user to the copy of this License. Also, you must do one of these things:

- a) Accompany the

work with the complete corresponding machine-readable source code for the Library including whatever changes were used in the work (which must be distributed under Sections 1 and 2 above); and, if the work is an executable linked with the Library, with the complete machine-readable "work that uses the Library", as object code and/or source code, so that the user can modify the Library and then relink to produce a modified executable containing the modified Library. (It is understood that the user who changes the contents of definitions files in the Library will not necessarily be able to recompile the application to use the modified definitions.)

b) Use a suitable shared library mechanism for linking with the Library. A suitable mechanism is one that (1) uses at run time a copy of the library already present on the user's computer system, rather than copying library functions into the executable, and (2) will operate properly with a modified version of the library, if the user installs one, as long as the modified version is interface-compatible with the version that the work was made with.

c) Accompany the work with a written offer, valid for at least three years, to give the same user the materials specified in Subsection 6a, above, for a charge no more than the cost of performing this distribution.

d) If distribution of the work is made by offering access to copy from a designated place, offer equivalent access to copy the above specified materials from the same place.

e) Verify that the user has already received a copy of these materials or that you have already sent this user a copy.

For an executable, the required form of the "work that uses the Library" must include any data and utility programs needed for reproducing the executable from it. However, as a special exception, the materials to be distributed need not include anything that is normally distributed (in either source or binary form) with the major components (compiler, kernel, and so on) of the operating system on which the executable runs, unless that component itself accompanies the executable.

It may happen that this requirement contradicts the license restrictions of other proprietary libraries that do not normally accompany the operating system. Such a contradiction means you cannot use both them and the Library together in an executable that you distribute.

7. You may place library facilities that are a work based on the Library side-by-side in a single library together with other library facilities not covered by this License, and distribute such a combined library, provided that the separate distribution of the work based on the Library and of the other library facilities is otherwise permitted, and provided that you do these two things:

a) Accompany the combined library with a copy of the same work based on the Library, uncombined with any other library facilities. This must be distributed under the terms of the Sections above.

b) Give prominent notice with the combined library of the fact that part of it is a work based on the Library, and explaining where to find the accompanying uncombined form of the same work.

8. You may not copy, modify, sublicense, link with, or distribute the Library except as expressly provided under this License. Any attempt otherwise to copy, modify, sublicense, link with, or distribute the Library is void, and will automatically terminate your rights under this License. However, parties who have received copies, or rights, from you under this License will not have their licenses terminated so long as such parties remain in full compliance.

9. You are not required to accept this License, since you have not signed it. However, nothing else grants you permission to modify or distribute the Library or its derivative works. These actions are prohibited by law if you do not accept this License. Therefore, by modifying or distributing the Library (or any work based on the Library), you indicate your acceptance of this License to do so, and all its terms and conditions for copying, distributing or modifying the Library or works based on it.

10. Each time you redistribute the Library (or any work based on the Library), the recipient automatically receives a license from the original licensor to copy, distribute, link with or modify the Library subject to these terms and conditions. You may not impose any further restrictions on the recipients' exercise of the rights granted herein. You are not responsible for enforcing compliance by third parties with this License.

11. If, as a consequence of a court judgment or allegation of patent infringement or for any other reason (not limited to patent issues), conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not

excuse

you from the conditions of this License. If you cannot distribute so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not distribute the Library at all. For example, if a patent license would not permit royalty-free redistribution of the Library by all those who receive copies directly or indirectly through you, then the only way you could satisfy both it and this License would be to refrain entirely from distribution of the Library.

If any portion of this section is held invalid or unenforceable under any particular circumstance, the balance of the section is intended to apply, and the section as a whole is intended to apply in other circumstances.

It is not the purpose of this section to induce you to infringe any patents or other property right claims or to contest validity of any such claims; this section has the sole purpose of protecting the integrity of the free software distribution system which is implemented by public license practices. Many people have made generous contributions to the wide range of software distributed through that system in reliance on consistent application of that system; it is up to the author/donor to decide if he or she is willing to distribute software through any other system and a licensee cannot impose that choice.

This section is intended to make thoroughly clear what is believed to be a consequence of the rest of this License.

12. If the distribution and/or use of the Library is restricted in certain countries either by patents or by copyrighted interfaces, the original copyright holder who places the Library under this License may add an explicit geographical distribution limitation excluding those countries, so that distribution is permitted only in or among countries not thus excluded. In such case, this License incorporates the limitation as if written in the body of this License.

13. The Free Software Foundation may publish revised and/or new versions of the Lesser General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Library specifies a version number of this License which applies to it and "any later version", you have the option of following the terms and conditions either of that version or of any later version published by

the Free Software Foundation. If the Library does not specify a license version number, you may choose any version ever published by the Free Software Foundation.

14. If you wish to incorporate parts of the Library into other free programs whose distribution conditions are incompatible with these, write to the author to ask for permission. For software which is copyrighted by the Free Software Foundation, write to the Free Software Foundation; we sometimes make exceptions for this. Our decision will be guided by the two goals of preserving the free status of all derivatives of our free software and of promoting the sharing and reuse of software generally.

NO WARRANTY

15. BECAUSE THE LIBRARY IS LICENSED FREE OF CHARGE, THERE IS NO WARRANTY FOR THE LIBRARY, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE LIBRARY "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE LIBRARY IS WITH YOU. SHOULD THE LIBRARY PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

16. IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY AND/OR REDISTRIBUTE THE LIBRARY AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE LIBRARY (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE LIBRARY TO OPERATE WITH ANY OTHER SOFTWARE), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Libraries

If you develop a new library, and you want it to be of the greatest possible use to the public, we recommend making it free software that everyone can redistribute and change. You can do so by permitting redistribution under these terms (or, alternatively, under the terms of the ordinary General Public License).

To apply these terms, attach the following notices to the library.
It is safest to attach them to the start of each source file to most effectively convey the exclusion of warranty; and each file should have at least the "copyright" line and a pointer to where the full notice is found.

<one line to give the library's name and a brief idea of what it does.>
Copyright (C) <year> <name of author>

This library is free software; you can redistribute it and/or modify it under the terms of the GNU Lesser General Public License as published by the Free Software Foundation; either version 2.1 of the License, or (at your option) any later version.

This library is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU Lesser General Public License for more details.

You should have received a copy of the GNU Lesser General Public License along with this library; if not, write to the Free Software Foundation, Inc., 51 Franklin St, Fifth Floor, Boston, MA 02110-1301 USA

Also add information on how to contact you by electronic and paper mail.

You should also get your employer (if you work as a programmer) or your school, if any, to sign a "copyright disclaimer" for the library, if necessary. Here is a sample; alter the names:

Yoyodyne, Inc., hereby disclaims all copyright interest in the library `Frob' (a library for tweaking knobs) written by James Random Hacker.

<signature of Ty Coon>, 1 April 1990
Ty Coon, President of Vice

That's all there is to it!
Copyright 1992, 1993, 1994 Henry Spencer. All rights reserved.
This software is not subject to any license of the American Telephone and Telegraph Company or of the Regents of the University of California.

Permission is granted to anyone to use this software for any purpose on any computer system, and to alter it and redistribute it, subject to the following restrictions:

1. The author is not responsible for the consequences of use of this software, no matter how awful, even if they arise from flaws in it.
2. The origin of this software must not be misrepresented, either by explicit claim or by omission. Since few users ever read sources, credits must appear in the documentation.
3. Altered versions must be plainly marked as such, and must not be misrepresented as being the original software. Since few users ever read sources, credits must appear in the documentation.
4. This notice may not be removed or altered.

/*-

```

* Copyright (c) 1994
* The Regents of the University of California. All rights reserved.
*
* Redistribution and use in source and binary forms, with or without
* modification, are permitted provided that the following conditions
* are met:
* 1. Redistributions of source code must retain the above copyright
*   notice, this list of conditions and the following disclaimer.
* 2. Redistributions in binary form must reproduce the above copyright
*   notice, this list of conditions and the following disclaimer in the
*   documentation and/or other materials provided with the distribution.
* 4. Neither the name of the University nor the names of its contributors
*   may be used to endorse or promote products derived from this software
*   without specific prior written permission.
*
* THIS SOFTWARE IS PROVIDED BY THE REGENTS AND CONTRIBUTORS ``AS IS" AND
* ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE
* IMPLIED WARRANTIES
OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE
* ARE DISCLAIMED. IN NO EVENT SHALL THE REGENTS OR CONTRIBUTORS BE LIABLE
* FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL
* DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS
* OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION)
* HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT
* LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY
* OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF
* SUCH DAMAGE.
*
* @(#)COPYRIGHT 8.1 (Berkeley) 3/16/94
*/
@ignore
@c Set file name and title for man page.
@setfilename gpl

```

@settitle GNU General Public License
@c man begin SEEALSO
gfdl(7), fsf-funding(7).
@c man end
@c man begin COPYRIGHT
Copyright @copyright{ } 2007 Free Software Foundation, Inc.

Everyone is permitted to copy and distribute verbatim copies of this license document, but changing it is not allowed.

@c man end
@end ignore
@node Copying
@c man begin DESCRIPTION
@unnumbered GNU General Public License
@center Version 3, 29 June 2007

@c This file is intended to be included in another file.

@display
Copyright @copyright{ } 2007 Free Software Foundation, Inc. @url{http://fsf.org/}

Everyone is permitted to copy and distribute verbatim copies of this license document, but changing it is not allowed.

@end display

@heading Preamble

The GNU General Public License is a free, copyleft license for software and other kinds of works.

The licenses for most software and other practical works are designed to take away your freedom to share and change the works. By contrast, the GNU General Public License is intended to guarantee your freedom to share and change all versions of a program--to make sure it remains free software for all its users. We, the Free Software Foundation, use the GNU General Public License for most of our software; it applies also to any other work released this way by its authors. You can apply it to your programs, too.

When we speak of free software, we are referring to freedom, not price. Our General Public Licenses are designed to make sure that you have the freedom to distribute copies of free software (and charge for them if you wish), that you receive source code or can get it if you want it, that you can change the software or use pieces of it in new free programs, and that you know you can do these things.

To protect your rights, we need to prevent others from denying you

these rights or asking you to surrender the rights. Therefore, you have certain responsibilities if you distribute copies of the software, or if you modify it: responsibilities to respect the freedom of others.

For example, if you distribute copies of such a program, whether gratis or for a fee, you must pass on to the recipients the same freedoms that you received. You must make sure that they, too, receive or can get the source code. And you must show them these terms so they know their rights.

Developers that use the GNU GPL protect your rights with two steps: (1) assert copyright on the software, and (2) offer you this License giving you legal permission to copy, distribute and/or modify it.

For the developers' and authors' protection, the GPL clearly explains that there is no warranty for this free software. For both users' and authors' sake, the GPL requires that modified versions be marked as changed, so that their problems will not be attributed erroneously to authors of previous versions.

Some devices are designed to deny users access to install or run modified versions of the software inside them, although the manufacturer can do so. This is fundamentally incompatible with the aim of protecting users' freedom to change the software. The systematic pattern of such abuse occurs in the area of products for individuals to use, which is precisely where it is most unacceptable. Therefore, we have designed this version of the GPL to prohibit the practice for those products. If such problems arise substantially in other domains, we stand ready to extend this provision to those domains in future versions of the GPL, as needed to protect the freedom of users.

Finally, every program is threatened constantly by software patents. States should not allow patents to restrict development and use of software on general-purpose computers, but in those that do, we wish to avoid the special danger that patents applied to a free program could make it effectively proprietary. To prevent this, the GPL assures that patents cannot be used to render the program non-free.

The precise terms and conditions for copying, distribution and modification follow.

@heading TERMS AND CONDITIONS

@enumerate 0

@item Definitions.

``This License" refers to version 3 of the GNU General Public License.

``Copyright" also means copyright-like laws that apply to other kinds of works, such as semiconductor masks.

``The Program" refers to any copyrightable work licensed under this License. Each licensee is addressed as ``you". ``Licensees" and ``recipients" may be individuals or organizations.

To ``modify" a work means to copy from or adapt all or part of the work in a fashion requiring copyright permission, other than the making of an exact copy. The resulting work is called a ``modified version" of the earlier work or a work ``based on" the earlier work.

A ``covered work" means either the unmodified Program or a work based on the Program.

To ``propagate" a work means to do anything with it that, without permission, would make you directly or secondarily liable for infringement under applicable copyright law, except executing it on a computer or modifying a private copy. Propagation includes copying, distribution (with or without modification), making available to the public, and in some countries other activities as well.

To ``convey" a work means any kind of propagation that enables other parties to make or receive copies. Mere interaction with a user through a computer network, with no transfer of a copy, is not conveying.

An interactive user interface displays ``Appropriate Legal Notices" to the extent that it includes a convenient and prominently visible feature that (1) displays an appropriate copyright notice, and (2) tells the user that there is no warranty for the work (except to the extent that warranties are provided), that licensees may convey the work under this License, and how to view a copy of this License. If the interface presents a list of user commands or options, such as a menu, a prominent item in the list meets this criterion.

@item Source Code.

The ``source code" for a work means the preferred form of the work for making modifications to it. ``Object code" means any non-source form of a work.

A "Standard Interface" means an interface that either is an official standard defined by a recognized standards body, or, in the case of interfaces specified for a particular programming language, one that is widely used among developers working in that language.

The "System Libraries" of an executable work include anything, other than the work as a whole, that (a) is included in the normal form of packaging a Major Component, but which is not part of that Major Component, and (b) serves only to enable use of the work with that Major Component, or to implement a Standard Interface for which an implementation is available to the public in source code form. A "Major Component", in this context, means a major essential component (kernel, window system, and so on) of the specific operating system (if any) on which the executable work runs, or a compiler used to produce the work, or an object code interpreter used to run it.

The "Corresponding Source" for a work in object code form means all the source code needed to generate, install, and (for an executable work) run the object code and to modify the work, including scripts to control those activities. However, it does not include the work's System Libraries, or general-purpose tools or generally available free programs which are used unmodified in performing those activities but which are not part of the work. For example, Corresponding Source includes interface definition files associated with source files for the work, and the source code for shared libraries and dynamically linked subprograms that the work is specifically designed to require, such as by intimate data communication or control flow between those subprograms and other parts of the work.

The Corresponding Source need not include anything that users can regenerate automatically from other parts of the Corresponding Source.

The Corresponding Source for a work in source code form is that same work.

@item Basic Permissions.

All rights granted under this License are granted for the term of copyright on the Program, and are irrevocable provided the stated conditions are met. This License explicitly affirms your unlimited permission to run the unmodified Program. The output from running a covered work is covered by this License only if the output, given its content, constitutes a covered work. This License acknowledges your rights of fair use or other equivalent, as provided by copyright law.

You may make, run and propagate covered works that you do not convey, without conditions so long as your license otherwise remains in force.

You may convey covered works to others for the sole purpose of having them make modifications exclusively for you, or provide you with facilities for running those works, provided that you comply with the terms

of this License in conveying all material for which you do not control copyright. Those thus making or running the covered works for you must do so exclusively on your behalf, under your direction and control, on terms that prohibit them from making any copies of your copyrighted material outside their relationship with you.

Conveying under any other circumstances is permitted solely under the conditions stated below. Sublicensing is not allowed; section 10 makes it unnecessary.

@item Protecting Users' Legal Rights From Anti-Circumvention Law.

No covered work shall be deemed part of an effective technological measure under any applicable law fulfilling obligations under article 11 of the WIPO copyright treaty adopted on 20 December 1996, or similar laws prohibiting or restricting circumvention of such measures.

When you convey a covered work, you waive any legal power to forbid circumvention of technological measures to the extent such circumvention is effected by exercising rights under this License with respect to the covered work, and you disclaim any intention to limit operation or modification of the work as a means of enforcing, against the work's users, your or third parties' legal rights to forbid circumvention of technological measures.

@item Conveying Verbatim Copies.

You may convey verbatim copies of the Program's source code as you receive it, in any medium, provided that you conspicuously and appropriately publish on each copy an appropriate copyright notice; keep intact all notices stating that this License and any non-permissive terms added in accord with section 7 apply to the code; keep intact all notices of the absence of any warranty; and give all recipients a copy of this License along with the Program.

You may charge any price or no price for each copy that you convey, and you may offer support or warranty protection for a fee.

@item Conveying Modified Source Versions.

You may convey a work based on the Program, or the modifications to produce it from the Program, in the form of source code under the terms of section 4, provided that you also meet all of these conditions:

@enumerate a

@item

The work must carry prominent notices stating that you modified it, and giving a relevant date.

@item

The work must carry prominent notices stating that it is released under this License and any conditions added under section 7. This requirement modifies the requirement in section 4 to ``keep intact all notices".

@item

You must license the entire work, as a whole, under this License to anyone who comes into possession of a copy. This License will therefore apply, along with any applicable section 7 additional terms, to the whole of the work, and all its parts, regardless of how they are packaged. This License gives no permission to license the work in any other way, but it does not invalidate such permission if you have separately received it.

@item

If the work has interactive user interfaces, each must display

Appropriate

Legal Notices; however, if the Program has interactive interfaces that do not display Appropriate Legal Notices, your work need not make them do so.

@end enumerate

A compilation of a covered work with other separate and independent works, which are not by their nature extensions of the covered work, and which are not combined with it such as to form a larger program, in or on a volume of a storage or distribution medium, is called an ``aggregate" if the compilation and its resulting copyright are not used to limit the access or legal rights of the compilation's users beyond what the individual works permit. Inclusion of a covered work in an aggregate does not cause this License to apply to the other parts of the aggregate.

@item Conveying Non-Source Forms.

You may convey a covered work in object code form under the terms of sections 4 and 5, provided that you also convey the machine-readable

Corresponding Source under the terms of this License, in one of these ways:

@enumerate

a

@item

Convey the object code in, or embodied in, a physical product (including a physical distribution medium), accompanied by the Corresponding Source fixed on a durable physical medium customarily used for software interchange.

@item

Convey the object code in, or embodied in, a physical product (including a physical distribution medium), accompanied by a written offer, valid for at least three years and valid for as long as you offer spare parts or customer support for that product model, to give anyone who possesses the object code either (1) a copy of the Corresponding Source for all the software in the product that is covered by this License, on a durable physical medium customarily used for software interchange, for a price no more than your reasonable cost of physically performing this conveying of source, or (2) access to copy the Corresponding Source from a network server at no charge.

@item

Convey individual copies of the object code with a copy of the written offer to provide the Corresponding Source. This alternative is allowed only occasionally and noncommercially, and only if you received the object code with such an offer, in accord with subsection 6b.

@item

Convey the object code by offering access from a designated place (gratis or for a charge), and offer equivalent access to the Corresponding Source in the same way through the same place at no further charge. You need not require recipients to copy the Corresponding Source along with the object code. If the place to copy the object code is a network server, the Corresponding Source may be on a different server (operated by you or a third party) that supports equivalent copying facilities, provided you maintain clear directions next to the object code saying where to find the Corresponding Source. Regardless of what server hosts the Corresponding Source, you remain obligated to ensure that it is available for as long as needed to satisfy these requirements.

@item

Convey the object

code using peer-to-peer transmission, provided you inform other peers where the object code and Corresponding Source of the work are being offered to the general public at no charge under subsection 6d.

@end enumerate

A separable portion of the object code, whose source code is excluded from the Corresponding Source as a System Library, need not be included in conveying the object code work.

A "User Product" is either (1) a "consumer product", which means any tangible personal property which is normally used for personal, family, or household purposes, or (2) anything designed or sold for incorporation into a dwelling. In determining whether a product is a consumer product, doubtful cases shall be resolved in favor of coverage. For a particular product received by a particular user, "normally used" refers to a typical or common use of that class of product, regardless of the status of the particular user or of the way in which the particular user actually uses, or expects or is expected to use, the product. A product is a consumer product regardless of whether the product has substantial commercial, industrial or non-consumer uses, unless such uses represent the only significant mode of use of the product.

"Installation Information" for a User Product means any methods, procedures, authorization keys, or other information required to install and execute modified versions of a covered work in that User Product from a modified version of its Corresponding Source. The information must suffice to ensure that the continued functioning of the modified object code is in no case prevented or interfered with solely because modification has been made.

If you convey an object code work under this section in, or with, or specifically for use in, a User Product, and the conveying occurs as part of a transaction in which the right of possession and use of the User Product is transferred to the recipient in perpetuity or for a fixed term (regardless of how the transaction is characterized), the Corresponding Source conveyed under this section must be accompanied by the Installation Information. But this requirement does not apply if neither you nor any third party retains the ability to install modified object code on the User Product (for example, the work has been installed in ROM).

The requirement to provide Installation Information does not include a requirement to continue to provide support service, warranty, or

updates for a work that has been modified or installed by the recipient, or for the User Product in which it has been modified or installed. Access to a network may be denied when the modification itself materially and adversely affects the operation of the network or violates the rules and protocols for communication across the network.

Corresponding Source conveyed, and Installation Information provided, in accord with this section must be in a format that is publicly documented (and with an implementation available to the public in source code form), and must require no special password or key for unpacking, reading or copying.

@item Additional Terms.

``Additional permissions'' are terms that supplement the terms of this License by making exceptions from one or more of its conditions. Additional permissions that are applicable to the entire Program shall be treated as though they were included in this License, to the extent that they are valid under applicable law. If additional permissions apply only to part of the Program, that part may be used separately under those permissions, but the entire Program remains governed by this License without regard to the additional permissions.

When you convey a copy of a covered work, you may at your option remove any additional permissions from that copy, or from any part of it. (Additional permissions may be written to require their own removal in certain cases when you modify the work.) You may place additional permissions on material, added by you to a covered work, for which you have or can give appropriate copyright permission.

Notwithstanding any other provision of this License, for material you add to a covered work, you may (if authorized by the copyright holders of that material) supplement the terms of this License with terms:

@enumerate a

@item

Disclaiming warranty or limiting liability differently from the terms of sections 15 and 16 of this License; or

@item

Requiring preservation of specified reasonable legal notices or author attributions in that material or in the Appropriate Legal Notices displayed by works containing it; or

@item

Prohibiting misrepresentation of the origin of that material, or requiring that modified versions of such material be marked in reasonable ways as different from the original version; or

@item

Limiting the use for publicity purposes of names of licensors or authors of the material; or

@item

Declining to grant rights under trademark law for use of some trade names, trademarks, or service marks;

or

@item

Requiring indemnification of licensors and authors of that material by anyone who conveys the material (or modified versions of it) with contractual assumptions of liability to the recipient, for any liability that these contractual assumptions directly impose on those licensors and authors.

@end enumerate

All other non-permissive additional terms are considered "further restrictions" within the meaning of section 10. If the Program as you received it, or any part of it, contains a notice stating that it is governed by this License along with a term that is a further restriction, you may remove that term. If a license document contains a further restriction but permits relicensing or conveying under this License, you may add to a covered work material governed by the terms of that license document, provided that the further restriction does not survive such relicensing or conveying.

If you add terms to a covered work in accord with this section, you must place, in the relevant source files, a statement of the additional terms that apply to those files, or a notice indicating where to find the applicable terms.

Additional terms, permissive or non-permissive, may be stated in the form of a separately written license, or stated as exceptions; the above requirements apply either way.

@item Termination.

You may not propagate or modify a covered work except as expressly provided under this License. Any attempt otherwise to propagate or modify it is void, and will automatically terminate your rights under this License (including any patent licenses granted under the third paragraph of section 11).

However, if you cease all violation of this License, then your license from a particular copyright holder is reinstated (a) provisionally, unless and until the copyright holder explicitly and finally terminates your license, and (b) permanently, if the copyright holder fails to notify you of the violation by some reasonable means prior to 60 days after the cessation.

Moreover, your license from a particular copyright holder is reinstated permanently if the copyright holder notifies you of the violation by some reasonable means, this is the first time you have received notice of violation of this License (for any work) from that copyright holder, and you cure the violation prior to 30 days after your receipt of the notice.

Termination of your rights under this section does not terminate the licenses of parties who have received copies or rights from you under this License. If your rights have been terminated and not permanently reinstated, you do not qualify to receive new licenses for the same material under section 10.

@item Acceptance Not Required for Having Copies.

You are not required to accept this License in order to receive or run a copy of the Program. Ancillary propagation of a covered work occurring solely as a consequence of using peer-to-peer transmission to receive a copy likewise does not require acceptance. However, nothing other than this License grants you permission to propagate or modify any covered work. These actions infringe copyright if you do not accept this License. Therefore, by modifying or propagating a covered work, you indicate your acceptance of this License to do so.

@item Automatic Licensing of Downstream Recipients.

Each time you convey a covered work, the recipient automatically receives a license from the original licensors, to run, modify and propagate that work, subject to this License. You are not responsible for enforcing compliance by third parties with this License.

An "entity transaction" is a transaction transferring control of an organization, or substantially all assets of one, or subdividing an organization, or merging organizations. If propagation of a covered work results from an entity transaction, each party to that transaction who receives a copy of the work also receives whatever licenses to the work the party's predecessor in interest had or could give

under the previous paragraph, plus a right to possession of the Corresponding Source of the work from the predecessor in interest, if the predecessor has it or can get it with reasonable efforts.

You may not impose any further restrictions on the exercise of the rights granted or affirmed under this License. For example, you may not impose a license fee, royalty, or other charge for exercise of rights granted under this License, and you may not initiate litigation (including a cross-claim or counterclaim in a lawsuit) alleging that any patent claim is infringed by making, using, selling, offering for sale, or importing the Program or any portion of it.

@item Patents.

A ``contributor" is a copyright holder who authorizes use under this License of the Program or a work on which the Program is based. The work thus licensed is called the contributor's ``contributor version".

A contributor's ``essential patent claims" are all patent claims owned or controlled by the contributor, whether already acquired or hereafter acquired, that would be infringed by some manner, permitted by this License, of making, using, or selling its contributor version, but do not include claims that would be infringed only as a consequence of further modification of the contributor version. For purposes of this definition, ``control" includes the right to grant patent sublicenses in a manner consistent with the requirements of this License.

Each contributor grants you a non-exclusive, worldwide, royalty-free patent license under the contributor's essential patent claims, to make, use, sell, offer for sale, import and otherwise run, modify and propagate the contents of its contributor version.

In the following three paragraphs, a ``patent license" is any express agreement or commitment, however denominated, not to enforce a patent (such as an express permission to practice a patent or covenant not to sue for patent infringement). To ``grant" such a patent license to a party means to make such an agreement or commitment not to enforce a patent against the party.

If you convey a covered work, knowingly relying on a patent license, and the Corresponding Source of the work is not available for anyone to copy, free of charge and under the terms of this License, through a publicly available network server or other readily accessible means, then you must either (1) cause the Corresponding Source to be so available, or (2) arrange to deprive yourself of the benefit of the

patent license for this particular work, or (3) arrange, in a manner consistent with the requirements of this License, to extend the patent license to downstream recipients. "Knowingly relying" means you have actual knowledge that, but for the patent license, your conveying the covered work in a country, or your recipient's use of the covered work in a country, would infringe one or more identifiable patents in that country that you have reason to believe are valid.

If, pursuant to or in connection with a single transaction or arrangement, you convey, or propagate by procuring conveyance of, a covered work, and grant a patent license to some of the parties receiving the covered work authorizing them to use, propagate, modify or convey a specific copy of the covered work, then the patent license you grant is automatically extended to all recipients of the covered work and works based on it.

A patent license is "discriminatory" if it does not include within the scope of its coverage, prohibits the exercise of, or is conditioned on the non-exercise of one or more of the rights that are specifically granted under this License. You may not convey a covered work if you are a party to an arrangement with a third party that is in the business of distributing software, under which you make payment to the third party based on the extent of your activity of conveying the work, and under which the third party grants, to any of the parties who would receive the covered work from you, a discriminatory patent license (a) in connection with copies of the covered work conveyed by you (or copies made from those copies), or (b) primarily for and in connection with specific products or compilations that contain the covered work, unless you entered into that arrangement, or that patent license was granted, prior to 28 March 2007.

Nothing in this License shall be construed as excluding or limiting any implied license or other defenses to infringement that may otherwise be available to you under applicable patent law.

@item No Surrender of Others' Freedom.

If conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot convey a covered work so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not convey it at all. For example, if you agree to terms that obligate you to collect a royalty for further conveying from those to whom you convey the Program, the only way you could

satisfy both those terms and this License would be to refrain entirely from conveying the Program.

@item Use with the GNU Affero General Public License.

Notwithstanding any other provision of this License, you have permission to link or combine any covered work with a work licensed under version 3 of the GNU Affero General Public License into a single combined work, and to convey the resulting work. The terms of this License will continue to apply to the part which is the covered work, but the special requirements of the GNU Affero General Public License, section 13, concerning interaction through a network will apply to the combination as such.

@item Revised Versions of this License.

The Free Software Foundation may publish revised and/or new versions of the GNU General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Program specifies that a certain numbered version of the GNU General Public License "or any later version" applies to it, you have the option of following the terms and conditions either of that numbered version or of any later version published by the Free Software Foundation. If the Program does not specify a version number of the GNU General Public License, you may choose any version ever published by the Free Software Foundation.

If the Program specifies that a proxy can decide which future versions of the GNU General Public License can be used, that proxy's public statement of acceptance of a version permanently authorizes you to choose that version for the Program.

Later license versions may give you additional or different permissions. However, no additional obligations are imposed on any author or copyright holder as a result of your choosing to follow a later version.

@item Disclaimer of Warranty.

THERE IS NO WARRANTY FOR THE PROGRAM, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE PROGRAM "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT

LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE PROGRAM IS WITH YOU. SHOULD THE PROGRAM PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

@item Limitation of Liability.

IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MODIFIES AND/OR CONVEYS THE PROGRAM AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE PROGRAM (INCLUDING BUT NOT

LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE PROGRAM TO OPERATE WITH ANY OTHER PROGRAMS), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

@item Interpretation of Sections 15 and 16.

If the disclaimer of warranty and limitation of liability provided above cannot be given local legal effect according to their terms, reviewing courts shall apply local law that most closely approximates an absolute waiver of all civil liability in connection with the Program, unless a warranty or assumption of liability accompanies a copy of the Program in return for a fee.

@end enumerate

@heading END OF TERMS AND CONDITIONS

@heading How to Apply These Terms to Your New Programs

If you develop a new program, and you want it to be of the greatest possible use to the public, the best way to achieve this is to make it free software which everyone can redistribute and change under these terms.

To

do so, attach the following notices to the program. It is safest to attach them to the start of each source file to most effectively state the exclusion of warranty; and each file should have at least the ``copyright" line and a pointer to where the full notice is found.

@smallexample

@var{one line to give the program's name and a brief idea of what it does.}

Copyright (C) @var{year} @var{name of author}

This program is free software: you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation, either version 3 of the License, or (at your option) any later version.

This program is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details.

You should have received a copy of the GNU General Public License along with this program. If not, see [@url{http://www.gnu.org/licenses/}](http://www.gnu.org/licenses/).
@end smallexample

Also add information on how to contact you by electronic and paper mail.

If the program does terminal interaction, make it output a short notice like this when it starts in an interactive mode:

```
@smallexample
@var{program} Copyright (C) @var{year} @var{name of author}
This program comes with ABSOLUTELY NO WARRANTY; for details type @samp{show w}.
This is free software, and you are welcome to redistribute it
under certain conditions; type @samp{show c} for details.
@end smallexample
```

The hypothetical commands `@samp{show w}` and `@samp{show c}` should show the appropriate parts of the General Public License. Of course, your program's commands might be different; for a GUI interface, you would use an ```about box"`.

You should also get your employer (if you work as a programmer) or school, if any, to sign a ```copyright disclaimer"` for the program, if necessary. For more information on this, and how to apply and follow the GNU GPL, see [@url{http://www.gnu.org/licenses/}](http://www.gnu.org/licenses/).

The GNU General Public License does not permit incorporating your program into proprietary programs. If your program is a subroutine library, you may consider it more useful to permit linking proprietary applications with the library. If this is what you want to do, use the GNU Lesser General Public License instead of this License. But first, please read [@url{http://www.gnu.org/philosophy/why-not-lgpl.html}](http://www.gnu.org/philosophy/why-not-lgpl.html).
@c man end

GNU LESSER GENERAL PUBLIC LICENSE

Version 2.1, February 1999

Copyright (C) 1991, 1999 Free Software Foundation, Inc.

51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA

Everyone is permitted to copy and distribute verbatim copies of this license document, but changing it is not allowed.

[This is the first released version of the Lesser GPL. It also counts as the successor of the GNU Library Public License, version 2, hence the version number 2.1.]

Preamble

The licenses for most software are designed to take away your freedom to share and change it. By contrast, the GNU General Public Licenses are intended to guarantee your freedom to share and change free software--to make sure the software is free for all its users.

This license, the Lesser General Public License, applies to some specially designated software packages--typically libraries--of the Free Software Foundation and other authors who decide to use it. You can use it too, but we suggest you first think carefully about whether this license or the ordinary General Public License is the better strategy to use in any particular case, based on the explanations below.

When we speak of free software, we are referring to freedom of use, not price. Our General Public Licenses are designed to make sure that you have the freedom to distribute copies of free software (and charge for this service if you wish); that you receive source code or can get it if you want it; that you can change the software and use pieces of it in new free programs; and that you are informed that you can do these things.

To protect your rights, we need to make restrictions that forbid distributors to deny you these rights or to ask you to surrender these rights. These restrictions translate to certain responsibilities for you if you distribute copies of the library or if you modify it.

For example, if you distribute copies of the library, whether gratis or for a fee, you must give the recipients all the rights that we gave you. You must make sure that they, too, receive or can get the source code. If you link other code with the library, you must provide complete object files to the recipients, so that they can relink them with the library after making changes to the library and recompiling it. And you must show them these terms so they know their rights.

We protect your rights with a two-step method: (1) we copyright the

library, and (2) we offer you this license, which gives you legal permission to copy, distribute and/or modify the library.

To protect each distributor, we want to make it very clear that there is no warranty for the free library. Also, if the library is modified by someone else and passed on, the recipients should know that what they have is not the original version, so that the original author's reputation will not be affected by problems that might be introduced by others.

Finally, software patents pose a constant threat to the existence of any free program. We wish to make sure that a company cannot effectively restrict the users of a free program by obtaining a restrictive license from a patent holder. Therefore, we insist that any patent license obtained for a version of the library must be consistent with the full freedom of use specified in this license.

Most GNU software, including some libraries, is covered by the ordinary GNU General Public License. This license, the GNU Lesser General Public License, applies to certain designated libraries, and is quite different from the ordinary General Public License. We use this license for certain libraries in order to permit linking those libraries into non-free programs.

When a program is linked with a library, whether statically or using a shared library, the combination of the two is legally speaking a combined work, a derivative of the original library. The ordinary General Public License therefore permits such linking only if the entire combination fits its criteria of freedom. The Lesser General Public License permits more lax criteria for linking other code with the library.

We call this license the "Lesser" General Public License because it does Less to protect the user's freedom than the ordinary General Public License. It also provides other free software developers Less of an advantage over competing non-free programs. These disadvantages are the reason we use the ordinary General Public License for many libraries. However, the Lesser license provides advantages in certain special circumstances.

For example, on rare occasions, there may be a special need to encourage the widest possible use of a certain library, so that it becomes a de-facto standard. To achieve this, non-free programs must be allowed to use the library. A more frequent case is that a free library does the same job as widely used non-free libraries. In this case, there is little to gain by limiting the free library to free

software only, so we
use the Lesser General Public License.

In other cases, permission to use a particular library in non-free programs enables a greater number of people to use a large body of free software. For example, permission to use the GNU C Library in non-free programs enables many more people to use the whole GNU operating system, as well as its variant, the GNU/Linux operating system.

Although the Lesser General Public License is Less protective of the users' freedom, it does ensure that the user of a program that is linked with the Library has the freedom and the wherewithal to run that program using a modified version of the Library.

The precise terms and conditions for copying, distribution and modification follow. Pay close attention to the difference between a "work based on the library" and a "work that uses the library". The former contains code derived from the library, whereas the latter must be combined with the library in order to run.

GNU LESSER GENERAL PUBLIC LICENSE TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

0. This License Agreement applies to any software library or other program which contains a notice placed by the copyright holder or other authorized party saying it may be distributed under the terms of this Lesser General Public License (also called "this License"). Each licensee is addressed as "you".

A "library" means a collection of software functions and/or data prepared so as to be conveniently linked with application programs (which use some of those functions and data) to form executables.

The "Library", below, refers to any such software library or work which has been distributed under these terms. A "work based on the Library" means either the Library or any derivative work under copyright law: that is to say, a work containing the Library or a portion of it, either verbatim or with modifications and/or translated straightforwardly into another language. (Hereinafter, translation is included without limitation in the term "modification".)

"Source code" for a work means the preferred form of the work for making modifications to it. For a library, complete source code means all the source code for all modules it contains, plus any associated interface definition files, plus the scripts used to control compilation and installation of the library.

Activities other than copying, distribution and modification are not covered by this License; they are outside its scope. The act of running a program using the Library is not restricted, and output from such a program is covered only if its contents constitute a work based on the Library (independent of the use of the Library in a tool for writing it). Whether that is true depends on what the Library does and what the program that uses the Library does.

1. You may copy and distribute verbatim copies of the Library's complete source code as you receive it, in any medium, provided that you conspicuously and appropriately publish on each copy an appropriate copyright notice and disclaimer of warranty; keep intact all the notices that refer to this License and to the absence of any warranty; and distribute a copy of this License along with the Library.

You may charge a fee for the physical act of transferring a copy, and you may at your option offer warranty protection in exchange for a fee.

2. You may modify your copy or copies of the Library or any portion of it, thus forming a work based on the Library, and copy and distribute such modifications or work under the terms of Section 1 above, provided that you also meet all of these conditions:

a) The modified work must itself be a software library.

b) You must cause the files modified to carry prominent notices stating that you changed the files and the date of any change.

c) You must cause the whole of the work to be licensed at no charge to all third parties under the terms of this License.

d) If a facility in the modified Library refers to a function or a table of data to be supplied by an application program that uses the facility, other than as an argument passed when the facility is invoked, then you must make a good faith effort to ensure that, in the event an application does not supply such function or table, the facility still operates, and performs whatever part of its purpose remains meaningful.

(For example, a function in a library to compute square roots has a purpose that is entirely well-defined independent of the application. Therefore, Subsection 2d requires that any application-supplied function or table used by this function must

be optional: if the application does not supply it, the square root function must still compute square roots.)

These requirements apply to the modified work as a whole. If identifiable sections of that work are not derived from the Library, and can be reasonably considered independent and separate works in themselves,

then this License, and its terms, do not apply to those sections when you distribute them as separate works. But when you distribute the same sections as part of a whole which is a work based on the Library, the distribution of the whole must be on the terms of this License, whose permissions for other licensees extend to the entire whole, and thus to each and every part regardless of who wrote it.

Thus, it is not the intent of this section to claim rights or contest your rights to work written entirely by you; rather, the intent is to exercise the right to control the distribution of derivative or collective works based on the Library.

In addition, mere aggregation of another work not based on the Library with the Library (or with a work based on the Library) on a volume of a storage or distribution medium does not bring the other work under the scope of this License.

3. You may opt to apply the terms of the ordinary GNU General Public License instead of this License to a given copy of the Library. To do this, you must alter all the notices that refer to this License, so that they refer to the ordinary GNU General Public License, version 2, instead of to this License. (If a newer version than version 2 of the ordinary GNU General Public License has appeared, then you can specify that version instead if you wish.) Do not make any other change in these notices.

Once this change is made in a given copy, it is irreversible for that copy, so the ordinary GNU General Public License applies to all subsequent copies and derivative works made from that copy.

This option is useful when you wish to copy part of the code of the Library into a program that is not a library.

4. You may copy and distribute the Library (or a portion or derivative of it, under Section 2) in object code or executable form under the terms of Sections 1 and 2 above provided that you accompany it with the complete corresponding machine-readable source code, which must be

distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange.

If distribution of object code is made by offering access to copy from a designated place, then offering equivalent access to copy the source code from the same place satisfies the requirement to distribute the source code, even though third parties are not compelled to copy the source along with the object code.

5. A program that contains no derivative of any portion of the Library, but is designed to work with the Library by being compiled or linked with it, is called a "work that uses the Library". Such a work, in isolation, is not a derivative work of the Library, and therefore falls outside the scope of this License.

However, linking a "work that uses the Library" with the Library creates an executable that is a derivative of the Library (because it contains portions of the Library), rather than a "work that uses the library". The executable is therefore covered by this License.

Section 6 states terms for distribution of such executables.

When a "work that uses the Library" uses material from a header file that is part of the Library, the object code for the work may be a derivative work of the Library even though the source code is not. Whether this is true is especially significant if the work can be linked without the Library, or if the work is itself a library. The threshold for this to be true is not precisely defined by law.

If such an object file uses only numerical parameters, data structure layouts and accessors, and small macros and small inline functions (ten lines or less in length), then the use of the object file is unrestricted, regardless of whether it is legally a derivative work. (Executables containing this object code plus portions of the Library will still fall under Section 6.)

Otherwise, if the work is a derivative of the Library, you may distribute the object code for the work under the terms of Section 6. Any executables containing that work also fall under Section 6, whether or not they are linked directly with the Library itself.

6. As an exception to the Sections above, you may also combine or link a "work that uses the Library" with the Library to produce a work containing portions of the Library, and distribute that work under terms of your choice, provided that the terms permit modification of the work for the customer's own use and reverse engineering for debugging such modifications.

You must give prominent notice with each copy of the work that the Library is used in it and that the Library and its use are covered by this License. You must supply a copy of this License. If the work during execution displays copyright notices, you must include the copyright notice for the Library among them, as well as a reference directing the user to the copy of this License. Also, you must do one of these things:

- a) Accompany the work with the complete corresponding machine-readable source code for the Library including whatever changes were used in the work (which must be distributed under Sections 1 and 2 above); and, if the work is an executable linked with the Library, with the complete machine-readable "work that uses the Library", as object code and/or source code, so that the user can modify the Library and then relink to produce a modified executable containing the modified Library. (It is understood that the user who changes the contents of definitions files in the Library will not necessarily be able to recompile the application to use the modified definitions.)
- b) Use a suitable shared library mechanism for linking with the Library. A suitable mechanism is one that (1) uses at run time a copy of the library already present on the user's computer system, rather than copying library functions into the executable, and (2) will operate properly with a modified version of the library, if the user installs one, as long as the modified version is interface-compatible with the version that the work was made with.
- c) Accompany the work with a written offer, valid for at least three years, to give the same user the materials specified in Subsection 6a, above, for a charge no more than the cost of performing this distribution.
- d) If distribution of the work is made by offering access to copy from a designated place, offer equivalent access to copy the above specified materials from the same place.
- e) Verify that the user has already received a copy of these materials or that you have already sent this user a copy.

For an executable, the required form of the "work that uses the Library" must include any data and utility programs needed for reproducing the executable from it. However, as a special exception, the materials to be distributed need not include anything that is normally distributed (in either source or binary form) with

the major components (compiler, kernel, and so on) of the operating system on which the executable runs, unless that component itself accompanies the executable.

It may happen that this requirement contradicts the license restrictions of other proprietary libraries that do not normally accompany the operating system. Such a contradiction means you cannot use both them and the Library together in an executable that you distribute.

7. You may place library facilities that are a work based on the Library side-by-side in a single library together with other library facilities not covered by this License, and distribute such a combined library, provided that the separate distribution of the work based on the Library and of the other library facilities is otherwise permitted, and provided that you do these two things:

a) Accompany the combined library with a copy of the same work based on the Library, uncombined with any other library facilities. This must be distributed under the terms of the Sections above.

b) Give prominent notice with the combined library of the fact that part of it is a work based on the Library, and explaining where to find the accompanying uncombined form of the same work.

8. You may not copy, modify, sublicense, link with, or distribute the Library except as expressly provided under this License. Any attempt otherwise to copy, modify, sublicense, link with, or distribute the Library is void, and will automatically terminate your rights under this License. However, parties who have received copies, or rights, from you under this License will not have their licenses terminated so long as such parties remain in full compliance.

9. You are not required to accept this License, since you have not signed it. However, nothing else grants you permission to modify or distribute the Library or its derivative works. These actions are prohibited by law if you do not accept this License. Therefore, by modifying or distributing the Library (or any work based on the Library), you indicate your acceptance of this License to do so, and all its terms and conditions for copying, distributing or modifying the Library or works based on it.

10. Each time you redistribute the Library (or any work based on the Library), the recipient automatically receives a license from the

original licensor to copy, distribute, link with or modify the Library subject to these terms and conditions. You may not impose any further restrictions on the recipients' exercise of the rights granted herein. You are not responsible for enforcing compliance by third parties with this License.

11. If, as a consequence of a court judgment or allegation of patent infringement or for any other reason (not limited to patent issues), conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot distribute so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not distribute the Library at all. For example, if a patent license would not permit royalty-free redistribution of the Library by all those who receive copies directly or indirectly through you, then the only way you could satisfy both it and this License would be to refrain entirely from distribution of the Library.

If any portion of this section is held invalid or unenforceable under any particular circumstance, the balance of the section is intended to apply, and the section as a whole is intended to apply in other circumstances.

It is not the purpose of this section to induce you to infringe any patents or other property right claims or to contest validity of any such claims; this section has the sole purpose of protecting the integrity of the free software distribution system which is implemented by public license practices. Many people have made generous contributions to the wide range of software distributed through that system in reliance on consistent application of that system; it is up to the author/donor to decide if he or she is willing to distribute software through any other system and a licensee cannot impose that choice.

This section is intended to make thoroughly clear what is believed to be a consequence of the rest of this License.

12. If the distribution and/or use of the Library is restricted in certain countries either by patents or by copyrighted interfaces, the original copyright holder who places the Library under this License may add an explicit geographical distribution limitation excluding those countries, so that distribution is permitted only in or among countries not thus excluded. In such case, this License incorporates the limitation as if written in the body of this License.

13. The Free Software Foundation may publish revised and/or new

versions of the Lesser General Public

License from time to time.

Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Library specifies a version number of this License which applies to it and "any later version", you have the option of following the terms and conditions either of that version or of any later version published by the Free Software Foundation. If the Library does not specify a license version number, you may choose any version ever published by the Free Software Foundation.

14. If you wish to incorporate parts of the Library into other free programs whose distribution conditions are incompatible with these, write to the author to ask for permission. For software which is copyrighted by the Free Software Foundation, write to the Free Software Foundation; we sometimes make exceptions for this. Our decision will be guided by the two goals of preserving the free status of all derivatives of our free software and of promoting the sharing and reuse of software generally.

NO WARRANTY

15. BECAUSE THE LIBRARY IS LICENSED FREE OF CHARGE, THERE IS NO WARRANTY FOR THE LIBRARY, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE LIBRARY "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE LIBRARY IS WITH YOU. SHOULD THE LIBRARY PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

16. IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY AND/OR REDISTRIBUTE THE LIBRARY AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE LIBRARY (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE LIBRARY TO OPERATE WITH ANY OTHER SOFTWARE), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Libraries

If you develop a new library, and you want it to be of the greatest possible use to the public, we recommend making it free software that everyone can redistribute and change. You can do so by permitting redistribution under these terms (or, alternatively, under the terms of the ordinary General Public License).

To apply these terms, attach the following notices to the library. It is safest to attach them to the start of each source file to most effectively convey the exclusion of warranty; and each file should have at least the "copyright" line and a pointer to where the full notice is found.

<one line to give the library's name and a brief idea of what it does.>
Copyright (C) <year> <name of author>

This library is free software; you can redistribute it and/or modify it under the terms of the GNU Lesser General Public License as published by the Free Software Foundation; either version 2.1 of the License, or (at your option) any later version.

This library is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU Lesser General Public License for more details.

You should have received a copy of the GNU Lesser General Public License along with this library; if not, write to the Free Software Foundation, Inc., 51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA

Also add information on how to contact you by electronic and paper mail.

You should also get your employer (if you work as a programmer) or your school, if any, to sign a "copyright disclaimer" for the library, if necessary. Here is a sample; alter the names:

Yoyodyne, Inc., hereby disclaims all copyright interest in the library `Frob' (a library for tweaking knobs) written by James Random Hacker.

<signature of Ty Coon>, 1 April 1990
Ty Coon, President of Vice

That's all there is to it!
Boost Software License - Version 1.0 - August 17th, 2003

Permission is hereby granted, free of charge, to any person or organization obtaining a copy of the software and accompanying documentation covered by this license (the "Software") to use, reproduce, display, distribute, execute, and transmit the Software, and to prepare derivative works of the Software, and to permit third-parties to whom the Software is furnished to do so, all subject to the following:

The copyright notices in the Software and this entire statement, including the above license grant, this restriction and the following disclaimer, must be included in all copies of the Software, in whole or in part, and all derivative works of the Software, unless such copies or derivative works are solely in the form of machine-executable object code generated by a source language processor.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS

FOR A PARTICULAR PURPOSE, TITLE AND NON-INFRINGEMENT. IN NO EVENT SHALL THE COPYRIGHT HOLDERS OR ANYONE DISTRIBUTING THE SOFTWARE BE LIABLE FOR ANY DAMAGES OR OTHER LIABILITY, WHETHER IN CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

GCC RUNTIME LIBRARY EXCEPTION

Version 3.1, 31 March 2009

Copyright (C) 2009 Free Software Foundation, Inc. <<http://fsf.org/>>

Everyone is permitted to copy and distribute verbatim copies of this license document, but changing it is not allowed.

This GCC Runtime Library Exception ("Exception") is an additional permission under section 7 of the GNU General Public License, version 3 ("GPLv3"). It applies to a given file (the "Runtime Library") that bears a notice placed by the copyright holder of the file stating that the file is governed by GPLv3 along with this Exception.

When you use GCC to compile a program, GCC may combine portions of certain GCC header files and runtime libraries with the compiled program. The purpose of this Exception is to allow compilation of non-GPL (including proprietary) programs to use, in this way, the header files and runtime libraries covered by this Exception.

0. Definitions.

A file is an "Independent Module" if it either requires the Runtime Library

for execution after a Compilation Process, or makes use of an interface provided by the Runtime Library, but is not otherwise based on the Runtime Library.

"GCC" means a version of the GNU Compiler Collection, with or without modifications, governed by version 3 (or a specified later version) of the GNU General Public License (GPL) with the option of using any subsequent versions published by the FSF.

"GPL-compatible Software" is software whose conditions of propagation, modification and use would permit combination with GCC in accord with the license of GCC.

"Target Code" refers to output from any compiler for a real or virtual target processor architecture, in executable form or suitable for input to an assembler, loader, linker and/or execution phase. Notwithstanding that, Target Code does not include data in any format that is used as a compiler intermediate representation, or used for producing a compiler intermediate representation.

The "Compilation Process" transforms code entirely represented in non-intermediate languages designed for human-written code, and/or in Java Virtual Machine byte code, into Target Code. Thus, for example, use of source code generators and preprocessors need not be considered part of the Compilation Process, since the Compilation Process can be understood as starting with the output of the generators or preprocessors.

A Compilation Process is "Eligible" if it is done using GCC, alone or with other GPL-compatible software, or if it is done without using any work based on GCC. For example, using non-GPL-compatible Software to optimize any GCC intermediate representations would not qualify as an Eligible Compilation Process.

1. Grant of Additional Permission.

You have permission to propagate a work of Target Code formed by combining the Runtime Library with Independent Modules, even if such propagation would otherwise violate the terms of GPLv3, provided that all Target Code was generated by Eligible Compilation Processes. You may then convey such a combination under terms of your choice, consistent with the licensing of the Independent Modules.

2. No Weakening of GCC Copyleft.

The availability of this Exception does not imply any general

presumption that third-party software is unaffected by the copyleft requirements of the license of GCC.

libffi - Copyright (c) 1996-2014 Anthony Green, Red Hat, Inc and others.
See source files for details.

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT,

TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

DRuntime: Runtime Library for the D Programming Language

=====

Boost Software License - Version 1.0 - August 17th, 2003

Permission is hereby granted, free of charge, to any person or organization obtaining a copy of the software and accompanying documentation covered by this license (the "Software") to use, reproduce, display, distribute, execute, and transmit the Software, and to prepare derivative works of the Software, and to permit third-parties to whom the Software is furnished to do so, all subject to the following:

The copyright notices in the Software and this entire statement, including the above license grant, this restriction and the following disclaimer, must be included in all copies of the Software, in whole or in part, and all derivative works of the Software, unless such copies or derivative works are solely in the form of machine-executable object code generated by a source language processor.

THE SOFTWARE IS PROVIDED

"AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, TITLE AND NON-INFRINGEMENT. IN NO EVENT SHALL THE COPYRIGHT HOLDERS OR ANYONE DISTRIBUTING THE SOFTWARE BE LIABLE

FOR ANY DAMAGES OR OTHER LIABILITY, WHETHER IN CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

The libgloss subdirectory is a collection of software from several sources.

Each file may have its own copyright/license that is embedded in the source file. Unless otherwise noted in the body of the source file(s), the following copyright notices will apply to the contents of the libgloss subdirectory:

(1) Red Hat Incorporated

Copyright (c) 1994-2009 Red Hat, Inc. All rights reserved.

This copyrighted material is made available to anyone wishing to use, modify, copy, or redistribute it subject to the terms and conditions of the BSD License. This program is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY expressed or implied, including the implied warranties of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. A copy of this license is available at <http://www.opensource.org/licenses>. Any Red Hat trademarks that are incorporated in the source code or documentation are not subject to the BSD License and may only be used or replicated with the express permission of Red Hat, Inc.

(2) University of California, Berkeley

Copyright (c) 1981-2000 The Regents of the University of California.
All rights reserved.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

- * Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.
- * Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.
- * Neither the name of the University nor the names of its contributors may be used to endorse or promote products derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED.

IN NO EVENT SHALL THE COPYRIGHT OWNER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT

NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

(3) DJ Delorie

Copyright (C) 1993 DJ Delorie
All rights reserved.

Redistribution, modification, and use in source and binary forms is permitted provided that the above copyright notice and following paragraph are duplicated in all such forms.

This file is distributed WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.

(4) (formerly GPL for fr30)

The GPL is no longer applicable to the fr30 platform. The piece of code (syscalls.c) referencing the GPL has been officially relicensed.

(5) Advanced Micro Devices

Copyright 1989, 1990 Advanced Micro Devices, Inc.

This software is the property of Advanced Micro Devices, Inc (AMD) which specifically grants the user the right to modify, use and distribute this software provided this notice is not removed or altered. All other rights are reserved by AMD.

AMD MAKES NO WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, WITH REGARD TO THIS SOFTWARE. IN NO EVENT SHALL AMD BE LIABLE FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES IN CONNECTION WITH OR ARISING FROM THE FURNISHING, PERFORMANCE, OR USE OF THIS SOFTWARE.

So that all may benefit from your experience, please report any problems or suggestions about this software to the 29K Technical Support Center at 800-29-29-AMD (800-292-9263) in the USA, or 0800-89-1131 in the UK, or 0031-11-1129 in Japan, toll free. The direct dial number is 512-462-4118.

Advanced Micro Devices, Inc.
29K Support Products

Mail Stop 573
5900 E. Ben White Blvd.
Austin, TX 78741
800-292-9263

(6) - Analog Devices, Inc. (bfin-* targets)

Copyright (C) 2006, 2008, 2009, 2011, 2012 Analog Devices, Inc.

The authors hereby grant permission to use, copy, modify, distribute, and license this software and its documentation for any purpose, provided that existing copyright notices are retained in all copies and that this notice is included verbatim in any distributions. No written agreement, license, or royalty fee is required for any of the authorized uses. Modifications to this software may be copyrighted by their authors and need not follow the licensing terms described here, provided that the new terms are clearly indicated on the first page of each file where they apply.

(7) University of Utah and the Computer Systems Laboratory (CSL)

[applies only to hppa*-*-pro* targets]

Copyright (c) 1990,1994

The University of Utah and
the Computer Systems Laboratory (CSL). All rights reserved.

Permission to use, copy, modify and distribute this software is hereby granted provided that (1) source code retains these copyright, permission, and disclaimer notices, and (2) redistributions including binaries reproduce the notices in supporting documentation, and (3) all advertising materials mentioning features or use of this software display the following acknowledgement: ``This product includes software developed by the Computer Systems Laboratory at the University of Utah."`

THE UNIVERSITY OF UTAH AND CSL ALLOW FREE USE OF THIS SOFTWARE IN ITS "AS IS" CONDITION. THE UNIVERSITY OF UTAH AND CSL DISCLAIM ANY LIABILITY OF ANY KIND FOR ANY DAMAGES WHATSOEVER RESULTING FROM THE USE OF THIS SOFTWARE.

CSL requests users of this software to return to csl-dist@cs.utah.edu any improvements that they make and grant CSL redistribution rights.

(8) Sun Microsystems

Copyright (C) 1993 by Sun Microsystems,
Inc. All rights reserved.

Developed at SunPro, a Sun Microsystems, Inc. business.
Permission to use, copy, modify, and distribute this
software is freely granted, provided that this notice is preserved.

(9) Hewlett Packard

(c) Copyright 1986 HEWLETT-PACKARD COMPANY

To anyone who acknowledges that this file is provided "AS IS" without any express or implied warranty:

permission to use, copy, modify, and distribute this file for any purpose is hereby granted without fee, provided that the above copyright notice and this notice appears in all copies, and that the name of Hewlett-Packard Company not be used in advertising or publicity pertaining to distribution of the software without specific, written prior permission. Hewlett-Packard Company makes no representations about the suitability of this software for any purpose.

(10) Hans-Peter Nilsson

Copyright (C) 2001 Hans-Peter Nilsson

Permission to use, copy, modify, and distribute this software is freely granted, provided that the above copyright notice, this notice and the following disclaimer are preserved with no changes.

THIS SOFTWARE IS PROVIDED ``AS IS" AND WITHOUT ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, WITHOUT LIMITATION, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE.

(11) IBM Corp. spu processor (only spu-* targets)

(C) Copyright IBM Corp. 2005, 2006

All rights reserved.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

- * Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.

- * Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.

- * Neither the name of IBM nor the names of its contributors may be used to endorse or promote products derived

from this software without
specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

(12) Jon Beniston (only lm32-* targets)

Contributed by Jon Beniston <jon@beniston.com>

Redistribution and use in source and binary forms, with or without
modification, are
permitted provided that the following conditions
are met:

1. Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.
2. Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.

THIS SOFTWARE IS PROVIDED BY THE AUTHOR AND CONTRIBUTORS ``AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE AUTHOR OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY,
OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

(13) - Xilinx, Inc. (microblaze-* and powerpc-* targets)

Copyright (c) 2004, 2009 Xilinx, Inc. All rights reserved.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions are

met:

1. Redistributions source code must retain the above copyright notice, this list of conditions and the following disclaimer.
2. Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.
3. Neither the name of Xilinx nor the names of its contributors may be used to endorse or promote products derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDER AND CONTRIBUTORS "AS IS"

AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT HOLDER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

(14) - National Semiconductor Corporation

Copyright (c) 2004 National Semiconductor Corporation

The authors hereby grant permission to use, copy, modify, distribute, and license this software and its documentation for any purpose, provided that existing copyright notices are retained in all copies and that this notice

is included verbatim in any distributions. No written agreement, license, or royalty fee is required for any of the authorized uses.

Modifications to this software may be copyrighted by their authors and need not follow the licensing terms described here, provided that the new terms are clearly indicated on the first page of each file where they apply.

(15) - CodeSourcery, Inc. (tic6x-* targets)

Copyright (c) 2010 CodeSourcery, Inc.

All rights reserved.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

- * Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.
- * Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.
- * Neither the name of CodeSourcery

nor the

names of its contributors may be used to endorse or promote products derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY CODESOURCERY, INC. ``AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL CODESOURCERY BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

(16) - GPL with exception (sparc-*leon*, crx-*, cr16-* targets only)

Copyright (C) 1992 Free Software Foundation,
Inc.

Written By David Vinayak Henkel-Wallace, June 1992

This file is free software; you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation; either version 2, or (at your option) any later version.

In addition to the permissions in the GNU General Public License, the Free Software Foundation gives you unlimited permission to link the compiled version of this file with other programs, and to distribute those programs without any restriction coming from the use of this file. (The General Public License restrictions do apply in other respects; for example, they cover modification of the file, and distribution when not linked into another program.)

This file is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details.

You should have received a copy of the GNU General Public License along with this program; see the file COPYING. If not, write to the Free Software Foundation, 59 Temple Place - Suite 330, Boston, MA 02111-1307, USA.

As a special exception, if you link this library with files compiled with GCC to produce an executable, this does not cause the resulting executable to be covered by the GNU General Public License. This exception does not however invalidate any other reasons why the executable file might be covered by the GNU General Public License.

(17) - Adapteva, Inc. (epiphany-* targets)

Copyright (c) 2011, Adapteva, Inc.
All rights reserved.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

- * Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.
- * Redistributions in binary form must reproduce the above copyright notice,

this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.

- * Neither the name of Adapteva nor the names of its contributors may be used to endorse or promote products derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT HOLDER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

(18) - Rolls-Royce Controls and Data Services Limited (visium-* targets)

Copyright (c) 2015 Rolls-Royce Controls and Data Services Limited.
All rights reserved.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

- * Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.
- * Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.
- * Neither the name of Rolls-Royce Controls and Data Services Limited nor the names of its contributors may be used to endorse or promote products derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT HOLDER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

(19) - FTDI (ft32-* targets)

Copyright (C) 2014 FTDI (support@ftdichip.com)

The authors hereby grant permission to use, copy, modify, distribute, and license this software and its documentation for any purpose, provided that existing copyright notices are retained in all copies and that this notice is included verbatim in any distributions. No written agreement, license, or royalty fee is required for any of the authorized uses. Modifications to this software may be copyrighted by their authors and need not follow the licensing terms described here, provided that the new terms are clearly indicated on the first page of each file where they apply.

(20) - Synopsys Inc (arc-* targets)

Copyright (c) 2015, Synopsys, Inc. All rights reserved.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

- 1) Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.

2) Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.

3) Neither the name of the Synopsys, Inc., nor the names of its contributors may be used to endorse or promote products derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT HOLDER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

Copyright (c) 2009 The Go Authors. All rights reserved.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

- * Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.

- * Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.

- * Neither the name of Google Inc. nor the names of its contributors may be used to endorse or promote products derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE

OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

GNU GENERAL PUBLIC LICENSE

Version 3, 29 June 2007

Copyright (C) 2007 Free Software Foundation, Inc. <<http://fsf.org/>>

Everyone is permitted to copy and distribute verbatim copies of this license document, but changing it is not allowed.

Preamble

The GNU General Public License is a free, copyleft license for software and other kinds of works.

The licenses for most software and other practical works are designed to take away your freedom to share and change the works. By contrast, the GNU General Public License is intended to guarantee your freedom to share and change all versions of a program--to make sure it remains free software for all its users. We, the Free Software Foundation, use the GNU General Public License for most of our software; it applies also to any other work released this way by its authors. You can apply it to your programs, too.

When we speak of free software, we are referring to freedom, not price. Our General Public Licenses are designed to make sure that you have the freedom to distribute copies of free software (and charge for them if you wish), that you receive source code or can get it if you want it, that you can change the software or use pieces of it in new free programs, and that you know you can do these things.

To protect your rights, we need to prevent others from denying you these rights or asking you to surrender the rights. Therefore, you have certain responsibilities if you distribute copies of the software, or if you modify it: responsibilities to respect the freedom of others.

For example, if you distribute copies of such a program, whether gratis or for a fee, you must pass on to the recipients the same freedoms that you received. You must make sure that they, too, receive or can get the source code. And you must show them these terms so they know their rights.

Developers that use the GNU GPL protect your rights with two steps:

- (1) assert copyright on the software, and
- (2) offer you this License giving you legal permission to copy, distribute and/or modify it.

For the developers' and authors' protection, the GPL clearly explains that there is no warranty for this free software. For both users' and

authors' sake, the GPL requires that modified versions be marked as changed, so that their problems will not be attributed erroneously to authors of previous versions.

Some devices are designed to deny users access to install or run modified versions of the software inside them, although the manufacturer can do so. This is fundamentally incompatible with the aim of protecting users' freedom to change the software. The systematic pattern of such abuse occurs in the area of products for individuals to use, which is precisely where it is most unacceptable. Therefore, we have designed this version of the GPL to prohibit the practice for those products. If such problems arise substantially in other domains, we stand ready to extend this provision to those domains in future versions of the GPL, as needed to protect the freedom of users.

Finally, every program is threatened constantly by software patents. States should not allow patents to restrict development and use of software on general-purpose computers, but in those that do, we wish to avoid the special danger that patents applied to a free program could make it effectively proprietary. To prevent this, the GPL assures that patents cannot be used to render the program non-free.

The precise terms and conditions for copying, distribution and modification follow.

TERMS AND CONDITIONS

0. Definitions.

"This License" refers to version 3 of the GNU General Public License.

"Copyright" also means copyright-like laws that apply to other kinds of works, such as semiconductor masks.

"The Program" refers to any copyrightable work licensed under this License. Each licensee is addressed as "you". "Licensees" and "recipients" may be individuals or organizations.

To "modify" a work means to copy from or adapt all or part of the work in a fashion requiring copyright permission, other than the making of an exact copy. The resulting work is called a "modified version" of the earlier work or a work "based on" the earlier work.

A "covered work" means either the unmodified Program or a work based on the Program.

To "propagate" a work means to do anything with it that, without permission, would make you directly or secondarily liable for infringement under applicable copyright law, except executing it on a computer or modifying a private copy. Propagation includes copying, distribution (with or without modification), making available to the public, and in some countries other activities as well.

To "convey" a work means any kind of propagation that enables other parties to make or receive copies. Mere interaction with a user through a computer network, with no transfer of a copy, is not conveying.

An interactive user interface displays "Appropriate Legal Notices" to the extent that it includes a convenient and prominently visible feature that (1) displays an appropriate copyright notice, and (2) tells the user that there is no warranty for the work (except to the extent that warranties are provided), that licensees may convey the work under this License, and how to view a copy of this License. If the interface presents a list of user commands or options, such as a menu, a prominent item in the list meets this criterion.

1. Source Code.

The "source code" for a work means the preferred form of the work for making modifications to it. "Object code" means any non-source form of a work.

A "Standard Interface" means an interface that either is an official standard defined by a recognized standards body, or, in the case of interfaces specified for a particular programming language, one that is widely used among developers working in that language.

The "System Libraries" of an executable work include anything, other than the work as a whole, that (a) is included in the normal form of packaging a Major Component, but which is not part of that Major Component, and (b) serves only to enable use of the work with that Major Component, or to implement a Standard Interface for which an implementation is available to the public in source code form. A "Major Component", in this context, means a major essential component (kernel, window system, and so on) of the specific operating system (if any) on which the executable work runs, or a compiler used to produce the work, or an object code interpreter used to run it.

The "Corresponding Source" for a work in object code form means all the source code needed to generate, install, and (for an executable work) run the object code and to modify the work, including scripts to control those activities. However, it does not include the work's

System Libraries, or general-purpose tools or generally available free programs which are used unmodified in performing those activities but which are not part of the work. For example, Corresponding Source includes interface definition files associated with source files for the work, and the source code for shared libraries and dynamically linked subprograms that the work is specifically designed to require, such as by intimate data communication or control flow between those subprograms and other parts of the work.

The Corresponding Source need not include anything that users can regenerate automatically from other parts of the Corresponding Source.

The Corresponding Source for a work in source code form is that same work.

2. Basic Permissions.

All rights granted under this License are granted for the term of copyright on the Program, and are irrevocable provided the stated conditions are met. This License explicitly affirms your unlimited permission to run the unmodified Program. The output from running a covered work is covered by this License only if the output, given its content, constitutes a covered work. This License acknowledges your rights of fair use or other equivalent, as provided by copyright law.

You may make, run and propagate covered works that you do not convey, without conditions so long as your license otherwise remains in force. You may convey covered works to others for the sole purpose of having them make modifications exclusively for you, or provide you with facilities for running those works, provided that you comply with the terms of this License in conveying all material for which you do not control copyright. Those thus making or running the covered works for you must do so exclusively on your behalf, under your direction and control, on terms that prohibit them from making any copies of your copyrighted material outside their relationship with you.

Conveying under any other circumstances is permitted solely under the conditions stated below. Sublicensing is not allowed; section 10 makes it unnecessary.

3. Protecting Users' Legal Rights From Anti-Circumvention Law.

No covered work shall be deemed part of an effective technological measure under any applicable law fulfilling obligations under article

11 of the WIPO copyright treaty adopted on 20 December 1996, or similar laws prohibiting or restricting circumvention of such measures.

When you convey a covered work, you waive any legal power to forbid circumvention of technological measures to the extent such circumvention is effected by exercising rights under this License with respect to the covered work, and you disclaim any intention to limit operation or modification of the work as a means of enforcing, against the work's users, your or third parties' legal rights to forbid circumvention of technological measures.

4. Conveying Verbatim Copies.

You may convey verbatim copies of the Program's source code as you receive it, in any medium, provided that you conspicuously and appropriately publish on each copy an appropriate copyright notice; keep intact all notices stating that this License and any non-permissive terms added in accord with section 7 apply to the code; keep intact all notices of the absence of any warranty; and give all recipients a copy of this License along with the Program.

You may charge any price or no price for each copy that you convey, and you may offer support or warranty protection for a fee.

5. Conveying Modified Source Versions.

You may convey a work based on the Program, or the modifications to produce it from the Program, in the form of source code under the terms of section 4, provided that you also meet all of these conditions:

- a) The work must carry prominent notices stating that you modified it, and giving a relevant date.
- b) The work must carry prominent notices stating that it is released under this License and any conditions added under section 7. This requirement modifies the requirement in section 4 to "keep intact all notices".
- c) You must license the entire work, as a whole, under this License to anyone who comes into possession of a copy. This License will therefore apply, along with any applicable section 7 additional terms, to the whole of the work, and all its parts, regardless of how they are packaged. This License gives no permission to license the work in any other way, but it does not invalidate such permission if you have separately received it.

d) If the work has interactive user interfaces, each must display Appropriate Legal Notices; however, if the Program has interactive interfaces that do not display Appropriate Legal Notices, your work need not make them do so.

A compilation of a covered work with other separate and independent works, which are not by their nature extensions of the covered work, and which are not combined with it such as to form a larger program, in or on a volume of a storage or distribution medium, is called an "aggregate" if the compilation and its resulting copyright are not used to limit the access or legal rights of the compilation's users beyond what the individual works permit. Inclusion of a covered work in an aggregate does not cause this License to apply to the other parts of the aggregate.

6. Conveying Non-Source Forms.

You may convey a covered work in object code form under the terms of sections 4 and 5, provided that you also convey the machine-readable Corresponding Source under the terms of this License, in one of these ways:

a) Convey the object code in, or embodied in, a physical product (including a physical distribution medium), accompanied by the Corresponding Source fixed on a durable physical medium customarily used for software interchange.

b) Convey the object code in, or embodied in, a physical product (including a physical distribution medium), accompanied by a written offer, valid for at least three years and valid for as long as you offer spare parts or customer support for that product model, to give anyone who possesses the object code either (1) a copy of the Corresponding Source for all the software in the product that is covered by this License, on a durable physical medium customarily used for software interchange, for a price no more than your reasonable cost of physically performing this conveying of source, or (2) access to copy the Corresponding Source from a network server at no charge.

c) Convey individual copies of the object code with a copy of the written offer to provide the Corresponding Source. This alternative is allowed only occasionally and noncommercially, and only if you received the object code with such an offer, in accord with subsection 6b.

d) Convey the object code by offering access from a designated place (gratis or for a charge), and offer equivalent access to the Corresponding Source in the same way through the same place at no further charge. You need not require recipients to copy the Corresponding Source along with the object code. If the place to copy the object code is a network server, the Corresponding Source may be on a different server (operated by you or a third party) that supports equivalent copying facilities, provided you maintain clear directions next to the object code saying where to find the Corresponding Source. Regardless of what server hosts the Corresponding Source, you remain obligated to ensure that it is available for as long as needed to satisfy these requirements.

e) Convey the object code using peer-to-peer transmission, provided you inform other peers where the object code and Corresponding Source of the work are being offered to the general public at no charge under subsection 6d.

A separable portion of the object code, whose source code is excluded from the Corresponding Source as a System Library, need not be included in conveying the object code work.

A "User Product" is either (1) a "consumer product", which means any tangible personal property which is normally used for personal, family, or household purposes, or (2) anything designed or sold for incorporation into a dwelling. In determining whether a product is a consumer product, doubtful cases shall be resolved in favor of coverage. For a particular product received by a particular user, "normally used" refers to a typical or common use of that class of product, regardless of the status of the particular user or of the way in which the particular user actually uses, or expects or is expected to use, the product. A product is a consumer product regardless of whether the product has substantial commercial, industrial or non-consumer uses, unless such uses represent the only significant mode of use of the product.

"Installation Information" for a User Product means any methods, procedures, authorization keys, or other information required to install and execute modified versions of a covered work in that User Product from a modified version of its Corresponding Source. The information must suffice to ensure that the continued functioning of the modified object code is in no case prevented or interfered with solely because modification has been made.

If you convey an object code work under this section in, or with, or specifically for use in, a User Product, and the conveying occurs as

part of a transaction in which the right of possession and use of the User Product is transferred to the recipient in perpetuity or for a fixed term (regardless of how the transaction is characterized), the Corresponding Source conveyed under this section must be accompanied by the Installation Information. But this requirement does not apply if neither you nor any third party retains the ability to install modified object code on the User Product (for example, the work has been installed in ROM).

The requirement to provide Installation Information does not include a requirement to continue to provide support service, warranty, or updates for a work that has been modified or installed by the recipient, or for the User Product in which it has been modified or installed. Access to a network may be denied when the modification itself materially and adversely affects the operation of the network or violates the rules and protocols for communication across the network.

Corresponding Source conveyed, and Installation Information provided, in accord with this section must be in a format that is publicly documented (and with an implementation available to the public in source code form), and must require no special password or key for unpacking, reading or copying.

7. Additional Terms.

"Additional permissions" are terms that supplement the terms of this License by making exceptions from one or more of its conditions. Additional permissions that are applicable to the entire Program shall be treated as though they were included in this License, to the extent that they are valid under applicable law. If additional permissions apply only to part of the Program, that part may be used separately under those permissions, but the entire Program remains governed by this License without regard to the additional permissions.

When you convey a copy of a covered work, you may at your option remove any additional permissions from that copy, or from any part of it. (Additional permissions may be written to require their own removal in certain cases when you modify the work.) You may place additional permissions on material, added by you to a covered work, for which you have or can give appropriate copyright permission.

Notwithstanding any other provision of this License, for material you add to a covered work, you may (if authorized by the copyright holders of that material) supplement the terms of this License with terms:

- a) Disclaiming warranty or

limiting liability differently from the terms of sections 15 and 16 of this License; or

- b) Requiring preservation of specified reasonable legal notices or author attributions in that material or in the Appropriate Legal Notices displayed by works containing it; or
- c) Prohibiting misrepresentation of the origin of that material, or requiring that modified versions of such material be marked in reasonable ways as different from the original version; or
- d) Limiting the use for publicity purposes of names of licensors or authors of the material; or
- e) Declining to grant rights under trademark law for use of some trade names, trademarks, or service marks; or
- f) Requiring indemnification of licensors and authors of that material by anyone who conveys the material (or modified versions of it) with contractual assumptions of liability to the recipient, for any liability that these contractual assumptions directly impose on those licensors and authors.

All other non-permissive additional terms are considered "further restrictions" within the meaning of section 10. If the Program as you received it, or any part of it, contains a notice stating that it is governed by this License along with a term that is a further restriction, you may remove that term. If a license document contains a further restriction but permits relicensing or conveying under this License, you may add to a covered work material governed by the terms of that license document, provided that the further restriction does not survive such relicensing or conveying.

If you add terms to a covered work in accord with this section, you must place, in the relevant source files, a statement of the additional terms that apply to those files, or a notice indicating where to find the applicable terms.

Additional terms, permissive or non-permissive, may be stated in the form of a separately written license, or stated as exceptions; the above requirements apply either way.

8. Termination.

You may not propagate or modify a covered work except as expressly provided under this License. Any attempt otherwise to propagate or

modify it is void, and will automatically terminate your rights under this License (including any patent licenses granted under the third paragraph of section 11).

However, if you cease all violation of this License, then your license from a particular copyright holder is reinstated (a) provisionally, unless and until the copyright holder explicitly and finally terminates your license, and (b) permanently, if the copyright holder fails to notify you of the violation by some reasonable means prior to 60 days after the cessation.

Moreover, your license from a particular copyright holder is reinstated permanently if the copyright holder notifies you of the violation by some reasonable means, this is the first time you have received notice of violation of this License (for any work) from that copyright holder, and you cure the violation prior to 30 days after your receipt of the notice.

Termination of your rights under this section does not terminate the licenses of parties who have received copies or rights from you under this License. If your rights have been terminated and not permanently reinstated, you do not qualify to receive new licenses for the same material under section 10.

9. Acceptance Not Required for Having Copies.

You are not required to accept this License in order to receive or run a copy of the Program. Ancillary propagation of a covered work occurring solely as a consequence of using peer-to-peer transmission to receive a copy likewise does not require acceptance. However, nothing other than this License grants you permission to propagate or modify any covered work. These actions infringe copyright if you do not accept this License. Therefore, by modifying or propagating a covered work, you indicate your acceptance of this License to do so.

10. Automatic Licensing of Downstream Recipients.

Each time you convey a covered work, the recipient automatically receives a license from the original licensors, to run, modify and propagate that work, subject to this License. You are not responsible for enforcing compliance by third parties with this License.

An "entity transaction" is a transaction transferring control of an organization, or substantially all assets of one, or subdividing an organization, or merging organizations. If propagation of a covered work results from an entity transaction, each party to that

transaction who receives a copy of the work also receives whatever licenses to the work the party's predecessor in interest had or could give under the previous paragraph, plus a right to possession of the Corresponding Source of the work from the predecessor in interest, if the predecessor has it or can get it with reasonable efforts.

You may not impose any further restrictions on the exercise of the rights

granted or affirmed under this License. For example, you may not impose a license fee, royalty, or other charge for exercise of rights granted under this License, and you may not initiate litigation (including a cross-claim or counterclaim in a lawsuit) alleging that any patent claim is infringed by making, using, selling, offering for sale, or importing the Program or any portion of it.

11. Patents.

A "contributor" is a copyright holder who authorizes use under this License of the Program or a work on which the Program is based. The work thus licensed is called the contributor's "contributor version".

A contributor's "essential patent claims" are all patent claims owned or controlled by the contributor, whether already acquired or hereafter acquired, that would be infringed by some manner, permitted by this License, of making, using, or selling its contributor version, but do not include claims that would be infringed only as a consequence of further modification of the contributor version. For purposes of this definition, "control" includes the right to grant patent sublicenses in a manner consistent with the requirements of this License.

Each contributor grants you a non-exclusive, worldwide, royalty-free patent license under the contributor's essential patent claims, to make, use, sell, offer for sale, import and otherwise run, modify and propagate the contents of its contributor version.

In the following three paragraphs, a "patent license" is any express agreement or commitment, however denominated, not to enforce a patent (such as an express permission to practice a patent or covenant not to sue for patent infringement). To "grant" such a patent license to a party means to make such an agreement or commitment not to enforce a patent against the party.

If you convey a covered work, knowingly relying on a patent license, and the Corresponding Source of the work is not available for anyone to copy, free of charge and under the terms of this

License, through a publicly available network server or other readily accessible means, then you must either (1) cause the Corresponding Source to be so available, or (2) arrange to deprive yourself of the benefit of the patent license for this particular work, or (3) arrange, in a manner consistent with the requirements of this License, to extend the patent license to downstream recipients. "Knowingly relying" means you have actual knowledge that, but for the patent license, your conveying the covered work in a country, or your recipient's use of the covered work in a country, would infringe one or more identifiable patents in that country that you have reason to believe are valid.

If, pursuant to or in connection with a single transaction or arrangement, you convey, or propagate by procuring conveyance of, a covered work, and grant a patent license to some of the parties receiving the covered work authorizing them to use, propagate, modify or convey a specific copy of the covered work, then the patent license you grant is automatically extended to all recipients of the covered work and works based on it.

A patent license is "discriminatory" if it does not include within the scope of its coverage, prohibits the exercise of, or is conditioned on the non-exercise of one or more of the rights that are specifically granted under this License. You may not convey a covered work if you are a party to an arrangement with a third party that is in the business of distributing software, under which you make payment to the third party based on the extent of your activity of conveying the work, and under which the third party grants, to any of the parties who would receive the covered work from you, a discriminatory patent license (a) in connection with copies of the covered work conveyed by you (or copies made from those copies), or (b) primarily for and in connection with specific products or compilations that contain the covered work, unless you entered into that arrangement, or that patent license was granted, prior to 28 March 2007.

Nothing in this License shall be construed as excluding or limiting any implied license or other defenses to infringement that may otherwise be available to you under applicable patent law.

12. No Surrender of Others' Freedom.

If conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot convey a covered work so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may

not convey it at all. For example, if you agree to terms that obligate you to collect a royalty for further conveying from those to whom you convey the Program, the only way you could satisfy both those terms and this License would be to refrain entirely from conveying the Program.

13. Use with the GNU Affero General Public License.

Notwithstanding any other provision of this License, you have permission to link or combine any covered work with a work licensed under version 3 of the GNU Affero General Public License into a single combined work, and to convey the resulting work. The terms of this License will continue to apply to the part which is the covered work, but the special requirements of the GNU Affero General Public License, section 13, concerning interaction through a network will apply to the combination as such.

14. Revised Versions of this License.

The Free Software Foundation may publish revised and/or new versions of the GNU General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Program specifies that a certain numbered version of the GNU General Public License "or any later version" applies to it, you have the option of following the terms and conditions either of that numbered version or of any later version published by the Free Software Foundation. If the Program does not specify a version number of the GNU General Public License, you may choose any version ever published by the Free Software Foundation.

If the Program specifies that a proxy can decide which future versions of the GNU General Public License can be used, that proxy's public statement of acceptance of a version permanently authorizes you to choose that version for the Program.

Later license versions may give you additional or different permissions. However, no additional obligations are imposed on any author or copyright holder as a result of your choosing to follow a later version.

15. Disclaimer of Warranty.

THERE IS NO WARRANTY FOR THE PROGRAM, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE PROGRAM "AS IS"

WITHOUT WARRANTY

OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE PROGRAM IS WITH YOU. SHOULD THE PROGRAM PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

16. Limitation of Liability.

IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MODIFIES AND/OR CONVEYS THE PROGRAM AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE PROGRAM (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE PROGRAM TO OPERATE WITH ANY OTHER PROGRAMS), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

17.

Interpretation of Sections 15 and 16.

If the disclaimer of warranty and limitation of liability provided above cannot be given local legal effect according to their terms, reviewing courts shall apply local law that most closely approximates an absolute waiver of all civil liability in connection with the Program, unless a warranty or assumption of liability accompanies a copy of the Program in return for a fee.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Programs

If you develop a new program, and you want it to be of the greatest possible use to the public, the best way to achieve this is to make it free software which everyone can redistribute and change under these terms.

To do so, attach the following notices to the program. It is safest to attach them to the start of each source file to most effectively state the exclusion of warranty; and each file should have at least the "copyright" line and a pointer to where the full notice is found.

```
<one line to give the program's name and a brief idea of what it does.>  
Copyright (C) <year> <name of author>
```

This program is free software: you can redistribute it and/or modify it under the terms of the GNU General Public License as published by

the Free Software Foundation, either version 3 of the License, or
(at your option) any later version.

This program is distributed in the hope that it will be useful,
but WITHOUT ANY WARRANTY; without even the implied warranty of
MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
GNU General Public License for more details.

You should have received a copy of the GNU General Public License
along with this program. If not, see <<http://www.gnu.org/licenses/>>.

Also add information on how to contact you by electronic and paper mail.

If the program does terminal interaction, make it output a short
notice like this when it starts in an interactive mode:

```
<program> Copyright (C) <year> <name of author>  
This program comes with ABSOLUTELY NO WARRANTY; for details type `show w'.  
This is free software, and you are welcome to redistribute it  
under certain conditions; type `show c' for details.
```

The hypothetical commands `show w' and `show c' should show the appropriate
parts of the General Public License. Of course, your program's commands
might be different; for a GUI interface, you would use an "about box".

You should also get your employer (if you work as a programmer) or school,
if any, to sign a "copyright disclaimer" for the program, if necessary.
For more information on this, and how to apply and follow the GNU GPL, see
<<http://www.gnu.org/licenses/>>.

The GNU General Public License does not permit incorporating your program
into proprietary programs. If your program is a subroutine library, you
may consider it more useful to permit linking proprietary applications with
the library. If this is what you want to
do, use the GNU Lesser General
Public License instead of this License. But first, please read
<<http://www.gnu.org/philosophy/why-not-lgpl.html>>.

GNU LIBRARY GENERAL PUBLIC LICENSE

Version 2, June 1991

Copyright (C) 1991 Free Software Foundation, Inc.
59 Temple Place -- Suite 330, Boston, MA 02111-1307, USA

Everyone is permitted to copy and distribute verbatim copies
of this license document, but changing it is not allowed.

[This is the first released version of the library GPL. It is numbered 2 because it goes with version 2 of the ordinary GPL.]

Preamble

=====

The licenses for most software are designed to take away your freedom to share and change it. By contrast, the GNU General Public Licenses are intended to guarantee your freedom to share and change free software--to make sure the software is free for all its users.

This license, the Library General Public License, applies to some specially designated Free Software Foundation software, and to any other libraries whose authors decide to use it. You can use it for your libraries, too.

When we speak of free software, we are referring to freedom, not price. Our General Public Licenses are designed to make sure that you have the freedom to distribute copies of free software (and charge for this service if you wish), that you receive source code or can get it if you want it, that you can change the software or use pieces of it in new free programs; and that you know you can do these things.

To protect your rights, we need to make restrictions that forbid anyone to deny you these rights or to ask you to surrender the rights. These restrictions translate to certain responsibilities for you if you distribute copies of the library, or if you modify it.

For example, if you distribute copies of the library, whether gratis or for a fee, you must give the recipients all the rights that we gave you. You must make sure that they, too, receive or can get the source code. If you link a program with the library, you must provide complete object files to the recipients so that they can relink them with the library, after making changes to the library and recompiling it. And you must show them these terms so they know their rights.

Our method of protecting your rights has two steps: (1) copyright the library, and (2) offer you this license which gives you legal permission to copy, distribute and/or modify the library.

Also, for each distributor's protection, we want to make certain that everyone understands that there is no warranty for this free library. If the library is modified by someone else and passed on, we want its recipients to know that what they have is not the original version, so that any problems introduced by others will not reflect on

the original authors' reputations.

Finally, any free program is threatened constantly by software patents. We wish to avoid the danger that companies distributing free software will individually obtain patent licenses, thus in effect transforming the program into proprietary software. To prevent this, we have made it clear that any patent must be licensed for everyone's free use or not licensed at all.

Most GNU software, including some libraries, is covered by the ordinary GNU General Public License, which was designed for utility programs. This license, the GNU Library General Public License, applies to certain designated libraries. This license is quite different from the ordinary one; be sure to read it in full, and don't assume that anything in it is the same as in the ordinary license.

The reason we have a separate public license for some libraries is that they blur the distinction we usually make between modifying or adding to a program and simply using it. Linking a program with a library, without changing the library, is in some sense simply using the library, and is analogous to running a utility program or application program. However, in a textual and legal sense, the linked executable is a combined work, a derivative of the original library, and the ordinary General Public License treats it as such.

Because of this blurred distinction, using the ordinary General Public License for libraries did not effectively promote software sharing, because most developers did not use the libraries. We concluded that weaker conditions might promote sharing better.

However, unrestricted linking of non-free programs would deprive the users of those programs of all benefit from the free status of the libraries themselves. This Library General Public License is intended to permit developers of non-free programs to use free libraries, while preserving your freedom as a user of such programs to change the free libraries that are incorporated in them. (We have not seen how to achieve this as regards changes in header files, but we have achieved it as regards changes in the actual functions of the Library.) The hope is that this will lead to faster development of free libraries.

The precise terms and conditions for copying, distribution and modification follow. Pay close attention to the difference between a "work based on the library" and a "work that uses the library". The former contains code derived from the library, while the latter only works together with the library.

Note that it is possible for a library to be covered by the ordinary General Public License rather than by this special one.

TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

0. This License Agreement applies to any software library which contains a notice placed by the copyright holder or other authorized party saying it may be distributed under the terms of this Library General Public License (also called "this License"). Each licensee is addressed as "you".

A "library" means a collection of software functions and/or data prepared so as to be conveniently linked with application programs (which use some of those functions and data) to form executables.

The "Library", below, refers to any such software library or work which has been distributed under these terms. A "work based on the Library" means either the Library or any derivative work under copyright law: that is to say, a work containing the Library or a portion of it, either verbatim or with modifications and/or translated straightforwardly into another language. (Hereinafter, translation is included without limitation in the term "modification".)

"Source code" for a work means the preferred form of the work for making modifications to it. For a library, complete source code means all the source code for all modules it contains, plus any associated interface definition files, plus the scripts used to control compilation and installation of the library.

Activities other than copying, distribution and modification are not covered by this License; they are outside its scope. The act of running a program using the Library is not restricted, and output from such a program is covered only if its contents constitute a work based on the Library (independent of the use of the Library in a tool for writing it). Whether that is true depends on what the Library does and what the program that uses the Library does.

1. You may copy and distribute verbatim copies of the Library's complete source code as you receive it, in any medium, provided that you conspicuously and appropriately publish on each copy an appropriate copyright notice and disclaimer of warranty; keep intact all the notices that refer to this License and to the absence of any warranty; and distribute a copy of this License along with the Library.

You may charge a fee for the physical act of transferring a copy, and you may at your option offer warranty protection in exchange for a fee.

2. You may modify your copy or copies of the Library or any portion of it, thus forming a work based on the Library, and copy and distribute such modifications or work under the terms of Section 1 above, provided that you also meet all of these conditions:

- a. The modified work must itself be a software library.
- b. You must cause the files modified to carry prominent notices stating that you changed the files and the date of any change.
- c. You must cause the whole of the work to be licensed at no charge to all third parties under the terms of this License.
- d. If a facility in the modified Library refers to a function or a table of data to be supplied by an application program that uses the facility, other than as an argument passed when the facility is invoked, then you must make a good faith effort to ensure that, in the event an application does not supply such function or table, the facility still operates, and

performs whatever part of its purpose remains meaningful.

(For example, a function in a library to compute square roots has a purpose that is entirely well-defined independent of the application. Therefore, Subsection 2d requires that any application-supplied function or table used by this function must be optional: if the application does not supply it, the square root function must still compute square roots.)

These requirements apply to the modified work as a whole. If identifiable sections of that work are not derived from the Library, and can be reasonably considered independent and separate works in themselves, then this License, and its terms, do not apply to those sections when you distribute them as separate works. But when you distribute the same sections as part of a whole which is a work based on the Library, the distribution of the whole must be on the terms of this License, whose permissions for other licensees extend to the entire whole, and thus to each and every part regardless of who wrote it.

Thus, it is not the intent of this section to claim rights or

contest your rights to work written entirely by you; rather, the intent is to exercise the right to control the distribution of derivative or collective works based on the Library.

In addition, mere aggregation of another work not based on the Library with the Library (or with a work based on the Library) on a volume of a storage or distribution medium does not bring the other work under the scope of this License.

3. You may opt to apply the terms of the ordinary GNU General Public License instead of this License to a given copy of the Library.

To do this, you must alter all the notices that refer to this License, so that they refer to the ordinary GNU General Public License, version 2, instead of to this License. (If a

newer

version than version 2 of the ordinary GNU General Public License has appeared, then you can specify that version instead if you wish.) Do not make any other change in these notices.

Once this change is made in a given copy, it is irreversible for that copy, so the ordinary GNU General Public License applies to all subsequent copies and derivative works made from that copy.

This option is useful when you wish to copy part of the code of the Library into a program that is not a library.

4. You may copy and distribute the Library (or a portion or derivative of it, under Section 2) in object code or executable form under the terms of Sections 1 and 2 above provided that you accompany it with the complete corresponding machine-readable source code, which must be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange.

If distribution of object code is made by offering access to copy

from a designated place, then offering equivalent access to copy the source code from the same place satisfies the requirement to distribute the source code, even though third parties are not compelled to copy the source along with the object code.

5. A program that contains no derivative of any portion of the Library, but is designed to work with the Library by being compiled or linked with it, is called a "work that uses the Library". Such a work, in isolation, is not a derivative work of the Library, and therefore falls outside the scope of this License.

However, linking a "work that uses the Library" with the Library

creates an executable that is a derivative of the Library (because it contains portions of the Library), rather than a "work that uses the library". The executable is therefore covered by this License. Section 6 states terms for distribution of such executables.

When a "work that uses the Library" uses material from a header file that is part of the Library, the object code for the work may be a derivative work of the Library even though the source code is not. Whether this is true is especially significant if the work can be linked without the Library, or if the work is itself a library. The threshold for this to be true is not precisely defined by law.

If such an object file uses only numerical parameters, data structure layouts and accessors, and small macros and small inline functions (ten lines or less in length), then the use of the object file is unrestricted, regardless of whether it is legally a derivative work. (Executables containing this object code plus portions of the Library will still fall under Section 6.)

Otherwise, if the work is a derivative of the Library, you may distribute the object code for the work under the terms of Section 6. Any executables containing that work also fall under Section 6, whether or not they are linked directly with the Library itself.

6. As an exception to the Sections above, you may also compile or link a "work that uses the Library" with the Library to produce a work containing portions of the Library, and distribute that work under terms of your choice, provided that the terms permit modification of the work for the customer's own use and reverse engineering for debugging such modifications.

You must give prominent notice with each copy of the work that the Library is used in it and that the Library and its use are covered by this License. You must supply a copy of this License. If the work during execution displays copyright notices, you must include the copyright notice for the Library among them, as well as a reference directing the user to the copy of this License. Also, you must do one of these things:

a.
Accompany the work with the complete corresponding machine-readable source code for the Library including whatever changes were used in the work (which must be distributed under Sections 1 and 2 above); and, if the work is an executable linked with the Library, with the complete

machine-readable "work that uses the Library", as object code and/or source code, so that the user can modify the Library and then relink to produce a modified executable containing the modified Library. (It is understood that the user who changes the contents of definitions files in the Library will not necessarily be able to recompile the application to use the modified definitions.)

b. Accompany the work with a written offer, valid for at least three years, to give the same user the materials specified in Subsection 6a, above, for a charge no more than the cost of

performing this distribution.

c. If distribution of the work is made by offering access to copy from a designated place, offer equivalent access to copy the above specified materials from the same place.

d. Verify that the user has already received a copy of these materials or that you have already sent this user a copy.

For an executable, the required form of the "work that uses the Library" must include any data and utility programs needed for reproducing the executable from it. However, as a special exception, the source code distributed need not include anything that is normally distributed (in either source or binary form) with the major components (compiler, kernel, and so on) of the operating system on which the executable runs, unless that component itself accompanies the executable.

It may happen that this requirement contradicts the license restrictions of other proprietary libraries that do not normally accompany the operating system. Such a contradiction means you cannot use both them and the Library together in an executable that you distribute.

7. You may place library facilities that are a work based on the Library side-by-side in a single library together with other library facilities not covered by this License, and distribute such a combined library, provided that the separate distribution of the work based on the Library and of the other library facilities is otherwise permitted, and provided that you do these two things:

a. Accompany the combined library with a copy of the same work based on the Library, uncombined with any other library facilities. This must be distributed under the terms of the

Sections above.

b. Give prominent notice with the combined library of the fact that part of it is a work based on the Library, and explaining

where to find the accompanying uncombined form of the same work.

8. You may not copy, modify, sublicense, link with, or distribute the Library except as expressly provided under this License. Any attempt otherwise to copy, modify, sublicense, link with, or distribute the Library is void, and will automatically terminate your rights under this License. However, parties who have received copies, or rights, from you under this License will not have their licenses terminated so long as such parties remain in full compliance.

9. You are not required to accept this License, since you have not signed it. However, nothing else grants you permission to modify or distribute the Library or its derivative works. These actions are prohibited by law if you do not accept this License. Therefore, by modifying or distributing the Library (or any work based on the Library), you indicate your acceptance of this License

to do so, and all its terms and conditions for copying, distributing or modifying the Library or works based on it.

10. Each time you redistribute the Library (or any work based on the Library), the recipient automatically receives a license from the original licensor to copy, distribute, link with or modify the Library subject to these terms and conditions. You may not impose any further restrictions on the recipients' exercise of the rights granted herein. You are not responsible for enforcing compliance by third parties to this License.

11. If, as a consequence of a court judgment or allegation of patent infringement or for any other reason (not limited to patent issues), conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot distribute so as to satisfy simultaneously

your obligations under this License and any other pertinent obligations, then as a consequence you may not distribute the Library at all. For example, if a patent license would not permit royalty-free redistribution of the Library by all those who receive copies directly or indirectly through you, then the only way you could satisfy both it and this License would be to refrain

entirely from distribution of the Library.

If any portion of this section is held invalid or unenforceable under any particular circumstance, the balance of the section is intended to apply, and the section as a whole is intended to apply in other circumstances.

It is not the purpose of this section to induce you to infringe any patents or other property right claims or to contest validity of any such claims; this section has the sole purpose of protecting the integrity of the free software distribution system which is implemented by public license practices. Many people have made generous contributions to the wide range of software distributed through that system in reliance on consistent application of that system; it is up to the author/donor to decide if he or she is willing to distribute software through any other system and a licensee cannot impose that choice.

This section is intended to make thoroughly clear what is believed to be a consequence of the rest of this License.

12. If the distribution and/or use of the Library is restricted in certain countries either by patents or by copyrighted interfaces, the original copyright holder who places the Library under this License may add an explicit geographical distribution limitation excluding those countries, so that distribution is permitted only in or among countries not thus excluded. In such case, this License incorporates the limitation as if written in the body of this License.

13. The Free Software Foundation may publish revised and/or new versions of the Library General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Library specifies a version number of this License which applies to it and "any later version", you have the option of following the terms and conditions either of that version or of any later version published by the Free Software Foundation. If the Library does not specify a license version number, you may choose any version ever published by the Free Software Foundation.

14. If you wish to incorporate parts of the Library into other free programs whose distribution conditions are incompatible with these, write to the author to ask for permission. For software which is copyrighted by the Free Software

Foundation, write to the Free

Software Foundation; we sometimes make exceptions for this. Our decision will be guided by the two goals of preserving the free status of all derivatives of our free software and of promoting the sharing and reuse of software generally.

NO WARRANTY

15. BECAUSE THE LIBRARY IS LICENSED FREE OF CHARGE, THERE IS NO WARRANTY FOR THE LIBRARY, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE LIBRARY "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE LIBRARY IS WITH YOU. SHOULD THE LIBRARY PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

16. IN NO EVENT

UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY AND/OR REDISTRIBUTE THE LIBRARY AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE LIBRARY (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE LIBRARY TO OPERATE WITH ANY OTHER SOFTWARE), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Libraries

=====

If you develop a new library, and you want it to be of the greatest possible use to the public, we recommend making it free software that everyone can redistribute and change. You can do so by permitting redistribution

under these terms (or, alternatively, under the terms of the ordinary General Public License).

To apply these terms, attach the following notices to the library. It is safest to attach them to the start of each source file to most effectively convey the exclusion of warranty; and each file should have at least the "copyright" line and a pointer to where the full notice is found.

ONE LINE TO GIVE THE LIBRARY'S NAME AND AN IDEA OF WHAT IT DOES.

Copyright (C) YEAR NAME OF AUTHOR

This library is free software; you can redistribute it and/or modify it under the terms of the GNU Library General Public License as published by the Free Software Foundation; either version 2 of the License, or (at your option) any later version.

This library is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU Library General Public License for more details.

You should have received a copy of the GNU General Public License along with this program; if not, write to the Free Software Foundation, Inc., 59 Temple Place, Suite 330, Boston, MA 02111-1307, USA.

Also add information on how to contact you by electronic and paper mail.

You should also get your employer (if you work as a programmer) or your school, if any, to sign a "copyright disclaimer" for the library, if necessary. Here is a sample; alter the names:

Yoyodyne, Inc., hereby disclaims all copyright interest in the library `Frob' (a library for tweaking knobs) written by James Random Hacker.

SIGNATURE OF TY COON, 1 April 1990
Ty Coon, President of Vice

That's all there is to it!

GNU LESSER GENERAL PUBLIC LICENSE
Version 3, 29 June 2007

Copyright (C) 2007 Free Software Foundation, Inc. <<http://fsf.org/>>
Everyone is permitted to copy and distribute verbatim copies of this license document, but changing it is not allowed.

This version of the GNU Lesser General Public License incorporates the terms and conditions of version 3 of the GNU General Public License, supplemented by the additional permissions listed below.

0. Additional Definitions.

As used herein, "this License" refers to version 3 of the GNU Lesser General Public License, and the "GNU GPL" refers to version 3 of the GNU

General Public License.

"The Library" refers to a covered work governed by this License, other than an Application or a Combined Work as defined below.

An "Application" is any work that makes use of an interface provided by the Library, but which is not otherwise based on the Library. Defining a subclass of a class defined by the Library is deemed a mode of using an interface provided by the Library.

A "Combined Work" is a work produced by combining or linking an Application with the Library. The particular version of the Library with which the Combined Work was made is also called the "Linked Version".

The "Minimal Corresponding Source" for a Combined Work means the Corresponding Source for the Combined Work, excluding any source code for portions of the Combined Work that, considered in isolation, are based on the Application, and not on the Linked Version.

The "Corresponding Application Code" for a Combined Work means the object code and/or source code for the Application, including any data and utility programs needed for reproducing the Combined Work from the Application, but excluding the System Libraries of the Combined Work.

1. Exception to Section 3 of the GNU GPL.

You may convey a covered work under sections 3 and 4 of this License without being bound by section 3 of the GNU GPL.

2. Conveying Modified Versions.

If you modify a copy of the Library, and, in your modifications, a facility refers to a function or data to be supplied by an Application that uses the facility (other than as an argument passed when the facility is invoked), then you may convey a copy of the modified version:

- a) under this License, provided that you make a good faith effort to ensure that, in the event an Application does not supply the function or data, the facility still operates, and performs whatever part of its purpose remains meaningful, or
- b) under the GNU GPL, with none of the additional permissions of this License applicable to that copy.

3. Object Code Incorporating Material from Library Header Files.

The object code form of an Application may incorporate material from a header file that is part of the Library. You may convey such object code under terms of your choice, provided that, if the incorporated material is not limited to numerical parameters, data structure layouts and accessors, or small macros, inline functions and templates (ten or fewer lines in length), you do both of the following:

- a) Give prominent notice with each copy of the object code that the Library is used in it and that the Library and its use are covered by this License.
- b) Accompany the object code with a copy of the GNU GPL and this license document.

4. Combined Works.

You may convey a Combined Work under terms of your choice that, taken together, effectively do not restrict modification of the portions of the Library contained in the Combined Work and reverse engineering for debugging such modifications, if you also do each of the following:

- a) Give prominent notice with each copy of the Combined Work that the Library is used in it and that the Library and its use are covered by this License.
- b) Accompany the Combined Work with a copy of the GNU GPL and this license document.
- c) For a Combined Work that displays copyright notices during execution, include the copyright notice for the Library among these notices, as well as a reference directing the user to the copies of the GNU GPL and this license document.
- d) Do one of the following:
 - 0) Convey the Minimal Corresponding Source under the terms of this License, and the Corresponding Application Code in a form suitable for, and under terms that permit, the user to recombine or relink the Application with a modified version of the Linked Version to produce a modified Combined Work, in the manner specified by section 6 of the GNU GPL for conveying Corresponding Source.

1) Use a suitable shared library mechanism for linking with the Library. A suitable mechanism is one that (a) uses at run time a copy of the Library already present on the user's computer system, and (b) will operate properly with a modified version of the Library that is interface-compatible with the Linked Version.

e) Provide Installation Information, but only if you would otherwise be required to provide such information under section 6 of the GNU GPL, and only to the extent that such information is necessary to install and execute a modified version of the Combined Work produced by recombining or relinking the Application with a modified version of the Linked Version. (If you use option 4d0, the Installation Information must accompany the Minimal Corresponding Source and Corresponding Application Code. If you use option 4d1, you must provide the Installation Information in the manner specified by section 6 of the GNU GPL for conveying Corresponding Source.)

5. Combined Libraries.

You may place library facilities that are a work based on the Library side by side in a single library together with other library facilities that are not Applications and are not covered by this License, and convey such a combined library under terms of your choice, if you do both of the following:

- a) Accompany the combined library with a copy of the same work based on the Library, uncombined with any other library facilities, conveyed under the terms of this License.
- b) Give prominent notice with the combined library that part of it is a work based on the Library, and explaining where to find the accompanying uncombined form of the same work.

6. Revised Versions of the GNU Lesser General Public License.

The Free Software Foundation may publish revised and/or new versions of the GNU Lesser General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Library as you received it specifies that a certain numbered version of the GNU Lesser General Public License "or any later version" applies to it, you have the option of following

the terms and conditions either of that published version or of any later version published by the Free Software Foundation. If the Library as you received it does not specify a version number of the GNU Lesser General Public License, you may choose any version of the GNU Lesser General Public License ever published by the Free Software Foundation.

If the Library as you received it specifies that a proxy can decide whether future versions of the GNU Lesser General Public License shall apply, that proxy's public statement of acceptance of any version is permanent authorization for you to choose that version for the Library.

=====
compiler_rt License
=====

The compiler_rt library is dual licensed under both the University of Illinois "BSD-Like" license and the MIT license. As a user of this code you may choose to use it under either license. As a contributor, you agree to allow your code to be used under both.

Full text of the relevant licenses is included below.

=====
University of Illinois/NCSA
Open Source License

Copyright (c) 2009-2012 by the contributors listed in CREDITS.TXT

All rights reserved.

Developed by:

LLVM Team

University of Illinois at Urbana-Champaign

<http://llvm.org>

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal with the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

* Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimers.

* Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimers in the documentation and/or other materials provided with the distribution.

* Neither the names of the LLVM Team, University of Illinois at Urbana-Champaign, nor the names of its contributors may be used to endorse or promote products derived from this Software without specific prior written permission.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS

FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE CONTRIBUTORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS WITH THE SOFTWARE.

=====

Copyright (c) 2009-2012 by the contributors listed in CREDITS.TXT

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

=====

Copyrights and Licenses for Third Party Software Distributed with LLVM:

=====

The LLVM software contains code written by third parties. Such software will

have its own individual LICENSE.TXT file in the directory in which it appears. This file will describe the copyrights, license, and restrictions which apply to that code.

The disclaimer of warranty in the University of Illinois Open Source License applies to all code in the LLVM Distribution, and nothing in any of the other licenses gives permission to use the names of the LLVM Team or the University of Illinois to endorse or promote products derived from this Software.

The following pieces of software have additional or alternate copyrights, licenses, and/or restrictions:

Program	Directory
-----	-----
mach_override	lib/interception/mach_override
Boost Software License - Version 1.0 - August 17th, 2003	

Permission is hereby granted, free of charge, to any person or organization obtaining a copy of the software and accompanying documentation covered by this license (the "Software") to use, reproduce, display, distribute, execute, and transmit the Software, and to prepare derivative works of the Software, and to permit third-parties to whom the Software is furnished to do so, all subject to the following:

The copyright notices in the Software and this entire statement, including the above license grant, this restriction and the following disclaimer, must be included in all copies of the Software, in whole or in part, and all derivative works of the Software, unless such copies or derivative works are solely in the form of machine-executable object code generated by a source language processor.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, TITLE AND NON-INFRINGEMENT. IN NO EVENT SHALL THE COPYRIGHT HOLDERS OR ANYONE DISTRIBUTING THE SOFTWARE BE LIABLE FOR ANY DAMAGES OR OTHER LIABILITY, WHETHER IN CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.36 libstd-c 8.4.0-1ubuntu1~18.04

1.36.1 Available under license :

GNU GENERAL PUBLIC LICENSE

Version 2, June 1991

Copyright (C) 1989, 1991 Free Software Foundation, Inc.

51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA

Everyone is permitted to copy and distribute verbatim copies of this license document, but changing it is not allowed.

Preamble

The licenses for most software are designed to take away your freedom to share and change it. By contrast, the GNU General Public License is intended to guarantee your freedom to share and change free software--to make sure the software is free for all its users. This General Public License applies to most of the Free Software Foundation's software and to any other program whose authors commit to using it. (Some other Free Software Foundation software is covered by the GNU Library General Public License instead.) You can apply it to your programs, too.

When we speak of free software, we are referring to freedom, not price. Our General Public Licenses are designed to make sure that you have the freedom to distribute copies of free software (and charge for this service if you wish), that you receive source code or can get it if you want it, that you can change the software or use pieces of it in new free programs; and that you know you can do these things.

To protect your rights, we need to make restrictions that forbid anyone to deny you these rights or to ask you to surrender the rights. These restrictions translate to certain responsibilities for you if you distribute copies of the software, or if you modify it.

For example, if you distribute copies of such a program, whether gratis or for a fee, you must give the recipients all the rights that you have. You must make sure that they, too, receive or can get the source code. And you must show them these terms so they know their rights.

We protect your rights with two steps: (1) copyright the software, and (2) offer you this license which gives you legal permission to copy, distribute and/or modify the software.

Also, for each author's protection and ours, we want to make certain that everyone understands that there is no warranty for this free software. If the software is modified by someone else and passed on, we

want its recipients to know that what they have is not the original, so that any problems introduced by others will not reflect on the original authors' reputations.

Finally, any free program is threatened constantly by software patents. We wish to avoid the danger that redistributors of a free program will individually obtain patent licenses, in effect making the program proprietary. To prevent this, we have made it clear that any patent must be licensed for everyone's free use or not licensed at all.

The precise terms and conditions for copying, distribution and modification follow.

GNU GENERAL PUBLIC LICENSE TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

0. This License applies to any program or other work which contains a notice placed by the copyright holder saying it may be distributed under the terms of this General Public License. The "Program", below, refers to any such program or work, and a "work based on the Program" means either the Program or any derivative work under copyright law: that is to say, a work containing the Program or a portion of it, either verbatim or with modifications and/or translated into another language. (Hereinafter, translation is included without limitation in the term "modification".) Each licensee is addressed as "you".

Activities other than copying, distribution and modification are not covered by this License; they are outside its scope. The act of running the Program is not restricted, and the output from the Program is covered only if its contents constitute a work based on the Program (independent of having been made by running the Program). Whether that is true depends on what the Program does.

1. You may copy and distribute verbatim copies of the Program's source code as you receive it, in any medium, provided that you conspicuously and appropriately publish on each copy an appropriate copyright notice and disclaimer of warranty; keep intact all the notices that refer to this License and to the absence of any warranty; and give any other recipients of the Program a copy of this License along with the Program.

You may charge a fee for the physical act of transferring a copy, and you may at your option offer warranty protection in exchange for a fee.

2. You may modify your copy or copies of the Program or any portion of it, thus forming a work based on the Program, and copy and

distribute such modifications or work under the terms of Section 1 above, provided that you also meet all of these conditions:

a) You must cause the modified files to carry prominent notices stating that you changed the files and the date of any change.

b) You must cause any work that you distribute or publish, that in whole or in part contains or is derived from the Program or any part thereof, to be licensed as a whole at no charge to all third parties under the terms of this License.

c) If the modified program normally reads commands interactively when run, you must cause it, when started running for such interactive use in the most ordinary way, to print or display an announcement including an appropriate copyright notice and a notice that there is no warranty (or else, saying that you provide a warranty) and that users may redistribute the program under these conditions, and telling the user how to view a copy of this License. (Exception: if the Program itself is interactive but does not normally print such an announcement, your work based on the Program is not required to print an announcement.)

These requirements apply to the modified work as a whole. If identifiable sections of that work are not derived from the Program, and can be reasonably considered independent and separate works in themselves, then this License, and its terms, do not apply to those sections when you distribute them as separate works. But when you distribute the same sections as part of a whole which is a work based on the Program, the distribution of the whole must be on the terms of this License, whose permissions for other licensees extend to the entire whole, and thus to each and every part regardless of who wrote it.

Thus, it is not the intent of this section to claim rights or contest your rights to work written entirely by you; rather, the intent is to exercise the right to control the distribution of derivative or collective works based on the Program.

In addition, mere aggregation of another work not based on the Program with the Program (or with a work based on the Program) on a volume of a storage or distribution medium does not bring the other work under the scope of this License.

3. You may copy and distribute the Program (or a work based on it, under Section 2) in object code or executable form under the terms of Sections 1 and 2 above provided that you also do one of the following:

- a) Accompany it with the complete corresponding machine-readable source code, which must be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange; or,

- b) Accompany it with a written offer, valid for at least three years, to give any third party, for a charge no more than your cost of physically performing source distribution, a complete machine-readable copy of the corresponding source code, to be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange; or,

- c) Accompany it with the information you received as to the offer to distribute corresponding source code. (This alternative is allowed only for noncommercial distribution and only if you received the program in object code or executable form with such an offer, in accord with Subsection b above.)

The source code for a work means the preferred form of the work for making modifications to it. For an executable work, complete source code means all the source code for all modules it contains, plus any associated interface definition files, plus the scripts used to control compilation and installation of the executable. However, as a special exception, the source code distributed need not include anything that is normally distributed (in either source or binary form) with the major components (compiler, kernel, and so on) of the operating system on which the executable runs, unless that component itself accompanies the executable.

If distribution of executable or object code is made by offering access to copy from a designated place, then offering equivalent access to copy the source code from the same place counts as distribution of the source code, even though third parties are not compelled to copy the source along with the object code.

4. You may not copy, modify, sublicense, or distribute the Program except as expressly provided under this License. Any attempt otherwise to copy, modify, sublicense or distribute the Program is void, and will automatically terminate your rights under this License. However, parties who have received copies, or rights, from you under this License will not have their licenses terminated so long as such parties remain in full compliance.

5. You are not required to accept this License, since you have not signed it. However, nothing else grants you permission to modify or distribute the Program or its derivative works. These actions are

prohibited by law if you do not accept this License. Therefore, by modifying or distributing the Program (or any work based on the Program), you indicate your acceptance of this License to do so, and all its terms and conditions for copying, distributing or modifying the Program or works based on it.

6.

Each time you redistribute the Program (or any work based on the Program), the recipient automatically receives a license from the original licensor to copy, distribute or modify the Program subject to these terms and conditions. You may not impose any further restrictions on the recipients' exercise of the rights granted herein. You are not responsible for enforcing compliance by third parties to this License.

7. If, as a consequence of a court judgment or allegation of patent infringement or for any other reason (not limited to patent issues), conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot distribute so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not distribute the Program at all. For example, if a patent license would not permit royalty-free redistribution of the Program by all those who receive copies directly or indirectly through you, then the only way you could satisfy both it and this License would be to refrain entirely from distribution of the Program.

If any portion of this section is held invalid or unenforceable under any particular circumstance, the balance of the section is intended to apply and the section as a whole is intended to apply in other circumstances.

It is not the purpose of this section to induce you to infringe any patents or other property right claims or to contest validity of any such claims; this section has the sole purpose of protecting the integrity of the free software distribution system, which is implemented by public license practices. Many people have made generous contributions to the wide range of software distributed through that system in reliance on consistent application of that system; it is up to the author/donor to decide if he or she is willing to distribute software through any other system and a licensee cannot impose that choice.

This section is intended to make thoroughly clear what is believed to be a consequence of the rest of this License.

8. If the distribution and/or use of the Program is restricted in certain countries either by patents or by copyrighted interfaces, the original copyright holder who places the Program under this License may add an explicit geographical distribution limitation excluding those countries, so that distribution is permitted only in or among countries not thus excluded. In such case, this License incorporates the limitation as if written in the body of this License.

9. The Free Software Foundation may publish revised and/or new versions of the General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Program specifies a version number of this License which applies to it and "any later version", you have the option of following the terms and conditions either of that version or of any later version published by the Free Software Foundation. If the Program does not specify a version number of this License, you may choose any version ever published by the Free Software Foundation.

10. If you wish to incorporate parts of the Program into other free programs whose distribution conditions are different, write to the author to ask for permission. For software which is copyrighted by the Free Software Foundation, write to the Free Software Foundation; we sometimes make exceptions for this. Our decision will be guided by the two goals of preserving the free status of all derivatives of our free software and of promoting the sharing and reuse of software generally.

NO WARRANTY

11. BECAUSE THE PROGRAM IS LICENSED FREE OF CHARGE, THERE IS NO WARRANTY FOR THE PROGRAM, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE PROGRAM "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE PROGRAM IS WITH YOU. SHOULD THE PROGRAM PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

12. IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY AND/OR REDISTRIBUTE THE PROGRAM AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING

OUT OF THE USE OR INABILITY TO USE THE PROGRAM (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE PROGRAM TO OPERATE WITH ANY OTHER PROGRAMS),
EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Programs

If you develop a new program, and you want it to be of the greatest possible use to the public, the best way to achieve this is to make it free software which everyone can redistribute and change under these terms.

To do so, attach the following notices to the program. It is safest to attach them to the start of each source file to most effectively convey the exclusion of warranty; and each file should have at least the "copyright" line and a pointer to where the full notice is found.

<one line to give the program's name and a brief idea of what it does.>
Copyright (C) <year> <name of author>

This program is free software; you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation; either version 2 of the License, or
(at your option) any later version.

This program is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details.

You should have received a copy of the GNU General Public License along with this program; if not, write to the Free Software Foundation, Inc., 51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA

Also add information on how to contact you by electronic and paper mail.

If the program is interactive, make it output a short notice like this when it starts in an interactive mode:

Gnomovision version 69, Copyright (C) year name of author
Gnomovision comes with ABSOLUTELY NO WARRANTY; for details type `show w'.
This is free software, and you are welcome to redistribute it under certain conditions; type `show c' for details.

The hypothetical commands

`show w' and `show c' should show the appropriate parts of the General Public License. Of course, the commands you use may be called something other than `show w' and `show c'; they could even be mouse-clicks or menu items--whatever suits your program.

You should also get your employer (if you work as a programmer) or your school, if any, to sign a "copyright disclaimer" for the program, if necessary. Here is a sample; alter the names:

Yoyodyne, Inc., hereby disclaims all copyright interest in the program
`Gnomovision' (which makes passes at compilers) written by James Hacker.

<signature of Ty Coon>, 1 April 1989

Ty Coon, President of Vice

This General Public License does not permit incorporating your program into proprietary programs. If your program is a subroutine library, you may consider it more useful to permit linking proprietary applications with the library. If this is what you want to do, use the GNU Library General Public License instead of this License.

This program, "bzip2", the associated library "libbzip2", and all documentation, are copyright (C) 1996-2010 Julian R Seward. All rights reserved.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

1. Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.
2. The origin of this software must not be misrepresented; you must not claim that you wrote the original software. If you use this software in a product, an acknowledgment in the product documentation would be appreciated but is not required.
3. Altered source versions must be plainly marked as such, and must not be misrepresented as being the original software.
4. The name of the author may not be used to endorse or promote products derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE AUTHOR ``AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE AUTHOR BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

Julian Seward, jseward@bzip.org
bzip2/libbzip2 version 1.0.6 of 6 September 2010

The newlib subdirectory is a collection of software from several sources.

Each file may have its own copyright/license that is embedded in the source file. Unless otherwise noted in the body of the source file(s), the following copyright notices will apply to the contents of the newlib subdirectory:

(1) Red Hat Incorporated

Copyright (c) 1994-2009 Red Hat, Inc. All rights reserved.

This copyrighted material is made available to anyone wishing to use, modify, copy, or redistribute it subject to the terms and conditions of the BSD License. This program is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY expressed or implied, including the implied warranties of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. A copy of this license is available at <http://www.opensource.org/licenses>. Any Red Hat trademarks that are incorporated in the source code or documentation are not subject to the BSD License and may only be used or replicated with the express permission of Red Hat, Inc.

(2) University of California, Berkeley

Copyright (c) 1981-2000 The Regents of the University of California.
All rights reserved.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

* Redistributions of source code must retain the above copyright notice,

this list of conditions and the following disclaimer.

- * Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.
- * Neither the name of the University nor the names of its contributors may be used to endorse or promote products derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED.

IN NO EVENT SHALL THE COPYRIGHT OWNER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

(3) David M. Gay (AT&T 1991, Lucent 1998)

The author of this software is David M. Gay.

Copyright (c) 1991 by AT&T.

Permission to use, copy, modify, and distribute this software for any purpose without fee is hereby granted, provided that this entire notice is included in all copies of any software which is or includes a copy or modification of this software and in all copies of the supporting documentation for such software.

THIS SOFTWARE IS BEING PROVIDED "AS IS", WITHOUT ANY EXPRESS OR IMPLIED WARRANTY. IN PARTICULAR, NEITHER THE AUTHOR NOR AT&T MAKES ANY REPRESENTATION OR WARRANTY OF ANY KIND CONCERNING THE MERCHANTABILITY OF THIS SOFTWARE OR ITS FITNESS FOR ANY PARTICULAR PURPOSE.

The author of this software is David M. Gay.

Copyright (C) 1998-2001 by Lucent Technologies
All Rights Reserved

Permission to use, copy, modify, and distribute this software and its documentation for any purpose and without fee is hereby granted, provided that the above copyright notice appear in all copies and that both that the copyright notice and this permission notice and warranty disclaimer appear in supporting documentation, and that the name of Lucent or any of its entities not be used in advertising or publicity pertaining to distribution of the software without specific, written prior permission.

LUCENT

DISCLAIMS ALL WARRANTIES WITH REGARD TO THIS SOFTWARE, INCLUDING ALL IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS. IN NO EVENT SHALL LUCENT OR ANY OF ITS ENTITIES BE LIABLE FOR ANY SPECIAL, INDIRECT OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES WHATSOEVER RESULTING FROM LOSS OF USE, DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE OR OTHER TORTIOUS ACTION, ARISING OUT OF OR IN CONNECTION WITH THE USE OR PERFORMANCE OF THIS SOFTWARE.

(4) Advanced Micro Devices

Copyright 1989, 1990 Advanced Micro Devices, Inc.

This software is the property of Advanced Micro Devices, Inc (AMD) which specifically grants the user the right to modify, use and distribute this software provided this notice is not removed or altered. All other rights are reserved by AMD.

AMD MAKES NO WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, WITH REGARD TO THIS SOFTWARE. IN NO EVENT SHALL AMD BE LIABLE FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES IN CONNECTION WITH OR ARISING FROM THE FURNISHING, PERFORMANCE, OR USE OF THIS SOFTWARE.

So that all may benefit from your experience, please report any problems or suggestions about this software to the 29K Technical Support Center at 800-29-29-AMD (800-292-9263) in the USA, or 0800-89-1131 in the UK, or 0031-11-1129 in Japan, toll free. The direct dial number is 512-462-4118.

Advanced Micro Devices, Inc.
29K Support Products
Mail Stop 573
5900 E. Ben White Blvd.
Austin, TX 78741
800-292-9263

(5)

(6)

(7) Sun Microsystems

Copyright (C) 1993 by Sun Microsystems, Inc. All rights reserved.

Developed at SunPro, a Sun Microsystems, Inc. business.
Permission to use, copy, modify, and distribute this software is freely granted, provided that this notice is preserved.

(8) Hewlett Packard

(c) Copyright 1986 HEWLETT-PACKARD COMPANY

To anyone who acknowledges that this file is provided "AS IS" without any express or implied warranty:

permission to use, copy, modify, and distribute this file for any purpose is hereby granted without fee, provided that the above copyright notice and this notice appears in all copies, and that the name of Hewlett-Packard Company not be used in advertising or publicity pertaining to distribution of the software without specific, written prior permission. Hewlett-Packard Company makes no representations about the suitability of this software for any purpose.

(9) Hans-Peter Nilsson

Copyright (C) 2001 Hans-Peter Nilsson

Permission to use, copy, modify, and distribute this software is freely granted, provided that the above copyright notice, this notice and the following disclaimer are preserved with no changes.

THIS SOFTWARE IS PROVIDED ``AS IS" AND WITHOUT ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, WITHOUT LIMITATION, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE.

(10) Stephane Carrez (m68hc11-elf/m68hc12-elf targets only)

Copyright (C) 1999, 2000, 2001, 2002 Stephane Carrez (stcarrez@nerim.fr)

The authors hereby grant permission to use, copy, modify, distribute, and license this software and its documentation for any purpose, provided

that existing copyright notices are retained in all copies and that this notice is included verbatim in any distributions. No written agreement, license, or royalty fee is required for any of the authorized uses. Modifications to this software may be copyrighted by their authors and need not follow the licensing terms described here, provided that the new terms are clearly indicated on the first page of each file where they apply.

(11) Christopher G. Demetriou

Copyright (c) 2001 Christopher G. Demetriou

All rights reserved.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

1. Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.
2. Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.
3. The name of the author may not be used to endorse or promote products derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE AUTHOR ``AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE AUTHOR BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

(12) SuperH, Inc.

Copyright

2002 SuperH, Inc. All rights reserved

This software is the property of SuperH, Inc (SuperH) which specifically grants the user the right to modify, use and distribute this software provided this notice is not removed or altered. All other rights are reserved by SuperH.

SUPERH MAKES NO WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, WITH REGARD TO THIS SOFTWARE. IN NO EVENT SHALL SUPERH BE LIABLE FOR INDIRECT, SPECIAL,

INCIDENTAL OR CONSEQUENTIAL DAMAGES IN CONNECTION WITH OR ARISING FROM THE FURNISHING, PERFORMANCE, OR USE OF THIS SOFTWARE.

So that all may benefit from your experience, please report any problems or suggestions about this software to the SuperH Support Center via e-mail at softwaresupport@superh.com .

SuperH, Inc.
405 River Oaks Parkway
San Jose
CA 95134
USA

(13) Royal Institute of Technology

Copyright (c) 1999 Kungliga Tekniska Hgskolan
(Royal Institute of Technology, Stockholm, Sweden).
All rights reserved.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

1. Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.
2. Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.
3. Neither the name of KTH nor the names of its contributors may be used to endorse or promote products derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY KTH AND ITS CONTRIBUTORS ``AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL KTH OR ITS CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

(14) Alexey Zelkin

Copyright (c) 2000, 2001 Alexey Zelkin <phantom@FreeBSD.org>
All rights reserved.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

1. Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.
2. Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.

THIS SOFTWARE IS PROVIDED BY THE AUTHOR AND CONTRIBUTORS

``AS IS" AND

ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE AUTHOR OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

(15) Andrey A. Chernov

Copyright (C) 1997 by Andrey A. Chernov, Moscow, Russia.
All rights reserved.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

1. Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.
2. Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.

THIS SOFTWARE IS PROVIDED BY THE AUTHOR ``AS IS" AND

ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE REGENTS OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION)

HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

(16)

FreeBSD

Copyright (c) 1997-2002 FreeBSD Project.

All rights reserved.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

1. Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.
2. Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.

THIS SOFTWARE IS PROVIDED BY THE AUTHOR AND CONTRIBUTORS ``AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE AUTHOR OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR

SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION)

HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

(17) S. L. Moshier

Author: S. L. Moshier.

Copyright (c) 1984,2000 S.L. Moshier

Permission to use, copy, modify, and distribute this software for any purpose without fee is hereby granted, provided that this entire notice is included in all copies of any software which is or includes a copy or modification of this software and in all copies of the supporting documentation for such software.

THIS SOFTWARE IS BEING PROVIDED "AS IS", WITHOUT ANY EXPRESS OR IMPLIED WARRANTY. IN PARTICULAR, THE AUTHOR MAKES NO REPRESENTATION OR WARRANTY OF ANY KIND CONCERNING THE MERCHANTABILITY OF THIS

SOFTWARE OR ITS FITNESS FOR ANY PARTICULAR PURPOSE.

(18) Citrus Project

Copyright (c)1999 Citrus Project,
All
rights reserved.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

1. Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.
2. Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.

THIS SOFTWARE IS PROVIDED BY THE AUTHOR AND CONTRIBUTORS ``AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE AUTHOR OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

(19) Todd C. Miller

Copyright (c) 1998 Todd C. Miller <Todd.Miller@courtesan.com>
All rights reserved.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

1. Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.
2. Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.
3. The name of the author may not be used to endorse or promote products derived from this software without specific prior written permission.

THIS SOFTWARE

IS PROVIDED ``AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE AUTHOR BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

(20) DJ Delorie (i386 / arm)
Copyright (C) 1991 DJ Delorie
All rights reserved.

Redistribution, modification, and use in source and binary forms is permitted provided that the above copyright notice and following paragraph are duplicated in all such forms.

This file is distributed WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.

(21) Free Software Foundation LGPL License (*-linux* targets only)

Copyright (C) 1990-1999, 2000, 2001 Free Software Foundation, Inc.
This file is part of the GNU C Library.
Contributed by Mark Kettenis <kettenis@phys.uva.nl>, 1997.

The GNU C Library is free software; you can redistribute it and/or modify it under the terms of the GNU Lesser General Public License as published by the Free Software Foundation; either version 2.1 of the License, or (at your option) any later version.

The GNU C Library is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU Lesser General Public License for more details.

You should have received a copy of the GNU Lesser General Public License along with the GNU C Library; if not, write to the Free Software Foundation, Inc., 51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA.

(22) Xavier Leroy LGPL License (i[3456]86-*-*linux* targets only)

Copyright (C) 1996 Xavier Leroy (Xavier.Leroy@inria.fr)

This program is free software; you can redistribute it and/or modify it under the terms of the GNU Library General Public License as published by the Free Software Foundation; either version 2 of the License, or (at your option) any later version.

This program is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU Library General Public License for more details.

(23) Intel (i960)

Copyright (c) 1993 Intel Corporation

Intel hereby grants you permission to copy, modify, and distribute this software and its documentation. Intel grants this permission provided that the above copyright notice appears in all copies and that both the copyright notice and this permission notice appear in supporting documentation. In addition, Intel grants this permission provided that you prominently mark as "not part of the original" any modifications made to this software or documentation, and that the name of Intel Corporation not be used in advertising or publicity pertaining to distribution of the software or the documentation without specific, written prior permission.

Intel Corporation provides this AS IS, WITHOUT ANY WARRANTY, EXPRESS OR IMPLIED, INCLUDING, WITHOUT LIMITATION, ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Intel makes no guarantee or representations regarding the use of, or the results of the use of, the software and documentation in terms of correctness, accuracy, reliability, currentness, or otherwise; and you rely on the software, documentation and results solely at your own risk.

IN NO EVENT SHALL INTEL BE LIABLE FOR ANY LOSS OF USE, LOSS OF BUSINESS, LOSS OF PROFITS, INDIRECT, INCIDENTAL, SPECIAL OR CONSEQUENTIAL DAMAGES OF ANY KIND. IN NO EVENT SHALL INTEL'S TOTAL LIABILITY EXCEED THE SUM PAID TO INTEL FOR THE PRODUCT LICENSED HEREUNDER.

(24) Hewlett-Packard (hppa targets only)

(c) Copyright 1986 HEWLETT-PACKARD COMPANY

To anyone who acknowledges that this file is provided "AS IS" without any express or implied warranty:
permission to use, copy, modify, and distribute this file

for any purpose is hereby granted without fee, provided that the above copyright notice and this notice appears in all copies, and that the name of Hewlett-Packard Company not be used in advertising or publicity pertaining to distribution of the software without specific, written prior permission. Hewlett-Packard Company makes no representations about the suitability of this software for any purpose.

(25) Henry Spencer (only *-linux targets)

Copyright 1992, 1993, 1994 Henry Spencer. All rights reserved. This software is not subject to any license of the American Telephone and Telegraph Company or of the Regents of the University of California.

Permission is granted to anyone to use this software for any purpose on any computer system, and to alter it and redistribute it, subject to the following restrictions:

1. The author is not responsible for the consequences of use of this software, no matter how awful, even if they arise from flaws in it.
2. The origin of this software must not be misrepresented, either by explicit claim or by omission. Since few users ever read sources, credits must appear in the documentation.
3. Altered versions must be plainly marked as such, and must not be misrepresented as being the original software. Since few users ever read sources, credits must appear in the documentation.
4. This notice may not be removed or altered.

(26) Mike Barcroft

Copyright (c) 2001 Mike Barcroft <mike@FreeBSD.org>
All rights reserved.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

1. Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.
2. Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.

THIS SOFTWARE IS PROVIDED BY THE AUTHOR AND CONTRIBUTORS ``AS IS'' AND

ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE AUTHOR OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

(27) Konstantin Chuguev (--enable-newlib-iconv)

Copyright (c) 1999, 2000

Konstantin Chuguev. All rights reserved.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

1. Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.
2. Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.

THIS SOFTWARE IS PROVIDED BY THE AUTHOR AND CONTRIBUTORS ``AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE AUTHOR OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

iconv (Charset Conversion Library) v2.0

(28) Artem Bityuckiy (--enable-newlib-iconv)

Copyright (c) 2003, Artem B. Bityuckiy, SoftMine Corporation.

Rights transferred to Franklin Electronic Publishers.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions

are met:

1. Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.
2. Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.

THIS SOFTWARE IS PROVIDED BY THE AUTHOR AND CONTRIBUTORS ``AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE AUTHOR OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

(29) IBM, Sony, Toshiba (only spu-* targets)

(C) Copyright 2001,2006,
International Business Machines Corporation,
Sony Computer Entertainment, Incorporated,
Toshiba Corporation,

All rights reserved.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

- * Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.
- * Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.
- * Neither the names of the copyright holders nor the names of their contributors may be used to endorse or promote products derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS

INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

(30) - Alex Tatmanjants (targets using libc/posix)

Copyright (c) 1995 Alex Tatmanjants <alex@elvisti.kiev.ua>
at Electronni Visti IA, Kiev, Ukraine.
All rights reserved.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

1. Redistributions of source code must retain the above copyright notice,
this list of conditions and the following disclaimer.
2. Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.

THIS SOFTWARE IS PROVIDED BY THE AUTHOR ``AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE AUTHOR BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

(31) - M. Warner Losh (targets using libc/posix)

Copyright (c) 1998, M. Warner Losh <imp@freebsd.org>
All rights reserved.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

1. Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.
2. Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.

THIS SOFTWARE IS PROVIDED BY THE AUTHOR AND CONTRIBUTORS ``AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE AUTHOR OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

(32) - Andrey A. Chernov (targets using libc/posix)

Copyright (C) 1996 by Andrey A. Chernov, Moscow, Russia.
All rights reserved.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

1. Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.
2. Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.

THIS SOFTWARE IS PROVIDED BY THE AUTHOR ``AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE REGENTS OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

(33) - Daniel Eischen (targets using libc/posix)

Copyright (c) 2001 Daniel Eischen <deischen@FreeBSD.org>.
All rights reserved.

Redistribution and use in source and binary forms, with or without modification,

are permitted provided that the following conditions

are met:

1. Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.
2. Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.

THIS SOFTWARE IS PROVIDED BY THE AUTHOR AND CONTRIBUTORS ``AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE REGENTS OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

(34) - Jon Beniston (only lm32-* targets)

Contributed by Jon Beniston <jon@beniston.com>

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

1. Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.
2. Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.

THIS SOFTWARE IS PROVIDED BY THE AUTHOR AND CONTRIBUTORS ``AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED.

IN NO EVENT SHALL THE AUTHOR OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

(35) - Arm Ltd

Copyright (c) 2009-2018 Arm Ltd
All rights reserved.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

1. Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.
2. Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.
3. The name of the company may not be used to endorse or promote products derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY ARM LTD ``AS IS'' AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL ARM LTD BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

(36) - Xilinx, Inc. (microblaze-* and powerpc-* targets)

Copyright
(c) 2004, 2009 Xilinx, Inc. All rights reserved.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

1. Redistributions source code must retain the above copyright notice, this list of conditions and the following disclaimer.
2. Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.
3. Neither the name of Xilinx nor the names of its contributors may be used to endorse or promote products derived from this software without

specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDER AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT HOLDER

OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

(37) Texas Instruments Incorporated (tic6x-*, *-tirtos targets)

Copyright (c) 1996-2010,2014 Texas Instruments Incorporated
<http://www.ti.com/>

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.

Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.

Neither the name of Texas Instruments Incorporated nor the names of its contributors may be used to endorse or promote products derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT

LIABILITY, OR TORT
(INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE
OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

(38) National Semiconductor (cr16-* and crx-* targets)

Copyright (c) 2004 National Semiconductor Corporation

The authors hereby grant permission to use, copy, modify, distribute,
and license this software and its documentation for any purpose, provided
that existing copyright notices are retained in all copies and that this
notice is included verbatim in any distributions. No written agreement,
license, or royalty fee is required for any of the authorized uses.

Modifications to this software may be copyrighted by their authors
and need not follow the licensing terms described here, provided that
the new terms are clearly indicated on the first page of each file where
they apply.

(39) - Adapteva, Inc. (epiphany-* targets)

Copyright (c) 2011, Adapteva, Inc.
All rights reserved.

Redistribution and use in source and binary
forms, with or without

modification, are permitted provided that the following conditions are met:

- * Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.
- * Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.
- * Neither the name of Adapteva nor the names of its contributors may be used to endorse or promote products derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT HOLDER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES

(INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

(40) - Altera Corporation (nios2-* targets)

Copyright (c) 2003 Altera Corporation

All rights reserved.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

- o Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.
- o Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.
- o Neither the name of Altera Corporation nor the names of its contributors may be used to endorse or promote products derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY ALTERA CORPORATION, THE COPYRIGHT HOLDER, AND ITS CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT HOLDER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

(41) Ed Schouten - Free
BSD

Copyright (c) 2008 Ed Schouten <ed@FreeBSD.org>

All rights reserved.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

1. Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.
2. Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.

THIS SOFTWARE IS PROVIDED BY THE AUTHOR AND CONTRIBUTORS ``AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE

ARE DISCLAIMED. IN NO EVENT SHALL THE AUTHOR OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

(42) - Rolls-Royce Controls and Data Services Limited (visium-* targets)

Copyright (c) 2015 Rolls-Royce Controls and Data Services Limited.
All rights reserved.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

- * Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.
- * Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.
- * Neither the name of Rolls-Royce Controls and Data Services Limited nor the names of its contributors may be used to endorse or promote products derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT HOLDER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

(43) - FTDI (ft32-* targets)

Copyright (C) 2014 FTDI (support@ftdichip.com)

The authors hereby grant permission to use, copy, modify, distribute, and license this software and its documentation for any purpose, provided that existing copyright notices are retained in all copies and that this notice is included verbatim in any distributions. No written agreement,

license, or royalty fee is required for any of the authorized uses. Modifications to this software may be copyrighted by their authors and need not follow the licensing terms described here, provided that the new terms are clearly indicated on the first page of each file where they apply.

(44) - Synopsys Inc (arc-* targets)

Copyright (c) 2015, Synopsys, Inc. All rights reserved.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

1) Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.

2) Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.

3) Neither the name of the Synopsys, Inc., nor the names of its contributors may be used to endorse or promote products derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT HOLDER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

(45) Phoenix Systems - Phoenix-RTOS targets

Copyright (c) 2016 Phoenix Systems
All rights reserved.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

1. Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.

2. Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.

THIS SOFTWARE IS PROVIDED BY THE AUTHOR AND CONTRIBUTORS ``AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE AUTHOR OR CONTRIBUTORS BE LIABLE FOR

ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

(46) embedded brains - RTEMS targets

Copyright (c) 2017 embedded brains GmbH
All rights reserved.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

1. Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.
2. Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.

THIS SOFTWARE IS PROVIDED BY THE AUTHOR AND CONTRIBUTORS ``AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE AUTHOR OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

(47) John Baldwin - RTEMS targets

Copyright (c) 2015 John Baldwin <jhb@FreeBSD.org>.
All rights reserved.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

1. Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.
2. Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.
3. Neither the name of the author nor the names of its contributors may be used to endorse or promote products derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE REGENTS AND CONTRIBUTORS ``AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE REGENTS OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES;

LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

(48) Jeffrey Roberson - RTEMS targets

Copyright (c) 2008, Jeffrey Roberson <jeff@freebsd.org>
All rights reserved.

Copyright (c) 2008 Nokia Corporation
All rights reserved.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

1. Redistributions of source code must retain the above copyright notice unmodified, this list of conditions, and the following disclaimer.
2. Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.

THIS SOFTWARE IS PROVIDED

BY THE AUTHOR ``AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE AUTHOR BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

(49) - SiFive Inc. (riscv-* targets)

Copyright (c) 2017 SiFive Inc. All rights reserved.

This copyrighted material is made available to anyone wishing to use, modify, copy, or redistribute it subject to the terms and conditions of the FreeBSD License. This program is distributed in the hope that it will be useful,

but WITHOUT ANY WARRANTY expressed or implied, including the implied warranties of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. A copy of this license is available at <http://www.opensource.org/licenses>.

(50) Michael R. Neilly (riscv-* targets)

(c) Copyright 2017 Michael R. Neilly
All rights reserved.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

* Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.

* Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.

* Neither the names of the copyright holders nor the names of their contributors may be used to endorse or promote products derived from this software without specific prior written permission.

THIS SOFTWARE
IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS
"AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT
LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS

FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

GNU LESSER GENERAL PUBLIC LICENSE

Version 2.1, February 1999

Copyright (C) 1991, 1999 Free Software Foundation, Inc.
51 Franklin St, Fifth Floor, Boston, MA 02110-1301 USA
Everyone is permitted to copy and distribute verbatim copies of this license document, but changing it is not allowed.

[This is the first released version of the Lesser GPL. It also counts as the successor of the GNU Library Public License, version 2, hence the version number 2.1.]

Preamble

The licenses for most software are designed to take away your freedom to share and change it. By contrast, the GNU General Public Licenses are intended to guarantee your freedom to share and change free software--to make sure the software is free for all its users.

This license, the Lesser General Public License, applies to some specially designated software packages--typically libraries--of the Free Software Foundation and other authors who decide to use it. You can use it too, but we suggest you first think carefully about whether this license or the ordinary General Public License is the better strategy to use in any particular case, based on the explanations below.

When we speak of free software, we are referring to freedom of use, not price. Our General Public Licenses are designed to make sure that you have the freedom to distribute copies of free software (and charge for this service if you wish); that you receive source code or can get it if you want it; that you can change the software and use pieces of it in new free programs; and that you are informed that you can do these things.

To protect your rights, we need to make restrictions that forbid distributors to deny you these rights or to ask you to surrender these

rights. These restrictions translate to certain responsibilities for you if you distribute copies of the library or if you modify it.

For example, if you distribute copies of the library, whether gratis or for a fee, you must give the recipients all the rights that we gave you. You must make sure that they, too, receive or can get the source code. If you link other code with the library, you must provide complete object files to the recipients, so that they can relink them with the library after making changes to the library and recompiling it. And you must show them these terms so they know their rights.

We protect your rights with a two-step method: (1) we copyright the library, and (2) we offer you this license, which gives you legal permission to copy, distribute and/or modify the library.

To protect each distributor, we want to make it very clear that there is no warranty for the free library. Also, if the library is modified by someone else and passed on, the recipients should know that what they have is not the original version, so that the original author's reputation will not be affected by problems that might be introduced by others.

Finally, software patents pose a constant threat to the existence of any free program. We wish to make sure that a company cannot effectively restrict the users of a free program by obtaining a restrictive license from a patent holder. Therefore, we insist that any patent license obtained for a version of the library must be consistent with the full freedom of use specified in this license.

Most GNU software, including some libraries, is covered by the ordinary GNU General Public License. This license, the GNU Lesser General Public License, applies to certain designated libraries, and is quite different from the ordinary General Public License. We use this license for certain libraries in order to permit linking those libraries into non-free programs.

When a program is linked with a library, whether statically or using a shared library, the combination of the two is legally speaking a combined work, a derivative of the original library. The ordinary General Public License therefore permits such linking only if the entire combination fits its criteria of freedom. The Lesser General Public License permits more lax criteria for linking other code with the library.

We call this license the "Lesser" General Public License because it

does Less to protect the user's freedom than the ordinary General Public License. It also provides other free software developers Less of an advantage over competing non-free programs. These disadvantages are the reason we use the ordinary General Public License for many libraries. However, the Lesser license provides advantages in certain special circumstances.

For example, on rare occasions, there may be a special need to encourage the widest possible use of a certain library, so that it becomes a de-facto standard. To achieve this, non-free programs must be allowed to use the library. A more frequent case is that a free library does the same job as widely used non-free libraries. In this case, there is little to gain by limiting the free library to free software only, so we use the Lesser General Public License.

In other cases, permission to use a particular library in non-free programs enables a greater number of people to use a large body of free software. For example, permission to use the GNU C Library in non-free programs enables many more people to use the whole GNU operating system, as well as its variant, the GNU/Linux operating system.

Although the Lesser General Public License is Less protective of the users' freedom, it does ensure that the user of a program that is linked with the Library has the freedom and the wherewithal to run that program using a modified version of the Library.

The precise terms and conditions for copying, distribution and modification follow. Pay close attention to the difference between a "work based on the library" and a "work that uses the library". The former contains code derived from the library, whereas the latter must be combined with the library in order to run.

GNU LESSER GENERAL PUBLIC LICENSE TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

0. This License Agreement applies to any software library or other program which contains a notice placed by the copyright holder or other authorized party saying it may be distributed under the terms of this Lesser General Public License (also called "this License"). Each licensee is addressed as "you".

A "library" means a collection of software functions and/or data prepared so as to be conveniently linked with application programs (which use some of those functions and data) to form executables.

The "Library", below, refers to any such software library or work which has been distributed under these terms. A "work based on the Library" means either the Library or any derivative work under copyright law: that is to say, a work containing the Library or a portion of it, either verbatim or with modifications and/or translated straightforwardly into another language. (Hereinafter, translation is included without limitation in the term "modification".)

"Source code" for a work means the preferred form of the work for making modifications to it. For a library, complete source code means all the source code for all modules it contains, plus any associated interface definition files, plus the scripts used to control compilation and installation of the library.

Activities other than copying, distribution and modification are not covered by this License; they are outside its scope. The act of running a program using the Library is not restricted, and output from such a program is covered only if its contents constitute a work based on the Library (independent of the use of the Library in a tool for writing it). Whether that is true depends on what the Library does and what the program that uses the Library does.

1. You may copy and distribute verbatim copies of the Library's complete source code as you receive it, in any medium, provided that you conspicuously and appropriately publish on each copy an appropriate copyright notice and disclaimer of warranty; keep intact all the notices that refer to this License and to the absence of any warranty; and distribute a copy of this License along with the Library.

You may charge a fee for the physical act of transferring a copy, and you may at your option offer warranty protection in exchange for a fee.

2. You may modify your copy or copies of the Library or any portion of it, thus forming a work based on the Library, and copy and distribute such modifications or work under the terms of Section 1 above, provided that you also meet all of these conditions:

- a) The modified work must itself be a software library.
- b) You must cause the files modified to carry prominent notices stating that you changed the files and the date of any change.
- c) You must cause the whole of the work to be licensed at no charge to all third parties under the terms

of this License.

d) If a facility in the modified Library refers to a function or a table of data to be supplied by an application program that uses the facility, other than as an argument passed when the facility is invoked, then you must make a good faith effort to ensure that, in the event an application does not supply such function or table, the facility still operates, and performs whatever part of its purpose remains meaningful.

(For example, a function in a library to compute square roots has a purpose that is entirely well-defined independent of the application. Therefore, Subsection 2d requires that any application-supplied function or table used by this function must be optional: if the application does not supply it, the square root function must still compute square roots.)

These requirements apply to the modified work as a whole. If identifiable sections of that work are not derived from the Library, and can be reasonably considered independent and separate works in themselves, then this License, and its terms, do not apply to those sections when you distribute them as separate works. But when you distribute the same sections as part of a whole which is a work based on the Library, the distribution of the whole must be on the terms of this License, whose permissions for other licensees extend to the entire whole, and thus to each and every part regardless of who wrote it.

Thus, it is not the intent of this section to claim rights or contest your rights to work written entirely by you; rather, the intent is to exercise the right to control the distribution of derivative or collective works based on the Library.

In addition, mere aggregation of another work not based on the Library with the Library (or with a work based on the Library) on a volume of a storage or distribution medium does not bring the other work under the scope of this License.

3. You may opt to apply the terms of the ordinary GNU General Public

License instead of this License to a given copy of the Library. To do this, you must alter all the notices that refer to this License, so that they refer to the ordinary GNU General Public License, version 2, instead of to this License. (If a newer version than version 2 of the ordinary GNU General Public License has appeared, then you can specify that version instead if you wish.) Do not make any other change in these notices.

Once this change is made in a given copy, it is irreversible for that copy, so the ordinary GNU General Public License applies to all subsequent copies and derivative works made from that copy.

This option is useful when you wish to copy part of the code of the Library into a program that is not a library.

4. You may copy and distribute the Library (or a portion or derivative of it, under Section 2) in object code or executable form under the terms of Sections 1 and 2 above provided that you accompany it with the complete corresponding machine-readable source code, which must be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange.

If distribution of object code is made by offering access to copy from a designated place, then offering equivalent access to copy the source code from the same place satisfies the requirement to distribute the source code, even though third parties are not compelled to copy the source along with the object code.

5. A program that contains no derivative of any portion of the Library, but is designed to work with the Library by being compiled or linked with it, is called a "work that uses the Library". Such a work, in isolation, is not a derivative work of the Library, and therefore falls outside the scope of this License.

However, linking a "work that uses the Library" with the Library creates an executable that is a derivative of the Library (because it contains portions of the Library), rather than a "work that uses the library". The executable is therefore covered by this License. Section 6 states terms for distribution of such executables.

When a "work that uses the Library" uses material from a header file that is part of the Library, the object code for the work may be a derivative work of the Library even though the source code is not. Whether this is true is especially significant if the work can be linked without the Library, or if the work is itself a library. The threshold for this to be true is not precisely defined by law.

If such an object file uses only numerical parameters, data structure layouts and accessors, and small macros and small inline functions (ten lines or less in length), then the use of the object file is unrestricted, regardless of whether it is legally a derivative work. (Executables containing this object code plus portions of the Library will still fall under Section 6.)

Otherwise, if the work is a derivative of the Library, you may distribute the object code for the work under the terms of Section 6. Any executables containing that work also fall under Section 6, whether or not they are linked directly with the Library itself.

6. As an exception to the Sections above, you may also combine or link a "work that uses the Library" with the Library to produce a work containing portions of the Library, and distribute that work under terms of your choice, provided that the terms permit modification of the work for the customer's own use and reverse engineering for debugging such modifications.

You must give prominent notice with each copy of the work that the Library is used in it and that the Library and its use are covered by this License. You must supply a copy of this License. If the work during execution displays copyright notices, you must include the copyright notice for the Library among them, as well as a reference directing the user to the copy of this License. Also, you must do one of these things:

a) Accompany the work with the complete corresponding machine-readable source code for the Library including whatever changes were used in the work (which must be distributed under Sections 1 and 2 above); and, if the work is an executable linked with the Library, with the complete machine-readable "work that uses the Library", as object code and/or source code, so that the user can modify the Library and then relink to produce a modified executable containing the modified Library. (It is understood that the user who changes the contents of definitions files in the Library will not necessarily be able to recompile the application to use the modified definitions.)

b) Use a suitable shared library mechanism for linking with the Library. A suitable mechanism is one that (1) uses at run time a copy of the library already present on the user's computer system, rather than copying library functions into the executable, and (2) will operate properly with a modified version of the library, if the user installs one, as long as the modified version is interface-compatible with the version that the work was made with.

c) Accompany the work with a written offer, valid for at least three years, to give the same user the materials specified in Subsection 6a, above, for a charge no more than the cost of performing this distribution.

d) If distribution of the work is made by offering access to copy from a designated place, offer equivalent access to copy the above specified materials from the same place.

e) Verify that the user has already received a copy of these materials or that you have already sent this user a copy.

For an executable, the required form of the "work that uses the Library" must include any data and utility programs needed for reproducing the executable from it. However, as a special exception, the materials to be distributed need not include anything that is normally

distributed (in either source or binary form) with the major components (compiler, kernel, and so on) of the operating system on which the executable runs, unless that component itself accompanies the executable.

It may happen that this requirement contradicts the license restrictions of other proprietary libraries that do not normally accompany the operating system. Such a contradiction means you cannot use both them and the Library together in an executable that you distribute.

7. You may place library facilities that are a work based on the Library side-by-side in a single library together with other library facilities not covered by this License, and distribute such a combined library, provided that the separate distribution of the work based on the Library and of the other library facilities is otherwise permitted, and provided that you do these two things:

a) Accompany the combined library with a copy of the same work based on the Library, uncombined with any other library facilities. This must be distributed under the terms of the Sections above.

b) Give prominent notice with the combined library of the fact that part of it is a work based on the Library, and explaining where to find the accompanying uncombined form of the same work.

8. You may not copy, modify, sublicense, link with, or distribute the Library except as expressly provided under this License. Any attempt otherwise to copy, modify, sublicense, link with, or distribute the Library is void, and will automatically terminate your rights under this License. However, parties who have received copies, or rights, from you under this License will not have their licenses terminated so long as such parties remain in full compliance.

9. You are not required to accept this License, since you have not signed it. However, nothing else grants you permission to modify or distribute the Library or its derivative works. These actions are prohibited by law if you do not accept this License. Therefore, by modifying or distributing the Library (or any work based on the Library), you indicate your acceptance of this License to do so, and all its terms and conditions for copying, distributing or modifying the Library or works based on it.

10. Each time you redistribute the Library (or any work based on the Library), the recipient automatically receives a license from the original licensor to copy, distribute, link with or modify the Library subject to these terms and conditions. You may not impose any further restrictions on the recipients' exercise of the rights granted herein. You are not responsible for enforcing compliance by third parties with this License.

11. If, as a consequence of a court judgment or allegation of patent infringement or for any other reason (not limited to patent issues), conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot distribute so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not distribute the Library at all. For example, if a patent license would not permit royalty-free redistribution of the Library by all those who receive copies directly or indirectly through you, then the only way you could satisfy both it and this License would be to refrain entirely from distribution of the Library.

If any portion of this section is held invalid or unenforceable under any particular circumstance, the balance of the section is intended to apply, and the section as a whole is intended to apply in other circumstances.

It is not the purpose of this section to induce you to infringe any patents or other property right claims or to contest validity of any such claims; this section has the sole purpose of protecting the integrity of the free software distribution system which is implemented by public license practices. Many people have made generous contributions to the wide range of software distributed through that system in reliance on consistent application of that system; it is up to the author/donor to decide if he or she is willing to distribute software through any other system and a licensee cannot

impose that choice.

This section is intended to make thoroughly clear what is believed to be a consequence of the rest of this License.

12. If the distribution and/or use of the Library is restricted in certain countries either by patents or by copyrighted interfaces, the original copyright holder who places the Library under this License may add an explicit geographical distribution limitation excluding those countries, so that distribution is permitted only in or among countries not thus excluded. In such case, this License incorporates the limitation as if written in the body of this License.

13. The Free Software Foundation may publish revised and/or new versions of the Lesser General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Library specifies a version number of this License which applies to it and "any later version", you have the option of following the terms and conditions either of that version or of any later version published by the Free Software Foundation. If the Library does not specify a license version number, you may choose any version ever published by the Free Software Foundation.

14. If you wish to incorporate parts of the Library into other free programs whose distribution conditions are incompatible with these, write to the author to ask for permission. For software which is copyrighted by the Free Software Foundation, write to the Free Software Foundation; we sometimes make exceptions for this. Our decision will be guided by the two goals of preserving the free status of all derivatives of our free software and of promoting the sharing and reuse of software generally.

NO WARRANTY

15. BECAUSE THE LIBRARY IS LICENSED FREE OF CHARGE, THERE IS NO WARRANTY FOR THE LIBRARY, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE LIBRARY "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE LIBRARY IS WITH YOU. SHOULD THE LIBRARY PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

16. IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY AND/OR REDISTRIBUTE THE LIBRARY AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE LIBRARY (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE LIBRARY TO OPERATE WITH ANY OTHER SOFTWARE), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Libraries

If you develop a new library, and you want it to be of the greatest possible use to the public, we recommend making it free software that everyone can redistribute and change. You can do so by permitting redistribution under these terms (or, alternatively, under the terms of the ordinary General Public License).

To apply these terms, attach the following notices to the library. It is safest to attach them to the start of each source file to most effectively convey the exclusion of warranty; and each file should have at least the "copyright" line and a pointer to where the full notice is found.

<one line to give the library's name and a brief idea of what it does.>
Copyright (C) <year> <name of author>

This library is free software; you can redistribute it and/or modify it under the terms of the GNU Lesser General Public License as published by the Free Software Foundation; either version 2.1 of the License, or (at your option) any later version.

This library is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU Lesser General Public License for more details.

You should have received a copy of the GNU Lesser General Public License along with this library; if not, write to the Free Software Foundation, Inc., 51 Franklin St, Fifth Floor, Boston, MA 02110-1301

USA

Also add information on how to contact you by electronic and paper mail.

You should also get your employer (if you work as a programmer) or your school, if any, to sign a "copyright disclaimer" for the library, if necessary. Here is a sample; alter the names:

Yoyodyne, Inc., hereby disclaims all copyright interest in the library `Frob' (a library for tweaking knobs) written by James Random Hacker.

<signature of Ty Coon>, 1 April 1990
Ty Coon, President of Vice

That's all there is to it!

Copyright 1992, 1993, 1994 Henry Spencer. All rights reserved.

This software is not subject to any license of the American Telephone and Telegraph Company or of the Regents of the University of California.

Permission is granted to anyone to use this software for any purpose on any computer system, and to alter it and redistribute it, subject to the following restrictions:

1. The author is not responsible for the consequences of use of this software, no matter how awful, even if they arise from flaws in it.
2. The origin of this software must not be misrepresented, either by explicit claim or by omission. Since few users ever read sources, credits must appear in the documentation.
3. Altered versions must be plainly marked as such, and must not be misrepresented as being the original software. Since few users ever read sources, credits must appear in the documentation.
4. This notice may not be removed or altered.

/*-

* Copyright (c) 1994

* The Regents of the University of California. All rights reserved.

*

* Redistribution and use in source and binary forms, with or without

* modification, are permitted provided that the following conditions

* are met:

* 1. Redistributions of source code must retain the above copyright

* notice, this list of conditions and the following disclaimer.

* 2. Redistributions in binary form must reproduce the above copyright

* notice, this list of conditions and the following disclaimer in the
 * documentation and/or other materials provided with the distribution.
 * 4. Neither the name of the University nor the names of its contributors
 * may be used to endorse or promote products derived from this software
 * without specific prior written permission.
 *
 * THIS SOFTWARE IS PROVIDED BY THE REGENTS AND CONTRIBUTORS ``AS IS" AND
 * ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE
 * IMPLIED WARRANTIES
 * OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE
 * ARE DISCLAIMED. IN NO EVENT SHALL THE REGENTS OR CONTRIBUTORS BE LIABLE
 * FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL
 * DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS
 * OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION)
 * HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT
 * LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY
 * OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF
 * SUCH DAMAGE.
 *
 * @(#)COPYRIGHT 8.1 (Berkeley) 3/16/94
 */
 @ignore
 @c Set file name and title for man page.
 @setfilename gpl
 @settitle GNU General Public License
 @c man begin SEEALSO
 gfdl(7), fsf-funding(7).
 @c man end
 @c man begin COPYRIGHT
 Copyright @copyright{ } 2007 Free Software Foundation, Inc.

Everyone is permitted to copy and distribute verbatim copies of this
 license document, but changing it is not allowed.

@c man end
 @end ignore
 @node Copying
 @c man begin DESCRIPTION
 @unnumbered GNU General Public License
 @center Version 3, 29 June 2007

@c This file is intended to be included in another file.

@display
 Copyright @copyright{ } 2007 Free Software Foundation, Inc. @url{http://fsf.org/}

Everyone is permitted to copy and distribute verbatim copies of this
 license document, but changing it is not allowed.

@end display

@heading Preamble

The GNU General Public License is a free, copyleft license for software and other kinds of works.

The licenses for most software and other practical works are designed to take away your freedom to share and change the works. By contrast, the GNU General Public License is intended to guarantee your freedom to share and change all versions of a program--to make sure it remains free software for all its users. We, the Free Software Foundation, use the GNU General Public License for most of our software; it applies also to any other work released this way by its authors. You can apply it to your programs, too.

When we speak of free software, we are referring to freedom, not price. Our General Public Licenses are designed to make sure that you have the freedom to distribute copies of free software (and charge for them if you wish), that you receive source code or can get it if you want it, that you can change the software or use pieces of it in new free programs, and that you know you can do these things.

To protect your rights, we need to prevent others from denying you these rights or asking you to surrender the rights. Therefore, you have certain responsibilities if you distribute copies of the software, or if you modify it: responsibilities to respect the freedom of others.

For example, if you distribute copies of such a program, whether gratis or for a fee, you must pass on to the recipients the same freedoms that you received. You must make sure that they, too, receive or can get the source code. And you must show them these terms so they know their rights.

Developers that use the GNU GPL protect your rights with two steps: (1) assert copyright on the software, and (2) offer you this License giving you legal permission to copy, distribute and/or modify it.

For the developers' and authors' protection, the GPL clearly explains that there is no warranty for this free software. For both users' and authors' sake, the GPL requires that modified versions be marked as changed, so that their problems will not be attributed erroneously to authors of previous versions.

Some devices are designed to deny users access to install or run modified versions of the software

inside them, although the manufacturer can do so. This is fundamentally incompatible with the aim of protecting users' freedom to change the software. The systematic pattern of such abuse occurs in the area of products for individuals to use, which is precisely where it is most unacceptable. Therefore, we have designed this version of the GPL to prohibit the practice for those products. If such problems arise substantially in other domains, we stand ready to extend this provision to those domains in future versions of the GPL, as needed to protect the freedom of users.

Finally, every program is threatened constantly by software patents. States should not allow patents to restrict development and use of software on general-purpose computers, but in those that do, we wish to avoid the special danger that patents applied to a free program could make it effectively proprietary. To prevent this, the GPL assures that patents cannot be used to render the program non-free.

The precise terms and conditions for copying, distribution and modification follow.

@heading TERMS AND CONDITIONS

@enumerate 0

@item Definitions.

``This License" refers to version 3 of the GNU General Public License.

``Copyright" also means copyright-like laws that apply to other kinds of works, such as semiconductor masks.

``The Program" refers to any copyrightable work licensed under this License. Each licensee is addressed as ``you". ``Licensees" and ``recipients" may be individuals or organizations.

To ``modify" a work means to copy from or adapt all or part of the work in a fashion requiring copyright permission, other than the making of an exact copy. The resulting work is called a ``modified version" of the earlier work or a work ``based on" the earlier work.

A ``covered work" means either the unmodified Program or a work based on the Program.

To ``propagate" a work means to do anything with it that, without permission, would make you directly or secondarily liable for infringement under applicable copyright law, except executing it on a

computer or modifying a private copy. Propagation includes copying, distribution (with or without modification), making available to the public, and in some countries other activities as well.

To "convey" a work means any kind of propagation that enables other parties to make or receive copies. Mere interaction with a user through a computer network, with no transfer of a copy, is not conveying.

An interactive user interface displays "Appropriate Legal Notices" to the extent that it includes a convenient and prominently visible feature that (1) displays an appropriate copyright notice, and (2) tells the user that there is no warranty for the work (except to the extent that warranties are provided), that licensees may convey the work under this License, and how to view a copy of this License. If the interface presents a list of user commands or options, such as a menu, a prominent item in the list meets this criterion.

@item Source Code.

The "source code" for a work means the preferred form of the work for making modifications to it. "Object code" means any non-source form of a work.

A "Standard Interface" means an interface that either is an official standard defined by a recognized standards body, or, in the case of interfaces specified for a particular programming language, one that is widely used among developers working in that language.

The "System Libraries" of an executable work include anything, other than the work as a whole, that (a) is included in the normal form of packaging a Major Component, but which is not part of that Major Component, and (b) serves only to enable use of the work with that Major Component, or to implement a Standard Interface for which an implementation is available to the public in source code form. A "Major Component", in this context, means a major essential component (kernel, window system, and so on) of the specific operating system (if any) on which the executable work runs, or a compiler used to produce the work, or an object code interpreter used to run it.

The "Corresponding Source" for a work in object code form means all the source code needed to generate, install, and (for an executable work) run the object code and to modify the work, including scripts to control those activities. However, it does not include the work's System Libraries, or general-purpose tools or generally available free programs which are used unmodified in performing those activities but

which are not part of the work. For example, Corresponding Source includes interface definition files associated with source files for the work, and the source code for shared libraries and dynamically linked subprograms that the work is specifically designed to require, such as by intimate data communication or control flow between those subprograms and other parts of the work.

The Corresponding Source need not include anything that users can regenerate automatically from other parts of the Corresponding Source.

The Corresponding Source for a work in source code form is that same work.

@item Basic Permissions.

All rights granted under this License are granted for the term of copyright on the Program, and are irrevocable provided the stated conditions are met. This License explicitly affirms your unlimited permission to run the unmodified Program. The output from running a covered work is covered by this License only if the output, given its content, constitutes a covered work. This License acknowledges your rights of fair use or other equivalent, as provided by copyright law.

You may make, run and propagate covered works that you do not convey, without conditions so long as your license otherwise remains in force. You may convey covered works to others for the sole purpose of having them make modifications exclusively for you, or provide you with facilities for running those works, provided that you comply with the terms of this License in conveying all material for which you do not control copyright. Those thus making or running the covered works for you must do so exclusively on your behalf, under your direction and control, on terms that prohibit them from making any copies of your copyrighted material outside their relationship with you.

Conveying under any other circumstances is permitted solely under the conditions stated below. Sublicensing is not allowed; section 10 makes it unnecessary.

@item Protecting Users' Legal Rights From Anti-Circumvention Law.

No covered work shall be deemed part of an effective technological measure under any applicable law fulfilling obligations under article 11 of the WIPO copyright treaty adopted on 20 December 1996, or similar laws prohibiting or restricting circumvention of such measures.

When you convey a covered work, you waive any legal power to forbid circumvention of technological measures to the extent such circumvention is effected by exercising rights under this License with respect to the covered work, and you disclaim any intention to limit operation or modification of the work as a means of enforcing, against the work's users, your or third parties' legal rights to forbid circumvention of technological measures.

@item Conveying Verbatim Copies.

You may convey verbatim copies of the Program's source code as you receive it, in any medium, provided that you conspicuously and appropriately publish on each copy an appropriate copyright notice; keep intact all notices stating that this License and any non-permissive terms added in accord with section 7 apply to the code; keep intact all notices of the absence of any warranty; and give all recipients a copy of this License along with the Program.

You may charge any price or no price for each copy that you convey, and you may offer support or warranty protection for a fee.

@item Conveying Modified Source Versions.

You may convey a work based on the Program, or the modifications to produce it from the Program, in the form of source code under the terms of section 4, provided that you also meet all of these conditions:

@enumerate a

@item

The work must carry prominent notices stating that you modified it, and giving a relevant date.

@item

The work must carry prominent notices stating that it is released under this License and any conditions added under section 7. This requirement modifies the requirement in section 4 to "keep intact all notices".

@item

You must license the entire work, as a whole, under this License to anyone who comes into possession of a copy. This License will therefore apply, along with any applicable section 7 additional terms, to the whole of the work, and all its parts, regardless of how they are packaged. This License gives no permission to license the work in any other way, but it does not invalidate such permission if you have

separately received it.

@item

If the work has interactive user interfaces, each must display

Appropriate

Legal Notices; however, if the Program has interactive interfaces that do not display Appropriate Legal Notices, your work need not make them do so.

@end enumerate

A compilation of a covered work with other separate and independent works, which are not by their nature extensions of the covered work, and which are not combined with it such as to form a larger program, in or on a volume of a storage or distribution medium, is called an "aggregate" if the compilation and its resulting copyright are not used to limit the access or legal rights of the compilation's users beyond what the individual works permit. Inclusion of a covered work in an aggregate does not cause this License to apply to the other parts of the aggregate.

@item Conveying Non-Source Forms.

You may convey a covered work in object code form under the terms of sections 4 and 5, provided that you also convey the machine-readable Corresponding Source under the terms of this License, in one of these ways:

@enumerate

a

@item

Convey the object code in, or embodied in, a physical product (including a physical distribution medium), accompanied by the Corresponding Source fixed on a durable physical medium customarily used for software interchange.

@item

Convey the object code in, or embodied in, a physical product (including a physical distribution medium), accompanied by a written offer, valid for at least three years and valid for as long as you offer spare parts or customer support for that product model, to give anyone who possesses the object code either (1) a copy of the Corresponding Source for all the software in the product that is covered by this License, on a durable physical medium customarily used for software interchange, for a price no more than your reasonable cost of physically performing this conveying of source, or (2) access to copy the Corresponding Source from a network server at no charge.

@item

Convey individual copies of the object code with a copy of the written offer

to provide the Corresponding Source. This alternative is allowed only occasionally and noncommercially, and only if you received the object code with such an offer, in accord with subsection 6b.

@item

Convey the object code by offering access from a designated place (gratis or for a charge), and offer equivalent access to the Corresponding Source in the same way through the same place at no further charge. You need not require recipients to copy the Corresponding Source along with the object code. If the place to copy the object code is a network server, the Corresponding Source may be on a different server (operated by you or a third party) that supports equivalent copying facilities, provided you maintain clear directions next to the object code saying where to find the Corresponding Source. Regardless of what server hosts the Corresponding Source, you remain obligated to ensure that it is available for as long as needed to satisfy these requirements.

@item

Convey the object code using peer-to-peer transmission, provided you inform other peers where the object code and Corresponding Source of the work are being offered to the general public at no charge under subsection 6d.

@end enumerate

A separable portion of the object code, whose source code is excluded from the Corresponding Source as a System Library, need not be included in conveying the object code work.

A "User Product" is either (1) a "consumer product", which means any tangible personal property which is normally used for personal, family, or household purposes, or (2) anything designed or sold for incorporation into a dwelling. In determining whether a product is a consumer product, doubtful cases shall be resolved in favor of coverage. For a particular product received by a particular user, "normally used" refers to a typical or common use of that class of product, regardless of the status of the particular user or of the way in which the particular user actually uses, or expects or is expected to use, the product. A product is a consumer product regardless of whether the product has substantial commercial, industrial or non-consumer uses, unless such uses represent the only significant mode of use of the product.

“Installation Information” for a User Product means any methods, procedures, authorization keys, or other information required to install and execute modified versions of a covered work in that User Product from a modified version of its Corresponding Source. The information must suffice to ensure that the continued functioning of the modified object code is in no case prevented or interfered with solely because modification has been made.

If you convey an object code work under this section in, or with, or specifically for use in, a User Product, and the conveying occurs as part of a transaction in which the right of possession and use of the User Product is transferred to the recipient in perpetuity or for a fixed term (regardless of how the transaction is characterized), the Corresponding Source conveyed under this section must be accompanied by the Installation Information. But this requirement does not apply if neither you nor any third party retains the ability to install modified object code on the User Product (for example, the work has been installed in ROM).

The requirement to provide Installation Information does not include a requirement to continue to provide support service, warranty, or updates for a work that has been modified or installed by the recipient, or for the User Product in which it has been modified or installed. Access to a network may be denied when the modification itself materially and adversely affects the operation of the network or violates the rules and protocols for communication across the network.

Corresponding Source conveyed, and Installation Information provided, in accord with this section must be in a format that is publicly documented (and with an implementation available to the public in source code form), and must require no special password or key for unpacking, reading or copying.

@item Additional Terms.

“Additional permissions” are terms that supplement the terms of this License by making exceptions from one or more of its conditions. Additional permissions that are applicable to the entire Program shall be treated as though they were included in this License, to the extent that they are valid under applicable law. If additional permissions apply only to part of the Program, that part may be used separately under those permissions, but the entire Program remains governed by this License without regard to the additional permissions.

When you convey a copy of a covered work, you may at your option remove any additional permissions from that copy, or from any part of it. (Additional permissions may be written to require their own removal in certain cases when you modify the work.) You may place additional permissions on material, added by you to a covered work, for which you have or can give appropriate copyright permission.

Notwithstanding any other provision of this License, for material you add to a covered work, you may (if authorized by the copyright holders of that material) supplement the terms of this License with terms:

@enumerate a

@item

Disclaiming warranty or limiting liability differently from the terms of sections 15 and 16 of this License; or

@item

Requiring preservation of specified reasonable legal notices or author attributions in that material or in the Appropriate Legal Notices displayed by works containing it; or

@item

Prohibiting misrepresentation of the origin of that material, or requiring that modified versions of such material be marked in reasonable ways as different from the original version; or

@item

Limiting the use for publicity purposes of names of licensors or authors of the material; or

@item

Declining to grant rights under trademark law for use of some trade names, trademarks, or service marks;
or

@item

Requiring indemnification of licensors and authors of that material by anyone who conveys the material (or modified versions of it) with contractual assumptions of liability to the recipient, for any liability that these contractual assumptions directly impose on those licensors and authors.

@end enumerate

All other non-permissive additional terms are considered ``further restrictions'' within the meaning of section 10. If the Program as you received it, or any part of it, contains a notice stating that it is governed by this License along with a term that is a further

restriction, you may remove that term. If a license document contains a further restriction but permits relicensing or conveying under this License, you may add to a covered work material governed by the terms of that license document, provided that the further restriction does not survive such relicensing or conveying.

If you add terms to a covered work in accord with this section, you must place, in the relevant source files, a statement of the additional terms that apply to those files, or a notice indicating where to find the applicable terms.

Additional terms, permissive or non-permissive, may be stated in the form of a separately written license, or stated as exceptions; the above requirements apply either way.

@item Termination.

You may not propagate or modify a covered work except as expressly provided under this License. Any attempt otherwise to propagate or modify it is void, and will automatically terminate your rights under this License (including any patent licenses granted under the third paragraph of section 11).

However, if you cease all violation of this License, then your license from a particular copyright holder is reinstated (a) provisionally, unless and until the copyright holder explicitly and finally terminates your license, and (b) permanently, if the copyright holder fails to notify you of the violation by some reasonable means prior to 60 days after the cessation.

Moreover, your license from a particular copyright holder is reinstated permanently if the copyright holder notifies you of the violation by some reasonable means, this is the first time you have received notice of violation of this License (for any work) from that copyright holder, and you cure the violation prior to 30 days after your receipt of the notice.

Termination of your rights under this section does not terminate the licenses of parties who have received copies or rights from you under this License. If your rights have been terminated and not permanently reinstated, you do not qualify to receive new licenses for the same material under section 10.

@item Acceptance Not Required for Having Copies.

You are not required to accept this License in order to receive or run

a copy of the Program. Ancillary propagation of a covered work occurring solely as a consequence of using peer-to-peer transmission to receive a copy likewise does not require acceptance. However, nothing

other than this License grants you permission to propagate or modify any covered work. These actions infringe copyright if you do not accept this License. Therefore, by modifying or propagating a covered work, you indicate your acceptance of this License to do so.

@item Automatic Licensing of Downstream Recipients.

Each time you convey a covered work, the recipient automatically receives a license from the original licensors, to run, modify and propagate that work, subject to this License. You are not responsible for enforcing compliance by third parties with this License.

An "entity transaction" is a transaction transferring control of an organization, or substantially all assets of one, or subdividing an organization, or merging organizations. If propagation of a covered work results from an entity transaction, each party to that transaction who receives a copy of the work also receives whatever licenses to the work the party's predecessor in interest had or could give

under the previous paragraph, plus a right to possession of the Corresponding Source of the work from the predecessor in interest, if the predecessor has it or can get it with reasonable efforts.

You may not impose any further restrictions on the exercise of the rights granted or affirmed under this License. For example, you may not impose a license fee, royalty, or other charge for exercise of rights granted under this License, and you may not initiate litigation (including a cross-claim or counterclaim in a lawsuit) alleging that any patent claim is infringed by making, using, selling, offering for sale, or importing the Program or any portion of it.

@item Patents.

A "contributor" is a copyright holder who authorizes use under this License of the Program or a work on which the Program is based. The work thus licensed is called the contributor's "contributor version".

A contributor's "essential patent claims" are all patent claims owned or controlled by the contributor, whether already acquired or hereafter acquired, that would be infringed by some manner, permitted by this License, of making, using, or selling its contributor version, but do not include claims that would be infringed only as a consequence of further modification of the contributor version. For

purposes of this definition, ``control" includes the right to grant patent sublicenses in a manner consistent with the requirements of this License.

Each contributor grants you a non-exclusive, worldwide, royalty-free patent license under the contributor's essential patent claims, to make, use, sell, offer for sale, import and otherwise run, modify and propagate the contents of its contributor version.

In the following three paragraphs, a ``patent license" is any express agreement or commitment, however denominated, not to enforce a patent (such as an express permission to practice a patent or covenant not to sue for patent infringement). To ``grant" such a patent license to a party means to make such an agreement or commitment not to enforce a patent against the party.

If you convey a covered work, knowingly relying on a patent license, and the Corresponding Source of the work is not available for anyone to copy, free of charge and under the terms of this License, through a publicly available network server or other readily accessible means, then you must either (1) cause the Corresponding Source to be so available, or (2) arrange to deprive yourself of the benefit of the patent license for this particular work, or (3) arrange, in a manner consistent with the requirements of this License, to extend the patent license to downstream recipients. ``Knowingly relying" means you have actual knowledge that, but for the patent license, your conveying the covered work in a country, or your recipient's use of the covered work in a country, would infringe one or more identifiable patents in that country that you have reason to believe are valid.

If, pursuant to or in connection with a single transaction or arrangement, you convey, or propagate by procuring conveyance of, a covered work, and grant a patent license to some of the parties receiving the covered work authorizing them to use, propagate, modify or convey a specific copy of the covered work, then the patent license you grant is automatically extended to all recipients of the covered work and works based on it.

A patent license is ``discriminatory" if it does not include within the scope of its coverage, prohibits the exercise of, or is conditioned on the non-exercise of one or more of the rights that are specifically granted under this License. You may not convey a covered work if you are a party to an arrangement with a third party that is in the business of distributing software, under which you make payment to the third party based on the extent of your activity of conveying the work, and under which the third party grants, to any of the parties

who would receive the covered work from you, a discriminatory patent license (a) in connection with copies of the covered work conveyed by you (or copies made from those copies), or (b) primarily for and in connection with specific products or compilations that contain the covered work, unless you entered into that arrangement, or that patent license was granted, prior to 28 March 2007.

Nothing in this License shall be construed as excluding or limiting any implied license or other defenses to infringement that may otherwise be available to you under applicable patent law.

@item No Surrender of Others' Freedom.

If conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot convey a covered work so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not convey it at all. For example, if you agree to terms that obligate you to collect a royalty for further conveying from those to whom you convey the Program, the only way you could satisfy both those terms and this License would be to refrain entirely from conveying the Program.

@item Use with the GNU Affero General Public License.

Notwithstanding any other provision of this License, you have permission to link or combine any covered work with a work licensed under version 3 of the GNU Affero General Public License into a single combined work, and to convey the resulting work. The terms of this License will continue to apply to the part which is the covered work, but the special requirements of the GNU Affero General Public License, section 13, concerning interaction through a network will apply to the combination as such.

@item Revised Versions of this License.

The Free Software Foundation may publish revised and/or new versions of the GNU General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Program specifies that a certain numbered version of the GNU General Public License ``or any later version" applies to it, you have the option of

following the terms and conditions either of that numbered version or of any later version published by the Free Software Foundation. If the Program does not specify a version number of the GNU General Public License, you may choose any version ever published by the Free Software Foundation.

If the Program specifies that a proxy can decide which future versions of the GNU General Public License can be used, that proxy's public statement of acceptance of a version permanently authorizes you to choose that version for the Program.

Later license versions may give you additional or different permissions. However, no additional obligations are imposed on any author or copyright holder as a result of your choosing to follow a later version.

@item Disclaimer of Warranty.

THERE IS NO WARRANTY FOR THE PROGRAM, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE PROGRAM ``AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE PROGRAM IS WITH YOU. SHOULD THE PROGRAM PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

@item Limitation of Liability.

IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MODIFIES AND/OR CONVEYS THE PROGRAM AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE PROGRAM (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE PROGRAM TO OPERATE WITH ANY OTHER PROGRAMS), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

@item Interpretation of Sections 15 and 16.

If the disclaimer of warranty and limitation of liability provided above cannot be given local legal effect according to their terms, reviewing courts shall apply local law that most closely approximates an absolute waiver of all civil liability in connection with the

Program, unless a warranty or assumption of liability accompanies a copy of the Program in return for a fee.

@end enumerate

@heading END OF TERMS AND CONDITIONS

@heading How to Apply These Terms to Your New Programs

If you develop a new program, and you want it to be of the greatest possible use to the public, the best way to achieve this is to make it free software which everyone can redistribute and change under these terms.

To

do so, attach the following notices to the program. It is safest to attach them to the start of each source file to most effectively state the exclusion of warranty; and each file should have at least the ``copyright" line and a pointer to where the full notice is found.

@smallexample

@var{one line to give the program's name and a brief idea of what it does.}

Copyright (C) @var{year} @var{name of author}

This program is free software: you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation, either version 3 of the License, or (at your option) any later version.

This program is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details.

You should have received a copy of the GNU General Public License along with this program. If

not, see @url{<http://www.gnu.org/licenses/>}.

@end smallexample

Also add information on how to contact you by electronic and paper mail.

If the program does terminal interaction, make it output a short notice like this when it starts in an interactive mode:

@smallexample

@var{program} Copyright (C) @var{year} @var{name of author}

This program comes with ABSOLUTELY NO WARRANTY; for details type @samp{show w}.

This is free software, and you are welcome to redistribute it

under certain conditions; type @samp{show c} for details.

@end smallexample

The hypothetical commands @samp{show w} and @samp{show c} should show the appropriate parts of the General Public License. Of course, your program's commands might be different; for a GUI interface, you would use an ``about box".

You should also get your employer (if you work as a programmer) or school, if any, to sign a ``copyright disclaimer" for the program, if necessary.

For more information on this, and how to apply and follow the GNU GPL, see

@url{http://www.gnu.org/licenses/}.

The GNU General Public License does not permit incorporating your program into proprietary programs. If your program is a subroutine library, you may consider it more useful to permit linking proprietary applications with the library. If this is what you want to do, use the GNU Lesser General Public License instead of this License. But first, please read @url{http://www.gnu.org/philosophy/why-not-lgpl.html}.

@c man end

GNU LESSER GENERAL PUBLIC LICENSE

Version 2.1, February 1999

Copyright (C) 1991, 1999 Free Software Foundation, Inc.

51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA

Everyone is permitted to copy and distribute verbatim copies of this license document, but changing it is not allowed.

[This is the first released version of the Lesser GPL. It also counts as the successor of the GNU Library Public License, version 2, hence the version number 2.1.]

Preamble

The licenses for most software are designed to take away your freedom to share and change it. By contrast, the GNU General Public Licenses are intended to guarantee your freedom to share and change free software--to make sure the software is free for all its users.

This license, the Lesser General Public License, applies to some specially designated software packages--typically libraries--of the Free Software Foundation and other authors who decide to use it. You can use it too, but we

suggest you first think carefully about whether this license or the ordinary General Public License is the better strategy to use in any particular case, based on the explanations below.

When we speak of free software, we are referring to freedom of use, not price. Our General Public Licenses are designed to make sure that you have the freedom to distribute copies of free software (and charge for this service if you wish); that you receive source code or can get it if you want it; that you can change the software and use pieces of it in new free programs; and that you are informed that you can do these things.

To protect your rights, we need to make restrictions that forbid distributors to deny you these rights or to ask you to surrender these rights. These restrictions translate to certain responsibilities for you if you distribute copies of the library or if you modify it.

For example, if you distribute copies of the library, whether gratis or for a fee, you must give the recipients all the rights that we gave you. You must make sure that they, too, receive or can get the source code. If you link other code with the library, you must provide complete object files to the recipients, so that they can relink them with the library after making changes to the library and recompiling it. And you must show them these terms so they know their rights.

We protect your rights with a two-step method: (1) we copyright the library, and (2) we offer you this license, which gives you legal permission to copy, distribute and/or modify the library.

To protect each distributor, we want to make it very clear that there is no warranty for the free library. Also, if the library is modified by someone else and passed on, the recipients should know that what they have is not the original version, so that the original author's reputation will not be affected by problems that might be introduced by others.

Finally, software patents pose a constant threat to the existence of any free program. We wish to make sure that a company cannot effectively restrict the users of a free program by obtaining a restrictive license from a patent holder. Therefore, we insist that any patent license obtained for a version of the library must be consistent with the full freedom of use specified in this license.

Most GNU software, including some libraries, is covered by the ordinary GNU General Public License. This license, the GNU Lesser General Public License, applies to certain designated libraries, and is quite different from the ordinary General Public License. We use this license for certain libraries in order to permit linking those libraries into non-free programs.

When a program is linked with a library, whether statically or using a shared library, the combination of the two is legally speaking a combined work, a derivative of the original library. The ordinary General Public License therefore permits such linking only if the entire combination fits its criteria of freedom. The Lesser General Public License permits more lax criteria for linking other code with the library.

We call this license the "Lesser" General Public License because it does Less to protect the user's freedom than the ordinary General Public License. It also provides other free software developers Less of an advantage over competing non-free programs. These disadvantages are the reason we use the ordinary General Public License for many libraries. However, the Lesser license provides advantages in certain special circumstances.

For example, on rare occasions, there may be a special need to encourage the widest possible use of a certain library, so that it becomes a de-facto standard. To achieve this, non-free programs must be allowed to use the library. A more frequent case is that a free library does the same job as widely used non-free libraries. In this case, there is little to gain by limiting the free library to free software only, so we use the Lesser General Public License.

In other cases, permission to use a particular library in non-free programs enables a greater number of people to use a large body of free software. For example, permission to use the GNU C Library in non-free programs enables many more people to use the whole GNU operating system, as well as its variant, the GNU/Linux operating system.

Although the Lesser General Public License is Less protective of the users' freedom, it does ensure that the user of a program that is linked with the Library has the freedom and the wherewithal to run that program using a modified version of the Library.

The precise terms and conditions for copying, distribution and modification follow. Pay close attention to the difference between a "work based on the library" and a "work that uses the library". The former contains code derived from the library, whereas the latter must be combined with the library in order to run.

**GNU LESSER GENERAL PUBLIC LICENSE
TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION**

0. This License Agreement applies to any software library or other

program which contains a notice placed by the copyright holder or other authorized party saying it may be distributed under the terms of this Lesser General Public License (also called "this License"). Each licensee is addressed as "you".

A "library" means a collection of software functions and/or data prepared so as to be conveniently linked with application programs (which use some of those functions and data) to form executables.

The "Library", below, refers to any such software library or work which has been distributed under these terms. A "work based on the Library" means either the Library or any derivative work under copyright law: that is to say, a work containing the Library or a portion of it, either verbatim or with modifications and/or translated straightforwardly into another language. (Hereinafter, translation is included without limitation in the term "modification".)

"Source code" for a work means the preferred form of the work for making modifications to it. For a library, complete source code means all the source code for all modules it contains, plus any associated interface definition files, plus the scripts used to control compilation and installation of the library.

Activities other than copying, distribution and modification are not covered by this License; they are outside its scope. The act of running a program using the Library is not restricted, and output from such a program is covered only if its contents constitute a work based on the Library (independent of the use of the Library in a tool for writing it). Whether that is true depends on what the Library does and what the program that uses the Library does.

1. You may copy and distribute verbatim copies of the Library's complete source code as you receive it, in any medium, provided that you conspicuously and appropriately publish on each copy an appropriate copyright notice and disclaimer of warranty; keep intact all the notices that refer to this License and to the absence of any warranty; and distribute a copy of this License along with the Library.

You may charge a fee for the physical act of transferring a copy, and you may at your option offer warranty protection in exchange for a fee.

2. You may modify your copy or copies of the Library or any portion of it, thus forming a work based on the Library, and copy and distribute such modifications or work under the terms of Section 1

above, provided that you also meet all of these conditions:

- a) The modified work must itself be a software library.
- b) You must cause the files modified to carry prominent notices stating that you changed the files and the date of any change.
- c) You must cause the whole of the work to be licensed at no charge to all third parties under the terms of this License.

d) If a facility in the modified Library refers to a function or a table of data to be supplied by an application program that uses the facility, other than as an argument passed when the facility is invoked, then you must make a good faith effort to ensure that, in the event an application does not supply such function or table, the facility still operates, and performs whatever part of its purpose remains meaningful.

(For example, a function in a library to compute square roots has a purpose that is entirely well-defined independent of the application. Therefore, Subsection 2d requires that any application-supplied function or table used by this function must be optional: if the application does not supply it, the square root function must still compute square roots.)

These requirements apply to the modified work as a whole. If identifiable sections of that work are not derived from the Library, and can be reasonably considered independent and separate works in themselves,

then this License, and its terms, do not apply to those sections when you distribute them as separate works. But when you distribute the same sections as part of a whole which is a work based on the Library, the distribution of the whole must be on the terms of this License, whose permissions for other licensees extend to the entire whole, and thus to each and every part regardless of who wrote it.

Thus, it is not the intent of this section to claim rights or contest your rights to work written entirely by you; rather, the intent is to exercise the right to control the distribution of derivative or collective works based on the Library.

In addition, mere aggregation of another work not based on the Library with the Library (or with a work based on the Library) on a volume of a storage or distribution medium does not bring the other work under the scope of this License.

3. You may opt to apply the terms of the ordinary GNU General Public License instead of this License to a given copy of the Library. To do this, you must alter all the notices that refer to this License, so that they refer to the ordinary GNU General Public License, version 2, instead of to this License. (If a newer version than version 2 of the ordinary GNU General Public License has appeared, then you can specify that version instead if you wish.) Do not make any other change in these notices.

Once this change is made in a given copy, it is irreversible for that copy, so the ordinary GNU General Public License applies to all subsequent copies and derivative works made from that copy.

This option is useful when you wish to copy part of the code of the Library into a program that is not a library.

4. You may copy and distribute the Library (or a portion or derivative of it, under Section 2) in object code or executable form under the terms of Sections 1 and 2 above provided that you accompany it with the complete corresponding machine-readable source code, which must be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange.

If distribution of object code is made by offering access to copy from a designated place, then offering equivalent access to copy the source code from the same place satisfies the requirement to distribute the source code, even though third parties are not compelled to copy the source along with the object code.

5. A program that contains no derivative of any portion of the Library, but is designed to work with the Library by being compiled or linked with it, is called a "work that uses the Library". Such a work, in isolation, is not a derivative work of the Library, and therefore falls outside the scope of this License.

However, linking a "work that uses the Library" with the Library creates an executable that is a derivative of the Library (because it contains portions of the Library), rather than a "work that uses the library". The executable is therefore covered by this License.

Section 6 states terms for distribution of such executables.

When a "work that uses the Library" uses material from a header file that is part of the Library, the object code for the work may be a derivative work of the Library even though the source code is not. Whether this is true is especially significant if the work can be

linked without the Library, or if the work is itself a library. The threshold for this to be true is not precisely defined by law.

If such an object file uses only numerical parameters, data structure layouts and accessors, and small macros and small inline functions (ten lines or less in length), then the use of the object file is unrestricted, regardless of whether it is legally a derivative work. (Executables containing this object code plus portions of the Library will still fall under Section 6.)

Otherwise, if the work is a derivative of the Library, you may distribute the object code for the work under the terms of Section 6.

Any

executables containing that work also fall under Section 6, whether or not they are linked directly with the Library itself.

6. As an exception to the Sections above, you may also combine or link a "work that uses the Library" with the Library to produce a work containing portions of the Library, and distribute that work under terms of your choice, provided that the terms permit modification of the work for the customer's own use and reverse engineering for debugging such modifications.

You must give prominent notice with each copy of the work that the Library is used in it and that the Library and its use are covered by this License. You must supply a copy of this License. If the work during execution displays copyright notices, you must include the copyright notice for the Library among them, as well as a reference directing the user to the copy of this License. Also, you must do one of these things:

a) Accompany the work with the complete corresponding machine-readable source code for the Library including whatever changes were used in the work (which must be distributed under Sections 1 and 2 above); and, if the work is an executable linked with the Library, with the complete machine-readable "work that uses the Library", as object code and/or source code, so that the user can modify the Library and then relink to produce a modified executable containing the modified Library. (It is understood that the user who changes the contents of definitions files in the Library will not necessarily be able to recompile the application to use the modified definitions.)

b) Use a suitable shared library mechanism for linking with the Library. A suitable mechanism is one that (1) uses at run time a copy of the library already present on the user's computer system, rather than copying library functions into the executable, and (2)

will operate properly with a modified version of the library, if the user installs one, as long as the modified version is interface-compatible with the version that the work was made with.

c) Accompany the work with a written offer, valid for at least three years, to give the same user the materials specified in Subsection 6a, above, for a charge no more than the cost of performing this distribution.

d) If distribution of the work is made by offering access to copy from a designated place, offer equivalent access to copy the above specified materials from the same place.

e) Verify that the user has already received a copy of these materials or that you have already sent this user a copy.

For an executable, the required form of the "work that uses the Library" must include any data and utility programs needed for reproducing the executable from it. However, as a special exception, the materials to be distributed need not include anything that is normally distributed (in either source or binary form) with the major components (compiler, kernel, and so on) of the operating system on which the executable runs, unless that component itself accompanies the executable.

It may happen that this requirement contradicts the license restrictions of other proprietary libraries that do not normally accompany the operating system. Such a contradiction means you cannot use both them and the Library together in an executable that you distribute.

7. You may place library facilities that are a work based on the Library side-by-side in a single library together with other library facilities not covered by this License, and distribute such a combined library, provided that the separate distribution of the work based on the Library and of the other library facilities is otherwise permitted, and provided that you do these two things:

a) Accompany the combined library with a copy of the same work based on the Library, uncombined with any other library facilities. This must be distributed under the terms of the Sections above.

b) Give prominent notice with the combined library of the fact that part of it is a work based on the Library, and explaining

where to find the accompanying uncombined form of the same work.

8. You may not copy, modify, sublicense, link with, or distribute the Library except as expressly provided under this License. Any attempt otherwise to copy, modify, sublicense, link with, or distribute the Library is void, and will automatically terminate your rights under this License. However, parties who have received copies, or rights, from you under this License will not have their licenses terminated so long as such parties remain in full compliance.

9. You are not required to accept this License, since you have not signed it. However, nothing else grants you permission to modify or distribute the Library or its derivative works. These actions are prohibited by law if you do not accept this License. Therefore, by modifying or distributing the Library (or any work based on the Library), you indicate your acceptance of this License to do so, and all its terms and conditions for copying, distributing or modifying the Library or works based on it.

10. Each time you redistribute the Library (or any work based on the Library), the recipient automatically receives a license from the original licensor to copy, distribute, link with or modify the Library subject to these terms and conditions. You may not impose any further restrictions on the recipients' exercise of the rights granted herein. You are not responsible for enforcing compliance by third parties with this License.

11. If, as a consequence of a court judgment or allegation of patent infringement or for any other reason (not limited to patent issues), conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot distribute so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not distribute the Library at all. For example, if a patent license would not permit royalty-free redistribution of the Library by all those who receive copies directly or indirectly through you, then the only way you could satisfy both it and this License would be to refrain entirely from distribution of the Library.

If any portion of this section is held invalid or unenforceable under any particular circumstance, the balance of the section is intended to apply, and the section as a whole is intended to apply in other circumstances.

It is not the purpose of this section to induce you to infringe any patents or other property right claims or to contest validity of any

such claims; this section has the sole purpose of protecting the integrity of the free software distribution system which is implemented by public license practices. Many people have made generous contributions to the wide range of software distributed through that system in reliance on consistent application of that system; it is up to the author/donor to decide if he or she is willing to distribute software through any other system and a licensee cannot impose that choice.

This section is intended to make thoroughly clear what is believed to be a consequence of the rest of this License.

12. If the distribution and/or use of the Library is restricted in certain countries either by patents or by copyrighted interfaces, the original copyright holder who places the Library under this License may add an explicit geographical distribution limitation excluding those countries, so that distribution is permitted only in or among countries not thus excluded. In such case, this License incorporates the limitation as if written in the body of this License.

13. The Free Software Foundation may publish revised and/or new versions of the Lesser General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Library specifies a version number of this License which applies to it and "any later version", you have the option of following the terms and conditions either of that version or of any later version published by the Free Software Foundation. If the Library does not specify a license version number, you may choose any version ever published by the Free Software Foundation.

14. If you wish to incorporate parts of the Library into other free programs whose distribution conditions are incompatible with these, write to the author to ask for permission. For software which is copyrighted by the Free Software Foundation, write to the Free Software Foundation; we sometimes make exceptions for this. Our decision will be guided by the two goals of preserving the free status of all derivatives of our free software and of promoting the sharing and reuse of software generally.

NO WARRANTY

15. BECAUSE THE LIBRARY IS LICENSED FREE OF CHARGE, THERE IS NO

WARRANTY FOR THE LIBRARY, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE LIBRARY "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE LIBRARY IS WITH YOU. SHOULD THE LIBRARY PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

16. IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY AND/OR REDISTRIBUTE THE LIBRARY AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL

DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE LIBRARY (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE LIBRARY TO OPERATE WITH ANY OTHER SOFTWARE), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Libraries

If you develop a new library, and you want it to be of the greatest possible use to the public, we recommend making it free software that everyone can redistribute and change. You can do so by permitting redistribution under these terms (or, alternatively, under the terms of the ordinary General Public License).

To apply these terms, attach the following notices to the library. It is safest to attach them to the start of each source file to most effectively convey the exclusion of warranty; and each file should have at least the "copyright" line and a pointer to where the full notice is found.

<one line to give the library's name and a brief idea of what it does.>
Copyright (C) <year> <name of author>

This library is free software; you can redistribute it and/or modify it under the terms of the GNU Lesser General Public License as published by the Free Software Foundation; either version 2.1 of the License, or (at your option) any later version.

This library is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU

Lesser General Public License for more details.

You should have received a copy of the GNU Lesser General Public License along with this library; if not, write to the Free Software Foundation, Inc., 51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA

Also add information on how to contact you by electronic and paper mail.

You

should also get your employer (if you work as a programmer) or your school, if any, to sign a "copyright disclaimer" for the library, if necessary. Here is a sample; alter the names:

Yoyodyne, Inc., hereby disclaims all copyright interest in the library `Frob' (a library for tweaking knobs) written by James Random Hacker.

<signature of Ty Coon>, 1 April 1990
Ty Coon, President of Vice

That's all there is to it!
Boost Software License - Version 1.0 - August 17th, 2003

Permission is hereby granted, free of charge, to any person or organization obtaining a copy of the software and accompanying documentation covered by this license (the "Software") to use, reproduce, display, distribute, execute, and transmit the Software, and to prepare derivative works of the Software, and to permit third-parties to whom the Software is furnished to do so, all subject to the following:

The copyright notices in the Software and this entire statement, including the above license grant, this restriction and the following disclaimer, must be included in all copies of the Software, in whole or in part, and all derivative works of the Software, unless such copies or derivative works are solely in the form of machine-executable object code generated by a source language processor.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS

FOR A PARTICULAR PURPOSE, TITLE AND NON-INFRINGEMENT. IN NO EVENT SHALL THE COPYRIGHT HOLDERS OR ANYONE DISTRIBUTING THE SOFTWARE BE LIABLE FOR ANY DAMAGES OR OTHER LIABILITY, WHETHER IN CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

GCC RUNTIME LIBRARY EXCEPTION

Version 3.1, 31 March 2009

Copyright (C) 2009 Free Software Foundation, Inc. <<http://fsf.org/>>

Everyone is permitted to copy and distribute verbatim copies of this license document, but changing it is not allowed.

This GCC Runtime Library Exception ("Exception") is an additional permission under section 7 of the GNU General Public License, version 3 ("GPLv3"). It applies to a given file (the "Runtime Library") that bears a notice placed by the copyright holder of the file stating that the file is governed by GPLv3 along with this Exception.

When you use GCC to compile a program, GCC may combine portions of certain GCC header files and runtime libraries with the compiled program. The purpose of this Exception is to allow compilation of non-GPL (including proprietary) programs to use, in this way, the header files and runtime libraries covered by this Exception.

0. Definitions.

A file is an "Independent Module" if it either requires the Runtime Library for execution after a Compilation Process, or makes use of an interface provided by the Runtime Library, but is not otherwise based on the Runtime Library.

"GCC" means a version of the GNU Compiler Collection, with or without modifications, governed by version 3 (or a specified later version) of the GNU General Public License (GPL) with the option of using any subsequent versions published by the FSF.

"GPL-compatible Software" is software whose conditions of propagation, modification and use would permit combination with GCC in accord with the license of GCC.

"Target Code" refers to output from any compiler for a real or virtual target processor architecture, in executable form or suitable for input to an assembler, loader, linker and/or execution phase. Notwithstanding that, Target Code does not include data in any format that is used as a compiler intermediate representation, or used for producing a compiler intermediate representation.

The "Compilation Process" transforms code entirely represented in non-intermediate languages designed for human-written code, and/or in Java Virtual Machine byte code, into Target Code. Thus, for example, use of source code generators and preprocessors need not be considered part of the Compilation Process, since the Compilation Process can be understood as starting with the output of the generators or

preprocessors.

A Compilation Process is "Eligible" if it is done using GCC, alone or with other GPL-compatible software, or if it is done without using any work based on GCC. For example, using non-GPL-compatible Software to optimize any GCC intermediate representations would not qualify as an Eligible Compilation Process.

1. Grant of Additional Permission.

You have permission to propagate a work of Target Code formed by combining the Runtime Library with Independent Modules, even if such propagation would otherwise violate the terms of GPLv3, provided that all Target Code was generated by Eligible Compilation Processes. You may

then convey such a combination under terms of your choice, consistent with the licensing of the Independent Modules.

2. No Weakening of GCC Copyleft.

The availability of this Exception does not imply any general presumption that third-party software is unaffected by the copyleft requirements of the license of GCC.

libffi - Copyright (c) 1996-2014 Anthony Green, Red Hat, Inc and others.

See source files for details.

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

DRuntime: Runtime Library for the D Programming Language

=====

Permission is hereby granted, free of charge, to any person or organization obtaining a copy of the software and accompanying documentation covered by this license (the "Software") to use, reproduce, display, distribute, execute, and transmit the Software, and to prepare derivative works of the Software, and to permit third-parties to whom the Software is furnished to do so, all subject to the following:

The copyright notices in the Software and this entire statement, including the above license grant, this restriction and the following disclaimer, must be included in all copies of the Software, in whole or in part, and all derivative works of the Software, unless such copies or derivative works are solely in the form of machine-executable object code generated by a source language processor.

THE SOFTWARE IS PROVIDED

"AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, TITLE AND NON-INFRINGEMENT. IN NO EVENT SHALL THE COPYRIGHT HOLDERS OR ANYONE DISTRIBUTING THE SOFTWARE BE LIABLE FOR ANY DAMAGES OR OTHER LIABILITY, WHETHER IN CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

The libgloss subdirectory is a collection of software from several sources.

Each file may have its own copyright/license that is embedded in the source file. Unless otherwise noted in the body of the source file(s), the following copyright notices will apply to the contents of the libgloss subdirectory:

(1) Red Hat Incorporated

Copyright (c) 1994-2009 Red Hat, Inc. All rights reserved.

This copyrighted material is made available to anyone wishing to use, modify, copy, or redistribute it subject to the terms and conditions of the BSD License. This program is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY expressed or implied, including the implied warranties of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. A copy of this license is available at <http://www.opensource.org/licenses>. Any Red Hat trademarks that are incorporated in the source code or documentation are not subject to the BSD License and may only be used or replicated with the express permission of Red Hat, Inc.

(2) University of California, Berkeley

Copyright (c) 1981-2000 The Regents of the University of California.

All rights reserved.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

- * Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.
- * Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.
- * Neither the name of the University nor the names of its contributors may be used to endorse or promote products derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED.

IN NO EVENT SHALL THE COPYRIGHT OWNER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

(3) DJ Delorie

Copyright (C) 1993 DJ Delorie
All rights reserved.

Redistribution, modification, and use in source and binary forms is permitted provided that the above copyright notice and following paragraph are duplicated in all such forms.

This file is distributed WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.

(4) (formerly GPL for fr30)

The GPL is no longer applicable to the fr30 platform. The piece of code (syscalls.c) referencing the GPL has been officially relicensed.

(5) Advanced Micro Devices

Copyright 1989, 1990 Advanced Micro Devices, Inc.

This software is the property of Advanced Micro Devices, Inc (AMD) which specifically grants the user the right to modify, use and distribute this software provided this notice is not removed or altered. All other rights are reserved by AMD.

AMD MAKES NO WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, WITH REGARD TO THIS SOFTWARE. IN NO EVENT SHALL AMD BE LIABLE FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES IN CONNECTION WITH OR ARISING FROM THE FURNISHING, PERFORMANCE, OR USE OF THIS SOFTWARE.

So that all may benefit from your experience, please report any problems or suggestions about this software to the 29K Technical Support Center at 800-29-29-AMD (800-292-9263) in the USA, or 0800-89-1131 in the UK, or 0031-11-1129 in Japan, toll free. The direct dial number is 512-462-4118.

Advanced Micro Devices, Inc.
29K Support Products
Mail Stop 573
5900 E. Ben White Blvd.
Austin, TX 78741
800-292-9263

(6) - Analog Devices, Inc. (bfin-* targets)

Copyright (C) 2006, 2008, 2009, 2011, 2012 Analog Devices, Inc.

The authors hereby grant permission to use, copy, modify, distribute, and license this software and its documentation for any purpose, provided that existing copyright notices are retained in all copies and that this notice is included verbatim in any distributions. No written agreement, license, or royalty fee is required for any of the authorized uses. Modifications to this software may be copyrighted by their authors and need not follow the licensing terms described here, provided that the new terms are clearly indicated on the first page of each file where they apply.

(7) University of Utah and the Computer Systems Laboratory (CSL)

[applies only to hppa*-*-pro* targets]

Copyright (c) 1990,1994

The University of Utah and
the Computer Systems Laboratory (CSL). All rights reserved.

Permission to use, copy, modify and distribute this software is hereby granted provided that (1) source code retains these copyright, permission,

and disclaimer notices, and (2) redistributions including binaries reproduce the notices in supporting documentation, and (3) all advertising materials mentioning features or use of this software display the following acknowledgement: ``This product includes software developed by the Computer Systems Laboratory at the University of Utah."

THE UNIVERSITY OF UTAH AND CSL ALLOW FREE USE OF THIS SOFTWARE IN ITS "AS IS" CONDITION. THE UNIVERSITY OF UTAH AND CSL DISCLAIM ANY LIABILITY OF ANY KIND FOR ANY DAMAGES WHATSOEVER RESULTING FROM THE USE OF THIS SOFTWARE.

CSL requests users of this software to return to csl-dist@cs.utah.edu any improvements that they make and grant CSL redistribution rights.

(8) Sun Microsystems

Copyright (C) 1993 by Sun Microsystems,
Inc. All rights reserved.

Developed at SunPro, a Sun Microsystems, Inc. business.
Permission to use, copy, modify, and distribute this software is freely granted, provided that this notice is preserved.

(9) Hewlett Packard

(c) Copyright 1986 HEWLETT-PACKARD COMPANY

To anyone who acknowledges that this file is provided "AS IS" without any express or implied warranty:

permission to use, copy, modify, and distribute this file for any purpose is hereby granted without fee, provided that the above copyright notice and this notice appears in all copies, and that the name of Hewlett-Packard Company not be used in advertising or publicity pertaining to distribution of the software without specific, written prior permission. Hewlett-Packard Company makes no representations about the suitability of this software for any purpose.

(10) Hans-Peter Nilsson

Copyright (C) 2001 Hans-Peter Nilsson

Permission to use, copy, modify, and distribute this software is freely granted, provided that the above copyright notice, this notice and the following disclaimer are preserved with no changes.

THIS SOFTWARE IS PROVIDED ``AS IS" AND WITHOUT ANY EXPRESS OR

IMPLIED WARRANTIES, INCLUDING, WITHOUT LIMITATION, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE.

(11) IBM Corp. spu processor (only spu-* targets)

(C) Copyright IBM Corp. 2005, 2006

All rights reserved.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

* Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.

* Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.

* Neither the name of IBM nor the names of its contributors may be used to endorse or promote products derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

(12) Jon Beniston (only lm32-* targets)

Contributed by Jon Beniston <jon@beniston.com>

Redistribution and use in source and binary forms, with or without modification, are

permitted provided that the following conditions are met:

1. Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.
2. Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.

THIS SOFTWARE IS PROVIDED BY THE AUTHOR AND CONTRIBUTORS ``AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE AUTHOR OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

(13) - Xilinx, Inc. (microblaze-* and powerpc-* targets)

Copyright (c) 2004, 2009 Xilinx, Inc. All rights reserved.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

1. Redistributions source code must retain the above copyright notice, this list of conditions and the following disclaimer.
2. Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.
3. Neither the name of Xilinx nor the names of its contributors may be used to endorse or promote products derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDER AND CONTRIBUTORS "AS IS"

AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT HOLDER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

(14) - National Semiconductor Corporation

Copyright (c) 2004 National Semiconductor Corporation

The authors hereby grant permission to use, copy, modify, distribute, and license this software and its documentation for any purpose, provided that existing copyright notices are retained in all copies and that this notice

is included verbatim in any distributions. No written agreement, license, or royalty fee is required for any of the authorized uses.

Modifications to this software may be copyrighted by their authors and need not follow the licensing terms described here, provided that the new terms are clearly indicated on the first page of each file where they apply.

(15) - CodeSourcery, Inc. (tic6x-* targets)

Copyright (c) 2010 CodeSourcery, Inc.

All rights reserved.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

- * Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.
- * Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.
- * Neither the name of CodeSourcery

nor the

names of its contributors may be used to endorse or promote products derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY CODESOURCERY, INC. ``AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL CODESOURCERY BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

(16) - GPL with exception (sparc-*leon*, crx-*, cr16-* targets only)

Copyright (C) 1992 Free Software Foundation,

Inc.

Written By David Vinayak Henkel-Wallace, June 1992

This file is free software; you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation; either version 2, or (at your option) any later version.

In addition to the permissions in the GNU General Public License, the Free Software Foundation gives you unlimited permission to link the compiled version of this file with other programs, and to distribute those programs without any restriction coming from the use of this file. (The General Public License restrictions do apply in other respects; for example, they cover modification of the file, and distribution when not linked into another program.)

This file is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details.

You should have received a copy of the GNU General Public License along with this program; see the file COPYING. If not, write to the Free Software Foundation, 59 Temple Place - Suite 330, Boston, MA 02111-1307, USA.

As a special exception, if you link this library with files compiled with GCC to produce an executable, this does not cause the resulting executable to be covered by the GNU General Public License. This exception does not however invalidate any other reasons why the executable file might be covered by the GNU General Public License.

(17) - Adapteva, Inc. (epiphany-* targets)

Copyright (c) 2011, Adapteva, Inc.
All rights reserved.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:
* Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.
* Redistributions in binary form must reproduce the above copyright notice,

this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.

* Neither the name of Adapteva nor the names of its contributors may be used

to endorse or promote products derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT HOLDER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

(18) - Rolls-Royce Controls and Data Services Limited (visium-* targets)

Copyright (c) 2015 Rolls-Royce Controls and Data Services Limited.
All rights reserved.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

- * Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.
- * Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.
- * Neither the name of Rolls-Royce Controls and Data Services Limited nor the names of its contributors may be used to endorse or promote products derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT HOLDER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

(19) - FTDI (ft32-* targets)

Copyright (C) 2014 FTDI (support@ftdichip.com)

The authors hereby grant permission to use, copy, modify, distribute, and license this software and its documentation for any purpose, provided that existing copyright notices are retained in all copies and that this notice is included verbatim in any distributions. No written agreement, license, or royalty fee is required for any of the authorized uses. Modifications to this software may be copyrighted by their authors and need not follow the licensing terms described here, provided that the new terms are clearly indicated on the first page of each file where they apply.

(20) - Synopsys Inc (arc-* targets)

Copyright (c) 2015, Synopsys, Inc. All rights reserved.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

- 1) Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.
- 2) Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.
- 3) Neither the name of the Synopsys, Inc., nor the names of its contributors may be used to endorse or promote products derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT HOLDER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

Copyright (c) 2009 The Go Authors. All rights reserved.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

- * Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.
- * Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.
- * Neither the name of Google Inc. nor the names of its contributors may be used to endorse or promote products derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER

OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

GNU GENERAL PUBLIC LICENSE

Version 3, 29 June 2007

Copyright (C) 2007 Free Software Foundation, Inc. <<http://fsf.org/>>
Everyone is permitted to copy and distribute verbatim copies of this license document, but changing it is not allowed.

Preamble

The GNU General Public License is a free, copyleft license for software and other kinds of works.

The licenses for most software and other practical works are designed to take away your freedom to share and change the works. By contrast, the GNU General Public License is intended to guarantee your freedom to share and change all versions of a program--to make sure it remains free software for all its users. We, the Free Software Foundation, use the GNU General Public License for most of our software; it applies also to any other work released this way by its authors. You can apply it to your programs, too.

When we speak of free software, we are referring to freedom, not price. Our General Public Licenses are designed to make sure that you have the freedom to distribute copies of free software (and charge for them if you wish), that you receive source code or can get it if you

want it, that you can change the software or use pieces of it in new free programs, and that you know you can do these things.

To protect your rights, we need to prevent others from denying you these rights or asking you to surrender the rights. Therefore, you have certain responsibilities if you distribute copies of the software, or if you modify it: responsibilities to respect the freedom of others.

For example, if you distribute copies of such a program, whether gratis or for a fee, you must pass on to the recipients the same freedoms that you received. You must make sure that they, too, receive or can get the source code. And you must show them these terms so they know their rights.

Developers that use the GNU GPL protect your rights with two steps:

(1) assert copyright on the software, and (2) offer you this License giving you legal permission to copy, distribute and/or modify it.

For the developers' and authors' protection, the GPL clearly explains that there is no warranty for this free software. For both users' and authors' sake, the GPL requires that modified versions be marked as changed, so that their problems will not be attributed erroneously to authors of previous versions.

Some devices are designed to deny users access to install or run modified versions of the software inside them, although the manufacturer can do so. This is fundamentally incompatible with the aim of protecting users' freedom to change the software. The systematic pattern of such abuse occurs in the area of products for individuals to use, which is precisely where it is most unacceptable. Therefore, we have designed this version of the GPL to prohibit the practice for those products. If such problems arise substantially in other domains, we stand ready to extend this provision to those domains in future versions of the GPL, as needed to protect the freedom of users.

Finally, every program is threatened constantly by software patents. States should not allow patents to restrict development and use of software on general-purpose computers, but in those that do, we wish to avoid the special danger that patents applied to a free program could make it effectively proprietary. To prevent this, the GPL assures that patents cannot be used to render the program non-free.

The precise terms and conditions for copying, distribution and modification follow.

TERMS AND CONDITIONS

0. Definitions.

"This License" refers to version 3 of the GNU General Public License.

"Copyright" also means copyright-like laws that apply to other kinds of works, such as semiconductor masks.

"The Program" refers to any copyrightable work licensed under this License. Each licensee is addressed as "you". "Licensees" and "recipients" may be individuals or organizations.

To "modify" a work means to copy from or adapt all or part of the work in a fashion requiring copyright permission, other than the making of an exact copy. The resulting work is called a "modified version" of the earlier work or a work "based on" the earlier work.

A "covered work" means either the unmodified Program or a work based on the Program.

To "propagate" a work means to do anything with it that, without permission, would make you directly or secondarily liable for infringement under applicable copyright law, except executing it on a computer or modifying a private copy. Propagation includes copying, distribution (with or without modification), making available to the public, and in some countries other activities as well.

To "convey" a work means any kind of propagation that enables other parties to make or receive copies. Mere interaction with a user through a computer network, with no transfer of a copy, is not conveying.

An interactive user interface displays "Appropriate Legal Notices" to the extent that it includes a convenient and prominently visible feature that (1) displays an appropriate copyright notice, and (2) tells the user that there is no warranty for the work (except to the extent that warranties are provided), that licensees may convey the work under this License, and how to view a copy of this License. If the interface presents a list of user commands or options, such as a menu, a prominent item in the list meets this criterion.

1. Source Code.

The "source code" for a work means the preferred form of the work for making modifications to it. "Object code" means any non-source form of a work.

A "Standard Interface" means an interface that either is an official standard defined by a recognized standards body, or, in the case of interfaces specified for a particular programming language, one that is widely used among developers working in that language.

The

"System Libraries" of an executable work include anything, other than the work as a whole, that (a) is included in the normal form of packaging a Major Component, but which is not part of that Major Component, and (b) serves only to enable use of the work with that Major Component, or to implement a Standard Interface for which an implementation is available to the public in source code form. A "Major Component", in this context, means a major essential component (kernel, window system, and so on) of the specific operating system (if any) on which the executable work runs, or a compiler used to produce the work, or an object code interpreter used to run it.

The "Corresponding Source" for a work in object code form means all the source code needed to generate, install, and (for an executable work) run the object code and to modify the work, including scripts to control those activities. However, it does not include the work's System Libraries, or general-purpose tools or generally available free programs which are used unmodified in performing those activities but which are not part of the work. For example, Corresponding Source includes interface definition files associated with source files for the work, and the source code for shared libraries and dynamically linked subprograms that the work is specifically designed to require, such as by intimate data communication or control flow between those subprograms and other parts of the work.

The Corresponding Source need not include anything that users can regenerate automatically from other parts of the Corresponding Source.

The Corresponding Source for a work in source code form is that same work.

2. Basic Permissions.

All rights granted under this License are granted for the term of copyright on the Program, and are irrevocable provided the stated conditions are met. This License explicitly affirms your unlimited permission to run the unmodified Program. The output from running a covered work is covered

by this License only if the output, given its content, constitutes a covered work. This License acknowledges your rights of fair use or other equivalent, as provided by copyright law.

You may make, run and propagate covered works that you do not convey, without conditions so long as your license otherwise remains in force. You may convey covered works to others for the sole purpose of having them make modifications exclusively for you, or provide you with facilities for running those works, provided that you comply with the terms of this License in conveying all material for which you do not control copyright. Those thus making or running the covered works for you must do so exclusively on your behalf, under your direction and control, on terms that prohibit them from making any copies of your copyrighted material outside their relationship with you.

Conveying under any other circumstances is permitted solely under the conditions stated below. Sublicensing is not allowed; section 10 makes it unnecessary.

3. Protecting Users' Legal Rights From Anti-Circumvention Law.

No covered work shall be deemed part of an effective technological measure under any applicable law fulfilling obligations under article 11 of the WIPO copyright treaty adopted on 20 December 1996, or similar laws prohibiting or restricting circumvention of such measures.

When you convey a covered work, you waive any legal power to forbid circumvention of technological measures to the extent such circumvention is effected by exercising rights under this License with respect to the covered work, and you disclaim any intention to limit operation or modification of the work as a means of enforcing, against the work's users, your or third parties' legal rights to forbid circumvention of technological measures.

4. Conveying Verbatim Copies.

You may convey verbatim copies of the Program's source code as you receive it, in any medium, provided that you conspicuously and appropriately publish on each copy an appropriate copyright notice; keep intact all notices stating that this License and any non-permissive terms added in accord with section 7 apply to the code; keep intact all notices of the absence of any warranty; and give all recipients a copy of this License along with the Program.

You may charge any price or no price for each copy that you convey, and you may offer support or warranty protection for a fee.

5. Conveying Modified Source Versions.

You may convey a work based on the Program, or the modifications to produce it from the Program, in the form of source code under the terms of section 4, provided that you also meet all of these conditions:

- a) The work must carry prominent notices stating that you modified it, and giving a relevant date.
- b) The work must carry prominent notices stating that it is released under this License and any conditions added under section 7. This requirement modifies the requirement in section 4 to "keep intact all notices".
- c) You must license the entire work, as a whole, under this License to anyone who comes into possession of a copy. This License will therefore apply, along with any applicable section 7 additional terms, to the whole of the work, and all its parts, regardless of how they are packaged. This License gives no permission to license the work in any other way, but it does not invalidate such permission if you have separately received it.
- d) If the work has interactive user interfaces, each must display Appropriate Legal Notices; however, if the Program has interactive interfaces that do not display Appropriate Legal Notices, your work need not make them do so.

A compilation of a covered work with other separate and independent works, which are not by their nature extensions of the covered work, and which are not combined with it such as to form a larger program, in or on a volume of a storage or distribution medium, is called an "aggregate" if the compilation and its resulting copyright are not used to limit the access or legal rights of the compilation's users beyond what the individual works permit. Inclusion of a covered work in an aggregate does not cause this License to apply to the other parts of the aggregate.

6. Conveying Non-Source Forms.

You may convey a covered work in object code form under the terms of sections 4 and 5, provided that you also convey the machine-readable Corresponding Source under the terms of this License, in one of these ways:

- a) Convey the object code in, or embodied in, a physical product (including a physical distribution medium), accompanied by the Corresponding Source fixed on a durable physical medium

customarily used for software interchange.

b) Convey the object code in, or embodied in, a physical product (including a physical distribution medium), accompanied by a written offer, valid for at least three years

and valid for as

long as you offer spare parts or customer support for that product model, to give anyone who possesses the object code either (1) a copy of the Corresponding Source for all the software in the product that is covered by this License, on a durable physical medium customarily used for software interchange, for a price no more than your reasonable cost of physically performing this conveying of source, or (2) access to copy the Corresponding Source from a network server at no charge.

c) Convey individual copies of the object code with a copy of the written offer to provide the Corresponding Source. This alternative is allowed only occasionally and noncommercially, and only if you received the object code with such an offer, in accord with subsection 6b.

d) Convey the object code by offering access from a designated place (gratis or for a charge), and offer equivalent access to the Corresponding Source in the same way through the same place at no further charge. You need not require recipients to copy the Corresponding Source along with the object code. If the place to copy the object code is a network server, the Corresponding Source may be on a different server (operated by you or a third party) that supports equivalent copying facilities, provided you maintain clear directions next to the object code saying where to find the Corresponding Source. Regardless of what server hosts the Corresponding Source, you remain obligated to ensure that it is available for as long as needed to satisfy these requirements.

e) Convey the object code using peer-to-peer transmission, provided you inform other peers where the object code and Corresponding Source of the work are being offered to the general public at no charge under subsection 6d.

A separable portion of the object code, whose source code is excluded from the Corresponding Source as a System Library, need not be included in conveying the object code work.

A "User Product" is either (1) a "consumer product", which means any tangible personal property which is normally used for personal, family, or household purposes, or (2) anything designed or sold for incorporation

into a dwelling. In determining whether a product is a consumer product, doubtful cases shall be resolved in favor of coverage. For a particular product received by a particular user, "normally used" refers to a typical or common use of that class of product, regardless of the status of the particular user or of the way in which the particular user actually uses, or expects or is expected to use, the product. A product is a consumer product regardless of whether the product has substantial commercial, industrial or non-consumer uses, unless such uses represent the only significant mode of use of the product.

"Installation Information" for a User Product means any methods, procedures, authorization keys, or other information required to install and execute modified versions of a covered work in that User Product from a modified version of its Corresponding Source. The information must suffice to ensure that the continued functioning of the modified object code is in no case prevented or interfered with solely because modification has been made.

If you convey an object code work under this section in, or with, or specifically for use in, a User Product, and the conveying occurs as part of a transaction in which the right of possession and use of the User Product is transferred to the recipient in perpetuity or for a fixed term (regardless of how the transaction is characterized), the Corresponding Source conveyed under this section must be accompanied by the Installation Information. But this requirement does not apply if neither you nor any third party retains the ability to install modified object code on the User Product (for example, the work has been installed in ROM).

The requirement to provide Installation Information does not include a requirement to continue to provide support service, warranty, or updates for a work that has been modified or installed by the recipient, or for the User Product in which it has been modified or installed. Access to a network may be denied when the modification itself materially and adversely affects the operation of the network or violates the rules and protocols for communication across the network.

Corresponding Source conveyed, and Installation Information provided, in accord with this section must be in a format that is publicly documented (and with an implementation available to the public in source code form), and must require no special password or key for unpacking, reading or copying.

7. Additional Terms.

"Additional permissions" are terms that supplement the terms of this

License by making exceptions from one or more of its conditions. Additional permissions that are applicable to the entire Program shall be treated as though they were included in this License, to the extent that they are valid under applicable law. If additional permissions apply only to part of the Program, that part may be used separately under those permissions, but the entire Program remains governed by this License without regard to the additional permissions.

When you convey a copy of a covered work, you may at your option remove any additional permissions from that copy, or from any part of it. (Additional permissions may be written to require their own removal in certain cases when you modify the work.) You may place additional permissions on material, added by you to a covered work, for which you have or can give appropriate copyright permission.

Notwithstanding any other provision of this License, for material you add to a covered work, you may (if authorized by the copyright holders of that material) supplement the terms of this License with terms:

- a) Disclaiming warranty or limiting liability differently from the terms of sections 15 and 16 of this License; or
- b) Requiring preservation of specified reasonable legal notices or author attributions in that material or in the Appropriate Legal Notices displayed by works containing it; or
- c) Prohibiting misrepresentation of the origin of that material, or requiring that modified versions of such material be marked in reasonable ways as different from the original version; or
- d) Limiting the use for publicity purposes of names of licensors or authors of the material; or
- e) Declining to grant rights under trademark law for use of some trade names, trademarks, or service marks; or
- f) Requiring indemnification of licensors and authors of that material by anyone who conveys the material (or modified versions of it) with contractual assumptions of liability to the recipient, for any liability that these contractual assumptions directly impose on those licensors and authors.

All other non-permissive additional terms are considered "further restrictions" within the meaning of section 10. If the Program as you received it, or any part of it, contains a notice stating that it is

governed by this License along with a term that is a further restriction, you may remove that term. If a license document contains a further restriction but permits relicensing or conveying under this License, you may add to a covered work material governed by the terms of that license document, provided that the further restriction does not survive such relicensing or conveying.

If you add terms to a covered work in accord with this section, you must place, in the relevant source files, a statement of the additional terms that apply to those files, or a notice indicating where to find the applicable terms.

Additional terms, permissive or non-permissive, may be stated in the form of a separately written license, or stated as exceptions; the above requirements apply either way.

8. Termination.

You may not propagate or modify a covered work except as expressly provided under this License. Any attempt otherwise to propagate or modify it is void, and will automatically terminate your rights under this License (including any patent licenses granted under the third paragraph of section 11).

However, if you cease all violation of this License, then your license from a particular copyright holder is reinstated (a) provisionally, unless and until the copyright holder explicitly and finally terminates your license, and (b) permanently, if the copyright holder fails to notify you of the violation by some reasonable means prior to 60 days after the cessation.

Moreover, your license from a particular copyright holder is reinstated permanently if the copyright holder notifies you of the violation by some reasonable means, this is the first time you have received notice of violation of this License (for any work) from that copyright holder, and you cure the violation prior to 30 days after your receipt of the notice.

Termination of your rights under this section does not terminate the licenses of parties who have received copies or rights from you under this License. If your rights have been terminated and not permanently reinstated, you do not qualify to receive new licenses for the same material under section 10.

9. Acceptance Not Required for Having Copies.

You are not required to accept this License in order to receive or run a copy of the Program. Ancillary propagation of a covered work occurring solely as a consequence of using peer-to-peer transmission to receive a copy likewise does not require acceptance. However, nothing other than this License grants you permission to propagate or modify any covered work. These actions infringe copyright if you do not accept this License. Therefore, by modifying or propagating a covered work, you indicate your acceptance of this License to do so.

10. Automatic Licensing of Downstream Recipients.

Each time you convey a covered work, the recipient automatically receives a license from the original licensors, to run, modify and propagate that work, subject to this License. You are not responsible for enforcing compliance by third parties with this License.

An "entity transaction" is a transaction transferring control of an organization, or substantially all assets of one, or subdividing an organization, or merging organizations. If propagation of a covered work results from an entity transaction, each party to that transaction who receives a copy of the work also receives whatever licenses to the work the party's predecessor in interest had or could give under the previous paragraph, plus a right to possession of the Corresponding Source of the work from the predecessor in interest, if the predecessor has it or can get it with reasonable efforts.

You may not impose any further restrictions on the exercise of the rights granted or affirmed under this License. For example, you may not impose a license fee, royalty, or other charge for exercise of rights granted under this License, and you may not initiate litigation (including a cross-claim or counterclaim in a lawsuit) alleging that any patent claim is infringed by making, using, selling, offering for sale, or importing the Program or any portion of it.

11. Patents.

A "contributor" is a copyright holder who authorizes use under this License of the Program or a work on which the Program is based. The work thus licensed is called the contributor's "contributor version".

A contributor's "essential patent claims" are all patent claims owned or controlled by the contributor, whether already acquired or hereafter acquired, that would be infringed by some manner, permitted by this License, of making, using, or selling its contributor version, but do not include claims that would be infringed only as a consequence of further modification of the contributor

version. For purposes of this definition, "control" includes the right to grant patent sublicenses in a manner consistent with the requirements of this License.

Each contributor grants you a non-exclusive, worldwide, royalty-free patent license under the contributor's essential patent claims, to make, use, sell, offer for sale, import and otherwise run, modify and propagate the contents of its contributor version.

In the following three paragraphs, a "patent license" is any express agreement or commitment, however denominated, not to enforce a patent (such as an express permission to practice a patent or covenant not to sue for patent infringement). To "grant" such a patent license to a party means to make such an agreement or commitment not to enforce a patent against the party.

If you convey a covered work, knowingly relying on a patent license, and the Corresponding Source of the work is not available for anyone to copy, free of charge and under the terms of this License, through a publicly available network server or other readily accessible means, then you must either (1) cause the Corresponding Source to be so available, or (2) arrange to deprive yourself of the benefit of the patent license for this particular work, or (3) arrange, in a manner consistent with the requirements of this License, to extend the patent license to downstream recipients. "Knowingly relying" means you have actual knowledge that, but for the patent license, your conveying the covered work in a country, or your recipient's use of the covered work in a country, would infringe one or more identifiable patents in that country that you have reason to believe are valid.

If, pursuant to or in connection with a single transaction or arrangement, you convey, or propagate by procuring conveyance of, a covered work, and grant a patent license to some of the parties receiving the covered work authorizing them to use, propagate, modify or convey a specific copy of the covered work, then the patent license you grant is automatically extended to all recipients of the covered work and works based on it.

A patent license is "discriminatory" if it does not include within the scope of its coverage, prohibits the exercise of, or is conditioned on the non-exercise of one or more of the rights that are specifically granted under this License. You may not convey a covered work if you are a party to an arrangement with a third party that is in the business of distributing software, under which you make payment to the third party based on the extent of your activity of conveying

the work, and under which the third party grants, to any of the parties who would receive the covered work from you, a discriminatory patent license (a) in connection with copies of the covered work conveyed by you (or copies made from those copies), or (b) primarily for and in connection with specific products or compilations that contain the covered work, unless you entered into that arrangement, or that patent license was granted, prior to 28 March 2007.

Nothing in this License shall be construed as excluding or limiting any implied license or other defenses to infringement that may otherwise be available to you under applicable patent law.

12. No Surrender of Others' Freedom.

If conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot convey a covered work so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not convey it at all. For example, if you agree to terms that obligate you to collect a royalty for further conveying from those to whom you convey the Program, the only way you could satisfy both those terms and this License would be to refrain entirely from conveying the Program.

13. Use with the GNU Affero General Public License.

Notwithstanding any other provision of this License, you have permission to link or combine any covered work with a work licensed under version 3 of the GNU Affero General Public License into a single combined work, and to convey the resulting work. The terms of this License will continue to apply to the part which is the covered work, but the special requirements of the GNU Affero General Public License, section 13, concerning interaction through a network will apply to the combination as such.

14. Revised Versions of this License.

The Free Software Foundation may publish revised and/or new versions of the GNU General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Program specifies that a certain numbered version of the GNU General Public License "or any later version" applies to it, you have the option of following the terms and conditions either of that numbered

version or of any later version published by the Free Software Foundation. If the Program does not specify a version number of the GNU General Public License, you may choose any version ever published by the Free Software Foundation.

If the Program specifies that a proxy can decide which future versions of the GNU General Public License can be used, that proxy's public statement of acceptance of a version permanently authorizes you to choose that version for the Program.

Later license versions may give you additional or different permissions. However, no additional obligations are imposed on any author or copyright holder as a result of your choosing to follow a later version.

15. Disclaimer of Warranty.

THERE IS NO WARRANTY FOR THE PROGRAM, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE PROGRAM "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE PROGRAM IS WITH YOU. SHOULD THE PROGRAM PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

16. Limitation of Liability.

IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MODIFIES AND/OR CONVEYS THE PROGRAM AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE PROGRAM (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE PROGRAM TO OPERATE WITH ANY OTHER PROGRAMS), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

17.

Interpretation of Sections 15 and 16.

If the disclaimer of warranty and limitation of liability provided above cannot be given local legal effect according to their terms, reviewing courts shall apply local law that most closely approximates an absolute waiver of all civil liability in connection with the Program, unless a warranty or assumption of liability accompanies a copy of the Program in return for a fee.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Programs

If you develop a new program, and you want it to be of the greatest possible use to the public, the best way to achieve this is to make it free software which everyone can redistribute and change under these terms.

To do so, attach the following notices to the program. It is safest to attach them to the start of each source file to most effectively state the exclusion of warranty; and each file should have at least the "copyright" line and a pointer to where the full notice is found.

```
<one line to give the program's name and a brief idea of what it does.>  
Copyright (C) <year> <name of author>
```

This program is free software: you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation, either version 3 of the License, or (at your option) any later version.

This program is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details.

You should have received a copy of the GNU General Public License along with this program. If not, see <http://www.gnu.org/licenses/>.

Also add information on how to contact you by electronic and paper mail.

If the program does terminal interaction, make it output a short notice like this when it starts in an interactive mode:

```
<program> Copyright (C) <year> <name of author>  
This program comes with ABSOLUTELY NO WARRANTY; for details type `show w'.  
This is free software, and you are welcome to redistribute it  
under certain conditions; type `show c' for details.
```

The hypothetical commands `show w' and `show c' should show the appropriate parts of the General Public License. Of course, your program's commands might be different; for a GUI interface, you would use an "about box".

You should also get your employer (if you work as a programmer) or school, if any, to sign a "copyright disclaimer" for the program, if necessary.

For more information on this, and how to apply and follow the GNU GPL, see
<<http://www.gnu.org/licenses/>>.

The GNU General Public License does not permit incorporating your program into proprietary programs. If your program is a subroutine library, you may consider it more useful to permit linking proprietary applications with the library. If this is what you want to do, use the GNU Lesser General Public License instead of this License. But first, please read
<<http://www.gnu.org/philosophy/why-not-lgpl.html>>.

GNU LIBRARY GENERAL PUBLIC LICENSE

Version 2, June 1991

Copyright (C) 1991 Free Software Foundation, Inc.
59 Temple Place -- Suite 330, Boston, MA 02111-1307, USA

Everyone is permitted to copy and distribute verbatim copies of this license document, but changing it is not allowed.

[This is the first released version of the library GPL. It is numbered 2 because it goes with version 2 of the ordinary GPL.]

Preamble

=====

The licenses for most software are designed to take away your freedom to share and change it. By contrast, the GNU General Public Licenses are intended to guarantee your freedom to share and change free software--to make sure the software is free for all its users.

This license, the Library General Public License, applies to some specially designated Free Software Foundation software, and to any other libraries whose authors decide to use it. You can use it for your libraries, too.

When we speak of free software, we are referring to freedom, not price. Our General Public Licenses are designed to make sure that you have the freedom to distribute copies of free software (and charge for this service if you wish), that you receive source code or can get it if you want it, that you can change the software or use pieces of it in new free programs; and that you know you can do these things.

To protect your rights, we need to make restrictions that forbid anyone to deny you these rights or to ask you to surrender the rights. These restrictions translate to certain responsibilities for you if you

distribute copies of the library, or if you modify it.

For example, if you distribute copies of the library, whether gratis or for a fee, you must give the recipients all the rights that we gave you. You must make sure that they, too, receive or can get the source code. If you link a program with the library, you must provide complete object files to the recipients so that they can relink them with the library, after making changes to the library and recompiling it. And you must show them these terms so they know their rights.

Our method of protecting your rights has two steps: (1) copyright the library, and (2) offer you this license which gives you legal permission to copy, distribute and/or modify the library.

Also, for each distributor's protection, we want to make certain that everyone understands that there is no warranty for this free library. If the library is modified by someone else and passed on, we want its recipients to know that what they have is not the original version, so that any problems introduced by others will not reflect on the original authors' reputations.

Finally, any free program is threatened constantly by software patents. We wish to avoid the danger that companies distributing free software will individually obtain patent licenses, thus in effect transforming the program into proprietary software. To prevent this, we have made it clear that any patent must be licensed for everyone's free use or not licensed at all.

Most GNU software, including some libraries, is covered by the ordinary GNU General Public License, which was designed for utility programs. This license, the GNU Library General Public License, applies to certain designated libraries. This license is quite different from the ordinary one; be sure to read it in full, and don't assume that anything in it is the same as in the ordinary license.

The reason we have a separate public license for some libraries is that they blur the distinction we usually make between modifying or adding to a program and simply using it. Linking a program with a library, without changing the library, is in some sense simply using the library, and is analogous to running a utility program or application program. However, in a textual and legal sense, the linked executable is a combined work, a derivative of the original library, and the ordinary General Public License treats it as such.

Because of this blurred distinction, using the ordinary General

Public License for libraries did not effectively promote software sharing, because most developers did not use the libraries. We concluded that weaker conditions might promote sharing better.

However, unrestricted linking of non-free programs would deprive the users of those programs of all benefit from the free status of the libraries themselves. This Library General Public License is intended to permit developers of non-free programs to use free libraries, while preserving your freedom as a user of such programs to change the free libraries that are incorporated in them. (We have not seen how to achieve this as regards changes in header files, but we have achieved it as regards changes in the actual functions of the Library.) The hope is that this will lead to faster development of free libraries.

The precise terms and conditions for copying, distribution and modification follow. Pay close attention to the difference between a "work based on the library" and a "work that uses the library". The former contains code derived from the library, while the latter only works together with the library.

Note that it is possible for a library to be covered by the ordinary General Public License rather than by this special one.

TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

0. This License Agreement applies to any software library which contains a notice placed by the copyright holder or other authorized party saying it may be distributed under the terms of this Library General Public License (also called "this License"). Each licensee is addressed as "you".

A "library" means a collection of software functions and/or data prepared so as to be conveniently linked with application programs (which use some of those functions and data) to form executables.

The "Library", below, refers to any such software library or work which has been distributed under these terms. A "work based on the Library" means either the Library or any derivative work under copyright law: that is to say, a work containing the Library or a portion of it, either verbatim or with modifications and/or translated straightforwardly into another language. (Hereinafter, translation is included without limitation in the term "modification".)

"Source code" for a work means the preferred form of the work for making modifications to it. For a library, complete source code means all the source code for all modules it contains, plus any

associated interface definition files, plus the scripts used to control compilation and installation of the library.

Activities other than copying, distribution and modification are not covered by this License; they are outside its scope. The act of running a program using the Library is not restricted, and output from such a program is covered only if its contents constitute a work based on the Library (independent of the use of the Library in a tool for writing it). Whether that is true depends on what the Library does and what the program that uses the Library does.

1. You may copy and distribute verbatim copies of the Library's complete source code as you receive it, in any medium, provided that you conspicuously and appropriately publish on each copy an appropriate copyright notice and disclaimer of warranty; keep intact all the notices that refer to this License and to the absence of any warranty; and distribute a copy of this License along with the Library.

You may charge a fee for the physical act of transferring a copy, and you may at your option offer warranty protection in exchange for a fee.

2. You may modify your copy or copies of the Library or any portion of it, thus forming a work based on the Library, and copy and distribute such modifications or work under the terms of Section 1 above, provided that you also meet all of these conditions:

- a. The modified work must itself be a software library.
- b. You must cause the files modified to carry prominent notices stating that you changed the files and the date of any change.
- c. You must cause the whole of the work to be licensed at no charge to all third parties under the terms of this License.
- d. If a facility in the modified Library refers to a function or a table of data to be supplied by an application program that uses the facility, other than as an argument passed when the facility is invoked, then you must make a good faith effort to ensure that, in the event an application does not supply such function or table, the facility still operates, and

performs whatever part of its purpose remains meaningful.

(For example, a function in a library to compute square roots has a purpose that is entirely well-defined independent of the application. Therefore, Subsection 2d requires that any application-supplied function or table used by this function must be optional: if the application does not supply it, the square root function must still compute square roots.)

These requirements apply to the modified work as a whole. If identifiable sections of that work are not derived from the Library, and can be reasonably considered independent and separate works in themselves, then this License, and its terms, do not apply to those sections when you distribute them as separate works. But when you distribute the same sections as part of a whole which is a work based on the Library, the distribution of the whole must be on the terms of this License, whose permissions for other licensees extend to the entire whole, and thus to each and every part regardless of who wrote it.

Thus, it is not the intent of this section to claim rights or contest your rights to work written entirely by you; rather, the intent is to exercise the right to control the distribution of derivative or collective works based on the Library.

In addition, mere aggregation of another work not based on the Library with the Library (or with a work based on the Library) on a volume of a storage or distribution medium does not bring the other work under the scope of this License.

3. You may opt to apply the terms of the ordinary GNU General Public License instead of this License to a given copy of the Library. To do this, you must alter all the notices that refer to this License, so that they refer to the ordinary GNU General Public License, version 2, instead of to this License. (If a newer version than version 2 of the ordinary GNU General Public License has appeared, then you can specify that version instead if you wish.) Do not make any other change in these notices.

Once this change is made in a given copy, it is irreversible for that copy, so the ordinary GNU General Public License applies to all subsequent copies and derivative works made from that copy.

This option is useful when you wish to copy part of the code of the Library into a program that is not a library.

4. You may copy and distribute the Library (or a portion or derivative of it, under Section 2) in object code or executable

form under the terms of Sections 1 and 2 above provided that you accompany it with the complete corresponding machine-readable source code, which must be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange.

If distribution of object code is made by offering access to copy from a designated place, then offering equivalent access to copy the source code from the same place satisfies the requirement to distribute the source code, even though third parties are not compelled to copy the source along with the object code.

5. A program that contains no derivative of any portion of the Library, but is designed to work with the Library by being compiled or linked with it, is called a "work that uses the Library". Such a work, in isolation, is not a derivative work of the Library, and therefore falls outside the scope of this License.

However, linking a "work that uses the Library" with the Library creates an executable that is a derivative of the Library (because it contains portions of the Library), rather than a "work that uses the library". The executable is therefore covered by this License. Section 6 states terms for distribution of such executables.

When a "work that uses the Library" uses material from a header file that is part of the Library, the object code for the work may be a derivative work of the Library even though the source code is not. Whether this is true is especially significant if the work can be linked without the Library, or if the work is itself a library. The threshold for this to be true is not precisely defined by law.

If such an object file uses only numerical parameters, data structure layouts and accessors, and small macros and small inline functions (ten lines or less in length), then the use of the object file is unrestricted, regardless of whether it is legally a derivative work. (Executables containing this object code plus portions of the Library will still fall under Section 6.)

Otherwise, if the work is a derivative of the Library, you may distribute the object code for the work under the terms of Section 6. Any executables containing that work also fall under Section 6, whether or not they are linked directly with the Library itself.

6. As an exception to the Sections above, you may also compile or

link a "work that uses the Library" with the Library to produce a work containing portions of the Library, and distribute that work under terms of your choice, provided that the terms permit modification of the work for the customer's own use and reverse engineering for debugging such modifications.

You must give prominent notice with each copy of the work that the Library is used in it and that the Library and its use are covered by this License. You must supply a copy of this License. If the work during execution displays copyright notices, you must include the copyright notice for the Library among them, as well as a reference directing the user to the copy of this License. Also, you must do one of these things:

a.

Accompany the work with the complete corresponding machine-readable source code for the Library including whatever changes were used in the work (which must be distributed under Sections 1 and 2 above); and, if the work is an executable linked with the Library, with the complete machine-readable "work that uses the Library", as object code and/or source code, so that the user can modify the Library and then relink to produce a modified executable containing the modified Library. (It is understood that the user who changes the contents of definitions files in the Library will not necessarily be able to recompile the application to use the modified definitions.)

b. Accompany the work with a written offer, valid for at least three years, to give the same user the materials specified in Subsection 6a, above, for a charge no more than the cost of

performing this distribution.

c. If distribution of the work is made by offering access to copy from a designated place, offer equivalent access to copy the above specified materials from the same place.

d. Verify that the user has already received a copy of these materials or that you have already sent this user a copy.

For an executable, the required form of the "work that uses the Library" must include any data and utility programs needed for reproducing the executable from it. However, as a special exception, the source code distributed need not include anything that is normally distributed (in either source or binary form) with the major components (compiler, kernel, and so on) of the operating system on which the executable runs, unless that

component itself accompanies the executable.

It may happen that this requirement contradicts the license restrictions of other proprietary libraries that do not normally accompany the operating system. Such a contradiction means you cannot use both them and the Library together in an executable that you distribute.

7. You may place library facilities that are a work based on the Library side-by-side in a single library together with other library facilities not covered by this License, and distribute such a combined library, provided that the separate distribution of the work based on the Library and of the other library facilities is otherwise permitted, and provided that you do these two things:
 - a. Accompany the combined library with a copy of the same work based on the Library, uncombined with any other library facilities. This must be distributed under the terms of the Sections above.
 - b. Give prominent notice with the combined library of the fact that part of it is a work based on the Library, and explaining where to find the accompanying uncombined form of the same work.
8. You may not copy, modify, sublicense, link with, or distribute the Library except as expressly provided under this License. Any attempt otherwise to copy, modify, sublicense, link with, or distribute the Library is void, and will automatically terminate your rights under this License. However, parties who have received copies, or rights, from you under this License will not have their licenses terminated so long as such parties remain in full compliance.
9. You are not required to accept this License, since you have not signed it. However, nothing else grants you permission to modify or distribute the Library or its derivative works. These actions are prohibited by law if you do not accept this License. Therefore, by modifying or distributing the Library (or any work based on the Library), you indicate your acceptance of this License to do so, and all its terms and conditions for copying, distributing or modifying the Library or works based on it.
10. Each time you redistribute the Library (or any work based on the

Library), the recipient automatically receives a license from the original licensor to copy, distribute, link with or modify the Library subject to these terms and conditions. You may not impose any further restrictions on the recipients' exercise of the rights granted herein. You are not responsible for enforcing compliance by third parties to this License.

11. If, as a consequence of a court judgment or allegation of patent infringement or for any other reason (not limited to patent issues), conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot distribute so as to satisfy simultaneously

your obligations under this License and any other pertinent obligations, then as a consequence you may not distribute the Library at all. For example, if a patent license would not permit royalty-free redistribution of the Library by all those who receive copies directly or indirectly through you, then the only way you could satisfy both it and this License would be to refrain entirely from distribution of the Library.

If any portion of this section is held invalid or unenforceable under any particular circumstance, the balance of the section is intended to apply, and the section as a whole is intended to apply in other circumstances.

It is not the purpose of this section to induce you to infringe any patents or other property right claims or to contest validity of any such claims; this section has the sole purpose of protecting the integrity of the free software distribution system which is implemented by public license practices. Many people have made generous contributions to the wide range of software distributed through that system in reliance on consistent application of that system; it is up to the author/donor to decide if he or she is willing to distribute software through any other system and a licensee cannot impose that choice.

This section is intended to make thoroughly clear what is believed to be a consequence of the rest of this License.

12. If the distribution and/or use of the Library is restricted in certain countries either by patents or by copyrighted interfaces, the original copyright holder who places the Library under this License may add an explicit geographical distribution limitation excluding those countries, so that distribution is permitted only in or among countries not thus excluded. In such case, this

License incorporates the limitation as if written in the body of this License.

13. The Free Software Foundation may publish revised and/or new versions of the Library General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Library specifies a version number of this License which applies to it and "any later version", you have the option of following the terms and conditions either of that version or of any later version published by the Free Software Foundation. If the Library does not specify a license version number, you may choose any version ever published by the Free Software Foundation.

14. If you wish to incorporate parts of the Library into other free programs whose distribution conditions are incompatible with these, write to the author to ask for permission. For software which is copyrighted by the Free Software Foundation, write to the Free Software Foundation; we sometimes make exceptions for this. Our decision will be guided by the two goals of preserving the free status of all derivatives of our free software and of promoting the sharing and reuse of software generally.

NO WARRANTY

15. BECAUSE THE LIBRARY IS LICENSED FREE OF CHARGE, THERE IS NO WARRANTY FOR THE LIBRARY, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE LIBRARY "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE LIBRARY IS WITH YOU. SHOULD THE LIBRARY PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

16. IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY AND/OR REDISTRIBUTE THE LIBRARY AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE LIBRARY (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE LIBRARY TO OPERATE WITH ANY

OTHER SOFTWARE), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Libraries

=====

If you develop a new library, and you want it to be of the greatest possible use to the public, we recommend making it free software that everyone can redistribute and change. You can do so by permitting redistribution under these terms (or, alternatively, under the terms of the ordinary General Public License).

To apply these terms, attach the following notices to the library. It is safest to attach them to the start of each source file to most effectively convey the exclusion of warranty; and each file should have at least the "copyright" line and a pointer to where the full notice is found.

ONE LINE TO GIVE THE LIBRARY'S NAME AND AN IDEA OF WHAT IT DOES.
Copyright (C) YEAR NAME OF AUTHOR

This library is free software; you can redistribute it and/or modify it under the terms of the GNU Library General Public License as published by the Free Software Foundation; either version 2 of the License, or (at your option) any later version.

This library is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU Library General Public License for more details.

You should have received a copy of the GNU General Public License along with this program; if not, write to the Free Software Foundation, Inc., 59 Temple Place, Suite 330, Boston, MA 02111-1307, USA.

Also add information on how to contact you by electronic and paper mail.

You should also get your employer (if you work as a programmer) or your school, if any, to sign a "copyright disclaimer" for the library, if necessary. Here is a sample; alter the names:

Yoyodyne, Inc., hereby disclaims all copyright interest in the library `Frob' (a library for tweaking knobs) written by James Random Hacker.

SIGNATURE OF TY COON, 1 April 1990

Ty Coon, President of Vice

That's all there is to it!

GNU LESSER GENERAL PUBLIC LICENSE

Version 3, 29 June 2007

Copyright (C) 2007 Free Software Foundation, Inc. <<http://fsf.org/>>

Everyone is permitted to copy and distribute verbatim copies of this license document, but changing it is not allowed.

This version of the GNU Lesser General Public License incorporates the terms and conditions of version 3 of the GNU General Public License, supplemented by the additional permissions listed below.

0. Additional Definitions.

As used herein, "this License" refers to version 3 of the GNU Lesser General Public License, and the "GNU GPL" refers to version 3 of the GNU General Public License.

"The Library" refers to a covered work governed by this License, other than an Application or a Combined Work as defined below.

An "Application" is any work that makes use of an interface provided by the Library, but which is not otherwise based on the Library.

Defining a subclass of a class defined by the Library is deemed a mode of using an interface provided by the Library.

A "Combined Work" is a work produced by combining or linking an Application with the Library. The particular version of the Library with which the Combined Work was made is also called the "Linked Version".

The "Minimal Corresponding Source" for a Combined Work means the Corresponding Source for the Combined Work, excluding any source code for portions of the Combined Work that, considered in isolation, are based on the Application, and not on the Linked Version.

The "Corresponding Application Code" for a Combined Work means the object code and/or source code for the Application, including any data and utility programs needed for reproducing the Combined Work from the Application, but excluding the System Libraries of the Combined Work.

1. Exception to Section 3 of the GNU GPL.

You may convey a covered work under sections 3 and 4 of this License without being bound by section 3 of the GNU GPL.

2. Conveying Modified Versions.

If you modify a copy of the Library, and, in your modifications, a facility refers to a function or data to be supplied by an Application that uses the facility (other than as an argument passed when the facility is invoked), then you may convey a copy of the modified version:

- a) under this License, provided that you make a good faith effort to ensure that, in the event an Application does not supply the function or data, the facility still operates, and performs whatever part of its purpose remains meaningful, or
- b) under the GNU GPL, with none of the additional permissions of this License applicable to that copy.

3. Object Code Incorporating Material from Library Header Files.

The object code form of an Application may incorporate material from a header file that is part of the Library. You may convey such object code under terms of your choice, provided that, if the incorporated material is not limited to numerical parameters, data structure layouts and accessors, or small macros, inline functions and templates (ten or fewer lines in length), you do both of the following:

- a) Give prominent notice with each copy of the object code that the Library is used in it and that the Library and its use are covered by this License.
- b) Accompany the object code with a copy of the GNU GPL and this license document.

4. Combined Works.

You may convey a Combined Work under terms of your choice that, taken together, effectively do not restrict modification of the portions of the Library contained in the Combined Work and reverse engineering for debugging such modifications, if you also do each of the following:

- a) Give prominent notice with each copy of the Combined Work that the Library is used in it and that the Library and its use are covered by this License.

b) Accompany the Combined Work with a copy of the GNU GPL and this license document.

c) For a Combined Work that displays copyright notices during execution, include the copyright notice for the Library among these notices, as well as a reference directing the user to the copies of the GNU GPL and this license document.

d) Do one of the following:

0) Convey the Minimal Corresponding Source under the terms of this License, and the Corresponding Application Code in a form suitable for, and under terms that permit, the user to recombine or relink the Application with a modified version of the Linked Version to produce a modified Combined Work, in the manner specified by section 6 of the GNU GPL for conveying Corresponding Source.

1) Use a suitable shared library mechanism for linking with the Library. A suitable mechanism is one that (a) uses at run time a copy of the Library already present on the user's computer system, and (b) will operate properly with a modified version of the Library that is interface-compatible with the Linked Version.

e) Provide Installation Information, but only if you would otherwise be required to provide such information under section 6 of the GNU GPL, and only to the extent that such information is necessary to install and execute a modified version of the Combined Work produced by recombining or relinking the Application with a modified version of the Linked Version. (If you use option 4d0, the Installation Information must accompany the Minimal Corresponding Source and Corresponding Application Code. If you use option 4d1, you must provide the Installation Information in the manner specified by section 6 of the GNU GPL for conveying Corresponding Source.)

5. Combined Libraries.

You may place library facilities that are a work based on the Library side by side in a single library together with other library facilities that are not Applications and are not covered by this License, and convey such a combined library under terms of your choice, if you do both of the following:

a) Accompany the combined library with a copy of the same work based on the Library, uncombined with any other library facilities, conveyed under the terms of this License.

b) Give prominent notice with the combined library that part of it is a work based on the Library, and explaining where to find the accompanying uncombined form of the same work.

6. Revised Versions of the GNU Lesser General Public License.

The Free Software Foundation may publish revised and/or new versions of the GNU Lesser General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Library as you received it specifies that a certain numbered version of the GNU Lesser General Public License "or any later version" applies to it, you have the option of following the terms and conditions either of that published version or of any later version published by the Free Software Foundation. If the Library as you received it does not specify a version number of the GNU Lesser General Public License, you may choose any version of the GNU Lesser General Public License ever published by the Free Software Foundation.

If the Library as you received it specifies that a proxy can decide whether future versions of the GNU Lesser General Public License shall apply, that proxy's public statement of acceptance of any version is permanent authorization for you to choose that version for the Library.

=====
compiler_rt License
=====

The compiler_rt library is dual licensed under both the University of Illinois "BSD-Like" license and the MIT license. As a user of this code you may choose to use it under either license. As a contributor, you agree to allow your code to be used under both.

Full text of the relevant licenses is included below.

=====
University of Illinois/NCSA
Open Source License

Copyright (c) 2009-2012 by the contributors listed in CREDITS.TXT

All rights reserved.

Developed by:

LLVM Team

University of Illinois at Urbana-Champaign

<http://llvm.org>

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal with the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

- * Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimers.
- * Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimers in the documentation and/or other materials provided with the distribution.
- * Neither the names of the LLVM Team, University of Illinois at Urbana-Champaign, nor the names of its contributors may be used to endorse or promote products derived from this Software without specific prior written permission.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE CONTRIBUTORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS WITH THE SOFTWARE.

=====

Copyright (c) 2009-2012 by the contributors listed in CREDITS.TXT

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights

to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

Copyrights and Licenses for Third Party Software Distributed with LLVM:

The LLVM software contains code written by third parties. Such software will have its own individual LICENSE.TXT file in the directory in which it appears. This file will describe the copyrights, license, and restrictions which apply to that code.

The disclaimer of warranty in the University of Illinois Open Source License applies to all code in the LLVM Distribution, and nothing in any of the other licenses gives permission to use the names of the LLVM Team or the University of Illinois to endorse or promote products derived from this Software.

The following pieces of software have additional or alternate copyrights, licenses, and/or restrictions:

Program	Directory
-----	-----
mach_override	lib/interception/mach_override
Boost Software License - Version 1.0 - August 17th, 2003	

Permission is hereby granted, free of charge, to any person or organization obtaining a copy of the software and accompanying documentation covered by this license (the "Software") to use, reproduce, display, distribute, execute, and transmit the Software, and to prepare derivative works of the Software, and to permit third-parties to whom the Software is furnished to do so, all subject to the following:

The copyright notices in the Software and this entire statement, including the above license grant, this restriction and the following disclaimer,

must be included in all copies of the Software, in whole or in part, and all derivative works of the Software, unless such copies or derivative works are solely in the form of machine-executable object code generated by a source language processor.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, TITLE AND NON-INFRINGEMENT. IN NO EVENT SHALL THE COPYRIGHT HOLDERS OR ANYONE DISTRIBUTING THE SOFTWARE BE LIABLE FOR ANY DAMAGES OR OTHER LIABILITY, WHETHER IN CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.37 fdisk 2.31.1

1.37.1 Available under license :

GNU GENERAL PUBLIC LICENSE

Version 2, June 1991

Copyright (C) 1989, 1991 Free Software Foundation, Inc.,
51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA

Everyone is permitted to copy and distribute verbatim copies of this license document, but changing it is not allowed.

Preamble

The licenses for most software are designed to take away your freedom to share and change it. By contrast, the GNU General Public License is intended to guarantee your freedom to share and change free software--to make sure the software is free for all its users. This General Public License applies to most of the Free Software Foundation's software and to any other program whose authors commit to using it. (Some other Free Software Foundation software is covered by the GNU Lesser General Public License instead.) You can apply it to your programs, too.

When we speak of free software, we are referring to freedom, not price.

Our General Public Licenses are designed to make sure that you have the freedom to distribute copies of free software (and charge for this service if you wish), that you receive source code or can get it if you want it, that you can change the software or use pieces of it in new free programs; and that you know you can do these things.

To protect your rights, we need to make restrictions that forbid anyone to deny you these rights or to ask you to surrender the rights.

These restrictions translate to certain responsibilities for you if you distribute copies of the software, or if you modify it.

For example, if you distribute copies of such a program, whether gratis or for a fee, you must give the recipients all the rights that you have. You must make sure that they, too, receive or can get the source code. And you must show them these terms so they know their rights.

We protect your rights with two steps: (1) copyright the software, and (2) offer you this license which gives you legal permission to copy, distribute and/or modify the software.

Also, for each author's protection and ours, we want to make certain that everyone understands that there is no warranty for this free software. If the software is modified by someone else and passed on, we want its recipients to know that what they have is not the original, so that any problems introduced by others will not reflect on the original authors' reputations.

Finally, any free program is threatened constantly by software patents. We wish to avoid the danger that redistributors of a free program will individually obtain patent licenses, in effect making the program proprietary. To prevent this, we have made it clear that any patent must be licensed for everyone's free use or not licensed at all.

The precise terms and conditions for copying, distribution and modification follow.

GNU GENERAL PUBLIC LICENSE

TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

0. This License applies to any program or other work which contains a notice placed by the copyright holder saying it may be distributed under the terms of this General Public License. The "Program", below, refers to any such program or work, and a "work based on the Program" means either the Program or any derivative work under copyright law: that is to say, a work containing the Program or a portion of it, either verbatim or with modifications and/or translated into another language. (Hereinafter, translation is included without limitation in the term "modification".) Each licensee is addressed as "you".

Activities other than copying, distribution and modification are not covered by this License; they are outside its scope. The act of running the Program is not restricted, and the output from the Program is covered only if its contents constitute a work based on the Program (independent of having been made by running the Program).

Whether that is true depends on what the Program does.

1. You may copy and distribute verbatim copies of the Program's source code as you receive it, in any medium, provided that you conspicuously and appropriately publish on each copy an appropriate copyright notice and disclaimer of warranty; keep intact all the notices that refer to this License and to the absence of any warranty; and give any other recipients of the Program a copy of this License along with the Program.

You may charge a fee for the physical act of transferring a copy, and you may at your option offer warranty protection in exchange for a fee.

2. You may modify your copy or copies of the Program or any portion of it, thus forming a work based on the Program, and copy and distribute such modifications or work under the terms of Section 1 above, provided that you also meet all of these conditions:

a) You must cause the modified files to carry prominent notices stating that you changed the files and the date of any change.

b) You must cause any work that you distribute or publish, that in whole or in part contains or is derived from the Program or any part thereof, to be licensed as a whole at no charge to all third parties under the terms of this License.

c) If the modified program normally reads commands interactively when run, you must cause it, when started running for such interactive use in the most ordinary way, to print or display an announcement including an appropriate copyright notice and a notice that there is no warranty (or else, saying that you provide a warranty) and that users may redistribute the program under these conditions, and telling the user how to view a copy of this License. (Exception: if the Program itself is interactive but does not normally print such an announcement, your work based on the Program is not required to print an announcement.)

These requirements apply to the modified work as a whole. If identifiable sections of that work are not derived from the Program, and can be reasonably considered independent and separate works in themselves, then this License, and its terms, do not apply to those sections when you distribute them as separate works. But when you distribute the same sections as part of a whole which is a work based on the Program, the distribution of the whole must be on the terms of this License, whose permissions for other licensees extend to the

entire whole, and thus to each and every part regardless of who wrote it.

Thus, it is not the intent of this section to claim rights or contest your rights to work written entirely by you; rather, the intent is to exercise the right to control the distribution of derivative or collective works based on the Program.

In addition, mere aggregation of another work not based on the Program with the Program (or with a work based on the Program) on a volume of a storage or distribution medium does not bring the other work under the scope of this License.

3. You may copy and distribute the Program (or a work based on it, under Section 2) in object code or executable form under the terms of Sections 1 and 2 above provided that you also do one of the following:

- a) Accompany it with the complete corresponding machine-readable source code, which must be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange; or,
- b) Accompany it with a written offer, valid for at least three years, to give any third party, for a charge no more than your cost of physically performing source distribution, a complete machine-readable copy of the corresponding source code, to be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange; or,
- c) Accompany it with the information you received as to the offer to distribute corresponding source code. (This alternative is allowed only for noncommercial distribution and only if you received the program in object code or executable form with such an offer, in accord with Subsection b above.)

The source code for a work means the preferred form of the work for making modifications to it. For an executable work, complete source code means all the source code for all modules it contains, plus any associated interface definition files, plus the scripts used to control compilation and installation of the executable. However, as a special exception, the source code distributed need not include anything that is normally distributed (in either source or binary form) with the major components (compiler, kernel, and so on) of the operating system on which the executable runs, unless that component itself accompanies the executable.

If distribution of executable or object code is made by offering access to copy from a designated place, then offering equivalent access to copy the source code from the same place counts as

distribution of the source code, even though third parties are not compelled to copy the source along with the object code.

4. You may not copy, modify, sublicense, or distribute the Program except as expressly provided under this License. Any attempt otherwise to copy, modify, sublicense or distribute the Program is void, and will automatically terminate your rights under this License. However, parties who have received copies, or rights, from you under this License will not have their licenses terminated so long as such parties remain in full compliance.

5. You are not required to accept this License, since you have not signed it. However, nothing else grants you permission to modify or distribute the Program or its derivative works. These actions are prohibited by law if you do not accept this License. Therefore, by modifying or distributing the Program (or any work based on the Program), you indicate your acceptance of this License to do so, and all its terms and conditions for copying, distributing or modifying the Program or works based on it.

6. Each time you redistribute the Program (or any work based on the Program), the recipient automatically receives a license from the original licensor to copy, distribute or modify the Program subject to these terms and conditions. You may not impose any further restrictions on the recipients' exercise of the rights granted herein. You are not responsible for enforcing compliance by third parties to this License.

7. If, as a consequence of a court judgment or allegation of patent infringement or for any other reason (not limited to patent issues), conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot distribute so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not distribute the Program at all. For example, if a patent license would not permit royalty-free redistribution of the Program by all those who receive copies directly or indirectly through you, then the only way you could satisfy both it and this License would be to refrain entirely from distribution of the Program.

If any portion of this section is held invalid or unenforceable under any particular circumstance, the balance of the section is intended to apply and the section as a whole is intended to apply in other circumstances.

It is not the purpose of this section to induce you to infringe any patents or other property right claims or to contest validity of any such claims; this section has the sole purpose of protecting the integrity of the free software distribution system, which is implemented by public license practices. Many people have made generous contributions to the wide range of software distributed through that system in reliance on consistent application of that system; it is up to the author/donor to decide if he or she is willing to distribute software through any other system and a licensee cannot impose that choice.

This section is intended to make thoroughly clear what is believed to be a consequence of the rest of this License.

8. If the distribution and/or use of the Program is restricted in certain countries either by patents or by copyrighted interfaces, the original copyright holder who places the Program under this License may add an explicit geographical distribution limitation excluding those countries, so that distribution is permitted only in or among countries not thus excluded. In such case, this License incorporates the limitation as if written in the body of this License.

9. The Free Software Foundation may publish revised and/or new versions of the General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Program specifies a version number of this License which applies to it and "any later version", you have the option of following the terms and conditions either of that version or of any later version published by the Free Software Foundation. If the Program does not specify a version number of this License, you may choose any version ever published by the Free Software Foundation.

10. If you wish to incorporate parts of the Program into other free programs whose distribution conditions are different, write to the author to ask for permission. For software which is copyrighted by the Free Software Foundation, write to the Free Software Foundation; we sometimes make exceptions for this. Our decision will be guided by the two goals of preserving the free status of all derivatives of our free software and of promoting the sharing and reuse of software generally.

NO WARRANTY

11. BECAUSE THE PROGRAM IS LICENSED FREE OF CHARGE,
THERE IS NO WARRANTY
FOR THE PROGRAM, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN
OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES
PROVIDE THE PROGRAM "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED
OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF
MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS
TO THE QUALITY AND PERFORMANCE OF THE PROGRAM IS WITH YOU. SHOULD THE
PROGRAM PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING,
REPAIR OR CORRECTION.

12. IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING
WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY AND/OR
REDISTRIBUTE THE PROGRAM AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES,
INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING
OUT OF THE USE OR INABILITY TO USE THE PROGRAM (INCLUDING BUT NOT LIMITED
TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY
YOU OR
THIRD PARTIES OR A FAILURE OF THE PROGRAM TO OPERATE WITH ANY OTHER
PROGRAMS), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE
POSSIBILITY OF SUCH DAMAGES.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Programs

If you develop a new program, and you want it to be of the greatest
possible use to the public, the best way to achieve this is to make it
free software which everyone can redistribute and change under these terms.

To do so, attach the following notices to the program. It is safest
to attach them to the start of each source file to most effectively
convey the exclusion of warranty; and each file should have at least
the "copyright" line and a pointer to where the full notice is found.

<one line to give the program's name and a brief idea of what it does.>

Copyright (C) <year> <name of author>

This program is free software; you can redistribute it and/or modify
it under the terms of the GNU

General Public License as published by

the Free Software Foundation; either version 2 of the License, or
(at your option) any later version.

This program is distributed in the hope that it will be useful,
but WITHOUT ANY WARRANTY; without even the implied warranty of
MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
GNU General Public License for more details.

You should have received a copy of the GNU General Public License along with this program; if not, write to the Free Software Foundation, Inc., 51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA.

Also add information on how to contact you by electronic and paper mail.

If the program is interactive, make it output a short notice like this when it starts in an interactive mode:

```
Gnomovision version 69, Copyright (C) year name of author
Gnomovision comes with ABSOLUTELY NO WARRANTY; for details type `show w'.
This is free software, and you are welcome to redistribute
it
under certain conditions; type `show c' for details.
```

The hypothetical commands ``show w'` and ``show c'` should show the appropriate parts of the General Public License. Of course, the commands you use may be called something other than ``show w'` and ``show c'`; they could even be mouse-clicks or menu items--whatever suits your program.

You should also get your employer (if you work as a programmer) or your school, if any, to sign a "copyright disclaimer" for the program, if necessary. Here is a sample; alter the names:

```
Yoyodyne, Inc., hereby disclaims all copyright interest in the program
`Gnomovision' (which makes passes at compilers) written by James Hacker.
```

```
<signature of Ty Coon>, 1 April 1989
Ty Coon, President of Vice
```

This General Public License does not permit incorporating your program into proprietary programs. If your program is a subroutine library, you may consider it more useful to permit linking proprietary applications with the library. If this is what you want to do, use the GNU Lesser General Public License instead of this License.

1.38 libncursesw 6.1-1ubuntu1.18.04

1.38.1 Available under license :

Upstream source <https://invisible-island.net/ncurses/ncurses-examples.html>

Current ncurses maintainer: Thomas Dickey <dickey@invisible-island.net>

Files: *

Copyright: 1998-2017,2018 Free Software Foundation, Inc.

Licence: X11

Files: aclocal.m4 package

Copyright: 2010-2017,2018 by Thomas E. Dickey

Licence: X11

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, distribute with modifications, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE ABOVE COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

Except as contained in this notice, the name(s) of the above copyright holders shall not be used in advertising or otherwise to promote the sale, use or other dealings in this Software without prior written authorization.

Files: install-sh

Copyright: 1994 X Consortium

Licence: X11

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE X CONSORTIUM BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

Except as contained in this notice, the name of the X Consortium shall not be used in advertising or otherwise to promote the sale, use or other dealings in this Software without prior written authorization from the X Consortium.

FSF changes to this file are in the public domain.

Calling this script install-sh is preferred over install.sh, to prevent `make` implicit rules from creating a file called install from it when there is no Makefile.

This script is compatible with the BSD install script, but was written from scratch. It can only install one file at a time, a restriction shared with many OS's install programs.

On Debian systems, the complete text of the GNU General Public License can be found in '/usr/share/common-licenses/GPL-2'

-- vile: txtmode file-encoding=utf-8
Upstream source <https://invisible-island.net/ncurses/ncurses.html>
This package is used for testing builds of ncurses.

Current ncurses maintainer: Thomas Dickey <dickey@invisible-island.net>

Files: *
Copyright: 1998-2017,2018 Free Software Foundation, Inc.
Licence: X11

Files: aclocal.m4 package
Copyright: 1996-2017,2018 by Thomas E. Dickey
Licence: X11

Files: doc/html/NCURSES-Programming-HOWTO.html
Copyright: 2001 by Pradeep Padala
Licence: X11

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including

without limitation the rights to use, copy, modify, merge, publish, distribute, distribute with modifications, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE ABOVE COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

Except as contained in this notice, the name(s) of the above copyright holders shall not be used in advertising or otherwise to promote the sale, use or other dealings in this Software without prior written authorization.

Files: install-sh
Copyright: 1994
X Consortium
Licence: X11

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE X CONSORTIUM BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

Except as contained in this notice, the name of the X Consortium shall not be used in advertising or otherwise to promote the sale, use or other deal-

ings in this Software without prior written authorization from the X Consortium.

Files: progs/tset.c ncurses/tinfo/read_termcap.c

Copyright: 1980,1991,1992,1993 The Regents of the University of California.

License: BSD

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

1. Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.
2. Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.
3. Neither the name of the University nor the names of its contributors may be used to endorse or promote products derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE REGENTS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE REGENTS OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

-- vile: txtmode file-encoding=utf-8

Upstream source <https://invisible-island.net/ncurses/ncurses-examples.html>

Current ncurses maintainer: Thomas Dickey <dickey@invisible-island.net>

Files: *

Copyright: 1998-2017,2018 Free Software Foundation, Inc.

Licence: X11

Files: alocal.m4 package

Copyright: 2003-2017,2018 by Thomas E. Dickey

Licence: X11

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, distribute with modifications, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE ABOVE COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

Except as contained in this notice, the name(s) of the above copyright holders shall not be used in advertising or otherwise to promote the sale, use or other dealings in this Software without prior written authorization.

Files: install-sh

Copyright: 1994 X Consortium

Licence: X11

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE X CONSORTIUM BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

Except as contained in this notice, the name of the X Consortium shall not be used in advertising or otherwise to promote the sale, use or other dealings in this Software without prior written authorization from the X Consortium.

FSF changes to this file are in the public domain.

Calling this script install-sh is preferred over install.sh, to prevent `make` implicit rules from creating a file called install from it when there is no Makefile.

This script is compatible with the BSD install script, but was written from scratch. It can only install one file at a time, a restriction shared with many OS's install programs.

On Debian systems, the complete text of the GNU General Public License can be found in '/usr/share/common-licenses/GPL-2'

-- vile:txtmode file-encoding=utf-8

Copyright (c) 1998-2017,2018 Free Software Foundation, Inc.

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, distribute with modifications, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE ABOVE COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

Except as contained in this notice, the name(s) of the above copyright holders shall not be used in advertising or otherwise to promote the sale, use or other dealings in this Software without prior written authorization.

-- vile:txtmode fc=72

-- \$Id: COPYING,v 1.6 2018/01/01 12:00:00 tom Exp \$

This is the Debian prepackaged version of the ncurses library and terminfo utilities. ncurses/terminfo was originally written by Pavel Curtis and Zeyd M. Ben-Halim <zmbenhal@netcom.com>, and is currently held by the Free Software Foundation.

This package was put together by Vaidhyanathan G Mayilrangam <vaidhy@debian.org> and Joel Klecker <espy@debian.org>, using sources obtained from ftp://ftp.gnu.org/gnu/ncurses/ncurses-5.0.tar.gz. Current versions of the ncurses sources are found at ftp://invisible-island.net/ncurses/.

It is based somewhat on work done by Bruce Perens <Bruce@Pixar.com>, David Engel <david@elo.ods.com>. Michael Alan Dorman <mdorman@debian.org>, Richard Braakman <dark@xs4all.nl>, James Troup <jjttroupe@comp.brad.ac.uk>, J.H.M. Dassen (Ray) <jdassen@wi.LeidenUniv.nl>, and Galen Hazelwood <galenh@micron.net> over various years.

Copyright (c) 1998-2018 Free Software Foundation, Inc.
Copyright 2001 by Pradeep Padala

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, distribute with modifications, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE ABOVE COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

Except as contained in this notice, the name(s) of the above copyright holders shall not be used in advertising or otherwise to promote the sale, use or other dealings in this Software without prior written authorization.

Copyright (C) 1994 X Consortium

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE X CONSORTIUM BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

Except as contained in this notice, the name of the X Consortium shall not be used in advertising or otherwise to promote the sale, use or other dealings in this Software without prior written authorization from the X Consortium.

Copyright (c) 1980, 1991, 1992, 1993

The Regents of the University of California. All rights reserved.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

1. Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.
2. Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.
3. Neither the name of the University nor the names of its contributors may be used to endorse or promote products derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE REGENTS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE REGENTS OR CONTRIBUTORS BE LIABLE

FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

Copyright 1996-2018 by Thomas E. Dickey

All Rights Reserved

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE ABOVE LISTED COPYRIGHT HOLDER(S) BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

Except as contained in this notice, the name(s) of the above copyright holders shall not be used in advertising or otherwise to promote the sale, use or other dealings in this Software without prior written authorization.

1.39 sysvinit-utils 2.88dsf-59.10ubuntu1

1.39.1 Available under license :

GNU GENERAL PUBLIC LICENSE

Version 2, June 1991

Copyright (C) 1989, 1991 Free Software Foundation, Inc.,
51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA

Everyone is permitted to copy and distribute verbatim copies of this license document, but changing it is not allowed.

Preamble

The licenses for most software are designed to take away your freedom to share and change it. By contrast, the GNU General Public License is intended to guarantee your freedom to share and change free software--to make sure the software is free for all its users. This General Public License applies to most of the Free Software Foundation's software and to any other program whose authors commit to using it. (Some other Free Software Foundation software is covered by the GNU Lesser General Public License instead.) You can apply it to your programs, too.

When we speak of free software, we are referring to freedom, not price. Our General Public Licenses are designed to make sure that you have the freedom to distribute copies of free software (and charge for this service if you wish), that you receive source code or can get it if you want it, that you can change the software or use pieces of it in new free programs; and that you know you can do these things.

To protect your rights, we need to make restrictions that forbid anyone to deny you these rights or to ask you to surrender the rights. These restrictions translate to certain responsibilities for you if you distribute copies of the software, or if you modify it.

For example, if you distribute copies of such a program, whether gratis or for a fee, you must give the recipients all the rights that you have. You must make sure that they, too, receive or can get the source code. And you must show them these terms so they know their rights.

We protect your rights with two steps: (1) copyright the software, and (2) offer you this license which gives you legal permission to copy, distribute and/or modify the software.

Also, for each author's protection and ours, we want to make certain that everyone understands that there is no warranty for this free software. If the software is modified by someone else and passed on, we want its recipients to know that what they have is not the original, so that any problems introduced by others will not reflect on the original authors' reputations.

Finally, any free program is threatened constantly by software patents. We wish to avoid the danger that redistributors of a free

program will individually obtain patent licenses, in effect making the program proprietary. To prevent this, we have made it clear that any patent must be licensed for everyone's free use or not licensed at all.

The precise terms and conditions for copying, distribution and modification follow.

GNU GENERAL PUBLIC LICENSE TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

0. This License applies to any program or other work which contains a notice placed by the copyright holder saying it may be distributed under the terms of this General Public License. The "Program", below, refers to any such program or work, and a "work based on the Program" means either the Program or any derivative work under copyright law: that is to say, a work containing the Program or a portion of it, either verbatim or with modifications and/or translated into another language. (Hereinafter, translation is included without limitation in the term "modification".) Each licensee is addressed as "you".

Activities other than copying, distribution and modification are not covered by this License; they are outside its scope. The act of running the Program is not restricted, and the output from the Program is covered only if its contents constitute a work based on the Program (independent of having been made by running the Program). Whether that is true depends on what the Program does.

1. You may copy and distribute verbatim copies of the Program's source code as you receive it, in any medium, provided that you conspicuously and appropriately publish on each copy an appropriate copyright notice and disclaimer of warranty; keep intact all the notices that refer to this License and to the absence of any warranty; and give any other recipients of the Program a copy of this License along with the Program.

You may charge a fee for the physical act of transferring a copy, and you may at your option offer warranty protection in exchange for a fee.

2. You may modify your copy or copies of the Program or any portion of it, thus forming a work based on the Program, and copy and distribute such modifications or work under the terms of Section 1 above, provided that you also meet all of these conditions:

- a) You must cause the modified files to carry prominent notices stating that you changed the files and the date of any change.

b) You must cause any work that you distribute or publish, that in whole or in part contains or is derived from the Program or any part thereof, to be licensed as a whole at no charge to all third parties under the terms of this License.

c) If the modified program normally reads commands interactively when run, you must cause it, when started running for such interactive use in the most ordinary way, to print or display an announcement including an appropriate copyright notice and a notice that there is no warranty (or else, saying that you provide a warranty) and that users may redistribute the program under these conditions, and telling the user how to view a copy of this License. (Exception: if the Program itself is interactive but does not normally print such an announcement, your work based on the Program is not required to print an announcement.)

These requirements apply to the modified work as a whole. If identifiable sections of that work are not derived from the Program, and can be reasonably considered independent and separate works in themselves, then this License, and its terms, do not apply to those sections when you distribute them as separate works. But when you distribute the same sections as part of a whole which is a work based on the Program, the distribution of the whole must be on the terms of this License, whose permissions for other licensees extend to the entire whole, and thus to each and every part regardless of who wrote it.

Thus, it is not the intent of this section to claim rights or contest your rights to work written entirely by you; rather, the intent is to exercise the right to control the distribution of derivative or collective works based on the Program.

In addition, mere aggregation of another work not based on the Program with the Program (or with a work based on the Program) on a volume of a storage or distribution medium does not bring the other work under the scope of this License.

3. You may copy and distribute the Program (or a work based on it, under Section 2) in object code or executable form under the terms of Sections 1 and 2 above provided that you also do one of the following:

a) Accompany it with the complete corresponding machine-readable source code, which must be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange; or,

b) Accompany it with a written offer, valid for at least three

years, to give any third party, for a charge no more than your cost of physically performing source distribution, a complete machine-readable copy of the corresponding source code, to be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange; or,

c) Accompany it with the information you received as to the offer to distribute corresponding source code. (This alternative is allowed only for noncommercial distribution and only if you received the program in object code or executable form with such an offer, in accord with Subsection b above.)

The source code for a work means the preferred form of the work for making modifications to it. For an executable work, complete source code means all the source code for all modules it contains, plus any associated interface definition files, plus the scripts used to control compilation and installation of the executable. However, as a special exception, the source code distributed need not include anything that is normally distributed (in either source or binary form) with the major components (compiler, kernel, and so on) of the operating system on which the executable runs, unless that component itself accompanies the executable.

If distribution of executable or object code is made by offering access to copy from a designated place, then offering equivalent access to copy the source code from the same place counts as distribution of the source code, even though third parties are not compelled to copy the source along with the object code.

4. You may not copy, modify, sublicense, or distribute the Program except as expressly provided under this License. Any attempt otherwise to copy, modify, sublicense or distribute the Program is void, and will automatically terminate your rights under this License. However, parties who have received copies, or rights, from you under this License will not have their licenses terminated so long as such parties remain in full compliance.

5. You are not required to accept this License, since you have not signed it. However, nothing else grants you permission to modify or distribute the Program or its derivative works. These actions are prohibited by law if you do not accept this License. Therefore, by modifying or distributing the Program (or any work based on the Program), you indicate your acceptance of this License to do so, and all its terms and conditions for copying, distributing or modifying the Program or works based on it.

6. Each

time you redistribute the Program (or any work based on the Program), the recipient automatically receives a license from the original licensor to copy, distribute or modify the Program subject to these terms and conditions. You may not impose any further restrictions on the recipients' exercise of the rights granted herein. You are not responsible for enforcing compliance by third parties to this License.

7. If, as a consequence of a court judgment or allegation of patent infringement or for any other reason (not limited to patent issues), conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot distribute so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not distribute the Program at all. For example, if a patent license would not permit royalty-free redistribution of the Program by all those who receive copies directly or indirectly through you, then the only way you could satisfy both it and this License would be to refrain entirely from distribution of the Program.

If any portion of this section is held invalid or unenforceable under any particular circumstance, the balance of the section is intended to apply and the section as a whole is intended to apply in other circumstances.

It is not the purpose of this section to induce you to infringe any patents or other property right claims or to contest validity of any such claims; this section has the sole purpose of protecting the integrity of the free software distribution system, which is implemented by public license practices. Many people have made generous contributions to the wide range of software distributed through that system in reliance on consistent application of that system; it is up to the author/donor to decide if he or she is willing to distribute software through any other system and a licensee cannot impose that choice.

This section is intended to make thoroughly clear what is believed to be a consequence of the rest of this License.

8. If the distribution and/or use of the Program is restricted in certain countries either by patents or by copyrighted interfaces, the original copyright holder who places the Program under this License may add an explicit geographical distribution limitation excluding those countries, so that distribution is permitted only in or among

countries not thus excluded. In such case, this License incorporates the limitation as if written in the body of this License.

9. The Free Software Foundation may publish revised and/or new versions of the General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Program specifies a version number of this License which applies to it and "any later version", you have the option of following the terms and conditions either of that version or of any later version published by the Free Software Foundation. If the Program does not specify a version number of this License, you may choose any version ever published by the Free Software Foundation.

10. If you wish to incorporate parts of the Program into other free programs whose distribution conditions are different, write to the author to ask for permission. For software which is copyrighted by the Free Software Foundation, write to the Free Software Foundation; we sometimes make exceptions for this. Our decision will be guided by the two goals of preserving the free status of all derivatives of our free software and of promoting the sharing and reuse of software generally.

NO WARRANTY

11. BECAUSE THE PROGRAM IS LICENSED FREE OF CHARGE, THERE IS NO WARRANTY FOR THE PROGRAM, TO THE EXTENT PERMITTED BY APPLICABLE LAW.

EXCEPT WHEN

OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE PROGRAM "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE PROGRAM IS WITH YOU. SHOULD THE PROGRAM PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

12. IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY AND/OR REDISTRIBUTE THE PROGRAM AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE PROGRAM (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE PROGRAM TO OPERATE WITH ANY OTHER PROGRAMS), EVEN

IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Programs

If you develop a new program, and you want it to be of the greatest possible use to the public, the best way to achieve this is to make it free software which everyone can redistribute and change under these terms.

To do so, attach the following notices to the program. It is safest to attach them to the start of each source file to most effectively convey the exclusion of warranty; and each file should have at least the "copyright" line and a pointer to where the full notice is found.

<one line to give the program's name and a brief idea of what it does.>

Copyright (C) <year> <name of author>

This program is free software; you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation; either version 2 of the License, or
(at your option) any later version.

This program is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details.

You should have received a copy of the GNU General Public License along with this program; if not, write to the Free Software Foundation, Inc., 51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA.

Also add information on how to contact you by electronic and paper mail.

If the program is interactive, make it output a short notice like this when it starts in an interactive mode:

```
Gnomovision version 69, Copyright (C) year name of author
Gnomovision comes with ABSOLUTELY NO WARRANTY; for details type `show w'.
This is free software, and you are welcome to redistribute it
under certain conditions; type `show c' for details.
```

The hypothetical commands `show w' and `show c' should show the appropriate parts of the General Public License. Of course, the commands you use may be called something other than `show w' and `show c'; they could even be mouse-clicks or menu items--whatever suits your program.

You should also get your employer (if you work as a programmer) or your school, if any, to sign a "copyright disclaimer" for the program, if necessary. Here is a sample; alter the names:

Yoyodyne, Inc., hereby disclaims all copyright interest in the program
'Gnomovision' (which makes passes at compilers) written by James Hacker.

<signature of Ty Coon>, 1 April 1989

Ty Coon, President of Vice

This General Public License does not permit incorporating your program into proprietary programs. If your program is a subroutine library, you may consider it more useful to permit linking proprietary applications with the library. If this is what you want to do, use the GNU Lesser General Public License instead of this License.

Sysvinit is Copyright (C) 1991-2004 Miquel van Smoorenburg

This program is free software; you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation; either version 2 of the License, or (at your option) any later version.

This program is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details.

You should have received a copy of the GNU General Public License along with this program; if not, write to the Free Software Foundation, Inc., 51 Franklin St, Fifth Floor, Boston, MA 02110-1301 USA

On Debian GNU/Linux systems, the complete text of the GNU General Public License can be found in `~/usr/share/common-licenses/GPL-2'`.

Send patches to sysvinit-devel@nongnu.org

The of the start-stop-daemon

- * A rewrite
- of the original Debian's start-stop-daemon Perl script
- * in C (faster - it is executed many times during system startup).
- *
- * Written by Marek Michalkiewicz <marekm@i17linuxb.ists.pwr.wroc.pl>,
- * public domain.

1.40 libncurses 6.1-1ubuntu1.18.04

1.40.1 Available under license :

Upstream source <https://invisible-island.net/ncurses/ncurses-examples.html>

Current ncurses maintainer: Thomas Dickey <dickey@invisible-island.net>

Files: *

Copyright: 1998-2017,2018 Free Software Foundation, Inc.

Licence: X11

Files: aclocal.m4 package

Copyright: 2010-2017,2018 by Thomas E. Dickey

Licence: X11

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, distribute with modifications, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE ABOVE COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

Except as contained in this notice, the name(s) of the above copyright holders shall not be used in advertising or otherwise to promote the sale, use or other dealings in this Software without prior written authorization.

Files: install-sh

Copyright: 1994 X Consortium

Licence: X11

Permission is hereby granted, free of charge, to any person obtaining a copy

of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE X CONSORTIUM BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

Except as contained in this notice, the name of the X Consortium shall not be used in advertising or otherwise to promote the sale, use or other dealings in this Software without prior written authorization from the X Consortium.

FSF changes to this file are in the public domain.

Calling this script install-sh is preferred over install.sh, to prevent `make` implicit rules from creating a file called install from it when there is no Makefile.

This script is compatible with the BSD install script, but was written from scratch. It can only install one file at a time, a restriction shared with many OS's install programs.

On Debian systems, the complete text of the GNU General Public License can be found in '/usr/share/common-licenses/GPL-2'

-- vile: txtmode file-encoding=utf-8

Upstream source <https://invisible-island.net/ncurses/ncurses.html>

This package is used for testing builds of ncurses.

Current ncurses maintainer: Thomas Dickey <dickey@invisible-island.net>

Files: *

Copyright: 1998-2017,2018 Free Software Foundation, Inc.

Licence: X11

Files: aclocal.m4 package

Copyright: 1996-2017,2018 by Thomas E. Dickey

Licence: X11

Files: doc/html/NCURSES-Programming-HOWTO.html

Copyright: 2001 by Pradeep Padala

Licence: X11

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, distribute with modifications, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE ABOVE COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

Except as contained in this notice, the name(s) of the above copyright holders shall not be used in advertising or otherwise to promote the sale, use or other dealings in this Software without prior written authorization.

Files: install-sh

Copyright: 1994

X Consortium

Licence: X11

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE X CONSORTIUM BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

Except as contained in this notice, the name of the X Consortium shall not be used in advertising or otherwise to promote the sale, use or other dealings in this Software without prior written authorization from the X Consortium.

Files: progs/tset.c ncurses/tinfo/read_termcap.c

Copyright: 1980,1991,1992,1993 The Regents of the University of California.

License: BSD

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

1. Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.
2. Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.
3. Neither the name of the University nor the names of its contributors may be used to endorse or promote products derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE REGENTS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE REGENTS OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

-- vile: txtmode file-encoding=utf-8

Upstream source <https://invisible-island.net/ncurses/ncurses-examples.html>

Current ncurses maintainer: Thomas Dickey <dickey@invisible-island.net>

Files: *

Copyright: 1998-2017,2018 Free Software Foundation, Inc.

Licence: X11

Files: aclocal.m4 package

Copyright: 2003-2017,2018 by Thomas E. Dickey

Licence: X11

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, distribute with modifications, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE ABOVE COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

Except as contained in this notice, the name(s) of the above copyright holders shall not be used in advertising or otherwise to promote the sale, use or other dealings in this Software without prior written authorization.

Files: install-sh

Copyright: 1994 X Consortium

Licence: X11

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE X CONSORTIUM BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

Except as contained in this notice, the name of the X Consortium shall not be used in advertising or otherwise to promote the sale, use or other dealings in this Software without prior written authorization from the X Consortium.

FSF changes to this file are in the public domain.

Calling this script install-sh is preferred over install.sh, to prevent `make` implicit rules from creating a file called install from it when there is no Makefile.

This script is compatible with the BSD install script, but was written from scratch. It can only install one file at a time, a restriction shared with many OS's install programs.

On Debian systems, the complete text of the GNU General Public License can be found in `/usr/share/common-licenses/GPL-2`

-- vile: txtmode file-encoding=utf-8

Copyright (c) 1998-2017,2018 Free Software Foundation, Inc.

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, distribute with modifications, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE ABOVE COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR

OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR
THE USE OR OTHER DEALINGS IN THE SOFTWARE.

Except as contained in this notice, the name(s) of the above copyright holders shall not be used in advertising or otherwise to promote the sale, use or other dealings in this Software without prior written authorization.

```
-- vile:txtmode fc=72
-- $Id: COPYING,v 1.6 2018/01/01 12:00:00 tom Exp $
```

This is the Debian prepackaged version of the ncurses library and terminfo utilities. ncurses/terminfo was originally written by Pavel Curtis and Zeyd M. Ben-Halim <zmbenhal@netcom.com>, and is currently held by the Free Software Foundation.

This package was put together by Vaidhyanathan G Mayilrangam <vaidhy@debian.org> and Joel Klecker <espy@debian.org>, using sources obtained from <ftp://ftp.gnu.org/gnu/ncurses/ncurses-5.0.tar.gz>. Current versions of the ncurses sources are found at <ftp://invisible-island.net/ncurses/>.

It is based somewhat on work done by Bruce Perens <Bruce@Pixar.com>, David Engel <david@elo.ods.com>. Michael Alan Dorman <mdorman@debian.org>, Richard Braakman <dark@xs4all.nl>, James Troup <jjttrou@comp.brad.ac.uk>, J.H.M. Dassen (Ray) <jdassen@wi.LeidenUniv.nl>, and Galen Hazelwood <galenh@micron.net> over various years.

Copyright (c) 1998-2018 Free Software Foundation, Inc.
Copyright 2001 by Pradeep Padala

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, distribute with modifications, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT.

IN NO EVENT SHALL THE ABOVE COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

Except

as contained in this notice, the name(s) of the above copyright holders shall not be used in advertising or otherwise to promote the sale, use or other dealings in this Software without prior written authorization.

Copyright (C) 1994 X Consortium

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE X CONSORTIUM BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

Except as contained in this notice, the name of the X Consortium shall not be used in advertising or otherwise to promote the sale, use or other dealings in this Software without prior written authorization from the X Consortium.

Copyright (c) 1980, 1991, 1992, 1993

The Regents of the University of California. All rights reserved.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

1. Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.
2. Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following

disclaimer in the documentation and/or other materials provided with the distribution.

3. Neither the name of the University nor the names of its contributors may be used to endorse or promote products derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE REGENTS AND CONTRIBUTORS ``AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE REGENTS OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

Copyright 1996-2018 by Thomas E. Dickey

All Rights Reserved

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE ABOVE LISTED COPYRIGHT HOLDER(S) BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

Except as contained in this notice, the name(s) of the above copyright holders shall not be used in advertising or otherwise to promote the sale, use or other dealings in this Software without prior written authorization.

1.41 libdebconfclient0 0.213ubuntu1

1.41.1 Available under license :

CDebConf was initially written by Randolph Chung <tausq@debian.org>

Other contributors include:

Anthony Towns <ajt@debian.org>
David Whedon <dwhedon@gordian.com>
Dan Jacobowitz <dan@debian.org>
Tollef Fog Heen <tfheen@debian.org>
Attilio Fiandrotti <fiandro@tiscali.it>
Colin Watson <cjwatson@debian.org>
Regis Boudin <regis@debian.org>

CDebConf includes ideas and code from:

debconf - The original, de facto, perl implementation
(c) Joey Hess <joeyh@debian.org>
apt - The Debian Advanced Package Tool
(c) Jason Gunthorpe <jgg@debian.org>
(derived portions are public domain)

CDebConf is copyrighted (c) 2000-2009 by Randolph Chung <tausq@debian.org>, the d-i team (see above), and Canonical Ltd. under the following license:

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

1. Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.
2. Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.

THIS SOFTWARE IS PROVIDED BY THE AUTHORS AND CONTRIBUTORS ``AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE AUTHOR OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

1.42 Isb-base 9.20170808ubuntu1

1.42.1 Available under license :

Format: <http://www.debian.org/doc/packaging-manuals/copyright-format/1.0/>

Upstream-Name: LSB implementation package

Files: *

Copyright: 2002-2010, Chris Lawrence <lawrenc@debian.org>

License: GPL-2

Files: init-functions.d/50-ubuntu-logging

Copyright: 2005-2011, Canonical Ltd.

License: GPL-2

Files: init-functions

Copyright: 2002-2009, Chris Lawrence <lawrenc@debian.org>

License: BSD-3-clause

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

1. Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.
2. Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.
3. Neither the name of the author nor the names of other contributors may be used to endorse or promote products derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE REGENTS AND CONTRIBUTORS ``AS IS'' AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE REGENTS OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

License: GPL-2

This program is free software; you can redistribute it and/or modify it under the terms of the GNU General Public

License as published by the

Free Software Foundation;
version 2 dated June 1991.

.
This program is distributed in the hope that it will be
useful, but WITHOUT ANY WARRANTY; without even the implied
warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR
PURPOSE. See the GNU General Public License for more
details.

.
You should have received a copy of the GNU General Public
License along with this package; if not, write to the Free
Software Foundation, Inc., 51 Franklin St, Fifth Floor,
Boston, MA 02110-1301 USA

.
On Debian systems, the full text of the GNU General Public
License version 2 can be found in the file
'/usr/share/common-licenses/GPL-2'.

1.43 util-linux 2.31.1-0.4ubuntu3.7

1.43.1 Available under license :

Format: <http://www.debian.org/doc/packaging-manuals/copyright-format/1.0/>

Upstream-Name: util-linux

Upstream-Contact: util-linux@vger.kernel.org

Source: <https://www.kernel.org/pub/linux/utils/util-linux/>

Files: *

Copyright: Michal Luscon <mluscon@redhat.com>

1986 Gary S. Brown

1990 Gordon Irlam (gordoni@cs.ua.oz.au)

1991, 1992 Linus Torvalds

1991-2004 Miquel van Smoorenburg

1992 A. V. Le Blanc (LeBlanc@mcc.ac.uk)

1992-1997 Michael K. Johnson, johnsonm@redhat.com

1993, 1994, 1995, 1996, 1997, 1998, 1999, 2000, 2001, 2002,

2003, 2004, 2005, 2008 Theodore Ts'o <tytso@mit.edu>

1994 Kevin E. Martin (martin@cs.unc.edu)

1994 Salvatore Valente <svalente@mit.edu>

1994,1996 Alessandro Rubini (rubini@ipvvis.unipv.it)

1994-2005 Jeff Tranter (tranter@pobox.com)

1995, 1999, 2000 Andries E. Brouwer <aeb@cw.nl>

1997-2005 Frodo Looijaard

<frodo@frodo.looijaard.name>

1998 Danek Duvall <duvall@alumni.princeton.edu>

1999 Andreas Dilger

1999-2002 Transmeta Corporation

1999, 2000, 2002-2009, 2010, 2011, 2012, 2014 Red Hat, Inc.

2000 Werner Almesberger
2004-2006 Michael Holzt, kju -at- fqdn.org
2005 Adrian Bunk
2007-2014 Karel Zak <kzak@redhat.com>
2007, 2011 SuSE LINUX Products GmbH
2008 Cai Qian <qcai@redhat.com>
2008 Hayden A. James (hayden.james@gmail.com)
2008 James Youngman <jay@gnu.org>
2008 Roy Peled, the.roy.peled -at- gmail.com
2009 Mikhail Gusarov <dottedmag@dottedmag.net>
2010, 2011, 2012 Davidlohr Bueso <dave@gnu.org>
2010 Jason Borden <jborden@bluehost.com>A
2010 Hajime Taira <htaira@redhat.com>
2010 Masatake Yamato <yamato@redhat.com>
2011 IBM Corp.
2012 Andy Lutomirski <luto@amacapital.net>
2012 Lennart Poettering
2012 Sami Kerola <kerolasa@iki.fi>
2012 Cody Maloney <cmaloney@theoreticalchaos.com>
2012 Werner Fink <werner@suse.de>
2013,2014 Ondrej Oprala <ooprala@redhat.com>

License: GPL-2+

Files: schedutils/ionice.c

Copyright: 2005 Jens Axboe <jens@axboe.dk>

License: GPL-2

Files: schedutils/chrt.c

 schedutils/taskset.c

Copyright: 2004 Robert Love <rml@tech9.net>

 2010 Karel Zak <kzak@redhat.com>

License: GPL-2

Files: disk-utils/raw.c

Copyright: 1999, 2000, Red Hat Software

License: GPL-2

Files: sys-utils/nsenter.c

Copyright: 2012-2013 Eric Biederman <ebiederm@xmission.com>

License: GPL-2

Files: disk-utils/mkfs.minix.c

 disk-utils/mkswap.c

Copyright: 1991, 1992 Linus Torvalds

License: GPL-2

Files: lib/at.c

 lib/blkdev.c

lib/loopdev.c
lib/sysfs.c
lib/ttyutils.c
lib/xgetpass.c
misc-utils/mcookie.c
sys-utils/setsid.c
text-utils/line.c

Copyright:

n/a

License: public-domain

Files: login-utils/vipw.c

misc-utils/cal.c
misc-utils/kill.c
misc-utils/logger.c
misc-utils/look.c
misc-utils/whereis.c
sys-utils/renice.c
term-utils/mesg.c
term-utils/script.c
term-utils/ttymsg.c
term-utils/wall.c
term-utils/write.c
text-utils/col.c
text-utils/colcrt.c
text-utils/colrm.c
text-utils/column.c
text-utils/hexdump.c
text-utils/hexdump.h
text-utils/hexdump-conv.c
text-utils/hexdump-display.c
text-utils/hexdump-parse.c
text-utils/rev.c
text-utils/ul.c

Copyright: 1980, 1983, 1987, 1988, 1989, 1990, 1991, 1992, 1993, 1994

The Regents of the University of California

2014 Sami Kerola <kerolasa@iki.fi>

2014 Karel Zak <kzak@redhat.com>

License: BSD-4-clause

Files: text-utils/tailf.c

Copyright: 1996, 2003 Rickard E. Faith (faith@acm.org)

License: MIT

Files:

sys-utils/flock.c

Copyright: 2003-2005 H. Peter Anvin

License: MIT

Files: text-utils/pg.c
Copyright: 2000-2001 Gunnar Ritter
License: BSD-2-clause

Files: login-utils/last-deprecated.c
Copyright: 1987 Regents of the University of California
License: BSD-2-clause

Files: login-utils/login.c
Copyright: 1980, 1987, 1988 The Regents of the University of California.
2011 Karel Zak <kzak@redhat.com>
License: BSD-2-clause

Files: login-utils/logindefs.c
Copyright: 2003, 2004, 2005 Thorsten Kukuk
License: BSD-3-clause

Files: libuuid/*
libuuid/src/*
libuuid/man/*
Copyright: 1996, 1997, 1998, 1999, 2007 Theodore Ts'o.
1999 Andreas Dilger (adilger@enel.ucalgary.ca)
License: BSD-3-clause

Files: lib/procutils.c
include/xalloc.h
Copyright: 2010, 2011 Davidlohr Bueso <dave@gnu.org>
License: LGPL-2+

Files: */colors.*
Copyright: 2012 Ondrej Oprala <oprala@redhat.com>
2012-2014 Karel Zak <kzak@redhat.com>
License: LGPL-2+

Files: login-utils/setpwnam.h
login-utils/setpwnam.c
Copyright: 1994 Martin Schulze <joe@infodrom.north.de>
1994 Salvatore Valente <svalente@mit.edu>
License: LGPL-2+

Files: libfdisk/*
libfdisk/src/*
Copyright: 2007-2013 Karel Zak <kzak@redhat.com>
2012 Davidlohr Bueso <dave@gnu.org>
License: LGPL-2.1+

Files: lib/cpuset.c

/match.

lib/canonicalize.c

include/at.h

Copyright: 2008-2009, 2010, 2011, 2012 Karel Zak <kzak@redhat.com>

License: LGPL-2.1+

Files: */mbsalign.*

Copyright: 2009-2010 Free Software Foundation, Inc.

2010-2013 Karel Zak <kzak@redhat.com>

License: LGPL-2.1+

Files: */readutmp.*

Copyright: 1992-2007, 2009-2014 Free Software Foundation, Inc.

License: GPL-3+

Files: */timeutils.*

Copyright: 2010 Lennart Poettering

License: LGPL-2.1+

Files: include/list.h

Copyright: 2008 Karel Zak <kzak@redhat.com>

1999-2008 by Theodore Ts'o

License: LGPL

Files: libblkid/*

libblkid/src/*

libblkid/samples/*

libblkid/src/partitions/*

libblkid/src/superblocks/*

libblkid/src/topology/*

Copyright: 1999, 2001 Andries Brouwer

1995, 1995, 1996, 1997, 1999, 2000, 2001, 2002, 2003, 2004

Theodore Ts'o.

2001 Andreas Dilger (adilger@turbolinux.com)

2004-2008 Kay Sievers <kay.sievers@vrfy.org>

2008-2013 Karel Zak <kzak@redhat.com>

2009 Bastian Friedrich <bastian.friedrich@collax.com>

2009 Corentin Chary <corentincj@iksaif.net>

2009 Mike Hommey <mh@glandium.org>

2009 Red Hat, Inc.

2009-2010 Andreas Dilger <adilger@sun.com>

2010 Andrew Nayenko <resver@gmail.com>

2010 Jeroen Oortwijn <oortwijn@gmail.com>

2010 Jiro SEKIBA <jir@unicus.jp>

2011 Philipp Marek <philipp.marek@linbit.com>

2012 Milan Broz <mbroz@redhat.com>

2013 Alejandro Martinez Ruiz <alex@nowcomputing.com>

2013 Eric Sandeen <sandeen@redhat.com>
2013 Rolf Fokkens <rolf@fokkens.nl>
2013 Zeeshan Ali (Khattak) <zeeshanak@gnome.org>

License: LGPL-2.1+

Files: include/cpuset.h

lib/randutils.c

Copyright: *unknown*

License: LGPL

Files: misc-utils/blkid.c

Copyright: 2001 Andreas Dilger

License: LGPL

Files: libmount/*

libmount/src/*

Copyright: 2008-2012 Karel Zak <kzak@redhat.com>

License: LGPL-2.1+

Files: libmount/python/*

Copyright: 2013, Red Hat, Inc.

License: LGPL-3+

Files: libsmartcols/*

Copyright: 2009-2014 Karel Zak <kzak@redhat.com>

2014 Ondrej Oprala <oprala@redhat.com>

License: LGPL

Files: debian/*

Copyright: Guy Maor <maor@debian.org>

Sean 'Shaleh' Perry <shaleh@debian.org>

Adrian Bunk <bunk@stusta.de>

LaMont Jones <lamont@debian.org>

2014 Andreas Henriksson <andreas@fatal.se>

License: GPL-2+

License: public-domain

The files tagged with this license contains the following paragraphs:

.

No copyright

is claimed. This code is in the public domain; do with
it what you wish.

.

Written by Karel Zak <kzak@redhat.com>

License: GPL-2

This program is free software; you can redistribute it and/or modify

it under the terms of the GNU General Public License, v2, as published by the Free Software Foundation

.

This program is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details.

.

You should have received a copy of the GNU General Public License along with this program; if not, write to the Free Software Foundation, Inc., 51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA.

.

On Debian systems, the complete text of the GNU General Public License version 2 can be found in ``usr/share/common-licenses/GPL-2'`.

License: GPL-2+

This program is free software; you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation; either version 2 of the License, or (at your option) any later version.

.

This program is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details.

.

You should have received a copy of the GNU General Public License along with this program; if not, write to the Free Software Foundation, Inc., 51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA.

.

On Debian systems, the complete text of the GNU General Public License version 2 can be found in ``usr/share/common-licenses/GPL-2'`.

License: GPL-3+

This program is free software: you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation; either version 3 of the License, or (at your option) any later version.

.

This program is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details.

.

You should have received a copy of the GNU General Public License along with this program. If not, see <http://www.gnu.org/licenses/>.

.
On Debian systems, the complete text of the GNU General Public License version 3 can be found in `~/usr/share/common-licenses/GPL-3'`.

License: BSD-2-clause

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

1. Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.
2. Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.

License: BSD-3-clause

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

- .
- 1) Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.
 - 2) Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.
 - 3) Neither the name of the ORGANIZATION nor the names of its contributors may be used to endorse or promote products derived from this software without specific prior written permission.
- .

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED.

IN NO EVENT SHALL THE COPYRIGHT HOLDER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

License: BSD-4-clause

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

1. Redistributions of source code must retain the above copyright

- notice, this list of conditions and the following disclaimer.
2. Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.
 3. All advertising materials mentioning features or use of this software must display the following acknowledgement:
This product includes software developed by the University of California, Berkeley and its contributors.
 4. Neither the name of the University nor the names of its contributors may be used to endorse or promote products derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE REGENTS AND CONTRIBUTORS ``AS IS'' AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE REGENTS OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

License: LGPL

This file may be redistributed under the terms of the GNU Lesser General Public License.

On Debian systems, the complete text of the GNU Lesser General Public License can be found in `/usr/share/common-licenses/LGPL`.

License: LGPL-2+

This program is free software: you can redistribute it and/or modify it under the terms of the GNU Lesser General Public License as published by the Free Software Foundation, either version 2 of the License, or (at your option) any later version.

This program is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU Lesser General Public License for more details.

You should have received a copy of the GNU Lesser General Public License along with this program. If not, see <http://www.gnu.org/licenses/>.

The complete text of the GNU Lesser General Public License can be found in /usr/share/common-licenses/LGPL-2 file.

License: LGPL-2.1+

This program is free software; you can redistribute it and/or modify it under the terms of the GNU Lesser General Public License as published by the Free Software Foundation; either version 2.1, or (at your option) any later version.

.

This program is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU Lesser General Public License for more details.

.

You should have received a copy of the GNU Lesser General Public License along with this program; if not, write to the Free Software Foundation, Inc., 51 Franklin Street, Fifth Floor, Boston, MA 02110-1301, USA.

.

On Debian systems, the complete text of the GNU Lesser General Public License version 2.1 can be found in /usr/share/common-licenses/LGPL-2.1.

License: LGPL-3+

This package is free software; you can redistribute it and/or modify it under the terms of the GNU Lesser General Public License as published by the Free Software Foundation; either version 3 of the License, or (at your option) any later version.

.

This package is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU Lesser General Public License for more details.

.

You should have received a copy of the GNU General Public License along with this program. If not, see <<http://www.gnu.org/licenses/>>.

.

On Debian systems, the complete text of the GNU Lesser General Public License can be found in "/usr/share/common-licenses/LGPL-3".

License: MIT

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

GNU GENERAL PUBLIC LICENSE

Version 2, June 1991

Copyright (C) 1989, 1991 Free Software Foundation, Inc.,
51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA
Everyone is permitted to copy and distribute verbatim copies
of this license document, but changing it is not allowed.

Preamble

The licenses for most software are designed to take away your freedom to share and change it. By contrast, the GNU General Public License is intended to guarantee your freedom to share and change free software--to make sure the software is free for all its users. This General Public License applies to most of the Free Software Foundation's software and to any other program whose authors commit to using it. (Some other Free Software Foundation software is covered by the GNU Lesser General Public License instead.) You can apply it to your programs, too.

When we speak of free software, we are referring to freedom, not price.

Our General Public Licenses are designed to make sure that you have the freedom to distribute copies of free software (and charge for this service if you wish), that you receive source code or can get it if you want it, that you can change the software or use pieces of it in new free programs; and that you know you can do these things.

To protect your rights, we need to make restrictions that forbid anyone to deny you these rights or to ask you to surrender the rights. These restrictions translate to certain responsibilities for you if you distribute copies of the software, or if you modify it.

For example, if you distribute copies of such a program, whether gratis or for a fee, you must give the recipients all the rights that you have. You must make sure that they, too, receive or can get the

source code. And you must show them these terms so they know their rights.

We protect your rights with two steps: (1) copyright the software, and (2) offer you this license which gives you legal permission to copy, distribute and/or modify the software.

Also, for each author's protection and ours, we want to make certain that everyone understands that there is no warranty for this free software. If the software is modified by someone else and passed on, we want its recipients to know that what they have is not the original, so that any problems introduced by others will not reflect on the original authors' reputations.

Finally, any free program is threatened constantly by software patents. We wish to avoid the danger that redistributors of a free program will individually obtain patent licenses, in effect making the program proprietary. To prevent this, we have made it clear that any patent must be licensed for everyone's free use or not licensed at all.

The precise terms and conditions for copying, distribution and modification follow.

GNU GENERAL PUBLIC LICENSE TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

0. This License applies to any program or other work which contains a notice placed by the copyright holder saying it may be distributed under the terms of this General Public License. The "Program", below, refers to any such program or work, and a "work based on the Program" means either the Program or any derivative work under copyright law: that is to say, a work containing the Program or a portion of it, either verbatim or with modifications and/or translated into another language. (Hereinafter, translation is included without limitation in the term "modification".) Each licensee is addressed as "you".

Activities other than copying, distribution and modification are not covered by this License; they are outside its scope. The act of running the Program is not restricted, and the output from the Program is covered only if its contents constitute a work based on the Program (independent of having been made by running the Program). Whether that is true depends on what the Program does.

1. You may copy and distribute verbatim copies of the Program's source code as you receive it, in any medium, provided that you conspicuously and appropriately publish on each copy an appropriate

copyright notice and disclaimer of warranty; keep intact all the notices that refer to this License and to the absence of any warranty; and give any other recipients of the Program a copy of this License along with the Program.

You may charge a fee for the physical act of transferring a copy, and you may at your option offer warranty protection in exchange for a fee.

2. You may modify your copy or copies of the Program or any portion of it, thus forming a work based on the Program, and copy and distribute such modifications or work under the terms of Section 1 above, provided that you also meet all of these conditions:

a) You must cause the modified files to carry prominent notices stating that you changed the files and the date of any change.

b) You must cause any work that you distribute or publish, that in whole or in part contains or is derived from the Program or any part thereof, to be licensed as a whole at no charge to all third parties under the terms of this License.

c) If the modified program normally reads commands interactively when run, you must cause it, when started running for such interactive use in the most ordinary way, to print or display an announcement including an appropriate copyright notice and a notice that there is no warranty (or else, saying that you provide a warranty) and that users may redistribute the program under these conditions, and telling the user how to view a copy of this License. (Exception: if the Program itself is interactive but does not normally print such an announcement, your work based on the Program is not required to print an announcement.)

These requirements apply to the modified work as a whole. If identifiable sections of that work are not derived from the Program, and can be reasonably considered independent and separate works in themselves, then this License, and its terms, do not apply to those sections when you distribute them as separate works. But when you distribute the same sections as part of a whole which is a work based on the Program, the distribution of the whole must be on the terms of this License, whose permissions for other licensees extend to the entire whole, and thus to each and every part regardless of who wrote it.

Thus, it is not the intent of this section to claim rights or contest your rights to work written entirely by you; rather, the intent is to exercise the right to control the distribution of derivative or collective works based on the Program.

In addition, mere aggregation of another work not based on the Program with the Program (or with a work based on the Program) on a volume of a storage or distribution medium does not bring the other work under the scope of this License.

3. You may copy and distribute the Program (or a work based on it, under Section 2) in object code or executable form under the terms of Sections 1 and 2 above provided that you also do one of the following:

a) Accompany it with the complete corresponding machine-readable source code, which must be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange; or,

b) Accompany it with a written offer, valid for at least three years, to give any third party, for a charge no more than your cost of physically performing source distribution, a complete machine-readable copy of the corresponding source code, to be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange; or,

c) Accompany it with the information you received as to the offer to distribute corresponding source code. (This alternative is allowed only for noncommercial distribution and only if you received the program in object code or executable form with such an offer, in accord with Subsection b above.)

The source code for a work means the preferred form of the work for making modifications to it. For an executable work, complete source code means all the source code for all modules it contains, plus any associated interface definition files, plus the scripts used to control compilation and installation of the executable. However, as a special exception, the source code distributed need not include anything that is normally distributed (in either source or binary form) with the major components (compiler, kernel, and so on) of the operating system on which the executable runs, unless that component itself accompanies the executable.

If distribution of executable or object code is made by offering access to copy from a designated place, then offering equivalent access to copy the source code from the same place counts as distribution of the source code, even though third parties are not compelled to copy the source along with the object code.

4. You may not copy, modify, sublicense, or distribute the Program except as expressly provided under this License. Any attempt

otherwise to copy, modify, sublicense or distribute the Program is void, and will automatically terminate your rights under this License. However, parties who have received copies, or rights, from you under this License will not have their licenses terminated so long as such parties remain in full compliance.

5. You are not required to accept this License, since you have not signed it. However, nothing else grants you permission to modify or distribute the Program or its derivative works. These actions are prohibited by law if you do not accept this License. Therefore, by modifying or distributing the Program (or any work based on the Program), you indicate your acceptance of this License to do so, and all its terms and conditions for copying, distributing or modifying the Program or works based on it.

6. Each time you redistribute the Program (or any work based on the Program), the recipient automatically receives a license from the original licensor to copy, distribute or modify the Program subject to these terms and conditions. You may not impose any further restrictions on the recipients' exercise of the rights granted herein. You are not responsible for enforcing compliance by third parties to this License.

7. If, as a consequence of a court judgment or allegation of patent infringement or for any other reason (not limited to patent issues), conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot distribute so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not distribute the Program at all. For example, if a patent license would not permit royalty-free redistribution of the Program by all those who receive copies directly or indirectly through you, then the only way you could satisfy both it and this License would be to refrain entirely from distribution of the Program.

If any portion of this section is held invalid or unenforceable under any particular circumstance, the balance of the section is intended to apply and the section as a whole is intended to apply in other circumstances.

It is not the purpose of this section to induce you to infringe any patents or other property right claims or to contest validity of any such claims; this section has the sole purpose of protecting the integrity of the free software distribution system, which is implemented by public license practices. Many people have made

generous contributions to the wide range of software distributed through that system in reliance on consistent application of that system; it is up to the author/donor to decide if he or she is willing to distribute software through any other system and a licensee cannot impose that choice.

This section is intended to make thoroughly clear what is believed to be a consequence of the rest of this License.

8. If the distribution and/or use of the Program is restricted in certain countries either by patents or by copyrighted interfaces, the original copyright holder who places the Program under this License may add an explicit geographical distribution limitation excluding those countries, so that distribution is permitted only in or among countries not thus excluded. In such case, this License incorporates the limitation as if written in the body of this License.

9. The Free Software Foundation may publish revised and/or new versions of the General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Program specifies a version number of this License which applies to it and "any later version", you have the option of following the terms and conditions either of that version or of any later version published by the Free Software Foundation. If the Program does not specify a version number of this License, you may choose any version ever published by the Free Software Foundation.

10. If you wish to incorporate parts of the Program into other free programs whose distribution conditions are different, write to the author to ask for permission. For software which is copyrighted by the Free Software Foundation, write to the Free Software Foundation; we sometimes make exceptions for this. Our decision will be guided by the two goals of preserving the free status of all derivatives of our free software and of promoting the sharing and reuse of software generally.

NO WARRANTY

11. BECAUSE THE PROGRAM IS LICENSED FREE OF CHARGE, THERE IS NO WARRANTY FOR THE PROGRAM, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE PROGRAM "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF

MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE PROGRAM IS WITH YOU. SHOULD THE PROGRAM PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

12. IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY AND/OR REDISTRIBUTE THE PROGRAM AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE PROGRAM (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE PROGRAM TO OPERATE WITH ANY OTHER PROGRAMS), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Programs

If you develop a new program, and you want it to be of the greatest possible use to the public, the best way to achieve this is to make it free software which everyone can redistribute and change under these terms.

To do so, attach the following notices to the program. It is safest to attach them to the start of each source file to most effectively convey the exclusion of warranty; and each file should have at least the "copyright" line and a pointer to where the full notice is found.

<one line to give the program's name and a brief idea of what it does.>
Copyright (C) <year> <name of author>

This program is free software; you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation; either version 2 of the License, or (at your option) any later version.

This program is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details.

You should have received a copy of the GNU General Public License along with this program; if not, write to the Free Software Foundation, Inc., 51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA.

Also add information on how to contact you by electronic and paper mail.

If the program is interactive, make it output a short notice like this when it starts in an interactive mode:

```
Gnomovision version 69, Copyright (C) year name of author
Gnomovision comes with ABSOLUTELY NO WARRANTY; for details type `show w'.
This is free software, and you are welcome to redistribute
it
under certain conditions; type `show c' for details.
```

The hypothetical commands ``show w'` and ``show c'` should show the appropriate parts of the General Public License. Of course, the commands you use may be called something other than ``show w'` and ``show c'`; they could even be mouse-clicks or menu items--whatever suits your program.

You should also get your employer (if you work as a programmer) or your school, if any, to sign a "copyright disclaimer" for the program, if necessary. Here is a sample; alter the names:

```
Yoyodyne, Inc., hereby disclaims all copyright interest in the program
`Gnomovision' (which makes passes at compilers) written by James Hacker.
```

```
<signature of Ty Coon>, 1 April 1989
Ty Coon, President of Vice
```

This General Public License does not permit incorporating your program into proprietary programs. If your program is a subroutine library, you may consider it more useful to permit linking proprietary applications with the library. If this

is what you want to do, use the GNU Lesser General Public License instead of this License.

This library is free software; you can redistribute it and/or modify it under the terms of the GNU Lesser General Public License as published by the Free Software Foundation; either version 2.1 of the License, or (at your option) any later version.

The complete text of the license is available in the `../Documentation/licenses/COPYING.LGPLv2.1` file.

```
WEV @@ WEV[B "1
```

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

1. Redistributions of source code must retain the above copyright notice, and the entire permission notice in its entirety, including the disclaimer of warranties.
2. Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the

documentation and/or other materials provided with the distribution.

- 3. The name of the author may not be used to endorse or promote products derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED ``AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, ALL OF WHICH ARE HEREBY DISCLAIMED. IN NO EVENT SHALL THE AUTHOR BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL

DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF NOT ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

x ?"U@,5 @mISmIN<GimCN7g1u|E
 43mI,5WEV @@ WEV @mImImIAmImImI0mImImI*mImI
 A0mImImI...
 lost+found...

;9GimCN7g

!"#\$%&'()*+,-
 ./0123456789:;<=>?@ABCDEFGHIJKLMNOPQRSTUVWXYZ[\]^_`abcdefghijklmnopqrstuvwxyz{|}~

!"#\$%&'()*+,-
 ./0123456789:;<=>?@ABCDEFGHIJKLMNOPQRSTUVWXYZ[\]^_`abcdefghijklmnopqrstuvwxyz{|}~

!"#\$%&'()*+,-
 ./0123456789:;<=>?@ABCDEFGHIJKLMNOPQRSTUVWXYZ[\]^_`abcdefghijklmnopqrstuvwxyz{|}~

!"#\$%&'()*+,-
 ./0123456789:;<=>?@ABCDEFGHIJKLMNOPQRSTUVWXYZ[\]^_`abcdefghijklmnopqrstuvwxyz{|}~WEV @@
 WEV[B "1
 /*

- * Copyright (c) 1989 The Regents of the University of California.
- * All rights reserved.
- *
- * Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:
- * 1. Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.
- * 2. Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the

- * documentation and/or other materials provided with the distribution.
- * 3. All advertising materials mentioning features or use of this software
- * must display the following acknowledgement:
- * This product includes software developed by the University of
- * California, Berkeley and its contributors.
- * 4. Neither the name of the University nor the names of its contributors
- * may be used to endorse or promote products derived from this software
- *
 * without specific prior written permission.
- *
 * THIS SOFTWARE IS PROVIDED BY THE REGENTS AND CONTRIBUTORS ``AS IS" AND
- * ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE
- * IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE
- * ARE DISCLAIMED. IN NO EVENT SHALL THE REGENTS OR CONTRIBUTORS BE LIABLE
- * FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL
- * DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS
- * OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION)
- * HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT
- * LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY
- * OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF
- * SUCH DAMAGE.
- */

This library is free software; you can redistribute it and/or modify it under the terms of the Modified BSD License.

The complete text of the license is available in the
 ../Documentation/licenses/COPYING.BSD-3 file.

1.44 selinux 2.7-2build2

1.44.1 Available under license :

This is the Debian packe for libselinux, and it is built from sources obtained from:
<http://userspace.selinuxproject.org/trac/wiki/Releases>

This package was debianized by Colin Walters <walters@debian.org> on
 Thu, 3 Jul 2003 17:10:57 -0400.

This library (libselinux) is public domain software, i.e. not copyrighted.

Warranty Exclusion

You agree that this software is a non-commercially developed program that may contain "bugs" (as that term is used in the industry) and that it may not function as intended. The software is licensed "as is". NSA makes no, and hereby expressly disclaims all, warranties, express, implied, statutory, or otherwise with respect to the software, including noninfringement and the implied

warranties of merchantability and fitness for a particular purpose.

Limitation of Liability

In no event will NSA be liable for any damages, including loss of data, lost profits, cost of cover, or other special, incidental, consequential, direct or indirect damages arising from the software or the use thereof, however caused and on any theory of liability. This limitation will apply even if NSA has been advised of the possibility of such damage. You acknowledge that this is a reasonable allocation of risk.

However, one file (utils/avcstat.c) is
Copyright: 2004 Red Hat, Inc., James Morris <jmorris@redhat.com>
and is distributed under the terms of the GNU General Public License, version 2.

In addition, The Debian specific package was modified to include an excerpt from the GNU libc package in the file
utils/ia64-inline-syscall.h. The GNU C Library is distributed under the terms of the GNU Lesser General Public License as published by the Free Software Foundation; either version 2.1 of the License, or (at your option) any later version.

You should have received
a copy of the GNU Lesser General Public
License along with the GNU C Library; if not, write to
Free Software Foundation, Inc., 51 Franklin St, Fifth Floor,
Boston, MA 02110-1301, USA.

On Debian systems, the complete text of the GNU Library
General Public License can be found in ``usr/share/common-licenses/LGPL-2.1'`.

This package is maintained by Manoj Srivastava <srivasta@debian.org>.

The Debian specific changes are 2005, 2006, Manoj Srivastava
<srivasta@debian.org>, and distributed under the terms of the GNU
General Public License, version 2.

On Debian GNU/Linux systems, the complete text of the GNU General
Public License can be found in ``usr/share/common-licenses/GPL-2'`.

A copy of the GNU General Public License is also available at

<URL:<http://www.gnu.org/copyleft/gpl.html>>. You may also obtain it by writing to the Free Software Foundation, Inc., 51 Franklin St, Fifth Floor, Boston, MA 02110-1301, USA.

Manoj Srivastava <svivasta@debian.org>
arch-tag: d4250e44-a0e0-4ee0-adb9-2bd74f6eeb27

1.45 audit 2.8.2-1ubuntu1.1

1.45.1 Available under license :

GNU LESSER GENERAL PUBLIC LICENSE
Version 2.1, February 1999

Copyright (C) 1991, 1999 Free Software Foundation, Inc.
51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA
Everyone is permitted to copy and distribute verbatim copies of this license document, but changing it is not allowed.

[This is the first released version of the Lesser GPL. It also counts as the successor of the GNU Library Public License, version 2, hence the version number 2.1.]

Preamble

The licenses for most software are designed to take away your freedom to share and change it. By contrast, the GNU General Public Licenses are intended to guarantee your freedom to share and change free software--to make sure the software is free for all its users.

This license, the Lesser General Public License, applies to some specially designated software packages--typically libraries--of the Free Software Foundation and other authors who decide to use it. You can use it too, but we suggest you first think carefully about whether this license or the ordinary General Public License is the better strategy to use in any particular case, based on the explanations below.

When we speak of free software, we are referring to freedom of use, not price. Our General Public Licenses are designed to make sure that you have the freedom to distribute copies of free software (and charge for this service if you wish); that you receive source code or can get it if you want it; that you can change the software and use pieces of it in new free programs; and that you are informed that you can do these things.

To protect your rights, we need to make restrictions that forbid distributors to deny you these rights or to ask you to surrender these rights. These restrictions translate to certain responsibilities for you if you distribute copies of the library or if you modify it.

For example, if you distribute copies of the library, whether gratis or for a fee, you must give the recipients all the rights that we gave you. You must make sure that they, too, receive or can get the source code. If you link other code with the library, you must provide complete object files to the recipients, so that they can relink them with the library after making changes to the library and recompiling it. And you must show them these terms so they know their rights.

We protect your rights with a two-step method: (1) we copyright the library, and (2) we offer you this license, which gives you legal permission to copy, distribute and/or modify the library.

To protect each distributor, we want to make it very clear that there is no warranty for the free library. Also, if the library is modified by someone else and passed on, the recipients should know that what they have is not the original version, so that the original author's reputation will not be affected by problems that might be introduced by others.

^L

Finally, software patents pose a constant threat to the existence of any free program. We wish to make sure that a company cannot effectively restrict the users of a free program by obtaining a restrictive license from a patent holder. Therefore, we insist that any patent license obtained for a version of the library must be consistent with the full freedom of use specified in this license.

Most GNU software, including some libraries, is covered by the ordinary GNU General Public License. This license, the GNU Lesser General Public License, applies to certain designated libraries, and is quite different from the ordinary General Public License. We use this license for certain libraries in order to permit linking those libraries into non-free programs.

When a program is linked with a library, whether statically or using a shared library, the combination of the two is legally speaking a combined work, a derivative of the original library. The ordinary General Public License therefore permits such linking only if the entire combination fits its criteria of freedom. The Lesser General Public License permits more lax criteria for linking other code with

the library.

We call this license the "Lesser" General Public License because it does Less to protect the user's freedom than the ordinary General Public License. It also provides other free software developers Less of an advantage over competing non-free programs. These disadvantages are the reason we use the ordinary General Public License for many libraries. However, the Lesser license provides advantages in certain special circumstances.

For example, on rare occasions, there may be a special need to encourage the widest possible use of a certain library, so that it becomes a de-facto standard. To achieve this, non-free programs must be allowed to use the library. A more frequent case is that a free library does the same job as widely used non-free libraries. In this case, there is little to gain by limiting the free library to free software only, so we use the Lesser General Public License.

In other cases, permission to use a particular library in non-free programs enables a greater number of people to use a large body of free software. For example, permission to use the GNU C Library in non-free programs enables many more people to use the whole GNU operating system, as well as its variant, the GNU/Linux operating system.

Although the Lesser General Public License is Less protective of the users' freedom, it does ensure that the user of a program that is linked with the Library has the freedom and the wherewithal to run that program using a modified version of the Library.

The precise terms and conditions for copying, distribution and modification follow. Pay close attention to the difference between a "work based on the library" and a "work that uses the library". The former contains code derived from the library, whereas the latter must be combined with the library in order to run.

^L

GNU LESSER GENERAL PUBLIC LICENSE TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

0. This License Agreement applies to any software library or other program which contains a notice placed by the copyright holder or other authorized party saying it may be distributed under the terms of this Lesser General Public License (also called "this License"). Each licensee is addressed as "you".

A "library" means a collection of software functions and/or data prepared so as to be conveniently linked with application programs (which use some of those functions and data) to form executables.

The "Library", below, refers to any such software library or work which has been distributed under these terms. A "work based on the Library" means either the Library or any derivative work under copyright law: that is to say, a work containing the Library or a portion of it, either verbatim or with modifications and/or translated straightforwardly into another language. (Hereinafter, translation is included without limitation in the term "modification".)

"Source code" for a work means the preferred form of the work for making modifications to it. For a library, complete source code means all the source code for all modules it contains, plus any associated interface definition files, plus the scripts used to control compilation and installation of the library.

Activities other than copying, distribution and modification are not covered by this License; they are outside its scope. The act of running a program using the Library is not restricted, and output from such a program is covered only if its contents constitute a work based on the Library (independent of the use of the Library in a tool for writing it). Whether that is true depends on what the Library does and what the program that uses the Library does.

1. You may copy and distribute verbatim copies of the Library's complete source code as you receive it, in any medium, provided that you conspicuously and appropriately publish on each copy an appropriate copyright notice and disclaimer of warranty; keep intact all the notices that refer to this License and to the absence of any warranty; and distribute a copy of this License along with the Library.

You may charge a fee for the physical act of transferring a copy, and you may at your option offer warranty protection in exchange for a fee.

2. You may modify your copy or copies of the Library or any portion of it, thus forming a work based on the Library, and copy and distribute such modifications or work under the terms of Section 1 above, provided that you also meet all of these conditions:

- a) The modified work must itself be a software library.

b) You must cause the files modified to carry prominent notices stating that you changed the files and the date of any change.

c) You must cause the whole of the work to be licensed at no charge to all third parties under the terms of this License.

d) If a facility in the modified Library refers to a function or a table of data to be supplied by an application program that uses the facility, other than as an argument passed when the facility is invoked, then you must make a good faith effort to ensure that, in the event an application does not supply such function or table, the facility still operates, and performs whatever part of its purpose remains meaningful.

(For example, a function in a library to compute square roots has a purpose that is entirely well-defined independent of the application. Therefore, Subsection 2d requires that any application-supplied function or table used by this function must be optional: if the application does not supply it, the square root function must still compute square roots.)

These requirements apply to the modified work as a whole. If identifiable sections of that work are not derived from the Library, and

can be reasonably considered independent and separate works in themselves, then this License, and its terms, do not apply to those sections when you distribute them as separate works. But when you distribute the same sections as part of a whole which is a work based on the Library, the distribution of the whole must be on the terms of this License, whose permissions for other licensees extend to the entire whole, and thus to each and every part regardless of who wrote it.

Thus, it is not the intent of this section to claim rights or contest your rights to work written entirely by you; rather, the intent is to exercise the right to control the distribution of derivative or collective works based on the Library.

In addition, mere aggregation of another work not based on the Library with the Library (or with a work based on the Library) on a volume of a storage or distribution medium does not bring the other work under the scope of this License.

3. You may opt to apply the terms of the ordinary GNU General Public License instead of this License to a given copy of the Library. To do this, you must alter all the notices that refer to this License, so

that they refer to the ordinary GNU General Public License, version 2, instead of to this License. (If a newer version than version 2 of the ordinary GNU General Public License has appeared, then you can specify that version instead if you wish.) Do not make any other change in these notices.

^L

Once this change is made in a given copy, it is irreversible for that copy, so the ordinary GNU General Public License applies to all subsequent copies and derivative works made from that copy.

This option is useful when you wish to copy part of the code of the Library into a program that is not a library.

4. You may copy and distribute the Library (or a portion or derivative of it, under Section 2) in object code or executable form under the terms of Sections 1 and 2 above provided that you accompany it with the

complete corresponding machine-readable source code, which must be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange.

If distribution of object code is made by offering access to copy from a designated place, then offering equivalent access to copy the source code from the same place satisfies the requirement to distribute the source code, even though third parties are not compelled to copy the source along with the object code.

5. A program that contains no derivative of any portion of the Library, but is designed to work with the Library by being compiled or linked with it, is called a "work that uses the Library". Such a work, in isolation, is not a derivative work of the Library, and therefore falls outside the scope of this License.

However, linking a "work that uses the Library" with the Library creates an executable that is a derivative of the Library (because it contains portions of the Library), rather than a "work that uses the library". The executable is therefore covered by this License. Section 6 states terms for distribution of such executables.

When a "work that uses the Library" uses material from a header file that is part of the Library, the object code for the work may be a derivative work of the Library even though the source code is not. Whether this is true is especially significant if the work can be linked without the Library, or if the work is itself a library. The threshold for this to be true is not precisely defined by law.

If such an object file uses only numerical parameters, data

structure layouts and accessors, and small macros and small inline functions (ten lines or less in length), then the use of the object file is unrestricted, regardless of whether it is legally a derivative work. (Executables containing this object code plus portions of the Library will still fall under Section 6.)

Otherwise, if the work is a derivative of the Library, you may distribute

the object code for the work under the terms of Section 6.

Any executables containing that work also fall under Section 6, whether or not they are linked directly with the Library itself.

^L

6. As an exception to the Sections above, you may also combine or link a "work that uses the Library" with the Library to produce a work containing portions of the Library, and distribute that work under terms of your choice, provided that the terms permit modification of the work for the customer's own use and reverse engineering for debugging such modifications.

You must give prominent notice with each copy of the work that the Library is used in it and that the Library and its use are covered by this License. You must supply a copy of this License. If the work during execution displays copyright notices, you must include the copyright notice for the Library among them, as well as a reference directing the user to the copy of this License. Also, you must do one of these things:

a) Accompany the work with the complete corresponding machine-readable source code for the Library including whatever changes were used in the work (which must be distributed under Sections 1 and 2 above); and, if the work is an executable linked with the Library, with the complete machine-readable "work that uses the Library", as object code and/or source code, so that the user can modify the Library and then relink to produce a modified executable containing the modified Library. (It is understood that the user who changes the contents of definitions files in the Library will not necessarily be able to recompile the application to use the modified definitions.)

b) Use a suitable shared library mechanism for linking with the Library. A suitable mechanism is one that (1) uses at run time a copy of the library already present on the user's computer system, rather than copying library functions into the executable, and (2)

will operate properly with a modified version of the library, if the user installs one, as long as the modified version is interface-compatible with the version that the work was made with.

c) Accompany the work with a written offer, valid for at least three years, to give the same user the materials specified in Subsection 6a, above, for a charge no more than the cost of performing this distribution.

d) If distribution of the work is made by offering access to copy from a designated place, offer equivalent access to copy the above specified materials from the same place.

e) Verify that the user has already received a copy of these materials or that you have already sent this user a copy.

For an executable, the required form of the "work that uses the Library" must include any data and utility programs needed for reproducing the executable from it. However, as a special exception, the materials to be distributed need not include anything that is normally distributed (in either source or binary form) with the major components (compiler, kernel, and so on) of the operating system on which the executable runs, unless that component itself accompanies the executable.

It may happen that this requirement contradicts the license restrictions of other proprietary libraries that do not normally accompany the operating system. Such a contradiction means you cannot use both them and the Library together in an executable that you distribute.

^L

7. You may place library facilities that are a work based on the Library side-by-side in a single library together with other library facilities not covered by this License, and distribute such a combined library, provided that the separate distribution of the work based on the Library and of the other library facilities is otherwise permitted, and provided that you do these two things:

a) Accompany the combined library with a copy of the same work based on the Library, uncombined with any other library facilities. This must be distributed under the terms of the Sections above.

b) Give prominent notice with the combined library of the fact that part of it is a work based on the Library, and explaining where to find the accompanying uncombined form of the same work.

8. You may not copy, modify, sublicense, link with, or distribute the Library except as expressly provided under this License. Any

attempt otherwise to copy, modify, sublicense, link with, or distribute the Library is void, and will automatically terminate your rights under this License. However, parties who have received copies, or rights, from you under this License will not have their licenses terminated so long as such parties remain in full compliance.

9. You are not required to accept this License, since you have not signed it. However, nothing else grants you permission to modify or distribute the Library or its derivative works. These actions are prohibited

by law if you do not accept this License. Therefore, by modifying or distributing the Library (or any work based on the Library), you indicate your acceptance of this License to do so, and all its terms and conditions for copying, distributing or modifying the Library or works based on it.

10. Each time you redistribute the Library (or any work based on the Library), the recipient automatically receives a license from the original licensor to copy, distribute, link with or modify the Library subject to these terms and conditions. You may not impose any further restrictions on the recipients' exercise of the rights granted herein. You are not responsible for enforcing compliance by third parties with this License.

^L

11. If, as a consequence of a court judgment or allegation of patent infringement or for any other reason (not limited to patent issues), conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot distribute so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not distribute the Library at all. For example, if a patent license would not permit royalty-free redistribution of the Library by all those who receive copies directly or indirectly through you, then the only way you could satisfy both it and this License would be to refrain entirely from distribution of the Library.

If any portion of this section is held invalid or unenforceable under any particular circumstance, the balance of the section is intended to apply, and the section as a whole is intended to apply in other circumstances.

It is not the purpose of this section to induce you to infringe any patents or other property right claims or to contest validity of any such claims; this section has the sole purpose of protecting the integrity of the free software

distribution system which is implemented by public license practices. Many people have made generous contributions to the wide range of software distributed through that system in reliance on consistent application of that system; it is up to the author/donor to decide if he or she is willing to distribute software through any other system and a licensee cannot impose that choice.

This section is intended to make thoroughly clear what is believed to be a consequence of the rest of this License.

12. If the distribution and/or use of the Library is restricted in certain countries either by patents or by copyrighted interfaces, the original copyright holder who places the Library under this License may add an explicit geographical distribution limitation excluding those countries, so that distribution is permitted only in or among countries not thus excluded. In such case, this License incorporates the limitation as if written in the body of this License.

13. The Free Software Foundation may publish revised and/or new versions of the Lesser General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Library specifies a version number of this License which applies to it and "any later version", you have the option of following the terms and conditions either of that version or of any later version published by the Free Software Foundation. If the Library does not specify a license version number, you may choose any version ever published by the Free Software Foundation.

^L

14. If you wish to incorporate parts of the Library into other free programs whose distribution conditions are incompatible with these, write to the author to ask for permission. For software which is copyrighted by the Free Software Foundation, write to the Free Software Foundation; we sometimes make exceptions for this. Our decision will be guided by the two goals of preserving the free status of all derivatives of our free software and of promoting the sharing and reuse of software generally.

NO WARRANTY

15. BECAUSE THE LIBRARY IS LICENSED FREE OF CHARGE, THERE IS NO WARRANTY FOR THE LIBRARY, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR

OTHER PARTIES PROVIDE THE LIBRARY "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE LIBRARY IS WITH YOU. SHOULD THE LIBRARY PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

16. IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY AND/OR REDISTRIBUTE THE LIBRARY AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE LIBRARY (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE LIBRARY TO OPERATE WITH ANY OTHER SOFTWARE), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

END OF TERMS AND CONDITIONS

^L

How to Apply These Terms to Your New Libraries

If you develop a new library, and you want it to be of the greatest possible use to the public, we recommend making it free software that everyone can redistribute and change. You can do so by permitting redistribution under these terms (or, alternatively, under the terms of the ordinary General Public License).

To apply these terms, attach the following notices to the library. It is safest to attach them to the start of each source file to most effectively convey the exclusion of warranty; and each file should have at least the "copyright" line and a pointer to where the full notice is found.

<one line to give the library's name and a brief idea of what it does.>

Copyright (C) <year> <name of author>

This library is free software; you can redistribute it and/or modify it under the terms of the GNU Lesser General Public License as published by the Free Software Foundation; either version 2 of the License, or (at your option) any later version.

This library is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of

MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU Lesser General Public License for more details.

You should have received a copy of the GNU Lesser General Public License along with this library; if not, write to the Free Software Foundation, Inc., 51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA

Also add information on how to contact you by electronic and paper mail.

You should also get your employer (if you work as a programmer) or your school, if any, to sign a "copyright disclaimer" for the library, if necessary. Here is a sample; alter the names:

Yoyodyne, Inc., hereby disclaims all copyright interest in the library `Frob' (a library for tweaking knobs) written by James Random Hacker.

<signature of Ty Coon>, 1 April 1990
Ty Coon, President of Vice

That's all there is to it!

GNU GENERAL PUBLIC LICENSE
Version 2, June 1991

Copyright (C) 1989, 1991 Free Software Foundation, Inc.
59 Temple Place, Suite 330, Boston, MA 02111-1307 USA
Everyone is permitted to copy and distribute verbatim copies of this license document, but changing it is not allowed.

Preamble

The licenses for most software are designed to take away your freedom to share and change it. By contrast, the GNU General Public License is intended to guarantee your freedom to share and change free software--to make sure the software is free for all its users. This General Public License applies to most of the Free Software Foundation's software and to any other program whose authors commit to using it. (Some other Free Software Foundation software is covered by the GNU Library General Public License instead.) You can apply it to your programs, too.

When we speak of free software, we are referring to freedom, not price. Our General Public Licenses are designed to make sure that you have the freedom to distribute copies of free software (and charge for

this service if you wish), that you receive source code or can get it if you want it, that you can change the software or use pieces of it in new free programs; and that you know you can do these things.

To protect your rights, we need to make restrictions that forbid anyone to deny you these rights or to ask you to surrender the rights. These restrictions translate to certain responsibilities for you if you distribute copies of the software, or if you modify it.

For example, if you distribute copies of such a program, whether gratis or for a fee, you must give the recipients all the rights that you have. You must make sure that they, too, receive or can get the source code. And you must show them these terms so they know their rights.

We protect your rights with two steps: (1) copyright the software, and (2) offer you this license which gives you legal permission to copy, distribute and/or modify the software.

Also, for each author's protection and ours, we want to make certain that everyone understands that there is no warranty for this free software. If the software is modified by someone else and passed on, we want its recipients to know that what they have is not the original, so that any problems introduced by others will not reflect on the original authors' reputations.

Finally, any free program is threatened constantly by software patents. We wish to avoid the danger that redistributors of a free program will individually obtain patent licenses, in effect making the program proprietary. To prevent this, we have made it clear that any patent must be licensed for everyone's free use or not licensed at all.

The precise terms and conditions for copying, distribution and modification follow.

GNU GENERAL PUBLIC LICENSE TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

0. This License applies to any program or other work which contains a notice placed by the copyright holder saying it may be distributed under the terms of this General Public License. The "Program", below, refers to any such program or work, and a "work based on the Program" means either the Program or any derivative work under copyright law: that is to say, a work containing the Program or a portion of it, either verbatim or with modifications and/or translated into another language. (Hereinafter, translation is included without limitation in

the term "modification".) Each licensee is addressed as "you".

Activities other than copying, distribution and modification are not covered by this License; they are outside its scope. The act of running the Program is not restricted, and the output from the Program is covered only if its contents constitute a work based on the Program (independent of having been made by running the Program). Whether that is true depends on what the Program does.

1. You may copy and distribute verbatim copies of the Program's source code as you receive it, in any medium, provided that you conspicuously and appropriately publish on each copy an appropriate copyright notice and disclaimer of warranty; keep intact all the notices that refer to this License and to the absence of any warranty; and give any other recipients of the Program a copy of this License along with the Program.

You may charge a fee for the physical act of transferring a copy, and you may at your option offer warranty protection in exchange for a fee.

2. You may modify your copy or copies of the Program or any portion of it, thus forming a work based on the Program, and copy and distribute such modifications or work under the terms of Section 1 above, provided that you also meet all of these conditions:

- a) You must cause the modified files to carry prominent notices stating that you changed the files and the date of any change.
- b) You must cause any work that you distribute or publish, that in whole or in part contains or is derived from the Program or any part thereof, to be licensed as a whole at no charge to all third parties under the terms of this License.
- c) If the modified program normally reads commands interactively when run, you must cause it, when started running for such interactive use in the most ordinary way, to print or display an announcement including an appropriate copyright notice and a notice that there is no warranty (or else, saying that you provide a warranty) and that users may redistribute the program under these conditions, and telling the user how to view a copy of this License. (Exception: if the Program itself is interactive but does not normally print such an announcement, your work based on the Program is not required to print an announcement.)

These requirements apply to the modified work as a whole. If identifiable sections of that work are not derived from the Program,

and can be reasonably considered independent and separate works in themselves, then this License, and its terms, do not apply to those sections when you distribute them as separate works. But when you distribute the same sections as part of a whole which is a work based on the Program, the distribution of the whole must be on the terms of this License, whose permissions for other licensees extend to the entire whole, and thus to each and every part regardless of who wrote it.

Thus, it is not the intent of this section to claim rights or contest your rights to work written entirely by you; rather, the intent is to exercise the right to control the distribution of derivative or collective works based on the Program.

In addition, mere aggregation of another work not based on the Program with the Program (or with a work based on the Program) on a volume of a storage or distribution medium does not bring the other work under the scope of this License.

3. You may copy and distribute the Program (or a work based on it, under Section 2) in object code or executable form under the terms of Sections 1 and 2 above provided that you also do one of the following:

a) Accompany it with the complete corresponding machine-readable source code, which must be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange; or,

b) Accompany it with a written offer, valid for at least three years, to give any third party, for a charge no more than your cost of physically performing source distribution, a complete machine-readable copy of the corresponding source code, to be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange; or,

c) Accompany it with the information you received as to the offer to distribute corresponding source code. (This alternative is allowed only for noncommercial distribution and only if you received the program in object code or executable form with such an offer, in accord with Subsection b above.)

The source code for a work means the preferred form of the work for making modifications to it. For an executable work, complete source code means all the source code for all modules it contains, plus any associated interface definition files, plus the scripts used to control compilation and installation of the executable. However, as a special exception, the source code distributed need not include

anything that is normally distributed (in either source or binary form) with the major components (compiler, kernel, and so on) of the operating system on which the executable runs, unless that component itself accompanies the executable.

If distribution of executable or object code is made by offering access to copy from a designated place, then offering equivalent access to copy the source code from the same place counts as distribution of the source code, even though third parties are not compelled to copy the source along with the object code.

4. You may not copy, modify, sublicense, or distribute the Program except as expressly provided under this License. Any attempt otherwise to copy, modify, sublicense or distribute the Program is void, and will automatically terminate your rights under this License. However, parties who have received copies, or rights, from you under this License will not have their licenses terminated so long as such parties remain in full compliance.

5. You are not required to accept this License, since you have not signed it. However, nothing else grants you permission to modify or distribute the Program or its derivative works. These actions are prohibited by law if you do not accept this License. Therefore, by modifying or distributing the Program (or any work based on the Program), you indicate your acceptance of this License to do so, and all its terms and conditions for copying, distributing or modifying the Program or works based on it.

6. Each time you redistribute the Program (or any work based on the Program), the recipient automatically receives a license from the original licensor to copy, distribute or modify the Program subject to these terms and conditions. You may not impose any further restrictions on the recipients' exercise of the rights granted herein. You are not responsible for enforcing compliance by third parties to this License.

7. If, as a consequence of a court judgment or allegation of patent infringement or for any other reason (not limited to patent issues), conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot distribute so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not distribute the Program at all. For example, if a patent license would not permit royalty-free redistribution

of the Program by all those who receive copies directly or indirectly through you, then the only way you could satisfy both it and this License would be to refrain entirely from distribution of the Program.

If any portion of this section is held invalid or unenforceable under any particular circumstance, the balance of the section is intended to apply and the section as a whole is intended to apply in other circumstances.

It is not the purpose of this section to induce you to infringe any patents or other property right claims or to contest validity of any such claims; this section has the sole purpose of protecting the integrity of the free software distribution system, which is implemented by public license practices. Many people have made generous contributions to the wide range of software distributed through that system in reliance on consistent application of that system; it is up to the author/donor to decide if he or she is willing to distribute software through any other system and a licensee cannot impose that choice.

This section is intended to make thoroughly clear what is believed to be a consequence of the rest of this License.

8. If the distribution and/or use of the Program is restricted in certain countries either by patents or by copyrighted interfaces, the original copyright holder who places the Program under this License may add an explicit geographical distribution limitation excluding those countries, so that distribution is permitted only in or among countries not thus excluded. In such case, this License incorporates the limitation as if written in the body of this License.

9. The Free Software Foundation may publish revised and/or new versions of the General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Program specifies a version number of this License which applies to it and "any later version", you have the option of following the terms and conditions either of that version or of any later version published by the Free Software Foundation. If the Program does not specify a version number of this License, you may choose any version ever published by the Free Software Foundation.

10. If you wish to incorporate parts of the Program into other free

programs whose distribution conditions are different, write to the author to ask for permission. For software which is copyrighted by the Free Software Foundation, write to the Free Software Foundation; we sometimes make exceptions for this. Our decision will be guided by the two goals of preserving the free status of all derivatives of our free software and of promoting the sharing and reuse of software generally.

NO WARRANTY

11. BECAUSE THE PROGRAM IS LICENSED FREE OF CHARGE, THERE IS NO WARRANTY FOR THE PROGRAM, TO THE EXTENT PERMITTED BY APPLICABLE LAW.

EXCEPT WHEN

OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE PROGRAM "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE PROGRAM IS WITH YOU. SHOULD THE PROGRAM PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

12. IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY AND/OR REDISTRIBUTE THE PROGRAM AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE PROGRAM (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE PROGRAM TO OPERATE WITH ANY OTHER PROGRAMS), EVEN

IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Programs

If you develop a new program, and you want it to be of the greatest possible use to the public, the best way to achieve this is to make it free software which everyone can redistribute and change under these terms.

To do so, attach the following notices to the program. It is safest to attach them to the start of each source file to most effectively convey the exclusion of warranty; and each file should have at least the "copyright" line and a pointer to where the full notice is found.

<one line to give the program's name and a brief idea of what it does.>

Copyright (C) <year> <name of author>

This program is free software; you can redistribute it and/or modify

it under the terms of the GNU General Public License as published by the Free Software Foundation; either version 2 of the License, or (at your option) any later version.

This program is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details.

You should have received a copy of the GNU General Public License along with this program; if not, write to the Free Software Foundation, Inc., 59 Temple Place, Suite 330, Boston, MA 02111-1307 USA

Also add information on how to contact you by electronic and paper mail.

If the program is interactive, make it output a short notice like this when it starts in an interactive mode:

```
Gnomovision version 69, Copyright (C) year name of author
Gnomovision comes with ABSOLUTELY NO WARRANTY; for details type `show w'.
This is free software, and you are welcome to redistribute it
under certain conditions; type `show c' for details.
```

The hypothetical commands `show w' and `show c' should show the appropriate parts of the General Public License. Of course, the commands you use may be called something other than `show w' and `show c'; they could even be mouse-clicks or menu items--whatever suits your program.

You should also get your employer (if you work as a programmer) or your school, if any, to sign a "copyright disclaimer" for the program, if necessary. Here is a sample; alter the names:

```
Yoyodyne, Inc., hereby disclaims all copyright interest in the program
`Gnomovision' (which makes passes at compilers) written by James Hacker.
```

```
<signature of Ty Coon>, 1 April 1989
Ty Coon, President of Vice
```

This General Public License does not permit incorporating your program into proprietary programs. If your program is a subroutine library, you may consider it more useful to permit linking proprietary applications with the library. If this is what you want to do, use the GNU Library General Public License instead of this License.

1.46 iconv 2.27

1.46.1 Available under license :

GNU LIBRARY GENERAL PUBLIC LICENSE

Version 2, June 1991

Copyright (C) 1991 Free Software Foundation, Inc.
51 Franklin Street, Fifth Floor, Boston, MA 02110-1301, USA
Everyone is permitted to copy and distribute verbatim copies
of this license document, but changing it is not allowed.

[This is the first released version of the library GPL. It is
numbered 2 because it goes with version 2 of the ordinary GPL.]

Preamble

The licenses for most software are designed to take away your
freedom to share and change it. By contrast, the GNU General Public
Licenses are intended to guarantee your freedom to share and change
free software--to make sure the software is free for all its users.

This license, the Library General Public License, applies to some
specially designated Free Software Foundation software, and to any
other libraries whose authors decide to use it. You can use it for
your libraries, too.

When we speak of free software, we are referring to freedom,
not
price. Our General Public Licenses are designed to make sure that you
have the freedom to distribute copies of free software (and charge for
this service if you wish), that you receive source code or can get it
if you want it, that you can change the software or use pieces of it
in new free programs; and that you know you can do these things.

To protect your rights, we need to make restrictions that forbid
anyone to deny you these rights or to ask you to surrender the rights.
These restrictions translate to certain responsibilities for you if
you distribute copies of the library, or if you modify it.

For example, if you distribute copies of the library, whether gratis
or for a fee, you must give the recipients all the rights that we gave
you. You must make sure that they, too, receive or can get the source
code. If you link a program with the library, you must provide
complete object files to the recipients so that they can relink them
with the library, after making
changes to the library and recompiling
it. And you must show them these terms so they know their rights.

Our method of protecting your rights has two steps: (1) copyright the library, and (2) offer you this license which gives you legal permission to copy, distribute and/or modify the library.

Also, for each distributor's protection, we want to make certain that everyone understands that there is no warranty for this free library. If the library is modified by someone else and passed on, we want its recipients to know that what they have is not the original version, so that any problems introduced by others will not reflect on the original authors' reputations.

Finally, any free program is threatened constantly by software patents. We wish to avoid the danger that companies distributing free software will individually obtain patent licenses, thus in effect transforming the program into proprietary software. To prevent this, we have made it clear that any patent must be licensed for everyone's free use or not licensed at all.

Most GNU software, including some libraries, is covered by the ordinary GNU General Public License, which was designed for utility programs. This license, the GNU Library General Public License, applies to certain designated libraries. This license is quite different from the ordinary one; be sure to read it in full, and don't assume that anything in it is the same as in the ordinary license.

The reason we have a separate public license for some libraries is that they blur the distinction we usually make between modifying or adding to a program and simply using it. Linking a program with a library, without changing the library, is in some sense simply using the library, and is analogous to running a utility program or application program. However, in a textual and legal sense, the linked executable is a combined work, a derivative of the original library, and the ordinary General Public License treats it as such.

Because of this blurred distinction, using the ordinary General Public License for libraries did not effectively promote software sharing, because most developers did not use the libraries. We concluded that weaker conditions might promote sharing better.

However, unrestricted linking of non-free programs would deprive the users of those programs of all benefit from the free status of the libraries themselves. This Library General Public License is intended to permit developers of non-free programs to use free libraries, while preserving your freedom as a user of such programs to change the free libraries that are incorporated in them. (We have not seen how to achieve

this as regards changes in header files, but we have achieved it as regards changes in the actual functions of the Library.) The hope is that this will lead to faster development of free libraries.

The precise terms and conditions for copying, distribution and modification follow. Pay close attention to the difference between a "work based on the library" and a "work that uses the library". The former contains code derived from the library, while the latter only works together with the library.

Note that it is possible for a library to be covered by the ordinary General Public License rather than by this special one.

GNU LIBRARY GENERAL PUBLIC LICENSE TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

0. This License Agreement applies to any software library which contains a notice placed by the copyright holder or other authorized party saying it may be distributed under the terms of this Library General Public License (also called "this License"). Each licensee is addressed as "you".

A "library" means a collection of software functions and/or data prepared so as to be conveniently linked with application programs (which use some of those functions and data) to form executables.

The "Library", below, refers to any such software library or work which has been distributed under these terms. A "work based on the Library" means either the Library or any derivative work under copyright law: that is to say, a work containing the Library or a portion of it, either verbatim or with modifications and/or translated straightforwardly into another language. (Hereinafter, translation is included without limitation in the term "modification".)

"Source code" for a work means the preferred form of the work for making modifications to it. For a library, complete source code means all the source code for all modules it contains, plus any associated interface definition files, plus the scripts used to control compilation and installation of the library.

Activities other than copying, distribution and modification are not covered by this License; they are outside its scope. The act of running a program using the Library is not restricted, and output from such a program is covered only if its contents constitute a work based on the Library (independent

of the use of the Library in a tool for writing it). Whether that is true depends on what the Library does and what the program that uses the Library does.

1. You may copy and distribute verbatim copies of the Library's complete source code as you receive it, in any medium, provided that you conspicuously and appropriately publish on each copy an appropriate copyright notice and disclaimer of warranty; keep intact all the notices that refer to this License and to the absence of any warranty; and distribute a copy of this License along with the Library.

You may charge a fee for the physical act of transferring a copy, and you may at your option offer warranty protection in exchange for a fee.

2. You may modify your copy or copies of the Library or any portion of it, thus forming a work based on the Library, and copy and distribute such modifications or work under the terms of Section 1 above, provided that you also meet all of these conditions:

a) The modified work must itself be a software library.

b) You must cause the files modified to carry prominent notices stating that you changed the files and the date of any change.

c) You must cause the whole of the work to be licensed at no charge to all third parties under the terms of this License.

d) If a facility in the modified Library refers to a function or a table of data to be supplied by an application program that uses the facility, other than as an argument passed when the facility is invoked, then you must make a good faith effort to ensure that, in the event an application does not supply such function or table, the facility still operates, and performs whatever part of its purpose remains meaningful.

(For example, a function in a library to compute square roots has a purpose that is entirely well-defined independent of the application. Therefore, Subsection 2d requires that any application-supplied function or table used by this function must

be optional: if the application does not supply it, the square root function must still compute square roots.)

These requirements apply to the modified work as a whole. If identifiable sections of that work are not derived from the Library,

and can be reasonably considered independent and separate works in themselves, then this License, and its terms, do not apply to those sections when you distribute them as separate works. But when you distribute the same sections as part of a whole which is a work based on the Library, the distribution of the whole must be on the terms of this License, whose permissions for other licensees extend to the entire whole, and thus to each and every part regardless of who wrote it.

Thus, it is not the intent of this section to claim rights or contest your rights to work written entirely by you; rather, the intent is to exercise the right to control the distribution of derivative or collective works based on the Library.

In addition,

mere aggregation of another work not based on the Library with the Library (or with a work based on the Library) on a volume of a storage or distribution medium does not bring the other work under the scope of this License.

3. You may opt to apply the terms of the ordinary GNU General Public License instead of this License to a given copy of the Library. To do this, you must alter all the notices that refer to this License, so that they refer to the ordinary GNU General Public License, version 2, instead of to this License. (If a newer version than version 2 of the ordinary GNU General Public License has appeared, then you can specify that version instead if you wish.) Do not make any other change in these notices.

Once this change is made in a given copy, it is irreversible for that copy, so the ordinary GNU General Public License applies to all subsequent copies and derivative works made from that copy.

This option is useful when you wish to copy part of the code of the

Library into a program that is not a library.

4. You may copy and distribute the Library (or a portion or derivative of it, under Section 2) in object code or executable form under the terms of Sections 1 and 2 above provided that you accompany it with the complete corresponding machine-readable source code, which must be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange.

If distribution of object code is made by offering access to copy from a designated place, then offering equivalent access to copy the source code from the same place satisfies the requirement to distribute the source code, even though third parties are not

compelled to copy the source along with the object code.

5. A program that contains no derivative of any portion of the Library, but is designed to work with the Library by being compiled or linked with it, is called a "work that uses the Library". Such a work, in isolation, is not a derivative work of the Library, and therefore falls outside the scope of this License.

However, linking a "work that uses the Library" with the Library creates an executable that is a derivative of the Library (because it contains portions of the Library), rather than a "work that uses the library". The executable is therefore covered by this License. Section 6 states terms for distribution of such executables.

When a "work that uses the Library" uses material from a header file that is part of the Library, the object code for the work may be a derivative work of the Library even though the source code is not. Whether this is true is especially significant if the work can be linked without the Library, or if the work is itself a library. The threshold for this to be true is not precisely defined by law.

If such an object file uses only numerical parameters, data structure layouts and accessors, and small macros and small inline functions (ten lines or less in length), then the use of the object file is unrestricted, regardless of whether it is legally a derivative work. (Executables containing this object code plus portions of the Library will still fall under Section 6.)

Otherwise, if the work is a derivative of the Library, you may distribute the object code for the work under the terms of Section 6. Any executables containing that work also fall under Section 6, whether or not they are linked directly with the Library itself.

6. As an exception to the Sections above, you may also compile or link a "work that uses the Library" with the Library to produce a work containing portions of the Library, and distribute that work under terms of your choice, provided that the terms permit modification of the work for the customer's own use and reverse engineering for debugging such modifications.

You must give prominent notice with each copy of the work that the Library is used in it and that the Library and its use are covered by this License. You must supply a copy of this License. If the work during execution displays copyright notices, you must include the copyright notice for the Library among them, as well as a reference

directing the user to the copy of this License. Also, you must do one of these things:

a) Accompany the work with the complete corresponding machine-readable source code for the Library including whatever changes were used in the work (which must be distributed under Sections 1 and 2 above); and, if the work is an executable linked with the Library, with the complete machine-readable "work that uses the Library", as object code and/or source code, so that the user can modify the Library and then relink to produce a modified executable containing the modified Library. (It is understood that the user who changes the contents of definitions files in the Library will not necessarily be able to recompile the application to use the modified definitions.)

b) Accompany the work with a written offer, valid for at least three years, to give the same user the materials specified in Subsection 6a, above, for a charge no more than the cost of performing this distribution.

c) If distribution of the work is made by offering access to copy from a designated place, offer equivalent access to copy the above specified materials from the same place.

d) Verify that the user has already received a copy of these materials or that you have already sent this user a copy.

For an executable, the required form of the "work that uses the Library" must include any data and utility programs needed for reproducing the executable from it. However, as a special exception, the source code distributed need not include anything that is normally distributed (in either source or binary form) with the major components (compiler, kernel, and so on) of the operating system on which the executable runs, unless that component itself accompanies the executable.

It may happen that this requirement contradicts the license restrictions of other proprietary libraries that do not normally accompany the operating system. Such a contradiction means you cannot use both them and the Library together in an executable that you distribute.

7. You may place library facilities that are a work based on the Library side-by-side in a single library together with other library facilities not covered by this License, and distribute such a combined library, provided that the separate distribution of the work based on the Library and of the other library facilities is otherwise

permitted, and provided that you do these two things:

a) Accompany the combined library with a copy of the same work based on the Library, uncombined with any other library facilities. This must be distributed under the terms of the Sections above.

b) Give prominent notice with the combined library of the fact that part of it is a work based on the Library, and explaining where to find the accompanying uncombined form of the same work.

8. You may not copy, modify, sublicense, link with, or distribute the Library except as expressly provided under this License. Any attempt otherwise to copy, modify, sublicense, link with, or distribute the Library is void, and will automatically terminate your rights under this License. However, parties who have received copies, or rights, from you under this License will not have their licenses terminated so long as such parties remain in full compliance.

9. You are not required to accept this License, since you have not signed it. However, nothing else grants you permission to modify or distribute the Library or its derivative works. These actions are prohibited by law if you do not accept this License. Therefore, by modifying or distributing the Library (or any work based on the Library), you indicate your acceptance of this License to do so, and all its terms and conditions for copying, distributing or modifying the Library or works based on it.

10. Each time you redistribute the Library (or any work based on the Library), the recipient automatically receives a license from the original licensor to copy, distribute, link with or modify the Library subject to these terms and conditions. You may not impose any further restrictions on the recipients' exercise of the rights granted herein. You are not responsible for enforcing compliance by third parties to this License.

11. If, as a consequence of a court judgment or allegation of patent infringement or for any other reason (not limited to patent issues), conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot distribute so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not distribute the Library at all. For example, if a patent license would not permit royalty-free redistribution of the Library by

all those who receive copies directly or indirectly through you, then the only way you could satisfy both it and this License would be to refrain entirely from distribution of the Library.

If any portion of this section is held invalid or unenforceable under any particular circumstance, the balance of the section is intended to apply, and the section as a whole is intended to apply in other circumstances.

It is not the purpose of this section to induce you to infringe any patents or other property right claims or to contest validity of any such claims; this section has the sole purpose of protecting the integrity of the free software distribution system which is implemented by public license practices. Many people have made generous contributions to the wide range of software distributed through that system in reliance on consistent application of that system;

it is up to the author/donor to decide if he or she is willing to distribute software through any other system and a licensee cannot impose that choice.

This section is intended to make thoroughly clear what is believed to be a consequence of the rest of this License.

12. If the distribution and/or use of the Library is restricted in certain countries either by patents or by copyrighted interfaces, the original copyright holder who places the Library under this License may add an explicit geographical distribution limitation excluding those countries, so that distribution is permitted only in or among countries not thus excluded. In such case, this License incorporates the limitation as if written in the body of this License.

13. The Free Software Foundation may publish revised and/or new versions of the Library General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each

version is given a distinguishing version number. If the Library specifies a version number of this License which applies to it and "any later version", you have the option of following the terms and conditions either of that version or of any later version published by the Free Software Foundation. If the Library does not specify a license version number, you may choose any version ever published by the Free Software Foundation.

14. If you wish to incorporate parts of the Library into other free programs whose distribution conditions are incompatible with these, write to the author to ask for permission. For software which is

copyrighted by the Free Software Foundation, write to the Free Software Foundation; we sometimes make exceptions for this. Our decision will be guided by the two goals of preserving the free status of all derivatives of our free software and of promoting the sharing and reuse of software generally.

NO WARRANTY

15. BECAUSE THE LIBRARY IS LICENSED FREE OF CHARGE, THERE IS NO WARRANTY FOR THE LIBRARY, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE LIBRARY "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE LIBRARY IS WITH YOU. SHOULD THE LIBRARY PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

16. IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY AND/OR REDISTRIBUTE THE LIBRARY AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE LIBRARY (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE LIBRARY TO OPERATE WITH ANY OTHER SOFTWARE), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

END OF TERMS AND CONDITIONS

Appendix: How to Apply These Terms to Your New Libraries

If you develop a new library, and you want it to be of the greatest possible use to the public, we recommend making it free software that everyone can redistribute and change. You can do so by permitting redistribution under these terms (or, alternatively, under the terms of the ordinary General Public License).

To apply these terms, attach the following notices to the library. It is safest to attach them to the start of each source file to most effectively convey the exclusion of warranty; and each file should have at least the "copyright" line and a pointer to where the full notice is found.

<one line to give the library's name and a brief idea of what it does.>

Copyright (C) <year>

<name of author>

This library is free software; you can redistribute it and/or modify it under the terms of the GNU Library General Public License as published by the Free Software Foundation; either version 2 of the License, or (at your option) any later version.

This library is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU Library General Public License for more details.

You should have received a copy of the GNU Library General Public License along with this library; if not, write to the Free Software Foundation, Inc., 51 Franklin Street, Fifth Floor, Boston, MA 02110-1301, USA

Also add information on how to contact you by electronic and paper mail.

You should also get your employer (if you work as a programmer) or your school, if any, to sign a "copyright disclaimer" for the library, if necessary.

Here is a sample; alter the names:

Yoyodyne, Inc., hereby disclaims all copyright interest in the library `Frob' (a library for tweaking knobs) written by James Random Hacker.

<signature of Ty Coon>, 1 April 1990
Ty Coon, President of Vice

That's all there is to it!

GNU GENERAL PUBLIC LICENSE
Version 3, 29 June 2007

Copyright (C) 2007 Free Software Foundation, Inc. <<http://fsf.org/>>
Everyone is permitted to copy and distribute verbatim copies of this license document, but changing it is not allowed.

Preamble

The GNU General Public License is a free, copyleft license for software and other kinds of works.

The licenses for most software and other practical works are designed to take away your freedom to share and change the works. By contrast, the GNU General Public License is intended to guarantee your freedom to share and change all versions of a program--to make sure it remains free software for all its users. We, the Free Software Foundation, use the

GNU General Public License for most of our software; it applies also to any other work released this way by its authors. You can apply it to your programs, too.

When we speak of free software, we are referring to freedom, not price. Our General Public Licenses are designed to make sure that you have the freedom to distribute copies of free software (and charge for them if you wish), that you receive source code or can get it if you want it, that you can change the software or use pieces of it in new free programs, and that you know you can do these things.

To protect your rights, we need to prevent others from denying you these rights or asking you to surrender the rights. Therefore, you have certain responsibilities if you distribute copies of the software, or if you modify it: responsibilities to respect the freedom of others.

For example, if you distribute copies of such a program, whether gratis or for a fee, you must pass on to the recipients the same freedoms that you received. You must make sure that they, too, receive or can get the source code. And you must show them these terms so they know their rights.

Developers that use the GNU GPL protect your rights with two steps:

(1) assert copyright on the software, and (2) offer you this License giving you legal permission to copy, distribute and/or modify it.

For the developers' and authors' protection, the GPL clearly explains that there is no warranty for this free software. For both users' and authors' sake, the GPL requires that modified versions be marked as changed, so that their problems will not be attributed erroneously to authors of previous versions.

Some devices are designed to deny users access to install or run modified versions of the software inside them, although the manufacturer can do so. This is fundamentally incompatible with the aim of protecting users' freedom to change the software. The systematic pattern of such abuse occurs in the area of products for individuals to use, which is precisely where it is most unacceptable. Therefore, we have designed this version of the GPL to prohibit the practice for those products. If such problems arise substantially in other domains, we stand ready to extend this provision to those domains in future versions of the GPL, as needed to protect the freedom of users.

Finally, every program is threatened constantly by software patents. States should not allow patents to restrict development and use of

software on general-purpose computers, but in those that do, we wish to avoid the special danger that patents applied to a free program could make it effectively proprietary. To prevent this, the GPL assures that patents cannot be used to render the program non-free.

The precise terms and conditions for copying, distribution and modification follow.

TERMS AND CONDITIONS

0. Definitions.

"This License" refers to version 3 of the GNU General Public License.

"Copyright" also means copyright-like laws that apply to other kinds of works, such as semiconductor masks.

"The Program" refers to any copyrightable work licensed under this License. Each licensee is addressed as "you". "Licensees" and "recipients" may be individuals or organizations.

To "modify" a work means to copy from or adapt all or part of the work in a fashion requiring copyright permission, other than the making of an exact copy. The resulting work is called a "modified version" of the earlier work or a work "based on" the earlier work.

A "covered work" means either the unmodified Program or a work based on the Program.

To "propagate" a work means to do anything with it that, without permission, would make you directly or secondarily liable for infringement under applicable copyright law, except executing it on a computer or modifying a private copy. Propagation includes copying, distribution (with or without modification), making available to the public, and in some countries other activities as well.

To "convey" a work means any kind of propagation that enables other parties to make or receive copies. Mere interaction with a user through a computer network, with no transfer of a copy, is not conveying.

An interactive user interface displays "Appropriate Legal Notices" to the extent that it includes a convenient and prominently visible feature that (1) displays an appropriate copyright notice, and (2) tells the user that there is no warranty for the work (except to the extent that warranties are provided), that licensees may convey the work under this License, and how to view a copy of this License. If

the interface presents a list of user commands or options, such as a menu, a prominent item in the list meets this criterion.

1. Source Code.

The "source code" for a work means the preferred form of the work for making modifications to it. "Object code" means any non-source form of a work.

A "Standard Interface" means an interface that either is an official standard defined by a recognized standards body, or, in the case of interfaces specified for a particular programming language, one that is widely used among developers working in that language.

The

"System Libraries" of an executable work include anything, other than the work as a whole, that (a) is included in the normal form of packaging a Major Component, but which is not part of that Major Component, and (b) serves only to enable use of the work with that Major Component, or to implement a Standard Interface for which an implementation is available to the public in source code form. A "Major Component", in this context, means a major essential component (kernel, window system, and so on) of the specific operating system (if any) on which the executable work runs, or a compiler used to produce the work, or an object code interpreter used to run it.

The "Corresponding Source" for a work in object code form means all the source code needed to generate, install, and (for an executable work) run the object code and to modify the work, including scripts to control those activities. However, it does not include the work's System Libraries, or general-purpose tools or generally available free programs which are used unmodified in performing those activities but which are not part of the work. For example, Corresponding Source includes interface definition files associated with source files for the work, and the source code for shared libraries and dynamically linked subprograms that the work is specifically designed to require, such as by intimate data communication or control flow between those subprograms and other parts of the work.

The Corresponding Source need not include anything that users can regenerate automatically from other parts of the Corresponding Source.

The Corresponding Source for a work in source code form is that same work.

2. Basic Permissions.

All rights granted under this License are granted for the term of copyright on the Program, and are irrevocable provided the stated conditions are met. This License explicitly affirms your unlimited permission to run the unmodified Program. The output from running a covered work is covered

by this License only if the output, given its content, constitutes a covered work. This License acknowledges your rights of fair use or other equivalent, as provided by copyright law.

You may make, run and propagate covered works that you do not convey, without conditions so long as your license otherwise remains in force. You may convey covered works to others for the sole purpose of having them make modifications exclusively for you, or provide you with facilities for running those works, provided that you comply with the terms of this License in conveying all material for which you do not control copyright. Those thus making or running the covered works for you must do so exclusively on your behalf, under your direction and control, on terms that prohibit them from making any copies of your copyrighted material outside their relationship with you.

Conveying under any other circumstances is permitted solely under the conditions stated below. Sublicensing is not allowed;

section 10
makes it unnecessary.

3. Protecting Users' Legal Rights From Anti-Circumvention Law.

No covered work shall be deemed part of an effective technological measure under any applicable law fulfilling obligations under article 11 of the WIPO copyright treaty adopted on 20 December 1996, or similar laws prohibiting or restricting circumvention of such measures.

When you convey a covered work, you waive any legal power to forbid circumvention of technological measures to the extent such circumvention is effected by exercising rights under this License with respect to the covered work, and you disclaim any intention to limit operation or modification of the work as a means of enforcing, against the work's users, your or third parties' legal rights to forbid circumvention of technological measures.

4. Conveying Verbatim Copies.

You may convey verbatim copies of the Program's source code as you receive it, in any medium, provided that you conspicuously and appropriately

publish on each copy an appropriate copyright notice;
keep intact all notices stating that this License and any
non-permissive terms added in accord with section 7 apply to the code;
keep intact all notices of the absence of any warranty; and give all
recipients a copy of this License along with the Program.

You may charge any price or no price for each copy that you convey,
and you may offer support or warranty protection for a fee.

5. Conveying Modified Source Versions.

You may convey a work based on the Program, or the modifications to
produce it from the Program, in the form of source code under the
terms of section 4, provided that you also meet all of these conditions:

- a) The work must carry prominent notices stating that you modified
it, and giving a relevant date.

- b) The work must carry prominent notices stating that it is
released under this License and any conditions added under section
7. This requirement modifies the requirement in section
4 to
"keep intact all notices".

- c) You must license the entire work, as a whole, under this
License to anyone who comes into possession of a copy. This
License will therefore apply, along with any applicable section 7
additional terms, to the whole of the work, and all its parts,
regardless of how they are packaged. This License gives no
permission to license the work in any other way, but it does not
invalidate such permission if you have separately received it.

- d) If the work has interactive user interfaces, each must display
Appropriate Legal Notices; however, if the Program has interactive
interfaces that do not display Appropriate Legal Notices, your
work need not make them do so.

A compilation of a covered work with other separate and independent
works, which are not by their nature extensions of the covered work,
and which are not combined with it such as to form a larger program,
in or on a volume of a storage or distribution
medium, is called an
"aggregate" if the compilation and its resulting copyright are not
used to limit the access or legal rights of the compilation's users
beyond what the individual works permit. Inclusion of a covered work
in an aggregate does not cause this License to apply to the other
parts of the aggregate.

6. Conveying Non-Source Forms.

You may convey a covered work in object code form under the terms of sections 4 and 5, provided that you also convey the machine-readable Corresponding Source under the terms of this License, in one of these ways:

- a) Convey the object code in, or embodied in, a physical product (including a physical distribution medium), accompanied by the Corresponding Source fixed on a durable physical medium customarily used for software interchange.
- b) Convey the object code in, or embodied in, a physical product (including a physical distribution medium), accompanied by a written offer, valid for at least three years and valid for as long as you offer spare parts or customer support for that product model, to give anyone who possesses the object code either (1) a copy of the Corresponding Source for all the software in the product that is covered by this License, on a durable physical medium customarily used for software interchange, for a price no more than your reasonable cost of physically performing this conveying of source, or (2) access to copy the Corresponding Source from a network server at no charge.
- c) Convey individual copies of the object code with a copy of the written offer to provide the Corresponding Source. This alternative is allowed only occasionally and noncommercially, and only if you received the object code with such an offer, in accord with subsection 6b.
- d) Convey the object code by offering access from a designated place (gratis or for a charge), and offer equivalent access to the Corresponding Source in the same way through the same place at no further charge. You need not require recipients to copy the Corresponding Source along with the object code. If the place to copy the object code is a network server, the Corresponding Source may be on a different server (operated by you or a third party) that supports equivalent copying facilities, provided you maintain clear directions next to the object code saying where to find the Corresponding Source. Regardless of what server hosts the Corresponding Source, you remain obligated to ensure that it is available for as long as needed to satisfy these requirements.
- e) Convey the object code using peer-to-peer transmission, provided you inform other peers where the object code and Corresponding Source of the work are being offered to the general public at no

charge under subsection 6d.

A separable portion of the object code, whose source code is excluded from the Corresponding Source as a System Library, need not be included in conveying the object code work.

A "User Product" is either (1) a "consumer product", which means any tangible personal property which is normally used for personal, family, or household purposes, or (2) anything designed or sold for incorporation into a dwelling. In determining whether a product is a consumer product, doubtful cases shall be resolved in favor of coverage. For a particular product received by a particular user, "normally used" refers to a typical or common use of that class of product, regardless of the status of the particular user or of the way in which the particular user actually uses, or expects or is expected to use, the product. A product is a consumer product regardless of whether the product has substantial commercial, industrial or non-consumer uses, unless such uses represent the only significant mode of use of the product.

"Installation Information" for a User Product means any methods, procedures, authorization keys, or other information required to install and execute modified versions of a covered work in that User Product from a modified version of its Corresponding Source. The information must suffice to ensure that the continued functioning of the modified object code is in no case prevented or interfered with solely because modification has been made.

If you convey an object code work under this section in, or with, or specifically for use in, a User Product, and the conveying occurs as part of a transaction in which the right of possession and use of the User Product is transferred to the recipient in perpetuity or for a fixed term (regardless of how the transaction is characterized), the Corresponding Source conveyed under this section must be accompanied by the Installation Information. But this requirement does not apply if neither you nor any third party retains the ability to install modified object code on the User Product (for example, the work has been installed in ROM).

The requirement to provide Installation Information does not include a requirement to continue to provide support service, warranty, or updates for a work that has been modified or installed by the recipient, or for the User Product in which it has been modified or installed. Access to a network may be denied when the modification itself materially and adversely affects the operation of the network or violates the rules and protocols for communication across the network.

Corresponding Source conveyed, and Installation Information provided, in accord with this section must be in a format that is publicly documented (and with an implementation available to the public in source code form), and must require no special password or key for unpacking, reading or copying.

7. Additional Terms.

"Additional permissions" are terms that supplement the terms of this License by making exceptions from one or more of its conditions. Additional permissions that are applicable to the entire Program shall be treated as though they were included in this License, to the extent that they are valid under applicable law. If additional permissions apply only to part of the Program, that part may be used separately under those permissions, but the entire Program remains governed by this License without regard to the additional permissions.

When you convey a copy of a covered work, you may at your option remove any additional permissions from that copy, or from any part of it. (Additional permissions may be written to require their own removal in certain cases when you modify the work.) You may place additional permissions on material, added by you to a covered work, for which you have or can give appropriate copyright permission.

Notwithstanding any other provision of this License, for material you add to a covered work, you may (if authorized by the copyright holders of that material) supplement the terms of this License with terms:

- a) Disclaiming warranty or limiting liability differently from the terms of sections 15 and 16 of this License; or
- b) Requiring preservation of specified reasonable legal notices or author attributions in that material or in the Appropriate Legal Notices displayed by works containing it; or
- c) Prohibiting misrepresentation of the origin of that material, or requiring that modified versions of such material be marked in reasonable ways as different from the original version; or
- d) Limiting the use for publicity purposes of names of licensors or authors of the material; or
- e) Declining to grant rights under trademark law for use of some trade names, trademarks, or service marks; or

f) Requiring indemnification of licensors and authors of that material by anyone who conveys the material (or modified versions of it) with contractual assumptions of liability to the recipient, for any liability that these contractual assumptions directly impose on

those licensors and authors.

All other non-permissive additional terms are considered "further restrictions" within the meaning of section 10. If the Program as you received it, or any part of it, contains a notice stating that it is governed by this License along with a term that is a further restriction, you may remove that term. If a license document contains a further restriction but permits relicensing or conveying under this License, you may add to a covered work material governed by the terms of that license document, provided that the further restriction does not survive such relicensing or conveying.

If you add terms to a covered work in accord with this section, you must place, in the relevant source files, a statement of the additional terms that apply to those files, or a notice indicating where to find the applicable terms.

Additional terms, permissive or non-permissive, may be stated in the form of a separately written license, or stated as exceptions; the above requirements apply either way.

8. Termination.

You may not propagate or modify a covered work except as expressly provided under this License. Any attempt otherwise to propagate or modify it is void, and will automatically terminate your rights under this License (including any patent licenses granted under the third paragraph of section 11).

However, if you cease all violation of this License, then your license from a particular copyright holder is reinstated (a) provisionally, unless and until the copyright holder explicitly and finally terminates your license, and (b) permanently, if the copyright holder fails to notify you of the violation by some reasonable means prior to 60 days after the cessation.

Moreover, your license from a particular copyright holder is reinstated permanently if the copyright holder notifies you of the violation by some reasonable means, this is the first time you have received notice of violation of this License (for any work) from that copyright

holder, and you cure the violation prior to 30 days after your receipt of the notice.

Termination of your rights under this section does not terminate the licenses of parties who have received copies or rights from you under this License. If your rights have been terminated and not permanently reinstated, you do not qualify to receive new licenses for the same material under section 10.

9. Acceptance Not Required for Having Copies.

You are not required to accept this License in order to receive or run a copy of the Program. Ancillary propagation of a covered work occurring solely as a consequence of using peer-to-peer transmission to receive a copy likewise does not require acceptance. However, nothing other than this License grants you permission to propagate or modify any covered work. These actions infringe copyright if you do not accept this License. Therefore, by modifying or propagating a covered work, you indicate your acceptance of this License to do so.

10. Automatic Licensing of Downstream Recipients.

Each time you convey a covered work, the recipient automatically receives a license from the original licensors, to run, modify and propagate that work, subject to this License. You are not responsible for enforcing compliance by third parties with this License.

An "entity transaction" is a transaction transferring control of an organization, or substantially all assets of one, or subdividing an organization, or merging organizations. If propagation of a covered work results from an entity transaction, each party to that transaction who receives a copy of the work also receives whatever licenses to the work the party's predecessor in interest had or could give under the previous paragraph, plus a right to possession of the Corresponding Source of the work from the predecessor in interest, if the predecessor has it or can get it with reasonable efforts.

You may not impose any further restrictions on the exercise of the rights granted or affirmed under this License. For example, you may not impose a license fee, royalty, or other charge for exercise of rights granted under this License, and you may not initiate litigation (including a cross-claim or counterclaim in a lawsuit) alleging that any patent claim is infringed by making, using, selling, offering for sale, or importing the Program or any portion of it.

11. Patents.

A "contributor" is a copyright holder who authorizes use under this License of the Program or a work on which the Program is based. The work thus licensed is called the contributor's "contributor version".

A contributor's "essential patent claims" are all patent claims owned or controlled by the contributor, whether already acquired or hereafter acquired, that would be infringed by some manner, permitted by this License, of making, using, or selling its contributor version, but do not include claims that would be infringed only as a consequence of further modification of the contributor version. For purposes of this definition, "control" includes the right to grant patent sublicenses in a manner consistent with the requirements of this License.

Each contributor grants you a non-exclusive, worldwide, royalty-free patent license under the contributor's essential patent claims, to make, use, sell, offer for sale, import and otherwise run, modify and propagate the contents of its contributor version.

In the following three paragraphs, a "patent license" is any express agreement or commitment, however denominated, not to enforce a patent (such as an express permission to practice a patent or covenant not to sue for patent infringement). To "grant" such a patent license to a party means to make such an agreement or commitment not to enforce a patent against the party.

If you convey a covered work, knowingly relying on a patent license, and the Corresponding Source of the work is not available for anyone to copy, free of charge and under the terms of this License, through a publicly available network server or other readily accessible means, then you must either (1) cause the Corresponding Source to be so available, or (2) arrange to deprive yourself of the benefit of the patent license for this particular work, or (3) arrange, in a manner consistent with the requirements of this License, to extend the patent license to downstream recipients. "Knowingly relying" means you have actual knowledge that, but for the patent license, your conveying the covered work in a country, or your recipient's use of the covered work in a country, would infringe one or more identifiable patents in that country that you have reason to believe are valid.

If, pursuant to or in connection with a single transaction or arrangement, you convey, or propagate by procuring conveyance of, a covered work, and grant a patent license to some of the parties receiving the covered work authorizing them to use, propagate, modify or convey a specific copy of the covered

work, then the patent license you grant is automatically extended to all recipients of the covered work and works based on it.

A patent license is "discriminatory" if it does not include within the scope of its coverage, prohibits the exercise of, or is conditioned on the non-exercise of one or more of the rights that are specifically granted under this License. You may not convey a covered work if you are a party to an arrangement with a third party that is in the business of distributing software, under which you make payment to the third party based on the extent of your activity of conveying the work, and under which the third party grants, to any of the parties who would receive the covered work from you, a discriminatory patent license (a) in connection with copies of the covered work conveyed by you (or copies made from those copies), or (b) primarily for and in connection with specific products or compilations that contain the covered work, unless you entered into that arrangement, or that patent license was granted, prior to 28 March 2007.

Nothing in this License shall be construed as excluding or limiting any implied license or other defenses to infringement that may otherwise be available to you under applicable patent law.

12. No Surrender of Others' Freedom.

If conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot convey a covered work so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not convey it at all. For example, if you agree to terms that obligate you to collect a royalty for further conveying from those to whom you convey the Program, the only way you could satisfy both those terms and this License would be to refrain entirely from conveying the Program.

13. Use with the GNU Affero General Public License.

Notwithstanding any other provision of this License, you have permission to link or combine any covered work with a work licensed under version 3 of the GNU Affero General Public License into a single combined work, and to convey the resulting work. The terms of this License will continue to apply to the part which is the covered work, but the special requirements of the GNU Affero General Public License, section 13, concerning interaction through a network will apply to the combination as such.

14. Revised Versions of this License.

The Free Software Foundation may publish revised and/or new versions of the GNU General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Program specifies that a certain numbered version of the GNU General Public License "or any later version" applies to it, you have the option of following the terms and conditions either of that numbered version or of any later version published by the Free Software Foundation. If the Program does not specify a version number of the GNU General Public License, you may choose any version ever published by the Free Software Foundation.

If the Program specifies that a proxy can decide which future versions of the GNU General Public License can be used, that proxy's public statement of acceptance of a version permanently authorizes you to choose that version for the Program.

Later license versions may give you additional or different permissions. However, no additional obligations are imposed on any author or copyright holder as a result of your choosing to follow a later version.

15. Disclaimer of Warranty.

THERE IS NO WARRANTY FOR THE PROGRAM, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE PROGRAM "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE PROGRAM IS WITH YOU. SHOULD THE PROGRAM PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

16. Limitation of Liability.

IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MODIFIES AND/OR CONVEYS THE PROGRAM AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE PROGRAM (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE PROGRAM TO OPERATE WITH ANY OTHER PROGRAMS), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF

SUCH DAMAGES.

17.

Interpretation of Sections 15 and 16.

If the disclaimer of warranty and limitation of liability provided above cannot be given local legal effect according to their terms, reviewing courts shall apply local law that most closely approximates an absolute waiver of all civil liability in connection with the Program, unless a warranty or assumption of liability accompanies a copy of the Program in return for a fee.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Programs

If you develop a new program, and you want it to be of the greatest possible use to the public, the best way to achieve this is to make it free software which everyone can redistribute and change under these terms.

To do so, attach the following notices to the program. It is safest to attach them to the start of each source file to most effectively state the exclusion of warranty; and each file should have at least the "copyright" line and a pointer to where the full notice is found.

```
<one line to give the program's name and a brief idea of what it does.>  
Copyright (C) <year> <name of author>
```

```
This program is free software: you can redistribute it and/or modify  
it under the terms of the GNU General Public License as published by  
the Free Software Foundation, either version 3 of the License, or  
(at your option) any later version.
```

```
This program is distributed in the hope that it will be useful,  
but WITHOUT ANY WARRANTY; without even the implied warranty of  
MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the  
GNU General Public License for more details.
```

```
You should have received a copy of the GNU General Public License  
along with this program. If not, see <http://www.gnu.org/licenses/>.
```

Also add information on how to contact you by electronic and paper mail.

If the program does terminal interaction, make it output a short notice like this when it starts in an interactive mode:

<program> Copyright (C) <year> <name of author>

This program comes with ABSOLUTELY NO WARRANTY; for details type `show w'.

This is free software, and you are welcome to redistribute it under certain conditions; type `show c' for details.

The hypothetical commands `show w' and `show c' should show the appropriate parts of the General Public License. Of course, your program's commands might be different; for a GUI interface, you would use an "about box".

You should also get your employer (if you work as a programmer) or school, if any, to sign a "copyright disclaimer" for the program, if necessary.

For more information on this, and how to apply and follow the GNU GPL, see <<http://www.gnu.org/licenses/>>.

The GNU General Public License does not permit incorporating your program into proprietary programs. If your program is a subroutine library, you may consider it more useful to permit linking proprietary applications with the library. If this is what you want to do, use the GNU Lesser General Public License instead of this License. But first, please read <<http://www.gnu.org/philosophy/why-not-lgpl.html>>.

1.47 zstd 1.3.3+dfsg-2ubuntu1.2

1.47.1 Available under license :

GNU GENERAL PUBLIC LICENSE

Version 2, June 1991

Copyright (C) 1989, 1991 Free Software Foundation, Inc.,
51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA
Everyone is permitted to copy and distribute verbatim copies
of this license document, but changing it is not allowed.

Preamble

The licenses for most software are designed to take away your freedom to share and change it. By contrast, the GNU General Public License is intended to guarantee your freedom to share and change free software--to make sure the software is free for all its users. This General Public License applies to most of the Free Software Foundation's software and to any other program whose authors commit to using it. (Some other Free Software Foundation software is covered by the GNU Lesser General Public License instead.) You can apply it to your programs, too.

When we speak of free software, we are referring to freedom, not price.

Our General Public Licenses are designed to make sure that you have the freedom to distribute copies of free software (and charge for this service if you wish), that you receive source code or can get it if you want it, that you can change the software or use pieces of it in new free programs; and that you know you can do these things.

To protect your rights, we need to make restrictions that forbid anyone to deny you these rights or to ask you to surrender the rights. These restrictions translate to certain responsibilities for you if you distribute copies of the software, or if you modify it.

For example, if you distribute copies of such a program, whether gratis or for a fee, you must give the recipients all the rights that you have. You must make sure that they, too, receive or can get the source code. And you must show them these terms so they know their rights.

We protect your rights with two steps: (1) copyright the software, and (2) offer you this license which gives you legal permission to copy, distribute and/or modify the software.

Also, for each author's protection and ours, we want to make certain that everyone understands that there is no warranty for this free software. If the software is modified by someone else and passed on, we want its recipients to know that what they have is not the original, so that any problems introduced by others will not reflect on the original authors' reputations.

Finally, any free program is threatened constantly by software patents. We wish to avoid the danger that redistributors of a free program will individually obtain patent licenses, in effect making the program proprietary. To prevent this, we have made it clear that any patent must be licensed for everyone's free use or not licensed at all.

The precise terms and conditions for copying, distribution and modification follow.

GNU GENERAL PUBLIC LICENSE

TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

0. This License applies to any program or other work which contains a notice placed by the copyright holder saying it may be distributed under the terms of this General Public License. The "Program", below, refers to any such program or work, and a "work based on the Program" means either the Program or any derivative work under copyright law: that is to say, a work containing the Program or a portion of it, either verbatim or with modifications and/or translated into another

language. (Hereinafter, translation is included without limitation in the term "modification".) Each licensee is addressed as "you".

Activities other than copying, distribution and modification are not covered by this License; they are outside its scope. The act of running the Program is not restricted, and the output from the Program is covered only if its contents constitute a work based on the Program (independent of having been made by running the Program). Whether that is true depends on what the Program does.

1. You may copy and distribute verbatim copies of the Program's source code as you receive it, in any medium, provided that you conspicuously and appropriately publish on each copy an appropriate copyright notice and disclaimer of warranty; keep intact all the notices that refer to this License and to the absence of any warranty; and give any other recipients of the Program a copy of this License along with the Program.

You may charge a fee for the physical act of transferring a copy, and you may at your option offer warranty protection in exchange for a fee.

2. You may modify your copy or copies of the Program or any portion of it, thus forming a work based on the Program, and copy and distribute such modifications or work under the terms of Section 1 above, provided that you also meet all of these conditions:

a) You must cause the modified files to carry prominent notices stating that you changed the files and the date of any change.

b) You must cause any work that you distribute or publish, that in whole or in part contains or is derived from the Program or any part thereof, to be licensed as a whole at no charge to all third parties under the terms of this License.

c) If the modified program normally reads commands interactively when run, you must cause it, when started running for such interactive use in the most ordinary way, to print or display an announcement including an appropriate copyright notice and a notice that there is no warranty (or else, saying that you provide a warranty) and that users may redistribute the program under these conditions, and telling the user how to view a copy of this License. (Exception: if the Program itself is interactive but does not normally print such an announcement, your work based on the Program is not required to print an announcement.)

These requirements apply to the modified work as a whole. If

identifiable sections of that work
are not derived from the Program,
and can be reasonably considered independent and separate works in
themselves, then this License, and its terms, do not apply to those
sections when you distribute them as separate works. But when you
distribute the same sections as part of a whole which is a work based
on the Program, the distribution of the whole must be on the terms of
this License, whose permissions for other licensees extend to the
entire whole, and thus to each and every part regardless of who wrote it.

Thus, it is not the intent of this section to claim rights or contest
your rights to work written entirely by you; rather, the intent is to
exercise the right to control the distribution of derivative or
collective works based on the Program.

In addition, mere aggregation of another work not based on the Program
with the Program (or with a work based on the Program) on a volume of
a storage or distribution medium does not bring the other work under
the scope of this License.

3. You may copy and distribute the Program (or a work based on it,
under Section 2) in object code or executable form under the terms of
Sections 1 and 2 above provided that you also do one of the following:

a) Accompany it with the complete corresponding machine-readable
source code, which must be distributed under the terms of Sections
1 and 2 above on a medium customarily used for software interchange; or,

b) Accompany it with a written offer, valid for at least three
years, to give any third party, for a charge no more than your
cost of physically performing source distribution, a complete
machine-readable copy of the corresponding source code, to be
distributed under the terms of Sections 1 and 2 above on a medium
customarily used for software interchange; or,

c) Accompany it with the information you received as to the offer
to distribute corresponding source code. (This alternative is
allowed only for noncommercial distribution
and only if you
received the program in object code or executable form with such
an offer, in accord with Subsection b above.)

The source code for a work means the preferred form of the work for
making modifications to it. For an executable work, complete source
code means all the source code for all modules it contains, plus any
associated interface definition files, plus the scripts used to
control compilation and installation of the executable. However, as a
special exception, the source code distributed need not include

anything that is normally distributed (in either source or binary form) with the major components (compiler, kernel, and so on) of the operating system on which the executable runs, unless that component itself accompanies the executable.

If distribution of executable or object code is made by offering access to copy from a designated place, then offering equivalent access to copy the source code from the same place counts as distribution of the source code, even though third parties are not compelled to copy the source along with the object code.

4. You may not copy, modify, sublicense, or distribute the Program except as expressly provided under this License. Any attempt otherwise to copy, modify, sublicense or distribute the Program is void, and will automatically terminate your rights under this License. However, parties who have received copies, or rights, from you under this License will not have their licenses terminated so long as such parties remain in full compliance.

5. You are not required to accept this License, since you have not signed it. However, nothing else grants you permission to modify or distribute the Program or its derivative works. These actions are prohibited by law if you do not accept this License. Therefore, by modifying or distributing the Program (or any work based on the Program), you indicate your acceptance of this License to do so, and all its terms and conditions for copying, distributing or modifying the Program or works based on it.

6. Each time you redistribute the Program (or any work based on the Program), the recipient automatically receives a license from the original licensor to copy, distribute or modify the Program subject to these terms and conditions. You may not impose any further restrictions on the recipients' exercise of the rights granted herein. You are not responsible for enforcing compliance by third parties to this License.

7. If, as a consequence of a court judgment or allegation of patent infringement or for any other reason (not limited to patent issues), conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot distribute so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not distribute the Program at all. For example, if a patent license would not permit royalty-free redistribution of the Program by

all those who receive copies directly or indirectly through you, then the only way you could satisfy both it and this License would be to refrain entirely from distribution of the Program.

If any portion of this section is held invalid or unenforceable under any particular circumstance, the balance of the section is intended to apply and the section as a whole is intended to apply in other circumstances.

It is not the purpose of this section to induce you to infringe any patents or other property right claims or to contest validity of any such claims; this section has the sole purpose of protecting the integrity of the free software distribution system, which is implemented by public license practices. Many people have made generous contributions to the wide range of software distributed through that system in reliance on consistent application of that system; it is up to the author/donor to decide if he or she is willing to distribute software through any other system and a licensee cannot impose that choice.

This section is intended to make thoroughly clear what is believed to be a consequence of the rest of this License.

8. If the distribution and/or use of the Program is restricted in certain countries either by patents or by copyrighted interfaces, the original copyright holder who places the Program under this License may add an explicit geographical distribution limitation excluding those countries, so that distribution is permitted only in or among countries not thus excluded. In such case, this License incorporates the limitation as if written in the body of this License.

9. The Free Software Foundation may publish revised and/or new versions of the General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Program specifies a version number of this License which applies to it and "any later version", you have the option of following the terms and conditions either of that version or of any later version published by the Free Software Foundation. If the Program does not specify a version number of this License, you may choose any version ever published by the Free Software Foundation.

10. If you wish to incorporate parts of the Program into other free programs whose distribution conditions are different, write to the author

to ask for permission. For software which is copyrighted by the Free Software Foundation, write to the Free Software Foundation; we sometimes make exceptions for this. Our decision will be guided by the two goals of preserving the free status of all derivatives of our free software and of promoting the sharing and reuse of software generally.

NO WARRANTY

11. BECAUSE THE PROGRAM IS LICENSED FREE OF CHARGE, THERE IS NO WARRANTY FOR THE PROGRAM, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE PROGRAM "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE PROGRAM IS WITH YOU. SHOULD THE PROGRAM PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

12. IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY AND/OR REDISTRIBUTE THE PROGRAM AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE PROGRAM (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE PROGRAM TO OPERATE WITH ANY OTHER PROGRAMS), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Programs

If you develop a new program, and you want it to be of the greatest possible use to the public, the best way to achieve this is to make it free software which everyone can redistribute and change under these terms.

To do so, attach the following notices to the program. It is safest to attach them to the start of each source file to most effectively convey the exclusion of warranty; and each file should have at least the "copyright" line and a pointer to where the full notice is found.

```
<one line to give the program's name and a brief idea of what it does.>  
Copyright (C) <year> <name of author>
```

```
This program is free software; you can redistribute it and/or modify  
it under the terms of the GNU
```

General Public License as published by
the Free Software Foundation; either version 2 of the License, or
(at your option) any later version.

This program is distributed in the hope that it will be useful,
but WITHOUT ANY WARRANTY; without even the implied warranty of
MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
GNU General Public License for more details.

You should have received a copy of the GNU General Public License along
with this program; if not, write to the Free Software Foundation, Inc.,
51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA.

Also add information on how to contact you by electronic and paper mail.

If the program is interactive, make it output a short notice like this
when it starts in an interactive mode:

```
Gnomovision version 69, Copyright (C) year name of author
Gnomovision comes with ABSOLUTELY NO WARRANTY; for details type `show w'.
This is free software, and you are welcome to redistribute
it
under certain conditions; type `show c' for details.
```

The hypothetical commands ``show w'` and ``show c'` should show the appropriate
parts of the General Public License. Of course, the commands you use may
be called something other than ``show w'` and ``show c'`; they could even be
mouse-clicks or menu items--whatever suits your program.

You should also get your employer (if you work as a programmer) or your
school, if any, to sign a "copyright disclaimer" for the program, if
necessary. Here is a sample; alter the names:

```
Yoyodyne, Inc., hereby disclaims all copyright interest in the program
`Gnomovision' (which makes passes at compilers) written by James Hacker.
```

```
<signature of Ty Coon>, 1 April 1989
Ty Coon, President of Vice
```

This General Public License does not permit incorporating your program into
proprietary programs. If your program is a subroutine library, you may
consider it more useful to permit linking proprietary applications with the
library. If this
is what you want to do, use the GNU Lesser General
Public License instead of this License.
BSD License

For Zstandard software

Copyright (c) 2016-present, Facebook, Inc. All rights reserved.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

* Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.

* Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.

* Neither the name Facebook nor the names of its contributors may be used to endorse or promote products derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED.

IN NO EVENT SHALL THE COPYRIGHT HOLDER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

1.48 libpkit 0.23.9-2ubuntu0.1

1.48.1 Available under license :

Format: <http://dep.debian.net/deps/dep5>

Upstream-Name: p11-kit

Source: <http://p11-glue.freedesktop.org/p11-kit.html>

Files: *

Copyright: 2011 Collabora Ltd.

License: BSD-3-Clause

Files: p11-kit/conf.* p11-kit/modules.c p11-kit/proxy.c

common/dict.c common/dict.h

Copyright: 2011 Collabora Ltd.

2004 Stefan Walter

License: BSD-3-Clause

Files: common/buffer.c common/buffer.h

Copyright: 2007, 2012 Stefan Walter

2013 Red Hat Inc.

License: BSD-3-Clause

Files: common/library.c common/library.h common/message.c

p11-kit/client-init.c p11-kit/proxy-init.c

Copyright: 2011 Collabora Ltd.

2012 Stef Walter

License: BSD-3-Clause

Files: common/url.c common/url.h

Copyright: 2011 Collabora Ltd.

2013 Red Hat Inc.

License: BSD-3-Clause

Files: p11-kit/log.c

Copyright: 2007, Stefan Walter

2013, Red Hat Inc.

License: BSD-3-Clause

Files: common/pkcs11.h

Copyright: 2006, 2007 g10 Code GmbH

2006 Andreas Jellinghaus

Copyright 2017 Red Hat, Inc.

License: permissive-like-automake-output

This file is free software; as a special exception the author gives unlimited permission to copy and/or distribute it, with or without modifications, as long as this notice is preserved.

.

This file is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY, to the extent permitted by law; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. */

Files: common/argv.c common/argv.h common/hash.h

trust/oid.c trust/oid.h

trust/pem.c trust/pem.h common/argv.c common/argv.h common/pkcs11x.h

common/pkcs11i.h

common/test-constants.c common/test-hash.c

p11-kit/pkcs11.h p11-kit/test-managed.c

trust/builder.c

trust/builder.h trust/digest.h trust/module.c trust/module.h trust/pem.c

trust/pem.h trust/oid.c trust/oid.h trust/parser.h

trust/session.c trust/session.h trust/frob-cert.c

trust/frob-eku.c trust/frob-token.c

trust/test-digest.c trust/test-enumerate.c

trust/test-index.c trust/test-module.c

trust/test-oid.c
trust/test-parser.c trust/test-pem.c trust/test-token.c
trust/token.c trust/token.h trust/test-trust.c
trust/test-trust.h trust/x509.c trust/x509.h p11-kit/frob-setuid.c
Copyright: 2012 Red Hat Inc.
License: BSD-3-Clause

Files: common/attrs.c common/attrs.h
Copyright: 2012, Redhat Inc.
2011, Collabora Ltd.
License: BSD-3-Clause

Files: common/test-attrs.c common/test-buffer.c
trust/frob-ku.c trust/frob-oid.c trust/test-asn1.c
Copyright: 2012, Redhat Inc.
License: BSD-3-Clause

Files: p11-kit/test-modules.c
Copyright: 2012, 2015, 2016 Red Hat Inc
License: BSD-3-Clause

Files: common/constants.c common/constants.h common/test.c
common/test.h common/test-compat.c common/test-tests.c
common/tool.h p11-kit/deprecated.h
p11-kit/docs.h p11-kit/log.h p11-kit/modules.h p11-kit/proxy.h
p11-kit/test-log.c trust/anchor.c trust/anchor.h
trust/enumerate.c trust/enumerate.h trust/extract.c
trust/extract-cer.c trust/extract.h trust/extract-jks.c
trust/extract-openssl.c trust/extract-pem.c trust/index.c
trust/index.h trust/list.c trust/list.h trust/persist.c
trust/persist.h trust/save.c trust/save.h trust/frob-bc.c
trust/frob-ext.c trust/frob-pow.c
trust/test-base64.c
trust/test-builder.c trust/test-save.c
trust/test-utf8.c trust/test-x509.c
trust/types.h trust/utf8.c trust/utf8.h
Copyright: 2013, Redhat Inc.
License: BSD-3-Clause

Files: p11-kit/remote.h common/frob-getenv.c
common/unix-peer.h
Copyright: 2014 Red Hat Inc.
License: BSD-3-Clause

Files: p11-kit/server.c
common/unix-peer.h
Copyright: 2014 Red Hat Inc.
License: BSD-3-Clause
Comment: make_private_security_descriptor() and the helper functions were
* copied from putty/windows/winsecur.c in the PuTTY source code as of
* git commit 12bd5a6c722152aa27f24598785593e72b3284ea.
*
* PuTTY is copyright 1997-2017 Simon Tatham.
*
* Portions copyright Robert de Bath, Joris van Rantwijk, Delian
* Delchev, Andreas Schultz, Jeroen Massar, Wez Furlong, Nicolas Barry,
* Justin Bradford, Ben Harris, Malcolm Smith, Ahmad Khalifa, Markus
* Kuhn, Colin Watson, Christopher Staite, and CORE SDI S.A.
*
* Permission is hereby granted, free of charge, to any person
* obtaining a copy of this software and associated documentation files
* (the "Software"), to deal in the Software without restriction,
* including without limitation the rights to use, copy, modify, merge,
* publish, distribute, sublicense, and/or sell copies of the Software,
* and to permit persons to whom the Software is furnished to do so,
* subject to the following conditions:
*
* The above copyright notice and this permission notice shall be
* included in all copies or substantial portions of the Software.

Files: p11-kit/remote.c
Copyright: 2014,2016 Red Hat Inc.
License: BSD-3-Clause

Files: p11-kit/test-mock.c
Copyright: 2012 Stefan Walter
2012-2013 Red Hat Inc.
License: BSD-3-Clause

Files: p11-kit/test-virtual.c p11-kit/test-transport.c
Copyright: 2012 Stefan Walter
2012 Red Hat Inc.
License: BSD-3-Clause

Files: p11-kit/test-rpc.c
Copyright: 2012 Stefan Walter
Copyright (C) 2012-2017 Red Hat Inc.
License: BSD-3-Clause

Files: p11-kit/rpc-transport.c
Copyright: 2012 Stefan Walter
2013 Red Hat Inc.
License: BSD-3-Clause

Files: p11-kit/test-deprecated.c
Copyright: 2011, Collabora Ltd.
2012 Red Hat Inc.
License: BSD-3-Clause

Files: p11-kit/virtual.c trust/asn1.c trust/asn1.h p11-kit/rpc-client.c
p11-kit/rpc-message.c p11-kit/rpc-message.h p11-kit/rpc-server.c
Copyright: 2008 Stefan Walter
2012 Red Hat Inc.
License: BSD-3-Clause

Files: p11-kit/rpc.h
Copyright: 2012-2013 Stefan Walter
License: BSD-3-Clause

Files: trust/digest.c trust/digest.c common/hash.c
Copyright: 2004, 2005, 2007, 2011 Internet Systems Consortium, Inc. ("ISC")
2000, 2001, 2003 Internet Software Consortium.

License: ISC

Permission to use, copy, modify, and/or distribute this software for any purpose with or without fee is hereby granted, provided that the above copyright notice and this permission notice appear in all copies.

.
THE SOFTWARE IS PROVIDED "AS IS" AND ISC DISCLAIMS ALL WARRANTIES WITH REGARD TO THIS SOFTWARE INCLUDING ALL IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS. IN NO EVENT SHALL ISC BE LIABLE FOR ANY SPECIAL, DIRECT, INDIRECT, OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES WHATSOEVER RESULTING FROM LOSS OF USE, DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE OR OTHER TORTIOUS ACTION, ARISING OUT OF OR IN CONNECTION WITH THE USE OR PERFORMANCE OF THIS SOFTWARE.

Files: trust/base64.c trust/base64.h
Copyright: 1996, 1998 by Internet Software Consortium
Portions Copyright (c) 1995 by International Business Machines, Inc.
License: ISC+IBM
Copyright (c) 1996, 1998 by Internet Software Consortium.

.
Permission to use, copy, modify, and distribute this software for any purpose with or without fee is hereby granted, provided that the above copyright notice and this permission notice appear in all

copies.

.
THE SOFTWARE IS PROVIDED "AS IS" AND INTERNET SOFTWARE CONSORTIUM DISCLAIMS ALL WARRANTIES WITH REGARD TO THIS SOFTWARE INCLUDING ALL IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS. IN NO EVENT SHALL INTERNET SOFTWARE CONSORTIUM BE LIABLE FOR ANY SPECIAL, DIRECT, INDIRECT, OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES WHATSOEVER RESULTING FROM LOSS OF USE, DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE OR OTHER TORTIOUS ACTION, ARISING OUT OF OR IN CONNECTION WITH THE USE OR PERFORMANCE OF THIS SOFTWARE.

.
Portions Copyright (c) 1995 by International Business Machines, Inc.

.
International Business Machines, Inc. (hereinafter called IBM) grants permission under its copyrights to use, copy, modify, and distribute this Software with or without fee, provided that the above copyright notice and all paragraphs of this notice appear in all copies, and that the name of IBM not be used in connection with the marketing of any product incorporating the Software or modifications thereof, without specific, written prior permission.

.
To the extent it has a right to do so, IBM grants an immunity from suit under its patents, if any, for the use, sale or manufacture of products to the extent that such products are used for performing Domain Name System dynamic updates in TCP/IP networks by means of the Software. No immunity is granted for any product per se or for any other function of any product.

.
THE SOFTWARE IS PROVIDED "AS IS", AND IBM DISCLAIMS ALL WARRANTIES, INCLUDING ALL IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. IN NO EVENT SHALL IBM BE LIABLE FOR ANY SPECIAL, DIRECT, INDIRECT, OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES WHATSOEVER ARISING OUT OF OR IN CONNECTION WITH THE USE OR PERFORMANCE OF THIS SOFTWARE, EVEN IF IBM IS APPRISED OF THE POSSIBILITY OF SUCH DAMAGES.

Files: common/lexer.c common/lexer.h common/path.c

Copyright: 2005 Stefan Walter

2011 Collabora Ltd.

2013 Red Hat Inc.

License:

BSD-3-Clause

Files: common/compat.c

Copyright: Copyright (c) 2011 Collabora Ltd.

Portions of this file are covered by the following copyright:

Copyright (c) 2001 Mike Barcroft <mike@FreeBSD.org>

Copyright (c) 1990, 1993

Copyright (c) 1987, 1993

The Regents of the University of California.

License: BSD-3-Clause

This code is derived from software contributed to Berkeley by
Chris Torek.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions
are met:

1. Redistributions of source code must retain the above copyright
notice, this list of conditions and the following disclaimer.
2. Redistributions in binary form must reproduce the above copyright
notice, this list of conditions and the following disclaimer in the
documentation and/or other materials provided with the distribution.
4. Neither the name of the University nor the names of its contributors
may be used
to endorse or promote products derived from this software
without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE REGENTS AND CONTRIBUTORS ``AS IS'' AND
ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE
IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE
ARE DISCLAIMED. IN NO EVENT SHALL THE REGENTS OR CONTRIBUTORS BE LIABLE
FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL
DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS
OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION)
HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT
LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY
OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF
SUCH DAMAGE.

Files: common/mock.h common/path.h common/frob-getauxval.c
common/test-lexer.c common/test-message.c
common/test-path.c common/test-url.c
p11-kit/test-proxy.c p11-kit/virtual.h p11-kit/test-util.c
trust/frob-nss-trust.c trust/test-parser.c
trust/test-persist.c p11-kit/client.h
Copyright: 2013 Red Hat Inc.
License: BSD-3-Clause

Files: p11-kit/iter.c p11-kit/iter.h p11-kit/test-iter.c
Copyright: 2013,2016 Red Hat Inc.
License: BSD-3-Clause

Files: p11-kit/client.c p11-kit/filter.c p11-kit/filter.h
p11-kit/test-filter.c p11-kit/virtual-fixed.h

Copyright: 2016 Red Hat Inc.

License: BSD-3-Clause

Files: common/test-argv.c

Copyright: 2017 Red Hat Inc.

License: BSD-3-Clause

Files: p11-kit/mock-module-ep.c p11-kit/test-progname.c p11-kit/mock-module-ep3.c

Copyright: 2012 Stefan Walter

License: BSD-3-Clause

Files: common/unix-peer.c

Copyright: 2013 Nikos Mavrogiannopoulos

License: BSD-3-Clause

Files: debian/*

Copyright: 2011 Chris Coulson <chris.coulson@canonical.com>

2011-2013 Andreas Metzler <ametzler@debian.org>

License: BSD-3-Clause

Files: po/de.po

Copyright: 2011 Chris Leick

Comment: This file is distributed

under the same license as the
debian files of the p11-kit package.

License: BSD-3-Clause

Files: po/fi.po

Copyright: 2012 Rosetta Contributors and Canonical Ltd 2012

Eerik Uusi-Illikainen <https://launchpad.net/~ekiuusi-4>, 2012

Timo Jyrinki <timo.jyrinki@iki.fi>, 2012

License: same-as-rest-of-p11kit

This file is distributed under the same license as the p11-kit
package.

License: BSD-3-Clause

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions
are met:

1. Redistributions of source code must retain the above copyright
notice, this list of conditions and the following disclaimer.
2. Redistributions in binary form must reproduce the above copyright

notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.

3. Neither the name of the University nor the names of its contributors may be used to endorse or promote products derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE REGENTS AND CONTRIBUTORS ``AS IS'' AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE REGENTS OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

1.49 libtasn 4.13-2

1.49.1 Available under license :

GNU LESSER GENERAL PUBLIC LICENSE

Version 2.1, February 1999

Copyright (C) 1991, 1999 Free Software Foundation, Inc.
51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA
Everyone is permitted to copy and distribute verbatim copies of this license document, but changing it is not allowed.

[This is the first released version of the Lesser GPL. It also counts as the successor of the GNU Library Public License, version 2, hence the version number 2.1.]

Preamble

The licenses for most software are designed to take away your freedom to share and change it. By contrast, the GNU General Public Licenses are intended to guarantee your freedom to share and change free software--to make sure the software is free for all its users.

This license, the Lesser General Public License, applies to some specially designated software packages--typically libraries--of the Free Software Foundation and other authors who decide to use it. You can use it too, but we suggest you first think carefully about whether this license or the ordinary General Public License is the better

strategy to use in any particular case, based on the explanations below.

When we speak of free software, we are referring to freedom of use, not price. Our General Public Licenses are designed to make sure that you have the freedom to distribute copies of free software (and charge for this service if you wish); that you receive source code or can get it if you want it; that you can change the software and use pieces of it in new free programs; and that you are informed that you can do these things.

To protect your rights, we need to make restrictions that forbid distributors to deny you these rights or to ask you to surrender these rights. These restrictions translate to certain responsibilities for you if you distribute copies of the library or if you modify it.

For example, if you distribute copies of the library, whether gratis or for a fee, you must give the recipients all the rights that we gave you. You must make sure that they, too, receive or can get the source code. If you link other code with the library, you must provide complete object files to the recipients, so that they can relink them with the library after making changes to the library and recompiling it. And you must show them these terms so they know their rights.

We protect your rights with a two-step method: (1) we copyright the library, and (2) we offer you this license, which gives you legal permission to copy, distribute and/or modify the library.

To protect each distributor, we want to make it very clear that there is no warranty for the free library. Also, if the library is modified by someone else and passed on, the recipients should know that what they have is not the original version, so that the original author's reputation will not be affected by problems that might be introduced by others.

Finally, software patents pose a constant threat to the existence of any free program. We wish to make sure that a company cannot effectively restrict the users of a free program by obtaining a restrictive license from a patent holder. Therefore, we insist that any patent license obtained for a version of the library must be consistent with the full freedom of use specified in this license.

Most GNU software, including some libraries, is covered by the ordinary GNU General Public License. This license, the GNU Lesser General Public License, applies to certain designated libraries, and is quite different from the ordinary General Public License. We use this license for certain libraries in order to permit linking those

libraries into non-free programs.

When a program is linked with a library, whether statically or using a shared library, the combination of the two is legally speaking a combined work, a derivative of the original library. The ordinary General Public License therefore permits such linking only if the entire combination fits its criteria of freedom. The Lesser General Public License permits more lax criteria for linking other code with the library.

We call this license the "Lesser" General Public License because it does Less to protect the user's freedom than the ordinary General Public License. It also provides other free software developers Less of an advantage over competing non-free programs. These disadvantages are the reason we use the ordinary General Public License for many libraries. However, the Lesser license provides advantages in certain special circumstances.

For example, on rare occasions, there may be a special need to encourage the widest possible use of a certain library, so that it becomes a de-facto standard. To achieve this, non-free programs must be allowed to use the library. A more frequent case is that a free library does the same job as widely used non-free libraries. In this case, there is little to gain by limiting the free library to free software only, so we use the Lesser General Public License.

In other cases, permission to use a particular library in non-free programs enables a greater number of people to use a large body of free software. For example, permission to use the GNU C Library in non-free programs enables many more people to use the whole GNU operating system, as well as its variant, the GNU/Linux operating system.

Although the Lesser General Public License is Less protective of the users' freedom, it does ensure that the user of a program that is linked with the Library has the freedom and the wherewithal to run that program using a modified version of the Library.

The precise terms and conditions for copying, distribution and modification follow. Pay close attention to the difference between a "work based on the library" and a "work that uses the library". The former contains code derived from the library, whereas the latter must be combined with the library in order to run.

GNU LESSER GENERAL PUBLIC LICENSE

TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

0. This License Agreement applies to any software library or other program which contains a notice placed by the copyright holder or other authorized party saying it may be distributed under the terms of this Lesser General Public License (also called "this License").

Each licensee is addressed as "you".

A "library" means a collection of software functions and/or data prepared so as to be conveniently linked with application programs (which use some of those functions and data) to form executables.

The "Library", below, refers to any such software library or work which has been distributed under these terms. A "work based on the Library" means either the Library or any derivative work under copyright law: that is to say, a work containing the Library or a portion of it, either verbatim or with modifications and/or translated straightforwardly into

another language. (Hereinafter, translation is included without limitation in the term "modification".)

"Source code" for a work means the preferred form of the work for making modifications to it. For a library, complete source code means all the source code for all modules it contains, plus any associated interface definition files, plus the scripts used to control compilation and installation of the library.

Activities other than copying, distribution and modification are not covered by this License; they are outside its scope. The act of running a program using the Library is not restricted, and output from such a program is covered only if its contents constitute a work based on the Library (independent of the use of the Library in a tool for writing it). Whether that is true depends on what the Library does and what the program that uses the Library does.

1. You may copy and distribute verbatim copies of the Library's complete source code as you receive it, in any medium, provided that you conspicuously and appropriately publish on each copy an appropriate copyright notice and disclaimer of warranty; keep intact all the notices that refer to this License and to the absence of any warranty; and distribute a copy of this License along with the Library.

You may charge a fee for the physical act of transferring a copy, and you may at your option offer warranty protection in exchange for a fee.

2. You may modify your copy or copies of the Library or any portion of it, thus forming a work based on the Library, and copy and distribute such modifications or work under the terms of Section 1 above, provided that you also meet all of these conditions:

- a) The modified work must itself be a software library.
- b) You must cause the files modified to carry prominent notices stating that you changed the files and the date of any change.
- c) You must cause the whole of the work to be licensed at no charge to all third parties under the terms of this License.
- d) If a facility in the modified Library refers to a function or a table of data to be supplied by an application program that uses the facility, other than as an argument passed when the facility is invoked, then you must make a good faith effort to ensure that, in the event an application does not supply such function or table, the facility still operates, and performs whatever part of its purpose remains meaningful.

(For example, a function in a library to compute square roots has a purpose that is entirely well-defined independent of the application. Therefore, Subsection 2d requires that any application-supplied function or table used by this function must be optional: if the application does not supply it, the square root function must still compute square roots.)

These requirements apply to the modified work as a whole. If identifiable sections of that work are not derived from the Library, and can be reasonably considered independent and separate works in themselves, then this License, and its terms, do not apply to those sections when you distribute them as separate works. But when you distribute the same sections as part of a whole which is a work based on the Library, the distribution of the whole must be on the terms of this License, whose permissions for other licensees extend to the entire whole, and thus to each and every part regardless of who wrote it.

Thus, it is not the intent of this section to claim rights or contest your rights to work written entirely by you; rather, the intent is to exercise the right to control the distribution of derivative or collective works based on the Library.

In addition, mere aggregation of another work not based on the Library with the Library (or with a work based on the Library) on a volume of

a storage or distribution medium does not bring the other work under the scope of this License.

3. You may opt to apply the terms of the ordinary GNU General Public

License instead of this License to a given copy of the Library. To do this, you must alter all the notices that refer to this License, so that they refer to the ordinary GNU General Public License, version 2, instead of to this License. (If a newer version than version 2 of the ordinary GNU General Public License has appeared, then you can specify that version instead if you wish.) Do not make any other change in these notices.

Once this change is made in a given copy, it is irreversible for that copy, so the ordinary GNU General Public License applies to all subsequent copies and derivative works made from that copy.

This option is useful when you wish to copy part of the code of the Library into a program that is not a library.

4. You may copy and distribute the Library (or a portion or derivative of it, under Section 2) in object code or executable form under the terms of Sections 1 and 2 above provided that you accompany it with the complete corresponding machine-readable source code, which must be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange.

If distribution of object code is made by offering access to copy from a designated place, then offering equivalent access to copy the source code from the same place satisfies the requirement to distribute the source code, even though third parties are not compelled to copy the source along with the object code.

5. A program that contains no derivative of any portion of the Library, but is designed to work with the Library by being compiled or linked with it, is called a "work that uses the Library". Such a work, in isolation, is not a derivative work of the Library, and therefore falls outside the scope of this License.

However, linking a "work that uses the Library" with the Library creates an executable that is a derivative of the Library (because it contains portions of the Library), rather than a "work that uses the library". The executable is therefore covered by this License. Section 6 states terms for distribution of such executables.

When a "work that uses the Library" uses material from a header file

that is part of the Library, the object code for the work may be a derivative work of the Library even though the source code is not. Whether this is true is especially significant if the work can be linked without the Library, or if the work is itself a library. The threshold for this to be true is not precisely defined by law.

If such an object file uses only numerical parameters, data structure layouts and accessors, and small macros and small inline functions (ten lines or less in length), then the use of the object file is unrestricted, regardless of whether it is legally a derivative work. (Executables containing this object code plus portions of the Library will still fall under Section 6.)

Otherwise, if the work is a derivative of the Library, you may distribute the object code for the work under the terms of Section 6. Any executables containing that work also fall under Section 6, whether or not they are linked directly with the Library itself.

6. As an exception to the Sections above, you may also combine or link a "work that uses the Library" with the Library to produce a work containing portions of the Library, and distribute that work under terms of your choice, provided that the terms permit modification of the work for the customer's own use and reverse engineering for debugging such modifications.

You must give prominent notice with each copy of the work that the Library is used in it and that the Library and its use are covered by this License. You must supply a copy of this License. If the work during execution displays copyright notices, you must include the copyright notice for the Library among them, as well as a reference directing the user to the copy of this License. Also, you must do one of these things:

a) Accompany the work with the complete corresponding machine-readable source code for the Library including whatever changes were used in the work (which must be distributed under Sections 1 and 2 above); and, if the work is an executable linked with the Library, with the complete machine-readable "work that uses the Library", as object code and/or source code, so that the user can modify the Library and then relink to produce a modified executable containing the modified Library. (It is understood that the user who changes the contents of definitions files in the Library will not necessarily be able to recompile the application to use the modified definitions.)

b) Use a suitable shared library mechanism for linking with the

Library. A suitable mechanism is one that (1) uses at run time a copy of the library already present on the user's computer system, rather than copying library functions into the executable, and (2) will operate properly with a modified version of the library, if the user installs one, as long as the modified version is interface-compatible with the version that the work was made with.

c) Accompany the work with a written offer, valid for at least three years, to give the same user the materials specified in Subsection 6a, above, for a charge no more than the cost of performing this distribution.

d) If distribution of the work is made by offering access to copy from a designated place, offer equivalent access to copy the above specified materials from the same place.

e) Verify that the user has already received a copy of these materials or that you have already sent this user a copy.

For an executable, the required form of the "work that uses the Library" must include any data and utility programs needed for reproducing the executable from it. However, as a special exception, the materials to be distributed need not include anything that is normally distributed (in either source or binary form) with the major components (compiler, kernel, and so on) of the operating system on which the executable runs, unless that component itself accompanies the executable.

It may happen that this requirement contradicts the license restrictions of other proprietary libraries that do not normally accompany the operating system. Such a contradiction means you cannot use both them and the Library together in an executable that you distribute.

7. You may place library facilities that are a work based on the Library side-by-side in a single library together with other library facilities not covered by this License, and distribute such a combined library, provided that the separate distribution of the work based on the Library and of the other library facilities is otherwise permitted, and provided that you do these two things:

a) Accompany the combined library with a copy of the same work based on the Library, uncombined with any other library facilities. This must be distributed under the terms of the Sections above.

b) Give prominent notice with the combined library of the fact that part of it is a work based on the Library, and explaining where to find the accompanying uncombined form of the same work.

8. You may not copy, modify, sublicense, link with, or distribute the Library except as expressly provided under this License. Any attempt otherwise to copy, modify, sublicense, link with, or distribute the Library is void, and will automatically terminate your rights under this License. However, parties who have received copies, or rights, from you under this License will not have their licenses terminated so long as such parties remain in full compliance.

9. You are not required to accept this License, since you have not signed it. However, nothing else grants you permission to modify or distribute the Library or its derivative works. These actions are prohibited by law if you do not accept this License. Therefore, by modifying or distributing the Library (or any work based on the Library), you indicate your acceptance of this License to do so, and all its terms and conditions for copying, distributing or modifying the Library or works based on it.

10. Each time you redistribute the Library (or any work based on the Library), the recipient automatically receives a license from the original licensor to copy, distribute, link with or modify the Library subject to these terms and conditions. You may not impose any further restrictions on the recipients' exercise of the rights granted herein. You are not responsible for enforcing compliance by third parties with this License.

11. If, as a consequence of a court judgment or allegation of patent infringement or for any other reason (not limited to patent issues), conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot distribute so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not distribute the Library at all. For example, if a patent license would not permit royalty-free redistribution of the Library by all those who receive copies directly or indirectly through you, then the only way you could satisfy both it and this License would be to refrain entirely from distribution of the Library.

If any portion of this section is held invalid or unenforceable under any particular circumstance, the balance of the section is intended to apply, and the section as a whole is intended to apply in other circumstances.

It is not the purpose of this section to induce you to infringe any patents or other property right claims or to contest validity of any such claims; this section has the sole purpose of protecting the integrity of the free software distribution system which is implemented by public license practices. Many people have made generous contributions to the wide range of software distributed through that system in reliance on consistent application of that system; it is up to the author/donor to decide if he or she is willing to distribute software through any other system and a licensee cannot impose that choice.

This section is intended to make thoroughly clear what is believed to be a consequence of the rest of this License.

12. If the distribution and/or use of the Library is restricted in certain countries either by patents or by copyrighted interfaces, the original copyright holder who places the Library under this License may add an explicit geographical distribution limitation excluding those countries, so that distribution is permitted only in or among countries not thus excluded. In such case, this License incorporates the limitation as if written in the body of this License.

13. The Free Software Foundation may publish revised and/or new versions of the Lesser General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Library specifies a version number of this License which applies to it and "any later version", you have the option of following the terms and conditions either of that version or of any later version published by the Free Software Foundation. If the Library does not specify a license version number, you may choose any version ever published by the Free Software Foundation.

14. If you wish to incorporate parts of the Library into other free programs whose distribution conditions are incompatible with these, write to the author to ask for permission. For software which is copyrighted by the Free Software Foundation, write to the Free Software Foundation; we sometimes make exceptions for this. Our decision will be guided by the two goals of preserving the free status of all derivatives of our free software and of promoting the sharing and reuse of software generally.

NO WARRANTY

15. BECAUSE THE LIBRARY IS LICENSED FREE OF CHARGE, THERE IS NO WARRANTY FOR THE LIBRARY, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE LIBRARY "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE LIBRARY IS WITH YOU. SHOULD THE LIBRARY PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

16. IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY AND/OR REDISTRIBUTE THE LIBRARY AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE LIBRARY (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE LIBRARY TO OPERATE WITH ANY OTHER SOFTWARE), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Libraries

If you develop a new library, and you want it to be of the greatest possible use to the public, we recommend making it free software that everyone can redistribute and change. You can do so by permitting redistribution under these terms (or, alternatively, under the terms of the ordinary General Public License).

To apply these terms, attach the following notices to the library. It is safest to attach them to the start of each source file to most effectively convey

the exclusion of warranty; and each file should have at least the "copyright" line and a pointer to where the full notice is found.

```
<one line to give the library's name and a brief idea of what it does.>  
Copyright (C) <year> <name of author>
```

This library is free software; you can redistribute it and/or modify it under the terms of the GNU Lesser General Public License as published by the Free Software Foundation; either version 2.1 of the License, or (at your option) any later version.

This library is distributed in the hope that it will be useful,
but WITHOUT ANY WARRANTY; without even the implied warranty of
MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU
Lesser General Public License for more details.

You should have received a copy of the GNU Lesser General Public
License along with this library; if not, write to the Free Software
Foundation, Inc., 51 Franklin Street, Fifth Floor, Boston, MA 02110-1301
USA

Also add information on how to contact you by electronic and paper mail.

You should also get your employer (if you work as a programmer) or your
school, if any, to sign a "copyright disclaimer" for the library, if
necessary. Here is a sample; alter the names:

Yoyodyne, Inc., hereby disclaims all copyright interest in the
library `Frob' (a library for tweaking knobs) written by James Random Hacker.

<signature of Ty Coon>, 1 April 1990
Ty Coon, President of Vice

That's all there is to it!

GNU GENERAL PUBLIC LICENSE
Version 3, 29 June 2007

Copyright (C) 2007 Free Software Foundation, Inc. <<http://fsf.org/>>
Everyone is permitted to copy and distribute verbatim copies
of this license document, but changing it is not allowed.

Preamble

The GNU General Public License is a free, copyleft license for
software and other kinds of works.

The licenses for most software and other practical works are designed
to take away your freedom to share and change the works. By contrast,
the GNU General Public License is intended to guarantee your freedom to
share and change all versions of a program--to make sure it remains free
software for all its users. We, the Free Software Foundation, use the
GNU General Public License for most of our software; it applies also to
any other work released this way by its authors. You can apply it to
your programs, too.

When we speak of free software, we are referring to
freedom, not
price. Our General Public Licenses are designed to make sure that you
have the freedom to distribute copies of free software (and charge for

them if you wish), that you receive source code or can get it if you want it, that you can change the software or use pieces of it in new free programs, and that you know you can do these things.

To protect your rights, we need to prevent others from denying you these rights or asking you to surrender the rights. Therefore, you have certain responsibilities if you distribute copies of the software, or if you modify it: responsibilities to respect the freedom of others.

For example, if you distribute copies of such a program, whether gratis or for a fee, you must pass on to the recipients the same freedoms that you received. You must make sure that they, too, receive or can get the source code. And you must show them these terms so they know their rights.

Developers that use the GNU GPL protect your rights with two steps:

(1)

assert copyright on the software, and (2) offer you this License giving you legal permission to copy, distribute and/or modify it.

For the developers' and authors' protection, the GPL clearly explains that there is no warranty for this free software. For both users' and authors' sake, the GPL requires that modified versions be marked as changed, so that their problems will not be attributed erroneously to authors of previous versions.

Some devices are designed to deny users access to install or run modified versions of the software inside them, although the manufacturer can do so. This is fundamentally incompatible with the aim of protecting users' freedom to change the software. The systematic pattern of such abuse occurs in the area of products for individuals to use, which is precisely where it is most unacceptable. Therefore, we have designed this version of the GPL to prohibit the practice for those products. If such problems arise substantially in other domains, we stand

ready to extend this provision to those domains in future versions of the GPL, as needed to protect the freedom of users.

Finally, every program is threatened constantly by software patents. States should not allow patents to restrict development and use of software on general-purpose computers, but in those that do, we wish to avoid the special danger that patents applied to a free program could make it effectively proprietary. To prevent this, the GPL assures that patents cannot be used to render the program non-free.

The precise terms and conditions for copying, distribution and modification follow.

TERMS AND CONDITIONS

0. Definitions.

"This License" refers to version 3 of the GNU General Public License.

"Copyright" also means copyright-like laws that apply to other kinds of works, such as semiconductor masks.

"The Program" refers to any copyrightable work licensed under this License. Each licensee is addressed as "you". "Licensees" and "recipients" may be individuals or organizations.

To "modify" a work means to copy from or adapt all or part of the work in a fashion requiring copyright permission, other than the making of an exact copy. The resulting work is called a "modified version" of the earlier work or a work "based on" the earlier work.

A "covered work" means either the unmodified Program or a work based on the Program.

To "propagate" a work means to do anything with it that, without permission, would make you directly or secondarily liable for infringement under applicable copyright law, except executing it on a computer or modifying a private copy. Propagation includes copying, distribution (with or without modification), making available to the public, and in some countries other activities as well.

To "convey" a work means any kind of propagation that enables other parties to make or receive copies. Mere interaction with a user through a computer network, with no transfer of a copy, is not conveying.

An interactive user interface displays "Appropriate Legal Notices" to the extent that it includes a convenient and prominently visible feature that (1) displays an appropriate copyright notice, and (2) tells the user that there is no warranty for the work (except to the extent that warranties are provided), that licensees may convey the work under this License, and how to view a copy of this License. If the interface presents a list of user commands or options, such as a menu, a prominent item in the list meets this criterion.

1. Source Code.

The "source code" for a work means the preferred form of the work for making modifications to it. "Object code" means any non-source form of a work.

A "Standard Interface" means an interface that either is an official standard defined by a recognized standards body, or, in the case of interfaces specified for a particular programming language, one that is widely used among developers working in that language.

The

"System Libraries" of an executable work include anything, other than the work as a whole, that (a) is included in the normal form of packaging a Major Component, but which is not part of that Major Component, and (b) serves only to enable use of the work with that Major Component, or to implement a Standard Interface for which an implementation is available to the public in source code form. A "Major Component", in this context, means a major essential component (kernel, window system, and so on) of the specific operating system (if any) on which the executable work runs, or a compiler used to produce the work, or an object code interpreter used to run it.

The "Corresponding Source" for a work in object code form means all the source code needed to generate, install, and (for an executable work) run the object code and to modify the work, including scripts to control those activities. However, it does not include the work's System Libraries, or general-purpose tools or generally available free programs which are used unmodified in performing those activities but which are not part of the work. For example, Corresponding Source includes interface definition files associated with source files for the work, and the source code for shared libraries and dynamically linked subprograms that the work is specifically designed to require, such as by intimate data communication or control flow between those subprograms and other parts of the work.

The Corresponding Source need not include anything that users can regenerate automatically from other parts of the Corresponding Source.

The Corresponding Source for a work in source code form is that same work.

2. Basic Permissions.

All rights granted under this License are granted for the term of copyright on the Program, and are irrevocable provided the stated conditions are met. This License explicitly affirms your unlimited permission to run the unmodified Program. The output from running a covered work is covered

by this License only if the output, given its content, constitutes a covered work. This License acknowledges your

rights of fair use or other equivalent, as provided by copyright law.

You may make, run and propagate covered works that you do not convey, without conditions so long as your license otherwise remains in force. You may convey covered works to others for the sole purpose of having them make modifications exclusively for you, or provide you with facilities for running those works, provided that you comply with the terms of this License in conveying all material for which you do not control copyright. Those thus making or running the covered works for you must do so exclusively on your behalf, under your direction and control, on terms that prohibit them from making any copies of your copyrighted material outside their relationship with you.

Conveying under any other circumstances is permitted solely under the conditions stated below. Sublicensing is not allowed; section 10 makes it unnecessary.

3. Protecting Users' Legal Rights From Anti-Circumvention Law.

No covered work shall be deemed part of an effective technological measure under any applicable law fulfilling obligations under article 11 of the WIPO copyright treaty adopted on 20 December 1996, or similar laws prohibiting or restricting circumvention of such measures.

When you convey a covered work, you waive any legal power to forbid circumvention of technological measures to the extent such circumvention is effected by exercising rights under this License with respect to the covered work, and you disclaim any intention to limit operation or modification of the work as a means of enforcing, against the work's users, your or third parties' legal rights to forbid circumvention of technological measures.

4. Conveying Verbatim Copies.

You may convey verbatim copies of the Program's source code as you receive it, in any medium, provided that you conspicuously and appropriately
publish on each copy an appropriate copyright notice;
keep intact all notices stating that this License and any non-permissive terms added in accord with section 7 apply to the code;
keep intact all notices of the absence of any warranty; and give all recipients a copy of this License along with the Program.

You may charge any price or no price for each copy that you convey, and you may offer support or warranty protection for a fee.

5. Conveying Modified Source Versions.

You may convey a work based on the Program, or the modifications to produce it from the Program, in the form of source code under the terms of section 4, provided that you also meet all of these conditions:

- a) The work must carry prominent notices stating that you modified it, and giving a relevant date.
- b) The work must carry prominent notices stating that it is released under this License and any conditions added under section 7. This requirement modifies the requirement in section 4 to "keep intact all notices".
- c) You must license the entire work, as a whole, under this License to anyone who comes into possession of a copy. This License will therefore apply, along with any applicable section 7 additional terms, to the whole of the work, and all its parts, regardless of how they are packaged. This License gives no permission to license the work in any other way, but it does not invalidate such permission if you have separately received it.
- d) If the work has interactive user interfaces, each must display Appropriate Legal Notices; however, if the Program has interactive interfaces that do not display Appropriate Legal Notices, your work need not make them do so.

A compilation of a covered work with other separate and independent works, which are not by their nature extensions of the covered work, and which are not combined with it such as to form a larger program, in or on a volume of a storage or distribution medium, is called an "aggregate" if the compilation and its resulting copyright are not used to limit the access or legal rights of the compilation's users beyond what the individual works permit. Inclusion of a covered work in an aggregate does not cause this License to apply to the other parts of the aggregate.

6. Conveying Non-Source Forms.

You may convey a covered work in object code form under the terms of sections 4 and 5, provided that you also convey the machine-readable Corresponding Source under the terms of this License, in one of these ways:

- a) Convey the object code in, or embodied in, a physical product (including a physical distribution medium), accompanied by the

Corresponding Source fixed on a durable physical medium customarily used for software interchange.

b) Convey the object code in, or embodied in, a physical product (including a physical distribution medium), accompanied by a written offer, valid for at least three years and valid for as

long as you offer spare parts or customer support for that product model, to give anyone who possesses the object code either (1) a copy of the Corresponding Source for all the software in the product that is covered by this License, on a durable physical medium customarily used for software interchange, for a price no more than your reasonable cost of physically performing this conveying of source, or (2) access to copy the Corresponding Source from a network server at no charge.

c) Convey individual copies of the object code with a copy of the written offer to provide the Corresponding Source. This alternative is allowed only occasionally and noncommercially, and only if you received the object code with such an offer, in accord with subsection 6b.

d) Convey the object code by offering access from a designated place (gratis or for a charge), and offer equivalent access to the Corresponding Source in the same way through the same place at no further charge. You need not require recipients to copy the Corresponding Source along with the object code. If the place to copy the object code is a network server, the Corresponding Source may be on a different server (operated by you or a third party) that supports equivalent copying facilities, provided you maintain clear directions next to the object code saying where to find the Corresponding Source. Regardless of what server hosts the Corresponding Source, you remain obligated to ensure that it is available for as long as needed to satisfy these requirements.

e) Convey the object code using peer-to-peer transmission, provided you inform other peers where the object code and Corresponding Source of the work are being offered to the general public at no charge under subsection 6d.

A separable portion of the object code, whose source code is excluded from the Corresponding Source as a System Library, need not be included in conveying the object code work.

A "User Product" is either (1) a "consumer product", which means any tangible personal property which is normally used for personal, family,

or household purposes, or (2) anything designed or sold for incorporation into a dwelling. In determining whether a product is a consumer product, doubtful cases shall be resolved in favor of coverage. For a particular product received by a particular user, "normally used" refers to a typical or common use of that class of product, regardless of the status of the particular user or of the way in which the particular user actually uses, or expects or is expected to use, the product. A product is a consumer product regardless of whether the product has substantial commercial, industrial or non-consumer uses, unless such uses represent the only significant mode of use of the product.

"Installation Information" for a User Product means any methods, procedures, authorization keys, or other information required to install and execute modified versions of a covered work in that User Product from a modified version of its Corresponding Source. The information must suffice to ensure that the continued functioning of the modified object code is in no case prevented or interfered with solely because modification has been made.

If you convey an object code work under this section in, or with, or specifically for use in, a User Product, and the conveying occurs as part of a transaction in which the right of possession and use of the User Product is transferred to the recipient in perpetuity or for a fixed term (regardless of how the transaction is characterized), the Corresponding Source conveyed under this section must be accompanied by the Installation Information. But this requirement does not apply if neither you nor any third party retains the ability to install modified object code on the User Product (for example, the work has been installed in ROM).

The requirement to provide Installation Information does not include a requirement to continue to provide support service, warranty, or updates for a work that has been modified or installed by the recipient, or for the User Product in which it has been modified or installed. Access to a network may be denied when the modification itself materially and adversely affects the operation of the network or violates the rules and protocols for communication across the network.

Corresponding Source conveyed, and Installation Information provided, in accord with this section must be in a format that is publicly documented (and with an implementation available to the public in source code form), and must require no special password or key for unpacking, reading or copying.

7. Additional Terms.

"Additional permissions" are terms that supplement the terms of this License by making exceptions from one or more of its conditions. Additional permissions that are applicable to the entire Program shall be treated as though they were included in this License, to the extent that they are valid under applicable law. If additional permissions apply only to part of the Program, that part may be used separately under those permissions, but the entire Program remains governed by this License without regard to the additional permissions.

When you convey a copy of a covered work, you may at your option remove any additional permissions from that copy, or from any part of it. (Additional permissions may be written to require their own removal in certain cases when you modify the work.) You may place additional permissions on material, added by you to a covered work, for which you have or can give appropriate copyright permission.

Notwithstanding any other provision of this License, for material you add to a covered work, you may (if authorized by the copyright holders of that material) supplement the terms of this License with terms:

- a) Disclaiming warranty or limiting liability differently from the terms of sections 15 and 16 of this License; or
- b) Requiring preservation of specified reasonable legal notices or author attributions in that material or in the Appropriate Legal Notices displayed by works containing it; or
- c) Prohibiting misrepresentation of the origin of that material, or requiring that modified versions of such material be marked in reasonable ways as different from the original version; or
- d) Limiting the use for publicity purposes of names of licensors or authors of the material; or
- e) Declining to grant rights under trademark law for use of some trade names, trademarks, or service marks; or
- f) Requiring indemnification of licensors and authors of that material by anyone who conveys the material (or modified versions of it) with contractual assumptions of liability to the recipient, for any liability that these contractual assumptions directly impose on those licensors and authors.

All other non-permissive additional terms are considered "further restrictions" within the meaning of section 10. If the Program as you

received it, or any part of it, contains a notice stating that it is governed by this License along with a term that is a further restriction, you may remove that term. If a license document contains a further restriction but permits relicensing or conveying under this License, you may add to a covered work material governed by the terms of that license document, provided that the further restriction does not survive such relicensing or conveying.

If you add terms to a covered work in accord with this section, you must place, in the relevant source files, a statement of the additional terms that apply to those files, or a notice indicating where to find the applicable terms.

Additional terms, permissive or non-permissive, may be stated in the form of a separately written license, or stated as exceptions; the above requirements apply either way.

8. Termination.

You may not propagate or modify a covered work except as expressly provided under this License. Any attempt otherwise to propagate or modify it is void, and will automatically terminate your rights under this License (including any patent licenses granted under the third paragraph of section 11).

However, if you cease all violation of this License, then your license from a particular copyright holder is reinstated (a) provisionally, unless and until the copyright holder explicitly and finally terminates your license, and (b) permanently, if the copyright holder fails to notify you of the violation by some reasonable means prior to 60 days after the cessation.

Moreover, your license from a particular copyright holder is reinstated permanently if the copyright holder notifies you of the violation by some reasonable means, this is the first time you have received notice of violation of this License (for any work) from that copyright holder, and you cure the violation prior to 30 days after your receipt of the notice.

Termination of your rights under this section does not terminate the licenses of parties who have received copies or rights from you under this License. If your rights have been terminated and not permanently reinstated, you do not qualify to receive new licenses for the same material under section 10.

9. Acceptance Not Required for Having Copies.

You are not required to accept this License in order to receive or run a copy of the Program. Ancillary propagation of a covered work occurring solely as a consequence of using peer-to-peer transmission to receive a copy likewise does not require acceptance. However, nothing other than this License grants you permission to propagate or modify any covered work. These actions infringe copyright if you do not accept this License. Therefore, by modifying or propagating a covered work, you indicate your acceptance of this License to do so.

10. Automatic Licensing of Downstream Recipients.

Each time you convey a covered work, the recipient automatically receives a license from the original licensors, to run, modify and propagate that work, subject to this License. You are not responsible for enforcing compliance by third parties with this License.

An "entity transaction" is a transaction transferring control of an organization, or substantially all assets of one, or subdividing an organization, or merging organizations. If propagation of a covered work results from an entity transaction, each party to that transaction who receives a copy of the work also receives whatever licenses to the work the party's predecessor in interest had or could give under the previous paragraph, plus a right to possession of the Corresponding Source of the work from the predecessor in interest, if the predecessor has it or can get it with reasonable efforts.

You may not impose any further restrictions on the exercise of the rights granted or affirmed under this License. For example, you may not impose a license fee, royalty, or other charge for exercise of rights granted under this License, and you may not initiate litigation (including a cross-claim or counterclaim in a lawsuit) alleging that any patent claim is infringed by making, using, selling, offering for sale, or importing the Program or any portion of it.

11. Patents.

A "contributor" is a copyright holder who authorizes use under this License of the Program or a work on which the Program is based. The work thus licensed is called the contributor's "contributor version".

A contributor's "essential patent claims" are all patent claims owned or controlled by the contributor, whether already acquired or hereafter acquired, that would be infringed by some manner, permitted by this License, of making, using, or selling its contributor version, but do not include claims that would be infringed only as a

consequence of further modification of the contributor version. For purposes of this definition, "control" includes the right to grant patent sublicenses in a manner consistent with the requirements of this License.

Each contributor grants you a non-exclusive, worldwide, royalty-free patent license under the contributor's essential patent claims, to make, use, sell, offer for sale, import and otherwise run, modify and propagate the contents of its contributor version.

In the following three paragraphs, a "patent license" is any express agreement or commitment, however denominated, not to enforce a patent (such as an express permission to practice a patent or covenant not to sue for patent infringement). To "grant" such a patent license to a party means to make such an agreement or commitment not to enforce a patent against the party.

If you convey a covered work, knowingly relying on a patent license, and the Corresponding Source of the work is not available for anyone to copy, free of charge and under the terms of this License, through a publicly available network server or other readily accessible means, then you must either (1) cause the Corresponding Source to be so available, or (2) arrange to deprive yourself of the benefit of the patent license for this particular work, or (3) arrange, in a manner consistent with the requirements of this License, to extend the patent license to downstream recipients. "Knowingly relying" means you have actual knowledge that, but for the patent license, your conveying the covered work in a country, or your recipient's use of the covered work in a country, would infringe one or more identifiable patents in that country that you have reason to believe are valid.

If, pursuant to or in connection with a single transaction or arrangement, you convey, or propagate by procuring conveyance of, a covered work, and grant a patent license to some of the parties receiving the covered work authorizing them to use, propagate, modify or convey a specific copy of the covered work, then the patent license you grant is automatically extended to all recipients of the covered work and works based on it.

A patent license is "discriminatory" if it does not include within the scope of its coverage, prohibits the exercise of, or is conditioned on the non-exercise of one or more of the rights that are specifically granted under this License. You may not convey a covered work if you are a party to an arrangement with a third party that is in the business of distributing software, under which you make payment

to the third party based on the extent of your activity of conveying the work, and under which the third party grants, to any of the parties who would receive the covered work from you, a discriminatory patent license (a) in connection with copies of the covered work conveyed by you (or copies made from those copies), or (b) primarily for and in connection with specific products or compilations that contain the covered work, unless you entered into that arrangement, or that patent license was granted, prior to 28 March 2007.

Nothing in this License shall be construed as excluding or limiting any implied license or other defenses to infringement that may otherwise be available to you under applicable patent law.

12. No Surrender of Others' Freedom.

If conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot convey a covered work so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not convey it at all. For example, if you agree to terms that obligate you to collect a royalty for further conveying from those to whom you convey the Program, the only way you could satisfy both those terms and this License would be to refrain entirely from conveying the Program.

13. Use with the GNU Affero General Public License.

Notwithstanding any other provision of this License, you have permission to link or combine any covered work with a work licensed under version 3 of the GNU Affero General Public License into a single combined work, and to convey the resulting work. The terms of this License will continue to apply to the part which is the covered work, but the special requirements of the GNU Affero General Public License, section 13, concerning interaction through a network will apply to the combination as such.

14. Revised Versions of this License.

The Free Software Foundation may publish revised and/or new versions of the GNU General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Program specifies that a certain numbered version of the GNU General Public License "or any later version" applies to it, you

have the option of following the terms and conditions either of that numbered version or of any later version published by the Free Software Foundation. If the Program does not specify a version number of the GNU General Public License, you may choose any version ever published by the Free Software Foundation.

If the Program specifies that a proxy can decide which future versions of the GNU General Public License can be used, that proxy's public statement of acceptance of a version permanently authorizes you to choose that version for the Program.

Later license versions may give you additional or different permissions. However, no additional obligations are imposed on any author or copyright holder as a result of your choosing to follow a later version.

15. Disclaimer of Warranty.

THERE IS NO WARRANTY FOR THE PROGRAM, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE PROGRAM "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE PROGRAM IS WITH YOU. SHOULD THE PROGRAM PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

16. Limitation of Liability.

IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MODIFIES AND/OR CONVEYS THE PROGRAM AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE PROGRAM (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE PROGRAM TO OPERATE WITH ANY OTHER PROGRAMS), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

17.

Interpretation of Sections 15 and 16.

If the disclaimer of warranty and limitation of liability provided above cannot be given local legal effect according to their terms, reviewing courts shall apply local law that most closely approximates an absolute waiver of all civil liability in connection with the

Program, unless a warranty or assumption of liability accompanies a copy of the Program in return for a fee.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Programs

If you develop a new program, and you want it to be of the greatest possible use to the public, the best way to achieve this is to make it free software which everyone can redistribute and change under these terms.

To do so, attach the following notices to the program. It is safest to attach them to the start of each source file to most effectively state the exclusion of warranty; and each file should have at least the "copyright" line and a pointer to where the full notice is found.

```
<one line to give the program's name and a brief idea of what it does.>  
Copyright (C) <year> <name of author>
```

This program is free software: you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation, either version 3 of the License, or (at your option) any later version.

This program is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details.

You should have received a copy of the GNU General Public License along with this program. If not, see <http://www.gnu.org/licenses/>.

Also add information on how to contact you by electronic and paper mail.

If the program does terminal interaction, make it output a short notice like this when it starts in an interactive mode:

```
<program> Copyright (C) <year> <name of author>  
This program comes with ABSOLUTELY NO WARRANTY; for details type `show w'.  
This is free software, and you are welcome to redistribute it  
under certain conditions; type `show c' for details.
```

The hypothetical commands `show w' and `show c' should show the appropriate parts of the General Public License. Of course, your program's commands might be different; for a GUI interface, you would use an "about box".

You should also get your employer (if you work as a programmer) or school, if any, to sign a "copyright disclaimer" for the program, if necessary. For more information on this, and how to apply and follow the GNU GPL, see <<http://www.gnu.org/licenses/>>.

The GNU General Public License does not permit incorporating your program into proprietary programs. If your program is a subroutine library, you may consider it more useful to permit linking proprietary applications with the library. If this is what you want to do, use the GNU Lesser General Public License instead of this License. But first, please read <<http://www.gnu.org/philosophy/why-not-lgpl.html>>.

@c The GNU Free Documentation License.
@center Version 1.3, 3 November 2008

@c This file is intended to be included within another document,
@c hence no sectioning command or @node.

@display
Copyright @copyright{ } 2000, 2001, 2002, 2007, 2008 Free Software Foundation, Inc.
@uref{<http://fsf.org/>}

Everyone is permitted to copy and distribute verbatim copies of this license document, but changing it is not allowed.

@end display

@enumerate 0
@item
PREAMBLE

The purpose of this License is to make a manual, textbook, or other functional and useful document @dfn{free} in the sense of freedom: to assure everyone the effective freedom to copy and redistribute it, with or without modifying it, either commercially or noncommercially. Secondly, this License preserves for the author and publisher a way to get credit for their work, while not being considered responsible for modifications made by others.

This License is a kind of ``copyleft'', which means that derivative works of the document must themselves be free in the same sense. It complements the GNU General Public License, which is a copyleft license designed for free software.

We have designed this License in order to use it for manuals for free software, because free software needs free documentation: a free program should come with manuals providing the same freedoms that the software does. But this License is not limited to software manuals;

it can be used for any textual work, regardless of subject matter or whether it is published as a printed book. We recommend this License principally for works whose purpose is instruction or reference.

@item

APPLICABILITY AND DEFINITIONS

This License applies to any manual or other work, in any medium, that contains a notice placed by the copyright holder saying it can be distributed under the terms of this License. Such a notice grants a world-wide, royalty-free license, unlimited in duration, to use that work under the conditions stated herein. The ``Document'', below, refers

to any such manual or work. Any member of the public is a licensee, and is addressed as ``you''. You accept the license if you copy, modify or distribute the work in a way requiring permission under copyright law.

A ``Modified Version'' of the Document means any work containing the Document or a portion of it, either copied verbatim, or with modifications and/or translated into another language.

A ``Secondary Section'' is a named appendix or a front-matter section of the Document that deals exclusively with the relationship of the publishers or authors of the Document to the Document's overall subject (or to related matters) and contains nothing that could fall directly within that overall subject. (Thus, if the Document is in part a textbook of mathematics, a Secondary Section may not explain any mathematics.) The relationship could be a matter of historical connection with the subject or with related matters, or of legal, commercial, philosophical, ethical or political position regarding them.

The ``Invariant Sections'' are certain Secondary Sections whose titles are designated, as being those of Invariant Sections, in the notice that says that the Document is released under this License. If a section does not fit the above definition of Secondary then it is not allowed to be designated as Invariant. The Document may contain zero Invariant Sections. If the Document does not identify any Invariant Sections then there are none.

The ``Cover Texts'' are certain short passages of text that are listed, as Front-Cover Texts or Back-Cover Texts, in the notice that says that the Document is released under this License. A Front-Cover Text may be at most 5 words, and a Back-Cover Text may be at most 25 words.

A ``Transparent'' copy of the Document means a machine-readable copy,

represented in a format whose specification is available to the general public, that is suitable for revising the document straightforwardly with generic text editors or (for images composed of pixels) generic paint programs or (for drawings) some widely available drawing editor, and that is suitable for input to text formatters or for automatic translation to a variety of formats suitable for input to text formatters. A copy made in an otherwise Transparent file format whose markup, or absence of markup, has been arranged to thwart or discourage subsequent modification by readers is not Transparent. An image format is not Transparent if used for any substantial amount of text. A copy that is not ``Transparent" is called ``Opaque".

Examples of suitable formats for Transparent copies include plain ASCII without markup, Texinfo input format, La@TeX{ } input format, SGML or XML using a publicly available DTD, and standard-conforming simple HTML, PostScript or PDF designed for human modification. Examples of transparent image formats include PNG, XCF and JPG@. Opaque formats include proprietary formats that can be read and edited only by proprietary word processors, SGML or XML for which the DTD and/or processing tools are not generally available, and the machine-generated HTML, PostScript or PDF produced by some word processors for output purposes only.

The ``Title Page" means, for a printed book, the title page itself, plus such following pages as are needed to hold, legibly, the material this License requires to appear in the title page. For works in formats which do not have any title page as such, ``Title Page" means the text near the most prominent appearance of the work's title, preceding the beginning of the body of the text.

The ``publisher" means any person or entity that distributes copies of the Document to the public.

A section ``Entitled XYZ" means a named subunit of the Document whose title either is precisely XYZ or contains XYZ in parentheses following text that translates XYZ in another language. (Here XYZ stands for a specific section name mentioned below, such as ``Acknowledgements", ``Dedications", ``Endorsements", or ``History".) To ``Preserve the Title" of such a section when you modify the Document means that it remains a section ``Entitled XYZ" according to this definition.

The Document may include Warranty Disclaimers next to the notice which states that this License applies to the Document. These Warranty

Disclaimers are considered to be included by reference in this License, but only as regards disclaiming warranties: any other implication that these Warranty Disclaimers may have is void and has no effect on the meaning of this License.

@item

VERBATIM COPYING

You may copy and distribute the Document in any medium, either commercially or noncommercially, provided that this License, the copyright notices, and the license notice saying this License applies to the Document are reproduced in all copies, and that you add no other conditions whatsoever to those of this License. You may not use technical measures to obstruct or control the reading or further copying of the copies you make or distribute. However, you may accept compensation in exchange for copies. If you distribute a large enough number of copies you must also follow the conditions in section 3.

You may also lend copies, under the same conditions stated above, and you may publicly display copies.

@item

COPYING IN QUANTITY

If you publish printed copies (or copies in media that commonly have printed covers) of the Document, numbering more than 100, and the Document's license notice requires Cover Texts, you must enclose the copies in covers that carry, clearly and legibly, all these Cover Texts: Front-Cover Texts on the front cover, and Back-Cover Texts on the back cover. Both covers must also clearly and legibly identify you as the publisher of these copies. The front cover must present the full title with all words of the title equally prominent and visible. You may add other material on the covers in addition. Copying with changes limited to the covers, as long as they preserve the title of the Document and satisfy these conditions, can be treated as verbatim copying in other respects.

If the required texts for either cover are too voluminous to fit legibly, you should put the first ones listed (as many as fit reasonably) on the actual cover, and continue the rest onto adjacent pages.

If you publish or distribute Opaque copies of the Document numbering more than 100, you must either include a machine-readable Transparent copy along with each Opaque copy, or state in or with each Opaque copy a computer-network location from which the general network-using

public has access to download using public-standard network protocols a complete Transparent copy of the Document, free of added material. If you use the latter option, you must take reasonably prudent steps, when you begin distribution of Opaque copies in quantity, to ensure that this Transparent copy will remain thus accessible at the stated location until at least one year after the last time you distribute an Opaque copy (directly or through your agents or retailers) of that edition to the public.

It is requested, but not required, that you contact the authors of the Document well before redistributing any large number of copies, to give them a chance to provide you with an updated version of the Document.

@item

MODIFICATIONS

You may copy and distribute a Modified Version of the Document under the conditions of sections 2 and 3 above, provided that you release the Modified Version under precisely this License, with the Modified Version filling the role of the Document, thus licensing distribution and modification of the Modified Version to whoever possesses a copy of it. In addition, you must do these things in the Modified Version:

@enumerate A

@item

Use in the Title Page (and on the covers, if any) a title distinct from that of the Document, and from those of previous versions (which should, if there were any, be listed in the History section of the Document). You may use the same title as a previous version if the original publisher of that version gives permission.

@item

List on the Title Page, as authors, one or more persons or entities responsible for authorship of the modifications in the Modified Version, together with at least five of the principal authors of the Document (all of its principal authors, if it has fewer than five), unless they release you from this requirement.

@item

State on the Title page the name of the publisher of the Modified Version, as the publisher.

@item

Preserve all the copyright notices of the Document.

@item

Add an appropriate copyright notice for your modifications adjacent to the other copyright notices.

@item

Include, immediately after the copyright notices, a license notice giving the public permission to use the Modified Version under the terms of this License, in the form shown in the Addendum below.

@item

Preserve in that license notice the full lists of Invariant Sections and required Cover Texts given in the Document's license notice.

@item

Include an unaltered copy of this License.

@item

Preserve the section Entitled ``History'', Preserve its Title, and add to it an item stating at least the title, year, new authors, and publisher of the Modified Version as given on the Title Page. If there is no section Entitled ``History'' in the Document, create one stating the title, year, authors, and publisher of the Document as given on its Title Page, then add an item describing the Modified Version as stated in the previous sentence.

@item

Preserve the network location, if any, given in the Document for public access to a Transparent copy of the Document, and likewise the network locations given in the Document for previous versions it was based on. These may be placed in the ``History'' section. You may omit a network location for a work that was published at least four years before the Document itself, or if the original publisher of the version it refers to gives permission.

@item

For any section Entitled ``Acknowledgements'' or ``Dedications'', Preserve the Title of the section, and preserve in the section all the substance and tone of each of the contributor acknowledgements and/or dedications given therein.

@item

Preserve all the Invariant Sections of the Document, unaltered in their text and in their titles. Section numbers or the equivalent are not considered part of the section titles.

@item

Delete any section Entitled ``Endorsements''. Such a section

may not be included in the Modified Version.

@item

Do not retitle any existing section to be Entitled ``Endorsements" or to conflict in title with any Invariant Section.

@item

Preserve any Warranty Disclaimers.

@end enumerate

If the Modified Version includes new front-matter sections or appendices that qualify as Secondary Sections and contain no material copied from the Document, you may at your option designate some or all of these sections as invariant. To do this, add their titles to the list of Invariant

Sections in the Modified Version's license notice.

These titles must be distinct from any other section titles.

You may add a section Entitled ``Endorsements", provided it contains nothing but endorsements of your Modified Version by various parties---for example, statements of peer review or that the text has been approved by an organization as the authoritative definition of a standard.

You may add a passage of up to five words as a Front-Cover Text, and a passage of up to 25 words as a Back-Cover Text, to the end of the list of Cover Texts in the Modified Version. Only one passage of Front-Cover Text and one of Back-Cover Text may be added by (or through arrangements made by) any one entity. If the Document already includes a cover text for the same cover, previously added by you or by arrangement made by the same entity you are acting on behalf of, you may not add another; but you may replace the old one, on explicit permission from the previous publisher that added the old one.

The author(s) and publisher(s) of the Document do not by this License give permission to use their names for publicity for or to assert or imply endorsement of any Modified Version.

@item

COMBINING DOCUMENTS

You may combine the Document with other documents released under this License, under the terms defined in section 4 above for modified versions, provided that you include in the combination all of the Invariant Sections of all of the original documents, unmodified, and list them all as Invariant Sections of your combined work in its license notice, and that you preserve all their Warranty Disclaimers.

The combined work need only contain one copy of this License, and multiple identical Invariant Sections may be replaced with a single copy. If there are multiple Invariant Sections with the same name but different contents, make the title of each such section unique by adding at the end of it, in parentheses, the name of the original author or publisher of that section if known, or else a unique number.

Make the same adjustment to the section titles in the list of Invariant Sections in the license notice of the combined work.

In the combination, you must combine any sections Entitled ``History'' in the various original documents, forming one section Entitled ``History''; likewise combine any sections Entitled ``Acknowledgements'', and any sections Entitled ``Dedications''. You must delete all sections Entitled ``Endorsements.''

@item

COLLECTIONS OF DOCUMENTS

You may make a collection consisting of the Document and other documents released under this License, and replace the individual copies of this License in the various documents with a single copy that is included in the collection, provided that you follow the rules of this License for verbatim copying of each of the documents in all other respects.

You may extract a single document from such a collection, and distribute it individually under this License, provided you insert a copy of this License into the extracted document, and follow this License in all other respects regarding verbatim copying of that document.

@item

AGGREGATION WITH INDEPENDENT WORKS

A compilation of the Document or its derivatives with other separate and independent documents or works, in or on a volume of a storage or distribution medium, is called an ``aggregate'' if the copyright resulting from the compilation is not used to limit the legal rights of the compilation's users beyond what the individual works permit. When the Document is included in an aggregate, this License does not apply to the other works in the aggregate which are not themselves derivative works of the Document.

If the Cover Text requirement of section 3 is applicable to these copies of the Document, then if the Document is less than one half of the entire aggregate, the Document's Cover Texts may be placed on covers that bracket the Document within the aggregate, or the

electronic equivalent of covers if the Document is in electronic form.

Otherwise they must appear on printed covers that bracket the whole aggregate.

@item

TRANSLATION

Translation is considered a kind of modification, so you may distribute translations of the Document under the terms of section 4.

Replacing Invariant Sections with translations requires special permission from their copyright holders, but you may include translations of some or all Invariant Sections in addition to the original versions of these Invariant Sections. You may include a translation of this License, and all the license notices in the Document, and any Warranty Disclaimers, provided that you also include the original English version of this License and the original versions of those notices and disclaimers. In case of a disagreement between the translation and the original version of this License or a notice or disclaimer, the original version will prevail.

If a section in the Document is Entitled ``Acknowledgements'', ``Dedications'', or ``History'', the requirement (section 4) to Preserve its Title (section 1) will typically require changing the actual title.

@item

TERMINATION

You may not copy, modify, sublicense, or distribute the Document except as expressly provided under this License. Any attempt otherwise to copy, modify, sublicense, or distribute it is void, and will automatically terminate your rights under this License.

However, if you cease all violation of this License, then your license from a particular copyright holder is reinstated (a) provisionally, unless and until the copyright holder explicitly and finally terminates your license, and (b) permanently, if the copyright holder fails to notify you of the violation by some reasonable means prior to 60 days after the cessation.

Moreover, your license from a particular copyright holder is reinstated permanently if the copyright holder notifies you of the violation by some reasonable means, this is the first time you have received notice of violation of this License (for any work) from that copyright holder, and you cure the violation prior to 30 days after

your receipt of the notice.

Termination of your rights under this section does not terminate the licenses of parties who have received copies or rights from you under this License. If your rights have been terminated and not permanently reinstated, receipt of a copy of some or all of the same material does not give you any rights to use it.

@item

FUTURE REVISIONS OF THIS LICENSE

The Free Software Foundation may publish new, revised versions of the GNU Free Documentation License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns. See [@uref{http://www.gnu.org/copyleft/}](http://www.gnu.org/copyleft/).

Each version of the License is given a distinguishing version number. If the Document specifies that a particular numbered version of this License ``or any later version" applies to it, you have the option of following the terms and conditions either of that specified version or of any later version that has been published (not as a draft) by the Free Software Foundation. If the Document does not specify a version number of this License, you may choose any version ever published (not as a draft) by the Free Software Foundation. If the Document specifies that a proxy can decide which future versions of this License can be used, that proxy's public statement of acceptance of a version permanently authorizes you to choose that version for the Document.

@item

RELICENSING

``Massive Multiauthor Collaboration Site" (or ``MMC Site") means any World Wide Web server that publishes copyrightable works and also provides prominent facilities for anybody to edit those works. A public wiki that anybody can edit is an example of such a server. A ``Massive Multiauthor Collaboration" (or ``MMC") contained in the site means any set of copyrightable works thus published on the MMC site.

``CC-BY-SA" means the Creative Commons Attribution-Share Alike 3.0 license published by Creative Commons Corporation, a not-for-profit corporation with a principal place of business in San Francisco, California, as well as future copyleft versions of that license published by that same organization.

``Incorporate" means to publish or republish a Document, in whole or in part, as part of another Document.

An MMC is ``eligible for relicensing" if it is licensed under this License, and if all works that were first published under this License somewhere other than this MMC, and subsequently incorporated in whole or in part into the MMC, (1) had no cover texts or invariant sections, and (2) were thus incorporated prior to November 1, 2008.

The operator of an MMC Site may republish an MMC contained in the site under CC-BY-SA on the same site at any time before August 1, 2009, provided the MMC is eligible for relicensing.

@end enumerate

@page

@heading ADDENDUM: How to use this License for your documents

To use this License in a document you have written, include a copy of the License in the document and put the following copyright and license notices just after the title page:

@smallexample

@group

Copyright (C) @var{year} @var{your name}.

Permission is granted to copy, distribute and/or modify this document under the terms of the GNU Free Documentation License, Version 1.3 or any later version published by the Free Software Foundation; with no Invariant Sections, no Front-Cover Texts, and no Back-Cover Texts. A copy of the license is included in the section entitled ``GNU Free Documentation License".

@end group

@end smallexample

If you have Invariant Sections, Front-Cover Texts and Back-Cover Texts, replace the ``with@dots{ }Texts."@: line with this:

@smallexample

@group

with the Invariant Sections being @var{list their titles}, with the Front-Cover Texts being @var{list}, and with the Back-Cover Texts being @var{list}.

@end group

@end smallexample

If you have Invariant

Sections without Cover Texts, or some other combination of the three, merge those two alternatives to suit the situation.

If your document contains nontrivial examples of program code, we recommend releasing these examples in parallel under your choice of free software license, such as the GNU General Public License, to permit their use in free software.

```
@c Local Variables:
@c ispell-local-pdict: "ispell-dict"
@c End:
```

1.50 util-linux 1:2.31.1-0.4ubuntu3.7

1.50.1 Available under license :

```
Format: http://www.debian.org/doc/packaging-manuals/copyright-format/1.0/
Upstream-Name: util-linux
Upstream-Contact: util-linux@vger.kernel.org
Source: https://www.kernel.org/pub/linux/utils/util-linux/
```

Files: *

```
Copyright:  Michal Luscon <mluscon@redhat.com>
            1986 Gary S. Brown
            1990 Gordon Irlam (gordoni@cs.ua.oz.au)
            1991, 1992 Linus Torvalds
            1991-2004 Miquel van Smoorenburg
            1992 A. V. Le Blanc (LeBlanc@mcc.ac.uk)
            1992-1997 Michael K. Johnson, johnsonm@redhat.com
            1993, 1994, 1995, 1996, 1997, 1998, 1999, 2000, 2001, 2002,
            2003, 2004, 2005, 2008 Theodore Ts'o <tytso@mit.edu>
            1994 Kevin E. Martin (martin@cs.unc.edu)
            1994 Salvatore Valente <svalente@mit.edu>
            1994,1996 Alessandro Rubini (rubini@ipvvis.unipv.it)
            1994-2005 Jeff Tranter (tranter@pobox.com)
            1995, 1999, 2000 Andries E. Brouwer <aeb@cwi.nl>
            1997-2005 Frodo Looijaard
            <frodo@frodo.looijaard.name>
            1998 Danek Duvall <duvall@alumni.princeton.edu>
            1999 Andreas Dilger
            1999-2002 Transmeta Corporation
            1999, 2000, 2002-2009, 2010, 2011, 2012, 2014 Red Hat, Inc.
            2000 Werner Almesberger
            2004-2006 Michael Holzt, kju -at- fqdn.org
            2005 Adrian Bunk
            2007-2014 Karel Zak <kzak@redhat.com>
            2007, 2011 SuSE LINUX Products GmbH
```

2008 Cai Qian <qcai@redhat.com>
2008 Hayden A. James (hayden.james@gmail.com)
2008 James Youngman <jay@gnu.org>
2008 Roy Peled, the.roy.peled -at- gmail.com
2009 Mikhail Gusarov <dottedmag@dottedmag.net>
2010, 2011, 2012 Davidlohr Bueso <dave@gnu.org>
2010 Jason Borden <jborden@bluehost.com>A
2010 Hajime Taira <htaira@redhat.com>
2010 Masatake Yamato <yamato@redhat.com>
2011 IBM Corp.
2012 Andy Lutomirski <luto@amacapital.net>
2012 Lennart Poettering
2012 Sami Kerola <kerolasa@iki.fi>
2012 Cody Maloney <cmaloney@theoreticalchaos.com>
2012 Werner Fink <werner@suse.de>
2013,2014 Ondrej Oprala <ooprala@redhat.com>

License: GPL-2+

Files: schedutils/ionice.c

Copyright: 2005 Jens Axboe <jens@axboe.dk>

License: GPL-2

Files: schedutils/chrt.c

 schedutils/taskset.c

Copyright: 2004 Robert Love <rml@tech9.net>

 2010 Karel Zak <kzak@redhat.com>

License: GPL-2

Files: disk-utils/raw.c

Copyright: 1999, 2000, Red Hat Software

License: GPL-2

Files: sys-utils/nsenter.c

Copyright: 2012-2013 Eric Biederman <ebiederm@xmission.com>

License: GPL-2

Files: disk-utils/mkfs.minix.c

 disk-utils/mkswap.c

Copyright: 1991, 1992 Linus Torvalds

License: GPL-2

Files: lib/at.c

 lib/blkdev.c

 lib/loopdev.c

 lib/sysfs.c

 lib/ttyutils.c

 lib/xgetpass.c

 misc-utils/mcookie.c

sys-utils/setsid.c

text-utils/line.c

Copyright:

n/a

License: public-domain

Files: login-utils/vipw.c

misc-utils/cal.c

misc-utils/kill.c

misc-utils/logger.c

misc-utils/look.c

misc-utils/whereis.c

sys-utils/renice.c

term-utils/mesg.c

term-utils/script.c

term-utils/ttymsg.c

term-utils/wall.c

term-utils/write.c

text-utils/col.c

text-utils/colcrt.c

text-utils/colrm.c

text-utils/column.c

text-utils/hexdump.c

text-utils/hexdump.h

text-utils/hexdump-conv.c

text-utils/hexdump-display.c

text-utils/hexdump-parse.c

text-utils/rev.c

text-utils/ul.c

Copyright: 1980, 1983, 1987, 1988, 1989, 1990, 1991, 1992, 1993, 1994

The Regents of the University of California

2014 Sami Kerola <kerolasa@iki.fi>

2014 Karel Zak <kzak@redhat.com>

License: BSD-4-clause

Files: text-utils/tailf.c

Copyright: 1996, 2003 Rickard E. Faith (faith@acm.org)

License: MIT

Files:

sys-utils/flock.c

Copyright: 2003-2005 H. Peter Anvin

License: MIT

Files: text-utils/pg.c

Copyright: 2000-2001 Gunnar Ritter

License: BSD-2-clause

Files: login-utils/last-deprecated.c
Copyright: 1987 Regents of the University of California
License: BSD-2-clause

Files: login-utils/login.c
Copyright: 1980, 1987, 1988 The Regents of the University of California.
2011 Karel Zak <kzak@redhat.com>
License: BSD-2-clause

Files: login-utils/logindefs.c
Copyright: 2003, 2004, 2005 Thorsten Kukuk
License: BSD-3-clause

Files: libuuid/*
libuuid/src/*
libuuid/man/*
Copyright: 1996, 1997, 1998, 1999, 2007 Theodore Ts'o.
1999 Andreas Dilger (adilger@enel.ucalgary.ca)
License: BSD-3-clause

Files: lib/procutils.c
include/xalloc.h
Copyright: 2010, 2011 Davidlohr Bueso <dave@gnu.org>
License: LGPL-2+

Files: */colors.*
Copyright: 2012 Ondrej Oprala <ooprala@redhat.com>
2012-2014 Karel Zak <kzak@redhat.com>
License: LGPL-2+

Files: login-utils/setpwnam.h
login-utils/setpwnam.c
Copyright: 1994 Martin Schulze <joe@infodrom.north.de>
1994 Salvatore Valente <svalente@mit.edu>
License: LGPL-2+

Files: libfdisk/*
libfdisk/src/*
Copyright: 2007-2013 Karel Zak <kzak@redhat.com>
2012 Davidlohr Bueso <dave@gnu.org>
License: LGPL-2.1+

Files: lib/cpuset.c
/match.
lib/canonicalize.c
include/at.h
Copyright: 2008-2009, 2010, 2011, 2012 Karel Zak <kzak@redhat.com>
License: LGPL-2.1+

Files: */mbsalign.*

Copyright: 2009-2010 Free Software Foundation, Inc.

2010-2013 Karel Zak <kzak@redhat.com>

License: LGPL-2.1+

Files: */readutmp.*

Copyright: 1992-2007, 2009-2014 Free Software Foundation, Inc.

License: GPL-3+

Files: */timeutils.*

Copyright: 2010 Lennart Poettering

License: LGPL-2.1+

Files: include/list.h

Copyright: 2008 Karel Zak <kzak@redhat.com>

1999-2008 by Theodore Ts'o

License: LGPL

Files: libblkid/*

libblkid/src/*

libblkid/samples/*

libblkid/src/partitions/*

libblkid/src/superblocks/*

libblkid/src/topology/*

Copyright: 1999, 2001 Andries Brouwer

1995, 1995, 1996, 1997, 1999, 2000, 2001, 2002, 2003, 2004

Theodore Ts'o.

2001 Andreas Dilger (adilger@turbolinux.com)

2004-2008 Kay Sievers <kay.sievers@vrfy.org>

2008-2013 Karel Zak <kzak@redhat.com>

2009 Bastian Friedrich <bastian.friedrich@collax.com>

2009 Corentin Chary <corentincj@iksaif.net>

2009 Mike Hommey <mh@glandium.org>

2009 Red Hat, Inc.

2009-2010 Andreas Dilger <adilger@sun.com>

2010 Andrew Nayenko <resver@gmail.com>

2010 Jeroen Oortwijn <oortwijn@gmail.com>

2010 Jiro SEKIBA <jir@unicus.jp>

2011 Philipp Marek <philipp.marek@linbit.com>

2012 Milan Broz <mbroz@redhat.com>

2013 Alejandro Martinez Ruiz <alex@nowcomputing.com>

2013 Eric Sandeen <sandeen@redhat.com>

2013 Rolf Fokkens <rolf@fokkens.nl>

2013 Zeeshan Ali (Khattak) <zeeshanak@gnome.org>

License: LGPL-2.1+

Files: include/cpuset.h

lib/randutils.c

Copyright: *unknown*

License: LGPL

Files: misc-utils/blkid.c

Copyright: 2001 Andreas Dilger

License: LGPL

Files: libmount/*

libmount/src/*

Copyright: 2008-2012 Karel Zak <kzak@redhat.com>

License: LGPL-2.1+

Files: libmount/python/*

Copyright: 2013, Red Hat, Inc.

License: LGPL-3+

Files: libsmartcols/*

Copyright: 2009-2014 Karel Zak <kzak@redhat.com>

2014 Ondrej Oprala <ooprala@redhat.com>

License: LGPL

Files: debian/*

Copyright: Guy Maor <maor@debian.org>

Sean 'Shaleh' Perry <shaleh@debian.org>

Adrian Bunk <bunk@stusta.de>

LaMont Jones <lamont@debian.org>

2014 Andreas Henriksson <andreas@fatal.se>

License: GPL-2+

License: public-domain

The files tagged with this license contains the following paragraphs:

.

No copyright

is claimed. This code is in the public domain; do with it what you wish.

.

Written by Karel Zak <kzak@redhat.com>

License: GPL-2

This program is free software; you can redistribute it and/or modify it under the terms of the GNU General Public License, v2, as published by the Free Software Foundation

.

This program is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of

MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details.

.
You should have received a copy of the GNU General Public License along with this program; if not, write to the Free Software Foundation, Inc., 51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA.

.
On Debian systems, the complete text of the GNU General Public License version 2 can be found in ``usr/share/common-licenses/GPL-2'`.

License: GPL-2+

This program is free software; you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation; either version 2 of the License, or (at your option) any later version.

.
This program is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details.

.
You should have received a copy of the GNU General Public License along with this program; if not, write to the Free Software Foundation, Inc., 51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA.

.
On Debian systems, the complete text of the GNU General Public License version 2 can be found in ``usr/share/common-licenses/GPL-2'`.

License: GPL-3+

This program is free software: you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation; either version 3 of the License, or (at your option) any later version.

.
This program is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details.

.
You should have received a copy of the GNU General Public License along with this program. If not, see <http://www.gnu.org/licenses/>.

.
On Debian systems, the complete text of the GNU General Public License version 3 can be found in ``usr/share/common-licenses/GPL-3'`.

License: BSD-2-clause

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

1. Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.
2. Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.

License: BSD-3-clause

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

.

1) Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.

.

2) Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.

.

3) Neither the name of the ORGANIZATION nor the names of its contributors may be used to endorse or promote products derived from this software without specific prior written permission.

.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED.

IN NO EVENT SHALL THE COPYRIGHT HOLDER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

License: BSD-4-clause

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

1. Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.
2. Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials

provided with the distribution.

3. All advertising materials mentioning features or use of this software must display the following acknowledgement:

This product includes software developed by the University of California, Berkeley and its contributors.

4. Neither the name of the University nor the names of its contributors may be used to endorse or promote products derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE REGENTS AND CONTRIBUTORS ``AS IS'' AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE REGENTS OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

License: LGPL

This file may be redistributed under the terms of the GNU Lesser General Public License.

On Debian systems, the complete text of the GNU Lesser General Public License can be found in `/usr/share/common-licenses/LGPL`.

License: LGPL-2+

This program is free software: you can redistribute it and/or modify it under the terms of the GNU Lesser General Public License as published by the Free Software Foundation, either version 2 of the License, or (at your option) any later version.

This program is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU Lesser General Public License for more details.

You should have received a copy of the GNU Lesser General Public License along with this program. If not, see <http://www.gnu.org/licenses/>.

The complete text of the GNU Lesser General Public License can be found in `/usr/share/common-licenses/LGPL-2` file.

License: LGPL-2.1+

This program is free software; you can redistribute it and/or modify it under the terms of the GNU Lesser General Public License as published by the Free Software Foundation; either version 2.1, or (at your option) any later version.

.

This program is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU Lesser General Public License for more details.

.

You should have received a copy of the GNU Lesser General Public License along with this program; if not, write to the Free Software Foundation, Inc., 51 Franklin Street, Fifth Floor, Boston, MA 02110-1301, USA.

.

On Debian systems, the complete text of the GNU Lesser General Public License version 2.1 can be found in `/usr/share/common-licenses/LGPL-2.1`.

License: LGPL-3+

This package is free software; you can redistribute it and/or modify it under the terms of the GNU Lesser General Public License as published by the Free Software Foundation; either version 3 of the License, or (at your option) any later version.

.

This package is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU Lesser General Public License for more details.

.

You should have received a copy of the GNU General Public License along with this program. If not, see <http://www.gnu.org/licenses/>.

.

On Debian systems, the complete text of the GNU Lesser General Public License can be found in `"/usr/share/common-licenses/LGPL-3"`.

License: MIT

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

.

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

GNU GENERAL PUBLIC LICENSE

Version 2, June 1991

Copyright (C) 1989, 1991 Free Software Foundation, Inc.,
51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA
Everyone is permitted to copy and distribute verbatim copies
of this license document, but changing it is not allowed.

Preamble

The licenses for most software are designed to take away your freedom to share and change it. By contrast, the GNU General Public License is intended to guarantee your freedom to share and change free software--to make sure the software is free for all its users. This General Public License applies to most of the Free Software Foundation's software and to any other program whose authors commit to using it. (Some other Free Software Foundation software is covered by the GNU Lesser General Public License instead.) You can apply it to your programs, too.

When we speak of free software, we are referring to freedom, not price.

Our General Public Licenses are designed to make sure that you have the freedom to distribute copies of free software (and charge for this service if you wish), that you receive source code or can get it if you want it, that you can change the software or use pieces of it in new free programs; and that you know you can do these things.

To protect your rights, we need to make restrictions that forbid anyone to deny you these rights or to ask you to surrender the rights. These restrictions translate to certain responsibilities for you if you distribute copies of the software, or if you modify it.

For example, if you distribute copies of such a program, whether gratis or for a fee, you must give the recipients all the rights that you have. You must make sure that they, too, receive or can get the source code. And you must show them these terms so they know their rights.

We protect your rights with two steps: (1) copyright the software, and

(2) offer you this license which gives you legal permission to copy, distribute and/or modify the software.

Also, for each author's protection and ours, we want to make certain that everyone understands that there is no warranty for this free software. If the software is modified by someone else and passed on, we want its recipients to know that what they have is not the original, so that any problems introduced by others will not reflect on the original authors' reputations.

Finally, any free program is threatened constantly by software patents. We wish to avoid the danger that redistributors of a free program will individually obtain patent licenses, in effect making the program proprietary. To prevent this, we have made it clear that any patent must be licensed for everyone's free use or not licensed at all.

The precise terms and conditions for copying, distribution and modification follow.

GNU GENERAL PUBLIC LICENSE TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

0. This License applies to any program or other work which contains a notice placed by the copyright holder saying it may be distributed under the terms of this General Public License. The "Program", below, refers to any such program or work, and a "work based on the Program" means either the Program or any derivative work under copyright law: that is to say, a work containing the Program or a portion of it, either verbatim or with modifications and/or translated into another language. (Hereinafter, translation is included without limitation in the term "modification".) Each licensee is addressed as "you".

Activities other than copying, distribution and modification are not covered by this License; they are outside its scope. The act of running the Program is not restricted, and the output from the Program is covered only if its contents constitute a work based on the Program (independent of having been made by running the Program). Whether that is true depends on what the Program does.

1. You may copy and distribute verbatim copies of the Program's source code as you receive it, in any medium, provided that you conspicuously and appropriately publish on each copy an appropriate copyright notice and disclaimer of warranty; keep intact all the notices that refer to this License and to the absence of any warranty; and give any other recipients of the Program a copy of this License along with the Program.

You may charge a fee for the physical act of transferring a copy, and you may at your option offer warranty protection in exchange for a fee.

2. You may modify your copy or copies of the Program or any portion of it, thus forming a work based on the Program, and copy and distribute such modifications or work under the terms of Section 1 above, provided that you also meet all of these conditions:

- a) You must cause the modified files to carry prominent notices stating that you changed the files and the date of any change.
- b) You must cause any work that you distribute or publish, that in whole or in part contains or is derived from the Program or any part thereof, to be licensed as a whole at no charge to all third parties under the terms of this License.
- c) If the modified program normally reads commands interactively when run, you must cause it, when started running for such interactive use in the most ordinary way, to print or display an announcement including an appropriate copyright notice and a notice that there is no warranty (or else, saying that you provide a warranty) and that users may redistribute the program under these conditions, and telling the user how to view a copy of this License. (Exception: if the Program itself is interactive but does not normally print such an announcement, your work based on the Program is not required to print an announcement.)

These requirements apply to the modified work as a whole. If identifiable sections of that work are not derived from the Program, and can be reasonably considered independent and separate works in themselves, then this License, and its terms, do not apply to those sections when you distribute them as separate works. But when you distribute the same sections as part of a whole which is a work based on the Program, the distribution of the whole must be on the terms of this License, whose permissions for other licensees extend to the entire whole, and thus to each and every part regardless of who wrote it.

Thus, it is not the intent of this section to claim rights or contest your rights to work written entirely by you; rather, the intent is to exercise the right to control the distribution of derivative or collective works based on the Program.

In addition, mere aggregation of another work not based on the Program with the Program (or with a work based on the Program) on a volume of a storage or distribution medium does not bring the other work under

the scope of this License.

3. You may copy and distribute the Program (or a work based on it, under Section 2) in object code or executable form under the terms of Sections 1 and 2 above provided that you also do one of the following:

- a) Accompany it with the complete corresponding machine-readable source code, which must be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange; or,
- b) Accompany it with a written offer, valid for at least three years, to give any third party, for a charge no more than your cost of physically performing source distribution, a complete machine-readable copy of the corresponding source code, to be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange; or,
- c) Accompany it with the information you received as to the offer to distribute corresponding source code. (This alternative is allowed only for noncommercial distribution and only if you received the program in object code or executable form with such an offer, in accord with Subsection b above.)

The source code for a work means the preferred form of the work for making modifications to it. For an executable work, complete source code means all the source code for all modules it contains, plus any associated interface definition files, plus the scripts used to control compilation and installation of the executable. However, as a special exception, the source code distributed need not include anything that is normally distributed (in either source or binary form) with the major components (compiler, kernel, and so on) of the operating system on which the executable runs, unless that component itself accompanies the executable.

If distribution of executable or object code is made by offering access to copy from a designated place, then offering equivalent access to copy the source code from the same place counts as distribution of the source code, even though third parties are not compelled to copy the source along with the object code.

4. You may not copy, modify, sublicense, or distribute the Program except as expressly provided under this License. Any attempt otherwise to copy, modify, sublicense or distribute the Program is void, and will automatically terminate your rights under this License. However, parties who have received copies, or rights, from you under this License will not have their licenses terminated so long as such

parties remain in full compliance.

5. You are not required to accept this License, since you have not signed it. However, nothing else grants you permission to modify or distribute the Program or its derivative works. These actions are prohibited by law if you do not accept this License. Therefore, by modifying or distributing the Program (or any work based on the Program), you indicate your acceptance of this License to do so, and all its terms and conditions for copying, distributing or modifying the Program or works based on it.

6. Each time you redistribute the Program (or any work based on the Program), the recipient automatically receives a license from the original licensor to copy, distribute or modify the Program subject to these terms and conditions. You may not impose any further restrictions on the recipients' exercise of the rights granted herein. You are not responsible for enforcing compliance by third parties to this License.

7. If, as a consequence of a court judgment or allegation of patent infringement or for any other reason (not limited to patent issues), conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot distribute so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not distribute the Program at all. For example, if a patent license would not permit royalty-free redistribution of the Program by all those who receive copies directly or indirectly through you, then the only way you could satisfy both it and this License would be to refrain entirely from distribution of the Program.

If any portion of this section is held invalid or unenforceable under any particular circumstance, the balance of the section is intended to apply and the section as a whole is intended to apply in other circumstances.

It is not the purpose of this section to induce you to infringe any patents or other property right claims or to contest validity of any such claims; this section has the sole purpose of protecting the integrity of the free software distribution system, which is implemented by public license practices. Many people have made generous contributions to the wide range of software distributed through that system in reliance on consistent application of that system; it is up to the author/donor to

decide if he or she is willing to distribute software through any other system and a licensee cannot impose that choice.

This section is intended to make thoroughly clear what is believed to be a consequence of the rest of this License.

8. If the distribution and/or use of the Program is restricted in certain countries either by patents or by copyrighted interfaces, the original copyright holder who places the Program under this License may add an explicit geographical distribution limitation excluding those countries, so that distribution is permitted only in or among countries not thus excluded. In such case, this License incorporates the limitation as if written in the body of this License.

9. The Free Software Foundation may publish revised and/or new versions of the General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Program specifies a version number of this License which applies to it and "any later version", you have the option of following the terms and conditions either of that version or of any later version published by the Free Software Foundation. If the Program does not specify a version number of this License, you may choose any version ever published by the Free Software Foundation.

10. If you wish to incorporate parts of the Program into other free programs whose distribution conditions are different, write to the author to ask for permission. For software which is copyrighted by the Free Software Foundation, write to the Free Software Foundation; we sometimes make exceptions for this. Our decision will be guided by the two goals of preserving the free status of all derivatives of our free software and of promoting the sharing and reuse of software generally.

NO WARRANTY

11. BECAUSE THE PROGRAM IS LICENSED FREE OF CHARGE, THERE IS NO WARRANTY FOR THE PROGRAM, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE PROGRAM "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE PROGRAM IS WITH YOU. SHOULD THE PROGRAM PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING,

REPAIR OR CORRECTION.

12. IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY AND/OR REDISTRIBUTE THE PROGRAM AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE PROGRAM (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE PROGRAM TO OPERATE WITH ANY OTHER PROGRAMS), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Programs

If you develop a new program, and you want it to be of the greatest possible use to the public, the best way to achieve this is to make it free software which everyone can redistribute and change under these terms.

To do so, attach the following notices to the program. It is safest to attach them to the start of each source file to most effectively convey the exclusion of warranty; and each file should have at least the "copyright" line and a pointer to where the full notice is found.

<one line to give the program's name and a brief idea of what it does.>
Copyright (C) <year> <name of author>

This program is free software; you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation; either version 2 of the License, or (at your option) any later version.

This program is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details.

You should have received a copy of the GNU General Public License along with this program; if not, write to the Free Software Foundation, Inc., 51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA.

Also add information on how to contact you by electronic and paper mail.

If the program is interactive, make it output a short notice like this when it starts in an interactive mode:

Gnomovision version 69, Copyright (C) year name of author
Gnomovision comes with ABSOLUTELY NO WARRANTY; for details type `show w'.
This is free software, and you are welcome to redistribute
it
under certain conditions; type `show c' for details.

The hypothetical commands `show w' and `show c' should show the appropriate parts of the General Public License. Of course, the commands you use may be called something other than `show w' and `show c'; they could even be mouse-clicks or menu items--whatever suits your program.

You should also get your employer (if you work as a programmer) or your school, if any, to sign a "copyright disclaimer" for the program, if necessary. Here is a sample; alter the names:

Yoyodyne, Inc., hereby disclaims all copyright interest in the program
`Gnomovision' (which makes passes at compilers) written by James Hacker.

<signature of Ty Coon>, 1 April 1989
Ty Coon, President of Vice

This General Public License does not permit incorporating your program into proprietary programs. If your program is a subroutine library, you may consider it more useful to permit linking proprietary applications with the library. If this

is what you want to do, use the GNU Lesser General Public License instead of this License.

This library is free software; you can redistribute it and/or modify it under the terms of the GNU Lesser General Public License as published by the Free Software Foundation; either version 2.1 of the License, or (at your option) any later version.

The complete text of the license is available in the
../Documentation/licenses/COPYING.LGPLv2.1 file.

WEV @@ WEV[B "1

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

1. Redistributions of source code must retain the above copyright notice, and the entire permission notice in its entirety, including the disclaimer of warranties.
2. Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.
3. The name of the author may not be used to endorse or promote products derived from this software without specific prior

written permission.

THIS SOFTWARE IS PROVIDED ``AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, ALL OF WHICH ARE HEREBY DISCLAIMED. IN NO EVENT SHALL THE AUTHOR BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL

DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF NOT ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

x ?"U@,5 @mISmIN<GimCN7g1uE
43mI,5WEV @@ WEV @mImImIAmImImI0mImImI*mImI
A0mImImI...
lost+found...

;9GimCN7g

!"#\$%&'()*+,-
./0123456789:;<=>?@ABCDEFGHIJKLMNOPQRSTUVWXYZ[\]^_`abcdefghijklmnopqrstuvwxyz{|}~

!"#\$%&'()*+,-
./0123456789:;<=>?@ABCDEFGHIJKLMNOPQRSTUVWXYZ[\]^_`abcdefghijklmnopqrstuvwxyz{|}~

!"#\$%&'()*+,-
./0123456789:;<=>?@ABCDEFGHIJKLMNOPQRSTUVWXYZ[\]^_`abcdefghijklmnopqrstuvwxyz{|}~

!"#\$%&'()*+,-
./0123456789:;<=>?@ABCDEFGHIJKLMNOPQRSTUVWXYZ[\]^_`abcdefghijklmnopqrstuvwxyz{|}~WEV @@
WEV[B "1
/*

- * Copyright (c) 1989 The Regents of the University of California.
- * All rights reserved.
- *
- * Redistribution and use in source and binary forms, with or without
- * modification, are permitted provided that the following conditions
- * are met:
- * 1. Redistributions of source code must retain the above copyright
- * notice, this list of conditions and the following disclaimer.
- * 2. Redistributions in binary form must reproduce the above copyright
- * notice, this list of conditions and the following disclaimer in the
- * documentation and/or other materials provided with the distribution.
- * 3. All advertising materials mentioning features or use of this software
- * must display the following acknowledgement:

* This product includes software developed by the University of
 * California, Berkeley and its contributors.
 * 4. Neither the name of the University nor the names of its contributors
 * may be used to endorse or promote products derived from this software
 *
 without specific prior written permission.
 *
 * THIS SOFTWARE IS PROVIDED BY THE REGENTS AND CONTRIBUTORS ``AS IS" AND
 * ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE
 * IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE
 * ARE DISCLAIMED. IN NO EVENT SHALL THE REGENTS OR CONTRIBUTORS BE LIABLE
 * FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL
 * DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS
 * OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION)
 * HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT
 * LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY
 * OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF
 * SUCH DAMAGE.
 */
 This library is free software; you can redistribute it and/or
 modify it under the terms of the Modified BSD License.

The complete text of the license is available in the
 ../Documentation/licenses/COPYING.BSD-3 file.

1.51 libmount 2.31.1-0.4ubuntu3.7

1.51.1 Available under license :

Format: <http://www.debian.org/doc/packaging-manuals/copyright-format/1.0/>
 Upstream-Name: util-linux
 Upstream-Contact: util-linux@vger.kernel.org
 Source: <https://www.kernel.org/pub/linux/utils/util-linux/>

Files: *

Copyright: Michal Luscon <mluscon@redhat.com>
 1986 Gary S. Brown
 1990 Gordon Irlam (gordoni@cs.ua.oz.au)
 1991, 1992 Linus Torvalds
 1991-2004 Miquel van Smoorenburg
 1992 A. V. Le Blanc (LeBlanc@mcc.ac.uk)
 1992-1997 Michael K. Johnson, johnsonm@redhat.com
 1993, 1994, 1995, 1996, 1997, 1998, 1999, 2000, 2001, 2002,
 2003, 2004, 2005, 2008 Theodore Ts'o <tytso@mit.edu>
 1994 Kevin E. Martin (martin@cs.unc.edu)
 1994 Salvatore Valente <svalente@mit.edu>
 1994,1996 Alessandro Rubini (rubini@ipvvis.unipv.it)
 1994-2005 Jeff Tranter (tranter@pobox.com)

1995, 1999, 2000 Andries E. Brouwer <aeb@cwi.nl>
1997-2005 Frodo Looijaard
<frodo@frodo.looijaard.name>
1998 Danek Duvall <duvall@alumni.princeton.edu>
1999 Andreas Dilger
1999-2002 Transmeta Corporation
1999, 2000, 2002-2009, 2010, 2011, 2012, 2014 Red Hat, Inc.
2000 Werner Almesberger
2004-2006 Michael Holzt, kju -at- fqdn.org
2005 Adrian Bunk
2007-2014 Karel Zak <kzak@redhat.com>
2007, 2011 SuSE LINUX Products GmbH
2008 Cai Qian <qcai@redhat.com>
2008 Hayden A. James (hayden.james@gmail.com)
2008 James Youngman <jay@gnu.org>
2008 Roy Peled, the.roy.peled -at- gmail.com
2009 Mikhail Gusarov <dottedmag@dottedmag.net>
2010, 2011, 2012 Davidlohr Bueso <dave@gnu.org>
2010 Jason Borden <jborden@bluehost.com>A
2010 Hajime Taira <htaira@redhat.com>
2010 Masatake Yamato <yamato@redhat.com>
2011 IBM Corp.
2012 Andy Lutomirski <luto@amacapital.net>
2012 Lennart Poettering
2012 Sami Kerola <kerolasa@iki.fi>
2012 Cody Maloney <cmaloney@theoreticalchaos.com>
2012 Werner Fink <werner@suse.de>
2013,2014 Ondrej Oprala <ooprala@redhat.com>

License: GPL-2+

Files: schedutils/ionice.c

Copyright: 2005 Jens Axboe <jens@axboe.dk>

License: GPL-2

Files: schedutils/chrt.c

 schedutils/taskset.c

Copyright: 2004 Robert Love <rml@tech9.net>

 2010 Karel Zak <kzak@redhat.com>

License: GPL-2

Files: disk-utils/raw.c

Copyright: 1999, 2000, Red Hat Software

License: GPL-2

Files: sys-utils/nsenter.c

Copyright: 2012-2013 Eric Biederman <ebiederm@xmission.com>

License: GPL-2

Files: disk-utils/mkfs.minix.c
disk-utils/mkswap.c
Copyright: 1991, 1992 Linus Torvalds
License: GPL-2

Files: lib/at.c
lib/blkdev.c
lib/loopdev.c
lib/sysfs.c
lib/ttyutils.c
lib/xgetpass.c
misc-utils/mcookie.c
sys-utils/setsid.c
text-utils/line.c

Copyright:
n/a
License: public-domain

Files: login-utils/vipw.c
misc-utils/cal.c
misc-utils/kill.c
misc-utils/logger.c
misc-utils/look.c
misc-utils/whereis.c
sys-utils/renice.c
term-utils/mesg.c
term-utils/script.c
term-utils/ttymsg.c
term-utils/wall.c
term-utils/write.c
text-utils/col.c
text-utils/colcrt.c
text-utils/colrm.c
text-utils/column.c
text-utils/hexdump.c
text-utils/hexdump.h
text-utils/hexdump-conv.c
text-utils/hexdump-display.c
text-utils/hexdump-parse.c
text-utils/rev.c
text-utils/ul.c

Copyright: 1980, 1983, 1987, 1988, 1989, 1990, 1991, 1992, 1993, 1994
The Regents of the University of California
2014 Sami Kerola <kerolasa@iki.fi>
2014 Karel Zak <kzak@redhat.com>

License: BSD-4-clause

Files: text-utils/tailf.c

Copyright: 1996, 2003 Rickard E. Faith (faith@acm.org)

License: MIT

Files:

sys-utils/flock.c

Copyright: 2003-2005 H. Peter Anvin

License: MIT

Files: text-utils/pg.c

Copyright: 2000-2001 Gunnar Ritter

License: BSD-2-clause

Files: login-utils/last-deprecated.c

Copyright: 1987 Regents of the University of California

License: BSD-2-clause

Files: login-utils/login.c

Copyright: 1980, 1987, 1988 The Regents of the University of California.

2011 Karel Zak <kzak@redhat.com>

License: BSD-2-clause

Files: login-utils/logindefs.c

Copyright: 2003, 2004, 2005 Thorsten Kukuk

License: BSD-3-clause

Files: libuuid/*

libuuid/src/*

libuuid/man/*

Copyright: 1996, 1997, 1998, 1999, 2007 Theodore Ts'o.

1999 Andreas Dilger (adilger@enel.ucalgary.ca)

License: BSD-3-clause

Files: lib/procutils.c

include/xalloc.h

Copyright: 2010, 2011 Davidlohr Bueso <dave@gnu.org>

License: LGPL-2+

Files: */colors.*

Copyright: 2012 Ondrej Oprala <oprala@redhat.com>

2012-2014 Karel Zak <kzak@redhat.com>

License: LGPL-2+

Files: login-utils/setpwnam.h

login-utils/setpwnam.c

Copyright: 1994 Martin Schulze <joey@infodrom.north.de>

1994 Salvatore Valente <svalente@mit.edu>

License: LGPL-2+

Files: libfdisk/*
libfdisk/src/*
Copyright: 2007-2013 Karel Zak <kzak@redhat.com>
2012 Davidlohr Bueso <dave@gnu.org>
License: LGPL-2.1+

Files: lib/cpuset.c
/match.
lib/canonicalize.c
include/at.h
Copyright: 2008-2009, 2010, 2011, 2012 Karel Zak <kzak@redhat.com>
License: LGPL-2.1+

Files: */mbsalign.*
Copyright: 2009-2010 Free Software Foundation, Inc.
2010-2013 Karel Zak <kzak@redhat.com>
License: LGPL-2.1+

Files: */readutmp.*
Copyright: 1992-2007, 2009-2014 Free Software Foundation, Inc.
License: GPL-3+

Files: */timeutils.*
Copyright: 2010 Lennart Poettering
License: LGPL-2.1+

Files: include/list.h
Copyright: 2008 Karel Zak <kzak@redhat.com>
1999-2008 by Theodore Ts'o
License: LGPL

Files: libblkid/*
libblkid/src/*
libblkid/samples/*

libblkid/src/partitions/*
libblkid/src/superblocks/*
libblkid/src/topology/*
Copyright: 1999, 2001 Andries Brouwer
1995, 1995, 1996, 1997, 1999, 2000, 2001, 2002, 2003, 2004
Theodore Ts'o.
2001 Andreas Dilger (adilger@turbolinux.com)
2004-2008 Kay Sievers <kay.sievers@vrfy.org>
2008-2013 Karel Zak <kzak@redhat.com>
2009 Bastian Friedrich <bastian.friedrich@collax.com>
2009 Corentin Chary <corentincj@iksaif.net>
2009 Mike Hommey <mh@glandium.org>
2009 Red Hat, Inc.

2009-2010 Andreas Dilger <adilger@sun.com>
2010 Andrew Nayenko <resver@gmail.com>
2010 Jeroen Oortwijn <oortwijn@gmail.com>
2010 Jiro SEKIBA <jir@unicus.jp>
2011 Philipp Marek <philipp.marek@linbit.com>
2012 Milan Broz <mbroz@redhat.com>
2013 Alejandro Martinez Ruiz <alex@nowcomputing.com>
2013 Eric Sandeen <sandeen@redhat.com>
2013 Rolf Fokkens <rolf@fokkens.nl>
2013 Zeeshan Ali (Khattak) <zeeshanak@gnome.org>

License: LGPL-2.1+

Files: include/cpuset.h

lib/randutils.c

Copyright: *unknown*

License: LGPL

Files: misc-utils/blkid.c

Copyright: 2001 Andreas Dilger

License: LGPL

Files: libmount/*

libmount/src/*

Copyright: 2008-2012 Karel Zak <kzak@redhat.com>

License: LGPL-2.1+

Files: libmount/python/*

Copyright: 2013, Red Hat, Inc.

License: LGPL-3+

Files: libsmartcols/*

Copyright: 2009-2014 Karel Zak <kzak@redhat.com>

2014 Ondrej Oprala <ooprala@redhat.com>

License: LGPL

Files: debian/*

Copyright: Guy Maor <maor@debian.org>

Sean 'Shaleh' Perry <shaleh@debian.org>

Adrian Bunk <bunk@stusta.de>

LaMont Jones <lamont@debian.org>

2014 Andreas Henriksson <andreas@fatal.se>

License: GPL-2+

License: public-domain

The files tagged with this license contains the following paragraphs:

.

No copyright

is claimed. This code is in the public domain; do with it what you wish.

.
Written by Karel Zak <kzak@redhat.com>

License: GPL-2

This program is free software; you can redistribute it and/or modify it under the terms of the GNU General Public License, v2, as published by the Free Software Foundation

.
This program is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details.

.
You should have received a copy of the GNU General Public License along with this program; if not, write to the Free Software Foundation, Inc., 51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA.

.
On Debian systems, the complete text of the GNU General Public License version 2 can be found in `~/usr/share/common-licenses/GPL-2`.

License: GPL-2+

This program is free software; you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation; either version 2 of the License, or (at your option) any later version.

.
This program is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details.

.
You should have received a copy of the GNU General Public License along with this program; if not, write to the Free Software Foundation, Inc., 51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA.

.
On Debian systems, the complete text of the GNU General Public License version 2 can be found in `~/usr/share/common-licenses/GPL-2`.

License: GPL-3+

This program is free software: you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation; either version 3 of the License, or (at your option) any later version.

This program is distributed in the hope that it will be useful,
but WITHOUT ANY WARRANTY; without even the implied warranty of
MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
GNU General Public License for more details.

.
You should have received a copy of the GNU General Public License
along with this program. If not, see <<http://www.gnu.org/licenses/>>.

.
On Debian systems, the complete text of the GNU General Public
License version 3 can be found in ``usr/share/common-licenses/GPL-3'`.

License: BSD-2-clause

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions
are met:

1. Redistributions of source code must retain the above copyright
notice, this list of conditions and the following disclaimer.
2. Redistributions in binary form must reproduce the above copyright
notice, this list of conditions and the following disclaimer in the
documentation and/or other
materials provided with the distribution.

License: BSD-3-clause

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions are met:

- 1) Redistributions of source code must retain the above copyright notice,
this list of conditions and the following disclaimer.
- 2) Redistributions in binary form must reproduce the above copyright notice,
this list of conditions and the following disclaimer in the documentation
and/or other materials provided with the distribution.
- 3) Neither the name of the ORGANIZATION nor the names of its contributors
may be used to endorse or promote products derived from this software
without specific prior written permission.

.
THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS"
AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE
IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE
ARE DISCLAIMED.

IN NO EVENT SHALL THE COPYRIGHT HOLDER OR CONTRIBUTORS BE
LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR
CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF
SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS
INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN
CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE)
ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE

POSSIBILITY OF SUCH DAMAGE.

License: BSD-4-clause

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

1. Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.
2. Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.
3. All advertising materials mentioning features or use of this software must display the following acknowledgement:
This product includes software developed by the University of California, Berkeley and its contributors.
4. Neither the name of the University nor the names of its contributors may be used to endorse or promote products derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE REGENTS AND CONTRIBUTORS ``AS IS'' AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE REGENTS OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

License: LGPL

This file may be redistributed under the terms of the GNU Lesser General Public License.

On Debian systems, the complete text of the GNU Lesser General Public License can be found in `/usr/share/common-licenses/LGPL`.

License: LGPL-2+

This program is free software: you can redistribute it and/or modify it under the terms of the GNU Lesser General Public License as published by the Free Software Foundation, either version 2 of the License, or (at your option) any later version.

This program is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of

MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU Lesser General Public License for more details.

.
You should have received
a copy of the GNU Lesser General Public License
along with this program. If not, see <<http://www.gnu.org/licenses/>>.

.
The complete text of the GNU Lesser General Public License
can be found in /usr/share/common-licenses/LGPL-2 file.

License: LGPL-2.1+

This program is free software; you can redistribute it and/or modify
it under the terms of the GNU Lesser General Public License as published by
the Free Software Foundation; either version 2.1, or (at your option)
any later version.

.
This program is distributed in the hope that it will be useful,
but WITHOUT ANY WARRANTY; without even the implied warranty of
MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
GNU Lesser General Public License for more details.

.
You should have received a copy of the GNU Lesser General Public License along
with this program; if not, write to the Free Software Foundation,
Inc., 51 Franklin Street, Fifth Floor, Boston, MA 02110-1301, USA.

.
On Debian systems, the complete text
of the GNU Lesser General Public
License version 2.1 can be found in /usr/share/common-licenses/LGPL-2.1.

License: LGPL-3+

This package is free software; you can redistribute it and/or
modify it under the terms of the GNU Lesser General Public
License as published by the Free Software Foundation; either
version 3 of the License, or (at your option) any later version.

.
This package is distributed in the hope that it will be useful,
but WITHOUT ANY WARRANTY; without even the implied warranty of
MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU
Lesser General Public License for more details.

.
You should have received a copy of the GNU General Public License
along with this program. If not, see <<http://www.gnu.org/licenses/>>.

.
On Debian systems, the complete text of the GNU Lesser General
Public License can be found in "/usr/share/common-licenses/LGPL-3".

License: MIT

Permission is hereby granted, free of charge, to any person

obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

GNU GENERAL PUBLIC LICENSE
Version 2, June 1991

Copyright (C) 1989, 1991 Free Software Foundation, Inc.,
51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA
Everyone is permitted to copy and distribute verbatim copies of this license document, but changing it is not allowed.

Preamble

The licenses for most software are designed to take away your freedom to share and change it. By contrast, the GNU General Public License is intended to guarantee your freedom to share and change free software--to make sure the software is free for all its users. This General Public License applies to most of the Free Software Foundation's software and to any other program whose authors commit to using it. (Some other Free Software Foundation software is covered by the GNU Lesser General Public License instead.) You can apply it to your programs, too.

When we speak of free software, we are referring to freedom, not price.

Our General Public Licenses are designed to make sure that you have the freedom to distribute copies of free software (and charge for this service if you wish), that you receive source code or can get it if you want it, that you can change the software or use pieces of it in new free programs; and that you know you can do these things.

To protect your rights, we need to make restrictions that forbid

anyone to deny you these rights or to ask you to surrender the rights. These restrictions translate to certain responsibilities for you if you distribute copies of the software, or if you modify it.

For example, if you distribute copies of such a program, whether gratis or for a fee, you must give the recipients all the rights that you have. You must make sure that they, too, receive or can get the source code. And you must show them these terms so they know their rights.

We protect your rights with two steps: (1) copyright the software, and (2) offer you this license which gives you legal permission to copy, distribute and/or modify the software.

Also, for each author's protection and ours, we want to make certain that everyone understands that there is no warranty for this free software. If the software is modified by someone else and passed on, we want its recipients to know that what they have is not the original, so that any problems introduced by others will not reflect on the original authors' reputations.

Finally, any free program is threatened constantly by software patents. We wish to avoid the danger that redistributors of a free program will individually obtain patent licenses, in effect making the program proprietary. To prevent this, we have made it clear that any patent must be licensed for everyone's free use or not licensed at all.

The precise terms and conditions for copying, distribution and modification follow.

GNU GENERAL PUBLIC LICENSE TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

0. This License applies to any program or other work which contains a notice placed by the copyright holder saying it may be distributed under the terms of this General Public License. The "Program", below, refers to any such program or work, and a "work based on the Program" means either the Program or any derivative work under copyright law: that is to say, a work containing the Program or a portion of it, either verbatim or with modifications and/or translated into another language. (Hereinafter, translation is included without limitation in the term "modification".) Each licensee is addressed as "you".

Activities other than copying, distribution and modification are not covered by this License; they are outside its scope. The act of running the Program is not restricted, and the output from the Program is covered only if its contents constitute a work based on the

Program (independent of having been made by running the Program). Whether that is true depends on what the Program does.

1. You may copy and distribute verbatim copies of the Program's source code as you receive it, in any medium, provided that you conspicuously and appropriately publish on each copy an appropriate copyright notice and disclaimer of warranty; keep intact all the notices that refer to this License and to the absence of any warranty; and give any other recipients of the Program a copy of this License along with the Program.

You may charge a fee for the physical act of transferring a copy, and you may at your option offer warranty protection in exchange for a fee.

2. You may modify your copy or copies of the Program or any portion of it, thus forming a work based on the Program, and copy and distribute such modifications or work under the terms of Section 1 above, provided that you also meet all of these conditions:

a) You must cause the modified files to carry prominent notices stating that you changed the files and the date of any change.

b) You must cause any work that you distribute or publish, that in whole or in part contains or is derived from the Program or any part thereof, to be licensed as a whole at no charge to all third parties under the terms of this License.

c) If the modified program normally reads commands interactively when run, you must cause it, when started running for such interactive use in the most ordinary way, to print or display an announcement including an appropriate copyright notice and a notice that there is no warranty (or else, saying that you provide a warranty) and that users may redistribute the program under these conditions, and telling the user how to view a copy of this License. (Exception: if the Program itself is interactive but does not normally print such an announcement, your work based on the Program is not required to print an announcement.)

These requirements apply to the modified work as a whole. If identifiable sections of that work are not derived from the Program, and can be reasonably considered independent and separate works in themselves, then this License, and its terms, do not apply to those sections when you distribute them as separate works. But when you distribute the same sections as part of a whole which is a work based on the Program, the distribution of the whole must be on the terms of

this License, whose permissions for other licensees extend to the entire whole, and thus to each and every part regardless of who wrote it.

Thus, it is not the intent of this section to claim rights or contest your rights to work written entirely by you; rather, the intent is to exercise the right to control the distribution of derivative or collective works based on the Program.

In addition, mere aggregation of another work not based on the Program with the Program (or with a work based on the Program) on a volume of a storage or distribution medium does not bring the other work under the scope of this License.

3. You may copy and distribute the Program (or a work based on it, under Section 2) in object code or executable form under the terms of Sections 1 and 2 above provided that you also do one of the following:

a) Accompany it with the complete corresponding machine-readable source code, which must be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange; or,

b) Accompany it with a written offer, valid for at least three years, to give any third party, for a charge no more than your cost of physically performing source distribution, a complete machine-readable copy of the corresponding source code, to be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange; or,

c) Accompany it with the information you received as to the offer to distribute corresponding source code. (This alternative is allowed only for noncommercial distribution and only if you received the program in object code or executable form with such an offer, in accord with Subsection b above.)

The source code for a work means the preferred form of the work for making modifications to it. For an executable work, complete source code means all the source code for all modules it contains, plus any associated interface definition files, plus the scripts used to control compilation and installation of the executable. However, as a special exception, the source code distributed need not include anything that is normally distributed (in either source or binary form) with the major components (compiler, kernel, and so on) of the operating system on which the executable runs, unless that component itself accompanies the executable.

If distribution of executable or object code is made by offering access to copy from a designated place, then offering equivalent

access to copy the source code from the same place counts as distribution of the source code, even though third parties are not compelled to copy the source along with the object code.

4. You may not copy, modify, sublicense, or distribute the Program except as expressly provided under this License. Any attempt otherwise to copy, modify, sublicense or distribute the Program is void, and will automatically terminate your rights under this License. However, parties who have received copies, or rights, from you under this License will not have their licenses terminated so long as such parties remain in full compliance.

5. You are not required to accept this License, since you have not signed it. However, nothing else grants you permission to modify or distribute the Program or its derivative works. These actions are prohibited by law if you do not accept this License. Therefore, by modifying or distributing the Program (or any work based on the Program), you indicate your acceptance of this License to do so, and all its terms and conditions for copying, distributing or modifying the Program or works based on it.

6. Each time you redistribute the Program (or any work based on the Program), the recipient automatically receives a license from the original licensor to copy, distribute or modify the Program subject to these terms and conditions. You may not impose any further restrictions on the recipients' exercise of the rights granted herein. You are not responsible for enforcing compliance by third parties to this License.

7. If, as a consequence of a court judgment or allegation of patent infringement or for any other reason (not limited to patent issues), conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot distribute so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not distribute the Program at all. For example, if a patent license would not permit royalty-free redistribution of the Program by all those who receive copies directly or indirectly through you, then the only way you could satisfy both it and this License would be to refrain entirely from distribution of the Program.

If any portion of this section is held invalid or unenforceable under any particular circumstance, the balance of the section is intended to apply and the section as a whole is intended to apply in other

circumstances.

It is not the purpose of this section to induce you to infringe any patents or other property right claims or to contest validity of any such claims; this section has the sole purpose of protecting the integrity of the free software distribution system, which is implemented by public license practices. Many people have made generous contributions to the wide range of software distributed through that system in reliance on consistent application of that system; it is up to the author/donor to decide if he or she is willing to distribute software through any other system and a licensee cannot impose that choice.

This section is intended to make thoroughly clear what is believed to be a consequence of the rest of this License.

8. If the distribution and/or use of the Program is restricted in certain countries either by patents or by copyrighted interfaces, the original copyright holder who places the Program under this License may add an explicit geographical distribution limitation excluding those countries, so that distribution is permitted only in or among countries not thus excluded. In such case, this License incorporates the limitation as if written in the body of this License.

9. The Free Software Foundation may publish revised and/or new versions of the General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Program specifies a version number of this License which applies to it and "any later version", you have the option of following the terms and conditions either of that version or of any later version published by the Free Software Foundation. If the Program does not specify a version number of this License, you may choose any version ever published by the Free Software Foundation.

10. If you wish to incorporate parts of the Program into other free programs whose distribution conditions are different, write to the author to ask for permission. For software which is copyrighted by the Free Software Foundation, write to the Free Software Foundation; we sometimes make exceptions for this. Our decision will be guided by the two goals of preserving the free status of all derivatives of our free software and of promoting the sharing and reuse of software generally.

NO WARRANTY

11. BECAUSE THE PROGRAM IS LICENSED FREE OF CHARGE,
THERE IS NO WARRANTY
FOR THE PROGRAM, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN
OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES
PROVIDE THE PROGRAM "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED
OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF
MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS
TO THE QUALITY AND PERFORMANCE OF THE PROGRAM IS WITH YOU. SHOULD THE
PROGRAM PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING,
REPAIR OR CORRECTION.

12. IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING
WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY AND/OR
REDISTRIBUTE THE PROGRAM AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES,
INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING
OUT OF THE USE OR INABILITY TO USE THE PROGRAM (INCLUDING BUT NOT LIMITED
TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY
YOU OR
THIRD PARTIES OR A FAILURE OF THE PROGRAM TO OPERATE WITH ANY OTHER
PROGRAMS), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE
POSSIBILITY OF SUCH DAMAGES.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Programs

If you develop a new program, and you want it to be of the greatest
possible use to the public, the best way to achieve this is to make it
free software which everyone can redistribute and change under these terms.

To do so, attach the following notices to the program. It is safest
to attach them to the start of each source file to most effectively
convey the exclusion of warranty; and each file should have at least
the "copyright" line and a pointer to where the full notice is found.

```
<one line to give the program's name and a brief idea of what it does.>  
Copyright (C) <year> <name of author>
```

```
This program is free software; you can redistribute it and/or modify  
it under the terms of the GNU  
General Public License as published by  
the Free Software Foundation; either version 2 of the License, or  
(at your option) any later version.
```

```
This program is distributed in the hope that it will be useful,  
but WITHOUT ANY WARRANTY; without even the implied warranty of  
MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
```

GNU General Public License for more details.

You should have received a copy of the GNU General Public License along with this program; if not, write to the Free Software Foundation, Inc., 51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA.

Also add information on how to contact you by electronic and paper mail.

If the program is interactive, make it output a short notice like this when it starts in an interactive mode:

```
Gnomovision version 69, Copyright (C) year name of author
Gnomovision comes with ABSOLUTELY NO WARRANTY; for details type `show w'.
This is free software, and you are welcome to redistribute
it
under certain conditions; type `show c' for details.
```

The hypothetical commands ``show w'` and ``show c'` should show the appropriate parts of the General Public License. Of course, the commands you use may be called something other than ``show w'` and ``show c'`; they could even be mouse-clicks or menu items--whatever suits your program.

You should also get your employer (if you work as a programmer) or your school, if any, to sign a "copyright disclaimer" for the program, if necessary. Here is a sample; alter the names:

```
Yoyodyne, Inc., hereby disclaims all copyright interest in the program
`Gnomovision' (which makes passes at compilers) written by James Hacker.
```

```
<signature of Ty Coon>, 1 April 1989
Ty Coon, President of Vice
```

This General Public License does not permit incorporating your program into proprietary programs. If your program is a subroutine library, you may consider it more useful to permit linking proprietary applications with the library. If this

is what you want to do, use the GNU Lesser General Public License instead of this License.

This library is free software; you can redistribute it and/or modify it under the terms of the GNU Lesser General Public License as published by the Free Software Foundation; either version 2.1 of the License, or (at your option) any later version.

The complete text of the license is available in the `../Documentation/licenses/COPYING.LGPLv2.1` file.
WEV @@ WEV[B "1

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

1. Redistributions of source code must retain the above copyright notice, and the entire permission notice in its entirety, including the disclaimer of warranties.
2. Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.
3. The name of the author may not be used to endorse or promote products derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED ``AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, ALL OF WHICH ARE HEREBY DISCLAIMED. IN NO EVENT SHALL THE AUTHOR BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL

DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF NOT ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

x ?"U@,5 @mISmIN<GimCN7g1u|E
43mI,5WEV @@ WEV @mImImIAmImImI0mImImI*mImI
A0mImImI...
lost+found...

;9GimCN7g

!"#\$%&'()*+,-
./0123456789:;<=>?@ABCDEFGHIJKLMNOPQRSTUVWXYZ[\]^_`abcdefghijklmnopqrstuvwxyz{|}~

!"#\$%&'()*+,-
./0123456789:;<=>?@ABCDEFGHIJKLMNOPQRSTUVWXYZ[\]^_`abcdefghijklmnopqrstuvwxyz{|}~

!"#\$%&'()*+,-
./0123456789:;<=>?@ABCDEFGHIJKLMNOPQRSTUVWXYZ[\]^_`abcdefghijklmnopqrstuvwxyz{|}~

!"#\$%&'()*+,-
./0123456789:;<=>?@ABCDEFGHIJKLMNOPQRSTUVWXYZ[\]^_`abcdefghijklmnopqrstuvwxyz{|}~WEV @@
WEV[B "1
/*

* Copyright (c) 1989 The Regents of the University of California.

* All rights reserved.

*
 * Redistribution and use in source and binary forms, with or without
 * modification, are permitted provided that the following conditions
 * are met:
 * 1. Redistributions of source code must retain the above copyright
 * notice, this list of conditions and the following disclaimer.
 * 2. Redistributions in binary form must reproduce the above copyright
 * notice, this list of conditions and the following disclaimer in the
 * documentation and/or other materials provided with the distribution.
 * 3. All advertising materials mentioning features or use of this software
 * must display the following acknowledgement:
 * This product includes software developed by the University of
 * California, Berkeley and its contributors.
 * 4. Neither the name of the University nor the names of its contributors
 * may be used to endorse or promote products derived from this software
 *
 * without specific prior written permission.
 *
 * THIS SOFTWARE IS PROVIDED BY THE REGENTS AND CONTRIBUTORS ``AS IS" AND
 * ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE
 * IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE
 * ARE DISCLAIMED. IN NO EVENT SHALL THE REGENTS OR CONTRIBUTORS BE LIABLE
 * FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL
 * DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS
 * OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION)
 * HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT
 * LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY
 * OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF
 * SUCH DAMAGE.
 */
 This library is free software; you can redistribute it and/or
 modify it under the terms of the Modified BSD License.

The complete text of the license is available in the
 ../Documentation/licenses/COPYING.BSD-3 file.

1.52 libuuid 2.31.1-0.4ubuntu3.7

1.52.1 Available under license :

Format: <http://www.debian.org/doc/packaging-manuals/copyright-format/1.0/>
 Upstream-Name: util-linux
 Upstream-Contact: util-linux@vger.kernel.org
 Source: <https://www.kernel.org/pub/linux/utils/util-linux/>

Files: *
 Copyright: Michal Luscon <miluscon@redhat.com>
 1986 Gary S. Brown

1990 Gordon Irlam (gordoni@cs.ua.oz.au)
1991, 1992 Linus Torvalds
1991-2004 Miquel van Smoorenburg
1992 A. V. Le Blanc (LeBlanc@mcc.ac.uk)
1992-1997 Michael K. Johnson, johnsonm@redhat.com
1993, 1994, 1995, 1996, 1997, 1998, 1999, 2000, 2001, 2002,
2003, 2004, 2005, 2008 Theodore Ts'o <tytso@mit.edu>
1994 Kevin E. Martin (martin@cs.unc.edu)
1994 Salvatore Valente <svalente@mit.edu>
1994,1996 Alessandro Rubini (rubini@ipvvis.unipv.it)
1994-2005 Jeff Tranter (tranter@pobox.com)
1995, 1999, 2000 Andries E. Brouwer <aeb@cwi.nl>
1997-2005 Frodo Looijaard
<frodo@frodo.looijaard.name>
1998 Danek Duvall <duvall@alumni.princeton.edu>
1999 Andreas Dilger
1999-2002 Transmeta Corporation
1999, 2000, 2002-2009, 2010, 2011, 2012, 2014 Red Hat, Inc.
2000 Werner Almesberger
2004-2006 Michael Holzt, kju -at- fqdn.org
2005 Adrian Bunk
2007-2014 Karel Zak <kzak@redhat.com>
2007, 2011 SuSE LINUX Products GmbH
2008 Cai Qian <qcai@redhat.com>
2008 Hayden A. James (hayden.james@gmail.com)
2008 James Youngman <jay@gnu.org>
2008 Roy Peled, the.roy.peled -at- gmail.com
2009 Mikhail Gusarov <dottedmag@dottedmag.net>
2010, 2011, 2012 Davidlohr Bueso <dave@gnu.org>
2010 Jason Borden <jborden@bluehost.com>A
2010 Hajime Taira <htaira@redhat.com>
2010 Masatake Yamato <yamato@redhat.com>
2011 IBM Corp.
2012 Andy Lutomirski <luto@amacapital.net>
2012 Lennart Poettering
2012 Sami Kerola <kerolasa@iki.fi>
2012 Cody Maloney <cmaloney@theoreticalchaos.com>
2012 Werner Fink <werner@suse.de>
2013,2014 Ondrej Oprala <ooprala@redhat.com>

License: GPL-2+

Files: schedutils/ionice.c

Copyright: 2005 Jens Axboe <jens@axboe.dk>

License: GPL-2

Files: schedutils/chrt.c

schedutils/taskset.c

Copyright: 2004 Robert Love <rml@tech9.net>

2010 Karel Zak <kzak@redhat.com>

License: GPL-2

Files: disk-utils/raw.c

Copyright: 1999, 2000, Red Hat Software

License: GPL-2

Files: sys-utils/nsenter.c

Copyright: 2012-2013 Eric Biederman <ebiederm@xmission.com>

License: GPL-2

Files: disk-utils/mkfs.minix.c

disk-utils/mkswap.c

Copyright: 1991, 1992 Linus Torvalds

License: GPL-2

Files: lib/at.c

lib/blkdev.c

lib/loopdev.c

lib/sysfs.c

lib/ttyutils.c

lib/xgetpass.c

misc-utils/mcookie.c

sys-utils/setsid.c

text-utils/line.c

Copyright:

n/a

License: public-domain

Files: login-utils/vipw.c

misc-utils/cal.c

misc-utils/kill.c

misc-utils/logger.c

misc-utils/look.c

misc-utils/whereis.c

sys-utils/renice.c

term-utils/mesg.c

term-utils/script.c

term-utils/ttymsg.c

term-utils/wall.c

term-utils/write.c

text-utils/col.c

text-utils/colcrt.c

text-utils/colrm.c

text-utils/column.c

text-utils/hexdump.c

text-utils/hexdump.h

text-utils/hexdump-conv.c

text-utils/hexdump-display.c
text-utils/hexdump-parse.c
text-utils/rev.c
text-utils/ul.c

Copyright: 1980, 1983, 1987, 1988, 1989, 1990, 1991, 1992, 1993, 1994

The Regents of the University of California

2014 Sami Kerola <kerolasa@iki.fi>

2014 Karel Zak <kzak@redhat.com>

License: BSD-4-clause

Files: text-utils/tailf.c

Copyright: 1996, 2003 Rickard E. Faith (faith@acm.org)

License: MIT

Files:

sys-utils/flock.c

Copyright: 2003-2005 H. Peter Anvin

License: MIT

Files: text-utils/pg.c

Copyright: 2000-2001 Gunnar Ritter

License: BSD-2-clause

Files: login-utils/last-deprecated.c

Copyright: 1987 Regents of the University of California

License: BSD-2-clause

Files: login-utils/login.c

Copyright: 1980, 1987, 1988 The Regents of the University of California.

2011 Karel Zak <kzak@redhat.com>

License: BSD-2-clause

Files: login-utils/logindefs.c

Copyright: 2003, 2004, 2005 Thorsten Kukuk

License: BSD-3-clause

Files: libuuid/*

libuuid/src/*

libuuid/man/*

Copyright: 1996, 1997, 1998, 1999, 2007 Theodore Ts'o.

1999 Andreas Dilger (adilger@enel.ucalgary.ca)

License: BSD-3-clause

Files: lib/procutils.c

include/xalloc.h

Copyright: 2010, 2011 Davidlohr Bueso <dave@gnu.org>

License: LGPL-2+

Files: */colors.*
Copyright: 2012 Ondrej Oprala <ooprala@redhat.com>
2012-2014 Karel Zak <kzak@redhat.com>
License: LGPL-2+

Files: login-utils/setpwnam.h
login-utils/setpwnam.c
Copyright: 1994 Martin Schulze <joe@infodrom.north.de>
1994 Salvatore Valente <svalente@mit.edu>
License: LGPL-2+

Files: libfdisk/*
libfdisk/src/*
Copyright: 2007-2013 Karel Zak <kzak@redhat.com>
2012 Davidlohr Bueso <dave@gnu.org>
License: LGPL-2.1+

Files: lib/cpuset.c
/match.
lib/canonicalize.c
include/at.h
Copyright: 2008-2009, 2010, 2011, 2012 Karel Zak <kzak@redhat.com>
License: LGPL-2.1+

Files: */mbsalign.*
Copyright: 2009-2010 Free Software Foundation, Inc.
2010-2013 Karel Zak <kzak@redhat.com>
License: LGPL-2.1+

Files: */readutmp.*
Copyright: 1992-2007, 2009-2014 Free Software Foundation, Inc.
License: GPL-3+

Files: */timeutils.*
Copyright: 2010 Lennart Poettering
License: LGPL-2.1+

Files: include/list.h
Copyright: 2008 Karel Zak <kzak@redhat.com>
1999-2008 by Theodore Ts'o
License: LGPL

Files: libblkid/*
libblkid/src/*
libblkid/samples/*

libblkid/src/partitions/*
libblkid/src/superblocks/*

libblkid/src/topology/*

Copyright: 1999, 2001 Andries Brouwer

1995, 1995, 1996, 1997, 1999, 2000, 2001, 2002, 2003, 2004

Theodore Ts'o.

2001 Andreas Dilger (adilger@turbolinux.com)

2004-2008 Kay Sievers <kay.sievers@vrfy.org>

2008-2013 Karel Zak <kzak@redhat.com>

2009 Bastian Friedrich <bastian.friedrich@collax.com>

2009 Corentin Chary <corentincj@iksaif.net>

2009 Mike Hommey <mh@glandium.org>

2009 Red Hat, Inc.

2009-2010 Andreas Dilger <adilger@sun.com>

2010 Andrew Nayenko <resver@gmail.com>

2010 Jeroen Oortwijn <oortwijn@gmail.com>

2010 Jiro SEKIBA <jir@unicus.jp>

2011 Philipp Marek <philipp.marek@linbit.com>

2012 Milan Broz <mbroz@redhat.com>

2013 Alejandro Martinez Ruiz <alex@nowcomputing.com>

2013 Eric Sandeen <sandeen@redhat.com>

2013 Rolf Fokkens <rolf@fokkens.nl>

2013 Zeeshan Ali (Khattak) <zeeshanak@gnome.org>

License: LGPL-2.1+

Files: include/cpuset.h

lib/randutils.c

Copyright: *unknown*

License: LGPL

Files: misc-utils/blkid.c

Copyright: 2001 Andreas Dilger

License: LGPL

Files: libmount/*

libmount/src/*

Copyright: 2008-2012 Karel Zak <kzak@redhat.com>

License: LGPL-2.1+

Files: libmount/python/*

Copyright: 2013, Red Hat, Inc.

License: LGPL-3+

Files: libsmartcols/*

Copyright: 2009-2014 Karel Zak <kzak@redhat.com>

2014 Ondrej Oprala <ooprala@redhat.com>

License: LGPL

Files: debian/*

Copyright: Guy Maor <maor@debian.org>

Sean 'Shaleh' Perry <shaleh@debian.org>

Adrian Bunk <bunk@stusta.de>

LaMont Jones <lamont@debian.org>

2014 Andreas Henriksson <andreas@fatal.se>

License: GPL-2+

License: public-domain

The files tagged with this license contains the following paragraphs:

.

No copyright

is claimed. This code is in the public domain; do with it what you wish.

.

Written by Karel Zak <kzak@redhat.com>

License: GPL-2

This program is free software; you can redistribute it and/or modify it under the terms of the GNU General Public License, v2, as published by the Free Software Foundation

.

This program is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details.

.

You should have received a copy of the GNU General Public License along with this program; if not, write to the Free Software Foundation, Inc., 51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA.

.

On Debian systems, the complete text of the GNU General Public License version 2 can be found in `~/usr/share/common-licenses/GPL-2'`.

License: GPL-2+

This program is free software; you can redistribute it and/or modify it under the

terms of the GNU General Public License as published by the Free Software Foundation; either version 2 of the License, or (at your option) any later version.

.

This program is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details.

.

You should have received a copy of the GNU General Public License along with this program; if not, write to the Free Software Foundation, Inc., 51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA.

.
On Debian systems, the complete text of the GNU General Public License version 2 can be found in `~/usr/share/common-licenses/GPL-2`.

License: GPL-3+

This program is free software: you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation; either version 3 of the License, or (at your option) any later version.

.
This program is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details.

.
You should have received a copy of the GNU General Public License along with this program. If not, see <http://www.gnu.org/licenses/>.

.
On Debian systems, the complete text of the GNU General Public License version 3 can be found in `~/usr/share/common-licenses/GPL-3`.

License: BSD-2-clause

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

1. Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.
2. Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.

License: BSD-3-clause

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

- 1) Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.
 - 2) Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.
 - 3) Neither the name of the ORGANIZATION nor the names of its contributors may be used to endorse or promote products derived from this software without specific prior written permission.
- .

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED.

IN NO EVENT SHALL THE COPYRIGHT HOLDER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

License: BSD-4-clause

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

1. Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.
2. Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.
3. All advertising materials mentioning features or use of this software must display the following acknowledgement:
This product includes software developed by the University of California, Berkeley and its contributors.
4. Neither the name of the University nor the names of its contributors may be used to endorse or promote products derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE REGENTS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE REGENTS OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

License: LGPL

This file may be redistributed under the terms of the GNU Lesser General Public License.

On Debian systems, the complete text of the GNU Lesser General Public License can be found in `/usr/share/common-licenses/LGPL`.

License: LGPL-2+

This program is free software: you can redistribute it and/or modify it under the terms of the GNU Lesser General Public License as published by the Free Software Foundation, either version 2 of the License, or (at your option) any later version.

.

This program is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU Lesser General Public License for more details.

.

You should have received a copy of the GNU Lesser General Public License along with this program. If not, see <http://www.gnu.org/licenses/>.

.

The complete text of the GNU Lesser General Public License can be found in `/usr/share/common-licenses/LGPL-2` file.

License: LGPL-2.1+

This program is free software; you can redistribute it and/or modify it under the terms of the GNU Lesser General Public License as published by the Free Software Foundation; either version 2.1, or (at your option) any later version.

.

This program is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU Lesser General Public License for more details.

.

You should have received a copy of the GNU Lesser General Public License along with this program; if not, write to the Free Software Foundation, Inc., 51 Franklin Street, Fifth Floor, Boston, MA 02110-1301, USA.

.

On Debian systems, the complete text of the GNU Lesser General Public License version 2.1 can be found in `/usr/share/common-licenses/LGPL-2.1`.

License: LGPL-3+

This package is free software; you can redistribute it and/or modify it under the terms of the GNU Lesser General Public License as published by the Free Software Foundation; either version 3 of the License, or (at your option) any later version.

.

This package is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of

MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU Lesser General Public License for more details.

You should have received a copy of the GNU General Public License along with this program. If not, see <<http://www.gnu.org/licenses/>>.

On Debian systems, the complete text of the GNU Lesser General Public License can be found in "/usr/share/common-licenses/LGPL-3".

License: MIT

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

GNU GENERAL PUBLIC LICENSE

Version 2, June 1991

Copyright (C) 1989, 1991 Free Software Foundation, Inc.,
51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA
Everyone is permitted to copy and distribute verbatim copies
of this license document, but changing it is not allowed.

Preamble

The licenses for most software are designed to take away your freedom to share and change it. By contrast, the GNU General Public License is intended to guarantee your freedom to share and change free software--to make sure the software is free for all its users. This General Public License applies to most of the Free Software Foundation's software and to any other program whose authors commit to using it. (Some other Free Software Foundation software is covered by the GNU Lesser General Public License instead.) You can apply it to

your programs, too.

When we speak of free software, we are referring to freedom, not price.

Our General Public Licenses are designed to make sure that you have the freedom to distribute copies of free software (and charge for this service if you wish), that you receive source code or can get it if you want it, that you can change the software or use pieces of it in new free programs; and that you know you can do these things.

To protect your rights, we need to make restrictions that forbid anyone to deny you these rights or to ask you to surrender the rights. These restrictions translate to certain responsibilities for you if you distribute copies of the software, or if you modify it.

For example, if you distribute copies of such a program, whether gratis or for a fee, you must give the recipients all the rights that you have. You must make sure that they, too, receive or can get the source code. And you must show them these terms so they know their rights.

We protect your rights with two steps: (1) copyright the software, and (2) offer you this license which gives you legal permission to copy, distribute and/or modify the software.

Also, for each author's protection and ours, we want to make certain that everyone understands that there is no warranty for this free software. If the software is modified by someone else and passed on, we want its recipients to know that what they have is not the original, so that any problems introduced by others will not reflect on the original authors' reputations.

Finally, any free program is threatened constantly by software patents. We wish to avoid the danger that redistributors of a free program will individually obtain patent licenses, in effect making the program proprietary. To prevent this, we have made it clear that any patent must be licensed for everyone's free use or not licensed at all.

The precise terms and conditions for copying, distribution and modification follow.

GNU GENERAL PUBLIC LICENSE TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

0. This License applies to any program or other work which contains a notice placed by the copyright holder saying it may be distributed under the terms of this General Public License. The "Program", below,

refers to any such program or work, and a "work based on the Program" means either the Program or any derivative work under copyright law: that is to say, a work containing the Program or a portion of it, either verbatim or with modifications and/or translated into another language. (Hereinafter, translation is included without limitation in the term "modification".) Each licensee is addressed as "you".

Activities other than copying, distribution and modification are not covered by this License; they are outside its scope. The act of running the Program is not restricted, and the output from the Program is covered only if its contents constitute a work based on the Program (independent of having been made by running the Program). Whether that is true depends on what the Program does.

1. You may copy and distribute verbatim copies of the Program's source code as you receive it, in any medium, provided that you conspicuously and appropriately publish on each copy an appropriate copyright notice and disclaimer of warranty; keep intact all the notices that refer to this License and to the absence of any warranty; and give any other recipients of the Program a copy of this License along with the Program.

You may charge a fee for the physical act of transferring a copy, and you may at your option offer warranty protection in exchange for a fee.

2. You may modify your copy or copies of the Program or any portion of it, thus forming a work based on the Program, and copy and distribute such modifications or work under the terms of Section 1 above, provided that you also meet all of these conditions:

a) You must cause the modified files to carry prominent notices stating that you changed the files and the date of any change.

b) You must cause any work that you distribute or publish, that in whole or in part contains or is derived from the Program or any part thereof, to be licensed as a whole at no charge to all third parties under the terms of this License.

c) If the modified program normally reads commands interactively when run, you must cause it, when started running for such interactive use in the most ordinary way, to print or display an announcement including an appropriate copyright notice and a notice that there is no warranty (or else, saying that you provide a warranty) and that users may redistribute the program under these conditions, and telling the user how to view a copy of this License. (Exception: if the Program itself is interactive but

does not normally print such an announcement, your work based on the Program is not required to print an announcement.)

These requirements apply to the modified work as a whole. If identifiable sections of that work are not derived from the Program, and can be reasonably considered independent and separate works in themselves, then this License, and its terms, do not apply to those sections when you distribute them as separate works. But when you distribute the same sections as part of a whole which is a work based on the Program, the distribution of the whole must be on the terms of this License, whose permissions for other licensees extend to the entire whole, and thus to each and every part regardless of who wrote it.

Thus, it is not the intent of this section to claim rights or contest your rights to work written entirely by you; rather, the intent is to exercise the right to control the distribution of derivative or collective works based on the Program.

In addition, mere aggregation of another work not based on the Program with the Program (or with a work based on the Program) on a volume of a storage or distribution medium does not bring the other work under the scope of this License.

3. You may copy and distribute the Program (or a work based on it, under Section 2) in object code or executable form under the terms of Sections 1 and 2 above provided that you also do one of the following:

- a) Accompany it with the complete corresponding machine-readable source code, which must be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange; or,
- b) Accompany it with a written offer, valid for at least three years, to give any third party, for a charge no more than your cost of physically performing source distribution, a complete machine-readable copy of the corresponding source code, to be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange; or,
- c) Accompany it with the information you received as to the offer to distribute corresponding source code. (This alternative is allowed only for noncommercial distribution and only if you received the program in object code or executable form with such an offer, in accord with Subsection b above.)

The source code for a work means the preferred form of the work for making modifications to it. For an executable work, complete source

code means all the source code for all modules it contains, plus any associated interface definition files, plus the scripts used to control compilation and installation of the executable. However, as a special exception, the source code distributed need not include anything that is normally distributed (in either source or binary form) with the major components (compiler, kernel, and so on) of the operating system on which the executable runs, unless that component itself accompanies the executable.

If distribution of executable or object code is made by offering access to copy from a designated place, then offering equivalent access to copy the source code from the same place counts as distribution of the source code, even though third parties are not compelled to copy the source along with the object code.

4. You may not copy, modify, sublicense, or distribute the Program except as expressly provided under this License. Any attempt otherwise to copy, modify, sublicense or distribute the Program is void, and will automatically terminate your rights under this License. However, parties who have received copies, or rights, from you under this License will not have their licenses terminated so long as such parties remain in full compliance.

5. You are not required to accept this License, since you have not signed it. However, nothing else grants you permission to modify or distribute the Program or its derivative works. These actions are prohibited by law if you do not accept this License. Therefore, by modifying or distributing the Program (or any work based on the Program), you indicate your acceptance of this License to do so, and all its terms and conditions for copying, distributing or modifying the Program or works based on it.

6. Each time you redistribute the Program (or any work based on the Program), the recipient automatically receives a license from the original licensor to copy, distribute or modify the Program subject to these terms and conditions. You may not impose any further restrictions on the recipients' exercise of the rights granted herein. You are not responsible for enforcing compliance by third parties to this License.

7. If, as a consequence of a court judgment or allegation of patent infringement or for any other reason (not limited to patent issues), conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot distribute so as to satisfy simultaneously your obligations under this

License and any other pertinent obligations, then as a consequence you may not distribute the Program at all. For example, if a patent license would not permit royalty-free redistribution of the Program by all those who receive copies directly or indirectly through you, then the only way you could satisfy both it and this License would be to refrain entirely from distribution of the Program.

If any portion of this section is held invalid or unenforceable under any particular circumstance, the balance of the section is intended to apply and the section as a whole is intended to apply in other circumstances.

It is not the purpose of this section to induce you to infringe any patents or other property right claims or to contest validity of any such claims; this section has the sole purpose of protecting the integrity of the free software distribution system, which is implemented by public license practices. Many people have made generous contributions to the wide range of software distributed through that system in reliance on consistent application of that system; it is up to the author/donor to decide if he or she is willing to distribute software through any other system and a licensee cannot impose that choice.

This section is intended to make thoroughly clear what is believed to be a consequence of the rest of this License.

8. If the distribution and/or use of the Program is restricted in certain countries either by patents or by copyrighted interfaces, the original copyright holder who places the Program under this License may add an explicit geographical distribution limitation excluding those countries, so that distribution is permitted only in or among countries not thus excluded. In such case, this License incorporates the limitation as if written in the body of this License.

9. The Free Software Foundation may publish revised and/or new versions of the General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Program specifies a version number of this License which applies to it and "any later version", you have the option of following the terms and conditions either of that version or of any later version published by the Free Software Foundation. If the Program does not specify a version number of this License, you may choose any version ever published by the Free Software

Foundation.

10. If you wish to incorporate parts of the Program into other free programs whose distribution conditions are different, write to the author to ask for permission. For software which is copyrighted by the Free Software Foundation, write to the Free Software Foundation; we sometimes make exceptions for this. Our decision will be guided by the two goals of preserving the free status of all derivatives of our free software and of promoting the sharing and reuse of software generally.

NO WARRANTY

11. BECAUSE THE PROGRAM IS LICENSED FREE OF CHARGE, THERE IS NO WARRANTY FOR THE PROGRAM, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE PROGRAM "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE PROGRAM IS WITH YOU. SHOULD THE PROGRAM PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

12. IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY AND/OR REDISTRIBUTE THE PROGRAM AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE PROGRAM (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE PROGRAM TO OPERATE WITH ANY OTHER PROGRAMS), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Programs

If you develop a new program, and you want it to be of the greatest possible use to the public, the best way to achieve this is to make it free software which everyone can redistribute and change under these terms.

To do so, attach the following notices to the program. It is safest to attach them to the start of each source file to most effectively convey the exclusion of warranty; and each file should have at least the "copyright" line and a pointer to where the full notice is found.

<one line to give the program's name and a brief idea of what it does.>

Copyright (C) <year> <name of author>

This program is free software; you can redistribute it and/or modify it under the terms of the GNU

General Public License as published by the Free Software Foundation; either version 2 of the License, or (at your option) any later version.

This program is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details.

You should have received a copy of the GNU General Public License along with this program; if not, write to the Free Software Foundation, Inc., 51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA.

Also add information on how to contact you by electronic and paper mail.

If the program is interactive, make it output a short notice like this when it starts in an interactive mode:

```
Gnomovision version 69, Copyright (C) year name of author
Gnomovision comes with ABSOLUTELY NO WARRANTY; for details type `show w'.
This is free software, and you are welcome to redistribute
it
under certain conditions; type `show c' for details.
```

The hypothetical commands `show w' and `show c' should show the appropriate parts of the General Public License. Of course, the commands you use may be called something other than `show w' and `show c'; they could even be mouse-clicks or menu items--whatever suits your program.

You should also get your employer (if you work as a programmer) or your school, if any, to sign a "copyright disclaimer" for the program, if necessary. Here is a sample; alter the names:

```
Yoyodyne, Inc., hereby disclaims all copyright interest in the program
`Gnomovision' (which makes passes at compilers) written by James Hacker.
```

```
<signature of Ty Coon>, 1 April 1989
Ty Coon, President of Vice
```

This General Public License does not permit incorporating your program into proprietary programs. If your program is a subroutine library, you may consider it more useful to permit linking proprietary applications with the library. If this

is what you want to do, use the GNU Lesser General Public License instead of this License.

This library is free software; you can redistribute it and/or modify it under the terms of the GNU Lesser General Public License as published by the Free Software Foundation; either version 2.1 of the License, or (at your option) any later version.

The complete text of the license is available in the `../Documentation/licenses/COPYING.LGPLv2.1` file.

WEV @@ WEV[B "1

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

1. Redistributions of source code must retain the above copyright notice, and the entire permission notice in its entirety, including the disclaimer of warranties.
2. Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.
3. The name of the author may not be used to endorse or promote products derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED ``AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, ALL OF WHICH ARE HEREBY DISCLAIMED. IN NO EVENT SHALL THE AUTHOR BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL

DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF NOT ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

x ?"U@,5 @mISmIN<GimCN7g1uE
43mI,5WEV @@ WEV @mImImIAmImImI0mImImI*mImI
A0mImImI...
lost+found...

;9GimCN7g

!"#\$%&'()*+,-

./0123456789;<=>?@ABCDEFGHIJKLMN0PQRSTUVWXYZ[\]^_`abcdefghijklmnopqrstuvwxyz{|}~

!"#\$%&'()*+,-

./0123456789;.<=>?@ABCDEFGHIJKLMNOPQRSTUVWXYZ[\]^_`abcdefghijklmnopqrstuvwxyz{|}~

!"#\$%&'()*+,-

./0123456789;.<=>?@ABCDEFGHIJKLMNOPQRSTUVWXYZ[\]^_`abcdefghijklmnopqrstuvwxyz{|}~

!"#\$%&'()*+,-

./0123456789;.<=>?@ABCDEFGHIJKLMNOPQRSTUVWXYZ[\]^_`abcdefghijklmnopqrstuvwxyz{|}~WEV @@
WEV[B "1

/*

- * Copyright (c) 1989 The Regents of the University of California.
- * All rights reserved.
- *
- * Redistribution and use in source and binary forms, with or without
- * modification, are permitted provided that the following conditions
- * are met:
- * 1. Redistributions of source code must retain the above copyright
- * notice, this list of conditions and the following disclaimer.
- * 2. Redistributions in binary form must reproduce the above copyright
- * notice, this list of conditions and the following disclaimer in the
- * documentation and/or other materials provided with the distribution.
- * 3. All advertising materials mentioning features or use of this software
- * must display the following acknowledgement:
- * This product includes software developed by the University of
- * California, Berkeley and its contributors.
- * 4. Neither the name of the University nor the names of its contributors
- * may be used to endorse or promote products derived from this software
- *

without specific prior written permission.

*

- * THIS SOFTWARE IS PROVIDED BY THE REGENTS AND CONTRIBUTORS ``AS IS" AND
- * ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE
- * IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE
- * ARE DISCLAIMED. IN NO EVENT SHALL THE REGENTS OR CONTRIBUTORS BE LIABLE
- * FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL
- * DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS
- * OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION)
- * HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT
- * LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY
- * OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF
- * SUCH DAMAGE.

*/

This library is free software; you can redistribute it and/or
modify it under the terms of the Modified BSD License.

The complete text of the license is available in the
../Documentation/licenses/COPYING.BSD-3 file.

1.53 mount 2.31.1-0.4ubuntu3.7

1.53.1 Available under license :

GNU GENERAL PUBLIC LICENSE

Version 2, June 1991

Copyright (C) 1989, 1991 Free Software Foundation, Inc.,
51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA
Everyone is permitted to copy and distribute verbatim copies
of this license document, but changing it is not allowed.

Preamble

The licenses for most software are designed to take away your freedom to share and change it. By contrast, the GNU General Public License is intended to guarantee your freedom to share and change free software--to make sure the software is free for all its users. This General Public License applies to most of the Free Software Foundation's software and to any other program whose authors commit to using it. (Some other Free Software Foundation software is covered by the GNU Lesser General Public License instead.) You can apply it to your programs, too.

When we speak of free software, we are referring to freedom, not price.

Our General Public Licenses are designed to make sure that you have the freedom to distribute copies of free software (and charge for this service if you wish), that you receive source code or can get it if you want it, that you can change the software or use pieces of it in new free programs; and that you know you can do these things.

To protect your rights, we need to make restrictions that forbid anyone to deny you these rights or to ask you to surrender the rights. These restrictions translate to certain responsibilities for you if you distribute copies of the software, or if you modify it.

For example, if you distribute copies of such a program, whether gratis or for a fee, you must give the recipients all the rights that you have. You must make sure that they, too, receive or can get the source code. And you must show them these terms so they know their rights.

We protect your rights with two steps: (1) copyright the software, and (2) offer you this license which gives you legal permission to copy, distribute and/or modify the software.

Also, for each author's protection and ours, we want to make certain that everyone understands that there is no warranty for this free software. If the software is modified by someone else and passed on, we want its recipients to know that what they have is not the original, so that any problems introduced by others will not reflect on the original authors' reputations.

Finally, any free program is threatened constantly by software patents. We wish to avoid the danger that redistributors of a free program will individually obtain patent licenses, in effect making the program proprietary. To prevent this, we have made it clear that any patent must be licensed for everyone's free use or not licensed at all.

The precise terms and conditions for copying, distribution and modification follow.

GNU GENERAL PUBLIC LICENSE TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

0. This License applies to any program or other work which contains a notice placed by the copyright holder saying it may be distributed under the terms of this General Public License. The "Program", below, refers to any such program or work, and a "work based on the Program" means either the Program or any derivative work under copyright law: that is to say, a work containing the Program or a portion of it, either verbatim or with modifications and/or translated into another language. (Hereinafter, translation is included without limitation in the term "modification".) Each licensee is addressed as "you".

Activities other than copying, distribution and modification are not covered by this License; they are outside its scope. The act of running the Program is not restricted, and the output from the Program is covered only if its contents constitute a work based on the Program (independent of having been made by running the Program). Whether that is true depends on what the Program does.

1. You may copy and distribute verbatim copies of the Program's source code as you receive it, in any medium, provided that you conspicuously and appropriately publish on each copy an appropriate copyright notice and disclaimer of warranty; keep intact all the notices that refer to this License and to the absence of any warranty; and give any other recipients of the Program a copy of this License along with the Program.

You may charge a fee for the physical act of transferring a copy, and you may at your option offer warranty protection in exchange for a fee.

2. You may modify your copy or copies of the Program or any portion of it, thus forming a work based on the Program, and copy and distribute such modifications or work under the terms of Section 1 above, provided that you also meet all of these conditions:

a) You must cause the modified files to carry prominent notices stating that you changed the files and the date of any change.

b) You must cause any work that you distribute or publish, that in whole or in part contains or is derived from the Program or any part thereof, to be licensed as a whole at no charge to all third parties under the terms of this License.

c) If the modified program normally reads commands interactively when run, you must cause it, when started running for such interactive use in the most ordinary way, to print or display an announcement including an appropriate copyright notice and a notice that there is no warranty (or else, saying that you provide a warranty) and that users may redistribute the program under these conditions, and telling the user how to view a copy of this License. (Exception: if the Program itself is interactive but does not normally print such an announcement, your work based on the Program is not required to print an announcement.)

These requirements apply to the modified work as a whole. If identifiable sections of that work are not derived from the Program, and can be reasonably considered independent and separate works in themselves, then this License, and its terms, do not apply to those sections when you distribute them as separate works. But when you distribute the same sections as part of a whole which is a work based on the Program, the distribution of the whole must be on the terms of this License, whose permissions for other licensees extend to the entire whole, and thus to each and every part regardless of who wrote it.

Thus, it is not the intent of this section to claim rights or contest your rights to work written entirely by you; rather, the intent is to exercise the right to control the distribution of derivative or collective works based on the Program.

In addition, mere aggregation of another work not based on the Program with the Program (or with a work based on the Program) on a volume of a storage or distribution medium does not bring the other work under the scope of this License.

3. You may copy and distribute the Program (or a work based on it, under Section 2) in object code or executable form under the terms of

Sections 1 and 2 above provided that you also do one of the following:

- a) Accompany it with the complete corresponding machine-readable source code, which must be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange; or,
- b) Accompany it with a written offer, valid for at least three years, to give any third party, for a charge no more than your cost of physically performing source distribution, a complete machine-readable copy of the corresponding source code, to be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange; or,
- c) Accompany it with the information you received as to the offer to distribute corresponding source code. (This alternative is allowed only for noncommercial distribution and only if you received the program in object code or executable form with such an offer, in accord with Subsection b above.)

The source code for a work means the preferred form of the work for making modifications to it. For an executable work, complete source code means all the source code for all modules it contains, plus any associated interface definition files, plus the scripts used to control compilation and installation of the executable. However, as a special exception, the source code distributed need not include anything that is normally distributed (in either source or binary form) with the major components (compiler, kernel, and so on) of the operating system on which the executable runs, unless that component itself accompanies the executable.

If distribution of executable or object code is made by offering access to copy from a designated place, then offering equivalent access to copy the source code from the same place counts as distribution of the source code, even though third parties are not compelled to copy the source along with the object code.

4. You may not copy, modify, sublicense, or distribute the Program except as expressly provided under this License. Any attempt otherwise to copy, modify, sublicense or distribute the Program is void, and will automatically terminate your rights under this License. However, parties who have received copies, or rights, from you under this License will not have their licenses terminated so long as such parties remain in full compliance.

5. You are not required to accept this License, since you have not signed it. However, nothing else grants you permission to modify or

distribute the Program or its derivative works. These actions are prohibited by law if you do not accept this License. Therefore, by modifying or distributing the Program (or any work based on the Program), you indicate your acceptance of this License to do so, and all its terms and conditions for copying, distributing or modifying the Program or works based on it.

6. Each time you redistribute the Program (or any work based on the Program), the recipient automatically receives a license from the original licensor to copy, distribute or modify the Program subject to these terms and conditions. You may not impose any further restrictions on the recipients' exercise of the rights granted herein. You are not responsible for enforcing compliance by third parties to this License.

7. If, as a consequence of a court judgment or allegation of patent infringement or for any other reason (not limited to patent issues), conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot distribute so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not distribute the Program at all. For example, if a patent license would not permit royalty-free redistribution of the Program by all those who receive copies directly or indirectly through you, then the only way you could satisfy both it and this License would be to refrain entirely from distribution of the Program.

If any portion of this section is held invalid or unenforceable under any particular circumstance, the balance of the section is intended to apply and the section as a whole is intended to apply in other circumstances.

It is not the purpose of this section to induce you to infringe any patents or other property right claims or to contest validity of any such claims; this section has the sole purpose of protecting the integrity of the free software distribution system, which is implemented by public license practices. Many people have made generous contributions to the wide range of software distributed through that system in reliance on consistent application of that system; it is up to the author/donor to decide if he or she is willing to distribute software through any other system and a licensee cannot impose that choice.

This section is intended to make thoroughly clear what is believed to

be a consequence of the rest of this License.

8. If the distribution and/or use of the Program is restricted in certain countries either by patents or by copyrighted interfaces, the original copyright holder who places the Program under this License may add an explicit geographical distribution limitation excluding those countries, so that distribution is permitted only in or among countries not thus excluded. In such case, this License incorporates the limitation as if written in the body of this License.

9. The Free Software Foundation may publish revised and/or new versions of the General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Program specifies a version number of this License which applies to it and "any later version", you have the option of following the terms and conditions either of that version or of any later version published by the Free Software Foundation. If the Program does not specify a version number of this License, you may choose any version ever published by the Free Software Foundation.

10. If you wish to incorporate parts of the Program into other free programs whose distribution conditions are different, write to the author to ask for permission. For software which is copyrighted by the Free Software Foundation, write to the Free Software Foundation; we sometimes make exceptions for this. Our decision will be guided by the two goals of preserving the free status of all derivatives of our free software and of promoting the sharing and reuse of software generally.

NO WARRANTY

11. BECAUSE THE PROGRAM IS LICENSED FREE OF CHARGE, THERE IS NO WARRANTY FOR THE PROGRAM, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE PROGRAM "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE PROGRAM IS WITH YOU. SHOULD THE PROGRAM PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

12. IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY AND/OR REDISTRIBUTE THE PROGRAM AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES,

INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE PROGRAM (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR

THIRD PARTIES OR A FAILURE OF THE PROGRAM TO OPERATE WITH ANY OTHER PROGRAMS), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Programs

If you develop a new program, and you want it to be of the greatest possible use to the public, the best way to achieve this is to make it free software which everyone can redistribute and change under these terms.

To do so, attach the following notices to the program. It is safest to attach them to the start of each source file to most effectively convey the exclusion of warranty; and each file should have at least the "copyright" line and a pointer to where the full notice is found.

```
<one line to give the program's name and a brief idea of what it does.>  
Copyright (C) <year> <name of author>
```

This program is free software; you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation; either version 2 of the License, or (at your option) any later version.

This program is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details.

You should have received a copy of the GNU General Public License along with this program; if not, write to the Free Software Foundation, Inc., 51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA.

Also add information on how to contact you by electronic and paper mail.

If the program is interactive, make it output a short notice like this when it starts in an interactive mode:

```
Gnomovision version 69, Copyright (C) year name of author  
Gnomovision comes with ABSOLUTELY NO WARRANTY; for details type `show w'.  
This is free software, and you are welcome to redistribute
```

it

under certain conditions; type `show c' for details.

The hypothetical commands `show w' and `show c' should show the appropriate parts of the General Public License. Of course, the commands you use may be called something other than `show w' and `show c'; they could even be mouse-clicks or menu items--whatever suits your program.

You should also get your employer (if you work as a programmer) or your school, if any, to sign a "copyright disclaimer" for the program, if necessary. Here is a sample; alter the names:

Yoyodyne, Inc., hereby disclaims all copyright interest in the program
`Gnomovision' (which makes passes at compilers) written by James Hacker.

<signature of Ty Coon>, 1 April 1989

Ty Coon, President of Vice

This General Public License does not permit incorporating your program into proprietary programs. If your program is a subroutine library, you may consider it more useful to permit linking proprietary applications with the library. If this

is what you want to do, use the GNU Lesser General Public License instead of this License.

This library is free software; you can redistribute it and/or modify it under the terms of the GNU Lesser General Public License as published by the Free Software Foundation; either version 2.1 of the License, or (at your option) any later version.

The complete text of the license is available in the
../Documentation/licenses/COPYING.LGPLv2.1 file.

WEV @@ WEV[B "1

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

1. Redistributions of source code must retain the above copyright notice, and the entire permission notice in its entirety, including the disclaimer of warranties.
2. Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.
3. The name of the author may not be used to endorse or promote products derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED ``AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES

OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, ALL OF WHICH ARE HEREBY DISCLAIMED. IN NO EVENT SHALL THE AUTHOR BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL

DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF NOT ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

x ?"U@,5 @mISmIN<GimCN7g1uE
43mI,5WEV @@ WEV @mImImIAmImImI0mImImI*mImI
A0mImImI...
lost+found...

;9GimCN7g

!"#\$%&'()*+,-
./0123456789:;<=>?@ABCDEFGHIJKLMNOPQRSTUVWXYZ[\]^_`abcdefghijklmnopqrstuvwxyz{|}~

!"#\$%&'()*+,-
./0123456789:;<=>?@ABCDEFGHIJKLMNOPQRSTUVWXYZ[\]^_`abcdefghijklmnopqrstuvwxyz{|}~

!"#\$%&'()*+,-
./0123456789:;<=>?@ABCDEFGHIJKLMNOPQRSTUVWXYZ[\]^_`abcdefghijklmnopqrstuvwxyz{|}~

!"#\$%&'()*+,-
./0123456789:;<=>?@ABCDEFGHIJKLMNOPQRSTUVWXYZ[\]^_`abcdefghijklmnopqrstuvwxyz{|}~WEV @@
WEV[B "1
/*

- * Copyright (c) 1989 The Regents of the University of California.
- * All rights reserved.
- *
- * Redistribution and use in source and binary forms, with or without
- * modification, are permitted provided that the following conditions
- * are met:
- * 1. Redistributions of source code must retain the above copyright
- * notice, this list of conditions and the following disclaimer.
- * 2. Redistributions in binary form must reproduce the above copyright
- * notice, this list of conditions and the following disclaimer in the
- * documentation and/or other materials provided with the distribution.
- * 3. All advertising materials mentioning features or use of this software
- * must display the following acknowledgement:
- * This product includes software developed by the University of
- * California, Berkeley and its contributors.
- * 4. Neither the name of the University nor the names of its contributors
- * may be used to endorse or promote products derived from this software

*
without specific prior written permission.
*
* THIS SOFTWARE IS PROVIDED BY THE REGENTS AND CONTRIBUTORS ``AS IS" AND
* ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE
* IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE
* ARE DISCLAIMED. IN NO EVENT SHALL THE REGENTS OR CONTRIBUTORS BE LIABLE
* FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL
* DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS
* OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION)
* HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT
* LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY
* OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF
* SUCH DAMAGE.
*/

This library is free software; you can redistribute it and/or
modify it under the terms of the Modified BSD License.

The complete text of the license is available in the
../Documentation/licenses/COPYING.BSD-3 file.

1.54 libaudit 1:2.8.2-1ubuntu1.1

1.54.1 Available under license :

Format: <http://www.debian.org/doc/packaging-manuals/copyright-format/1.0/>

Upstream-Name: auditd

Source: <https://people.redhat.com/sgrubb/audit/>

Files: *

Copyright: 2012-2016 Steve Grubb <sgrubb@redhat.com>

2006-2012 Rik Faith

License: GPL-2

Files: src/libev/*

Copyright: 2007-2009 Marc Alexander Lehmann

License: GPL-2

Files: lib/*

Copyright: 2005-2008 Steve Grubb <sgrubb@redhat.com>

License: LGPL-2.1

The audit daemon's library libaudit.* is released under LGPL
so that it may be linked with 3rd party software.

.

On Debian systems, refer to </usr/share/common-licenses/LGPL-2.1>
for the complete text of the GNU Lesser General Public License.

Files: debian/*

Copyright: 2007-2011 Philipp Matthias Hahn <pmhahn@debian.org>

2012-2016 Laurent Bigonville <bigon@debian.org>

License: GPL-2

License: GPL-2

This package is free software; you can redistribute it and/or modify it under the terms of the GNU General Public License version 2, as published by the Free Software Foundation.

This package is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details.

You should have received a copy of the GNU General Public License along with this package; if not, write to the Free Software Foundation, Inc., 51 Franklin St, Fifth Floor, Boston, MA 02110-1301 USA

On Debian systems, the complete text of the GNU General Public License can be found in `~/usr/share/common-licenses/GPL-1'`.

1.55 fdisk 2.31.1-0.4ubuntu3.7

1.55.1 Available under license :

GNU GENERAL PUBLIC LICENSE

Version 2, June 1991

Copyright (C) 1989, 1991 Free Software Foundation, Inc.,
51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA
Everyone is permitted to copy and distribute verbatim copies
of this license document, but changing it is not allowed.

Preamble

The licenses for most software are designed to take away your freedom to share and change it. By contrast, the GNU General Public License is intended to guarantee your freedom to share and change free software--to make sure the software is free for all its users. This General Public License applies to most of the Free Software Foundation's software and to any other program whose authors commit to using it. (Some other Free Software Foundation software is covered by the GNU Lesser General Public License instead.) You can apply it to your programs, too.

When we speak of free software, we are referring to freedom, not price.

Our General Public Licenses are designed to make sure that you have the freedom to distribute copies of free software (and charge for this service if you wish), that you receive source code or can get it if you want it, that you can change the software or use pieces of it in new free programs; and that you know you can do these things.

To protect your rights, we need to make restrictions that forbid anyone to deny you these rights or to ask you to surrender the rights. These restrictions translate to certain responsibilities for you if you distribute copies of the software, or if you modify it.

For example, if you distribute copies of such a program, whether gratis or for a fee, you must give the recipients all the rights that you have. You must make sure that they, too, receive or can get the source code. And you must show them these terms so they know their rights.

We protect your rights with two steps: (1) copyright the software, and (2) offer you this license which gives you legal permission to copy, distribute and/or modify the software.

Also, for each author's protection and ours, we want to make certain that everyone understands that there is no warranty for this free software. If the software is modified by someone else and passed on, we want its recipients to know that what they have is not the original, so that any problems introduced by others will not reflect on the original authors' reputations.

Finally, any free program is threatened constantly by software patents. We wish to avoid the danger that redistributors of a free program will individually obtain patent licenses, in effect making the program proprietary. To prevent this, we have made it clear that any patent must be licensed for everyone's free use or not licensed at all.

The precise terms and conditions for copying, distribution and modification follow.

GNU GENERAL PUBLIC LICENSE

TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

0. This License applies to any program or other work which contains a notice placed by the copyright holder saying it may be distributed under the terms of this General Public License. The "Program", below, refers to any such program or work, and a "work based on the Program" means either the Program or any derivative work under copyright law: that is to say, a work containing the Program or a portion of it, either verbatim or with modifications and/or translated into another

language. (Hereinafter, translation is included without limitation in the term "modification".) Each licensee is addressed as "you".

Activities other than copying, distribution and modification are not covered by this License; they are outside its scope. The act of running the Program is not restricted, and the output from the Program is covered only if its contents constitute a work based on the Program (independent of having been made by running the Program). Whether that is true depends on what the Program does.

1. You may copy and distribute verbatim copies of the Program's source code as you receive it, in any medium, provided that you conspicuously and appropriately publish on each copy an appropriate copyright notice and disclaimer of warranty; keep intact all the notices that refer to this License and to the absence of any warranty; and give any other recipients of the Program a copy of this License along with the Program.

You may charge a fee for the physical act of transferring a copy, and you may at your option offer warranty protection in exchange for a fee.

2. You may modify your copy or copies of the Program or any portion of it, thus forming a work based on the Program, and copy and distribute such modifications or work under the terms of Section 1 above, provided that you also meet all of these conditions:

a) You must cause the modified files to carry prominent notices stating that you changed the files and the date of any change.

b) You must cause any work that you distribute or publish, that in whole or in part contains or is derived from the Program or any part thereof, to be licensed as a whole at no charge to all third parties under the terms of this License.

c) If the modified program normally reads commands interactively when run, you must cause it, when started running for such interactive use in the most ordinary way, to print or display an announcement including an appropriate copyright notice and a notice that there is no warranty (or else, saying that you provide a warranty) and that users may redistribute the program under these conditions, and telling the user how to view a copy of this License. (Exception: if the Program itself is interactive but does not normally print such an announcement, your work based on the Program is not required to print an announcement.)

These requirements apply to the modified work as a whole. If

identifiable sections of that work
are not derived from the Program,
and can be reasonably considered independent and separate works in
themselves, then this License, and its terms, do not apply to those
sections when you distribute them as separate works. But when you
distribute the same sections as part of a whole which is a work based
on the Program, the distribution of the whole must be on the terms of
this License, whose permissions for other licensees extend to the
entire whole, and thus to each and every part regardless of who wrote it.

Thus, it is not the intent of this section to claim rights or contest
your rights to work written entirely by you; rather, the intent is to
exercise the right to control the distribution of derivative or
collective works based on the Program.

In addition, mere aggregation of another work not based on the Program
with the Program (or with a work based on the Program) on a volume of
a storage or distribution medium does not bring the other work under
the scope of this License.

3. You may copy and distribute the Program (or a work based on it,
under Section 2) in object code or executable form under the terms of
Sections 1 and 2 above provided that you also do one of the following:

a) Accompany it with the complete corresponding machine-readable
source code, which must be distributed under the terms of Sections
1 and 2 above on a medium customarily used for software interchange; or,

b) Accompany it with a written offer, valid for at least three
years, to give any third party, for a charge no more than your
cost of physically performing source distribution, a complete
machine-readable copy of the corresponding source code, to be
distributed under the terms of Sections 1 and 2 above on a medium
customarily used for software interchange; or,

c) Accompany it with the information you received as to the offer
to distribute corresponding source code. (This alternative is
allowed only for noncommercial distribution
and only if you
received the program in object code or executable form with such
an offer, in accord with Subsection b above.)

The source code for a work means the preferred form of the work for
making modifications to it. For an executable work, complete source
code means all the source code for all modules it contains, plus any
associated interface definition files, plus the scripts used to
control compilation and installation of the executable. However, as a
special exception, the source code distributed need not include

anything that is normally distributed (in either source or binary form) with the major components (compiler, kernel, and so on) of the operating system on which the executable runs, unless that component itself accompanies the executable.

If distribution of executable or object code is made by offering access to copy from a designated place, then offering equivalent access to copy the source code from the same place counts as distribution of the source code, even though third parties are not compelled to copy the source along with the object code.

4. You may not copy, modify, sublicense, or distribute the Program except as expressly provided under this License. Any attempt otherwise to copy, modify, sublicense or distribute the Program is void, and will automatically terminate your rights under this License. However, parties who have received copies, or rights, from you under this License will not have their licenses terminated so long as such parties remain in full compliance.

5. You are not required to accept this License, since you have not signed it. However, nothing else grants you permission to modify or distribute the Program or its derivative works. These actions are prohibited by law if you do not accept this License. Therefore, by modifying or distributing the Program (or any work based on the Program), you indicate your acceptance of this License to do so, and all its terms and conditions for copying, distributing or modifying the Program or works based on it.

6. Each time you redistribute the Program (or any work based on the Program), the recipient automatically receives a license from the original licensor to copy, distribute or modify the Program subject to these terms and conditions. You may not impose any further restrictions on the recipients' exercise of the rights granted herein. You are not responsible for enforcing compliance by third parties to this License.

7. If, as a consequence of a court judgment or allegation of patent infringement or for any other reason (not limited to patent issues), conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot distribute so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not distribute the Program at all. For example, if a patent license would not permit royalty-free redistribution of the Program by

all those who receive copies directly or indirectly through you, then the only way you could satisfy both it and this License would be to refrain entirely from distribution of the Program.

If any portion of this section is held invalid or unenforceable under any particular circumstance, the balance of the section is intended to apply and the section as a whole is intended to apply in other circumstances.

It is not the purpose of this section to induce you to infringe any patents or other property right claims or to contest validity of any such claims; this section has the sole purpose of protecting the integrity of the free software distribution system, which is implemented by public license practices. Many people have made generous contributions to the wide range of software distributed through that system in reliance on consistent application of that system; it is up to the author/donor to decide if he or she is willing to distribute software through any other system and a licensee cannot impose that choice.

This section is intended to make thoroughly clear what is believed to be a consequence of the rest of this License.

8. If the distribution and/or use of the Program is restricted in certain countries either by patents or by copyrighted interfaces, the original copyright holder who places the Program under this License may add an explicit geographical distribution limitation excluding those countries, so that distribution is permitted only in or among countries not thus excluded. In such case, this License incorporates the limitation as if written in the body of this License.

9. The Free Software Foundation may publish revised and/or new versions of the General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Program specifies a version number of this License which applies to it and "any later version", you have the option of following the terms and conditions either of that version or of any later version published by the Free Software Foundation. If the Program does not specify a version number of this License, you may choose any version ever published by the Free Software Foundation.

10. If you wish to incorporate parts of the Program into other free programs whose distribution conditions are different, write to the author

to ask for permission. For software which is copyrighted by the Free Software Foundation, write to the Free Software Foundation; we sometimes make exceptions for this. Our decision will be guided by the two goals of preserving the free status of all derivatives of our free software and of promoting the sharing and reuse of software generally.

NO WARRANTY

11. BECAUSE THE PROGRAM IS LICENSED FREE OF CHARGE, THERE IS NO WARRANTY FOR THE PROGRAM, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE PROGRAM "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE PROGRAM IS WITH YOU. SHOULD THE PROGRAM PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

12. IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY AND/OR REDISTRIBUTE THE PROGRAM AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE PROGRAM (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE PROGRAM TO OPERATE WITH ANY OTHER PROGRAMS), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Programs

If you develop a new program, and you want it to be of the greatest possible use to the public, the best way to achieve this is to make it free software which everyone can redistribute and change under these terms.

To do so, attach the following notices to the program. It is safest to attach them to the start of each source file to most effectively convey the exclusion of warranty; and each file should have at least the "copyright" line and a pointer to where the full notice is found.

```
<one line to give the program's name and a brief idea of what it does.>  
Copyright (C) <year> <name of author>
```

```
This program is free software; you can redistribute it and/or modify  
it under the terms of the GNU
```

General Public License as published by
the Free Software Foundation; either version 2 of the License, or
(at your option) any later version.

This program is distributed in the hope that it will be useful,
but WITHOUT ANY WARRANTY; without even the implied warranty of
MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
GNU General Public License for more details.

You should have received a copy of the GNU General Public License along
with this program; if not, write to the Free Software Foundation, Inc.,
51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA.

Also add information on how to contact you by electronic and paper mail.

If the program is interactive, make it output a short notice like this
when it starts in an interactive mode:

```
Gnomovision version 69, Copyright (C) year name of author
Gnomovision comes with ABSOLUTELY NO WARRANTY; for details type `show w'.
This is free software, and you are welcome to redistribute
it
under certain conditions; type `show c' for details.
```

The hypothetical commands ``show w'` and ``show c'` should show the appropriate
parts of the General Public License. Of course, the commands you use may
be called something other than ``show w'` and ``show c'`; they could even be
mouse-clicks or menu items--whatever suits your program.

You should also get your employer (if you work as a programmer) or your
school, if any, to sign a "copyright disclaimer" for the program, if
necessary. Here is a sample; alter the names:

```
Yoyodyne, Inc., hereby disclaims all copyright interest in the program
`Gnomovision' (which makes passes at compilers) written by James Hacker.
```

```
<signature of Ty Coon>, 1 April 1989
Ty Coon, President of Vice
```

This General Public License does not permit incorporating your program into
proprietary programs. If your program is a subroutine library, you may
consider it more useful to permit linking proprietary applications with the
library. If this
is what you want to do, use the GNU Lesser General
Public License instead of this License.

This library is free software; you can redistribute it and/or
modify it under the terms of the GNU Lesser General Public
License as published by the Free Software Foundation; either

version 2.1 of the License, or (at your option) any later version.

The complete text of the license is available in the `../Documentation/licenses/COPYING.LGPLv2.1` file.

WEV @@ WEV[B "1

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

1. Redistributions of source code must retain the above copyright notice, and the entire permission notice in its entirety, including the disclaimer of warranties.
2. Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.
3. The name of the author may not be used to endorse or promote products derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED ``AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, ALL OF WHICH ARE HEREBY DISCLAIMED. IN NO EVENT SHALL THE AUTHOR BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL

DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF NOT ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

x ?"U@,5 @mISmIN<GimCN7g1u|E
43mI,5WEV @@ WEV @mImImIAmImImI0mImImI*mImI
A0mImImI...
lost+found...

;9GimCN7g

!"#\$%&'()*+,-
./0123456789;:<=>?@ABCDEFGHIJKLMNOPQRSTUVWXYZ[\]^_`abcdefghijklmnopqrstuvwxyz{|}~

!"#\$%&'()*+,-
./0123456789;:<=>?@ABCDEFGHIJKLMNOPQRSTUVWXYZ[\]^_`abcdefghijklmnopqrstuvwxyz{|}~

!"#\$%&'()*+,-
./0123456789;:<=>?@ABCDEFGHIJKLMNOPQRSTUVWXYZ[\]^_`abcdefghijklmnopqrstuvwxyz{|}~

```

!"#$%&'()*+,-
./0123456789:;<=>?@ABCDEFGHIJKLMNQRSTUvwxyz[ ]^_`abcdefghijklmnopqrstuvwxyz{|}~WEV @@
WEV[B "1
/*
* Copyright (c) 1989 The Regents of the University of California.
* All rights reserved.
*
* Redistribution and use in source and binary forms, with or without
* modification, are permitted provided that the following conditions
* are met:
* 1. Redistributions of source code must retain the above copyright
* notice, this list of conditions and the following disclaimer.
* 2. Redistributions in binary form must reproduce the above copyright
* notice, this list of conditions and the following disclaimer in the
* documentation and/or other materials provided with the distribution.
* 3. All advertising materials mentioning features or use of this software
* must display the following acknowledgement:
* This product includes software developed by the University of
* California, Berkeley and its contributors.
* 4. Neither the name of the University nor the names of its contributors
* may be used to endorse or promote products derived from this software
*
* without specific prior written permission.
*
* THIS SOFTWARE IS PROVIDED BY THE REGENTS AND CONTRIBUTORS ``AS IS" AND
* ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE
* IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE
* ARE DISCLAIMED. IN NO EVENT SHALL THE REGENTS OR CONTRIBUTORS BE LIABLE
* FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL
* DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS
* OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION)
* HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT
* LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY
* OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF
* SUCH DAMAGE.
*/
This library is free software; you can redistribute it and/or
modify it under the terms of the Modified BSD License.

The complete text of the license is available in the
../Documentation/licenses/COPYING.BSD-3 file.

```

1.56 libzstd1 1.3.3+dfsg-2ubuntu1.2

1.56.1 Available under license :

GNU GENERAL PUBLIC LICENSE

Version 2, June 1991

Copyright (C) 1989, 1991 Free Software Foundation, Inc.,
51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA
Everyone is permitted to copy and distribute verbatim copies
of this license document, but changing it is not allowed.

Preamble

The licenses for most software are designed to take away your freedom to share and change it. By contrast, the GNU General Public License is intended to guarantee your freedom to share and change free software--to make sure the software is free for all its users. This General Public License applies to most of the Free Software Foundation's software and to any other program whose authors commit to using it. (Some other Free Software Foundation software is covered by the GNU Lesser General Public License instead.) You can apply it to your programs, too.

When we speak of free software, we are referring to freedom, not price.

Our General Public Licenses are designed to make sure that you have the freedom to distribute copies of free software (and charge for this service if you wish), that you receive source code or can get it if you want it, that you can change the software or use pieces of it in new free programs; and that you know you can do these things.

To protect your rights, we need to make restrictions that forbid anyone to deny you these rights or to ask you to surrender the rights. These restrictions translate to certain responsibilities for you if you distribute copies of the software, or if you modify it.

For example, if you distribute copies of such a program, whether gratis or for a fee, you must give the recipients all the rights that you have. You must make sure that they, too, receive or can get the source code. And you must show them these terms so they know their rights.

We protect your rights with two steps: (1) copyright the software, and (2) offer you this license which gives you legal permission to copy, distribute and/or modify the software.

Also, for each author's protection and ours, we want to make certain that everyone understands that there is no warranty for this free software. If the software is modified by someone else and passed on, we

want its recipients to know that what they have is not the original, so that any problems introduced by others will not reflect on the original authors' reputations.

Finally, any free program is threatened constantly by software patents. We wish to avoid the danger that redistributors of a free program will individually obtain patent licenses, in effect making the program proprietary. To prevent this, we have made it clear that any patent must be licensed for everyone's free use or not licensed at all.

The precise terms and conditions for copying, distribution and modification follow.

GNU GENERAL PUBLIC LICENSE TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

0. This License applies to any program or other work which contains a notice placed by the copyright holder saying it may be distributed under the terms of this General Public License. The "Program", below, refers to any such program or work, and a "work based on the Program" means either the Program or any derivative work under copyright law: that is to say, a work containing the Program or a portion of it, either verbatim or with modifications and/or translated into another language. (Hereinafter, translation is included without limitation in the term "modification".) Each licensee is addressed as "you".

Activities other than copying, distribution and modification are not covered by this License; they are outside its scope. The act of running the Program is not restricted, and the output from the Program is covered only if its contents constitute a work based on the Program (independent of having been made by running the Program). Whether that is true depends on what the Program does.

1. You may copy and distribute verbatim copies of the Program's source code as you receive it, in any medium, provided that you conspicuously and appropriately publish on each copy an appropriate copyright notice and disclaimer of warranty; keep intact all the notices that refer to this License and to the absence of any warranty; and give any other recipients of the Program a copy of this License along with the Program.

You may charge a fee for the physical act of transferring a copy, and you may at your option offer warranty protection in exchange for a fee.

2. You may modify your copy or copies of the Program or any portion of it, thus forming a work based on the Program, and copy and distribute such modifications or work under the terms of Section 1

above, provided that you also meet all of these conditions:

- a) You must cause the modified files to carry prominent notices stating that you changed the files and the date of any change.

- b) You must cause any work that you distribute or publish, that in whole or in part contains or is derived from the Program or any part thereof, to be licensed as a whole at no charge to all third parties under the terms of this License.

- c) If the modified program normally reads commands interactively when run, you must cause it, when started running for such interactive use in the most ordinary way, to print or display an announcement including an appropriate copyright notice and a notice that there is no warranty (or else, saying that you provide a warranty) and that users may redistribute the program under these conditions, and telling the user how to view a copy of this License. (Exception: if the Program itself is interactive but does not normally print such an announcement, your work based on the Program is not required to print an announcement.)

These requirements apply to the modified work as a whole. If identifiable sections of that work are not derived from the Program, and can be reasonably considered independent and separate works in themselves, then this License, and its terms, do not apply to those sections when you distribute them as separate works. But when you distribute the same sections as part of a whole which is a work based on the Program, the distribution of the whole must be on the terms of this License, whose permissions for other licensees extend to the entire whole, and thus to each and every part regardless of who wrote it.

Thus, it is not the intent of this section to claim rights or contest your rights to work written entirely by you; rather, the intent is to exercise the right to control the distribution of derivative or collective works based on the Program.

In addition, mere aggregation of another work not based on the Program with the Program (or with a work based on the Program) on a volume of a storage or distribution medium does not bring the other work under the scope of this License.

3. You may copy and distribute the Program (or a work based on it, under Section 2) in object code or executable form under the terms of Sections 1 and 2 above provided that you also do one of the following:

- a) Accompany it with the complete corresponding machine-readable

source code, which must be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange; or,

b) Accompany it with a written offer, valid for at least three years, to give any third party, for a charge no more than your cost of physically performing source distribution, a complete machine-readable copy of the corresponding source code, to be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange; or,

c) Accompany it with the information you received as to the offer to distribute corresponding source code. (This alternative is allowed only for noncommercial distribution and only if you received the program in object code or executable form with such an offer, in accord with Subsection b above.)

The source code for a work means the preferred form of the work for making modifications to it. For an executable work, complete source code means all the source code for all modules it contains, plus any associated interface definition files, plus the scripts used to control compilation and installation of the executable. However, as a special exception, the source code distributed need not include anything that is normally distributed (in either source or binary form) with the major components (compiler, kernel, and so on) of the operating system on which the executable runs, unless that component itself accompanies the executable.

If distribution of executable or object code is made by offering access to copy from a designated place, then offering equivalent access to copy the source code from the same place counts as distribution of the source code, even though third parties are not compelled to copy the source along with the object code.

4. You may not copy, modify, sublicense, or distribute the Program except as expressly provided under this License. Any attempt otherwise to copy, modify, sublicense or distribute the Program is void, and will automatically terminate your rights under this License. However, parties who have received copies, or rights, from you under this License will not have their licenses terminated so long as such parties remain in full compliance.

5. You are not required to accept this License, since you have not signed it. However, nothing else grants you permission to modify or distribute the Program or its derivative works. These actions are prohibited by law if you do not accept this License. Therefore, by modifying or distributing the Program (or any work based on the

Program), you indicate your acceptance of this License to do so, and all its terms and conditions for copying, distributing or modifying the Program or works based on it.

6. Each time you redistribute the Program (or any work based on the Program), the recipient automatically receives a license from the original licensor to copy, distribute or modify the Program subject to these terms and conditions. You may not impose any further restrictions on the recipients' exercise of the rights granted herein. You are not responsible for enforcing compliance by third parties to this License.

7. If, as a consequence of a court judgment or allegation of patent infringement or for any other reason (not limited to patent issues), conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot distribute so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not distribute the Program at all. For example, if a patent license would not permit royalty-free redistribution of the Program by all those who receive copies directly or indirectly through you, then the only way you could satisfy both it and this License would be to refrain entirely from distribution of the Program.

If any portion of this section is held invalid or unenforceable under any particular circumstance, the balance of the section is intended to apply and the section as a whole is intended to apply in other circumstances.

It is not the purpose of this section to induce you to infringe any patents or other property right claims or to contest validity of any such claims; this section has the sole purpose of protecting the integrity of the free software distribution system, which is implemented by public license practices. Many people have made generous contributions to the wide range of software distributed through that system in reliance on consistent application of that system; it is up to the author/donor to decide if he or she is willing to distribute software through any other system and a licensee cannot impose that choice.

This section is intended to make thoroughly clear what is believed to be a consequence of the rest of this License.

8. If the distribution and/or use of the Program is restricted in

certain countries either by patents or by copyrighted interfaces, the original copyright holder who places the Program under this License may add an explicit geographical distribution limitation excluding those countries, so that distribution is permitted only in or among countries not thus excluded. In such case, this License incorporates the limitation as if written in the body of this License.

9. The Free Software Foundation may publish revised and/or new versions of the General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Program specifies a version number of this License which applies to it and "any later version", you have the option of following the terms and conditions either of that version or of any later version published by the Free Software Foundation. If the Program does not specify a version number of this License, you may choose any version ever published by the Free Software Foundation.

10. If you wish to incorporate parts of the Program into other free programs whose distribution conditions are different, write to the author to ask for permission. For software which is copyrighted by the Free Software Foundation, write to the Free Software Foundation; we sometimes make exceptions for this. Our decision will be guided by the two goals of preserving the free status of all derivatives of our free software and of promoting the sharing and reuse of software generally.

NO WARRANTY

11. BECAUSE THE PROGRAM IS LICENSED FREE OF CHARGE, THERE IS NO WARRANTY FOR THE PROGRAM, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE PROGRAM "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE PROGRAM IS WITH YOU. SHOULD THE PROGRAM PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

12. IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY AND/OR REDISTRIBUTE THE PROGRAM AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE PROGRAM (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY

YOU OR

THIRD PARTIES OR A FAILURE OF THE PROGRAM TO OPERATE WITH ANY OTHER PROGRAMS), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Programs

If you develop a new program, and you want it to be of the greatest possible use to the public, the best way to achieve this is to make it free software which everyone can redistribute and change under these terms.

To do so, attach the following notices to the program. It is safest to attach them to the start of each source file to most effectively convey the exclusion of warranty; and each file should have at least the "copyright" line and a pointer to where the full notice is found.

<one line to give the program's name and a brief idea of what it does.>

Copyright (C) <year> <name of author>

This program is free software; you can redistribute it and/or modify it under the terms of the GNU

General Public License as published by

the Free Software Foundation; either version 2 of the License, or (at your option) any later version.

This program is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details.

You should have received a copy of the GNU General Public License along with this program; if not, write to the Free Software Foundation, Inc., 51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA.

Also add information on how to contact you by electronic and paper mail.

If the program is interactive, make it output a short notice like this when it starts in an interactive mode:

Gnomovision version 69, Copyright (C) year name of author

Gnomovision comes with ABSOLUTELY NO WARRANTY; for details type `show w'.

This is free software, and you are welcome to redistribute

it

under certain conditions; type `show c' for details.

The hypothetical commands `show w' and `show c' should show the appropriate

parts of the General Public License. Of course, the commands you use may be called something other than `show w` and `show c`; they could even be mouse-clicks or menu items--whatever suits your program.

You should also get your employer (if you work as a programmer) or your school, if any, to sign a "copyright disclaimer" for the program, if necessary. Here is a sample; alter the names:

Yoyodyne, Inc., hereby disclaims all copyright interest in the program
`Gnomovision' (which makes passes at compilers) written by James Hacker.

<signature of Ty Coon>, 1 April 1989
Ty Coon, President of Vice

This General Public License does not permit incorporating your program into proprietary programs. If your program is a subroutine library, you may consider it more useful to permit linking proprietary applications with the library. If this is what you want to do, use the GNU Lesser General Public License instead of this License.
BSD License

For Zstandard software

Copyright (c) 2016-present, Facebook, Inc. All rights reserved.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

- * Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.
- * Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.
- * Neither the name Facebook nor the names of its contributors may be used to endorse or promote products derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED.

IN NO EVENT SHALL THE COPYRIGHT HOLDER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON

ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

1.57 audit 1:2.8.2-1ubuntu1.1

1.57.1 Available under license :

GNU LESSER GENERAL PUBLIC LICENSE

Version 2.1, February 1999

Copyright (C) 1991, 1999 Free Software Foundation, Inc.

51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA

Everyone is permitted to copy and distribute verbatim copies of this license document, but changing it is not allowed.

[This is the first released version of the Lesser GPL. It also counts as the successor of the GNU Library Public License, version 2, hence the version number 2.1.]

Preamble

The licenses for most software are designed to take away your freedom to share and change it. By contrast, the GNU General Public Licenses are intended to guarantee your freedom to share and change free software--to make sure the software is free for all its users.

This license, the Lesser General Public License, applies to some specially designated software packages--typically libraries--of the Free Software Foundation and other authors who decide to use it. You can use it too, but we suggest you first think carefully about whether this license or the ordinary General Public License is the better strategy to use in any particular case, based on the explanations below.

When we speak of free software, we are referring to freedom of use, not price. Our General Public Licenses are designed to make sure that you have the freedom to distribute copies of free software (and charge for this service if you wish); that you receive source code or can get it if you want it; that you can change the software and use pieces of it in new free programs; and that you are informed that you can do these things.

To protect your rights, we need to make restrictions that forbid distributors to deny you these rights or to ask you to surrender these rights. These restrictions translate to certain responsibilities for

you if you distribute copies of the library or if you modify it.

For example, if you distribute copies of the library, whether gratis or for a fee, you must give the recipients all the rights that we gave you. You must make sure that they, too, receive or can get the source code. If you link other code with the library, you must provide complete object files to the recipients, so that they can relink them with the library after making changes to the library and recompiling it. And you must show them these terms so they know their rights.

We protect your rights with a two-step method: (1) we copyright the library, and (2) we offer you this license, which gives you legal permission to copy, distribute and/or modify the library.

To protect each distributor, we want to make it very clear that there is no warranty for the free library. Also, if the library is modified by someone else and passed on, the recipients should know that what they have is not the original version, so that the original author's reputation will not be affected by problems that might be introduced by others.

^L

Finally, software patents pose a constant threat to the existence of any free program. We wish to make sure that a company cannot effectively restrict the users of a free program by obtaining a restrictive license from a patent holder. Therefore, we insist that any patent license obtained for a version of the library must be consistent with the full freedom of use specified in this license.

Most GNU software, including some libraries, is covered by the ordinary GNU General Public License. This license, the GNU Lesser General Public License, applies to certain designated libraries, and is quite different from the ordinary General Public License. We use this license for certain libraries in order to permit linking those libraries into non-free programs.

When a program is linked with a library, whether statically or using a shared library, the combination of the two is legally speaking a combined work, a derivative of the original library. The ordinary General Public License therefore permits such linking only if the entire combination fits its criteria of freedom. The Lesser General Public License permits more lax criteria for linking other code with the library.

We call this license the "Lesser" General Public License because it does Less to protect the user's freedom than the ordinary General

Public License. It also provides other free software developers Less of an advantage over competing non-free programs. These disadvantages are the reason we use the ordinary General Public License for many libraries. However, the Lesser license provides advantages in certain special circumstances.

For example, on rare occasions, there may be a special need to encourage the widest possible use of a certain library, so that it becomes a de-facto standard. To achieve this, non-free programs must be allowed to use the library. A more frequent case is that a free library does the same job as widely used non-free libraries. In this case, there is little to gain by limiting the free library to free software only, so we use the Lesser General Public License.

In other cases, permission to use a particular library in non-free programs enables a greater number of people to use a large body of free software. For example, permission to use the GNU C Library in non-free programs enables many more people to use the whole GNU operating system, as well as its variant, the GNU/Linux operating system.

Although the Lesser General Public License is Less protective of the users' freedom, it does ensure that the user of a program that is linked with the Library has the freedom and the wherewithal to run that program using a modified version of the Library.

The precise terms and conditions for copying, distribution and modification follow. Pay close attention to the difference between a "work based on the library" and a "work that uses the library". The former contains code derived from the library, whereas the latter must be combined with the library in order to run.

^L

GNU LESSER GENERAL PUBLIC LICENSE TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

0. This License Agreement applies to any software library or other program which contains a notice placed by the copyright holder or other authorized party saying it may be distributed under the terms of this Lesser General Public License (also called "this License"). Each licensee is addressed as "you".

A "library" means a collection of software functions and/or data prepared so as to be conveniently linked with application programs (which use some of those functions and data) to form executables.

The "Library", below, refers to any such software library or work which has been distributed under these terms. A "work based on the Library" means either the Library or any derivative work under copyright law: that is to say, a work containing the Library or a portion of it, either verbatim or with modifications and/or translated straightforwardly into another language. (Hereinafter, translation is included without limitation in the term "modification".)

"Source code" for a work means the preferred form of the work for making modifications to it. For a library, complete source code means all the source code for all modules it contains, plus any associated interface definition files, plus the scripts used to control compilation and installation of the library.

Activities other than copying, distribution and modification are not covered by this License; they are outside its scope. The act of running a program using the Library is not restricted, and output from such a program is covered only if its contents constitute a work based on the Library (independent of the use of the Library in a tool for writing it). Whether that is true depends on what the Library does and what the program that uses the Library does.

1. You may copy and distribute verbatim copies of the Library's complete source code as you receive it, in any medium, provided that you conspicuously and appropriately publish on each copy an appropriate copyright notice and disclaimer of warranty; keep intact all the notices that refer to this License and to the absence of any warranty; and distribute a copy of this License along with the Library.

You may charge a fee for the physical act of transferring a copy, and you may at your option offer warranty protection in exchange for a fee.

2. You may modify your copy or copies of the Library or any portion of it, thus forming a work based on the Library, and copy and distribute such modifications or work under the terms of Section 1 above, provided that you also meet all of these conditions:

- a) The modified work must itself be a software library.
- b) You must cause the files modified to carry prominent notices stating that you changed the files and the date of any change.
- c) You must cause the whole of the work to be licensed at no

charge to all third parties under the terms of this License.

d) If a facility in the modified Library refers to a function or a table of data to be supplied by an application program that uses the facility, other than as an argument passed when the facility is invoked, then you must make a good faith effort to ensure that, in the event an application does not supply such function or table, the facility still operates, and performs whatever part of its purpose remains meaningful.

(For example, a function in a library to compute square roots has a purpose that is entirely well-defined independent of the application. Therefore, Subsection 2d requires that any application-supplied function or table used by this function must be optional: if the application does not supply it, the square root function must still compute square roots.)

These requirements apply to the modified work as a whole. If identifiable sections of that work are not derived from the Library, and can be reasonably considered independent and separate works in themselves, then this License, and its terms, do not apply to those sections when you distribute them as separate works. But when you distribute the same sections as part of a whole which is a work based on the Library, the distribution of the whole must be on the terms of this License, whose permissions for other licensees extend to the entire whole, and thus to each and every part regardless of who wrote it.

Thus, it is not the intent of this section to claim rights or contest your rights to work written entirely by you; rather, the intent is to exercise the right to control the distribution of derivative or collective works based on the Library.

In addition, mere aggregation of another work not based on the Library with the Library (or with a work based on the Library) on a volume of a storage or distribution medium does not bring the other work under the scope of this License.

3. You may opt to apply the terms of the ordinary GNU General Public License instead of this License to a given copy of the Library. To do this, you must alter all the notices that refer to this License, so that they refer to the ordinary GNU General Public License, version 2, instead of to this License. (If a newer version than version 2 of the ordinary GNU General Public License has appeared, then you can specify that version instead if you wish.) Do not make any other change in

these notices.

^L

Once this change is made in a given copy, it is irreversible for that copy, so the ordinary GNU General Public License applies to all subsequent copies and derivative works made from that copy.

This option is useful when you wish to copy part of the code of the Library into a program that is not a library.

4. You may copy and distribute the Library (or a portion or derivative of it, under Section 2) in object code or executable form under the terms of Sections 1 and 2 above provided that you accompany it with the

complete corresponding machine-readable source code, which must be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange.

If distribution of object code is made by offering access to copy from a designated place, then offering equivalent access to copy the source code from the same place satisfies the requirement to distribute the source code, even though third parties are not compelled to copy the source along with the object code.

5. A program that contains no derivative of any portion of the Library, but is designed to work with the Library by being compiled or linked with it, is called a "work that uses the Library". Such a work, in isolation, is not a derivative work of the Library, and therefore falls outside the scope of this License.

However, linking a "work that uses the Library" with the Library creates an executable that is a derivative of the Library (because it contains portions of the Library), rather than a "work that uses the library". The executable is therefore covered by this License. Section 6 states terms for distribution of such executables.

When a "work that uses the Library" uses material from a header file that is part of the Library, the object code for the work may be a derivative work of the Library even though the source code is not. Whether this is true is especially significant if the work can be linked without the Library, or if the work is itself a library. The threshold for this to be true is not precisely defined by law.

If such an object file uses only numerical parameters, data structure layouts and accessors, and small macros and small inline functions (ten lines or less in length), then the use of the object file is unrestricted, regardless of whether it is legally a derivative work. (Executables containing this object code plus portions of the

Library will still fall under Section 6.)

Otherwise, if the work is a derivative of the Library, you may distribute

the object code for the work under the terms of Section 6.

Any executables containing that work also fall under Section 6, whether or not they are linked directly with the Library itself.

^L

6. As an exception to the Sections above, you may also combine or link a "work that uses the Library" with the Library to produce a work containing portions of the Library, and distribute that work under terms of your choice, provided that the terms permit modification of the work for the customer's own use and reverse engineering for debugging such modifications.

You must give prominent notice with each copy of the work that the Library is used in it and that the Library and its use are covered by this License. You must supply a copy of this License. If the work during execution displays copyright notices, you must include the copyright notice for the Library among them, as well as a reference directing the user to the copy of this License. Also, you must do one of these things:

a) Accompany the work with the complete corresponding machine-readable source code for the Library including whatever changes were used in the work (which must be distributed under Sections 1 and 2 above); and, if the work is an executable linked with the Library, with the complete machine-readable "work that uses the Library", as object code and/or source code, so that the user can modify the Library and then relink to produce a modified executable containing the modified Library. (It is understood that the user who changes the contents of definitions files in the Library will not necessarily be able to recompile the application to use the modified definitions.)

b) Use a suitable shared library mechanism for linking with the Library. A suitable mechanism is one that (1) uses at run time a copy of the library already present on the user's computer system, rather than copying library functions into the executable, and (2)

will operate properly with a modified version of the library, if the user installs one, as long as the modified version is interface-compatible with the version that the work was made with.

c) Accompany the work with a written offer, valid for at least three years, to give the same user the materials specified in Subsection 6a, above, for a charge no more

than the cost of performing this distribution.

d) If distribution of the work is made by offering access to copy from a designated place, offer equivalent access to copy the above specified materials from the same place.

e) Verify that the user has already received a copy of these materials or that you have already sent this user a copy.

For an executable, the required form of the "work that uses the Library" must include any data and utility programs needed for reproducing the executable from it. However, as a special exception, the materials to be distributed need not include anything that is normally distributed (in either source or binary form) with the major components (compiler, kernel, and so on) of the operating system on which the executable runs, unless that component itself accompanies the executable.

It may happen that this requirement contradicts the license restrictions of other proprietary libraries that do not normally accompany the operating system. Such a contradiction means you cannot use both them and the Library together in an executable that you distribute.

^L

7. You may place library facilities that are a work based on the Library side-by-side in a single library together with other library facilities not covered by this License, and distribute such a combined library, provided that the separate distribution of the work based on the Library and of the other library facilities is otherwise permitted, and provided that you do these two things:

a) Accompany the combined library with a copy of the same work based on the Library, uncombined

with any other library

facilities. This must be distributed under the terms of the Sections above.

b) Give prominent notice with the combined library of the fact that part of it is a work based on the Library, and explaining where to find the accompanying uncombined form of the same work.

8. You may not copy, modify, sublicense, link with, or distribute the Library except as expressly provided under this License. Any attempt otherwise to copy, modify, sublicense, link with, or distribute the Library is void, and will automatically terminate your rights under this License. However, parties who have received copies, or rights, from you under this License will not have their licenses

terminated so long as such parties remain in full compliance.

9. You are not required to accept this License, since you have not signed it. However, nothing else grants you permission to modify or distribute the Library or its derivative works. These actions are prohibited

by law if you do not accept this License. Therefore, by modifying or distributing the Library (or any work based on the Library), you indicate your acceptance of this License to do so, and all its terms and conditions for copying, distributing or modifying the Library or works based on it.

10. Each time you redistribute the Library (or any work based on the Library), the recipient automatically receives a license from the original licensor to copy, distribute, link with or modify the Library subject to these terms and conditions. You may not impose any further restrictions on the recipients' exercise of the rights granted herein. You are not responsible for enforcing compliance by third parties with this License.

^L

11. If, as a consequence of a court judgment or allegation of patent infringement or for any other reason (not limited to patent issues), conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot distribute so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not distribute the Library at all. For example, if a patent license would not permit royalty-free redistribution of the Library by all those who receive copies directly or indirectly through you, then the only way you could satisfy both it and this License would be to refrain entirely from distribution of the Library.

If any portion of this section is held invalid or unenforceable under any particular circumstance, the balance of the section is intended to apply, and the section as a whole is intended to apply in other circumstances.

It is not the purpose of this section to induce you to infringe any patents or other property right claims or to contest validity of any such claims; this section has the sole purpose of protecting the integrity of the free software distribution system which is implemented by public license practices. Many people have made generous contributions to the wide range of software distributed through that system in reliance on consistent application of that system; it is up to the author/donor to decide if he or she is willing

to distribute software through any other system and a licensee cannot impose that choice.

This section is intended to make thoroughly clear what is believed to be a consequence of the rest of this License.

12. If the distribution and/or use of the Library is restricted in certain countries either by patents or by copyrighted interfaces, the original copyright holder who places the Library under this License may add an explicit geographical distribution limitation excluding those countries, so that distribution is permitted only in or among countries not thus excluded. In such case, this License incorporates the limitation as if written in the body of this License.

13. The Free Software Foundation may publish revised and/or new versions of the Lesser General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Library specifies a version number of this License which applies to it and "any later version", you have the option of following the terms and conditions either of that version or of any later version published by the Free Software Foundation. If the Library does not specify a license version number, you may choose any version ever published by the Free Software Foundation.

^L

14. If you wish to incorporate parts of the Library into other free programs whose distribution conditions are incompatible with these, write to the author to ask for permission. For software which is copyrighted by the Free Software Foundation, write to the Free Software Foundation; we sometimes make exceptions for this. Our decision will be guided by the two goals of preserving the free status of all derivatives of our free software and of promoting the sharing and reuse of software generally.

NO WARRANTY

15. BECAUSE THE LIBRARY IS LICENSED FREE OF CHARGE, THERE IS NO WARRANTY FOR THE LIBRARY, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE LIBRARY "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE LIBRARY IS WITH YOU. SHOULD THE LIBRARY PROVE DEFECTIVE, YOU ASSUME

THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

16. IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY AND/OR REDISTRIBUTE THE LIBRARY AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE LIBRARY (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE LIBRARY TO OPERATE WITH ANY OTHER SOFTWARE), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

END OF TERMS AND CONDITIONS

^L

How to Apply These Terms to Your New Libraries

If you develop a new library, and you want it to be of the greatest possible use to the public, we recommend making it free software that everyone can redistribute and change. You can do so by permitting redistribution under these terms (or, alternatively, under the terms of the ordinary General Public License).

To apply these terms, attach the following notices to the library.

It is safest to attach them to the start of each source file to most

effectively convey the exclusion of warranty; and each file should have at least the "copyright" line and a pointer to where the full notice is found.

<one line to give the library's name and a brief idea of what it does.>

Copyright (C) <year> <name of author>

This library is free software; you can redistribute it and/or modify it under the terms of the GNU Lesser General Public License as published by the Free Software Foundation; either version 2 of the License, or (at your option) any later version.

This library is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU Lesser General Public License for more details.

You should have received a copy of the GNU Lesser General Public License along with this library; if not, write to the Free Software

Foundation, Inc., 51 Franklin Street, Fifth Floor,
Boston, MA 02110-1301 USA

Also add information on how to contact you by electronic and paper mail.

You should also get your employer (if you work as a programmer) or your school, if any, to sign a "copyright disclaimer" for the library, if necessary. Here is a sample; alter the names:

Yoyodyne, Inc., hereby disclaims all copyright interest in the library `Frob' (a library for tweaking knobs) written by James Random Hacker.

<signature of Ty Coon>, 1 April 1990
Ty Coon, President of Vice

That's all there is to it!

GNU GENERAL PUBLIC LICENSE
Version 2, June 1991

Copyright (C) 1989, 1991 Free Software Foundation, Inc.
59 Temple Place, Suite 330, Boston, MA 02111-1307 USA
Everyone is permitted to copy and distribute verbatim copies of this license document, but changing it is not allowed.

Preamble

The licenses for most software are designed to take away your freedom to share and change it. By contrast, the GNU General Public License is intended to guarantee your freedom to share and change free software--to make sure the software is free for all its users. This General Public License applies to most of the Free Software Foundation's software and to any other program whose authors commit to using it. (Some other Free Software Foundation software is covered by the GNU Library General Public License instead.) You can apply it to your programs, too.

When we speak of free software, we are referring to freedom, not price. Our General Public Licenses are designed to make sure that you have the freedom to distribute copies of free software (and charge for this service if you wish), that you receive source code or can get it if you want it, that you can change the software or use pieces of it in new free programs; and that you know you can do these things.

To protect your rights, we need to make restrictions that forbid

anyone to deny you these rights or to ask you to surrender the rights. These restrictions translate to certain responsibilities for you if you distribute copies of the software, or if you modify it.

For example, if you distribute copies of such a program, whether gratis or for a fee, you must give the recipients all the rights that you have. You must make sure that they, too, receive or can get the source code. And you must show them these terms so they know their rights.

We protect your rights with two steps: (1) copyright the software, and (2) offer you this license which gives you legal permission to copy, distribute and/or modify the software.

Also, for each author's protection and ours, we want to make certain that everyone understands that there is no warranty for this free software. If the software is modified by someone else and passed on, we want its recipients to know that what they have is not the original, so that any problems introduced by others will not reflect on the original authors' reputations.

Finally, any free program is threatened constantly by software patents. We wish to avoid the danger that redistributors of a free program will individually obtain patent licenses, in effect making the program proprietary. To prevent this, we have made it clear that any patent must be licensed for everyone's free use or not licensed at all.

The precise terms and conditions for copying, distribution and modification follow.

GNU GENERAL PUBLIC LICENSE TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

0. This License applies to any program or other work which contains a notice placed by the copyright holder saying it may be distributed under the terms of this General Public License. The "Program", below, refers to any such program or work, and a "work based on the Program" means either the Program or any derivative work under copyright law: that is to say, a work containing the Program or a portion of it, either verbatim or with modifications and/or translated into another language. (Hereinafter, translation is included without limitation in the term "modification".) Each licensee is addressed as "you".

Activities other than copying, distribution and modification are not covered by this License; they are outside its scope. The act of running the Program is not restricted, and the output from the Program

is covered only if its contents constitute a work based on the Program (independent of having been made by running the Program). Whether that is true depends on what the Program does.

1. You may copy and distribute verbatim copies of the Program's source code as you receive it, in any medium, provided that you conspicuously and appropriately publish on each copy an appropriate copyright notice and disclaimer of warranty; keep intact all the notices that refer to this License and to the absence of any warranty; and give any other recipients of the Program a copy of this License along with the Program.

You may charge a fee for the physical act of transferring a copy, and you may at your option offer warranty protection in exchange for a fee.

2. You may modify your copy or copies of the Program or any portion of it, thus forming a work based on the Program, and copy and distribute such modifications or work under the terms of Section 1 above, provided that you also meet all of these conditions:

a) You must cause the modified files to carry prominent notices stating that you changed the files and the date of any change.

b) You must cause any work that you distribute or publish, that in whole or in part contains or is derived from the Program or any part thereof, to be licensed as a whole at no charge to all third parties under the terms of this License.

c) If the modified program normally reads commands interactively when run, you must cause it, when started running for such interactive use in the most ordinary way, to print or display an announcement including an appropriate copyright notice and a notice that there is no warranty (or else, saying that you provide a warranty) and that users may redistribute the program under these conditions, and telling the user how to view a copy of this License. (Exception: if the Program itself is interactive but does not normally print such an announcement, your work based on the Program is not required to print an announcement.)

These requirements apply to the modified work as a whole. If identifiable sections of that work are not derived from the Program, and can be reasonably considered independent and separate works in themselves, then this License, and its terms, do not apply to those sections when you distribute them as separate works. But when you distribute the same sections as part of a whole which is a work based

on the Program, the distribution of the whole must be on the terms of this License, whose permissions for other licensees extend to the entire whole, and thus to each and every part regardless of who wrote it.

Thus, it is not the intent of this section to claim rights or contest your rights to work written entirely by you; rather, the intent is to exercise the right to control the distribution of derivative or collective works based on the Program.

In addition, mere aggregation of another work not based on the Program with the Program (or with a work based on the Program) on a volume of a storage or distribution medium does not bring the other work under the scope of this License.

3. You may copy and distribute the Program (or a work based on it, under Section 2) in object code or executable form under the terms of Sections 1 and 2 above provided that you also do one of the following:

a) Accompany it with the complete corresponding machine-readable source code, which must be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange; or,

b) Accompany it with a written offer, valid for at least three years, to give any third party, for a charge no more than your cost of physically performing source distribution, a complete machine-readable copy of the corresponding source code, to be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange; or,

c) Accompany it with the information you received as to the offer to distribute corresponding source code. (This alternative is allowed only for noncommercial distribution and only if you received the program in object code or executable form with such an offer, in accord with Subsection b above.)

The source code for a work means the preferred form of the work for making modifications to it. For an executable work, complete source code means all the source code for all modules it contains, plus any associated interface definition files, plus the scripts used to control compilation and installation of the executable. However, as a special exception, the source code distributed need not include anything that is normally distributed (in either source or binary form) with the major components (compiler, kernel, and so on) of the operating system on which the executable runs, unless that component itself accompanies the executable.

If distribution of executable or object code is made by offering access to copy from a designated place, then offering equivalent access to copy the source code from the same place counts as distribution of the source code, even though third parties are not compelled to copy the source along with the object code.

4. You may not copy, modify, sublicense, or distribute the Program except as expressly provided under this License. Any attempt otherwise to copy, modify, sublicense or distribute the Program is void, and will automatically terminate your rights under this License. However, parties who have received copies, or rights, from you under this License will not have their licenses terminated so long as such parties remain in full compliance.

5. You are not required to accept this License, since you have not signed it. However, nothing else grants you permission to modify or distribute the Program or its derivative works. These actions are prohibited by law if you do not accept this License. Therefore, by modifying or distributing the Program (or any work based on the Program), you indicate your acceptance of this License to do so, and all its terms and conditions for copying, distributing or modifying the Program or works based on it.

6. Each time you redistribute the Program (or any work based on the Program), the recipient automatically receives a license from the original licensor to copy, distribute or modify the Program subject to these terms and conditions. You may not impose any further restrictions on the recipients' exercise of the rights granted herein. You are not responsible for enforcing compliance by third parties to this License.

7. If, as a consequence of a court judgment or allegation of patent infringement or for any other reason (not limited to patent issues), conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot distribute so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not distribute the Program at all. For example, if a patent license would not permit royalty-free redistribution of the Program by all those who receive copies directly or indirectly through you, then the only way you could satisfy both it and this License would be to refrain entirely from distribution of the Program.

If any portion of this section is held invalid or unenforceable under

any particular circumstance, the balance of the section is intended to apply and the section as a whole is intended to apply in other circumstances.

It is not the purpose of this section to induce you to infringe any patents or other property right claims or to contest validity of any such claims; this section has the sole purpose of protecting the integrity of the free software distribution system, which is implemented by public license practices. Many people have made generous contributions to the wide range of software distributed through that system in reliance on consistent application of that system; it is up to the author/donor to decide if he or she is willing to distribute software through any other system and a licensee cannot impose that choice.

This section is intended to make thoroughly clear what is believed to be a consequence of the rest of this License.

8. If the distribution and/or use of the Program is restricted in certain countries either by patents or by copyrighted interfaces, the original copyright holder who places the Program under this License may add an explicit geographical distribution limitation excluding those countries, so that distribution is permitted only in or among countries not thus excluded. In such case, this License incorporates the limitation as if written in the body of this License.

9. The Free Software Foundation may publish revised and/or new versions of the General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Program specifies a version number of this License which applies to it and "any later version", you have the option of following the terms and conditions either of that version or of any later version published by the Free Software Foundation. If the Program does not specify a version number of this License, you may choose any version ever published by the Free Software Foundation.

10. If you wish to incorporate parts of the Program into other free programs whose distribution conditions are different, write to the author to ask for permission. For software which is copyrighted by the Free Software Foundation, write to the Free Software Foundation; we sometimes make exceptions for this. Our decision will be guided by the two goals of preserving the free status of all derivatives of our free software and of promoting the sharing and reuse of software generally.

NO WARRANTY

11. BECAUSE THE PROGRAM IS LICENSED FREE OF CHARGE, THERE IS NO WARRANTY FOR THE PROGRAM, TO THE EXTENT PERMITTED BY APPLICABLE LAW.

EXCEPT WHEN

OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE PROGRAM "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE PROGRAM IS WITH YOU. SHOULD THE PROGRAM PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

12. IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY AND/OR REDISTRIBUTE THE PROGRAM AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE PROGRAM (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE PROGRAM TO OPERATE WITH ANY OTHER PROGRAMS), EVEN

IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Programs

If you develop a new program, and you want it to be of the greatest possible use to the public, the best way to achieve this is to make it free software which everyone can redistribute and change under these terms.

To do so, attach the following notices to the program. It is safest to attach them to the start of each source file to most effectively convey the exclusion of warranty; and each file should have at least the "copyright" line and a pointer to where the full notice is found.

<one line to give the program's name and a brief idea of what it does.>

Copyright (C) <year> <name of author>

This program is free software; you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation; either version 2 of the License,

or

(at your option) any later version.

This program is distributed in the hope that it will be useful,

but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details.

You should have received a copy of the GNU General Public License along with this program; if not, write to the Free Software Foundation, Inc., 59 Temple Place, Suite 330, Boston, MA 02111-1307 USA

Also add information on how to contact you by electronic and paper mail.

If the program is interactive, make it output a short notice like this when it starts in an interactive mode:

```
Gnomovision version 69, Copyright (C) year name of author
Gnomovision comes with ABSOLUTELY NO WARRANTY; for details type `show w'.
This is free software, and you are welcome to redistribute it
under certain conditions; type `show c' for details.
```

The hypothetical commands `show w' and `show c' should show the appropriate parts of the General Public License. Of course, the commands you use may be called something other than `show w' and `show c'; they could even be mouse-clicks or menu items--whatever suits your program.

You should also get your employer (if you work as a programmer) or your school, if any, to sign a "copyright disclaimer" for the program, if necessary. Here is a sample; alter the names:

```
Yoyodyne, Inc., hereby disclaims all copyright interest in the program
`Gnomovision' (which makes passes at compilers) written by James Hacker.
```

```
<signature of Ty Coon>, 1 April 1989
Ty Coon, President of Vice
```

This General Public License does not permit incorporating your program into proprietary programs. If your program is a subroutine library, you may consider it more useful to permit linking proprietary applications with the library. If this is what you want to do, use the GNU Library General Public License instead of this License.

1.58 Iz4 0.0~r131-2ubuntu3.1

1.58.1 Available under license :

GNU GENERAL PUBLIC LICENSE
Version 2, June 1991

Copyright (C) 1989, 1991 Free Software Foundation, Inc.,
51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA
Everyone is permitted to copy and distribute verbatim copies
of this license document, but changing it is not allowed.

Preamble

The licenses for most software are designed to take away your freedom to share and change it. By contrast, the GNU General Public License is intended to guarantee your freedom to share and change free software--to make sure the software is free for all its users. This General Public License applies to most of the Free Software Foundation's software and to any other program whose authors commit to using it. (Some other Free Software Foundation software is covered by the GNU Lesser General Public License instead.) You can apply it to your programs, too.

When we speak of free software, we are referring to freedom, not price.

Our General Public Licenses are designed to make sure that you have the freedom to distribute copies of free software (and charge for this service if you wish), that you receive source code or can get it if you want it, that you can change the software or use pieces of it in new free programs; and that you know you can do these things.

To protect your rights, we need to make restrictions that forbid anyone to deny you these rights or to ask you to surrender the rights. These restrictions translate to certain responsibilities for you if you distribute copies of the software, or if you modify it.

For example, if you distribute copies of such a program, whether gratis or for a fee, you must give the recipients all the rights that you have. You must make sure that they, too, receive or can get the source code. And you must show them these terms so they know their rights.

We protect your rights with two steps: (1) copyright the software, and (2) offer you this license which gives you legal permission to copy, distribute and/or modify the software.

Also, for each author's protection and ours, we want to make certain that everyone understands that there is no warranty for this free software. If the software is modified by someone else and passed on, we want its recipients to know that what they have is not the original, so that any problems introduced by others will not reflect on the original authors' reputations.

Finally, any free program is threatened constantly by software patents. We wish to avoid the danger that redistributors of a free program will individually obtain patent licenses, in effect making the program proprietary. To prevent this, we have made it clear that any patent must be licensed for everyone's free use or not licensed at all.

The precise terms and conditions for copying, distribution and modification follow.

GNU GENERAL PUBLIC LICENSE TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

0. This License applies to any program or other work which contains a notice placed by the copyright holder saying it may be distributed under the terms of this General Public License. The "Program", below, refers to any such program or work, and a "work based on the Program" means either the Program or any derivative work under copyright law: that is to say, a work containing the Program or a portion of it, either verbatim or with modifications and/or translated into another language. (Hereinafter, translation is included without limitation in the term "modification".) Each licensee is addressed as "you".

Activities other than copying, distribution and modification are not covered by this License; they are outside its scope. The act of running the Program is not restricted, and the output from the Program is covered only if its contents constitute a work based on the Program (independent of having been made by running the Program). Whether that is true depends on what the Program does.

1. You may copy and distribute verbatim copies of the Program's source code as you receive it, in any medium, provided that you conspicuously and appropriately publish on each copy an appropriate copyright notice and disclaimer of warranty; keep intact all the notices that refer to this License and to the absence of any warranty; and give any other recipients of the Program a copy of this License along with the Program.

You may charge a fee for the physical act of transferring a copy, and you may at your option offer warranty protection in exchange for a fee.

2. You may modify your copy or copies of the Program or any portion of it, thus forming a work based on the Program, and copy and distribute such modifications or work under the terms of Section 1 above, provided that you also meet all of these conditions:

- a) You must cause the modified files to carry prominent notices stating that you changed the files and the date of any change.

- b) You must cause any work that you distribute or publish, that in whole or in part contains or is derived from the Program or any part thereof, to be licensed as a whole at no charge to all third parties under the terms of this License.

- c) If the modified program normally reads commands interactively when run, you must cause it, when started running for such interactive use in the most ordinary way, to print or display an announcement including an appropriate copyright notice and a notice that there is no warranty (or else, saying that you provide a warranty) and that users may redistribute the program under these conditions, and telling the user how to view a copy of this License. (Exception: if the Program itself is interactive but does not normally print such an announcement, your work based on the Program is not required to print an announcement.)

These requirements apply to the modified work as a whole. If identifiable sections of that work are not derived from the Program, and can be reasonably considered independent and separate works in themselves, then this License, and its terms, do not apply to those sections when you distribute them as separate works. But when you distribute the same sections as part of a whole which is a work based on the Program, the distribution of the whole must be on the terms of this License, whose permissions for other licensees extend to the entire whole, and thus to each and every part regardless of who wrote it.

Thus, it is not the intent of this section to claim rights or contest your rights to work written entirely by you; rather, the intent is to exercise the right to control the distribution of derivative or collective works based on the Program.

In addition, mere aggregation of another work not based on the Program with the Program (or with a work based on the Program) on a volume of a storage or distribution medium does not bring the other work under the scope of this License.

3. You may copy and distribute the Program (or a work based on it, under Section 2) in object code or executable form under the terms of Sections 1 and 2 above provided that you also do one of the following:

- a) Accompany it with the complete corresponding machine-readable source code, which must be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange; or,

- b) Accompany it with a written offer, valid for at least three

years, to give any third party, for a charge no more than your cost of physically performing source distribution, a complete machine-readable copy of the corresponding source code, to be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange; or,

c) Accompany it with the information you received as to the offer to distribute corresponding source code. (This alternative is allowed only for noncommercial distribution and only if you received the program in object code or executable form with such an offer, in accord with Subsection b above.)

The source code for a work means the preferred form of the work for making modifications to it. For an executable work, complete source code means all the source code for all modules it contains, plus any associated interface definition files, plus the scripts used to control compilation and installation of the executable. However, as a special exception, the source code distributed need not include anything that is normally distributed (in either source or binary form) with the major components (compiler, kernel, and so on) of the operating system on which the executable runs, unless that component itself accompanies the executable.

If distribution of executable or object code is made by offering access to copy from a designated place, then offering equivalent access to copy the source code from the same place counts as distribution of the source code, even though third parties are not compelled to copy the source along with the object code.

4. You may not copy, modify, sublicense, or distribute the Program except as expressly provided under this License. Any attempt otherwise to copy, modify, sublicense or distribute the Program is void, and will automatically terminate your rights under this License. However, parties who have received copies, or rights, from you under this License will not have their licenses terminated so long as such parties remain in full compliance.

5. You are not required to accept this License, since you have not signed it. However, nothing else grants you permission to modify or distribute the Program or its derivative works. These actions are prohibited by law if you do not accept this License. Therefore, by modifying or distributing the Program (or any work based on the Program), you indicate your acceptance of this License to do so, and all its terms and conditions for copying, distributing or modifying the Program or works based on it.

6. Each time you redistribute the Program (or any work based on the Program), the recipient automatically receives a license from the original licensor to copy, distribute or modify the Program subject to these terms and conditions. You may not impose any further restrictions on the recipients' exercise of the rights granted herein. You are not responsible for enforcing compliance by third parties to this License.

7. If, as a consequence of a court judgment or allegation of patent infringement or for any other reason (not limited to patent issues), conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot distribute so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not distribute the Program at all. For example, if a patent license would not permit royalty-free redistribution of the Program by all those who receive copies directly or indirectly through you, then the only way you could satisfy both it and this License would be to refrain entirely from distribution of the Program.

If any portion of this section is held invalid or unenforceable under any particular circumstance, the balance of the section is intended to apply and the section as a whole is intended to apply in other circumstances.

It is not the purpose of this section to induce you to infringe any patents or other property right claims or to contest validity of any such claims; this section has the sole purpose of protecting the integrity of the free software distribution system, which is implemented by public license practices. Many people have made generous contributions to the wide range of software distributed through that system in reliance on consistent application of that system; it is up to the author/donor to decide if he or she is willing to distribute software through any other system and a licensee cannot impose that choice.

This section is intended to make thoroughly clear what is believed to be a consequence of the rest of this License.

8. If the distribution and/or use of the Program is restricted in certain countries either by patents or by copyrighted interfaces, the original copyright holder who places the Program under this License may add an explicit geographical distribution limitation excluding those countries, so that distribution is permitted only in or among

countries not thus excluded. In such case, this License incorporates the limitation as if written in the body of this License.

9. The Free Software Foundation may publish revised and/or new versions of the General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Program specifies a version number of this License which applies to it and "any later version", you have the option of following the terms and conditions either of that version or of any later version published by the Free Software Foundation. If the Program does not specify a version number of this License, you may choose any version ever published by the Free Software Foundation.

10. If you wish to incorporate parts of the Program into other free programs whose distribution conditions are different, write to the author to ask for permission. For software which is copyrighted by the Free Software Foundation, write to the Free Software Foundation; we sometimes make exceptions for this. Our decision will be guided by the two goals of preserving the free status of all derivatives of our free software and of promoting the sharing and reuse of software generally.

NO WARRANTY

11. BECAUSE THE PROGRAM IS LICENSED FREE OF CHARGE, THERE IS NO WARRANTY FOR THE PROGRAM, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE PROGRAM "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE PROGRAM IS WITH YOU. SHOULD THE PROGRAM PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

12. IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY AND/OR REDISTRIBUTE THE PROGRAM AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE PROGRAM (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE PROGRAM TO OPERATE WITH ANY OTHER PROGRAMS), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Programs

If you develop a new program, and you want it to be of the greatest possible use to the public, the best way to achieve this is to make it free software which everyone can redistribute and change under these terms.

To do so, attach the following notices to the program. It is safest to attach them to the start of each source file to most effectively convey the exclusion of warranty; and each file should have at least the "copyright" line and a pointer to where the full notice is found.

```
<one line to give the program's name and a brief idea of what it does.>  
Copyright (C) <year> <name of author>
```

```
This program is free software; you can redistribute it and/or modify  
it under the terms of the GNU  
General Public License as published by  
the Free Software Foundation; either version 2 of the License, or  
(at your option) any later version.
```

```
This program is distributed in the hope that it will be useful,  
but WITHOUT ANY WARRANTY; without even the implied warranty of  
MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the  
GNU General Public License for more details.
```

```
You should have received a copy of the GNU General Public License along  
with this program; if not, write to the Free Software Foundation, Inc.,  
51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA.
```

Also add information on how to contact you by electronic and paper mail.

If the program is interactive, make it output a short notice like this when it starts in an interactive mode:

```
Gnomovision version 69, Copyright (C) year name of author  
Gnomovision comes with ABSOLUTELY NO WARRANTY; for details type `show w'.  
This is free software, and you are welcome to redistribute  
it  
under certain conditions; type `show c' for details.
```

The hypothetical commands `show w' and `show c' should show the appropriate parts of the General Public License. Of course, the commands you use may be called something other than `show w' and `show c'; they could even be mouse-clicks or menu items--whatever suits your program.

You should also get your employer (if you work as a programmer) or your school, if any, to sign a "copyright disclaimer" for the program, if necessary. Here is a sample; alter the names:

Yoyodyne, Inc., hereby disclaims all copyright interest in the program
'Gnomovision' (which makes passes at compilers) written by James Hacker.

<signature of Ty Coon>, 1 April 1989

Ty Coon, President of Vice

This General Public License does not permit incorporating your program into proprietary programs. If your program is a subroutine library, you may consider it more useful to permit linking proprietary applications with the library. If this

is what you want to do, use the GNU Lesser General

Public License instead of this License.

Copyright (c) 2014, Ipsantil

All rights reserved.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

* Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.

* Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT HOLDER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES;

LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

LZ4 Library

Copyright (c) 2011-2014, Yann Collet

All rights reserved.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

* Redistributions of source code must retain the above copyright notice, this

list of conditions and the following disclaimer.

* Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT HOLDER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

1.59 ubuntu-keyring 2018.09.18.1~18.04.2

1.59.1 Available under license :

This is Ubuntu GNU's GnuPG keyrings of archive keys.

This package was originally put together by Michael Vogt
<michael.vogt@canonical.com>

The keys in the keyrings don't fall under any copyright. Everything else in the package is covered by the GNU GPL.

Ubuntu support files Copyright (C) 2004 Michael Vogt <michael.vogt@canonical.com> based on the debian-keyring package maintained by James Troup

Ubuntu support files for ubuntu-keyring are free software; you can redistribute them and/or modify them under the terms of the GNU General Public License as published by the Free Software Foundation; either version 2, or (at your option) any later version.

Ubuntu support files for ubuntu-keyring are distributed in the hope that they will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details.

You should have received a copy of the GNU General Public License with your

Ubuntu system, in /usr/share/common-licenses/GPL, or with the Ubuntu GNU ubuntu-keyring source package as the file COPYING. If not, write to the Free Software Foundation, Inc., 51 Franklin Street, Fifth

1.60 apt 1.6.14

1.60.1 Available under license :

GNU GENERAL PUBLIC LICENSE
Version 2, June 1991

Copyright (C) 1989, 1991 Free Software Foundation, Inc.,
51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA
Everyone is permitted to copy and distribute verbatim copies
of this license document, but changing it is not allowed.

Preamble

The licenses for most software are designed to take away your freedom to share and change it. By contrast, the GNU General Public License is intended to guarantee your freedom to share and change free software--to make sure the software is free for all its users. This General Public License applies to most of the Free Software Foundation's software and to any other program whose authors commit to using it. (Some other Free Software Foundation software is covered by the GNU Lesser General Public License instead.) You can apply it to your programs, too.

When we speak of free software, we are referring to freedom, not price.

Our General Public Licenses are designed to make sure that you have the freedom to distribute copies of free software (and charge for this service if you wish), that you receive source code or can get it if you want it, that you can change the software or use pieces of it in new free programs; and that you know you can do these things.

To protect your rights, we need to make restrictions that forbid anyone to deny you these rights or to ask you to surrender the rights. These restrictions translate to certain responsibilities for you if you distribute copies of the software, or if you modify it.

For example, if you distribute copies of such a program, whether gratis or for a fee, you must give the recipients all the rights that you have. You must make sure that they, too, receive or can get the source code. And you must show them these terms so they know their rights.

We protect your rights with two steps: (1) copyright the software, and (2) offer you this license which

gives you legal permission to copy,
distribute and/or modify the software.

Also, for each author's protection and ours, we want to make certain that everyone understands that there is no warranty for this free software. If the software is modified by someone else and passed on, we want its recipients to know that what they have is not the original, so that any problems introduced by others will not reflect on the original authors' reputations.

Finally, any free program is threatened constantly by software patents. We wish to avoid the danger that redistributors of a free program will individually obtain patent licenses, in effect making the program proprietary. To prevent this, we have made it clear that any patent must be licensed for everyone's free use or not licensed at all.

The precise terms and conditions for copying, distribution and modification follow.

GNU GENERAL PUBLIC LICENSE TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

0. This License applies to any program or other work which contains a notice placed by the copyright holder saying it may be distributed under the terms of this General Public License. The "Program", below, refers to any such program or work, and a "work based on the Program" means either the Program or any derivative work under copyright law: that is to say, a work containing the Program or a portion of it, either verbatim or with modifications and/or translated into another language. (Hereinafter, translation is included without limitation in the term "modification".) Each licensee is addressed as "you".

Activities other than copying, distribution and modification are not covered by this License; they are outside its scope. The act of running the Program is not restricted, and the output from the Program is covered only if its contents constitute a work based on the Program (independent of having been made by running the Program). Whether that is true depends on what the Program does.

1. You may copy and distribute verbatim copies of the Program's source code as you receive it, in any medium, provided that you conspicuously and appropriately publish on each copy an appropriate copyright notice and disclaimer of warranty; keep intact all the notices that refer to this License and to the absence of any warranty; and give any other recipients of the Program a copy of this License along with the Program.

You may charge a fee for the physical act of transferring a copy, and you may at your option offer warranty protection in exchange for a fee.

2. You may modify your copy or copies of the Program or any portion of it, thus forming a work based on the Program, and copy and distribute such modifications or work under the terms of Section 1 above, provided that you also meet all of these conditions:

a) You must cause the modified files to carry prominent notices stating that you changed the files and the date of any change.

b) You must cause any work that you distribute or publish, that in whole or in part contains or is derived from the Program or any part thereof, to be licensed as a whole at no charge to all third parties under the terms of this License.

c) If the modified program normally reads commands interactively when run, you must cause it, when started running for such interactive use in the most ordinary way, to print or display an announcement including an appropriate copyright notice and a notice that there is no warranty (or else, saying that you provide a warranty) and that users may redistribute the program under these conditions, and telling the user how to view a copy of this License. (Exception: if the Program itself is interactive but does not normally print such an announcement, your work based on the Program is not required to print an announcement.)

These requirements apply to the modified work as a whole. If identifiable sections of that work are not derived from the Program, and can be reasonably considered independent and separate works in themselves, then this License, and its terms, do not apply to those sections when you distribute them as separate works. But when you distribute the same sections as part of a whole which is a work based on the Program, the distribution of the whole must be on the terms of this License, whose permissions for other licensees extend to the entire whole, and thus to each and every part regardless of who wrote it.

Thus, it is not the intent of this section to claim rights or contest your rights to work written entirely by you; rather, the intent is to exercise the right to control the distribution of derivative or collective works based on the Program.

In addition, mere aggregation of another work not based on the Program with the Program (or with a work based on the Program) on a volume of a storage or distribution medium does not bring the other work under the scope of this License.

3. You may copy and distribute the Program (or a work based on it, under Section 2) in object code or executable form under the terms of Sections 1 and 2 above provided that you also do one of the following:

- a) Accompany it with the complete corresponding machine-readable source code, which must be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange; or,
- b) Accompany it with a written offer, valid for at least three years, to give any third party, for a charge no more than your cost of physically performing source distribution, a complete machine-readable copy of the corresponding source code, to be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange; or,
- c) Accompany it with the information you received as to the offer to distribute corresponding source code. (This alternative is allowed only for noncommercial distribution and only if you received the program in object code or executable form with such an offer, in accord with Subsection b above.)

The source code for a work means the preferred form of the work for making modifications to it. For an executable work, complete source code means all the source code for all modules it contains, plus any associated interface definition files, plus the scripts used to control compilation and installation of the executable. However, as a special exception, the source code distributed need not include anything that is normally distributed (in either source or binary form) with the major components (compiler, kernel, and so on) of the operating system on which the executable runs, unless that component itself accompanies the executable.

If distribution of executable or object code is made by offering access to copy from a designated place, then offering equivalent access to copy the source code from the same place counts as distribution of the source code, even though third parties are not compelled to copy the source along with the object code.

4. You may not copy, modify, sublicense, or distribute the Program except as expressly provided under this License. Any attempt otherwise to copy, modify, sublicense or distribute the Program is void, and will automatically terminate your rights under this License. However, parties who have received copies, or rights, from you under this License will not have their licenses terminated so long as such parties remain in full compliance.

5. You are not required to accept this License, since you have not signed it. However, nothing else grants you permission to modify or distribute the Program or its derivative works. These actions are prohibited by law if you do not accept this License. Therefore, by modifying or distributing the Program (or any work based on the Program), you indicate your acceptance of this License to do so, and all its terms and conditions for copying, distributing or modifying the Program or works based on it.

6. Each time you redistribute the Program (or any work based on the Program), the recipient automatically receives a license from the original licensor to copy, distribute or modify the Program subject to these terms and conditions. You may not impose any further restrictions on the recipients' exercise of the rights granted herein. You are not responsible for enforcing compliance by third parties to this License.

7. If, as a consequence of a court judgment or allegation of patent infringement or for any other reason (not limited to patent issues), conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot distribute so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not distribute the Program at all. For example, if a patent license would not permit royalty-free redistribution of the Program by all those who receive copies directly or indirectly through you, then the only way you could satisfy both it and this License would be to refrain entirely from distribution of the Program.

If any portion of this section is held invalid or unenforceable under any particular circumstance, the balance of the section is intended to apply and the section as a whole is intended to apply in other circumstances.

It is not the purpose of this section to induce you to infringe any patents or other property right claims or to contest validity of any such claims; this section has the sole purpose of protecting the integrity of the free software distribution system, which is implemented by public license practices. Many people have made generous contributions to the wide range of software distributed through that system in reliance on consistent application of that system; it is up to the author/donor to decide if he or she is willing to distribute software through any other system and a licensee cannot

impose that choice.

This section is intended to make thoroughly clear what is believed to be a consequence of the rest of this License.

8. If the distribution and/or use of the Program is restricted in certain countries either by patents or by copyrighted interfaces, the original copyright holder who places the Program under this License may add an explicit geographical distribution limitation excluding those countries, so that distribution is permitted only in or among countries not thus excluded. In such case, this License incorporates the limitation as if written in the body of this License.

9. The Free Software Foundation may publish revised and/or new versions of the General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Program specifies a version number of this License which applies to it and "any later version", you have the option of following the terms and conditions either of that version or of any later version published by the Free Software Foundation. If the Program does not specify a version number of this License, you may choose any version ever published by the Free Software Foundation.

10. If you wish to incorporate parts of the Program into other free programs whose distribution conditions are different, write to the author to ask for permission. For software which is copyrighted by the Free Software Foundation, write to the Free Software Foundation; we sometimes make exceptions for this. Our decision will be guided by the two goals of preserving the free status of all derivatives of our free software and of promoting the sharing and reuse of software generally.

NO WARRANTY

11. BECAUSE THE PROGRAM IS LICENSED FREE OF CHARGE, THERE IS NO WARRANTY FOR THE PROGRAM, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE PROGRAM "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE PROGRAM IS WITH YOU. SHOULD THE PROGRAM PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

12. IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY AND/OR REDISTRIBUTE THE PROGRAM AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE PROGRAM (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR

THIRD PARTIES OR A FAILURE OF THE PROGRAM TO OPERATE WITH ANY OTHER PROGRAMS), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Programs

If you develop a new program, and you want it to be of the greatest possible use to the public, the best way to achieve this is to make it free software which everyone can redistribute and change under these terms.

To do so, attach the following notices to the program. It is safest to attach them to the start of each source file to most effectively convey the exclusion of warranty; and each file should have at least the "copyright" line and a pointer to where the full notice is found.

<one line to give the program's name and a brief idea of what it does.>
Copyright (C) <year> <name of author>

This program is free software; you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation; either version 2 of the License, or (at your option) any later version.

This program is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details.

You should have received a copy of the GNU General Public License along with this program; if not, write to the Free Software Foundation, Inc., 51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA.

Also add information on how to contact you by electronic and paper mail.

If the program is interactive, make it output a short notice like this when it starts in an interactive mode:

Gnomovision version 69, Copyright (C) year name of author

Gnomovision comes with ABSOLUTELY NO WARRANTY; for details type `show w'.
This is free software, and you are welcome to redistribute
it
under certain conditions; type `show c' for details.

The hypothetical commands `show w' and `show c' should show the appropriate parts of the General Public License. Of course, the commands you use may be called something other than `show w' and `show c'; they could even be mouse-clicks or menu items--whatever suits your program.

You should also get your employer (if you work as a programmer) or your school, if any, to sign a "copyright disclaimer" for the program, if necessary. Here is a sample; alter the names:

Yoyodyne, Inc., hereby disclaims all copyright interest in the program
'Gnomovision' (which makes passes at compilers) written by James Hacker.

<signature of Ty Coon>, 1 April 1989
Ty Coon, President of Vice

This General Public License does not permit incorporating your program into proprietary programs. If your program is a subroutine library, you may consider it more useful to permit linking proprietary applications with the library. If this is what you want to do, use the GNU Lesser General Public License instead of this License.

Apt is copyright 1997, 1998, 1999 Jason Gunthorpe and others.

Apt is currently developed by APT Development Team <deity@lists.debian.org>.

License: GPLv2+

This program is free software; you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation; either version 2 of the License, or (at your option) any later version.

This program is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details.

You should have received a copy of the GNU General Public License along with this program; if not, write to the Free Software Foundation, Inc., 51 Franklin St, Fifth Floor, Boston, MA 02110-1301, USA.

See /usr/share/common-licenses/GPL-2, or
<<http://www.gnu.org/copyleft/gpl.txt>> for the terms of the latest version of the

GNU General Public License.

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.61 base-files 10.1ubuntu2.11

1.61.1 Available under license :

Copyright (c) The Regents of the University of California.
All rights reserved.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

1. Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.
2. Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.
3. Neither the name of the University nor the names of its contributors may be used to endorse or promote products derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE REGENTS AND CONTRIBUTORS ``AS IS'' AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE REGENTS OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT

LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

GNU LESSER GENERAL PUBLIC LICENSE

Version 3, 29 June 2007

Copyright (C) 2007 Free Software Foundation, Inc. <<http://fsf.org/>>

Everyone is permitted to copy and distribute verbatim copies of this license document, but changing it is not allowed.

This version of the GNU Lesser General Public License incorporates the terms and conditions of version 3 of the GNU General Public License, supplemented by the additional permissions listed below.

0. Additional Definitions.

As used herein, "this License" refers to version 3 of the GNU Lesser General Public License, and the "GNU GPL" refers to version 3 of the GNU General Public License.

"The Library" refers to a covered work governed by this License, other than an Application or a Combined Work as defined below.

An "Application" is any work that makes use of an interface provided by the Library, but which is not otherwise based on the Library. Defining a subclass of a class defined by the Library is deemed a mode of using an interface provided by the Library.

A "Combined Work" is a work produced by combining or linking an Application with the Library. The particular version of the Library with which the Combined Work was made is also called the "Linked Version".

The "Minimal Corresponding Source" for a Combined Work means the Corresponding Source for the Combined Work, excluding any source code for portions of the Combined Work that, considered in isolation, are based on the Application, and not on the Linked Version.

The "Corresponding Application Code" for a Combined Work means the object code and/or source code for the Application, including any data and utility programs needed for reproducing the Combined Work from the Application, but excluding the System Libraries of the Combined Work.

1. Exception to Section 3 of the GNU GPL.

You may convey a covered work under sections 3 and 4 of this License

without being bound by section 3 of the GNU GPL.

2. Conveying Modified Versions.

If you modify a copy of the Library, and, in your modifications, a facility refers to a function or data to be supplied by an Application that uses the facility (other than as an argument passed when the facility is invoked), then you may convey a copy of the modified version:

- a) under this License, provided that you make a good faith effort to ensure that, in the event an Application does not supply the function or data, the facility still operates, and performs whatever part of its purpose remains meaningful, or
- b) under the GNU GPL, with none of the additional permissions of this License applicable to that copy.

3. Object Code Incorporating Material from Library Header Files.

The object code form of an Application may incorporate material from a header file that is part of the Library. You may convey such object code under terms of your choice, provided that, if the incorporated material is not limited to numerical parameters, data structure layouts and accessors, or small macros, inline functions and templates (ten or fewer lines in length), you do both of the following:

- a) Give prominent notice with each copy of the object code that the Library is used in it and that the Library and its use are covered by this License.
- b) Accompany the object code with a copy of the GNU GPL and this license document.

4. Combined Works.

You may convey a Combined Work under terms of your choice that, taken together, effectively do not restrict modification of the portions of the Library contained in the Combined Work and reverse engineering for debugging such modifications, if you also do each of the following:

- a) Give prominent notice with each copy of the Combined Work that the Library is used in it and that the Library and its use are covered by this License.
- b) Accompany the Combined Work with a copy of the GNU GPL and this license

document.

c) For a Combined Work that displays copyright notices during execution, include the copyright notice for the Library among these notices, as well as a reference directing the user to the copies of the GNU GPL and this license document.

d) Do one of the following:

0) Convey the Minimal Corresponding Source under the terms of this License, and the Corresponding Application Code in a form suitable for, and under terms that permit, the user to recombine or relink the Application with a modified version of the Linked Version to produce a modified Combined Work, in the manner specified by section 6 of the GNU GPL for conveying Corresponding Source.

1) Use a suitable shared library mechanism for linking with the Library. A suitable mechanism is one that (a) uses at run time a copy of the Library already present on the user's computer system, and (b) will operate properly with a modified version of the Library that is interface-compatible with the Linked Version.

e) Provide Installation Information, but only if you would otherwise be required to provide such information under section 6 of the GNU GPL, and only to the extent that such information is necessary to install and execute a modified version of the Combined Work produced by recombining or relinking the Application with a modified version of the Linked Version. (If you use option 4d0, the Installation Information must accompany the Minimal Corresponding Source and Corresponding Application Code. If you use option 4d1, you must provide the Installation Information in the manner specified by section 6 of the GNU GPL for conveying Corresponding Source.)

5. Combined Libraries.

You may place library facilities that are a work based on the Library side by side in a single library together with other library facilities that are not Applications and are not covered by this License, and convey such a combined library under terms of your choice, if you do both of the following:

a) Accompany the combined library with a copy of the same work based

on the Library, uncombined with any other library facilities,
conveyed under the terms of this License.

b) Give prominent notice with the combined library that part of it
is a work based on the Library, and explaining where to find the
accompanying uncombined form of the same work.

6. Revised Versions of the GNU Lesser General Public License.

The Free Software Foundation may publish revised and/or new versions
of the GNU Lesser General Public License from time to time. Such new
versions will be similar in spirit to the present version, but may
differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the
Library as you received it specifies that a certain numbered version
of the GNU Lesser General Public License "or any later version"
applies to it, you have the option
of following the terms and
conditions either of that published version or of any later version
published by the Free Software Foundation. If the Library as you
received it does not specify a version number of the GNU Lesser
General Public License, you may choose any version of the GNU Lesser
General Public License ever published by the Free Software Foundation.

If the Library as you received it specifies that a proxy can decide
whether future versions of the GNU Lesser General Public License shall
apply, that proxy's public statement of acceptance of any version is
permanent authorization for you to choose that version for the
Library.

GNU LIBRARY GENERAL PUBLIC LICENSE Version 2, June 1991

Copyright (C) 1991 Free Software Foundation, Inc.
51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA
Everyone is permitted to copy and distribute verbatim copies
of this license document, but changing it is not allowed.

[This is the first released version of the library GPL. It is
numbered 2 because it goes with version 2 of the ordinary GPL.]

Preamble

The licenses for most software are designed to take away your
freedom to share and change it. By contrast, the GNU General Public
Licenses are intended to guarantee your freedom to share and change
free software--to make sure the software is free for all its users.

This license, the Library General Public License, applies to some specially designated Free Software Foundation software, and to any other libraries whose authors decide to use it. You can use it for your libraries, too.

When

we speak of free software, we are referring to freedom, not price. Our General Public Licenses are designed to make sure that you have the freedom to distribute copies of free software (and charge for this service if you wish), that you receive source code or can get it if you want it, that you can change the software or use pieces of it in new free programs; and that you know you can do these things.

To protect your rights, we need to make restrictions that forbid anyone to deny you these rights or to ask you to surrender the rights. These restrictions translate to certain responsibilities for you if you distribute copies of the library, or if you modify it.

For example, if you distribute copies of the library, whether gratis or for a fee, you must give the recipients all the rights that we gave you. You must make sure that they, too, receive or can get the source code. If you link a program with the library, you must provide complete object files to the recipients so that they can relink them with the library, after making changes to the library and recompiling it. And you must show them these terms so they know their rights.

Our method of protecting your rights has two steps: (1) copyright the library, and (2) offer you this license which gives you legal permission to copy, distribute and/or modify the library.

Also, for each distributor's protection, we want to make certain that everyone understands that there is no warranty for this free library. If the library is modified by someone else and passed on, we want its recipients to know that what they have is not the original version, so that any problems introduced by others will not reflect on the original authors' reputations.

Finally, any free program is threatened constantly by software patents. We wish to avoid the danger that companies distributing free software will individually obtain patent licenses, thus in effect transforming the program into proprietary software. To prevent this, we have made it clear that any patent must be licensed for everyone's free use or not licensed at all.

Most GNU software, including some libraries, is covered by the ordinary GNU General Public License, which was designed for utility programs. This

license, the GNU Library General Public License, applies to certain designated libraries. This license is quite different from the ordinary one; be sure to read it in full, and don't assume that anything in it is the same as in the ordinary license.

The reason we have a separate public license for some libraries is that they blur the distinction we usually make between modifying or adding to a program and simply using it. Linking a program with a library, without changing the library, is in some sense simply using the library, and is analogous to running a utility program or application program. However, in a textual and legal sense, the linked executable is a combined work, a derivative of the original library, and the ordinary General Public License treats it as such.

Because of this blurred distinction, using the ordinary General Public License for libraries did not effectively promote software sharing, because most developers did not use the libraries. We concluded that weaker conditions might promote sharing better.

However, unrestricted linking of non-free programs would deprive the users of those programs of all benefit from the free status of the libraries themselves. This Library General Public License is intended to permit developers of non-free programs to use free libraries, while preserving your freedom as a user of such programs to change the free libraries that are incorporated in them. (We have not seen how to achieve this as regards changes in header files, but we have achieved it as regards changes in the actual functions of the Library.) The hope is that this will lead to faster development of free libraries.

The precise terms and conditions for copying, distribution and modification follow. Pay close attention to the difference between a "work based on the library" and a "work that uses the library". The former contains code derived from the library, while the latter only works together with the library.

Note that it is possible for a library to be covered by the ordinary General Public License rather than by this special one.

GNU LIBRARY GENERAL PUBLIC LICENSE TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

0. This License Agreement applies to any software library which contains a notice placed by the copyright holder or other authorized party saying it may be distributed under the terms of this Library General Public License (also called "this License"). Each licensee is addressed as "you".

A "library" means a collection of software functions and/or data prepared so as to be conveniently linked with application programs (which use some of those functions and data) to form executables.

The "Library", below, refers to any such software library or work which has been distributed under these terms. A "work based on the Library" means either the Library or any derivative work under copyright law: that is to say, a work containing the Library or a portion of it, either verbatim or with modifications and/or translated straightforwardly into another language. (Hereinafter, translation is included without limitation in the term "modification".)

"Source code" for a work means the preferred form of the work for making modifications to it. For a library, complete source code means all the source code for all modules it contains, plus any associated interface definition files, plus the scripts used to control compilation and installation of the library.

Activities other than copying, distribution and modification are not covered by this License; they are outside its scope. The act of running a program using the Library is not restricted, and output from such a program is covered only if its contents constitute a work based on the Library (independent of the use of the Library in a tool for writing it). Whether that is true depends on what the Library does and what the program that uses the Library does.

1. You may copy and distribute verbatim copies of the Library's complete source code as you receive it, in any medium, provided that you conspicuously and appropriately publish on each copy an appropriate copyright notice and disclaimer of warranty; keep intact all the notices that refer to this License and to the absence of any warranty; and distribute a copy of this License along with the Library.

You may charge a fee for the physical act of transferring a copy, and you may at your option offer warranty protection in exchange for a fee.

2. You may modify your copy or copies of the Library or any portion of it, thus forming a work based on the Library, and copy and distribute such modifications or work under the terms of Section 1 above, provided that you also meet all of these conditions:

- a) The modified work must itself be a software library.

b) You must cause the files modified to carry prominent notices stating that you changed the files and the date of any change.

c) You must cause the whole of the work to be licensed at no charge to all third parties under the terms of this License.

d) If a facility in the modified Library refers to a function or a table of data to be supplied by an application program that uses the facility, other than as an argument passed when the facility is invoked, then you must make a good faith effort to ensure that, in the event an application does not supply such function or table, the facility still operates, and performs whatever part of its purpose remains meaningful.

(For example, a function in a library to compute square roots has a purpose that is entirely well-defined independent of the application. Therefore, Subsection 2d requires that any application-supplied function or table used by this function must be optional: if the application does not supply it, the square root function must still compute square roots.)

These requirements apply to the modified work as a whole. If identifiable sections of that work are not derived from the Library, and can be reasonably considered independent and separate works in themselves, then this License, and its terms, do not apply to those sections when you distribute them as separate works. But when you distribute the same sections as part of a whole which is a work based on the Library, the distribution of the whole must be on the terms of this License, whose permissions for other licensees extend to the entire whole, and thus to each and every part regardless of who wrote it.

Thus, it is not the intent of this section to claim rights or contest your rights to work written entirely by you; rather, the intent is to exercise the right to control the distribution of derivative or collective works based on the Library.

In addition, mere aggregation of another work not based on the Library with the Library (or with a work based on the Library) on a volume of a storage or distribution medium does not bring the other work under the scope of this License.

3. You may opt to apply the terms of the ordinary GNU General Public License instead of this License to a given copy of the Library. To do this, you must alter all the notices that refer to this License, so

that they refer to the ordinary GNU General Public License, version 2, instead of to this License. (If a newer version than version 2 of the ordinary GNU General Public License has appeared, then you can specify that version instead if you wish.) Do not make any other change in these notices.

Once this change is made in a given copy, it is irreversible for that copy, so the ordinary GNU General Public License applies to all subsequent copies and derivative works made from that copy.

This option is useful when you wish to copy part of the code of the Library into a program that is not a library.

4. You may copy and distribute the Library (or a portion or derivative of it, under Section 2) in object code or executable form under the terms of Sections 1 and 2 above provided that you accompany it with the complete corresponding machine-readable source code, which must be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange.

If distribution of object code is made by offering access to copy from a designated place, then offering equivalent access to copy the source code from the same place satisfies the requirement to distribute the source code, even though third parties are not compelled to copy the source along with the object code.

5. A program that contains no derivative of any portion of the Library, but is designed to work with the Library by being compiled or linked with it, is called a "work that uses the Library". Such a work, in isolation, is not a derivative work of the Library, and therefore falls outside the scope of this License.

However, linking a "work that uses the Library" with the Library creates an executable that is a derivative of the Library (because it contains portions of the Library), rather than a "work that uses the library". The executable is therefore covered by this License. Section 6 states terms for distribution of such executables.

When a "work that uses the Library" uses material from a header file that is part of the Library, the object code for the work may be a derivative work of the Library even though the source code is not. Whether this is true is especially significant if the work can be linked without the Library, or if the work is itself a library. The threshold for this to be true is not precisely defined by law.

If such an object file uses only numerical parameters, data structure layouts and accessors, and small macros and small

inline

functions (ten lines or less in length), then the use of the object file is unrestricted, regardless of whether it is legally a derivative work. (Executables containing this object code plus portions of the Library will still fall under Section 6.)

Otherwise, if the work is a derivative of the Library, you may distribute the object code for the work under the terms of Section 6. Any executables containing that work also fall under Section 6, whether or not they are linked directly with the Library itself.

6. As an exception to the Sections above, you may also compile or link a "work that uses the Library" with the Library to produce a work containing portions of the Library, and distribute that work under terms of your choice, provided that the terms permit modification of the work for the customer's own use and reverse engineering for debugging such modifications.

You must give prominent notice with each copy of the work that the Library is used in it and that the Library and its use are covered by this License. You must supply a copy of this License. If the work during execution displays copyright notices, you must include the copyright notice for the Library among them, as well as a reference directing the user to the copy of this License. Also, you must do one of these things:

- a) Accompany the work with the complete corresponding machine-readable source code for the Library including whatever changes were used in the work (which must be distributed under Sections 1 and 2 above); and, if the work is an executable linked with the Library, with the complete machine-readable "work that uses the Library", as object code and/or source code, so that the user can modify the Library and then relink to produce a modified executable containing the modified Library. (It is understood that the user who changes the contents of definitions files in the Library will not necessarily be able to recompile the application to use the modified definitions.)
- b) Accompany the work with a written offer, valid for at least three years, to give the same user the materials specified in Subsection 6a, above, for a charge no more than the cost of performing this distribution.
- c) If distribution of the work is made by offering access to copy from a designated place, offer equivalent access to copy the above specified materials from the same place.

d) Verify that the user has already received a copy of these materials or that you have already sent this user a copy.

For an executable, the required form of the "work that uses the Library" must include any data and utility programs needed for reproducing the executable from it. However, as a special exception, the source code distributed need not include anything that is normally distributed (in either source or binary form) with the major components (compiler, kernel, and so on) of the operating system on which the executable runs, unless that component itself accompanies the executable.

It may happen that this requirement contradicts the license restrictions of other proprietary libraries that do not normally accompany the operating system. Such a contradiction means you cannot use both them and the Library together in an executable that you distribute.

7. You may place library facilities that are a work based on the Library side-by-side in a single library together with other library facilities not covered by this License, and distribute such a combined library, provided that the separate distribution of the work based on the Library and of the other library facilities is otherwise permitted, and provided that you do these two things:

a) Accompany the combined library with a copy of the same work based on the Library, uncombined with any other library facilities. This must be distributed under the terms of the Sections above.

b) Give prominent notice with the combined library of the fact that part of it is a work based on the Library, and explaining where to find the accompanying uncombined form of the same work.

8. You may not copy, modify, sublicense, link with, or distribute the Library except as expressly provided under this License. Any attempt otherwise to copy, modify, sublicense, link with, or distribute the Library is void, and will automatically terminate your rights under this License. However, parties who have received copies, or rights, from you under this License will not have their licenses terminated so long as such parties remain in full compliance.

9. You are not required to accept this License, since you have not signed it. However, nothing else grants you permission to modify or distribute the Library or its derivative works. These actions are prohibited by law if you do not accept this License. Therefore, by

modifying or distributing the Library (or any work based on the Library), you indicate your acceptance of this License to do so, and all its terms and conditions for copying, distributing or modifying the Library or works based on it.

10. Each time you redistribute the Library (or any work based on the Library), the recipient automatically receives a license from the original licensor to copy, distribute, link with or modify the Library subject to these terms and conditions. You may not impose any further restrictions on the recipients' exercise of the rights granted herein. You are not responsible for enforcing compliance by third parties to this License.

11. If, as a consequence of a court judgment or allegation of patent infringement or for any other reason (not limited to patent issues), conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot distribute so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not distribute the Library at all. For example, if a patent license would not permit royalty-free redistribution of the Library by all those who receive copies directly or indirectly through you, then the only way you could satisfy both it and this License would be to refrain entirely from distribution of the Library.

If any portion of this section is held invalid or unenforceable under any particular circumstance, the balance of the section is intended to apply, and the section as a whole is intended to apply in other circumstances.

It is not the purpose of this section to induce you to infringe any patents or other property right claims or to contest validity of any such claims; this section has the sole purpose of protecting the integrity of the free software distribution system which is implemented by public license practices. Many people have made generous contributions to the wide range of software distributed through that system in reliance on consistent application of that system; it is up to the author/donor to decide if he or she is willing to distribute software through any other system and a licensee cannot impose that choice.

This section is intended to make thoroughly clear what is believed to be a consequence of the rest of this License.

12. If the distribution and/or use of the Library is restricted in

certain countries either by patents or by copyrighted interfaces, the original copyright holder who places the Library under this License may add an explicit geographical distribution limitation excluding those countries, so that distribution is permitted only in or among countries not thus excluded. In such case, this License incorporates the limitation as if written in the body of this License.

13. The Free Software Foundation may publish revised and/or new versions of the Library General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Library specifies a version number of this License which applies to it and "any later version", you have the option of following the terms and conditions either of that version or of any later version published by the Free Software Foundation. If the Library does not specify a license version number, you may choose any version ever published by the Free Software Foundation.

14. If you wish to incorporate parts of the Library into other free programs whose distribution conditions are incompatible with these, write to the author to ask for permission. For software which is copyrighted by the Free Software Foundation, write to the Free Software Foundation; we sometimes make exceptions for this. Our decision will be guided by the two goals of preserving the free status of all derivatives of our free software and of promoting the sharing and reuse of software generally.

NO WARRANTY

15. BECAUSE THE LIBRARY IS LICENSED FREE OF CHARGE, THERE IS NO WARRANTY FOR THE LIBRARY, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE LIBRARY "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE LIBRARY IS WITH YOU. SHOULD THE LIBRARY PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

16. IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY AND/OR REDISTRIBUTE THE LIBRARY AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE

LIBRARY

(INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE LIBRARY TO OPERATE WITH ANY OTHER SOFTWARE), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Libraries

If you develop a new library, and you want it to be of the greatest possible use to the public, we recommend making it free software that everyone can redistribute and change. You can do so by permitting redistribution under these terms (or, alternatively, under the terms of the ordinary General Public License).

To apply these terms, attach the following notices to the library. It is safest to attach them to the start of each source file to most effectively convey the exclusion of warranty; and each file should have at least the "copyright" line and a pointer to where the full notice is found.

<one line to give the library's name and a brief idea of what it does.>

Copyright (C) <year> <name of author>

This library is free software; you can redistribute it and/or modify it under the terms of the GNU Library General Public License as published by the Free Software Foundation; either version 2 of the License, or (at your option) any later version.

This library is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU Library General Public License for more details.

You should have received a copy of the GNU Library General Public License along with this library; if not, write to the Free Software Foundation, Inc., 51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA

Also add information on how to contact you by electronic and paper mail.

You should also get your employer (if you work as a programmer) or your school, if any, to sign a "copyright disclaimer" for the library, if necessary. Here is a sample; alter the names:

Yoyodyne, Inc., hereby disclaims all copyright interest in the

library `Frob' (a library for tweaking knobs) written by James Random Hacker.

<signature of Ty Coon>, 1 April 1990

Ty Coon, President of Vice

That's all there is to it!

GNU GENERAL PUBLIC LICENSE

Version 2, June 1991

Copyright (C) 1989, 1991 Free Software Foundation, Inc.,
51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA
Everyone is permitted to copy and distribute verbatim copies
of this license document, but changing it is not allowed.

Preamble

The licenses for most software are designed to take away your freedom to share and change it. By contrast, the GNU General Public License is intended to guarantee your freedom to share and change free software--to make sure the software is free for all its users. This General Public License applies to most of the Free Software Foundation's software and to any other program whose authors commit to using it. (Some other Free Software Foundation software is covered by the GNU Lesser General Public License instead.) You can apply it to your programs, too.

When we speak of free software, we are referring to freedom, not price.

Our General Public Licenses are designed to make sure that you have the freedom to distribute copies of free software (and charge for this service if you wish), that you receive source code or can get it if you want it, that you can change the software or use pieces of it in new free programs; and that you know you can do these things.

To protect your rights, we need to make restrictions that forbid anyone to deny you these rights or to ask you to surrender the rights. These restrictions translate to certain responsibilities for you if you distribute copies of the software, or if you modify it.

For example, if you distribute copies of such a program, whether gratis or for a fee, you must give the recipients all the rights that you have. You must make sure that they, too, receive or can get the source code. And you must show them these terms so they know their rights.

We protect your rights with two steps: (1) copyright the software, and (2) offer you this license which

gives you legal permission to copy,
distribute and/or modify the software.

Also, for each author's protection and ours, we want to make certain that everyone understands that there is no warranty for this free software. If the software is modified by someone else and passed on, we want its recipients to know that what they have is not the original, so that any problems introduced by others will not reflect on the original authors' reputations.

Finally, any free program is threatened constantly by software patents. We wish to avoid the danger that redistributors of a free program will individually obtain patent licenses, in effect making the program proprietary. To prevent this, we have made it clear that any patent must be licensed for everyone's free use or not licensed at all.

The precise terms and conditions for copying, distribution and modification follow.

GNU GENERAL PUBLIC LICENSE TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

0. This License applies to any program or other work which contains a notice placed by the copyright holder saying it may be distributed under the terms of this General Public License. The "Program", below, refers to any such program or work, and a "work based on the Program" means either the Program or any derivative work under copyright law: that is to say, a work containing the Program or a portion of it, either verbatim or with modifications and/or translated into another language. (Hereinafter, translation is included without limitation in the term "modification".) Each licensee is addressed as "you".

Activities other than copying, distribution and modification are not covered by this License; they are outside its scope. The act of running the Program is not restricted, and the output from the Program is covered only if its contents constitute a work based on the Program (independent of having been made by running the Program). Whether that is true depends on what the Program does.

1. You may copy and distribute verbatim copies of the Program's source code as you receive it, in any medium, provided that you conspicuously and appropriately publish on each copy an appropriate copyright notice and disclaimer of warranty; keep intact all the notices that refer to this License and to the absence of any warranty; and give any other recipients of the Program a copy of this License along with the Program.

You may charge a fee for the physical act of transferring a copy, and you may at your option offer warranty protection in exchange for a fee.

2. You may modify your copy or copies of the Program or any portion of it, thus forming a work based on the Program, and copy and distribute such modifications or work under the terms of Section 1 above, provided that you also meet all of these conditions:

a) You must cause the modified files to carry prominent notices stating that you changed the files and the date of any change.

b) You must cause any work that you distribute or publish, that in whole or in part contains or is derived from the Program or any part thereof, to be licensed as a whole at no charge to all third parties under the terms of this License.

c) If the modified program normally reads commands interactively when run, you must cause it, when started running for such interactive use in the most ordinary way, to print or display an announcement including an appropriate copyright notice and a notice that there is no warranty (or else, saying that you provide a warranty) and that users may redistribute the program under these conditions, and telling the user how to view a copy of this License. (Exception: if the Program itself is interactive but does not normally print such an announcement, your work based on the Program is not required to print an announcement.)

These requirements apply to the modified work as a whole. If identifiable sections of that work are not derived from the Program, and can be reasonably considered independent and separate works in themselves, then this License, and its terms, do not apply to those sections when you distribute them as separate works. But when you distribute the same sections as part of a whole which is a work based on the Program, the distribution of the whole must be on the terms of this License, whose permissions for other licensees extend to the entire whole, and thus to each and every part regardless of who wrote it.

Thus, it is not the intent of this section to claim rights or contest your rights to work written entirely by you; rather, the intent is to exercise the right to control the distribution of derivative or collective works based on the Program.

In addition, mere aggregation of another work not based on the Program with the Program (or with a work based on the Program) on a volume of a storage or distribution medium does not bring the other work under the scope of this License.

3. You may copy and distribute the Program (or a work based on it, under Section 2) in object code or executable form under the terms of Sections 1 and 2 above provided that you also do one of the following:

- a) Accompany it with the complete corresponding machine-readable source code, which must be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange; or,
- b) Accompany it with a written offer, valid for at least three years, to give any third party, for a charge no more than your cost of physically performing source distribution, a complete machine-readable copy of the corresponding source code, to be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange; or,
- c) Accompany it with the information you received as to the offer to distribute corresponding source code. (This alternative is allowed only for noncommercial distribution and only if you received the program in object code or executable form with such an offer, in accord with Subsection b above.)

The source code for a work means the preferred form of the work for making modifications to it. For an executable work, complete source code means all the source code for all modules it contains, plus any associated interface definition files, plus the scripts used to control compilation and installation of the executable. However, as a special exception, the source code distributed need not include anything that is normally distributed (in either source or binary form) with the major components (compiler, kernel, and so on) of the operating system on which the executable runs, unless that component itself accompanies the executable.

If distribution of executable or object code is made by offering access to copy from a designated place, then offering equivalent access to copy the source code from the same place counts as distribution of the source code, even though third parties are not compelled to copy the source along with the object code.

4. You may not copy, modify, sublicense, or distribute the Program except as expressly provided under this License. Any attempt otherwise to copy, modify, sublicense or distribute the Program is void, and will automatically terminate your rights under this License. However, parties who have received copies, or rights, from you under this License will not have their licenses terminated so long as such parties remain in full compliance.

5. You are not required to accept this License, since you have not signed it. However, nothing else grants you permission to modify or distribute the Program or its derivative works. These actions are prohibited by law if you do not accept this License. Therefore, by modifying or distributing the Program (or any work based on the Program), you indicate your acceptance of this License to do so, and all its terms and conditions for copying, distributing or modifying the Program or works based on it.

6. Each time you redistribute the Program (or any work based on the Program), the recipient automatically receives a license from the original licensor to copy, distribute or modify the Program subject to these terms and conditions. You may not impose any further restrictions on the recipients' exercise of the rights granted herein. You are not responsible for enforcing compliance by third parties to this License.

7. If, as a consequence of a court judgment or allegation of patent infringement or for any other reason (not limited to patent issues), conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot distribute so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not distribute the Program at all. For example, if a patent license would not permit royalty-free redistribution of the Program by all those who receive copies directly or indirectly through you, then the only way you could satisfy both it and this License would be to refrain entirely from distribution of the Program.

If any portion of this section is held invalid or unenforceable under any particular circumstance, the balance of the section is intended to apply and the section as a whole is intended to apply in other circumstances.

It is not the purpose of this section to induce you to infringe any patents or other property right claims or to contest validity of any such claims; this section has the sole purpose of protecting the integrity of the free software distribution system, which is implemented by public license practices. Many people have made generous contributions to the wide range of software distributed through that system in reliance on consistent application of that system; it is up to the author/donor to decide if he or she is willing to distribute software through any other system and a licensee cannot

impose that choice.

This section is intended to make thoroughly clear what is believed to be a consequence of the rest of this License.

8. If the distribution and/or use of the Program is restricted in certain countries either by patents or by copyrighted interfaces, the original copyright holder who places the Program under this License may add an explicit geographical distribution limitation excluding those countries, so that distribution is permitted only in or among countries not thus excluded. In such case, this License incorporates the limitation as if written in the body of this License.

9. The Free Software Foundation may publish revised and/or new versions of the General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Program specifies a version number of this License which applies to it and "any later version", you have the option of following the terms and conditions either of that version or of any later version published by the Free Software Foundation. If the Program does not specify a version number of this License, you may choose any version ever published by the Free Software Foundation.

10. If you wish to incorporate parts of the Program into other free programs whose distribution conditions are different, write to the author to ask for permission. For software which is copyrighted by the Free Software Foundation, write to the Free Software Foundation; we sometimes make exceptions for this. Our decision will be guided by the two goals of preserving the free status of all derivatives of our free software and of promoting the sharing and reuse of software generally.

NO WARRANTY

11. BECAUSE THE PROGRAM IS LICENSED FREE OF CHARGE, THERE IS NO WARRANTY FOR THE PROGRAM, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE PROGRAM "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE PROGRAM IS WITH YOU. SHOULD THE PROGRAM PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

12. IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY AND/OR REDISTRIBUTE THE PROGRAM AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE PROGRAM (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR

THIRD PARTIES OR A FAILURE OF THE PROGRAM TO OPERATE WITH ANY OTHER PROGRAMS), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Programs

If you develop a new program, and you want it to be of the greatest possible use to the public, the best way to achieve this is to make it free software which everyone can redistribute and change under these terms.

To do so, attach the following notices to the program. It is safest to attach them to the start of each source file to most effectively convey the exclusion of warranty; and each file should have at least the "copyright" line and a pointer to where the full notice is found.

<one line to give the program's name and a brief idea of what it does.>
Copyright (C) <year> <name of author>

This program is free software; you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation; either version 2 of the License, or (at your option) any later version.

This program is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details.

You should have received a copy of the GNU General Public License along with this program; if not, write to the Free Software Foundation, Inc., 51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA.

Also add information on how to contact you by electronic and paper mail.

If the program is interactive, make it output a short notice like this when it starts in an interactive mode:

Gnomovision version 69, Copyright (C) year name of author

Gnomovision comes with ABSOLUTELY NO WARRANTY; for details type `show w'.
This is free software, and you are welcome to redistribute
it
under certain conditions; type `show c' for details.

The hypothetical commands `show w' and `show c' should show the appropriate parts of the General Public License. Of course, the commands you use may be called something other than `show w' and `show c'; they could even be mouse-clicks or menu items--whatever suits your program.

You should also get your employer (if you work as a programmer) or your school, if any, to sign a "copyright disclaimer" for the program, if necessary. Here is a sample; alter the names:

Yoyodyne, Inc., hereby disclaims all copyright interest in the program
`Gnomovision' (which makes passes at compilers) written by James Hacker.

<signature of Ty Coon>, 1 April 1989
Ty Coon, President of Vice

This General Public License does not permit incorporating your program into proprietary programs. If your program is a subroutine library, you may consider it more useful to permit linking proprietary applications with the library. If this is what you want to do, use the GNU Lesser General Public License instead of this License.

The programs included with the Ubuntu system are free software; the exact distribution terms for each program are described in the individual files in /usr/share/doc/*/copyright.

Ubuntu comes with ABSOLUTELY NO WARRANTY, to the extent permitted by applicable law.

GNU GENERAL PUBLIC LICENSE
Version 1, February 1989

Copyright (C) 1989 Free Software Foundation, Inc.
51 Franklin St, Fifth Floor, Boston, MA 02110-1301 USA

Everyone is permitted to copy and distribute verbatim copies of this license document, but changing it is not allowed.

Preamble

The license agreements of most software companies try to keep users at the mercy of those companies. By contrast, our General Public License is intended to guarantee your freedom to share and change free

software--to make sure the software is free for all its users. The General Public License applies to the Free Software Foundation's software and to any other program whose authors commit to using it. You can use it for your programs, too.

When we speak of free software, we are referring to freedom, not price. Specifically, the General Public License is designed to make sure that you have the freedom to give away or sell copies of free software, that you receive source code or can get it if you want it, that you can change the software or use pieces of it in new free programs; and that you know you can do these things.

To protect your rights, we need to make restrictions that forbid anyone to deny you these rights or to ask you to surrender the rights. These restrictions translate to certain responsibilities for you if you distribute copies of the software, or if you modify it.

For example, if you distribute copies of a such a program, whether gratis or for a fee, you must give the recipients all the rights that you have. You must make sure that they, too, receive or can get the source code. And you must tell them their rights.

We protect your rights with two steps: (1) copyright the software, and (2) offer you this license which gives you legal permission to copy, distribute and/or modify the software.

Also, for each author's protection and ours, we want to make certain that everyone understands that there is no warranty for this free software. If the software is modified by someone else and passed on, we want its recipients to know that what they have is not the original, so that any problems introduced by others will not reflect on the original authors' reputations.

The precise terms and conditions for copying, distribution and modification follow.

GNU GENERAL PUBLIC LICENSE TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

0. This License Agreement applies to any program or other work which contains a notice placed by the copyright holder saying it may be distributed under the terms of this General Public License. The "Program", below, refers to any such program or work, and a "work based on the Program" means either the Program or any work containing the Program or a portion of it, either verbatim or with modifications. Each licensee is addressed as "you".

1. You may copy and distribute verbatim copies of the Program's source code as you receive it, in any medium, provided that you conspicuously and appropriately publish on each copy an appropriate copyright notice and disclaimer of warranty; keep intact all the notices that refer to this General Public License and to the absence of any warranty; and give any other recipients of the Program a copy of this General Public License along with the Program. You may charge a fee for the physical act of transferring a copy.

2. You may modify your copy or copies of the Program or any portion of it, and copy and distribute such modifications under the terms of Paragraph 1 above, provided that you also do the following:

a) cause the modified files to carry prominent notices stating that you changed the files and the date of any change; and

b) cause the whole of any work that you distribute or publish, that in whole or in part contains the Program or any part thereof, either with or without modifications, to be licensed at no charge to all third parties under the terms of this General Public License (except that you may choose to grant warranty protection to some or all third parties, at your option).

c) If the modified program normally reads commands interactively when run, you must cause it, when started running for such interactive use in the simplest and most usual way, to print or display an announcement including an appropriate copyright notice and a notice that there is no warranty (or else, saying that you provide a warranty) and that users may redistribute the program under these conditions, and telling the user how to view a copy of this General Public License.

d) You may charge a fee for the physical act of transferring a copy, and you may at your option offer warranty protection in exchange for a fee.

Mere aggregation of another independent work with the Program (or its derivative) on a volume of a storage or distribution medium does not bring the other work under the scope of these terms.

3. You may copy and distribute the Program (or a portion or derivative of it, under Paragraph 2) in object code or executable form under the terms of Paragraphs 1 and 2 above provided that you also do one of the following:

a) accompany it with the complete corresponding machine-readable source code, which must be distributed under the terms of Paragraphs 1 and 2 above; or,

b) accompany it with a written offer, valid for at least three years, to give any third party free (except for a nominal charge for the cost of distribution) a complete machine-readable copy of the corresponding source code, to be distributed under the terms of Paragraphs 1 and 2 above; or,

c) accompany it with the information you received as to where the corresponding source code may be obtained. (This alternative is allowed only for noncommercial distribution and only if you received the program in object code or executable form alone.)

Source code for a work means the preferred form of the work for making modifications to it. For an executable file, complete source code means all the source code for all modules it contains; but, as a special exception, it need not include source code for modules which are standard libraries that accompany the operating system on which the executable file runs, or for standard header files or definitions files that accompany that operating system.

4. You may not copy, modify, sublicense, distribute or transfer the Program except as expressly provided under this General Public License. Any attempt otherwise to copy, modify, sublicense, distribute or transfer the Program is void, and will automatically terminate your rights to use the Program under this License. However, parties who have received copies, or rights to use copies, from you under this General Public License will not have their licenses terminated so long as such parties remain in full compliance.

5. By copying, distributing or modifying the Program (or any work based on the Program) you indicate your acceptance of this license to do so, and all its terms and conditions.

6. Each time you redistribute the Program (or any work based on the Program), the recipient automatically receives a license from the original licensor to copy, distribute or modify the Program subject to these terms and conditions. You may not impose any further restrictions on the recipients' exercise of the rights granted herein.

7. The Free Software Foundation may publish revised and/or new versions of the General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Program specifies a version number of the license which applies to it and "any later version", you have the option of following the terms and conditions either of that version or of any later version published by the Free Software Foundation. If the Program does not specify a version number of the license, you may choose any version ever published by the Free Software Foundation.

8. If you wish to incorporate parts of the Program into other free programs whose distribution conditions are different, write to the author to ask for permission. For software which is copyrighted by the Free Software Foundation, write to the Free Software Foundation; we sometimes make exceptions for this. Our decision will be guided by the two goals of preserving the free status of all derivatives of our free software and of promoting the sharing and reuse of software generally.

NO WARRANTY

9. BECAUSE THE PROGRAM IS LICENSED FREE OF CHARGE, THERE IS NO WARRANTY FOR THE PROGRAM, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE

THE PROGRAM "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE PROGRAM IS WITH YOU. SHOULD THE PROGRAM PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

10. IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY AND/OR REDISTRIBUTE THE PROGRAM AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE PROGRAM (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE PROGRAM TO OPERATE WITH ANY OTHER PROGRAMS), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

END OF TERMS AND CONDITIONS

Appendix: How to Apply These Terms to Your New Programs

If you develop a new program, and you want it to be of the greatest possible use to humanity, the best way to achieve this is to make it free software which everyone can redistribute and change under these

terms.

To do so, attach the following notices to the program. It is safest to attach them to the start of each source file to most effectively convey the exclusion of warranty; and each file should have at least the "copyright" line and a pointer to where the full notice is found.

```
<one line to give the program's name and a brief idea of what it does.>  
Copyright (C) 19yy <name of author>
```

This program is free software; you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation; either version 1, or (at your option) any later version.

This program is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details.

You should have received a copy of the GNU General Public License along with this program; if not, write to the Free Software Foundation, Inc., 51 Franklin Street, Fifth Floor, Boston MA 02110-1301 USA

Also add information on how to contact you by electronic and paper mail.

If the program is interactive, make it output a short notice like this when it starts in an interactive mode:

```
Gnomovision version 69, Copyright (C) 19xx name of author  
Gnomovision comes with ABSOLUTELY NO WARRANTY; for details type `show w'.  
This is free software, and you are welcome to redistribute it  
under certain conditions; type `show c' for details.
```

The hypothetical commands `show w' and `show c' should show the appropriate parts of the General Public License.

Of course, the commands you use may be called something other than `show w' and `show c'; they could even be mouse-clicks or menu items--whatever suits your program.

You should also get your employer (if you work as a programmer) or your school, if any, to sign a "copyright disclaimer" for the program, if necessary. Here a sample; alter the names:

Yoyodyne, Inc., hereby disclaims all copyright interest in the

program 'Gnomovision' (a program to direct compilers to make passes at assemblers) written by James Hacker.

<signature of Ty Coon>, 1 April 1989
Ty Coon, President of Vice

That's all there is to it!

GNU GENERAL PUBLIC LICENSE
Version 3, 29 June 2007

Copyright (C) 2007 Free Software Foundation, Inc. <<http://fsf.org/>>
Everyone is permitted to copy and distribute verbatim copies of this license document, but changing it is not allowed.

Preamble

The GNU General Public License is a free, copyleft license for software and other kinds of works.

The licenses for most software and other practical works are designed to take away your freedom to share and change the works. By contrast, the GNU General Public License is intended to guarantee your freedom to share and change all versions of a program--to make sure it remains free software for all its users. We, the Free Software Foundation, use the GNU General Public License for most of our software; it applies also to any other work released this way by its authors. You can apply it to your programs, too.

When we speak of free software, we are referring to freedom, not price. Our General Public Licenses are designed to make sure that you have the freedom to distribute copies of free software (and charge for them if you wish), that you receive source code or can get it if you want it, that you can change the software or use pieces of it in new free programs, and that you know you can do these things.

To protect your rights, we need to prevent others from denying you these rights or asking you to surrender the rights. Therefore, you have certain responsibilities if you distribute copies of the software, or if you modify it: responsibilities to respect the freedom of others.

For example, if you distribute copies of such a program, whether gratis or for a fee, you must pass on to the recipients the same freedoms that you received. You must make sure that they, too, receive or can get the source code. And you must show them these terms so they know their rights.

Developers that use the GNU GPL protect your rights with two steps:

(1)

assert copyright on the software, and (2) offer you this License giving you legal permission to copy, distribute and/or modify it.

For the developers' and authors' protection, the GPL clearly explains that there is no warranty for this free software. For both users' and authors' sake, the GPL requires that modified versions be marked as changed, so that their problems will not be attributed erroneously to authors of previous versions.

Some devices are designed to deny users access to install or run modified versions of the software inside them, although the manufacturer can do so. This is fundamentally incompatible with the aim of protecting users' freedom to change the software. The systematic pattern of such abuse occurs in the area of products for individuals to use, which is precisely where it is most unacceptable. Therefore, we have designed this version of the GPL to prohibit the practice for those products. If such problems arise substantially in other domains, we stand

ready to extend this provision to those domains in future versions of the GPL, as needed to protect the freedom of users.

Finally, every program is threatened constantly by software patents. States should not allow patents to restrict development and use of software on general-purpose computers, but in those that do, we wish to avoid the special danger that patents applied to a free program could make it effectively proprietary. To prevent this, the GPL assures that patents cannot be used to render the program non-free.

The precise terms and conditions for copying, distribution and modification follow.

TERMS AND CONDITIONS

0. Definitions.

"This License" refers to version 3 of the GNU General Public License.

"Copyright" also means copyright-like laws that apply to other kinds of works, such as semiconductor masks.

"The Program" refers to any copyrightable work licensed under this License. Each licensee is addressed as "you". "Licensees" and "recipients" may be individuals or organizations.

To "modify" a work means to copy from or adapt all or part of the work in a fashion requiring copyright permission, other than the making of an

exact copy. The resulting work is called a "modified version" of the earlier work or a work "based on" the earlier work.

A "covered work" means either the unmodified Program or a work based on the Program.

To "propagate" a work means to do anything with it that, without permission, would make you directly or secondarily liable for infringement under applicable copyright law, except executing it on a computer or modifying a private copy. Propagation includes copying, distribution (with or without modification), making available to the public, and in some countries other activities as well.

To "convey" a work means any kind of propagation that enables other parties to make or receive copies. Mere interaction with a user through a computer network, with no transfer of a copy, is not conveying.

An interactive user interface displays "Appropriate Legal Notices" to the extent that it includes a convenient and prominently visible feature that (1) displays an appropriate copyright notice, and (2) tells the user that there is no warranty for the work (except to the extent that warranties are provided), that licensees may convey the work under this License, and how to view a copy of this License. If the interface presents a list of user commands or options, such as a menu, a prominent item in the list meets this criterion.

1. Source Code.

The "source code" for a work means the preferred form of the work for making modifications to it. "Object code" means any non-source form of a work.

A "Standard Interface" means an interface that either is an official standard defined by a recognized standards body, or, in the case of interfaces specified for a particular programming language, one that is widely used among developers working in that language.

The "System Libraries" of an executable work include anything, other than the work as a whole, that (a) is included in the normal form of packaging a Major Component, but which is not part of that Major Component, and (b) serves only to enable use of the work with that Major Component, or to implement a Standard Interface for which an implementation is available to the public in source code form. A "Major Component", in this context, means a major essential component (kernel, window system, and so on) of the specific operating system (if any) on which the executable work runs, or a compiler used to

produce the work, or an object code interpreter used to run it.

The "Corresponding Source" for a work in object code form means all the source code needed to generate, install, and (for an executable work) run the object code and to modify the work, including scripts to control those activities. However, it does not include the work's System Libraries, or general-purpose tools or generally available free programs which are used unmodified in performing those activities but which are not part of the work. For example, Corresponding Source includes interface definition files associated with source files for the work, and the source code for shared libraries and dynamically linked subprograms that the work is specifically designed to require, such as by intimate data communication or control flow between those subprograms and other parts of the work.

The Corresponding Source need not include anything that users can regenerate automatically from other parts of the Corresponding Source.

The Corresponding Source for a work in source code form is that same work.

2. Basic Permissions.

All rights granted under this License are granted for the term of copyright on the Program, and are irrevocable provided the stated conditions are met. This License explicitly affirms your unlimited permission to run the unmodified Program. The output from running a covered work is covered by this License only if the output, given its content, constitutes a covered work. This License acknowledges your rights of fair use or other equivalent, as provided by copyright law.

You may make, run and propagate covered works that you do not convey, without conditions so long as your license otherwise remains in force. You may convey covered works to others for the sole purpose of having them make modifications exclusively for you, or provide you with facilities for running those works, provided that you comply with the terms of this License in conveying all material for which you do not control copyright. Those thus making or running the covered works for you must do so exclusively on your behalf, under your direction and control, on terms that prohibit them from making any copies of your copyrighted material outside their relationship with you.

Conveying under any other circumstances is permitted solely under the conditions stated below. Sublicensing is not allowed;

section 10
makes it unnecessary.

3. Protecting Users' Legal Rights From Anti-Circumvention Law.

No covered work shall be deemed part of an effective technological measure under any applicable law fulfilling obligations under article 11 of the WIPO copyright treaty adopted on 20 December 1996, or similar laws prohibiting or restricting circumvention of such measures.

When you convey a covered work, you waive any legal power to forbid circumvention of technological measures to the extent such circumvention is effected by exercising rights under this License with respect to the covered work, and you disclaim any intention to limit operation or modification of the work as a means of enforcing, against the work's users, your or third parties' legal rights to forbid circumvention of technological measures.

4. Conveying Verbatim Copies.

You may convey verbatim copies of the Program's source code as you receive it, in any medium, provided that you conspicuously and appropriately
publish on each copy an appropriate copyright notice;
keep intact all notices stating that this License and any
non-permissive terms added in accord with section 7 apply to the code;
keep intact all notices of the absence of any warranty; and give all
recipients a copy of this License along with the Program.

You may charge any price or no price for each copy that you convey, and you may offer support or warranty protection for a fee.

5. Conveying Modified Source Versions.

You may convey a work based on the Program, or the modifications to produce it from the Program, in the form of source code under the terms of section 4, provided that you also meet all of these conditions:

- a) The work must carry prominent notices stating that you modified it, and giving a relevant date.
- b) The work must carry prominent notices stating that it is released under this License and any conditions added under section 7. This requirement modifies the requirement in section 4 to
"keep intact all notices".

c) You must license the entire work, as a whole, under this License to anyone who comes into possession of a copy. This License will therefore apply, along with any applicable section 7 additional terms, to the whole of the work, and all its parts, regardless of how they are packaged. This License gives no permission to license the work in any other way, but it does not invalidate such permission if you have separately received it.

d) If the work has interactive user interfaces, each must display Appropriate Legal Notices; however, if the Program has interactive interfaces that do not display Appropriate Legal Notices, your work need not make them do so.

A compilation of a covered work with other separate and independent works, which are not by their nature extensions of the covered work, and which are not combined with it such as to form a larger program, in or on a volume of a storage or distribution medium, is called an "aggregate" if the compilation and its resulting copyright are not used to limit the access or legal rights of the compilation's users beyond what the individual works permit. Inclusion of a covered work in an aggregate does not cause this License to apply to the other parts of the aggregate.

6. Conveying Non-Source Forms.

You may convey a covered work in object code form under the terms of sections 4 and 5, provided that you also convey the machine-readable Corresponding Source under the terms of this License, in one of these ways:

a) Convey the object code in, or embodied in, a physical product (including a physical distribution medium), accompanied by the Corresponding Source fixed on a durable physical medium customarily used for software interchange.

b) Convey the object code in, or embodied in, a physical product (including a physical distribution medium), accompanied by a written offer, valid for at least three years and valid for as long as you offer spare parts or customer support for that product model, to give anyone who possesses the object code either (1) a copy of the Corresponding Source for all the software in the product that is covered by this License, on a durable physical medium customarily used for software interchange, for a price no more than your reasonable cost of physically performing this conveying of source, or (2) access to copy the Corresponding Source from a network server at no charge.

c) Convey individual copies of the object code with a copy of the written offer to provide the Corresponding Source. This alternative is allowed only occasionally and noncommercially, and only if you received the object code with such an offer, in accord with subsection 6b.

d) Convey the object code by offering access from a designated place (gratis or for a charge), and offer equivalent access to the Corresponding Source in the same way through the same place at no further charge. You need not require recipients to copy the Corresponding Source along with the object code. If the place to copy the object code is a network server, the Corresponding Source may be on a different server (operated by you or a third party) that supports equivalent copying facilities, provided you maintain clear directions next to the object code saying where to find the Corresponding Source. Regardless of what server hosts the Corresponding Source, you remain obligated to ensure that it is available for as long as needed to satisfy these requirements.

e) Convey the object code using peer-to-peer transmission, provided you inform other peers where the object code and Corresponding Source of the work are being offered to the general public at no charge under subsection 6d.

A separable portion of the object code, whose source code is excluded from the Corresponding Source as a System Library, need not be included in conveying the object code work.

A "User Product" is either (1) a "consumer product", which means any tangible personal property which is normally used for personal, family, or household purposes, or (2) anything designed or sold for incorporation into a dwelling. In determining whether a product is a consumer product, doubtful cases shall be resolved in favor of coverage. For a particular product received by a particular user, "normally used" refers to a typical or common use of that class of product, regardless of the status of the particular user or of the way in which the particular user actually uses, or expects or is expected to use, the product. A product is a consumer product regardless of whether the product has substantial commercial, industrial or non-consumer uses, unless such uses represent the only significant mode of use of the product.

"Installation Information" for a User Product means any methods, procedures, authorization keys, or other information required to install and execute modified versions of a covered work in that User Product from

a modified version of its Corresponding Source. The information must suffice to ensure that the continued functioning of the modified object code is in no case prevented or interfered with solely because modification has been made.

If you convey an object code work under this section in, or with, or specifically for use in, a User Product, and the conveying occurs as part of a transaction in which the right of possession and use of the User Product is transferred to the recipient in perpetuity or for a fixed term (regardless of how the transaction is characterized), the Corresponding Source conveyed under this section must be accompanied by the Installation Information. But this requirement does not apply if neither you nor any third party retains the ability to install modified object code on the User Product (for example, the work has been installed in ROM).

The requirement to provide Installation Information does not include a requirement to continue to provide support service, warranty, or updates for a work that has been modified or installed by the recipient, or for the User Product in which it has been modified or installed. Access to a network may be denied when the modification itself materially and adversely affects the operation of the network or violates the rules and protocols for communication across the network.

Corresponding Source conveyed, and Installation Information provided, in accord with this section must be in a format that is publicly documented (and with an implementation available to the public in source code form), and must require no special password or key for unpacking, reading or copying.

7. Additional Terms.

"Additional permissions" are terms that supplement the terms of this License by making exceptions from one or more of its conditions. Additional permissions that are applicable to the entire Program shall be treated as though they were included in this License, to the extent that they are valid under applicable law. If additional permissions apply only to part of the Program, that part may be used separately under those permissions, but the entire Program remains governed by this License without regard to the additional permissions.

When you convey a copy of a covered work, you may at your option remove any additional permissions from that copy, or from any part of it. (Additional permissions may be written to require their own removal in certain cases when you modify the work.) You may place additional permissions on material, added by you to a covered work,

for which you have or can give appropriate copyright permission.

Notwithstanding any other provision of this License, for material you add to a covered work, you may (if authorized by the copyright holders of that material) supplement the terms of this License with terms:

- a) Disclaiming warranty or limiting liability differently from the terms of sections 15 and 16 of this License; or
- b) Requiring preservation of specified reasonable legal notices or author attributions in that material or in the Appropriate Legal Notices displayed by works containing it; or
- c) Prohibiting misrepresentation of the origin of that material, or requiring that modified versions of such material be marked in reasonable ways as different from the original version; or
- d) Limiting the use for publicity purposes of names of licensors or authors of the material; or
- e) Declining to grant rights under trademark law for use of some trade names, trademarks, or service marks; or
- f) Requiring indemnification of licensors and authors of that material by anyone who conveys the material (or modified versions of it) with contractual assumptions of liability to the recipient, for any liability that these contractual assumptions directly impose on those licensors and authors.

All other non-permissive additional terms are considered "further restrictions" within the meaning of section 10. If the Program as you received it, or any part of it, contains a notice stating that it is governed by this License along with a term that is a further restriction, you may remove that term. If a license document contains a further restriction but permits relicensing or conveying under this License, you may add to a covered work material governed by the terms of that license document, provided that the further restriction does not survive such relicensing or conveying.

If you add terms to a covered work in accord with this section, you must place, in the relevant source files, a statement of the additional terms that apply to those files, or a notice indicating where to find the applicable terms.

Additional terms, permissive or non-permissive, may be stated in the form of a separately written license, or stated as exceptions;

the above requirements apply either way.

8. Termination.

You may not propagate or modify a covered work except as expressly provided under this License. Any attempt otherwise to propagate or modify it is void, and will automatically terminate your rights under this License (including any patent licenses granted under the third paragraph of section 11).

However, if you cease all violation of this License, then your license from a particular copyright holder is reinstated (a) provisionally, unless and until the copyright holder explicitly and finally terminates your license, and (b) permanently, if the copyright holder fails to notify you of the violation by some reasonable means prior to 60 days after the cessation.

Moreover, your license from a particular copyright holder is reinstated permanently if the copyright holder notifies you of the violation by some reasonable means, this is the first time you have received notice of violation of this License (for any work) from that copyright holder, and you cure the violation prior to 30 days after your receipt of the notice.

Termination of your rights under this section does not terminate the licenses of parties who have received copies or rights from you under this License. If your rights have been terminated and not permanently reinstated, you do not qualify to receive new licenses for the same material under section 10.

9. Acceptance Not Required for Having Copies.

You are not required to accept this License in order to receive or run a copy of the Program. Ancillary propagation of a covered work occurring solely as a consequence of using peer-to-peer transmission to receive a copy likewise does not require acceptance. However, nothing other than this License grants you permission to propagate or modify any covered work. These actions infringe copyright if you do not accept this License. Therefore, by modifying or propagating a covered work, you indicate your acceptance of this License to do so.

10. Automatic Licensing of Downstream Recipients.

Each time you convey a covered work, the recipient automatically receives a license from the original licensors, to run, modify and

propagate that work, subject to this License. You are not responsible for enforcing compliance by third parties with this License.

An "entity transaction" is a transaction transferring control of an organization, or substantially all assets of one, or subdividing an organization, or merging organizations. If propagation of a covered work results from an entity transaction, each party to that transaction who receives a copy of the work also receives whatever licenses to the work the party's predecessor in interest had or could give under the previous paragraph, plus a right to possession of the Corresponding Source of the work from the predecessor in interest, if the predecessor has it or can get it with reasonable efforts.

You may not impose any further restrictions on the exercise of the rights

granted or affirmed under this License. For example, you may not impose a license fee, royalty, or other charge for exercise of rights granted under this License, and you may not initiate litigation (including a cross-claim or counterclaim in a lawsuit) alleging that any patent claim is infringed by making, using, selling, offering for sale, or importing the Program or any portion of it.

11. Patents.

A "contributor" is a copyright holder who authorizes use under this License of the Program or a work on which the Program is based. The work thus licensed is called the contributor's "contributor version".

A contributor's "essential patent claims" are all patent claims owned or controlled by the contributor, whether already acquired or hereafter acquired, that would be infringed by some manner, permitted by this License, of making, using, or selling its contributor version, but do not include claims that would be infringed only as a consequence of further modification of the contributor version. For purposes of this definition, "control" includes the right to grant patent sublicenses in a manner consistent with the requirements of this License.

Each contributor grants you a non-exclusive, worldwide, royalty-free patent license under the contributor's essential patent claims, to make, use, sell, offer for sale, import and otherwise run, modify and propagate the contents of its contributor version.

In the following three paragraphs, a "patent license" is any express agreement or commitment, however denominated, not to enforce a patent (such as an express permission to practice a patent or covenant not to sue for patent infringement). To "grant" such a patent license to a

party means to make such an agreement or commitment not to enforce a patent against the party.

If you convey a covered work, knowingly relying on a patent license, and the Corresponding Source of the work is not available for anyone to copy, free of charge and under the terms of this

License, through a publicly available network server or other readily accessible means, then you must either (1) cause the Corresponding Source to be so available, or (2) arrange to deprive yourself of the benefit of the patent license for this particular work, or (3) arrange, in a manner consistent with the requirements of this License, to extend the patent license to downstream recipients. "Knowingly relying" means you have actual knowledge that, but for the patent license, your conveying the covered work in a country, or your recipient's use of the covered work in a country, would infringe one or more identifiable patents in that country that you have reason to believe are valid.

If, pursuant to or in connection with a single transaction or arrangement, you convey, or propagate by procuring conveyance of, a covered work, and grant a patent license to some of the parties receiving the covered work authorizing them to use, propagate, modify or convey a specific copy of the covered work, then the patent license you grant is automatically extended to all recipients of the covered work and works based on it.

A patent license is "discriminatory" if it does not include within the scope of its coverage, prohibits the exercise of, or is conditioned on the non-exercise of one or more of the rights that are specifically granted under this License. You may not convey a covered work if you are a party to an arrangement with a third party that is in the business of distributing software, under which you make payment to the third party based on the extent of your activity of conveying the work, and under which the third party grants, to any of the parties who would receive the covered work from you, a discriminatory patent license (a) in connection with copies of the covered work conveyed by you (or copies made from those copies), or (b) primarily for and in connection with specific products or compilations that contain the covered work, unless you entered into that arrangement, or that patent license was granted, prior to 28 March 2007.

Nothing in this License shall be construed as excluding or limiting any implied license or other defenses to infringement that may otherwise be available to you under applicable patent law.

12. No Surrender of Others' Freedom.

If conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot convey a covered work so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not convey it at all. For example, if you agree to terms that obligate you to collect a royalty for further conveying from those to whom you convey the Program, the only way you could satisfy both those terms and this License would be to refrain entirely from conveying the Program.

13. Use with the GNU Affero General Public License.

Notwithstanding any other provision of this License, you have permission to link or combine any covered work with a work licensed under version 3 of the GNU Affero General Public License into a single combined work, and to convey the resulting work. The terms of this License will continue to apply to the part which is the covered work, but the special requirements of the GNU Affero General Public License, section 13, concerning interaction through a network will apply to the combination as such.

14. Revised Versions of this License.

The Free Software Foundation may publish revised and/or new versions of the GNU General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Program specifies that a certain numbered version of the GNU General Public License "or any later version" applies to it, you have the option of following the terms and conditions either of that numbered version or of any later version published by the Free Software Foundation. If the Program does not specify a version number of the GNU General Public License, you may choose any version ever published by the Free Software Foundation.

If the Program specifies that a proxy can decide which future versions of the GNU General Public License can be used, that proxy's public statement of acceptance of a version permanently authorizes you to choose that version for the Program.

Later license versions may give you additional or different permissions. However, no additional obligations are imposed on any author or copyright holder as a result of your choosing to follow a later version.

15. Disclaimer of Warranty.

THERE IS NO WARRANTY FOR THE PROGRAM, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE PROGRAM "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE PROGRAM IS WITH YOU. SHOULD THE PROGRAM PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

16. Limitation of Liability.

IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MODIFIES AND/OR CONVEYS THE PROGRAM AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE PROGRAM (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE PROGRAM TO OPERATE WITH ANY OTHER PROGRAMS), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

17.

Interpretation of Sections 15 and 16.

If the disclaimer of warranty and limitation of liability provided above cannot be given local legal effect according to their terms, reviewing courts shall apply local law that most closely approximates an absolute waiver of all civil liability in connection with the Program, unless a warranty or assumption of liability accompanies a copy of the Program in return for a fee.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Programs

If you develop a new program, and you want it to be of the greatest possible use to the public, the best way to achieve this is to make it free software which everyone can redistribute and change under these terms.

To do so, attach the following notices to the program. It is safest to attach them to the start of each source file to most effectively state the exclusion of warranty; and each file should have at least the "copyright" line and a pointer to where

the full notice is found.

<one line to give the program's name and a brief idea of what it does.>
Copyright (C) <year> <name of author>

This program is free software: you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation, either version 3 of the License, or (at your option) any later version.

This program is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details.

You should have received a copy of the GNU General Public License along with this program. If not, see <<http://www.gnu.org/licenses/>>.

Also add information on how to contact you by electronic and paper mail.

If the program does terminal interaction, make it output a short notice like this when it starts in an interactive mode:

```
<program> Copyright (C) <year> <name of author>  
This program comes with ABSOLUTELY NO WARRANTY; for details type `show w'.  
This is free software, and you are welcome to redistribute it  
under certain conditions; type `show c' for details.
```

The hypothetical commands `show w' and `show c' should show the appropriate parts of the General Public License. Of course, your program's commands might be different; for a GUI interface, you would use an "about box".

You should also get your employer (if you work as a programmer) or school, if any, to sign a "copyright disclaimer" for the program, if necessary. For more information on this, and how to apply and follow the GNU GPL, see <<http://www.gnu.org/licenses/>>.

The GNU General Public License does not permit incorporating your program into proprietary programs. If your program is a subroutine library, you may consider it more useful to permit linking proprietary applications with the library. If this is what you want to do, use the GNU Lesser General Public License instead of this License. But first, please read <<http://www.gnu.org/philosophy/why-not-lgpl.html>>.

The "Artistic License"

Preamble

The intent of this document is to state the conditions under which a Package may be copied, such that the Copyright Holder maintains some semblance of artistic control over the development of the package, while giving the users of the package the right to use and distribute the Package in a more-or-less customary fashion, plus the right to make reasonable modifications.

Definitions:

"Package" refers to the collection of files distributed by the Copyright Holder, and derivatives of that collection of files created through textual modification.

"Standard Version" refers to such a Package if it has not been modified, or has been modified in accordance with the wishes of the Copyright Holder as specified below.

"Copyright Holder" is whoever is named in the copyright or copyrights for the package.

"You" is you, if you're thinking about copying or distributing this Package.

"Reasonable copying fee" is whatever you can justify on the basis of media cost, duplication charges, time of people involved, and so on. (You will not be required to justify it to the Copyright Holder, but only to the computing community at large as a market that must bear the fee.)

"Freely Available" means that no fee is charged for the item itself, though there may be fees involved in handling the item. It also means that recipients of the item may redistribute it under the same conditions they received it.

1. You may make and give away verbatim copies of the source form of the Standard Version of this Package without restriction, provided that you duplicate all of the original copyright notices and associated disclaimers.
2. You may apply bug fixes, portability fixes and other modifications derived from the Public Domain or from the Copyright Holder. A Package modified in such a way shall still be considered the Standard Version.

3. You may otherwise modify your copy of this Package in any way, provided that you insert a prominent notice in each changed file stating how and when you changed that file, and provided that you do at least ONE of the following:

a) place your modifications in the Public Domain or otherwise make them Freely Available, such as by posting said modifications to Usenet or an equivalent medium, or placing the modifications on a major archive site such as uunet.uu.net, or by allowing the Copyright Holder to include your modifications in the Standard Version of the Package.

b) use the modified Package only within your corporation or organization.

c) rename any non-standard executables so the names do not conflict with standard executables, which must also be provided, and provide a separate manual page for each non-standard executable that clearly documents how it differs from the Standard Version.

d) make other distribution arrangements with the Copyright Holder.

4. You may distribute the programs of this Package in object code or executable form, provided that you do at least ONE of the following:

a) distribute a Standard Version of the executables and library files, together with instructions (in the manual page or equivalent) on where to get the Standard Version.

b) accompany the distribution with the machine-readable source of the Package with your modifications.

c) give non-standard executables non-standard names, and clearly document the differences in manual pages (or equivalent), together with instructions on where to get the Standard Version.

d) make other distribution arrangements with the Copyright Holder.

5. You may charge a reasonable copying fee for any distribution of this Package. You may charge any fee you choose for support of this Package. You may not charge a fee for this Package itself. However, you may distribute this Package in aggregate with other (possibly commercial) programs as part of a larger (possibly commercial) software distribution provided

that you do not advertise this Package as a product of your own. You may embed this Package's interpreter within an executable of yours (by linking); this shall be construed as a mere form of aggregation, provided that the complete Standard Version of the

interpreter is so embedded.

6. The scripts and library files supplied as input to or produced as output from the programs of this Package do not automatically fall under the copyright of this Package, but belong to whoever generated them, and may be sold commercially, and may be aggregated with this Package. If such scripts or library files are aggregated with this Package via the so-called "undump" or "unexec" methods of producing a binary executable image, then distribution of such an image shall neither be construed as a distribution of this Package nor shall it fall under the restrictions of Paragraphs 3 and 4, provided that you do not represent such an executable image as a Standard Version of this Package.

7. C subroutines

(or comparably compiled subroutines in other languages) supplied by you and linked into this Package in order to emulate subroutines and variables of the language defined by this Package shall not be considered part of this Package, but are the equivalent of input as in Paragraph 6, provided these subroutines do not change the language in any way that would cause it to fail the regression tests for the language.

8. Aggregation of this Package with a commercial distribution is always permitted provided that the use of this Package is embedded; that is, when no overt attempt is made to make this Package's interfaces visible to the end user of the commercial distribution. Such use shall not be construed as a distribution of this Package.

9. The name of the Copyright Holder may not be used to endorse or promote products derived from this software without specific prior written permission.

10. THIS PACKAGE IS PROVIDED "AS IS" AND WITHOUT ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, WITHOUT LIMITATION, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE.

The End

1.62 libgrypt 1.8.1-4ubuntu1.3

1.62.1 Available under license :

This package was debianized by Ivo Timmermans <ivo@debian.org> on Fri, 3 Aug 2001 10:02:38 +0200.

It was taken over by Matthias Urlichs <smurf@debian.org>, and is now maintained by Andreas Metzler <ametzler@debian.org> Eric Dorland <eric@debian.org>, James Westby <jw+debian@jameswestby.net>

It was downloaded from <https://ftp.gnupg.org/gcrypt/libgcrypt/>.

Up to end of 2012 libgcrypt copyright was owned solely by FSF, since then contributions without copyright assignment to the FSF have been integrated.

Upstream Authors (from AUTHORS)

8X-----

List of Copyright holders

=====

Copyright (C) 1989,1991-2017 Free Software Foundation, Inc.
Copyright (C) 1994 X Consortium
Copyright (C) 1996 L. Peter Deutsch
Copyright (C) 1997 Werner Koch
Copyright (C) 1998 The Internet Society
Copyright (C) 1996-1999 Peter Gutmann, Paul Kendall, and Chris Wedgwood
Copyright (C) 1996-2006 Peter Gutmann, Matt Thomlinson and Blake Coverett
Copyright (C) 2003 Nikos Mavroyanopoulos
Copyright (C) 2006-2007 NTT (Nippon Telegraph and Telephone Corporation)
Copyright (C) 2012-2017 g10 Code GmbH
Copyright (C) 2012 Simon Josefsson, Niels Mller
Copyright (c) 2012 Intel Corporation
Copyright (C) 2013 Christian Grothoff
Copyright (C) 2013-2017 Jussi Kivilinna
Copyright (C) 2013-2014 Dmitry Eremin-Solenikov
Copyright (C) 2014 Stephan Mueller
Copyright (C) 2017 Bundesamt fr Sicherheit in der Informationstechnik

Authors with a FSF copyright assignment

=====

LIBGCRYPT Werner Koch 2001-06-07

Assigns past and future changes.

Assignment for future changes terminated on 2012-12-04.

wk@gnupg.org

Designed and implemented Libgcrypt.

GNUPG Matthew Skala 1998-08-10

Disclaims changes.

mskala@ansuz.sooke.bc.ca

Wrote cipher/twofish.c.

GNUPG Natural Resources Canada 1998-08-11

Disclaims changes by Matthew Skala.

GNUPG Michael Roth Germany 1998-09-17

Assigns changes.

mroth@nessie.de

Wrote

cipher/des.c.

Changes and bug fixes all over the place.

GNUPG Niklas Hernaes 1998-09-18

Disclaims changes.

nh@df.lth.se

Weak key patches.

GNUPG Rmi Guyomarch 1999-05-25

Assigns past and future changes. (g10/compress.c, g10/encr-data.c,
g10/free-packet.c, g10/mdfilter.c, g10/plaintext.c, util/iobuf.c)

rguyom@mail.dotcom.fr

ANY g10 Code GmbH 2001-06-07

Assignment for future changes terminated on 2012-12-04.

Code marked with ChangeLog entries of g10 Code employees.

LIBGCRYPT Timo Schulz 2001-08-31

Assigns past and future changes.

twoaday@freakmail.de

LIBGCRYPT Simon Josefsson 2002-10-25

Assigns past and future changes to FSF (cipher/{md4,crc}.c, CTR mode,
CTS/MAC flags, self test improvements)

simon@josefsson.org

LIBGCRYPT Moritz Schulte 2003-04-17

Assigns past and future changes.

moritz@g10code.com

GNUTLS Nikolaos Mavrogiannopoulos 2003-11-22

nmav@gnutls.org

Original code for cipher/rfc2268.c.

LIBGCRYPT The Written Word 2005-04-15

Assigns

past and future changes. (new: src/libcrypt.pc.in,
src/Makefile.am, src/secmem.c, mpi/hppa1.1/mpih-mul3.S,
mpi/hppa1.1/udiv-qrnd.S, mpi/hppa1.1/mpih-mul2.S,
mpi/hppa1.1/mpih-mul1.S, mpi/Makefile.am, tests/prime.c,
tests/register.c, tests/ac.c, tests/basic.c, tests/tsexp.c,
tests/keygen.c, tests/pubkey.c, configure.ac, acinclude.m4)

LIBGCRYPT Brad Hards 2006-02-09
Assigns Past and Future Changes
bradh@frogmouth.net
(Added OFB mode. Changed cipher/cipher.c, test/basic.c doc/gcrypt.tex.
added SHA-224, changed cipher/sha256.c, added HMAC tests.)

LIBGCRYPT Hye-Shik Chang 2006-09-07
Assigns Past and Future Changes
perky@freebsd.org
(SEED cipher)

LIBGCRYPT Werner Dittmann 2009-05-20
Assigns Past and Future Changes
werner.dittmann@t-online.de
(mpi/amd64, tests/mpitests.c)

GNUPG David Shaw
Assigns past and future changes.
dshaw@jabberwocky.com
(cipher/camellia-glue.c and related stuff)

LIBGCRYPT Andrey Jivsov 2010-12-09
Assigns
Past and Future Changes
openpgp@brainhub.org
(cipher/ecc.c and related files)

LIBGCRYPT Ulrich Mller 2012-02-15
Assigns Past and Future Changes
ulm@gentoo.org
(Changes to cipher/idea.c and related files)

LIBGCRYPT Vladimir Serbinenko 2012-04-26
Assigns Past and Future Changes
phcoder@gmail.com
(cipher/serpent.c)

Authors with a DCO

=====

Andrei Scherer <andsch@inbox.com>
2014-08-22:BF7CEF794F9.000003F0andsch@inbox.com:

Christian Aistleitner <christian@quelltextlich.at>
2013-02-26:20130226110144.GA12678@quelltextlich.at:

Christian Grothoff <christian@grothoff.org>

2013-03-21:514B5D8A.6040705@grothoff.org:

Dmitry Eremin-Solenikov <dbaryshkov@gmail.com>

2013-07-13:20130713144407.GA27334@fangorn.rup.mentorg.com:

Dmitry Kasatkin <dmitry.kasatkin@intel.com>

2012-12-14:50CAE2DB.80302@intel.com:

Jrmie Courges-Anglas <jca@wxcvbn.org>

2016-05-26:87bn3ssqg0.fsf@ritchie.wxcvbn.org

Jussi Kivilinna <jussi.kivilinna@mbnet.fi>

2012-11-15:20121115172331.150537dzb5i6jmy8@www.dalek.fi:

Jussi

Kivilinna <jussi.kivilinna@iki.fi>

2013-05-06:5186720A.4090101@iki.fi:

Markus Teich <markus dot teich at stusta dot mhn dot de>

2014-10-08:20141008180509.GA2770@trolle:

Mathias L. Baumann <mathias.baumann at sociomantic.com>

2017-01-30:07c06d79-0828-b564-d604-fd16c7c86ebe@sociomantic.com:

Milan Broz <gmazyland@gmail.com>

2014-01-13:52D44CC6.4050707@gmail.com:

Peter Wu <peter@lekensteyn.nl>

2015-07-22:20150722191325.GA8113@al:

Rafal Carr <funman@videolan.org>

2012-04-20:4F91988B.1080502@videolan.org:

Sergey V. <sftp.mtuci@gmail.com>

2013-11-07:2066221.5IYa7Yq760@darkstar:

Stephan Mueller <smueller@chronox.de>

2014-08-22:2008899.25OeolVVA@myon.chronox.de:

Tom Mrz <tm@t8m.info>

2012-04-16:1334571250.5056.52.camel@vespa.frost.loc:

Vitezslav Cizek <vcizek@suse.com>

2015-11-05:20151105131424.GA32700@kolac.suse.cz

Werner Koch <wk@gnupg.org> (g10 Code GmbH)

2012-12-05:87obi8u4h2.fsf@vigenere.g10code.de:

More credits

=====

Libgcrypt used

to be part of GnuPG but has been taken out into its own package on 2000-12-21.

Most of the stuff in mpi has been taken from an old GMP library version by Torbjorn Granlund <tege@noisy.tmg.se>.

The files cipher/rndunix.c and cipher/rndw32.c are based on those files from Cryptlib. Copyright Peter Gutmann, Paul Kendall, and Chris Wedgwood 1996-1999.

The ECC code cipher/ecc.c was based on code by Sergi Blanch i Torne, sergi at calcurco dot org.

The implementation of the Camellia cipher has been taken from the original NTT provided GPL source.

The CAVS testing program tests/cavs_driver.pl is not to be considered a part of libgcrypt proper. We distribute it merely for convenience. It has a permissive license and is copyrighted by atsec information security corporation. See the file for details.

The file salsa20.c is based on D.J. Bernstein's public domain code and taken from Nettle. Copyright 2012 Simon Josefsson and Niels Miller.

This file is free software; as a special exception the author gives unlimited permission to copy and/or distribute it, with or without modifications, as long as this notice is preserved.

This file is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY, to the extent permitted by law; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.
8X-----

License:

Most of the package is licensed under the GNU Lesser General Public License (LGPL) version 2.1 (or later), except for helper and debugging binaries. See below for details. The documentation is licensed under the GPLv2 (or later), see below.

Excerpt from upstream's README:

The library is distributed under the terms of the GNU Lesser General Public License (LGPL); see the file COPYING.LIB for the actual terms. The helper programs (e.g. gcryptrd and getrandom) as well as the documentation are distributed under the terms of the GNU General Public License (GPL); see the file COPYING for the actual terms.

This library used to be available under the GPL - this was changed with version 1.1.7 with the rationale that there are now many free crypto libraries available and many of them come with capabilities similar to Libcrypt. We decided that to foster the use of cryptography in Free Software an LGPLed library would make more sense because it avoids problems due to license incompatibilities between some Free Software licenses and the GPL.

Please note that in many cases it is better for a library to be licensed under the GPL, so that it provides an advantage for free software projects. The Lesser GPL is so named because it does less to protect the freedom of the users of the code that it covers. See <http://www.gnu.org/philosophy/why-not-lgpl.html> for more explanation.

An example of the license headers of the LGPL is

Copyright (C) 1998, 1999, 2000, 2001, 2002, 2003,
2004, 2006
2007, 2008, 2009, 2010, 2011 Free Software Foundation, Inc.

This file is part of Libgcrypt.

Libgcrypt is free software; you can redistribute it and/or modify it under the terms of the GNU Lesser General Public License as published by the Free Software Foundation; either version 2.1 of the License, or (at your option) any later version.

Libgcrypt is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU Lesser General Public License for more details.

You should have received a copy of the GNU Lesser General Public License along with this program; if not, see [<http://www.gnu.org/licenses/>](http://www.gnu.org/licenses/).

On Debian GNU/Linux systems, the complete text of the GNU Lesser

General Public License can be found in
`/usr/share/common-licenses/LGPL`;

The documentation licensed under the GPL

Copyright

@copyright{ } 2000, 2002, 2003, 2004, 2006, 2007, 2008, 2009, 2011, 2012 Free Software Foundation, Inc. @*
Copyright @copyright{ } 2012, 2013, 2016 2017 g10 Code GmbH

@quotation

Permission is granted to copy, distribute and/or modify this document under the terms of the GNU General Public License as published by the Free Software Foundation; either version 2 of the License, or (at your option) any later version. The text of the license can be found in the section entitled ``GNU General Public License".

Further details on licensing:

From upstream's LICENSES file

8X-----

Additional license notices for Libgcrypt. - *- org - *-

This file contains the copying permission notices for various files in the Libgcrypt distribution which are not covered by the GNU Lesser General Public License (LGPL) or the GNU General Public License (GPL).

These notices all require that a copy of the notice be included in the

accompanying documentation and be distributed with binary distributions of the code, so be sure to include this file along with any binary distributions derived from the GNU C Library.

* BSD_3Clause

For files:

- cipher/sha256-avx-amd64.S
- cipher/sha256-avx2-bmi2-amd64.S
- cipher/sha256-ssse3-amd64.S
- cipher/sha512-avx-amd64.S
- cipher/sha512-avx2-bmi2-amd64.S
- cipher/sha512-ssse3-amd64.S

#+begin_quote

Copyright (c) 2012, Intel Corporation

All rights reserved.

Redistribution and use in source and binary forms, with or without

modification, are permitted provided that the following conditions are met:

- * Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.

- * Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.

*

Neither the name of the Intel Corporation nor the names of its contributors may be used to endorse or promote products derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY INTEL CORPORATION "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL INTEL CORPORATION OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

#+end_quote

For files:

- random/jitterentropy-base.c
- random/jitterentropy.h
- random/rndjent.c (plus common Libgcrypt copyright holders)

#+begin_quote

- * Copyright Stephan Mueller <smueller@chronox.de>, 2013

*

- * License

- * =====

*

- * Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

- * 1. Redistributions of source code must retain the above copyright

- * notice, and the entire permission notice in its entirety,

- * including the disclaimer of warranties.

- * 2. Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.
- * 3. The name of the author may not be used to endorse or promote products derived from this software without specific prior written permission.

*
* ALTERNATIVELY, this product may be distributed under the terms of the GNU General Public License, in which case the provisions of the GPL are required INSTEAD OF the above restrictions. (This clause is necessary due to a potential bad interaction between the GPL and the restrictions contained in a BSD-style copyright.)

* THIS SOFTWARE IS PROVIDED ``AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, ALL OF WHICH ARE HEREBY DISCLAIMED. IN NO EVENT SHALL THE AUTHOR BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF NOT ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

#+end_quote

*
X License

For files:
- install.sh

#+begin_quote
Copyright (C) 1994 X Consortium

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR

IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE X CONSORTIUM BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

Except as contained in this notice, the name of the X Consortium shall not be used in advertising or otherwise to promote the sale, use or other dealings in this Software without prior written authorization from the X Consortium.

#+end_quote

* Public domain

For files:

- cipher/arcfour-amd64.S

#+begin_quote

Author: Marc Bevand <bevand_m (at) epita.fr>

Licence: I hereby disclaim the copyright on this code and place it in the public domain.

#+end_quote

* OCB license 1

For files:

- cipher/cipher-ocb.c

#+begin_quote

OCB is covered by several patents but may be used freely by most software. See <http://web.cs.ucdavis.edu/~rogaway/ocb/license.htm> .

In particular license 1 is suitable for Libgcrypt: See

<http://web.cs.ucdavis.edu/~rogaway/ocb/license1.pdf> for the full license document; it basically says:

License 1 License for Open-Source Software Implementations of OCB
(Jan 9, 2013)

Under this license, you are authorized to make, use, and distribute open-source software implementations of OCB. This license terminates for you if you sue someone over their open-source software implementation of OCB claiming that you have a patent covering their implementation.

License for Open Source Software Implementations of OCB

January 9, 2013

1 Definitions

1.1 Licensor means Phillip Rogaway.

1.2 Licensed Patents means any patent that claims priority to United States Patent Application No. 09/918,615 entitled Method and Apparatus for Facilitating Efficient Authenticated Encryption, and any utility, divisional, provisional, continuation, continuations-in-part, reexamination, reissue, or foreign counterpart patents that may issue with respect to the aforesaid patent application. This includes, but is not limited to, United States Patent No. 7,046,802;

United States Patent No. 7,200,227; United States Patent No. 7,949,129; United States Patent No. 8,321,675 ; and any patent that issues out of United States Patent Application No. 13/669,114.

1.3 Use means any practice of any invention claimed in the Licensed Patents.

1.4 Software Implementation means any practice of any invention claimed in the Licensed Patents that takes the form of software executing on a user-programmable, general-purpose computer or that takes the form of a computer-readable medium storing such software. Software Implementation does not include, for example, application-specific integrated circuits (ASICs), field-programmable gate arrays (FPGAs), embedded systems, or IP cores.

1.5 Open Source Software means software whose source code is published and made available for inspection and use by anyone because either (a) the source code is subject to a license that permits recipients to copy, modify, and distribute the source code without payment of fees or royalties, or (b) the source code is in the public domain, including code released for public use through a CC0 waiver. All licenses certified by the Open Source Initiative at opensource.org as of January 9, 2013 and all Creative Commons licenses identified on the creativecommons.org website as of January 9, 2013, including the Public License Fallback of the CC0 waiver, satisfy these requirements for the purposes of this license.

1.6 Open Source Software Implementation means a Software Implementation in which the software implicating the Licensed Patents is Open Source Software. Open Source Software Implementation does not include any Software Implementation in which the software implicating the Licensed Patents is combined, so as to form a larger program, with software that is not Open Source Software.

2 License Grant

2.1 License. Subject to your compliance with the terms of this license,

including the restriction set forth in Section 2.2, Licensor hereby grants to you a perpetual, worldwide, non-exclusive, non-transferable, non-sublicenseable, no-charge, royalty-free, irrevocable license to practice any invention claimed in the Licensed Patents in any Open Source Software Implementation.

2.2 Restriction. If you or your affiliates institute patent litigation (including, but not limited to, a cross-claim or counterclaim in a lawsuit) against any entity alleging that any Use authorized by this license infringes another patent, then any rights granted to you under this license automatically terminate as of the date such litigation is filed.

3 Disclaimer

YOUR USE OF THE LICENSED PATENTS IS AT YOUR OWN RISK AND UNLESS REQUIRED BY APPLICABLE LAW, LICENSOR MAKES NO REPRESENTATIONS OR WARRANTIES OF ANY KIND CONCERNING THE LICENSED PATENTS OR ANY PRODUCT EMBODYING ANY LICENSED PATENT, EXPRESS OR IMPLIED, STATUTORY OR OTHERWISE, INCLUDING, WITHOUT LIMITATION, WARRANTIES OF TITLE, MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE,

OR NONINFRINGEMENT. IN NO EVENT WILL LICENSOR BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN CONTRACT, TORT OR OTHERWISE, ARISING FROM OR RELATED TO ANY USE OF THE LICENSED PATENTS, INCLUDING, WITHOUT LIMITATION, DIRECT, INDIRECT, INCIDENTAL, CONSEQUENTIAL, PUNITIVE OR SPECIAL DAMAGES, EVEN IF LICENSOR HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES PRIOR TO SUCH AN OCCURRENCE.

#+end_quote

8X-----

On Debian GNU/Linux systems, the text of the GNU General Public License, version 2 can be found in `~/usr/share/common-licenses/GPL-2`.

1.63 afero 1.0.5

1.63.1 Available under license :

Apache License
Version 2.0, January 2004
<http://www.apache.org/licenses/>

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction, and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by

the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all other entities that control, are controlled by, or are under common control with that entity. For the purposes of this definition, "control" means (i) the power, direct or indirect, to cause the direction or management of such entity, whether by contract or otherwise, or (ii) ownership of fifty percent (50%) or more of the outstanding shares, or (iii) beneficial ownership of such entity.

"You" (or "Your") shall mean an individual or Legal Entity exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications, including but not limited to software source code, documentation source, and configuration files.

"Object" form shall mean any form resulting from mechanical transformation or translation of a Source form, including but not limited to compiled object code, generated documentation, and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or Object form, made available under the License, as indicated by a copyright notice that is included in or attached to the work (an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object form, that is based on (or derived from) the Work and for which the editorial revisions, annotations, elaborations, or other modifications represent, as a whole, an original work of authorship. For the purposes of this License, Derivative Works shall not include works that remain separable from, or merely link (or bind by name) to the interfaces of, the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including the original version of the Work and any modifications or additions to that Work or Derivative Works thereof, that is intentionally submitted to Licensor for inclusion in the Work by the copyright owner or by an individual or Legal Entity authorized to submit on behalf of the copyright owner. For the purposes of this definition, "submitted" means any form of electronic, verbal, or written communication sent to the Licensor or its representatives, including but not limited to communication on electronic mailing lists, source code control systems, and issue tracking systems that are managed by, or on behalf of, the Licensor for the purpose of discussing and improving the Work, but

excluding communication that is conspicuously marked or otherwise designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity on behalf of whom a Contribution has been received by Licensor and subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative Works of, publicly display, publicly perform, sublicense, and distribute the Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable (except as stated in this section) patent license to make, have made, use, offer to sell, sell, import, and otherwise transfer the Work, where such license applies only to those patent claims licensable by such Contributor that are necessarily infringed by their Contribution(s) alone or by combination of their Contribution(s) with the Work to which such Contribution(s) was submitted. If You institute patent litigation against any entity (including a cross-claim or counterclaim in a lawsuit) alleging that the Work or a Contribution incorporated within the Work constitutes direct or contributory patent infringement, then any patent licenses granted to You under this License for that Work shall terminate as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute copies of the Work or Derivative Works thereof in any medium, with or without modifications, and in Source or Object form, provided that You meet the following conditions:

- (a) You must give any other recipients of the Work or Derivative Works a copy of this License; and
- (b) You must cause any modified files to carry prominent notices stating that You changed the files; and
- (c) You must retain, in the Source form of any Derivative Works that You distribute, all copyright, patent, trademark, and attribution notices from the Source form of the Work, excluding those notices that do not pertain to any part of the Derivative Works; and

(d) If the Work includes a "NOTICE" text file as part of its distribution, then any Derivative Works that You distribute must include a readable copy of the attribution notices contained within such NOTICE file, excluding

those notices that do not

pertain to any part of the Derivative Works, in at least one of the following places: within a NOTICE text file distributed as part of the Derivative Works; within the Source form or documentation, if provided along with the Derivative Works; or, within a display generated by the Derivative Works, if and wherever such third-party notices normally appear. The contents of the NOTICE file are for informational purposes only and do not modify the License. You may add Your own attribution notices within Derivative Works that You distribute, alongside or as an addendum to the NOTICE text from the Work, provided that such additional attribution notices cannot be construed as modifying the License.

You may add Your own copyright statement to Your modifications and may provide additional or different license terms and conditions

for use, reproduction, or distribution of Your modifications, or for any such Derivative Works as a whole, provided Your use, reproduction, and distribution of the Work otherwise complies with the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise, any Contribution intentionally submitted for inclusion in the Work by You to the Licensor shall be under the terms and conditions of this License, without any additional terms or conditions.

Notwithstanding the above, nothing herein shall supersede or modify the terms of any separate license agreement you may have executed with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade names, trademarks, service marks, or product names of the Licensor, except as required for reasonable and customary use in describing the origin of the Work and reproducing the content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or agreed to in writing, Licensor provides the Work (and each Contributor provides its Contributions) on an "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied, including, without limitation, any warranties or conditions of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A PARTICULAR PURPOSE. You are solely responsible for determining the

appropriateness of using or redistributing the Work and assume any risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory, whether in tort (including negligence), contract, or otherwise, unless required by applicable law (such as deliberate and grossly negligent acts) or agreed to in writing, shall any Contributor be liable to You for damages, including any direct, indirect, special, incidental, or consequential damages of any character arising as a result of this License or out of the use or inability to use the Work (including but not limited to damages for loss of goodwill, work stoppage, computer failure or malfunction, or any and all other commercial damages or losses), even if such Contributor has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing the Work or Derivative Works thereof, You may choose to offer, and charge a fee for, acceptance of support, warranty, indemnity, or other liability obligations and/or rights consistent with this License. However, in accepting such obligations, You may act only on Your own behalf and on Your sole responsibility, not on behalf of any other Contributor, and only if You agree to indemnify, defend, and hold each Contributor harmless for any liability

incurred by, or claims asserted against, such Contributor by reason of your accepting any such warranty or additional liability.

1.64 tdb 1.44.1

1.64.1 Available under license :

GNU GENERAL PUBLIC LICENSE

Version 3, 29 June 2007

Copyright (C) 2007 Free Software Foundation, Inc. <<http://fsf.org/>>

Everyone is permitted to copy and distribute verbatim copies of this license document, but changing it is not allowed.

Preamble

The GNU General Public License is a free, copyleft license for software and other kinds of works.

The licenses for most software and other practical works are designed to take away your freedom to share and change the works. By contrast, the GNU General Public License is intended to guarantee your freedom to share and change all versions of a program--to make sure it remains free

software for all its users. We, the Free Software Foundation, use the GNU General Public License for most of our software; it applies also to any other work released this way by its authors. You can apply it to your programs, too.

When we speak of free software, we are referring to freedom, not price. Our General Public Licenses are designed to make sure that you have the freedom to distribute copies of free software (and charge for them if you wish), that you receive source code or can get it if you want it, that you can change the software or use pieces of it in new free programs, and that you know you can do these things.

To protect your rights, we need to prevent others from denying you these rights or asking you to surrender the rights. Therefore, you have certain responsibilities if you distribute copies of the software, or if you modify it: responsibilities to respect the freedom of others.

For example, if you distribute copies of such a program, whether gratis or for a fee, you must pass on to the recipients the same freedoms that you received. You must make sure that they, too, receive or can get the source code. And you must show them these terms so they know their rights.

Developers that use the GNU GPL protect your rights with two steps:

(1) assert copyright on the software, and (2) offer you this License giving you legal permission to copy, distribute and/or modify it.

For the developers' and authors' protection, the GPL clearly explains that there is no warranty for this free software. For both users' and authors' sake, the GPL requires that modified versions be marked as changed, so that their problems will not be attributed erroneously to authors of previous versions.

Some devices are designed to deny users access to install or run modified versions of the software inside them, although the manufacturer can do so. This is fundamentally incompatible with the aim of protecting users' freedom to change the software. The systematic pattern of such abuse occurs in the area of products for individuals to use, which is precisely where it is most unacceptable. Therefore, we have designed this version of the GPL to prohibit the practice for those products. If

such problems arise substantially in other domains, we stand ready to extend this provision to those domains in future versions of the GPL, as needed to protect the freedom of users.

Finally, every program is threatened constantly by software patents.

States should not allow patents to restrict development and use of software on general-purpose computers, but in those that do, we wish to avoid the special danger that patents applied to a free program could make it effectively proprietary. To prevent this, the GPL assures that patents cannot be used to render the program non-free.

The precise terms and conditions for copying, distribution and modification follow.

TERMS AND CONDITIONS

0. Definitions.

"This License" refers to version 3 of the GNU General Public License.

"Copyright" also means copyright-like laws that apply to other kinds of works, such as semiconductor masks.

"The Program" refers to any copyrightable work licensed under this License. Each licensee is addressed as "you". "Licensees" and "recipients" may be individuals or organizations.

To "modify" a work means to copy from or adapt all or part of the work in a fashion requiring copyright permission, other than the making of an exact copy. The resulting work is called a "modified version" of the earlier work or a work "based on" the earlier work.

A "covered work" means either the unmodified Program or a work based on the Program.

To "propagate" a work means to do anything with it that, without permission, would make you directly or secondarily liable for infringement under applicable copyright law, except executing it on a computer or modifying a private copy. Propagation includes copying, distribution (with or without modification), making available to the public, and in some countries other activities as well.

To "convey" a work means any kind of propagation that enables other parties to make or receive copies. Mere interaction with a user through a computer network, with no transfer of a copy, is not conveying.

An interactive user interface displays "Appropriate Legal Notices" to the extent that it includes a convenient and prominently visible feature that (1) displays an appropriate copyright notice, and (2) tells the user that there is no warranty for the work (except to the extent that warranties are provided), that licensees may convey the

work under this License, and how to view a copy of this License. If the interface presents a list of user commands or options, such as a menu, a prominent item in the list meets this criterion.

1. Source Code.

The "source code" for a work means the preferred form of the work for making modifications to it. "Object code" means any non-source form of a work.

A "Standard Interface" means an interface that either is an official standard defined by a recognized standards body, or, in the case of interfaces specified

for a particular programming language, one that is widely used among developers working in that language.

The "System Libraries" of an executable work include anything, other than the work as a whole, that (a) is included in the normal form of packaging a Major Component, but which is not part of that Major Component, and (b) serves only to enable use of the work with that Major Component, or to implement a Standard Interface for which an implementation is available to the public in source code form. A "Major Component", in this context, means a major essential component (kernel, window system, and so on) of the specific operating system (if any) on which the executable work runs, or a compiler used to produce the work, or an object code interpreter used to run it.

The "Corresponding Source" for a work in object code form means all the source code needed to generate, install, and (for an executable work) run the object code and to modify the work, including scripts to control those activities. However, it does not include the work's System Libraries, or general-purpose tools or generally available free programs which are used unmodified in performing those activities but which are not part of the work. For example, Corresponding Source includes interface definition files associated with source files for the work, and the source code for shared libraries and dynamically linked subprograms that the work is specifically designed to require, such as by intimate data communication or control flow between those subprograms and other parts of the work.

The Corresponding Source need not include anything that users can regenerate automatically from other parts of the Corresponding Source.

The Corresponding Source for a work in source code form is that same work.

2. Basic Permissions.

All rights granted under this License are granted for the term of copyright on the Program, and are irrevocable provided the stated conditions are met. This License explicitly affirms your unlimited permission to run the unmodified Program. The output from running a covered work is covered by this License only if the output, given its content, constitutes a covered work. This License acknowledges your rights of fair use or other equivalent, as provided by copyright law.

You may make, run and propagate covered works that you do not convey, without conditions so long as your license otherwise remains in force. You may convey covered works to others for the sole purpose of having them make modifications exclusively for you, or provide you with facilities for running those works, provided that you comply with the terms of this License in conveying all material for which you do not control copyright. Those thus making or running the covered works for you must do so exclusively on your behalf, under your direction and control, on terms that prohibit them from making any copies of your copyrighted material outside their relationship with you.

Conveying under any other circumstances is permitted solely under the conditions stated below. Sublicensing is not allowed; section 10 makes it unnecessary.

3. Protecting Users' Legal Rights From Anti-Circumvention Law.

No covered work shall be deemed part of an effective technological measure under any applicable law fulfilling obligations under article 11 of the WIPO copyright treaty adopted on 20 December 1996, or similar laws prohibiting or restricting circumvention of such measures.

When you convey a covered work, you waive any legal power to forbid circumvention of technological measures to the extent such circumvention is effected by exercising rights under this License with respect to the covered work, and you disclaim any intention to limit operation or modification of the work as a means of enforcing, against the work's users, your or third parties' legal rights to forbid circumvention of technological measures.

4. Conveying Verbatim Copies.

You may convey verbatim copies of the Program's source code as you receive it, in any medium, provided that you conspicuously and

appropriately publish on each copy an appropriate copyright notice; keep intact all notices stating that this License and any non-permissive terms added in accord with section 7 apply to the code; keep intact all notices of the absence of any warranty; and give all recipients a copy of this License along with the Program.

You may charge any price or no price for each copy that you convey, and you may offer support or warranty protection for a fee.

5. Conveying Modified Source Versions.

You may convey a work based on the Program, or the modifications to produce it from the Program, in the form of source code under the terms of section 4, provided that you also meet all of these conditions:

- a) The work must carry prominent notices stating that you modified it, and giving a relevant date.
- b) The work must carry prominent notices stating that it is released under this License and any conditions added under section 7. This requirement modifies the requirement in section 4 to "keep intact all notices".
- c) You must license the entire work, as a whole, under this License to anyone who comes into possession of a copy. This License will therefore apply, along with any applicable section 7 additional terms, to the whole of the work, and all its parts, regardless of how they are packaged. This License gives no permission to license the work in any other way, but it does not invalidate such permission if you have separately received it.
- d) If the work has interactive user interfaces, each must display Appropriate Legal Notices; however, if the Program has interactive interfaces that do not display Appropriate Legal Notices, your work need not make them do so.

A compilation of a covered work with other separate and independent works, which are not by their nature extensions of the covered work, and which are not combined with it such as to form a larger program, in or on a volume of a storage or distribution medium, is called an "aggregate" if the compilation and its resulting copyright are not used to limit the access or legal rights of the compilation's users beyond what the individual works permit. Inclusion of a covered work in an aggregate does not cause this License to apply to the other parts of the aggregate.

6. Conveying Non-Source Forms.

You may convey a covered work in object code form under the terms of sections 4 and 5, provided that you also convey the machine-readable Corresponding Source under the terms of this License, in one of these ways:

- a) Convey the object code in, or embodied in, a physical product (including a physical distribution medium), accompanied by the Corresponding Source fixed on a durable physical medium customarily used for software interchange.
- b) Convey the object code in, or embodied in, a physical product (including a physical distribution medium), accompanied by a written offer, valid for at least three years and valid for as long as you offer spare parts or customer support for that product model, to give anyone who possesses the object code either (1) a copy of the Corresponding Source for all the software in the product that is covered by this License, on a durable physical medium customarily used for software interchange, for a price no more than your reasonable cost of physically performing this conveying of source, or (2) access to copy the Corresponding Source from a network server at no charge.
- c) Convey individual copies of the object code with a copy of the written offer to provide the Corresponding Source. This alternative is allowed only occasionally and noncommercially, and only if you received the object code with such an offer, in accord with subsection 6b.
- d) Convey the object code by offering access from a designated place (gratis or for a charge), and offer equivalent access to the Corresponding Source in the same way through the same place at no further charge. You need not require recipients to copy the Corresponding Source along with the object code. If the place to copy the object code is a network server, the Corresponding Source may be on a different server (operated by you or a third party) that supports equivalent copying facilities, provided you maintain clear directions next to the object code saying where to find the Corresponding Source. Regardless of what server hosts the Corresponding Source, you remain obligated to ensure that it is available for as long as needed to satisfy these requirements.
- e) Convey the object code using peer-to-peer transmission, provided you inform other peers where the object code and Corresponding

Source of the work are being offered to the general public at no charge under subsection 6d.

A separable portion of the object code, whose source code is excluded from the Corresponding Source as a System Library, need not be included in conveying the object code work.

A "User Product" is either (1) a "consumer product", which means any tangible personal property which is normally used for personal, family, or household purposes, or (2) anything designed or sold for incorporation into a dwelling. In determining whether a product is a consumer product, doubtful cases shall be resolved in favor of coverage. For a particular product received by a particular user, "normally used" refers to a typical or common use of that class of product, regardless of the status of the particular user or of the way in which the particular user actually uses, or expects or is expected to use, the product. A product is a consumer product regardless of whether the product has substantial commercial, industrial or non-consumer uses, unless such uses represent the only significant mode of use of the product.

"Installation Information" for a User Product means any methods, procedures, authorization keys, or other information required to install and execute modified versions of a covered work in that User Product from a modified version of its Corresponding Source. The information must suffice to ensure that the continued functioning of the modified object code is in no case prevented or interfered with solely because modification has been made.

If you convey an object code work under this section in, or with, or specifically for use in, a User Product, and the conveying occurs as part of a transaction in which the right of possession and use of the User Product is transferred to the recipient in perpetuity or for a fixed term (regardless of how the transaction is characterized), the Corresponding Source conveyed under this section must be accompanied by the Installation Information. But this requirement does not apply if neither you nor any third party retains the ability to install modified object code on the User Product (for example, the work has been installed in ROM).

The requirement to provide Installation Information does not include a requirement to continue to provide support service, warranty, or updates for a work that has been modified or installed by the recipient, or for the User Product in which it has been modified or installed. Access to a network may be denied when the modification itself materially and adversely affects the operation of the network or violates the rules and protocols for communication across the network.

Corresponding Source conveyed, and Installation Information provided, in accord with this section must be in a format that is publicly documented (and with an implementation available to the public in source code form), and must require no special password or key for unpacking, reading or copying.

7. Additional Terms.

"Additional permissions" are terms that supplement the terms of this License by making exceptions from one or more of its conditions. Additional permissions that are applicable to the entire Program shall be treated as though they were included in this License, to the extent that they are valid under applicable law. If additional permissions apply only to part of the Program, that part may be used separately under those permissions, but the entire Program remains governed by this License without regard to the additional permissions.

When you convey a copy of a covered work, you may at your option remove any additional permissions from that copy, or from any part of it. (Additional permissions may be written to require their own removal in certain cases when you modify the work.) You may place additional permissions on material, added by you to a covered work, for which you have or can give appropriate copyright permission.

Notwithstanding any other provision of this License, for material you add to a covered work, you may (if authorized by the copyright holders of that material) supplement the terms of this License with terms:

- a) Disclaiming warranty or limiting liability differently from the terms of sections 15 and 16 of this License; or
- b) Requiring preservation of specified reasonable legal notices or author attributions in that material or in the Appropriate Legal Notices displayed by works containing it; or
- c) Prohibiting misrepresentation of the origin of that material, or requiring that modified versions of such material be marked in reasonable ways as different from the original version; or
- d) Limiting the use for publicity purposes of names of licensors or authors of the material; or
- e) Declining to grant rights under trademark law for use of some trade names, trademarks, or service marks; or

f) Requiring indemnification of licensors and authors of that material by anyone who conveys the material (or modified versions of it) with contractual assumptions of liability to the recipient, for any liability that these contractual assumptions directly impose on those licensors and authors.

All other non-permissive additional terms are considered "further restrictions" within the meaning of section 10. If the Program as you received it, or any part of it, contains a notice stating that it is governed by this License along with a term that is a further restriction, you may remove that term. If a license document contains a further restriction but permits relicensing or conveying under this License, you may add to a covered work material governed by the terms of that license document, provided that the further restriction does not survive such relicensing or conveying.

If you add terms to a covered work in accord with this section, you must place, in the relevant source files, a statement of the additional terms that apply to those files, or a notice indicating where to find the applicable terms.

Additional terms, permissive or non-permissive, may be stated in the form of a separately written license, or stated as exceptions; the above requirements apply either way.

8. Termination.

You may not propagate or modify a covered work except as expressly provided under this License. Any attempt otherwise to propagate or modify it is void, and will automatically terminate your rights under this License (including any patent licenses granted under the third paragraph of section 11).

However, if you cease all violation of this License, then your license from a particular copyright holder is reinstated (a) provisionally, unless and until the copyright holder explicitly and finally terminates your license, and (b) permanently, if the copyright holder fails to notify you of the violation by some reasonable means prior to 60 days after the cessation.

Moreover, your license from a particular copyright holder is reinstated permanently if the copyright holder notifies you of the violation by some reasonable means, this is the first time you have received notice of violation of this License (for any work) from that copyright holder, and you cure the violation prior to 30 days after

your receipt of the notice.

Termination of your rights under this section does not terminate the licenses of parties who have received copies or rights from you under this License. If your rights have been terminated and not permanently reinstated, you do not qualify to receive new licenses for the same material under section 10.

9. Acceptance Not Required for Having Copies.

You are not required to accept this License in order to receive or run a copy of the Program. Ancillary propagation of a covered work occurring solely as a consequence of using peer-to-peer transmission to receive a copy likewise does not require acceptance. However, nothing other than this License grants you permission to propagate or modify any covered work. These actions infringe copyright if you do not accept this License. Therefore, by modifying or propagating a covered work, you indicate your acceptance of this License to do so.

10. Automatic Licensing of Downstream Recipients.

Each time you convey a covered work, the recipient automatically receives a license from the original licensors, to run, modify and propagate that work, subject to this License. You are not responsible for enforcing compliance by third parties with this License.

An "entity transaction" is a transaction transferring control of an organization, or substantially all assets of one, or subdividing an organization, or merging organizations. If propagation of a covered work results from an entity transaction, each party to that transaction who receives a copy of the work also receives whatever licenses to the work the party's predecessor in interest had or could give under the previous paragraph, plus a right to possession of the Corresponding Source of the work from the predecessor in interest, if the predecessor has it or can get it with reasonable efforts.

You may not impose any further restrictions on the exercise of the rights granted or affirmed under this License. For example, you may not impose a license fee, royalty, or other charge for exercise of rights granted under this License, and you may not initiate litigation (including a cross-claim or counterclaim in a lawsuit) alleging that any patent claim is infringed by making, using, selling, offering for sale, or importing the Program or any portion of it.

11. Patents.

A "contributor" is a copyright holder who authorizes use under this License of the Program or a work on which the Program is based. The work thus licensed is called the contributor's "contributor version".

A contributor's "essential patent claims" are all patent claims owned or controlled by the contributor, whether already acquired or hereafter acquired, that would be infringed by some manner, permitted by this License, of making, using, or selling its contributor version, but do not include claims that would be infringed only as a consequence of further modification of the contributor version. For purposes of this definition, "control" includes the right to grant patent sublicenses in a manner consistent with the requirements of this License.

Each contributor grants you a non-exclusive, worldwide, royalty-free patent license under the contributor's essential patent claims, to make, use, sell, offer for sale, import and otherwise run, modify and propagate the contents of its contributor version.

In the following three paragraphs, a "patent license" is any express agreement or commitment, however denominated, not to enforce a patent (such as an express permission to practice a patent or covenant not to sue for patent infringement). To "grant" such a patent license to a party means to make such an agreement or commitment not to enforce a patent against the party.

If you convey a covered work, knowingly relying on a patent license, and the Corresponding Source of the work is not available for anyone to copy, free of charge and under the terms of this License, through a publicly available network server or other readily accessible means, then you must either (1) cause the Corresponding Source to be so available, or (2) arrange to deprive yourself of the benefit of the patent license for this particular work, or (3) arrange, in a manner consistent with the requirements of this License, to extend the patent license to downstream recipients. "Knowingly relying" means you have actual knowledge that, but for the patent license, your conveying the covered work in a country, or your recipient's use of the covered work in a country, would infringe one or more identifiable patents in that country that you have reason to believe are valid.

If, pursuant to or in connection with a single transaction or arrangement, you convey, or propagate by procuring conveyance of, a covered work, and grant a patent license to some of the parties receiving the covered work authorizing them to use, propagate, modify or convey a specific copy of the covered work, then the patent license

you grant is automatically extended to all recipients of the covered work and works based on it.

A patent license is "discriminatory" if it does not include within the scope of its coverage, prohibits the exercise of, or is conditioned on the non-exercise of one or more of the rights that are specifically granted under this License. You may not convey a covered work if you are a party to an arrangement with a third party that is in the

business of distributing software, under which you make payment to the third party based on the extent of your activity of conveying the work, and under which the third party grants, to any of the parties who would receive the covered work from you, a discriminatory patent license (a) in connection with copies of the covered work conveyed by you (or copies made from those copies), or (b) primarily for and in connection with specific products or compilations that contain the covered work, unless you entered into that arrangement, or that patent license was granted, prior to 28 March 2007.

Nothing in this License shall be construed as excluding or limiting any implied license or other defenses to infringement that may otherwise be available to you under applicable patent law.

12. No Surrender of Others' Freedom.

If conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot convey a covered work so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not convey it at all. For example, if you agree to terms that obligate you to collect a royalty for further conveying from those to whom you convey the Program, the only way you could satisfy both those terms and this License would be to refrain entirely from conveying the Program.

13. Use with the GNU Affero General Public License.

Notwithstanding any other provision of this License, you have permission to link or combine any covered work with a work licensed under version 3 of the GNU Affero General Public License into a single combined work, and to convey the resulting work. The terms of this License will continue to apply to the part which is the covered work, but the special requirements of the GNU Affero General Public License, section 13, concerning interaction through a network will apply to the combination as such.

14. Revised Versions of this License.

The Free Software Foundation may publish revised and/or new versions of the GNU General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Program specifies that a certain numbered version of the GNU General Public License "or any later version" applies to it, you have the option of following the terms and conditions either of that numbered version or of any later version published by the Free Software Foundation. If the Program does not specify a version number of the GNU General Public License, you may choose any version ever published by the Free Software Foundation.

If the Program specifies that a proxy can decide which future versions of the GNU General Public License can be used, that proxy's public statement of acceptance of a version permanently authorizes you to choose that version for the Program.

Later license versions may give you additional or different permissions. However, no additional obligations are imposed on any author or copyright holder as a result of your choosing to follow a later version.

15. Disclaimer of Warranty.

THERE IS NO WARRANTY FOR THE PROGRAM, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE PROGRAM "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE PROGRAM IS WITH YOU. SHOULD THE PROGRAM PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

16. Limitation of Liability.

IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MODIFIES AND/OR CONVEYS THE PROGRAM AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE PROGRAM (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE PROGRAM TO OPERATE WITH ANY OTHER PROGRAMS),

EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

17. Interpretation of Sections 15 and 16.

If the disclaimer of warranty and limitation of liability provided above cannot be given local legal effect according to their terms, reviewing courts shall apply local law that most closely approximates an absolute waiver of all civil liability in connection with the Program, unless a warranty or assumption of liability accompanies a copy of the Program in return for a fee.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Programs

If you develop a new program, and you want it to be of the greatest possible use to the public, the best way to achieve this is to make it free software which everyone can redistribute and change under these terms.

To do so, attach the following notices to the program. It is safest to attach them to the start of each source file to most effectively state the exclusion of warranty; and each file should have at least the "copyright" line and a pointer to where the full notice is found.

<one line to give the program's name and a brief idea of what it does.>
Copyright (C) <year> <name of author>

This program is free software: you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation, either version 3 of the License, or (at your option) any later version.

This program is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details.

You should have received a copy of the GNU General Public License along with this program. If not, see <<http://www.gnu.org/licenses/>>.

Also add information on how to contact you by electronic and paper mail.

If the program does terminal interaction, make it output a short notice like this when it starts in an interactive mode:

<program> Copyright (C) <year> <name of author>

This program comes with ABSOLUTELY NO WARRANTY; for details type 'show w'.
This is free software, and you are welcome to redistribute it
under certain conditions; type 'show c' for details.

The hypothetical commands 'show w' and 'show c' should show the appropriate
parts of
the General Public License. Of course, your program's commands
might be different; for a GUI interface, you would use an "about box".

You should also get your employer (if you work as a programmer) or school,
if any, to sign a "copyright disclaimer" for the program, if necessary.
For more information on this, and how to apply and follow the GNU GPL, see
<<http://www.gnu.org/licenses/>>.

The GNU General Public License does not permit incorporating your program
into proprietary programs. If your program is a subroutine library, you
may consider it more useful to permit linking proprietary applications with
the library. If this is what you want to do, use the GNU Lesser General
Public License instead of this License. But first, please read
<<http://www.gnu.org/philosophy/why-not-lgpl.html>>.

1.65 libseccomp 2.5.1-1ubuntu1~18.04.2

1.65.1 Available under license :

GNU LESSER GENERAL PUBLIC LICENSE

Version 2.1, February 1999

Copyright (C) 1991, 1999 Free Software Foundation, Inc.
51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA
Everyone is permitted to copy and distribute verbatim copies
of this license document, but changing it is not allowed.

[This is the first released version of the Lesser GPL. It also counts
as the successor of the GNU Library Public License, version 2, hence
the version number 2.1.]

Preamble

The licenses for most software are designed to take away your

freedom to share and change it. By contrast, the GNU General Public Licenses are intended to guarantee your freedom to share and change free software--to make sure the software is free for all its users.

This license, the Lesser General Public License, applies to some specially designated software packages--typically libraries--of the Free Software Foundation and other authors who decide to use it. You can use it too, but we suggest you first think carefully about whether this license or the ordinary General Public License is the better strategy to use in any particular case, based on the explanations below.

When we speak of free software, we are referring to freedom of use, not price. Our General Public Licenses are designed to make sure that you have the freedom to distribute copies of free software (and charge for this service if you wish); that you receive source code or can get it if you want it; that you can change the software and use pieces of it in new free programs; and that you are informed that you can do these things.

To protect your rights, we need to make restrictions that forbid distributors to deny you these rights or to ask you to surrender these rights. These restrictions translate to certain responsibilities for you if you distribute copies of the library or if you modify it.

For example, if you distribute copies of the library, whether gratis or for a fee, you must give the recipients all the rights that we gave you. You must make sure that they, too, receive or can get the source code. If you link other code with the library, you must provide complete object files to the recipients, so that they can relink them with the library after making changes to the library and recompiling it. And you must show them these terms so they know their rights.

We protect your rights with a two-step method: (1) we copyright the library, and (2) we offer you this license, which gives you legal permission to copy, distribute and/or modify the library.

To protect each distributor, we want to make it very clear that there is no warranty for the free library. Also, if the library is modified by someone else and passed on, the recipients should know that what they have is not the original version, so that the original author's reputation will not be affected by problems that might be introduced by others.

Finally, software patents pose a constant threat to the existence of any free program. We wish to make sure that a company cannot

effectively restrict the users of a free program by obtaining a restrictive license from a patent holder. Therefore, we insist that any patent license obtained for a version of the library must be consistent with the full freedom of use specified in this license.

Most GNU software, including some libraries, is covered by the ordinary GNU General Public License. This license, the GNU Lesser General Public License, applies to certain designated libraries, and is quite different from the ordinary General Public License. We use this license for certain libraries in order to permit linking those libraries into non-free programs.

When a program is linked with a library, whether statically or using a shared library, the combination of the two is legally speaking a combined work, a derivative of the original library. The ordinary General Public License therefore permits such linking only if the entire combination fits its criteria of freedom. The Lesser General Public License permits more lax criteria for linking other code with the library.

We call this license the "Lesser" General Public License because it does Less to protect the user's freedom than the ordinary General Public License. It also provides other free software developers Less of an advantage over competing non-free programs. These disadvantages are the reason we use the ordinary General Public License for many libraries. However, the Lesser license provides advantages in certain special circumstances.

For example, on rare occasions, there may be a special need to encourage the widest possible use of a certain library, so that it becomes a de-facto standard. To achieve this, non-free programs must be allowed to use the library. A more frequent case is that a free library does the same job as widely used non-free libraries. In this case, there is little to gain by limiting the free library to free software only, so we use the Lesser General Public License.

In other cases, permission to use a particular library in non-free programs enables a greater number of people to use a large body of free software. For example, permission to use the GNU C Library in non-free programs enables many more people to use the whole GNU operating system, as well as its variant, the GNU/Linux operating system.

Although the Lesser General Public License is Less protective of the users' freedom, it does ensure that the user of a program that is linked with the Library has the freedom and the wherewithal to run

that program using a modified version of the Library.

The precise terms and conditions for copying, distribution and modification follow. Pay close attention to the difference between a "work based on the library" and a "work that uses the library". The former contains code derived from the library, whereas the latter must be combined with the library in order to run.

GNU LESSER GENERAL PUBLIC LICENSE TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

0. This License Agreement applies to any software library or other program which contains a notice placed by the copyright holder or other authorized party saying it may be distributed under the terms of this Lesser General Public License (also called "this License"). Each licensee is addressed as "you".

A "library" means a collection of software functions and/or data prepared so as to be conveniently linked with application programs (which use some of those functions and data) to form executables.

The "Library", below, refers to any such software library or work which has been distributed under these terms. A "work based on the Library" means either the Library or any derivative work under copyright law: that is to say, a work containing the Library or a portion of it, either verbatim or with modifications and/or translated straightforwardly into another language. (Hereinafter, translation is included without limitation in the term "modification".)

"Source code" for a work means the preferred form of the work for making modifications to it. For a library, complete source code means all the source code for all modules it contains, plus any associated interface definition files, plus the scripts used to control compilation and installation of the library.

Activities other than copying, distribution and modification are not covered by this License; they are outside its scope. The act of running a program using the Library is not restricted, and output from such a program is covered only if its contents constitute a work based on the Library (independent of the use of the Library in a tool for writing it). Whether that is true depends on what the Library does and what the program that uses the Library does.

1. You may copy and distribute verbatim copies of the Library's complete source code as you receive it, in any medium,

provided that you conspicuously and appropriately publish on each copy an appropriate copyright notice and disclaimer of warranty; keep intact all the notices that refer to this License and to the absence of any warranty; and distribute a copy of this License along with the Library.

You may charge a fee for the physical act of transferring a copy, and you may at your option offer warranty protection in exchange for a fee.

2. You may modify your copy or copies of the Library or any portion of it, thus forming a work based on the Library, and copy and distribute such modifications or work under the terms of Section 1 above, provided that you also meet all of these conditions:

- a) The modified work must itself be a software library.
- b) You must cause the files modified to carry prominent notices stating that you changed the files and the date of any change.
- c) You must cause the whole of the work to be licensed at no charge to all third parties under the terms of this License.
- d) If a facility in the modified Library refers to a function or a table of data to be supplied by an application program that uses the facility, other than as an argument passed when the facility is invoked, then you must make a good faith effort to ensure that, in the event an application does not supply such function or table, the facility still operates, and performs whatever part of its purpose remains meaningful.

(For example, a function in a library to compute square roots has a purpose that is entirely well-defined independent of the application. Therefore, Subsection 2d requires that any application-supplied function or table used by this function must be optional: if the application does not supply it, the square root function must still compute square roots.)

These requirements apply to the modified work as a whole. If identifiable sections of that work are not derived from the Library, and can be reasonably considered independent and separate works in themselves, then this License, and its terms, do not apply to those sections when you distribute them as separate works. But when you distribute the same sections as part of a whole which is a work based on the Library, the distribution of the whole must be on the terms of

this License, whose permissions for other licensees extend to the entire whole, and thus to each and every part regardless of who wrote it.

Thus, it is not the intent of this section to claim rights or contest your rights to work written entirely by you; rather, the intent is to exercise the right to control the distribution of derivative or collective works based on the Library.

In addition, mere aggregation of another work not based on the Library with the Library (or with a work based on the Library) on a volume of a storage or distribution medium does not bring the other work under the scope of this License.

3. You may opt to apply the terms of the ordinary

GNU General Public

License instead of this License to a given copy of the Library. To do this, you must alter all the notices that refer to this License, so that they refer to the ordinary GNU General Public License, version 2, instead of to this License. (If a newer version than version 2 of the ordinary GNU General Public License has appeared, then you can specify that version instead if you wish.) Do not make any other change in these notices.

Once this change is made in a given copy, it is irreversible for that copy, so the ordinary GNU General Public License applies to all subsequent copies and derivative works made from that copy.

This option is useful when you wish to copy part of the code of the Library into a program that is not a library.

4. You may copy and distribute the Library (or a portion or derivative of it, under Section 2) in object code or executable form under the terms of Sections 1 and 2 above provided that you accompany it with the complete corresponding machine-readable source code, which must be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange.

If distribution of object code is made by offering access to copy from a designated place, then offering equivalent access to copy the source code from the same place satisfies the requirement to distribute the source code, even though third parties are not compelled to copy the source along with the object code.

5. A program that contains no derivative of any portion of the Library, but is designed to work with the Library by being compiled or linked with it, is called a "work that uses the Library". Such a

work, in isolation, is not a derivative work of the Library, and therefore falls outside the scope of this License.

However, linking a "work that uses the Library" with the Library creates an executable that is a derivative of the Library (because it contains portions of the Library), rather than a "work that uses the library". The executable is therefore covered by this License. Section 6 states terms for distribution of such executables.

When a "work that uses the Library" uses material from a header file that is part of the Library, the object code for the work may be a derivative work of the Library even though the source code is not. Whether this is true is especially significant if the work can be linked without the Library, or if the work is itself a library. The threshold for this to be true is not precisely defined by law.

If such an object file uses only numerical parameters, data structure layouts and accessors, and small macros and small inline functions (ten lines or less in length), then the use of the object file is unrestricted, regardless of whether it is legally a derivative work. (Executables containing this object code plus portions of the Library will still fall under Section 6.)

Otherwise, if the work is a derivative of the Library, you may distribute the object code for the work under the terms of Section 6. Any executables containing that work also fall under Section 6, whether or not they are linked directly with the Library itself.

6. As an exception to the Sections above, you may also combine or link a "work that uses the Library" with the Library to produce a work containing portions of the Library, and distribute that work under terms of your choice, provided that the terms permit modification of the work for the customer's own use and reverse engineering for debugging such modifications.

You must give prominent notice with each copy of the work that the Library is used in it and that the Library and its use are covered by this License. You must supply a copy of this License. If the work during execution displays copyright notices, you must include the copyright notice for the Library among them, as well as a reference directing the user to the copy of this License. Also, you must do one of these things:

- a) Accompany the work with the complete corresponding machine-readable source code for the Library including whatever

changes were used in the work (which must be distributed under Sections 1 and 2 above); and, if the work is an executable linked with the Library, with the complete machine-readable "work that uses the Library", as object code and/or source code, so that the user can modify the Library and then relink to produce a modified executable containing the modified Library. (It is understood that the user who changes the contents of definitions files in the Library will not necessarily be able to recompile the application to use the modified definitions.)

b) Use a suitable shared library mechanism for linking with the Library. A suitable mechanism is one that (1) uses at run time a copy of the library already present on the user's computer system, rather than copying library functions into the executable, and (2) will operate properly with a modified version of the library, if the user installs one, as long as the modified version is interface-compatible with the version that the work was made with.

c) Accompany the work with a written offer, valid for at least three years, to give the same user the materials specified in Subsection 6a, above, for a charge no more than the cost of performing this distribution.

d) If distribution of the work is made by offering access to copy from a designated place, offer equivalent access to copy the above specified materials from the same place.

e) Verify that the user has already received a copy of these materials or that you have already sent this user a copy.

For an executable, the required form of the "work that uses the Library" must include any data and utility programs needed for reproducing the executable from it. However, as a special exception, the materials to be distributed need not include anything that is normally distributed (in either source or binary form) with the major components (compiler, kernel, and so on) of the operating system on which the executable runs, unless that component itself accompanies the executable.

It may happen that this requirement contradicts the license restrictions of other proprietary libraries that do not normally accompany the operating system. Such a contradiction means you cannot use both them and the Library together in an executable that you distribute.

7. You may place library facilities that are a work based on the

Library side-by-side in a single library together with other library facilities not covered by this License, and distribute such a combined library, provided that the separate distribution of the work based on the Library and of the other library facilities is otherwise permitted, and provided that you do these two things:

a) Accompany the combined library with a copy of the same work based on the Library, uncombined with any other library facilities. This must be distributed under the terms of the Sections above.

b) Give prominent notice with the combined library of the fact that part of it is a work based on the Library, and explaining where to find the accompanying uncombined form of the same work.

8. You may not copy, modify, sublicense, link with, or distribute the Library except as expressly provided under this License. Any attempt otherwise to copy, modify, sublicense, link with, or distribute the Library is void, and will automatically terminate your rights under this License. However, parties who have received copies, or rights, from you under this License will not have their licenses terminated so long as such parties remain in full compliance.

9. You are not required to accept this License, since you have not signed it. However, nothing else grants you permission to modify or distribute the Library or its derivative works. These actions are prohibited by law if you do not accept this License. Therefore, by modifying or distributing the Library (or any work based on the Library), you indicate your acceptance of this License to do so, and all its terms and conditions for copying, distributing or modifying the Library or works based on it.

10. Each time you redistribute the Library (or any work based on the Library), the recipient automatically receives a license from the original licensor to copy, distribute, link with or modify the Library subject to these terms and conditions. You may not impose any further restrictions on the recipients' exercise of the rights granted herein. You are not responsible for enforcing compliance by third parties with this License.

11. If, as a consequence of a court judgment or allegation of patent infringement or for any other reason (not limited to patent issues), conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse

you from the conditions of this License. If you cannot distribute so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not distribute the Library at all. For example, if a patent license would not permit royalty-free redistribution of the Library by all those who receive copies directly or indirectly through you, then the only way you could satisfy both it and this License would be to refrain entirely from distribution of the Library.

If any portion of this section is held invalid or unenforceable under any particular circumstance, the balance of the section is intended to apply, and the section as a whole is intended to apply in other circumstances.

It is not the purpose of this section to induce you to infringe any patents or other property right claims or to contest validity of any such claims; this section has the sole purpose of protecting the integrity of the free software distribution system which is implemented by public license practices. Many people have made generous contributions to the wide range of software distributed through that system in reliance on consistent application of that system; it is up to the author/donor to decide if he or she is willing to distribute software through any other system and a licensee cannot impose that choice.

This section is intended to make thoroughly clear what is believed to be a consequence of the rest of this License.

12. If the distribution and/or use of the Library is restricted in certain countries either by patents or by copyrighted interfaces, the original copyright holder who places the Library under this License may add an explicit geographical distribution limitation excluding those countries, so that distribution is permitted only in or among countries not thus excluded. In such case, this License incorporates the limitation as if written in the body of this License.

13. The Free Software Foundation may publish revised and/or new versions of the Lesser General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Library specifies a version number of this License which applies to it and "any later version", you have the option of following the terms and conditions either of that version or of any later version published by the Free Software Foundation. If the Library does not specify a license version number, you may choose any version ever published by

the Free Software Foundation.

14. If you wish to incorporate parts of the Library into other free programs whose distribution conditions are incompatible with these, write to the author to ask for permission. For software which is copyrighted by the Free Software Foundation, write to the Free Software Foundation; we sometimes make exceptions for this. Our decision will be guided by the two goals of preserving the free status of all derivatives of our free software and of promoting the sharing and reuse of software generally.

NO WARRANTY

15. BECAUSE THE LIBRARY IS LICENSED FREE OF CHARGE, THERE IS NO WARRANTY FOR THE LIBRARY, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE LIBRARY "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE LIBRARY IS WITH YOU. SHOULD THE LIBRARY PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

16. IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY AND/OR REDISTRIBUTE THE LIBRARY AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE LIBRARY (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE LIBRARY TO OPERATE WITH ANY OTHER SOFTWARE), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

1.66 spf13-cobra v1.3.0

1.66.1 Available under license :

```
// Copyright © 2015 Steve Francia <spf@spf13.com>.  
//  
// Licensed under the Apache License, Version 2.0 (the "License");  
// you may not use this file except in compliance with the License.  
// You may obtain a copy of the License at  
// http://www.apache.org/licenses/LICENSE-2.0  
//  
// Unless required by applicable law or agreed to in writing, software
```

// distributed under the License is distributed on an "AS IS" BASIS,
// WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
// See the License for the specific language governing permissions and
// limitations under the License.

Apache License
Version 2.0, January 2004
<http://www.apache.org/licenses/>

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction, and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all other entities that control, are controlled by, or are under common control with that entity. For the purposes of this definition, "control" means (i) the power, direct or indirect, to cause the direction or management of such entity, whether by contract or otherwise, or (ii) ownership of fifty percent (50%) or more of the outstanding shares, or (iii) beneficial ownership of such entity.

"You" (or "Your") shall mean an individual or Legal Entity exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications, including but not limited to software source code, documentation source, and configuration files.

"Object" form shall mean any form resulting from mechanical transformation or translation of a Source form, including but not limited to compiled object code, generated documentation, and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or Object form, made available under the License, as indicated by a copyright notice that is included in or attached to the work (an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object form, that is based on (or derived from) the Work and for which the editorial

revisions, annotations, elaborations, or other modifications represent, as a whole, an original work of authorship. For the purposes of this License, Derivative Works shall not include works that remain separable from, or merely link (or bind by name) to the interfaces of, the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including the original version of the Work and any modifications or additions to that Work or Derivative Works thereof, that is intentionally submitted to Licensor for inclusion in the Work by the copyright owner or by an individual or Legal Entity authorized to submit on behalf of the copyright owner. For the purposes of this definition, "submitted" means any form of electronic, verbal, or written communication sent to the Licensor or its representatives, including but not limited to communication on electronic mailing lists, source code control systems, and issue tracking systems that are managed by, or on behalf of, the Licensor for the purpose of discussing and improving the Work, but excluding communication that is conspicuously marked or otherwise designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity on behalf of whom a Contribution has been received by Licensor and subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative Works of, publicly display, publicly perform, sublicense, and distribute the Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable (except as stated in this section) patent license to make, have made, use, offer to sell, sell, import, and otherwise transfer the Work, where such license applies only to those patent claims licensable by such Contributor that are necessarily infringed by their Contribution(s) alone or by combination of their Contribution(s) with the Work to which such Contribution(s) was submitted. If You institute patent litigation against any entity (including a cross-claim or counterclaim in a lawsuit) alleging that the Work or a Contribution incorporated within the Work constitutes direct or contributory patent infringement, then any patent licenses granted to You under this License for that Work shall terminate as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute copies of the Work or Derivative Works thereof in any medium, with or without modifications, and in Source or Object form, provided that You meet the following conditions:

- (a) You must give any other recipients of the Work or Derivative Works a copy of this License; and
- (b) You must cause any modified files to carry prominent notices stating that You changed the files; and
- (c) You must retain, in the Source form of any Derivative Works that You distribute, all copyright, patent, trademark, and attribution notices from the Source form of the Work, excluding those notices that do not pertain to any part of the Derivative Works; and
- (d) If the Work includes a "NOTICE" text file as part of its distribution, then any Derivative Works that You distribute must include a readable copy of the attribution notices contained within such NOTICE file, excluding those notices that do not pertain to any part of the Derivative Works, in at least one of the following places: within a NOTICE text file distributed as part of the Derivative Works; within the Source form or documentation, if provided along with the Derivative Works; or, within a display generated by the Derivative Works, if and wherever such third-party notices normally appear. The contents of the NOTICE file are for informational purposes only and do not modify the License. You may add Your own attribution notices within Derivative Works that You distribute, alongside or as an addendum to the NOTICE text from the Work, provided that such additional attribution notices cannot be construed as modifying the License.

You may add Your own copyright statement to Your modifications and may provide additional or different license terms and conditions for use, reproduction, or distribution of Your modifications, or for any such Derivative Works as a whole, provided Your use, reproduction, and distribution of the Work otherwise complies with the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise, any Contribution intentionally submitted for inclusion in the Work by You to the Licensor shall be under the terms and conditions of this License, without any additional terms or conditions.

Notwithstanding the above, nothing herein shall supersede or modify the terms of any separate license agreement you may have executed with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade names, trademarks, service marks, or product names of the Licensor, except as required for reasonable and customary use in describing the origin of the Work and reproducing the content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or agreed to in writing, Licensor provides the Work (and each Contributor provides its Contributions) on an "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied, including, without limitation, any warranties or conditions of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A PARTICULAR PURPOSE. You are solely responsible for determining the appropriateness of using or redistributing the Work and assume any risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory, whether in tort (including negligence), contract, or otherwise, unless required by applicable law (such as deliberate and grossly negligent acts) or agreed to in writing, shall any Contributor be liable to You for damages, including any direct, indirect, special, incidental, or consequential damages of any character arising as a result of this License or out of the use or inability to use the Work (including but not limited to damages for loss of goodwill, work stoppage, computer failure or malfunction, or any and all other commercial damages or losses), even if such Contributor has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing the Work or Derivative Works thereof, You may choose to offer, and charge a fee for, acceptance of support, warranty, indemnity, or other liability obligations and/or rights consistent with this License. However, in accepting such obligations, You may act only on Your own behalf and on Your sole responsibility, not on behalf of any other Contributor, and only if You agree to indemnify, defend, and hold each Contributor harmless for any liability

incurred by, or claims asserted against, such Contributor by reason of your accepting any such warranty or additional liability.

// Copyright © 2013 Steve Francia <spf@spf13.com>.

//

// Licensed under the Apache License, Version 2.0 (the "License");

// you may not use this file except in compliance with the License.

```
// You may obtain a copy of the License at
// http://www.apache.org/licenses/LICENSE-2.0
//
// Unless required by applicable law or agreed to in writing, software
// distributed under the License is distributed on an "AS IS" BASIS,
// WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
// See the License for the specific language governing permissions and
// limitations under the License.

// Commands similar to git, go tools and other modern CLI tools
// inspired by go, go-Commander, gh and subcommand
```

1.67 cobra 1.3.0

1.67.1 Available under license :

Apache License
Version 2.0, January 2004
<http://www.apache.org/licenses/>

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction, and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all other entities that control, are controlled by, or are under common control with that entity. For the purposes of this definition, "control" means (i) the power, direct or indirect, to cause the direction or management of such entity, whether by contract or otherwise, or (ii) ownership of fifty percent (50%) or more of the outstanding shares, or (iii) beneficial ownership of such entity.

"You" (or "Your") shall mean an individual or Legal Entity exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications, including but not limited to software source code, documentation source, and configuration files.

"Object" form shall mean any form resulting from mechanical transformation or translation of a Source form, including but

not limited to compiled object code, generated documentation, and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or Object form, made available under the License, as indicated by a copyright notice that is included in or attached to the work (an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object form, that is based on (or derived from) the Work and for which the editorial revisions, annotations, elaborations, or other modifications represent, as a whole, an original work of authorship. For the purposes of this License, Derivative Works shall not include works that remain separable from, or merely link (or bind by name) to the interfaces of, the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including the original version of the Work and any modifications or additions to that Work or Derivative Works thereof, that is intentionally submitted to Licensor for inclusion in the Work by the copyright owner or by an individual or Legal Entity authorized to submit on behalf of the copyright owner. For the purposes of this definition, "submitted" means any form of electronic, verbal, or written communication sent to the Licensor or its representatives, including but not limited to communication on electronic mailing lists, source code control systems, and issue tracking systems that are managed by, or on behalf of, the Licensor for the purpose of discussing and improving the Work, but excluding communication that is conspicuously marked or otherwise designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity on behalf of whom a Contribution has been received by Licensor and subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative Works of, publicly display, publicly perform, sublicense, and distribute the Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable (except as stated in this section) patent license to make, have made, use, offer to sell, sell, import, and otherwise transfer the Work,

where such license applies only to those patent claims licensable by such Contributor that are necessarily infringed by their Contribution(s) alone or by combination of their Contribution(s) with the Work to which such Contribution(s) was submitted. If You institute patent litigation against any entity (including a cross-claim or counterclaim in a lawsuit) alleging that the Work or a Contribution incorporated within the Work constitutes direct or contributory patent infringement, then any patent licenses granted to You under this License for that Work shall terminate as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute copies of the Work or Derivative Works thereof in any medium, with or without modifications, and in Source or Object form, provided that You meet the following conditions:

- (a) You must give any other recipients of the Work or Derivative Works a copy of this License; and
- (b) You must cause any modified files to carry prominent notices stating that You changed the files; and
- (c) You must retain, in the Source form of any Derivative Works that You distribute, all copyright, patent, trademark, and attribution notices from the Source form of the Work, excluding those notices that do not pertain to any part of the Derivative Works; and
- (d) If the Work includes a "NOTICE" text file as part of its distribution, then any Derivative Works that You distribute must include a readable copy of the attribution notices contained within such NOTICE file, excluding those notices that do not pertain to any part of the Derivative Works, in at least one of the following places: within a NOTICE text file distributed as part of the Derivative Works; within the Source form or documentation, if provided along with the Derivative Works; or, within a display generated by the Derivative Works, if and wherever such third-party notices normally appear. The contents of the NOTICE file are for informational purposes only and do not modify the License. You may add Your own attribution notices within Derivative Works that You distribute, alongside or as an addendum to the NOTICE text from the Work, provided that such additional attribution notices cannot be construed as modifying the License.

You may add Your own copyright statement to Your modifications and

may provide additional or different license terms and conditions

for use, reproduction, or distribution of Your modifications, or for any such Derivative Works as a whole, provided Your use, reproduction, and distribution of the Work otherwise complies with the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise, any Contribution intentionally submitted for inclusion in the Work by You to the Licensor shall be under the terms and conditions of this License, without any additional terms or conditions.

Notwithstanding the above, nothing herein shall supersede or modify the terms of any separate license agreement you may have executed with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade names, trademarks, service marks, or product names of the Licensor, except as required for reasonable and customary use in describing the origin of the Work and reproducing the content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or agreed to in writing, Licensor provides the Work (and each Contributor provides its Contributions) on an "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied, including, without limitation, any warranties or conditions of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A PARTICULAR PURPOSE. You are solely responsible for determining the appropriateness of using or redistributing the Work and assume any risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory, whether in tort (including negligence), contract, or otherwise, unless required by applicable law (such as deliberate and grossly negligent acts) or agreed to in writing, shall any Contributor be liable to You for damages, including any direct, indirect, special, incidental, or consequential damages of any character arising as a result of this License or out of the use or inability to use the Work (including but not limited to damages for loss of goodwill, work stoppage, computer failure or malfunction, or any and all other commercial damages or losses), even if such Contributor has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing the Work or Derivative Works thereof, You may choose to offer, and charge a fee for, acceptance of support, warranty, indemnity, or other liability obligations and/or rights consistent with this

License. However, in accepting such obligations, You may act only on Your own behalf and on Your sole responsibility, not on behalf of any other Contributor, and only if You agree to indemnify, defend, and hold each Contributor harmless for any liability

incurred by, or claims asserted against, such Contributor by reason of your accepting any such warranty or additional liability.

// Copyright © 2013 Steve Francia <spf@spf13.com>.

//

// Licensed under the Apache License, Version 2.0 (the "License");

// you may not use this file except in compliance with the License.

// You may obtain a copy of the License at

// <http://www.apache.org/licenses/LICENSE-2.0>

//

// Unless required by applicable law or agreed to in writing, software

// distributed under the License is distributed on an "AS IS" BASIS,

// WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.

// See the License for the specific language governing permissions and

// limitations under the License.

// Package cobra is a commander providing a simple interface to create powerful modern CLI interfaces.

// In addition to providing an interface, Cobra simultaneously provides a controller to organize your application code.

1.68 xz 5.2.2-1.3ubuntu0.1

1.68.1 Available under license :

GNU GENERAL PUBLIC LICENSE

Version 2, June 1991

Copyright (C) 1989, 1991 Free Software Foundation, Inc.,
51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA
Everyone is permitted to copy and distribute verbatim copies
of this license document, but changing it is not allowed.

Preamble

The licenses for most software are designed to take away your freedom to share and change it. By contrast, the GNU General Public License is intended to guarantee your freedom to share and change free software--to make sure the software is free for all its users. This General Public License applies to most of the Free Software Foundation's software and to any other program whose authors commit to using it. (Some other Free Software Foundation software is covered by the GNU Lesser General Public License instead.) You can apply it to your programs, too.

When we speak of free software, we are referring to freedom, not price.

Our General Public Licenses are designed to make sure that you have the freedom to distribute copies of free software (and charge for this service if you wish), that you receive source code or can get it if you want it, that you can change the software or use pieces of it in new free programs; and that you know you can do these things.

To protect your rights, we need to make restrictions that forbid anyone to deny you these rights or to ask you to surrender the rights. These restrictions translate to certain responsibilities for you if you distribute copies of the software, or if you modify it.

For example, if you distribute copies of such a program, whether gratis or for a fee, you must give the recipients all the rights that you have. You must make sure that they, too, receive or can get the source code. And you must show them these terms so they know their rights.

We protect your rights with two steps: (1) copyright the software, and (2) offer you this license which gives you legal permission to copy, distribute and/or modify the software.

Also, for each author's protection and ours, we want to make certain that everyone understands that there is no warranty for this free software. If the software is modified by someone else and passed on, we want its recipients to know that what they have is not the original, so that any problems introduced by others will not reflect on the original authors' reputations.

Finally, any free program is threatened constantly by software patents. We wish to avoid the danger that redistributors of a free program will individually obtain patent licenses, in effect making the program proprietary. To prevent this, we have made it clear that any patent must be licensed for everyone's free use or not licensed at all.

The precise terms and conditions for copying, distribution and modification follow.

GNU GENERAL PUBLIC LICENSE TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

0. This License applies to any program or other work which contains a notice placed by the copyright holder saying it may be distributed under the terms of this General Public License. The "Program", below, refers to any such program or work, and a "work based on the Program" means either the Program or any derivative work under copyright law:

that is to say, a work containing the Program or a portion of it, either verbatim or with modifications and/or translated into another language. (Hereinafter, translation is included without limitation in the term "modification".) Each licensee is addressed as "you".

Activities other than copying, distribution and modification are not covered by this License; they are outside its scope. The act of running the Program is not restricted, and the output from the Program is covered only if its contents constitute a work based on the Program (independent of having been made by running the Program). Whether that is true depends on what the Program does.

1. You may copy and distribute verbatim copies of the Program's source code as you receive it, in any medium, provided that you conspicuously and appropriately publish on each copy an appropriate copyright notice and disclaimer of warranty; keep intact all the notices that refer to this License and to the absence of any warranty; and give any other recipients of the Program a copy of this License along with the Program.

You may charge a fee for the physical act of transferring a copy, and you may at your option offer warranty protection in exchange for a fee.

2. You may modify your copy or copies of the Program or any portion of it, thus forming a work based on the Program, and copy and distribute such modifications or work under the terms of Section 1 above, provided that you also meet all of these conditions:

a) You must cause the modified files to carry prominent notices stating that you changed the files and the date of any change.

b) You must cause any work that you distribute or publish, that in whole or in part contains or is derived from the Program or any part thereof, to be licensed as a whole at no charge to all third parties under the terms of this License.

c) If the modified program normally reads commands interactively when run, you must cause it, when started running for such interactive use in the most ordinary way, to print or display an announcement including an appropriate copyright notice and a notice that there is no warranty (or else, saying that you provide a warranty) and that users may redistribute the program under these conditions, and telling the user how to view a copy of this License. (Exception: if the Program itself is interactive but does not normally print such an announcement, your work based on the Program is not required to print an announcement.)

These requirements apply to the modified work as a whole. If identifiable sections of that work are not derived from the Program, and can be reasonably considered independent and separate works in themselves, then this License, and its terms, do not apply to those sections when you distribute them as separate works. But when you distribute the same sections as part of a whole which is a work based on the Program, the distribution of the whole must be on the terms of this License, whose permissions for other licensees extend to the entire whole, and thus to each and every part regardless of who wrote it.

Thus, it is not the intent of this section to claim rights or contest your rights to work written entirely by you; rather, the intent is to exercise the right to control the distribution of derivative or collective works based on the Program.

In addition, mere aggregation of another work not based on the Program with the Program (or with a work based on the Program) on a volume of a storage or distribution medium does not bring the other work under the scope of this License.

3. You may copy and distribute the Program (or a work based on it, under Section 2) in object code or executable form under the terms of Sections 1 and 2 above provided that you also do one of the following:

a) Accompany it with the complete corresponding machine-readable source code, which must be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange; or,

b) Accompany it with a written offer, valid for at least three years, to give any third party, for a charge no more than your cost of physically performing source distribution, a complete machine-readable copy of the corresponding source code, to be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange; or,

c) Accompany it with the information you received as to the offer to distribute corresponding source code. (This alternative is allowed only for noncommercial distribution and only if you received the program in object code or executable form with such an offer, in accord with Subsection b above.)

The source code for a work means the preferred form of the work for making modifications to it. For an executable work, complete source code means all the source code for all modules it contains, plus any associated interface definition files, plus the scripts used to

control compilation and installation of the executable. However, as a special exception, the source code distributed need not include anything that is normally distributed (in either source or binary form) with the major components (compiler, kernel, and so on) of the operating system on which the executable runs, unless that component itself accompanies the executable.

If distribution of executable or object code is made by offering access to copy from a designated place, then offering equivalent access to copy the source code from the same place counts as distribution of the source code, even though third parties are not compelled to copy the source along with the object code.

4. You may not copy, modify, sublicense, or distribute the Program except as expressly provided under this License. Any attempt otherwise to copy, modify, sublicense or distribute the Program is void, and will automatically terminate your rights under this License. However, parties who have received copies, or rights, from you under this License will not have their licenses terminated so long as such parties remain in full compliance.

5. You are not required to accept this License, since you have not signed it. However, nothing else grants you permission to modify or distribute the Program or its derivative works. These actions are prohibited by law if you do not accept this License. Therefore, by modifying or distributing the Program (or any work based on the Program), you indicate your acceptance of this License to do so, and all its terms and conditions for copying, distributing or modifying the Program or works based on it.

6. Each time you redistribute the Program (or any work based on the Program), the recipient automatically receives a license from the original licensor to copy, distribute or modify the Program subject to these terms and conditions. You may not impose any further restrictions on the recipients' exercise of the rights granted herein. You are not responsible for enforcing compliance by third parties to this License.

7. If, as a consequence of a court judgment or allegation of patent infringement or for any other reason (not limited to patent issues), conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot distribute so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not distribute the Program at all. For

example, if a patent license would not permit royalty-free redistribution of the Program by all those who receive copies directly or indirectly through you, then the only way you could satisfy both it and this License would be to refrain entirely from distribution of the Program.

If any portion of this section is held invalid or unenforceable under any particular circumstance, the balance of the section is intended to apply and the section as a whole is intended to apply in other circumstances.

It is not the purpose of this section to induce you to infringe any patents or other property right claims or to contest validity of any such claims; this section has the sole purpose of protecting the integrity of the free software distribution system, which is implemented by public license practices. Many people have made generous contributions to the wide range of software distributed through that system in reliance on consistent application of that system; it is up to the author/donor to decide if he or she is willing to distribute software through any other system and a licensee cannot impose that choice.

This section is intended to make thoroughly clear what is believed to be a consequence of the rest of this License.

8. If the distribution and/or use of the Program is restricted in certain countries either by patents or by copyrighted interfaces, the original copyright holder who places the Program under this License may add an explicit geographical distribution limitation excluding those countries, so that distribution is permitted only in or among countries not thus excluded. In such case, this License incorporates the limitation as if written in the body of this License.

9. The Free Software Foundation may publish revised and/or new versions of the General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Program specifies a version number of this License which applies to it and "any later version", you have the option of following the terms and conditions either of that version or of any later version published by the Free Software Foundation. If the Program does not specify a version number of this License, you may choose any version ever published by the Free Software Foundation.

10. If you wish to incorporate parts of the Program into other free programs whose distribution conditions are different, write to the author to ask for permission. For software which is copyrighted by the Free Software Foundation, write to the Free Software Foundation; we sometimes make exceptions for this. Our decision will be guided by the two goals of preserving the free status of all derivatives of our free software and of promoting the sharing and reuse of software generally.

NO WARRANTY

11. BECAUSE THE PROGRAM IS LICENSED FREE OF CHARGE, THERE IS NO WARRANTY FOR THE PROGRAM, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE PROGRAM "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE PROGRAM IS WITH YOU. SHOULD THE PROGRAM PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

12. IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY AND/OR REDISTRIBUTE THE PROGRAM AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE PROGRAM (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE PROGRAM TO OPERATE WITH ANY OTHER PROGRAMS), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Programs

If you develop a new program, and you want it to be of the greatest possible use to the public, the best way to achieve this is to make it free software which everyone can redistribute and change under these terms.

To do so, attach the following notices to the program. It is safest to attach them to the start of each source file to most effectively convey the exclusion of warranty; and each file should have at least the "copyright" line and a pointer to where the full notice is found.

<one line to give the program's name and a brief idea of what it does.>
Copyright (C) <year> <name of author>

This program is free software; you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation; either version 2 of the License, or (at your option) any later version.

This program is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details.

You should have received a copy of the GNU General Public License along with this program; if not, write to the Free Software Foundation, Inc., 51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA.

Also add information on how to contact you by electronic and paper mail.

If the program is interactive, make it output a short notice like this when it starts in an interactive mode:

```
Gnomovision version 69, Copyright (C) year name of author
Gnomovision comes with ABSOLUTELY NO WARRANTY; for details type `show w'.
This is free software, and you are welcome to redistribute
it
under certain conditions; type `show c' for details.
```

The hypothetical commands ``show w'` and ``show c'` should show the appropriate parts of the General Public License. Of course, the commands you use may be called something other than ``show w'` and ``show c'`; they could even be mouse-clicks or menu items--whatever suits your program.

You should also get your employer (if you work as a programmer) or your school, if any, to sign a "copyright disclaimer" for the program, if necessary. Here is a sample; alter the names:

```
Yoyodyne, Inc., hereby disclaims all copyright interest in the program
`Gnomovision' (which makes passes at compilers) written by James Hacker.
```

```
<signature of Ty Coon>, 1 April 1989
Ty Coon, President of Vice
```

This General Public License does not permit incorporating your program into proprietary programs. If your program is a subroutine library, you may consider it more useful to permit linking proprietary applications with the library. If this is what you want to do, use the GNU Lesser General Public License instead of this License.

XZ Utils Licensing

=====

Different licenses apply to different files in this package. Here is a rough summary of which licenses apply to which parts of this package (but check the individual files to be sure!):

- liblzma is in the public domain.

- xz, xzdec, and lzmadec command line tools are in the public domain unless GNU getopt_long had to be compiled and linked in from the lib directory. The getopt_long code is under GNU LGPLv2.1+.

- The scripts to grep, diff, and view compressed files have been adapted from gzip. These scripts and their documentation are under GNU GPLv2+.

- All the documentation in the doc directory and most of the XZ Utils specific documentation files in other directories are in the public domain.

- Translated messages are in the public domain.

- The build system contains public domain files, and files that are under GNU GPLv2+ or GNU GPLv3+. None of these files end up in the binaries being built.

- Test files and test code in the tests directory, and debugging utilities in the debug directory are in the public domain.

- The extra directory may contain public domain files, and files that are under various free software licenses.

You can do whatever you want with the files that have been put into the public domain. If you find public domain legally problematic, take the previous sentence as a license grant. If you still find the lack of copyright legally problematic, you have too many lawyers.

As usual, this software is provided "as is", without any warranty.

If you copy significant amounts of public domain code from XZ Utils into your project, acknowledging this somewhere in your software is polite (especially if it is proprietary, non-free software), but naturally it is not legally required. Here is an example of a good

notice to
put into "about box" or into documentation:

This software includes code from XZ Utils <<http://tukaani.org/xz/>>.

The following license texts are included in the following files:

- COPYING.LGPLv2.1: GNU Lesser General Public License version 2.1
- COPYING.GPLv2: GNU General Public License version 2
- COPYING.GPLv3: GNU General Public License version 3

Note that the toolchain (compiler, linker etc.) may add some code pieces that are copyrighted. Thus, it is possible that e.g. liblzma binary wouldn't actually be in the public domain in its entirety even though it contains no copyrighted code from the XZ Utils source package.

If you have questions, don't hesitate to ask the author(s) for more information.

GNU GENERAL PUBLIC LICENSE

Version 3, 29 June 2007

Copyright (C) 2007 Free Software Foundation, Inc. <<http://fsf.org/>>

Everyone is permitted to copy and distribute verbatim copies of this license document, but changing it is not allowed.

Preamble

The GNU General Public License is a free, copyleft license for software and other kinds of works.

The licenses for most software and other practical works are designed to take away your freedom to share and change the works. By contrast, the GNU General Public License is intended to guarantee your freedom to share and change all versions of a program--to make sure it remains free software for all its users. We, the Free Software Foundation, use the GNU General Public License for most of our software; it applies also to any other work released this way by its authors. You can apply it to your programs, too.

When we speak of free software, we are referring to freedom, not price. Our General Public Licenses are designed to make sure that you have the freedom to distribute copies of free software (and charge for them if you wish), that you receive source code or can get it if you want it, that you can change the software or use pieces of it in new free programs, and that you know you can do these things.

To protect your rights, we need to prevent others from denying you

these rights or asking you to surrender the rights. Therefore, you have certain responsibilities if you distribute copies of the software, or if you modify it: responsibilities to respect the freedom of others.

For example, if you distribute copies of such a program, whether gratis or for a fee, you must pass on to the recipients the same freedoms that you received. You must make sure that they, too, receive or can get the source code. And you must show them these terms so they know their rights.

Developers that use the GNU GPL protect your rights with two steps:

(1)

assert copyright on the software, and (2) offer you this License giving you legal permission to copy, distribute and/or modify it.

For the developers' and authors' protection, the GPL clearly explains that there is no warranty for this free software. For both users' and authors' sake, the GPL requires that modified versions be marked as changed, so that their problems will not be attributed erroneously to authors of previous versions.

Some devices are designed to deny users access to install or run modified versions of the software inside them, although the manufacturer can do so. This is fundamentally incompatible with the aim of protecting users' freedom to change the software. The systematic pattern of such abuse occurs in the area of products for individuals to use, which is precisely where it is most unacceptable. Therefore, we have designed this version of the GPL to prohibit the practice for those products. If such problems arise substantially in other domains, we stand

ready to extend this provision to those domains in future versions of the GPL, as needed to protect the freedom of users.

Finally, every program is threatened constantly by software patents. States should not allow patents to restrict development and use of software on general-purpose computers, but in those that do, we wish to avoid the special danger that patents applied to a free program could make it effectively proprietary. To prevent this, the GPL assures that patents cannot be used to render the program non-free.

The precise terms and conditions for copying, distribution and modification follow.

TERMS AND CONDITIONS

0. Definitions.

"This License" refers to version 3 of the GNU General Public License.

"Copyright" also means copyright-like laws that apply to other kinds of works, such as semiconductor masks.

"The Program" refers to any copyrightable work licensed under this License. Each licensee is addressed as "you". "Licensees" and "recipients" may be individuals or organizations.

To "modify" a work means to copy from or adapt all or part of the work in a fashion requiring copyright permission, other than the making of an exact copy. The resulting work is called a "modified version" of the earlier work or a work "based on" the earlier work.

A "covered work" means either the unmodified Program or a work based on the Program.

To "propagate" a work means to do anything with it that, without permission, would make you directly or secondarily liable for infringement under applicable copyright law, except executing it on a computer or modifying a private copy. Propagation includes copying, distribution (with or without modification), making available to the public, and in some countries other activities as well.

To "convey" a work means any kind of propagation that enables other parties to make or receive copies. Mere interaction with a user through a computer network, with no transfer of a copy, is not conveying.

An interactive user interface displays "Appropriate Legal Notices" to the extent that it includes a convenient and prominently visible feature that (1) displays an appropriate copyright notice, and (2) tells the user that there is no warranty for the work (except to the extent that warranties are provided), that licensees may convey the work under this License, and how to view a copy of this License. If the interface presents a list of user commands or options, such as a menu, a prominent item in the list meets this criterion.

1. Source Code.

The "source code" for a work means the preferred form of the work for making modifications to it. "Object code" means any non-source form of a work.

A "Standard Interface" means an interface that either is an official standard defined by a recognized standards body, or, in the case of interfaces specified for a particular programming language, one that is widely used among developers working in that language.

The

"System Libraries" of an executable work include anything, other than the work as a whole, that (a) is included in the normal form of packaging a Major Component, but which is not part of that Major Component, and (b) serves only to enable use of the work with that Major Component, or to implement a Standard Interface for which an implementation is available to the public in source code form. A "Major Component", in this context, means a major essential component (kernel, window system, and so on) of the specific operating system (if any) on which the executable work runs, or a compiler used to produce the work, or an object code interpreter used to run it.

The "Corresponding Source" for a work in object code form means all the source code needed to generate, install, and (for an executable work) run the object code and to modify the work, including scripts to control those activities. However, it does not include the work's System Libraries, or general-purpose tools or generally available free programs which are used unmodified in performing those activities but which are not part of the work. For example, Corresponding Source includes interface definition files associated with source files for the work, and the source code for shared libraries and dynamically linked subprograms that the work is specifically designed to require, such as by intimate data communication or control flow between those subprograms and other parts of the work.

The Corresponding Source need not include anything that users can regenerate automatically from other parts of the Corresponding Source.

The Corresponding Source for a work in source code form is that same work.

2. Basic Permissions.

All rights granted under this License are granted for the term of copyright on the Program, and are irrevocable provided the stated conditions are met. This License explicitly affirms your unlimited permission to run the unmodified Program. The output from running a covered work is covered by this License only if the output, given its content, constitutes a covered work. This License acknowledges your rights of fair use or other equivalent, as provided by copyright law.

You may make, run and propagate covered works that you do not convey, without conditions so long as your license otherwise remains in force. You may convey covered works to others for the sole purpose

of having them make modifications exclusively for you, or provide you with facilities for running those works, provided that you comply with the terms of this License in conveying all material for which you do not control copyright. Those thus making or running the covered works for you must do so exclusively on your behalf, under your direction and control, on terms that prohibit them from making any copies of your copyrighted material outside their relationship with you.

Conveying under any other circumstances is permitted solely under the conditions stated below. Sublicensing is not allowed; section 10 makes it unnecessary.

3. Protecting Users' Legal Rights From Anti-Circumvention Law.

No covered work shall be deemed part of an effective technological measure under any applicable law fulfilling obligations under article 11 of the WIPO copyright treaty adopted on 20 December 1996, or similar laws prohibiting or restricting circumvention of such measures.

When you convey a covered work, you waive any legal power to forbid circumvention of technological measures to the extent such circumvention is effected by exercising rights under this License with respect to the covered work, and you disclaim any intention to limit operation or modification of the work as a means of enforcing, against the work's users, your or third parties' legal rights to forbid circumvention of technological measures.

4. Conveying Verbatim Copies.

You may convey verbatim copies of the Program's source code as you receive it, in any medium, provided that you conspicuously and appropriately publish on each copy an appropriate copyright notice; keep intact all notices stating that this License and any non-permissive terms added in accord with section 7 apply to the code; keep intact all notices of the absence of any warranty; and give all recipients a copy of this License along with the Program.

You may charge any price or no price for each copy that you convey, and you may offer support or warranty protection for a fee.

5. Conveying Modified Source Versions.

You may convey a work based on the Program, or the modifications to produce it from the Program, in the form of source code under the terms of section 4, provided that you also meet all of these conditions:

- a) The work must carry prominent notices stating that you modified it, and giving a relevant date.

- b) The work must carry prominent notices stating that it is released under this License and any conditions added under section 7. This requirement modifies the requirement in section 4 to "keep intact all notices".

- c) You must license the entire work, as a whole, under this License to anyone who comes into possession of a copy. This License will therefore apply, along with any applicable section 7 additional terms, to the whole of the work, and all its parts, regardless of how they are packaged. This License gives no permission to license the work in any other way, but it does not invalidate such permission if you have separately received it.

- d) If the work has interactive user interfaces, each must display Appropriate Legal Notices; however, if the Program has interactive interfaces that do not display Appropriate Legal Notices, your work need not make them do so.

A compilation of a covered work with other separate and independent works, which are not by their nature extensions of the covered work, and which are not combined with it such as to form a larger program, in or on a volume of a storage or distribution medium, is called an "aggregate" if the compilation and its resulting copyright are not used to limit the access or legal rights of the compilation's users beyond what the individual works permit. Inclusion of a covered work in an aggregate does not cause this License to apply to the other parts of the aggregate.

6. Conveying Non-Source Forms.

You may convey a covered work in object code form under the terms of sections 4 and 5, provided that you also convey the machine-readable Corresponding Source under the terms of this License, in one of these ways:

- a) Convey the object code in, or embodied in, a physical product (including a physical distribution medium), accompanied by the Corresponding Source fixed on a durable physical medium customarily used for software interchange.

- b) Convey the object code in, or embodied in, a physical product (including a physical distribution medium), accompanied by a

written offer, valid for at least three years

and valid for as

long as you offer spare parts or customer support for that product model, to give anyone who possesses the object code either (1) a copy of the Corresponding Source for all the software in the product that is covered by this License, on a durable physical medium customarily used for software interchange, for a price no more than your reasonable cost of physically performing this conveying of source, or (2) access to copy the Corresponding Source from a network server at no charge.

c) Convey individual copies of the object code with a copy of the written offer to provide the Corresponding Source. This alternative is allowed only occasionally and noncommercially, and only if you received the object code with such an offer, in accord with subsection 6b.

d) Convey the object code by offering access from a designated place (gratis or for a charge), and offer equivalent access to the Corresponding Source in the same way through the same place at no further charge. You need not require recipients to copy the Corresponding Source along with the object code. If the place to copy the object code is a network server, the Corresponding Source may be on a different server (operated by you or a third party) that supports equivalent copying facilities, provided you maintain clear directions next to the object code saying where to find the Corresponding Source. Regardless of what server hosts the Corresponding Source, you remain obligated to ensure that it is available for as long as needed to satisfy these requirements.

e) Convey the object code using peer-to-peer transmission, provided you inform other peers where the object code and Corresponding Source of the work are being offered to the general public at no charge under subsection 6d.

A separable portion of the object code, whose source code is excluded from the Corresponding Source as a System Library, need not be included in conveying the object code work.

A "User Product" is either (1) a "consumer product", which means any tangible personal property which is normally used for personal, family, or household purposes, or (2) anything designed or sold for incorporation into a dwelling. In determining whether a product is a consumer product, doubtful cases shall be resolved in favor of coverage. For a particular product received by a particular user, "normally used" refers to a typical or common use of that class of product, regardless of the status

of the particular user or of the way in which the particular user actually uses, or expects or is expected to use, the product. A product is a consumer product regardless of whether the product has substantial commercial, industrial or non-consumer uses, unless such uses represent the only significant mode of use of the product.

"Installation Information" for a User Product means any methods, procedures, authorization keys, or other information required to install and execute modified versions of a covered work in that User Product from a modified version of its Corresponding Source. The information must suffice to ensure that the continued functioning of the modified object code is in no case prevented or interfered with solely because modification has been made.

If you convey an object code work under this section in, or with, or specifically for use in, a User Product, and the conveying occurs as part of a transaction in which the right of possession and use of the User Product is transferred to the recipient in perpetuity or for a fixed term (regardless of how the transaction is characterized), the Corresponding Source conveyed under this section must be accompanied by the Installation Information. But this requirement does not apply if neither you nor any third party retains the ability to install modified object code on the User Product (for example, the work has been installed in ROM).

The requirement to provide Installation Information does not include a requirement to continue to provide support service, warranty, or updates for a work that has been modified or installed by the recipient, or for the User Product in which it has been modified or installed. Access to a network may be denied when the modification itself materially and adversely affects the operation of the network or violates the rules and protocols for communication across the network.

Corresponding Source conveyed, and Installation Information provided, in accord with this section must be in a format that is publicly documented (and with an implementation available to the public in source code form), and must require no special password or key for unpacking, reading or copying.

7. Additional Terms.

"Additional permissions" are terms that supplement the terms of this License by making exceptions from one or more of its conditions. Additional permissions that are applicable to the entire Program shall be treated as though they were included in this License, to the extent

that they are valid under applicable law. If additional permissions apply only to part of the Program, that part may be used separately under those permissions, but the entire Program remains governed by this License without regard to the additional permissions.

When you convey a copy of a covered work, you may at your option remove any additional permissions from that copy, or from any part of it. (Additional permissions may be written to require their own removal in certain cases when you modify the work.) You may place additional permissions on material, added by you to a covered work, for which you have or can give appropriate copyright permission.

Notwithstanding any other provision of this License, for material you add to a covered work, you may (if authorized by the copyright holders of that material) supplement the terms of this License with terms:

- a) Disclaiming warranty or limiting liability differently from the terms of sections 15 and 16 of this License; or
- b) Requiring preservation of specified reasonable legal notices or author attributions in that material or in the Appropriate Legal Notices displayed by works containing it; or
- c) Prohibiting misrepresentation of the origin of that material, or requiring that modified versions of such material be marked in reasonable ways as different from the original version; or
- d) Limiting the use for publicity purposes of names of licensors or authors of the material; or
- e) Declining to grant rights under trademark law for use of some trade names, trademarks, or service marks; or
- f) Requiring indemnification of licensors and authors of that material by anyone who conveys the material (or modified versions of it) with contractual assumptions of liability to the recipient, for any liability that these contractual assumptions directly impose on those licensors and authors.

All other non-permissive additional terms are considered "further restrictions" within the meaning of section 10. If the Program as you received it, or any part of it, contains a notice stating that it is governed by this License along with a term that is a further restriction, you may remove that term. If a license document contains a further restriction but permits relicensing or conveying under this License, you may add to a covered work material governed by the terms

of that license document, provided that the further restriction does not survive such relicensing or conveying.

If you add terms to a covered work in accord with this section, you must place, in the relevant source files, a statement of the additional terms that apply to those files, or a notice indicating where to find the applicable terms.

Additional terms, permissive or non-permissive, may be stated in the form of a separately written license, or stated as exceptions; the above requirements apply either way.

8. Termination.

You may not propagate or modify a covered work except as expressly provided under this License. Any attempt otherwise to propagate or modify it is void, and will automatically terminate your rights under this License (including any patent licenses granted under the third paragraph of section 11).

However, if you cease all violation of this License, then your license from a particular copyright holder is reinstated (a) provisionally, unless and until the copyright holder explicitly and finally terminates your license, and (b) permanently, if the copyright holder fails to notify you of the violation by some reasonable means prior to 60 days after the cessation.

Moreover, your license from a particular copyright holder is reinstated permanently if the copyright holder notifies you of the violation by some reasonable means, this is the first time you have received notice of violation of this License (for any work) from that copyright holder, and you cure the violation prior to 30 days after your receipt of the notice.

Termination of your rights under this section does not terminate the licenses of parties who have received copies or rights from you under this License. If your rights have been terminated and not permanently reinstated, you do not qualify to receive new licenses for the same material under section 10.

9. Acceptance Not Required for Having Copies.

You are not required to accept this License in order to receive or run a copy of the Program. Ancillary propagation of a covered work occurring solely as a consequence of using peer-to-peer transmission to receive a copy likewise does not require acceptance. However,

nothing other than this License grants you permission to propagate or modify any covered work. These actions infringe copyright if you do not accept this License. Therefore, by modifying or propagating a covered work, you indicate your acceptance of this License to do so.

10. Automatic Licensing of Downstream Recipients.

Each time you convey a covered work, the recipient automatically receives a license from the original licensors, to run, modify and propagate that work, subject to this License. You are not responsible for enforcing compliance by third parties with this License.

An "entity transaction" is a transaction transferring control of an organization, or substantially all assets of one, or subdividing an organization, or merging organizations. If propagation of a covered work results from an entity transaction, each party to that transaction who receives a copy of the work also receives whatever licenses to the work the party's predecessor in interest had or could give under the previous paragraph, plus a right to possession of the Corresponding Source of the work from the predecessor in interest, if the predecessor has it or can get it with reasonable efforts.

You may not impose any further restrictions on the exercise of the rights granted or affirmed under this License. For example, you may not impose a license fee, royalty, or other charge for exercise of rights granted under this License, and you may not initiate litigation (including a cross-claim or counterclaim in a lawsuit) alleging that any patent claim is infringed by making, using, selling, offering for sale, or importing the Program or any portion of it.

11. Patents.

A "contributor" is a copyright holder who authorizes use under this License of the Program or a work on which the Program is based. The work thus licensed is called the contributor's "contributor version".

A contributor's "essential patent claims" are all patent claims owned or controlled by the contributor, whether already acquired or hereafter acquired, that would be infringed by some manner, permitted by this License, of making, using, or selling its contributor version, but do not include claims that would be infringed only as a consequence of further modification of the contributor version. For purposes of this definition, "control" includes the right to grant patent sublicenses in a manner consistent with the requirements of this License.

Each contributor grants you a non-exclusive, worldwide, royalty-free patent license under the contributor's essential patent claims, to make, use, sell, offer for sale, import and otherwise run, modify and propagate the contents of its contributor version.

In the following three paragraphs, a "patent license" is any express agreement or commitment, however denominated, not to enforce a patent (such as an express permission to practice a patent or covenant not to sue for patent infringement). To "grant" such a patent license to a party means to make such an agreement or commitment not to enforce a patent against the party.

If you convey a covered work, knowingly relying on a patent license, and the Corresponding Source of the work is not available for anyone to copy, free of charge and under the terms of this

License, through a publicly available network server or other readily accessible means, then you must either (1) cause the Corresponding Source to be so available, or (2) arrange to deprive yourself of the benefit of the patent license for this particular work, or (3) arrange, in a manner consistent with the requirements of this License, to extend the patent license to downstream recipients. "Knowingly relying" means you have actual knowledge that, but for the patent license, your conveying the covered work in a country, or your recipient's use of the covered work in a country, would infringe one or more identifiable patents in that country that you have reason to believe are valid.

If, pursuant to or in connection with a single transaction or arrangement, you convey, or propagate by procuring conveyance of, a covered work, and grant a patent license to some of the parties receiving the covered work authorizing them to use, propagate, modify or convey a specific copy of the covered work, then the patent license you grant is automatically extended to all recipients of the covered work and works based on it.

A patent license is "discriminatory" if it does not include within the scope of its coverage, prohibits the exercise of, or is conditioned on the non-exercise of one or more of the rights that are specifically granted under this License. You may not convey a covered work if you are a party to an arrangement with a third party that is in the business of distributing software, under which you make payment to the third party based on the extent of your activity of conveying the work, and under which the third party grants, to any of the parties who would receive the covered work from you, a discriminatory patent license (a) in connection with copies of the covered work conveyed by you (or copies made from those copies), or (b) primarily

for and in connection with specific products or compilations that contain the covered work, unless you entered into that arrangement, or that patent license was granted, prior to 28 March 2007.

Nothing in this License shall be construed as excluding or limiting any implied license or other defenses to infringement that may otherwise be available to you under applicable patent law.

12. No Surrender of Others' Freedom.

If conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot convey a covered work so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not convey it at all. For example, if you agree to terms that obligate you to collect a royalty for further conveying from those to whom you convey the Program, the only way you could satisfy both those terms and this License would be to refrain entirely from conveying the Program.

13. Use with the GNU Affero General Public License.

Notwithstanding any other provision of this License, you have permission to link or combine any covered work with a work licensed under version 3 of the GNU Affero General Public License into a single combined work, and to convey the resulting work. The terms of this License will continue to apply to the part which is the covered work, but the special requirements of the GNU Affero General Public License, section 13, concerning interaction through a network will apply to the combination as such.

14. Revised Versions of this License.

The Free Software Foundation may publish revised and/or new versions of the GNU General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Program specifies that a certain numbered version of the GNU General Public License "or any later version" applies to it, you have the option of following the terms and conditions either of that numbered version or of any later version published by the Free Software Foundation. If the Program does not specify a version number of the GNU General Public License, you may choose any version ever published by the Free Software Foundation.

If the Program specifies that a proxy can decide which future versions of the GNU General Public License can be used, that proxy's public statement of acceptance of a version permanently authorizes you to choose that version for the Program.

Later license versions may give you additional or different permissions. However, no additional obligations are imposed on any author or copyright holder as a result of your choosing to follow a later version.

15. Disclaimer of Warranty.

THERE IS NO WARRANTY FOR THE PROGRAM, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE PROGRAM "AS IS"

WITHOUT WARRANTY

OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE PROGRAM IS WITH YOU. SHOULD THE PROGRAM PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

16. Limitation of Liability.

IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MODIFIES AND/OR CONVEYS THE PROGRAM AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE PROGRAM (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE PROGRAM TO OPERATE WITH ANY OTHER PROGRAMS), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

17.

Interpretation of Sections 15 and 16.

If the disclaimer of warranty and limitation of liability provided above cannot be given local legal effect according to their terms, reviewing courts shall apply local law that most closely approximates an absolute waiver of all civil liability in connection with the Program, unless a warranty or assumption of liability accompanies a copy of the Program in return for a fee.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Programs

If you develop a new program, and you want it to be of the greatest possible use to the public, the best way to achieve this is to make it free software which everyone can redistribute and change under these terms.

To do so, attach the following notices to the program. It is safest to attach them to the start of each source file to most effectively state the exclusion of warranty; and each file should have at least the "copyright" line and a pointer to where the full notice is found.

```
<one line to give the program's name and a brief idea of what it does.>  
Copyright (C) <year> <name of author>
```

This program is free software: you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation, either version 3 of the License, or (at your option) any later version.

This program is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details.

You should have received a copy of the GNU General Public License along with this program. If not, see <http://www.gnu.org/licenses/>.

Also add information on how to contact you by electronic and paper mail.

If the program does terminal interaction, make it output a short notice like this when it starts in an interactive mode:

```
<program> Copyright (C) <year> <name of author>  
This program comes with ABSOLUTELY NO WARRANTY; for details type `show w'.  
This is free software, and you are welcome to redistribute it  
under certain conditions; type `show c' for details.
```

The hypothetical commands `show w' and `show c' should show the appropriate parts of the General Public License. Of course, your program's commands might be different; for a GUI interface, you would use an "about box".

You should also get your employer (if you work as a programmer) or school, if any, to sign a "copyright disclaimer" for the program, if necessary. For more information on this, and how to apply and follow the GNU GPL, see <http://www.gnu.org/licenses/>.

The GNU General Public License does not permit incorporating your program

into proprietary programs. If your program is a subroutine library, you may consider it more useful to permit linking proprietary applications with the library. If this is what you want to do, use the GNU Lesser General Public License instead of this License. But first, please read <<http://www.gnu.org/philosophy/why-not-lgpl.html>>.

1.69 gzip 1.6-5ubuntu1.2

1.69.1 Available under license :

This package is maintained for Debian by Bdale Garbee <bdale@gag.com>, and was built from the sources found at:

`ftp://ftp.gnu.org/gnu/gzip/`

Copyright (C) 1999, 2001-2002, 2006-2007, 2009-2010 Free Software Foundation, Inc.

Copyright (C) 1992-1993 Jean-loup Gailly

This program is free software; you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation; either version 3, or (at your option) any later version.

This program is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details.

You should have received a copy of the GNU General Public License along with this program; if not, write to the Free Software Foundation, Inc., 51 Franklin Street, Fifth Floor, Boston, MA 02110-1301, USA. */

On Debian GNU/Linux systems, the complete text of the GNU General Public License can be found in `"/usr/share/common-licenses/GPL"`.

1.70 liblzma 5.2.2-1.3ubuntu0.1

1.70.1 Available under license :

GNU GENERAL PUBLIC LICENSE
Version 2, June 1991

Copyright (C) 1989, 1991 Free Software Foundation, Inc.,
51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA
Everyone is permitted to copy and distribute verbatim copies

of this license document, but changing it is not allowed.

Preamble

The licenses for most software are designed to take away your freedom to share and change it. By contrast, the GNU General Public License is intended to guarantee your freedom to share and change free software--to make sure the software is free for all its users. This General Public License applies to most of the Free Software Foundation's software and to any other program whose authors commit to using it. (Some other Free Software Foundation software is covered by the GNU Lesser General Public License instead.) You can apply it to your programs, too.

When we speak of free software, we are referring to freedom, not price.

Our General Public Licenses are designed to make sure that you have the freedom to distribute copies of free software (and charge for this service if you wish), that you receive source code or can get it if you want it, that you can change the software or use pieces of it in new free programs; and that you know you can do these things.

To protect your rights, we need to make restrictions that forbid anyone to deny you these rights or to ask you to surrender the rights. These restrictions translate to certain responsibilities for you if you distribute copies of the software, or if you modify it.

For example, if you distribute copies of such a program, whether gratis or for a fee, you must give the recipients all the rights that you have. You must make sure that they, too, receive or can get the source code. And you must show them these terms so they know their rights.

We protect your rights with two steps: (1) copyright the software, and (2) offer you this license which gives you legal permission to copy, distribute and/or modify the software.

Also, for each author's protection and ours, we want to make certain that everyone understands that there is no warranty for this free software. If the software is modified by someone else and passed on, we want its recipients to know that what they have is not the original, so that any problems introduced by others will not reflect on the original authors' reputations.

Finally, any free program is threatened constantly by software patents. We wish to avoid the danger that redistributors of a free program will individually obtain patent licenses, in effect making the

program proprietary. To prevent this, we have made it clear that any patent must be licensed for everyone's free use or not licensed at all.

The precise terms and conditions for copying, distribution and modification follow.

GNU GENERAL PUBLIC LICENSE
TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

0. This License applies to any program or other work which contains a notice placed by the copyright holder saying it may be distributed under the terms of this General Public License. The "Program", below, refers to any such program or work, and a "work based on the Program" means either the Program or any derivative work under copyright law: that is to say, a work containing the Program or a portion of it, either verbatim or with modifications and/or translated into another language. (Hereinafter, translation is included without limitation in the term "modification".) Each licensee is addressed as "you".

Activities other than copying, distribution and modification are not covered by this License; they are outside its scope. The act of running the Program is not restricted, and the output from the Program is covered only if its contents constitute a work based on the Program (independent of having been made by running the Program). Whether that is true depends on what the Program does.

1. You may copy and distribute verbatim copies of the Program's source code as you receive it, in any medium, provided that you conspicuously and appropriately publish on each copy an appropriate copyright notice and disclaimer of warranty; keep intact all the notices that refer to this License and to the absence of any warranty; and give any other recipients of the Program a copy of this License along with the Program.

You may charge a fee for the physical act of transferring a copy, and you may at your option offer warranty protection in exchange for a fee.

2. You may modify your copy or copies of the Program or any portion of it, thus forming a work based on the Program, and copy and distribute such modifications or work under the terms of Section 1 above, provided that you also meet all of these conditions:

- a) You must cause the modified files to carry prominent notices stating that you changed the files and the date of any change.
- b) You must cause

any work that you distribute or publish, that in whole or in part contains or is derived from the Program or any part thereof, to be licensed as a whole at no charge to all third parties under the terms of this License.

c) If the modified program normally reads commands interactively when run, you must cause it, when started running for such interactive use in the most ordinary way, to print or display an announcement including an appropriate copyright notice and a notice that there is no warranty (or else, saying that you provide a warranty) and that users may redistribute the program under these conditions, and telling the user how to view a copy of this License. (Exception: if the Program itself is interactive but does not normally print such an announcement, your work based on the Program is not required to print an announcement.)

These requirements apply to the modified work as a whole. If identifiable sections of that work are not derived from the Program, and can be reasonably considered independent and separate works in themselves, then this License, and its terms, do not apply to those sections when you distribute them as separate works. But when you distribute the same sections as part of a whole which is a work based on the Program, the distribution of the whole must be on the terms of this License, whose permissions for other licensees extend to the entire whole, and thus to each and every part regardless of who wrote it.

Thus, it is not the intent of this section to claim rights or contest your rights to work written entirely by you; rather, the intent is to exercise the right to control the distribution of derivative or collective works based on the Program.

In addition, mere aggregation of another work not based on the Program with the Program (or with a work based on the Program) on a volume of a storage or distribution medium does not bring the other work under the scope of this License.

3. You may copy and distribute the Program (or a work based on it, under Section 2) in object code or executable form under the terms of Sections 1 and 2 above provided that you also do one of the following:

a) Accompany it with the complete corresponding machine-readable source code, which must be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange; or,

b) Accompany it with a written offer, valid for at least three years, to give any third party, for a charge no more than your cost of physically performing source distribution, a complete

machine-readable copy of the corresponding source code, to be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange; or,

c) Accompany it with the information you received as to the offer to distribute corresponding source code. (This alternative is allowed only for noncommercial distribution and only if you received the program in object code or executable form with such an offer, in accord with Subsection b above.)

The source code for a work means the preferred form of the work for making modifications to it. For an executable work, complete source code means all the source code for all modules it contains, plus any associated interface definition files, plus the scripts used to control compilation and installation of the executable. However, as a special exception, the source code distributed need not include anything that is normally distributed (in either source or binary form) with the major components (compiler, kernel, and so on) of the operating system on which the executable runs, unless that component itself accompanies the executable.

If distribution of executable or object code is made by offering access to copy from a designated place, then offering equivalent access to copy the source code from the same place counts as distribution of the source code, even though third parties are not compelled to copy the source along with the object code.

4. You may not copy, modify, sublicense, or distribute the Program except as expressly provided under this License. Any attempt otherwise to copy, modify, sublicense or distribute the Program is void, and will automatically terminate your rights under this License. However, parties who have received copies, or rights, from you under this License will not have their licenses terminated so long as such parties remain in full compliance.

5. You are not required to accept this License, since you have not signed it. However, nothing else grants you permission to modify or distribute the Program or its derivative works. These actions are prohibited by law if you do not accept this License. Therefore, by modifying or distributing the Program (or any work based on the Program), you indicate your acceptance of this License to do so, and all its terms and conditions for copying, distributing or modifying the Program or works based on it.

6. Each time you redistribute the Program (or any work based on the

Program), the recipient automatically receives a license from the original licensor to copy, distribute or modify the Program subject to these terms and conditions. You may not impose any further restrictions on the recipients' exercise of the rights granted herein. You are not responsible for enforcing compliance by third parties to this License.

7. If, as a consequence of a court judgment or allegation of patent infringement or for any other reason (not limited to patent issues), conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot distribute so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not distribute the Program at all. For example, if a patent license would not permit royalty-free redistribution of the Program by all those who receive copies directly or indirectly through you, then the only way you could satisfy both it and this License would be to refrain entirely from distribution of the Program.

If any portion of this section is held invalid or unenforceable under any particular circumstance, the balance of the section is intended to apply and the section as a whole is intended to apply in other circumstances.

It is not the purpose of this section to induce you to infringe any patents or other property right claims or to contest validity of any such claims; this section has the sole purpose of protecting the integrity of the free software distribution system, which is implemented by public license practices. Many people have made generous contributions to the wide range of software distributed through that system in reliance on consistent application of that system; it is up to the author/donor to decide if he or she is willing to distribute software through any other system and a licensee cannot impose that choice.

This section is intended to make thoroughly clear what is believed to be a consequence of the rest of this License.

8. If the distribution and/or use of the Program is restricted in certain countries either by patents or by copyrighted interfaces, the original copyright holder who places the Program under this License may add an explicit geographical distribution limitation excluding those countries, so that distribution is permitted only in or among countries not thus excluded. In such case, this License incorporates the limitation as if written in the body of this License.

9. The Free Software Foundation may publish revised and/or new versions of the General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Program specifies a version number of this License which applies to it and "any later version", you have the option of following the terms and conditions either of that version or of any later version published by the Free Software Foundation. If the Program does not specify a version number of this License, you may choose any version ever published by the Free Software Foundation.

10. If you wish to incorporate parts of the Program into other free programs whose distribution conditions are different, write to the author to ask for permission. For software which is copyrighted by the Free Software Foundation, write to the Free Software Foundation; we sometimes make exceptions for this. Our decision will be guided by the two goals of preserving the free status of all derivatives of our free software and of promoting the sharing and reuse of software generally.

NO WARRANTY

11. BECAUSE THE PROGRAM IS LICENSED FREE OF CHARGE, THERE IS NO WARRANTY FOR THE PROGRAM, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE PROGRAM "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE PROGRAM IS WITH YOU. SHOULD THE PROGRAM PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

12. IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY AND/OR REDISTRIBUTE THE PROGRAM AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE PROGRAM (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE PROGRAM TO OPERATE WITH ANY OTHER PROGRAMS), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Programs

If you develop a new program, and you want it to be of the greatest possible use to the public, the best way to achieve this is to make it free software which everyone can redistribute and change under these terms.

To do so, attach the following notices to the program. It is safest to attach them to the start of each source file to most effectively convey the exclusion of warranty; and each file should have at least the "copyright" line and a pointer to where the full notice is found.

```
<one line to give the program's name and a brief idea of what it does.>  
Copyright (C) <year> <name of author>
```

This program is free software; you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation; either version 2 of the License, or (at your option) any later version.

This program is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details.

You should have received a copy of the GNU General Public License along with this program; if not, write to the Free Software Foundation, Inc., 51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA.

Also add information on how to contact you by electronic and paper mail.

If the program is interactive, make it output a short notice like this when it starts in an interactive mode:

```
Gnomovision version 69, Copyright (C) year name of author  
Gnomovision comes with ABSOLUTELY NO WARRANTY; for details type `show w'.  
This is free software, and you are welcome to redistribute  
it  
under certain conditions; type `show c' for details.
```

The hypothetical commands `show w' and `show c' should show the appropriate parts of the General Public License. Of course, the commands you use may be called something other than `show w' and `show c'; they could even be mouse-clicks or menu items--whatever suits your program.

You should also get your employer (if you work as a programmer) or your school, if any, to sign a "copyright disclaimer" for the program, if

necessary. Here is a sample; alter the names:

Yoyodyne, Inc., hereby disclaims all copyright interest in the program
'Gnomovision' (which makes passes at compilers) written by James Hacker.

<signature of Ty Coon>, 1 April 1989

Ty Coon, President of Vice

This General Public License does not permit incorporating your program into
proprietary programs. If your program is a subroutine library, you may
consider it more useful to permit linking proprietary applications with the
library. If this
is what you want to do, use the GNU Lesser General
Public License instead of this License.

XZ Utils Licensing

=====

Different licenses apply to different files in this package. Here
is a rough summary of which licenses apply to which parts of this
package (but check the individual files to be sure!):

- liblzma is in the public domain.
- xz, xzdec, and lzmadec command line tools are in the public
domain unless GNU getopt_long had to be compiled and linked
in from the lib directory. The getopt_long code is under
GNU LGPLv2.1+.
- The scripts to grep, diff, and view compressed files have been
adapted from gzip. These scripts and their documentation are
under GNU GPLv2+.
- All the documentation in the doc directory and most of the
XZ Utils specific documentation files in other directories
are in the public domain.
- Translated messages are in the public domain.
- The build system contains public domain files, and files that
are under GNU GPLv2+ or GNU
GPLv3+. None of these files end up
in the binaries being built.
- Test files and test code in the tests directory, and debugging
utilities in the debug directory are in the public domain.
- The extra directory may contain public domain files, and files

that are under various free software licenses.

You can do whatever you want with the files that have been put into the public domain. If you find public domain legally problematic, take the previous sentence as a license grant. If you still find the lack of copyright legally problematic, you have too many lawyers.

As usual, this software is provided "as is", without any warranty.

If you copy significant amounts of public domain code from XZ Utils into your project, acknowledging this somewhere in your software is polite (especially if it is proprietary, non-free software), but naturally it is not legally required. Here is an example of a good notice to put into "about box" or into documentation:

This software includes code from XZ Utils <<http://tukaani.org/xz/>>.

The following license texts are included in the following files:

- COPYING.LGPLv2.1: GNU Lesser General Public License version 2.1
- COPYING.GPLv2: GNU General Public License version 2
- COPYING.GPLv3: GNU General Public License version 3

Note that the toolchain (compiler, linker etc.) may add some code pieces that are copyrighted. Thus, it is possible that e.g. liblzma binary wouldn't actually be in the public domain in its entirety even though it contains no copyrighted code from the XZ Utils source package.

If you have questions, don't hesitate to ask the author(s) for more information.

GNU GENERAL PUBLIC LICENSE

Version 3, 29 June 2007

Copyright (C) 2007 Free Software Foundation, Inc. <<http://fsf.org/>>

Everyone is permitted to copy and distribute verbatim copies of this license document, but changing it is not allowed.

Preamble

The GNU General Public License is a free, copyleft license for software and other kinds of works.

The licenses for most software and other practical works are designed to take away your freedom to share and change the works. By contrast, the GNU General Public License is intended to guarantee your freedom to share and change all versions of a program--to make sure it remains free

software for all its users. We, the Free Software Foundation, use the GNU General Public License for most of our software; it applies also to any other work released this way by its authors. You can apply it to your programs, too.

When we speak of free software, we are referring to freedom, not price. Our General Public Licenses are designed to make sure that you have the freedom to distribute copies of free software (and charge for them if you wish), that you receive source code or can get it if you want it, that you can change the software or use pieces of it in new free programs, and that you know you can do these things.

To protect your rights, we need to prevent others from denying you these rights or asking you to surrender the rights. Therefore, you have certain responsibilities if you distribute copies of the software, or if you modify it: responsibilities to respect the freedom of others.

For example, if you distribute copies of such a program, whether gratis or for a fee, you must pass on to the recipients the same freedoms that you received. You must make sure that they, too, receive or can get the source code. And you must show them these terms so they know their rights.

Developers that use the GNU GPL protect your rights with two steps:

- (1) assert copyright on the software, and (2) offer you this License giving you legal permission to copy, distribute and/or modify it.

For the developers' and authors' protection, the GPL clearly explains that there is no warranty for this free software. For both users' and authors' sake, the GPL requires that modified versions be marked as changed, so that their problems will not be attributed erroneously to authors of previous versions.

Some devices are designed to deny users access to install or run modified versions of the software inside them, although the manufacturer can do so. This is fundamentally incompatible with the aim of protecting users' freedom to change the software. The systematic pattern of such abuse occurs in the area of products for individuals to use, which is precisely where it is most unacceptable. Therefore, we have designed this version of the GPL to prohibit the practice for those products. If such problems arise substantially in other domains, we stand ready to extend this provision to those domains in future versions of the GPL, as needed to protect the freedom of users.

Finally, every program is threatened constantly by software patents.

States should not allow patents to restrict development and use of software on general-purpose computers, but in those that do, we wish to avoid the special danger that patents applied to a free program could make it effectively proprietary. To prevent this, the GPL assures that patents cannot be used to render the program non-free.

The precise terms and conditions for copying, distribution and modification follow.

TERMS AND CONDITIONS

0. Definitions.

"This License" refers to version 3 of the GNU General Public License.

"Copyright" also means copyright-like laws that apply to other kinds of works, such as semiconductor masks.

"The Program" refers to any copyrightable work licensed under this License. Each licensee is addressed as "you". "Licensees" and "recipients" may be individuals or organizations.

To "modify" a work means to copy from or adapt all or part of the work in a fashion requiring copyright permission, other than the making of an exact copy. The resulting work is called a "modified version" of the earlier work or a work "based on" the earlier work.

A "covered work" means either the unmodified Program or a work based on the Program.

To "propagate" a work means to do anything with it that, without permission, would make you directly or secondarily liable for infringement under applicable copyright law, except executing it on a computer or modifying a private copy. Propagation includes copying, distribution (with or without modification), making available to the public, and in some countries other activities as well.

To "convey" a work means any kind of propagation that enables other parties to make or receive copies. Mere interaction with a user through a computer network, with no transfer of a copy, is not conveying.

An interactive user interface displays "Appropriate Legal Notices" to the extent that it includes a convenient and prominently visible feature that (1) displays an appropriate copyright notice, and (2) tells the user that there is no warranty for the work (except to the extent that warranties are provided), that licensees may convey the

work under this License, and how to view a copy of this License. If the interface presents a list of user commands or options, such as a menu, a prominent item in the list meets this criterion.

1. Source Code.

The "source code" for a work means the preferred form of the work for making modifications to it. "Object code" means any non-source form of a work.

A "Standard Interface" means an interface that either is an official standard defined by a recognized standards body, or, in the case of interfaces specified for a particular programming language, one that is widely used among developers working in that language.

The

"System Libraries" of an executable work include anything, other than the work as a whole, that (a) is included in the normal form of packaging a Major Component, but which is not part of that Major Component, and (b) serves only to enable use of the work with that Major Component, or to implement a Standard Interface for which an implementation is available to the public in source code form. A "Major Component", in this context, means a major essential component (kernel, window system, and so on) of the specific operating system (if any) on which the executable work runs, or a compiler used to produce the work, or an object code interpreter used to run it.

The "Corresponding Source" for a work in object code form means all the source code needed to generate, install, and (for an executable work) run the object code and to modify the work, including scripts to control those activities. However, it does not include the work's System Libraries, or general-purpose tools or generally available free programs which are used unmodified in performing those activities but which are not part of the work. For example, Corresponding Source includes interface definition files associated with source files for the work, and the source code for shared libraries and dynamically linked subprograms that the work is specifically designed to require, such as by intimate data communication or control flow between those subprograms and other parts of the work.

The Corresponding Source need not include anything that users can regenerate automatically from other parts of the Corresponding Source.

The Corresponding Source for a work in source code form is that same work.

2. Basic Permissions.

All rights granted under this License are granted for the term of copyright on the Program, and are irrevocable provided the stated conditions are met. This License explicitly affirms your unlimited permission to run the unmodified Program. The output from running a covered work is covered

by this License only if the output, given its content, constitutes a covered work. This License acknowledges your rights of fair use or other equivalent, as provided by copyright law.

You may make, run and propagate covered works that you do not convey, without conditions so long as your license otherwise remains in force. You may convey covered works to others for the sole purpose of having them make modifications exclusively for you, or provide you with facilities for running those works, provided that you comply with the terms of this License in conveying all material for which you do not control copyright. Those thus making or running the covered works for you must do so exclusively on your behalf, under your direction and control, on terms that prohibit them from making any copies of your copyrighted material outside their relationship with you.

Conveying under any other circumstances is permitted solely under the conditions stated below. Sublicensing is not allowed; section 10 makes it unnecessary.

3. Protecting Users' Legal Rights From Anti-Circumvention Law.

No covered work shall be deemed part of an effective technological measure under any applicable law fulfilling obligations under article 11 of the WIPO copyright treaty adopted on 20 December 1996, or similar laws prohibiting or restricting circumvention of such measures.

When you convey a covered work, you waive any legal power to forbid circumvention of technological measures to the extent such circumvention is effected by exercising rights under this License with respect to the covered work, and you disclaim any intention to limit operation or modification of the work as a means of enforcing, against the work's users, your or third parties' legal rights to forbid circumvention of technological measures.

4. Conveying Verbatim Copies.

You may convey verbatim copies of the Program's source code as you receive it, in any medium, provided that you conspicuously and appropriately

publish on each copy an appropriate copyright notice;
keep intact all notices stating that this License and any
non-permissive terms added in accord with section 7 apply to the code;
keep intact all notices of the absence of any warranty; and give all
recipients a copy of this License along with the Program.

You may charge any price or no price for each copy that you convey,
and you may offer support or warranty protection for a fee.

5. Conveying Modified Source Versions.

You may convey a work based on the Program, or the modifications to
produce it from the Program, in the form of source code under the
terms of section 4, provided that you also meet all of these conditions:

- a) The work must carry prominent notices stating that you modified
it, and giving a relevant date.

- b) The work must carry prominent notices stating that it is
released under this License and any conditions added under section
7. This requirement modifies the requirement in section
4 to
"keep intact all notices".

- c) You must license the entire work, as a whole, under this
License to anyone who comes into possession of a copy. This
License will therefore apply, along with any applicable section 7
additional terms, to the whole of the work, and all its parts,
regardless of how they are packaged. This License gives no
permission to license the work in any other way, but it does not
invalidate such permission if you have separately received it.

- d) If the work has interactive user interfaces, each must display
Appropriate Legal Notices; however, if the Program has interactive
interfaces that do not display Appropriate Legal Notices, your
work need not make them do so.

A compilation of a covered work with other separate and independent
works, which are not by their nature extensions of the covered work,
and which are not combined with it such as to form a larger program,
in or on a volume of a storage or distribution
medium, is called an
"aggregate" if the compilation and its resulting copyright are not
used to limit the access or legal rights of the compilation's users
beyond what the individual works permit. Inclusion of a covered work
in an aggregate does not cause this License to apply to the other
parts of the aggregate.

6. Conveying Non-Source Forms.

You may convey a covered work in object code form under the terms of sections 4 and 5, provided that you also convey the machine-readable Corresponding Source under the terms of this License, in one of these ways:

- a) Convey the object code in, or embodied in, a physical product (including a physical distribution medium), accompanied by the Corresponding Source fixed on a durable physical medium customarily used for software interchange.
- b) Convey the object code in, or embodied in, a physical product (including a physical distribution medium), accompanied by a written offer, valid for at least three years and valid for as long as you offer spare parts or customer support for that product model, to give anyone who possesses the object code either (1) a copy of the Corresponding Source for all the software in the product that is covered by this License, on a durable physical medium customarily used for software interchange, for a price no more than your reasonable cost of physically performing this conveying of source, or (2) access to copy the Corresponding Source from a network server at no charge.
- c) Convey individual copies of the object code with a copy of the written offer to provide the Corresponding Source. This alternative is allowed only occasionally and noncommercially, and only if you received the object code with such an offer, in accord with subsection 6b.
- d) Convey the object code by offering access from a designated place (gratis or for a charge), and offer equivalent access to the Corresponding Source in the same way through the same place at no further charge. You need not require recipients to copy the Corresponding Source along with the object code. If the place to copy the object code is a network server, the Corresponding Source may be on a different server (operated by you or a third party) that supports equivalent copying facilities, provided you maintain clear directions next to the object code saying where to find the Corresponding Source. Regardless of what server hosts the Corresponding Source, you remain obligated to ensure that it is available for as long as needed to satisfy these requirements.
- e) Convey the object code using peer-to-peer transmission, provided you inform other peers where the object code and Corresponding Source of the work are being offered to the general public at no

charge under subsection 6d.

A separable portion of the object code, whose source code is excluded from the Corresponding Source as a System Library, need not be included in conveying the object code work.

A "User Product" is either (1) a "consumer product", which means any tangible personal property which is normally used for personal, family, or household purposes, or (2) anything designed or sold for incorporation into a dwelling. In determining whether a product is a consumer product, doubtful cases shall be resolved in favor of coverage. For a particular product received by a particular user, "normally used" refers to a typical or common use of that class of product, regardless of the status of the particular user or of the way in which the particular user actually uses, or expects or is expected to use, the product. A product is a consumer product regardless of whether the product has substantial commercial, industrial or non-consumer uses, unless such uses represent the only significant mode of use of the product.

"Installation Information" for a User Product means any methods, procedures, authorization keys, or other information required to install and execute modified versions of a covered work in that User Product from a modified version of its Corresponding Source. The information must suffice to ensure that the continued functioning of the modified object code is in no case prevented or interfered with solely because modification has been made.

If you convey an object code work under this section in, or with, or specifically for use in, a User Product, and the conveying occurs as part of a transaction in which the right of possession and use of the User Product is transferred to the recipient in perpetuity or for a fixed term (regardless of how the transaction is characterized), the Corresponding Source conveyed under this section must be accompanied by the Installation Information. But this requirement does not apply if neither you nor any third party retains the ability to install modified object code on the User Product (for example, the work has been installed in ROM).

The requirement to provide Installation Information does not include a requirement to continue to provide support service, warranty, or updates for a work that has been modified or installed by the recipient, or for the User Product in which it has been modified or installed. Access to a network may be denied when the modification itself materially and adversely affects the operation of the network or violates the rules and protocols for communication across the network.

Corresponding Source conveyed, and Installation Information provided, in accord with this section must be in a format that is publicly documented (and with an implementation available to the public in source code form), and must require no special password or key for unpacking, reading or copying.

7. Additional Terms.

"Additional permissions" are terms that supplement the terms of this License by making exceptions from one or more of its conditions. Additional permissions that are applicable to the entire Program shall be treated as though they were included in this License, to the extent that they are valid under applicable law. If additional permissions apply only to part of the Program, that part may be used separately under those permissions, but the entire Program remains governed by this License without regard to the additional permissions.

When you convey a copy of a covered work, you may at your option remove any additional permissions from that copy, or from any part of it. (Additional permissions may be written to require their own removal in certain cases when you modify the work.) You may place additional permissions on material, added by you to a covered work, for which you have or can give appropriate copyright permission.

Notwithstanding any other provision of this License, for material you add to a covered work, you may (if authorized by the copyright holders of that material) supplement the terms of this License with terms:

- a) Disclaiming warranty or limiting liability differently from the terms of sections 15 and 16 of this License; or
- b) Requiring preservation of specified reasonable legal notices or author attributions in that material or in the Appropriate Legal Notices displayed by works containing it; or
- c) Prohibiting misrepresentation of the origin of that material, or requiring that modified versions of such material be marked in reasonable ways as different from the original version; or
- d) Limiting the use for publicity purposes of names of licensors or authors of the material; or
- e) Declining to grant rights under trademark law for use of some trade names, trademarks, or service marks; or

f) Requiring indemnification of licensors and authors of that material by anyone who conveys the material (or modified versions of it) with contractual assumptions of liability to the recipient, for any liability that these contractual assumptions directly impose on

those licensors and authors.

All other non-permissive additional terms are considered "further restrictions" within the meaning of section 10. If the Program as you received it, or any part of it, contains a notice stating that it is governed by this License along with a term that is a further restriction, you may remove that term. If a license document contains a further restriction but permits relicensing or conveying under this License, you may add to a covered work material governed by the terms of that license document, provided that the further restriction does not survive such relicensing or conveying.

If you add terms to a covered work in accord with this section, you must place, in the relevant source files, a statement of the additional terms that apply to those files, or a notice indicating where to find the applicable terms.

Additional terms, permissive or non-permissive, may be stated in the form of a separately written license, or stated as exceptions; the above requirements apply either way.

8. Termination.

You may not propagate or modify a covered work except as expressly provided under this License. Any attempt otherwise to propagate or modify it is void, and will automatically terminate your rights under this License (including any patent licenses granted under the third paragraph of section 11).

However, if you cease all violation of this License, then your license from a particular copyright holder is reinstated (a) provisionally, unless and until the copyright holder explicitly and finally terminates your license, and (b) permanently, if the copyright holder fails to notify you of the violation by some reasonable means prior to 60 days after the cessation.

Moreover, your license from a particular copyright holder is reinstated permanently if the copyright holder notifies you of the violation by some reasonable means, this is the first time you have received notice of violation of this License (for any work) from that copyright

holder, and you cure the violation prior to 30 days after your receipt of the notice.

Termination of your rights under this section does not terminate the licenses of parties who have received copies or rights from you under this License. If your rights have been terminated and not permanently reinstated, you do not qualify to receive new licenses for the same material under section 10.

9. Acceptance Not Required for Having Copies.

You are not required to accept this License in order to receive or run a copy of the Program. Ancillary propagation of a covered work occurring solely as a consequence of using peer-to-peer transmission to receive a copy likewise does not require acceptance. However, nothing other than this License grants you permission to propagate or modify any covered work. These actions infringe copyright if you do not accept this License. Therefore, by modifying or propagating a covered work, you indicate your acceptance of this License to do so.

10. Automatic Licensing of Downstream Recipients.

Each time you convey a covered work, the recipient automatically receives a license from the original licensors, to run, modify and propagate that work, subject to this License. You are not responsible for enforcing compliance by third parties with this License.

An "entity transaction" is a transaction transferring control of an organization, or substantially all assets of one, or subdividing an organization, or merging organizations. If propagation of a covered work results from an entity transaction, each party to that transaction who receives a copy of the work also receives whatever licenses to the work the party's predecessor in interest had or could give under the previous paragraph, plus a right to possession of the Corresponding Source of the work from the predecessor in interest, if the predecessor has it or can get it with reasonable efforts.

You may not impose any further restrictions on the exercise of the rights granted or affirmed under this License. For example, you may not impose a license fee, royalty, or other charge for exercise of rights granted under this License, and you may not initiate litigation (including a cross-claim or counterclaim in a lawsuit) alleging that any patent claim is infringed by making, using, selling, offering for sale, or importing the Program or any portion of it.

11. Patents.

A "contributor" is a copyright holder who authorizes use under this License of the Program or a work on which the Program is based. The work thus licensed is called the contributor's "contributor version".

A contributor's "essential patent claims" are all patent claims owned or controlled by the contributor, whether already acquired or hereafter acquired, that would be infringed by some manner, permitted by this License, of making, using, or selling its contributor version, but do not include claims that would be infringed only as a consequence of further modification of the contributor version. For purposes of this definition, "control" includes the right to grant patent sublicenses in a manner consistent with the requirements of this License.

Each contributor grants you a non-exclusive, worldwide, royalty-free patent license under the contributor's essential patent claims, to make, use, sell, offer for sale, import and otherwise run, modify and propagate the contents of its contributor version.

In the following three paragraphs, a "patent license" is any express agreement or commitment, however denominated, not to enforce a patent (such as an express permission to practice a patent or covenant not to sue for patent infringement). To "grant" such a patent license to a party means to make such an agreement or commitment not to enforce a patent against the party.

If you convey a covered work, knowingly relying on a patent license, and the Corresponding Source of the work is not available for anyone to copy, free of charge and under the terms of this License, through a publicly available network server or other readily accessible means, then you must either (1) cause the Corresponding Source to be so available, or (2) arrange to deprive yourself of the benefit of the patent license for this particular work, or (3) arrange, in a manner consistent with the requirements of this License, to extend the patent license to downstream recipients. "Knowingly relying" means you have actual knowledge that, but for the patent license, your conveying the covered work in a country, or your recipient's use of the covered work in a country, would infringe one or more identifiable patents in that country that you have reason to believe are valid.

If, pursuant to or in connection with a single transaction or arrangement, you convey, or propagate by procuring conveyance of, a covered work, and grant a patent license to some of the parties receiving the covered work authorizing them to use, propagate, modify or convey a specific copy of the covered

work, then the patent license you grant is automatically extended to all recipients of the covered work and works based on it.

A patent license is "discriminatory" if it does not include within the scope of its coverage, prohibits the exercise of, or is conditioned on the non-exercise of one or more of the rights that are specifically granted under this License. You may not convey a covered work if you are a party to an arrangement with a third party that is in the business of distributing software, under which you make payment to the third party based on the extent of your activity of conveying the work, and under which the third party grants, to any of the parties who would receive the covered work from you, a discriminatory patent license (a) in connection with copies of the covered work conveyed by you (or copies made from those copies), or (b) primarily for and in connection with specific products or compilations that contain the covered work, unless you entered into that arrangement, or that patent license was granted, prior to 28 March 2007.

Nothing in this License shall be construed as excluding or limiting any implied license or other defenses to infringement that may otherwise be available to you under applicable patent law.

12. No Surrender of Others' Freedom.

If conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot convey a covered work so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not convey it at all. For example, if you agree to terms that obligate you to collect a royalty for further conveying from those to whom you convey the Program, the only way you could satisfy both those terms and this License would be to refrain entirely from conveying the Program.

13. Use with the GNU Affero General Public License.

Notwithstanding any other provision of this License, you have permission to link or combine any covered work with a work licensed under version 3 of the GNU Affero General Public License into a single combined work, and to convey the resulting work. The terms of this License will continue to apply to the part which is the covered work, but the special requirements of the GNU Affero General Public License, section 13, concerning interaction through a network will apply to the combination as such.

14. Revised Versions of this License.

The Free Software Foundation may publish revised and/or new versions of the GNU General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Program specifies that a certain numbered version of the GNU General Public License "or any later version" applies to it, you have the option of following the terms and conditions either of that numbered version or of any later version published by the Free Software Foundation. If the Program does not specify a version number of the GNU General Public License, you may choose any version ever published by the Free Software Foundation.

If the Program specifies that a proxy can decide which future versions of the GNU General Public License can be used, that proxy's public statement of acceptance of a version permanently authorizes you to choose that version for the Program.

Later license versions may give you additional or different permissions. However, no additional obligations are imposed on any author or copyright holder as a result of your choosing to follow a later version.

15. Disclaimer of Warranty.

THERE IS NO WARRANTY FOR THE PROGRAM, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE PROGRAM "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE PROGRAM IS WITH YOU. SHOULD THE PROGRAM PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

16. Limitation of Liability.

IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MODIFIES AND/OR CONVEYS THE PROGRAM AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE PROGRAM (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE PROGRAM TO OPERATE WITH ANY OTHER PROGRAMS), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF

SUCH DAMAGES.

17.

Interpretation of Sections 15 and 16.

If the disclaimer of warranty and limitation of liability provided above cannot be given local legal effect according to their terms, reviewing courts shall apply local law that most closely approximates an absolute waiver of all civil liability in connection with the Program, unless a warranty or assumption of liability accompanies a copy of the Program in return for a fee.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Programs

If you develop a new program, and you want it to be of the greatest possible use to the public, the best way to achieve this is to make it free software which everyone can redistribute and change under these terms.

To do so, attach the following notices to the program. It is safest to attach them to the start of each source file to most effectively state the exclusion of warranty; and each file should have at least the "copyright" line and a pointer to where the full notice is found.

```
<one line to give the program's name and a brief idea of what it does.>  
Copyright (C) <year> <name of author>
```

```
This program is free software: you can redistribute it and/or modify  
it under the terms of the GNU General Public License as published by  
the Free Software Foundation, either version 3 of the License, or  
(at your option) any later version.
```

```
This program is distributed in the hope that it will be useful,  
but WITHOUT ANY WARRANTY; without even the implied warranty of  
MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the  
GNU General Public License for more details.
```

```
You should have received a copy of the GNU General Public License  
along with this program. If not, see <http://www.gnu.org/licenses/>.
```

Also add information on how to contact you by electronic and paper mail.

If the program does terminal interaction, make it output a short notice like this when it starts in an interactive mode:

<program> Copyright (C) <year> <name of author>

This program comes with ABSOLUTELY NO WARRANTY; for details type `show w'.

This is free software, and you are welcome to redistribute it under certain conditions; type `show c' for details.

The hypothetical commands `show w' and `show c' should show the appropriate parts of the General Public License. Of course, your program's commands might be different; for a GUI interface, you would use an "about box".

You should also get your employer (if you work as a programmer) or school, if any, to sign a "copyright disclaimer" for the program, if necessary.

For more information on this, and how to apply and follow the GNU GPL, see <<http://www.gnu.org/licenses/>>.

The GNU General Public License does not permit incorporating your program into proprietary programs. If your program is a subroutine library, you may consider it more useful to permit linking proprietary applications with the library. If this is what you want to do, use the GNU Lesser General Public License instead of this License. But first, please read <<http://www.gnu.org/philosophy/why-not-lgpl.html>>.

1.71 bash 4.4.18-2ubuntu1.3

1.71.1 Available under license :

This is Debian GNU/Linux's prepackaged version of the FSF's GNU Bash, the Bourne Again SHell.

This package was put together by Matthias Klose <doko@debian.org>, from the following sources:

bash: <ftp.gnu.org:/pub/gnu/bash/bash-4.3.tar.gz>

Bash homepage: <http://tiswww.case.edu/php/chet/bash/bashtop.html>

Copyright (C) 1987-2014 Free Software Foundation, Inc.

Bash is free software; you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation; either version 3, or (at your option) any later version.

Bash is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details.

You should have received a copy of the GNU General Public License along with Bash. If not, see <<http://www.gnu.org/licenses/>>. On Debian systems, the complete text of the GNU General Public License can be found in ``usr/share/common-licenses/GPL-3'`.

The Free Software Foundation has exempted Bash from the requirement of Paragraph 2c of the General Public License. This is to say, there is no requirement for Bash to print a notice when it is started interactively in the usual way. We made this exception because users and standards expect shells not to print such messages. This exception applies to any program that serves as a shell and that is based primarily on Bash as opposed to other GNU software.

Files with other copyright statement than: Copyright FSF, License GPL

doc/FAQ ("the Bash FAQ")

This document is Copyright 1995-2005 by Chester Ramey.

Permission is hereby granted, without written agreement and without license or royalty fees, to use, copy, and distribute this document for any purpose, provided that the above copyright notice appears in all copies of this document and that the contents of this document remain unaltered.

doc/bashref.texi ("Bash Reference Manual"):

Copyright (c) 1988-2014 Free Software Foundation, Inc.

Permission is granted to make and distribute verbatim copies of this manual provided the copyright notice and this permission notice are preserved on all copies.

Permission is granted to copy, distribute and/or modify this document under the terms of the GNU Free Documentation License, Version 1.3 or any later version published by the Free Software Foundation; with no Invariant Sections, no Front-Cover Texts, and no Back-Cover Texts. A copy of the license is included in the section entitled ``GNU Free Documentation License''.

lib/readline/doc/rlman.texi (part of the GNU Readline Library manual)

Copyright (c) 1988-2014 Free Software Foundation, Inc.

Permission is granted to copy, distribute and/or modify this document under the terms of the GNU Free Documentation License, Version 1.3 or any later version published by the Free Software Foundation; with no Invariant Sections, no Front-Cover Texts, and no Back-Cover Texts. A copy of the license is included in the section entitled ``GNU Free Documentation License".

lib/readline/doc/rltech.texi (part of the GNU Readline Library manual)

Copyright (C) 1988-2014 Free Software Foundation, Inc.

Permission is granted to make and distribute verbatim copies of this manual provided the copyright notice and this permission notice are preserved on all copies.

Permission is granted to process this file through TeX and print the results, provided the printed document carries copying permission notice identical to this one except for the removal of this paragraph (this paragraph not being relevant to the printed manual).

Permission is granted to copy and distribute modified versions of this manual under the conditions for verbatim copying, provided that the entire resulting derived work is distributed under the terms of a permission notice identical to this one.

Permission is granted to copy and distribute translations of this manual into another language, under the above conditions for modified versions, except that this permission notice may be stated in a translation approved by the Foundation.

lib/readline/doc/rluser.texi (part of the GNU Readline Library manual)

Copyright (C) 1988-2014 Free Software Foundation, Inc.

Authored by Brian Fox and Chet Ramey.

Permission is granted to process this file through TeX and print the results, provided the printed document carries copying permission notice identical to this one except for the removal of this paragraph (this paragraph not being relevant to the printed manual).

Permission is granted to make and distribute verbatim copies of this manual provided the copyright notice and this permission notice are preserved on all copies.

Permission is granted to copy and distribute modified versions of this manual under the conditions for verbatim copying, provided also that the GNU Copyright statement is available to the distributee, and provided that the entire resulting derived work is distributed under the terms of a permission notice identical to this one.

Permission is granted to copy and distribute translations of this manual into another language, under the above conditions for modified versions.

readline/doc/history.texi (GNU History Library Manual)

Copyright (C) 1988-2014 Free Software Foundation, Inc.
Authored by Brian Fox and Chet Ramey.

Permission is granted to copy, distribute and/or modify this document under the terms of the GNU Free Documentation License, Version 1.3 or any later version published by the Free Software Foundation; with no Invariant Sections, no Front-Cover Texts, and no Back-Cover Texts. A copy of the license is included in the section entitled ``GNU Free Documentation License".

readline/doc/{hstech,hsuser}.texi (GNU History Library Manual)

Copyright (C) 1988-2014 Free Software Foundation, Inc.
Authored by Brian Fox and Chet Ramey.

Permission is granted to make and distribute verbatim copies of this manual provided the copyright notice and this permission notice are preserved on all copies.

Permission is granted to process this file through Tex and print the results, provided the printed document carries copying permission notice identical to this one except for the removal of this paragraph (this paragraph not being relevant to the printed manual).

Permission is granted to copy and distribute modified versions of this manual under the conditions for verbatim copying, provided also that the GNU Copyright statement is available to the distributee, and provided that the entire resulting derived work is distributed under the terms of a permission notice identical to this one.

Permission is granted to copy and distribute translations of this manual into another language, under the above conditions for modified versions.

lib/sh/inet_aton.c:

* Copyright (c) 1983,
1990, 1993

* The Regents of the University of California. All rights reserved.

*

* Redistribution and use in source and binary forms, with or without
* modification, are permitted provided that the following conditions
* are met:

* 1. Redistributions of source code must retain the above copyright
* notice, this list of conditions and the following disclaimer.

* 2. Redistributions in binary form must reproduce the above copyright
* notice, this list of conditions and the following disclaimer in the
* documentation and/or other materials provided with the distribution.

* 3. All advertising materials mentioning features or use of this software
* must display the following acknowledgement:

* This product includes software developed by the University of
* California, Berkeley and its contributors.

* 4. Neither the name of the University nor the names of its contributors
* may be used to endorse or promote products derived from this software
* without specific prior written permission.

*

* THIS SOFTWARE IS PROVIDED BY THE REGENTS AND CONTRIBUTORS ``AS IS" AND
* ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE
* IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE
* ARE DISCLAIMED. IN NO EVENT SHALL THE REGENTS OR CONTRIBUTORS BE LIABLE
* FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL
* DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS
* OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION)
* HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT
* LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY
* OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF
* SUCH DAMAGE.

* -

* Portions Copyright (c) 1993 by Digital Equipment Corporation.

*

* Permission to use, copy, modify, and distribute this software for any
* purpose with or without fee

is hereby granted, provided that the above

* copyright notice and this permission notice appear in all copies, and that

* the name of Digital Equipment Corporation not be used in advertising or

* publicity pertaining to distribution of the document or software without

* specific, written prior permission.

*

* THE SOFTWARE IS PROVIDED "AS IS" AND DIGITAL EQUIPMENT CORP. DISCLAIMS ALL

* WARRANTIES WITH REGARD TO THIS SOFTWARE, INCLUDING ALL IMPLIED WARRANTIES

* OF MERCHANTABILITY AND FITNESS. IN NO EVENT SHALL DIGITAL EQUIPMENT

* CORPORATION BE LIABLE FOR ANY SPECIAL, DIRECT, INDIRECT, OR CONSEQUENTIAL

* DAMAGES OR ANY DAMAGES WHATSOEVER RESULTING FROM LOSS OF USE, DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE OR OTHER TORTIOUS ACTION, ARISING OUT OF OR IN CONNECTION WITH THE USE OR PERFORMANCE OF THIS SOFTWARE.

support/man2html.c

* This program was written by Richard Verhoeven (NL:5482ZX35)
* at the Eindhoven University of Technology. Email: rcb5@win.tue.nl
*
* Permission is granted to distribute, modify and use this program as long
* as this comment is not removed or changed.
*
* THIS IS A MODIFIED VERSION. IT WAS MODIFIED BY chet@po.cwru.edu FOR
* USE BY BASH.

1.72 libsepol 2.7-1ubuntu0.1

1.72.1 Available under license :

GNU LESSER GENERAL PUBLIC LICENSE

Version 2.1, February 1999

Copyright (C) 1991, 1999 Free Software Foundation, Inc.

51 Franklin St, Fifth Floor, Boston, MA 02110-1301 USA

Everyone is permitted to copy and distribute verbatim copies of this license document, but changing it is not allowed.

[This is the first released version of the Lesser GPL. It also counts as the successor of the GNU Library Public License, version 2, hence the version number 2.1.]

Preamble

The licenses for most software are designed to take away your freedom to share and change it. By contrast, the GNU General Public Licenses are intended to guarantee your freedom to share and change free software--to make sure the software is free for all its users.

This license, the Lesser General Public License, applies to some specially designated software packages--typically libraries--of the Free Software Foundation and other authors who decide to use it. You can use it too, but we suggest you first think carefully about whether this license or the ordinary General Public License is the better strategy to use in any particular case, based on the explanations below.

When we speak of free software, we are referring to freedom of use, not price. Our General Public Licenses are designed to make sure that you have the freedom to distribute copies of free software (and charge for this service if you wish); that you receive source code or can get it if you want it; that you can change the software and use pieces of it in new free programs; and that you are informed that you can do these things.

To protect your rights, we need to make restrictions that forbid distributors to deny you these rights or to ask you to surrender these rights. These restrictions translate to certain responsibilities for you if you distribute copies of the library or if you modify it.

For example, if you distribute copies of the library, whether gratis or for a fee, you must give the recipients all the rights that we gave you. You must make sure that they, too, receive or can get the source code. If you link other code with the library, you must provide complete object files to the recipients, so that they can relink them with the library after making changes to the library and recompiling it. And you must show them these terms so they know their rights.

We protect your rights with a two-step method: (1) we copyright the library, and (2) we offer you this license, which gives you legal permission to copy, distribute and/or modify the library.

To protect each distributor, we want to make it very clear that there is no warranty for the free library. Also, if the library is modified by someone else and passed on, the recipients should know that what they have is not the original version, so that the original author's reputation will not be affected by problems that might be introduced by others.

Finally, software patents pose a constant threat to the existence of any free program. We wish to make sure that a company cannot effectively restrict the users of a free program by obtaining a restrictive license from a patent holder. Therefore, we insist that any patent license obtained for a version of the library must be consistent with the full freedom of use specified in this license.

Most GNU software, including some libraries, is covered by the ordinary GNU General Public License. This license, the GNU Lesser General Public License, applies to certain designated libraries, and is quite different from the ordinary General Public License. We use this license for certain libraries in order to permit linking those libraries into non-free programs.

When a program is linked with a library, whether statically or using a shared library, the combination of the two is legally speaking a combined work, a derivative of the original library. The ordinary General Public License therefore permits such linking only if the entire combination fits its criteria of freedom. The Lesser General Public License permits more lax criteria for linking other code with the library.

We call this license the "Lesser" General Public License because it does Less to protect the user's freedom than the ordinary General Public License. It also provides other free software developers Less of an advantage over competing non-free programs. These disadvantages are the reason we use the ordinary General Public License for many libraries. However, the Lesser license provides advantages in certain special circumstances.

For example, on rare occasions, there may be a special need to encourage the widest possible use of a certain library, so that it becomes a de-facto standard. To achieve this, non-free programs must be allowed to use the library. A more frequent case is that a free library does the same job as widely used non-free libraries. In this case, there is little to gain by limiting the free library to free software only, so we use the Lesser General Public License.

In other cases, permission to use a particular library in non-free programs enables a greater number of people to use a large body of free software. For example, permission to use the GNU C Library in non-free programs enables many more people to use the whole GNU operating system, as well as its variant, the GNU/Linux operating system.

Although the Lesser General Public License is Less protective of the users' freedom, it does ensure that the user of a program that is linked with the Library has the freedom and the wherewithal to run that program using a modified version of the Library.

The precise terms and conditions for copying, distribution and modification follow. Pay close attention to the difference between a "work based on the library" and a "work that uses the library". The former contains code derived from the library, whereas the latter must be combined with the library in order to run.

**GNU LESSER GENERAL PUBLIC LICENSE
TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION**

0. This License Agreement applies to any software library or other

program which contains a notice placed by the copyright holder or other authorized party saying it may be distributed under the terms of this Lesser General Public License (also called "this License"). Each licensee is addressed as "you".

A "library" means a collection of software functions and/or data prepared so as to be conveniently linked with application programs (which use some of those functions and data) to form executables.

The "Library", below, refers to any such software library or work which has been distributed under these terms. A "work based on the Library" means either the Library or any derivative work under copyright law: that is to say, a work containing the Library or a portion of it, either verbatim or with modifications and/or translated straightforwardly into another language. (Hereinafter, translation is included without limitation in the term "modification".)

"Source code" for a work means the preferred form of the work for making modifications to it. For a library, complete source code means all the source code for all modules it contains, plus any associated interface definition files, plus the scripts used to control compilation and installation of the library.

Activities other than copying, distribution and modification are not covered by this License; they are outside its scope. The act of running a program using the Library is not restricted, and output from such a program is covered only if its contents constitute a work based on the Library (independent of the use of the Library in a tool for writing it). Whether that is true depends on what the Library does and what the program that uses the Library does.

1. You may copy and distribute verbatim copies of the Library's complete source code as you receive it, in any medium, provided that you conspicuously and appropriately publish on each copy an appropriate copyright notice and disclaimer of warranty; keep intact all the notices that refer to this License and to the absence of any warranty; and distribute a copy of this License along with the Library.

You may charge a fee for the physical act of transferring a copy, and you may at your option offer warranty protection in exchange for a fee.

2. You may modify your copy or copies of the Library or any portion of it, thus forming a work based on the Library, and copy and distribute such modifications or work under the terms of Section 1

above, provided that you also meet all of these conditions:

- a) The modified work must itself be a software library.
- b) You must cause the files modified to carry prominent notices stating that you changed the files and the date of any change.
- c) You must cause the whole of the work to be licensed at no charge to all third parties under the terms of this License.

d) If a facility in the modified Library refers to a function or a table of data to be supplied by an application program that uses the facility, other than as an argument passed when the facility is invoked, then you must make a good faith effort to ensure that, in the event an application does not supply such function or table, the facility still operates, and performs whatever part of its purpose remains meaningful.

(For example, a function in a library to compute square roots has a purpose that is entirely well-defined independent of the application. Therefore, Subsection 2d requires that any application-supplied function or table used by this function must be optional: if the application does not supply it, the square root function must still compute square roots.)

These requirements apply to the modified work as a whole. If identifiable sections of that work are not derived from the Library, and can be reasonably considered independent and separate works in themselves,

then this License, and its terms, do not apply to those sections when you distribute them as separate works. But when you distribute the same sections as part of a whole which is a work based on the Library, the distribution of the whole must be on the terms of this License, whose permissions for other licensees extend to the entire whole, and thus to each and every part regardless of who wrote it.

Thus, it is not the intent of this section to claim rights or contest your rights to work written entirely by you; rather, the intent is to exercise the right to control the distribution of derivative or collective works based on the Library.

In addition, mere aggregation of another work not based on the Library with the Library (or with a work based on the Library) on a volume of a storage or distribution medium does not bring the other work under the scope of this License.

3. You may opt to apply the terms of the ordinary GNU General Public License instead of this License to a given copy of the Library. To do this, you must alter all the notices that refer to this License, so that they refer to the ordinary GNU General Public License, version 2, instead of to this License. (If a newer version than version 2 of the ordinary GNU General Public License has appeared, then you can specify that version instead if you wish.) Do not make any other change in these notices.

Once this change is made in a given copy, it is irreversible for that copy, so the ordinary GNU General Public License applies to all subsequent copies and derivative works made from that copy.

This option is useful when you wish to copy part of the code of the Library into a program that is not a library.

4. You may copy and distribute the Library (or a portion or derivative of it, under Section 2) in object code or executable form under the terms of Sections 1 and 2 above provided that you accompany it with the complete corresponding machine-readable source code, which must be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange.

If distribution of object code is made by offering access to copy from a designated place, then offering equivalent access to copy the source code from the same place satisfies the requirement to distribute the source code, even though third parties are not compelled to copy the source along with the object code.

5. A program that contains no derivative of any portion of the Library, but is designed to work with the Library by being compiled or linked with it, is called a "work that uses the Library". Such a work, in isolation, is not a derivative work of the Library, and therefore falls outside the scope of this License.

However, linking a "work that uses the Library" with the Library creates an executable that is a derivative of the Library (because it contains portions of the Library), rather than a "work that uses the library". The executable is therefore covered by this License.

Section 6 states terms for distribution of such executables.

When a "work that uses the Library" uses material from a header file that is part of the Library, the object code for the work may be a derivative work of the Library even though the source code is not. Whether this is true is especially significant if the work can be

linked without the Library, or if the work is itself a library. The threshold for this to be true is not precisely defined by law.

If such an object file uses only numerical parameters, data structure layouts and accessors, and small macros and small inline functions (ten lines or less in length), then the use of the object file is unrestricted, regardless of whether it is legally a derivative work. (Executables containing this object code plus portions of the Library will still fall under Section 6.)

Otherwise, if the work is a derivative of the Library, you may distribute the object code for the work under the terms of Section 6.

Any executables

containing that work also fall under Section 6,

whether or not they are linked directly with the Library itself.

6. As an exception to the Sections above, you may also combine or link a "work that uses the Library" with the Library to produce a work containing portions of the Library, and distribute that work under terms of your choice, provided that the terms permit modification of the work for the customer's own use and reverse engineering for debugging such modifications.

You must give prominent notice with each copy of the work that the Library is used in it and that the Library and its use are covered by this License. You must supply a copy of this License. If the work during execution displays copyright notices, you must include the copyright notice for the Library among them, as well as a reference directing the user to the copy of this License. Also, you must do one of these things:

a) Accompany the work with the complete corresponding machine-readable

source code for the Library including whatever

changes were used in the work (which must be distributed under Sections 1 and 2 above); and, if the work is an executable linked with the Library, with the complete machine-readable "work that uses the Library", as object code and/or source code, so that the user can modify the Library and then relink to produce a modified executable containing the modified Library. (It is understood that the user who changes the contents of definitions files in the Library will not necessarily be able to recompile the application to use the modified definitions.)

b) Use a suitable shared library mechanism for linking with the Library. A suitable mechanism is one that (1) uses at run time a copy of the library already present on the user's computer system, rather than copying library functions into the executable, and (2)

will operate properly with a modified version of the library, if the user installs one, as long as the modified version is interface-compatible with the version that the work was made with.

c) Accompany the work with a written offer, valid for at least three years, to give the same user the materials specified in Subsection 6a, above, for a charge no more than the cost of performing this distribution.

d) If distribution of the work is made by offering access to copy from a designated place, offer equivalent access to copy the above specified materials from the same place.

e) Verify that the user has already received a copy of these materials or that you have already sent this user a copy.

For an executable, the required form of the "work that uses the Library" must include any data and utility programs needed for reproducing the executable from it. However, as a special exception, the materials to be distributed need not include anything that is normally distributed (in either source or binary form) with the major components (compiler, kernel, and so on) of the operating system on which the executable runs, unless that component itself accompanies the executable.

It may happen that this requirement contradicts the license restrictions of other proprietary libraries that do not normally accompany the operating system. Such a contradiction means you cannot use both them and the Library together in an executable that you distribute.

7. You may place library facilities that are a work based on the Library side-by-side in a single library together with other library facilities not covered by this License, and distribute such a combined library, provided that the separate distribution of the work based on the Library and of the other library facilities is otherwise permitted, and provided that you do these two things:

a) Accompany the combined library with a copy of the same work based on the Library, uncombined with any other library facilities. This must be distributed under the terms of the Sections above.

b) Give prominent notice with the combined library of the fact that part of it is a work based on the Library, and explaining

where to find the accompanying uncombined form of the same work.

8. You may not copy, modify, sublicense, link with, or distribute the Library except as expressly provided under this License. Any attempt otherwise to copy, modify, sublicense, link with, or distribute the Library is void, and will automatically terminate your rights under this License. However, parties who have received copies, or rights, from you under this License will not have their licenses terminated so long as such parties remain in full compliance.

9. You are not required to accept this License, since you have not signed it. However, nothing else grants you permission to modify or distribute the Library or its derivative works. These actions are prohibited by law if you do not accept this License. Therefore, by modifying or distributing the Library (or any work based on the Library), you indicate your acceptance of this License to do so, and all its terms and conditions for copying, distributing or modifying the Library or works based on it.

10. Each time you redistribute the Library (or any work based on the Library), the recipient automatically receives a license from the original licensor to copy, distribute, link with or modify the Library subject to these terms and conditions. You may not impose any further restrictions on the recipients' exercise of the rights granted herein. You are not responsible for enforcing compliance by third parties with this License.

11. If, as a consequence of a court judgment or allegation of patent infringement or for any other reason (not limited to patent issues), conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot distribute so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not distribute the Library at all. For example, if a patent license would not permit royalty-free redistribution of the Library by all those who receive copies directly or indirectly through you, then the only way you could satisfy both it and this License would be to refrain entirely from distribution of the Library.

If any portion of this section is held invalid or unenforceable under any particular circumstance, the balance of the section is intended to apply, and the section as a whole is intended to apply in other circumstances.

It is not the purpose of this section to induce you to infringe any patents or other property right claims or to contest validity of any

such claims; this section has the sole purpose of protecting the integrity of the free software distribution system which is implemented by public license practices. Many people have made generous contributions to the wide range of software distributed through that system in reliance on consistent application of that system; it is up to the author/donor to decide if he or she is willing to distribute software through any other system and a licensee cannot impose that choice.

This section is intended to make thoroughly clear what is believed to be a consequence of the rest of this License.

12. If the distribution and/or use of the Library is restricted in certain countries either by patents or by copyrighted interfaces, the original copyright holder who places the Library under this License may add an explicit geographical distribution limitation excluding those countries, so that distribution is permitted only in or among countries not thus excluded. In such case, this License incorporates the limitation as if written in the body of this License.

13. The Free Software Foundation may publish revised and/or new versions of the Lesser General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Library specifies a version number of this License which applies to it and "any later version", you have the option of following the terms and conditions either of that version or of any later version published by the Free Software Foundation. If the Library does not specify a license version number, you may choose any version ever published by the Free Software Foundation.

14. If you wish to incorporate parts of the Library into other free programs whose distribution conditions are incompatible with these, write to the author to ask for permission. For software which is copyrighted by the Free Software Foundation, write to the Free Software Foundation; we sometimes make exceptions for this. Our decision will be guided by the two goals of preserving the free status of all derivatives of our free software and of promoting the sharing and reuse of software generally.

NO WARRANTY

15. BECAUSE THE LIBRARY IS LICENSED FREE OF CHARGE, THERE IS NO

WARRANTY FOR THE LIBRARY, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE LIBRARY "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE LIBRARY IS WITH YOU. SHOULD THE LIBRARY PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

16. IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY AND/OR REDISTRIBUTE THE LIBRARY AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL

DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE LIBRARY (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE LIBRARY TO OPERATE WITH ANY OTHER SOFTWARE), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Libraries

If you develop a new library, and you want it to be of the greatest possible use to the public, we recommend making it free software that everyone can redistribute and change. You can do so by permitting redistribution under these terms (or, alternatively, under the terms of the ordinary General Public License).

To apply these terms, attach the following notices to the library. It is safest to attach them to the start of each source file to most effectively convey the exclusion of warranty; and each file should have at least the "copyright" line and a pointer to where the full notice is found.

<one line to give the library's name and a brief idea of what it does.>

Copyright (C) <year> <name of author>

This library is free software; you can redistribute it and/or modify it under the terms of the GNU Lesser General Public License as published by the Free Software Foundation; either version 2.1 of the License, or (at your option) any later version.

This library is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU

Lesser General Public License for more details.

You should have received a copy of the GNU Lesser General Public License along with this library; if not, write to the Free Software Foundation, Inc., 51 Franklin St, Fifth Floor, Boston, MA 02110-1301 USA

Also add information on how to contact you by electronic and paper mail.

You should also get your employer (if you work as a programmer) or your school, if any, to sign a "copyright disclaimer" for the library, if necessary. Here is a sample; alter the names:

Yoyodyne, Inc., hereby disclaims all copyright interest in the library `Frob' (a library for tweaking knobs) written by James Random Hacker.

<signature of Ty Coon>, 1 April 1990
Ty Coon, President of Vice

That's all there is to it!

1.73 pcre 8.39-9ubuntu0.1

1.73.1 Available under license :

PCRE LICENCE

PCRE is a library of functions to support regular expressions whose syntax and semantics are as close as possible to those of the Perl 5 language.

Release 8 of PCRE is distributed under the terms of the "BSD" licence, as specified below. The documentation for PCRE, supplied in the "doc" directory, is distributed under the same terms as the software itself. The data in the testdata directory is not copyrighted and is in the public domain.

The basic library functions are written in C and are freestanding. Also included in the distribution is a set of C++ wrapper functions, and a just-in-time compiler that can be used to optimize pattern matching. These are both optional features that can be omitted when the library is built.

THE BASIC LIBRARY FUNCTIONS

Written by: Philip Hazel
Email local part: ph10
Email domain: cam.ac.uk

University of Cambridge Computing Service,
Cambridge, England.

Copyright (c) 1997-2016 University
of Cambridge
All rights reserved.

PCRE JUST-IN-TIME COMPILATION SUPPORT

Written by: Zoltan Herczeg
Email local part: hzmester
Email domain: freemail.hu

Copyright(c) 2010-2016 Zoltan Herczeg
All rights reserved.

STACK-LESS JUST-IN-TIME COMPILER

Written by: Zoltan Herczeg
Email local part: hzmester
Email domain: freemail.hu

Copyright(c) 2009-2016 Zoltan Herczeg
All rights reserved.

THE C++ WRAPPER FUNCTIONS

Contributed by: Google Inc.

Copyright (c) 2007-2012, Google Inc.
All rights reserved.

THE "BSD" LICENCE

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions are met:

* Redistributions of source code must retain the above copyright notice,
this list of conditions and the following disclaimer.

* Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.

* Neither the name of the University of Cambridge nor the name of Google Inc. nor the names of their contributors may be used to endorse or promote products derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

End
PCRE LICENCE

Please see the file LICENCE in the PCRE distribution for licensing details.

End
Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

1. Redistributions of source code must retain the copyright notice, this list of conditions and the following disclaimer.
2. Redistributions in binary form must reproduce the copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.
3. The name of the author may not be used to endorse or promote products derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE AUTHOR ``AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE AUTHOR BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT

OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

1.74 dpkg 1.19.0.5ubuntu2.4

1.74.1 Available under license :

Format: <https://www.debian.org/doc/packaging-manuals/copyright-format/1.0/>

Upstream-Name: dpkg

Files: *

Copyright:

Copyright 1994 Ian Murdock <imurdock@debian.org>

Copyright 1994 Matt Welsh <mdw@sunsite.unc.edu>

Copyright 1994 Carl Streeter <streeter@cae.wisc.edu>

Copyright 1994-1999, 2008 Ian Jackson <ijackson@chiark.greenend.org.uk>

Copyright 1995 Bruce Perens <bruce@pixar.com>

Copyright 1995-1996 Erick Branderhorst <branderhorst@heel.fgg.eur.nl>

Copyright 1996 Michael Shields <shields@crosslink.net>

Copyright 1996 Klee Dienes <klee@debian.org>

Copyright 1996 Kim-Minh Kaplan <kkaplan@cdfhp3.in2p3.fr>

Copyright 1996-1998 Miquel van Smoorenburg <miquels@cistron.nl>

Copyright 1997-1998 Charles Briscoe-Smith <cpbs@debian.org>

Copyright 1997-1998 Juho Vuori <javuori@cc.helsinki.fi>

Copyright 1998 Koichi Sekido <sekido@mbox.kyoto-inet.or.jp>

Copyright 1998 Jim Van Zandt <jrv@vanzandt.mv.com>

Copyright 1998 Juan Cespedes <cespedes@debian.org>

Copyright 1998 Nils

Rennebarth <nils@debian.org>

Copyright 1998 Heiko Schlittermann <hs@schlittermann.de>

Copyright 1998-1999, 2001, 2003, 2006 Martin Schulze <joe@infodrom.org>

Copyright 1999 Roderick Shertler <roderick@argon.org>

Copyright 1999 Ben Collins <bcollins@debian.org>

Copyright 1999 Richard Kettlewell <rjk@sfero.greenend.org.uk>

Copyright 1999-2001 Marcus Brinkmann <brinkmd@debian.org>

Copyright 1999-2002 Wichert Akkerman <wakkerma@debian.org>

Copyright 2001, 2007, 2010 Joey Hess <joe@debian.org>

Copyright 2004-2005, 2007-2008, 2010 Canonical Ltd.

Copyright 2004-2005 Scott James Remnant <scott@netsplit.com>

Copyright 2006-2008 Frank Lichtenheld <djpig@debian.org>

Copyright 2006-2015 Guillem Jover <guillem@debian.org>

Copyright 2007-2012 Raphael Hertzog <hertzog@debian.org>

Copyright 2007 Nicolas François <nicolas.francois@centraliens.net>

Copyright 2007 Don Armstrong <don@donarmstrong.com>

Copyright 2007 Colin Watson <cjwatson@debian.org>

Copyright 2007,
2008 Tollef Fog Heen <tfheen@err.no>
Copyright 2008 Zack Weinberg <zackw@panix.com>
Copyright 2008 Pierre Habouzit <madcoder@debian.org>
Copyright 2009 Romain Françoise <rfrancoise@debian.org>
Copyright 2009-2010 Modestas Vainius <modax@debian.org>
Copyright 2009-2011 Kees Cook <kees@debian.org>
License: GPL-2+

Files:

lib/compat/getopt*
lib/compat/gettext.h
lib/compat/obstack.*
lib/compat/strnlen.c

Copyright:

Copyright 1987-2006 Free Software Foundation, Inc.
License: GPL-2+

Files:

dselect/methods/Dselect/Ftp.pm
dselect/methods/ftp/*

Copyright:

Copyright 1996 Andy Guy <awpguy@acs.ualgary.ca>
Copyright 1998 Martin Schulze <joe@infodrom.org>
Copyright 1999-2001, 2005-2006, 2009 Raphael Hertzog <hertzog@debian.org>
License: GPL-2

Files:

scripts/Dpkg/Gettext.pm

Copyright:

Copyright 2000 Joey Hess <joe@debian.org>
Copyright 2007, 2009-2010, 2012-2015 Guillem Jover <guillem@debian.org>
License: BSD-2-clause

Files:

utils/start-stop-daemon.c

Copyright:

Copyright

1999 Marek Michalkiewicz <marekm@i17linuxb.ists.pwr.wroc.pl>
Copyright 1999 Christian Schwarz <schwarz@monet.m.isar.de>
Copyright 1999 Klee Dienes <klee@debian.org>
Copyright 1999 Ben Collins <bcollins@debian.org>
Copyright 1999-2002 Wichert Akkerman <wakkerma@debian.org>
Copyright 2000-2003 Adam Heath <doogie@debian.org>
Copyright 2001 Sontri Tomo Huynh <huynh.29@osu.edu>
Copyright 2001 Andreas Schuldei <andreas@schuldei.org>
Copyright 2001 Ian Jackson <ijackson@chiark.greenend.org.uk>
Copyright 2004-2005 Scott James Remnant <keybuk@debian.org>

Copyright 2006-2014 Guillem Jover <guillem@debian.org>
Copyright 2008 Samuel Thibault <samuel.thibault@ens-lyon.org>
Copyright 2008 Andreas Pahlsson <andreas.pahlsson@xcerion.com>
Copyright 2009 Chris Coulson <chrisccoulson@googlemail.com>
Copyright 2012 Carsten Hey <carsten@debian.org>
Copyright 2014 Nir Soffer <nirs@hyperms.com>

License: public-domain-s-s-d

Written by Marek Michalkiewicz <marekm@i17linuxb.ists.pwr.wroc.pl>, public domain. Based conceptually on start-stop-daemon.pl, by Ian Jackson <ijackson@gnu.ai.mit.edu>. May be used and distributed freely for any purpose. Changes by Christian Schwarz <schwarz@monet.m.isar.de>, to make output conform to the Debian Console Message Standard, also placed in public domain. Minor changes by Klee Dienes <klee@debian.org>, also placed in the Public Domain.

.

Changes by Ben Collins <bcollins@debian.org>, added --chuid, --background and --make-pidfile options, placed in public domain as well.

Files: lib/compat/md5.*

Copyright:

Copyright 1993 Colin Plumb

License: public-domain-md5

This code implements the MD5 message-digest algorithm. The algorithm is due to Ron Rivest. This code was written by Colin Plumb in 1993, no copyright is claimed. This code is in the public domain; do with it what you wish.

.

Equivalent code is available from RSA Data Security, Inc. This code has been tested against that, and is equivalent, except that you don't need to include two pages of legalese with every copy.

License: GPL-2+

This program is free software; you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation; either version 2 of the License, or (at your option) any later version.

.

This program is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details.

.

You should have received a copy of the GNU General Public License along with this program. If not, see <<https://www.gnu.org/licenses/>>.

Comment:

On Debian systems, the complete text of the GNU General Public License can be found in /usr/share/common-licenses/GPL-2 or in the dpkg source as the file COPYING.

License: GPL-2

This is free software; you can redistribute it and/or modify it under the terms of version

2 of the GNU General Public

License version 2 as published by the Free Software Foundation.

.
This is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details.

.
You should have received a copy of the GNU General Public License along with this program. If not, see <<https://www.gnu.org/licenses/>>.

License: BSD-2-clause

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

1. Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.
2. Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.

.
THIS SOFTWARE

IS PROVIDED BY AUTHORS AND CONTRIBUTORS ``AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE AUTHORS OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

GNU GENERAL PUBLIC LICENSE

Version 2, June 1991

Copyright (C) 1989, 1991 Free Software Foundation, Inc.,
51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA
Everyone is permitted to copy and distribute verbatim copies of this license document, but changing it is not allowed.

Preamble

The licenses for most software are designed to take away your freedom to share and change it. By contrast, the GNU General Public License is intended to guarantee your freedom to share and change free software--to make sure the software is free for all its users. This General Public License applies to most of the Free Software Foundation's software and to any other program whose authors commit to using it. (Some other Free Software Foundation software is covered by the GNU Lesser General Public License instead.) You can apply it to your programs, too.

When we speak of free software, we are referring to freedom, not price. Our General Public Licenses are designed to make sure that you have the freedom to distribute copies of free software (and charge for this service if you wish), that you receive source code or can get it if you want it, that you can change the software or use pieces of it in new free programs; and that you know you can do these things.

To protect your rights, we need to make restrictions that forbid anyone to deny you these rights or to ask you to surrender the rights. These restrictions translate to certain responsibilities for you if you distribute copies of the software, or if you modify it.

For example, if you distribute copies of such a program, whether gratis or for a fee, you must give the recipients all the rights that you have. You must make sure that they, too, receive or can get the source code. And you must show them these terms so they know their rights.

We protect your rights with two steps: (1) copyright the software, and (2) offer you this license which gives you legal permission to copy, distribute and/or modify the software.

Also, for each author's protection and ours, we want to make certain that everyone understands that there is no warranty for this free software. If the software is modified by someone else and passed on, we want its recipients to know that what they have is not the original, so that any problems introduced by others will not reflect on the original authors' reputations.

Finally, any free program is threatened constantly by software patents. We wish to avoid the danger that redistributors of a free program will individually obtain patent licenses, in effect making the program proprietary. To prevent this, we have made it clear that any patent must be licensed for everyone's free use or not licensed at all.

The precise terms and conditions for copying, distribution and modification follow.

GNU GENERAL PUBLIC LICENSE
TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

0. This License applies to any program or other work which contains a notice placed by the copyright holder saying it may be distributed under the terms of this General Public License. The "Program", below, refers to any such program or work, and a "work based on the Program" means either the Program or any derivative work under copyright law: that is to say, a work containing the Program or a portion of it, either verbatim or with modifications and/or translated into another language. (Hereinafter, translation is included without limitation in the term "modification".) Each licensee is addressed as "you".

Activities other than copying, distribution and modification are not covered by this License; they are outside its scope. The act of running the Program is not restricted, and the output from the Program is covered only if its contents constitute a work based on the Program (independent of having been made by running the Program). Whether that is true depends on what the Program does.

1. You may copy and distribute verbatim copies of the Program's source code as you receive it, in any medium, provided that you conspicuously and appropriately publish on each copy an appropriate copyright notice and disclaimer of warranty; keep intact all the notices that refer to this License and to the absence of any warranty; and give any other recipients of the Program a copy of this License along with the Program.

You may charge a fee for the physical act of transferring a copy, and you may at your option offer warranty protection in exchange for a fee.

2. You may modify your copy or copies of the Program or any portion of it, thus forming a work based on the Program, and copy and distribute such modifications or work under the terms of Section 1 above, provided that you also meet all of these conditions:

- a) You must cause the modified files to carry prominent notices stating that you changed the files and the date of any change.
- b) You must cause any work that you distribute or publish, that in whole

or in part contains or is derived from the Program or any part thereof, to be licensed as a whole at no charge to all third parties under the terms of this License.

c) If the modified program normally reads commands interactively when run, you must cause it, when started running for such interactive use in the most ordinary way, to print or display an announcement including an appropriate copyright notice and a notice that there is no warranty (or else, saying that you provide a warranty) and that users may redistribute the program under these conditions, and telling the user how to view a copy of this License. (Exception: if the Program itself is interactive but does not normally print such an announcement, your work based on the Program is not required to print an announcement.)

These requirements apply to the modified work as a whole. If identifiable sections of that work are not derived from the Program, and can be reasonably considered independent and separate works in themselves, then this License, and its terms, do not apply to those sections when you distribute them as separate works. But when you distribute the same sections as part of a whole which is a work based on the Program, the distribution of the whole must be on the terms of this License, whose permissions for other licensees extend to the entire whole, and thus to each and every part regardless of who wrote it.

Thus, it is not the intent of this section to claim rights or contest your rights to work written entirely by you; rather, the intent is to exercise the right to control the distribution of derivative or collective works based on the Program.

In addition, mere aggregation of another work not based on the Program with the Program (or with a work based on the Program) on a volume of a storage or distribution medium does not bring the other work under the scope of this License.

3. You may copy and distribute the Program (or a work based on it, under Section 2) in object code or executable form under the terms of Sections 1 and 2 above provided that you also do one of the following:

a) Accompany it with the complete corresponding machine-readable source code, which must be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange; or,

b) Accompany it with a written offer, valid for at least three years, to give any third party, for a charge no more than your cost of physically performing source distribution, a complete

machine-readable copy of the corresponding source code, to be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange; or,

c) Accompany it with the information you received as to the offer to distribute corresponding source code. (This alternative is allowed only for noncommercial distribution and only if you received the program in object code or executable form with such an offer, in accord with Subsection b above.)

The source code for a work means the preferred form of the work for making modifications to it. For an executable work, complete source code means all the source code for all modules it contains, plus any associated interface definition files, plus the scripts used to control compilation and installation of the executable. However, as a special exception, the source code distributed need not include anything that is normally distributed (in either source or binary form) with the major components (compiler, kernel, and so on) of the operating system on which the executable runs, unless that component itself accompanies the executable.

If distribution of executable or object code is made by offering access to copy from a designated place, then offering equivalent access to copy the source code from the same place counts as distribution of the source code, even though third parties are not compelled to copy the source along with the object code.

4. You may not copy, modify, sublicense, or distribute the Program except as expressly provided under this License. Any attempt otherwise to copy, modify, sublicense or distribute the Program is void, and will automatically terminate your rights under this License. However, parties who have received copies, or rights, from you under this License will not have their licenses terminated so long as such parties remain in full compliance.

5. You are not required to accept this License, since you have not signed it. However, nothing else grants you permission to modify or distribute the Program or its derivative works. These actions are prohibited by law if you do not accept this License. Therefore, by modifying or distributing the Program (or any work based on the Program), you indicate your acceptance of this License to do so, and all its terms and conditions for copying, distributing or modifying the Program or works based on it.

6. Each

time you redistribute the Program (or any work based on the Program), the recipient automatically receives a license from the original licensor to copy, distribute or modify the Program subject to these terms and conditions. You may not impose any further restrictions on the recipients' exercise of the rights granted herein. You are not responsible for enforcing compliance by third parties to this License.

7. If, as a consequence of a court judgment or allegation of patent infringement or for any other reason (not limited to patent issues), conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot distribute so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not distribute the Program at all. For example, if a patent license would not permit royalty-free redistribution of the Program by all those who receive copies directly or indirectly through you, then the only way you could satisfy both it and this License would be to refrain entirely from distribution of the Program.

If any portion of this section is held invalid or unenforceable under any particular circumstance, the balance of the section is intended to apply and the section as a whole is intended to apply in other circumstances.

It is not the purpose of this section to induce you to infringe any patents or other property right claims or to contest validity of any such claims; this section has the sole purpose of protecting the integrity of the free software distribution system, which is implemented by public license practices. Many people have made generous contributions to the wide range of software distributed through that system in reliance on consistent application of that system; it is up to the author/donor to decide if he or she is willing to distribute software through any other system and a licensee cannot impose that choice.

This section is intended to make thoroughly clear what is believed to be a consequence of the rest of this License.

8. If the distribution and/or use of the Program is restricted in certain countries either by patents or by copyrighted interfaces, the original copyright holder who places the Program under this License may add an explicit geographical distribution limitation excluding those countries, so that distribution is permitted only in or among countries not thus excluded. In such case, this License incorporates

the limitation as if written in the body of this License.

9. The Free Software Foundation may publish revised and/or new versions of the General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Program specifies a version number of this License which applies to it and "any later version", you have the option of following the terms and conditions either of that version or of any later version published by the Free Software Foundation. If the Program does not specify a version number of this License, you may choose any version ever published by the Free Software Foundation.

10. If you wish to incorporate parts of the Program into other free programs whose distribution conditions are different, write to the author to ask for permission. For software which is copyrighted by the Free Software Foundation, write to the Free Software Foundation; we sometimes make exceptions for this. Our decision will be guided by the two goals of preserving the free status of all derivatives of our free software and of promoting the sharing and reuse of software generally.

NO WARRANTY

11. BECAUSE THE PROGRAM IS LICENSED FREE OF CHARGE, THERE IS NO WARRANTY FOR THE PROGRAM, TO THE EXTENT PERMITTED BY APPLICABLE LAW.

EXCEPT WHEN

OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE PROGRAM "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE PROGRAM IS WITH YOU. SHOULD THE PROGRAM PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

12. IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY AND/OR REDISTRIBUTE THE PROGRAM AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE PROGRAM (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE PROGRAM TO OPERATE WITH ANY OTHER PROGRAMS), EVEN

IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Programs

If you develop a new program, and you want it to be of the greatest possible use to the public, the best way to achieve this is to make it free software which everyone can redistribute and change under these terms.

To do so, attach the following notices to the program. It is safest to attach them to the start of each source file to most effectively convey the exclusion of warranty; and each file should have at least the "copyright" line and a pointer to where the full notice is found.

```
<one line to give the program's name and a brief idea of what it does.>  
Copyright (C) <year> <name of author>
```

This program is free software; you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation; either version 2 of the License,
or
(at your option) any later version.

This program is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details.

You should have received a copy of the GNU General Public License along with this program; if not, write to the Free Software Foundation, Inc., 51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA.

Also add information on how to contact you by electronic and paper mail.

If the program is interactive, make it output a short notice like this when it starts in an interactive mode:

```
Gnomovision version 69, Copyright (C) year name of author  
Gnomovision comes with ABSOLUTELY NO WARRANTY; for details type `show w'.  
This is free software, and you are welcome to redistribute it  
under certain conditions; type `show c' for details.
```

The hypothetical commands `show w' and `show c' should show the appropriate parts of the General Public License. Of course, the commands you use may be called something other than `show w' and `show c'; they could even be mouse-clicks or menu items--whatever suits your program.

You should also get your employer (if you work as a programmer) or your

school, if any, to sign a "copyright disclaimer" for the program, if necessary. Here is a sample; alter the names:

Yoyodyne, Inc., hereby disclaims all copyright interest in the program
'Gnomovision' (which makes passes at compilers) written by James Hacker.

<signature of Ty Coon>, 1 April 1989
Ty Coon, President of Vice

This General Public License does not permit incorporating your program into proprietary programs. If your program is a subroutine library, you may consider it more useful to permit linking proprietary applications with the library. If this is what you want to do, use the GNU Lesser General Public License instead of this License.

1.75 glibc 2.27-3ubuntu1.6

1.75.1 Available under license :

Copyright 1992, 1993, 1994, 1997 Henry Spencer. All rights reserved.
This software is not subject to any license of the American Telephone and Telegraph Company or of the Regents of the University of California.

Permission is granted to anyone to use this software for any purpose on any computer system, and to alter it and redistribute it, subject to the following restrictions:

1. The author is not responsible for the consequences of use of this software, no matter how awful, even if they arise from flaws in it.
2. The origin of this software must not be misrepresented, either by explicit claim or by omission. Since few users ever read sources, credits must appear in the documentation.
3. Altered versions must be plainly marked as such, and must not be misrepresented as being the original software. Since few users ever read sources, credits must appear in the documentation.
4. This notice may not be removed or altered.

GNU GENERAL PUBLIC LICENSE
Version 2, June 1991

Copyright (C) 1989, 1991 Free Software Foundation, Inc.,
51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA
Everyone is permitted to copy and distribute verbatim copies
of this license document, but changing it is not allowed.

Preamble

The licenses for most software are designed to take away your freedom to share and change it. By contrast, the GNU General Public License is intended to guarantee your freedom to share and change free software--to make sure the software is free for all its users. This General Public License applies to most of the Free Software Foundation's software and to any other program whose authors commit to using it. (Some other Free Software Foundation software is covered by the GNU Lesser General Public License instead.) You can apply it to your programs, too.

When we speak of free software, we are referring to freedom, not price.

Our General Public Licenses are designed to make sure that you have the freedom to distribute copies of free software (and charge for this service if you wish), that you receive source code or can get it if you want it, that you can change the software or use pieces of it in new free programs; and that you know you can do these things.

To protect your rights, we need to make restrictions that forbid anyone to deny you these rights or to ask you to surrender the rights. These restrictions translate to certain responsibilities for you if you distribute copies of the software, or if you modify it.

For example, if you distribute copies of such a program, whether gratis or for a fee, you must give the recipients all the rights that you have. You must make sure that they, too, receive or can get the source code. And you must show them these terms so they know their rights.

We protect your rights with two steps: (1) copyright the software, and (2) offer you this license which gives you legal permission to copy, distribute and/or modify the software.

Also, for each author's protection and ours, we want to make certain that everyone understands that there is no warranty for this free software. If the software is modified by someone else and passed on, we want its recipients to know that what they have is not the original, so that any problems introduced by others will not reflect on the original authors' reputations.

Finally, any free program is threatened constantly by software patents. We wish to avoid the danger that redistributors of a free program will individually obtain patent licenses, in effect making the program proprietary. To prevent this, we have made it clear that any patent must be licensed for everyone's free use or not licensed at all.

The precise terms and conditions for copying, distribution and modification follow.

GNU GENERAL PUBLIC LICENSE
TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

0. This License applies to any program or other work which contains a notice placed by the copyright holder saying it may be distributed under the terms of this General Public License. The "Program", below, refers to any such program or work, and a "work based on the Program" means either the Program or any derivative work under copyright law: that is to say, a work containing the Program or a portion of it, either verbatim or with modifications and/or translated into another language. (Hereinafter, translation is included without limitation in the term "modification".) Each licensee is addressed as "you".

Activities other than copying, distribution and modification are not covered by this License; they are outside its scope. The act of running the Program is not restricted, and the output from the Program is covered only if its contents constitute a work based on the Program (independent of having been made by running the Program). Whether that is true depends on what the Program does.

1. You may copy and distribute verbatim copies of the Program's source code as you receive it, in any medium, provided that you conspicuously and appropriately publish on each copy an appropriate copyright notice and disclaimer of warranty; keep intact all the notices that refer to this License and to the absence of any warranty; and give any other recipients of the Program a copy of this License along with the Program.

You may charge a fee for the physical act of transferring a copy, and you may at your option offer warranty protection in exchange for a fee.

2. You may modify your copy or copies of the Program or any portion of it, thus forming a work based on the Program, and copy and distribute such modifications or work under the terms of Section 1 above, provided that you also meet all of these conditions:

a) You must cause the modified files to carry prominent notices stating that you changed the files and the date of any change.

b) You must cause any work that you distribute or publish, that in whole or in part contains or is derived from the Program or any part thereof, to be licensed as a whole at no charge to all third parties under the terms of this License.

c) If the modified program normally reads commands interactively when run, you must cause it, when started running for such interactive use in the most ordinary way, to print or display an announcement including an appropriate copyright notice and a notice that there is no warranty (or else, saying that you provide a warranty) and that users may redistribute the program under these conditions, and telling the user how to view a copy of this License. (Exception: if the Program itself is interactive but does not normally print such an announcement, your work based on the Program is not required to print an announcement.)

These requirements apply to the modified work as a whole. If identifiable sections of that work are not derived from the Program, and can be reasonably considered independent and separate works in themselves, then this License, and its terms, do not apply to those sections when you distribute them as separate works. But when you distribute the same sections as part of a whole which is a work based on the Program, the distribution of the whole must be on the terms of this License, whose permissions for other licensees extend to the entire whole, and thus to each and every part regardless of who wrote it.

Thus, it is not the intent of this section to claim rights or contest your rights to work written entirely by you; rather, the intent is to exercise the right to control the distribution of derivative or collective works based on the Program.

In addition, mere aggregation of another work not based on the Program with the Program (or with a work based on the Program) on a volume of a storage or distribution medium does not bring the other work under the scope of this License.

3. You may copy and distribute the Program (or a work based on it, under Section 2) in object code or executable form under the terms of Sections 1 and 2 above provided that you also do one of the following:

a) Accompany it with the complete corresponding machine-readable source code, which must be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange; or,

b) Accompany it with a written offer, valid for at least three years, to give any third party, for a charge no more than your cost of physically performing source distribution, a complete machine-readable copy of the corresponding source code, to be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange; or,

c) Accompany it with the information you received as to the offer to distribute corresponding source code. (This alternative is allowed only for noncommercial distribution and only if you received the program in object code or executable form with such an offer, in accord with Subsection b above.)

The source code for a work means the preferred form of the work for making modifications to it. For an executable work, complete source code means all the source code for all modules it contains, plus any associated interface definition files, plus the scripts used to control compilation and installation of the executable. However, as a special exception, the source code distributed need not include anything that is normally distributed (in either source or binary form) with the major components (compiler, kernel, and so on) of the operating system on which the executable runs, unless that component itself accompanies the executable.

If distribution of executable or object code is made by offering access to copy from a designated place, then offering equivalent access to copy the source code from the same place counts as distribution of the source code, even though third parties are not compelled to copy the source along with the object code.

4. You may not copy, modify, sublicense, or distribute the Program except as expressly provided under this License. Any attempt otherwise to copy, modify, sublicense or distribute the Program is void, and will automatically terminate your rights under this License. However, parties who have received copies, or rights, from you under this License will not have their licenses terminated so long as such parties remain in full compliance.

5. You are not required to accept this License, since you have not signed it. However, nothing else grants you permission to modify or distribute the Program or its derivative works. These actions are prohibited by law if you do not accept this License. Therefore, by modifying or distributing the Program (or any work based on the Program), you indicate your acceptance of this License to do so, and all its terms and conditions for copying, distributing or modifying the Program or works based on it.

6. Each time you redistribute the Program (or any work based on the Program), the recipient automatically receives a license from the original licensor to copy, distribute or modify the Program subject to these terms and conditions. You may not impose any further restrictions on the recipients' exercise of the rights granted herein.

You are not responsible for enforcing compliance by third parties to this License.

7. If, as a consequence of a court judgment or allegation of patent infringement or for any other reason (not limited to patent issues), conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot distribute so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not distribute the Program at all. For example, if a patent license would not permit royalty-free redistribution of the Program by all those who receive copies directly or indirectly through you, then the only way you could satisfy both it and this License would be to refrain entirely from distribution of the Program.

If any portion of this section is held invalid or unenforceable under any particular circumstance, the balance of the section is intended to apply and the section as a whole is intended to apply in other circumstances.

It is not the purpose of this section to induce you to infringe any patents or other property right claims or to contest validity of any such claims; this section has the sole purpose of protecting the integrity of the free software distribution system, which is implemented by public license practices. Many people have made generous contributions to the wide range of software distributed through that system in reliance on consistent application of that system; it is up to the author/donor to decide if he or she is willing to distribute software through any other system and a licensee cannot impose that choice.

This section is intended to make thoroughly clear what is believed to be a consequence of the rest of this License.

8. If the distribution and/or use of the Program is restricted in certain countries either by patents or by copyrighted interfaces, the original copyright holder who places the Program under this License may add an explicit geographical distribution limitation excluding those countries, so that distribution is permitted only in or among countries not thus excluded. In such case, this License incorporates the limitation as if written in the body of this License.

9. The Free Software Foundation may publish revised and/or new versions of the General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to

address new problems or concerns.

Each version is given a distinguishing version number. If the Program specifies a version number of this License which applies to it and "any later version", you have the option of following the terms and conditions either of that version or of any later version published by the Free Software Foundation. If the Program does not specify a version number of this License, you may choose any version ever published by the Free Software Foundation.

10. If you wish to incorporate parts of the Program into other free programs whose distribution conditions are different, write to the author to ask for permission. For software which is copyrighted by the Free Software Foundation, write to the Free Software Foundation; we sometimes make exceptions for this. Our decision will be guided by the two goals of preserving the free status of all derivatives of our free software and of promoting the sharing and reuse of software generally.

NO WARRANTY

11. BECAUSE THE PROGRAM IS LICENSED FREE OF CHARGE, THERE IS NO WARRANTY FOR THE PROGRAM, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE PROGRAM "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE PROGRAM IS WITH YOU. SHOULD THE PROGRAM PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

12. IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY AND/OR REDISTRIBUTE THE PROGRAM AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE PROGRAM (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE PROGRAM TO OPERATE WITH ANY OTHER PROGRAMS), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Programs

If you develop a new program, and you want it to be of the greatest

possible use to the public, the best way to achieve this is to make it free software which everyone can redistribute and change under these terms.

To do so, attach the following notices to the program. It is safest to attach them to the start of each source file to most effectively convey the exclusion of warranty; and each file should have at least the "copyright" line and a pointer to where the full notice is found.

```
<one line to give the program's name and a brief idea of what it does.>  
Copyright (C) <year> <name of author>
```

This program is free software; you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation; either version 2 of the License, or (at your option) any later version.

This program is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details.

You should have received a copy of the GNU General Public License along with this program; if not, write to the Free Software Foundation, Inc., 51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA.

Also add information on how to contact you by electronic and paper mail.

If the program is interactive, make it output a short notice like this when it starts in an interactive mode:

```
Gnomovision version 69, Copyright (C) year name of author  
Gnomovision comes with ABSOLUTELY NO WARRANTY; for details type `show w'.  
This is free software, and you are welcome to redistribute  
it  
under certain conditions; type `show c' for details.
```

The hypothetical commands `show w' and `show c' should show the appropriate parts of the General Public License. Of course, the commands you use may be called something other than `show w' and `show c'; they could even be mouse-clicks or menu items--whatever suits your program.

You should also get your employer (if you work as a programmer) or your school, if any, to sign a "copyright disclaimer" for the program, if necessary. Here is a sample; alter the names:

```
Yoyodyne, Inc., hereby disclaims all copyright interest in the program  
'Gnomovision' (which makes passes at compilers) written by James Hacker.
```

<signature of Ty Coon>, 1 April 1989

Ty Coon, President of Vice

This General Public License does not permit incorporating your program into proprietary programs. If your program is a subroutine library, you may consider it more useful to permit linking proprietary applications with the library. If this

is what you want to do, use the GNU Lesser General Public License instead of this License.

GNU LESSER GENERAL PUBLIC LICENSE

Version 2.1, February 1999

Copyright (C) 1991, 1999 Free Software Foundation, Inc.
51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA
Everyone is permitted to copy and distribute verbatim copies of this license document, but changing it is not allowed.

[This is the first released version of the Lesser GPL. It also counts as the successor of the GNU Library Public License, version 2, hence the version number 2.1.]

Preamble

The licenses for most software are designed to take away your freedom to share and change it. By contrast, the GNU General Public Licenses are intended to guarantee your freedom to share and change free software--to make sure the software is free for all its users.

This license, the Lesser General Public License, applies to some specially designated software packages--typically libraries--of the Free Software Foundation and other authors who decide to use it. You can use it too, but we suggest you first think carefully about whether this license or the ordinary General Public License is the better strategy to use in any particular case, based on the explanations below.

When we speak of free software, we are referring to freedom of use, not price. Our General Public Licenses are designed to make sure that you have the freedom to distribute copies of free software (and charge for this service if you wish); that you receive source code or can get it if you want it; that you can change the software and use pieces of it in new free programs; and that you are informed that you can do these things.

To protect your rights, we need to make restrictions that forbid distributors to deny you these rights or to ask you to surrender these rights. These restrictions translate to certain responsibilities for

you if you distribute copies of the library or if you modify it.

For example, if you distribute copies of the library, whether gratis or for a fee, you must give the recipients all the rights that we gave you. You must make sure that they, too, receive or can get the source code. If you link other code with the library, you must provide complete object files to the recipients, so that they can relink them with the library after making changes to the library and recompiling it. And you must show them these terms so they know their rights.

We protect your rights with a two-step method: (1) we copyright the library, and (2) we offer you this license, which gives you legal permission to copy, distribute and/or modify the library.

To protect each distributor, we want to make it very clear that there is no warranty for the free library. Also, if the library is modified by someone else and passed on, the recipients should know that what they have is not the original version, so that the original author's reputation will not be affected by problems that might be introduced by others.

Finally, software patents pose a constant threat to the existence of any free program. We wish to make sure that a company cannot effectively restrict the users of a free program by obtaining a restrictive license from a patent holder. Therefore, we insist that any patent license obtained for a version of the library must be consistent with the full freedom of use specified in this license.

Most GNU software, including some libraries, is covered by the ordinary GNU General Public License. This license, the GNU Lesser General Public License, applies to certain designated libraries, and is quite different from the ordinary General Public License. We use this license for certain libraries in order to permit linking those libraries into non-free programs.

When a program is linked with a library, whether statically or using a shared library, the combination of the two is legally speaking a combined work, a derivative of the original library. The ordinary General Public License therefore permits such linking only if the entire combination fits its criteria of freedom. The Lesser General Public License permits more lax criteria for linking other code with the library.

We call this license the "Lesser" General Public License because it does Less to protect the user's freedom than the ordinary General

Public License. It also provides other free software developers Less of an advantage over competing non-free programs. These disadvantages are the reason we use the ordinary General Public License for many libraries. However, the Lesser license provides advantages in certain special circumstances.

For example, on rare occasions, there may be a special need to encourage the widest possible use of a certain library, so that it becomes a de-facto standard. To achieve this, non-free programs must be allowed to use the library. A more frequent case is that a free library does the same job as widely used non-free libraries. In this case, there is little to gain by limiting the free library to free software only, so we use the Lesser General Public License.

In other cases, permission to use a particular library in non-free programs enables a greater number of people to use a large body of free software. For example, permission to use the GNU C Library in non-free programs enables many more people to use the whole GNU operating system, as well as its variant, the GNU/Linux operating system.

Although the Lesser General Public License is Less protective of the users' freedom, it does ensure that the user of a program that is linked with the Library has the freedom and the wherewithal to run that program using a modified version of the Library.

The precise terms and conditions for copying, distribution and modification follow. Pay close attention to the difference between a "work based on the library" and a "work that uses the library". The former contains code derived from the library, whereas the latter must be combined with the library in order to run.

GNU LESSER GENERAL PUBLIC LICENSE TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

0. This License Agreement applies to any software library or other program which contains a notice placed by the copyright holder or other authorized party saying it may be distributed under the terms of this Lesser General Public License (also called "this License"). Each licensee is addressed as "you".

A "library" means a collection of software functions and/or data prepared so as to be conveniently linked with application programs (which use some of those functions and data) to form executables.

The "Library", below, refers to any such software library or work

which has been distributed under these terms. A "work based on the Library" means either the Library or any derivative work under copyright law: that is to say, a work containing the Library or a portion of it, either verbatim or with modifications and/or translated straightforwardly into another language. (Hereinafter, translation is included without limitation in the term "modification".)

"Source code" for a work means the preferred form of the work for making modifications to it. For a library, complete source code means all the source code for all modules it contains, plus any associated interface definition files, plus the scripts used to control compilation and installation of the library.

Activities other than copying, distribution and modification are not covered by this License; they are outside its scope. The act of running a program using the Library is not restricted, and output from such a program is covered only if its contents constitute a work based on the Library (independent of the use of the Library in a tool for writing it). Whether that is true depends on what the Library does and what the program that uses the Library does.

1. You may copy and distribute verbatim copies of the Library's complete source code as you receive it, in any medium, provided that you conspicuously and appropriately publish on each copy an appropriate copyright notice and disclaimer of warranty; keep intact all the notices that refer to this License and to the absence of any warranty; and distribute a copy of this License along with the Library.

You may charge a fee for the physical act of transferring a copy, and you may at your option offer warranty protection in exchange for a fee.

2. You may modify your copy or copies of the Library or any portion of it, thus forming a work based on the Library, and copy and distribute such modifications or work under the terms of Section 1 above, provided that you also meet all of these conditions:

- a) The modified work must itself be a software library.
- b) You must cause the files modified to carry prominent notices stating that you changed the files and the date of any change.
- c) You must cause the whole of the work to be licensed at no charge to all third parties under the

terms of this License.

d) If a facility in the modified Library refers to a function or a table of data to be supplied by an application program that uses the facility, other than as an argument passed when the facility is invoked, then you must make a good faith effort to ensure that, in the event an application does not supply such function or table, the facility still operates, and performs whatever part of its purpose remains meaningful.

(For example, a function in a library to compute square roots has a purpose that is entirely well-defined independent of the application. Therefore, Subsection 2d requires that any application-supplied function or table used by this function must be optional: if the application does not supply it, the square root function must still compute square roots.)

These requirements apply to the modified work as a whole. If identifiable sections of that work are not derived from the Library, and can be reasonably considered independent and separate works in themselves, then this License, and its terms, do not apply to those sections when you distribute them as separate works. But when you distribute the same sections as part of a whole which is a work based on the Library, the distribution of the whole must be on the terms of this License, whose permissions for other licensees extend to the entire whole, and thus to each and every part regardless of who wrote it.

Thus, it is not the intent of this section to claim rights or contest your rights to work written entirely by you; rather, the intent is to exercise the right to control the distribution of derivative or collective works based on the Library.

In addition, mere aggregation of another work not based on the Library with the Library (or with a work based on the Library) on a volume of a storage or distribution medium does not bring the other work under the scope of this License.

3. You may opt to apply the terms of the ordinary GNU General Public

License instead of this License to a given copy of the Library. To do this, you must alter all the notices that refer to this License, so that they refer to the ordinary GNU General Public License, version 2, instead of to this License. (If a newer version than version 2 of the ordinary GNU General Public License has appeared, then you can specify that version instead if you wish.) Do not make any other change in these notices.

Once this change is made in a given copy, it is irreversible for that copy, so the ordinary GNU General Public License applies to all subsequent copies and derivative works made from that copy.

This option is useful when you wish to copy part of the code of the Library into a program that is not a library.

4. You may copy and distribute the Library (or a portion or derivative of it, under Section 2) in object code or executable form under the terms of Sections 1 and 2 above provided that you accompany it with the complete corresponding machine-readable source code, which must be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange.

If distribution of object code is made by offering access to copy from a designated place, then offering equivalent access to copy the source code from the same place satisfies the requirement to distribute the source code, even though third parties are not compelled to copy the source along with the object code.

5. A program that contains no derivative of any portion of the Library, but is designed to work with the Library by being compiled or linked with it, is called a "work that uses the Library". Such a work, in isolation, is not a derivative work of the Library, and therefore falls outside the scope of this License.

However, linking a "work that uses the Library" with the Library creates an executable that is a derivative of the Library (because it contains portions of the Library), rather than a "work that uses the library". The executable is therefore covered by this License. Section 6 states terms for distribution of such executables.

When a "work that uses the Library" uses material from a header file that is part of the Library, the object code for the work may be a derivative work of the Library even though the source code is not. Whether this is true is especially significant if the work can be linked without the Library, or if the work is itself a library. The threshold for this to be true is not precisely defined by law.

If such an object file uses only numerical parameters, data structure layouts and accessors, and small macros and small inline functions (ten lines or less in length), then the use of the object file is unrestricted, regardless of whether it is legally a derivative work. (Executables containing this object code plus portions of the Library will still fall under Section 6.)

Otherwise, if the work is a derivative of the Library, you may distribute the object code for the work under the terms of Section 6. Any executables containing that work also fall under Section 6, whether or not they are linked directly with the Library itself.

6. As an exception to the Sections above, you may also combine or link a "work that uses the Library" with the Library to produce a work containing portions of the Library, and distribute that work under terms of your choice, provided that the terms permit modification of the work for the customer's own use and reverse engineering for debugging such modifications.

You must give prominent notice with each copy of the work that the Library is used in it and that the Library and its use are covered by this License. You must supply a copy of this License. If the work during execution displays copyright notices, you must include the copyright notice for the Library among them, as well as a reference directing the user to the copy of this License. Also, you must do one of these things:

a) Accompany the work with the complete corresponding machine-readable source code for the Library including whatever changes were used in the work (which must be distributed under Sections 1 and 2 above); and, if the work is an executable linked with the Library, with the complete machine-readable "work that uses the Library", as object code and/or source code, so that the user can modify the Library and then relink to produce a modified executable containing the modified Library. (It is understood that the user who changes the contents of definitions files in the Library will not necessarily be able to recompile the application to use the modified definitions.)

b) Use a suitable shared library mechanism for linking with the Library. A suitable mechanism is one that (1) uses at run time a copy of the library already present on the user's computer system, rather than copying library functions into the executable, and (2) will operate properly with a modified version of the library, if the user installs one, as long as the modified version is interface-compatible with the version that the work was made with.

c) Accompany the work with a written offer, valid for at least three years, to give the same user the materials specified in Subsection 6a, above, for a charge no more than the cost of performing this distribution.

d) If distribution of the work is made by offering access to copy from a designated place, offer equivalent access to copy the above specified materials from the same place.

e) Verify that the user has already received a copy of these materials or that you have already sent this user a copy.

For an executable, the required form of the "work that uses the Library" must include any data and utility programs needed for reproducing the executable from it. However, as a special exception, the materials to be distributed need not include anything that is normally

distributed (in either source or binary form) with the major components (compiler, kernel, and so on) of the operating system on which the executable runs, unless that component itself accompanies the executable.

It may happen that this requirement contradicts the license restrictions of other proprietary libraries that do not normally accompany the operating system. Such a contradiction means you cannot use both them and the Library together in an executable that you distribute.

7. You may place library facilities that are a work based on the Library side-by-side in a single library together with other library facilities not covered by this License, and distribute such a combined library, provided that the separate distribution of the work based on the Library and of the other library facilities is otherwise permitted, and provided that you do these two things:

a) Accompany the combined library with a copy of the same work based on the Library, uncombined with any other library facilities. This must be distributed under the terms of the Sections above.

b) Give prominent notice with the combined library of the fact that part of it is a work based on the Library, and explaining where to find the accompanying uncombined form of the same work.

8. You may not copy, modify, sublicense, link with, or distribute the Library except as expressly provided under this License. Any attempt otherwise to copy, modify, sublicense, link with, or distribute the Library is void, and will automatically terminate your rights under this License. However, parties who have received copies, or rights, from you under this License will not have their licenses terminated so long as such parties remain in full compliance.

9. You are not required to accept this License, since you have not signed it. However, nothing else grants you permission to modify or distribute the Library or its derivative works. These actions are prohibited by law if you do not accept this License. Therefore, by modifying or distributing the Library (or any work based on the Library), you indicate your acceptance of this License to do so, and all its terms and conditions for copying, distributing or modifying the Library or works based on it.

10. Each time you redistribute the Library (or any work based on the Library), the recipient automatically receives a license from the original licensor to copy, distribute, link with or modify the Library subject to these terms and conditions. You may not impose any further restrictions on the recipients' exercise of the rights granted herein. You are not responsible for enforcing compliance by third parties with this License.

11. If, as a consequence of a court judgment or allegation of patent infringement or for any other reason (not limited to patent issues), conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot distribute so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not distribute the Library at all. For example, if a patent license would not permit royalty-free redistribution of the Library by all those who receive copies directly or indirectly through you, then the only way you could satisfy both it and this License would be to refrain entirely from distribution of the Library.

If any portion of this section is held invalid or unenforceable under any particular circumstance, the balance of the section is intended to apply, and the section as a whole is intended to apply in other circumstances.

It is not the purpose of this section to induce you to infringe any patents or other property right claims or to contest validity of any such claims; this section has the sole purpose of protecting the integrity of the free software distribution system which is implemented by public license practices. Many people have made generous contributions to the wide range of software distributed through that system in reliance on consistent application of that system; it is up to the author/donor to decide if he or she is willing to distribute software through any other system and a licensee cannot impose that choice.

This section is intended to make thoroughly clear what is believed to be a consequence of the rest of this License.

12. If the distribution and/or use of the Library is restricted in certain countries either by patents or by copyrighted interfaces, the original copyright holder who places the Library under this License may add an explicit geographical distribution limitation excluding those countries, so that distribution is permitted only in or among countries not thus excluded. In such case, this License incorporates the limitation as if written in the body of this License.

13. The Free Software Foundation may publish revised and/or new versions of the Lesser General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Library specifies a version number of this License which applies to it and "any later version", you have the option of following the terms and conditions either of that version or of any later version published by the Free Software Foundation. If the Library does not specify a license version number, you may choose any version ever published by the Free Software Foundation.

14. If you wish to incorporate parts of the Library into other free programs whose distribution conditions are incompatible with these, write to the author to ask for permission. For software which is copyrighted by the Free Software Foundation, write to the Free Software Foundation; we sometimes make exceptions for this. Our decision will be guided by the two goals of preserving the free status of all derivatives of our free software and of promoting the sharing and reuse of software generally.

NO WARRANTY

15. BECAUSE THE LIBRARY IS LICENSED FREE OF CHARGE, THERE IS NO WARRANTY FOR THE LIBRARY, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE LIBRARY "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE LIBRARY IS WITH YOU. SHOULD THE LIBRARY PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

16. IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY AND/OR REDISTRIBUTE THE LIBRARY AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE LIBRARY (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE LIBRARY TO OPERATE WITH ANY OTHER SOFTWARE), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Libraries

If you develop a new library, and you want it to be of the greatest possible use to the public, we recommend making it free software that everyone can redistribute and change. You can do so by permitting redistribution under these terms (or, alternatively, under the terms of the ordinary General Public License).

To apply these terms, attach the following notices to the library. It is safest to attach them to the start of each source file to most effectively convey the exclusion of warranty; and each file should have at least the "copyright" line and a pointer to where the full notice is found.

```
<one line to give the library's name and a brief idea of what it does.>  
Copyright (C) <year> <name of author>
```

This library is free software; you can redistribute it and/or modify it under the terms of the GNU Lesser General Public License as published by the Free Software Foundation; either version 2.1 of the License, or (at your option) any later version.

This library is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU Lesser General Public License for more details.

You should have received a copy of the GNU Lesser General Public License along with this library; if not, write to the Free Software Foundation, Inc., 51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA

Also add information on how to contact you by electronic and paper mail.

You should also get your employer (if you work as a programmer) or your school, if any, to sign a "copyright disclaimer" for the library, if necessary. Here is a sample; alter the names:

Yoyodyne, Inc., hereby disclaims all copyright interest in the library `Frob' (a library for tweaking knobs) written by James Random Hacker.

<signature of Ty Coon>, 1 April 1990
Ty Coon, President of Vice

That's all there is to it!

UNICODE, INC. LICENSE AGREEMENT - DATA FILES AND SOFTWARE

Unicode Data Files include all data files under the directories <http://www.unicode.org/Public/>, <http://www.unicode.org/reports/>, and <http://www.unicode.org/cldr/data/>. Unicode Data Files do not include PDF online code charts under the directory <http://www.unicode.org/Public/>. Software includes any source code published in the Unicode Standard or under the directories <http://www.unicode.org/Public/>, <http://www.unicode.org/reports/>, and <http://www.unicode.org/cldr/data/>.

NOTICE TO USER: Carefully read the following legal agreement. BY DOWNLOADING, INSTALLING, COPYING OR OTHERWISE USING UNICODE INC.'S DATA FILES ("DATA FILES"), AND/OR SOFTWARE ("SOFTWARE"), YOU UNEQUIVOCALLY ACCEPT, AND AGREE TO BE BOUND BY, ALL OF THE TERMS AND CONDITIONS OF THIS AGREEMENT. IF YOU DO NOT AGREE, DO NOT DOWNLOAD, INSTALL, COPY, DISTRIBUTE OR USE THE DATA FILES OR SOFTWARE.

COPYRIGHT AND PERMISSION NOTICE

Copyright 1991-2013 Unicode, Inc. All rights reserved. Distributed under the Terms of Use in <http://www.unicode.org/copyright.html>.

Permission is hereby granted, free of charge, to any person obtaining a copy of the Unicode data files and any associated documentation (the "Data Files") or Unicode software and any associated documentation (the "Software") to deal in the Data Files or Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, and/or sell copies of the Data Files or Software, and to permit persons to whom the Data Files or Software are furnished to do so, provided that (a) the above copyright notice(s) and this permission notice appear with all copies of the Data Files or Software, (b) both the above copyright notice(s) and this permission notice appear in associated documentation, and (c) there is clear notice in each modified Data File or in the Software as well as in the documentation associated with the Data File(s) or Software that the data or software has been modified.

THE DATA FILES AND SOFTWARE ARE PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT OF THIRD PARTY RIGHTS. IN NO EVENT SHALL THE COPYRIGHT HOLDER OR HOLDERS INCLUDED IN THIS NOTICE BE LIABLE FOR ANY CLAIM, OR ANY SPECIAL INDIRECT OR CONSEQUENTIAL DAMAGES, OR ANY DAMAGES WHATSOEVER RESULTING FROM LOSS OF USE, DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE OR OTHER TORTIOUS ACTION, ARISING OUT OF OR IN CONNECTION WITH THE USE OR PERFORMANCE OF THE DATA FILES OR SOFTWARE.

Except as contained in this notice, the name of a copyright holder shall not be used in advertising or otherwise to promote the sale, use or other dealings in these Data Files or Software without prior written authorization of the copyright holder.

This file contains the copying permission notices for various files in the GNU C Library distribution that have copyright owners other than the Free Software Foundation. These notices all require that a copy of the notice be included in the accompanying documentation and be distributed with binary distributions of the code, so be sure to include this file along with any binary distributions derived from the GNU C Library.

All code incorporated from 4.4 BSD is distributed under the following license:

Copyright (C) 1991 Regents of the University of California.
All rights reserved.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

1. Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.
2. Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.
3. [This condition was removed.]
4. Neither the name of the University nor the names of its contributors may be used to endorse or promote products derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE REGENTS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE REGENTS OR CONTRIBUTORS BE LIABLE

FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

The DNS resolver code, taken from BIND 4.9.5, is copyrighted by UC Berkeley, by Digital Equipment Corporation and by Internet Software Consortium. The DEC portions are under the following license:

Portions Copyright (C) 1993 by Digital Equipment Corporation.

Permission to use, copy, modify, and distribute this software for any purpose with or without fee is hereby granted, provided that the above copyright notice and this permission notice appear in all copies, and that the name of Digital Equipment Corporation not be used in advertising or publicity pertaining to distribution of the document or software without specific, written prior permission.

THE SOFTWARE IS PROVIDED ``AS IS" AND DIGITAL EQUIPMENT CORP. DISCLAIMS ALL WARRANTIES WITH REGARD TO THIS SOFTWARE, INCLUDING ALL IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS. IN NO EVENT SHALL DIGITAL EQUIPMENT CORPORATION BE LIABLE FOR ANY SPECIAL, DIRECT, INDIRECT, OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES WHATSOEVER RESULTING FROM LOSS OF USE, DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE OR OTHER TORTIOUS ACTION, ARISING OUT OF OR IN CONNECTION WITH THE USE OR PERFORMANCE OF THIS SOFTWARE.

The ISC portions are under the following license:

Portions Copyright (c) 1996-1999 by Internet Software Consortium.

Permission to use, copy, modify, and distribute this software for any purpose with or without fee is hereby granted, provided that the above copyright notice and this permission notice appear in all copies.

THE SOFTWARE IS PROVIDED "AS IS" AND INTERNET SOFTWARE CONSORTIUM DISCLAIMS ALL WARRANTIES WITH REGARD TO THIS SOFTWARE INCLUDING ALL IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS. IN NO EVENT SHALL INTERNET SOFTWARE CONSORTIUM BE LIABLE FOR ANY SPECIAL, DIRECT, INDIRECT, OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES WHATSOEVER RESULTING FROM LOSS OF USE, DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE OR OTHER TORTIOUS ACTION, ARISING

OUT OF OR IN CONNECTION WITH THE USE OR PERFORMANCE OF THIS SOFTWARE.

The Sun RPC support (from rpcsrc-4.0) is covered by the following license:

Copyright (c) 2010, Oracle America, Inc.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

- * Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.
- * Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.
- * Neither the name of the "Oracle America, Inc." nor the names of its contributors may be used to endorse or promote products derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT HOLDER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

The following CMU license covers some of the support code for Mach, derived from Mach 3.0:

Mach Operating System
Copyright (C) 1991,1990,1989 Carnegie Mellon University
All Rights Reserved.

Permission to use, copy, modify and distribute this software and its documentation is hereby granted, provided that both the copyright notice and this permission notice appear in all copies of the

software, derivative works or modified versions, and any portions thereof, and that both notices appear in supporting documentation.

CARNEGIE MELLON ALLOWS FREE USE OF THIS SOFTWARE IN ITS ``AS IS" CONDITION. CARNEGIE MELLON DISCLAIMS ANY LIABILITY OF ANY KIND FOR ANY DAMAGES WHATSOEVER RESULTING FROM THE USE OF THIS SOFTWARE.

Carnegie Mellon requests users of this software to return to

Software Distribution Coordinator
School of Computer Science
Carnegie Mellon University
Pittsburgh PA 15213-3890

or Software.Distribution@CS.CMU.EDU any improvements or extensions that they make and grant Carnegie Mellon the rights to redistribute these changes.

The file if_ppp.h is under the following CMU license:

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

1. Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.
2. Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.
3. Neither the name of the University nor the names of its contributors may be used to endorse or promote products derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY CARNEGIE MELLON UNIVERSITY AND CONTRIBUTORS ``AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE UNIVERSITY OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

The following license covers the files from Intel's "Highly Optimized

Mathematical Functions for Itanium" collection:

Intel License Agreement

Copyright (c) 2000, Intel Corporation

All rights reserved.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

* Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.

* Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.

* The name of Intel Corporation may not be used to endorse or promote products derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL INTEL OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

The files inet/getnameinfo.c and sysdeps/posix/getaddrinfo.c are copyright (C) by Craig Metz and are distributed under the following license:

```
/* The Inner Net License,  
Version 2.00
```

The author(s) grant permission for redistribution and use in source and binary forms, with or without modification, of the software and documentation provided that the following conditions are met:

0. If you receive a version of the software that is specifically labelled as not being for redistribution (check the version message and/or README),

you are not permitted to redistribute that version of the software in any way or form.

1. All terms of the all other applicable copyrights and licenses must be followed.
2. Redistributions of source code must retain the authors' copyright notice(s), this list of conditions, and the following disclaimer.
3. Redistributions in binary form must reproduce the authors' copyright notice(s), this list of conditions, and the following disclaimer in the documentation and/or other materials provided with the distribution.
4. [The copyright holder has authorized the removal of this clause.]
5. Neither the name(s)
of the author(s) nor the names of its contributors
may be used to endorse or promote products derived from this software
without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY ITS AUTHORS AND CONTRIBUTORS ``AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE AUTHORS OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

If these license terms cause you a real problem, contact the author. */

The file sunrpc/des_impl.c
is copyright Eric Young:

Copyright (C) 1992 Eric Young

Collected from libdes and modified for SECURE RPC by Martin Kuck 1994

This file is distributed under the terms of the GNU Lesser General
Public License, version 2.1 or later - see the file COPYING.LIB for details.

If you did not receive a copy of the license with this program, please
see <<http://www.gnu.org/licenses/>> to obtain a copy.

The libidn code is copyright Simon Josefsson, with portions copyright
The Internet Society, Tom Tromey and Red Hat, Inc.:

Copyright (C) 2002, 2003, 2004, 2011 Simon Josefsson

This file is part of GNU Libidn.

GNU Libidn is free software; you can redistribute it and/or
modify it under the terms of the GNU Lesser General Public
License as published by the Free Software Foundation; either

version 2.1 of the License, or (at your option) any later version.

GNU Libidn is distributed in the hope that it will be useful,
but WITHOUT ANY WARRANTY; without even the implied warranty of
MERCHANTABILITY
or FITNESS FOR A PARTICULAR PURPOSE. See the GNU
Lesser General Public License for more details.

You should have received a copy of the GNU Lesser General Public
License along with GNU Libidn; if not, see <<http://www.gnu.org/licenses/>>.

The following notice applies to portions of libidn/nfkc.c:

This file contains functions from GLIB, including gutf8.c and
gunidecomp.c, all licensed under LGPL and copyright hold by:

Copyright (C) 1999, 2000 Tom Tromeey
Copyright 2000 Red Hat, Inc.

The following applies to portions of libidn/punycodes.c and
libidn/punycodes.h:

This file is derived from RFC 3492bis written by Adam M. Costello.

Disclaimer and license: Regarding this entire document or any
portion of it (including the pseudocode and C code), the author
makes no guarantees and is not responsible for any damage resulting
from its use. The author grants irrevocable permission to anyone
to use, modify, and distribute it in any way that does not diminish
the rights of anyone else
to use, modify, and distribute it,
provided that redistributed derivative works do not contain
misleading author or version information. Derivative works need
not be licensed under similar terms.

Copyright (C) The Internet Society (2003). All Rights Reserved.

This document and translations of it may be copied and furnished to
others, and derivative works that comment on or otherwise explain it
or assist in its implementation may be prepared, copied, published
and distributed, in whole or in part, without restriction of any
kind, provided that the above copyright notice and this paragraph are
included on all such copies and derivative works. However, this
document itself may not be modified in any way, such as by removing
the copyright notice or references to the Internet Society or other
Internet organizations, except as needed for the purpose of
developing Internet standards in which case the procedures for
copyrights defined in the Internet Standards process must be

followed,
or as required to translate it into languages other than
English.

The limited permissions granted above are perpetual and will not be
revoked by the Internet Society or its successors or assigns.

This document and the information contained herein is provided on an
"AS IS" basis and THE INTERNET SOCIETY AND THE INTERNET ENGINEERING
TASK FORCE DISCLAIMS ALL WARRANTIES, EXPRESS OR IMPLIED, INCLUDING
BUT NOT LIMITED TO ANY WARRANTY THAT THE USE OF THE INFORMATION
HEREIN WILL NOT INFRINGE ANY RIGHTS OR ANY IMPLIED WARRANTIES OF
MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.

The file inet/rcmd.c is under a UCB copyright and the following:

Copyright (C) 1998 WIDE Project.
All rights reserved.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions
are met:

1. Redistributions of source code must retain the above copyright
notice, this list of conditions and the following disclaimer.
2. Redistributions
in binary form must reproduce the above copyright
notice, this list of conditions and the following disclaimer in the
documentation and/or other materials provided with the distribution.
3. Neither the name of the project nor the names of its contributors
may be used to endorse or promote products derived from this software
without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE PROJECT AND CONTRIBUTORS ``AS IS" AND
ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE
IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE
ARE DISCLAIMED. IN NO EVENT SHALL THE PROJECT OR CONTRIBUTORS BE LIABLE
FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL
DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS
OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION)
HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT
LIABILITY, OR TORT (INCLUDING NEGLIGENCE
OR OTHERWISE) ARISING IN ANY WAY
OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF
SUCH DAMAGE.

The file posix/runtests.c is copyright Tom Lord:

Copyright 1995 by Tom Lord

All Rights Reserved

Permission to use, copy, modify, and distribute this software and its documentation for any purpose and without fee is hereby granted, provided that the above copyright notice appear in all copies and that both that copyright notice and this permission notice appear in supporting documentation, and that the name of the copyright holder not be used in advertising or publicity pertaining to distribution of the software without specific, written prior permission.

Tom Lord DISCLAIMS ALL WARRANTIES WITH REGARD TO THIS SOFTWARE, INCLUDING ALL IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS, IN NO EVENT SHALL TOM LORD BE LIABLE FOR ANY SPECIAL, INDIRECT OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES WHATSOEVER RESULTING FROM LOSS OF USE, DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE OR OTHER TORTIOUS ACTION, ARISING OUT OF OR IN CONNECTION WITH THE USE OR PERFORMANCE OF THIS SOFTWARE.

The posix/rxspencer tests are copyright Henry Spencer:

Copyright 1992, 1993, 1994, 1997 Henry Spencer. All rights reserved. This software is not subject to any license of the American Telephone and Telegraph Company or of the Regents of the University of California.

Permission is granted to anyone to use this software for any purpose on any computer system, and to alter it and redistribute it, subject to the following restrictions:

1. The author is not responsible for the consequences of use of this software, no matter how awful, even if they arise from flaws in it.
2. The origin of this software must not be misrepresented, either by explicit claim or by omission. Since few users ever read sources, credits must appear in the documentation.
3. Altered versions must be plainly marked as such, and must not be misrepresented as being the original software. Since few users ever read sources, credits must appear in the documentation.
4. This notice may not be removed or altered.

The file posix/PCRE.tests is copyright University of Cambridge:

Copyright (c) 1997-2003 University of Cambridge

Permission is granted to anyone to use this software for any purpose on any computer system, and to redistribute it freely, subject to the following restrictions:

1. This software is distributed in the hope that it will be useful, but **WITHOUT ANY WARRANTY**; without even the implied warranty of **MERCHANTABILITY** or **FITNESS FOR A PARTICULAR PURPOSE**.
2. The origin of this software must not be misrepresented, either by explicit claim or by omission. In practice, this means that if you use PCRE in software that you distribute to others, commercially or otherwise, you must put a sentence like this

Regular expression support is provided by the PCRE library package, which is open source software, written by Philip Hazel, and copyright by the University of Cambridge, England.

somewhere reasonably visible in your documentation and in any relevant files or online help data or similar. A reference to the ftp site for the source, that is, to

<ftp://ftp.csx.cam.ac.uk/pub/software/programming/pcre/>

should also be given in the documentation. However, this condition is not intended to apply to whole chains of software. If package A includes PCRE, it must acknowledge it, but if package B is software that includes package A, the condition is not imposed on package B (unless it uses PCRE independently).

3. Altered versions must be plainly marked as such, and must not be misrepresented as being the original software.
4. If PCRE is embedded in any software that is released under the GNU General Purpose Licence (GPL), or Lesser General Purpose Licence (LGPL), then the terms of that licence shall supersede any condition above with which it is incompatible.

Files

from Sun fdlbm are copyright Sun Microsystems, Inc.:

Copyright (C) 1993 by Sun Microsystems, Inc. All rights reserved.

Developed at SunPro, a Sun Microsystems, Inc. business.
Permission to use, copy, modify, and distribute this software is freely granted, provided that this notice is preserved.

Part of stdio-common/tst-printf.c is copyright C E Chew:

(C) Copyright C E Chew

Feel free to copy, use and distribute this software provided:

1. you do not pretend that you wrote it
2. you leave this copyright notice intact.

Various long double libm functions are copyright Stephen L. Moshier:

Copyright 2001 by Stephen L. Moshier <moshier@na-net.ornl.gov>

This library is free software; you can redistribute it and/or modify it under the terms of the GNU Lesser General Public License as published by the Free Software Foundation; either version 2.1 of the License, or (at your option) any later version.

This library is distributed in the hope that it will be useful,
but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU Lesser General Public License for more details.

You should have received a copy of the GNU Lesser General Public License along with this library; if not, see
<<http://www.gnu.org/licenses/>>. */

1.76 libc 2.27-3ubuntu1.6

1.76.1 Available under license :

Copyright 1992, 1993, 1994, 1997 Henry Spencer. All rights reserved.
This software is not subject to any license of the American Telephone and Telegraph Company or of the Regents of the University of California.

Permission is granted to anyone to use this software for any purpose on any computer system, and to alter it and redistribute it, subject to the following restrictions:

1. The author is not responsible for the consequences of use of this software, no matter how awful, even if they arise from flaws in it.
2. The origin of this software must not be misrepresented, either by explicit claim or by omission. Since few users ever read sources, credits must appear in the documentation.
3. Altered versions must be plainly marked as such, and must not be

misrepresented as being the original software. Since few users ever read sources, credits must appear in the documentation.

4. This notice may not be removed or altered.

GNU GENERAL PUBLIC LICENSE

Version 2, June 1991

Copyright (C) 1989, 1991 Free Software Foundation, Inc.,
51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA
Everyone is permitted to copy and distribute verbatim copies
of this license document, but changing it is not allowed.

Preamble

The licenses for most software are designed to take away your freedom to share and change it. By contrast, the GNU General Public License is intended to guarantee your freedom to share and change free software--to make sure the software is free for all its users. This General Public License applies to most of the Free Software Foundation's software and to any other program whose authors commit to using it. (Some other Free Software Foundation software is covered by the GNU Lesser General Public License instead.) You can apply it to your programs, too.

When we speak of free software, we are referring to freedom, not price.

Our General Public Licenses are designed to make sure that you have the freedom to distribute copies of free software (and charge for this service if you wish), that you receive source code or can get it if you want it, that you can change the software or use pieces of it in new free programs; and that you know you can do these things.

To protect your rights, we need to make restrictions that forbid anyone to deny you these rights or to ask you to surrender the rights. These restrictions translate to certain responsibilities for you if you distribute copies of the software, or if you modify it.

For example, if you distribute copies of such a program, whether gratis or for a fee, you must give the recipients all the rights that you have. You must make sure that they, too, receive or can get the source code. And you must show them these terms so they know their rights.

We protect your rights with two steps: (1) copyright the software, and (2) offer you this license which gives you legal permission to copy, distribute and/or modify the software.

Also, for each author's protection and ours, we want to make certain that everyone understands that there is no warranty for this free software. If the software is modified by someone else and passed on, we want its recipients to know that what they have is not the original, so that any problems introduced by others will not reflect on the original authors' reputations.

Finally, any free program is threatened constantly by software patents. We wish to avoid the danger that redistributors of a free program will individually obtain patent licenses, in effect making the program proprietary. To prevent this, we have made it clear that any patent must be licensed for everyone's free use or not licensed at all.

The precise terms and conditions for copying, distribution and modification follow.

GNU GENERAL PUBLIC LICENSE TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

0. This License applies to any program or other work which contains a notice placed by the copyright holder saying it may be distributed under the terms of this General Public License. The "Program", below, refers to any such program or work, and a "work based on the Program" means either the Program or any derivative work under copyright law: that is to say, a work containing the Program or a portion of it, either verbatim or with modifications and/or translated into another language. (Hereinafter, translation is included without limitation in the term "modification".) Each licensee is addressed as "you".

Activities other than copying, distribution and modification are not covered by this License; they are outside its scope. The act of running the Program is not restricted, and the output from the Program is covered only if its contents constitute a work based on the Program (independent of having been made by running the Program). Whether that is true depends on what the Program does.

1. You may copy and distribute verbatim copies of the Program's source code as you receive it, in any medium, provided that you conspicuously and appropriately publish on each copy an appropriate copyright notice and disclaimer of warranty; keep intact all the notices that refer to this License and to the absence of any warranty; and give any other recipients of the Program a copy of this License along with the Program.

You may charge a fee for the physical act of transferring a copy, and you may at your option offer warranty protection in exchange for a fee.

2. You may modify your copy or copies of the Program or any portion of it, thus forming a work based on the Program, and copy and distribute such modifications or work under the terms of Section 1 above, provided that you also meet all of these conditions:

a) You must cause the modified files to carry prominent notices stating that you changed the files and the date of any change.

b) You must cause any work that you distribute or publish, that in whole or in part contains or is derived from the Program or any part thereof, to be licensed as a whole at no charge to all third parties under the terms of this License.

c) If the modified program normally reads commands interactively when run, you must cause it, when started running for such interactive use in the most ordinary way, to print or display an announcement including an appropriate copyright notice and a notice that there is no warranty (or else, saying that you provide a warranty) and that users may redistribute the program under these conditions, and telling the user how to view a copy of this License. (Exception: if the Program itself is interactive but does not normally print such an announcement, your work based on the Program is not required to print an announcement.)

These requirements apply to the modified work as a whole. If identifiable sections of that work are not derived from the Program, and can be reasonably considered independent and separate works in themselves, then this License, and its terms, do not apply to those sections when you distribute them as separate works. But when you distribute the same sections as part of a whole which is a work based on the Program, the distribution of the whole must be on the terms of this License, whose permissions for other licensees extend to the entire whole, and thus to each and every part regardless of who wrote it.

Thus, it is not the intent of this section to claim rights or contest your rights to work written entirely by you; rather, the intent is to exercise the right to control the distribution of derivative or collective works based on the Program.

In addition, mere aggregation of another work not based on the Program with the Program (or with a work based on the Program) on a volume of a storage or distribution medium does not bring the other work under the scope of this License.

3. You may copy and distribute the Program (or a work based on it, under Section 2) in object code or executable form under the terms of

Sections 1 and 2 above provided that you also do one of the following:

- a) Accompany it with the complete corresponding machine-readable source code, which must be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange; or,
- b) Accompany it with a written offer, valid for at least three years, to give any third party, for a charge no more than your cost of physically performing source distribution, a complete machine-readable copy of the corresponding source code, to be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange; or,
- c) Accompany it with the information you received as to the offer to distribute corresponding source code. (This alternative is allowed only for noncommercial distribution and only if you received the program in object code or executable form with such an offer, in accord with Subsection b above.)

The source code for a work means the preferred form of the work for making modifications to it. For an executable work, complete source code means all the source code for all modules it contains, plus any associated interface definition files, plus the scripts used to control compilation and installation of the executable. However, as a special exception, the source code distributed need not include anything that is normally distributed (in either source or binary form) with the major components (compiler, kernel, and so on) of the operating system on which the executable runs, unless that component itself accompanies the executable.

If distribution of executable or object code is made by offering access to copy from a designated place, then offering equivalent access to copy the source code from the same place counts as distribution of the source code, even though third parties are not compelled to copy the source along with the object code.

4. You may not copy, modify, sublicense, or distribute the Program except as expressly provided under this License. Any attempt otherwise to copy, modify, sublicense or distribute the Program is void, and will automatically terminate your rights under this License. However, parties who have received copies, or rights, from you under this License will not have their licenses terminated so long as such parties remain in full compliance.

5. You are not required to accept this License, since you have not signed it. However, nothing else grants you permission to modify or

distribute the Program or its derivative works. These actions are prohibited by law if you do not accept this License. Therefore, by modifying or distributing the Program (or any work based on the Program), you indicate your acceptance of this License to do so, and all its terms and conditions for copying, distributing or modifying the Program or works based on it.

6. Each time you redistribute the Program (or any work based on the Program), the recipient automatically receives a license from the original licensor to copy, distribute or modify the Program subject to these terms and conditions. You may not impose any further restrictions on the recipients' exercise of the rights granted herein. You are not responsible for enforcing compliance by third parties to this License.

7. If, as a consequence of a court judgment or allegation of patent infringement or for any other reason (not limited to patent issues), conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot distribute so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not distribute the Program at all. For example, if a patent license would not permit royalty-free redistribution of the Program by all those who receive copies directly or indirectly through you, then the only way you could satisfy both it and this License would be to refrain entirely from distribution of the Program.

If any portion of this section is held invalid or unenforceable under any particular circumstance, the balance of the section is intended to apply and the section as a whole is intended to apply in other circumstances.

It is not the purpose of this section to induce you to infringe any patents or other property right claims or to contest validity of any such claims; this section has the sole purpose of protecting the integrity of the free software distribution system, which is implemented by public license practices. Many people have made generous contributions to the wide range of software distributed through that system in reliance on consistent application of that system; it is up to the author/donor to decide if he or she is willing to distribute software through any other system and a licensee cannot impose that choice.

This section is intended to make thoroughly clear what is believed to

be a consequence of the rest of this License.

8. If the distribution and/or use of the Program is restricted in certain countries either by patents or by copyrighted interfaces, the original copyright holder who places the Program under this License may add an explicit geographical distribution limitation excluding those countries, so that distribution is permitted only in or among countries not thus excluded. In such case, this License incorporates the limitation as if written in the body of this License.

9. The Free Software Foundation may publish revised and/or new versions of the General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Program specifies a version number of this License which applies to it and "any later version", you have the option of following the terms and conditions either of that version or of any later version published by the Free Software Foundation. If the Program does not specify a version number of this License, you may choose any version ever published by the Free Software Foundation.

10. If you wish to incorporate parts of the Program into other free programs whose distribution conditions are different, write to the author to ask for permission. For software which is copyrighted by the Free Software Foundation, write to the Free Software Foundation; we sometimes make exceptions for this. Our decision will be guided by the two goals of preserving the free status of all derivatives of our free software and of promoting the sharing and reuse of software generally.

NO WARRANTY

11. BECAUSE THE PROGRAM IS LICENSED FREE OF CHARGE, THERE IS NO WARRANTY FOR THE PROGRAM, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE PROGRAM "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE PROGRAM IS WITH YOU. SHOULD THE PROGRAM PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

12. IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY AND/OR REDISTRIBUTE THE PROGRAM AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES,

INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE PROGRAM (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR

THIRD PARTIES OR A FAILURE OF THE PROGRAM TO OPERATE WITH ANY OTHER PROGRAMS), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Programs

If you develop a new program, and you want it to be of the greatest possible use to the public, the best way to achieve this is to make it free software which everyone can redistribute and change under these terms.

To do so, attach the following notices to the program. It is safest to attach them to the start of each source file to most effectively convey the exclusion of warranty; and each file should have at least the "copyright" line and a pointer to where the full notice is found.

```
<one line to give the program's name and a brief idea of what it does.>  
Copyright (C) <year> <name of author>
```

```
This program is free software; you can redistribute it and/or modify  
it under the terms of the GNU  
General Public License as published by  
the Free Software Foundation; either version 2 of the License, or  
(at your option) any later version.
```

```
This program is distributed in the hope that it will be useful,  
but WITHOUT ANY WARRANTY; without even the implied warranty of  
MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the  
GNU General Public License for more details.
```

```
You should have received a copy of the GNU General Public License along  
with this program; if not, write to the Free Software Foundation, Inc.,  
51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA.
```

Also add information on how to contact you by electronic and paper mail.

If the program is interactive, make it output a short notice like this when it starts in an interactive mode:

```
Gnomovision version 69, Copyright (C) year name of author  
Gnomovision comes with ABSOLUTELY NO WARRANTY; for details type `show w'.  
This is free software, and you are welcome to redistribute
```

it

under certain conditions; type `show c' for details.

The hypothetical commands `show w' and `show c' should show the appropriate parts of the General Public License. Of course, the commands you use may be called something other than `show w' and `show c'; they could even be mouse-clicks or menu items--whatever suits your program.

You should also get your employer (if you work as a programmer) or your school, if any, to sign a "copyright disclaimer" for the program, if necessary. Here is a sample; alter the names:

Yoyodyne, Inc., hereby disclaims all copyright interest in the program
`Gnomovision' (which makes passes at compilers) written by James Hacker.

<signature of Ty Coon>, 1 April 1989

Ty Coon, President of Vice

This General Public License does not permit incorporating your program into proprietary programs. If your program is a subroutine library, you may consider it more useful to permit linking proprietary applications with the library. If this is what you want to do, use the GNU Lesser General Public License instead of this License.

GNU LESSER GENERAL PUBLIC LICENSE

Version 2.1, February 1999

Copyright (C) 1991, 1999 Free Software Foundation, Inc.
51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA
Everyone is permitted to copy and distribute verbatim copies
of this license document, but changing it is not allowed.

[This is the first released version of the Lesser GPL. It also counts
as the successor of the GNU Library Public License, version 2, hence
the version number 2.1.]

Preamble

The licenses for most software are designed to take away your freedom to share and change it. By contrast, the GNU General Public Licenses are intended to guarantee your freedom to share and change free software--to make sure the software is free for all its users.

This license, the Lesser General Public License, applies to some specially designated software packages--typically libraries--of the Free Software Foundation and other authors who decide to use it. You can use it too, but we suggest you first think carefully about whether

this license or the ordinary General Public License is the better strategy to use in any particular case, based on the explanations below.

When we speak of free software, we are referring to freedom of use, not price. Our General Public Licenses are designed to make sure that you have the freedom to distribute copies of free software (and charge for this service if you wish); that you receive source code or can get it if you want it; that you can change the software and use pieces of it in new free programs; and that you are informed that you can do these things.

To protect your rights, we need to make restrictions that forbid distributors to deny you these rights or to ask you to surrender these rights. These restrictions translate to certain responsibilities for you if you distribute copies of the library or if you modify it.

For example, if you distribute copies of the library, whether gratis or for a fee, you must give the recipients all the rights that we gave you. You must make sure that they, too, receive or can get the source code. If you link other code with the library, you must provide complete object files to the recipients, so that they can relink them with the library after making changes to the library and recompiling it. And you must show them these terms so they know their rights.

We protect your rights with a two-step method: (1) we copyright the library, and (2) we offer you this license, which gives you legal permission to copy, distribute and/or modify the library.

To protect each distributor, we want to make it very clear that there is no warranty for the free library. Also, if the library is modified by someone else and passed on, the recipients should know that what they have is not the original version, so that the original author's reputation will not be affected by problems that might be introduced by others.

Finally, software patents pose a constant threat to the existence of any free program. We wish to make sure that a company cannot effectively restrict the users of a free program by obtaining a restrictive license from a patent holder. Therefore, we insist that any patent license obtained for a version of the library must be consistent with the full freedom of use specified in this license.

Most GNU software, including some libraries, is covered by the ordinary GNU General Public License. This license, the GNU Lesser General Public License, applies to certain designated libraries, and is quite different from the ordinary General Public License. We use

this license for certain libraries in order to permit linking those libraries into non-free programs.

When a program is linked with a library, whether statically or using a shared library, the combination of the two is legally speaking a combined work, a derivative of the original library. The ordinary General Public License therefore permits such linking only if the entire combination fits its criteria of freedom. The Lesser General Public License permits more lax criteria for linking other code with the library.

We call this license the "Lesser" General Public License because it does Less to protect the user's freedom than the ordinary General Public License. It also provides other free software developers Less of an advantage over competing non-free programs. These disadvantages are the reason we use the ordinary General Public License for many libraries. However, the Lesser license provides advantages in certain special circumstances.

For example, on rare occasions, there may be a special need to encourage the widest possible use of a certain library, so that it becomes a de-facto standard. To achieve this, non-free programs must be allowed to use the library. A more frequent case is that a free library does the same job as widely used non-free libraries. In this case, there is little to gain by limiting the free library to free software only, so we use the Lesser General Public License.

In other cases, permission to use a particular library in non-free programs enables a greater number of people to use a large body of free software. For example, permission to use the GNU C Library in non-free programs enables many more people to use the whole GNU operating system, as well as its variant, the GNU/Linux operating system.

Although the Lesser General Public License is Less protective of the users' freedom, it does ensure that the user of a program that is linked with the Library has the freedom and the wherewithal to run that program using a modified version of the Library.

The precise terms and conditions for copying, distribution and modification follow. Pay close attention to the difference between a "work based on the library" and a "work that uses the library". The former contains code derived from the library, whereas the latter must be combined with the library in order to run.

GNU LESSER GENERAL PUBLIC LICENSE
TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

0. This License Agreement applies to any software library or other program which contains a notice placed by the copyright holder or other authorized party saying it may be distributed under the terms of this Lesser General Public License (also called "this License"). Each licensee is addressed as "you".

A "library" means a collection of software functions and/or data prepared so as to be conveniently linked with application programs (which use some of those functions and data) to form executables.

The "Library", below, refers to any such software library or work which has been distributed under these terms. A "work based on the Library" means either the Library or any derivative work under copyright law: that is to say, a work containing the Library or a portion of it, either verbatim or with modifications and/or translated straightforwardly into another language. (Hereinafter, translation is included without limitation in the term "modification".)

"Source code" for a work means the preferred form of the work for making modifications to it. For a library, complete source code means all the source code for all modules it contains, plus any associated interface definition files, plus the scripts used to control compilation and installation of the library.

Activities other than copying, distribution and modification are not covered by this License; they are outside its scope. The act of running a program using the Library is not restricted, and output from such a program is covered only if its contents constitute a work based on the Library (independent of the use of the Library in a tool for writing it). Whether that is true depends on what the Library does and what the program that uses the Library does.

1. You may copy and distribute verbatim copies of the Library's complete source code as you receive it, in any medium, provided that you conspicuously and appropriately publish on each copy an appropriate copyright notice and disclaimer of warranty; keep intact all the notices that refer to this License and to the absence of any warranty; and distribute a copy of this License along with the Library.

You may charge a fee for the physical act of transferring a copy, and you may at your option offer warranty protection in exchange for a fee.

2. You may modify your copy or copies of the Library or any portion of it, thus forming a work based on the Library, and copy and distribute such modifications or work under the terms of Section 1 above, provided that you also meet all of these conditions:

- a) The modified work must itself be a software library.
- b) You must cause the files modified to carry prominent notices stating that you changed the files and the date of any change.
- c) You must cause the whole of the work to be licensed at no charge to all third parties under the terms of this License.
- d) If a facility in the modified Library refers to a function or a table of data to be supplied by an application program that uses the facility, other than as an argument passed when the facility is invoked, then you must make a good faith effort to ensure that, in the event an application does not supply such function or table, the facility still operates, and performs whatever part of its purpose remains meaningful.

(For example, a function in a library to compute square roots has a purpose that is entirely well-defined independent of the application. Therefore, Subsection 2d requires that any application-supplied function or table used by this function must be optional: if the application does not supply it, the square root function must still compute square roots.)

These requirements apply to the modified work as a whole. If identifiable sections of that work are not derived from the Library, and can be reasonably considered independent and separate works in themselves, then this License, and its terms, do not apply to those sections when you distribute them as separate works. But when you distribute the same sections as part of a whole which is a work based on the Library, the distribution of the whole must be on the terms of this License, whose permissions for other licensees extend to the entire whole, and thus to each and every part regardless of who wrote it.

Thus, it is not the intent of this section to claim rights or contest your rights to work written entirely by you; rather, the intent is to exercise the right to control the distribution of derivative or collective works based on the Library.

In addition, mere aggregation of another work not based on the Library

with the Library (or with a work based on the Library) on a volume of a storage or distribution medium does not bring the other work under the scope of this License.

3. You may opt to apply the terms of the ordinary
GNU General Public

License instead of this License to a given copy of the Library. To do this, you must alter all the notices that refer to this License, so that they refer to the ordinary GNU General Public License, version 2, instead of to this License. (If a newer version than version 2 of the ordinary GNU General Public License has appeared, then you can specify that version instead if you wish.) Do not make any other change in these notices.

Once this change is made in a given copy, it is irreversible for that copy, so the ordinary GNU General Public License applies to all subsequent copies and derivative works made from that copy.

This option is useful when you wish to copy part of the code of the Library into a program that is not a library.

4. You may copy and distribute the Library (or a portion or derivative of it, under Section 2) in object code or executable form under the terms of Sections 1 and 2 above provided that you accompany it with the complete corresponding machine-readable source code, which must be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange.

If distribution of object code is made by offering access to copy from a designated place, then offering equivalent access to copy the source code from the same place satisfies the requirement to distribute the source code, even though third parties are not compelled to copy the source along with the object code.

5. A program that contains no derivative of any portion of the Library, but is designed to work with the Library by being compiled or linked with it, is called a "work that uses the Library". Such a work, in isolation, is not a derivative work of the Library, and therefore falls outside the scope of this License.

However, linking a "work that uses the Library" with the Library creates an executable that is a derivative of the Library (because it contains portions of the Library), rather than a "work that uses the library". The executable is therefore covered by this License. Section 6 states terms for distribution of such executables.

When a "work that uses the Library" uses material from a header file that is part of the Library, the object code for the work may be a derivative work of the Library even though the source code is not. Whether this is true is especially significant if the work can be linked without the Library, or if the work is itself a library. The threshold for this to be true is not precisely defined by law.

If such an object file uses only numerical parameters, data structure layouts and accessors, and small macros and small inline functions (ten lines or less in length), then the use of the object file is unrestricted, regardless of whether it is legally a derivative work. (Executables containing this object code plus portions of the Library will still fall under Section 6.)

Otherwise, if the work is a derivative of the Library, you may distribute the object code for the work under the terms of Section 6. Any executables containing that work also fall under Section 6, whether or not they are linked directly with the Library itself.

6. As an exception to the Sections above, you may also combine or link a "work that uses the Library" with the Library to produce a work containing portions of the Library, and distribute that work under terms of your choice, provided that the terms permit modification of the work for the customer's own use and reverse engineering for debugging such modifications.

You must give prominent notice with each copy of the work that the Library is used in it and that the Library and its use are covered by this License. You must supply a copy of this License. If the work during execution displays copyright notices, you must include the copyright notice for the Library among them, as well as a reference directing the user to the copy of this License. Also, you must do one of these things:

- a) Accompany the work with the complete corresponding machine-readable source code for the Library including whatever changes were used in the work (which must be distributed under Sections 1 and 2 above); and, if the work is an executable linked with the Library, with the complete machine-readable "work that uses the Library", as object code and/or source code, so that the user can modify the Library and then relink to produce a modified executable containing the modified Library. (It is understood that the user who changes the contents of definitions files in the Library will not necessarily be able to recompile the application to use the modified definitions.)

- b) Use a suitable shared library mechanism for linking with the Library. A suitable mechanism is one that (1) uses at run time a copy of the library already present on the user's computer system, rather than copying library functions into the executable, and (2) will operate properly with a modified version of the library, if the user installs one, as long as the modified version is interface-compatible with the version that the work was made with.
- c) Accompany the work with a written offer, valid for at least three years, to give the same user the materials specified in Subsection 6a, above, for a charge no more than the cost of performing this distribution.
- d) If distribution of the work is made by offering access to copy from a designated place, offer equivalent access to copy the above specified materials from the same place.
- e) Verify that the user has already received a copy of these materials or that you have already sent this user a copy.

For an executable, the required form of the "work that uses the Library" must include any data and utility programs needed for reproducing the executable from it. However, as a special exception, the materials to be distributed need not include anything that is normally distributed (in either source or binary form) with the major components (compiler, kernel, and so on) of the operating system on which the executable runs, unless that component itself accompanies the executable.

It may happen that this requirement contradicts the license restrictions of other proprietary libraries that do not normally accompany the operating system. Such a contradiction means you cannot use both them and the Library together in an executable that you distribute.

7. You may place library facilities that are a work based on the Library side-by-side in a single library together with other library facilities not covered by this License, and distribute such a combined library, provided that the separate distribution of the work based on the Library and of the other library facilities is otherwise permitted, and provided that you do these two things:

- a) Accompany the combined library with a copy of the same work based on the Library, uncombined with any other library facilities. This must be distributed under the terms of the

Sections above.

b) Give prominent notice with the combined library of the fact that part of it is a work based on the Library, and explaining where to find the accompanying uncombined form of the same work.

8. You may not copy, modify, sublicense, link with, or distribute the Library except as expressly provided under this License. Any attempt otherwise to copy, modify, sublicense, link with, or distribute the Library is void, and will automatically terminate your rights under this License. However, parties who have received copies, or rights, from you under this License will not have their licenses terminated so long as such parties remain in full compliance.

9. You are not required to accept this License, since you have not signed it. However, nothing else grants you permission to modify or distribute the Library or its derivative works. These actions are prohibited by law if you do not accept this License. Therefore, by modifying or distributing the Library (or any work based on the Library), you indicate your acceptance of this License to do so, and all its terms and conditions for copying, distributing or modifying the Library or works based on it.

10. Each time you redistribute the Library (or any work based on the Library), the recipient automatically receives a license from the original licensor to copy, distribute, link with or modify the Library subject to these terms and conditions. You may not impose any further restrictions on the recipients' exercise of the rights granted herein. You are not responsible for enforcing compliance by third parties with this License.

11. If, as a consequence of a court judgment or allegation of patent infringement or for any other reason (not limited to patent issues), conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot distribute so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not distribute the Library at all. For example, if a patent license would not permit royalty-free redistribution of the Library by all those who receive copies directly or indirectly through you, then the only way you could satisfy both it and this License would be to refrain entirely from distribution of the Library.

If any portion of this section is held invalid or unenforceable under any particular circumstance, the balance of the section is intended to apply,

and the section as a whole is intended to apply in other circumstances.

It is not the purpose of this section to induce you to infringe any patents or other property right claims or to contest validity of any such claims; this section has the sole purpose of protecting the integrity of the free software distribution system which is implemented by public license practices. Many people have made generous contributions to the wide range of software distributed through that system in reliance on consistent application of that system; it is up to the author/donor to decide if he or she is willing to distribute software through any other system and a licensee cannot impose that choice.

This section is intended to make thoroughly clear what is believed to be a consequence of the rest of this License.

12. If the distribution and/or use of the Library is restricted in certain countries either by patents or by copyrighted interfaces, the original copyright holder who places the Library under this License may add an explicit geographical distribution limitation excluding those countries, so that distribution is permitted only in or among countries not thus excluded. In such case, this License incorporates the limitation as if written in the body of this License.

13. The Free Software Foundation may publish revised and/or new versions of the Lesser General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Library specifies a version number of this License which applies to it and "any later version", you have the option of following the terms and conditions either of that version or of any later version published by the Free Software Foundation. If the Library does not specify a license version number, you may choose any version ever published by the Free Software Foundation.

14. If you wish to incorporate parts of the Library into other free programs whose distribution conditions are incompatible with these, write to the author to ask for permission. For software which is copyrighted by the Free Software Foundation, write to the Free Software Foundation; we sometimes make exceptions for this. Our decision will be guided by the two goals of preserving the free status of all derivatives of our free software and of promoting the sharing and reuse of software generally.

NO WARRANTY

15. BECAUSE THE LIBRARY IS LICENSED FREE OF CHARGE, THERE IS NO WARRANTY FOR THE LIBRARY, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE LIBRARY "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE LIBRARY IS WITH YOU. SHOULD THE LIBRARY PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

16. IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY AND/OR REDISTRIBUTE THE LIBRARY AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE LIBRARY (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE LIBRARY TO OPERATE WITH ANY OTHER SOFTWARE), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Libraries

If you develop a new library, and you want it to be of the greatest possible use to the public, we recommend making it free software that everyone can redistribute and change. You can do so by permitting redistribution under these terms (or, alternatively, under the terms of the ordinary General Public License).

To apply these terms, attach the following notices to the library. It is safest to attach them to the start of each source file to most effectively convey the exclusion of warranty; and each file should have at least the "copyright" line and a pointer to where the full notice is found.

```
<one line to give the library's name and a brief idea of what it does.>  
Copyright (C) <year> <name of author>
```

This library is free software; you can redistribute it and/or modify it under the terms of the GNU Lesser General Public License as published by the Free Software Foundation; either version 2.1 of the License, or (at your option) any later version.

This library is distributed in the hope that it will be useful,
but WITHOUT ANY WARRANTY; without even the implied warranty of
MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU
Lesser General Public License for more details.

You should have received a copy of the GNU Lesser General Public
License along with this library; if not, write to the Free Software
Foundation, Inc., 51 Franklin Street, Fifth Floor, Boston, MA 02110-1301
USA

Also add information on how to contact you by electronic and paper mail.

You should also get your employer (if you work as a programmer) or your
school, if any, to sign a "copyright disclaimer" for the library, if
necessary. Here is a sample; alter the names:

Yoyodyne, Inc., hereby disclaims all copyright interest in the
library `Frob' (a library for tweaking knobs) written by James Random Hacker.

<signature of Ty Coon>, 1 April 1990
Ty Coon, President of Vice

That's all there is to it!
UNICODE, INC. LICENSE AGREEMENT - DATA FILES AND SOFTWARE

Unicode Data Files include all data files under the directories
<http://www.unicode.org/Public/>, <http://www.unicode.org/reports/>, and
<http://www.unicode.org/cldr/data/>. Unicode Data Files do not include PDF
online code charts under the directory <http://www.unicode.org/Public/>.
Software includes any source code published in the Unicode Standard or under
the directories <http://www.unicode.org/Public/>,
<http://www.unicode.org/reports/>, and <http://www.unicode.org/cldr/data/>.

NOTICE TO USER: Carefully read the following legal agreement. BY
DOWNLOADING, INSTALLING, COPYING OR OTHERWISE USING UNICODE INC.'S DATA FILES
("DATA FILES"), AND/OR SOFTWARE ("SOFTWARE"), YOU UNEQUIVOCALLY ACCEPT, AND
AGREE TO BE BOUND BY, ALL OF THE TERMS AND CONDITIONS OF THIS AGREEMENT. IF
YOU DO NOT AGREE, DO NOT DOWNLOAD, INSTALL, COPY, DISTRIBUTE OR USE THE DATA
FILES OR SOFTWARE.

COPYRIGHT AND PERMISSION NOTICE

Copyright 1991-2013 Unicode,
Inc. All rights reserved. Distributed under
the Terms of Use in <http://www.unicode.org/copyright.html>.

Permission is hereby granted, free of charge, to any person obtaining a

copy of the Unicode data files and any associated documentation (the "Data Files") or Unicode software and any associated documentation (the "Software") to deal in the Data Files or Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, and/or sell copies of the Data Files or Software, and to permit persons to whom the Data Files or Software are furnished to do so, provided that (a) the above copyright notice(s) and this permission notice appear with all copies of the Data Files or Software, (b) both the above copyright notice(s) and this permission notice appear in associated documentation, and (c) there is clear notice in each modified Data File or in the Software as well as in the documentation associated with the Data File(s) or Software that the data or software has been modified.

THE DATA FILES AND SOFTWARE ARE PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT OF THIRD PARTY RIGHTS. IN NO EVENT SHALL THE COPYRIGHT HOLDER OR HOLDERS INCLUDED IN THIS NOTICE BE LIABLE FOR ANY CLAIM, OR ANY SPECIAL INDIRECT OR CONSEQUENTIAL DAMAGES, OR ANY DAMAGES WHATSOEVER RESULTING FROM LOSS OF USE, DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE OR OTHER TORTIOUS ACTION, ARISING OUT OF OR IN CONNECTION WITH THE USE OR PERFORMANCE OF THE DATA FILES OR SOFTWARE.

Except as contained in this notice, the name of a copyright holder shall not be used in advertising or otherwise to promote the sale, use or other dealings in these Data Files or Software without prior written authorization of the copyright holder.

This file contains the copying permission notices for various files in the GNU C Library distribution that have copyright owners other than the Free Software Foundation. These notices all require that a copy of the notice be included in the accompanying documentation and be distributed with binary distributions of the code, so be sure to include this file along with any binary distributions derived from the GNU C Library.

All code incorporated from 4.4 BSD is distributed under the following license:

Copyright (C) 1991 Regents of the University of California.
All rights reserved.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

1. Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.

2. Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.
3. [This condition was removed.]
4. Neither the name of the University nor the names of its contributors may be used to endorse or promote products derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE REGENTS AND CONTRIBUTORS ``AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE REGENTS OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

The DNS resolver code, taken from BIND 4.9.5, is copyrighted by UC Berkeley, by Digital Equipment Corporation and by Internet Software Consortium. The DEC portions are under the following license:

Portions Copyright (C) 1993 by Digital Equipment Corporation.

Permission to use, copy, modify, and distribute this software for any purpose with or without fee is hereby granted, provided that the above copyright notice and this permission notice appear in all copies, and that the name of Digital Equipment Corporation not be used in advertising or publicity pertaining to distribution of the document or software without specific, written prior permission.

THE SOFTWARE IS PROVIDED ``AS IS" AND DIGITAL EQUIPMENT CORP. DISCLAIMS ALL WARRANTIES WITH REGARD TO THIS SOFTWARE, INCLUDING ALL IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS. IN NO EVENT SHALL DIGITAL EQUIPMENT CORPORATION BE LIABLE FOR ANY SPECIAL, DIRECT, INDIRECT, OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES WHATSOEVER RESULTING FROM LOSS OF USE, DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE OR OTHER TORTIOUS ACTION, ARISING OUT OF OR IN CONNECTION WITH THE USE OR PERFORMANCE OF THIS SOFTWARE.

The ISC portions are under the following license:

Portions Copyright (c) 1996-1999 by Internet Software Consortium.

Permission to use, copy, modify, and distribute this software for any purpose with or without fee is hereby granted, provided that the above copyright notice and this permission notice appear in all copies.

THE SOFTWARE IS PROVIDED "AS IS" AND INTERNET SOFTWARE CONSORTIUM DISCLAIMS ALL WARRANTIES WITH REGARD TO THIS SOFTWARE INCLUDING ALL IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS. IN NO EVENT SHALL INTERNET SOFTWARE CONSORTIUM BE LIABLE FOR ANY SPECIAL, DIRECT, INDIRECT, OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES WHATSOEVER RESULTING FROM LOSS OF USE, DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE OR OTHER TORTIOUS ACTION, ARISING OUT OF OR IN CONNECTION WITH THE USE OR PERFORMANCE OF THIS SOFTWARE.

The Sun RPC support (from rpcsrc-4.0) is covered by the following license:

Copyright (c) 2010, Oracle America, Inc.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

- * Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.
- * Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.
- * Neither the name of the "Oracle America, Inc." nor the names of its contributors may be used to endorse or promote products derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT HOLDER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

The following CMU license covers some of the support code for Mach, derived from Mach 3.0:

Mach Operating System
Copyright (C) 1991,1990,1989 Carnegie Mellon University
All Rights Reserved.

Permission to use, copy, modify and distribute this software and its documentation is hereby granted, provided that both the copyright notice and this permission notice appear in all copies of the software, derivative works or modified versions, and any portions thereof, and that both notices appear in supporting documentation.

CARNEGIE MELLON ALLOWS FREE USE OF THIS SOFTWARE IN ITS ``AS IS" CONDITION. CARNEGIE MELLON DISCLAIMS ANY LIABILITY OF ANY KIND FOR ANY DAMAGES WHATSOEVER RESULTING FROM THE USE OF THIS SOFTWARE.

Carnegie Mellon requests users of this software to return to

Software Distribution Coordinator
School of Computer Science
Carnegie Mellon University
Pittsburgh PA 15213-3890

or Software.Distribution@CS.CMU.EDU any improvements or extensions that they make and grant Carnegie Mellon the rights to redistribute these changes.

The file `if_ppp.h` is under the following CMU license:

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

1. Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.
2. Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.
3. Neither the name of the University nor the names of its contributors may be used to endorse or promote products derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY CARNEGIE MELLON UNIVERSITY AND CONTRIBUTORS ``AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF

MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE UNIVERSITY OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS

INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

The following license covers the files from Intel's "Highly Optimized Mathematical Functions for Itanium" collection:

Intel License Agreement

Copyright (c) 2000, Intel Corporation

All rights reserved.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

* Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.

* Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.

* The name of Intel Corporation may not be used to endorse or promote products derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL INTEL OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

The files inet/getnameinfo.c and sysdeps/posix/getaddrinfo.c are copyright (C) by Craig Metz and are distributed under the following license:

```
/* The Inner Net License,  
Version 2.00
```

The author(s) grant permission for redistribution and use in source and binary forms, with or without modification, of the software and documentation provided that the following conditions are met:

0. If you receive a version of the software that is specifically labelled as not being for redistribution (check the version message and/or README), you are not permitted to redistribute that version of the software in any way or form.
1. All terms of the all other applicable copyrights and licenses must be followed.
2. Redistributions of source code must retain the authors' copyright notice(s), this list of conditions, and the following disclaimer.
3. Redistributions in binary form must reproduce the authors' copyright notice(s), this list of conditions, and the following disclaimer in the documentation and/or other materials provided with the distribution.
4. [The copyright holder has authorized the removal of this clause.]
5. Neither the name(s)
of the author(s) nor the names of its contributors
may be used to endorse or promote products derived from this software
without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY ITS AUTHORS AND CONTRIBUTORS ``AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE AUTHORS OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

If these license terms cause you a real problem, contact the author. */

The file sunrpc/des_impl.c
is copyright Eric Young:

Copyright (C) 1992 Eric Young

Collected from libdes and modified for SECURE RPC by Martin Kuck 1994

This file is distributed under the terms of the GNU Lesser General

Public License, version 2.1 or later - see the file COPYING.LIB for details.

If you did not receive a copy of the license with this program, please

see <<http://www.gnu.org/licenses/>> to obtain a copy.

The libidn code is copyright Simon Josefsson, with portions copyright
The Internet Society, Tom Tromej and Red Hat, Inc.:

Copyright (C) 2002, 2003, 2004, 2011 Simon Josefsson

This file is part of GNU Libidn.

GNU Libidn is free software; you can redistribute it and/or
modify it under the terms of the GNU Lesser General Public
License as published by the Free Software Foundation; either
version 2.1 of the License, or (at your option) any later version.

GNU Libidn is distributed in the hope that it will be useful,
but WITHOUT ANY WARRANTY; without even the implied warranty of
MERCHANTABILITY
or FITNESS FOR A PARTICULAR PURPOSE. See the GNU
Lesser General Public License for more details.

You should have received a copy of the GNU Lesser General Public
License along with GNU Libidn; if not, see <<http://www.gnu.org/licenses/>>.

The following notice applies to portions of libidn/nfkc.c:

This file contains functions from GLIB, including gutf8.c and
gunidecomp.c, all licensed under LGPL and copyright hold by:

Copyright (C) 1999, 2000 Tom Tromej
Copyright 2000 Red Hat, Inc.

The following applies to portions of libidn/punycod.c and
libidn/punycod.h:

This file is derived from RFC 3492bis written by Adam M. Costello.

Disclaimer and license: Regarding this entire document or any
portion of it (including the pseudocode and C code), the author
makes no guarantees and is not responsible for any damage resulting
from its use. The author grants irrevocable permission to anyone
to use, modify, and distribute it in any way that does not diminish
the rights of anyone else
to use, modify, and distribute it,
provided that redistributed derivative works do not contain
misleading author or version information. Derivative works need
not be licensed under similar terms.

Copyright (C) The Internet Society (2003). All Rights Reserved.

This document and translations of it may be copied and furnished to others, and derivative works that comment on or otherwise explain it or assist in its implementation may be prepared, copied, published and distributed, in whole or in part, without restriction of any kind, provided that the above copyright notice and this paragraph are included on all such copies and derivative works. However, this document itself may not be modified in any way, such as by removing the copyright notice or references to the Internet Society or other Internet organizations, except as needed for the purpose of developing Internet standards in which case the procedures for copyrights defined in the Internet Standards process must be followed,
or as required to translate it into languages other than English.

The limited permissions granted above are perpetual and will not be revoked by the Internet Society or its successors or assigns.

This document and the information contained herein is provided on an "AS IS" basis and THE INTERNET SOCIETY AND THE INTERNET ENGINEERING TASK FORCE DISCLAIMS ALL WARRANTIES, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO ANY WARRANTY THAT THE USE OF THE INFORMATION HEREIN WILL NOT INFRINGE ANY RIGHTS OR ANY IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.

The file inet/rcmd.c is under a UCB copyright and the following:

Copyright (C) 1998 WIDE Project.
All rights reserved.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

1. Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.
2. Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.
3. Neither the name of the project nor the names of its contributors may be used to endorse or promote products derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE PROJECT AND CONTRIBUTORS ``AS IS'' AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE PROJECT OR CONTRIBUTORS BE LIABLE

FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

The file posix/runtests.c is copyright Tom Lord:

Copyright 1995 by Tom Lord

All Rights Reserved

Permission to use, copy, modify, and distribute this software and its documentation for any purpose and without fee is hereby granted, provided that the above copyright notice appear in all copies and that both that copyright notice and this permission notice appear in supporting documentation, and that the name of the copyright holder not be used in advertising or publicity pertaining to distribution of the software without specific, written prior permission.

Tom Lord DISCLAIMS ALL WARRANTIES WITH REGARD TO THIS SOFTWARE, INCLUDING ALL IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS, IN NO EVENT SHALL TOM LORD BE LIABLE FOR ANY SPECIAL, INDIRECT OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES WHATSOEVER RESULTING FROM LOSS OF USE, DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE OR OTHER TORTIOUS ACTION, ARISING OUT OF OR IN CONNECTION WITH THE USE OR PERFORMANCE OF THIS SOFTWARE.

The posix/rxspencer tests are copyright Henry Spencer:

Copyright 1992, 1993, 1994, 1997 Henry Spencer. All rights reserved. This software is not subject to any license of the American Telephone and Telegraph Company or of the Regents of the University of California.

Permission is granted to anyone to use this software for any purpose on any computer system, and to alter it and redistribute it, subject to the following restrictions:

1. The author is not responsible for the consequences of use of this software, no matter how awful, even if they arise from flaws in it.
2. The origin of this software must not be misrepresented, either by explicit claim or by omission. Since few users ever read sources, credits must appear in the documentation.

3. Altered versions must be plainly marked as such, and must not be misrepresented as being the original software. Since few users ever read sources, credits must appear in the documentation.

4. This notice may not be removed or altered.

The file `posix/PCRE.tests` is copyright University of Cambridge:

Copyright (c) 1997-2003 University of Cambridge

Permission is granted to anyone to use this software for any purpose on any computer system, and to redistribute it freely, subject to the following restrictions:

1. This software is distributed in the hope that it will be useful, but **WITHOUT ANY WARRANTY**; without even the implied warranty of **MERCHANTABILITY** or **FITNESS FOR A PARTICULAR PURPOSE**.
2. The origin of this software must not be misrepresented, either by explicit claim or by omission. In practice, this means that if you use PCRE in software that you distribute to others, commercially or otherwise, you must put a sentence like this

Regular expression support is provided by the PCRE library package, which is open source software, written by Philip Hazel, and copyright by the University of Cambridge, England.

somewhere reasonably visible in your documentation and in any relevant files or online help data or similar. A reference to the ftp site for the source, that is, to

`ftp://ftp.csx.cam.ac.uk/pub/software/programming/pcre/`

should also be given in the documentation. However, this condition is not intended to apply to whole chains of software. If package A includes PCRE, it must acknowledge it, but if package B is software that includes package A, the condition is not imposed on package B (unless it uses PCRE independently).

3. Altered versions must be plainly marked as such, and must not be misrepresented as being the original software.

4. If PCRE is embedded in any software that is released under the GNU General Purpose Licence (GPL), or Lesser General Purpose Licence (LGPL), then the terms of that licence shall supersede any condition above with

which it is incompatible.

Files

from Sun fdlibm are copyright Sun Microsystems, Inc.:

Copyright (C) 1993 by Sun Microsystems, Inc. All rights reserved.

Developed at SunPro, a Sun Microsystems, Inc. business.

Permission to use, copy, modify, and distribute this software is freely granted, provided that this notice is preserved.

Part of stdio-common/tst-printf.c is copyright C E Chew:

(C) Copyright C E Chew

Feel free to copy, use and distribute this software provided:

1. you do not pretend that you wrote it
2. you leave this copyright notice intact.

Various long double libm functions are copyright Stephen L. Moshier:

Copyright 2001 by Stephen L. Moshier <moshier@na-net.ornl.gov>

This library is free software; you can redistribute it and/or modify it under the terms of the GNU Lesser General Public License as published by the Free Software Foundation; either version 2.1 of the License, or (at your option) any later version.

This library is distributed in the hope that it will be useful,
but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU Lesser General Public License for more details.

You should have received a copy of the GNU Lesser General Public License along with this library; if not, see
<<http://www.gnu.org/licenses/>>. */

1.77 e2fsprogs 1.44.1-1ubuntu1.4

1.77.1 Available under license :

This package was added to the e2fsprogs debian source package by Theodore Ts'o <tytso@mit.edu> on Sat Mar 15 15:33:37 EST 2003

It is part of the main e2fsprogs distribution, which can be found at:

<http://sourceforge.net/projects/e2fsprogs>

Upstream Author: Theodore Ts'o <tytso@mit.edu>

Copyright:

Copyright (C) 1999, 2001 by Andries Brouwer

Copyright (C) 1999, 2000, 2003 by Theodore Ts'o

You are free to distribute this software under the terms of the GNU Lesser (Library) General Public License.

On Debian systems, the complete text of the GNU Lesser (Library) General Public License can be found in /usr/share/common-licenses/LGPL-2. This is the Debian GNU/Linux prepackaged version of the static EXT2 file system consistency checker (e2fsck.static). The EXT2 utilities were written by Theodore Ts'o <tytso@mit.edu> and Remy Card <card@masi.ibp.fr>.

Sources were obtained from <http://sourceforge.net/projects/e2fsprogs>

Packaging is Copyright (c) 2003-2006 Theodore Ts'o <tytso@mit.edu>

Copyright (c) 1997-2003 Yann Dirson <dirson@debian.org>

Copyright (c) 2001 Alcove <<http://www.alcove.com/>>

Copyright (c) 1997 Klee Dienes

Copyright (c) 1995-1996 Michael Nonweiler <mrn20@cam.ac.uk>

Upstream Author: Theodore Ts'o <tytso@mit.edu>

Copyright notice:

This package, the EXT2 filesystem utilities, is protected by the GNU General Public License.

Copyright (c) 1993, 1994, 1995, 1996, 1997, 1998, 1999, 2000, 2001, 2002, 2003, 2004, 2005, 2006, 2007, 2008 by Theodore Ts'o

On Debian GNU systems, the complete text of the GNU General Public License can be found in /usr/share/common-licenses/GPL-2'. Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

1. Redistributions of source code must retain the above copyright notice, and the entire permission notice in its entirety, including the disclaimer of warranties.
2. Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the

documentation and/or other materials provided with the distribution.

3. The name of the author may not be used to endorse or promote products derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED ``AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, ALL OF WHICH ARE HEREBY DISCLAIMED. IN NO EVENT SHALL THE AUTHOR BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL

DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF NOT ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

This is the Debian GNU/Linux prepackaged version of the translation files of the EXT2 file system utilities. The EXT2 utilities were written by Theodore Ts'o <tytso@mit.edu> and Remy Card <card@masi.ibp.fr>.

Sources were obtained from <http://sourceforge.net/projects/e2fsprogs>

Packaging is Copyright (c) 2003-2006 Theodore Ts'o <tytso@mit.edu>

Copyright (c) 1997-2003 Yann Dirson <dirson@debian.org>

Copyright (c) 2001 Alcové <<http://www.alcove.com/>>

Copyright (c) 1997 Klee Dienes

Copyright (c) 1995-1996 Michael Nonweiler <mrn20@cam.ac.uk>

Upstream Author: Theodore Ts'o <tytso@mit.edu>

Copyright notice:

This package, the EXT2 filesystem utilities, is protected by the GNU General Public License.

Copyright (c) 1993, 1994, 1995, 1996, 1997, 1998, 1999, 2000, 2001, 2002, 2003, 2004, 2005, 2006, 2007, 2008 by Theodore Ts'o

On Debian GNU systems, the complete text of the GNU General Public License can be found in `~/usr/share/common-licenses/GPL-2`. This package was added to the e2fsprogs debian source package by Theodore Ts'o <tytso@mit.edu> on Fri Dec 14 22:24:35 EST 2007

It is part of the main e2fsprogs distribution, which can be found at:

<http://sourceforge.net/projects/e2fsprogs>

Upstream Author: Theodore Ts'o <tytso@mit.edu>

Copyright:

Copyright (C) 1999, 2000, 2001, 2002, 2003, 2004, 2005, 2006, 2007 by Theodore Ts'o

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

1. Redistributions of source code must retain the above copyright notice, and the entire permission notice in its entirety, including the disclaimer of warranties.
2. Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.
3. The name of the author may not be used to endorse or promote products derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED ``AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, ALL OF WHICH ARE HEREBY DISCLAIMED. IN NO EVENT SHALL THE AUTHOR BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF NOT ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

Index: tdbsa/tdb.c

=====

--- tdbsa.orig/tdb.c

+++ tdbsa/tdb.c

@@ -4,11 +4,11 @@ Rev: 23371

Last Changed Date: 2007-06-06 20:14:06 -0400 (Wed, 06 Jun 2007)

*/

/*

- Unix SMB/CIFS implementation.
- + trivial database library - standalone version

- trivial database library - private includes
-

- Copyright (C) Andrew Tridgell 2005
- + Copyright (C) Andrew Tridgell 1999-2005
- + Copyright (C) Jeremy Allison 2000-2006
- + Copyright (C) Paul 'Rusty' Russell 2000

** NOTE! The following LGPL license applies to the tdb
** library. This does NOT imply that all of Samba is released
EXT2ED is hereby placed under the terms of the GNU General Public License.
Follows the GNU license.

Gadi Oxman, August 1995

GNU GENERAL PUBLIC LICENSE

Version 2, June 1991

Copyright (C) 1989, 1991 Free Software Foundation, Inc.
675 Mass Ave, Cambridge, MA 02139, USA
Everyone is permitted to copy and distribute verbatim copies
of this license document, but changing it is not allowed.

Preamble

The licenses for most software are designed to take away your
freedom to share and change it. By contrast, the GNU General Public
License is intended to guarantee your freedom to share and change free
software--to make sure the software is free for all its users. This
General Public License applies to most of the Free Software
Foundation's software and to any other program whose authors commit to
using it. (Some other Free Software Foundation software is covered by
the
GNU Library General Public License instead.) You can apply it to
your programs, too.

When we speak of free software, we are referring to freedom, not
price. Our General Public Licenses are designed to make sure that you
have the freedom to distribute copies of free software (and charge for
this service if you wish), that you receive source code or can get it
if you want it, that you can change the software or use pieces of it
in new free programs; and that you know you can do these things.

To protect your rights, we need to make restrictions that forbid
anyone to deny you these rights or to ask you to surrender the rights.
These restrictions translate to certain responsibilities for you if you
distribute copies of the software, or if you modify it.

For example, if you distribute copies of such a program, whether

gratis or for a fee, you must give the recipients all the rights that you have. You must make sure that they, too, receive or can get the source code. And you must show them these terms so they know their rights.

We protect your rights with two steps: (1) copyright the software, and (2) offer you this license which gives you legal permission to copy, distribute and/or modify the software.

Also, for each author's protection and ours, we want to make certain that everyone understands that there is no warranty for this free software. If the software is modified by someone else and passed on, we want its recipients to know that what they have is not the original, so that any problems introduced by others will not reflect on the original authors' reputations.

Finally, any free program is threatened constantly by software patents. We wish to avoid the danger that redistributors of a free program will individually obtain patent licenses, in effect making the program proprietary. To prevent this, we have made it clear that any patent must be licensed for everyone's free use or not licensed at all.

The precise terms and conditions for copying, distribution and modification follow.

GNU GENERAL PUBLIC LICENSE TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

0. This License applies to any program or other work which contains a notice placed by the copyright holder saying it may be distributed under the terms of this General Public License. The "Program", below, refers to any such program or work, and a "work based on the Program" means either the Program or any derivative work under copyright law: that is to say, a work containing the Program or a portion of it, either verbatim or with modifications and/or translated into another language. (Hereinafter, translation is included without limitation in the term "modification".) Each licensee is addressed as "you".

Activities other than copying, distribution and modification are not covered by this License; they are outside its scope. The act of running the Program is not restricted, and the output from the Program is covered only if its contents constitute a work based on the Program (independent of having been made by running the Program). Whether that is true depends on what the Program does.

1. You may copy and distribute verbatim copies of the Program's source code as you receive it, in any medium, provided that you conspicuously and appropriately publish on each copy an appropriate copyright notice and disclaimer of warranty; keep intact all the notices that refer to this License and to the absence of any warranty; and give any other recipients of the Program a copy of this License along with the Program.

You may charge a fee for the physical act of transferring a copy, and you may at your option offer warranty protection in exchange for a fee.

2. You may modify your copy or copies of the Program or any portion of it, thus forming a work based on the Program, and copy and distribute such modifications or work under the terms of Section 1 above, provided that you also meet all of these conditions:

- a) You must cause the modified files to carry prominent notices stating that you changed the files and the date of any change.
- b) You must cause any work that you distribute or publish, that in whole or in part contains or is derived from the Program or any part thereof, to be licensed as a whole at no charge to all third parties under the terms of this License.
- c) If the modified program normally reads commands interactively when run, you must cause it, when started running for such interactive use in the most ordinary way, to print or display an announcement including an appropriate copyright notice and a notice that there is no warranty (or else, saying that you provide a warranty) and that users may redistribute the program under these conditions, and telling the user how to view a copy of this License. (Exception: if the Program itself is interactive but does not normally print such an announcement, your work based on the Program is not required to print an announcement.)

These requirements apply to the modified work as a whole. If identifiable sections of that work are not derived from the Program, and can be reasonably considered independent and separate works in themselves, then this License, and its terms, do not apply to those sections when you distribute them as separate works. But when you distribute the same sections as part of a whole which is a work based on the Program, the distribution of the whole must be on the terms of this License, whose permissions for other licensees extend to the entire whole, and thus to each and every part regardless of who wrote it.

Thus, it is not the intent of this section to claim rights or contest

your rights to work written entirely by you; rather, the intent is to exercise the right to control the distribution of derivative or collective works based on the Program.

In addition, mere aggregation of another work not based on the Program with the Program (or with a work based on the Program) on a volume of a storage or distribution medium does not bring the other work under the scope of this License.

3. You may copy and distribute the Program (or a work based on it, under Section 2) in object code or executable form under the terms of Sections 1 and 2 above provided that you also do one of the following:

a) Accompany it with the complete corresponding machine-readable source code, which must be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange; or,

b) Accompany it with a written offer, valid for at least three years, to give any third party, for a charge no more than your cost of physically performing source distribution, a complete machine-readable copy of the corresponding source code, to be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange; or,

c) Accompany it with the information you received as to the offer to distribute corresponding source code. (This alternative is allowed only for noncommercial distribution and only if you received the program in object code or executable form with such an offer, in accord with Subsection b above.)

The source code for a work means the preferred form of the work for making modifications to it. For an executable work, complete source code means all the source code for all modules it contains, plus any associated interface definition files, plus the scripts used to control compilation and installation of the executable. However, as a special exception, the source code distributed need not include anything that is normally distributed (in either source or binary form) with the major components (compiler, kernel, and so on) of the operating system on which the executable runs, unless that component itself accompanies the executable.

If distribution of executable or object code is made by offering access to copy from a designated place, then offering equivalent access to copy the source code from the same place counts as distribution of the source code, even though third parties are not

compelled to copy the source along with the object code.

4. You may not copy, modify, sublicense, or distribute the Program except as expressly provided under this License. Any attempt otherwise to copy, modify, sublicense or distribute the Program is void, and will automatically terminate your rights under this License. However, parties who have received copies, or rights, from you under this License will not have their licenses terminated so long as such parties remain in full compliance.

5. You are not required to accept this License, since you have not signed it. However, nothing else grants you permission to modify or distribute the Program or its derivative works. These actions are prohibited by law if you do not accept this License. Therefore, by modifying or distributing the Program (or any work based on the Program), you indicate your acceptance of this License to do so, and all its terms and conditions for copying, distributing or modifying the Program or works based on it.

6. Each time you redistribute the Program (or any work based on the Program), the recipient automatically receives a license from the original licensor to copy, distribute or modify the Program subject to these terms and conditions. You may not impose any further restrictions on the recipients' exercise of the rights granted herein. You are not responsible for enforcing compliance by third parties to this License.

7. If, as a consequence of a court judgment or allegation of patent infringement or for any other reason (not limited to patent issues), conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot distribute so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not distribute the Program at all. For example, if a patent license would not permit royalty-free redistribution of the Program by all those who receive copies directly or indirectly through you, then the only way you could satisfy both it and this License would be to refrain entirely from distribution of the Program.

If any portion of this section is held invalid or unenforceable under any particular circumstance, the balance of the section is intended to apply and the section as a whole is intended to apply in other circumstances.

It is not the purpose of this section to induce you to infringe any

patents or other property right claims or to contest validity of any such claims; this section has the sole purpose of protecting the integrity of the free software distribution system, which is implemented by public license practices. Many people have made generous contributions to the wide range of software distributed through that system in reliance on consistent application of that system; it is up to the author/donor to decide if he or she is willing to distribute software through any other system and a licensee cannot impose that choice.

This section is intended to make thoroughly clear what is believed to be a consequence of the rest of this License.

8. If the distribution and/or use of the Program is restricted in certain countries either by patents or by copyrighted interfaces, the original copyright holder who places the Program under this License may add an explicit geographical distribution limitation excluding those countries, so that distribution is permitted only in or among countries not thus excluded. In such case, this License incorporates the limitation as if written in the body of this License.

9. The Free Software Foundation may publish revised and/or new versions of the General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Program specifies a version number of this License which applies to it and "any later version", you have the option of following the terms and conditions either of that version or of any later version published by the Free Software Foundation. If the Program does not specify a version number of this License, you may choose any version ever published by the Free Software Foundation.

10. If you wish to incorporate parts of the Program into other free programs whose distribution conditions are different, write to the author to ask for permission. For software which is copyrighted by the Free Software Foundation, write to the Free Software Foundation; we sometimes make exceptions for this. Our decision will be guided by the two goals of preserving the free status of all derivatives of our free software and of promoting the sharing and reuse of software generally.

NO WARRANTY

11. BECAUSE THE PROGRAM IS LICENSED FREE OF CHARGE, THERE IS NO WARRANTY

FOR THE PROGRAM, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE PROGRAM "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE PROGRAM IS WITH YOU. SHOULD THE PROGRAM PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

12. IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY AND/OR REDISTRIBUTE THE PROGRAM AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY

TO USE THE PROGRAM (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE PROGRAM TO OPERATE WITH ANY OTHER PROGRAMS), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

END OF TERMS AND CONDITIONS

Appendix: How to Apply These Terms to Your New Programs

If you develop a new program, and you want it to be of the greatest possible use to the public, the best way to achieve this is to make it free software which everyone can redistribute and change under these terms.

To do so, attach the following notices to the program. It is safest to attach them to the start of each source file to most effectively convey the exclusion of warranty; and each file should have at least the "copyright" line and a pointer to where the full notice is found.

```
<one line to give the program's name and a brief idea of what it does.>  
Copyright (C) 19yy <name of author>
```

```
This program is free software; you can redistribute it and/or modify  
it under the terms of the GNU General Public License as published by  
the Free Software Foundation; either version 2 of the License, or  
(at your option) any later version.
```

```
This program is distributed in the hope that it will be useful,  
but WITHOUT ANY WARRANTY; without even the implied warranty of  
MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the  
GNU General Public License for more details.
```

```
You should have received a copy of the GNU General Public License  
along with this program; if not, write to the Free Software
```

Foundation, Inc., 675 Mass Ave, Cambridge, MA 02139, USA.

Also add information on how to contact you by electronic and paper mail.

If the program is interactive, make it output a short notice like this when it starts in an interactive mode:

```
Gnomovision version 69, Copyright (C) 19yy name of author
Gnomovision comes with ABSOLUTELY NO WARRANTY;
for details type `show w'.
This is free software, and you are welcome to redistribute it
under certain conditions; type `show c' for details.
```

The hypothetical commands `show w' and `show c' should show the appropriate parts of the General Public License. Of course, the commands you use may be called something other than `show w' and `show c'; they could even be mouse-clicks or menu items--whatever suits your program.

You should also get your employer (if you work as a programmer) or your school, if any, to sign a "copyright disclaimer" for the program, if necessary. Here is a sample; alter the names:

```
Yoyodyne, Inc., hereby disclaims all copyright interest in the program
`Gnomovision' (which makes passes at compilers) written by James Hacker.
```

```
<signature of Ty Coon>, 1 April 1989
Ty Coon, President of Vice
```

This General Public License does not permit incorporating your program into proprietary programs. If your program is a subroutine library, you may consider

it more useful to permit linking proprietary applications with the library. If this is what you want to do, use the GNU Library General Public License instead of this License.

This is the Debian GNU/Linux prepackaged version of the EXT2 file system utilities (e2fsck, mke2fs, etc.). The EXT2 utilities were written by Theodore Ts'o <tytso@mit.edu> and Remy Card <card@masi.ibp.fr>.

Sources were obtained from <http://sourceforge.net/projects/e2fsprogs>

Packaging is Copyright (c) 2003-2007 Theodore Ts'o <tytso@mit.edu>

Copyright (c) 1997-2003 Yann Dirson <dirson@debian.org>

Copyright (c) 2001 Alcove <<http://www.alcove.com/>>

Copyright (c) 1997 Klee Dienes

Copyright (c) 1995-1996 Michael Nonweiler <mrn20@cam.ac.uk>

Upstream Author: Theodore Ts'o <tytso@mit.edu>

Copyright notice:

This package, the EXT2 filesystem utilities, are made available under the GNU General Public License version 2, with the exception of the lib/ext2fs and lib/e2p libraries, which are made available under the GNU Library General Public License Version 2, the lib/uuid library which is made available under a BSD-style license and the lib/et and lib/ss libraries

which are made available under an MIT-style license.

Copyright (c) 1993, 1994, 1995, 1996, 1997, 1998, 1999, 2000, 2001, 2002, 2003, 2004, 2005, 2006, 2007, 2008 by Theodore Ts'o

On Debian GNU systems, the complete text of the GNU General Public License can be found in `~/usr/share/common-licenses/GPL-2`. The complete text of the GNU Library General Public License can be found in `~/usr/share/common-licenses/LGPL-2`.

The license used for lib/et and lib/ss libraries is:

Copyright 1987 by the Student Information Processing Board
of the Massachusetts Institute of Technology

Permission to use, copy, modify, and distribute this software and its documentation for any purpose is hereby granted, provided that the names of M.I.T. and the M.I.T. S.I.P.B. not be used in advertising or publicity pertaining to distribution of the software without specific, written prior permission. M.I.T. and the M.I.T. S.I.P.B. make no representations about the suitability of this software for any purpose. It is provided "as is" without express or implied warranty.

The license used for lib/uuid is:

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

1. Redistributions of source code must retain the above copyright notice, and the entire permission notice in its entirety, including the disclaimer of warranties.
2. Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.
3. The name of the author may not be used to endorse or promote products derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED ``AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, ALL OF WHICH ARE HEREBY DISCLAIMED. IN NO EVENT SHALL THE AUTHOR BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF NOT ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

This package was added to the e2fsprogs debian source package by Theodore Ts'o <tytso@mit.edu> on Sat Mar 15 15:33:37 EST 2003

It is part of the main e2fsprogs distribution, which can be found at:

<http://sourceforge.net/projects/e2fsprogs>

Upstream Author: Theodore Ts'o <tytso@mit.edu>

Copyright:

Copyright (C) 1999, 2000, 2003, 2004 by Theodore Ts'o

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

1. Redistributions of source code must retain the above copyright notice, and the entire permission notice in its entirety, including the disclaimer of warranties.
2. Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.
3. The name of the author may not be used to endorse or promote products derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED ``AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, ALL OF WHICH ARE HEREBY DISCLAIMED. IN NO EVENT SHALL THE AUTHOR BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR

BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF NOT ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

```
#
# This is a Makefile stub which handles the creation of BSD shared
# libraries.
#
# In order to use this stub, the following makefile variables must be defined.
#
# BSDLIB_VERSION = 1.0
# BSDLIB_IMAGE = libce
# BSDLIB_MYDIR = et
# BSDLIB_INSTALL_DIR = $(SHLIBDIR)
#
```

```
all:: image
```

```
real-subdirs:: Makefile
@echo " MKDIR pic"
@mkdir -p pic
```

```
BSD_LIB = $(BSDLIB_IMAGE).so.$(BSDLIB_VERSION)
BSDLIB_PIC_FLAG = -fpic
```

```
image: $(BSD_LIB)
```

```
$(BSD_LIB): $(OBJS)
(cd pic; ld -Bshareable -o $(BSD_LIB) $(LDFLAGS_SHLIB) $(OBJS))
$(MV) pic/$(BSD_LIB) .
$(RM) -f ../$(BSD_LIB)
(cd ..; $(LN) $(LINK_BUILD_FLAGS) \
`echo $(my_dir) | sed -e 's;lib/;;'"/$(BSD_LIB) $(BSD_LIB))
```

```
install-shlibs install:: $(BSD_LIB)
@echo " INSTALL_PROGRAM $(BSDLIB_INSTALL_DIR)/$(BSD_LIB)"
@$(INSTALL_PROGRAM) $(BSD_LIB) \
$(DESTDIR)$$(BSDLIB_INSTALL_DIR)/$(BSD_LIB)
@-$(LDCONFIG)
```

```
install-strip: install
```

```
install-shlibs-strip: install-shlibs
```

```
uninstall-shlibs uninstall::
$(RM) -f $(DESTDIR)$$(BSDLIB_INSTALL_DIR)/$(BSD_LIB)
```

```
clean::
$(RM)
-rf pic
$(RM) -f $(BSD_LIB)
$(RM) -f ../$(BSD_LIB)
```

This is the Debian GNU/Linux prepackaged version of the `ss` command-line interface parsing library. It is currently distributed together with the EXT2 file system utilities, which are otherwise packaged as "e2fsprogs".

This package was put together by Yann Dirson <dirson@debian.org>, from sources obtained from a mirror of:
tsx-11.mit.edu:/pub/linux/packages/ext2fs/

From the original distribution:

Copyright 1987, 1988 by the Student Information Processing Board of the Massachusetts Institute of Technology

Permission to use, copy, modify, and distribute this software and its documentation for any purpose and without fee is hereby granted, provided that the above copyright notice appear in all copies and that both that copyright notice and this permission notice appear in supporting documentation, and that the names of M.I.T. and the M.I.T. S.I.P.B. not be used in advertising or publicity pertaining to distribution of the software without specific, written prior permission.

M.I.T. and

the M.I.T. S.I.P.B. make no representations about the suitability of this software for any purpose. It is provided "as is" without express or implied warranty.

This package, the EXT2 filesystem utilities, are made available under the GNU Public License version 2, with the exception of the `lib/ext2fs` and `lib/e2p` libraries, which are made available under the GNU Library General Public License Version 2, the `lib/uuid` library which is made available under a BSD-style license and the `lib/et` and `lib/ss` libraries which are made available under an MIT-style license. Please see `lib/uuid/COPYING` for more details for the license for the files comprising the `libuuid` library, and the source file headers of the `libet` and `libss` libraries for more information.

The most recent officially distributed version can be found at <http://e2fsprogs.sourceforge.net>. If you need to make a distribution, that's the one you should use. If there is some reason why you'd like a more recent version that is still in ALPHA testing (i.e., either using the "WIP" test distributions or one from the `hg` or `git` repository from the development branch, please contact me (tytso@mit.edu)

before you ship. The release schedules for this package are flexible, if you give me enough lead time.

Theodore Ts'o
23-June-2007

GNU GENERAL PUBLIC LICENSE
Version 2, June 1991

Copyright (C) 1989, 1991 Free Software Foundation, Inc.
59 Temple Place, Suite 330, Boston, MA 02111-1307 USA
Everyone is permitted to copy and distribute verbatim copies of this license document, but changing it is not allowed.

Preamble

The licenses for most software are designed to take away your freedom to share and change it. By contrast, the GNU General Public License is intended to guarantee your freedom to share and change free software--to make sure the software is free for all its users. This General Public License applies to most of the Free Software Foundation's software and to any other program whose authors commit to using it. (Some other Free Software Foundation software is covered by the GNU Library General Public License instead.) You can apply it to your programs, too.

When we speak of free software, we are referring to freedom, not price. Our General Public Licenses are designed to make sure that you have the freedom to distribute copies of free software (and charge for this service if you wish), that you receive source code or can get it if you want it, that you can change the software or use pieces of it in new free programs; and that you know you can do these things.

To protect your rights, we need to make restrictions that forbid anyone to deny you these rights or to ask you to surrender the rights. These restrictions translate to certain responsibilities for you if you distribute copies of the software, or if you modify it.

For example, if you distribute copies of such a program, whether gratis or for a fee, you must give the recipients all the rights that you have. You must make sure that they, too, receive or can get the source code. And you must show them these terms so they know their rights.

We protect your rights with two steps: (1) copyright the software, and (2) offer you this license which gives you legal permission to copy, distribute and/or modify the software.

Also, for each author's protection and ours, we want to make certain that everyone understands that there is no warranty for this free software. If the software is modified by someone else and passed on, we want its recipients to know that what they have is not the original, so that any problems introduced by others will not reflect on the original authors' reputations.

Finally, any free program is threatened constantly by software patents. We wish to avoid the danger that redistributors of a free program will individually obtain patent licenses, in effect making the program proprietary. To prevent this, we have made it clear that any patent must be licensed for everyone's free use or not licensed at all.

The precise terms and conditions for copying, distribution and modification follow.

GNU GENERAL PUBLIC LICENSE TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

0. This License applies to any program or other work which contains a notice placed by the copyright holder saying it may be distributed under the terms of this General Public License. The "Program", below, refers to any such program or work, and a "work based on the Program" means either the Program or any derivative work under copyright law: that is to say, a work containing the Program or a portion of it, either verbatim or with modifications and/or translated into another language. (Hereinafter, translation is included without limitation in the term "modification".) Each licensee is addressed as "you".

Activities other than copying, distribution and modification are not covered by this License; they are outside its scope. The act of running the Program is not restricted, and the output from the Program is covered

only if its contents constitute a work based on the Program (independent of having been made by running the Program). Whether that is true depends on what the Program does.

1. You may copy and distribute verbatim copies of the Program's source code as you receive it, in any medium, provided that you conspicuously and appropriately publish on each copy an appropriate copyright notice and disclaimer of warranty; keep intact all the notices that refer to this License and to the absence of any warranty;

and give any other recipients of the Program a copy of this License along with the Program.

You may charge a fee for the physical act of transferring a copy, and you may at your option offer warranty protection in exchange for a fee.

2. You may modify your copy or copies of the Program or any portion of it, thus forming a work based on the Program, and copy and distribute such modifications or work under the terms of Section 1 above, provided that you also meet all of these conditions:

- a) You must cause the modified files to carry prominent notices stating that you changed the files and the date of any change.
- b) You must cause any work that you distribute or publish, that in whole or in part contains or is derived from the Program or any part thereof, to be licensed as a whole at no charge to all third parties under the terms of this License.
- c) If the modified program normally reads commands interactively when run, you must cause it, when started running for such interactive use in the most ordinary way, to print or display an announcement including an appropriate copyright notice and a notice that there is no warranty (or else, saying that you provide a warranty) and that users may redistribute the program under these conditions, and telling the user how to view a copy of this License. (Exception: if the Program itself is interactive but does not normally print such an announcement, your work based on the Program is not required to print an announcement.)

These requirements apply to the modified work as a whole. If identifiable sections of that work are not derived from the Program, and can be reasonably considered independent and separate works in themselves, then this License, and its terms, do not apply to those sections when you distribute them as separate works. But when you distribute the same sections as part of a whole which is a work based on the Program, the distribution of the whole must be on the terms of this License, whose permissions for other licensees extend to the entire whole, and thus to each and every part regardless of who wrote it.

Thus, it is not the intent of this section to claim rights or contest your rights to work written entirely by you; rather, the intent is to exercise the right to control the distribution of derivative or collective works based on the Program.

In addition, mere aggregation of another work not based on the Program with the

Program (or with a work based on the Program) on a volume of a storage or distribution medium does not bring the other work under the scope of this License.

3. You may copy and distribute the Program (or a work based on it, under Section 2) in object code or executable form under the terms of Sections 1 and 2 above provided that you also do one of the following:

a) Accompany it with the complete corresponding machine-readable source code, which must be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange; or,

b) Accompany it with a written offer, valid for at least three years, to give any third party, for a charge no more than your cost of physically performing source distribution, a complete machine-readable copy of the corresponding source code, to be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange; or,

c) Accompany it with the information you received as to the offer to distribute corresponding source code. (This alternative is allowed only for noncommercial distribution and only if you received the program in object code or executable form with such an offer, in accord with Subsection b above.)

The source code for a work means the preferred form of the work for making modifications to it. For an executable work, complete source code means all the source code for all modules it contains, plus any associated interface definition files, plus the scripts used to control compilation and installation of the executable. However, as a special exception, the source code distributed need not include anything that is normally distributed (in either source or binary form) with the major components (compiler, kernel, and so on) of the operating system on which the executable runs, unless that component itself accompanies the executable.

If distribution of executable or object code is made by offering access

to copy from a designated place, then offering equivalent access to copy the source code from the same place counts as distribution of the source code, even though third parties are not compelled to copy the source along with the object code.

4. You may not copy, modify, sublicense, or distribute the Program except as expressly provided under this License. Any attempt otherwise to copy, modify, sublicense or distribute the Program is void, and will automatically terminate your rights under this License.

However, parties who have received copies, or rights, from you under this License will not have their licenses terminated so long as such parties remain in full compliance.

5. You are not required to accept this License, since you have not signed it. However, nothing else grants you permission to modify or distribute the Program or its derivative works. These actions are prohibited by law if you do not accept this License. Therefore, by modifying or distributing the Program (or any work based on the Program), you indicate your acceptance of this License to do so, and all its terms and conditions for copying, distributing or modifying the Program or works based on it.

6. Each time you redistribute the Program (or any work based on the Program), the recipient automatically receives a license from the original licensor to copy, distribute or modify the Program subject to these terms and conditions. You may not impose any further restrictions on the recipients' exercise of the rights granted herein. You are not responsible for enforcing compliance by third parties to this License.

7. If, as a consequence of a court judgment or allegation of patent infringement or for any other reason (not limited to patent issues), conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot distribute so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not distribute the Program at all. For example, if a patent license would not permit royalty-free redistribution of the Program by all those who receive copies directly or indirectly through you, then the only way you could satisfy both it and this License would be to refrain entirely from distribution of the Program.

If any portion of this section is held invalid or unenforceable under any particular circumstance, the balance of the section is intended to apply and the section as a whole is intended to apply in other circumstances.

It is not the purpose of this section to induce you to infringe any patents or other property right claims or to contest validity of any such claims; this section has the sole purpose of protecting the integrity of the free software distribution system, which is implemented by public license practices. Many people have made generous contributions

to the wide range of software distributed through that system in reliance on consistent application of that system; it is up to the author/donor to decide if he or she is willing to distribute software through any other system and a licensee cannot impose that choice.

This section is intended to make thoroughly clear what is believed to be a consequence of the rest of this License.

8. If the distribution and/or use of the Program is restricted in certain countries either by patents or by copyrighted interfaces, the original copyright holder who places the Program under this License may add an explicit geographical distribution limitation excluding those countries, so that distribution is permitted only in or among countries not thus excluded. In such case, this License incorporates the limitation as if written in the body of this License.

9. The Free Software Foundation may publish revised and/or new versions of the General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Program specifies a version number of this License which applies to it and "any later version", you have the option of following the terms and conditions either of that version or of any later version published by the Free Software Foundation. If the Program does not specify a version number of this License, you may choose any version ever published by the Free Software Foundation.

10. If you wish to incorporate parts of the Program into other free programs whose distribution conditions are different, write to the author to ask for permission. For software which is copyrighted by the Free Software Foundation, write to the Free Software Foundation; we sometimes make exceptions for this. Our decision will be guided by the two goals of preserving the free status of all derivatives of our free software and of promoting the sharing and reuse of software generally.

NO WARRANTY

11. BECAUSE THE PROGRAM IS LICENSED FREE OF CHARGE, THERE IS NO WARRANTY FOR THE PROGRAM, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE PROGRAM "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS

TO THE QUALITY AND PERFORMANCE OF THE PROGRAM IS WITH YOU. SHOULD THE PROGRAM PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

12. IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY AND/OR REDISTRIBUTE THE PROGRAM AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE PROGRAM (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE PROGRAM TO OPERATE WITH ANY OTHER PROGRAMS), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Programs

If you develop a new program, and you want it to be of the greatest possible use to the public, the best way to achieve this is to make it free software which everyone can redistribute and change under these terms.

To do so, attach the following notices to the program. It is safest to attach them to the start of each source file to most effectively convey the exclusion of warranty; and each file should have at least the "copyright" line and a pointer to where the full notice is found.

```
<one line to give the program's name and a brief idea of what it does.>  
Copyright (C) <year> <name  
of author>
```

This program is free software; you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation; either version 2 of the License, or (at your option) any later version.

This program is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details.

You should have received a copy of the GNU General Public License along with this program; if not, write to the Free Software Foundation, Inc., 59 Temple Place, Suite 330, Boston, MA 02111-1307 USA

Also add information on how to contact you by electronic and paper mail.

If the program is interactive, make it output a short notice like this when it starts in an interactive mode:

```
Gnomovision version 69, Copyright (C) year name of author
Gnomovision comes
with ABSOLUTELY NO WARRANTY; for details type `show w'.
This is free software, and you are welcome to redistribute it
under certain conditions; type `show c' for details.
```

The hypothetical commands `show w' and `show c' should show the appropriate parts of the General Public License. Of course, the commands you use may be called something other than `show w' and `show c'; they could even be mouse-clicks or menu items--whatever suits your program.

You should also get your employer (if you work as a programmer) or your school, if any, to sign a "copyright disclaimer" for the program, if necessary. Here is a sample; alter the names:

```
Yoyodyne, Inc., hereby disclaims all copyright interest in the program
`Gnomovision' (which makes passes at compilers) written by James Hacker.
```

```
<signature of Ty Coon>, 1 April 1989
Ty Coon, President of Vice
```

This General Public License does not permit incorporating your program into proprietary programs. If your program is a subroutine library, you may consider it more useful to permit linking proprietary applications with the library. If this is what you want to do, use the GNU Library General Public License instead of this License.

GNU LIBRARY GENERAL PUBLIC LICENSE
Version 2, June 1991

Copyright (C) 1991 Free Software Foundation, Inc.
59 Temple Place, Suite 330, Boston, MA 02111-1307 USA
Everyone is permitted to copy and distribute verbatim copies
of this license document, but changing it is not allowed.

[This is the first released version of the library GPL. It is
numbered 2 because it goes with version 2 of the ordinary GPL.]

Preamble

The licenses for most software are designed to take away your

freedom to share and change it. By contrast, the GNU General Public Licenses are intended to guarantee your freedom to share and change free software--to make sure the software is free for all its users.

This license, the Library General Public License, applies to some specially designated Free Software Foundation software, and to any other libraries whose authors decide to use it. You can use it for your libraries, too.

When we speak of free software, we are referring to freedom, not price. Our General Public Licenses are designed to make sure that you have the freedom to distribute copies of free software (and charge for this service if you wish), that you receive source code or can get it if you want it, that you can change the software or use pieces of it in new free programs; and that you know you can do these things.

To protect your rights, we need to make restrictions that forbid anyone to deny you these rights or to ask you to surrender the rights. These restrictions translate to certain responsibilities for you if you distribute copies of the library, or if you modify it.

For example, if you distribute copies of the library, whether gratis or for a fee, you must give the recipients all the rights that we gave you. You must make sure that they, too, receive or can get the source code. If you link a program with the library, you must provide complete object files to the recipients so that they can relink them with the library, after making changes to the library and recompiling it. And you must show them these terms so they know their rights.

Our method of protecting your rights has two steps: (1) copyright the library, and (2) offer you this license which gives you legal permission to copy, distribute and/or modify the library.

Also, for each distributor's protection, we want to make certain that everyone understands that there is no warranty for this free library. If the library is modified by someone else and passed on, we want its recipients to know that what they have is not the original version, so that any problems introduced by others will not reflect on the original authors' reputations.

Finally, any free program is threatened constantly by software patents. We wish to avoid the danger that companies distributing free software will individually obtain patent licenses, thus in effect transforming the program into proprietary software. To prevent this, we have made it clear that any patent must be licensed for everyone's free use or not licensed at all.

Most GNU software, including some libraries, is covered by the ordinary GNU General Public License, which was designed for utility programs. This license, the GNU Library General Public License, applies to certain designated libraries. This license is quite different from the ordinary one; be sure to read it in full, and don't assume that anything in it is the same as in the ordinary license.

The reason we have a separate public license for some libraries is that they blur the distinction we usually make between modifying or adding to a program and simply using it. Linking a program with a library, without changing the library, is in some sense simply using the library, and is analogous to running a utility program or application program. However, in a textual and legal sense, the linked executable is a combined work, a derivative of the original library, and the ordinary General Public License treats it as such.

Because of this blurred distinction, using the ordinary General Public License for libraries did not effectively promote software sharing, because most developers did not use the libraries. We concluded that weaker conditions might promote sharing better.

However, unrestricted linking of non-free programs would deprive the users of those programs of all benefit from the free status of the libraries themselves. This Library General Public License is intended to permit developers of non-free programs to use free libraries, while preserving your freedom as a user of such programs to change the free libraries that are incorporated in them. (We have not seen how to achieve this as regards changes in header files, but we have achieved it as regards changes in the actual functions of the Library.) The hope is that this will lead to faster development of free libraries.

The precise terms and conditions for copying, distribution and modification follow. Pay close attention to the difference between a "work based on the library" and a "work that uses the library". The former contains code derived from the library, while the latter only works together with the library.

Note that it is possible for a library to be covered by the ordinary General Public License rather than by this special one.

GNU LIBRARY GENERAL PUBLIC LICENSE TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

0. This License Agreement applies to any software library which contains a notice placed by the copyright holder or other authorized

party saying it may be distributed under the terms of this Library General Public License (also called "this License"). Each licensee is addressed as "you".

A "library" means a collection of software functions and/or data prepared so as to be conveniently linked with application programs (which use some of those functions and data) to form executables.

The "Library", below, refers to any such software library or work which has been distributed under these terms. A "work based on the Library" means either the Library or any derivative work under copyright law: that is to say, a work containing the Library or a portion of it, either verbatim or with modifications and/or translated straightforwardly into another language. (Hereinafter, translation is included without limitation in the term "modification".)

"Source code" for a work means the preferred form of the work for making modifications to it. For a library, complete source code means all the source code for all modules it contains, plus any associated interface definition files, plus the scripts used to control compilation and installation of the library.

Activities other than copying, distribution and modification are not covered by this License; they are outside its scope. The act of running a program using the Library is not restricted, and output from such a program is covered only if its contents constitute a work based on the Library (independent of the use of the Library in a tool for writing it). Whether that is true depends on what the Library does and what the program that uses the Library does.

1. You may copy and distribute verbatim copies of the Library's complete source code as you receive it, in any medium, provided that you conspicuously and appropriately publish on each copy an appropriate copyright notice and disclaimer of warranty; keep intact all the notices that refer to this License and to the absence of any warranty; and distribute a copy of this License along with the Library.

You may charge a fee for the physical act of transferring a copy, and you may at your option offer warranty protection in exchange for a fee.

- 2.

You may modify your copy or copies of the Library or any portion of it, thus forming a work based on the Library, and copy and distribute such modifications or work under the terms of Section 1 above, provided that you also meet all of these conditions:

- a) The modified work must itself be a software library.
- b) You must cause the files modified to carry prominent notices stating that you changed the files and the date of any change.
- c) You must cause the whole of the work to be licensed at no charge to all third parties under the terms of this License.
- d) If a facility in the modified Library refers to a function or a table of data to be supplied by an application program that uses the facility, other than as an argument passed when the facility is invoked, then you must make a good faith effort to ensure that, in the event an application does not supply such function or table, the facility still operates, and performs whatever part of its purpose remains meaningful.

(For example, a function in a library to compute square roots has a purpose that is entirely well-defined independent of the application. Therefore, Subsection 2d requires that any application-supplied function or table used by this function must be optional: if the application does not supply it, the square root function must still compute square roots.)

These requirements apply to the modified work as a whole. If identifiable sections of that work are not derived from the Library, and can be reasonably considered independent and separate works in themselves, then this License, and its terms, do not apply to those sections when you distribute them as separate works. But when you distribute the same sections as part of a whole which is a work based on the Library, the distribution of the whole must be on the terms of this License, whose permissions for other licensees extend to the entire whole, and thus to each and every part regardless of who wrote it.

Thus, it is not the intent of this section to claim rights or contest your rights to work written entirely by you; rather, the intent is to exercise the right to control the distribution of derivative or collective works based on the Library.

In addition, mere aggregation of another work not based on the Library with the Library (or with a work based on the Library) on a volume of a storage or distribution medium does not bring the other work under the scope of this License.

3. You may opt to apply the terms of the ordinary GNU General Public License instead of this License to a given copy of the Library. To do

this, you must alter all the notices that refer to this License, so that they refer to the ordinary GNU General Public License, version 2, instead of to this License. (If a newer version than version 2 of the ordinary GNU General Public License has appeared, then you can specify that version instead if you wish.) Do not make any other change in these notices.

Once this change is made in a given copy, it is irreversible for that copy, so the ordinary GNU General Public License applies to all subsequent copies and derivative works made from that copy.

This option is useful when you wish to copy part of the code of the Library into a program that is not a library.

4. You may copy and distribute the Library (or a portion or derivative of it, under Section 2) in object code or executable form under the terms of Sections 1 and 2 above provided that you accompany it with the complete corresponding machine-readable source code, which must be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange.

If distribution of object code is made by offering access to copy from a designated place, then offering equivalent access to copy the source code from the same place satisfies the requirement to distribute the source code, even though third parties are not compelled to copy the source along with the object code.

5. A program that contains no derivative of any portion of the Library, but is designed to work with the Library by being compiled or linked with it, is called a "work that uses the Library". Such a work, in isolation, is not a derivative work of the Library, and therefore falls outside the scope of this License.

However, linking a "work that uses the Library" with the Library creates an executable that is a derivative of the Library (because it contains portions of the Library), rather than a "work that uses the library". The executable is therefore covered by this License. Section 6 states terms for distribution of such executables.

When a "work that uses the Library" uses material from a header file that is part of the Library, the object code for the work may be a derivative work of the Library even though the source code is not. Whether this is true is especially significant if the work can be linked without the Library, or if the work is itself a library. The threshold for this to be true is not precisely defined by law.

If such an object file uses only numerical parameters, data structure layouts and accessors, and small macros and small inline functions (ten lines or less in length), then the use of the object file is unrestricted, regardless of whether it is legally a derivative work. (Executables containing this object code plus portions of the Library will still fall under Section 6.)

Otherwise, if the work is a derivative of the Library, you may distribute the object code for the work under the terms of Section 6. Any executables containing that work also fall under Section 6, whether or not they are linked directly with the Library itself.

6. As an exception to the Sections above, you may also compile or link a "work that uses the Library" with the Library to produce a work containing portions of the Library, and distribute that work under terms of your choice, provided that the terms permit modification of the work for the customer's own use and reverse engineering for debugging such modifications.

You must give prominent notice with each copy of the work that the Library is used in it and that the Library and its use are covered by this License. You must supply a copy of this License. If the work during execution displays copyright notices, you must include the copyright notice for the Library among them, as well as a reference directing the user to the copy of this License. Also, you must do one of these things:

a) Accompany the work with the complete corresponding machine-readable source code for the Library including whatever changes were used in the work (which must be distributed under Sections 1 and 2 above); and, if the work is an executable linked with the Library, with the complete machine-readable "work that uses the Library", as object code and/or source code, so that the user can modify the Library and then relink to produce a modified executable containing the modified Library. (It is understood that the user who changes the contents of definitions files in the Library will not necessarily be able to recompile the application to use the modified definitions.)

b) Accompany the work with a written offer, valid for at least three years, to give the same user the materials specified in Subsection 6a, above, for a charge no more than the cost of performing this distribution.

c) If distribution of the work is made by offering access to copy

from a designated place, offer equivalent access to copy the above specified materials from the same place.

d) Verify that the user has already received a copy of these materials or that you have already sent this user a copy.

For an executable, the required form of the "work that uses the Library" must include any data and utility programs needed for reproducing the executable from it. However, as a special exception, the

source code distributed need not include anything that is normally distributed (in either source or binary form) with the major components (compiler, kernel, and so on) of the operating system on which the executable runs, unless that component itself accompanies the executable.

It may happen that this requirement contradicts the license restrictions of other proprietary libraries that do not normally accompany the operating system. Such a contradiction means you cannot use both them and the Library together in an executable that you distribute.

7. You may place library facilities that are a work based on the Library side-by-side in a single library together with other library facilities not covered by this License, and distribute such a combined library, provided that the separate distribution of the work based on the Library and of the other library facilities is otherwise permitted, and provided that you do these two things:

a) Accompany the combined library

with a copy of the same work

based on the Library, uncombined with any other library facilities. This must be distributed under the terms of the Sections above.

b) Give prominent notice with the combined library of the fact that part of it is a work based on the Library, and explaining where to find the accompanying uncombined form of the same work.

8. You may not copy, modify, sublicense, link with, or distribute the Library except as expressly provided under this License. Any attempt otherwise to copy, modify, sublicense, link with, or distribute the Library is void, and will automatically terminate your rights under this License. However, parties who have received copies, or rights, from you under this License will not have their licenses terminated so long as such parties remain in full compliance.

9. You are not required to accept this License, since you have not

signed it. However, nothing else grants you permission to modify or distribute the

Library or its derivative works. These actions are prohibited by law if you do not accept this License. Therefore, by modifying or distributing the Library (or any work based on the Library), you indicate your acceptance of this License to do so, and all its terms and conditions for copying, distributing or modifying the Library or works based on it.

10. Each time you redistribute the Library (or any work based on the Library), the recipient automatically receives a license from the original licensor to copy, distribute, link with or modify the Library subject to these terms and conditions. You may not impose any further restrictions on the recipients' exercise of the rights granted herein. You are not responsible for enforcing compliance by third parties to this License.

11. If, as a consequence of a court judgment or allegation of patent infringement or for any other reason (not limited to patent issues), conditions are imposed on you (whether by court order, agreement or otherwise)

that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot distribute so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not distribute the Library at all. For example, if a patent license would not permit royalty-free redistribution of the Library by all those who receive copies directly or indirectly through you, then the only way you could satisfy both it and this License would be to refrain entirely from distribution of the Library.

If any portion of this section is held invalid or unenforceable under any particular circumstance, the balance of the section is intended to apply, and the section as a whole is intended to apply in other circumstances.

It is not the purpose of this section to induce you to infringe any patents or other property right claims or to contest validity of any such claims; this section has the sole purpose of protecting the integrity of the free software distribution system which is implemented by public license practices. Many people have made generous contributions to the wide range of software distributed through that system in reliance on consistent application of that system; it is up to the author/donor to decide if he or she is willing to distribute software through any other system and a licensee cannot impose that choice.

This section is intended to make thoroughly clear what is believed to

be a consequence of the rest of this License.

12. If the distribution and/or use of the Library is restricted in certain countries either by patents or by copyrighted interfaces, the original copyright holder who places the Library under this License may add an explicit geographical distribution limitation excluding those countries, so that distribution is permitted only in or among countries not thus excluded. In such case, this License incorporates the limitation as if written in the body of this License.

13. The Free Software Foundation may publish revised and/or new versions of the Library General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Library specifies a version number of this License which applies to it and "any later version", you have the option of following the terms and conditions either of that version or of any later version published by the Free Software Foundation. If the Library does not specify a license version number, you may choose any version ever published by the Free Software Foundation.

14. If you wish to incorporate parts of the Library into other free programs whose distribution conditions are incompatible with these, write to the author to ask for permission. For software which is copyrighted by the Free Software Foundation, write to the Free Software Foundation; we sometimes make exceptions for this. Our decision will be guided by the two goals of preserving the free status of all derivatives of our free software and of promoting the sharing and reuse of software generally.

NO WARRANTY

15. BECAUSE THE LIBRARY IS LICENSED FREE OF CHARGE, THERE IS NO WARRANTY FOR THE LIBRARY, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE LIBRARY "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE LIBRARY IS WITH YOU. SHOULD THE LIBRARY PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

16. IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY

AND/OR

REDISTRIBUTE THE LIBRARY AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE LIBRARY (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE LIBRARY TO OPERATE WITH ANY OTHER SOFTWARE), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Libraries

If you develop a new library, and you want it to be of the greatest possible use to the public, we recommend making it free software that everyone can redistribute and change. You can do so by permitting redistribution under these terms (or, alternatively, under the terms of the ordinary General Public License).

To apply these terms, attach the following notices to the library. It is safest to attach them to the start of each source file to most effectively convey the exclusion of warranty; and each file should have at least the "copyright" line and a pointer to where the full notice is found.

<one line to give the library's name and a brief idea of what it does.>
Copyright (C) <year> <name of author>

This library is free software; you can redistribute it and/or modify it under the terms of the GNU Library General Public License as published by the Free Software Foundation; either version 2 of the License, or (at your option) any later version.

This library is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU Library General Public License for more details.

You should have received a copy of the GNU Library General Public License along with this library; if not, write to the Free Software Foundation, Inc., 59 Temple Place, Suite 330, Boston, MA 02111-1307 USA

Also add information on how to contact you by electronic and paper mail.

You should also get your employer (if you work as a programmer) or your school, if any, to sign a "copyright disclaimer" for the library, if

necessary. Here is a sample; alter the names:

Yoyodyne, Inc., hereby disclaims all copyright interest in the library `Frob' (a library for tweaking knobs) written by James Random Hacker.

<signature of Ty Coon>, 1 April 1990

Ty Coon, President of Vice

That's all there is to it!

This is the Debian GNU/Linux prepackaged version of the Common Error Description library. It is currently distributed together with the EXT2 file system utilities, which are otherwise packaged as "e2fsprogs".

This package was put together by Yann Dirson <dirson@debian.org>, from sources obtained from a mirror of:
tsx-11.mit.edu:/pub/linux/packages/ext2fs/

From the original distribution:

Copyright 1987, 1988 by the Student Information Processing Board of the Massachusetts Institute of Technology

Permission to use, copy, modify, and distribute this software and its documentation for any purpose and without fee is hereby granted, provided that the above copyright notice appear in all copies and that both that copyright notice and this permission notice appear in supporting documentation, and that the names of M.I.T. and the M.I.T. S.I.P.B. not be used in advertising or publicity pertaining to distribution of the software without specific, written prior permission. M.I.T. and the M.I.T.

S.I.P.B. make no representations about the suitability of this software for any purpose. It is provided "as is" without express or implied warranty.

1.78 libcom-err 1.44.1-1ubuntu1.4

1.78.1 Available under license :

This package was added to the e2fsprogs debian source package by Theodore Ts'o <tytso@mit.edu> on Sat Mar 15 15:33:37 EST 2003

It is part of the main e2fsprogs distribution, which can be found at:

<http://sourceforge.net/projects/e2fsprogs>

Upstream Author: Theodore Ts'o <tytso@mit.edu>

Copyright:

Copyright (C) 1999, 2001 by Andries Brouwer

Copyright (C) 1999, 2000, 2003 by Theodore Ts'o

You are free to distribute this software under the terms of the GNU Lesser (Library) General Public License.

On Debian systems, the complete text of the GNU Lesser (Library) General Public License can be found in /usr/share/common-licenses/LGPL-2. This is the Debian GNU/Linux prepackaged version of the static EXT2 file system consistency checker (e2fsck.static). The EXT2 utilities were written by Theodore Ts'o <tytso@mit.edu> and Remy Card <card@masi.ibp.fr>.

Sources were obtained from <http://sourceforge.net/projects/e2fsprogs>

Packaging is Copyright (c) 2003-2006 Theodore Ts'o <tytso@mit.edu>

Copyright (c) 1997-2003 Yann Dirson <dirson@debian.org>

Copyright (c) 2001 Alcove <<http://www.alcove.com/>>

Copyright (c) 1997 Klee Dienes

Copyright (c) 1995-1996 Michael Nonweiler <mrn20@cam.ac.uk>

Upstream Author: Theodore Ts'o <tytso@mit.edu>

Copyright notice:

This package, the EXT2 filesystem utilities, is protected by the GNU General Public License.

Copyright (c) 1993, 1994, 1995, 1996, 1997, 1998, 1999, 2000, 2001, 2002, 2003, 2004, 2005, 2006, 2007, 2008 by Theodore Ts'o

On Debian GNU systems, the complete text of the GNU General Public License can be found in `~/usr/share/common-licenses/GPL-2`. Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

1. Redistributions of source code must retain the above copyright notice, and the entire permission notice in its entirety, including the disclaimer of warranties.
2. Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.
3. The name of the author may not be used to endorse or promote products derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED ``AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, ALL OF WHICH ARE HEREBY DISCLAIMED. IN NO EVENT SHALL THE AUTHOR BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL

DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF NOT ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

This is the Debian GNU/Linux prepackaged version of the translation files of the EXT2 file system utilities. The EXT2 utilities were written by Theodore Ts'o <tytso@mit.edu> and Remy Card <card@masi.ibp.fr>.

Sources were obtained from <http://sourceforge.net/projects/e2fsprogs>

Packaging is Copyright (c) 2003-2006 Theodore Ts'o <tytso@mit.edu>
Copyright (c) 1997-2003 Yann Dirson <dirson@debian.org>
Copyright (c) 2001 Alcove <<http://www.alcove.com/>>
Copyright (c) 1997 Klee Dienes
Copyright (c) 1995-1996 Michael Nonweiler <mrn20@cam.ac.uk>

Upstream Author: Theodore Ts'o <tytso@mit.edu>

Copyright notice:

This package, the EXT2 filesystem utilities, is protected by the GNU General Public License.

Copyright (c) 1993, 1994, 1995, 1996, 1997, 1998, 1999, 2000, 2001, 2002, 2003, 2004, 2005, 2006, 2007, 2008 by Theodore Ts'o

On Debian GNU systems, the complete text of the GNU General Public License can be found in ``usr/share/common-licenses/GPL-2'`. This package was added to the e2fsprogs debian source package by Theodore Ts'o <tytso@mit.edu> on Fri Dec 14 22:24:35 EST 2007

It is part of the main e2fsprogs distribution, which can be found at:

<http://sourceforge.net/projects/e2fsprogs>

Upstream Author: Theodore Ts'o <tytso@mit.edu>

Copyright:

Copyright (C) 1999, 2000, 2001, 2002, 2003, 2004, 2005, 2006, 2007 by
Theodore Ts'o

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions
are met:

1. Redistributions of source code must retain the above copyright
notice, and the entire permission notice in its entirety,
including the disclaimer of warranties.
2. Redistributions in binary form must reproduce the above copyright
notice, this list of conditions and the following disclaimer in the
documentation and/or other materials provided with the distribution.
3. The name of the author may not be used to endorse or promote
products derived from
this software without specific prior
written permission.

THIS SOFTWARE IS PROVIDED ``AS IS" AND ANY EXPRESS OR IMPLIED
WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES
OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, ALL OF
WHICH ARE HEREBY DISCLAIMED. IN NO EVENT SHALL THE AUTHOR BE
LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR
CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT
OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR
BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF
LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT
(INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE
USE OF THIS SOFTWARE, EVEN IF NOT ADVISED OF THE POSSIBILITY OF SUCH
DAMAGE.

Index: tdbsa/tdb.c

=====
--- tdbsa.orig/tdb.c

+++ tdbsa/tdb.c

@@ -4,11 +4,11 @@ Rev: 23371

Last Changed Date: 2007-06-06 20:14:06 -0400 (Wed, 06 Jun 2007)

*/

/*

- Unix SMB/CIFS implementation.
- + trivial database library - standalone version

- trivial database library - private includes
-
- Copyright (C) Andrew Tridgell 2005
- + Copyright (C) Andrew Tridgell 1999-2005
- + Copyright (C) Jeremy Allison 2000-2006
- + Copyright (C) Paul `Rusty' Russell 2000

** NOTE! The following LGPL license applies to the tdb
** library. This does NOT imply that all of Samba is released
EXT2ED is hereby placed under the terms of the GNU General Public License.
Follows the GNU license.

Gadi Oxman, August 1995

GNU GENERAL PUBLIC LICENSE

Version 2, June 1991

Copyright (C) 1989, 1991 Free Software Foundation, Inc.

675 Mass Ave, Cambridge, MA 02139, USA

Everyone is permitted to copy and distribute verbatim copies
of this license document, but changing it is not allowed.

Preamble

The licenses for most software are designed to take away your
freedom to share and change it. By contrast, the GNU General Public
License is intended to guarantee your freedom to share and change free
software--to make sure the software is free for all its users. This
General Public License applies to most of the Free Software
Foundation's software and to any other program whose authors commit to
using it. (Some other Free Software Foundation software is covered by
the
GNU Library General Public License instead.) You can apply it to
your programs, too.

When we speak of free software, we are referring to freedom, not
price. Our General Public Licenses are designed to make sure that you
have the freedom to distribute copies of free software (and charge for
this service if you wish), that you receive source code or can get it
if you want it, that you can change the software or use pieces of it
in new free programs; and that you know you can do these things.

To protect your rights, we need to make restrictions that forbid
anyone to deny you these rights or to ask you to surrender the rights.
These restrictions translate to certain responsibilities for you if you
distribute copies of the software, or if you modify it.

For example, if you distribute copies of such a program, whether
gratis or for a fee, you must give the recipients all the rights that
you have. You must make sure that they, too, receive or can get the
source code. And you
must show them these terms so they know their
rights.

We protect your rights with two steps: (1) copyright the software, and (2) offer you this license which gives you legal permission to copy, distribute and/or modify the software.

Also, for each author's protection and ours, we want to make certain that everyone understands that there is no warranty for this free software. If the software is modified by someone else and passed on, we want its recipients to know that what they have is not the original, so that any problems introduced by others will not reflect on the original authors' reputations.

Finally, any free program is threatened constantly by software patents. We wish to avoid the danger that redistributors of a free program will individually obtain patent licenses, in effect making the program proprietary. To prevent this, we have made it clear that any patent must be licensed for everyone's free use or not licensed at all.

The precise terms and conditions for copying, distribution and modification follow.

GNU GENERAL PUBLIC LICENSE TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

0. This License applies to any program or other work which contains a notice placed by the copyright holder saying it may be distributed under the terms of this General Public License. The "Program", below, refers to any such program or work, and a "work based on the Program" means either the Program or any derivative work under copyright law: that is to say, a work containing the Program or a portion of it, either verbatim or with modifications and/or translated into another language. (Hereinafter, translation is included without limitation in the term "modification".) Each licensee is addressed as "you".

Activities other than copying, distribution and modification are not covered by this License; they are outside its scope. The act of running the Program is not restricted, and the output from the Program is covered only if its contents constitute a work based on the Program (independent of having been made by running the Program). Whether that is true depends on what the Program does.

1. You may copy and distribute verbatim copies of the Program's source code as you receive it, in any medium, provided that you conspicuously and appropriately publish on each copy an appropriate copyright notice and disclaimer of warranty; keep intact all the notices that refer to this License and to the absence of any warranty;

and give any other recipients of the Program a copy of this License along with the Program.

You may charge a fee for the physical act of transferring a copy, and you may at your option offer warranty protection in exchange for a fee.

2. You may modify your copy or copies of the Program or any portion of it, thus forming a work based on the Program, and copy and distribute such modifications or work under the terms of Section 1 above, provided that you also meet all of these conditions:

- a) You must cause the modified files to carry prominent notices stating that you changed the files and the date of any change.
- b) You must cause any work that you distribute or publish, that in whole or in part contains or is derived from the Program or any part thereof, to be licensed as a whole at no charge to all third parties under the terms of this License.
- c) If the modified program normally reads commands interactively when run, you must cause it, when started running for such interactive use in the most ordinary way, to print or display an announcement including an appropriate copyright notice and a notice that there is no warranty (or else, saying that you provide a warranty) and that users may redistribute the program under these conditions, and telling the user how to view a copy of this License. (Exception: if the Program itself is interactive but does not normally print such an announcement, your work based on the Program is not required to print an announcement.)

These requirements apply to the modified work as a whole. If identifiable sections of that work are not derived from the Program, and can be reasonably considered independent and separate works in themselves, then this License, and its terms, do not apply to those sections when you distribute them as separate works. But when you distribute the same sections as part of a whole which is a work based on the Program, the distribution of the whole must be on the terms of this License, whose permissions for other licensees extend to the entire whole, and thus to each and every part regardless of who wrote it.

Thus, it is not the intent of this section to claim rights or contest your rights to work written entirely by you; rather, the intent is to exercise the right to control the distribution of derivative or collective works based on the Program.

In addition, mere aggregation of another work not based on the Program

with the Program (or with a work based on the Program) on a volume of a storage or distribution medium does not bring the other work under the scope of this License.

3. You may copy and distribute the Program (or a work based on it, under Section 2) in object code or executable form under the terms of Sections 1 and 2 above provided that you also do one of the following:

a) Accompany it with the complete corresponding machine-readable source code, which must be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange; or,

b) Accompany it with a written offer, valid for at least three years, to give any third party, for a charge no more than your cost of physically performing source distribution, a complete machine-readable copy of the corresponding source code, to be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange; or,

c) Accompany it with the information you received as to the offer to distribute corresponding source code. (This alternative is allowed only for noncommercial distribution and only if you received the program in object code or executable form with such an offer, in accord with Subsection b above.)

The source code for a work means the preferred form of the work for making modifications to it. For an executable work, complete source code means all the source code for all modules it contains, plus any associated interface definition files, plus the scripts used to control compilation and installation of the executable. However, as a special exception, the source code distributed need not include anything that is normally distributed (in either source or binary form) with the major components (compiler, kernel, and so on) of the operating system on which the executable runs, unless that component itself accompanies the executable.

If distribution of executable or object code is made by offering access

to copy from a designated place, then offering equivalent access to copy the source code from the same place counts as distribution of the source code, even though third parties are not compelled to copy the source along with the object code.

4. You may not copy, modify, sublicense, or distribute the Program except as expressly provided under this License. Any attempt otherwise to copy, modify, sublicense or distribute the Program is

void, and will automatically terminate your rights under this License. However, parties who have received copies, or rights, from you under this License will not have their licenses terminated so long as such parties remain in full compliance.

5. You are not required to accept this License, since you have not signed it. However, nothing else grants you permission to modify or distribute the Program or its derivative works. These actions are prohibited by law if you do not accept this License. Therefore, by modifying or distributing the Program (or any work based on the Program), you indicate your acceptance of this License to do so, and all its terms and conditions for copying, distributing or modifying the Program or works based on it.

6. Each time you redistribute the Program (or any work based on the Program), the recipient automatically receives a license from the original licensor to copy, distribute or modify the Program subject to these terms and conditions. You may not impose any further restrictions on the recipients' exercise of the rights granted herein. You are not responsible for enforcing compliance by third parties to this License.

7. If, as a consequence of a court judgment or allegation of patent infringement or for any other reason (not limited to patent issues), conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot distribute so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not distribute the Program at all. For example, if a patent license would not permit royalty-free redistribution of the Program by all those who receive copies directly or indirectly through you, then the only way you could satisfy both it and this License would be to refrain entirely from distribution of the Program.

If any portion of this section is held invalid or unenforceable under any particular circumstance, the balance of the section is intended to apply and the section as a whole is intended to apply in other circumstances.

It is not the purpose of this section to induce you to infringe any patents or other property right claims or to contest validity of any such claims; this section has the sole purpose of protecting the integrity of the free software distribution system, which is implemented by public license practices. Many people have made generous contributions to

the wide range of software distributed through that system in reliance on consistent application of that system; it is up to the author/donor to decide if he or she is willing to distribute software through any other system and a licensee cannot impose that choice.

This section is intended to make thoroughly clear what is believed to be a consequence of the rest of this License.

8. If the distribution and/or use of the Program is restricted in certain countries either by patents or by copyrighted interfaces, the original copyright holder who places the Program under this License may add an explicit geographical distribution limitation excluding those countries, so that distribution is permitted only in or among countries not thus excluded. In such case, this License incorporates the limitation as if written in the body of this License.

9. The Free Software Foundation may publish revised and/or new versions of the General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Program specifies a version number of this License which applies to it and "any later version", you have the option of following the terms and conditions either of that version or of any later version published by the Free Software Foundation. If the Program does not specify a version number of this License, you may choose any version ever published by the Free Software Foundation.

10. If you wish to incorporate parts of the Program into other free programs whose distribution conditions are different, write to the author to ask for permission. For software which is copyrighted by the Free Software Foundation, write to the Free Software Foundation; we sometimes make exceptions for this. Our decision will be guided by the two goals of preserving the free status of all derivatives of our free software and of promoting the sharing and reuse of software generally.

NO WARRANTY

11. BECAUSE THE PROGRAM IS LICENSED FREE OF CHARGE, THERE IS NO WARRANTY FOR THE PROGRAM, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE PROGRAM "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS

TO THE QUALITY AND PERFORMANCE OF THE PROGRAM IS WITH YOU. SHOULD THE PROGRAM PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

12. IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY AND/OR REDISTRIBUTE THE PROGRAM AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE PROGRAM (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE PROGRAM TO OPERATE WITH ANY OTHER PROGRAMS), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

END OF TERMS AND CONDITIONS

Appendix: How to Apply These Terms to Your New Programs

If you develop a new program, and you want it to be of the greatest possible use to the public, the best way to achieve this is to make it free software which everyone can redistribute and change under these terms.

To do so, attach the following notices to the program. It is safest to attach them to the start of each source file to most effectively convey the exclusion of warranty; and each file should have at least the "copyright" line and a pointer to where the full notice is found.

```
<one line to give the program's name and a brief idea of what it does.>  
Copyright (C) 19yy <name of author>
```

This program is free software; you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation; either version 2 of the License, or (at your option) any later version.

This program is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details.

You should have received a copy of the GNU General Public License along with this program; if not, write to the Free Software Foundation, Inc., 675 Mass Ave, Cambridge, MA 02139, USA.

Also add information on how to contact you by electronic and paper mail.

If the program is interactive, make it output a short notice like this

when it starts in an interactive mode:

Gnomovision version 69, Copyright (C) 19yy name of author
Gnomovision comes with ABSOLUTELY NO WARRANTY;
for details type `show w'.

This is free software, and you are welcome to redistribute it
under certain conditions; type `show c' for details.

The hypothetical commands `show w' and `show c' should show the appropriate parts of the General Public License. Of course, the commands you use may be called something other than `show w' and `show c'; they could even be mouse-clicks or menu items--whatever suits your program.

You should also get your employer (if you work as a programmer) or your school, if any, to sign a "copyright disclaimer" for the program, if necessary. Here is a sample; alter the names:

Yoyodyne, Inc., hereby disclaims all copyright interest in the program
`Gnomovision' (which makes passes at compilers) written by James Hacker.

<signature of Ty Coon>, 1 April 1989
Ty Coon, President of Vice

This General Public License does not permit incorporating your program into proprietary programs. If your program is a subroutine library, you may consider

it more useful to permit linking proprietary applications with the library. If this is what you want to do, use the GNU Library General Public License instead of this License.

This is the Debian GNU/Linux prepackaged version of the EXT2 file system utilities (e2fsck, mke2fs, etc.). The EXT2 utilities were written by Theodore Ts'o <tytso@mit.edu> and Remy Card <card@masi.ibp.fr>.

Sources were obtained from <http://sourceforge.net/projects/e2fsprogs>

Packaging is Copyright (c) 2003-2007 Theodore Ts'o <tytso@mit.edu>

Copyright (c) 1997-2003 Yann Dirson <dirson@debian.org>

Copyright (c) 2001 Alcove <<http://www.alcove.com/>>

Copyright (c) 1997 Klee Dienes

Copyright (c) 1995-1996 Michael Nonweiler <mrn20@cam.ac.uk>

Upstream Author: Theodore Ts'o <tytso@mit.edu>

Copyright notice:

This package, the EXT2 filesystem utilities, are made available under the GNU General Public License version 2, with the exception of the lib/ext2fs and lib/e2p libraries, which are made available under the

GNU Library General Public License Version 2, the lib/uuid library which is made available under a BSD-style license and the lib/et and lib/ss libraries which are made available under an MIT-style license.

Copyright (c) 1993, 1994, 1995, 1996, 1997, 1998, 1999, 2000, 2001, 2002, 2003, 2004, 2005, 2006, 2007, 2008 by Theodore Ts'o

On Debian GNU systems, the complete text of the GNU General Public License can be found in `/usr/share/common-licenses/GPL-2`. The complete text of the GNU Library General Public License can be found in `/usr/share/common-licenses/LGPL-2`.

The license used for lib/et and lib/ss libraries is:

Copyright 1987 by the Student Information Processing Board of the Massachusetts Institute of Technology

Permission to use, copy, modify, and distribute this software and its documentation for any purpose is hereby granted, provided that the names of M.I.T. and the M.I.T. S.I.P.B. not be used in advertising or publicity pertaining to distribution of the software without specific, written prior permission. M.I.T. and the M.I.T. S.I.P.B. make no representations about the suitability of this software for any purpose. It is provided "as is" without express or implied warranty.

The license used for lib/uuid is:

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

1. Redistributions of source code must retain the above copyright notice, and the entire permission notice in its entirety, including the disclaimer of warranties.
2. Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.
3. The name of the author may not be used to endorse or promote products derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND

FITNESS FOR A PARTICULAR PURPOSE, ALL OF WHICH ARE HEREBY DISCLAIMED. IN NO EVENT SHALL THE AUTHOR BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF NOT ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

This package was added to the e2fsprogs debian source package by Theodore Ts'o <tytso@mit.edu> on Sat Mar 15 15:33:37 EST 2003

It is part of the main e2fsprogs distribution, which can be found at:

<http://sourceforge.net/projects/e2fsprogs>

Upstream Author: Theodore Ts'o <tytso@mit.edu>

Copyright:

Copyright (C) 1999, 2000, 2003, 2004 by Theodore Ts'o

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

1. Redistributions of source code must retain the above copyright notice, and the entire permission notice in its entirety, including the disclaimer of warranties.
2. Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.
3. The name of the author may not be used to endorse or promote products derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED ``AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, ALL OF WHICH ARE HEREBY DISCLAIMED. IN NO EVENT SHALL THE AUTHOR BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF NOT ADVISED OF THE POSSIBILITY OF SUCH

```

DAMAGE.
#
# This is a Makefile stub which handles the creation of BSD shared
# libraries.
#
# In order to use this stub, the following makefile variables must be defined.
#
# BSDLIB_VERSION = 1.0
# BSDLIB_IMAGE = libce
# BSDLIB_MYDIR = et
# BSDLIB_INSTALL_DIR = $(SHLIBDIR)
#

all:: image

real-subdirs:: Makefile
@echo " MKDIR pic"
@mkdir -p pic

BSD_LIB = $(BSDLIB_IMAGE).so.$(BSDLIB_VERSION)
BSDLIB_PIC_FLAG = -fpic

image: $(BSD_LIB)

$(BSD_LIB): $(OBJS)
(cd pic; ld -Bshareable -o $(BSD_LIB) $(LDFLAGS_SHLIB) $(OBJS))
$(MV) pic/$(BSD_LIB) .
$(RM) -f ../$(BSD_LIB)
(cd ..; $(LN) $(LINK_BUILD_FLAGS) \
`echo $(my_dir) | sed -e 's;lib/;;'"/$(BSD_LIB) $(BSD_LIB)`)

install-shlibs install:: $(BSD_LIB)
@echo " INSTALL_PROGRAM $(BSDLIB_INSTALL_DIR)/$(BSD_LIB)"
@$(INSTALL_PROGRAM) $(BSD_LIB) \
$(DESTDIR)$$(BSDLIB_INSTALL_DIR)/$(BSD_LIB)
@-$(LDCONFIG)

install-strip: install

install-shlibs-strip: install-shlibs

uninstall-shlibs uninstall::
$(RM) -f $(DESTDIR)$$(BSDLIB_INSTALL_DIR)/$(BSD_LIB)

clean::
$(RM)
-rf pic
$(RM) -f $(BSD_LIB)

```

\$(RM) -f ../\$(BSD_LIB)

This is the Debian GNU/Linux prepackaged version of the ss command-line interface parsing library. It is currently distributed together with the EXT2 file system utilities, which are otherwise packaged as "e2fsprogs".

This package was put together by Yann Dirson <dirson@debian.org>, from sources obtained from a mirror of:
tsx-11.mit.edu:/pub/linux/packages/ext2fs/

From the original distribution:

Copyright 1987, 1988 by the Student Information Processing Board of the Massachusetts Institute of Technology

Permission to use, copy, modify, and distribute this software and its documentation for any purpose and without fee is hereby granted, provided that the above copyright notice appear in all copies and that both that copyright notice and this permission notice appear in supporting documentation, and that the names of M.I.T. and the M.I.T. S.I.P.B. not be used in advertising or publicity pertaining to distribution of the software without specific, written prior permission.

M.I.T. and

the M.I.T. S.I.P.B. make no representations about the suitability of this software for any purpose. It is provided "as is" without express or implied warranty.

This package, the EXT2 filesystem utilities, are made available under the GNU Public License version 2, with the exception of the lib/ext2fs and lib/e2p libraries, which are made available under the GNU Library General Public License Version 2, the lib/uuid library which is made available under a BSD-style license and the lib/et and lib/ss libraries which are made available under an MIT-style license. Please see lib/uuid/COPYING for more details for the license for the files comprising the libuuid library, and the source file headers of the libet and libss libraries for more information.

The most recent officially distributed version can be found at <http://e2fsprogs.sourceforge.net>. If you need to make a distribution, that's the one you should use. If there is some reason why you'd like a more recent version that is still in ALPHA testing (i.e., either using the "WIP" test distributions or one from the hg or git repository from the development branch, please contact me (tytso@mit.edu)

before you ship. The release schedules for this package are flexible, if you give me enough lead time.

Theodore Ts'o
23-June-2007

GNU GENERAL PUBLIC LICENSE

Version 2, June 1991

Copyright (C) 1989, 1991 Free Software Foundation, Inc.

59 Temple Place, Suite 330, Boston, MA 02111-1307 USA

Everyone is permitted to copy and distribute verbatim copies of this license document, but changing it is not allowed.

Preamble

The licenses for most software are designed to take away your freedom to share and change it. By contrast, the GNU General Public License is intended to guarantee your freedom to share and change free software--to make sure the software is free for all its users. This General Public License applies to most of the Free Software Foundation's software and to any other program whose authors commit to using it. (Some other Free Software Foundation software is covered by the GNU Library General Public License instead.) You can apply it to your programs, too.

When we speak of free software, we are referring to freedom, not price. Our General Public Licenses are designed to make sure that you have the freedom to distribute copies of free software (and charge for this service if you wish), that you receive source code or can get it if you want it, that you can change the software or use pieces of it in new free programs; and that you know you can do these things.

To protect your rights, we need to make restrictions that forbid anyone to deny you these rights or to ask you to surrender the rights. These restrictions translate to certain responsibilities for you if you distribute copies of the software, or if you modify it.

For example, if you distribute copies of such a program, whether gratis or for a fee, you must give the recipients all the rights that you have. You must make sure that they, too, receive or can get the source code. And you must show them these terms so they know their rights.

We protect your rights with two steps: (1) copyright the software, and (2) offer you this license which gives you legal permission to copy, distribute and/or modify the software.

Also, for each author's protection and ours, we want to make certain that everyone understands that there is no warranty for this free software. If the software is modified by someone else and passed on, we want its recipients to know that what they have is not the original, so that any problems introduced by others will not reflect on the original authors' reputations.

Finally, any free program is threatened constantly by software patents. We wish to avoid the danger that redistributors of a free program will individually obtain patent licenses, in effect making the program proprietary. To prevent this, we have made it clear that any patent must be licensed for everyone's free use or not licensed at all.

The precise terms and conditions for copying, distribution and modification follow.

GNU GENERAL PUBLIC LICENSE TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

0. This License applies to any program or other work which contains a notice placed by the copyright holder saying it may be distributed under the terms of this General Public License. The "Program", below, refers to any such program or work, and a "work based on the Program" means either the Program or any derivative work under copyright law: that is to say, a work containing the Program or a portion of it, either verbatim or with modifications and/or translated into another language. (Hereinafter, translation is included without limitation in the term "modification".) Each licensee is addressed as "you".

Activities other than copying, distribution and modification are not covered by this License; they are outside its scope. The act of running the Program is not restricted, and the output from the Program is covered

only if its contents constitute a work based on the Program (independent of having been made by running the Program). Whether that is true depends on what the Program does.

1. You may copy and distribute verbatim copies of the Program's source code as you receive it, in any medium, provided that you conspicuously and appropriately publish on each copy an appropriate copyright notice and disclaimer of warranty; keep intact all the notices that refer to this License and to the absence of any warranty; and give any other recipients of the Program a copy of this License along with the Program.

You may charge a fee for the physical act of transferring a copy, and

you may at your option offer warranty protection in exchange for a fee.

2. You may modify your copy or copies of the Program or any portion of it, thus forming a work based on the Program, and copy and distribute such modifications or work under the terms of Section 1 above, provided that you also meet all of these conditions:

- a) You must cause the modified files to carry prominent notices stating that you changed the files and the date of any change.
- b) You must cause any work that you distribute or publish, that in whole or in part contains or is derived from the Program or any part thereof, to be licensed as a whole at no charge to all third parties under the terms of this License.
- c) If the modified program normally reads commands interactively when run, you must cause it, when started running for such interactive use in the most ordinary way, to print or display an announcement including an appropriate copyright notice and a notice that there is no warranty (or else, saying that you provide a warranty) and that users may redistribute the program under these conditions, and telling the user how to view a copy of this License. (Exception: if the Program itself is interactive but does not normally print such an announcement, your work based on the Program is not required to print an announcement.)

These requirements apply to the modified work as a whole. If identifiable sections of that work are not derived from the Program, and can be reasonably considered independent and separate works in themselves, then this License, and its terms, do not apply to those sections when you distribute them as separate works. But when you distribute the same sections as part of a whole which is a work based on the Program, the distribution of the whole must be on the terms of this License, whose permissions for other licensees extend to the entire whole, and thus to each and every part regardless of who wrote it.

Thus, it is not the intent of this section to claim rights or contest your rights to work written entirely by you; rather, the intent is to exercise the right to control the distribution of derivative or collective works based on the Program.

In addition, mere aggregation of another work not based on the Program with the Program (or with a work based on the Program) on a volume of a storage or distribution medium does not bring the other work under the scope of this License.

3. You may copy and distribute the Program (or a work based on it, under Section 2) in object code or executable form under the terms of Sections 1 and 2 above provided that you also do one of the following:

a) Accompany it with the complete corresponding machine-readable source code, which must be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange; or,

b) Accompany it with a written offer, valid for at least three years, to give any third party, for a charge no more than your cost of physically performing source distribution, a complete machine-readable copy of the corresponding source code, to be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange; or,

c) Accompany it with the information you received as to the offer to distribute corresponding source code. (This alternative is allowed only for noncommercial distribution and only if you received the program in object code or executable form with such an offer, in accord with Subsection b above.)

The source code for a work means the preferred form of the work for making modifications to it. For an executable work, complete source code means all the source code for all modules it contains, plus any associated interface definition files, plus the scripts used to control compilation and installation of the executable. However, as a special exception, the source code distributed need not include anything that is normally distributed (in either source or binary form) with the major components (compiler, kernel, and so on) of the operating system on which the executable runs, unless that component itself accompanies the executable.

If distribution of executable or object code is made by offering access to copy from a designated place, then offering equivalent access to copy the source code from the same place counts as distribution of the source code, even though third parties are not compelled to copy the source along with the object code.

4. You may not copy, modify, sublicense, or distribute the Program except as expressly provided under this License. Any attempt otherwise to copy, modify, sublicense or distribute the Program is void, and will automatically terminate your rights under this License. However, parties who have received copies, or rights, from you under this License will not have their licenses terminated so long as such parties remain in full compliance.

5. You are not required to accept this License, since you have not signed it. However, nothing else grants you permission to modify or distribute the Program or its derivative works. These actions are prohibited by law if you do not accept this License. Therefore, by modifying or distributing the Program (or any work based on the Program), you indicate your acceptance of this License to do so, and all its terms and conditions for copying, distributing or modifying the Program or works based on it.

6. Each time you redistribute the Program (or any work based on the Program), the recipient automatically receives a license from the original licensor to copy, distribute or modify the Program subject to these terms and conditions. You may not impose any further restrictions on the recipients' exercise of the rights granted herein. You are not responsible for enforcing compliance by third parties to this License.

7. If, as a consequence of a court judgment or allegation of patent infringement or for any other reason (not limited to patent issues), conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot distribute so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not distribute the Program at all. For example, if a patent license would not permit royalty-free redistribution of the Program by all those who receive copies directly or indirectly through you, then the only way you could satisfy both it and this License would be to refrain entirely from distribution of the Program.

If any portion of this section is held invalid or unenforceable under any particular circumstance, the balance of the section is intended to apply and the section as a whole is intended to apply in other circumstances.

It is not the purpose of this section to induce you to infringe any patents or other property right claims or to contest validity of any such claims; this section has the sole purpose of protecting the integrity of the free software distribution system, which is implemented by public license practices. Many people have made generous contributions to the wide range of software distributed through that system in reliance on consistent application of that system; it is up to the author/donor to decide if he or she is willing to distribute software through any other system and a licensee cannot impose that choice.

This section is intended to make thoroughly clear what is believed to be a consequence of the rest of this License.

8. If the distribution and/or use of the Program is restricted in certain countries either by patents or by copyrighted interfaces, the original copyright holder who places the Program under this License may add an explicit geographical distribution limitation excluding those countries, so that distribution is permitted only in or among countries not thus excluded. In such case, this License incorporates the limitation as if written in the body of this License.

9. The Free Software Foundation may publish revised and/or new versions of the General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Program specifies a version number of this License which applies to it and "any later version", you have the option of following the terms and conditions either of that version or of any later version published by the Free Software Foundation. If the Program does not specify a version number of this License, you may choose any version ever published by the Free Software Foundation.

10. If you wish to incorporate parts of the Program into other free programs whose distribution conditions are different, write to the author to ask for permission. For software which is copyrighted by the Free Software Foundation, write to the Free Software Foundation; we sometimes make exceptions for this. Our decision will be guided by the two goals of preserving the free status of all derivatives of our free software and of promoting the sharing and reuse of software generally.

NO WARRANTY

11. BECAUSE THE PROGRAM IS LICENSED FREE OF CHARGE, THERE IS NO WARRANTY FOR THE PROGRAM, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE PROGRAM "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE PROGRAM IS WITH YOU. SHOULD THE PROGRAM PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

12. IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING

WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY AND/OR REDISTRIBUTE THE PROGRAM AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE

OR INABILITY TO USE THE PROGRAM (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE PROGRAM TO OPERATE WITH ANY OTHER PROGRAMS), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Programs

If you develop a new program, and you want it to be of the greatest possible use to the public, the best way to achieve this is to make it free software which everyone can redistribute and change under these terms.

To do so, attach the following notices to the program. It is safest to attach them to the start of each source file to most effectively convey the exclusion of warranty; and each file should have at least the "copyright" line and a pointer to where the full notice is found.

```
<one line to give the program's name and a brief idea of what it does.>  
Copyright (C) <year> <name  
of author>
```

This program is free software; you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation; either version 2 of the License, or (at your option) any later version.

This program is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details.

You should have received a copy of the GNU General Public License along with this program; if not, write to the Free Software Foundation, Inc., 59 Temple Place, Suite 330, Boston, MA 02111-1307 USA

Also add information on how to contact you by electronic and paper mail.

If the program is interactive, make it output a short notice like this when it starts in an interactive mode:

```
Gnomovision version 69, Copyright (C) year name of author
```

Gnomovision comes
with ABSOLUTELY NO WARRANTY; for details type `show w'.
This is free software, and you are welcome to redistribute it
under certain conditions; type `show c' for details.

The hypothetical commands `show w' and `show c' should show the appropriate
parts of the General Public License. Of course, the commands you use may
be called something other than `show w' and `show c'; they could even be
mouse-clicks or menu items--whatever suits your program.

You should also get your employer (if you work as a programmer) or your
school, if any, to sign a "copyright disclaimer" for the program, if
necessary. Here is a sample; alter the names:

Yoyodyne, Inc., hereby disclaims all copyright interest in the program
'Gnomovision' (which makes passes at compilers) written by James Hacker.

<signature of Ty Coon>, 1 April 1989
Ty Coon, President of Vice

This General Public License does not permit incorporating your program into
proprietary programs. If your program is a subroutine
library, you may
consider it more useful to permit linking proprietary applications with the
library. If this is what you want to do, use the GNU Library General
Public License instead of this License.

GNU LIBRARY GENERAL PUBLIC LICENSE
Version 2, June 1991

Copyright (C) 1991 Free Software Foundation, Inc.
59 Temple Place, Suite 330, Boston, MA 02111-1307 USA
Everyone is permitted to copy and distribute verbatim copies
of this license document, but changing it is not allowed.

[This is the first released version of the library GPL. It is
numbered 2 because it goes with version 2 of the ordinary GPL.]

Preamble

The licenses for most software are designed to take away your
freedom to share and change it. By contrast, the GNU General Public
Licenses are intended to guarantee your freedom to share and change
free software--to make sure the software is free for all its users.

This license, the Library General Public License, applies to some specially designated Free Software Foundation software, and to any other libraries whose authors decide to use it. You can use it for your libraries, too.

When we speak of free software, we are referring to freedom, not price. Our General Public Licenses are designed to make sure that you have the freedom to distribute copies of free software (and charge for this service if you wish), that you receive source code or can get it if you want it, that you can change the software or use pieces of it in new free programs; and that you know you can do these things.

To protect your rights, we need to make restrictions that forbid anyone to deny you these rights or to ask you to surrender the rights. These restrictions translate to certain responsibilities for you if you distribute copies of the library, or if you modify it.

For example, if you distribute copies of the library, whether gratis or for a fee, you must give the recipients all the rights that we gave you. You must make sure that they, too, receive or can get the source code. If you link a program with the library, you must provide complete object files to the recipients so that they can relink them with the library, after making changes to the library and recompiling it. And you must show them these terms so they know their rights.

Our method of protecting your rights has two steps: (1) copyright the library, and (2) offer you this license which gives you legal permission to copy, distribute and/or modify the library.

Also, for each distributor's protection, we want to make certain that everyone understands that there is no warranty for this free library. If the library is modified by someone else and passed on, we want its recipients to know that what they have is not the original version, so that any problems introduced by others will not reflect on the original authors' reputations.

Finally, any free program is threatened constantly by software patents. We wish to avoid the danger that companies distributing free software will individually obtain patent licenses, thus in effect transforming the program into proprietary software. To prevent this, we have made it clear that any patent must be licensed for everyone's free use or not licensed at all.

Most GNU software, including some libraries, is covered by the ordinary GNU General Public License, which was designed for utility programs. This license, the GNU Library General Public License, applies to certain

designated libraries. This license is quite different from the ordinary one; be sure to read it in full, and don't assume that anything in it is the same as in the ordinary license.

The reason we have a separate public license for some libraries is that they blur the distinction we usually make between modifying or adding to a program and simply using it. Linking a program with a library, without changing the library, is in some sense simply using the library, and is analogous to running a utility program or application program. However, in a textual and legal sense, the linked executable is a combined work, a derivative of the original library, and the ordinary General Public License treats it as such.

Because of this blurred distinction, using the ordinary General Public License for libraries did not effectively promote software sharing, because most developers did not use the libraries. We concluded that weaker conditions might promote sharing better.

However, unrestricted linking of non-free programs would deprive the users of those programs of all benefit from the free status of the libraries themselves. This Library General Public License is intended to permit developers of non-free programs to use free libraries, while preserving your freedom as a user of such programs to change the free libraries that are incorporated in them. (We have not seen how to achieve this as regards changes in header files, but we have achieved it as regards changes in the actual functions of the Library.) The hope is that this will lead to faster development of free libraries.

The precise terms and conditions for copying, distribution and modification follow. Pay close attention to the difference between a "work based on the library" and a "work that uses the library". The former contains code derived from the library, while the latter only works together with the library.

Note that it is possible for a library to be covered by the ordinary General Public License rather than by this special one.

GNU LIBRARY GENERAL PUBLIC LICENSE TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

0. This License Agreement applies to any software library which contains a notice placed by the copyright holder or other authorized party saying it may be distributed under the terms of this Library General Public License (also called "this License"). Each licensee is addressed as "you".

A "library" means a collection of software functions and/or data prepared so as to be conveniently linked with application programs (which use some of those functions and data) to form executables.

The "Library", below, refers to any such software library or work which has been distributed under these terms. A "work based on the Library" means either the Library or any derivative work under copyright law: that is to say, a work containing the Library or a portion of it, either verbatim or with modifications and/or translated straightforwardly into another language. (Hereinafter, translation is included without limitation in the term "modification".)

"Source code" for a work means the preferred form of the work for making modifications to it. For a library, complete source code means all the source code for all modules it contains, plus any associated interface definition files, plus the scripts used to control compilation and installation of the library.

Activities other than copying, distribution and modification are not covered by this License; they are outside its scope. The act of running a program using the Library is not restricted, and output from such a program is covered only if its contents constitute a work based on the Library (independent of the use of the Library in a tool for writing it). Whether that is true depends on what the Library does and what the program that uses the Library does.

1. You may copy and distribute verbatim copies of the Library's complete source code as you receive it, in any medium, provided that you conspicuously and appropriately publish on each copy an appropriate copyright notice and disclaimer of warranty; keep intact all the notices that refer to this License and to the absence of any warranty; and distribute a copy of this License along with the Library.

You may charge a fee for the physical act of transferring a copy, and you may at your option offer warranty protection in exchange for a fee.

2.

You may modify your copy or copies of the Library or any portion of it, thus forming a work based on the Library, and copy and distribute such modifications or work under the terms of Section 1 above, provided that you also meet all of these conditions:

- a) The modified work must itself be a software library.
- b) You must cause the files modified to carry prominent notices

stating that you changed the files and the date of any change.

c) You must cause the whole of the work to be licensed at no charge to all third parties under the terms of this License.

d) If a facility in the modified Library refers to a function or a table of data to be supplied by an application program that uses the facility, other than as an argument passed when the facility is invoked, then you must make a good faith effort to ensure that, in the event an application does not supply such function or table, the facility still operates, and performs whatever part of its purpose remains meaningful.

(For example, a function in a library to compute square roots has a purpose that is entirely well-defined independent of the application. Therefore, Subsection 2d requires that any application-supplied function or table used by this function must be optional: if the application does not supply it, the square root function must still compute square roots.)

These requirements apply to the modified work as a whole. If identifiable sections of that work are not derived from the Library, and can be reasonably considered independent and separate works in themselves, then this License, and its terms, do not apply to those sections when you distribute them as separate works. But when you distribute the same sections as part of a whole which is a work based on the Library, the distribution of the whole must be on the terms of this License, whose permissions for other licensees extend to the entire whole, and thus to each and every part regardless of who wrote it.

Thus, it is not the intent of this section to claim rights or contest your rights to work written entirely by you; rather, the intent is to exercise the right to control the distribution of derivative or collective works based on the Library.

In addition, mere aggregation of another work not based on the Library with the Library (or with a work based on the Library) on a volume of a storage or distribution medium does not bring the other work under the scope of this License.

3. You may opt to apply the terms of the ordinary GNU General Public License instead of this License to a given copy of the Library. To do this, you must alter all the notices that refer to this License, so that they refer to the ordinary GNU General Public License, version 2, instead of to this License. (If a newer version than version 2 of the ordinary GNU General Public License has appeared, then you can specify

that version instead if you wish.) Do not make any other change in these notices.

Once this change is made in a given copy, it is irreversible for that copy, so the ordinary GNU General Public License applies to all subsequent copies and derivative works made from that copy.

This option is useful when you wish to copy part of the code of the Library into a program that is not a library.

4. You may copy and distribute the Library (or a portion or derivative of it, under Section 2) in object code or executable form under the terms of Sections 1 and 2 above provided that you accompany it with the complete corresponding machine-readable source code, which must be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange.

If distribution of object code is made by offering access to copy from a designated place, then offering equivalent access to copy the source code from the same place satisfies the requirement to distribute the source code, even though third parties are not compelled to copy the source along with the object code.

5. A program that contains no derivative of any portion of the Library, but is designed to work with the Library by being compiled or linked with it, is called a "work that uses the Library". Such a work, in isolation, is not a derivative work of the Library, and therefore falls outside the scope of this License.

However, linking a "work that uses the Library" with the Library creates an executable that is a derivative of the Library (because it contains portions of the Library), rather than a "work that uses the library". The executable is therefore covered by this License. Section 6 states terms for distribution of such executables.

When a "work that uses the Library" uses material from a header file that is part of the Library, the object code for the work may be a derivative work of the Library even though the source code is not. Whether this is true is especially significant if the work can be linked without the Library, or if the work is itself a library. The threshold for this to be true is not precisely defined by law.

If such an object file uses only numerical parameters, data structure layouts and accessors, and small macros and small inline functions (ten lines or less in length), then the use of the object

file is unrestricted, regardless of whether it is legally a derivative work. (Executables containing this object code plus portions of the Library will still fall under Section 6.)

Otherwise, if the work is a derivative of the Library, you may distribute the object code for the work under the terms of Section 6. Any executables containing that work also fall under Section 6, whether or not they are linked directly with the Library itself.

6. As an exception to the Sections above, you may also compile or link a "work that uses the Library" with the Library to produce a work containing portions of the Library, and distribute that work under terms of your choice, provided that the terms permit modification of the work for the customer's own use and reverse engineering for debugging such modifications.

You must give prominent notice with each copy of the work that the Library is used in it and that the Library and its use are covered by this License. You must supply a copy of this License. If the work during execution displays copyright notices, you must include the copyright notice for the Library among them, as well as a reference directing the user to the copy of this License. Also, you must do one of these things:

a) Accompany the work with the complete corresponding machine-readable source code for the Library including whatever changes were used in the work (which must be distributed under Sections 1 and 2 above); and, if the work is an executable linked with the Library, with the complete machine-readable "work that uses the Library", as object code and/or source code, so that the user can modify the Library and then relink to produce a modified

executable containing the modified Library. (It is understood that the user who changes the contents of definitions files in the Library will not necessarily be able to recompile the application to use the modified definitions.)

b) Accompany the work with a written offer, valid for at least three years, to give the same user the materials specified in Subsection 6a, above, for a charge no more than the cost of performing this distribution.

c) If distribution of the work is made by offering access to copy from a designated place, offer equivalent access to copy the above specified materials from the same place.

d) Verify that the user has already received a copy of these

materials or that you have already sent this user a copy.

For an executable, the required form of the "work that uses the Library" must include any data and utility programs needed for reproducing the executable from it. However, as a special exception, the

source code distributed need not include anything that is normally distributed (in either source or binary form) with the major components (compiler, kernel, and so on) of the operating system on which the executable runs, unless that component itself accompanies the executable.

It may happen that this requirement contradicts the license restrictions of other proprietary libraries that do not normally accompany the operating system. Such a contradiction means you cannot use both them and the Library together in an executable that you distribute.

7. You may place library facilities that are a work based on the Library side-by-side in a single library together with other library facilities not covered by this License, and distribute such a combined library, provided that the separate distribution of the work based on the Library and of the other library facilities is otherwise permitted, and provided that you do these two things:

- a) Accompany the combined library with a copy of the same work based on the Library, uncombined with any other library facilities. This must be distributed under the terms of the Sections above.
- b) Give prominent notice with the combined library of the fact that part of it is a work based on the Library, and explaining where to find the accompanying uncombined form of the same work.

8. You may not copy, modify, sublicense, link with, or distribute the Library except as expressly provided under this License. Any attempt otherwise to copy, modify, sublicense, link with, or distribute the Library is void, and will automatically terminate your rights under this License. However, parties who have received copies, or rights, from you under this License will not have their licenses terminated so long as such parties remain in full compliance.

9. You are not required to accept this License, since you have not signed it. However, nothing else grants you permission to modify or distribute the

Library or its derivative works. These actions are prohibited by law if you do not accept this License. Therefore, by

modifying or distributing the Library (or any work based on the Library), you indicate your acceptance of this License to do so, and all its terms and conditions for copying, distributing or modifying the Library or works based on it.

10. Each time you redistribute the Library (or any work based on the Library), the recipient automatically receives a license from the original licensor to copy, distribute, link with or modify the Library subject to these terms and conditions. You may not impose any further restrictions on the recipients' exercise of the rights granted herein. You are not responsible for enforcing compliance by third parties to this License.

11. If, as a consequence of a court judgment or allegation of patent infringement or for any other reason (not limited to patent issues), conditions are imposed on you (whether by court order, agreement or otherwise)

that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot distribute so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not distribute the Library at all. For example, if a patent license would not permit royalty-free redistribution of the Library by all those who receive copies directly or indirectly through you, then the only way you could satisfy both it and this License would be to refrain entirely from distribution of the Library.

If any portion of this section is held invalid or unenforceable under any particular circumstance, the balance of the section is intended to apply, and the section as a whole is intended to apply in other circumstances.

It is not the purpose of this section to induce you to infringe any patents or other property right claims or to contest validity of any such claims; this section has the sole purpose of protecting the integrity of the free software distribution system which is implemented by public license practices. Many people have made generous contributions to the wide range of software distributed through that system in reliance on consistent application of that system; it is up to the author/donor to decide if he or she is willing to distribute software through any other system and a licensee cannot impose that choice.

This section is intended to make thoroughly clear what is believed to be a consequence of the rest of this License.

12. If the distribution and/or use of the Library is restricted in certain countries either by patents or by copyrighted interfaces, the

original copyright holder who places the Library under this License may add an explicit geographical distribution limitation excluding those countries, so that distribution is permitted only in or among countries not thus excluded. In such case, this License incorporates the limitation as if written in the body of this License.

13. The Free Software Foundation may publish revised and/or new versions of the Library General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Library specifies a version number of this License which applies to it and "any later version", you have the option of following the terms and conditions either of that version or of any later version published by the Free Software Foundation. If the Library does not specify a license version number, you may choose any version ever published by the Free Software Foundation.

14. If you wish to incorporate parts of the Library into other free programs whose distribution conditions are incompatible with these, write to the author to ask for permission. For software which is copyrighted by the Free Software Foundation, write to the Free Software Foundation; we sometimes make exceptions for this. Our decision will be guided by the two goals of preserving the free status of all derivatives of our free software and of promoting the sharing and reuse of software generally.

NO WARRANTY

15. BECAUSE THE LIBRARY IS LICENSED FREE OF CHARGE, THERE IS NO WARRANTY FOR THE LIBRARY, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE LIBRARY "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE LIBRARY IS WITH YOU. SHOULD THE LIBRARY PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

16. IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY AND/OR REDISTRIBUTE THE LIBRARY AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE

LIBRARY (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE LIBRARY TO OPERATE WITH ANY OTHER SOFTWARE), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Libraries

If you develop a new library, and you want it to be of the greatest possible use to the public, we recommend making it free software that everyone can redistribute and change. You can do so by permitting redistribution under these terms (or, alternatively, under the terms of the ordinary General Public License).

To apply these terms, attach the following notices to the library. It is safest to attach them to the start of each source file to most effectively convey the exclusion of warranty; and each file should have at least the "copyright" line and a pointer to where the full notice is found.

<one line to give the library's name and a brief idea of what it does.>
Copyright (C) <year> <name of author>

This library is free software; you can redistribute it and/or modify it under the terms of the GNU Library General Public License as published by the Free Software Foundation; either version 2 of the License, or (at your option) any later version.

This library is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU Library General Public License for more details.

You should have received a copy of the GNU Library General Public License along with this library; if not, write to the Free Software Foundation, Inc., 59 Temple Place, Suite 330, Boston, MA 02111-1307 USA

Also add information on how to contact you by electronic and paper mail.

You should also get your employer (if you work as a programmer) or your school, if any, to sign a "copyright disclaimer" for the library, if necessary. Here is a sample; alter the names:

Yoyodyne, Inc., hereby disclaims all copyright interest in the library `Frob' (a library for tweaking knobs) written by James Random Hacker.

<signature of Ty Coon>, 1 April 1990

Ty Coon, President of Vice

That's all there is to it!

This is the Debian GNU/Linux prepackaged version of the Common Error Description library. It is currently distributed together with the EXT2 file system utilities, which are otherwise packaged as "e2fsprogs".

This package was put together by Yann Dirson <dirson@debian.org>, from sources obtained from a mirror of:
tsx-11.mit.edu:/pub/linux/packages/ext2fs/

From the original distribution:

Copyright 1987, 1988 by the Student Information Processing Board of the Massachusetts Institute of Technology

Permission to use, copy, modify, and distribute this software and its documentation for any purpose and without fee is hereby granted, provided that the above copyright notice appear in all copies and that both that copyright notice and this permission notice appear in supporting documentation, and that the names of M.I.T. and the M.I.T. S.I.P.B. not be used in advertising or publicity pertaining to distribution of the software without specific, written prior permission. M.I.T. and the M.I.T.

S.I.P.B. make no representations about the suitability of this software for any purpose. It is provided "as is" without express or implied warranty.

1.79 pcre 2:8.39-9ubuntu0.1

1.79.1 Available under license :

This is Debian GNU/Linux's prepackaged version of the PCRE regular expression library and associated pgrep utility.

This package was put together by me, Mark Baker <mbaker@iee.org> from the original sources obtained from ftp.csx.cam.ac.uk:/pub/software/programming/pcre.

PCRE LICENCE

PCRE is a library of functions to support regular expressions whose syntax and semantics are as close as possible to those of the Perl 5 language.

Release 7 of PCRE is distributed under the terms of the "BSD" licence, as

specified below. The documentation for PCRE, supplied in the "doc" directory, is distributed under the same terms as the software itself.

The basic library functions are written in C and are freestanding. Also included in the distribution is a set of C++ wrapper functions.

THE BASIC LIBRARY FUNCTIONS

Written by: Philip Hazel
Email local part: ph10
Email domain: cam.ac.uk

University of Cambridge Computing Service,
Cambridge, England.

Copyright
(c) 1997-2007 University of Cambridge
All rights reserved.

THE C++ WRAPPER FUNCTIONS

Contributed by: Google Inc.

Copyright (c) 2007, Google Inc.
All rights reserved.

THE "BSD" LICENCE

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

- * Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.
- * Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.
- * Neither the name of the University of Cambridge nor the name of Google Inc. nor the names of their contributors may be used to endorse or promote products derived from this software without specific prior written permission.

THIS

SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

End

1.80 libext2fs2 1.44.1-1ubuntu1.4

1.80.1 Available under license :

This package was added to the e2fsprogs debian source package by Theodore Ts'o <tytso@mit.edu> on Sat Mar 15 15:33:37 EST 2003

It is part of the main e2fsprogs distribution, which can be found at:

<http://sourceforge.net/projects/e2fsprogs>

Upstream Author: Theodore Ts'o <tytso@mit.edu>

Copyright:

Copyright (C) 1999, 2001 by Andries Brouwer

Copyright (C) 1999, 2000, 2003 by Theodore Ts'o

You are free to distribute this software under the terms of the GNU Lesser (Library) General Public License.

On Debian systems, the complete text of the GNU Lesser (Library) General Public License can be found in /usr/share/common-licenses/LGPL-2.

This is the Debian GNU/Linux prepackaged version of the static EXT2 file system consistency checker (e2fsck.static). The EXT2 utilities were written by Theodore Ts'o <tytso@mit.edu> and Remy Card <card@masi.ibp.fr>.

Sources were obtained from <http://sourceforge.net/projects/e2fsprogs>

Packaging is Copyright (c) 2003-2006 Theodore Ts'o <tytso@mit.edu>

Copyright (c) 1997-2003 Yann Dirson <dirson@debian.org>

Copyright (c) 2001 Alcove <<http://www.alcove.com/>>

Copyright (c) 1997 Klee Dienes

Copyright (c) 1995-1996 Michael Nonweiler <mrn20@cam.ac.uk>

Upstream Author: Theodore Ts'o <tytso@mit.edu>

Copyright notice:

This package, the EXT2 filesystem utilities, is protected by the GNU General Public License.

Copyright (c) 1993, 1994, 1995, 1996, 1997, 1998, 1999, 2000, 2001, 2002, 2003, 2004, 2005, 2006, 2007, 2008 by Theodore Ts'o

On Debian GNU systems, the complete text of the GNU General Public License can be found in `/usr/share/common-licenses/GPL-2`. Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

1. Redistributions of source code must retain the above copyright notice, and the entire permission notice in its entirety, including the disclaimer of warranties.
2. Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.
3. The name of the author may not be used to endorse or promote products derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED ``AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, ALL OF WHICH ARE HEREBY DISCLAIMED. IN NO EVENT SHALL THE AUTHOR BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL

DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF NOT ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

This is the Debian GNU/Linux prepackaged version of the translation files of the EXT2 file system utilities. The EXT2 utilities were written by Theodore Ts'o <tytso@mit.edu> and Remy Card <card@masi.ibp.fr>.

Sources were obtained from <http://sourceforge.net/projects/e2fsprogs>

Packaging is Copyright (c) 2003-2006 Theodore Ts'o <tytso@mit.edu>
Copyright (c) 1997-2003 Yann Dirson <dirson@debian.org>
Copyright (c) 2001 Alcove <<http://www.alcove.com/>>
Copyright (c) 1997 Klee Dienes
Copyright (c) 1995-1996 Michael Nonweiler <mrn20@cam.ac.uk>

Upstream Author: Theodore Ts'o <tytso@mit.edu>

Copyright notice:

This package, the EXT2 filesystem utilities, is protected by the GNU
General Public License.

Copyright (c) 1993, 1994, 1995, 1996, 1997, 1998, 1999, 2000,
2001, 2002, 2003, 2004, 2005, 2006, 2007, 2008 by Theodore Ts'o

On Debian GNU systems, the complete text of the GNU General
Public License can be found in `~/usr/share/common-licenses/GPL-2`.
This package was added to the e2fsprogs debian source package by
Theodore Ts'o <tytso@mit.edu> on Fri Dec 14 22:24:35 EST 2007

It is part of the main e2fsprogs distribution, which can be found at:

<http://sourceforge.net/projects/e2fsprogs>

Upstream Author: Theodore Ts'o <tytso@mit.edu>

Copyright:

Copyright (C) 1999, 2000, 2001, 2002, 2003, 2004, 2005, 2006, 2007 by
Theodore Ts'o

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions
are met:

1. Redistributions of source code must retain the above copyright
notice, and the entire permission notice in its entirety,
including the disclaimer of warranties.
2. Redistributions in binary form must reproduce the above copyright
notice, this list of conditions and the following disclaimer in the
documentation and/or other materials provided with the distribution.
3. The name of the author may not be used to endorse or promote
products derived from
this software without specific prior
written permission.

THIS SOFTWARE IS PROVIDED ``AS IS" AND ANY EXPRESS OR IMPLIED

WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, ALL OF WHICH ARE HEREBY DISCLAIMED. IN NO EVENT SHALL THE AUTHOR BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF NOT ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

Index: tdbsa/tdb.c

--- tdbsa.orig/tdb.c

+++ tdbsa/tdb.c

@@ -4,11 +4,11 @@ Rev: 23371

Last Changed Date: 2007-06-06 20:14:06 -0400 (Wed, 06 Jun 2007)

*/

/*

- Unix SMB/CIFS implementation.
- + trivial database library - standalone version

- trivial database library - private includes

-

- Copyright (C) Andrew Tridgell 2005
- + Copyright (C) Andrew Tridgell 1999-2005
- + Copyright (C) Jeremy Allison 2000-2006
- + Copyright (C) Paul 'Rusty' Russell 2000

** NOTE! The following LGPL license applies to the tdb
** library. This does NOT imply that all of Samba is released
EXT2ED is hereby placed under the terms of the GNU General Public License.
Follows the GNU license.

Gadi Oxman, August 1995

GNU GENERAL PUBLIC LICENSE

Version 2, June 1991

Copyright (C) 1989, 1991 Free Software Foundation, Inc.
675 Mass Ave, Cambridge, MA 02139, USA
Everyone is permitted to copy and distribute verbatim copies
of this license document, but changing it is not allowed.

Preamble

The licenses for most software are designed to take away your freedom to share and change it. By contrast, the GNU General Public License is intended to guarantee your freedom to share and change free software--to make sure the software is free for all its users. This General Public License applies to most of the Free Software Foundation's software and to any other program whose authors commit to using it. (Some other Free Software Foundation software is covered by the GNU Library General Public License instead.) You can apply it to your programs, too.

When we speak of free software, we are referring to freedom, not price. Our General Public Licenses are designed to make sure that you have the freedom to distribute copies of free software (and charge for this service if you wish), that you receive source code or can get it if you want it, that you can change the software or use pieces of it in new free programs; and that you know you can do these things.

To protect your rights, we need to make restrictions that forbid anyone to deny you these rights or to ask you to surrender the rights. These restrictions translate to certain responsibilities for you if you distribute copies of the software, or if you modify it.

For example, if you distribute copies of such a program, whether gratis or for a fee, you must give the recipients all the rights that you have. You must make sure that they, too, receive or can get the source code. And you must show them these terms so they know their rights.

We protect your rights with two steps: (1) copyright the software, and (2) offer you this license which gives you legal permission to copy, distribute and/or modify the software.

Also, for each author's protection and ours, we want to make certain that everyone understands that there is no warranty for this free software. If the software is modified by someone else and passed on, we want its recipients to know that what they have is not the original, so that any problems introduced by others will not reflect on the original authors' reputations.

Finally, any free program is threatened constantly by software patents. We wish to avoid the danger that redistributors of a free program will individually obtain patent licenses, in effect making the program proprietary. To prevent this, we have made it clear that any patent must be licensed for everyone's free use or not licensed at all.

The precise terms and conditions for

copying, distribution and modification follow.

GNU GENERAL PUBLIC LICENSE TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

0. This License applies to any program or other work which contains a notice placed by the copyright holder saying it may be distributed under the terms of this General Public License. The "Program", below, refers to any such program or work, and a "work based on the Program" means either the Program or any derivative work under copyright law: that is to say, a work containing the Program or a portion of it, either verbatim or with modifications and/or translated into another language. (Hereinafter, translation is included without limitation in the term "modification".) Each licensee is addressed as "you".

Activities other than copying, distribution and modification are not covered by this License; they are outside its scope. The act of running the Program is not restricted, and the output from the Program is covered only if its contents constitute a work based on the Program (independent of having been made by running the Program). Whether that is true depends on what the Program does.

1. You may copy and distribute verbatim copies of the Program's source code as you receive it, in any medium, provided that you conspicuously and appropriately publish on each copy an appropriate copyright notice and disclaimer of warranty; keep intact all the notices that refer to this License and to the absence of any warranty; and give any other recipients of the Program a copy of this License along with the Program.

You may charge a fee for the physical act of transferring a copy, and you may at your option offer warranty protection in exchange for a fee.

2. You may modify your copy or copies of the Program or any portion of it, thus forming a work based on the Program, and copy and distribute such modifications or work under the terms of Section 1 above, provided that you also meet all of these conditions:

- a) You must cause the modified files to carry prominent notices stating that you changed the files and the date of any change.
- b) You must cause any work that you distribute or publish, that in whole or in part contains or is derived from the Program or any part thereof, to be licensed as a whole at no charge to all third parties under the terms of this License.

c) If the modified program normally reads commands interactively when run, you must cause it, when started running for such interactive use in the most ordinary way, to print or display an announcement including an appropriate copyright notice and a notice that there is no warranty (or else, saying that you provide a warranty) and that users may redistribute the program under these conditions, and telling the user how to view a copy of this License. (Exception: if the Program itself is interactive but does not normally print such an announcement, your work based on the Program is not required to print an announcement.)

These requirements apply to the modified work as a whole. If identifiable sections of that work are not derived from the Program, and can be reasonably considered independent and separate works in themselves, then this License, and its terms, do not apply to those sections when you distribute them as separate works. But when you distribute the same sections as part of a whole which is a work based on the Program, the distribution of the whole must be on the terms of this License, whose permissions for other licensees extend to the entire whole, and thus to each and every part regardless of who wrote it.

Thus, it is not the intent of this section to claim rights or contest your rights to work written entirely by you; rather, the intent is to exercise the right to control the distribution of derivative or collective works based on the Program.

In addition, mere aggregation of another work not based on the Program with the Program (or with a work based on the Program) on a volume of a storage or distribution medium does not bring the other work under the scope of this License.

3. You may copy and distribute the Program (or a work based on it, under Section 2) in object code or executable form under the terms of Sections 1 and 2 above provided that you also do one of the following:

a) Accompany it with the complete corresponding machine-readable source code, which must be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange; or,

b) Accompany it with a written offer, valid for at least three years, to give any third party, for a charge no more than your cost of physically performing source distribution, a complete machine-readable copy of the corresponding source code, to be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange; or,

c) Accompany it with the information you received as to the offer to distribute corresponding source code. (This alternative is allowed only for noncommercial distribution and only if you received the program in object code or executable form with such an offer, in accord with Subsection b above.)

The source code for a work means the preferred form of the work for making modifications to it. For an executable work, complete source code means all the source code for all modules it contains, plus any associated interface definition files, plus the scripts used to control compilation and installation of the executable. However, as a special exception, the source code distributed need not include anything that is normally distributed (in either source or binary form) with the major components (compiler, kernel, and so on) of the operating system on which the executable runs, unless that component itself accompanies the executable.

If distribution of executable or object code is made by offering access to copy from a designated place, then offering equivalent access to copy the source code from the same place counts as distribution of the source code, even though third parties are not compelled to copy the source along with the object code.

4. You may not copy, modify, sublicense, or distribute the Program except as expressly provided under this License. Any attempt otherwise to copy, modify, sublicense or distribute the Program is void, and will automatically terminate your rights under this License. However, parties who have received copies, or rights, from you under this License will not have their licenses terminated so long as such parties remain in full compliance.

5. You are not required to accept this License, since you have not signed it. However, nothing else grants you permission to modify or distribute the Program or its derivative works. These actions are prohibited by law if you do not accept this License. Therefore, by modifying or distributing the Program (or any work based on the Program), you indicate your acceptance of this License to do so, and all its terms and conditions for copying, distributing or modifying the Program or works based on it.

6. Each time you redistribute the Program (or any work based on the Program), the recipient automatically receives a license from the original licensor to copy, distribute or modify the Program subject to these terms and conditions. You may not impose any further

restrictions on the recipients' exercise of the rights granted herein. You are not responsible for enforcing compliance by third parties to this License.

7. If, as a consequence of a court judgment or allegation of patent infringement or for any other reason (not limited to patent issues), conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot distribute so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not distribute the Program at all. For example, if a patent license would not permit royalty-free redistribution of the Program by all those who receive copies directly or indirectly through you, then the only way you could satisfy both it and this License would be to refrain entirely from distribution of the Program.

If any portion of this section is held invalid or unenforceable under any particular circumstance, the balance of the section is intended to apply and the section as a whole is intended to apply in other circumstances.

It is not the purpose of this section to induce you to infringe any patents or other property right claims or to contest validity of any such claims; this section has the sole purpose of protecting the integrity of the free software distribution system, which is implemented by public license practices. Many people have made generous contributions to the wide range of software distributed through that system in reliance on consistent application of that system; it is up to the author/donor to decide if he or she is willing to distribute software through any other system and a licensee cannot impose that choice.

This section is intended to make thoroughly clear what is believed to be a consequence of the rest of this License.

8. If the distribution and/or use of the Program is restricted in certain countries either by patents or by copyrighted interfaces, the original copyright holder who places the Program under this License may add an explicit geographical distribution limitation excluding those countries, so that distribution is permitted only in or among countries not thus excluded. In such case, this License incorporates the limitation as if written in the body of this License.

9. The Free Software Foundation may publish revised and/or new versions of the General Public License from time to time. Such new versions will

be

similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Program specifies a version number of this License which applies to it and "any later version", you have the option of following the terms and conditions either of that version or of any later version published by the Free Software Foundation. If the Program does not specify a version number of this License, you may choose any version ever published by the Free Software Foundation.

10. If you wish to incorporate parts of the Program into other free programs whose distribution conditions are different, write to the author to ask for permission. For software which is copyrighted by the Free Software Foundation, write to the Free Software Foundation; we sometimes make exceptions for this. Our decision will be guided by the two goals of preserving the free status of all derivatives of our free software and of promoting the sharing and reuse of software generally.

NO WARRANTY

11. BECAUSE THE PROGRAM IS LICENSED FREE OF CHARGE, THERE IS NO WARRANTY FOR THE PROGRAM, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE PROGRAM "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE PROGRAM IS WITH YOU. SHOULD THE PROGRAM PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

12. IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY AND/OR REDISTRIBUTE THE PROGRAM AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE PROGRAM (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE PROGRAM TO OPERATE WITH ANY OTHER PROGRAMS), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

END OF TERMS AND CONDITIONS

Appendix: How to Apply These Terms to Your New Programs

If you develop a new program, and you want it to be of the greatest possible use to the public, the best way to achieve this is to make it free software which everyone can redistribute and change under these terms.

To do so, attach the following notices to the program. It is safest to attach them to the start of each source file to most effectively convey the exclusion of warranty; and each file should have at least the "copyright" line and a pointer to where the full notice is found.

```
<one line to give the program's name and a brief idea of what it does.>  
Copyright (C) 19yy <name of author>
```

This program is free software; you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation; either version 2 of the License, or (at your option) any later version.

This program is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details.

You should have received a copy of the GNU General Public License along with this program; if not, write to the Free Software Foundation, Inc., 675 Mass Ave, Cambridge, MA 02139, USA.

Also add information on how to contact you by electronic and paper mail.

If the program is interactive, make it output a short notice like this when it starts in an interactive mode:

```
Gnomovision version 69, Copyright (C) 19yy name of author  
Gnomovision comes with ABSOLUTELY NO WARRANTY;  
for details type `show w'.  
This is free software, and you are welcome to redistribute it  
under certain conditions; type `show c' for details.
```

The hypothetical commands `show w' and `show c' should show the appropriate parts of the General Public License. Of course, the commands you use may be called something other than `show w' and `show c'; they could even be mouse-clicks or menu items--whatever suits your program.

You should also get your employer (if you work as a programmer) or your school, if any, to sign a "copyright disclaimer" for the program, if necessary. Here is a sample; alter the names:

```
Yoyodyne, Inc., hereby disclaims all copyright interest in the program  
'Gnomovision' (which makes passes at compilers) written by James Hacker.
```

<signature of Ty Coon>, 1 April 1989

Ty Coon, President of Vice

This General Public License does not permit incorporating your program into proprietary programs. If your program is a subroutine library, you may consider

it more useful to permit linking proprietary applications with the library. If this is what you want to do, use the GNU Library General Public License instead of this License.

This is the Debian GNU/Linux prepackaged version of the EXT2 file system utilities (e2fsck, mke2fs, etc.). The EXT2 utilities were written by Theodore Ts'o <tytso@mit.edu> and Remy Card <card@masi.ibp.fr>.

Sources were obtained from <http://sourceforge.net/projects/e2fsprogs>

Packaging is Copyright (c) 2003-2007 Theodore Ts'o <tytso@mit.edu>

Copyright (c) 1997-2003 Yann Dirson <dirson@debian.org>

Copyright (c) 2001 Alcove <<http://www.alcove.com/>>

Copyright (c) 1997 Klee Dienes

Copyright (c) 1995-1996 Michael Nonweiler <mrn20@cam.ac.uk>

Upstream Author: Theodore Ts'o <tytso@mit.edu>

Copyright notice:

This package, the EXT2 filesystem utilities, are made available under the GNU General Public License version 2, with the exception of the lib/ext2fs and lib/e2p libraries, which are made available under the GNU Library General Public License Version 2, the lib/uuid library which is made available under a BSD-style license and the lib/et and lib/ss libraries

which are made available under an MIT-style license.

Copyright (c) 1993, 1994, 1995, 1996, 1997, 1998, 1999, 2000, 2001, 2002, 2003, 2004, 2005, 2006, 2007, 2008 by Theodore Ts'o

On Debian GNU systems, the complete text of the GNU General Public License can be found in `"/usr/share/common-licenses/GPL-2"`. The complete text of the GNU Library General Public License can be found in `"/usr/share/common-licenses/LGPL-2"`.

The license used for lib/et and lib/ss libraries is:

Copyright 1987 by the Student Information Processing Board
of the Massachusetts Institute of Technology

Permission to use, copy, modify, and distribute this software and its documentation for any purpose is hereby granted, provided that the names of M.I.T. and the M.I.T. S.I.P.B. not be used in advertising or publicity pertaining to distribution of the software without specific, written prior permission. M.I.T. and the M.I.T. S.I.P.B. make no representations about the suitability of this software for any purpose. It is provided "as is" without express or implied warranty.

The license used for lib/uuid is:

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

1. Redistributions of source code must retain the above copyright notice, and the entire permission notice in its entirety, including the disclaimer of warranties.
2. Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.
3. The name of the author may not be used to endorse or promote products derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED ``AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, ALL OF WHICH ARE HEREBY DISCLAIMED. IN NO EVENT SHALL THE AUTHOR BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF NOT ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

This package was added to the e2fsprogs debian source package by Theodore Ts'o <tytso@mit.edu> on Sat Mar 15 15:33:37 EST 2003

It is part of the main e2fsprogs distribution, which can be found at:

<http://sourceforge.net/projects/e2fsprogs>

Upstream Author: Theodore Ts'o <tytso@mit.edu>

Copyright:

Copyright (C) 1999, 2000, 2003, 2004 by Theodore Ts'o

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

1. Redistributions of source code must retain the above copyright notice, and the entire permission notice in its entirety, including the disclaimer of warranties.
2. Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.
3. The name of the author may not be used to endorse or promote products derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED ``AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, ALL OF WHICH ARE HEREBY DISCLAIMED. IN NO EVENT SHALL THE AUTHOR BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF NOT ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

#

This is a Makefile stub which handles the creation of BSD shared
libraries.

#

In order to use this stub, the following makefile variables must be defined.

#

BSDLIB_VERSION = 1.0

BSDLIB_IMAGE = libce

BSDLIB_MYDIR = et

BSDLIB_INSTALL_DIR = \$(SHLIBDIR)

#

all:: image

real-subdirs:: Makefile

@echo " MKDIR pic"

@mkdir -p pic

BSD_LIB = \$(BSDLIB_IMAGE).so.\$(BSDLIB_VERSION)

```
BSDLIB_PIC_FLAG = -fpic
```

```
image: $(BSD_LIB)
```

```
$(BSD_LIB): $(OBJS)
(cd pic; ld -Bshareable -o $(BSD_LIB) $(LDFLAGS_SHLIB) $(OBJS))
$(MV) pic/$(BSD_LIB) .
$(RM) -f ../$(BSD_LIB)
(cd ..; $(LN) $(LINK_BUILD_FLAGS) \
`echo $(my_dir) | sed -e 's;lib/;;'"/$(BSD_LIB) $(BSD_LIB))
```

```
install-shlibs install:: $(BSD_LIB)
@echo " INSTALL_PROGRAM $(BSDLIB_INSTALL_DIR)/$(BSD_LIB)"
@$(INSTALL_PROGRAM) $(BSD_LIB) \
$(DESTDIR)$$(BSDLIB_INSTALL_DIR)/$(BSD_LIB)
@-$(LDCONFIG)
```

```
install-strip: install
```

```
install-shlibs-strip: install-shlibs
```

```
uninstall-shlibs uninstall::
$(RM) -f $(DESTDIR)$$(BSDLIB_INSTALL_DIR)/$(BSD_LIB)
```

```
clean::
$(RM)
-rf pic
$(RM) -f $(BSD_LIB)
$(RM) -f ../$(BSD_LIB)
```

This is the Debian GNU/Linux prepackaged version of the `ss` command-line interface parsing library. It is currently distributed together with the EXT2 file system utilities, which are otherwise packaged as "e2fsprogs".

This package was put together by Yann Dirson <dirson@debian.org>, from sources obtained from a mirror of:
tsx-11.mit.edu/pub/linux/packages/ext2fs/

From the original distribution:

Copyright 1987, 1988 by the Student Information Processing Board of the Massachusetts Institute of Technology

Permission to use, copy, modify, and distribute this software and its documentation for any purpose and without fee is hereby granted, provided that the above copyright notice appear in all copies and that both that copyright notice and this permission notice appear in supporting documentation,

and that the names of M.I.T. and the M.I.T. S.I.P.B. not be used in advertising or publicity pertaining to distribution of the software without specific, written prior permission.

M.I.T. and

the M.I.T. S.I.P.B. make no representations about the suitability of this software for any purpose. It is provided "as is" without express or implied warranty.

This package, the EXT2 filesystem utilities, are made available under the GNU Public License version 2, with the exception of the lib/ext2fs and lib/e2p libraries, which are made available under the GNU Library General Public License Version 2, the lib/uuid library which is made available under a BSD-style license and the lib/et and lib/ss libraries which are made available under an MIT-style license. Please see lib/uuid/COPYING for more details for the license for the files comprising the libuuid library, and the source file headers of the libet and libss libraries for more information.

The most recent officially distributed version can be found at <http://e2fsprogs.sourceforge.net>. If you need to make a distribution, that's the one you should use. If there is some reason why you'd like a more recent version that is still in ALPHA testing (i.e., either using the "WIP" test distributions or one from the hg or git repository from the development branch, please contact me (tytso@mit.edu)

before you ship. The release schedules for this package are flexible, if you give me enough lead time.

Theodore Ts'o
23-June-2007

GNU GENERAL PUBLIC LICENSE
Version 2, June 1991

Copyright (C) 1989, 1991 Free Software Foundation, Inc.
59 Temple Place, Suite 330, Boston, MA 02111-1307 USA
Everyone is permitted to copy and distribute verbatim copies of this license document, but changing it is not allowed.

Preamble

The licenses for most software are designed to take away your freedom to share and change it. By contrast, the GNU General Public License is intended to guarantee your freedom to share and change free software--to make sure the software is free for all its users. This General Public License applies to most of the Free Software

Foundation's software and to any other program whose authors commit to using it. (Some other Free Software Foundation software is covered by the GNU Library General Public License instead.) You can apply it to your programs, too.

When we speak of free software, we are referring to freedom, not price. Our General Public Licenses are designed to make sure that you have the freedom to distribute copies of free software (and charge for this service if you wish), that you receive source code or can get it if you want it, that you can change the software or use pieces of it in new free programs; and that you know you can do these things.

To protect your rights, we need to make restrictions that forbid anyone to deny you these rights or to ask you to surrender the rights. These restrictions translate to certain responsibilities for you if you distribute copies of the software, or if you modify it.

For example, if you distribute copies of such a program, whether gratis or for a fee, you must give the recipients all the rights that you have. You must make sure that they, too, receive or can get the source code. And you must show them these terms so they know their rights.

We protect your rights with two steps: (1) copyright the software, and (2) offer you this license which gives you legal permission to copy, distribute and/or modify the software.

Also, for each author's protection and ours, we want to make certain that everyone understands that there is no warranty for this free software. If the software is modified by someone else and passed on, we want its recipients to know that what they have is not the original, so that any problems introduced by others will not reflect on the original authors' reputations.

Finally, any free program is threatened constantly by software patents. We wish to avoid the danger that redistributors of a free program will individually obtain patent licenses, in effect making the program proprietary. To prevent this, we have made it clear that any patent must be licensed for everyone's free use or not licensed at all.

The precise terms and conditions for copying, distribution and modification follow.

GNU GENERAL PUBLIC LICENSE
TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

0. This License applies to any program or other work which contains a notice placed by the copyright holder saying it may be distributed under the terms of this General Public License. The "Program", below, refers to any such program or work, and a "work based on the Program" means either the Program or any derivative work under copyright law: that is to say, a work containing the Program or a portion of it, either verbatim or with modifications and/or translated into another language. (Hereinafter, translation is included without limitation in the term "modification".) Each licensee is addressed as "you".

Activities other than copying, distribution and modification are not covered by this License; they are outside its scope. The act of running the Program is not restricted, and the output from the Program is covered

only if its contents constitute a work based on the Program (independent of having been made by running the Program). Whether that is true depends on what the Program does.

1. You may copy and distribute verbatim copies of the Program's source code as you receive it, in any medium, provided that you conspicuously and appropriately publish on each copy an appropriate copyright notice and disclaimer of warranty; keep intact all the notices that refer to this License and to the absence of any warranty; and give any other recipients of the Program a copy of this License along with the Program.

You may charge a fee for the physical act of transferring a copy, and you may at your option offer warranty protection in exchange for a fee.

2. You may modify your copy or copies of the Program or any portion of it, thus forming a work based on the Program, and copy and distribute such modifications or work under the terms of Section 1 above, provided that you also meet all of these conditions:

- a) You must cause the modified files to carry prominent notices stating that you changed the files and the date of any change.
- b) You must cause any work that you distribute or publish, that in whole or in part contains or is derived from the Program or any part thereof, to be licensed as a whole at no charge to all third parties under the terms of this License.
- c) If the modified program normally reads commands interactively when run, you must cause it, when started running for such interactive use in the most ordinary way, to print or display an announcement including an appropriate copyright notice and a notice that there is no warranty (or else, saying that you provide

a warranty) and that users may redistribute the program under these conditions, and telling the user how to view a copy of this License. (Exception: if the Program itself is interactive but does not normally print such an announcement, your work based on the Program is not required to print an announcement.)

These requirements apply to the modified work as a whole. If identifiable sections of that work are not derived from the Program, and can be reasonably considered independent and separate works in themselves, then this License, and its terms, do not apply to those sections when you distribute them as separate works. But when you distribute the same sections as part of a whole which is a work based on the Program, the distribution of the whole must be on the terms of this License, whose permissions for other licensees extend to the entire whole, and thus to each and every part regardless of who wrote it.

Thus, it is not the intent of this section to claim rights or contest your rights to work written entirely by you; rather, the intent is to exercise the right to control the distribution of derivative or collective works based on the Program.

In addition, mere aggregation of another work not based on the Program with the Program (or with a work based on the Program) on a volume of a storage or distribution medium does not bring the other work under the scope of this License.

3. You may copy and distribute the Program (or a work based on it, under Section 2) in object code or executable form under the terms of Sections 1 and 2 above provided that you also do one of the following:

a) Accompany it with the complete corresponding machine-readable source code, which must be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange; or,

b) Accompany it with a written offer, valid for at least three years, to give any third party, for a charge no more than your cost of physically performing source distribution, a complete machine-readable copy of the corresponding source code, to be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange; or,

c) Accompany it with the information you received as to the offer to distribute corresponding source code. (This alternative is allowed only for noncommercial distribution and only if you received the program in object code or executable form with such

an offer, in accord with Subsection b above.)

The source code for a work means the preferred form of the work for making modifications to it. For an executable work, complete source code means all the source code for all modules it contains, plus any associated interface definition files, plus the scripts used to control compilation and installation of the executable. However, as a special exception, the source code distributed need not include anything that is normally distributed (in either source or binary form) with the major components (compiler, kernel, and so on) of the operating system on which the executable runs, unless that component itself accompanies the executable.

If distribution of executable or object code is made by offering access

to copy from a designated place, then offering equivalent access to copy the source code from the same place counts as distribution of the source code, even though third parties are not compelled to copy the source along with the object code.

4. You may not copy, modify, sublicense, or distribute the Program except as expressly provided under this License. Any attempt otherwise to copy, modify, sublicense or distribute the Program is void, and will automatically terminate your rights under this License. However, parties who have received copies, or rights, from you under this License will not have their licenses terminated so long as such parties remain in full compliance.

5. You are not required to accept this License, since you have not signed it. However, nothing else grants you permission to modify or distribute the Program or its derivative works. These actions are prohibited by law if you do not accept this License. Therefore, by modifying or distributing the Program (or any work based on the Program), you indicate your acceptance of this License to do so, and all its terms and conditions for copying, distributing or modifying the Program or works based on it.

6. Each time you redistribute the Program (or any work based on the Program), the recipient automatically receives a license from the original licensor to copy, distribute or modify the Program subject to these terms and conditions. You may not impose any further restrictions on the recipients' exercise of the rights granted herein. You are not responsible for enforcing compliance by third parties to this License.

7. If, as a consequence of a court judgment or allegation of patent infringement or for any other reason (not limited to patent issues),

conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot distribute so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not distribute the Program at all. For example, if a patent license would not permit royalty-free redistribution of the Program by all those who receive copies directly or indirectly through you, then the only way you could satisfy both it and this License would be to refrain entirely from distribution of the Program.

If any portion of this section is held invalid or unenforceable under any particular circumstance, the balance of the section is intended to apply and the section as a whole is intended to apply in other circumstances.

It is not the purpose of this section to induce you to infringe any patents or other property right claims or to contest validity of any such claims; this section has the sole purpose of protecting the integrity of the free software distribution system, which is implemented by public license practices. Many people have made generous contributions to the wide range of software distributed through that system in reliance on consistent application of that system; it is up to the author/donor to decide if he or she is willing to distribute software through any other system and a licensee cannot impose that choice.

This section is intended to make thoroughly clear what is believed to be a consequence of the rest of this License.

8. If the distribution and/or use of the Program is restricted in certain countries either by patents or by copyrighted interfaces, the original copyright holder who places the Program under this License may add an explicit geographical distribution limitation excluding those countries, so that distribution is permitted only in or among countries not thus excluded. In such case, this License incorporates the limitation as if written in the body of this License.

9. The Free Software Foundation may publish revised and/or new versions of the General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Program specifies a version number of this License which applies to it and "any

later version", you have the option of following the terms and conditions either of that version or of any later version published by the Free Software Foundation. If the Program does not specify a version number of this License, you may choose any version ever published by the Free Software Foundation.

10. If you wish to incorporate parts of the Program into other free programs whose distribution conditions are different, write to the author to ask for permission. For software which is copyrighted by the Free Software Foundation, write to the Free Software Foundation; we sometimes make exceptions for this. Our decision will be guided by the two goals of preserving the free status of all derivatives of our free software and of promoting the sharing and reuse of software generally.

NO WARRANTY

11. BECAUSE THE PROGRAM IS LICENSED FREE OF CHARGE, THERE IS NO WARRANTY FOR THE PROGRAM, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE PROGRAM "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE PROGRAM IS WITH YOU. SHOULD THE PROGRAM PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

12. IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY AND/OR REDISTRIBUTE THE PROGRAM AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE PROGRAM (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE PROGRAM TO OPERATE WITH ANY OTHER PROGRAMS), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Programs

If you develop a new program, and you want it to be of the greatest possible use to the public, the best way to achieve this is to make it free software which everyone can redistribute and change under these terms.

To do so, attach the following notices to the program. It is safest to attach them to the start of each source file to most effectively

convey the exclusion of warranty; and each file should have at least the "copyright" line and a pointer to where the full notice is found.

```
<one line to give the program's name and a brief idea of what it does.>  
Copyright (C) <year> <name  
of author>
```

This program is free software; you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation; either version 2 of the License, or (at your option) any later version.

This program is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details.

You should have received a copy of the GNU General Public License along with this program; if not, write to the Free Software Foundation, Inc., 59 Temple Place, Suite 330, Boston, MA 02111-1307 USA

Also add information on how to contact you by electronic and paper mail.

If the program is interactive, make it output a short notice like this when it starts in an interactive mode:

```
Gnomovision version 69, Copyright (C) year name of author  
Gnomovision comes  
with ABSOLUTELY NO WARRANTY; for details type `show w'.  
This is free software, and you are welcome to redistribute it  
under certain conditions; type `show c' for details.
```

The hypothetical commands `show w' and `show c' should show the appropriate parts of the General Public License. Of course, the commands you use may be called something other than `show w' and `show c'; they could even be mouse-clicks or menu items--whatever suits your program.

You should also get your employer (if you work as a programmer) or your school, if any, to sign a "copyright disclaimer" for the program, if necessary. Here is a sample; alter the names:

```
Yoyodyne, Inc., hereby disclaims all copyright interest in the program  
'Gnomovision' (which makes passes at compilers) written by James Hacker.
```

```
<signature of Ty Coon>, 1 April 1989  
Ty Coon, President of Vice
```

This General Public License does not permit incorporating your program into proprietary programs. If your program is a subroutine library, you may consider it more useful to permit linking proprietary applications with the library. If this is what you want to do, use the GNU Library General Public License instead of this License.

GNU LIBRARY GENERAL PUBLIC LICENSE

Version 2, June 1991

Copyright (C) 1991 Free Software Foundation, Inc.

59 Temple Place, Suite 330, Boston, MA 02111-1307 USA

Everyone is permitted to copy and distribute verbatim copies of this license document, but changing it is not allowed.

[This is the first released version of the library GPL. It is numbered 2 because it goes with version 2 of the ordinary GPL.]

Preamble

The licenses for most software are designed to take away your freedom to share and change it. By contrast, the GNU General Public Licenses are intended to guarantee your freedom to share and change free software--to make sure the software is free for all its users.

This license, the Library General Public License, applies to some specially designated Free Software Foundation software, and to any other libraries whose authors decide to use it. You can use it for your libraries, too.

When we speak of free software, we are referring to freedom, not price. Our General Public Licenses are designed to make sure that you have the freedom to distribute copies of free software (and charge for this service if you wish), that you receive source code or can get it if you want it, that you can change the software or use pieces of it in new free programs; and that you know you can do these things.

To protect your rights, we need to make restrictions that forbid anyone to deny you these rights or to ask you to surrender the rights. These restrictions translate to certain responsibilities for you if you distribute copies of the library, or if you modify it.

For example, if you distribute copies of the library, whether gratis or for a fee, you must give the recipients all the rights that we gave you. You must make sure that they, too, receive or can get the source

code. If you link a program with the library, you must provide complete object files to the recipients so that they can relink them with the library, after making changes to the library and recompiling it. And you must show them these terms so they know their rights.

Our method of protecting your rights has two steps: (1) copyright the library, and (2) offer you this license which gives you legal permission to copy, distribute and/or modify the library.

Also, for each distributor's protection, we want to make certain that everyone understands that there is no warranty for this free library. If the library is modified by someone else and passed on, we want its recipients to know that what they have is not the original version, so that any problems introduced by others will not reflect on the original authors' reputations.

Finally, any free program is threatened constantly by software patents. We wish to avoid the danger that companies distributing free software will individually obtain patent licenses, thus in effect transforming the program into proprietary software. To prevent this, we have made it clear that any patent must be licensed for everyone's free use or not licensed at all.

Most GNU software, including some libraries, is covered by the ordinary GNU General Public License, which was designed for utility programs. This license, the GNU Library General Public License, applies to certain designated libraries. This license is quite different from the ordinary one; be sure to read it in full, and don't assume that anything in it is the same as in the ordinary license.

The reason we have a separate public license for some libraries is that they blur the distinction we usually make between modifying or adding to a program and simply using it. Linking a program with a library, without changing the library, is in some sense simply using the library, and is analogous to running a utility program or application program. However, in a textual and legal sense, the linked executable is a combined work, a derivative of the original library, and the ordinary General Public License treats it as such.

Because of this blurred distinction, using the ordinary General Public License for libraries did not effectively promote software sharing, because most developers did not use the libraries. We concluded that weaker conditions might promote sharing better.

However, unrestricted linking of non-free programs would deprive the users of those programs of all benefit from the free status of the

libraries themselves. This Library General Public License is intended to permit developers of non-free programs to use free libraries, while preserving your freedom as a user of such programs to change the free libraries that are incorporated in them. (We have not seen how to achieve this as regards changes in header files, but we have achieved it as regards changes in the actual functions of the Library.) The hope is that this will lead to faster development of free libraries.

The precise terms and conditions for copying, distribution and modification follow. Pay close attention to the difference between a "work based on the library" and a "work that uses the library". The former contains code derived from the library, while the latter only works together with the library.

Note that it is possible for a library to be covered by the ordinary General Public License rather than by this special one.

GNU LIBRARY GENERAL PUBLIC LICENSE TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

0. This License Agreement applies to any software library which contains a notice placed by the copyright holder or other authorized party saying it may be distributed under the terms of this Library General Public License (also called "this License"). Each licensee is addressed as "you".

A "library" means a collection of software functions and/or data prepared so as to be conveniently linked with application programs (which use some of those functions and data) to form executables.

The "Library", below, refers to any such software library or work which has been distributed under these terms. A "work based on the Library" means either the Library or any derivative work under copyright law: that is to say, a work containing the Library or a portion of it, either verbatim or with modifications and/or translated straightforwardly into another language. (Hereinafter, translation is included without limitation in the term "modification".)

"Source code" for a work means the preferred form of the work for making modifications to it. For a library, complete source code means all the source code for all modules it contains, plus any associated interface definition files, plus the scripts used to control compilation and installation of the library.

Activities other than copying, distribution and modification are not covered by this License; they are outside its scope. The act of

running a program using the Library is not restricted, and output from such a program is covered only if its contents constitute a work based on the Library (independent of the use of the Library in a tool for writing it). Whether that is true depends on what the Library does and what the program that uses the Library does.

1. You may copy and distribute verbatim copies of the Library's complete source code as you receive it, in any medium, provided that you conspicuously and appropriately publish on each copy an appropriate copyright notice and disclaimer of warranty; keep intact all the notices that refer to this License and to the absence of any warranty; and distribute a copy of this License along with the Library.

You may charge a fee for the physical act of transferring a copy, and you may at your option offer warranty protection in exchange for a fee.

2.

You may modify your copy or copies of the Library or any portion of it, thus forming a work based on the Library, and copy and distribute such modifications or work under the terms of Section 1 above, provided that you also meet all of these conditions:

- a) The modified work must itself be a software library.
- b) You must cause the files modified to carry prominent notices stating that you changed the files and the date of any change.
- c) You must cause the whole of the work to be licensed at no charge to all third parties under the terms of this License.
- d) If a facility in the modified Library refers to a function or a table of data to be supplied by an application program that uses the facility, other than as an argument passed when the facility is invoked, then you must make a good faith effort to ensure that, in the event an application does not supply such function or table, the facility still operates, and performs whatever part of its purpose remains meaningful.

(For example, a function in a library to compute square roots has a purpose that is entirely well-defined independent of the application. Therefore, Subsection 2d requires that any application-supplied function or table used by this function must be optional: if the application does not supply it, the square root function must still compute square roots.)

These requirements apply to the modified work as a whole. If

identifiable sections of that work are not derived from the Library, and can be reasonably considered independent and separate works in themselves, then this License, and its terms, do not apply to those sections when you distribute them as separate works. But when you distribute the same sections as part of a whole which is a work based on the Library, the distribution of the whole must be on the terms of this License, whose permissions for other licensees extend to the entire whole, and thus to each and every part regardless of who wrote it.

Thus, it is not the intent of this section to claim rights or contest your rights to work written entirely by you; rather, the intent is to exercise the right to control the distribution of derivative or collective works based on the Library.

In addition, mere aggregation of another work not based on the Library with the Library (or with a work based on the Library) on a volume of a storage or distribution medium does not bring the other work under the scope of this License.

3. You may opt to apply the terms of the ordinary GNU General Public License instead of this License to a given copy of the Library. To do this, you must alter all the notices that refer to this License, so that they refer to the ordinary GNU General Public License, version 2, instead of to this License. (If a newer version than version 2 of the ordinary GNU General Public License has appeared, then you can specify that version instead if you wish.) Do not make any other change in these notices.

Once this change is made in a given copy, it is irreversible for that copy, so the ordinary GNU General Public License applies to all subsequent copies and derivative works made from that copy.

This option is useful when you wish to copy part of the code of the Library into a program that is not a library.

4. You may copy and distribute the Library (or a portion or derivative of it, under Section 2) in object code or executable form under the terms of Sections 1 and 2 above provided that you accompany it with the complete corresponding machine-readable source code, which must be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange.

If distribution of object code is made by offering access to copy from a designated place, then offering equivalent access to copy the source code from the same place satisfies the requirement to

distribute the source code, even though third parties are not compelled to copy the source along with the object code.

5. A program that contains no derivative of any portion of the Library, but is designed to work with the Library by being compiled or linked with it, is called a "work that uses the Library". Such a work, in isolation, is not a derivative work of the Library, and therefore falls outside the scope of this License.

However, linking a "work that uses the Library" with the Library creates an executable that is a derivative of the Library (because it contains portions of the Library), rather than a "work that uses the library". The executable is therefore covered by this License. Section 6 states terms for distribution of such executables.

When a "work that uses the Library" uses material from a header file that is part of the Library, the object code for the work may be a derivative work of the Library even though the source code is not. Whether this is true is especially significant if the work can be linked without the Library, or if the work is itself a library. The threshold for this to be true is not precisely defined by law.

If such an object file uses only numerical parameters, data structure layouts and accessors, and small macros and small inline functions (ten lines or less in length), then the use of the object file is unrestricted, regardless of whether it is legally a derivative work. (Executables containing this object code plus portions of the Library will still fall under Section 6.)

Otherwise, if the work is a derivative of the Library, you may distribute the object code for the work under the terms of Section 6. Any executables containing that work also fall under Section 6, whether or not they are linked directly with the Library itself.

6. As an exception to the Sections above, you may also compile or link a "work that uses the Library" with the Library to produce a work containing portions of the Library, and distribute that work under terms of your choice, provided that the terms permit modification of the work for the customer's own use and reverse engineering for debugging such modifications.

You must give prominent notice with each copy of the work that the Library is used in it and that the Library and its use are covered by this License. You must supply a copy of this License. If the work during execution displays copyright notices, you must include the

copyright notice for the Library among them, as well as a reference directing the user to the copy of this License. Also, you must do one of these things:

- a) Accompany the work with the complete corresponding machine-readable source code for the Library including whatever changes were used in the work (which must be distributed under Sections 1 and 2 above); and, if the work is an executable linked with the Library, with the complete machine-readable "work that uses the Library", as object code and/or source code, so that the user can modify the Library and then relink to produce a modified executable containing the modified Library. (It is understood that the user who changes the contents of definitions files in the Library will not necessarily be able to recompile the application to use the modified definitions.)
- b) Accompany the work with a written offer, valid for at least three years, to give the same user the materials specified in Subsection 6a, above, for a charge no more than the cost of performing this distribution.
- c) If distribution of the work is made by offering access to copy from a designated place, offer equivalent access to copy the above specified materials from the same place.
- d) Verify that the user has already received a copy of these materials or that you have already sent this user a copy.

For an executable, the required form of the "work that uses the Library" must include any data and utility programs needed for reproducing the executable from it. However, as a special exception, the source code distributed need not include anything that is normally distributed (in either source or binary form) with the major components (compiler, kernel, and so on) of the operating system on which the executable runs, unless that component itself accompanies the executable.

It may happen that this requirement contradicts the license restrictions of other proprietary libraries that do not normally accompany the operating system. Such a contradiction means you cannot use both them and the Library together in an executable that you distribute.

7. You may place library facilities that are a work based on the Library side-by-side in a single library together with other library facilities not covered by this License, and distribute such a combined

library, provided that the separate distribution of the work based on the Library and of the other library facilities is otherwise permitted, and provided that you do these two things:

- a) Accompany the combined library with a copy of the same work based on the Library, uncombined with any other library facilities. This must be distributed under the terms of the Sections above.
- b) Give prominent notice with the combined library of the fact that part of it is a work based on the Library, and explaining where to find the accompanying uncombined form of the same work.

8. You may not copy, modify, sublicense, link with, or distribute the Library except as expressly provided under this License. Any attempt otherwise to copy, modify, sublicense, link with, or distribute the Library is void, and will automatically terminate your rights under this License. However, parties who have received copies, or rights, from you under this License will not have their licenses terminated so long as such parties remain in full compliance.

9. You are not required to accept this License, since you have not signed it. However, nothing else grants you permission to modify or distribute the Library or its derivative works. These actions are prohibited by law if you do not accept this License. Therefore, by modifying or distributing the Library (or any work based on the Library), you indicate your acceptance of this License to do so, and all its terms and conditions for copying, distributing or modifying the Library or works based on it.

10. Each time you redistribute the Library (or any work based on the Library), the recipient automatically receives a license from the original licensor to copy, distribute, link with or modify the Library subject to these terms and conditions. You may not impose any further restrictions on the recipients' exercise of the rights granted herein. You are not responsible for enforcing compliance by third parties to this License.

11. If, as a consequence of a court judgment or allegation of patent infringement or for any other reason (not limited to patent issues), conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot distribute so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you

may not distribute the Library at all. For example, if a patent license would not permit royalty-free redistribution of the Library by all those who receive copies directly or indirectly through you, then the only way you could satisfy both it and this License would be to refrain entirely from distribution of the Library.

If any portion of this section is held invalid or unenforceable under any particular circumstance, the balance of the section is intended to apply, and the section as a whole is intended to apply in other circumstances.

It is not the purpose of this section to induce you to infringe any patents or other property right claims or to contest validity of any such claims; this section has the sole purpose of protecting the integrity of the free software distribution system which is implemented by public license practices. Many people have made generous contributions to the wide range of software distributed through that system in reliance on consistent application of that system; it is up to the author/donor to decide if he or she is willing to distribute software through any other system and a licensee cannot impose that choice.

This section is intended to make thoroughly clear what is believed to be a consequence of the rest of this License.

12. If the distribution and/or use of the Library is restricted in certain countries either by patents or by copyrighted interfaces, the original copyright holder who places the Library under this License may add an explicit geographical distribution limitation excluding those countries, so that distribution is permitted only in or among countries not thus excluded. In such case, this License incorporates the limitation as if written in the body of this License.

13. The Free Software Foundation may publish revised and/or new versions of the Library General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Library specifies a version number of this License which applies to it and "any later version", you have the option of following the terms and conditions either of that version or of any later version published by the Free Software Foundation. If the Library does not specify a license version number, you may choose any version ever published by the Free Software Foundation.

14. If you wish to incorporate parts of the Library into other free

programs whose distribution conditions are incompatible with these, write to the author to ask for permission. For software which is copyrighted by the Free Software Foundation, write to the Free Software

Foundation; we sometimes make exceptions for this. Our decision will be guided by the two goals of preserving the free status of all derivatives of our free software and of promoting the sharing and reuse of software generally.

NO WARRANTY

15. BECAUSE THE LIBRARY IS LICENSED FREE OF CHARGE, THERE IS NO WARRANTY FOR THE LIBRARY, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE LIBRARY "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE LIBRARY IS WITH YOU. SHOULD THE LIBRARY PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

16. IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY AND/OR REDISTRIBUTE THE LIBRARY AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE LIBRARY (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE LIBRARY TO OPERATE WITH ANY OTHER SOFTWARE), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Libraries

If you develop a new library, and you want it to be of the greatest possible use to the public, we recommend making it free software that everyone can redistribute and change. You can do so by permitting redistribution under these terms (or, alternatively, under the terms of the ordinary General Public License).

To apply these terms, attach the following notices to the library. It is safest to attach them to the start of each source file to most effectively convey the exclusion of warranty; and each file should have at least the "copyright" line and a pointer to where the full notice is found.

<one line to give the library's name and a brief idea of what it does.>

Copyright (C) <year> <name of author>

This library is free software; you can redistribute it and/or modify it under the terms of the GNU Library General Public License as published by the Free Software Foundation; either version 2 of the License, or (at your option) any later version.

This library is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU Library General Public License for more details.

You should have received a copy of the GNU Library General Public License along with this library; if not, write to the Free Software Foundation, Inc., 59 Temple Place, Suite 330, Boston, MA 02111-1307 USA

Also add information on how to contact you by electronic and paper mail.

You should also get your employer (if you work as a programmer) or your school, if any, to sign a "copyright disclaimer" for the library, if necessary. Here is a sample; alter the names:

Yoyodyne, Inc., hereby disclaims all copyright interest in the library `Frob' (a library for tweaking knobs) written by James Random Hacker.

<signature of Ty Coon>, 1 April 1990

Ty Coon, President of Vice

That's all there is to it!

This is the Debian GNU/Linux prepackaged version of the Common Error Description library. It is currently distributed together with the EXT2 file system utilities, which are otherwise packaged as "e2fsprogs".

This package was put together by Yann Dirson <dirson@debian.org>, from sources obtained from a mirror of:
tsx-11.mit.edu:/pub/linux/packages/ext2fs/

From the original distribution:

Copyright 1987, 1988 by the Student Information Processing Board of the Massachusetts Institute of Technology

Permission to use, copy, modify, and distribute this software and its documentation for any purpose and without fee is hereby granted, provided that the above copyright notice

appear in all copies and that both that copyright notice and this permission notice appear in supporting documentation, and that the names of M.I.T. and the M.I.T. S.I.P.B. not be used in advertising or publicity pertaining to distribution of the software without specific, written prior permission. M.I.T. and the M.I.T.

S.I.P.B. make no representations about the suitability of this software for any purpose. It is provided "as is" without express or implied warranty.

1.81 libcbn 2.27-3ubuntu1.6

1.81.1 Available under license :

Copyright 1992, 1993, 1994, 1997 Henry Spencer. All rights reserved. This software is not subject to any license of the American Telephone and Telegraph Company or of the Regents of the University of California.

Permission is granted to anyone to use this software for any purpose on any computer system, and to alter it and redistribute it, subject to the following restrictions:

1. The author is not responsible for the consequences of use of this software, no matter how awful, even if they arise from flaws in it.
2. The origin of this software must not be misrepresented, either by explicit claim or by omission. Since few users ever read sources, credits must appear in the documentation.
3. Altered versions must be plainly marked as such, and must not be misrepresented as being the original software. Since few users ever read sources, credits must appear in the documentation.
4. This notice may not be removed or altered.

GNU GENERAL PUBLIC LICENSE
Version 2, June 1991

Copyright (C) 1989, 1991 Free Software Foundation, Inc.,
51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA
Everyone is permitted to copy and distribute verbatim copies
of this license document, but changing it is not allowed.

Preamble

The licenses for most software are designed to take away your freedom to share and change it. By contrast, the GNU General Public License is intended to guarantee your freedom to share and change free software--to make sure the software is free for all its users. This

General Public License applies to most of the Free Software Foundation's software and to any other program whose authors commit to using it. (Some other Free Software Foundation software is covered by the GNU Lesser General Public License instead.) You can apply it to your programs, too.

When we speak of free software, we are referring to freedom, not price.

Our General Public Licenses are designed to make sure that you have the freedom to distribute copies of free software (and charge for this service if you wish), that you receive source code or can get it if you want it, that you can change the software or use pieces of it in new free programs; and that you know you can do these things.

To protect your rights, we need to make restrictions that forbid anyone to deny you these rights or to ask you to surrender the rights. These restrictions translate to certain responsibilities for you if you distribute copies of the software, or if you modify it.

For example, if you distribute copies of such a program, whether gratis or for a fee, you must give the recipients all the rights that you have. You must make sure that they, too, receive or can get the source code. And you must show them these terms so they know their rights.

We protect your rights with two steps: (1) copyright the software, and (2) offer you this license which gives you legal permission to copy, distribute and/or modify the software.

Also, for each author's protection and ours, we want to make certain that everyone understands that there is no warranty for this free software. If the software is modified by someone else and passed on, we want its recipients to know that what they have is not the original, so that any problems introduced by others will not reflect on the original authors' reputations.

Finally, any free program is threatened constantly by software patents. We wish to avoid the danger that redistributors of a free program will individually obtain patent licenses, in effect making the program proprietary. To prevent this, we have made it clear that any patent must be licensed for everyone's free use or not licensed at all.

The precise terms and conditions for copying, distribution and modification follow.

GNU GENERAL PUBLIC LICENSE
TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

0. This License applies to any program or other work which contains a notice placed by the copyright holder saying it may be distributed under the terms of this General Public License. The "Program", below, refers to any such program or work, and a "work based on the Program" means either the Program or any derivative work under copyright law: that is to say, a work containing the Program or a portion of it, either verbatim or with modifications and/or translated into another language. (Hereinafter, translation is included without limitation in the term "modification".) Each licensee is addressed as "you".

Activities other than copying, distribution and modification are not covered by this License; they are outside its scope. The act of running the Program is not restricted, and the output from the Program is covered only if its contents constitute a work based on the Program (independent of having been made by running the Program). Whether that is true depends on what the Program does.

1. You may copy and distribute verbatim copies of the Program's source code as you receive it, in any medium, provided that you conspicuously and appropriately publish on each copy an appropriate copyright notice and disclaimer of warranty; keep intact all the notices that refer to this License and to the absence of any warranty; and give any other recipients of the Program a copy of this License along with the Program.

You may charge a fee for the physical act of transferring a copy, and you may at your option offer warranty protection in exchange for a fee.

2. You may modify your copy or copies of the Program or any portion of it, thus forming a work based on the Program, and copy and distribute such modifications or work under the terms of Section 1 above, provided that you also meet all of these conditions:

a) You must cause the modified files to carry prominent notices stating that you changed the files and the date of any change.

b) You must cause any work that you distribute or publish, that in whole or in part contains or is derived from the Program or any part thereof, to be licensed as a whole at no charge to all third parties under the terms of this License.

c) If the modified program normally reads commands interactively when run, you must cause it, when started running for such interactive use in the most ordinary way, to print or display an announcement including an appropriate copyright notice and a

notice that there is no warranty (or else, saying that you provide a warranty) and that users may redistribute the program under these conditions, and telling the user how to view a copy of this License. (Exception: if the Program itself is interactive but does not normally print such an announcement, your work based on the Program is not required to print an announcement.)

These requirements apply to the modified work as a whole. If identifiable sections of that work are not derived from the Program, and can be reasonably considered independent and separate works in themselves, then this License, and its terms, do not apply to those sections when you distribute them as separate works. But when you distribute the same sections as part of a whole which is a work based on the Program, the distribution of the whole must be on the terms of this License, whose permissions for other licensees extend to the entire whole, and thus to each and every part regardless of who wrote it.

Thus, it is not the intent of this section to claim rights or contest your rights to work written entirely by you; rather, the intent is to exercise the right to control the distribution of derivative or collective works based on the Program.

In addition, mere aggregation of another work not based on the Program with the Program (or with a work based on the Program) on a volume of a storage or distribution medium does not bring the other work under the scope of this License.

3. You may copy and distribute the Program (or a work based on it, under Section 2) in object code or executable form under the terms of Sections 1 and 2 above provided that you also do one of the following:

a) Accompany it with the complete corresponding machine-readable source code, which must be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange; or,

b) Accompany it with a written offer, valid for at least three years, to give any third party, for a charge no more than your cost of physically performing source distribution, a complete machine-readable copy of the corresponding source code, to be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange; or,

c) Accompany it with the information you received as to the offer to distribute corresponding source code. (This alternative is allowed only for noncommercial distribution and only if you received the program in object code or executable form with such

an offer, in accord with Subsection b above.)

The source code for a work means the preferred form of the work for making modifications to it. For an executable work, complete source code means all the source code for all modules it contains, plus any associated interface definition files, plus the scripts used to control compilation and installation of the executable. However, as a special exception, the source code distributed need not include anything that is normally distributed (in either source or binary form) with the major components (compiler, kernel, and so on) of the operating system on which the executable runs, unless that component itself accompanies the executable.

If distribution of executable or object code is made by offering access to copy from a designated place, then offering equivalent access to copy the source code from the same place counts as distribution of the source code, even though third parties are not compelled to copy the source along with the object code.

4. You may not copy, modify, sublicense, or distribute the Program except as expressly provided under this License. Any attempt otherwise to copy, modify, sublicense or distribute the Program is void, and will automatically terminate your rights under this License. However, parties who have received copies, or rights, from you under this License will not have their licenses terminated so long as such parties remain in full compliance.

5. You are not required to accept this License, since you have not signed it. However, nothing else grants you permission to modify or distribute the Program or its derivative works. These actions are prohibited by law if you do not accept this License. Therefore, by modifying or distributing the Program (or any work based on the Program), you indicate your acceptance of this License to do so, and all its terms and conditions for copying, distributing or modifying the Program or works based on it.

6. Each time you redistribute the Program (or any work based on the Program), the recipient automatically receives a license from the original licensor to copy, distribute or modify the Program subject to these terms and conditions. You may not impose any further restrictions on the recipients' exercise of the rights granted herein. You are not responsible for enforcing compliance by third parties to this License.

7. If, as a consequence of a court judgment or allegation of patent infringement or for any other reason (not limited to patent issues),

conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot distribute so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not distribute the Program at all. For

example, if a patent license would not permit royalty-free redistribution of the Program by all those who receive copies directly or indirectly through you, then the only way you could satisfy both it and this License would be to refrain entirely from distribution of the Program.

If any portion of this section is held invalid or unenforceable under any particular circumstance, the balance of the section is intended to apply and the section as a whole is intended to apply in other circumstances.

It is not the purpose of this section to induce you to infringe any patents or other property right claims or to contest validity of any such claims; this section has the sole purpose of protecting the integrity of the free software distribution system, which is implemented by public license practices. Many people have made generous contributions to the wide range of software distributed through that system in reliance on consistent application of that system; it is up to the author/donor to decide if he or she is willing to distribute software through any other system and a licensee cannot impose that choice.

This section is intended to make thoroughly clear what is believed to be a consequence of the rest of this License.

8. If the distribution and/or use of the Program is restricted in certain countries either by patents or by copyrighted interfaces, the original copyright holder who places the Program under this License may add an explicit geographical distribution limitation excluding those countries, so that distribution is permitted only in or among countries not thus excluded. In such case, this License incorporates the limitation as if written in the body of this License.

9. The Free Software Foundation may publish revised and/or new versions of the General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Program specifies a version number of this License which applies to it and "any

later version", you have the option of following the terms and conditions either of that version or of any later version published by the Free Software Foundation. If the Program does not specify a version number of this License, you may choose any version ever published by the Free Software Foundation.

10. If you wish to incorporate parts of the Program into other free programs whose distribution conditions are different, write to the author to ask for permission. For software which is copyrighted by the Free Software Foundation, write to the Free Software Foundation; we sometimes make exceptions for this. Our decision will be guided by the two goals of preserving the free status of all derivatives of our free software and of promoting the sharing and reuse of software generally.

NO WARRANTY

11. BECAUSE THE PROGRAM IS LICENSED FREE OF CHARGE, THERE IS NO WARRANTY FOR THE PROGRAM, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE PROGRAM "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE PROGRAM IS WITH YOU. SHOULD THE PROGRAM PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

12. IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY AND/OR REDISTRIBUTE THE PROGRAM AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE PROGRAM (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE PROGRAM TO OPERATE WITH ANY OTHER PROGRAMS), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Programs

If you develop a new program, and you want it to be of the greatest possible use to the public, the best way to achieve this is to make it free software which everyone can redistribute and change under these terms.

To do so, attach the following notices to the program. It is safest to attach them to the start of each source file to most effectively

convey the exclusion of warranty; and each file should have at least the "copyright" line and a pointer to where the full notice is found.

<one line to give the program's name and a brief idea of what it does.>
Copyright (C) <year> <name of author>

This program is free software; you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation; either version 2 of the License, or (at your option) any later version.

This program is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details.

You should have received a copy of the GNU General Public License along with this program; if not, write to the Free Software Foundation, Inc., 51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA.

Also add information on how to contact you by electronic and paper mail.

If the program is interactive, make it output a short notice like this when it starts in an interactive mode:

```
Gnomovision version 69, Copyright (C) year name of author
Gnomovision comes with ABSOLUTELY NO WARRANTY; for details type `show w'.
This is free software, and you are welcome to redistribute
it
under certain conditions; type `show c' for details.
```

The hypothetical commands `show w' and `show c' should show the appropriate parts of the General Public License. Of course, the commands you use may be called something other than `show w' and `show c'; they could even be mouse-clicks or menu items--whatever suits your program.

You should also get your employer (if you work as a programmer) or your school, if any, to sign a "copyright disclaimer" for the program, if necessary. Here is a sample; alter the names:

```
Yoyodyne, Inc., hereby disclaims all copyright interest in the program
`Gnomovision' (which makes passes at compilers) written by James Hacker.
```

```
<signature of Ty Coon>, 1 April 1989
Ty Coon, President of Vice
```

This General Public License does not permit incorporating your program into

proprietary programs. If your program is a subroutine library, you may consider it more useful to permit linking proprietary applications with the library. If this is what you want to do, use the GNU Lesser General Public License instead of this License.

GNU LESSER GENERAL PUBLIC LICENSE

Version 2.1, February 1999

Copyright (C) 1991, 1999 Free Software Foundation, Inc.
51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA
Everyone is permitted to copy and distribute verbatim copies of this license document, but changing it is not allowed.

[This is the first released version of the Lesser GPL. It also counts as the successor of the GNU Library Public License, version 2, hence the version number 2.1.]

Preamble

The licenses for most software are designed to take away your freedom to share and change it. By contrast, the GNU General Public Licenses are intended to guarantee your freedom to share and change free software--to make sure the software is free for all its users.

This license, the Lesser General Public License, applies to some specially designated software packages--typically libraries--of the Free Software Foundation and other authors who decide to use it. You can use it too, but we suggest you first think carefully about whether this license or the ordinary General Public License is the better strategy to use in any particular case, based on the explanations below.

When we speak of free software, we are referring to freedom of use, not price. Our General Public Licenses are designed to make sure that you have the freedom to distribute copies of free software (and charge for this service if you wish); that you receive source code or can get it if you want it; that you can change the software and use pieces of it in new free programs; and that you are informed that you can do these things.

To protect your rights, we need to make restrictions that forbid distributors to deny you these rights or to ask you to surrender these rights. These restrictions translate to certain responsibilities for you if you distribute copies of the library or if you modify it.

For example, if you distribute copies of the library, whether gratis or for a fee, you must give the recipients all the rights that we gave

you. You must make sure that they, too, receive or can get the source code. If you link other code with the library, you must provide complete object files to the recipients, so that they can relink them with the library after making changes to the library and recompiling it. And you must show them these terms so they know their rights.

We protect your rights with a two-step method: (1) we copyright the library, and (2) we offer you this license, which gives you legal permission to copy, distribute and/or modify the library.

To protect each distributor, we want to make it very clear that there is no warranty for the free library. Also, if the library is modified by someone else and passed on, the recipients should know that what they have is not the original version, so that the original author's reputation will not be affected by problems that might be introduced by others.

Finally, software patents pose a constant threat to the existence of any free program. We wish to make sure that a company cannot effectively restrict the users of a free program by obtaining a restrictive license from a patent holder. Therefore, we insist that any patent license obtained for a version of the library must be consistent with the full freedom of use specified in this license.

Most GNU software, including some libraries, is covered by the ordinary GNU General Public License. This license, the GNU Lesser General Public License, applies to certain designated libraries, and is quite different from the ordinary General Public License. We use this license for certain libraries in order to permit linking those libraries into non-free programs.

When a program is linked with a library, whether statically or using a shared library, the combination of the two is legally speaking a combined work, a derivative of the original library. The ordinary General Public License therefore permits such linking only if the entire combination fits its criteria of freedom. The Lesser General Public License permits more lax criteria for linking other code with the library.

We call this license the "Lesser" General Public License because it does Less to protect the user's freedom than the ordinary General Public License. It also provides other free software developers Less of an advantage over competing non-free programs. These disadvantages are the reason we use the ordinary General Public License for many libraries. However, the Lesser license provides advantages in certain special circumstances.

For example, on rare occasions, there may be a special need to encourage the widest possible use of a certain library, so that it becomes a de-facto standard. To achieve this, non-free programs must be allowed to use the library. A more frequent case is that a free library does the same job as widely used non-free libraries. In this case, there is little to gain by limiting the free library to free software only, so we use the Lesser General Public License.

In other cases, permission to use a particular library in non-free programs enables a greater number of people to use a large body of free software. For example, permission to use the GNU C Library in non-free programs enables many more people to use the whole GNU operating system, as well as its variant, the GNU/Linux operating system.

Although the Lesser General Public License is Less protective of the users' freedom, it does ensure that the user of a program that is linked with the Library has the freedom and the wherewithal to run that program using a modified version of the Library.

The precise terms and conditions for copying, distribution and modification follow. Pay close attention to the difference between a "work based on the library" and a "work that uses the library". The former contains code derived from the library, whereas the latter must be combined with the library in order to run.

GNU LESSER GENERAL PUBLIC LICENSE TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

0. This License Agreement applies to any software library or other program which contains a notice placed by the copyright holder or other authorized party saying it may be distributed under the terms of this Lesser General Public License (also called "this License"). Each licensee is addressed as "you".

A "library" means a collection of software functions and/or data prepared so as to be conveniently linked with application programs (which use some of those functions and data) to form executables.

The "Library", below, refers to any such software library or work which has been distributed under these terms. A "work based on the Library" means either the Library or any derivative work under copyright law: that is to say, a work containing the Library or a portion of it, either verbatim or with modifications and/or translated straightforwardly into

another language. (Hereinafter, translation is included without limitation in the term "modification".)

"Source code" for a work means the preferred form of the work for making modifications to it. For a library, complete source code means all the source code for all modules it contains, plus any associated interface definition files, plus the scripts used to control compilation and installation of the library.

Activities other than copying, distribution and modification are not covered by this License; they are outside its scope. The act of running a program using the Library is not restricted, and output from such a program is covered only if its contents constitute a work based on the Library (independent of the use of the Library in a tool for writing it). Whether that is true depends on what the Library does and what the program that uses the Library does.

1. You may copy and distribute verbatim copies of the Library's complete source code as you receive it, in any medium, provided that you conspicuously and appropriately publish on each copy an appropriate copyright notice and disclaimer of warranty; keep intact all the notices that refer to this License and to the absence of any warranty; and distribute a copy of this License along with the Library.

You may charge a fee for the physical act of transferring a copy, and you may at your option offer warranty protection in exchange for a fee.

2. You may modify your copy or copies of the Library or any portion of it, thus forming a work based on the Library, and copy and distribute such modifications or work under the terms of Section 1 above, provided that you also meet all of these conditions:

- a) The modified work must itself be a software library.
- b) You must cause the files modified to carry prominent notices stating that you changed the files and the date of any change.
- c) You must cause the whole of the work to be licensed at no charge to all third parties under the terms of this License.
- d) If a facility in the modified Library refers to a function or a table of data to be supplied by an application program that uses the facility, other than as an argument passed when the facility is invoked, then you must make a good faith effort to ensure that,

in the event an application does not supply such function or table, the facility still operates, and performs whatever part of its purpose remains meaningful.

(For example, a function in a library to compute square roots has a purpose that is entirely well-defined independent of the application. Therefore, Subsection 2d requires that any application-supplied function or table used by this function must be optional: if the application does not supply it, the square root function must still compute square roots.)

These requirements apply to the modified work as a whole. If identifiable sections of that work are not derived from the Library, and can be reasonably considered independent and separate works in themselves, then this License, and its terms, do not apply to those sections when you distribute them as separate works. But when you distribute the same sections as part of a whole which is a work based on the Library, the distribution of the whole must be on the terms of this License, whose permissions for other licensees extend to the entire whole, and thus to each and every part regardless of who wrote it.

Thus, it is not the intent of this section to claim rights or contest your rights to work written entirely by you; rather, the intent is to exercise the right to control the distribution of derivative or collective works based on the Library.

In addition, mere aggregation of another work not based on the Library with the Library (or with a work based on the Library) on a volume of a storage or distribution medium does not bring the other work under the scope of this License.

3. You may opt to apply the terms of the ordinary GNU General Public

License instead of this License to a given copy of the Library. To do this, you must alter all the notices that refer to this License, so that they refer to the ordinary GNU General Public License, version 2, instead of to this License. (If a newer version than version 2 of the ordinary GNU General Public License has appeared, then you can specify that version instead if you wish.) Do not make any other change in these notices.

Once this change is made in a given copy, it is irreversible for that copy, so the ordinary GNU General Public License applies to all subsequent copies and derivative works made from that copy.

This option is useful when you wish to copy part of the code of

the Library into a program that is not a library.

4. You may copy and distribute the Library (or a portion or derivative of it, under Section 2) in object code or executable form under the terms of Sections 1 and 2 above provided that you accompany it with the complete corresponding machine-readable source code, which must be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange.

If distribution of object code is made by offering access to copy from a designated place, then offering equivalent access to copy the source code from the same place satisfies the requirement to distribute the source code, even though third parties are not compelled to copy the source along with the object code.

5. A program that contains no derivative of any portion of the Library, but is designed to work with the Library by being compiled or linked with it, is called a "work that uses the Library". Such a work, in isolation, is not a derivative work of the Library, and therefore falls outside the scope of this License.

However, linking a "work that uses the Library" with the Library creates an executable that is a derivative of the Library (because it contains portions of the Library), rather than a "work that uses the library". The executable is therefore covered by this License. Section 6 states terms for distribution of such executables.

When a "work that uses the Library" uses material from a header file that is part of the Library, the object code for the work may be a derivative work of the Library even though the source code is not. Whether this is true is especially significant if the work can be linked without the Library, or if the work is itself a library. The threshold for this to be true is not precisely defined by law.

If such an object file uses only numerical parameters, data structure layouts and accessors, and small macros and small inline functions (ten lines or less in length), then the use of the object file is unrestricted, regardless of whether it is legally a derivative work. (Executables containing this object code plus portions of the Library will still fall under Section 6.)

Otherwise, if the work is a derivative of the Library, you may distribute the object code for the work under the terms of Section 6. Any executables containing that work also fall under Section 6, whether or not they are linked directly with the Library itself.

6. As an exception to the Sections above, you may also combine or link a "work that uses the Library" with the Library to produce a work containing portions of the Library, and distribute that work under terms of your choice, provided that the terms permit modification of the work for the customer's own use and reverse engineering for debugging such modifications.

You must give prominent notice with each copy of the work that the Library is used in it and that the Library and its use are covered by this License. You must supply a copy of this License. If the work during execution displays copyright notices, you must include the copyright notice for the Library among them, as well as a reference directing the user to the copy of this License. Also, you must do one of these things:

- a) Accompany the work with the complete corresponding machine-readable source code for the Library including whatever changes were used in the work (which must be distributed under Sections 1 and 2 above); and, if the work is an executable linked with the Library, with the complete machine-readable "work that uses the Library", as object code and/or source code, so that the user can modify the Library and then relink to produce a modified executable containing the modified Library. (It is understood that the user who changes the contents of definitions files in the Library will not necessarily be able to recompile the application to use the modified definitions.)
- b) Use a suitable shared library mechanism for linking with the Library. A suitable mechanism is one that (1) uses at run time a copy of the library already present on the user's computer system, rather than copying library functions into the executable, and (2) will operate properly with a modified version of the library, if the user installs one, as long as the modified version is interface-compatible with the version that the work was made with.
- c) Accompany the work with a written offer, valid for at least three years, to give the same user the materials specified in Subsection 6a, above, for a charge no more than the cost of performing this distribution.
- d) If distribution of the work is made by offering access to copy from a designated place, offer equivalent access to copy the above specified materials from the same place.
- e) Verify that the user has already received a copy of these

materials or that you have already sent this user a copy.

For an executable, the required form of the "work that uses the Library" must include any data and utility programs needed for reproducing the executable from it. However, as a special exception, the materials to be distributed need not include anything that is normally

distributed (in either source or binary form) with the major components (compiler, kernel, and so on) of the operating system on which the executable runs, unless that component itself accompanies the executable.

It may happen that this requirement contradicts the license restrictions of other proprietary libraries that do not normally accompany the operating system. Such a contradiction means you cannot use both them and the Library together in an executable that you distribute.

7. You may place library facilities that are a work based on the Library side-by-side in a single library together with other library facilities not covered by this License, and distribute such a combined library, provided that the separate distribution of the work based on the Library and of the other library facilities is otherwise permitted, and provided that you do these two things:

a) Accompany the combined library with a copy of the same work based on the Library, uncombined with any other library facilities. This must be distributed under the terms of the Sections above.

b) Give prominent notice with the combined library of the fact that part of it is a work based on the Library, and explaining where to find the accompanying uncombined form of the same work.

8. You may not copy, modify, sublicense, link with, or distribute the Library except as expressly provided under this License. Any attempt otherwise to copy, modify, sublicense, link with, or distribute the Library is void, and will automatically terminate your rights under this License. However, parties who have received copies, or rights, from you under this License will not have their licenses terminated so long as such parties remain in full compliance.

9. You are not required to accept this License, since you have not signed it. However, nothing else grants you permission to modify or distribute the Library or its derivative works. These actions are prohibited by law if

you do not accept this License. Therefore, by modifying or distributing the Library (or any work based on the Library), you indicate your acceptance of this License to do so, and all its terms and conditions for copying, distributing or modifying the Library or works based on it.

10. Each time you redistribute the Library (or any work based on the Library), the recipient automatically receives a license from the original licensor to copy, distribute, link with or modify the Library subject to these terms and conditions. You may not impose any further restrictions on the recipients' exercise of the rights granted herein. You are not responsible for enforcing compliance by third parties with this License.

11. If, as a consequence of a court judgment or allegation of patent infringement or for any other reason (not limited to patent issues), conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse

you from the conditions of this License. If you cannot distribute so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not distribute the Library at all. For example, if a patent license would not permit royalty-free redistribution of the Library by all those who receive copies directly or indirectly through you, then the only way you could satisfy both it and this License would be to refrain entirely from distribution of the Library.

If any portion of this section is held invalid or unenforceable under any particular circumstance, the balance of the section is intended to apply, and the section as a whole is intended to apply in other circumstances.

It is not the purpose of this section to induce you to infringe any patents or other property right claims or to contest validity of any such claims; this section has the sole purpose of protecting the integrity of the free software distribution system

which is implemented by public license practices. Many people have made generous contributions to the wide range of software distributed through that system in reliance on consistent application of that system; it is up to the author/donor to decide if he or she is willing to distribute software through any other system and a licensee cannot impose that choice.

This section is intended to make thoroughly clear what is believed to be a consequence of the rest of this License.

12. If the distribution and/or use of the Library is restricted in

certain countries either by patents or by copyrighted interfaces, the original copyright holder who places the Library under this License may add an explicit geographical distribution limitation excluding those countries, so that distribution is permitted only in or among countries not thus excluded. In such case, this License incorporates the limitation as if written in the body of this License.

13. The Free Software Foundation may publish revised and/or new versions of the Lesser General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Library specifies a version number of this License which applies to it and "any later version", you have the option of following the terms and conditions either of that version or of any later version published by the Free Software Foundation. If the Library does not specify a license version number, you may choose any version ever published by the Free Software Foundation.

14. If you wish to incorporate parts of the Library into other free programs whose distribution conditions are incompatible with these, write to the author to ask for permission. For software which is copyrighted by the Free Software Foundation, write to the Free Software Foundation; we sometimes make exceptions for this. Our decision will be guided by the two goals of preserving the free status of all derivatives of our free software and of promoting the sharing and reuse of software generally.

NO WARRANTY

15. BECAUSE THE LIBRARY IS LICENSED FREE OF CHARGE, THERE IS NO WARRANTY FOR THE LIBRARY, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE LIBRARY "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE LIBRARY IS WITH YOU. SHOULD THE LIBRARY PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

16. IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY AND/OR REDISTRIBUTE THE LIBRARY AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR

CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE LIBRARY (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE LIBRARY TO OPERATE WITH ANY OTHER SOFTWARE), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Libraries

If you develop a new library, and you want it to be of the greatest possible use to the public, we recommend making it free software that everyone can redistribute and change. You can do so by permitting redistribution under these terms (or, alternatively, under the terms of the ordinary General Public License).

To apply these terms, attach the following notices to the library. It is safest to attach them to the start of each source file to most effectively convey the exclusion of warranty; and each file should have at least the "copyright" line and a pointer to where the full notice is found.

<one line to give the library's name and a brief idea of what it does.>
Copyright (C) <year> <name of author>

This library is free software; you can redistribute it and/or modify it under the terms of the GNU Lesser General Public License as published by the Free Software Foundation; either version 2.1 of the License, or (at your option) any later version.

This library is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU Lesser General Public License for more details.

You should have received a copy of the GNU Lesser General Public License along with this library; if not, write to the Free Software Foundation, Inc., 51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA

Also add information on how to contact you by electronic and paper mail.

You should also get your employer (if you work as a programmer) or your school, if any, to sign a "copyright disclaimer" for the library, if necessary. Here is a sample; alter the names:

Yoyodyne, Inc., hereby disclaims all copyright interest in the

library `Frob' (a library for tweaking knobs) written by James Random Hacker.

<signature of Ty Coon>, 1 April 1990

Ty Coon, President of Vice

That's all there is to it!

UNICODE, INC. LICENSE AGREEMENT - DATA FILES AND SOFTWARE

Unicode Data Files include all data files under the directories <http://www.unicode.org/Public/>, <http://www.unicode.org/reports/>, and <http://www.unicode.org/cldr/data/>. Unicode Data Files do not include PDF online code charts under the directory <http://www.unicode.org/Public/>. Software includes any source code published in the Unicode Standard or under the directories <http://www.unicode.org/Public/>, <http://www.unicode.org/reports/>, and <http://www.unicode.org/cldr/data/>.

NOTICE TO USER: Carefully read the following legal agreement. BY DOWNLOADING, INSTALLING, COPYING OR OTHERWISE USING UNICODE INC.'S DATA FILES ("DATA FILES"), AND/OR SOFTWARE ("SOFTWARE"), YOU UNEQUIVOCALLY ACCEPT, AND AGREE TO BE BOUND BY, ALL OF THE TERMS AND CONDITIONS OF THIS AGREEMENT. IF YOU DO NOT AGREE, DO NOT DOWNLOAD, INSTALL, COPY, DISTRIBUTE OR USE THE DATA FILES OR SOFTWARE.

COPYRIGHT AND PERMISSION NOTICE

Copyright 1991-2013 Unicode, Inc. All rights reserved. Distributed under the Terms of Use in <http://www.unicode.org/copyright.html>.

Permission is hereby granted, free of charge, to any person obtaining a copy of the Unicode data files and any associated documentation (the "Data Files") or Unicode software and any associated documentation (the "Software") to deal in the Data Files or Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, and/or sell copies of the Data Files or Software, and to permit persons to whom the Data Files or Software are furnished to do so, provided that (a) the above copyright notice(s) and this permission notice appear with all copies of the Data Files or Software, (b) both the above copyright notice(s) and this permission notice appear in associated documentation, and (c) there is clear notice in each modified Data File or in the Software as well as in the documentation associated with the Data File(s) or Software that the data or software has been modified.

THE DATA FILES AND SOFTWARE ARE PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT OF THIRD PARTY RIGHTS. IN NO EVENT SHALL THE COPYRIGHT HOLDER OR HOLDERS INCLUDED IN

THIS NOTICE BE LIABLE FOR ANY CLAIM, OR ANY SPECIAL INDIRECT OR CONSEQUENTIAL DAMAGES, OR ANY DAMAGES WHATSOEVER RESULTING FROM LOSS OF USE, DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE OR OTHER TORTIOUS ACTION, ARISING OUT OF OR IN CONNECTION WITH THE USE OR PERFORMANCE OF THE DATA FILES OR SOFTWARE.

Except as contained in this notice, the name of a copyright holder shall not be used in advertising or otherwise to promote the sale, use or other dealings in these Data Files or Software without prior written authorization of the copyright holder.

This file contains the copying permission notices for various files in the GNU C Library distribution that have copyright owners other than the Free Software Foundation. These notices all require that a copy of the notice be included in the accompanying documentation and be distributed with binary distributions of the code, so be sure to include this file along with any binary distributions derived from the GNU C Library.

All code incorporated from 4.4 BSD is distributed under the following license:

Copyright (C) 1991 Regents of the University of California.
All rights reserved.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

1. Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.
2. Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.
3. [This condition was removed.]
4. Neither the name of the University nor the names of its contributors may be used to endorse or promote products derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE REGENTS AND CONTRIBUTORS ``AS IS'' AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE REGENTS OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY

OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED
OF THE POSSIBILITY OF
SUCH DAMAGE.

The DNS resolver code, taken from BIND 4.9.5, is copyrighted by UC Berkeley, by Digital Equipment Corporation and by Internet Software Consortium. The DEC portions are under the following license:

Portions Copyright (C) 1993 by Digital Equipment Corporation.

Permission to use, copy, modify, and distribute this software for any purpose with or without fee is hereby granted, provided that the above copyright notice and this permission notice appear in all copies, and that the name of Digital Equipment Corporation not be used in advertising or publicity pertaining to distribution of the document or software without specific, written prior permission.

THE SOFTWARE IS PROVIDED ``AS IS" AND DIGITAL EQUIPMENT CORP. DISCLAIMS ALL WARRANTIES WITH REGARD TO THIS SOFTWARE, INCLUDING ALL IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS. IN NO EVENT SHALL DIGITAL EQUIPMENT CORPORATION BE LIABLE FOR ANY SPECIAL, DIRECT, INDIRECT, OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES WHATSOEVER RESULTING FROM LOSS OF USE, DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE OR OTHER TORTIOUS ACTION, ARISING OUT OF OR IN CONNECTION WITH THE USE OR PERFORMANCE OF THIS SOFTWARE.

The ISC portions are under the following license:

Portions Copyright (c) 1996-1999 by Internet Software Consortium.

Permission to use, copy, modify, and distribute this software for any purpose with or without fee is hereby granted, provided that the above copyright notice and this permission notice appear in all copies.

THE SOFTWARE IS PROVIDED "AS IS" AND INTERNET SOFTWARE CONSORTIUM DISCLAIMS ALL WARRANTIES WITH REGARD TO THIS SOFTWARE INCLUDING ALL IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS. IN NO EVENT SHALL INTERNET SOFTWARE CONSORTIUM BE LIABLE FOR ANY SPECIAL, DIRECT, INDIRECT, OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES WHATSOEVER RESULTING FROM LOSS OF USE, DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE OR OTHER TORTIOUS ACTION, ARISING OUT OF OR IN CONNECTION WITH THE USE OR PERFORMANCE OF THIS SOFTWARE.

The Sun RPC support (from rpcsrc-4.0) is covered by the following license:

Copyright (c) 2010, Oracle America, Inc.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

- * Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.
- * Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.
- * Neither the name of the "Oracle America, Inc." nor the names of its contributors may be used to endorse or promote products derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT HOLDER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

The following CMU license covers some of the support code for Mach, derived from Mach 3.0:

Mach Operating System
Copyright (C) 1991,1990,1989 Carnegie Mellon University
All Rights Reserved.

Permission to use, copy, modify and distribute this software and its documentation is hereby granted, provided that both the copyright notice and this permission notice appear in all copies of the software, derivative works or modified versions, and any portions thereof, and that both notices appear in supporting documentation.

CARNEGIE MELLON ALLOWS FREE USE OF THIS SOFTWARE IN ITS ``AS IS'' CONDITION. CARNEGIE MELLON DISCLAIMS ANY LIABILITY OF ANY KIND FOR ANY DAMAGES WHATSOEVER RESULTING FROM THE USE OF THIS SOFTWARE.

Carnegie Mellon requests users of this software to return to

Software Distribution Coordinator
School of Computer Science
Carnegie Mellon University
Pittsburgh PA 15213-3890

or Software.Distribution@CS.CMU.EDU any improvements or extensions that they make and grant Carnegie Mellon the rights to redistribute these changes.

The file `if_ppp.h` is under the following CMU license:

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

1. Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.
2. Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.
3. Neither the name of the University nor the names of its contributors may be used to endorse or promote products derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY CARNEGIE MELLON UNIVERSITY AND CONTRIBUTORS ``AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE UNIVERSITY OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

The following license covers the files from Intel's "Highly Optimized Mathematical Functions for Itanium" collection:

Intel License Agreement

Copyright (c) 2000, Intel Corporation

All rights reserved.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

- * Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.
- * Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.
- * The name of Intel Corporation may not be used to endorse or promote products derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL INTEL OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

The files inet/getnameinfo.c and sysdeps/posix/getaddrinfo.c are copyright (C) by Craig Metz and are distributed under the following license:

```
/* The Inner Net License,  
Version 2.00
```

The author(s) grant permission for redistribution and use in source and binary forms, with or without modification, of the software and documentation provided that the following conditions are met:

0. If you receive a version of the software that is specifically labelled as not being for redistribution (check the version message and/or README), you are not permitted to redistribute that version of the software in any way or form.
1. All terms of the all other applicable copyrights and licenses must be followed.
2. Redistributions of source code must retain the authors' copyright notice(s), this list of conditions, and the following disclaimer.

3. Redistributions in binary form must reproduce the authors' copyright notice(s), this list of conditions, and the following disclaimer in the documentation and/or other materials provided with the distribution.
4. [The copyright holder has authorized the removal of this clause.]
5. Neither the name(s)
of the author(s) nor the names of its contributors
may be used to endorse or promote products derived from this software
without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY ITS AUTHORS AND CONTRIBUTORS ``AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE AUTHORS OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

If these license terms cause you a real problem, contact the author. */

The file sunrpc/des_impl.c
is copyright Eric Young:

Copyright (C) 1992 Eric Young
Collected from libdes and modified for SECURE RPC by Martin Kuck 1994
This file is distributed under the terms of the GNU Lesser General
Public License, version 2.1 or later - see the file COPYING.LIB for details.
If you did not receive a copy of the license with this program, please
see <<http://www.gnu.org/licenses/>> to obtain a copy.

The libidn code is copyright Simon Josefsson, with portions copyright
The Internet Society, Tom Tromey and Red Hat, Inc.:

Copyright (C) 2002, 2003, 2004, 2011 Simon Josefsson

This file is part of GNU Libidn.

GNU Libidn is free software; you can redistribute it and/or
modify it under the terms of the GNU Lesser General Public
License as published by the Free Software Foundation; either
version 2.1 of the License, or (at your option) any later version.

GNU Libidn is distributed in the hope that it will be useful,
but WITHOUT ANY WARRANTY; without even the implied warranty of
MERCHANTABILITY

or FITNESS FOR A PARTICULAR PURPOSE. See the GNU Lesser General Public License for more details.

You should have received a copy of the GNU Lesser General Public License along with GNU Libidn; if not, see <<http://www.gnu.org/licenses/>>.

The following notice applies to portions of libidn/nfkc.c:

This file contains functions from GLIB, including gutf8.c and gunidecomp.c, all licensed under LGPL and copyright hold by:

Copyright (C) 1999, 2000 Tom Tromeey
Copyright 2000 Red Hat, Inc.

The following applies to portions of libidn/punycode.c and libidn/punycode.h:

This file is derived from RFC 3492bis written by Adam M. Costello.

Disclaimer and license: Regarding this entire document or any portion of it (including the pseudocode and C code), the author makes no guarantees and is not responsible for any damage resulting from its use. The author grants irrevocable permission to anyone to use, modify, and distribute it in any way that does not diminish the rights of anyone else to use, modify, and distribute it, provided that redistributed derivative works do not contain misleading author or version information. Derivative works need not be licensed under similar terms.

Copyright (C) The Internet Society (2003). All Rights Reserved.

This document and translations of it may be copied and furnished to others, and derivative works that comment on or otherwise explain it or assist in its implementation may be prepared, copied, published and distributed, in whole or in part, without restriction of any kind, provided that the above copyright notice and this paragraph are included on all such copies and derivative works. However, this document itself may not be modified in any way, such as by removing the copyright notice or references to the Internet Society or other Internet organizations, except as needed for the purpose of developing Internet standards in which case the procedures for copyrights defined in the Internet Standards process must be followed, or as required to translate it into languages other than English.

The limited permissions granted above are perpetual and will not be

revoked by the Internet Society or its successors or assigns.

This document and the information contained herein is provided on an "AS IS" basis and THE INTERNET SOCIETY AND THE INTERNET ENGINEERING TASK FORCE DISCLAIMS ALL WARRANTIES, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO ANY WARRANTY THAT THE USE OF THE INFORMATION HEREIN WILL NOT INFRINGE ANY RIGHTS OR ANY IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.

The file inet/remd.c is under a UCB copyright and the following:

Copyright (C) 1998 WIDE Project.
All rights reserved.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

1. Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.
2. Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.
3. Neither the name of the project nor the names of its contributors may be used to endorse or promote products derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE PROJECT AND CONTRIBUTORS ``AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE PROJECT OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

The file posix/runtests.c is copyright Tom Lord:

Copyright 1995 by Tom Lord

All Rights Reserved

Permission to use, copy, modify, and distribute this software and its documentation for any purpose and without fee is hereby granted,

provided that the above copyright notice appear in all copies and that both that copyright notice and this permission notice appear in supporting documentation, and that the name of the copyright holder not be used in advertising or publicity pertaining to distribution of the software without specific, written prior permission.

Tom Lord DISCLAIMS ALL WARRANTIES WITH REGARD TO THIS SOFTWARE, INCLUDING ALL IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS, IN NO EVENT SHALL TOM LORD BE LIABLE FOR ANY SPECIAL, INDIRECT OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES WHATSOEVER RESULTING FROM LOSS OF USE, DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE OR OTHER TORTIOUS ACTION, ARISING OUT OF OR IN CONNECTION WITH THE USE OR PERFORMANCE OF THIS SOFTWARE.

The posix/rxspencer tests are copyright Henry Spencer:

Copyright 1992, 1993, 1994, 1997 Henry Spencer. All rights reserved. This software is not subject to any license of the American Telephone and Telegraph Company or of the Regents of the University of California.

Permission is granted to anyone to use this software for any purpose on any computer system, and to alter it and redistribute it, subject to the following restrictions:

1. The author is not responsible for the consequences of use of this software, no matter how awful, even if they arise from flaws in it.
2. The origin of this software must not be misrepresented, either by explicit claim or by omission. Since few users ever read sources, credits must appear in the documentation.
3. Altered versions must be plainly marked as such, and must not be misrepresented as being the original software. Since few users ever read sources, credits must appear in the documentation.
4. This notice may not be removed or altered.

The file posix/PCRE.tests is copyright University of Cambridge:

Copyright (c) 1997-2003 University of Cambridge

Permission is granted to anyone to use this software for any purpose on any computer system, and to redistribute it freely, subject to the following restrictions:

1. This software is distributed in the hope that it will be useful,

but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.

2. The origin of this software must not be misrepresented, either by explicit claim or by omission. In practice, this means that if you use PCRE in software that you distribute to others, commercially or otherwise, you must put a sentence like this

Regular expression support is provided by the PCRE library package, which is open source software, written by Philip Hazel, and copyright by the University of Cambridge, England.

somewhere reasonably visible in your documentation and in any relevant files or online help data or similar. A reference to the ftp site for the source, that is, to

<ftp://ftp.csx.cam.ac.uk/pub/software/programming/pcre/>

should also be given in the documentation. However, this condition is not intended to apply to whole chains of software. If package A includes PCRE, it must acknowledge it, but if package B is software that includes package A, the condition is not imposed on package B (unless it uses PCRE independently).

3. Altered versions must be plainly marked as such, and must not be misrepresented as being the original software.
4. If PCRE is embedded in any software that is released under the GNU General Purpose Licence (GPL), or Lesser General Purpose Licence (LGPL), then the terms of that licence shall supersede any condition above with which it is incompatible.

Files

from Sun fdlibm are copyright Sun Microsystems, Inc.:

Copyright (C) 1993 by Sun Microsystems, Inc. All rights reserved.

Developed at SunPro, a Sun Microsystems, Inc. business.

Permission to use, copy, modify, and distribute this software is freely granted, provided that this notice is preserved.

Part of stdio-common/tst-printf.c is copyright C E Chew:

(C) Copyright C E Chew

Feel free to copy, use and distribute this software provided:

1. you do not pretend that you wrote it
2. you leave this copyright notice intact.

Various long double libm functions are copyright Stephen L. Moshier:

Copyright 2001 by Stephen L. Moshier <moshier@na-net.ornl.gov>

This library is free software; you can redistribute it and/or modify it under the terms of the GNU Lesser General Public License as published by the Free Software Foundation; either version 2.1 of the License, or (at your option) any later version.

This library is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU Lesser General Public License for more details.

You should have received a copy of the GNU Lesser General Public License along with this library; if not, see <<http://www.gnu.org/licenses/>>. */

1.82 libss 1.44.1-1ubuntu1.4

1.82.1 Available under license :

This package was added to the e2fsprogs debian source package by Theodore Ts'o <tytso@mit.edu> on Sat Mar 15 15:33:37 EST 2003

It is part of the main e2fsprogs distribution, which can be found at:

<http://sourceforge.net/projects/e2fsprogs>

Upstream Author: Theodore Ts'o <tytso@mit.edu>

Copyright:

Copyright (C) 1999, 2001 by Andries Brouwer
Copyright (C) 1999, 2000, 2003 by Theodore Ts'o

You are free to distribute this software under the terms of the GNU Lesser (Library) General Public License.

On Debian systems, the complete text of the GNU Lesser (Library) General Public License can be found in /usr/share/common-licenses/LGPL-2.

This is the Debian GNU/Linux prepackaged version of the static EXT2 file system consistency checker (e2fsck.static). The EXT2 utilities

were written by Theodore Ts'o <tytso@mit.edu> and Remy Card <card@masi.ibp.fr>.

Sources were obtained from <http://sourceforge.net/projects/e2fsprogs>

Packaging is Copyright (c) 2003-2006 Theodore Ts'o <tytso@mit.edu>

Copyright (c) 1997-2003 Yann Dirson <dirson@debian.org>

Copyright (c) 2001 Alcove <<http://www.alcove.com/>>

Copyright (c) 1997 Klee Dienes

Copyright (c) 1995-1996 Michael Nonweiler <mrn20@cam.ac.uk>

Upstream Author: Theodore Ts'o <tytso@mit.edu>

Copyright notice:

This package, the EXT2 filesystem utilities, is protected by the GNU General Public License.

Copyright (c) 1993, 1994, 1995, 1996, 1997, 1998, 1999, 2000, 2001, 2002, 2003, 2004, 2005, 2006, 2007, 2008 by Theodore Ts'o

On Debian GNU systems, the complete text of the GNU General Public License can be found in `~/usr/share/common-licenses/GPL-2`. Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

1. Redistributions of source code must retain the above copyright notice, and the entire permission notice in its entirety, including the disclaimer of warranties.
2. Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.
3. The name of the author may not be used to endorse or promote products derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED ``AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, ALL OF WHICH ARE HEREBY DISCLAIMED. IN NO EVENT SHALL THE AUTHOR BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL

DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF NOT ADVISED OF THE POSSIBILITY OF SUCH

DAMAGE.

This is the Debian GNU/Linux prepackaged version of the translation files of the EXT2 file system utilities. The EXT2 utilities were written by Theodore Ts'o <tytso@mit.edu> and Remy Card <card@masi.ibp.fr>.

Sources were obtained from <http://sourceforge.net/projects/e2fsprogs>

Packaging is Copyright (c) 2003-2006 Theodore Ts'o <tytso@mit.edu>

Copyright (c) 1997-2003 Yann Dirson <dirson@debian.org>

Copyright (c) 2001 Alcove <<http://www.alcove.com/>>

Copyright (c) 1997 Klee Dienes

Copyright (c) 1995-1996 Michael Nonweiler <mrn20@cam.ac.uk>

Upstream Author: Theodore Ts'o <tytso@mit.edu>

Copyright notice:

This package, the EXT2 filesystem utilities, is protected by the GNU General Public License.

Copyright (c) 1993, 1994, 1995, 1996, 1997, 1998, 1999, 2000, 2001, 2002, 2003, 2004, 2005, 2006, 2007, 2008 by Theodore Ts'o

On Debian GNU systems, the complete text of the GNU General Public License can be found in ``/usr/share/common-licenses/GPL-2'`. This package was added to the e2fsprogs debian source package by Theodore Ts'o <tytso@mit.edu> on Fri Dec 14 22:24:35 EST 2007

It is part of the main e2fsprogs distribution, which can be found at:

<http://sourceforge.net/projects/e2fsprogs>

Upstream Author: Theodore Ts'o <tytso@mit.edu>

Copyright:

Copyright (C) 1999, 2000, 2001, 2002, 2003, 2004, 2005, 2006, 2007 by Theodore Ts'o

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

1. Redistributions of source code must retain the above copyright notice, and the entire permission notice in its entirety, including the disclaimer of warranties.
2. Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the

documentation and/or other materials provided with the distribution.

3. The name of the author may not be used to endorse or promote products derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED ``AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, ALL OF WHICH ARE HEREBY DISCLAIMED. IN NO EVENT SHALL THE AUTHOR BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF NOT ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

Index: tdbsa/tdb.c

=====

--- tdbsa.orig/tdb.c

+++ tdbsa/tdb.c

@@ -4,11 +4,11 @@ Rev: 23371

Last Changed Date: 2007-06-06 20:14:06 -0400 (Wed, 06 Jun 2007)

*/

/*

- Unix SMB/CIFS implementation.
- + trivial database library - standalone version

- trivial database library - private includes

-

- Copyright (C) Andrew Tridgell 2005
- + Copyright (C) Andrew Tridgell 1999-2005
- + Copyright (C) Jeremy Allison 2000-2006
- + Copyright (C) Paul 'Rusty' Russell 2000

** NOTE! The following LGPL license applies to the tdb
** library. This does NOT imply that all of Samba is released
EXT2ED is hereby placed under the terms of the GNU General Public License.
Follows the GNU license.

Gadi Oxman, August 1995

GNU GENERAL PUBLIC LICENSE

Version 2, June 1991

Copyright (C) 1989, 1991 Free Software Foundation, Inc.

675 Mass Ave, Cambridge, MA 02139, USA

Everyone is permitted to copy and distribute verbatim copies of this license document, but changing it is not allowed.

Preamble

The licenses for most software are designed to take away your freedom to share and change it. By contrast, the GNU General Public License is intended to guarantee your freedom to share and change free software--to make sure the software is free for all its users. This General Public License applies to most of the Free Software Foundation's software and to any other program whose authors commit to using it. (Some other Free Software Foundation software is covered by the GNU Library General Public License instead.) You can apply it to your programs, too.

When we speak of free software, we are referring to freedom, not price. Our General Public Licenses are designed to make sure that you have the freedom to distribute copies of free software (and charge for this service if you wish), that you receive source code or can get it if you want it, that you can change the software or use pieces of it in new free programs; and that you know you can do these things.

To protect your rights, we need to make restrictions that forbid anyone to deny you these rights or to ask you to surrender the rights. These restrictions translate to certain responsibilities for you if you distribute copies of the software, or if you modify it.

For example, if you distribute copies of such a program, whether gratis or for a fee, you must give the recipients all the rights that you have. You must make sure that they, too, receive or can get the source code. And you must show them these terms so they know their rights.

We protect your rights with two steps: (1) copyright the software, and (2) offer you this license which gives you legal permission to copy, distribute and/or modify the software.

Also, for each author's protection and ours, we want to make certain that everyone understands that there is no warranty for this free software. If the software is modified by someone else and passed on, we want its recipients to know that what they have is not the original, so that any problems introduced by others will not reflect on the original authors' reputations.

Finally, any free program is threatened constantly by software patents. We wish to avoid the danger that redistributors of a free program will individually obtain patent licenses, in effect making the program proprietary. To prevent this, we have made it clear that any patent must be licensed for everyone's free use or not licensed at all.

The precise terms and conditions for copying, distribution and modification follow.

GNU GENERAL PUBLIC LICENSE TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

0. This License applies to any program or other work which contains a notice placed by the copyright holder saying it may be distributed under the terms of this General Public License. The "Program", below, refers to any such program or work, and a "work based on the Program" means either the Program or any derivative work under copyright law: that is to say, a work containing the Program or a portion of it, either verbatim or with modifications and/or translated into another language. (Hereinafter, translation is included without limitation in the term "modification".) Each licensee is addressed as "you".

Activities other than copying, distribution and modification are not covered by this License; they are outside its scope. The act of running the Program is not restricted, and the output from the Program is covered only if its contents constitute a work based on the Program (independent of having been made by running the Program). Whether that is true depends on what the Program does.

1. You may copy and distribute verbatim copies of the Program's source code as you receive it, in any medium, provided that you conspicuously and appropriately publish on each copy an appropriate copyright notice and disclaimer of warranty; keep intact all the notices that refer to this License and to the absence of any warranty; and give any other recipients of the Program a copy of this License along with the Program.

You may charge a fee for the physical act of transferring a copy, and you may at your option offer warranty protection in exchange for a fee.

2. You may modify your copy or copies of the Program or any portion of it, thus forming a work based on the Program, and copy and distribute such modifications or work under the terms of Section 1 above, provided that you also meet all of these conditions:

a) You

must cause the modified files to carry prominent notices stating that you changed the files and the date of any change.

b) You must cause any work that you distribute or publish, that in whole or in part contains or is derived from the Program or any part thereof, to be licensed as a whole at no charge to all third parties under the terms of this License.

c) If the modified program normally reads commands interactively when run, you must cause it, when started running for such interactive use in the most ordinary way, to print or display an announcement including an appropriate copyright notice and a notice that there is no warranty (or else, saying that you provide a warranty) and that users may redistribute the program under these conditions, and telling the user how to view a copy of this License. (Exception: if the Program itself is interactive but does not normally print such an announcement, your work based on the Program is not required to print an announcement.)

These requirements apply to the modified work as a whole. If identifiable sections of that work are not derived from the Program, and can be reasonably considered independent and separate works in themselves, then this License, and its terms, do not apply to those sections when you distribute them as separate works. But when you distribute the same sections as part of a whole which is a work based on the Program, the distribution of the whole must be on the terms of this License, whose permissions for other licensees extend to the entire whole, and thus to each and every part regardless of who wrote it.

Thus, it is not the intent of this section to claim rights or contest your rights to work written entirely by you; rather, the intent is to exercise the right to control the distribution of derivative or collective works based on the Program.

In addition, mere aggregation of another work not based on the Program with the Program (or with a work based on the Program) on a volume of a storage or distribution medium does not bring the other work under the scope of this License.

3. You may copy and distribute the Program (or a work based on it, under Section 2) in object code or executable form under the terms of Sections 1 and 2 above provided that you also do one of the following:

a) Accompany it with the complete corresponding machine-readable source code, which must be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange; or,

b) Accompany it with a written offer, valid for at least three years, to give any third party, for a charge no more than your cost of physically performing source distribution, a complete machine-readable copy of the corresponding source code, to be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange; or,

c) Accompany it with the information you received as to the offer to distribute corresponding source code. (This alternative is allowed only for noncommercial distribution and only if you received the program in object code or executable form with such an offer, in accord with Subsection b above.)

The source code for a work means the preferred form of the work for making modifications to it. For an executable work, complete source code means all the source code for all modules it contains, plus any associated interface definition files, plus the scripts used to control compilation and installation of the executable. However, as a special exception, the source code distributed need not include anything that is normally distributed (in either source or binary form) with the major components (compiler, kernel, and so on) of the operating system on which the executable runs, unless that component itself accompanies the executable.

If distribution of executable or object code is made by offering access

to copy from a designated place, then offering equivalent access to copy the source code from the same place counts as distribution of the source code, even though third parties are not compelled to copy the source along with the object code.

4. You may not copy, modify, sublicense, or distribute the Program except as expressly provided under this License. Any attempt otherwise to copy, modify, sublicense or distribute the Program is void, and will automatically terminate your rights under this License. However, parties who have received copies, or rights, from you under this License will not have their licenses terminated so long as such parties remain in full compliance.

5. You are not required to accept this License, since you have not signed it. However, nothing else grants you permission to modify or distribute the Program or its derivative works. These actions are prohibited by law if you do not accept this License. Therefore, by modifying or distributing the Program

(or any work based on the Program), you indicate your acceptance of this License to do so, and

all its terms and conditions for copying, distributing or modifying the Program or works based on it.

6. Each time you redistribute the Program (or any work based on the Program), the recipient automatically receives a license from the original licensor to copy, distribute or modify the Program subject to these terms and conditions. You may not impose any further restrictions on the recipients' exercise of the rights granted herein. You are not responsible for enforcing compliance by third parties to this License.

7. If, as a consequence of a court judgment or allegation of patent infringement or for any other reason (not limited to patent issues), conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot distribute so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not distribute the Program at all. For example, if a patent license would not permit royalty-free redistribution of the Program by all those who receive copies directly or indirectly through you, then the only way you could satisfy both it and this License would be to refrain entirely from distribution of the Program.

If any portion of this section is held invalid or unenforceable under any particular circumstance, the balance of the section is intended to apply and the section as a whole is intended to apply in other circumstances.

It is not the purpose of this section to induce you to infringe any patents or other property right claims or to contest validity of any such claims; this section has the sole purpose of protecting the integrity of the free software distribution system, which is implemented by public license practices. Many people have made generous contributions to the wide range of software distributed through that system in reliance on consistent application of that system; it is up to the author/donor to decide if he or she is willing to distribute software through any other system and a licensee cannot impose that choice.

This section is intended to make thoroughly clear what is believed to be a consequence of the rest of this License.

8. If the distribution and/or use of the Program is restricted in certain countries either by patents or by copyrighted interfaces, the original copyright holder who places the Program under this License

may add an explicit geographical distribution limitation excluding those countries, so that distribution is permitted only in or among countries not thus excluded. In such case, this License incorporates the limitation as if written in the body of this License.

9. The Free Software Foundation may publish revised and/or new versions of the General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Program specifies a version number of this License which applies to it and "any later version", you have the option of following the terms and conditions either of that version or of any later version published by the Free Software Foundation. If the Program does not specify a version number of this License, you may choose any version ever published by the Free Software Foundation.

10. If you wish to incorporate parts of the Program into other free programs whose distribution conditions are different, write to the author to ask for permission. For software which is copyrighted by the Free Software Foundation, write to the Free Software Foundation; we sometimes make exceptions for this. Our decision will be guided by the two goals of preserving the free status of all derivatives of our free software and of promoting the sharing and reuse of software generally.

NO WARRANTY

11. BECAUSE THE PROGRAM IS LICENSED FREE OF CHARGE, THERE IS NO WARRANTY FOR THE PROGRAM, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE PROGRAM "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE PROGRAM IS WITH YOU. SHOULD THE PROGRAM PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

12. IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY AND/OR REDISTRIBUTE THE PROGRAM AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE PROGRAM (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE PROGRAM TO OPERATE WITH ANY OTHER

PROGRAMS), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

END OF TERMS AND CONDITIONS

Appendix: How to Apply These Terms to Your New Programs

If you develop a new program, and you want it to be of the greatest possible use to the public, the best way to achieve this is to make it free software which everyone can redistribute and change under these terms.

To do so, attach the following notices to the program. It is safest to attach them to the start of each source file to most effectively convey the exclusion of warranty; and each file should have at least the "copyright" line and a pointer to where the full notice is found.

```
<one line to give the program's name and a brief idea of what it does.>  
Copyright (C) 19yy <name of author>
```

```
This program is free software; you can redistribute it and/or modify  
it under the terms of the GNU General Public License as published by  
the Free Software Foundation; either version 2 of the License, or  
(at your option) any later version.
```

```
This program is distributed in the hope that it will be useful,  
but WITHOUT ANY WARRANTY; without even the implied warranty of  
MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the  
GNU General Public License for more details.
```

```
You should have received a copy of the GNU General Public License  
along with this program; if not, write to the Free Software  
Foundation, Inc., 675 Mass Ave, Cambridge, MA 02139, USA.
```

Also add information on how to contact you by electronic and paper mail.

If the program is interactive, make it output a short notice like this when it starts in an interactive mode:

```
Gnomovision version 69, Copyright (C) 19yy name of author  
Gnomovision comes with ABSOLUTELY NO WARRANTY;  
for details type `show w'.  
This is free software, and you are welcome to redistribute it  
under certain conditions; type `show c' for details.
```

The hypothetical commands `show w' and `show c' should show the appropriate parts of the General Public License. Of course, the commands you use may be called something other than `show w' and `show c'; they could even be mouse-clicks or menu items--whatever suits your program.

You should also get your employer (if you work as a programmer) or your school, if any, to sign a "copyright disclaimer" for the program, if necessary. Here is a sample; alter the names:

Yoyodyne, Inc., hereby disclaims all copyright interest in the program
'Gnomovision' (which makes passes at compilers) written by James Hacker.

<signature of Ty Coon>, 1 April 1989
Ty Coon, President of Vice

This General Public License does not permit incorporating your program into proprietary programs. If your program is a subroutine library, you may consider

it more useful to permit linking proprietary applications with the library. If this is what you want to do, use the GNU Library General Public License instead of this License.

This is the Debian GNU/Linux prepackaged version of the EXT2 file system utilities (e2fsck, mke2fs, etc.). The EXT2 utilities were written by Theodore Ts'o <tytso@mit.edu> and Remy Card <card@masi.ibp.fr>.

Sources were obtained from <http://sourceforge.net/projects/e2fsprogs>

Packaging is Copyright (c) 2003-2007 Theodore Ts'o <tytso@mit.edu>
Copyright (c) 1997-2003 Yann Dirson <dirson@debian.org>
Copyright (c) 2001 Alcove <<http://www.alcove.com/>>
Copyright (c) 1997 Klee Dienes
Copyright (c) 1995-1996 Michael Nonweiler <mrn20@cam.ac.uk>

Upstream Author: Theodore Ts'o <tytso@mit.edu>

Copyright notice:

This package, the EXT2 filesystem utilities, are made available under the GNU General Public License version 2, with the exception of the lib/ext2fs and lib/e2p libraries, which are made available under the GNU Library General Public License Version 2, the lib/uuid library which is made available under a BSD-style license and the lib/et and lib/ss libraries which are made available under an MIT-style license.

Copyright (c) 1993, 1994, 1995, 1996, 1997, 1998, 1999, 2000, 2001, 2002, 2003, 2004, 2005, 2006, 2007, 2008 by Theodore Ts'o

On Debian GNU systems, the complete text of the GNU General Public License can be found in `/usr/share/common-licenses/GPL-2`. The complete text of the GNU Library General Public License can be found in `/usr/share/common-licenses/LGPL-2`.

The license used for lib/et and lib/ss libraries is:

Copyright 1987 by the Student Information Processing Board
of the Massachusetts Institute of Technology

Permission to use, copy, modify, and distribute this software and its documentation for any purpose is hereby granted, provided that the names of M.I.T. and the M.I.T. S.I.P.B. not be used in advertising or publicity pertaining to distribution of the software without specific, written prior permission. M.I.T. and the M.I.T. S.I.P.B. make no representations about the suitability of this software for any purpose. It is provided "as is" without express or implied warranty.

The license used for lib/uuid is:

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

1. Redistributions of source code must retain the above copyright notice, and the entire permission notice in its entirety, including the disclaimer of warranties.
2. Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.
3. The name of the author may not be used to endorse or promote products derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED ``AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, ALL OF WHICH ARE HEREBY DISCLAIMED. IN NO EVENT SHALL THE AUTHOR BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF NOT ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

This package was added to the e2fsprogs debian source package by Theodore Ts'o <tytso@mit.edu> on Sat Mar 15 15:33:37 EST 2003

It is part of the main e2fsprogs distribution, which can be found at:

<http://sourceforge.net/projects/e2fsprogs>

Upstream Author: Theodore Ts'o <tytso@mit.edu>

Copyright:

Copyright (C) 1999, 2000, 2003, 2004 by Theodore Ts'o

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

1. Redistributions of source code must retain the above copyright notice, and the entire permission notice in its entirety, including the disclaimer of warranties.
2. Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.
3. The name of the author may not be used to endorse or promote products derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED ``AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, ALL OF WHICH ARE HEREBY DISCLAIMED. IN NO EVENT SHALL THE AUTHOR BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF NOT ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

#

This is a Makefile stub which handles the creation of BSD shared
libraries.

#

In order to use this stub, the following makefile variables must be defined.

#

BSDLIB_VERSION = 1.0

BSDLIB_IMAGE = libce

BSDLIB_MYDIR = et

BSDLIB_INSTALL_DIR = \$(SHLIBDIR)

#

all:: image

real-subdirs:: Makefile

@echo " MKDIR pic"

@mkdir -p pic

BSD_LIB = \$(BSDLIB_IMAGE).so.\$(BSDLIB_VERSION)

BSDLIB_PIC_FLAG = -fpic

image: \$(BSD_LIB)

\$(BSD_LIB): \$(OBJS)

(cd pic; ld -Bshareable -o \$(BSD_LIB) \$(LDFLAGS_SHLIB) \$(OBJS))

\$(MV) pic/\$(BSD_LIB) .

\$(RM) -f ../\$(BSD_LIB)

(cd ..; \$(LN) \$(LINK_BUILD_FLAGS) \

`echo \$(my_dir) | sed -e 's/lib/;`"/\$(BSD_LIB) \$(BSD_LIB))

install-shlibs install:: \$(BSD_LIB)

@echo " INSTALL_PROGRAM \$(BSDLIB_INSTALL_DIR)/\$(BSD_LIB)"

@\$(INSTALL_PROGRAM) \$(BSD_LIB) \

\$(DESTDIR)\$ (BSDLIB_INSTALL_DIR)/\$(BSD_LIB)

@-\$(LDCONFIG)

install-strip: install

install-shlibs-strip: install-shlibs

uninstall-shlibs uninstall::

\$(RM) -f \$(DESTDIR)\$ (BSDLIB_INSTALL_DIR)/\$(BSD_LIB)

clean::

\$(RM)

-rf pic

\$(RM) -f \$(BSD_LIB)

\$(RM) -f ../\$(BSD_LIB)

This is the Debian GNU/Linux prepackaged version of the ss command-line interface parsing library. It is currently distributed together with the EXT2 file system utilities, which are otherwise packaged as "e2fsprogs".

This package was put together by Yann Dirson <dirson@debian.org>, from sources obtained from a mirror of:
tsx-11.mit.edu:/pub/linux/packages/ext2fs/

From the original distribution:

Copyright 1987, 1988 by the Student Information Processing Board

of the Massachusetts Institute of Technology

Permission to use, copy, modify, and distribute this software and its documentation for any purpose and without fee is hereby granted, provided that the above copyright notice appear in all copies and that both that copyright notice and this permission notice appear in supporting documentation, and that the names of M.I.T. and the M.I.T. S.I.P.B. not be used in advertising or publicity pertaining to distribution of the software without specific, written prior permission.

M.I.T. and

the M.I.T. S.I.P.B. make no representations about the suitability of this software for any purpose. It is provided "as is" without express or implied warranty.

This package, the EXT2 filesystem utilities, are made available under the GNU Public License version 2, with the exception of the lib/ext2fs and lib/e2p libraries, which are made available under the GNU Library General Public License Version 2, the lib/uuid library which is made available under a BSD-style license and the lib/et and lib/ss libraries which are made available under an MIT-style license. Please see lib/uuid/COPYING for more details for the license for the files comprising the libuuid library, and the source file headers of the libet and libss libraries for more information.

The most recent officially distributed version can be found at <http://e2fsprogs.sourceforge.net>. If you need to make a distribution, that's the one you should use. If there is some reason why you'd like a more recent version that is still in ALPHA testing (i.e., either using the "WIP" test distributions or one from the hg or git repository from the development branch, please contact me (tytso@mit.edu)

before you ship. The release schedules for this package are flexible, if you give me enough lead time.

Theodore Ts'o

23-June-2007

GNU GENERAL PUBLIC LICENSE

Version 2, June 1991

Copyright (C) 1989, 1991 Free Software Foundation, Inc.

59 Temple Place, Suite 330, Boston, MA 02111-1307 USA

Everyone is permitted to copy and distribute verbatim copies of this license document, but changing it is not allowed.

Preamble

The licenses for most software are designed to take away your freedom to share and change it. By contrast, the GNU General Public License is intended to guarantee your freedom to share and change free software--to make sure the software is free for all its users. This General Public License applies to most of the Free Software Foundation's software and to any other program whose authors commit to using it. (Some other Free Software Foundation software is covered by the GNU Library General Public License instead.) You can apply it to your programs, too.

When we speak of free software, we are referring to freedom, not price. Our General Public Licenses are designed to make sure that you have the freedom to distribute copies of free software (and charge for this service if you wish), that you receive source code or can get it if you want it, that you can change the software or use pieces of it in new free programs; and that you know you can do these things.

To protect your rights, we need to make restrictions that forbid anyone to deny you these rights or to ask you to surrender the rights. These restrictions translate to certain responsibilities for you if you distribute copies of the software, or if you modify it.

For example, if you distribute copies of such a program, whether gratis or for a fee, you must give the recipients all the rights that you have. You must make sure that they, too, receive or can get the source code. And you must show them these terms so they know their rights.

We protect your rights with two steps: (1) copyright the software, and (2) offer you this license which gives you legal permission to copy, distribute and/or modify the software.

Also, for each author's protection and ours, we want to make certain that everyone understands that there is no warranty for this free software. If the software is modified by someone else and passed on, we want its recipients to know that what they have is not the original, so that any problems introduced by others will not reflect on the original authors' reputations.

Finally, any free program is threatened constantly by software patents. We wish to avoid the danger that redistributors of a free program will individually obtain patent licenses, in effect making the program proprietary. To prevent this, we have made it clear that any patent must be licensed for everyone's free use or not licensed at all.

The precise terms and conditions for copying, distribution and modification follow.

GNU GENERAL PUBLIC LICENSE
TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

0. This License applies to any program or other work which contains a notice placed by the copyright holder saying it may be distributed under the terms of this General Public License. The "Program", below, refers to any such program or work, and a "work based on the Program" means either the Program or any derivative work under copyright law: that is to say, a work containing the Program or a portion of it, either verbatim or with modifications and/or translated into another language. (Hereinafter, translation is included without limitation in the term "modification".) Each licensee is addressed as "you".

Activities other than copying, distribution and modification are not covered by this License; they are outside its scope. The act of running the Program is not restricted, and the output from the Program is covered

only if its contents constitute a work based on the Program (independent of having been made by running the Program). Whether that is true depends on what the Program does.

1. You may copy and distribute verbatim copies of the Program's source code as you receive it, in any medium, provided that you conspicuously and appropriately publish on each copy an appropriate copyright notice and disclaimer of warranty; keep intact all the notices that refer to this License and to the absence of any warranty; and give any other recipients of the Program a copy of this License along with the Program.

You may charge a fee for the physical act of transferring a copy, and you may at your option offer warranty protection in exchange for a fee.

2. You may modify your copy or copies of the Program or any portion of it, thus forming a work based on the Program, and copy and distribute such modifications or work under the terms of Section 1 above, provided that you also meet all of these conditions:

a) You must cause the modified files to carry prominent notices stating that you changed the files and the date of any change.

b) You must cause any work that you distribute or publish, that in whole or in part contains or is derived from the Program or any part thereof, to be licensed as a whole at no charge to all third

parties under the terms of this License.

c) If the modified program normally reads commands interactively when run, you must cause it, when started running for such interactive use in the most ordinary way, to print or display an announcement including an appropriate copyright notice and a notice that there is no warranty (or else, saying that you provide a warranty) and that users may redistribute the program under these conditions, and telling the user how to view a copy of this License. (Exception: if the Program itself is interactive but does not normally print such an announcement, your work based on the Program is not required to print an announcement.)

These requirements apply to the modified work as a whole. If identifiable sections of that work are not derived from the Program, and can be reasonably considered independent and separate works in themselves, then this License, and its terms, do not apply to those sections when you distribute them as separate works. But when you distribute the same sections as part of a whole which is a work based on the Program, the distribution of the whole must be on the terms of this License, whose permissions for other licensees extend to the entire whole, and thus to each and every part regardless of who wrote it.

Thus, it is not the intent of this section to claim rights or contest your rights to work written entirely by you; rather, the intent is to exercise the right to control the distribution of derivative or collective works based on the Program.

In addition, mere aggregation of another work not based on the Program with the Program (or with a work based on the Program) on a volume of a storage or distribution medium does not bring the other work under the scope of this License.

3. You may copy and distribute the Program (or a work based on it, under Section 2) in object code or executable form under the terms of Sections 1 and 2 above provided that you also do one of the following:

- a) Accompany it with the complete corresponding machine-readable source code, which must be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange; or,
- b) Accompany it with a written offer, valid for at least three years, to give any third party, for a charge no more than your cost of physically performing source distribution, a complete machine-readable copy of the corresponding source code, to be distributed under the terms of Sections 1 and 2 above on a medium

customarily used for software interchange; or,

c) Accompany it with the information you received as to the offer to distribute corresponding source code. (This alternative is allowed only for noncommercial distribution and only if you received the program in object code or executable form with such an offer, in accord with Subsection b above.)

The source code for a work means the preferred form of the work for making modifications to it. For an executable work, complete source code means all the source code for all modules it contains, plus any associated interface definition files, plus the scripts used to control compilation and installation of the executable. However, as a special exception, the source code distributed need not include anything that is normally distributed (in either source or binary form) with the major components (compiler, kernel, and so on) of the operating system on which the executable runs, unless that component itself accompanies the executable.

If distribution of executable or object code is made by offering access to copy from a designated place, then offering equivalent access to copy the source code from the same place counts as distribution of the source code, even though third parties are not compelled to copy the source along with the object code.

4. You may not copy, modify, sublicense, or distribute the Program except as expressly provided under this License. Any attempt otherwise to copy, modify, sublicense or distribute the Program is void, and will automatically terminate your rights under this License. However, parties who have received copies, or rights, from you under this License will not have their licenses terminated so long as such parties remain in full compliance.

5. You are not required to accept this License, since you have not signed it. However, nothing else grants you permission to modify or distribute the Program or its derivative works. These actions are prohibited by law if you do not accept this License. Therefore, by modifying or distributing the Program (or any work based on the Program), you indicate your acceptance of this License to do so, and all its terms and conditions for copying, distributing or modifying the Program or works based on it.

6. Each time you redistribute the Program (or any work based on the Program), the recipient automatically receives a license from the original licensor to copy, distribute or modify the Program subject to

these terms and conditions. You may not impose any further restrictions on the recipients' exercise of the rights granted herein. You are not responsible for enforcing compliance by third parties to this License.

7. If, as a consequence of a court judgment or allegation of patent infringement or for any other reason (not limited to patent issues), conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot distribute so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not distribute the Program at all. For example, if a patent license would not permit royalty-free redistribution of the Program by all those who receive copies directly or indirectly through you, then the only way you could satisfy both it and this License would be to refrain entirely from distribution of the Program.

If any portion of this section is held invalid or unenforceable under any particular circumstance, the balance of the section is intended to apply and the section as a whole is intended to apply in other circumstances.

It is not the purpose of this section to induce you to infringe any patents or other property right claims or to contest validity of any such claims; this section has the sole purpose of protecting the integrity of the free software distribution system, which is implemented by public license practices. Many people have made generous contributions to the wide range of software distributed through that system in reliance on consistent application of that system; it is up to the author/donor to decide if he or she is willing to distribute software through any other system and a licensee cannot impose that choice.

This section is intended to make thoroughly clear what is believed to be a consequence of the rest of this License.

8. If the distribution and/or use of the Program is restricted in certain countries either by patents or by copyrighted interfaces, the original copyright holder who places the Program under this License may add an explicit geographical distribution limitation excluding those countries, so that distribution is permitted only in or among countries not thus excluded. In such case, this License incorporates the limitation as if written in the body of this License.

9. The Free Software Foundation may publish revised and/or new versions

of the General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Program specifies a version number of this License which applies to it and "any later version", you have the option of following the terms and conditions either of that version or of any later version published by the Free Software Foundation. If the Program does not specify a version number of this License, you may choose any version ever published by the Free Software Foundation.

10. If you wish to incorporate parts of the Program into other free programs whose distribution conditions are different, write to the author to ask for permission. For software which is copyrighted by the Free Software Foundation, write to the Free Software Foundation; we sometimes make exceptions for this. Our decision will be guided by the two goals of preserving the free status of all derivatives of our free software and of promoting the sharing and reuse of software generally.

NO WARRANTY

11. BECAUSE THE PROGRAM IS LICENSED FREE OF CHARGE, THERE IS NO WARRANTY FOR THE PROGRAM, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE PROGRAM "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE PROGRAM IS WITH YOU. SHOULD THE PROGRAM PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

12. IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY AND/OR REDISTRIBUTE THE PROGRAM AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE PROGRAM (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE PROGRAM TO OPERATE WITH ANY OTHER PROGRAMS), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Programs

If you develop a new program, and you want it to be of the greatest possible use to the public, the best way to achieve this is to make it free software which everyone can redistribute and change under these terms.

To do so, attach the following notices to the program. It is safest to attach them to the start of each source file to most effectively convey the exclusion of warranty; and each file should have at least the "copyright" line and a pointer to where the full notice is found.

```
<one line to give the program's name and a brief idea of what it does.>  
Copyright (C) <year> <name  
of author>
```

This program is free software; you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation; either version 2 of the License, or (at your option) any later version.

This program is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details.

You should have received a copy of the GNU General Public License along with this program; if not, write to the Free Software Foundation, Inc., 59 Temple Place, Suite 330, Boston, MA 02111-1307 USA

Also add information on how to contact you by electronic and paper mail.

If the program is interactive, make it output a short notice like this when it starts in an interactive mode:

```
Gnomovision version 69, Copyright (C) year name of author  
Gnomovision comes  
with ABSOLUTELY NO WARRANTY; for details type `show w'.  
This is free software, and you are welcome to redistribute it  
under certain conditions; type `show c' for details.
```

The hypothetical commands `show w' and `show c' should show the appropriate parts of the General Public License. Of course, the commands you use may be called something other than `show w' and `show c'; they could even be mouse-clicks or menu items--whatever suits your program.

You should also get your employer (if you work as a programmer) or your school, if any, to sign a "copyright disclaimer" for the program, if necessary. Here is a sample; alter the names:

Yoyodyne, Inc., hereby disclaims all copyright interest in the program
'Gnomovision' (which makes passes at compilers) written by James Hacker.

<signature of Ty Coon>, 1 April 1989
Ty Coon, President of Vice

This General Public License does not permit incorporating your program into
proprietary programs. If your program is a subroutine
library, you may
consider it more useful to permit linking proprietary applications with the
library. If this is what you want to do, use the GNU Library General
Public License instead of this License.

GNU LIBRARY GENERAL PUBLIC LICENSE
Version 2, June 1991

Copyright (C) 1991 Free Software Foundation, Inc.
59 Temple Place, Suite 330, Boston, MA 02111-1307 USA
Everyone is permitted to copy and distribute verbatim copies
of this license document, but changing it is not allowed.

[This is the first released version of the library GPL. It is
numbered 2 because it goes with version 2 of the ordinary GPL.]

Preamble

The licenses for most software are designed to take away your
freedom to share and change it. By contrast, the GNU General Public
Licenses are intended to guarantee your freedom to share and change
free software--to make sure the software is free for all its users.

This license, the Library General Public License, applies to some
specially designated Free Software Foundation software, and to any
other libraries whose authors decide to use it. You can use it for
your libraries, too.

When we speak of free software, we are referring to freedom, not
price. Our General Public Licenses are designed to make sure that you
have the freedom to distribute copies of free software (and charge for
this service if you wish), that you receive source code or can get it
if you want it, that you can change the software or use pieces of it
in new free programs; and that you know you can do these things.

To protect your rights, we need to make restrictions that forbid
anyone to deny you these rights or to ask you to surrender the rights.

These restrictions translate to certain responsibilities for you if you distribute copies of the library, or if you modify it.

For example, if you distribute copies of the library, whether gratis or for a fee, you must give the recipients all the rights that we gave you. You must make sure that they, too, receive or can get the source code. If you link a program with the library, you must provide complete object files to the recipients so that they can relink them with the library, after making changes to the library and recompiling it. And you must show them these terms so they know their rights.

Our method of protecting your rights has two steps: (1) copyright the library, and (2) offer you this license which gives you legal permission to copy, distribute and/or modify the library.

Also, for each distributor's protection, we want to make certain that everyone understands that there is no warranty for this free library. If the library is modified by someone else and passed on, we want its recipients to know that what they have is not the original version, so that any problems introduced by others will not reflect on the original authors' reputations.

Finally, any free program is threatened constantly by software patents. We wish to avoid the danger that companies distributing free software will individually obtain patent licenses, thus in effect transforming the program into proprietary software. To prevent this, we have made it clear that any patent must be licensed for everyone's free use or not licensed at all.

Most GNU software, including some libraries, is covered by the ordinary GNU General Public License, which was designed for utility programs. This license, the GNU Library General Public License, applies to certain designated libraries. This license is quite different from the ordinary one; be sure to read it in full, and don't assume that anything in it is the same as in the ordinary license.

The reason we have a separate public license for some libraries is that they blur the distinction we usually make between modifying or adding to a program and simply using it. Linking a program with a library, without changing the library, is in some sense simply using the library, and is analogous to running a utility program or application program. However, in a textual and legal sense, the linked executable is a combined work, a derivative of the original library, and the ordinary General Public License treats it as such.

Because of this blurred distinction, using the ordinary General Public License for libraries did not effectively promote software sharing, because most developers did not use the libraries. We concluded that weaker conditions might promote sharing better.

However, unrestricted linking of non-free programs would deprive the users of those programs of all benefit from the free status of the libraries themselves. This Library General Public License is intended to permit developers of non-free programs to use free libraries, while preserving your freedom as a user of such programs to change the free libraries that are incorporated in them. (We have not seen how to achieve this as regards changes in header files, but we have achieved it as regards changes in the actual functions of the Library.) The hope is that this will lead to faster development of free libraries.

The precise terms and conditions for copying, distribution and modification follow. Pay close attention to the difference between a "work based on the library" and a "work that uses the library". The former contains code derived from the library, while the latter only works together with the library.

Note that it is possible for a library to be covered by the ordinary General Public License rather than by this special one.

GNU LIBRARY GENERAL PUBLIC LICENSE TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

0. This License Agreement applies to any software library which contains a notice placed by the copyright holder or other authorized party saying it may be distributed under the terms of this Library General Public License (also called "this License"). Each licensee is addressed as "you".

A "library" means a collection of software functions and/or data prepared so as to be conveniently linked with application programs (which use some of those functions and data) to form executables.

The "Library", below, refers to any such software library or work which has been distributed under these terms. A "work based on the Library" means either the Library or any derivative work under copyright law: that is to say, a work containing the Library or a portion of it, either verbatim or with modifications and/or translated straightforwardly into another language. (Hereinafter, translation is included without limitation in the term "modification".)

"Source code" for a work means the preferred form of the work for making modifications to it. For a library, complete source code means

all the source code for all modules it contains, plus any associated interface definition files, plus the scripts used to control compilation and installation of the library.

Activities other than copying, distribution and modification are not covered by this License; they are outside its scope. The act of running a program using the Library is not restricted, and output from such a program is covered only if its contents constitute a work based on the Library (independent of the use of the Library in a tool for writing it). Whether that is true depends on what the Library does and what the program that uses the Library does.

1. You may copy and distribute verbatim copies of the Library's complete source code as you receive it, in any medium, provided that you conspicuously and appropriately publish on each copy an appropriate copyright notice and disclaimer of warranty; keep intact all the notices that refer to this License and to the absence of any warranty; and distribute a copy of this License along with the Library.

You may charge a fee for the physical act of transferring a copy, and you may at your option offer warranty protection in exchange for a fee.

2.

You may modify your copy or copies of the Library or any portion of it, thus forming a work based on the Library, and copy and distribute such modifications or work under the terms of Section 1 above, provided that you also meet all of these conditions:

- a) The modified work must itself be a software library.
- b) You must cause the files modified to carry prominent notices stating that you changed the files and the date of any change.
- c) You must cause the whole of the work to be licensed at no charge to all third parties under the terms of this License.
- d) If a facility in the modified Library refers to a function or a table of data to be supplied by an application program that uses the facility, other than as an argument passed when the facility is invoked, then you must make a good faith effort to ensure that, in the event an application does not supply such function or table, the facility still operates, and performs whatever part of its purpose remains meaningful.

(For example, a function in a library to compute square roots has

a purpose that is entirely well-defined independent of the application. Therefore, Subsection 2d requires that any application-supplied function or table used by this function must be optional: if the application does not supply it, the square root function must still compute square roots.)

These requirements apply to the modified work as a whole. If identifiable sections of that work are not derived from the Library, and can be reasonably considered independent and separate works in themselves, then this License, and its terms, do not apply to those sections when you distribute them as separate works. But when you distribute the same sections as part of a whole which is a work based on the Library, the distribution of the whole must be on the terms of this License, whose permissions for other licensees extend to the entire whole, and thus to each and every part regardless of who wrote it.

Thus, it is not the intent of this section to claim rights or contest your rights to work written entirely by you; rather, the intent is to exercise the right to control the distribution of derivative or collective works based on the Library.

In addition, mere aggregation of another work not based on the Library with the Library (or with a work based on the Library) on a volume of a storage or distribution medium does not bring the other work under the scope of this License.

3. You may opt to apply the terms of the ordinary GNU General Public License instead of this License to a given copy of the Library. To do this, you must alter all the notices that refer to this License, so that they refer to the ordinary GNU General Public License, version 2, instead of to this License. (If a newer version than version 2 of the ordinary GNU General Public License has appeared, then you can specify that version instead if you wish.) Do not make any other change in these notices.

Once this change is made in a given copy, it is irreversible for that copy, so the ordinary GNU General Public License applies to all subsequent copies and derivative works made from that copy.

This option is useful when you wish to copy part of the code of the Library into a program that is not a library.

4. You may copy and distribute the Library (or a portion or derivative of it, under Section 2) in object code or executable form under the terms of Sections 1 and 2 above provided that you accompany

it with the complete corresponding machine-readable source code, which must be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange.

If distribution of object code is made by offering access to copy from a designated place, then offering equivalent access to copy the source code from the same place satisfies the requirement to distribute the source code, even though third parties are not compelled to copy the source along with the object code.

5. A program that contains no derivative of any portion of the Library, but is designed to work with the Library by being compiled or linked with it, is called a "work that uses the Library". Such a work, in isolation, is not a derivative work of the Library, and therefore falls outside the scope of this License.

However, linking a "work that uses the Library" with the Library creates an executable that is a derivative of the Library (because it contains portions of the Library), rather than a "work that uses the library". The executable is therefore covered by this License. Section 6 states terms for distribution of such executables.

When a "work that uses the Library" uses material from a header file that is part of the Library, the object code for the work may be a derivative work of the Library even though the source code is not. Whether this is true is especially significant if the work can be linked without the Library, or if the work is itself a library. The threshold for this to be true is not precisely defined by law.

If such an object file uses only numerical parameters, data structure layouts and accessors, and small macros and small inline functions (ten lines or less in length), then the use of the object file is unrestricted, regardless of whether it is legally a derivative work. (Executables containing this object code plus portions of the Library will still fall under Section 6.)

Otherwise, if the work is a derivative of the Library, you may distribute the object code for the work under the terms of Section 6. Any executables containing that work also fall under Section 6, whether or not they are linked directly with the Library itself.

6. As an exception to the Sections above, you may also compile or link a "work that uses the Library" with the Library to produce a work containing portions of the Library, and distribute that work under terms of your choice, provided that the terms permit modification

of the work for the customer's own use and reverse engineering for debugging such modifications.

You must give prominent notice with each copy of the work that the Library is used in it and that the Library and its use are covered by this License. You must supply a copy of this License. If the work during execution displays copyright notices, you must include the copyright notice for the Library among them, as well as a reference directing the user to the copy of this License. Also, you must do one of these things:

- a) Accompany the work with the complete corresponding machine-readable source code for the Library including whatever changes were used in the work (which must be distributed under Sections 1 and 2 above); and, if the work is an executable linked with the Library, with the complete machine-readable "work that uses the Library", as object code and/or source code, so that the user can modify the Library and then relink to produce a modified executable containing the modified Library. (It is understood that the user who changes the contents of definitions files in the Library will not necessarily be able to recompile the application to use the modified definitions.)
- b) Accompany the work with a written offer, valid for at least three years, to give the same user the materials specified in Subsection 6a, above, for a charge no more than the cost of performing this distribution.
- c) If distribution of the work is made by offering access to copy from a designated place, offer equivalent access to copy the above specified materials from the same place.
- d) Verify that the user has already received a copy of these materials or that you have already sent this user a copy.

For an executable, the required form of the "work that uses the Library" must include any data and utility programs needed for reproducing the executable from it. However, as a special exception, the source code distributed need not include anything that is normally distributed (in either source or binary form) with the major components (compiler, kernel, and so on) of the operating system on which the executable runs, unless that component itself accompanies the executable.

It may happen that this requirement contradicts the license restrictions of other proprietary libraries that do not normally

accompany the operating system. Such a contradiction means you cannot use both them and the Library together in an executable that you distribute.

7. You may place library facilities that are a work based on the Library side-by-side in a single library together with other library facilities not covered by this License, and distribute such a combined library, provided that the separate distribution of the work based on the Library and of the other library facilities is otherwise permitted, and provided that you do these two things:

- a) Accompany the combined library with a copy of the same work based on the Library, uncombined with any other library facilities. This must be distributed under the terms of the Sections above.
- b) Give prominent notice with the combined library of the fact that part of it is a work based on the Library, and explaining where to find the accompanying uncombined form of the same work.

8. You may not copy, modify, sublicense, link with, or distribute the Library except as expressly provided under this License. Any attempt otherwise to copy, modify, sublicense, link with, or distribute the Library is void, and will automatically terminate your rights under this License. However, parties who have received copies, or rights, from you under this License will not have their licenses terminated so long as such parties remain in full compliance.

9. You are not required to accept this License, since you have not signed it. However, nothing else grants you permission to modify or distribute the Library or its derivative works. These actions are prohibited by law if you do not accept this License. Therefore, by modifying or distributing the Library (or any work based on the Library), you indicate your acceptance of this License to do so, and all its terms and conditions for copying, distributing or modifying the Library or works based on it.

10. Each time you redistribute the Library (or any work based on the Library), the recipient automatically receives a license from the original licensor to copy, distribute, link with or modify the Library subject to these terms and conditions. You may not impose any further restrictions on the recipients' exercise of the rights granted herein. You are not responsible for enforcing compliance by third parties to this License.

11. If, as a consequence of a court judgment or allegation of patent

infringement or for any other reason (not limited to patent issues), conditions are imposed on you (whether by court order, agreement or otherwise)

that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot distribute so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not distribute the Library at all. For example, if a patent license would not permit royalty-free redistribution of the Library by all those who receive copies directly or indirectly through you, then the only way you could satisfy both it and this License would be to refrain entirely from distribution of the Library.

If any portion of this section is held invalid or unenforceable under any particular circumstance, the balance of the section is intended to apply, and the section as a whole is intended to apply in other circumstances.

It is not the purpose of this section to induce you to infringe any patents or other property right claims or to contest validity of any such claims; this section has the sole purpose of protecting the integrity of the free software distribution system which is implemented by public license practices. Many people have made generous contributions to the wide range of software distributed through that system in reliance on consistent application of that system; it is up to the author/donor to decide if he or she is willing to distribute software through any other system and a licensee cannot impose that choice.

This section is intended to make thoroughly clear what is believed to be a consequence of the rest of this License.

12. If the distribution and/or use of the Library is restricted in certain countries either by patents or by copyrighted interfaces, the original copyright holder who places the Library under this License may add an explicit geographical distribution limitation excluding those countries, so that distribution is permitted only in or among countries not thus excluded. In such case, this License incorporates the limitation as if written in the body of this License.

13. The Free Software Foundation may publish revised and/or new versions of the Library General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Library specifies a version number of this License which applies to it and

"any later version", you have the option of following the terms and conditions either of that version or of any later version published by the Free Software Foundation. If the Library does not specify a license version number, you may choose any version ever published by the Free Software Foundation.

14. If you wish to incorporate parts of the Library into other free programs whose distribution conditions are incompatible with these, write to the author to ask for permission. For software which is copyrighted by the Free Software Foundation, write to the Free Software

Foundation; we sometimes make exceptions for this. Our decision will be guided by the two goals of preserving the free status of all derivatives of our free software and of promoting the sharing and reuse of software generally.

NO WARRANTY

15. BECAUSE THE LIBRARY IS LICENSED FREE OF CHARGE, THERE IS NO WARRANTY FOR THE LIBRARY, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE LIBRARY "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE LIBRARY IS WITH YOU. SHOULD THE LIBRARY PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

16. IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY AND/OR REDISTRIBUTE THE LIBRARY AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE LIBRARY (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE LIBRARY TO OPERATE WITH ANY OTHER SOFTWARE), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Libraries

If you develop a new library, and you want it to be of the greatest possible use to the public, we recommend making it free software that everyone can redistribute and change. You can do so by permitting redistribution under these terms (or, alternatively, under the terms of the

ordinary General Public License).

To apply these terms, attach the following notices to the library. It is safest to attach them to the start of each source file to most effectively convey the exclusion of warranty; and each file should have at least the "copyright" line and a pointer to where the full notice is found.

<one line to give the library's name and a brief idea of what it does.>
Copyright (C) <year> <name of author>

This library is free software; you can redistribute it and/or modify it under the terms of the GNU Library General Public License as published by the Free Software Foundation; either version 2 of the License, or (at your option) any later version.

This library is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU Library General Public License for more details.

You should have received a copy of the GNU Library General Public License along with this library; if not, write to the Free Software Foundation, Inc., 59 Temple Place, Suite 330, Boston, MA 02111-1307 USA

Also add information on how to contact you by electronic and paper mail.

You should also get your employer (if you work as a programmer) or your school, if any, to sign a "copyright disclaimer" for the library, if necessary. Here is a sample; alter the names:

Yoyodyne, Inc., hereby disclaims all copyright interest in the library `Frob' (a library for tweaking knobs) written by James Random Hacker.

<signature of Ty Coon>, 1 April 1990
Ty Coon, President of Vice

That's all there is to it!

This is the Debian GNU/Linux prepackaged version of the Common Error Description library. It is currently distributed together with the EXT2 file system utilities, which are otherwise packaged as "e2fsprogs".

This package was put together by Yann Dirson <dirson@debian.org>, from sources obtained from a mirror of:
tsx-11.mit.edu:/pub/linux/packages/ext2fs/

From the original distribution:

Copyright 1987, 1988 by the Student Information Processing Board
of the Massachusetts Institute of Technology

Permission to use, copy, modify, and distribute this software
and its documentation for any purpose and without fee is
hereby granted, provided that the above copyright notice
appear in all copies and that both that copyright notice and
this permission notice appear in supporting documentation,
and that the names of M.I.T. and the M.I.T. S.I.P.B. not be
used in advertising or publicity pertaining to distribution
of the software without specific, written prior permission.
M.I.T. and the M.I.T.

S.I.P.B. make no representations about
the suitability of this software for any purpose. It is
provided "as is" without express or implied warranty.

1.83 golang 1.18.1

1.83.1 Available under license :

Apache License
Version 2.0, January 2004
<http://www.apache.org/licenses/>

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction,
and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by
the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all
other entities that control, are controlled by, or are under common
control with that entity. For the purposes of this definition,
"control" means (i) the power, direct or indirect, to cause the
direction or management of such entity, whether by contract or
otherwise, or (ii) ownership of fifty percent (50%) or more of the
outstanding shares, or (iii) beneficial ownership
of such entity.

"You" (or "Your") shall mean an individual or Legal Entity
exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications,

including but not limited to software source code, documentation source, and configuration files.

"Object" form shall mean any form resulting from mechanical transformation or translation of a Source form, including but not limited to compiled object code, generated documentation, and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or Object form, made available under the License, as indicated by a copyright notice that is included in or attached to the work (an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object form, that is based on (or derived from) the Work and for which the editorial revisions, annotations, elaborations, or other modifications represent, as a whole, an original work of authorship. For the purposes of this License, Derivative Works shall not include works that remain separable from, or merely link (or bind by name) to the interfaces of, the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including the original version of the Work and any modifications or additions to that Work or Derivative Works thereof, that is intentionally submitted to Licensor for inclusion in the Work by the copyright owner or by an individual or Legal Entity authorized to submit on behalf of the copyright owner. For the purposes of this definition, "submitted" means any form of electronic, verbal, or written communication sent to the Licensor or its representatives, including but not limited to communication on electronic mailing lists, source code control systems, and issue tracking systems that are managed by, or on behalf of, the Licensor for the purpose of discussing and improving the Work, but excluding communication that is conspicuously marked or otherwise designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity on behalf of whom a Contribution has been received by Licensor and subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative Works of, publicly display, publicly perform, sublicense, and distribute the Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of

this License,
each Contributor hereby grants to You a perpetual,
worldwide, non-exclusive, no-charge, royalty-free, irrevocable
(except as stated in this section) patent license to make, have made,
use, offer to sell, sell, import, and otherwise transfer the Work,
where such license applies only to those patent claims licensable
by such Contributor that are necessarily infringed by their
Contribution(s) alone or by combination of their Contribution(s)
with the Work to which such Contribution(s) was submitted. If You
institute patent litigation against any entity (including a
cross-claim or counterclaim in a lawsuit) alleging that the Work
or a Contribution incorporated within the Work constitutes direct
or contributory patent infringement, then any patent licenses
granted to You under this License for that Work shall terminate
as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute
copies of the

Work or Derivative Works thereof in any medium, with or without
modifications, and in Source or Object form, provided that You
meet the following conditions:

- (a) You must give any other recipients of the Work or
Derivative Works a copy of this License; and
- (b) You must cause any modified files to carry prominent notices
stating that You changed the files; and
- (c) You must retain, in the Source form of any Derivative Works
that You distribute, all copyright, patent, trademark, and
attribution notices from the Source form of the Work,
excluding those notices that do not pertain to any part of
the Derivative Works; and
- (d) If the Work includes a "NOTICE" text file as part of its
distribution, then any Derivative Works that You distribute must
include a readable copy of the attribution notices contained
within such NOTICE file, excluding

those notices that do not

pertain to any part of the Derivative Works, in at least one
of the following places: within a NOTICE text file distributed
as part of the Derivative Works; within the Source form or
documentation, if provided along with the Derivative Works; or,
within a display generated by the Derivative Works, if and
wherever such third-party notices normally appear. The contents
of the NOTICE file are for informational purposes only and
do not modify the License. You may add Your own attribution
notices within Derivative Works that You distribute, alongside

or as an addendum to the NOTICE text from the Work, provided that such additional attribution notices cannot be construed as modifying the License.

You may add Your own copyright statement to Your modifications and may provide additional or different license terms and conditions

for use, reproduction, or distribution of Your modifications, or for any such Derivative Works as a whole, provided Your use, reproduction, and distribution of the Work otherwise complies with the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise, any Contribution intentionally submitted for inclusion in the Work by You to the Licensor shall be under the terms and conditions of this License, without any additional terms or conditions. Notwithstanding the above, nothing herein shall supersede or modify the terms of any separate license agreement you may have executed with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade names, trademarks, service marks, or product names of the Licensor, except as required for reasonable and customary use in describing the origin of the Work and reproducing the content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or agreed to in writing, Licensor provides the Work (and each Contributor provides its Contributions) on an "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied, including, without limitation, any warranties or conditions of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A PARTICULAR PURPOSE. You are solely responsible for determining the appropriateness of using or redistributing the Work and assume any risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory, whether in tort (including negligence), contract, or otherwise, unless required by applicable law (such as deliberate and grossly negligent acts) or agreed to in writing, shall any Contributor be liable to You for damages, including any direct, indirect, special, incidental, or consequential damages of any character arising as a result of this License or out of the use or inability to use the Work (including but not limited to damages for loss of goodwill, work stoppage, computer failure or malfunction, or any and all other commercial damages or losses), even if such Contributor has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing the Work or Derivative Works thereof, You may choose to offer, and charge a fee for, acceptance of support, warranty, indemnity, or other liability obligations and/or rights consistent with this License. However, in accepting such obligations, You may act only on Your own behalf and on Your sole responsibility, not on behalf of any other Contributor, and only if You agree to indemnify, defend, and hold each Contributor harmless for any liability incurred by, or claims asserted against, such Contributor by reason of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

APPENDIX: How to apply the Apache License to your work.

To apply the Apache License to your work, attach the following boilerplate notice, with the fields enclosed by brackets "{}" replaced with your own identifying information. (Don't include the brackets!) The text should be enclosed in the appropriate comment syntax for the file format. We also recommend that a file or class name and description of purpose be included on the same "printed page" as the copyright notice for easier identification within third-party archives.

Copyright {yyyy} {name of copyright owner}

Licensed under the Apache License, Version 2.0 (the "License");
you may not use this file except in compliance with the License.
You may obtain a copy of the License at

<http://www.apache.org/licenses/LICENSE-2.0>

Unless required by applicable law or agreed to in writing, software distributed under the License is distributed on an "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the License for the specific language governing permissions and limitations under the License.

```
# This source code was written by the Go contributors.  
# The master list of contributors is in the main Go distribution,  
# visible at http://tip.golang.org/CONTRIBUTORS.  
# This is the official list of people who can contribute  
# (and typically have contributed) code to the Go repository.  
# The AUTHORS file lists the copyright holders; this file  
# lists people. For example, Google employees are listed here  
# but not in AUTHORS, because Google holds the copyright.  
#  
# Names should be added to this file only after verifying that
```

```
# the individual or the individual's organization has agreed to
# the appropriate Contributor License Agreement, found here:
#
# http://code.google.com/legal/individual-cla-v1.0.html
# http://code.google.com/legal/corporate-cla-v1.0.html
#
# The agreement for individuals can be filled out on the web.

# Names should be added to this file like so:
# Individual's name <submission email address>
# Individual's name <submission email address> <email2> <emailN>
#
# An entry with multiple email addresses specifies that the
# first address should be used in the submit logs and
# that the other addresses should be recognized
# as the
# same person when interacting with Gerrit.

# Please keep the list sorted.

Aamir Khan <syst3m.w0rm@gmail.com>
Aaron Beitch <aaronb@arista.com>
Aaron Bieber <deftly@gmail.com>
Aaron Cannon <cannona@fireantproductions.com>
Aaron France <aaron.l.france@gmail.com>
Aaron Jacobs <jacobsa@google.com>
Aaron Jensen <jensen.aaro@gmail.com>
Aaron Kemp <kemp.aaron@gmail.com>
Aaron Patterson <tenderlove@ruby-lang.org>
Aaron Sheah <aaronsheah@gmail.com>
Aaron Stein <aaronstein12@gmail.com>
Aaron Torres <tcboox@gmail.com>
Aaron Zinman <aaron@azinman.com>
Aarti Parikh <aarti.parikh@gmail.com>
Abdullah Al Maruf <mymail.maruf@gmail.com>
Abe Haskins <abeisgreat@abeisgreat.com>
Abhinav Gupta <abhinav.g90@gmail.com>
Adam Azarchs <adam.azarchs@10xgenomics.com>
Adam Bender <abender@google.com>
Adam Eijdenberg <adam@continusec.com>
Adam Harvey <aharvey@php.net>
Adam Kisala <adam.kisala@gmail.com>
Adam Langley <agl@golang.org>
Adam Medzinski <adam.medzinski@gmail.com>
Adam Mitha <adam.mitha@gmail.com>
Adam
Shannon <adamkshannon@gmail.com>
Adam Shelton <aashelt90@gmail.com>
```

Adam Sindelar <adamsh@google.com>
Adam Thomason <athomason@gmail.com>
Adam Williams <pwnfactory@gmail.com>
Adam Woodbeck <adam@woodbeck.net>
Adarsh Ravichandran <adarshravichandran91@gmail.com>
Adel Rodriguez <adel.rodriguez@leftfieldlabs.com>
Adin Scannell <ascannell@google.com>
Aditya Harindar <aditya.harindar@gmail.com>
Aditya Mukerjee <dev@chimeracoder.net>
Adrian Hesketh <adrianhesketh@hushmail.com>
Adrian Nos <nos.adrian@gmail.com>
Adrian O'Grady <elpollouk@gmail.com>
Adrien Bustany <adrien-xx-google@bustany.org>
Adrien Delorme <adrien.delorme@icloud.com>
Adrien Petel <peteladrien@gmail.com>
Acio Jnior <aeciodantasjunior@gmail.com>
Aeneas Rekkas (arekkas) <aeneas@ory.am>
Afanasev Stanislav <phpprogger@gmail.com>
Agis Anastasopoulos <agis.anast@gmail.com>
Agniva De Sarker <agnivade@yahoo.co.in>
Ahmed W. Mones <oneofone@gmail.com>
Ahmet Aktrk <aakturk000@gmail.com>
Ahmet Alp Balkan <ahmetb@google.com>
Ahmet
Soormally <ahmet@mangomm.co.uk>
Ahmy Yulrizka <yulrizka@gmail.com>
Ahsun Ahmed <ahmed.ahsun@gmail.com>
Aidan Coyle <packrat386@gmail.com>
Aiden Scandella <ai@uber.com>
Ainar Garipov <gugl.zadolbal@gmail.com>
Aishraj Dahal <aishraj@users.noreply.github.com>
Ajanthan Balachandran <balaajanthan@gmail.com>
Akhil Indurti <aindurti@gmail.com>
Akihiro Suda <suda.kyoto@gmail.com>
Akshat Kumar <seed@mail.nanosouffle.net>
Al Cutter <al@google.com>
Alan Braithwaite <alan@ipaddr.org>
Alan Donovan <adonovan@google.com>
Alan Shreve <alan@inconshreveable.com>
Albert Nigmatzianov <albertnigma@gmail.com>
Albert Strasheim <fullung@gmail.com>
Albert Teoh <albert.teoh@gmail.com>
Albert Yu <yukinying@gmail.com>
Alberto Bertogli <albertito@blitiri.com.ar>
Alberto Donizetti <alb.donizetti@gmail.com>
Alberto Garca Hierro <alberto@garciahierro.com> <alberto.garcia.hierro@gmail.com>
Alec Benzer <alec.benzer@gmail.com>
Alejandro Garca Montoro <alejandro.garciamontoro@gmail.com>

Aleksa Sarai <cyphar@cyphar.com>
Aleksandar
Dezelin <dezelin@gmail.com>
Aleksandr Lukinykh <a.lukinykh@xsolla.com>
Aleksandr Razumov <ar@cydev.ru>
Alekseev Artem <a.artem060@gmail.com>
Aleksei Tirman <aleksei.tirman@jetbrains.com>
Alessandro Arzilli <alessandro.arzilli@gmail.com>
Alessandro Baffa <alessandro.baffa@gmail.com>
Alex A Skinner <alex@lx.lc>
Alex Brainman <alex.brainman@gmail.com>
Alex Bramley <abramley@google.com>
Alex Browne <stephenalexbrowne@gmail.com>
Alex Buchanan <buchanae@gmail.com>
Alex Carol <alex.carol.c@gmail.com>
Alex Gaynor <alex@alloy.us>
Alex Harford <alex.harford@saucelabs.com>
Alex Hays <alex.hays@leftfieldlabs.com>
Alex Jin <toalexjin@gmail.com>
Alex Kohler <alexjohnkohler@gmail.com>
Alex Myasoedov <msoedov@gmail.com>
Alex Opie <amtopie@gmail.com>
Alex Plugaru <alex@plugaru.org> <alexandru.plugaru@gmail.com>
Alex Schade <39062967+aschade92@users.noreply.github.com>
Alex Schroeder <alex@gnu.org>
Alex Sergeev <abc@alexsergeev.com>
Alex Tokarev <aleksator@gmail.com>
Alex Vaghin <crhyme@google.com>
Alex
Zhirov <azhirov@google.com>
Alexander Demakin <alexander.demakin@gmail.com>
Alexander Dring <email@alex.d.ch>
Alexander F Rdseth <alexander.rodseth@appeartv.com>
Alexander Greim <alexxx@iltempo.de>
Alexander Guz <kalimatas@gmail.com>
Alexander Kauer <alexander@affine.space>
Alexander Klauer <Alexander.Klauer@googlemail.com>
Alexander Kucherenko <alxkchr@gmail.com>
Alexander Larsson <alexander.larsson@gmail.com>
Alexander Lourier <aml@rulezz.ru>
Alexander Melentyev <alexander@melentyev.org>
Alexander Menzhinsky <amenzhinsky@gmail.com>
Alexander Morozov <lk4d4math@gmail.com>
Alexander Neumann <alexander@bumpen.de>
Alexander Nohe <alex.nohe427@gmail.com>
Alexander Orlov <alexander.orlov@loxal.net>
Alexander Pantyukhin <apantykhin@gmail.com>
Alexander Polcyn <apolcyn@google.com>

Alexander Rakoczy <alex@golang.org>
Alexander Reece <awreece@gmail.com>
Alexander Surma <surma@surmair.de>
Alexander Yastrebov <yastrebov.alex@gmail.com>
Alexander Zhavnerchik <alex.vizor@gmail.com>
Alexander
Zillion <alex@alexzillion.com>
Alexander Zolotov <goldifit@gmail.com>
Alexandr Mayorskiy <a.mayorskiy@corp.mail.ru>
Alexandre Cesaro <alexandre.cesaro@gmail.com>
Alexandre Fiori <fiorix@gmail.com>
Alexandre Maari <draeron@gmail.com>
Alexandre Normand <alexandre.normand@gmail.com>
Alexandre Parentea <aubonbeurre@gmail.com>
Alexandre Viau <alexandre@alexandreviau.net>
Alexandru Mooi <brtznr@gmail.com>
Alexei Sholik <alcosholik@gmail.com>
Alexey Alexandrov <aalexand@google.com>
Alexey Borzenkov <snaury@gmail.com>
Alexey Naidonov <alexey.naidyonov@gmail.com>
Alexey Neganov <neganovalexey@gmail.com>
Alexey Palazhchenko <alexey.palazhchenko@gmail.com>
Alexey Semenyuk <alexsemenyuk88@gmail.com>
Alexey Vilenskiy <bynovhack@gmail.com>
Alexis Hildebrandt <surryhill@gmail.com>
Alexis Hunt <lexer@google.com>
Alexis Imperial-Legrand <ail@google.com>
Ali Farooq <ali.farooq0@pm.me>
Ali Rizvi-Santiago <arizvisa@gmail.com>
Aliaksandr Valialkin <valyala@gmail.com>
Alice Merrick <amerrick@google.com>
Alif
Rachmawadi <subosito@gmail.com>
Allan Guwatudde <guwats10@gmail.com>
Allan Simon <allan.simon@supinfo.com>
Allen Li <ayatane@google.com>
Alok Menghrajani <alok.menghrajani@gmail.com>
Alwin Doss <alwindoss84@gmail.com>
Aman Gupta <aman@tmm1.net>
Amarjeet Anand <amarjeetanandsingh@gmail.com>
Amelia Downs <adowns@vmware.com>
Amir Mohammad Saied <amir@gluegadget.com>
Amit Kumar <mittalmailbox@gmail.com>
Amr Mohammed <merodiro@gmail.com>
Amrut Joshi <amrut.joshi@gmail.com>
An Long <aisk1988@gmail.com>
An Xiao <hac@zju.edu.cn>
Anand K. Mistry <anand@mistry.ninja>

Ananya Saxena <ananyasaxena1@gmail.com>
Anatol Pomozov <anatol.pomozov@gmail.com>
Anders Pearson <anders@columbia.edu>
Anderson Queiroz <contato@andersonq.eti.br>
Andr Carvalho <asantostc@gmail.com>
Andre Marianiello <andremarianiello@users.noreply.github.com>
Andr Martins <aanm90@gmail.com>
Andre Nathan <andrenth@gmail.com>
Andrea Nodari <andrea.nodari91@gmail.com>
Andrea Simonini <andrea.simonini@gmail.com>
Andrea Spadaccini
<spadaccio@google.com>
Andreas Auernhammer <aead@mail.de>
Andreas Jellinghaus <andreas@ionisiert.de> <anj@google.com>
Andreas Litt <andreas.litt@gmail.com>
Andrei Enshin <b1os@bk.ru>
Andrei Gherzan <andrei@resin.io>
Andrei Korzhevskii <a.korzhevskiy@gmail.com>
Andrei Matei <andrei@cockroachlabs.com>
Andrei Tudor Clin <mail@acln.ro>
Andrei Vagin <avagin@google.com>
Andrei Vieru <euvieru@gmail.com>
Andres Erbsen <andreser@google.com>
Andres Lowrie <andres.lowrie@gmail.com>
Andrew Austin <andrewacht@gmail.com>
Andrew Balholm <andybalholm@gmail.com>
Andrew Benton <andrewmbenton@gmail.com>
Andrew Bonventre <andybons@chromium.org>
Andrew Braunstein <awbraunstein@gmail.com>
Andrew Bursavich <abursavich@gmail.com>
Andrew Ekstedt <andrew.ekstedt@gmail.com>
Andrew Etter <andrew.etter@gmail.com>
Andrew G. Morgan <agm@google.com>
Andrew Gerrand <adg@golang.org>
Andrew Harding <andrew@spacemonkey.com>
Andrew Jackura <ajackura@google.com>
Andrew Kemm <andrewkemm@gmail.com>
Andrew LeFevre <capnspacehook@gmail.com>
Andrew
Louis <alouis@digitalocean.com>
Andrew Lutomirski <andy@luto.us>
Andrew Medvedev <andrew.y.medvedev@gmail.com>
Andrew Pilloud <andrewpilloud@igneoussystem.com>
Andrew Pogrebnoy <absourd.noise@gmail.com>
Andrew Poydence <apoydence@pivotal.io>
Andrew Pritchard <awpritchard@gmail.com>
Andrew Radev <andrey.radev@gmail.com>
Andrew Skiba <skibaa@gmail.com>

Andrew Stormont <astormont@racktopsystems.com>
Andrew Stribblehill <ads@wompom.org>
Andrew Szeto <andrew@jabagawee.com>
Andrew Todd <andrew.todd@wework.com>
Andrew Wansink <wansink@uber.com>
Andrew Werner <andrew@upthere.com> <awerner32@gmail.com>
Andrew Wilkins <axwalk@gmail.com>
Andrew Williams <williams.andrew@gmail.com>
Andrew Z Allen <me@andrewzallen.com>
Andrey Bokhanko <andreybokhanko@gmail.com>
Andrey Mirtchovski <mirtchovski@gmail.com>
Andrey Petrov <andrey.petrov@shazow.net>
Andrii Soldatenko <andrii.soldatenko@gmail.com>
Andrii Soluk <isoluchok@gmail.com>
Andriy Lytvynov <lytvynov.a.v@gmail.com>
Andrzej
eel <andrii.zhezhel@gmail.com>
Andy Balholm <andy@balholm.com>
Andy Davis <andy@bigandian.com>
Andy Finkenstadt <afinkenstadt@zynga.com>
Andy Lindeman <andy@lindeman.io>
Andy Maloney <asmaloney@gmail.com>
Andy Pan <panjf2000@gmail.com> <panjf2000@golangcn.org> <i@andypan.me>
Andy Walker <walkeraj@gmail.com>
Andy Wang <cbeuw.andy@gmail.com>
Andy Williams <andy@andy.xyz>
Andy Zhao <andyzhao@google.com>
Andzej Maciusovic <andzej.maciusovic@gmail.com>
Anfernee Yongkun Gui <anfernee.gui@gmail.com>
Angelo Bulfone <mbulfone@gmail.com>
Anh Hai Trinh <anh.hai.trinh@gmail.com>
Anit Gandhi <anitgandhi@gmail.com>
Ankit Goyal <ankit3goyal@gmail.com>
Anmol Sethi <anmol@aubble.com>
Annirudh Prasad <annirudh@wandb.com>
Anschel Schaffer-Cohen <anschelsc@gmail.com>
Anthony Alves <cvballa3g0@gmail.com>
Anthony Canino <anthony.canino1@gmail.com>
Anthony Eufemio <anthony.eufemio@gmail.com>
Anthony Fok <foka@debian.org>
Anthony Martin <ality@pbrane.org>
Anthony Sottile <asottile@umich.edu>
Anthony Starks
<ajstarks@gmail.com>
Anthony Voutas <voutasaurus@gmail.com>
Anthony Woods <awoods@raintank.io>
Antoine GIRARD <sapk@sapk.fr>
Antoine Martin <antoine97.martin@gmail.com>

Anton Gyllenberg <anton@iki.fi>
Anton Kuklin <anton.a.kuklin@gmail.com>
Antonin Amand <antonin.amand@gmail.com>
Antonio Antelo <aantelov87@gmail.com>
Antonio Bibiano <antbbn@gmail.com>
Antonio Garcia <garcia.olais@gmail.com>
Antonio Huete Jimenez <tuxillo@quantumachine.net>
Antonio Murdaca <runcom@redhat.com>
Antonio Ojea <antonio.ojea.garcia@gmail.com>
Antonio Troina <thoeni@gmail.com>
Anze Kolar <me@akolar.com>
Aofei Sheng <aofei@aofeisheng.com>
Apisak Darakananda <pongad@gmail.com>
Aram Hvrneanu <aram@mgk.ro>
Araragi Hokuto <kanseihonbucho@protonmail.com>
Arash Bina <arash@arash.io>
Archana Ravindar <aravind5@in.ibm.com>
Arda Gl <ardaguclu@gmail.com>
Areski Belaid <areski@gmail.com>
Ariel Mashraki <ariel@mashraki.co.il>
Arkadi Pyuro <arkadi@google.com>
Arlo Breault <arlolra@gmail.com>
Arnaud Ysmal <arnaud.ysmal@gmail.com>
Arne
Hormann <arnehormann@gmail.com>
Arnout Engelen <arnout@bzzt.net>
Aron Nopanen <aron.nopanen@gmail.com>
Arran Walker <arran.walker@fiveturns.org>
Artem Alekseev <artem.alekseev@intel.com>
Artem Khvastunov <artem.khvastunov@jetbrains.com>
Artem Kolin <artemkaxboy@gmail.com>
Arthur Fabre <arthur@arthurfabre.com>
Arthur Khashaev <arthur@khashaev.ru>
Artur M. Wolff <artur.m.wolff@gmail.com>
Artyom Pervukhin <artyom.pervukhin@gmail.com>
Arvinth Rajesh Tamilmani <art@a-30.net>
Ashish Bhate <ab.listsubs@gmail.com>
Ashish Gandhi <ag@ashishgandhi.org>
Asim Shankar <asimshankar@gmail.com>
Assel Meher <asselmeher@gmail.com>
Atin Malaviya <amalaviy@akamai.com>
Ato Araki <ato.araki@gmail.com>
Atsushi Toyama <atsushi.tohyama.160.333@gmail.com>
Audrey Lim <audreylh@gmail.com>
Audrius Butkevicius <audrius.butkevicius@gmail.com>
Augusto Roman <aroman@gmail.com>
Aulus Egnatius Varialus <varialus@gmail.com>
Aurlien Rainone <aurelien.rainone@gmail.com>

Aurlio A. Heckert <aurium@gmail.com>
Austin
Clements <austin@google.com> <aclements@csail.mit.edu>
Avi Flax <avi@timehop.com>
Aviv Klasquin Komissar <avivklas@gmail.com>
awaw fumin <awawfumin@gmail.com>
Awn Umar <awn@cryptolosophy.io>
Axel Wagner <axel.wagner.hh@googlemail.com>
Ayan George <ayan@ayan.net>
Ayanamist Yang <ayanamist@gmail.com>
Ayke van Laethem <aykevanlaethem@gmail.com>
Aymerick Jhanne <aymerick@jehanne.org>
Ayzat Sadykov <ayzat.ziko.93@gmail.com>
Azat Kaumov <kaumov.a.r@gmail.com>
Baiju Muthukadan <baiju.m.mail@gmail.com>
Balaram Makam <bmakam.qdt@qualcommdatacenter.com>
Balazs Lecz <leczb@google.com>
Baokun Lee <nototon@gmail.com> <bk@golangcn.org>
Barnaby Keene <accounts@southcla.ws>
Bartomiej Klimczak <bartlomiej.klimczak88@gmail.com>
Bartosz Grzybowski <melkorm@gmail.com>
Bartosz Oler <brtsz@google.com>
Bassam Ojeil <bojeil@google.com>
Bastian Ike <bastian.ike@gmail.com>
Ben Burkert <ben@benburkert.com>
Ben Cartwright-Cox <Ben@Benjojo.co.uk>
Ben Eitzen <eitzenb@golang.org>
Ben Fried <ben.fried@gmail.com>
Ben
Haines <bhainesva@gmail.com>
Ben Hoyt <benhoyt@gmail.com>
Ben Hutchings <ben.hutchings@essensium.com>
Ben Kraft <benkraft@khanacademy.org>
Ben Laurie <ben@links.org> <benl@google.com>
Ben Lubar <ben.lubar@gmail.com>
Ben Lynn <benlynn@gmail.com>
Ben Olive <sionide21@gmail.com>
Ben Schwartz <bemasc@google.com>
Ben Shi <powerman1st@163.com>
Ben Toews <mastahyeti@gmail.com>
Benjamin Barenblat <bbaren@google.com>
Benjamin Black <b@b3k.us>
Benjamin Cable <cable.benjamin@gmail.com>
Benjamin Hsieh <tanookiben@users.noreply.github.com>
Benjamin Peterson <benjamin@python.org>
Benjamin Prosnitz <bprosnitz@google.com>
Benjamin Wester <bwester@squareup.com>
Benjamin Wuethrich <benjamin.wuethrich@gmail.com>

Benny Siegert <bsiegert@gmail.com>
Benoit Sigoure <tsunanet@gmail.com>
Berengar Lehr <Berengar.Lehr@gmx.de>
Berkant Ipek <41230766+0xbkt@users.noreply.github.com>
Beth Brown <ecbrown@google.com>
Bharath Kumar Uppala <uppala.bharath@gmail.com>
Bharath Thiruveedula <tbharath91@gmail.com>
Bhavin
Gandhi <bhavin7392@gmail.com>
Bill Neubauer <wcn@golang.org> <wcn@google.com> <bill.neubauer@gmail.com>
Bill O'Farrell <billo@ca.ibm.com>
Bill Prin <waprin@google.com>
Bill Thiede <couchmoney@gmail.com>
Bill Zissimopoulos <billziss@navimatics.com>
Billie Harold Cleek <bhcleek@gmail.com>
Billy Lynch <wlynch@google.com>
Billy Zaelani Malik <m.billyzaelani@gmail.com>
Bjrn Erik Pedersen <bjorn.erik.pedersen@gmail.com>
Bjorn Tillenius <bjorn@tillenius.me>
Bjorn Tipling <bjorn.tipling@gmail.com>
Blain Smith <rebelgeek@blainsmith.com>
Blake Gentry <blakesgentry@gmail.com>
Blake Mesdag <blakemesdag@gmail.com>
Blake Mizerany <blake.mizerany@gmail.com>
Blixt <me@blixt.nyc>
Bob Briski <rbriski@gmail.com>
Bob McNaughton <bobmcn@gmail.com>
Bob Potter <bobby.potter@gmail.com>
Bobby DeSimone <bobbydesimone@gmail.com>
Bobby Powers <bobbypowers@gmail.com>
Boqin Qin <bobbqqin@gmail.com>
Boris Nagaev <nagaev@google.com>
Borja Clemente <borja.clemente@gmail.com>
Boshi Lian <bolian@microsoft.com>
Brad Burch
<brad.burch@gmail.com>
Brad Erickson <bderickson@gmail.com>
Brad Fitzpatrick <bradfitz@golang.org> <bradfitz@gmail.com>
Brad Garcia <bgarcia@golang.org>
Brad Jones <rbjones@google.com>
Brad Morgan <brad@morgabra.com>
Brad Whitaker <bwhitaker@fastly.com>
Braden Bassingthwaite <bbassingthwaite@vendasta.com>
Bradford Lamson-Scribner <brad.lamson@gmail.com>
Bradley Falzon <brad@teambrad.net>
Brady Catherman <brady@gmail.com>
Brady Sullivan <brady@bsull.com>
Branden J. Brown <zephyrtronium@gmail.com>

Brandon Bennett <bbennett@fb.com>
Brandon Gilmore <varz@google.com>
Brandon Philips <brandon@ifup.org>
Brandon Ryan <bjryan19@gmail.com>
Brave Cow <rsr715@gmail.com>
Brayden Cloud <bcloud@google.com>
Brendan Daniel Tracey <tracey.brendan@gmail.com>
Brendan O'Dea <bod@golang.org>
Brett Cannon <bcannon@gmail.com>
Brett Merrill <brett.j.merrill94@gmail.com>
Brian Dellisanti <briandellisanti@gmail.com>
Brian Downs <brian.downs@gmail.com>
Brian Falk <falk@logicparty.org>
Brian G. Merrell <bgmerrell@gmail.com>
Brian
Gitonga Marete <marete@tohnix.com> <bgmarete@gmail.com> <bgm@google.com>
Brian Kennedy <btkennedy@gmail.com>
Brian Kessler <brian.m.kessler@gmail.com>
Brian Ketelsen <bketelsen@gmail.com>
Brian Slesinsky <skybrian@google.com>
Brian Smith <ohohvi@gmail.com>
Brian Starke <brian.starke@gmail.com>
Bruce Huang <helbingxxx@gmail.com>
Bryan Alexander <Kozical@msn.com>
Bryan Boreham <bjboreham@gmail.com>
Bryan C. Mills <bcmills@google.com>
Bryan Chan <bryan.chan@ca.ibm.com>
Bryan Ford <brynosaurus@gmail.com>
Bryan Heden <b.heden@gmail.com>
Bulat Gaifullin <gaifullinbf@gmail.com>
Burak Guven <bguven@gmail.com>
Caine Tighe <arctanofyourface@gmail.com>
Caio Marcelo de Oliveira Filho <caio.oliveira@intel.com>
Caleb Martinez <accounts@calebmartinez.com>
Caleb Spare <cespare@gmail.com>
Carl Chatfield <carlchatfield@gmail.com>
Carl Henrik Lunde <chlunde@ifi.uio.no>
Carl Jackson <carl@stripe.com>
Carl Johnson <me@carlmjohnson.net>
Carl Mastrangelo <notcarl@google.com>
Carl Menezes
<carleeto@gmail.com>
Carl Shapiro <cshapiro@google.com> <cshapiro@golang.org>
Carlisia Campos <carlisia@grokkingtech.io>
Carlo Alberto Ferraris <cafxx@strayorange.com>
Carlos Alexandro Becker <caarlos0@gmail.com>
Carlos Amedee <carlos@golang.org>
Carlos Castillo <cookieo9@gmail.com>

Carlos Cirello <uldericofilho@gmail.com>
Carlos Eduardo <me@carlopedp.com>
Carlos Eduardo Seo <cseo@linux.vnet.ibm.com>
Carlos Iriarte <ciriarte@gmail.com>
Carlos Souza <carloshrsouza@gmail.com>
Carolyn Van Slyck <me@carolynvanslyck.com>
Carrie Bynon <cbynon@gmail.com>
Carson Hoffman <c@rsonhoffman.com>
Cary Hull <chull@google.com>
Case Nelson <case.nelson@gmail.com>
Casey Callendrello <squeed@gmail.com>
Casey Marshall <casey.marshall@gmail.com>
Catalin Nicutar <cnicutar@google.com>
Catalin Patulea <catalinp@google.com>
Cathal O'Callaghan <cathalsocallaghan@gmail.com>
Cedric Staub <cs@squareup.com>
Cezar S Espinola <cezarsa@gmail.com>
Chad Rosier <mrosier.qdt@qualcommdatacenter.com>
ChaiShushan <chaishushan@gmail.com>
Changkun
Ou <hi@changkun.us>
Channing Kimble-Brown <channing@golang.org>
Chao Xu <xuchao@google.com>
Chaoqun Han <hansscv@gmail.com>
Charles Fenwick Elliott <Charles@FenwickElliott.io>
Charles Kenney <charlesc.kenney@gmail.com>
Charles L. Dorian <cldorian@gmail.com>
Charles Lee <zombie.fml@gmail.com>
Charles Weill <weill@google.com>
Charlie Getzen <charlie@bolt.com>
Charlie Moog <moogcharlie@gmail.com>
Charlotte Brandhorst-Satzkorn <catzkorn@gmail.com>
Chauncy Cullitan <chauncyc@google.com>
Chen Zhidong <njutcd@gmail.com>
Chen Zhihan <energiehund@gmail.com>
Cheng Wang <>wangchengiscool@gmail.com>
Cherry Mui <cherryyz@google.com>
Chew Choon Keat <choonkeat@gmail.com>
Chia-Chi Hsu <wuchi5457@gmail.com>
Chiawen Chen <golopot@gmail.com>
Chirag Sukhala <cchirag77@gmail.com>
Cholerae Hu <choleraehyq@gmail.com>
Chotepud Teo <AlexRouSg@users.noreply.github.com>
Chressie Himpel <chressie@google.com>
Chris Ball <chris@printf.net>
Chris Biscardi <chris@christopherbiscardi.com>
Chris

Broadfoot <cbro@golang.org>
Chris Dollin <ehog.hedge@gmail.com>
Chris Farmiloe <chrisfarms@gmail.com>
Chris Hines <chris.cs.guy@gmail.com>
Chris Howey <howeyc@gmail.com>
Chris Hundt <hundt@google.com>
Chris Jones <chris@cjones.org> <chris.jones.yar@gmail.com>
Chris Kastorff <encryptio@gmail.com>
Chris Le Roy <brompwnie@users.noreply.github.com>
Chris Lennert <calennert@gmail.com>
Chris Liles <caveryliles@gmail.com>
Chris Manghane <cmang@golang.org>
Chris Marchesi <chrism@vanclueverttech.com>
Chris McGee <sirnewton_01@yahoo.ca> <newton688@gmail.com>
Chris Raynor <raynor@google.com>
Chris Roche <rodaine@gmail.com>
Chris Smith <chrsmith@users.noreply.github.com>
Chris Stockton <chrisstocktonaz@gmail.com>
Chris Taylor <taylorza@gmail.com>
Chris Waldon <christopher.waldon.dev@gmail.com>
Chris Zou <chriszou@ca.ibm.com>
Christian Alexander <christian@linux.com>
Christian Couder <chriscool@tuxfamily.org>
Christian Himpel <chressie@googlemail.com> <chressie@gmail.com>
Christian Muehlhaeuser <muesli@gmail.com>
Christian
Pellegrin <chri@evolware.org>
Christian R. Petrin <christianpetrin@gmail.com>
Christian Svensson <blue@cmd.nu>
Christine Hansmann <chhansmann@gmail.com>
Christoffer Buchholz <christoffer.buchholz@gmail.com>
Christoph Blecker <admin@toph.ca>
Christoph Hack <christoph@tux21b.org>
Christopher Cahoon <chris.cahoon@gmail.com>
Christopher Guiney <chris@guiney.net>
Christopher Henderson <chris@chenderson.org>
Christopher Hlubek <christopher.hlubek@networkteam.com>
Christopher Koch <chrisko@google.com>
Christopher Loessl <cloessl+github@gmail.com>
Christopher Nelson <nadiasvertex@gmail.com>
Christopher Nielsen <m4dh4tt3r@gmail.com>
Christopher Redden <christopher.redden@gmail.com>
Christopher Swenson <cswenson@google.com>
Christopher Thomas <53317512+chrissstomas@users.noreply.github.com>
Christopher Wedgwood <cw@f00f.org>
Christos Zoulas <christos@zoulas.com> <zoulasc@gmail.com>
Christy Perez <christy@linux.vnet.ibm.com>
CL Sung <clsung@gmail.com> <cl_sung@htc.com>

Clement

Chigot <clement.chigot@atos.net>

Clement Skau <clementskau@gmail.com>

Clint J. Edwards <clint.j.edwards@gmail.com>

Cody Oss <the.cody.oss@gmail.com>

Colby Ranger <cranger@google.com>

Colin Arnott <colin@urandom.co.uk>

Colin Cross <ccross@android.com>

Colin Edwards <colin@recursivepenguin.com>

Colin Kennedy <moshen.colin@gmail.com>

Colin Nelson <colnnelson@google.com>

Colin Rice <clr@google.com>

Conrad Irwin <conrad.irwin@gmail.com>

Conrad Meyer <cemeyer@cs.washington.edu>

Conrado Gouvea <conradopl@gmail.com>

Constantin Konstantinidis <constantinkonstantinidis@gmail.com>

Corey Thomasson <cthom.lists@gmail.com>

Corne van der Plas <vdplas@gmail.com>

Cosmos Nicolaou <cnicolaou@google.com>

Costin Chirvasuta <ctin@google.com>

Craig Citro <craigcitro@google.com>

Cristian Staretu <unclejacksons@gmail.com>

Cristo Garca <cgg.code@gmail.com>

cui fliter <imcusg@gmail.com>

Cuihtlauac ALVARADO <cuihtlauac.alvarado@orange.com>

Cuong Manh Le <cuong@orijtech.com>

Curtis La Graff <curtis@lagraff.me>

Cyrill

Schumacher <cyrill@schumacher.fm>

Dai Jie <gzdaijie@gmail.com>

Dai Wentao <dwt136@gmail.com>

Daisuke Fujita <dtanshi45@gmail.com>

Daisuke Suzuki <daisuzu@gmail.com>

Daker Fernandes Pinheiro <daker.fernandes.pinheiro@intel.com>

Damian Gryski <dgryski@gmail.com>

Damien Lespiau <damien.lespiau@gmail.com> <damien.lespiau@intel.com>

Damien Mathieu <42@dmathieu.com>

Damien Neil <dneil@google.com>

Damien Tournoud <damien@platform.sh>

Dan Ballard <dan@mindstab.net>

Dan Caddigan <goldcaddy77@gmail.com>

Dan Callahan <dan.callahan@gmail.com>

Dan Harrington <harringtond@google.com>

Dan Jacques <dnj@google.com>

Dan Johnson <computerdruid@google.com>

Dan McArdle <dmcardle@google.com>

Dan Peterson <dpiddy@gmail.com>

Dan Pupius <dan@medium.com>

Dan Scales <danscales@google.com>
Dan Sinclair <dan.sinclair@gmail.com>
Daniel Cohen <dcohen@gatech.edu>
Daniel Cormier <danielc@knowbe4.com>
Danil de Kok <me@danieldk.eu>
Daniel Fleischman <danielfleischman@gmail.com>
Daniel Ingram <ingramds@appstate.edu>
Daniel
Johansson <dajo2002@gmail.com>
Daniel Kerwin <d.kerwin@gini.net>
Daniel Kessler <dkess@google.com>
Daniel Krech <eikeon@eikeon.com>
Daniel Kumor <rdkumor@gmail.com>
Daniel Langner <s8572327@gmail.com>
Daniel Lidn <daniel.liden.87@gmail.com>
Daniel Lublin <daniel@lublin.se>
Daniel Mangum <georgedanielmangum@gmail.com>
Daniel Marshall <daniel.marshall2@ibm.com>
Daniel Mart <mvdan@mvdan.cc>
Daniel McCarney <cpu@letsencrypt.org>
Daniel Morsing <daniel.morsing@gmail.com>
Daniel Nadasi <dnadasi@google.com>
Daniel Nephin <dnephin@gmail.com>
Daniel Ortiz Pereira da Silva <daniel.particular@gmail.com>
Daniel S. Fava <danielsfava@gmail.com>
Daniel Skinner <daniel@dasa.cc>
Daniel Speichert <daniel@speichert.pl>
Daniel Theophanes <kardianos@gmail.com>
Daniel Upton <daniel@floppy.co>
Daniela Petruzalek <daniela.petruzalek@gmail.com>
Danish Dua <danishdua@google.com>
Danish Prakash <grafitykoncept@gmail.com>
Danny Rosseau <daniel.rosseau@gmail.com>
Daria Kolistratova <daria.kolistratova@intel.com>
Darien
Raymond <admin@v2ray.com>
Darren Elwood <darren@textnode.com>
Darren Grant <darren.e.grant@gmail.com>
Darren McCleary <darren.rmc@gmail.com>
Darshan Parajuli <parajulidarshan@gmail.com>
Datong Sun <dndx@idndx.com>
Dave Borowitz <dborowitz@google.com>
Dave Bort <dbort@golang.org>
Dave Cheney <dave@cheney.net>
Dave Day <djd@golang.org>
Dave Grijalva <dgrijalva@ngmoco.com>
Dave MacFarlane <driusan@gmail.com>
Dave Pifke <dave@pifke.org>

Dave Russell <forfuncsake@gmail.com>
David Anderson <danderson@google.com>
David Barnett <dbarnett@google.com>
David Benjamin <davidben@google.com>
David Black <dblack@atlassian.com>
David Bond <davidsbond93@gmail.com>
David Brophy <dave@brophy.uk>
David Brgin <676c7473@gmail.com>
David Calavera <david.calavera@gmail.com>
David Carlier <devnexen@gmail.com>
David Carter <fresco.raja@gmail.com>
David Chase <drchase@google.com>
David Covert <davidhcovert@gmail.com>
David Crawshaw <david.crawshaw@zentus.com> <crawshaw@google.com> <crawshaw@golang.org>
David
du Colombier <0intro@gmail.com>
David Finkel <david.finkel@gmail.com>
David Forsythe <dforsythe@gmail.com>
David G. Andersen <dave.andersen@gmail.com>
David Glasser <glasser@meteor.com>
David Golden <david@autopragmatic.com>
David Heuschmann <heuschmann.d@gmail.com>
David Howden <dhowden@gmail.com>
David Hubbard <dsp@google.com>
David Jakob Fritz <david.jakob.fritz@gmail.com>
David Jones <dxjones@gmail.com>
David Lazar <lazard@golang.org>
David Leon Gil <coruus@gmail.com>
David McLeish <davemc@google.com>
David Ndungu <dnjuguna@gmail.com>
David NewHamlet <david@newhamlet.com>
David Presotto <presotto@gmail.com>
David Qu <davidqu12345@gmail.com>
David R. Jenni <david.r.jenni@gmail.com>
David Sansome <me@davidsansome.com>
David Stainton <dstainton415@gmail.com>
David Symonds <dsymonds@golang.org>
David Thomas <davidthomas426@gmail.com>
David Timm <dtimm@pivotal.io>
David Titarenco <david.titarenco@gmail.com>
David Tolpin <david.tolpin@gmail.com>
David Url <david@urld.io>
David
Volquartz Lebech <david@lebech.info>
David Wimmer <davidlwimmer@gmail.com>
Davies Liu <davies.liu@gmail.com>
Davor Kapsa <davor.kapsa@gmail.com>
Dean Eigenmann <7621705+decanus@users.noreply.github.com>

Dean Prichard <dean.prichard@gmail.com>
Deepak Jois <deepak.jois@gmail.com>
Deepak S <deepakspavoodath@gmail.com>
Denis Bernard <db047h@gmail.com>
Denis Brandolini <denis.brandolini@gmail.com>
Denis Isaev <idenx@yandex.com>
Denis Nagorny <denis.nagorny@intel.com>
Dennis Kuhnert <mail.kuhnert@gmail.com>
Denys Honsiorovskyi <honsiorovskyi@gmail.com>
Denys Smirnov <denis.smirnov.91@gmail.com>
Derek Buitenhuis <derek.buitenhuis@gmail.com>
Derek Che <drc@yahoo-inc.com>
Derek McGowan <derek@mcgstyle.net>
Derek Parker <parkerderek86@gmail.com>
Derek Phan <derekphan94@gmail.com>
Derek Shockey <derek.shockey@gmail.com>
Dev Ojha <dojha12@gmail.com>
Dev Zhoujun <dev.zhoujun@gmail.com>
Devon H. O'Dell <devon.odell@gmail.com>
Dhaivat Pandit <dhaivatpandit@gmail.com>
Dhananjay Nakrani <dhananjayn@google.com>
Dhiru
Kholia <dhiru.kholia@gmail.com>
Dhruvduddt Jadhav <dhrvduddt.jadhav@gmail.com>
Di Xiao <dixiao@google.com>
Didier Spezia <didier.06@gmail.com>
Diego Medina <fmpwizard@gmail.com>
Diego Siqueira <diego9889@gmail.com>
Dieter Plaetinck <dieter@raintank.io>
Dilyn Corner <dilyn.corner@gmail.com>
Dimitri Sokolyuk <sokolyuk@gmail.com>
Dimitri Tcaciuc <dtcaciuc@gmail.com>
Dina Garmash <dgrmsh@gmail.com>
Diogo Pinela <diogoid7400@gmail.com>
Dirk Gadsden <dirk@esherido.com>
Diwaker Gupta <diwakergupta@gmail.com>
Dmitri Goutnik <dgoutnik@gmail.com>
Dmitri Popov <operator@cv.dp-net.com>
Dmitri Shuralyov <dmitshur@golang.org> <dmitri@shuralyov.com>
Dmitrii Okunev <xaionaro@gmail.com>
Dmitriy Cherchenko <dcherchenko@gmail.com>
Dmitriy Dudkin <dudkin.dmitriy@gmail.com>
Dmitriy Shelenin <deemok@googlemail.com> <deemok@gmail.com>
Dmitriy Vyukov <dvyukov@google.com>
Dmitry Chestnykh <dchest@gmail.com>
Dmitry Doroginin <doroginin@gmail.com>
Dmitry Mottl <dmitry.mottl@gmail.com>
Dmitry

Neverov <dmitry.neverov@gmail.com>
Dmitry Savintsev <dsavints@gmail.com>
Dmitry Yakunin <nonamezeil@gmail.com>
Dmytro Shynkevych <dm.shynk@gmail.com>
Doga Fincan <doga@icloud.com>
Domas Tamauskas <puerdomus@gmail.com>
Domen Ipavec <domen@ipavec.net>
Dominic Della Valle <ddvpublic@Gmail.com>
Dominic Green <dominicgreen1@gmail.com>
Dominik Honnef <dominik.honnef@gmail.com>
Dominik Vogt <vogt@linux.vnet.ibm.com>
Don Byington <don@dbyington.com>
Donald Huang <don.hcd@gmail.com>
Dong-hee Na <donghee.na92@gmail.com>
Donovan Hide <donovanhide@gmail.com>
Doug Anderson <douga@google.com>
Doug Fawley <dfawley@google.com>
Douglas Danger Manley <doug.manley@gmail.com>
Drew Flower <drewvanstone@gmail.com>
Drew Hintz <adhintz@google.com>
Drew Richardson <drewrichardson@gmail.com>
Duco van Amstel <duco.vanamstel@gmail.com>
Duncan Holm <mail@frou.org>
Dustin Carlino <dcarlino@google.com>
Dustin Herbison <djherbis@gmail.com>
Dustin Long <dustmop@gmail.com>
Dustin Sallings <dsallings@gmail.com>
Dustin
Shields-Cloues <dcloues@gmail.com>
Dustin Spicuzza <dustin.spicuzza@gmail.com>
Dvir Volk <dvir@everything.me> <dvirsky@gmail.com>
Dylan Waits <dylan@waits.io>
Ed Schouten <ed@nuxi.nl>
Edan Bedrik <3d4nb3@gmail.com>
Eddie Scholtz <escholtz@google.com>
Eden Li <eden.li@gmail.com>
Eduard Urbach <e.urbach@gmail.com>
Eduardo Ramalho <eduardo.ramalho@gmail.com>
Eduardo Villaseor <evillasrmx@gmail.com>
Edward Muller <edwardam@interlix.com>
Egon Elbre <egonelbre@gmail.com>
Ehren Kret <ehren.kret@gmail.com>
Eitan Adler <lists@eitanadler.com>
Eivind Uggedal <eivind@uggedal.com>
El Mostafa Idrassi <el.mostafa.idrassi@gmail.com>
Elbert Fliek <efliek@gmail.com>
Eldar Rakhimberdin <ibeono@gmail.com>
Elena Grahovac <elena@grahovac.me>

Eli Bendersky <eliben@google.com>
Elias Naur <mail@eliasnaur.com> <elias.naur@gmail.com>
Elliot Morrison-Reed <elliottmr@gmail.com>
Ellison Leao <ellisonleao@gmail.com>
Elvina Yakubova <elvinayakubova@gmail.com>
Emerson Lin <linyintor@gmail.com>
Emil Bektimirov <lefelys@gmail.com>
Emil
Hessman <emil@hessman.se>
Emil Mursalimov <mursalimovemeel@gmail.com>
Emilien Kenler <hello@emilienkenler.com>
Emmanuel Odeke <emm.odeke@gmail.com> <odeke@ualberta.ca>
Emrehan Bati <emrehanbati@gmail.com>
Eno Compton <enocom@google.com>
Eoghan Sherry <ejsherry@gmail.com>
Eric Biggers <ebiggers@google.com>
Eric Brown <browne@vmware.com>
Eric Chiang <eric.chiang.m@gmail.com>
Eric Clark <zerohp@gmail.com>
Eric Daniels <eric@erdaniels.com>
Eric Engestrom <eric@engestrom.ch>
Eric Garrido <ekg@google.com>
Eric Koleda <ekoleda+devrel@google.com>
Eric Lagergren <ericscottlagergren@gmail.com>
Eric Milliken <emilliken@gmail.com>
Eric Pauley <eric@pauley.me>
Eric Ponce <tricokun@gmail.com>
Eric Rescorla <ekr@rtfm.com>
Eric Roshan-Eisner <eric.d.eisner@gmail.com>
Eric Rutherford <erutherford@gmail.com>
Eric Rykwalder <e.rykwalder@gmail.com>
Eric Wang <wangchaogo1990@gmail.com>
Erick Tryzelaar <etryzelaar@google.com>
Erik Aigner <aigner.erik@gmail.com>
Erik Dubbelboer <erik@dubbelboer.com>
Erik
St. Martin <alakriti@gmail.com>
Erik Staab <estaab@google.com>
Erik Westrup <erik.westrup@gmail.com>
Erin Masatsugu <erin.masatsugu@gmail.com>
Ernest Chiang <ernest_chiang@htc.com>
Erwin Oegema <blablaechthema@hotmail.com>
Esko Luontola <esko.luontola@gmail.com>
Ethan Anderson <eanderson@atlassian.com>
Ethan Burns <eaburns@google.com>
Ethan Hur <ethan0311@gmail.com>
Ethan Miller <eamiller@us.ibm.com>
Ethan Reesor <ethan.reesor@gmail.com>

Euan Kemp <euank@euank.com>
Eugene Formanenko <mo4islona@gmail.com>
Eugene Kalinin <e.v.kalinin@gmail.com>
Evan Broder <evan@stripe.com>
Evan Brown <evanbrown@google.com>
Evan Digby <evandigby@gmail.com>
Evan Hicks <evan.hicks2@gmail.com>
Evan Jones <ej@evanjones.ca>
Evan Klitzke <evan@eklitzke.org>
Evan Kroske <evankroske@google.com>
Evan Martin <evan.martin@gmail.com>
Evan Phoenix <evan@phx.io>
Evan Shaw <chickencha@gmail.com>
Evgeniy Kulikov <tuxuls@gmail.com>
Evgeniy Polyakov <zbr@ioremap.net>
Ewan Chou <coocood@gmail.com>
Ewan Valentine
<ewan.valentine89@gmail.com>
Eyal Posener <posener@gmail.com>
F. Talha Altnel <talhaaltnel@hotmail.com>
Fabian Wickborn <fabian@wickborn.net>
Fabian Zaremba <fabian@youreemail.eu>
Fabio Falzoi <fabio.falzoi84@gmail.com>
Fabrizio Milo <mistobaan@gmail.com>
Faiyaz Ahmed <ahmedf@vmware.com>
Fan Hongjian <fan.howard@gmail.com>
Fangming Fang <fangming.fang@arm.com>
Fannie Zhang <fannie.zhang@arm.com>
Fatih Arslan <fatih@arslan.io>
Fazal Majid <majid@apsalar.com>
Fazlul Shahriar <fshahriar@gmail.com>
Federico Bond <federicobond@gmail.com>
Federico Guerinoni <guerinoni.federico@gmail.com>
Federico Simoncelli <fsimonce@redhat.com>
Fedor Indutny <fedor@indutny.com>
Fedor Korotkiy <dartslon@gmail.com>
Felipe Oliveira <felipeweb.programador@gmail.com>
Felix Bnemann <Felix.Buenemann@gmail.com>
Felix Cornelius <9767036+fcornelius@users.noreply.github.com>
Felix Geisendrfer <haimuiba@gmail.com>
Felix Kollmann <fk@konsorten.de>
Ferenc Szabo <frncmx@gmail.com>
Fernandez Ludovic <lfernandez.dev@gmail.com>
Filip
Gruszczyski <gruszczyski@gmail.com>
Filip Haglund <drathier@users.noreply.github.com>
Filip Stanis <fstanis@google.com>
Filippo Valsorda <filippo@golang.org> <filippo@cloudflare.com> <hi@filippo.io>

Firmansyah Adiputra <frm.adiputra@gmail.com>
Florian Forster <octo@google.com>
Florian Uekermann <florian@uekermann-online.de> <f1@uekermann-online.de>
Florian Weimer <fw@deneb.enyo.de>
Florin Papa <fpapa@google.com>
Florin Patan <florinpatan@gmail.com>
Folke Behrens <folke@google.com>
Ford Hurley <ford.hurley@gmail.com>
Forest Johnson <forest.n.johnson@gmail.com>
Francesc Campoy <campoy@golang.org>
Francesco Guardiani <francescoguard@gmail.com>
Francesco Renzi <rentziass@gmail.com>
Francisco Claude <fclaude@recoded.cl>
Francisco Rojas <francisco.rojas.gallegos@gmail.com>
Francisco Souza <francissouza@gmail.com>
Frank Chiarulli Jr <frank@frankchiarulli.com>
Frank Schroeder <frank.schroeder@gmail.com>
Frank Somers <fsomers@arista.com>
Frederic Guillot <frederic.guillot@gmail.com>
Frederick
Kelly Mayle III <frederickmayle@gmail.com>
Frederik Ring <frederik.ring@gmail.com>
Frederik Zipp <fzipp@gmx.de>
Frediano Ziglio <freddy77@gmail.com>
Fredrik Enestad <fredrik.enestad@soundtrackyourbrand.com>
Fredrik Forsmo <fredrik.forsmo@gmail.com>
Fredrik Wallgren <fredrik.wallgren@gmail.com>
Frew Schmidt <github@frew.co>
Frithjof Schulze <schulze@math.uni-hannover.de> <sfritjhjof@gmail.com>
Frits van Bommel <fvbommel@gmail.com>
Fujimoto Kyosuke <kyoro.f@gmail.com>
Fumitoshi Ukai <ukai@google.com>
G. Hussain Chinoy <ghchinoy@gmail.com>
Gaal Yahas <gaal@google.com>
Gabrel Arthr Ptursson <gabriel@system.is>
Gabriel Aszalos <gabriel.aszalos@gmail.com>
Gabriel Guzman <gabe.guzman@gmail.com>
Gabriel Nelle <tehsphinx@web.de>
Gabriel Nicolas Avellaneda <avellaneda.gabriel@gmail.com>
Gabriel Rosenhouse <rosenhouse@gmail.com>
Gabriel Russell <gabriel.russell@gmail.com>
Gabriel Vasile <gabriel.vasile0793@gmail.com>
Gareth Paul Jones <gpj@foursquare.com>
Garret Kelly <gdk@google.com>
Garrick
Evans <garrick@google.com>
Garry McNulty <garrmcnu@gmail.com>
Gary Burd <gary@beagledreams.com> <gary.burd@gmail.com>

Gary Elliott <garyelliott@google.com>
Gaurav Singh <gaurav1086@gmail.com>
Gaurish Sharma <contact@aurishsharma.com>
Gautham Thambidorai <gautham.dorai@gmail.com>
Gauthier Jolly <gauthier.jolly@gmail.com>
Gawen Arab <gawen.arab@c.zen.ly>
Geert-Johan Riemer <gjr19912@gmail.com>
Genevieve Luyt <genevieve.luyt@gmail.com>
Gengliang Wang <ltnwgl@gmail.com>
Geoff Berry <gberry.qdt@qualcommdatacenter.com>
Geoffroy Lorieux <lorieux.g@gmail.com>
Geon Kim <geon0250@gmail.com>
Georg Reinke <guelfey@gmail.com>
George Gkirtsou <ggirtsou@gmail.com>
George Hartzell <hartzell@alerce.com>
George Looshch <looshch@loosh.ch>
George Shammass <george@shamm.as> <georgyo@gmail.com>
George Tsilias <tsiliasg@gmail.com>
Gerasimos (Makis) Maropoulos <kataras2006@hotmail.com>
Gerasimos Dimitriadis <gedimitr@gmail.com>
Gergely Brautigam <skarlso777@gmail.com>
Gernot Vormayr <gvormayr@gmail.com>
Gert
Cuykens <gert.cuykens@gmail.com>
Getulio Snchez <valentin2507@gmail.com>
Ghazni Nattarshah <ghazni.nattarshah@gmail.com>
Gianguido Sora` <g.sora4@gmail.com>
Gideon Jan-Wessel Redelinghuys <gjredelinghuys@gmail.com>
Giles Lean <giles.lean@pobox.com>
Giovanni Bajo <rasky@develer.com>
GitHub User @180909 (70465953) <734461790@qq.com>
GitHub User @6543 (24977596) <6543@obermui.de>
GitHub User @aca (50316549) <acadx0@gmail.com>
GitHub User @ajnrp (1688456) <ajnrp@users.noreply.github.com>
GitHub User @ajz01 (4744634) <ajzdenek@gmail.com>
GitHub User @alkesh26 (1019076) <alkesh26@gmail.com>
GitHub User @andig (184815) <cpuidle@gmx.de>
GitHub User @andrius4669 (4699695) <andrius4669@gmail.com>
GitHub User @as (8127015) <as.utf8@gmail.com>
GitHub User @bakape (7851952) <bakape@gmail.com>
GitHub User @bgadrian (830001) <aditza8@gmail.com>
GitHub User @bontequero (2674999) <bontequero@gmail.com>
GitHub User @cch123 (384546) <buaa.cch@gmail.com>
GitHub User @chainhelen (7046329) <chainhelen@gmail.com>
GitHub
User @chanxuehong (3416908) <chanxuehong@gmail.com>
GitHub User @Cluas (10056928) <Cluas@live.cn>
GitHub User @cncal (23520240) <flycalvin@qq.com>

GitHub User @DQNEO (188741) <dqneo@gmail.com>
GitHub User @Dreamacro (8615343) <chuainian@gmail.com>
GitHub User @dupoxy (1143957) <dupoxy@users.noreply.github.com>
GitHub User @EndlessCheng (7086966) <loli.con@qq.com>
GitHub User @erifan (31343225) <eric.fang@arm.com>
GitHub User @esell (9735165) <eujon.sellers@gmail.com>
GitHub User @fatedier (7346661) <fatedier@gmail.com>
GitHub User @frennkie (6499251) <mail@rhab.de>
GitHub User @geedchin (11672310) <geedchin@gmail.com>
GitHub User @GrigoriyMikhalkin (3637857) <grigoriymikhalkin@gmail.com>
GitHub User @Gusted (25481501) <williamzjl7@hotmail.com>
GitHub User @hengwu0 (41297446) <41297446+hengwu0@users.noreply.github.com>
GitHub User @hitzhangjie (3725760) <hit.zhangjie@gmail.com>
GitHub User @hkhere (33268704) <33268704+hkhere@users.noreply.github.com>
GitHub User
@hopehook (7326168) <hopehook.com@gmail.com>
GitHub User @hqpk0 (13887251) <whaibin01@hotmail.com>
GitHub User @Illirgway (5428603) <illirgway@gmail.com>
GitHub User @itchyny (375258) <itchyny@hatena.ne.jp>
GitHub User @jinmiaoluo (39730824) <jinmiaoluo@icloud.com>
GitHub User @jobbrown (6345470) <msshane2008@gmail.com>
GitHub User @kazysshr (30496953) <kazysshr0301@gmail.com>
GitHub User @kc1212 (1093806) <kc1212@users.noreply.github.com>
GitHub User @komisan19 (18901496) <komiyama6219@gmail.com>
GitHub User @korzhao (64203902) <korzhao95@gmail.com>
GitHub User @Kropekk (13366453) <kamilkropiewnicki@gmail.com>
GitHub User @lgbgbl (65756378) <lgbgbl@qq.com>
GitHub User @lhl2617 (33488131) <l.h.lee2617@gmail.com>
GitHub User @linguohua (3434367) <lghchinaidea@gmail.com>
GitHub User @lloydchang (1329685) <lloydchang@gmail.com>
GitHub User @LotusFenn (13775899) <fenn.lotus@gmail.com>
GitHub User @luochuanhang (96416201) <chuanhangluo@gmail.com>
GitHub User @ly303550688 (11519839) <yang.liu636@gmail.com>
GitHub
User @madiganz (18340029) <zacharywmadigan@gmail.com>
GitHub User @maltalex (10195391) <code@bit48.net>
GitHub User @markruler (38225900) <csu0414@gmail.com>
GitHub User @Matt966 (28551465) <Matt966@users.noreply.github.com>
GitHub User @micnncim (21333876) <micnncim@gmail.com>
GitHub User @mkishere (224617) <224617+mkishere@users.noreply.github.com>
GitHub User @nu50218 (40682920) <nu_ll@icloud.com>
GitHub User @OlgaVlPetrova (44112727) <OVPPetrova@gmail.com>
GitHub User @pierwill (19642016) <pierwill@users.noreply.github.com>
GitHub User @pityonline (438222) <pityonline@gmail.com>
GitHub User @po3rin (29445112) <abctail30@gmail.com>
GitHub User @pokutuna (57545) <popopopokutuna@gmail.com>
GitHub User @povsister (11040951) <pov@mahou-shoujo.moe>
GitHub User @pytimer (17105586) <lixin20101023@gmail.com>

GitHub User @qcrao (7698088) <qcrao91@gmail.com>
GitHub User @ramenjuniti (32011829) <ramenjuniti@gmail.com>
GitHub User @renthraysk (30576707) <renthraysk@gmail.com>
GitHub
User @roudkerk (52280478) <roudkerk@google.com>
GitHub User @saitarunreddy (21041941) <saitarunreddypalla@gmail.com>
GitHub User @SataQiu (9354727) <shidaqiu2018@gmail.com>
GitHub User @seifchen (23326132) <chenxuefeng1207@gmail.com>
GitHub User @shogo-ma (9860598) <Choroma194@gmail.com>
GitHub User @sivchari (55221074) <shibuuuu5@gmail.com>
GitHub User @skanehira (7888591) <sho19921005@gmail.com>
GitHub User @soolaugust (10558124) <soolaugust@gmail.com>
GitHub User @surechen (7249331) <surechen17@gmail.com>
GitHub User @syumai (6882878) <syumai@gmail.com>
GitHub User @tangxi666 (48145175) <tx1275044634@gmail.com>
GitHub User @tatsumack (4510569) <tatsu.mack@gmail.com>
GitHub User @tell-k (26263) <ffk2005@gmail.com>
GitHub User @tennashi (10219626) <tennashio@gmail.com>
GitHub User @uhei (2116845) <uhei@users.noreply.github.com>
GitHub User @uji (49834542) <ujiprogram@gmail.com>
GitHub User @unbyte (5772358) <i@shangyes.net>
GitHub User @uropek (39370426) <uropek@gmail.com>
GitHub
User @utkarsh-extc (53217283) <utkarsh.extc@gmail.com>
GitHub User @witchard (4994659) <witchard@hotmail.co.uk>
GitHub User @wmdngngng (22067700) <wangmingdong@gmail.com>
GitHub User @wolf1996 (5901874) <ksgiv37@gmail.com>
GitHub User @yah01 (12216890) <kagaminehuan@gmail.com>
GitHub User @yuanhh (1298735) <yuan415030@gmail.com>
GitHub User @zikaeroh (48577114) <zikaeroh@gmail.com>
GitHub User @ZZMarquis (7624583) <zhonglingjian3821@163.com>
Giulio Iotti <dullgiulio@gmail.com>
Giulio Micheloni <giulio.micheloni@gmail.com>
Giuseppe Valente <gvalente@arista.com>
Gleb Stepanov <glebstepanov1992@gmail.com>
Glenn Brown <glennb@google.com>
Glenn Lewis <gmlewis@google.com>
Gordon Klaus <gordon.klaus@gmail.com>
Gordon Tyler <gordon@doxxx.net>
Grace Han <hgrace503@gmail.com>
Graham King <graham4king@gmail.com>
Graham Miller <graham.miller@gmail.com>
Grant Griffiths <ggp493@gmail.com>
Green Lightning <GreenLightning.git@googlemail.com>
Greg Poirier <greg.istehbest@gmail.com>
Greg Steuck
<gnezdo+github@google.com>
Greg Thelen <gthelen@google.com>

Greg Ward <greg@gerg.ca>
Grgoire Delattre <gregoire.delattre@gmail.com>
Gregory Man <man.gregory@gmail.com>
Gregory Petrosyan <gregory.petrosyan@gmail.com>
Guilherme Caruso <gui.martinscaruso@gmail.com>
Guilherme Garnier <guilherme.garnier@gmail.com>
Guilherme Goncalves <guilhermeaugustosg@gmail.com>
Guilherme Rezende <guilhermebr@gmail.com>
Guilherme Souza <32180229+gqgs@users.noreply.github.com>
Guillaume Blaquiere <guillaume.blaquiere@gmail.com>
Guillaume J. Charmes <guillaume@charmes.net>
Guillaume Sottas <guillaumesottas@gmail.com>
Gnther Noack <gnoack@google.com>
Guobiao Mei <meiguobiao@gmail.com>
Guodong Li <guodongli@google.com>
Guoliang Wang <iamwgliang@gmail.com>
Guoqi Chen <chenguoqi@loongson.cn>
Gustav Paul <gustav.paul@gmail.com>
Gustav Westling <gustav@westling.xyz>
Gustavo Franco <gustavorfranco@gmail.com>
Gustavo Niemeyer <gustavo@niemeyer.net> <n13m3y3r@gmail.com>
Gwenael Treguier <gwenn.kahz@gmail.com>
Gyu-Ho
Lee <gyuhox@gmail.com>
H. brahim Gngr <igungor@gmail.com>
Hajime Hoshi <hajimehoshi@gmail.com>
Hallgrimur Gunnarsson <halg@google.com>
HAMANO Tsukasa <hamano@osstech.co.jp>
Han-Wen Nienhuys <hanwen@google.com>
Hang Qian <hangqian90@gmail.com>
Hanjun Kim <hallazzang@gmail.com>
Hanlin He <hanling.he@gmail.com>
Hanlin Shi <shihanlin9@gmail.com>
Hans Nielsen <hans@stackallocated.com>
Hao Mou <mouhao.mu@gmail.com>
Haoran Luo <haoran.luo@chaitin.com>
Haosdent Huang <haosdent@gmail.com>
Harald Nordgren <haraldnordgren@gmail.com>
Hari haran <hariharan.uno@gmail.com>
Hariharan Srinath <srinathh@gmail.com>
Harley Laue <losinggeneration@gmail.com>
Harry Moreno <morenoh149@gmail.com>
Harshavardhana <hrshvardhana@gmail.com>
Hasan Ozgan <hasan@ozgan.net>
Hasit Bhatt <hasit.p.bhatt@gmail.com>
Hauke Lffler <hloeffler@users.noreply.github.com>
Hvard Haugen <havard.haugen@gmail.com>
He Liu <liulonnie@gmail.com>

Hector Chu <hectorchu@gmail.com>
Hector Martin Cantero <hector@marcansoft.com>
Hein Khant
Zaw <heinkhantzaw1@gmail.com>
Henning Schmiedehausen <henning@schmiedehausen.org>
Henrik Edwards <henrik.edwards@gmail.com>
Henrik Hodne <henrik@hodne.io>
Henrique Vicente <henriquevicente@gmail.com>
Henry Adi Sumarto <henry.adisumarto@gmail.com>
Henry Bubert <google@mindeco.de>
Henry Chang <mr.changyuheng@gmail.com>
Henry Clifford <h.a.clifford@gmail.com>
Henry Wong <liushuai.wang@elastic.co>
Herbert Georg Fischer <herbert.fischer@gmail.com>
Herbie Ong <herbie@google.com>
Heschi Kreinick <heschi@google.com>
Hidetatsu Yaginuma <ygnmhdt@gmail.com>
Hilko Bengen <bengen@hilluzination.de>
Himanshu Kishna Srivastava <28himanshu@gmail.com>
Hiroaki Nakamura <hnakamur@gmail.com>
Hiromichi Ema <ema.hiro@gmail.com>
Hironao OTSUBO <motemen@gmail.com>
Hiroshi Ioka <hirochachacha@gmail.com>
Hitoshi Mitake <mitake.hitoshi@gmail.com>
Holden Huang <ttyh061@gmail.com>
Hong Ruiqi <hongruiqi@gmail.com>
Hongfei Tan <feilengcui008@gmail.com>
Horacio Duran <horacio.duran@gmail.com>
Horst Rutter <hhrutter@gmail.com>
Hossein
Sheikh Attar <hattar@google.com>
Hossein Zolfi <hossein.zolfi@gmail.com>
Howard Zhang <howard.zhang@arm.com>
Hsin Tsao <tsao@google.com>
Hsin-Ho Yeh <yhh92u@gmail.com>
Hu Keping <hukeping@huawei.com>
Huan Du <i@huandu.me>
Hugues Bruant <hugues.bruant@gmail.com>
Huy Le <huy.dinh.le.89@gmail.com>
Hyang-Ah Hana Kim <hakim@google.com> <hyangah@gmail.com>
Hyoyoung Chang <hyoyoung@gmail.com>
Ian Cottrell <iancottrell@google.com>
Ian Davis <nospam@iandavis.com>
Ian Gudger <ian@loosescre.ws>
Ian Haken <ihaken@netflix.com>
Ian Kent <iankent85@gmail.com>
Ian Lance Taylor <iant@golang.org>
Ian Leue <ian@appboy.com>

Ian Mckay <iann0036@gmail.com>
Ian Tay <iantay@google.com>
Ian Zapolsky <ianzapolsky@gmail.com>
Ibrahim AshShohail <ibra.sho@gmail.com>
Icarus Sparry <golang@icarus.freeuk.com>
Iccha Sethi <icchasethi@gmail.com>
Ichinose Shogo <shogo82148@gmail.com>
Idora Shinatose <idora.shinatose@gmail.com>
Ignacio Hagopian <jsign.uy@gmail.com>
Igor Bernstein <igorbernstein@google.com>
Igor
Bolotnikov <igor.v.bolotnikov@gmail.com>
Igor Dolzhikov <bluesriverz@gmail.com>
Igor Vashyst <ivashyst@gmail.com>
Igor Zhilianin <igor.zhilianin@gmail.com>
Ikko Ashimine <eltoclear@gmail.com>
Ilya Yalovyy <yalovoy@gmail.com>
Ilya Chukov <56119080+Elias506@users.noreply.github.com>
Ilya Mateyko <me@astrophena.name>
Ilya Sinelnikov <sidhmangh@gmail.com>
Ilya Tocar <ilya.tocar@intel.com>
INADA Naoki <songofacandy@gmail.com>
Inanc Gumus <m@inanc.io>
Ingo Gottwald <in.gottwald@gmail.com>
Ingo Krabbe <ikrabbe.ask@gmail.com>
Ingo Oeser <nightlyone@googlemail.com> <nightlyone@gmail.com>
Ioannis Georgoulas <geototti21@hotmail.com>
Irbe Krumina <irbekrm@gmail.com>
Irfan Sharif <irfanmahmoudsharif@gmail.com>
Irieda Noboru <irieda@gmail.com>
Isaac Ardis <isaac.ardis@gmail.com>
Isaac Wagner <ibw@isaacwagner.me>
Isfan Azhabil <isfanazhabil@gmail.com>
Iskander Sharipov <iskander.sharipov@intel.com> <quasilyte@gmail.com>
Issac Trotts <issactrotts@google.com>
Ivan Babrou <ivan@cloudflare.com>
Ivan
Bertona <ivan.bertona@gmail.com>
Ivan Krasin <krasin@golang.org>
Ivan Kutuzov <arbrix@gmail.com>
Ivan Markin <sw@nogoegst.net>
Ivan Moscoso <moscoso@gmail.com>
Ivan Osadchiy <ivan.osadchii@gmail.com>
Ivan Sharavuev <shpiwan@gmail.com>
Ivan Trubach <mr.trubach@icloud.com>
Ivan Ukhov <ivan.ukhov@gmail.com>
Ivy Evans <ivy@ivyevans.net>
Jaana Burcu Dogan <jbd@google.com> <jbd@golang.org> <burcujdogan@gmail.com>

Jaap Aarts <jaap.aarts1@gmail.com>
Jack Britton <jackxbritton@gmail.com>
Jack Lindamood <jlindamo@justin.tv>
Jack You <jamesyou@google.com>
Jacob Baskin <jbaskin@google.com>
Jacob Blain Christen <dweomer5@gmail.com>
Jacob H. Haven <jacob@cloudflare.com>
Jacob Hoffman-Andrews <github@hoffman-andrews.com>
Jacob Walker <jacobwalker0814@gmail.com>
Jaden Teng <long.asyn@gmail.com>
Jae Kwon <jae@tendermint.com>
Jake B <doogie1012@gmail.com>
Jake Ciolek <jakub@ciolek.dev>
Jakob Borg <jakob@nym.se>
Jakob Weisblat <jakobw@mit.edu>
Jakub ajka <jcajka@redhat.com>
Jakub Kaczmarzyk <jakubk@mit.edu>
Jakub
Ryszard Czarnowicz <j.czarnowicz@gmail.com>
Jakub Warczarek <jakub.warczarek@gmail.com>
Jamal Carvalho <jamal.a.carvalho@gmail.com>
James Aguilar <jaguilar@google.com>
James Bardin <j.bardin@gmail.com>
James Chacon <jchacon@google.com>
James Clarke <jrtc27@jrtc27.com>
James Cowgill <James.Cowgill@imgtec.com>
James Craig Burley <james-github@burleyarch.com>
James David Chalfant <james.chalfant@gmail.com>
James Eady <jmeady@google.com>
James Fennell <jpfennell@google.com>
James Fysh <james.fysh@gmail.com>
James Gray <james@james4k.com>
James Harris <mailjamesharris@gmail.com>
James Hartig <fastest963@gmail.com>
James Kasten <jdkasten@google.com>
James Lawrence <jljatone@gmail.com>
James Meneghello <rawrz0r@gmail.com>
James Myers <jfmyers9@gmail.com>
James Naftel <james.naftel@gmail.com>
James Neve <jamesoneve@gmail.com>
James Nugent <james@jen20.com>
James P. Cooper <jamespcooper@gmail.com>
James Robinson <jamesr@google.com> <jamesr.gatech@gmail.com>
James Schofield <james@shoeboxapp.com>
James
Smith <jrs1995@icloud.com>
James Sweet <james.sweet88@googlemail.com>
James Toy <nil@opensesame.st>

James Treanor <jtreanor3@gmail.com>
James Tucker <raggi@google.com>
James Whitehead <jnwhiteh@gmail.com>
Jamie Beverly <jamie.r.beverly@gmail.com>
Jamie Gennis <jgennis@google.com> <jgennis@gmail.com>
Jamie Kerr <jkerr113@googlemail.com>
Jamie Liu <jamieliu@google.com>
Jamie Stackhouse <contin673@gmail.com>
Jamie Turner <jamwt@dropbox.com>
Jamie Wilkinson <jaq@spacepants.org>
Jamil Djadala <djadala@gmail.com>
Jan Berktold <jan@berktold.co>
Jan H. Hosang <jan.hosang@gmail.com>
Jan Kratochvil <jan.kratochvil@redhat.com>
Jan Lehnardt <jan@apache.org>
Jan Mercl <0xjnml@gmail.com> <befelemepeseveze@gmail.com>
Jan Newmarch <jan.newmarch@gmail.com>
Jan Pilzer <jan.pilzer@gmx.de>
Jan Steinke <jan.steinke@gmail.com>
Jan Ziak <0xe2.0x9a.0x9b@gmail.com>
Jani Monoses <jani.monoses@ubuntu.com> <jani.monoses@gmail.com>
Jannis Andrija Schnitzer <jannis@schnitzer.im>
Jared Allard
<jaredallard@users.noreply.github.com>
Jared Culp <jculp14@gmail.com>
Jaroslavas Poepko <jp@webmaster.ms>
Jason A. Donenfeld <Jason@zx2c4.com>
Jason Baker <jason-baker@users.noreply.github.com>
Jason Barnett <jason.w.barnett@gmail.com>
Jason Buberel <jbuberel@google.com>
Jason Chu <jasonchujc@gmail.com>
Jason Del Ponte <delpontej@gmail.com>
Jason Hall <jasonhall@google.com>
Jason Keene <jasonkeene@gmail.com>
Jason LeBrun <jblebrun@gmail.com>
Jason Smale <jsmale@zendesk.com>
Jason Travis <infomaniac7@gmail.com>
Jason Wangsadinata <jwangsadinata@gmail.com>
Javier Kohen <jkohen@google.com>
Javier Revillas <jrevillas@massivedynamic.io>
Javier Segura <javism@gmail.com>
Jay Chen <chenjie@chenjie.info>
Jay Conrod <jayconrod@google.com>
Jay Lee <BusyJayLee@gmail.com>
Jay Taylor <outtatime@gmail.com>
Jay Weiskopf <jay@jayschwa.net>
Jean de Klerk <deklerk@google.com>
Jean-Andr Santoni <jean.andre.santoni@gmail.com>

Jean-Francois Bustarret <jf@bustarret.com>
Jean-Francois Cantin <jfcantin@gmail.com>
Jean-Hadrien
Chabran <jh@chabran.fr>
Jean-Marc Eurin <jmeurin@google.com>
Jean-Nicolas Moal <jn.moal@gmail.com>
Jed Denlea <jed@fastly.com>
Jdrzej Szczepaniak <jbszczepaniak@gmail.com>
Jeet Parekh <jeetparekh96@gmail.com>
Jeevanandam M <jeeva@myjeeva.com>
Jeff (Zhefu) Jiang <jeffjiang@google.com>
Jeff Craig <jeffcraig@google.com>
Jeff Dupont <jeff.dupont@gmail.com>
Jeff Hodges <jeff@somethingsimilar.com>
Jeff Johnson <jrjohnson@google.com>
Jeff R. Allen <jra@nella.org> <jeff.allen@gmail.com>
Jeff Sickel <jas@corpus-callosum.com>
Jeff Wendling <jeff@spacemonkey.com>
Jeff Wentworth <j.wentworth@gmail.com>
Jeff Widman <jeff@jeffwidman.com>
Jeffrey H <jeffreyh192@gmail.com>
Jelte Fennema <github-tech@jeltef.nl>
Jens Frederich <jfrederich@gmail.com>
Jeremiah Harmsen <jeremiah@google.com>
Jeremy Banks <_@jeremy.ca>
Jeremy Canady <jcanady@gmail.com>
Jeremy Faller <jeremy@golang.org>
Jeremy Jackins <jeremyjackins@gmail.com>
Jeremy Jay <jeremy@pbnjay.com>
Jeremy Schlatter <jeremy.schlatter@gmail.com>
Jero
Bado <tokidokitalkyou@gmail.com>
Jeroen Bobbeldijk <jerbob92@gmail.com>
Jeroen Simonetti <jeroen@simonetti.nl>
Jrme Doucet <jerdct@gmail.com>
Jerrin Shaji George <jerrinsg@gmail.com>
Jess Frazelle <me@jessfraz.com>
Jesse Szwedko <jesse.szwedko@gmail.com>
Jess Espino <jespinog@gmail.com>
Jia Zhan <jzhan@uber.com>
Jiacai Liu <jiacai2050@gmail.com>
Jiahao Lu <lujjjh@gmail.com>
Jiahua Wang <wjh180909@gmail.com>
Jianing Yu <jnyu@google.com>
Jianqiao Li <jianqiaoli@google.com>
Jiayu Yi <yijiayu@gmail.com>
Jie Ma <jienius@outlook.com>
Jihyun Yu <yjh0502@gmail.com>

Jim Cote <jfcote87@gmail.com>
Jim Kingdon <jim@bolt.me>
Jim McGrath <jimmc2@gmail.com>
Jim Minter <jminter@redhat.com>
Jimmy Frasche <soapboxcicero@gmail.com>
Jimmy Zelinskie <jimmyzelinskie@gmail.com>
Jin-wook Jeong <jeweljar@hanmail.net>
Jingcheng Zhang <diogin@gmail.com>
Jingguo Yao <yaojingguo@gmail.com>
Jingnan Si <jingnan.si@gmail.com>
Jinkun Zhang <franksnolf@gmail.com>
Jinwen Wo <wojinwen@huawei.com>
Jiong Du
<londdevil@gmail.com>
Jirka Dank <dnk@mail.muni.cz>
Jiulong Wang <jiulongw@gmail.com>
Joakim Sembrant <serbaut@gmail.com>
Jochen Weber <jochen.weber80@gmail.com>
Joe Bowbeer <joe.bowbeer@gmail.com>
Joe Cortopassi <joe@joecortopassi.com>
Joe Farrell <joe2farrell@gmail.com>
Joe Harrison <joehazzers@gmail.com>
Joe Henke <joed.henke@gmail.com>
Joe Kyo <xunianzu@gmail.com>
Joe Poirier <jdpoirier@gmail.com>
Joe Richey <joerichey@google.com>
Joe Shaw <joe@joeshaw.org>
Joe Sylve <joe.sylve@gmail.com>
Joe Tsai <joetsai@digital-static.net>
Joel Courtney <euphemize@gmail.com>
Joel Ferrier <joelferrier@google.com>
Joel Sing <joel@sing.id.au> <jsing@google.com>
Jol Stemmer <jstemmer@google.com>
Joel Stemmer <stemmertech@gmail.com>
Joey Geiger <jgeiger@users.noreply.github.com>
Johan Brandhorst <johan.brandhorst@gmail.com>
Johan Euphrosine <propy@google.com>
Johan Jansson <johan.jansson@iki.fi>
Johan Knutzen <johan@senri.se>
Johan Sageryd <j@1616.se>
Johannes Altmanninger <aclopte@gmail.com>
Johannes
Huning <johannes.huning@gmail.com>
John Asmuth <jasmuth@gmail.com>
John Bampton <jbampton@gmail.com>
John Beisley <huin@google.com>
John C Barstow <jbowtie@amathaine.com>
John DeNero <denero@google.com>

John Dethridge <jcd@golang.org>
John Gibb <johngibb@gmail.com>
John Gilik <john@jgilik.com>
John Graham-Cumming <jgc@jgc.org> <jgrahamc@gmail.com>
John Howard Palevich <jack.palevich@gmail.com>
John Jago <johnjago@protonmail.com>
John Jeffery <jjeffery@sp.com.au>
John Jenkins <twodopeshaggy@gmail.com>
John Kelly <jkelly@squarespace.com>
John Leidegren <john.leidegren@gmail.com>
John McCabe <john@johnmccabe.net>
John Moore <johnkenneth.moore@gmail.com>
John Newlin <jnewlin@google.com>
John Olheiser <john.olheiser@gmail.com>
John Papandriopoulos <jpap.code@gmail.com>
John Potocny <johnp@vividcortex.com>
John R. Lenton <jlenton@gmail.com>
John Schnake <schnake.john@gmail.com>
John Shahid <jvshahid@gmail.com>
John Tuley <john@tuley.org>
John Weldon <johnweldon4@gmail.com>
Johnny Luo <johnnyluo1980@gmail.com>
Jon
Chen <jchen@justin.tv>
Jon Johnson <jonjohnson@google.com>
Jonas Bernoulli <jonas@bernoul.li>
Jonathan Albrecht <jonathan.albrecht@ibm.com>
Jonathan Allie <jonallie@google.com>
Jonathan Amsterdam <jba@google.com>
Jonathan Boulle <jonathanboulle@gmail.com>
Jonathan Chen <dijonkitchen@users.noreply.github.com>
Jonathan Feinberg <feinberg@google.com>
Jonathan Gold <jgold.bg@gmail.com>
Jonathan Hseu <jhseu@google.com>
Jonathan Mark <jhmark@xenops.com> <jhmark000@gmail.com>
Jonathan Nieder <jrn@google.com>
Jonathan Pentecost <pentecostjonathan@gmail.com>
Jonathan Pittman <jmpittman@google.com> <jonathan.mark.pittman@gmail.com>
Jonathan Rudenberg <jonathan@titanous.com>
Jonathan Stacks <jonstacks13@gmail.com>
Jonathan Swinney <jswinney@amazon.com>
Jonathan Wills <runningwild@gmail.com>
Jonathon Lacher <jonathon.lacher@gmail.com>
Jongmin Kim <atomaths@gmail.com>
Joonas Kuorilehto <joneskoo@derbian.fi>
Joop Kiefte <ikojba@gmail.com> <joop@kiefte.net>
Jordan Christiansen

<xordspar0@gmail.com>
Jordan Krage <jmank88@gmail.com>
Jordan Lewis <jordanthelewis@gmail.com>
Jordan Liggitt <liggitt@google.com>
Jordan Rhee <jordanrh@microsoft.com>
Jordan Rupprecht <rupprecht@google.com>
Jordi Martin <jordimartin@gmail.com>
Jorge Araya <jorgejavieran@yahoo.com.mx>
Jorge L. Fatta <jorge.fatta@auth0.com>
Jorge Troncoso <jatron@google.com>
Jos Visser <josv@google.com>
Josa Gesell <josa@gesell.me>
Jose Luis Vazquez Gonzalez <josvazg@gmail.com>
Joseph Bonneau <jcb@google.com>
Joseph Holsten <joseph@josephholsten.com>
Joseph Morag <sefim96@gmail.com>
Josh Baum <joshbaum@google.com>
Josh Bleecher Snyder <josharian@gmail.com>
Josh Chorlton <jchorlton@gmail.com>
Josh Deprez <josh.deprez@gmail.com>
Josh Goebel <dreamer3@gmail.com>
Josh Hoak <jhoak@google.com>
Josh Holland <jrh@joshh.co.uk>
Josh Rickmar <jrick@companyzero.com>
Josh Roppo <joshroppo@gmail.com>
Josh Varga <josh.varga@gmail.com>
Joshua Bezaleel Abednego <joshua.bezaleel@gmail.com>
Joshua Boelter <joshua.boelter@intel.com>
Joshua
Chase <jcJoshuaChase@gmail.com>
Joshua Crowgey <jcrowgey@uw.edu>
Joshua Harshman <joshgreyhat@gmail.com>
Joshua M. Clulow <josh.clulow@joyent.com>
Joshua Rubin <joshua@rubixconsulting.com>
Josselin Costanzi <josselin@costanzi.fr>
Jostein Stuhauug <js@solidsystem.no>
JP Sugarbroad <jpsugar@google.com>
JT Olds <jtolds@xnet5.com>
JT Olio <hello@jtolio.com>
Juan Carlos <juanjcsr@gmail.com>
Juan Pablo Civile <elementohb@gmail.com>
Jude Pereira <judebpereira@gmail.com>
Jukka-Pekka Kekkonen <karatepekka@gmail.com>
Julia Hansbrough <flowerhack@google.com>
Julian Kornberger <jk+github@digineo.de>
Julian Pastarmov <pastarmovj@google.com>
Julian Phillips <julian@quantumfyre.co.uk>
Julian Tibble <julian.tibble@gmail.com>

Julie Qiu <julie@golang.org>
Julien Kauffmann <julien.kauffmann@freelan.org>
Julien Salleyron <julien.salleyron@gmail.com>
Julien Schmidt <google@julienschmidt.com>
Julien Tant <julien@craftyx.fr>
Julio Montes <julio.montes@intel.com>
Jun Zhang <jim.zoumo@gmail.com>
Junchen
Li <junchen.li@arm.com>
Junda Liu <junda@celer.network>
Jungho Ahn <jhahn@google.com>
Junya Hayashi <ledmonster@gmail.com>
Juraj Sukop <sukop@users.noreply.github.com>
Jure Ham <jure.ham@zemanta.com>
Justin Gracenin <jgracenin@gmail.com>
Justin Li <git@justinli.net>
Justin Nu <nuss.justin@gmail.com>
Justyn Temme <justyntemme@gmail.com>
Kai Backman <kaib@golang.org>
Kai Dong <dokia2357@gmail.com>
Kai Lke <kai@kinvolk.io>
Kai Trukenmiller <ktye78@gmail.com>
Kale Blankenship <kale@lemnisis.com>
Kaleb Elwert <kelwert@atlassian.com>
Kalman Bekesi <kalmanb@google.com>
Kamal Aboul-Hosn <aboulhosn@google.com>
Kamil Chmielewski <kamil.chm@gmail.com>
Kamil Kisiel <kamil@kamilkisiel.net> <kamil.kisiel@gmail.com>
Kamil Rytarowski <krytarowski@users.noreply.github.com>
Kang Hu <hukangustc@gmail.com>
Kanta Ebihara <kantaebihara@gmail.com>
Karan Dhiman <karandhi@ca.ibm.com>
Karel Pazdera <pazderak@gmail.com>
Karoly Negyesi <chx1975@gmail.com>
Karsten Khler <karsten.koehler95@gmail.com>
Karthik
Nayak <karthik.188@gmail.com>
Kashav Madan <kshvmdn@gmail.com>
Kate Manson <kate.manson@izettle.com>
Katharine Berry <ktbry@google.com>
Katie Hockman <katie@golang.org>
Kato Kazuyoshi <kato.kazuyoshi@gmail.com>
Katrina Owen <katrina.owen@gmail.com>
Kaviraj Kanagaraj <kavirajkanagaraj@gmail.com>
Kay Zhu <kayzhu@google.com>
Kazuhiro Sera <seratch@gmail.com>
KB Sriram <kbsriram@google.com>
Keegan Carruthers-Smith <keegan.csmith@gmail.com>

Kei Son <hey.calmdown@gmail.com>
Keiichi Hirobe <chalenge.akane@gmail.com>
Keiji Yoshida <keijiyoshida.mail@gmail.com>
Keisuke Kishimoto <keisuke.kishimoto@gmail.com>
Keith Ball <inflatablewoman@gmail.com>
Keith Randall <khr@golang.org>
Keith Rarick <kr@xph.us>
Kelly Heller <pestophagous@gmail.com>
Kelsey Hightower <kelsey.hightower@gmail.com>
Kelvin Foo Chuan Lyi <vmirage@gmail.com>
Kemal Elmizan <kemalelmizan@gmail.com>
Ken Friedenbach <kenliz@cruzio.com>
Ken Rockot <ken@oz.gs> <ken.rockot@gmail.com>
Ken Sedgwick <ken@bonsai.com>
Ken Thompson <ken@golang.org>
Kenichi
Tsunokawa <kenichi.tsunokawa@gmail.com>
Kenji Kaneda <kenji.kaneda@gmail.com>
Kenji Yano <kenji.yano@gmail.com>
Kenneth Shaw <kenshaw@gmail.com>
Kenny Grant <kennygrant@gmail.com>
Kensei Nakada <handbomusic@gmail.com>
Kenta Mori <zoncoen@gmail.com>
Kerollos Magdy <kerolloz@yahoo.com>
Ketan Parmar <ketanbparmar@gmail.com>
Kevan Swanberg <kevswanberg@gmail.com>
Kevin Albertson <kevin.albertson@mongodb.com>
Kevin Ballard <kevin@sb.org>
Kevin Burke <kev@inburke.com>
Kvin Dunglas <dunglas@gmail.com>
Kevin Gillette <extemporalgenome@gmail.com>
Kevin Herro <kevin109104@gmail.com>
Kevin Kirsche <kev.kirsche@gmail.com>
Kevin Klues <klueska@gmail.com> <klueska@google.com>
Kevin Malachowski <chowski@google.com>
Kevin Parsons <kevpar@microsoft.com>
Kevin Ruffin <kruffin@gmail.com>
Kevin Vu <kevin.m.vu@gmail.com>
Kevin Zita <bleedgreenandgold@gmail.com>
Keyan Pishdadian <kpishdadian@gmail.com>
Keyuan Li <keyuanli123@gmail.com>
Kezhu Wang <kezhuw@gmail.com>
Khosrow Moossavi <khos2ow@gmail.com>
Kieran
Colford <kieran@kcolford.com>
Kieran Gorman <kieran.j.gorman@gmail.com>
Kim Shrier <kshrier@racktopsystems.com>
Kim Yongbin <kybinz@gmail.com>

Kir Kolyshkin <kolyshkin@gmail.com>
Kirill Korotaev <kirillx@gmail.com>
Kirill Motkov <Motkov.Kirill@gmail.com>
Kirill Smelkov <kirr@nexedi.com>
Kirill Tatchihin <kirabsuir@gmail.com>
Kirk Han <kirk91.han@gmail.com>
Kirklin McDonald <kirklin.mcdonald@gmail.com>
KJ Tsanaktisidis <ktsanaktisidis@zendesk.com>
Klaus Post <klauspost@gmail.com>
Kodie Goodwin <kodiegoodwin@gmail.com>
Koichi Shiraishi <zchee.io@gmail.com>
Koki Ide <niconegoto@yahoo.co.jp>
Koki Tomoshige <tomocy.dev@gmail.com>
Komu Wairagu <komuw05@gmail.com>
Konstantin <konstantin8105@gmail.com>
Konstantin Shaposhnikov <k.shaposhnikov@gmail.com>
Koya IWAMURA <kiwamura0314@gmail.com>
Kris Kwiatkowski <kris@cloudflare.com>
Kris Nova <kris@nivenly.com>
Kris Rousey <krousey@google.com>
Krishna Birla <krishnabirla16@gmail.com>
Kristopher Watts <traetox@gmail.com>
Krzysztof
Dbrowski <krzysdabro@live.com>
Kshitij Saraogi <kshitijgaraogi@gmail.com>
Kun Li <likunarmstrong@gmail.com>
Kunpei Sakai <namusyaka@gmail.com>
Kuntal Majumder <hellozee@disroot.org>
Kush Patel <kush.patel@hootsuite.com>
Kyle Consalus <consalus@gmail.com>
Kyle Isom <kyle@gokyle.net>
Kyle Jones <kyle@kyledj.com>
Kyle Lemons <kyle@kylelemons.net> <kevlar@google.com>
Kyle Nusbaum <kyle@datadog.com>
Kyle Shannon <kyle@pobox.com>
Kyle Spiers <eiais@google.com>
Kyle Wood <kyle@kylewood.cc>
Kyohei Kadota <lufia@lufia.org>
Kyrylo Silin <silin@kyrylo.org>
L Campbell <unpantso@gmail.com>
Lai Jiangshan <eag0628@gmail.com>
Lajos Papp <lalyos@yahoo.com>
Lakshay Garg <lakshay.garg.1996@gmail.com>
Lann Martin <lanm@google.com>
Lanre Adelowo <yo@lanre.wtf>
Lapo Luchini <lapo@lapo.it>
Larry Clapp <larry@theclapp.org>
Larry Hosken <lahosken@golang.org>

Lars Jeppesen <jeppesen.lars@gmail.com>
Lars Lehtonen <lars.lehtonen@gmail.com>
Lars Wiegman <lars@namsral.com>
Larz Conwell <larzconwell@gmail.com>
Laurent
Voisin <lpvoisin@gmail.com>
Laurie Clark-Michalek <laurie@qubit.com>
LE Manh Cuong <cuong.manhle.vn@gmail.com>
Lee Hinman <hinman@gmail.com>
Lee Packham <lpackham@gmail.com>
Lehner Florian <dev@der-flo.net>
Leigh McCulloch <leighmcc@gmail.com>
Leo Antunes <leo@costela.net>
Leo Rudberg <ljr@google.com>
Leon Klingele <git@leonklingele.de>
Leonard Wang <>wangdeyu0907@gmail.com> <wangdeyu@golangcn.org>
Leonardo Comelli <leonardo.comelli@gmail.com>
Leonel Quinteros <leonel.quinteros@gmail.com>
Lev Shamardin <shamardin@gmail.com>
Lewin Bormann <lewin.bormann@gmail.com>
Lewis Waddicor <nemesismk2@gmail.com>
Li-Yu Yu <aaronyu@google.com>
Liam Haworth <liam@haworth.id.au>
Lily Chung <lilithkchung@gmail.com>
Lingchao Xin <douglarek@gmail.com>
Lion Yang <lion@aosc.xyz>
Liz Rice <liz@lizrice.com>
Lize Cai <lizzcai1@gmail.com>
Lloyd Dewolf <foolswisdom@gmail.com>
Llus Batlle i Rossell <viric@viric.name>
Lorenz Bauer <lmb@cloudflare.com>
Lorenz Brun <lorenz@brun.one>
Lorenz Nickel <mail@lorenznickel.de>
Lorenzo
Masini <rugginoso@develer.com>
Lorenzo Stoakes <lstoakes@gmail.com>
Louis Kruger <louisk@google.com>
Luan Santos <cfcluan@gmail.com>
Lubomir I. Ivanov <neolit123@gmail.com>
Luca Bruno <luca.bruno@coreos.com>
Luca Greco <luca.greco@alcacoop.it>
Luca Spiller <luca@stackednotion.com>
Lucas Bremgartner <lucas.bremgartner@gmail.com>
Lucas Clemente <lclemente@google.com>
Lucien Stuker <lucien.stuker@gmail.com>
Lucio De Re <lucio.dere@gmail.com>
Ludi Rehak <ludi317@gmail.com>
Luigi Riefolo <luigi.riefolo@gmail.com>

Luit van Drongelen <luitvd@gmail.com>
Luka Zakrajek <tr00.g33k@gmail.com>
Luka Zitnik <luka.zitnik@gmail.com>
Lukasz Milewski <lmmilewski@gmail.com>
Luke Champine <luke.champine@gmail.com>
Luke Curley <qpingu@gmail.com>
Luke Granger-Brown <git@lukegb.com>
Luke Shumaker <lukeshu@datawire.io>
Luke Young <bored-engineer@users.noreply.github.com>
Luna Duclos <luna.duclos@palmstonegames.com>
Luuk van Dijk <lvd@golang.org> <lvd@google.com>
Lyle Franklin <lylejfranklin@gmail.com>
Lynn
Boger <laboger@linux.vnet.ibm.com>
Ma Peiqi <mapeiqi2017@gmail.com>
Maarten Bezemer <maarten.bezemer@gmail.com>
Maciej Dbski <maciejd@google.com>
Madhu Rajanna <madhupr007@gmail.com>
Magnus Hiie <magnus.hiie@gmail.com>
Mahdi Hosseini Moghaddam <seyed.mahdi.hosseini.moghaddam@ibm.com>
Maia Lee <maia.lee@leftfieldlabs.com>
Maicon Costa <maiconscosta@gmail.com>
Mak Kolybabi <mak@kolybabi.com>
Maksym Trykur <maksym.trykur@gmail.com>
Mal Curtis <mal@mal.co.nz>
Manfred Touron <m@42.am>
Manigandan Dharmalingam <manigandan.jeff@gmail.com>
Manish Goregaokar <manishsmail@gmail.com>
Manlio Perillo <manlio.perillo@gmail.com>
Manoj Dayaram <platform-dev@moovweb.com> <manoj.dayaram@moovweb.com>
Mansour Rahimi <rahimi.mnr@gmail.com>
Manu Garg <manugarg@google.com>
Manu S Ajith <neo@codingarena.in>
Manuel Mendez <mmendez534@gmail.com>
Marat Khabibullin <marat.khabibullin@jetbrains.com>
Marc Sanmiquel <marcsanmiquel@gmail.com>
Marc Weistroff <marc@weistroff.net>
Marc-Antoine Ruel <maruel@chromium.org>
Marcel
Edmund Franke <marcel.edmund.franke@gmail.com>
Marcel van Lohuizen <mpvl@golang.org>
Marcelo Cantos <marcelo.cantos@gmail.com>
Marcelo E. Magallon <marcelo.magallon@gmail.com>
Marco Gazerro <gazerro@open2b.com>
Marco Hennings <marco.hennings@freiheit.com>
Marcus Weiner <marcus.weiner@gmail.com>
Marcus Willock <crazcalm@gmail.com>
Marga Manterola <marga@google.com>

Mariano Cano <mariano@smallstep.com>
Marin Bai <marin.basic02@gmail.com>
Mario Arranz <marioarranzr@gmail.com>
Marius A. Eriksen <marius@grailbio.com>
Marius Nuennerich <mnu@google.com>
Mark Adams <mark@markadams.me>
Mark Bucciarelli <mkbucc@gmail.com>
Mark Dain <mark@markdain.net>
Mark Glines <mark@glines.org>
Mark Hansen <markhansen@google.com>
Mark Harrison <marhar@google.com>
Mark Jeffery <dandare100@gmail.com>
Mark Percival <m@mdp.im>
Mark Pulford <mark@kyne.com.au>
Mark Rushakoff <mark.rushakoff@gmail.com>
Mark Ryan <mark.d.ryan@intel.com>
Mark Severson <miquella@gmail.com>
Mark Theunissen <mark.theunissen@gmail.com>
Mark
Villacampa <m@markvillacampa.com>
Mark Wolfe <mark@wolfe.id.au>
Mark Zavislak <zavislak@google.com>
Marko Juhani Silokunnas <marko.silokunnas@gmail.com>
Marko Kevac <marko@kevac.org>
Marko Kungla <marko.kungla@gmail.com>
Marko Mikulicic <mkm@google.com>
Marko Mudrinic <mudrinic.mare@gmail.com>
Marko Tiikkaja <marko@joh.to>
Markus Duft <markus.duft@salomon.at>
Markus Sonderegger <marraison@gmail.com>
Markus Zimmermann <zimmski@gmail.com>
Marten Seemann <martenseemann@gmail.com>
Martin Asquino <martin.asquino@gmail.com>
Martin Bertschler <mbertschler@gmail.com>
Martin Garton <garton@gmail.com>
Martin Habbecke <marhab@google.com>
Martin Hamrle <martin.hamrle@gmail.com>
Martin Hoefling <martin.hoefling@gmx.de>
Martin Kreichgauer <martinkr@google.com>
Martin Kunc <martinkunc@users.noreply.github.com>
Martin Lindhe <martin.j.lindhe@gmail.com>
Martin Mhrmann <martin@golang.org> <moehrmann@google.com> <martisch@uos.de>
Martin Neubauer <m.ne@gmx.net>
Martin Olsen <github.com@martinolsen.net>
Martin
Olsson <martin@minimum.se>
Martin Probst <martin@probst.io>
Martin Sucha <anty.sk+git@gmail.com>

Martin Tournoij <martin@arp242.net>
Martins Sipenko <martins.sipenko@gmail.com>
Martynas Budrinas <mabu@google.com>
Marvin Stenger <marvin.stenger94@gmail.com>
Marwan Sulaiman <marwan.sulaiman@work.co>
Maryan Hratson <gmarik@gmail.com>
Masahiro Furudate <masahiro.furudate@gmail.com>
Masahiro Wakame <vvakame@gmail.com>
Masaki Yoshida <yoshida.masaki@gmail.com>
Masaya Watanabe <sfbgwm30@gmail.com>
Mat Byczkowski <mbyczkowski@gmail.com>
Mat Ryer <thatmatryer@gmail.com>
Mt Gulys <mgulyas86@gmail.com>
Matej Bao <matejbaco@gmail.com>
Mateus Amin <mateus.amin@gmail.com>
Mateusz Czapliski <czapkofan@gmail.com>
Matheus Alcantara <matheusssilv97@gmail.com>
Mathias Beke <git@denbeke.be>
Mathias Hall-Andersen <mathias@hall-andersen.dk>
Mathias Leppich <mleppich@muhqu.de>
Mathieu Lonjaret <mathieu.lonjaret@gmail.com>
Mats Lidell <mats.lidell@cag.se> <mats.lidell@gmail.com>
Matt
Aimonetti <mattaimonetti@gmail.com>
Matt Blair <me@matthewblair.net>
Matt Bostock <matt@mattbostock.com>
Matt Brown <mdbrown@google.com>
Matt Dee <mdee@hioscar.com>
Matt Drollette <matt@drollette.com>
Matt Harden <matt.harden@gmail.com>
Matt Jibson <matt.jibson@gmail.com>
Matt Joiner <anacrolix@gmail.com>
Matt Jones <mrjones@google.com>
Matt Juran <thepciet@gmail.com>
Matt Layher <mdllyher@gmail.com>
Matt Masurka <masurka@google.com>
Matt Pearring <broskies@google.com>
Matt Reiferson <mreiferson@gmail.com>
Matt Robenolt <matt@ydekproductions.com>
Matt Strong <mstrong1341@gmail.com>
Matt T. Proud <matt.proud@gmail.com>
Matt Williams <gh@mattyw.net> <mattyjwilliams@gmail.com>
Matthew Brennan <matty.brennan@gmail.com>
Matthew Broberg <matthewbbroberg@gmail.com>
Matthew Cottingham <mattcottingham@gmail.com>
Matthew Dempsky <mdempsky@google.com>
Matthew Denton <mdenton@skyportsystems.com>
Matthew Holt <Matthew.Holt+git@gmail.com>

Matthew Horsnell <matthew.horsnell@gmail.com>
Matthew
Waters <mwwaters@gmail.com>
Matthias Dtsch <matze@mdoetsch.de>
Matthias Frei <matthias.frei@inf.ethz.ch>
Matthieu Hauglustaine <matt.hauglustaine@gmail.com>
Matthieu Olivier <olivier.matthieu@gmail.com>
Matthijs Kooijman <matthijs@stdin.nl>
Mattias Appelgren <mattias@ppelgren.se>
Mauricio Alvarado <mauricio.alvarado@leftfieldlabs.com>
Max Drosdo.wwww <gIranIq@gmail.com>
Max Riveiro <kavu13@gmail.com>
Max Schmitt <max@schmitt.mx>
Max Semenik <maxsem.wiki@gmail.com>
Max Ushakov <ushmax@gmail.com>
Maxim Eryomenko <moeryomenko@gmail.com>
Maxim Khitrov <max@mxcrypt.com>
Maxim Pimenov <mpimenov@google.com>
Maxim Pugachev <pugachev.mm@gmail.com>
Maxim Ushakov <ushakov@google.com>
Maxime de Roucy <maxime.deroucy@gmail.com>
Mximo Cuadros Ortiz <mcuadros@gmail.com>
Maxwell Krohn <themax@gmail.com>
Maya Rashish <maya@NetBSD.org>
Mayank Kumar <krmayankk@gmail.com>
Mehrad Sadeghi <2012.linkinpark@gmail.com>
Meir Fischer <meirfischer@gmail.com>
Meng Zhuo <mengzhuo1203@gmail.com> <mzh@golangcn.org>
Mhd
Sulhan <m.shulhan@gmail.com>
Mia Zhu <CrystalZhu1025getu@gmail.com>
Micah Stetson <micah.stetson@gmail.com>
Michael Anthony Knyszek <mknyszek@google.com>
Michael Brandenburg <mbrandenburg@bolste.com>
Michael Chaten <mchaten@gmail.com>
Michael Cook <code@mdcook.net>
Michael Darakananda <pongad@google.com>
Michael Dorner <mail@michaeldorner.de>
Michael Edwards <medwards@walledcity.ca>
Michael Elkins <michael.elkins@gmail.com>
Michael Ellis <micellis@justin.tv>
Michael Fraenkel <michael.fraenkel@gmail.com>
Michael Fromberger <michael.j.fromberger@gmail.com>
Michael Gehring <mg@ebfe.org> <gnirheg.leahcim@gmail.com>
Michael Henderson <mdhender@users.noreply.github.com>
Michael Hendricks <michael@ndrix.org>
Michael Hoisie <hoisie@gmail.com>
Michael Hudson-Doyle <michael.hudson@linaro.org>

Michael Kasch <michael.kasch@gmail.com>
Michael Kufl <golang@c.michael-kaeufl.de>
Michael Kelly <mjk@google.com>
Michal Lvesque-Dion <mlevesquedion@google.com>
Michael Lewis <mikelikespie@gmail.com>
Michael
MacInnis <Michael.P.MacInnis@gmail.com>
Michael Marineau <michael.marineau@coreos.com>
Michael Matloob <matloob@google.com>
Michael McConville <momconville@gmail.com>
Michael McGreevy <mcgreevy@golang.org>
Michael McLoughlin <mmcloughlin@gmail.com>
Michael Munday <mike.munday@ibm.com>
Michael Pearson <mipearson@gmail.com>
Michael Piatek <piatek@google.com>
Michael Pratt <mpratt@google.com>
Michael Schaller <michael@5challer.de>
Michael Schurter <michael.schurter@gmail.com>
Michael Shields <mshields@google.com>
Michael Stapelberg <michael@stapelberg.de> <mstplbrg@googlemail.com>
Michael Steinert <mike.steinert@gmail.com>
Michael T. Jones <mtj@google.com> <michael.jones@gmail.com>
Michael Teichgrber <mteichgraeber@gmx.de> <mt4swm@googlemail.com>
Michael Traver <mtraver@google.com>
Michael Vetter <g.bluehut@gmail.com>
Michael Vogt <mvo@ubuntu.com>
Michail Kargakis <mkargaki@redhat.com>
Michal Bohuslvek <mbohuslvek@gmail.com>
Michal Cierniak <cierniak@google.com>
Micha Derkacz <ziutek@inet.pl>
Michal
Franc <lam.michal.franc@gmail.com>
Michal Hruby <michal@axiom.co>
Micha owicki <mlowicki@gmail.com>
Michal Pristas <michal.pristas@gmail.com>
Michal Rostecki <mrostecki@suse.de>
Michal Stokluska <mstoklus@redhat.com>
Michalis Kargakis <michaliskargakis@gmail.com>
Michel Lespinasse <>walken@google.com>
Michel Levieux <mlevieux42@gmail.com>
Michele Di Pede <michele.di.pede@gmail.com>
Mickael Kerjean <mickael.kerjean@gmail.com>
Mickey Reiss <mickeyreiss@gmail.com>
Miek Gieben <miek@miek.nl> <remigius.gieben@gmail.com>
Miguel Acero <acero@google.com>
Miguel Mendez <stxmendez@gmail.com>
Miguel Molina <hi@mvader.me>
Mihai Borobocea <MihaiBorobocea@gmail.com>

Mihai Moldovan <ionic@ionic.de>
Mihai Todor <todormihai@gmail.com>
Mihail Minaev <minaev.mike@gmail.com>
Mikael Tillenius <mikti42@gmail.com>
Mike Andrews <mra@xoba.com>
Mike Appleby <mike@app.leby.org>
Mike Danese <mikedanese@google.com>
Mike Houston <mike@kothar.net>
Mike Kabischev <kabischev@gmail.com>
Mike Rosset <mike.rosset@gmail.com>
Mike
Samuel <mikesamuel@gmail.com>
Mike Solomon <msolo@gmail.com>
Mike Strosaker <strosake@us.ibm.com>
Mike Tsao <mike@sowbug.com>
Mike Wiacek <mjwiacek@google.com>
Mikhail Faraponov <11322032+moredure@users.noreply.github.com>
Mikhail Fesenko <proggga@gmail.com>
Mikhail Gusarov <dottedmag@dottedmag.net>
Mikhail Panchenko <m@mihasya.com>
Miki Tebeka <miki.tebeka@gmail.com>
Mikio Hara <mikioh.mikioh@gmail.com>
Mikkel Krautz <mikkel@krautz.dk> <krautz@gmail.com>
Mikoaj Baranowski <mikolajb@gmail.com>
Milan Knezevic <milan.knezevic@mips.com>
Milan Patel <bicelot3@gmail.com>
Milutin Jovanovic <jovanovic.milutin@gmail.com>
MinJae Kwon <mingrammer@gmail.com>
Miquel Sabat Sol <mikisabate@gmail.com>
Mirko Hansen <baaazen@gmail.com>
Miroslav Genov <mgenov@gmail.com>
Misty De Meo <mistydemeo@gmail.com>
Mohamed Attahri <mohamed@attahri.com>
Mohit Agarwal <mohit@sdf.org>
Mohit kumar Bajoria <mohitbajo36@gmail.com>
Mohit Verma <vmohit.93@gmail.com>
Momchil Velikov <momchil.velikov@gmail.com>
Monis
Khan <mkhan@redhat.com>
Monty Taylor <mordred@inaugust.com>
Moritz Fain <moritz@fain.io>
Moriyoshi Koizumi <mozo@mozo.jp>
Morten Siebuhr <sbhr@sbhr.dk>
Mshe van der Sterre <moshevds@gmail.com>
Mostafa Solati <mostafa.solati@gmail.com>
Mostyn Bramley-Moore <mostyn@antipode.se>
Mrunal Patel <mrunalp@gmail.com>
Muhammad Falak R Wani <falakreyaz@gmail.com>

Muhammad Hamza Farrukh <hamzafarrukh141@gmail.com>
Muhammed Uluyol <uluyol0@gmail.com>
Muir Manders <muir@mnd.rs>
Mukesh Sharma <sharma.mukesh439@gmail.com>
Mura Li <mura_li@castech.com.tw>
Mykhailo Lesyk <mikhail@lesyk.org>
Nahum Shalman <nahamu@gmail.com>
Naman Aggarwal <aggarwal.nam@gmail.com>
Naman Gera <namangera15@gmail.com>
Nan Deng <monnand@gmail.com>
Nao Yonashiro <owan.orisano@gmail.com>
Naoki Kanatani <k12naoki@gmail.com>
Natanael Copa <ncopa@mirantis.com>
Nate Wilkinson <nathanwilk7@gmail.com>
Nathan Cantelmo <n.cantelmo@gmail.com>
Nathan Caza <mastercactapus@gmail.com>
Nathan Dias <nathan.dias@orijtech.com>
Nathan
Fiscaletti <nathan.fiscaletti@vrazo.com>
Nathan Humphreys <nkhumphreys@gmail.com>
Nathan John Youngman <nj@nathany.com>
Nathan Otterness <otternes@cs.unc.edu>
Nathan P Finch <nate.finch@gmail.com>
Nathan VanBenschoten <nvanbenschoten@gmail.com>
Nathan Youngman <git@nathany.com>
Nathan(yinian) Hu <nathanhu@google.com>
Nathaniel Cook <nvcook42@gmail.com>
Naveen Kumar Sangi <naveenkumarsangi@protonmail.com>
Neeilan Selvalingam <neeilan96@gmail.com>
Neelesh Chandola <neelesh.c98@gmail.com>
Nehal J Wani <nehaljw.kkd1@gmail.com>
Neil Alexander <neilalexander@neilalexander.dev>
Neil Lyons <nwjlyons@googlemail.com>
Neuman Vong <neuman.vong@gmail.com>
Neven Sajko <nsajko@gmail.com>
Nevins Bartolomeo <nevins.bartolomeo@gmail.com>
Niall Sheridan <nsheridan@gmail.com>
Nic Day <nic.day@me.com>
Nicholas Asimov <nicholas@asimov.me>
Nicholas Katsaros <nick@nickkatsaros.com>
Nicholas Maniscalco <nicholas@maniscalco.com>
Nicholas Ng <nickng@nickng.io>
Nicholas Presta <nick@nickpresta.ca> <nick1presta@gmail.com>
Nicholas
Sullivan <nicholas.sullivan@gmail.com>
Nicholas Waples <nwaples@gmail.com>
Nick Anthony <Liberatys@outlook.com>
Nick Cooper <nmvc@google.com>

Nick Craig-Wood <nick@craig-wood.com> <nickcw@gmail.com>
Nick Harper <nharper@google.com>
Nick Kubala <nkubala@google.com>
Nick Leli <nicholasleli@gmail.com>
Nick Miyake <nmiyake@users.noreply.github.com>
Nick Patavalis <nick.patavalis@gmail.com>
Nick Petroni <npetroni@cs.umd.edu>
Nick Robinson <nrobinson13@gmail.com>
Nick Sherron <nsherron90@gmail.com>
Nick Smolin <nick27surgut@gmail.com>
Nicolas BRULEZ <n.brulez@gmail.com>
Nicolas Kaiser <nikai@nikai.net>
Nicolas Owens <mischief@offblast.org>
Nicolas S. Dade <nic.dade@gmail.com>
Niek Sanders <niek.sanders@gmail.com>
Niels Widger <niels.widger@gmail.com>
Nigel Kerr <nigel.kerr@gmail.com>
Nigel Tao <nigeltao@golang.org>
Nik Nyby <nnyby@columbia.edu>
Nikhil Benesch <nikhil.benesch@gmail.com>
Nikita Gillmann <nikita@n0.is> <ng0@n0.is>
Nikita Kryuchkov <nkryuchkov10@gmail.com>
Nikita
Melekhin <nimelehin@gmail.com>
Nikita Vanyasin <nikita.vanyasin@gmail.com>
Niklas Schnelle <niklas.schnelle@gmail.com>
Niko Dziemba <niko@dziemba.com>
Nikolay Turpitko <nikolay@turpitko.com>
Nikson Kanti Paul <nikson.sust@gmail.com>
Nils Larsgrd <nilsmagnus@gmail.com>
Nir Soffer <nirsof@gmail.com>
Niranjan Godbole <niranjan8192@gmail.com>
Nishanth Shanmugham <nishanth.gerrard@gmail.com>
Noah Campbell <noahcampbell@gmail.com>
Noah Goldman <noahg34@gmail.com>
Noah Santschi-Cooney <noah@santschi-cooney.ch>
Noble Johnson <noblepoly@gmail.com>
Nodir Turakulov <nodir@google.com>
Noel Georgi <git@frezbo.com>
Nooras Saba <saba@golang.org>
Norberto Lopes <nlopes.ml@gmail.com>
Norman B. Lancaster <qbradq@gmail.com>
Nuno Cruces <ncruces@users.noreply.github.com>
Obei Sideg <obei.sideg@gmail.com>
Obeyda Djefal <djefobey@gmail.com>
Odin Ugedal <odin@ugedal.com>
Oleg Bulatov <dmage@yandex-team.ru>
Oleg Vakheta <helginet@gmail.com>

Oleku Konko <oleku.konko@gmail.com>
Oling Cat <olingcat@gmail.com>
Oliver
Hookins <ohookins@gmail.com>
Oliver Powell <oliverpowell84@gmail.com>
Oliver Stenbom <ostenbom@pivotal.io>
Oliver Tan <otan@cockroachlabs.com>
Oliver Tonnhofer <olt@bogosoftware.com>
Olivier Antoine <olivier.antoine@gmail.com>
Olivier Duperray <duperray.olivier@gmail.com>
Olivier Mengue <olivier.mengue@gmail.com>
Olivier Poitrey <rs@dailyotion.com>
Olivier Saingre <osaingre@gmail.com>
Olivier Wulveryck <olivier.wulveryck@gmail.com>
Omar Jarjur <ojarjur@google.com>
Onkar Jadhav <omjadhav2610@gmail.com>
Ori Bernstein <ori@eigenstate.org>
Ori Rawlings <orirawlings@gmail.com>
Oryan Moshe <iamoryanmoshe@gmail.com>
Osamu TONOMORI <osamingo@gmail.com>
Oscar Sderlund <oscar.soderlund@einride.tech>
zgr Kesim <oec-go@kesim.org>
Pablo Caderno <kaderno@gmail.com>
Pablo Lalloni <plalloni@gmail.com>
Pablo Rozas Larraondo <pablo.larraondo@anu.edu.au>
Pablo Santiago Blum de Aguiar <scorphus@gmail.com>
Padraig Kitterick <padraigkitterick@gmail.com>
Pallat Anchaleechamaikorn <yod.pallat@gmail.com>
Pan
Chenglong <1004907659@qq.com>
Panos Georgiadis <pgeorgiadis@suse.de>
Pantelis Sampaziotis <psampaz@gmail.com>
Paolo Giarrusso <p.giarrusso@gmail.com>
Paolo Martini <mrtnpaolo@gmail.com>
Parker Moore <parkrmoore@gmail.com>
Parminder Singh <parmsingh101@gmail.com>
Pascal Dierich <pascal@pascaldierich.com>
Pascal S. de Kloe <pascal@quies.net>
Paschalis Tsilias <paschalis.tsilias@gmail.com>
Pasi Thkp <pasi.tahkapaa@gmail.com>
Pat Moroney <pat@pat.email>
Patrick Barker <barkerp@vmware.com>
Patrick Crosby <patrick@stathat.com>
Patrick Gavlin <pgavlin@gmail.com>
Patrick Gundlach <gundlach@speedata.de>
Patrick Higgins <patrick.allen.higgins@gmail.com>
Patrick Jones <ithuriel@google.com>
Patrick Lee <pattyshack101@gmail.com>

Patrick Mzard <patrick@mezard.eu>
Patrick Mylund Nielsen <patrick@patrickmn.com>
Patrick Pelletier <pp.pelletier@gmail.com>
Patrick Riley <pfr@google.com>
Patrick Smith <pat42smith@gmail.com>
Patrik Lundin <patrik@sigterm.se>
Patrik Nyblom <pnyb@google.com>
Paul
A Querna <paul.querna@gmail.com>
Paul Borman <borman@google.com>
Paul Boyd <boyd.paul2@gmail.com>
Paul Chang <paulchang@google.com>
Paul D. Weber <x0bdev@gmail.com>
Paul Davis <43160081+Pawls@users.noreply.github.com>
Paul E. Murphy <murp@ibm.com>
Paul Forgey <paulf@tessier-ashpool.net>
Paul Hammond <paul@paulhammond.org>
Paul Hankin <paulhankin@google.com>
Paul Jolly <paul@myitcv.org.uk>
Paul Lalonde <paul.a.lalonde@gmail.com>
Paul M Furley <paul@paulfurley.com>
Paul Marks <pmarks@google.com>
Paul Meyer <paul.meyer@microsoft.com>
Paul Nasrat <pnasrat@google.com>
Paul PISCUC <paul.piscuc@gmail.com>
Paul Querna <pquerna@apache.org>
Paul Rosania <paul.rosania@gmail.com>
Paul Ruest <pruest@gmail.com>
Paul Sbarra <Sbarra.Paul@gmail.com>
Paul Smith <paulsmith@pobox.com> <paulsmith@gmail.com>
Paul Tyng <paul@paultyng.net>
Paul van Brouwershaven <paul@vanbrouwershaven.com>
Paul Wankadia <junyer@google.com>
Paulo Casaretto <pcasaretto@gmail.com>
Paulo Flabiano Smorigo <pfsmorigo@linux.vnet.ibm.com>
Paulo
Gomes <paulo.gomes.uk@gmail.com>
Pavel Kositsyn <kositsyn.pa@phystech.edu>
Pavel Paulau <pavel.paulau@gmail.com>
Pavel Watson <watsonpavel@gmail.com>
Pavel Zinovkin <pavel.zinovkin@gmail.com>
Pavlo Sumkin <ymkins@gmail.com>
Pawel Knap <pawelknap88@gmail.com>
Pawel Szczur <filemon@google.com>
Pawe Szulik <pawel.szulik@intel.com>
Pedro Lopez Mareque <pedro.lopez.mareque@gmail.com>
Pei Xian Chee <luciolas1991@gmail.com>
Pei-Ming Wu <p408865@gmail.com>

Pen Tree <appletree2479@outlook.com>
Peng Gao <peng.gao.dut@gmail.com>
Percy Wegmann <ox.to.a.cart@gmail.com>
Perry Abbott <perry.j.abbott@gmail.com>
Petar Dambovaliev <petar.atanasov.1987@gmail.com>
Petar Maymoukov <petarm@gmail.com>
Peter Armitage <peter.armitage@gmail.com>
Peter Bourgon <peter@bourgon.org>
Peter Collingbourne <pcc@google.com>
Peter Conerly <pconerly@gmail.com>
Peter Dotchev <dotchev@gmail.com>
Peter Froehlich <peter.hans.froehlich@gmail.com>
Peter Gonda <pgonda@google.com>
Peter Hoyes <pahoyes@gmail.com>
Peter
Kleiweg <pkleiweg@xs4all.nl>
Peter McKenzie <petermck@google.com>
Peter Moody <pmoody@uber.com>
Peter Morjan <pmorjan@gmail.com>
Peter Mundy <go.peter.90@gmail.com>
Peter Nguyen <peter@mictis.com>
Pter Surnyi <speter.go1@gmail.com>
Pter Szab <pts@google.com>
Pter Szilgyi <peterke@gmail.com>
Peter Teichman <pteichman@fastly.com>
Peter Tseng <ptseng@squareup.com>
Peter Waldschmidt <peter@waldschmidt.com>
Peter Waller <peter.waller@gmail.com>
Peter Weinberger <pjw@golang.org>
Peter Williams <pwil3058@gmail.com>
Peter Wu <pwu@cloudflare.com>
Peter Zhang <i@ddatsh.com>
Petr Jedin <petr.jediny@gmail.com>
Petrica Voicu <pvoicu@paypal.com>
Phil Pearl <philip.j.r.pearl@gmail.com>
Phil Pennock <pdp@golang.org>
Philip Brgesen <philip.brgesen@gmail.com>
Philip Brown <phil@bolthole.com>
Philip Hofer <phofer@umich.edu>
Philip K. Warren <pkwarren@gmail.com>
Philip Nelson <me@pnelson.ca>
Philipp Sauter <sauterp@protonmail.com>
Philipp Stephani <phst@google.com>
Phillip Campbell <15082+phillc@users.noreply.github.com>
Pierre
Carru <pierre.carru@eshard.com>
Pierre Durand <pierredurand@gmail.com>
Pierre Prinetti <pierreprinetti@gmail.com>

Pierre Roullon <pierre.roullon@gmail.com>
Piers <google@hellopiers.pro>
Pieter Droogendijk <pieter@binky.org.uk>
Pietro Gagliardi <pietro10@mac.com>
Piyush Mishra <piyush@codeitout.com>
Plekhanov Maxim <kishtatix@gmail.com>
Poh Zi How <poh.zihow@gmail.com>
Polina Osadcha <polliosa@google.com>
Pontus Leitzler <leitzler@gmail.com>
Povilas Versockas <p.versockas@gmail.com>
Prajwal Koirala <16564273+Prajwal-Koirala@users.noreply.github.com>
Prasanga Siripala <pj@pjebs.com.au>
Prasanna Swaminathan <prasanna@mediamath.com>
Prashant Agrawal <prashant.a.vjti@gmail.com>
Prashant Varanasi <prashant@prashantv.com>
Praveen Kumar <praveen+git@kumar.in>
Pravendra Singh <hackpravj@gmail.com>
Preetam Jinka <pj@preet.am>
Pure White <wu.purewhite@gmail.com>
Qais Patankar <qaisjp@gmail.com>
Qiuxuan Zhu <ilsh1022@gmail.com>
Quan Tran <qeed.quan@gmail.com>
Quan Yong
Zhai <qyzhai@gmail.com>
Quentin Perez <qperez@ocs.online.net>
Quentin Renard <contact@asticode.com>
Quentin Smith <quentin@golang.org>
Quey-Liang Kao <s101062801@m101.nthu.edu.tw>
Quim Muntal <quimmuntal@gmail.com>
Quinn Slack <sqs@sourcegraph.com>
Quinten Yearsley <qyearsley@chromium.org>
Quoc-Viet Nguyen <afelion@gmail.com>
Rabin Gaire <rabingaire20@gmail.com>
Radek Simko <radek.simko@gmail.com>
Radek Sohlich <sohlich@gmail.com>
Radu Berinde <radu@cockroachlabs.com>
Rafal Jeczalik <rjeczalik@gmail.com>
Raghavendra Nagaraj <jamdagni86@gmail.com>
Rahul Bajaj <rahulrb0509@gmail.com>
Rahul Chaudhry <rahulchaudhry@chromium.org>
Rahul Wadhvani <rahulwadhvani21@gmail.com>
Raif S. Naffah <go@naffah-raif.name>
Rajat Goel <rajat.goel2010@gmail.com>
Rajath Agasthya <rajathagasthya@gmail.com>
Rajender Reddy Kompally <rajenderreddykompally@gmail.com>
Ralph Corderoy <ralph@inputplus.co.uk>
Ramazan AYYILDIZ <rayyildiz@gmail.com>
Ramesh Dharan <dharan@google.com>

Randy Reddig <randy@alta.software>
Raph
Levien <raph@google.com>
Raphael Geronimi <raphael.geronimi@gmail.com>
Raul Silvera <rsilvera@google.com>
Ravil Bikbulatov <weeellz12@gmail.com>
RaviTeja Pothana <ravi.tezu@gmail.com>
Ray Tung <rtung@thoughtworks.com>
Ray Wu <ray@liftoff.io>
Raymond Kazlauskas <raima220@gmail.com>
Rebecca Stambler <rstambler@golang.org>
Reilly Watson <reillywatson@gmail.com>
Reinaldo de Souza Jr <juniorz@gmail.com>
Remi Gillig <remigillig@gmail.com>
Rmy Oudompheng <oudomphe@phare.normalesup.org> <remyoudompheng@gmail.com>
Ren Ogaki <re.yuz77777@gmail.com>
Rens Rikkerink <Ikkerens@users.noreply.github.com>
Rhys Hiltner <rhys@justin.tv>
Ricardo Padilha <ricardospadilha@gmail.com>
Ricardo Pchevuzinske Katz <ricardo.katz@serpro.gov.br>
Ricardo Seriani <ricardo.seriani@gmail.com>
Rich Hong <hong.rich@gmail.com>
Richard Barnes <rlb@ipv.sx>
Richard Crowley <r@rcrowley.org>
Richard Dingwall <rdingwall@gmail.com>
Richard Eric Gavaletz <gavaletz@gmail.com>
Richard Gibson <richard.gibson@gmail.com>
Richard
Miller <miller.research@gmail.com>
Richard Musiol <mail@richard-musiol.de> <neelance@gmail.com>
Richard Pickering <richard.pickering@hotmail.co.uk>
Richard Ulmer <codesoap@mailbox.org>
Richard Wilkes <wilkes@me.com>
Rick Arnold <rickarnoldjr@gmail.com>
Rick Hudson <rlh@golang.org>
Rick Sayre <whorfin@gmail.com>
Rijnard van Tonder <rvantonder@gmail.com>
Riku Voipio <riku.voipio@linaro.org>
Riley Avron <ra.git@posteo.net>
Risto Jaakko Saarelmä <rsaarelm@gmail.com>
Rob Earhart <earhart@google.com>
Rob Findley <rfindley@google.com>
Rob Norman <rob.norman@infinitycloud.com>
Rob Phoenix <rob@robphoenix.com>
Rob Pike <r@golang.org>
Robert Ayrapetyan <robert.ayrapetyan@gmail.com>
Robert Burke <rebo@google.com>
Robert Daniel Kortschak <dan.kortschak@adelaide.edu.au> <dan@kortschak.io>

Robert Dinu <r@varp.se>
Robert Engels <rengels@ix.netcom.com>
Robert Figueiredo <robfig@gmail.com>
Robert Griesemer <gri@golang.org>
Robert Hencke <robert.hencke@gmail.com>
Robert Iannucci <iannucci@google.com>
Robert
Kuska <rkuska@gmail.com>
Robert Obryk <robryk@gmail.com>
Robert Seseek <rseseek@google.com>
Robert Snedegar <roberts@google.com>
Robert Stepanek <robert.stepanek@gmail.com>
Robert van Gent <rvangent@google.com>
Robert-Andr Mauchin <zebob.m@gmail.com>
Roberto Clapis <robclap8@gmail.com>
Roberto Selbach <roberto@selbach.ca>
Robin Eklind <r.eklind.87@gmail.com>
Robin Zhong <robin@robinzhong.co>
Rodolfo Carvalho <rhcarvalho@gmail.com>
Rodolfo Rodriguez <rodolfobgibson@gmail.com>
Rodrigo Moraes de Oliveira <rodrigo.moraes@gmail.com>
Rodrigo Rafael Monti Kochenburger <divoxx@gmail.com>
Roger Pau Monn <royger@gmail.com>
Roger Peppe <rogpeppe@gmail.com>
Rohan Challa <rohan@golang.org>
Rohan Verma <rohanverma2004@gmail.com>
Rohith Ravi <entombedvirus@gmail.com>
Roi Martin <jroi.martin@gmail.com>
Roland Illig <roland.illig@gmx.de>
Roland Shoemaker <rolandshoemaker@gmail.com>
Romain Bague <romain.bague@elwinar.com>
Roman Budnikov <romanyx90@yandex.ru>
Roman Kollr <roman.kollar.0@gmail.com>
Roman
Shchekin <mrqtros@gmail.com>
Ron Hashimoto <mail@h2so5.net>
Ron Minnich <rminnich@gmail.com>
Ronnie Ebrin <ebrin.ronnie@protonmail.com>
Ross Chater <rdchater@gmail.com>
Ross Kinsey <rossikinsey@gmail.com>
Ross Light <light@google.com> <rlight2@gmail.com>
Ross Smith II <ross@smithii.com>
Rowan Marshall <rowanajmarshall@gmail.com>
Rowan Worth <sqweek@gmail.com>
Rudi Kramer <rudi.kramer@gmail.com>
Rui Ueyama <ruiui@google.com>
Ruixin Bao <ruixin.bao@ibm.com>
Ruslan Andreev <ruslan.andreev@huawei.com>

Ruslan Nigmatullin <elessar@dropbox.com>
Russ Cox <rsc@golang.org>
Russell Haering <russellhaering@gmail.com>
Ryan Bagwell <ryanbagwell@outlook.com>
Ryan Barrett <ryanb@google.com>
Ryan Boehning <ryan.boehning@apcera.com>
Ryan Brown <ribrd@b@gmail.com>
Ryan Canty <jrcanty@gmail.com>
Ryan Dahl <ry@tinyclouds.org>
Ryan Hitchman <hitchmanr@gmail.com>
Ryan Kohler <ryankohler@google.com>
Ryan Leung <rleungx@gmail.com>
Ryan Lower <rpjlower@gmail.com>
Ryan Roden-Corrent <ryan@rcorre.net>
Ryan
Seys <ryan@ryanseys.com>
Ryan Slade <ryanslade@gmail.com>
Ryan Zhang <ryan.zhang@docker.com>
Ryoichi KATO <ryo1kato@gmail.com>
Ryoya Sekino <ryoyasekino1993@gmail.com>
Ryuji Iwata <qt.luigi@gmail.com>
Ryuma Yoshida <ryuma.y1117@gmail.com>
Ryuzo Yamamoto <ryuzo.yamamoto@gmail.com>
S.alar Onur <caglar@10ur.org>
Sabin Mihai Rapan <sabin.rapan@gmail.com>
Sad Pencil <qh06@qq.com>
Sai Cheemalapati <saicheems@google.com>
Sai Kiran Dasika <kirandasika30@gmail.com>
Sakeven Jiang <jc5930@sina.cn>
Salaheddin M. Mahmud <salah.mahmud@gmail.com>
Salmn Aljammz <s@0x65.net>
Sam Arnold <sarnold64@bloomberg.net>
Sam Boyer <tech@samboyer.org>
Sam Chen <chenxsan@gmail.com>
Sam Cross <samgcdev@gmail.com>
Sam Ding <samding@ca.ibm.com>
Sam Hug <samuel.b.hug@gmail.com>
Sam Thorogood <thorogood@google.com> <sam.thorogood@gmail.com>
Sam Whited <sam@samwhited.com>
Sam Xie <xsambundy@gmail.com>
Sameer Ajmani <sameer@golang.org> <ajmani@gmail.com>
Sami Commerot <samic@google.com>
Sami Pnknen <sami.ponkanen@gmail.com>
Samuel
Kelemen <SCKelemen@users.noreply.github.com>
Samuel Tan <samueltan@google.com>
Samuele Pedroni <pedronis@lucediaruna.net>
San Ye <xyesan@gmail.com>

Sander van Harmelen <sander@vanharmelen.nl>
Sanjay Menakuru <balasanjay@gmail.com>
Santhosh Kumar Tekuri <santhosh.tekuri@gmail.com>
Santiago De la Cruz <51337247+xhit@users.noreply.github.com>
Sarah Adams <shadams@google.com>
Sardorbek Pulatov <sardorbek.pulatov@outlook.com>
Sascha Brawer <sascha@brawer.ch>
Sasha Lionheart <lionhearts@google.com>
Sasha Sobol <sasha@scaledinference.com>
Satoru Kitaguchi <rule.the.fate.myfirststory@gmail.com>
Scott Barron <scott.barron@github.com>
Scott Bell <scott@sctsm.com>
Scott Cotton <scott@mindowl.com>
Scott Crunkleton <crunk1@gmail.com>
Scott Ferguson <scottwferg@gmail.com>
Scott Lawrence <bytbox@gmail.com>
Scott Mansfield <smansfield@netflix.com>
Scott Ragan <ragansa@fb.com>
Scott Schwartz <scotts@golang.org>
Scott Van Woudenberg <scottvw@google.com>
Sean Burford <sburford@google.com>
Sean
Chen <oohcode@gmail.com>
Sean Chittenden <seanc@joyent.com>
Sean Christopherson <sean.j.christopherson@intel.com>
Sean Dolphin <Sean.Dolphin@kpcompass.com>
Sean Harger <sharger@google.com>
Sean Harrington <sean.harrington@leftfieldlabs.com>
Sean Hildebrand <seanwhildebrand@gmail.com>
Sean Liao <seankhliao@gmail.com>
Sean Rees <sean@erifax.org>
Sebastiaan van Stijn <github@gone.nl>
Sebastian Chlopecki <sebsebmc@gmail.com>
Sebastian Kinne <skinne@google.com>
Sebastian Schmidt <yath@google.com>
Sebastien Binet <seb.binet@gmail.com>
Sbastien Paolacci <sebastien.paolacci@gmail.com>
Sebastien Williams-Wynn <sebastien@cytora.com>
Segev Finer <segev208@gmail.com>
Seiji Takahashi <timaki.st@gmail.com>
Sergei Lemeshkin <sergeilem@gmail.com>
Sergei Skorobogatov <skorobo@rambler.ru>
Sergei Zagurskii <gvozdoder@gmail.com>
Sergey 'Snake' Gromov <snake.scaly@gmail.com>
Sergey Arseev <sergey.arseev@intel.com>
Sergey Dobrodey <sergey.dobrodey@synesis.ru>
Sergey Frolov <sfrolov@google.com>
Sergey Glushchenko

<gsserge@gmail.com>
Sergey Ivanov <ser1325@gmail.com>
Sergey Kacheev <S.Kacheev@gmail.com>
Sergey Lukjanov <me@slukjanov.name>
Sergey Mishin <sergeymishine@gmail.com>
Sergey Mudrik <sergey.mudrik@gmail.com>
Sergey Semin <gray12511@gmail.com>
Sergey Yanykin <syanykin@ozon.ru>
Sergio Luis O. B. Correia <sergio@correia.cc>
Sergiusz Bazanski <bazanski@gmail.com>
Serhat Giydiren <serhatgydiren@gmail.com>
Serhii Aheienko <serhii.aheienko@gmail.com>
Seth Hoenig <seth.a.hoenig@gmail.com>
Seth Vargo <sethvargo@gmail.com>
Shaba Abhiram <shabarivas.abhiram@gmail.com>
Shahar Kohanim <skohanim@gmail.com>
Shailesh Suryawanshi <ss.shailesh28@gmail.com>
Shamil Garatuev <garatuev@gmail.com>
Shamim Akhtar <shamim.rhce@gmail.com>
Shane Hansen <shanemhansen@gmail.com>
Shang Jian Ding <sding3@ncsu.edu>
Shaozhen Ding <dsz0111@gmail.com>
Shaquille Que <shaquille@golang.org>
Shaquille Wyan Que <shaqywyuan@gmail.com>
Shaun Dunning <shaun.dunning@uservoice.com>
Shawn Elliott <selliot@microsoft.com>
Shawn
Ledbetter <sledbetter@google.com>
Shawn Smith <shawn.p.smith@gmail.com>
Shawn Walker-Salas <shawn.walker@oracle.com>
Shenghou Ma <minux@golang.org> <minux.ma@gmail.com>
Shengjing Zhu <zs950618@gmail.com>
Shengyu Zhang <shengyu.zhang@chaitin.com>
Shi Han Ng <shihanng@gmail.com>
ShihCheng Tu <mrtoastcheng@gmail.com>
Shijie Hao <haormj@gmail.com>
Shin Fan <shinfan@google.com>
Shinji Tanaka <shinji.tanaka@gmail.com>
Shinnosuke Sawada <6warashi9@gmail.com>
Shintaro Kaneko <kaneshin0120@gmail.com>
Shivakumar GN <shivakumar.gn@gmail.com>
Shivani Singhal <shivani.singhal2804@gmail.com>
Shivansh Rai <shivansh@freebsd.org>
Shivashis Padhi <shivashispadhi@gmail.com>
Shoshin Nikita <shoshin_nikita@fastmail.com>
Shota Sugiura <s.shota.710.3506@gmail.com>
Shubham Sharma <shubham.sha12@gmail.com>
Shuhei Takahashi <nya@chromium.org>

Shun Fan <sfan@google.com>
Silvan Jegen <s.jegen@gmail.com>
Simo Gomes Viana <simaogmv@gmail.com>
Simarpreet Singh <simar@linux.com>
Simon Drake <simondrake1990@gmail.com>
Simon
 Ferquel <simon.ferquel@docker.com>
Simon Frei <freisim93@gmail.com>
Simon Jefford <simon.jefford@gmail.com>
Simon Law <sfllaw@sfllaw.ca>
Simon Rawet <simon@rawet.se>
Simon Rozman <simon@rozman.si>
Simon Ser <contact@emersion.fr>
Simon Thulbourn <simon+github@thulbourn.com>
Simon Whitehead <chemnova@gmail.com>
Sina Siadat <siadat@gmail.com>
Sjoerd Siebinga <sjoerd.siebinga@gmail.com>
Sokolov Yura <funny.falcon@gmail.com>
Song Gao <song@gao.io>
Song Lim <songlim327@gmail.com>
Songjiayang <songjiayang1@gmail.com>
Songlin Jiang <hollowman@hollowman.ml>
Soojin Nam <jsunam@gmail.com>
Sren L. Hansen <soren@linux2go.dk>
Sparrow Li <liyuancylx@gmail.com>
Spencer Kocot <spencerkocot@gmail.com>
Spencer Nelson <s@spenczar.com>
Spencer Tung <spencertung@google.com>
Spenser Black <spenserblack01@gmail.com>
Spring Mc <heresy.mc@gmail.com>
Srdjan Petrovic <spetrovic@google.com>
Sridhar Venkatakrishnan <sridhar@laddoo.net>
Srinidhi Kaushik <shrinidhi.kaushik@gmail.com>
StalkR <stalkr@stalkr.net>
Stan
 Hu <stanhu@gmail.com>
Stan Schwertly <stan@schwertly.com>
Stanislav Afanasev <php.progger@gmail.com>
Steeve Morin <steeve.morin@gmail.com>
Stefan Baebler <sbaebler@outbrain.com>
Stefan Nilsson <snilsson@nada.kth.se> <trolleriprofessorn@gmail.com>
Stepan Shabalin <neverliberty@gmail.com>
Stephan Klatt <stephan.klatt@gmail.com>
Stephan Renatus <srenatus@chef.io>
Stephan Zuercher <zuercher@gmail.com>
Stphane Travostino <stephane.travostino@gmail.com>
Stephen Lewis <stephen@sock.org.uk>
Stephen Lu <steuhs@users.noreply.github.com>

Stephen Ma <stephenm@golang.org>
Stephen McQuay <stephen@mcquay.me>
Stephen Searles <stephens2424@gmail.com>
Stephen Weinberg <stephen@q5comm.com>
Steve Francia <spf@golang.org>
Steve Gilbert <stevegilbert23@gmail.com>
Steve LoFurno <slofurno@gmail.com>
Steve McCoy <mccoyst@gmail.com>
Steve Mynott <steve.mynott@gmail.com>
Steve Newman <snewman@google.com>
Steve Phillips <elimistev@gmail.com>
Steve Streeting <steve@stevestreeting.com>
Steve Traut <straut@google.com>
Steven
Buss <sbuss@google.com>
Steven Elliot Harris <seharris@gmail.com>
Steven Erenst <stevenerenst@gmail.com>
Steven Hartland <steven.hartland@multiplay.co.uk>
Steven Littiebrant <imgroxx@gmail.com>
Steven Maude <git@stevenmaude.co.uk>
Steven Wilkin <stevenwilkin@gmail.com>
Stuart Jansen <sjansen@buscaluz.org>
Subham Sarkar <sarkar.subhams2@gmail.com>
Sue Spence <virtuallysue@gmail.com>
Sugu Sougoumarane <ssougou@gmail.com>
Suharsh Sivakumar <suharshs@google.com>
Sukrit Handa <sukrit.handa@utoronto.ca>
Sunny <me@darkowlzz.space>
Suriyaa Sundararuban <suriyaasundararuban@gmail.com>
Suvaditya Sur <suvaditya.sur@gmail.com>
Suyash <dextrous93@gmail.com>
Suzy Mueller <suzmue@golang.org>
Sven Almgren <sven@tras.se>
Sven Blumenstein <svbl@google.com>
Sven Lee <lee1300394324@gmail.com>
Sven Taute <sven.taute@gmail.com>
Sylvain Zimmer <sylvain@sylvainzimmer.com>
Syohei YOSHIDA <syohex@gmail.com>
Szabolcs Nagy <nsz@port70.net>
Taavi Kivisik <taavi.kivisik@gmail.com>
Tad Fisher <tadfisher@gmail.com>
Tad
Glines <tad.glines@gmail.com>
Tadas Valiukas <tadovas@gmail.com>
Tadeo Kondrak <me@tadeo.ca>
Taesu Pyo <pyotaesu@gmail.com>
Tai Le <letientai299@gmail.com>
Taj Khattrra <taj.khattrra@gmail.com>

Takashi Matsuo <tmatsuo@google.com>
Takashi Mima <tk.s.m1205@gmail.com>
Takayoshi Nishida <takayoshi.nishida@gmail.com>
Takeshi YAMANASHI <9.nashi@gmail.com>
Takuto Ikuta <tikuta@google.com>
Takuya Ueda <uedatakuya@gmail.com>
Tal Shprecher <tshprecher@gmail.com>
Tams Gulcsi <tgulcsi78@gmail.com>
Tamir Duberstein <tamird@gmail.com>
Tao Qingyun <qingyunha@gmail.com>
Tao Shen <shentaoskyking@gmail.com>
Tao Wang <twang2218@gmail.com>
Tarmigan Casebolt <tarmigan@gmail.com>
Taro Aoki <aizu.s1230022@gmail.com>
Taru Karttunen <taruti@taruti.net>
Tatsuhiko Tsujikawa <tatsuhiko.t@gmail.com>
Tatsuya Kaneko <m.ddotx.f@gmail.com>
Taufiq Rahman <taufiqrx8@gmail.com>
Teague Cole <tnc1443@gmail.com>
Ted Kornish <golang@tedkornish.com>
Tejasvi Nareddy <tejunareddy@gmail.com>
Terin Stock <terinjokes@gmail.com>
Terrel
Shumway <gopher@shumway.us>
Tetsuo Kiso <tetsuokiso9@gmail.com>
Than McIntosh <thanm@google.com>
Thanabodee Charoenpiriyakij <wingyminus@gmail.com>
Thanatat Tamtan <acoshift@gmail.com>
The Hatsune Daishi <nao20010128@gmail.com>
Thiago Avelino <t@avelino.xxx>
Thiago Fransosi Farina <thiago.farina@gmail.com> <tfarina@chromium.org>
Thom Wiggers <thom@thomwiggers.nl>
Thomas Alan Copeland <talan.copeland@gmail.com>
Thomas Bonfort <thomas.bonfort@gmail.com>
Thomas Bouldin <inlined@google.com>
Thomas Bruyelle <thomas.bruyelle@gmail.com>
Thomas Bushnell, BSG <tbushnell@google.com>
Thomas de Zeeuw <thomasdezeeuw@gmail.com>
Thomas Desrosiers <thomasdesr@gmail.com>
Thomas Habets <habets@google.com>
Thomas Kappler <tkappler@gmail.com>
Thomas Meson <zllak@hycik.org>
Thomas Symborski <thomas.symborski@gmail.com>
Thomas Wanielista <tomwans@gmail.com>
Thorben Krueger <thorben.krueger@gmail.com>
Thordur Bjornsson <thorduri@secnorth.net>
Tiago Peczenyj <tpeczenyj@weborama.com>
Tiago

Queiroz <contato@tiago.eti.br>
Tianji Wu <the729@gmail.com>
Tianon Gravi <admwiggin@gmail.com>
Tilman Dilo <tilman.dilo@gmail.com>
Tim Cooijmans <timcooijmans@gmail.com>
Tim Cooper <tim.cooper@layeh.com>
Tim Ebringer <tim.ebringer@gmail.com>
Tim Heckman <t@heckman.io>
Tim Henderson <tim.tadh@gmail.com>
Tim Hockin <thockin@google.com>
Tim King <taking@google.com>
Tim Mhlmann <muhlemmer@gmail.com>
Tim Swast <swast@google.com>
Tim Wright <tenortim@gmail.com>
Tim Xu <xiaoxubeii@gmail.com>
Timmy Douglas <timmyd983@gmail.com>
Timo Savola <timo.savola@gmail.com>
Timo Truys <alkaloid.btx@gmail.com>
Timothy Gu <timothygu99@gmail.com>
Timothy Studd <tim@timstudd.com>
Tipp Moseley <tipp@google.com>
Tiwei Bie <tiwei.btw@antgroup.com>
Tobias Assarsson <tobias.assarsson@gmail.com>
Tobias Columbus <tobias.columbus@gmail.com> <tobias.columbus@googlemail.com>
Tobias Klauser <tklauser@distanz.ch>
Tobias Kohlbau <tobias@kohlbau.de>
Toby Burrell <kurin@google.com>
Todd Kulesza <tkulesza@google.com>
Todd
Neal <todd@tneal.org>
Todd Wang <toddwang@gmail.com>
Tom Anthony <git@tomanthony.co.uk>
Tom Bergan <tombergan@google.com>
Tom Freudenberg <tom.freudenberg@4commerce.de>
Tom Heng <zhm20070928@gmail.com>
Tom Lanyon <tomlanyon@google.com>
Tom Levy <tomlevy93@gmail.com>
Tom Limoncelli <tal@whatexit.org>
Tom Linfoord <tomlinfoord@gmail.com>
Tom Panton <tom@tomandtally.co.uk>
Tom Parkin <tom.parkin@gmail.com>
Tom Payne <twpayne@gmail.com>
Tom Szymanski <tgs@google.com>
Tom Thorogood <me+google@tomthorogood.co.uk>
Tom Wilkie <tom@weave.works>
Tom Zierbock <tomzierbock@gmail.com>
Tomas Dabasinskas <tomas@dabasinskas.net>
Tommy Schaefer <tommy.schaefer@teecom.com>

Tomohiro Kusumoto <zabio1192@gmail.com>
Tomoya Ishizaki <zaq1tomo@gmail.com>
Tonis Tiigi <tonistiigi@gmail.com>
Tony Reix <tony.reix@bull.net>
Tony Walker <walkert.uk@gmail.com>
Tooru Takahashi <tooru.takahashi134@gmail.com>
Tor Andersson <tor.andersson@gmail.com>
Torben Schinke <torben.schinke@neotos.de>
Tormod Erevik Lea <tormodlea@gmail.com>
Toshihiro
Shiino <shiino.toshihiro@gmail.com>
Toshiki Shima <hayabusa1419@gmail.com>
Totoro W <tw19881113@gmail.com>
Travis Bischel <travis.bischel@gmail.com>
Travis Cline <travis.cline@gmail.com>
Trevor Dixon <trevordixon@gmail.com>
Trevor Strohman <trevor.strohman@gmail.com>
Trey Lawrence <lawrence.trey@gmail.com>
Trey Roessig <trey.roessig@gmail.com>
Trey Tacon <ttacon@gmail.com>
Tristan Amini <tamini01@ca.ibm.com>
Tristan Colgate <tcolgate@gmail.com>
Tristan Oohry <ooohry@gmail.com>
Tristan Rice <rice@fn.lc>
Troels Thomsen <troels@thomsen.io>
Trong Bui <trong.buiquoc@gmail.com>
Trung Nguyen <trung.n.k@gmail.com>
Tsuji Daishiro <dram.dt.shonan@gmail.com>
Tudor Golubenco <tudor.g@gmail.com>
Tugdual Saunier <tugdual.saunier@gmail.com>
Tuo Shan <sturbo89@gmail.com> <shantuo@google.com>
Tyler Bui-Palsulich <tpalsulich@google.com>
Tyler Bunnell <tylerbunnell@gmail.com>
Tyler Treat <ttreat31@gmail.com>
Tyson Andre <tysonandre775@gmail.com>
Tzach Shabtay <tzachshabtay@gmail.com>
Tzu-Chiao
Yeh <su3g4284zo6y7@gmail.com>
Tzu-Jung Lee <roylee17@currant.com>
Udalov Max <re.udalov@gmail.com>
Uddeshya Singh <singhuddeshyaofficial@gmail.com>
Ugorji Nwoke <ugorji@gmail.com>
Ulf Holm Nielsen <doktor@dyregod.dk>
Ulrich Kunitz <uli.kunitz@gmail.com>
Umang Parmar <umangjparmar@gmail.com>
Uriel Mangado <uriel@berlinblue.org>
Urvil Patel <patelurvil38@gmail.com>
Utkarsh Dixit <53217283+utkarsh-extc@users.noreply.github.com>

Uttam C Pawar <uttam.c.pawar@intel.com>
Vadim Grek <vadimprog@gmail.com>
Vadim Vygonets <unixdj@gmail.com>
Val Polouchkine <vpolouch@justin.tv>
Valentin Vidic <vvidic@valentin-vidic.from.hr>
Vaughn Iverson <vsivsi@yahoo.com>
Vee Zhang <veezhang@126.com> <vveezhang@gmail.com>
Vega Garcia Luis Alfonso <vegacom@gmail.com>
Venil Noronha <veniln@vmware.com>
Veselkov Konstantin <kostozyb@gmail.com>
Viacheslav Poturaev <vearutop@gmail.com>
Victor Chudnovsky <vchudnov@google.com>
Victor Michel <victor@optimize.cloud>
Victor Vrantchan <vrancean+github@gmail.com>
Vignesh
Ramachandra <vickyramachandra@gmail.com>
Vikas Kedia <vikask@google.com>
Ville Skytt <ville.skytta@iki.fi>
Vincent Ambo <tazjin@googlemail.com>
Vincent Batts <vbatts@hashbangbash.com> <vbatts@gmail.com>
Vincent Vanackere <vincent.vanackere@gmail.com>
Vinu Rajashekhar <vinutheraj@gmail.com>
Vish Subramanian <vish@google.com>
Vishal Dalwadi <dalwadivishal26@gmail.com>
Vishvananda Ishaya <vishvananda@gmail.com>
Visweswara R <r.visweswara@gmail.com>
Vitaly Zdanevich <zdanevich.vitaly@ya.ru>
Vitor De Mario <vitordemario@gmail.com>
Vivek Sekhar <vsekhar@google.com>
Vivek V <iamvivekv96@gmail.com>
Vivian Liang <vliang88@gmail.com>
Vlad Krasnov <vlad@cloudflare.com>
Vladimir Evgrafov <evgrafov.vladimir@gmail.com>
Vladimir Kovpak <cn007b@gmail.com>
Vladimir Kuzmin <vkuzmin@uber.com>
Vladimir Mihailenco <vladimir.webdev@gmail.com>
Vladimir Nikishenko <vova616@gmail.com>
Vladimir Stefanovic <vladimir.stefanovic@imgtec.com>
Vladimir Varankin <nek.narqo@gmail.com>
Vojtech Bocek <vbocek@gmail.com>
Volker
Dobler <dr.volker.dobler@gmail.com>
Volodymyr Paprotski <vpaprots@ca.ibm.com>
Vyacheslav Pachkov <slava.pach@gmail.com>
W. Trevor King <wking@tremily.us>
Wade Simmons <wade@wades.im>
Wagner Riffel <wgrriffel@gmail.com>
Walt Della <walt@javins.net>

Walter Poupore <wpoupore@google.com>
Wander Lairson Costa <wcosta@mozilla.com>
Wang Xuerui <git@xen0n.name>
Warren Fernandes <warren.f.fernandes@gmail.com>
Wayne Ashley Berry <wayneashleyberry@gmail.com>
Wedson Almeida Filho <wedsonaf@google.com>
Weerasak Chongnguluam <singpor@gmail.com>
Wi Cngru <crvv.mail@gmail.com>
Wei Fu <fhfuwei@163.com>
Wei Guangjing <vcc.163@gmail.com>
Wei Xiao <wei.xiao@arm.com>
Wei Xikai <xykwei@gmail.com>
Weichao Tang <tevic.tt@gmail.com>
Weilu Jia <optix2000@gmail.com>
Weixie Cui <cuiweixie@gmail.com> <523516579@qq.com>
Wembley G. Leach, Jr <wembley.gl@gmail.com>
Wenlei (Frank) He <wlhe@google.com>
Wenzel Lowe <lowewenzel@gmail.com>
Wil Selwood <wselwood@gmail.com>
Wilfried Teiken <wteiken@google.com>
Will
Beason <willbeason@gmail.com>
Will Chan <willchan@google.com>
Will Faught <will.faught@gmail.com>
Will Morrow <wmorrow.qdt@qualcommdatacenter.com>
Will Norris <willnorris@google.com>
Will Storey <will@summercat.com>
Willem van der Schyff <willemvds@gmail.com>
William Chan <willchan@chromium.org>
William Chang <mr.williamchang@gmail.com>
William Josephson <wjosephson@gmail.com>
William Langford <wlangfor@gmail.com>
William Orr <will@worrbase.com> <ay1244@gmail.com>
William Poussier <william.poussier@gmail.com>
Wisdom Omuya <deafgoat@gmail.com>
Wu Yunzhou <yunzhouwu@gmail.com>
Xi Ruoyao <xry23333@gmail.com>
Xia Bin <snyh@snyh.org>
Xiangdong Ji <xiangdong.ji@arm.com>
Xiaodong Liu <teaofmoli@gmail.com>
Xing Gao <18340825824@163.com>
Xing Xing <mikespook@gmail.com>
Xingqiang Bai <bxq2011hust@qq.com>
Xu Fei <badgangkiller@gmail.com>
Xudong Zhang <felixmelon@gmail.com>
Xudong Zheng <7pkvm5aw@slicealias.com>
Xuyang Kang <xuyangkang@gmail.com>
Yamagishi Kazutoshi <ykzts@desire.sh>

Yan
Zou <yzou@google.com>
Yang Hau <vulxj0j8j8@gmail.com>
Yang Tian <linuxty@gmail.com>
Yann Hodique <yhodique@google.com>
Yann Kerherv <yann.kerherve@gmail.com>
Yann Salan <yannsalaun1@gmail.com>
Yannic Bonenberger <contact@yannic-bonenberger.com>
Yao Zhang <lunaria21@gmail.com>
Yaron de Leeuw <jarondl@google.com>
Yaroslav Vorobiov <yar.vorobiov@gmail.com>
Yasha Bubnov <girokompass@gmail.com>
Yasser Abdolmaleki <yasser@yasser.ca>
Yasuharu Goto <matope.ono@gmail.com>
Yasuhiro Matsumoto <mattn.jp@gmail.com>
Yasutaka Shinzaki <shinzaki@yasu26.tech>
Yasuyuki Oka <yasuyk@gmail.com>
Yazen Shunnar <yazen.shunnar@gmail.com>
Yestin Sun <ylh@pdx.edu>
Yesudeep Mangalapilly <yesudeep@google.com>
Yissakhar Z. Beck <yissakhar.beck@gmail.com>
Yo-An Lin <yoanlin93@gmail.com>
Yohei Takeda <yo.tak0812@gmail.com>
Yongjian Xu <i3dmaster@gmail.com>
Yorman Arias <cixtords@gmail.com>
Yoshiyuki Kanno <nekotaroh@gmail.com> <yoshiyuki.kanno@stoic.co.jp>
Yoshiyuki Mineo <yoshiyuki.mineo@gmail.com>
Yosuke Akatsuka
<yosuke.akatsuka@gmail.com>
Youfu Zhang <zhangyoufu@gmail.com>
Yu Heng Zhang <annita.zhang@cn.ibm.com>
Yu Xuan Zhang <zyxsh@cn.ibm.com>
Yu, Li-Yu <afg984@gmail.com>
Yuichi Kishimoto <yk2220s@gmail.com>
Yuichi Nishiwaki <yuichi.nishiwaki@gmail.com>
Yuji Yaginuma <yuuji.yaginuma@gmail.com>
Yuki Ito <mrno110y@gmail.com>
Yuki OKUSHI <huyuumi.dev@gmail.com>
Yuki Osaki <yuki.osaki7@gmail.com>
Yuki Yugui Sonoda <yugui@google.com>
Yukihiro Nishinaka <6elpinal@gmail.com>
YunQiang Su <syq@debian.org>
Yuntao Wang <ytcoode@gmail.com>
Yury Smolsky <yury@smolsky.by>
Yusuke Kagiwada <block.rxckin.beats@gmail.com>
Yuusei Kuwana <kuwana@kumama.org>
Yuval Pavel Zholkover <paulzhol@gmail.com>
Yves Junqueira <yvesj@google.com> <yves.junqueira@gmail.com>

Zac Bergquist <zbergquist99@gmail.com>
Zach Bintliff <zbintliff@gmail.com>
Zach Gershman <zachgersh@gmail.com>
Zach Hoffman <zrhoffman@apache.org>
Zach Jones <zachj1@gmail.com>
Zachary Amsden <zach@thundertoken.com>
Zachary Burkett <zburkett@splitcubestudios.com>
Zachary
Gershman <zgershman@pivotal.io>
Zaiyang Li <zaiyangli777@gmail.com>
Zak <zrjknill@gmail.com>
Zakatell Kanda <hi@zkanda.io>
Zellyn Hunter <zellyn@squareup.com> <zellyn@gmail.com>
Zev Goldstein <zev.goldstein@gmail.com>
Zhang Boyang <zhangboyang.id@gmail.com>
Zheng Dayu <davidzheng23@gmail.com>
Zheng Xu <zheng.xu@arm.com>
Zhengyu He <hzy@google.com>
Zhi Zheng <zhi.zheng052@gmail.com>
Zhongpeng Lin <zplin@uber.com>
Zhongtao Chen <chenzhongtao@126.com>
Zhongwei Yao <zhongwei.yao@arm.com>
Zhou Guangyuan <zhouguangyuan.xian@gmail.com>
Zhou Peng <p@ctruple.cn>
Ziad Hatahet <hatahet@gmail.com>
Ziheng Liu <lzhfromustc@gmail.com>
Zizhao Zhang <btw515wolf2@gmail.com>
Zorion Arrizabalaga <zorionk@gmail.com>
Zvonimir Pavlinovic <zpavlinovic@google.com>
Zyad A. Ali <zyad.ali.me@gmail.com>
<a.maksadbek@gmail.com>
<max.faceless.frei@gmail.com>
<hagen1778@gmail.com>
<tbunyk@gmail.com>
<faxriddinjon@gmail.com>
<zs349596@gmail.com>
<bronze1man@gmail.com>
People who have agreed to one of the CLAs and can contribute patches.
The AUTHORS file lists the copyright holders; this file
lists people. For example, Google employees are listed here
but not in AUTHORS, because Google holds the copyright.

<https://developers.google.com/open-source/cla/individual>
<https://developers.google.com/open-source/cla/corporate>

Names should be added to this file as:
Name <email address>
Raul Silvera <rsilvera@google.com>

Tipp Moseley <tipp@google.com>
Hyoun Kyu Cho <netforce@google.com>
Martin Spier <spiermar@gmail.com>
Taco de Wolff <tacodewolff@gmail.com>
Andrew Hunter <andrewhhunter@gmail.com>
Copyright (c) 2009 The Go Authors. All rights reserved.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

- * Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.
- * Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.
- * Neither the name of Google Inc. nor the names of its contributors may be used to endorse or promote products derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER

OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

- # This source code was written by the Go contributors.
- # The master list of contributors is in the main Go distribution,
- # visible at <https://tip.golang.org/CONTRIBUTORS>.

Apache License
Version 2.0, January 2004
<http://www.apache.org/licenses/>

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction, and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all other entities that control, are controlled by, or are under common control with that entity. For the purposes of this definition, "control" means (i) the power, direct or indirect, to cause the direction or management of such entity, whether by contract or otherwise, or (ii) ownership of fifty percent (50%) or more of the outstanding shares, or (iii) beneficial ownership of such entity.

"You" (or "Your") shall mean an individual or Legal Entity exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications, including but not limited to software source code, documentation source, and configuration files.

"Object" form shall mean any form resulting from mechanical transformation or translation of a Source form, including but not limited to compiled object code, generated documentation, and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or Object form, made available under the License, as indicated by a copyright notice that is included in or attached to the work (an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object form, that is based on (or derived from) the Work and for which the editorial revisions, annotations, elaborations, or other modifications represent, as a whole, an original work of authorship. For the purposes of this License, Derivative Works shall not include works that remain separable from, or merely link (or bind by name) to the interfaces of, the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including the original version of the Work and any modifications or additions to that Work or Derivative Works thereof, that is intentionally submitted to Licensor for inclusion in the Work by the copyright owner or by an individual or Legal Entity authorized to submit on behalf of the copyright owner. For the purposes of this definition, "submitted" means any form of electronic, verbal, or written communication sent to the Licensor or its representatives, including but not limited to communication on electronic mailing lists, source code control systems,

and issue tracking systems that are managed by, or on behalf of, the Licensor for the purpose of discussing and improving the Work, but excluding communication that is conspicuously marked or otherwise designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity on behalf of whom a Contribution has been received by Licensor and subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative Works of, publicly display, publicly perform, sublicense, and distribute the Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of this

License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable (except as stated in this section) patent license to make, have made, use, offer to sell, sell, import, and otherwise transfer the Work, where such license applies only to those patent claims licensable by such Contributor that are necessarily infringed by their Contribution(s) alone or by combination of their Contribution(s) with the Work to which such Contribution(s) was submitted. If You institute patent litigation against any entity (including a cross-claim or counterclaim in a lawsuit) alleging that the Work or a Contribution incorporated within the Work constitutes direct or contributory patent infringement, then any patent licenses granted to You under this License for that Work shall terminate as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute copies of the

Work or Derivative Works thereof in any medium, with or without modifications, and in Source or Object form, provided that You meet the following conditions:

- (a) You must give any other recipients of the Work or Derivative Works a copy of this License; and
- (b) You must cause any modified files to carry prominent notices stating that You changed the files; and
- (c) You must retain, in the Source form of any Derivative Works that You distribute, all copyright, patent, trademark, and attribution notices from the Source form of the Work,

excluding those notices that do not pertain to any part of the Derivative Works; and

(d) If the Work includes a "NOTICE" text file as part of its distribution, then any Derivative Works that You distribute must include a readable copy of the attribution notices contained within such NOTICE file, excluding

those notices that do not

pertain to any part of the Derivative Works, in at least one of the following places: within a NOTICE text file distributed as part of the Derivative Works; within the Source form or documentation, if provided along with the Derivative Works; or, within a display generated by the Derivative Works, if and wherever such third-party notices normally appear. The contents of the NOTICE file are for informational purposes only and do not modify the License. You may add Your own attribution notices within Derivative Works that You distribute, alongside or as an addendum to the NOTICE text from the Work, provided that such additional attribution notices cannot be construed as modifying the License.

You may add Your own copyright statement to Your modifications and may provide additional or different license terms and conditions

for use, reproduction, or distribution of Your modifications, or for any such Derivative Works as a whole, provided Your use, reproduction, and distribution of the Work otherwise complies with the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise, any Contribution intentionally submitted for inclusion in the Work by You to the Licensor shall be under the terms and conditions of this License, without any additional terms or conditions.

Notwithstanding the above, nothing herein shall supersede or modify the terms of any separate license agreement you may have executed with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade names, trademarks, service marks, or product names of the Licensor, except as required for reasonable and customary use in describing the origin of the Work and reproducing the

content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or agreed to in writing, Licensor provides the Work (and each Contributor provides its Contributions) on an "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied, including, without limitation, any warranties or conditions

of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A PARTICULAR PURPOSE. You are solely responsible for determining the appropriateness of using or redistributing the Work and assume any risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory, whether in tort (including negligence), contract, or otherwise, unless required by applicable law (such as deliberate and grossly negligent acts) or agreed to in writing, shall any Contributor be liable to You for damages, including any direct, indirect, special, incidental, or consequential damages of any character arising as a result of this License or out of the use or inability to use the Work (including but not limited to damages for loss of goodwill, work stoppage, computer failure or malfunction, or any and all other commercial damages or losses), even if such Contributor has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing the Work or Derivative Works thereof, You may choose to offer, and charge a fee for, acceptance of support, warranty, indemnity, or other liability obligations and/or rights consistent with this License. However, in accepting such obligations, You may act only on Your own behalf and on Your sole responsibility, not on behalf of any other Contributor, and only if You agree to indemnify, defend, and hold each Contributor harmless for any liability incurred by, or claims asserted against, such Contributor by reason of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

APPENDIX: How to apply the Apache License to your work.

To apply the Apache License to your work, attach the following boilerplate notice, with the fields enclosed by brackets "[]" replaced with your own identifying information. (Don't include the brackets!) The text should be enclosed in the appropriate comment syntax for the file format. We also recommend that a file or class name and description of purpose be included on the same "printed page" as the copyright notice for easier identification within third-party archives.

Copyright [yyyy] [name of copyright owner]

Licensed under the Apache License, Version 2.0 (the "License"); you may not use this file except in compliance with the License. You may obtain a copy of the License at

<http://www.apache.org/licenses/LICENSE-2.0>

Unless required by applicable law or agreed to in writing, software distributed under the License is distributed on an "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the License for the specific language governing permissions and limitations under the License.

Copyright 2010-2017 Mike Bostock
All rights reserved.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

- * Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.
- * Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.
- * Neither the name of the author nor the names of contributors may be used to endorse or promote products derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

Copyright (c) 2019 The Go Authors. All rights reserved.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

- * Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.
- * Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.
- * Neither the name of Google Inc. nor the names of its

contributors may be used to endorse or promote products derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER

OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

Copyright (c) 2015 The Go Authors. All rights reserved.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

- * Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.

- * Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.

- * Neither the name of Google Inc. nor the names of its contributors may be used to endorse or promote products derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER

OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

Copyright 2009-2017 Andrea Leofreddi <a.leofreddi@vleo.net>. All rights reserved.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

1. Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.
2. Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.
3. Neither the name of the copyright holder nor the names of its contributors may be used to endorse or promote products derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY COPYRIGHT HOLDERS AND CONTRIBUTORS ``AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL COPYRIGHT HOLDERS OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

The views and conclusions contained in the software and documentation are those of the authors and should not be interpreted as representing official policies, either expressed or implied, of Andrea Leofreddi.

1.84 gnupg 2.2.4-1ubuntu1.6

1.84.1 Available under license :

Here is a list with collected copyright notices. For details see the description of each individual package. [Compiled by wk 2017-11-07]

GNUPG is

Copyright (C) 1997-2017 Werner Koch

Copyright (C) 1994-2017 Free Software Foundation, Inc.

Copyright (C) 2003-2017 g10 Code GmbH

Copyright (C) 2002 Klarlvdalens Datakonsult AB

Copyright (C) 1995-1997, 2000-2007 Ulrich Drepper <drepper@gnu.ai.mit.edu>

Copyright (C) 1994 X Consortium

Copyright (C) 1998 by The Internet Society.

Copyright (C) 1998-2004 The OpenLDAP Foundation

Copyright (C) 1998-2004 Kurt D. Zeilenga.

Copyright (C) 1998-2004 Net Boolean Incorporated.
Copyright (C) 2001-2004 IBM Corporation.
Copyright (C) 1999-2003 Howard Y.H. Chu.
Copyright (C) 1999-2003 Symas Corporation.
Copyright (C) 1998-2003 Hallvard B. Furuseth.
Copyright (C) 1992-1996 Regents of the University of Michigan.
Copyright (C) 2000 Dimitrios Souflis
Copyright (C) 2008,2009,2010,2012-2016 William Ahern

GnuPG is free software;
you can redistribute it and/or modify it
under the terms of the GNU General Public License as published by
the Free Software Foundation; either version 3 of the License, or
(at your option) any later version.

GnuPG is distributed in the hope that it will be useful, but WITHOUT
ANY WARRANTY; without even the implied warranty of MERCHANTABILITY
or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public
License for more details.

You should have received a copy of the GNU General Public License
along with this program; if not, see <<https://www.gnu.org/licenses/>>.

LIBGCRYPT is

Copyright (C) 1989,1991-2017 Free Software Foundation, Inc.
Copyright (C) 1994 X Consortium
Copyright (C) 1996 L. Peter Deutsch
Copyright (C) 1997 Werner Koch
Copyright (C) 1998 The Internet Society
Copyright (C) 1996-1999 Peter Gutmann, Paul Kendall, and Chris Wedgwood
Copyright (C) 1996-2006 Peter Gutmann, Matt Thomlinson and Blake Coverett
Copyright (C) 2003 Nikos Mavroyanopoulos
Copyright (C) 2006-2007 NTT (Nippon Telegraph and Telephone Corporation)
Copyright (C) 2012-2017 g10 Code GmbH
Copyright (C) 2012 Simon Josefsson, Niels Mller
Copyright (c) 2012 Intel Corporation
Copyright (C) 2013 Christian Grothoff
Copyright (C) 2013-2017 Jussi Kivilinna
Copyright (C) 2013-2014 Dmitry Eremin-Solenikov
Copyright (C) 2014 Stephan Mueller
Copyright (C) 2017 Bundesamt fr Sicherheit in der Informationstechnik

Libgrypt is free software; you can redistribute it and/or modify
it under the terms of the GNU Lesser General Public License as
published by the Free Software Foundation; either version 2.1 of
the License, or (at your option) any later version.

Libgcrypt is distributed in the hope that it will be useful,
but WITHOUT ANY WARRANTY; without even the implied warranty of
MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
GNU Lesser General Public License for more details.

You should have received a copy of the
GNU Lesser General Public
License along with this program; if not, see <<http://www.gnu.org/licenses/>>.

LIBGPG-ERROR is

Copyright (C) 2003-2004, 2010, 2013-2017 g10 Code GmbH

libgpg-error is free software; you can redistribute it and/or
modify it under the terms of the GNU Lesser General Public License
as published by the Free Software Foundation; either version 2.1 of
the License, or (at your option) any later version.

libgpg-error is distributed in the hope that it will be useful, but
WITHOUT ANY WARRANTY; without even the implied warranty of
MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU
Lesser General Public License for more details.

You should have received a copy of the GNU Lesser General Public License
along with this program; if not, see <<http://www.gnu.org/licenses/>>.

LIBASSUAN is

Copyright (C) 1992-2013 Free Software Foundation, Inc.

Copyright (C) 1994 X Consortium

Copyright (C) 2000 Werner Koch (dd9jn)

Copyright (C)

2001-2016 g10 Code GmbH

Copyright (C) 2004 Simon Josefsson

Assuan is free software; you can redistribute it and/or modify it
under the terms of the GNU Lesser General Public License as
published by the Free Software Foundation; either version 2.1 of
the License, or (at your option) any later version.

Assuan is distributed in the hope that it will be useful, but
WITHOUT ANY WARRANTY; without even the implied warranty of
MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU
Lesser General Public License for more details.

You should have received a copy of the GNU Lesser General Public License along with this program; if not, see <<http://www.gnu.org/licenses/>>.

LIBKSBA is

Copyright (C) 2001, 2002, 2003, 2004, 2005, 2006, 2010, 2011
2012, 2013, 2014, 2015 g10 Code GmbH

Copyright (C) 2001, 2002, 2003, 2007 Free Software Foundation, Inc.

Copyright (C) 2000, 2001 Fabio Fiorina

The library and the header files are distributed under the following terms (LGPLv3+/GPLv2+):

KSBA is free software; you can redistribute it and/or modify it under the terms of either

- the GNU Lesser General Public License as published by the Free Software Foundation; either version 3 of the License, or (at your option) any later version.

or

- the GNU General Public License as published by the Free Software Foundation; either version 2 of the License, or (at your option) any later version.

or both in parallel, as here.

KSBA is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details.

The other parts (e.g. manual, build system, tests) are distributed under the following terms (GPLv3):

KSBA is free software; you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation; either version 3 of the License, or (at your option) any later version.

KSBA is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details.

NPTH is

Copyright (C) 2011, 2012, 2014, 2015, 2017 g10 Code GmbH

nPth is free software; you can redistribute it and/or modify it under the terms of the GNU Lesser General Public License as published by the Free Software Foundation; either version 2.1 of the License, or (at your option) any later version.

nPth is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU Lesser General Public License for more details.

You should have received a copy of the GNU Lesser General Public License along with this program; if not, see <<https://www.gnu.org/licenses/>>.

NTBTLS is

Copyright (C) 2006-2014 Brainspark B.V.
Copyright (C) 2014-2017 g10 Code GmbH

NTBTLS is free software; you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation; either version 3 of the License, or (at your option) any later version.

NTBTLS is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details.

You should have received a copy of the GNU General Public License along with this program; if not, see <<http://www.gnu.org/licenses/>>.

PINENTRY is

Copyright (C) 1999 Robert Bihlmeyer <robbe@orcus.priv.at>
Copyright (C) 2001-2004, 2007-2008, 2010, 2015-2016 g10 Code GmbH
Copyright (C) 2002, 2008 Klarlvdalens Datakonsult AB (KDAB)
Copyright (C) 2004 by Albrecht
Dre <albrecht.dress@arcor.de>
Copyright 2007 Ingo Klöcker

Copyright (C) 2014 Serge Voilokov
Copyright (C) 2015 Daiki Ueno
Copyright (C) 2015 Daniel Kahn Gillmor <dkg@fifthhorseman.net>
Copyright 2016 Intevation GmbH

PINENTRY is free software; you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation; either version 2 of the License, or (at your option) any later version.

PINENTRY is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details.

You should have received a copy of the GNU General Public License along with this program; if not, see <<https://www.gnu.org/licenses/>>.

GPGME is

Copyright (C) 1991-2013 Free Software Foundation, Inc.
Copyright (C) 2000-2001 Werner Koch
Copyright (C) 2001-2017 g10 Code GmbH

Copyright (C) 2002 Klarlvdalens Datakonsult AB
Copyright (C) 2004-2008 Igor Belyi
Copyright (C) 2002 John Goerzen
Copyright (C) 2014, 2015 Martin Albrecht
Copyright (C) 2015 Ben McGinnes
Copyright (C) 2015-2016 Bundesamt fr Sicherheit in der Informationstechnik
Copyright (C) 2016 Intevation GmbH

GPGME is free software; you can redistribute it and/or modify it under the terms of the GNU Lesser General Public License as published by the Free Software Foundation; either version 2.1 of the License, or (at your option) any later version.

GPGME is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU Lesser General Public License for more details.

You should have received a copy of the GNU Lesser General Public License along with this program; if not, see <<http://www.gnu.org/licenses/>>.

NSIS is

Copyright 1999-2009 Nullsoft and Contributors

Copyright 2002-2008 Amir Szekely

Copyright 2003 Ramon

This license applies to everything in the NSIS package, except where otherwise noted.

This software is provided 'as-is', without any express or implied warranty. In no event will the authors be held liable for any damages arising from the use of this software.

Permission is granted to anyone to use this software for any purpose, including commercial applications, and to alter it and redistribute it freely, subject to the following restrictions:

1. The origin of this software must not be misrepresented; you must not claim that you wrote the original software. If you use this software in a product, an acknowledgment in the product documentation would be appreciated but is not required.
2. Altered source versions must be plainly marked as such, and must not be misrepresented as being the original software.
3. This notice may not be removed or altered from any source distribution.

The user interface used with the installer is

Copyright 2002-2009 Joost Verburg

[It is distributed along with NSIS and the same conditions as stated above apply]

TinySCHEME is part of the GnuPG package and is

Copyright (c) 2000, Dimitrios Souflis

All rights reserved.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.

Redistributions in binary form must reproduce the above copyright

notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.

Neither the name of Dimitrios Souflis nor the names of the contributors may be used to endorse or promote products derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED
BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS
``AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT
LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR
A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE REGENTS OR
CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL,
EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO,
PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR
PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF
LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING
NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

LIBDNS is part of the GnuPG package and is

Copyright (c) 2008, 2009, 2010, 2012-2016 William Ahern

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"),
to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to permit
persons to whom the Software is furnished to do so, subject to the
following conditions:

The above copyright notice and this permission notice shall be included
in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS
OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN
NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM,
DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR
OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE
USE OR OTHER DEALINGS IN THE SOFTWARE.

ZLIB is

(C) 1995-2013 Jean-loup Gailly and Mark Adler

This software is provided 'as-is', without any express or implied warranty. In no event will the authors be held liable for any damages arising from the use of this software.

Permission is granted to anyone to use this software for any purpose, including commercial applications, and to alter it and redistribute it freely, subject to the following restrictions:

1. The origin of this software must not be misrepresented; you must not claim that you wrote the original software. If you use this software in a product, an acknowledgment in the product documentation would be appreciated but is not required.
2. Altered source versions must be plainly marked as such, and must not be misrepresented as being the original software.
3. This notice may not be removed or altered from any source distribution.

Jean-loup Gailly Mark Adler
jloup@gzip.org madler@alumni.caltech.edu

BZIP2 is

This program, "bzip2", the associated library "libbzip2", and all documentation, are copyright (C) 1996-2010 Julian R Seward. All rights reserved.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

1. Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.
2. The origin of this software must not be misrepresented; you must not claim that you wrote the original software. If you use this software in a product, an acknowledgment in the product documentation would be appreciated but is not required.
3. Altered source versions must be plainly marked as such, and must not be misrepresented as being the original software.
4. The name of the author may not be used to endorse or promote products derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE AUTHOR ``AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE AUTHOR BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

SQLITE has

been put into the public-domain by its author D. Richard Hipp:
The author disclaims copyright to this source code. In place of a legal notice, here is a blessing:

May you do good and not evil.

May you find forgiveness for yourself and forgive others.

May you share freely, never taking more than you give.

[Note that only a few files are distributed under this license.]

Creative Commons Legal Code

CC0 1.0 Universal

CREATIVE COMMONS CORPORATION IS NOT A LAW FIRM AND DOES NOT PROVIDE LEGAL SERVICES. DISTRIBUTION OF THIS DOCUMENT DOES NOT CREATE AN ATTORNEY-CLIENT RELATIONSHIP. CREATIVE COMMONS PROVIDES THIS INFORMATION ON AN "AS-IS" BASIS. CREATIVE COMMONS MAKES NO WARRANTIES REGARDING THE USE OF THIS DOCUMENT OR THE INFORMATION OR WORKS PROVIDED HEREUNDER, AND DISCLAIMS LIABILITY FOR DAMAGES RESULTING FROM THE USE OF THIS DOCUMENT OR THE INFORMATION OR WORKS PROVIDED HEREUNDER.

Statement of Purpose

The laws of most jurisdictions throughout the world automatically confer exclusive Copyright and Related Rights (defined below) upon the creator and subsequent owner(s) (each and all, an "owner") of an original work of authorship and/or a database (each, a "Work").

Certain owners wish to permanently relinquish those rights to a Work for the purpose of contributing

to a commons of creative, cultural and scientific works ("Commons") that the public can reliably and without fear of later claims of infringement build upon, modify, incorporate in other works, reuse and redistribute as freely as possible in any form whatsoever and for any purposes, including without limitation commercial purposes. These owners may contribute to the Commons to promote the ideal of a free culture and the further production of creative, cultural and scientific works, or to gain reputation or greater distribution for their Work in part through the use and efforts of others.

For these and/or other purposes and motivations, and without any expectation of additional consideration or compensation, the person associating CC0 with a Work (the "Affirmer"), to the extent that he or she is an owner of Copyright and Related Rights in the Work, voluntarily elects to apply CC0 to the Work and publicly distribute the Work under its terms, with knowledge of his or her Copyright and Related Rights in the Work and the meaning and intended legal effect of CC0 on those rights.

1. Copyright and Related Rights. A Work made available under CC0 may be protected by copyright and related or neighboring rights ("Copyright and Related Rights"). Copyright and Related Rights include, but are not limited to, the following:

- i. the right to reproduce, adapt, distribute, perform, display, communicate, and translate a Work;
- ii. moral rights retained by the original author(s) and/or performer(s);
- iii. publicity and privacy rights pertaining to a person's image or likeness depicted in a Work;
- iv. rights protecting against unfair competition in regards to a Work, subject to the limitations in paragraph 4(a), below;
- v. rights protecting the extraction, dissemination, use and reuse of data in a Work;
- vi. database rights (such as those arising under Directive 96/9/EC of the European Parliament and of the Council of 11 March 1996 on the legal protection of databases, and under any national implementation thereof, including any amended or successor version of such directive); and
- vii. other similar, equivalent or corresponding rights throughout the world based on applicable law or treaty, and any national implementations thereof.

2. Waiver. To the greatest extent permitted by, but not in contravention of, applicable law, Affirmer hereby overtly, fully, permanently, irrevocably and unconditionally waives, abandons, and surrenders all of Affirmer's Copyright and Related Rights and associated claims and causes of action, whether now known or unknown (including existing as well as

future claims and causes of action), in the Work (i) in all territories worldwide, (ii) for the maximum duration provided by applicable law or treaty (including future time extensions), (iii) in any current or future medium and for any number of copies, and (iv) for any purpose whatsoever, including without limitation commercial, advertising or promotional purposes (the "Waiver"). Affirmer makes the Waiver for the benefit of each member of the public at large and to the detriment of Affirmer's heirs and successors, fully intending that such Waiver shall not be subject to revocation, rescission, cancellation, termination, or any other legal or equitable action to disrupt the quiet enjoyment of the Work by the public as contemplated by Affirmer's express Statement of Purpose.

3. Public License Fallback. Should any part of the Waiver for any reason be judged legally invalid or ineffective under applicable law, then the Waiver shall be preserved to the maximum extent permitted taking into account Affirmer's express Statement of Purpose. In addition, to the extent the Waiver is so judged Affirmer hereby grants to each affected person a royalty-free, non transferable, non sublicensable, non exclusive, irrevocable and unconditional license to exercise Affirmer's Copyright and Related Rights in the Work (i) in all territories worldwide, (ii) for the maximum duration provided by applicable law or treaty (including future time extensions), (iii) in any current or future medium and for any number of copies, and (iv) for any purpose whatsoever, including without limitation commercial, advertising or promotional purposes (the "License"). The License shall be deemed effective as of the date CC0 was applied by Affirmer to the Work. Should any part of the License for any reason be judged legally invalid or ineffective under applicable law, such partial invalidity or ineffectiveness shall not invalidate the remainder of the License, and in such case Affirmer hereby affirms that he or she will not (i) exercise any of his or her remaining Copyright and Related Rights in the Work or (ii) assert any associated claims and causes of action with respect to the Work, in either case contrary to Affirmer's express Statement of Purpose.

4. Limitations and Disclaimers.

- a. No trademark or patent rights held by Affirmer are waived, abandoned, surrendered, licensed or otherwise affected by this document.
- b. Affirmer offers the Work as-is and makes no representations or warranties of any kind concerning the Work, express, implied, statutory or otherwise, including without limitation warranties of title, merchantability, fitness for a particular purpose, non infringement, or the absence of latent or other defects, accuracy, or the present or absence of errors, whether or not discoverable, all to the greatest extent permissible under applicable law.

- c. Affirmer disclaims responsibility for clearing rights of other persons that may apply to the Work or any use thereof, including without limitation any person's Copyright and Related Rights in the Work. Further, Affirmer disclaims responsibility for obtaining any necessary consents, permissions or other rights required for any use of the Work.
- d. Affirmer understands and acknowledges that Creative Commons is not a party to this document and has no duty or obligation with respect to this CC0 or use of the Work.

GNU GENERAL PUBLIC LICENSE
Version 3, 29 June 2007

Copyright (C) 2007 Free Software Foundation, Inc. <<https://fsf.org/>>
Everyone is permitted to copy and distribute verbatim copies of this license document, but changing it is not allowed.

Preamble

The GNU General Public License is a free, copyleft license for software and other kinds of works.

The licenses for most software and other practical works are designed to take away your freedom to share and change the works. By contrast, the GNU General Public License is intended to guarantee your freedom to share and change all versions of a program--to make sure it remains free software for all its users. We, the Free Software Foundation, use the GNU General Public License for most of our software; it applies also to any other work released this way by its authors. You can apply it to your programs, too.

When we speak of free software, we are referring to freedom, not price. Our General Public Licenses are designed to make sure that you have the freedom to distribute copies of free software (and charge for them if you wish), that you receive source code or can get it if you want it, that you can change the software or use pieces of it in new free programs, and that you know you can do these things.

To protect your rights, we need to prevent others from denying you these rights or asking you to surrender the rights. Therefore, you have certain responsibilities if you distribute copies of the software, or if you modify it: responsibilities to respect the freedom of others.

For example, if you distribute copies of such a program, whether gratis or for a fee, you must pass on to the recipients the same freedoms that you received. You must make sure that they, too, receive

or can get the source code. And you must show them these terms so they know their rights.

Developers that use the GNU GPL protect your rights with two steps: (1) assert copyright on the software, and (2) offer you this License giving you legal permission to copy, distribute and/or modify it.

For the developers' and authors' protection, the GPL clearly explains that there is no warranty for this free software. For both users' and authors' sake, the GPL requires that modified versions be marked as changed, so that their problems will not be attributed erroneously to authors of previous versions.

Some devices are designed to deny users access to install or run modified versions of the software inside them, although the manufacturer can do so. This is fundamentally incompatible with the aim of protecting users' freedom to change the software. The systematic pattern of such abuse occurs in the area of products for individuals to use, which is precisely where it is most unacceptable. Therefore, we have designed this version of the GPL to prohibit the practice for those products. If such problems arise substantially in other domains, we stand ready to extend this provision to those domains in future versions of the GPL, as needed to protect the freedom of users.

Finally, every program is threatened constantly by software patents. States should not allow patents to restrict development and use of software on general-purpose computers, but in those that do, we wish to avoid the special danger that patents applied to a free program could make it effectively proprietary. To prevent this, the GPL assures that patents cannot be used to render the program non-free.

The precise terms and conditions for copying, distribution and modification follow.

TERMS AND CONDITIONS

0. Definitions.

"This License" refers to version 3 of the GNU General Public License.

"Copyright" also means copyright-like laws that apply to other kinds of works, such as semiconductor masks.

"The Program" refers to any copyrightable work licensed under this License. Each licensee is addressed as "you". "Licensees" and "recipients" may be individuals or organizations.

To

"modify" a work means to copy from or adapt all or part of the work in a fashion requiring copyright permission, other than the making of an exact copy. The resulting work is called a "modified version" of the earlier work or a work "based on" the earlier work.

A "covered work" means either the unmodified Program or a work based on the Program.

To "propagate" a work means to do anything with it that, without permission, would make you directly or secondarily liable for infringement under applicable copyright law, except executing it on a computer or modifying a private copy. Propagation includes copying, distribution (with or without modification), making available to the public, and in some countries other activities as well.

To "convey" a work means any kind of propagation that enables other parties to make or receive copies. Mere interaction with a user through a computer network, with no transfer of a copy, is not conveying.

An interactive user interface displays "Appropriate Legal Notices"

to the extent that it includes a convenient and prominently visible feature that (1) displays an appropriate copyright notice, and (2) tells the user that there is no warranty for the work (except to the extent that warranties are provided), that licensees may convey the work under this License, and how to view a copy of this License. If the interface presents a list of user commands or options, such as a menu, a prominent item in the list meets this criterion.

1. Source Code.

The "source code" for a work means the preferred form of the work for making modifications to it. "Object code" means any non-source form of a work.

A "Standard Interface" means an interface that either is an official standard defined by a recognized standards body, or, in the case of interfaces specified for a particular programming language, one that is widely used among developers working in that language.

The "System Libraries" of an executable work include anything, other than

the work as a whole, that (a) is included in the normal form of packaging a Major Component, but which is not part of that Major Component, and (b) serves only to enable use of the work with that Major Component, or to implement a Standard Interface for which an

implementation is available to the public in source code form. A "Major Component", in this context, means a major essential component (kernel, window system, and so on) of the specific operating system (if any) on which the executable work runs, or a compiler used to produce the work, or an object code interpreter used to run it.

The "Corresponding Source" for a work in object code form means all the source code needed to generate, install, and (for an executable work) run the object code and to modify the work, including scripts to control those activities. However, it does not include the work's System Libraries, or general-purpose tools or generally available free programs which are used unmodified in performing those activities but which are not part of the work. For example, Corresponding Source includes interface definition files associated with source files for the work, and the source code for shared libraries and dynamically linked subprograms that the work is specifically designed to require, such as by intimate data communication or control flow between those subprograms and other parts of the work.

The Corresponding Source need not include anything that users can regenerate automatically from other parts of the Corresponding Source.

The Corresponding Source for a work in source code form is that same work.

2. Basic Permissions.

All rights granted under this License are granted for the term of copyright on the Program, and are irrevocable provided the stated conditions are met. This License explicitly affirms your unlimited permission to run the unmodified Program. The output from running a covered work is covered by this License only if the output, given its content, constitutes a covered work. This License acknowledges your rights of fair use or other equivalent, as provided by copyright law.

You may make, run and propagate covered works that you do not convey, without conditions so long as your license otherwise remains in force. You may convey covered works to others for the sole purpose of having them make modifications exclusively for you, or provide you with facilities for running those works, provided that you comply with the terms of this License in conveying all material for which you do not control copyright. Those thus making or running the covered works for you must do so exclusively on your behalf, under your direction and control, on terms that prohibit them from making any copies of your copyrighted material outside their relationship with you.

Conveying under any other circumstances is permitted solely under the conditions stated below. Sublicensing is not allowed; section 10 makes it unnecessary.

3. Protecting Users'

Legal Rights From Anti-Circumvention Law.

No covered work shall be deemed part of an effective technological measure under any applicable law fulfilling obligations under article 11 of the WIPO copyright treaty adopted on 20 December 1996, or similar laws prohibiting or restricting circumvention of such measures.

When you convey a covered work, you waive any legal power to forbid circumvention of technological measures to the extent such circumvention is effected by exercising rights under this License with respect to the covered work, and you disclaim any intention to limit operation or modification of the work as a means of enforcing, against the work's users, your or third parties' legal rights to forbid circumvention of technological measures.

4. Conveying Verbatim Copies.

You may convey verbatim copies of the Program's source code as you receive it, in any medium, provided that you conspicuously and appropriately publish on each copy an appropriate copyright notice; keep intact all notices stating that this License and any non-permissive terms added in accord with section 7 apply to the code; keep intact all notices of the absence of any warranty; and give all recipients a copy of this License along with the Program.

You may charge any price or no price for each copy that you convey, and you may offer support or warranty protection for a fee.

5. Conveying Modified Source Versions.

You may convey a work based on the Program, or the modifications to produce it from the Program, in the form of source code under the terms of section 4, provided that you also meet all of these conditions:

- a) The work must carry prominent notices stating that you modified it, and giving a relevant date.
- b) The work must carry prominent notices stating that it is released under this License and any conditions added under section 7. This requirement modifies the requirement in section 4 to

"keep intact all notices".

c) You must license

the entire work, as a whole, under this

License to anyone who comes into possession of a copy. This License will therefore apply, along with any applicable section 7 additional terms, to the whole of the work, and all its parts, regardless of how they are packaged. This License gives no permission to license the work in any other way, but it does not invalidate such permission if you have separately received it.

d) If the work has interactive user interfaces, each must display Appropriate Legal Notices; however, if the Program has interactive interfaces that do not display Appropriate Legal Notices, your work need not make them do so.

A compilation of a covered work with other separate and independent works, which are not by their nature extensions of the covered work, and which are not combined with it such as to form a larger program, in or on a volume of a storage or distribution medium, is called an "aggregate" if the compilation and its resulting copyright are not used to limit the access or legal rights of the compilation's users beyond what the individual works permit. Inclusion of a covered work in an aggregate does not cause this License to apply to the other parts of the aggregate.

6. Conveying Non-Source Forms.

You may convey a covered work in object code form under the terms of sections 4 and 5, provided that you also convey the machine-readable Corresponding Source under the terms of this License, in one of these ways:

a) Convey the object code in, or embodied in, a physical product (including a physical distribution medium), accompanied by the Corresponding Source fixed on a durable physical medium customarily used for software interchange.

b) Convey the object code in, or embodied in, a physical product (including a physical distribution medium), accompanied by a written offer, valid for at least three years and valid for as long as you offer spare parts or customer support for that product model, to give anyone who possesses the object code either (1) a copy of the Corresponding Source for all the software in the product that is covered by this License, on a durable physical medium customarily used for software interchange, for a price no

more than your reasonable cost of physically performing this conveying of source, or (2) access to copy the Corresponding Source from a network server at no charge.

c) Convey individual copies of the object code with a copy of the written offer to provide the Corresponding Source. This alternative is allowed only occasionally and noncommercially, and only if you received the object code with such an offer, in accord with subsection 6b.

d) Convey the object code by offering access from a designated place (gratis or for a charge), and offer equivalent access to the Corresponding Source in the same way through the same place at no further charge.

You need not require recipients to copy the Corresponding Source along with the object code. If the place to copy the object code is a network server, the Corresponding Source may be on a different server (operated by you or a third party) that supports equivalent copying facilities, provided you maintain clear directions next to the object code saying where to find the Corresponding Source. Regardless of what server hosts the Corresponding Source, you remain obligated to ensure that it is available for as long as needed to satisfy these requirements.

e) Convey the object code using peer-to-peer transmission, provided you inform other peers where the object code and Corresponding Source of the work are being offered to the general public at no charge under subsection 6d.

A separable portion of the object code, whose source code is excluded from the Corresponding Source as a System Library, need not be included in conveying the object code work.

A "User Product" is either (1) a "consumer product", which means any tangible personal property which is normally used for personal, family, or household purposes, or (2) anything designed or sold for incorporation into a dwelling. In determining whether a product is a consumer product, doubtful cases shall be resolved in favor of coverage. For a particular product received by a particular user, "normally used" refers to a typical or common use of that class of product, regardless of the status of the particular user or of the way in which the particular user actually uses, or expects or is expected to use, the product. A product is a consumer product regardless of whether the product has substantial commercial, industrial or non-consumer uses, unless such uses represent the only significant mode of use of the product.

"Installation Information" for a User Product means any methods,

procedures, authorization keys, or other information required to install and execute

modified versions of a covered work in that User Product from a modified version of its Corresponding Source. The information must suffice to ensure that the continued functioning of the modified object code is in no case prevented or interfered with solely because modification has been made.

If you convey an object code work under this section in, or with, or specifically for use in, a User Product, and the conveying occurs as part of a transaction in which the right of possession and use of the User Product is transferred to the recipient in perpetuity or for a fixed term (regardless of how the transaction is characterized), the Corresponding Source conveyed under this section must be accompanied by the Installation Information. But this requirement does not apply if neither you nor any third party retains the ability to install modified object code on the User Product (for example, the work has been installed in ROM).

The requirement to provide Installation Information does not include a requirement to continue to provide support service, warranty, or updates for a work that has been modified or installed by the recipient, or for the User Product in which it has been modified or installed. Access to a network may be denied when the modification itself materially and adversely affects the operation of the network or violates the rules and protocols for communication across the network.

Corresponding Source conveyed, and Installation Information provided, in accord with this section must be in a format that is publicly documented (and with an implementation available to the public in source code form), and must require no special password or key for unpacking, reading or copying.

7. Additional Terms.

"Additional permissions" are terms that supplement the terms of this License by making exceptions from one or more of its conditions. Additional permissions that are applicable to the entire Program shall be treated as though they were included in this License, to the extent that they are valid under applicable law. If additional permissions apply only to part of the Program, that part may be used separately under those permissions, but the entire Program remains governed by this License without regard to the additional permissions.

When you convey a copy of a covered work, you may at your option remove any additional permissions from that copy, or from any part of

it. (Additional permissions may be written to require their own removal in certain cases when you modify the work.) You may place additional permissions on material, added by you to a covered work, for which you have or can give appropriate copyright permission.

Notwithstanding any other provision of this License, for material you add to a covered work, you may (if authorized by the copyright holders of that material) supplement the terms of this License with terms:

- a) Disclaiming warranty or limiting liability differently from the terms of sections 15 and 16 of this License; or
- b) Requiring preservation of specified reasonable legal notices or author attributions in that material or in the Appropriate Legal Notices displayed by works containing it; or
- c) Prohibiting misrepresentation of the origin of that material, or requiring that modified versions of such material be marked in reasonable ways as different from the original version; or
- d) Limiting the use for publicity purposes of names of licensors or authors of the material; or
- e) Declining to grant rights under trademark law for use of some trade names, trademarks, or service marks; or
- f) Requiring indemnification of licensors and authors of that material by anyone who conveys the material (or modified versions of it) with contractual assumptions of liability to the recipient, for any liability that these contractual assumptions directly impose on those licensors and authors.

All other non-permissive additional terms are considered "further restrictions" within the meaning of section 10. If the Program as you received it, or any part of it, contains a notice stating that it is governed by this License along with a term that is a further restriction, you may remove that term. If a license document contains a further restriction but permits relicensing or conveying under this License, you may add to a covered work material governed by the terms of that license document, provided that the further restriction does not survive such relicensing or conveying.

If you add terms to a covered work in accord with this section, you must place, in the relevant source files, a statement of the additional terms that apply to those files, or a notice indicating where to find the applicable terms.

Additional terms, permissive or non-permissive, may be stated in the form of a separately written license, or stated as exceptions; the above requirements apply either way.

8. Termination.

You may not propagate or modify a covered work except as expressly provided under this License. Any attempt otherwise to propagate or modify it is void, and will automatically terminate your rights under this License (including any patent licenses granted under the third paragraph of section 11).

However, if you cease all violation of this License, then your license from a particular copyright holder is reinstated (a) provisionally, unless and until the copyright holder explicitly and finally terminates your license, and (b) permanently, if the copyright holder fails to notify you of the violation by some reasonable means prior to 60 days after the cessation.

Moreover, your license from a particular copyright holder is reinstated permanently if the copyright holder notifies you of the violation by some reasonable means, this is the first time you have received notice of violation of this License (for any work) from that copyright holder, and you cure the violation prior to 30 days after your receipt of the notice.

Termination of your rights under this section does not terminate the licenses of parties who have received copies or rights from you under this License. If your rights have been terminated and not permanently reinstated, you do not qualify to receive new licenses for the same material under section 10.

9. Acceptance Not Required for Having Copies.

You are not required to accept this License in order to receive or run a copy of the Program. Ancillary propagation of a covered work occurring solely as a consequence of using peer-to-peer transmission to receive a copy likewise does not require acceptance. However, nothing other than this License grants you permission to propagate or modify any covered work. These actions infringe copyright if you do not accept this License. Therefore, by modifying or propagating a covered work, you indicate your acceptance of this License to do so.

10. Automatic Licensing of Downstream Recipients.

Each time you convey a covered work, the recipient automatically receives a license from the original licensors, to run, modify and propagate that work, subject to this License. You are not responsible for enforcing compliance by third parties with this License.

An "entity transaction" is a transaction transferring control of an organization, or substantially all assets of one, or subdividing an organization, or merging organizations. If propagation of a covered work results from an entity transaction, each party to that transaction who receives a copy of the work also receives whatever licenses to the work the party's predecessor in interest had or could give under the previous paragraph, plus a right to possession of the Corresponding Source of the work from the predecessor in interest, if the predecessor has it or can get it with reasonable efforts.

You may not impose any further restrictions on the exercise of the rights granted or affirmed under this License. For example, you may not impose a license fee, royalty, or other charge for exercise of rights granted under this License, and you may not initiate litigation (including a cross-claim or counterclaim in a lawsuit) alleging that any patent claim is infringed by making, using, selling, offering for sale, or importing the Program or any portion of it.

11. Patents.

A "contributor" is a copyright holder who authorizes use under this License of the Program or a work on which the Program is based. The work thus licensed is called the contributor's "contributor version".

A contributor's "essential patent claims" are all patent claims owned or controlled by the contributor, whether already acquired or hereafter acquired, that would be infringed by some manner, permitted by this License, of making, using, or selling its contributor version, but do not include claims that would be infringed only as a consequence of further modification of the contributor version. For purposes of this definition, "control" includes the right to grant patent sublicenses in a manner consistent with the requirements of this License.

Each contributor grants you a non-exclusive, worldwide, royalty-free patent license under the contributor's essential patent claims, to make, use, sell, offer for sale, import and otherwise run, modify and propagate the contents of its contributor version.

In the following three paragraphs, a "patent license" is any express

agreement or commitment, however denominated, not to enforce a patent (such as an express permission to practice a patent or covenant not to sue for patent infringement). To "grant" such a patent license to a party means to make such an agreement or commitment not to enforce a patent against the party.

If you convey a covered work, knowingly relying on a patent license, and the Corresponding Source of the work is not available for anyone to copy, free of charge and under the terms of this License, through a publicly available network server or other readily accessible means, then you must either (1) cause the Corresponding Source to be so available, or (2) arrange to deprive yourself of the benefit of the patent license for this particular work, or (3) arrange, in a manner consistent with the requirements of this License, to extend the patent license to downstream recipients. "Knowingly relying" means you have actual knowledge that, but for the patent license, your conveying the covered work in a country, or your recipient's use of the covered work in a country, would infringe one or more identifiable patents in that country that you have reason to believe are valid.

If, pursuant to or in connection with a single transaction or arrangement, you convey, or propagate by procuring conveyance of, a covered work, and grant a patent license to some of the parties receiving the covered work authorizing them to use, propagate, modify or convey a specific copy of the covered work, then the patent license you grant is automatically extended to all recipients of the covered work and works based on it.

A patent license is "discriminatory" if it does not include within the scope of its coverage, prohibits the exercise of, or is conditioned on the non-exercise of one or more of the rights that are specifically granted under this License. You may not convey a covered work if you are a party to an arrangement with a third party that is in the business of distributing software, under which you make payment to the third party based on the extent of your activity of conveying the work, and under which the third party grants, to any of the parties who would receive the covered work from you, a discriminatory patent license (a) in connection with copies of the covered work conveyed by you (or copies made from those copies), or (b) primarily for and in connection with specific products or compilations that contain the covered work, unless you entered into that arrangement, or that patent license was granted, prior to 28 March 2007.

Nothing in this License shall be construed as excluding or limiting any implied license or other defenses to infringement that may

otherwise be available to you under applicable patent law.

12. No Surrender of Others' Freedom.

If conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot convey a covered work so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not convey it at all. For example, if you agree to terms that obligate you to collect a royalty for further conveying from those to whom you convey the Program, the only way you could satisfy both those terms and this License would be to refrain entirely from conveying the Program.

13. Use with the GNU Affero General Public License.

Notwithstanding any other provision of this License, you have permission to link or combine any covered work with a work licensed under version 3 of the GNU Affero General Public License into a single combined work, and to convey the resulting work. The terms of this License will continue to apply to the part which is the covered work, but the special requirements of the GNU Affero General Public License, section 13, concerning interaction through a network will apply to the combination as such.

14. Revised Versions of this License.

The Free Software Foundation may publish revised and/or new versions of the GNU General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Program specifies that a certain numbered version of the GNU General Public License "or any later version" applies to it, you have the option of following the terms and conditions either of that numbered version or of any later version published by the Free Software Foundation. If the Program does not specify a version number of the GNU General Public License, you may choose any version ever published by the Free Software Foundation.

If the Program specifies that a proxy can decide which future versions of the GNU General Public License can be used, that proxy's public statement of acceptance of a version permanently authorizes you to choose that version for the Program.

Later license versions may give you additional or different permissions. However, no additional obligations are imposed on any author or copyright holder as a result of your choosing to follow a later version.

15. Disclaimer of Warranty.

THERE IS NO WARRANTY FOR THE PROGRAM, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE PROGRAM "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE PROGRAM IS WITH YOU. SHOULD THE PROGRAM PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

16. Limitation of Liability.

IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MODIFIES AND/OR CONVEYS THE PROGRAM AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE PROGRAM (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE PROGRAM TO OPERATE WITH ANY OTHER PROGRAMS), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

17. Interpretation of Sections 15 and 16.

If the disclaimer of warranty and limitation of liability provided above cannot be given local legal effect according to their terms, reviewing courts shall apply local law that most closely approximates an absolute waiver of all civil liability in connection with the Program, unless a warranty or assumption of liability accompanies a copy of the Program in return for a fee.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Programs

If you develop a new program, and you want it to be of the greatest possible use to the public, the best way to achieve this is to make it free software which everyone can redistribute and change under these terms.

To do so, attach the following notices to the program. It is safest

to attach them to the start of each source file to most effectively state the exclusion of warranty; and each file should have at least the "copyright" line and a pointer to where the full notice is found.

<one line to give the program's name and a brief idea of what it does.>

Copyright (C) <year> <name of author>

This program is free software: you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation, either version 3 of the License, or (at your option) any later version.

This program is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details.

You should have received a copy of the GNU General Public License along with this program. If not, see <<https://www.gnu.org/licenses/>>.

Also add information on how to contact you by electronic and paper mail.

If the program does terminal interaction, make it output a short notice like this when it starts in an interactive mode:

<program> Copyright (C) <year> <name of author>

This program comes with ABSOLUTELY NO WARRANTY; for details type `show w'.

This is free software, and you are welcome to redistribute it under certain conditions; type `show c' for details.

The hypothetical commands `show w' and `show c' should show the appropriate parts of the General Public License. Of course, your program's commands might be different; for a GUI interface, you would use an "about box".

You should also get your employer (if you work as a programmer) or school, if any, to sign a "copyright disclaimer" for the program, if necessary. For more information on this, and how to apply and follow the GNU GPL, see <<https://www.gnu.org/licenses/>>.

The GNU General Public License does not permit incorporating your program into proprietary programs. If your program is a subroutine library, you may consider it more useful to permit linking proprietary applications with the library. If this is what you want to do, use the GNU Lesser General Public License instead of this License. But first,

please read

<<https://www.gnu.org/philosophy/why-not-lgpl.html>>.

GNU GENERAL PUBLIC LICENSE

Version 2, June 1991

Copyright (C) 1989, 1991 Free Software Foundation, Inc.,
51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA
Everyone is permitted to copy and distribute verbatim copies
of this license document, but changing it is not allowed.

Preamble

The licenses for most software are designed to take away your freedom to share and change it. By contrast, the GNU General Public License is intended to guarantee your freedom to share and change free software--to make sure the software is free for all its users. This General Public License applies to most of the Free Software Foundation's software and to any other program whose authors commit to using it. (Some other Free Software Foundation software is covered by the GNU Lesser General Public License instead.) You can apply it to your programs, too.

When we speak of free software, we are referring to freedom, not price.

Our General Public Licenses are designed to make sure that you have the freedom to distribute copies of free software (and charge for this service if you wish), that you receive source code or can get it if you want it, that you can change the software or use pieces of it in new free programs; and that you know you can do these things.

To protect your rights, we need to make restrictions that forbid anyone to deny you these rights or to ask you to surrender the rights. These restrictions translate to certain responsibilities for you if you distribute copies of the software, or if you modify it.

For example, if you distribute copies of such a program, whether gratis or for a fee, you must give the recipients all the rights that you have. You must make sure that they, too, receive or can get the source code. And you must show them these terms so they know their rights.

We protect your rights with two steps: (1) copyright the software, and (2) offer you this license which gives you legal permission to copy, distribute and/or modify the software.

Also, for each author's protection and ours, we want to make certain that everyone understands that there is no warranty for this free software. If the software is modified by someone else and passed on, we want its recipients to know that what they have is not the original, so

that any problems introduced by others will not reflect on the original authors' reputations.

Finally, any free program is threatened constantly by software patents. We wish to avoid the danger that redistributors of a free program will individually obtain patent licenses, in effect making the program proprietary. To prevent this, we have made it clear that any patent must be licensed for everyone's free use or not licensed at all.

The precise terms and conditions for copying, distribution and modification follow.

GNU GENERAL PUBLIC LICENSE TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

0. This License applies to any program or other work which contains a notice placed by the copyright holder saying it may be distributed under the terms of this General Public License. The "Program", below, refers to any such program or work, and a "work based on the Program" means either the Program or any derivative work under copyright law: that is to say, a work containing the Program or a portion of it, either verbatim or with modifications and/or translated into another language. (Hereinafter, translation is included without limitation in the term "modification".) Each licensee is addressed as "you".

Activities other than copying, distribution and modification are not covered by this License; they are outside its scope. The act of running the Program is not restricted, and the output from the Program is covered only if its contents constitute a work based on the Program (independent of having been made by running the Program). Whether that is true depends on what the Program does.

1. You may copy and distribute verbatim copies of the Program's source code as you receive it, in any medium, provided that you conspicuously and appropriately publish on each copy an appropriate copyright notice and disclaimer of warranty; keep intact all the notices that refer to this License and to the absence of any warranty; and give any other recipients of the Program a copy of this License along with the Program.

You may charge a fee for the physical act of transferring a copy, and you may at your option offer warranty protection in exchange for a fee.

2. You may modify your copy or copies of the Program or any portion of it, thus forming a work based on the Program, and copy and distribute such modifications or work under the terms of Section 1 above, provided that you also meet all of these conditions:

- a) You must cause the modified files to carry prominent notices stating that you changed the files and the date of any change.

- b) You must cause any work that you distribute or publish, that in whole or in part contains or is derived from the Program or any part thereof, to be licensed as a whole at no charge to all third parties under the terms of this License.

- c) If the modified program normally reads commands interactively when run, you must cause it, when started running for such interactive use in the most ordinary way, to print or display an announcement including an appropriate copyright notice and a notice that there is no warranty (or else, saying that you provide a warranty) and that users may redistribute the program under these conditions, and telling the user how to view a copy of this License. (Exception: if the Program itself is interactive but does not normally print such an announcement, your work based on the Program is not required to print an announcement.)

These requirements apply to the modified work as a whole. If identifiable sections of that work are not derived from the Program, and can be reasonably considered independent and separate works in themselves, then this License, and its terms, do not apply to those sections when you distribute them as separate works. But when you distribute the same sections as part of a whole which is a work based on the Program, the distribution of the whole must be on the terms of this License, whose permissions for other licensees extend to the entire whole, and thus to each and every part regardless of who wrote it.

Thus, it is not the intent of this section to claim rights or contest your rights to work written entirely by you; rather, the intent is to exercise the right to control the distribution of derivative or collective works based on the Program.

In addition, mere aggregation of another work not based on the Program with the Program (or with a work based on the Program) on a volume of a storage or distribution medium does not bring the other work under the scope of this License.

3. You may copy and distribute the Program (or a work based on it, under Section 2) in object code or executable form under the terms of Sections 1 and 2 above provided that you also do one of the following:

- a) Accompany it with the complete corresponding machine-readable source code, which must be distributed under the terms of Sections

1 and 2 above on a medium customarily used for software interchange; or,

b) Accompany it with a written offer, valid for at least three years, to give any third party, for a charge no more than your cost of physically performing source distribution, a complete machine-readable copy of the corresponding source code, to be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange; or,

c) Accompany it with the information you received as to the offer to distribute corresponding source code. (This alternative is allowed only for noncommercial distribution and only if you received the program in object code or executable form with such an offer, in accord with Subsection b above.)

The source code for a work means the preferred form of the work for making modifications to it. For an executable work, complete source code means all the source code for all modules it contains, plus any associated interface definition files, plus the scripts used to control compilation and installation of the executable. However, as a special exception, the source code distributed need not include anything that is normally distributed (in either source or binary form) with the major components (compiler, kernel, and so on) of the operating system on which the executable runs, unless that component itself accompanies the executable.

If distribution of executable or object code is made by offering access to copy from a designated place, then offering equivalent access to copy the source code from the same place counts as distribution of the source code, even though third parties are not compelled to copy the source along with the object code.

4. You may not copy, modify, sublicense, or distribute the Program except as expressly provided under this License. Any attempt otherwise to copy, modify, sublicense or distribute the Program is void, and will automatically terminate your rights under this License. However, parties who have received copies, or rights, from you under this License will not have their licenses terminated so long as such parties remain in full compliance.

5. You are not required to accept this License, since you have not signed it. However, nothing else grants you permission to modify or distribute the Program or its derivative works. These actions are prohibited by law if you do not accept this License. Therefore, by modifying or distributing the Program (or any work based on the Program), you indicate your acceptance of this License to do so, and

all its terms and conditions for copying, distributing
or modifying
the Program or works based on it.

6. Each time you redistribute the Program (or any work based on the Program), the recipient automatically receives a license from the original licensor to copy, distribute or modify the Program subject to these terms and conditions. You may not impose any further restrictions on the recipients' exercise of the rights granted herein. You are not responsible for enforcing compliance by third parties to this License.

7. If, as a consequence of a court judgment or allegation of patent infringement or for any other reason (not limited to patent issues), conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot distribute so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not distribute the Program at all. For example, if a patent license would not permit royalty-free redistribution of the Program by all those who receive copies directly or indirectly through you, then the only way you could satisfy both it and this License would be to refrain entirely from distribution of the Program.

If any portion of this section is held invalid or unenforceable under any particular circumstance, the balance of the section is intended to apply and the section as a whole is intended to apply in other circumstances.

It is not the purpose of this section to induce you to infringe any patents or other property right claims or to contest validity of any such claims; this section has the sole purpose of protecting the integrity of the free software distribution system, which is implemented by public license practices. Many people have made generous contributions to the wide range of software distributed through that system in reliance on consistent application of that system; it is up to the author/donor to decide if he or she is willing to distribute software through any other system and a licensee cannot impose that choice.

This section is intended to make thoroughly clear what is believed to be a consequence of the rest of this License.

8. If the distribution and/or use of the Program is restricted in certain countries either by patents or by copyrighted interfaces, the

original copyright holder who places the Program under this License may add an explicit geographical distribution limitation excluding those countries, so that distribution is permitted only in or among countries not thus excluded. In such case, this License incorporates the limitation as if written in the body of this License.

9. The Free Software Foundation may publish revised and/or new versions of the General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Program specifies a version number of this License which applies to it and "any later version", you have the option of following the terms and conditions either of that version or of any later version published by the Free Software Foundation. If the Program does not specify a version number of this License, you may choose any version ever published by the Free Software Foundation.

10. If you wish to incorporate parts of the Program into other free programs whose distribution conditions are different, write to the author to ask for permission. For software which is copyrighted by the Free Software Foundation, write to the Free Software Foundation; we sometimes make exceptions for this. Our decision will be guided by the two goals of preserving the free status of all derivatives of our free software and of promoting the sharing and reuse of software generally.

NO WARRANTY

11. BECAUSE THE PROGRAM IS LICENSED FREE OF CHARGE, THERE IS NO WARRANTY FOR THE PROGRAM, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE PROGRAM "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE PROGRAM IS WITH YOU. SHOULD THE PROGRAM PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

12. IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY AND/OR REDISTRIBUTE THE PROGRAM AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE PROGRAM (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR

THIRD PARTIES OR A FAILURE OF THE PROGRAM TO OPERATE WITH ANY OTHER PROGRAMS), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Programs

If you develop a new program, and you want it to be of the greatest possible use to the public, the best way to achieve this is to make it free software which everyone can redistribute and change under these terms.

To do so, attach the following notices to the program. It is safest to attach them to the start of each source file to most effectively convey the exclusion of warranty; and each file should have at least the "copyright" line and a pointer to where the full notice is found.

```
<one line to give the program's name and a brief idea of what it does.>  
Copyright (C) <year> <name of author>
```

```
This program is free software; you can redistribute it and/or modify  
it under the terms of the GNU  
General Public License as published by  
the Free Software Foundation; either version 2 of the License, or  
(at your option) any later version.
```

```
This program is distributed in the hope that it will be useful,  
but WITHOUT ANY WARRANTY; without even the implied warranty of  
MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the  
GNU General Public License for more details.
```

```
You should have received a copy of the GNU General Public License along  
with this program; if not, write to the Free Software Foundation, Inc.,  
51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA.
```

Also add information on how to contact you by electronic and paper mail.

If the program is interactive, make it output a short notice like this when it starts in an interactive mode:

```
Gnomovision version 69, Copyright (C) year name of author  
Gnomovision comes with ABSOLUTELY NO WARRANTY; for details type `show w'.  
This is free software, and you are welcome to redistribute  
it  
under certain conditions; type `show c' for details.
```

The hypothetical commands `show w' and `show c' should show the appropriate parts of the General Public License. Of course, the commands you use may

be called something other than `show w' and `show c'; they could even be mouse-clicks or menu items--whatever suits your program.

You should also get your employer (if you work as a programmer) or your school, if any, to sign a "copyright disclaimer" for the program, if necessary. Here is a sample; alter the names:

Yoyodyne, Inc., hereby disclaims all copyright interest in the program `Gnomovision' (which makes passes at compilers) written by James Hacker.

<signature of Ty Coon>, 1 April 1989

Ty Coon, President of Vice

This General Public License does not permit incorporating your program into proprietary programs. If your program is a subroutine library, you may consider it more useful to permit linking proprietary applications with the library. If this

is what you want to do, use the GNU Lesser General Public License instead of this License.

[Note that only a few files are distributed under this license.]

GNU LESSER GENERAL PUBLIC LICENSE

Version 2.1, February 1999

Copyright (C) 1991, 1999 Free Software Foundation, Inc.

59 Temple Place, Suite 330, Boston, MA 02111-1307 USA

Everyone is permitted to copy and distribute verbatim copies of this license document, but changing it is not allowed.

[This is the first released version of the Lesser GPL. It also counts as the successor of the GNU Library Public License, version 2, hence the version number 2.1.]

Preamble

The licenses for most software are designed to take away your freedom to share and change it. By contrast, the GNU General Public Licenses are intended to guarantee your freedom to share and change free software--to make sure the software is free for all its users.

This license, the Lesser General Public License, applies to some specially designated software packages--typically libraries--of the Free Software Foundation and other authors who decide to use it. You can use it too, but we suggest you first think carefully about whether this license or the ordinary General Public License is the better strategy to use in any particular case, based on the explanations below.

When we speak of free software, we are referring to freedom of use, not price. Our General Public Licenses are designed to make sure that you have the freedom to distribute copies of free software (and charge for this service if you wish); that you receive source code or can get it if you want it; that you can change the software and use pieces of it in new free programs; and that you are informed that you can do these things.

To protect your rights, we need to make restrictions that forbid distributors to deny you these rights or to ask you to surrender these rights. These restrictions translate to certain responsibilities for you if you distribute copies of the library or if you modify it.

For example, if you distribute copies of the library, whether gratis or for a fee, you must give the recipients all the rights that we gave you. You must make sure that they, too, receive or can get the source code. If you link other code with the library, you must provide complete object files to the recipients, so that they can relink them with the library after making changes to the library and recompiling it. And you must show them these terms so they know their rights.

We protect your rights with a two-step method: (1) we copyright the library, and (2) we offer you this license, which gives you legal permission to copy, distribute and/or modify the library.

To protect each distributor, we want to make it very clear that there is no warranty for the free library. Also, if the library is modified by someone else and passed on, the recipients should know that what they have is not the original version, so that the original author's reputation will not be affected

by problems that might be introduced by others.

^L

Finally, software patents pose a constant threat to the existence of any free program. We wish to make sure that a company cannot effectively restrict the users of a free program by obtaining a restrictive license from a patent holder. Therefore, we insist that any patent license obtained for a version of the library must be consistent with the full freedom of use specified in this license.

Most GNU software, including some libraries, is covered by the ordinary GNU General Public License. This license, the GNU Lesser General Public License, applies to certain designated libraries, and is quite different from the ordinary General Public License. We use this license for certain libraries in order to permit linking those libraries into non-free programs.

When a program is linked with a library, whether statically or using a shared library, the combination of the two is legally speaking a combined work, a derivative of the original library. The ordinary General Public License therefore permits such linking only if the entire combination fits its criteria of freedom. The Lesser General Public License permits more lax criteria for linking other code with the library.

We call this license the "Lesser" General Public License because it does Less to protect the user's freedom than the ordinary General Public License. It also provides other free software developers Less of an advantage over competing non-free programs. These disadvantages are the reason we use the ordinary General Public License for many libraries. However, the Lesser license provides advantages in certain special circumstances.

For example, on rare occasions, there may be a special need to encourage the widest possible use of a certain library, so that it becomes a de-facto standard. To achieve this, non-free programs must be allowed to use the library. A more frequent case is that a free library does the same job as widely used non-free libraries. In this case, there is little to gain by limiting the free library to free software only, so we use the Lesser General Public License.

In other cases, permission to use a particular library in non-free programs enables a greater number of people to use a large body of free software. For example, permission to use the GNU C Library in non-free programs enables many more people to use the whole GNU operating system, as well as its variant, the GNU/Linux operating system.

Although the Lesser General Public License is Less protective of the users' freedom, it does ensure that the user of a program that is linked with the Library has the freedom and the wherewithal to run that program using a modified version of the Library.

The precise terms and conditions for copying, distribution and modification follow. Pay close attention to the difference between a "work based on the library" and a "work that uses the library". The former contains code derived from the library, whereas the latter must be combined with the library in order to run.

^L

GNU LESSER GENERAL PUBLIC LICENSE
TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

0. This License Agreement applies to any software library or other program which contains a notice placed by the copyright holder or other authorized party saying it may be distributed under the terms of this Lesser General Public License (also called "this License"). Each licensee is addressed as "you".

A "library" means a collection of software functions and/or data prepared so as to be conveniently linked with application programs (which use some of those functions and data) to form executables.

The "Library", below, refers to any such software library or work which has been distributed under these terms. A "work based on the Library" means either the Library or any derivative work under copyright law: that is to say, a work containing the Library or a portion of it, either verbatim or with modifications and/or translated straightforwardly into another language. (Hereinafter, translation is included without limitation in the term "modification".)

"Source code" for a work means the preferred form of the work for making modifications to it. For a library, complete source code means all the source code for all modules it contains, plus any associated interface definition files, plus the scripts used to control compilation and installation of the library.

Activities other than copying, distribution and modification are not covered by this License; they are outside its scope. The act of running a program using the Library is not restricted, and output from such a program is covered only if its contents constitute a work based on the Library (independent of the use of the Library in a tool for writing it). Whether that is true depends on what the Library does and what the program that uses the Library does.

1. You may copy and distribute verbatim copies of the Library's complete source code as you receive it, in any medium, provided that you conspicuously and appropriately publish on each copy an appropriate copyright notice and disclaimer of warranty; keep intact all the notices that refer to this License and to the absence of any warranty; and distribute a copy of this License along with the Library.

You may charge a fee for the physical act of transferring a copy, and you may at your option offer warranty protection in exchange for a fee.

2. You may modify your copy or copies of the Library or any portion

of it, thus forming a work based on the Library, and copy and distribute such modifications or work under the terms of Section 1 above, provided that you also meet all of these conditions:

- a) The modified work must itself be a software library.
- b) You must cause the files modified to carry prominent notices stating that you changed the files and the date of any change.
- c) You must cause the whole of the work to be licensed at no charge to all third parties under the terms of this License.
- d) If a facility in the modified Library refers to a function or a table of data to be supplied by an application program that uses the facility, other than as an argument passed when the facility is invoked, then you must make a good faith effort to ensure that, in the event an application does not supply such function or table, the facility still operates, and performs whatever part of its purpose remains meaningful.

(For example, a function in a library to compute square roots has a purpose that is entirely well-defined independent of the application. Therefore, Subsection 2d requires that any application-supplied function or table used by this function must be optional: if the application does not supply it, the square root function must still compute square roots.)

These requirements apply to the modified work as a whole. If identifiable sections of that work are not derived from the Library, and can be reasonably considered independent and separate works in themselves, then this License, and its terms, do not apply to those sections when you distribute them as separate works. But when you distribute the same sections as part of a whole which is a work based on the Library, the distribution of the whole must be on the terms of this License, whose permissions for other licensees extend to the entire whole, and thus to each and every part regardless of who wrote it.

Thus, it is not the intent of this section to claim rights or contest your rights to work written entirely by you; rather, the intent is to exercise the right to control the distribution of derivative or collective works based on the Library.

In addition, mere aggregation of another work not based on the Library with the Library (or with a work based on the Library) on a volume of a storage or distribution medium does not bring the other work under

the
scope of this License.

3. You may opt to apply the terms of the ordinary GNU General Public License instead of this License to a given copy of the Library. To do this, you must alter all the notices that refer to this License, so that they refer to the ordinary GNU General Public License, version 2, instead of to this License. (If a newer version than version 2 of the ordinary GNU General Public License has appeared, then you can specify that version instead if you wish.) Do not make any other change in these notices.

^L

Once this change is made in a given copy, it is irreversible for that copy, so the ordinary GNU General Public License applies to all subsequent copies and derivative works made from that copy.

This option is useful when you wish to copy part of the code of the Library into a program that is not a library.

4. You may copy and distribute the Library (or a portion or derivative of it, under Section 2) in object code or executable form under the terms of Sections

1 and 2 above provided that you accompany it with the complete corresponding machine-readable source code, which must be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange.

If distribution of object code is made by offering access to copy from a designated place, then offering equivalent access to copy the source code from the same place satisfies the requirement to distribute the source code, even though third parties are not compelled to copy the source along with the object code.

5. A program that contains no derivative of any portion of the Library, but is designed to work with the Library by being compiled or linked with it, is called a "work that uses the Library". Such a work, in isolation, is not a derivative work of the Library, and therefore falls outside the scope of this License.

However, linking a "work that uses the Library" with the Library creates an executable that is a derivative of the Library (because it contains portions of the Library), rather than a "work that uses the library". The executable is therefore covered by this License. Section 6 states terms for distribution of such executables.

When a "work that uses the Library" uses material from a header file that is part of the Library, the object code for the work may be a

derivative work of the Library even though the source code is not. Whether this is true is especially significant if the work can be linked without the Library, or if the work is itself a library. The threshold for this to be true is not precisely defined by law.

If such an object file uses only numerical parameters, data structure layouts and accessors, and small macros and small inline functions (ten lines or less in length), then the use of the object file is unrestricted, regardless of whether it is legally a derivative work. (Executables containing this object code plus portions of the Library will still fall under Section 6.)

Otherwise,
if the work is a derivative of the Library, you may distribute the object code for the work under the terms of Section 6. Any executables containing that work also fall under Section 6, whether or not they are linked directly with the Library itself.

^L

6. As an exception to the Sections above, you may also combine or link a "work that uses the Library" with the Library to produce a work containing portions of the Library, and distribute that work under terms of your choice, provided that the terms permit modification of the work for the customer's own use and reverse engineering for debugging such modifications.

You must give prominent notice with each copy of the work that the Library is used in it and that the Library and its use are covered by this License. You must supply a copy of this License. If the work during execution displays copyright notices, you must include the copyright notice for the Library among them, as well as a reference directing the user to the copy of this License. Also, you must do one of these things:

a) Accompany the work with the complete corresponding machine-readable source code for the Library including whatever changes were used in the work (which must be distributed under Sections 1 and 2 above); and, if the work is an executable linked with the Library, with the complete machine-readable "work that uses the Library", as object code and/or source code, so that the user can modify the Library and then relink to produce a modified executable containing the modified Library. (It is understood that the user who changes the contents of definitions files in the Library will not necessarily be able to recompile the application to use the modified definitions.)

b) Use a suitable shared library mechanism for linking with the Library. A suitable mechanism is one that (1) uses at run time a

copy of the library already present on the user's computer system, rather than copying library functions into the executable, and (2) will operate properly with a modified version of the library, if the user installs one, as long as the modified version is interface-compatible with the version that the work was made with.

c) Accompany the work with a written offer, valid for at least three years, to give the same user the materials specified in Subsection 6a, above, for a charge no more than the cost of performing this distribution.

d) If distribution of the work is made by offering access to copy from a designated place, offer equivalent access to copy the above specified materials from the same place.

e) Verify that the user has already received a copy of these materials or that you have already sent this user a copy.

For an executable, the required form of the "work that uses the Library" must include any data and utility programs needed for reproducing the executable from it. However, as a special exception, the

materials to be distributed need not include anything that is normally distributed (in either source or binary form) with the major components (compiler, kernel, and so on) of the operating system on which the executable runs, unless that component itself accompanies the executable.

It may happen that this requirement contradicts the license restrictions of other proprietary libraries that do not normally accompany the operating system. Such a contradiction means you cannot use both them and the Library together in an executable that you distribute.

^L

7. You may place library facilities that are a work based on the Library side-by-side in a single library together with other library facilities not covered by this License, and distribute such a combined library, provided that the separate distribution of the work based on the Library and of the other library facilities is otherwise permitted, and provided that you do these two things:

a) Accompany the combined library with a copy of the same work based on the Library, uncombined with any other library facilities. This must be distributed under the terms of the Sections above.

b) Give prominent notice with the combined library of the fact that part of it is a work based on the Library, and explaining where to find the accompanying uncombined form of the same work.

8. You may not copy, modify, sublicense, link with, or distribute the Library except as expressly provided under this License. Any attempt otherwise to copy, modify, sublicense, link with, or distribute the Library is void, and will automatically terminate your rights under this License. However, parties who have received copies, or rights, from you under this License will not have their licenses terminated so long as such parties remain in full compliance.

9. You are not required to accept this License, since you have not signed it. However, nothing else grants you permission to modify or distribute the

Library or its derivative works. These actions are prohibited by law if you do not accept this License. Therefore, by modifying or distributing the Library (or any work based on the Library), you indicate your acceptance of this License to do so, and all its terms and conditions for copying, distributing or modifying the Library or works based on it.

10. Each time you redistribute the Library (or any work based on the Library), the recipient automatically receives a license from the original licensor to copy, distribute, link with or modify the Library subject to these terms and conditions. You may not impose any further restrictions on the recipients' exercise of the rights granted herein. You are not responsible for enforcing compliance by third parties with this License.

^L

11. If, as a consequence of a court judgment or allegation of patent infringement or for any other reason (not limited to patent issues), conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot distribute so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not distribute the Library at all. For example, if a patent license would not permit royalty-free redistribution of the Library by all those who receive copies directly or indirectly through you, then the only way you could satisfy both it and this License would be to refrain entirely from distribution of the Library.

If any portion of this section is held invalid or unenforceable under any particular circumstance, the balance of the section is intended to apply, and the section as a whole is intended to apply in other circumstances.

It is not the purpose of this section to induce you to infringe any patents or other property right claims or to contest validity of any such claims; this section has the sole purpose of protecting the integrity of the free software distribution system which is implemented by public license practices. Many people have made generous contributions to the wide range of software distributed through that system in reliance on consistent application of that system; it is up to the author/donor to decide if he or she is willing to distribute software through any other system and a licensee cannot impose that choice.

This section is intended to make thoroughly clear what is believed to be a consequence of the rest of this License.

12. If the distribution and/or use of the Library is restricted in certain countries either by patents or by copyrighted interfaces, the original copyright holder who places the Library under this License may add an explicit geographical distribution limitation excluding those countries, so that distribution is permitted only in or among countries not thus excluded. In such case, this License incorporates the limitation as if written in the body of this License.

13. The Free Software Foundation may publish revised and/or new versions of the Lesser General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Library specifies a version number of this License which applies to it and "any later version", you have the option of following the terms and conditions either of that version or of any later version published by the Free Software Foundation. If the Library does not specify a license version number, you may choose any version ever published by the Free Software Foundation.

^L

14. If you wish to incorporate parts of the Library into other free programs whose distribution conditions are incompatible with these, write to the author to ask for permission. For software which is copyrighted by the Free Software Foundation, write to the Free Software Foundation; we sometimes make exceptions for this. Our decision will be guided by the two goals of preserving the free status of all derivatives of our free software and of promoting the sharing and reuse of software generally.

NO WARRANTY

15. BECAUSE THE LIBRARY IS LICENSED FREE OF CHARGE, THERE IS NO WARRANTY FOR THE LIBRARY, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE LIBRARY "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE LIBRARY IS WITH YOU. SHOULD THE LIBRARY PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

16. IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY AND/OR REDISTRIBUTE THE LIBRARY AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE LIBRARY (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE LIBRARY TO OPERATE WITH ANY OTHER SOFTWARE), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

END OF TERMS AND CONDITIONS

^L

How to Apply These Terms to Your New Libraries

If you develop a new library, and you want it to be of the greatest possible use to the public, we recommend making it free software that everyone can redistribute and change. You can do so by permitting redistribution under these terms (or, alternatively, under the terms of the ordinary General Public License).

To apply these terms, attach the following notices to the library.

It

is safest to attach them to the start of each source file to most effectively convey the exclusion of warranty; and each file should have at least the "copyright" line and a pointer to where the full notice is found.

<one line to give the library's name and a brief idea of what it does.>

Copyright (C) <year> <name of author>

This library is free software; you can redistribute it and/or modify it under the terms of the GNU Lesser General Public License as published by the Free Software Foundation; either

version 2.1 of the License, or (at your option) any later version.

This library is distributed in the hope that it will be useful,
but WITHOUT ANY WARRANTY; without even the implied warranty of
MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU
Lesser General Public License for more details.

You should have received a copy of the GNU Lesser General Public
License along with this library; if not, write to the Free
Software
Foundation, Inc., 59 Temple Place, Suite 330, Boston, MA 02111-1307 USA

Also add information on how to contact you by electronic and paper mail.

You should also get your employer (if you work as a programmer) or
your school, if any, to sign a "copyright disclaimer" for the library,
if necessary. Here is a sample; alter the names:

Yoyodyne, Inc., hereby disclaims all copyright interest in the
library `Frob' (a library for tweaking knobs) written by James
Random Hacker.

<signature of Ty Coon>, 1 April 1990
Ty Coon, President of Vice

That's all there is to it!

LICENSE TERMS

Copyright (c) 2000, Dimitrios Souflis
All rights reserved.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions are
met:

Redistributions of source code must retain the above copyright notice,
this list of conditions and the following disclaimer.

Redistributions in binary form must reproduce the above copyright
notice, this list of conditions and the following disclaimer in the
documentation and/or other materials provided with the distribution.

Neither the name of Dimitrios Souflis nor the names of the
contributors may be used to endorse or promote products derived from
this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS
``AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT

LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED.

IN NO EVENT SHALL THE REGENTS OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

[Note that only a few files are distributed under this license.]

GNU LESSER GENERAL PUBLIC LICENSE

Version 3, 29 June 2007

Copyright (C) 2007 Free Software Foundation, Inc. <<https://fsf.org/>>

Everyone is permitted to copy and distribute verbatim copies of this license document, but changing it is not allowed.

This version of the GNU Lesser General Public License incorporates the terms and conditions of version 3 of the GNU General Public License, supplemented by the additional permissions listed below.

0. Additional Definitions.

As used herein, "this License" refers to version 3 of the GNU Lesser General Public License, and the "GNU GPL" refers to version 3 of the GNU General Public License.

"The Library" refers to a covered work governed by this License, other than an Application or a Combined Work as defined below.

An "Application" is any work that makes use of an interface provided by the Library, but which is not otherwise based on the Library.

Defining a subclass of a class defined by the Library is deemed a mode of using an interface provided by the Library.

A "Combined Work" is a work produced by combining or linking an Application with the Library. The particular version of the Library with which the Combined Work was made is also called the "Linked Version".

The "Minimal Corresponding Source" for a Combined Work means the Corresponding Source for the Combined Work, excluding any source code for portions of the Combined Work that, considered in isolation, are based on the Application, and not on the Linked Version.

The "Corresponding Application Code" for a Combined Work means the object code and/or source code for the Application, including any data and utility programs needed for reproducing the Combined Work from the Application, but excluding the System Libraries of the Combined Work.

1. Exception to Section 3 of the GNU GPL.

You may convey a covered work under sections 3 and 4 of this License without being bound by section 3 of the GNU GPL.

2. Conveying Modified Versions.

If you modify a copy of the Library, and, in your modifications, a facility refers to a function or data to be supplied by an Application that uses the facility (other than as an argument passed when the facility is invoked), then you may convey a copy of the modified version:

- a) under this License, provided that you make a good faith effort to ensure that, in the event an Application does not supply the function or data, the facility still operates, and performs whatever part of its purpose remains meaningful, or
- b) under the GNU GPL, with none of the additional permissions of this License applicable to that copy.

3. Object Code Incorporating Material from Library Header Files.

The object code form of an Application may incorporate material from a header file that is part of the Library. You may convey such object code under terms of your choice, provided that, if the incorporated material is not limited to numerical parameters, data structure layouts and accessors, or small macros, inline functions and templates (ten or fewer lines in length), you do both of the following:

- a) Give prominent notice with each copy of the object code that the Library is used in it and that the Library and its use are covered by this License.
- b) Accompany the object code with a copy of the GNU GPL and this license document.

4. Combined Works.

You may convey a Combined Work under terms of your choice that,

taken together, effectively do not restrict modification of the portions of the Library contained in the Combined Work and reverse engineering for debugging such modifications, if you also do each of the following:

a) Give prominent notice with each copy of the Combined Work that the Library is used in it and that the Library and its use are covered by this License.

b) Accompany the Combined Work with a copy of the GNU GPL and this license document.

c) For a Combined Work that displays copyright notices during execution, include the copyright notice for the Library among these notices, as well as a reference directing the user to the copies of the GNU GPL and this license document.

d) Do one of the following:

0) Convey the Minimal Corresponding Source under the terms of this License, and the Corresponding Application Code in a form suitable for, and under terms that permit, the user to recombine or relink the Application with a modified version of the Linked Version to produce a modified Combined Work, in the manner specified by section 6 of the GNU GPL for conveying Corresponding Source.

1) Use a suitable shared library mechanism for linking with the Library. A suitable mechanism is one that (a) uses at run time a copy of the Library already present on the user's computer system, and (b) will operate properly with a modified version of the Library that is interface-compatible with the Linked Version.

e) Provide Installation Information, but only if you would otherwise be required to provide such information under section 6 of the GNU GPL, and only to the extent that such information is necessary to install and execute a modified version of the Combined Work produced by recombining or relinking the Application with a modified version of the Linked Version. (If you use option 4d0, the Installation Information must accompany the Minimal Corresponding Source and Corresponding Application Code. If you use option 4d1, you must provide the Installation Information in the manner specified by section 6 of the GNU GPL for conveying Corresponding Source.)

5. Combined Libraries.

You may place library facilities that are a work based on the Library side by side in a single library together with other library facilities that are not Applications and are not covered by this License, and convey such a combined library under terms of your choice, if you do both of the following:

- a) Accompany the combined library with a copy of the same work based on the Library, uncombined with any other library facilities, conveyed under the terms of this License.
- b) Give prominent notice with the combined library that part of it is a work based on the Library, and explaining where to find the accompanying uncombined form of the same work.

6. Revised Versions of the GNU Lesser General Public License.

The Free Software Foundation may publish revised and/or new versions of the GNU Lesser General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Library as you received it specifies that a certain numbered version of the GNU Lesser General Public License "or any later version" applies to it, you have the option of following the terms and conditions either of that published version or of any later version published by the Free Software Foundation. If the Library as you received it does not specify a version number of the GNU Lesser General Public License, you may choose any version of the GNU Lesser General Public License ever published by the Free Software Foundation.

If the Library as you received it specifies that a proxy can decide whether future versions of the GNU Lesser General Public License shall apply, that proxy's public statement of acceptance of any version is permanent authorization for you to choose that version for the Library.

```
# COPYING.other          -*- org -*-  
#+TITLE: List of code with permissive licenses as used by GnuPG.  
#+STARTUP: showall
```

* DNS resolver (dirmngr/dns.c)

dns.c - Recursive, Reentrant DNS Resolver.

Copyright (c) 2008, 2009, 2010, 2012-2016 William Ahern

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

* TinySCHEME (tests/gpgscm/LICENSE.TinySCHEME)

Copyright (c) 2000, Dimitrios Souflis
All rights reserved.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.

Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.

Neither the name of Dimitrios Souflis nor the names of the contributors may be used to endorse or promote products derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS ``AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE REGENTS OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL,

EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

1.85 gpgv 2.2.4-1ubuntu1.6

1.85.1 Available under license :

Here is a list with collected copyright notices. For details see the description of each individual package. [Compiled by wk 2017-11-07]

GNUPG is

Copyright (C) 1997-2017 Werner Koch
Copyright (C) 1994-2017 Free Software Foundation, Inc.
Copyright (C) 2003-2017 g10 Code GmbH
Copyright (C) 2002 Klarlvdalens Datakonsult AB
Copyright (C) 1995-1997, 2000-2007 Ulrich Drepper <drepper@gnu.ai.mit.edu>
Copyright (C) 1994 X Consortium
Copyright (C) 1998 by The Internet Society.
Copyright (C) 1998-2004 The OpenLDAP Foundation
Copyright (C) 1998-2004 Kurt D. Zeilenga.
Copyright (C) 1998-2004 Net Boolean Incorporated.
Copyright (C) 2001-2004 IBM Corporation.
Copyright (C) 1999-2003 Howard Y.H. Chu.
Copyright (C) 1999-2003 Symas Corporation.
Copyright (C) 1998-2003 Hallvard B. Furuseth.
Copyright (C) 1992-1996 Regents of the University of Michigan.
Copyright (C) 2000 Dimitrios Souflis
Copyright (C) 2008,2009,2010,2012-2016 William Ahern

GnuPG is free software;
you can redistribute it and/or modify it
under the terms of the GNU General Public License as published by
the Free Software Foundation; either version 3 of the License, or
(at your option) any later version.

GnuPG is distributed in the hope that it will be useful, but WITHOUT
ANY WARRANTY; without even the implied warranty of MERCHANTABILITY
or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public
License for more details.

You should have received a copy of the GNU General Public License
along with this program; if not, see <<https://www.gnu.org/licenses/>>.

LIBGCRYPT is

Copyright (C) 1989,1991-2017 Free Software Foundation, Inc.
Copyright (C) 1994 X Consortium
Copyright (C) 1996 L. Peter Deutsch
Copyright (C) 1997 Werner Koch
Copyright (C) 1998 The Internet Society
Copyright (C) 1996-1999 Peter Gutmann, Paul Kendall, and Chris Wedgwood
Copyright (C) 1996-2006 Peter Gutmann, Matt Thomlinson and Blake Coverett
Copyright (C) 2003 Nikos Mavroyanopoulos
Copyright (C) 2006-2007 NTT (Nippon Telegraph and Telephone Corporation)
Copyright (C) 2012-2017 g10 Code GmbH
Copyright (C) 2012 Simon Josefsson, Niels Mller
Copyright (c) 2012 Intel Corporation
Copyright (C) 2013 Christian Grothoff
Copyright (C) 2013-2017 Jussi Kivilinna
Copyright (C) 2013-2014 Dmitry Eremin-Solenikov
Copyright (C) 2014 Stephan Mueller
Copyright (C) 2017 Bundesamt fr Sicherheit in der Informationstechnik

Libgcrypto is free software; you can redistribute it and/or modify it under the terms of the GNU Lesser General Public License as published by the Free Software Foundation; either version 2.1 of the License, or (at your option) any later version.

Libgcrypto is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU Lesser General Public License for more details.

You should have received a copy of the GNU Lesser General Public License along with this program; if not, see <<http://www.gnu.org/licenses/>>.

LIBGPG-ERROR is

Copyright (C) 2003-2004, 2010, 2013-2017 g10 Code GmbH

libpgp-error is free software; you can redistribute it and/or modify it under the terms of the GNU Lesser General Public License as published by the Free Software Foundation; either version 2.1 of the License, or (at your option) any later version.

libpgp-error is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of

MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU Lesser General Public License for more details.

You should have received a copy of the GNU Lesser General Public License along with this program; if not, see <<http://www.gnu.org/licenses/>>.

LIBASSUAN is

Copyright (C) 1992-2013 Free Software Foundation, Inc.

Copyright (C) 1994 X Consortium

Copyright (C) 2000 Werner Koch (dd9jn)

Copyright (C)

2001-2016 g10 Code GmbH

Copyright (C) 2004 Simon Josefsson

Assuan is free software; you can redistribute it and/or modify it under the terms of the GNU Lesser General Public License as published by the Free Software Foundation; either version 2.1 of the License, or (at your option) any later version.

Assuan is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU Lesser General Public License for more details.

You should have received a copy of the GNU Lesser General Public License along with this program; if not, see <<http://www.gnu.org/licenses/>>.

LIBKSBA is

Copyright (C) 2001, 2002, 2003, 2004, 2005, 2006, 2010, 2011

2012, 2013, 2014, 2015 g10 Code GmbH

Copyright (C) 2001, 2002, 2003, 2007 Free Software Foundation, Inc.

Copyright (C) 2000, 2001 Fabio Fiorina

The library and the header files are distributed under the following terms (LGPLv3+/GPLv2+):

KSBA is free software; you can redistribute it and/or modify it under the terms of either

- the GNU Lesser General Public License as published by the Free Software Foundation; either version 3 of the License, or (at your option) any later version.

or

- the GNU General Public License as published by the Free Software Foundation; either version 2 of the License, or (at your option) any later version.

or both in parallel, as here.

KSBA is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details.

The other parts (e.g. manual, build system, tests) are distributed under the following terms (GPLv3):

KSBA is free software; you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation; either version 3 of the License, or (at your option) any later version.

KSBA is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details.

NPTH is

Copyright (C) 2011, 2012, 2014, 2015, 2017 g10 Code GmbH

nPth is free software; you can redistribute it and/or modify it under the terms of the GNU Lesser General Public License as published by the Free Software Foundation; either version 2.1 of the License, or (at your option) any later version.

nPth is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU Lesser General Public License for more details.

You should have received a copy of the GNU Lesser General Public License along with this program;
if not, see <<https://www.gnu.org/licenses/>>.

NTBTLS is

Copyright (C) 2006-2014 Brainspark B.V.
Copyright (C) 2014-2017 g10 Code GmbH

NTBTLS is free software; you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation; either version 3 of the License, or (at your option) any later version.

NTBTLS is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details.

You should have received a copy of the GNU General Public License along with this program; if not, see <<http://www.gnu.org/licenses/>>.

PINENTRY is

Copyright (C) 1999 Robert Bihlmeyer <robbe@orcus.priv.at>
Copyright (C) 2001-2004, 2007-2008, 2010, 2015-2016 g10 Code GmbH
Copyright (C) 2002, 2008 Klarlvdalens Datakonsult AB (KDAB)
Copyright (C) 2004 by Albrecht
Dre <albrecht.dress@arcor.de>
Copyright 2007 Ingo Klöcker
Copyright (C) 2014 Serge Voilokov
Copyright (C) 2015 Daiki Ueno
Copyright (C) 2015 Daniel Kahn Gillmor <dkg@fifthhorseman.net>
Copyright 2016 Intevation GmbH

PINENTRY is free software; you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation; either version 2 of the License, or (at your option) any later version.

PINENTRY is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details.

You should have received a copy of the GNU General Public License along with this program; if not, see <<https://www.gnu.org/licenses/>>.

GPGME is

Copyright (C) 1991-2013 Free Software Foundation, Inc.

Copyright (C) 2000-2001 Werner Koch
Copyright (C) 2001-2017 g10 Code GmbH

Copyright (C) 2002 Klarlvdalens Datakonsult AB
Copyright (C) 2004-2008 Igor Belyi
Copyright (C) 2002 John Goerzen
Copyright (C) 2014, 2015 Martin Albrecht
Copyright (C) 2015 Ben McGinnes
Copyright (C) 2015-2016 Bundesamt fr Sicherheit in der Informationstechnik
Copyright (C) 2016 Intevation GmbH

GPGME is free software; you can redistribute it and/or modify it under the terms of the GNU Lesser General Public License as published by the Free Software Foundation; either version 2.1 of the License, or (at your option) any later version.

GPGME is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU Lesser General Public License for more details.

You should have received a copy of the GNU Lesser General Public License along with this program; if not, see <<http://www.gnu.org/licenses/>>.

NSIS is

Copyright 1999-2009 Nullsoft and Contributors
Copyright 2002-2008 Amir Szekely
Copyright 2003 Ramon

This license applies to everything in the NSIS package, except where otherwise noted.

This software is provided 'as-is', without any express or implied warranty. In no event will the authors be held liable for any damages arising from the use of this software.

Permission is granted to anyone to use this software for any purpose, including commercial applications, and to alter it and redistribute it freely, subject to the following restrictions:

1. The origin of this software must not be misrepresented; you must not claim that you wrote the original software. If you use this software in a product, an acknowledgment in the product documentation would be appreciated but is not required.
2. Altered source versions must be plainly marked as such, and must

not be misrepresented as being the original software.

3. This notice may not be removed or altered from any source distribution.

The user interface used with the installer is

Copyright 2002-2009 Joost Verburg

[It is distributed along with NSIS and the same conditions as stated above apply]

TinySCHEME is part of the GnuPG package and is

Copyright (c) 2000, Dimitrios Souflis
All rights reserved.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.

Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.

Neither the name of Dimitrios Souflis nor the names of the contributors may be used to endorse or promote products derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED
BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS
``AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT
LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR
A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE REGENTS OR
CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL,
EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO,
PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR
PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF
LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING
NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

LIBDNS is part of the GnuPG package and is

Copyright (c) 2008, 2009, 2010, 2012-2016 William Ahern

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"),
to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

ZLIB is

(C) 1995-2013 Jean-loup Gailly and Mark Adler

This software is provided 'as-is', without any express or implied warranty. In no event will the authors be held liable for any damages arising from the use of this software.

Permission is granted to anyone to use this software for any purpose, including commercial applications, and to alter it and redistribute it freely, subject to the following restrictions:

1. The origin of this software must not be misrepresented; you must not claim that you wrote the original software. If you use this software in a product, an acknowledgment in the product documentation would be appreciated but is not required.
2. Altered source versions must be plainly marked as such, and must not be misrepresented as being the original software.
3. This notice may not be removed or altered from any source distribution.

Jean-loup Gailly Mark Adler
jloup@gzip.org madler@alumni.caltech.edu

BZIP2 is

This program, "bzip2", the associated library "libbzip2", and all documentation, are copyright (C) 1996-2010 Julian R Seward. All rights reserved.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

1. Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.
2. The origin of this software must not be misrepresented; you must not claim that you wrote the original software. If you use this software in a product, an acknowledgment in the product documentation would be appreciated but is not required.
3. Altered source versions must be plainly marked as such, and must not be misrepresented as being the original software.
4. The name of the author may not be used to endorse or promote products derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE AUTHOR ``AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE AUTHOR BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

SQLITE has

been put into the public-domain by its author D. Richard Hipp:
The author disclaims copyright to this source code. In place of a legal notice, here is a blessing:

May you do good and not evil.

May you find forgiveness for yourself and forgive others.
May you share freely, never taking more than you give.
[Note that only a few files are distributed under this license.]

Creative Commons Legal Code

CC0 1.0 Universal

CREATIVE COMMONS CORPORATION IS NOT A LAW FIRM AND DOES NOT PROVIDE LEGAL SERVICES. DISTRIBUTION OF THIS DOCUMENT DOES NOT CREATE AN ATTORNEY-CLIENT RELATIONSHIP. CREATIVE COMMONS PROVIDES THIS INFORMATION ON AN "AS-IS" BASIS. CREATIVE COMMONS MAKES NO WARRANTIES REGARDING THE USE OF THIS DOCUMENT OR THE INFORMATION OR WORKS PROVIDED HEREUNDER, AND DISCLAIMS LIABILITY FOR DAMAGES RESULTING FROM THE USE OF THIS DOCUMENT OR THE INFORMATION OR WORKS PROVIDED HEREUNDER.

Statement of Purpose

The laws of most jurisdictions throughout the world automatically confer exclusive Copyright and Related Rights (defined below) upon the creator and subsequent owner(s) (each and all, an "owner") of an original work of authorship and/or a database (each, a "Work").

Certain owners wish to permanently relinquish those rights to a Work for the purpose of contributing to a commons of creative, cultural and scientific works ("Commons") that the public can reliably and without fear of later claims of infringement build upon, modify, incorporate in other works, reuse and redistribute as freely as possible in any form whatsoever and for any purposes, including without limitation commercial purposes. These owners may contribute to the Commons to promote the ideal of a free culture and the further production of creative, cultural and scientific works, or to gain reputation or greater distribution for their Work in part through the use and efforts of others.

For these and/or other purposes and motivations, and without any expectation of additional consideration or compensation, the person associating CC0 with a Work (the "Affirmer"), to the extent that he or she is an owner of Copyright and Related Rights in the Work, voluntarily elects to apply CC0 to the Work and publicly distribute the Work under its terms, with knowledge of his or her Copyright and Related Rights in the Work and the meaning and intended legal effect of CC0 on those rights.

1. Copyright and Related Rights. A Work made available under CC0 may be protected by copyright and related or neighboring rights ("Copyright and Related Rights"). Copyright and Related Rights include, but are not

limited to, the following:

- i. the right to reproduce, adapt, distribute, perform, display, communicate, and translate a Work;
- ii. moral rights retained by the original author(s) and/or performer(s);
- iii. publicity and privacy rights pertaining to a person's image or likeness depicted in a Work;
- iv. rights protecting against unfair competition in regards to a Work, subject to the limitations in paragraph 4(a), below;
- v. rights protecting the extraction, dissemination, use and reuse of data in a Work;
- vi. database rights (such as those arising under Directive 96/9/EC of the European Parliament and of the Council of 11 March 1996 on the legal protection of databases, and under any national implementation thereof, including any amended or successor version of such directive); and
- vii. other similar, equivalent or corresponding rights throughout the world based on applicable law or treaty, and any national implementations thereof.

2. Waiver. To the greatest extent permitted by, but not in contravention of, applicable law, Affirmer hereby overtly, fully, permanently, irrevocably and unconditionally waives, abandons, and surrenders all of Affirmer's Copyright and Related Rights and associated claims and causes of action, whether now known or unknown (including existing as well as future claims and causes of action), in the Work (i) in all territories worldwide, (ii) for the maximum duration provided by applicable law or treaty (including future time extensions), (iii) in any current or future medium and for any number of copies, and (iv) for any purpose whatsoever, including without limitation commercial, advertising or promotional purposes (the "Waiver"). Affirmer makes the Waiver for the benefit of each member of the public at large and to the detriment of Affirmer's heirs and successors, fully intending that such Waiver shall not be subject to revocation, rescission, cancellation, termination, or any other legal or equitable action to disrupt the quiet enjoyment of the Work by the public as contemplated by Affirmer's express Statement of Purpose.

3. Public License Fallback. Should any part of the Waiver for any reason be judged legally invalid or ineffective under applicable law, then the Waiver shall be preserved to the maximum extent permitted taking into account Affirmer's express Statement of Purpose. In addition, to the extent the Waiver is so judged Affirmer hereby grants to each affected person a royalty-free, non transferable, non sublicensable, non exclusive, irrevocable and unconditional license to exercise Affirmer's Copyright and Related Rights in the Work (i) in all territories

worldwide, (ii) for the maximum duration provided by applicable law or treaty (including future time extensions), (iii) in any current or future medium and for any number of copies, and (iv) for any purpose whatsoever, including without limitation commercial, advertising or promotional purposes (the "License"). The License shall be deemed effective as of the date CC0 was applied by Affirmer to the Work. Should any part of the License for any reason be judged legally invalid or ineffective under applicable law, such partial invalidity or ineffectiveness shall not invalidate the remainder of the License, and in such case Affirmer hereby affirms that he or she will not (i) exercise any of his or her remaining Copyright and Related Rights in the Work or (ii) assert any associated claims and causes of action with respect to the Work, in either case contrary to Affirmer's express Statement of Purpose.

4. Limitations and Disclaimers.

- a. No trademark or patent rights held by Affirmer are waived, abandoned, surrendered, licensed or otherwise affected by this document.
- b. Affirmer offers the Work as-is and makes no representations or warranties of any kind concerning the Work, express, implied, statutory or otherwise, including without limitation warranties of title, merchantability, fitness for a particular purpose, non infringement, or the absence of latent or other defects, accuracy, or the present or absence of errors, whether or not discoverable, all to the greatest extent permissible under applicable law.
- c. Affirmer disclaims responsibility for clearing rights of other persons that may apply to the Work or any use thereof, including without limitation any person's Copyright and Related Rights in the Work. Further, Affirmer disclaims responsibility for obtaining any necessary consents, permissions or other rights required for any use of the Work.
- d. Affirmer understands and acknowledges that Creative Commons is not a party to this document and has no duty or obligation with respect to this CC0 or use of the Work.

GNU GENERAL PUBLIC LICENSE

Version 3, 29 June 2007

Copyright (C) 2007 Free Software Foundation, Inc. <<https://fsf.org/>>
Everyone is permitted to copy and distribute verbatim copies of this license document, but changing it is not allowed.

Preamble

The GNU General Public License is a free, copyleft license for

software and other kinds of works.

The licenses for most software and other practical works are designed to take away your freedom to share and change the works. By contrast, the GNU General Public License is intended to guarantee your freedom to share and change all versions of a program--to make sure it remains free software for all its users. We, the Free Software Foundation, use the GNU General Public License for most of our software; it applies also to any other work released this way by its authors. You can apply it to your programs, too.

When we speak of free software, we are referring to freedom, not price. Our General Public Licenses are designed to make sure that you have the freedom to distribute copies of free software (and charge for them if you wish), that you receive source code or can get it if you want it, that you can change the software or use pieces of it in new free programs, and that you know you can do these things.

To protect your rights, we need to prevent others from denying you these rights or asking you to surrender the rights. Therefore, you have certain responsibilities if you distribute copies of the software, or if you modify it: responsibilities to respect the freedom of others.

For example, if you distribute copies of such a program, whether gratis or for a fee, you must pass on to the recipients the same freedoms that you received. You must make sure that they, too, receive or can get the source code. And you must show them these terms so they know their rights.

Developers that use the GNU GPL protect your rights with two steps: (1) assert copyright on the software, and (2) offer you this License giving you legal permission to copy, distribute and/or modify it.

For the developers' and authors' protection, the GPL clearly explains that there is no warranty for this free software. For both users' and authors' sake, the GPL requires that modified versions be marked as changed, so that their problems will not be attributed erroneously to authors of previous versions.

Some devices are designed to deny users access to install or run modified versions of the software inside them, although the manufacturer can do so. This is fundamentally incompatible with the aim of protecting users' freedom to change the software. The systematic pattern of such abuse occurs in the area of products for individuals to use, which is precisely where it is most unacceptable. Therefore, we have designed this version of the GPL to prohibit the practice for those

products. If such problems arise substantially in other domains, we stand ready to extend this provision to those domains in future versions of the GPL, as needed to protect the freedom of users.

Finally, every program is threatened constantly by software patents. States should not allow patents to restrict development and use of software on general-purpose computers, but in those that do, we wish to avoid the special danger that patents applied to a free program could make it effectively proprietary. To prevent this, the GPL assures that patents cannot be used to render the program non-free.

The precise terms and conditions for copying, distribution and modification follow.

TERMS AND CONDITIONS

0. Definitions.

"This License" refers to version 3 of the GNU General Public License.

"Copyright" also means copyright-like laws that apply to other kinds of works, such as semiconductor masks.

"The Program" refers to any copyrightable work licensed under this License. Each licensee is addressed as "you". "Licensees" and "recipients" may be individuals or organizations.

To

"modify" a work means to copy from or adapt all or part of the work in a fashion requiring copyright permission, other than the making of an exact copy. The resulting work is called a "modified version" of the earlier work or a work "based on" the earlier work.

A "covered work" means either the unmodified Program or a work based on the Program.

To "propagate" a work means to do anything with it that, without permission, would make you directly or secondarily liable for infringement under applicable copyright law, except executing it on a computer or modifying a private copy. Propagation includes copying, distribution (with or without modification), making available to the public, and in some countries other activities as well.

To "convey" a work means any kind of propagation that enables other parties to make or receive copies. Mere interaction with a user through a computer network, with no transfer of a copy, is not conveying.

An interactive user interface displays "Appropriate Legal Notices"

to the extent that it includes a convenient and prominently visible feature that (1) displays an appropriate copyright notice, and (2) tells the user that there is no warranty for the work (except to the extent that warranties are provided), that licensees may convey the work under this License, and how to view a copy of this License. If the interface presents a list of user commands or options, such as a menu, a prominent item in the list meets this criterion.

1. Source Code.

The "source code" for a work means the preferred form of the work for making modifications to it. "Object code" means any non-source form of a work.

A "Standard Interface" means an interface that either is an official standard defined by a recognized standards body, or, in the case of interfaces specified for a particular programming language, one that is widely used among developers working in that language.

The "System Libraries" of an executable work include anything, other than the work as a whole, that (a) is included in the normal form of packaging a Major Component, but which is not part of that Major Component, and (b) serves only to enable use of the work with that Major Component, or to implement a Standard Interface for which an implementation is available to the public in source code form. A "Major Component", in this context, means a major essential component (kernel, window system, and so on) of the specific operating system (if any) on which the executable work runs, or a compiler used to produce the work, or an object code interpreter used to run it.

The "Corresponding Source" for a work in object code form means all the source code needed to generate, install, and (for an executable work) run the object code and to modify the work, including scripts to control those activities. However, it does not include the work's System Libraries, or general-purpose tools or generally available free programs which are used unmodified in performing those activities but which are not part of the work. For example, Corresponding Source includes interface definition files associated with source files for the work, and the source code for shared libraries and dynamically linked subprograms that the work is specifically designed to require, such as by intimate data communication or control flow between those subprograms and other parts of the work.

The Corresponding Source need not include anything that users

can regenerate automatically from other parts of the Corresponding Source.

The Corresponding Source for a work in source code form is that same work.

2. Basic Permissions.

All rights granted under this License are granted for the term of copyright on the Program, and are irrevocable provided the stated conditions are met. This License explicitly affirms your unlimited permission to run the unmodified Program. The output from running a covered work is covered by this License only if the output, given its content, constitutes a covered work. This License acknowledges your rights of fair use or other equivalent, as provided by copyright law.

You may make, run and propagate covered works that you do not convey, without conditions so long as your license otherwise remains in force. You may convey covered works to others for the sole purpose of having them make modifications exclusively for you, or provide you with facilities for running those works, provided that you comply with the terms of this License in conveying all material for which you do not control copyright. Those thus making or running the covered works for you must do so exclusively on your behalf, under your direction and control, on terms that prohibit them from making any copies of your copyrighted material outside their relationship with you.

Conveying under any other circumstances is permitted solely under the conditions stated below. Sublicensing is not allowed; section 10 makes it unnecessary.

3. Protecting Users'

Legal Rights From Anti-Circumvention Law.

No covered work shall be deemed part of an effective technological measure under any applicable law fulfilling obligations under article 11 of the WIPO copyright treaty adopted on 20 December 1996, or similar laws prohibiting or restricting circumvention of such measures.

When you convey a covered work, you waive any legal power to forbid circumvention of technological measures to the extent such circumvention is effected by exercising rights under this License with respect to the covered work, and you disclaim any intention to limit operation or modification of the work as a means of enforcing, against the work's users, your or third parties' legal rights to forbid circumvention of technological measures.

4. Conveying Verbatim Copies.

You may convey verbatim copies of the Program's source code as you receive it, in any medium, provided that you conspicuously and appropriately publish on each copy an appropriate copyright notice; keep intact all notices stating that this License and any non-permissive terms added in accord with section 7 apply to the code; keep intact all notices of the absence of any warranty; and give all recipients a copy of this License along with the Program.

You may charge any price or no price for each copy that you convey, and you may offer support or warranty protection for a fee.

5. Conveying Modified Source Versions.

You may convey a work based on the Program, or the modifications to produce it from the Program, in the form of source code under the terms of section 4, provided that you also meet all of these conditions:

a) The work must carry prominent notices stating that you modified it, and giving a relevant date.

b) The work must carry prominent notices stating that it is released under this License and any conditions added under section 7. This requirement modifies the requirement in section 4 to "keep intact all notices".

c) You must license the entire work, as a whole, under this License to anyone who comes into possession of a copy. This License will therefore apply, along with any applicable section 7 additional terms, to the whole of the work, and all its parts, regardless of how they are packaged. This License gives no permission to license the work in any other way, but it does not invalidate such permission if you have separately received it.

d) If the work has interactive user interfaces, each must display Appropriate Legal Notices; however, if the Program has interactive interfaces that do not display Appropriate Legal Notices, your work need not make them do so.

A compilation of a covered work with other separate and independent works, which are not by their nature extensions of the covered work, and which are not combined with it such as to form a larger program, in or on a volume of a storage or distribution medium, is called an "aggregate" if the compilation and

its resulting copyright are not used to limit the access or legal rights of the compilation's users beyond what the individual works permit. Inclusion of a covered work in an aggregate does not cause this License to apply to the other parts of the aggregate.

6. Conveying Non-Source Forms.

You may convey a covered work in object code form under the terms of sections 4 and 5, provided that you also convey the machine-readable Corresponding Source under the terms of this License, in one of these ways:

a) Convey the object code in, or embodied in, a physical product (including a physical distribution medium), accompanied by the Corresponding Source fixed on a durable physical medium customarily used for software interchange.

b) Convey the object code in, or embodied in, a physical product (including a physical distribution medium), accompanied by a written offer, valid for at least three years and valid for as long as you offer spare parts or customer

support for that product

model, to give anyone who possesses the object code either (1) a copy of the Corresponding Source for all the software in the product that is covered by this License, on a durable physical medium customarily used for software interchange, for a price no more than your reasonable cost of physically performing this conveying of source, or (2) access to copy the Corresponding Source from a network server at no charge.

c) Convey individual copies of the object code with a copy of the written offer to provide the Corresponding Source. This alternative is allowed only occasionally and noncommercially, and only if you received the object code with such an offer, in accord with subsection 6b.

d) Convey the object code by offering access from a designated place (gratis or for a charge), and offer equivalent access to the Corresponding Source in the same way through the same place at no further charge.

You need not require recipients to copy the

Corresponding Source along with the object code. If the place to copy the object code is a network server, the Corresponding Source may be on a different server (operated by you or a third party) that supports equivalent copying facilities, provided you maintain clear directions next to the object code saying where to find the Corresponding Source. Regardless of what server hosts the

Corresponding Source, you remain obligated to ensure that it is available for as long as needed to satisfy these requirements.

e) Convey the object code using peer-to-peer transmission, provided you inform other peers where the object code and Corresponding Source of the work are being offered to the general public at no charge under subsection 6d.

A separable portion of the object code, whose source code is excluded from the Corresponding Source as a System Library, need not be included in conveying the object code work.

A "User Product" is either (1) a "consumer product", which means any tangible personal property which is normally used for personal, family, or household purposes, or (2) anything designed or sold for incorporation into a dwelling. In determining whether a product is a consumer product, doubtful cases shall be resolved in favor of coverage. For a particular product received by a particular user, "normally used" refers to a typical or common use of that class of product, regardless of the status of the particular user or of the way in which the particular user actually uses, or expects or is expected to use, the product. A product is a consumer product regardless of whether the product has substantial commercial, industrial or non-consumer uses, unless such uses represent the only significant mode of use of the product.

"Installation Information" for a User Product means any methods, procedures, authorization keys, or other information required to install and execute

modified versions of a covered work in that User Product from a modified version of its Corresponding Source. The information must suffice to ensure that the continued functioning of the modified object code is in no case prevented or interfered with solely because modification has been made.

If you convey an object code work under this section in, or with, or specifically for use in, a User Product, and the conveying occurs as part of a transaction in which the right of possession and use of the User Product is transferred to the recipient in perpetuity or for a fixed term (regardless of how the transaction is characterized), the Corresponding Source conveyed under this section must be accompanied by the Installation Information. But this requirement does not apply if neither you nor any third party retains the ability to install modified object code on the User Product (for example, the work has been installed in ROM).

The requirement to provide Installation Information

does not include a requirement to continue to provide support service, warranty, or updates for a work that has been modified or installed by the recipient, or for the User Product in which it has been modified or installed. Access to a network may be denied when the modification itself materially and adversely affects the operation of the network or violates the rules and protocols for communication across the network.

Corresponding Source conveyed, and Installation Information provided, in accord with this section must be in a format that is publicly documented (and with an implementation available to the public in source code form), and must require no special password or key for unpacking, reading or copying.

7. Additional Terms.

"Additional permissions" are terms that supplement the terms of this License by making exceptions from one or more of its conditions. Additional permissions that are applicable to the entire Program shall be treated as though they were included in this License, to the extent that they are valid under applicable law. If additional permissions apply only to part of the Program, that part may be used separately under those permissions, but the entire Program remains governed by this License without regard to the additional permissions.

When you convey a copy of a covered work, you may at your option remove any additional permissions from that copy, or from any part of it. (Additional permissions may be written to require their own removal in certain cases when you modify the work.) You may place additional permissions on material, added by you to a covered work, for which you have or can give appropriate copyright permission.

Notwithstanding any other provision of this License, for material you add to a covered work, you may (if authorized by the copyright holders of that material) supplement the terms of this License with terms:

- a) Disclaiming warranty or limiting liability differently from the terms of sections 15 and 16 of this License; or
- b) Requiring preservation of specified reasonable legal notices or author attributions in that material or in the Appropriate Legal Notices displayed by works containing it; or
- c) Prohibiting misrepresentation of the origin of that material, or requiring that modified versions of such material be marked in reasonable ways as different from the original version; or

- d) Limiting the use for publicity purposes of names of licensors or authors of the material; or
- e) Declining to grant rights under trademark law for use of some trade names, trademarks, or service marks; or
- f) Requiring indemnification of licensors and authors of that material by anyone who conveys the material (or modified versions of it) with contractual assumptions of liability to the recipient, for any liability that these contractual assumptions directly impose on those licensors and authors.

All other non-permissive additional terms are considered "further restrictions" within the meaning of section 10. If the Program as you received it, or any part of it, contains a notice stating that it is governed by this License along with a term that is a further restriction, you may remove that term. If a license document contains a further restriction but permits relicensing or conveying under this License, you may add to a covered work material governed by the terms of that license document, provided that the further restriction does not survive such relicensing or conveying.

If you add terms to a covered work in accord with this section, you must place, in the relevant source files, a statement of the additional terms that apply to those files, or a notice indicating where to find the applicable terms.

Additional terms, permissive or non-permissive, may be stated in the form of a separately written license, or stated as exceptions; the above requirements apply either way.

8. Termination.

You may not propagate or modify a covered work except as expressly provided under this License. Any attempt otherwise to propagate or modify it is void, and will automatically terminate your rights under this License (including any patent licenses granted under the third paragraph of section 11).

However, if you cease all violation of this License, then your license from a particular copyright holder is reinstated (a) provisionally, unless and until the copyright holder explicitly and finally terminates your license, and (b) permanently, if the copyright holder fails to notify you of the violation by some reasonable means prior to 60 days after the cessation.

Moreover, your license from a particular copyright holder is reinstated permanently if the copyright holder notifies you of the violation by some reasonable means, this is the first time you have received notice of violation of this License (for any work) from that copyright holder, and you cure the violation prior to 30 days after your receipt of the notice.

Termination of your rights under this section does not terminate the licenses of parties who have received copies or rights from you under this License. If your rights have been terminated and not permanently reinstated, you do not qualify to receive new licenses for the same material under section 10.

9. Acceptance Not Required for Having Copies.

You are not required to accept this License in order to receive or run a copy of the Program. Ancillary propagation of a covered work occurring solely as a consequence of using peer-to-peer transmission to receive a copy likewise does not require acceptance. However, nothing other than this License grants you permission to propagate or modify any covered work. These actions infringe copyright if you do not accept this License. Therefore, by modifying or propagating a covered work, you indicate your acceptance of this License to do so.

10. Automatic Licensing of Downstream Recipients.

Each time you convey a covered work, the recipient automatically receives a license from the original licensors, to run, modify and propagate that work, subject to this License. You are not responsible for enforcing compliance by third parties with this License.

An "entity transaction" is a transaction transferring control of an organization, or substantially all assets of one, or subdividing an organization, or merging organizations. If propagation of a covered work results from an entity transaction, each party to that transaction who receives a copy of the work also receives whatever licenses to the work the party's predecessor in interest had or could give under the previous paragraph, plus a right to possession of the Corresponding Source of the work from the predecessor in interest, if the predecessor has it or can get it with reasonable efforts.

You may not impose any further restrictions on the exercise of the rights granted or affirmed under this License. For example, you may not

impose a license fee, royalty, or other charge for exercise of rights granted under this License, and you may not initiate litigation (including a cross-claim or counterclaim in a lawsuit) alleging that any patent claim is infringed by making, using, selling, offering for sale, or importing the Program or any portion of it.

11. Patents.

A "contributor" is a copyright holder who authorizes use under this License of the Program or a work on which the Program is based. The work thus licensed is called the contributor's "contributor version".

A contributor's "essential patent claims" are all patent claims owned or controlled by the contributor, whether already acquired or hereafter acquired, that would be infringed by some manner, permitted by this License, of making, using, or selling its contributor version, but do not include claims that would be infringed only as a consequence of further modification of the contributor version. For purposes of this definition, "control" includes the right to grant patent sublicenses in a manner consistent with the requirements of this License.

Each contributor grants you a non-exclusive, worldwide, royalty-free patent license under the contributor's essential patent claims, to make, use, sell, offer for sale, import and otherwise run, modify and propagate the contents of its contributor version.

In the following three paragraphs, a "patent license" is any express agreement or commitment, however denominated, not to enforce a patent (such as an express permission to practice a patent or covenant not to sue for patent infringement). To "grant" such a patent license to a party means to make such an agreement or commitment not to enforce a patent against the party.

If you convey a covered work, knowingly relying on a patent license, and the Corresponding Source of the work is not available for anyone to copy, free of charge and under the terms of this License, through a publicly available network server or other readily accessible means, then you must either (1) cause the Corresponding Source to be so available, or (2) arrange to deprive yourself of the benefit of the patent license for this particular work, or (3) arrange, in a manner consistent with the requirements of this License, to extend the patent license to downstream recipients. "Knowingly relying" means you have actual knowledge that, but for the patent license, your conveying the covered work in a country, or your recipient's use of the covered work in a country, would infringe one or more identifiable patents in that

country that you have reason to believe are valid.

If, pursuant to or in connection with a single transaction or arrangement, you convey, or propagate by procuring conveyance of, a covered work, and grant a patent license to some of the parties receiving the covered work authorizing them to use, propagate, modify or convey a specific copy of the covered work, then the patent license you grant is automatically extended to all recipients of the covered work and works based on it.

A patent license is "discriminatory" if it does not include within the scope of its coverage, prohibits the exercise of, or is conditioned on the non-exercise of one or more of the rights that are specifically granted under this License. You may not convey a covered work if you are a party to an arrangement with a third party that is in the business of distributing software, under which you make payment to the third party based on the extent of your activity of conveying the work, and under which the third party grants, to any of the parties who would receive the covered work from you, a discriminatory patent license (a) in connection with copies of the covered work conveyed by you (or copies made from those copies), or (b) primarily for and in connection with specific products or compilations that contain the covered work, unless you entered into that arrangement, or that patent license was granted, prior to 28 March 2007.

Nothing in this License shall be construed as excluding or limiting any implied license or other defenses to infringement that may otherwise be available to you under applicable patent law.

12. No Surrender of Others' Freedom.

If conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot convey a covered work so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not convey it at all. For example, if you agree to terms that obligate you to collect a royalty for further conveying from those to whom you convey the Program, the only way you could satisfy both those terms and this License would be to refrain entirely from conveying the Program.

13. Use with the GNU Affero General Public License.

Notwithstanding any other provision of this License, you have permission to link or combine any covered work with a work licensed

under version 3 of the GNU Affero General Public License into a single combined work, and to convey the resulting work. The terms of this License will continue to apply to the part which is the covered work, but the special requirements of the GNU Affero General Public License, section 13, concerning interaction through a network will apply to the combination as such.

14. Revised Versions of this License.

The Free Software Foundation may publish revised and/or new versions of the GNU General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Program specifies that a certain numbered version of the GNU General Public License "or any later version" applies to it, you have the option of following the terms and conditions either of that numbered version or of any later version published by the Free Software Foundation. If the Program does not specify a version number of the GNU General Public License, you may choose any version ever published by the Free Software Foundation.

If the Program specifies that a proxy can decide which future versions of the GNU General Public License can be used, that proxy's public statement of acceptance of a version permanently authorizes you to choose that version for the Program.

Later license versions may give you additional or different permissions. However, no additional obligations are imposed on any author or copyright holder as a result of your choosing to follow a later version.

15. Disclaimer of Warranty.

THERE IS NO WARRANTY FOR THE PROGRAM, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE PROGRAM "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE PROGRAM IS WITH YOU. SHOULD THE PROGRAM PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

16. Limitation of Liability.

IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MODIFIES AND/OR CONVEYS THE PROGRAM AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE PROGRAM (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE PROGRAM TO OPERATE WITH ANY OTHER PROGRAMS), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

17. Interpretation of Sections 15 and 16.

If the disclaimer of warranty and limitation of liability provided above cannot be given local legal effect according to their terms, reviewing courts shall apply local law that most closely approximates an absolute waiver of all civil liability in connection with the Program, unless a warranty or assumption of liability accompanies a copy of the Program in return for a fee.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Programs

If you develop a new program, and you want it to be of the greatest possible use to the public, the best way to achieve this is to make it free software which everyone can redistribute and change under these terms.

To do so, attach the following notices to the program. It is safest to attach them to the start of each source file to most effectively state the exclusion of warranty; and each file should have at least the "copyright" line and a pointer to where the full notice is found.

<one line to give the program's name and a brief idea of what it does.>

Copyright (C) <year> <name of author>

This program is free software: you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation, either version 3 of the License, or (at your option) any later version.

This program is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details.

You should have received a copy of the GNU General Public License

along with this program. If not, see <https://www.gnu.org/licenses/>.

Also add information on how to contact you by electronic and paper mail.

If the program does terminal interaction, make it output a short notice like this when it starts in an interactive mode:

```
<program> Copyright (C) <year> <name of author>
This program comes with ABSOLUTELY
NO WARRANTY; for details type `show w'.
This is free software, and you are welcome to redistribute it
under certain conditions; type `show c' for details.
```

The hypothetical commands `show w' and `show c' should show the appropriate parts of the General Public License. Of course, your program's commands might be different; for a GUI interface, you would use an "about box".

You should also get your employer (if you work as a programmer) or school, if any, to sign a "copyright disclaimer" for the program, if necessary. For more information on this, and how to apply and follow the GNU GPL, see <https://www.gnu.org/licenses/>.

The GNU General Public License does not permit incorporating your program into proprietary programs. If your program is a subroutine library, you may consider it more useful to permit linking proprietary applications with the library. If this is what you want to do, use the GNU Lesser General Public License instead of this License. But first, please read <https://www.gnu.org/philosophy/why-not-lgpl.html>.

GNU GENERAL PUBLIC LICENSE
Version 2, June 1991

Copyright (C) 1989, 1991 Free Software Foundation, Inc.,
51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA
Everyone is permitted to copy and distribute verbatim copies
of this license document, but changing it is not allowed.

Preamble

The licenses for most software are designed to take away your freedom to share and change it. By contrast, the GNU General Public License is intended to guarantee your freedom to share and change free software--to make sure the software is free for all its users. This General Public License applies to most of the Free Software Foundation's software and to any other program whose authors commit to using it. (Some other Free Software Foundation software is covered by the GNU Lesser General Public License instead.) You can apply it to your programs, too.

When we speak of free software, we are referring to freedom, not price.

Our General Public Licenses are designed to make sure that you have the freedom to distribute copies of free software (and charge for this service if you wish), that you receive source code or can get it if you want it, that you can change the software or use pieces of it in new free programs; and that you know you can do these things.

To protect your rights, we need to make restrictions that forbid anyone to deny you these rights or to ask you to surrender the rights. These restrictions translate to certain responsibilities for you if you distribute copies of the software, or if you modify it.

For example, if you distribute copies of such a program, whether gratis or for a fee, you must give the recipients all the rights that you have. You must make sure that they, too, receive or can get the source code. And you must show them these terms so they know their rights.

We protect your rights with two steps: (1) copyright the software, and (2) offer you this license which gives you legal permission to copy, distribute and/or modify the software.

Also, for each author's protection and ours, we want to make certain that everyone understands that there is no warranty for this free software. If the software is modified by someone else and passed on, we want its recipients to know that what they have is not the original, so that any problems introduced by others will not reflect on the original authors' reputations.

Finally, any free program is threatened constantly by software patents. We wish to avoid the danger that redistributors of a free program will individually obtain patent licenses, in effect making the program proprietary. To prevent this, we have made it clear that any patent must be licensed for everyone's free use or not licensed at all.

The precise terms and conditions for copying, distribution and modification follow.

GNU GENERAL PUBLIC LICENSE TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

0. This License applies to any program or other work which contains a notice placed by the copyright holder saying it may be distributed under the terms of this General Public License. The "Program", below, refers to any such program or work, and a "work based on the Program"

means either the Program or any derivative work under copyright law: that is to say, a work containing the Program or a portion of it, either verbatim or with modifications and/or translated into another language. (Hereinafter, translation is included without limitation in the term "modification".) Each licensee is addressed as "you".

Activities other than copying, distribution and modification are not covered by this License; they are outside its scope. The act of running the Program is not restricted, and the output from the Program is covered only if its contents constitute a work based on the Program (independent of having been made by running the Program). Whether that is true depends on what the Program does.

1. You may copy and distribute verbatim copies of the Program's source code as you receive it, in any medium, provided that you conspicuously and appropriately publish on each copy an appropriate copyright notice and disclaimer of warranty; keep intact all the notices that refer to this License and to the absence of any warranty; and give any other recipients of the Program a copy of this License along with the Program.

You may charge a fee for the physical act of transferring a copy, and you may at your option offer warranty protection in exchange for a fee.

2. You may modify your copy or copies of the Program or any portion of it, thus forming a work based on the Program, and copy and distribute such modifications or work under the terms of Section 1 above, provided that you also meet all of these conditions:

a) You must cause the modified files to carry prominent notices stating that you changed the files and the date of any change.

b) You must cause any work that you distribute or publish, that in whole or in part contains or is derived from the Program or any part thereof, to be licensed as a whole at no charge to all third parties under the terms of this License.

c) If the modified program normally reads commands interactively when run, you must cause it, when started running for such interactive use in the most ordinary way, to print or display an announcement including an appropriate copyright notice and a notice that there is no warranty (or else, saying that you provide a warranty) and that users may redistribute the program under these conditions, and telling the user how to view a copy of this License. (Exception: if the Program itself is interactive but does not normally print such an announcement, your work based on

the Program is not required to print an announcement.)

These requirements apply to the modified work as a whole. If identifiable sections of that work are not derived from the Program, and can be reasonably considered independent and separate works in themselves, then this License, and its terms, do not apply to those sections when you distribute them as separate works. But when you distribute the same sections as part of a whole which is a work based on the Program, the distribution of the whole must be on the terms of this License, whose permissions for other licensees extend to the entire whole, and thus to each and every part regardless of who wrote it.

Thus, it is not the intent of this section to claim rights or contest your rights to work written entirely by you; rather, the intent is to exercise the right to control the distribution of derivative or collective works based on the Program.

In addition, mere aggregation of another work not based on the Program with the Program (or with a work based on the Program) on a volume of a storage or distribution medium does not bring the other work under the scope of this License.

3. You may copy and distribute the Program (or a work based on it, under Section 2) in object code or executable form under the terms of Sections 1 and 2 above provided that you also do one of the following:

- a) Accompany it with the complete corresponding machine-readable source code, which must be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange; or,
- b) Accompany it with a written offer, valid for at least three years, to give any third party, for a charge no more than your cost of physically performing source distribution, a complete machine-readable copy of the corresponding source code, to be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange; or,
- c) Accompany it with the information you received as to the offer to distribute corresponding source code. (This alternative is allowed only for noncommercial distribution and only if you received the program in object code or executable form with such an offer, in accord with Subsection b above.)

The source code for a work means the preferred form of the work for making modifications to it. For an executable work, complete source code means all the source code for all modules it contains, plus any

associated interface definition files, plus the scripts used to control compilation and installation of the executable. However, as a special exception, the source code distributed need not include anything that is normally distributed (in either source or binary form) with the major components (compiler, kernel, and so on) of the operating system on which the executable runs, unless that component itself accompanies the executable.

If distribution of executable or object code is made by offering access to copy from a designated place, then offering equivalent access to copy the source code from the same place counts as distribution of the source code, even though third parties are not compelled to copy the source along with the object code.

4. You may not copy, modify, sublicense, or distribute the Program except as expressly provided under this License. Any attempt otherwise to copy, modify, sublicense or distribute the Program is void, and will automatically terminate your rights under this License. However, parties who have received copies, or rights, from you under this License will not have their licenses terminated so long as such parties remain in full compliance.

5. You are not required to accept this License, since you have not signed it. However, nothing else grants you permission to modify or distribute the Program or its derivative works. These actions are prohibited by law if you do not accept this License. Therefore, by modifying or distributing the Program (or any work based on the Program), you indicate your acceptance of this License to do so, and all its terms and conditions for copying, distributing or modifying the Program or works based on it.

6. Each time you redistribute the Program (or any work based on the Program), the recipient automatically receives a license from the original licensor to copy, distribute or modify the Program subject to these terms and conditions. You may not impose any further restrictions on the recipients' exercise of the rights granted herein. You are not responsible for enforcing compliance by third parties to this License.

7. If, as a consequence of a court judgment or allegation of patent infringement or for any other reason (not limited to patent issues), conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot distribute so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you

may not distribute the Program at all. For example, if a patent license would not permit royalty-free redistribution of the Program by all those who receive copies directly or indirectly through you, then the only way you could satisfy both it and this License would be to refrain entirely from distribution of the Program.

If any portion of this section is held invalid or unenforceable under any particular circumstance, the balance of the section is intended to apply and the section as a whole is intended to apply in other circumstances.

It is not the purpose of this section to induce you to infringe any patents or other property right claims or to contest validity of any such claims; this section has the sole purpose of protecting the integrity of the free software distribution system, which is implemented by public license practices. Many people have made generous contributions to the wide range of software distributed through that system in reliance on consistent application of that system; it is up to the author/donor to decide if he or she is willing to distribute software through any other system and a licensee cannot impose that choice.

This section is intended to make thoroughly clear what is believed to be a consequence of the rest of this License.

8. If the distribution and/or use of the Program is restricted in certain countries either by patents or by copyrighted interfaces, the original copyright holder who places the Program under this License may add an explicit geographical distribution limitation excluding those countries, so that distribution is permitted only in or among countries not thus excluded. In such case, this License incorporates the limitation as if written in the body of this License.

9. The Free Software Foundation may publish revised and/or new versions of the General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Program specifies a version number of this License which applies to it and "any later version", you have the option of following the terms and conditions either of that version or of any later version published by the Free Software Foundation. If the Program does not specify a version number of this License, you may choose any version ever published by the Free Software Foundation.

10. If you wish to incorporate parts of the Program into other free programs whose distribution conditions are different, write to the author to ask for permission. For software which is copyrighted by the Free Software Foundation, write to the Free Software Foundation; we sometimes make exceptions for this. Our decision will be guided by the two goals of preserving the free status of all derivatives of our free software and of promoting the sharing and reuse of software generally.

NO WARRANTY

11. BECAUSE THE PROGRAM IS LICENSED FREE OF CHARGE, THERE IS NO WARRANTY FOR THE PROGRAM, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE PROGRAM "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE PROGRAM IS WITH YOU. SHOULD THE PROGRAM PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

12. IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY AND/OR REDISTRIBUTE THE PROGRAM AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE PROGRAM (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE PROGRAM TO OPERATE WITH ANY OTHER PROGRAMS), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Programs

If you develop a new program, and you want it to be of the greatest possible use to the public, the best way to achieve this is to make it free software which everyone can redistribute and change under these terms.

To do so, attach the following notices to the program. It is safest to attach them to the start of each source file to most effectively convey the exclusion of warranty; and each file should have at least the "copyright" line and a pointer to where the full notice is found.

<one line to give the program's name and a brief idea of what it does.>

Copyright (C) <year> <name of author>

This program is free software; you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation; either version 2 of the License, or (at your option) any later version.

This program is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details.

You should have received a copy of the GNU General Public License along with this program; if not, write to the Free Software Foundation, Inc., 51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA.

Also add information on how to contact you by electronic and paper mail.

If the program is interactive, make it output a short notice like this when it starts in an interactive mode:

```
Gnomovision version 69, Copyright (C) year name of author
Gnomovision comes with ABSOLUTELY NO WARRANTY; for details type `show w'.
This is free software, and you are welcome to redistribute
it
under certain conditions; type `show c' for details.
```

The hypothetical commands ``show w'` and ``show c'` should show the appropriate parts of the General Public License. Of course, the commands you use may be called something other than ``show w'` and ``show c'`; they could even be mouse-clicks or menu items--whatever suits your program.

You should also get your employer (if you work as a programmer) or your school, if any, to sign a "copyright disclaimer" for the program, if necessary. Here is a sample; alter the names:

```
Yoyodyne, Inc., hereby disclaims all copyright interest in the program
`Gnomovision' (which makes passes at compilers) written by James Hacker.
```

```
<signature of Ty Coon>, 1 April 1989
Ty Coon, President of Vice
```

This General Public License does not permit incorporating your program into proprietary programs. If your program is a subroutine library, you may consider it more useful to permit linking proprietary applications with the library. If this is what you want to do, use the GNU Lesser General Public License instead of this License.

[Note that only a few files are distributed under this license.]

GNU LESSER GENERAL PUBLIC LICENSE
Version 2.1, February 1999

Copyright (C) 1991, 1999 Free Software Foundation, Inc.

59 Temple Place, Suite 330, Boston, MA 02111-1307 USA

Everyone is permitted to copy and distribute verbatim copies of this license document, but changing it is not allowed.

[This is the first released version of the Lesser GPL. It also counts as the successor of the GNU Library Public License, version 2, hence the version number 2.1.]

Preamble

The licenses for most software are designed to take away your freedom to share and change it. By contrast, the GNU General Public Licenses are intended to guarantee your freedom to share and change free software--to make sure the software is free for all its users.

This license, the Lesser General Public License, applies to some specially designated software packages--typically libraries--of the Free Software Foundation and other authors who decide to use it. You can use it too, but we suggest you first think carefully about whether this license or the ordinary General Public License is the better strategy to use in any particular case, based on the explanations below.

When we speak of free software, we are referring to freedom of use, not price. Our General Public Licenses are designed to make sure that you have the freedom to distribute copies of free software (and charge for this service if you wish); that you receive source code or can get it if you want it; that you can change the software and use pieces of it in new free programs; and that you are informed that you can do these things.

To protect your rights, we need to make restrictions that forbid distributors to deny you these rights or to ask you to surrender these rights. These restrictions translate to certain responsibilities for you if you distribute copies of the library or if you modify it.

For example, if you distribute copies of the library, whether gratis or for a fee, you must give the recipients all the rights that we gave you. You must make sure that they, too, receive or can get the source code. If you link other code with the library, you must provide

complete object files to the recipients, so that they can relink them with the library after making changes to the library and recompiling it. And you must show them these terms so they know their rights.

We protect your rights with a two-step method: (1) we copyright the library, and (2) we offer you this license, which gives you legal permission to copy, distribute and/or modify the library.

To protect each distributor, we want to make it very clear that there is no warranty for the free library. Also, if the library is modified by someone else and passed on, the recipients should know that what they have is not the original version, so that the original author's reputation will not be affected by problems that might be introduced by others.

^L

Finally, software patents pose a constant threat to the existence of any free program. We wish to make sure that a company cannot effectively restrict the users of a free program by obtaining a restrictive license from a patent holder. Therefore, we insist that any patent license obtained for a version of the library must be consistent with the full freedom of use specified in this license.

Most GNU software, including some libraries, is covered by the ordinary GNU General Public License. This license, the GNU Lesser General Public License, applies to certain designated libraries, and is quite different from the ordinary General Public License. We use this license for certain libraries in order to permit linking those libraries into non-free programs.

When a program is linked with a library, whether statically or using a shared library, the combination of the two is legally speaking a combined work, a derivative of the original library. The ordinary General Public License therefore permits such linking only if the entire combination fits its criteria of freedom. The Lesser General Public License permits more lax criteria for linking other code with the library.

We call this license the "Lesser" General Public License because it does Less to protect the user's freedom than the ordinary General Public License. It also provides other free software developers Less of an advantage over competing non-free programs. These disadvantages are the reason we use the ordinary General Public License for many libraries. However, the Lesser license provides advantages in certain special circumstances.

For example, on rare occasions, there may be a special need to

encourage the widest possible use of a certain library, so that it becomes a de-facto standard. To achieve this, non-free programs must be allowed to use the library. A more frequent case is that a free library does the same job as widely used non-free libraries. In this case, there is little to gain by limiting the free library to free software only, so we use the Lesser General Public License.

In other cases, permission to use a particular library in non-free programs enables a greater number of people to use a large body of free software. For example, permission to use the GNU C Library in non-free programs enables many more people to use the whole GNU operating system, as well as its variant, the GNU/Linux operating system.

Although the Lesser General Public License is Less protective of the users' freedom, it does ensure that the user of a program that is linked with the Library has the freedom and the wherewithal to run that program using a modified version of the Library.

The precise terms and conditions for copying, distribution and modification follow. Pay close attention to the difference between a "work based on the library" and a "work that uses the library". The former contains code derived from the library, whereas the latter must be combined with the library in order to run.

^L

GNU LESSER GENERAL PUBLIC LICENSE TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

0. This License Agreement applies to any software library or other program which contains a notice placed by the copyright holder or other authorized party saying it may be distributed under the terms of this Lesser General Public License (also called "this License"). Each licensee is addressed as "you".

A "library" means a collection of software functions and/or data prepared so as to be conveniently linked with application programs (which use some of those functions and data) to form executables.

The "Library", below, refers to any such software library or work which has been distributed under these terms. A "work based on the Library" means either the Library or any derivative work under copyright law: that is to say, a work containing the Library or a portion of it, either verbatim or with modifications and/or translated straightforwardly into another language. (Hereinafter, translation is included without limitation in the term "modification".)

"Source code" for a work means the preferred form of the work for making modifications to it. For a library, complete source code means all the source code for all modules it contains, plus any associated interface definition files, plus the scripts used to control compilation and installation of the library.

Activities other than copying, distribution and modification are not covered by this License; they are outside its scope. The act of running a program using the Library is not restricted, and output from such a program is covered only if its contents constitute a work based on the Library (independent of the use of the Library in a tool for writing it). Whether that is true depends on what the Library does and what the program that uses the Library does.

1. You may copy and distribute verbatim copies of the Library's complete source code as you receive it, in any medium, provided that you conspicuously and appropriately publish on each copy an appropriate copyright notice and disclaimer of warranty; keep intact all the notices that refer to this License and to the absence of any warranty; and distribute a copy of this License along with the Library.

You may charge a fee for the physical act of transferring a copy, and you may at your option offer warranty protection in exchange for a fee.

2. You may modify your copy or copies of the Library or any portion of it, thus forming a work based on the Library, and copy and distribute such modifications or work under the terms of Section 1 above, provided that you also meet all of these conditions:

- a) The modified work must itself be a software library.
- b) You must cause the files modified to carry prominent notices stating that you changed the files and the date of any change.
- c) You must cause the whole of the work to be licensed at no charge to all third parties under the terms of this License.
- d) If a facility in the modified Library refers to a function or a table of data to be supplied by an application program that uses the facility, other than as an argument passed when the facility is invoked, then you must make a good faith effort to ensure that, in the event an application does not supply such function or table, the facility still operates, and performs whatever part of

its purpose remains meaningful.

(For example, a function in a library to compute square roots has a purpose that is entirely well-defined independent of the application. Therefore, Subsection 2d requires that any application-supplied function or table used by this function must be optional: if the application does not supply it, the square root function must still compute square roots.)

These requirements apply to the modified work as a whole. If identifiable sections of that work are not derived from the Library, and can be reasonably considered independent and separate works in themselves, then this License, and its terms, do not apply to those sections when you distribute them as separate works. But when you distribute the same sections as part of a whole which is a work based on the Library, the distribution of the whole must be on the terms of this License, whose permissions for other licensees extend to the entire whole, and thus to each and every part regardless of who wrote it.

Thus, it is not the intent of this section to claim rights or contest your rights to work written entirely by you; rather, the intent is to exercise the right to control the distribution of derivative or collective works based on the Library.

In addition, mere aggregation of another work not based on the Library with the Library (or with a work based on the Library) on a volume of a storage or distribution medium does not bring the other work under the scope of this License.

3. You may opt to apply the terms of the ordinary GNU General Public License instead of this License to a given copy of the Library. To do this, you must alter all the notices that refer to this License, so that they refer to the ordinary GNU General Public License, version 2, instead of to this License. (If a newer version than version 2 of the ordinary GNU General Public License has appeared, then you can specify that version instead if you wish.) Do not make any other change in these notices.

^L

Once this change is made in a given copy, it is irreversible for that copy, so the ordinary GNU General Public License applies to all subsequent copies and derivative works made from that copy.

This option is useful when you wish to copy part of the code of the Library into a program that is not a library.

4. You may copy and distribute the Library (or a portion or derivative of it, under Section 2) in object code or executable form under the terms of Sections

1 and 2 above provided that you accompany it with the complete corresponding machine-readable source code, which must be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange.

If distribution of object code is made by offering access to copy from a designated place, then offering equivalent access to copy the source code from the same place satisfies the requirement to distribute the source code, even though third parties are not compelled to copy the source along with the object code.

5. A program that contains no derivative of any portion of the Library, but is designed to work with the Library by being compiled or linked with it, is called a "work that uses the Library". Such a work, in isolation, is not a derivative work of the Library, and therefore falls outside the scope of this License.

However, linking a "work that uses the Library" with the Library creates an executable that is a derivative of the Library (because it contains portions of the Library), rather than a "work that uses the library". The executable is therefore covered by this License. Section 6 states terms for distribution of such executables.

When a "work that uses the Library" uses material from a header file that is part of the Library, the object code for the work may be a derivative work of the Library even though the source code is not. Whether this is true is especially significant if the work can be linked without the Library, or if the work is itself a library. The threshold for this to be true is not precisely defined by law.

If such an object file uses only numerical parameters, data structure layouts and accessors, and small macros and small inline functions (ten lines or less in length), then the use of the object file is unrestricted, regardless of whether it is legally a derivative work. (Executables containing this object code plus portions of the Library will still fall under Section 6.)

Otherwise, if the work is a derivative of the Library, you may distribute the object code for the work under the terms of Section 6. Any executables containing that work also fall under Section 6, whether or not they are linked directly with the Library itself.

^L

6. As an exception to the Sections above, you may also combine or

link a "work that uses the Library" with the Library to produce a work containing portions of the Library, and distribute that work under terms of your choice, provided that the terms permit modification of the work for the customer's own use and reverse engineering for debugging such modifications.

You must give prominent notice with each copy of the work that the Library is used in it and that the Library and its use are covered by this License. You must supply a copy of this License. If the work during execution displays copyright notices, you must include the copyright notice for the Library among them, as well as a reference directing the user to the copy of this License. Also, you must do one of these things:

a) Accompany the work with the complete corresponding machine-readable source code for the Library including whatever changes were used in the work (which must be distributed under Sections 1 and 2 above); and, if the work is an executable linked with the Library, with the complete machine-readable "work that uses the Library", as object code and/or source code, so that the user can modify the Library and then relink to produce a modified executable containing the modified Library. (It is understood that the user who changes the contents of definitions files in the Library will not necessarily be able to recompile the application to use the modified definitions.)

b) Use a suitable shared library mechanism for linking with the Library. A suitable mechanism is one that (1) uses at run time a copy of the library already present on the user's computer system, rather than copying library functions into the executable, and (2) will operate properly with a modified version of the library, if the user installs one, as long as the modified version is interface-compatible with the version that the work was made with.

c) Accompany the work with a written offer, valid for at least three years, to give the same user the materials specified in Subsection 6a, above, for a charge no more than the cost of performing this distribution.

d) If distribution of the work is made by offering access to copy from a designated place, offer equivalent access to copy the above specified materials from the same place.

e) Verify that the user has already received a copy of these materials or that you have already sent this user a copy.

For an executable, the required form of the "work that uses the Library" must include any data and utility programs needed for reproducing the executable from it. However, as a special exception, the

materials to be distributed need not include anything that is normally distributed (in either source or binary form) with the major components (compiler, kernel, and so on) of the operating system on which the executable runs, unless that component itself accompanies the executable.

It may happen that this requirement contradicts the license restrictions of other proprietary libraries that do not normally accompany the operating system. Such a contradiction means you cannot use both them and the Library together in an executable that you distribute.

^L

7. You may place library facilities that are a work based on the Library side-by-side in a single library together with other library facilities not covered by this License, and distribute such a combined library, provided that the separate distribution of the work based on the Library and of the other library facilities is otherwise permitted, and provided that you do these two things:

- a) Accompany the combined library with a copy of the same work based on the Library, uncombined with any other library facilities. This must be distributed under the terms of the Sections above.
- b) Give prominent notice with the combined library of the fact that part of it is a work based on the Library, and explaining where to find the accompanying uncombined form of the same work.

8. You may not copy, modify, sublicense, link with, or distribute the Library except as expressly provided under this License. Any attempt otherwise to copy, modify, sublicense, link with, or distribute the Library is void, and will automatically terminate your rights under this License. However, parties who have received copies, or rights, from you under this License will not have their licenses terminated so long as such parties remain in full compliance.

9. You are not required to accept this License, since you have not signed it. However, nothing else grants you permission to modify or distribute the

Library or its derivative works. These actions are prohibited by law if you do not accept this License. Therefore, by modifying or distributing the Library (or any work based on the Library), you indicate your acceptance of this License to do so, and

all its terms and conditions for copying, distributing or modifying the Library or works based on it.

10. Each time you redistribute the Library (or any work based on the Library), the recipient automatically receives a license from the original licensor to copy, distribute, link with or modify the Library subject to these terms and conditions. You may not impose any further restrictions on the recipients' exercise of the rights granted herein. You are not responsible for enforcing compliance by third parties with this License.

^L

11. If, as a consequence of a court judgment or allegation of patent infringement or for any other reason (not limited to patent issues), conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot distribute so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not distribute the Library at all. For example, if a patent license would not permit royalty-free redistribution of the Library by all those who receive copies directly or indirectly through you, then the only way you could satisfy both it and this License would be to refrain entirely from distribution of the Library.

If any portion of this section is held invalid or unenforceable under any particular circumstance, the balance of the section is intended to apply, and the section as a whole is intended to apply in other circumstances.

It is not the purpose of this section to induce you to infringe any patents or other property right claims or to contest validity of any such claims; this section has the sole purpose of protecting the integrity of the free software distribution system which is implemented by public license practices. Many people have made generous contributions to the wide range of software distributed through that system in reliance on consistent application of that system; it is up to the author/donor to decide if he or she is willing to distribute software through any other system and a licensee cannot impose that choice.

This section is intended to make thoroughly clear what is believed to be a consequence of the rest of this License.

12. If the distribution and/or use of the Library is restricted in certain countries either by patents or by copyrighted interfaces, the original copyright holder who places the Library under this License

may add an explicit geographical distribution limitation excluding those countries, so that distribution is permitted only in or among countries not thus excluded. In such case, this License incorporates the limitation as if written in the body of this License.

13. The Free Software Foundation may publish revised and/or new versions of the Lesser General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Library specifies a version number of this License which applies to it and "any later version", you have the option of following the terms and conditions either of that version or of any later version published by the Free Software Foundation. If the Library does not specify a license version number, you may choose any version ever published by the Free Software Foundation.

^L

14. If you wish to incorporate parts of the Library into other free programs whose distribution conditions are incompatible with these, write to the author to ask for permission. For software which is copyrighted by the Free Software Foundation, write to the Free Software Foundation; we sometimes make exceptions for this. Our decision will be guided by the two goals of preserving the free status of all derivatives of our free software and of promoting the sharing and reuse of software generally.

NO WARRANTY

15. BECAUSE THE LIBRARY IS LICENSED FREE OF CHARGE, THERE IS NO WARRANTY FOR THE LIBRARY, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE LIBRARY "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE LIBRARY IS WITH YOU. SHOULD THE LIBRARY PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

16. IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY AND/OR REDISTRIBUTE THE LIBRARY AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE LIBRARY (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING

RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE LIBRARY TO OPERATE WITH ANY OTHER SOFTWARE), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

END OF TERMS AND CONDITIONS

^L

How to Apply These Terms to Your New Libraries

If you develop a new library, and you want it to be of the greatest possible use to the public, we recommend making it free software that everyone can redistribute and change. You can do so by permitting redistribution under these terms (or, alternatively, under the terms of the ordinary General Public License).

To apply these terms, attach the following notices to the library.

It

is safest to attach them to the start of each source file to most effectively convey the exclusion of warranty; and each file should have at least the "copyright" line and a pointer to where the full notice is found.

<one line to give the library's name and a brief idea of what it does.>

Copyright (C) <year> <name of author>

This library is free software; you can redistribute it and/or modify it under the terms of the GNU Lesser General Public License as published by the Free Software Foundation; either version 2.1 of the License, or (at your option) any later version.

This library is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU Lesser General Public License for more details.

You should have received a copy of the GNU Lesser General Public License along with this library; if not, write to the Free Software

Foundation, Inc., 59 Temple Place, Suite 330, Boston, MA 02111-1307 USA

Also add information on how to contact you by electronic and paper mail.

You should also get your employer (if you work as a programmer) or your school, if any, to sign a "copyright disclaimer" for the library, if necessary. Here is a sample; alter the names:

Yoyodyne, Inc., hereby disclaims all copyright interest in the

library `Frob' (a library for tweaking knobs) written by James
Random Hacker.

<signature of Ty Coon>, 1 April 1990
Ty Coon, President of Vice

That's all there is to it!

LICENSE TERMS

Copyright (c) 2000, Dimitrios Souflis
All rights reserved.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions are
met:

Redistributions of source code must retain the above copyright notice,
this list of conditions and the following disclaimer.

Redistributions in binary form must reproduce the above copyright
notice, this list of conditions and the following disclaimer in the
documentation and/or other materials provided with the distribution.

Neither the name of Dimitrios Souflis nor the names of the
contributors may be used to endorse or promote products derived from
this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS
``AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT
LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR
A PARTICULAR PURPOSE ARE DISCLAIMED.

IN NO EVENT SHALL THE REGENTS OR
CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL,
EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO,
PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR
PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF
LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING
NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

[Note that only a few files are distributed under this license.]

GNU LESSER GENERAL PUBLIC LICENSE

Version 3, 29 June 2007

Copyright (C) 2007 Free Software Foundation, Inc. <<https://fsf.org/>>
Everyone is permitted to copy and distribute verbatim copies
of this license document, but changing it is not allowed.

This version of the GNU Lesser General Public License incorporates the terms and conditions of version 3 of the GNU General Public License, supplemented by the additional permissions listed below.

0. Additional Definitions.

As used herein, "this License" refers to version 3 of the GNU Lesser General Public License, and the "GNU GPL" refers to version 3 of the GNU General Public License.

"The Library" refers to a covered work governed by this License, other than an Application or a Combined Work as defined below.

An "Application" is any work that makes use of an interface provided by the Library, but which is not otherwise based on the Library.

Defining a subclass of a class defined by the Library is deemed a mode of using an interface provided by the Library.

A "Combined Work" is a work produced by combining or linking an Application with the Library. The particular version of the Library with which the Combined Work was made is also called the "Linked Version".

The "Minimal Corresponding Source" for a Combined Work means the Corresponding Source for the Combined Work, excluding any source code for portions of the Combined Work that, considered in isolation, are based on the Application, and not on the Linked Version.

The "Corresponding Application Code" for a Combined Work means the object code and/or source code for the Application, including any data and utility programs needed for reproducing the Combined Work from the Application, but excluding the System Libraries of the Combined Work.

1. Exception to Section 3 of the GNU GPL.

You may convey a covered work under sections 3 and 4 of this License without being bound by section 3 of the GNU GPL.

2. Conveying Modified Versions.

If you modify a copy of the Library, and, in your modifications, a facility refers to a function or data to be supplied by an Application that uses the facility (other than as an argument passed when the facility is invoked), then you may convey a copy of the modified version:

a) under this License, provided that you make a good faith effort to ensure that, in the event an Application does not supply the function or data, the facility still operates, and performs whatever part of its purpose remains meaningful, or

b) under the GNU GPL, with none of the additional permissions of this License applicable to that copy.

3. Object Code Incorporating Material from Library Header Files.

The object code form of an Application may incorporate material from a header file that is part of the Library. You may convey such object code under terms of your choice, provided that, if the incorporated material

is not limited to numerical parameters, data structure layouts and accessors, or small macros, inline functions and templates (ten or fewer lines in length), you do both of the following:

a) Give prominent notice with each copy of the object code that the Library is used in it and that the Library and its use are covered by this License.

b) Accompany the object code with a copy of the GNU GPL and this license document.

4. Combined Works.

You may convey a Combined Work under terms of your choice that, taken together, effectively do not restrict modification of the portions of the Library contained in the Combined Work and reverse engineering for debugging such modifications, if you also do each of the following:

a) Give prominent notice with each copy of the Combined Work that the Library is used in it and that the Library and its use are covered by this License.

b) Accompany the Combined Work with a copy of the GNU GPL and this license document.

c) For a Combined Work that displays copyright notices during execution, include the copyright notice for the Library among these notices, as well as a reference directing the user to the copies of the GNU GPL and this license document.

d) Do one of the following:

0) Convey the Minimal Corresponding Source under the terms of this License, and the Corresponding Application Code in a form suitable for, and under terms that permit, the user to recombine or relink the Application with a modified version of the Linked Version to produce a modified Combined Work, in the manner specified by section 6 of the GNU GPL for conveying Corresponding Source.

1) Use a suitable shared library mechanism for linking with the Library. A suitable mechanism is one that (a) uses at run time a copy of the Library already present on the user's computer system, and (b) will operate properly with a modified version of the Library that is interface-compatible with the Linked Version.

e) Provide Installation Information, but only if you would otherwise be required to provide such information under section 6 of the GNU GPL, and only to the extent that such information is necessary to install and execute a modified version of the Combined Work produced by recombining or relinking the Application with a modified version of the Linked Version. (If you use option 4d0, the Installation Information must accompany the Minimal Corresponding Source and Corresponding Application Code. If you use option 4d1, you must provide the Installation Information in the manner specified by section 6 of the GNU GPL for conveying Corresponding Source.)

5. Combined Libraries.

You may place library facilities that are a work based on the Library side by side in a single library together with other library facilities that are not Applications and are not covered by this License, and convey such a combined library under terms of your choice, if you do both of the following:

a) Accompany the combined library with a copy of the same work based on the Library, uncombined with any other library facilities, conveyed under the terms of this License.

b) Give prominent notice with the combined library that part of it is a work based on the Library, and explaining where to find the accompanying uncombined form of the same work.

6. Revised Versions of the GNU Lesser General Public License.

The Free Software Foundation may publish revised and/or new versions of the GNU Lesser General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Library as you received it specifies that a certain numbered version of the GNU Lesser General Public License "or any later version" applies to it, you have the option of following the terms and conditions either of that published version or of any later version published by the Free Software Foundation. If the Library as you received it does not specify a version number of the GNU Lesser General Public License, you may choose any version of the GNU Lesser General Public License ever published by the Free Software Foundation.

If the Library as you received it specifies that a proxy can decide whether future versions of the GNU Lesser General Public License shall apply, that proxy's public statement of acceptance of any version is permanent authorization for you to choose that version for the Library.

```
# COPYING.other                -*- org -*-  
#+TITLE: List of code with permissive licenses as used by GnuPG.  
#+STARTUP: showall
```

* DNS resolver (dirmngr/dns.c)

dns.c - Recursive, Reentrant DNS Resolver.

Copyright (c) 2008, 2009, 2010, 2012-2016 William Ahern

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR

OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

* TinySCHEME (tests/gpgscm/LICENSE.TinySCHEME)

Copyright (c) 2000, Dimitrios Souflis

All rights reserved.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.

Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.

Neither the name of Dimitrios Souflis nor the names of the contributors may be used to endorse or promote products derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS ``AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE REGENTS OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

1.86 gnutls 3.5.18-1ubuntu1.6

1.86.1 Available under license :

GNU LESSER GENERAL PUBLIC LICENSE

Version 2.1, February 1999

Copyright (C) 1991, 1999 Free Software Foundation, Inc.

51 Franklin St, Fifth Floor, Boston, MA 02110-1301 USA

Everyone is permitted to copy and distribute verbatim copies of this license document, but changing it is not allowed.

[This is the first released version of the Lesser GPL. It also counts as the successor of the GNU Library Public License, version 2, hence the version number 2.1.]

Preamble

The licenses for most software are designed to take away your freedom to share and change it. By contrast, the GNU General Public Licenses are intended to guarantee your freedom to share and change free software--to make sure the software is free for all its users.

This license, the Lesser General Public License, applies to some specially designated software packages--typically libraries--of the Free Software Foundation and other authors who decide to use it. You can use it too, but we suggest you first think carefully about whether this license or the ordinary General Public License is the better strategy to use in any particular case, based on the explanations below.

When we speak of free software, we are referring to freedom of use, not price. Our General Public Licenses are designed to make sure that you have the freedom to distribute copies of free software (and charge for this service if you wish); that you receive source code or can get it if you want it; that you can change the software and use pieces of it in new free programs; and that you are informed that you can do these things.

To protect your rights, we need to make restrictions that forbid distributors to deny you these rights or to ask you to surrender these rights. These restrictions translate to certain responsibilities for you if you distribute copies of the library or if you modify it.

For example, if you distribute copies of the library, whether gratis or for a fee, you must give the recipients all the rights that we gave you. You must make sure that they, too, receive or can get the source code. If you link other code with the library, you must provide complete object files to the recipients, so that they can relink them with the library after making changes to the library and recompiling it. And you must show them these terms so they know their rights.

We protect your rights with a two-step method: (1) we copyright the library, and (2) we offer you this license, which gives you legal permission to copy, distribute and/or modify the library.

To protect each distributor, we want to make it very clear that there is no warranty for the free library. Also, if the library is modified by someone else and passed on, the recipients should know

that what they have is not the original version, so that the original author's reputation will not be affected by problems that might be introduced by others.

Finally, software patents pose a constant threat to the existence of any free program. We wish to make sure that a company cannot effectively restrict the users of a free program by obtaining a restrictive license from a patent holder. Therefore, we insist that any patent license obtained for a version of the library must be consistent with the full freedom of use specified in this license.

Most GNU software, including some libraries, is covered by the ordinary GNU General Public License. This license, the GNU Lesser General Public License, applies to certain designated libraries, and is quite different from the ordinary General Public License. We use this license for certain libraries in order to permit linking those libraries into non-free programs.

When a program is linked with a library, whether statically or using a shared library, the combination of the two is legally speaking a combined work, a derivative of the original library. The ordinary General Public License therefore permits such linking only if the entire combination fits its criteria of freedom. The Lesser General Public License permits more lax criteria for linking other code with the library.

We call this license the "Lesser" General Public License because it does Less to protect the user's freedom than the ordinary General Public License. It also provides other free software developers Less of an advantage over competing non-free programs. These disadvantages are the reason we use the ordinary General Public License for many libraries. However, the Lesser license provides advantages in certain special circumstances.

For example, on rare occasions, there may be a special need to encourage the widest possible use of a certain library, so that it becomes a de-facto standard. To achieve this, non-free programs must be allowed to use the library. A more frequent case is that a free library does the same job as widely used non-free libraries. In this case, there is little to gain by limiting the free library to free software only, so we use the Lesser General Public License.

In other cases, permission to use a particular library in non-free programs enables a greater number of people to use a large body of free software. For example, permission to use the GNU C Library in

non-free programs enables many more people to use the whole GNU operating system, as well as its variant, the GNU/Linux operating system.

Although the Lesser General Public License is Less protective of the users' freedom, it does ensure that the user of a program that is linked with the Library has the freedom and the wherewithal to run that program using a modified version of the Library.

The precise terms and conditions for copying, distribution and modification follow. Pay close attention to the difference between a "work based on the library" and a "work that uses the library". The former contains code derived from the library, whereas the latter must be combined with the library in order to run.

GNU LESSER GENERAL PUBLIC LICENSE TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

0. This License Agreement applies to any software library or other program which contains a notice placed by the copyright holder or other authorized party saying it may be distributed under the terms of this Lesser General Public License (also called "this License"). Each licensee is addressed as "you".

A "library" means a collection of software functions and/or data prepared so as to be conveniently linked with application programs (which use some of those functions and data) to form executables.

The "Library", below, refers to any such software library or work which has been distributed under these terms. A "work based on the Library" means either the Library or any derivative work under copyright law: that is to say, a work containing the Library or a portion of it, either verbatim or with modifications and/or translated straightforwardly into another language. (Hereinafter, translation is included without limitation in the term "modification".)

"Source code" for a work means the preferred form of the work for making modifications to it. For a library, complete source code means all the source code for all modules it contains, plus any associated interface definition files, plus the scripts used to control compilation and installation of the library.

Activities other than copying, distribution and modification are not covered by this License; they are outside its scope. The act of running a program using the Library is not restricted, and output from such a program is covered only if its contents constitute a work based on the Library (independent of the use of the Library in a tool for

writing it). Whether that is true depends on what the Library does and what the program that uses the Library does.

1. You may copy and distribute verbatim copies of the Library's complete source code as you receive it, in any medium, provided that you conspicuously and appropriately publish on each copy an appropriate copyright notice and disclaimer of warranty; keep intact all the notices that refer to this License and to the absence of any warranty; and distribute a copy of this License along with the Library.

You may charge a fee for the physical act of transferring a copy, and you may at your option offer warranty protection in exchange for a fee.

2. You may modify your copy or copies of the Library or any portion of it, thus forming a work based on the Library, and copy and distribute such modifications or work under the terms of Section 1 above, provided that you also meet all of these conditions:

a) The modified work must itself be a software library.

b) You must cause the files modified to carry prominent notices stating that you changed the files and the date of any change.

c) You must cause the whole of the work to be licensed at no charge to all third parties under the terms of this License.

d) If a facility in the modified Library refers to a function or a table of data to be supplied by an application program that uses the facility, other than as an argument passed when the facility is invoked, then you must make a good faith effort to ensure that, in the event an application does not supply such function or table, the facility still operates, and performs whatever part of its purpose remains meaningful.

(For example, a function in a library to compute square roots has a purpose that is entirely well-defined independent of the application. Therefore, Subsection 2d requires that any application-supplied function or table used by this function must be optional: if the application does not supply it, the square root function must still compute square roots.)

These requirements apply to the modified work as a whole. If identifiable sections of that work are not derived from the Library, and can be reasonably considered independent and separate works in

themselves,

then this License, and its terms, do not apply to those sections when you distribute them as separate works. But when you distribute the same sections as part of a whole which is a work based on the Library, the distribution of the whole must be on the terms of this License, whose permissions for other licensees extend to the entire whole, and thus to each and every part regardless of who wrote it.

Thus, it is not the intent of this section to claim rights or contest your rights to work written entirely by you; rather, the intent is to exercise the right to control the distribution of derivative or collective works based on the Library.

In addition, mere aggregation of another work not based on the Library with the Library (or with a work based on the Library) on a volume of a storage or distribution medium does not bring the other work under the scope of this License.

3. You may opt to apply the terms of the ordinary GNU General Public License instead of this License to a given copy of the Library. To do this, you must alter all the notices that refer to this License, so that they refer to the ordinary GNU General Public License, version 2, instead of to this License. (If a newer version than version 2 of the ordinary GNU General Public License has appeared, then you can specify that version instead if you wish.) Do not make any other change in these notices.

Once this change is made in a given copy, it is irreversible for that copy, so the ordinary GNU General Public License applies to all subsequent copies and derivative works made from that copy.

This option is useful when you wish to copy part of the code of the Library into a program that is not a library.

4. You may copy and distribute the Library (or a portion or derivative of it, under Section 2) in object code or executable form under the terms of Sections 1 and 2 above provided that you accompany it with the complete corresponding machine-readable source code, which must be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange.

If distribution of object code is made by offering access to copy from a designated place, then offering equivalent access to copy the source code from the same place satisfies the requirement to distribute the source code, even though third parties are not

compelled to copy the source along with the object code.

5. A program that contains no derivative of any portion of the Library, but is designed to work with the Library by being compiled or linked with it, is called a "work that uses the Library". Such a work, in isolation, is not a derivative work of the Library, and therefore falls outside the scope of this License.

However, linking a "work that uses the Library" with the Library creates an executable that is a derivative of the Library (because it contains portions of the Library), rather than a "work that uses the library". The executable is therefore covered by this License.

Section 6 states terms for distribution of such executables.

When a "work that uses the Library" uses material from a header file that is part of the Library, the object code for the work may be a derivative work of the Library even though the source code is not. Whether this is true is especially significant if the work can be linked without the Library, or if the work is itself a library. The threshold for this to be true is not precisely defined by law.

If such an object file uses only numerical parameters, data structure layouts and accessors, and small macros and small inline functions (ten lines or less in length), then the use of the object file is unrestricted, regardless of whether it is legally a derivative work. (Executables containing this object code plus portions of the Library will still fall under Section 6.)

Otherwise, if the work is a derivative of the Library, you may distribute the object code for the work under the terms of Section 6. Any executables containing that work also fall under Section 6, whether or not they are linked directly with the Library itself.

6. As an exception to the Sections above, you may also combine or link a "work that uses the Library" with the Library to produce a work containing portions of the Library, and distribute that work under terms of your choice, provided that the terms permit modification of the work for the customer's own use and reverse engineering for debugging such modifications.

You must give prominent notice with each copy of the work that the Library is used in it and that the Library and its use are covered by this License. You must supply a copy of this License. If the work during execution displays copyright notices, you must include the copyright notice for the Library among them, as well as a reference directing the user to the copy of this License. Also, you must do one

of these things:

a) Accompany the work with the complete corresponding machine-readable source code for the Library including whatever changes were used in the work (which must be distributed under Sections 1 and 2 above); and, if the work is an executable linked with the Library, with the complete machine-readable "work that uses the Library", as object code and/or source code, so that the user can modify the Library and then relink to produce a modified executable containing the modified Library. (It is understood that the user who changes the contents of definitions files in the Library will not necessarily be able to recompile the application to use the modified definitions.)

b) Use a suitable shared library mechanism for linking with the Library. A suitable mechanism is one that (1) uses at run time a copy of the library already present on the user's computer system, rather than copying library functions into the executable, and (2) will operate properly with a modified version of the library, if the user installs one, as long as the modified version is interface-compatible with the version that the work was made with.

c) Accompany the work with a written offer, valid for at least three years, to give the same user the materials specified in Subsection 6a, above, for a charge no more than the cost of performing this distribution.

d) If distribution of the work is made by offering access to copy from a designated place, offer equivalent access to copy the above specified materials from the same place.

e) Verify that the user has already received a copy of these materials or that you have already sent this user a copy.

For an executable, the required form of the "work that uses the Library" must include any data and utility programs needed for reproducing the executable from it. However, as a special exception, the materials to be distributed need not include anything that is normally distributed (in either source or binary form) with the major components (compiler, kernel, and so on) of the operating system on which the executable runs, unless that component itself accompanies the executable.

It may happen that this requirement contradicts the license restrictions of other proprietary libraries that do not normally

accompany the operating system. Such a contradiction means you cannot use both them and the Library together in an executable that you distribute.

7. You may place library facilities that are a work based on the Library side-by-side in a single library together with other library facilities not covered by this License, and distribute such a combined library, provided that the separate distribution of the work based on the Library and of the other library facilities is otherwise permitted, and provided that you do these two things:

a) Accompany the combined library with a copy of the same work based on the Library, uncombined with any other library facilities. This must be distributed under the terms of the Sections above.

b) Give prominent notice with the combined library of the fact that part of it is a work based on the Library, and explaining where to find the accompanying uncombined form of the same work.

8. You may not copy, modify, sublicense, link with, or distribute the Library except as expressly provided under this License. Any attempt otherwise to copy, modify, sublicense, link with, or distribute the Library is void, and will automatically terminate your rights under this License. However, parties who have received copies, or rights, from you under this License will not have their licenses terminated so long as such parties remain in full compliance.

9. You are not required to accept this License, since you have not signed it. However, nothing else grants you permission to modify or distribute the Library or its derivative works. These actions are prohibited by law if you do not accept this License. Therefore, by modifying or distributing the Library (or any work based on the Library), you indicate your acceptance of this License to do so, and all its terms and conditions for copying, distributing or modifying the Library or works based on it.

10. Each time you redistribute the Library (or any work based on the Library), the recipient automatically receives a license from the original licensor to copy, distribute, link with or modify the Library subject to these terms and conditions. You may not impose any further restrictions on the recipients' exercise of the rights granted herein. You are not responsible for enforcing compliance by third parties with this License.

11. If, as a consequence of a court judgment or allegation of patent

infringement or for any other reason (not limited to patent issues), conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot distribute

so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not distribute the Library at all. For example, if a patent license would not permit royalty-free redistribution of the Library by all those who receive copies directly or indirectly through you, then the only way you could satisfy both it and this License would be to refrain entirely from distribution of the Library.

If any portion of this section is held invalid or unenforceable under any particular circumstance, the balance of the section is intended to apply, and the section as a whole is intended to apply in other circumstances.

It is not the purpose of this section to induce you to infringe any patents or other property right claims or to contest validity of any such claims; this section has the sole purpose of protecting the integrity of the free software distribution system which is implemented by public license practices. Many people have made generous contributions to the wide range of software distributed through that system in reliance on consistent application of that system; it is up to the author/donor to decide if he or she is willing to distribute software through any other system and a licensee cannot impose that choice.

This section is intended to make thoroughly clear what is believed to be a consequence of the rest of this License.

12. If the distribution and/or use of the Library is restricted in certain countries either by patents or by copyrighted interfaces, the original copyright holder who places the Library under this License may add an explicit geographical distribution limitation excluding those countries, so that distribution is permitted only in or among countries not thus excluded. In such case, this License incorporates the limitation as if written in the body of this License.

13. The Free Software Foundation may publish revised and/or new versions of the Lesser General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Library specifies a version number of this License which applies to it and

"any later version", you have the option of following the terms and conditions either of that version or of any later version published by the Free Software Foundation. If the Library does not specify a license version number, you may choose any version ever published by the Free Software Foundation.

14. If you wish to incorporate parts of the Library into other free programs whose distribution conditions are incompatible with these, write to the author to ask for permission. For software which is copyrighted by the Free Software Foundation, write to the Free Software Foundation; we sometimes make exceptions for this. Our decision will be guided by the two goals of preserving the free status of all derivatives of our free software and of promoting the sharing and reuse of software generally.

NO WARRANTY

15. BECAUSE THE LIBRARY IS LICENSED FREE OF CHARGE, THERE IS NO WARRANTY FOR THE LIBRARY, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE LIBRARY "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE LIBRARY IS WITH YOU. SHOULD THE LIBRARY PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

16. IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY AND/OR REDISTRIBUTE THE LIBRARY AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE LIBRARY (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE LIBRARY TO OPERATE WITH ANY OTHER SOFTWARE), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Libraries

If you develop a new library, and you want it to be of the greatest possible use to the public, we recommend making it free software that everyone can redistribute and change. You can do so by permitting redistribution under these terms (or, alternatively, under the terms of the

ordinary General Public License).

To apply these terms, attach the following notices to the library. It is safest to attach them to the start of each source file to most effectively convey the exclusion of warranty; and each file should have at least the "copyright" line and a pointer to where the full notice is found.

<one line to give the library's name and a brief idea of what it does.>
Copyright (C) <year> <name of author>

This library is free software; you can redistribute it and/or modify it under the terms of the GNU Lesser General Public License as published by the Free Software Foundation; either version 2.1 of the License, or (at your option) any later version.

This library is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU Lesser General Public License for more details.

You should have received a copy of the GNU Lesser General Public License along with this library; if not, write to the Free Software Foundation, Inc., 51 Franklin St, Fifth Floor, Boston, MA 02110-1301 USA

Also add information on how to contact you by electronic and paper mail.

You should also get your employer (if you work as a programmer) or your school, if any, to sign a "copyright disclaimer" for the library, if necessary. Here is a sample; alter the names:

Yoyodyne, Inc., hereby disclaims all copyright interest in the library `Frob' (a library for tweaking knobs) written by James Random Hacker.

<signature of Ty Coon>, 1 April 1990
Ty Coon, President of Vice

That's all there is to it!
Statement of Purpose

The laws of most jurisdictions throughout the world automatically confer exclusive Copyright and Related Rights (defined below) upon the creator and subsequent owner(s) (each and all, an "owner") of an original work of authorship and/or a database (each, a "Work").

Certain owners wish to permanently relinquish those rights to a Work for the purpose of contributing to a commons of creative, cultural and scientific works ("Commons") that the public can reliably and without fear of later claims of infringement build upon, modify, incorporate in other works, reuse and redistribute as freely as possible in any form

whatsoever and for any purposes, including without limitation commercial purposes. These owners may contribute to the Commons to promote the ideal of a free culture and the further production of creative, cultural and scientific works, or to gain reputation or greater distribution for their Work in part through the use and efforts of others.

For these and/or

other purposes and motivations, and without any expectation of additional consideration or compensation, the person associating CC0 with a Work (the "Affirmer"), to the extent that he or she is an owner of Copyright and Related Rights in the Work, voluntarily elects to apply CC0 to the Work and publicly distribute the Work under its terms, with knowledge of his or her Copyright and Related Rights in the Work and the meaning and intended legal effect of CC0 on those rights.

1. Copyright and Related Rights. A Work made available under CC0 may be protected by copyright and related or neighboring rights ("Copyright and Related Rights"). Copyright and Related Rights include, but are not limited to, the following:

- the right to reproduce, adapt, distribute, perform, display, communicate, and translate a Work;
- moral rights retained by the original author(s) and/or performer(s);
- publicity and privacy rights pertaining to a person's image or likeness depicted in a Work;
- rights protecting against unfair competition in regards to a Work, subject to the limitations in paragraph 4(a), below;
- rights protecting the extraction, dissemination, use and reuse of data in a Work;
- database rights (such as those arising under Directive 96/9/EC of the European Parliament and of the Council of 11 March 1996 on the legal protection of databases, and under any national implementation thereof, including any amended or successor version of such directive); and
- other similar, equivalent or corresponding rights throughout the world based on applicable law or treaty, and any national implementations thereof.

2. Waiver. To the greatest extent permitted by, but not in contravention of, applicable law, Affirmer hereby overtly, fully, permanently, irrevocably and unconditionally waives, abandons, and surrenders all of Affirmer's Copyright and Related Rights and associated claims and causes of action, whether now known or unknown (including existing as well as future claims

and causes of action), in the Work (i) in all territories worldwide, (ii) for the maximum duration provided by applicable law or treaty (including future time extensions), (iii) in any current or future medium and for any number of copies, and (iv) for any purpose whatsoever, including without limitation commercial, advertising or promotional purposes (the "Waiver"). Affirmer makes the Waiver for the benefit of each member of the public at large and to the detriment of Affirmer's heirs and successors, fully intending that such Waiver shall not be subject to revocation, rescission, cancellation, termination, or any other legal or equitable action to disrupt the quiet enjoyment of the Work by the public as contemplated by Affirmer's express Statement of Purpose.

3. Public License Fallback. Should any part of the Waiver for any reason be judged legally invalid or ineffective under applicable law, then the Waiver shall be preserved to the maximum extent permitted taking into account Affirmer's

express Statement of Purpose. In addition, to the extent the Waiver is so judged Affirmer hereby grants to each affected person a royalty-free, non transferable, non sublicensable, non exclusive, irrevocable and unconditional license to exercise Affirmer's Copyright and Related Rights in the Work (i) in all territories worldwide, (ii) for the maximum duration provided by applicable law or treaty (including future time extensions), (iii) in any current or future medium and for any number of copies, and (iv) for any purpose whatsoever, including without limitation commercial, advertising or promotional purposes (the "License"). The License shall be deemed effective as of the

date CC0 was applied by Affirmer to the Work. Should any part of the License for any reason be judged legally invalid or ineffective under applicable law, such partial invalidity or ineffectiveness shall not invalidate the remainder of the License, and in such case Affirmer hereby affirms that he or she will not (i) exercise any of his or her remaining Copyright and Related Rights in the Work or (ii) assert any associated claims and causes of action with respect to the Work, in either case contrary to Affirmer's express Statement of Purpose.

4. Limitations and Disclaimers.

No trademark or patent rights held by Affirmer are waived, abandoned, surrendered, licensed or otherwise affected by this document.

Affirmer offers the Work as-is and makes no representations or warranties of any kind concerning the Work, express, implied, statutory or otherwise, including without limitation warranties of title, merchantability, fitness for a particular purpose, non infringement, or the absence of latent or other defects, accuracy, or the present or absence of errors, whether or not discoverable, all to the greatest extent permissible under applicable law.

Affirmer disclaims responsibility for clearing rights of other persons that may apply to the Work or any use thereof, including without

limitation any person's Copyright and Related Rights in the Work. Further, Affirmer disclaims responsibility for obtaining any necessary consents, permissions or other rights required for any use of the Work.

Affirmer understands and acknowledges that Creative Commons is not a party to this document and has no duty or obligation with respect to this CC0 or use of the Work.

=====

Written by Andy Polyakov <appro@fy.chalmers.se> for the OpenSSL project. The module is, however, dual licensed under OpenSSL and CRYPTOGRAMS licenses depending on where you obtain it. For further details see <http://www.openssl.org/~appro/cryptograms/>.

=====

Copyright (c) 2006-2012, CRYPTOGRAMS by <appro@openssl.org>
All rights reserved.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

- * Redistributions of source code must retain copyright notices, this list of conditions and the following disclaimer.

- * Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.

- * Neither the name of the CRYPTOGRAMS nor the names of its copyright holder and contributors may be used to endorse or promote products derived from this software without specific prior written permission.

ALTERNATIVELY, provided that this notice is retained in full, this product may be distributed under the terms of the GNU General Public License (GPL), in which case the provisions of the GPL apply INSTEAD OF those given above.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDER AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

```
#####  
## Constant-time SSSE3 AES core implementation.  
## version 0.1  
##  
## By Mike Hamburg (Stanford University), 2009  
## Public domain.  
##  
## For details see http://shiftleft.org/papers/vector\_aes/ and  
## http://crypto.stanford.edu/vpaes/.
```

LICENSING
=====

Since GnuTLS version 3.1.10, the core library is released under the GNU Lesser General Public License (LGPL) version 2.1 or later (see doc/COPYING.LESSER for the license terms).

The GNU LGPL applies to the main GnuTLS library, while the included applications as well as gnutls-openssl library are under the GNU GPL version 3. The gnutls library is located in the lib/ and libdane/ directories, while the applications in src/ and, the gnutls-openssl library is at extra/.

The documentation in doc/ is under the GNU FDL license 1.3.

Note, however, that the nettle and the gmp libraries which are GnuTLS dependencies, they are distributed under a LGPLv3+ or GPLv2+ dual license. As such binaries linking to them need to adhere to either LGPLv3+

or the GPLv2+ license.

For any copyright year range specified as YYYY-ZZZZ in this package note that the range specifies every single year in that closed interval.

GNU LESSER GENERAL PUBLIC LICENSE

Version 3, 29 June 2007

Copyright (C) 1992-2015 by Bruce Korb - all rights reserved
Everyone is permitted to copy and distribute verbatim copies
of this license document, but changing it is not allowed.

This version of the GNU Lesser General Public License incorporates
the terms and conditions of version 3 of the GNU General Public
License, supplemented by the additional permissions listed below.

0. Additional Definitions.

As used herein, "this License" refers to version 3 of the GNU Lesser
General Public License, and the "GNU GPL" refers to version 3 of the GNU
General Public License.

"The Library" refers to a covered work governed by this License,
other than an Application or a Combined Work as defined below.

An "Application" is any work that makes use of an interface provided
by the Library, but which is not otherwise based on the Library.
Defining a subclass of a class defined by the Library is deemed
a mode
of using an interface provided by the Library.

A "Combined Work" is a work produced by combining or linking an
Application with the Library. The particular version of the Library
with which the Combined Work was made is also called the "Linked
Version".

The "Minimal Corresponding Source" for a Combined Work means the
Corresponding Source for the Combined Work, excluding any source code
for portions of the Combined Work that, considered in isolation, are
based on the Application, and not on the Linked Version.

The "Corresponding Application Code" for a Combined Work means the
object code and/or source code for the Application, including any data
and utility programs needed for reproducing the Combined Work from the
Application, but excluding the System Libraries of the Combined Work.

1. Exception to Section 3 of the GNU GPL.

You may convey a covered work under sections 3 and 4 of this License without being bound by section 3 of the GNU GPL.

2. Conveying Modified Versions.

If you modify a copy of the Library, and, in your modifications, a facility refers to a function or data to be supplied by an Application that uses the facility (other than as an argument passed when the facility is invoked), then you may convey a copy of the modified version:

- a) under this License, provided that you make a good faith effort to ensure that, in the event an Application does not supply the function or data, the facility still operates, and performs whatever part of its purpose remains meaningful, or
- b) under the GNU GPL, with none of the additional permissions of this License applicable to that copy.

3. Object Code Incorporating Material from Library Header Files.

The object code form of an Application may incorporate material from a header file that is part of the Library. You may convey such object code under terms of your choice, provided that, if the incorporated material is not limited to numerical parameters, data structure layouts and accessors, or small macros, inline functions and templates (ten or fewer lines in length), you do both of the following:

- a) Give prominent notice with each copy of the object code that the Library is used in it and that the Library and its use are covered by this License.
- b) Accompany the object code with a copy of the GNU GPL and this license document.

4. Combined Works.

You may convey a Combined Work under terms of your choice that, taken together, effectively do not restrict modification of the portions of the Library contained in the Combined Work and reverse engineering for debugging such modifications, if you also do each of the following:

- a) Give prominent notice with each copy of the Combined Work that the Library is used in it and that the Library and its use are covered by this License.

b) Accompany the Combined Work with a copy of the GNU GPL and this license document.

c) For a Combined Work that displays copyright notices during execution, include the copyright notice for the Library among these notices, as well as a reference directing the user to the copies of the GNU GPL and this license document.

d) Do one of the following:

0) Convey the Minimal Corresponding Source under the terms of this License, and the Corresponding Application Code in a form suitable for, and under terms that permit, the user to recombine or relink the Application with a modified version of the Linked Version to produce a modified Combined Work, in the manner specified by section 6 of the GNU GPL for conveying Corresponding Source.

1) Use a suitable shared library mechanism for linking with the Library. A suitable mechanism is one that (a) uses at run time a copy of the Library already present on the user's computer system, and (b) will operate properly with a modified version of the Library that is interface-compatible with the Linked Version.

e) Provide Installation Information, but only if you would otherwise be required to provide such information under section 6 of the GNU GPL, and only to the extent that such information is necessary to install and execute a modified version of the Combined Work produced by recombining or relinking the Application with a modified version of the Linked Version. (If you use option 4d0, the Installation Information must accompany the Minimal Corresponding Source and Corresponding Application Code. If you use option 4d1, you must provide the Installation Information in the manner specified by section 6 of the GNU GPL for conveying Corresponding Source.)

5. Combined Libraries.

You may place library facilities that are a work based on the Library side by side in a single library together with other library facilities that are not Applications and are not covered by this License, and convey such a combined library under terms of your choice, if you do both of the following:

a) Accompany the combined library with a copy of the same work based on the Library, uncombined with any other library facilities, conveyed under the terms of this License.

b) Give prominent notice with the combined library that part of it is a work based on the Library, and explaining where to find the accompanying uncombined form of the same work.

6. Revised Versions of the GNU Lesser General Public License.

The Free Software Foundation may publish revised and/or new versions of the GNU Lesser General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Library as you received it specifies that a certain numbered version of the GNU Lesser General Public License "or any later version" applies to it, you have the option of following the terms and conditions either of that published version or of any later version published by the Free Software Foundation. If the Library as you received it does not specify a version number of the GNU Lesser General Public License, you may choose any version of the GNU Lesser General Public License ever published by the Free Software Foundation.

If the Library as you received it specifies that a proxy can decide whether future versions of the GNU Lesser General Public License shall apply, that proxy's public statement of acceptance of any version is permanent authorization for you to choose that version for the Library.

Copyright (C) 1992-2015 by Bruce Korb - all rights reserved
Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

1. Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.
2. Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.
3. The name of the author may not be used to endorse or promote products derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE AUTHOR ``AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE AUTHOR BE LIABLE FOR ANY DIRECT, INDIRECT,

INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

GNU GENERAL PUBLIC LICENSE

Version 3, 29 June 2007

Copyright (C) 2007 Free Software Foundation, Inc. <<http://fsf.org/>>

Everyone is permitted to copy and distribute verbatim copies of this license document, but changing it is not allowed.

Preamble

The GNU General Public License is a free, copyleft license for software and other kinds of works.

The licenses for most software and other practical works are designed to take away your freedom to share and change the works. By contrast, the GNU General Public License is intended to guarantee your freedom to share and change all versions of a program--to make sure it remains free software for all its users. We, the Free Software Foundation, use the GNU General Public License for most of our software; it applies also to any other work released this way by its authors. You can apply it to your programs, too.

When we speak of free software, we are referring to freedom, not price. Our General Public Licenses are designed to make sure that you have the freedom to distribute copies of free software (and charge for them if you wish), that you receive source code or can get it if you want it, that you can change the software or use pieces of it in new free programs, and that you know you can do these things.

To protect your rights, we need to prevent others from denying you these rights or asking you to surrender the rights. Therefore, you have certain responsibilities if you distribute copies of the software, or if you modify it: responsibilities to respect the freedom of others.

For example, if you distribute copies of such a program, whether gratis or for a fee, you must pass on to the recipients the same

freedoms that you received. You must make sure that they, too, receive or can get the source code. And you must show them these terms so they know their rights.

Developers that use the GNU GPL protect your rights with two steps:

(1)

assert copyright on the software, and (2) offer you this License giving you legal permission to copy, distribute and/or modify it.

For the developers' and authors' protection, the GPL clearly explains that there is no warranty for this free software. For both users' and authors' sake, the GPL requires that modified versions be marked as changed, so that their problems will not be attributed erroneously to authors of previous versions.

Some devices are designed to deny users access to install or run modified versions of the software inside them, although the manufacturer can do so. This is fundamentally incompatible with the aim of protecting users' freedom to change the software. The systematic pattern of such abuse occurs in the area of products for individuals to use, which is precisely where it is most unacceptable. Therefore, we have designed this version of the GPL to prohibit the practice for those products. If such problems arise substantially in other domains, we stand

ready to extend this provision to those domains in future versions of the GPL, as needed to protect the freedom of users.

Finally, every program is threatened constantly by software patents. States should not allow patents to restrict development and use of software on general-purpose computers, but in those that do, we wish to avoid the special danger that patents applied to a free program could make it effectively proprietary. To prevent this, the GPL assures that patents cannot be used to render the program non-free.

The precise terms and conditions for copying, distribution and modification follow.

TERMS AND CONDITIONS

0. Definitions.

"This License" refers to version 3 of the GNU General Public License.

"Copyright" also means copyright-like laws that apply to other kinds of works, such as semiconductor masks.

"The Program" refers to any copyrightable work licensed under this License. Each licensee is addressed as "you". "Licensees"

and

"recipients" may be individuals or organizations.

To "modify" a work means to copy from or adapt all or part of the work in a fashion requiring copyright permission, other than the making of an exact copy. The resulting work is called a "modified version" of the earlier work or a work "based on" the earlier work.

A "covered work" means either the unmodified Program or a work based on the Program.

To "propagate" a work means to do anything with it that, without permission, would make you directly or secondarily liable for infringement under applicable copyright law, except executing it on a computer or modifying a private copy. Propagation includes copying, distribution (with or without modification), making available to the public, and in some countries other activities as well.

To "convey" a work means any kind of propagation that enables other parties to make or receive copies. Mere interaction with a user through a computer network, with no transfer of a copy, is not conveying.

An interactive user interface displays "Appropriate Legal Notices" to the extent that it includes a convenient and prominently visible feature that (1) displays an appropriate copyright notice, and (2) tells the user that there is no warranty for the work (except to the extent that warranties are provided), that licensees may convey the work under this License, and how to view a copy of this License. If the interface presents a list of user commands or options, such as a menu, a prominent item in the list meets this criterion.

1. Source Code.

The "source code" for a work means the preferred form of the work for making modifications to it. "Object code" means any non-source form of a work.

A "Standard Interface" means an interface that either is an official standard defined by a recognized standards body, or, in the case of interfaces specified for a particular programming language, one that is widely used among developers working in that language.

The

"System Libraries" of an executable work include anything, other than the work as a whole, that (a) is included in the normal form of packaging a Major Component, but which is not part of that Major Component, and (b) serves only to enable use of the work with that

Major Component, or to implement a Standard Interface for which an implementation is available to the public in source code form. A "Major Component", in this context, means a major essential component (kernel, window system, and so on) of the specific operating system (if any) on which the executable work runs, or a compiler used to produce the work, or an object code interpreter used to run it.

The "Corresponding Source" for a work in object code form means all the source code needed to generate, install, and (for an executable work) run the object code and to modify the work, including scripts to control those activities. However, it does not include the work's System Libraries, or general-purpose tools or generally available free programs which are used unmodified in performing those activities but which are not part of the work. For example, Corresponding Source includes interface definition files associated with source files for the work, and the source code for shared libraries and dynamically linked subprograms that the work is specifically designed to require, such as by intimate data communication or control flow between those subprograms and other parts of the work.

The Corresponding Source need not include anything that users can regenerate automatically from other parts of the Corresponding Source.

The Corresponding Source for a work in source code form is that same work.

2. Basic Permissions.

All rights granted under this License are granted for the term of copyright on the Program, and are irrevocable provided the stated conditions are met. This License explicitly affirms your unlimited permission to run the unmodified Program. The output from running a covered work is covered by this License only if the output, given its content, constitutes a covered work. This License acknowledges your rights of fair use or other equivalent, as provided by copyright law.

You may make, run and propagate covered works that you do not convey, without conditions so long as your license otherwise remains in force. You may convey covered works to others for the sole purpose of having them make modifications exclusively for you, or provide you with facilities for running those works, provided that you comply with the terms of this License in conveying all material for which you do not control copyright. Those thus making or running the covered works for you must do so exclusively on your behalf, under your direction and control, on terms that prohibit them from making any copies of

your copyrighted material outside their relationship with you.

Conveying under any other circumstances is permitted solely under the conditions stated below. Sublicensing is not allowed; section 10 makes it unnecessary.

3. Protecting Users' Legal Rights From Anti-Circumvention Law.

No covered work shall be deemed part of an effective technological measure under any applicable law fulfilling obligations under article 11 of the WIPO copyright treaty adopted on 20 December 1996, or similar laws prohibiting or restricting circumvention of such measures.

When you convey a covered work, you waive any legal power to forbid circumvention of technological measures to the extent such circumvention is effected by exercising rights under this License with respect to the covered work, and you disclaim any intention to limit operation or modification of the work as a means of enforcing, against the work's users, your or third parties' legal rights to forbid circumvention of technological measures.

4. Conveying Verbatim Copies.

You may convey verbatim copies of the Program's source code as you receive it, in any medium, provided that you conspicuously and appropriately publish on each copy an appropriate copyright notice; keep intact all notices stating that this License and any non-permissive terms added in accord with section 7 apply to the code; keep intact all notices of the absence of any warranty; and give all recipients a copy of this License along with the Program.

You may charge any price or no price for each copy that you convey, and you may offer support or warranty protection for a fee.

5. Conveying Modified Source Versions.

You may convey a work based on the Program, or the modifications to produce it from the Program, in the form of source code under the terms of section 4, provided that you also meet all of these conditions:

a) The work must carry prominent notices stating that you modified it, and giving a relevant date.

b) The work must carry prominent notices stating that it is released under this License and any conditions added under section

7. This requirement modifies the requirement in section 4 to

"keep intact all notices".

c) You must license the entire work, as a whole, under this License to anyone who comes into possession of a copy. This License will therefore apply, along with any applicable section 7 additional terms, to the whole of the work, and all its parts, regardless of how they are packaged. This License gives no permission to license the work in any other way, but it does not invalidate such permission if you have separately received it.

d) If the work has interactive user interfaces, each must display Appropriate Legal Notices; however, if the Program has interactive interfaces that do not display Appropriate Legal Notices, your work need not make them do so.

A compilation of a covered work with other separate and independent works, which are not by their nature extensions of the covered work, and which are not combined with it such as to form a larger program, in or on a volume of a storage or distribution medium, is called an "aggregate" if the compilation and its resulting copyright are not used to limit the access or legal rights of the compilation's users beyond what the individual works permit. Inclusion of a covered work in an aggregate does not cause this License to apply to the other parts of the aggregate.

6. Conveying Non-Source Forms.

You may convey a covered work in object code form under the terms of sections 4 and 5, provided that you also convey the machine-readable Corresponding Source under the terms of this License, in one of these ways:

a) Convey the object code in, or embodied in, a physical product (including a physical distribution medium), accompanied by the Corresponding Source fixed on a durable physical medium customarily used for software interchange.

b) Convey the object code in, or embodied in, a physical product (including a physical distribution medium), accompanied by a written offer, valid for at least three years and valid for as long as you offer spare parts or customer support for that product model, to give anyone who possesses the object code either (1) a copy of the Corresponding Source for all the software in the product that is covered by this License, on a durable physical

medium customarily used for software interchange, for a price no more than your reasonable cost of physically performing this conveying of source, or (2) access to copy the Corresponding Source from a network server at no charge.

c) Convey individual copies of the object code with a copy of the written offer to provide the Corresponding Source. This alternative is allowed only occasionally and noncommercially, and only if you received the object code with such an offer, in accord with subsection 6b.

d) Convey the object code by offering access from a designated place (gratis or for a charge), and offer equivalent access to the Corresponding Source in the same way through the same place at no further charge. You need not require recipients to copy the Corresponding Source along with the object code. If the place to copy the object code is a network server, the Corresponding Source may be on a different server (operated by you or a third party) that supports equivalent copying facilities, provided you maintain clear directions next to the object code saying where to find the Corresponding Source. Regardless of what server hosts the Corresponding Source, you remain obligated to ensure that it is available for as long as needed to satisfy these requirements.

e) Convey the object code using peer-to-peer transmission, provided you inform other peers where the object code and Corresponding Source of the work are being offered to the general public at no charge under subsection 6d.

A separable portion of the object code, whose source code is excluded from the Corresponding Source as a System Library, need not be included in conveying the object code work.

A "User Product" is either (1) a "consumer product", which means any tangible personal property which is normally used for personal, family, or household purposes, or (2) anything designed or sold for incorporation into a dwelling. In determining whether a product is a consumer product, doubtful cases shall be resolved in favor of coverage. For a particular product received by a particular user, "normally used" refers to a typical or common use of that class of product, regardless of the status of the particular user or of the way in which the particular user actually uses, or expects or is expected to use, the product. A product is a consumer product regardless of whether the product has substantial commercial, industrial or non-consumer uses, unless such uses represent the only significant mode of use of the product.

"Installation Information" for a User Product means any methods, procedures, authorization keys, or other information required to install and execute modified versions of a covered work in that User Product from a modified version of its Corresponding Source. The information must suffice to ensure that the continued functioning of the modified object code is in no case prevented or interfered with solely because modification has been made.

If you convey an object code work under this section in, or with, or specifically for use in, a User Product, and the conveying occurs as part of a transaction in which the right of possession and use of the User Product is transferred to the recipient in perpetuity or for a fixed term (regardless of how the transaction is characterized), the Corresponding Source conveyed under this section must be accompanied by the Installation Information. But this requirement does not apply if neither you nor any third party retains the ability to install modified object code on the User Product (for example, the work has been installed in ROM).

The requirement to provide Installation Information does not include a requirement to continue to provide support service, warranty, or updates for a work that has been modified or installed by the recipient, or for the User Product in which it has been modified or installed. Access to a network may be denied when the modification itself materially and adversely affects the operation of the network or violates the rules and protocols for communication across the network.

Corresponding Source conveyed, and Installation Information provided, in accord with this section must be in a format that is publicly documented (and with an implementation available to the public in source code form), and must require no special password or key for unpacking, reading or copying.

7. Additional Terms.

"Additional permissions" are terms that supplement the terms of this License by making exceptions from one or more of its conditions. Additional permissions that are applicable to the entire Program shall be treated as though they were included in this License, to the extent that they are valid under applicable law. If additional permissions apply only to part of the Program, that part may be used separately under those permissions, but the entire Program remains governed by this License without regard to the additional permissions.

When you convey a copy of a covered work, you may at your option

remove any additional permissions from that copy, or from any part of it. (Additional permissions may be written to require their own removal in certain cases when you modify the work.) You may place additional permissions on material, added by you to a covered work, for which you have or can give appropriate copyright permission.

Notwithstanding any other provision of this License, for material you add to a covered work, you may (if authorized by the copyright holders of that material) supplement the terms of this License with terms:

- a) Disclaiming warranty or limiting liability differently from the terms of sections 15 and 16 of this License; or
- b) Requiring preservation of specified reasonable legal notices or author attributions in that material or in the Appropriate Legal Notices displayed by works containing it; or
- c) Prohibiting misrepresentation of the origin of that material, or requiring that modified versions of such material be marked in reasonable ways as different from the original version; or
- d) Limiting the use for publicity purposes of names of licensors or authors of the material; or
- e) Declining to grant rights under trademark law for use of some trade names, trademarks, or service marks; or
- f) Requiring indemnification of licensors and authors of that material by anyone who conveys the material (or modified versions of it) with contractual assumptions of liability to the recipient, for any liability that these contractual assumptions directly impose on those licensors and authors.

All other non-permissive additional terms are considered "further restrictions" within the meaning of section 10. If the Program as you received it, or any part of it, contains a notice stating that it is governed by this License along with a term that is a further restriction, you may remove that term. If a license document contains a further restriction but permits relicensing or conveying under this License, you may add to a covered work material governed by the terms of that license document, provided that the further restriction does not survive such relicensing or conveying.

If you add terms to a covered work in accord with this section, you must place, in the relevant source files, a statement of the additional terms that apply to those files, or a notice indicating

where to find the applicable terms.

Additional terms, permissive or non-permissive, may be stated in the form of a separately written license, or stated as exceptions; the above requirements apply either way.

8. Termination.

You may not propagate or modify a covered work except as expressly provided under this License. Any attempt otherwise to propagate or modify it is void, and will automatically terminate your rights under this License (including any patent licenses granted under the third paragraph of section 11).

However, if you cease all violation of this License, then your license from a particular copyright holder is reinstated (a) provisionally, unless and until the copyright holder explicitly and finally terminates your license, and (b) permanently, if the copyright holder fails to notify you of the violation by some reasonable means prior to 60 days after the cessation.

Moreover, your license from a particular copyright holder is reinstated permanently if the copyright holder notifies you of the violation by some reasonable means, this is the first time you have received notice of violation of this License (for any work) from that copyright holder, and you cure the violation prior to 30 days after your receipt of the notice.

Termination of your rights under this section does not terminate the licenses of parties who have received copies or rights from you under this License. If your rights have been terminated and not permanently reinstated, you do not qualify to receive new licenses for the same material under section 10.

9. Acceptance Not Required for Having Copies.

You are not required to accept this License in order to receive or run a copy of the Program. Ancillary propagation of a covered work occurring solely as a consequence of using peer-to-peer transmission to receive a copy likewise does not require acceptance. However, nothing other than this License grants you permission to propagate or modify any covered work. These actions infringe copyright if you do not accept this License. Therefore, by modifying or propagating a covered work, you indicate your acceptance of this License to do so.

10. Automatic Licensing of Downstream Recipients.

Each time you convey a covered work, the recipient automatically receives a license from the original licensors, to run, modify and propagate that work, subject to this License. You are not responsible for enforcing compliance by third parties with this License.

An "entity transaction" is a transaction transferring control of an organization, or substantially all assets of one, or subdividing an organization, or merging organizations. If propagation of a covered work results from an entity transaction, each party to that transaction who receives a copy of the work also receives whatever licenses to the work the party's predecessor in interest had or could give under the previous paragraph, plus a right to possession of the Corresponding Source of the work from the predecessor in interest, if the predecessor has it or can get it with reasonable efforts.

You may not impose any further restrictions on the exercise of the rights

granted or affirmed under this License. For example, you may not impose a license fee, royalty, or other charge for exercise of rights granted under this License, and you may not initiate litigation (including a cross-claim or counterclaim in a lawsuit) alleging that any patent claim is infringed by making, using, selling, offering for sale, or importing the Program or any portion of it.

11. Patents.

A "contributor" is a copyright holder who authorizes use under this License of the Program or a work on which the Program is based. The work thus licensed is called the contributor's "contributor version".

A contributor's "essential patent claims" are all patent claims owned or controlled by the contributor, whether already acquired or hereafter acquired, that would be infringed by some manner, permitted by this License, of making, using, or selling its contributor version, but do not include claims that would be infringed only as a consequence of further modification of the contributor version. For purposes of this definition, "control" includes the right to grant patent sublicenses in a manner consistent with the requirements of this License.

Each contributor grants you a non-exclusive, worldwide, royalty-free patent license under the contributor's essential patent claims, to make, use, sell, offer for sale, import and otherwise run, modify and propagate the contents of its contributor version.

In the following three paragraphs, a "patent license" is any express agreement or commitment, however denominated, not to enforce a patent (such as an express permission to practice a patent or covenant not to sue for patent infringement). To "grant" such a patent license to a party means to make such an agreement or commitment not to enforce a patent against the party.

If you convey a covered work, knowingly relying on a patent license, and the Corresponding Source of the work is not available for anyone to copy, free of charge and under the terms of this

License, through a publicly available network server or other readily accessible means, then you must either (1) cause the Corresponding Source to be so available, or (2) arrange to deprive yourself of the benefit of the patent license for this particular work, or (3) arrange, in a manner consistent with the requirements of this License, to extend the patent license to downstream recipients. "Knowingly relying" means you have actual knowledge that, but for the patent license, your conveying the covered work in a country, or your recipient's use of the covered work in a country, would infringe one or more identifiable patents in that country that you have reason to believe are valid.

If, pursuant to or in connection with a single transaction or arrangement, you convey, or propagate by procuring conveyance of, a covered work, and grant a patent license to some of the parties receiving the covered work authorizing them to use, propagate, modify or convey a specific copy of the covered work, then the patent license you grant is automatically extended to all recipients of the covered work and works based on it.

A patent license is "discriminatory" if it does not include within the scope of its coverage, prohibits the exercise of, or is conditioned on the non-exercise of one or more of the rights that are specifically granted under this License. You may not convey a covered work if you are a party to an arrangement with a third party that is in the business of distributing software, under which you make payment to the third party based on the extent of your activity of conveying the work, and under which the third party grants, to any of the parties who would receive the covered work from you, a discriminatory patent license (a) in connection with copies of the covered work conveyed by you (or copies made from those copies), or (b) primarily for and in connection with specific products or compilations that contain the covered work, unless you entered into that arrangement, or that patent license was granted, prior to 28 March 2007.

Nothing in this License shall be construed as excluding or limiting

any implied license or other defenses to infringement that may otherwise be available to you under applicable patent law.

12. No Surrender of Others' Freedom.

If conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot convey a covered work so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not convey it at all. For example, if you agree to terms that obligate you to collect a royalty for further conveying from those to whom you convey the Program, the only way you could satisfy both those terms and this License would be to refrain entirely from conveying the Program.

13. Use with the GNU Affero General Public License.

Notwithstanding any other provision of this License, you have permission to link or combine any covered work with a work licensed under version 3 of the GNU Affero General Public License into a single combined work, and to convey the resulting work. The terms of this License will continue to apply to the part which is the covered work, but the special requirements of the GNU Affero General Public License, section 13, concerning interaction through a network will apply to the combination as such.

14. Revised Versions of this License.

The Free Software Foundation may publish revised and/or new versions of the GNU General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Program specifies that a certain numbered version of the GNU General Public License "or any later version" applies to it, you have the option of following the terms and conditions either of that numbered version or of any later version published by the Free Software Foundation. If the Program does not specify a version number of the GNU General Public License, you may choose any version ever published by the Free Software Foundation.

If the Program specifies that a proxy can decide which future versions of the GNU General Public License can be used, that proxy's public statement of acceptance of a version permanently authorizes you to choose that version for the Program.

Later license versions may give you additional or different permissions. However, no additional obligations are imposed on any author or copyright holder as a result of your choosing to follow a later version.

15. Disclaimer of Warranty.

THERE IS NO WARRANTY FOR THE PROGRAM, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE PROGRAM "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE PROGRAM IS WITH YOU. SHOULD THE PROGRAM PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

16. Limitation of Liability.

IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MODIFIES AND/OR CONVEYS THE PROGRAM AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE PROGRAM (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE PROGRAM TO OPERATE WITH ANY OTHER PROGRAMS), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

17.

Interpretation of Sections 15 and 16.

If the disclaimer of warranty and limitation of liability provided above cannot be given local legal effect according to their terms, reviewing courts shall apply local law that most closely approximates an absolute waiver of all civil liability in connection with the Program, unless a warranty or assumption of liability accompanies a copy of the Program in return for a fee.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Programs

If you develop a new program, and you want it to be of the greatest possible use to the public, the best way to achieve this is to make it free software which everyone can redistribute and change under these terms.

To do so, attach the following notices to the program. It is safest

to attach them to the start of each source file to most effectively state the exclusion of warranty; and each file should have at least the "copyright" line and a pointer to where the full notice is found.

```
<one line to give the program's name and a brief idea of what it does.>  
Copyright (C) <year> <name of author>
```

This program is free software: you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation, either version 3 of the License, or (at your option) any later version.

This program is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details.

You should have received a copy of the GNU General Public License along with this program. If not, see <http://www.gnu.org/licenses/>.

Also add information on how to contact you by electronic and paper mail.

If the program does terminal interaction, make it output a short notice like this when it starts in an interactive mode:

```
<program> Copyright (C) <year> <name of author>  
This program comes with ABSOLUTELY NO WARRANTY; for details type `show w'.  
This is free software, and you are welcome to redistribute it  
under certain conditions; type `show c' for details.
```

The hypothetical commands `show w' and `show c' should show the appropriate parts of the General Public License. Of course, your program's commands might be different; for a GUI interface, you would use an "about box".

You should also get your employer (if you work as a programmer) or school, if any, to sign a "copyright disclaimer" for the program, if necessary. For more information on this, and how to apply and follow the GNU GPL, see <http://www.gnu.org/licenses/>.

The GNU General Public License does not permit incorporating your program into proprietary programs. If your program is a subroutine library, you may consider it more useful to permit linking proprietary applications with the library. If this is what you want to do, use the GNU Lesser General Public License instead of this License. But first, please read <http://www.gnu.org/philosophy/why-not-lgpl.html>.

The MIT License (MIT)

Copyright (c) 2016 Wrymouth Innovation Ltd

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

GNU GENERAL PUBLIC LICENSE
Version 3, 29 June 2007

Copyright (C) 1992-2015 by Bruce Korb - all rights reserved
Everyone is permitted to copy and distribute verbatim copies of this license document, but changing it is not allowed.

Preamble

The GNU General Public License is a free, copyleft license for software and other kinds of works.

The licenses for most software and other practical works are designed to take away your freedom to share and change the works. By contrast, the GNU General Public License is intended to guarantee your freedom to share and change all versions of a program--to make sure it remains free software for all its users. We, the Free Software Foundation, use the GNU General Public License for most of our software; it applies also to any other work released this way by its authors. You can apply it to your programs, too.

When we speak of free software, we are referring to freedom, not price. Our General Public Licenses are designed to make sure that you have the freedom to distribute copies of free software (and charge for them if you wish), that you receive source code or can get it if you

want it, that you can change the software or use pieces of it in new free programs, and that you know you can do these things.

To protect your rights, we need to prevent others from denying you these rights or asking you to surrender the rights. Therefore, you have certain responsibilities if you distribute copies of the software, or if you modify it: responsibilities to respect the freedom of others.

For example, if you distribute copies of such a program, whether gratis or for a fee, you must pass on to the recipients the same freedoms that you received. You must make sure that they, too, receive or can get the source code. And you must show them these terms so they know their rights.

Developers that use the GNU GPL protect your rights with two steps: (1) assert copyright on the software, and (2) offer you this License giving you legal permission to copy, distribute and/or modify it.

For the developers' and authors' protection, the GPL clearly explains that there is no warranty for this free software. For both users' and authors' sake, the GPL requires that modified versions be marked as changed, so that their problems will not be attributed erroneously to authors of previous versions.

Some devices are designed to deny users access to install or run modified versions of the software inside them, although the manufacturer can do so. This is fundamentally incompatible with the aim of protecting users' freedom to change the software. The systematic pattern of such abuse occurs in the area of products for individuals to use, which is precisely where it is most unacceptable. Therefore, we have designed this version of the GPL to prohibit the practice for those products. If such problems arise substantially in other domains, we stand ready to extend this provision to those domains in future versions of the GPL, as needed to protect the freedom of users.

Finally, every program is threatened constantly by software patents. States should not allow patents to restrict development and use of software on general-purpose computers, but in those that do, we wish to avoid the special danger that patents applied to a free program could make it effectively proprietary. To prevent this, the GPL assures that patents cannot be used to render the program non-free.

The precise terms and conditions for copying, distribution and modification follow.

TERMS AND CONDITIONS

0. Definitions.

"This License" refers to version 3 of the GNU General Public License.

"Copyright" also means copyright-like laws that apply to other kinds of works, such as semiconductor masks.

"The Program" refers to any copyrightable work licensed under this License. Each licensee is addressed as "you". "Licensees" and "recipients" may be individuals or organizations.

To "modify" a work means to copy from or adapt all or part of the work in a fashion requiring copyright permission, other than the making of an exact copy. The resulting work is called a "modified version" of the earlier work or a work "based on" the earlier work.

A "covered work" means either the unmodified Program or a work based on the Program.

To "propagate" a work means to do anything with it that, without permission, would make you directly or secondarily liable for infringement under applicable copyright law, except executing it on a computer or modifying a private copy. Propagation includes copying, distribution (with or without modification), making available to the public, and in some countries other activities as well.

To "convey" a work means any kind of propagation that enables other parties to make or receive copies. Mere interaction with a user through a computer network, with no transfer of a copy, is not conveying.

An interactive user interface displays "Appropriate Legal Notices" to the extent that it includes a convenient and prominently visible feature that (1) displays an appropriate copyright notice, and (2) tells the user that there is no warranty for the work (except to the extent that warranties are provided), that licensees may convey the work under this License, and how to view a copy of this License. If the interface presents a list of user commands or options, such as a menu, a prominent item in the list meets this criterion.

1. Source Code.

The "source code" for a work means the preferred form of the work for making modifications to it. "Object code" means any non-source form of a work.

A "Standard Interface" means an interface that either is an official

standard defined by a recognized standards body, or, in the case of interfaces specified for a particular programming language, one that is widely used among developers working in that language.

The "System

Libraries" of an executable work include anything, other than the work as a whole, that (a) is included in the normal form of packaging a Major Component, but which is not part of that Major Component, and (b) serves only to enable use of the work with that Major Component, or to implement a Standard Interface for which an implementation is available to the public in source code form. A "Major Component", in this context, means a major essential component (kernel, window system, and so on) of the specific operating system (if any) on which the executable work runs, or a compiler used to produce the work, or an object code interpreter used to run it.

The "Corresponding Source" for a work in object code form means all the source code needed to generate, install, and (for an executable work) run the object code and to modify the work, including scripts to control those activities. However, it does not include the work's System Libraries, or general-purpose tools or generally available free programs which are used unmodified in performing those activities but which are not part of the work. For example, Corresponding Source includes interface definition files associated with source files for the work, and the source code for shared libraries and dynamically linked subprograms that the work is specifically designed to require, such as by intimate data communication or control flow between those subprograms and other parts of the work.

The Corresponding Source need not include anything that users can regenerate automatically from other parts of the Corresponding Source.

The Corresponding Source for a work in source code form is that same work.

2. Basic Permissions.

All rights granted under this License are granted for the term of copyright on the Program, and are irrevocable provided the stated conditions are met. This License explicitly affirms your unlimited permission to run the unmodified Program. The output from running a covered work is covered by this License only if the output, given its content, constitutes a covered work. This License acknowledges your rights of fair use or other equivalent, as provided by copyright law.

You may make, run and propagate covered works that you do not convey, without conditions so long as your license otherwise remains in force. You may convey covered works to others for the sole purpose of having them make modifications exclusively for you, or provide you with facilities for running those works, provided that you comply with the terms of this License in conveying all material for which you do not control copyright. Those thus making or running the covered works for you must do so exclusively on your behalf, under your direction and control, on terms that prohibit them from making any copies of your copyrighted material outside their relationship with you.

Conveying under any other circumstances is permitted solely under the conditions stated below. Sublicensing is not allowed; section 10 makes it unnecessary.

3. Protecting Users' Legal Rights From Anti-Circumvention Law.

No covered work shall be deemed part of an effective technological measure under any applicable law fulfilling obligations under article 11 of the WIPO copyright treaty adopted on 20 December 1996, or similar laws prohibiting or restricting circumvention of such measures.

When you convey a covered work, you waive any legal power to forbid circumvention of technological measures to the extent such circumvention is effected by exercising rights under this License with respect to the covered work, and you disclaim any intention to limit operation or modification of the work as a means of enforcing, against the work's users, your or third parties' legal rights to forbid circumvention of technological measures.

4. Conveying Verbatim Copies.

You may convey verbatim copies of the Program's source code as you receive it, in any medium, provided that you conspicuously and appropriately publish on each copy an appropriate copyright notice; keep intact all notices stating that this License and any non-permissive terms added in accord with section 7 apply to the code; keep intact all notices of the absence of any warranty; and give all recipients a copy of this License along with the Program.

You may charge any price or no price for each copy that you convey, and you may offer support or warranty protection for a fee.

5. Conveying Modified Source Versions.

You may convey a work based on the Program, or the modifications to produce it from the Program, in the form of source code under the terms of section 4, provided that you also meet all of these conditions:

- a) The work must carry prominent notices stating that you modified it, and giving a relevant date.
- b) The work must carry prominent notices stating that it is released under this License and any conditions added under section 7. This requirement modifies the requirement in section 4 to "keep intact all notices".
- c) You must license the entire work, as a whole, under this License to anyone who comes into possession of a copy. This License will therefore apply, along with any applicable section 7 additional terms, to the whole of the work, and all its parts, regardless of how they are packaged. This License gives no permission to license the work in any other way, but it does not invalidate such permission if you have separately received it.
- d) If the work has interactive user interfaces, each must display Appropriate Legal Notices; however, if the Program has interactive interfaces that do not display Appropriate Legal Notices, your work need not make them do so.

A compilation of a covered work with other separate and independent works, which are not by their nature extensions of the covered work, and which are not combined with it such as to form a larger program, in or on a volume of a storage or distribution medium, is called an "aggregate" if the compilation and its resulting copyright are not used to limit the access or legal rights of the compilation's users beyond what the individual works permit. Inclusion of a covered work in an aggregate does not cause this License to apply to the other parts of the aggregate.

6. Conveying Non-Source Forms.

You may convey a covered work in object code form under the terms of sections 4 and 5, provided that you also convey the machine-readable Corresponding Source under the terms of this License, in one of these ways:

- a) Convey the object code in, or embodied in, a physical product (including a physical distribution medium), accompanied by the Corresponding Source fixed on a durable physical medium customarily used for software interchange.

b) Convey the object code in, or embodied in, a physical product (including a physical distribution medium), accompanied by a written offer, valid for at least three years and valid for as

long as you offer spare parts or customer support for that product model, to give anyone who possesses the object code either (1) a copy of the Corresponding Source for all the software in the product that is covered by this License, on a durable physical medium customarily used for software interchange, for a price no more than your reasonable cost of physically performing this conveying of source, or (2) access to copy the Corresponding Source from a network server at no charge.

c) Convey individual copies of the object code with a copy of the written offer to provide the Corresponding Source. This alternative is allowed only occasionally and noncommercially, and only if you received the object code with such an offer, in accord with subsection 6b.

d) Convey the object code by offering access from a designated place (gratis or for a charge), and offer equivalent access to the Corresponding Source in the same way through the same place at no further charge. You need not require recipients to copy the Corresponding Source along with the object code. If the place to copy the object code is a network server, the Corresponding Source may be on a different server (operated by you or a third party) that supports equivalent copying facilities, provided you maintain clear directions next to the object code saying where to find the Corresponding Source. Regardless of what server hosts the Corresponding Source, you remain obligated to ensure that it is available for as long as needed to satisfy these requirements.

e) Convey the object code using peer-to-peer transmission, provided you inform other peers where the object code and Corresponding Source of the work are being offered to the general public at no charge under subsection 6d.

A separable portion of the object code, whose source code is excluded from the Corresponding Source as a System Library, need not be included in conveying the object code work.

A "User Product" is either (1) a "consumer product", which means any tangible personal property which is normally used for personal, family, or household purposes, or (2) anything designed or sold for incorporation into a dwelling. In determining whether a product is a consumer product, doubtful cases shall be resolved in favor of coverage. For a particular

product received by a particular user, "normally used" refers to a typical or common use of that class of product, regardless of the status of the particular user or of the way in which the particular user actually uses, or expects or is expected to use, the product. A product is a consumer product regardless of whether the product has substantial commercial, industrial or non-consumer uses, unless such uses represent the only significant mode of use of the product.

"Installation Information" for a User Product means any methods, procedures, authorization keys, or other information required to install and execute modified versions of a covered work in that User Product from a modified version of its Corresponding Source. The information must suffice to ensure that the continued functioning of the modified object code is in no case prevented or interfered with solely because modification has been made.

If you convey an object code work under this section in, or with, or specifically for use in, a User Product, and the conveying occurs as part of a transaction in which the right of possession and use of the User Product is transferred to the recipient in perpetuity or for a fixed term (regardless of how the transaction is characterized), the Corresponding Source conveyed under this section must be accompanied by the Installation Information. But this requirement does not apply if neither you nor any third party retains the ability to install modified object code on the User Product (for example, the work has been installed in ROM).

The requirement to provide Installation Information does not include a requirement to continue to provide support service, warranty, or updates for a work that has been modified or installed by the recipient, or for the User Product in which it has been modified or installed. Access to a network may be denied when the modification itself materially and adversely affects the operation of the network or violates the rules and protocols for communication across the network.

Corresponding Source conveyed, and Installation Information provided, in accord with this section must be in a format that is publicly documented (and with an implementation available to the public in source code form), and must require no special password or key for unpacking, reading or copying.

7. Additional Terms.

"Additional permissions" are terms that supplement the terms of this License by making exceptions from one or more of its conditions. Additional permissions that are applicable to the entire Program

shall

be treated as though they were included in this License, to the extent that they are valid under applicable law. If additional permissions apply only to part of the Program, that part may be used separately under those permissions, but the entire Program remains governed by this License without regard to the additional permissions.

When you convey a copy of a covered work, you may at your option remove any additional permissions from that copy, or from any part of it. (Additional permissions may be written to require their own removal in certain cases when you modify the work.) You may place additional permissions on material, added by you to a covered work, for which you have or can give appropriate copyright permission.

Notwithstanding any other provision of this License, for material you add to a covered work, you may (if authorized by the copyright holders of that material) supplement the terms of this License with terms:

- a) Disclaiming warranty or limiting liability differently from the terms of sections 15 and 16 of this License; or
- b) Requiring preservation of specified reasonable legal notices or author attributions in that material or in the Appropriate Legal Notices displayed by works containing it; or
- c) Prohibiting misrepresentation of the origin of that material, or requiring that modified versions of such material be marked in reasonable ways as different from the original version; or
- d) Limiting the use for publicity purposes of names of licensors or authors of the material; or
- e) Declining to grant rights under trademark law for use of some trade names, trademarks, or service marks; or
- f) Requiring indemnification of licensors and authors of that material by anyone who conveys the material (or modified versions of it) with contractual assumptions of liability to the recipient, for any liability that these contractual assumptions directly impose on those licensors and authors.

All other non-permissive additional terms are considered "further restrictions" within the meaning of section 10. If the Program as you received it, or any part of it, contains a notice stating that it is governed by this License along with a term that is a further restriction, you may remove that term. If a license document contains

a further restriction but permits relicensing or conveying under this License, you may add to a covered work material governed by the terms of that license document, provided that the further restriction does not survive such relicensing or conveying.

If you add terms to a covered work in accord with this section, you must place, in the relevant source files, a statement of the additional terms that apply to those files, or a notice indicating where to find the applicable terms.

Additional terms, permissive or non-permissive, may be stated in the form of a separately written license, or stated as exceptions; the above requirements apply either way.

8. Termination.

You may not propagate or modify a covered work except as expressly provided under this License. Any attempt otherwise to propagate or modify it is void, and will automatically terminate your rights under this License (including any patent licenses granted under the third paragraph of section 11).

However, if you cease all violation of this License, then your license from a particular copyright holder is reinstated (a) provisionally, unless and until the copyright holder explicitly and finally terminates your license, and (b) permanently, if the copyright holder fails to notify you of the violation by some reasonable means prior to 60 days after the cessation.

Moreover, your license from a particular copyright holder is reinstated permanently if the copyright holder notifies you of the violation by some reasonable means, this is the first time you have received notice of violation of this License (for any work) from that copyright holder, and you cure the violation prior to 30 days after your receipt of the notice.

Termination of your rights under this section does not terminate the licenses of parties who have received copies or rights from you under this License. If your rights have been terminated and not permanently reinstated, you do not qualify to receive new licenses for the same material under section 10.

9. Acceptance Not Required for Having Copies.

You are not required to accept this License in order to receive or run a copy of the Program. Ancillary propagation of a covered work

occurring solely as a consequence of using peer-to-peer transmission to receive a copy likewise does not require acceptance. However, nothing other than this License grants you permission to propagate or modify any covered work. These actions infringe copyright if you do not accept this License. Therefore, by modifying or propagating a covered work, you indicate your acceptance of this License to do so.

10. Automatic

Licensing of Downstream Recipients.

Each time you convey a covered work, the recipient automatically receives a license from the original licensors, to run, modify and propagate that work, subject to this License. You are not responsible for enforcing compliance by third parties with this License.

An "entity transaction" is a transaction transferring control of an organization, or substantially all assets of one, or subdividing an organization, or merging organizations. If propagation of a covered work results from an entity transaction, each party to that transaction who receives a copy of the work also receives whatever licenses to the work the party's predecessor in interest had or could give under the previous paragraph, plus a right to possession of the Corresponding Source of the work from the predecessor in interest, if the predecessor has it or can get it with reasonable efforts.

You may not impose any further restrictions on the exercise of the rights granted

or affirmed under this License. For example, you may not impose a license fee, royalty, or other charge for exercise of rights granted under this License, and you may not initiate litigation (including a cross-claim or counterclaim in a lawsuit) alleging that any patent claim is infringed by making, using, selling, offering for sale, or importing the Program or any portion of it.

11. Patents.

A "contributor" is a copyright holder who authorizes use under this License of the Program or a work on which the Program is based. The work thus licensed is called the contributor's "contributor version".

A contributor's "essential patent claims" are all patent claims owned or controlled by the contributor, whether already acquired or hereafter acquired, that would be infringed by some manner, permitted by this License, of making, using, or selling its contributor version, but do not include claims that would be infringed only as a consequence of further modification of the contributor version. For purposes of this definition, "control" includes the right to grant

patent sublicenses in a manner consistent with the requirements of this License.

Each contributor grants you a non-exclusive, worldwide, royalty-free patent license under the contributor's essential patent claims, to make, use, sell, offer for sale, import and otherwise run, modify and propagate the contents of its contributor version.

In the following three paragraphs, a "patent license" is any express agreement or commitment, however denominated, not to enforce a patent (such as an express permission to practice a patent or covenant not to sue for patent infringement). To "grant" such a patent license to a party means to make such an agreement or commitment not to enforce a patent against the party.

If you convey a covered work, knowingly relying on a patent license, and the Corresponding Source of the work is not available for anyone to copy, free of charge and under the terms of this License, through a publicly available network server or other readily accessible means, then you must either (1) cause the Corresponding Source to be so available, or (2) arrange to deprive yourself of the benefit of the patent license for this particular work, or (3) arrange, in a manner consistent with the requirements of this License, to extend the patent license to downstream recipients. "Knowingly relying" means you have actual knowledge that, but for the patent license, your conveying the covered work in a country, or your recipient's use of the covered work in a country, would infringe one or more identifiable patents in that country that you have reason to believe are valid.

If, pursuant to or in connection with a single transaction or arrangement, you convey, or propagate by procuring conveyance of, a covered work, and grant a patent license to some of the parties receiving the covered work authorizing them to use, propagate, modify or convey a specific copy of the covered work, then the patent license you grant is automatically extended to all recipients of the covered work and works based on it.

A patent license is "discriminatory" if it does not include within the scope of its coverage, prohibits the exercise of, or is conditioned on the non-exercise of one or more of the rights that are specifically granted under this License. You may not convey a covered work if you are a party to an arrangement with a third party that is in the business of distributing software, under which you make payment to the third party based on the extent of your activity of conveying the work, and under which the third party grants, to any of the parties who would receive the covered work from you, a discriminatory

patent license (a) in connection with copies of the covered work conveyed by you (or copies made from those copies), or (b) primarily for and in connection with specific products or compilations that contain the covered work, unless you entered into that arrangement, or that patent license was granted, prior to 28 March 2007.

Nothing in this License shall be construed as excluding or limiting any implied license or other defenses to infringement that may otherwise be available to you under applicable patent law.

12. No Surrender of Others' Freedom.

If conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot convey a covered work so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not convey it at all. For example, if you agree to terms that obligate you to collect a royalty for further conveying from those to whom you convey the Program, the only way you could satisfy both those terms and this License would be to refrain entirely from conveying the Program.

13. Use with the GNU Affero General Public License.

Notwithstanding any other provision of this License, you have permission to link or combine any covered work with a work licensed under version 3 of the GNU Affero General Public License into a single combined work, and to convey the resulting work. The terms of this License will continue to apply to the part which is the covered work, but the special requirements of the GNU Affero General Public License, section 13, concerning interaction through a network will apply to the combination as such.

14. Revised Versions of this License.

The Free Software Foundation may publish revised and/or new versions of the GNU General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Program specifies that a certain numbered version of the GNU General Public License "or any later version" applies to it, you have the option of following the terms and conditions either of that numbered version or of any later version published by the Free Software Foundation. If the Program does not specify a version number of the

GNU General Public License, you may choose any version ever published by the Free Software Foundation.

If the Program specifies that a proxy can decide which future versions of the GNU General Public License can be used, that proxy's public statement of acceptance of a version permanently authorizes you to choose that version for the Program.

Later license versions may give you additional or different permissions. However, no additional obligations are imposed on any author or copyright holder as a result of your choosing to follow a later version.

15. Disclaimer of Warranty.

THERE IS NO WARRANTY FOR THE PROGRAM, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE PROGRAM "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE PROGRAM IS WITH YOU. SHOULD THE PROGRAM PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

16. Limitation of Liability.

IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MODIFIES AND/OR CONVEYS THE PROGRAM AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE PROGRAM (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE PROGRAM TO OPERATE WITH ANY OTHER PROGRAMS), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

17. Interpretation of Sections 15 and 16.

If the disclaimer of warranty and limitation of liability provided above cannot be given local legal effect according to their terms, reviewing courts shall apply local law that most closely approximates an absolute waiver of all civil liability in connection with the Program, unless a warranty or assumption of liability accompanies a copy of the Program in return for a fee.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Programs

If you develop a new program, and you want it to be of the greatest possible use to the public, the best way to achieve this is to make it free software which everyone can redistribute and change under these terms.

To do so, attach the following notices to the program. It is safest to attach them to the start of each source file to most effectively state the exclusion of warranty; and each file should have at least the "copyright" line and a pointer to where the full notice is found.

```
<one line to give the program's name and a brief idea of what it does.>  
Copyright (C) by Bruce Korb - all rights reserved
```

```
This program is free software: you can redistribute it and/or modify  
it under the terms of the GNU General Public License as published by  
the Free Software Foundation, either version 3 of the License, or  
(at your option) any later version.
```

```
This program is distributed in the hope that it will be useful,  
but WITHOUT ANY WARRANTY; without even the implied warranty of  
MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the  
GNU General Public License for more details.
```

```
You should have received a copy of the GNU General Public License  
along with this program. If not, see <http://www.gnu.org/licenses/>.
```

Also add information on how to contact you by electronic and paper mail.

If the program does terminal interaction, make it output a short notice like this when it starts in an interactive mode:

```
<program> Copyright (C) by Bruce Korb - all rights reserved  
This program comes with ABSOLUTELY NO WARRANTY; for details type `show w'.  
This is free software, and you are welcome to redistribute it  
under certain conditions; type `show c' for details.
```

The hypothetical commands `show w' and `show c' should show the appropriate parts of the General Public License. Of course, your program's commands might be different; for a GUI interface, you would use an "about box".

You should also get your employer (if you work as a programmer) or school, if any, to sign a "copyright disclaimer" for the program, if necessary. For more information on this, and how to apply and follow the GNU GPL, see <http://www.gnu.org/licenses/>.

The GNU General Public License does not permit incorporating your program into proprietary programs. If your program is a subroutine library, you may consider it more useful to permit linking proprietary applications with the library. If this is what you want to do, use the GNU Lesser General Public License instead of this License. But first, please read <<http://www.gnu.org/philosophy/why-not-lgpl.html>>.

1.87 zlib 1.2.11.dfsg-0ubuntu2.2

1.87.1 Available under license :

No license file was found, but licenses were detected in source scan.

MiniZip - Copyright (c) 1998-2010 - by Gilles Vollant - version 1.1 64 bits from Mathias Svensson

Introduction

MiniZip 1.1 is built from MiniZip 1.0 by Gilles Vollant (<http://www.winimage.com/zLibDll/minizip.html>)

When adding ZIP64 support into minizip it would result into risk of breaking compatibility with minizip 1.0. All possible work was done for compatibility.

Background

When adding ZIP64 support Mathias Svensson found that Even Rouault have added ZIP64 support for unzip.c into minizip for a open source project called gdal (<http://www.gdal.org/>)

That was used as a starting point. And after that ZIP64 support was added to zip.c some refactoring and code cleanup was also done.

Changed from MiniZip 1.0 to MiniZip 1.1

- * Added ZIP64 support for unzip (by Even Rouault)
- * Added ZIP64 support for zip (by Mathias Svensson)
- * Reverted some changed that Even Rouault did.
- * Bunch of patches received from Guller Vollant that he received for MiniZip from various users.
- * Added unzip patch for BZIP Compression method (patch create by Daniel Borca)
- * Added BZIP Compress method for zip
- * Did some refactoring and code cleanup

Credits

Gilles Vollant - Original MiniZip author

Even Rouault - ZIP64 unzip Support
Daniel Borca - BZip Compression method support in unzip
Mathias Svensson - ZIP64 zip support
Mathias Svensson - BZip Compression method support in zip

Resources

ZipLayout <http://result42.com/projects/ZipFileLayout>

Command line tool for Windows that shows the layout and information of the headers in a zip archive.
Used when debugging and validating the creation of zip files using MiniZip64

ZIP App Note <http://www.pkware.com/documents/casestudies/APPNOTE.TXT>
Zip File specification

Notes.

* To be able to use BZip compression method in
zip64.c or unzip64.c the BZIP2 lib is needed and HAVE_BZIP2 need to be defined.

License

Condition of use and distribution are the same than zlib :

This software is provided 'as-is', without any express or implied
warranty. In no event will the authors be held liable for any damages
arising from the use of this software.

Permission is granted to anyone to use this software for any purpose,
including commercial applications, and to alter it and redistribute it
freely, subject to the following restrictions:

1. The origin of this software must not be misrepresented; you must not
claim that you wrote the original software. If you use this software
in a product, an acknowledgment in the product documentation would be
appreciated but is not required.
2. Altered source versions must be plainly marked as such, and must not be
misrepresented as being the original software.
3. This notice may
not be removed or altered from any source distribution.

Found in path(s):

* /opt/cola/permits/1394173797_1660873286.0583425/0/zlib-1-2-11-dfsg-orig-2-tar-xz/zlib-
1.2.11/contrib/minizip/MiniZip64_info.txt

No license file was found, but licenses were detected in source scan.

```
/* trees.c -- output deflated data using Huffman coding
* Copyright (C) 1995-2017 Jean-loup Gailly
* detect_data_type() function provided freely by Cosmin Truta, 2006
* For conditions of distribution and use, see copyright notice in zlib.h
*/
```

Found in path(s):

```
* /opt/cola/permits/1394173797_1660873286.0583425/0/zlib-1-2-11-dfsg-orig-2-tar-xz/zlib-1.2.11/trees.c
No license file was found, but licenses were detected in source scan.
```

```
/* deflate.h -- internal compression state
* Copyright (C) 1995-2016 Jean-loup Gailly
* For conditions of distribution and use, see copyright notice in zlib.h
*/
```

Found in path(s):

```
* /opt/cola/permits/1394173797_1660873286.0583425/0/zlib-1-2-11-dfsg-orig-2-tar-xz/zlib-1.2.11/deflate.h
No license file was found, but licenses were detected in source scan.
```

```
/* compress.c -- compress a memory buffer
* Copyright (C) 1995-2005, 2014, 2016 Jean-loup Gailly, Mark Adler
* For conditions of distribution and use, see copyright notice in zlib.h
*/
```

Found in path(s):

```
* /opt/cola/permits/1394173797_1660873286.0583425/0/zlib-1-2-11-dfsg-orig-2-tar-xz/zlib-1.2.11/compress.c
No license file was found, but licenses were detected in source scan.
```

```
/* gzappend -- command to append to a gzip file
```

Copyright (C) 2003, 2012 Mark Adler, all rights reserved
version 1.2, 11 Oct 2012

This software is provided 'as-is', without any express or implied warranty. In no event will the author be held liable for any damages arising from the use of this software.

Permission is granted to anyone to use this software for any purpose, including commercial applications, and to alter it and redistribute it freely, subject to the following restrictions:

1. The origin of this software must not be misrepresented; you must not claim that you wrote the original software. If you use this software in a product, an acknowledgment in the product documentation would be appreciated but is not required.
2. Altered source versions must be plainly marked as such, and must not be misrepresented as being the original software.
3. This notice may not be

removed or altered from any source distribution.

Mark Adler madler@alumni.caltech.edu

*/

Found in path(s):

* /opt/cola/permits/1394173797_1660873286.0583425/0/zlib-1-2-11-dfsg-orig-2-tar-xz/zlib-1.2.11/examples/gzappend.c

No license file was found, but licenses were detected in source scan.

/* zip.h -- IO on .zip files using zlib

Version 1.1, February 14h, 2010

part of the MiniZip project - (<http://www.winimage.com/zLibDll/minizip.html>)

Copyright (C) 1998-2010 Gilles Vollant (<http://www.winimage.com/zLibDll/minizip.html>)

Modifications for Zip64 support

Copyright (C) 2009-2010 Mathias Svensson (<http://result42.com>)

For more info read MiniZip_info.txt

Condition of use and distribution are the same than zlib :

This software is provided 'as-is', without any express or implied warranty. In no event will the authors be held liable for any damages arising from the use of this software.

Permission is granted to anyone to use this software for any purpose, including commercial applications, and to alter it and redistribute it freely, subject to the following restrictions:

1. The origin of this software must not be misrepresented; you must not claim that you wrote the original software. If you use this software in a product, an acknowledgment in the product documentation would be appreciated but is not required.
2. Altered source versions must be plainly marked as such, and must not be misrepresented as being the original software.
3. This notice may not be removed or altered from any source distribution.

Changes

See header of zip.h

*/

Found in path(s):

* /opt/cola/permits/1394173797_1660873286.0583425/0/zlib-1-2-11-dfsg-orig-2-tar-xz/zlib-1.2.11/contrib/minizip/zip.h

No license file was found, but licenses were detected in source scan.

/* gzread.c -- zlib functions for reading gzip files

* Copyright (C) 2004, 2005, 2010, 2011, 2012, 2013, 2016 Mark Adler

* For conditions of distribution and use, see copyright notice in zlib.h

*/

Found in path(s):

* /opt/cola/permits/1394173797_1660873286.0583425/0/zlib-1-2-11-dfsg-orig-2-tar-xz/zlib-1.2.11/gzread.c

No license file was found, but licenses were detected in source scan.

Frequently Asked Questions about ZLIB1.DLL

This document describes the design, the rationale, and the usage of the official DLL build of zlib, named ZLIB1.DLL. If you have general questions about zlib, you should see the file "FAQ" found in the zlib distribution, or at the following location:

http://www.gzip.org/zlib/zlib_faq.html

1. What is ZLIB1.DLL, and how can I get it?

- ZLIB1.DLL is the official build of zlib as a DLL.
(Please remark the character '1' in the name.)

Pointers to a precompiled ZLIB1.DLL can be found in the zlib web site at:

<http://www.zlib.net/>

Applications that link to ZLIB1.DLL can rely on the following specification:

- * The exported symbols are exclusively defined in the source files "zlib.h" and "zlib.def", found in an official zlib source distribution.
- * The symbols are exported by name, not by ordinal.
- * The exported names are undecorated.
- * The calling convention of functions is "C" (CDECL).
- * The ZLIB1.DLL binary is linked to MSVCRT.DLL.

The archive in which ZLIB1.DLL is bundled contains compiled test programs that must run with a valid build of ZLIB1.DLL.

It is recommended to download the prebuilt DLL from the zlib web site, instead of building it yourself, to avoid potential incompatibilities that could be introduced by your compiler and build settings. If you do build the DLL yourself, please make sure that it complies with all the above requirements, and it runs with the precompiled test programs, bundled with the original ZLIB1.DLL distribution.

If, for any reason, you need to build an incompatible DLL, please use a different file name.

2. Why did you change the name of the DLL to ZLIB1.DLL?
What happened to the old ZLIB.DLL?

- The old ZLIB.DLL, built from zlib-1.1.4 or earlier, required compilation settings that were incompatible to those used by

a static build. The DLL settings were supposed to be enabled by defining the macro ZLIB_DLL, before including "zlib.h". Incorrect handling of this macro was silently accepted at build time, resulting in two major problems:

* ZLIB_DLL was missing from the old makefile. When building the DLL, not all people added it to the build options. In consequence, incompatible incarnations of ZLIB.DLL started to circulate around the net.

* When switching from using the static library to using the DLL, applications had to define the ZLIB_DLL macro and to recompile all the sources that contained calls to zlib functions. Failure to do so resulted in creating binaries that were unable to run with the official ZLIB.DLL build.

The only possible solution that we could foresee was to make a binary-incompatible change in the DLL interface, in order to remove the dependency on the ZLIB_DLL macro, and to release the new DLL under a different name.

We chose the name ZLIB1.DLL, where '1' indicates the major zlib version number. We hope that we will not have to break the binary compatibility again, at least not as long as the zlib-1.x series will last.

There is still a ZLIB_DLL macro, that can trigger a more efficient build and use of the DLL, but compatibility no longer depends on it.

3. Can I build ZLIB.DLL from the new zlib sources, and replace an old ZLIB.DLL, that was built from zlib-1.1.4 or earlier?

- In principle, you can do it by assigning calling convention keywords to the macros ZEXPORT and ZEXPORTVA. In practice, it depends on what you mean by "an old ZLIB.DLL", because the old DLL exists in several mutually-incompatible versions. You have to find out first what kind of calling convention is being used in your particular ZLIB.DLL build, and to use the same one in the new build. If you don't know what this is all about, you might be better off if you would just leave the old DLL intact.

4. Can I compile my application using the new zlib interface, and link it to an old ZLIB.DLL, that was built from zlib-1.1.4 or earlier?

- The official answer is "no"; the real answer depends again on what kind of ZLIB.DLL you have. Even if you are lucky, this course of action is unreliable.

If you rebuild your application and you intend to use a newer version of zlib (post- 1.1.4), it is strongly recommended to link it to the new ZLIB1.DLL.

5. Why are the zlib symbols exported by name, and not by ordinal?

- Although exporting symbols by ordinal is a little faster, it is risky. Any single glitch in the maintenance or use of the DEF file that contains the ordinals can result in incompatible builds and frustrating crashes. Simply put, the benefits of exporting symbols by ordinal do not justify the risks.

Technically, it should be possible to maintain ordinals in the DEF file, and still export the symbols by name. Ordinals exist in every DLL, and even if the dynamic linking performed at the DLL startup is searching for names, ordinals serve as hints, for a faster name lookup. However, if the DEF file contains ordinals, the Microsoft linker automatically builds an implib that will cause the executables linked to it to use those ordinals, and not the names. It is interesting to notice that the GNU linker for Win32 does not suffer from this problem.

It is possible to avoid the DEF file if the exported symbols are accompanied by a "__declspec(dllexport)" attribute in the source files. You can do this in zlib by predefining the ZLIB_DLL macro.

6. I see that the ZLIB1.DLL functions use the "C" (CDECL) calling convention. Why not use the STDCALL convention? STDCALL is the standard convention in Win32, and I need it in my Visual Basic project!

(For readability, we use CDECL to refer to the convention triggered by the "__cdecl" keyword, STDCALL to refer to the convention triggered by "__stdcall", and FASTCALL to refer to the convention triggered by "__fastcall".)

- Most of the native Windows API functions (without varargs) use indeed the WINAPI convention (which translates to STDCALL in Win32), but the standard C functions use CDECL. If a user application is intrinsically tied to the Windows API (e.g. it calls native Windows API functions such as CreateFile()), sometimes it makes sense to decorate its own functions with WINAPI. But if ANSI C or POSIX portability is a goal (e.g. it calls standard C functions such as fopen()), it is not a sound decision to request the inclusion of <windows.h>, or to use non-ANSI constructs, for the sole purpose to make the user functions STDCALL-able.

The functionality offered by zlib is not in the category of "Windows functionality", but is more like "C functionality".

Technically, STDCALL is not bad; in fact, it is slightly faster than CDECL, and it works with variable-argument functions, just like CDECL. It is unfortunate that, in spite of using STDCALL in the Windows API, it is not the default convention used by the C compilers that run under Windows. The roots of the problem reside deep inside the unsafety of the K&R-style function prototypes, where the argument types are not specified; but that is another story for another day.

The remaining fact is that CDECL is the default convention. Even if an explicit convention is hard-coded into the function prototypes inside C headers, problems may appear. The necessity to expose the convention in users' callbacks is one of these problems.

The calling convention issues are also important when using zlib in other programming languages. Some of them, like Ada (GNAT) and Fortran (GNU G77), have C bindings implemented initially on Unix, and relying on the C calling convention. On the other hand, the pre-.NET versions of Microsoft Visual Basic require STDCALL, while Borland Delphi prefers, although it does not require, FASTCALL.

In fairness to all possible uses of zlib outside the C programming language, we choose the default "C" convention. Anyone interested in different bindings or conventions is encouraged to maintain specialized projects. The "contrib/" directory from the zlib distribution already holds a couple of foreign bindings, such as Ada, C++, and Delphi.

7. I need a DLL for my Visual Basic project. What can I do?

- Define the ZLIB_WINAPI macro before including "zlib.h", when building both the DLL and the user application (except that you don't need to define anything when using the DLL in Visual Basic). The ZLIB_WINAPI macro will switch on the WINAPI (STDCALL) convention. The name of this DLL must be different than the official ZLIB1.DLL.

Gilles Vollant has contributed a build named ZLIBWAPI.DLL, with the ZLIB_WINAPI macro turned on, and with the minizip functionality built in. For more information, please read the notes inside "contrib/vstudio/readme.txt", found in the zlib distribution.

8. I need to use zlib in my Microsoft .NET project. What can I do?

- Henrik Ravn has contributed a .NET wrapper around zlib. Look into contrib/dotzlib/, inside the zlib distribution.

9. If my application uses ZLIB1.DLL, should I link it to MSVCRT.DLL? Why?

- It is not required, but it is recommended to link your application to MSVCRT.DLL, if it uses ZLIB1.DLL.

The executables (.EXE, .DLL, etc.) that are involved in the same process and are using the C run-time library (i.e. they

are calling standard C functions), must link to the same library. There are several libraries in the Win32 system: CRTDLL.DLL, MSVCRT.DLL, the static C libraries, etc.

Since ZLIB1.DLL is linked to MSVCRT.DLL, the executables that depend on it should also be linked to MSVCRT.DLL.

10. Why are you saying that ZLIB1.DLL and my application should be linked to the same C run-time (CRT) library? I linked my application and my DLLs to different C libraries (e.g. my application to a static library, and my DLLs to MSVCRT.DLL), and everything works fine.

- If a user library invokes only pure Win32 API (accessible via <windows.h> and the related headers), its DLL build will work in any context. But if this library invokes standard C API, things get more complicated.

There is a single Win32 library in a Win32 system. Every function in this library resides in a single DLL module, that is safe to call from anywhere. On the other hand, there are multiple versions of the C library, and each of them has its own separate internal state. Standalone executables and user DLLs that call standard C functions must link to a C run-time (CRT) library, be it static or shared (DLL). Intermixing occurs when an executable (not necessarily standalone) and a DLL are linked to different CRTs, and both are running in the same process.

Intermixing multiple CRTs is possible, as long as their internal states are kept intact. The Microsoft Knowledge Base articles KB94248 "HOWTO: Use the C Run-Time" and KB140584 "HOWTO: Link with the Correct C Run-Time (CRT) Library" mention the potential problems raised by intermixing.

If intermixing works for you, it's because your application and DLLs are avoiding the corruption of each of the CRTs' internal states, maybe by careful design, or maybe by fortune.

Also note that linking ZLIB1.DLL to non-Microsoft CRTs, such as those provided by Borland, raises similar problems.

11. Why are you linking ZLIB1.DLL to MSVCRT.DLL?

- MSVCRT.DLL exists on every Windows 95 with a new service

pack

installed, or with Microsoft Internet Explorer 4 or later, and on all other Windows 4.x or later (Windows 98, Windows NT 4, or later). It is freely distributable; if not present in the system, it can be downloaded from Microsoft or from other software provider for free.

The fact that MSVCRT.DLL does not exist on a virgin Windows 95 is not so problematic. Windows 95 is scarcely found nowadays, Microsoft ended its support a long time ago, and many recent applications from various vendors, including Microsoft, do not even run on it. Furthermore, no serious user should run Windows 95 without a proper update installed.

12. Why are you not linking ZLIB1.DLL to <<my favorite C run-time library>> ?

- We considered and abandoned the following alternatives:

- * Linking ZLIB1.DLL to a static C library (LIBC.LIB, or LIBCMT.LIB) is not a good option. People are using the DLL mainly to save disk space. If you are linking your program to a static C library, you may as well consider linking zlib in statically, too.
- * Linking ZLIB1.DLL to CRTDLL.DLL looks appealing, because CRTDLL.DLL is present on every Win32 installation. Unfortunately, it has a series of problems: it does not work properly with Microsoft's C++ libraries, it does not provide support for 64-bit file offsets, (and so on...), and Microsoft discontinued its support a long time ago.
- * Linking ZLIB1.DLL to MSVCR70.DLL or MSVCR71.DLL, supplied with the Microsoft .NET platform, and Visual C++ 7.0/7.1, raises problems related to the status of ZLIB1.DLL as a system component. According to the Microsoft Knowledge Base article KB326922 "INFO: Redistribution of the Shared C Runtime Component in Visual C++ .NET", MSVCR70.DLL and MSVCR71.DLL are not supposed to function as system DLLs, because they may clash with MSVCRT.DLL. Instead, the application's installer is supposed to put these DLLs (if needed) in the application's private directory. If ZLIB1.DLL depends on a non-system runtime, it cannot function as a redistributable system component.

* Linking ZLIB1.DLL to non-Microsoft runtimes, such as Borland's, or Cygwin's, raises problems related to the reliable presence of these runtimes on Win32 systems. It's easier to let the DLL build of zlib up to the people who distribute these runtimes, and who may proceed as explained in the answer to Question 14.

13. If ZLIB1.DLL cannot be linked to MSVCR70.DLL or MSVCR71.DLL, how can I build/use ZLIB1.DLL in Microsoft Visual C++ 7.0 (Visual Studio .NET) or newer?

- Due to the problems explained in the Microsoft Knowledge Base article KB326922 (see the previous answer), the C runtime that comes with the VC7 environment is no longer considered a system component. That is, it should not be assumed that this runtime

exists, or may be installed in a system directory.

Since ZLIB1.DLL is supposed to be a system component, it may not depend on a non-system component.

In order to link ZLIB1.DLL and your application to MSVCRT.DLL in VC7, you need the library of Visual C++ 6.0 or older. If you don't have this library at hand, it's probably best not to use ZLIB1.DLL.

We are hoping that, in the future, Microsoft will provide a way to build applications linked to a proper system runtime, from the Visual C++ environment. Until then, you have a couple of alternatives, such as linking zlib in statically.

If your application requires dynamic linking, you may proceed as explained in the answer to Question 14.

14. I need to link my own DLL build to a CRT different than MSVCRT.DLL. What can I do?

- Feel free to rebuild the DLL from the zlib sources, and link it the way you want. You should, however, clearly state that your build is unofficial.

You should give it a different file

name, and/or install it in a private directory that can be accessed by your application only, and is not visible to the others (i.e. it's neither in the PATH, nor in the SYSTEM or SYSTEM32 directories). Otherwise, your build may clash with applications that link to the official build.

For example, in Cygwin, zlib is linked to the Cygwin runtime

CYGWIN1.DLL, and it is distributed under the name CYGZ.DLL.

15. May I include additional pieces of code that I find useful, link them in ZLIB1.DLL, and export them?

- No. A legitimate build of ZLIB1.DLL must not include code that does not originate from the official zlib source code. But you can make your own private DLL build, under a different file name, as suggested in the previous answer.

For example, zlib is a part of the VCL library, distributed with Borland Delphi and C++ Builder. The DLL build of VCL is a redistributable file, named VCLxx.DLL.

16. May I remove some functionality out of ZLIB1.DLL, by enabling macros like NO_GZCOMPRESS or NO_GZIP at compile time?

- No. A legitimate build of ZLIB1.DLL must provide the complete zlib functionality, as implemented in the official zlib source code. But you can make your own private DLL build, under a different file name, as suggested in the previous answer.

17. I made my own ZLIB1.DLL build. Can I test it for compliance?

- We prefer that you download the official DLL from the zlib web site. If you need something peculiar from this DLL, you can send your suggestion to the zlib mailing list.

However, in case you do rebuild the DLL yourself, you can run it with the test programs found in the DLL distribution. Running these test programs is not a guarantee of compliance, but a failure can imply a detected problem.

**

This document is written and maintained by
Cosmin Truta <cosmint@cs.ubbcluj.ro>

Found in path(s):

* /opt/cola/permits/1394173797_1660873286.0583425/0/zlib-1-2-11-dfsg-orig-2-tar-xz/zlib-1.2.11/win32/DLL_FAQ.txt

No license file was found, but licenses were detected in source scan.

Permission is granted to anyone to use this software for any purpose,

The origin of this software must not be misrepresented; you must not
Altered source versions must be plainly marked as such, and must not be
This notice may not be removed or altered from any source distribution.

Found in path(s):

* /opt/cola/permits/1394173797_1660873286.0583425/0/zlib-1-2-11-dfsg-orig-2-tar-xz/zlib-1.2.11/zlib.3

No license file was found, but licenses were detected in source scan.

/* zutil.c -- target dependent utility functions for the compression library

* Copyright (C) 1995-2017 Jean-loup Gailly

* For conditions of distribution and use, see copyright notice in zlib.h

*/

Found in path(s):

* /opt/cola/permits/1394173797_1660873286.0583425/0/zlib-1-2-11-dfsg-orig-2-tar-xz/zlib-1.2.11/zutil.c

No license file was found, but licenses were detected in source scan.

/* infcover.c -- test zlib's inflate routines with full code coverage

* Copyright (C) 2011, 2016 Mark Adler

* For conditions of distribution and use, see copyright notice in zlib.h

*/

Found in path(s):

* /opt/cola/permits/1394173797_1660873286.0583425/0/zlib-1-2-11-dfsg-orig-2-tar-xz/zlib-1.2.11/test/infcover.c

No license file was found, but licenses were detected in source scan.

/* zconf.h -- configuration of the zlib compression library

* Copyright (C) 1995-2016 Jean-loup Gailly, Mark Adler

* For conditions of distribution and use, see copyright notice in zlib.h

*/

Found in path(s):

* /opt/cola/permits/1394173797_1660873286.0583425/0/zlib-1-2-11-dfsg-orig-2-tar-xz/zlib-1.2.11/zconf.h.cmakein

* /opt/cola/permits/1394173797_1660873286.0583425/0/zlib-1-2-11-dfsg-orig-2-tar-xz/zlib-1.2.11/zconf.h.in

* /opt/cola/permits/1394173797_1660873286.0583425/0/zlib-1-2-11-dfsg-orig-2-tar-xz/zlib-1.2.11/zconf.h

No license file was found, but licenses were detected in source scan.

/* adler32.c -- compute the Adler-32 checksum of a data stream

* Copyright (C) 1995-2011, 2016 Mark Adler

* For conditions of distribution and use, see copyright notice in zlib.h

*/

Found in path(s):

* /opt/cola/permits/1394173797_1660873286.0583425/0/zlib-1-2-11-dfsg-orig-2-tar-xz/zlib-1.2.11/adler32.c

No license file was found, but licenses were detected in source scan.

/* gun.c -- simple gunzip to give an example of the use of inflateBack()

* Copyright (C) 2003, 2005, 2008, 2010, 2012 Mark Adler

* For conditions of distribution and use, see copyright notice in zlib.h
Version 1.7 12 August 2012 Mark Adler */

Found in path(s):

* /opt/cola/permits/1394173797_1660873286.0583425/0/zlib-1-2-11-dfsg-orig-2-tar-xz/zlib-1.2.11/examples/gun.c
No license file was found, but licenses were detected in source scan.

```
/* crc32.c -- compute the CRC-32 of a data stream
* Copyright (C) 1995-2006, 2010, 2011, 2012, 2016 Mark Adler
* For conditions of distribution and use, see copyright notice in zlib.h
*
* Thanks to Rodney Brown <rbrown64@csc.com.au> for his contribution of faster
* CRC methods: exclusive-oring 32 bits of data at a time, and pre-computing
* tables for updating the shift register in one step with three exclusive-ors
* instead of four steps with four exclusive-ors. This results in about a
* factor of two increase in speed on a Power PC G4 (PPC7455) using gcc -O3.
*/
```

Found in path(s):

* /opt/cola/permits/1394173797_1660873286.0583425/0/zlib-1-2-11-dfsg-orig-2-tar-xz/zlib-1.2.11/crc32.c
No license file was found, but licenses were detected in source scan.

```
/* inftrees.h -- header to use inftrees.c
* Copyright (C) 1995-2005, 2010 Mark Adler
* For conditions of distribution and use, see copyright notice in zlib.h
*/
```

Found in path(s):

* /opt/cola/permits/1394173797_1660873286.0583425/0/zlib-1-2-11-dfsg-orig-2-tar-xz/zlib-1.2.11/inftrees.h
No license file was found, but licenses were detected in source scan.

```
/* inffast.h -- header to use inffast.c
* Copyright (C) 1995-2003, 2010 Mark Adler
* For conditions of distribution and use, see copyright notice in zlib.h
*/
```

Found in path(s):

* /opt/cola/permits/1394173797_1660873286.0583425/0/zlib-1-2-11-dfsg-orig-2-tar-xz/zlib-1.2.11/inffast.h
No license file was found, but licenses were detected in source scan.

```
/* unzip.c -- IO for uncompress .zip files using zlib
Version 1.1, February 14h, 2010
part of the MiniZip project - ( http://www.winimage.com/zLibDll/minizip.html )
```

Copyright (C) 1998-2010 Gilles Vollant (minizip) (<http://www.winimage.com/zLibDll/minizip.html>)

Modifications of Unzip for Zip64
Copyright (C) 2007-2008 Even Rouault

Modifications for Zip64 support on both zip and unzip
Copyright (C) 2009-2010 Mathias Svensson (<http://result42.com>)

For more info read MiniZip_info.txt

Decryption code comes from crypt.c by Info-ZIP but has been greatly reduced in terms of compatibility with older software. The following is from the original crypt.c.
Code woven in by Terry Thorsen 1/2003.

Copyright (c) 1990-2000 Info-ZIP. All rights reserved.

See the accompanying
file LICENSE, version 2000-Apr-09 or later
(the contents of which are also included in zip.h) for terms of use.
If, for some reason, all these files are missing, the Info-ZIP license
also may be found at: <ftp://ftp.info-zip.org/pub/infozip/license.html>

crypt.c (full version) by Info-ZIP. Last revised: [see crypt.h]

The encryption/decryption parts of this source code (as opposed to the non-echoing password parts) were originally written in Europe. The whole source package can be freely distributed, including from the USA. (Prior to January 2000, re-export from the US was a violation of US law.)

This encryption code is a direct transcription of the algorithm from Roger Schlafly, described by Phil Katz in the file appnote.txt. This file (appnote.txt) is distributed with the PKZIP program (even in the version without encryption capabilities).

Changes in unzip.c

2007-2008 - Even Rouault - Addition of cpl_unzGetCurrentFileZStreamPos
2007-2008 - Even Rouault - Decoration of symbol names unz* -> cpl_unz*
2007-2008 - Even Rouault - Remove old C style function prototypes
2007-2008 - Even Rouault - Add unzip support for ZIP64

Copyright (C) 2007-2008 Even Rouault

Oct-2009 - Mathias Svensson - Removed cpl_* from symbol names (Even Rouault added them but since this is now moved to a new project (minizip64) I renamed them again).

Oct-2009 - Mathias Svensson - Fixed problem if uncompressed size was > 4G and compressed size was <4G
should only read the compressed/uncompressed size from the Zip64 format if

the size from normal header was 0xFFFFFFFF

Oct-2009 - Mathias Svensson - Applied some bug fixes from patches received from Gilles Vollant

Oct-2009 - Mathias Svensson - Applied support to unzip files with compression method
BZIP2 (bzip2 lib is required)

Patch created by Daniel Borca

Jan-2010 - back to unzip and minizip 1.0 name scheme, with compatibility layer

Copyright (C) 1998 - 2010 Gilles Vollant, Even Rouault, Mathias Svensson

*/

Found in path(s):

* /opt/cola/permits/1394173797_1660873286.0583425/0/zlib-1-2-11-dfsg-orig-2-tar-xz/zlib-1.2.11/contrib/minizip/unzip.c

No license file was found, but licenses were detected in source scan.

/* inftrees.c -- generate Huffman trees for efficient decoding

* Copyright (C) 1995-2017 Mark Adler

* For conditions of distribution and use, see copyright notice in zlib.h

*/

Found in path(s):

* /opt/cola/permits/1394173797_1660873286.0583425/0/zlib-1-2-11-dfsg-orig-2-tar-xz/zlib-1.2.11/inftrees.c

No license file was found, but licenses were detected in source scan.

/* zutil.h -- internal interface and configuration of the compression library

* Copyright (C) 1995-2016 Jean-loup Gailly, Mark Adler

* For conditions of distribution and use, see copyright notice in zlib.h

*/

Found in path(s):

* /opt/cola/permits/1394173797_1660873286.0583425/0/zlib-1-2-11-dfsg-orig-2-tar-xz/zlib-1.2.11/zutil.h

No license file was found, but licenses were detected in source scan.

/*

Additional tools for Minizip

Code: Xavier Roche '2004

License: Same as ZLIB (www.gzip.org)

*/

Found in path(s):

* /opt/cola/permits/1394173797_1660873286.0583425/0/zlib-1-2-11-dfsg-orig-2-tar-xz/zlib-1.2.11/contrib/minizip/mztools.h

* /opt/cola/permits/1394173797_1660873286.0583425/0/zlib-1-2-11-dfsg-orig-2-tar-xz/zlib-1.2.11/contrib/minizip/mztools.c

No license file was found, but licenses were detected in source scan.

```
/* gzclose.c -- zlib gzclose() function
* Copyright (C) 2004, 2010 Mark Adler
* For conditions of distribution and use, see copyright notice in zlib.h
*/
```

Found in path(s):

```
* /opt/cola/permits/1394173797_1660873286.0583425/0/zlib-1-2-11-dfsg-orig-2-tar-xz/zlib-1.2.11/gzclose.c
No license file was found, but licenses were detected in source scan.
```

```
/* deflate.c -- compress data using the deflation algorithm
* Copyright (C) 1995-2017 Jean-loup Gailly and Mark Adler
* For conditions of distribution and use, see copyright notice in zlib.h
*/
```

Found in path(s):

```
* /opt/cola/permits/1394173797_1660873286.0583425/0/zlib-1-2-11-dfsg-orig-2-tar-xz/zlib-1.2.11/deflate.c
No license file was found, but licenses were detected in source scan.
```

```
# For conditions of distribution and use, see copyright notice in zlib.h
```

Found in path(s):

```
* /opt/cola/permits/1394173797_1660873286.0583425/0/zlib-1-2-11-dfsg-orig-2-tar-xz/zlib-1.2.11/msdos/Makefile.dj2
* /opt/cola/permits/1394173797_1660873286.0583425/0/zlib-1-2-11-dfsg-orig-2-tar-xz/zlib-1.2.11/msdos/Makefile.emx
* /opt/cola/permits/1394173797_1660873286.0583425/0/zlib-1-2-11-dfsg-orig-2-tar-xz/zlib-1.2.11/win32/Makefile.gcc
* /opt/cola/permits/1394173797_1660873286.0583425/0/zlib-1-2-11-dfsg-orig-2-tar-xz/zlib-1.2.11/old/Makefile.emx
* /opt/cola/permits/1394173797_1660873286.0583425/0/zlib-1-2-11-dfsg-orig-2-tar-xz/zlib-1.2.11/old/os2/Makefile.os2
No license file was found, but licenses were detected in source scan.
```

```
/* gzlib.c -- zlib functions common to reading and writing gzip files
* Copyright (C) 2004-2017 Mark Adler
* For conditions of distribution and use, see copyright notice in zlib.h
*/
```

Found in path(s):

```
* /opt/cola/permits/1394173797_1660873286.0583425/0/zlib-1-2-11-dfsg-orig-2-tar-xz/zlib-1.2.11/gzlib.c
No license file was found, but licenses were detected in source scan.
```

```
/* zlib.h -- interface of the 'zlib' general purpose compression library
version 1.2.11, January 15th, 2017
```

Copyright (C) 1995-2017 Jean-loup Gailly and Mark Adler

This software is provided 'as-is', without any express or implied

warranty. In no event will the authors be held liable for any damages arising from the use of this software.

Permission is granted to anyone to use this software for any purpose, including commercial applications, and to alter it and redistribute it freely, subject to the following restrictions:

1. The origin of this software must not be misrepresented; you must not claim that you wrote the original software. If you use this software in a product, an acknowledgment in the product documentation would be appreciated but is not required.
2. Altered source versions must be plainly marked as such, and must not be misrepresented as being the original software.
3. This notice may not be removed or altered from any source distribution.

Jean-loup Gailly Mark Adler
jloup@gzip.org madler@alumni.caltech.edu

The data format used by the zlib library is described by RFCs (Request for Comments) 1950 to 1952 in the files <http://tools.ietf.org/html/rfc1950> (zlib format), rfc1951 (deflate format) and rfc1952 (gzip format).

*/

Found in path(s):

* /opt/cola/permits/1394173797_1660873286.0583425/0/zlib-1-2-11-dfsg-orig-2-tar-xz/zlib-1.2.11/zlib.h

No license file was found, but licenses were detected in source scan.

/* zran.c -- example of zlib/gzip stream indexing and random access

* Copyright (C) 2005, 2012 Mark Adler

* For conditions of distribution and use, see copyright notice in zlib.h

Version 1.1 29 Sep 2012 Mark Adler */

Found in path(s):

* /opt/cola/permits/1394173797_1660873286.0583425/0/zlib-1-2-11-dfsg-orig-2-tar-xz/zlib-1.2.11/examples/zran.c

No license file was found, but licenses were detected in source scan.

/* example.c -- usage example of the zlib compression library

* Copyright (C) 1995-2006, 2011, 2016 Jean-loup Gailly

* For conditions of distribution and use, see copyright notice in zlib.h

*/

Found in path(s):

* /opt/cola/permits/1394173797_1660873286.0583425/0/zlib-1-2-11-dfsg-orig-2-tar-xz/zlib-1.2.11/test/example.c

No license file was found, but licenses were detected in source scan.

/* infback.c -- inflate using a call-back interface

* Copyright (C) 1995-2016 Mark Adler

* For conditions of distribution and use, see copyright notice in zlib.h

*/

Found in path(s):

* /opt/cola/permits/1394173797_1660873286.0583425/0/zlib-1-2-11-dfsg-orig-2-tar-xz/zlib-1.2.11/infbck.c

No license file was found, but licenses were detected in source scan.

/* gzjoin -- command to join gzip files into one gzip file

Copyright (C) 2004, 2005, 2012 Mark Adler, all rights reserved
version 1.2, 14 Aug 2012

This software is provided 'as-is', without any express or implied warranty. In no event will the author be held liable for any damages arising from the use of this software.

Permission is granted to anyone to use this software for any purpose, including commercial applications, and to alter it and redistribute it freely, subject to the following restrictions:

1. The origin of this software must not be misrepresented; you must not claim that you wrote the original software. If you use this software in a product, an acknowledgment in the product documentation would be appreciated but is not required.
2. Altered source versions must be plainly marked as such, and must not be misrepresented as being the original software.
3. This notice may not be removed or altered from any source distribution.

Mark Adler madler@alumni.caltech.edu

*/

Found in path(s):

* /opt/cola/permits/1394173797_1660873286.0583425/0/zlib-1-2-11-dfsg-orig-2-tar-xz/zlib-1.2.11/examples/gzjoin.c

No license file was found, but licenses were detected in source scan.

Frequently Asked Questions about zlib

If your question is not there, please check the zlib home page

<http://zlib.net/> which may have more recent information.

The latest zlib FAQ is at http://zlib.net/zlib_faq.html

1. Is zlib Y2K-compliant?

Yes. zlib doesn't handle dates.

2. Where can I get a Windows DLL version?

The zlib sources can be compiled without change to produce a DLL. See the file win32/DLL_FAQ.txt in the zlib distribution. Pointers to the precompiled DLL are found in the zlib web site at <http://zlib.net/> .

3. Where can I get a Visual Basic interface to zlib?

See

* <http://marknelson.us/1997/01/01/zlib-engine/>

* win32/DLL_FAQ.txt in the zlib distribution

4. compress() returns Z_BUF_ERROR.

Make sure that before the call of compress(), the length of the compressed buffer is equal to the available size of the compressed buffer and not zero. For Visual

Basic, check that this parameter is passed by reference ("as any"), not by value ("as long").

5. deflate() or inflate() returns Z_BUF_ERROR.

Before making the call, make sure that avail_in and avail_out are not zero. When setting the parameter flush equal to Z_FINISH, also make sure that avail_out is big enough to allow processing all pending input. Note that a Z_BUF_ERROR is not fatal--another call to deflate() or inflate() can be made with more input or output space. A Z_BUF_ERROR may in fact be unavoidable depending on how the functions are used, since it is not possible to tell whether or not there is more output pending when strm.avail_out returns with zero. See http://zlib.net/zlib_how.html for a heavily annotated example.

6. Where's the zlib documentation (man pages, etc.)?

It's in zlib.h . Examples of zlib usage are in the files test/example.c and test/minigzip.c, with more in examples/ .

7. Why don't you use GNU autoconf or libtool or ...?

Because we would like to keep zlib as a very small and simple package. zlib is rather portable and doesn't need much configuration.

8. I found a bug in zlib.

Most of the time, such problems are due to an incorrect usage of zlib. Please try to reproduce the problem with a small program and send the

corresponding source to us at zlib@gzip.org . Do not send multi-megabyte data files without prior agreement.

9. Why do I get "undefined reference to gzputc"?

If "make test" produces something like

```
example.o(.text+0x154): undefined reference to `gzputc'
```

check that you don't have old files libz.* in /usr/lib, /usr/local/lib or /usr/X11R6/lib. Remove any old versions, then do "make install".

10. I need a Delphi interface to zlib.

See the contrib/delphi directory in the zlib distribution.

11. Can zlib handle .zip archives?

Not by itself, no. See the directory contrib/minizip in the zlib distribution.

12.

Can zlib handle .Z files?

No, sorry. You have to spawn an uncompress or gunzip subprocess, or adapt the code of uncompress on your own.

13. How can I make a Unix shared library?

By default a shared (and a static) library is built for Unix. So:

```
make distclean
./configure
make
```

14. How do I install a shared zlib library on Unix?

After the above, then:

```
make install
```

However, many flavors of Unix come with a shared zlib already installed. Before going to the trouble of compiling a shared version of zlib and trying to install it, you may want to check if it's already there! If you can `#include <zlib.h>`, it's there. The `-lz` option will probably link to it. You can check the version at the top of `zlib.h` or with the `ZLIB_VERSION` symbol defined in `zlib.h` .

15. I have a question about OttoPDF.

We are not the authors of OttoPDF. The real author is on the OttoPDF web site: Joel Hainley, jhainley@myndkryme.com.

16.

Can zlib decode Flate data in an Adobe PDF file?

Yes. See <http://www.pdflib.com/> . To modify PDF forms, see <http://sourceforge.net/projects/acroformtool/> .

17. Why am I getting this "register_frame_info not found" error on Solaris?

After installing zlib 1.1.4 on Solaris 2.6, running applications using zlib generates an error such as:

```
ld.so.1: rpm: fatal: relocation error: file /usr/local/lib/libz.so:
symbol __register_frame_info: referenced symbol not found
```

The symbol `__register_frame_info` is not part of zlib, it is generated by the C compiler (cc or gcc). You must recompile applications using zlib which have this problem. This problem is specific to Solaris. See <http://www.sunfreeware.com> for Solaris versions of zlib and applications using zlib.

18. Why does gzip give an error on a file I make with compress/deflate?

The compress and deflate functions produce data in the zlib format, which is different and incompatible with the gzip format. The `gz*` functions in zlib on the other hand use the gzip format. Both the zlib and gzip formats use the same compressed data format internally, but have different headers and trailers around the compressed data.

19. Ok, so why are there two different formats?

The gzip format was designed to retain the directory information about a single file, such as the name and last modification date. The zlib format on the other hand was designed for in-memory and communication channel applications, and has a much more compact header and trailer and uses a faster integrity check than gzip.

20. Well that's nice, but how do I make a gzip file in memory?

You can request that deflate write the gzip format instead of the zlib format using `deflateInit2()`. You can also request that inflate decode the gzip format using `inflateInit2()`. Read `zlib.h` for more details.

21. Is zlib thread-safe?

Yes. However any library routines that zlib uses and any application-provided memory allocation routines must also be thread-safe. zlib's gz* functions use stdio library routines, and most of zlib's functions use the library memory allocation routines by default. zlib's *Init* functions allow for the application to provide custom memory allocation routines.

Of course, you should only operate on any given zlib or gzip stream from a single thread at a time.

22. Can I use zlib in my commercial application?

Yes. Please read the license in zlib.h.

23. Is zlib under the GNU license?

No. Please read the license in zlib.h.

24. The license says that altered source versions must be "plainly marked". So what exactly do I need to do to meet that requirement?

You need to change the ZLIB_VERSION and ZLIB_VERNUM #defines in zlib.h. In particular, the final version number needs to be changed to "f", and an identification string should be appended to ZLIB_VERSION. Version numbers x.x.x.f are reserved for modifications to zlib by others than the zlib maintainers. For example, if the version of the base zlib you are altering is "1.2.3.4", then in zlib.h you should change ZLIB_VERNUM to 0x123f, and ZLIB_VERSION to something like "1.2.3.f-zachary-mods-v3". You can also update the version strings in deflate.c and infrees.c.

For altered source distributions, you should also note the origin and nature of the changes in zlib.h, as well as in ChangeLog and README, along with the dates of the alterations. The origin should include at least your name (or your company's name), and an email address to contact for help or issues with the library.

Note that distributing a compiled zlib library along with zlib.h and zconf.h is also a source distribution, and so you should change ZLIB_VERSION and ZLIB_VERNUM and note the origin and nature of the changes in zlib.h as you would for a full source distribution.

25.

Will zlib work on a big-endian or little-endian architecture, and can I exchange compressed data between them?

Yes and yes.

26. Will zlib work on a 64-bit machine?

Yes. It has been tested on 64-bit machines, and has no dependence on any data types being limited to 32-bits in length. If you have any difficulties, please provide a complete problem report to zlib@gzip.org

27. Will zlib decompress data from the PKWare Data Compression Library?

No. The PKWare DCL uses a completely different compressed data format than does PKZIP and zlib. However, you can look in zlib's contrib/blast directory for a possible solution to your problem.

28. Can I access data randomly in a compressed stream?

No, not without some preparation. If when compressing you periodically use `Z_FULL_FLUSH`, carefully write all the pending data at those points, and keep an index of those locations, then you can start decompression at those points. You have to be careful to not use `Z_FULL_FLUSH` too often, since it can significantly degrade compression. Alternatively, you can scan a deflate stream once to generate an index, and then use that index for random access. See `examples/zran.c`.

29. Does zlib work on MVS, OS/390, CICS, etc.?

It has in the past, but we have not heard of any recent evidence. There were working ports of zlib 1.1.4 to MVS, but those links no longer work. If you know of recent, successful applications of zlib on these operating systems, please let us know. Thanks.

30. Is there some simpler, easier to read version of inflate I can look at to understand the deflate format?

First off, you should read RFC 1951. Second, yes. Look in zlib's contrib/puff directory.

31. Does zlib infringe on any patents?

As far as we know, no. In fact, that was originally the whole point behind zlib. Look here for some more information:

<http://www.gzip.org/#faq11>

32. Can zlib work with greater than 4 GB of data?

Yes. `inflate()` and `deflate()` will process any amount of data correctly.

Each call of `inflate()` or `deflate()` is limited to input and output chunks of the maximum value that can be stored in the compiler's "unsigned int" type, but there is no limit to the number of chunks. Note however that the `strm.total_in` and `strm_total_out` counters may be limited to 4 GB. These counters are provided as a convenience and are not used internally by `inflate()` or `deflate()`. The application can easily set up its own counters updated after each call of `inflate()` or `deflate()` to count beyond 4 GB. `compress()` and `uncompress()` may be limited to 4 GB, since they operate in a single call. `gzseek()` and `gztell()` may be limited to 4 GB depending on how `zlib` is compiled. See the `zlibCompileFlags()` function in `zlib.h`.

The word "may" appears several times above since there is a 4 GB limit only if the compiler's "long" type is 32 bits. If the compiler's "long" type is 64 bits, then the limit is 16 exabytes.

33. Does `zlib` have any security vulnerabilities?

The only one that we are aware of is potentially in `gzprintf()`. If `zlib` is compiled to use `sprintf()` or `vsprintf()`, then there is no protection against a buffer overflow of an 8K string space (or other value as set by `gzbuffer()`), other than the caller of `gzprintf()` assuring that the output will not exceed 8K. On the other hand, if `zlib` is compiled to use `snprintf()` or `vsnprintf()`, which should normally be the case, then there is no vulnerability. The `./configure` script will display warnings if an insecure variation of `sprintf()` will be used by `gzprintf()`. Also the `zlibCompileFlags()` function will return information on what variant of `sprintf()` is used by `gzprintf()`.

If you don't have `snprintf()` or `vsnprintf()` and would like one, you can find a portable implementation here:

<http://www.ijs.si/software/snprintf/>

Note that you should be using the most recent version of `zlib`. Versions 1.1.3 and before were subject to a double-free vulnerability, and versions 1.2.1 and 1.2.2 were subject to an access exception when decompressing invalid compressed data.

34. Is there a Java version of `zlib`?

Probably what you want is to use `zlib` in Java. `zlib` is already included as part of the Java SDK in the `java.util.zip` package. If you really want a version of `zlib` written in the Java language, look on the `zlib` home page for links: <http://zlib.net/>.

35. I get this or that compiler or source-code scanner warning when I crank it up to maximally-pedantic. Can't you guys write proper code?

Many years ago, we gave up attempting to avoid warnings on every compiler in the universe. It just got to be a waste of time, and some compilers were downright silly as well as contradicted each other. So now, we simply make sure that the code always works.

36. Valgrind (or some similar memory access checker) says that deflate is performing a conditional jump that depends on an uninitialized value. Isn't that a bug?

No. That is intentional for performance reasons, and the output of deflate is not affected. This only started showing up recently since zlib 1.2.x uses malloc() by default for allocations, whereas earlier versions used calloc(), which zeros out the allocated memory. Even though the code was correct, versions 1.2.4 and later was changed to not stimulate these checkers.

37. Will zlib read the (insert any ancient or arcane format here) compressed data format?

Probably not. Look in the comp.compression FAQ for pointers to various formats and associated software.

38. How can I encrypt/decrypt zip files with zlib?

zlib doesn't support encryption. The original PKZIP encryption is very weak and can be broken with freely available programs. To get strong encryption, use GnuPG, <http://www.gnupg.org/>, which already includes zlib compression. For PKZIP compatible "encryption", look at <http://www.info-zip.org/>

39. What's the difference between the "gzip" and "deflate" HTTP 1.1 encodings?

"gzip" is the gzip format, and "deflate" is the zlib format. They should probably have called the second one "zlib" instead to avoid confusion with the raw deflate compressed data format. While the HTTP 1.1 RFC 2616 correctly points to the zlib specification in RFC 1950 for the "deflate" transfer encoding, there have been reports of servers and browsers that incorrectly produce or expect raw deflate data per the deflate specification in RFC 1951, most notably Microsoft. So even though the "deflate" transfer encoding using the zlib format would be the more efficient approach (and in fact exactly what the zlib format was designed for), using the "gzip" transfer encoding is probably more reliable due to an unfortunate choice of name on the part of the HTTP 1.1 authors.

Bottom line: use the gzip format for HTTP 1.1 encoding.

40. Does zlib support the new "Deflate64" format introduced by PKWare?

No. PKWare has apparently decided to keep that format proprietary, since they have not documented it as they have previous compression formats. In any case, the compression improvements are so modest compared to other more modern approaches, that it's not worth the effort to implement.

41. I'm having a problem with the zip functions in zlib, can you help?

There are no zip functions in zlib. You are probably using minizip by Giles Vollant, which is found in the contrib directory of zlib. It is not part of zlib. In fact none of the stuff in contrib is part of zlib. The files in there are not supported by the zlib authors. You need to contact the authors of the respective contribution for help.

42. The match.asm code in contrib is under the GNU General Public License.

Since it's part of zlib, doesn't that mean that all of zlib falls under the GNU GPL?

No. The files in contrib are not part of zlib. They were contributed by other authors and are provided as a convenience to the user within the zlib distribution. Each item in contrib has its own license.

43. Is zlib subject to export controls? What is its ECCN?

zlib is not subject to export controls, and so is classified as EAR99.

44. Can you please sign these lengthy legal documents and fax them back to us so that we can use your software in our product?

No. Go away. Shoo.

Found in path(s):

```
* /opt/cola/permits/1394173797_1660873286.0583425/0/zlib-1-2-11-dfsg-orig-2-tar-xz/zlib-1.2.11/FAQ
```

No license file was found, but licenses were detected in source scan.

```
/* zpipe.c: example of proper use of zlib's inflate() and deflate()
```

```
Not copyrighted -- provided to the public domain
```

```
Version 1.4 11 December 2005 Mark Adler */
```

Found in path(s):

```
* /opt/cola/permits/1394173797_1660873286.0583425/0/zlib-1-2-11-dfsg-orig-2-tar-xz/zlib-1.2.11/examples/zpipe.c
```

No license file was found, but licenses were detected in source scan.

Not copyrighted -- provided to the public domain

Found in path(s):

* /opt/cola/permits/1394173797_1660873286.0583425/0/zlib-1-2-11-dfsg-orig-2-tar-xz/zlib-1.2.11/examples/zlib_how.html

No license file was found, but licenses were detected in source scan.

/* minigzip.c -- simulate gzip using the zlib compression library

* Copyright (C) 1995-2006, 2010, 2011, 2016 Jean-loup Gailly

* For conditions of distribution and use, see copyright notice in zlib.h

*/

Found in path(s):

* /opt/cola/permits/1394173797_1660873286.0583425/0/zlib-1-2-11-dfsg-orig-2-tar-xz/zlib-1.2.11/test/minigzip.c

No license file was found, but licenses were detected in source scan.

/* uncompr.c -- decompress a memory buffer

* Copyright (C) 1995-2003, 2010, 2014, 2016 Jean-loup Gailly, Mark Adler

* For conditions of distribution and use, see copyright notice in zlib.h

*/

Found in path(s):

* /opt/cola/permits/1394173797_1660873286.0583425/0/zlib-1-2-11-dfsg-orig-2-tar-xz/zlib-1.2.11/uncompr.c

No license file was found, but licenses were detected in source scan.

/* unzip.h -- IO for uncompress .zip files using zlib

Version 1.1, February 14h, 2010

part of the MiniZip project - (<http://www.winimage.com/zLibDll/minizip.html>)

Copyright (C) 1998-2010 Gilles Vollant (<http://www.winimage.com/zLibDll/minizip.html>)

Modifications of Unzip for Zip64

Copyright (C) 2007-2008 Even Rouault

Modifications for Zip64 support on both zip and unzip

Copyright (C) 2009-2010 Mathias Svensson (<http://result42.com>)

For more info read MiniZip_info.txt

Condition of use and distribution are the same than zlib :

This software is provided 'as-is', without any express or implied warranty. In no event will the authors be held liable for any damages arising from the use of this software.

Permission is granted to anyone

to use this software for any purpose,
including commercial applications, and to alter it and redistribute it
freely, subject to the following restrictions:

1. The origin of this software must not be misrepresented; you must not claim that you wrote the original software. If you use this software in a product, an acknowledgment in the product documentation would be appreciated but is not required.
2. Altered source versions must be plainly marked as such, and must not be misrepresented as being the original software.
3. This notice may not be removed or altered from any source distribution.

Changes

See header of unzip64.c

*/

Found in path(s):

* /opt/cola/permits/1394173797_1660873286.0583425/0/zlib-1-2-11-dfsg-orig-2-tar-xz/zlib-1.2.11/contrib/minizip/unzip.h

No license file was found, but licenses were detected in source scan.

/* inflate.h -- internal inflate state definition

* Copyright (C) 1995-2016 Mark Adler

* For conditions of distribution and use, see copyright notice in zlib.h

*/

Found in path(s):

* /opt/cola/permits/1394173797_1660873286.0583425/0/zlib-1-2-11-dfsg-orig-2-tar-xz/zlib-1.2.11/inflate.h

No license file was found, but licenses were detected in source scan.

/* gzlog.h

Copyright (C) 2004, 2008, 2012 Mark Adler, all rights reserved
version 2.2, 14 Aug 2012

This software is provided 'as-is', without any express or implied warranty. In no event will the author be held liable for any damages arising from the use of this software.

Permission is granted to anyone to use this software for any purpose,
including commercial applications, and to alter it and redistribute it
freely, subject to the following restrictions:

1. The origin of this software must not be misrepresented; you must not claim that you wrote the original software. If you use this software

in a product, an acknowledgment in the product documentation would be appreciated but is not required.

2. Altered source versions must be plainly marked as such, and must not be misrepresented as being the original software.
3. This notice may not be removed or altered from any source distribution.

Mark Adler madler@alumni.caltech.edu

*/

Found in path(s):

* /opt/cola/permits/1394173797_1660873286.0583425/0/zlib-1-2-11-dfsg-orig-2-tar-xz/zlib-1.2.11/examples/gzlog.h

No license file was found, but licenses were detected in source scan.

/* gzwrite.c -- zlib functions for writing gzip files

* Copyright (C) 2004-2017 Mark Adler

* For conditions of distribution and use, see copyright notice in zlib.h

*/

Found in path(s):

* /opt/cola/permits/1394173797_1660873286.0583425/0/zlib-1-2-11-dfsg-orig-2-tar-xz/zlib-1.2.11/gzwrite.c

No license file was found, but licenses were detected in source scan.

ZLIB DATA COMPRESSION LIBRARY

zlib 1.2.11 is a general purpose data compression library. All the code is thread safe. The data format used by the zlib library is described by RFCs (Request for Comments) 1950 to 1952 in the files <http://tools.ietf.org/html/rfc1950> (zlib format), [rfc1951](http://tools.ietf.org/html/rfc1951) (deflate format) and [rfc1952](http://tools.ietf.org/html/rfc1952) (gzip format).

All functions of the compression library are documented in the file `zlib.h` (volunteer to write man pages welcome, contact zlib@gzip.org). A usage example of the library is given in the file `test/example.c` which also tests that the library is working correctly. Another example is given in the file `test/minigzip.c`. The compression library itself is composed of all source files in the root directory.

To compile all files and run the test program, follow the instructions given at the top of `Makefile.in`. In short `./configure; make test`, and if that goes well, `make install` should work for most flavors of Unix. For Windows, use one of the special makefiles in `win32/` or `contrib/vstudio/`. For VMS, use `make_vms.com`.

Questions about zlib should be sent to zlib@gzip.org, or to Gilles Vollant info@winimage.com for the Windows DLL version. The zlib home page is

<http://zlib.net/> . Before reporting a problem, please check this site to verify that you have the latest version of zlib; otherwise get the latest version and check whether the problem still exists or not.

PLEASE read the zlib FAQ http://zlib.net/zlib_faq.html before asking for help.

Mark Nelson <markn@ieee.org> wrote an article about zlib for the Jan. 1997 issue of Dr. Dobbs's Journal; a copy of the article is available at <http://marknelson.us/1997/01/01/zlib-engine/> .

The changes made in version 1.2.11 are documented in the file ChangeLog.

Unsupported third party contributions are provided in directory contrib/ .

zlib is available in Java using the `java.util.zip` package, documented at <http://java.sun.com/developer/technicalArticles/Programming/compression/> .

A Perl interface to zlib written by Paul Marquess <pmqs@cpan.org> is available at CPAN (Comprehensive Perl Archive Network) sites, including <http://search.cpan.org/~pmqs/IO-Compress-Zlib/> .

A Python interface to zlib written by A.M. Kuchling <amk@amk.ca> is available in Python 1.5 and later versions, see <http://docs.python.org/library/zlib.html> .

zlib is built into tcl: <http://wiki.tcl.tk/4610> .

An experimental package to read and write files in .zip format, written on top of zlib by Gilles Vollant <info@winimage.com>, is available in the contrib/minizip directory of zlib.

Notes for some targets:

- For Windows DLL versions, please see `win32/DLL_FAQ.txt`
- For 64-bit Irix, `deflate.c` must be compiled without any optimization. With `-O`, one libpng test fails. The test works in 32 bit mode (with the `-n32` compiler flag). The compiler bug has been reported to SGI.
- zlib doesn't work with gcc 2.6.3 on a DEC 3000/300LX under OSF/1 2.1 it works when compiled with `cc`.
- On Digital Unix 4.0D (formely OSF/1) on AlphaServer, the `cc` option `-std1` is necessary to get `gzprintf` working correctly. This is done by `configure`.

- zlib doesn't work on HP-UX 9.05 with some versions of /bin/cc. It works with other compilers. Use "make test" to check your compiler.

- gzdopen is not supported on RISCOS or BEOS.

- For PalmOs, see <http://palmzlib.sourceforge.net/>

Acknowledgments:

The deflate format used by zlib was defined by Phil Katz. The deflate and zlib specifications were written by L. Peter Deutsch. Thanks to all the people who reported problems and suggested various improvements in zlib; they are too numerous to cite here.

Copyright notice:

(C) 1995-2017 Jean-loup Gailly and Mark Adler

This software is provided 'as-is', without any express or implied warranty. In no event will the authors be held liable for any damages arising from the use of this software.

Permission is granted to anyone to use this software for any purpose, including commercial applications, and to alter it and redistribute it freely, subject to the following restrictions:

1. The origin of this software must not be misrepresented; you must not claim that you wrote the original software. If you use this software in a product, an acknowledgment in the product documentation would be appreciated but is not required.
2. Altered source versions must be plainly marked as such, and must not be misrepresented as being the original software.
3. This notice may not be removed or altered from any source distribution.

Jean-loup Gailly Mark Adler
jloup@gzip.org madler@alumni.caltech.edu

If you use the zlib library in a product, we would appreciate *not* receiving lengthy legal documents to sign. The sources are provided for free but without warranty of any kind. The library has been entirely written by Jean-loup Gailly and Mark Adler; it does not include third-party code.

If you redistribute modified sources, we would appreciate that you include in the file ChangeLog history information documenting your changes. Please read the FAQ for more information on the distribution of modified source versions.

Found in path(s):

* /opt/cola/permits/1394173797_1660873286.0583425/0/zlib-1-2-11-dfsg-orig-2-tar-xz/zlib-1.2.11/README
No license file was found, but licenses were detected in source scan.

/* inflate.c -- zlib decompression

* Copyright (C) 1995-2016 Mark Adler
* For conditions of distribution and use, see copyright notice in zlib.h
*/

Found in path(s):

* /opt/cola/permits/1394173797_1660873286.0583425/0/zlib-1-2-11-dfsg-orig-2-tar-xz/zlib-1.2.11/inflate.c
No license file was found, but licenses were detected in source scan.

/* inffast.c -- fast decoding

* Copyright (C) 1995-2017 Mark Adler
* For conditions of distribution and use, see copyright notice in zlib.h
*/

Found in path(s):

* /opt/cola/permits/1394173797_1660873286.0583425/0/zlib-1-2-11-dfsg-orig-2-tar-xz/zlib-1.2.11/inffast.c
No license file was found, but licenses were detected in source scan.

/* gzguts.h -- zlib internal header definitions for gz* operations

* Copyright (C) 2004, 2005, 2010, 2011, 2012, 2013, 2016 Mark Adler
* For conditions of distribution and use, see copyright notice in zlib.h
*/

Found in path(s):

* /opt/cola/permits/1394173797_1660873286.0583425/0/zlib-1-2-11-dfsg-orig-2-tar-xz/zlib-1.2.11/gzguts.h
No license file was found, but licenses were detected in source scan.

ZLIB DATA COMPRESSION LIBRARY

zlib 1.2.11 is a general purpose data compression library. All the code is thread safe. The data format used by the zlib library is described by RFCs (Request for Comments) 1950 to 1952 in the files <http://www.ietf.org/rfc/rfc1950.txt> (zlib format), [rfc1951.txt](http://www.ietf.org/rfc/rfc1951.txt) (deflate format) and [rfc1952.txt](http://www.ietf.org/rfc/rfc1952.txt) (gzip format).

All functions of the compression library are documented in the file `zlib.h` (volunteer to write man pages welcome, contact zlib@gzip.org). Two compiled examples are distributed in this package, `example` and `minigzip`. The `example_d` and `minigzip_d` flavors validate that the `zlib1.dll` file is working correctly.

Questions about zlib should be sent to [<zlib@gzip.org>](mailto:zlib@gzip.org). The zlib home page is <http://zlib.net/>. Before reporting a problem, please check this site to verify that you have the latest version of zlib; otherwise get the latest

version and check whether the problem still exists
or not.

PLEASE read DLL_FAQ.txt, and the the zlib FAQ http://zlib.net/zlib_faq.html
before asking for help.

Manifest:

The package zlib-1.2.11-win32-x86.zip will contain the following files:

README-WIN32.txt This document

ChangeLog Changes since previous zlib packages

DLL_FAQ.txt Frequently asked questions about zlib1.dll

zlib.3.pdf Documentation of this library in Adobe Acrobat format

example.exe A statically-bound example (using zlib.lib, not the dll)

example.pdb Symbolic information for debugging example.exe

example_d.exe A zlib1.dll bound example (using zdll.lib)

example_d.pdb Symbolic information for debugging example_d.exe

minigzip.exe A statically-bound test program (using zlib.lib, not the dll)

minigzip.pdb Symbolic information for debugging minigzip.exe

minigzip_d.exe A zlib1.dll bound test program (using zdll.lib)

minigzip_d.pdb Symbolic information for debugging minigzip_d.exe

zlib.h

Install these files into the compilers' INCLUDE path to

zconf.h compile programs which use zlib.lib or zdll.lib

zdll.lib Install these files into the compilers' LIB path if linking

zdll.exp a compiled program to the zlib1.dll binary

zlib.lib Install these files into the compilers' LIB path to link zlib

zlib.pdb into compiled programs, without zlib1.dll runtime dependency
(zlib.pdb provides debugging info to the compile time linker)

zlib1.dll Install this binary shared library into the system PATH, or
the program's runtime directory (where the .exe resides)

zlib1.pdb Install in the same directory as zlib1.dll, in order to debug
an application crash using WinDbg or similar tools.

All .pdb files above are entirely optional, but are very useful to a developer
attempting to diagnose program misbehavior or a crash. Many additional
important files for developers

can be found in the zlib127.zip source package
available from <http://zlib.net/> - review that package's README file for details.

Acknowledgments:

The deflate format used by zlib was defined by Phil Katz. The deflate and zlib specifications were written by L. Peter Deutsch. Thanks to all the people who reported problems and suggested various improvements in zlib; they are too numerous to cite here.

Copyright notice:

(C) 1995-2017 Jean-loup Gailly and Mark Adler

This software is provided 'as-is', without any express or implied warranty. In no event will the authors be held liable for any damages arising from the use of this software.

Permission is granted to anyone to use this software for any purpose, including commercial applications, and to alter it and redistribute it freely, subject to the following restrictions:

1. The origin of this software must not be misrepresented; you must not claim that you wrote the original software. If you use this software in a product, an acknowledgment in the product documentation would be appreciated but is not required.
2. Altered source versions must be plainly marked as such, and must not be misrepresented as being the original software.
3. This notice may not be removed or altered from any source distribution.

Jean-loup Gailly Mark Adler
jloup@gzip.org madler@alumni.caltech.edu

If you use the zlib library in a product, we would appreciate *not* receiving lengthy legal documents to sign. The sources are provided for free but without warranty of any kind. The library has been entirely written by Jean-loup Gailly and Mark Adler; it does not include third-party code.

If you redistribute modified sources, we would appreciate that you include in the file ChangeLog history information documenting your changes. Please read the FAQ for more information on the distribution of modified source versions.

Found in path(s):

* /opt/cola/permits/1394173797_1660873286.0583425/0/zlib-1-2-11-dfsg-orig-2-tar-xz/zlib-1.2.11/win32/README-WIN32.txt

No license file was found, but licenses were detected in source scan.

```
/* fitblk.c: example of fitting compressed output to a specified size
   Not copyrighted -- provided to the public domain
   Version 1.1 25 November 2004 Mark Adler */
```

Found in path(s):

```
* /opt/cola/permits/1394173797_1660873286.0583425/0/zlib-1-2-11-dfsg-orig-2-tar-xz/zlib-1.2.11/examples/fitblk.c
```

No license file was found, but licenses were detected in source scan.

```
/*
 * gzlog.c
 * Copyright (C) 2004, 2008, 2012, 2016 Mark Adler, all rights reserved
 * For conditions of distribution and use, see copyright notice in gzlog.h
 * version 2.2, 14 Aug 2012
 */
```

Found in path(s):

```
* /opt/cola/permits/1394173797_1660873286.0583425/0/zlib-1-2-11-dfsg-orig-2-tar-xz/zlib-1.2.11/examples/gzlog.c
```

1.88 zlib1g 1:1.2.11.dfsg-0ubuntu2.2

1.88.1 Available under license :

No license file was found, but licenses were detected in source scan.

```
/* gzlib.c -- zlib functions common to reading and writing gzip files
 * Copyright (C) 2004-2017 Mark Adler
 * For conditions of distribution and use, see copyright notice in zlib.h
 */
```

Found in path(s):

```
* /opt/cola/permits/1397844474_1661343334.7470329/0/zlib-1-2-11-dfsg-orig-2-tar-xz/zlib-1.2.11/gzlib.c
```

No license file was found, but licenses were detected in source scan.

```
/* zutil.h -- internal interface and configuration of the compression library
 * Copyright (C) 1995-2016 Jean-loup Gailly, Mark Adler
 * For conditions of distribution and use, see copyright notice in zlib.h
 */
```

Found in path(s):

```
* /opt/cola/permits/1397844474_1661343334.7470329/0/zlib-1-2-11-dfsg-orig-2-tar-xz/zlib-1.2.11/zutil.h
```

No license file was found, but licenses were detected in source scan.

ZLIB DATA COMPRESSION LIBRARY

zlib 1.2.11 is a general purpose data compression library. All the code is thread safe. The data format used by the zlib library is described by RFCs (Request for Comments) 1950 to 1952 in the files <http://tools.ietf.org/html/rfc1950> (zlib format), [rfc1951](http://tools.ietf.org/html/rfc1951) (deflate format) and [rfc1952](http://tools.ietf.org/html/rfc1952) (gzip format).

All functions of the compression library are documented in the file `zlib.h` (volunteer to write man pages welcome, contact zlib@gzip.org). A usage example of the library is given in the file `test/example.c` which also tests that the library is working correctly. Another example is given in the file `test/minigzip.c`. The compression library itself is composed of all source files in the root directory.

To compile all files and run the test program, follow the instructions given at the top of `Makefile.in`. In short `./configure; make test`, and if that goes well, `make install` should work for most flavors of Unix. For Windows, use one of the special makefiles in `win32/` or `contrib/vstudio/`. For VMS, use `make_vms.com`.

Questions about zlib should be sent to [<zlib@gzip.org>](mailto:zlib@gzip.org), or to Gilles Vollant [<info@winimage.com>](mailto:info@winimage.com) for the Windows DLL version. The zlib home page is <http://zlib.net/>. Before reporting a problem, please check this site to verify that you have the latest version of zlib; otherwise get the latest version and check whether the problem still exists or not.

PLEASE read the zlib FAQ http://zlib.net/zlib_faq.html before asking for help.

Mark Nelson [<markn@ieee.org>](mailto:markn@ieee.org) wrote an article about zlib for the Jan. 1997 issue of Dr. Dobbs's Journal; a copy of the article is available at <http://marknelson.us/1997/01/01/zlib-engine/>.

The changes made in version 1.2.11 are documented in the file `ChangeLog`.

Unsupported third party contributions are provided in directory `contrib/`.

zlib is available in Java using the `java.util.zip` package, documented at <http://java.sun.com/developer/technicalArticles/Programming/compression/>.

A Perl interface to zlib written by Paul Marquess [<pmqs@cpan.org>](mailto:pmqs@cpan.org) is available at CPAN (Comprehensive Perl Archive Network) sites, including <http://search.cpan.org/~pmqs/IO-Compress-Zlib/>.

A Python interface to zlib written by A.M. Kuchling [<amk@amk.ca>](mailto:amk@amk.ca) is available in Python 1.5 and later versions, see <http://docs.python.org/library/zlib.html>.

zlib is built into tcl: <http://wiki.tcl.tk/4610> .

An experimental package to read and write files in .zip format, written on top of zlib by Gilles Vollant <info@winimage.com>, is available in the contrib/minizip directory of zlib.

Notes for some targets:

- For Windows DLL versions, please see win32/DLL_FAQ.txt
- For 64-bit Irix, deflate.c must be compiled without any optimization. With -O, one libpng test fails. The test works in 32 bit mode (with the -n32 compiler flag). The compiler bug has been reported to SGI.
- zlib doesn't work with gcc 2.6.3 on a DEC 3000/300LX under OSF/1 2.1 it works when compiled with cc.
- On Digital Unix 4.0D (formely OSF/1) on AlphaServer, the cc option -std1 is necessary to get gzprintf working correctly. This is done by configure.
- zlib doesn't work on HP-UX 9.05 with some versions of /bin/cc. It works with other compilers. Use "make test" to check your compiler.
- gzdopen is not supported on RISCOS or BEOS.
- For PalmOs, see <http://palmzlib.sourceforge.net/>

Acknowledgments:

The deflate format used by zlib was defined by Phil Katz. The deflate and zlib specifications were written by L. Peter Deutsch. Thanks to all the people who reported problems and suggested various improvements in zlib; they are too numerous to cite here.

Copyright notice:

(C) 1995-2017 Jean-loup Gailly and Mark Adler

This software is provided 'as-is', without any express or implied warranty. In no event will the authors be held liable for any damages arising from the use of this software.

Permission is granted to anyone to use this software for any purpose, including commercial applications, and to alter it and redistribute it

freely, subject to the following restrictions:

1. The origin of this software must not be misrepresented; you must not claim that you wrote the original software. If you use this software in a product, an acknowledgment in the product documentation would be appreciated but is not required.
2. Altered source versions must be plainly marked as such, and must not be misrepresented as being the original software.
3. This notice may not be removed or altered from any source distribution.

Jean-loup Gailly Mark Adler
jloup@gzip.org madler@alumni.caltech.edu

If you use the zlib library in a product, we would appreciate *not* receiving lengthy legal documents to sign. The sources are provided for free but without warranty of any kind. The library has been entirely written by Jean-loup Gailly and Mark Adler; it does not include third-party code.

If you redistribute modified sources, we would appreciate that you include in the file ChangeLog history information documenting your changes. Please read the FAQ for more information on the distribution of modified source versions.

Found in path(s):

* /opt/cola/permits/1397844474_1661343334.7470329/0/zlib-1-2-11-dfsg-orig-2-tar-xz/zlib-1.2.11/README
No license file was found, but licenses were detected in source scan.

```
/* uncompr.c -- decompress a memory buffer
* Copyright (C) 1995-2003, 2010, 2014, 2016 Jean-loup Gailly, Mark Adler
* For conditions of distribution and use, see copyright notice in zlib.h
*/
```

Found in path(s):

* /opt/cola/permits/1397844474_1661343334.7470329/0/zlib-1-2-11-dfsg-orig-2-tar-xz/zlib-1.2.11/uncompr.c
No license file was found, but licenses were detected in source scan.

```
/*
Additional tools for Minizip
Code: Xavier Roche '2004
License: Same as ZLIB (www.gzip.org)
*/
```

Found in path(s):

* /opt/cola/permits/1397844474_1661343334.7470329/0/zlib-1-2-11-dfsg-orig-2-tar-xz/zlib-1.2.11/contrib/minizip/mztools.h
* /opt/cola/permits/1397844474_1661343334.7470329/0/zlib-1-2-11-dfsg-orig-2-tar-xz/zlib-1.2.11/contrib/minizip/mztools.c

No license file was found, but licenses were detected in source scan.

```
/* inflate.h -- internal inflate state definition
* Copyright (C) 1995-2016 Mark Adler
* For conditions of distribution and use, see copyright notice in zlib.h
*/
```

Found in path(s):

```
* /opt/cola/permits/1397844474_1661343334.7470329/0/zlib-1-2-11-dfsg-orig-2-tar-xz/zlib-1.2.11/inflate.h
No license file was found, but licenses were detected in source scan.
```

```
/* gzwrite.c -- zlib functions for writing gzip files
* Copyright (C) 2004-2017 Mark Adler
* For conditions of distribution and use, see copyright notice in zlib.h
*/
```

Found in path(s):

```
* /opt/cola/permits/1397844474_1661343334.7470329/0/zlib-1-2-11-dfsg-orig-2-tar-xz/zlib-1.2.11/gzwrite.c
No license file was found, but licenses were detected in source scan.
```

```
/* deflate.c -- compress data using the deflation algorithm
* Copyright (C) 1995-2017 Jean-loup Gailly and Mark Adler
* For conditions of distribution and use, see copyright notice in zlib.h
*/
```

Found in path(s):

```
* /opt/cola/permits/1397844474_1661343334.7470329/0/zlib-1-2-11-dfsg-orig-2-tar-xz/zlib-1.2.11/deflate.c
No license file was found, but licenses were detected in source scan.
```

```
/* zconf.h -- configuration of the zlib compression library
* Copyright (C) 1995-2016 Jean-loup Gailly, Mark Adler
* For conditions of distribution and use, see copyright notice in zlib.h
*/
```

Found in path(s):

```
* /opt/cola/permits/1397844474_1661343334.7470329/0/zlib-1-2-11-dfsg-orig-2-tar-xz/zlib-1.2.11/zconf.h.in
* /opt/cola/permits/1397844474_1661343334.7470329/0/zlib-1-2-11-dfsg-orig-2-tar-xz/zlib-1.2.11/zconf.h
* /opt/cola/permits/1397844474_1661343334.7470329/0/zlib-1-2-11-dfsg-orig-2-tar-xz/zlib-1.2.11/zconf.h.cmakein
No license file was found, but licenses were detected in source scan.
```

MiniZip - Copyright (c) 1998-2010 - by Gilles Vollant - version 1.1 64 bits from Mathias Svensson

Introduction

MiniZip 1.1 is built from MiniZip 1.0 by Gilles Vollant (<http://www.winimage.com/zLibDll/minizip.html>)

When adding ZIP64 support into minizip it would result into risk of breaking compatibility with minizip 1.0.

All possible work was done for compatibility.

Background

When adding ZIP64 support Mathias Svensson found that Even Rouault have added ZIP64 support for unzip.c into minizip for a open source project called gdal (<http://www.gdal.org/>)

That was used as a starting point. And after that ZIP64 support was added to zip.c some refactoring and code cleanup was also done.

Changed from MiniZip 1.0 to MiniZip 1.1

-
- * Added ZIP64 support for unzip (by Even Rouault)
 - * Added ZIP64 support for zip (by Mathias Svensson)
 - * Reverted some changed that Even Rouault did.
 - * Bunch of patches received from Gilles Vollant that he received for MiniZip from various users.
 - * Added unzip patch for BZIP Compression method (patch create by Daniel Borca)
 - * Added BZIP Compress method for zip
 - * Did some refactoring and code cleanup

Credits

Gilles Vollant - Original MiniZip author
Even Rouault - ZIP64 unzip Support
Daniel Borca - BZip Compression method support in unzip
Mathias Svensson - ZIP64 zip support
Mathias Svensson - BZip Compression method support in zip

Resources

ZipLayout <http://result42.com/projects/ZipFileLayout>

Command line tool for Windows that shows the layout and information of the headers in a zip archive.
Used when debugging and validating the creation of zip files using MiniZip64

ZIP App Note <http://www.pkware.com/documents/casestudies/APPNOTE.TXT>
Zip File specification

Notes.

- * To be able to use BZip compression method in zip64.c or unzip64.c the BZIP2 lib is needed and HAVE_BZIP2 need to be defined.

License

Condition of use and distribution are the same than zlib :

This software is provided 'as-is', without any express or implied warranty. In no event will the authors be held liable for any damages arising from the use of this software.

Permission is granted to anyone to use this software for any purpose, including commercial applications, and to alter it and redistribute it freely, subject to the following restrictions:

1. The origin of this software must not be misrepresented; you must not claim that you wrote the original software. If you use this software in a product, an acknowledgment in the product documentation would be appreciated but is not required.
2. Altered source versions must be plainly marked as such, and must not be misrepresented as being the original software.
3. This notice may not be removed or altered from any source distribution.

Found in path(s):

* /opt/cola/permits/1397844474_1661343334.7470329/0/zlib-1-2-11-dfsg-orig-2-tar-xz/zlib-1.2.11/contrib/minizip/MiniZip64_info.txt

No license file was found, but licenses were detected in source scan.

/* gzread.c -- zlib functions for reading gzip files

* Copyright (C) 2004, 2005, 2010, 2011, 2012, 2013, 2016 Mark Adler

* For conditions of distribution and use, see copyright notice in zlib.h

*/

Found in path(s):

* /opt/cola/permits/1397844474_1661343334.7470329/0/zlib-1-2-11-dfsg-orig-2-tar-xz/zlib-1.2.11/gzread.c

No license file was found, but licenses were detected in source scan.

/* gzlog.h

Copyright (C) 2004, 2008, 2012 Mark Adler, all rights reserved

version 2.2, 14 Aug 2012

This software is provided 'as-is', without any express or implied warranty. In no event will the author be held liable for any damages arising from the use of this software.

Permission is granted to anyone to use this software for any purpose, including commercial applications, and to alter it and redistribute it freely, subject to the following restrictions:

1. The origin of this software must not be misrepresented; you must not

claim that you wrote the original software. If you use this software in a product, an acknowledgment in the product documentation would be appreciated but is not required.

2. Altered source versions must be plainly marked as such, and must not be misrepresented as being the original software.
3. This notice may not be removed or altered from any source distribution.

Mark Adler madler@alumni.caltech.edu

*/

Found in path(s):

* /opt/cola/permits/1397844474_1661343334.7470329/0/zlib-1-2-11-dfsg-orig-2-tar-xz/zlib-1.2.11/examples/gzlog.h

No license file was found, but licenses were detected in source scan.

Permission is granted to anyone to use this software for any purpose,
The origin of this software must not be misrepresented; you must not
Altered source versions must be plainly marked as such, and must not be
This notice may not be removed or altered from any source distribution.

Found in path(s):

* /opt/cola/permits/1397844474_1661343334.7470329/0/zlib-1-2-11-dfsg-orig-2-tar-xz/zlib-1.2.11/zlib.3

No license file was found, but licenses were detected in source scan.

/* gzjoin -- command to join gzip files into one gzip file

Copyright (C) 2004, 2005, 2012 Mark Adler, all rights reserved
version 1.2, 14 Aug 2012

This software is provided 'as-is', without any express or implied warranty. In no event will the author be held liable for any damages arising from the use of this software.

Permission is granted to anyone to use this software for any purpose, including commercial applications, and to alter it and redistribute it freely, subject to the following restrictions:

1. The origin of this software must not be misrepresented; you must not claim that you wrote the original software. If you use this software in a product, an acknowledgment in the product documentation would be appreciated but is not required.
2. Altered source versions must be plainly marked as such, and must not be misrepresented as being the original software.
3. This notice may not be removed or altered from any source distribution.

Mark Adler madler@alumni.caltech.edu

*/

Found in path(s):

* /opt/cola/permits/1397844474_1661343334.7470329/0/zlib-1-2-11-dfsg-orig-2-tar-xz/zlib-1.2.11/examples/gzjoin.c

No license file was found, but licenses were detected in source scan.

/* deflate.h -- internal compression state

* Copyright (C) 1995-2016 Jean-loup Gailly

* For conditions of distribution and use, see copyright notice in zlib.h

*/

Found in path(s):

* /opt/cola/permits/1397844474_1661343334.7470329/0/zlib-1-2-11-dfsg-orig-2-tar-xz/zlib-1.2.11/deflate.h

No license file was found, but licenses were detected in source scan.

/* unzip.h -- IO for uncompress .zip files using zlib

Version 1.1, February 14h, 2010

part of the MiniZip project - (<http://www.winimage.com/zLibDll/minizip.html>)

Copyright (C) 1998-2010 Gilles Vollant (minizip) (<http://www.winimage.com/zLibDll/minizip.html>)

Modifications of Unzip for Zip64

Copyright (C) 2007-2008 Even Rouault

Modifications for Zip64 support on both zip and unzip

Copyright (C) 2009-2010 Mathias Svensson (<http://result42.com>)

For more info read MiniZip_info.txt

Condition of use and distribution are the same than zlib :

This software is provided 'as-is', without any express or implied warranty. In no event will the authors be held liable for any damages arising from the use of this software.

Permission is granted to anyone to use this software for any purpose, including commercial applications, and to alter it and redistribute it freely, subject to the following restrictions:

1. The origin of this software must not be misrepresented; you must not claim that you wrote the original software. If you use this software in a product, an acknowledgment in the product documentation would be appreciated but is not required.
2. Altered source versions must be plainly marked as such, and must not be

misrepresented as being the original software.

3. This notice may not be removed or altered from any source distribution.

Changes

See header of unzip64.c

*/

Found in path(s):

* /opt/cola/permits/1397844474_1661343334.7470329/0/zlib-1-2-11-dfsg-orig-2-tar-xz/zlib-1.2.11/contrib/minizip/unzip.h

No license file was found, but licenses were detected in source scan.

/* gzclose.c -- zlib gzclose() function

* Copyright (C) 2004, 2010 Mark Adler

* For conditions of distribution and use, see copyright notice in zlib.h

*/

Found in path(s):

* /opt/cola/permits/1397844474_1661343334.7470329/0/zlib-1-2-11-dfsg-orig-2-tar-xz/zlib-1.2.11/gzclose.c

No license file was found, but licenses were detected in source scan.

/* zpipe.c: example of proper use of zlib's inflate() and deflate()

Not copyrighted -- provided to the public domain

Version 1.4 11 December 2005 Mark Adler */

Found in path(s):

* /opt/cola/permits/1397844474_1661343334.7470329/0/zlib-1-2-11-dfsg-orig-2-tar-xz/zlib-1.2.11/examples/zpipe.c

No license file was found, but licenses were detected in source scan.

/* minigzip.c -- simulate gzip using the zlib compression library

* Copyright (C) 1995-2006, 2010, 2011, 2016 Jean-loup Gailly

* For conditions of distribution and use, see copyright notice in zlib.h

*/

Found in path(s):

* /opt/cola/permits/1397844474_1661343334.7470329/0/zlib-1-2-11-dfsg-orig-2-tar-xz/zlib-1.2.11/test/minigzip.c

No license file was found, but licenses were detected in source scan.

/* Adler32.c -- compute the Adler-32 checksum of a data stream

* Copyright (C) 1995-2011, 2016 Mark Adler

* For conditions of distribution and use, see copyright notice in zlib.h

*/

Found in path(s):

* /opt/cola/permits/1397844474_1661343334.7470329/0/zlib-1-2-11-dfsg-orig-2-tar-xz/zlib-1.2.11/adler32.c

No license file was found, but licenses were detected in source scan.

Not copyrighted -- provided to the public domain

Found in path(s):

* /opt/cola/permits/1397844474_1661343334.7470329/0/zlib-1-2-11-dfsg-orig-2-tar-xz/zlib-1.2.11/examples/zlib_how.html

No license file was found, but licenses were detected in source scan.

Frequently Asked Questions about zlib

If your question is not there, please check the zlib home page

<http://zlib.net/> which may have more recent information.

The latest zlib FAQ is at http://zlib.net/zlib_faq.html

1. Is zlib Y2K-compliant?

Yes. zlib doesn't handle dates.

2. Where can I get a Windows DLL version?

The zlib sources can be compiled without change to produce a DLL. See the file win32/DLL_FAQ.txt in the zlib distribution. Pointers to the precompiled DLL are found in the zlib web site at <http://zlib.net/>.

3. Where can I get a Visual Basic interface to zlib?

See

* <http://marknelson.us/1997/01/01/zlib-engine/>

* win32/DLL_FAQ.txt in the zlib distribution

4. compress() returns Z_BUF_ERROR.

Make sure that before the call of compress(), the length of the compressed buffer is equal to the available size of the compressed buffer and not zero. For Visual

Basic, check that this parameter is passed by reference

("as any"), not by value ("as long").

5. deflate() or inflate() returns Z_BUF_ERROR.

Before making the call, make sure that avail_in and avail_out are not zero.

When setting the parameter flush equal to Z_FINISH, also make sure that avail_out is big enough to allow processing all pending input. Note that a

Z_BUF_ERROR is not fatal--another call to deflate() or inflate() can be made with more input or output space. A Z_BUF_ERROR may in fact be unavoidable depending on how the functions are used, since it is not possible to tell whether or not there is more output pending when strm.avail_out returns with zero. See http://zlib.net/zlib_how.html for a heavily annotated example.

6. Where's the zlib documentation (man pages, etc.)?

It's in zlib.h . Examples of zlib usage are in the files test/example.c and test/minizip.c, with more in examples/ .

7. Why don't you use GNU autoconf or libtool or ...?

Because we would like to keep zlib as a very small and simple package. zlib is rather portable and doesn't need much configuration.

8. I found a bug in zlib.

Most of the time, such problems are due to an incorrect usage of zlib. Please try to reproduce the problem with a small program and send the corresponding source to us at zlib@gzip.org . Do not send multi-megabyte data files without prior agreement.

9. Why do I get "undefined reference to gzputc"?

If "make test" produces something like

```
example.o(.text+0x154): undefined reference to `gzputc'
```

check that you don't have old files libz.* in /usr/lib, /usr/local/lib or /usr/X11R6/lib. Remove any old versions, then do "make install".

10. I need a Delphi interface to zlib.

See the contrib/delphi directory in the zlib distribution.

11. Can zlib handle .zip archives?

Not by itself, no. See the directory contrib/minizip in the zlib distribution.

12.

Can zlib handle .Z files?

No, sorry. You have to spawn an uncompress or gunzip subprocess, or adapt the code of uncompress on your own.

13. How can I make a Unix shared library?

By default a shared (and a static) library is built for Unix. So:

```
make distclean
./configure
make
```

14. How do I install a shared zlib library on Unix?

After the above, then:

```
make install
```

However, many flavors of Unix come with a shared zlib already installed. Before going to the trouble of compiling a shared version of zlib and trying to install it, you may want to check if it's already there! If you can `#include <zlib.h>`, it's there. The `-lz` option will probably link to it. You can check the version at the top of `zlib.h` or with the `ZLIB_VERSION` symbol defined in `zlib.h`.

15. I have a question about OttoPDF.

We are not the authors of OttoPDF. The real author is on the OttoPDF web site: Joel Hainley, jhainley@myndkryme.com.

16.

Can zlib decode Flate data in an Adobe PDF file?

Yes. See <http://www.pdflib.com/>. To modify PDF forms, see <http://sourceforge.net/projects/acroformtool/>.

17. Why am I getting this "register_frame_info not found" error on Solaris?

After installing zlib 1.1.4 on Solaris 2.6, running applications using zlib generates an error such as:

```
ld.so.1: rpm: fatal: relocation error: file /usr/local/lib/libz.so:
symbol __register_frame_info: referenced symbol not found
```

The symbol `__register_frame_info` is not part of zlib, it is generated by the C compiler (`cc` or `gcc`). You must recompile applications using zlib which have this problem. This problem is specific to Solaris. See <http://www.sunfreeware.com> for Solaris versions of zlib and applications using zlib.

18. Why does gzip give an error on a file I make with compress/deflate?

The compress and deflate functions produce data in the zlib format, which is different and incompatible with the gzip format. The gz* functions in zlib on the other hand use the gzip format. Both the zlib and gzip formats use the same compressed data format internally, but have different headers and trailers around the compressed data.

19. Ok, so why are there two different formats?

The gzip format was designed to retain the directory information about a single file, such as the name and last modification date. The zlib format on the other hand was designed for in-memory and communication channel applications, and has a much more compact header and trailer and uses a faster integrity check than gzip.

20. Well that's nice, but how do I make a gzip file in memory?

You can request that deflate write the gzip format instead of the zlib format using deflateInit2(). You can also request that inflate decode the gzip format using inflateInit2(). Read zlib.h for more details.

21. Is zlib thread-safe?

Yes. However any library routines that zlib uses and any application-provided memory allocation routines must also be thread-safe. zlib's gz* functions use stdio library routines, and most of zlib's functions use the library memory allocation routines by default. zlib's *Init* functions allow for the application to provide custom memory allocation routines.

Of course, you should only operate on any given zlib or gzip stream from a single thread at a time.

22. Can I use zlib in my commercial application?

Yes. Please read the license in zlib.h.

23. Is zlib under the GNU license?

No. Please read the license in zlib.h.

24. The license says that altered source versions must be "plainly marked". So what exactly do I need to do to meet that requirement?

You need to change the ZLIB_VERSION and ZLIB_VERNUM #defines in zlib.h. In particular, the final version number needs to be changed to "f", and an identification string should be appended to ZLIB_VERSION. Version numbers

x.x.x.f are reserved for modifications to zlib by others than the zlib maintainers. For example, if the version of the base zlib you are altering is "1.2.3.4", then in zlib.h you should change ZLIB_VERNUM to 0x123f, and ZLIB_VERSION to something like "1.2.3.f-zachary-mods-v3". You can also update the version strings in deflate.c and infrees.c.

For altered source distributions, you should also note the origin and nature of the changes in zlib.h, as well as in ChangeLog and README, along with the dates of the alterations. The origin should include at least your name (or your company's name), and an email address to contact for help or issues with the library.

Note that distributing a compiled zlib library along with zlib.h and zconf.h is also a source distribution, and so you should change ZLIB_VERSION and ZLIB_VERNUM and note the origin and nature of the changes in zlib.h as you would for a full source distribution.

25.

Will zlib work on a big-endian or little-endian architecture, and can I exchange compressed data between them?

Yes and yes.

26. Will zlib work on a 64-bit machine?

Yes. It has been tested on 64-bit machines, and has no dependence on any data types being limited to 32-bits in length. If you have any difficulties, please provide a complete problem report to zlib@gzip.org

27. Will zlib decompress data from the PKWare Data Compression Library?

No. The PKWare DCL uses a completely different compressed data format than does PKZIP and zlib. However, you can look in zlib's contrib/blast directory for a possible solution to your problem.

28. Can I access data randomly in a compressed stream?

No, not without some preparation. If when compressing you periodically use Z_FULL_FLUSH, carefully write all the pending data at those points, and keep an index of those locations, then you can start decompression at those points. You have to be careful to not use Z_FULL_FLUSH too often, since it can significantly degrade compression. Alternatively, you can scan a deflate stream once to generate an index, and then use that index for random access. See examples/zran.c .

29. Does zlib work on MVS, OS/390, CICS, etc.?

It has in the past, but we have not heard of any recent evidence. There were working ports of zlib 1.1.4 to MVS, but those links no longer work. If you know of recent, successful applications of zlib on these operating systems, please let us know. Thanks.

30. Is there some simpler, easier to read version of inflate I can look at to understand the deflate format?

First off, you should read RFC 1951. Second, yes. Look in zlib's contrib/puff directory.

31. Does zlib infringe on any patents?

As far as we know, no. In fact, that was originally the whole point behind zlib. Look here for some more information:

<http://www.gzip.org/#faq11>

32. Can zlib work with greater than 4 GB of data?

Yes. inflate() and deflate() will process any amount of data correctly. Each call of inflate() or deflate() is limited to input and output chunks of the maximum value that can be stored in the compiler's "unsigned int" type, but there is no limit to the number of chunks. Note however that the strm.total_in and strm_total_out counters may be limited to 4 GB. These counters are provided as a convenience and are not used internally by inflate() or deflate(). The application can easily set up its own counters updated after each call of inflate() or deflate() to count beyond 4 GB. compress() and uncompress() may be limited to 4 GB, since they operate in a single call. gzseek() and gztell() may be limited to 4 GB depending on how zlib is compiled. See the zlibCompileFlags() function in zlib.h.

The word "may" appears several times above since there is a 4 GB limit only if the compiler's "long" type is

32 bits. If the compiler's "long" type is

64 bits, then the limit is 16 exabytes.

33. Does zlib have any security vulnerabilities?

The only one that we are aware of is potentially in gzprintf(). If zlib is compiled to use sprintf() or vsprintf(), then there is no protection against a buffer overflow of an 8K string space (or other value as set by gzbuffer()), other than the caller of gzprintf() assuring that the output will not exceed 8K. On the other hand, if zlib is compiled to use snprintf() or vsnprintf(), which should normally be the case, then there is no vulnerability. The ./configure script will display warnings if an insecure variation of sprintf() will be used by gzprintf(). Also the

zlibCompileFlags() function will return information on what variant of sprintf() is used by gzprintf().

If you don't have snprintf() or vsnprintf() and would like one, you can find a portable implementation here:

<http://www.ijs.si/software/snprintf/>

Note that you should be using the most recent version of zlib. Versions 1.1.3 and before were subject to a double-free vulnerability, and versions 1.2.1 and 1.2.2 were subject to an access exception when decompressing invalid compressed data.

34. Is there a Java version of zlib?

Probably what you want is to use zlib in Java. zlib is already included as part of the Java SDK in the java.util.zip package. If you really want a version of zlib written in the Java language, look on the zlib home page for links: <http://zlib.net/>.

35. I get this or that compiler or source-code scanner warning when I crank it up to maximally-pedantic. Can't you guys write proper code?

Many years ago, we gave up attempting to avoid warnings on every compiler in the universe. It just got to be a waste of time, and some compilers were downright silly as well as contradicted each other. So now, we simply make sure that the code always works.

36. Valgrind (or some similar memory access checker) says that deflate is performing a conditional jump that depends on an uninitialized value. Isn't that a bug?

No. That is intentional for performance reasons, and the output of deflate is not affected. This only started showing up recently since zlib 1.2.x uses malloc() by default for allocations, whereas earlier versions used calloc(), which zeros out the allocated memory. Even though the code was correct, versions 1.2.4 and later was changed to not stimulate these checkers.

37. Will zlib read the (insert any ancient or arcane format here) compressed data format?

Probably not. Look in the comp.compression FAQ for pointers to various formats and associated software.

38. How can I encrypt/decrypt zip files with zlib?

zlib doesn't support encryption. The original PKZIP encryption is very weak and can be broken with freely available programs. To get strong encryption, use GnuPG, <http://www.gnupg.org/>, which already includes zlib compression. For PKZIP compatible "encryption", look at <http://www.info-zip.org/>

39. What's the difference between the "gzip" and "deflate" HTTP 1.1 encodings?

"gzip" is the gzip format, and "deflate" is the zlib format. They should probably have called the second one "zlib" instead to avoid confusion with the raw deflate compressed data format. While the HTTP 1.1 RFC 2616 correctly points to the zlib specification in RFC 1950 for the "deflate" transfer encoding, there have been reports of servers and browsers that incorrectly produce or expect raw deflate data per the deflate specification in RFC 1951, most notably Microsoft. So even though the "deflate" transfer encoding using the zlib format would be the more efficient approach (and in fact exactly what the zlib format was designed for), using the "gzip" transfer encoding is probably more reliable due to an unfortunate choice of name on the part of the HTTP 1.1 authors.

Bottom line: use the gzip format for HTTP 1.1 encoding.

40. Does zlib support the new "Deflate64" format introduced by PKWare?

No. PKWare has apparently decided to keep that format proprietary, since they have not documented it as they have previous compression formats. In any case, the compression improvements are so modest compared to other more modern approaches, that it's not worth the effort to implement.

41. I'm having a problem with the zip functions in zlib, can you help?

There are no zip functions in zlib. You are probably using minizip by Giles Vollant, which is found in the contrib directory of zlib. It is not part of zlib. In fact none of the stuff in contrib is part of zlib. The files in there are not supported by the zlib authors. You need to contact the authors of the respective contribution for help.

42. The match.asm code in contrib is under the GNU General Public License.

Since it's part of zlib, doesn't that mean that all of zlib falls under the GNU GPL?

No. The files in contrib are not part of zlib. They were contributed by other authors and are provided as a convenience to the user within the zlib distribution. Each item in contrib has its own license.

43. Is zlib subject to export controls? What is its ECCN?

zlib is not subject to export controls, and so is classified as EAR99.

44. Can you please sign these lengthy legal documents and fax them back to us so that we can use your software in our product?

No. Go away. Shoo.

Found in path(s):

* /opt/cola/permits/1397844474_1661343334.7470329/0/zlib-1-2-11-dfsg-orig-2-tar-xz/zlib-1.2.11/FAQ

No license file was found, but licenses were detected in source scan.

```
/* gun.c -- simple gunzip to give an example of the use of inflateBack()
```

```
* Copyright (C) 2003, 2005, 2008, 2010, 2012 Mark Adler
```

```
* For conditions of distribution and use, see copyright notice in zlib.h
```

```
Version 1.7 12 August 2012 Mark Adler */
```

Found in path(s):

* /opt/cola/permits/1397844474_1661343334.7470329/0/zlib-1-2-11-dfsg-orig-2-tar-xz/zlib-1.2.11/examples/gun.c

No license file was found, but licenses were detected in source scan.

```
/* trees.c -- output deflated data using Huffman coding
```

```
* Copyright (C) 1995-2017 Jean-loup Gailly
```

```
* detect_data_type() function provided freely by Cosmin Truta, 2006
```

```
* For conditions of distribution and use, see copyright notice in zlib.h
```

```
*/
```

Found in path(s):

* /opt/cola/permits/1397844474_1661343334.7470329/0/zlib-1-2-11-dfsg-orig-2-tar-xz/zlib-1.2.11/trees.c

No license file was found, but licenses were detected in source scan.

```
/* zip.h -- IO on .zip files using zlib
```

```
Version 1.1, February 14h, 2010
```

```
part of the MiniZip project - ( http://www.winimage.com/zLibDll/minizip.html )
```

```
Copyright (C) 1998-2010 Gilles Vollant (minizip) ( http://www.winimage.com/zLibDll/minizip.html )
```

```
Modifications for Zip64 support
```

```
Copyright (C) 2009-2010 Mathias Svensson ( http://result42.com )
```

```
For more info read MiniZip_info.txt
```

Condition of use and distribution are the same than zlib :

This software is provided 'as-is', without any express or implied

warranty. In no event will the authors be held liable for any damages arising from the use of this software.

Permission is granted to anyone to use this software for any purpose, including commercial applications, and to alter it and redistribute it freely, subject to the following restrictions:

1. The origin of this software must not be misrepresented; you must not claim that you wrote the original software. If you use this software in a product, an acknowledgment in the product documentation would be appreciated but is not required.
2. Altered source versions must be plainly marked as such, and must not be misrepresented as being the original software.
3. This notice may not be removed or altered from any source distribution.

Changes

See header of zip.h

*/

Found in path(s):

* /opt/cola/permits/1397844474_1661343334.7470329/0/zlib-1-2-11-dfsg-orig-2-tar-xz/zlib-1.2.11/contrib/minizip/zip.h

No license file was found, but licenses were detected in source scan.

/* infcover.c -- test zlib's inflate routines with full code coverage

* Copyright (C) 2011, 2016 Mark Adler

* For conditions of distribution and use, see copyright notice in zlib.h

*/

Found in path(s):

* /opt/cola/permits/1397844474_1661343334.7470329/0/zlib-1-2-11-dfsg-orig-2-tar-xz/zlib-1.2.11/test/infcover.c

No license file was found, but licenses were detected in source scan.

For conditions of distribution and use, see copyright notice in zlib.h

Found in path(s):

* /opt/cola/permits/1397844474_1661343334.7470329/0/zlib-1-2-11-dfsg-orig-2-tar-xz/zlib-1.2.11/old/Makefile.emx

* /opt/cola/permits/1397844474_1661343334.7470329/0/zlib-1-2-11-dfsg-orig-2-tar-xz/zlib-1.2.11/old/os2/Makefile.os2

* /opt/cola/permits/1397844474_1661343334.7470329/0/zlib-1-2-11-dfsg-orig-2-tar-xz/zlib-1.2.11/win32/Makefile.gcc

* /opt/cola/permits/1397844474_1661343334.7470329/0/zlib-1-2-11-dfsg-orig-2-tar-xz/zlib-

1.2.11/msdos/Makefile.emx

* /opt/cola/permits/1397844474_1661343334.7470329/0/zlib-1-2-11-dfsg-orig-2-tar-xz/zlib-

1.2.11/msdos/Makefile.dj2

No license file was found, but licenses were detected in source scan.

/* compress.c -- compress a memory buffer

* Copyright (C) 1995-2005, 2014, 2016 Jean-loup Gailly, Mark Adler

* For conditions of distribution and use, see copyright notice in zlib.h

*/

Found in path(s):

* /opt/cola/permits/1397844474_1661343334.7470329/0/zlib-1-2-11-dfsg-orig-2-tar-xz/zlib-1.2.11/compress.c

No license file was found, but licenses were detected in source scan.

/*

* gzlog.c

* Copyright (C) 2004, 2008, 2012, 2016 Mark Adler, all rights reserved

* For conditions of distribution and use, see copyright notice in gzlog.h

* version 2.2, 14 Aug 2012

*/

Found in path(s):

* /opt/cola/permits/1397844474_1661343334.7470329/0/zlib-1-2-11-dfsg-orig-2-tar-xz/zlib-

1.2.11/examples/gzlog.c

No license file was found, but licenses were detected in source scan.

/* inffast.h -- header to use inffast.c

* Copyright (C) 1995-2003, 2010 Mark Adler

* For conditions of distribution and use, see copyright notice in zlib.h

*/

Found in path(s):

* /opt/cola/permits/1397844474_1661343334.7470329/0/zlib-1-2-11-dfsg-orig-2-tar-xz/zlib-1.2.11/inffast.h

No license file was found, but licenses were detected in source scan.

/* fitblk.c: example of fitting compressed output to a specified size

Not copyrighted -- provided to the public domain

Version 1.1 25 November 2004 Mark Adler */

Found in path(s):

* /opt/cola/permits/1397844474_1661343334.7470329/0/zlib-1-2-11-dfsg-orig-2-tar-xz/zlib-

1.2.11/examples/fitblk.c

No license file was found, but licenses were detected in source scan.

ZLIB DATA COMPRESSION LIBRARY

zlib 1.2.11 is a general purpose data compression library. All the code is thread safe. The data format used by the zlib library is described by RFCs

(Request for Comments) 1950 to 1952 in the files
<http://www.ietf.org/rfc/rfc1950.txt> (zlib format), [rfc1951.txt](http://www.ietf.org/rfc/rfc1951.txt) (deflate format)
and [rfc1952.txt](http://www.ietf.org/rfc/rfc1952.txt) (gzip format).

All functions of the compression library are documented in the file `zlib.h`
(volunteer to write man pages welcome, contact zlib@gzip.org). Two compiled
examples are distributed in this package, `example` and `minigzip`. The `example_d`
and `minigzip_d` flavors validate that the `zlib1.dll` file is working correctly.

Questions about zlib should be sent to [<zlib@gzip.org>](mailto:zlib@gzip.org). The zlib home page
is <http://zlib.net/>. Before reporting a problem, please check this site to
verify that you have the latest version of zlib; otherwise get the latest
version and check whether the problem still exists
or not.

PLEASE read `DLL_FAQ.txt`, and the the zlib FAQ http://zlib.net/zlib_faq.html
before asking for help.

Manifest:

The package `zlib-1.2.11-win32-x86.zip` will contain the following files:

`README-WIN32.txt` This document
`ChangeLog` Changes since previous zlib packages
`DLL_FAQ.txt` Frequently asked questions about `zlib1.dll`
`zlib.3.pdf` Documentation of this library in Adobe Acrobat format

`example.exe` A statically-bound example (using `zlib.lib`, not the dll)
`example.pdb` Symbolic information for debugging `example.exe`

`example_d.exe` A `zlib1.dll` bound example (using `zdll.lib`)
`example_d.pdb` Symbolic information for debugging `example_d.exe`

`minigzip.exe` A statically-bound test program (using `zlib.lib`, not the dll)
`minigzip.pdb` Symbolic information for debugging `minigzip.exe`

`minigzip_d.exe` A `zlib1.dll` bound test program (using `zdll.lib`)
`minigzip_d.pdb` Symbolic information for debugging `minigzip_d.exe`

`zlib.h`
Install these files into the compilers' `INCLUDE` path to
`zconf.h` compile programs which use `zlib.lib` or `zdll.lib`

`zdll.lib` Install these files into the compilers' `LIB` path if linking
`zdll.exp` a compiled program to the `zlib1.dll` binary

`zlib.lib` Install these files into the compilers' `LIB` path to link zlib

zlib.pdb into compiled programs, without zlib1.dll runtime dependency
(zlib.pdb provides debugging info to the compile time linker)

zlib1.dll Install this binary shared library into the system PATH, or
the program's runtime directory (where the .exe resides)

zlib1.pdb Install in the same directory as zlib1.dll, in order to debug
an application crash using WinDbg or similar tools.

All .pdb files above are entirely optional, but are very useful to a developer attempting to diagnose program misbehavior or a crash. Many additional important files for developers can be found in the zlib127.zip source package available from <http://zlib.net/> - review that package's README file for details.

Acknowledgments:

The deflate format used by zlib was defined by Phil Katz. The deflate and zlib specifications were written by L. Peter Deutsch. Thanks to all the people who reported problems and suggested various improvements in zlib; they are too numerous to cite here.

Copyright notice:

(C) 1995-2017 Jean-loup Gailly and Mark Adler

This software is provided 'as-is', without any express or implied warranty. In no event will the authors be held liable for any damages arising from the use of this software.

Permission is granted to anyone to use this software for any purpose, including commercial applications, and to alter it and redistribute it freely, subject to the following restrictions:

1. The origin of this software must not be misrepresented; you must not claim that you wrote the original software. If you use this software in a product, an acknowledgment in the product documentation would be appreciated but is not required.
2. Altered source versions must be plainly marked as such, and must not be misrepresented as being the original software.
3. This notice may not be removed or altered from any source distribution.

Jean-loup Gailly Mark Adler
jloup@gzip.org madler@alumni.caltech.edu

If you use the zlib library in a product, we would appreciate *not* receiving lengthy legal documents to sign. The sources are provided for free but without

warranty of any kind. The library has been entirely written by Jean-loup Gailly and Mark Adler; it does not include third-party code.

If you redistribute modified sources, we would appreciate that you include in the file ChangeLog history information documenting your changes. Please read the FAQ for more information on the distribution of modified source versions.

Found in path(s):

```
* /opt/cola/permits/1397844474_1661343334.7470329/0/zlib-1-2-11-dfsg-orig-2-tar-xz/zlib-1.2.11/win32/README-WIN32.txt
```

No license file was found, but licenses were detected in source scan.

```
/* zutil.c -- target dependent utility functions for the compression library
```

```
* Copyright (C) 1995-2017 Jean-loup Gailly
```

```
* For conditions of distribution and use, see copyright notice in zlib.h
```

```
*/
```

Found in path(s):

```
* /opt/cola/permits/1397844474_1661343334.7470329/0/zlib-1-2-11-dfsg-orig-2-tar-xz/zlib-1.2.11/zutil.c
```

No license file was found, but licenses were detected in source scan.

```
/* gzappend -- command to append to a gzip file
```

Copyright (C) 2003, 2012 Mark Adler, all rights reserved

version 1.2, 11 Oct 2012

This software is provided 'as-is', without any express or implied warranty. In no event will the author be held liable for any damages arising from the use of this software.

Permission is granted to anyone to use this software for any purpose, including commercial applications, and to alter it and redistribute it freely, subject to the following restrictions:

1. The origin of this software must not be misrepresented; you must not claim that you wrote the original software. If you use this software in a product, an acknowledgment in the product documentation would be appreciated but is not required.
2. Altered source versions must be plainly marked as such, and must not be misrepresented as being the original software.
3. This notice may not be removed or altered from any source distribution.

Mark Adler madler@alumni.caltech.edu

```
*/
```

Found in path(s):

```
* /opt/cola/permits/1397844474_1661343334.7470329/0/zlib-1-2-11-dfsg-orig-2-tar-xz/zlib-
```

1.2.11/examples/gzappend.c

No license file was found, but licenses were detected in source scan.

```
/* inffast.c -- fast decoding
```

```
* Copyright (C) 1995-2017 Mark Adler
```

```
* For conditions of distribution and use, see copyright notice in zlib.h
```

```
*/
```

Found in path(s):

```
* /opt/cola/permits/1397844474_1661343334.7470329/0/zlib-1-2-11-dfsg-orig-2-tar-xz/zlib-1.2.11/inffast.c
```

No license file was found, but licenses were detected in source scan.

```
/* inflate.c -- zlib decompression
```

```
* Copyright (C) 1995-2016 Mark Adler
```

```
* For conditions of distribution and use, see copyright notice in zlib.h
```

```
*/
```

Found in path(s):

```
* /opt/cola/permits/1397844474_1661343334.7470329/0/zlib-1-2-11-dfsg-orig-2-tar-xz/zlib-1.2.11/inflate.c
```

No license file was found, but licenses were detected in source scan.

```
/* zlib.h -- interface of the 'zlib' general purpose compression library
version 1.2.11, January 15th, 2017
```

Copyright (C) 1995-2017 Jean-loup Gailly and Mark Adler

This software is provided 'as-is', without any express or implied warranty. In no event will the authors be held liable for any damages arising from the use of this software.

Permission is granted to anyone to use this software for any purpose, including commercial applications, and to alter it and redistribute it freely, subject to the following restrictions:

1. The origin of this software must not be misrepresented; you must not claim that you wrote the original software. If you use this software in a product, an acknowledgment in the product documentation would be appreciated but is not required.
2. Altered source versions must be plainly marked as such, and must not be misrepresented as being the original software.
3. This notice may not be removed or altered from any source distribution.

Jean-loup Gailly

Mark Adler

jloup@gzip.org

madler@alumni.caltech.edu

The data format used by the zlib library is described by RFCs (Request for Comments) 1950 to 1952 in the files <http://tools.ietf.org/html/rfc1950>

(zlib format), rfc1951 (deflate format) and rfc1952 (gzip format).

*/

Found in path(s):

* /opt/cola/permits/1397844474_1661343334.7470329/0/zlib-1-2-11-dfsg-orig-2-tar-xz/zlib-1.2.11/zlib.h

No license file was found, but licenses were detected in source scan.

/* example.c -- usage example of the zlib compression library

* Copyright (C) 1995-2006, 2011, 2016 Jean-loup Gailly

* For conditions of distribution and use, see copyright notice in zlib.h

*/

Found in path(s):

* /opt/cola/permits/1397844474_1661343334.7470329/0/zlib-1-2-11-dfsg-orig-2-tar-xz/zlib-1.2.11/test/example.c

No license file was found, but licenses were detected in source scan.

/* unzip.c -- IO for uncompress .zip files using zlib

Version 1.1, February 14h, 2010

part of the MiniZip project - (<http://www.winimage.com/zLibDll/minizip.html>)

Copyright (C) 1998-2010 Gilles Vollant (minizip) (<http://www.winimage.com/zLibDll/minizip.html>)

Modifications of Unzip for Zip64

Copyright (C) 2007-2008 Even Rouault

Modifications for Zip64 support on both zip and unzip

Copyright (C) 2009-2010 Mathias Svensson (<http://result42.com>)

For more info read MiniZip_info.txt

Decryption code comes from crypt.c by Info-ZIP but has been greatly reduced in terms of compatibility with older software. The following is from the original crypt.c.

Code woven in by Terry Thorsen 1/2003.

Copyright (c) 1990-2000 Info-ZIP. All rights reserved.

See the accompanying

file LICENSE, version 2000-Apr-09 or later

(the contents of which are also included in zip.h) for terms of use.

If, for some reason, all these files are missing, the Info-ZIP license also may be found at: <ftp://ftp.info-zip.org/pub/infozip/license.html>

crypt.c (full version) by Info-ZIP. Last revised: [see crypt.h]

The encryption/decryption parts of this source code (as opposed to the non-echoing password parts) were originally written in Europe. The

whole source package can be freely distributed, including from the USA.
(Prior to January 2000, re-export from the US was a violation of US law.)

This encryption code is a direct transcription of the algorithm from Roger Schlafly, described by Phil Katz in the file appnote.txt. This file (appnote.txt) is distributed with the PKZIP program (even in the version without encryption capabilities).

Changes in unzip.c

2007-2008 - Even Rouault - Addition of cpl_unzGetCurrentFileZStreamPos
2007-2008 - Even Rouault - Decoration of symbol names unz* -> cpl_unz*
2007-2008 - Even Rouault - Remove old C style function prototypes
2007-2008 - Even Rouault - Add unzip support for ZIP64

Copyright (C) 2007-2008 Even Rouault

Oct-2009 - Mathias Svensson - Removed cpl_* from symbol names (Even Rouault added them but since this is now moved to a new project (minizip64) I renamed them again).

Oct-2009 - Mathias Svensson - Fixed problem if uncompressed size was > 4G and compressed size was <4G
should only read the compressed/uncompressed size from the Zip64 format if
the size from normal header was 0xFFFFFFFF

Oct-2009 - Mathias Svensson - Applied some bug fixes from patches received from Gilles Vollant

Oct-2009 - Mathias Svensson - Applied support to unzip files with compression method
BZIP2 (bzip2 lib is required)

Patch created by Daniel Borca

Jan-2010 - back to unzip and minizip 1.0 name scheme, with compatibility layer

Copyright (C) 1998 - 2010 Gilles Vollant, Even Rouault, Mathias Svensson

*/

Found in path(s):

* /opt/cola/permits/1397844474_1661343334.7470329/0/zlib-1-2-11-dfsg-orig-2-tar-xz/zlib-
1.2.11/contrib/minizip/unzip.c

No license file was found, but licenses were detected in source scan.

/* crc32.c -- compute the CRC-32 of a data stream

* Copyright (C) 1995-2006, 2010, 2011, 2012, 2016 Mark Adler

* For conditions of distribution and use, see copyright notice in zlib.h

*

* Thanks to Rodney Brown <rbrown64@csc.com.au> for his contribution of faster

* CRC methods: exclusive-oring 32 bits of data at a time, and pre-computing

* tables for updating the shift register in one step with three exclusive-ors

* instead of four steps with four exclusive-ors. This results in about a
* factor of two increase in speed on a Power PC G4 (PPC7455) using gcc -O3.
*/

Found in path(s):

* /opt/cola/permits/1397844474_1661343334.7470329/0/zlib-1-2-11-dfsg-orig-2-tar-xz/zlib-1.2.11/crc32.c

No license file was found, but licenses were detected in source scan.

/* inftrees.h -- header to use inftrees.c

* Copyright (C) 1995-2005, 2010 Mark Adler

* For conditions of distribution and use, see copyright notice in zlib.h

*/

Found in path(s):

* /opt/cola/permits/1397844474_1661343334.7470329/0/zlib-1-2-11-dfsg-orig-2-tar-xz/zlib-1.2.11/inftrees.h

No license file was found, but licenses were detected in source scan.

Frequently Asked Questions about ZLIB1.DLL

This document describes the design, the rationale, and the usage of the official DLL build of zlib, named ZLIB1.DLL. If you have general questions about zlib, you should see the file "FAQ" found in the zlib distribution, or at the following location:

http://www.gzip.org/zlib/zlib_faq.html

1. What is ZLIB1.DLL, and how can I get it?

- ZLIB1.DLL is the official build of zlib as a DLL.
(Please remark the character '1' in the name.)

Pointers to a precompiled ZLIB1.DLL can be found in the zlib web site at:

<http://www.zlib.net/>

Applications that link to ZLIB1.DLL can rely on the following specification:

- * The exported symbols are exclusively defined in the source files "zlib.h" and "zlib.def", found in an official zlib source distribution.
- * The symbols are exported by name, not by ordinal.
- * The exported names are undecorated.
- * The calling convention of functions is "C" (CDECL).
- * The ZLIB1.DLL binary is linked to MSVCRT.DLL.

The archive in which ZLIB1.DLL is bundled contains compiled

test programs that must run with a valid build of ZLIB1.DLL. It is recommended to download the prebuilt DLL from the zlib web site, instead of building it yourself, to avoid potential incompatibilities that could be introduced by your compiler and build settings. If you do build the DLL yourself, please make sure that it complies with all the above requirements, and it runs with the precompiled test programs, bundled with the original ZLIB1.DLL distribution.

If, for any reason, you need to build an incompatible DLL, please use a different file name.

2. Why did you change the name of the DLL to ZLIB1.DLL?

What happened to the old ZLIB.DLL?

- The old ZLIB.DLL, built from zlib-1.1.4 or earlier, required compilation settings that were incompatible to those used by

a static build. The DLL settings were supposed to be enabled by defining the macro ZLIB_DLL, before including "zlib.h". Incorrect handling of this macro was silently accepted at build time, resulting in two major problems:

* ZLIB_DLL was missing from the old makefile. When building the DLL, not all people added it to the build options. In consequence, incompatible incarnations of ZLIB.DLL started to circulate around the net.

* When switching from using the static library to using the DLL, applications had to define the ZLIB_DLL macro and to recompile all the sources that contained calls to zlib functions. Failure to do so resulted in creating binaries that were unable to run with the official ZLIB.DLL build.

The only possible solution that we could foresee was to make a binary-incompatible change in the DLL interface, in order to remove the dependency on the ZLIB_DLL macro, and to release the new DLL under a different name.

We chose the name ZLIB1.DLL, where '1' indicates the major zlib version number. We hope that we will not have to break the binary compatibility again, at least not as long as the zlib-1.x series will last.

There is still a ZLIB_DLL macro, that can trigger a more efficient build and use of the DLL, but compatibility no longer depends on it.

3. Can I build ZLIB.DLL from the new zlib sources, and replace an old ZLIB.DLL, that was built from zlib-1.1.4 or earlier?

- In principle, you can do it by assigning calling convention keywords to the macros ZEXPORT and ZEXPORTVA. In practice, it depends on what you mean by "an old ZLIB.DLL", because the old DLL exists in several mutually-incompatible versions. You have to find out first what kind of calling convention is being used in your particular ZLIB.DLL build, and to use the same one in the new build. If you don't know what this is all about, you might be better off if you would just leave the old DLL intact.

4. Can I compile my application using the new zlib interface, and link it to an old ZLIB.DLL, that was built from zlib-1.1.4 or earlier?

- The official answer is "no"; the real answer depends again on what kind of ZLIB.DLL you have. Even if you are lucky, this course of action is unreliable.

If you rebuild your application and you intend to use a newer version of zlib (post- 1.1.4), it is strongly recommended to link it to the new ZLIB1.DLL.

5. Why are the zlib symbols exported by name, and not by ordinal?

- Although exporting symbols by ordinal is a little faster, it is risky. Any single glitch in the maintenance or use of the DEF file that contains the ordinals can result in incompatible builds and frustrating crashes. Simply put, the benefits of exporting symbols by ordinal do not justify the risks.

Technically, it should be possible to maintain ordinals in the DEF file, and still export the symbols by name. Ordinals exist in every DLL, and even if the dynamic linking performed at the DLL startup is searching for names, ordinals serve as hints, for a faster name lookup. However, if the DEF file contains ordinals, the Microsoft linker automatically builds an implib that will cause the executables linked to it to use those ordinals, and not the names. It is interesting to notice that the GNU linker for Win32 does not suffer from this problem.

It is possible to avoid the DEF file if the exported symbols are accompanied by a "__declspec(dllexport)" attribute in the source files. You can do this in zlib by predefining the ZLIB_DLL macro.

6. I see that the ZLIB1.DLL functions use the "C" (CDECL) calling convention. Why not use the STDCALL convention? STDCALL is the standard convention in Win32, and I need it in my Visual Basic project!

(For readability, we use CDECL to refer to the convention triggered by the "__cdecl" keyword, STDCALL to refer to the convention triggered by "__stdcall", and FASTCALL to refer to the convention triggered by "__fastcall".)

- Most of the native Windows API functions (without varargs) use indeed the WINAPI convention (which translates to STDCALL in Win32), but the standard C functions use CDECL. If a user application is intrinsically tied to the Windows API (e.g. it calls native Windows API functions such as CreateFile()), sometimes it makes sense to decorate its own functions with WINAPI. But if ANSI C or POSIX portability is a goal (e.g. it calls standard C functions such as fopen()), it is not a sound decision to request the inclusion of <windows.h>, or to use non-ANSI constructs, for the sole purpose to make the user functions STDCALL-able.

The functionality offered by zlib is not in the category of "Windows functionality", but is more like "C functionality".

Technically, STDCALL is not bad; in fact, it is slightly faster than CDECL, and it works with variable-argument functions, just like CDECL. It is unfortunate that, in spite of using STDCALL in the Windows API, it is not the default convention used by the C compilers that run under Windows. The roots of the problem reside deep inside the unsafety of the K&R-style function prototypes, where the argument types are not specified; but that is another story for another day.

The remaining fact is that CDECL is the default convention. Even if an explicit convention is hard-coded into the function prototypes inside C headers, problems may appear. The necessity to expose the convention in users' callbacks is one of these problems.

The calling convention issues are also important when using zlib in other programming languages. Some of them, like Ada (GNAT) and Fortran (GNU G77), have C bindings implemented initially on Unix, and relying on the C calling convention. On the other hand, the pre-.NET versions of Microsoft Visual Basic require STDCALL, while Borland Delphi prefers, although it does not require, FASTCALL.

In fairness to all possible uses of zlib outside the C programming language, we choose the default "C" convention. Anyone interested in different bindings or conventions is encouraged to maintain specialized projects. The "contrib/" directory from the zlib distribution already holds a couple of foreign bindings, such as Ada, C++, and Delphi.

7. I need a DLL for my Visual Basic project. What can I do?

- Define the ZLIB_WINAPI macro before including "zlib.h", when building both the DLL and the user application (except that you don't need to define anything when using the DLL in Visual Basic). The ZLIB_WINAPI macro will switch on the WINAPI (STDCALL) convention. The name of this DLL must be different than the official ZLIB1.DLL.

Gilles Vollant has contributed a build named ZLIBWAPI.DLL, with the ZLIB_WINAPI macro turned on, and with the minizip functionality built in. For more information, please read the notes inside "contrib/vstudio/readme.txt", found in the zlib distribution.

8. I need to use zlib in my Microsoft .NET project. What can I do?

- Henrik Ravn has contributed a .NET wrapper around zlib. Look into contrib/dotzlib/, inside the zlib distribution.

9. If my application uses ZLIB1.DLL, should I link it to MSVCRT.DLL? Why?

- It is not required, but it is recommended to link your application to MSVCRT.DLL, if it uses ZLIB1.DLL.

The executables (.EXE, .DLL, etc.) that are involved in the

same process and are using the C run-time library (i.e. they are calling standard C functions), must link to the same library. There are several libraries in the Win32 system: CRTDLL.DLL, MSVCRT.DLL, the static C libraries, etc.

Since ZLIB1.DLL is linked to MSVCRT.DLL, the executables that depend on it should also be linked to MSVCRT.DLL.

10. Why are you saying that ZLIB1.DLL and my application should be linked to the same C run-time (CRT) library? I linked my application and my DLLs to different C libraries (e.g. my application to a static library, and my DLLs to MSVCRT.DLL), and everything works fine.

- If a user library invokes only pure Win32 API (accessible via <windows.h> and the related headers), its DLL build will work in any context. But if this library invokes standard C API, things get more complicated.

There is a single Win32 library in a Win32 system. Every function in this library resides in a single DLL module, that is safe to call from anywhere. On the other hand, there are multiple versions of the C library, and each of them has its own separate internal state. Standalone executables and user DLLs that call standard C functions must link to a C run-time (CRT) library, be it static or shared (DLL). Intermixing occurs when an executable (not necessarily standalone) and a DLL are linked to different CRTs, and both are running in the same process.

Intermixing multiple CRTs is possible, as long as their internal states are kept intact. The Microsoft Knowledge Base articles KB94248 "HOWTO: Use the C Run-Time" and KB140584 "HOWTO: Link with the Correct C Run-Time (CRT) Library" mention the potential problems raised by intermixing.

If intermixing works for you, it's because your application and DLLs are avoiding the corruption of each of the CRTs' internal states, maybe by careful design, or maybe by fortune.

Also note that linking ZLIB1.DLL to non-Microsoft CRTs, such as those provided by Borland, raises similar problems.

11. Why are you linking ZLIB1.DLL to MSVCRT.DLL?

- MSVCRT.DLL exists on every Windows 95 with a new service pack installed, or with Microsoft Internet Explorer 4 or later, and on all other Windows 4.x or later (Windows 98, Windows NT 4, or later). It is freely distributable; if not present in the system, it can be downloaded from Microsoft or from other software provider for free.

The fact that MSVCRT.DLL does not exist on a virgin Windows 95 is not so problematic. Windows 95 is scarcely found nowadays, Microsoft ended its support a long time ago, and many recent applications from various vendors, including Microsoft, do not even run on it. Furthermore, no serious user should run Windows 95 without a proper update installed.

12. Why are you not linking ZLIB1.DLL to <<my favorite C run-time library>> ?

- We considered and abandoned the following alternatives:

* Linking ZLIB1.DLL to a static C library (LIBC.LIB, or LIBCMT.LIB) is not a good option. People are using the DLL mainly to save disk space. If you are linking your program to a static C library, you may as well consider linking zlib in statically, too.

* Linking ZLIB1.DLL to CRTDLL.DLL looks appealing, because CRTDLL.DLL is present on every Win32 installation. Unfortunately, it has a series of problems: it does not work properly with Microsoft's C++ libraries, it does not provide support for 64-bit file offsets, (and so on...), and Microsoft discontinued its support a long time ago.

* Linking ZLIB1.DLL to MSVCR70.DLL or MSVCR71.DLL, supplied with the Microsoft .NET platform, and Visual C++ 7.0/7.1, raises problems related to the status of ZLIB1.DLL as a system component. According to the Microsoft Knowledge Base article KB326922 "INFO: Redistribution of the Shared C Runtime Component in Visual C++ .NET", MSVCR70.DLL and MSVCR71.DLL are not supposed to function as system DLLs, because they may clash with MSVCRT.DLL. Instead, the application's installer is supposed to put these DLLs (if needed) in the application's private directory. If ZLIB1.DLL depends on a non-system runtime, it cannot function as a redistributable system component.

* Linking ZLIB1.DLL to non-Microsoft runtimes, such as Borland's, or Cygwin's, raises problems related to the reliable presence of these runtimes on Win32 systems. It's easier to let the DLL build of zlib up to the people who distribute these runtimes, and who may proceed as explained in the answer to Question 14.

13. If ZLIB1.DLL cannot be linked to MSVCR70.DLL or MSVCR71.DLL, how can I build/use ZLIB1.DLL in Microsoft Visual C++ 7.0 (Visual Studio .NET) or newer?

- Due to the problems explained in the Microsoft Knowledge Base article KB326922 (see the previous answer), the C runtime that comes with the VC7 environment is no longer considered a system component. That is, it should not be assumed that this runtime exists, or may be installed in a system directory. Since ZLIB1.DLL is supposed to be a system component, it may not depend on a non-system component.

In order to link ZLIB1.DLL and your application to MSVCRT.DLL in VC7, you need the library of Visual C++ 6.0 or older. If you don't have this library at hand, it's probably best not to use ZLIB1.DLL.

We are hoping that, in the future, Microsoft will provide a way to build applications linked to a proper system runtime, from the Visual C++ environment. Until then, you have a couple of alternatives, such as linking zlib in statically. If your application requires dynamic linking, you may proceed as explained in the answer to Question 14.

14. I need to link my own DLL build to a CRT different than MSVCRT.DLL. What can I do?

- Feel free to rebuild the DLL from the zlib sources, and link it the way you want. You should, however, clearly state that your build is unofficial. You should give it a different file name, and/or install it in a private directory that can be accessed by your application only, and is not visible to the others (i.e. it's neither in the PATH, nor in the SYSTEM or SYSTEM32 directories). Otherwise, your build may clash with applications that link to the official build.

For example, in Cygwin, zlib is linked to the Cygwin runtime CYGWIN1.DLL, and it is distributed under the name CYGZ.DLL.

15. May I include additional pieces of code that I find useful, link them in ZLIB1.DLL, and export them?

- No. A legitimate build of ZLIB1.DLL must not include code that does not originate from the official zlib source code. But you can make your own private DLL build, under a different file name, as suggested in the previous answer.

For example, zlib is a part of the VCL library, distributed with Borland Delphi and C++ Builder. The DLL build of VCL is a redistributable file, named VCLxx.DLL.

16. May I remove some functionality out of ZLIB1.DLL, by enabling macros like NO_GZCOMPRESS or NO_GZIP at compile time?

- No. A legitimate build of ZLIB1.DLL must provide the complete zlib functionality, as implemented in the official zlib source code. But you can make your own private DLL build, under a different file name, as suggested in the previous answer.

17. I made my own ZLIB1.DLL build. Can I test it for compliance?

- We prefer that you download the official DLL from the zlib web site. If you need something peculiar from this DLL, you can send your suggestion to the zlib mailing list.

However, in case you do rebuild the DLL yourself, you can run it with the test programs found in the DLL distribution.

Running these test programs is not a guarantee of compliance, but a failure can imply a detected problem.

**

This document is written and maintained by
Cosmin Truta <cosmint@cs.ubbcluj.ro>

Found in path(s):

* /opt/cola/permits/1397844474_1661343334.7470329/0/zlib-1-2-11-dfsg-orig-2-tar-xz/zlib-1.2.11/win32/DLL_FAQ.txt

No license file was found, but licenses were detected in source scan.

```
/* zran.c -- example of zlib/gzip stream indexing and random access
* Copyright (C) 2005, 2012 Mark Adler
* For conditions of distribution and use, see copyright notice in zlib.h
Version 1.1 29 Sep 2012 Mark Adler */
```

Found in path(s):

```
*/opt/cola/permits/1397844474_1661343334.7470329/0/zlib-1-2-11-dfsg-orig-2-tar-xz/zlib-1.2.11/examples/zran.c
```

No license file was found, but licenses were detected in source scan.

```
/* inftrees.c -- generate Huffman trees for efficient decoding
* Copyright (C) 1995-2017 Mark Adler
* For conditions of distribution and use, see copyright notice in zlib.h
*/
```

Found in path(s):

```
*/opt/cola/permits/1397844474_1661343334.7470329/0/zlib-1-2-11-dfsg-orig-2-tar-xz/zlib-1.2.11/inftrees.c
```

No license file was found, but licenses were detected in source scan.

```
/* infback.c -- inflate using a call-back interface
* Copyright (C) 1995-2016 Mark Adler
* For conditions of distribution and use, see copyright notice in zlib.h
*/
```

Found in path(s):

```
*/opt/cola/permits/1397844474_1661343334.7470329/0/zlib-1-2-11-dfsg-orig-2-tar-xz/zlib-1.2.11/infback.c
```

No license file was found, but licenses were detected in source scan.

```
/* gzguts.h -- zlib internal header definitions for gz* operations
* Copyright (C) 2004, 2005, 2010, 2011, 2012, 2013, 2016 Mark Adler
* For conditions of distribution and use, see copyright notice in zlib.h
*/
```

Found in path(s):

```
*/opt/cola/permits/1397844474_1661343334.7470329/0/zlib-1-2-11-dfsg-orig-2-tar-xz/zlib-1.2.11/gzguts.h
```

1.89 systemd 237-3ubuntu10.56

1.89.1 Available under license :

GNU GENERAL PUBLIC LICENSE
Version 2, June 1991

Copyright (C) 1989, 1991 Free Software Foundation, Inc.,
51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA
Everyone is permitted to copy and distribute verbatim copies
of this license document, but changing it is not allowed.

Preamble

The licenses for most software are designed to take away your freedom to share and change it. By contrast, the GNU General Public License is intended to guarantee your freedom to share and change free software--to make sure the software is free for all its users. This General Public License applies to most of the Free Software Foundation's software and to any other program whose authors commit to using it. (Some other Free Software Foundation software is covered by the GNU Lesser General Public License instead.) You can apply it to your programs, too.

When we speak of free software, we are referring to freedom, not price. Our General Public Licenses are designed to make sure that you have the freedom to distribute copies of free software (and charge for this service if you wish), that you receive source code or can get it if you want it, that you can change the software or use pieces of it in new free programs; and that you know you can do these things.

To protect your rights, we need to make restrictions that forbid anyone to deny you these rights or to ask you to surrender the rights. These restrictions translate to certain responsibilities for you if you distribute copies of the software, or if you modify it.

For example, if you distribute copies of such a program, whether gratis or for a fee, you must give the recipients all the rights that you have. You must make sure that they, too, receive or can get the source code. And you must show them these terms so they know their rights.

We protect your rights with two steps: (1) copyright the software, and (2) offer you this license which gives you legal permission to copy, distribute and/or modify the software.

Also, for each author's protection and ours, we want to make certain that everyone understands that there is no warranty for this free software. If the software is modified by someone else and passed on, we want its recipients to know that what they have is not the original, so that any problems introduced by others will not reflect on the original authors' reputations.

Finally, any free program is threatened constantly by software patents. We wish to avoid the danger that redistributors of a free program will individually obtain patent licenses, in effect making the program proprietary. To prevent this, we have made it clear that any patent must be licensed for everyone's free use or not licensed at all.

The precise terms and conditions for copying, distribution and modification follow.

GNU GENERAL PUBLIC LICENSE
TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

0. This License applies to any program or other work which contains a notice placed by the copyright holder saying it may be distributed under the terms of this General Public License. The "Program", below, refers to any such program or work, and a "work based on the Program" means either the Program or any derivative work under copyright law: that is to say, a work containing the Program or a portion of it, either verbatim or with modifications and/or translated into another language. (Hereinafter, translation is included without limitation in the term "modification".) Each licensee is addressed as "you".

Activities other than copying, distribution and modification are not covered by this License; they are outside its scope. The act of running the Program is not restricted, and the output from the Program is covered only if its contents constitute a work based on the Program (independent of having been made by running the Program). Whether that is true depends on what the Program does.

1. You may copy and distribute verbatim copies of the Program's source code as you receive it, in any medium, provided that you conspicuously and appropriately publish on each copy an appropriate copyright notice and disclaimer of warranty; keep intact all the notices that refer to this License and to the absence of any warranty; and give any other recipients of the Program a copy of this License along with the Program.

You may charge a fee for the physical act of transferring a copy, and you may at your option offer warranty protection in exchange for a fee.

2. You may modify your copy or copies of the Program or any portion of it, thus forming a work based on the Program, and copy and distribute such modifications or work under the terms of Section 1 above, provided that you also meet all of these conditions:

- a) You must cause the modified files to carry prominent notices stating that you changed the files and the date of any change.
- b) You must cause any work that you distribute or publish, that in whole or in part contains or is derived from the Program or any part thereof, to be licensed as a whole at no charge to all third

parties under the terms of this License.

c) If the modified program normally reads commands interactively when run, you must cause it, when started running for such interactive use in the most ordinary way, to print or display an announcement including an appropriate copyright notice and a notice that there is no warranty (or else, saying that you provide a warranty) and that users may redistribute the program under these conditions, and telling the user how to view a copy of this License. (Exception: if the Program itself is interactive but does not normally print such an announcement, your work based on the Program is not required to print an announcement.)

These requirements apply to the modified work as a whole. If identifiable sections of that work are not derived from the Program, and can be reasonably considered independent and separate works in themselves, then this License, and its terms, do not apply to those sections when you distribute them as separate works. But when you distribute the same sections as part of a whole which is a work based on the Program, the distribution of the whole must be on the terms of this License, whose permissions for other licensees extend to the entire whole, and thus to each and every part regardless of who wrote it.

Thus, it is not the intent of this section to claim rights or contest your rights to work written entirely by you; rather, the intent is to exercise the right to control the distribution of derivative or collective works based on the Program.

In addition, mere aggregation of another work not based on the Program with the Program (or with a work based on the Program) on a volume of a storage or distribution medium does not bring the other work under the scope of this License.

3. You may copy and distribute the Program (or a work based on it, under Section 2) in object code or executable form under the terms of Sections 1 and 2 above provided that you also do one of the following:

a) Accompany it with the complete corresponding machine-readable source code, which must be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange; or,

b) Accompany it with a written offer, valid for at least three years, to give any third party, for a charge no more than your cost of physically performing source distribution, a complete machine-readable copy of the corresponding source code, to be distributed under the terms of Sections 1 and 2 above on a medium

customarily used for software interchange; or,

c) Accompany it with the information you received as to the offer to distribute corresponding source code. (This alternative is allowed only for noncommercial distribution and only if you received the program in object code or executable form with such an offer, in accord with Subsection b above.)

The source code for a work means the preferred form of the work for making modifications to it. For an executable work, complete source code means all the source code for all modules it contains, plus any associated interface definition files, plus the scripts used to control compilation and installation of the executable. However, as a special exception, the source code distributed need not include anything that is normally distributed (in either source or binary form) with the major components (compiler, kernel, and so on) of the operating system on which the executable runs, unless that component itself accompanies the executable.

If distribution of executable or object code is made by offering access to copy from a designated place, then offering equivalent access to copy the source code from the same place counts as distribution of the source code, even though third parties are not compelled to copy the source along with the object code.

4. You may not copy, modify, sublicense, or distribute the Program except as expressly provided under this License. Any attempt otherwise to copy, modify, sublicense or distribute the Program is void, and will automatically terminate your rights under this License. However, parties who have received copies, or rights, from you under this License will not have their licenses terminated so long as such parties remain in full compliance.

5. You are not required to accept this License, since you have not signed it. However, nothing else grants you permission to modify or distribute the Program or its derivative works. These actions are prohibited by law if you do not accept this License. Therefore, by modifying or distributing the Program (or any work based on the Program), you indicate your acceptance of this License to do so, and all its terms and conditions for copying, distributing or modifying the Program or works based on it.

6. Each time you redistribute the Program (or any work based on the Program), the recipient automatically receives a license from the original licensor to copy, distribute or modify the Program subject to

these terms and conditions. You may not impose any further restrictions on the recipients' exercise of the rights granted herein. You are not responsible for enforcing compliance by third parties to this License.

7. If, as a consequence of a court judgment or allegation of patent infringement or for any other reason (not limited to patent issues), conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot distribute so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not distribute the Program at all. For example, if a patent license would not permit royalty-free redistribution of the Program by all those who receive copies directly or indirectly through you, then the only way you could satisfy both it and this License would be to refrain entirely from distribution of the Program.

If any portion of this section is held invalid or unenforceable under any particular circumstance, the balance of the section is intended to apply and the section as a whole is intended to apply in other circumstances.

It is not the purpose of this section to induce you to infringe any patents or other property right claims or to contest validity of any such claims; this section has the sole purpose of protecting the integrity of the free software distribution system, which is implemented by public license practices. Many people have made generous contributions to the wide range of software distributed through that system in reliance on consistent application of that system; it is up to the author/donor to decide if he or she is willing to distribute software through any other system and a licensee cannot impose that choice.

This section is intended to make thoroughly clear what is believed to be a consequence of the rest of this License.

8. If the distribution and/or use of the Program is restricted in certain countries either by patents or by copyrighted interfaces, the original copyright holder who places the Program under this License may add an explicit geographical distribution limitation excluding those countries, so that distribution is permitted only in or among countries not thus excluded. In such case, this License incorporates the limitation as if written in the body of this License.

9. The Free Software Foundation may publish revised and/or new versions

of the General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Program specifies a version number of this License which applies to it and "any later version", you have the option of following the terms and conditions either of that version or of any later version published by the Free Software Foundation. If the Program does not specify a version number of this License, you may choose any version ever published by the Free Software Foundation.

10. If you wish to incorporate parts of the Program into other free programs whose distribution conditions are different, write to the author to ask for permission. For software which is copyrighted by the Free Software Foundation, write to the Free Software Foundation; we sometimes make exceptions for this. Our decision will be guided by the two goals of preserving the free status of all derivatives of our free software and of promoting the sharing and reuse of software generally.

NO WARRANTY

11. BECAUSE THE PROGRAM IS LICENSED FREE OF CHARGE, THERE IS NO WARRANTY FOR THE PROGRAM, TO THE EXTENT PERMITTED BY APPLICABLE LAW.

EXCEPT WHEN

OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE PROGRAM "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE PROGRAM IS WITH YOU. SHOULD THE PROGRAM PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

12. IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY AND/OR REDISTRIBUTE THE PROGRAM AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE PROGRAM (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE PROGRAM TO OPERATE WITH ANY OTHER PROGRAMS), EVEN

IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Programs

If you develop a new program, and you want it to be of the greatest possible use to the public, the best way to achieve this is to make it free software which everyone can redistribute and change under these terms.

To do so, attach the following notices to the program. It is safest to attach them to the start of each source file to most effectively convey the exclusion of warranty; and each file should have at least the "copyright" line and a pointer to where the full notice is found.

<one line to give the program's name and a brief idea of what it does.>

Copyright (C) <year> <name of author>

This program is free software; you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation; either version 2 of the License, or
(at your option) any later version.

This program is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details.

You should have received a copy of the GNU General Public License along with this program; if not, write to the Free Software Foundation, Inc., 51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA.

Also add information on how to contact you by electronic and paper mail.

If the program is interactive, make it output a short notice like this when it starts in an interactive mode:

```
Gnomovision version 69, Copyright (C) year name of author
Gnomovision comes with ABSOLUTELY NO WARRANTY; for details type `show w'.
This is free software, and you are welcome to redistribute it
under certain conditions; type `show c' for details.
```

The hypothetical commands `show w' and `show c' should show the appropriate parts of the General Public License. Of course, the commands you use may be called something other than `show w' and `show c'; they could even be mouse-clicks or menu items--whatever suits your program.

You should also get your employer (if you work as a programmer) or your school, if any, to sign a "copyright disclaimer" for the program, if necessary. Here is a sample; alter the names:

Yoyodyne, Inc., hereby disclaims all copyright interest in the program
'Gnomovision' (which makes passes at compilers) written by James Hacker.

<signature of Ty Coon>, 1 April 1989
Ty Coon, President of Vice

This General Public License does not permit incorporating your program into
proprietary programs. If your program is a subroutine library, you may
consider it more useful to permit linking proprietary applications with the
library. If this is what you want to do, use the GNU Lesser General
Public License instead of this License.

1.90 libsystemd 237-3ubuntu10.56

1.90.1 Available under license :

GNU GENERAL PUBLIC LICENSE
Version 2, June 1991

Copyright (C) 1989, 1991 Free Software Foundation, Inc.,
51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA
Everyone is permitted to copy and distribute verbatim copies
of this license document, but changing it is not allowed.

Preamble

The licenses for most software are designed to take away your
freedom to share and change it. By contrast, the GNU General Public
License is intended to guarantee your freedom to share and change free
software--to make sure the software is free for all its users. This
General Public License applies to most of the Free Software
Foundation's software and to any other program whose authors commit to
using it. (Some other Free Software Foundation software is covered by
the GNU Lesser General Public License instead.) You can apply it to
your programs, too.

When we speak of free software, we are referring to freedom, not
price. Our General Public Licenses are designed
to make sure that you
have the freedom to distribute copies of free software (and charge for
this service if you wish), that you receive source code or can get it
if you want it, that you can change the software or use pieces of it
in new free programs; and that you know you can do these things.

To protect your rights, we need to make restrictions that forbid
anyone to deny you these rights or to ask you to surrender the rights.
These restrictions translate to certain responsibilities for you if you
distribute copies of the software, or if you modify it.

For example, if you distribute copies of such a program, whether gratis or for a fee, you must give the recipients all the rights that you have. You must make sure that they, too, receive or can get the source code. And you must show them these terms so they know their rights.

We protect your rights with two steps: (1) copyright the software, and (2) offer you this license which gives you legal permission to copy, distribute and/or modify the software.

Also, for each author's protection and ours, we want to make certain that everyone understands that there is no warranty for this free software. If the software is modified by someone else and passed on, we want its recipients to know that what they have is not the original, so that any problems introduced by others will not reflect on the original authors' reputations.

Finally, any free program is threatened constantly by software patents. We wish to avoid the danger that redistributors of a free program will individually obtain patent licenses, in effect making the program proprietary. To prevent this, we have made it clear that any patent must be licensed for everyone's free use or not licensed at all.

The precise terms and conditions for copying, distribution and modification follow.

GNU GENERAL PUBLIC LICENSE TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

0. This License applies to any program or other work which contains a notice placed by the copyright holder saying it may be distributed under the terms of this General Public License. The "Program", below, refers to any such program or work, and a "work based on the Program" means either the Program or any derivative work under copyright law: that is to say, a work containing the Program or a portion of it, either verbatim or with modifications and/or translated into another language. (Hereinafter, translation is included without limitation in the term "modification".) Each licensee is addressed as "you".

Activities other than copying, distribution and modification are not covered by this License; they are outside its scope. The act of running the Program is not restricted, and the output from the Program is covered only if its contents constitute a work based on the Program (independent of having been made by running the Program). Whether that is true depends on what the Program does.

1. You may copy and distribute verbatim copies of the Program's source code as you receive it, in any medium, provided that you conspicuously and appropriately publish on each copy an appropriate copyright notice and disclaimer of warranty; keep intact all the notices that refer to this License and to the absence of any warranty; and give any other recipients of the Program a copy of this License along with the Program.

You may charge a fee for the physical act of transferring a copy, and you may at your option offer warranty protection in exchange for a fee.

2. You may modify your copy or copies of the Program or any portion of it, thus forming a work based on the Program, and copy and distribute such modifications or work under the terms of Section 1 above, provided that you also meet all of these conditions:

a) You must cause the modified files to carry prominent notices stating that you changed the files and the date of any change.

b) You must cause any work that you distribute or publish, that in whole or in part contains or is derived from the Program or any part thereof, to be licensed as a whole at no charge to all third parties under the terms of this License.

c) If the modified program normally reads commands interactively when run, you must cause it, when started running for such interactive use in the most ordinary way, to print or display an announcement including an appropriate copyright notice and a notice that there is no warranty (or else, saying that you provide a warranty) and that users may redistribute the program under these conditions, and telling the user how to view a copy of this License. (Exception: if the Program itself is interactive but does not normally print such an announcement, your work based on the Program is not required to print an announcement.)

These requirements apply to the modified work as a whole. If identifiable sections of that work are not derived from the Program, and can be reasonably considered independent and separate works in themselves, then this License, and its terms, do not apply to those sections when you distribute them as separate works. But when you distribute the same sections as part of a whole which is a work based on the Program, the distribution of the whole must be on the terms of this License, whose permissions for other licensees extend to the entire whole, and thus to each and every part regardless of who wrote it.

Thus, it is not the intent of this section to claim rights or contest your rights to work written entirely by you; rather, the intent is to exercise the right to control the distribution of derivative or collective works based on the Program.

In addition, mere aggregation of another work not based on the Program with the Program (or with a work based on the Program) on a volume of a storage or distribution medium does not bring the other work under the scope of this License.

3. You may copy and distribute the Program (or a work based on it, under Section 2) in object code or executable form under the terms of Sections 1 and 2 above provided that you also do one of the following:

a) Accompany it with the complete corresponding machine-readable source code, which must be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange; or,

b) Accompany it with a written offer, valid for at least three years, to give any third party, for a charge no more than your cost of physically performing source distribution, a complete machine-readable copy of the corresponding source code, to be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange; or,

c) Accompany it with the information you received as to the offer to distribute corresponding source code. (This alternative is allowed only for noncommercial distribution and only if you received the program in object code or executable form with such an offer, in accord with Subsection b above.)

The source code for a work means the preferred form of the work for making modifications to it. For an executable work, complete source code means all the source code for all modules it contains, plus any associated interface definition files, plus the scripts used to control compilation and installation of the executable. However, as a special exception, the source code distributed need not include anything that is normally distributed (in either source or binary form) with the major components (compiler, kernel, and so on) of the operating system on which the executable runs, unless that component itself accompanies the executable.

If distribution of executable or object code is made by offering access to copy from a designated place, then offering equivalent access to copy the source code from the same place counts as

distribution of the source code, even though third parties are not compelled to copy the source along with the object code.

4. You may not copy, modify, sublicense, or distribute the Program except as expressly provided under this License. Any attempt otherwise to copy, modify, sublicense or distribute the Program is void, and will automatically terminate your rights under this License. However, parties who have received copies, or rights, from you under this License will not have their licenses terminated so long as such parties remain in full compliance.

5. You are not required to accept this License, since you have not signed it. However, nothing else grants you permission to modify or distribute the Program or its derivative works. These actions are prohibited by law if you do not accept this License. Therefore, by modifying or distributing the Program (or any work based on the Program), you indicate your acceptance of this License to do so, and all its terms and conditions for copying, distributing or modifying the Program or works based on it.

6. Each time you redistribute the Program (or any work based on the Program), the recipient automatically receives a license from the original licensor to copy, distribute or modify the Program subject to these terms and conditions. You may not impose any further restrictions on the recipients' exercise of the rights granted herein. You are not responsible for enforcing compliance by third parties to this License.

7. If, as a consequence of a court judgment or allegation of patent infringement or for any other reason (not limited to patent issues), conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot distribute so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not distribute the Program at all. For example, if a patent license would not permit royalty-free redistribution of the Program by all those who receive copies directly or indirectly through you, then the only way you could satisfy both it and this License would be to refrain entirely from distribution of the Program.

If any portion of this section is held invalid or unenforceable under any particular circumstance, the balance of the section is intended to apply and the section as a whole is intended to apply in other circumstances.

It is not the purpose of this section to induce you to infringe any patents or other property right claims or to contest validity of any such claims; this section has the sole purpose of protecting the integrity of the free software distribution system, which is implemented by public license practices. Many people have made generous contributions to the wide range of software distributed through that system in reliance on consistent application of that system; it is up to the author/donor to decide if he or she is willing to distribute software through any other system and a licensee cannot impose that choice.

This section is intended to make thoroughly clear what is believed to be a consequence of the rest of this License.

8. If the distribution and/or use of the Program is restricted in certain countries either by patents or by copyrighted interfaces, the original copyright holder who places the Program under this License may add an explicit geographical distribution limitation excluding those countries, so that distribution is permitted only in or among countries not thus excluded. In such case, this License incorporates the limitation as if written in the body of this License.

9. The Free Software Foundation may publish revised and/or new versions of the General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Program specifies a version number of this License which applies to it and "any later version", you have the option of following the terms and conditions either of that version or of any later version published by the Free Software Foundation. If the Program does not specify a version number of this License, you may choose any version ever published by the Free Software Foundation.

10. If you wish to incorporate parts of the Program into other free programs whose distribution conditions are different, write to the author to ask for permission. For software which is copyrighted by the Free Software Foundation, write to the Free Software Foundation; we sometimes make exceptions for this. Our decision will be guided by the two goals of preserving the free status of all derivatives of our free software and of promoting the sharing and reuse of software generally.

NO WARRANTY

11. BECAUSE THE PROGRAM IS LICENSED FREE OF CHARGE, THERE IS NO WARRANTY FOR THE PROGRAM, TO THE EXTENT PERMITTED BY APPLICABLE LAW.

EXCEPT WHEN

OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE PROGRAM "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE PROGRAM IS WITH YOU. SHOULD THE PROGRAM PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

12. IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY AND/OR REDISTRIBUTE THE PROGRAM AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE PROGRAM (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE PROGRAM TO OPERATE WITH ANY OTHER PROGRAMS), EVEN

IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Programs

If you develop a new program, and you want it to be of the greatest possible use to the public, the best way to achieve this is to make it free software which everyone can redistribute and change under these terms.

To do so, attach the following notices to the program. It is safest to attach them to the start of each source file to most effectively convey the exclusion of warranty; and each file should have at least the "copyright" line and a pointer to where the full notice is found.

<one line to give the program's name and a brief idea of what it does.>

Copyright (C) <year> <name of author>

This program is free software; you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation; either version 2 of the License,

or

(at your option) any later version.

This program is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details.

You should have received a copy of the GNU General Public License along with this program; if not, write to the Free Software Foundation, Inc., 51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA.

Also add information on how to contact you by electronic and paper mail.

If the program is interactive, make it output a short notice like this when it starts in an interactive mode:

```
Gnomovision version 69, Copyright (C) year name of author
Gnomovision comes with ABSOLUTELY NO WARRANTY; for details type `show w'.
This is free software, and you are welcome to redistribute it
under certain conditions; type `show c' for details.
```

The hypothetical commands `show w' and `show c' should show the appropriate parts of the General Public License. Of course, the commands you use may be called something other than `show w' and `show c'; they could even be mouse-clicks or menu items--whatever suits your program.

You should also get your employer (if you work as a programmer) or your school, if any, to sign a "copyright disclaimer" for the program, if necessary. Here is a sample; alter the names:

```
Yoyodyne, Inc., hereby disclaims all copyright interest in the program
`Gnomovision' (which makes passes at compilers) written by James Hacker.
```

```
<signature of Ty Coon>, 1 April 1989
Ty Coon, President of Vice
```

This General Public License does not permit incorporating your program into proprietary programs. If your program is a subroutine library, you may consider it more useful to permit linking proprietary applications with the library. If this is what you want to do, use the GNU Lesser General Public License instead of this License.

Format: <https://www.debian.org/doc/packaging-manuals/copyright-format/1.0/>

Upstream-Name: systemd

Upstream-Contact: systemd-devel@lists.freedesktop.org

Source: <https://www.freedesktop.org/wiki/Software/systemd/>

Files: debian/*

Copyright: 2010-2013 Tollef Fog Heen <tfheen@debian.org>

2013-2015 Michael Biebl <biebl@debian.org>

2013 Michael Stapelberg <stapelberg@debian.org>

License: LGPL-2.1+

Files: *

Copyright: 2008-2015 Kay Sievers <kay@vrfy.org>
2010-2015 Lennart Poettering
2012-2015 Zbigniew Jdrzejewski-Szmek <zbyszek@in.waw.pl>
2013-2015 Tom Gundersen <teg@jklm.no>
2013-2015 Daniel Mack
2010-2015 Harald Hoyer
2013-2015 David Herrmann
2013, 2014 Thomas H.P. Andersen
2013, 2014 Daniel Buch
2014 Susant Sahani
2009-2015 Intel Corporation
2000, 2005 Red Hat, Inc.
2009 Alan Jenkins <alan-jenkins@tuffmail.co.uk>
2010 ProFUSION

embedded systems

2010 Maarten Lankhorst
1995-2004 Miquel van Smoorenburg
1999 Tom Tromey
2011 Michal Schmidt
2012 B. Poettering
2012 Holger Hans Peter Freyther
2012 Dan Walsh
2012 Roberto Sassu
2013 David Strauss
2013 Marius Vollmer
2013 Jan Janssen
2013 Simon Peeters

License: LGPL-2.1+

Files: src/basic/siphhash24.h

src/basic/siphhash24.c

Copyright: 2012 Jean-Philippe Aumasson <jeanphilippe.aumasson@gmail.com>

2012 Daniel J. Bernstein <djb@cr.yp.to>

License: CC0-1.0

Files: src/basic/securebits.h

Copyright: Linus Torvalds <torvalds@athlon.transmeta.com>

License: GPL-2

Files: src/basic/ioprio.h

Copyright: Jens Axboe <axboe@suse.de>

License: GPL-2

Files: src/shared/linux/auto_dev-ioctl.h

Copyright: 2008 Red Hat, Inc.

2008 Ian Kent <raven@themaw.net>

License: GPL-2+

Files: src/basic/sparse-endian.h

Copyright: 2012 Josh Triplett

<josh@joshtriplett.org>

License: Expat

Files: src/journal/lookup3.c

src/journal/lookup3.h

Copyright: none

License: public-domain

You can use this free for any purpose. It's in the public domain. It has no warranty.

Files: src/udev/*

Copyright: 2003-2012 Kay Sievers <kay@vrfy.org>

2003-2004 Greg Kroah-Hartman <greg@kroah.com>

2004 Chris Friesen <chris_friesen@sympatico.ca>

2004, 2009, 2010 David Zeuthen <david@fubar.dk>

2005, 2006 SUSE Linux Products GmbH

2003 IBM Corp.

2007 Hannes Reinecke <hare@suse.de>

2009 Canonical Ltd.

2009 Scott James Remnant <scott@netsplit.com>

2009 Martin Pitt <martin.pitt@ubuntu.com>

2009 Piter Punk <piterpunk@slackware.com>

2009, 2010 Lennart Poettering

2009 Filippo Argiolas <filippo.argiolas@gmail.com>

2010 Maxim Levitsky

2011 ProFUSION embedded systems

2011 Karel Zak <kzak@redhat.com>

2014 Zbigniew Jdrzejewski-Szmek <zbyszek@in.waw.pl>

2014 David Herrmann <dh.herrmann@gmail.com>

2014 Carlos Garnacho <carlosg@gnome.org>

License: GPL-2+

Files: src/udev/udev-ctrl.c

src/udev/udevadm-hwdb.c

src/udev/udev-builtin.c

src/udev/udev-builtin-net_id.c

src/udev/udev-builtin-net_setup_link.c

src/udev/udev-builtin-hwdb.c

src/udev/udev-builtin-btrfs.c

src/udev/udev-builtin-keyboard.c

src/udev/net/link-config.h

src/udev/net/link-config.c

src/udev/net/ethtool-util.c

src/udev/net/ethtool-util.h

Copyright: 2007-2013 Kay Sievers <kay@vrfy.org>

2013 Tom Gundersen <teg@jklm.no>

License: LGPL-2.1+

Files: src/udev/scsi_id/scsi.h
Copyright: 2003 IBM Corp.
License: GPL-2

License: Expat

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

.

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

License: GPL-2

This program is free software; you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation; version 2 of the License.

.

This program is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details.

.

You should have received a copy of the GNU General Public License along with this program; if not, write to the Free Software Foundation, Inc., 51 Franklin St, Fifth Floor, Boston, MA 02110-1301, USA.

.

On Debian and systems the full text of the GNU General Public License version 2 can be found in the file
`/usr/share/common-licenses/GPL-2`

License: GPL-2+

This program is free software; you can redistribute it and/or modify it under the terms of the GNU General Public License as published by

the Free Software Foundation; either version 2, or (at your option) any later version.

.
This program is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details.

.
You should have received a copy of the GNU General Public License along with this program; if not, write to the Free Software Foundation, Inc., 51 Franklin Street, Fifth Floor, Boston, MA 02110-1301, USA.

.
On Debian systems, the complete text of the GNU General Public License version 2 can be found in /usr/share/common-licenses/GPL-2.

License: LGPL-2.1+

This program is free software; you can redistribute it and/or modify it under the terms of the GNU Lesser General Public License as published by the Free Software Foundation; either version 2.1, or (at your option) any later version.

.
This program is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU Lesser General Public License for more details.

.
You should have received a copy of the GNU Lesser General Public License along with this program; if not, write to the Free Software Foundation, Inc., 51 Franklin Street, Fifth Floor, Boston, MA 02110-1301, USA.

.
On Debian systems, the complete text of the GNU Lesser General Public License version 2.1 can be found in /usr/share/common-licenses/LGPL-2.1.

License: CC0-1.0

To the extent possible under law, the author(s) have dedicated all copyright and related and neighboring rights to this software to the public domain worldwide. This software is distributed without any warranty.

.
You should have received a copy of the CC0 Public Domain Dedication along with this software. If not, see <<http://creativecommons.org/publicdomain/zero/1.0/>>.

.
On Debian systems, the complete text of the CC0 1.0 Universal license can be found in /usr/share/common-licenses/CC0-1.0.

1.91 libudev 237-3ubuntu10.56

1.91.1 Available under license :

GNU GENERAL PUBLIC LICENSE

Version 2, June 1991

Copyright (C) 1989, 1991 Free Software Foundation, Inc.,
51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA
Everyone is permitted to copy and distribute verbatim copies
of this license document, but changing it is not allowed.

Preamble

The licenses for most software are designed to take away your freedom to share and change it. By contrast, the GNU General Public License is intended to guarantee your freedom to share and change free software--to make sure the software is free for all its users. This General Public License applies to most of the Free Software Foundation's software and to any other program whose authors commit to using it. (Some other Free Software Foundation software is covered by the GNU Lesser General Public License instead.) You can apply it to your programs, too.

When we speak of free software, we are referring to freedom, not price. Our General Public Licenses are designed to make sure that you have the freedom to distribute copies of free software (and charge for this service if you wish), that you receive source code or can get it if you want it, that you can change the software or use pieces of it in new free programs; and that you know you can do these things.

To protect your rights, we need to make restrictions that forbid anyone to deny you these rights or to ask you to surrender the rights. These restrictions translate to certain responsibilities for you if you distribute copies of the software, or if you modify it.

For example, if you distribute copies of such a program, whether gratis or for a fee, you must give the recipients all the rights that you have. You must make sure that they, too, receive or can get the source code. And you must show them these terms so they know their rights.

We protect your rights with two steps: (1) copyright the software, and (2) offer you this license which gives you legal permission to copy, distribute and/or modify the software.

Also, for each author's protection and ours, we want to make certain that everyone understands that there is no warranty for this free software. If the software is modified by someone else and passed on, we want its recipients to know that what they have is not the original, so that any problems introduced by others will not reflect on the original authors' reputations.

Finally, any free program is threatened constantly by software patents. We wish to avoid the danger that redistributors of a free program will individually obtain patent licenses, in effect making the program proprietary. To prevent this, we have made it clear that any patent must be licensed for everyone's free use or not licensed at all.

The precise terms and conditions for copying, distribution and modification follow.

GNU GENERAL PUBLIC LICENSE TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

0. This License applies to any program or other work which contains a notice placed by the copyright holder saying it may be distributed under the terms of this General Public License. The "Program", below, refers to any such program or work, and a "work based on the Program" means either the Program or any derivative work under copyright law: that is to say, a work containing the Program or a portion of it, either verbatim or with modifications and/or translated into another language. (Hereinafter, translation is included without limitation in the term "modification".) Each licensee is addressed as "you".

Activities other than copying, distribution and modification are not covered by this License; they are outside its scope. The act of running the Program is not restricted, and the output from the Program is covered only if its contents constitute a work based on the Program (independent of having been made by running the Program). Whether that is true depends on what the Program does.

1. You may copy and distribute verbatim copies of the Program's source code as you receive it, in any medium, provided that you conspicuously and appropriately publish on each copy an appropriate copyright notice and disclaimer of warranty; keep intact all the notices that refer to this License and to the absence of any warranty; and give any other recipients of the Program a copy of this License along with the Program.

You may charge a fee for the physical act of transferring a copy, and you may at your option offer warranty protection in exchange for a fee.

2. You may modify your copy or copies of the Program or any portion of it, thus forming a work based on the Program, and copy and distribute such modifications or work under the terms of Section 1 above, provided that you also meet all of these conditions:

a) You must cause the modified files to carry prominent notices stating that you changed the files and the date of any change.

b) You must cause any work that you distribute or publish, that in whole or in part contains or is derived from the Program or any part thereof, to be licensed as a whole at no charge to all third parties under the terms of this License.

c) If the modified program normally reads commands interactively when run, you must cause it, when started running for such interactive use in the most ordinary way, to print or display an announcement including an appropriate copyright notice and a notice that there is no warranty (or else, saying that you provide a warranty) and that users may redistribute the program under these conditions, and telling the user how to view a copy of this License. (Exception: if the Program itself is interactive but does not normally print such an announcement, your work based on the Program is not required to print an announcement.)

These requirements apply to the modified work as a whole. If identifiable sections of that work are not derived from the Program, and can be reasonably considered independent and separate works in themselves, then this License, and its terms, do not apply to those sections when you distribute them as separate works. But when you distribute the same sections as part of a whole which is a work based on the Program, the distribution of the whole must be on the terms of this License, whose permissions for other licensees extend to the entire whole, and thus to each and every part regardless of who wrote it.

Thus, it is not the intent of this section to claim rights or contest your rights to work written entirely by you; rather, the intent is to exercise the right to control the distribution of derivative or collective works based on the Program.

In addition, mere aggregation of another work not based on the Program with the Program (or with a work based on the Program) on a volume of a storage or distribution medium does not bring the other work under the scope of this License.

3. You may copy and distribute the Program (or a work based

on it,
under Section 2) in object code or executable form under the terms of
Sections 1 and 2 above provided that you also do one of the following:

- a) Accompany it with the complete corresponding machine-readable source code, which must be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange; or,
- b) Accompany it with a written offer, valid for at least three years, to give any third party, for a charge no more than your cost of physically performing source distribution, a complete machine-readable copy of the corresponding source code, to be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange; or,
- c) Accompany it with the information you received as to the offer to distribute corresponding source code. (This alternative is allowed only for noncommercial distribution and only if you received the program in object code or executable form with such offer, in accord with Subsection b above.)

The source code for a work means the preferred form of the work for making modifications to it. For an executable work, complete source code means all the source code for all modules it contains, plus any associated interface definition files, plus the scripts used to control compilation and installation of the executable. However, as a special exception, the source code distributed need not include anything that is normally distributed (in either source or binary form) with the major components (compiler, kernel, and so on) of the operating system on which the executable runs, unless that component itself accompanies the executable.

If distribution of executable or object code is made by offering access to copy from a designated place, then offering equivalent access to copy the source code from the same place counts as distribution of the source code, even though third parties are not compelled to copy the source along with the object code.

4. You may not copy, modify, sublicense, or distribute the Program except as expressly provided under this License. Any attempt otherwise to copy, modify, sublicense or distribute the Program is void, and will automatically terminate your rights under this License. However, parties who have received copies, or rights, from you under this License will not have their licenses terminated so long as such parties remain in full compliance.

5. You are not required to accept this License, since you have not signed it. However, nothing else grants you permission to modify or distribute the Program or its derivative works. These actions are prohibited by law if you do not accept this License. Therefore, by modifying or distributing the Program (or any work based on the Program), you indicate your acceptance of this License to do so, and all its terms and conditions for copying, distributing or modifying the Program or works based on it.

6. Each time you redistribute the Program (or any work based on the Program), the recipient automatically receives a license from the original licensor to copy, distribute or modify the Program subject to these terms and conditions. You may not impose any further restrictions on the recipients' exercise of the rights granted herein. You are not responsible for enforcing compliance by third parties to this License.

7. If, as a consequence of a court judgment or allegation of patent infringement or for any other reason (not limited to patent issues), conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot distribute so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not distribute the Program at all. For example, if a patent license would not permit royalty-free redistribution of the Program by all those who receive copies directly or indirectly through you, then the only way you could satisfy both it and this License would be to refrain entirely from distribution of the Program.

If any portion of this section is held invalid or unenforceable under any particular circumstance, the balance of the section is intended to apply and the section as a whole is intended to apply in other circumstances.

It is not the purpose of this section to induce you to infringe any patents or other property right claims or to contest validity of any such claims; this section has the sole purpose of protecting the integrity of the free software distribution system, which is implemented by public license practices. Many people have made generous contributions to the wide range of software distributed through that system in reliance on consistent application of that system; it is up to the author/donor to decide if he or she is willing to distribute software through any other system and a licensee cannot impose that choice.

This section is intended to make thoroughly clear what is believed to be a consequence of the rest of this License.

8. If the distribution and/or use of the Program is restricted in certain countries either by patents or by copyrighted interfaces, the original copyright holder who places the Program under this License may add an explicit geographical distribution limitation excluding those countries, so that distribution is permitted only in or among countries not thus excluded. In such case, this License incorporates the limitation as if written in the body of this License.

9. The Free Software Foundation may publish revised and/or new versions of the General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Program specifies a version number of this License which applies to it and "any later version", you have the option of following the terms and conditions either of that version or of any later version published by the Free Software Foundation. If the Program does not specify a version number of this License, you may choose any version ever published by the Free Software Foundation.

10. If you wish to incorporate parts of the Program into other free programs whose distribution conditions are different, write to the author to ask for permission. For software which is copyrighted by the Free Software Foundation, write to the Free Software Foundation; we sometimes make exceptions for this. Our decision will be guided by the two goals of preserving the free status of all derivatives of our free software and of promoting the sharing and reuse of software generally.

NO WARRANTY

11. BECAUSE THE PROGRAM IS LICENSED FREE OF CHARGE, THERE IS NO WARRANTY FOR THE PROGRAM, TO THE EXTENT PERMITTED BY APPLICABLE LAW.

EXCEPT WHEN

OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE PROGRAM "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE PROGRAM IS WITH YOU. SHOULD THE PROGRAM PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

12. IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING

WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY AND/OR REDISTRIBUTE THE PROGRAM AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE PROGRAM (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE PROGRAM TO OPERATE WITH ANY OTHER PROGRAMS), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Programs

If you develop a new program, and you want it to be of the greatest possible use to the public, the best way to achieve this is to make it free software which everyone can redistribute and change under these terms.

To do so, attach the following notices to the program. It is safest to attach them to the start of each source file to most effectively convey the exclusion of warranty; and each file should have at least the "copyright" line and a pointer to where the full notice is found.

```
<one line to give the program's name and a brief idea of what it does.>  
Copyright (C) <year> <name of author>
```

This program is free software; you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation; either version 2 of the License, or (at your option) any later version.

This program is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details.

You should have received a copy of the GNU General Public License along with this program; if not, write to the Free Software Foundation, Inc., 51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA.

Also add information on how to contact you by electronic and paper mail.

If the program is interactive, make it output a short notice like this when it starts in an interactive mode:

```
Gnomovision version 69, Copyright (C) year name of author  
Gnomovision comes with ABSOLUTELY NO WARRANTY; for details type `show w'.
```

This is free software, and you are welcome to redistribute it under certain conditions; type `show c' for details.

The hypothetical commands `show w' and `show c' should show the appropriate parts of the General Public License. Of course, the commands you use may be called something other than `show w' and `show c'; they could even be mouse-clicks or menu items--whatever suits your program.

You should also get your employer (if you work as a programmer) or your school, if any, to sign a "copyright disclaimer" for the program, if necessary. Here is a sample; alter the names:

Yoyodyne, Inc., hereby disclaims all copyright interest in the program `Gnomovision' (which makes passes at compilers) written by James Hacker.

<signature of Ty Coon>, 1 April 1989
Ty Coon, President of Vice

This General Public License does not permit incorporating your program into proprietary programs. If your program is a subroutine library, you may consider it more useful to permit linking proprietary applications with the library. If this is what you want to do, use the GNU Lesser General Public License instead of this License.

Format: <https://www.debian.org/doc/packaging-manuals/copyright-format/1.0/>
Upstream-Name: systemd
Upstream-Contact: systemd-devel@lists.freedesktop.org
Source: <https://www.freedesktop.org/wiki/Software/systemd/>

Files: debian/*
Copyright: 2010-2013 Tollef Fog Heen <tfheen@debian.org>
2013-2015 Michael Biebl <biebl@debian.org>
2013 Michael Stapelberg <stapelberg@debian.org>
License: LGPL-2.1+

Files: *
Copyright: 2008-2015 Kay Sievers <kay@vrfy.org>
2010-2015 Lennart Poettering
2012-2015 Zbigniew Jdrzejewski-Szmek <zbyszek@in.waw.pl>
2013-2015 Tom Gundersen <teg@jklm.no>
2013-2015 Daniel Mack
2010-2015 Harald Hoyer
2013-2015 David Herrmann
2013, 2014 Thomas H.P. Andersen
2013, 2014 Daniel Buch
2014 Susant Sahani
2009-2015 Intel Corporation
2000, 2005 Red Hat, Inc.

2009 Alan Jenkins <alan-jenkins@tuffmail.co.uk>
2010 ProFUSION
embedded systems
2010 Maarten Lankhorst
1995-2004 Miquel van Smoorenburg
1999 Tom Tromeu
2011 Michal Schmidt
2012 B. Poettering
2012 Holger Hans Peter Freyther
2012 Dan Walsh
2012 Roberto Sassu
2013 David Strauss
2013 Marius Vollmer
2013 Jan Janssen
2013 Simon Peeters

License: LGPL-2.1+

Files: src/basic/siphhash24.h
src/basic/siphhash24.c

Copyright: 2012 Jean-Philippe Aumasson <jeanphilippe.aumasson@gmail.com>
2012 Daniel J. Bernstein <djb@cr.yp.to>

License: CC0-1.0

Files: src/basic/securebits.h

Copyright: Linus Torvalds <torvalds@athlon.transmeta.com>

License: GPL-2

Files: src/basic/ioprio.h

Copyright: Jens Axboe <axboe@suse.de>

License: GPL-2

Files: src/shared/linux/auto_dev-ioctl.h

Copyright: 2008 Red Hat, Inc.

2008 Ian Kent <raven@themaw.net>

License: GPL-2+

Files: src/basic/sparse-endian.h

Copyright: 2012 Josh Triplett

<josh@joshtriplett.org>

License: Expat

Files: src/journal/lookup3.c

src/journal/lookup3.h

Copyright: none

License: public-domain

You can use this free for any purpose. It's in the public domain. It has no warranty.

Files: src/udev/*

Copyright: 2003-2012 Kay Sievers <kay@vrfy.org>

2003-2004 Greg Kroah-Hartman <greg@kroah.com>

2004 Chris Friesen <chris_friesen@sympatico.ca>

2004, 2009, 2010 David Zeuthen <david@fubar.dk>

2005, 2006 SUSE Linux Products GmbH

2003 IBM Corp.

2007 Hannes Reinecke <hare@suse.de>

2009 Canonical Ltd.

2009 Scott James Remnant <scott@netsplit.com>

2009 Martin Pitt <martin.pitt@ubuntu.com>

2009 Piter Punk <piterpunk@slackware.com>

2009, 2010 Lennart Poettering

2009 Filippo Argiolas <filippo.argiolas@gmail.com>

2010 Maxim Levitsky

2011 ProFUSION embedded systems

2011 Karel Zak <kzak@redhat.com>

2014 Zbigniew Jdrzejewski-Szmek <zbyszek@in.waw.pl>

2014 David Herrmann <dh.herrmann@gmail.com>

2014 Carlos Garnacho <carlosg@gnome.org>

License: GPL-2+

Files: src/udev/udev-ctrl.c

src/udev/udevadm-hwdb.c

src/udev/udev-builtin.c

src/udev/udev-builtin-net_id.c

src/udev/udev-builtin-net_setup_link.c

src/udev/udev-builtin-hwdb.c

src/udev/udev-builtin-btrfs.c

src/udev/udev-builtin-keyboard.c

src/udev/net/link-config.h

src/udev/net/link-config.c

src/udev/net/ethtool-util.c

src/udev/net/ethtool-util.h

Copyright: 2007-2013 Kay Sievers <kay@vrfy.org>

2013 Tom Gundersen <teg@jklm.no>

License: LGPL-2.1+

Files: src/udev/scsi_id/scsi.h

Copyright: 2003 IBM Corp.

License: GPL-2

License: Expat

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction,

including without limitation the

rights to use, copy, modify, merge, publish, distribute, sublicense, and/or

sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

.

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

License: GPL-2

This program is free software; you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation; version 2 of the License.

.

This program is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details.

.

You should have received a copy of the GNU General Public License along with this program; if not, write to the Free Software Foundation, Inc., 51 Franklin St, Fifth Floor, Boston, MA 02110-1301, USA.

.

On Debian and systems the full text of the GNU General Public License version 2 can be found in the file
`/usr/share/common-licenses/GPL-2`

License: GPL-2+

This program is free software; you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation; either version 2, or (at your option) any later version.

.

This program is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details.

.

You should have received a copy of the GNU General Public License along with this program; if not, write to the Free Software Foundation, Inc., 51 Franklin Street, Fifth Floor, Boston, MA 02110-1301, USA.

.
On Debian systems, the complete text of the GNU General Public License version 2 can be found in `/usr/share/common-licenses/GPL-2`.

License: LGPL-2.1+

This program is free software; you can redistribute it and/or modify it under the terms of the GNU Lesser General Public License as published by the Free Software Foundation; either version 2.1, or (at your option) any later version.

.
This program is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU Lesser General Public License for more details.

.
You should have received a copy of the GNU Lesser General Public License along with this program; if not, write to the Free Software Foundation, Inc., 51 Franklin Street, Fifth Floor, Boston, MA 02110-1301, USA.

.
On Debian systems, the complete text of the GNU Lesser General Public License version 2.1 can be found in `/usr/share/common-licenses/LGPL-2.1`.

License: CC0-1.0

To the extent possible under law, the author(s) have dedicated all copyright and related and neighboring rights to this software to the public domain worldwide. This software is distributed without any warranty.

.
You should have received a copy of the CC0 Public Domain Dedication along with this software. If not, see <http://creativecommons.org/publicdomain/zero/1.0/>.

.
On Debian systems, the complete text of the CC0 1.0 Universal license can be found in `/usr/share/common-licenses/CC0-1.0`.

1.92 gmp 6.1.2+dfsg-2ubuntu0.1

1.92.1 Available under license :

GNU GENERAL PUBLIC LICENSE

Version 2, June 1991

Copyright (C) 1989, 1991 Free Software Foundation, Inc.,
51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA
Everyone is permitted to copy and distribute verbatim copies
of this license document, but changing it is not allowed.

Preamble

The licenses for most software are designed to take away your

freedom to share and change it. By contrast, the GNU General Public License is intended to guarantee your freedom to share and change free software--to make sure the software is free for all its users. This General Public License applies to most of the Free Software Foundation's software and to any other program whose authors commit to using it. (Some other Free Software Foundation software is covered by the GNU Lesser General Public License instead.) You can apply it to your programs, too.

When we speak of free software, we are referring to freedom, not price.

Our General Public Licenses are designed to make sure that you have the freedom to distribute copies of free software (and charge for this service if you wish), that you receive source code or can get it if you want it, that you can change the software or use pieces of it in new free programs; and that you know you can do these things.

To protect your rights, we need to make restrictions that forbid anyone to deny you these rights or to ask you to surrender the rights. These restrictions translate to certain responsibilities for you if you distribute copies of the software, or if you modify it.

For example, if you distribute copies of such a program, whether gratis or for a fee, you must give the recipients all the rights that you have. You must make sure that they, too, receive or can get the source code. And you must show them these terms so they know their rights.

We protect your rights with two steps: (1) copyright the software, and (2) offer you this license which gives you legal permission to copy, distribute and/or modify the software.

Also, for each author's protection and ours, we want to make certain that everyone understands that there is no warranty for this free software. If the software is modified by someone else and passed on, we want its recipients to know that what they have is not the original, so that any problems introduced by others will not reflect on the original authors' reputations.

Finally, any free program is threatened constantly by software patents. We wish to avoid the danger that redistributors of a free program will individually obtain patent licenses, in effect making the program proprietary. To prevent this, we have made it clear that any patent must be licensed for everyone's free use or not licensed at all.

The precise terms and conditions for copying, distribution and modification follow.

GNU GENERAL PUBLIC LICENSE
TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

0. This License applies to any program or other work which contains a notice placed by the copyright holder saying it may be distributed under the terms of this General Public License. The "Program", below, refers to any such program or work, and a "work based on the Program" means either the Program or any derivative work under copyright law: that is to say, a work containing the Program or a portion of it, either verbatim or with modifications and/or translated into another language. (Hereinafter, translation is included without limitation in the term "modification".) Each licensee is addressed as "you".

Activities other than copying, distribution and modification are not covered by this License; they are outside its scope. The act of running the Program is not restricted, and the output from the Program is covered only if its contents constitute a work based on the Program (independent of having been made by running the Program). Whether that is true depends on what the Program does.

1. You may copy and distribute verbatim copies of the Program's source code as you receive it, in any medium, provided that you conspicuously and appropriately publish on each copy an appropriate copyright notice and disclaimer of warranty; keep intact all the notices that refer to this License and to the absence of any warranty; and give any other recipients of the Program a copy of this License along with the Program.

You may charge a fee for the physical act of transferring a copy, and you may at your option offer warranty protection in exchange for a fee.

2. You may modify your copy or copies of the Program or any portion of it, thus forming a work based on the Program, and copy and distribute such modifications or work under the terms of Section 1 above, provided that you also meet all of these conditions:

a) You must cause the modified files to carry prominent notices stating that you changed the files and the date of any change.

b) You must cause any work that you distribute or publish, that in whole or in part contains or is derived from the Program or any part thereof, to be licensed as a whole at no charge to all third parties under the terms of this License.

c) If the modified program normally reads commands interactively

when run, you must cause it, when started running for such interactive use in the most ordinary way, to print or display an announcement including an appropriate copyright notice and a notice that there is no warranty (or else, saying that you provide a warranty) and that users may redistribute the program under these conditions, and telling the user how to view a copy of this License. (Exception: if the Program itself is interactive but does not normally print such an announcement, your work based on the Program is not required to print an announcement.)

These requirements apply to the modified work as a whole. If identifiable sections of that work are not derived from the Program, and can be reasonably considered independent and separate works in themselves, then this License, and its terms, do not apply to those sections when you distribute them as separate works. But when you distribute the same sections as part of a whole which is a work based on the Program, the distribution of the whole must be on the terms of this License, whose permissions for other licensees extend to the entire whole, and thus to each and every part regardless of who wrote it.

Thus, it is not the intent of this section to claim rights or contest your rights to work written entirely by you; rather, the intent is to exercise the right to control the distribution of derivative or collective works based on the Program.

In addition, mere aggregation of another work not based on the Program with the Program (or with a work based on the Program) on a volume of a storage or distribution medium does not bring the other work under the scope of this License.

3. You may copy and distribute the Program (or a work based on it, under Section 2) in object code or executable form under the terms of Sections 1 and 2 above provided that you also do one of the following:

a) Accompany it with the complete corresponding machine-readable source code, which must be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange; or,

b) Accompany it with a written offer, valid for at least three years, to give any third party, for a charge no more than your cost of physically performing source distribution, a complete machine-readable copy of the corresponding source code, to be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange; or,

c) Accompany it with the information you received as to the offer to distribute corresponding source code. (This alternative is

allowed only for noncommercial distribution
and only if you
received the program in object code or executable form with such
an offer, in accord with Subsection b above.)

The source code for a work means the preferred form of the work for making modifications to it. For an executable work, complete source code means all the source code for all modules it contains, plus any associated interface definition files, plus the scripts used to control compilation and installation of the executable. However, as a special exception, the source code distributed need not include anything that is normally distributed (in either source or binary form) with the major components (compiler, kernel, and so on) of the operating system on which the executable runs, unless that component itself accompanies the executable.

If distribution of executable or object code is made by offering access to copy from a designated place, then offering equivalent access to copy the source code from the same place counts as distribution of the source code, even though third parties are not compelled to copy the source along with the object code.

4. You may not copy, modify, sublicense, or distribute the Program except as expressly provided under this License. Any attempt otherwise to copy, modify, sublicense or distribute the Program is void, and will automatically terminate your rights under this License. However, parties who have received copies, or rights, from you under this License will not have their licenses terminated so long as such parties remain in full compliance.

5. You are not required to accept this License, since you have not signed it. However, nothing else grants you permission to modify or distribute the Program or its derivative works. These actions are prohibited by law if you do not accept this License. Therefore, by modifying or distributing the Program (or any work based on the Program), you indicate your acceptance of this License to do so, and all its terms and conditions for copying, distributing or modifying the Program or works based on it.

6. Each time you redistribute the Program (or any work based on the Program), the recipient automatically receives a license from the original licensor to copy, distribute or modify the Program subject to these terms and conditions. You may not impose any further restrictions on the recipients' exercise of the rights granted herein. You are not responsible for enforcing compliance by third parties to this License.

7. If, as a consequence of a court judgment or allegation of patent infringement or for any other reason (not limited to patent issues), conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot distribute so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not distribute the Program at all. For example, if a patent license would not permit royalty-free redistribution of the Program by all those who receive copies directly or indirectly through you, then the only way you could satisfy both it and this License would be to refrain entirely from distribution of the Program.

If any portion of this section is held invalid or unenforceable under any particular circumstance, the balance of the section is intended to apply and the section as a whole is intended to apply in other circumstances.

It is not the purpose of this section to induce you to infringe any patents or other property right claims or to contest validity of any such claims; this section has the sole purpose of protecting the integrity of the free software distribution system, which is implemented by public license practices. Many people have made generous contributions to the wide range of software distributed through that system in reliance on consistent application of that system; it is up to the author/donor to decide if he or she is willing to distribute software through any other system and a licensee cannot impose that choice.

This section is intended to make thoroughly clear what is believed to be a consequence of the rest of this License.

8. If the distribution and/or use of the Program is restricted in certain countries either by patents or by copyrighted interfaces, the original copyright holder who places the Program under this License may add an explicit geographical distribution limitation excluding those countries, so that distribution is permitted only in or among countries not thus excluded. In such case, this License incorporates the limitation as if written in the body of this License.

9. The Free Software Foundation may publish revised and/or new versions of the General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Program specifies a version number of this License which applies to it and "any later version", you have the option of following the terms and conditions either of that version or of any later version published by the Free Software Foundation. If the Program does not specify a version number of this License, you may choose any version ever published by the Free Software Foundation.

10. If you wish to incorporate parts of the Program into other free programs whose distribution conditions are different, write to the author to ask for permission. For software which is copyrighted by the Free Software Foundation, write to the Free Software Foundation; we sometimes make exceptions for this. Our decision will be guided by the two goals of preserving the free status of all derivatives of our free software and of promoting the sharing and reuse of software generally.

NO WARRANTY

11. BECAUSE THE PROGRAM IS LICENSED FREE OF CHARGE, THERE IS NO WARRANTY FOR THE PROGRAM, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE PROGRAM "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE PROGRAM IS WITH YOU. SHOULD THE PROGRAM PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

12. IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY AND/OR REDISTRIBUTE THE PROGRAM AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE PROGRAM (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE PROGRAM TO OPERATE WITH ANY OTHER PROGRAMS), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Programs

If you develop a new program, and you want it to be of the greatest possible use to the public, the best way to achieve this is to make it free software which everyone can redistribute and change under these terms.

To do so, attach the following notices to the program. It is safest to attach them to the start of each source file to most effectively convey the exclusion of warranty; and each file should have at least the "copyright" line and a pointer to where the full notice is found.

<one line to give the program's name and a brief idea of what it does.>
Copyright (C) <year> <name of author>

This program is free software; you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation; either version 2 of the License, or (at your option) any later version.

This program is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details.

You should have received a copy of the GNU General Public License along with this program; if not, write to the Free Software Foundation, Inc., 51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA.

Also add information on how to contact you by electronic and paper mail.

If the program is interactive, make it output a short notice like this when it starts in an interactive mode:

```
Gnomovision version 69, Copyright (C) year name of author
Gnomovision comes with ABSOLUTELY NO WARRANTY; for details type `show w'.
This is free software, and you are welcome to redistribute
it
under certain conditions; type `show c' for details.
```

The hypothetical commands `show w' and `show c' should show the appropriate parts of the General Public License. Of course, the commands you use may be called something other than `show w' and `show c'; they could even be mouse-clicks or menu items--whatever suits your program.

You should also get your employer (if you work as a programmer) or your school, if any, to sign a "copyright disclaimer" for the program, if necessary. Here is a sample; alter the names:

```
Yoyodyne, Inc., hereby disclaims all copyright interest in the program
`Gnomovision' (which makes passes at compilers) written by James Hacker.
```

<signature of Ty Coon>, 1 April 1989

Ty Coon, President of Vice

This General Public License does not permit incorporating your program into proprietary programs. If your program is a subroutine library, you may consider it more useful to permit linking proprietary applications with the library. If this

is what you want to do, use the GNU Lesser General Public License instead of this License.

GNU GENERAL PUBLIC LICENSE

Version 3, 29 June 2007

Copyright (C) 2007 Free Software Foundation, Inc. <<http://fsf.org/>>

Everyone is permitted to copy and distribute verbatim copies of this license document, but changing it is not allowed.

Preamble

The GNU General Public License is a free, copyleft license for software and other kinds of works.

The licenses for most software and other practical works are designed to take away your freedom to share and change the works. By contrast, the GNU General Public License is intended to guarantee your freedom to share and change all versions of a program--to make sure it remains free software for all its users. We, the Free Software Foundation, use the GNU General Public License for most of our software; it applies also to any other work released this way by its authors. You can apply it to your programs, too.

When we speak of free software, we are referring to freedom, not price. Our General Public Licenses are designed to make sure that you have the freedom to distribute copies of free software (and charge for them if you wish), that you receive source code or can get it if you want it, that you can change the software or use pieces of it in new free programs, and that you know you can do these things.

To protect your rights, we need to prevent others from denying you these rights or asking you to surrender the rights. Therefore, you have certain responsibilities if you distribute copies of the software, or if you modify it: responsibilities to respect the freedom of others.

For example, if you distribute copies of such a program, whether gratis or for a fee, you must pass on to the recipients the same freedoms that you received. You must make sure that they, too, receive or can get the source code. And you must show them these terms so they know their rights.

Developers that use the GNU GPL protect your rights with two steps:

(1)

assert copyright on the software, and (2) offer you this License giving you legal permission to copy, distribute and/or modify it.

For the developers' and authors' protection, the GPL clearly explains that there is no warranty for this free software. For both users' and authors' sake, the GPL requires that modified versions be marked as changed, so that their problems will not be attributed erroneously to authors of previous versions.

Some devices are designed to deny users access to install or run modified versions of the software inside them, although the manufacturer can do so. This is fundamentally incompatible with the aim of protecting users' freedom to change the software. The systematic pattern of such abuse occurs in the area of products for individuals to use, which is precisely where it is most unacceptable. Therefore, we have designed this version of the GPL to prohibit the practice for those products. If such problems arise substantially in other domains, we stand

ready to extend this provision to those domains in future versions of the GPL, as needed to protect the freedom of users.

Finally, every program is threatened constantly by software patents. States should not allow patents to restrict development and use of software on general-purpose computers, but in those that do, we wish to avoid the special danger that patents applied to a free program could make it effectively proprietary. To prevent this, the GPL assures that patents cannot be used to render the program non-free.

The precise terms and conditions for copying, distribution and modification follow.

TERMS AND CONDITIONS

0. Definitions.

"This License" refers to version 3 of the GNU General Public License.

"Copyright" also means copyright-like laws that apply to other kinds of works, such as semiconductor masks.

"The Program" refers to any copyrightable work licensed under this License. Each licensee is addressed as "you". "Licensees" and

"recipients" may be individuals or organizations.

To "modify" a work means to copy from or adapt all or part of the work

in a fashion requiring copyright permission, other than the making of an exact copy. The resulting work is called a "modified version" of the earlier work or a work "based on" the earlier work.

A "covered work" means either the unmodified Program or a work based on the Program.

To "propagate" a work means to do anything with it that, without permission, would make you directly or secondarily liable for infringement under applicable copyright law, except executing it on a computer or modifying a private copy. Propagation includes copying, distribution (with or without modification), making available to the public, and in some countries other activities as well.

To "convey" a work means any kind of propagation that enables other parties to make or receive copies. Mere interaction with a user through a computer network, with no transfer of a copy, is not conveying.

An interactive user interface displays "Appropriate Legal Notices" to the extent that it includes a convenient and prominently visible feature that (1) displays an appropriate copyright notice, and (2) tells the user that there is no warranty for the work (except to the extent that warranties are provided), that licensees may convey the work under this License, and how to view a copy of this License. If the interface presents a list of user commands or options, such as a menu, a prominent item in the list meets this criterion.

1. Source Code.

The "source code" for a work means the preferred form of the work for making modifications to it. "Object code" means any non-source form of a work.

A "Standard Interface" means an interface that either is an official standard defined by a recognized standards body, or, in the case of interfaces specified for a particular programming language, one that is widely used among developers working in that language.

The

"System Libraries" of an executable work include anything, other than the work as a whole, that (a) is included in the normal form of packaging a Major Component, but which is not part of that Major Component, and (b) serves only to enable use of the work with that Major Component, or to implement a Standard Interface for which an implementation is available to the public in source code form. A "Major Component", in this context, means a major essential component (kernel, window system, and so on) of the specific operating system

(if any) on which the executable work runs, or a compiler used to produce the work, or an object code interpreter used to run it.

The "Corresponding Source" for a work in object code form means all the source code needed to generate, install, and (for an executable work) run the object code and to modify the work, including scripts to control those activities. However, it does not include the work's System Libraries, or general-purpose tools or generally available free programs which are used unmodified in performing those activities but which are not part of the work. For example, Corresponding Source includes interface definition files associated with source files for the work, and the source code for shared libraries and dynamically linked subprograms that the work is specifically designed to require, such as by intimate data communication or control flow between those subprograms and other parts of the work.

The Corresponding Source need not include anything that users can regenerate automatically from other parts of the Corresponding Source.

The Corresponding Source for a work in source code form is that same work.

2. Basic Permissions.

All rights granted under this License are granted for the term of copyright on the Program, and are irrevocable provided the stated conditions are met. This License explicitly affirms your unlimited permission to run the unmodified Program. The output from running a covered work is covered by this License only if the output, given its content, constitutes a covered work. This License acknowledges your rights of fair use or other equivalent, as provided by copyright law.

You may make, run and propagate covered works that you do not convey, without conditions so long as your license otherwise remains in force. You may convey covered works to others for the sole purpose of having them make modifications exclusively for you, or provide you with facilities for running those works, provided that you comply with the terms of this License in conveying all material for which you do not control copyright. Those thus making or running the covered works for you must do so exclusively on your behalf, under your direction and control, on terms that prohibit them from making any copies of your copyrighted material outside their relationship with you.

Conveying under any other circumstances is permitted solely under the conditions stated below. Sublicensing is not allowed;

section 10
makes it unnecessary.

3. Protecting Users' Legal Rights From Anti-Circumvention Law.

No covered work shall be deemed part of an effective technological measure under any applicable law fulfilling obligations under article 11 of the WIPO copyright treaty adopted on 20 December 1996, or similar laws prohibiting or restricting circumvention of such measures.

When you convey a covered work, you waive any legal power to forbid circumvention of technological measures to the extent such circumvention is effected by exercising rights under this License with respect to the covered work, and you disclaim any intention to limit operation or modification of the work as a means of enforcing, against the work's users, your or third parties' legal rights to forbid circumvention of technological measures.

4. Conveying Verbatim Copies.

You may convey verbatim copies of the Program's source code as you receive it, in any medium, provided that you conspicuously and appropriately publish on each copy an appropriate copyright notice; keep intact all notices stating that this License and any non-permissive terms added in accord with section 7 apply to the code; keep intact all notices of the absence of any warranty; and give all recipients a copy of this License along with the Program.

You may charge any price or no price for each copy that you convey, and you may offer support or warranty protection for a fee.

5. Conveying Modified Source Versions.

You may convey a work based on the Program, or the modifications to produce it from the Program, in the form of source code under the terms of section 4, provided that you also meet all of these conditions:

- a) The work must carry prominent notices stating that you modified it, and giving a relevant date.
- b) The work must carry prominent notices stating that it is released under this License and any conditions added under section 7. This requirement modifies the requirement in section 4 to "keep intact all notices".

c) You must license the entire work, as a whole, under this License to anyone who comes into possession of a copy. This License will therefore apply, along with any applicable section 7 additional terms, to the whole of the work, and all its parts, regardless of how they are packaged. This License gives no permission to license the work in any other way, but it does not invalidate such permission if you have separately received it.

d) If the work has interactive user interfaces, each must display Appropriate Legal Notices; however, if the Program has interactive interfaces that do not display Appropriate Legal Notices, your work need not make them do so.

A compilation of a covered work with other separate and independent works, which are not by their nature extensions of the covered work, and which are not combined with it such as to form a larger program, in or on a volume of a storage or distribution medium, is called an "aggregate" if the compilation and its resulting copyright are not used to limit the access or legal rights of the compilation's users beyond what the individual works permit. Inclusion of a covered work in an aggregate does not cause this License to apply to the other parts of the aggregate.

6. Conveying Non-Source Forms.

You may convey a covered work in object code form under the terms of sections 4 and 5, provided that you also convey the machine-readable Corresponding Source under the terms of this License, in one of these ways:

a) Convey the object code in, or embodied in, a physical product (including a physical distribution medium), accompanied by the Corresponding Source fixed on a durable physical medium customarily used for software interchange.

b) Convey the object code in, or embodied in, a physical product (including a physical distribution medium), accompanied by a written offer, valid for at least three years and valid for as long as you offer spare parts or customer support for that product model, to give anyone who possesses the object code either (1) a copy of the Corresponding Source for all the software in the product that is covered by this License, on a durable physical medium customarily used for software interchange, for a price no more than your reasonable cost of physically performing this conveying of source, or (2) access to copy the Corresponding Source from a network server at no charge.

c) Convey individual copies of the object code with a copy of the written offer to provide the Corresponding Source. This alternative is allowed only occasionally and noncommercially, and only if you received the object code with such an offer, in accord with subsection 6b.

d) Convey the object code by offering access from a designated place (gratis or for a charge), and offer equivalent access to the Corresponding Source in the same way through the same place at no further charge. You need not require recipients to copy the Corresponding Source along with the object code. If the place to copy the object code is a network server, the Corresponding Source may be on a different server (operated by you or a third party) that supports equivalent copying facilities, provided you maintain clear directions next to the object code saying where to find the Corresponding Source. Regardless of what server hosts the Corresponding Source, you remain obligated to ensure that it is available for as long as needed to satisfy these requirements.

e) Convey the object code using peer-to-peer transmission, provided you inform other peers where the object code and Corresponding Source of the work are being offered to the general public at no charge under subsection 6d.

A separable portion of the object code, whose source code is excluded from the Corresponding Source as a System Library, need not be included in conveying the object code work.

A "User Product" is either (1) a "consumer product", which means any tangible personal property which is normally used for personal, family, or household purposes, or (2) anything designed or sold for incorporation into a dwelling. In determining whether a product is a consumer product, doubtful cases shall be resolved in favor of coverage. For a particular product received by a particular user, "normally used" refers to a typical or common use of that class of product, regardless of the status of the particular user or of the way in which the particular user actually uses, or expects or is expected to use, the product. A product is a consumer product regardless of whether the product has substantial commercial, industrial or non-consumer uses, unless such uses represent the only significant mode of use of the product.

"Installation Information" for a User Product means any methods, procedures, authorization keys, or other information required to install and execute modified versions of a covered work in that User Product from

a modified version of its Corresponding Source. The information must suffice to ensure that the continued functioning of the modified object code is in no case prevented or interfered with solely because modification has been made.

If you convey an object code work under this section in, or with, or specifically for use in, a User Product, and the conveying occurs as part of a transaction in which the right of possession and use of the User Product is transferred to the recipient in perpetuity or for a fixed term (regardless of how the transaction is characterized), the Corresponding Source conveyed under this section must be accompanied by the Installation Information. But this requirement does not apply if neither you nor any third party retains the ability to install modified object code on the User Product (for example, the work has been installed in ROM).

The requirement to provide Installation Information does not include a requirement to continue to provide support service, warranty, or updates for a work that has been modified or installed by the recipient, or for the User Product in which it has been modified or installed. Access to a network may be denied when the modification itself materially and adversely affects the operation of the network or violates the rules and protocols for communication across the network.

Corresponding Source conveyed, and Installation Information provided, in accord with this section must be in a format that is publicly documented (and with an implementation available to the public in source code form), and must require no special password or key for unpacking, reading or copying.

7. Additional Terms.

"Additional permissions" are terms that supplement the terms of this License by making exceptions from one or more of its conditions. Additional permissions that are applicable to the entire Program shall be treated as though they were included in this License, to the extent that they are valid under applicable law. If additional permissions apply only to part of the Program, that part may be used separately under those permissions, but the entire Program remains governed by this License without regard to the additional permissions.

When you convey a copy of a covered work, you may at your option remove any additional permissions from that copy, or from any part of it. (Additional permissions may be written to require their own removal in certain cases when you modify the work.) You may place additional permissions on material, added by you to a covered work,

for which you have or can give appropriate copyright permission.

Notwithstanding any other provision of this License, for material you add to a covered work, you may (if authorized by the copyright holders of that material) supplement the terms of this License with terms:

- a) Disclaiming warranty or limiting liability differently from the terms of sections 15 and 16 of this License; or
- b) Requiring preservation of specified reasonable legal notices or author attributions in that material or in the Appropriate Legal Notices displayed by works containing it; or
- c) Prohibiting misrepresentation of the origin of that material, or requiring that modified versions of such material be marked in reasonable ways as different from the original version; or
- d) Limiting the use for publicity purposes of names of licensors or authors of the material; or
- e) Declining to grant rights under trademark law for use of some trade names, trademarks, or service marks; or
- f) Requiring indemnification of licensors and authors of that material by anyone who conveys the material (or modified versions of it) with contractual assumptions of liability to the recipient, for any liability that these contractual assumptions directly impose on those licensors and authors.

All other non-permissive additional terms are considered "further restrictions" within the meaning of section 10. If the Program as you received it, or any part of it, contains a notice stating that it is governed by this License along with a term that is a further restriction, you may remove that term. If a license document contains a further restriction but permits relicensing or conveying under this License, you may add to a covered work material governed by the terms of that license document, provided that the further restriction does not survive such relicensing or conveying.

If you add terms to a covered work in accord with this section, you must place, in the relevant source files, a statement of the additional terms that apply to those files, or a notice indicating where to find the applicable terms.

Additional terms, permissive or non-permissive, may be stated in the form of a separately written license, or stated as exceptions;

the above
requirements apply either way.

8. Termination.

You may not propagate or modify a covered work except as expressly provided under this License. Any attempt otherwise to propagate or modify it is void, and will automatically terminate your rights under this License (including any patent licenses granted under the third paragraph of section 11).

However, if you cease all violation of this License, then your license from a particular copyright holder is reinstated (a) provisionally, unless and until the copyright holder explicitly and finally terminates your license, and (b) permanently, if the copyright holder fails to notify you of the violation by some reasonable means prior to 60 days after the cessation.

Moreover, your license from a particular copyright holder is reinstated permanently if the copyright holder notifies you of the violation by some reasonable means, this is the first time you have received notice of violation of this License (for any work) from that copyright holder, and you cure the violation prior to 30 days after your receipt of the notice.

Termination of your rights under this section does not terminate the licenses of parties who have received copies or rights from you under this License. If your rights have been terminated and not permanently reinstated, you do not qualify to receive new licenses for the same material under section 10.

9. Acceptance Not Required for Having Copies.

You are not required to accept this License in order to receive or run a copy of the Program. Ancillary propagation of a covered work occurring solely as a consequence of using peer-to-peer transmission to receive a copy likewise does not require acceptance. However, nothing other than this License grants you permission to propagate or modify any covered work. These actions infringe copyright if you do not accept this License. Therefore, by modifying or propagating a covered work, you indicate your acceptance of this License to do so.

10. Automatic Licensing of Downstream Recipients.

Each time you convey a covered work, the recipient automatically receives a license from the original licensors, to run, modify and

propagate that work, subject to this License. You are not responsible for enforcing compliance by third parties with this License.

An "entity transaction" is a transaction transferring control of an organization, or substantially all assets of one, or subdividing an organization, or merging organizations. If propagation of a covered work results from an entity transaction, each party to that transaction who receives a copy of the work also receives whatever licenses to the work the party's predecessor in interest had or could give under the previous paragraph, plus a right to possession of the Corresponding Source of the work from the predecessor in interest, if the predecessor has it or can get it with reasonable efforts.

You may not impose any further restrictions on the exercise of the rights

granted or affirmed under this License. For example, you may not impose a license fee, royalty, or other charge for exercise of rights granted under this License, and you may not initiate litigation (including a cross-claim or counterclaim in a lawsuit) alleging that any patent claim is infringed by making, using, selling, offering for sale, or importing the Program or any portion of it.

11. Patents.

A "contributor" is a copyright holder who authorizes use under this License of the Program or a work on which the Program is based. The work thus licensed is called the contributor's "contributor version".

A contributor's "essential patent claims" are all patent claims owned or controlled by the contributor, whether already acquired or hereafter acquired, that would be infringed by some manner, permitted by this License, of making, using, or selling its contributor version, but do not include claims that would be infringed only as a consequence of further modification of the contributor version. For purposes of this definition, "control" includes the right to grant patent sublicenses in a manner consistent with the requirements of this License.

Each contributor grants you a non-exclusive, worldwide, royalty-free patent license under the contributor's essential patent claims, to make, use, sell, offer for sale, import and otherwise run, modify and propagate the contents of its contributor version.

In the following three paragraphs, a "patent license" is any express agreement or commitment, however denominated, not to enforce a patent (such as an express permission to practice a patent or covenant not to sue for patent infringement). To "grant" such a patent license to a

party means to make such an agreement or commitment not to enforce a patent against the party.

If you convey a covered work, knowingly relying on a patent license, and the Corresponding Source of the work is not available for anyone to copy, free of charge and under the terms of this

License, through a publicly available network server or other readily accessible means, then you must either (1) cause the Corresponding Source to be so available, or (2) arrange to deprive yourself of the benefit of the patent license for this particular work, or (3) arrange, in a manner consistent with the requirements of this License, to extend the patent license to downstream recipients. "Knowingly relying" means you have actual knowledge that, but for the patent license, your conveying the covered work in a country, or your recipient's use of the covered work in a country, would infringe one or more identifiable patents in that country that you have reason to believe are valid.

If, pursuant to or in connection with a single transaction or arrangement, you convey, or propagate by procuring conveyance of, a covered work, and grant a patent license to some of the parties receiving the covered work authorizing them to use, propagate, modify or convey a specific copy of the covered work, then the patent license you grant is automatically extended to all recipients of the covered work and works based on it.

A patent license is "discriminatory" if it does not include within the scope of its coverage, prohibits the exercise of, or is conditioned on the non-exercise of one or more of the rights that are specifically granted under this License. You may not convey a covered work if you are a party to an arrangement with a third party that is in the business of distributing software, under which you make payment to the third party based on the extent of your activity of conveying the work, and under which the third party grants, to any of the parties who would receive the covered work from you, a discriminatory patent license (a) in connection with copies of the covered work conveyed by you (or copies made from those copies), or (b) primarily for and in connection with specific products or compilations that contain the covered work, unless you entered into that arrangement, or that patent license was granted, prior to 28 March 2007.

Nothing in this License shall be construed as excluding or limiting any implied license or other defenses to infringement that may otherwise be available to you under applicable patent law.

12. No Surrender of Others' Freedom.

If conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot convey a covered work so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not convey it at all. For example, if you agree to terms that obligate you to collect a royalty for further conveying from those to whom you convey the Program, the only way you could satisfy both those terms and this License would be to refrain entirely from conveying the Program.

13. Use with the GNU Affero General Public License.

Notwithstanding any other provision of this License, you have permission to link or combine any covered work with a work licensed under version 3 of the GNU Affero General Public License into a single combined work, and to convey the resulting work. The terms of this License will continue to apply to the part which is the covered work, but the special requirements of the GNU Affero General Public License, section 13, concerning interaction through a network will apply to the combination as such.

14. Revised Versions of this License.

The Free Software Foundation may publish revised and/or new versions of the GNU General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Program specifies that a certain numbered version of the GNU General Public License "or any later version" applies to it, you have the option of following the terms and conditions either of that numbered version or of any later version published by the Free Software Foundation. If the Program does not specify a version number of the GNU General Public License, you may choose any version ever published by the Free Software Foundation.

If the Program specifies that a proxy can decide which future versions of the GNU General Public License can be used, that proxy's public statement of acceptance of a version permanently authorizes you to choose that version for the Program.

Later license versions may give you additional or different permissions. However, no additional obligations are imposed on any author or copyright holder as a result of your choosing to follow a later version.

15. Disclaimer of Warranty.

THERE IS NO WARRANTY FOR THE PROGRAM, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE PROGRAM "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE PROGRAM IS WITH YOU. SHOULD THE PROGRAM PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

16. Limitation of Liability.

IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MODIFIES AND/OR CONVEYS THE PROGRAM AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE PROGRAM (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE PROGRAM TO OPERATE WITH ANY OTHER PROGRAMS), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

17.

Interpretation of Sections 15 and 16.

If the disclaimer of warranty and limitation of liability provided above cannot be given local legal effect according to their terms, reviewing courts shall apply local law that most closely approximates an absolute waiver of all civil liability in connection with the Program, unless a warranty or assumption of liability accompanies a copy of the Program in return for a fee.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Programs

If you develop a new program, and you want it to be of the greatest possible use to the public, the best way to achieve this is to make it free software which everyone can redistribute and change under these terms.

To do so, attach the following notices to the program. It is safest to attach them to the start of each source file to most effectively state the exclusion of warranty; and each file should have at least the "copyright" line and a pointer to where

the full notice is found.

<one line to give the program's name and a brief idea of what it does.>
Copyright (C) <year> <name of author>

This program is free software: you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation, either version 3 of the License, or (at your option) any later version.

This program is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details.

You should have received a copy of the GNU General Public License along with this program. If not, see <<http://www.gnu.org/licenses/>>.

Also add information on how to contact you by electronic and paper mail.

If the program does terminal interaction, make it output a short notice like this when it starts in an interactive mode:

```
<program> Copyright (C) <year> <name of author>  
This program comes with ABSOLUTELY NO WARRANTY; for details type `show w'.  
This is free software, and you are welcome to redistribute it  
under certain conditions; type `show c' for details.
```

The hypothetical commands `show w' and `show c' should show the appropriate parts of the General Public License. Of course, your program's commands might be different; for a GUI interface, you would use an "about box".

You should also get your employer (if you work as a programmer) or school, if any, to sign a "copyright disclaimer" for the program, if necessary. For more information on this, and how to apply and follow the GNU GPL, see <<http://www.gnu.org/licenses/>>.

The GNU General Public License does not permit incorporating your program into proprietary programs. If your program is a subroutine library, you may consider it more useful to permit linking proprietary applications with the library. If this is what you want to do, use the GNU Lesser General Public License instead of this License. But first, please read <<http://www.gnu.org/philosophy/why-not-lgpl.html>>.

GNU LESSER GENERAL PUBLIC LICENSE

Version 3, 29 June 2007

Copyright (C) 2007 Free Software Foundation, Inc. <<http://fsf.org/>>

Everyone is permitted to copy and distribute verbatim copies of this license document, but changing it is not allowed.

This version of the GNU Lesser General Public License incorporates the terms and conditions of version 3 of the GNU General Public License, supplemented by the additional permissions listed below.

0. Additional Definitions.

As used herein, "this License" refers to version 3 of the GNU Lesser General Public License, and the "GNU GPL" refers to version 3 of the GNU General Public License.

"The Library" refers to a covered work governed by this License, other than an Application or a Combined Work as defined below.

An "Application" is any work that makes use of an interface provided by the Library, but which is not otherwise based on the Library. Defining a subclass of a class defined by the Library is deemed a mode of using an interface provided by the Library.

A "Combined Work" is a work produced by combining or linking an Application with the Library. The particular version of the Library with which the Combined Work was made is also called the "Linked Version".

The "Minimal Corresponding Source" for a Combined Work means the Corresponding Source for the Combined Work, excluding any source code for portions of the Combined Work that, considered in isolation, are based on the Application, and not on the Linked Version.

The "Corresponding Application Code" for a Combined Work means the object code and/or source code for the Application, including any data and utility programs needed for reproducing the Combined Work from the Application, but excluding the System Libraries of the Combined Work.

1. Exception to Section 3 of the GNU GPL.

You may convey a covered work under sections 3 and 4 of this License without being bound by section 3 of the GNU GPL.

2. Conveying Modified Versions.

If you modify a copy of the Library, and, in your modifications, a

facility refers to a function or data to be supplied by an Application that uses the facility (other than as an argument passed when the facility is invoked), then you may convey a copy of the modified version:

- a) under this License, provided that you make a good faith effort to ensure that, in the event an Application does not supply the function or data, the facility still operates, and performs whatever part of its purpose remains meaningful, or
- b) under the GNU GPL, with none of the additional permissions of this License applicable to that copy.

3. Object Code Incorporating Material from Library Header Files.

The object code form of an Application may incorporate material from a header file that is part of the Library. You may convey such object code under terms of your choice, provided that, if the incorporated material is not limited to numerical parameters, data structure layouts and accessors, or small macros, inline functions and templates (ten or fewer lines in length), you do both of the following:

- a) Give prominent notice with each copy of the object code that the Library is used in it and that the Library and its use are covered by this License.
- b) Accompany the object code with a copy of the GNU GPL and this license document.

4. Combined Works.

You may convey a Combined Work under terms of your choice that, taken together, effectively do not restrict modification of the portions of the Library contained in the Combined Work and reverse engineering for debugging such modifications, if you also do each of the following:

- a) Give prominent notice with each copy of the Combined Work that the Library is used in it and that the Library and its use are covered by this License.
- b) Accompany the Combined Work with a copy of the GNU GPL and this license document.
- c) For a Combined Work that displays copyright notices during execution, include the copyright notice for the Library among

these notices, as well as a reference directing the user to the copies of the GNU GPL and this license document.

d) Do one of the following:

0) Convey the Minimal Corresponding Source under the terms of this License, and the Corresponding Application Code in a form suitable for, and under terms that permit, the user to recombine or relink the Application with a modified version of the Linked Version to produce a modified Combined Work, in the manner specified by section 6 of the GNU GPL for conveying Corresponding Source.

1) Use a suitable shared library mechanism for linking with the Library. A suitable mechanism is one that (a) uses at run time a copy of the Library already present on the user's computer system, and (b) will operate properly with a modified version of the Library that is interface-compatible

with the Linked

Version.

e) Provide Installation Information, but only if you would otherwise be required to provide such information under section 6 of the GNU GPL, and only to the extent that such information is necessary to install and execute a modified version of the Combined Work produced by recombining or relinking the Application with a modified version of the Linked Version. (If you use option 4d0, the Installation Information must accompany the Minimal Corresponding Source and Corresponding Application Code. If you use option 4d1, you must provide the Installation Information in the manner specified by section 6 of the GNU GPL for conveying Corresponding Source.)

5. Combined Libraries.

You may place library facilities that are a work based on the Library side by side in a single library together with other library facilities that are not Applications and are not covered by this License, and convey such a combined library under terms of your choice, if you do both of the following:

a) Accompany the combined library with a copy of the same work based on the Library, uncombined with any other library facilities, conveyed under the terms of this License.

b) Give prominent notice with the combined library that part of it is a work based on the Library, and explaining where to find the

accompanying uncombined form of the same work.

6. Revised Versions of the GNU Lesser General Public License.

The Free Software Foundation may publish revised and/or new versions of the GNU Lesser General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Library as you received it specifies that a certain numbered version of the GNU Lesser General Public License "or any later version" applies to it, you have the option of following the terms and conditions either of that published version or of any later version published by the Free Software Foundation. If the Library as you received it does not specify a version number of the GNU Lesser General Public License, you may choose any version of the GNU Lesser General Public License ever published by the Free Software Foundation.

If the Library as you received it specifies that a proxy can decide whether future versions of the GNU Lesser General Public License shall apply, that proxy's public statement of acceptance of any version is permanent authorization for you to choose that version for the Library.

GNU GENERAL PUBLIC LICENSE

Version 3, 29 June 2007

Copyright (C) 2007 Free Software Foundation, Inc. <<http://fsf.org/>>
Everyone is permitted to copy and distribute verbatim copies of this license document, but changing it is not allowed.

Preamble

The GNU General Public License is a free, copyleft license for software and other kinds of works.

The licenses for most software and other practical works are designed to take away your freedom to share and change the works. By contrast, the GNU General Public License is intended to guarantee your freedom to share and change all versions of a program--to make sure it remains free software for all its users. We, the Free Software Foundation, use the GNU General Public License for most of our software; it applies also to any other work released this way by its authors. You can apply it to your programs, too.

When we speak of free software, we are referring to

freedom, not price. Our General Public Licenses are designed to make sure that you have the freedom to distribute copies of free software (and charge for them if you wish), that you receive source code or can get it if you want it, that you can change the software or use pieces of it in new free programs, and that you know you can do these things.

To protect your rights, we need to prevent others from denying you these rights or asking you to surrender the rights. Therefore, you have certain responsibilities if you distribute copies of the software, or if you modify it: responsibilities to respect the freedom of others.

For example, if you distribute copies of such a program, whether gratis or for a fee, you must pass on to the recipients the same freedoms that you received. You must make sure that they, too, receive or can get the source code. And you must show them these terms so they know their rights.

Developers that use the GNU GPL protect your rights with two steps: (1) assert copyright on the software, and (2) offer you this License giving you legal permission to copy, distribute and/or modify it.

For the developers' and authors' protection, the GPL clearly explains that there is no warranty for this free software. For both users' and authors' sake, the GPL requires that modified versions be marked as changed, so that their problems will not be attributed erroneously to authors of previous versions.

Some devices are designed to deny users access to install or run modified versions of the software inside them, although the manufacturer can do so. This is fundamentally incompatible with the aim of protecting users' freedom to change the software. The systematic pattern of such abuse occurs in the area of products for individuals to use, which is precisely where it is most unacceptable. Therefore, we have designed this version of the GPL to prohibit the practice for those products. If such problems arise substantially in other domains, we stand ready to extend this provision to those domains in future versions of the GPL, as needed to protect the freedom of users.

Finally, every program is threatened constantly by software patents. States should not allow patents to restrict development and use of software on general-purpose computers, but in those that do, we wish to avoid the special danger that patents applied to a free program could make it effectively proprietary. To prevent this, the GPL assures that patents cannot be used to render the program non-free.

The precise terms and conditions for copying, distribution and modification follow.

TERMS AND CONDITIONS

0. Definitions.

"This License" refers to version 3 of the GNU General Public License.

"Copyright" also means copyright-like laws that apply to other kinds of works, such as semiconductor masks.

"The Program" refers to any copyrightable work licensed under this License. Each licensee is addressed as "you". "Licensees" and "recipients" may be individuals or organizations.

To "modify" a work means to copy from or adapt all or part of the work in a fashion requiring copyright permission, other than the making of an exact copy. The resulting work is called a "modified version" of the earlier work or a work "based on" the earlier work.

A "covered work" means either the unmodified Program or a work based on the Program.

To "propagate" a work means to do anything with it that, without permission, would make you directly or secondarily liable for infringement under applicable copyright law, except executing it on a computer or modifying a private copy. Propagation includes copying, distribution (with or without modification), making available to the public, and in some countries other activities as well.

To "convey" a work means any kind of propagation that enables other parties to make or receive copies. Mere interaction with a user through a computer network, with no transfer of a copy, is not conveying.

An interactive user interface displays "Appropriate Legal Notices" to the extent that it includes a convenient and prominently visible feature that (1) displays an appropriate copyright notice, and (2) tells the user that there is no warranty for the work (except to the extent that warranties are provided), that licensees may convey the work under this License, and how to view a copy of this License. If the interface presents a list of user commands or options, such as a menu, a prominent item in the list meets this criterion.

1. Source Code.

The "source code" for a work means the preferred form of the work for making modifications to it. "Object code" means any non-source form of a work.

A "Standard Interface" means an interface that either is an official standard defined by a recognized standards body, or, in the case of interfaces specified for a particular programming language, one that is widely used among developers working in that language.

The

"System Libraries" of an executable work include anything, other than the work as a whole, that (a) is included in the normal form of packaging a Major Component, but which is not part of that Major Component, and (b) serves only to enable use of the work with that Major Component, or to implement a Standard Interface for which an implementation is available to the public in source code form. A "Major Component", in this context, means a major essential component (kernel, window system, and so on) of the specific operating system (if any) on which the executable work runs, or a compiler used to produce the work, or an object code interpreter used to run it.

The "Corresponding Source" for a work in object code form means all the source code needed to generate, install, and (for an executable work) run the object code and to modify the work, including scripts to control those activities. However, it does not include the work's System Libraries, or general-purpose tools or generally available free programs which are used unmodified in performing those activities but which are not part of the work. For example, Corresponding Source includes interface definition files associated with source files for the work, and the source code for shared libraries and dynamically linked subprograms that the work is specifically designed to require, such as by intimate data communication or control flow between those subprograms and other parts of the work.

The Corresponding Source need not include anything that users can regenerate automatically from other parts of the Corresponding Source.

The Corresponding Source for a work in source code form is that same work.

2. Basic Permissions.

All rights granted under this License are granted for the term of copyright on the Program, and are irrevocable provided the stated conditions are met. This License explicitly affirms your unlimited permission to run the unmodified Program. The output from running a

covered work is covered

by this License only if the output, given its content, constitutes a covered work. This License acknowledges your rights of fair use or other equivalent, as provided by copyright law.

You may make, run and propagate covered works that you do not convey, without conditions so long as your license otherwise remains in force. You may convey covered works to others for the sole purpose of having them make modifications exclusively for you, or provide you with facilities for running those works, provided that you comply with the terms of this License in conveying all material for which you do not control copyright. Those thus making or running the covered works for you must do so exclusively on your behalf, under your direction and control, on terms that prohibit them from making any copies of your copyrighted material outside their relationship with you.

Conveying under any other circumstances is permitted solely under the conditions stated below. Sublicensing is not allowed; section 10 makes it unnecessary.

3. Protecting Users' Legal Rights From Anti-Circumvention Law.

No covered work shall be deemed part of an effective technological measure under any applicable law fulfilling obligations under article 11 of the WIPO copyright treaty adopted on 20 December 1996, or similar laws prohibiting or restricting circumvention of such measures.

When you convey a covered work, you waive any legal power to forbid circumvention of technological measures to the extent such circumvention is effected by exercising rights under this License with respect to the covered work, and you disclaim any intention to limit operation or modification of the work as a means of enforcing, against the work's users, your or third parties' legal rights to forbid circumvention of technological measures.

4. Conveying Verbatim Copies.

You may convey verbatim copies of the Program's source code as you receive it, in any medium, provided that you conspicuously and appropriately publish on each copy an appropriate copyright notice; keep intact all notices stating that this License and any non-permissive terms added in accord with section 7 apply to the code; keep intact all notices of the absence of any warranty; and give all recipients a copy of this License along with the Program.

You may charge any price or no price for each copy that you convey, and you may offer support or warranty protection for a fee.

5. Conveying Modified Source Versions.

You may convey a work based on the Program, or the modifications to produce it from the Program, in the form of source code under the terms of section 4, provided that you also meet all of these conditions:

- a) The work must carry prominent notices stating that you modified it, and giving a relevant date.
- b) The work must carry prominent notices stating that it is released under this License and any conditions added under section 7. This requirement modifies the requirement in section 4 to "keep intact all notices".
- c) You must license the entire work, as a whole, under this License to anyone who comes into possession of a copy. This License will therefore apply, along with any applicable section 7 additional terms, to the whole of the work, and all its parts, regardless of how they are packaged. This License gives no permission to license the work in any other way, but it does not invalidate such permission if you have separately received it.
- d) If the work has interactive user interfaces, each must display Appropriate Legal Notices; however, if the Program has interactive interfaces that do not display Appropriate Legal Notices, your work need not make them do so.

A compilation of a covered work with other separate and independent works, which are not by their nature extensions of the covered work, and which are not combined with it such as to form a larger program, in or on a volume of a storage or distribution medium, is called an "aggregate" if the compilation and its resulting copyright are not used to limit the access or legal rights of the compilation's users beyond what the individual works permit. Inclusion of a covered work in an aggregate does not cause this License to apply to the other parts of the aggregate.

6. Conveying Non-Source Forms.

You may convey a covered work in object code form under the terms of sections 4 and 5, provided that you also convey the machine-readable Corresponding Source under the terms of this License, in one of these ways:

a) Convey the object code in, or embodied in, a physical product (including a physical distribution medium), accompanied by the Corresponding Source fixed on a durable physical medium customarily used for software interchange.

b) Convey the object code in, or embodied in, a physical product (including a physical distribution medium), accompanied by a written offer, valid for at least three years and valid for as

long as you offer spare parts or customer support for that product model, to give anyone who possesses the object code either (1) a copy of the Corresponding Source for all the software in the product that is covered by this License, on a durable physical medium customarily used for software interchange, for a price no more than your reasonable cost of physically performing this conveying of source, or (2) access to copy the Corresponding Source from a network server at no charge.

c) Convey individual copies of the object code with a copy of the written offer to provide the Corresponding Source. This alternative is allowed only occasionally and noncommercially, and only if you received the object code with such an offer, in accord with subsection 6b.

d) Convey the object code by offering access from a designated place (gratis or for a charge), and offer equivalent access to the Corresponding Source in the same way through the same place at no further charge. You need not require recipients to copy the Corresponding Source along with the object code. If the place to copy the object code is a network server, the Corresponding Source may be on a different server (operated by you or a third party) that supports equivalent copying facilities, provided you maintain clear directions next to the object code saying where to find the Corresponding Source. Regardless of what server hosts the Corresponding Source, you remain obligated to ensure that it is available for as long as needed to satisfy these requirements.

e) Convey the object code using peer-to-peer transmission, provided you inform other peers where the object code and Corresponding Source of the work are being offered to the general public at no charge under subsection 6d.

A separable portion of the object code, whose source code is excluded from the Corresponding Source as a System Library, need not be included in conveying the object code work.

A "User Product" is either (1) a "consumer product", which means any tangible personal property which is normally used for personal, family, or household purposes, or (2) anything designed or sold for incorporation into a dwelling. In determining whether a product is a consumer product, doubtful cases shall be resolved in favor of coverage. For a particular product received by a particular user, "normally used" refers to a typical or common use of that class of product, regardless of the status of the particular user or of the way in which the particular user actually uses, or expects or is expected to use, the product. A product is a consumer product regardless of whether the product has substantial commercial, industrial or non-consumer uses, unless such uses represent the only significant mode of use of the product.

"Installation Information" for a User Product means any methods, procedures, authorization keys, or other information required to install and execute modified versions of a covered work in that User Product from a modified version of its Corresponding Source. The information must suffice to ensure that the continued functioning of the modified object code is in no case prevented or interfered with solely because modification has been made.

If you convey an object code work under this section in, or with, or specifically for use in, a User Product, and the conveying occurs as part of a transaction in which the right of possession and use of the User Product is transferred to the recipient in perpetuity or for a fixed term (regardless of how the transaction is characterized), the Corresponding Source conveyed under this section must be accompanied by the Installation Information. But this requirement does not apply if neither you nor any third party retains the ability to install modified object code on the User Product (for example, the work has been installed in ROM).

The requirement to provide Installation Information does not include a requirement to continue to provide support service, warranty, or updates for a work that has been modified or installed by the recipient, or for the User Product in which it has been modified or installed. Access to a network may be denied when the modification itself materially and adversely affects the operation of the network or violates the rules and protocols for communication across the network.

Corresponding Source conveyed, and Installation Information provided, in accord with this section must be in a format that is publicly documented (and with an implementation available to the public in source code form), and must require no special password or key for unpacking, reading or copying.

7. Additional Terms.

"Additional permissions" are terms that supplement the terms of this License by making exceptions from one or more of its conditions. Additional permissions that are applicable to the entire Program shall be treated as though they were included in this License, to the extent that they are valid under applicable law. If additional permissions apply only to part of the Program, that part may be used separately under those permissions, but the entire Program remains governed by this License without regard to the additional permissions.

When you convey a copy of a covered work, you may at your option remove any additional permissions from that copy, or from any part of it. (Additional permissions may be written to require their own removal in certain cases when you modify the work.) You may place additional permissions on material, added by you to a covered work, for which you have or can give appropriate copyright permission.

Notwithstanding any other provision of this License, for material you add to a covered work, you may (if authorized by the copyright holders of that material) supplement the terms of this License with terms:

- a) Disclaiming warranty or limiting liability differently from the terms of sections 15 and 16 of this License; or
- b) Requiring preservation of specified reasonable legal notices or author attributions in that material or in the Appropriate Legal Notices displayed by works containing it; or
- c) Prohibiting misrepresentation of the origin of that material, or requiring that modified versions of such material be marked in reasonable ways as different from the original version; or
- d) Limiting the use for publicity purposes of names of licensors or authors of the material; or
- e) Declining to grant rights under trademark law for use of some trade names, trademarks, or service marks; or
- f) Requiring indemnification of licensors and authors of that material by anyone who conveys the material (or modified versions of it) with contractual assumptions of liability to the recipient, for any liability that these contractual assumptions directly impose on

those licensors and authors.

All other non-permissive additional terms are considered "further restrictions" within the meaning of section 10. If the Program as you received it, or any part of it, contains a notice stating that it is governed by this License along with a term that is a further restriction, you may remove that term. If a license document contains a further restriction but permits relicensing or conveying under this License, you may add to a covered work material governed by the terms of that license document, provided that the further restriction does not survive such relicensing or conveying.

If you add terms to a covered work in accord with this section, you must place, in the relevant source files, a statement of the additional terms that apply to those files, or a notice indicating where to find the applicable terms.

Additional terms, permissive or non-permissive, may be stated in the form of a separately written license, or stated as exceptions; the above requirements apply either way.

8. Termination.

You may not propagate or modify a covered work except as expressly provided under this License. Any attempt otherwise to propagate or modify it is void, and will automatically terminate your rights under this License (including any patent licenses granted under the third paragraph of section 11).

However, if you cease all violation of this License, then your license from a particular copyright holder is reinstated (a) provisionally, unless and until the copyright holder explicitly and finally terminates your license, and (b) permanently, if the copyright holder fails to notify you of the violation by some reasonable means prior to 60 days after the cessation.

Moreover, your license from a particular copyright holder is reinstated permanently if the copyright holder notifies you of the violation by some reasonable means, this is the first time you have received notice of violation of this License (for any work) from that copyright holder, and you cure the violation prior to 30 days after your receipt of the notice.

Termination of your rights under this section does not terminate the licenses of parties who have received copies or rights from you under this License. If your rights have been terminated and not permanently

reinstated, you do not qualify to receive new licenses for the same material under section 10.

9. Acceptance Not Required for Having Copies.

You are not required to accept this License in order to receive or run a copy of the Program. Ancillary propagation of a covered work occurring solely as a consequence of using peer-to-peer transmission to receive a copy likewise does not require acceptance. However, nothing other than this License grants you permission to propagate or modify any covered work. These actions infringe copyright if you do not accept this License. Therefore, by modifying or propagating a covered work, you indicate your acceptance of this License to do so.

10. Automatic Licensing of Downstream Recipients.

Each time you convey a covered work, the recipient automatically receives a license from the original licensors, to run, modify and propagate that work, subject to this License. You are not responsible for enforcing compliance by third parties with this License.

An "entity transaction" is a transaction transferring control of an organization, or substantially all assets of one, or subdividing an organization, or merging organizations. If propagation of a covered work results from an entity transaction, each party to that transaction who receives a copy of the work also receives whatever licenses to the work the party's predecessor in interest had or could give under the previous paragraph, plus a right to possession of the Corresponding Source of the work from the predecessor in interest, if the predecessor has it or can get it with reasonable efforts.

You may not impose any further restrictions on the exercise of the rights granted or affirmed under this License. For example, you may not impose a license fee, royalty, or other charge for exercise of rights granted under this License, and you may not initiate litigation (including a cross-claim or counterclaim in a lawsuit) alleging that any patent claim is infringed by making, using, selling, offering for sale, or importing the Program or any portion of it.

11. Patents.

A "contributor" is a copyright holder who authorizes use under this License of the Program or a work on which the Program is based. The work thus licensed is called the contributor's "contributor version".

A contributor's "essential patent claims" are all patent claims

owned or controlled by the contributor, whether already acquired or hereafter acquired, that would be infringed by some manner, permitted by this License, of making, using, or selling its contributor version, but do not include claims that would be infringed only as a consequence of further modification of the contributor version. For purposes of this definition, "control" includes the right to grant patent sublicenses in a manner consistent with the requirements of this License.

Each contributor grants you a non-exclusive, worldwide, royalty-free patent license under the contributor's essential patent claims, to make, use, sell, offer for sale, import and otherwise run, modify and propagate the contents of its contributor version.

In the following three paragraphs, a "patent license" is any express agreement or commitment, however denominated, not to enforce a patent (such as an express permission to practice a patent or covenant not to sue for patent infringement). To "grant" such a patent license to a party means to make such an agreement or commitment not to enforce a patent against the party.

If you convey a covered work, knowingly relying on a patent license, and the Corresponding Source of the work is not available for anyone to copy, free of charge and under the terms of this License, through a publicly available network server or other readily accessible means, then you must either (1) cause the Corresponding Source to be so available, or (2) arrange to deprive yourself of the benefit of the patent license for this particular work, or (3) arrange, in a manner consistent with the requirements of this License, to extend the patent license to downstream recipients. "Knowingly relying" means you have actual knowledge that, but for the patent license, your conveying the covered work in a country, or your recipient's use of the covered work in a country, would infringe one or more identifiable patents in that country that you have reason to believe are valid.

If, pursuant to or in connection with a single transaction or arrangement, you convey, or propagate by procuring conveyance of, a covered work, and grant a patent license to some of the parties receiving the covered work authorizing them to use, propagate, modify or convey a specific copy of the covered work, then the patent license you grant is automatically extended to all recipients of the covered work and works based on it.

A patent license is "discriminatory" if it does not include within the scope of its coverage, prohibits the exercise of, or is

conditioned on the non-exercise of one or more of the rights that are specifically granted under this License. You may not convey a covered work if you are a party to an arrangement with a third party that is in the business of distributing software, under which you make payment to the third party based on the extent of your activity of conveying the work, and under which the third party grants, to any of the parties who would receive the covered work from you, a discriminatory patent license (a) in connection with copies of the covered work conveyed by you (or copies made from those copies), or (b) primarily for and in connection with specific products or compilations that contain the covered work, unless you entered into that arrangement, or that patent license was granted, prior to 28 March 2007.

Nothing in this License shall be construed as excluding or limiting any implied license or other defenses to infringement that may otherwise be available to you under applicable patent law.

12. No Surrender of Others' Freedom.

If conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot convey a covered work so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not convey it at all. For example, if you agree to terms that obligate you to collect a royalty for further conveying from those to whom you convey the Program, the only way you could satisfy both those terms and this License would be to refrain entirely from conveying the Program.

13. Use with the GNU Affero General Public License.

Notwithstanding any other provision of this License, you have permission to link or combine any covered work with a work licensed under version 3 of the GNU Affero General Public License into a single combined work, and to convey the resulting work. The terms of this License will continue to apply to the part which is the covered work, but the special requirements of the GNU Affero General Public License, section 13, concerning interaction through a network will apply to the combination as such.

14. Revised Versions of this License.

The Free Software Foundation may publish revised and/or new versions of the GNU General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Program specifies that a certain numbered version of the GNU General Public License "or any later version" applies to it, you have the option of following the terms and conditions either of that numbered version or of any later version published by the Free Software Foundation. If the Program does not specify a version number of the GNU General Public License, you may choose any version ever published by the Free Software Foundation.

If the Program specifies that a proxy can decide which future versions of the GNU General Public License can be used, that proxy's public statement of acceptance of a version permanently authorizes you to choose that version for the Program.

Later license versions may give you additional or different permissions. However, no additional obligations are imposed on any author or copyright holder as a result of your choosing to follow a later version.

15. Disclaimer of Warranty.

THERE IS NO WARRANTY FOR THE PROGRAM, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE PROGRAM "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE PROGRAM IS WITH YOU. SHOULD THE PROGRAM PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

16. Limitation of Liability.

IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MODIFIES AND/OR CONVEYS THE PROGRAM AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE PROGRAM (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE PROGRAM TO OPERATE WITH ANY OTHER PROGRAMS), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

17.

Interpretation of Sections 15 and 16.

If the disclaimer of warranty and limitation of liability provided

above cannot be given local legal effect according to their terms, reviewing courts shall apply local law that most closely approximates an absolute waiver of all civil liability in connection with the Program, unless a warranty or assumption of liability accompanies a copy of the Program in return for a fee.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Programs

If you develop a new program, and you want it to be of the greatest possible use to the public, the best way to achieve this is to make it free software which everyone can redistribute and change under these terms.

To do so, attach the following notices to the program. It is safest to attach them to the start of each source file to most effectively state the exclusion of warranty; and each file should have at least the "copyright" line and a pointer to where the full notice is found.

```
<one line to give the program's name and a brief idea of what it does.>  
Copyright (C) <year> <name of author>
```

This program is free software: you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation, either version 3 of the License, or (at your option) any later version.

This program is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details.

You should have received a copy of the GNU General Public License along with this program. If not, see <https://www.gnu.org/licenses/>.

Also add information on how to contact you by electronic and paper mail.

If the program does terminal interaction, make it output a short notice like this when it starts in an interactive mode:

```
<program> Copyright (C) <year> <name of author>  
This program comes with ABSOLUTELY NO WARRANTY; for details type `show w'.  
This is free software, and you are welcome to redistribute it  
under certain conditions; type `show c' for details.
```

The hypothetical commands `show w' and `show c' should show the appropriate parts of the General Public License. Of course, your program's commands

might be different; for a GUI interface, you would use an "about box".

You should also get your employer (if you work as a programmer) or school, if any, to sign a "copyright disclaimer" for the program, if necessary. For more information on this, and how to apply and follow the GNU GPL, see <https://www.gnu.org/licenses/>.

The GNU General Public License does not permit incorporating your program into proprietary programs. If your program is a subroutine library, you may consider it more useful to permit linking proprietary applications with the library. If this is what you want to do, use the GNU Lesser General Public License instead of this License. But first, please read <https://www.gnu.org/philosophy/why-not-lgpl.html>.

1.93 perl 5.26.1-6ubuntu0.6

1.93.1 Available under license :

No license file was found, but licenses were detected in source scan.

```
?RCS: Copyright (c) 2016 Tony Cook
?RCS:
?RCS: You may distribute under the terms of either the GNU General Public
?RCS: License or the Artistic License, as specified in the README file.
?RCS:
?MAKE:dtraceobject dtracexnolib: usedtrace dtrace cc cflags optimize \
  Compile cat rm_try
?MAKE: -pick add $@ %<
?S:dtraceobject:
?S: Whether we need to build an object file with the dtrace tool.
?S:.
?S:dtracexnolib:
?S: Whether dtrace accepts -xnolib. If available we call dtrace -h
?S: and dtrace -G with -xnolib to allow dtrace to run in a jail on
?S: FreeBSD.
?S:.
?T:xnolib
: Probe whether dtrace builds an object, as newer Illumos requires an input
: object file that uses at least one of the probes defined in the .d file
case "$usedtrace" in
$define)
  case "$dtracexnolib" in
  $define|true|[yY]*)
    dtracexnolib=$define
$dtrace -h -xnolib -s ../perldtrace.d -o perldtrace.h
;;
'')
```

```

    if $dtrace
-h -xnolib -s ../perldtrace.d -o perldtrace.h 2>&1 ; then
    dtracexnolib=$define
    echo "Your dtrace accepts -xnolib"
elif $dtrace -h -s ../perldtrace.d -o perldtrace.h 2>&1 ; then
    dtracexnolib=$undef
    echo "Your dtrace doesn't accept -xnolib"
else
    echo "Your dtrace doesn't work at all, try building without dtrace support" >&4
    exit 1
fi
;;
*)
    dtracexnolib=$undef
$dtrace -h -s ../perldtrace.d -o perldtrace.h
;;
esac
case $dtracexnolib in
$define) xnolib=-xnolib ;;
*) xnolib= ;;
esac

case "$dtraceobject" in
$define|true|[yY]*)
    dtraceobject=$define
    ;;
'|")
    $cat >try.c <<EOM
#include "perldtrace.h"
int main(void) {
    PERL_LOADED_FILE("dummy");
    return 0;
}
EOM
    dtraceobject=$undef
    if $cc -c -o try.o $optimize $ccflags try.c \
        && $dtrace -G $xnolib -s ../perldtrace.d try.o >/dev/null 2>&1; then
        dtraceobject=$define
        echo "Your dtrace builds an object file"
    fi
    ;;
*) dtraceobject=$undef ;;
esac
$rm_try perldtrace.o perldtrace.h
esac

```

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-

debian-perl-5.26.1/U/perl/dtraceobject.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: vendorscript.U,v 1.1 1999/07/08 18:32:57 doughera Exp doughera \$

?RCS:

?RCS: Copyright (c) 1999, Andy Dougherty

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 3.0.

?RCS:

?RCS: \$Log: vendorscript.U,v \$

?RCS: Revision 1.1 1999/07/08 18:32:57 doughera

?RCS: Initial revision

?RCS:

?MAKE:d_vendorscript vendorscript vendorscriptexp installvendorscript: Getfile \

vendorbin cat Setprefixvar Oldconfig Prefixit test vendorprefix

?MAKE: -pick add \$@ %<

?Y:TOP

?S:vendorscript:

?S: This variable contains the eventual value of the VENDORSRIPT symbol.

?S: It may have a ~ on the front.

?S: The standard distribution will put nothing in this directory.

?S: Vendors who distribute perl may wish to place additional

?S: executable scripts in this directory with

?S: MakeMaker Makefile.PL INSTALLDIRS=vendor

?S: or equivalent. See INSTALL for details.

?S:.

?S:vendorscriptexp:

?S: This variable is the ~name expanded version of vendorscript, so that you

?S: may use it directly in Makefiles or shell scripts.

?S:.

?D:installvendorscript="

?S:installvendorscript:

?S: This variable is really the same as vendorscriptexp but may differ on

?S: those systems using AFS. For extra portability, only this variable

?S: should be used in makefiles.

?S:.

?S:d_vendorscript:

?S: This variable conditionally defines PERL_VENDORSRIPT.

?S:.

?C:PERL_VENDORSRIPT:

?C: If defined, this symbol contains the name of a directory

?C: for holding vendor-supplied executable scripts.

?C: It may have a ~ on the front.

?C: The standard distribution will put nothing in this directory.
 ?C: Vendors who distribute perl may wish to place additional
 ?C: executable
 scripts in this directory with
 ?C: MakeMaker Makefile.PL INSTALLDIRS=vendor
 ?C: or equivalent. See INSTALL for details.
 ?C:.
 ?C:PERL_VENDORSCRIPT_EXP:
 ?C: This symbol contains the ~name expanded version of VENDORSCRIPT, to be used
 ?C: in programs that are not prepared to deal with ~ expansion at run-time.
 ?C:.
 ?H:#\$d_vendorscript PERL_VENDORSCRIPT "\$vendorscript" /**/
 ?H:#\$d_vendorscript PERL_VENDORSCRIPT_EXP "\$vendorscriptexp" /**/
 ?H:.
 ?LINT:change prefixvar
 ?LINT:set installvendorscript
 : Set the vendorscript variables
 case "\$vendorprefix" in
 ") d_vendorscript="\$undef"
 vendorscript="
 vendorscriptexp="
 ;;
 *) d_vendorscript="\$define"
 : determine where vendor-supplied scripts go.
 case "\$vendorscript" in
 ") dflt=\$vendorprefix/script
 \$test -d \$dflt || dflt=\$vendorbin ;;
 *) dflt="\$vendorscript" ;;
 esac
 \$cat <<EOM

The installation process will create a directory for
 vendor-supplied scripts.

```
EOM
fn=d~+
rp='Pathname for the vendor-supplied scripts directory?'
./getfile
vendorscript="$ans"
vendorscriptexp="$ansexp"
;;
esac
prefixvar=vendorscript
.
./installprefix
```

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-

debian-perl-5.26.1/U/installdirs/vendorscript.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: d_castneg.U,v \$

?RCS: Revision 3.0.1.2 1995/05/12 12:11:21 ram

?RCS: patch54: made sure cc and cflags are conditional dependencies

?RCS: patch54: added improved test case for Interactive Unix

?RCS:

?RCS: Revision 3.0.1.1 1994/10/29 16:10:50 ram

?RCS: patch36: don't forget to tell user about compilation failures (ADO)

?RCS: patch36: declare signal handler correctly using 'signal_t' (ADO)

?RCS:

?RCS: Revision 3.0 1993/08/18 12:05:47 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?X:

?X: Can

the compiler cast negative / odd floats to unsigned values.

?X:

?MAKE:d_castneg castflags: cat +cc +cflags rm_try Setvar signal_t

?MAKE: -pick add \$@ %<

?S:d_castneg:

?S: This variable conditionally defines CASTNEG, which indicates

?S: whether the C compiler can cast negative float to unsigned.

?S:.

?S:castflags:

?S: This variable contains a flag that precise difficulties the

?S: compiler has casting odd floating values to unsigned long:

?S: 0 = ok

?S: 1 = couldn't cast < 0

?S: 2 = couldn't cast >= 0x80000000

?S: 4 = couldn't cast in argument expression list

?S:.

?C:CASTNEGFLOAT:

?C: This symbol is defined if the C compiler can cast negative

?C: numbers to unsigned longs, ints and shorts.

?C:.

?C:CASTFLAGS:

```

?C: This symbol contains flags that say what difficulties the compiler
?C: has casting odd floating values to unsigned long:
?C: 0 = ok
?C: 1 = couldn't cast < 0
?C: 2 = couldn't cast >= 0x80000000
?C: 4 = couldn't cast in argument expression list
?C:.
?H:#$d_castneg CASTNEGFLOAT /**/
?H:#define
CASTFLAGS $castflags /**/
?H:.
?F:!try
?LINT:set d_castneg
: check for ability to cast negative floats to unsigned
echo " "
echo 'Checking whether your C compiler can cast negative float to unsigned.' >&4
$cat >try.c <<EOCP
#include <sys/types.h>
#include <signal.h>
$signal_t blech() { exit(7); }
$signal_t blech_in_list() { exit(4); }
unsigned long dummy_long(p) unsigned long p; { return p; }
unsigned int dummy_int(p) unsigned int p; { return p; }
unsigned short dummy_short(p) unsigned short p; { return p; }
int main()
{
double f = -123.;
unsigned long along;
unsigned int aint;
unsigned short ashort;
int result = 0;

signal(SIGFPE, blech);
along = (unsigned long)f;
aint = (unsigned int)f;
ashort = (unsigned short)f;
if (along != (unsigned long)-123)
result |= 1;
if (aint != (unsigned int)-123)
result |= 1;
if (ashort != (unsigned short)-123)
result |= 1;
f = (double)0x40000000;
f = f + f;
along = 0;
along = (unsigned long)f;
if

```

```

(long != 0x80000000)
result |= 2;
f -= 1.;
along = 0;
along = (unsigned long)f;
if (along != 0x7fffffff)
    result |= 1;
f += 2.;
along = 0;
along = (unsigned long)f;
if (along != 0x80000001)
    result |= 2;
if (result)
    exit(result);

```

?X:

?X: The following is a test for Interactive Unix Version 4.1, which
?X: has an 'improved' compiler which can correctly cast negative
?X: floats in expression lists, but apparently not in argument lists.
?X: Contributed by Winfried Koenig <win@incom.rhein-main.de>

?X:

```

signal(SIGFPE, blech_in_list);
f = 123.;
along = dummy_long((unsigned long)f);
aint = dummy_int((unsigned int)f);
ashort = dummy_short((unsigned short)f);
if (along != (unsigned long)123)
    result |= 4;
if (aint != (unsigned int)123)
    result |= 4;
if (ashort != (unsigned short)123)
    result |= 4;
exit(result);

```

}

EOCP

```

if $cc $ccflags -o try try.c >/dev/null 2>&1; then
./try
castflags=$?
else
echo "(I can't seem to compile the test program--assuming it can't)"
castflags=7
fi
case
"$castflags" in
0) val="$define"
echo "Yup, it can."
;;
*) val="$undef"

```

```
echo "Nope, it can't."  
;;  
esac  
set d_castneg  
eval $setvar  
$rm_try
```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/d_castneg.U
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1999, Jarkko Hietaniemi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 3.0.

?RCS:

?MAKE:d_sigwait: Inlibc

?MAKE: -pick add \$@ %<

?S:d_sigwait:

?S: This variable conditionally defines HAS_SIGWAIT

?S: if sigwait() is available to wait a signal.

?S:.

?C:HAS_SIGWAIT:

?C: This symbol, if defined, indicates that the sigwait

?C: system call is available to wait a signal.

?C:.

?H:#\$d_sigwait HAS_SIGWAIT /**/

?H:.

?LINT:set d_sigwait

: see if sigwait exists

set sigwait d_sigwait

eval \$inlibc

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_sigwait.U
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: pidtype.U,v 3.0.1.1 1994/08/29 16:31:27 ram Exp \$

?RCS:

?RCS: Copyright (c) 1991-1993, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 3.0.

?RCS:

?RCS: \$Log: pidtype.U,v \$

?RCS: Revision 3.0.1.1 1994/08/29 16:31:27 ram

?RCS: patch32: now uses new Typedef unit to compute type information

?RCS:

?RCS: Revision 3.0 1993/08/18 12:09:33 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?MAKE:pidtype: Myread Typedef

?MAKE: -pick add \$@ %<

?S:pidtype:

?S: This variable defines PIDTYPE to be something like pid_t, int,

?S: ushort, or whatever type is used to declare process ids in the kernel.

?S:.

?C:Pid_t (PIDTYPE):

?C: This

symbol holds the type used to declare process ids in the kernel.

?C: It can be int, uint, pid_t, etc... It may be necessary to include

?C: <sys/types.h> to get any typedef'ed information.

?C:.

?H:#define Pid_t \$pidtype /* PID type */

?H:.

?LINT: set pidtype

: see what type pids are declared as in the kernel

rp="What is the type of process ids on this system?"

set pid_t pidtype int stdio.h sys/types.h

eval \$typedef_ask

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/typedefs/pidtype.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 2000 Jarkko Hietaniemi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 3.0.

?RCS:

?MAKE:d__fwalk: Inlibc
?MAKE: -pick add \$@ %<
?S:d__fwalk:
?S: This variable conditionally defines HAS__FWALK if _fwalk() is
?S: available to apply a function to all the file handles.
?S:.
?C:HAS__FWALK:
?C: This symbol, if defined, indicates that the _fwalk system call is
?C: available to apply a function to all the file handles.
?C:.
?H:#\$d__fwalk HAS__FWALK /**/
?H:.
?LINT:set d__fwalk
: see if _fwalk exists
set fwalk d__fwalk
eval \$inlibc

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d__fwalk.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1998, Jarkko Hietaniemi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 3.0.

?X:

?X: Useless unit dropped. Use randfunc instead.

?X:

?LINT:empty

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/compline/randbits.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: longsize.U 1 2006-08-24 12:32:52Z rmanfredi \$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic Licence,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: \$Log: longsize.U,v \$
?RCS: Revision 3.0.1.2 1997/02/28 16:09:35 ram
?RCS: patch61: code moved to intsize.U
?RCS:
?RCS: Revision 3.0.1.1 1994/10/29 16:24:31 ram
?RCS: patch36: added ?F: line for metalint file checking
?RCS:
?RCS: Revision 3.0 1993/08/18 12:09:07 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?X:
?X: 'longsize' is now defined within intsize.U
?X:
?LINT: empty

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/longsize.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 2000 Jarkko Hietaniemi

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?MAKE:d_modfl d_modflproto: Inlibc Compile Hasproto cat \
test ccflags uselongdouble i_math \
d_sqrtl d_aintl d_copysignl d_ilogbl d_scalbnl d_frexp d_ldexpl \
d_truncl

?MAKE: -pick add \$@ %<

?S:d_modfl:

?S: This variable conditionally defines the HAS_MODFL symbol, which

?S: indicates to the C program that the modfl() routine is available.

?S:.

?S:d_modflproto:

?S: This symbol, if defined, indicates that the system provides

?S: a prototype for the modfl() function. Otherwise, it is up

?S: to the program to supply one. C99 says it should be

?S: long double modfl(long double, long double *);

?S:.

?C:HAS_MODFL:

?C: This symbol, if defined, indicates that the modfl routine is

?C: available to split a

```

long double x into a fractional part f and
?C: an integer part i such that  $|f| < 1.0$  and  $(f + i) = x$ .
?C:.
?C:HAS_MODFL_PROTO:
?C: This symbol, if defined, indicates that the system provides
?C: a prototype for the modfl() function. Otherwise, it is up
?C: to the program to supply one.
?C:.
?H:#$d_modfl HAS_MODFL /**/
?H:#$d_modflproto HAS_MODFL_PROTO /**/
?H:.
?T:message
?LINT:set d_modfl
?LINT:set d_modflproto
?LINT:change ccflags
: see if modfl exists
set modfl d_modfl
eval $inlibc

: see if prototype for modfl is available
echo " "
set d_modflproto modfl $i_math math.h
eval $hasproto

if $test "$uselongdouble" = "$define"; then
    message=""
    if $test "$d_sqrtl" != "$define"; then
        message="$message sqrtl"
    fi
    if $test "$d_modfl" != "$define"; then
        if $test "$d_trunc1:$d_copysign1" = "$define:$define"; then
            echo "You have both trunc1 and copysign1, so I can emulate modfl."
        else
            if $test "$d_aintl:$d_copysign1" = "$define:$define"; then
                echo "You have both
aintl and copysign1, so I can emulate modfl."
            else
                message="$message modfl"
            fi
        fi
    fi
    if $test "$d_frexp1" != "$define"; then
        if $test "$d_ilogbl:$d_scalbn1" = "$define:$define"; then
            echo "You have both ilogbl and scalbn1, so I can emulate frexp1."
        else
            message="$message frexp1"
        fi
    fi
fi

```

```
if $test "$d_ldexpl" != "$define"; then
message="$message ldexpl"
fi
```

```
if $test "$message" != ""; then
$cat <<EOM >&4
```

```
*** You requested the use of long doubles but you do not seem to have
*** the following mathematical functions needed for long double support:
*** $message
*** Please rerun Configure without -Duselongdouble and/or -Dusemorebits.
*** Cannot continue, aborting.
```

EOM

```
exit 1
fi
fi
```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/perl/d_modfl.U
```

No license file was found, but licenses were detected in source scan.

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?MAKE:d_llrintl: Inlibc

?MAKE: -pick add \$@ %<

?S:d_llrintl:

?S: This variable conditionally defines the HAS_LLRLNTL symbol, which

?S: indicates to the C program that the llrintl() routine is available

?S: to return the long long value closest to a long double (according

?S: to the current rounding mode).

?S:.

?C:HAS_LLRLNTL:

?C: This symbol, if defined, indicates that the llrintl routine is

?C: available to return the long long value closest to a long double

?C: (according to the current rounding mode).

?C:.

?H:#\$d_llrintl HAS_LLRLNTL /**/

?H:.

?LINT:set d_llrintl

: see if llrintl exists

set llrintl d_llrintl

eval \$inlibc

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_llrintl.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_chroot.U 1 2006-08-24 12:32:52Z rmanfredi \$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic Licence,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic Licence; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: Original Author: Andy Dougherty <doughera@lafcol.lafayette.edu>

?RCS:

?RCS: \$Log: d_chroot.U,v \$

?RCS: Revision 3.0.1.1 1994/08/29 16:07:17 ram

?RCS: patch32: created by ADO

?RCS:

?MAKE:d_chroot: Inlibc

?MAKE: -pick add \$@ %<

?S:d_chroot:

?S: This variable conditionally defines the HAS_CHROOT symbol, which

?S: indicates to the C program that the chroot() routine is available.

?S:.

?C:HAS_CHROOT :

?C: This symbol, if defined, indicates that the chroot routine

is

?C: available.

?C:.

?H:#\$d_chroot HAS_CHROOT /**/

?H:.

?LINT:set d_chroot

: see if chroot exists

set chroot d_chroot

eval \$inlibc

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/d_chroot.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_ulimit.U 1 2006-08-24 12:32:52Z rmanfredi \$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic Licence,

```

?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: $Log: d_ulimit.U,v $
?RCS: Revision 3.0 1993/08/18 12:07:51 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:d_ulimit: Inlibc
?MAKE: -pick add $@ %<
?S:d_ulimit:
?S: This variable conditionally defines HAS_ULIMIT if ulimit() is
?S: available to get the user limits.
?S:.
?C:HAS_ULIMIT (ULIMIT):
?C: This symbol, if defined, indicates that the ulimit system call is
?C: available to get the user limits.
?C:.
?H:#$d_ulimit HAS_ULIMIT /**/
?H:.
?LINT:set
d_ulimit
: see if ulimit exists
set ulimit d_ulimit
eval $inlibc

```

Found in path(s):

```

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/d_ulimit.U

```

No license file was found, but licenses were detected in source scan.

```

?RCS: $Id: d_endsent.U,v 3.0 1993/08/18 12:06:09 ram Exp $
?RCS:
?RCS: Copyright (c) 1991-1993, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 3.0.
?RCS:
?RCS: $Log: d_endsent.U,v $
?RCS: Revision 3.0 1993/08/18 12:06:09 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:d_endsent: Inlibc
?MAKE: -pick add $@ %<

```

?S:d_endsent:
?S: This variable conditionally defines HAS_ENDSERVENT if endservent() is
?S: available to close whatever was being used for service queries.
?S:.
?C:HAS_ENDSERVENT:
?C: This symbol, if defined, indicates that the endservent() routine is
?C: available to close whatever was being used for
service queries.
?C:.
?H:#\$d_endsent HAS_ENDSERVENT /**/
?H:.
?LINT:set d_endsent
: see if endservent exists
set endservent d_endsent
eval \$inlibc

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/modified/d_endsent.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_loconv.U 1 2006-08-24 12:32:52Z rmanfredi \$
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: Original Author: Andy Dougherty <doughera@lafcol.lafayette.edu>
?RCS:
?RCS: \$Log: d_loconv.U,v \$
?RCS: Revision 3.0.1.1 1994/10/29 16:14:11 ram
?RCS: patch36: created by ADO
?RCS:
?MAKE:d_loconv: Inlibc
?MAKE: -pick add \$@ %<
?S:d_loconv:
?S: This variable conditionally defines HAS_LOCALECONV if localeconv() is
?S: available for numeric and monetary formatting conventions.
?S:.
?C:HAS_LOCALECONV:
?C: This symbol, if defined, indicates that the localeconv
routine is
?C: available for numeric and monetary formatting conventions.
?C:.

?H:#\$d_loconv HAS_LOCALECONV /**/

?H:.

?LINT:set d_loconv

: see if localeconv exists

set localeconv d_loconv

eval \$inlibc

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/d_loconv.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: i_grp.U,v \$

?RCS: Revision 3.0 1993/08/18 12:08:20 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?MAKE:i_grp: Inhdr

?MAKE: -pick add \$@ %<

?S:i_grp:

?S: This variable conditionally defines the I_GRP symbol, and indicates

?S: whether a C program should include <grp.h>.

?S:.

?C:I_GRP:

?C: This symbol, if defined, indicates to the C program that it should

?C: include <grp.h>.

?C:.

?H:#\$i_grp I_GRP /**/

?H:.

?LINT:set i_grp

: see if this is an grp system

set grp.h i_grp

eval \$inhdr

Found

in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/i_grp.U

No license file was found, but licenses were detected in source scan.

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?MAKE:d_scalbn: Inlibc

?MAKE: -pick add \$@ %<

?S:d_scalbn:

?S: This variable conditionally defines the HAS_SCALBN symbol, which

?S: indicates to the C program that the scalbn() routine is available.

?S:.

?C:HAS_SCALBN:

?C: This symbol, if defined, indicates that the scalbn routine is

?C: available to multiply floating-point number by integral power

?C: of radix.

?C:.

?H:#\$d_scalbn HAS_SCALBN /**/

?H:.

?LINT:set d_scalbn

: see if scalbn exists

set scalbn d_scalbn

eval \$inlibc

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_scalbn.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: i_shadow.U,v \$

?RCS:

?RCS: Copyright (c) 1998 Jarkko Hietaniemi

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?MAKE:i_shadow: Inhdr Hasfield

?MAKE: -pick add \$@ %<

?S:i_shadow:

?S: This variable conditionally defines the I_SHADOW symbol, and indicates

?S: whether a C program should include <shadow.h>.

?S:.

?C:I_SHADOW:

?C: This symbol, if defined, indicates that <shadow.h> exists and

?C: should be included.

?C:.

?H:#\$i_shadow I_SHADOW /**/

?H:.

?LINT:set i_shadow

: see if this is a shadow.h system

set shadow.h i_shadow

eval \$inhdr

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/i_shadow.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: vendorhtml1.U,v 1.1 1999/07/08 18:32:57 doughera Exp doughera \$

?RCS:

?RCS: Copyright (c) 1999, Andy Dougherty

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 3.0.

?RCS:

?RCS: \$Log: vendorhtml1.U,v \$

?RCS: Revision 1.1 1999/07/08 18:32:57 doughera

?RCS: Initial revision

?RCS:

?MAKE:vendorhtml1 vendorhtml1exp installvendorhtml1: html1dir Getfile \

Oldconfig Setprefixvar Prefixit test vendorprefix prefix sed

?MAKE: -pick add \$@ %<

?Y:TOP

?S:vendorhtml1:

?S: This variable contains the name of the directory for html

?S: pages. It may have a ~ on the front.

?S: The standard distribution will put nothing in this directory.

?S: Vendors

who distribute perl may wish to place their own

?S: html pages in this directory with

?S: MakeMaker Makefile.PL INSTALLDIRS=vendor

?S: or equivalent. See INSTALL for details.

?S:.

?S:vendorhtml1exp:

?S: This variable is the ~name expanded version of vendorhtml1, so that you

?S: may use it directly in Makefiles or shell scripts.

?S:.

?D:installvendorhtml1="

?S:installvendorhtml1:

?S: This variable is really the same as vendorhtml1exp but may differ on

?S: those systems using AFS. For extra portability, only this variable

?S: should be used in makefiles.

?S:.

?LINT:change prefixvar

```

?LINT:set installvendorhtml1
: Set the vendorhtml1 variables
case "$vendorprefix" in
") vendorhtml1="
vendorhtml1exp="
;;
*) : determine where vendor-supplied html pages go.
: There is no standard location, so try to copy the previously-selected
: directory structure for the core html pages.
: XXX Better default suggestions would be welcome.
case "$vendorhtml1" in
") dflt=`echo "$html1dir"
| $sed "s#^$prefix#$vendorprefix#"` ;;
*) dflt=$vendorhtml1 ;;
esac
case "$dflt" in
"|' ') dflt=none ;;
esac
fn=dn+~
rp='Pathname for the vendor-supplied html pages?'
./getfile
vendorhtml1="$ans"
vendorhtml1exp="$ansexp"
;;
esac
: Use ' ' for none so value is preserved next time through Configure
$test X"$vendorhtml1" = "X" && vendorhtml1='
prefixvar=vendorhtml1
./installprefix

```

Found in path(s):

```

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/installdirs/vendorhtml1.U

```

No license file was found, but licenses were detected in source scan.

```

?RCS: $Id: i_niin.U 1 2006-08-24 12:32:52Z rmanfredi $

```

```

?RCS:

```

```

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

```

```

?RCS:

```

```

?RCS: You may redistribute only under the terms of the Artistic Licence,

```

```

?RCS: as specified in the README file that comes with the distribution.

```

```

?RCS: You may reuse parts of this distribution only within the terms of

```

```

?RCS: that same Artistic Licence; a copy of which may be found at the root

```

```

?RCS: of the source tree for dist 4.0.

```

```

?RCS:

```

```

?RCS: $Log: i_niin.U,v $

```

```

?RCS: Revision 3.0 1993/08/18 12:08:24 ram

```

```

?RCS: Baseline for dist 3.0 netwide release.

```

```

?RCS:
?X:
?X: This unit looks whether <netinet/in.h> is available or not
?X:
?MAKE:i_niin i_sysin: Inhdr
?MAKE: -pick add $@ %<
?S:i_niin:
?S: This variable conditionally defines I_NETINET_IN, which indicates
?S: to the C program that it should include <netinet/in.h>. Otherwise,
?S: you may try <sys/in.h>.
?S:.
?S:i_sysin:
?S: This variable conditionally
defines I_SYS_IN, which indicates
?S: to the C program that it should include <sys/in.h> instead of
?S: <netinet/in.h>.
?S:.
?C:I_NETINET_IN:
?C: This symbol, if defined, indicates to the C program that it should
?C: include <netinet/in.h>. Otherwise, you may try <sys/in.h>.
?C:.
?C:I_SYS_IN (I_SYSIN):
?C: This symbol, if defined, indicates to the C program that it should
?C: include <sys/in.h> instead of <netinet/in.h>.
?C:.
?H:#$i_niin I_NETINET_IN /**/
?H:#$i_sysin I_SYS_IN /**/
?H:.
?LINT:set i_niin i_sysin
: see if this is a netinet/in.h or sys/in.h system
set netinet/in.h i_niin sys/in.h i_sysin
eval $inhdr

```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/i_niin.U
```

No license file was found, but licenses were detected in source scan.

```

?RCS: $Id$
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:

```

```

?RCS: $Log: pidtype.U,v $
?RCS: Revision 3.0.1.1 1994/08/29 16:31:27 ram
?RCS: patch32: now uses new Typedef unit to compute type information
?RCS:
?RCS: Revision 3.0 1993/08/18 12:09:33 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:pidtype: Myread Typedef
?MAKE: -pick add $@ %<
?S:pidtype:
?S: This variable defines PIDTYPE to be something like pid_t, int,
?S: ushort, or whatever type is used to declare process ids in the kernel.
?S:.
?C:Pid_t (PIDTYPE):
?C: This symbol holds the type
    used to declare process ids in the kernel.
?C: It can be int, uint, pid_t, etc... It may be necessary to include
?C: <sys/types.h> to get any typedef'ed information.
?C:.
?H:#define Pid_t $pidtype /* PID type */
?H:.
: see what type pids are declared as in the kernel
set pid_t pidtype int stdio.h sys/types.h
eval $typedef
dflt="$pidtype"
echo " "
rp="What type are process ids on this system declared as?"
./myread
pidtype="$ans"

```

Found in path(s):

```

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/pidtype.U

```

No license file was found, but licenses were detected in source scan.

```

?RCS: $Id: d_socket.U,v 3.0.1.2 1997/02/28 15:46:00 ram Exp $
?RCS:
?RCS: Copyright (c) 1991-1993, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 3.0.
?RCS:
?RCS: $Log: d_socket.U,v $
?RCS: Revision 3.0.1.2 1997/02/28 15:46:00 ram
?RCS: patch61: replaced .a with $_a all over the place

```

?RCS:
?RCS: Revision 3.0.1.1 1994/01/24 14:08:04 ram
?RCS: patch16: can now safely declare private nm_extract in dependencies
?RCS:
?RCS: Revision 3.0 1993/08/18 12:07:26 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:d_socket d_oldsock d_sockpair socketlib sockethdr \
d_msg_trunc d_msg_dontroute d_msg_oob d_msg_peek
d_msg_proxy \
d_scm_rights d_sockaddr_sa_len d_sockaddr_in6 d_sin6_scope_id \
d_ip_mreq d_ip_mreq_source d_ipv6_mreq d_ipv6_mreq_source: \
contains echo n c ar nm nm_opt nm_extract Inlibc Csym_a \
Compile cat rm_try Setvar Hasfield sysroot
?MAKE: -pick add \$@ %<
?S:d_socket:
?S: This variable conditionally defines HAS_SOCKET, which indicates
?S: that the BSD socket interface is supported.
?S:.
?S:d_sockpair:
?S: This variable conditionally defines the HAS_SOCKETPAIR symbol, which
?S: indicates that the BSD socketpair() is supported.
?S:.
?S:d_oldsock:
?S: This variable conditionally defines the OLDSOCKET symbol, which
?S: indicates that the BSD socket interface is based on 4.1c and not 4.2.
?S:.
?S:d_msg_trunc:
?S: This variable conditionally defines the HAS_MSG_CTRUNC symbol,
?S: which indicates that the MSG_CTRUNC is available. #ifdef is
?S: not enough because it may be an enum, glibc has been known to do this.
?S:.
?S:d_msg_dontroute:
?S: This variable conditionally defines
the HAS_MSG_DONTRROUTE symbol,
?S: which indicates that the MSG_DONTRROUTE is available. #ifdef is
?S: not enough because it may be an enum, glibc has been known to do this.
?S:.
?S:d_msg_oob:
?S: This variable conditionally defines the HAS_MSG_OOB symbol,
?S: which indicates that the MSG_OOB is available. #ifdef is
?S: not enough because it may be an enum, glibc has been known to do this.
?S:.
?S:d_msg_peek:
?S: This variable conditionally defines the HAS_MSG_PEEK symbol,
?S: which indicates that the MSG_PEEK is available. #ifdef is
?S: not enough because it may be an enum, glibc has been known to do this.
?S:.

?S:d_msg_proxy:

?S: This variable conditionally defines the HAS_MSG_PROXY symbol,

?S: which indicates that the MSG_PROXY is available. #ifdef is

?S: not enough because it may be an enum, glibc has been known to do this.

?S:.

?S:d_scm_rights:

?S: This variable conditionally defines the HAS_SCM_RIGHTS symbol,

?S: which indicates that the SCM_RIGHTS is available. #ifdef is

?S: not

enough because it may be an enum, glibc has been known to do this.

?S:.

?S:d_sockaddr_sa_len:

?S: This variable conditionally defines the HAS_SOCKADDR_SA_LEN symbol,

?S: which indicates that a struct sockaddr structure has the sa_len

?S: member.

?S:.

?S:d_sockaddr_in6:

?S: This variable conditionally defines the HAS_SOCKADDR_IN6 symbol, which

?S: indicates the availability of a struct sockaddr_in6.

?S:.

?S:d_sin6_scope_id:

?S: This variable conditionally defines the HAS_SIN6_SCOPE_ID symbol, which

?S: indicates that a struct sockaddr_in6 structure has the sin6_scope_id

?S: member.

?S:.

?S:d_ip_mreq:

?S: This variable conditionally defines the HAS_IP_MREQ symbol, which

?S: indicates the availability of a struct ip_mreq.

?S:.

?S:d_ip_mreq_source:

?S: This variable conditionally defines the HAS_IP_MREQ_SOURCE symbol,

?S: which indicates the availability of a struct ip_mreq_source.

?S:.

?S:d_ipv6_mreq:

?S: This variable conditionally defines the HAS_IPV6_MREQ symbol, which

?S: indicates

the availability of a struct ipv6_mreq.

?S:.

?S:d_ipv6_mreq_source:

?S: This variable conditionally defines the HAS_IPV6_MREQ_SOURCE symbol,

?S: which indicates the availability of a struct ipv6_mreq_source.

?S:.

?S:socketlib:

?S: This variable has the names of any libraries needed for socket support.

?S:.

?S:sockethdr:

?S: This variable has any cpp '-I' flags needed for socket support.

?S:.

?C:HAS_SOCKET (SOCKET):

?C: This symbol, if defined, indicates that the BSD socket interface is

?C: supported.

?C:.

?C:HAS_SOCKETPAIR (SOCKETPAIR):

?C: This symbol, if defined, indicates that the BSD socketpair() call is

?C: supported.

?C:.

?C:USE_OLD_SOCKET (OLDSOCKET):

?C: This symbol, if defined, indicates that the 4.1c BSD socket interface

?C: is supported instead of the 4.2/4.3 BSD socket interface. For instance,

?C: there is no setsockopt() call.

?C:.

?C:HAS_MSG_TRUNC:

?C: This symbol, if defined, indicates that the MSG_TRUNC is supported.

?C: Checking just with #ifdef might not be enough

because this symbol

?C: has been known to be an enum.

?C:.

?C:HAS_MSG_DONTROUTE:

?C: This symbol, if defined, indicates that the MSG_DONTROUTE is supported.

?C: Checking just with #ifdef might not be enough because this symbol

?C: has been known to be an enum.

?C:.

?C:HAS_MSG_OOB:

?C: This symbol, if defined, indicates that the MSG_OOB is supported.

?C: Checking just with #ifdef might not be enough because this symbol

?C: has been known to be an enum.

?C:.

?C:HAS_MSG_PEEK:

?C: This symbol, if defined, indicates that the MSG_PEEK is supported.

?C: Checking just with #ifdef might not be enough because this symbol

?C: has been known to be an enum.

?C:.

?C:HAS_MSG_PROXY:

?C: This symbol, if defined, indicates that the MSG_PROXY is supported.

?C: Checking just with #ifdef might not be enough because this symbol

?C: has been known to be an enum.

?C:.

?C:HAS_SCM_RIGHTS:

?C: This symbol, if defined, indicates that the SCM_RIGHTS is supported.

?C: Checking just with #ifdef might not be enough

because this symbol

?C: has been known to be an enum.

?C:.

?C:HAS_SOCKADDR_SA_LEN:

?C: This symbol, if defined, indicates that the struct sockaddr

?C: structure has a member called sa_len, indicating the length of

?C: the structure.

?C:.

?C:HAS_SOCKETADDR_IN6:

?C: This symbol, if defined, indicates the availability of

?C: struct sockaddr_in6;

?C:.

?C:HAS_SIN6_SCOPE_ID:

?C: This symbol, if defined, indicates that the struct sockaddr_in6

?C: structure has a member called sin6_scope_id.

?C:.

?C:HAS_IP_MREQ:

?C: This symbol, if defined, indicates the availability of

?C: struct ip_mreq;

?C:.

?C:HAS_IP_MREQ_SOURCE:

?C: This symbol, if defined, indicates the availability of

?C: struct ip_mreq_source;

?C:.

?C:HAS_IPV6_MREQ:

?C: This symbol, if defined, indicates the availability of

?C: struct ipv6_mreq;

?C:.

?C:HAS_IPV6_MREQ_SOURCE:

?C: This symbol, if defined, indicates the availability of

?C: struct ipv6_mreq_source;

?C:.

?H:#\$d_socket HAS_SOCKET /**/

?H:#\$d_sockpair HAS_SOCKETPAIR /**/

?H:#\$d_sockaddr_sa_len HAS_SOCKETADDR_SA_LEN /**/

?H:#\$d_oldsock USE_OLD_SOCKET /**/

?H:#\$d_msg_ctrunc HAS_MSG_CTRUNC /**/

?H:#\$d_msg_dontroute HAS_MSG_DONTROUTE /**/

?H:#\$d_msg_oob HAS_MSG_OOB /**/

?H:#\$d_msg_peek HAS_MSG_PEEK /**/

?H:#\$d_msg_proxy HAS_MSG_PROXY /**/

?H:#\$d_scm_rights HAS_SCM_RIGHTS /**/

?H:#\$d_sockaddr_in6 HAS_SOCKETADDR_IN6 /**/

?H:#\$d_sin6_scope_id HAS_SIN6_SCOPE_ID /**/

?H:#\$d_ip_mreq HAS_IP_MREQ /**/

?H:#\$d_ip_mreq_source HAS_IP_MREQ_SOURCE /**/

?H:#\$d_ipv6_mreq HAS_IPV6_MREQ /**/

?H:#\$d_ipv6_mreq_source HAS_IPV6_MREQ_SOURCE /**/

?H:.

?T:val

net ENUM enum

?LINT:set d_sockpair d_sockaddr_sa_len

?LINT:set d_msg_ctrunc d_msg_dontroute d_msg_oob d_msg_peek d_msg_proxy

?LINT:set d_scm_rights d_sockaddr_in6 d_sin6_scope_id d_ip_mreq

```

?LINT:set d_ip_mreq_source d_ipv6_mreq d_ipv6_mreq_source
: see whether socket exists
socketlib=""
sockethdr=""
echo " "
$echo $n "Hmm... $c" >&4
if set socket val -f d_socket; eval $csym; $val; then
    echo "Looks like you have Berkeley networking
support." >&4
    d_socket="$define"
?X: now check for advanced features
    if set setsockopt val -f; eval $csym; $val; then
d_oldsock="$undef"
    else
echo "...but it uses the old BSD 4.1c interface, rather than 4.2." >&4
    d_oldsock="$define"
    fi
else
?X: HP-UX, for one, puts all the socket stuff in socklib.o. Note that if we
?X: come here on HP-UX, then we must have used nm to get symbols, or we really
?X: don't have sockets anyway...
    if $contains socklib libc.list >/dev/null 2>&1; then
echo "Looks like you have Berkeley networking support." >&4
    d_socket="$define"
: we will have to assume that it supports the 4.2 BSD interface
d_oldsock="$undef"
    else
echo "You don't have Berkeley networking in libc$_a..." >&4
?X: look for optional networking libraries
if test "X$d_socket" = "X$define"; then
    echo "...but you seem to believe that you have sockets." >&4
else
    for net in net socket
    do
if test -f $sysroot/usr/lib/lib$net$_a; then
?X: space between two
'(' needed for ksh
    ( ($nm $nm_opt $sysroot/usr/lib/lib$net$_a | eval $nm_extract) || \
    $ar t $sysroot/usr/lib/lib$net$_a 2>/dev/null >> libc.list
    if $contains socket libc.list >/dev/null 2>&1; then
d_socket="$define"
socketlib="-l$net"
case "$net" in
net)
    echo "...but the Wollongong group seems to have hacked it in." >&4
    sockethdr="-I$sysroot/usr/netinclude"
    ;;
esac

```

```

    echo "Found Berkeley sockets interface in lib$net." >&4
?X: now check for advanced features
    if $contains setsockopt libc.list >/dev/null 2>&1; then
        d_oldsock="$undef"
    else
        echo "...using the old BSD 4.1c interface, rather than 4.2." >&4
        d_oldsock="$define"
    fi
break
    fi
fi
done
    if test "X$d_socket" != "X$define"; then
        echo "or anywhere else I see." >&4
        d_socket="$undef"
        d_oldsock="$undef"
    fi
fi
fi
fi

@if HAS_SOCKETPAIR || d_socketpair
: see if socketpair exists
set socketpair d_socketpair
eval
$inlibc

@end

echo " "
?X: ...
echo "Checking the availability sa_len in the sock struct ..." >&4
$cat >try.c <<EOF
#include <sys/types.h>
#include <sys/socket.h>
int main() {
struct sockaddr sa;
return (sa.sa_len);
}
EOF
val="$undef"
set try; if eval $compile; then
    val="$define"
fi
set d_sockaddr_sa_len; eval $setvar
$rm_try

echo " "

```

```

?X: ...
echo "Checking the availability struct sockaddr_in6 ..." >&4
$cat >try.c <<EOF
#include <sys/types.h>
#include <sys/socket.h>
#include <netinet/in.h>
int main() {
struct sockaddr_in6 sin6;
return (sin6.sin6_family);
}
EOF
val="$undef"
set try; if eval $compile; then
    val="$define"
fi
set d_sockaddr_in6; eval $setvar
$rm_try

echo " "
?X: ...
echo "Checking the availability sin6_scope_id in struct sockaddr_in6 ..." >&4
$cat >try.c <<EOF
#include <sys/types.h>
#include <sys/socket.h>
#include <netinet/in.h>
int main() {
struct sockaddr_in6 sin6;
return (sin6.sin6_scope_id);
}
EOF
val="$undef"
set try; if eval $compile; then
    val="$define"
fi
set
d_sin6_scope_id; eval $setvar
$rm_try

echo " "
?X: ...
echo "Checking the availability struct ip_mreq ..." >&4
$cat >try.c <<EOF
#include <sys/types.h>
#include <sys/socket.h>
#include <netinet/in.h>
int main() {
struct ip_mreq mreq;
return (mreq.imr_multiaddr.s_addr);

```

```

}
EOF
val="$undef"
set try; if eval $compile; then
    val="$define"
fi
set d_ip_mreq; eval $setvar
$rm_try

echo " "
?X: ...
echo "Checking the availability struct ip_mreq_source ..." >&4
$cat >try.c <<EOF
#include <sys/types.h>
#include <sys/socket.h>
#include <netinet/in.h>
int main() {
    struct ip_mreq_source mreq;
    return (mreq.imr_multiaddr.s_addr);
}
EOF
val="$undef"
set try; if eval $compile; then
    val="$define"
fi
set d_ip_mreq_source; eval $setvar
$rm_try

echo " "
?X: ...
echo "Checking the availability struct ipv6_mreq ..." >&4
$cat >try.c <<EOF
#include <sys/types.h>
#include <sys/socket.h>
#include <netinet/in.h>
int main() {
    struct ipv6_mreq mreq;
    return (mreq.ipv6mr_interface);
}
EOF
val="$undef"
set
try; if eval $compile; then
    val="$define"
fi
set d_ipv6_mreq; eval $setvar
$rm_try

```

```

echo " "
?X: ...
echo "Checking the availability struct ipv6_mreq_source ..." >&4
$cat >try.c <<EOF
#include <sys/types.h>
#include <sys/socket.h>
#include <netinet/in.h>
int main() {
struct ipv6_mreq_source mreq;
return (mreq.imr_multiaddr.s_addr);
}
EOF
val="$undef"
set try; if eval $compile; then
    val="$define"
fi
set d_ipv6_mreq_source; eval $setvar
$rm_try

echo " "
?X: these constants are known to be troublesomely defined as enums
?X: so that ifdef will not work for detecting their presence.
echo "Checking the availability of certain socket constants..." >&4
for ENUM in MSG_CTRUNC MSG_DONTROUTE MSG_OOB MSG_PEEK MSG_PROXY SCM_RIGHTS; do
    enum=`$echo $ENUM|./tr '[A-Z]' '[a-z]`
    $cat >try.c <<EOF
#include <sys/types.h>
#include <sys/socket.h>
int main() {
    int i = $ENUM;
}
EOF
    val="$undef"
    set try; if eval $compile; then
        val="$define"
    fi
    set d_${enum};
    eval $setvar
    $rm_try
done

```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/modified/d_socket.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: i_features.U,v $
```

```
?RCS:
```

?RCS: Copyright (c) 2001 Jarkko Hietaniemi
?RCS:
?RCS: You may distribute under the terms of either the GNU General Public
?RCS: License or the Artistic License, as specified in the README file.
?RCS:
?MAKE:i_features: Inhdr Hasfield
?MAKE: -pick add \$@ %<
?S:i_features:
?S: This variable conditionally defines the I_FEATURES symbol,
?S: and indicates whether a C program should include <features.h>.
?S:.
?C:I_FEATURES:
?C: This symbol, if defined, indicates that <features.h> exists and
?C: should be included.
?C:.
?H:#\$i_features I_FEATURES /**/
?H:.
?LINT:set i_features
: see if this is a features.h system
set features.h i_features
eval \$inhdr

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/i_features.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_getservbyname_r.U,v 0RCS:
?RCS: Copyright (c) 2002,2003 Jarkko Hietaniemi
?RCS:
?RCS: You may distribute under the terms of either the GNU General Public
?RCS: License or the Artistic License, as specified in the README file.
?RCS:
?RCS: Generated by the reentr.pl from the Perl 5.8 distribution.
?RCS:
?MAKE:d_getservbyname_r getservbyname_r_proto: Inlibc Protochk Hasproto \
i_systypes usethreads i_netdb extern_C
?MAKE: -pick add \$@ %<
?S:d_getservbyname_r:
?S: This variable conditionally defines the HAS_GETSERVBYNAME_R symbol,
?S: which indicates to the C program that the getservbyname_r()
?S: routine is available.
?S:.
?S:getservbyname_r_proto:
?S: This variable encodes the prototype of getservbyname_r.
?S: It is zero if d_getservbyname_r is undef, and one of the
?S: REENTRANT_PROTO_T_ABC macros of reentr.h if d_getservbyname_r
?S: is defined.

```

?S:.
?C:HAS_GETSERVBYNAME_R:
?C: This symbol, if defined, indicates
    that the getservbyname_r routine
?C: is available to getservbyname re-entrantly.
?C:.
?C:GETSERVBYNAME_R_PROTO:
?C: This symbol encodes the prototype of getservbyname_r.
?C: It is zero if d_getservbyname_r is undef, and one of the
?C: REENTRANT_PROTO_T_ABC macros of reentr.h if d_getservbyname_r
?C: is defined.
?C:.
?H:#$d_getservbyname_r HAS_GETSERVBYNAME_R  /**/
?H:#define GETSERVBYNAME_R_PROTO $getservbyname_r_proto  /**/
?H:.
?T:try hdrs d_getservbyname_r_proto
: see if getservbyname_r exists
set getservbyname_r d_getservbyname_r
eval $inlibc
case "$d_getservbyname_r" in
"$define")
hdrs="$i_systypes sys/types.h define stdio.h $i_netdb netdb.h"
case "$d_getservbyname_r_proto:$usetthreads" in
":define") d_getservbyname_r_proto=define
set d_getservbyname_r_proto getservbyname_r $hdrs
eval $hasproto ;;
*) ;;
esac
case "$d_getservbyname_r_proto" in
define)
case "$getservbyname_r_proto" in
"|0) try='int getservbyname_r(const char*, const char*, struct servent*,
char*, size_t, struct servent**);'
./protochk "$extern_C $try" $hdrs && getservbyname_r_proto=I_CCSEBWR ;;
esac
case "$getservbyname_r_proto" in
"|0) try='struct servent* getservbyname_r(const char*, const char*, struct servent*, char*, int);'
./protochk "$extern_C $try" $hdrs && getservbyname_r_proto=S_CCSEBI ;;
esac
case "$getservbyname_r_proto" in
"|0) try='int getservbyname_r(const char*, const char*, struct servent*, struct servent_data*);'
./protochk "$extern_C $try" $hdrs && getservbyname_r_proto=I_CCSD ;;
esac
case "$getservbyname_r_proto" in
"|0) d_getservbyname_r=undef
getservbyname_r_proto=0
echo "Disabling getservbyname_r, cannot determine prototype." >&4 ;;
* ) case "$getservbyname_r_proto" in

```

```

REENTRANT_PROTO*) ;;
*) getservbyname_r_proto="REENTRANT_PROTO_$getservbyname_r_proto" ;;
esac
echo "Prototype: $try" ;;
esac
;;
*) case "$susetthreads" in
define) echo "getservbyname_r has no prototype, not using it." >&4 ;;
esac
d_getservbyname_r=undef
getservbyname_r_proto=0
;;
esac
;;
*) getservbyname_r_proto=0
;;
esac

```

Found

in path(s):

```

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/threads/d_getservbyname_r.U

```

No license file was found, but licenses were detected in source scan.

?RCS: Copyright (c) 2016 Dagfinn Ilmari Mannsker & H.Merijn Brand

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?X:

?X: This unit produces a variable that is intended to be eval'ed in

?X: order to define/undefine a symbol. A consistency check is made

?X: regarding any previous value and a warning is issued if there

?X: is any discrepancy.

?X:

?X: To use it, say:

```

?X: set d_siginfo_si_errno siginfo_t int si_errno $d_sigaction signal.h

```

```

?X: eval $hasfield_t;

```

?X:

```

?MAKE:Hasfield_t: test Compile rm_try Setvar

```

```

?MAKE: -pick add $@ %<

```

```

?LINT:define hasfield_t

```

```

?S:hasfield_t:

```

?S: Internal macro for Configure

?S:.

```

?V:hasfield_t:

```

?T:varname struct type field

: Define hasfield_t macro for Configure internal use

```

hasfield_t='varname=$1; struct=$2; type=$3; field=$4; shift; shift; shift; shift;
while $test $# -ge 2; do
    case
"$1" in
$define) echo "#include <$2>";;
    esac ;
    shift 2;
done > try.c;
echo "int main () { $struct foo; $type bar = foo.$field; }" >> try.c;
set try;
if eval $compile; then
    val="$define";
else
    val="$undef";
fi;
set $varname;
eval $setvar;
$rm_try'

```

Found in path(s):

```

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/perl/Hasfield_t.U

```

No license file was found, but licenses were detected in source scan.

```

?RCS: $Id: d_strdup.U 1 2006-08-24 12:32:52Z rmanfredi $
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: $Log: d_strdup.U,v $
?RCS: Revision 3.0.1.1 1993/12/15 08:21:41 ram
?RCS: patch15: created
?RCS:
?MAKE:d_strdup: Inlibc
?MAKE: -pick add $@ %<
?S:d_strdup:
?S: This variable conditionally defines HAS_STRDUP if strdup() is
?S: available to duplicate strings in memory.
?S:.
?C:HAS_STRDUP:
?C: This symbol, if defined, indicates that the strdup routine is
?C: available to duplicate strings in memory. Otherwise, roll up
?C: your own...

```

?C:.
?H:#\$d_strdup HAS_STRDUP /**/
?H:.
?LINT:set
d_strdup
: see if strdup exists
set strdup d_strdup
eval \$inlibc

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/d_strdup.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: i_dbm.U 1 2006-08-24 12:32:52Z rmanfredi \$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic Licence,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic Licence; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: i_dbm.U,v \$

?RCS: Revision 3.0.1.2 1997/02/28 15:48:20 ram

?RCS: patch61: added I_RPCSVCS_DBM check

?RCS:

?RCS: Revision 3.0.1.1 1995/05/12 12:16:05 ram

?RCS: patch54: made more robust by checking both header and lib (ADO)

?RCS:

?RCS: Revision 3.0 1993/08/18 12:08:15 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?MAKE:i_dbm i_rpcsvcdbm: Inhdr Inlibc Setvar

?MAKE: -pick add \$@ %<

?S:i_dbm (d_odbm):

?S: This variable conditionally defines

the I_DBM symbol, which

?S: indicates to the C program that <dbm.h> exists and should

?S: be included.

?S:.

?S:i_rpcsvcdbm:

?S: This variable conditionally defines the I_RPCSVCS_DBM symbol, which

?S: indicates to the C program that <rpcsvc/dbm.h> exists and should

?S: be included. Some System V systems might need this instead of <dbm.h>.

?S:.

?C:I_DBM (HAS_ODBM ODBM):

?C: This symbol, if defined, indicates that <dbm.h> exists and should

?C: be included.

?C:.

?C:I_RPCSVCSVC_DBM:

?C: This symbol, if defined, indicates that <rpcsvc/dbm.h> exists and

?C: should be included.

?C:.

?H:#\$i_dbm I_DBM /**/

?H:#\$i_rpcsvcdbm I_RPCSVCSVC_DBM /**/

?H:.

?T:d_dbmclose

?LINT:set i_dbm i_rpcsvcdbm

: see if dbm.h is available

?X: We might just have the header, not the library.

?X: We look for dbmclose() rather than dbmopen() because

?X: some versions of SCO Unix have -ldb, but are missing dbmclose(). -- ADO

?X: Some System V systems have <rpcsvc/dbm.h> instead of <dbm.h>.

: see if dbmclose exists

set dbmclose

d_dbmclose

eval \$inlibc

case "\$d_dbmclose" in

\$define)

set dbm.h i_dbm

eval \$inhdr

case "\$i_dbm" in

\$define)

val="\$sundef"

set i_rpcsvcdbm

eval \$setvar

::

*) set rpcsvc/dbm.h i_rpcsvcdbm

eval \$inhdr

::

esac

::

*) echo "We won't be including <dbm.h>"

val="\$sundef"

set i_dbm

eval \$setvar

val="\$sundef"

set i_rpcsvcdbm

eval \$setvar

::

esac

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-  
debian-perl-5.26.1/dist/U/i_dbm.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: Setprefixvar.U,v 3.0 2006/04/01 17:25:29 hmbrand $
```

```
?RCS:
```

```
?RCS: Copyright (c) 2006-2006, H.Merijn Brand & Nicholas Clark
```

```
?RCS:
```

```
?RCS: This file is included with or a derivative work of a file included
```

```
?RCS: with the metaconfig program of Raphael Manfredi's "dist" distribution.
```

```
?RCS: In accordance with clause 7 of dist's modified Artistic License:
```

```
?RCS:
```

```
?RCS: You may distribute under the terms of either the GNU General Public
```

```
?RCS: License or the Artistic License, as specified in the README file.
```

```
?RCS:
```

```
?X:
```

```
?X: This unit sets up the scripts installprefix and setprefixvar, so code
```

```
?X: in other parts can be more simple and maintainable
```

```
?X:
```

```
?MAKE:Setprefixvar: Myread Getfile startsh eunicefix test \  
prefix prefixexp installprefix installprefixexp
```

```
?MAKE: -pick add $@ %<
```

```
?LINT:extern prefixvar
```

```
?X: metalint still sees "\${prefixvar}exp`" as variable :(
```

```
?T:prefixvarexp
```

```
?F:./setprefixvar
```

```
?F:./installprefix
```

```
: Perform
```

```
the prefixexp/installprefixexp correction if necessary
```

```
cat <<EOS >installprefix
```

```
$startsh
```

```
EOS
```

```
cat <<'EOOSC' >>installprefix
```

```
: Change installation prefix, if necessary.
```

```
if $test X"$prefix" != X"$installprefix"; then
```

```
eval "install${prefixvar}=\`echo \${${prefixvar}exp | sed \"s#^\${prefixexp#\$installprefixexp#\"`"
```

```
else
```

```
eval "install${prefixvar}=\"\${${prefixvar}exp\""
```

```
fi
```

```
EOOSC
```

```
chmod +x installprefix
```

```
$eunicefix installprefix
```

```
: Perform
```

```
the prefixexp/installprefixexp correction if necessary
```

```
cat <<EOS >setprefixvar
```

```
$startsh
```

```
EOS
```

```
: Perform
```

```
the prefixexp/installprefixexp correction if necessary.
```

```
cat <<EOS >setprefixvar
```

```
$startsh
```

```
EOS
```

```
cat <<'EOSC' >>setprefixvar
eval "${prefixvar}=\\"$ans\""
eval "${prefixvar}exp=\\"$ansexp\""
./installprefix
EOSC
chmod +x setprefixvar
$unicefix setprefixvar
```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/installdirs/Setprefixvar.U
```

No license file was found, but licenses were detected in source scan.

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?MAKE:d_acosh: Inlibc

?MAKE: -pick add \$@ %<

?S:d_acosh:

?S: This variable conditionally defines the HAS_ACOSH symbol, which

?S: indicates to the C program that the acosh() routine is available.

?S:.

?C:HAS_ACOSH:

?C: This symbol, if defined, indicates that the acosh routine is

?C: available to do the inverse hyperbolic cosine function.

?C:.

?H:#\$d_acosh HAS_ACOSH /**/

?H:.

?LINT:set d_acosh

: see if acosh exists

set acosh d_acosh

eval \$inlibc

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/perl/d_acosh.U
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_mkstemp.U,v 3.0.1.1 1994/08/29 16:11:57 ram Exp \$

?RCS:

?RCS: Copyright (c) 1998 Andy Dougherty

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?RCS: Original Author: Andy Dougherty <doughera@lafcol.lafayette.edu>

?RCS:

?RCS: \$Log: d_mkstemp.U,v \$

?RCS:
?MAKE:d_mkstemp: Inlibc
?MAKE: -pick add \$@ %<
?S:d_mkstemp:
?S: This variable conditionally defines the HAS_MKSTEMP symbol, which
?S: indicates to the C program that the mkstemp() routine is available
?S: to exclusively create and open a uniquely named temporary file.
?S:.
?C:HAS_MKSTEMP :
?C: This symbol, if defined, indicates that the mkstemp routine is
?C: available to exclusively create and open a uniquely named
?C: temporary file.
?C:.
?H:#\$d_mkstemp HAS_MKSTEMP /**/
?H:.
?LINT:set d_mkstemp
: see if mkstemp exists
set mkstemp d_mkstemp
eval
\$inlibc

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/modified/d_mkstemp.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_tcgetpgrp.U 1 2006-08-24 12:32:52Z rmanfredi \$
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: Original Author: Andy Dougherty <doughera@lafcol.lafayette.edu>
?RCS:
?RCS: \$Log: d_tcgetpgrp.U,v \$
?RCS: Revision 3.0.1.1 1994/08/29 16:12:08 ram
?RCS: patch32: created by ADO
?RCS:
?MAKE:d_tcgetpgrp: Inlibc
?MAKE: -pick add \$@ %<
?S:d_tcgetpgrp:
?S: This variable conditionally defines the HAS_TCGETPGRP symbol, which
?S: indicates to the C program that the tcgetpgrp() routine is available.
?S: to get foreground process group ID.

```

?S:.
?C:HAS_TCGETPGRP
:
?C: This symbol, if defined, indicates that the tcgetpgrp routine is
?C: available to get foreground process group ID.
?C:.
?H:#$d_tcgetpgrp HAS_TCGETPGRP /**/
?H:.
?LINT:set d_tcgetpgrp
: see if tcgetpgrp exists
set tcgetpgrp d_tcgetpgrp
eval $inlibc

```

Found in path(s):

```

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/d_tcgetpgrp.U

```

No license file was found, but licenses were detected in source scan.

```

?RCS: $Id$
?RCS:
?RCS: Copyright (c) 1998 Andy Dougherty
?RCS:
?RCS: You may distribute under the terms of either the GNU General Public
?RCS: License or the Artistic License, as specified in the README file.
?RCS:
?MAKE:uselongdouble: Myread Oldconfig Setvar cat test usemorebits
?MAKE: -pick add $@ %<
?Y:TOP
?S:uselongdouble:
?S: This variable conditionally defines the USE_LONG_DOUBLE symbol,
?S: and indicates that long doubles should be used when available.
?S:.
?C:USE_LONG_DOUBLE:
?C: This symbol, if defined, indicates that long doubles should
?C: be used when available.
?C:.
?H:?%<:#ifndef USE_LONG_DOUBLE
?H:?%<:#$uselongdouble USE_LONG_DOUBLE /**/
?H:?%<:#endif
?H:.
?LINT:extern ccflags
?LINT:use usemorebits
?F:!uselongdouble.cbu
: Check for uselongdouble support
case "$ccflags" in
*-DUSE_LONG_DOUBLE*|*-DUSE_MORE_BITS*) uselongdouble="$define" ;;
esac

```

```

case "$uselongdouble" in
$define|true|[yY]*) dflt='y';
*)
dflt='n';
esac
cat <<EOM

```

Perl can be built to take advantage of long doubles which (if available) may give more accuracy and range for floating point numbers.

If this doesn't make any sense to you, just accept the default '\$dflt'.

EOM

```

rp='Try to use long doubles if available?'
. ./myread
case "$ans" in
y|Y) val="$define" ;;
*) val="$undef" ;;
esac
set uselongdouble
eval $setvar

```

```

case "$uselongdouble" in
true|[yY]*) uselongdouble="$define" ;;
esac

```

```

: Look for a hint-file generated 'call-back-unit'. If the
: user has specified that long doubles should be used,
: we may need to set or change some other defaults.
if $test -f uselongdouble.cbu; then
echo "Your platform has some specific hints regarding long doubles, using them..."
. ./uselongdouble.cbu
else
case "$uselongdouble" in
$define)
$cat <<EOM
(Your platform does not have any specific hints for long doubles.)
EOM
;;
esac
fi

```

Found in path(s):

```

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/uselongdbl.U

```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: i_locale.U 1 2006-08-24 12:32:52Z rmanfredi \$

?RCS:

?RCS: Copyright (c) 1996, Andy Dougherty
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: \$Log: i_locale.U,v \$
?RCS: Revision 3.0.1.1 1997/02/28 15:48:23 ram
?RCS: patch61: created
?RCS:
?MAKE:i_locale: Inhdr
?MAKE: -pick add \$@ %<
?S:i_locale:
?S: This variable conditionally defines the I_LOCALE symbol,
?S: and indicates whether a C program should include <locale.h>.
?S:.
?C:I_LOCALE:
?C: This symbol, if defined, indicates to the C program that it should
?C: include <locale.h>.
?C:.
?H:#\$i_locale I_LOCALE /**/
?H:.
?LINT:set
i_locale
: see if locale.h is available
set locale.h i_locale
eval \$inhdr

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/i_locale.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: \$Log: package.U,v \$
?RCS: Revision 3.0.1.3 1994/10/29 16:27:21 ram

?RCS: patch36: beware of non-ascii character sets when translating case

?RCS:

?RCS: Revision 3.0.1.2 1993/11/10 17:37:02 ram

?RCS: patch14: skip definition of spackage if not otherwise used

?RCS:

?RCS: Revision 3.0.1.1 1993/09/13 16:11:10 ram

?RCS: patch10: added package, suitable for starting sentences

?RCS:

?RCS: Revision 3.0 1993/08/18 12:09:28 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?MAKE:package spackage:

Nothing

?MAKE: -pick wipe \$@ %<

?S:package:

?S: This variable contains the name of the package being constructed.

?S: It is primarily intended for the use of later Configure units.

?S:.

?S:spackage:

?S: This variable contains the name of the package being constructed,

?S: with the first letter uppercased, i.e. suitable for starting

?S: sentences.

?S:.

?C:PACKAGE:

?C: This variable contains the name of the package being built.

?C:.

?H:#define PACKAGE "\$package"

?H:.

?T:first last

: set package name

package='<PACKAGENAME>'

@if spackage

first=`echo \$package | sed -e 's/^(.).*\1/'`

last=`echo \$package | sed -e 's/^(.*)\1/'`

?X:

?X: So early in the Configure script, we don't have ./tr set up and can't

?X: include Tr in our dependency or that would create a cycle. Therefore,

?X: we have to somehow duplicate the work done in Tr. That's life.

?X:

case "" echo AbyZ | tr '[:lower:]' '[:upper:]' 2>/dev/null" in

ABYZ) spackage=`echo \$first | tr '[:lower:]' '[:upper:]'`\$last;;

*) spackage=`echo

\$first | tr '[a-z]' '[A-Z]'`\$last;;

esac

@end

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-

debian-perl-5.26.1/dist/U/package.U

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: d_sjis2jis.U 1 2006-08-24 12:32:52Z rmanfredi $
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: $Log: d_sjis2jis.U,v $
?RCS: Revision 3.0 1993/08/18 12:07:25 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:d_sjis2jis: Inlibc
?MAKE: -pick add $@ %<
?S:d_sjis2jis:
?S: This variable conditionally defines the HAS_SJIS2JIS symbol, which
?S: indicates to the C program that the sjis2jis() routine is available
?S: to convert SJIS to JIS.
?S:.
?C:HAS_SJIS2JIS:
?C: This symbol, if defined, indicates that the sjis2jis routine is
?C: available
?C: to convert SJIS to JIS.
?C:.
?H:#$d_sjis2jis HAS_SJIS2JIS /**/
?H:.
?LINT:set d_sjis2jis
: see if sjis2jis exists
set sjis2jis d_sjis2jis
eval $inlibc
```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/d_sjis2jis.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: d_setsent.U,v 3.0 1993/08/18 12:06:09 ram Exp $
?RCS:
?RCS: Copyright (c) 1991-1993, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
```

?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 3.0.
?RCS:
?RCS: \$Log: d_setsent.U,v \$
?RCS: Revision 3.0 1993/08/18 12:06:09 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:d_setsent: Inlibc
?MAKE: -pick add \$@ %<
?S:d_setsent:
?S: This variable conditionally defines HAS_SETSERVENT if setservernt() is
?S: available.
?S:.
?C:HAS_SETSERVENT:
?C: This symbol, if defined, indicates that the setservernt() routine is
?C: available.
?C:.
?H:#\$d_setsent HAS_SETSERVENT /**/
?H:.
?LINT:set d_setsent
: see if setservernt exists
set
setservernt d_setsent
eval \$inlibc

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/modified/d_setsent.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$
?RCS:
?RCS: Copyright (c) 1999, Jarkko Hietaniemi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 3.0.
?RCS:
?MAKE:d_clock_getres: Inlibc
?MAKE: -pick add \$@ %<
?S:d_clock_getres:
?S: This variable conditionally defines HAS_CLOCK_GETRES
?S: if clock_getres() is available to get the resolution of a POSIX clock.
?S:.
?C:HAS_CLOCK_GETRES:
?C: This symbol, if defined, indicates that the clock_getres

?C: system call is available to get the resolution of a POSIX clock.

?C:.

?H:#\$d_clock_getres HAS_CLOCK_GETRES /**/

?H:.

?LINT:set d_clock_getres

: see if clock_getres exists

set clock_getres d_clock_getres

eval \$inlibc

Found in path(s):

*

/opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_clock_getres.U

No license file was found, but licenses were detected in source scan.

?RCS: Copyright (c) 1996, Chip Salzenberg

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?MAKE:bincompat5005 d_bincompat5005: Oldconfig Myread Setvar cat \
usethreads usemultiplicity

?MAKE: -pick add \$@ %<

?Y:TOP

?S:bincompat5005:

?S: This variable contains y if this version of Perl should be

?S: binary-compatible with Perl 5.005.

?S:.

?S:d_bincompat5005:

?S: This variable conditionally defines BINCOMPAT5005 so that embed.h

?S: can take special action if this version of Perl should be

?S: binary-compatible with Perl 5.005. This is impossible for builds

?S: that use features like threads and multiplicity it is always \$undef

?S: for those versions.

?S:.

?C:PERL_BINCOMPAT_5005:

?C: This symbol, if defined, indicates that this version of Perl should be

?C: binary-compatible with Perl 5.005. This is impossible
for builds

?C: that use features like threads and multiplicity it is always \$undef

?C: for those versions.

?C:.

?H:#\$d_bincompat5005 PERL_BINCOMPAT_5005 /**/

?H:.

: Binary compatibility with 5.005 is not possible for builds

: with advanced features

case "\$usethreads\$usemultiplicity" in

define)

```
bincompat5005="$undef"  
d_bincompat5005="$undef"  
;;  
) $cat <<EOM
```

This version of Perl can be compiled for binary compatibility with 5.005.
If you decide to do so, you will be able to continue using most of the
extensions that were compiled for Perl 5.005.

```
EOM  
case "$bincompat5005$d_bincompat5005" in  
*" $undef"*) dflt=n ;;  
*) dflt=y ;;  
esac  
rp='Binary compatibility with Perl 5.005?'  
. ./myread  
case "$ans" in  
y*) val="$define" ;;  
*) val="$undef" ;;  
esac  
set d_bincompat5005  
eval $setvar  
case "$d_bincompat5005" in  
"$define")  
    bincompat5005="$define"  
    ;;  
*) bincompat5005="$undef"  
    d_bincompat5005="$undef"  
    ;;  
esac  
;;  
esac
```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-  
debian-perl-5.26.1/U/perl/bincompat5005.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: orderlib.U,v 3.0.1.4 1997/02/28 16:18:18 ram Exp $
```

```
?RCS:
```

```
?RCS: Copyright (c) 1991-1993, Raphael Manfredi
```

```
?RCS:
```

```
?RCS: You may redistribute only under the terms of the Artistic License,
```

```
?RCS: as specified in the README file that comes with the distribution.
```

```
?RCS: You may reuse parts of this distribution only within the terms of
```

```
?RCS: that same Artistic License; a copy of which may be found at the root
```

```
?RCS: of the source tree for dist 3.0.
```

```
?RCS:
```

```

?RCS: $Log: orderlib.U,v $
?RCS: Revision 3.0.1.4 1997/02/28 16:18:18 ram
?RCS: patch61: replaced .a with $_a all over the place
?RCS: patch61: likewise for .o replaced by $_o
?RCS: patch61: now uses the ar located by Loc.U
?RCS:
?RCS: Revision 3.0.1.3 1995/01/11 15:33:04 ram
?RCS: patch45: allows hint files to specify their own value for 'ranlib'
?RCS:
?RCS: Revision 3.0.1.2 1994/10/29 16:26:48 ram
?RCS: patch36: now performs a real small compile for accurate
checks (ADO)
?RCS:
?RCS: Revision 3.0.1.1 1994/08/29 16:31:17 ram
?RCS: patch32: use cc variable instead of hardwired 'cc' in 1st compile
?RCS:
?RCS: Revision 3.0 1993/08/18 12:09:26 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:orderlib ranlib: Loc ar cat test rm +cc +ccflags +ldflags +libs i_stdlib _a _o run
?MAKE: -pick add $@ %<
?S:orderlib:
?S: This variable is "true" if the components of libraries must be ordered
?S: (with `lorder $* | tsort`) before placing them in an archive. Set to
?S: "false" if ranlib or ar can generate random libraries.
?S:.
?S:ranlib:
?S: This variable is set to the pathname of the ranlib program, if it is
?S: needed to generate random libraries. Set to ":" if ar can generate
?S: random libraries or if random libraries are not supported
?S:.
?F:!foobar
: see if ar generates random libraries by itself
echo " "
echo "Checking how to generate random libraries on your machine..." >&4
?X: Some systems (like MIPS) complain when running
ar... Others like Ultrix
?X: need an explicit 'ar ts' to add the table of contents.
?X: Still others like Linux run ar ts successfully, but still need ranlib.
?X: This set of tests seems the minimum necessary to check out Linux.
?X: We need to explicitly put the entries in out-of-order so that Sun's ld
?X: will fail. (Otherwise it complains, but gives an exit status of 0.)
echo 'int bar1() { return bar2(); }' > bar1.c
echo 'int bar2() { return 2; }' > bar2.c
$cat > foo.c <<EOP
#i_stdlib I_STDLIB
#ifdef I_STDLIB
#include <stdlib.h>

```

```

#endif
int main() { printf("%d\n", bar1()); exit(0); }
EOP
$cc $ccflags -c bar1.c >/dev/null 2>&1
$cc $ccflags -c bar2.c >/dev/null 2>&1
$cc $ccflags -c foo.c >/dev/null 2>&1
$ar rc bar$_a bar2$_o bar1$_o >/dev/null 2>&1
if $cc -o foobar $ccflags $ldflags foo$_o bar$_a $libs > /dev/null 2>&1 &&
$run ./foobar >/dev/null 2>&1; then
echo "$ar appears to generate random libraries itself."
orderlib=false
if [ "X$ranlib" = "X" ]; then
    ranlib=":"
fi
elif
$ar s bar$_a >/dev/null 2>&1 &&
$cc -o foobar $ccflags $ldflags foo$_o bar$_a $libs > /dev/null 2>&1 &&
$run ./foobar >/dev/null 2>&1; then
    echo "a table of contents needs to be added with '$ar s'."
    orderlib=false
    ranlib="$ar s"
elif $ar ts bar$_a >/dev/null 2>&1 &&
$cc -o foobar $ccflags $ldflags foo$_o bar$_a $libs > /dev/null 2>&1 &&
$run ./foobar >/dev/null 2>&1; then
    echo "a table of contents needs to be added with '$ar ts'."
    orderlib=false
    ranlib="$ar ts"
else
?X: Allow hints to specify their own ranlib "script". For instance, on
?X: some NeXT machines, the timestamp put by ranlib is not correct, and this
?X: may raise tedious recompiles for nothing. Therefore, NeXT may add the
?X: ranlib='sleep 5; /bin/ranlib' line in their hints to "fix" that.
?X: (reported by Andreas Koenig <k@franz.ww.tu-berlin.de>)
case "$ranlib" in
:) ranlib="";;
")
    ranlib=`./loc ranlib X /usr/bin /bin /usr/local/bin`
    $test -f $ranlib || ranlib="
;;
esac
if $test -n "$ranlib";
then
echo "your system has '$ranlib'; we'll use that."
orderlib=false
else
echo "your system doesn't seem to support random libraries"
echo "so we'll use lorder and tsort to order the libraries."
orderlib=true

```

```
ranlib=":"  
fi  
fi  
$rm -f foo* bar*
```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/compline/orderlib.U
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1999, Jarkko Hietaniemi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 3.0.

?RCS:

?MAKE:d_posix_timer: Setvar d_timer_create d_timer_delete d_timer_gettime d_timer_settime
d_timer_getoverrun i_time

?MAKE: -pick add \$@ %<

?S:d_posix_timer:

?S: This variable conditionally defines the HAS_POSIX_TIMER symbol, which

?S: indicates that the entire POSIX timer_*(2) library is present.

?S:.

?C:HAS_POSIX_TIMER:

?C: This symbol, if defined, indicates that the entire POSIX timer_*(2)

?C: library is supported.

?C:.

?H:#\$d_posix_timer HAS_POSIX_TIMER /**/

?H:.

?LINT:set d_posix_timer

: see how much of the 'POSIX timer_*(2)'

library is present.

echo " "

case "\$i_time\$d_timer_create\$d_timer_delete\$d_timer_gettime\$d_timer_settime\$d_timer_getoverrun" in

"\$undef") val="\$undef" ;;

*) val="\$define" ;;

esac

case "\$val" in

"\$define") echo "You have the full POSIX timer_*(2) library." >&4 ;;

"\$undef") echo "You don't have the full POSIX timer_*(2) library." >&4 ;;

esac

set d_posix_timer

eval \$setvar

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_posix_timer.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: models.U,v \$

?RCS: Revision 3.0.1.2 1997/02/28 16:13:17 ram

?RCS: patch61: added ?F: metalint hint

?RCS:

?RCS: Revision 3.0.1.1 1993/08/25 14:02:39 ram

?RCS: patch6: added default for large

?RCS:

?RCS: Revision 3.0 1993/08/18 12:09:17 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?MAKE:models split small medium large huge: test cat Myread sysman Oldconfig \

Loc Warn contains rm

?MAKE: -pick add \$@ %<

?S:models:

?S: This variable contains the list of memory models supported by

this

?S: system. Possible component values are none, split, unsplit, small,

?S: medium, large, and huge. The component values are space separated.

?S:.

?S:split:

?S: This variable contains a flag which will tell the C compiler and loader

?S: to produce a program that will run in separate I and D space, for those

?S: machines that support separation of instruction and data space. It is

?S: up to the Makefile to use this.

?S:.

?S:small:

?S: This variable contains a flag which will tell the C compiler and loader

?S: to produce a program running with a small memory model. It is up to

?S: the Makefile to use this.

?S:.

?S:medium:

?S: This variable contains a flag which will tell the C compiler and loader

?S: to produce a program running with a medium memory model. If the

?S: medium model is not supported, contains the flag to produce large

?S: model programs. It is up to the Makefile to use this.

?S:.

?S:large:

?S: This variable contains a flag which will tell the C compiler and loader

?S: to

produce a program running with a large memory model. It is up to

?S: the Makefile to use this.

?S:.

?S:huge:

?S: This variable contains a flag which will tell the C compiler and loader

?S: to produce a program running with a huge memory model. If the

?S: huge model is not supported, contains the flag to produce large

?S: model programs. It is up to the Makefile to use this.

?S:.

?T:unsplit tans modelcc

?F:!pdp11

?D:large=""

?LINT:extern cc

: see what memory models we can support

case "\$models" in

")

?X: We may not use Cppsym or we get a circular dependency through cc.

?X: But this should work regardless of which cc we eventually use.

\$cat >pdp11.c <<'EOP'

int main() {

#ifdef pdp11

exit(0);

#else

exit(1);

#endif

}

EOP

?X: Run cc in a subshell in case they don't have a 'cc' command.

?X: Presumably they do have gcc or something.

case "\$cc" in

") modelcc="\$cc" ;;

*) modelcc="cc" ;;

esac

(\$modelcc -o pdp11 pdp11.c) >/dev/null 2>&1

if \$test -f pdp11 && ./pdp11 2>/dev/null;

then

dflt='unsplit split'

else

tans=`./loc . X /lib/small /lib/large /usr/lib/small /usr/lib/large /lib/medium /usr/lib/medium /lib/huge`

case "\$tans" in

X) dflt='none';;

*) if \$test -d /lib/small || \$test -d /usr/lib/small; then

```

    dflt='small'
else
    dflt=""
fi
if $test -d /lib/medium || $test -d /usr/lib/medium; then
    dflt="$dflt medium"
fi
if $test -d /lib/large || $test -d /usr/lib/large; then
    dflt="$dflt large"
fi
if $test -d /lib/huge || $test -d /usr/lib/huge; then
    dflt="$dflt huge"
fi
esac
fi;;
*) dflt="$models";;
esac
$cat <<EOM

```

Some systems have different model sizes. On most systems they are called small, medium, large, and huge. On the PDP11 they are called unsplit and split. If your system doesn't support different memory models, say "none". If you wish to force everything to one memory model, say "none" here and put the appropriate flags later when it asks you for other cc and ld flags. Venix systems may wish to put "none" and let the compiler figure things out. (In the following question multiple model names should be space separated.)

The default for most systems is "none".

```

EOM
rp="Which memory models are supported?"
./myread
models="$ans"

case "$models" in
none)
small=""
medium=""
large=""
huge=""
unsplit=""
split=""
;;
*split)
case "$split" in
") if $contains \-i' $sysman/ld.1 >/dev/null 2>&1 || \
    $contains \-i' $sysman/cc.1 >/dev/null 2>&1; then

```

```

    dflt='-i'
else
    dflt='none'
fi;;
*) dflt="$split";;
esac
rp="What flag indicates separate I and D space?"
./myread
tans="$ans"
case "$tans" in
none) tans="";;
esac
split="$tans"
unsplit="";;
*large*|*small*|*medium*|*huge*)
case "$models" in
*large*)
case "$large" in
") dflt='-Ml';;
*) dflt="$large";;
esac
rp="What flag indicates large model?"
./myread
tans="$ans"
case "$tans" in
none) tans="";;
esac
large="$tans";;
*) large="";;
esac
case "$models" in
*huge*) case "$huge" in
")
dflt='-Mh';;
*) dflt="$huge";;
esac
rp="What flag indicates huge model?"
./myread
tans="$ans"
case "$tans" in
none) tans="";;
esac
huge="$tans";;
*) huge="$large";;
esac
case "$models" in
*medium*) case "$medium" in
") dflt='-Mm';;

```

```

*) dflt="$medium";;
esac
rp="What flag indicates medium model?"
./myread
tans="$ans"
case "$tans" in
none) tans="";
esac
medium="$tans";;
*) medium="$large";;
esac
case "$models" in
*small*) case "$small" in
") dflt='none';;
*) dflt="$small";;
esac
rp="What flag indicates small model?"
./myread
tans="$ans"
case "$tans" in
none) tans="";
esac
small="$tans";;
*) small="";;
esac
;;
*)
./warn "Unrecognized memory models--you may have to edit Makefile.SH"
;;
esac
$rm -f pdp11.* pdp11

```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/models.U
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: i_sunmath.U,v \$

?RCS:

?RCS: Copyright (c) 2000 Jarkko Hietaniemi

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?MAKE:i_sunmath: Inhdr Hasfield

?MAKE: -pick add \$@ %<

?S:i_sunmath:

?S: This variable conditionally defines the I_SUNMATH symbol, and indicates

?S: whether a C program should include <sunmath.h>.

?S:.

?C:I_SUNMATH:

?C: This symbol, if defined, indicates that <sunmath.h> exists and

?C: should be included.

?C:.

?H:#\$i_sunmath I_SUNMATH /**/

?H:.

?LINT:set i_sunmath

: see if this is a sunmath.h system

set sunmath.h i_sunmath

eval \$inhdr

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/i_sunmath.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: sysman.U,v 3.0.1.2 1994/06/20 07:08:43 ram Exp \$

?RCS:

?RCS: Copyright (c) 1991-1993, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 3.0.

?RCS:

?RCS: \$Log: sysman.U,v \$

?RCS: Revision 3.0.1.2 1994/06/20 07:08:43 ram

?RCS: patch30: now explicitly states that /usr/man/man1 is the default

?RCS: patch30: added /usr/local/man/man1 to the search list

?RCS:

?RCS: Revision 3.0.1.1 1993/09/13 16:13:50 ram

?RCS: patch10: added support for /local/man/man1 (WAD)

?RCS: patch10: added temporary syspath variable to cut down on line length

?RCS:

?RCS: Revision 3.0 1993/08/18 12:09:55 ram

?RCS: Baseline for dist 3.0 netwide

release.

?RCS:

?MAKE:sysman: test Loc Oldconfig

?MAKE: -pick add \$@ %<

?S:sysman:

?S: This variable holds the place where the manual is located on this

?S: system. It is not the place where the user wants to put his manual

?S: pages. Rather it is the place where Configure may look to find manual

?S: for unix commands (section 1 of the manual usually). See mansrc.

```

?S:.
?T:syspath
: determine where manual pages are on this system
echo " "
case "$sysman" in
")
syspath=/usr/share/man/man1 /usr/man/man1'
syspath="$syspath /usr/man/mann /usr/man/man1 /usr/man/local/man1"
syspath="$syspath /usr/man/u_man/man1"
syspath="$syspath /usr/catman/u_man/man1 /usr/man/l_man/man1"
syspath="$syspath /usr/local/man/u_man/man1 /usr/local/man/l_man/man1"
syspath="$syspath /usr/man/man.L /local/man/man1 /usr/local/man/man1"
sysman=`./loc . /usr/man/man1 $syspath`
;;
esac
if $test -d "$sysman"; then
echo "System manual is in $sysman." >&4
else
echo "Could not find manual pages in source form."
>&4
fi

```

Found in path(s):

```

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/modified/sysman.U

```

No license file was found, but licenses were detected in source scan.

```

?RCS: $Id: d_wctomb.U 1 2006-08-24 12:32:52Z rmanfredi $
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: Original Author: Andy Dougherty <doughera@lafcol.lafayette.edu>
?RCS:
?RCS: $Log: d_wctomb.U,v $
?RCS: Revision 3.0.1.1 1994/08/29 16:20:43 ram
?RCS: patch32: created by ADO
?RCS:
?MAKE:d_wctomb: Inlibc
?MAKE: -pick add $@ %<
?S:d_wctomb:
?S: This variable conditionally defines the HAS_WCTOMB symbol, which
?S: indicates to the C program that the wctomb() routine is available

```

?S: to convert a wide character to a multibyte.

?S:.

?C:HAS_WCTOMB (WCTOMB):

?C: This

symbol, if defined, indicates that the wctomb routine is available

?C: to convert a wide character to a multibyte.

?C:.

?H:#\$d_wctomb HAS_WCTOMB /**/

?H:.

?LINT:set d_wctomb

: see if wctomb exists

set wctomb d_wctomb

eval \$inlibc

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/d_wctomb.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: i_sysdir.U 1 2006-08-24 12:32:52Z rmanfredi \$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic Licence,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic Licence; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: i_sysdir.U,v \$

?RCS: Revision 3.0.1.1 1994/08/29 16:22:30 ram

?RCS: patch32: fixed typo in I_SYS_DIR symbol name

?RCS:

?RCS: Revision 3.0 1993/08/18 12:08:30 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?MAKE:i_sysdir: Inhdr

?MAKE: -pick add \$@ %<

?S:i_sysdir:

?S: This variable conditionally defines the I_SYS_DIR symbol, and indicates

?S: whether a C program should include <sys/dir.h>.

?S:.

?C:I_SYS_DIR (I_SYSDIR):

?C: This symbol, if

defined, indicates to the C program that it should

?C: include <sys/dir.h>.

?C:.

?H:#\$i_sysdir I_SYS_DIR /**/

```
?H:
?LINT:set i_sysdir
: see if this is an sysdir system
set sys/dir.h i_sysdir
eval $inhdr
```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/i_sysdir.U
```

No license file was found, but licenses were detected in source scan.

```
/*
```

```
* $Id: rename.C,v 3.0.1.1 1994/01/24 13:58:42 ram Exp ram $
*
* Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
*
* You may redistribute only under the terms of the Artistic Licence,
* as specified in the README file that comes with the distribution.
* You may reuse parts of this distribution only within the terms of
* that same Artistic Licence; a copy of which may be found at the root
* of the source tree for dist 4.0.
*
* $Log: rename.C,v $
* Revision 3.0.1.1 1994/01/24 13:58:42 ram
* patch16: created
*
*/
```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/lib/C/fake/rename.C
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: d_pwrite.U 1 2006-08-24 12:32:52Z rmanfredi $
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: $Log: d_pwrite.U,v $
?RCS:
?MAKE:d_pwrite: Inlibc
?MAKE:-pick add $@ %<
?S:d_pwrite:
```

?S: This variable conditionally defines the HAS_PWRITE symbol, which

?S: indicates to the C program that the pwrite() routine is available.

?S:.

?C:HAS_PWRITE :

?C: This symbol, if defined, indicates that the pwrite routine is

?C: available to perform writes on a file descriptor at a given offset.

?C:.

?H:#\$d_pwrite HAS_PWRITE /**/

?H:.

?LINT:set d_pwrite

: see if pwrite

exists

set pwrite d_pwrite

eval \$inlibc

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/d_pwrite.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: installstyle.U,v 1.2 1999/07/13 14:56:06 doughera Exp \$

?RCS:

?RCS: Copyright (c) 1999 Andy Dougherty

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 3.0.

?RCS:

?RCS: \$Log: installstyle.U,v \$

?RCS: Revision 1.2 1999/07/13 14:56:06 doughera

?RCS: Fix dependencies. Add more comments.

?RCS:

?RCS: Revision 1.1 1999/07/12 17:30:41 doughera

?RCS: Initial revision

?RCS:

?RCS:

?MAKE:installstyle: prefix Myread

?MAKE: -pick add \$@ %<

?X: Myread dependence is for dflt.

?S:installstyle:

?S: This variable describes the "style" of the perl installation.

?S: This is intended to be useful for tools that need to

?S: manipulate entire perl

distributions. Perl itself doesn't use

?S: this to find its libraries -- the library directories are

?S: stored directly in Config.pm. Currently, there are only two

?S: styles: "lib" and "lib/perl5". The default library locations
 ?S: (e.g. privlib, sitelib) are either \$prefix/lib or
 ?S: \$prefix/lib/perl5. The former is useful if \$prefix is a
 ?S: directory dedicated to perl (e.g. /opt/perl), while the latter
 ?S: is useful if \$prefix is shared by many packages, e.g. if
 ?S: \$prefix=/usr/local.
 ?S:
 ?S: Unfortunately, while this "style" variable is used to set
 ?S: defaults for all three directory hierarchies (core, vendor, and
 ?S: site), there is no guarantee that the same style is actually
 ?S: appropriate for all those directories. For example, \$prefix
 ?S: might be /opt/perl, but \$siteprefix might be /usr/local.
 ?S: (Perhaps, in retrospect, the "lib" style should never have been
 ?S: supported, but it did seem like a nice idea at the time.)
 ?S:
 ?S: The situation is even less clear for
 ?S: tools such as MakeMaker
 ?S: that can be used to install additional modules into
 ?S: non-standard places. For example, if a user intends to install
 ?S: a module into a private directory (perhaps by setting PREFIX on
 ?S: the Makefile.PL command line), then there is no reason to
 ?S: assume that the Configure-time \$installstyle setting will be
 ?S: relevant for that PREFIX.
 ?S:
 ?S: This may later be extended to include other information, so
 ?S: be careful with pattern-matching on the results.
 ?S:
 ?S: For compatibility with perl5.005 and earlier, the default
 ?S: setting is based on whether or not \$prefix contains the string
 ?S: "perl".
 ?S:.
 : determine installation style
 : For now, try to deduce it from prefix unless it is already set.
 : Reproduce behavior of 5.005 and earlier, maybe drop that in 5.7.
 case "\$installstyle" in
 ") case "\$prefix" in
 perl) dflt='lib';;
 *) dflt='lib/perl5' ;;
 esac
 ;;
 *) dflt="\$installstyle" ;;
 esac
 : Probably not worth prompting for this since we prompt
 for all
 : the directories individually, and the prompt would be too long and
 : confusing anyway.
 installstyle=\$dflt

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/installdirs/installstyle.U
```

No license file was found, but licenses were detected in source scan.

?RCS: Copyright (c) 1996, Andy Dougherty

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?MAKE:perladmin: cf_email Oldconfig Myread cat

?MAKE: -pick add \$@ %<

?Y:TOP

?S:perladmin:

?S: Electronic mail address of the perl5 administrator.

?S:.

: Ask e-mail of administrator

\$cat <<EOM

If you or somebody else will be maintaining perl at your site, please fill in the correct e-mail address here so that they may be contacted if necessary. Currently, the "perlbug" program included with perl will send mail to this address in addition to perlbug@perl.org. You may enter "none" for no administrator.

EOM

case "\$perladmin" in

*) dflt="\$cf_email";;

*) dflt="\$perladmin";;

esac

rp='Perl administrator e-mail address'

./myread

perladmin="\$ans"

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/perladmin.U
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_euc2jis.U 1 2006-08-24 12:32:52Z rmanfredi \$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic Licence,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic Licence; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:
?RCS: \$Log: d_euc2jis.U,v \$
?RCS: Revision 3.0 1993/08/18 12:05:58 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:d_euc2jis: Inlibc
?MAKE: -pick add \$@ %<
?S:d_euc2jis:
?S: This variable conditionally defines the HAS_EUC2JIS symbol, which
?S: indicates to the C program that the euc2jis() routine is available
?S: to convert EUC to JIS.
?S:.
?C:HAS_EUC2JIS:
?C: This symbol, if defined, indicates that the euc2jis routine is
?C: available to convert
EUC to JIS.
?C:.
?H:#\$d_euc2jis HAS_EUC2JIS /**/
?H:.
?LINT:set d_euc2jis
: see if euc2jis exists
set euc2jis d_euc2jis
eval \$inlibc

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/d_euc2jis.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: nis.U,v 3.0.1.3 1997/02/28 16:17:38 ram Exp \$
?RCS:
?RCS: Copyright (c) 1991-1993, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 3.0.
?RCS:
?RCS: \$Log: nis.U,v \$
?RCS: Revision 3.0.1.3 1997/02/28 16:17:38 ram
?RCS: patch61: ensure suitable defaults for hostcat and friends
?RCS:
?RCS: Revision 3.0.1.2 1995/03/21 08:48:34 ram
?RCS: patch52: continued fix for NeXT NIS/NetInfo handling
?RCS:
?RCS: Revision 3.0.1.1 1995/02/15 14:16:23 ram
?RCS: patch51: now correctly handles NeXT using NIS rather than NetInfo

```

?RCS:
?RCS: Revision 3.0 1993/08/18 12:09:24 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:passcat
groupcat hostcat: Myread Oldconfig test contains
?MAKE: -pick add $@ %<
?S:passcat:
?S: This variable contains a command that produces the text of the
?S: /etc/passwd file. This is normally "cat /etc/passwd", but can be
?S: "ypcat passwd" when NIS is used.
?S: On some systems, such as os390, there may be no equivalent
?S: command, in which case this variable is unset.
?S:.
?S:groupcat:
?S: This variable contains a command that produces the text of the
?S: /etc/group file. This is normally "cat /etc/group", but can be
?S: "ypcat group" when NIS is used.
?S: On some systems, such as os390, there may be no equivalent
?S: command, in which case this variable is unset.
?S:.
?S:hostcat:
?S: This variable contains a command that produces the text of the
?S: /etc/hosts file. This is normally "cat /etc/hosts", but can be
?S: "ypcat hosts" when NIS is used.
?S: On some systems, such as os390, there may be no equivalent
?S: command, in which case this variable is unset.
?S:.
:
see if we have to deal with yellow pages, now NIS.
?X: NeXT gives us some fun here, as always, by having both NIS (former YP)
?X: and NetInfo. But since it has both, it's ok to put the test inside the if.
?X: Contributed by Thomas Neumann <tom@smart.bo.open.de>.
if $test -d /usr/etc/yp || $test -d /etc/yp || $test -d /usr/lib/yp; then
@if passcat || groupcat
case "$passcat" in
nidump*) ;;
*)
case "$passcat" in
*ypcat*) dflt=y;;
") if $contains '^+' /etc/passwd >/dev/null 2>&1; then
dflt=y
else
dflt=n
fi;;
*) dflt=n;;
esac
echo " "

```

```

rp='Are you getting the passwd file via yellow pages?'
./myread
case "$ans" in
y*) passcat='ypcat passwd'
@if groupcat
echo "(Assuming /etc/group is also distributed.)"
groupcat='ypcat group'
@end
;;
*) passcat='cat /etc/passwd'
@if groupcat
echo "(Assuming /etc/group is also local.)"
groupcat='cat /etc/group'
@end
;;
esac
;;
esac
@end
@if hostcat
case "$hostcat" in
nidump*) ;;
*)
case
"$hostcat" in
*y*) dflt=y;;
") if $contains '^+' /etc/passwd >/dev/null 2>&1; then
dflt=y
else
dflt=n
fi;;
*) dflt=n;;
esac
echo " "
rp='Are you getting the hosts file via yellow pages?'
./myread
case "$ans" in
y*) hostcat='ypcat hosts';;
*) hostcat='cat /etc/hosts';;
esac
;;
esac
@end
fi
?X: Ensure suitable default -- Manoj Srivastava
case "$hostcat" in
") test -f /etc/hosts && hostcat='cat /etc/hosts';;
esac

```

```
case "$groupcat" in
") test -f /etc/group && groupcat='cat /etc/group';;
esac
case "$passcat" in
") test -f /etc/passwd && passcat='cat /etc/passwd';;
esac
```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/modified/nis.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: i_fp_class.U,v $
```

```
?RCS:
```

```
?RCS: Copyright (c) 1998 Jarkko Hietaniemi
```

```
?RCS:
```

```
?RCS: You may distribute under the terms of either the GNU General Public
```

```
?RCS: License or the Artistic License, as specified in the README file.
```

```
?RCS:
```

```
?MAKE:i_fp_class: Inhdr Hasfield
```

```
?MAKE: -pick add $@ %<
```

```
?S:i_fp_class:
```

```
?S: This variable conditionally defines the I_FP_CLASS symbol, and indicates
```

```
?S: whether a C program should include <fp_class.h>.
```

```
?S:.
```

```
?C:I_FP_CLASS:
```

```
?C: This symbol, if defined, indicates that <fp_class.h> exists and
```

```
?C: should be included.
```

```
?C:.
```

```
?H:#$i_fp_class I_FP_CLASS /**/
```

```
?H:.
```

```
?LINT:set i_fp_class
```

```
: see if this is a fp_class.h system
```

```
set fp_class.h i_fp_class
```

```
eval $inhdr
```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/perl/i_fp_class.U
```

No license file was found, but licenses were detected in source scan.

```
/*
```

```
* $Id: getopt.C,v 3.0.1.1 1994/01/24 13:58:40 ram Exp ram $
```

```
*
```

```
* Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
```

```
*
```

```
* You may redistribute only under the terms of the Artistic Licence,
```

```
* as specified in the README file that comes with the distribution.
```

* You may reuse parts of this distribution only within the terms of
* that same Artistic Licence; a copy of which may be found at the root
* of the source tree for dist 4.0.
*
* Original Author: unknown, got this off net.sources
*
* \$Log: getopt.C,v \$
* Revision 3.0.1.1 1994/01/24 13:58:40 ram
* patch16: created
*
*/

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/lib/C/fake/getopt.C

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: mailfile.U 1 2006-08-24 12:32:52Z rmanfredi \$
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: \$Log: mailfile.U,v \$
?RCS: Revision 3.0.1.2 1994/10/29 16:24:57 ram
?RCS: patch36: the Loc unit was missing from the dependency line
?RCS:
?RCS: Revision 3.0.1.1 1993/12/15 08:22:08 ram
?RCS: patch15: now also looks under /var/mail for BSD/386
?RCS:
?RCS: Revision 3.0 1993/08/18 12:09:11 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:mailfile: Myread Oldconfig Filexp Loc
?MAKE: -pick add \$@ %<
?S:mailfile:
?S: This variable contains
the eventual value of the MAILFILE symbol,
?S: which contains an interpretable name of the mail spool file for the
?S: current user.
?S:.
?C:MAILFILE:
?C: This symbol contains the interpretable name of the mail spool file
?C: for the current user. The program must be prepared to substitute

?C: the HOME directory for %~, and the login id for %L.

?C:.

```
?H:#define MAILFILE "$mailfile" /**/
```

?H:.

: determine where mail is spooled

```
case "$mailfile" in
```

```
)
```

```
  dflt=`./loc . XXX /usr/spool/mail /usr/mail /var/mail`
```

```
  case "$dflt" in
```

```
    XXX) dflt='%~/mailbox';;
```

```
    *) dflt="$dflt/%L";;
```

```
  esac
```

```
;;
```

```
*) dflt="$mailfile"
```

```
;;
```

```
esac
```

```
cat <<'EOM'
```

In the following question, you may use %~ to represent the user's home directory, and %L to represent a users name.

EOM

```
rp='In which file is yet-to-be-read mail spooled? (~name ok)'
```

```
./myread
```

```
mailfile=`./filexp "$ans"`
```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/mailfile.U
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1998 Jarkko Hietaniemi

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the WRITEME file.

?RCS:

?MAKE:d_writev: Inlibc

?MAKE: -pick add \$@ %<

?S:d_writev:

?S: This variable conditionally defines the HAS_WRITEV symbol, which

?S: indicates to the C program that the writev() routine is available.

?S:.

?C:HAS_WRITEV:

?C: This symbol, if defined, indicates that the writev routine is

?C: available to do scatter writes.

?C:.

?H:#\$d_writev HAS_WRITEV /**/

?H:.

?LINT:set d_writev

: see if writev exists

set writev d_writev

eval \$inlibc

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_writev.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1999 Jarkko Hietaniemi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 3.0.

?RCS:

?MAKE:d_getspnam: Inlibc

?MAKE: -pick add \$@ %<

?S:d_getspnam:

?S: This variable conditionally defines HAS_GETSPNAM if getspnam() is

?S: available to retrieve SysV shadow password entries by name.

?S:.

?C:HAS_GETSPNAM:

?C: This symbol, if defined, indicates that the getspnam system call is

?C: available to retrieve SysV shadow password entries by name.

?C:.

?H:#\$d_getspnam HAS_GETSPNAM /**/

?H:.

?LINT:set d_getspnam

: see if getspnam exists

set getspnam d_getspnam

eval \$inlibc

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_getspnam.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_endnetent_r.U,v 0RCS:

?RCS: Copyright (c) 2002,2003 Jarkko Hietaniemi

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?RCS: Generated by the reentr.pl from the Perl 5.8 distribution.

?RCS:

?MAKE:d_endnetent_r endnetent_r_proto: Inlibc Protochk Hasproto i_systypes \
 usethreads i_netdb extern_C

?MAKE: -pick add \$@ %<

?S:d_endnetent_r:

?S: This variable conditionally defines the HAS_ENDNETENT_R symbol,
 ?S: which indicates to the C program that the endnetent_r()
 ?S: routine is available.

?S:.

?S:endnetent_r_proto:

?S: This variable encodes the prototype of endnetent_r.
 ?S: It is zero if d_endnetent_r is undef, and one of the
 ?S: REENTRANT_PROTO_T_ABC macros of reentr.h if d_endnetent_r
 ?S: is defined.

?S:.

?C:HAS_ENDNETENT_R:

?C: This symbol, if defined, indicates that the endnetent_r routine
 ?C: is
 available to endnetent re-entrantly.

?C:.

?C:ENDNETENT_R_PROTO:

?C: This symbol encodes the prototype of endnetent_r.
 ?C: It is zero if d_endnetent_r is undef, and one of the
 ?C: REENTRANT_PROTO_T_ABC macros of reentr.h if d_endnetent_r
 ?C: is defined.

?C:.

?H:#\$d_endnetent_r HAS_ENDNETENT_R /**/
 ?H:#define ENDNETENT_R_PROTO \$endnetent_r_proto /**/
 ?H:.

?T:try hdrs d_endnetent_r_proto
 : see if endnetent_r exists
 set endnetent_r d_endnetent_r
 eval \$inlibc
 case "\$d_endnetent_r" in
 "\$define")
 hdrs="\$i_systypes sys/types.h define stdio.h \$i_netdb netdb.h"
 case "\$d_endnetent_r_proto:\$usethreads" in
 ":define") d_endnetent_r_proto=define
 set d_endnetent_r_proto endnetent_r \$hdrs
 eval \$hasproto ;;
 *) ;;
 esac
 case "\$d_endnetent_r_proto" in
 define)
 case "\$endnetent_r_proto" in

```

"|0) try='int endnetent_r(struct netent_data*);'
./protochk "$extern_C $try" $hdrs && endnetent_r_proto=I_D ;;
esac
case "$endnetent_r_proto" in
"|0) try='void endnetent_r(struct netent_data*);'
./protochk
"$extern_C $try" $hdrs && endnetent_r_proto=V_D ;;
esac
case "$endnetent_r_proto" in
"|0) d_endnetent_r=undef
    endnetent_r_proto=0
    echo "Disabling endnetent_r, cannot determine prototype." >&4 ;;
*) case "$endnetent_r_proto" in
    REENTRANT_PROTO*) ;;
*) endnetent_r_proto="REENTRANT_PROTO_$endnetent_r_proto" ;;
esac
echo "Prototype: $try" ;;
esac
;;
*) case "$usetthreads" in
define) echo "endnetent_r has no prototype, not using it." >&4 ;;
esac
d_endnetent_r=undef
endnetent_r_proto=0
;;
esac
;;
*) endnetent_r_proto=0
;;
esac

```

Found in path(s):

```

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/threads/d_endnetent_r.U

```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: Myinit.U,v \$

?RCS: Revision 3.0.1.1 1994/10/31 09:47:29 ram

?RCS: patch44: leading comment states this unit comes before option processing
?RCS:
?RCS: Revision 3.0 1993/08/18 12:05:07 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?X:
?X: If you want to initialize any default values, copy this unit to your
?X: personal U directory and add the assignments to the end. This file
?X: is included after variables are initialized but before any old
?X: config.sh file is read in and before
?X: any Configure switch processing.
?X:
?MAKE:Myinit: Init
?MAKE: -pick add \$@ %<
?LINT: nocomment

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/Myinit.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: html3dir.U,v \$
?RCS:
?RCS: Copyright (c) 1999 Andy Dougherty
?RCS:
?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 3.0.
?RCS:
?RCS: \$Log: html3dir.U,v \$
?RCS:
?MAKE:html3dir html3direxp installhtml3dir: cat sed Loc Myread \
package test Getfile Setprefixvar Prefixit Prefixup html1dir
?MAKE: -pick add \$@ %<
?Y:TOP
?D:html3dir="
?S:html3dir:
?S: This variable contains the name of the directory in which html
?S: source pages are to be put. This directory is for pages
?S: that describe libraries or modules. It is intended to
?S: correspond roughly to section 3 of the Unix manuals.
?S:.
?D:html3direxp="
?S:html3direxp:
?S: This variable

```

is the same as the html3dir variable, but is filename
?S: expanded at configuration time, for convenient use in makefiles.
?S:.
?D:installhtml3dir="
?S:installhtml3dir:
?S: This variable is really the same as html3direxp, unless you are
?S: using a different installprefix. For extra portability, you
?S: should only use this variable within your makefiles.
?S:.
?LINT:change prefixvar
?LINT:set html3direxp
?LINT:set installhtml3dir
: determine where html pages for libraries and modules go
set html3dir html3dir none
eval $prefixit
$cat <<EOM

```

If you wish to install html files for modules associated with \$spackage, indicate the appropriate directory here. To skip installing html files, answer "none".

EOM

```

: There is no obvious default. If they have specified html1dir, then
: try to key off that, possibly changing ../html1 into ../html3.

```

```

case "$html3dir" in

```

```

*) html3dir=`echo "$html1dir" | $sed 's/1$/3$/'` ;;

```

```

*) dflt=$html3dir ;;

```

```

esac

```

```

fn=dn+~

```

```

rp="Directory for the $spackage module

```

```

html pages?"

```

```

./getfile

```

```

prefixvar=html3dir

```

```

./setprefixvar

```

```

: Use ' ' for none so value is preserved next time through Configure

```

```

$test X"$html3dir" = "X" && html3dir=' '

```

Found in path(s):

```

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/installdirs/html3dir.U

```

No license file was found, but licenses were detected in source scan.

```

?RCS: $Id$

```

```

?RCS:

```

```

?RCS: Copyright (c) 2003 Jarkko Hietaniemi

```

```

?RCS:

```

```

?RCS: You may distribute under the terms of either the GNU General Public

```

```

?RCS: License or the Artistic License, as specified in the README file.

```

```

?RCS:

```

?MAKE:d_ilogbl: Inlibc
?MAKE: -pick add \$@ %<
?S:d_ilogbl:
?S: This variable conditionally defines the HAS_ILOGBL symbol, which
?S: indicates to the C program that the ilogbl() routine is available
?S: for extracting the exponent of long double x as a signed integer.
?S: If scalbnl is also present we can emulate frexpl.
?S:.
?C:HAS_ILOGBL:
?C: This symbol, if defined, indicates that the ilogbl routine is
?C: available. If scalbnl is also present we can emulate frexpl.
?C:.
?H:#\$d_ilogbl HAS_ILOGBL /**/
?H:.
?LINT:set d_ilogbl
: see if ilogbl exists
set ilogbl d_ilogbl
eval \$inlibc

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_ilogbl.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: Filexp.U,v \$

?RCS: Revision 3.0.1.2 1994/10/29 15:52:53 ram

?RCS: patch36: added ?F: line for metalint file checking

?RCS: patch36: added HOME to the ?T: line since metalint now checks \${HOME}

?RCS:

?RCS: Revision 3.0.1.1 1994/05/06 14:03:00 ram

?RCS: patch23: made sure error status from csh is propagated (WED)

?RCS:

?RCS: Revision 3.0 1993/08/18 12:04:53 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?X:

?X: This unit produces a shell script which will expand filenames beginning

?X:

+x filexp
\$eunicefix filexp

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/Filexp.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_newsadm.U 1 2006-08-24 12:32:52Z rmanfredi \$
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: \$Log: d_newsadm.U,v \$
?RCS: Revision 3.0.1.2 1997/02/28 15:36:53 ram
?RCS: patch61: added Guess dependency
?RCS:
?RCS: Revision 3.0.1.1 1994/10/29 16:14:33 ram
?RCS: patch36: call ./eunice explicitly instead of relying on PATH
?RCS:
?RCS: Revision 3.0 1993/08/18 12:06:42 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:d_newsadm newsadmin: cat contains Guess Setvar Myread Oldconfig
?MAKE: -pick add \$@ %<
?S:d_newsadm:
?S: This variable
conditionally defines the NEWS_ADMIN symbol, which
?S: indicates to the C program that there is a user who is in charge
?S: of news administration.
?S:.
?S:newsadmin:
?S: This variable holds the login name of the news administrator, if any.
?S:.
?C:NEWS_ADMIN (NEWSADMIN):
?C: This symbol, if defined, contains the login name of the news
?C: administrator.
?C:.
?H:#\$d_newsadm NEWS_ADMIN "\$newsadmin" /**/
?H:.
?LINT:set d_newsadm
: get news administrator name
case "\$newsadmin" in

```

")
if $contains "^news:" /etc/passwd >/dev/null 2>&1 ; then
    dflt=news
elif $contains "^usenet:" /etc/passwd >/dev/null 2>&1 ; then
    dflt=usenet
elif ./eunice; then
    dflt=system
else
    dflt=root
fi
;;
*)
dflt="$newsadmin"
;;
esac
$cat <<'EOM'

```

Many systems keep their news in a private directory, or have a non-superuser in charge of administering news. (If you don't have such a user, take the default answer.) I need the login name (not directory) which is used for news administration.

```

EOM
rp="News
admin login?"
./myread
newsadmin="$ans"
case "$newsadmin" in
root) val="$undef" ;;
*) val="$define" ;;
esac
set d_newsadm
eval $setvar

```

Found in path(s):

```

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/d_newsadm.U

```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: d_fmod.U 1 2006-08-24 12:32:52Z rmanfredi $
```

```
?RCS:
```

```
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
```

```
?RCS:
```

```
?RCS: You may redistribute only under the terms of the Artistic Licence,
```

```
?RCS: as specified in the README file that comes with the distribution.
```

```
?RCS: You may reuse parts of this distribution only within the terms of
```

```
?RCS: that same Artistic Licence; a copy of which may be found at the root
```

```
?RCS: of the source tree for dist 4.0.
```

?RCS:
 ?RCS: Original Author: Andy Dougherty <doughera@lafcol.lafayette.edu>
 ?RCS:
 ?RCS: \$Log: d_fmod.U,v \$
 ?RCS: Revision 3.0.1.1 1994/10/29 16:12:46 ram
 ?RCS: patch36: created by ADO
 ?RCS:
 ?MAKE:d_fmod: Inlibc
 ?MAKE: -pick add \$@ %<
 ?S:d_fmod:
 ?S: This variable conditionally defines the HAS_FMOD symbol, which
 ?S: indicates to the C program that the fmod() routine is available.
 ?S: See also d_drem for the drem() routine which does roughly the same.
 ?S:.
 ?C:HAS_FMOD
 :
 ?C: This symbol, if defined, indicates that the fmod routine is
 ?C: available to compute the remainder $r=x-n*y$ where $n=\text{trunc}(x/y)$.
 ?C:.
 ?H:#\$d_fmod HAS_FMOD /**/
 ?H:.
 ?LINT:set d_fmod
 : see if fmod exists
 set fmod d_fmod
 eval \$inlibc

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/d_fmod.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$
 ?RCS:
 ?RCS: Copyright (c) 1999, Jarkko Hietaniemi
 ?RCS:
 ?RCS: You may redistribute only under the terms of the Artistic License,
 ?RCS: as specified in the README file that comes with the distribution.
 ?RCS: You may reuse parts of this distribution only within the terms of
 ?RCS: that same Artistic License; a copy of which may be found at the root
 ?RCS: of the source tree for dist 3.0.
 ?RCS:
 ?MAKE:d_sched_setscheduler: Inlibc
 ?MAKE: -pick add \$@ %<
 ?S:d_sched_setscheduler:
 ?S: This variable conditionally defines HAS_SCHED_SETSCHEDULER if
 ?S: sched_setscheduler() is available to set the scheduling policy.
 ?S:.
 ?C:HAS_SCHED_SETSCHEDULER:

?C: This symbol, if defined, indicates that the sched_setscheduler
?C: system call is available to set the scheduling policy.
?C:.
?H:#\$d_sched_setscheduler HAS_SCHED_SETSCHEDULER /**/
?H:.
?LINT:set d_sched_setscheduler
: see if sched_setscheduler exists
set sched_setscheduler
d_sched_setscheduler
eval \$inlibc

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_sched_setscheduler.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_getservbyport_r.U,v 0RCS:
?RCS: Copyright (c) 2002,2003 Jarkko Hietaniemi
?RCS:
?RCS: You may distribute under the terms of either the GNU General Public
?RCS: License or the Artistic License, as specified in the README file.
?RCS:
?RCS: Generated by the reentr.pl from the Perl 5.8 distribution.
?RCS:
?MAKE:d_getservbyport_r getservbyport_r_proto: Inlibc Protochk Hasproto \
i_systypes usethreads i_netdb extern_C
?MAKE: -pick add \$@ %<
?S:d_getservbyport_r:
?S: This variable conditionally defines the HAS_GETSERVBYPORTR symbol,
?S: which indicates to the C program that the getservbyport_r()
?S: routine is available.
?S:.
?S:getservbyport_r_proto:
?S: This variable encodes the prototype of getservbyport_r.
?S: It is zero if d_getservbyport_r is undef, and one of the
?S: REENTRANT_PROTO_T_ABC macros of reentr.h if d_getservbyport_r
?S: is defined.
?S:.
?C:HAS_GETSERVBYPORTR:
?C: This symbol, if defined, indicates
that the getservbyport_r routine
?C: is available to getservbyport re-entrantly.
?C:.
?C:GETSERVBYPORTR_PROTO:
?C: This symbol encodes the prototype of getservbyport_r.
?C: It is zero if d_getservbyport_r is undef, and one of the
?C: REENTRANT_PROTO_T_ABC macros of reentr.h if d_getservbyport_r
?C: is defined.

```

?C:.
?H:#$d_getservbyport_r HAS_GETSERVBYPORTR /**/
?H:#define GETSERVBYPORTR_PROTO $getservbyport_r_proto /**/
?H:.
?T:try hdrs d_getservbyport_r_proto
: see if getservbyport_r exists
set getservbyport_r d_getservbyport_r
eval $inlibc
case "$d_getservbyport_r" in
"$define")
hdrs="$i_systypes sys/types.h define stdio.h $i_netdb netdb.h"
case "$d_getservbyport_r_proto:$susetheads" in
":define") d_getservbyport_r_proto=define
set d_getservbyport_r_proto getservbyport_r $hdrs
eval $hasproto ;;
*) ;;
esac
case "$d_getservbyport_r_proto" in
define)
case "$getservbyport_r_proto" in
"|0) try='int getservbyport_r(int, const char*, struct servent*, char*, size_t,
struct servent**);'
./protochk "$extern_C $try" $hdrs && getservbyport_r_proto=I_ICSBWR ;;
esac
case "$getservbyport_r_proto" in
"|0) try='struct servent* getservbyport_r(int, const char*, struct servent*, char*, int);'
./protochk "$extern_C $try" $hdrs && getservbyport_r_proto=S_ICSBW ;;
esac
case "$getservbyport_r_proto" in
"|0) try='int getservbyport_r(int, const char*, struct servent*, struct servent_data*);'
./protochk "$extern_C $try" $hdrs && getservbyport_r_proto=I_ICSD ;;
esac
case "$getservbyport_r_proto" in
"|0) d_getservbyport_r=undef
getservbyport_r_proto=0
echo "Disabling getservbyport_r, cannot determine prototype." >&4 ;;
*) case "$getservbyport_r_proto" in
REENTRANT_PROTO*) ;;
*) getservbyport_r_proto="REENTRANT_PROTO_$getservbyport_r_proto" ;;
esac
echo "Prototype: $try" ;;
esac
;;
*) case "$susetheads" in
define) echo "getservbyport_r has no prototype, not using it." >&4 ;;
esac
d_getservbyport_r=undef
getservbyport_r_proto=0

```

```
;;
esac
;;
*) getservbyport_r_proto=0
;;
esac
```

Found

in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/threads/d_getservbyport_r.U
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_getprotobyname_r.U,v 0RCS:

?RCS: Copyright (c) 2002,2003 Jarkko Hietaniemi

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?RCS: Generated by the reentr.pl from the Perl 5.8 distribution.

?RCS:

?MAKE:d_getprotobyname_r getprotobyname_r_proto: Inlibc Protochk Hasproto \
i_systypes usethreads i_netdb extern_C

?MAKE: -pick add \$@ %<

?S:d_getprotobyname_r:

?S: This variable conditionally defines the HAS_GETPROTOBYNAME_R symbol,

?S: which indicates to the C program that the getprotobyname_r()

?S: routine is available.

?S:.

?S:getprotobyname_r_proto:

?S: This variable encodes the prototype of getprotobyname_r.

?S: It is zero if d_getprotobyname_r is undef, and one of the

?S: REENTRANT_PROTO_T_ABC macros of reentr.h if d_getprotobyname_r

?S: is defined.

?S:.

?C:HAS_GETPROTOBYNAME_R:

?C: This symbol, if
defined, indicates that the getprotobyname_r routine

?C: is available to getprotobyname re-entrantly.

?C:.

?C:GETPROTOBYNAME_R_PROTO:

?C: This symbol encodes the prototype of getprotobyname_r.

?C: It is zero if d_getprotobyname_r is undef, and one of the

?C: REENTRANT_PROTO_T_ABC macros of reentr.h if d_getprotobyname_r

?C: is defined.

?C:.

?H:#\$d_getprotobyname_r HAS_GETPROTOBYNAME_R /**/

?H:#define GETPROTOBYNAME_R_PROTO \$getprotobyname_r_proto /**/

```

?H:
?T:try hdrs d_getprotobyname_r_proto
: see if getprotobyname_r exists
set getprotobyname_r d_getprotobyname_r
eval $inlibc
case "$d_getprotobyname_r" in
"$define")
hdrs="$i_systypes sys/types.h define stdio.h $i_netdb netdb.h"
case "$d_getprotobyname_r_proto:$usethreads" in
":define") d_getprotobyname_r_proto=define
set d_getprotobyname_r_proto getprotobyname_r $hdrs
eval $hasproto ;;
*) ;;
esac
case "$d_getprotobyname_r_proto" in
define)
case "$getprotobyname_r_proto" in
"|0) try='int getprotobyname_r(const char*,
struct protoent*, char*, size_t, struct protoent**);'
./protochk "$extern_C $try" $hdrs && getprotobyname_r_proto=I_CSBWR ;;
esac
case "$getprotobyname_r_proto" in
"|0) try='struct protoent* getprotobyname_r(const char*, struct protoent*, char*, int);'
./protochk "$extern_C $try" $hdrs && getprotobyname_r_proto=S_CSBI ;;
esac
case "$getprotobyname_r_proto" in
"|0) try='int getprotobyname_r(const char*, struct protoent*, struct protoent_data*);'
./protochk "$extern_C $try" $hdrs && getprotobyname_r_proto=I_CSD ;;
esac
case "$getprotobyname_r_proto" in
"|0) d_getprotobyname_r=undef
getprotobyname_r_proto=0
echo "Disabling getprotobyname_r, cannot determine prototype." >&4 ;;
*) case "$getprotobyname_r_proto" in
REENTRANT_PROTO*) ;;
*) getprotobyname_r_proto="REENTRANT_PROTO_$getprotobyname_r_proto" ;;
esac
echo "Prototype: $try" ;;
esac
;;
*) case "$usethreads" in
define) echo "getprotobyname_r has no prototype, not using it." >&4 ;;
esac
d_getprotobyname_r=undef
getprotobyname_r_proto=0
;;
esac
;;

```

```
*) getprotobyname_r_proto=0
```

```
::
```

```
esac
```

Found

in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/threads/d_getprotobyname_r.U
```

No license file was found, but licenses were detected in source scan.

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?MAKE:d_strerror_l: Inlibc

?MAKE: -pick add \$@ %<

?S:d_strerror_l:

?S: This variable conditionally defines the HAS_STRERROR_L symbol, which

?S: indicates to the C program that the strerror_l() routine is available

?S: to return the error message for a given errno value in a particular

?S: locale (identified by a locale_t object).

?S:.

?C:HAS_STRERROR_L:

?C: This symbol, if defined, indicates that the strerror_l routine is

?C: available to return the error message for a given errno value in

?C: a particular locale (identified by a locale_t object).

?C:.

?H:#\$d_strerror_l HAS_STRERROR_L /**/

?H:.

?LINT:set d_strerror_l

: see if strerror_l exists

set strerror_l d_strerror_l

eval \$inlibc

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_strerror_l.U
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 2001 Jarkko Hietaniemi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 3.0.

?RCS:

```

?MAKE:d_flockproto: Hasproto i_sysfile
?MAKE: -pick add $@ %<
?S:d_flockproto:
?S: This variable conditionally defines the HAS_FLOCK_PROTO symbol,
?S: which indicates to the C program that the system provides
?S: a prototype for the flock() function. Otherwise, it is
?S: up to the program to supply one.
?S:.
?C:HAS_FLOCK_PROTO:
?C: This symbol, if defined, indicates that the system provides
?C: a prototype for the flock() function. Otherwise, it is up
?C: to the program to supply one. A good guess is
?C: extern int flock(int,
int);
?C:.
?H:#$d_flockproto HAS_FLOCK_PROTO /**/
?H:.
?LINT:set d_flockproto
: see if prototype for flock is available
echo " "
set d_flockproto flock $i_sysfile sys/file.h
eval $hasproto

```

Found in path(s):

```

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/perl/d_flockproto.U

```

No license file was found, but licenses were detected in source scan.

```

?RCS: $Id: usecbacktrace.U,v $
?RCS:
?RCS: Copyright (c) 2014 H.Merijn Brand
?RCS:
?RCS: You may distribute under the terms of either the GNU General Public
?RCS: License or the Artistic License, as specified in the README file.
?RCS:
?RCS: $Log: usecbacktrace.U,v $
?RCS:
?MAKE:usecbacktrace: Myread Oldconfig Setvar Getfile d_backtrace
?MAKE: -pick add $@ %<
?Y:TOP
?S:usecbacktrace:
?S: This variable indicates whether we are compiling with backtrace
?S: support.
?S:.
?C:USE_CBACKTRACE:
?C: This symbol, if defined, indicates that Perl should
?C: be built with support for backtrace.
?C:.

```

```

?H:#$usecbacktrace USE_CBACKTRACE /**/
?H:.
?LINT:extern ccflags
?LINT:change ccflags
: add flags if using c backtrace
case "$usecbacktrace" in
  "") usecbacktrace=$undef ;;
  [yY]*|true|$define)
    case "$d_backtrace" in
      [yY]*|true|$define)
        case " $ccflags " in
          *" -DUSE_C_BACKTRACE "*" ;; # Already there.
          *) ccflags="$ccflags
-DUSE_C_BACKTRACE -g" ;;
        esac
      ;;
    *)
      echo "This system does not support backtrace" >&4
      usecbacktrace=$undef
      ;;
    esac
  ;;
esac

```

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/usebacktrace.U

No license file was found, but licenses were detected in source scan.

```

?RCS: $Id$
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: $Log: i_ndbm.U,v $
?RCS: Revision 3.0.1.1 1995/05/12 12:16:53 ram
?RCS: patch54: made more robust by checking both header and lib (ADO)
?RCS:
?RCS: Revision 3.0 1993/08/18 12:08:23 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:i_ndbm: Inhdr Inlibc Setvar
?MAKE: -pick add $@ %<

```

```

?S:i_ndbm (d_ndbm):
?S: This variable conditionally defines the I_NDBM symbol, which
?S: indicates to the C program that <ndbm.h> exists and should
?S: be included.
?S:.
?C:I_NDBM (HAS_NDBM NDBM):
?C: This
symbol, if defined, indicates that <ndbm.h> exists and should
?C: be included.
?C:.
?H:#$i_ndbm I_NDBM /**/
?H:.
?T:t_ndbm d_dbm_open
?LINT:set i_ndbm
: see if ndbm.h is available
?X: t_ndbm is a tentative check. We might just have the .h, not the lib -- ADO
set ndbm.h t_ndbm
eval $inhdr
case "$t_ndbm" in
$define)
: see if dbm_open exists
set dbm_open d_dbm_open
eval $inlibc
case "$d_dbm_open" in
$undef)
t_ndbm="$undef"
echo "We won't be including <ndbm.h>"
;;
esac
;;
esac
val="$t_ndbm"
set i_ndbm
eval $setvar

```

Found in path(s):

```

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/i_ndbm.U

```

No license file was found, but licenses were detected in source scan.

```

?RCS: $Id: d_setpgid.U 1 2006-08-24 12:32:52Z rmanfredi $

```

```

?RCS:

```

```

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

```

```

?RCS:

```

```

?RCS: You may redistribute only under the terms of the Artistic Licence,

```

```

?RCS: as specified in the README file that comes with the distribution.

```

```

?RCS: You may reuse parts of this distribution only within the terms of

```

```

?RCS: that same Artistic Licence; a copy of which may be found at the root

```

?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: \$Log: d_setpgid.U,v \$
?RCS: Revision 3.0.1.2 1997/02/28 15:41:49 ram
?RCS: patch61: reworded symbol comments
?RCS:
?RCS: Revision 3.0.1.1 1994/01/24 14:06:40 ram
?RCS: patch16: created
?RCS:
?RCS: Revision 3.0 1993/08/18 12:05:56 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:d_setpgid: Inlibc
?MAKE: -pick add \$@ %<
?S:d_setpgid:
?S: This variable conditionally defines the HAS_SETPGID symbol if the
?S: setpgid(pid, gpid) function is
available to set process group ID.
?S:.
?C:HAS_SETPGID:
?C: This symbol, if defined, indicates that the setpgid(pid, gpid)
?C: routine is available to set process group ID.
?C:.
?H:#\$d_setpgid HAS_SETPGID /**/
?H:.
?LINT:set d_setpgid
: see if setpgid exists
set setpgid d_setpgid
eval \$inlibc

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/d_setpgid.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: i_sysvfs.U,v \$
?RCS:
?RCS: Copyright (c) 1999 Jarkko Hietaniemi
?RCS:
?RCS: You may distribute under the terms of either the GNU General Public
?RCS: License or the Artistic License, as specified in the README file.
?RCS:
?MAKE:i_sysvfs: Inhdr Hasfield
?MAKE: -pick add \$@ %<
?S:i_sysvfs:
?S: This variable conditionally defines the I_SYSVFS symbol,
?S: and indicates whether a C program should include <sys/vfs.h>.
?S:.

?C:I_SYS_VFS:

?C: This symbol, if defined, indicates that <sys/vfs.h> exists and

?C: should be included.

?C:.

?H:#\$i_sysvfs I_SYS_VFS /**/

?H:.

?LINT:set i_sysvfs

: see if this is a sys/vfs.h system

set sys/vfs.h i_sysvfs

eval \$inhdr

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/i_sysvfs.U

No license file was found, but licenses were detected in source scan.

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?MAKE:d_logb: Inlibc

?MAKE: -pick add @\$ %<

?S:d_logb:

?S: This variable conditionally defines the HAS_LOGB symbol, which

?S: indicates to the C program that the logb() routine is available

?S: to extract the exponent of x.

?S:.

?C:HAS_LOGB:

?C: This symbol, if defined, indicates that the logb routine is

?C: available to do the logb function.

?C:.

?H:#\$d_logb HAS_LOGB /**/

?H:.

?LINT:set d_logb

: see if logb exists

set logb d_logb

eval \$inlibc

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_logb.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_getppid.U 1 2006-08-24 12:32:52Z rmanfredi \$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic Licence,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: Original Author: Andy Dougherty <doughera@lafcol.lafayette.edu>
?RCS:
?RCS: \$Log: d_getppid.U,v \$
?RCS: Revision 3.0.1.1 1994/08/29 16:07:45 ram
?RCS: patch32: created by ADO
?RCS:
?MAKE:d_getppid: Inlibc
?MAKE: -pick add \$@ %<
?S:d_getppid:
?S: This variable conditionally defines the HAS_GETPPID symbol, which
?S: indicates to the C program that the getppid() routine is available
?S: to get the parent process ID.
?S:.
?C:HAS_GETPPID :
?C: This symbol,
if defined, indicates that the getppid routine is
?C: available to get the parent process ID.
?C:.
?H:#\$d_getppid HAS_GETPPID /**/
?H:.
?LINT:set d_getppid
: see if getppid exists
set getppid d_getppid
eval \$inlibc

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/d_getppid.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: Original Author: Andy Dougherty <doughera@lafcol.lafayette.edu>
?RCS:
?RCS: \$Log: modetype.U,v \$
?RCS: Revision 3.0.1.1 1994/10/29 16:25:07 ram

```

?RCS: patch36: created by ADO
?RCS:
?MAKE:modetype: Myread Typedef
?MAKE: -pick add $@ %<
?S:modetype:
?S: This variable defines modetype to be something like mode_t,
?S: int, unsigned short, or whatever type is used to declare file
?S: modes for system calls.
?S:.
?C:Mode_t:
?C: This symbol holds the type used to declare file modes
?C: for systems calls.
    It is usually mode_t, but may be
?C: int or unsigned short. It may be necessary to include <sys/types.h>
?C: to get any typedef'ed information.
?C:.
?H:#define Mode_t $modetype /* file mode parameter for system calls */
?H:.
: see what type is used for mode_t
set mode_t modetype int stdio.h sys/types.h
eval $typedef
dflt="$modetype"
echo " "
rp="What type is used for file modes?"
./myread
modetype="$ans"

```

Found in path(s):

```

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/modetype.U

```

No license file was found, but licenses were detected in source scan.

```

?RCS: $Id$
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: $Log: Whoa.U,v $
?RCS: Revision 3.0.1.2 1997/02/28 15:21:21 ram
?RCS: patch61: whoa script now starts with leading "startsh"
?RCS:
?RCS: Revision 3.0.1.1 1994/10/29 16:02:01 ram
?RCS: patch36: added ?F: line for metalint file checking

```

```

?RCS:
?RCS: Revision 3.0 1993/08/18 12:05:19 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?X:
?X: This unit produces a bit of shell code that must be dotted in in order
?X: to warn the user in case a change into a variable is noticed.
?X:
?X: To use this
unit, $was must hold the old value that has changed. Upon
?X: exit, the two variables $td and $tu are set to the correct value for
?X: respectively defining or undefining a variable. For instance, if $was was
?X: $undef, but now $var is $define, after calling . whoa, you should use
?X: eval "$var=\$tu" to finally set $var to the correct value. See unit Inlibc.
?X:
?MAKE:Whoa: Myread startsh hint
?MAKE: -pick add $@ %<
?F:./whoa
?T:var was
?LINT:change td tu
: set up the script used to warn in case of inconsistency
cat <<EOS >whoa
$startsh
EOS
cat <<'EOOSC' >>whoa
dflt=y
echo " "
echo "*** WHOA THERE!!! ***" >&4
echo " The $hint value for \$$var on this machine was \"\$was\"!" >&4
rp=" Keep the $hint value?"
./myread
case "$ans" in
y) td=$was; tu=$was;;
esac
EOOSC

```

Found in path(s):

```

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/Whoa.U

```

No license file was found, but licenses were detected in source scan.

```

?RCS: $Id: sitelib.U,v 1.1 1999/07/08 18:32:57 doughera Exp doughera $

```

```

?RCS:

```

```

?RCS: Copyright (c) 1996-1998, Andy Dougherty

```

```

?RCS: Copyright (c) 1991-1993, Raphael Manfredi

```

```

?RCS:

```

```

?RCS: You may redistribute only under the terms of the Artistic License,

```

```

?RCS: as specified in the README file that comes with the distribution.

```

?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 3.0.

?RCS:
?RCS: \$Log: sitelib.U,v \$
?RCS: Revision 1.1 1999/07/08 18:32:57 doughera
?RCS: Initial revision
?RCS:
?RCS: Revision 3.0.1.1 1997/02/28 16:21:35 ram
?RCS: patch61: created
?RCS:

?MAKE:sitelib sitelibexp installsitelib sitelib_stem: cat Getfile Oldconfig \
Setprefixvar Prefixit package version sed installstyle siteprefix
?MAKE: -pick add \$@ %<
?Y:TOP
?D:sitelib="
?S:sitelib:
?S: This variable contains the
eventual value of the SITELIB symbol,
?S: which is the name of the private library for this package. It may
?S: have a ~ on the front. It is up to the makefile to eventually create
?S: this directory while performing installation (with ~ substitution).
?S: The standard distribution will put nothing in this directory.
?S: After perl has been installed, users may install their own local
?S: architecture-independent modules in this directory with
?S: MakeMaker Makefile.PL
?S: or equivalent. See INSTALL for details.
?S:.
?D:sitelibexp="
?S:sitelibexp:
?S: This variable is the ~name expanded version of sitelib, so that you
?S: may use it directly in Makefiles or shell scripts.
?S:.
?D:installsitelib="
?S:installsitelib:
?S: This variable is really the same as sitelibexp but may differ on
?S: those systems using AFS. For extra portability, only this variable
?S: should be used in makefiles.
?S:.
?S:sitelib_stem:
?S: This variable is \$sitelibexp with any trailing version-specific component
?S: removed.
The elements in inc_version_list (inc_version_list.U) can
?S: be tacked onto this variable to generate a list of directories to search.
?S:.
?C:SITELIB:
?C: This symbol contains the name of the private library for this package.
?C: The library is private in the sense that it needn't be in anyone's

?C: execution path, but it should be accessible by the world. The program
?C: should be prepared to do ~ expansion.
?C: The standard distribution will put nothing in this directory.
?C: After perl has been installed, users may install their own local
?C: architecture-independent modules in this directory with
?C: MakeMaker Makefile.PL
?C: or equivalent. See INSTALL for details.
?C:.
?C:SITELIB_EXP:
?C: This symbol contains the ~name expanded version of SITELIB, to be used
?C: in programs that are not prepared to deal with ~ expansion at run-time.
?C:.
?C:SITELIB_STEM:
?C: This define is SITELIB_EXP with any trailing version-specific component
?C: removed. The elements in
inc_version_list (inc_version_list.U) can
?C: be tacked onto this variable to generate a list of directories to search.
?C:.
?H:#define SITELIB "\$sitelib" /**/
?H:#define SITELIB_EXP "\$sitelibexp" /**/
?H:#define SITELIB_STEM "\$sitelib_stem" /**/
?H:.
?T:prog
?LINT:change prefixvar
?LINT:set installsitelib
?LINT:set sitelib
?LINT:set sitelibexp
: determine where site specific libraries go.
: Usual default is /usr/local/lib/perl5/site_perl/\$version
: The default "style" setting is made in installstyle.U
: XXX No longer works with Prefixit stuff.
?X: remove any trailing -3.0 or other version identification
prog=`echo \$package | \$sed 's/-*[0-9.]*\$//'
case "\$sitelib" in
") case "\$installstyle" in
lib/perl5) dflt=\$siteprefix/lib/\$package/site_\$prog/\$version ;;
*) dflt=\$siteprefix/lib/site_\$prog/\$version ;;
esac
;;
*) dflt="\$sitelib"
;;
esac
\$cat <<EOM

The installation process will create a directory for
site-specific extensions and modules. Most users find it convenient
to place

all site-specific files in this directory rather than in the main distribution directory.

EOM

fn=d~+

rp='Pathname for the site-specific library files?'

./getfile

prefixvar=sitelib

./setprefixvar

sitelib_stem=`echo "\$sitelibexp" | sed "s,/\$version\$,,"`

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/installdirs/sitelib.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 2000 Jarkko Hietaniemi

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?MAKE:d_frexp! Inlibc

?MAKE: -pick add \$@ %<

?S:d_frexp!

?S: This variable conditionally defines the HAS_FREXP symbol, which

?S: indicates to the C program that the frexp() routine is available.

?S:.

?C:HAS_FREXP!

?C: This symbol, if defined, indicates that the frexp routine is

?C: available to break a long double floating-point number into

?C: a normalized fraction and an integral power of 2.

?C:.

?H:#\$d_frexp! HAS_FREXP! /**/

?H:.

?LINT:set d_frexp!

: see if frexp exists

set frexp d_frexp!

eval \$inlibc

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_frexp!.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1999, Jarkko Hietaniemi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 3.0.
?RCS:
?MAKE:d_timer_delete: Inlibc
?MAKE: -pick add \$@ %<
?S:d_timer_delete:
?S: This variable conditionally defines HAS_TIMER_DELETE if timer_delete()
?S: is available to delete a POSIX timer.
?S:.
?C:HAS_TIMER_DELETE:
?C: This symbol, if defined, indicates that the timer_delete system call is
?C: available to delete a POSIX timer.
?C:.
?H:#\$d_timer_delete HAS_TIMER_DELETE /**/
?H:.
?LINT:set d_timer_delete
: see if timer_delete exists
set timer_delete d_timer_delete
eval \$inlibc

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_timer_delete.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_mbstowcs.U 1 2006-08-24 12:32:52Z rmanfredi \$
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: \$Log: d_mbstowcs.U,v \$
?RCS: Revision 3.0 1993/08/18 12:06:29 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:d_mbstowcs: Inlibc
?MAKE: -pick add \$@ %<
?S:d_mbstowcs:
?S: This variable conditionally defines the HAS_MBSTOWCS symbol, which

?S: indicates to the C program that the mbstowcs() routine is available

?S: to convert a multibyte string into a wide character string.

?S:.

?C:HAS_MBSTOWCS (MBSTOWCS):

?C: This symbol, if defined, indicates

that the mbstowcs routine is

?C: available to convert a multibyte string into a wide character string.

?C:.

?H:#\$d_mbstowcs HAS_MBSTOWCS /**/

?H:.

?LINT:set d_mbstowcs

: see if mbstowcs exists

set mbstowcs d_mbstowcs

eval \$inlibc

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/d_mbstowcs.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1999, Jarkko Hietaniemi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 3.0.

?RCS:

?MAKE:d_sched_setparam: Inlibc

?MAKE: -pick add \$@ %<

?S:d_sched_setparam:

?S: This variable conditionally defines HAS_SCHED_SETPARAM if

?S: sched_setparam() is available to set the scheduling parameters.

?S:.

?C:HAS_SCHED_SETPARAM:

?C: This symbol, if defined, indicates that the sched_setparam

?C: system call is available to set the scheduling parameters.

?C:.

?H:#\$d_sched_setparam HAS_SCHED_SETPARAM /**/

?H:.

?LINT:set d_sched_setparam

: see if sched_setparam exists

set sched_setparam d_sched_setparam

eval \$inlibc

Found

in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_sched_setparam.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1999 Jarkko Hietaniemi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 3.0.

?RCS:

?MAKE:d_getspent: Inlibc

?MAKE: -pick add \$@ %<

?S:d_getspent:

?S: This variable conditionally defines HAS_GETSPENT if getspent() is

?S: available to retrieve SysV shadow password entries sequentially.

?S:.

?C:HAS_GETSPENT:

?C: This symbol, if defined, indicates that the getspent system call is

?C: available to retrieve SysV shadow password entries sequentially.

?C:.

?H:#\$d_getspent HAS_GETSPENT /**/

?H:.

?LINT:set d_getspent

: see if getspent exists

set getspent d_getspent

eval \$inlibc

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_getspent.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: Config_h.U,v \$

```

?RCS: Revision 3.0.1.5 1997/02/28 14:57:43 ram
?RCS: patch61: added support for src.U
?RCS:
?RCS: Revision 3.0.1.4 1995/09/25 09:10:49 ram
?RCS: patch59: commented the purpose of the #un-def directive
?RCS:
?RCS: Revision 3.0.1.3 1995/01/30 14:25:39 ram
?RCS: patch49: typo fixes in leading config.h comment (WED)
?RCS:
?RCS: Revision 3.0.1.2 1993/08/24 12:13:20 ram
?RCS: patch3: added TOP as a local shell temporary variable
?RCS:
?RCS: Revision 3.0.1.1 1993/08/19 06:42:20
ram
?RCS: patch1: leading config.sh searching was not aborting properly
?RCS:
?RCS: Revision 3.0 1993/08/18 12:04:47 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?X:
?X: This file ends up producing the config_h.SH script, which is run to produce
?X: the config.h file. The file ./Config_h below contains all the ?H: lines
?X: extracted out of all the units. Metaconfig itself adds the !GROK!THIS!.
?X: Note that this code isn't included into Configure, but must be shipped with.
?X:
?X: For those who wish to know why the file is config_h.SH instead of the more
?X: natural config.h.SH, well... it is to support systems like MS-DOG. Only one
?X: 'dot' is allowed within the file name, as it is part of the "extension" of
?X: the file. MS-DOG will not let you have two 'dots' because that would mean
?X: two "extensions".
?X:
?MAKE:Config_h: Id End Config_sh Obsol_h myuname cf_time cf_by package src
?MAKE: -pick c_h_weed $@ %<
?MAKE: -pick c_h_weed $@ ./Config_h
?MAKE: -pick
c_h_weed $@ ./Obsol_h
?T:CONFIG TOP
?LINT:unclosed !GROK!THIS!
?LINT:extern CONFIG_H CONFIG_SH
?LINT:change CONFIG_H CONFIG_SH
?LINT:nocomment
case "$CONFIG_SH" in
") CONFIG_SH=config.sh;;
esac
case "$CONFIG_H" in
") CONFIG_H=config.h;;
esac
case $CONFIG in

```

```

")
if test -f $CONFIG_SH; then TOP=.;
elif test -f ../$CONFIG_SH; then TOP=..;
elif test -f ../../$CONFIG_SH; then TOP=../../.;
elif test -f ../../../$CONFIG_SH; then TOP=../../../.;
elif test -f ../../../../$CONFIG_SH; then TOP=../../../../.;
else
  echo "Can't find $CONFIG_SH."; exit 1
fi
. $TOP/$CONFIG_SH
;;
esac
?X: Make sure we are in the directory where the .SH file is located.
case "$0" in
*/*) cd `expr X$0 : 'X\(.*/\)` ;;
esac
echo "Extracting $CONFIG_H (with variable substitutions)"
?X:
?X: Since we unconditionally translate leading #undef into /*#define, we're
?X: stuck when we really want to have a #undef in config.h. That's why there
?X: is provision here for #un-def, which is translated back into #undef after
?X:
all original #undef have been processed.
?X:
?X: Previously, we changed all
?X: #undef FOO /**/
?X: into
?X: /*#define FOO /**/
?X: The xlc compiler (available on IBM's AIX) complains that this is
?X: an illegal attempt to write a nested comment, and warns against it.
?X: There's apparently no way to shut the compiler up, either.
?X: This sed command from Hallvard B Furuseth <h.b.furuseth@usit.uio.no>
?X: changes it to
?X: /*#define FOO / **/
sed <<!GROK!THIS!>$CONFIG_H -e 's!^#undef\(.*/\)*!\^*#define\1 \!' -e 's!^#un-def!#undef!'
/*
* This file was produced by running the config_h.SH script, which
* gets its values from $CONFIG_SH, which is generally produced by
* running Configure.
*
* Feel free to modify any of this as the need arises. Note, however,
* that running config_h.SH again will wipe out any changes you've made.
* For a more permanent change edit $CONFIG_SH and rerun config_h.SH.
*
*\$Id: Config_h.U 1 2006-08-24 12:32:52Z rmanfredi $
*/
/*

```

```
* Package name
  : $package
* Source directory : $src
* Configuration time: $cf_time
* Configured by   : $cf_by
* Target system   : $myuname
*/
```

```
#ifndef _config_h_
#define _config_h_
```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/Config_h.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id$
```

```
?RCS:
```

```
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
```

```
?RCS:
```

```
?RCS: You may redistribute only under the terms of the Artistic License,
```

```
?RCS: as specified in the README file that comes with the distribution.
```

```
?RCS: You may reuse parts of this distribution only within the terms of
```

```
?RCS: that same Artistic License; a copy of which may be found at the root
```

```
?RCS: of the source tree for dist 4.0.
```

```
?RCS:
```

```
?RCS: $Log: scriptdir.U,v $
```

```
?RCS: Revision 3.0.1.3 1995/09/25 09:17:15 ram
```

```
?RCS: patch59: unit is now forced to the top of Configure, if possible
```

```
?RCS:
```

```
?RCS: Revision 3.0.1.2 1995/01/30 14:46:13 ram
```

```
?RCS: patch49: can now handle installation prefix changes (from WED)
```

```
?RCS:
```

```
?RCS: Revision 3.0.1.1 1994/08/29 16:32:04 ram
```

```
?RCS: patch32: now uses installation prefix
```

```
?RCS:
```

```
?RCS: Revision 3.0 1993/08/18 12:09:45 ram
```

```
?RCS: Baseline for dist 3.0 netwide release.
```

```
?RCS:
```

```
?MAKE:scriptdir scriptdirexp installscript:
```

```
afs cat test Getfile Loc \
```

```
Oldconfig +bin Prefixit prefixexp Prefixup
```

```
?MAKE: -pick add $@ %<
```

```
?Y:TOP
```

```
?S:scriptdir:
```

```
?S: This variable holds the name of the directory in which the user wants
```

```
?S: to put publicly scripts for the package in question. It is either
```

```
?S: the same directory as for binaries, or a special one that can be
```

?S: mounted across different architectures, like /usr/share. Programs
 ?S: must be prepared to deal with ~name expansion.
 ?S:.
 ?S:scriptdirexp:
 ?S: This variable is the same as scriptdir, but is filename expanded
 ?S: at configuration time, for programs not wanting to bother with it.
 ?S:.
 ?S:installscript:
 ?S: This variable is usually the same as scriptdirexp, unless you are on
 ?S: a system running AFS, in which case they may differ slightly. You
 ?S: should always use this variable within your makefiles for portability.
 ?S:.
 ?C:SCRIPTDIR:
 ?C: This symbol holds the name of the directory in which the user wants
 ?C: to put publicly executable scripts for the
 package in question. It
 ?C: is often a directory that is mounted across diverse architectures.
 ?C: Programs must be prepared to deal with ~name expansion.
 ?C:.
 ?C:SCRIPTDIR_EXP:
 ?C: This is the same as SCRIPTDIR, but is filename expanded at
 ?C: configuration time, for use in programs not prepared to do
 ?C: ~name substitutions at run-time.
 ?C:.
 ?H:#define SCRIPTDIR "\$scriptdir" /**/
 ?H:#define SCRIPTDIR_EXP "\$scriptdirexp" /**/
 ?H:.
 : determine where public executable scripts go
 set scriptdir scriptdir
 eval \$prefixit
 case "\$scriptdir" in
 ")
 dflt="\$bin"
 : guess some guesses
 \$test -d /usr/share/scripts && dflt=/usr/share/scripts
 \$test -d /usr/share/bin && dflt=/usr/share/bin
 \$test -d /usr/local/script && dflt=/usr/local/script
 \$test -d \$prefixexp/script && dflt=\$prefixexp/script
 set dflt
 eval \$prefixup
 ;;
 *) dflt="\$scriptdir"
 ;;
 esac
 \$cat <<EOM

Some installations have a separate directory just for executable scripts so
 that they can mount it across multiple architectures but

keep the scripts in one spot. You might, for example, have a subdirectory of /usr/share for this. Or you might just lump your scripts in with all your other executables.

```
EOM
fn=d~
rp='Where do you keep publicly executable scripts?'
./getfile
if $test "X$ansexp" != "X$scriptdirexp"; then
installscript="
fi
scriptdir="$ans"
scriptdirexp="$ansexp"
if $afs; then
$cat <<EOM
```

Since you are running AFS, I need to distinguish the directory in which scripts reside from the directory in which they are installed (and from which they are presumably copied to the former directory by occult means).

```
EOM
case "$installscript" in
") dflt=`echo $scriptdirexp | sed 's#^/afs/#/afs/#'`;
*) dflt="$installscript";
esac
fn=de~
rp='Where will public scripts be installed?'
./getfile
installscript="$ans"
else
installscript="$scriptdirexp"
fi
```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/scriptdir.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: d_msgctl.U 1 2006-08-24 12:32:52Z rmanfredi $
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
```

?RCS: \$Log: d_msgctl.U,v \$
 ?RCS: Revision 3.0 1993/08/18 12:06:38 ram
 ?RCS: Baseline for dist 3.0 netwide release.
 ?RCS:
 ?MAKE:d_msgctl: Inlibc
 ?MAKE: -pick add \$@ %<
 ?S:d_msgctl:
 ?S: This variable conditionally defines the HAS_MSGCTL symbol, which
 ?S: indicates to the C program that the msgctl() routine is available.
 ?S:.
 ?C:HAS_MSGCTL:
 ?C: This symbol, if defined, indicates that the msgctl() routine is
 ?C: available to perform message control operations.
 ?C:.
 ?H:#\$d_msgctl
 HAS_MSGCTL /**/
 ?H:.
 ?LINT:set d_msgctl
 : see if msgctl exists
 set msgctl d_msgctl
 eval \$inlibc

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/d_msgctl.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: otherlibdirs.U,v 1.1 1999/07/08 18:32:57 doughera Exp doughera \$
 ?RCS:
 ?RCS: Copyright (c) 1999-2000, Andy Dougherty
 ?RCS:
 ?RCS: You may redistribute only under the terms of the Artistic License,
 ?RCS: as specified in the README file that comes with the distribution.
 ?RCS: You may reuse parts of this distribution only within the terms of
 ?RCS: that same Artistic License; a copy of which may be found at the root
 ?RCS: of the source tree for dist 3.0.
 ?RCS:
 ?RCS: \$Log: otherlibdirs.U,v \$
 ?RCS: Revision 1.1 1999/07/08 18:32:57 doughera
 ?RCS: Initial revision
 ?RCS:
 ?RCS: Revision 1.1 1999/07/08 18:20:26 doughera
 ?RCS: Initial revision
 ?RCS:
 ?RCS:
 ?MAKE:otherlibdirs d_perl_otherlibdirs: Myread cat sitelib sitearch \
 vendorarch vendorlib Setvar
 ?MAKE: -pick add \$@ %<

```

?Y:TOP
?S:otherlibdirs:
?S: This variable contains a colon-separated set of paths for the perl
?S: binary to search for additional library files
or modules.
?S: These directories will be tacked to the end of @INC.
?S: Perl will automatically search below each path for version-
?S: and architecture-specific directories. See inc_version_list
?S: for more details.
?S: A value of '' means 'none' and is used to preserve this value
?S: for the next run through Configure.
?S:.
?S:d_perl_otherlibdirs:
?S: This variable conditionally defines PERL_OTHERLIBDIRS, which
?S: contains a colon-separated set of paths for the perl binary to
?S: include in @INC. See also otherlibdirs.
?S:.
?C:PERL_OTHERLIBDIRS:
?C: This variable contains a colon-separated set of paths for the perl
?C: binary to search for additional library files or modules.
?C: These directories will be tacked to the end of @INC.
?C: Perl will automatically search below each path for version-
?C: and architecture-specific directories. See PERL_INC_VERSION_LIST
?C: for more details.
?C:.
?H:#$d_perl_otherlibdirs PERL_OTHERLIBDIRS "$otherlibdirs" /**/
?H:.
?LINT: set d_perl_otherlibdirs
:
Final catch-all directories to search
$cat <<EOM

```

Lastly, you can have perl look in other directories for extensions and modules in addition to those already specified.

These directories will be searched after

\$sitearch

\$sitelib

EOM

```

test X"$vendorlib" != "X" && echo ' ' $vendorlib
test X"$vendorarch" != "X" && echo ' ' $vendorarch
echo ' '
case "$otherlibdirs" in
'| ') dflt='none' ;;
*) dflt="$otherlibdirs" ;;
esac
$cat <<EOM

```

Enter a colon-separated set of extra paths to include in perl's @INC search path, or enter 'none' for no extra paths.

EOM

rp='Colon-separated list of additional directories for perl to search?'

```
./myread
case "$ans" in
'|"|none) otherlibdirs=' ' ' ;;
*) otherlibdirs="$ans" ;;
esac
case "$otherlibdirs" in
'|') val=$undef ;;
*) val=$define ;;
esac
set d_perl_otherlibdirs
eval $setvar
```

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/installdirs/otherlibdirs.U

No license file was found, but licenses were detected in source scan.

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?MAKE:d_nearbyint: Inlibc

?MAKE: -pick add \$@ %<

?S:d_nearbyint:

?S: This variable conditionally defines HAS_NEARBYINT if nearbyint()

?S: is available to return the integral value closest to (according to

?S: the current rounding mode) to x.

?S:.

?C:HAS_NEARBYINT:

?C: This symbol, if defined, indicates that the nearbyint routine is

?C: available to return the integral value closest to (according to

?C: the current rounding mode) to x.

?C:.

?H:#\$d_nearbyint HAS_NEARBYINT /**/

?H:.

?LINT:set d_nearbyint

: see if nearbyint exists

set nearbyint d_nearbyint

eval \$inlibc

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_nearbyint.U

No license file was found, but licenses were detected in source scan.

```

?RCS: $Id$
?RCS:
?RCS: Copyright (c) 1999, Jarkko Hietaniemi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 3.0.
?RCS:
?MAKE:d_mq_notify: Inlibc
?MAKE: -pick add $@ %<
?S:d_mq_notify:
?S: This variable conditionally defines HAS_MQ_NOTIFY if mq_notify() is
?S: available to ask for a notification from a POSIX message queue.
?S:.
?C:HAS_MQ_NOTIFY:
?C: This symbol, if defined, indicates that the mq_notify system call is
?C: available to ask for a notification from a POSIX message queue.
?C:.
?H:#$d_mq_notify HAS_MQ_NOTIFY /**/
?H:.
?LINT:set d_mq_notify
: see if mq_notify exists
set mq_notify d_mq_notify
eval $inlibc

```

Found in path(s):

```

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/perl/d_mq_notify.U

```

No license file was found, but licenses were detected in source scan.

```

?RCS: $Id: d_vfork.U,v 3.0.1.6 1994/08/29 16:18:21 ram Exp $
?RCS:
?RCS: Copyright (c) 1991-1993, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 3.0.
?RCS:
?RCS: $Log: d_vfork.U,v $
?RCS: Revision 3.0.1.6 1994/08/29 16:18:21 ram
?RCS: patch32: set default to 'y' the first time
?RCS:
?RCS: Revision 3.0.1.5 1994/06/20 06:59:14 ram
?RCS: patch30: usevfork was not always properly set

```

?RCS:
?RCS: Revision 3.0.1.4 1994/05/13 15:20:56 ram
?RCS: patch27: modified to avoid spurious Whoa warnings (ADO)
?RCS:
?RCS: Revision 3.0.1.3 1994/05/06 14:59:09 ram
?RCS: patch23: now explicitly ask whether vfork() should be used
(ADO)
?RCS:
?RCS: Revision 3.0.1.2 1993/10/16 13:49:39 ram
?RCS: patch12: added magic for vfork()
?RCS:
?RCS: Revision 3.0.1.1 1993/09/13 16:06:57 ram
?RCS: patch10: removed automatic remapping of vfork on fork (WAD)
?RCS: patch10: added compatibility code for older config.sh (WAD)
?RCS:
?RCS: Revision 3.0 1993/08/18 12:07:55 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:d_vfork usevfork d_pseudofork: Inlibc Myread Oldconfig Setvar
?MAKE: -pick add \$@ %<
?S:d_vfork:
?S: This variable conditionally defines the HAS_VFORK symbol, which
?S: indicates the vfork() routine is available.
?S:.
?S:usevfork:
?S: This variable is set to true when the user accepts to use vfork.
?S: It is set to false when no vfork is available or when the user
?S: explicitly requests not to use vfork.
?S:.
?S:d_pseudofork:
?S: This variable conditionally defines the HAS_PSEUDOFORK symbol,
?S: which indicates that an emulation of the fork routine is available.
?S:.
?C:HAS_VFORK (VFORK):
?C: This
symbol, if defined, indicates that vfork() exists.
?C:.
?H:#\$d_vfork HAS_VFORK /**/
?H:.
?C:HAS_PSEUDOFORK:
?C: This symbol, if defined, indicates that an emulation of the
?C: fork routine is available.
?C:.
?H:#\$d_pseudofork HAS_PSEUDOFORK /**/
?H:.
?M:vfork: HAS_VFORK
?M:#ifndef HAS_VFORK
?M:#define vfork fork

```

?M:#endif
?M:.
?T:d_hvfork
: backward compatibility for d_hvfork
if test X$d_hvfork != X; then
  d_vfork="$d_hvfork"
  d_hvfork="
fi
?X:=====
: see if there is a vfork
val="
set vfork val
eval $inlibc

d_pseudofork=$undef

: Ok, but do we want to use it. vfork is reportedly unreliable in
: perl on Solaris 2.x, and probably elsewhere.
case "$val" in
$define)
  echo " "
  case "$usevfork" in
  false) dflt='n';;
  *) dflt='y';;
  esac
  cat <<'EOM'

```

Perl can only use a vfork() that doesn't suffer from strict restrictions on calling functions or modifying global data in the child. For example, glibc-2.1 contains such a vfork() that is unsuitable. If your system provides a proper fork() call, chances are that you do NOT want perl to use vfork().

```

EOM
rp="Do you still want to use vfork()?"
./myread
case "$ans" in
y|Y) ;;
*)
  echo "Ok, we won't use vfork()."
  val="$undef"
  ;;
esac
;;
esac
;;
esac
?X:
?X: Only set it when final value is known to avoid spurious Whoa's

```

?X: Then set usevfork accordingly to the current value, for next run

?X:

```
set d_vfork
```

```
eval $setvar
```

```
case "$d_vfork" in
```

```
$define) usevfork='true';;
```

```
*) usevfork='false';;
```

```
esac
```

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/modified/d_vfork.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?MAKE:i_poll: Inhdr

?MAKE: -pick add \$@ %<

?S:i_poll:

?S: This variable conditionally defines the I_POLL symbol, which

?S: indicates to the C program that it should include <poll.h>.

?S:.

?C:I_POLL:

?C: This symbol, if defined, indicates that the program may include

?C: <poll.h>. If there is no <poll.h>, then you may check I_SYS_POLL

?C: instead to see whether there is a <sys/poll.h> to include.

?C:.

?H:#\$i_poll I_POLL /**/

?H:.

?LINT:set i_poll

: see if there is a poll.h file

```
set poll.h i_poll
```

```
eval $inhdr
```

Found

in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/i_poll.U

No license file was found, but licenses were detected in source scan.

```

?RCS: $Id: i_sysun.U 1 2006-08-24 12:32:52Z rmanfredi $
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: $Log: i_sysun.U,v $
?RCS: Revision 3.0 1993/08/18 12:08:42 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?X:
?X: This unit looks wether <sys/un.h> is available or not
?X:
?MAKE:i_sysun: Inhdr
?MAKE: -pick add $@ %<
?S:i_sysun:
?S: This variable conditionally defines I_SYS_UN, which indicates
?S: to the C program that it should include <sys/un.h> to get UNIX
?S: domain socket definitions.
?S:.
?C:I_SYS_UN:
?C: This symbol, if defined, indicates
?C: to the C program that it should
?C: include <sys/un.h> to get UNIX domain socket definitions.
?C:.
?H:#$i_sysun I_SYS_UN /**/
?H:.
?LINT:set i_sysun
: see if this is a sys/un.h system
set sys/un.h i_sysun
eval $inhdr

```

Found in path(s):

```

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/i_sysun.U

```

No license file was found, but licenses were detected in source scan.

```

?RCS: Copyright (c) 2012 H.Merijn Brand
?RCS:
?RCS: You may distribute under the terms of either the GNU General Public
?RCS: License or the Artistic License, as specified in the README file.
?RCS:
?MAKE:d_strptime: Inlibc
?MAKE: -pick add $@ %<

```

?S:d_strptime:
?S: This variable conditionally defines the HAS_STRPTIME symbol, which
?S: indicates to the C program that the strptime() routine is available.
?S:.
?C:HAS_STRPTIME:
?C: This symbol, if defined, indicates that the strptime routine is
?C: available to set process title.
?C:.
?H:#\$d_strptime HAS_STRPTIME /**/
?H:.
?LINT:set d_strptime
: see if strptime exists
set strptime d_strptime
eval \$inlibc

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_strptime.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: Tye McQueen <tye@metronet.com> added safe setuid script checks.
?RCS:
?RCS: \$Log: d_dosuid.U,v \$
?RCS: Revision 3.0.1.2 1997/02/28 15:33:03 ram
?RCS: patch61: moved unit to TOP via a ?Y: layout directive
?RCS: patch61: tell them /dev/fd is not about floppy disks
?RCS:
?RCS: Revision 3.0.1.1 1994/10/29 16:12:08 ram
?RCS: patch36: added checks for secure setuid scripts (Tye McQueen)
?RCS:
?RCS: Revision 3.0 1993/08/18 12:05:55 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:d_dosuid
d_suidsafes: cat contains ls rm test Myread Setvar \
Oldconfig Guess package hint
?MAKE: -pick add \$@ %<
?S:d_suidsafes:

```

?S: This variable conditionally defines SETUID_SCRIPTS_ARE_SECURE_NOW
?S: if setuid scripts can be secure. This test looks in /dev/fd/.
?S:.
?S:d_dosuid:
?S: This variable conditionally defines the symbol DOSUID, which
?S: tells the C program that it should insert setuid emulation code
?S: on hosts which have setuid #! scripts disabled.
?S:.
?C:SETUID_SCRIPTS_ARE_SECURE_NOW:
?C: This symbol, if defined, indicates that the bug that prevents
?C: setuid scripts from being secure is not present in this kernel.
?C:.
?C:DOSUID:
?C: This symbol, if defined, indicates that the C program should
?C: check the script that it is executing for setuid/setgid bits, and
?C: attempt to emulate setuid/setgid on systems that have disabled
?C: setuid #! scripts because the kernel can't do it securely.
?C: It is up to the package designer to make sure that this emulation
?C: is done securely.
    Among other things, it should do an fstat on
?C: the script it just opened to make sure it really is a setuid/setgid
?C: script, it should make sure the arguments passed correspond exactly
?C: to the argument on the #! line, and it should not trust any
?C: subprocesses to which it must pass the filename rather than the
?C: file descriptor of the script to be executed.
?C:.
?H:#$d_suidsafes SETUID_SCRIPTS_ARE_SECURE_NOW /**/
?H:#$d_dosuid DOSUID /**/
?H:.
?Y:TOP
?F:!reflect
?LINT: set d_suidsafes
?LINT: set d_dosuid
: see if setuid scripts can be secure
$cat <<EOM

```

Some kernels have a bug that prevents setuid #! scripts from being secure. Some sites have disabled setuid #! scripts because of this.

First let's decide if your kernel supports secure setuid #! scripts.
(If setuid #! scripts would be secure but have been disabled anyway,
don't say that they are secure if asked.)

EOM

```

val="$undef"
if $test -d /dev/fd; then
echo "#!$ls" >reflect

```

```

chmod +x,u+s reflect
./reflect >flect
2>&1
if $contains "/dev/fd" flect >/dev/null; then
  echo "Congratulations, your kernel has secure setuid scripts!" >&4
  val="$define"
else
  $cat <<EOM

```

If you are not sure if they are secure, I can check but I'll need a username and password different from the one you are using right now. If you don't have such a username or don't want me to test, simply enter 'none'.

EOM

```

rp='Other username to test security of setuid scripts with?'
dflt='none'
. ./myread
case "$ans" in
n|none)
  case "$d_suidsafesafe" in
*) echo "I'll assume setuid scripts are *not* secure." >&4
  dflt=n;;
"$undef")
  echo "Well, the $hint value is *not* secure." >&4
  dflt=n;;
*) echo "Well, the $hint value *is* secure." >&4
  dflt=y;;
esac
;;
*)
$rm -f reflect flect
echo "#!$ls" >reflect
chmod +x,u+s reflect
echo >flect
chmod a+w flect
echo "'su' will (probably) prompt you for '$ans's password.'"
su $ans -c './reflect >flect'
if $contains "/dev/fd" flect
>/dev/null; then
  echo "Okay, it looks like setuid scripts are secure." >&4
  dflt=y
else
  echo "I don't think setuid scripts are secure." >&4
  dflt=n
fi
;;
esac
rp='Does your kernel have *secure* setuid scripts?'

```

```

./myread
case "$ans" in
[yY]*) val="$define";;
*) val="$undef";;
esac
fi
else
echo "I don't think setuid scripts are secure (no /dev/fd directory)." >&4
echo "(That's for file descriptors, not floppy disks.)"
val="$undef"
fi
set d_suidsafe
eval $setvar

```

```
$rm -f reflect flect
```

```

: now see if they want to do setuid emulation
echo " "
val="$undef"
case "$d_suidsafe" in
"$define")
val="$undef"
echo "No need to emulate SUID scripts since they are secure here." >& 4
;;
*)

```

```
$cat <<EOM
```

Some systems have disabled setuid scripts, especially systems where setuid scripts cannot be secure. On systems where setuid scripts have been disabled, the setuid/setgid bits on scripts are currently useless. It is possible for \$package to detect those bits and emulate setuid/setgid in a secure fashion. This emulation will only work if setuid scripts have been disabled in your kernel.

```
EOM
```

```

case "$d_dosuid" in
"$define") dflt=y ;;
*) dflt=n ;;
esac
rp="Do you want to do setuid/setgid emulation?"
./myread
case "$ans" in
[yY]*) val="$define";;
*) val="$undef";;
esac
;;
esac
set d_dosuid

```

eval \$setvar

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/d_dosuid.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1999, Jarkko Hietaniemi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 3.0.

?RCS:

?MAKE:d_clock_gettime: Inlibc

?MAKE: -pick add \$@ %<

?S:d_clock_gettime:

?S: This variable conditionally defines HAS_CLOCK_GETTIME

?S: if clock_gettime() is available to get the time of a POSIX clock.

?S:.

?C:HAS_CLOCK_GETTIME:

?C: This symbol, if defined, indicates that the clock_gettime

?C: system call is available to get the time of a POSIX clock.

?C:.

?H:#\$d_clock_gettime HAS_CLOCK_GETTIME /**/

?H:.

?LINT:set d_clock_gettime

: see if clock_gettime exists

set clock_gettime d_clock_gettime

eval \$inlibc

Found in path(s):

*

/opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_clock_gettime.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: i_crypt.U,v \$

?RCS:

?RCS: Copyright (c) 2002 Jarkko Hietaniemi

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?MAKE:i_crypt: Inhdr Hasfield

?MAKE: -pick add \$@ %<
?S:i_crypt:
?S: This variable conditionally defines the I_CRYPT symbol, and indicates
?S: whether a C program should include <crypt.h>.
?S:.
?C:I_CRYPT:
?C: This symbol, if defined, indicates that <crypt.h> exists and
?C: should be included.
?C:.
?H:#\$i_crypt I_CRYPT /**/
?H:.
?LINT:set i_crypt
: see if this is a crypt.h system
set crypt.h i_crypt
eval \$inhdr

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/i_crypt.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_stdstdio.U,v 3.0.1.3 1997/02/28 15:46:32 ram Exp \$
?RCS:
?RCS: Copyright (c) 1991-1993, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 3.0.
?RCS:
?RCS: Original Author: Tye McQueen <tye@metronet.com>
?RCS:
?RCS: \$Log: d_stdstdio.U,v \$
?RCS: Revision 3.0.1.3 1997/02/28 15:46:32 ram
?RCS: patch61: merged with perl5's unit
?RCS:
?RCS: Revision 3.0.1.2 1995/07/25 14:06:54 ram
?RCS: patch56: typo fix on ?C: line for FILE_bufsiz
?RCS: patch56: fixed unbalanced parenthesis (ADO)
?RCS: patch56: check whether FILE_cnt and FILE_ptr can be assigned to (ADO)
?RCS:
?RCS: Revision 3.0.1.1 1995/05/12 12:12:11 ram
?RCS:
patch54: complete rewrite by Tye McQueen to fit modern systems
?RCS:
?RCS: Revision 3.0 1993/08/18 12:07:31 ram
?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?MAKE:d_stdstdio d_stdiobase stdio_ptr stdio_cnt \
d_stdio_ptr_lval_sets_cnt d_stdio_ptr_lval_nochange_cnt stdio_base \
stdio_bufsiz d_stdio_cnt_lval d_stdio_ptr_lval stdio_filbuf: cat \
Compile contains rm_try d_gnulibc gnuilibc_version i_stdlib \
Setvar Findhdr Oldconfig run to

?MAKE: -pick weed \$@ %<

?S:d_stdstdio:

?S: This variable conditionally defines USE_STDIO_PTR if this system
?S: has a FILE structure declaring usable _ptr and _cnt fields (or
?S: equivalent) in stdio.h.

?S:.

?S:stdio_ptr:

?S: This variable defines how, given a FILE pointer, fp, to access the
?S: _ptr field (or equivalent) of stdio.h's FILE structure. This will
?S: be used to define the macro FILE_ptr(fp).

?S:.

?S:d_stdio_ptr_lval:

?S: This variable conditionally defines STDIO_PTR_LVALUE if the
?S: FILE_ptr macro can be used as an lvalue.

?S:.

?S:stdio_cnt:

?S: This
variable defines how, given a FILE pointer, fp, to access the
?S: _cnt field (or equivalent) of stdio.h's FILE structure. This will
?S: be used to define the macro FILE_cnt(fp).

?S:.

?S:d_stdio_cnt_lval:

?S: This variable conditionally defines STDIO_CNT_LVALUE if the
?S: FILE_cnt macro can be used as an lvalue.

?S:.

?S:d_stdio_ptr_lval_sets_cnt:

?S: This symbol is defined if using the FILE_ptr macro as an lvalue
?S: to increase the pointer by n has the side effect of decreasing the
?S: value of File_cnt(fp) by n.

?S:.

?S:d_stdio_ptr_lval_nochange_cnt:

?S: This symbol is defined if using the FILE_ptr macro as an lvalue
?S: to increase the pointer by n leaves File_cnt(fp) unchanged.

?S:.

?S:stdio_filbuf:

?S: This variable defines how, given a FILE pointer, fp, to tell
?S: stdio to refill its internal buffers (?). This will
?S: be used to define the macro FILE_filbuf(fp).

?S:.

?S:d_stdiobase:

?S: This variable conditionally defines USE_STDIO_BASE if this system
?S: has

a FILE structure declaring a usable `_base` field (or equivalent)

?S: in `stdio.h`.

?S:.

?S:`stdio_base`:

?S: This variable defines how, given a FILE pointer, `fp`, to access the

?S: `_base` field (or equivalent) of `stdio.h`'s FILE structure. This will

?S: be used to define the macro `FILE_base(fp)`.

?S:.

?S:`stdio_bufsiz`:

?S: This variable defines how, given a FILE pointer, `fp`, to determine

?S: the number of bytes store in the I/O buffer pointer to by the

?S: `_base` field (or equivalent) of `stdio.h`'s FILE structure. This will

?S: be used to define the macro `FILE_bufsiz(fp)`.

?S:.

?C:`USE_STDIO_PTR ~ d_stdstdio (USE_STD_STDIO STDSTDIO)`:

?C: This symbol is defined if the `_ptr` and `_cnt` fields (or similar)

?C: of the `stdio` FILE structure can be used to access the `stdio` buffer

?C: for a file handle. If this is defined, then the `FILE_ptr(fp)`

?C: and `FILE_cnt(fp)` macros will also be defined and should be used

?C: to access these fields.

?C:.

?C:`FILE_ptr`:

?C: This macro is used to access the `_ptr`

?C: field (or equivalent) of the

?C: FILE structure pointed to by its argument. This macro will always be

?C: defined if `USE_STDIO_PTR` is defined.

?C:.

?C:`STDIO_PTR_LVALUE`:

?C: This symbol is defined if the `FILE_ptr` macro can be used as an

?C: lvalue.

?C:.

?C:`FILE_cnt`:

?C: This macro is used to access the `_cnt` field (or equivalent) of the

?C: FILE structure pointed to by its argument. This macro will always be

?C: defined if `USE_STDIO_PTR` is defined.

?C:.

?C:`STDIO_CNT_LVALUE`:

?C: This symbol is defined if the `FILE_cnt` macro can be used as an

?C: lvalue.

?C:.

?C:`STDIO_PTR_LVAL_SETS_CNT`:

?C: This symbol is defined if using the `FILE_ptr` macro as an lvalue

?C: to increase the pointer by `n` has the side effect of decreasing the

?C: value of `File_cnt(fp)` by `n`.

?C:.

?C:`STDIO_PTR_LVAL_NOCHANGE_CNT`:

?C: This symbol is defined if using the `FILE_ptr` macro as an lvalue

?C: to increase the pointer by `n` leaves `File_cnt(fp)` unchanged.

?C:.

?C:FILE_filbuf:

?C: This macro is used to access the internal stdio
_filbuf function

?C: (or equivalent), if STDIO_CNT_LVALUE and STDIO_PTR_LVALUE
?C: are defined. It is typically either _filbuf or __filbuf.

?C: This macro will only be defined if both STDIO_CNT_LVALUE and
?C: STDIO_PTR_LVALUE are defined.

?C:.

```
?H:?d_stdstdio:#$d_stdstdio USE_STDIO_PTR /**/
?H:?d_stdstdio:#ifdef USE_STDIO_PTR
?H:#define FILE_ptr(fp) $stdio_ptr
?H:#$d_stdstdio_ptr_lval STDIO_PTR_LVALUE /**/
?H:#define FILE_cnt(fp) $stdio_cnt
?H:#$d_stdstdio_cnt_lval STDIO_CNT_LVALUE /**/
?H:#$d_stdstdio_ptr_lval_sets_cnt STDIO_PTR_LVAL_SETS_CNT /**/
?H:#$d_stdstdio_ptr_lval_nochange_cnt STDIO_PTR_LVAL_NOCHANGE_CNT /**/
?H:?FILE_filbuf:#if defined(STDIO_PTR_LVALUE) && defined(STDIO_CNT_LVALUE)
?H:?FILE_filbuf:#define FILE_filbuf(fp) $stdio_filbuf /**/
?H:?FILE_filbuf:#endif
?H:?d_stdstdio:#endif
?H:.
```

?W:d_stdstdio:FILE_ptr FILE_cnt FILE_filbuf

?C:USE_STDIO_BASE ~ d_stdibase:

?C: This symbol is defined if the _base field (or similar) of the
?C: stdio FILE structure can be used to access
the stdio buffer for
?C: a file handle. If this is defined, then the FILE_base(fp) macro
?C: will also be defined and should be used to access this field.
?C: Also, the FILE_bufsiz(fp) macro will be defined and should be used
?C: to determine the number of bytes in the buffer. USE_STDIO_BASE
?C: will never be defined unless USE_STDIO_PTR is.

?C:.

?C:FILE_base:

?C: This macro is used to access the _base field (or equivalent) of the
?C: FILE structure pointed to by its argument. This macro will always be
?C: defined if USE_STDIO_BASE is defined.

?C:.

?C:FILE_bufsiz:

?C: This macro is used to determine the number of bytes in the I/O
?C: buffer pointed to by _base field (or equivalent) of the FILE
?C: structure pointed to its argument. This macro will always be defined
?C: if USE_STDIO_BASE is defined.

?C:.

```
?H:?d_stdibase:#$d_stdibase USE_STDIO_BASE /**/
?H:?d_stdibase:#ifdef USE_STDIO_BASE
?H:#define FILE_base(fp) $stdio_base
?H:#define FILE_bufsiz(fp) $stdio_bufsiz
```

```

?H:?d_stdibase:#endif
?H:.
?W:d_stdibase:FILE_base
FILE_bufsiz
?T:ptr_lval cnt_lval filbuf xxx
?F:!try
?LINT:set d_stdstdio d_stdibase
: see if _ptr and _cnt from stdio act std
echo " "

if $contains '_lbfsize' `./findhdr stdio.h` >/dev/null 2>&1 ; then
echo "(Looks like you have stdio.h from BSD.)"
case "$stdio_ptr" in
") stdio_ptr='((fp)->_p)'
ptr_lval=$define
;;
*) ptr_lval=$d_stdio_ptr_lval;;
esac
case "$stdio_cnt" in
") stdio_cnt='((fp)->_r)'
cnt_lval=$define
;;
*) cnt_lval=$d_stdio_cnt_lval;;
esac
case "$stdio_base" in
") stdio_base='((fp)->_ub._base ? (fp)->_ub._base : (fp)->_bf._base)';;
esac
case "$stdio_bufsiz" in
") stdio_bufsiz='((fp)->_ub._base ? (fp)->_ub._size : (fp)->_bf._size)';;
esac
elif $contains '_IO_fpos_t' `./findhdr stdio.h` `./findhdr libio.h` >/dev/null 2>&1 ; then
echo "(Looks like you have stdio.h from Linux.)"
case "$stdio_ptr" in
") stdio_ptr='((fp)->_IO_read_ptr)'
ptr_lval=$define
;;
*) ptr_lval=$d_stdio_ptr_lval;;
esac
case "$stdio_cnt"
in
") stdio_cnt='((fp)->_IO_read_end - (fp)->_IO_read_ptr)'
cnt_lval=$undef
;;
*) cnt_lval=$d_stdio_cnt_lval;;
esac
case "$stdio_base" in
") stdio_base='((fp)->_IO_read_base)';;
esac

```

```

case "$stdio_bufsiz" in
") stdio_bufsiz=$((fp->_IO_read_end - (fp->_IO_read_base));;
esac
else
case "$stdio_ptr" in
") stdio_ptr='(fp->_ptr)'
ptr_lval=$define
;;
*) ptr_lval=$d_stdio_ptr_lval;;
esac
case "$stdio_cnt" in
") stdio_cnt='(fp->_cnt)'
cnt_lval=$define
;;
*) cnt_lval=$d_stdio_cnt_lval;;
esac
case "$stdio_base" in
") stdio_base='(fp->_base)';;
esac
case "$stdio_bufsiz" in
") stdio_bufsiz='(fp->_cnt + (fp->_ptr - (fp->_base)';;
esac
fi

```

```

: test whether _ptr and _cnt really work
echo "Checking how std your stdio is..." >&4
$cat >try.c <<EOP
#include <stdio.h>
#ifdef I_STDLIB
#include <stdlib.h>
#endif
#define FILE_ptr(fp) $stdio_ptr
#define FILE_cnt(fp) $stdio_cnt
int main() {
FILE *fp = fopen("try.c", "r");
char c =
getc(fp);
if (
18 <= FILE_cnt(fp) &&
strncmp(FILE_ptr(fp), "include <stdio.h>\n", 18) == 0
)
exit(0);
exit(1);
}
EOP
val="$undef"
set try

```

```

if eval $compile && $to try.c; then
if $run ./try; then
echo "Your stdio acts pretty std."
val="$define"
else
echo "Your stdio isn't very std."
fi
else
echo "Your stdio doesn't appear very std."
fi
$rm_try

# glibc 2.2.90 and above apparently change stdio streams so Perl's
# direct buffer manipulation no longer works. The Configure tests
# should be changed to correctly detect this, but until then,
# the following check should at least let perl compile and run.
# (This quick fix should be updated before 5.8.1.)
# To be defensive, reject all unknown versions, and all versions > 2.2.9.
# A. Dougherty, June 3, 2002.
case "$d_gnulibc" in
$define)
case "$gnulibc_version" in
2.[01]*) ;;
2.2) ;;
2.2.[0-9]) ;;
*) echo "But I will not snoop inside glibc $gnulibc_version stdio buffers."
val="$undef"
;;
esac
;;
esac
set d_stdstdio
eval
$setvar

@if STDIO_PTR_LVALUE || d_stdio_ptr_lval
: Can _ptr be used as an lvalue?
?X: Only makes sense if we have a known stdio implementation.
case "$d_stdstdio$d_ptr_lval" in
$define$define) val=$define ;;
*) val=$undef ;;
esac
set d_stdio_ptr_lval
eval $setvar
@end

@if STDIO_CNT_LVALUE || d_stdio_cnt_lval
: Can _cnt be used as an lvalue?

```

?X: Only makes sense if we have a known stdio implementation.

```
case "$d_stdstdio$cnt_lval" in
$define$define) val=$define ;;
*) val=$undef ;;
esac
set d_stdio_cnt_lval
eval $setvar
@end
```

@if FILE_filbuf

: How to access the stdio _filbuf or __filbuf function.

: If this fails, check how the getc macro in stdio.h works.

```
case "${d_stdio_ptr_lval}${d_stdio_cnt_lval}" in
```

```
${define}${define})
```

: Try \$hint value, if any, then _filbuf, __filbuf, _fill, then punt.

: _fill is for os/2.

```
xxx='notok'
```

```
for filbuf in $stdio_filbuf '_filbuf(fp)' '__filbuf(fp)' '_fill(fp)' ; do
```

```
$cat >try.c <<EOP
```

```
#include <stdio.h>
```

```
#$i_stdlib I_STDLIB
```

```
#ifdef I_STDLIB
```

```
#include
```

```
<stdlib.h>
```

```
#endif
```

```
#define FILE_ptr(fp) $stdio_ptr
```

```
#define FILE_cnt(fp) $stdio_cnt
```

```
#define FILE_filbuf(fp) $filbuf
```

```
int main() {
```

```
FILE *fp = fopen("try.c", "r");
```

```
int c;
```

```
c = getc(fp);
```

```
c = FILE_filbuf(fp); /* Just looking for linker errors.*/
```

```
exit(0);
```

```
}
```

```
EOP
```

```
set try
```

```
if eval $compile && $to try.c && $run ./try; then
```

```
echo "Your stdio appears to use $filbuf"
```

```
stdio_filbuf="$filbuf"
```

```
xxx='ok'
```

```
break
```

```
else
```

```
echo "Hmm. $filbuf doesn't seem to work."
```

```
fi
```

```
$rm_try
```

```
done
```

```
case "$xxx" in
```

```

notok) echo "I can't figure out how to access _filbuf"
    echo "I'll just have to work around it."
    d_stdio_ptr_lval="$undef"
    d_stdio_cnt_lval="$undef"
    ;;
esac
;;
esac
@end

@if STDIO_PTR_LVALUE
: test whether setting _ptr sets _cnt as a side effect
d_stdio_ptr_lval_sets_cnt="$undef"
d_stdio_ptr_lval_nochange_cnt="$undef"
case "$d_stdio_ptr_lval$d_stdstdio" in
$define$define)
    echo "Checking to see what happens if we set the stdio ptr..." >&4
$cat >try.c <<EOP
#include <stdio.h>
/*
    Can we scream? */
/* Eat dust sed :-) */
/* In the buffer space, no one can hear you scream. */
#$i_stdlib I_STDLIB
#ifdef I_STDLIB
#include <stdlib.h>
#endif
#define FILE_ptr(fp) $stdio_ptr
#define FILE_cnt(fp) $stdio_cnt
#include <sys/types.h>
int main() {
    FILE *fp = fopen("try.c", "r");
    int c;
    char *ptr;
    size_t cnt;
    if (!fp) {
        puts("Fail even to read");
        exit(1);
    }
    c = getc(fp); /* Read away the first # */
    if (c == EOF) {
        puts("Fail even to read");
        exit(1);
    }
    if (!(
        18 <= FILE_cnt(fp) &&
        strncmp(FILE_ptr(fp), "include <stdio.h>\n", 18) == 0
    )) {

```

```

puts("Fail even to read");
exit (1);
}
ptr = (char*) FILE_ptr(fp);
cnt = (size_t)FILE_cnt(fp);

FILE_ptr(fp) += 42;

if ((char*)FILE_ptr(fp) != (ptr + 42)) {
printf("Fail ptr check %p != %p", FILE_ptr(fp), (ptr + 42));
exit (1);
}
if (FILE_cnt(fp) <= 20) {
printf ("Fail (<20 chars to test)");
exit (1);
}
if (strcmp(FILE_ptr(fp), "Eat dust sed :-) *\n", 20) != 0) {
puts("Fail compare");
exit
(1);
}
if (cnt == FILE_cnt(fp)) {
puts("Pass_unchanged");
exit (0);
}
if (FILE_cnt(fp) == (cnt - 42)) {
puts("Pass_changed");
exit (0);
}
printf("Fail count was %d now %d\n", cnt, FILE_cnt(fp));
return 1;

}
EOP
set try
if eval $compile && $to try.c; then
case ` $run ./try ` in
Pass_changed)
echo "Increasing ptr in your stdio decreases cnt by the same amount. Good." >&4
d_stdio_ptr_lval_sets_cnt="$define" ;;
Pass_unchanged)
echo "Increasing ptr in your stdio leaves cnt unchanged. Good." >&4
d_stdio_ptr_lval_nochange_cnt="$define" ;;
Fail*)
echo "Increasing ptr in your stdio didn't do exactly what I expected. We'll not be doing that then." >&4 ;;
*)
echo "It appears attempting to set ptr in your stdio is a bad plan." >&4 ;;
esac

```

```

else
  echo "It seems we can't set ptr in your stdio. Nevermind." >&4
fi
$rm_try
;;
esac
@end

@if d_stdio_base || USE_STDIO_BASE || FILE_base || FILE_bufsiz
: see if _base is also standard
val="$undef"
case
"$d_stdstdio" in
$define)
  $cat >try.c <<EOP
#include <stdio.h>
#$i_stdlib I_STDLIB
#ifdef I_STDLIB
#include <stdlib.h>
#endif
#define FILE_base(fp) $stdio_base
#define FILE_bufsiz(fp) $stdio_bufsiz
int main() {
  FILE *fp = fopen("try.c", "r");
  char c = getc(fp);
  if (
    19 <= FILE_bufsiz(fp) &&
    strncmp(FILE_base(fp), "#include <stdio.h>\n", 19) == 0
  )
    exit(0);
  exit(1);
}
EOP
set try
if eval $compile && $to try.c; then
  if $run ./try; then
    echo "And its _base field acts std."
    val="$define"
  else
    echo "But its _base field isn't std."
  fi
else
  echo "However, it seems to be lacking the _base field."
fi
$rm_try
;;
esac
set d_stdio_base

```

eval \$setvar

@end

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/compline/d_stdstdio.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: dlsrc.U,v\$

?RCS:

?RCS: Copyright (c) 1996-1998, Andy Dougherty

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?RCS: \$Log: dlsrc.U,v \$

?RCS:

?X: hpux support thanks to Jeff Okamoto <okamoto@hpcc101.corp.hp.com>

?X:

?X: To create a shared library, you must compile ALL source files in the

?X: library with +z (or possibly +Z if the library is whopping huge),

?X: then link the library with -b. Example:

?X: cc -c +z module_a.c

?X: cc -c +z module_b.c

?X: ld -b module_a.o module_b.o -o module.sl

?X:

?MAKE:usedl ld dlsrc cccdlflags lddlflags ccdlflags bin_ELF ld_can_script: \

rm_try Getfile Myread test osname sed d_dlopen Findhdr Setvar \

src run cc ccflags ldflags optimize ls gccversion cat rsrc i_stdlib \

i_unistd osvers sysroot

?MAKE: -pick add \$@ %<

?Y:BOTTOM

?S:usedl:

?S: This variable

indicates if the system supports dynamic

?S: loading of some sort. See also dlsrc and dlobj.

?S:.

?S:ld:

?S: This variable indicates the program to be used to link

?S: libraries for dynamic loading. On some systems, it is 'ld'.

?S: On ELF systems, it should be \$cc. Mostly, we'll try to respect

?S: the hint file setting.

?S:.

?S:dlsrc:

?S: This variable contains the name of the dynamic loading file that

?S: will be used with the package.

?S:.

?S:cccdlflags:
 ?S: This variable contains any special flags that might need to be
 ?S: passed with 'cc -c' to compile modules to be used to create a shared
 ?S: library that will be used for dynamic loading. For hpux, this
 ?S: should be +z. It is up to the makefile to use it.
 ?S:.
 ?S:lddlflags:
 ?S: This variable contains any special flags that might need to be
 ?S: passed to \$ld to create a shared library suitable for dynamic
 ?S: loading. It is up to the makefile to use it. For hpux, it
 ?S: should be '-b'. For sunos 4.1, it is empty.
 ?S:.
 ?S:ccdflags:
 ?S: This
 ?S: variable contains any special flags that might need to be
 ?S: passed to cc to link with a shared library for dynamic loading.
 ?S: It is up to the makefile to use it. For sunos 4.1, it should
 ?S: be empty.
 ?S:.
 ?S:bin_ELF:
 ?S: This variable saves the result from configure if generated binaries
 ?S: are in ELF format. Only set to defined when the test has actually
 ?S: been performed, and the result was positive.
 ?S:.
 ?S:ld_can_script:
 ?S: This variable shows if the loader accepts scripts in the form of
 ?S: -Wl,--version-script=ld.script. This is currently only supported
 ?S: for GNU ld on ELF in dynamic loading builds.
 ?S:.
 ?C:USE_DYNAMIC_LOADING ~ %<:
 ?C: This symbol, if defined, indicates that dynamic loading of
 ?C: some sort is available.
 ?C:.
 ?H:%<:#\$usedl USE_DYNAMIC_LOADING /**/
 ?H:.
 ?W:%<:dlopen
 ?T:dldir thisflag tdir
 ?F:!a.out
 : determine which dynamic loading, if any, to compile in
 echo " "
 dldir="ext/DynaLoader"
 case "\$usedl" in
 \$define|y|true)
 dflt='y'
 usedl="\$define"
 ;;
 \$undef|n|false)
 dflt='n'

```

usedl="$undef"
;;
*)
dflt='n'
case "$d_dlopen" in
    $define) dflt='y' ;;
esac
: Does a dl_XXX.XS file exist for this operating system
$test -f $Rsrc/$dldir/dl_${osname}.xs && dflt='y'
;;
esac
rp="Do you wish to use dynamic loading?"
./myread
usedl="$ans"
bin_ELF="$undef"
case "$ans" in
    y*) usedl="$define"
case "$dlsrc" in
    ") if $test -f $Rsrc/$dldir/dl_${osname}.xs ; then
        dflt="$dldir/dl_${osname}.xs"
    elif $test "$d_dlopen" = "$define" ; then
        dflt="$dldir/dl_dlopen.xs"
    else
        dflt="
    fi
    ;;
    *) dflt="$dldir/$dlsrc"
    ;;
esac
echo "The following dynamic loading files are available:"
: Can not go over to $dldir because getfile has path hard-coded in.
tdir=`pwd`; cd "$Rsrc"; $ls -C $dldir/dl*.xs; cd "$tdir"
rp="Source file to use for dynamic loading"
fn="fne"
gfpth="$src"
./getfile
usedl="$define"
: emulate basename
dlsrc=`echo $ans | $sed -e 's%.*^([/]*%)$%\1%'`

$cat
<< EOM

```

Some systems may require passing special flags to \$cc -c to compile modules that will be used to create a shared library. To use no flags, say "none".

EOM

```

case "$cccdlflags" in
  ") case "$gccversion" in
  ") case "$osname" in
  hpux) dflt='+z' ;;
  irix*) dflt='-KPIC' ;;
  svr4*|esix*|solaris|nonstopux) dflt='-KPIC' ;;
  sunos) dflt='-pic' ;;
  *) dflt='none' ;;
  esac
  ;;
  *) case "$osname" in
  darwin) dflt='none' ;;
  *linux*|svr4*|esix*|solaris|nonstopux) dflt='-fPIC' ;;
  *) dflt='-fpic' ;;
  esac ;;
esac ;;
  ') dflt='none' ;;
  *) dflt="$cccdlflags" ;;
esac

case "$dflt" in
  none) dflt="" ;;
esac

# If -Dsysroot was specified, now's the time to add it
# to cccdlflags
if test "X$sysroot" != X; then
  case "$gccversion" in
  ") ;;
  *) case "$dflt" in
  *sysroot*) ;;
  'undef'*)
    dflt="$dflt --sysroot=$sysroot" ;;
  esac
  ;;
  esac
fi

case "$dflt" in
  ") dflt='none';;
esac

rp="Any
special flags to pass to $cc -c to compile shared library modules?"
./myread
case "$ans" in
?X: Use ' ' so that a subsequent Configure run preserves the old state.
  none) cccdlflags=' ' ;;

```

```
*) cccdlflags="$ans" ;;
esac
```

```
cat << EOM
```

Some systems use ld to create libraries that can be dynamically loaded, while other systems (such as those using ELF) use \$cc.

```
EOM
```

```
: Determine if this is ELF
```

```
$cat >try.c <<EOM
```

```
/* Test for whether ELF binaries are produced */
```

```
#include <fcntl.h>
```

```
#$i_stdlib I_STDLIB
```

```
#ifdef I_STDLIB
```

```
#include <stdlib.h>
```

```
#endif
```

```
#$i_unistd I_UNISTD
```

```
#ifdef I_UNISTD
```

```
#include <unistd.h>
```

```
#endif
```

```
int main() {
```

```
    char b[4];
```

```
    int i = open("a.out",O_RDONLY);
```

```
    if(i == -1)
```

```
        exit(1); /* fail */
```

```
    if(read(i,b,4)==4 && b[0]==127 && b[1]=='E' && b[2]=='L' && b[3]=='F')
```

```
        exit(0); /* succeed (yes, it is ELF) */
```

```
    exit(1); /* fail */
```

```
}
```

```
EOM
```

```
if $cc $ccflags $ldflags -o a.out try.c >/dev/null 2>&1 && $run ./a.out; then
```

```
    bin_ELF="$define"
```

```
fi
```

```
$rm_try
```

```
case "$ld" in
```

```
    *) if $test $bin_ELF = "$define"; then
```

```
        cat <<EOM
```

You appear to have ELF support. I'll use \$cc to build dynamic libraries.

```
EOM
```

```
        dflt="$cc"
```

```
    else
```

```
        echo "I'll use ld to build dynamic libraries."
```

```
        dflt='ld'
```

```
    fi
```

```
;;
*) dflt="$ld"
;;
esac
```

```
rp="What command should be used to create dynamic libraries?"
./myread
ld="$ans"
```

```
cat << EOM
```

Some systems may require passing special flags to `$ld` to create a library that can be dynamically loaded. If your `ld` flags include `-L/other/path` options to locate libraries outside your loader's normal search path, you may need to specify those `-L` options here as well. To use no flags, say "none".

EOM

```
case "$lddflags" in
  *) case "$osname" in
      haiku) dflt='-shared' ;;
      hpux) dflt='-b';
      case "$gccversion" in
        *) dflt="$dflt +vnocompatwarnings" ;;
      esac
    ;;
  *linux*|irix*|gnu*) dflt="-shared $optimize" ;;
  solaris) # See [perl #66604].
    # On Solaris 11, gcc -m64
on amd64
  # appears not to understand -G. gcc versions at
  # least as old as 3.4.3 support -shared, so just
  # use that with Solaris 11 and later, but keep
  # the old behavior for older Solaris versions.
  case "$gccversion" in
    *) dflt='-G' ;;
  *) case "$osvers" in
      2.?|2.10) dflt='-G' ;;
      *) dflt='-shared' ;;
    esac
  ;;
  esac
  ;;
  sunos) dflt='-assert nodefinitions' ;;
  svr4*|esix*|nonstopux) dflt="-G $ldflags" ;;
  *) dflt='none' ;;
esac
;;
```

```

*) dflt="$lddflags" ;;
esac

: Only do this for gcc, since, for example, qcc has no concept
: of --sysroot.
if $test "X$sysroot" != X; then
  case "$gccversion" in
  *) ;;
  *) dflt="$dflt --sysroot $sysroot" ;;
  esac
fi

: Try to guess additional flags to pick up local libraries.
: Be careful not to append to a plain 'none'
case "$dflt" in
  none) dflt=" ;;
esac
for thisflag in $ldflags; do
  case "$thisflag" in
  -L*|-R*|-Wl,-R*)

  case " $dflt " in
  *" $thisflag "*) ;;
  *) dflt="$dflt $thisflag" ;;
  esac
  ;;
  esac
done

case "$dflt" in
  '| ') dflt='none' ;;
esac

case "$ldflags" in
  *-fstack-protector-strong*)
  case "$dflt" in
    *-fstack-protector-strong*) ;; # Don't add it again
    *) dflt="$dflt -fstack-protector-strong" ;;
  esac
  ;;
  *-fstack-protector*)
  case "$dflt" in
    *-fstack-protector*) ;; # Don't add it again
    *) dflt="$dflt -fstack-protector" ;;
  esac
  ;;
esac

```

```
rp="Any special flags to pass to $ld to create a dynamically loaded library?"
```

```
. ./myread
```

```
case "$ans" in
```

```
?X: Use ' ' so that a subsequent Configure run preserves the old state.
```

```
  none) lddflags=' ' ;;
```

```
  *) lddflags="$ans" ;;
```

```
esac
```

```
cat <<EOM
```

Some systems may require passing special flags to \$cc to indicate that the resulting executable will use dynamic linking. To use no flags, say "none".

```
EOM
```

```
case "$ccdlflags" in
```

```
  ") case "$osname" in
```

```
    *linux*|hpux|gnu*)
```

```
    dflt='-Wl,-E' ;;
```

```
    sunos)      dflt='none' ;;
```

```
    *)          dflt='none' ;;
```

```
esac ;;
```

```
  ') dflt='none' ;;
```

```
  *) dflt="$ccdlflags" ;;
```

```
esac
```

```
rp="Any special flags to pass to $cc to use dynamic linking?"
```

```
. ./myread
```

```
case "$ans" in
```

```
?X: Use ' ' so that a subsequent Configure run preserves the old state.
```

```
  none) ccldflags=' ' ;;
```

```
  *) ccldflags="$ans" ;;
```

```
esac
```

```
;;
```

```
?X: End of usedl=y section
```

```
  *) usedl="$undef"
```

```
ld='ld'
```

```
dlsrc='dl_none.xs'
```

```
lddflags=''
```

```
ccldflags=''
```

```
;;
```

```
esac
```

```
ld_can_script="$undef"
```

```
case "$bin_ELF$usedl" in
```

```
  $define$define)
```

```
  # Abuse try.h and a.out names for neat cleanup
```

```
  $cat >try.c <<EOM
```

```

void foo() {}
void bar() {}
EOM
$cat >try.h <<EOM
LIBTEST_42 {
global:
foo;
local: *;
};
EOM
if $cc $cccdlflags $ccdlflags $ccflags \
    $ldflags $lddlflags -o a.out try.c \
    -Wl,--version-script=try.h >/dev/null 2>&1 \
    && $stest -s a.out ; then
    echo "ld supports scripting" >&4
    ld_can_script="$define"
else

    echo "ld does not support scripting" >&4
fi
$rm_try
;;
esac

```

Found in path(s):

```

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/perl/dlsrc.U

```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_getgrnam_r.U,v 0RCS:

?RCS: Copyright (c) 2002,2003 Jarkko Hietaniemi

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?RCS: Generated by the reentr.pl from the Perl 5.8 distribution.

?RCS:

?MAKE:d_getgrnam_r getgrnam_r_proto: Inlibc Protochk Hasproto i_systypes \
 usethreads i_grp extern_C

?MAKE: -pick add \$@ %<

?S:d_getgrnam_r:

?S: This variable conditionally defines the HAS_GETGRNAM_R symbol,

?S: which indicates to the C program that the getgrnam_r()

?S: routine is available.

?S:.

?S:getgrnam_r_proto:

?S: This variable encodes the prototype of getgrnam_r.

?S: It is zero if d_getgrnam_r is undef, and one of the

?S: REENTRANT_PROTO_T_ABC macros of reentr.h if d_getgrnam_r
?S: is defined.
?S:.
?C:HAS_GETGRNAM_R:
?C: This symbol, if defined, indicates that the getgrnam_r routine
?C: is available to
getgrnam re-entrantly.
?C:.
?C:GETGRNAM_R_PROTO:
?C: This symbol encodes the prototype of getgrnam_r.
?C: It is zero if d_getgrnam_r is undef, and one of the
?C: REENTRANT_PROTO_T_ABC macros of reentr.h if d_getgrnam_r
?C: is defined.
?C:.
?H:#\$d_getgrnam_r HAS_GETGRNAM_R /**/
?H:#define GETGRNAM_R_PROTO \$getgrnam_r_proto /**/
?H:.
?T:try hdrs d_getgrnam_r_proto
: see if getgrnam_r exists
set getgrnam_r d_getgrnam_r
eval \$inlibc
case "\$d_getgrnam_r" in
"\$define")
hdrs="\$i_systypes sys/types.h define stdio.h \$i_grp grp.h"
case "\$d_getgrnam_r_proto:\$usetreads" in
":define") d_getgrnam_r_proto=define
set d_getgrnam_r_proto getgrnam_r \$hdrs
eval \$hasproto ;;
*) ;;
esac
case "\$d_getgrnam_r_proto" in
define)
case "\$getgrnam_r_proto" in
"|0) try='int getgrnam_r(const char*, struct group*, char*, size_t, struct group**);'
./protochk "\$extern_C \$try" \$hdrs && getgrnam_r_proto=I_CSBWR ;;
esac
case "\$getgrnam_r_proto" in
"|0) try='int getgrnam_r(const char*, struct group*,
char*, int, struct group**);'
./protochk "\$extern_C \$try" \$hdrs && getgrnam_r_proto=I_CSBI ;;
esac
case "\$getgrnam_r_proto" in
"|0) try='struct group* getgrnam_r(const char*, char*, int);'
./protochk "\$extern_C \$try" \$hdrs && getgrnam_r_proto=S_CBI ;;
esac
case "\$getgrnam_r_proto" in
"|0) try='int getgrnam_r(const char*, struct group*, char*, int);'
./protochk "\$extern_C \$try" \$hdrs && getgrnam_r_proto=I_CSBI ;;

```

esac
case "$getgrnam_r_proto" in
"|0) try='struct group* getgrnam_r(const char*, struct group*, char*, int);'
./protochk "$extern_C $try" $hdrs && getgrnam_r_proto=S_CSBI ;;
esac
case "$getgrnam_r_proto" in
"|0) d_getgrnam_r=undef
    getgrnam_r_proto=0
    echo "Disabling getgrnam_r, cannot determine prototype." >&4 ;;
*) case "$getgrnam_r_proto" in
REENTRANT_PROTO*) ;;
*) getgrnam_r_proto="REENTRANT_PROTO_${getgrnam_r_proto}" ;;
esac
echo "Prototype: $try" ;;
esac
;;
*) case "$usetthreads" in
define) echo "getgrnam_r has no prototype,
not using it." >&4 ;;
esac
d_getgrnam_r=undef
getgrnam_r_proto=0
;;
esac
;;
*) getgrnam_r_proto=0
;;
esac

```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/threads/d_getgrnam_r.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: d_setpgrp2.U 1 2006-08-24 12:32:52Z rmanfredi $
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: $Log: d_setpgrp2.U,v $
?RCS: Revision 3.0 1993/08/18 12:07:10 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:

```

?MAKE:d_setpgrp2: Inlibc
?MAKE: -pick add \$@ %<
?S:d_setpgrp2:
?S: This variable conditionally defines the HAS_SETPGRP2 symbol, which
?S: indicates to the C program that the setpgrp2() (as in DG/UX) routine
?S: is available to set the current process group.
?S:.
?C:HAS_SETPGRP2 (SETPGRP2):
?C: This symbol, if defined, indicates that the
setpgrp2() (as in DG/UX)
?C: routine is available to set the current process group.
?C:.
?H:#\$d_setpgrp2 HAS_SETPGRP2 /**/
?H:.
?LINT:set d_setpgrp2
: see if setpgrp2 exists
set setpgrp2 d_setpgrp2
eval \$inlibc

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/d_setpgrp2.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_pause.U 1 2006-08-24 12:32:52Z rmanfredi \$
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: Original Author: Andy Dougherty <doughera@lafcol.lafayette.edu>
?RCS:
?RCS: \$Log: d_pause.U,v \$
?RCS: Revision 3.0.1.1 1994/08/29 16:09:54 ram
?RCS: patch32: created by ADO
?RCS:
?MAKE:d_pause: Inlibc
?MAKE: -pick add \$@ %<
?S:d_pause:
?S: This variable conditionally defines the HAS_PAUSE symbol, which
?S: indicates to the C program that the pause() routine is available
?S: to suspend a process until a signal is received.
?S:.
?C:HAS_PAUSE :

?C: This symbol,
if defined, indicates that the pause routine is
?C: available to suspend a process until a signal is received.
?C:.
?H:#\$d_pause HAS_PAUSE /**/
?H:.
?LINT:set d_pause
: see if pause exists
set pause d_pause
eval \$inlibc

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/d_pause.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$
?RCS:
?RCS: Copyright (c) 2014, H.Merijn Brand
?RCS:
?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: \$Log: d_backtrace.U,v \$
?RCS:
?MAKE:d_backtrace: Inlibc
?MAKE: -pick add \$@ %<
?S:d_backtrace:
?S: This variable conditionally defines the HAS_BACKTRACE symbol, which
?S: indicates to the C program that the backtrace() routine is available
?S: to get a stack trace.
?S:.
?C:HAS_BACKTRACE:
?C: This symbol, if defined, indicates that the backtrace() routine is
?C: available to get a stack trace. The <execinfo.h> header must be
?C: included to use this routine.
?C:.
?H:#\$d_backtrace HAS_BACKTRACE /**/
?H:.
?LINT:set d_backtrace
:
see if backtrace exists
set backtrace d_backtrace
eval \$inlibc

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/modified/d_backtrace.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1998 Jarkko Hietaniemi

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?MAKE:d_fgetpos64 d_fopen64 d_freopen64 d_fseek64 d_fseeko64 d_fsetpos64 \
d_ftell64 d_ftello64 d_tmpfile64: Inlibc use64bitint Setvar test

?MAKE: -pick add \$@ %<

?S:d_fgetpos64:

?S: This variable conditionally defines the HAS_FGETPOS64 symbol, which

?S: indicates to the C program that the fgetpos64() routine is available.

?S:.

?S:d_fopen64:

?S: This variable conditionally defines the HAS_FOPEN64 symbol, which

?S: indicates to the C program that the fopen64() routine is available.

?S:.

?S:d_freopen64:

?S: This variable conditionally defines the HAS_FREOPEN64 symbol, which

?S: indicates to the C program that the freopen64() routine is available.

?S:.

?S:d_fseek64:

?S: This variable conditionally defines

the HAS_FSEEK64 symbol, which

?S: indicates to the C program that the fseek64() routine is available.

?S:.

?S:d_fseeko64:

?S: This variable conditionally defines the HAS_FSEEKO64 symbol, which

?S: indicates to the C program that the fseeko64() routine is available.

?S:.

?S:d_fsetpos64:

?S: This variable conditionally defines the HAS_FSETPOS64 symbol, which

?S: indicates to the C program that the fsetpos64() routine is available.

?S:.

?S:d_ftell64:

?S: This variable conditionally defines the HAS_FTELL64 symbol, which

?S: indicates to the C program that the ftell64() routine is available.

?S:.

?S:d_ftello64:

?S: This variable conditionally defines the HAS_FTELLO64 symbol, which

?S: indicates to the C program that the ftello64() routine is available.

?S:.

?S:d_tmpfile64:

?S: This variable conditionally defines the HAS_TMPFILE64 symbol, which

?S: indicates to the C program that the tmpfile64() routine is available.

?S:.

?C:HAS_FGETPOS64:

?C: This symbol, if defined, indicates that the fgetpos64 routine is

?C: available to getpos files larger than 2 gigabytes.

?C:.

?C:HAS_FOPEN64:

?C: This symbol, if defined, indicates that the fopen64 routine is

?C: available to open files larger than 2 gigabytes.

?C:.

?C:HAS_FREOPEN64:

?C: This symbol, if defined, indicates that the freopen64 routine is

?C: available to reopen files larger than 2 gigabytes.

?C:.

?C:HAS_FSEEK64:

?C: This symbol, if defined, indicates that the fseek64 routine is

?C: available to seek files larger than 2 gigabytes.

?C:.

?C:HAS_FSEEKO64:

?C: This symbol, if defined, indicates that the fseeko64 routine is

?C: available to seek files larger than 2 gigabytes.

?C:.

?C:HAS_FSETPOS64:

?C: This symbol, if defined, indicates that the fsetpos64 routine is

?C: available to setpos files larger than 2 gigabytes.

?C:.

?C:HAS_FTELL64:

?C: This symbol, if defined, indicates that the ftell64 routine is

?C: available to tell files larger than 2 gigabytes.

?C:.

?C:HAS_FTELLO64:

?C: This symbol, if defined, indicates that the ftello64 routine is

?C: available to tell files larger than 2 gigabytes.

?C:.

?C:HAS_TMPFILE64:

?C: This symbol, if defined, indicates that the tmpfile64 routine is

?C: available to tmpfile files larger than 2 gigabytes.

?C:.

?H:#\$d_fgetpos64 HAS_FGETPOS64 /**/

?H:#\$d_fopen64 HAS_FOPEN64 /**/

?H:#\$d_freopen64 HAS_FREOPEN64 /**/

?H:#\$d_fseek64 HAS_FSEEK64 /**/

?H:#\$d_fseeko64 HAS_FSEEKO64 /**/

?H:#\$d_fsetpos64 HAS_FSETPOS64 /**/

```
?H:#$d_ftell64 HAS_FTELL64 /**/  
?H:#$d_ftello64 HAS_FTELLO64 /**/  
?H:#$d_tmpfile64 HAS_TMPFILE64 /**/  
?H.:  
?T:xxx  
?LINT:set d_fgetpos64  
?LINT:set d_fopen64  
?LINT:set d_freopen64  
?LINT:set d_fseek64  
?LINT:set d_fseeko64  
?LINT:set d_fsetpos64  
?LINT:set d_ftell64  
?LINT:set d_ftello64  
?LINT:set d_tmpfile64  
: Check for 64bit versions of basic file IO  
if $test X"$use64bitint" = X"$define"; then  
: see if fgetpos64 exists  
set fgetpos64 d_fgetpos64  
eval $inlibc  
  
: see if fopen64 exists  
set freopen64 d_fopen64  
eval $inlibc  
  
: see if  
freopen64 exists  
set freopen64 d_freopen64  
eval $inlibc  
  
: see if fseek64 exists  
set fseek64 d_fseek64  
eval $inlibc  
  
: see if fseeko64 exists  
set fseeko64 d_fseeko64  
eval $inlibc  
  
: see if fsetpos64 exists  
set fsetpos64 d_fsetpos64  
eval $inlibc  
  
: see if ftell64 exists  
set ftell64 d_ftell64  
eval $inlibc  
  
: see if ftello64 exists  
set ftello64 d_ftello64  
eval $inlibc
```

```

: see if tmpfile64 exists
set tmpfile64 d_tmpfile64
eval $inlibc
else
val="$undef"
for xxx in d_fgetpos64 d_fopen64 d_freopen64 d_fseek64 d_fseeko64 d_fsetpos64 d_ftell64 d_ftello64 d_tmpfile64
do
set $xxx
eval $setvar
done
fi

```

Found in path(s):

```

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/perl/stdio64.U

```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: uidtype.U,v \$

?RCS: Revision 3.0.1.3 1994/08/29 16:33:25 ram

?RCS: patch32: now uses new Typedef unit to compute type information

?RCS:

?RCS: Revision 3.0.1.2 1994/06/20 07:09:36 ram

?RCS: patch30: comment for uidtype referred to the obsoleted symbol

?RCS:

?RCS: Revision 3.0.1.1 1994/05/13 15:28:27 ram

?RCS: patch27: made conform to its gidtype.U companion

?RCS: patch27: question now explicitly mentions getuid()

?RCS:

?RCS: Revision 3.0 1993/08/18 12:09:56 ram

?RCS: Baseline for dist

3.0 netwide release.

?RCS:

?MAKE:uidtype: Myread Typedef Findhdr

?MAKE: -pick add \$@ %<

?S:uidtype:

?S: This variable defines Uid_t to be something like uid_t, int,

?S: ushort, or whatever type is used to declare user ids in the kernel.

?S:
?C:Uid_t (UIDTYPE):
?C: This symbol holds the type used to declare user ids in the kernel.
?C: It can be int, ushort, uid_t, etc... It may be necessary to include
?C: <sys/types.h> to get any typedef'ed information.

?C:.

?H:#define Uid_t \$uidtype /* UID type */

?H:.

?T:xxx

: see what type uids are declared as in the kernel

set uid_t uidtype xxx stdio.h sys/types.h

eval \$typedef

case "\$uidtype" in

xxx)

xxx=`./findhdr sys/user.h`

set `grep '_ruid;' "\$xxx" 2>/dev/null` unsigned short

case \$1 in

unsigned) dflt="\$1 \$2" ;;

*) dflt="\$1" ;;

esac

;;

*) dflt="\$uidtype";;

esac

echo " "

rp="What is the type for user ids returned by getuid()?"

./myread

uidtype="\$ans"

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/uidtype.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 2009 H.Merijn Brand

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?MAKE:d_getaddrinfo: Inlibc

?MAKE: -pick add \$@ %<

?S:d_getaddrinfo:

?S: This variable conditionally defines the HAS_GETADDRINFO symbol,

?S: which indicates to the C program that the getaddrinfo() function

?S: is available.

?S:.

?C:HAS_GETADDRINFO:

?C: This symbol, if defined, indicates that the getaddrinfo() function

?C: is available for use.

?C:.

?H:#\$d_getaddrinfo HAS_GETADDRINFO /**/

?H:.

?LINT:set d_getaddrinfo

: see if getaddrinfo exists

set getaddrinfo d_getaddrinfo

eval \$inlibc

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_getaddrinfo.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: i_libutil.U,v \$

?RCS:

?RCS: Copyright (c) 2000 Jarkko Hietaniemi

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?MAKE:i_libutil: Inhdr Hasfield

?MAKE: -pick add \$@ %<

?S:i_libutil:

?S: This variable conditionally defines the I_LIBUTIL symbol, and indicates

?S: whether a C program should include <libutil.h>.

?S:.

?C:I_LIBUTIL:

?C: This symbol, if defined, indicates that <libutil.h> exists and

?C: should be included.

?C:.

?H:#\$i_libutil I_LIBUTIL /**/

?H:.

?LINT:set i_libutil

: see if this is a libutil.h system

set libutil.h i_libutil

eval \$inhdr

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/i_libutil.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_ftncate.U 1 2006-08-24 12:32:52Z rmanfredi \$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: \$Log: d_ftrncate.U,v \$
?RCS: Revision 3.0 1993/08/18 12:06:07 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:d_ftrncate: Inlibc
?MAKE: -pick add \$@ %<
?S:d_ftrncate (d_ftrncate):
?S: This variable conditionally defines the HAS_FTRUNCATE symbol, which
?S: indicates to the C program that the ftrncate() subroutine exists.
?S:.
?C:HAS_FTRUNCATE:
?C: This symbol, if defined, indicates that the ftrncate() subroutine
?C: exists.
?C:.
?H:#\$d_ftrncate
HAS_FTRUNCATE /**/
?H:.
?LINT:set d_ftrncate
: see if ftrncate exists
set ftrncate d_ftrncate
eval \$inlibc

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/d_ftrncate.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: sbrktype.U 1 2006-08-24 12:32:52Z rmanfredi \$
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: \$Log: sbrktype.U,v \$
?RCS: Revision 3.0 1993/08/18 12:09:43 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:sbrktype: Myread Oldconfig Loc contains Findhdr

```
?MAKE: -pick add $@ %<
?S:sbrktype:
?S: This variable defines sbrktype to be something like caddr_t, char *,
?S: or whatever type is used to declare sbrk() in the kernel.
?S:.
?C:Caddr_t (SBRKTYPE):
?C: This symbol holds the type of a core address. It is intended to be used
?C: to safely
declare the return type of system calls like sbrk(). It might
?C: be necessary to include <sys/types.h> as well.
?C:.
?H:#define Caddr_t $sbrktype /* <core address> type */
?H:.
: see what type sbrk is declared as in the kernel
case "$sbrktype" in
")
if $contains 'caddr_t;' `./findhdr sys/types.h` >/dev/null 2>&1 ; then
dflt='caddr_t';
else
dflt='char *';
fi
;;
*) dflt="$sbrktype"
;;
esac
echo " "
rp="What is the return type of sbrk() on this system?"
./myread
sbrktype="$ans"
```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/sbrktype.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: vendorprefix.U,v 1.1 1999/07/08 18:32:57 doughera Exp doughera $
```

```
?RCS:
```

```
?RCS: Copyright (c) 1999 Andy Dougherty
```

```
?RCS:
```

```
?RCS: You may redistribute only under the terms of the Artistic License,
```

```
?RCS: as specified in the README file that comes with the distribution.
```

```
?RCS: You may reuse parts of this distribution only within the terms of
```

```
?RCS: that same Artistic License; a copy of which may be found at the root
```

```
?RCS: of the source tree for dist 3.0.
```

```
?RCS:
```

```
?RCS: $Log: vendorprefix.U,v $
```

```
?RCS: Revision 1.1 1999/07/08 18:32:57 doughera
```

```
?RCS: Initial revision
```

```

?RCS:
?MAKE:usevendorprefix vendorprefix vendorprefixexp +oldvendorprefix: \
  Getfile Loc Oldconfig cat prefix Myread
?MAKE: -pick add $@ %<
?S:usevendorprefix:
?S: This variable tells whether the vendorprefix
?S: and consequently other vendor* paths are in use.
?S:.
?S:vendorprefix:
?S: This variable holds the full absolute path of the directory below
?S: which
  the vendor will install add-on packages.
?S: See INSTALL for usage and examples.
?S:.
?S:vendorprefixexp:
?S: This variable holds the full absolute path of the directory below
?S: which the vendor will install add-on packages. Derived from vendorprefix.
?S:.
?S:oldvendorprefix:
?S: This variable is set non-null if the vendorprefix was previously defined
?S: and gets set to a new value. Used internally by Configure only.
?S:.
: Set the vendorprefix variables
$cat <<EOM

```

The installation process will also create a directory for vendor-supplied add-ons. Vendors who supply perl with their system may find it convenient to place all vendor-supplied files in this directory rather than in the main distribution directory. This will ease upgrades between binary-compatible maintenance versions of perl.

Of course you may also use these directories in whatever way you see fit. For example, you might use them to access modules shared over a company-wide network.

The default answer should be
fine for most people.

This causes further questions about vendor add-ons to be skipped and no vendor-specific directories will be configured for perl.

EOM

```

rp="Do you want to configure vendor-specific add-on directories?"
case "$usevendorprefix" in
define|true|[yY]*) dflt=y ;;
*) : User may have set vendorprefix directly on Configure command line.
case "$vendorprefix" in
"|" ) dflt=n ;;
*) dflt=y ;;

```

```

esac
;;
esac
./myread
case "$ans" in
[yY]*) fn=d~+
rp='Installation prefix to use for vendor-supplied add-ons?'
case "$vendorprefix" in
") dflt="$prefix" ;;
*) dflt=$vendorprefix ;;
esac
./getfile
: XXX Prefixit unit does not yet support siteprefix and vendorprefix
oldvendorprefix="
case "$vendorprefix" in
") ;;
*) case "$ans" in
"$prefix") ;;
*) oldvendorprefix="$prefix";;
esac
;;
esac
usevendorprefix="$define"
vendorprefix="$ans"
vendorprefixexp="$ansexp"
;;
*) usevendorprefix="$undef"
vendorprefix="
vendorprefixexp="
;;
esac

```

Found in path(s):

*

/opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/installdirs/vendorprefix.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_memalign.U 1 2006-08-24 12:32:52Z rmanfredi \$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic Licence,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic Licence; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: d_memalign.U,v \$
?RCS:
?MAKE:d_memalign: Inlibc
?MAKE: -pick add \$@ %<
?S:d_memalign:
?S: This variable conditionally defines the HAS_MEMALIGN symbol, which
?S: indicates to the C program that the memalign() routine is available.
?S:.
?C:HAS_MEMALIGN :
?C: This symbol, if defined, indicates that the memalign routine is
?C: available to allocate aligned memory.
?C:.
?H:#\$d_memalign HAS_MEMALIGN /**/
?H:.
?LINT:set d_memalign
: see if memalign exists
set
memalign d_memalign
eval \$inlibc

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/d_memalign.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: \$Log: i_dirent.U,v \$
?RCS: Revision 3.0.1.4 1994/10/29 16:20:01 ram
?RCS: patch36: failed scanning for 'd_namlen' with missing <dirent.h> (ADO)
?RCS:
?RCS: Revision 3.0.1.3 1994/06/20 07:01:25 ram
?RCS: patch30: added direntrytype for hints, merely for NeXT (ADO)
?RCS: patch30: now checks for both struct dirent and direct (ADO)
?RCS:
?RCS: Revision 3.0.1.2 1994/05/13 15:22:37 ram
?RCS: patch27: new variable direntrytype for proper type setting (ADO)
?RCS:
?RCS: Revision 3.0.1.1 1994/01/24

14:11:15 ram

?RCS: patch16: added new Direntry_t pseudo-type for directory entries

?RCS:

?RCS: Revision 3.0 1993/08/18 12:08:17 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?X:

?X: This unit looks whether there is a dirent system or not

?X:

?MAKE:i_dirent d_dirnamlen direntrytype: test contains Setvar \
 Myread Findhdr cppstdin cppflags cppminus rm_try

?MAKE: -pick add \$@ %<

?S:i_dirent:

?S: This variable conditionally defines I_DIRENT, which indicates

?S: to the C program that it should include <dirent.h>.

?S:.

?S:d_dirnamlen:

?S: This variable conditionally defines DIRNAMLEN, which indicates

?S: to the C program that the length of directory entry names is

?S: provided by a d_namelen field.

?S:.

?S:direntrytype:

?S: This symbol is set to 'struct direct' or 'struct dirent' depending on

?S: whether dirent is available or not. You should use this pseudo type to

?S: portably declare your directory entries.

?S:.

?C:I_DIRENT:

?C: This symbol, if defined, indicates to the C program

that it should

?C: include <dirent.h>. Using this symbol also triggers the definition

?C: of the Direntry_t define which ends up being 'struct dirent' or

?C: 'struct direct' depending on the availability of <dirent.h>.

?C:.

?C:DIRNAMLEN:

?C: This symbol, if defined, indicates to the C program that the length

?C: of directory entry names is provided by a d_namlen field. Otherwise

?C: you need to do strlen() on the d_name field.

?C:.

?C:Direntry_t:

?C: This symbol is set to 'struct direct' or 'struct dirent' depending on

?C: whether dirent is available or not. You should use this pseudo type to

?C: portably declare your directory entries.

?C:.

?H:#\$i_dirent I_DIRENT /**/
 ?H:#\$d_dirnamlen DIRNAMLEN /**/
 ?H:%<:@if I_DIRENT && Direntry_t
 ?H:%<:#define Direntry_t \$direntrytype
 ?H:%<:@end

```

?H:
?T:xinc guess1 guess2
?LINT:set i_dirent d_dirnamlen
: see if this is a dirent system
echo " "
if xinc=`./findhdr dirent.h`; $test "$xinc"; then
  val="$define"
  echo "<dirent.h> found." >&4
else
  val="$undef"
  if
  xinc=`./findhdr sys/dir.h`; $test "$xinc"; then
    echo "<sys/dir.h> found." >&4
    echo " "
  else
    xinc=`./findhdr sys/ndir.h`
  fi
  echo "<dirent.h> NOT found." >&4
fi
set i_dirent
eval $setvar

```

```

?X: Use struct dirent or struct direct?  If we're using dirent.h,
?X: it's probably struct dirent, but apparently not always.
?X: Assume $xinc still contains the name of the header file we're using.
@if direntrytype || Direntry_t
: Look for type of directory structure.
echo " "
$ccpstdin $ccpflags $ccpminus < "$xinc" > try.c

```

```

case "$direntrytype" in
'|' )
  case "$i_dirent" in
$define) guess1='struct dirent' ;;
*) guess1='struct direct' ;;
  esac
;;
*) guess1="$direntrytype"
;;
esac

```

```

case "$guess1" in
'struct dirent') guess2='struct direct' ;;
*) guess2='struct dirent' ;;
esac

```

```

if $contains "$guess1" try.c >/dev/null 2>&1; then
  direntrytype="$guess1"

```

```

echo "Your directory entries are $direntrytype." >&4
elif $contains "$guess2" try.c >/dev/null 2>&1; then
direntrytype="$guess2"
echo
"Your directory entries seem to be $direntrytype." >&4
else
echo "I don't recognize your system's directory entries." >&4
rp="What type is used for directory entries on this system?"
dflt="$guess1"
./myread
direntrytype="$ans"
fi
$rm_try

@end

@if d_dirnamlen || DIRNAMLEN
: see if the directory entry stores field length
echo " "
$cppstdin $cppflags $cppminus < "$xinc" > try.c
if $contains 'd_namlen' try.c >/dev/null 2>&1; then
echo "Good, your directory entry keeps length information in d_namlen." >&4
val="$define"
else
echo "Your directory entry does not know about the d_namlen field." >&4
val="$undef"
fi
set d_dirnamlen
eval $setvar
$rm_try

@end

```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/i_dirent.U
```

No license file was found, but licenses were detected in source scan.

```

?RCS: $Id: d_ffs.U 1 2006-08-24 12:32:52Z rmanfredi $
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:

```

```
?RCS: $Log: d_ffs.U,v $
?RCS: Revision 3.0 1993/08/18 12:06:03 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:d_ffs: Inlibc
?MAKE: -pick add $@ %<
?S:d_ffs:
?S: This variable conditionally defines the HAS_FFS symbol, which
?S: indicates to the C program that the ffs() routine is available
?S: to find the first bit which is set in its integer argument.
?S:.
?C:HAS_FFS:
?C: This symbol, if defined, indicates that the ffs routine is available
?C: to
    find the first bit set in its argument. If it's not available,
?C: roll your own.
?C:.
?H:#$d_ffs HAS_FFS /**/
?H:.
?LINT:set d_ffs
: see if ffs exists
set ffs d_ffs
eval $inlibc
```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/d_ffs.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id$
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: Original Author: Andy Dougherty <doughera@lafcol.lafayette.edu>
?RCS:
?RCS: $Log: d_dlopen.U,v $
?RCS: Revision 3.0.1.2 1995/07/25 13:52:56 ram
?RCS: patch56: force compile-link test since symbol might lie in crt0.o (ADO)
?RCS:
?RCS: Revision 3.0.1.1 1994/08/29 16:07:34 ram
?RCS: patch32: created by ADO
?RCS:
```

```

?MAKE:d_dlopen: Inlibc runnm
?MAKE: -pick add $@ %<
?S:d_dlopen:
?S: This variable conditionally defines the HAS_DLOPEN symbol, which
?S: indicates to the C program that the dlopen() routine
is available.
?S:.
?C:HAS_DLOPEN :
?C: This symbol, if defined, indicates that the dlopen routine is
?C: available.
?C:.
?H:#$d_dlopen HAS_DLOPEN /**/
?H:.
?T: xxx_runnm
?LINT:set d_dlopen
?X: We don't permanently change runnm, but we do temporarily.
?LINT: change runnm
: see if dlopen exists
?X: On NetBSD and FreeBSD, dlopen is available, but it is in
?X: /usr/lib/crt0.o, not in any of the libraries. Therefore, do not
?X: use the nm extraction, but use a real compile and link test instead.
xxx_runnm="$runnm"
runnm=false
set dlopen d_dlopen
eval $inlibc
runnm="$xxx_runnm"

```

Found in path(s):

```

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/d_dlopen.U

```

No license file was found, but licenses were detected in source scan.

```

?RCS: $Id: shm_for.U 1 2006-08-24 12:32:52Z rmanfredi $
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: $Log: shm_for.U,v $
?RCS: Revision 3.0.1.1 1994/10/29 16:28:37 ram
?RCS: patch36: call ./Cpplib explicitly instead of relying on PATH
?RCS:
?RCS: Revision 3.0 1993/08/18 12:09:46 ram
?RCS: Baseline for dist 3.0 netwide release.

```

```

?RCS:
?MAKE:shm_for shm_att shm_lim: Cppsym Myread ipc uname
?MAKE: -pick add $@ %<
?S:shm_for:
?S: This variable tells us the type of machine we're expecting the
?S: shared memory code to run on. The value is available to C
  programs
?S: in the C_SHM_FOR manifest.
?S:.
?S:shm_att:
?S: This variable tells us where a shared memory segment should be
?S: attached. Good values are HIGH, LOW, and ZERO.
?S:.
?S:shm_lim:
?S: This variable tells us if shared memory attached HIGH should
?S: have an upper limit.
?S:.
?X: -----
?X: It's a potential lose to define anything beginning with SHM...
?X: At least we can think that S_ stands for "String version of ..." -- HMS
?X: -----
?C:S_SHM_FOR ~ %<:
?C: This symbol identifies what we chose for the target system's
?C: default shared memory configuration parameters.
?C:.
?C:S_SHM_ATT ~ %<:
?C: This symbol holds the default "place" to attach shared memory.
?C: Values are "HIGH", "ZERO", and "LOW".
?C:.
?C:S_SHM_LIM ~ %<:
?C: This symbol holds the default upper bound address limit if shared
?C: memory is attached HIGH. If zero, there is no upper limit.
?C:.
?H:?%<:#ifdef
  SERVE_SHM
?H:?%<:#define S_SHM_FOR "$shm_for"
?H:?%<:#define S_SHM_ATT "$shm_att"
?H:?%<:#define S_SHM_LIM "$shm_lim"
?H:?%<:#endif
?H:.
?W:?%<:S_SHM_FOR S_SHM_ATT S_SHM_LIM
: see how to attach shared memory
echo " "
echo "Deciding how to attach shared memory..." >&4

case "$ipc" in
shm)
  shm_for='Default case'

```

```

shm_att='HIGH'
shm_lim='0x0'
if ./Cppsym tower32 tower32_600; then
    echo "NCR Towers are usually normal..."
    : echo "Oh, an NCR Tower."
    : This works for the 600
    shm_for='NCR Tower 32'
    shm_att='LOW'
else
    case "$uname" in
    */uname)
        case "`uname -m`" in
        ACS??68*)
            echo "Oh, an Altos 3068."
            shm_for='Altos 3068:'
            shm_lim='0x800000'
            ;;
        esac
        ;;
    *)
        echo "Looks normal to me..."
        ;;
    esac
fi

dflt="$shm_for"
rp='Description of shared memory configuration?'
./myread
shm_for="$ans"

dflt="$shm_att"
rp='Where should shared memory be attached?'
./myread
shm_att="$ans"

case "$shm_att" in
HIGH)
    dflt="$shm_lim"
    rp='What is
the upper address limit for shared memory?'
    ./myread
    shm_lim="$ans"
    ;;
*)
    shm_lim=""
    ;;
esac
;;

```

```

*)
echo "but you aren't using shared memory so I won't bother." >&4
shm_for='NOT CONFIGURED'
shm_att='NONE'
shm_lim='-1'
;;
esac

```

Found in path(s):

```

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/shm_for.U

```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_strerror_r.U,v 0RCS:

?RCS: Copyright (c) 2002,2003 Jarkko Hietaniemi

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?RCS: Generated by the reentr.pl from the Perl 5.8 distribution.

?RCS:

?MAKE:d_strerror_r strerror_r_proto: Inlibc Protochk Hasproto i_systypes \
 usethreads i_string extern_C

?MAKE: -pick add \$@ %<

?S:d_strerror_r:

?S: This variable conditionally defines the HAS_STRERROR_R symbol,

?S: which indicates to the C program that the strerror_r()

?S: routine is available.

?S:.

?S:strerror_r_proto:

?S: This variable encodes the prototype of strerror_r.

?S: It is zero if d_strerror_r is undef, and one of the

?S: REENTRANT_PROTO_T_ABC macros of reentr.h if d_strerror_r

?S: is defined.

?S:.

?C:HAS_STRERROR_R:

?C: This symbol, if defined, indicates that the strerror_r routine

?C: is available

to strerror re-entrantly.

?C:.

?C:STRERROR_R_PROTO:

?C: This symbol encodes the prototype of strerror_r.

?C: It is zero if d_strerror_r is undef, and one of the

?C: REENTRANT_PROTO_T_ABC macros of reentr.h if d_strerror_r

?C: is defined.

?C:.

?H:#\$d_strerror_r HAS_STRERROR_R /**/

```

?H:#define STRError_R_PROTO $sterror_r_proto  /**/
?H:.
?T:try hdrs d_sterror_r_proto
: see if sterror_r exists
set sterror_r d_sterror_r
eval $inlibc
case "$d_sterror_r" in
"$define")
hdrs="$i_systypes sys/types.h define stdio.h $i_string string.h"
case "$d_sterror_r_proto:$usethreads" in
":define") d_sterror_r_proto=define
set d_sterror_r_proto sterror_r $hdrs
eval $hasproto ;;
*) ;;
esac
case "$d_sterror_r_proto" in
define)
case "$sterror_r_proto" in
"|0) try='int sterror_r(int, char*, size_t);'
./protochk "$extern_C $try" $hdrs && sterror_r_proto=I_IBW ;;
esac
case "$sterror_r_proto" in
"|0) try='int sterror_r(int, char*, int);'
./protochk "$extern_C $try" $hdrs &&
sterror_r_proto=I_IBI ;;
esac
case "$sterror_r_proto" in
"|0) try='char* sterror_r(int, char*, size_t);'
./protochk "$extern_C $try" $hdrs && sterror_r_proto=B_IBW ;;
esac
case "$sterror_r_proto" in
"|0) d_sterror_r=undef
sterror_r_proto=0
echo "Disabling sterror_r, cannot determine prototype." >&4 ;;
*) case "$sterror_r_proto" in
REENTRANT_PROTO*) ;;
*) sterror_r_proto="REENTRANT_PROTO_$sterror_r_proto" ;;
esac
echo "Prototype: $try" ;;
esac
;;
*) case "$usethreads" in
define) echo "sterror_r has no prototype, not using it." >&4 ;;
esac
d_sterror_r=undef
sterror_r_proto=0
;;
esac

```

```
::
*) strerror_r_proto=0
::
esac
```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/threads/d_strerror_r.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: i_systable.U 1 2006-08-24 12:32:52Z rmanfredi $
```

```
?RCS:
```

```
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
```

```
?RCS:
```

```
?RCS: You may redistribute only under the terms of the Artistic Licence,
```

```
?RCS: as specified in the README file that comes with the distribution.
```

```
?RCS: You may reuse parts of this distribution only within the terms of
```

```
?RCS: that same Artistic Licence; a copy of which may be found at the root
```

```
?RCS: of the source tree for dist 4.0.
```

```
?RCS:
```

```
?RCS: $Log: i_systable.U,v $
```

```
?RCS: Revision 3.0.1.1 1993/10/16 13:50:20 ram
```

```
?RCS: patch12: created
```

```
?RCS:
```

```
?RCS:
```

```
?MAKE:i_systable: Inhdr
```

```
?MAKE: -pick add $@ %<
```

```
?S:i_systable:
```

```
?S: This variable conditionally defines the I_SYS_TABLE symbol, and
```

```
?S: indicates whether a C program should include <sys/table.h>.
```

```
?S:.
```

```
?C:I_SYS_TABLE:
```

```
?C: This symbol, if defined, indicates to the C program that it should
```

```
?C: include <sys/table.h> for the OSF/1 table() system call.
```

```
?C:.
```

```
?H:#$i_systable
```

```
I_SYS_TABLE /**/
```

```
?H:.
```

```
?LINT:set i_systable
```

```
: see if this is an OSF sys/table system
```

```
set sys/table.h i_systable
```

```
eval $inhdr
```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/i_systable.U
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$
?RCS:
?RCS: Copyright (c) 1999 Jarkko Hietaniemi
?RCS:
?RCS: You may distribute under the terms of either the GNU General Public
?RCS: License or the Artistic License, as specified in the README file.
?RCS:
?MAKE:d_getmntent_r: Inlibc
?MAKE: -pick add \$@ %<
?S:d_getmntent_r:
?S: This variable conditionally defines the HAS_GETMNTENT_R symbol,
?S: which indicates to the C program that the getmntent_r()
?S: routine is available.
?S:.
?C:HAS_GETMNTENT_R:
?C: This symbol, if defined, indicates that the getmntent_r routine
?C: is available to getmntent re-entrantly.
?C:.
?H:#\$d_getmntent_r HAS_GETMNTENT_R /**/
?H:.
?LINT:set d_getmntent_r
: see if getmntent_r exists
set getmntent_r d_getmntent_r
eval \$inlibc

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/threads/d_getmntent_r.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: randfunc.U,v 3.0 1993/08/18 12:09:39 ram Exp \$
?RCS:
?RCS: Copyright (c) 1991-1993, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 3.0.
?RCS:
?RCS: \$Log: randfunc.U,v \$
?RCS: Revision 3.0 1993/08/18 12:09:39 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?X:
?X: This is the new unit that should be used when random
?X: functions are to be used. It thus makes randbits.U obsolete.
?X:

?X: This unit gives a simple #define for Drand01, which produces
?X: doubles in the range [0,1) using the "best" random number
?X: generator available. The source should just call Drand01
?X: and not worry about the underlying
implementation.

?X: Andy Dougherty July 1998

?X:

?MAKE:randfunc drand01 seedfunc randbits randseedtype: \
Compile Myread Csym ccflags
?MAKE: -pick add \$@ %<
?S:randfunc:
?S: Indicates the name of the random number function to use.
?S: Values include drand48, random, and rand. In C programs,
?S: the 'Drand01' macro is defined to generate uniformly distributed
?S: random numbers over the range [0., 1.[(see drand01 and nrand).
?S:.
?S:drand01:
?S: Indicates the macro to be used to generate normalized
?S: random numbers. Uses randfunc, often divided by
?S: (double) (((unsigned long) 1 << randbits)) in order to
?S: normalize the result.
?S: In C programs, the macro 'Drand01' is mapped to drand01.
?S:.
?S:randseedtype:
?S: Indicates the type of the argument of the seedfunc.
?S:.
?S:seedfunc:
?S: Indicates the random number generating seed function.
?S: Values include srand48, srandom, and srand.
?S:.
?S:randbits:
?S: Indicates how many bits are produced by the function used to
?S: generate
normalized random numbers.
?S:.
?C:RANDFUNC:
?C: This symbol defines the random function used to define Drand01().
?C:.
?C:Drand01:
?C: This macro is to be used to generate uniformly distributed
?C: random numbers over the range [0., 1.[. You may have to supply
?C: an 'extern double drand48();' in your program since SunOS 4.1.3
?C: doesn't provide you with anything relevant in its headers.
?C: See HAS_DRAND48_PROTO.
?C:.
?C:Rand_seed_t:
?C: This symbol defines the type of the argument of the
?C: random seed function.

```

?C:.
?C:seedDrand01:
?C: This symbol defines the macro to be used in seeding the
?C: random number generator (see Drand01).
?C:.
?C:RANDBITS:
?C: This symbol indicates how many bits are produced by the
?C: function used to generate normalized random numbers.
?C: Values include 15, 16, 31, and 48.
?C:.
?H:#define RANDFUNC $randfunc /**/
?H:#define Drand01() $drand01 /**/
?H:#define Rand_seed_t $randseedtype /**/
?H:#define seedDrand01(x) $seedfunc((Rand_seed_t)x) /**/
?H:#define
RANDBITS $randbits /**/
?H:.
?LINT:change ccflags
?LINT:unclosed $randbits))"
: How can we generate normalized random numbers ?
echo " "
echo "Using our internal random number implementation..." >&4

case "$ccflags" in
*-Dmy_rand=|*-Dmy_srand=*)
echo "Removing obsolete -Dmy_rand, -Dmy_srand, and -Drandbits from ccflags." >&4
ccflags="`echo $ccflags | sed -e 's/-Dmy_rand=random/ /'"
ccflags="`echo $ccflags | sed -e 's/-Dmy_srand=srandom/ /'"
ccflags="`echo $ccflags | sed -e 's/-Drandbits=[0-9][0-9]*/ /'"
;;
esac

randfunc=Perl_drand48
drand01="Perl_drand48()"
seedfunc="Perl_drand48_init"
randbits=48
randseedtype=U32

```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/compline/randfunc.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: d_itimer.U 1 2006-08-24 12:32:52Z rmanfredi $
```

```
?RCS:
```

```
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
```

```
?RCS:
```

```
?RCS: You may redistribute only under the terms of the Artistic Licence,
```

?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: \$Log: d_itimer.U,v \$
?RCS: Revision 3.0 1993/08/18 12:06:25 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:d_itimer: Inlibc
?MAKE: -pick add \$@ %<
?S:d_itimer:
?S: This variable conditionally defines the HAS_ITIMER symbol, which
?S: indicates that the setitimer() routine exists. The setitimer()
?S: routine supports sub-second accuracy for one real-time and two
?S: cpu clocks.
?S:.
?C:HAS_ITIMER (ITIMER):
?C: This symbol, if defined, indicates
that the setitimer() routine exists.
?C:.
?H:#\$d_itimer HAS_ITIMER /**/
?H:.
?LINT:set d_itimer
: see if setitimer exists
set setitimer d_itimer
eval \$inlibc

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/d_itimer.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_poll.U 15 2006-08-30 18:21:51Z rmanfredi \$
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: \$Log: d_poll.U,v \$
?RCS: Revision 3.0.1.2 1997/02/28 15:38:17 ram
?RCS: patch61: mention that <poll.h> can be included if HAS_POLL defined
?RCS:
?RCS: Revision 3.0.1.1 1995/01/11 15:26:31 ram

```

?RCS: patch45: created
?RCS:
?MAKE:d_poll: Inlibc
?MAKE: -pick add $@ %<
?S:d_poll:
?S: This variable conditionally defines the HAS_POLL symbol, which
?S: indicates to the C program that the poll() routine is available
?S: to poll active file descriptors.
?S:.
?C:HAS_POLL
:
?C: This symbol, if defined, indicates that the poll routine is
?C: available to poll active file descriptors. Please check I_POLL and
?C: I_SYS_POLL to know which header should be included as well.
?C:.
?H:#$d_poll HAS_POLL /**/
?H:.
?LINT:set d_poll
: see if poll exists
set poll d_poll
eval $inlibc

```

Found in path(s):

```

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/d_poll.U

```

No license file was found, but licenses were detected in source scan.

```

?RCS: $Id: d_safebcpy.U,v 3.0.1.4 1997/02/28 15:40:58 ram Exp $
?RCS:
?RCS: Copyright (c) 1991-1993, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 3.0.
?RCS:
?RCS: $Log: d_safebcpy.U,v $
?RCS: Revision 3.0.1.4 1997/02/28 15:40:58 ram
?RCS: patch61: improved overlapping copy check
?RCS: patch61: comfort them if they have memmove
?RCS: patch61: added ?F: metalint hint
?RCS:
?RCS: Revision 3.0.1.3 1995/07/25 13:58:40 ram
?RCS: patch56: re-arranged compile line to include ldflags before objects
?RCS:
?RCS: Revision 3.0.1.2 1995/01/11 15:29:23 ram
?RCS: patch45: added 'ldflags' to the test compile line (ADO)

```

```

?RCS:
?RCS:
Revision 3.0.1.1 1994/05/06 14:49:03 ram
?RCS: patch23: ensure string is not optimized in read-only memory (ADO)
?RCS:
?RCS: Revision 3.0 1993/08/18 12:06:58 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:d_safebcpy: cat d_bcopy Compile rm_try run \
d_memmove i_memory i_stdlib i_string i_unistd Oldconfig Setvar
?MAKE: -pick add $@ %<
?S:d_safebcpy:
?S: This variable conditionally defines the HAS_SAFE_BCOPY symbol if
?S: the bcopy() routine can do overlapping copies. Normally, you
?S: should probably use memmove().
?S:.
?C:HAS_SAFE_BCOPY (SAFE_BCOPY):
?C: This symbol, if defined, indicates that the bcopy routine is available
?C: to copy potentially overlapping memory blocks. Normally, you should
?C: probably use memmove() or memcpy(). If neither is defined, roll your
?C: own version.
?C:.
?H:#$d_safebcpy HAS_SAFE_BCOPY /**/
?H:.
?F:!try
?LINT: set d_safebcpy
: can bcopy handle overlapping blocks?
echo " "
?X: assume the worst.
val="$undef"
case "$d_memmove" in
"$define")
echo "I'll use memmove() instead of bcopy() for overlapping copies." ;;
*) case "$d_bcopy" in
"$define")
echo "Checking to see if bcopy() can do overlapping copies..." >&4
$cat >try.c <<EOCP
#$i_memory I_MEMORY
#$i_stdlib I_STDLIB
#$i_string I_STRING
#$i_unistd I_UNISTD
EOCP
$cat >>try.c <<'EOCP'
#include <stdio.h>
#ifdef I_MEMORY
# include <memory.h>
#endif
#ifdef I_STDLIB

```

```

# include <stdlib.h>
#endif
#ifdef I_STRING
# include <string.h>
#else
# include <strings.h>
#endif
#ifdef I_UNISTD
# include <unistd.h> /* Needed for NetBSD */
#endif
int main()
{
char buf[128], abc[128];
char *b;
int len;
int off;
int align;

/* Copy "abcde..." string to char abc[] so that gcc doesn't
   try to store the string in read-only memory. */
bcopy("abcdefghijklmnopqrstuvwxy0123456789", abc, 36);

for (align = 7; align >= 0; align--) {
for (len = 36; len; len--) {
b = buf+align;
bcopy(abc, b, len);
for (off = 1; off <= len; off++) {
bcopy(b, b+off, len);
bcopy(b+off,
b, len);
if (bcmp(b, abc, len))
exit(1);
}
}
}
exit(0);
}
EOCP
set try
if eval $compile_ok; then
if $run ./try 2>/dev/null; then
echo "Yes, it can."
val="$define"
else
echo "It can't, sorry."
fi
else
echo "(I can't compile the test program, so we'll assume not...)"

```

```
fi
;;
esac
$rm_try
;;
esac
set d_safebcpy
eval $setvar
```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/compline/d_safebcpy.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: installprefix.U,v 1.1 1999/07/08 18:32:57 doughera Exp doughera $
```

```
?RCS:
```

```
?RCS: Copyright (c) 1999 Andy Dougherty
```

```
?RCS:
```

```
?RCS: You may redistribute only under the terms of the Artistic License,
```

```
?RCS: as specified in the README file that comes with the distribution.
```

```
?RCS: You may reuse parts of this distribution only within the terms of
```

```
?RCS: that same Artistic License; a copy of which may be found at the root
```

```
?RCS: of the source tree for dist 3.0.
```

```
?RCS:
```

```
?RCS: Original Author: Andy Dougherty <doughera@lafcol.lafayette.edu>
```

```
?RCS:
```

```
?RCS: $Log: installprefix.U,v $
```

```
?RCS: Revision 1.1 1999/07/08 18:32:57 doughera
```

```
?RCS: Initial revision
```

```
?RCS:
```

```
?RCS:
```

```
?MAKE:installprefix installprefixexp: Getfile Loc \
```

```
Oldconfig afs cat package prefix
```

```
?MAKE: -pick add $@ %<
```

```
?S:installprefix:
```

```
?S: This variable holds the name of the directory below which
```

```
?S: "make install" will install the package. For most users, this
```

```
?S: is the same
```

```
as prefix. However, it is useful for
```

```
?S: installing the software into a different (usually temporary)
```

```
?S: location after which it can be bundled up and moved somehow
```

```
?S: to the final location specified by prefix.
```

```
?S:.
```

```
?S:installprefixexp:
```

```
?S: This variable holds the full absolute path of installprefix
```

```
?S: with all ~-expansion done.
```

```
?S:.
```

```
: determine installation prefix for where package is to be installed.
```

```
if $afs; then
$cat <<EOM
```

Since you are running AFS, I need to distinguish the directory in which files will reside from the directory in which they are installed (and from which they are presumably copied to the former directory by occult means).

```
EOM
case "$installprefix" in
") dflt=`echo $prefix | sed 's#^/afs/#/afs/.#`;;
*) dflt="$installprefix";;
esac
else
$cat <<EOM
```

In some special cases, particularly when building \$package for distribution, it is convenient to distinguish the directory in which files should be installed from the directory (\$prefix) in which they will eventually reside. For most users, these two directories are the same.

```
EOM
case "$installprefix" in
") dflt=$prefix ;;
*) dflt=$installprefix;;
esac
fi
fn=d~
rp='What installation prefix should I use for installing files?'
./getfile
installprefix="$ans"
installprefixexp="$ansexp"
```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/installdirs/installprefix.U
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 2000 Jarkko Hietaniemi

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?MAKE:d_strtold: Inlibc

?MAKE:-pick add \$@ %<

?S:d_strtold:

?S: This variable conditionally defines the HAS_STRTOLD symbol, which

?S: indicates to the C program that the strtold() routine is available.

?S:.

?C:HAS_STRTOLD:

?C: This symbol, if defined, indicates that the strtold routine is

?C: available to convert strings to long doubles.

?C:.

?H:#\$d_strtold HAS_STRTOLD /**/

?H:.

?LINT:set d_strtold

: see if strtold exists

set strtold d_strtold

eval \$inlibc

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_strtold.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: Compile.U,v \$

?RCS:

?RCS: Copyright (c) 1998 Andy Dougherty

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?RCS:

?X:

?X: This unit is just a quick shorthand for the compile command

?X: to be used in all the other metaconfig units.

?X:

?MAKE:Compile: +cc +optimize +ccflags +ldflags +libs test

?MAKE: -pick add \$@ %<

?LINT:extern usedevel

?LINT:define compile compile_ok

?V:compile compile_ok mc_file

?S:compile:

?S: This shell variable is used internally by Configure to provide

?S: a convenient shorthand for the typical compile command, namely

?S: \$cc \$optimize \$ccflags \$ldflags -o \$1 \$1.c \$libs > /dev/null 2>&1

?S: Note that the output filename does not include the _exe

?S: extension. Instead we assume that the linker will be

?S: "helpful" and automatically appending the correct suffix.

?S: OS/2 users

will apparently need to supply the -Zexe flag to

?S: get this behavior.

?S:

?S: To use this variable, say something like:

```

?S: echo 'int main() { exit(0); }' > try.c
?S: set try
?S: if eval $compile; then
?S: echo "success" # and do whatever . . .
?S: else
?S: echo "failure" # and do whatever . . .
?S: fi
?S: To add extra flags cc flags (e.g. -DWHATEVER) just put them
?S: in $*, e.g.
?S: set try -DTRY_THIS_FLAG
?S:.
?S:compile_ok:
?S: This shell variable is used internally by Configure to provide
?S: a convenient shorthand for the typical compile command that you
?S: expect to work ok. It is the same as $compile, except we
?S: deliberately let the user see any error messages.
?S:.
: define a shorthand compile call
compile='
mc_file=$1;
shift;
case "$usedevel" in $define|true|[yY]*) if $test ! -f "${mc_file}.c"; then
echo "Internal Configure script bug - compiler test file ${mc_file}.c is missing. Please report this to
perlbug@perl.org" >&4;
exit 1;
fi;
esac;
$cc -o ${mc_file}
$optimize $ccflags $ldflags $* ${mc_file}.c $libs > /dev/null 2>&1;'
: define a shorthand compile call for compilations that should be ok.
compile_ok='
mc_file=$1;
shift;
$cc -o ${mc_file} $optimize $ccflags $ldflags $* ${mc_file}.c $libs;'

```

Found in path(s):

```

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/compline/Compile.U

```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: d_sethent.U,v 3.0 1993/08/18 12:06:09 ram Exp $
```

```
?RCS:
```

```
?RCS: Copyright (c) 1991-1993, Raphael Manfredi
```

```
?RCS:
```

```
?RCS: You may redistribute only under the terms of the Artistic License,
```

```
?RCS: as specified in the README file that comes with the distribution.
```

```
?RCS: You may reuse parts of this distribution only within the terms of
```

```
?RCS: that same Artistic License; a copy of which may be found at the root
```

?RCS: of the source tree for dist 3.0.
?RCS:
?RCS: \$Log: d_sethent.U,v \$
?RCS: Revision 3.0 1993/08/18 12:06:09 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:d_sethent: Inlibc
?MAKE: -pick add \$@ %<
?S:d_sethent:
?S: This variable conditionally defines HAS_SETHOSTENT if sethostent() is
?S: available.
?S:.
?C:HAS_SETHOSTENT:
?C: This symbol, if defined, indicates that the sethostent() routine is
?C: available.
?C:.
?H:#\$d_sethent HAS_SETHOSTENT /**/
?H:.
?LINT:set d_sethent
: see if sethostent exists
set
sethostent d_sethent
eval \$inlibc

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/modified/d_sethent.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: \$Log: perlpath.U,v \$
?RCS: Revision 3.0.1.2 1995/09/25 09:17:04 ram
?RCS: patch59: unit is now forced to the top of Configure, if possible
?RCS:
?RCS: Revision 3.0.1.1 1995/01/11 15:33:53 ram
?RCS: patch45: can now use Loc variables since path stripping is deferred
?RCS:
?RCS: Revision 3.0 1993/08/18 12:09:32 ram
?RCS: Baseline for dist 3.0 netwide release.

```

?RCS:
?X:
?X: The purpose of this unit is to locate perl good enough to construct a #!
?X:
?MAKE:perlpath: Getfile Oldconfig Loc perl
?MAKE: -pick
add $@ %<
?Y:TOP
?S:perlpath:
?S: This variable contains the eventual value of the PERLPATH symbol,
?S: which contains the absolute location of the perl interpreter.
?S:.
?C:PERLPATH:
?C: This symbol contains the absolute location of the perl interpreter.
?C:.
?H:#define PERLPATH "$perlpath" /**/
?H:.
: determine perl absolute location
case "$perlpath" in
")
if test -f /usr/bin/perl; then
dflt=/usr/bin/perl
else
case "$perl" in
*/*) dflt="$perl";;
*) dflt=/usr/bin/perl;;
esac
fi
;;
*) dflt="$perlpath"
;;
esac
echo " "
fn=f~/
rp="Where is perl located on your system?"
./getfile
perlpath="$ans"

```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/perlpath.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: Null.U 1 2006-08-24 12:32:52Z rmanfredi $
```

```
?RCS:
```

```
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
```

```
?RCS:
```

```
?RCS: You may redistribute only under the terms of the Artistic Licence,
```

?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: \$Log: Null.U,v \$
?RCS: Revision 3.0 1993/08/18 12:05:10 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?X:
?X: This unit ends up producing shell code to set all variables to ". This
?X: probably isn't necessary, but I'm paranoid. About certain things.
?X:
?MAKE:Null: Head
?MAKE: -pick add.Null \$@ %<

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/Null.U

No license file was found, but licenses were detected in source scan.

Perl5 Metaconfig Units

Copyright (c) 1996-1998, Andy Dougherty
Copyright (c) 1999-2011, H.Merijn Brand
All rights reserved.

These units are the ones used to build Configure and config_h.SH
in the Perl5 distribution.

metaconfig will first look in its standard locations (specified when you
installed dist). It will then recurse through the 'U' subdirectory
and find any additional "private" units. Private units override
standard ones supplied with metaconfig.

Files in this directory:

README

This file.

Glossary.patch

The standard dist units contain some strings that make pod2man
complain. This patch silences those warnings. As new units are
added and Configure is regenerated, this patch may need more and more
'fuzz' to be applied. It should be freshly regenerated every once
in a while. See also mkgloss.pl

In-all.pl

Re-generate the all/ folder

mkglossary

A script

to regenerate Porting/Glossary. You have to manually edit the top of the script to point the location of your metaconfig units. It is called automatically by 'mksample'. See also mkgloss.pl

mkgloss.pl

A perl script that calls U/mkglossary from the perl source tree, sorts the list of symbols, and applies the patch mentioned in Glossary.patch. When called on its own, redirect the output to a temporary file, and compare that file to Porting/Glossary before applying.

mksample

A script to regenerate Porting/config.sh and Porting/config.H. It also calls mkglossary, if necessary.

Subdirectories:

The units and other related files have been broken up into the following directories.

a_dvisory/

These are units that have to go first in the generated config_h.SH. A word of explanation: Configure and config_h.SH are generated from 'Units' (the *.U files). Files indicate dependencies (using make(1)), and Configure is built to follow those dependencies.

However, config_h.SH

is simply built by putting all the units in alphabetical order and extracting the relevant lines. (This could be fixed, I suppose, but it wasn't trivial the one time I looked.)

The a_dvisory/ directory, then, is a place to put units that need to be early in config_h.SH. (Most units are self-contained and ought to be able to go anywhere. However, some things, like byteorder, need to have the #defines from multiarch available.)

acl/

This is an old patch to begin to detect and use ACL (access control list) file protection schemes.

all/

A folder that conveniently holds symbolic links to all the modules that are used to build the current Configure and config_h.SH.

compline/

These are similar to the standard units, but I have modified them to have a more uniform compile command line, usually using the

new Compile.U unit. (The cflags.U unit is perl-specific since it mentions -DDEBUGGING and -DPOSIX_SOURCE, but that's the only place it is perl-specific.)

dist_patches/

These are patches to dist that must be applied before it is built and installed. I have submitted these for inclusion in the regular dist distribution. They have already been applied to the ../dist-3.0at70b directory.

ebcdic/

These are units that had to be specially modified to work under either EBCDIC or ASCII.

installdirs/

These are units to handle perl's installation directories and related issues.

modified/

These are modified versions of the standard units. Also included in this directory are new units that are clearly derived from existing units. I have submitted these for inclusion in the regular dist distribution.

nullified/

These are null units that replace units in the standard distribution. Typically they are there because some part of the perl source accidentally uses a symbol that metaconfig means we want the corresponding unit.

perl/

These are specific to perl. Some are heavily derived from original dist units, and are marked as such. Others are original.

perl_patches/

These are patches to the perl source. This directory should ordinarily be empty, but there may have been drift between the standard version of perl and the one associated with these units.

protos/

These are units modified to use the new Hasproto.U or Protochk.U units to check for prototypes.

threads/

These are specific to threading perl.

typedefs/

These are standard units modified to use the modified Typedef.U unit to check for typedefs. (The modified Typdef.U includes a function to avoid unnecessary prompts if the typedef being searched for exists.)

Where appropriate, I submitted these units for inclusion into the regular dist distribution. However, since dist is no longer actively maintained, and the alternative is for *me* to actively maintain it, the units just sit here.

Copyright

Information:

Unless otherwise indicated, the files contained in this distribution are:

Copyright (c) 1996-1998, Andy Dougherty

The following licensing terms apply to all files contained in this distribution:

You may distribute the files contained in this distribution under the terms of either

- a) the "Artistic License" which comes with Perl, or
- b) the "Artistic License" which comes with dist, or
- c) the GNU General Public License as published by the Free Software Foundation; either version 1, or (at your option) any later version (see the file "Copying" that comes with the Perl distribution).

Which one to use is your choice.

The units in the "modified" directory have been derived from units associated with the metaconfig program of Raphael Manfredi's "dist" distribution. These units list Raphael Manfredi as the Copyright holder. dist is distributed under a modified version of the Perl Artistic License. Clause 7 of this modified license as contained in dist-3.0-pl60 provides:

- 7. You may reuse parts of this Package in your own programs, provided that you explicitly state where you got them from, in the source code (and, left to your courtesy, in the documentation), duplicating

all the associated copyright notices and disclaimers. Besides your changes, if any, must be clearly marked as such. Parts reused that way will no longer fall under this license if, and only if, the name of your program(s) have no immediate connection with the name of the Package itself or its associated programs. You may then apply whatever restrictions you wish on the reused parts or choose to place them in the Public Domain--this will apply only within the context of your package.

In accordance with this clause, the versions of these units contained here are made available under the same terms as the rest of the units.

If you have any questions about the use of these units or about the differences between these units and the standard versions, please feel free to ask.

Andy Dougherty doughera@lafayette.edu
Dept. of Physics
Lafayette College
Easton, PA 18042-1782

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/README
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: kernel.U 1 2006-08-24 12:32:52Z rmanfredi $
```

```
?RCS:
```

```
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
```

```
?RCS:
```

```
?RCS: You may redistribute only under the terms of the Artistic Licence,
```

```
?RCS: as specified in the README file that comes with the distribution.
```

```
?RCS: You may reuse parts of this distribution only within the terms of
```

```
?RCS: that same Artistic Licence; a copy of which may be found at the root
```

```
?RCS: of the source tree for dist 4.0.
```

```
?RCS:
```

```
?RCS: $Log: kernel.U,v $
```

```
?RCS: Revision 3.0 1993/08/18 12:08:54 ram
```

```
?RCS: Baseline for dist 3.0 netwide release.
```

```
?RCS:
```

```
?MAKE:kernel: Getfile test
```

```
?MAKE: -pick add $@ %<
```

```
?S:kernel:
```

```
?S: This variable becomes the (fully rooted) path name of the kernel.
```

```
?S:.
```

```
: find the name of the kernel.
```

```

echo " "
case "$kernel" in
")
if $test -r /unix; then
dflt=/unix
elif $test -r /vmunix; then
dflt=/vmunix
elif $test -r /xenix; then
dflt=/xenix
elif $test -r /mach; then
dflt=/mach
elif
$test -r /dgux; then
dflt=/dgux
elif $test -r /hp-ux; then
dflt=/hp-ux
elif $test -r /syst; then
dflt=/syst
elif $test -r /arix; then
dflt=/arix
elif $test -r /irix; then
dflt=/arix
else
dflt='unknown'
set X /*x
shift
case $# in
1)
if $test -r "$1"; then
dflt="$1"
fi
;;
esac
fi
;;
*)
dflt="$kernel"
;;
esac
fn=f
rp='What is the name of your kernel?'
./getfile
kernel="$ans"

```

Found in path(s):

```

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/kernel.U

```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: mallocsrc.U,v 3.0.1.2 1997/02/28 16:10:26 ram Exp $
?RCS:
?RCS: Copyright (c) 1991-1993, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 3.0.
?RCS:
?RCS: $Log: mallocsrc.U,v $
?RCS: Revision 3.0.1.2 1997/02/28 16:10:26 ram
?RCS: patch61: added support for Free_t, the type of free()
?RCS: patch61: replaced .o with $_o all over the place
?RCS:
?RCS: Revision 3.0.1.1 1994/05/06 15:10:46 ram
?RCS: patch23: added support for MYMALLOC, mainly for perl5 (ADO)
?RCS:
?RCS: Revision 3.0 1993/08/18 12:09:12 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:mallocsrc mallocobj usemallocwrap usemymalloc
malloctype d_mymalloc \
freetype: Myread \
Oldconfig package Guess Setvar rm cat +cc +ccflags Findhdr \
i_malloc i_stdlib sed libs _o ptrsize useithreads
?MAKE: -pick add $@ %<
?X: Put near top so that other tests don't erroneously include
?X: -lmalloc. --AD 22 June 1998
?Y:TOP
?S:usemymalloc:
?S: This variable contains y if the malloc that comes with this package
?S: is desired over the system's version of malloc. People often include
?S: special versions of malloc for efficiency, but such versions are often
?S: less portable. See also mallocsrc and mallocobj.
?S: If this is 'y', then -lmalloc is removed from $libs.
?S:.
?S:usemallocwrap:
?S: This variable contains y if we are wrapping malloc to prevent
?S: integer overflow during size calculations.
?S:.
?S:mallocsrc:
?S: This variable contains the name of the malloc.c that comes with
?S: the package, if that malloc.c is preferred over the system malloc.
?S: Otherwise the value is null. This variable is intended for generating
?S: Makefiles.
```

?S:
?S:d_mymalloc:
?S: This
variable conditionally defines MYMALLOC in case other parts
?S: of the source want to take special action if MYMALLOC is used.
?S: This may include different sorts of profiling or error detection.
?S:.
?S:mallocobj:
?S: This variable contains the name of the malloc.o that this package
?S: generates, if that malloc.o is preferred over the system malloc.
?S: Otherwise the value is null. This variable is intended for generating
?S: Makefiles. See malloccsrc.
?S:.
?S:freetype:
?S: This variable contains the return type of free(). It is usually
?S: void, but occasionally int.
?S:.
?S:malloctype:
?S: This variable contains the kind of ptr returned by malloc and realloc.
?S:.
?C:Free_t:
?C: This variable contains the return type of free(). It is usually
?C: void, but occasionally int.
?C:.
?C:Malloc_t (MALLOCPTRTYPE):
?C: This symbol is the type of pointer returned by malloc and realloc.
?C:.
?H:#define Malloc_t \$malloctype /**/
?H:#define Free_t
\$freetype /**/
?H:.
?C:PERL_MALLOC_WRAP:
?C: This symbol, if defined, indicates that we'd like malloc wrap checks.
?C:.
?H:\$Usemallocwrap PERL_MALLOC_WRAP /**/
?H:.
?C:MYMALLOC:
?C: This symbol, if defined, indicates that we're using our own malloc.
?C:.
?H:#\$d_mymalloc MYMALLOC /**/
?H:.
?LINT:extern usedevel
?LINT:change libs
?X: Cannot test for malloccsrc; it is the unit's name and there is a bug in
?X: the interpreter which defines all the names, even though they are not used.
@if mallocobj
: determine whether to use malloc wrapping
echo " "

```

case "$usemallocwrap" in
[yY]*|true|$define) dflt='y' ;;
[nN]*|false|$undef) dflt='n' ;;
*) case "$usedevel" in
[yY]*|true|$define) dflt='y' ;;
*) dflt='n' ;;
esac
;;
esac
rp="Do you wish to wrap malloc calls to protect against potential overflows?"
./myread
usemallocwrap="$ans"
case "$ans" in
y*|true)
usemallocwrap="$define" ;;
*)
usemallocwrap="$undef" ;;
esac

```

: determine which malloc to compile in

```

echo " "
case "$usemymalloc"
in
[yY]*|true|$define) dflt='y' ;;
[nN]*|false|$undef) dflt='n' ;;
*) case "$ptrsize" in
4) dflt='y' ;;
*) dflt='n' ;;
esac
if test "$useithreads" = "$define"; then dflt='n'; fi
;;
esac

```

rp="Do you wish to attempt to use the malloc that comes with \$package?"

```

./myread
usemymalloc="$ans"
case "$ans" in
y*|true)
usemymalloc='y'
mallosrc='malloc.c'
mallocobj="malloc$_o"
d_mymalloc="$define"

```

?X: Maybe libs.U should be dependent on mallosrc.U, but then

?X: most packages that use dist probably don't supply their own

?X: malloc, so this is probably an o.k. compromise

```

case "$libs" in
*-lmalloc*)

```

: Remove malloc from list of libraries to use

```

echo "Removing unneeded -lmalloc from library list" >&4

```

```

set `echo X $libs | $sed -e 's/-lmalloc / /' -e 's/-lmalloc$/'`
shift
libs="$*"
echo "libs = $libs" >&4
;;
esac
;;
*)
usemymalloc='n'
malloclsrc=""
malloclobj=""
d_mymalloc="$undef"
;;
esac

@end
@if MALLOC_PTRTYPE || Malloc_t || Free_t
: compute the return types of
malloc and free
echo " "
$cat >malloc.c <<END
#$i_malloc I_MALLOC
#$i_stdlib I_STDLIB
#include <stdio.h>
#include <sys/types.h>
#ifdef I_MALLOC
#include <malloc.h>
#endif
#ifdef I_STDLIB
#include <stdlib.h>
#endif
#ifdef TRY_MALLOC
void *malloc();
#endif
#ifdef TRY_FREE
void free();
#endif
END
@if MALLOC_PTRTYPE || Malloc_t
case "$malloctype" in
")
if $cc $ccflags -c -DTRY_MALLOC malloc.c >/dev/null 2>&1; then
malloctype='void *'
else
malloctype='char *'
fi
;;
esac

```

```

echo "Your system wants malloc to return '$malloctype', it would seem." >&4
@end

@if Free_t
case "$freetype" in
")
if $cc $ccflags -c -DTRY_FREE malloc.c >/dev/null 2>&1; then
freetype='void'
else
freetype='int'
fi
;;
esac
echo "Your system uses $freetype free(), it would seem." >&4
@end
$rm -f malloc.[co]
@end

```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/modified/mallocsrc.U
```

No license file was found, but licenses were detected in source scan.

```

?RCS: $Id: d_strcoll.U 1 2006-08-24 12:32:52Z rmanfredi $
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: Original Author: Andy Dougherty <doughera@lafcol.lafayette.edu>
?RCS:
?RCS: $Log: d_strcoll.U,v $
?RCS: Revision 3.0.1.1 1994/08/29 16:12:01 ram
?RCS: patch32: created by ADO
?RCS:
?MAKE:d_strcoll: Inlibc
?MAKE: -pick add $@ %<
?S:d_strcoll:
?S: This variable conditionally defines HAS_STRCOLL if strcoll() is
?S: available to compare strings using collating information.
?S:.
?C:HAS_STRCOLL:
?C: This symbol, if defined, indicates that the strcoll routine

```

is
?C: available to compare strings using collating information.
?C:.
?H:#\$d_strcoll HAS_STRCOLL /**/
?H:.
?LINT:set d_strcoll
: see if strcoll exists
set strcoll d_strcoll
eval \$inlibc

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/d_strcoll.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$
?RCS:
?RCS: Copyright (c) 1999, Jarkko Hietaniemi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 3.0.
?RCS:
?MAKE:d_mq_setattr: Inlibc
?MAKE:-pick add \$@ %<
?S:d_mq_setattr:
?S: This variable conditionally defines HAS_MQ_SETATTR if mq_setattr() is
?S: available to set the attributes of a POSIX message queue.
?S:.
?C:HAS_MQ_SETATTR:
?C: This symbol, if defined, indicates that the mq_setattr system call is
?C: available to set the attributes of a POSIX message queue.
?C:.
?H:#\$d_mq_setattr HAS_MQ_SETATTR /**/
?H:.
?LINT:set d_mq_setattr
: see if mq_setattr exists
set mq_setattr d_mq_setattr
eval \$inlibc

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_mq_setattr.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_setrgid.U 1 2006-08-24 12:32:52Z rmanfredi \$

?RCS:
 ?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
 ?RCS:
 ?RCS: You may redistribute only under the terms of the Artistic Licence,
 ?RCS: as specified in the README file that comes with the distribution.
 ?RCS: You may reuse parts of this distribution only within the terms of
 ?RCS: that same Artistic Licence; a copy of which may be found at the root
 ?RCS: of the source tree for dist 4.0.
 ?RCS:
 ?RCS: \$Log: d_setrgid.U,v \$
 ?RCS: Revision 3.0 1993/08/18 12:07:14 ram
 ?RCS: Baseline for dist 3.0 netwide release.
 ?RCS:
 ?MAKE:d_setrgid: Inlibc
 ?MAKE: -pick add \$@ %<
 ?S:d_setrgid:
 ?S: This variable conditionally defines the HAS_SETRGID symbol, which
 ?S: indicates to the C program that the setrgid() routine is available
 ?S: to change the real gid of the current program.
 ?S:.
 ?C:HAS_SETRGID (SETRGID):
 ?C: This symbol, if defined, indicates that the setrgid
 routine is available
 ?C: to change the real gid of the current program.
 ?C:.
 ?H:#\$d_setrgid HAS_SETRGID /**/
 ?H:.
 ?LINT:set d_setrgid
 : see if setrgid exists
 set setrgid d_setrgid
 eval \$inlibc

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/d_setrgid.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$
 ?RCS:
 ?RCS: Copyright (c) 1999, Jarkko Hietaniemi
 ?RCS:
 ?RCS: You may redistribute only under the terms of the Artistic License,
 ?RCS: as specified in the README file that comes with the distribution.
 ?RCS: You may reuse parts of this distribution only within the terms of
 ?RCS: that same Artistic License; a copy of which may be found at the root
 ?RCS: of the source tree for dist 3.0.
 ?RCS:
 ?MAKE:d_shm_unlink: Inlibc

```
?MAKE: -pick add $@ %<
?S:d_shm_unlink:
?S: This variable conditionally defines HAS_SHM_UNLINK if shm_unlink() is
?S: available to unlink a POSIX shared memory object.
?S:.
?C:HAS_SHM_UNLINK:
?C: This symbol, if defined, indicates that the shm_unlink system call is
?C: available to unlink a POSIX shared memory object.
?C:.
?H:#$d_shm_unlink HAS_SHM_UNLINK /**/
?H:.
?LINT:set d_shm_unlink
: see if shm_unlink exists
set shm_unlink d_shm_unlink
eval $inlibc
```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/perl/d_shm_unlink.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: h_fcntl.U 1 2006-08-24 12:32:52Z rmanfredi $
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: $Log: h_fcntl.U,v $
?RCS: Revision 3.0 1993/08/18 12:08:12 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:h_fcntl: Nothing
?MAKE: -pick add $@ %<
?S:h_fcntl:
?S: This is variable gets set in various places to tell i_fcntl that
?S: <fcntl.h> should be included.
?S:.
: Initialize h_fcntl
h_fcntl=false
```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/h_fcntl.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id$
?RCS:
?RCS: Copyright (c) 1997, Chip Salzenberg
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: $Log: sh.U,v $
?RCS: Revision 3.0.1.1 1997/02/28 16:20:13 ram
?RCS: patch61: created
?RCS:
?MAKE:sh: Head
?MAKE: -pick wipe $@ %<
?S:sh:
?S: This variable contains the full pathname of the shell used
?S: on this system to execute Bourne shell scripts. Usually, this will be
?S: /bin/sh, though it's possible that some systems will have /bin/ksh,
?S: /bin/pdksh, /bin/ash, /bin/bash, or even something such as
?S: D:/bin/sh.exe.
?S: This unit comes before Options.U,
?S: so you can't set sh with a -D
?S: option, though you can override this (and startsh)
?S: with -O -Dsh=/bin/whatever -Dstartsh=whatever
?S:.
?C:SH_PATH:
?C: This symbol contains the full pathname to the shell used on this
?C: on this system to execute Bourne shell scripts. Usually, this will be
?C: /bin/sh, though it's possible that some systems will have /bin/ksh,
?C: /bin/pdksh, /bin/ash, /bin/bash, or even something such as
?C: D:/bin/sh.exe.
?C:.
?H:#define SH_PATH "$sh" /**/
?H:.
?T:xxx try pth p SYSTYPE
?LINT:extern maintloc maintname
?X:
?X: Be quiet unless something unusual happens because this gets
?X: loaded up even before options are processed.
?X: Can't use ./loc because that depends on startsh, which, in turn
?X: depends on this unit.
?X:
: Find the basic shell for Bourne shell scripts
```

```

case "$sh" in
")
?X: SYSTYPE is for some older MIPS systems.
?X: I do not know if it is still needed.
case "$SYSTYPE" in
*bsd*|sys5*) xxx="/$SYSTYPE/bin/sh";;
*) xxx="/bin/sh";;
esac
if
test -f "$xxx"; then
sh="$xxx"
else
: Build up a list and do a single loop so we can 'break' out.
pth=`echo $PATH | sed -e "s/$p_/ /g"`
for xxx in sh bash ksh pdksh ash; do
for p in $pth; do
try="$try ${p}/${xxx}"
done
done
for xxx in $try; do
if test -f "$xxx"; then
sh="$xxx"
break
elif test -f "$xxx$_exe"; then
sh="$xxx"
break
elif test -f "$xxx.exe"; then
sh="$xxx"
break
fi
done
fi
;;
esac

```

?X: fd 4 isn't open yet...

```

case "$sh" in
") cat >&2 <<EOM
$me: Fatal Error: I can't find a Bourne Shell anywhere.

```

Usually it's in /bin/sh. How did you even get this far?
Please contact me (<\$maintname>) at <\$maintloc> and
we'll try to straighten this all out.

```

EOM
exit 1
;;
esac

```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/sh.U
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_setnetent_r.U,v 0RCS:

?RCS: Copyright (c) 2002,2003 Jarkko Hietaniemi

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?RCS: Generated by the reentr.pl from the Perl 5.8 distribution.

?RCS:

?MAKE:d_setnetent_r setnetent_r_proto: Inlibc Protochk Hasproto i_systypes \
 usethreads i_netdb extern_C

?MAKE: -pick add \$@ %<

?S:d_setnetent_r:

?S: This variable conditionally defines the HAS_SETNETENT_R symbol,

?S: which indicates to the C program that the setnetent_r()

?S: routine is available.

?S:.

?S:setnetent_r_proto:

?S: This variable encodes the prototype of setnetent_r.

?S: It is zero if d_setnetent_r is undef, and one of the

?S: REENTRANT_PROTO_T_ABC macros of reentr.h if d_setnetent_r

?S: is defined.

?S:.

?C:HAS_SETNETENT_R:

?C: This symbol, if defined, indicates that the setnetent_r routine

?C: is

available to setnetent re-entrantly.

?C:.

?C:SETNETENT_R_PROTO:

?C: This symbol encodes the prototype of setnetent_r.

?C: It is zero if d_setnetent_r is undef, and one of the

?C: REENTRANT_PROTO_T_ABC macros of reentr.h if d_setnetent_r

?C: is defined.

?C:.

?H:#\$d_setnetent_r HAS_SETNETENT_R /**/

?H:#define SETNETENT_R_PROTO \$setnetent_r_proto /**/

?H:.

?T:try hdrs d_setnetent_r_proto

: see if setnetent_r exists

set setnetent_r d_setnetent_r

eval \$inlibc

case "\$d_setnetent_r" in

"\$define")

hdrs="\$i_systypes sys/types.h define stdio.h \$i_netdb netdb.h"

```

case "$d_setnetent_r_proto:$susetheads" in
":define") d_setnetent_r_proto=define
set d_setnetent_r_proto setnetent_r $hdrs
eval $hasproto ;;
*) ;;
esac
case "$d_setnetent_r_proto" in
define)
case "$setnetent_r_proto" in
"|0) try='int setnetent_r(int, struct netent_data*);'
./protochk "$xtern_C $try" $hdrs && setnetent_r_proto=I_ID ;;
esac
case "$setnetent_r_proto" in
"|0) try='void setnetent_r(int, struct netent_data*);'
./protochk
"$xtern_C $try" $hdrs && setnetent_r_proto=V_ID ;;
esac
case "$setnetent_r_proto" in
"|0) d_setnetent_r=undef
setnetent_r_proto=0
echo "Disabling setnetent_r, cannot determine prototype." >&4 ;;
*) case "$setnetent_r_proto" in
REENTRANT_PROTO*) ;;
*) setnetent_r_proto="REENTRANT_PROTO_${setnetent_r_proto}" ;;
esac
echo "Prototype: $try" ;;
esac
;;
*) case "$susetheads" in
define) echo "setnetent_r has no prototype, not using it." >&4 ;;
esac
d_setnetent_r=undef
setnetent_r_proto=0
;;
esac
;;
*) setnetent_r_proto=0
;;
esac

```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/threads/d_setnetent_r.U
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: Configdir.U 1 2006-08-24 12:32:52Z rmanfredi \$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: \$Log: Configdir.U,v \$
?RCS: Revision 3.0.1.1 1997/02/28 14:58:36 ram
?RCS: patch61: have README explicitly mention the package name
?RCS:
?RCS: Revision 3.0 1993/08/18 12:04:49 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:Configdir: package
?MAKE: -pick add \$@ %<
: create .config dir to save info across Configure sessions
test -d ../.config || mkdir ../.config
cat >../.config/README <<EOF
This directory created by Configure to save
information that should
persist across sessions for \$package.

You may safely delete it if you wish.

EOF

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/Configdir.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: afs.U 1 2006-08-24 12:32:52Z rmanfredi \$
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: \$Log: afs.U,v \$
?RCS: Revision 3.0.1.2 1997/02/28 15:23:06 ram
?RCS: patch61: can now explicitly tell Configure whether AFS is running
?RCS:
?RCS: Revision 3.0.1.1 1993/08/24 12:24:43 ram
?RCS: patch3: created
?RCS:

```

?MAKE:afs afsroot: test
?MAKE: -pick add $@ %<
?S:afs:
?S: This variable is set to 'true' if AFS (Andrew File System) is used
?S: on the system, 'false' otherwise. It is possible to override this
?S: with a hint value or command line option,
    but you'd better know
?S: what you are doing.
?S:.
?S:afsroot:
?S: This variable is by default set to '/afs'. In the unlikely case
?S: this is not the correct root, it is possible to override this with
?S: a hint value or command line option. This will be used in subsequent
?S: tests for AFSness in the configure and test process.
?S:.
: allow them to override the AFS root
case "$afsroot" in
") afsroot=/afs ;;
*) afsroot=$afsroot ;;
esac

: is AFS running?
echo " "
case "$afs" in
$define|true) afs=true ;;
$undef|false) afs=false ;;
*) if $test -d $afsroot; then
    afs=true
    else
    afs=false
    fi
;;
esac
if $afs; then
    echo "AFS may be running... I'll be extra cautious then..." >&4
else
    echo "AFS does not seem to be running..." >&4
fi

```

Found in path(s):

```

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/afs.U

```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1998 Jarkko Hietaniemi

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?X: This unit generates a \$hasfield string that is used internally

?X: by Configure to check if this system has a field for a

?X: particular struct (of if this system has a particular struct!)

?X:

?X: To use it, say something like:

?X: set d_statblocks stat st_blocks i_sysstat sys/stat.h

?X: eval \$hasfield

?X: Or, for more complicated sets of headers, do something like

?X: hdrs="\$define sys/foo.h

?X: \$i_sysbar sys/bar.h

?X: \$i_syszot sys/zot.h

?X: \$i_zappa zappa.h"

?X: set d_statblocks stat st_blocks \$hdrs

?X: eval \$hasfield

?X:

?MAKE:Hasfield: Setvar rm_try test Compile

?MAKE: -pick add \$@ %<

?T:varname struct field

?V:hasfield

: Define hasfield macro for Configure internal use

```
hasfield='varname=$1;
```

```
struct=$2; field=$3; shift; shift; shift;
```

```
while $test $# -ge 2; do
```

```
case "$1" in
```

```
$define) echo "#include <$2>";;
```

```
esac ;
```

```
shift 2;
```

```
done > try.c;
```

```
echo "int main () { struct $struct foo; char* bar; bar = (char*)foo.$field; }" >> try.c;
```

```
set try;
```

```
if eval $compile; then
```

```
val="$define";
```

```
else
```

```
val="$undef";
```

```
fi;
```

```
set $varname;
```

```
eval $setvar;
```

```
$rm_try'
```

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/protos/Hasfield.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_crypt.U 1 2006-08-24 12:32:52Z rmanfredi \$

```

?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: $Log: d_crypt.U,v $
?RCS: Revision 3.0.1.1 1997/02/28 15:31:47 ram
?RCS: patch61: replaced .a with $_a all over the place
?RCS:
?RCS: Revision 3.0 1993/08/18 12:05:52 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:d_crypt cryptlib: Loc test xlibpth libpth Csym Setvar _a Inlibc
?MAKE: -pick add $@ %<
?S:d_crypt:
?S: This variable conditionally defines the CRYPT symbol, which
?S: indicates to the C program that the crypt() routine is available
?S: to
encrypt passwords and the like.
?S:.
?S: cryptlib:
?S: This variable holds -lcrypt or the path to a libcrypt.a archive if
?S: the crypt() function is not defined in the standard C library. It is
?S: up to the Makefile to use this.
?S:.
?C:HAS_CRYPT (CRYPT):
?C: This symbol, if defined, indicates that the crypt routine is available
?C: to encrypt passwords and the like.
?C:.
?H:#$d_crypt HAS_CRYPT /**/
?H:.
?LINT:set d_crypt
?T:val
: see if crypt exists
echo " "
set crypt d_crypt
eval $inlibc
case "$d_crypt" in
$define) cryptlib=" ;;
*) if set crypt val -f d_crypt; eval $csym; $val; then
echo 'crypt() found.' >&4
val="$define"
cryptlib="
else

```

```

cryptlib=`./loc Slibcrypt$_a "" $xlibpth`
if $test -z "$cryptlib"; then
  cryptlib=`./loc Mlibcrypt$_a "" $xlibpth`
else
  cryptlib=-lcrypt
fi
if $test -z "$cryptlib"; then
  cryptlib=`./loc Libcrypt$_a "" $xlibpth`
else
  cryptlib=-lcrypt
fi
if $test -z "$cryptlib"; then
  cryptlib=`./loc libcrypt$_a ""
$libpth`
else
  cryptlib=-lcrypt
fi
if $test -z "$cryptlib"; then
  echo 'crypt() NOT found.' >&4
  val="$undef"
else
  val="$define"
fi
fi
set d_crypt
eval $setvar
;;
esac

```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/d_crypt.U
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_strchr.U 1 2006-08-24 12:32:52Z rmanfredi \$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic Licence,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic Licence; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: d_strchr.U,v \$

?RCS: Revision 3.0.1.2 1993/10/16 13:49:20 ram

?RCS: patch12: added support for HAS_INDEX

?RCS: patch12: added magic for index() and rindex()

```

?RCS:
?RCS: Revision 3.0.1.1 1993/09/13 16:05:26 ram
?RCS: patch10: now only defines HAS_STRCHR, no macro remap of index (WAD)
?RCS:
?RCS: Revision 3.0 1993/08/18 12:07:32 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:d_strchr d_index: contains strings Setvar Myread Oldconfig
Csym
?MAKE: -pick add $@ %<
?S:d_strchr:
?S: This variable conditionally defines HAS_STRCHR if strchr() and
?S: strrchr() are available for string searching.
?S:.
?S:d_index:
?S: This variable conditionally defines HAS_INDEX if index() and
?S: rindex() are available for string searching.
?S:.
?C:HAS_STRCHR:
?C: This symbol is defined to indicate that the strchr()/strrchr()
?C: functions are available for string searching. If not, try the
?C: index()/rindex() pair.
?C:.
?C:HAS_INDEX:
?C: This symbol is defined to indicate that the index()/rindex()
?C: functions are available for string searching.
?C:.
?H:#$d_strchr HAS_STRCHR /**/
?H:#$d_index HAS_INDEX /**/
?H:.
?M:index: HAS_INDEX
?M:#ifndef HAS_INDEX
?M:#ifndef index
?M:#define index strchr
?M:#endif
?M:#endif
?M:.
?M:rindex: HAS_INDEX
?M:#ifndef HAS_INDEX
?M:#ifndef rindex
?M:#define rindex strrchr
?M:#endif
?M:#endif
?M:.
?T:vali
?LINT:set d_strchr d_index
: index or strchr
echo " "

```

```

if set index val -f; eval $csym; $val; then
if
set strchr val -f d_strchr; eval $csym; $val; then
if $contains strchr "$strings" >/dev/null 2>&1 ; then
?X: has index, strchr, and strchr in string header
val="$define"
vali="$undef"
echo "strchr() found." >&4
else
?X: has index, strchr, and no strchr in string header
val="$undef"
vali="$define"
echo "index() found." >&4
fi
else
?X: has only index, no strchr, string header is a moot point
val="$undef"
vali="$define"
echo "index() found." >&4
fi
else
if set strchr val -f d_strchr; eval $csym; $val; then
val="$define"
vali="$undef"
echo "strchr() found." >&4
else
echo "No index() or strchr() found!" >&4
val="$undef"
vali="$undef"
fi
fi
set d_strchr; eval $setvar
val="$vali"
set d_index; eval $setvar

```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/d_strchr.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: d_linuxstd.U 1 2006-08-24 12:32:52Z rmanfredi $
```

```
?RCS:
```

```
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
```

```
?RCS:
```

```
?RCS: You may redistribute only under the terms of the Artistic Licence,
```

```
?RCS: as specified in the README file that comes with the distribution.
```

```
?RCS: You may reuse parts of this distribution only within the terms of
```

```
?RCS: that same Artistic Licence; a copy of which may be found at the root
```

```

?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: Original Author: Andy Dougherty <doughera@lafcol.lafayette.edu>
?RCS:
?RCS: $Log: d_linuxstd.U,v $
?RCS: Revision 3.0.1.1 1994/10/29 16:14:05 ram
?RCS: patch36: created by ADO
?RCS:
?MAKE:d_linuxstd: d_stdstdio cppstdin cppflags cppminus \
contains rm Setvar Findhdr
?MAKE: -pick add $@ %<
?S:d_linuxstd:
?S: This variable conditionally defines USE_LINUX_STDIO if this system
?S: has a FILE structure declaring _IO_read_base, _IO_read_ptr,
?S: and _IO_read_end
?S: in stdio.h.
?S:.
?C:USE_LINUX_STDIO:
?C: This symbol is defined if this system has a FILE structure declaring
?C: _IO_read_base, _IO_read_ptr, and _IO_read_end in stdio.h.
?C:.
?H:#$d_linuxstd USE_LINUX_STDIO /**/
?H:.
?T:xxx
?LINT:set d_linuxstd
: see if stdio is like that in linux
case "$d_stdstdio" in
"$undef")
echo " "
xxx=`./findhdr stdio.h`
$cppstdin $cppflags $cppminus < "$xxx" > stdio.E
if $contains 'char.*_IO_read_base' stdio.E >/dev/null 2>&1 && \
$contains '_IO_read_ptr' stdio.E >/dev/null 2>&1 && \
$contains '_IO_read_end' stdio.E >/dev/null 2>&1 ; then
echo "Your stdio looks like linux." >&4
val="$define"
else
echo "You don't have linux stdio, either." >&4
val="$undef"
fi
$rm -f stdio.E
;;
*) val="$undef" ;;
esac

set d_linuxstd
eval $setvar

```

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/d_linuxstd.U

No license file was found, but licenses were detected in source scan.

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?MAKE:d_nextafter: Inlibc

?MAKE: -pick add \$@ %<

?S:d_nextafter:

?S: This variable conditionally defines HAS_NEXTAFTER if nextafter()

?S: is available to return the next machine representable double from

?S: x in direction y.

?S:.

?C:HAS_NEXTAFTER:

?C: This symbol, if defined, indicates that the nextafter routine is

?C: available to return the next machine representable double from

?C: x in direction y.

?C:.

?H:#\$d_nextafter HAS_NEXTAFTER /**/

?H:.

?LINT:set d_nextafter

: see if nextafter exists

set nextafter d_nextafter

eval \$inlibc

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_nextafter.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_tcstgrp.U 1 2006-08-24 12:32:52Z rmanfredi \$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic Licence,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic Licence; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: Original Author: Andy Dougherty <doughera@lafcol.lafayette.edu>

?RCS:

?RCS: \$Log: d_tcstgrp.U,v \$

?RCS: Revision 3.0.1.1 1994/08/29 16:12:11 ram

?RCS: patch32: created by ADO

?RCS:

```
?MAKE:d_tcsetpgrp: Inlibc
?MAKE: -pick add $@ %<
?S:d_tcsetpgrp:
?S: This variable conditionally defines the HAS_TCSETPGRP symbol, which
?S: indicates to the C program that the tcsetpgrp() routine is available
?S: to set foreground process group ID.
?S:.
?C:HAS_TCSETPGRP
:
?C: This symbol, if defined, indicates that the tcsetpgrp routine is
?C: available to set foreground process group ID.
?C:.
?H:#$d_tcsetpgrp HAS_TCSETPGRP /**/
?H:.
?LINT:set d_tcsetpgrp
: see if tcsetpgrp exists
set tcsetpgrp d_tcsetpgrp
eval $inlibc
```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/d_tcstpgrp.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: i_fp.U,v $
?RCS:
?RCS: Copyright (c) 1998 Jarkko Hietaniemi
?RCS:
?RCS: You may distribute under the terms of either the GNU General Public
?RCS: License or the Artistic License, as specified in the README file.
?RCS:
?MAKE:i_fp: Inhdr
?MAKE: -pick add $@ %<
?S:i_fp:
?S: This variable conditionally defines the I_FP symbol, and indicates
?S: whether a C program should include <fp.h>.
?S:.
?C:I_FP:
?C: This symbol, if defined, indicates that <fp.h> exists and
?C: should be included.
?C:.
?H:#$i_fp I_FP /**/
?H:.
?LINT:set i_fp
: see if this is a fp.h system
set fp.h i_fp
eval $inhdr
```

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/i_fp.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: html1dir.U,v \$

?RCS:

?RCS: Copyright (c) 1999 Andy Dougherty

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 3.0.

?RCS:

?RCS: \$Log: html1dir.U,v \$

?RCS:

?MAKE:html1dir html1direxp installhtml1dir: cat Loc Myread \

package test Getfile Setprefixvar Prefixit Prefixup

?MAKE: -pick add \$@ %<

?Y:TOP

?D:html1dir="

?S:html1dir:

?S: This variable contains the name of the directory in which html

?S: source pages are to be put. This directory is for pages

?S: that describe whole programs, not libraries or modules. It

?S: is intended to correspond roughly to section 1 of the Unix

?S: manuals.

?S:.

?D:html1direxp="

?S:html1direxp:

?S: This

variable is the same as the html1dir variable, but is filename

?S: expanded at configuration time, for convenient use in makefiles.

?S:.

?D:installhtml1dir="

?S:installhtml1dir:

?S: This variable is really the same as html1direxp, unless you are

?S: using a different installprefix. For extra portability, you

?S: should only use this variable within your makefiles.

?S:.

?LINT:change prefixvar

?LINT:set html1direxp

?LINT:set installhtml1dir

: determine where html pages for programs go

set html1dir html1dir none

eval \$prefixit

\$cat <<EOM

If you wish to install html files for programs in \$spackage, indicate the appropriate directory here. To skip installing html files, answer "none".

EOM

```
case "$html1dir" in
"|none|$undef|' ') dflt=none ;;
*) dflt=$html1dir ;;
esac
fn=dn+~
rp="Directory for the main $spackage html pages?"
./getfile
prefixvar=html1dir
./setprefixvar
: Use ' ' for none so value is preserved next time through Configure
$test X"$html1dir" = "X" && html1dir=' '
```

Found

in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/installdirs/html1dir.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: Finish.U,v \$

?RCS: Revision 3.0.1.6 1995/02/15 14:09:30 ram

?RCS: patch51: now clearer about how to edit config.sh at the prompt (WED)

?RCS:

?RCS: Revision 3.0.1.5 1994/10/29 15:53:14 ram

?RCS: patch36: added ?F: line for metalint file checking

?RCS:

?RCS: Revision 3.0.1.4 1994/05/06 14:19:37 ram

?RCS: patch23: added blank lines around 'End of Configure'

?RCS:

?RCS: Revision 3.0.1.3 1993/10/16 13:46:09 ram

?RCS: patch12: replaced Config_h by Magic_h in the dependency line

?RCS:

?RCS:

Revision 3.0.1.2 1993/09/13 15:45:26 ram

?RCS: patch10: fixed shell evaluation w/o shell escape while in silent mode

?RCS:

?RCS: Revision 3.0.1.1 1993/08/30 08:55:59 ram

?RCS: patch8: prevents myread from blocking on empty answers, exceptionally

?RCS:

?RCS: Revision 3.0 1993/08/18 12:04:55 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?X:

?X: This unit is the very last one in the Configure script. It runs all the

?X: SH files, which among other things produce config.h and (usually) Makefile.

?X: It offers to do a make depend if the Makefile contains that target.

?X:

?MAKE:Finish: Chk_MANI Extract Myread Oldsym Magic_h cat rm contains \
test package make

?MAKE: -pick add \$@ %<

?F:!config.sh

?T:pwd

: Finish up by extracting the .SH files

case "\$alldone" in

exit)

?X: They supplied the -E switch

echo "Stopping at your request, leaving temporary files around."

exit 0

::

cont)

::

")

dflt="

nostick=true

\$cat <<EOM

If you'd like to make any changes to the config.sh

file before I begin

to configure things, do it as a shell escape now (e.g. !vi config.sh).

EOM

rp="Press return or use a shell escape to edit config.sh:"

. UU/myread

nostick="

case "\$ans" in

") ;;

*) : in case they cannot read

sh 1>&4 -c "\$ans";;

esac

::

esac

: if this fails, just run all the .SH files by hand

```
./config.sh
```

?X:

?X: Turn silent mode off from now on (we want a verbose file extraction).

?X: This means we have to explicitly test for '\$silent' from now on to

?X: strip off any verbose messages.

?X:

```
echo " "
```

```
exec 1>&4
```

```
pwd=`pwd`
```

```
./UU/extract
```

```
cd "$pwd"
```

```
if $contains '^depend:' [Mm]akefile >/dev/null 2>&1; then
```

```
dfit=y
```

```
case "$silent" in
```

```
true) ;;
```

```
*)
```

```
  $cat <<EOM
```

Now you need to generate make dependencies by running "\$make depend".

You might prefer to run it in background: "\$make depend > makedepend.out &"

It can take a while, so you might not want to run it right now.

EOM

```
;;
```

```
esac
```

```
rp="Run $make depend now?"
```

```
. UU/myread
```

```
case "$ans" in
```

```
y*)
```

```
  $make depend
```

```
&& echo "Now you must run '$make'."
```

```
;;
```

```
*)
```

```
  echo "You must run '$make depend' then '$make'."
```

```
;;
```

```
esac
```

```
elif test -f [Mm]akefile; then
```

```
echo " "
```

```
echo "Now you must run a $make."
```

```
else
```

```
echo "Configure done."
```

```
fi
```

```
if $test -f Policy.sh; then
```

\$cat <<EOM

If you compile \$package on a different machine or from a different object directory, copy the Policy.sh file from this object directory to the new one before you run Configure -- this will help you with most of the policy defaults.

EOM

fi

```
if $test -f UU/config.msg; then
```

```
    echo "Hmm. I also noted the following information while running:"
```

```
    echo " "
```

```
    $cat UU/config.msg >&4
```

```
fi
```

?X:

?X: kit*isdone files are left over by shell archives built using the makedist

?X: script which comes from dist, while ark*isdone files are left over by

?X: the cshar archive maker.

?X:

```
$rm -f kit*isdone ark*isdone
```

```
$rm -rf UU
```

: End of Configure

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/Finish.U
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 2001 Jarkko Hietaniemi

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?MAKE:run to from targetarch targetdir targetmkdir targethost targetport \

usecrosscompile hostperl hostgenerate hostosname targetenv: \

src test rm echo sed mkdir cp chmod make touch

?MAKE: -pick add \$@ %<

?Y:TOP

?S:usecrosscompile:

?S: This variable conditionally defines the USE_CROSS_COMPILE symbol,

?S: and indicates that Perl has been cross-compiled.

?S:.

?S:run:

?S: This variable contains the command used by Configure

?S: to copy and execute a cross-compiled executable in the

?S: target host. Useful and available only during Perl build.
?S: Empty string " if not cross-compiling.
?S:.
?S:from:
?S: This variable contains the command used by Configure
?S: to copy files from the target host. Useful
and available
?S: only during Perl build.
?S: The string ':' if not cross-compiling.
?S:.
?S:to:
?S: This variable contains the command used by Configure
?S: to copy to from the target host. Useful and available
?S: only during Perl build.
?S: The string ':' if not cross-compiling.
?S:.
?S:targetarch:
?S: If cross-compiling, this variable contains the target architecture.
?S: If not, this will be empty.
?S:.
?S:targetdir:
?S: This variable contains a path that will be created on the target
?S: host using targetmkdir, and then used to copy the cross-compiled
?S: executables to. Defaults to '/tmp' if not set.
?S:.
?S:targetmkdir:
?S: This variable contains the command used by Configure to create a
?S: new directory on the target host.
?S:.
?S:targethost:
?S: This variable contains the name of a separate host machine that
?S: can be used to run compiled test programs and perl tests on.
?S: Set to empty string if not in use.
?S:.
?S:targetport:
?S: This variable contains the number
of a network port to be used to
?S: connect to the host in targethost, if unset defaults to 22 for ssh.
?S:.
?S:hostperl:
?S: This variable contains the path to a miniperl binary that can be
?S: run on the host OS when cross-compiling. Useful and available only
?S: during Perl build.
?S: Empty string " if not cross-compiling.
?S:.
?S:hostgenerate:
?S: This variable contains the path to a generate_uudmap binary that
?S: can be run on the host OS when cross-compiling. Useful and

?S: available only during Perl build.

?S: Empty string " if not cross-compiling.

?S:.

?S:hostosname:

?S: This variable contains the original value of '\$^O' for hostperl

?S: when cross-compiling. This is useful to pick the proper tools

?S: when running build code in the host.

?S: Empty string " if not cross-compiling.

?S:.

?S:targetenv:

?S: If cross-compiling, this variable can be used to modify the

?S: environment on the target system.

?S: However, how and where it's used, and even if it's used at all, is

?S: entirely

dependent on both the transport mechanism (targetrun) and

?S: what the target system is. Unless the relevant documentation says

?S: otherwise, it is generally not useful.

?S:.

?C:USE_CROSS_COMPILE:

?C: This symbol, if defined, indicates that Perl is being cross-compiled.

?C:.

?C:PERL_TARGETARCH:

?C: This symbol, if defined, indicates the target architecture

?C: Perl has been cross-compiled to. Undefined if not a cross-compile.

?C:.

?H:?%<:#ifndef USE_CROSS_COMPILE

?H:?%<:#\$usecrosscompile USE_CROSS_COMPILE /**/

?H:?%<:#define PERL_TARGETARCH "\$targetarch" /**/

?H:?%<:#endif

?H:.

?D:targetenv="

?D:targethost="

?D:targetmkdir="

?T:croak pwd exe f q cwd file xxx env

?LINT:extern usecrosscompile

?LINT:extern cc

?LINT:extern usrinc

?LINT:change ar

?LINT:change nm

?LINT:change ranlib

?LINT:change src

?LINT:extern targetenv

?LINT:extern targetport

?LINT:extern targetdir

?LINT:extern targetuser

?LINT:change targetuser

?LINT:extern targetrun

?LINT:extern targetfrom

```

?LINT:extern
targetto
?LINT:change targetrun
?LINT:change targetfrom
?LINT:change targetto
?LINT:extern incpth
?LINT:extern libpth
?LINT:extern locincpth
?LINT:extern loclibpth
?LINT:change locincpth
?LINT:change loclibpth
?LINT:extern hostperl
?LINT:extern hostgenerate
?LINT:extern before_host
?LINT:change before_host
?LINT:extern hostosname
?LINT:extern multiarch
: Check for Cross-Compilation
?X: targethost and targetenv mainly set to allow ?S: documentation
?X: otherwise it could have been declared extern
if $test "X$targethost" = "X"; then
    targethost=""
fi
if $test "X$targetenv" = "X"; then
    targetenv=""
fi
case "$usecrosscompile" in
$define|true|[yY]*)
    $echo "Cross-compiling..."
    croak=""
    case "$cc" in
*-gcc*|*-g++*) # A cross-compiling gcc, probably.
        # arm-linux-androideabi-gcc -> arm-linux-androideabi
        # x86_64-w64-mingw32-gcc.exe -> x86_64-w64-mingw32
        targetarch=`$echo $cc|$sed 's/-g[c+][c+].*$/^`
        ar=`$echo $cc|$sed 's/-g[c+][c+]/-ar/^`
        # leave out ld,
choosing it is more complex
        nm=`$echo $cc|$sed 's/-g[c+][c+]/-nm/^`
        ranlib=`$echo $cc|$sed 's/-g[c+][c+]/-ranlib/^`
        # We are in a weird spot. Just before us, some values
        # were 'saved', to be restored after the hints are
        # run. This means that the changes we made to ar,
        # nm and ranlib will get reverted.
        # To avoid that, we hijack the saving mechanism and
        # have it save our new values.
        for file in ar nm ranlib; do
            eval xxx=\$$file

```

```

eval $file=$xxx$_exe
eval _$file=$xxx
done
;;
esac
case "$targetarch" in
") echo "Targetarch not defined." >&4; croak=y ;;
*) echo "Using targetarch $targetarch." >&4 ;;
esac
case "$targethost" in
") echo "Targethost not defined." >&4; croak=n ;;
*) echo "Using targethost $targethost." >&4
esac
locincpth=' '
loclibpth=' '
case "$croak" in
y) echo "Cannot continue, aborting." >&4; exit 1 ;;
esac
: compile a host miniperl and generate_uudmap, unless we got passed them
if
$test "X$hostperl" = X; then
echo "Building host miniperl and generate_uudmap binaries" >&4
before_host=`pwd`
cd ..
cd $src
src=`pwd`
rm -rf $src/host
mkdir $src/host
cd $src/host
$src/Configure -des -Dusedevel -Dmksymlinks
$make miniperl
case "$hostgenerate" in
") $make generate_uudmap
hostgenerate=$src/host/generate_uudmap
;;
"$undef") hostgenerate="
;;
esac
hostperl=$src/host/miniperl
cd $before_host
fi
hostosname=`$hostperl -le 'print $^O`
;;
*)
usecrosscompile="$undef"
;;
esac

```

```

: Define -Dtargethost=somecomputer to run compiled tests on another machine
case "$targethost" in
  *) echo "Checking for cross-compile" >&4
  case "$susecrosscompile$multiarch" in
    *$define*) echo "Skipping the try tests in the rest of Configure as no targethost was defined when cross-
compiling" >&4
    if [ -f Makefile ]; then
      echo
    " "
      echo "Now you must ensure config.sh, config.h and the generated headers exist and run a $make."
    else
      echo "Configure done."
    fi
    exit 0
    ;;
  *) echo "No targethost for running compiler tests against defined, running locally" >&4
    run="
to=:
from=:
    ;;
  esac
  ;;
  *) echo "Using targethost $targethost." >&4
case "$src" in
/*) run=$src/Cross/run
  targetmkdir=$src/Cross/mkdir
  to=$src/Cross/to
  from=$src/Cross/from
  ;;
*) pwd=`$test -f ../Configure & cd ..; pwd`
  run=$pwd/Cross/run
  targetmkdir=$pwd/Cross/mkdir
  to=$pwd/Cross/to
  from=$pwd/Cross/from
  ;;
  esac
case "$targetrun" in
  *) targetrun=ssh ;;
  esac
case "$targetto" in
  *) targetto=scp ;;
  esac
case "$targetfrom" in
  *) targetfrom=scp ;;
  esac
run=$run-$targetrun
to=$to-$targetto
from=$from-$targetfrom

```

```

case "$targetdir" in
") targetdir=/tmp
    echo "Guessing targetdir $targetdir."
>&4
    ;;
esac
case "$targetuser" in
") targetuser=root
    echo "Guessing targetuser $targetuser." >&4
    ;;
esac
case "$targetport" in
") targetport=22
    echo "Guessing targetport $targetport." >&4
    ;;
esac
case "$targetfrom" in
scp) q=-q ;;
*) q=" ;;
esac
case "$targetrun" in
ssh|rsh)
    cat >$run <<EOF
#!/bin/sh
env="
case "\$1" in
-cwd)
    shift
    cwd=\$1
    shift
    ;;
esac
case "\$1" in
-env)
    shift
    env=\$1
    shift
    ;;
esac
case "\$cwd" in
") cwd=$targetdir ;;
esac
exe=\$1
shift
$to \$exe
$targetrun -p $targetport -l $targetuser $targethost "cd \$cwd && \$env \$exe \$@"
EOF
    ;;

```

```

adb)
    $touch $run
    ;;
*) echo "Unknown targetrun '$targetrun'" >&4
    exit 1
    ;;
esac
case "$targetmkdir" in
*/Cross/mkdir)
    cat >$targetmkdir <<EOF
#!/bin/sh
$targetrun -p $targetport -l $targetuser $targethost "mkdir -p \$@"
EOF
    $chmod a+rx $targetmkdir
    ;;
*) echo "Unknown targetmkdir '$targetmkdir'" >&4
    exit 1
    ;;
esac
case
"$targetto" in
scp|rcp)
    cat >$to <<EOF
#!/bin/sh
for f in \$@
do
case "\$f" in
/*)
    $targetmkdir \dirname \$f\
    $targetto -P $targetport -r \$q \$f $targetuser@$targethost:\$f      2>/dev/null || exit 1
    ;;
*)
    $targetmkdir $targetdir/\dirname \$f\
    $targetto -P $targetport -r \$q \$f $targetuser@$targethost:$targetdir/\$f 2>/dev/null || exit 1
    ;;
esac
done
exit 0
EOF
    ;;
cp) cat >$to <<EOF
#!/bin/sh
for f in \$@
do
case "\$f" in
/*)
    $mkdir -p $targetdir/\dirname \$f\
    $scp \$f $targetdir/\$f || exit 1

```

```

;;
*)
    $targetmkdir $targetdir/\dirname \$f\
    $cp \$f $targetdir/\$f || exit 1
;;
esac
done
exit 0
EOF
;;
*) echo "Unknown targetto '$targetto'" >&4
    exit 1
;;
esac
case "$targetfrom" in
scp|rcp)
    cat >$from <<EOF
#!/bin/sh
for f in \$@
do
    $rm -f \$f
    $targetfrom -P $targetport $q $targetuser@$targethost:$targetdir/\$f . || exit 1
done
exit 0
EOF
;;
cp) cat >$from <<EOF
#!/bin/sh
for
f in \$@
do
    $rm -f \$f
    cp $targetdir/\$f . || exit 1
done
exit 0
EOF
;;
*) echo "Unknown targetfrom '$targetfrom'" >&4
    exit 1
;;
esac
if $test ! -f $run; then
    echo "Target 'run' script '$run' not found." >&4
else
    $chmod a+rx $run
fi
if $test ! -f $to; then
    echo "Target 'to' script '$to' not found." >&4

```

```

else
    $chmod a+rx $to
fi
if $test ! -f $from; then
    echo "Target 'from' script '$from' not found." >&4
else
    $chmod a+rx $from
fi
if $test ! -f $run -o ! -f $to -o ! -f $from; then
    exit 1
fi
cat >&4 <<EOF
Using '$run' for remote execution,
and '$from' and '$to'
for remote file transfer.
EOF
;;
*) run="
to=:
from=:
usecrosscompile="$undef"
targetarch="
;;
esac

```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/perl/Cross.U
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_gmtime_r.U,v 0RCS:

?RCS: Copyright (c) 2002,2003 Jarkko Hietaniemi

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?RCS: Generated by the reentr.pl from the Perl 5.8 distribution.

?RCS:

?MAKE:d_gmtime_r gmtime_r_proto: Inlibc Protochk Hasproto i_systypes \
 usethreads i_time i_systime extern_C

?MAKE: -pick add \$@ %<

?S:d_gmtime_r:

?S: This variable conditionally defines the HAS_GMTIME_R symbol,

?S: which indicates to the C program that the gmtime_r()

?S: routine is available.

?S:.

?S:gmtime_r_proto:

?S: This variable encodes the prototype of gmtime_r.

?S: It is zero if d_gmtime_r is undef, and one of the
?S: REENTRANT_PROTO_T_ABC macros of reentr.h if d_gmtime_r
?S: is defined.
?S:.
?C:HAS_GMTIME_R:
?C: This symbol, if defined, indicates that the gmtime_r routine
?C: is available to gmtime re-entrantly.
?C:.
?C:GMTIME_R_PROTO:
?C: This
symbol encodes the prototype of gmtime_r.
?C: It is zero if d_gmtime_r is undef, and one of the
?C: REENTRANT_PROTO_T_ABC macros of reentr.h if d_gmtime_r
?C: is defined.
?C:.
?H:#\$d_gmtime_r HAS_GMTIME_R /**/
?H:#define GMTIME_R_PROTO \$gmtime_r_proto /**/
?H:.
?T:try hdrs d_gmtime_r_proto
: see if gmtime_r exists
set gmtime_r d_gmtime_r
eval \$inlibc
case "\$d_gmtime_r" in
"\$define")
hdrs="\$i_systypes sys/types.h define stdio.h \$i_time time.h \$i_systime sys/time.h"
case "\$d_gmtime_r_proto:\$usethreads" in
":define") d_gmtime_r_proto=define
set d_gmtime_r_proto gmtime_r \$hdrs
eval \$hasproto ;;
*) ;;
esac
case "\$d_gmtime_r_proto" in
define)
case "\$gmtime_r_proto" in
"|0) try='struct tm* gmtime_r(const time_t*, struct tm*);'
./protochk "\$extern_C \$try" \$hdrs && gmtime_r_proto=S_TS ;;
esac
case "\$gmtime_r_proto" in
"|0) try='int gmtime_r(const time_t*, struct tm*);'
./protochk "\$extern_C \$try" \$hdrs && gmtime_r_proto=I_TS ;;
esac
case
"\$gmtime_r_proto" in
"|0) d_gmtime_r=undef
gmtime_r_proto=0
echo "Disabling gmtime_r, cannot determine prototype." >&4 ;;
*) case "\$gmtime_r_proto" in
REENTRANT_PROTO*) ;;

```

*) gmtime_r_proto="REENTRANT_PROTO_$gmtime_r_proto" ;;
esac
echo "Prototype: $try" ;;
esac
;;
*) case "$usethreads" in
define) echo "gmtime_r has no prototype, not using it." >&4 ;;
esac
d_gmtime_r=undef
gmtime_r_proto=0
;;
esac
;;
*) gmtime_r_proto=0
;;
esac

```

Found in path(s):

```

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/threads/d_gmtime_r.U

```

No license file was found, but licenses were detected in source scan.

```

?RCS: $Id: pkgsrc.U 1 2006-08-24 12:32:52Z rmanfredi $
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?MAKE:pkgsrc: src rsrc
?MAKE: -pick add $@ %<
?S:pkgsrc:
?S: This variable holds the absolute path of the package source.
?S:.
?C:PACKAGE_SOURCE_DIR:
?C: Holds the directory name holding the package source.
?C:.
?H:#define PACKAGE_SOURCE_DIR "$pkgsrc"
?H:.
: define absolute package source directory
case "$src" in
/*) pkgsrc=$src;;
*) pkgsrc=`cd $rsrc; pwd`;;
esac

```

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/pkgsrc.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: sitescriptdir.U,v \$

?RCS:

?RCS: Copyright (c) 1999 Andy Dougherty

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 3.0.

?RCS:

?RCS: \$Log: sitescriptdir.U,v \$

?RCS:

?MAKE:sitescriptdir sitescriptdirexp installsitescriptdir : Getfile \

Setprefixvar Oldconfig scriptdir prefix siteprefix sed

?MAKE: -pick add \$@ %<

?Y:TOP

?D:sitescriptdir="

?S:sitescriptdir:

?S: This variable holds the name of the directory in which the user wants

?S: to put add-on publicly executable files for the package in question. It

?S: is most often a local directory such as /usr/local/bin. Programs using

?S: this variable must be prepared to deal with ~name substitution.

?S: The standard distribution will put nothing in this directory.

?S: After perl has been installed, users may install their own local

?S: scripts in this directory with

?S: MakeMaker Makefile.PL

?S: or equivalent. See INSTALL for details.

?S:.

?D:sitescriptdirexp="

?S:sitescriptdirexp:

?S: This is the same as the sitescriptdir variable, but is filename expanded at

?S: configuration time, for use in your makefiles.

?S:.

?S:installsitescriptdir:

?D:installsitescriptdir="

?S: This variable is usually the same as sitescriptdirexp, unless you are on

?S: a system running AFS, in which case they may differ slightly. You

?S: should always use this variable within your makefiles for portability.

?S:.

?LINT:change prefixvar

?LINT:set installsitescriptdir

?LINT:set sitescriptdir

```
?LINT:set sitescriptdirexp
: determine where add-on public executables go
case "$sitescriptdir" in
") dflt=`echo $scriptdir | $sed "s#^$prefix#$siteprefix#" ` ;;
*) dflt=$sitescriptdir ;;
esac
fn=d~
rp='Pathname
where add-on public executable scripts should be installed?'
./getfile
prefixvar=sitescriptdir
./setprefixvar
```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/installdirs/sitescriptdir.U
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 2000 Jarkko Hietaniemi

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?MAKE:d_finite: Inlibc

?MAKE: -pick add \$@ %<

?S:d_finite:

?S: This variable conditionally defines the HAS_FINITE symbol, which

?S: indicates to the C program that the finite() routine is available.

?S:.

?C:HAS_FINITE:

?C: This symbol, if defined, indicates that the finite routine is

?C: available to check whether a double is finite (non-infinity non-NaN).

?C:.

?H:#\$d_finite HAS_FINITE /**/

?H:.

?LINT:set d_finite

: see if finite exists

set finite d_finite

eval \$inlibc

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/perl/d_finite.U
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:
?RCS: Copyright (c) 2009 H.Merijn Brand
?RCS:
?RCS: You may distribute under the terms of either the GNU General Public
?RCS: License or the Artistic License, as specified in the README file.
?RCS:
?MAKE:d_getnameinfo: Inlibc
?MAKE: -pick add \$@ %<
?S:d_getnameinfo:
?S: This variable conditionally defines the HAS_GETNAMEINFO symbol,
?S: which indicates to the C program that the getnameinfo() function
?S: is available.
?S:.
?C:HAS_GETNAMEINFO:
?C: This symbol, if defined, indicates that the getnameinfo() function
?C: is available for use.
?C:.
?H:#\$d_getnameinfo HAS_GETNAMEINFO /**/
?H:.
?LINT:set d_getnameinfo
: see if getnameinfo exists
set getnameinfo d_getnameinfo
eval \$inlibc

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_getnameinfo.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: i_bfd.U,v \$
?RCS:
?RCS: Copyright (c) 2014 H.Merijn Brand
?RCS:
?RCS: You may distribute under the terms of either the GNU General Public
?RCS: License or the Artistic License, as specified in the README file.
?RCS:
?MAKE:i_bfd: Inhdr Hasfield
?MAKE: -pick add \$@ %<
?S:i_bfd:
?S: This variable conditionally defines the I_BFD symbol, and
?S: indicates whether a C program can include <bfd.h>.
?S:.
?C:I_BFD:
?C: This symbol, if defined, indicates that <bfd.h> exists and
?C: can be included.
?C:.
?H:#\$i_bfd I_BFD /**/
?H:.

```
?LINT:set i_bfd
: see if this is a bfd.h system
set bfd.h i_bfd
eval $inhdr
```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/perl/i_bfd.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: d_memmove.U 1 2006-08-24 12:32:52Z rmanfredi $
```

```
?RCS:
```

```
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
```

```
?RCS:
```

```
?RCS: You may redistribute only under the terms of the Artistic Licence,
```

```
?RCS: as specified in the README file that comes with the distribution.
```

```
?RCS: You may reuse parts of this distribution only within the terms of
```

```
?RCS: that same Artistic Licence; a copy of which may be found at the root
```

```
?RCS: of the source tree for dist 4.0.
```

```
?RCS:
```

```
?RCS: $Log: d_memmove.U,v $
```

```
?RCS: Revision 3.0 1993/08/18 12:06:35 ram
```

```
?RCS: Baseline for dist 3.0 netwide release.
```

```
?RCS:
```

```
?MAKE:d_memmove: Inlibc
```

```
?MAKE: -pick add $@ %<
```

```
?S:d_memmove:
```

```
?S: This variable conditionally defines the HAS_MEMMOVE symbol, which
```

```
?S: indicates to the C program that the memmove() routine is available
```

```
?S: to copy potentially overlapping blocks of memory.
```

```
?S:.
```

```
?C:HAS_MEMMOVE:
```

```
?C: This symbol, if defined, indicates that the memmove routine
```

```
is available
```

```
?C: to copy potentially overlapping blocks of memory. This should be used
```

```
?C: only when HAS_SAFE_BCOPY is not defined. If neither is there, roll your
```

```
?C: own version.
```

```
?C:.
```

```
?H:#$d_memmove HAS_MEMMOVE /**/
```

```
?H:.
```

```
?LINT:set d_memmove
```

```
: see if memmove exists
```

```
set memmove d_memmove
```

```
eval $inlibc
```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/d_memmove.U
```

No license file was found, but licenses were detected in source scan.

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?MAKE:d_lround: Inlibc

?MAKE: -pick add \$@ %<

?S:d_lround:

?S: This variable conditionally defines the HAS_LROUND symbol, which

?S: indicates to the C program that the lround() routine is available

?S: to return the integral value nearest to x.

?S:.

?C:HAS_LROUND:

?C: This symbol, if defined, indicates that the lround routine is

?C: available to return the nearest integral value.

?C:.

?H:#\$d_lround HAS_LROUND /**/

?H:.

?LINT:set d_lround

: see if lround exists

set lround d_lround

eval \$inlibc

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_lround.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_fsetpos.U 1 2006-08-24 12:32:52Z rmanfredi \$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic Licence,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic Licence; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: d_fsetpos.U,v \$

?RCS: Revision 3.0.1.1 1994/06/20 06:57:38 ram

?RCS: patch30: created

?RCS:

?MAKE:d_fsetpos: Inlibc

?MAKE: -pick add \$@ %<

?S:d_fsetpos:

?S: This variable conditionally defines HAS_FSETPOS if fsetpos() is

?S: available to set the file position indicator.

?S:.

?C:HAS_FSETPOS:

?C: This symbol, if defined, indicates that the fsetpos routine is

?C: available to set the file position indicator, similar to fseek().

?C:.

?H:#\$d_fsetpos

HAS_FSETPOS /**/

?H:.

?LINT:set d_fsetpos

: see if fsetpos exists

set fsetpos d_fsetpos

eval \$inlibc

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/d_fsetpos.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_stat.U 1 2006-08-24 12:32:52Z rmanfredi \$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic Licence,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic Licence; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: d_stat.U,v \$

?RCS: Revision 3.0 1993/08/18 12:07:28 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?MAKE:d_stat: Inlibc

?MAKE: -pick add \$@ %<

?S:d_stat:

?S: This variable conditionally defines HAS_STAT if stat() is

?S: available to get file status.

?S:.

?C:HAS_STAT (STAT):

?C: This symbol, if defined, indicates that the stat routine is

?C: available to get file status.

?C:.

?H:#\$d_stat HAS_STAT /**/

?H:.

?LINT:set d_stat

: see if stat exists

set

stat d_stat

eval \$inlibc

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/d_stat.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1999 Jarkko Hietaniemi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 3.0.

?RCS:

?MAKE:d_setspent: Inlibc

?MAKE: -pick add \$@ %<

?S:d_setspent:

?S: This variable conditionally defines HAS_SETSPENT if setspent() is

?S: available to initialize the scan of SysV shadow password entries.

?S:.

?C:HAS_SETSPENT:

?C: This symbol, if defined, indicates that the setspent system call is

?C: available to initialize the scan of SysV shadow password entries.

?C:.

?H:#\$d_setspent HAS_SETSPENT /**/

?H:.

?LINT:set d_setspent

: see if setspent exists

set setspent d_setspent

eval \$inlibc

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_setspent.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_chown.U 1 2006-08-24 12:32:52Z rmanfredi \$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic Licence,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic Licence; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: Original Author: Andy Dougherty <doughera@lafcol.lafayette.edu>

?RCS:

?RCS: \$Log: d_chown.U,v \$

?RCS: Revision 3.0.1.1 1994/08/29 16:07:14 ram

?RCS: patch32: created by ADO

?RCS:

?MAKE:d_chown: Inlibc

?MAKE: -pick add \$@ %<

?S:d_chown:

?S: This variable conditionally defines the HAS_CHOWN symbol, which

?S: indicates to the C program that the chown() routine is available.

?S:.

?C:HAS_CHOWN :

?C: This symbol, if defined, indicates that the chown routine is

?C: available.

?C:.

?H:#\$d_chown

HAS_CHOWN /**/

?H:.

?LINT:set d_chown

: see if chown exists

set chown d_chown

eval \$inlibc

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/d_chown.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1999 Jarkko Hietaniemi

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?MAKE:usesocks: Myread Oldconfig Setvar

?MAKE: -pick add \$@ %<

?Y:TOP

?S:usesocks:

?S: This variable conditionally defines the USE SOCKS symbol,

?S: and indicates that Perl should be built to use SOCKS.

?S:.

?C:USE SOCKS:

?C: This symbol, if defined, indicates that Perl should

?C: be built to use socks.

?C:.

?H:?%<:#ifndef USE SOCKS

```

?H:?%<:#$usesocks USE SOCKS /**/
?H:?%<:#endif
?H:
?LINT:set usesocks
?INIT:: set usesocks on the Configure command line to enable socks.
: Check is we will use socks
?X: We should really have some explanatory text here, and some
?X: automatic setting of sensible defaults.
case "$usesocks" in
$define|true|[yY]*) dflt='y';
*) dflt='n';;
esac
cat <<EOM

```

Perl can be built to use the SOCKS proxy protocol library. To do so, Configure must be run with `-Dusesocks`. If you use SOCKS you also need to use the PerlIO abstraction layer, this will be implicitly selected.

If this doesn't make any sense to you, just accept the default '\$dflt'.

```

EOM
rp='Build Perl for SOCKS?'
./myread
case "$ans" in
y|Y) val="$define" ;;
*) val="$undef" ;;
esac
set usesocks
eval $setvar

```

Found in path(s):

```

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/usesocks.U

```

No license file was found, but licenses were detected in source scan.

```

?RCS: $Id$
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: $Log: myhostname.U,v $
?RCS: Revision 3.0.1.3 1997/02/28 16:15:55 ram
?RCS: patch61: improved hostname lookup by using ypmatch when NIS is used

```

?RCS:
?RCS: Revision 3.0.1.2 1994/10/29 16:25:43 ram
?RCS: patch36: call ./xenix explicitly instead of relying on PATH
?RCS: patch36: now uses new Tr unit to convert to/from lowercase
?RCS:
?RCS: Revision 3.0.1.1 1994/06/20 07:06:20 ram
?RCS: patch30: now a little more clever for domain name guessing
?RCS:
?RCS: Revision 3.0 1993/08/18 12:09:18 ram
?RCS:
Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:myhostname phostname mydomain: contains sed test Myread Oldconfig \
Guess Loc awk echo sort uniq +usrinc rm hostcat Tr osname
?MAKE: -pick add \$@ %<
?S:myhostname (hostname):
?S: This variable contains the eventual value of the MYHOSTNAME symbol,
?S: which is the name of the host the program is going to run on.
?S: The domain is not kept with hostname, but must be gotten from mydomain.
?S: The dot comes with mydomain, and need not be supplied by the program.
?S:.
?S:mydomain:
?S: This variable contains the eventual value of the MYDOMAIN symbol,
?S: which is the domain of the host the program is going to run on.
?S: The domain must be appended to myhostname to form a complete host name.
?S: The dot comes with mydomain, and need not be supplied by the program.
?S:.
?S:phostname:
?S: This variable contains the eventual value of the PHOSTNAME symbol,
?S: which is a command that can be fed to popen() to get the host name.
?S: The program
should probably not presume that the domain is or isn't
?S: there already.
?S:.
?C:MYHOSTNAME (HOSTNAME):
?C: This symbol contains name of the host the program is going to run on.
?C: The domain is not kept with hostname, but must be gotten from MYDOMAIN.
?C: The dot comes with MYDOMAIN, and need not be supplied by the program.
?C: If gethostname() or uname() exist, MYHOSTNAME may be ignored. If MYDOMAIN
?C: is not used, MYHOSTNAME will hold the name derived from PHOSTNAME.
?C:.
?C:MYDOMAIN:
?C: This symbol contains the domain of the host the program is going to
?C: run on. The domain must be appended to HOSTNAME to form a complete
?C: host name. The dot comes with MYDOMAIN, and need not be supplied by
?C: the program. If the host name is derived from PHOSTNAME, the domain
?C: may or may not already be there, and the program should check.
?C:.

```

?H:#define MYHOSTNAME "$myhostname" /**/
?H:#define MYDOMAIN "$mydomain" /**/
?H:.
?T:cont i tans tmp_re file
: now get the host name
echo
" "
echo "Figuring out host name..." >&4
case "$myhostname" in
") cont=true
echo 'Maybe "hostname" will work...'
if tans=`sh -c hostname 2>&1` ; then
myhostname=$tans
phostname=hostname
cont="
fi
;;
*) cont="";;
esac
if $test "$cont"; then
if ./xenix; then
echo 'Oh, dear. Maybe "/etc/systemid" is the key...'
if tans=`cat /etc/systemid 2>&1` ; then
myhostname=$tans
phostname='cat /etc/systemid'
echo "Whadyaknow. Xenix always was a bit strange..."
cont="
fi
elif $test -r /etc/systemid; then
echo "(What is a non-Xenix system doing with /etc/systemid?)"
fi
fi
if $test "$cont"; then
echo 'No, maybe "uname -l" will work...'
if tans=`sh -c 'uname -l' 2>&1` ; then
myhostname=$tans
phostname='uname -l'
else
echo 'Strange. Maybe "uname -n" will work...'
if tans=`sh -c 'uname -n' 2>&1` ; then
myhostname=$tans
phostname='uname -n'
else
echo 'Oh well, maybe I can mine it out of whoami.h...'
if tans=`sh -c $contains' sysname $usrinc/whoami.h'
2>&1` ; then
myhostname=`echo "$tans" | $sed 's/^\.*\(\.*\)/\1/^
phostname="sed -n -e ""'/sysname/s/^\.*\(\.*\)/\1/{"" -e p -e q -e }' <$usrinc/whoami.h"

```

```

else
case "$myhostname" in
") echo "Does this machine have an identity crisis or something?"
phostname="";
*)
echo "Well, you said $myhostname before..."
phostname='echo $myhostname';;
esac
fi
fi
fi
fi
case "$myhostname" in
") myhostname=noname ;;
esac
: you do not want to know about this
set $myhostname
myhostname=$1

: verify guess
if $test "$myhostname" ; then
dflt=y
rp='Your host name appears to be "$myhostname". Right?'
./myread
case "$ans" in
y*) ;;
*) myhostname="";;
esac
fi

: bad guess or no guess
while $test "X$myhostname" = X ; do
dflt=""
rp="Please type the (one word) name of your host:"
./myread
myhostname="$ans"
done

: translate upper to lower if necessary
case "$myhostname" in
*[A-Z]*)
echo "(Normalizing case in your host name)"
myhostname=`echo
$myhostname | ./tr '[A-Z]' '[a-z]'`
;;
esac

```

?X: Do not ask for domain name if this is not used later on. In that

?X: case, the hostname may keep its domain name, but it doesn't matter.

```
@if MYDOMAIN || mydomain
case "$myhostname" in
*.*)
dflt=`expr "X$myhostname" : "X[^.]*\(\..*\)"`
myhostname=`expr "X$myhostname" : "X\([^.*]\)"`
echo "(Trimming domain name from host name--host name is now $myhostname)"
;;
*) case "$mydomain" in
```

```
)
?X:
```

?X: There is currently no way to say we do not want hostcat if mydomain is not

?X: used. One way to achieve that would be to put that code in a mydomain.U

?X: unit. However, we want to stick the sanity checks right after the domain

?X: name computation, or if none is done, right after the hostname computation.

?X:

```
{
```

?X: If we use NIS, try ypmatch.

```
test "X$hostcat" = "Xypcat hosts" &&
ypmatch "$myhostname" hosts 2>/dev/null \
$sed -e 's/[ ]*#.*//; s/$/ /' > hosts && \
$stest -s hosts
} || {
```

?X: Extract only

the relevant hosts, reducing file size,

?X: remove comments, insert trailing space for later use.

```
$hostcat | $sed -n -e "s/[ ]*#.*//; s/$/ /
/[ ]$myhostname[ . ]/p" > hosts
}
tmp_re="[ . ]"
$stest x`$awk "/[0-9].*[ ]$myhostname$tmp_re/ { sum++ }
END { print sum }" hosts` = x1 || tmp_re="[ ]"
dflt=`$awk \
"/[0-9].*[ ]$myhostname$tmp_re/ {for(i=2; i<=NF;i++) print \\$i}" \
hosts | $sort | $uniq | \
$sed -n -e "s/$myhostname\.\([-a-zA-Z0-9_]\)\^1/p"
case `$echo X$dflt` in
X*\ *) echo "(Several hosts in /etc/hosts matched hostname)"
dflt=.
```

```
;;
```

?X: There is no /etc/hosts on os390

```
X.)
```

```
if $stest -f /etc/hosts; then
```

```
echo "(You do not have fully-qualified names in /etc/hosts)"
```

```
else
```

```
echo "(I cannot locate a hosts database anywhere)"
```

```
fi
```

```
;;
```

```

esac
case "$dflt" in
.)
tans=`./loc resolv.conf X /etc /usr/etc`
if $test -f "$tans"; then
echo "(Attempting domain name extraction from $tans)"
?X: Look for either a search
or a domain directive.
dflt=`$sed -n -e 's// /g' \
-e 's/^search *([ ]*).*/\1/p' $tans \
| ./tr '[A-Z]' '[a-z]' 2>/dev/null`
case "$dflt" in
.) dflt=`$sed -n -e 's// /g' \
-e 's/^domain *([ ]*).*/\1/p' $tans \
| ./tr '[A-Z]' '[a-z]' 2>/dev/null`
;;
esac
fi
;;
esac
case "$dflt" in
.) echo "(No help from resolv.conf either -- attempting clever guess)"
dflt=`sh -c domainname 2>/dev/null`
case "$dflt" in
") dflt='.';
.nis.*|.yp.*|.main.*) dflt=`echo $dflt | $sed -e 's/^\.[^.]*/'`;
esac
;;
esac
case "$dflt$osname" in
.os390)
file="//SYS1.TCPPARMS(TCPDATA)"
echo "(Attempting domain name extraction from $file)"
dflt=`awk '/^DOMAINORIGIN/ {print $2}' "$file" 2>/dev/null`
;;
esac
case "$dflt" in
.) echo "(Lost all hope -- silly guess then)"
dflt='.nonet'
;;
esac
$rm -f hosts
;;
*) dflt="$mydomain";
esac;;
esac
echo " "
rp="What is your domain name?"

```

```

.
./myread
tans="$sans"
case "$sans" in
") ;;
.*) ;;
*) tans=".$stans";;
esac
mydomain="$stans"

: translate upper to lower if necessary
case "$mydomain" in
*[A-Z]*)
echo "(Normalizing case in your domain name)"
mydomain=`echo $mydomain | ./tr '[A-Z]' '[a-z]'`
;;
esac

@end
: a little sanity check here
case "$phostname" in
") ;;
*)
case ` $phostname | ./tr '[A-Z]' '[a-z]'` in
$myhostname$mydomain|$myhostname) ;;
*)
case "$phostname" in
sed*)
echo "(That doesn't agree with your whoami.h file, by the way.)"
;;
*)
echo "(That doesn't agree with your $phostname command, by the way.)"
;;
esac
;;
esac
;;
esac
;;
esac

```

Found in path(s):

```

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/myhostname.U

```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1991-1993, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 3.0.
?RCS:
?MAKE:d_drand48proto: Hasproto i_stdlib i_unistd
?MAKE: -pick add \$@ %<
?S:d_drand48proto:
?S: This variable conditionally defines the HAS_DRAND48_PROTO symbol,
?S: which indicates to the C program that the system provides
?S: a prototype for the drand48() function. Otherwise, it is
?S: up to the program to supply one.
?S:.
?C:HAS_DRAND48_PROTO:
?C: This symbol, if defined, indicates that the system provides
?C: a prototype for the drand48() function. Otherwise, it is up
?C: to the program to supply one. A good guess
is
?C: extern double drand48(void);
?C:.
?H:#\$d_drand48proto HAS_DRAND48_PROTO /**/
?H:.
?LINT:set d_drand48proto
: see if prototype for drand48 is available
echo " "
set d_drand48proto drand48 \$i_stdlib stdlib.h \$i_unistd unistd.h
eval \$hasproto

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/protos/d_drand48proto.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: \$Log: lseektype.U,v \$
?RCS: Revision 3.0.1.1 1994/08/29 16:30:10 ram
?RCS: patch32: now uses new Typedef unit to compute type information
?RCS:

```

?RCS: Revision 3.0 1993/08/18 12:09:08 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:lseektype: Myread Typedef
?MAKE: -pick add $@ %<
?S:lseektype:
?S: This variable defines lseektype to be something like off_t, long,
?S: or whatever type is used to declare lseek offset's type in the
?S: kernel (which also appears to be lseek's return type).
?S:.
?C:Off_t
(LSEEKTYPE):
?C: This symbol holds the type used to declare offsets in the kernel.
?C: It can be int, long, off_t, etc... It may be necessary to include
?C: <sys/types.h> to get any typedef'ed information.
?C:.
?H:#define Off_t $lseektype /* <offset> type */
?H:.
: see what type lseek is declared as in the kernel
set off_t lseektype long stdio.h sys/types.h
eval $typedef
echo " "
dflt="$lseektype"
rp="What type is lseek's offset on this system declared as?"
./myread
lseektype="$ans"

```

Found in path(s):

```

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/lseektype.U

```

No license file was found, but licenses were detected in source scan.

```

?RCS: $Id$
?RCS:
?RCS: Copyright (c) 1999, Jarkko Hietaniemi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 3.0.
?RCS:
?MAKE:d_sched_getscheduler: Inlibc
?MAKE: -pick add $@ %<
?S:d_sched_getscheduler:
?S: This variable conditionally defines HAS_SCHED_GETSCHEDULER if
?S: sched_getscheduler() is available to get the scheduling policy.
?S:.

```

?C:HAS_SCHED_GETSCHEDULER:
?C: This symbol, if defined, indicates that the sched_getscheduler
?C: system call is available to get the scheduling policy.
?C:.
?H:#\$d_sched_getscheduler HAS_SCHED_GETSCHEDULER /**/
?H:.
?LINT:set d_sched_getscheduler
: see if sched_getscheduler exists
set sched_getscheduler
d_sched_getscheduler
eval \$inlibc

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_sched_getscheduler.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_getnbyaddr.U,v \$
?RCS:
?RCS: Copyright (c) 1998 Andy Dougherty
?RCS:
?RCS: You may distribute under the terms of either the GNU General Public
?RCS: License or the Artistic License, as specified in the README file.
?RCS:
?MAKE:d_getnbyaddr: Inlibc
?MAKE: -pick add \$@ %<
?S:d_getnbyaddr:
?S: This variable conditionally defines the HAS_GETNETBYADDR symbol, which
?S: indicates to the C program that the getnetbyaddr() routine is available
?S: to look up networks by their IP addresses.
?S:.
?C:HAS_GETNETBYADDR:
?C: This symbol, if defined, indicates that the getnetbyaddr() routine is
?C: available to look up networks by their IP addresses.
?C:.
?H:#\$d_getnbyaddr HAS_GETNETBYADDR /**/
?H:.
?LINT:set d_getnbyaddr
: see if getnetbyaddr exists
set getnetbyaddr d_getnbyaddr
eval \$inlibc

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/modified/d_getnbyaddr.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: i_dld.U 1 2006-08-24 12:32:52Z rmanfredi \$

```

?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: Original Author: Andy Dougherty <doughera@lafcol.lafayette.edu>
?RCS:
?RCS: $Log: i_dld.U,v $
?RCS: Revision 3.0.1.1 1994/10/29 16:20:07 ram
?RCS: patch36: created by ADO
?RCS:
?MAKE:i_dld: Inhdr
?MAKE: -pick add $@ %<
?S:i_dld:
?S: This variable conditionally defines the I_DLD symbol, which
?S: indicates to the C program that <dld.h> (GNU dynamic loading)
?S: exists and should be included.
?S:.
?C:I_DLD:
?C: This symbol, if defined, indicates that <dld.h>
exists and should
?C: be included before using GNU dynamic loading features.
?C:.
?H:#$i_dld I_DLD /**/
?H:.
?LINT:set i_dld
: see if dld is available
set dld.h i_dld
eval $inhdr

```

Found in path(s):

```

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/i_dld.U

```

No license file was found, but licenses were detected in source scan.

```

?RCS: $Id: locallib.U,v 1.1 1999/07/08 18:32:57 doughera Exp doughera $
?RCS:
?RCS: Copyright (c) 1999, Jarkko Hietaniemi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 3.0.

```

?RCS:
?RCS:
?MAKE:uselocallib locallib locallibexp installlocallib installlocallibexp: \
cat Getfile Oldconfig Prefixit test afs sitelib
?MAKE: -pick add \$@ %<
?Y:TOP
?S:uselocallib:
?S: This variable tells whether the USELOCALLIB is defined.
?S:.
?S:locallib:
?S: This variable contains the eventual value of the LOCALLIB symbol,
?S: which is the name of the private library for this package. It may
?S: have a ~ on the front. It is up to the makefile to eventually create
?S: this
directory while performing installation (with ~ substitution).
?S: This differs from \$sitelib in that \$sitelib is often
?S: a shared network directory while \$locallib is
?S: at a local disk, because of policy/administrative issues
?S: like for example caching (performance), licensing, or security.
?S:.
?S:locallibexp:
?S: This variable is the ~name expanded version of locallib, so that you
?S: may use it directly in Makefiles or shell scripts.
?S:.
?S:installlocallib:
?S: This variable is really the same as locallibexp but may differ on
?S: those systems using AFS. For extra portability, only this variable
?S: should be used in makefiles.
?S:.
?S:installlocallibexp:
?S: This variable is the ~name expanded version of installlocallib,
?S: so that you may use it directly in Makefiles or shell scripts.
?S:.
?C:USELOCALLIB:
?C: This symbol, if defined, tells that the directories
?C: LOCALLIB, LOCALLIB_EXP, LOCALARCH, and LOCALARCH_EXP,
?C: are used in this installation.
?C:.
?C:LOCALLIB:
?C: This
symbol contains the name of the private library for this package.
?C: The library is private in the sense that it needn't be in anyone's
?C: execution path, but it should be accessible by the world. The program
?C: should be prepared to do ~ expansion.
?C: The standard distribution will put nothing in this directory.
?C: Local administration may place extensions and modules in
?C: this directory.
?C: This differs from SITELIB in that SITELIB is often

```

?C: a shared network directory while LOCALLIB is
?C: at a local disk, because of policy/administrative issues
?C: like for example caching (performance), licensing, or security.
?C:.
?C:LOCALLIB_EXP:
?C: This symbol contains the ~name expanded version of LOCALLIB, to be used
?C: in programs that are not prepared to deal with ~ expansion at run-time.
?C:.
?H:#$uselocallib USELOCALLIB /**/
?H:#define LOCALLIB "$locallib" /**/
?H:#define LOCALLIB_EXP "$locallibexp" /**/
?H:.
: determine where local libraries go.
case
"$locallib" in
") dflt=none ;;
*) dflt=$locallib ;;
esac
$cat <<EOM

```

For various local software administration reasons and especially if \$sitelib happens to be a shared network resource, you may want to have a directory for extensions and modules that resides on a possibly local disk. If this scenario doesn't sound applicable, accept the default 'none'.

```

EOM
fn=nd~+
rp='Pathname for such local library files?'
./getfile
if $test "X$sans" = X; then
  uselocallib="$undef"
  locallib=""
  locallibexp=""
  installlocallib=""
  installlocallibexp=""
else
  uselocallib="$define"
  if $test "X$locallibexp" != "X$sansexp"; then
    installlocallib="
  fi
  locallib="$sans"
  locallibexp="$sansexp"
  if $afs; then
    $cat <<EOM

```

Since you are running AFS, I need to distinguish the directory in which locally installed files reside from the directory in which they

are installed (and from which they are presumably copied to the former directory by occult means).

EOM

```
case "$installlocallib" in
  *) dflt=`echo
$locallibexp | sed 's#^/afs/#/afs/#^';
  *) dflt="$installlocallib";;
esac
fn=de~
rp='Where will the locally installed files be installed?'
. ./getfile
installlocallib="$ans"
else
  installlocallibexp="$locallibexp"
fi
fi
```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/installdirs/locallib.U
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: perlpath.U,v 3.0.1.2 1995/09/25 09:17:04 ram Exp \$

?RCS:

?RCS: Copyright (c) 1991-1993, Raphael Manfredi

?RCS:

?RCS: This file is included with or a derivative work of a file included

?RCS: with the metaconfig program of Raphael Manfredi's "dist" distribution.

?RCS: In accordance with clause 7 of dist's modified Artistic License:

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?RCS: \$Log: perlpath.U,v \$

?RCS:

?RCS: Special perl5 unit -- we haven't installed perl yet.

?RCS:

?RCS: Revision 3.0.1.2 1995/09/25 09:17:04 ram

?RCS: patch59: unit is now forced to the top of Configure, if possible

?RCS:

?RCS: Revision 3.0.1.1 1995/01/11 15:33:53 ram

?RCS: patch45: can now use Loc variables since path stripping is deferred

?RCS:

?RCS: Revision 3.0 1993/08/18 12:09:32 ram

?RCS: Baseline for dist

3.0 netwide release.

?RCS:

?X:

?X: The purpose of this unit is to locate perl good enough to construct a #!

?X:

?MAKE:perlpath: cat Getfile Loc Myread Oldconfig initialinstalllocation \
startperl version versiononly

?MAKE: -pick add \$@ %<

?Y:TOP

?S:perlpath:

?S: This variable contains the eventual value of the PERLPATH symbol,

?S: which contains the name of the perl interpreter to be used in

?S: shell scripts and in the "eval 'exec'" idiom. This variable is

?S: not necessarily the pathname of the file containing the perl

?S: interpreter; you must append the executable extension (_exe) if

?S: it is not already present. Note that Perl code that runs during

?S: the Perl build process cannot reference this variable, as Perl

?S: may not have been installed, or even if installed, may be a

?S: different version of Perl.

?S:.

?C:PERLPATH:

?C: This symbol contains the name of the perl interpreter to be

?C: used in shell scripts and in the "eval 'exec'" idiom.

?C:.

?H:#define PERLPATH "\$perlpath" /**/

?H:.

:

figure best path for perl in scripts

case "\$perlpath" in

")

case "\$versiononly" in

"\$define") perlpath="\$initialinstalllocation/perl\$version";;

*) perlpath="\$initialinstalllocation/perl";;

esac

case "\$startperl" in

!) ;;

*)

\$cat <<EOH

I will use the "eval 'exec'" idiom to start Perl on your system.

I can use the full path of your Perl binary for this purpose, but

doing so may cause problems if you want to share those scripts and

Perl is not always in a standard place (\$initialinstalllocation/perl).

EOH

dflt="\$initialinstalllocation/perl"

rp="What path shall I use in \"eval 'exec'\"?"

./myread

perlpath="\$ans"

::

```
esac
;;
esac
case "$startperl" in
*!*) ;;
*) echo "I'll use $perlpath in \"eval 'exec'\"" ;;
esac
```

Found in path(s):

```
*/opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/perl/perlpath.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: d_closedir.U,v 3.0.1.3 1997/02/28 15:31:26 ram Exp $
?RCS:
?RCS: Copyright (c) 1991-1993, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 3.0.
?RCS:
?RCS: Original Author: Andy Dougherty <doughera@lafcol.lafayette.edu>
?RCS:
?RCS: $Log: d_closedir.U,v $
?RCS: Revision 3.0.1.3 1997/02/28 15:31:26 ram
?RCS: patch61: added ?F: metalint hint
?RCS:
?RCS: Revision 3.0.1.2 1994/10/29 16:11:18 ram
?RCS: patch36: added 'ldflags' to the test compile line (ADO)
?RCS:
?RCS: Revision 3.0.1.1 1994/08/29 16:07:21 ram
?RCS: patch32: created by ADO
?RCS:
?MAKE:d_closedir d_void_closedir: Inlibc i_dirent i_sysdir i_sysndir
\
i_systypes Compile Setvar rm_try run
?MAKE: -pick add $@ %<
?S:d_closedir:
?S: This variable conditionally defines HAS_CLOSEDIR if closedir() is
?S: available.
?S:.
?C:HAS_CLOSEDIR:
?C: This symbol, if defined, indicates that the closedir() routine is
?C: available.
?C:.
?H:#$d_closedir HAS_CLOSEDIR /**/
```

?H:
 ?S:d_void_closedir:
 ?S: This variable conditionally defines VOID_CLOSEDIR if closedir()
 ?S: does not return a value.
 ?S:.
 ?C:VOID_CLOSEDIR:
 ?C: This symbol, if defined, indicates that the closedir() routine
 ?C: does not return a value.
 ?C:.
 ?H:#\$d_void_closedir VOID_CLOSEDIR /**/
 ?H:
 ?F:!try
 ?LINT:set d_closedir d_void_closedir
 : see if closedir exists
 set closedir d_closedir
 eval \$inlibc

```
@if VOID_CLOSEDIR || d_void_closedir
?X: The following contortions are designed so we can call closedir()
?X: and check whether it returns a value. The contortions are designed
?X: to portably pick up the correct directory header, for those
?X: systems that support various mutually incompatible
directory functions.
?X: This is from perl5's perl.h
case "$d_closedir" in
"$define")
echo " "
echo "Checking whether closedir() returns a status..." >&4
cat > try.c <<EOM
#$i_dirent I_DIRENT /**/
#$i_sysdir I_SYS_DIR /**/
#$i_sysndir I_SYS_NDIR /**/
#$i_systypes I_SYS_TYPES /**/

#if defined(I_SYS_TYPES)
#include <sys/types.h>
#endif
#if defined(I_DIRENT)
#include <dirent.h>
#else
#ifdef I_SYS_NDIR
#include <sys/ndir.h>
#else
#ifdef I_SYS_DIR
#ifdef hp9000s500
#include <ndir.h> /* may be wrong in the future */
#else
#include <sys/dir.h>
```

```

#endif
#endif
#endif
#endif
int main() { return closedir(opendir(".")); }
EOM
set try
if eval $compile_ok; then
if $run ./try > /dev/null 2>&1 ; then
echo "Yes, it does."
val="$undef"
else
echo "No, it doesn't."
val="$define"
fi
else
echo "(I can't seem to compile the test program--assuming it doesn't)"
val="$define"
fi
;;
*)
val="$undef";
;;
esac
set d_void_closedir
eval $setvar
$rm_try
@end

```

Found in path(s):

*

/opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/compline/d_closedir.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: i_sysstatfs.U,v \$

?RCS:

?RCS: Copyright (c) 1999 Jarkko Hietaniemi

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?MAKE:i_sysstatfs: Inhdr Hasfield

?MAKE: -pick add \$@ %<

?S:i_sysstatfs:

?S: This variable conditionally defines the I_SYSSTATFS symbol,

?S: and indicates whether a C program should include <sys/statfs.h>.

?S:.

?C:I_SYS_STATFS:

?C: This symbol, if defined, indicates that <sys/statfs.h> exists.

?C:.

?H:#\$i_sysstatfs I_SYS_STATFS /**/

?H:.

?LINT:set i_sysstatfs

: see if this is a sys/statfs.h system

set sys/statfs.h i_sysstatfs

eval \$inhdr

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/i_sysstatfs.U

No license file was found, but licenses were detected in source scan.

/*

* \$Id: scandir.C,v 3.0.1.1 1994/01/24 13:58:45 ram Exp ram \$

*

* Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

*

* You may redistribute only under the terms of the Artistic Licence,

* as specified in the README file that comes with the distribution.

* You may reuse parts of this distribution only within the terms of

* that same Artistic Licence; a copy of which may be found at the root

* of the source tree for dist 4.0.

*

* \$Log: scandir.C,v \$

* Revision 3.0.1.1 1994/01/24 13:58:45 ram

* patch16: created

*

*/

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/lib/C/fake/scandir.C

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1999, Jarkko Hietaniemi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 3.0.

?RCS:

?MAKE:d_sem_close: Inlibc

?MAKE: -pick add \$@ %<
?S:d_sem_close:
?S: This variable conditionally defines HAS_SEM_CLOSE if sem_close() is
?S: available to close a POSIX semaphore.
?S:.
?C:HAS_SEM_CLOSE:
?C: This symbol, if defined, indicates that the sem_close system call is
?C: available to close a POSIX semaphore.
?C:.
?H:#\$d_sem_close HAS_SEM_CLOSE /**/
?H:.
?LINT:set d_sem_close
: see if sem_close exists
set sem_close d_sem_close
eval \$inlibc

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_sem_close.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_chsize.U 1 2006-08-24 12:32:52Z rmanfredi \$
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: \$Log: d_chsize.U,v \$
?RCS: Revision 3.0 1993/08/18 12:05:50 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:d_chsize: Inlibc
?MAKE: -pick add \$@ %<
?S:d_chsize:
?S: This variable conditionally defines the CHSIZE symbol, which
?S: indicates to the C program that the chsize() routine is available
?S: to truncate files. You might need a -lx to get this routine.
?S:.
?C:HAS_CHSIZE (CHSIZE):
?C: This symbol, if defined, indicates that the chsize
routine is available
?C: to truncate files. You might need a -lx to get this routine.
?C:.
?H:#\$d_chsize HAS_CHSIZE /**/

?H:
?LINT:set d_chsize
: see if chsize exists
set chsize d_chsize
eval \$inlibc

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/d_chsize.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: Guess.U,v \$

?RCS: Revision 3.0.1.5 1995/07/25 13:37:14 ram

?RCS: patch56: now knows about OS/2 platforms

?RCS:

?RCS: Revision 3.0.1.4 1994/10/29 15:53:55 ram

?RCS: patch36: added ?F: line for metalint file checking

?RCS: patch36: call ./xenix explicitly instead of relying on PATH

?RCS:

?RCS: Revision 3.0.1.3 1993/12/15 08:14:35 ram

?RCS: patch15: variable d_bsd was not always set properly

?RCS:

?RCS: Revision 3.0.1.2 1993/08/30 08:57:14 ram

?RCS: patch8: fixed comment which wrongly

attributed the usrinc symbol

?RCS: patch8: no more ugly messages when no /usr/include/ctype.h

?RCS:

?RCS: Revision 3.0.1.1 1993/08/27 14:37:37 ram

?RCS: patch7: added support for OSF/1 machines

?RCS:

?RCS: Revision 3.0 1993/08/18 12:04:57 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?X:

?X: This unit hazards some guesses as to what the general nature of the system

?X: is. The information it collects here is used primarily to establish default

?X: answers to other questions.

?X:

?MAKE:Guess d_eunice d_xenix d_bsd d_linux d_dos d_os2: cat test echo n c \
contains rm tr Loc eunicefix

?MAKE: -pick add \$@ %<

?S:d_eunice:
?S: This variable conditionally defines the symbols EUNICE_SYSTEM, which
?S: alerts the C program that it must deal with ideosyncracies of VMS.
?S:.

?S:d_xenix:
?S: This variable conditionally defines the symbol XENIX_SYSTEM, which alerts
?S: the C program that it runs under Xenix.
?S:.

?S:d_dos:
?S: This symbol conditionally defines the symbol DOS_SYSTEM
when running on
?S: DOS with DJGPP or Cygwin.
?S:.

?S:d_os2:
?S: This symbol conditionally defines the symbol OS2_SYSTEM when running on
?S: an OS/2 system.
?S:.

?S:d_bsd:
?S: This symbol conditionally defines the symbol BSD_SYSTEM when running on a
?S: BSD system.
?S:.

?S:d_linux:
?S: This symbol conditionally defines the symbol LINUX_SYSTEM when running
?S: on a Linux system.
?S:.

?C:EUNICE_SYSTEM (EUNICE):
?C: This symbol, if defined, indicates that the program is being compiled
?C: under the EUNICE package under VMS. The program will need to handle
?C: things like files that don't go away the first time you unlink them,
?C: due to version numbering. It will also need to compensate for lack
?C: of a respectable link() command.
?C:.

?C:VMS_SYSTEM (VMS):
?C: This symbol, if defined, indicates that the program is running under
?C: VMS. It is currently only set in conjunction with the EUNICE symbol.
?C:.

?C:XENIX_SYSTEM (XENIX):
?C: This symbol, if defined, indicates that the program
is running under
?C: Xenix (at least 3.0 ?).
?C:.

?C:DOS_SYSTEM:
?C: This symbol, if defined, indicates that the program is running under
?C: DOS with DJGPP.
?C:.

```

?C:OS2_SYSTEM:
?C: This symbol, if defined, indicates that the program is running under
?C: an OS/2 system.
?C:.
?C:BSD_SYSTEM:
?C: This symbol, if defined, indicates that the program is running under
?C: a BSD system.
?C:.
?C:LINUX_SYSTEM:
?C: This symbol, if defined, indicates that the program is running under
?C: a Linux system.
?C:.
?H:#$d_eunice EUNICE_SYSTEM /**/
?H:#$d_eunice VMS_SYSTEM /**/
?H:#$d_xenix XENIX_SYSTEM /**/
?H:#$d_dos DOS_SYSTEM /**/
?H:#$d_os2 OS2_SYSTEM /**/
?H:#$d_bsd BSD_SYSTEM /**/
?H:#$d_linux LINUX_SYSTEM /**/
?H:.
?F:./bsd ./usg ./v7 ./osf1 ./eunice ./xenix ./venix ./dos ./os2 ./gnu ./linux
?T:xxx DJGPP MACHTYPE
: make some quick guesses about what we are up against
echo " "
$echo $n "Hmm... $c"
echo exit 1 >bsd
echo exit 1 >usg
echo exit 1 >v7
echo exit 1 >osf1
echo exit 1 >eunice
echo
  exit 1 >xenix
echo exit 1 >venix
echo exit 1 >os2
echo exit 1 >gnu
echo exit 1 >linux
echo exit 1 >dos
d_bsd="$undef"
d_linux="$undef"
d_dos="$undef"
d_os2="$undef"
?X:
?X: Do not use 'usrinc', or we get a circular dependency. because
?X: usrinc is defined in usrinc.U, which relies on us...
?X:
$cat /usr/include/signal.h /usr/include/sys/signal.h >foo 2>/dev/null
if test -f /osf_boot || $contains 'OSF/1' /usr/include/ctype.h >/dev/null 2>&1
then

```

```

echo "Looks kind of like an OSF/1 system, but we'll see..."
echo exit 0 >osf1
elif test `echo abc | $tr a-z A-Z` = Abc ; then
xxx=`./loc addbib blurfl $pth`
if $test -f $xxx; then
echo "Looks kind of like a USG system with BSD features, but we'll see..."
echo exit 0 >bsd
echo exit 0 >usg
else
if $contains SIGTSTP foo >/dev/null 2>&1 ; then
echo "Looks kind of like an extended USG system, but we'll see..."
else
echo "Looks kind of like a USG system, but we'll see..."
fi
echo exit 0 >usg
fi
elif $contains SIGTSTP foo >/dev/null
2>&1 ; then
echo "Looks kind of like a BSD system, but we'll see..."
d_bsd="$define"
echo exit 0 >bsd
elif
$rm --version 2>/dev/null >foo;
$contains "Free Software Foundation" foo >/dev/null
then
xxx=`uname`
echo exit 0 >gnu
echo "Looks kind of like a GNU/$xxx system, but we'll see..."
if $test X$xxx = XLinux; then
d_linux="$define"
echo exit 0 >linux
fi
else
echo "Looks kind of like a Version 7 system, but we'll see..."
echo exit 0 >v7
fi
case "$eunicefix" in
*unixtovms*)
$cat <<'EOI'
There is, however, a strange, musty smell in the air that reminds me of
something...hmm...yes...I've got it...there's a VMS nearby, or I'm a Blit.
EOI
echo exit 0 >eunice
d_eunice="$define"
: it so happens the Eunice I know will not run shell scripts in Unix format
;;
*)
echo " "

```

```

echo "Congratulations. You aren't running Eunice."
d_eunice="$undef"
;;
esac
case "$p_" in
:) ;;
*)
$cat <<'EOI'
I have the feeling something is not exactly right, however...don't tell me...
EOI
if
test -n "$DJGPP"; then
case "X${MACHTYPE:-nonesuchmach}" in
cygwin) echo "hah!... you're running under Cygwin!";;
*) echo "got it... you're running DOS with DJGPP!";;
esac
echo exit 0 >dos
d_dos="$define"
else
$cat <<'EOI'
lemme think...does HAL ring a bell?...no, of course, you're only running OS/2!
EOI
echo exit 0 >os2
d_os2="$define"
fi
;;
esac
if test -f /xenix; then
echo "Actually, this looks more like a XENIX system..."
echo exit 0 >xenix
d_xenix="$define"
else
echo " "
echo "It's not Xenix..."
d_xenix="$undef"
fi
chmod +x xenix
$eunicefix xenix
if test -f /venix; then
echo "Actually, this looks more like a VENIX system..."
echo exit 0 >venix
else
echo " "
if ./xenix; then
: null
else
echo "Nor is it Venix..."
fi

```

```
fi
chmod +x bsd usg v7 osf1 eunice xenix venix dos os2 gnu linux
$eunicefix bsd usg v7 osf1 eunice xenix venix dos os2 gnu linux
$rm -f foo
```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/Guess.U
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1999 Jarkko Hietaniemi

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?X: This unit generates a \$hasstruct string that is used internally

?X: by Configure to check if this system has a field for a

?X: particular struct (of if this system has a particular struct!)

?X:

?X: To use it, say something like:

?X: set d_statblocks stat i_sysstat sys/stat.h

?X: eval \$hasstruct

?X: Or, for more complicated sets of headers, do something like

?X: hdrs="\$define sys/foo.h

?X: \$i_sysbar sys/bar.h

?X: \$i_syszot sys/zot.h

?X: \$i_zappa zappa.h"

?X: set d_statblocks stat \$hdrs

?X: eval \$hasstruct

?X:

?MAKE:Hasstruct: Setvar rm_try test Compile

?MAKE: -pick add \$@ %<

?T:varname struct

?V:hasstruct

: Define hasstruct macro for Configure internal use

```
hasstruct='varname=$1; struct=$2; shift;
```

```
shift;
```

```
while $test $# -ge 2; do
```

```
case "$1" in
```

```
$define) echo "#include <$2>";;
```

```
esac ;
```

```
shift 2;
```

```
done > try.c;
```

```
echo "int main () { struct $struct foo; }" >> try.c;
```

```
set try;
```

```
if eval $compile; then
```

```
val="$define";
else
val="$undef";
fi;
set $varname;
eval $setvar;
$rm_try'
```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/protos/Hasstruct.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: d_raster.U 1 2006-08-24 12:32:52Z rmanfredi $
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: $Log: d_raster.U,v $
?RCS: Revision 3.0 1993/08/18 12:06:50 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:d_raster rasterlib: cat test Setvar Myread Oldconfig
?MAKE: -pick add $@ %<
?S:d_raster:
?S: Conditionally defines RASTER_TEK if this is a raster tech machine.
?S:.
?S:rasterlib (d_rasterlib):
?S: Set to the needed compile flag if this is a raster tech machine.
?S: It is up to the Makefile to use this variable.
?S:.
?C:RASTER_TEK:
?C: Defined
if this is a rastertech machine.
?C:.
?H:#$d_raster RASTER_TEK /**/
?H:.
?LINT:set d_raster
: See if this is a raster tech machine.
val="$undef"
rasterlib="
if $test -r /dev/mirage; then
$cat <<'EOM'
```

You seem to have a mirage device... this is normally associated with a raster technologies graphics workstation. If this is right, you may want to use raster tech in this program.

```
EOM
dflt=y
case "$d_raster" in
"$undef") dflt=n;;
esac
rp='Use raster tech?'
. ./myread
case "$ans" in
y*) val="$define";;
esac
fi
set d_raster
eval $setvar

case "$d_raster" in
"$define") rasterlib='-lphigs';;
esac
```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/d_raster.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: d_munmap.U 1 2006-08-24 12:32:52Z rmanfredi $
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: $Log: d_munmap.U,v $
?RCS: Revision 3.0.1.1 1993/12/15 08:19:22 ram
?RCS: patch15: created
?RCS:
?MAKE:d_munmap: Inlibc
?MAKE: -pick add $@ %<
?S:d_munmap:
?S: This variable conditionally defines HAS_MUNMAP if munmap() is
?S: available to unmap a region mapped by mmap().
?S:.
```

```
?C:HAS_MUNMAP:
?C: This symbol, if defined, indicates that the munmap system call is
?C: available to unmap a region, usually mapped by mmap().
?C:.
?H:#$d_munmap HAS_MUNMAP /**/
?H:.
?LINT:set
d_munmap
: see if munmap exists
set munmap d_munmap
eval $inlibc
```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/d_munmap.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id$
?RCS:
?RCS: Copyright (c) 1999, Jarkko Hietaniemi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 3.0.
?RCS:
?MAKE:d_posix_clock: Setvar d_clock_getres d_clock_gettime d_clock_settime i_time
?MAKE:-pick add $@ %<
?S:d_posix_clock:
?S: This variable conditionally defines the HAS_POSIX_CLOCK symbol, which
?S: indicates that the entire POSIX clock_*(2) library is present.
?S:.
?C:HAS_POSIX_CLOCK:
?C: This symbol, if defined, indicates that the entire POSIX clock_*(2)
?C: library is supported.
?C:.
?H:#$d_posix_clock HAS_POSIX_CLOCK /**/
?H:.
?LINT:set d_posix_clock
: see how much of the 'POSIX clock_*(2)' library is present.
echo
" "
case "$i_time$d_clock_getres$d_clock_gettime$d_clock_settime" in
*$undef*) val="$undef" ;;
*) val="$define" ;;
esac
case "$val" in
```

```
"$define") echo "You have the full POSIX clock_*(2) library." >&4 ;;
"$undef") echo "You don't have the full POSIX clock_*(2) library." >&4 ;;
esac
set d_posix_clock
eval $setvar
```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/perl/d_posix_clock.U
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1999, Jarkko Hietaniemi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 3.0.

?RCS:

?MAKE:d_timer_settime: Inlibc

?MAKE: -pick add \$@ %<

?S:d_timer_settime:

?S: This variable conditionally defines HAS_TIMER_SETTIME

?S: if timer_settime() is available to set the time of a POSIX timer.

?S:.

?C:HAS_TIMER_SETTIME:

?C: This symbol, if defined, indicates that the timer_settime

?C: system call is available to set the time of a POSIX timer.

?C:.

?H:#\$d_timer_settime HAS_TIMER_SETTIME /**/

?H:.

?LINT:set d_timer_settime

: see if timer_settime exists

set timer_settime d_timer_settime

eval \$inlibc

Found in path(s):

```
*
```

```
/opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/perl/d_timer_settime.U
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 2000 Jarkko Hietaniemi

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?MAKE:d_setitimer: Inlibc

?MAKE: -pick add \$@ %<

?S:d_setitimer:

?S: This variable conditionally defines the HAS_SETITIMER symbol, which

?S: indicates to the C program that the setitimer() routine is available.

?S:.

?C:HAS_SETITIMER:

?C: This symbol, if defined, indicates that the setitimer routine is

?C: available to set interval timers.

?C:.

?H:#\$d_setitimer HAS_SETITIMER /**/

?H:.

?LINT:set d_setitimer

: see if setitimer exists

set setitimer d_setitimer

eval \$inlibc

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_setitimer.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: d_msg.U,v \$

?RCS: Revision 3.0 1993/08/18 12:06:37 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?MAKE:d_msg: test d_msgctl d_msgget d_msgsnd d_msgrcv Setvar Findhdr osname

?MAKE: -pick add \$@ %<

?S:d_msg:

?S: This variable conditionally defines the HAS_MSG symbol, which

?S: indicates that the entire msg*(2) library is present.

?S:.

?C:HAS_MSG:

?C: This symbol, if defined, indicates that the entire msg*(2) library is

?C: supported (IPC mechanism based on message queues).

```

?C:.
?H:#$d_msg
HAS_MSG /**/
?H:.
?T:h_msg
?LINT:set d_msg
: see how much of the 'msg*(2)' library is present.
h_msg=true
echo " "
case "$d_msgctl$d_msgget$d_msgsnd$d_msgrcv" in
*"$undef"*) h_msg=false;;
esac
case "$osname" in
freebsd)
    case "`ipcs 2>&1`" in
    "SVID messages"*"not configured"*)
    echo "Your $osname does not have the msg*(2) configured." >&4
        h_msg=false
    val="$undef"
    set msgctl d_msgctl
    eval $setvar
    set msgget d_msgget
    eval $setvar
    set msgsnd d_msgsnd
    eval $setvar
    set msgrcv d_msgrcv
    eval $setvar
    ;;
    esac
    ;;
esac
: we could also check for sys/ipc.h ...
if $h_msg && $test `./findhdr sys/msg.h`; then
    echo "You have the full msg*(2) library." >&4
    val="$define"
else
    echo "You don't have the full msg*(2) library." >&4
    val="$undef"
fi
set d_msg
eval $setvar

```

Found in path(s):

```

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/d_msg.U
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/modified/d_msg.U

```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id$
?RCS:
?RCS: Copyright (c) 1999 Jarkko Hietaniemi
?RCS:
?RCS: You may distribute under the terms of either the GNU General Public
?RCS: License or the Artistic License, as specified in the README file.
?RCS:
?MAKE:d_cmsg_hdr_s: Hasstruct i_systypes d_socket i_sysuio Setvar
?MAKE: -pick add $@ %<
?S:d_cmsg_hdr_s:
?S: This variable conditionally defines the HAS_STRUCT_CMSGHDR symbol,
?S: which indicates that the struct cmsghdr is supported.
?S:.
?C:HAS_STRUCT_CMSGHDR:
?C: This symbol, if defined, indicates that the struct cmsghdr
?C: is supported.
?C:.
?H:#$d_cmsg_hdr_s HAS_STRUCT_CMSGHDR /**/
?H:.
?LINT:set d_cmsg_hdr_s
: Check for cmsghdr support
echo " "
echo "Checking to see if your system supports struct cmsghdr..." >&4
set d_cmsg_hdr_s cmsghdr $i_systypes sys/types.h $d_socket sys/socket.h $i_sysuio sys/uio.h
eval $hasstruct
case "$d_cmsg_hdr_s" in
"$define") echo "Yes, it does." ;;
*) echo
"No, it doesn't." ;;
esac
```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/perl/d_cmsg_hdr_s.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id$
?RCS:
?RCS: Copyright (c) 1999, Jarkko Hietaniemi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 3.0.
?RCS:
```

?MAKE:d_mq_receive: Inlibc
?MAKE: -pick add \$@ %<
?S:d_mq_receive:
?S: This variable conditionally defines HAS_MQ_RECEIVE if mq_receive() is
?S: available to receive a message from a POSIX message queue.
?S:.
?C:HAS_MQ_RECEIVE:
?C: This symbol, if defined, indicates that the mq_receive system call is
?C: available to receive a message from a POSIX message queue.
?C:.
?H:#\$d_mq_receive HAS_MQ_RECEIVE /**/
?H:.
?LINT:set d_mq_receive
: see if mq_receive exists
set mq_receive d_mq_receive
eval \$inlibc

Found in path(s):

*

/opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_mq_receive.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1999 Jarkko Hietaniemi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 3.0.

?RCS:

?MAKE:sitehtml3 sitehtml3exp installsitehtml3: Getfile Setprefixvar \
prefix siteprefix html3dir sed

?MAKE: -pick add \$@ %<

?Y:TOP

?D:sitehtml3="

?S:sitehtml3:

?S: This variable contains the name of the directory in which site-specific

?S: library html source pages are to be put. It is the responsibility of the

?S: Makefile.SH to get the value of this into the proper command.

?S: You must be prepared to do the ~name expansion yourself.

?S: The standard distribution will put nothing in this directory.

?S: After perl has

been installed, users may install their own local

?S: library html pages in this directory with

?S: MakeMaker Makefile.PL

?S: or equivalent. See INSTALL for details.

?S:.

?D:sitehtml3exp="

?S:sitehtml3exp:

?S: This variable is the same as the sitehtml3 variable, but is filename expanded at configuration time, for convenient use in makefiles.

?S:.

?D:installsitehtml3="

?S:installsitehtml3:

?S: This variable is really the same as sitehtml3exp, unless you are using AFS in which case it points to the read/write location whereas html3direxp only points to the read-only access location. For extra portability, you should only use this variable within your makefiles.

?S:.

?LINT:change prefixvar

?LINT:set installsitehtml3

?LINT:set sitehtml3

?LINT:set sitehtml3exp

: determine where add-on library html pages go

: There is no standard location, so try to copy the previously-selected directory structure for the core html pages.

case "\$sitehtml3" in

) dflt=`echo "\$html3dir"

| \$sed "s#^\$prefix#\$siteprefix#"` ;;

*) dflt=\$sitehtml3 ;;

esac

case "\$dflt" in

"| ") dflt=none ;;

esac

fn=dn+~

rp='Pathname where the site-specific library html pages should be installed?'

./getfile

prefixvar=sitehtml3

./setprefixvar

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/installdirs/sitehtml3.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_inetaton.U 1 2006-08-24 12:32:52Z rmanfredi \$

?RCS:

?RCS: Copyright (c) 1996, Spider Boardman

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic Licence,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: \$Log: d_inetaton.U,v \$
?RCS: Revision 3.0.1.1 1997/02/28 15:36:35 ram
?RCS: patch61: created
?RCS:
?MAKE:d_inetaton: Inlibc
?MAKE: -pick add \$@ %<
?S:d_inetaton:
?S: This variable conditionally defines the HAS_INET_ATON symbol, which
?S: indicates to the C program that the inet_aton() function is available
?S: to parse IP address "dotted-quad" strings.
?S:.
?C:HAS_INET_ATON:
?C: This symbol, if defined, indicates
to the C program that the
?C: inet_aton() function is available to parse IP address "dotted-quad"
?C: strings.
?C:.
?H:#\$d_inetaton HAS_INET_ATON /**/
?H:.
?LINT:set d_inetaton
: check whether inet_aton exists
set inet_aton d_inetaton
eval \$inlibc

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/d_inetaton.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$
?RCS:
?RCS: Copyright (c) 2015 Jarkko Hietaniemi, H.Merijn Brand
?RCS:
?RCS: You may distribute under the terms of either the GNU General Public
?RCS: License or the Artistic License, as specified in the README file.
?RCS:
?MAKE:longdblfnbytes longdblfnbytes doublefnbytes doublefnbytes: Inlibc \
cat i_math i_string Compile run rm_try Setvar echo d_longdbl \
doublekind doublesize longdblkind longdblsize
?MAKE: -pick add \$@ %<
?S:longdblfnbytes:
?S: This variable contains comma-separated list of hexadecimal bytes
?S: for the long double precision infinity.
?S:.
?S:longdblfnbytes:

```

?S: This variable contains comma-separated list of hexadecimal bytes
?S: for the long double precision not-a-number.
?S:.
?S:doubleinfbytes:
?S: This variable contains comma-separated list of hexadecimal bytes
?S: for the double precision infinity.
?S:.
?S:doublenanbytes:
?S: This variable contains comma-separated list of hexadecimal
bytes
?S: for the double precision not-a-number.
?S:.
?C:DOUBLEINFBYTES:
?C: This symbol, if defined, is a comma-separated list of
?C: hexadecimal bytes for the double precision infinity.
?C:.
?C:DOUBLENANBYTES:
?C: This symbol, if defined, is a comma-separated list of
?C: hexadecimal bytes (0xHH) for the double precision not-a-number.
?C:.
?C:LONGDBLINFBYTES:
?C: This symbol, if defined, is a comma-separated list of
?C: hexadecimal bytes for the long double precision infinity.
?C:.
?C:LONGDBLNANBYTES:
?C: This symbol, if defined, is a comma-separated list of
?C: hexadecimal bytes (0xHH) for the long double precision not-a-number.
?C:.
?H:#define DOUBLEINFBYTES $doubleinfbytes /**/
?H:#define DOUBLENANBYTES $doublenanbytes /**/
?H:#define LONGDBLINFBYTES $longdblinfbytes /**/
?H:#define LONGDBLNANBYTES $longdbl nanbytes /**/
?H:.
?F:!try
: Check what kind of inf/nan your system has
$echo "Checking the kind of infinities and nans you have..." >&4
$echo "(The following tests
may crash. That's okay.)" >&4
$cat >try.c <<EOP
#define DOUBLESIZE $doublesize
#$d_longdbl HAS_LONG_DOUBLE
#ifdef HAS_LONG_DOUBLE
#define LONG_DOUBLESIZE $longdblsize
#define LONG_DOUBLEKIND $longdblkind
#endif
#$i_math I_MATH
#$i_string I_STRING
#ifdef I_MATH

```

```

#include <math.h>
#endif
#ifdef I_STRING
# include <string.h>
#endif
#include <stdio.h>
/* Note that whether the sign bit is on or off
 * for NaN depends on the CPU/FPU, and possibly
 * can be affected by the build toolchain.
 *
 * For example for older MIPS and HP-PA 2.0 the quiet NaN is:
 * 0x7f, 0xf7, 0xff, 0xff, 0xff, 0xff, 0xff, 0xff
 * 0x7f, 0xf4, 0x00, 0x00, 0x00, 0x00, 0x00, 0x00
 * (respectively) as opposed to the more usual
 * 0x7f, 0xf8, 0x00, 0x00, 0x00, 0x00, 0x00, 0x00
 *
 * Pre-IEEE-754 floating point format do not even have inf/nan support
 * at all. They might have a "max" value (DBL_MAX), which may be deadly
 * to even mention, causing immediate SIGFPE or equivalent: this is
 * the case with VAX floating point,
 * for example.
 */
static void bytes(void *v, unsigned int n) {
    unsigned char *p = (unsigned char *)v;
    int i;
    for (i = 0; i < n; i++) {
        printf("0x%02x%s", p[i], i < n - 1 ? ", " : "\n");
    }
}

int main(int argc, char *argv[]) {
    /* We cannot use 1.0/0.0 and 0.0/0.0 (with L suffixes for long double)
     * because some compilers are 'smart' and not only warn but refuse to
     * compile such 'illegal' values. */
    double dinf = exp(1e9);
    double dnan = sqrt(-1.0);
#ifdef HAS_LONG_DOUBLE
    long double ldinf = (long double)exp(1e9);
    long double ldnan = (long double)sqrt(-1.0);
# if LONG_DOUBLEKIND == 3 || LONG_DOUBLEKIND == 4
/* the 80-bit long doubles might have garbage in their excess bytes */
    memset((char *)&ldinf + 10, '\0', LONG_DOUBLESIZE - 10);
    memset((char *)&ldnan + 10, '\0', LONG_DOUBLESIZE - 10);
# endif
    if (argc == 2) {
        switch (argv[1][0]) {
            case '1': bytes(&dinf, sizeof(dinf)); break;
            case '2': bytes(&dnan, sizeof(dnan)); break;
        }
    }
}

```

```

case '3': bytes(&ldinf, sizeof(ldinf)); break;
case '4': bytes(&ldnan, sizeof(ldnan)); break;
#endif
}
}
return 0;
}
EOP
set try
if eval $compile; then
doubleinfbytes=`$run ./try 1`
doublenanbytes=`$run ./try 2`
case "$d_longdbl" in
$define)
longdblinfbytes=`$run ./try 3`
longdbl nanbytes=`$run ./try 4`
;;
esac
else
# Defaults in case the above test program failed.
case "$doublekind" in
1) # IEEE 754 32-bit LE
doubleinfbytes='0x00, 0x00, 0xf0, 0x7f'
doublenanbytes='0x00, 0x00, 0xf8, 0x7f'
;;
2) # IEEE 754 32-bit BE
doubleinfbytes='0x7f, 0xf0, 0x00, 0x00'
doublenanbytes='0x7f, 0xf8, 0x00, 0x00'
;;
3) # IEEE 754 64-bit LE
doubleinfbytes='0x00, 0x00, 0x00, 0x00, 0x00, 0x00, 0xf0, 0x7f'
doublenanbytes='0x00, 0x00, 0x00, 0x00, 0x00, 0x00, 0xf8, 0x7f'
;;
4) # IEEE 754 64-bit BE
doubleinfbytes='0x7f, 0xf0, 0x00, 0x00, 0x00, 0x00, 0x00, 0x00'
doublenanbytes='0x7f,
0xf8, 0x00, 0x00, 0x00, 0x00, 0x00, 0x00'
;;
5) # IEEE 754 128-bit LE
doubleinfbytes='0x00, 0x00, 0xf0,
0x7f'
doublenanbytes='0x00, 0x00, 0xf8,
0x7f'
;;
6) # IEEE 754 128-bit BE
doubleinfbytes='0x7f, 0xf0, 0x00, 0x00,
0x00'
doublenanbytes='0x7f, 0xf8, 0x00, 0x00,
0x00'

```

```

0x00'
;;
7) # IEEE 754 64-bit mixed: 32-bit LEs in BE
doubleinbytes='0x00, 0x00, 0xf0, 0x7f, 0x00, 0x00, 0x00, 0x00'
doublenanbytes='0x00, 0x00, 0xf8, 0x7f, 0x00, 0x00, 0x00, 0x00'
;;
8) # IEEE 754 64-bit mixed: 32-bit BEs in LE
doubleinbytes='0x00, 0x00, 0x00, 0x00, 0x7f, 0xf0, 0x00, 0x00'
doublenanbytes='0x00, 0x00, 0x00, 0x00, 0x7f, 0xf8,
0x00, 0x00'
;;
9|10|11|12|13|14) # VAX/Cray/IBM floating point formats, no inf/nan.
doubleinbytes=$undef
doublenanbytes=$undef
;;
*) # No idea.
doubleinbytes=$undef
doublenanbytes=$undef
;;
esac
case "$longdblkind" in
1) # IEEE 754 128-bit LE
longdblifbytes='0x00, 0x00, 0xff,
0x7f'
longdblifnanbytes='0x00, 0x00, 0x80, 0xff,
0x7f'
;;
2) # IEEE 754 128-bit BE
longdblifbytes='0x7f, 0xff, 0x00, 0x00,
0x00'
longdblifnanbytes='0x7f, 0xff, 0x80, 0x00, 0x00,
0x00'
;;
3) # IEEE 754 80-bit LE, 12 or 16 bytes (x86)
case "$longdblsize" in
12) # x86 32-bit (96 bits, or 4 x 32, or 12 x 8)
longdblifbytes='0x00,
0x00, 0x00, 0x00, 0x00, 0x00, 0x00, 0x80, 0xff, 0x7f, 0x00, 0x00'
longdblifnanbytes='0x00, 0x00, 0x00, 0x00, 0x00, 0x00, 0x00, 0xc0, 0xff, 0x7f, 0x00, 0x00'
;;
16) # x86_64
longdblifbytes='0x00, 0x00, 0x00, 0x00, 0x00, 0x00, 0x00, 0x80, 0xff, 0x7f, 0x00, 0x00, 0x00, 0x00, 0x00,
0x00'
longdblifnanbytes='0x00, 0x00, 0x00, 0x00, 0x00, 0x00, 0x00, 0xc0, 0xff, 0x7f, 0x00, 0x00, 0x00, 0x00, 0x00,
0x00'
;;
*) # No idea.
longdblifbytes=$undef

```

```

    longdblmanbytes=$undef
;;
esac
;;
4) # IEEE 754 80-bit BE, 12 or 16 bytes
case "$longdblsize" in
12) # 32-bit system
    longdblmanbytes='0x7f, 0xff, 0x80, 0x00, 0x00, 0x00, 0x00, 0x00, 0x00, 0x00, 0x00, 0x00'
    longdblmanbytes='0x7f, 0xff, 0xc0, 0x00, 0x00, 0x00, 0x00, 0x00, 0x00, 0x00, 0x00, 0x00'
    ;;
16) # 64-bit system
    longdblmanbytes='0x7f, 0xff, 0x80, 0x00, 0x00,
0x00, 0x00, 0x00, 0x00, 0x00, 0x00, 0x00, 0x00, 0x00, 0x00, 0x00'
    longdblmanbytes='0x7f, 0xff, 0xc0, 0x00, 0x00,
0x00'
    ;;
*) # No idea.
    longdblmanbytes=$undef
    longdblmanbytes=$undef
    ;;
esac
;;
5) # 128-bit LE-LE "double double"
    longdblmanbytes='0x00, 0x00, 0xf0,
0x7f'
    longdblmanbytes='0x00, 0x00, 0xf8,
0x7f'
    ;;
6) # 128-bit BE-BE "double double"
    longdblmanbytes='0x7f, 0xf0, 0x00, 0x00,
0x00'
    longdblmanbytes='0x7f, 0xf8, 0x00, 0x00,
0x00'
    ;;
7) # 128-bit LE-BE "double double"
    longdblmanbytes='0x00, 0x00, 0x00, 0x00, 0x00, 0x00,
0xf0, 0x7f, 0x00, 0x00, 0x00, 0x00, 0x00, 0x00, 0x00'
    longdblmanbytes='0x00, 0x00, 0x00, 0x00, 0x00, 0x00, 0xf8, 0x7f, 0x00, 0x00, 0x00, 0x00, 0x00, 0x00, 0x00,
0x00'
    ;;
8) # 128-bit BE-LE "double double"
    longdblmanbytes='0x00, 0x00, 0x00, 0x00, 0x00, 0x00, 0x00, 0x00, 0x7f, 0xf0, 0x00, 0x00, 0x00, 0x00, 0x00,
0x00'
    longdblmanbytes='0x00, 0x00, 0x00, 0x00, 0x00, 0x00, 0x00, 0x00, 0x7f, 0xf8, 0x00, 0x00, 0x00, 0x00, 0x00,
0x00'
    ;;
9|10|11|12|13|14) # VAX/Cray/IBM floating point formats, no inf/nan.
    longdblmanbytes=$undef

```

```

    longdblmanbytes=$undef
    ;;
*) # No idea.
    longdblmanbytes=$undef
    longdblmanbytes=$undef
    ;;
esac
fi
# In case the program crashed the values are empty, turn them undef.
case "$doubleinbytes" in
") doubleinbytes=$undef ;;
esac
case "$doublemanbytes" in
") doublemanbytes=$undef ;;
esac
case "$longdblmanbytes" in
") longdblmanbytes=$undef ;;
esac
case "$longdblmanbytes"
in
") longdblmanbytes=$undef ;;
esac
$rm_try

```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/infman.U
```

No license file was found, but licenses were detected in source scan.

```

?RCS: $Id: lib.U,v 3.0.1.3 1995/09/25 09:16:47 ram Exp $
?RCS:
?RCS: Copyright (c) 1991-1993, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 3.0.
?RCS:
?RCS: $Log: lib.U,v $
?RCS: Revision 3.0.1.3 1995/09/25 09:16:47 ram
?RCS: patch59: unit is now forced to the top of Configure, if possible
?RCS:
?RCS: Revision 3.0.1.2 1995/01/30 14:38:08 ram
?RCS: patch49: can now handle installation prefix changes (from WED)
?RCS:
?RCS: Revision 3.0.1.1 1994/08/29 16:27:40 ram
?RCS: patch32: now uses installation prefix to set the default

```

```

?RCS:
?RCS: Revision 3.0 1993/08/18 12:08:56 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?LINT:
empty
?X:?MAKE:lib libexp: Getfile Loc Oldconfig Prefixit Prefixup prefixexp
?X:?MAKE: -pick add $@ %<
?X:?Y:TOP
?X:?S:lib:
?X:?S: This variable holds the name of the directory in which the user wants
?X:?S: to put public library files for the package in question. It is most
?X:?S: often a local directory such as /usr/local/lib. Programs using this
?X:?S: variable must be prepared to deal with filename expansion.
?X:?S:.
?X:?S:libexp:
?X:?S: This variable is the same as the lib variable, but is filename expanded
?X:?S: at configuration time, for convenient use in your makefiles.
?X:?S:.
?X:: determine where public libraries go
?X:set lib lib
?X:eval $prefixit
?X:case "$lib" in
?X:")
?X: dflt=`./loc . ." $prefixexp/lib /usr/local/lib /usr/lib /lib`
?X: set dflt
?X: eval $prefixup
?X: ;;
?X:*) dflt="$lib";;
?X:esac
?X:echo " "
?X:fn=d~
?X:rp='Where do you want to put the public libraries?'
?X:. /getfile
?X:lib="$ans"
?X:libexp="$ansexp"

```

Found in path(s):

```

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/nullified/lib.U

```

No license file was found, but licenses were detected in source scan.

```

?RCS: $Id$
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.

```

?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: Copyright (c) 1998 Andy Dougherty
?RCS:
?RCS: Original author Jarkko Hietaniemi <jhi@iki.fi>
?RCS: Merged into dist by Andy Dougherty July 13, 1998
?RCS:
?MAKE:trnl: Nothing
?MAKE: -pick add \$@ %<
?S:trnl:
?S: This variable contains the value to be passed to the tr(1)
?S: command to transliterate a newline. Typical values are
?S: '\012' and '\n'. This is needed for EBCDIC systems where
?S: newline is not necessarily '\012'.
?S:.
?T: DJGPP
: Find the appropriate value for a newline for tr
?X: We can't
use \$tr since that would cause a circular dependency via Myread
?X: dos djgpp uses '\015\012', but reportedly is happy with '\012' in the
?X: tr command. I don't know why it passes the '\n' test but later
?X: refuses to work correctly with it. --AD 6/14/98
if test -n "\$DJGPP"; then
trnl='\012'
fi
if test X"\$trnl" = X; then
case "`echo foo | tr '\n' x 2>/dev/null`" in
foox) trnl='\n' ;;
esac
fi
if test X"\$trnl" = X; then
case "`echo foo | tr '\012' x 2>/dev/null`" in
foox) trnl='\012' ;;
esac
fi
if test X"\$trnl" = X; then
case "`echo foo | tr '\r\n' xy 2>/dev/null`" in
fooxy) trnl='\n\r' ;;
esac
fi
if test X"\$trnl" = X; then
cat <<EOM >&2

\$me: Fatal Error: cannot figure out how to translate newlines with 'tr'.

EOM

```
exit 1
fi
```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/trnl.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id$
```

```
?RCS:
```

```
?RCS: Copyright (c) 1999 Jarkko Hietaniemi
```

```
?RCS:
```

```
?RCS: You may distribute under the terms of either the GNU General Public
```

```
?RCS: License or the Artistic License, as specified in the README file.
```

```
?RCS:
```

```
?MAKE:uselonglong: Myread Oldconfig Setvar cat test ccflags
```

```
?MAKE: -pick add $@ %<
```

```
?Y:TOP
```

```
?S:uselonglong:
```

```
?S: This variable conditionally defines the USE_LONG_LONG symbol,
```

```
?S: and indicates that long longs should be used when available.
```

```
?S:.
```

```
?C:USE_LONG_LONG:
```

```
?C: This symbol, if defined, indicates that long longs should
```

```
?C: be used when available.
```

```
?C:.
```

```
?H:%<:#ifndef USE_LONG_LONG
```

```
?H:%<:#$uselonglong USE_LONG_LONG /**/
```

```
?H:%<:#endif
```

```
?H:.
```

```
?LINT:extern ccflags
```

```
?F:!uselonglong.cbu
```

```
: Check for longlong support
```

```
case "$uselonglong" in
```

```
"|true|[yY]*) uselonglong="$define" ;;
```

```
*) case "$ccflags" in
```

```
*-DUSE_LONG_LONG*) uselonglong="$define" ;;
```

```
*) uselonglong="$undef" ;;
```

```
esac
```

```
::
```

```
esac
```

```
case "$uselonglong"
```

```
in
```

```
$define) dflt='y';;
```

```
*) dflt='n';;
```

```
esac
```

```
cat <<EOM
```

Perl can be built to take advantage of long longs which (if available) may give more range for integer numbers.

If this doesn't make any sense to you, just accept the default '\$dflt'.

EOM

```
rp="Try to use long longs if available?"
```

```
./myread
```

```
case "$ans" in
```

```
y|Y) val="$define" ;;
```

```
*) val="$undef" ;;
```

```
esac
```

```
set uselonglong
```

```
eval $setvar
```

```
case "$uselonglong" in
```

```
$define)
```

```
: Look for a hint-file generated 'call-back-unit'. If the
```

```
: user has specified that long longs should be used,
```

```
: we may need to set or change some other defaults.
```

```
if $test -f uselonglong.cbu; then
```

```
echo "Your platform has some specific hints for long longs, using them..."
```

```
./uselonglong.cbu
```

```
else
```

```
$cat <<EOM
```

```
(Your platform doesn't have any specific hints for long longs.)
```

```
EOM
```

```
fi
```

```
::
```

```
esac
```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/uselonglong.U
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 2000 Jarkko Hietaniemi

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?MAKE:d_fchdir: Inlibc

?MAKE:-pick add \$@ %<

?S:d_fchdir:

?S: This variable conditionally defines the HAS_FCHDIR symbol, which

?S: indicates to the C program that the fchdir() routine is available.

?S:.

?C:HAS_FCHDIR:

?C: This symbol, if defined, indicates that the fchdir routine is

?C: available to change directory using a file descriptor.

?C:.

?H:#\$d_fchdir HAS_FCHDIR /**/

?H:.

?LINT:set d_fchdir

: see if fchdir exists

set fchdir d_fchdir

eval \$inlibc

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_fchdir.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1999 Jarkko Hietaniemi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 3.0.

?RCS:

?MAKE:d_telldirproto: Hasproto i_systypes i_dirent

?MAKE: -pick add \$@ %<

?S:d_telldirproto:

?S: This variable conditionally defines the HAS_TELLDIR_PROTO symbol,

?S: which indicates to the C program that the system provides

?S: a prototype for the telldir() function. Otherwise, it is

?S: up to the program to supply one.

?S:.

?C:HAS_TELLDIR_PROTO:

?C: This symbol, if defined, indicates that the system provides

?C: a prototype for the telldir() function. Otherwise, it is up

?C: to the program to supply one. A good guess

is

?C: extern long telldir(DIR*);

?C:.

?H:#\$d_telldirproto HAS_TELLDIR_PROTO /**/

?H:.

?LINT:set d_telldirproto

: see if prototype for telldir is available

echo " "

set d_telldirproto telldir \$i_systypes sys/types.h \$i_dirent dirent.h

eval \$hasproto

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_telldirproto.U
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: d_NOFILE.U,v \$

?RCS: Revision 3.0.1.1 1994/10/29 16:08:38 ram

?RCS: patch36: added ?F: line for metalint file checking

?RCS:

?RCS: Revision 3.0 1993/08/18 12:05:39 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?MAKE:nofile d_gettblsz tablesize: Myread Guess cat +cc +ccflags +libs \
test rm Csym

?MAKE: -pick add \$@ %<

?S:nofile:

?S: This variable contains the number of file descriptors available to the

?S: process.

?S:.

?S:d_gettblsz:

?S: This variable conditionally handles remapping
of the getdtablesize()

?S: subroutine to ulimit(4,0), or the NOFILE manifest constant.

?S:.

?S:tablesize:

?S: This variable contains either the 'NOFILE' constant or 'ulimit(4, 0L)'

?S: and is used as the remapped value for the getdtablesize() macro.

?S:.

?C:getdtablesize:

?C: This catches use of the getdtablesize() subroutine, and remaps it

?C: to either ulimit(4,0) or NOFILE, if getdtablesize() isn't available.

?C:.

?C:VAL_NOFILE:

?C: This symbol contains the number of file descriptors available to the

?C: process, as determined at configuration time. Unless a static constant

?C: is needed, you should rely on getdtablesize() to obtain that number.

?C:.

?H:#\$d_gettblsz getdtablesize() \$tablesize /**/

```

?H:#define VAL_NOFILE $nofile /* Number of file descriptors */
?H:.
?F:!nofile
?T:d_ulimit4 val
: see if getdtablesize exists
echo " "
?X: Revert logical value (d_gettblsz is undef iff getdtablesize is present)
case "$d_gettblsz" in
$define) d_gettblsz="$undef";;
$undef) d_gettblsz="$define";;
esac
if
set getdtablesize val -f d_gettblsz; eval $csym; $val; then
echo 'getdtablesize() found.' >&4
d_gettblsz="$undef"
tablesize="
@if VAL_NOFILE || nofile
$cat >nofile.c <<'EOCP'
#include <stdio.h>
int main()
{
printf("%d\n", getdtablesize());
}
EOCP
nofile="
if $cc $ccflags -o nofile nofile.c $libs >/dev/null 2>&1; then
nofile=`./nofile 2>/dev/null`
fi
if $test "$nofile"; then
echo "(You have $nofile file descriptors available per process.)"
else
nofile='20'
if ./bsd; then
nofile='64'
fi
echo "(Hmm... Let's say you have $nofile file descriptors available.)"
fi
@end
else
echo 'getdtablesize() NOT found...' >&4
if set ulimit val -f; eval $csym; $val; then
echo 'Maybe ulimit(4,0) will work...!'
$cat >nofile.c <<'EOCP'
#include <stdio.h>
#ifdef GETPARAM_H
#include <sys/param.h>
#endif
int main()

```

```

{
printf("%d %d\n",
#ifdef NOFILE
NOFILE,
#else
0,
#endif
ulimit(4,0));
exit(0);
}
EOCP
if $cc $cflags -DGETPARAM_H -o nofile nofile.c $libs
>/dev/null 2>&1 \
|| $cc $cflags -o nofile nofile.c $libs >/dev/null 2>&1 ; then
set `./nofile`
d_gettblsz=$1
d_ulimit4=$2
if $test "$d_ulimit4" -lt 0; then
echo "Your ulimit() call doesn't tell me what I want to know."
echo "We'll just use NOFILE in this case."
nofile=$d_gettblsz
d_gettblsz="$define"
tablesize='NOFILE'
else
if $test "$d_gettblsz" -gt 0; then
echo "Your system defines NOFILE to be $d_gettblsz, and" >&4
else
echo "I had trouble getting NOFILE from your system, but" >&4
fi
echo "ulimit returns $d_ulimit4 as the number of available file descriptors." >&4
dflt='y';
echo " "
rp='Should I use ulimit to get the number of available file descriptors?'
. ./myread
case "$ans" in
y*)
nofile=$d_ulimit4
d_gettblsz="$define"
tablesize='ulimit(4, 0L)'
echo "Using ulimit(4,0)."
;;
*)
nofile=$d_gettblsz
d_gettblsz="$define"
tablesize='NOFILE'
echo "Using NOFILE."
;;
esac

```

```

fi
else
echo
"Strange, I couldn't get my test program to compile."
echo "We'll just use NOFILE in this case."
d_gettblsz="$define"
tablesize='NOFILE'
nofile=""
fi
else
echo 'Using NOFILE instead.'
d_gettblsz="$define"
tablesize='NOFILE'
nofile=""
fi
fi
@if VAL_NOFILE || nofile
case "$nofile" in
")
$cat >nofile.c <<'EOCP'
#include <stdio.h>
#ifdef GETPARAM_H
#include <sys/param.h>
#endif
int main()
{
printf("%d\n",
#ifdef NOFILE
NOFILE,
#else
0,
#endif
);
exit(0);
}
EOCP
if $cc $ccflags -DGETPARAM_H -o nofile nofile.c $libs >/dev/null 2>&1 \
|| $cc $ccflags -o nofile nofile.c $libs >/dev/null 2>&1 ; then
nofile=`./nofile 2>/dev/null`
fi
if $test "$nofile"; then
echo "(You have $nofile file descriptors available per process.)"
else
nofile='20'
if ./bsd; then
nofile='64'
fi
echo "(Hmm... Let's say you have $nofile file descriptors available.)"

```

```
fi
;;
esac
@end
$rm -f nofile*
```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/d_NOFILE.U
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 2000, Andy Dougherty

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 3.0.

?RCS:

?MAKE:versiononly: cat Myread Setvar Devel

?MAKE:-pick add \$@ %<

?LINT:set versiononly

?Y:TOP

?S:versiononly:

?S: If set, this symbol indicates that only the version-specific

?S: components of a perl installation should be installed.

?S: This may be useful for making a test installation of a new

?S: version without disturbing the existing installation.

?S: Setting versiononly is equivalent to setting installperl's -v option.

?S: In particular, the non-versioned scripts and programs such as

?S: a2p, c2ph, h2xs, pod2*, and perldoc

are not installed

?S: (see INSTALL for a more complete list). Nor are the man

?S: pages installed.

?S: Usually, this is undef.

?S:.

?LINT:extern inc_version_list

?LINT:change inc_version_list

?LINT:extern inc_version_list_init

?LINT:change inc_version_list_init

?LINT:extern version

: determine whether to use a version number suffix for installed binaries

echo " "

\$cat <<EOM

Do you want to use a version number suffix for installed binaries? This

will install 'perl\$version' instead of 'perl', and likewise for other

binaries like 'perldoc' and 'cpan'. This allows many versions of perl to be installed side-by-side. Unless you are a developer, you probably do *not* want to do this.

EOM

```
case "$versiononly" in
"$define"[[Yy]*|true) dflt='y' ;;
*) dflt='n';
esac
rp="Do you want to use a version number suffix for installed binaries?"
./myread
case "$ans" in
[yY]*) val="$define";;
*) val="$undef" ;;
esac
set versiononly
eval $setvar

case "$versiononly" in
"$define") inc_version_list="
    inc_version_list_init=0
    ;;
esac
```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/versiononly.U
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: Oldsym.U,v \$

?RCS: Revision 3.0.1.1 1997/02/28 15:06:58 ram

?RCS: patch61: added support for src.U

?RCS:

?RCS: Revision 3.0 1993/08/18 12:05:13 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?X:

?X: This unit follows the creation of the config.sh file. It adds some

?X: special symbols: defines from patchlevel.h file if any and CONFIG,

```

?X: which is set to true. Then, we try to keep all the new symbols that
?X: may come from a hint file or a previous config.sh file.
?X:
?MAKE:Oldsym:
  Config_sh Options test hint src sed sort uniq
?MAKE: -pick add $@ %<
?T:CONFIG sym tmp
?F:!UU
: add special variables
$test -f $src/patchlevel.h && \
awk '/^#define/ {printf "%s=%s\n", $2, $3}' $src/patchlevel.h >>config.sh
echo "CONFIG=true" >>config.sh

: propagate old symbols
if $test -f UU/config.sh; then
?X: Make sure each symbol is unique in oldconfig.sh
<UU/config.sh $sort | $uniq >UU/oldconfig.sh
?X:
?X: All the symbols that appear twice come only from config.sh (hence the
?X: two config.sh in the command line). These symbols will be removed by
?X: the uniq -u command. The oldsyms file thus contains all the symbols
?X: that did not appear in the produced config.sh (Larry Wall).
?X:
?X: Do not touch the -u flag of uniq. This means you too, Jarkko.
?X:
$sed -n 's/^\([a-zA-Z_0-9]*\)=.*\1/p' \
config.sh config.sh UU/oldconfig.sh \
$sort | $uniq -u >UU/oldsyms
set X `cat UU/oldsyms`
shift
case $# in
0) ;;
*)
cat <<EOM
Hmm...You had some extra variables I don't know about...I'll
try to keep 'em...
EOM
echo ": Variables propagated from previous config.sh file." >>config.sh
for sym in `cat UU/oldsyms`; do
echo "  Propagating $hint variable ""$""$sym..."
eval `tmp=""$""${sym}""`
echo "$tmp" | \
sed -e "s/'\"/\"'/g" -e "s/^\$sym=/'" -e "s/$/'" >>config.sh
done
;;
esac
fi

```

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/Oldsym.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_fork.U 1 2006-08-24 12:32:52Z rmanfredi \$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic Licence,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic Licence; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: Original Author: Andy Dougherty <doughera@lafcol.lafayette.edu>

?RCS:

?RCS: \$Log: d_fork.U,v \$

?RCS: Revision 3.0.1.1 1994/08/29 16:07:38 ram

?RCS: patch32: created by ADO

?RCS:

?MAKE:d_fork: Inlibc

?MAKE: -pick add \$@ %<

?S:d_fork:

?S: This variable conditionally defines the HAS_FORK symbol, which

?S: indicates to the C program that the fork() routine is available.

?S:.

?C:HAS_FORK :

?C: This symbol, if defined, indicates that the fork routine is

?C: available.

?C:.

?H:#\$d_fork

HAS_FORK /**/

?H:.

?LINT:set d_fork

: see if fork exists

set fork d_fork

eval \$inlibc

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/d_fork.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_getprotoprotos.U,v \$

?RCS:

?RCS: Copyright (c) 1991-1993, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 3.0.
?RCS:
?MAKE:d_getprotoprotos : Hasproto i_netdb
?MAKE: -pick add \$@ %<
?S:d_getprotoprotos:
?S: This variable conditionally defines the HAS_GETPROTO_PROTOS symbol,
?S: which indicates to the C program that <netdb.h> supplies
?S: prototypes for the various getproto*() functions.
?S: See also netdbtype.U for probing for various netdb types.
?S:.
?C:HAS_GETPROTO_PROTOS:
?C: This symbol, if defined, indicates that <netdb.h> includes
?C: prototypes for getprotoent(), getprotobyname(), and
?C: getprotobyaddr().
Otherwise, it is up to the program to guess
?C: them. See netdbtype.U for probing for various Netdb_xxx_t types.
?C:.
?H:#\$d_getprotoprotos HAS_GETPROTO_PROTOS /**/
?H:.
?LINT:set d_getprotoprotos
: see if prototypes for various getprotoxxx netdb.h functions are available
echo " "
set d_getprotoprotos getprotoent \$i_netdb netdb.h
eval \$hasproto

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/protos/d_getprotoprotos.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: i_syslog.U,v \$
?RCS:
?RCS: Copyright (c) 2000 Jarkko Hietaniemi
?RCS:
?RCS: You may distribute under the terms of either the GNU General Public
?RCS: License or the Artistic License, as specified in the README file.
?RCS:
?MAKE:i_syslog: Inhdr Hasfield
?MAKE: -pick add \$@ %<
?S:i_syslog:
?S: This variable conditionally defines the I_SYSLOG symbol,
?S: and indicates whether a C program should include <syslog.h>.
?S:.
?C:I_SYSLOG:

?C: This symbol, if defined, indicates that <syslog.h> exists and

?C: should be included.

?C:.

?H:#\$i_syslog I_SYSLOG /**/

?H:.

?LINT:set i_syslog

: see if this is a syslog.h system

set syslog.h i_syslog

eval \$inhdr

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/i_syslog.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: i_execinfo.U 34 2010-11-27 11:55:39Z rmanfredi \$

?RCS:

?RCS: Copyright (c) 2011, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?MAKE:i_execinfo: Inhdr

?MAKE:-pick add \$@ %<

?S:i_execinfo:

?S: This variable conditionally defines the I_EXECINFO symbol, and indicates

?S: whether a C program may include <execinfo.h>, for backtrace() support.

?S:.

?C:I_EXECINFO:

?C: This symbol, if defined, indicates to the C program that it should

?C: include <execinfo.h> for backtrace() support.

?C:.

?H:#\$i_execinfo I_EXECINFO /**/

?H:.

?LINT:set i_execinfo

: see if this is an execinfo.h system

set execinfo.h i_execinfo

eval

\$inhdr

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/modified/i_execinfo.U

No license file was found, but licenses were detected in source scan.

?RCS: You may distribute under the terms of either the GNU General Public
 ?RCS: License or the Artistic License, as specified in the README file.
 ?RCS:
 ?MAKE:d_remainder: Inlibc
 ?MAKE: -pick add \$@ %<
 ?S:d_remainder:
 ?S: This variable conditionally defines the HAS_REMAINDER symbol, which
 ?S: indicates to the C program that the remainder() routine is available.
 ?S:.
 ?C:HAS_REMAINDER:
 ?C: This symbol, if defined, indicates that the remainder routine is
 ?C: available to return the floating-point remainder.
 ?C:.
 ?H:#\$d_remainder HAS_REMAINDER /**/
 ?H:.
 ?LINT:set d_remainder
 : see if remainder exists
 set remainder d_remainder
 eval \$inlibc

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_remainder.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: netdbtype.U,v \$
 ?RCS:
 ?RCS: Copyright (c) 1998 Andy Dougherty
 ?RCS:
 ?RCS: You may distribute under the terms of either the GNU General Public
 ?RCS: License or the Artistic License, as specified in the README file.
 ?RCS:
 ?RCS: Original Author: Andy Dougherty <doughera@lafcol.lafayette.edu>
 ?RCS:
 ?RCS: \$Log: netdbtype.U,v \$
 ?RCS:
 ?MAKE:netdb_host_type netdb_hlen_type netdb_name_type netdb_net_type: \
 Protochk Oldconfig Myread cat \
 d_gethbyaddr d_gethbyname d_getnbyaddr \
 i_niin i_netdb i_unistd d_socket sizetype extern_C
 ?MAKE: -pick add \$@ %<
 ?S:netdb_host_type:
 ?S: This variable holds the type used for the 1st argument to
 ?S: gethostbyaddr(). Usually, this is char * or void *, possibly
 ?S: with or without a const prefix.
 ?S: This is only useful if you have gethostbyaddr(), naturally.
 ?S:.
 ?S:netdb_hlen_type:

?S: This variable holds the type used for the 2nd argument to
 ?S: gethostbyaddr(). Usually,
 this is int or size_t or unsigned.
 ?S: This is only useful if you have gethostbyaddr(), naturally.
 ?S:.
 ?S:netdb_name_type:
 ?S: This variable holds the type used for the argument to
 ?S: gethostbyname(). Usually, this is char * or const char *.
 ?S: This is only useful if you have gethostbyname(), naturally.
 ?S:.
 ?S:netdb_net_type:
 ?S: This variable holds the type used for the 1st argument to
 ?S: getnetbyaddr(). Usually, this is int or long.
 ?S: This is only useful if you have getnetbyaddr(), naturally.
 ?S:.
 ?C:Netdb_host_t:
 ?C: This symbol holds the type used for the 1st argument
 ?C: to gethostbyaddr().
 ?C:.
 ?C:Netdb_hlen_t:
 ?C: This symbol holds the type used for the 2nd argument
 ?C: to gethostbyaddr().
 ?C:.
 ?C:Netdb_name_t:
 ?C: This symbol holds the type used for the argument to
 ?C: gethostbyname().
 ?C:.
 ?C:Netdb_net_t:
 ?C: This symbol holds the type used for the 1st argument to
 ?C: getnetbyaddr().
 ?C:.
 ?H:#define Netdb_host_t \$netdb_host_type /**/
 ?H:#define Netdb_hlen_t \$netdb_hlen_type
 /**/
 ?H:#define Netdb_name_t \$netdb_name_type /**/
 ?H:#define Netdb_net_t \$netdb_net_type /**/
 ?H:.
 ?T:xxx yyy try hdrs
 @if netdb_host_type || Netdb_host_t || netdb_hlen_type || Netdb_hlen_t
 : check for type of arguments to gethostbyaddr.
 if test "X\$netdb_host_type" = X -o "X\$netdb_hlen_type" = X; then
 case "\$d_gethbyaddr" in
 \$define)
 \$cat <<EOM

Checking to see what type of arguments are accepted by gethostbyaddr().

EOM

hdrs="\$define sys/types.h

```

$D_socket sys/socket.h
$I_niin netinet/in.h
$I_netdb netdb.h
$I_unistd unistd.h"
: The first arg can 'char *' or 'void *'
: The second arg is some of integral type
for xxx in in_addr_t 'const void *' 'const char *' 'void *' 'char *'; do
for yyy in size_t long int; do
case "$netdb_host_type" in
") try="$Sextern_C struct hostent *gethostbyaddr($xxx, $yyy, int);"
if ./protochk "$try" $hdrs; then
echo "Your system accepts $xxx for the first arg."
echo "...and $yyy for the second arg."
netdb_host_type="$xxx"
netdb_hlen_type="$yyy"
fi
;;
esac
done
done
:
In case none of those worked, prompt the user.
case "$netdb_host_type" in
") rp='What is the type for the 1st argument to gethostbyaddr?'
dflt='char *'
./myread
netdb_host_type=$ans
rp='What is the type for the 2nd argument to gethostbyaddr?'
dflt="$sizetype"
./myread
netdb_hlen_type=$ans
;;
esac
;;
*) : no gethostbyaddr, so pick harmless defaults
netdb_host_type='char *'
netdb_hlen_type="$sizetype"
;;
esac
# Remove the "const" if needed. -- but then we'll have a
# prototype clash!
# netdb_host_type=`echo "$netdb_host_type" | sed 's/^const //'`
fi
@end

@if netdb_name_type || Netdb_name_t
: check for type of argument to gethostbyname.
if test "X$netdb_name_type" = X ; then

```

```

case "$d_gethbyname" in
$define)
$cat <<EOM

```

Checking to see what type of argument is accepted by gethostbyname().

EOM

```

hdrs="$define sys/types.h
$d_socket sys/socket.h
$i_niin
netinet/in.h
$i_netdb netdb.h
$i_unistd unistd.h"
for xxx in "const char *" "char *"; do
case "$netdb_name_type" in
") try="$xtern_C struct hostent *gethostbyname($xxx);"
if ./protochk "$stry" $hdrs; then
echo "Your system accepts $xxx."
netdb_name_type="$xxx"
fi
;;
esac
done
: In case none of those worked, prompt the user.
case "$netdb_name_type" in
") rp='What is the type for the 1st argument to gethostbyname?'
dflt='char *'
./myread
netdb_name_type=$ans
;;
esac
*) : no gethostbyname, so pick harmless default
netdb_name_type='char *'
;;
esac
fi
@end

```

```

@if netdb_net_type || Netdb_net_t
: check for type of 1st argument to getnetbyaddr.
if test "X$netdb_net_type" = X ; then
case "$d_getnbyaddr" in
$define)
$cat <<EOM

```

Checking to see what type of 1st argument is accepted by getnetbyaddr().

EOM

```

hdrs="$define sys/types.h

```

```

$d_socket sys/socket.h
$i_niin netinet/in.h
$i_netdb netdb.h
$i_unistd
unistd.h"
for xxx in in_addr_t "unsigned long" long "unsigned int" int; do
case "$netdb_net_type" in
") try="$extern_C struct netent *getnetbyaddr($xxx, int);"
if ./protochk "$try" $hdrs; then
echo "Your system accepts $xxx."
netdb_net_type="$xxx"
fi
;;
esac
done
: In case none of those worked, prompt the user.
case "$netdb_net_type" in
") rp='What is the type for the 1st argument to getnetbyaddr?'
dflt='long'
./myread
netdb_net_type=$ans
;;
esac
;;
*) : no getnetbyaddr, so pick harmless default
netdb_net_type='long'
;;
esac
fi
@end

```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/protos/netdbtype.U
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_endpwent_r.U,v 0RCS:

?RCS: Copyright (c) 2002,2003 Jarkko Hietaniemi

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?RCS: Generated by the reentr.pl from the Perl 5.8 distribution.

?RCS:

?MAKE:d_endpwent_r endpwent_r_proto: Inlibc Protochk Hasproto i_systypes \
 usethreads i_pwd extern_C

?MAKE: -pick add \$@ %<

?S:d_endpwent_r:

?S: This variable conditionally defines the HAS_ENDPWENT_R symbol,
?S: which indicates to the C program that the endpwent_r()
?S: routine is available.
?S:.
?S:endpwent_r_proto:
?S: This variable encodes the prototype of endpwent_r.
?S: It is zero if d_endpwent_r is undef, and one of the
?S: REENTRANT_PROTO_T_ABC macros of reentr.h if d_endpwent_r
?S: is defined.
?S:.
?C:HAS_ENDPWENT_R:
?C: This symbol, if defined, indicates that the endpwent_r routine
?C: is available to
endpwent re-entrantly.
?C:.
?C:ENDPWENT_R_PROTO:
?C: This symbol encodes the prototype of endpwent_r.
?C: It is zero if d_endpwent_r is undef, and one of the
?C: REENTRANT_PROTO_T_ABC macros of reentr.h if d_endpwent_r
?C: is defined.
?C:.
?H:#\$d_endpwent_r HAS_ENDPWENT_R /**/
?H:#define ENDPWENT_R_PROTO \$endpwent_r_proto /**/
?H:.
?T:try hdrs d_endpwent_r_proto
: see if endpwent_r exists
set endpwent_r d_endpwent_r
eval \$inlibc
case "\$d_endpwent_r" in
"\$define")
hdrs="\$i_systypes sys/types.h define stdio.h \$i_pwd pwd.h"
case "\$d_endpwent_r_proto:\$usetreads" in
":define") d_endpwent_r_proto=define
set d_endpwent_r_proto endpwent_r \$hdrs
eval \$hasproto ;;
*) ;;
esac
case "\$d_endpwent_r_proto" in
define)
case "\$endpwent_r_proto" in
"|0) try='int endpwent_r(FILE**);'
./protochk "\$sextern_C \$try" \$hdrs && endpwent_r_proto=I_H ;;
esac
case "\$endpwent_r_proto" in
"|0) try='void endpwent_r(FILE**);'
./protochk "\$sextern_C \$try" \$hdrs && endpwent_r_proto=V_H ;;
esac
case

```

"$endpwent_r_proto" in
"|0) d_endpwent_r=undef
    endpwent_r_proto=0
    echo "Disabling endpwent_r, cannot determine prototype." >&4 ;;
*) case "$endpwent_r_proto" in
    REENTRANT_PROTO*) ;;
*) endpwent_r_proto="REENTRANT_PROTO_$endpwent_r_proto" ;;
esac
echo "Prototype: $try" ;;
esac
;;
*) case "$usethreads" in
define) echo "endpwent_r has no prototype, not using it." >&4 ;;
esac
d_endpwent_r=undef
endpwent_r_proto=0
;;
esac
;;
*) endpwent_r_proto=0
;;
esac

```

Found in path(s):

```

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/threads/d_endpwent_r.U

```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1999, Jarkko Hietaniemi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 3.0.

?RCS:

?MAKE:d_posix_shm: Setvar d_shm_open d_shm_unlink i_sysmman

?MAKE: -pick add \$@ %<

?S:d_posix_shm:

?S: This variable conditionally defines the HAS_POSIX_SHM symbol, which

?S: indicates that the entire POSIX shm_*(2) library is present.

?S:.

?C:HAS_POSIX_SHM:

?C: This symbol, if defined, indicates that the entire POSIX shm_*(2)

?C: library is supported.

?C:.

```

?H:#$d_posix_shm HAS_POSIX_SHM /**/
?H:.
?LINT:set d_posix_shm
: see how much of the 'POSIX shm_*(2)' library is present.
echo " "
case "$i_sysmman$d_shm_open$d_shm_unlink"
in
*"$sundef"*) val="$sundef" ;;
*) val="$define" ;;
esac
case "$sval" in
"$define") echo "You have the full POSIX shm_*(2) library." >&4 ;;
"$sundef") echo "You don't have the full POSIX shm_*(2) library." >&4 ;;
esac
set d_posix_shm
eval $setvar

```

Found in path(s):

```

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/perl/d_posix_shm.U

```

No license file was found, but licenses were detected in source scan.

```

?RCS: $Id: mailer.U 1 2006-08-24 12:32:52Z rmanfredi $
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: $Log: mailer.U,v $
?RCS: Revision 3.0.1.3 1995/01/11 15:32:11 ram
?RCS: patch45: can now use Loc variables since path stripping is deferred
?RCS:
?RCS: Revision 3.0.1.2 1994/05/06 15:10:04 ram
?RCS: patch23: ensure full path value is used for rmail also
?RCS:
?RCS: Revision 3.0.1.1 1994/01/24 14:14:18 ram
?RCS: patch16: now use _sendmail vars and friends for portability issues
?RCS:
?RCS: Revision 3.0 1993/08/18 12:09:10 ram
?RCS: Baseline for dist
3.0 netwide release.
?RCS:
?MAKE:mailer: test cat rmail mail smail sendmail Getfile Oldconfig
?MAKE: -pick add $@ %<

```

```

?S:mailer:
?S: This variable contains the full pathname of a reasonable mailer.
?S: By reasonable, we mean some program which can understand internet
?S: addresses or at least forward them to some internet router. This
?S: mailer should be invoked as "mailer [options] recipients <mail>".
?S:.
: determine the name of a reasonable mailer
case "$mailer" in
")
if $test -f "$sendmail"; then
  dflt="$sendmail"
elif $test -f "$smail"; then
  dflt="$smail"
elif $test -f "$rmail"; then
  dflt="$rmail"
elif $test -f /bin/mail; then
  dflt=/bin/mail
else
  dflt=$mail
fi
;;
*) dflt="$mailer";;
esac
$cat <<EOM

```

I need the full pathname of the program used to deliver mail on your system. A typical answer would be /usr/lib/sendmail or /bin/rmail, but you may choose any other program, as long as it can be fed from standard input and will honour any user-supplied headers.

```

EOM
fn=f
rp='Mail
transport agent to be used?'
./getfile
mailer="$ans"

```

Found in path(s):
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/mailer.U
No license file was found, but licenses were detected in source scan.

```

?RCS: $Id$
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.

```

?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: d_gethname.U,v \$

?RCS: Revision 3.0.1.1 1994/10/29 16:13:00 ram

?RCS: patch36: call ./xenix explicitly instead of relying on PATH

?RCS:

?RCS: Revision 3.0 1993/08/18 12:06:11 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?MAKE:d_gethname d_uname d_phostname aphostname: phostname cat \
myhostname package d_portable Loc echo n c +i_whoami +usrinc \
Myread Guess Oldconfig Csym

?MAKE: -pick add \$@ %<

?S:d_gethname:

?S: This variable conditionally defines the HAS_GETHOSTNAME symbol,
which

?S: indicates to the C program that the gethostname() routine may be

?S: used to derive the host name.

?S:.

?S:d_uname:

?S: This variable conditionally defines the HAS_UNAME symbol, which

?S: indicates to the C program that the uname() routine may be

?S: used to derive the host name.

?S:.

?S:d_phostname:

?S: This variable conditionally defines the PHOSTNAME symbol, which

?S: contains the shell command which, when fed to popen(), may be

?S: used to derive the host name.

?S:.

?S:aphostname:

?S: This variable contains the command which can be used to compute the

?S: host name. The command is fully qualified by its absolute path, to make

?S: it safe when used by a process with super-user privileges.

?S:.

?C:HAS_GETHOSTNAME (GETHOSTNAME):

?C: This symbol, if defined, indicates that the C program may use the

?C: gethostname() routine to derive the host name. See also HAS_UNAME

?C: and PHOSTNAME.

?C:.

?C:HAS_UNAME (UNAME):

?C: This symbol, if defined, indicates that the C program may

use the

?C: uname() routine to derive the host name. See also HAS_GETHOSTNAME

?C: and PHOSTNAME.

?C:.

?C:PHOSTNAME:

?C: This symbol, if defined, indicates that the C program may use the
 ?C: contents of PHOSTNAME as a command to feed to the popen() routine
 ?C: to derive the host name. See also HAS_GETHOSTNAME and HAS_UNAME.
 ?C: Note that the command uses a fully qualified path, so that it is safe
 ?C: even if used by a process with super-user privileges.
 ?C:.
 ?H:#\$d_gethname HAS_GETHOSTNAME /**/
 ?H:#\$d_uname HAS_UNAME /**/
 ?H:#\$d_phostname PHOSTNAME "\$aphostname" /* How to get the host name */
 ?H:.
 ?T:file val call
 ?LINT:change i_whoami
 : see how we will look up host name
 echo " "
 if false; then
 : dummy stub to allow use of elif
 @if HAS_GETHOSTNAME
 elif set gethostname val -f d_gethname; eval \$csym; \$val; then
 echo 'gethostname() found.' >&4
 d_gethname="\$define"
 call=gethostname
 @end
 @if HAS_UNAME
 elif set uname val -f d_uname; eval \$csym; \$val; then
 if ./xenix; then
 \$cat <<'EOM'
 uname()
 was found, but you're running xenix, and older versions of xenix
 have a broken uname(). If you don't really know whether your xenix is old
 enough to have a broken system call, use the default answer.

EOM

```
dflt=y
case "$d_uname" in
"$define") dflt=n;;
esac
rp='Is your uname() broken?'
./myread
case "$ans" in
n*) d_uname="$define"; call=uname;;
esac
else
echo 'uname() found.' >&4
d_uname="$define"
call=uname
fi
@end
fi
```

```

case "$d_gethname" in
") d_gethname="$undef";;
esac
case "$d_uname" in
") d_uname="$undef";;
esac
@if PHOSTNAME || MYHOSTNAME
case "$d_uname$d_gethname" in
*define*)
dflt=n
cat <<EOM

```

Every now and then someone has a \$call() that lies about the hostname but can't be fixed for political or economic reasons. If you wish, I can

```

@if MYHOSTNAME && PHOSTNAME
pretend $call() isn't there and maybe compile in the hostname or
compute it from the '$phostname' command at run-time.
@elsif MYHOSTNAME
pretend $call() isn't there and maybe compile
in the hostname.
@elsif PHOSTNAME
pretend $call() isn't there and maybe compute hostname at run-time
thanks to the '$phostname' command.
@elsif WHOAMI
get the hostname from whomai.h (provided you have one).
@else
simply ignore your host name and use something like "noname" instead.
@end

```

```

EOM
rp="Shall I ignore $call() from now on?"
./myread
case "$ans" in
y*) d_uname="$undef" d_gethname="$undef"; $echo $n "Okay...$c";;
esac;;
esac
@end
@if PHOSTNAME || aphostname
?X: Compute the full path name for the command
case "$phostname" in
") aphostname="";;
*) case "$aphostname" in
/*) ;;
*) set X $phostname
shift
file=$1
shift
file=`./loc $file $file $pth`

```

```

aphostname=`echo $file $*`
;;
esac
;;
esac
@end
@if PHOSTNAME && MYHOSTNAME
case "$d_uname$d_gethname" in
*define*) ;;
*)
case "$phostname" in
") ;;
*)
$cat <<EOT

```

There is no gethostname() or uname() on this system. You have two possibilities at this point:

- 1) You can have your host name (\$myhostname) compiled into \$package, which lets \$package start up faster, but makes your binaries non-portable, or
- 2) you can have \$package use a

```
popen("$aphostname","r")
```

which will start slower but be more portable.

```
@ if WHOAMI
```

Option 1 will give you the option of using whoami.h if you have one.

```
@ end
```

If you want option 2 but with a different command, you can edit config.sh at the end of this shell script.

```
EOT
```

```

case "$d_phostname" in
"$define") dflt=n;;
"$undef") dflt=y;;
")
case "$d_portable" in
"$define") dflt=n ;;
*) dflt=y ;;
esac;;
esac
rp="Do you want your host name compiled in?"
./myread
case "$ans" in
n*) d_phostname="$define" ;;
*) aphostname=""; d_phostname="$undef";;

```

```

esac;;
esac
case "$phostname" in
")
@ if WHOAMI
case "$i_whoami" in
"$define")
dflt=y
$cat <<EOM

```

No hostname function--you can either use the whoami.h file, which has this line:

```
`grep sysname $usrinc/whoami.h`
```

or you can have the name we came up with earlier
(\$myhostname) hardwired in.

```

EOM
rp="Use whoami.h to get hostname?"
./myread
case "$ans" in
n*) i_whoami="$undef";;
esac
;;
"$undef")
$cat <<EOM

```

No hostname function and no whoami.h -- hardwiring "\$myhostname".

```

EOM
;;
esac;;
@ else
echo 'No hostname function -- hardwiring "$myhostname".' >&4;;
@ end
esac;;
esac
@elsif PHOSTNAME
case "$d_uname$d_gethname" in
*define*);;
*)
case "$phostname" in
")
@ if WHOAMI
case "$i_whoami" in
"$define")
$cat <<EOM

```

No hostname function--we'll use the whoami.h file, which has this line:

```
`grep sysname $usrinc/whoami.h`
```

```

EOM
;;
*) echo "There will be no way for $package to get your hostname." >&4;;
esac;;
@ else
echo "There will be no way for $package to get your hostname." >&4;;
@ end
*)
echo "I'll use 'popen('"'$aphostname"', "r")' to get your hostname." >&4
;;
esac;;
esac
@elsif MYHOSTNAME
case "$d_uname$d_gethname" in
*define*) ;;
*)
@ if WHOAMI
case "$i_whoami" in
"$define")
dflt=y
$cat
<<EOM

```

No hostname function--you can either use the whoami.h file, which has this line:

```
`grep sysname $usrinc/whoami.h`
```

or you can have the name we came up with earlier (\$myhostname) hardwired in.

```

EOM
rp="Use whoami.h to get hostname?"
. ./myread
case "$ans" in
n*) i_whoami="$undef";;
esac
;;
"$undef")
echo 'No whoami.h--hardwiring "$myhostname".' >&4;;
esac;;
@ else
echo 'Hardwiring "$myhostname".' >&4;;
@ end
esac
@end
case "$d_phostname" in
") d_phostname="$undef";;
esac

```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/d_gethname.U
```

No license file was found, but licenses were detected in source scan.

```
case $CONFIG in
")
if test -f config.sh; then TOP=.;
elif test -f ../config.sh; then TOP=..;
elif test -f ../../config.sh; then TOP=../../;
elif test -f ../../../config.sh; then TOP=../../../;
elif test -f ../../../../config.sh; then TOP=../../../../;
else
echo "Can't find config.sh."; exit 1
fi
. $TOP/config.sh
;;
esac
case "$0" in
*/*) cd `expr X$0 : 'X\(.*/\)^'` ;;
esac
echo "Extracting makedir (with variable substitutions)"
$spitshell >makedir <<!GROK!THIS!
$startsh
# $Id: makedir.sh,v 3.0.1.1 1994/01/24 14:00:08 ram Exp ram $
#
# Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
#
# You may redistribute only under the terms of the Artistic Licence,
# as specified in the README file that comes with the distribution.
# You may reuse parts of this distribution only within the terms of
# that same Artistic Licence; a copy of which may be found at the root
# of the source tree for dist 4.0.
#
# Original
Author: Larry Wall <lwall@netlabs.com>
#
# $Log: makedir.sh,v $
# Revision 3.0.1.1 1994/01/24 14:00:08 ram
# patch16: changed top ln-style config.sh lookup into test-style one
#
# Revision 3.0 1993/08/18 12:04:38 ram
# Baseline for dist 3.0 netwide release.
#

export PATH || (echo "OOPS, this isn't sh. Desperation time. I will feed myself to sh."; sh $0; kill $$)

case $# in
```

```

0)
  $echo "mkdir pathname filenameflag"
  exit 1
  ;;
esac

```

: guarantee one slash before 1st component

```

case \ $1 in
/*) ;;
*) set .^ $1 \ $2 ;;
esac

```

: strip last component if it is to be a filename

```

case X $2 in
X1) set \ $echo \ $1 | $sed 's:(.*)/[^\]*\ $:1:' ;;
*) set \ $1 ;;
esac

```

: return reasonable status if nothing to be created

```

if $test -d "\ $1" ; then
  exit 0
fi

```

list="

while true ; do

```

  case \ $1 in
  /*)
list="\ $1 \ $list"
set \ echo \ $1 | $sed 's:(.*)/:1 :'\`
  ;;
  *)
break
  ;;
  esac
done

```

set \ \$list

for dir do

```

  $mkdir \ $dir >/dev/null 2>&1
done
!GROK!THIS!
$unicefix
  mkdir
chmod +x mkdir

```

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-

debian-perl-5.26.1/dist/lib/makedir.SH

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: d_havetlib.U 1 2006-08-24 12:32:52Z rmanfredi $
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: $Log: d_havetlib.U,v $
?RCS: Revision 3.0.1.2 1997/02/28 15:36:31 ram
?RCS: patch61: replaced .a with $_a all over the place
?RCS: patch61: likewise for .o replaced by $_o
?RCS:
?RCS: Revision 3.0.1.1 1994/05/06 14:44:06 ram
?RCS: patch23: added AIX support to accept shared lib stub as termlib (WED)
?RCS:
?RCS: Revision 3.0 1993/08/18 12:06:19 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:d_havetlib termlib: cat contains Myread Loc
Filexp Oldconfig libpth \
test uname _a _o
?MAKE: -pick add $@ %<
?S:d_havetlib:
?S: This variable conditionally defines the HAS_TERMLIB symbol, which
?S: indicates to the C program that termlib-style routines are available.
?S:.
?S:termlib:
?S: This variable contains the argument to pass to the loader to get
?S: termlib-style routines. It is up to the Makefile.SH to make sure
?S: the value gets to the right command. Note that on many systems the
?S: termlib routines are emulated by the curses or terminfo library.
?S:.
?C:HAS_TERMLIB (HAVETERMLIB):
?C: This symbol, when defined, indicates that termlib-style routines
?C: are available. There is nothing to include.
?C:.
?H:#$d_havetlib HAS_TERMLIB /**/
?H:.
?T:xxx
: where do we get termlib routines from
echo " "
xxx=`./loc libcurses$_a x $libpth`
```

```

case "$xxx" in
/*)
ar t $xxx >grimble
if $contains tputs$_o grimble >/dev/null 2>&1; then
termlib='-lcurses'
d_havetlib="$define"
echo "Terminfo library found." >&4
elif $test "x`$uname
2>/dev/null`" = xAIX; then
# Ok, do the AIX shr.o fun thing
/usr/ccs/bin/nm -en $xxx 2>/dev/null >grimble
if $contains '^tputs.*|extern|' grimble >/dev/null 2>&1; then
termlib='-lcurses'
d_havetlib="$define"
echo "AIX Terminfo library found." >&4
else
xxx=x
fi
else
xxx=x
fi
rm -f grimble
;;
esac
case "$xxx" in
x)
xxx=`./loc libtermcap$_a x $libpth`
case "$xxx" in
/usr/lib*/lib*)
termlib='-ltermcap'
d_havetlib="$define"
echo "Termcap library found." >&4
;;
/*)
termlib="$xxx"
d_havetlib="$define"
echo "Termcap library found." >&4
;;
*)
xxx=`./loc libtermcap$_a x $libpth`
case "$xxx" in
/usr/lib*/lib*)
termlib='-ltermcap'
d_havetlib="$define"
echo "Termcap library found." >&4
;;
/*)
termlib="$xxx"

```

```

d_havetlib="$define"
echo "Termcap library found." >&4
;;
*)
case "$termlib" in
")
dflt=y
rp="Your system appears to NOT have termlib-style routines. Is this true?"
./myread
case "$ans"
in
n*[f*]) d_havetlib="$define"
$cat <<'EOM'

```

Then where are the termlib-style routines kept? Specify either -llibname or a full pathname (~name ok).

EOM

```

dflt="
rp='Specify termlib path:'
./myread
termlib=`./filexp $ans`
;;
*)
d_havetlib="$undef"
termlib="
echo "You will have to play around with term.c then." >&4
;;
esac
echo " ";;
*) echo "You said termlib was $termlib before." >&4;;
esac;;
esac;;
esac
esac

```

Found in path(s):

```

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/d_havetlib.U

```

No license file was found, but licenses were detected in source scan.

```

?RCS: $Id: d_memcmp.U 1 2006-08-24 12:32:52Z rmanfredi $
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root

```

?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: \$Log: d_memcmp.U,v \$
?RCS: Revision 3.0.1.1 1993/09/13 16:02:35 ram
?RCS: patch10: removed text recommending bcmp over memcmp (WAD)
?RCS:
?RCS: Revision 3.0 1993/08/18 12:06:33 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:d_memcmp: Inlibc
?MAKE: -pick add \$@ %<
?S:d_memcmp:
?S: This variable conditionally defines the HAS_MEMCMP symbol, which
?S: indicates to the C program that the memcmp() routine is available
?S: to compare blocks of
memory.
?S:.
?C:HAS_MEMCMP (MEMCMP):
?C: This symbol, if defined, indicates that the memcmp routine is available
?C: to compare blocks of memory.
?C:.
?H:#\$d_memcmp HAS_MEMCMP /**/
?H:.
?LINT:set d_memcmp
: see if memcmp exists
set memcmp d_memcmp
eval \$inlibc

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/d_memcmp.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_strxfrm.U 1 2006-08-24 12:32:52Z rmanfredi \$
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: Original Author: Andy Dougherty <doughera@lafcol.lafayette.edu>
?RCS:
?RCS: \$Log: d_strxfrm.U,v \$
?RCS: Revision 3.0.1.1 1994/08/29 16:12:04 ram
?RCS: patch32: created by ADO

?RCS:
?MAKE:d_strxfrm: Inlibc
?MAKE: -pick add \$@ %<
?S:d_strxfrm:
?S: This variable conditionally defines HAS_STRXFRM if strxfrm() is
?S: available to transform strings.
?S:.
?C:HAS_STRXFRM:
?C: This symbol, if defined, indicates that the strxfrm() routine is
?C: available to transform
strings.
?C:.
?H:#\$d_strxfrm HAS_STRXFRM /**/
?H:.
?LINT:set d_strxfrm
: see if strxfrm exists
set strxfrm d_strxfrm
eval \$inlibc

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/d_strxfrm.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_fgetpos.U 1 2006-08-24 12:32:52Z rmanfredi \$
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: \$Log: d_fgetpos.U,v \$
?RCS: Revision 3.0.1.1 1994/06/20 06:57:33 ram
?RCS: patch30: created
?RCS:
?MAKE:d_fgetpos: Inlibc
?MAKE: -pick add \$@ %<
?S:d_fgetpos:
?S: This variable conditionally defines HAS_FGETPOS if fgetpos() is
?S: available to get the file position indicator.
?S:.
?C:HAS_FGETPOS:
?C: This symbol, if defined, indicates that the fgetpos routine is
?C: available to get the file position indicator, similar to ftell().
?C:.

```
?H:#$d_fgetpos
HAS_FGETPOS /**/
?H:
?LINT:set d_fgetpos
: see if fgetpos exists
set fgetpos d_fgetpos
eval $inlibc
```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/d_fgetpos.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id$
?RCS:
?RCS: Copyright (c) 1996, Andy Dougherty
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: $Log: Unix.U,v $
?RCS: Revision 3.0.1.1 1997/02/28 15:20:06 ram
?RCS: patch61: created
?RCS:
?X:
?X: The purpose of this unit is to define things that are common across all
?X: known UNIX platforms. If Configure is ported/used on a non-UNIX
?X: environment, then some of the following variables can be redefined in hint
?X: files.
?X:
?MAKE:Unix _a _o firstmakefile archobjs: Oldconfig
?MAKE: -pick add $@ %<
?S:_a (lib_ext):
?S: This variable defines the extension
used for ordinary libraries.
?S: For unix, it is 'a'. The '.' is included. Other possible
?S: values include '.lib'.
?S:.
?S:_o (obj_ext):
?S: This variable defines the extension used for object files.
?S: For unix, it is 'o'. The '.' is included. Other possible
?S: values include '.obj'.
?S:.
?S:firstmakefile:
```

?S: This variable defines the first file searched by make. On unix,
?S: it is makefile (then Makefile). On case-insensitive systems,
?S: it might be something else. This is only used to deal with
?S: convoluted make depend tricks.

?S:.

?S:archobjs:

?S: This variable defines any additional objects that must be linked
?S: in with the program on this architecture. On unix, it is usually
?S: empty. It is typically used to include emulations of unix calls
?S: or other facilities. For perl on OS/2, for example, this would
?S: include os2/os2.obj.

?S:.

?INIT:: Extra object files, if any, needed on this platform.

?INIT:archobjs="

: Define several unixisms.

: Hints files

or command line option can be used to override them.

```
case "$_a" in
```

```
) _a='.a';;
```

```
esac
```

```
case "$_o" in
```

```
) _o='.o';;
```

```
esac
```

@if firstmakefile

: Which makefile gets called first. This is used by make depend.

```
case "$firstmakefile" in
```

```
) firstmakefile='makefile';;
```

```
esac
```

@end

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/Unix.U
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_setreuid.U 1 2006-08-24 12:32:52Z rmanfredi \$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic Licence,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic Licence; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: d_setreuid.U,v \$

?RCS: Revision 3.0 1993/08/18 12:07:13 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?MAKE:d_setreuid d_setresuid: Inlibc

?MAKE: -pick add \$@ %<

?S:d_setreuid:

?S: This variable conditionally defines HAS_SETREUID if setreuid() is

?S: available to change the real and effective uid of the current

?S: process.

?S:.

?S:d_setresuid:

?S: This variable conditionally defines HAS_SETREUID if setresuid() is

?S: available to change

the real, effective and saved uid of the current

?S: process.

?S:.

?C:HAS_SETREUID (SETREUID):

?C: This symbol, if defined, indicates that the setreuid routine is

?C: available to change the real and effective uid of the current

?C: process.

?C:.

?C:HAS_SETRESUID (SETRESUID):

?C: This symbol, if defined, indicates that the setresuid routine is

?C: available to change the real, effective and saved uid of the current

?C: process.

?C:.

?H:#\$d_setreuid HAS_SETREUID /**/

?H:#\$d_setresuid HAS_SETRESUID /**/

?H:.

?LINT:set d_setreuid d_setresuid

: see if setreuid exists

set setreuid d_setreuid

eval \$inlibc

set setresuid d_setresuid

eval \$inlibc

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/d_setreuid.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: i_pwd.U,v 3.0.1.2 1995/07/25 14:10:57 ram Exp \$

?RCS:

?RCS: Copyright (c) 1991-1993, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 3.0.
?RCS:
?RCS: \$Log: i_pwd.U,v \$
?RCS: Revision 3.0.1.2 1995/07/25 14:10:57 ram
?RCS: patch56: use setvar so hint file values can override our guesses (ADO)
?RCS:
?RCS: Revision 3.0.1.1 1994/05/06 15:03:27 ram
?RCS: patch23: had forgotten cppminus in cppstd in test (ADO)
?RCS:
?RCS: Revision 3.0 1993/08/18 12:08:25 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?X:
?X: This unit checks whether there is a pwd system or not
?X:
?MAKE:i_pwd d_pwquota d_pwage d_pwchange
d_pwclass d_pwexpire \
d_pwgecos d_pwpasswd d_pwcomment: \
contains rm cppstd in cppflags cppminus Inhdr Findhdr Setvar
?MAKE: -pick add \$@ %<
?S:i_pwd:
?S: This variable conditionally defines I_PWD, which indicates
?S: to the C program that it should include <pwd.h>.
?S:.
?S:d_pwquota:
?S: This variable conditionally defines PWQUOTA, which indicates
?S: that struct passwd contains pw_quota.
?S:.
?S:d_pwage:
?S: This variable conditionally defines PWAGE, which indicates
?S: that struct passwd contains pw_age.
?S:.
?S:d_pwchange:
?S: This variable conditionally defines PWCHANGE, which indicates
?S: that struct passwd contains pw_change.
?S:.
?S:d_pwclass:
?S: This variable conditionally defines PWCLASS, which indicates
?S: that struct passwd contains pw_class.
?S:.
?S:d_pwexpire:
?S: This variable conditionally defines PWEXPIRE, which indicates
?S: that struct passwd contains pw_expire.
?S:.
?S:d_pwcomment:
?S: This variable conditionally defines PWCOMMENT, which indicates
?S: that

struct passwd contains pw_comment.

?S:

?S:d_pwgecos:

?S: This variable conditionally defines PWGECOS, which indicates

?S: that struct passwd contains pw_gecos.

?S:

?S:d_pwpasswd:

?S: This variable conditionally defines PWPASSWD, which indicates

?S: that struct passwd contains pw_passwd.

?S:

?C:I_PWD:

?C: This symbol, if defined, indicates to the C program that it should

?C: include <pwd.h>.

?C:

?C:PWQUOTA:

?C: This symbol, if defined, indicates to the C program that struct passwd

?C: contains pw_quota.

?C:

?C:PWAGE:

?C: This symbol, if defined, indicates to the C program that struct passwd

?C: contains pw_age.

?C:

?C:PWCHANGE:

?C: This symbol, if defined, indicates to the C program that struct passwd

?C: contains pw_change.

?C:

?C:PWCLASS:

?C: This symbol, if defined, indicates to the C program that struct passwd

?C: contains pw_class.

?C:

?C:PWEXPIRE:

?C: This symbol, if defined, indicates to the C program that struct passwd

?C: contains pw_expire.

?C:

?C:PWCOMMENT:

?C: This

symbol, if defined, indicates to the C program that struct passwd

?C: contains pw_comment.

?C:

?C:PWGECOS:

?C: This symbol, if defined, indicates to the C program that struct passwd

?C: contains pw_gecos.

?C:

?C:PWPASSWD:

?C: This symbol, if defined, indicates to the C program that struct passwd

?C: contains pw_passwd.

?C:

?H:#\$_pwd I_PWD /**/

```

?H:#$d_pwquota PWQUOTA /**/
?H:#$d_pwage PWAGE /**/
?H:#$d_pwchange PWCHANGE /**/
?H:#$d_pwclass PWCLASS /**/
?H:#$d_pwexpire PWEXPIRE /**/
?H:#$d_pwcomment PWCOMMENT /**/
?H:#$d_pwgecos PWGECOS /**/
?H:#$d_pwpasswd PWPASSWD /**/
?H:
?LINT: set i_pwd d_pwquota d_pwage d_pwchange d_pwclass d_pwexpire d_pwcomment
?LINT: set d_pwgecos d_pwpasswd
?T:xxx
: see if this is a pwd.h system
set pwd.h i_pwd
eval $inhdr

case "$i_pwd" in
$define)
xxx=`./findhdr pwd.h`
Scppstdin Scppflags Scppminus < $xxx >$$.h

if $contains 'pw_quota' $$h >/dev/null 2>&1; then
val="$define"
else
val="$undef"
fi
set d_pwquota
eval $setvar

if $contains 'pw_age'
$$h >/dev/null 2>&1; then
val="$define"
else
val="$undef"
fi
set d_pwage
eval $setvar

if $contains 'pw_change' $$h >/dev/null 2>&1; then
val="$define"
else
val="$undef"
fi
set d_pwchange
eval $setvar

if $contains 'pw_class' $$h >/dev/null 2>&1; then
val="$define"

```

```

else
  val="$undef"
fi
set d_pwclass
eval $setvar

if $contains 'pw_expire' $$h >/dev/null 2>&1; then
  val="$define"
else
  val="$undef"
fi
set d_pwexpire
eval $setvar

if $contains 'pw_comment' $$h >/dev/null 2>&1; then
  val="$define"
else
  val="$undef"
fi
set d_pwcomment
eval $setvar

if $contains 'pw_gecos' $$h >/dev/null 2>&1; then
  val="$define"
else
  val="$undef"
fi
set d_pwgecos
eval $setvar

if $contains 'pw_passwd' $$h >/dev/null 2>&1; then
  val="$define"
else
  val="$undef"
fi
set d_pwpasswd
eval $setvar

$rm -f $$h
;;
*)
val="$undef";
set d_pwquota; eval $setvar
set d_pwage; eval $setvar
set d_pwchange; eval $setvar
set d_pwclass; eval $setvar
set

```

```
d_pwexpire; eval $setvar
set d_pwcomment; eval $setvar
set d_pwgecos; eval $setvar
set d_pwpasswd; eval $setvar
;;
esac
```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/modified/i_pwd.U
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: cppstdin.U,v \$

?RCS: Revision 3.0.1.4 1994/10/29 16:08:34 ram

?RCS: patch36: added ?F: line for metalint file checking

?RCS:

?RCS: Revision 3.0.1.3 1994/01/24 14:05:38 ram

?RCS: patch16: comment for CPPLAST was missing

?RCS:

?RCS: Revision 3.0.1.2 1993/12/15 08:18:58 ram

?RCS: patch15: new variables cpprun and cpplast, guaranteed wrapper-free

?RCS: patch15: cppstdin now tries to use cc, even at the cost of a wrapper

?RCS:

?RCS: Revision 3.0.1.1 1993/08/25 14:00:53 ram

?RCS: patch6:

remove wrapper when not actually used

?RCS:

?RCS: Revision 3.0 1993/08/18 12:05:38 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?MAKE:cppstdin cppminus cpprun cpplast: contains test Myread Oldconfig Loc \

cpp +cc rm hint osname gccversion startsh eunicefix

?MAKE: -pick add \$@ %<

?S:cppstdin:

?S: This variable contains the command which will invoke the C

?S: preprocessor on standard input and put the output to stdout.

?S: It is primarily used by other Configure units that ask about

?S: preprocessor symbols.

?S:.

?S:cppminus:

?S: This variable contains the second part of the string which will invoke

?S: the C preprocessor on the standard input and produce to standard

?S: output. This variable will have the value "-" if cppstdin needs

?S: a minus to specify standard input, otherwise the value is "".

?S:.

?S:cpprun:

?S: This variable contains the command which will invoke a C preprocessor

?S: on standard input and put the output to stdout. It is guaranteed not

?S: to be a wrapper

and may be a null string if no preprocessor can be

?S: made directly available. This preprocessor might be different from the

?S: one used by the C compiler. Don't forget to append cpplast after the

?S: preprocessor options.

?S:.

?S:cpplast:

?S: This variable has the same functionality as cppminus, only it applies to

?S: cpprun and not cppstdin.

?S:.

?C:CPPSTDIN:

?C: This symbol contains the first part of the string which will invoke

?C: the C preprocessor on the standard input and produce to standard

?C: output. Typical value of "cc -E" or "/lib/cpp", but it can also

?C: call a wrapper. See CPPRUN.

?C:.

?C:CPPMINUS:

?C: This symbol contains the second part of the string which will invoke

?C: the C preprocessor on the standard input and produce to standard

?C: output. This symbol will have the value "-" if CPPSTDIN needs a minus

?C: to specify standard input, otherwise the value is "".

?C:.

?C:CPPRUN:

?C: This symbol contains the string which will invoke a C preprocessor on

?C: the

standard input and produce to standard output. It needs to end

?C: with CPPLAST, after all other preprocessor flags have been specified.

?C: The main difference with CPPSTDIN is that this program will never be a

?C: pointer to a shell wrapper, i.e. it will be empty if no preprocessor is

?C: available directly to the user. Note that it may well be different from

?C: the preprocessor used to compile the C program.

?C:.

?C:CPPLAST:

?C: This symbol is intended to be used along with CPPRUN in the same manner

?C: symbol CPPMINUS is used with CPPSTDIN. It contains either "-" or "".

?C:.

?H:#define CPPSTDIN "\$cppstdin"

?H:#define CPPMINUS "\$cppminus"

```

?H:#define CPPRUN "$cpprun"
?H:#define CPPLAST "$cpplast"
?H:.
?F:cppstdin !testcpp.out !testcpp.c
?T:wrapper x_cpp x_minus ok
: see how we invoke the C preprocessor
echo " "
echo "Now, how can we feed standard input to your C preprocessor..." >&4
cat <<'EOT' >testcpp.c
#define ABC abc
#define XYZ xyz
ABC.XYZ
EOT
cd ..
if $test ! -f cppstdin;
then
echo "$startsh" >cppstdin
if $test "X$osname" = "Xaix" -a "X$gccversion" = X; then
?X: AIX cc -E doesn't show the absolute headerfile
?X: locations but we'll cheat by using the -M flag.
echo 'cat >.$$.c; rm -f .$$.u; ""$cc"" ${1+"$@"} -M -c .$$.c 2>/dev/null; \
test -s .$$.u && \
awk """"$2 ~ /\.h$/ { print "# 0 \\""$2"\\""" }"""" .$$.u; \
rm -f .$$.o .$$.u; ""$cc"" -E ${1+"$@"} .$$.c; rm .$$.c' >> cppstdin
else
echo 'cat >.$$.c; ""$cc"" -E ${1+"$@"} .$$.c; rm .$$.c' >>cppstdin
fi; else
echo "Keeping your $hint cppstdin wrapper."
fi
chmod 755 cppstdin
$eunicefix cppstdin
wrapper=`pwd`/cppstdin
ok='false'
cd UU

?X:
?X: We'll run the cpp tests again if we don't have any valid C preprocessor
?X: yet or don't know how to proceed without a wrapper (in which case cpprun
?X: is empty and that's really annoying...)
?X:
if $test "X$cppstdin" != "X" && \
$cppstdin $cppminus <testcpp.c >testcpp.out 2>&1 && \
$contains 'abc.*xyz' testcpp.out >/dev/null 2>&1
then
echo "You used to use
$cppstdin $cppminus so we'll use that again."
case "$cpprun" in
") echo "But let's see if we can live without a wrapper..." ;;

```

```

*)
if $cpprun $cpplast <testcpp.c >testcpp.out 2>&1 && \
  $contains 'abc.*xyz' testcpp.out >/dev/null 2>&1
then
  echo "(And we'll use $cpprun $cpplast to preprocess directly.)"
  ok='true'
else
  echo "(However, $cpprun $cpplast does not work, let's see...)"
fi
;;
esac
else
case "$cppstdin" in
  *)
    echo "Good old $cppstdin $cppminus does not seem to be of any help..."
    ;;
  esac
fi

```

```

if $ok; then
  : nothing
elif echo 'Maybe ""$cc" -E" will work...'; \
  $cc -E <testcpp.c >testcpp.out 2>&1; \
  $contains 'abc.*xyz' testcpp.out >/dev/null 2>&1 ; then
  echo "Yup, it does."
  x_cpp="$cc -E"
  x_minus="";
elif echo 'Nope...maybe ""$cc" -E -" will work...'; \
  $cc -E - <testcpp.c >testcpp.out 2>&1; \
  $contains 'abc.*xyz' testcpp.out >/dev/null 2>&1 ; then
  echo "Yup, it does."
  x_cpp="$cc -E"
  x_minus='-';
elif echo 'Nope...maybe ""$cc"
-P" will work...'; \
  $cc -P <testcpp.c >testcpp.out 2>&1; \
  $contains 'abc.*xyz' testcpp.out >/dev/null 2>&1 ; then
  echo "Yipee, that works!"
  x_cpp="$cc -P"
  x_minus="";
elif echo 'Nope...maybe ""$cc" -P -" will work...'; \
  $cc -P - <testcpp.c >testcpp.out 2>&1; \
  $contains 'abc.*xyz' testcpp.out >/dev/null 2>&1 ; then
  echo "At long last!"
  x_cpp="$cc -P"
  x_minus='-';
elif echo 'No such luck, maybe "$cpp" will work...'; \

```

```

$cpp <testcpp.c >testcpp.out 2>&1; \
$contains 'abc.*xyz' testcpp.out >/dev/null 2>&1 ; then
echo "It works!"
x_cpp="$cpp"
x_minus="";
elif echo 'Nixed again...maybe "$cpp' -" will work...'; \
$cpp - <testcpp.c >testcpp.out 2>&1; \
$contains 'abc.*xyz' testcpp.out >/dev/null 2>&1 ; then
echo "Hooray, it works! I was beginning to wonder."
x_cpp="$cpp"
x_minus='-';
elif echo 'Uh-uh. Time to get fancy. Trying a wrapper...'; \
$wrapper <testcpp.c >testcpp.out 2>&1; \
$contains 'abc.*xyz' testcpp.out >/dev/null 2>&1 ; then
x_cpp="$wrapper"
x_minus="
echo
"Eureka!"
else
dflt="
rp="No dice. I can't find a C preprocessor. Name one:"
./myread
x_cpp="$ans"
x_minus="
$x_cpp <testcpp.c >testcpp.out 2>&1
if $contains 'abc.*xyz' testcpp.out >/dev/null 2>&1 ; then
echo "OK, that will do." >&4
else
echo "Sorry, I can't get that to work. Go find one and rerun Configure." >&4
exit 1
fi
fi

case "$ok" in
false)
cppstdin="$x_cpp"
cppminus="$x_minus"
cpprun="$x_cpp"
cpplast="$x_minus"
?X:
?X: If /lib/cpp is used, try using a wrapper to increase our chances to have
?X: the C compiler and our $cppstdin agree on the same symbols... However,
?X: since cpprun is guaranteed not to be a wrapper, we must clear it if the
?X: only preprocessor we found was a wrapper, with all our luck...
?X:
set X $x_cpp
shift
case "$1" in

```

```

"$cpp")
echo "Perhaps can we force $cc -E using a wrapper..."
if $wrapper <testcpp.c >testcpp.out 2>&1; \
  $contains 'abc.*xyz' testcpp.out >/dev/null 2>&1
then
  echo "Yup, we can."
  cppstdin="$wrapper"
  cppminus="";
else
  echo
  "Nope, we'll have to live without it..."
fi
;;
esac
case "$cpprun" in
"$wrapper")
  cpprun="
  cpplast="
  ;;
esac
;;
esac

case "$cppstdin" in
"$wrapper"|"cppstdin") ;;
*) $rm -f $wrapper;;
esac
$rm -f testcpp.c testcpp.out

```

Found in path(s):

```

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/cppstdin.U

```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: socksizetype.U,v \$

?RCS:

?RCS: Copyright (c) 2000 Jarkko Hietaniemi

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?MAKE:socksizetype: \

Protochk Oldconfig Myread cat d_socket d_socklen_t sizetype \

usesocks i_socks i_systypes extern_C

?MAKE: -pick add \$@ %<

?S:socksizetype:

?S: This variable holds the type used for the size argument

?S: for various socket calls like accept. Usual values include

?S: socklen_t, size_t, and int.

?S:.

?C:Sock_size_t:

?C: This symbol holds the type used for the size argument of

?C: various socket calls (just the base type, not the pointer-to).

?C:.

?H:#define Sock_size_t \$socksizetype /**/

?H:.

?T:xxx yyy try

@if Sock_size_t

: check for type of the size argument to socket calls

case "\$d_socket" in

"\$define")

\$cat <<EOM

Checking to see what type is the last argument
of accept().

EOM

yyy="

case "\$d_socklen_t" in

"\$define") yyy="\$yyy socklen_t"

esac

yyy="\$yyy \$sizetype int long unsigned"

for xxx in \$yyy; do

case "\$socksizetype" in

") try="\$extern_C int accept(int, struct sockaddr *, \$xxx *);"

case "\$usesocks" in

"\$define")

if ./protochk "\$try" \$i_systypes sys/types.h \$d_socket sys/socket.h literal '#define INCLUDE_PROTOTYPES'

\$i_socks socks.h.; then

echo "Your system accepts '\$xxx *' for the last argument of accept()."

socksizetype="\$xxx"

fi

::

*) if ./protochk "\$try" \$i_systypes sys/types.h \$d_socket sys/socket.h; then

echo "Your system accepts '\$xxx *' for the last argument of accept()."

socksizetype="\$xxx"

fi

::

esac

::

esac

done

: In case none of those worked, prompt the user.

case "\$socksizetype" in

") rp='What is the type for socket address structure sizes?'

dflt='int'

. ./myread

```

socksizetype=$ans
;;
esac
;;
*) : no sockets, so pick relatively harmless default
socksizetype='int'
;;
esac
@end

```

Found

in path(s):

```

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/protos/socksizetype.U

```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1999, Jarkko Hietaniemi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 3.0.

?RCS:

?MAKE:d_sem_getvalue: Inlibc

?MAKE: -pick add \$@ %<

?S:d_sem_getvalue:

?S: This variable conditionally defines HAS_SEM_GETVALUE if sem_getvalue()

?S: is available to get the value of a POSIX semaphore.

?S:.

?C:HAS_SEM_GETVALUE:

?C: This symbol, if defined, indicates that the sem_getvalue system call is

?C: available to get the value of a POSIX semaphore.

?C:.

?H:#\$d_sem_getvalue HAS_SEM_GETVALUE /**/

?H:.

?LINT:set d_sem_getvalue

: see if sem_getvalue exists

set sem_getvalue d_sem_getvalue

eval \$inlibc

Found in path(s):

*

```

/opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/perl/d_sem_getvalue.U

```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: i_pwd.U,v \$

?RCS: Revision 3.0.1.2 1995/07/25 14:10:57 ram

?RCS: patch56: use setvar so hint file values can override our guesses (ADO)

?RCS:

?RCS: Revision 3.0.1.1 1994/05/06 15:03:27 ram

?RCS: patch23: had forgotten cppminus in cppstdin test (ADO)

?RCS:

?RCS: Revision 3.0 1993/08/18 12:08:25 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?X:

?X: This unit checks whether there is a pwd system or not

?X:

?MAKE:i_pwd d_pwquota d_pwage d_pwchange d_pwclass d_pwexpire d_pwcomment:

\

contains rm cppstdin cppflags cppminus Inhdr Findhdr Setvar

?MAKE: -pick add \$@ %<

?S:i_pwd:

?S: This variable conditionally defines I_PWD, which indicates

?S: to the C program that it should include <pwd.h>.

?S:.

?S:d_pwquota:

?S: This variable conditionally defines PWQUOTA, which indicates

?S: that struct passwd contains pw_quota.

?S:.

?S:d_pwage:

?S: This variable conditionally defines PWAGE, which indicates

?S: that struct passwd contains pw_age.

?S:.

?S:d_pwchange:

?S: This variable conditionally defines PWCHANGE, which indicates

?S: that struct passwd contains pw_change.

?S:.

?S:d_pwclass:

?S: This variable conditionally defines PWCLASS, which indicates

?S: that struct passwd contains pw_class.

?S:
?S:d_pwexpire:
?S: This variable conditionally defines PWEXPIRE, which indicates
?S: that struct passwd contains pw_expire.
?S:
?S:d_pwcomment:
?S: This variable conditionally defines PWCOMMENT, which indicates
?S: that struct passwd contains pw_comment.
?S:
?C:I_PWD:
?C: This symbol,
if defined, indicates to the C program that it should
?C: include <pwd.h>.
?C:
?C:PWQUOTA:
?C: This symbol, if defined, indicates to the C program that struct passwd
?C: contains pw_quota.
?C:
?C:PWAGE:
?C: This symbol, if defined, indicates to the C program that struct passwd
?C: contains pw_age.
?C:
?C:PWCHANGE:
?C: This symbol, if defined, indicates to the C program that struct passwd
?C: contains pw_change.
?C:
?C:PWCLASS:
?C: This symbol, if defined, indicates to the C program that struct passwd
?C: contains pw_class.
?C:
?C:PWEXPIRE:
?C: This symbol, if defined, indicates to the C program that struct passwd
?C: contains pw_expire.
?C:
?C:PWCOMMENT:
?C: This symbol, if defined, indicates to the C program that struct passwd
?C: contains pw_comment.
?C:
?H:#\$i_pwd I_PWD /**/
?H:#\$d_pwquota PWQUOTA /**/
?H:#\$d_pwage PWAGE /**/
?H:#\$d_pwchange PWCHANGE /**/
?H:#\$d_pwclass PWCLASS /**/
?H:#\$d_pwexpire PWEXPIRE /**/
?H:#\$d_pwcomment PWCOMMENT /**/
?H:
?LINT: set i_pwd d_pwquota

d_pwage d_pwchange d_pwclass d_pwexpire d_pwcomment

?T:xxx

: see if this is a pwd.h system

set pwd.h i_pwd

eval \$inhdr

case "\$i_pwd" in

\$define)

xxx=`./findhdr pwd.h`

\$cppstdin \$cppflags \$cppminus < \$xxx >\$\$h

if \$contains 'pw_quota' \$\$h >/dev/null 2>&1; then

val="\$define"

else

val="\$undef"

fi

set d_pwquota

eval \$setvar

if \$contains 'pw_age' \$\$h >/dev/null 2>&1; then

val="\$define"

else

val="\$undef"

fi

set d_pwage

eval \$setvar

if \$contains 'pw_change' \$\$h >/dev/null 2>&1; then

val="\$define"

else

val="\$undef"

fi

set d_pwchange

eval \$setvar

if \$contains 'pw_class' \$\$h >/dev/null 2>&1; then

val="\$define"

else

val="\$undef"

fi

set d_pwclass

eval \$setvar

if \$contains 'pw_expire' \$\$h >/dev/null 2>&1; then

val="\$define"

else

val="\$undef"

fi

```
set d_pwexpire
eval $setvar

if $contains 'pw_comment' $$h >/dev/null 2>&1; then
  val="$define"
else
  val="$undef"
fi
set d_pwcomment
eval $setvar
```

```
$rm -f $$h
;;
*)
val="$undef";
set
d_pwquota; eval $setvar
set d_pwage; eval $setvar
set d_pwchange; eval $setvar
set d_pwclass; eval $setvar
set d_pwexpire; eval $setvar
set d_pwcomment; eval $setvar
;;
esac
```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/i_pwd.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: d_pipe.U 1 2006-08-24 12:32:52Z rmanfredi $
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: Original Author: Andy Dougherty <doughera@lafcol.lafayette.edu>
?RCS:
?RCS: $Log: d_pipe.U,v $
?RCS: Revision 3.0.1.1 1994/08/29 16:11:44 ram
?RCS: patch32: created by ADO
?RCS:
?MAKE:d_pipe: Inlibc
?MAKE: -pick add $@ %<
```

?S:d_pipe:
?S: This variable conditionally defines the HAS_PIPE symbol, which
?S: indicates to the C program that the pipe() routine is available
?S: to create an inter-process channel.
?S:.
?C:HAS_PIPE :
?C: This symbol, if defined, indicates
that the pipe routine is
?C: available to create an inter-process channel.
?C:.
?H:#\$d_pipe HAS_PIPE /**/
?H:.
?LINT:set d_pipe
: see if pipe exists
set pipe d_pipe
eval \$inlibc

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/d_pipe.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$
?RCS:
?RCS: Copyright (c) 2000, Jarkko Hietaniemi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 3.0.
?RCS:
?MAKE:Devel usedevel: Myread rsrc package
?MAKE: -pick wipe \$@ %<
?T:xversion
?X: waiver of rights
?S:usedevel:
?S: This variable indicates that Perl was configured with development
?S: features enabled. This should not be done for production builds.
?S:.
?C:PERL_USE_DEVEL:
?C: This symbol, if defined, indicates that Perl was configured with
?C: -Dusedevel, to enable development features. This should not be
?C: done for production builds.
?C:.
?H:#\$usedevel PERL_USE_DEVEL /**/
?H:.
?LINT:extern versiononly

```
?LINT:extern
installusrbinperl
?LINT:change versiononly
?LINT:change installusrbinperl
: See if we are using a devel version and want that
xversion=`awk '/define[ ]+PERL_VERSION/ {print $3}' $src/patchlevel.h`
case "$usedevel" in
$define|true|[yY]*)
    usedevel="$define" ;;
*) case "$xversion" in
    *[13579])
    cat >&4 <<EOH
*** WHOA THERE!!! ***
```

This is an UNSTABLE DEVELOPMENT release.
The version of this \$package distribution is \$xversion, that is, odd,
(as opposed to even) and that signifies a development release.
If you want a maintenance release, you want an even-numbered version.

Do ***NOT*** install this into production use.
Data corruption and crashes are possible.

It is most seriously suggested that you do not continue any further
unless you want to help in developing and debugging Perl.

If you *still* want to build perl, you can answer 'y' now,
or pass -Dusedevel to Configure.

```
EOH
rp='Do you really want to continue?'
dflt='n'
. ./myread
case
"$ans" in
[yY]) echo >&4 "Okay, continuing."
    usedevel="$define" ;;
*) echo >&4 "Okay, bye."
    exit 1
    ;;
esac
;;
esac
usedevel="$undef"
;;
esac
case "$usedevel" in
$define|true|[yY]*)
case "$versiononly" in
```

```
) versiononly="$define" ;;
esac
case "$installusrbinperl" in
) installusrbinperl="$undef" ;;
esac
;;
esac
```

Found in path(s):

```
*/opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/perl/Devel.U
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: d_safebcpy.U,v \$

?RCS: Revision 3.0.1.4 1997/02/28 15:40:58 ram

?RCS: patch61: improved overlapping copy check

?RCS: patch61: comfort them if they have memmove

?RCS: patch61: added ?F: metalint hint

?RCS:

?RCS: Revision 3.0.1.3 1995/07/25 13:58:40 ram

?RCS: patch56: re-arranged compile line to include ldflags before objects

?RCS:

?RCS: Revision 3.0.1.2 1995/01/11 15:29:23 ram

?RCS: patch45: added 'ldflags' to the test compile line (ADO)

?RCS:

?RCS: Revision 3.0.1.1 1994/05/06 14:49:03

ram

?RCS: patch23: ensure string is not optimized in read-only memory (ADO)

?RCS:

?RCS: Revision 3.0 1993/08/18 12:06:58 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?MAKE:d_safebcpy: cat d_bcopy +cc +optimize +ccflags +ldflags +libs rm \

d_memmove i_memory i_stdlib i_string i_unistd Oldconfig Setvar

?MAKE: -pick add \$@ %<

?S:d_safebcpy:

?S: This variable conditionally defines the HAS_SAFE_BCOPY symbol if

?S: the bcopy() routine can do overlapping copies.

```

?S:
?C:HAS_SAFE_BCOPY (SAFE_BCOPY):
?C: This symbol, if defined, indicates that the bcopy routine is available
?C: to copy potentially overlapping memory blocks. Otherwise you should
?C: probably use memmove() or memcpy(). If neither is defined, roll your
?C: own version.
?C:
?H:#$d_safebcopy HAS_SAFE_BCOPY /**/
?H:
?F:!safebcopy
?LINT: set d_safebcopy
: can bcopy handle overlapping blocks?
?X: assume the worst
val="$undef"
case "$d_bcopy" in
"$define")
echo " "
echo "Checking to see if your bcopy() can do overlapping
copies..." >&4
$cat >foo.c <<EOCP
#$i_memory I_MEMORY
#$i_stdlib I_STDLIB
#$i_string I_STRING
#$i_unistd I_UNISTD
EOCP
$cat >>foo.c <<'EOCP'
#include <stdio.h>
#ifdef I_MEMORY
# include <memory.h>
#endif
#ifdef I_STDLIB
# include <stdlib.h>
#endif
#ifdef I_STRING
# include <string.h>
#else
# include <strings.h>
#endif
#ifdef I_UNISTD
# include <unistd.h> /* Needed for NetBSD */
#endif
int main()
{
char buf[128], abc[128];
char *b;
int len;
int off;
int align;

```

?X: Copy "abcde..." string to char abc[] so that gcc doesn't
?X: try to store the string in read-only memory.
bcopy("abcdefghijklmnopqrstuvwxy0123456789", abc, 36);

```
for (align = 7; align >= 0; align--) {  
  for (len = 36; len; len--) {  
    b = buf+align;  
    bcopy(abc, b, len);  
    for (off = 1; off <= len; off++) {  
      bcopy(b, b+off, len);  
      bcopy(b+off, b, len);  
      if (bcmp(b, abc, len))  
        exit(1);  
    }  
  }  
}  
exit(0);  
}
```

EOCP

```
if $cc $optimize $ccflags $ldflags \  
  -o safebcpy foo.c $libs >/dev/null 2>&1; then  
  if ./safebcpy  
  2>/dev/null; then  
    echo "Yes, it can."  
    val="$define"  
  else  
    echo "It can't, sorry."  
    case "$d_memmove" in  
      "$define") echo "But that's Ok since you have memmove()." ;;  
    esac  
  fi  
else  
  echo "(I can't compile the test program, so we'll assume not...)"  
  case "$d_memmove" in  
    "$define") echo "But that's Ok since you have memmove()." ;;  
  esac  
fi  
;;  
esac  
$rm -f foo.* safebcpy core  
set d_safebcpy  
eval $setvar
```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-  
debian-perl-5.26.1/dist/U/d_safebcpy.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id$
?RCS:
?RCS: Copyright (c) 2014 Jarkko Hietaniemi & H.Merijn Brand
?RCS:
?RCS: You may distribute under the terms of either the GNU General Public
?RCS: License or the Artistic License, as specified in the README file.
?RCS:
?MAKE:d_copysign: Inlibc
?MAKE: -pick add $@ %<
?S:d_copysign:
?S: This variable conditionally defines the HAS_COPYSIGN symbol, which
?S: indicates to the C program that the copysign() routine is available.
?S:.
?C:HAS_COPYSIGN:
?C: This symbol, if defined, indicates that the copysign routine is
?C: available to do the copysign function.
?C:.
?H:#$d_copysign HAS_COPYSIGN /**/
?H:.
?LINT:set d_copysign
: see if copysign exists
set copysign d_copysign
eval $inlibc
```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/perl/d_copysign.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id$
?RCS:
?RCS: Copyright (c) 1998 Jarkko Hietaniemi
?RCS:
?RCS: You may distribute under the terms of either the GNU General Public
?RCS: License or the Artistic License, as specified in the README file.
?RCS:
?MAKE:d_accessx: Inlibc
?MAKE: -pick add $@ %<
?S:d_accessx:
?S: This variable conditionally defines the HAS_ACCESSX symbol, which
?S: indicates to the C program that the accessx() routine is available.
?S:.
?C:HAS_ACCESSX :
?C: This symbol, if defined, indicates that the accessx routine is
?C: available to do extended access checks.
?C:.
```

```
?H:#$d_accessx HAS_ACCESSX /**/  
?H.:  
?LINT:set d_accessx  
: see if accessx exists  
set accessx d_accessx  
eval $inlibc
```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-  
debian-perl-5.26.1/U/acl/d_accessx.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: warnflags.U 1 2006-08-24 12:32:52Z rmanfredi $  
?RCS:  
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi  
?RCS:  
?RCS: You may redistribute only under the terms of the Artistic Licence,  
?RCS: as specified in the README file that comes with the distribution.  
?RCS: You may reuse parts of this distribution only within the terms of  
?RCS: that same Artistic Licence; a copy of which may be found at the root  
?RCS: of the source tree for dist 4.0.  
?RCS:  
?RCS: Original Author: Graham Stoney <greyham@research.canon.oz.au>  
?RCS:  
?RCS: $Log: warnflags.U,v $  
?RCS: Revision 3.0 1993/08/18 12:10:02 ram  
?RCS: Baseline for dist 3.0 netwide release.  
?RCS:  
?MAKE:warnflags: cat cc contains Myread Guess Oldconfig Findhdr  
?MAKE: -pick add $@ %<  
?S:warnflags:  
?S: This variable contains any additional C compiler flags to generate  
?S: warnings from the compiler. It is up to the Makefile to use this.  
?S:.  
: offer additional  
warning flags for compilation  
$cat <<EOH
```

You may wish to compile with extra compiler warnings enabled.
Note that doing so enhances your chance of receiving your free set of steak
knives, particularly if you find any bugs and report them.
If you don't want extra warnings, answer "none".

```
EOH  
case "$warnflags" in  
") case "$cc" in  
*gcc*)  
dflt="-Wall -Wno-comment"
```

```

if $contains 'fprintf' `./findhdr stdio.h` >/dev/null 2>&1; then
:
else
dflt="$dflt -Wno-implicit"
fi
;;
*) dflt="none";;
esac
;;
') dflt="none";;
*) dflt="$warnflags";;
esac

```

```

rp="Any $cc flags to enable warnings?"
./myread
case "$ans" in
none) warnflags=' ';;
*) warnflags="$ans";;
esac

```

Found in path(s):

```

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/warnflags.U

```

No license file was found, but licenses were detected in source scan.

```

?RCS: $Id: Whoa.U,v 3.0.1.2 1997/02/28 15:21:21 ram Exp $
?RCS:
?RCS: Copyright (c) 1991-1993, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 3.0.
?RCS:
?RCS: $Log: Whoa.U,v $
?RCS: Revision 3.0.1.2 1997/02/28 15:21:21 ram
?RCS: patch61: whoa script now starts with leading "startsh"
?RCS:
?RCS: Revision 3.0.1.1 1994/10/29 16:02:01 ram
?RCS: patch36: added ?F: line for metalint file checking
?RCS:
?RCS: Revision 3.0 1993/08/18 12:05:19 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?X:
?X: This unit produces a bit of shell code that must be dotted in in order
?X: to warn the user in case a change into a variable

```

is noticed.

?X:

?X: To use this unit, \$was must hold the old value that has changed. Upon

?X: exit, the two variables \$td and \$tu are set to the correct value for

?X: respectively defining or undefining a variable. For instance, if \$vas was

?X: \$undef, but now \$var is \$define, after calling . whoa, you should use

?X: eval "\$var=\\$tu" to finally set \$var to the correct value. See unit Inlibc.

?X:

?MAKE:Whoa: Myread startsh hint

?MAKE: -pick add \$@ %<

?F:./whoa

?T:var was td tu hintfile

: set up the script used to warn in case of inconsistency

cat <<EOS >whoa

\$startsh

EOS

cat <<'EOOSC' >>whoa

dflt=y

case "\$hint" in

recommended)

case "\$hintfile" in

) echo "The \$hint value for \\$\$var on this machine was \"\\$was\!" >&4

::

*) echo "Hmm. Based on the hints in hints/\$hintfile.sh, " >&4

echo "the \$hint value for \\$\$var on this machine was \"\\$was\!" >&4

::

esac

::

*) echo " "

echo "*** WHOA THERE!!! ***" >&4

echo " The \$hint value for \\$\$var on this machine was

\"\$was\!" >&4

::

esac

rp=" Keep the \$hint value?"

./myread

case "\$ans" in

y) td=\$was; tu=\$was;;

esac

EOOSC

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/modified/Whoa.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: Copyright (c) 2001 Jarkko Hietaniemi
?RCS:
?MAKE:run to from targetarch usecrosscompile: src awk cat grep test rm \
echo sed mkdir cp touch chmod
?MAKE: -pick add \$@ %<
?Y:TOP
?S:usecrosscompile:
?S: This variable conditionally defines the USE_CROSS_COMPILE symbol,
?S: and indicates that our package has been cross-compiled.
?S:.
?S:run:
?S: This variable contains the command used by Configure
?S: to copy and execute a cross-compiled executable in the
?S: target host. Useful and available only during
the build.
?S: Empty string " if not cross-compiling.
?S:.
?S:from:
?S: This variable contains the command used by Configure
?S: to copy files from the target host. Useful and available
?S: only during the build.
?S: The string ':' if not cross-compiling.
?S:.
?S:to:
?S: This variable contains the command used by Configure
?S: to copy to from the target host. Useful and available
?S: only during the build.
?S: The string ':' if not cross-compiling.
?S:.
?S:targetarch:
?S: If cross-compiling, this variable contains the target architecture.
?S: If not, this will be empty.
?S:.
?C:USE_CROSS_COMPILE:
?C: This symbol, if defined, indicates that the package is being
?C: cross-compiled.
?C:.
?C:CROSS_TARGET_ARCH:
?C: This symbol, if defined, indicates the target architecture
?C: the package has been cross-compiled to.

```

?C: Undefined if not a cross-compile.
?C:.
?H:?usecrosscompile:#ifndef USE_CROSS_COMPILE
?H:?usecrosscompile:#$usecrosscompile USE_CROSS_COMPILE /**/
?H:?usecrosscompile:#define
  CROSS_TARGET_ARCH "$targetarch" /**/
?H:?usecrosscompile:#endif
?H:.
?T:croak pwd exe f q i j cwd
?LINT:extern usecrosscompile
?LINT:extern cc
?LINT:extern usrinc
?LINT:change usrinc
?LINT:change ar
?LINT:change nm
?LINT:change ranlib
?LINT:extern targethost
?LINT:extern targetdir
?LINT:change targetdir
?LINT:extern targetuser
?LINT:change targetuser
?LINT:extern targetrun
?LINT:extern targetfrom
?LINT:extern targetto
?LINT:extern targetmkdir
?LINT:change targetrun
?LINT:change targetfrom
?LINT:change targetto
?LINT:change targetmkdir
?LINT:extern incpth
?LINT:extern libpth
?LINT:change incpth
?LINT:change libpth
?LINT:extern locincpth
?LINT:extern loclibpth
?LINT:change locincpth
?LINT:change loclibpth
?LINT:extern TMPDIR
: setup for possible cross-compilation
run="
to=:
from=:
usecrosscompile='undef'
targetarch="
case "$usecrosscompile" in
$define|true|[yY]*)
@if { test -d ../Cross }
?X:

```

?X: Cross-compilation is enabled when there is a 'Cross' directory found
?X: at the root
of the package. This directory must contain the following
?X: entries for defining the cross-compilation process:
?X:
?X: FIXME FIXME
?X: WE MUST DISTINGUISH BETWEEN LOCAL cross-compiling AND REMOTE ONE
?X: ACTUALLY, REMOTE COMPILATION SHOULD BE CONFIGURED INTERACTIVELY
?X: IT WILL COPY ALL THE FILES FROM THE MANIFEST DOWN TO THE REMOTE DIR...
?X: (and copy things like 'mkdep', etc...)
?X:
\$echo "Cross-compiling..."
croak="
case "\$cc" in
--gcc)
?X: A cross-compiling gcc, probably.
targetarch=`\$echo \$cc|\$sed 's/-gcc\$//`
ar=\$targetarch-ar
?X: leave out ld, choosing it is more complex
nm=\$targetarch-nm
ranlib=\$targetarch-ranlib
\$echo 'extern int foo;' > try.c
set X ` \$cc -v -E try.c 2>&1 | \
\$awk '/^#include </,/^End of search /|'\$grep '/include`
shift
if \$test \$# -gt 0; then
incpth="\$incpth \$*"
incpth="\$echo \$incpth|\$sed 's/^ //'"
echo "Guessing incpth '\$incpth'." >&4
for i in \$*; do
j="\$echo \$i|\$sed 's,/include\$,/lib,'" "
if
\$test -d \$j; then
libpth="\$libpth \$j"
fi
done
libpth="\$echo \$libpth|\$sed 's/^ //'"
echo "Guessing libpth '\$libpth'." >&4
fi
\$rm -f try.c
;;
esac
case "\$targetarch" in
") echo "Targetarch not defined." >&4; croak=y ;;
*) echo "Using targetarch \$targetarch." >&4 ;;
esac
case "\$incpth" in
") echo "Incpth not defined." >&4; croak=y ;;

```

*) echo "Using incpth '$incpth.'" >&4 ;;
esac
case "$libpth" in
") echo "Libpth not defined." >&4; croak=y ;;
*) echo "Using libpth '$libpth.'" >&4 ;;
esac
case "$usrinc" in
")
for i in $incpth; do
if $test -f $i/errno.h -a -f $i/stdio.h -a -f $i/time.h; then
usrinc=$i
echo "Guessing usrinc $usrinc." >&4
break
fi
done
case "$usrinc" in
") echo "Usrinc not defined." >&4; croak=y ;;
esac
;;
*) echo "Using usrinc $usrinc." >&4 ;;
esac
case "$targethost" in
") echo "Targethost not defined." >&4; croak=y ;;
*) echo "Using targethost $targethost."
>&4
esac
locincpth=' '
loclibpth=' '
case "$croak" in
y) echo "Cannot continue, aborting." >&4; exit 1 ;;
esac
case "$src" in
/*) run=$src/Cross/run
targetmkdir=$src/Cross/mkdir
to=$src/Cross/to
from=$src/Cross/from
;;
*) pwd=`$test -f ../Configure & cd ..; pwd`
run=$pwd/Cross/run
targetmkdir=$pwd/Cross/mkdir
to=$pwd/Cross/to
from=$pwd/Cross/from
;;
esac
case "$targetrun" in
") targetrun=ssh ;;
esac
case "$targetto" in

```

```

") targetto=scp ;;
esac
case "$targetfrom" in
") targetfrom=scp ;;
esac
run=$run-$targetrun
to=$to-$targetto
from=$from-$targetfrom
case "$targetdir" in
")
targetdir="{TMPDIR:-/tmp}"
echo "Guessing targetdir $targetdir." >&4
;;
esac
case "$targetuser" in
")
targetuser=root
echo "Guessing targetuser $targetuser." >&4
;;
esac
case "$targetfrom" in
scp) q=-q ;;
*) q="" ;;
esac
case "$targetrun" in
ssh|rsh)
$cat >$run <<EOF
#!/bin/sh
case "$1" in
-cwd)
shift
cwd=$1
shift
;;
esac
case "$cwd" in
") cwd=$targetdir ;;
esac
exe=$1
shift
if $test ! -f \${exe}.xok; then
$to \${exe}
$touch \${exe}.xok
fi
$targetrun -l $targetuser $targethost "cd $cwd && ./\${exe} \$@"
EOF
;;
*) echo "Unknown targetrun '$targetrun'" >&4

```

```

    exit 1
    ;;
esac
case "$targetmkdir" in
*/Cross/mkdir)
    $cat >$targetmkdir <<EOF
#!/bin/sh
$targetrun -l $targetuser $targethost "mkdir -p \${@"
EOF
    $chmod a+rx $targetmkdir
    ;;
*) echo "Unknown targetmkdir '$targetmkdir'" >&4
    exit 1
    ;;
esac
case "$targetto" in
scp|rcp)
    $cat >$to <<EOF
#!/bin/sh
for f in \${@"
do
case "\${f}" in
/*)
    $targetmkdir \dirname \${f}\
    $targetto $q \${f} $targetuser@$targethost:\${f} || exit 1
    ;;
*)
    $targetmkdir $targetdir/\dirname \${f}\
    $targetto $q \${f} $targetuser@$targethost:$targetdir/\${f} || exit 1
    ;;
esac
done
exit 0
EOF
    ;;
cp) $cat >$to <<EOF
#!/bin/sh
for f in \${@"
do
case "\${f}" in
/*)
    $mkdir -p $targetdir/\dirname
\${f}\
    $cp \${f} $targetdir/\${f} || exit 1
    ;;
*)
    $targetmkdir $targetdir/\dirname \${f}\
    $cp \${f} $targetdir/\${f} || exit 1

```

```

;;
esac
done
exit 0
EOF
;;
*) echo "Unknown targetto '$targetto'" >&4
    exit 1
;;
esac
case "$targetfrom" in
scp|rcp)
    $cat >$from <<EOF
#!/bin/sh
for f in @$@
do
    $rm -f $f
    Targetfrom $q $targetuser@$targethost:$targetdir/$f . || exit 1
done
exit 0
EOF
;;
cp) $cat >$from <<EOF
#!/bin/sh
for f in @$@
do
    $rm -f $f
    cp $targetdir/$f . || exit 1
done
exit 0
EOF
;;
*) echo "Unknown targetfrom '$targetfrom'" >&4
    exit 1
;;
esac
if $test ! -f $run; then
    echo "Target 'run' script '$run' not found." >&4
else
    $chmod a+rx $run
fi
if $test ! -f $to; then
    echo "Target 'to' script '$to' not found." >&4
else
    $chmod a+rx $to
fi
if $test ! -f $from; then
    echo "Target 'from' script '$from' not found." >&4

```

```

else
    $chmod a+rx $from
fi
if $test ! -f $run -o ! -f $to -o !
-f $from; then
    exit 1
fi
$cat >&4 <<EOF
Using '$run' for remote execution,
and '$from' and '$to'
for remote file transfer.
EOF
@else
echo "Cross-compilation is not supported for this package." >&4
exit 1
@end
;;
esac

```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/Cross.U
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1998 Jarkko Hietaniemi

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?MAKE:d_fseeko: Inlibc longsize

?MAKE: -pick add \$@ %<

?S:d_fseeko:

?S: This variable conditionally defines the HAS_FSEEKO symbol, which

?S: indicates to the C program that the fseeko() routine is available.

?S:.

?C:HAS_FSEEKO:

?C: This symbol, if defined, indicates that the fseeko routine is

?C: available to fseek beyond 32 bits (useful for ILP32 hosts).

?C:.

?H:#\$d_fseeko HAS_FSEEKO /**/

?H:.

?LINT:set d_fseeko

: see if fseeko exists

set fseeko d_fseeko

eval \$inlibc

case "\$longsize" in

```
8) echo "(Your long is 64 bits, so you could use fseek.)" ;;
esac
```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/perl/d_fseeko.U
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: oldarchlib.U,v \$

?RCS:

?RCS: Copyright (c) 1996-1998, Andy Dougherty

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?MAKE:d_oldarchlib oldarchlib oldarchlibexp : archname privlib \
archlib sitearch Getfile test Setvar Prefixit

?MAKE: -pick add \$@ %<

?Y:TOP

?S:d_oldarchlib:

?S: This variable conditionally defines OLDARCHLIB to hold the pathname

?S: of architecture-dependent library files for a previous

?S: version of \$package.

?S:.

?S:oldarchlib:

?S: This variable holds the name of the directory in which perl5.000

?S: and perl5.001 stored

?S: architecture-dependent public library files.

?S:.

?S:oldarchlibexp:

?S: This variable is the same as the oldarchlib variable, but is

?S: filename expanded at configuration time, for convenient use.

?S:.

?C:OLDARCHLIB:

?C: This variable, if defined, holds the
name of the directory in

?C: which the user has perl5.000 or perl5.001 architecture-dependent

?C: public library files for \$package. For the most part, these

?C: files will work with 5.002 (and later), but that is not

?C: guaranteed.

?C:.

?C:OLDARCHLIB_EXP:

?C: This symbol contains the ~name expanded version of OLDARCHLIB, to be

?C: used in programs that are not prepared to deal with ~ expansion at

?C: run-time.

?C:.

?H:#\$d_oldarchlib OLDARCHLIB "\$oldarchlib" /**/

?H:#\$d_oldarchlib OLDARCHLIB_EXP "\$oldarchlibexp" /**/

```

?H:
?LINT:set d_oldarchlib
: determine where old public architecture dependent libraries might be
case "$oldarchlib" in
") case "$privlib" in
") ;;
*) dflt="$privlib/$sarchname"
;;
esac
;;
*) dflt="$oldarchlib"
;;
esac
if $test ! -d "$dflt/auto"; then
dflt=none
fi
cat <<EOM

```

In 5.001, Perl stored architecture-dependent library files in a directory with a name such as \$privlib/\$sarchname, and this directory contained files from the standard extensions and files from any additional extensions you might have added. Starting with version 5.002, all the architecture-dependent standard extensions will go into a version-specific directory such as \$sarchlib, while locally-added extensions will go into \$sitearch.

If you wish Perl to continue to search the old architecture-dependent library for your local extensions, give the path to that directory. If you do not wish to use your old architecture-dependent library files, answer 'none'.

```

EOM
fn=dn~
rp='Directory for your old 5.001 architecture-dependent libraries?'
./getfile
oldarchlib="$ans"
oldarchlibexp="$ansexp"
case "$oldarchlib" in
'|' ) val="$undef" ;;
*) val="$define" ;;
esac
set d_oldarchlib
eval $setvar

```

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/oldarchlib.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_wcstombs.U 1 2006-08-24 12:32:52Z rmanfredi \$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic Licence,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic Licence; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: d_wcstombs.U,v \$

?RCS: Revision 3.0 1993/08/18 12:08:03 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?MAKE:d_wcstombs: Inlibc

?MAKE: -pick add \$@ %<

?S:d_wcstombs:

?S: This variable conditionally defines the HAS_WCSTOMBS symbol, which

?S: indicates to the C program that the wcstombs() routine is available

?S: to convert wide character strings to multibyte strings.

?S:.

?C:HAS_WCSTOMBS:

?C: This symbol, if defined, indicates that the wcstombs
routine is

?C: available to convert wide character strings to multibyte strings.

?C:.

?H:#\$d_wcstombs HAS_WCSTOMBS /**/

?H:.

?LINT:set d_wcstombs

: see if wcstombs exists

set wcstombs d_wcstombs

eval \$inlibc

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/d_wcstombs.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 2001 Jarkko Hietaniemi

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:
?MAKE:d_strftime: Inlibc
?MAKE: -pick add \$@ %<
?S:d_strftime:
?S: This variable conditionally defines the HAS_STRFTIME symbol, which
?S: indicates to the C program that the strftime() routine is available.
?S:.
?C:HAS_STRFTIME:
?C: This symbol, if defined, indicates that the strftime routine is
?C: available to do time formatting.
?C:.
?H:#\$d_strftime HAS_STRFTIME /**/
?H:.
?LINT:set d_strftime
: see if strftime exists
set strftime d_strftime
eval \$inlibc

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_strftime.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: inc.U 1 2006-08-24 12:32:52Z rmanfredi \$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic Licence,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic Licence; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: inc.U,v \$

?RCS: Revision 3.0 1993/08/18 12:08:51 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?MAKE:inc incexp: Loc Oldconfig Getfile usrinc

?MAKE: -pick add \$@ %<

?S:inc:

?S: This variable holds the name of the directory in which the user wants

?S: to put public header files for the package in question. It is most

?S: often a local directory such as /usr/local/include.

?S:.

?S:incexp:

?S: This is the same as the inc variable, but is filename

expanded

?S: at configuration time for convenient use in your makefiles.

```
?S:
: determine where public header files go
case "$inc" in
")
dflt=`./loc . ." /usr/local/include /usr/include/local $usrinc`
;;
*) dflt="$inc"
;;
esac
fn=d~
rp='Where do you want to put the public header files?'
./getfile
inc="$ans"
incexp="$ansexp"
```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/inc.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: d_speedopt.U 1 2006-08-24 12:32:52Z rmanfredi $
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: $Log: d_speedopt.U,v $
?RCS: Revision 3.0.1.1 1994/10/29 16:15:51 ram
?RCS: patch36: call ./Cpplib explicitly instead of relying on PATH
?RCS:
?RCS: Revision 3.0 1993/08/18 12:07:27 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:d_speedopt: Myread Cpplib Oldconfig cat models Setvar
?MAKE: -pick add $@ %<
?S:d_speedopt:
?S: This variable conditionally defines the SPEED_OVER_MEM symbol, which
?S: indicates to the C program that it can
?S: burn memory in order to save
?S: CPU time.
?S:
?C:SPEED_OVER_MEM (SPEEDOVERMEM):
?C: This symbol, if defined, indicates that the program can use more
?C: memory in order to reduce CPU time. The symbol doesn't say whether
```

?C: we are more interested in saving text space or data space.

?C:.

?H:#\$d_speedopt SPEED_OVER_MEM /**/

?H:.

?LINT:set d_speedopt

: do we want speed at the expense of memory

\$cat <<'EOM'

I can try to optimize this package for either speed or memory. If you have limited address space you may wish to optimize for memory. Otherwise you should probably optimize for speed.

EOM

```
case "$d_speedopt" in
") if ./Cppsym $smallmach; then
case "$models" in
*large*|*huge*) dflt=speed;;
*) dflt=memory;;
esac
else
dflt=speed
fi
;;
*define*) dflt=speed;;
*) dflt=memory;;
esac
rp="What to optimize for?"
./myread
case "$ans" in
mem*) val="$undef";;
*) val="$define";;
esac
set d_speedopt
eval $setvar
```

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/d_speedopt.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.
 ?RCS:
 ?RCS: \$Log: Instruct.U,v \$
 ?RCS: Revision 3.0.1.3 1997/02/28 15:02:55 ram
 ?RCS: patch61: logname / whoami sequence rewritten to use case
 ?RCS:
 ?RCS: Revision 3.0.1.2 1995/02/15 14:11:34 ram
 ?RCS: patch51: author name now appears at the end of the paragraph (WED)
 ?RCS:
 ?RCS: Revision 3.0.1.1 1995/01/11 15:12:05 ram
 ?RCS: patch45: now documents the & escape to turn -d on at the read prompt
 ?RCS:
 ?RCS: Revision 3.0 1993/08/18 12:05:04 ram
 ?RCS: Baseline for dist 3.0 netwide release.
 ?RCS:

?X:
 ?X:

This unit spew out the directions that we want everyone to read. I try to
 ?X: keep the first "pagefull" much less than a page since they don't know it
 ?X: isn't going to go shooting off the top of the screen, and we don't want
 ?X: to panic them yet.

?X:

?MAKE:Instruct: Begin Myread Configdir contains

?MAKE: -pick wipe \$@ %<

?T:user needman firsttime

: general instructions

needman=true

firsttime=true

user=`(logname) 2>/dev/null`

case "\$user" in

) user=`whoami 2>&1`;;

esac

if \$contains "^\$user\$" ../.config/instruct >/dev/null 2>&1; then

firsttime=false

echo " "

rp='Would you like to see the instructions?'

dflt=n

. ./myread

case "\$ans" in

[yY]*) ;;

*) needman=false;;

esac

fi

if \$needman; then

cat <<EOH

This installation shell script will examine your system and ask you questions to determine how the <PACKAGENAME> package should be installed. If you get

stuck on a question, you may use a ! shell escape to start a subshell or execute a command. Many of the questions will have default answers in square brackets; typing carriage return will give you the default.

On some of the questions which ask for file or directory names you are allowed to use the ~name construct to specify the login directory belonging to "name", even if you don't have a shell which knows about that. Questions where this is allowed will be marked "(~name ok)".

```
EOH
rp="
dflt='Type carriage return to continue'
. ./myread
cat <<'EOH'
```

The prompter used in this script allows you to use shell variables and backticks in your answers. You may use \$1, \$2, etc... to refer to the words in the default answer, as if the default line was a set of arguments given to a script shell. This means you may also use \$* to repeat the whole default line, so you do not have to re-type everything to add something to the default.

Everytime there is a substitution, you will have to confirm. If there is an error (e.g. an unmatched backtick), the default answer will remain unchanged and you will be prompted again.

If you are in a hurry, you may run 'Configure -d'. This will bypass nearly all the questions and use the computed defaults (or the previous answers if there was already a config.sh file). Type 'Configure -h' for a list of options. You may also start interactively and then answer '& -d' at any prompt to turn on the non-interactive behaviour for the remainder of the execution.

```
EOH
. ./myread
cat <<EOH
```

Much effort has been expended to ensure that this shell script will run on any Unix system. If despite that it blows up on yours, your best bet is to edit Configure and run it again. If you can't run Configure for some reason, you'll have to generate a config.sh file by hand. Whatever problems you have, let me (<MAINTLOC>) know how I blew it.

This installation script affects things in two ways:

- 1) it may do direct variable substitutions on some of the files included in this kit.
- 2) it builds a config.h file for inclusion in C programs. You may edit

any of these
files as the need arises after running this script.

If you make a mistake on a question, there is no easy way to back up to it currently. The easiest thing to do is to edit config.sh and rerun all the SH files. Configure will offer to let you do this before it runs the SH files.

EOH

```
?X: In case they played with the promptter...
dflt='Type carriage return to continue'
. ./myread
case "$firsttime" in
true) echo $user >>../config/instruct;;
esac
fi
```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/Instruct.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: d_syslog.U 1 2006-08-24 12:32:52Z rmanfredi $
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: $Log: d_syslog.U,v $
?RCS: Revision 3.0.1.1 1997/02/28 15:46:56 ram
?RCS: patch61: replaced .o with $_o all over the place
?RCS:
?RCS: Revision 3.0 1993/08/18 12:07:43 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:d_syslog: test Csym Setvar Findhdr
?MAKE: -pick add $@ %<
?S:d_syslog:
?S: This variable conditionally defines the HAS_SYSLOG symbol, which
?S: indicates to the C program that syslog() exists on this system.
?S:.
?C:HAS_SYSLOG
(LIBSYSLOG):
?C: This symbol, if defined, indicates that the program can rely on the
?C: system providing syslog(). Otherwise, the syslog code provided by
```

```

?C: the package should be used.
?C:.
?H:#$d_syslog HAS_SYSLOG /**/
?H:.
?LINT:set d_syslog
: see if syslog is available
echo " "
if $test `./findhdr syslog.h` && \
(set syslog val -f d_syslog; eval $csym; $val); then
echo "syslog() found." >&4
val="$define"
else
echo "syslog() not found in your C library." >&4
val="$undef"
fi
set d_syslog
eval $setvar

```

Found in path(s):

```

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/d_syslog.U

```

No license file was found, but licenses were detected in source scan.

```

?RCS: $Id: i_sfio.U 1 2006-08-24 12:32:52Z rmanfredi $
?RCS:
?RCS: Copyright (c) 1996, Andy Dougherty
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: $Log: i_sfio.U,v $
?RCS: Revision 3.0.1.1 1997/02/28 15:48:27 ram
?RCS: patch61: created
?RCS:
?MAKE:i_sfio: Inhdr Setvar
?MAKE: -pick add $@ %<
?S:i_sfio:
?S: This variable conditionally defines the I_SFIO symbol,
?S: and indicates whether a C program should include <sfio.h>.
?S:.
?C:I_SFIO:
?C: This symbol, if defined, indicates to the C program that it should
?C: include <sfio.h>.
?C:.

```

?H:#\$i_sfio I_SFIO /**/

?H:.

?LINT:set

i_sfio

: see if sfio.h is available

set sfio.h i_sfio

eval \$inhdr

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/i_sfio.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: d_csh.U,v \$

?RCS: Revision 3.0.1.1 1997/02/28 15:32:18 ram

?RCS: patch61: added full_csh to preserve the full path even when portable

?RCS:

?RCS: Revision 3.0 1993/08/18 12:05:53 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?MAKE:d_csh full_csh: csh Setvar

?MAKE: -pick add \$@ %<

?S:d_csh:

?S: This variable conditionally defines the CSH symbol, which

?S: indicates to the C program that the C-shell exists.

?S:.

?S:full_csh:

?S: This variable contains the full pathname to 'csh', whether

or

?S: not the user has specified 'portability'. This is only used

?S: in the compiled C program, and we assume that all systems which

?S: can share this executable will have the same full pathname to

?S: 'csh.'

?S:.

?C:HAS_CSH:

?C: This symbol, if defined, indicates that the C-shell exists.

?C:.

?C:CSH:

```

?C: This symbol, if defined, contains the full pathname of csh.
?C:.
?X: Previously, I just did $d_csh CSH "$full_csh", but that caused
?X: problems on VMS where the config.sh extraction program changes
?X: $undef to a real cpp undef, and they then had #undef CSH ""
?X: which the compiler didn't like. It's easy to work around this,
?X: so I did. --AD 3/1998.
?X: And we don't want to define CSH if !HAS_CSH, but we don't want
?X: those lines in config.h if they don't need CSH, so protect with ?CSH
?X: and not ?%<. --RAM, 15/02/2004
?H:?%<:#$d_csh HAS_CSH /**/
?H:?CSH:#ifdef HAS_CSH
?H:?CSH:#define CSH "$full_csh" /**/
?H:?CSH:#endif
?H:.
?LINT:set d_csh
: get csh whereabouts
case
"$csh" in
'csh') val="$undef" ;;
*) val="$define" ;;
esac
set d_csh
eval $setvar
: Respect a hint or command line value for full_csh.
case "$full_csh" in
") full_csh=$csh ;;
esac

```

Found in path(s):

```

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/d_csh.U

```

No license file was found, but licenses were detected in source scan.

```

?RCS: $Id: startperl.U,v 3.0 1993/08/18 12:09:50 ram Exp $
?RCS:
?RCS: Copyright (c) 1991-1993, Raphael Manfredi
?RCS:
?RCS: This file is included with or a derivative work of a file included
?RCS: with the metaconfig program of Raphael Manfredi's "dist" distribution.
?RCS: In accordance with clause 7 of dist's modified Artistic License:
?RCS:
?RCS: You may distribute under the terms of either the GNU General Public
?RCS: License or the Artistic License, as specified in the README file.
?RCS:
?RCS: $Log: startperl.U,v $
?RCS: Perl5 version -- I always have d_portable=define.
?RCS:

```

```

?RCS: Revision 3.0 1993/08/18 12:09:50 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:startperl: cat Myread sharpbang initialinstalllocation test \
versiononly version
?MAKE: -pick add $@ %<
?Y:TOP
?X: This is different from dist's standard startperl.U unit because
?X: we can't directly test #!/usr/local/bin/perl (or
whatever) because
?X: we haven't built and installed perl yet.
?S:startperl:
?S: This variable contains the string to put on the front of a perl
?S: script to make sure (hopefully) that it runs with perl and not some
?S: shell. Of course, that leading line must be followed by the classical
?S: perl idiom:
?S: eval 'exec perl -S $0 ${1+"$@"}'
?S: if $running_under_some_shell;
?S: to guarantee perl startup should the shell execute the script. Note
?S: that this magic incantation is not understood by csh.
?S:.
?C:STARTPERL:
?C: This variable contains the string to put in front of a perl
?C: script to make sure (one hopes) that it runs with perl and not
?C: some shell.
?C:.
?H:#define STARTPERL "$startperl" /**/
?H:.
: figure out how to guarantee perl startup
: XXX Note that this currently takes advantage of the bug that binexp ignores
: the Configure -Dinstallprefix setting, which in turn means that under
: relocatable @INC, initialinstalllocation is what binexp started as.
case
"$startperl" in
")
case "$sharpbang" in
*)
$cat <<EOH

```

I can use the #! construct to start perl on your system. This will make startup of perl scripts faster, but may cause problems if you want to share those scripts and perl is not in a standard place (\$initialinstalllocation/perl) on all your platforms. The alternative is to force a shell by starting the script with a single ':' character.

```

EOH
case "$versiononly" in
"$define") dflt="$initialinstalllocation/perl$version";

```

```

*)      dflt="$initialinstallocation/perl";;
esac
rp='What shall I put after the #! to start up perl ("none" to not use #!)?'
./myread
case "$ans" in
none) startperl=": # use perl";;
*) startperl="#!/$ans"
if $test 30 -lt `echo "$ans" | wc -c`; then
$cat >&4 <<EOM

```

WARNING: Some systems limit the #! command to 32 characters.
If you experience difficulty running Perl scripts with #!, try
installing Perl in a directory with a shorter pathname.

```

EOM
fi ;;
esac
;;
*)
startperl=": # use perl"
;;
esac
;;
esac
echo "I'll use $startperl to start perl scripts."

```

Found in path(s):

```

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/perl/startperl.U

```

No license file was found, but licenses were detected in source scan.

```

?RCS: $Id: d_setlocale_r.U,v 0RCS:
?RCS: Copyright (c) 2002,2003 Jarkko Hietaniemi
?RCS:
?RCS: You may distribute under the terms of either the GNU General Public
?RCS: License or the Artistic License, as specified in the README file.
?RCS:
?RCS: Generated by the reentr.pl from the Perl 5.8 distribution.
?RCS:
?MAKE:d_setlocale_r setlocale_r_proto: Inlibc Protochk Hasproto i_systypes \
  usethreads i_locale extern_C
?MAKE: -pick add $@ %<
?S:d_setlocale_r:
?S: This variable conditionally defines the HAS_SETLOCALE_R symbol,
?S: which indicates to the C program that the setlocale_r()
?S: routine is available.
?S:.
?S:setlocale_r_proto:

```

?S: This variable encodes the prototype of setlocale_r.

?S: It is zero if d_setlocale_r is undef, and one of the

?S: REENTRANT_PROTO_T_ABC macros of reentr.h if d_setlocale_r

?S: is defined.

?S:.

?C:HAS_SETLOCALE_R:

?C: This symbol, if defined, indicates that the setlocale_r routine

?C: is

available to setlocale re-entrantly.

?C:.

?C:SETLOCALE_R_PROTO:

?C: This symbol encodes the prototype of setlocale_r.

?C: It is zero if d_setlocale_r is undef, and one of the

?C: REENTRANT_PROTO_T_ABC macros of reentr.h if d_setlocale_r

?C: is defined.

?C:.

?H:#\$d_setlocale_r HAS_SETLOCALE_R /**/

?H:#define SETLOCALE_R_PROTO \$setlocale_r_proto /**/

?H:.

?T:try hdrs d_setlocale_r_proto

: see if setlocale_r exists

set setlocale_r d_setlocale_r

eval \$inlibc

case "\$d_setlocale_r" in

"\$define")

hdrs="\$i_systypes sys/types.h define stdio.h \$i_locale locale.h"

case "\$d_setlocale_r_proto:\$usetthreads" in

":define") d_setlocale_r_proto=define

set d_setlocale_r_proto setlocale_r \$hdrs

eval \$hasproto ;;

*) ;;

esac

case "\$d_setlocale_r_proto" in

define)

case "\$setlocale_r_proto" in

"|0) try='int setlocale_r(int, const char*, char*, int);'

./protochk "\$extern_C \$try" \$hdrs && setlocale_r_proto=I_ICBI ;;

esac

case "\$setlocale_r_proto" in

"|0) d_setlocale_r=undef

setlocale_r_proto=0

echo

"Disabling setlocale_r, cannot determine prototype." >&4 ;;

*) case "\$setlocale_r_proto" in

REENTRANT_PROTO*) ;;

*) setlocale_r_proto="REENTRANT_PROTO_\$setlocale_r_proto" ;;

esac

echo "Prototype: \$try" ;;

```

esac
;;
*) case "$usethreads" in
define) echo "setlocale_r has no prototype, not using it." >&4 ;;
esac
d_setlocale_r=undef
setlocale_r_proto=0
;;
esac
;;
*) setlocale_r_proto=0
;;
esac

```

Found in path(s):

```

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/threads/d_setlocale_r.U

```

No license file was found, but licenses were detected in source scan.

```

#####
;# Jmake rules for building libraries, programs, scripts, and data files
;# $Id: Jmake.rules 18 2006-12-27 10:35:09Z rmanfredi $

```

```

/*
* MACHINE-INDEPENDENT RULES -- DO NOT MODIFY
*/

```

```

/* $Id: Jmake.rules 18 2006-12-27 10:35:09Z rmanfredi $
*
* Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
*
* You may redistribute only under the terms of the Artistic Licence,
* as specified in the README file that comes with the distribution.
* You may reuse parts of this distribution only within the terms of
* that same Artistic Licence; a copy of which may be found at the root
* of the source tree for dist 4.0.
*

```

```

* $Log: Jmake.rules,v $
* Revision 3.0.1.7 2004/08/22 08:28:58 ram
* patch71: random cleanup
*
* Revision 3.0.1.6 1997/02/28 14:56:01 ram
* patch61: now handles USRINC for dependencies
* patch61: smarter about dependencies
computation
*
* Revision 3.0.1.5 1995/09/25 09:07:19 ram
* patch59: smarter sed command to strip /usr/include dependencies

```

```

*
* Revision 3.0.1.4 1995/07/25 13:33:59 ram
* patch56: install of script man pages can now cope with missing files
* patch56: the clobber target now removes the .config directory as well
*
* Revision 3.0.1.3 1995/03/21 08:35:28 ram
* patch52: suppressed extra argument to NormalProgramTarget call
*
* Revision 3.0.1.2 1995/01/11 14:49:55 ram
* patch45: new macros ShellScriptTargetExt and SimpleShellScriptTargetExt
* patch45: directory installation is now made via INSTALLDIR (Configure)
*
* Revision 3.0.1.1 1994/10/29 15:46:30 ram
* patch36: added RemoteDependency rule
*
* Revision 3.0 1993/08/18 12:04:14 ram
* Baseline for dist 3.0 netwide release.
*
*/

```

```

/* Please, edit only with tabstops = 4 (":set ts=4" under vi) */

```

```

/*
* AddedByConfigure:
* Gives name of the files generated by Configure that can safely
* be removed
* when a "make clobber" is issued. Not that it is useless
* to name config.h or config.sh because these are already taken care
* of by jmake.
*/

```

```

#define AddedByConfigure(files) @!\
local_clobber:: @@\
$(RM) files

```

```

/*
* AddSuffix:
* Adds a suffix to the .SUFFIXES: list.
*/

```

```

#define AddSuffix(ext) @!\
|suffix ext

```

```

/*
* AllTarget:
* Generate rules to build necessary things during make all.
*/

```

```

#define AllTarget(depends) @!\
all:: depends @!\

```

```

    @!\
local_realclean::  @@\
$(RM) depends

/*
* RemoveTargetProgram:
* This is used in some other macros in order to remove the target
* before starting its building (saves disk space). There should be
* no '@!' at the end of the '#define' line, because this macro is
* used *inside* building rules.
*/
#define RemoveTargetProgram(program) \
$(RM) program @@\
if test -f program^^^$_EXE; then \ @@\
$(MV) program^^^$_EXE program^^~^^^$_EXE; fi

/*
* NormalProgramTarget:
* Generate rules to compile and link the
  indicated program; since
* it does not use any default object files, it may be used for
* multiple programs in the same Jmakefile.
*/
#define NormalProgramTarget(program,sources,objects) @!\
++OBJECTS objects @!\
++SOURCES sources @!\
NormalObjectRule() @!\
AllTarget(program) @!\
    @!\
program: objects  @@\
RemoveTargetProgram($@) @@\
$(CC) -o $@ objects $(JLDFLAGS) $(LIBS) @!\

/*
* SingleProgramTarget:
* Obsolete version of NormalProgramTarget that doesn't have
* deplibs.
*/
#define SingleProgramTarget(program,objects,libs) \
NormalProgramTarget(program,objects,libs)

/*
* SimpleProgramTarget:
* Generate rules for compiling and linking programs that only have
* one C source file. It should only be used in Jmakefiles that
* describe a single program.
*/

```

```

#define SimpleProgramTarget(program) @!\
NormalProgramTarget(program,program.c,program.o)

/*
* ComplexProgramTarget:
* Generate rules for compiling and linking the program specified by
* $(OBJS) and
* $(SRCS), installing the program and its man page, and
* generating dependencies. It should only be used in Jmakefiles
* that describe a single program.
*/
#define ComplexProgramTarget(program) @!\
++OBJECTS $(OBJS) @!\
++SOURCES $(SRCS) @!\
NormalObjectRule() @!\
AllTarget(program) @!\
    @!\
program: $(OBJS) @@\
RemoveTargetProgram($@) @@\
$(CC) -o $@ $(OBJS) $(JLDFLAGS) $(LIBS) @!\
    @!\
InstallProgram(program,$(BINDIR)) @!\
InstallManPage(program,$(MANSRC)) @!\
DependTarget() @!\
LintTarget()

/*
* ComplexProgramTarget_1:
* Generate rules for compiling and linking the program specified by
* $(OBJS1) and $(SRCS1), installing the program and its man page,
* and generating dependencies for it and any programs described by
* $(SRCS2) and $(SRCS3). It should be used to build the primary
* program in Jmakefiles that describe multiple programs.
*/
#define ComplexProgramTarget_1(program) @!\
++OBJECTS $(OBJS1) @!\
++SOURCES $(SRCS1) @!\
NormalObjectRule() @!\
AllTarget(program) @!\
    @!\
program:
$(OBJS1) @@\
RemoveTargetProgram($@) @@\
$(CC) -o $@ $(OBJS1) $(JLDFLAGS) $(LIBS) @!\
    @!\

```

```

InstallProgram(program,$(BINDIR)) @!\
InstallManPage(program,$(MANSRC)) @!\
    @!\
DependTarget()    @!\
LintTarget()

/*
* ComplexProgramTarget_2:
* Generate rules for compiling and linking the program specified by
* $(OBJS2) and $(SRCS2) and installing the program and man page.
* It should be used to build the second program in Jmakefiles
* describing more than one program.
*/
#define ComplexProgramTarget_2(program) @!\
++OBJECTS $(OBJS2) @!\
++SOURCES $(SRCS2) @!\
NormalObjectRule()    @!\
AllTarget(program)    @!\
    @!\
program: $(OBJS2)    @@\
RemoveTargetProgram($@)    @@\
$(CC) -o $@ $(OBJS2) $(JLDFLAGS) $(LIBS) @!\
    @!\
InstallProgram(program,$(BINDIR)) @!\
InstallManPage(program,$(MANSRC))

/*
* ComplexProgramTarget_3:
* Generate rules for compiling and linking the
program specified by
* $(OBJS3) and $(SRCS3) and installing the program and man page. It
* should be used to build the third program in Jmakefiles describing
* more than one program.
*/
#define ComplexProgramTarget_3(program) @!\
++OBJECTS $(OBJS3) @!\
++SOURCES $(SRCS3) @!\
NormalObjectRule()    @!\
AllTarget(program)    @!\
    @!\
program: $(OBJS3)    @@\
RemoveTargetProgram($@)    @@\
$(CC) -o $@ $(OBJS3) $(JLDFLAGS) $(LIBS) @!\
    @!\
InstallProgram(program,$(BINDIR)) @!\
InstallManPage(program,$(MANSRC))

```

```

/*
* ComplexShellManualTarget:
* Builds manual pages that are to be extracted from .SH files into
* .$manext files.
*/
#define ComplexShellManualTarget(manpages) @!\
++MANPAGE manpages @!\
|once _ShellManualRule_ @!\
|rule:.SH.$manext: @!\
|rule: /bin/sh $< @!\
|rule: @!\
-once @!\
AddSuffix(.SH) @!\
AddSuffix($manext) @!\
AllTarget(manpages) @!\
    @!\
local_install.man:: @@\
    _MakeInstallDirIgnore($(MANSRC)) \    @@\
for
file in manpages; do \    @@\
    (set -x; $(INSTALL) -c -m 444 $$file \    @@\
    $(INSTALL_PREFIX)$(MANSRC)) || exit 1; \    @@\
done @!\
    @!\
local_deinstall.man:: @@\
    @case '${MFLAGS}' in *[i]*) set +e;; esac; \    @@\
for file in manpages; do \    @@\
    (set -x; $(RM) $(INSTALL_PREFIX)$(MANSRC)/$$file); \    @@\
done

/*
* Initialize:
* Puts the line symbol = value in the initialization section of
* Makefile.SH (the one that is subject to parameter substitutions).
*/
#define Initialize(symbol,value) @!\
+symbol = value

/*
* InstallLibrary:
* Generate rules to install the indicated library.
*/
#define InstallLibrary(libname,dest) @!\
local_install:: lib^^libname.a @@\

```

```

_MakeInstallDirIgnore(dest) \ @@\
$(INSTALL) -c -m 644 lib^^libname.a $(INSTALL_PREFIX)^^dest @@\
$(RANLIB) dest/lib^^libname.a @@\
chmod 444 dest/lib^^libname.a @!\
    @!\
local_deinstall::  @@\
$(RM) $(INSTALL_PREFIX)^^dest/lib^^libname.a

/*
* InstallSharedLibrary:
* Generate rules to install
the shared library.
*/
#define InstallSharedLibrary(libname,rev,dest) @!\
local_install:: lib^^libname.so.rev @@\
_MakeInstallDirIgnore(dest) \ @@\
$(INSTALL) -c -m 444 lib^^libname.so.rev $(INSTALL_PREFIX)^^dest @!\
    @!\
local_deinstall::  @@\
$(RM) $(INSTALL_PREFIX)^^dest/lib^^libname.so.rev

/*
* InstallSharedLibraryData:
* Generate rules to install the shared library data
*/
#define InstallSharedLibraryData(libname,rev,dest) @!\
local_install:: lib^^libname.sa.rev @@\
_MakeInstallDirIgnore(dest) \ @@\
$(INSTALL) -c -m 444 lib^^libname.sa.rev $(INSTALL_PREFIX)^^dest @!\
    @!\
local_deinstall::  @@\
$(RM) $(INSTALL_PREFIX)^^dest/lib^^libname.sa.rev

/*
* InstallLibraryAlias:
* Generate rules to create a link from one library name to another
* for the purposes of aliasing.
*/
#define InstallLibraryAlias(libname,alias,dest) @!\
local_install:: lib^^libname.a @@\
$(RM) lib^^alias.a @@\
-(cd dest; $(LN) lib^^libname.a lib^^alias.a)
@!\
    @!\
local_deinstall::  @@\

```

```
$(RM) dest/lib^^alias.a
```

```
/*
```

```
* InstallLintLibrary:
```

```
* Generate rules to install the indicated lint library.
```

```
*/
```

```
#define InstallLintLibrary(libname,dest) @!\
```

```
install.ln:: llib-I^^libname.ln @@\
```

```
_MakeInstallDirIgnore(dest) \ @@\
```

```
$(INSTALL) -c -m 444 llib-I^^libname.ln $(INSTALL_PREFIX)^^dest @!\
```

```
@!\
```

```
deinstall.ln:: @@\
```

```
$(RM) $(INSTALL_PREFIX)^^dest/llib-I^^libname.ln
```

```
/*
```

```
* InstallManPageLong:
```

```
* Generate rules to install the indicated manual page, giving it an  
* alternate name. This is used for installing man pages whose base  
* name without the .man suffix would normally be longer than 8  
* characters (the limit for using source code control systems on  
* files systems with short file names).
```

```
*/
```

```
#define InstallManPageLong(file,destdir,dest) @!\
```

```
local_install.man:: file.man @@\
```

```
_MakeInstallDirIgnore(destdir) \ @@\
```

```
$(INSTALL) -c -m 444 file.man $(INSTALL_PREFIX)^^destdir/dest.$(L) @!\
```

```
@!\
```

```
local_deinstall.man:: @@\
```

```
$(RM)
```

```
$(INSTALL_PREFIX)^^destdir/dest.$(L) @!\
```

```
/*
```

```
* InstallManPage:
```

```
* Generate rules to install the indicated manual page.
```

```
*/
```

```
#define InstallManPage(file,dest) @!\
```

```
InstallManPageLong(file,dest,file)
```

```
/*
```

```
* InstallNonExec:
```

```
* Generate rules to install a data file using any special  
* install flags.
```

```
*/
```

```
#define InstallNonExec(file,dest) @!\
```

```

local_install:: file  @@\
  _MakeInstallDirIgnore(dest) \ @@\
  $(INSTALL) -c -m 444 file $(INSTALL_PREFIX)^^^dest @!\
    @!\
local_deinstall::  @@\
  $(RM) $(INSTALL_PREFIX)^^^dest/file

/*
* InstallProgramWithFlags:
* Generate rules to install an executable program using given
* install flags.
*/
#define InstallProgramWithFlags(program,dest,flags) @!\
local_install:: program  @@\
  _MakeInstallDirIgnore(dest) \ @@\
  $(INSTALL) -c -s -m 555 flags program^^^$_EXE $(INSTALL_PREFIX)^^^dest @!\
    @!\
local_deinstall::  @@\
  $(RM) $(INSTALL_PREFIX)^^^dest/program^^^$_EXE

/*
* InstallProgramNoStripWithFlags:
* Generate rules to install an executable program using given
* install flags.
*/
#define InstallProgramNoStripWithFlags(program,dest,flags) @!\
local_install:: program  @@\
  _MakeInstallDirIgnore(dest) \ @@\
  $(INSTALL) -c -m 555 flags program^^^$_EXE $(INSTALL_PREFIX)^^^dest @!\
    @!\
local_deinstall::  @@\
  $(RM) $(INSTALL_PREFIX)^^^dest/program^^^$_EXE

/*
* InstallProgram:
* Generate rules to install an executable program using any special
* install flags set in $(INSTALLFLAGS).
*/
#define InstallProgram(program,dest) @!\
InstallProgramWithFlags(program,dest,^^)

/*
* InstallProgramNoStrip:
* Generate rules to install an executable program using any special

```

```

* install flags set in $(INSTALLFLAGS), but without stripping the
* executable from debugging symbols.
*/
#define InstallProgramNoStrip(program,dest) @!\
InstallProgramNoStripWithFlags(program,dest,^^)

/*
* InstallScriptWithFlags:
* Generate rules to install an executable script using given
* install
* flags.
*/
#define InstallScriptWithFlags(script,dest,flags) @!\
local_install:: script  @@\
_MakeInstallDirIgnore(dest) \ @@\
$(INSTALL) -c -m 555 flags script $(INSTALL_PREFIX)^^^dest @!\
    @!\
local_deinstall::  @@\
$(RM) $(INSTALL_PREFIX)^^^dest/script

/*
* InstallScript:
* Generate rules to install an executable script using any special
* install flags set in $(INSTALLFLAGS).
*/
#define InstallScript(script,dest) @!\
InstallScriptWithFlags(script,dest,^^)

/*
* InstallScripts:
* Generate rules to install all the scripts listed in the generated
* $(SCRIPTS) and $(LSCRIPTS) macros.
*/
#define InstallScripts() @!\
|once _InstallScripts_ @!\
local_install:: $(SCRIPTS) $(LSCRIPTS)  @@\
_MakeInstallDirIgnore($(SCRIPTDIR)) \ @@\
for file in $(SCRIPTS) $(LSCRIPTS); do \ @@\
(set -x; \ @@\
$(INSTALL) -c -m 555 $$file $(INSTALL_PREFIX)$(SCRIPTDIR) || \ @@\
exit 1; \ @@\
done  @!\
    @!\
local_deinstall::  @@\
@for file in $(SCRIPTS)

```

```

$(LSCRIPTS); do \ @@\
  case '${MFLAGS}' in *[i]*) set +e;; esac; \ @@\
  (set -x; $(RM) $(INSTALL_PREFIX)$(SCRIPTDIR)/$$file); \ @@\
done  @!\
-once

/*
* InstallManScripts:
* Generate rule to install/deinstall manual pages for scripts listed
* in the automatically generated $(SCRIPTS) macro.
*/
#define InstallManScripts() @!\
|once _InstallManScripts_ @!\
?NOMAN:|skip  @!\
local_install.man::  @@\
  _MakeInstallDirIgnore($(MANSRC)) \ @@\
  for file in $(SCRIPTS); do \  @@\
  if test -f $$file.man; then \  @@\
    (set -x; \  @@\
    $(INSTALL) -c -m 444 $$file.man \ @@\
    $(INSTALL_PREFIX)$(MANSRC)/$$file.$(L)) || \ @@\
    exit 1; \ @@\
  fi; \  @@\
done  @!\
  @!\
local_deinstall.man::  @@\
  case '${MFLAGS}' in *[i]*) set +e;; esac; \ @@\
  for file in $(SCRIPTS); do \  @@\
    (set -x; $(RM) $(INSTALL_PREFIX)$(MANSRC)/$$file.$(L)); \ @@\
  done  @!\
  @!\
-skip  @!\
-once

/*
* LinkFileList:
* Link a list of list of files from one place to another
*/
#define LinkFileList(step,list,dir,sub) @!\
step:: list  @@\
  @case '${MFLAGS}' in *[i]*) set +e;; esac; \ @@\
  echo " cd" dir; cd dir; for i in list; do (set -x; $(LN) sub/$$i .); done

/*
* InstallMultipleDestFlags:

```

```

* Generate rules to install multiple files at once during a particular
* step in the build using a specific set of install flags.
*/
#define InstallMultipleDestFlags(step,list,dest,flags) @!\
step:: list    @@\
  _MakeInstallDirIgnore(dest) \ @@\
  for i in list; do \    @@\
    (set -x; $(INSTALL) -c flags \ @@\
     $$i $(INSTALL_PREFIX)^^^dest) || exit 1;\    @@\
  done

/*
* DeinstallMultipleDest:
* Generate rules to deinstall multiple files at once during a particular
* step in the build.
*/
#define DeinstallMultipleDest(step,list,dest) @!\
step::    @@\
  @case '${MFLAGS}' in *[i]*) set +e;; esac; \ @@\
  for i in list; do \    @@\
    (set -x; $(RM) $(INSTALL_PREFIX)^^^dest/$$i); \    @@\
  done

/*
* InstallMultiple:
* Generate rules to install multiple
  files at once during the install
* step of the build using any install flags set in $(INSTALLFLAGS)
* and deinstall them.
*/
#define InstallMultiple(list,dest) @!\
InstallMultipleDestFlags(local_install,list,dest,$(INSTALLFLAGS)) @!\
DeinstallMultipleDest(local_deinstall,list,dest)

/*
* InstallMultipleFlags:
* Generate rules to install multiple files at once during the
* install step of the build using the given install flags.
*/
#define InstallMultipleFlags(list,dest,flags) @!\
InstallMultipleDestFlags(local_install,list,dest,flags) @!\
DeinstallMultipleDest(local_deinstall,list,dest)

/*
* InstallMultipleMan:
* Generate rules to install a variety of manual pages

```

```

* during the install.man step of the build.
*/
#define InstallMultipleMan(list,dest) @!\
InstallMultipleDestFlags(local_install.man,list,dest,$(INSTALLFLAGS)) @!\
DeinstallMultipleDest(local_deinstall.man,list,dest)

/*
* DependDependency:
* Generate rules to build the makedepend program.
*/
#define DependDependency()
    @!\
depend:: TOPDIR/mkdep    @!\
    @!\
TOPDIR/mkdep:    @!\
?TOP: @echo "You have to run Configure first."; exit 1 @!\
%TOP: @echo "You have to run Configure in $(TOP) first."; exit 1

/*
* DependTarget:
* Generate rules to compute dependencies for all files listed
* in $(SOURCES) (automatically generated macro).
*/
#define DependTarget() @!\
+USRINC = $usrinc @!\
|once _DependTarget_ @!\
DependDependency() @!\
    @!\
depend::    @@\
    $(SED) /^# DO NOT DELETE/q' Makefile && \ @@\
    $(MKDEP) $(SOURCES) | \ @@\
    $(SED) -e 's:/usr/lib[^ ]*::g; s:${USRINC}[^ ]*::g; ' \ @@\
    -e '/: / b print' -e '$$ b print' -e 'H; d; n; : print' \ @@\
    -e 'x; s/\$\$/; s/\n//g; s/ ^ ^ */ /g; s/ :/:;' -e '/: *$$/d' \ @@\
) > Makefile.new    @@\
cp Makefile Makefile.bak    @@\
cp Makefile.new Makefile    @@\
$(RM) Makefile.new    @!\
    @!\
-once

/*
* CleanTarget:
* Generate rules to remove any garbage files.
*/

```

```

#define CleanTarget() @!\
?SUBDIRS:clean:
  sub_clean local_clean @!\
%SUBDIRS:clean: local_clean @!\
?SUBDIRS:realclean: sub_realclean local_realclean @!\
%SUBDIRS:realclean: local_realclean @!\
?SUBDIRS:clobber: sub_clobber local_clobber @!\
%SUBDIRS:clobber: local_clobber @!\
  @!\
local_clean:: @@\
if test -f core; then $(RM) core; fi @@\
$(RM) *~*.o @!\
  @!\
local_realclean:: local_clean @!\
?TOP: $(RM) -r UU @!\
  @!\
local_clobber:: local_realclean @!\
%TOP: $(RM) Makefile config.sh @!\
?TOP: $(RM) config.sh config.h @!\
?TOP: $(RM) -r .config @!\
?TOP: $(RM) Makefile @!\

/*
* InstallTarget:
* Generate rules to recursively install files
*/
#define InstallTarget() @!\
?SUBDIRS:install:: local_install sub_install @!\
%SUBDIRS:install:: local_install @!\
?SUBDIRS:install.man:: maybe_install.man sub_install.man @!\
%SUBDIRS:install.man:: maybe_install.man @!\
?SUBDIRS:deinstall:: sub_deinstall local_deinstall @!\
%SUBDIRS:deinstall::
  local_deinstall @!\
?SUBDIRS:deinstall.man:: sub_deinstall.man maybe_deinstall.man @!\
%SUBDIRS:deinstall.man:: maybe_deinstall.man @!\
  @!\
?MANSRC:install.man-yes: local_install.man @!\
install.man-no: @!\
?MANSRC:deinstall.man-yes: local_deinstall.man @!\
deinstall.man-no: @!\

/*
* TagsTarget:
* Generate rules to compute tags files for C source code.
*/

```

```

#define TagsTarget()  @!\
tags::  @@\
$(CTAGS) -w *.ch  @@\
$(CTAGS) -xw *.ch > tags  @!\
    @!\
local_clobber::  @@\
$(RM) tags

/*
* BuildMakefileSH:
* Generate rules to build a Makefile.SH from an Jmakefile and any
* special jmake flags. This is generally done automatically by the
* template or by any special Jmakefiles.
* This function will simply touch Makefile.SH if no $(TOP)/.package
* exists, assuming the Jmakefile is not in a production environment.
*/
#define BuildMakefileSH(jmakeflags) @!\
Makefile.SH:
Jmakefile  @@\
-@if test -f $(TOP)/.package; then \ @@\
if test -f Makefile.SH; then \ @@\
    echo "$(RM) Makefile.SH~; $(MV) Makefile.SH Makefile.SH~"; \ @@\
    $(RM) Makefile.SH~; $(MV) Makefile.SH Makefile.SH~; \ @@\
fi; \  @@\
echo " $(JMAKE) -DTOPDIR=$(TOP) -DCURDIR=$(CURRENT)" jmakeflags; \ @@\
$(JMAKE) -DTOPDIR=$(TOP) -DCURDIR=$(CURRENT) jmakeflags; \ @@\
else touch $@; fi

/*
* BuildMakefile:
* Generate rules to build a Makefile from a Makefile.SH.
*/
#define BuildMakefile() @!\
Makefile: Makefile.SH  @@\
/bin/sh Makefile.SH

/*
* MakefileTarget:
* Generate rules to build a normal Makefile.
*/
#define MakefileTarget() @!\
BuildMakefileSH(^)  @!\
BuildMakefile()

```

```

/*
* NormalObjectRule:
* Generate make rule to build usual object files.
*/
#define NormalObjectRule() @!\
|once _ObjectRule_ @!\
|rule:.c.o: @!\
|rule: $(CC) -c $(JCFLAGS) $< @!\
|rule: @!\
-once

/*
* NormalLibraryObjectRule:
* Generate make rules to build
"normal" objects.
*/
#define NormalLibraryObjectRule() @!\
|once _ObjectRule_ @!\
|rule:.c.o: @!\
|rule: $(RM) $@ @!\
|rule: $(CC) -c $(JCFLAGS) $< @!\
|rule: @!\
-once

/*
* ProfiledLibraryObjectRule:
* Generate make rules to build both profiled and "normal" objects.
*/
#define ProfiledLibraryObjectRule() @!\
all:: @@\
    @if [ ! -d profiled ]; then mkdir profiled; fi @!\
    @!\
|rule:.c.o: @!\
|rule: $(RM) $@ profiled/$@ @!\
|rule: $(CC) -pg -c $(JCFLAGS) $*.c @!\
|rule: $(MV) $*.o profiled/$*.o @!\
|rule: $(CC) -c $(JCFLAGS) $*.c @!\
|rule: @!\
local_clean:: @@\
    -@if [ -d profiled ]; then echo " $(RM) profiled/*.*"; \ @!\
    $(RM) profiled/*.*; fi

/*
* DebuggedLibraryObjectRule:
* Generate make rules to build both debuggable and "normal"
* objects.

```

```

*/
#define DebuggedLibraryObjectRule() @!\
all:: @!\
@if [ ! -d debugger ]; then mkdir debugger; fi @!\
    @!\
|rule:.c.o: @!\
|rule: $(RM) $@
debugger/$@ @!\
|rule: $(CC) -g -c $(JCFLAGS) $*.c @!\
|rule: $(MV) $*.o debugger/$*.o @!\
|rule: $(CC) -c $(JCFLAGS) $*.c @!\
|rule: @!\
local_clean:: @!\
-@if [ -d debugger ]; then echo " $(RM) debugger/?*.o"; \ @!\
$(RM) debugger/?*.o; fi

/*
* DebuggedAndProfiledLibraryObjectRule:
* Generate make rules to build debuggable, profiled, and "normal"
* objects.
*/
#define DebuggedAndProfiledLibraryObjectRule() @!\
all:: @!\
@if [ ! -d profiled ]; then mkdir profiled; fi @!\
@if [ ! -d debugger ]; then mkdir debugger; fi @!\
    @!\
|rule:.c.o: @!\
|rule: $(RM) $@ profiled/$@ debugger/$@ @!\
|rule: $(CC) -pg -c $(JCFLAGS) $*.c @!\
|rule: $(MV) $*.o profiled/$*.o @!\
|rule: $(CC) -g -c $(JCFLAGS) $*.c @!\
|rule: $(MV) $*.o debugger/$*.o @!\
|rule: $(CC) -c $(JCFLAGS) $*.c @!\
|rule: @!\
local_clean:: @!\
-@if [ -d profiled ]; then echo " $(RM) profiled/?*.o"; \ @!\
$(RM) profiled/?*.o; fi @!\
-@if [ -d debugger ];
then echo " $(RM) debugger/?*.o"; \ @!\
$(RM) debugger/?*.o; fi

/*
* SharedLibraryObjectRule:
* Generate make rules to build shared and "normal" object files.
*/
#define SharedLibraryObjectRule() @!\

```

```

all::    @@\
    @if [ ! -d shared ]; then mkdir shared; fi @!\
        @!\
|rule:.c.o:    @!\
|rule: $(RM) $@ shared/$@ @!\
|rule: $(CC) -pic -c $(SHARED_CODEDEF) $(SHLIBDEF) $(JCFLAGS) $*.c @!\
|rule: $(MV) $*.o shared/$*.o @!\
|rule: $(CC) -c $(SHLIBDEF) $(JCFLAGS) $*.c @!\
|rule:    @!\
local_clean::    @@\
-@if [ -d shared ]; then echo " $(RM) shared/?*.o"; \ @@\
$(RM) shared/?*.o; fi

```

```

/*
* SharedAndDebuggedLibraryObjectRule:
* Generate make rules to build shared, debuggable, and "normal"
* object files.
*/

```

```

#define SharedAndDebuggedLibraryObjectRule() @!\
all::    @@\
    @if [ ! -d shared ]; then mkdir shared; fi @@\
    @if [ ! -d debugger ]; then mkdir debugger; fi @!\
        @!\
|rule:.c.o:    @!\
|rule: $(RM) $@ shared/$@ debugger/$@ @!\
|rule:
$(CC) -pic -c $(SHARED_CODEDEF) $(SHLIBDEF) $(JCFLAGS) $*.c @!\
|rule: $(MV) $*.o shared/$*.o @!\
|rule: $(CC) -g -c $(SHLIBDEF) $(JCFLAGS) $*.c @!\
|rule: $(MV) $*.o debugger/$*.o @!\
|rule: $(CC) -c $(SHLIBDEF) $(JCFLAGS) $*.c @!\
|rule:    @!\
local_clean::    @@\
-@if [ -d shared ]; then echo " $(RM) shared/?*.o"; \ @@\
$(RM) shared/?*.o; fi @@\
-@if [ -d debugger ]; then echo " $(RM) debugger/?*.o"; \ @@\
$(RM) debugger/?*.o; fi

```

```

/*
* SpecialSharedAndDebuggedObjectRule:
* Generate rules to compile a file with special flags and to make
* shared and debuggable versions.
*/

```

```

#define SpecialSharedAndDebuggedObjectRule(objs,depends,options) @!\
all::    @@\
    @if [ ! -d shared ]; then mkdir shared; fi @@\
    @if [ ! -d debugger ]; then mkdir debugger; fi @!\
        @!\

```

```

objs: depends    @@\
$(RM) $@ shared/$@  @@\
$(CC) -pic -c $(SHARED_CODEDEF) $(SHLIBDEF) $(JCFLAGS) options $*.c @@\
$(MV) $*.o shared/$*.o  @@\
$(CC)
-g -c $(SHLIBDEF) $(JCFLAGS) options $*.c  @@\
$(MV) $*.o debugger/$*.o  @@\
$(CC) -c $(SHLIBDEF) $(JCFLAGS) options $*.c

/*
* SpecialSharedObjectRule:
* Generate rules to compile a file with special flags and to make
* shared and debuggable versions.
*/
#define SpecialSharedObjectRule(objs,depends,options) @!\
all::    @@\
@if [ ! -d shared ]; then mkdir shared; fi @!\
    @!\
objs: depends    @@\
$(RM) $@ shared/$@  @@\
$(CC) -pic -c $(SHARED_CODEDEF) $(SHLIBDEF) $(JCFLAGS) options $*.c @@\
$(MV) $*.o shared/$*.o  @@\
$(CC) -c $(SHLIBDEF) $(JCFLAGS) options $*.c

/*
* SpecialObjectRule:
* Generate rules to compile a file with special flags.
*/
#define SpecialObjectRule(objs,depends,options) @!\
objs: depends    @@\
$(RM) $@    @@\
$(CC) -c $(JCFLAGS) options $*.c

/*
* SpecialProfiledObjectRule:
* Generate rules to compile a file with special flags and to make a
* profiled version.
*/
#define SpecialProfiledObjectRule(objs,depends,options) @!\
all::    @@\
@if
[ ! -d profiled ]; then mkdir profiled; fi @!\
    @!\
objs: depends    @@\
$(RM) $@ profiled/$@  @@\
$(CC) -pg -c $(JCFLAGS) options $*.c @@\

```

```

$(MV) $*.o profiled/$*.o  @@\
$(CC) -c $(JCFLAGS) options $*.c

/*
* SpecialDebuggedObjectRule:
* Generate rules to compile a file with special flags and to make a
* debuggable version.
*/
#define SpecialDebuggedObjectRule(objs,depends,options) @!\
all::      @@\
    @if [ ! -d debugger ]; then mkdir debugger; fi @!\
    @!\
objs: depends      @@\
$(RM) $@ debugger/$@  @@\
$(CC) -g -c $(JCFLAGS) options $*.c @@\
$(MV) $*.o debugger/$*.o  @@\
$(CC) -c $(JCFLAGS) options $*.c

/*
* SpecialDebuggedAndProfiledObjectRule:
* Generate rules to compile a file with special flags and to make
* debuggable and profiled versions.
*/
#define SpecialDebuggedAndProfiledObjectRule(objs,depends,options) @!\
all::      @@\
    @if [ ! -d profiled ]; then mkdir profiled; fi @@\
    @if [ ! -d
debugger ]; then mkdir debugger; fi @!\
    @!\
objs: depends      @@\
$(RM) $@ profiled/$@ debugger/$@  @@\
$(CC) -pg -c $(JCFLAGS) options $*.c @@\
$(MV) $*.o profiled/$*.o  @@\
$(CC) -g -c $(JCFLAGS) options $*.c @@\
$(MV) $*.o debugger/$*.o  @@\
$(CC) -c $(JCFLAGS) options $*.c

/*
* NormalLibraryTarget:
* Generate rules to create a library. The 'srclist' and 'objlist'
* parameters are added to SOURCES and OBJECTS macros. The 'srclist'
* is not otherwise used by this rule, but is necessary for make depend.
*/
#define NormalLibraryTarget(libname,srclist,objlist) @!\
++OBJECTS objlist @!\

```

```

++SOURCES srclist @!\
NormalLibraryObjectRule() @!\
AllTarget(lib^^libname.a) @!\
    @!\
lib^^libname.a: objlist @@\
$(RM) $@ @@\
$(AR) $@ objlist @@\
$(RANLIB) $@

/*
* NormalSharedLibraryTarget:
* Generate rules to create a shared library; build it into a
* different name so that the we don't hose people by having the
* library gone for long periods.
*/
#define
NormalSharedLibraryTarget(libname,rev,so) @!\
AllTarget(lib^^libname.so.rev) @!\
    @!\
lib^^libname.so.rev: so @@\
$(RM) $@~ @@\
(cd shared; $(LD) -o ../$@~ -assert pure-text so) @@\
$(RM) $@ @@\
$(MV) $@~ $@

/*
* NormalSharedLibraryDataTarget:
* Generate rules to create shlib data file; build it into a
* different name so that the we don't hose people by having the
* library gone for long periods.
*/
#define NormalSharedLibraryDataTarget(libname,rev,salist) @!\
AllTarget(lib^^libname.sa.rev) @!\
    @!\
lib^^libname.sa.rev: salist @@\
$(RM) $@ @@\
$(AR) $@ salist @@\
$(RANLIB) $@

/*
* NormalLibraryTarget2:
* Generate rules to create a library in two steps. This is used to
* create libraries with large numbers of files.
*/
#define NormalLibraryTarget2(libname,srclist,objlist1,objlist2) @!\
++SOURCES srclist @!\

```

```

++OBJECTS objlist1 @!\
++OBJECTS objlist2 @!\
NormalLibraryObjectRule() @!\
AllTarget(lib^^libname.a) @!\
    @!\
lib^^libname.a:
objlist1 objlist2 @@\
$(RM) $@    @@\
$(AR) $@ objlist1    @@\
$(AR) $@ objlist2    @@\
$(RANLIB) $@

/*
* ProfiledLibraryTarget:
* Generate rules to create a profiled library.
*/
#define ProfiledLibraryTarget(libname,srclist,objlist) @!\
++SOURCES srclist @!\
++OBJECTS objlist @!\
AllTarget(lib^^libname^^_p.a) @!\
    @!\
lib^^libname^^_p.a: objlist    @@\
$(RM) $@    @@\
cd profiled; $(AR) ../$@ objlist @@\
$(RANLIB) $@

/*
* DebuggedLibraryTarget:
* Generate rules to create a debuggable library.
*/
#define DebuggedLibraryTarget(libname,srclist,objlist) @!\
++SOURCES srclist @!\
++OBJECTS objlist @!\
AllTarget(lib^^libname^^_d.a) @!\
    @!\
lib^^libname^^_d.a: objlist    @@\
$(RM) $@    @@\
cd debugger; $(AR) ../$@ objlist @@\
$(RANLIB) $@

/*
* AliasedLibraryTarget:
* Generate rules to link one library to another.
*/
#define AliasedLibraryTarget(libname,alias) @!\

```

```
AllTarget(lib^^alias.a) @!\
    @!\
lib^^alias.a:
lib^^libname.a @@\
$(RM) $@  @@\
$(LN) lib^^libname.a $@
```

```
/*
```

```
* PrelinkedRelocatableTarget:
* Generate rules to produce a relocatable object file instead of a
* library.
*/
```

```
#define PrelinkedRelocatableTarget(objname,objlist,libs) @!\
AllTarget(objname.o) @!\
    @!\
objname.o: objlist  @@\
$(RM) $@  @@\
$(LD) $(JLDFLAGS) -r objlist -o $@ libs
```

```
/*
```

```
* NormalObjectTarget:
* Generate rules to produce a single object file.o from a file.c.
*/
```

```
#define NormalObjectTarget(file) @!\
++SOURCES file^^.c  @!\
AllTarget(file^^.o) @!\
NormalObjectRule()
```

```
/*
```

```
* NormalRelocatableTarget:
* Generate rules to produce a relocatable object file instead of a
* library.
*/
```

```
#define NormalRelocatableTarget(objname,objlist) @!\
AllTarget(objname.o) @!\
    @!\
objname.o: objlist  @@\
$(RM) $@  @@\
$(LD) $(JLDFLAGS) -r objlist -o $@
```

```
/*
```

```
* ProfiledRelocatableTarget:
* Generate rules to produce a profiled relocatable object file
* instead
```

```

of a library.
*/
#define ProfiledRelocatableTarget(objname,objlist) @!\
AllTarget(objname^^_p.o) @!\
    @!\
objname^^_p.o: objlist  @@\
$(RM) $@  @@\
$(LD) -X -r objlist -o $@

/*
* DebuggedRelocatableTarget:
* Generate rules to produce a debuggable relocatable object file
* instead of a library.
*/
#define DebuggedRelocatableTarget(objname,objlist) @!\
AllTarget(objname^^_d.o) @!\
    @!\
objname^^_d.o: objlist  @@\
$(RM) $@  @@\
$(LD) -X -r objlist -o $@

/*
* LintLibraryTarget:
* Generate rules to create a lint library. Note that the lint
* library is always forced to be newer than the library itself.
*/
#define LintLibraryTarget(libname,srclist) @!\
lintlib:: llib-l^^libname.ln @!\
    @!\
llib-l^^libname.ln: srclist  @@\
$(RM) $@  @@\
$(LINT) $(LINTLIBFLAG)^^libname $(LINTFLAGS) srclist

/*
* NormalLintTarget:
* Generate rules to lint a set of sources.
*/
#define NormalLintTarget(srclist) @!\
lint:  @@\
$(LINT) $(LINTFLAGS) srclist
$(LINTLIBS)

/*
* LintTarget:
* Generate rules to lint $(SOURCES) (automatically generated)

```

```

*/
#define LintTarget() @!\
|once _LintTarget_ @!\
NormalLintTarget($(SOURCES)) @!\
-once

/*
* LinkSourceFile:
* Snag source file from some other directory
*/
#define LinkSourceFile(src,dir) @!\
src: dir/src @@\
$(RM) $@ @@\
$(LN) $? $@ @!\

/*
* MakeSubincludesForBuild:
* Make includes in sub directories.
*/
#define MakeSubincludesForBuild(step,dir,srclist) @!\
step:: dir srclist @@\
@-(list=`echo srclist | sed -e 's/[^ ]*///g^'; \ @@\
set -x; cd dir; $(RM) $$list) @@\
@for i in srclist; do \ @@\
(set -x; cd dir; $(LN) ../$$i .) || exit 1; \ @@\
done @!\
@!\
MakeDirectories(dir,dir) @!\
@!\
local_realclean:: @@\
@-(if [ -d dir ]; then \ @@\
list=`echo srclist | sed -e 's/[^ ]*///g^'; \ @@\
set -x; cd dir; $(RM) $$list; fi)

/*
* CommonSubdirsRule:
* Rule for making $(TARGET) in
every subdirectory, with $(VERB) as
* verbose message and $(FLAGS) as additional flags.
*/
#define CommonSubdirsRule(dirs) @!\
subdirs: @@\
@case '${MFLAGS}' in *[ik]*) set +e;; esac; \ @@\
for i in dirs ;\ @@\
do \ @@\

```

```
(cd $$i ; echo $(VERB) "in $(DIR)$$i..."; \ @@\
$(MAKE) $(MFLAGS) $(FLAGS) $(TARGET)) || exit 1; \ @@\
done
```

```
/*
* NamedTargetSubdirsRule:
* Recursively make a series of steps in the specified directories.
*/
```

```
#define NamedTargetSubdirsRule(dirs,name,verb,flags) @!\
name::    @@\
    @case '{$MFLAGS}' in *[ik]*) set +e;; esac; \ @@\
for i in dirs ;\    @@\
do \    @@\
    (cd $$i ; echo verb "in $(DIR)$$i..."; \ @@\
    $(MAKE) $(MFLAGS) flags name) || exit 1; \ @@\
done
```

```
/*
* NamedTargetSubdirs:
* Recursively make a series of steps.
*/
#define NamedTargetSubdirs(name,verb,flags) @!\
name::    @@\
    @$(MAKE) subdirs TARGET=name VERB=verb FLAGS=flags
```

```
/*
* NamedSubTargetSubdirs:
* Recursively make a series of steps,
like NamedTargetSubdirs.
* However, the supplied "name" has "sub_" prefixed to it.
*/
#define NamedSubTargetSubdirs(name,verb,flags) @!\
sub_^^name::    @@\
    @$(MAKE) subdirs TARGET=name VERB=verb FLAGS=flags
```

```
/*
* NamedDepthTargetSubdirs:
* Recursively make a series of steps. We first enter the
* subdirectories, then perform the local entries.
* The supplied "name" has "sub_" prefixed to it.
*/
#define NamedDepthTargetSubdirs(name,verb,flags) @!\
sub_^^name::    @@\
    @$(MAKE) subdirs TARGET=name VERB=verb FLAGS=flags @@\
    @echo "Back to $(CURRENT) for "name^^...
```

```

/*
* MakeSubdirs:
* Generate rules to do makes in the given subdirectories.
*/
#define MakeSubdirs() \
NamedTargetSubdirs(all,"Making all",^^)

/*
* DependDirs:
* Generate rules to recursively compute dependencies as part of the
* make depend step.
*/
#define DependDirs(dirs) \
NamedTargetSubdirsRule(dirs,depend,"Depending",^^)

/*
* DependSubdirs:
* Generate rules to recursively compute dependencies
as part of the
* make depend step.
*/
#define DependSubdirs() \
DependDirs($(SUBDIRS))

/*
* InstallSubdirs:
* Generate rules to recursively install and deinstall programs and
* files.
*/
#define InstallSubdirs() \
NamedSubTargetSubdirs(install,"Installing",^^) @!\
NamedDepthTargetSubdirs(deinstall,"Deinstalling",^^)

/*
* InstallManSubdirs:
* Generate rules to recursively install and deinstall manual pages.
*/
#define InstallManSubdirs() \
NamedSubTargetSubdirs(install.man,"Installing man pages",^^) @!\
NamedDepthTargetSubdirs(deinstall.man,"Deinstalling man pages",^^)

```

```

/*
* IncludesSubdirs:
* Generate rules to recursively put include files in build
*/
#define IncludesSubdirs() \
NamedTargetSubdirs(includes,including,^^)

/*
* CleanSubdirs:
* Generate rules to recursively clean out garbage files.
*/
#define CleanSubdirs() \
NamedDepthTargetSubdirs(clean,"Cleaning",^^) @!\
NamedDepthTargetSubdirs(realclean,"Real cleaning",^^) @!\
NamedDepthTargetSubdirs(clobber,"Clobbering",^^)

/*
* TagSubdirs:
* Generate rules to recursively create tags files.
*/
#define TagSubdirs(dirs) \
NamedTargetSubdirsRule(dirs,tag,"Tagging",^^)

/*
* MakeLintSubdirs:
* Generate rules to recursively lint directories as part of the
* named step.
*/
#define MakeLintSubdirs(dirs,target) \
NamedTargetSubdirsRule(dirs,target,"Linting",^^)

/*
* LintDirs:
* Generate rules to recursively lint directories as part of the
* make lint step.
*/
#define LintDirs(dirs) \
MakeLintSubdirs(dirs,lint)

/*
* LintSubdirs:
* Generate rules to recursively lint directories as part of the
* make lint step.
*/

```

```

#define LintSubdirs() \
LintDirs($(SUBDIRS))

/*
* MakeDirs:
* Creates a set of directories, even if some directories in the path
* do not already exist. There should be no '@!' at the end of the
* '#define' line, because this macro is used *inside* building rules.
*/
#define MakeDirs(dirs) \
@case '${MFLAGS}' in *[i]*) set +e;; esac; \ @@\
for dir in dirs;
do \    @@\
(set -x; test -d $$dir || $(INSTALLDIR) $$dir) || \ @@\
exit 1; \ @@\
done

/*
* _MakeInstallDirs:
* Creates a set of intall directories, even if some directories in the path
* do not already exist. There should be no '@!' at the end of the
* '#define' line, because this macro is used *inside* building rules.
*/
#define _MakeInstallDirs(dirs) \
@case '${MFLAGS}' in *[i]*) set +e;; esac; \ @@\
for dir in dirs; do \    @@\
_MakeInstallDir($$dir) \    @@\
done

/*
* _MakeInstallDir:
* Internal macro to create a missing install directory.
*/
#define _MakeInstallDir(dir) \
(set -x; test -d $(INSTALL_PREFIX)^dir || \ @@\
$(INSTALLDIR) $(INSTALL_PREFIX)^dir);

/*
* _MakeInstallDirIgnore:
* Same as _MakeInstallDir but handles "make -i" as well.
*/
#define _MakeInstallDirIgnore(dir) \
@case '${MFLAGS}' in *[i]*) set +e;; esac; \ @@\
_MakeInstallDir(dir)

/*
* _RmInstallDirs:

```

```

* Removes a set of intall directories.
* There should be no '@!'
  at the end of the '#define' line, because this
* macro is used *inside* building rules.
*/
#define _RmInstallDirs(dirs) \
  @case '${MFLAGS}' in *[i]*) set +e;; esac; \ @@\
  for dir in dirs; do \    @@\
    (set -x; test -d $$dir && $(RM) -r $(INSTALL_PREFIX)$$dir); \ @@\
  done

/*
* MakeDirectories:
* Generate rules to create a hierarchy of directories.
*/
#define MakeDirectories(step,dirs) @!\
step::    @@\
  MakeDirs(dirs)

/*
* MakeInstallDirectories:
* Generate a rule to create a set of directories at installation
* time (removed by deinstall).
*/
#define MakeInstallDirectories(dirs) @!\
local_install::  @@\
  _MakeInstallDirs(dirs) @!\
    @!\
local_deinstall:: @@\
  _RmInstallDirs(dirs)

/*
* MakeLintLibSubdirs:
* Generate rules to recursively create lint libraries.
*/
#define MakeLintLibSubdirs(dirs) @!\
MakeLintSubdirs(dirs,lintlib)

/*
* MakeMakeSubdirs:
* Generate rules to recursively recreate target as part of the
* specified step in the build.
  This assumes Makefile.SH has
* already been built (which is the case for a delivery), but does
* not rely on the existence of a Makefile.

```

```

*/
#define MakeMakeSubdirs(target) @!\
target::    @@\
    @case '${MFLAGS}' in *[ik]*) set +e;; esac; \ @@\
    for i in $(SUBDIRS);\    @@\
    do \    @@\
    echo "Making "target" in $(DIR)$Si..."; \ @@\
    (cd $Si || exit 1; \    @@\
    if test ! -f Makefile; then /bin/sh Makefile.SH; fi; \ @@\
    $(MAKE) $(MFLAGS) target) || exit 1;\    @@\
    done

/*
* MakeMakefilesSH:
* Generate rules to recursively recreate target as part of the
* specified step in the build. If $(TOP) is set to an absolute
* path, don't prepend the ../ prefix. This makes running things
* outside of the source tree to be much easier.
*/
#define MakeMakefilesSH() @!\
Makefiles.SH:: Makefile.SH    @@\
    @case '${MFLAGS}' in *[ik]*) set +e;; esac; \ @@\
    for i in $(SUBDIRS);\    @@\
    do \    @@\
    case "$(DIR)$Si/" in \    @@\
    ^^*^^/^^*^^/^^*^^/^^*^^) newtop=../../...;;
    \ @@\
    ^^*^^/^^*^^/^^*^^) newtop=../../...;; \    @@\
    ^^*^^/^^*^^) newtop=../...;; \    @@\
    *^^) newtop=...;; \    @@\
    esac; \    @@\
    case "$(TOP)" in \    @@\
    /^^*) newtop="$(TOP)" ;; \    @@\
    esac; \    @@\
    echo "Making Makefiles.SH in $(DIR)$Si..."; \ @@\
    (cd $Si || exit 1; \    @@\
    if test -f Jmakefile; then \    @@\
    $(MAKE) $(MFLAGS) -f ../Makefile \    @@\
    Makefile TOP=$$newtop CURRENT=$(DIR)$Si && \    @@\
    $(MAKE) $(MFLAGS) Makefiles.SH; \    @@\
    fi; \    @@\
    ) || exit 1; \    @@\
    done

/*
* MakefileSubdirs:

```

```

* Generate rules to create Makefiles.
*/
#define MakefileSubdirs() @!\
MakeMakeSubdirs(Makefiles) @!\
MakeMakefilesSH()

/*
* CppScriptTarget:
* Generate rules to create a shell script by running the input
* through cpp.
*/
#define CppScriptTarget(dst,src,defs,deplist) @!\
dst:: src deplist  @@\
$(RM) $@  @@\
$(CPP) defs <src | \  @@\
sed -e '/^# *[0-9][0-9]* *.*$$/d' >$@  @@\
chmod a+x $@

/*
* MakeScriptFromCpp:
* Generate rules to create a script from a file with a
* .cpp suffix.
*/
#define MakeScriptFromCpp(name,defs) @!\
CppScriptTarget(name,name.cpp,defs,^^)

/*
* ShellScriptTargetExt:
* Generate rules to create and install a set of scripts from
* ext files (.sh and .SH are the most common examples). Man pages
* derived from the name of the scripts are also installed unless
* NoManPages() is specified.
*/
#define ShellScriptTargetExt(scripts,ext) @!\
++SCRIPTS scripts @!\
SimpleShellScriptTargetExt(scripts,ext) @!\
InstallScripts()  @!\
InstallManScripts()

/*
* ShellScriptTarget:
* Generate rules to create and install a set of scripts from
* .SH files. Man pages derived from the name of the scripts are
* also installed unless NoManPages() is specified.

```

```

*/
#define ShellScriptTarget(scripts) @!\
ShellScriptTargetExt(scripts,.SH)

/*
* SimpleShellScriptTargetExt:
* Generate rules to create a set of scripts from ext files where
* ext is usually
* something like .sh or .SH, or whatever file
* extension you like..
*/
#define SimpleShellScriptTargetExt(scripts,ext) @!\
AllTarget(scripts) @!\
    @!\
|expand s!scripts! @!\
!s: !s^^ext @@\
/bin/sh !s^^ext @!\
    @!\
-expand

/*
* SimpleShellScriptTarget:
* Generate rules to create a set of scripts from .SH files.
*/
#define SimpleShellScriptTarget(scripts) @!\
SimpleShellScriptTargetExt(scripts,.SH)

/*
* ShellScriptLongTarget:
* Generate rules to create a set of scripts from .SH files where
* the name of the generated file is different from the basename of
* the .SH file (when, for instance, the total length with the .SH
* extension would not leave enough space for RCS ,v extension).
*/
#define ShellScriptLongTarget(basename,scriptname) @!\
++LSCRIPTS scriptname @!\
AllTarget(scriptname) @!\
    @!\
scriptname: basename^^.SH @@\
/bin/sh basename^^.SH @!\
    @!\
InstallScripts() @!\
?NOMAN:|skip @!\
InstallManPageLong(basename,$(MANSRC),scriptname) @!\
-skip

```

```

/*
 * ForceTarget:
 * The force target will force reconstruction of all the other
 * targets which include .FORCE in their own dependencies.
 */
#define ForceTarget() @!\
|once _force_ @!\
.FORCE: @!\
    @!\
-once

/*
 * RemoteTargetDependency:
 * A local target may rely on a remote dependency (e.g. a library)
 * made in a separate directory. This rule explicits the dependency
 * and forces a make of that dependency in the remote directory.
 */
#define RemoteTargetDependency(target,directory,dependency) @!\
RemoteDependency(directory,dependency) @!\
target: directory/^^^dependency @!\

/*
 * RemoteDependency:
 * Specify rules for making a remote dependency.
 */
#define RemoteDependency(directory,dependency) @!\
ForceTarget() @!\
|once =directory/^^^dependency= @!\
directory/^^^dependency: .FORCE @@\
    @echo "Checking "^^^dependency" in "^^^directory"..." @@\
    cd ^^^directory; $(MAKE) ^^^dependency @@\
    @echo "Continuing in $(CURRENT)..." @!\
    @!\
-once

/*
 * SetSubdirs:
 * Actually forces the definition of SUBDIRS, and lets the user
 * specify what the sub-directories are. This will be added to the
 * customization part.
 */
#define SetSubdirs(subdirs) @!\
>SUBDIRS @!\
+SUBDIRS = subdirs

```

```

/*
* NoManPages:
* Actually forces the definition of NOMAN, which tells the jmake
* program to not generate rules for installing manual pages.
*/
#define NoManPages() @!\
>NOMAN

```

```

/*
* Expand:
* This powerful macro expands the `rule' given a `pattern'. It
* relies on a built-in command in jmake. The expansion is
* documented in the short notes file that comes with jmake and
* gives some insights on the internal syntax.
*/
#define Expand(rule, pattern) @!\
|expand pattern @!\
rule @!\
-expand

```

```

/*
* Lex and yacc stuff.
*/

```

```

/*
* YaccRule:
* This is the rule which is used to build a .c file from a .y file.
*/
#define YaccRule() @!\
AddSuffix(.y) @!\
|once _YaccRule_ @!\
|rule:.y.c: @!\
|rule: $(YACC) $(JYFLAGS)
$< @!\
|rule: $(MV) y.tab.c $@ @!\
|rule: @!\
-once

```

```

/*
* SimpleYaccTarget:
* Declare a yacc base.y file to be used in the building of the
* specified target program. The source file must be given without
* its final .y extension. The name of the .c and .o will be
* derived from the source file basename provided.

```

```

*/
#define SimpleYaccTarget(program,base) @!\
++SOURCES base.y @!\
++OBJECTS base.o @!\
YaccRule() @!\
program: base.c @!\
    @!\
local_realclean:: @@\
$(RM) base.c @!\

/*
* ComplexYaccTarget:
* Declare a yacc base.y file to be used in the building of the
* specified target program. The source file must be given without
* its final .y extension. The name of the .c and .o will be
* derived from the source file basename provided.
* The difference with SimpleYaccTarget is the identifying process
* where all the 'yy' are replaced by the specified prefix.
*/
#define ComplexYaccTarget(program,base,prefix) @!\
++SOURCES base.y @!\
++OBJECTS base.o
    @!\
program: base.c @!\
    @!\
base.c: base.y    @@\
$(YACC) $(JYFLAGS) base.y @@\
$(SED) -e 's/yy\(.)/prefix\1/g' < y.tab.c > base.c @@\
$(SED) -e 's/yy\(.)/prefix\1/g' < y.tab.h > base.h @@\
$(RM) y.tab.c y.tab.h @!\
    @!\
local_realclean:: @@\
$(RM) base.c @!\

/*
* SimpleYaccInclude:
* Declare that program will need an include file produced by
* the output of yacc on base.y, which typically produces a file
* named y.tab.h, which will be renamed as base.h.
* The only problem is that the dependencies towards base.h have
* to be manually given in the Jmakefile.
*/
#define SimpleYaccInclude(base) @!\
base.h: base.c @@\
@if test -f y.tab.h; then \ @@\
    echo " $(MV) y.tab.h $@"; \ @@\

```

```

$(MV) y.tab.h $@; \ @@\
fi    @!\
    @!\
local_realclean::  @@\
$(RM) base.h

/*
* ComplexYaccInclude:
* Declare that program will need an include file produced by
* the output of yacc on base.y, which typically produces a file
* named y.tab.h, which will
* be renamed as base.h.
* The difference with SimpleYaccInclude is the identifying process
* of the y.tab.h file where all 'yy' are renamed to prefix.
* The only problem is that the dependencies towards base.h have
* to be manually given in the Jmakefile.
*/
#define ComplexYaccInclude(base,prefix) @!\
base.h: base.c  @@\
    @if test -f y.tab.h; then \ @@\
    echo " $(SED) -e 's/yy\(.)/prefix\1/g' < y.tab.h > base.h"; \ @@\
    $(SED) -e 's/yy\(.)/prefix\1/g' < y.tab.h > base.h; \ @@\
    echo " $(RM) y.tab.h"; \ @@\
    $(RM) y.tab.h; \ @@\
    elif test -f base.h; then \ @@\
    echo " $(CP) base.h base.ht"; \ @@\
    $(CP) base.h base.ht; \ @@\
    echo " $(SED) -e 's/yy\(.)/prefix\1/g' < base.ht > base.h"; \ @@\
    $(SED) -e 's/yy\(.)/prefix\1/g' < base.ht > base.h; \ @@\
    echo " $(RM) base.ht"; \ @@\
    $(RM) base.ht; \ @@\
fi    @!\
    @!\
local_realclean::  @@\
$(RM) base.h

/*
* NormalYaccTarget:
* Declare a yacc base.y file which should produce a base.c and
* base.h file
* as derived from the output of yacc, to be used by
* the specified program.
*/
#define NormalYaccTarget(program,base) @!\
SimpleYaccTarget(program,base) @!\
SimpleYaccInclude(base)

```

```

/*
* IdentifiedYaccTarget:
* Declare a yacc base.y file which should produce a base.c and
* base.h file as derived from the output of yacc, to be used by
* the specified program. The specified prefix is used to remplace
* all the 'yy' in the generated file, for use when more than a
* single parser is needed in one executable.
*/
#define IdentifiedYaccTarget(program,base,prefix) @!\
ComplexYaccTarget(program,base,prefix) @!\
ComplexYaccInclude(base,prefix)

```

```

/*
* SimpleLexTarget:
* This declares a lex base.l file which is to be ran through
* lex to produce a base.c file.
*/
#define SimpleLexTarget(program,base) @!\
++SOURCES base.l @!\
++OBJECTS base.o @!\
|once _LexRule_ @!\
|rule:.l.c: @!\
|rule: $(LEX) $(JLFLAGS) $< @!\
|rule: $(MV) lex.yy.c $@ @!\
|rule: @!\
-once @!\
AddSuffix(.l) @!\
program:
base.c @!\
    @!\
local_realclean:: @@\
$(RM) base.c @!\

```

```

/*
* IdentifiedLexTarget:
* This declares a lex base.l file which is to be ran through
* lex to produce a base.c file. The prefix is used to replace
* the 'yy', so that the lexical analyzer may be identified.
*/
#define IdentifiedLexTarget(program,base,prefix) @!\
++SOURCES base.l @!\
++OBJECTS base.o @!\
program: base.c @!\
    @!\
base.c: base.l @@\

```

```
$(LEX) $(JLFLAGS) base.l @@\  
$(SED) -e 's/yy\(.)/prefix\1/g' < lex.yy.c > base.c @@\  
$(RM) lex.yy.c @!  
@!  
local_realclean:: @@\  
$(RM) base.c @!
```

```
/*  
* NormalLexDependTarget:  
* Declare that program will need an include file produced by  
* the output of lex on base.l, which typically produces a file  
* named lex.yy.c which will be renamed as base.c. Besides, the  
* lexical analyzer needs the file parser.h produced by running  
* parser.y through yacc and renaming y.tab.h as parser.h.  
*/
```

```
#define NormalLexDependTarget(program,base,parser)  
@!  
base.o: parser.h @!  
@!  
SimpleLexTarget(program,base)
```

```
/*  
* IdentifiedLexDependTarget:  
* Declare that program will need an include file produced by  
* the output of lex on base.l, which typically produces a file  
* named lex.yy.c which will be renamed as base.c. Besides, the  
* lexical analyzer needs the file parser.h produced by running  
* parser.y through yacc and renaming y.tab.h as parser.h.  
* The lexical analyzer is identified with the supplied prefix,  
* which replaces the regular 'yy' prefix in the symbol names.  
*/
```

```
#define IdentifiedLexDependTarget(program,base,parser,prefix) @!  
base.o: parser.h @!  
@!  
IdentifiedLexTarget(program,base,prefix)
```

```
/*  
* NormalParserTarget:  
* Specify that program is using the lex/yacc combination to  
* produce a parser. The lexic and parser parameters are the  
* base name of the .l and .y file, respectively.  
*/  
#define NormalParserTarget(program,lexic,parser) @!  
NormalLexDependTarget(program,lexic,parser)
```

@!\

NormalYaccTarget(program,parser)

/*

* IdentifiedParserTarget:

* Specify that program is using the lex/yacc combination to

* produce a parser. The lexic and parser parameters are the

* base name of the .l and .y file, respectively. The parser

* produced is identified via its prefix, which replaces all

* the normally supplied 'yy' prefix, hence making it possible

* to have multiple parsers in a single executable.

*/

#define IdentifiedParserTarget(program,lexic,parser,prefix) @!\

IdentifiedLexDependTarget(program,lexic,parser,prefix) @!\

IdentifiedYaccTarget(program,parser,prefix)

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/files/Jmake.rules

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: i_gdbm.U 1 2006-08-24 12:32:52Z rmanfredi \$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic Licence,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic Licence; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: i_gdbm.U,v \$

?RCS: Revision 3.0.1.1 1995/05/12 12:16:39 ram

?RCS: patch54: made more robust by checking both header and lib (ADO)

?RCS:

?RCS: Revision 3.0 1993/08/18 12:08:19 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?MAKE:i_gdbm: Inhdr Inlibc Setvar

?MAKE: -pick add \$@ %<

?S:i_gdbm (d_gdbm):

?S: This variable conditionally defines the I_GDBM symbol, which

?S: indicates to the C program that <gdbm.h> exists and should

?S: be included.

?S:.

?C:I_GDBM

(HAS_GDBM):

?C: This symbol, if defined, indicates that <gdbm.h> exists and should

?C: be included.

?C:.

?H:#\$i_gdbm I_GDBM /**/

?H:.

?T:t_gdbm d_gdbm_open

?LINT:set i_gdbm

: see if gdbm.h is available

?X: t_gdbm is a tentative check. We might just have the .h, not the lib -- ADO

set gdbm.h t_gdbm

eval \$inhdr

case "\$t_gdbm" in

\$define)

: see if gdbm_open exists

set gdbm_open d_gdbm_open

eval \$inlibc

case "\$d_gdbm_open" in

\$undef)

t_gdbm="\$undef"

echo "We won't be including <gdbm.h>"

::

esac

::

esac

val="\$t_gdbm"

set i_gdbm

eval \$setvar

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/i_gdbm.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1999 Jarkko Hietaniemi

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?MAKE:usemorebits: Setvar

?MAKE: -pick add \$@ %<

?Y:TOP

?S:usemorebits:

?S: This variable conditionally defines the USE_MORE_BITS symbol,

?S: and indicates that explicit 64-bit interfaces and long doubles

?S: should be used when available.

```

?S:.
?C:USE_MORE_BITS:
?C: This symbol, if defined, indicates that 64-bit interfaces and
?C: long doubles should be used when available.
?C:.
?H:??<:#ifndef USE_MORE_BITS
?H:??<:#$usemorebits USE_MORE_BITS /**/
?H:??<:#endif
?H:.
?LINT:extern use64bitint
?LINT:change use64bitint
?LINT:extern uselongdouble
?LINT:change uselongdouble
: Check if morebits is requested
case "$usemorebits" in
"$define"|true|[yY]*)
use64bitint="$define"
uselongdouble="$define"
usemorebits="$define"
;;
*) usemorebits="$undef"
;;
esac

```

Found

in path(s):

```

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/perl/usemorebits.U

```

No license file was found, but licenses were detected in source scan.

```

?RCS: $Id: vendorbin.U,v 1.1 1999/07/08 18:32:57 doughera Exp doughera $

```

```

?RCS:

```

```

?RCS: Copyright (c) 1999, Andy Dougherty

```

```

?RCS:

```

```

?RCS: You may redistribute only under the terms of the Artistic License,

```

```

?RCS: as specified in the README file that comes with the distribution.

```

```

?RCS: You may reuse parts of this distribution only within the terms of

```

```

?RCS: that same Artistic License; a copy of which may be found at the root

```

```

?RCS: of the source tree for dist 3.0.

```

```

?RCS:

```

```

?RCS: $Log: vendorbin.U,v $

```

```

?RCS: Revision 1.1 1999/07/08 18:32:57 doughera

```

```

?RCS: Initial revision

```

```

?RCS:

```

```

?MAKE:d_vendorbin vendorbin vendorbinexp installvendorbin: Getfile \

```

```

Setprefixvar Oldconfig Prefixit vendorprefix

```

```

?MAKE: -pick add $@ %<

```

```

?Y:TOP

```

?S:vendorbin:
 ?S: This variable contains the eventual value of the VENDORBIN symbol.
 ?S: It may have a ~ on the front.
 ?S: The standard distribution will put nothing in this directory.
 ?S: Vendors who distribute perl
 may wish to place additional
 ?S: binaries in this directory with
 ?S: MakeMaker Makefile.PL INSTALLDIRS=vendor
 ?S: or equivalent. See INSTALL for details.
 ?S:.
 ?S:vendorbinexp:
 ?S: This variable is the ~name expanded version of vendorbin, so that you
 ?S: may use it directly in Makefiles or shell scripts.
 ?S:.
 ?D:installvendorbin="
 ?S:installvendorbin:
 ?S: This variable is really the same as vendorbinexp but may differ on
 ?S: those systems using AFS. For extra portability, only this variable
 ?S: should be used in makefiles.
 ?S:.
 ?S:d_vendorbin:
 ?S: This variable conditionally defines PERL_VENDORBIN.
 ?S:.
 ?C:PERL_VENDORBIN:
 ?C: If defined, this symbol contains the name of a directory
 ?C: for holding vendor-supplied executables.
 ?C: It may have a ~ on the front.
 ?C: The standard distribution will put nothing in this directory.
 ?C: Vendors who distribute perl may wish to place additional
 ?C: binaries in this directory with
 ?C: MakeMaker Makefile.PL INSTALLDIRS=vendor
 ?C: or equivalent.
 See INSTALL for details.
 ?C:.
 ?C:PERL_VENDORBIN_EXP:
 ?C: This symbol contains the ~name expanded version of VENDORBIN, to be used
 ?C: in programs that are not prepared to deal with ~ expansion at run-time.
 ?C:.
 ?H:#\$d_vendorbin PERL_VENDORBIN "\$vendorbin" /**/
 ?H:#\$d_vendorbin PERL_VENDORBIN_EXP "\$vendorbinexp" /**/
 ?H:.
 ?LINT:change prefixvar
 ?LINT:set installvendorbin
 : Set the vendorbin variables
 case "\$vendorprefix" in
 ") d_vendorbin="\$undef"
 vendorbin="
 vendorbinexp="

```

;;
*) d_vendorbin="$define"
: determine where vendor-supplied executables go.
case "$vendorbin" in
") dflt=$vendorprefix/bin ;;
*) dflt="$vendorbin" ;;
esac
fn=d~+
rp='Pathname for the vendor-supplied executables directory?'
./getfile
vendorbin="$ans"
vendorbinexp="$ansexp"
;;
esac
prefixvar=vendorbin
./installprefix

```

Found in path(s):

```

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/installdirs/vendorbin.U

```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1999, Jarkko Hietaniemi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 3.0.

?RCS:

?MAKE:d_sched_getparam: Inlibc

?MAKE: -pick add \$@ %<

?S:d_sched_getparam:

?S: This variable conditionally defines HAS_SCHED_GETPARAM if

?S: sched_getparam() is available to get the scheduling parameters.

?S:.

?C:HAS_SCHED_GETPARAM:

?C: This symbol, if defined, indicates that the sched_getparam

?C: system call is available to get the scheduling parameters.

?C:.

?H:#\$d_sched_getparam HAS_SCHED_GETPARAM /**/

?H:.

?LINT:set d_sched_getparam

: see if sched_getparam exists

set sched_getparam d_sched_getparam

eval \$inlibc

Found

in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_sched_getparam.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: Obsol_h.U 1 2006-08-24 12:32:52Z rmanfredi \$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic Licence,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic Licence; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: Obsol_h.U,v \$

?RCS: Revision 3.0 1993/08/18 12:05:11 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?X:

?X: This file is prepended to .MT/Obsol_h if that file is not empty. That file

?X: contains the necessary mappings of new symbols to obsolete ones.

?X:

?MAKE:Obsol_h:

?MAKE: -pick prepend \$@ ./Obsol_h

?LINT:nocomment

/*

* The following symbols are obsolete. They are mapped to the the new

* symbols only to ease the transition process. The

sources should be

* updated so as to use the new symbols only, as the support for these

* obsolete symbols may end without notice.

*/

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/Obsol_h.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: i_mntent.U,v \$

?RCS:

?RCS: Copyright (c) 1999 Jarkko Hietaniemi

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?MAKE:i_mntent: Inhdr Hasfield
?MAKE: -pick add \$@ %<
?S:i_mntent:
?S: This variable conditionally defines the I_MNTENT symbol, and indicates
?S: whether a C program should include <mntent.h>.
?S:.
?C:I_MNTENT:
?C: This symbol, if defined, indicates that <mntent.h> exists and
?C: should be included.
?C:.
?H:#\$i_mntent I_MNTENT /**/
?H:.
?LINT:set i_mntent
: see if this is a mntent.h system
set mntent.h i_mntent
eval \$inhdr

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/i_mntent.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_statblks.U,v 3.0 1993/08/18 12:07:29 ram Exp \$
?RCS:
?RCS: Copyright (c) 1991-1993, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 3.0.
?RCS:
?RCS: \$Log: d_statblks.U,v \$
?RCS: Revision 3.0 1993/08/18 12:07:29 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:d_statblks: Hasfield i_sysstat
?MAKE: -pick add \$@ %<
?S:d_statblks:
?S: This variable conditionally defines USE_STAT_BLOCKS
?S: if this system has a stat structure declaring
?S: st_blksize and st_blocks.
?S:.
?C:USE_STAT_BLOCKS (STATBLOCKS):
?C: This symbol is defined if this system has a stat structure declaring
?C: st_blksize and st_blocks.
?C:.
?H:?%<:#ifndef

USE_STAT_BLOCKS

```
?H:?%<:#$d_statblks USE_STAT_BLOCKS /**/
?H:?%<:#endif
?H:.
?LINT:set d_statblks
: see if stat knows about block sizes
echo " "
echo "Checking to see if your struct stat has st_blocks field..." >&4
set d_statblks stat st_blocks $i_sysstat sys/stat.h
eval $hasfield
```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/modified/d_statblks.U
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?MAKE:sysroot: Head

?MAKE: -pick add \$@ %<

?S:sysroot:

?S: This variable is empty unless supplied by the Configure user.

?S: It can contain a path to an alternative root directory, under which

?S: headers and libraries for the compilation target can be found. This

?S: is generally used when cross-compiling using a gcc-like compiler.

?S:.

?LINT:extern cc

?LINT:extern cppflags

?LINT:change cppflags

?LINT:extern ccflags

?LINT:change ccflags

?LINT:extern ldflags

?LINT:change ldflags

?LINT:extern cccdlflags

?X: _sysroot is later used in ccflags, but we do not want it in config.sh

?T:var xxx path _sysroot

: Set 'sysroot' to change the logical root directory to your headers and libraries see man gcc

: This is primarily meant for cross-compile environments, and

may fail to be useful in other cases

if test "X\$sysroot" = X; then

sysroot=""

else

case "\$cc" in

gcc|*g++*)

echo "Using \$sysroot to find your headers and libraries, adding to ccflags"

```

# _sysroot is used in places where we need --sysroot=foo
# but using the rest of the flags could cause issues.
_sysroot="--sysroot=$sysroot";
case "$ccflags" in
*sysroot*) ;;
'undef'|*)
ccflags="$ccflags $_sysroot"
esac
case "$ldflags" in
*sysroot*) ;;
'undef'|*)
ldflags="$ldflags $_sysroot"
esac
case "$cppflags" in
*sysroot*) ;;
'undef'|*)
cppflags="$cppflags $_sysroot"
esac
# lddflags updated below in lddflags section;
# same with cccdlflags
;;
esac

# Adjust some defaults to also use $sysroot
for var in xlibpth loclibpth locincpth glibpth; do
eval xxx=\$$var
eval $var="
for path in $xxx; do
eval $var="\$$var $sysroot$path\"
done
done
fi

```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/Sysroot.U
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1996, Andy Dougherty

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: man1dir.U,v \$

?RCS: Revision 3.0.1.1 1997/02/28 16:10:29 ram

?RCS: patch61: created

?RCS:

?X:

?X: This was originally specific to perl5. Since perl5 has man pages that

?X: go in both man1/ and man3/ directories, we need both man1dir

?X: and man3dir. This unit is basically dist's mansrc.U with

?X: man1 used instead of man everywhere.

?X:

?MAKE:man1dir man1direxp man1ext installman1dir: afs cat nroff Loc Oldconfig \
 spackage test Getfile Prefixit prefixexp
 Prefixup sysman Myread

?MAKE: -pick add \$@ %<

?Y:TOP

?S:man1dir:

?S: This variable contains the name of the directory in which manual

?S: source pages are to be put. It is the responsibility of the

?S: Makefile.SH to get the value of this into the proper command.

?S: You must be prepared to do the ~name expansion yourself.

?S:.

?S:man1direxp:

?S: This variable is the same as the man1dir variable, but is filename

?S: expanded at configuration time, for convenient use in makefiles.

?S:.

?S:installman1dir:

?S: This variable is really the same as man1direxp, unless you are using

?S: AFS in which case it points to the read/write location whereas

?S: man1direxp only points to the read-only access location. For extra

?S: portability, you should only use this variable within your makefiles.

?S:.

?S:man1ext:

?S: This variable contains the extension that the manual page should

?S: have: one of 'n', 'l', or '1'. The Makefile must supply the '.'.

?S: See man1dir.

?S:.

?T:lookpath

: determine

where manual pages go

set man1dir man1dir none

eval \$prefixit

\$cat <<EOM

\$spackage has manual pages available in source form.

EOM

case "\$nroff" in

```

nroff)
echo "However, you don't have nroff, so they're probably useless to you."
case "$man1dir" in
") man1dir="none";;
esac;;
esac
echo "If you don't want the manual sources installed, answer 'none'."
case "$man1dir" in
') dflt=none
;;
")
lookpath="$prefixexp/man/man1 $prefixexp/man/l_man/man1"
lookpath="$lookpath $prefixexp/man/p_man/man1"
lookpath="$lookpath $prefixexp/man/u_man/man1"
lookpath="$lookpath $prefixexp/man/man.1"
?X: Experience has shown people expect man1dir to be under prefix,
?X: so we now always put it there. Users who want other behavior
?X: can answer interactively or use a command line option.
?X: Does user have System V-style man paths.
case "$sysman" in
*/?_man*) dflt=`./loc . $prefixexp/l_man/man1 $lookpath` ;;
*) dflt=`./loc . $prefixexp/man/man1 $lookpath` ;;
esac
set dflt
eval $prefixup
;;
*)
dflt="$man1dir"
;;
esac
echo " "
fn=dn+~
rp="Where do the main $spackage manual pages (source) go?"
./getfile
if $stest "X$man1direxp" != "X$ansexp"; then
installman1dir="
fi
man1dir="$sans"
man1direxp="$ansexp"
case "$man1dir" in
") man1dir=' '
installman1dir="";;
esac
if $afs; then
$cat <<EOM

```

Since you are running AFS, I need to distinguish the directory in which manual pages reside from the directory in which they are installed (and from

which they are presumably copied to the former directory by occult means).

EOM

```
case "$installman1dir" in
") dflt=`echo $man1direxp | sed 's#^/afs/#/afs/.#`;;
*) dflt="$installman1dir";;
esac
fn=de~
rp='Where will man pages be installed?'
./getfile
installman1dir="$ans"
else
installman1dir="$man1direxp"
fi
```

: What suffix to use on installed man pages

```
case "$man1dir" in
')
man1ext='0'
;;
*)
rp="What suffix should be used for the main $spackage man pages?"
case "$man1ext" in
") case "$man1dir" in
*1) dflt=1 ;;
*1p)
dflt=1p ;;
*1pm) dflt=1pm ;;
*1) dflt=1;;
*n) dflt=n;;
*o) dflt=o;;
*p) dflt=p;;
*C) dflt=C;;
*L) dflt=L;;
*L1) dflt=L1;;
*) dflt=1;;
esac
;;
*) dflt="$man1ext";;
esac
./myread
man1ext="$ans"
;;
esac
```

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-

debian-perl-5.26.1/dist/U/man1dir.U

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: d_truncate.U 1 2006-08-24 12:32:52Z rmanfredi $
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: $Log: d_truncate.U,v $
?RCS: Revision 3.0 1993/08/18 12:07:48 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:d_truncate: Inlibc
?MAKE: -pick add $@ %<
?S:d_truncate:
?S: This variable conditionally defines HAS_TRUNCATE if truncate() is
?S: available to truncate files.
?S:.
?C:HAS_TRUNCATE (TRUNCATE):
?C: This symbol, if defined, indicates that the truncate routine is
?C: available to truncate files.
?C:.
?H:#$d_truncate HAS_TRUNCATE /**/
?H:.
?LINT:set
d_truncate
: see if truncate exists
set truncate d_truncate
eval $inlibc
```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/d_truncate.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: vendorhtml1dir.U,v 1.1 1999/07/08 18:32:57 doughera Exp doughera $
?RCS:
?RCS: Copyright (c) 1999, Andy Dougherty
?RCS:
?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
```

?RCS: of the source tree for dist 3.0.

?RCS:

?RCS: \$Log: vendorhtml1dir.U,v \$

?RCS: Revision 1.1 1999/07/08 18:32:57 doughera

?RCS: Initial revision

?RCS:

?MAKE:vendorhtml1dir vendorhtml1direxp installvendorhtml1dir: html1dir Getfile \
 Setprefixvar Oldconfig Prefixit test vendorprefix prefix sed

?MAKE: -pick add \$@ %<

?Y:TOP

?S:vendorhtml1dir:

?S: This variable contains the name of the directory for html

?S: pages. It may have a ~ on the front.

?S: The standard distribution will put nothing in this

directory.

?S: Vendors who distribute perl may wish to place their own

?S: html pages in this directory with

?S: MakeMaker Makefile.PL INSTALLDIRS=vendor

?S: or equivalent. See INSTALL for details.

?S:.

?S:vendorhtml1direxp:

?S: This variable is the ~name expanded version of vendorhtml1dir, so that you

?S: may use it directly in Makefiles or shell scripts.

?S:.

?D:installvendorhtml1dir="

?S:installvendorhtml1dir:

?S: This variable is really the same as vendorhtml1direxp but may differ on

?S: those systems using AFS. For extra portability, only this variable

?S: should be used in makefiles.

?S:.

?LINT:change prefixvar

?LINT:set installvendorhtml1dir

: Set the vendorhtml1dir variables

case "\$vendorprefix" in

) vendorhtml1dir="

vendorhtml1direxp="

;;

*) : determine where vendor-supplied html pages go.

: There is no standard location, so try to copy the previously-selected

: directory structure for the core html pages.

: XXX Better default suggestions would be welcome.

case "\$vendorhtml1dir"

in

) dflt=`echo "\$html1dir" | \$sed "s#^\$prefix#\$vendorprefix#"` ;;

*) dflt=\$vendorhtml1dir ;;

esac

case "\$dflt" in

"| ") dflt=none ;;

```

esac
fn=dn+~
rp='Pathname for the vendor-supplied html pages?'
./getfile
vendorhtml1dir="$ans"
vendorhtml1direxp="$ansexp"
;;
esac
: Use ' ' for none so value is preserved next time through Configure
$test X"$vendorhtml1dir" = "X" && vendorhtml1dir=' '
prefixvar=vendorhtml1dir
./installprefix

```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/installdirs/vendorhtml1dir.U
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: i_varhdr.U,v \$

?RCS: Revision 3.0.1.3 1997/02/28 15:54:42 ram

?RCS: patch61: varargs script now starts with leading "startsh"

?RCS:

?RCS: Revision 3.0.1.2 1994/10/29 16:21:02 ram

?RCS: patch36: added ?F: line for metalint file checking

?RCS:

?RCS: Revision 3.0.1.1 1994/05/13 15:26:05 ram

?RCS: patch27: this unit now supersedes old i_stdarg.U and i_varargs.U

?RCS: patch27: modified to avoid spurious Whoa warnings (ADO)

?RCS:

?RCS: Revision 3.0 1993/08/18 12:08:49 ram

?RCS: Baseline for

dist 3.0 netwide release.

?RCS:

?MAKE:i_stdarg i_varargs i_varhdr: cat +cc +ccflags rm test Setvar \

Findhdr Warn startsh _o

?MAKE: -pick add \$@ %<

?S:i_stdarg:

?S: This variable conditionally defines the I_STDARG symbol, which

?S: indicates to the C program that <stdarg.h> exists and should
?S: be included.

?S:.

?S:i_varargs:
?S: This variable conditionally defines I_VARARGS, which indicates
?S: to the C program that it should include <varargs.h>.

?S:.

?S:i_varhdr:
?S: Contains the name of the header to be included to get va_dcl definition.
?S: Typically one of varargs.h or stdarg.h.

?S:.

?C:I_STDARG:
?C: This symbol, if defined, indicates that <stdarg.h> exists and should
?C: be included.

?C:.

?C:I_VARARGS:
?C: This symbol, if defined, indicates to the C program that it should
?C: include <varargs.h>.

?C:.

?H:#\$i_stdarg I_STDARG /**/
?H:#\$i_varargs I_VARARGS /**/
?H:.

?W:%<:va_dcl
?F:!varargs
?T:valstd
?LINT:set i_stdarg i_varargs
?X:
?X: Don't use setvar because the varargs test
below might override these.
?X: Actually, the messages here are just informative. We don't wish to set
?X: i_varargs or i_stdarg to their final value before knowing which of the
?X: two we'll include.
?X:
: see if stdarg is available
echo " "
if \$test `./findhdr stdarg.h`; then
echo "<stdarg.h> found." >&4
valstd="\$define"
else
echo "<stdarg.h> NOT found." >&4
valstd="\$undef"
fi

: see if varargs is available
echo " "
if \$test `./findhdr varargs.h`; then
echo "<varargs.h> found." >&4
else

```
echo "<varargs.h> NOT found, but that's ok (I hope)." >&4
fi
```

?X:

?X: if you have stdarg.h, you need to support prototypes to actually use it;

?X: but if stdarg.h exists and the compiler doesn't support prototypes (for some

?X: bizarre reason), we'll fall back to varargs.h anyway so it's not so bad.

?X:

: set up the varargs testing programs

```
$cat > varargs.c <<EOP
```

```
#ifdef I_STDARG
```

```
#include <stdarg.h>
```

```
#endif
```

```
#ifdef I_VARARGS
```

```
#include <varargs.h>
```

```
#endif
```

```
#ifdef I_STDARG
```

```
int f(char *p, ...)
```

```
#else
```

```
int
```

```
  f(va_alist)
```

```
  va_dcl
```

```
#endif
```

```
{
```

```
  va_list ap;
```

```
#ifndef I_STDARG
```

```
  char *p;
```

```
#endif
```

```
#ifdef I_STDARG
```

```
  va_start(ap,p);
```

```
#else
```

```
  va_start(ap);
```

```
  p = va_arg(ap, char *);
```

```
#endif
```

```
  va_end(ap);
```

```
}
```

```
EOP
```

```
$cat > varargs <<EOP
```

```
$startsh
```

```
if $cc -c $ccflags -D\${1} varargs.c >/dev/null 2>&1; then
```

```
  echo "true"
```

```
else
```

```
  echo "false"
```

```
fi
```

```
$rm -f varargs$_o
```

```
EOP
```

```
chmod +x varargs
```

```

: now check which varargs header should be included
echo " "
i_varhdr="
case "$valstd" in
"$define")
if `./varargs I_STDARG`; then
val='stdarg.h'
elif `./varargs I_VARARGS`; then
val='varargs.h'
fi
;;
*)
if `./varargs I_VARARGS`; then
val='varargs.h'
fi
;;
esac
case "$val" in
")
./warn "I could not find the definition for va_dcl... You have problems..."
val="$undef"; set i_stdarg; eval $setvar
val="$undef"; set i_varargs; eval $setvar
;;
*)
set i_varhdr
eval $setvar
case "$i_varhdr" in
stdarg.h)
val="$define"; set i_stdarg; eval $setvar
val="$undef"; set i_varargs; eval $setvar
;;
varargs.h)
val="$undef"; set i_stdarg;
eval $setvar
val="$define"; set i_varargs; eval $setvar
;;
esac
echo "We'll include <$i_varhdr> to get va_dcl definition." >&4;;
esac
$rm -f varargs*

```

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/i_varhdr.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:
 ?RCS: Copyright (c) 2001 Jarkko Hietaniemi
 ?RCS:
 ?RCS: You may distribute under the terms of either the GNU General Public
 ?RCS: License or the Artistic License, as specified in the README file.
 ?RCS:
 ?MAKE:d_realpath: Inlibc
 ?MAKE: -pick add \$@ %<
 ?S:d_realpath:
 ?S: This variable conditionally defines the HAS_REALPATH symbol, which
 ?S: indicates to the C program that the realpath() routine is available.
 ?S:.
 ?C:HAS_REALPATH:
 ?C: This symbol, if defined, indicates that the realpath routine is
 ?C: available to do resolve paths.
 ?C:.
 ?H:#\$d_realpath HAS_REALPATH /**/
 ?H:.
 ?LINT:set d_realpath
 : see if realpath exists
 set realpath d_realpath
 eval \$inlibc

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_realpath.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: Prefixit.U 1 2006-08-24 12:32:52Z rmanfredi \$
 ?RCS:
 ?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
 ?RCS:
 ?RCS: You may redistribute only under the terms of the Artistic Licence,
 ?RCS: as specified in the README file that comes with the distribution.
 ?RCS: You may reuse parts of this distribution only within the terms of
 ?RCS: that same Artistic Licence; a copy of which may be found at the root
 ?RCS: of the source tree for dist 4.0.
 ?RCS:
 ?RCS: \$Log: Prefixit.U,v \$
 ?RCS: Revision 3.0.1.1 1995/01/30 14:29:22 ram
 ?RCS: patch49: created
 ?RCS:
 ?X:
 ?X: Used as: "set dflt var dir; eval \$prefixit" to set \$dflt to be
 ?X: \$prefix/dir by default, or the previous \$var depending on certain
 ?X: conditions:
 ?X: - If the \$oldprefix variable is empty, then \$prefix holds the same
 ?X: value as on previous runs. Therefore, reuse \$var if set, otherwise

```

?X: set $dflt to $prefix/dir.
?X: - If $oldprefix is not
empty, then set $dflt to $prefix/dir if $var
?X: is empty (first run). Otherwise, if $var is $oldprefix/dir, then
?X: change it to $prefix/dir. If none of the above, reuse the old $var.
?X:
?X: When dir is omitted, the dflt variable is set to $var if prefix did not
?X: change, to an empty value otherwise. If dir=none, then a single space
?X: in var is kept as-is, even if the prefix changes.
?X:
?MAKE:Prefixit: prefix oldprefix
?MAKE: -pick add $@ %<
?LINT:define prefixit
?S:prefixit:
?S: This shell variable is used internally by Configure to reset
?S: the leading installation prefix correctly when it is changed.
?S: set dflt var [dir]
?S: eval $prefixit
?S: That will set $dflt to $var or $prefix/dir depending on the
?S: value of $var and $oldprefix.
?S:.
?V:prefixit
?T:tp
: set the prefixit variable, to compute a suitable default value
prefixit='case "$3" in
""|none)
case "$oldprefix" in
"" ) eval "$1=\"\$$2\"";;
*)
case "$3" in
"" ) eval "$1=";;
none)
eval "tp=\"\$$2\"";
case
"$tp" in
""|" ") eval "$1=\"\$$2\"";;
*) eval "$1=";;
esac;;
esac;;
esac;;
*)
eval "tp=\"$oldprefix-\$$2-\""; eval "tp=\"$tp\"";
case "$tp" in
-/*-|\~*--) eval "$1=\"$prefix/$3\"";;
/*-$oldprefix/*|\~*-$oldprefix/*)
eval "$1=\"echo \$$2 | sed \"s,^$oldprefix,$prefix,\"\"";;
*) eval "$1=\"\$$2\"";;
esac;;

```

esac'

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/Prefixit.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: Config_h.U 1 2006-08-24 12:32:52Z rmanfredi \$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: Config_h.U,v \$

?RCS: Revision 3.0.1.5 1997/02/28 14:57:43 ram

?RCS: patch61: added support for src.U

?RCS:

?RCS: Revision 3.0.1.4 1995/09/25 09:10:49 ram

?RCS: patch59: commented the purpose of the #un-def directive

?RCS:

?RCS: Revision 3.0.1.3 1995/01/30 14:25:39 ram

?RCS: patch49: typo fixes in leading config.h comment (WED)

?RCS:

?RCS: Revision 3.0.1.2 1993/08/24 12:13:20 ram

?RCS: patch3: added TOP as a local shell temporary variable

?RCS:

?RCS:

Revision 3.0.1.1 1993/08/19 06:42:20 ram

?RCS: patch1: leading config.sh searching was not aborting properly

?RCS:

?RCS: Revision 3.0 1993/08/18 12:04:47 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?X:

?X: This file ends up producing the config_h.SH script, which is run to produce

?X: the config.h file. The file ./Config_h below contains all the ?H: lines

?X: extracted out of all the units. Metaconfig itself adds the !GROK!THIS!.

?X: Note that this code isn't included into Configure, but must be shipped with.

?X:

?X: For those who wish to know why the file is config_h.SH instead of the more

?X: natural config.h.SH, well... it is to support systems like MS-DOG. Only one

?X: 'dot' is allowed within the file name, as it is part of the "extension" of

?X: the file. MS-DOG will not let you have two 'dots' because that would mean

?X: two "extensions".

```

?X:
?MAKE:Config_h: Id End Config_sh Obsol_h myuname cf_time cf_by package src
?MAKE: -pick c_h_weed $@ %<
?MAKE: -pick
c_h_weed $@ ./Config_h
?MAKE: -pick c_h_weed $@ ./Obsol_h
?T:PERL_CONFIG_SH TOP
?LINT:unclosed !GROK!THIS!
?LINT:extern CONFIG_H CONFIG_SH
?LINT:change CONFIG_H CONFIG_SH
?X:?LINT:nocomment
: Set up for generating config_h.SH
case "$CONFIG_SH" in
") CONFIG_SH=config.sh;;
esac
case "$CONFIG_H" in
") CONFIG_H=config.h;;
esac
case $PERL_CONFIG_SH in
")
if test -f $CONFIG_SH; then TOP=.;
elif test -f ../$CONFIG_SH; then TOP=..;
elif test -f ../../$CONFIG_SH; then TOP=../../;
elif test -f ../../../$CONFIG_SH; then TOP=../../../;
elif test -f ../../../../$CONFIG_SH; then TOP=../../../../;
else
echo "Can't find $CONFIG_SH."; exit 1
fi
. $TOP/$CONFIG_SH
;;
esac
?X: Make sure we are in the directory where the .SH file is located.
case "$0" in
*/*) cd `expr X$0 : 'X\(.*/\)'` ;;
esac
echo "Extracting $CONFIG_H (with variable substitutions)"
?X:
?X: Since we unconditionally translate leading #undef into /*#define, we're
?X: stuck when we really want to have a #undef in $CONFIG_H.
That's why there
?X: is provision here for #un-def, which is translated back into #undef after
?X: all original #undef have been processed.
?X:
?X: Previously, we changed all
?X: #undef FOO /**/
?X: into
?X: /*#define FOO /**/
?X: The xlc compiler (available on IBM's AIX) complains that this is

```

```

?X: an illegal attempt to write a nested comment, and warns against it.
?X: There's apparently no way to shut the compiler up, either.
?X: This sed command from Hallvard B Furuseth <h.b.furuseth@usit.uio.no>
?X: changes it to
?X: /*#define FOO / **/
sed <<!GROK!THIS! >$CONFIG_H -e 's!^#undef(.*^)\!/^##define\1 \!' -e 's!^#un-def!#undef!'
/* This file was produced by running the config_h.SH script, which
* gets its values from $CONFIG_SH, which is generally produced by
* running Configure.
*
* Feel free to modify any of this as the need arises. Note, however,
* that running config_h.SH again will wipe out any changes you've made.
* For a more permanent change edit $CONFIG_SH and
* rerun config_h.SH.
*/

/* Package name      : $package
* Source directory  : $src
* Configuration time: $cf_time
* Configured by     : $cf_by
* Target system     : $myuname
*/

```

```

#ifndef _config_h_
#define _config_h_

```

Found in path(s):

```

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/modified/Config_h.U

```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1999 Jarkko Hietaniemi

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

```

?MAKE:ivdformat uvuformat uvoformat uvxformat uvXUformat \
nvEUformat nvFUformat nvGUformat \
nveformat nvfformat nvgformat: \
ivsize longsize intsize shortsize \
sPRId64 sPRIu64 sPRIo64 sPRIx64 sPRIXU64 \
uselongdouble d_longdbl usequadmath d_PRIgldbl \
sPRIEUdbl sPRIFUdbl sPRIGUdbl sPRIeldbl sPRIfdbl sPRIgldbl \
test echo

```

?MAKE: -pick add \$@ %<

?S:ivdformat:

?S: This variable contains the format string used for printing
?S: a Perl IV as a signed decimal integer.
?S:.
?S:uvuformat:
?S: This variable contains the format string used for printing
?S: a Perl UV as an unsigned decimal integer.
?S:.
?S:uvoformat:
?S: This variable contains the format string used for printing
?S: a Perl UV as an unsigned
octal integer.
?S:.
?S:uvxformat:
?S: This variable contains the format string used for printing
?S: a Perl UV as an unsigned hexadecimal integer in lowercase abcdef.
?S:.
?S:uvXUformat:
?S: This variable contains the format string used for printing
?S: a Perl UV as an unsigned hexadecimal integer in uppercase ABCDEF.
?S:.
?S:nveformat:
?S: This variable contains the format string used for printing
?S: a Perl NV using %e-ish floating point format.
?S:.
?S:nvffformat:
?S: This variable contains the format string used for printing
?S: a Perl NV using %f-ish floating point format.
?S:.
?S:nvgformat:
?S: This variable contains the format string used for printing
?S: a Perl NV using %g-ish floating point format.
?S:.
?S:nvEUformat:
?S: This variable contains the format string used for printing
?S: a Perl NV using %E-ish floating point format.
?S:.
?S:nvFUformat:
?S: This variable contains the format string used for printing
?S: a Perl NV using %F-ish floating point format.
?S:.
?S:nvGUformat:
?S: This
variable contains the format string used for printing
?S: a Perl NV using %G-ish floating point format.
?S:.
?C:IVdf:
?C: This symbol defines the format string used for printing a Perl IV
?C: as a signed decimal integer.

?C:.

?C:UVuf:
?C: This symbol defines the format string used for printing a Perl UV
?C: as an unsigned decimal integer.

?C:.

?C:UVof:
?C: This symbol defines the format string used for printing a Perl UV
?C: as an unsigned octal integer.

?C:.

?C:UVxf:
?C: This symbol defines the format string used for printing a Perl UV
?C: as an unsigned hexadecimal integer in lowercase abcdef.

?C:.

?C:UVXf:
?C: This symbol defines the format string used for printing a Perl UV
?C: as an unsigned hexadecimal integer in uppercase ABCDEF.

?C:.

?C:NVef:
?C: This symbol defines the format string used for printing a Perl NV
?C: using %e-ish floating point format.

?C:.

?C:NVff:
?C: This symbol defines the format string used for printing a Perl NV
?C: using %f-ish floating point
format.

?C:.

?C:NVgf:
?C: This symbol defines the format string used for printing a Perl NV
?C: using %g-ish floating point format.

?C:.

?C:NVEf:
?C: This symbol defines the format string used for printing a Perl NV
?C: using %E-ish floating point format.

?C:.

?C:NVFf:
?C: This symbol defines the format string used for printing a Perl NV
?C: using %F-ish floating point format.

?C:.

?C:NVGf:
?C: This symbol defines the format string used for printing a Perl NV
?C: using %G-ish floating point format.

?C:.

?H:#define IVdf \$ivdformat /**/
?H:#define UVuf \$uvuformat /**/
?H:#define UVof \$uvoformat /**/
?H:#define UVxf \$uvxf format /**/
?H:#define UVXf \$uvXUformat /**/
?H:#define NVef \$nveformat /**/

```

?H:#define NVff $nvffformat /**/
?H:#define NVgf $nvgformat /**/
?H:#define NVEf $nvEUformat /**/
?H:#define NVFf $nvFUformat /**/
?H:#define NVGf $nvGUformat /**/
?H:.
: Check format strings for internal types
echo " "
$echo "Checking the format strings to be used for Perl's
internal types..." >&4

if $test X"$ivsize" = X8; then
ivdformat="$sPRId64"
uvuformat="$sPRIu64"
uvoformat="$sPRIo64"
uvxformat="$sPRIx64"
uvXUformat="$sPRIXU64"
else
if $test X"$ivsize" = X"$longsize"; then
ivdformat="ld"
uvuformat="lu"
uvoformat="lo"
uvxformat="lx"
uvXUformat="lX"
else
if $test X"$ivsize" = X"$intsize"; then
ivdformat="d"
uvuformat="u"
uvoformat="o"
uvxformat="x"
uvXUformat="X"
else
: far out
if $test X"$ivsize" = X"$shortsize"; then
ivdformat="hd"
uvuformat="hu"
uvoformat="ho"
uvxformat="hx"
uvXUformat="hX"
fi
fi
fi
fi

if $test X"$usequadmath" = X"$define"; then
nveformat="Qe"
nvffformat="Qf"
nvgformat="Qg"

```

```

    nvEUformat="QE"
    nvFUformat="QF"
    nvGUformat="QG"
else
    if $test X"$uselongdouble" = X"$define" -a X"$d_longdbl" = X"$define" -a X"$d_PRIgldbl" = X"$define"; then
    nveformat="$sPRIeldbl"
    nvffformat="$sPRIfldbl"
    nviformat="$sPRIgldbl"
    nvEUformat="$sPRIEUdbl"
    nvFUformat="$sPRIFUdbl"
    nvGUformat="$sPRIGUdbl"
    else
    nveformat="e"
    nvffformat="f"
    nviformat="g"
    nvEUformat="E"
    nvFUformat="F"
    nvGUformat="G"
    fi
fi

case "$ivdformat" in
") echo "$0: Fatal: failed to find format strings, cannot continue." >&4
    exit 1
    ;;
esac

```

Found in path(s):

```

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/perl/perlxf.U

```

No license file was found, but licenses were detected in source scan.

```

?RCS: $Id: d_bzero.U 1 2006-08-24 12:32:52Z rmanfredi $
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: $Log: d_bzero.U,v $
?RCS: Revision 3.0.1.2 1993/10/16 13:48:15 ram
?RCS: patch12: added magic support for bzero()
?RCS:
?RCS: Revision 3.0.1.1 1993/09/13 16:01:33 ram
?RCS: patch10: now only defines HAS_BZERO, no macro remap on memset (WAD)

```

?RCS:
?RCS: Revision 3.0 1993/08/18 12:05:46 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:d_bzero: Inlibc
?MAKE: -pick add \$@ %<
?S:d_bzero:
?S: This variable conditionally defines the HAS_BZERO
symbol if
?S: the bzero() routine is available to set memory to 0.
?S:.
?C:HAS_BZERO:
?C: This symbol is defined if the bzero() routine is available to
?C: set a memory block to 0.
?C:.
?H:#\$d_bzero HAS_BZERO /**/
?H:.
?M:bzero: HAS_BZERO
?M:#ifndef HAS_BZERO
?M:#ifndef bzero
?M:#define bzero(s,l) memset((s),0,(l))
?M:#endif
?M:#endif
?M:.
?LINT:set d_bzero
: see if bzero exists
set bzero d_bzero
eval \$inlibc

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/d_bzero.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_setgrent_r.U,v 0RCS:
?RCS: Copyright (c) 2002,2003 Jarkko Hietaniemi
?RCS:
?RCS: You may distribute under the terms of either the GNU General Public
?RCS: License or the Artistic License, as specified in the README file.
?RCS:
?RCS: Generated by the reentr.pl from the Perl 5.8 distribution.
?RCS:
?MAKE:d_setgrent_r setgrent_r_proto: Inlibc Protochk Hasproto i_systypes \
usethreads i_grp extern_C
?MAKE: -pick add \$@ %<
?S:d_setgrent_r:
?S: This variable conditionally defines the HAS_SETGRENT_R symbol,
?S: which indicates to the C program that the setgrent_r()

?S: routine is available.

?S:.

?S:setgrent_r_proto:

?S: This variable encodes the prototype of setgrent_r.

?S: It is zero if d_setgrent_r is undef, and one of the

?S: REENTRANT_PROTO_T_ABC macros of reentr.h if d_setgrent_r

?S: is defined.

?S:.

?C:HAS_SETGRENT_R:

?C: This symbol, if defined, indicates that the setgrent_r routine

?C: is available to

setgrent re-entrantly.

?C:.

?C:SETGRENT_R_PROTO:

?C: This symbol encodes the prototype of setgrent_r.

?C: It is zero if d_setgrent_r is undef, and one of the

?C: REENTRANT_PROTO_T_ABC macros of reentr.h if d_setgrent_r

?C: is defined.

?C:.

?H:#\$d_setgrent_r HAS_SETGRENT_R /**/

?H:#define SETGRENT_R_PROTO \$setgrent_r_proto /**/

?H:.

?T:try hdrs d_setgrent_r_proto

: see if setgrent_r exists

```
set setgrent_r d_setgrent_r
eval $inlibc
case "$d_setgrent_r" in
"$define")
hdrs="$i_systypes sys/types.h define stdio.h $i_grp grp.h"
case "$d_setgrent_r_proto:$usethreads" in
":define") d_setgrent_r_proto=define
set d_setgrent_r_proto setgrent_r $hdrs
eval $hasproto ;;
*) ;;
esac
case "$d_setgrent_r_proto" in
define)
case "$setgrent_r_proto" in
"|0) try='int setgrent_r(FILE**);'
./protochk "$extern_C $try" $hdrs && setgrent_r_proto=I_H ;;
esac
case "$setgrent_r_proto" in
"|0) try='void setgrent_r(FILE**);'
./protochk "$extern_C $try" $hdrs && setgrent_r_proto=V_H ;;
esac
case
"$setgrent_r_proto" in
"|0) d_setgrent_r=undef
```

```

    setgrent_r_proto=0
    echo "Disabling setgrent_r, cannot determine prototype." >&4 ;;
*) case "$setgrent_r_proto" in
    REENTRANT_PROTO*) ;;
*) setgrent_r_proto="REENTRANT_PROTO_$setgrent_r_proto" ;;
    esac
    echo "Prototype: $try" ;;
    esac
;;
*) case "$usetthreads" in
    define) echo "setgrent_r has no prototype, not using it." >&4 ;;
    esac
    d_setgrent_r=undef
    setgrent_r_proto=0
    ;;
    esac
;;
*) setgrent_r_proto=0
    ;;
    esac

```

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/threads/d_setgrent_r.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: Loc.U,v \$

?RCS: Revision 3.0.1.10 1997/02/28 15:04:16 ram

?RCS: patch61: allow users to specify paths on the command line

?RCS: patch61: will now substitute cp for ln if not supported

?RCS:

?RCS: Revision 3.0.1.9 1995/09/25 09:11:24 ram

?RCS: patch59: commented the purpose of the #un-def directive

?RCS: patch59: abort Configure run when mandatory command is missing

?RCS:

?RCS: Revision 3.0.1.8 1995/07/25 13:40:40 ram

?RCS: patch56: now knows about OS/2 platforms

?RCS:

?RCS: Revision 3.0.1.7
 1995/01/11 15:13:37 ram

?RCS: patch45: protected "sh -c" within backquotes for Linux and SGI

?RCS: patch45: added path lookup for the 'comm' program

?RCS:

?RCS: Revision 3.0.1.6 1994/10/29 15:56:14 ram

?RCS: patch36: added ?F: line for metalint file checking

?RCS: patch36: be careful and guard against wildcard searching (ADO)

?RCS:

?RCS: Revision 3.0.1.5 1994/06/20 06:54:55 ram

?RCS: patch30: now locates find

?RCS:

?RCS: Revision 3.0.1.4 1994/05/13 15:18:15 ram

?RCS: patch27: added yacc to the trylist (ADO)

?RCS: patch27: lint lines reformatted (ADO)

?RCS:

?RCS: Revision 3.0.1.3 1994/01/24 14:01:44 ram

?RCS: patch16: added metalint hint on changed PATH variable

?RCS:

?RCS: Revision 3.0.1.2 1993/12/15 08:16:52 ram

?RCS: patch15: now set _test variable when test is built-in

?RCS: patch15: fixed rare cases where echo is not needed

?RCS:

?RCS: Revision 3.0.1.1 1993/09/13 15:47:13 ram

?RCS: patch10: test program not always in /bin/test (WAD)

?RCS:

?RCS: Revision
 3.0 1993/08/18 12:05:05 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?X:

?X: This unit produces a shell script "loc" which can be used to find out
 ?X: where in a list of directories something is. It then uses loc to
 ?X: determine the location of commonly used programs. It leaves loc sitting
 ?X: around for other Configure units to use, but arranges for its demise
 ?X: at the end of Configure.

?X:

?X: To add a new program to find, add it both to the ?MAKE: line and to either
 ?X: the loclist or trylist variable.

?X:

?X: I put startsh at the end of the dependency list, in order to avoid the
 ?X: loading of the spitshell unit before the instructions.

?X:

?MAKE:Loc awk ar bash bison yacc cat chgrp chmod chown \
 comm compress cp cpio cpp csh date echo egrep emacs expr find flex \
 gmake gzip grep inews ksh less line lint ln lp lpr ls mail mailx \
 make mkdir more mv nm nroff perl pg pmake pr rm rmail sed sendmail \
 shar sleep smail sort submit tail tar tbl tee test touch tr troff

```

\
uname uniq uuname vi zcat zip: eunicefix n c startsh Instruct Warn
?MAKE: -pick weed $@ %<
?LINT:describe awk ar bash bison byacc cat chgrp chmod chown \
comm compress cp cpio cpp csh date echo egrep emacs expr find flex \
gmake gzip grep inews ksh less line lint ln lp lpr ls mail mailx \
make mkdir more mv nm nroff perl pg pmake pr rm rmail sed sendmail \
shar sleep smail sort submit tail tar tbl tee test touch tr troff \
uname uniq uuname vi zcat zip
?V::pth loclist trylist
?F:./loc
?T:thisthing thing xxx dir file say DJGPP
?T:_test _grep _cp _gmake _egrep _ln _make dflt
?LINT: change PATH
: find out where common programs are
echo " "
echo "Locating common programs..." >&4
cat <<EOOSC >loc
$startsh
case $# in
0) exit 1;;
esac
thing=${1}
shift
dflt=${1}
shift
for dir in \*; do
case "\$thing" in
.)
if test -d \$dir/\$thing; then
echo \$dir
exit 0
fi
;;
*)
?X: Be careful in case thing includes wildcards that might expand to multiple
?X: files. Choose the last one.
This happens when searching for shared
?X: libraries with version numbers. How to choose which one we want is
?X: probably an insoluble problem, in general.
?X: Some folks leave things like libc.so.orig around w/o read
?X: permission. A -r test would handle that, but since ./loc is
?X: also used to find executables (which are installed w/o read
?X: permission on SCO ODT 3.0, we can't include the -r test.
for thisthing in \$dir/\$thing; do
: just loop through to pick last item
done
if test -f \$thisthing; then

```

```
echo \$thisthing
exit 0
elif test -f \$thisthing$_exe; then
echo \$thisthing
exit 0
elif test -f \$dir/\$thing.exe; then
if test -n "$DJGPP"; then
echo \$dir/\$thing.exe
else
: on Eunice apparently
echo \$dir/\$thing
fi
exit 0
fi
;;
esac
done
echo \$dflt
exit 1
EOSC
chmod +x loc
$eunicefix loc
loclist="
?awk:awk
?cat:cat
?chgrp:chgrp
?chmod:chmod
?chown:chown
?comm:comm
?cp:cp
?echo:echo
?expr:expr
?find:find
?grep:grep
?ls:ls
?mkdir:mkdir
?mv:mv
?rm:rm
?sed:sed
?sleep:sleep
?sort:sort
?tail:tail
?touch:touch
?tr:tr
?uniq:uniq
"
trylist="
?Mcc:Mcc
```

?ar:ar
?bash:bash
?bison:bison
?byacc:byacc
?compress:compress
?cpio:cpio
?cpp:cpp
?csh:csh
?date:date
?egrep:egrep
?emacs:emacs
?flex:flex
?gmake:gmake
?gzip:gzip
?inews:inews
?ksh:ksh
?less:less
?line:line
?lint:lint
?ln:ln
?lp:lp
?lpr:lpr
?mail:mail
?mailx:mailx
?make:make
?more:more
?nm:nm
?nroff:nroff
?perl:perl
?pg:pg
?pmake:pmake
?pr:pr
?rmail:rmail
?sendmail:sendmail
?shar:shar
?smail:smail
?submit:submit
?tar:tar
?tbl:tbl
?tee:tee
?test:test
?troff:troff
?uname:uname
?uname:uname
?vi:vi
?zcat:zcat
?zip:zip
"

```

?LINT:set
awk ar bash bison byacc cat chgrp chmod chown \
comm compress cp cpio cpp csh date echo emacs expr find flex \
gmake gzip grep inews ksh less line lint lp lpr ls mail mailx \
mkdir more mv nm nroff perl pg pmake pr rm rmail sed sendmail \
shar sleep smail sort submit tail tar tbl tee touch tr troff \
uname uniq uuname vi zcat zip
pth=`echo $PATH | sed
-e "s/$p_/ /g"`
pth="$pth /lib /usr/lib"
for file in $loclist; do
?X:
?X: Allow them to -Dmake=pmake on the command line for instance...
?X: If the file is not fully qualified, as in -Dmake=pmake, then we
?X: look the for the specified command (pmake here). If they say
?X: -Dmake=/sbin/make for instance, then we make sure the file
?X: exists, or we die...
?X:
eval xxx=\$$file
case "$xxx" in
/*|?:[\\]*)
if test -f "$xxx"; then
: ok
else
./warn "no $xxx -- ignoring your setting for $file."
xxx=`./loc $file $file $pth`
fi
;;
*) xxx=`./loc $file $file $pth`;
*) xxx=`./loc $xxx $xxx $pth`;
esac
eval $file=$xxx$_exe
eval _$file=$xxx
case "$xxx" in
/*)
echo $file is in $xxx.
;;
?X: Under OS/2, we have PC-like paths
?:[\\]*)
echo $file is in $xxx.
;;
*)
echo "I don't know where '$file' is, and my life depends on it." >&4
echo "Go find a public domain implementation or fix your PATH setting!" >&4
exit 1
;;
esac
done

```

```

echo " "
echo "Don't worry
if any of the following aren't found..."
say=offhand
for file in $trylist; do
?X: Allow them to -Dmake=pmake on the command line for instance (see above)
eval xxx=\$$file
case "$xxx" in
/*|?:[\\]*)
if test -f "$xxx"; then
: ok
else
./warn "no $xxx -- ignoring your setting for $file."
xxx=`./loc $file $file $pth`
fi
;;
") xxx=`./loc $file $file $pth`;
*) xxx=`./loc $xxx $xxx $pth`;
esac
eval $file=$xxx$_exe
eval _$file=$xxx
case "$xxx" in
/*)
echo $file is in $xxx.
;;
?X: Under OS/2, we have PC-like paths
?:[\\]*)
echo $file is in $xxx.
;;
*)
echo "I don't see $file out there, $say."
say=either
;;
esac
done
case "$egrep" in
egrep)
echo "Substituting grep for egrep."
egrep=$grep
_egrep=$_grep
;;
esac
@if ln
case "$ln" in
ln)
echo "Substituting cp for ln."
ln=$cp
_ln=$_cp

```

```

;;
esac
@end
@if make || gmake
case "$make" in
make)
case "$gmake" in
gmake)
echo "I can't find make or gmake, and my life depends on it." >&4
echo "Go find a
public domain implementation or fix your PATH setting!" >&4
exit 1
;;
esac
;;
esac
case "$gmake" in
gmake) ;;
*) # We can't have osname yet.
if test -f "/system/gnu_library/bin/ar.pm"; then # Stratus VOS
# Assume that gmake, if found, is definitely GNU make
# and prefer it over the system make.
echo "Substituting gmake for make."
make=$gmake
_make=$_gmake
fi
;;
esac
@end
case "$test" in
test)
echo "Hopefully test is built into your sh."
;;
*)
if `sh -c "PATH= test true" >/dev/null 2>&1`; then
echo "Using the test built into your sh."
?X:
?X: We need to set both test and _test, since Oldconfig.U will use the _test
?X: value to systematically restore computed paths, which may be wrong if
?X: we choose to load an old config.sh generated on another platform.
?X:
test=test
_test=test
fi
;;
esac
?LINT:change n c
case "$echo" in

```

```

echo)
echo "Hopefully echo is built into your sh."
;;
?X: For those rare cases where we don't need $echo...
") ;;
*)
echo " "
echo "Checking
compatibility between $echo and builtin echo (if any)..." >&4
$echo $n "hi there$c" >foo1
echo $n "hi there$c" >foo2
if cmp foo1 foo2 >/dev/null 2>&1; then
echo "They are compatible. In fact, they may be identical."
else
case "$n" in
'-n') n=" c='\c';;
*) n='-n' c="";;
esac
cat <<FOO

```

They are not compatible! You are probably running ksh on a non-USG system. I'll have to use \$echo instead of the builtin, since Bourne shell doesn't have echo built in and we may have to run some Bourne shell scripts. That means I'll have to use '\$n\$c' to suppress newlines now. Life is ridiculous.

```

FOO
$echo $n "The star should be here-->$c"
$echo "*"
fi
$rm -f foo1 foo2
;;
esac

```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/Loc.U
```

No license file was found, but licenses were detected in source scan.

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?MAKE:d_erfc: Inlibc

?MAKE: -pick add \$@ %<

?S:d_erfc:

?S: This variable conditionally defines the HAS_ERFC symbol, which

?S: indicates to the C program that the erfc() routine is available.

?S:.

?C:HAS_ERFC:

?C: This symbol, if defined, indicates that the erfc routine is

?C: available to do the complementary error function.

?C:.

?H:#\$d_erfc HAS_ERFC /**/

?H:.

?LINT:set d_erfc

: see if erfc exists

set erfc d_erfc

eval \$inlibc

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_erfc.U

No license file was found, but licenses were detected in source scan.

* You may redistribute only under the terms of the Artistic Licence,

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/files/Imake.tmpl

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_mbtowc.U 1 2006-08-24 12:32:52Z rmanfredi \$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic Licence,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic Licence; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: d_mbtowc.U,v \$

?RCS: Revision 3.0 1993/08/18 12:06:30 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?MAKE:d_mbtowc: Inlibc

?MAKE: -pick add \$@ %<

?S:d_mbtowc:

?S: This variable conditionally defines the HAS_MBTOWC symbol, which

?S: indicates to the C program that the mbtowc() routine is available

?S: to convert multibyte to a wide character.

?S:.

?C:HAS_MBTOWC (MBTOWC):

?C: This symbol, if defined, indicates that the mbtowc routine is available

?C: to

convert a multibyte to a wide character.

?C:.

?H:#\$d_mbtowc HAS_MBTOWC /**/

```
?H:
?LINT:set d_mbtowc
: see if mbtowc exists
set mbtowc d_mbtowc
eval $inlibc
```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/d_mbtowc.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: newsspool.U 1 2006-08-24 12:32:52Z rmanfredi $
```

```
?RCS:
```

```
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
```

```
?RCS:
```

```
?RCS: You may redistribute only under the terms of the Artistic Licence,
```

```
?RCS: as specified in the README file that comes with the distribution.
```

```
?RCS: You may reuse parts of this distribution only within the terms of
```

```
?RCS: that same Artistic Licence; a copy of which may be found at the root
```

```
?RCS: of the source tree for dist 4.0.
```

```
?RCS:
```

```
?RCS: $Log: newsspool.U,v $
```

```
?RCS: Revision 3.0 1993/08/18 12:09:24 ram
```

```
?RCS: Baseline for dist 3.0 netwide release.
```

```
?RCS:
```

```
?MAKE:newsspool newsspoolexp: Getfile Oldconfig
```

```
?MAKE: -pick add $@ %<
```

```
?S:newsspool:
```

```
?S: This variable contains the eventual value of the NEWSSPOOL symbol,
```

```
?S: which is the directory name where news articles are spooled. It
```

```
?S: may have a ~ on the front of it.
```

```
?S:.
```

```
?S:newsspoolexp:
```

```
?S: This is the same as the newsspool variable, but is
```

```
filename expanded
```

```
?S: at configuration time, for programs not wanting to deal with it at
```

```
?S: run-time.
```

```
?S:.
```

```
?C:NEWSSPOOL:
```

```
?C: This symbol contains the directory name where news articles are
```

```
?C: spooled. The program must be prepared to do ~ expansion on it.
```

```
?C:.
```

```
?C:NEWSSPOOL_EXP:
```

```
?C: This is the same as NEWSSPOOL, but is filename expanded at
```

```
?C: configuration time, for use in programs not willing to do so
```

```
?C: at run-time.
```

```
?C:.
```

```
?H:#define NEWSSPOOL "$newsspool" /**/
```

```
?H:#define NEWSSPOOL_EXP "$newspool" /**/  
?H.:  
: locate news spool directory  
case "$newspool" in  
")  
  dflt=/usr/spool/news  
  ;;  
*) dflt="$newspool";;  
esac  
echo " "  
fn=d~  
rp="Where are news spooled?"  
./getfile  
newspool="$ans"  
newspoolexp="$ansexp"
```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/newspool.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: i_string.U 1 2006-08-24 12:32:52Z rmanfredi $  
?RCS:  
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi  
?RCS:  
?RCS: You may redistribute only under the terms of the Artistic Licence,  
?RCS: as specified in the README file that comes with the distribution.  
?RCS: You may reuse parts of this distribution only within the terms of  
?RCS: that same Artistic Licence; a copy of which may be found at the root  
?RCS: of the source tree for dist 4.0.  
?RCS:  
?RCS: $Log: i_string.U,v $  
?RCS: Revision 3.0.1.2 1993/10/16 13:50:12 ram  
?RCS: patch12: special units Loc and Guess were missing from dependencies  
?RCS:  
?RCS: Revision 3.0.1.1 1993/09/13 16:07:26 ram  
?RCS: patch10: removed "(Actually, this looks more like...)" messages (WAD)  
?RCS:  
?RCS: Revision 3.0 1993/08/18 12:08:28 ram  
?RCS: Baseline for dist 3.0 netwide release.  
?RCS:  
?X:  
?X: See if we should include <string.h> or <strings.h>  
?X:  
?MAKE:i_string strings:  
test Setvar Findhdr Warn  
?MAKE: -pick add $@ %<  
?S:i_string:
```

?S: This variable conditionally defines the I_STRING symbol, which
?S: indicates that <string.h> should be included rather than <strings.h>.

?S:.

?S:strings:

?S: This variable holds the full path of the string header that will be

?S: used. Typically /usr/include/string.h or /usr/include/strings.h.

?S:.

?C:I_STRING:

?C: This symbol, if defined, indicates to the C program that it should

?C: include <string.h> (USG systems) instead of <strings.h> (BSD systems).

?C:.

?H:#\$i_string I_STRING /**/

?H:.

?LINT:set i_string

: see which of string.h or strings.h is needed

echo " "

strings=`./findhdr string.h`

if \$test "\$strings" && \$test -r "\$strings"; then

echo "Using <string.h> instead of <strings.h>." >&4

val="\$define"

else

val="\$undef"

strings=`./findhdr strings.h`

if \$test "\$strings" && \$test -r "\$strings"; then

echo "Using <strings.h> instead of <string.h>." >&4

else

./warn "No string header found -- You'll surely

have problems."

fi

fi

set i_string

eval \$setvar

case "\$i_string" in

"\$undef") strings=`./findhdr strings.h`;;

*) strings=`./findhdr string.h`;;

esac

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/i_string.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: sysman.U,v \$

?RCS: Revision 3.0.1.2 1994/06/20 07:08:43 ram

?RCS: patch30: now explicitly states that /usr/man/man1 is the default

?RCS: patch30: added /usr/local/man/man1 to the search list

?RCS:

?RCS: Revision 3.0.1.1 1993/09/13 16:13:50 ram

?RCS: patch10: added support for /local/man/man1 (WAD)

?RCS: patch10: added temporary syspath variable to cut down on line length

?RCS:

?RCS: Revision 3.0 1993/08/18 12:09:55 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?MAKE:sysman: test

Loc Oldconfig

?MAKE: -pick add \$@ %<

?S:sysman:

?S: This variable holds the place where the manual is located on this

?S: system. It is not the place where the user wants to put his manual

?S: pages. Rather it is the place where Configure may look to find manual

?S: for unix commands (section 1 of the manual usually). See mansrc.

?S:.

?T:syspath

: determine where manual pages are on this system

echo " "

case "\$sysman" in

")

syspath="/usr/share/man/man1 /usr/man/man1"

syspath="\$syspath /usr/man/mann /usr/man/man1 /usr/man/local/man1"

syspath="\$syspath /usr/man/u_man/man1 /usr/share/man/man1"

syspath="\$syspath /usr/catman/u_man/man1 /usr/man/l_man/man1"

syspath="\$syspath /usr/local/man/u_man/man1 /usr/local/man/l_man/man1"

syspath="\$syspath /usr/man/man.L /local/man/man1 /usr/local/man/man1"

sysman=`./loc . /usr/man/man1 \$syspath`

::

esac

if \$test -d "\$sysman"; then

echo "System manual is in \$sysman." >&4

else

echo "Could not find manual pages in source form." >&4

fi

Found

in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-

debian-perl-5.26.1/dist/U/sysman.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_readlink.U 1 2006-08-24 12:32:52Z rmanfredi \$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic Licence,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic Licence; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: Original Author: Andy Dougherty <doughera@lafcol.lafayette.edu>

?RCS:

?RCS: \$Log: d_readlink.U,v \$

?RCS: Revision 3.0.1.1 1994/08/29 16:11:52 ram

?RCS: patch32: created by ADO

?RCS:

?MAKE:d_readlink: Inlibc

?MAKE: -pick add \$@ %<

?S:d_readlink:

?S: This variable conditionally defines the HAS_READLINK symbol, which

?S: indicates to the C program that the readlink() routine is available

?S: to read the value of a symbolic link.

?S:.

?C:HAS_READLINK :

?C: This

symbol, if defined, indicates that the readlink routine is

?C: available to read the value of a symbolic link.

?C:.

?H:#\$d_readlink HAS_READLINK /**/

?H:.

?LINT:set d_readlink

: see if readlink exists

set readlink d_readlink

eval \$inlibc

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/d_readlink.U

No license file was found, but licenses were detected in source scan.

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?MAKE:d_nexttoward: Inlibc

?MAKE: -pick add \$@ %<

?S:d_nexttoward:
?S: This variable conditionally defines HAS_NEXTTOWARD if nexttoward()
?S: is available to return the next machine representable long double from
?S: x in direction y.
?S:.
?C:HAS_NEXTTOWARD:
?C: This symbol, if defined, indicates that the nexttoward routine is
?C: available to return the next machine representable long double from
?C: x in direction y.
?C:.
?H:#\$d_nexttoward HAS_NEXTTOWARD /**/
?H:.
?LINT:set d_nexttoward
: see if nexttoward exists
set nexttoward d_nexttoward
eval \$inlibc

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_nexttoward.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_strtol.U 1 2006-08-24 12:32:52Z rmanfredi \$
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: \$Log: d_strtol.U,v \$
?RCS: Revision 3.0 1993/08/18 12:07:39 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:d_strtol: Inlibc
?MAKE: -pick add \$@ %<
?S:d_strtol:
?S: This variable conditionally defines the HAS_STRTOL symbol, which
?S: indicates to the C program that the strtol() routine is available
?S: to provide better numeric string conversion than atoi() and friends.
?S:.
?C:HAS_STRTOL (STRTOL):
?C: This symbol, if defined, indicates that
?C: the strtol routine is available
?C: to provide better numeric string conversion than atoi() and friends.
?C:.

?H:#\$d_strerror HAS_STRTOL /**/

?H:.

?LINT:set d_strerror

: see if strtol exists

set strtol d_strerror

eval \$inlibc

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/d_strerror.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1999, Jarkko Hietaniemi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 3.0.

?RCS:

?MAKE:d_mq_open: Inlibc

?MAKE: -pick add \$@ %<

?S:d_mq_open:

?S: This variable conditionally defines HAS_MQ_OPEN if mq_open() is

?S: available to open a POSIX message queue.

?S:.

?C:HAS_MQ_OPEN:

?C: This symbol, if defined, indicates that the mq_open system call is

?C: available to open a POSIX message queue.

?C:.

?H:#\$d_mq_open HAS_MQ_OPEN /**/

?H:.

?LINT:set d_mq_open

: see if mq_open exists

set mq_open d_mq_open

eval \$inlibc

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_mq_open.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1999, Jarkko Hietaniemi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 3.0.
?RCS:
?MAKE:d_posix_sched: Setvar d_sched_getparam d_sched_setparam d_sched_getscheduler d_sched_setscheduler
d_sched_rr_get_interval d_sched_get_priority_min d_sched_get_priority_max i_sched
?MAKE: -pick add \$@ %<
?S:d_posix_sched:
?S: This variable conditionally defines the HAS_POSIX_SCHED symbol, which
?S: indicates that the entire POSIX sched_*(2) library is present.
?S:.
?C:HAS_POSIX_SCHED:
?C: This symbol, if defined, indicates that the entire POSIX sched_*(2)
?C: library is supported.
?C:.
?H:#\$d_posix_sched HAS_POSIX_SCHED /**/
?H:.
?LINT:set
d_posix_sched
: see how much of the 'POSIX sched_*(2)' library is present.
echo " "
case
"\$i_sched\$d_sched_getparam\$d_sched_getscheduler\$d_sched_setscheduler\$d_sched_rr_get_interval\$d_sched_get_
priority_min\$d_sched_get_priority_max\$d_sched_setparam" in
\$undef) val="\$undef" ;;
*) val="\$define" ;;
esac
case "\$val" in
"\$define") echo "You have the full POSIX sched_*(2) library." >&4 ;;
"\$undef") echo "You don't have the full POSIX sched_*(2) library." >&4 ;;
esac
set d_posix_sched
eval \$setvar

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/perl/d_posix_sched.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 2000 Jarkko Hietaniemi

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?MAKE:d_qgcvt: Inlibc
?MAKE: -pick add \$@ %<
?S:d_qgcvt:
?S: This variable conditionally defines the HAS_QGCVT symbol, which
?S: indicates to the C program that the qgcvt() routine is available.
?S:.
?C:HAS_QGCVT:
?C: This symbol, if defined, indicates that the qgcvt routine is
?C: available to convert long doubles ("quad doubles") to strings.
?C: This is a low-level routine hopefully faster than sprintf.
?C:.
?H:#\$d_qgcvt HAS_QGCVT /**/
?H:.
?LINT:set d_qgcvt
: see if qgcvt exists
set qgcvt d_qgcvt
eval \$inlibc

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_qgcvt.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: i_sysselect.U 1 2006-08-24 12:32:52Z rmanfredi \$
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: \$Log: i_sysselect.U,v \$
?RCS: Revision 3.0.1.1 1993/08/25 14:01:33 ram
?RCS: patch6: added default for i_sysselect
?RCS:
?RCS: Revision 3.0 1993/08/18 12:08:35 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?X:
?X: Look wether <sys/select.h> exists
?X:
?MAKE:i_sysselect: Inhdr
?MAKE: -pick add \$@ %<
?S:i_sysselect:
?S: This variable conditionally defines I_SYS_SELECT, which indicates
?S: to the C program that it should include <sys/select.h> in

```

order to
?S: get the definition of struct timeval.
?S:.
?C:I_SYS_SELECT (I_SYSSSELECT):
?C: This symbol, if defined, indicates to the C program that it should
?C: include <sys/select.h> in order to get definition of struct timeval.
?C:.
?H:#$i_syssselct I_SYS_SELECT /**/
?H:.
?D:i_syssselct="
?LINT:set i_syssselct
: see if sys/select.h has to be included
set sys/select.h i_syssselct
eval $inhdr

```

Found in path(s):

```

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/i_syssselct.U

```

No license file was found, but licenses were detected in source scan.

```

?RCS: $Id$
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: $Log: Options.U,v $
?RCS: Revision 3.0.1.7 1997/02/28 15:08:15 ram
?RCS: patch61: optdef.sh now starts with a "startsh"
?RCS: patch61: moved some code from Head.U
?RCS:
?RCS: Revision 3.0.1.6 1995/09/25 09:14:46 ram
?RCS: patch59: protected option parsing code against 'echo -*' option failure
?RCS:
?RCS: Revision 3.0.1.5 1995/05/12 12:04:52 ram
?RCS: patch54: added -K option for experts
?RCS:
?RCS: Revision 3.0.1.4 1995/01/30 14:27:52 ram
?RCS: patch49: this unit now exports file optdef.sh,
not a variable
?RCS:
?RCS: Revision 3.0.1.3 1995/01/11 15:19:00 ram
?RCS: patch45: new -O option allowing -D and -U to override config.sh settings
?RCS: patch45: file optdef.sh is no longer removed after sourcing

```

```

?RCS:
?RCS: Revision 3.0.1.2 1994/10/29 15:58:06 ram
?RCS: patch36: ensure option definition file is removed before appending
?RCS: patch36: protect variable definitions with spaces in them
?RCS:
?RCS: Revision 3.0.1.1 1994/06/20 06:55:44 ram
?RCS: patch30: now uses new me symbol to tag error messages
?RCS: patch30: new -D and -U options to define/undef symbols (JHI)
?RCS:
?RCS: Revision 3.0 1993/08/18 12:05:14 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?X:
?X: Command line parsing. It is really important that the variables used here
?X: be not listed in the MAKE line, or they will be saved in config.sh and
?X: loading this file to fetch default answers would clobber the values set
?X: herein.
?X:
?MAKE:Options: startsh
?MAKE: -pick wipe $@ %<
?V:reuseval
alldone error realsilent silent extractsh fastread \
override knowitall: config_sh
?T:arg argn symbol config_arg0 config_args config_argc xxx yyy zzz uuu
?T:args_exp args_sep arg_exp
?F:!Configure
?F:/optdef.sh ./cmdline.opt ./posthint.sh ./cmdl.opt
: Save command line options in file UU/cmdline.opt for later use in
: generating config.sh.
?X: This temporary file will be read by Oldsym.U. I used a temporary
?X: file to preserve all sorts of potential command line quotes and
?X: also because we don't know in advance how many variables we'll
?X: need, so I can't actually declare them on the MAKE line.
?X: The config_args variable won't be quite correct if Configure is
?X: fed something like ./Configure -Dcc="gcc -B/usr/ccs/bin/"
?X: since the quotes are gone by the time we see them. You'd have to
?X: reconstruct the command line from the config_arg? lines, but since
?X: I don't imagine anyone actually having to do that, I'm not going
?X: to worry too much.
cat > cmdline.opt
<<EOSH
: Configure command line arguments.
config_arg0='$0'
config_args='$*'
config_argc=$#
EOSH
argn=1
args_exp="

```

```

args_sep="
for arg in "$@"; do
  cat >>cmdline.opt <<EOSH
  config_arg$argn='$arg'
EOSH
?X: Extreme backslashitis: replace each ' by """"
  cat <<EOC | sed -e "s/'/""""/g" > cmdl.opt
$arg
EOC
arg_exp=`cat cmdl.opt`
args_exp="$args_exp$args_sep'$arg_exp'"
argn=`expr $argn + 1`
args_sep=' '
done
?X: args_exp is good for restarting self: eval "set X $args_exp"; shift; $0 "$@"
?X: used by hints/os2.sh in Perl, for instance
rm -f cmdl.opt

```

: produce awk script to parse command line options

```

cat >options.awk <<'EOF'
BEGIN {
  optstr = "A:dD:eEf:hKOrsSU:V"; # getopt-style specification

  len = length(optstr);
  for (i = 1; i <= len; i++) {
    c = substr(optstr, i, 1);
?X: some older awk's do not have the C ?: construct
    if (i < len) a = substr(optstr, i + 1, 1); else a = "";
    if (a == ":") {
      arg[c] = 1;
      i++;
    }
    opt[c] = 1;
  }
}
{
  expect = 0;
  str = $0;
  if (substr(str,
  1, 1) != "-") {
    printf("%s\n", str);
    next;
  }
  len = length($0);
  for (i = 2; i <= len; i++) {
    c = substr(str, i, 1);
    if (!opt[c]) {
      printf("-%s\n", substr(str, i));

```

```

    next;
}
printf("-%s\n", c);
if (arg[c]) {
    if (i < len)
        printf("%s\n", substr(str, i + 1));
    else
        expect = 1;
    next;
}
}
}
}
END {
    if (expect)
        print "?";
}
EOF

```

: process the command line options

?X: Use "\$@" to keep arguments with spaces in them from being split apart.

?X: For the same reason, awk will output quoted arguments and the final eval

?X: removes them and sets a proper \$* array. An 'X' is prepended to each

?X: argument before being fed to echo to guard against 'echo -x', where -x

?X: would be understood as an echo option! It is removed before feeding awk.

```
set X `for arg in "$@"; do echo "X$arg"; done |
```

```
sed -e s/X// | awk -f options.awk`
```

```
eval "set $*"
```

```
shift
```

```
rm -f options.awk
```

: set up default values

```
fastread=""
```

```
reuseval=false
```

```
config_sh=""
```

```
alldone=""
```

```
error=""
```

```
silent=""
```

```
extractsh=""
```

```
override=""
```

```
knowitall=""
```

```
rm
```

```
-f optdef.sh posthint.sh
```

```
cat >optdef.sh <<EOS
```

```
$startsh
```

```
EOS
```

?X:

?X: Given that we now have the possibility to execute Configure remotely

?X: thanks to the new src.U support, we have to face the possibility
 ?X: of having to ask where the source lie, which means we need the Myread.U
 ?X: stuff and possibly other things that might echo something on the
 ?X: screen...
 ?X:
 ?X: That's not pretty, and might be confusing in 99% of the time. So...
 ?X: We introduce a new realsilent variable which is set when -s is given,
 ?X: and we force silent=true if -S is supplied. The Extractall.U unit
 ?X: will then undo the >&4 redirection based on the value of the
 ?X: realsilent variable... -- RAM, 18/93/96
 ?X:

```
: option parsing
while test $# -gt 0; do
  case "$1" in
    -d) shift; fastread=yes;;
    -e) shift; alldone=cont;;
    -f)
      shift
      cd ..
      if test -r "$1"; then
        config_sh="$1"
      else
        echo "$me: cannot read config file $1." >&2
        error=true
      fi
      cd UU
      shift;;
    -h)
      shift; error=true;;
    -r) shift; reuseval=true;;
    -s) shift; silent=true; realsilent=true;;
    -E) shift; alldone=exit;;
    -K) shift; knowitall=true;;
    -O) shift; override=true;;
    -S) shift; silent=true; extractsh=true;;
    -D)
      shift
      case "$1" in
        *=)
          echo "$me: use '-U symbol=', not '-D symbol='." >&2
          echo "$me: ignoring -D $1" >&2
          ;;
        *=*) echo "$1" | \
          sed -e "s/'\"/\"/g" -e "s/=(.*)/=\\1/'" >> optdef.sh;;
        *) echo "$1='define'" >> optdef.sh;;
      esac
      shift
  esac
done
```

```

;;
-U)
shift
case "$1" in
*) echo "$1" >> optdef.sh;;
*=*)
echo "$me: use '-D symbol=val', not '-U symbol=val'." >&2
echo "$me: ignoring -U $1" >&2
;;
*) echo "$1='undef'" >> optdef.sh;;
esac
shift
;;
-A)
shift
xxx=""
yyy="$1"
zzz=""
uuu=undef
case "$yyy" in
*=*) zzz=`echo "$yyy"|sed 's!:. *!!'^
case "$zzz" in
*:* ) zzz=" ";;
*) xxx=append
zzz=" "`echo
"$yyy"|sed 's!^[^=]*=!!'^
yyy=`echo "$yyy"|sed 's!:. *!!'^ ;;
esac
;;
esac
case "$xxx" in
") case "$yyy" in
*:* ) xxx=`echo "$yyy"|sed 's!:. *!!'^
yyy=`echo "$yyy"|sed 's!^[^:]*=!!'^
zzz=`echo "$yyy"|sed 's!^[^=]*=!!'^
yyy=`echo "$yyy"|sed 's!:. *!!'^ ;;
*) xxx=`echo "$yyy"|sed 's!:. *!!'^
yyy=`echo "$yyy"|sed 's!^[^:]*=!!'^ ;;
esac
;;
esac
case "$xxx" in
append)
echo "$yyy=\"\${yyy}$zzz\" >> posthint.sh ;;
clear)
echo "$yyy="" >> posthint.sh ;;
define)
case "$zzz" in

```

```

") zzz=define ;;
esac
echo "$yyy=$zzz" >> posthint.sh ;;
    eval)
echo "eval \"$yyy=$zzz\" >> posthint.sh ;;
    prepend)
echo "$yyy=\"$zzz\${$yyy}\" >> posthint.sh ;;
    undef)
        case "$zzz" in
")
zzz="$uuu" ;;
esac
echo "$yyy=$zzz" >> posthint.sh ;;
    *) echo "$me: unknown -A command '$xxx', ignoring -A $1" >&2 ;;
    esac
    shift
    ;;
-V) echo "$me generated by metaconfig <VERSION> PL<PATCHLEVEL>." >&2
    exit 0;;
--) break;;
-*) echo "$me: unknown option $1" >&2; shift; error=true;;
*) break;;
esac
done

```

```

case "$error" in
true)

```

```

cat >&2 <<EOM

```

```

Usage: $me [-dehrsEKOSV] [-f config.sh] [-D symbol] [-D symbol=value]

```

```

        [-U symbol] [-U symbol=] [-A command:symbol...]

```

```

-d : use defaults for all answers.

```

```

-e : go on without questioning past the production of config.sh.

```

```

-f : specify an alternate default configuration file.

```

```

-h : print this help message and exit (with an error status).

```

```

-r : reuse C symbols value if possible (skips costly nm extraction).

```

```

-s : silent mode, only echoes questions and essential information.

```

```

-D : define symbol to have some value:

```

```

    -D symbol      symbol gets the value 'define'

```

```

    -D symbol=value

```

```

    symbol gets the value 'value'

```

```

-E : stop at the end of questions, after having produced config.sh.

```

```

-K : do not use unless you know what you are doing.

```

```

-O : let -D and -U override definitions from loaded configuration file.

```

```

-S : perform variable substitutions on all .SH files (can mix with -f)

```

```

-U : undefine symbol:

```

```

    -U symbol      symbol gets the value 'undef'

```

```

    -U symbol=      symbol gets completely empty

```

```

-A : manipulate symbol after the platform specific hints have been applied:

```

```

-A symbol=value append " "value to symbol
-A append:symbol=value append value to symbol
-A define:symbol=value define symbol to have value
  -A clear:symbol define symbol to be "
-A define:symbol define symbol to be 'define'
-A eval:symbol=value define symbol to be eval of value
-A prepend:symbol=value prepend value to symbol
-A undef:symbol define symbol to be 'undef'
-A undef:symbol= define symbol to be "
-V : print version number and exit (with
a zero status).

```

EOM

```
exit 1
```

```
::
```

```
esac
```

?X:

?X: Unless they specified either -S or both -d and -e/E, make sure we're

?X: running interactively, i.e. attached to a terminal. Moved from Head.U to

?X: be able to handle batch configurations...

?X:

?X: We have to hardwire the Configure name and cannot use \$me, since if they

?X: said 'sh <Configure', then \$me is 'sh'...

?X:

```
: Sanity checks
```

```
case "$fastread$alldone" in
```

```
yescont|yesexit) ;;
```

```
*)
```

```
case "$extractsh" in
```

```
true) ;;
```

```
*)
```

```
if test ! -t 0; then
```

```
  echo "Say 'sh Configure', not 'sh <Configure'"
```

```
  exit 1
```

```
fi
```

```
::
```

```
esac
```

```
::
```

```
esac
```

?X: In silent mode, the standard output is closed. Questions are asked by

?X: outputting on file descriptor #4, which is the original stdout descriptor.

?X: This filters out all the "junk", since all the needed information is written

?X: on #4. Note that ksh will not let us redirect output if the file descriptor

?X: has not be defined yet, unlike sh, hence the following line...--RAM.

```
exec 4>&1
```

```
case "$silent" in
```

```
true)
```

```
exec 1>/dev/null;;
esac
```

: run the defines and the undefines, if any, but leave the file out there...

```
touch optdef.sh
```

```
./optdef.sh
```

: create the posthint manipulation script and leave the file out there...

?X: this file will be perused by Oldconfig.U

```
touch posthint.sh
```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/Options.U
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_ctermid.U 1 2006-08-24 12:32:52Z rmanfredi \$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic Licence,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic Licence; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: d_ctermid.U,v \$

?RCS: Revision 3.0 1993/08/18 12:05:54 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?MAKE:d_ctermid: Inlibc

?MAKE: -pick add \$@ %<

?S:d_ctermid:

?S: This variable conditionally defines CTERMID if ctermid() is

?S: available to generate filename for terminal.

?S:.

?C:HAS_CTERMID (CTERMID):

?C: This symbol, if defined, indicates that the ctermid routine is

?C: available to generate filename for terminal.

?C:.

?H:#\$d_ctermid

HAS_CTERMID /**/

?H:.

?LINT:set d_ctermid

: see if ctermid exists

```
set ctermid d_ctermid
```

```
eval $inlibc
```

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/d_ctermid.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1998 Jarkko Hietaniemi

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?MAKE:d_dbm64 d_dbmclose64 d_fetch64 d_store64 d_delete64 \
d_firstkey64 d_nextkey64: Inlibc use64bitint Setvar test

?MAKE: -pick add \$@ %<

?S:d_dbm64:

?S: This variable conditionally defines the HAS_DBM64 symbol, which

?S: indicates to the C program that the dbm64() routine is available.

?S:.

?S:d_dbmclose64:

?S: This variable conditionally defines the HAS_DBMCLOSE64 symbol, which

?S: indicates to the C program that the dbmclose64() routine is available.

?S:.

?S:d_fetch64:

?S: This variable conditionally defines the HAS_FETCH64 symbol, which

?S: indicates to the C program that the fetch64() routine is available.

?S:.

?S:d_delete64:

?S: This variable conditionally defines the HAS_DELETE64
symbol, which

?S: indicates to the C program that the delete64() routine is available.

?S:.

?S:d_store64:

?S: This variable conditionally defines the HAS_STORE64 symbol, which

?S: indicates to the C program that the store64() routine is available.

?S:.

?S:d_firstkey64:

?S: This variable conditionally defines the HAS_FIRSTKEY64 symbol, which

?S: indicates to the C program that the firstkey64() routine is available.

?S:.

?S:d_nextkey64:

?S: This variable conditionally defines the HAS_NEXTKEY64 symbol, which

?S: indicates to the C program that the nextkey64() routine is available.

?S:.

?C:HAS_DBM64:

?C: This symbol, if defined, indicates that the dbm64 routine is

?C: available to open dbm files larger than 2 gigabytes.

?C:.

?C:HAS_DBMCLOSE64:

?C: This symbol, if defined, indicates that the dbmclose64 routine is
?C: available to close dbm files larger than 2 gigabytes.
?C:.
?C:HAS_FETCH64:
?C: This symbol, if defined, indicates that the fetch64 routine is
?C: available to fetch
from dbm files larger than 2 gigabytes.
?C:.
?C:HAS_STORE64:
?C: This symbol, if defined, indicates that the store64 routine is
?C: available to store to dbm files larger than 2 gigabytes.
?C:.
?C:HAS_DELETE64:
?C: This symbol, if defined, indicates that the delete64 routine is
?C: available to delete from dbm files larger than 2 gigabytes.
?C:.
?C:HAS_FIRSTKEY64:
?C: This symbol, if defined, indicates that the firstkey64 routine is
?C: available to firstkey in dbm files larger than 2 gigabytes.
?C:.
?C:HAS_NEXTKEY64:
?C: This symbol, if defined, indicates that the nextkey64 routine is
?C: available to nextkey in dbm files larger than 2 gigabytes.
?C:.
?H:#\$d_dbminit64 HAS_DBMINIT64 /**/
?H:#\$d_dbmclose64 HAS_DBMCLOSE64 /**/
?H:#\$d_fetch64 HAS_FETCH64 /**/
?H:#\$d_store64 HAS_STORE64 /**/
?H:#\$d_delete64 HAS_DELETE64 /**/
?H:#\$d_firstkey64 HAS_FIRSTKEY64 /**/
?H:#\$d_nextkey64 HAS_NEXTKEY64 /**/
?H:.
?T:xxx
?LINT:set d_dbminit64
?LINT:set d_dbmclose64
?LINT:set d_fetch64
?LINT:set
d_store64
?LINT:set d_delete64
?LINT:set d_firstkey64
?LINT:set d_nextkey64
: Check if DBM has 64bit functions
if \$test X"\$use64bitint" = X"\$define"; then
: see if dbminit64 exists
set dbminit64 d_dbminit64
eval \$inlibc

: see if dbmclose64 exists

```

set dbmclose64 d_dbmclose64
eval $inlibc

: see if fetch64 exists
set fetch64 d_fetch64
eval $inlibc

: see if store64 exists
set store64 d_store64
eval $inlibc

: see if delete64 exists
set delete64 d_delete64
eval $inlibc

: see if firstkey64 exists
set firstkey64 d_firstkey64
eval $inlibc

: see if nextkey64 exists
set nextkey64 d_nextkey64
eval $inlibc
else
val="$undef"
for xxx in d_dbmclose64 d_fetch64 d_store64 d_delete64 d_firstkey64 d_nextkey64
do
set $xxx
eval $setvar
done
fi

```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/perl/dbm64.U
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_passwd.U 1 2006-08-24 12:32:52Z rmanfredi \$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic Licence,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic Licence; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: Original Author: Andy Dougherty <doughera@lafcol.lafayette.edu>

?RCS:

?RCS: \$Log: d_passwd.U,v \$
?RCS: Revision 3.0.1.2 1997/02/28 15:37:21 ram
?RCS: patch61: useless unit dropped.
?RCS:
?RCS: Revision 3.0.1.1 1994/08/29 16:09:51 ram
?RCS: patch32: created by ADO
?RCS:
?X:
?X: Useless unit dropped.
?X:
?LINT:empty

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/d_passwd.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: \$Log: charorder.U,v \$
?RCS: Revision 3.0.1.1 1994/10/29 16:07:08 ram
?RCS: patch36: added ?F: line for metalint file checking
?RCS:
?RCS: Revision 3.0 1993/08/18 12:05:33 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:chorder_int chorder_short chorder_long: Myread cat +cc +ccflags rm
?MAKE: -pick add \$@ %<
?S:chorder_short (d_cos d_bos):
?S: Holds the value describing the byte ordering of characters in a short.
?S: On a Big-Endian machine, that would be "c0c1".
?S:.
?S:chorder_int
(charoder):
?S: Holds the value describing the byte ordering of characters in an int.
?S: For instance, on a Big-Endian machine, this would be: "c0c1c2c3".
?S:.
?S:chorder_long (d_col d_bol):
?S: Holds the value describing the byte ordering of characters in a long.
?S: On a 64 bits Big-Endian machine, that would yield: "c0c1c2c3c4c5c6c7".

```

?S:.
?C:CHAR_ORDER_SHORT:
?C: Holds the byte ordering of characters in a short. It's a string
?C: value like "c0c1" on a Big-Endian machine.
?C:.
?C:CHAR_ORDER_INT:
?C: Holds the byte ordering of characters in an int. It's a string
?C: value like "c0c1c2c3" on a Big-Endian machine.
?C:.
?C:CHAR_ORDER_LONG:
?C: Holds the byte ordering of characters in a long. It's a string
?C: value like "c0c1c2c3c4c5c6c7" on a 64 bits Big-Endian machine.
?C:.
?H:#define CHAR_ORDER_SHORT "$chorder_short" /* byte order in a short */
?H:#define CHAR_ORDER_INT "$chorder_int" /* byte order in an int */
?H:#define CHAR_ORDER_LONG "$chorder_long" /* byte order in a long */
?H:.
?F:!byteorder
:
  check for character ordering
echo " "
echo "Checking out byte order..." >&4
$cat >byteorder.c <<'EOCP'
#include <stdio.h>

main(argc, argv)
int argc;
char *argv[]; {
int i;
int max;
union {
  short u_s;
  int u_i;
  long u_l;
  char u_c[sizeof(long)];
} u;
switch (argv[1][0]) {
case 'l':
  u.u_l = 0L;
  /* HMS: ASSERT: sizeof(long) < 10. */
  for(i = 0; i < sizeof(long); ++i) {
    u.u_l *= 0x100L;
    u.u_l += (0xc0 + i);
  }
  max = sizeof(long);
  break;
case 's':
  u.u_s = 0;

```

```

/* HMS: ASSERT: sizeof(short) < 10. */
for(i = 0; i < sizeof(short); ++i) {
    u.u_s *= 0x100L;
    u.u_s += (0xc0 + i);
}
max = sizeof(short);
break;
case 'i':
    u.u_i = 0;
/* RAM: ASSERT: sizeof(int) < 10. */
for(i = 0; i < sizeof(int); ++i) {
    u.u_l *= 0x100L;
    u.u_l += (0xc0 + i);
}
max = sizeof(int);
break;
default:
    max = 0;
    break;
}
for(i = 0; i < max; i++) {
    printf("%x", u.u_c[i] & 0x00FF);
}
printf("\n");
exit(0);
}
EOCP
if $cc $ccflags -o
byteorder byteorder.c >/dev/null 2>&1 ; then
: null statement
@if chorder_short
    chorder_short=`./byteorder s`
@end
@if chorder_int
    chorder_int=`./byteorder i`
@end
@if chorder_long
    chorder_long=`./byteorder l`
@end
else
$cat <<EOM
(I can't seem to get my test program to work. Guessing 32 bits big-endian.)
EOM
    chorder_short="c0c1"
    chorder_int="c0c1c2c3"
    chorder_long="c0c1c2c3"
fi
@if chorder_short

```

```

dflt=$chorder_short
rp='What is the order of characters in a short?'
./myread
chorder_short="$sans"
@end
@if chorder_int
dflt=$chorder_int
rp='What is the order of characters in an int?'
./myread
chorder_int="$sans"
@end
@if chorder_long
dflt=$chorder_long
rp='What is the order of characters in a long?'
./myread
chorder_long="$sans"
@end
$rm -f byteorder* core

```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/charorder.U
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: Typedef.U,v \$

?RCS: Revision 3.0.1.3 1995/07/25 13:42:07 ram

?RCS: patch56: added backslash escapes within evals to prevent space problems

?RCS:

?RCS: Revision 3.0.1.2 1994/10/29 16:01:16 ram

?RCS: patch36: don't clobber visible 'val' variable, use 'varval' instead

?RCS:

?RCS: Revision 3.0.1.1 1994/08/29 16:05:14 ram

?RCS: patch32: created

?RCS:

?X:

?X: This unit checks for the definition of a given typedef.

?X:

?X: To use it, say:

```

?X: set typedef val_t default [includes]
?X: eval $typedef
?X:
?MAKE:Typedef:
  cppstdin cppminus cppflags rm contains Oldconfig
?MAKE: -pick add $@ %<
?F:!temp.c
?LINT:define typedef
?V:typedef
?S:typedef:
?S: This shell variable is used internally by Configure to check
?S: whether a given typedef is defined or not. A typical use is:
?S: set typedef val_t default [includes]
?S: eval $typedef
?S: That will return val_t set to default if the typedef was not found,
?S: to typedef otherwise. If no includes are specified, look in sys/types.h.
?S:.
?T:type var def inclist varval inc
: define an is-a-typedef? function
typedef='type=$1; var=$2; def=$3; shift; shift; shift; inclist=$@;
case "$inclist" in
"" ) inclist="sys/types.h";;
esac;
eval "varval=\$$var";
case "$varval" in
"" )
$rm -f temp.c;
for inc in $inclist; do
  echo "#include <$inc>" >>temp.c;
done;
$cppstdin $cppflags $cppminus < temp.c >temp.E 2>/dev/null;
if $contains $type temp.E >/dev/null 2>&1; then
  eval "$var=\$type";
else
  eval "$var=\$def";
fi;
$rm -f temp.?.;
*) eval
"$var=\$varval";;
esac'

```

Found in path(s):

```

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/Typedef.U

```

No license file was found, but licenses were detected in source scan.

```

?RCS: $Id: d_preadv.U 1 2006-08-24 12:32:52Z rmanfredi $

```

```

?RCS:

```

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: \$Log: d_preadv.U,v \$
?RCS:
?MAKE:d_preadv: Inlibc
?MAKE: -pick add \$@ %<
?S:d_preadv:
?S: This variable conditionally defines the HAS_PREADV symbol, which
?S: indicates to the C program that the preadv() routine is available.
?S:.
?C:HAS_PREADV :
?C: This symbol, if defined, indicates that the preadv routine is
?C: available to perform vectored reads on a file descriptor at a
?C: given offset.
?C:.
?H:#\$d_preadv HAS_PREADV /**/
?H:.
?LINT:set d_preadv
:
 see if preadv exists
 set preadv d_preadv
 eval \$inlibc

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/d_preadv.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: i_sysrusage.U,v \$
?RCS:
?RCS: Copyright (c) 2000 Jarkko Hietaniemi
?RCS:
?RCS: You may distribute under the terms of either the GNU General Public
?RCS: License or the Artistic License, as specified in the README file.
?RCS:
?MAKE:i_sysrusage: Inhdr Hasfield
?MAKE: -pick add \$@ %<
?S:i_sysrusage:
?S: This variable conditionally defines the I_SYSRUSAGE symbol,
?S: and indicates whether a C program should include <sys/rusage.h>.
?S:.
?C:I_SYSRUSAGE:

?C: This symbol, if defined, indicates that <sys/rusage.h> exists and

?C: should be included.

?C:.

?H:#\$i_sysrusage I_SYSRUSAGE /**/

?H:.

?LINT:set i_sysrusage

: see if this is a sys/rusage.h system

set sys/rusage.h i_sysrusage

eval \$inhdr

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/i_sysrusage.U

No license file was found, but licenses were detected in source scan.

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?MAKE:d_lrint: Inlibc

?MAKE: -pick add \$@ %<

?S:d_lrint:

?S: This variable conditionally defines the HAS_LRINT symbol, which

?S: indicates to the C program that the lrint() routine is available

?S: to return the integral value closest to a double (according

?S: to the current rounding mode).

?S:.

?C:HAS_LRINT:

?C: This symbol, if defined, indicates that the lrint routine is

?C: available to return the integral value closest to a double

?C: (according to the current rounding mode).

?C:.

?H:#\$d_lrint HAS_LRINT /**/

?H:.

?LINT:set d_lrint

: see if lrint exists

set lrint d_lrint

eval \$inlibc

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_lrint.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_fchown.U 1 2006-08-24 12:32:52Z rmanfredi \$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic Licence,

?RCS: as specified in the README file that comes with the distribution.
 ?RCS: You may reuse parts of this distribution only within the terms of
 ?RCS: that same Artistic Licence; a copy of which may be found at the root
 ?RCS: of the source tree for dist 4.0.
 ?RCS:
 ?RCS: \$Log: d_fchown.U,v \$
 ?RCS: Revision 3.0 1993/08/18 12:06:01 ram
 ?RCS: Baseline for dist 3.0 netwide release.
 ?RCS:
 ?MAKE:d_fchown: Inlibc
 ?MAKE: -pick add \$@ %<
 ?S:d_fchown:
 ?S: This variable conditionally defines the HAS_FCHOWN symbol, which
 ?S: indicates to the C program that the fchown() routine is available
 ?S: to change ownership of opened files.
 ?S:.
 ?C:HAS_FCHOWN (FCHOWN):
 ?C: This symbol, if defined, indicates that the fchown routine is available
 ?C: to
 change ownership of opened files. If unavailable, use chown().
 ?C:.
 ?H:#\$d_fchown HAS_FCHOWN /**/
 ?H:.
 ?LINT:set d_fchown
 : see if fchown exists
 set fchown d_fchown
 eval \$inlibc

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/d_fchown.U

No license file was found, but licenses were detected in source scan.

?RCS: You may distribute under the terms of either the GNU General Public
 ?RCS: License or the Artistic License, as specified in the README file.
 ?RCS:
 ?MAKE:i_quadmath: Inhdr
 ?MAKE: -pick add \$@ %<
 ?S:i_quadmath:
 ?S: This variable conditionally defines I_QUADMATH, which indicates
 ?S: to the C program that it should include <quadmath.h>.
 ?S:.
 ?C:I_QUADMATH:
 ?C: This symbol, if defined, indicates that <quadmath.h> exists and
 ?C: should be included.
 ?C:.
 ?H:#\$i_quadmath I_QUADMATH /**/
 ?H:.

```
?LINT:set i_quadmath
: see if this is a quadmath.h system
set quadmath.h i_quadmath
eval $inhdr
```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/perl/i_quadmath.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: d_uwait.U 1 2006-08-24 12:32:52Z rmanfredi $
```

```
?RCS:
```

```
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
```

```
?RCS:
```

```
?RCS: You may redistribute only under the terms of the Artistic Licence,
```

```
?RCS: as specified in the README file that comes with the distribution.
```

```
?RCS: You may reuse parts of this distribution only within the terms of
```

```
?RCS: that same Artistic Licence; a copy of which may be found at the root
```

```
?RCS: of the source tree for dist 4.0.
```

```
?RCS:
```

```
?RCS: $Log: d_uwait.U,v $
```

```
?RCS: Revision 3.0.1.1 1994/01/24 14:10:49 ram
```

```
?RCS: patch16: added knowledge about wait3()
```

```
?RCS: patch16: revised 'union wait' look-up algorithm
```

```
?RCS: patch16: fixed make dependency line accordingly
```

```
?RCS:
```

```
?RCS: Revision 3.0 1993/08/18 12:07:54 ram
```

```
?RCS: Baseline for dist 3.0 netwide release.
```

```
?RCS:
```

```
?MAKE:d_uwait d_uwait3: cat contains cppstdin cppminus +cppflags rm \
Setvar Findhdr
```

```
?MAKE: -pick add $@ %<
```

```
?S:d_uwait:
```

```
?S: This symbol
```

```
conditionally defines UNION_WAIT which indicates to the C
```

```
?S: program that argument for the wait() system call should be declared as
```

```
?S: 'union wait status' instead of 'int status'.
```

```
?S:.
```

```
?S:d_uwait3:
```

```
?S: This symbol conditionally defines UNION_WAIT3 which indicates to the C
```

```
?S: program that the first argument for the wait3() system call should be
```

```
?S: declared as 'union wait status' instead of 'int status'.
```

```
?S:.
```

```
?C:UNION_WAIT:
```

```
?C: This symbol if defined indicates to the C program that the argument
```

```
?C: for the wait() system call should be declared as 'union wait status'
```

```
?C: instead of 'int status'. You probably need to include <sys/wait.h>
```

```
?C: in the former case (see I_SYSWAIT).
```

```

?C:.
?C:UNION_WAIT3:
?C: This symbol if defined indicates to the C program that the first argument
?C: for the wait3() system call should be declared as 'union wait status'
?C: instead of 'int status'. You probably need to include <sys/wait.h>
?C: in the former case (see I_SYSWAIT). It seems safe to assume that
the
?C: same rule applies to the second parameter of wait4().
?C:.
?H:#$d_uwait UNION_WAIT /**/
?H:#$d_uwait3 UNION_WAIT3 /**/
?H:.
?T:val2 flags f also
?LINT:set d_uwait d_uwait3
: see if union wait is available
echo " "
?X:
?X: Unfortunately, we can't just grep <sys/wait.h> for "union wait" because
?X: some weird systems (did I hear HP-UX?) define union wait only when _BSD
?X: is defined. The same thing happens on OSF/1, who is pushing weirdness to
?X: its limits by requiring wait() to use (int *) but wait3() to use
?X: (union wait *), unless _BSD is defined and -lbsd is used, in which case
?X: wait() also expects (union wait *). Aaargh!--RAM
?X:
set X $cppflags
shift
flags="
also="
for f in $*; do
case "$f" in
*NO_PROTO*) ;;
*) flags="$flags $f";;
esac
done
$cat `./findhdr sys/wait.h` /dev/null | \
$cppstdin $flags $cppminus >wait.out 2>/dev/null
if $contains 'union.*wait.*{' wait.out >/dev/null 2>&1 ; then
echo "Looks like your <sys/wait.h> knows about 'union wait'..."
>&4
val="$define"
@if UNION_WAIT
also='also '
if $contains 'extern.*wait[ ]*([ ]*int' wait.out >/dev/null 2>&1
then
echo "But wait() seems to expect an 'int' pointer (POSIX way)." >&4
val="$undef"
also="
elif $contains 'extern.*wait[ ]*([ ]*union' wait.out >/dev/null 2>&1

```

```

then
  echo "And indeed wait() expects an 'union wait' pointer (BSD way)." >&4
else
  echo "So we'll use that for wait()." >&4
fi
@end
@if UNION_WAIT3 || d_uwait3
  val2="$define"
@end
@if UNION_WAIT3
  if $contains 'extern.*wait3[ ]*([ ]*int' wait.out >/dev/null 2>&1
  then
    echo "However wait3() seems to expect an 'int' pointer, weird." >&4
    val2="$undef"
  elif $contains 'extern.*wait3[ ]*([ ]*union' wait.out >/dev/null 2>&1
  then
    echo "And wait3() ${also} expects an 'union wait' pointer, fine." >&4
  else
    echo "As expected, wait3() ${also} uses an 'union wait' pointer." >&4
  fi
fi
@end
else
  echo "No trace of 'union wait' in <sys/wait.h>..." >&4
  val="$undef"
@if UNION_WAIT && UNION_WAIT3
  echo
  "Both wait() and wait3() will use a plain 'int' pointer then." >&4
@elseif UNION_WAIT
  echo "Your wait() should be happy with a plain 'int' pointer." >&4
@elseif UNION_WAIT3
  echo "Your wait3() should be happy with a plain 'int' pointer." >&4
@end
fi
set d_uwait
eval $setvar
@if UNION_WAIT3 || d_uwait3
  val="$val2"; set d_uwait3
eval $setvar
@end
$rm -f wait.out

```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/d_uwait.U
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_rename.U 1 2006-08-24 12:32:52Z rmanfredi \$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: \$Log: d_rename.U,v \$
?RCS: Revision 3.0 1993/08/18 12:06:54 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:d_rename: Inlibc
?MAKE: -pick add \$@ %<
?S:d_rename:
?S: This variable conditionally defines the HAS_RENAME symbol, which
?S: indicates to the C program that the rename() routine is available
?S: to rename files.
?S:.
?C:HAS_RENAME (RENAME):
?C: This symbol, if defined, indicates that the rename routine is available
?C: to rename files.
 Otherwise you should do the unlink(), link(), unlink()
?C: trick.
?C:.
?H:#\$d_rename HAS_RENAME /**/
?H:.
?LINT:set d_rename
: see if rename exists
set rename d_rename
eval \$inlibc

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/d_rename.U

No license file was found, but licenses were detected in source scan.

?RCS: You may distribute under the terms of either the GNU General Public
?RCS: License or the Artistic License, as specified in the README file.
?RCS:
?MAKE:d_exp2: Inlibc
?MAKE: -pick add \$@ %<
?S:d_exp2:
?S: This variable conditionally defines the HAS_EXP2 symbol, which
?S: indicates to the C program that the exp2() routine is available.
?S:.
?C:HAS_EXP2:
?C: This symbol, if defined, indicates that the exp2 routine is

?C: available to do the 2**x function.

?C:.

?H:#\$d_exp2 HAS_EXP2 /**/

?H:.

?LINT:set d_exp2

: see if exp2 exists

set exp2 d_exp2

eval \$inlibc

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_exp2.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: i_sysmman.U,v \$

?RCS: Revision 3.0.1.1 1994/01/24 14:11:20 ram

?RCS: patch16: created

?RCS:

?X:

?X: Look wether <sys/mman.h> needs to be included.

?X:

?MAKE:i_sysmman: Inhdr

?MAKE: -pick add \$@ %<

?S:i_sysmman:

?S: This variable conditionally defines the I_SYS_MMAN symbol,

?S: and indicates whether a C program should include <sys/mman.h>.

?S:.

?C:I_SYS_MMAN:

?C: This symbol, if defined, indicates to the C program that it should

?C: include <sys/mman.h>.

?C:.

?H:#\$i_sysmman I_SYS_MMAN /**/

?H:.

?LINT:set

i_sysmman

: see if sys/mman.h has to be included

set sys/mman.h i_sysmman

eval \$inhdr

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/i_sysmman.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: i_sysstat.U 1 2006-08-24 12:32:52Z rmanfredi \$

?RCS:

?RCS: Copyright (c) 1996, Andy Dougherty

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic Licence,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic Licence; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: i_sysstat.U,v \$

?RCS: Revision 3.0.1.1 1997/02/28 15:48:30 ram

?RCS: patch61: created

?RCS:

?MAKE:i_sysstat: Inhdr

?MAKE: -pick add \$@ %<

?S:i_sysstat:

?S: This variable conditionally defines the I_SYS_STAT symbol,

?S: and indicates whether a C program should include <sys/stat.h>.

?S:.

?C:I_SYS_STAT (I_SYSSTAT):

?C: This symbol, if defined, indicates to the C program that it should

?C: include <sys/stat.h>.

?C:.

?H:#\$i_sysstat I_SYS_STAT /**/

?H:.

?LINT:set

i_sysstat

: see if sys/stat.h is available

set sys/stat.h i_sysstat

eval \$inhdr

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/i_sysstat.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_getnetbyaddr_r.U,v 0RCS:

?RCS: Copyright (c) 2002,2003 Jarkko Hietaniemi

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?RCS: Generated by the reentr.pl from the Perl 5.8 distribution.

?RCS:

?MAKE:d_getnetbyaddr_r getnetbyaddr_r_proto: Inlibc Protochk Hasproto \
i_systypes usethreads i_netdb extern_C

?MAKE: -pick add \$@ %<

?S:d_getnetbyaddr_r:

?S: This variable conditionally defines the HAS_GETNETBYADDR_R symbol,

?S: which indicates to the C program that the getnetbyaddr_r()

?S: routine is available.

?S:.

?S:getnetbyaddr_r_proto:

?S: This variable encodes the prototype of getnetbyaddr_r.

?S: It is zero if d_getnetbyaddr_r is undef, and one of the

?S: REENTRANT_PROTO_T_ABC macros of reentr.h if d_getnetbyaddr_r

?S: is defined.

?S:.

?C:HAS_GETNETBYADDR_R:

?C: This symbol, if defined, indicates that
the getnetbyaddr_r routine

?C: is available to getnetbyaddr re-entrantly.

?C:.

?C:GETNETBYADDR_R_PROTO:

?C: This symbol encodes the prototype of getnetbyaddr_r.

?C: It is zero if d_getnetbyaddr_r is undef, and one of the

?C: REENTRANT_PROTO_T_ABC macros of reentr.h if d_getnetbyaddr_r

?C: is defined.

?C:.

?H:#\$d_getnetbyaddr_r HAS_GETNETBYADDR_R /**/

?H:#define GETNETBYADDR_R_PROTO \$getnetbyaddr_r_proto /**/

?H:.

?T:try hdrs d_getnetbyaddr_r_proto

: see if getnetbyaddr_r exists

set getnetbyaddr_r d_getnetbyaddr_r

eval \$inlibc

case "\$d_getnetbyaddr_r" in

"\$define")

hdrs="\$i_systypes sys/types.h define stdio.h \$i_netdb netdb.h"

case "\$d_getnetbyaddr_r_proto:\$usethreads" in

":define") d_getnetbyaddr_r_proto=define

set d_getnetbyaddr_r_proto getnetbyaddr_r \$hdrs

eval \$hasproto ;;

*) ;;

esac

case "\$d_getnetbyaddr_r_proto" in

define)

case "\$getnetbyaddr_r_proto" in

```

"|0) try='int getnetbyaddr_r(unsigned long, int, struct netent*, char*, size_t, struct netent**, int*);'
./protochk
"$extern_C $try" $hdrs && getnetbyaddr_r_proto=I_UISBWRE ;;
esac
case "$getnetbyaddr_r_proto" in
"|0) try='int getnetbyaddr_r(long, int, struct netent*, char*, int);'
./protochk "$extern_C $try" $hdrs && getnetbyaddr_r_proto=I_LISBI ;;
esac
case "$getnetbyaddr_r_proto" in
"|0) try='struct netent* getnetbyaddr_r(in_addr_t, int, struct netent*, char*, int);'
./protochk "$extern_C $try" $hdrs && getnetbyaddr_r_proto=S_TISBI ;;
esac
case "$getnetbyaddr_r_proto" in
"|0) try='struct netent* getnetbyaddr_r(long, int, struct netent*, char*, int);'
./protochk "$extern_C $try" $hdrs && getnetbyaddr_r_proto=S_LISBI ;;
esac
case "$getnetbyaddr_r_proto" in
"|0) try='int getnetbyaddr_r(in_addr_t, int, struct netent*, struct netent_data*);'
./protochk "$extern_C $try" $hdrs && getnetbyaddr_r_proto=I_TISD ;;
esac
case "$getnetbyaddr_r_proto" in
"|0) try='int getnetbyaddr_r(long, int, struct netent*, struct netent_data*);'
./protochk "$extern_C $try" $hdrs && getnetbyaddr_r_proto=I_LISD
;;
esac
case "$getnetbyaddr_r_proto" in
"|0) try='int getnetbyaddr_r(int, int, struct netent*, struct netent_data*);'
./protochk "$extern_C $try" $hdrs && getnetbyaddr_r_proto=I_IISD ;;
esac
case "$getnetbyaddr_r_proto" in
"|0) try='int getnetbyaddr_r(uint32_t, int, struct netent*, char*, size_t, struct netent**, int*);'
./protochk "$extern_C $try" $hdrs && getnetbyaddr_r_proto=I_uISBWRE ;;
esac
case "$getnetbyaddr_r_proto" in
"|0) d_getnetbyaddr_r=undef
    getnetbyaddr_r_proto=0
    echo "Disabling getnetbyaddr_r, cannot determine prototype." >&4 ;;
*) case "$getnetbyaddr_r_proto" in
REENTRANT_PROTO*) ;;
*) getnetbyaddr_r_proto="REENTRANT_PROTO_${getnetbyaddr_r_proto}" ;;
esac
echo "Prototype: $try" ;;
esac
;;
*) case "$susetheads" in
define) echo "getnetbyaddr_r has no prototype, not using it." >&4 ;;
esac
d_getnetbyaddr_r=undef

```

```
getnetbyaddr_r_proto=0
;;
esac
;;
*) getnetbyaddr_r_proto=0
;;
esac
```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/threads/d_getnetbyaddr_r.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id$
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: $Log: i_malloc.U,v $
?RCS: Revision 3.0 1993/08/18 12:08:21 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:i_malloc: Inhdr
?MAKE: -pick add $@ %<
?S:i_malloc:
?S: This variable conditionally defines the I_MALLOC symbol, and indicates
?S: whether a C program should include <malloc.h>.
?S:.
?C:I_MALLOC:
?C: This symbol, if defined, indicates to the C program that it should
?C: include <malloc.h>.
?C:.
?H:#$i_malloc I_MALLOC /**/
?H:.
?LINT:set i_malloc
: see if this is a malloc.h system
set
malloc.h i_malloc
eval $inhdr
```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/i_malloc.U
```

No license file was found, but licenses were detected in source scan.

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?MAKE:d_fmax: Inlibc

?MAKE: -pick add \$@ %<

?S:d_fmax:

?S: This variable conditionally defines the HAS_FMAX symbol, which

?S: indicates to the C program that the fmax() routine is available.

?S:.

?C:HAS_FMAX:

?C: This symbol, if defined, indicates that the fmax routine is

?C: available to do the maximum function.

?C:.

?H:#\$d_fmax HAS_FMAX /**/

?H:.

?LINT:set d_fmax

: see if fmax exists

set fmax d_fmax

eval \$inlibc

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_fmax.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: nblock_io.U,v \$

?RCS: Revision 3.0.1.2 1997/02/28 16:17:14 ram

?RCS: patch61: simplify here document for shells that can't handle them well

?RCS: patch61: force use of "startsh" at the head of the generated script

?RCS: patch61: added new files to the ?F: metalint hint

?RCS:

?RCS: Revision 3.0.1.1 1995/07/25 14:13:22 ram

?RCS: patch56: created

?RCS:

?X:

?X: Simplify here document for shells that can't handle them well.

?X: (Problem reported on FreeBSD; it's unclear if this helps.) --AD

?X:

?MAKE:o_nonblock

eagain rd_nodata d_eofnblk: cat rm_try +cc +ccflags +ldflags \
d_open3 h_sysfile h_fcntl signal_t hint Oldconfig Setvar startsh Warn

?MAKE: -pick add \$@ %<

?S:o_nonblock:

?S: This variable bears the symbol value to be used during open() or fcntl()

?S: to turn on non-blocking I/O for a file descriptor. If you wish to switch

?S: between blocking and non-blocking, you may try ioctl(FIOSNBIO) instead,

?S: but that is only supported by some devices.

?S:.

?S:again:

?S: This variable bears the symbolic errno code set by read() when no

?S: data is present on the file and non-blocking I/O was enabled (otherwise,

?S: read() blocks naturally).

?S:.

?S:rd_nodata:

?S: This variable holds the return code from read() when no data is

?S: present. It should be -1, but some systems return 0 when O_NDELAY is

?S: used, which is a shame because you cannot make the difference between

?S: no data and an EOF.. Sigh!

?S:.

?S:d_eofnblk:

?S: This variable conditionally defines EOF_NONBLOCK

if EOF can be seen

?S: when reading from a non-blocking I/O source.

?S:.

?C:VAL_O_NONBLOCK:

?C: This symbol is to be used during open() or fcntl(F_SETFL) to turn on

?C: non-blocking I/O for the file descriptor. Note that there is no way

?C: back, i.e. you cannot turn it blocking again this way. If you wish to

?C: alternatively switch between blocking and non-blocking, use the

?C: ioctl(FIOSNBIO) call instead, but that is not supported by all devices.

?C:.

?C:VAL_EAGAIN:

?C: This symbol holds the errno error code set by read() when no data was

?C: present on the non-blocking file descriptor.

?C:.

?C:RD_NODATA:

?C: This symbol holds the return code from read() when no data is present

?C: on the non-blocking file descriptor. Be careful! If EOF_NONBLOCK is

?C: not defined, then you can't distinguish between no data and EOF by

?C: issuing a read(). You'll have to find another way to tell for sure!

?C:.

?C:EOF_NONBLOCK:

?C: This symbol, if defined, indicates to the C program that a read() on

?C: a

```

non-blocking file descriptor will return 0 on EOF, and not the value
?C: held in RD_NODATA (-1 usually, in that case!).
?C:.
?H:#define VAL_O_NONBLOCK $o_nonblock
?H:#define VAL_EAGAIN $eagain
?H:#define RD_NODATA $rd_nodata
?H:#$d_eofnblk EOF_NONBLOCK
?H:.
?F:!try !try.out !try.ret !try.err !mtry
?T:status
?LINT:use d_open3
: check for non-blocking I/O stuff
case "$h_sysfile" in
true) echo "#include <sys/file.h>" > head.c;;
*)
case "$h_fcntl" in
true) echo "#include <fcntl.h>" > head.c;;
*) echo "#include <sys/fcntl.h>" > head.c;;
esac
;;
esac
echo " "
echo "Figuring out the flag used by open() for non-blocking I/O..." >&4
case "$o_nonblock" in
")
$cat head.c > try.c
$cat >>try.c <<'EOCP'
int main() {
#ifdef O_NONBLOCK
printf("O_NONBLOCK\n");
exit(0);
#endif
#ifdef O_NDELAY
printf("O_NDELAY\n");
exit(0);
#endif
?X: Stevens "Advanced Programming in the UNIX Environment" page 364 mentions
?X: the FNDELAY symbol, used in 4.33BSD (source: Paul Marquess).
#ifdef FNDELAY
printf("FNDELAY\n");
exit(0);
#endif
exit(0);
}
EOCP
if
$cc $ccflags $ldflags -o try try.c >/dev/null 2>&1; then
o_nonblock=`./try`

```

```

case "$o_nonblock" in
") echo "I can't figure it out, assuming O_NONBLOCK will do.";;
*) echo "Seems like we can use $o_nonblock.";;
esac
else
echo "(I can't compile the test program; pray O_NONBLOCK is right!)"
fi
;;
*) echo "Using $hint value $o_nonblock.";;
esac
$rm_try

echo " "
echo "Let's see what value errno gets from read() on a $o_nonblock file..." >&4
case "$eagain" in
")
$cat head.c > try.c
$cat >>try.c <<EOCP
#include <errno.h>
#include <sys/types.h>
#include <signal.h>
#define MY_O_NONBLOCK $o_nonblock
extern int errno;
$signal_t blech(x) int x; { exit(3); }
EOCP
$cat >> try.c <<'EOCP'
int main()
{
int pd[2];
int pu[2];
char buf[1];
char string[100];

pipe(pd); /* Down: child -> parent */
pipe(pu); /* Up: parent -> child */
if (0 != fork()) {
int ret;
close(pd[1]); /* Parent reads from pd[0] */
close(pu[0]); /*
Parent writes (blocking) to pu[1] */
if (-1 == fcntl(pd[0], F_SETFL, MY_O_NONBLOCK))
exit(1);
signal(SIGALRM, blech);
alarm(5);
if ((ret = read(pd[0], buf, 1)) > 0) /* Nothing to read! */
exit(2);
sprintf(string, "%d\n", ret);
write(2, string, strlen(string));

```

```

alarm(0);
#ifdef EAGAIN
if (errno == EAGAIN) {
    printf("EAGAIN\n");
    goto ok;
}
#endif
#ifdef EWOULDBLOCK
if (errno == EWOULDBLOCK)
    printf("EWOULDBLOCK\n");
#endif
ok:
write(pu[1], buf, 1); /* Unblocks child, tell it to close our pipe */
sleep(2); /* Give it time to close our pipe */
alarm(5);
ret = read(pd[0], buf, 1); /* Should read EOF */
alarm(0);
sprintf(string, "%d\n", ret);
write(3, string, strlen(string));
exit(0);
}

close(pd[0]); /* We write to pd[1] */
close(pu[1]); /* We read from pu[0] */
read(pu[0], buf, 1); /* Wait for parent to signal us we may continue */
close(pd[1]); /* Pipe pd is now fully closed! */
exit(0); /* Bye bye, thank you for playing!
*/
}
EOCP
if $cc $ccflags $ldflags -o try try.c >/dev/null 2>&1; then
?X: Use script to avoid the possible 'alarm call' message
echo "$startsh" >mtry
echo "./try >try.out 2>try.ret 3>try.err || exit 4" >>mtry
chmod +x mtry
./mtry >/dev/null 2>&1
case $? in
0) eagain=`$cat try.out`;
1) echo "Could not perform non-blocking setting!";;
2) echo "I did a successful read() for something that was not there!";;
3) echo "Hmm... non-blocking I/O does not seem to be working!";;
*) echo "Something terribly wrong happened during testing.";;
esac
rd_nodata=`$cat try.ret`
echo "A read() system call with no data present returns $rd_nodata."
case "$rd_nodata" in
0|-1) ;;
*)

```

```

echo "(That's peculiar, fixing that to be -1.)"
rd_nodata=-1
;;
esac
case "$eagain" in
")
echo "Forcing errno EAGAIN on read() with no data available."
eagain=EAGAIN
;;
*)
echo "Your read() sets errno to $eagain when no data is available."
;;
esac
status=`$cat
try.err`
case "$status" in
0) echo "And it correctly returns 0 to signal EOF.";;
-1) echo "But it also returns -1 to signal EOF, so be careful!";;
*) echo "However, your read() returns '$status' on EOF??";;
esac
val="$define"
if test "$status" = "$rd_nodata"; then
./warn "your read() can't distinguish between EOF and no data!"
val="$undef"
fi
else
echo "I can't compile the test program--assuming errno EAGAIN will do."
eagain=EAGAIN
fi
set d_eofnblk
eval $setvar
;;
*)
echo "Using $hint value $eagain."
echo "Your read() returns $rd_nodata when no data is present."
case "$d_eofnblk" in
"$define") echo "And you can see EOF because read() returns 0.";;
"$undef") echo "But you can't see EOF status from read() returned value.";;
*)
?X: Should not happen, but if it does, assume the worst!
echo "(Assuming you can't see EOF status from read anyway.)"
d_eofnblk=$undef
;;
esac
;;
esac
$rm_try head.c mtry

```

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/nblock_io.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: i_sysstatvfs.U,v \$

?RCS:

?RCS: Copyright (c) 1999 Jarkko Hietaniemi

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?MAKE:i_sysstatvfs: Inhdr Hasfield

?MAKE: -pick add \$@ %<

?S:i_sysstatvfs:

?S: This variable conditionally defines the I_SYSSTATVFS symbol,

?S: and indicates whether a C program should include <sys/statvfs.h>.

?S:.

?C:I_SYS_STATVFS:

?C: This symbol, if defined, indicates that <sys/statvfs.h> exists and

?C: should be included.

?C:.

?H:#\$i_sysstatvfs I_SYS_STATVFS /**/

?H:.

?LINT:set i_sysstatvfs

: see if this is a sys/statvfs.h system

set sys/statvfs.h i_sysstatvfs

eval \$inhdr

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/i_sysstatvfs.U

No license file was found, but licenses were detected in source scan.

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?MAKE:d_trunc: Inlibc

?MAKE: -pick add \$@ %<

?S:d_trunc:

?S: This variable conditionally defines the HAS_TRUNC symbol, which

?S: indicates to the C program that the trunc() routine is available

?S: to round doubles towards zero.

?S:.

?C:HAS_TRUNC:

?C: This symbol, if defined, indicates that the trunc routine is

?C: available to round doubles towards zero.

?C:.

?H:#\$d_trunc HAS_TRUNC /**/

?H:.

?LINT:set d_trunc

: see if trunc exists

set trunc d_trunc

eval \$inlibc

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_trunc.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: i_sysmman.U,v \$

?RCS:

?RCS: Copyright (c) 1999 Jarkko Hietaniemi

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?MAKE:i_sysmman: Inhdr Hasfield

?MAKE: -pick add \$@ %<

?S:i_sysmman:

?S: This variable conditionally defines the I_SYS_MMAN symbol, and

?S: indicates whether a C program should include <sys/mman.h>.

?S:.

?C:I_SYS_MMAN:

?C: This symbol, if defined, indicates that <sys/mman.h> exists and

?C: should be included.

?C:.

?H:#\$i_sysmman I_SYS_MMAN /**/

?H:.

?LINT:set i_sysmman

: see if this is a sys/mman.h system

set sys/mman.h i_sysmman

eval \$inhdr

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/i_sysmman.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: Rcs.U 1 2006-08-24 12:32:52Z rmanfredi \$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic Licence,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: \$Log: Rcs.U,v \$
?RCS: Revision 3.0 1993/08/18 12:05:15 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?X:
?X: This is a unit that helps people who write SH scripts and keep them under
?X: RCS, but don't think to protect the \$Log and other \$Id keywords from
?X: variable substitution (or people like me who do not like to).
?X:
?MAKE:Author Date Header Id Locker Log RCSfile Revision Source State: Oldconfig
?MAKE: -pick weed \$@ %<
?LINT:describe Author
Date Header Id Locker Log RCSfile Revision Source State
: preserve RCS keywords in files with variable substitution, grrr
?Author:Author='\$Author'
?Date:Date='\$Date'
?Header:Header='\$Header'
?Id:Id='\$Id'
?\$Locker'
?Log:Log='\$Log'
?RCSfile:RCSfile='\$RCSfile'
?Revision:Revision='\$Revision'
?Source:Source='\$Source'
?State:State='\$State'

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/Rcs.U

No license file was found, but licenses were detected in source scan.

/*

* \$Id: setsid.C,v 3.0.1.1 1994/01/24 13:58:47 ram Exp ram \$

*

* Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

*

* You may redistribute only under the terms of the Artistic Licence,

* as specified in the README file that comes with the distribution.

* You may reuse parts of this distribution only within the terms of

* that same Artistic Licence; a copy of which may be found at the root

* of the source tree for dist 4.0.

*

* \$Log: setsid.C,v \$

* Revision 3.0.1.1 1994/01/24 13:58:47 ram

* patch16: created

*

*/

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/lib/C/fake/setsid.C

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: Head.U 6 2006-08-25 22:21:46Z rmanfredi \$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: Head.U,v \$

?RCS: Revision 3.0.1.9 1997/02/28 15:02:09 ram

?RCS: patch61: make sure we unset CDPATH for shells that support this

?RCS: patch61: improved Korn shell detection and handling

?RCS:

?RCS: Revision 3.0.1.8 1995/07/25 13:40:02 ram

?RCS: patch56: added SVR4-ish /opt directories to path list (ADO)

?RCS: patch56: OS/2 platforms are using another path separator

?RCS:

?RCS: Revision 3.0.1.7 1995/03/21 08:46:15 ram

?RCS: patch52: definition of

paths wrongly added spurious ':' chars

?RCS:

?RCS: Revision 3.0.1.6 1994/10/29 15:54:19 ram

?RCS: patch36: make sure ENV is unset before calling /bin/ksh

?RCS:

?RCS: Revision 3.0.1.5 1994/08/29 16:03:44 ram

?RCS: patch32: now sets PATH only using existing directories

?RCS:

?RCS: Revision 3.0.1.4 1994/06/20 06:54:28 ram

?RCS: patch30: now computes its invocation name into 'me'

?RCS: patch30: symbol me is made visible to all units read-only

?RCS:

?RCS: Revision 3.0.1.3 1993/12/15 08:15:07 ram

?RCS: patch15: added /sbin:/usr/sbin:/usr/libexec in PATH for BSD/386

?RCS:

?RCS: Revision 3.0.1.2 1993/11/10 17:32:35 ram

?RCS: patch14: ensure PATH is reset to '.' before testing for alias

?RCS:

?RCS: Revision 3.0.1.1 1993/08/27 14:38:07 ram

?RCS: patch7: not all 'test' programs support the -x option

```

?RCS:
?RCS: Revision 3.0 1993/08/18 12:04:58 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?X:
?X: This is the very first unit in the Configure script. It is mostly just
?X:
things to keep people from getting into a tizzy right off the bat.
?X:
?MAKE:Head:
?MAKE: -pick wipe $@ %<
?V:PATH p_ _exe me newsh
?T:argv p paths OS2_SHELL DJGPP
?T:inksh needksh avoidksh newsh changesh reason
?F:!*
?LINT:extern ENV CDPATH SHELL MACHTYPE _exe is_os2
?LINT:change ENV CDPATH is_os2
?LINT:nocomment
#!/bin/sh
#
# If these # comments don't work, trim them. Don't worry about any other
# shell scripts, Configure will trim # comments from them for you.
#
# (If you are trying to port this package to a machine without sh,
# I would suggest you have a look at the prototypical config_h.SH file
# and edit it to reflect your system. Some packages may include samples
# of config.h for certain machines, so you might look for one of those.)
#
?X:
?X: NOTE THAT A CONFIGURE SCRIPT IS IN THE PUBLIC DOMAIN (whether or not
?X: the software which uses it is in the public domain).
?X:
# Yes, you may rip this off to use in other distribution packages. This
# script belongs to the public
domain and cannot be copyrighted.
#
?X:
?X: WE ASK YOU NOT TO REMOVE OR ALTER THE FOLLOWING PARAGRAPH, PLEASE:
?X:
# Note: this Configure script was generated automatically by the tool
# called "metaconfig". Rather than working with this copy of Configure,
# you may wish to get metaconfig. Perl uses a modified version of this
# tool, available in the "dist" folder in the checkout of the git repo
# $ git clone git://perl5.git.perl.org/metaconfig.git metaconfig
# The original dist package (including metaconfig) is available via SVN:
# $ svn co https://svn.code.sf.net/p/dist/code/trunk/dist
#
?X: OK, I'll not alter, but I'll add to it then ...

```

```
# Though this script was generated by metaconfig from metaunits, it is
# OK to send patches against Configure itself. It's up to the Configure
# pumpkin to backport the patch to the metaunits if it is accepted.
# For more information on patching Configure, see pod/perlhack.pod
#
# The metaunits are also available from the public git repository:
#
#   http://perl5.git.perl.org/metaconfig.git/ or
#   $ git clone git://perl5.git.perl.org/metaconfig.git metaconfig
#
# See Porting/pumpkin.pod for more information on metaconfig.
?X:
?X: NOTA BENE:
?X: If you develop you own version of metaconfig based on this work,
?X: you have to add some comments telling that the script was generated
?X: by your version, not mine: It credits your work.
?X:
```

```
# Generated using [metaconfig <VERSION> PL<PATCHLEVEL>]
# (with additional metaconfig patches by <MAINTLOC>)
```

```
cat >c1$$ <<EOF
ARGGGHHHH!!!!
```

SCO csh still thinks true is false. Write to SCO today and tell them that next year Configure ought to "rm /bin/csh" unless they fix their blasted shell. :-)

(Actually, Configure ought to just patch csh in place. Hmm. Hmmmmm. All we'd have to do is go in and swap the && and || tokens, wherever they are.)

[End of diatribe. We now return you to your regularly scheduled programming...]

```
EOF
cat >c2$$ <<EOF
```

```
OOPS! You naughty creature! You didn't
run Configure with sh!
I will attempt to remedy the situation by running sh for you...
EOF
```

```
true || cat c1$$ c2$$
true || exec sh $0 $argv:q
```

```
(exit $?0) || cat c2$$
(exit $?0) || exec sh $0 $argv:q
rm -f c1$$ c2$$
```

```
if test -f /dev/cputype -a -f /dev/drivers -a -f /dev/osversion; then
cat <<EOF
```

```

***
*** I'm sorry but this system looks like Plan 9 and Plan 9 doesn't do
*** Configure that well. (Plan 9 is close to UNIX but not close enough.)
*** Please read the README.plan9 for further instructions.
*** Cannot continue, aborting.

```

```

***
EOF
exit 1
fi

```

```

if test -f /sys/utilities/MultiView ; then
# AmigaOS, test -c for /dev/null is not useful
:
elif test ! -c /dev/null ; then

```

```

cat <<EOF
***
*** I'm sorry, but /dev/null appears to be a file rather than a device.
*** Please consult your operating system's notes for making a device
*** in /dev.
*** Cannot continue, aborting.

```

```

***
EOF
exit 1
fi

```

```

: compute my invocation name
me=$0
case "$0" in
*/*)
me=`echo $0 | sed -e 's!.*^(.*)!\1!' 2>/dev/null`
test
"$me" || me=$0
;;
esac

```

```

?X:
?X: To be able to run under OS/2, we must detect that early enough to use
?X: the proper path separator, stored in $p_. It is : on UNIX and ; on
?X: DOS-ish systems such as OS/2.

```

```

?X:
: Proper separator for the PATH environment variable

```

```

p_=:
: On OS/2 this directory should exist if this is not floppy only system ":-]"
if test -d c:/ || ( uname -a | grep -i 'os\(\|\)2' 2>&1 ) 2>&1 >/dev/null ; then
if test -n "$OS2_SHELL"; then

```

```

p_=\;
PATH=`cmd /c "echo %PATH%" | tr "\\\\" /`

```

```

?X: That's a bug in ksh5.22

```

```

OS2_SHELL=`cmd /c "echo %OS2_SHELL%" | tr '\\\|' / | tr '[A-Z]' '[a-z]`
is_os2=yes
elif test -n "$DJGPP"; then
  case "X${MACHTYPE:-nonesuchmach}" in
    *cygwin|*msys) ;;
    *) p_=\; ;;
  esac
fi
fi

```

?X:

?X: There are two schools of thoughts here. Some people correctly argue that

?X: the user has a better chance than we do of setting a reasonable PATH and

?X: others argue that Configure is the best place there is to set up a suitable

?X:

PATH. Well, here we try to compromise by keeping the user's PATH and

?X: appending some directories which are known to work on some machine or the

?X: other. The rationale behind this being that a novice user might not have a

?X: proper environment variable set, and some directories like /etc (where

?X: chown is located on some BSD systems) may be missing--RAM.

?X:

?X: SVR4 adds an /opt directory for optional packages. Some sites use

?X: various permutations on /opt as opposed to /usr or /usr/local.-- ADO

?X:

?X: We only add directories that are not already in the PATH of the

?X: user and the directories must exist also.

?X:

?X: 20040627, Merijn, HP-UX's ANSI compiler is in /opt/ansic/bin if present

?X: and should be before /usr/ccs/bin, where the braindead bundled compiler

?X: can be found. The /usr/ccs/bin compiler cannot be used to build perl.

?X:

: Proper PATH setting

```
paths=/bin /usr/bin /usr/local/bin /usr/ucb /usr/local /usr/sbin'
```

```
paths="$paths /opt/bin /opt/local/bin /opt/local
```

```
/opt/sbin"
```

```
paths="$paths /usr/5bin /etc /usr/gnu/bin /usr/new /usr/new/bin /usr/nbin"
```

```
paths="$paths /opt/gnu/bin /opt/new /opt/new/bin /opt/nbin"
```

```
paths="$paths /sys5.3/bin /sys5.3/usr/bin /bsd4.3/bin /bsd4.3/usr/ucb"
```

```
paths="$paths /bsd4.3/usr/bin /usr/bsd /bsd43/bin /opt/ansic/bin /usr/ccs/bin"
```

```
paths="$paths /etc /usr/lib /usr/ucblib /lib /usr/ccs/lib"
```

```
paths="$paths /sbin /usr/sbin /usr/libexec"
```

```
paths="$paths /system/gnu_library/bin"
```

```
for p in $paths
```

```
do
```

```
  case "$p_${PATH}$p_" in
```

```
    *$p_-$p_*) ;;
```

```
    *) test -d $p && PATH=$PATH$p_-$p ;;
```

```
esac
done
```

```
PATH=.$p_$PATH
export PATH
```

: shall we be using ksh?

```
inksh=""
```

```
needksh=""
```

```
avoidksh=""
```

```
newsh=/bin/ksh
```

```
changesh=""
```

?X: Use (alias -x) and not (alias) since zsh and bash recognize the alias

?X: builtin but not the -x option which is typically ksh...

?X: We need to set up PATH before calling the "alias" built-in since some

?X: systems like HP-UX have a binary called /bin/alias.

```
if (PATH=.; alias -x) >/dev/null 2>&1; then
```

```
    inksh=true
```

```
fi
```

?X: On HP-UX,

large Configure scripts may exercise a bug in /bin/sh, use ksh

```
if test -f /hp-ux -a -f /bin/ksh; then
```

```
    needksh='to avoid sh bug in "here document" expansion'
```

```
fi
```

?X: On AIX4, /bin/sh is really ksh and it causes problems, use sh

```
if test -d /usr/lpp -a -f /usr/bin/bsh -a -f /usr/bin/uname; then
```

```
    if test X`/usr/bin/uname -v` = X4; then
```

```
        avoidksh="to avoid AIX 4's /bin/sh"
```

```
        newsh=/usr/bin/bsh
```

```
    fi
```

```
fi
```

?X: On Digital UNIX, /bin/sh may start up buggy /bin/ksh, use sh

```
if test -f /osf_boot -a -f /usr/sbin/setld; then
```

```
    if test X`/usr/bin/uname -s` = XOSF1; then
```

```
        avoidksh="to avoid Digital UNIX' ksh"
```

```
        newsh=/bin/sh
```

?X: if BIN_SH is set to 'xpg4', sh will start up ksh

```
    unset BIN_SH
```

```
fi
```

```
fi
```

?X: If we are not in ksh and need it, then feed us back to it

case "\$inksh/\$needksh" in

```
/[a-z]*)
```

?X: Clear ENV to avoid any ~/.kshrc that could alias cd or whatever...

?X: Don't use "unset ENV", that is not portable enough

```
ENV=""
```

```
changesh=true
```

```
reason="$needksh"
```

```

;;
esac
?X: If we are in ksh and must
avoid it, then feed us back to a new shell
case "$sinksh/$savoidksh" in
true/[a-z]*)
changesh=true
reason="$savoidksh"
;;
esac
?X: Warn them if they use ksh on other systems, which are those where
?X: we don't need ksh nor want to avoid it explicitly, yet are using it.
case "$sinksh/$sneedksh-$savoidksh-" in
true/--)
cat <<EOM
(I see you are using the Korn shell. Some ksh's blow up on $me,
mainly on older exotic systems. If yours does, try the Bourne shell instead.)
EOM
;;
esac
case "$changesh" in
true)
export newsh
echo "(Feeding myself to $newsh $reason.)"
?X: Make sure they didn't say sh <Configure by checking whether $0 ends
?X: with Configure or not. If they did say sh <.././Configure, then too
?X: bad for them anyway, since we lost that path indication...
?X: Otherwise, execing $0 ensures we keep the full remote source dir
?X: indication for src.U.
case "$0" in
Configure|*/Configure) exec $newsh $0 "$@";;
*) exec $newsh Configure "$@";;
esac
;;
esac
?X: 2004.06.09 rac
?X:
having $newsh persist as ksh here is bad news if ksh doesn't really
?X: exist. this causes us to toss away a perfectly good working test in
?X: bash in favor of more exotic external options. see bug 42665.
test -x "${newsh}" || unset newsh

?X: Unset CDPATH to avoid surprises when using cd under some shells
?X: Can't unset it because that's not portable to very old shells.
?X: Can't set it to " because then bash 2.02 won't do "cd UU" --AD 6/98.
?X: Don't want to set it to '.' because then ksh prints out the
?X: name of the directory every time you cd to it. --AD 6/98
?X: In order to inflict the least harm, change it only if it's set.

```

```

: if needed, set CDPATH to a harmless value that is not chatty
: avoid bash 2.02 problems with empty CDPATH.
case "$CDPATH" in
") ;;
*) case "$SHELL" in
*bash*) CDPATH='.' ;;
*) CDPATH="" ;;
esac
;;
esac

```

```

: Configure runs within the UU subdirectory
test -d UU || mkdir UU
?X: Use ./* to avoid any confirmation prompts from enhanced shells -- WED
cd
UU && rm -f ./*

```

Found in path(s):

```

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/modified/Head.U

```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1999, Jarkko Hietaniemi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 3.0.

?RCS:

?MAKE:d_sem_trywait: Inlibc

?MAKE: -pick add \$@ %<

?S:d_sem_trywait:

?S: This variable conditionally defines HAS_SEM_TRYWAIT if sem_trywait() is

?S: available to attempt to wait (grab, lock) a POSIX semaphore.

?S:.

?C:HAS_SEM_TRYWAIT:

?C: This symbol, if defined, indicates that the sem_trywait system call is

?C: available to attempt to wait (grab, lock) a POSIX semaphore.

?C:.

?H:#\$d_sem_trywait HAS_SEM_TRYWAIT /**/

?H:.

?LINT:set d_sem_trywait

: see if sem_trywait exists

set sem_trywait d_sem_trywait

eval \$inlibc

Found

in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_sem_trywait.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_asctime_r.U,v 0RCS:

?RCS: Copyright (c) 2002,2003 Jarkko Hietaniemi

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?RCS: Generated by the reentr.pl from the Perl 5.8 distribution.

?RCS:

?MAKE:d_asctime_r asctime_r_proto: Inlibc Protochk Hasproto i_systypes \
usethreads i_time i_systime extern_C

?MAKE: -pick add \$@ %<

?S:d_asctime_r:

?S: This variable conditionally defines the HAS_ASCTIME_R symbol,

?S: which indicates to the C program that the asctime_r()

?S: routine is available.

?S:.

?S:asctime_r_proto:

?S: This variable encodes the prototype of asctime_r.

?S: It is zero if d_asctime_r is undef, and one of the

?S: REENTRANT_PROTO_T_ABC macros of reentr.h if d_asctime_r

?S: is defined.

?S:.

?C:HAS_ASCTIME_R:

?C: This symbol, if defined, indicates that the asctime_r routine

?C: is available to asctime

re-entrantly.

?C:.

?C:ASCTIME_R_PROTO:

?C: This symbol encodes the prototype of asctime_r.

?C: It is zero if d_asctime_r is undef, and one of the

?C: REENTRANT_PROTO_T_ABC macros of reentr.h if d_asctime_r

?C: is defined.

?C:.

?H:#\$d_asctime_r HAS_ASCTIME_R /**/

?H:#define ASCTIME_R_PROTO \$asctime_r_proto /**/

?H:.

?T:try hdrs d_asctime_r_proto

: see if asctime_r exists

set asctime_r d_asctime_r

eval \$inlibc

case "\$d_asctime_r" in

```

"$define")
hdrs="$i_systypes sys/types.h define stdio.h $i_time time.h $i_systime sys/time.h"
case "$d_asctime_r_proto:$usethreads" in
":define") d_asctime_r_proto=define
set d_asctime_r_proto asctime_r $hdrs
eval $hasproto ;;
*) ;;
esac
case "$d_asctime_r_proto" in
define)
case "$asctime_r_proto" in
"|0) try='char* asctime_r(const struct tm*, char*);'
./protochk "$extern_C $try" $hdrs && asctime_r_proto=B_SB ;;
esac
case "$asctime_r_proto" in
"|0) try='char* asctime_r(const struct tm*, char*, int);'
./protochk "$extern_C $try"
$hdrs && asctime_r_proto=B_SBI ;;
esac
case "$asctime_r_proto" in
"|0) try='int asctime_r(const struct tm*, char*);'
./protochk "$extern_C $try" $hdrs && asctime_r_proto=I_SB ;;
esac
case "$asctime_r_proto" in
"|0) try='int asctime_r(const struct tm*, char*, int);'
./protochk "$extern_C $try" $hdrs && asctime_r_proto=I_SBI ;;
esac
case "$asctime_r_proto" in
"|0) d_asctime_r=undef
asctime_r_proto=0
echo "Disabling asctime_r, cannot determine prototype." >&4 ;;
* ) case "$asctime_r_proto" in
REENTRANT_PROTO*) ;;
*) asctime_r_proto="REENTRANT_PROTO_$asctime_r_proto" ;;
esac
echo "Prototype: $try" ;;
esac
;;
*) case "$usethreads" in
define) echo "asctime_r has no prototype, not using it." >&4 ;;
esac
d_asctime_r=undef
asctime_r_proto=0
;;
esac
;;
*) asctime_r_proto=0
;;

```

esac

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/threads/d_asctime_r.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_safemcpy.U,v 3.0.1.5 1997/02/28 15:41:12 ram Exp \$

?RCS:

?RCS: Copyright (c) 1991-1993, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 3.0.

?RCS:

?RCS: \$Log: d_safemcpy.U,v \$

?RCS: Revision 3.0.1.5 1997/02/28 15:41:12 ram

?RCS: patch61: improved overlapping copy check

?RCS: patch61: comfort them if they have memmove

?RCS: patch61: added ?F: metalint hint

?RCS:

?RCS: Revision 3.0.1.4 1995/07/25 13:58:46 ram

?RCS: patch56: re-arranged compile line to include ldflags before objects

?RCS:

?RCS: Revision 3.0.1.3 1995/03/21 08:47:26 ram

?RCS: patch52: swapped two first arguments of memcopy() calls

?RCS:

?RCS:

Revision 3.0.1.2 1994/10/29 16:15:10 ram

?RCS: patch36: added 'ldflags' to the test compile line (ADO)

?RCS:

?RCS: Revision 3.0.1.1 1994/05/06 14:53:12 ram

?RCS: patch23: ensure string is not optimized in read-only memory (ADO)

?RCS:

?RCS: Revision 3.0 1993/08/18 12:06:58 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?MAKE:d_safemcpy: Compile cat d_memcopy rm_try run \
d_memmove i_memory i_stdlib i_string i_unistd Oldconfig Setvar

?MAKE: -pick add \$@ %<

?S:d_safemcpy:

?S: This variable conditionally defines the HAS_SAFE_MEMCPY symbol if

?S: the memcopy() routine can do overlapping copies.

?S: For overlapping copies, memmove() should be used, if available.

?S:.

?C:HAS_SAFE_MEMCPY (SAFE_MEMCPY):

?C: This symbol, if defined, indicates that the memcpy routine is available

?C: to copy potentially overlapping memory blocks. If you need to

?C: copy overlapping memory blocks, you should check HAS_MEMMOVE and

?C: use memmove() instead, if available.

?C:.

?H:#\$d_safemcpy HAS_SAFE_MEMCPY /**/

?H:.

?F:!try

?LINT:

```
set d_safemcpy
```

: can memcpy handle overlapping blocks?

```
echo " "
```

?X: assume the worst

```
val="$undef"
```

```
case "$d_memmove" in
```

```
"$define") echo "I'll use memmove() instead of memcpy() for overlapping copies." ;;
```

```
*) case "$d_memcpy" in
```

```
"$define")
```

```
echo "Checking to see if memcpy() can do overlapping copies..." >&4
```

```
$cat >try.c <<EOCP
```

```
#$i_memory I_MEMORY
```

```
#$i_stdlib I_STDLIB
```

```
#$i_string I_STRING
```

```
#$i_unistd I_UNISTD
```

```
EOCP
```

```
$cat >>try.c <<'EOCP'
```

```
#include <stdio.h>
```

```
#ifdef I_MEMORY
```

```
# include <memory.h>
```

```
#endif
```

```
#ifdef I_STDLIB
```

```
# include <stdlib.h>
```

```
#endif
```

```
#ifdef I_STRING
```

```
# include <string.h>
```

```
#else
```

```
# include <strings.h>
```

```
#endif
```

```
#ifdef I_UNISTD
```

```
# include <unistd.h> /* Needed for NetBSD */
```

```
#endif
```

```
int main()
```

```
{
```

```
char buf[128], abc[128];
```

```
char *b;
```

```
int len;
```

```
int off;
```

```
int align;
```

```
/* Copy "abcde..." string to char abc[] so that gcc doesn't
   try to store the string in read-only memory. */
memcpy(abc, "abcdefghijklmnopqrstuvwxy0123456789", 36);
```

```
for (align = 7; align >=
0; align--) {
for (len = 36; len; len--) {
b = buf+align;
memcpy(b, abc, len);
for (off = 1; off <= len; off++) {
memcpy(b+off, b, len);
memcpy(b, b+off, len);
if (memcmp(b, abc, len))
exit(1);
}
}
}
exit(0);
}
```

EOCP

```
set try
if eval $compile_ok; then
if $run ./try 2>/dev/null; then
echo "Yes, it can."
val="$define"
else
echo "It can't, sorry."
fi
else
echo "(I can't compile the test program, so we'll assume not...)"
fi
;;
esac
$rm_try
;;
esac
set d_safemcpy
eval $setvar
```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/compline/d_safemcpy.U
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: vaproto.U 1 2006-08-24 12:32:52Z rmanfredi \$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: Original Author: Graham Stoney <greyham@research.canon.oz.au>
?RCS:
?RCS: \$Log: vaprotov \$
?RCS: Revision 3.0.1.1 1994/01/24 14:17:16 ram
?RCS: patch16: definition of _V now appears only when needed
?RCS:
?RCS: Revision 3.0 1993/08/18 12:09:59 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:vaprotov: prototype i_stdarg Setvar
?MAKE: -pick add \$@ %<
?S:vaprotov:
?S: This variable conditionally defines CAN_VAPROTO on systems supporting
?S: prototype
declaration of functions with a variable number of
?S: arguments. See also prototype.
?S:.
?C:CAN_VAPROTO ~ %<:
?C: This variable is defined on systems supporting prototype declaration
?C: of functions with a variable number of arguments.
?C:.
?C:_V:
?C: This macro is used to declare function parameters in prototypes for
?C: functions with a variable number of parameters. Use double parentheses.
?C: For example:
?C:
?C: int printf _V((char *fmt, ...));
?C:
?C: Remember to use the plain simple _() macro when declaring a function
?C: with no variable number of arguments, since it might be possible to
?C: have a non-effect _V() macro and still get prototypes via _().
?C:.
?H:%<:#\$vaprotov CAN_VAPROTO /**/
?H:?_V:#ifdef CAN_VAPROTO
?H:?_V:#define _V(args) args
?H:?_V:#else
?H:?_V:#define _V(args) ()
?H:?_V:#endif
?H:.
?W:%<:_V
?LINT:set vaprotov

```

: see if prototypes support variable argument declarations
echo " "
case "$prototype$i_stdarg" in
$define$define)
echo "It appears we'll
be able to prototype varargs functions." >&4
val="$define"
;;
*)
echo "Too bad... We won't be using prototyped varargs functions..." >&4
val="$undef"
;;
esac
set vaproto
eval $setvar

```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/vaproto.U
```

No license file was found, but licenses were detected in source scan.

```

?RCS: $Id: rcs_branch.U 1 2006-08-24 12:32:52Z rmanfredi $
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: $Log: rcs_branch.U,v $
?RCS: Revision 3.0 1993/08/18 12:09:40 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:rcs_branch: Myread contains Loc
?MAKE: -pick add $@ %<
?S:rcs_branch:
?S: This variable will hold "true" if rcs can take the -b<revision>
?S: option, which can make Life Easier on those folks who like to run
?S: rcsdiff manually.
?S:.
?T:xxx
: Tra la la la la
echo " "
echo "Checking to see if RCS understands the -b switch..." >&4
xxx=`./loc

```

```

rcs "$pth`
case "$xxx" in
")
rcs_branch=false
echo "Oh. You don't seem to have RCS here."
;;
*)
rcs > rcsbranch.out 2>&1
if $contains 'b\[rev\]' rcsbranch.out >/dev/null 2>&1 ; then
rcs_branch=true
echo "Nice! Your RCS is spiffy!"
else
rcs_branch=false
echo "Well, at least you have RCS. You know, a newer version is available."
fi
;;
esac

```

Found in path(s):

```

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/rcs_branch.U

```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 2000 Jarkko Hietaniemi

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?MAKE:d_fp_class_l: Inlibc

?MAKE: -pick add \$@ %<

?S:d_fp_class_l:

?S: This variable conditionally defines the HAS_FP_CLASS_L symbol, which

?S: indicates to the C program that the fp_class_l() routine is available.

?S:.

?C:HAS_FP_CLASS_L:

?C: This symbol, if defined, indicates that the fp_class_l routine is

?C: available to classify long doubles. Available for example in IRIX.

?C: The returned values are defined in <fp_class.h> and are:

?C:

?C: FP_SNAN Signaling NaN (Not-a-Number)

?C: FP_QNAN Quiet NaN (Not-a-Number)

?C: FP_POS_INF +infinity

?C: FP_NEG_INF -infinity

?C: FP_POS_NORM Positive normalized

?C: FP_NEG_NORM Negative normalized

?C: FP_POS_DENORM

```
Positive denormalized
?C: FP_NEG_DENORM Negative denormalized
?C: FP_POS_ZERO +0.0 (positive zero)
?C: FP_NEG_ZERO -0.0 (negative zero)
?C:.
?H:#$d_fp_class_1 HAS_FP_CLASS_L /**/
?H:.
?LINT:set d_fp_class_1
: see if fp_class_1 exists
set fp_class_1 d_fp_class_1
eval $inlibc
```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/perl/d_fp_class_1.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id$
?RCS:
?RCS: Copyright (c) 2000 Jarkko Hietaniemi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 3.0.
?RCS:
?MAKE:d_sbrkproto: Hasproto i_unistd
?MAKE: -pick add @$ %<
?S:d_sbrkproto:
?S: This variable conditionally defines the HAS_SBRK_PROTO symbol,
?S: which indicates to the C program that the system provides
?S: a prototype for the sbrk() function. Otherwise, it is
?S: up to the program to supply one.
?S:.
?C:HAS_SBRK_PROTO:
?C: This symbol, if defined, indicates that the system provides
?C: a prototype for the sbrk() function. Otherwise, it is up
?C: to the program to supply one. Good guesses are
?C: extern void* sbrk(int);
?C: extern
void* sbrk(size_t);
?C:.
?H:#$d_sbrkproto HAS_SBRK_PROTO /**/
?H:.
?LINT:set d_sbrkproto
: see if prototype for sbrk is available
echo " "
```

```
set d_sbrkproto sbrk $i_unistd unistd.h
eval $hasproto
```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/perl/d_sbrkproto.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: perlsv.U,v 1.1 2000/08/31 17:53:56 jhi Exp jhi $
```

```
?RCS:
```

```
?RCS: Copyright (c) 1999 Jarkko Hietaniemi
```

```
?RCS:
```

```
?RCS: You may distribute under the terms of either the GNU General Public
```

```
?RCS: License or the Artistic License, as specified in the README file.
```

```
?RCS:
```

```
?MAKE:ivtype uvtype nvtype ivsize uvsize nvsize \
    i8type u8type i16type u16type i32type u32type i64type u64type \
    i8size u8size i16size u16size i32size u32size i64size u64size \
    d_nv_preserves_uv nv_preserves_uv_bits nv_overflows_integers_at \
    d_nv_zero_is_allbits_zero: \
```

```
echo rm_try use64bitint d_quad quadtype uquadtype usequadmath \
```

```
d_longdbl uselongdouble longdblsize doublesize i_quadmath \
```

```
shortsize intsize longsize i_stdlib i_string libs gccversion \
```

```
cat Compile i_inttypes test d_volatile signal_t run
```

```
?MAKE: -pick add $@ %<
```

```
?S:ivtype:
```

```
?S: This variable contains the C type used for Perl's IV.
```

```
?S:.
```

```
?S:uvtype:
```

```
?S: This variable
contains the C type used for Perl's UV.
```

```
?S:.
```

```
?S:nvtype:
```

```
?S: This variable contains the C type used for Perl's NV.
```

```
?S:.
```

```
?S:i8type:
```

```
?S: This variable contains the C type used for Perl's I8.
```

```
?S:.
```

```
?S:u8type:
```

```
?S: This variable contains the C type used for Perl's U8.
```

```
?S:.
```

```
?S:i16type:
```

```
?S: This variable contains the C type used for Perl's I16.
```

```
?S:.
```

```
?S:u16type:
```

```
?S: This variable contains the C type used for Perl's U16.
```

```
?S:.
```

```
?S:i32type:
```

?S: This variable contains the C type used for Perl's I32.
?S:.
?S:u32type:
?S: This variable contains the C type used for Perl's U32.
?S:.
?S:i64type:
?S: This variable contains the C type used for Perl's I64.
?S:.
?S:u64type:
?S: This variable contains the C type used for Perl's U64.
?S:.
?S:ivsize:
?S: This variable is the size of an IV in bytes.
?S:.
?S:uvsize:
?S: This variable is the size of a UV in bytes.
?S:.
?S:i8size:
?S: This variable is the size of an I8 in bytes.
?S:.
?S:u8size:
?S: This variable is the size of an U8 in bytes.
?S:.
?S:i16size:
?S: This
variable is the size of an I16 in bytes.
?S:.
?S:u16size:
?S: This variable is the size of an U16 in bytes.
?S:.
?S:i32size:
?S: This variable is the size of an I32 in bytes.
?S:.
?S:u32size:
?S: This variable is the size of an U32 in bytes.
?S:.
?S:i64size:
?S: This variable is the size of an I64 in bytes.
?S:.
?S:u64size:
?S: This variable is the size of an U64 in bytes.
?S:.
?S:nvsize:
?S: This variable is the size of a Perl NV in bytes.
?S: Note that some floating point formats have unused bytes.
?S:.
?S:d_nv_preserves_uv:
?S: This variable indicates whether a variable of type nvtype

?S: can preserve all the bits a variable of type uvtype.
?S:.
?S:nv_preserves_uv_bits:
?S: This variable indicates how many of bits type uvtype
?S: a variable nvtype can preserve.
?S:.
?S:nv_overflows_integers_at:
?S: This variable gives the largest integer value that NVs can hold
?S: as a constant floating point expression.
?S: If it could not be determined, it holds the value 0.
?S:.
?S:d_nv_zero_is_allbits_zero:
?S: This
variable indicates whether a variable of type nvtype
?S: stores 0.0 in memory as all bits zero.
?S:.
?C:IVTYPE:
?C: This symbol defines the C type used for Perl's IV.
?C:.
?C:UVTYPE:
?C: This symbol defines the C type used for Perl's UV.
?C:.
?C:I8TYPE:
?C: This symbol defines the C type used for Perl's I8.
?C:.
?C:U8TYPE:
?C: This symbol defines the C type used for Perl's U8.
?C:.
?C:I16TYPE:
?C: This symbol defines the C type used for Perl's I16.
?C:.
?C:U16TYPE:
?C: This symbol defines the C type used for Perl's U16.
?C:.
?C:I32TYPE:
?C: This symbol defines the C type used for Perl's I32.
?C:.
?C:U32TYPE:
?C: This symbol defines the C type used for Perl's U32.
?C:.
?C:I64TYPE:
?C: This symbol defines the C type used for Perl's I64.
?C:.
?C:U64TYPE:
?C: This symbol defines the C type used for Perl's U64.
?C:.
?C:NVTYPE:
?C: This symbol defines the C type used for Perl's NV.

?C:.

?C:IVSIZE:

?C: This symbol contains the sizeof(IV).

?C:.

?C:UVSIZE:

?C: This

symbol contains the sizeof(UV).

?C:.

?C:I8SIZE:

?C: This symbol contains the sizeof(I8).

?C:.

?C:U8SIZE:

?C: This symbol contains the sizeof(U8).

?C:.

?C:I16SIZE:

?C: This symbol contains the sizeof(I16).

?C:.

?C:U16SIZE:

?C: This symbol contains the sizeof(U16).

?C:.

?C:I32SIZE:

?C: This symbol contains the sizeof(I32).

?C:.

?C:U32SIZE:

?C: This symbol contains the sizeof(U32).

?C:.

?C:I64SIZE:

?C: This symbol contains the sizeof(I64).

?C:.

?C:U64SIZE:

?C: This symbol contains the sizeof(U64).

?C:.

?C:NVSIZE:

?C: This symbol contains the sizeof(NV).

?C: Note that some floating point formats have unused bytes.

?C: The most notable example is the x86* 80-bit extended precision

?C: which comes in byte sizes of 12 and 16 (for 32 and 64 bit

?C: platforms, respectively), but which only uses 10 bytes.

?C: Perl compiled with -Duselongsdouble on x86* is like this.

?C:.

?C:NV_PRESERVES_UV:

?C: This symbol, if defined, indicates that a variable of type NVTYPE

?C: can preserve all the bits of a variable

of type UVTYPE.

?C:.

?C:NV_PRESERVES_UV_BITS:

?C: This symbol contains the number of bits a variable of type NVTYPE

?C: can preserve of a variable of type UVTYPE.

```

?C:.
?C:NV_OVERFLOWES_INTEGERS_AT:
?C: This symbol gives the largest integer value that NVs can hold. This
?C: value + 1.0 cannot be stored accurately. It is expressed as constant
?C: floating point expression to reduce the chance of decimal/binary
?C: conversion issues. If it can not be determined, the value 0 is given.
?C:.
?C:NV_ZERO_IS_ALLBITS_ZERO:
?C: This symbol, if defined, indicates that a variable of type NVTYPE
?C: stores 0.0 in memory as all bits zero.
?C:.
?H:#define IVTYPE $ivtype /**/
?H:#define UVTYPE $uvtype /**/
?H:#define I8TYPE $i8type /**/
?H:#define U8TYPE $u8type /**/
?H:#define I16TYPE $i16type /**/
?H:#define U16TYPE $u16type /**/
?H:#define I32TYPE $i32type /**/
?H:#define U32TYPE $u32type /**/
?H:??<:#ifdef HAS_QUAD
?H:??<:#define I64TYPE $i64type /**/
?H:??<:#define U64TYPE $u64type /**/
?H:??<:#endif
?H:#define NVTYPE $nvtype /**/
?H:#define IVSIZE $ivsize /**/
?H:#define UVSIZE $uvsize /**/
?H:#define I8SIZE $i8size /**/
?H:#define U8SIZE $u8size /**/
?H:#define I16SIZE $i16size /**/
?H:#define U16SIZE $u16size /**/
?H:#define I32SIZE $i32size /**/
?H:#define U32SIZE $u32size /**/
?H:??<:#ifdef
HAS_QUAD
?H:??<:#define I64SIZE $i64size /**/
?H:??<:#define U64SIZE $u64size /**/
?H:??<:#endif
?H:#define NVSIZE $nvsize /**/
?H:$d_nv_preserves_uv NV_PRESERVES_UV
?H:#define NV_PRESERVES_UV_BITS $nv_preserves_uv_bits
?H:#define NV_OVERFLOWES_INTEGERS_AT $nv_overflows_integers_at
?H:$d_nv_zero_is_allbits_zero NV_ZERO_IS_ALLBITS_ZERO
?H:??<:#if UVSIZE == 8
?H:??<:# ifdef BYTEORDER
?H:??<:# if BYTEORDER == 0x1234
?H:??<:# undef BYTEORDER
?H:??<:# define BYTEORDER 0x12345678
?H:??<:# else

```

```

?H:?%<:#      if BYTEORDER == 0x4321
?H:?%<:#      undef BYTEORDER
?H:?%<:#      define BYTEORDER 0x87654321
?H:?%<:#
        endif
?H:?%<:#      endif
?H:?%<:#      endif
?H:?%<:#endif
?H:
?T:volatile
?T:xxx
?T:d
?F:!try
: Check basic sizes
echo " "
$echo "Choosing the C types to be used for Perl's internal types..." >&4

```

```

case "$use64bitint:$d_quad:$quadtype" in
define:define:?)
ivtype="$quadtype"
uvtype="$quatype"
ivsize=8
uvsize=8
;;
*) ivtype="long"
uvtype="unsigned long"
ivsize=$longsize
uvsize=$longsize
;;
esac

```

```

case "$uselongdouble:$d_longdbl" in
define:define)
nvtype="long double"
nvsize=$longdblsize
;;
*) nvtype=double
nvsize=$doublesize
;;
esac

```

```

case "$usequadmath:$i_quadmath" in
define:define)
nvtype="__float128"
nvsize=16
case "$libs" in
*quadmath*) ;;
*) $cat <<EOM >&4

```

```
*** You requested the use of the quadmath library, but you
*** do not seem to have the quadmath library installed.
*** Cannot continue, aborting.
```

```
EOM
```

```
    exit 1
;;
esac
;;
define:*) $cat <<EOM >&4
```

```
*** You requested the use of the quadmath library, but you
*** do not seem to
have the required header, <quadmath.h>.
```

```
EOM
```

```
case "$gccversion" in
[23].*[4.[0-5]*)
    $cat <<EOM >&4
```

```
*** Your gcc looks a bit old:
```

```
*** $gccversion
```

```
EOM
```

```
;;
")
    $cat <<EOM >&4
```

```
*** You are not running a gcc.
```

```
EOM
```

```
;;
esac
$cat <<EOM >&4
```

```
*** For the quadmath library you need at least gcc 4.6.
```

```
*** Cannot continue, aborting.
```

```
EOM
```

```
    exit 1
;;
esac
```

```
$echo "(IV will be "$ivtype", $ivsize bytes)"
```

```
$echo "(UV will be "$uvtype", $uvsize bytes)"
```

```
$echo "(NV will be "$nvtype", $nvsize bytes)"
```

```
$cat >try.c <<EOCP
```

```
#$i_inttypes I_INTTYPES
```

```
#ifdef I_INTTYPES
```

```
#include <inttypes.h>
```

```
#endif
```

```
#include <stdio.h>
```

```
int main() {
```

```
#ifdef INT8
```

```

int8_t i = INT8_MAX;
uint8_t u = UINT8_MAX;
printf("int8_t\n");
#endif
#ifdef INT16
int16_t i = INT16_MAX;
uint16_t u = UINT16_MAX;
printf("int16_t\n");
#endif
#ifdef INT32
int32_t i = INT32_MAX;
uint32_t u = UINT32_MAX;
printf("int32_t\n");
#endif
}
EOCP

```

```

i8type="signed char"
u8type="unsigned char"
i8size=1
u8size=1

```

```

case "$i16type" in
") case
"$shortsize" in
2) i16type=short
u16type="unsigned short"
i16size=$shortsize
u16size=$shortsize
;;
esac
;;
esac
case "$i16type" in
") set try -DINT16
if eval $compile; then
case "$run ./try`" in
int16_t)
i16type=int16_t
u16type=uint16_t
i16size=2
u16size=2
;;
esac
fi
;;
esac
case "$i16type" in

```

```
) if $test $shortsize -ge 2; then
    i16type=short
    u16type="unsigned short"
    i16size=$shortsize
    u16size=$shortsize
fi
;;
esac
```

```
case "$i32type" in
) case "$longsize" in
4) i32type=long
    u32type="unsigned long"
    i32size=$longsize
    u32size=$longsize
;;
*) case "$intsize" in
4) i32type=int
    u32type="unsigned int"
    i32size=$intsize
    u32size=$intsize
;;
esac
```

```
;;
esac
;;
esac
```

```
case "$i32type" in
) set try -DINT32
if eval $compile; then
    case "$run ./try`" in
int32_t)
    i32type=int32_t
    u32type=uint32_t
    i32size=4
    u32size=4
;;
esac
```

```
fi
```

```
;;
```

```
esac
```

```
case "$i32type" in
) if $test $intsize -ge 4; then
    i32type=int
    u32type="unsigned
int"
    i32size=$intsize
    u32size=$intsize
```

```
fi
;;
esac
```

```
case "$i64type" in
") case "$d_quad:$quadtype" in
define:?)
i64type="$quadtype"
u64type="$uquadtype"
i64size=8
u64size=8
;;
esac
;;
esac
```

\$echo "Checking how many bits of your UVs your NVs can preserve..." >&4

: volatile so that the compiler has to store it out to memory.

```
if test X"$d_volatile" = X"$define"; then
```

```
volatile=volatile
```

```
fi
```

```
$cat <<EOP >try.c
```

```
#include <stdio.h>
```

```
#$i_stdlib I_STDLIB
```

```
#ifdef I_STDLIB
```

```
#include <stdlib.h>
```

```
#endif
```

```
#include <sys/types.h>
```

```
#include <signal.h>
```

```
#ifdef SIGFPE
```

```
$volatile int bleched = 0;
```

```
$signal_t blech(int s) { bleched = 1; }
```

```
#endif
```

```
int main() {
```

```
    $svtype u = 0;
```

```
    $nvtype d;
```

```
    int n = 8 * $svsize;
```

```
    int i;
```

```
#ifdef SIGFPE
```

```
    signal(SIGFPE, blech);
```

```
#endif
```

```
for (i = 0; i < n; i++) {
```

```
    u = u << 1 | ($svtype)1;
```

```
    d = ($nvtype)u;
```

```
    if (($svtype)d != u)
```

```
        break;
```

```
    if (d <= 0)
```

```

break;
    d = ($nvtype)(u - 1);
    if (($svtype)d
!= (u - 1))
        break;
#ifdef SIGFPE
    if (bletched)
break;
#endif
}
printf("%d\n", ((i == n) ? -n : i));
exit(0);
}
EOP
set try

d_nv_preserves_uv="$undef"
if eval $compile; then
    nv_preserves_uv_bits="$run ./try`"
fi
case "$nv_preserves_uv_bits" in
\[1-9]*)
    nv_preserves_uv_bits=`expr 0 - $nv_preserves_uv_bits`
    $echo "Your NVs can preserve all $nv_preserves_uv_bits bits of your UVs." 2>&1
    d_nv_preserves_uv="$define"
    ;;
[1-9]*) $echo "Your NVs can preserve only $nv_preserves_uv_bits bits of your UVs." 2>&1
    d_nv_preserves_uv="$undef" ;;
*) $echo "Can't figure out how many bits your NVs preserve." 2>&1
    nv_preserves_uv_bits="0" ;;
esac
$rm_try

$echo "Checking to find the largest integer value your NVs can hold..." >&4
: volatile so that the compiler has to store it out to memory.
if test X"$d_volatile" = X"$define"; then
    volatile=volatile
fi
$cat <<EOP >try.c
#include <stdio.h>

typedef $nvtype NV;

int
main() {
    NV value = 2;
    int count = 1;

```

```

while(count
< 256) {
    $volatile NV up = value + 1.0;
    $volatile NV negated = -value;
    $volatile NV down = negated - 1.0;
    $volatile NV got_up = up - value;
    int up_good = got_up == 1.0;
    int got_down = down - negated;
    int down_good = got_down == -1.0;

    if (down_good != up_good) {
        fprintf(stderr,
            "Inconsistency - up %d %f; down %d %f; for 2**%d (%.20f)\n",
            up_good, (double) got_up, down_good, (double) got_down,
            count, (double) value);
        return 1;
    }
    if (!up_good) {
        while (1) {
if (count > 8) {
            count -= 8;
            fputs("256.0", stdout);
        } else {
            count--;
            fputs("2.0", stdout);
        }
    }
    if (!count) {
        puts("");
        return 0;
    }
    fputs("2.0", stdout);
    }
    }
    value *= 2;
    ++count;
    }
    fprintf(stderr, "Cannot overflow integer range, even at 2**%d (%.20f)\n",
        count, (double) value);
    return 1;
}
EOP
set try

```

```

nv_overflows_integers_at='0'
if eval $compile; then
    xxx="$run ./try`"
    case "$?" in
    0)

```

```

case "$xxx" in
2*) cat >&4 <<EOM
The largest integer your NVs can preserve is equal to $xxx
EOM

```

```

    nv_overflows_integers_at="$xxx"
    ;;
*) cat >&4 <<EOM

```

Cannot determine the largest integer value your NVs can hold, unexpected output

```
'$xxx'
```

```
EOM
```

```

    ;;
    esac
    ;;
*) cat >&4 <<EOM

```

Cannot determine the largest integer value your NVs can hold

```
EOM
```

```

    ;;
    esac
fi
$rm_try

```

```
$echo "Checking whether NV 0.0 is all bits zero in memory..." >&4
```

```
: volatile so that the compiler has to store it out to memory.
```

```
if test X"$d_volatile" = X"$define"; then
```

```
    volatile=volatile
```

```
fi
```

```
$cat <<EOP >try.c
```

```
#include <stdio.h>
```

```
#$i_stdlib I_STDLIB
```

```
#ifdef I_STDLIB
```

```
#include <stdlib.h>
```

```
#endif
```

```
#$i_string I_STRING
```

```
#ifdef I_STRING
```

```
# include <string.h>
```

```
#else
```

```
# include <strings.h>
```

```
#endif
```

```
#include <sys/types.h>
```

```
#include <signal.h>
```

```
#ifdef SIGFPE
```

```
$volatile int bletched = 0;
```

```
$signal_t blech(int s) { bletched = 1; }
```

```
#endif
```

```
int checkit($nvtype d, const char *where) {
```

```
    void *v = &d;
```

```

    unsigned char *p
= (unsigned char *)v;
    unsigned char *end = p + sizeof(d);
    int fail = 0;

    while (p < end)
fail += *p++;

    if (!fail)
return 0;

    p = (unsigned char *)v;
    printf("No - %s: 0x", where);
    while (p < end)
printf ("%02X", *p++);
    printf("\n");
    return 1;
}

int main(int argc, char **argv) {
    $nctype d = 0.0;
    int fail = 0;
    fail += checkit(d, "0.0");

    /* The compiler shouldn't be assuming that bletched is 0 */
    d = bletched;

    fail += checkit(d, "bleched");

#ifdef SIGFPE
    signal(SIGFPE, blech);
#endif

    /* Paranoia - the compiler should have no way of knowing that ANSI says
    that argv[argc] will always be NULL. Actually, if it did assume this it
    would be buggy, as this is C and main() can be called from elsewhere in
    the program. */
    d = argv[argc] ? 1 : 0;

    if (d) {
printf("Odd argv[argc]=%p, d=%g\n", argv[argc], d);
    }

    fail += checkit(d, "ternary");

    memset(&d, sizeof(d), argv[argc] ? 1 :
0);

```

```

    if (d != 0.0) {
printf("No - memset doesn't give 0.0\n");
/* This might just blow up: */
printf("(gives %g)\n", d);
return 1;
    }

#ifdef SIGFPE
    if (bletched) {
printf("No - something bleched\n");
return 1;
    }
#endif
    if (fail) {
printf("No - %d fail(s)\n", fail);
return 1;
    }
printf("Yes\n");
return 0;
}
EOP
set try

d_nv_zero_is_allbits_zero="$undef"
if eval $compile; then
    xxx="$run ./try`"
    case "$?" in
0)
        case "$xxx" in
Yes) cat >&4 <<EOM
0.0 is represented as all bits zero in memory
EOM
            d_nv_zero_is_allbits_zero="$define"
            ;;
*) cat >&4 <<EOM
0.0 is not represented as all bits zero in memory
EOM
            d_nv_zero_is_allbits_zero="$undef"
            ;;
esac
            ;;
*) cat >&4 <<EOM
0.0 is not represented as all bits zero in memory
EOM
            d_nv_zero_is_allbits_zero="$undef"
            ;;
esac
fi

```

\$rm_try

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/perl.v.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: usenm.U,v \$

?RCS: Revision 3.0.1.1 1997/02/28 16:26:40 ram

?RCS: patch61: don't use nm with the GNU C library

?RCS: patch61: added support for Linux shared libs

?RCS:

?RCS: Revision 3.0 1993/08/18 12:09:57 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?MAKE:usenm runnm nm_opt nm_so_opt: cat test Myread Oldconfig grep \
d_gnulibc nm egrep rsrc osname Guess

?MAKE: -pick add \$@ %<

?S:usenm:

?S: This variable contains 'true' or 'false' depending whether the

?S: nm extraction is wanted

or not.

?S:.

?S:runnm:

?S: This variable contains 'true' or 'false' depending whether the

?S: nm extraction should be performed or not, according to the value

?S: of usenm and the flags on the Configure command line.

?S:.

?S:nm_opt:

?S: This variable holds the options that may be necessary for nm.

?S:.

?S:nm_so_opt:

?S: This variable holds the options that may be necessary for nm

?S: to work on a shared library but that can not be used on an

?S: archive library. Currently, this is only used by Linux, where

?S: nm --dynamic is *required* to get symbols from an ELF library which

?S: has been stripped, but nm --dynamic is *fatal* on an archive library.

?S: Maybe Linux should just always set usenm=false.

?S:.

: see if nm is to be used to determine whether a symbol is defined or not

?X: If there is enough inquiries, it might be worth to wait for the nm

?X: extraction. Otherwise, the C compilations might be a better deal.

?X:

?X: Don't bother if we're using GNU libc -- skimo

```
case "$usenm"
in
")
dflt="
case "$d_gnulibc" in
"$define")
echo " "
echo "$nm probably won't work on the GNU C Library." >&4
dflt=n
;;
esac
case "$dflt" in
")
if $test "$osname" = aix -a ! -f /lib/syscalls.exp; then
echo " "
echo "Whoops! This is an AIX system without /lib/syscalls.exp!" >&4
echo "'nm' won't be sufficient on this system." >&4
dflt=n
fi
;;
esac
case "$dflt" in
")
if ./gnu; then
echo " "
echo "Hmm... A GNU system without a GNU C Library? Weird..." >&4
dflt=n
else
dflt=`$grep 'inlibc|csym' $src/Configure | wc -l 2>/dev/null`
if $test $dflt -gt 20; then
dflt=y
else
dflt=n
fi
fi
;;
esac
*)
case "$usenm" in
true|$define) dflt=y;;
*) dflt=n;;
```

```

esac
;;
esac
$cat <<EOM

```

I can use \$nm to extract the symbols from your C libraries. This is a time consuming task which may generate huge output on the disk (up to 3 megabytes) but that should make the symbols extraction faster. The alternative is to skip the 'nm' extraction part and to compile a small test program instead to determine whether each symbol is present. If you have a fast C compiler and/or if your 'nm' output cannot be parsed, this may be the best solution.

```

EOM
rp='Shall I use nm to extract C symbols from the libraries?'
./myread
case "$ans" in
[Nn]*) usenm=false;;
*) usenm=true;;
esac

```

```

?X: Name extraction is to be run if 'nm' usage is wanted and if no -r flag
?X: was provided to configure (in which case we simply re-use the previous
?X: values).
runnm=$usenm
case "$reusel" in
true) runnm=false;;
esac

```

```

: nm options which may be necessary
case "$nm_opt" in
") if $test -f /mach_boot; then
nm_opt=" # Mach
elif $test -d /usr/ccs/lib; then
nm_opt='-p' # Solaris (and SunOS?)
elif $test -f /dgux; then
nm_opt='-p' # DG-UX
elif $test -f /lib64/rld; then
nm_opt='-p' # 64-bit Irix
else
nm_opt="
fi;;
esac

```

```

?X: nm options which may be necessary for shared libraries but illegal
?X: for archive libraries. Thank you,

```

```

Linux.
case "$nm_so_opt" in
") case "$osname" in
*linux*)
if $nm --help | $grep 'dynamic' > /dev/null 2>&1; then
nm_so_opt='--dynamic'
fi
;;
esac
;;
esac

```

Found in path(s):

```

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/usenm.U

```

No license file was found, but licenses were detected in source scan.

```

?RCS: $Id: prefix.U,v 3.1 1999/07/08 18:27:51 doughera Exp doughera $
?RCS:
?RCS: Copyright (c) 1991-1993, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 3.0.
?RCS:
?RCS: Original Author: Andy Dougherty <doughera@lafcol.lafayette.edu>
?RCS:
?RCS: $Log: prefix.U,v $
?RCS: Revision 3.1 1999/07/08 18:27:51 doughera
?RCS: 5.005_5x version -- Andy Dougherty
?RCS:
?RCS: Revision 3.0.1.2 1995/01/30 14:44:05 ram
?RCS: patch49: new prefixexp variable holding a fully expanded prefix
?RCS: patch49: save off previous prefix value in oldprefix if changed (WED)
?RCS: patch49: added the INSTALLPREFIX define for C programs to use (WED)
?RCS:
?RCS:
Revision 3.0.1.1 1994/08/29 16:31:34 ram
?RCS: patch32: created by ADO
?RCS:
?MAKE:prefix prefixexp +oldprefix: Getfile Loc Oldconfig cat package
?MAKE: -pick add $@ %<
?S:prefix:
?S: This variable holds the name of the directory below which the
?S: user will install the package. Usually, this is /usr/local, and
?S: executables go in /usr/local/bin, library stuff in /usr/local/lib,

```

?S: man pages in /usr/local/man, etc. It is only used to set defaults
 ?S: for things in bin.U, mansrc.U, privlib.U, or scriptdir.U.
 ?S:.
 ?S:prefixexp:
 ?S: This variable holds the full absolute path of the directory below
 ?S: which the user will install the package. Derived from prefix.
 ?S:.
 ?S:oldprefix:
 ?S: This variable is set non-null if the prefix was previously defined
 ?S: and gets set to a new value. Used internally by Configure only.
 ?S:.
 ?C:INSTALLPREFIX:
 ?C: This symbol contains the name of the install prefix for this package.
 ?C:.
 ?H:#define INSTALLPREFIX "\$prefix" /**/
 ?H:.
 :
 determine root of directory hierarchy where package will be installed.
 case "\$prefix" in
 ")
 dflt=`./loc . /usr/local /usr/local /local /opt /usr`
 ;;
 *)
 dflt=`echo "\$prefix" | sed 's/.\$//`
 ;;
 *)
 dflt="\$prefix"
 ;;
 esac
 \$cat <<EOM

By default, \$package will be installed in \$dflt/bin, manual pages under \$dflt/man, etc..., i.e. with \$dflt as prefix for all installation directories. Typically this is something like /usr/local. If you wish to have binaries under /usr/bin but other parts of the installation under /usr/local, that's ok: you will be prompted separately for each of the installation directories, the prefix being only used to set the defaults.

```
EOM
fn=d~
rp='Installation prefix to use?'
./getfile
oldprefix=""
case "$prefix" in
") ;;
*)
case "$ans" in
```

```
"$prefix") ;;
*) oldprefix="$prefix";;
esac
;;
esac
prefix="$ans"
prefixexp="$ansexp"
```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/installdirs/prefix.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: Chk_whoami.U 1 2006-08-24 12:32:52Z rmanfredi $
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: $Log: Chk_whoami.U,v $
?RCS: Revision 3.0 1993/08/18 12:04:46 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?X:
?X: This unit makes sure we don't try to include whoami.h if uname() exists.
?X:
?MAKE:Chk_whoami: d_uname i_whoami
?MAKE: -pick add $@ %<
?LINT:change i_whoami
: weed out incompatibilities
case "$d_uname" in
"$define") i_whoami="$sundef" ;;
esac
```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/Chk_whoami.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: d_symlink.U 1 2006-08-24 12:32:52Z rmanfredi $
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
```

?RCS: as specified in the README file that comes with the distribution.
 ?RCS: You may reuse parts of this distribution only within the terms of
 ?RCS: that same Artistic Licence; a copy of which may be found at the root
 ?RCS: of the source tree for dist 4.0.
 ?RCS:
 ?RCS: \$Log: d_symlink.U,v \$
 ?RCS: Revision 3.0 1993/08/18 12:07:41 ram
 ?RCS: Baseline for dist 3.0 netwide release.
 ?RCS:
 ?MAKE:d_symlink: Inlibc
 ?MAKE: -pick add \$@ %<
 ?S:d_symlink:
 ?S: This variable conditionally defines the HAS_SYMLINK symbol, which
 ?S: indicates to the C program that the symlink() routine is available
 ?S: to create symbolic links.
 ?S:.
 ?C:HAS_SYMLINK (SYMLINK):
 ?C: This symbol, if defined, indicates that the symlink routine is available
 ?C: to
 create symbolic links.
 ?C:.
 ?H:#\$d_symlink HAS_SYMLINK /**/
 ?H:.
 ?LINT:set d_symlink
 : see if symlink exists
 set symlink d_symlink
 eval \$inlibc

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/d_symlink.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$
 ?RCS:
 ?RCS: Copyright (c) 1999 Jarkko Hietaniemi
 ?RCS:
 ?RCS: You may distribute under the terms of either the GNU General Public
 ?RCS: License or the Artistic License, as specified in the README file.
 ?RCS:
 ?MAKE:d_getmnt: Inlibc
 ?MAKE: -pick add \$@ %<
 ?S:d_getmnt:
 ?S: This variable conditionally defines the HAS_GETMNT symbol, which
 ?S: indicates to the C program that the getmnt() routine is available
 ?S: to retrieve one or more mount info blocks by filename.
 ?S:.
 ?C:HAS_GETMNT:

?C: This symbol, if defined, indicates that the getmnt routine is

?C: available to get filesystem mount info by filename.

?C:.

?H:#\$d_getmnt HAS_GETMNT /**/

?H:.

?LINT:set d_getmnt

: see if getmnt exists

set getmnt d_getmnt

eval \$inlibc

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_getmnt.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_getnetent_r.U,v 0RCS:

?RCS: Copyright (c) 2002,2003 Jarkko Hietaniemi

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?RCS: Generated by the reentr.pl from the Perl 5.8 distribution.

?RCS:

?MAKE:d_getnetent_r getnetent_r_proto: Inlibc Protochk Hasproto i_systypes \
usethreads i_netdb extern_C

?MAKE: -pick add \$@ %<

?S:d_getnetent_r:

?S: This variable conditionally defines the HAS_GETNETENT_R symbol,

?S: which indicates to the C program that the getnetent_r()

?S: routine is available.

?S:.

?S:getnetent_r_proto:

?S: This variable encodes the prototype of getnetent_r.

?S: It is zero if d_getnetent_r is undef, and one of the

?S: REENTRANT_PROTO_T_ABC macros of reentr.h if d_getnetent_r

?S: is defined.

?S:.

?C:HAS_GETNETENT_R:

?C: This symbol, if defined, indicates that the getnetent_r routine

?C: is

available to getnetent re-entrantly.

?C:.

?C:GETNETENT_R_PROTO:

?C: This symbol encodes the prototype of getnetent_r.

?C: It is zero if d_getnetent_r is undef, and one of the

?C: REENTRANT_PROTO_T_ABC macros of reentr.h if d_getnetent_r

?C: is defined.

?C:.

```

?H:#$d_getnetent_r HAS_GETNETENT_R /**/
?H:#define GETNETENT_R_PROTO $getnetent_r_proto /**/
?H:.
?T:try hdrs d_getnetent_r_proto
: see if getnetent_r exists
set getnetent_r d_getnetent_r
eval $inlibc
case "$d_getnetent_r" in
"$define")
hdrs="$i_systypes sys/types.h define stdio.h $i_netdb netdb.h"
case "$d_getnetent_r_proto:$susetheads" in
":define") d_getnetent_r_proto=define
set d_getnetent_r_proto getnetent_r $hdrs
eval $hasproto ;;
*) ;;
esac
case "$d_getnetent_r_proto" in
define)
case "$getnetent_r_proto" in
"|0) try='int getnetent_r(struct netent*, char*, size_t, struct netent**, int*);'
./protochk "$extern_C $try" $hdrs && getnetent_r_proto=I_SBWRE ;;
esac
case "$getnetent_r_proto" in
"|0) try='int
getnetent_r(struct netent*, char*, int, int*);'
./protochk "$extern_C $try" $hdrs && getnetent_r_proto=I_SBIE ;;
esac
case "$getnetent_r_proto" in
"|0) try='struct netent* getnetent_r(struct netent*, char*, int, int*);'
./protochk "$extern_C $try" $hdrs && getnetent_r_proto=S_SBIE ;;
esac
case "$getnetent_r_proto" in
"|0) try='struct netent* getnetent_r(struct netent*, char*, int);'
./protochk "$extern_C $try" $hdrs && getnetent_r_proto=S_SBI ;;
esac
case "$getnetent_r_proto" in
"|0) try='int getnetent_r(struct netent*, char*, int);'
./protochk "$extern_C $try" $hdrs && getnetent_r_proto=I_SBI ;;
esac
case "$getnetent_r_proto" in
"|0) try='int getnetent_r(struct netent*, struct netent_data*);'
./protochk "$extern_C $try" $hdrs && getnetent_r_proto=I_SD ;;
esac
case "$getnetent_r_proto" in
"|0) d_getnetent_r=undef
getnetent_r_proto=0
echo "Disabling getnetent_r, cannot determine prototype." >&4 ;;
* ) case "$getnetent_r_proto" in

```

```

REENTRANT_PROTO*)
;;
*) getnetent_r_proto="REENTRANT_PROTO_${getnetent_r_proto}" ;;
esac
echo "Prototype: $try" ;;
esac
;;
*) case "$usetthreads" in
define) echo "getnetent_r has no prototype, not using it." >&4 ;;
esac
d_getnetent_r=undef
getnetent_r_proto=0
;;
esac
;;
*) getnetent_r_proto=0
;;
esac

```

Found in path(s):

```

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/threads/d_getnetent_r.U

```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1999, Jarkko Hietaniemi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 3.0.

?RCS:

?MAKE:d_mq_close: Inlibc

?MAKE: -pick add \$@ %<

?S:d_mq_close:

?S: This variable conditionally defines HAS_MQ_CLOSE if mq_close() is

?S: available to close a POSIX message queue.

?S:.

?C:HAS_MQ_CLOSE:

?C: This symbol, if defined, indicates that the mq_close system call is

?C: available to close a POSIX message queue.

?C:.

?H:#\$d_mq_close HAS_MQ_CLOSE /**/

?H:.

?LINT:set d_mq_close

: see if mq_close exists

```
set mq_close d_mq_close
eval $inlibc
```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/perl/d_mq_close.U
```

No license file was found, but licenses were detected in source scan.

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?MAKE:d_log1p: Inlibc

?MAKE: -pick add \$@ %<

?S:d_log1p:

?S: This variable conditionally defines the HAS_LOG1P symbol, which

?S: indicates to the C program that the logp1() routine is available

?S: to compute $\log(1 + x)$ for values of x close to zero.

?S:.

?C:HAS_LOG1P:

?C: This symbol, if defined, indicates that the log1p routine is

?C: available to do the logarithm of 1 plus argument function.

?C:.

?H:#\$d_log1p HAS_LOG1P /**/

?H:.

?LINT:set d_log1p

: see if log1p exists

set log1p d_log1p

eval \$inlibc

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/perl/d_log1p.U
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_dlopen.U,v 3.0.1.2 1995/07/25 13:52:56 ram Exp \$

?RCS:

?RCS: Copyright (c) 1991-1993, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 3.0.

?RCS:

?RCS: Original Author: Andy Dougherty <doughera@lafcol.lafayette.edu>

?RCS:

?RCS: \$Log: d_dlopen.U,v \$

?RCS: Revision 3.0.1.2 1995/07/25 13:52:56 ram

?RCS: patch56: force compile-link test since symbol might lie in crt0.o (ADO)

?RCS:

?RCS: Revision 3.0.1.1 1994/08/29 16:07:34 ram

?RCS: patch32: created by ADO

?RCS:

?MAKE:d_dlopen: Inlibc runnm d_cplusplus ccflags gccversion

?MAKE: -pick add \$@ %<

?S:d_dlopen:

?S: This variable conditionally defines the HAS_DLOPEN symbol, which

?S: indicates to the C program that the dlopen() routine is available.

?S:.

?C:HAS_DLOPEN :

?C: This symbol, if defined, indicates that the dlopen routine is

?C: available.

?C:.

?H:#\$d_dlopen HAS_DLOPEN /**/

?H:.

?T: xxx_runnm

?T: xxx_ccflags

?LINT:set d_dlopen

?X: We don't permanently change runnm and ccflags, but we do temporarily.

?LINT: change runnm

?LINT: change ccflags

: see if dlopen exists

?X: On NetBSD and FreeBSD, dlopen is available, but it is in

?X: /usr/lib/crt0.o, not in any of the libraries. Therefore, do not

?X: use the nm extraction, but use a real compile and link test instead.

xxx_runnm="\$runnm"

xxx_ccflags="\$ccflags"

runnm=false

: with g++ one needs -shared to get is-in-libc to work for dlopen

case "\$gccversion" in

) ;;

Clang) ;;

*) case "\$d_cplusplus" in

"\$define") ccflags="\$ccflags -shared" ;;

esac

;;

esac

set dlopen d_dlopen

eval \$inlibc

runnm="\$xxx_runnm"

ccflags="\$xxx_ccflags"

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/modified/d_dlopen.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: voidflags.U,v \$

?RCS: Revision 3.0.1.2 1997/02/28 16:27:58 ram

?RCS: patch61: don't prompt them if the void support is high enough for us

?RCS:

?RCS: Revision 3.0.1.1 1995/01/11 15:37:44 ram

?RCS: patch45: cosmetic change to avoid spurious blank lines when using -s

?RCS:

?RCS: Revision 3.0 1993/08/18 12:10:01 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?MAKE:voidflags defvoidused: cat sed rm rm_try contains +cc +ccflags package \
Oldconfig Myread

?MAKE: -pick add \$@ %<

?S:voidflags:

?S: This

variable contains the eventual value of the VOIDFLAGS symbol,

?S: which indicates how much support of the void type is given by this

?S: compiler. See VOIDFLAGS for more info.

?S:.

?S:defvoidused:

?S: This variable contains the default value of the VOIDUSED symbol (15).

?S:.

?X: Exceptionally, we have to explicitly alias the symbol name for

?X: config_h.SH, otherwise the comment would not appear.

?C:VOIDFLAGS ~ %<:

?C: This symbol indicates how much support of the void type is given by this

?C: compiler. What various bits mean:

?C:

?C: 1 = supports declaration of void

?C: 2 = supports arrays of pointers to functions returning void

?C: 4 = supports comparisons between pointers to void functions and

?C: addresses of void functions

?C: 8 = supports declaration of generic void pointers

?C:

?C: The package designer should define VOIDUSED to indicate the requirements

?C: of the package. This can be done either by #defining VOIDUSED before

```

?C: including
    config.h, or by defining defvoidused in Myinit.U. If the
?C: latter approach is taken, only those flags will be tested. If the
?C: level of void support necessary is not present, defines void to int.
?C:.
?H:?%<:#ifndef VOIDUSED
?H:?%<:#define VOIDUSED $defvoidused
?H:?%<:#endif
?H:?%<:#define VOIDFLAGS $voidflags
?H:?%<:#if (VOIDFLAGS & VOIDUSED) != VOIDUSED
?H:?%<:#define void int /* is void to be avoided? */
?H:?%<:#define M_VOID /* Xenix strikes again */
?H:?%<:#endif
?H:.
?W:%<:void
?F:!.out !try.c !flags
?LINT:usefile .out flags try.c
?INIT:: full support for void wanted by default
?INIT:defvoidused=15
?INIT:
?LINT:known void M_VOID VOIDUSED
: check for void type
echo " "
echo "Checking to see how well your C compiler groks the void type..." >&4
$cat >flags <<EOM

```

Support flag bits are:

- 1: basic void declarations.
- 2: arrays of pointers to functions returning void.
- 4: operations between pointers to and addresses of void functions.
- 8: generic void pointers.

EOM

```

case
"$voidflags" in
")
$cat >try.c <<'EOCP'
#if TRY & 1
void sub() {
#else
sub() {
#endif
extern void moo(); /* function returning void */
void (*goo)(); /* ptr to func returning void */
#if TRY & 8
void *hue; /* generic ptr */
#endif
#if TRY & 2

```

```

void (*foo[10])();
#endif

#if TRY & 4
if(goo == moo) {
    exit(0);
}
#endif
exit(0);
}
int main() { sub(); }
EOCP
?X: This unit used to use cc -S in those tests to try to speed up things, but
?X: unfortunately, AIX 3.2 does not support this option.
if $cc $ccflags -c -DTRY=$defvoidused try.c >/dev/null 2>&1 ; then
    voidflags=$defvoidused
    echo "Good. It appears to support void to the level $package wants."
    if $contains warning .out >/dev/null 2>&1; then
        echo "However, you might get some warnings that look like this:"
        $sed -e 's/^/' .out
    fi
else
echo "Hmm, your compiler has some difficulty with void. Checking further..." >&4
$cat >&4 flags
$rm -f flags
if $cc $ccflags -c -DTRY=1 try.c >/dev/null 2>&1; then
    echo
    "It supports 1..."
    if $cc $ccflags -c -DTRY=3 try.c >/dev/null 2>&1; then
        echo "It also supports 2..."
        if $cc $ccflags -c -DTRY=7 try.c >/dev/null 2>&1; then
            voidflags=7
            echo "And it supports 4 but not 8 definitely."
        else
            echo "It doesn't support 4..."
            if $cc $ccflags -c -DTRY=11 try.c >/dev/null 2>&1; then
                voidflags=11
                echo "But it supports 8."
            else
                voidflags=3
                echo "Neither does it support 8."
            fi
        fi
    else
        echo "It does not support 2..."
        if $cc $ccflags -c -DTRY=13 try.c >/dev/null 2>&1; then
            voidflags=13
            echo "But it supports 4 and 8."

```

```

else
if $cc $ccflags -c -DTRY=5 try.c >/dev/null 2>&1; then
voidflags=5
echo "And it supports 4 but has not heard about 8."
else
echo "However it supports 8 but not 4."
fi
fi
fi
else
echo "There is no support at all for void."
voidflags=0
fi
fi
esac
?X: Only prompt user if support does not match the
level we want
case "$voidflags" in
"$defvoidused")
echo "Good. I already know it supports void to the level $package wants."
;;
*)
dflt="$voidflags";
test -f flags && $cat flags
rp="Your void support flags add up to what?"
./myread
voidflags="$ans"
;;
esac
$rm_try flags

```

Found in path(s):

```

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/voidflags.U

```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1999 Jarkko Hietaniemi

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?MAKE:d_fs_data_s: Hasstruct i_sysparam i_sysmount i_systypes Setvar

?MAKE: -pick add \$@ %<

?S:d_fs_data_s:

?S: This variable conditionally defines the HAS_STRUCT_FS_DATA symbol,

?S: which indicates that the struct fs_data is supported.

```

?S:.
?C:HAS_STRUCT_FS_DATA:
?C: This symbol, if defined, indicates that the struct fs_data
?C: to do statfs() is supported.
?C:.
?H:#$d_fs_data_s HAS_STRUCT_FS_DATA /**/
?H:.
?LINT:set d_fs_data_s
: Check for fs_data_s
echo " "
echo "Checking to see if your system supports struct fs_data..." >&4
set d_fs_data_s fs_data $i_systypes sys/types.h $i_sysparam sys/param.h $i_sysmount sys/mount.h
eval $hasstruct
case "$d_fs_data_s" in
"$define")    echo "Yes, it does." ;;
*)
    echo "No, it doesn't." ;;
esac

```

Found in path(s):

```

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/perl/d_fs_data_s.U

```

No license file was found, but licenses were detected in source scan.

```

?RCS: $Id: instubperl.U,v 1.1 1999/07/08 18:32:57 doughera Exp doughera $

```

```

?RCS:

```

```

?RCS: Copyright (c) 1999, Jarkko Hietaniemi

```

```

?RCS:

```

```

?RCS: You may redistribute only under the terms of the Artistic License,

```

```

?RCS: as specified in the README file that comes with the distribution.

```

```

?RCS: You may reuse parts of this distribution only within the terms of

```

```

?RCS: that same Artistic License; a copy of which may be found at the root

```

```

?RCS: of the source tree for dist 3.0.

```

```

?RCS:

```

```

?MAKE:installusrbinperl: installbin cat bin Myread Setvar test Devel

```

```

?MAKE: -pick add $@ %<

```

```

?LINT:set installusrbinperl

```

```

?Y:TOP

```

```

?S:installusrbinperl:

```

```

?S: This variable tells whether Perl should be installed also as

```

```

?S: /usr/bin/perl in addition to

```

```

?S: $installbin/perl

```

```

?S:.

```

```

?C:INSTALL_USR_BIN_PERL:

```

```

?C: This symbol, if defined, indicates that Perl is to be installed

```

```

?C: also as /usr/bin/perl.

```

```

?C:.

```

```

?H:#$installusrbinperl INSTALL_USR_BIN_PERL /**/

```

?H:

: determine

whether to install perl also as /usr/bin/perl

echo " "

```
if $test -d /usr/bin -a "X$installbin" != X/usr/bin; then
```

```
$cat <<EOM
```

Many scripts expect perl to be installed as /usr/bin/perl.

If you want to, I can install the perl you are about to compile

as /usr/bin/perl (in addition to \$bin/perl).

EOM

```
if test -f /usr/bin/perl; then
```

```
$cat <<EOM
```

However, please note that because you already have a /usr/bin/perl,
overwriting that with a new Perl would very probably cause problems.

Therefore I'm assuming you don't want to do that (unless you insist).

EOM

```
case "$installusrbinperl" in
```

```
"$define"|[yY]*) dflt='y';;
```

```
*) dflt='n';;
```

```
esac
```

```
else
```

```
$cat <<EOM
```

Since you don't have a /usr/bin/perl I'm assuming creating one is okay.

EOM

```
case "$installusrbinperl" in
```

```
"$undef"|[nN]*) dflt='n';;
```

```
*) dflt='y';;
```

```
esac
```

```
fi
```

```
rp="Do you want to install perl as /usr/bin/perl?"
```

```
./myread
```

```
case "$ans" in
```

```
[yY]*) val="$define";;
```

```
*) val="$undef" ;;
```

```
esac
```

```
else
```

```
val="$undef"
```

```
fi
```

```
set
```

```
installusrbinperl
```

```
eval $setvar
```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/installdirs/instubperl.U
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_ctime_r.U,v 0RCS:

?RCS: Copyright (c) 2002,2003 Jarkko Hietaniemi

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?RCS: Generated by the reentr.pl from the Perl 5.8 distribution.

?RCS:

?MAKE:d_ctime_r ctime_r_proto: Inlibc Protochk Hasproto i_systypes \
usethreads i_time i_systime extern_C

?MAKE: -pick add \$@ %<

?S:d_ctime_r:

?S: This variable conditionally defines the HAS_CTIME_R symbol,

?S: which indicates to the C program that the ctime_r()

?S: routine is available.

?S:.

?S:ctime_r_proto:

?S: This variable encodes the prototype of ctime_r.

?S: It is zero if d_ctime_r is undef, and one of the

?S: REENTRANT_PROTO_T_ABC macros of reentr.h if d_ctime_r

?S: is defined.

?S:.

?C:HAS_CTIME_R:

?C: This symbol, if defined, indicates that the ctime_r routine

?C: is available to ctime re-entrantly.

?C:.

?C:CTIME_R_PROTO:

?C: This

symbol encodes the prototype of ctime_r.

?C: It is zero if d_ctime_r is undef, and one of the

?C: REENTRANT_PROTO_T_ABC macros of reentr.h if d_ctime_r

?C: is defined.

?C:.

?H:#\$d_ctime_r HAS_CTIME_R /**/

?H:#define CTIME_R_PROTO \$ctime_r_proto /**/

?H:.

?T:try hdrs d_ctime_r_proto

: see if ctime_r exists

set ctime_r d_ctime_r

eval \$inlibc

case "\$d_ctime_r" in

"\$define")

hdrs="\$i_systypes sys/types.h define stdio.h \$i_time time.h \$i_systime sys/time.h"

```

case "$d_ctime_r_proto:$susetheads" in
":define") d_ctime_r_proto=define
set d_ctime_r_proto ctime_r $hdrs
eval $hasproto ;;
*) ;;
esac
case "$d_ctime_r_proto" in
define)
case "$ctime_r_proto" in
"|0) try='char* ctime_r(const time_t*, char*);'
./protochk "$extern_C $try" $hdrs && ctime_r_proto=B_SB ;;
esac
case "$ctime_r_proto" in
"|0) try='char* ctime_r(const time_t*, char*, int);'
./protochk "$extern_C $try" $hdrs && ctime_r_proto=B_SBI ;;
esac
case "$ctime_r_proto" in
"|0) try='int
ctime_r(const time_t*, char*);'
./protochk "$extern_C $try" $hdrs && ctime_r_proto=L_SB ;;
esac
case "$ctime_r_proto" in
"|0) try='int ctime_r(const time_t*, char*, int);'
./protochk "$extern_C $try" $hdrs && ctime_r_proto=L_SBI ;;
esac
case "$ctime_r_proto" in
"|0) d_ctime_r=undef
ctime_r_proto=0
echo "Disabling ctime_r, cannot determine prototype." >&4 ;;
* ) case "$ctime_r_proto" in
REENTRANT_PROTO*) ;;
*) ctime_r_proto="REENTRANT_PROTO_${ctime_r_proto}" ;;
esac
echo "Prototype: $try" ;;
esac
;;
*) case "$susetheads" in
define) echo "ctime_r has no prototype, not using it." >&4 ;;
esac
d_ctime_r=undef
ctime_r_proto=0
;;
esac
;;
*) ctime_r_proto=0
;;
esac

```

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/threads/d_ctime_r.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 2000 Jarkko Hietaniemi

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?MAKE:d_fsync: Inlibc

?MAKE: -pick add \$@ %<

?S:d_fsync:

?S: This variable conditionally defines the HAS_FSYNC symbol, which

?S: indicates to the C program that the fsync() routine is available.

?S:.

?C:HAS_FSYNC:

?C: This symbol, if defined, indicates that the fsync routine is

?C: available to write a file's modified data and attributes to

?C: permanent storage.

?C:.

?H:#\$d_fsync HAS_FSYNC /**/

?H:.

?LINT:set d_fsync

: see if fsync exists

set fsync d_fsync

eval \$inlibc

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_fsync.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: h_sysfile.U 1 2006-08-24 12:32:52Z rmanfredi \$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic Licence,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic Licence; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: h_sysfile.U,v \$

?RCS: Revision 3.0 1993/08/18 12:08:13 ram

?RCS: Baseline for dist 3.0 netwide release.

```

?RCS:
?MAKE:h_sysfile: Nothing
?MAKE: -pick add $@ %<
?S:h_sysfile:
?S: This is variable gets set in various places to tell i_sys_file that
?S: <sys/file.h> should be included.
?S:.
: Initialize h_sysfile
h_sysfile=false

Found in path(s):
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/h_sysfile.U
No license file was found, but licenses were detected in source scan.

?RCS: $Id: i_regex.U 1 2006-08-24 12:32:52Z rmanfredi $
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: Original Author: Sidney C. Smith <scsmith@cbda9.apgea.army.mil>
?RCS:
?RCS: $Log: i_regex.U,v $
?RCS: Revision 3.0.1.1 1995/01/30 14:35:45 ram
?RCS: patch49: created
?RCS:
?RCS:
?MAKE:i_regex: Inhdr
?MAKE: -pick add $@ %<
?S:i_regex:
?S: This variable conditionally defines the I_REGEX symbol, which
?S: indicates to the C program that <regex.h> exists and should
?S: be included.
?S:.
?C:I_REGEX:
?C: This symbol, if defined, indicates that <regex.h> exists
and should
?C: be included.
?C:.
?H:#$i_regex I_REGEX /**/
?H:.
?LINT:set i_regex
: see if regex is available

```

```
set regex.h i_regex
eval $inhdr
```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/i_regex.U
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1996, Andy Dougherty

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: d_strtoul.U,v \$

?RCS: Revision 3.0.1.1 1997/02/28 15:46:43 ram

?RCS: patch61: created

?RCS:

?RCS:

?MAKE:d_strtoul: Inlibc

?MAKE: -pick add \$@ %<

?S:d_strtoul:

?S: This variable conditionally defines the HAS_STRTOUL symbol, which

?S: indicates to the C program that the strtoul() routine is available

?S: to provide conversion of strings to unsigned long.

?S:.

?C:HAS_STRTOUL (STRTOUL):

?C: This symbol, if defined, indicates that the strtoul routine is

?C: available

to provide conversion of strings to unsigned long.

?C:.

?H:#\$d_strtoul HAS_STRTOUL /**/

?H:.

?LINT:set d_strtoul

: see if strtoul exists

set strtoul d_strtoul

eval \$inlibc

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/d_strtoul.U
```

No license file was found, but licenses were detected in source scan.

```

?RCS: $Id: selecttype.U,v 3.0.1.3 1997/02/28 16:20:09 ram Exp $
?RCS:
?RCS: Copyright (c) 1991-1993, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 3.0.
?RCS:
?RCS: Original Author: Andy Dougherty <doughera@lafcol.lafayette.edu>
?RCS:
?RCS: $Log: selecttype.U,v $
?RCS: Revision 3.0.1.3 1997/02/28 16:20:09 ram
?RCS: patch61: always include <sys/select.h> when available for test
?RCS:
?RCS: Revision 3.0.1.2 1995/07/25 14:14:06 ram
?RCS: patch56: removed harmful spaces in assignment
?RCS:
?RCS: Revision 3.0.1.1 1994/06/20 07:06:31 ram
?RCS: patch30: created by ADO
?RCS:
?MAKE:selecttype: Protochk Oldconfig Myread cat
\
d_fd_set d_select d_socket i_systime i_sysselect extern_C
?MAKE: -pick add $@ %<
?S:selecttype:
?S: This variable holds the type used for the 2nd, 3rd, and 4th
?S: arguments to select. Usually, this is 'fd_set *', if HAS_FD_SET
?S: is defined, and 'int *' otherwise. This is only useful if you
?S: have select(), naturally.
?S:.
?C:Select_fd_set_t:
?C: This symbol holds the type used for the 2nd, 3rd, and 4th
?C: arguments to select. Usually, this is 'fd_set *', if HAS_FD_SET
?C: is defined, and 'int *' otherwise. This is only useful if you
?C: have select(), of course.
?C:.
?H:#define Select_fd_set_t $selecttype /**/
?H:.
?T:xxx nfd tmo try hdrs val
: check for type of arguments to select.
case "$selecttype" in
") case "$d_select" in
$define)
echo " "
$cat <<EOM
Checking to see what type of arguments are accepted by select().

```

EOM

```
hdrs="$define sys/types.h
$_systime sys/time.h
$_sysselect sys/select.h
$_socket sys/socket.h"
: The first arg can be int, unsigned,
or size_t
: The last arg may or may not be 'const'
val="
: void pointer has been seen but using that
: breaks the selectminbits test
for xxx in 'fd_set *' 'int *'; do
for nfd in 'int' 'size_t' 'unsigned long' 'unsigned' ; do
for tmo in 'struct timeval *' 'const struct timeval *'; do
case "$val" in
") try="$extern_C select _(($nfd, $xxx, $xxx, $xxx, $tmo));"
if ./protochk "$try" $hdrs; then
echo "Your system accepts $xxx."
val="$xxx"
fi
;;
esac
done
done
done
```

?X: In the unlikely event that none of those worked, prompt the user.

```
case "$val" in
") rp='What is the type for the 2nd, 3rd, and 4th arguments to select?'
case "$d_fd_set" in
$define) dflt="fd_set *" ;;
*) dflt="int *" ;;
esac
./myread
val=$ans
;;
esac
selecttype="$val"
;;
*) : no select, so pick a harmless default
selecttype='int *'
;;
esac
;;
esac
```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/protos/selecttype.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: i_syspoll.U 15 2006-08-30 18:21:51Z rmanfredi $
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?MAKE:i_syspoll: Inhdr
?MAKE: -pick add $@ %<
?S:i_syspoll:
?S: This variable conditionally defines the I_SYS_POLL symbol, which
?S: indicates to the C program that it should include <sys/poll.h>.
?S:.
?C:I_SYS_POLL:
?C: This symbol, if defined, indicates that the program may include
?C: <sys/poll.h>. When I_POLL is also defined, it's probably safest
?C: to only include <poll.h>.
?C:.
?H:#$i_syspoll I_SYS_POLL /**/
?H:.
?LINT:set i_syspoll
: see if there is
  a sys/poll.h file
set sys/poll.h i_syspoll
eval $inhdr
```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/i_syspoll.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id$
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: Original Author: Andy Dougherty <doughera@lafcol.lafayette.edu>
?RCS:
```

?RCS: \$Log: archlib.U,v \$

?RCS: Revision 3.0.1.5 1997/02/28 15:23:38 ram

?RCS: patch61: skip existence checks for archlib

?RCS:

?RCS: Revision 3.0.1.4 1995/09/25 09:15:18 ram

?RCS: patch59: unit is now forced to the top of Configure, if possible

?RCS:

?RCS: Revision 3.0.1.3 1995/02/15 14:14:14 ram

?RCS: patch51: architecture name is now computed by a separate unit

?RCS:

?RCS: Revision 3.0.1.2 1995/01/30 14:32:22 ram

?RCS:

patch49: archname is now systematically recomputed

?RCS: patch49: can now handle installation prefix changes (from WED)

?RCS:

?RCS: Revision 3.0.1.1 1994/10/29 16:02:36 ram

?RCS: patch36: created by ADO

?RCS:

?MAKE:d_archlib archlib archlibexp installarchlib: archname afs spackage \
 cat Getfile Loc Oldconfig prefixexp privlib test Prefixit Prefixup

?MAKE: -pick add \$@ %<

?Y:TOP

?S:d_archlib:

?S: This variable conditionally defines ARCHLIB to hold the pathname

?S: of architecture-dependent library files for \$package. If

?S: \$archlib is the same as \$privlib, then this is set to undef.

?S:.

?S:archlib:

?S: This variable holds the name of the directory in which the user wants

?S: to put architecture-dependent public library files for \$package.

?S: It is most often a local directory such as /usr/local/lib.

?S: Programs using this variable must be prepared to deal

?S: with filename expansion.

?S:.

?S:archlibexp:

?S: This variable is the same as the archlib variable, but is

?S: filename

expanded at configuration time, for convenient use.

?S:.

?S:installarchlib:

?S: This variable is really the same as archlibexp but may differ on

?S: those systems using AFS. For extra portability, only this variable

?S: should be used in makefiles.

?S:.

?C:ARCHLIB:

?C: This variable, if defined, holds the name of the directory in

?C: which the user wants to put architecture-dependent public

?C: library files for \$package. It is most often a local directory

?C: such as /usr/local/lib. Programs using this variable must be
 ?C: prepared to deal with filename expansion. If ARCHLIB is the
 ?C: same as PRIVLIB, it is not defined, since presumably the
 ?C: program already searches PRIVLIB.
 ?C:.
 ?C:ARCHLIB_EXP:
 ?C: This symbol contains the ~name expanded version of ARCHLIB, to be used
 ?C: in programs that are not prepared to deal with ~ expansion at run-time.
 ?C:.
 ?H:#\$d_archlib ARCHLIB "\$sarchlib" /**/
 ?H:#\$d_archlib ARCHLIB_EXP "\$sarchlibexp" /**/
 ?H:.

```
: determine where public architecture
dependent libraries go
set archlib archlib
eval $prefixit
case "$sarchlib" in
")
case "$sprivlib" in
")
dflt=`./loc . ." $prefixexp/lib /usr/local/lib /usr/lib /lib`
set dflt
eval $prefixup
;;
*) dflt="$sprivlib/$sarchname";;
esac
;;
*) dflt="$sarchlib";;
esac
cat <<EOM
```

\$spackage contains architecture-dependent library files. If you are sharing libraries in a heterogeneous environment, you might store these files in a separate location. Otherwise, you can just include them with the rest of the public library files.

```
EOM
fn=d+~
rp='Where do you want to put the public architecture-dependent libraries?'
./getfile
archlib="$ans"
archlibexp="$ansexp"

if $afs; then
$cat <<EOM
```

Since you are running AFS, I need to distinguish the directory in which private files reside from the directory in which they are installed (and from

which they are presumably copied to the former directory by occult means).

EOM

```
case "$installarchlib" in
  *) dflt=`echo $sarchlibexp | sed 's#^/afs/#/afs/#^';`
  *) dflt="$installarchlib";
esac
fn=de~
rp='Where will architecture-dependent library files be installed?'
./getfile
installarchlib="$ans"
else
installarchlib="$sarchlibexp"
fi
if $test X"$sarchlib" = X"$sprivlib"; then
d_archlib="$undef"
else
d_archlib="$define"
fi
```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/archlib.U
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: defeditor.U 1 2006-08-24 12:32:52Z rmanfredi \$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic Licence,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic Licence; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: defeditor.U,v \$

?RCS: Revision 3.0.1.1 1995/01/11 15:30:16 ram

?RCS: patch45: can now use the 'vi' variable since path stripping is deferred

?RCS:

?RCS: Revision 3.0 1993/08/18 12:08:05 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?MAKE: defeditor: Getfile Oldconfig Loc vi

?MAKE: -pick add \$@ %<

?S: defeditor:

?S: This variable contains the eventual value of the DEFEDITOR symbol,

?S: which contains the name of the default editor.

```

?S:.
?C:DEFEDITOR:
?C: This
    symbol contains the full pathname of the default editor.
?C:.
?H:#define DEFEDITOR "$defeditor" /**/
?H:.
: determine default editor
echo " "
case "$defeditor" in
")
case "$vi" in
*/*) dflt="$vi";;
*) dflt=/usr/ucb/vi;;
esac
;;
*) dflt="$defeditor"
;;
esac
fn=f/
rp="What is the default editor on your system?"
./getfile
defeditor="$ans"

```

Found in path(s):

```

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/defeditor.U

```

No license file was found, but licenses were detected in source scan.

```

?RCS: $Id: i_sysresrc.U 1 2006-08-24 12:32:52Z rmanfredi $
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: $Log: i_sysresrc.U,v $
?RCS: Revision 3.0 1993/08/18 12:08:34 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?X:
?X: Look wether <sys/resource.h> needs to be included
?X:
?MAKE:i_sysresrc: Inhdr
?MAKE: -pick add $@ %<

```

```
?S:i_sysresrc:
?S: This variable conditionally defines the I_SYS_RESOURCE symbol,
?S: and indicates whether a C program should include <sys/resource.h>.
?S:.
?C:I_SYS_RESOURCE (I_SYSRESOURCE):
?C: This symbol, if defined, indicates
to the C program that it should
?C: include <sys/resource.h>.
?C:.
?H:#$i_sysresrc I_SYS_RESOURCE /**/
?H:.
?LINT:set i_sysresrc
: see if sys/resource.h has to be included
set sys/resource.h i_sysresrc
eval $inhdr
```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/i_sysresrc.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: d_attribut.U 1 2006-08-24 12:32:52Z rmanfredi $
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 3.0.
?RCS:
?RCS: Original Author: Andy Dougherty <doughera@lafcol.lafayette.edu>
?RCS:
?RCS: $Log: d_attribut.U,v $
?RCS: Revision 3.0.1.3 1995/01/30 14:33:45 ram
?RCS: patch49: test C program now includes <stdio.h> (WED)
?RCS:
?RCS: Revision 3.0.1.2 1995/01/11 15:25:47 ram
?RCS: patch45: fixed typo in the d_attribut variable (ADO)
?RCS:
?RCS: Revision 3.0.1.1 1994/10/29 16:08:55 ram
?RCS: patch36: created by ADO
?RCS:
?MAKE:d_attribute_deprecated d_attribute_format
d_attribute_malloc \
d_attribute_nonnull d_attribute_noreturn d_attribute_pure \
d_attribute_unused d_attribute_warn_unused_result \
d_printf_format_null: \
```

Myread Oldconfig cat cc cflags rm Setvar contains i_stdlib run

?MAKE: -pick add \$@ %<

?S:d_attribute_format:

?S: This variable conditionally defines HASATTRIBUTE_FORMAT, which

?S: indicates the C compiler can check for printf-like formats.

?S:.

?S:d_attribute_deprecated:

?S: This variable conditionally defines HASATTRIBUTE_DEPRECATED, which

?S: indicates that GCC can handle the attribute for marking deprecated

?S: APIs

?S:.

?S:d_printf_format_null:

?S: This variable conditionally defines PRINTF_FORMAT_NULL_OK, which

?S: indicates the C compiler allows printf-like formats to be null.

?S:.

?S:d_attribute_malloc:

?S: This variable conditionally defines HASATTRIBUTE_MALLOC, which

?S: indicates the C compiler can understand functions as having

?S: malloc-like semantics.

?S:.

?S:d_attribute_nonnull:

?S: This variable conditionally

defines HASATTRIBUTE_NONNULL, which

?S: indicates that the C compiler can know that certain arguments

?S: must not be NULL, and will check accordingly at compile time.

?S:.

?S:d_attribute_noreturn:

?S: This variable conditionally defines HASATTRIBUTE_NORETURN, which

?S: indicates that the C compiler can know that certain functions

?S: are guaranteed never to return.

?S:.

?S:d_attribute_pure:

?S: This variable conditionally defines HASATTRIBUTE_PURE, which

?S: indicates that the C compiler can know that certain functions

?S: are "pure" functions, meaning that they have no side effects, and

?S: only rely on function input and/or global data for their results.

?S:.

?S:d_attribute_unused:

?S: This variable conditionally defines HASATTRIBUTE_UNUSED, which

?S: indicates that the C compiler can know that certain variables

?S: and arguments may not always be used, and to not throw warnings

?S: if they don't get used.

?S:.

?S:d_attribute_warn_unused_result:

?S: This variable conditionally

defines

?S: HASATTRIBUTE_WARN_UNUSED_RESULT, which indicates that the C

?S: compiler can know that certain functions have a return values

?S: that must not be ignored, such as malloc() or open().

?S:.

?C:HASATTRIBUTE_FORMAT ~ %< (GNU_ATTRIBUTE_CHECK):

?C: Can we handle GCC attribute for checking printf-style formats

?C:.

?C:PRINTF_FORMAT_NULL_OK:

?C: Allows __printf__ format to be null when checking printf-style

?C:.

?C:HASATTRIBUTE_MALLOC:

?C: Can we handle GCC attribute for malloc-style functions.

?C:.

?C:HASATTRIBUTE_NONNULL:

?C: Can we handle GCC attribute for nonnull function parms.

?C:.

?C:HASATTRIBUTE_NORETURN:

?C: Can we handle GCC attribute for functions that do not return

?C:.

?C:HASATTRIBUTE_PURE:

?C: Can we handle GCC attribute for pure functions

?C:.

?C:HASATTRIBUTE_UNUSED:

?C: Can we handle GCC attribute for unused variables and arguments

?C:.

?C:HASATTRIBUTE_DEPRECATED:

?C: Can we handle GCC attribute for marking deprecated APIs

?C:.

?C:HASATTRIBUTE_WARN_UNUSED_RESULT

~ %< (HASATTRIBUTE):

?C: Can we handle GCC attribute for warning on unused results

?C:.

?H:%<:#\$d_attribute_deprecated HASATTRIBUTE_DEPRECATED /**/

?H:%<:#\$d_attribute_format HASATTRIBUTE_FORMAT /**/

?H:%<:#\$d_printf_format_null PRINTF_FORMAT_NULL_OK /**/

?H:%<:#\$d_attribute_noreturn HASATTRIBUTE_NORETURN /**/

?H:%<:#\$d_attribute_malloc HASATTRIBUTE_MALLOC /**/

?H:%<:#\$d_attribute_nonnull HASATTRIBUTE_NONNULL /**/

?H:%<:#\$d_attribute_pure HASATTRIBUTE_PURE /**/

?H:%<:#\$d_attribute_unused HASATTRIBUTE_UNUSED /**/

?H:%<:#\$d_attribute_warn_unused_result HASATTRIBUTE_WARN_UNUSED_RESULT /**/

?H:.

?F:!attrib !attrib.out !attrib.c

?LINT:set d_attribute_deprecated

?LINT:set d_attribute_format

?LINT:set d_printf_format_null

?LINT:set d_attribute_malloc

?LINT:set d_attribute_nonnull

?LINT:set d_attribute_noreturn

?LINT:set d_attribute_pure

```

?LINT:set d_attribute_unused
?LINT:set d_attribute_warn_unused_result
: Look for GCC-style attribute format
case "$d_attribute_format" in
")
echo
" "
echo "Checking whether your compiler can handle __attribute__((format)) ..." >&4
$cat >attrib.c <<'EOCP'
#include <stdio.h>
void my_special_printf(char* pat,...) __attribute__((__format__(__printf__,1,2)));
EOCP
if $cc $ccflags -c attrib.c >attrib.out 2>&1 ; then
if $contains 'warning' attrib.out >/dev/null 2>&1; then
echo "Your C compiler doesn't support __attribute__((format))."
val="$undef"
else
echo "Your C compiler supports __attribute__((format))."
val="$define"
fi
else
echo "Your C compiler doesn't seem to understand __attribute__ at all."
val="$undef"
fi
;;
*) val="$d_attribute_format" ;;
esac
set d_attribute_format
eval $setvar
$rm -f attrib*

: Look for GCC-style attribute format with null format allowed
case "$d_printf_format_null" in
") case "$d_attribute_format" in
$define)
echo " "
echo "Checking whether your compiler allows __printf__ format to be null ..." >&4
$cat >attrib.c <<'EOCP
#include <stdio.h>
#ifdef I_STDLIB
#include
<stdlib.h>
#endif
int null_printf (char* pat,...) __attribute__((__format__(__printf__,1,2)));
int null_printf (char* pat,...) { return (int)pat; }
int main () { exit(null_printf(NULL)); }
EOCP

```

```

if $cc $cflags -o attrib attrib.c >attrib.out 2>&1 ; then
    : run the executable in case it produces a run-time warning
    if $run ./attrib >>attrib.out 2>&1; then
if $contains 'warning' attrib.out >/dev/null 2>&1; then
    echo "Your C compiler doesn't allow __printf__ format to be null."
    val="$undef"
else
    echo "Your C compiler allows __printf__ format to be null."
    val="$define"
fi
    else
    echo "Your C compiler executable failed with __printf__ format null."
    val="$undef"
fi
    else
    echo "Your C compiler fails with __printf__ format null."
    val="$undef"
    fi
    ;;
    *) val="$undef" ;;
esac
;;
*) val="$d_printf_format_null" ;;
esac
set d_printf_format_null
eval $setvar
$rm -f attrib*

: Look for GCC-style attribute malloc
case "$d_attribute_malloc"
in
")
echo " "
echo "Checking whether your compiler can handle __attribute__((malloc)) ..." >&4
$cat >attrib.c <<'EOCP'
#include <stdio.h>
char *go_get_some_memory( int how_many_bytes ) __attribute__((malloc));
EOCP
if $cc $cflags -c attrib.c >attrib.out 2>&1 ; then
if $contains 'warning' attrib.out >/dev/null 2>&1; then
    echo "Your C compiler doesn't support __attribute__((malloc))."
    val="$undef"
else
    echo "Your C compiler supports __attribute__((malloc))."
    val="$define"
fi
    else
    echo "Your C compiler doesn't seem to understand __attribute__ at all."

```

```

    val="$undef"
fi
;;
*) val="$d_attribute_malloc" ;;
esac
set d_attribute_malloc
eval $setvar
$rm -f attrib*

: Look for GCC-style attribute nonnull
case "$d_attribute_nonnull" in
")
echo " "
echo "Checking whether your compiler can handle __attribute__((nonnull(1))) ..." >&4
$cat >attrib.c <<'EOCP'
#include <stdio.h>
void do_something (char *some_pointer,...) __attribute__((nonnull(1)));
EOCP
if $cc $ccflags -c attrib.c
>attrib.out 2>&1 ; then
if $contains 'warning' attrib.out >/dev/null 2>&1; then
echo "Your C compiler doesn't support __attribute__((nonnull))."
val="$undef"
else
echo "Your C compiler supports __attribute__((nonnull))."
val="$define"
fi
else
echo "Your C compiler doesn't seem to understand __attribute__ at all."
val="$undef"
fi
;;
*) val="$d_attribute_nonnull" ;;
esac
set d_attribute_nonnull
eval $setvar
$rm -f attrib*

: Look for GCC-style attribute noreturn
case "$d_attribute_noreturn" in
")
echo " "
echo "Checking whether your compiler can handle __attribute__((noreturn)) ..." >&4
$cat >attrib.c <<'EOCP'
#include <stdio.h>
void fall_over_dead( void ) __attribute__((noreturn));
EOCP
if $cc $ccflags -c attrib.c >attrib.out 2>&1 ; then

```

```

if $contains 'warning' attrib.out >/dev/null 2>&1; then
  echo "Your C compiler doesn't support __attribute__((noreturn))."
  val="$undef"
else
  echo "Your C compiler supports __attribute__((noreturn))."
  val="$define"
fi
else
  echo
  "Your C compiler doesn't seem to understand __attribute__ at all."
  val="$undef"
fi
;;
*) val="$d_attribute_noreturn" ;;
esac
set d_attribute_noreturn
eval $setvar
$rm -f attrib*

: Look for GCC-style attribute pure
case "$d_attribute_pure" in
  ")
  echo " "
  echo "Checking whether your compiler can handle __attribute__((pure)) ..." >&4
  $cat >attrib.c <<'EOCP'
  #include <stdio.h>
  int square( int n ) __attribute__((pure));
  EOCP
  if $cc $ccflags -c attrib.c >attrib.out 2>&1 ; then
  if $contains 'warning' attrib.out >/dev/null 2>&1; then
    echo "Your C compiler doesn't support __attribute__((pure))."
    val="$undef"
  else
    echo "Your C compiler supports __attribute__((pure))."
    val="$define"
  fi
  else
    echo "Your C compiler doesn't seem to understand __attribute__ at all."
    val="$undef"
  fi
  ;;
  *) val="$d_attribute_pure" ;;
esac
set d_attribute_pure
eval $setvar
$rm -f attrib*

: Look for GCC-style attribute unused

```

```

case "$d_attribute_unused" in
")
echo " "
echo "Checking whether your compiler
can handle __attribute__((unused)) ..." >&4
$cat >attrib.c <<'EOCP'
#include <stdio.h>
int do_something( int dummy __attribute__((unused)), int n );
EOCP
if $cc $ccflags -c attrib.c >attrib.out 2>&1 ; then
if $contains 'warning' attrib.out >/dev/null 2>&1; then
echo "Your C compiler doesn't support __attribute__((unused))."
val="$undef"
else
echo "Your C compiler supports __attribute__((unused))."
val="$define"
fi
else
echo "Your C compiler doesn't seem to understand __attribute__ at all."
val="$undef"
fi
*) val="$d_attribute_unused" ;;
esac
set d_attribute_unused
eval $setvar
$rm -f attrib*

```

: Look for GCC-style attribute deprecated

```

case "$d_attribute_deprecated" in
")
echo " "
echo "Checking whether your compiler can handle __attribute__((deprecated)) ..." >&4
$cat >attrib.c <<'EOCP'
#include <stdio.h>
int I_am_deprecated(void) __attribute__((deprecated));
EOCP
if $cc $ccflags -c attrib.c >attrib.out 2>&1 ; then
if $contains 'warning' attrib.out >/dev/null 2>&1;
then
echo "Your C compiler doesn't support __attribute__((deprecated))."
val="$undef"
else
echo "Your C compiler supports __attribute__((deprecated))."
val="$define"
fi
else
echo "Your C compiler doesn't seem to understand __attribute__ at all."

```

```

val="$undef"
fi
;;
*) val="$d_attribute_deprecated" ;;
esac
set d_attribute_deprecated
eval $setvar
$rm -f attrib*

: Look for GCC-style attribute warn_unused_result
case "$d_attribute_warn_unused_result" in
")
echo " "
echo "Checking whether your compiler can handle __attribute__((warn_unused_result)) ..." >&4
$cat >attrib.c <<'EOCP'
#include <stdio.h>
int I_will_not_be_ignored(void) __attribute__((warn_unused_result));
EOCP
if $cc $ccflags -c attrib.c >attrib.out 2>&1 ; then
if $contains 'warning' attrib.out >/dev/null 2>&1 ; then
echo "Your C compiler doesn't support __attribute__((warn_unused_result))."
val="$undef"
else
echo "Your C compiler supports __attribute__((warn_unused_result))."
val="$define"
fi
else
echo
"Your C compiler doesn't seem to understand __attribute__ at all."
val="$undef"
fi
;;
*) val="$d_attribute_warn_unused_result" ;;
esac
set d_attribute_warn_unused_result
eval $setvar
$rm -f attrib*

```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/modified/d_attrib.U
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1999, Jarkko Hietaniemi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 3.0.

?RCS:

?MAKE:d_sigwaitinfo: Inlibc

?MAKE: -pick add \$@ %<

?S:d_sigwaitinfo:

?S: This variable conditionally defines HAS_SIGWAITINFO

?S: if sigwaitinfo() is available to wait a signal and additional

?S: information.

?S:.

?C:HAS_SIGWAITINFO:

?C: This symbol, if defined, indicates that the sigwaitinfo

?C: system call is available to wait a signal and additional information.

?C:.

?H:#\$d_sigwaitinfo HAS_SIGWAITINFO /**/

?H:.

?LINT:set d_sigwaitinfo

: see if sigwaitinfo exists

set sigwaitinfo d_sigwaitinfo

eval \$inlibc

Found in path(s):

*

/opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_sigwaitinfo.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_portable.U,v 3.0.1.2 1995/01/11 15:28:52 ram Exp \$

?RCS:

?RCS: Copyright (c) 1991-1993, Raphael Manfredi

?RCS:

?RCS: This file is included with or a derivative work of a file included

?RCS: with the metaconfig program of Raphael Manfredi's "dist" distribution.

?RCS: In accordance with clause 7 of dist's modified Artistic License:

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?RCS: \$Log: d_portable.U,v \$

?RCS: Revision 3.0.1.2 1995/01/11 15:28:52 ram

?RCS: patch45: executable path stripping moved to the end in Config_sh.U

?RCS:

?RCS: Revision 3.0.1.1 1993/12/15 08:21:17 ram

?RCS: patch15: did not strip variables properly when needed

?RCS: patch15: now also strips down variables from trylist

?RCS:

```

?RCS: Revision 3.0 1993/08/18 12:06:48 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?X:
    This is the same as the dist version, except I don't bother
?X: prompting people since it makes no difference for perl5,
?X: and only confuses people.
?X:
?X: The Loc unit is wanted to get the definition of all the locating variables.
?X:
?MAKE:d_portable: Loc Oldconfig
?MAKE: -pick add $@ %<
?S:d_portable:
?S: This variable conditionally defines the PORTABLE symbol, which
?S: indicates to the C program that it should not assume that it is
?S: running on the machine it was compiled on.
?S:.
?C:PORTABLE:
?C: This symbol, if defined, indicates to the C program that it should
?C: not assume that it is running on the machine it was compiled on.
?C: The program should be prepared to look up the host name, translate
?C: generic filenames, use PATH, etc.
?C:.
?H:#$d_portable PORTABLE /**/
?H:.
?D:d_portable="
: decide how portable to be. Allow command line overrides.
case "$d_portable" in
"$undef") ;;
*) d_portable="$define" ;;
esac

```

Found in path(s):

```

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/perl/d_portable.U

```

No license file was found, but licenses were detected in source scan.

```

?RCS: $Id: i_fcctl.U 1 2006-08-24 12:32:52Z rmanfredi $
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: $Log: i_fcctl.U,v $

```

```

?RCS: Revision 3.0 1993/08/18 12:08:18 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:i_fcntl: h_fcntl h_sysfile +i_sysfile Inhdr Setvar
?MAKE: -pick add $@ %<
?S:i_fcntl:
?S: This variable controls the value of I_FCNTL (which tells
?S: the C program to include <fcntl.h>).
?S:.
?C:I_FCNTL (HDR_O_STUFF FCNTL):
?C: This manifest constant tells the C program to include <fcntl.h>.
?C:.
?H:#$i_fcntl I_FCNTL /**/
?H:.
?T:val
?X:
    Make line lists +i_sysfile to ensure tests for <sys/file.h> will be
?X: conducted prior tests for <fcntl.h>, hece making sure the h_sysfile
?X: variable is correctly set when we reach that unit.
?LINT:set i_fcntl
?LINT:use i_sysfile
?LINT:change h_fcntl
: see if fcntl.h is there
val="
set fcntl.h val
eval $inhdr

: see if we can include fcntl.h
case "$val" in
"$define")
    echo " "
    if $h_fcntl; then
        val="$define"
        echo "We'll be including <fcntl.h>." >&4
    else
        val="$undef"
        if $h_sysfile; then
            echo "We don't need to include <fcntl.h> if we include <sys/file.h>." >&4
        else
            echo "We won't be including <fcntl.h>." >&4
        fi
    fi
;;
*)
    h_fcntl=false
    val="$undef"
;;
esac

```

```
set i_fcntl
eval $setvar
```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/i_fcntl.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: prototype.U,v 3.0.1.3 1994/05/06 15:11:49 ram Exp $
?RCS:
?RCS: Copyright (c) 1991-1993, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 3.0.
?RCS:
?RCS: $Log: prototype.U,v $
?RCS: Revision 3.0.1.3 1994/05/06 15:11:49 ram
?RCS: patch23: ensure cc flags used when looking for prototype support
?RCS:
?RCS: Revision 3.0.1.2 1994/01/24 14:15:36 ram
?RCS: patch16: prototype handling macros now appear only when needed
?RCS:
?RCS: Revision 3.0.1.1 1993/08/25 14:03:12 ram
?RCS: patch6: defines were referring to non-existent VOID symbol
?RCS:
?RCS: Revision 3.0 1993/08/18 12:09:36 ram
?RCS: Baseline for dist
3.0 netwide release.
?RCS:
?MAKE:prototype: Myread Oldconfig cat +cc +ccflags rm Setvar i_stdlib
?MAKE: -pick add $@ %<
?S:prototype:
?S: This variable holds the eventual value of CAN_PROTOTYPE, which
?S: indicates the C compiler can handle function prototypes.
?S:.
?C:CAN_PROTOTYPE ~ %<:
?C: If defined, this macro indicates that the C compiler can handle
?C: function prototypes.
?C:.
?C:DOTS:
?C: This macro is used to specify the ... in function prototypes which
?C: have arbitrary additional arguments.
?C:.
?C:NXT_ARG:
?C: This macro is used to separate arguments in the declared argument list.
```

?C:.

?C:P_FUNC:

?C: This macro is used to declare "private" (static) functions.

?C: It takes three arguments: the function type and name, a parenthesized

?C: traditional (comma separated) argument list, and the declared argument

?C: list (in which arguments are separated with NXT_ARG, and additional

?C: arbitrary arguments are specified with DOTS). For example:

?C:

?C: P_FUNC(int foo, (bar, baz),

int bar NXT_ARG char *baz[])

?C:.

?C:P_FUNC_VOID:

?C: This macro is used to declare "private" (static) functions that have

?C: no arguments. The macro takes one argument: the function type and name.

?C: For example:

?C:

?C: P_FUNC_VOID(int subr)

?C:.

?C:V_FUNC:

?C: This macro is used to declare "public" (non-static) functions.

?C: It takes three arguments: the function type and name, a parenthesized

?C: traditional (comma separated) argument list, and the declared argument

?C: list (in which arguments are separated with NXT_ARG, and additional

?C: arbitrary arguments are specified with DOTS). For example:

?C:

?C: V_FUNC(int main, (argc, argv), int argc NXT_ARG char *argv[])

?C:.

?C:V_FUNC_VOID:

?C: This macro is used to declare "public" (non-static) functions that have

?C: no arguments. The macro takes one argument: the function type and name.

?C: For example:

?C:

?C: V_FUNC_VOID(int fork)

?C:.

?C:_(P):

?C: This macro is used to declare function parameters for folks who want

?C: to

make declarations with prototypes using a different style than

?C: the above macros. Use double parentheses. For example:

?C:

?C: int main _((int argc, char *argv[]));

?C:.

?H:%<:#\$prototype CAN_PROTOTYPE /**/

?H:?:#ifdef CAN_PROTOTYPE

?H:?:NXT_ARG:#define NXT_ARG ,

?H:?:DOTS:#define DOTS , ...

?H:?:V_FUNC:#define V_FUNC(name, arglist, args)name(args)

?H:?:P_FUNC:#define P_FUNC(name, arglist, args)static name(args)

```

?H:?V_FUNC_VOID:#define V_FUNC_VOID(name)name(void)
?H:?P_FUNC_VOID:#define P_FUNC_VOID(name)static name(void)
?H:?_:#define _(args) args
?H:?_:#else
?H:?NXT_ARG:#define NXT_ARG ;
?H:?DOTS:#define DOTS
?H:?V_FUNC:#define V_FUNC(name, arglist, args)name arglist args;
?H:?P_FUNC:#define P_FUNC(name, arglist, args)static name arglist args;
?H:?V_FUNC_VOID:#define V_FUNC_VOID(name)name()
?H:?P_FUNC_VOID:#define P_FUNC_VOID(name)static name()
?H:?_:#define _(args) ()
?H:?_:#endif
?H:.
?W:%<:NXT_ARG DOTS V_FUNC P_FUNC V_FUNC_VOID P_FUNC_VOID _
?LINT:set prototype
: Cruising
  for prototypes
  echo " "
  echo "Checking out function prototypes..." >&4
$cat >prototype.c <<EOCP
#$_stdlib I_STDLIB
#ifdef I_STDLIB
#include <stdlib.h>
#endif
int main(int argc, char *argv[]) {
  exit(0);}
EOCP
if $cc $ccflags -c prototype.c >prototype.out 2>&1 ; then
  echo "Your C compiler appears to support function prototypes."
  val="$define"
else
  echo "Your C compiler doesn't seem to understand function prototypes."
  val="$undef"
fi
set prototype
eval $setvar
$rm -f prototype*

```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/modified/prototype.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: d_msgrcv.U 1 2006-08-24 12:32:52Z rmanfredi $
```

```
?RCS:
```

```
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
```

```
?RCS:
```

```
?RCS: You may redistribute only under the terms of the Artistic Licence,
```

?RCS: as specified in the README file that comes with the distribution.
 ?RCS: You may reuse parts of this distribution only within the terms of
 ?RCS: that same Artistic Licence; a copy of which may be found at the root
 ?RCS: of the source tree for dist 4.0.
 ?RCS:
 ?RCS: \$Log: d_msgrcv.U,v \$
 ?RCS: Revision 3.0 1993/08/18 12:06:40 ram
 ?RCS: Baseline for dist 3.0 netwide release.
 ?RCS:
 ?MAKE:d_msgrcv: Inlibc
 ?MAKE: -pick add \$@ %<
 ?S:d_msgrcv:
 ?S: This variable conditionally defines the HAS_MSGRCV symbol, which
 ?S: indicates to the C program that the msgrcv() routine is available.
 ?S:.
 ?C:HAS_MSGRCV:
 ?C: This symbol, if defined, indicates that the msgrcv() routine is
 ?C: available to extract a message from the message queue.
 ?C:.
 ?H:#\$d_msgrcv
 HAS_MSGRCV /**/
 ?H:.
 ?LINT:set d_msgrcv
 : see if msgrcv exists
 set msgrcv d_msgrcv
 eval \$inlibc

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/d_msgrcv.U

No license file was found, but licenses were detected in source scan.

?RCS: You may distribute under the terms of either the GNU General Public
 ?RCS: License or the Artistic License, as specified in the README file.
 ?RCS:
 ?MAKE:d_rint: Inlibc
 ?MAKE: -pick add \$@ %<
 ?S:d_rint:
 ?S: This variable conditionally defines the HAS_RINT symbol, which
 ?S: indicates to the C program that the rint() routine is available.
 ?S:.
 ?C:HAS_RINT:
 ?C: This symbol, if defined, indicates that the rint routine is
 ?C: available to return the nearest integral value to x as double
 ?C: using the current rounding mode.
 ?C:.
 ?H:#\$d_rint HAS_RINT /**/
 ?H:.

```
?LINT:set d_rint
: see if rint exists
set rint d_rint
eval $inlibc
```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/perl/d_rint.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: i_shadow.U,v $
```

```
?RCS:
```

```
?RCS: Copyright (c) 2000 Jarkko Hietaniemi
```

```
?RCS:
```

```
?RCS: You may distribute under the terms of either the GNU General Public
```

```
?RCS: License or the Artistic License, as specified in the README file.
```

```
?RCS:
```

```
?MAKE:i_prot: Inhdr Hasfield
```

```
?MAKE: -pick add $@ %<
```

```
?S:i_prot:
```

```
?S: This variable conditionally defines the I_PROT symbol, and indicates
```

```
?S: whether a C program should include <prot.h>.
```

```
?S:.
```

```
?C:I_PROT:
```

```
?C: This symbol, if defined, indicates that <prot.h> exists and
```

```
?C: should be included.
```

```
?C:.
```

```
?H:#$i_prot I_PROT /**/
```

```
?H:.
```

```
?LINT:set i_prot
```

```
: see if this is a prot.h system
```

```
set prot.h i_prot
```

```
eval $inhdr
```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/perl/i_prot.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id$
```

```
?RCS:
```

```
?RCS: Copyright (c) 2009 H.Merijn Brand
```

```
?RCS:
```

```
?RCS: You may distribute under the terms of either the GNU General Public
```

```
?RCS: License or the Artistic License, as specified in the README file.
```

```
?RCS:
```

```
?MAKE:d_inetntop: Inlibc
```

```
?MAKE: -pick add $@ %<
```

?S:d_inetntop:
?S: This variable conditionally defines the HAS_INETNTOP symbol,
?S: which indicates to the C program that the inet_ntop() function
?S: is available.

?S:.

?C:HAS_INETNTOP:

?C: This symbol, if defined, indicates that the inet_ntop() function
?C: is available to parse IPv4 and IPv6 strings.

?C:.

?H:#\$d_inetntop HAS_INETNTOP /**/

?H:.

?LINT:set d_inetntop

: see if inet_ntop exists

set inet_ntop d_inetntop

eval \$inlibc

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_inetntop.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: mandirs.U,v \$

?RCS:

?RCS: Copyright (c) 2000, Andy Dougherty

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 3.0.

?RCS:

?RCS: \$Log: mandirs.U,v \$

?RCS:

?MAKE: man1 man2 man3 man4 man5 man6 man7 man8 \

man2ext man4ext man5ext man6ext man7ext man8ext: \

mandirstyle man1dir man1ext man3dir prefix sed

?MAKE: -pick add \$@ %<

?Y:TOP

?X: This unit just provides convenient definitions so that

?X: MakeMaker can sensibly assume that man5 pages go in

?X: \$prefix/man/\$man5 (or \$siteprefix/man/\$man5 as appropriate)

?X: and the BSD vs. SVR4 directory naming conventions will be

?X: handled automatically, as will older System V

?X: \$prefix/man/u_man

style directories.

?X:

?S:man1:

?S: Man 1 pages will normally be installed in \$prefix/man/\$man1.

?S: This variable handles SysV/SVR4/BSD conventions appropriately.

?S: See mandirstyle.

?S:.

?S:man2:

?S: Man 2 pages will normally be installed in \$prefix/man/\$man2.

?S: This variable handles SysV/SVR4/BSD conventions appropriately.

?S: See mandirstyle.

?S:.

?S:man2ext:

?S: Extension for man2 pages, typically just '2'. See mandirstyle.

?S:.

?S:man3:

?S: Man 3 pages will normally be installed in \$prefix/man/\$man3.

?S: This variable handles SysV/SVR4/BSD conventions appropriately.

?S: See mandirstyle.

?S:.

?S:man4:

?S: Man 4 pages will normally be installed in \$prefix/man/\$man4.

?S: This variable handles SysV/SVR4/BSD conventions appropriately.

?S: See mandirstyle.

?S:.

?S:man4ext:

?S: Extension for man4 pages, typically just '4'. See mandirstyle.

?S:.

?S:man5:

?S: Man 5 pages will normally be installed in \$prefix/man/\$man5.

?S: This variable handles SysV/SVR4/BSD conventions appropriately.

?S: See

mandirstyle.

?S:.

?S:man5ext:

?S: Extension for man5 pages, typically just '5'. See mandirstyle.

?S:.

?S:man6:

?S: Man 6 pages will normally be installed in \$prefix/man/\$man6.

?S: This variable handles SysV/SVR4/BSD conventions appropriately.

?S: See mandirstyle.

?S:.

?S:man6ext:

?S: Extension for man6 pages, typically just '6'. See mandirstyle.

?S:.

?S:man7:

?S: Man 7 pages will normally be installed in \$prefix/man/\$man7.

?S: This variable handles SysV/SVR4/BSD conventions appropriately.

?S: See mandirstyle.

?S:.

?S:man7ext:

?S: Extension for man7 pages, typically just '7'. See mandirstyle.

```

?S:.
?S:man8:
?S: Man 8 pages will normally be installed in $prefix/man/$man8.
?S: This variable handles SysV/SVR4/BSD conventions appropriately.
?S: See mandirstyle.
?S:.
?S:man8ext:
?S: Extension for man8 pages, typically just '8'. See mandirstyle.
?S:.
?LINT: set man2 man4 man5 man6 man7 man8
?LINT: set man2ext man4ext
?LINT: set man5ext man6ext man7ext man8ext
?T: num s ts
text
?X: eval fools metalint
?T: man
: Determine locations for other man pages. For example, programs
: should place man4 pages in $prefix/man/$man4 with an extension
: of $man4ext. Use bsd naming conventions. See mandirstyle.
: man1 and man3 are handled separately above.
echo "Deducing locations for other man pages for future use."
: Deduce man1 and man3 from existing variables. Keep them for completeness.
: This approach preserves an existing SystemV-style
: /usr/local/man/l_man/man1 hierarchy.
man1=`echo $man1dir | $sed -e "s!$prefix/man/!!"``
man3=`echo $man3dir | $sed -e "s!$prefix/man/!!"``
for num in 2 4 5 6 7 8; do
s=$num
case "$mandirstyle" in
sysv|svr4)
case "$num" in
4) s='7' ;;
5) s='4' ;;
7) s='5' ;;
8) s='1M' ;;
esac
;;
esac
eval "ts=\"\$man${num}\""
eval "text=\"\$man${num}ext\""
case "$ts" in
") ts=`echo $man1 | $sed -e "s/1/$s/g"`` ;;
none|$undef) ts=' ' ;;
esac
case "$text" in
") text=`echo $man1ext | $sed -e "s/1/$s/g"`` ;;
none|$undef)

```

```
text=' ';;
esac
: Use extra quotes to preserve an empty '' value.
eval "man${num}=\${ts}"
eval "man${num}ext=\${text}"
done
```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/perl/mandirs.U
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1999 Jarkko Hietaniemi

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?MAKE:d_getspent_r: Inlibc

?MAKE: -pick add \$@ %<

?S:d_getspent_r:

?S: This variable conditionally defines the HAS_GETSPENT_R symbol,

?S: which indicates to the C prospam that the getspent_r()

?S: routine is available.

?S:.

?C:HAS_GETSPENT_R:

?C: This symbol, if defined, indicates that the getspent_r routine

?C: is available to getspent re-entrantly.

?C:.

?H:#\$d_getspent_r HAS_GETSPENT_R /**/

?H:.

?LINT:set d_getspent_r

: see if getspent_r exists

set getspent_r d_getspent_r

eval \$inlibc

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/threads/d_getspent_r.U
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: n.U 1 2006-08-24 12:32:52Z rmanfredi \$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic Licence,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: n.U,v \$

?RCS: Revision 3.0 1993/08/18 12:09:19 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?MAKE:n c: contains

?MAKE: -pick add \$@ %<

?S:n:

?S: This variable contains the -n flag if that is what causes the echo

?S: command to suppress newline. Otherwise it is null. Correct usage is

?S: \$echo \$n "prompt for a question: \$c".

?S:.

?S:c:

?S: This variable contains the \c string if that is what causes the echo

?S: command to suppress newline.

Otherwise it is null. Correct usage is

?S: \$echo \$n "prompt for a question: \$c".

?S:.

: first determine how to suppress newline on echo command

echo " "

echo "Checking echo to see how to suppress newlines..."

(echo "hi there\c" ; echo " ")>.echotmp

if \$contains c .echotmp >/dev/null 2>&1 ; then

echo "...using -n."

n='-n'

c=""

else

cat <<'EOM'

...using \c

EOM

n=""

c='\c'

fi

echo \$n "The star should be here-->\$c"

echo '*'

rm -f .echotmp

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/n.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_castneg.U,v 3.0.1.2 1995/05/12 12:11:21 ram Exp \$

?RCS:

?RCS: Copyright (c) 1991-1993, Raphael Manfredi

?RCS:
?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 3.0.
?RCS:
?RCS: \$Log: d_castneg.U,v \$
?RCS: Revision 3.0.1.2 1995/05/12 12:11:21 ram
?RCS: patch54: made sure cc and cflags are conditional dependencies
?RCS: patch54: added improved test case for Interactive Unix
?RCS:
?RCS: Revision 3.0.1.1 1994/10/29 16:10:50 ram
?RCS: patch36: don't forget to tell user about compilation failures (ADO)
?RCS: patch36: declare signal handler correctly using 'signal_t' (ADO)
?RCS:
?RCS: Revision 3.0 1993/08/18 12:05:47 ram
?RCS: Baseline
for dist 3.0 netwide release.
?RCS:
?X:
?X: Can the compiler cast negative / odd floats to unsigned values.
?X:
?MAKE:d_castneg castflags: cat Compile rm_try Setvar signal_t run i_stdlib
?MAKE: -pick add \$@ %<
?S:d_castneg:
?S: This variable conditionally defines CASTNEG, which indicates
?S: whether the C compiler can cast negative float to unsigned.
?S:.
?S:castflags:
?S: This variable contains a flag that precise difficulties the
?S: compiler has casting odd floating values to unsigned long:
?S: 0 = ok
?S: 1 = couldn't cast < 0
?S: 2 = couldn't cast >= 0x80000000
?S: 4 = couldn't cast in argument expression list
?S:.
?C:CASTNEGFLOAT:
?C: This symbol is defined if the C compiler can cast negative
?C: numbers to unsigned longs, ints and shorts.
?C:.
?C:CASTFLAGS:
?C: This symbol contains flags that say what difficulties the compiler
?C: has casting odd floating values to unsigned long:
?C: 0 = ok
?C: 1 = couldn't cast < 0
?C: 2 = couldn't cast >= 0x80000000
?C: 4 = couldn't

```

cast in argument expression list
?C:.
?H:#$d_castneg CASTNEGFLOAT /**/
?H:#define CASTFLAGS $castflags /**/
?H:.
?F:!try
?LINT:set d_castneg
: check for ability to cast negative floats to unsigned
echo " "
echo 'Checking whether your C compiler can cast negative float to unsigned.' >&4
$cat >try.c <<EOCP
#include <stdio.h>
#$i_stdlib I_STDLIB
#ifdef I_STDLIB
#include <stdlib.h>
#endif
#include <sys/types.h>
#include <signal.h>
$signal_t blech(int s) { exit(7); }
$signal_t blech_in_list(int s) { exit(4); }
unsigned long dummy_long(unsigned long p) { return p; }
unsigned int dummy_int(unsigned int p) { return p; }
unsigned short dummy_short(unsigned short p) { return p; }
int main()
{
double f;
unsigned long along;
unsigned int aint;
unsigned short ashort;
int result = 0;
char str[16];

/* Frustrate gcc-2.7.2's optimizer which failed this test with
   a direct f = -123. assignment. gcc-2.8.0 reportedly
   optimized the whole file away
*/
/* Store the number in a writable
string for gcc to pass to
scanf under HP-UX.
*/
sprintf(str, "-123");
scanf(str, "%lf", &f); /* f = -123.; */

signal(SIGFPE, blech);
along = (unsigned long)f;
aint = (unsigned int)f;
ashort = (unsigned short)f;
if (along != (unsigned long)-123)

```

```

result |= 1;
if (aint != (unsigned int)-123)
    result |= 1;
if (ashort != (unsigned short)-123)
    result |= 1;
sprintf(str, "1073741824.");
sscanf(str, "%lf", &f); /* f = (double)0x40000000; */
f = f + f;
along = 0;
along = (unsigned long)f;
if (along != 0x80000000)
    result |= 2;
f -= 1.;
along = 0;
along = (unsigned long)f;
if (along != 0x7fffffff)
    result |= 1;
f += 2.;
along = 0;
along = (unsigned long)f;
if (along != 0x80000001)
    result |= 2;
if (result)
    exit(result);

```

?X:

?X: The following is a test for Interactive Unix Version 4.1, which

?X: has an 'improved' compiler which can correctly cast negative

?X: floats in expression lists, but apparently not in argument lists.

?X: Contributed by Winfried Koenig

<win@incom.rhein-main.de>

?X:

```

signal(SIGFPE, blech_in_list);
sprintf(str, "123.");
sscanf(str, "%lf", &f); /* f = 123.; */
along = dummy_long((unsigned long)f);
aint = dummy_int((unsigned int)f);
ashort = dummy_short((unsigned short)f);
if (along != (unsigned long)123)
    result |= 4;
if (aint != (unsigned int)123)
    result |= 4;
if (ashort != (unsigned short)123)
    result |= 4;
exit(result);

```

}

EOCP

set try

```

if eval $compile_ok; then
  $run ./try 2>/dev/null
  castflags=$?
else
  echo "(I can't seem to compile the test program--assuming it can't)"
  castflags=7
fi
case "$castflags" in
0) val="$define"
  echo "Yup, it can."
  ;;
*) val="$undef"
  echo "Nope, it can't."
  ;;
esac
set d_castneg
eval $setvar
$rm_try

```

Found in path(s):

```

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/compline/d_castneg.U

```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_localtime_r.U,v 0RCS:

?RCS: Copyright (c) 2002,2003 Jarkko Hietaniemi

?RCS: Copyright (c) 2006,2007 H.Merijn Brand

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?RCS: Generated by the reentr.pl from the Perl 5.8 distribution.

?RCS:

?MAKE:d_localtime_r d_localtime_r_needs_tzset localtime_r_proto: Inlibc \

cat run Protochk Hasproto i_systypes usethreads i_time i_systime \

rm_try Compile extern_C i_stdlib i_unistd i_string i_malloc

?MAKE: -pick add \$@ %<

?S:d_localtime_r:

?S: This variable conditionally defines the HAS_LOCALTIME_R symbol,

?S: which indicates to the C program that the localtime_r()

?S: routine is available.

?S:.

?S:d_localtime_r_needs_tzset:

?S: This variable conditionally defines the LOCALTIME_R_NEEDS_TZSET

?S: symbol, which makes us call tzset before localtime_r()

?S:.

?S:localtime_r_proto:

?S: This

```

variable encodes the prototype of localtime_r.
?S: It is zero if d_localtime_r is undef, and one of the
?S: REENTRANT_PROTO_T_ABC macros of reentr.h if d_localtime_r
?S: is defined.
?S:.
?C:HAS_LOCALTIME_R:
?C: This symbol, if defined, indicates that the localtime_r routine
?C: is available to localtime re-entrantly.
?C:.
?C:LOCALTIME_R_NEEDS_TZSET:
?C: Many libc's localtime_r implementations do not call tzset,
?C: making them differ from localtime(), and making timezone
?C: changes using \${ENV}{TZ} without explicitly calling tzset
?C: impossible. This symbol makes us call tzset before localtime_r
?C:.
?H:%<:#$d_localtime_r_needs_tzset LOCALTIME_R_NEEDS_TZSET /**/
?H:%<:#ifdef LOCALTIME_R_NEEDS_TZSET
?H:%<:#define L_R_TZSET tzset(),
?H:%<:#else
?H:%<:#define L_R_TZSET
?H:%<:#endif
?H:.
?C:L_R_TZSET:
?C: If localtime_r() needs tzset, it is defined in this define
?C:.
?C:LOCALTIME_R_PROTO:
?C: This symbol encodes the prototype of localtime_r.
?C: It is zero if
d_localtime_r is undef, and one of the
?C: REENTRANT_PROTO_T_ABC macros of reentr.h if d_localtime_r
?C: is defined.
?C:.
?H:#$d_localtime_r HAS_LOCALTIME_R /**/
?H:#define LOCALTIME_R_PROTO $localtime_r_proto /**/
?H:.
?T:try hdrs d_localtime_r_proto
?F:!try
: see if localtime_r exists
set localtime_r d_localtime_r
eval $inlibc
case "$d_localtime_r" in
"$define")
hdrs="$i_systypes sys/types.h define stdio.h $i_time time.h $i_systime sys/time.h"
case "$d_localtime_r_proto:$usetheads" in
":define") d_localtime_r_proto=define
set d_localtime_r_proto localtime_r $hdrs
eval $hasproto ;;
*) ;;

```

```

esac
case "$d_localtime_r_proto" in
define)
case "$localtime_r_proto" in
"|0) try='struct tm* localtime_r(const time_t*, struct tm*);'
./protochk "$extern_C $try" $hdrs && localtime_r_proto=S_TS ;;
esac
case "$localtime_r_proto" in
"|0) try='int localtime_r(const time_t*, struct tm*);'
./protochk "$extern_C $try" $hdrs && localtime_r_proto=I_TS ;;
esac
case "$localtime_r_proto"
in
"|0) d_localtime_r=undef
localtime_r_proto=0
echo "Disabling localtime_r, cannot determine prototype." >&4 ;;
*) case "$localtime_r_proto" in
REENTRANT_PROTO*) ;;
*) localtime_r_proto="REENTRANT_PROTO_$localtime_r_proto" ;;
esac
echo "Prototype: $try" ;;
esac
;;
*) case "$susetheads" in
define) echo "localtime_r has no prototype, not using it." >&4 ;;
esac
d_localtime_r=undef
localtime_r_proto=0
;;
esac
;;
*) localtime_r_proto=0
;;
esac

```

```

: see if localtime_r calls tzset
case "$localtime_r_proto" in
REENTRANT_PROTO*)
$cat >try.c <<EOCP
/* Does our libc's localtime_r call tzset ?
* return 0 if so, 1 otherwise.
*/
#$i_systypes I_SYS_TYPES
#$i_unistd I_UNISTD
#$i_time I_TIME
#$i_stdlib I_STDLIB
#$i_string I_STRING
#$i_malloc I_MALLOC

```

```

#ifdef I_SYS_TYPES
# include <sys/types.h>
#endif
#ifdef I_UNISTD
# include <unistd.h>
#endif
#ifdef I_TIME
# include <time.h>
#endif
#ifdef I_STDLIB
#include <stdlib.h>
#endif
#ifdef I_STRING
# include
  <string.h>
#else
# include <strings.h>
#endif
#ifdef I_MALLOC
# include <malloc.h>
#endif
int main()
{
    time_t t = time(0L);
    char w_tz[]="TZ" "=GMT+5",
    e_tz[]="TZ" "=GMT-5",
    *tz_e = (char*)malloc(16),
    *tz_w = (char*)malloc(16);
    struct tm tm_e, tm_w;
    memset(&tm_e,'\0',sizeof(struct tm));
    memset(&tm_w,'\0',sizeof(struct tm));
    strcpy(tz_e,e_tz);
    strcpy(tz_w,w_tz);

    putenv(tz_e);
    localtime_r(&t, &tm_e);

    putenv(tz_w);
    localtime_r(&t, &tm_w);

    if( memcmp(&tm_e, &tm_w, sizeof(struct tm)) == 0 )
return 1;
    return 0;
}
EOCP
set try
if eval $compile; then
    if $run ./try; then

```

```

d_localtime_r_needs_tzset=undef;
    else
d_localtime_r_needs_tzset=define;
    fi;
else
    d_localtime_r_needs_tzset=undef;
fi;
;;
*)
    d_localtime_r_needs_tzset=undef;
    ;;
esac
$rm_try

```

Found in path(s):

```

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/threads/d_localtime_r.U

```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1996,1998 Andy Dougherty

?RCS: Copyright (c) 1996, Sven Verdoolaege

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?MAKE:d_gnulibc gnulibc_version: Myread Oldconfig Setvar rm_try \
cat Compile run

?MAKE: -pick add \$@ %<

?S:d_gnulibc:

?S: Defined if we're dealing with the GNU C Library.

?S:.

?S:gnulibc_version:

?S: This variable contains the version number of the GNU C library.

?S: It is usually something like '2.2.5'. It is a plain " if this

?S: is not the GNU C library, or if the version is unknown.

?S:.

?C:HAS_GNULIBC ~ %<:

?C: This

symbol, if defined, indicates to the C program that

?C: the GNU C library is being used. A better check is to use

?C: the __GLIBC__ and __GLIBC_MINOR__ symbols supplied with glibc.

?C:.

```

?H:?%<:#$d_gnulibc HAS_GNULIBC  /**/
?H:?%<:#if defined(HAS_GNULIBC) && !defined(_GNU_SOURCE)
?H:?%<:#define _GNU_SOURCE
?H:?%<:#endif
?H:
?F:!glibc.ver !try.c !try
?LINT: set d_gnulibc
?LINT: usefile try.c
?LINT: known _GNU_SOURCE
?X: glibc can be executed by calling __libc_main().
?X: Ulrich Drepper doesn't think any other libc does that,
?X: but we check if it says 'GNU C Library' to be sure.
?X:
?X: Alas, as of 3/1998 glibc 2.0.7 reportedly isn't going to
?X: have __libc_main() anymore. :-(. Fortunately, all released
?X: versions of glibc 2.x.x _do_ have CPP variables. For 2.0.6,
?X: they are:
?X: #define __GLIBC__ 2
?X: #define __GLIBC_MINOR__ 0.
?X: (The '6' isn't available :-(.
?X: glibc2.1 will also have
?X: extern const char * __gnu_get_libc_release(void);
?X: extern const char *
    __gnu_get_libc_version(void);
?X: functions. --thanks to Andreas Jaeger. --AD 6/1998.
?X: Although the exact format isn't documented, __gnu_get_libc_version()
?X: returns a simple string '2.1.3' in glibc 2.1.3.
?X:
: determine whether we are using a GNU C library
echo " "
echo "Checking for GNU C Library..." >&4
cat >try.c <<'EOCP'
/* Find out version of GNU C library. __GLIBC__ and __GLIBC_MINOR__
   alone are insufficient to distinguish different versions, such as
   2.0.6 and 2.0.7. The function gnu_get_libc_version() appeared in
   libc version 2.1.0. A. Dougherty, June 3, 2002.
*/
#include <stdio.h>
int main(void)
{
#ifdef __GLIBC__
# ifdef __GLIBC_MINOR__
#   if __GLIBC__ >= 2 && __GLIBC_MINOR__ >= 1
#     include <gnu/libc-version.h>
printf("%s\n", gnu_get_libc_version());
#   else
printf("%d.%d\n", __GLIBC__, __GLIBC_MINOR__);
#   endif
#endif
}

```

```

# else
printf("%d\n", __GLIBC__);
# endif
return 0;
#else
return 1;
#endif
}
EOCP
set
try
if eval $compile_ok && $run ./try > glibc.ver; then
val="$define"
gnulibc_version=`$cat glibc.ver`
echo "You are using the GNU C Library version $gnulibc_version"
else
val="$undef"
gnulibc_version=""
echo "You are not using the GNU C Library"
fi
$rm_try glibc.ver
set d_gnulibc
eval $setvar

```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/d_gnulibc.U
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: d_vfork.U,v \$

?RCS: Revision 3.0.1.6 1994/08/29 16:18:21 ram

?RCS: patch32: set default to 'y' the first time

?RCS:

?RCS: Revision 3.0.1.5 1994/06/20 06:59:14 ram

?RCS: patch30: usevfork was not always properly set

?RCS:

?RCS: Revision 3.0.1.4 1994/05/13 15:20:56 ram

?RCS: patch27: modified to avoid spurious Whoa warnings (ADO)

```

?RCS:
?RCS: Revision 3.0.1.3 1994/05/06 14:59:09 ram
?RCS: patch23: now explicitly ask whether vfork() should be used (ADO)
?RCS:
?RCS: Revision 3.0.1.2 1993/10/16
 13:49:39 ram
?RCS: patch12: added magic for vfork()
?RCS:
?RCS: Revision 3.0.1.1 1993/09/13 16:06:57 ram
?RCS: patch10: removed automatic remapping of vfork on fork (WAD)
?RCS: patch10: added compatibility code for older config.sh (WAD)
?RCS:
?RCS: Revision 3.0 1993/08/18 12:07:55 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:d_vfork usevfork: Inlibc Myread Oldconfig Setvar
?MAKE: -pick add $@ %<
?S:d_vfork:
?S: This variable conditionally defines the HAS_VFORK symbol, which
?S: indicates the vfork() routine is available.
?S:.
?S:usevfork:
?S: This variable is set to true when the user accepts to use vfork.
?S: It is set to false when no vfork is available or when the user
?S: explicitly requests not to use vfork.
?S:.
?C:HAS_VFORK (VFORK):
?C: This symbol, if defined, indicates that vfork() exists.
?C:.
?H:#$d_vfork HAS_VFORK /**/
?H:.
?M:vfork: HAS_VFORK
?M:#ifndef HAS_VFORK
?M:#define vfork fork
?M:#endif
?M:.
?LINT:set d_vfork
: see if there is a vfork
val="
set
vfork val
eval $inlibc

: Ok, but do we want to use it. vfork is reportedly unreliable in
: perl on Solaris 2.x, and probably elsewhere.
case "$val" in
$define)
echo " "

```

```

case "$usevfork" in
false) dflt='n';
*) dflt='y';;
esac
rp="Some systems have problems with vfork(). Do you want to use it?"
. ./myread
case "$ans" in
y|Y) ;;
*)
echo "Ok, we won't use vfork()."
val="$undef"
;;
esac
;;
esac
?X:
?X: Only set it when final value is known to avoid spurious Whoas
?X: Then set usevfork accordingly to the current value, for next run
?X:
set d_vfork
eval $setvar
case "$d_vfork" in
$define) usevfork='true';;
*) usevfork='false';;
esac

```

Found in path(s):

```

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/d_vfork.U

```

No license file was found, but licenses were detected in source scan.

```

?RCS: $Id: d_lchown.U,v 3.0.1.1 1994/08/29 16:07:14 ram Exp $
?RCS:
?RCS: Copyright (c) 1991-1993, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 3.0.
?RCS:
?RCS: Original Author: Andy Dougherty <doughera@lafcol.lafayette.edu>
?RCS:
?RCS: $Log: d_lchown.U,v $
?RCS: Revision 3.0.1.1 1994/08/29 16:07:14 ram
?RCS: patch32: created by ADO
?RCS:
?MAKE:d_lchown: Compile Setvar cat echo

```

```

?MAKE: -pick add $@ %<
?S:d_lchown:
?S: This variable conditionally defines the HAS_LCHOWN symbol, which
?S: indicates to the C program that the lchown() routine is available
?S: to operate on a symbolic link (instead of following the link).
?S:.
?C:HAS_LCHOWN
:
?C: This symbol, if defined, indicates that the lchown routine is
?C: available to operate on a symbolic link (instead of following the
?C: link).
?C:.
?H:#$d_lchown HAS_LCHOWN /**/
?H:.
?LINT:set d_lchown
: see if lchown exists
echo " "
?X: Some functions (such as lchown()) are present in libc, but are
?X: unimplemented. That is, they always fail and set errno=ENOSYS.
?X:
?X: Thomas Bushnell provided the following sample code and the explanation
?X: that follows.
?X:
?X: The choice of <assert.h> is essentially arbitrary. The GNU libc
?X: macros are found in <gnu/stubs.h>. You can include that file instead
?X: of <assert.h> (which itself includes <gnu/stubs.h>) if you test for
?X: its existence first. <assert.h> is assumed to exist on every system,
?X: which is why it's used here. Any GNU libc header file will include
?X: the stubs macros. If either __stub_NAME or __stub__NAME is defined,
?X: then the function doesn't actually exist. Tests using <assert.h>
work
?X: on every system around.
?X:
?X: The declaration of FOO is there to override builtin prototypes for
?X: ANSI C functions.
?X:
?X: I really ought to enhance the inlibc test to check for this, but
?X: I don't have time now. --A.D. 5/1998
?X:
$cat > try.c <<'EOCP'
/* System header to define __stub macros and hopefully few prototypes,
   which can conflict with char lchown(); below. */
#include <assert.h>
/* Override any gcc2 internal prototype to avoid an error. */
/* We use char because int might match the return type of a gcc2
   builtin and then its argument prototype would still apply. */
char lchown();
int main() {

```

```

/* The GNU C library defines this for functions which it implements
   to always fail with ENOSYS. Some functions are actually named
   something starting with __ and the normal name is an alias. */
#if defined (__stub_lchown) || defined (__stub___lchown)
choke me
#else
lchown();
#endif
; return 0; }
EOCP
set try
if eval $compile; then
    $echo
    "lchown() found." >&4
    val="$define"
else
    $echo "lchown() NOT found." >&4
    val="$undef"
fi
set d_lchown
eval $setvar

```

Found in path(s):

```

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/compline/d_lchown.U

```

No license file was found, but licenses were detected in source scan.

```

?RCS: $Id: sizetype.U,v 3.0.1.1 1994/08/29 16:32:10 ram Exp $
?RCS:
?RCS: Copyright (c) 1991-1993, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 3.0.
?RCS:
?RCS: Original Author: Andy Dougherty <doughera@lafcol.lafayette.edu>
?RCS:
?RCS: $Log: sizetype.U,v $
?RCS: Revision 3.0.1.1 1994/08/29 16:32:10 ram
?RCS: patch32: created by ADO
?RCS:
?MAKE:sizetype: Myread Typedef
?MAKE: -pick add $@ %<
?S:sizetype:
?S: This variable defines sizetype to be something like size_t,
?S: unsigned long, or whatever type is used to declare length

```

?S: parameters for string functions.

?S:.

?C:Size_t:

?C: This symbol holds the type used to declare length parameters

?C: for string functions. It is usually size_t, but may be

?C: unsigned long, int, etc. It may be necessary to include

?C: <sys/types.h> to get any typedef'ed information.

?C:.

?H:#define Size_t \$sizetype /* length parameter for string functions */

?H:.

?LINT: set sizetype

: see what type is used for size_t

rp="What is the type used for the length parameter for string functions?"

set size_t sizetype 'unsigned int' stdio.h sys/types.h

eval \$typedef_ask

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/typedefs/sizetype.U

No license file was found, but licenses were detected in source scan.

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?MAKE:d_llroundl: Inlibc

?MAKE: -pick add \$@ %<

?S:d_llroundl:

?S: This variable conditionally defines the HAS_LLROUNDL symbol, which

?S: indicates to the C program that the llroundl() routine is available

?S: to return the long long value nearest to x away from zero.

?S:.

?C:HAS_LLROUNDL:

?C: This symbol, if defined, indicates that the llroundl routine is

?C: available to return the nearest long long value away from zero of

?C: the long double argument value.

?C:.

?H:#\$d_llroundl HAS_LLROUNDL /**/

?H:.

?LINT:set d_llroundl

: see if llroundl exists

set llroundl d_llroundl

eval \$inlibc

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_llroundl.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 2000 Jarkko Hietaniemi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 3.0.

?RCS:

?MAKE:d_getprpwnam: Inlibc

?MAKE: -pick add \$@ %<

?S:d_getprpwnam:

?S: This variable conditionally defines HAS_GETPRPWNAM if getprpwnam() is

?S: available to retrieve protected (shadow) password entries by name.

?S:.

?C:HAS_GETPRPWNAM:

?C: This symbol, if defined, indicates that the getprpwnam system call is

?C: available to retrieve protected (shadow) password entries by name.

?C:.

?H:#\$d_getprpwnam HAS_GETPRPWNAM /**/

?H:.

?LINT:set d_getprpwnam

: see if getprpwnam exists

set getprpwnam d_getprpwnam

eval \$inlibc

Found

in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_getprpwnam.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 2005 H.Merijn Brand

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?MAKE:d_clearenv: Inlibc

?MAKE: -pick add \$@ %<

?S:d_clearenv:

?S: This variable conditionally defines the HAS_CLEARENV symbol, which

?S: indicates to the C program that the clearenv () routine is available.

?S:.

?C:HAS_CLEARENV:

?C: This symbol, if defined, indicates that the clearenv () routine is

?C: available for use.

?C:.

?H:#\$d_clearenv HAS_CLEARENV /**/

?H:.

?LINT:set d_clearenv

: see if clearenv exists

set clearenv d_clearenv

eval \$inlibc

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_clearenv.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: i_math.U 1 2006-08-24 12:32:52Z rmanfredi \$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic Licence,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic Licence; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: Original Author: Andy Dougherty <doughera@lafcol.lafayette.edu>

?RCS:

?RCS: \$Log: i_math.U,v \$

?RCS: Revision 3.0.1.1 1994/08/29 16:21:59 ram

?RCS: patch32: created by ADO

?RCS:

?MAKE:i_math: Inhdr

?MAKE: -pick add \$@ %<

?X: Are there really systems that *DON'T* have math.h?

?S:i_math:

?S: This variable conditionally defines the I_MATH symbol, and indicates

?S: whether a C program may include <math.h>.

?S:.

?C:I_MATH:

?C: This symbol, if defined, indicates

to the C program that it should

?C: include <math.h>.

?C:.

?H:#\$i_math I_MATH /**/

?H:.

?LINT:set i_math

: see if this is a math.h system

```
set math.h i_math
eval $inhdr
```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/i_math.U
```

No license file was found, but licenses were detected in source scan.

```
# $Id: errnolist.a,v 3.0 1993/08/18 12:04:35 ram Exp ram $
#
# Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
#
# You may redistribute only under the terms of the Artistic Licence,
# as specified in the README file that comes with the distribution.
# You may reuse parts of this distribution only within the terms of
# that same Artistic Licence; a copy of which may be found at the root
# of the source tree for dist 4.0.
#
# Original Author: Harlan Stenn <harlan@mumps.pfcs.com>
#
# $Log: errnolist.a,v $
# Revision 3.0 1993/08/18 12:04:35 ram
# Baseline for dist 3.0 netwide release.
#
#
# This is a simple-minded awk script to generate an initialization for
# sys_errnolist on systems that don't have it.
# This file now depends only on sys/errno.h error numbers under maxerr being
# in order. It will complain and die if not. NOTE: It will still produce
# a compilable output file, even with errors, so you
# must check the output.
```

```
BEGIN {
    format = "\t\"%s\", \n"
    printf("/*\n** This is a generated file. Do NOT edit it unless you really have to...\n*/\n\n")
    printf("char *sys_errnolist[] = {\n")
    maxerr = 89
}
```

```
$1=="#define" {
    if(count > maxerr || substr($2,1,1) != "E")
        next # we're not interested
    if($3 < count) { # this is bad
        printf("Fatal error: %s out of order at %s\n", \
            FILENAME, $2)>"/dev/tty"
        exit 1
    }
}
```

```

# fill in the blanks
while($3 > count) {
  dummy=sprintf("EDUMMY%d",count)
  printf(format,dummy)
  count++
}
printf(format,$2)
count++
}

END {
  printf("\t0\n");\n"
}

```

Found in path(s):

```

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/lib/errnolist.a

```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_getsrvby.U,v \$

?RCS:

?RCS: Copyright (c) 1998 Andy Dougherty

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?MAKE:d_getsbyname d_getsbyport: Inlibc

?MAKE: -pick add \$@ %<

?S:d_getsbyname:

?S: This variable conditionally defines the HAS_GETSERVBYNAME

?S: symbol, which indicates to the C program that the

?S: getservbyname() routine is available to look up services

?S: by their name.

?S:.

?S:d_getsbyport:

?S: This variable conditionally defines the HAS_GETSERVBYPOR

?S: symbol, which indicates to the C program that the

?S: getservbyport() routine is available to look up services

?S: by their port.

?S:.

?C:HAS_GETSERVBYNAME:

?C: This symbol, if defined, indicates that the getservbyname()

?C: routine is available to look up services by their name.

?C:.

?C:HAS_GETSERVBYPOR:

?C: This symbol, if defined,

indicates that the getservbyport()

?C: routine is available to look up services by their port.

```
?C:
?H:#$d_getsbyname HAS_GETSERVBYNAME /**/
?H:#$d_getsbyport HAS_GETSERVBYPORT /**/
?H:
?LINT:set d_getsbyname d_getsbyport
: Optional checks for getsbyname and getsbyport
```

```
@if d_getsbyname || HAS_GETSERVBYNAME
: see if getservbyname exists
set getservbyname d_getsbyname
eval $inlibc
@end
```

```
@if d_getsbyport || HAS_GETSERVBYPORT
: see if getservbyport exists
set getservbyport d_getsbyport
eval $inlibc
@end
```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/modified/d_getsrvby.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id$
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: $Log: d_strerror.U,v $
?RCS: Revision 3.0.1.3 1994/05/13 15:20:27 ram
?RCS: patch27: now uses new macro support for cleaner Strerror def
?RCS:
?RCS: Revision 3.0.1.2 1994/05/06 14:58:26 ram
?RCS: patch23: renamed strerror into Strerror to protect name space (ADO)
?RCS:
?RCS: Revision 3.0.1.1 1994/01/24 14:08:56 ram
?RCS: patch16: protected code looking for sys_errnolist[] with @if
?RCS: patch16: added default value for d_sysernlst
?RCS:
?RCS: Revision 3.0 1993/08/18 12:07:35 ram
?RCS: Baseline
```

for dist 3.0 netwide release.

?RCS:

?MAKE:d_strerror d_syserrlst d_sysernlst d_strerror: contains Csym Findhdr

?MAKE: -pick add \$@ %<

?S:d_strerror:

?S: This variable conditionally defines HAS_STRERROR if strerror() is

?S: available to translate error numbers to strings.

?S:.

?S:d_syserrlst:

?S: This variable conditionally defines HAS_SYS_ERRLIST if sys_errlist[] is

?S: available to translate error numbers to strings.

?S:.

?S:d_sysernlst:

?S: This variable conditionally defines HAS_SYS_ERRNOLIST if sys_errnolist[]

?S: is available to translate error numbers to the symbolic name.

?S:.

?S:d_strerror:

?S: This variable holds what Strerrr is defined as to translate an error

?S: code condition into an error message string. It could be 'strerror'

?S: or a more complex macro emulating strrror with sys_errlist[], or the

?S: "unknown" string when both strerror and sys_errlist are missing.

?S:.

?C:HAS_STRERROR (STRERROR):

?C: This symbol, if defined, indicates that the strerror routine is

?C: available

to translate error numbers to strings. See the writeup

?C: of Strerror() in this file before you try to define your own.

?C:.

?C:HAS_SYS_ERRLIST (SYSERRLIST):

?C: This symbol, if defined, indicates that the sys_errlist array is

?C: available to translate error numbers to strings. The extern int

?C: sys_nerr gives the size of that table.

?C:.

?C:HAS_SYS_ERRNOLIST (SYSERRNOLIST):

?C: This symbol, if defined, indicates that the sys_errnolist array is

?C: available to translate an errno code into its symbolic name (e.g.

?C: ENOENT). The extern int sys_nerrno gives the size of that table.

?C:.

?C:Strerror:

?C: This preprocessor symbol is defined as a macro if strerror() is

?C: not available to translate error numbers to strings but sys_errlist[]

?C: array is there.

?C:.

?H:#\$d_strerror HAS_STRERROR /**/

?H:#\$d_syserrlst HAS_SYS_ERRLIST /**/

?H:#\$d_sysernlst HAS_SYS_ERRNOLIST /**/

?H:#define Strerror(e) \$d_strerror

?H:.

```

?D:d_syserrlst="
?T:xxx val
: see if strerror and/or sys_errlist[]
exist
echo " "
if set strerror val -f d_strerror; eval $csym; $val; then
echo 'strerror() found.' >&4
d_strerror="$define"
d_strerrorrm='strerror(e)'
if set sys_errlist val -a d_syserrlst; eval $csym; $val; then
echo "(You also have sys_errlist[], so we could roll our own strerror.)"
d_syserrlst="$define"
else
echo "(Since you don't have sys_errlist[], strerror() is welcome.)"
d_syserrlst="$undef"
fi
elif xxx=`./findhdr string.h`; test "$xxx" || xxx=`./findhdr strings.h`; \
$contains '#[ ]*define.*strerror' "$xxx" >/dev/null 2>&1; then
echo 'strerror() found in string header.' >&4
d_strerror="$define"
d_strerrorrm='strerror(e)'
if set sys_errlist val -a d_syserrlst; eval $csym; $val; then
echo "(Most probably, strerror() uses sys_errlist[] for descriptions.)"
d_syserrlst="$define"
else
echo "(You don't appear to have any sys_errlist[], how can this be?)"
d_syserrlst="$undef"
fi
elif set sys_errlist val -a d_syserrlst; eval $csym; $val; then
echo "strerror()
not found, but you have sys_errlist[] so we'll use that." >&4
d_strerror="$undef"
d_syserrlst="$define"
d_strerrorrm='((e)<0||(e)>=sys_nerr?"unknown":sys_errlist[e])'
else
echo 'strerror() and sys_errlist[] NOT found.' >&4
d_strerror="$undef"
d_syserrlst="$undef"
d_strerrorrm=""unknown""
fi
@if d_syserrlst || HAS_SYS_ERRNOLIST
if set sys_errnolist val -a d_syserrlst; eval $csym; $val; then
echo "(Symbolic error codes can be fetched via the sys_errnolist[] array.)"
d_syserrlst="$define"
else
echo "(However, I can't extract the symbolic error code out of errno.)"
d_syserrlst="$undef"
fi

```

@end

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/d_strerror.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 2000 Jarkko Hietaniemi

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?MAKE:d_strerror: Inlibc

?MAKE: -pick add \$@ %<

?S:d_strerror:

?S: This variable conditionally defines the HAS_STRTOQ symbol, which

?S: indicates to the C program that the strtouq() routine is available.

?S:.

?C:HAS_STRTOQ:

?C: This symbol, if defined, indicates that the strtouq routine is

?C: available to convert strings to long longs (quads).

?C:.

?H:#\$d_strerror HAS_STRTOQ /**/

?H:.

?LINT:set d_strerror

: see if strtouq exists

set strtouq d_strerror

eval \$inlibc

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_strerror.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: patchlevel.U,v 3.0.1.1 1997/02/28 16:18:41 ram Exp \$

?RCS:

?RCS: Copyright (c) 1991-1993, Raphael Manfredi

?RCS:

?RCS: This file is included with or a derivative work of a file included

?RCS: with the metaconfig program of Raphael Manfredi's "dist" distribution.

?RCS: In accordance with clause 7 of dist's modified Artistic License:

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?RCS: \$Log: patchlevel.U,v \$

?RCS: Revision 3.0.1.1 1997/02/28 16:18:41 ram

?RCS: patch61: added support for src.U

?RCS:

?RCS: Revision 3.0 1993/08/18 12:09:31 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?MAKE:patchlevel revision version subversion \
 perl_patchlevel version_patchlevel_string \
 api_revision api_version api_subversion api_versionstring: \
 package test rsrc echo awk osname

?MAKE: -pick

add \$@ %<

?S:revision:

?S: The value of revision comes from the patchlevel.h file.

?S: In a version number such as 5.6.1, this is the "5".

?S: In patchlevel.h, this is referred to as "PERL_REVISION".

?S:.

?S:patchlevel:

?S: The patchlevel level of this package.

?S: The value of patchlevel comes from the patchlevel.h file.

?S: In a version number such as 5.6.1, this is the "6".

?S: In patchlevel.h, this is referred to as "PERL_VERSION".

?S:.

?S:subversion:

?S: The subversion level of this package.

?S: The value of subversion comes from the patchlevel.h file.

?S: In a version number such as 5.6.1, this is the "1".

?S: In patchlevel.h, this is referred to as "PERL_SUBVERSION".

?S: This is unique to perl.

?S:.

?S:version:

?S: The full version number of this package, such as 5.6.1 (or 5_6_1).

?S: This combines revision, patchlevel, and subversion to get the

?S: full version number, including any possible subversions.

?S: This is suitable for use as a directory name, and hence is

?S: filesystem

dependent.

?S:.

?S:api_revision:

?S: The three variables, api_revision, api_version, and

?S: api_subversion, specify the version of the oldest perl binary

?S: compatible with the present perl. In a full version string

?S: such as '5.6.1', api_revision is the '5'.

?S: Prior to 5.5.640, the format was a floating point number,

?S: like 5.00563.

?S:

?S: perl.c:incpush() and lib/lib.pm will automatically search in

?S: \$sitelib/.. for older directories back to the limit specified

?S: by these `api_` variables. This is only useful if you have a
?S: perl library directory tree structured like the default one.
?S: See `INSTALL` for how this works. The versioned `site_perl`
?S: directory was introduced in 5.005, so that is the lowest
?S: possible value. The version list appropriate for the current
?S: system is determined in `inc_version_list.U`.
?S:
?S: XXX To do: Since compatibility can depend on compile time
?S: options (such as `bincompat`, `longlong`, etc.) it should
?S: (perhaps) be set by
?S: `Configure`, but currently it isn't.
?S: Currently, we read a hard-wired value from `patchlevel.h`.
?S: Perhaps what we ought to do is take the hard-wired value from
?S: `patchlevel.h` but then modify it if the current `Configure`
?S: options warrant. `patchlevel.h` then would use an `#ifdef` guard.
?S:.
?S:`api_version`:
?S: The three variables, `api_revision`, `api_version`, and
?S: `api_subversion`, specify the version of the oldest perl binary
?S: compatible with the present perl. In a full version string
?S: such as '5.6.1', `api_version` is the '6'. See `api_revision` for
?S: full details. As a special case, 5.5.0 is rendered in the
?S: old-style as 5.005. (In the 5.005_0x maintenance series,
?S: this was the only versioned directory in `$sitelib`.)
?S:.
?S:`api_subversion`:
?S: The three variables, `api_revision`, `api_version`, and
?S: `api_subversion`, specify the version of the oldest perl binary
?S: compatible with the present perl. In a full version string
?S: such as '5.6.1', `api_subversion` is the
?S: '1'. See `api_revision` for
?S: full details.
?S:.
?S:`api_versionstring`:
?S: This variable combines `api_revision`, `api_version`, and
?S: `api_subversion` in a format such as 5.6.1 (or `5_6_1`) suitable
?S: for use as a directory name. This is filesystem dependent.
?S:.
?S:`perl_patchlevel`:
?S: This is the Perl patch level, a numeric change identifier,
?S: as defined by whichever source code maintenance system
?S: is used to maintain the patches; currently Perforce.
?S: It does not correlate with the Perl version numbers or
?S: the maintenance versus development dichotomy except
?S: by also being increasing.
?S:.
?S:`version_patchlevel_string`:
?S: This is a string combining version, subversion and

```

?S: perl_patchlevel (if perl_patchlevel is non-zero).
?S: It is typically something like
?S: 'version 7 subversion 1' or
?S: 'version 7 subversion 1 patchlevel 11224'
?S: It is computed here to avoid duplication of code in myconfig.SH
?S: and lib/Config.pm.
?S:.
?LINT:extern LC_ALL
?LINT:extern LANGUAGE
:
  get the patchlevel
  echo " "
  echo "Getting the current patchlevel..." >&4
  if $test -r $src/patchlevel.h;then
    revision=`awk '/define[ ]+PERL_REVISION/ {print $3}' $src/patchlevel.h`
    patchlevel=`awk '/define[ ]+PERL_VERSION/ {print $3}' $src/patchlevel.h`
    subversion=`awk '/define[ ]+PERL_SUBVERSION/ {print $3}' $src/patchlevel.h`
    api_revision=`awk '/define[ ]+PERL_API_REVISION/ {print $3}' $src/patchlevel.h`
    api_version=`awk '/define[ ]+PERL_API_VERSION/ {print $3}' $src/patchlevel.h`
    api_subversion=`awk '/define[ ]+PERL_API_SUBVERSION/ {print $3}' $src/patchlevel.h`
    perl_patchlevel=`egrep '(MAINT|SMOKE)[0-9][0-9]*' $src/patchlevel.h|tail -1|sed 's/[^0-9]//g`
  else
    revision=0
    patchlevel=0
    subversion=0
    api_revision=0
    api_version=0
    api_subversion=0
    perl_patchlevel=0
    $echo "(You do not have patchlevel.h. Eek.)"
  fi
: Define a handy string here to avoid duplication in myconfig.SH and configpm.
version_patchlevel_string="version $patchlevel subversion $subversion"
case
  "$perl_patchlevel" in
0) ;;
*) perl_patchlevel=`echo $perl_patchlevel | sed 's/.*/^`
   version_patchlevel_string="$version_patchlevel_string patch $perl_patchlevel"
   ;;
esac

$echo "(You have $package $version_patchlevel_string.)"

case "$osname" in
dos|vms)
: XXX Should be a Configure test for double-dots in filenames.
version=`echo $revision $patchlevel $subversion | \
  $awk '{ printf "%d_%d_%d", $1, $2, $3 }`

```

```

api_versionstring=`echo $api_revision $api_version $api_subversion | \
  $awk '{ printf "%d_%d_%d", $1, $2, $3 }`
;;
*)
version=`echo $revision $patchlevel $subversion | \
  $awk '{ printf "%d.%d.%d", $1, $2, $3 }`
api_versionstring=`echo $api_revision $api_version $api_subversion | \
  $awk '{ printf "%d.%d.%d", $1, $2, $3 }`
;;
esac
: Special case the 5.005_xx maintenance series, which used 5.005
: without any subversion label as a subdirectory in $sitelib
if test "${api_revision}${api_version}${api_subversion}" = "550"; then
  api_versionstring='5.005'
fi

```

Found

in path(s):

```

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/perl/patchlevel.U

```

No license file was found, but licenses were detected in source scan.

?RCS:

?RCS: Copyright (c) 1999, Jarkko Hietaniemi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 3.0.

?RCS:

?MAKE:d_memchr: Inlibc

?MAKE: -pick add \$@ %<

?S:d_memchr:

?S: This variable conditionally defines the HAS_MEMCHR symbol, which

?S: indicates to the C program that the memchr() routine is available

?S: to locate characters within a C string.

?S:.

?C:HAS_MEMCHR:

?C: This symbol, if defined, indicates that the memchr routine is available

?C: to locate characters within a C string.

?C:.

?H:#\$d_memchr HAS_MEMCHR /**/

?H:.

?LINT:set d_memchr

: see if memchr exists

set memchr d_memchr

eval \$inlibc

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/modified/d_memchr.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: Extractall.U,v \$

?RCS: Revision 3.0.1.1 1997/02/28 15:00:43 ram

?RCS: patch61: created

?RCS:

?X:

?X: If extraction has been requested, load the configuration file, perform

?X: the extraction and exit.

?X:

?X: This unit was originally a part of Options.U. It had to be removed from

?X: it to prevent a dependency cycle: Extract -> src -> Options -> Extract

?X: The Begin.U unit now requires us before beginning to do anything

?X: interesting, to ensure proper semantics. -- RAM, 15/03/96

?X:

?MAKE:Extractall:

Extract Options

?MAKE: -pick wipe \$@ %<

: extract files and exit if asked to do so

case "\$extractsh" in

true)

?X: Undo the forced silent=true when -S was supplied, by probing realsilent

?X: which was set iff -s was also given. See Options.U for details.

case "\$realsilent" in

true) ;;

*) exec 1>&4;;

esac

case "\$config_sh" in

") config_sh='config.sh';;

esac

echo " "

echo "Fetching answers from \$config_sh..."

cd ..

. \$config_sh

```
test "$override" && . ./optdef.sh
echo " "
?X: extract has to be run from the top directory, not within UU.
. UU/extract
rm -rf UU
echo "Extraction done."
exit 0
;;
esac
```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/Extractall.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: d_wait4.U 1 2006-08-24 12:32:52Z rmanfredi $
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: $Log: d_wait4.U,v $
?RCS: Revision 3.0 1993/08/18 12:08:01 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:d_wait4: Inlibc
?MAKE: -pick add $@ %<
?S:d_wait4:
?S: This variable conditionally defines the HAS_WAIT4 symbol, which
?S: indicates the wait4() routine is available.
?S:.
?C:HAS_WAIT4 (WAIT4):
?C: This symbol, if defined, indicates that wait4() exists.
?C:.
?H:#$d_wait4 HAS_WAIT4 /**/
?H:.
?LINT:set d_wait4
: see if there is a wait4
set
wait4 d_wait4
eval $inlibc
```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
```

debian-perl-5.26.1/dist/U/d_wait4.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1998 Jarkko Hietaniemi

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?MAKE:d_recvmsg: Inlibc

?MAKE: -pick add \$@ %<

?S:d_recvmsg:

?S: This variable conditionally defines the HAS_RECVMSG symbol, which

?S: indicates to the C program that the recvmsg() routine is available.

?S:.

?C:HAS_RECVMSG:

?C: This symbol, if defined, indicates that the recvmsg routine is

?C: available to send structured socket messages.

?C:.

?H:#\$d_recvmsg HAS_RECVMSG /**/

?H:.

?LINT:set d_recvmsg

: see if recvmsg exists

set recvmsg d_recvmsg

eval \$inlibc

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-

debian-perl-5.26.1/U/perl/d_recvmsg.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: i_sysioctl.U 1 2006-08-24 12:32:52Z rmanfredi \$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic Licence,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic Licence; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: i_sysioctl.U,v \$

?RCS: Revision 3.0.1.2 1994/05/06 15:04:57 ram

?RCS: patch23: added knowledge for <sys/filio.h> (WED)

?RCS: patch23: optimized amount of findhdr calls

?RCS:

?RCS: Revision 3.0.1.1 1993/11/10 17:36:09 ram

?RCS: patch14: now use a compiler check for TIOCNOTTY because of HP-UX 9.x

?RCS:

?RCS: Revision 3.0 1993/08/18 12:08:32 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?MAKE:i_sysioctl i_bsdioclt i_sysfilio i_syssockio

d_voidtty: test contains \

cat i_termio i_termios i_sgtty Setvar Findhdr +cc rm Inhdr

?MAKE: -pick add \$@ %<

?S:i_sysioctl:

?S: This variable conditionally defines the I_SYS_IOCTL symbol, which

?S: indicates to the C program that <sys/ioctl.h> exists and should

?S: be included.

?S:.

?S:i_sysfilio:

?S: This variable conditionally defines the I_SYS_FILIO symbol, which

?S: indicates to the C program that <sys/filio.h> exists and should

?S: be included in preference to <sys/ioctl.h>.

?S:.

?S:i_bsdioclt:

?S: This variable conditionally defines the I_SYS_BSDIOCTL symbol, which

?S: indicates to the C program that <sys/bsdioclt.h> exists and should

?S: be included.

?S:.

?S:i_syssockio:

?S: This variable conditionally defines I_SYS SOCKIO to indicate to the

?S: C program that socket ioctl codes may be found in <sys/sockio.h>

?S: instead of <sys/ioctl.h>.

?S:.

?S:d_voidtty:

?S: This variable conditionally defines USE_IOCTLTY to indicate that the

?S: ioctl() call with TIOCNOTTY should be used

to void tty association.

?S: Otherwise (on USG probably), it is enough to close the standard file

?S: descriptors and do a setpgrp().

?S:.

?C:I_SYS_IOCTL (I_SYS_IOCTL):

?C: This symbol, if defined, indicates that <sys/ioctl.h> exists and should

?C: be included. Otherwise, include <sgtty.h> or <termio.h>.

?C:.

?C:I_SYS_FILIO:

?C: This symbol, if defined, indicates that <sys/filio.h> exists and

?C: should be included instead of <sys/ioctl.h>.

?C:.

?C:I_SYS_BSDIOCTL (I_BSDIOCTL):

?C: This symbol, if defined, indicates that <sys/bsdioclt.h> exists and should

?C: be included. Otherwise, try <sys/ioctl.h>. This is primarily intended for

?C: definitions of sockets options, like SIOCATMARK.

?C:.

?C:I_SYS_SOCKIO (I_SYSSOCKIO):

?C: This symbol, if defined, indicates the <sys/sockio.h> should be included

?C: to get socket ioctl options, like SIOCATMARK.

?C:.

?C:USE_TIOCNOTTY (VOIDTTY):

?C: This symbol, if defined indicate to the C program that the ioctl()

?C: call with TIOCNOTTY should be used

to void tty association.

?C: Otherwise (on USG probably), it is enough to close the standard file

?C: descriptors and do a setpgrp().

?C:.

?H:#\$i_sysioctl I_SYS_IOCTL /**/

?H:#\$i_sysfilio I_SYS_FILIO /**/

?H:#\$i_bsdiocntl I_SYS_BSDIOCTL /**/

?H:#\$i_syssockio I_SYS_SOCKIO /**/

?H:#\$d_voidtty USE_TIOCNOTTY /**/

?H:.

?T:xxx

: see if ioctl defs are in sgTTY, termio, sys/filio or sys/ioctl

?LINT:set i_sysfilio

set sys/filio.h i_sysfilio

eval \$inhdr

echo " "

if \$test `./findhdr sys/ioctl.h`; then

val="\$define"

echo '<sys/ioctl.h> found.' >&4

else

val="\$undef"

if \$test \$i_sysfilio = "\$define"; then

echo '<sys/ioctl.h> NOT found.' >&4

else

\$test \$i_sgTTY = "\$define" && xxx="sgTTY.h"

\$test \$i_termio = "\$define" && xxx="termio.h"

\$test \$i_termios = "\$define" && xxx="termios.h"

echo "No <sys/ioctl.h> found, assuming ioctl args are defined in <\$xxx>." >&4

fi

fi

?LINT:set i_sysioctl

set i_sysioctl

eval \$setvar

@if I_BSDIOCTL || i_bsdiocntl

?X:

?X: The only machine I know where this

inclusion was necessary is a

?X: BULL DPX 5000 (a French machine).

?X:

```

: see if socket ioctl defs are in sys/bsdioc1 or sys/ioct1
echo " "
xxx=`./findhdr sys/bsdioc1.h`
if $test "$xxx"; then
if $contains SIOCATMARK $xxx >/dev/null 2>&1; then
val="$define"
echo "You have socket ioctls defined in <sys/bsdioc1.h>." >&4
else
val="$undef"
echo "No socket ioctls found in <sys/bsdioc1.h>." >&4
fi
else
val="$undef"
echo "<sys/bsdioc1.h> not found, but that's ok." >&4
fi
?LINT:set i_bsdioc1
set i_bsdioc1
eval $setvar

@end
@if I_SYSSOCKIO || i_syssockio
: see if socket ioctl defs are in sys/sockio.h
echo " "
xxx=`./findhdr sys/sockio.h`
if $test "$xxx"; then
if $contains SIOCATMARK $xxx >/dev/null 2>&1; then
val="$define"
echo "You have socket ioctls defined in <sys/sockio.h>." >&4
else
val="$undef"
echo "No socket ioctls found in <sys/sockio.h>." >&4
fi
else
val="$undef"
@if I_BSDIOCTL
case "$i_bsdioc1" in
"$define") $cat <<EOM
<sys/sockio.h> not found, using
ioctls from <sys/bsdioc1.h>.
EOM
;;
*) $cat <<EOM
<sys/sockio.h> not found, assuming socket ioctls are in <sys/ioct1.h>.
EOM
;;
esac
@else
$cat <<EOM

```

<sys/sockio.h> not found, assuming socket ioctls are in <sys/ioctl.h>.

EOM

@end

fi

?LINT:set i_syssockio

set i_syssockio

eval \$setvar

@end

@if VOIDTTY || d_voidtty

: check how to void tty association

echo " "

case "\$i_sysioctl" in

"\$define") xxx='sys/ioctl.h';

?X: otherwise \$xxx was set during the determination of i_sysioctl, above.

esac

?X:

?X: Can't use \$contains here since HP-UX 9.x has TIOCNOTTY between a pair

?X: of #ifdef/#endif and is never actually defined. Oh well...

?X:

\$cat > tcio.c <<EOM

#include <sys/types.h> /* Just in case */

#include <\$xxx>

int main()

{

#ifdef TIOCNOTTY

exit(0);

#else

exit(1);

#endif

}

EOM

if (\$cc -o tcio tcio.c && ./tcio) >/dev/null 2>&1; then

val="\$define"

echo "TIOCNOTTY found in <\$xxx>." >&4

echo "Using ioctl() call on /dev/tty to void tty association." >&4

else

val="\$undef"

echo "Closing

standard file descriptors should void tty association." >&4

fi

?LINT:set d_voidtty

set d_voidtty

eval \$setvar

\$rm -f tcio tcio.? core

@end

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/i_sysioctl.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 2003 Jarkko Hietaniemi

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?MAKE:d_scalbnl: Inlibc

?MAKE: -pick add \$@ %<

?S:d_scalbnl:

?S: This variable conditionally defines the HAS_SCALBNL symbol, which

?S: indicates to the C program that the scalbnl() routine is available.

?S: If ilogbl is also present we can emulate frexpl.

?S:.

?C:HAS_SCALBNL:

?C: This symbol, if defined, indicates that the scalbnl routine is

?C: available. If ilogbl is also present we can emulate frexpl.

?C:.

?H:#\$d_scalbnl HAS_SCALBNL /**/

?H:.

?LINT:set d_scalbnl

: see if scalbnl exists

set scalbnl d_scalbnl

eval \$inlibc

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_scalbnl.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_system.U 1 2006-08-24 12:32:52Z rmanfredi \$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic Licence,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic Licence; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: d_system.U,v \$

?RCS: Revision 3.0 1993/08/18 12:07:44 ram

?RCS: Baseline for dist 3.0 netwide release.
 ?RCS:
 ?MAKE:d_system: Inlibc
 ?MAKE: -pick add \$@ %<
 ?S:d_system:
 ?S: This variable conditionally defines HAS_SYSTEM if system() is
 ?S: available to issue a shell command.
 ?S:.
 ?C:HAS_SYSTEM (SYSTEM):
 ?C: This symbol, if defined, indicates that the system routine is
 ?C: available to issue a shell command.
 ?C:.
 ?H:#\$d_system HAS_SYSTEM /**/
 ?H:.
 ?LINT:set
 d_system
 : see if system exists
 set system d_system
 eval \$inlibc

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/d_system.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_srandom_r.U,v 0RCS:
 ?RCS: Copyright (c) 2002,2003 Jarkko Hietaniemi
 ?RCS:
 ?RCS: You may distribute under the terms of either the GNU General Public
 ?RCS: License or the Artistic License, as specified in the README file.
 ?RCS:
 ?RCS: Generated by the reentr.pl from the Perl 5.8 distribution.
 ?RCS:
 ?MAKE:d_srandom_r random_r_proto: Inlibc Protochk Hasproto i_systypes \
 usethreads i_stdlib extern_C
 ?MAKE: -pick add \$@ %<
 ?S:d_srandom_r:
 ?S: This variable conditionally defines the HAS_SRANDOM_R symbol,
 ?S: which indicates to the C program that the srandom_r()
 ?S: routine is available.
 ?S:.
 ?S:srandom_r_proto:
 ?S: This variable encodes the prototype of srandom_r.
 ?S: It is zero if d_srandom_r is undef, and one of the
 ?S: REENTRANT_PROTO_T_ABC macros of reentr.h if d_srandom_r
 ?S: is defined.
 ?S:.
 ?C:HAS_SRANDOM_R:

```

?C: This symbol, if defined, indicates that the srandom_r routine
?C: is available to srandom re-entrantly.
?C:.
?C:SRANDOM_R_PROTO:
?C: This
symbol encodes the prototype of srandom_r.
?C: It is zero if d_srandom_r is undef, and one of the
?C: REENTRANT_PROTO_T_ABC macros of reentr.h if d_srandom_r
?C: is defined.
?C:.
?H:#$d_srandom_r HAS_SRANDOM_R /**/
?H:#define SRANDOM_R_PROTO $srandom_r_proto /**/
?H:.
?T:try hdrs d_srandom_r_proto
: see if srandom_r exists
set srandom_r d_srandom_r
eval $inlibc
case "$d_srandom_r" in
"$define")
hdrs="$i_systypes sys/types.h define stdio.h $i_stdlib stdlib.h"
case "$d_srandom_r_proto:$usethreads" in
":define") d_srandom_r_proto=define
set d_srandom_r_proto srandom_r $hdrs
eval $hasproto ;;
*) ;;
esac
case "$d_srandom_r_proto" in
define)
case "$srandom_r_proto" in
"|0) try='int srandom_r(unsigned int, struct random_data*);'
./protochk "$extern_C $try" $hdrs && srandom_r_proto=I_TS ;;
esac
case "$srandom_r_proto" in
"|0) d_srandom_r=undef
srandom_r_proto=0
echo "Disabling srandom_r, cannot determine prototype."
>&4 ;;
* ) case "$srandom_r_proto" in
REENTRANT_PROTO*) ;;
*) srandom_r_proto="REENTRANT_PROTO_$$srandom_r_proto" ;;
esac
echo "Prototype: $try" ;;
esac
;;
*) case "$usethreads" in
define) echo "srandom_r has no prototype, not using it." >&4 ;;
esac
d_srandom_r=undef

```

```
srandom_r_proto=0
;;
esac
;;
*) srandom_r_proto=0
;;
esac
```

Found in path(s):

```
*/opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/threads/d_srandom_r.U
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: cf_who.U,v \$

?RCS: Revision 3.0.1.2 1997/02/28 15:28:50 ram

?RCS: patch61: new computation method avoiding use of temporary file

?RCS:

?RCS: Revision 3.0.1.1 1994/05/06 14:42:34 ram

?RCS: patch23: login name now computed the hard way

?RCS:

?RCS: Revision 3.0 1993/08/18 12:05:32 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?X:

?X: Oldconfig dependency is there to ensure computation occurs after old values

?X: from config.sh have been loaded, so that we can supersede them.

?X:

?MAKE:cf_time

cf_by: date Oldconfig

?MAKE: -pick add \$@ %<

?S:cf_time:

?S: Holds the output of the "date" command when the configuration file was

?S: produced. This is used to tag both config.sh and config_h.SH.

?S:.

?S:cf_by:

?S: Login name of the person who ran the Configure script and answered the

?S: questions. This is used to tag both config.sh and config_h.SH.

?S:.

?LINT:change LC_ALL LANGUAGE
: who configured the system
?X: Ensure English date -- Jarkko Hietaniemi
cf_time=`LC_ALL=C; LANGUAGE=C; export LC_ALL; export LANGUAGE; \$date 2>&1`
?X:
?X: Leave a white space between first two '(' for ksh. The sub-shell is needed
?X: on some machines to avoid the error message when logname is not found; e.g.
?X: on SUN-OS 3.2, (logname || whoami) would not execute whoami if logname was
?X: not found. Sigh!
?X:
?X: Convex had a broken logname executable which returned a non-zero status,
?X: and that broke the previous:
?X: cf_by=`(logname) 2>/dev/null || whoami) 2>&1`
?X: Switch to emergency
mode... -- RAM, 19/04/94
?X:
?X: Parentheses needed to avoid error message if the program does not exist.
?X: Uses case instead of \$test so it can be put before \$test is defined.
?X: Don't redirect to a file because on Ultrix (under script?) logname
?X: outputs a blank line first. This method will apparently work.
case "\$cf_by" in
"")
cf_by=`(logname) 2>/dev/null`
case "\$cf_by" in
"")
cf_by=`(whoami) 2>/dev/null`
case "\$cf_by" in
"") cf_by=unknown ;;
esac ;;
esac ;;
esac

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/modified/cf_who.U

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/cf_who.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_getgrps.U 1 2006-08-24 12:32:52Z rmanfredi \$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic Licence,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic Licence; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:
?RCS: \$Log: d_getgrps.U,v \$
?RCS: Revision 3.0 1993/08/18 12:06:08 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:d_getgrps: Inlibc
?MAKE: -pick add \$@ %<
?S:d_getgrps:
?S: This variable conditionally defines the HAS_GETGROUPS symbol, which
?S: indicates to the C program that the getgroups() routine is available
?S: to get the list of process groups.
?S:.
?C:HAS_GETGROUPS (GETGROUPS):
?C: This symbol, if defined, indicates that the getgroups()
routine is
?C: available to get the list of process groups. If unavailable, multiple
?C: groups are probably not supported.
?C:.
?H:#\$d_getgrps HAS_GETGROUPS /**/
?H:.
?LINT:set d_getgrps
: see if getgroups exists
set getgroups d_getgrps
eval \$inlibc

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/d_getgrps.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: i_sysparam.U 1 2006-08-24 12:32:52Z rmanfredi \$
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: \$Log: i_sysparam.U,v \$
?RCS: Revision 3.0.1.1 1994/08/29 16:22:43 ram
?RCS: patch32: created
?RCS:
?MAKE:i_sysparam: Inhdr
?MAKE: -pick add \$@ %<
?S:i_sysparam:
?S: This variable conditionally defines the I_SYS_PARAM symbol, and indicates

?S: whether a C program should include <sys/param.h>.
?S:.
?C:I_SYS_PARAM:
?C: This symbol, if defined, indicates to the C program that it should
?C: include <sys/param.h>.
?C:.
?H:#\$i_sysparam I_SYS_PARAM /**/
?H:.
?LINT:set
i_sysparam
: see if this is a sys/param system
set sys/param.h i_sysparam
eval \$inhdr

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/i_sysparam.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: i_systimes.U 1 2006-08-24 12:32:52Z rmanfredi \$
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: \$Log: i_systimes.U,v \$
?RCS: Revision 3.0 1993/08/18 12:08:39 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:i_systimes: Inhdr
?MAKE: -pick add \$@ %<
?S:i_systimes:
?S: This variable conditionally defines the I_SYS_TIMES symbol, and indicates
?S: whether a C program should include <sys/times.h>.
?S:.
?C:I_SYS_TIMES (I_SYSTIMES):
?C: This symbol, if defined, indicates to the C program that it should
?C: include <sys/times.h>.
?C:.
?H:#\$i_systimes I_SYS_TIMES /**/
?H:.
?LINT:set
i_systimes
: see if this is a sys/times.h system

```
set sys/times.h i_systimes
eval $inhdr
```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/i_systimes.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: d_getservprotos.U,v $
```

```
?RCS:
```

```
?RCS: Copyright (c) 1991-1993, Raphael Manfredi
```

```
?RCS:
```

```
?RCS: You may redistribute only under the terms of the Artistic License,
```

```
?RCS: as specified in the README file that comes with the distribution.
```

```
?RCS: You may reuse parts of this distribution only within the terms of
```

```
?RCS: that same Artistic License; a copy of which may be found at the root
```

```
?RCS: of the source tree for dist 3.0.
```

```
?RCS:
```

```
?MAKE:d_getservprotos : Hasproto i_netdb
```

```
?MAKE: -pick add $@ %<
```

```
?S:d_getservprotos:
```

```
?S: This variable conditionally defines the HAS_GETSERV_PROTOS symbol,
```

```
?S: which indicates to the C program that <netdb.h> supplies
```

```
?S: prototypes for the various getserv*() functions.
```

```
?S: See also netdbtype.U for probing for various netdb types.
```

```
?S:.
```

```
?C:HAS_GETSERV_PROTOS:
```

```
?C: This symbol, if defined, indicates that <netdb.h> includes
```

```
?C: prototypes for getservent(), getservbyname(), and
```

```
?C: getservbyaddr(). Otherwise,
```

```
it is up to the program to guess
```

```
?C: them. See netdbtype.U for probing for various Netdb_xxx_t types.
```

```
?C:.
```

```
?H:#$d_getservprotos HAS_GETSERV_PROTOS /**/
```

```
?H:.
```

```
?LINT:set d_getservprotos
```

```
: see if prototypes for various getservxxx netdb.h functions are available
```

```
echo " "
```

```
set d_getservprotos getservent $i_netdb netdb.h
```

```
eval $hasproto
```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/protos/d_getservprotos.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: d_setregid.U 1 2006-08-24 12:32:52Z rmanfredi $
```

```
?RCS:
```

```

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: $Log: d_setregid.U,v $
?RCS: Revision 3.0 1993/08/18 12:07:12 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:d_setregid d_setresgid: Inlibc
?MAKE: -pick add $@ %<
?S:d_setregid:
?S: This variable conditionally defines HAS_SETREGID if setregid() is
?S: available to change the real and effective gid of the current
?S: process.
?S:.
?S:d_setresgid:
?S: This variable conditionally defines HAS_SETRESGID if setresgid() is
?S: available to change
?S: the real, effective and saved gid of the current
?S: process.
?S:.
?C:HAS_SETREGID (SETREGID):
?C: This symbol, if defined, indicates that the setregid routine is
?C: available to change the real and effective gid of the current
?C: process.
?C:.
?C:HAS_SETRESGID (SETRESGID):
?C: This symbol, if defined, indicates that the setresgid routine is
?C: available to change the real, effective and saved gid of the current
?C: process.
?C:.
?H:#$d_setregid HAS_SETREGID /**/
?H:#$d_setresgid HAS_SETRESGID /**/
?H:.
?LINT: set d_setregid d_setresgid
: see if setregid exists
set setregid d_setregid
eval $inlibc
set setresgid d_setresgid
eval $inlibc

Found in path(s):
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/d_setregid.U

```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: d_rdchk.U 1 2006-08-24 12:32:52Z rmanfredi $
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: $Log: d_rdchk.U,v $
?RCS: Revision 3.0 1993/08/18 12:06:51 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:d_rdchk: Inlibc
?MAKE: -pick add $@ %<
?S:d_rdchk:
?S: This variable conditionally defines the HAS_RDCHK symbol, which
?S: indicates to the C program that the rdchk() routine is available
?S: to find out if there is input pending on an IO channel.
?S:.
?C:HAS_RDCHK (RDCHK):
?C: This symbol, if defined, indicates that the rdchk routine
is available
?C: to find out if there is input pending on an IO channel. Generally
?C: the routine is used only if FIONREAD and O_NDELAY aren't available.
?C:.
?H:#$d_rdchk HAS_RDCHK /**/
?H:.
?LINT:set d_rdchk
: see if rdchk exists
set rdchk d_rdchk
eval $inlibc
```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/d_rdchk.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id$
?RCS:
?RCS: Copyright (c) 1998, Jarkko Hietaniemi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
```

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 3.0.

?RCS:

?MAKE:i_netinettcp: Inhdr

?MAKE: -pick add \$@ %<

?S:i_netinettcp:

?S: This variable conditionally defines the I_NETINET_TCP symbol,

?S: and indicates whether a C program should include <netinet/tcp.h>.

?S:.

?C:I_NETINET_TCP:

?C: This symbol, if defined, indicates to the C program that it should

?C: include <netinet/tcp.h>.

?C:.

?H:#\$i_netinettcp I_NETINET_TCP /**/

?H:.

?LINT:set i_netinettcp

: see if netinet/tcp.h is available

set netinet/tcp.h i_netinettcp

eval \$inhdr

Found in path(s):

*

/opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/i_netinettcp.U

No license file was found, but licenses were detected in source scan.

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?MAKE:d_remquo: Inlibc

?MAKE: -pick add \$@ %<

?S:d_remquo:

?S: This variable conditionally defines the HAS_REMQUO symbol, which

?S: indicates to the C program that the remquo() routine is available.

?S:.

?C:HAS_REMQUO:

?C: This symbol, if defined, indicates that the remquo routine is

?C: available to return the remainder and part of quotient.

?C:.

?H:#\$d_remquo HAS_REMQUO /**/

?H:.

?LINT:set d_remquo

: see if remquo exists

set remquo d_remquo

eval \$inlibc

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-

debian-perl-5.26.1/U/perl/d_remquo.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 2009 H.Merijn Brand

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?MAKE:d_inetpton: Inlibc

?MAKE: -pick add \$@ %<

?S:d_inetpton:

?S: This variable conditionally defines the HAS_INETPTON symbol,

?S: which indicates to the C program that the inet_pton() function

?S: is available.

?S:.

?C:HAS_INETPTON:

?C: This symbol, if defined, indicates that the inet_pton() function

?C: is available to parse IPv4 and IPv6 strings.

?C:.

?H:#\$d_inetpton HAS_INETPTON /**/

?H:.

?LINT:set d_inetpton

: see if inet_pton exists

set inet_pton d_inetpton

eval \$inlibc

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-

debian-perl-5.26.1/U/perl/d_inetpton.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_getpagsz.U,v 3.0.1.1 1994/10/29 16:13:10 ram Exp \$

?RCS:

?RCS: Copyright (c) 1991-1993, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 3.0.

?RCS:

?RCS: \$Log: d_getpagsz.U,v \$

?RCS: Revision 3.0.1.1 1994/10/29 16:13:10 ram

?RCS: patch36: added ?F: line for metalint file checking

?RCS:

?RCS: Revision 3.0 1993/08/18 12:06:14 ram

?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:d_getpagsz: Compile Oldconfig Myread Inlibc Findhdr
?MAKE: -pick add \$@ %<
?S:d_getpagsz:
?S: This variable conditionally defines HAS_GETPAGESIZE if getpagesize()
?S: is available to get the system page size.
?S:.
?C:HAS_GETPAGESIZE
(GETPAGESIZE):
?C: This symbol, if defined, indicates that the getpagesize system call
?C: is available to get system page size, which is the granularity of
?C: many memory management calls.
?C:.
?H:#\$d_getpagsz HAS_GETPAGESIZE /**/
?H:.
?LINT:set d_getpagsz
: see if getpagesize exists
set getpagesize d_getpagsz
eval \$inlibc

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/compline/d_getpagsz.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$
?RCS:
?RCS: Copyright (c) 1999 Jarkko Hietaniemi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 3.0.
?RCS:
?MAKE:d_endspent: Inlibc
?MAKE: -pick add \$@ %<
?S:d_endspent:
?S: This variable conditionally defines HAS_ENDSPENT if endspent() is
?S: available to finalize the scan of SysV shadow password entries.
?S:.
?C:HAS_ENDSPENT:
?C: This symbol, if defined, indicates that the endspent system call is
?C: available to finalize the scan of SysV shadow password entries.
?C:.
?H:#\$d_endspent HAS_ENDSPENT /**/
?H:.

```
?LINT:set d_endspent
: see if endspent exists
set endspent d_endspent
eval $inlibc
```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/perl/d_endspent.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id$
```

```
?RCS:
```

```
?RCS: Copyright (c) 1999, Jarkko Hietaniemi
```

```
?RCS:
```

```
?RCS: This file is included with or a derivative work of a file included
```

```
?RCS: with the metaconfig program of Raphael Manfredi's "dist" distribution.
```

```
?RCS: In accordance with clause 7 of dist's modified Artistic License:
```

```
?RCS:
```

```
?RCS: You may distribute under the terms of either the GNU General Public
```

```
?RCS: License or the Artistic License, as specified in the README file.
```

```
?RCS:
```

```
?MAKE:multiarch: osname
```

```
?MAKE: -pick add $@ %<
```

```
?S:multiarch:
```

```
?S: This variable conditionally defines the MULTIARCH symbol
```

```
?S: which signifies the presence of multiplatform files.
```

```
?S: This is normally set by hints files.
```

```
?S:.
```

```
?C:MULTIARCH:
```

```
?C: This symbol, if defined, signifies that the build
```

```
?C: process will produce some binary files that are going to be
```

```
?C: used in a cross-platform environment. This is the case for
```

```
?C: example with the NeXT "fat" binaries that contain executables
```

```
?C: for
```

```
several CPUs.
```

```
?C:.
```

```
?H:#$multiarch MULTIARCH /**/
```

```
?H:.
```

```
: Check if is a multiplatform env
```

```
case "$osname" in
```

```
darwin) multiarch="$define" ;;
```

```
esac
```

```
case "$multiarch" in
```

```
"[nN]*) multiarch="$undef" ;;
```

```
esac
```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
```

debian-perl-5.26.1/U/a_dvisory/multiarch.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: i_memory.U 1 2006-08-24 12:32:52Z rmanfredi \$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic Licence,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic Licence; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: i_memory.U,v \$

?RCS: Revision 3.0.1.3 1994/06/20 07:01:55 ram

?RCS: patch30: cosmetic changes

?RCS:

?RCS: Revision 3.0.1.2 1994/05/13 15:23:56 ram

?RCS: patch27: modified to avoid spurious Whoa warnings (ADO)

?RCS:

?RCS: Revision 3.0.1.1 1994/05/06 15:02:25 ram

?RCS: patch23: avoid conflicts with <string.h>

?RCS:

?RCS: Revision 3.0 1993/08/18 12:08:22 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?MAKE:i_memory: Inhdr strings cppstdin

cppflags cppminus contains rm Setvar

?MAKE: -pick add \$@ %<

?S:i_memory:

?S: This variable conditionally defines the I_MEMORY symbol, and indicates

?S: whether a C program should include <memory.h>.

?S:.

?C:I_MEMORY:

?C: This symbol, if defined, indicates to the C program that it should

?C: include <memory.h>.

?C:.

?H:#\$i_memory I_MEMORY /**/

?H:.

?LINT:set i_memory

?X:

?X: Unfortunately, the definitions of memory functions sometimes

?X: conflict with those in <string.h>. We'll assume that if

?X: <string.h> contains memcpy, then we don't need memory.h

?X:

: see if memory.h is available.

val="

set memory.h val

eval \$inhdr

```
: See if it conflicts with string.h
case "$val" in
$define)
case "$strings" in
") ;;
*)
$cpptest $cpptestflags $cpptestminus < $strings > mem.h
if $contains 'memcpy' mem.h >/dev/null 2>&1; then
echo " "
echo "We won't be including <memory.h>."
val="$undef"
fi
$rm -f mem.h
;;
esac
esac
set i_memory
eval $setvar
```

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/i_memory.U

No license file was found, but licenses were detected in source scan.

?RCS: You may redistribute only under the terms of the Artistic Licence,

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/mkdep.U

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/d_PORTAR.U

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/d_pidcheck.U

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/d_dbl_dig.U

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/nlist_pfx.U

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/d_brokstat.U

*

/opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/d_bsdjmp.U

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/d_nolnbuf.U

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/d_charsprf.U

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/d_ckeypad.U

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/Magic_h.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1999, Jarkko Hietaniemi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 3.0.

?RCS:

?MAKE:d_sigtimedwait: Inlibc

?MAKE: -pick add \$@ %<

?S:d_sigtimedwait:

?S: This variable conditionally defines HAS_SIGTIMEDWAIT

?S: if sigtimedwait() is available to wait a signal and additional

?S: information, with a timeout.

?S:.

?C:HAS_SIGTIMEDWAIT:

?C: This symbol, if defined, indicates that the sigtimedwait

?C: system call is available to wait a signal and additional information,

?C: with a timeout.

?C:.

?H:#\$d_sigtimedwait HAS_SIGTIMEDWAIT /**/

?H:.

?LINT:set d_sigtimedwait

: see if sigtimedwait exists

set sigtimedwait

d_sigtimedwait

eval \$inlibc

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_sigtimedwait.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 2000 Jarkko Hietaniemi

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

```

?MAKE:d_fpclassl: Inlibc
?MAKE: -pick add $@ %<
?S:d_fpclassl:
?S: This variable conditionally defines the HAS_FPCLASSL symbol, which
?S: indicates to the C program that the fpclassl() routine is available.
?S:.
?C:HAS_FPCLASSL:
?C: This symbol, if defined, indicates that the fpclassl routine is
?C: available to classify long doubles. Available for example in IRIX.
?C: The returned values are defined in <ieeefp.h> and are:
?C:
?C: FP_SNAN signaling NaN
?C: FP_QNAN quiet NaN
?C: FP_NINF negative infinity
?C: FP_PINF positive infinity
?C: FP_NDENORM negative denormalized non-zero
?C: FP_PDENORM positive denormalized non-zero
?C: FP_NZERO negative zero
?C: FP_PZERO positive zero
?C: FP_NNORM negative
normalized non-zero
?C: FP_PNORM positive normalized non-zero
?C:.
?H:#$d_fpclassl HAS_FPCLASSL /**/
?H:.
?LINT:set d_fpclassl
: see if fpclassl exists
set fpclassl d_fpclassl
eval $inlibc

```

Found in path(s):

```

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/perl/d_fpclassl.U

```

No license file was found, but licenses were detected in source scan.

```

?RCS: $Id: d_su_chown.U 1 2006-08-24 12:32:52Z rmanfredi $
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: $Log: d_su_chown.U,v $
?RCS: Revision 3.0 1993/08/18 12:07:40 ram
?RCS: Baseline for dist 3.0 netwide release.

```

```

?RCS:
?MAKE:d_su_chown: Csym Setvar
?MAKE: -pick add $@ %<
?S:d_su_chown (d_rootchown):
?S: This variable conditionally defines the SU_CHOWN symbol, which
?S: indicates to the C program that only root can chown() the owner
?S: of a file.
?S:.
?C:SU_CHOWN (ROOT_CHOWN):
?C: This symbol, if defined, indicates that the system allows only root
?C: can
    change the owner of a file with chown().
?C:.
?H:#$d_su_chown SU_CHOWN /**/
?H:.
?LINT:set d_su_chown
: see if 'chown()' is restricted.
: but not too hard, as it is late and I am tired. -- HMS
echo " "
if set setreuid val -f d_su_chown; eval $csym; $val; then
echo 'It looks like only root can chown() the owner of a file.' >&4
val="$define"
else
echo 'It looks like root or the owner can chown() a file away.' >&4
val="$undef"
fi
set d_su_chown
eval $setvar

```

Found in path(s):

```

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/d_su_chown.U

```

No license file was found, but licenses were detected in source scan.

```

?RCS: $Id: cpp_stuff.U 1 2006-08-24 12:32:52Z rmanfredi $
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: $Log: cpp_stuff.U,v $
?RCS: Revision 3.0.1.1 1994/10/29 16:08:24 ram
?RCS: patch36: now uses cppstdin instead of plain cpp for consistency (ADO)
?RCS: patch36: remove temporary files when done

```

?RCS:
?RCS: Revision 3.0 1993/08/18 12:05:36 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:cpp_stuff: cat contains cppstdin cppflags cppminus rm
?MAKE: -pick add \$@ %<
?S:cpp_stuff:
?S: This variable contains an identification of the concatenation
mechanism
?S: used by the C preprocessor.
?S:.
?C:CAT2:
?C: This macro concatenates 2 tokens together.
?C:.
?C:CAT3:
?C: This macro concatenates 3 tokens together.
?C:.
?C:CAT4:
?C: This macro concatenates 4 tokens together.
?C:.
?C:CAT5:
?C: This macro concatenates 5 tokens together.
?C:.
?C:STRINGIFY:
?C: This macro surrounds its token with double quotes.
?C:.
?C:SCAT2:
?C: This macro concatenates 2 tokens together and stringifies the result.
?C: It might not exist, so #ifdef it in your code!
?C:.
?C:SCAT3:
?C: This macro concatenates 3 tokens together and stringifies the result.
?C: It might not exist, so #ifdef it in your code!
?C:.
?C:SCAT4:
?C: This macro concatenates 4 tokens together and stringifies the result.
?C: It might not exist, so #ifdef it in your code!
?C:.
?C:SCAT5:
?C: This macro concatenates 5 tokens together and stringifies the result.
?C: It might not exist, so #ifdef it in your code!
?C:.
?X: Dist pl70 included the following, but AIX's xlc compiler
?X: (which
is ANSI-ish and has cpp_stuff == 42)) rejects
?X: The SQuoTe/EQuoTe stuff because the string literals are on
?X: separate lines. Sigh.
?X: Andy Dougherty 24 Feb 1998

```

?X: ?H:??<:#if $cpp_stuff == 1
?X: ?H:?CAT2:#define CAT2(a,b)a/**/b
?X: ?H:?CAT3:#define CAT3(a,b,c)a/**/b/**/c
?X: ?H:?CAT4:#define CAT4(a,b,c,d)a/**/b/**/c/**/d
?X: ?H:?CAT5:#define CAT5(a,b,c,d,e)a/**/b/**/c/**/d/**/e
?X: ?H:?STRINGIFY:#define STRINGIFY(a)"a"
?X: ?H:??<:#define SQuoTe(a)"a"
?X: ?H:??<:#define EQuoTe(a)a"
?X: ?H:?SCAT2:#define SCAT2(a,b)EQuoTe(SQuoTe(a)b)
?X: ?H:?SCAT3:#define SCAT3(a,b,c)EQuoTe(SQuoTe(a)b/**/c)
?X: ?H:?SCAT4:#define SCAT4(a,b,c,d)EQuoTe(SQuoTe(a)b/**/c/**/d)
?X: ?H:?SCAT5:#define SCAT5(a,b,c,d,e)EQuoTe(SQuoTe(a)b/**/c/**/d/**/e)
?X: ?H:??<:#endif
?H:??<:#if $cpp_stuff == 1
?H:?CAT2:#define CAT2(a,b) a/**/b
?H:?CAT3:#define CAT3(a,b,c) a/**/b/**/c
?H:?CAT4:#define CAT4(a,b,c,d) a/**/b/**/c/**/d
?H:?CAT5:#define CAT5(a,b,c,d,e) a/**/b/**/c/**/d/**/e
?H:?STRINGIFY:#define STRINGIFY(a) "a"
?X: If
    you can get stringification with catify, tell me how!
?H:??<:#endif
?H:??<:#if $cpp_stuff == 42
?H:??<:#define PeRl_CaTiFy(a, b) a ## b
?H:??<:#define PeRl_StGiFy(a) #a
?X: The additional level of indirection enables these macros to be
?X: used as arguments to other macros. See K&R 2nd ed., page 231.
?H:?CAT2:#define CAT2(a,b) PeRl_CaTiFy(a,b)
?H:?CAT3:#define CAT3(a,b,c) CAT2(PeRl_CaTiFy(a,b),c)
?H:?CAT4:#define CAT4(a,b,c,d) CAT2(CAT3(a,b,c),d)
?H:?CAT5:#define CAT5(a,b,c,d,e) CAT2(CAT4(a,b,c,d),e)
?H:??<:#define StGiFy(a) PeRl_StGiFy(a)
?H:?STRINGIFY:#define STRINGIFY(a) PeRl_StGiFy(a)
?H:?SCAT2:#define SCAT2(a,b) PeRl_StGiFy(a) PeRl_StGiFy(b)
?H:?SCAT3:#define SCAT3(a,b,c) PeRl_StGiFy(a) PeRl_StGiFy(b) PeRl_StGiFy(c)
?H:?SCAT4:#define SCAT4(a,b,c,d) PeRl_StGiFy(a) PeRl_StGiFy(b) PeRl_StGiFy(c) PeRl_StGiFy(d)
?H:?SCAT5:#define SCAT5(a,b,c,d,e) PeRl_StGiFy(a) PeRl_StGiFy(b) PeRl_StGiFy(c) PeRl_StGiFy(d)
PeRl_StGiFy(e)
?H:??<:#endif
?H:??<:#if $cpp_stuff != 1 && $cpp_stuff
    != 42
?H:??<:#include "Bleth: How does this C preprocessor concatenate tokens?"
?H:??<:#endif
?H:.
?W:%<:CAT2 CAT3 CAT4 CAT5 STRINGIFY SCAT2 SCAT3 SCAT4 SCAT5
?F:!cpp_stuff.c
?LINT:known StGiFy
?LINT:known PeRl_CaTiFy

```

```

?LINT:known PeRI_StGiFy
: how do we concatenate cpp tokens here?
echo " "
echo "Checking to see how your cpp does stuff like concatenate tokens..." >&4
$cat >cpp_stuff.c <<'EOCP'
#define RCAT(a,b)a/**/b
#define ACAT(a,b)a ## b
RCAT(Rei,ser)
ACAT(Cir,cus)
EOCP
$cppstdin $cppflags $cppminus <cpp_stuff.c >cpp_stuff.out 2>&1
if $contains 'Circus' cpp_stuff.out >/dev/null 2>&1; then
echo "Oh! Smells like ANSI's been here." >&4
echo "We can catify or stringify, separately or together!"
cpp_stuff=42
elif $contains 'Reiser' cpp_stuff.out >/dev/null 2>&1; then
echo "Ah, yes! The good old days!" >&4
echo "However, in the good old days we don't know how to stringify and"
echo "catify at the same time."
cpp_stuff=1
else
$cat >&4 <<EOM
Hmm, I don't seem to be able to concatenate
tokens with your cpp.
You're going to have to edit the values of CAT[2-5] in config.h...
EOM
?X: It would be nice to have configure remind us at the end that some manual
?X: intervention is needed -- FIXME
cpp_stuff="/* Help! How do we handle cpp_stuff? */*/"
fi
$rm -f cpp_stuff.*

```

Found in path(s):

```

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/modified/cpp_stuff.U

```

No license file was found, but licenses were detected in source scan.

```

?RCS: $Id: d_NeWS.U 1 2006-08-24 12:32:52Z rmanfredi $
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: $Log: d_NeWS.U,v $

```

```

?RCS: Revision 3.0 1993/08/18 12:05:39 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:d_news d_news0 d_newshome d_textcan: test rm Myread Getfile
?MAKE: -pick add $@ %<
?S:d_news:
?S: Set if running NeWS 1.1
?S:.
?S:d_news0:
?S: Set if running NeWS 1.0
?S:.
?S:d_newshome:
?S: Path to the top directory of the NeWS structure.
?S:.
?S:d_textcan:
?S: Path to where the textcan.ps stuff is...
?S:.
?C:HAS_NEWS1_1 (NEWS1_1):
?C: This
symbol defined if running NeWS 1.1.
?C:.
?C:HAS_NEWS1_0 (NEWS1_0):
?C: This symbol defined if running NeWS 1.0.
?C:.
?C:TEXTCAN:
?C: Tells path to where the textcan.ps stuff is...
?C:.
?H:#$d_news HAS_NEWS1_1 /**/
?H:#$d_news0 HAS_NEWS1_0 /**/
?H:#define TEXTCAN $d_textcan /**/
?H:.
?INIT:: default path for NeWS
?INIT:d_newshome="/usr/NeWS"
?INIT:
: Check to see what version of NeWS is being run?
cd ..
echo " "
echo "Now for the interesting stuff... Lets see what kind of NeWS"
echo "they grow round here...."
echo " "
dflt='y'
if $test -d $d_newshome; then
d_newshome=`(cd $d_newshome ; /bin/pwd)`
echo "Ah...found myself a NeWS in $d_newshome..."
dflt='y'
rp="Is this the NeWS you want your children to grow up with?"
. UU/myread
fi

```

```

while $test $ans = "n"; do
dflt=$d_newshome
fn=d
rp="Path to NeWS you want:"
. UU/getfile
d_newshome=$ans

echo " "
if $test ! -d $d_newshome/lib; then
echo "ARG! No lib directory in $d_newshome!!!"
: heavy medicine. I wonder what the disease
is...
$rm -f kit*isdone
$rm -rf UU
: bye bye
set -t; echo "Sorry... no NeWS is bad news..."
fi

if $test -r $d_newshome/lib/NeWS/colors.ps ; then
echo 'Ahh... your running NeWS 1.1! Boy... that makes stuff easy....'
echo " "
d_news="$define"
d_news0="$undef"
if $test -r $d_newshome/lib/NeWS/textcan.ps; then
d_textcan=$d_newshome/lib/NeWS
echo "The textcan.ps stuff seems to be in : $d_textcan"
else
d_textcan=$d_newshome/clientsrc/client/nterm
if $test ! -r $d_textcan/textcan.ps; then
d_news="$undef"
d_news0="$define"
echo 'Hmm... must have been fooled... gotta be NeWS 1.1 beta!'
else
echo "The textcan.ps stuff seems to be in : $d_textcan"
fi
fi
else
echo 'snif... sniff... I smell the dilapidated smell of NeWS 1.0..'
echo 'Some things will not work under NeWS 1.0...'
d_news="$undef"
d_news0="$define"
fi
cd UU

Found in path(s):
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/d_NeWS.U

```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id$
?RCS:
?RCS: Copyright (c) 1999 Jarkko Hietaniemi
?RCS:
?RCS: You may distribute under the terms of either the GNU General Public
?RCS: License or the Artistic License, as specified in the README file.
?RCS:
?MAKE:uselargefiles \
ccflags_uselargefiles \
ldflags_uselargefiles \
libswanted_uselargefiles: \
Myread Oldconfig Setvar test lseeksize fpossize \
fpostype Compile echo n c cat lseektype rm_try run \
use64bitint use64bitall i_stdlib
?MAKE: -pick add $@ %<
?Y:TOP
?S:uselargefiles:
?S: This variable conditionally defines the USE_LARGE_FILES symbol,
?S: and indicates that large file interfaces should be used when
?S: available.
?S:.
?S:ccflags_uselargefiles:
?S: This variable contains the compiler flags needed by large file builds
?S: and added to ccflags by hints files.
?S:.
?S:ldflags_uselargefiles:
?S: This variable contains the loader flags needed by large file builds
?S: and added to ldflags by
?S: hints files.
?S:.
?S:libswanted_uselargefiles:
?S: This variable contains the libraries needed by large file builds
?S: and added to ldflags by hints files. It is a space separated list
?S: of the library names without the "lib" prefix or any suffix, just
?S: like libswanted..
?S:.
?C:USE_LARGE_FILES:
?C: This symbol, if defined, indicates that large file support
?C: should be used when available.
?C:.
?H:?%<:#ifndef USE_LARGE_FILES
?H:?%<:#$uselargefiles USE_LARGE_FILES /**/
?H:?%<:#endif
?H:.
?INIT:ccflags_uselargefiles="
?INIT:ldflags_uselargefiles="
```

```

?INIT:libswanted_uselargefiles="
?T:yyy zzz
?F:!uselargefiles.cbu !try
?LINT:change lseeksize
?LINT:change fpossize
?LINT:extern uselfs
?LINT:use use64bitint
?LINT:use use64bitall
: Check for large file support
# Backward compatibility (uselfs is deprecated).
case "$uselfs" in
"$define"|true|[yY]*)
cat <<EOM >&4

*** Configure -Duselfs is deprecated, using -Duselargefiles instead.

```

```

EOM
uselargefiles="$define"
;;
esac

```

```

case "$lseeksize:$fpossize"
in
8:8) cat <<EOM

```

You can have files larger than 2 gigabytes.

```

EOM
val="$define" ;;
*) case "$uselargefiles" in
"$undef"|false|[nN]*) dflt='n' ;;
*) dflt='y' ;;
esac
cat <<EOM

```

Perl can be built to understand large files (files larger than 2 gigabytes) on some systems. To do so, Configure can be run with `-Duselargefiles`.

If this doesn't make any sense to you, just accept the default `'$dflt'`.

```

EOM
rp="Try to understand large files, if available?"
./myread
case "$ans" in
y|Y) val="$define" ;;
*) val="$undef" ;;
esac
;;
esac
set uselargefiles
eval $setvar

```

```

: Look for a hint-file generated 'call-back-unit'. If the
: user has specified that a large files perl is to be built,
: we may need to set or change some other defaults.
if $test -f uselargefiles.cbu; then
  echo "Your platform has some specific hints regarding large file builds, using them..."
  . ./uselargefiles.cbu
fi
case "$uselargefiles" in
"$define")
  if $test -f uselargefiles.cbu;
  then
    echo " "
    echo "Rechecking to see how big your file offsets are..." >&4
    $cat >try.c <<EOCP
#include <sys/types.h>
#include <stdio.h>
int main()
{
  printf("%d\n", (int)sizeof($lseektype));
  return(0);
}
EOCP
  set try
  if eval $compile_ok; then
    lseeksize=`$run ./try`
    $echo "Your file offsets are now $lseeksize bytes long."
  else
    dflt="$lseeksize"
    echo " "
    echo "(I can't seem to compile the test program. Guessing...)"
    rp="What is the size of your file offsets (in bytes)?"
    . ./myread
    lseeksize="$ans"
  fi
  case "$fpostype" in
*_t) zzz="$fpostype" ;;
*) zzz="fpos_t" ;;
esac
  $echo $n "Rechecking the size of $zzz...$c" >&4
  $cat > try.c <<EOCP
#include <sys/types.h>
#include <stdio.h>
#include <stdlib.h>
#ifdef L_STDLIB
#include <stdlib.h>
#endif
int main() {
  printf("%d\n", (int)sizeof($fpostype));

```

```

    return(0);
}
EOCP
set try
if eval $compile_ok; then
    yyy=`$run ./try`
    dflt="$lseeksize"
    case "$yyy" in
    *) echo
    " "
        echo "(I can't execute the test program--guessing $fpossizem.)" >&4
        ;;
    *) fpossizem=$yyy
        echo "$fpossizem bytes." >&4
        ;;
    esac
else
    dflt="$fpossizem"
    echo " "
    echo "(I can't compile the test program. Guessing...)" >&4
    rp="What is the size of your file positions (in bytes)?"
    ./myread
    fpossizem="$ans"
fi
$rm_try
fi
;;
esac

```

Found in path(s):

```

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/perl/uselfs.U

```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_scandir.U 1 2006-08-24 12:32:52Z rmanfredi \$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic Licence,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic Licence; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: d_scandir.U,v \$

?RCS: Revision 3.0.1.1 1994/01/24 14:06:35 ram

?RCS: patch16: created

?RCS:

?MAKE:d_scandir: Inlibc
?MAKE: -pick add \$@ %<
?S:d_scandir:
?S: This variable conditionally defines HAS_SCANDIR if scandir() is
?S: available to scan a directory.
?S:.
?C:HAS_SCANDIR:
?C: This symbol, if defined, indicates that the scandir routine is
?C: available to scan a directory.
?C:.
?H:#\$d_scandir HAS_SCANDIR /**/
?H:.
?LINT:set d_scandir
: see if
scandir exists
set scandir d_scandir
eval \$inlibc

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/d_scandir.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1999-2016 Jarkko Hietaniemi

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?MAKE:d_PRIfldbl sPRIfldbl d_PRIgldbl d_PRIFUldbl sPRIGUldbl d_PRIEUldbl \
sPRIgldbl d_PRIldbl sPRIldbl sPRIFUldbl d_PRIGUldbl sPRIEUldbl \
d_SCNfldbl d_double_style_vax d_double_style_ieee \
d_double_style_ibm d_double_style_cray d_double_has_subnormals \
d_double_has_inf d_double_has_nan d_double_has_negative_zero \
sSCNfldbl doublekind: \
d_longdbl longdblsize doublesize uselongdouble test echo cat rm_try \
Setvar Compile run i_stdlib osname gccversion ccflags

?MAKE: -pick add \$@ %<

?S:doublekind:

?S: This variable, if defined, encodes the type of a double:

?S: 1 = IEEE 754 32-bit little endian,

?S: 2 = IEEE 754 32-bit big endian,

?S: 3 = IEEE 754 64-bit little endian,

?S: 4 = IEEE

754 64-bit big endian,

?S: 5 = IEEE 754 128-bit little endian,

?S: 6 = IEEE 754 128-bit big endian,

?S: 7 = IEEE 754 64-bit mixed endian le-be,
 ?S: 8 = IEEE 754 64-bit mixed endian be-le,
 ?S: 9 = VAX 32bit little endian F float format
 ?S: 10 = VAX 64bit little endian D float format
 ?S: 11 = VAX 64bit little endian G float format
 ?S: 12 = IBM 32bit format
 ?S: 13 = IBM 64bit format
 ?S: 14 = Cray 64bit format
 ?S: -1 = unknown format.
 ?S:.
 ?S:d_PRIfldbl:
 ?S: This variable conditionally defines the PERL_PRIfldbl symbol, which
 ?S: indicates that stdio has a symbol to print long doubles.
 ?S:.
 ?S:d_PRIgldbl:
 ?S: This variable conditionally defines the PERL_PRIfldbl symbol, which
 ?S: indicates that stdio has a symbol to print long doubles.
 ?S:.
 ?S:d_PRIeldbl:
 ?S: This variable conditionally defines the PERL_PRIfldbl symbol, which
 ?S: indicates that stdio has a symbol to print long doubles.
 ?S:.
 ?S:d_PRIFUldbl:
 ?S: This variable conditionally defines the PERL_PRIfldbl symbol, which
 ?S: indicates
 that stdio has a symbol to print long doubles.
 ?S: The 'U' in the name is to separate this from d_PRIfldbl so that even
 ?S: case-blind systems can see the difference.
 ?S:.
 ?S:d_PRIGUldbl:
 ?S: This variable conditionally defines the PERL_PRIfldbl symbol, which
 ?S: indicates that stdio has a symbol to print long doubles.
 ?S: The 'U' in the name is to separate this from d_PRIgldbl so that even
 ?S: case-blind systems can see the difference.
 ?S:.
 ?S:d_PRIEUldbl:
 ?S: This variable conditionally defines the PERL_PRIfldbl symbol, which
 ?S: indicates that stdio has a symbol to print long doubles.
 ?S: The 'U' in the name is to separate this from d_PRIeldbl so that even
 ?S: case-blind systems can see the difference.
 ?S:.
 ?S:d_SCNfldbl:
 ?S: This variable conditionally defines the PERL_PRIfldbl symbol, which
 ?S: indicates that stdio has a symbol to scan long doubles.
 ?S:.
 ?S:sPRIfldbl:
 ?S: This variable, if defined, contains the string used by stdio to
 ?S: format long doubles (format 'f') for

output.

?S:.

?S:sPRIGldbl:

?S: This variable, if defined, contains the string used by stdio to

?S: format long doubles (format 'g') for output.

?S:.

?S:sPRIeldbl:

?S: This variable, if defined, contains the string used by stdio to

?S: format long doubles (format 'e') for output.

?S:.

?S:sPRIFUdbl:

?S: This variable, if defined, contains the string used by stdio to

?S: format long doubles (format 'F') for output.

?S: The 'U' in the name is to separate this from sPRIfldbl so that even

?S: case-blind systems can see the difference.

?S:.

?S:sPRIGUdbl:

?S: This variable, if defined, contains the string used by stdio to

?S: format long doubles (format 'G') for output.

?S: The 'U' in the name is to separate this from sPRIGldbl so that even

?S: case-blind systems can see the difference.

?S:.

?S:sPRIEUdbl:

?S: This variable, if defined, contains the string used by stdio to

?S: format long doubles (format 'E') for output.

?S: The 'U' in the name is to separate this from sPRIeldbl so that even

?S: case-blind

systems can see the difference.

?S:.

?S:sSCNfldbl:

?S: This variable, if defined, contains the string used by stdio to

?S: format long doubles (format 'f') for input.

?S:.

?S:d_double_has_inf:

?S: This variable conditionally defines the symbol DOUBLE_HAS_INF

?S: which indicates that the double type has an infinity.

?S:.

?S:d_double_has_nan:

?S: This variable conditionally defines the symbol DOUBLE_HAS_INF

?S: which indicates that the double type has a not-a-number.

?S:.

?S:d_double_has_negative_zero:

?S: This variable conditionally defines the symbol DOUBLE_HAS_NEGATIVE_ZERO

?S: which indicates that the double type has a negative zero.

?S:.

?S:d_double_has_subnormals:

?S: This variable conditionally defines the symbol DOUBLE_HAS_SUBNORMALS

?S: which indicates that the double type has subnormals (denormals).

?S:.

?S:d_double_style_cray:

?S: This variable conditionally defines the symbol DOUBLE_STYLE_CRAY

?S: which indicates that the double is the 64-bit CRAY mainframe format.

?S:.

?S:d_double_style_ibm:

?S: This variable conditionally defines the symbol DOUBLE_STYLE_IBM,

?S: which indicates that the double is the 64-bit IBM mainframe format.

?S:.

?S:d_double_style_ieee:

?S: This variable conditionally defines the symbol DOUBLE_STYLE_IEEE,

?S: which indicates that the double is the 64-bit IEEE 754.

?S:.

?S:d_double_style_vax:

?S: This variable conditionally defines the symbol DOUBLE_STYLE_VAX,

?S: which indicates that the double is the 64-bit VAX format D or G.

?S:.

?C:PERL_PRIldbl:

?C: This symbol, if defined, contains the string used by stdio to

?C: format long doubles (format 'f') for output.

?C:.

?C:PERL_PRIGldbl:

?C: This symbol, if defined, contains the string used by stdio to

?C: format long doubles (format 'g') for output.

?C:.

?C:PERL_PRIeldbl:

?C: This symbol, if defined, contains the string used by stdio to

?C: format long doubles (format 'e') for output.

?C:.

?C:PERL_PRIFldbl:

?C: This symbol, if defined, contains the string used by stdio to

?C: format long doubles (format 'f') for output.

?C:.

?C:PERL_PRIGldbl:

?C: This symbol, if defined, contains the string used by stdio to

?C: format long doubles (format 'g') for output.

?C:.

?C:PERL_PRIeldbl:

?C: This symbol, if defined, contains the string used by stdio to

?C: format long doubles (format 'e') for output.

?C:.

?C:PERL_SCNfldbl:

?C: This symbol, if defined, contains the string used by stdio to

?C: format long doubles (format 'f') for input.

?C:.

?C:DOUBLEKIND:

?C: DOUBLEKIND will be one of
?C: DOUBLE_IS_IEEE_754_32_BIT_LITTLE_ENDIAN
?C: DOUBLE_IS_IEEE_754_32_BIT_BIG_ENDIAN
?C: DOUBLE_IS_IEEE_754_64_BIT_LITTLE_ENDIAN
?C: DOUBLE_IS_IEEE_754_64_BIT_BIG_ENDIAN
?C: DOUBLE_IS_IEEE_754_128_BIT_LITTLE_ENDIAN
?C: DOUBLE_IS_IEEE_754_128_BIT_BIG_ENDIAN
?C: DOUBLE_IS_IEEE_754_64_BIT_MIXED_ENDIAN_LE_BE
?C: DOUBLE_IS_IEEE_754_64_BIT_MIXED_ENDIAN_BE_LE
?C: DOUBLE_IS_VAX_F_FLOAT
?C: DOUBLE_IS_VAX_D_FLOAT
?C: DOUBLE_IS_VAX_G_FLOAT
?C: DOUBLE_IS_IBM_SINGLE_32_BIT
?C: DOUBLE_IS_IBM_DOUBLE_64_BIT
?C: DOUBLE_IS_CRAY_SINGLE_64_BIT
?C: DOUBLE_IS_UNKNOWN_FORMAT
?C:.
?C:DOUBLE_HAS_INF:
?C: This
symbol, if defined, indicates that the double has
?C: the infinity.
?C:.
?C:DOUBLE_HAS_NAN:
?C: This symbol, if defined, indicates that the double has
?C: the not-a-number.
?C:.
?C:DOUBLE_HAS_NEGATIVE_ZERO:
?C: This symbol, if defined, indicates that the double has
?C: the negative_zero.
?C:.
?C:DOUBLE_HAS_SUBNORMALS:
?C: This symbol, if defined, indicates that the double has
?C: the subnormals (denormals).
?C:.
?C:DOUBLE_STYLE_CRAY:
?C: This symbol, if defined, indicates that the double is
?C: the 64-bit CRAY mainframe format.
?C:.
?C:DOUBLE_STYLE_IBM:
?C: This symbol, if defined, indicates that the double is
?C: the 64-bit IBM mainframe format.
?C:.
?C:DOUBLE_STYLE_IEEE:
?C: This symbol, if defined, indicates that the double is
?C: the 64-bit IEEE 754.
?C:.
?C:DOUBLE_STYLE_VAX:
?C: This symbol, if defined, indicates that the double is

```

?C: the 64-bit VAX format D or G.
?C:.
?LINT:known
DOUBLE_IS_IEEE_754_32_BIT_LITTLE_ENDIAN
?LINT:known DOUBLE_IS_IEEE_754_32_BIT_BIG_ENDIAN
?LINT:known DOUBLE_IS_IEEE_754_64_BIT_LITTLE_ENDIAN
?LINT:known DOUBLE_IS_IEEE_754_64_BIT_BIG_ENDIAN
?LINT:known DOUBLE_IS_IEEE_754_128_BIT_LITTLE_ENDIAN
?LINT:known DOUBLE_IS_IEEE_754_128_BIT_BIG_ENDIAN
?LINT:known DOUBLE_IS_IEEE_754_64_BIT_MIXED_ENDIAN_LE_BE
?LINT:known DOUBLE_IS_IEEE_754_64_BIT_MIXED_ENDIAN_BE_LE
?LINT:known DOUBLE_IS_VAX_F_FLOAT
?LINT:known DOUBLE_IS_VAX_D_FLOAT
?LINT:known DOUBLE_IS_VAX_G_FLOAT
?LINT:known DOUBLE_IS_IBM_SINGLE_32_BIT
?LINT:known DOUBLE_IS_IBM_DOUBLE_64_BIT
?LINT:known DOUBLE_IS_CRAY_SINGLE_64_BIT
?LINT:known DOUBLE_IS_UNKNOWN_FORMAT
?H:#define DOUBLEKIND $doublekind /**/
?H:?DOUBLEKIND:#define DOUBLE_IS_IEEE_754_32_BIT_LITTLE_ENDIAN 1
?H:?DOUBLEKIND:#define DOUBLE_IS_IEEE_754_32_BIT_BIG_ENDIAN 2
?H:?DOUBLEKIND:#define DOUBLE_IS_IEEE_754_64_BIT_LITTLE_ENDIAN 3
?H:?DOUBLEKIND:#define DOUBLE_IS_IEEE_754_64_BIT_BIG_ENDIAN 4
?H:?DOUBLEKIND:#define DOUBLE_IS_IEEE_754_128_BIT_LITTLE_ENDIAN 5
?H:?DOUBLEKIND:#define
DOUBLE_IS_IEEE_754_128_BIT_BIG_ENDIAN 6
?H:?DOUBLEKIND:#define DOUBLE_IS_IEEE_754_64_BIT_MIXED_ENDIAN_LE_BE 7
?H:?DOUBLEKIND:#define DOUBLE_IS_IEEE_754_64_BIT_MIXED_ENDIAN_BE_LE 8
?H:?DOUBLEKIND:#define DOUBLE_IS_VAX_F_FLOAT 9
?H:?DOUBLEKIND:#define DOUBLE_IS_VAX_D_FLOAT 10
?H:?DOUBLEKIND:#define DOUBLE_IS_VAX_G_FLOAT 11
?H:?DOUBLEKIND:#define DOUBLE_IS_IBM_SINGLE_32_BIT 12
?H:?DOUBLEKIND:#define DOUBLE_IS_IBM_DOUBLE_64_BIT 13
?H:?DOUBLEKIND:#define DOUBLE_IS_CRAY_SINGLE_64_BIT 14
?H:?DOUBLEKIND:#define DOUBLE_IS_UNKNOWN_FORMAT -1
?H:#$d_PRIfldbl PERL_PRIfldbl $$PRIfldbl /**/
?H:#$d_PRIgldbl PERL_PRIgldbl $$PRIgldbl /**/
?H:#$d_PRIeldbl PERL_PRIeldbl $$PRIeldbl /**/
?H:#$d_PRIFUdbl PERL_PRIFUdbl $$PRIFUdbl /**/
?H:#$d_PRIGUdbl PERL_PRIGUdbl $$PRIGUdbl /**/
?H:#$d_PRIEUdbl PERL_PRIEUdbl $$PRIEUdbl /**/
?H:#$d_SCNfldbl PERL_SCNfldbl $$SCNfldbl /**/
?H:#$d_double_has_inf DOUBLE_HAS_INF
?H:#$d_double_has_nan DOUBLE_HAS_NAN
?H:#$d_double_has_negative_zero
DOUBLE_HAS_NEGATIVE_ZERO
?H:#$d_double_has_subnormals DOUBLE_HAS_SUBNORMALS
?H:#$d_double_style_cray DOUBLE_STYLE_CRAY

```

```

?H:#$d_double_style_ibm DOUBLE_STYLE_IBM
?H:#$d_double_style_ieee DOUBLE_STYLE_IEEE
?H:#$d_double_style_vax DOUBLE_STYLE_VAX
?H:.
?T:yyy message saveccflags
?F:!try
?LINT:change ccflags
?LINT:change uselongdouble
: Check what kind of doubles your system has
$echo "Checking the kind of doubles you have..." >&4
$cat >try.c <<EOP
#$i_stdlib I_STDLIB
#define DOUBLESIZE $doublesize
#ifdef I_STDLIB
#include <stdlib.h>
#endif
#include <stdio.h>
static const double d = -0.1;
int main() {
    unsigned const char* b = (unsigned const char*)&d;
    #if DOUBLESIZE == 4
    if (b[0] == 0xCD && b[3] == 0xBD) {
        /* IEEE 754 32-bit little-endian */
        printf("1\n");
        exit(0);
    }
    if (b[0] == 0xBD && b[3] == 0xCD) {
        /* IEEE 754 32-bit big-endian */
        printf("2\n");
        exit(0);
    }
    if (b[0] == 0xCC && b[3] == 0xCC) {
        /* VAX format F, 32-bit
        PDP-style mixed endian. */
        printf("9\n");
        exit(0);
    }
    if (b[0] == 0xC0 && b[3] == 0x9A) {
        /* IBM single 32-bit */
        printf("12\n");
        exit(0);
    }
    #endif
    #if DOUBLESIZE == 8
    if (b[0] == 0x9A && b[7] == 0xBF) {
        /* IEEE 754 64-bit little-endian */
        printf("3\n");
        exit(0);
    }

```

```

}
if (b[0] == 0xBF && b[7] == 0x9A) {
    /* IEEE 754 64-bit big-endian */
    printf("4\n");
    exit(0);
}
if (b[0] == 0x99 && b[3] == 0xBF && b[4] == 0x9A && b[7] == 0x99) {
    /* ARM mixed endian: two little-endian 32-bit floats, in big endian order:
    * 4 5 6 7 0 1 2 3 (MSB = 7, LSB = 0)
    * 99 99 b9 bf 9a 99 99 99 */
    printf("7\n");
    exit(0);
}
if (b[0] == 0x99 && b[3] == 0x9A && b[4] == 0xBF && b[7] == 0x99) {
    /* The opposite of case 7, mixed endian: two big-endian 32-bit floats,
    * in little endian order: 3 2 1 0 7 6 5 4 (MSB = 7, LSB = 0)
    * 99 99 99 9a bf b9 99 99 */
    printf("8\n");
    exit(0);
}
if (b[0] == 0xCC && b[7] == 0xCC) {
    /* VAX
    format D, 64-bit PDP-style mixed endian. */
    printf("10\n");
    exit(0);
}
if (b[0] == 0xD9 && b[7] == 0x99) {
    /* VAX format G, 64-bit PDP-style mixed endian. */
    printf("11\n");
    exit(0);
}
if (b[0] == 0xC0 && b[7] == 0x9A) {
    /* IBM double 64-bit */
    printf("13\n");
    exit(0);
}
if (b[0] == 0xBF && b[7] == 0xCD) {
    /* CRAY single 64-bit */
    printf("14\n");
    exit(0);
}
#endif
#if DOUBLESIZE == 16
if (b[0] == 0x9A && b[15] == 0xBF) {
    /* IEEE 754 128-bit little-endian */
    printf("5\n");
    exit(0);
}

```

```

if (b[0] == 0xBF && b[15] == 0x9A) {
    /* IEEE 754 128-bit big-endian */
    printf("6\n");
    exit(0);
}
#endif
/* Then there are old mainframe/miniframe formats like IBM and CRAY.
 * Whether those environments can still build Perl is debatable. */
printf("-1\n"); /* unknown */
exit(0);
}
EOP
set try
if eval $compile; then
    doublekind=`$run ./try`
else
    doublekind=-1
fi
case "$doublekind" in
1) echo "You have IEEE
    754 32-bit little endian doubles." >&4 ;;
2) echo "You have IEEE 754 32-bit big endian doubles." >&4 ;;
3) echo "You have IEEE 754 64-bit little endian doubles." >&4 ;;
4) echo "You have IEEE 754 64-bit big endian doubles." >&4 ;;
5) echo "You have IEEE 754 128-bit little endian doubles." >&4 ;;
6) echo "You have IEEE 754 128-bit big endian doubles." >&4 ;;
7) echo "You have IEEE 754 64-bit mixed endian doubles (32-bit LEs in BE)." >&4 ;;
8) echo "You have IEEE 754 64-bit mixed endian doubles (32-bit BEs in LE)." >&4 ;;
9) echo "You have VAX format F 32-bit PDP-style mixed endian doubles." >&4 ;;
10) echo "You have VAX format D 64-bit PDP-style mixed endian doubles." >&4 ;;
11) echo "You have VAX format G 64-bit PDP-style mixed endian doubles." >&4 ;;
12) echo "You have IBM short 32-bit doubles." >&4 ;;
13) echo "You have IBM long 64-bit doubles." >&4 ;;
14) echo "You have Cray single 64-bit doubles." >&4 ;;
*) echo "Cannot figure out your double. You Cyber, or something?" >&4 ;;
esac
d_double_style_ieee=$undef
d_double_style_vax=$undef
d_double_style_ibm=$undef
d_double_style_cray=$undef
case
"$doublekind" in
1|2|3|4|5|6|7|8) d_double_style_ieee=$define ;;
9|10|11) d_double_style_vax=$define ;;
12|13) d_double_style_ibm=$define ;;
14) d_double_style_cray=$define ;;
esac
case "$d_double_style_ieee" in

```

```

$define)
  d_double_has_inf=$define
  d_double_has_nan=$define
  d_double_has_negative_zero=$define
  d_double_has_subnormals=$define
  ;;
*)
  d_double_has_inf=$undef
  d_double_has_nan=$undef
  d_double_has_negative_zero=$undef
  d_double_has_subnormals=$undef
  ;;
esac
$rm_try

: Check print/scan long double stuff
echo " "

if $test X"$d_longdbl" = X"$define"; then

echo "Checking how to print long doubles..." >&4

if $test X"$sPRIfldbl" = X -a X"$doublesize" = X"$longdblsize"; then
  $cat >try.c <<'EOCP'
#include <sys/types.h>
#include <stdio.h>
int main() {
  double d = 123.456;
  printf("%.3f\n", d);
}
EOCP
set try
if eval $compile; then
  yyy=`$run
./try`
  case "$yyy" in
    123.456)
      sPRIfldbl="f"; sPRIgldbl="g"; sPRIeldbl="e";
      sPRIFUldbl="F"; sPRIGUldbl="G"; sPRIEUldbl="E";
      echo "We will use %f."
      ;;
    esac
  fi
fi

if $test X"$sPRIfldbl" = X; then
  $cat >try.c <<'EOCP'
#include <sys/types.h>

```

```

#include <stdio.h>
int main() {
    long double d = 123.456;
    printf("%.3Lf\n", d);
}
EOCP
set try
if eval $compile; then
    yyy=`$run ./try`
    case "$yyy" in
        123.456)
            sPRIfldbl="Lf"; sPRIGldbl="Lg"; sPRIeldbl="Le";
            sPRIFUldbl="LF"; sPRIGUldbl="LG"; sPRIEUldbl="LE";
            echo "We will use %Lf."
            ;;
        esac
    fi
fi

```

```

if $test X"$sPRIfldbl" = X; then
    $cat >try.c <<'EOCP'
#include <sys/types.h>
#include <stdio.h>
int main() {
    long double d = 123.456;
    printf("%.3llf\n", d);
}
EOCP
set try
if eval $compile; then
    yyy=`$run ./try`
    case "$yyy" in
        123.456)
            sPRIfldbl="llf"; sPRIGldbl="llg"; sPRIeldbl="lle";
            sPRIFUldbl="llF"; sPRIGUldbl="llG"; sPRIEUldbl="llE";
            echo "We
will use %llf."
            ;;
        esac
    fi
fi

```

```

if $test X"$sPRIfldbl" = X; then
    $cat >try.c <<'EOCP'
#include <sys/types.h>
#include <stdio.h>
int main() {
    long double d = 123.456;

```

```

printf("%.3lf\n", d);
}
EOCP
set try
if eval $compile; then
yyy=`$run ./try`
case "$yyy" in
123.456)
sPRIfdbl="lf"; sPRIGldbl="lg"; sPRIeldbl="le";
sPRIFUdbl="lF"; sPRIGUdbl="lG"; sPRIEUdbl="lE";
echo "We will use %lf."
;;
esac
fi
fi

if $test X"$sPRIfdbl" = X; then
echo "Cannot figure out how to print long doubles." >&4
else
sSCNfdbl=$sPRIfdbl # expect consistency
fi

$rm_try

fi # d_longdbl

case "$sPRIfdbl" in
") d_PRIfdbl="$sundef"; d_PRIGldbl="$sundef"; d_PRIeldbl="$sundef";
d_PRIFUdbl="$sundef"; d_PRIGUdbl="$sundef"; d_PRIEUdbl="$sundef";
d_SCNfdbl="$sundef";
;;
*) d_PRIfdbl="$sdefine"; d_PRIGldbl="$sdefine"; d_PRIeldbl="$sdefine";
d_PRIFUdbl="$sdefine"; d_PRIGUdbl="$sdefine"; d_PRIEUdbl="$sdefine";
d_SCNfdbl="$sdefine";
;;
esac

: Before committing on uselongdouble,
see whether that looks sane.
if $test "$uselongdouble" = "$sdefine"; then
message=""
echo " "
echo "Checking if your long double math functions work right..." >&4
$cat > try.c <<EOF
#include <math.h>
#include <stdio.h>
int main() {
printf("%"sPRIGldbl"n", sqrtl(logl(expl(cosl(sinl(0.0L)))))+powl(2.0L, 3.0L));

```

```

}
EOF
  case "$osname:$gccversion" in
  aix:*) saveccflags="$ccflags"
ccflags="$ccflags -qlongdouble" ;; # to avoid core dump
  esac
  set try
  if eval $compile_ok; then
    yyy=`$run ./try`
  fi
  case "$yyy" in
  3) echo "Your long double math functions are working correctly." >&4 ;;
  *) echo "Your long double math functions are broken, not using long doubles." >&4
    uselongdouble=$undef
    ;;
  esac
  $rm_try
  case "$osname:$gccversion" in
  aix:*) ccflags="$saveccflags" ;; # restore
  esac
fi

```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/perl/longdblfiio.U
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic Licence,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic Licence; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: cf_email.U,v \$

?RCS: Revision 3.0.1.1 1994/01/24 14:05:06 ram

?RCS: patch16: created

?RCS:

?RCS:

?MAKE:cf_email: cat cf_by test myhostname mydomain Oldconfig Myread

?MAKE: -pick add \$@ %<

?S:cf_email:

?S: Electronic mail address of the person who ran Configure. This can be

?S: used by units that require the user's e-mail, like MailList.U.

?S:.

```
?T:cont maildomain
?LINT:extern MAILDOMAIN
: determine the e-mail address of the user who is running us
$cat <<EOM
```

I need to get your e-mail address
in Internet format if possible, i.e.
something like user@host.domain. Please answer accurately since I have
no easy means to double check it. The default value provided below
is most probably close to reality but may not be valid from outside
your organization...

```
EOM
cont=x
while test "$cont"; do
case "$MAILDOMAIN" in
")
if $test -s /etc/mailname; then
maildomain=`$cat /etc/mailname`
else
maildomain="$myhostname$mydomain"
fi
;;
*) maildomain="$MAILDOMAIN";;
esac
case "$cf_email" in
") dflt="$cf_by@$maildomain";;
*) dflt="$cf_email";;
esac
rp='What is your e-mail address?'
./myread
cf_email="$ans"
case "$cf_email" in
*@*.*.) cont="";;
*)
rp='Address does not look like an Internet one. Use it anyway?'
case "$fastread" in
yes) dflt=y ;;
*) dflt=n ;;
esac
./myread
case "$ans" in
y*) cont="";;
*) echo " " ;;
esac
;;
esac
done
```

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/cf_email.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 2001 Jarkko Hietaniemi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 3.0.

?RCS:

?MAKE:d_dbminiproto: Hasproto i_dbm

?MAKE: -pick add \$@ %<

?S:d_dbminiproto:

?S: This variable conditionally defines the HAS_DBMINIT_PROTO symbol,

?S: which indicates to the C program that the system provides

?S: a prototype for the dbminiproto() function. Otherwise, it is

?S: up to the program to supply one.

?S:.

?C:HAS_DBMINIT_PROTO:

?C: This symbol, if defined, indicates that the system provides

?C: a prototype for the dbminiproto() function. Otherwise, it is up

?C: to the program to supply one. A good guess is

?C: extern

int dbminiproto(char *);

?C:.

?H:#\$d_dbminiproto HAS_DBMINIT_PROTO /**/

?H:.

?LINT:set d_dbminiproto

: see if prototype for dbminiproto is available

echo " "

set d_dbminiproto dbminiproto \$i_dbm dbm.h

eval \$hasproto

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_dbminiproto.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: mansrc.U 1 2006-08-24 12:32:52Z rmanfredi \$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: \$Log: mansrc.U,v \$
?RCS: Revision 3.0.1.9 1997/02/28 16:12:03 ram
?RCS: patch61: don't ask for AFS when they choose to not install pages
?RCS:
?RCS: Revision 3.0.1.8 1995/09/25 09:16:58 ram
?RCS: patch59: unit is now forced to the top of Configure, if possible
?RCS:
?RCS: Revision 3.0.1.7 1995/02/15 14:15:31 ram
?RCS: patch51: was mistakenly duplicating /usr/local/man/man1 (ADO)
?RCS: patch51: added /opt/man/man1 to the lookpath (ADO)
?RCS:
?RCS: Revision
3.0.1.6 1995/01/30 14:39:34 ram
?RCS: patch49: can now handle installation prefix changes (from WED)
?RCS:
?RCS: Revision 3.0.1.5 1995/01/11 15:32:25 ram
?RCS: patch45: can now use Loc variables since path stripping is deferred
?RCS:
?RCS: Revision 3.0.1.4 1994/08/29 16:30:38 ram
?RCS: patch32: now uses installation prefix for default setting
?RCS:
?RCS: Revision 3.0.1.3 1994/05/06 15:11:10 ram
?RCS: patch23: added lint hint, assuring that nroff is used
?RCS:
?RCS: Revision 3.0.1.2 1994/01/24 14:14:39 ram
?RCS: patch16: now uses _nroff in case user asked for portability
?RCS:
?RCS: Revision 3.0.1.1 1993/09/13 16:09:31 ram
?RCS: patch10: allows for L1 man page extension (WAD)
?RCS:
?RCS: Revision 3.0 1993/08/18 12:09:14 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:mansrc mansrcexp manext installmansrc: afs cat nroff Loc Oldconfig \
sysman spackage test Getfile Prefixit prefixexp Prefixup
?MAKE: -pick add \$@ %<
?Y:TOP
?S:mansrc:
?S: This variable
contains the name of the directory in which manual
?S: source pages are to be put. It is the responsibility of the
?S: Makefile.SH to get the value of this into the proper command.

?S: You must be prepared to do the ~name expansion yourself.

?S:.

?S:mansrcexp:

?S: This variable is the same as the mansrc variable, but is filename

?S: expanded at configuration time, for convenient use in makefiles.

?S:.

?S:installmansrc:

?S: This variable is really the same as mansrcexp, unless you are using

?S: AFS in which case it points to the read/write location whereas

?S: mansrcexp only points to the read-only access location. For extra

?S: portability, you should only use this variable within your makefiles.

?S:.

?S:manext:

?S: This variable contains the extension that the manual page should

?S: have: one of 'n', 'l', or 'L'. The Makefile must supply the 'l'.

?S: See mansrc.

?S:.

?T:lookpath

: determine where manual pages go

set mansrc mansrc none

eval \$prefixit

\$cat <<EOM

\$spackage has manual

pages available in source form.

EOM

case "\$nroff" in

nroff)

echo "However, you don't have nroff, so they're probably useless to you."

case "\$mansrc" in

") mansrc="none";;

esac;;

esac

echo "If you don't want the manual sources installed, answer 'none'."

case "\$mansrc" in

")

lookpath="\$prefixexp/share/man/man1 \$prefixexp/man/man1"

lookpath="\$lookpath \$prefixexp/man/u_man/man1 \$prefixexp/man/l_man/man1"

lookpath="\$lookpath /usr/local/man/man1 /opt/man/man1 /usr/man/man1"

lookpath="\$lookpath /usr/share/man/man1 /usr/local/share/man/man1"

lookpath="\$lookpath /usr/man/local/man1 /usr/man/l_man/man1"

lookpath="\$lookpath /usr/local/man/u_man/man1 /usr/local/man/l_man/man1"

lookpath="\$lookpath /usr/man/man.L"

mansrc=`./loc . \$prefixexp/man/man1 \$lookpath`

if \$test -d "\$mansrc"; then

 dflt="\$mansrc"

else

 dflt="\$sysman"

```

fi
set dflt
eval $prefixup
;;
') dflt=none;;
*) dflt="$mansrc"
;;
esac
echo " "
fn=dn~
rp='Where do the manual pages (source) go?'
./getfile
if test
"X$mansrcexp" != "X$ansexp"; then
installmansrc="
fi
mansrc="$ans"
mansrcexp="$ansexp"
case "$mansrc" in
") mansrc=' '
installmansrc="";;
esac
if $afs && $test "$mansrc"; then
$cat <<EOM

```

Since you are running AFS, I need to distinguish the directory in which manual pages reside from the directory in which they are installed (and from which they are presumably copied to the former directory by occult means).

```

EOM
case "$installmansrc" in
") dflt=`echo $mansrcexp | sed 's#^/afs/#/afs/#'`;
*) dflt="$installmansrc";;
esac
fn=de~
rp='Where will man pages be installed?'
./getfile
installmansrc="$ans"
else
installmansrc="$mansrcexp"
fi

case "$mansrc" in
') manext='0';;
*l) manext=l;;
*n) manext=n;;
*o) manext=l;;
*p) manext=n;;

```

```
*C) manext=C;;
*L) manext=L;;
*L1) manext=L1;;
*) manext=1;;
esac
```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/mansrc.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: d_pread.U 1 2006-08-24 12:32:52Z rmanfredi $
```

```
?RCS:
```

```
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
```

```
?RCS:
```

```
?RCS: You may redistribute only under the terms of the Artistic Licence,
```

```
?RCS: as specified in the README file that comes with the distribution.
```

```
?RCS: You may reuse parts of this distribution only within the terms of
```

```
?RCS: that same Artistic Licence; a copy of which may be found at the root
```

```
?RCS: of the source tree for dist 4.0.
```

```
?RCS:
```

```
?RCS: $Log: d_pread.U,v $
```

```
?RCS:
```

```
?MAKE:d_pread: Inlibc
```

```
?MAKE: -pick add $@ %<
```

```
?S:d_pread:
```

```
?S: This variable conditionally defines the HAS_PREAD symbol, which
```

```
?S: indicates to the C program that the pread() routine is available.
```

```
?S:.
```

```
?C:HAS_PREAD :
```

```
?C: This symbol, if defined, indicates that the pread routine is
```

```
?C: available to perform reads on a file descriptor at a given offset.
```

```
?C:.
```

```
?H:#$d_pread HAS_PREAD /**/
```

```
?H:.
```

```
?LINT:set d_pread
```

```
: see if pread exists
```

```
set
```

```
pread d_pread
```

```
eval $inlibc
```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/d_pread.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id$
```

```
?RCS:
```

?RCS: Copyright (c) 2000 Jarkko Hietaniemi
?RCS:
?RCS: You may distribute under the terms of either the GNU General Public
?RCS: License or the Artistic License, as specified in the README file.
?RCS:
?MAKE:d_getitimer: Inlibc
?MAKE: -pick add \$@ %<
?S:d_getitimer:
?S: This variable conditionally defines the HAS_GETITIMER symbol, which
?S: indicates to the C program that the getitimer() routine is available.
?S:.
?C:HAS_GETITIMER:
?C: This symbol, if defined, indicates that the getitimer routine is
?C: available to return interval timers.
?C:.
?H:#\$d_getitimer HAS_GETITIMER /**/
?H:.
?LINT:set d_getitimer
: see if getitimer exists
set getitimer d_getitimer
eval \$inlibc

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_getitimer.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: \$Log: fpostype.U,v \$
?RCS: Revision 3.0.1.2 1994/08/29 16:20:52 ram
?RCS: patch32: now uses new Typedef unit to compute type information
?RCS:
?RCS: Revision 3.0.1.1 1994/06/20 06:59:59 ram
?RCS: patch30: created
?RCS:
?MAKE:fpostype: Myread Typedef
?MAKE: -pick add \$@ %<
?S:fpostype:
?S: This variable defines Fpos_t to be something like fpost_t, long,

?S: uint, or whatever type is used to declare file positions in libc.

?S:.

?C:Fpos_t:

?C: This symbol holds the type used to declare file positions in libc.

?C: It can be fpos_t, long, uint, etc... It may be necessary to include

?C: <sys/types.h> to get any typedef'ed information.

?C:.

?H:#define Fpos_t \$fpostype /* File position type */

?H:.

: see what type file positions are declared as in the library

set fpos_t fpostype long stdio.h sys/types.h

eval \$typedef

echo " "

dflt="\$fpostype"

rp="What is the type for file position used by fsetpos()?"

./myread

fpostype="\$ans"

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/fpostype.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_setnent.U,v 3.0 1993/08/18 12:06:09 ram Exp \$

?RCS:

?RCS: Copyright (c) 1991-1993, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 3.0.

?RCS:

?RCS: \$Log: d_setnent.U,v \$

?RCS: Revision 3.0 1993/08/18 12:06:09 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?MAKE:d_setnent: Inlibc

?MAKE: -pick add \$@ %<

?S:d_setnent:

?S: This variable conditionally defines HAS_SETNETENT if setnentent() is

?S: available.

?S:.

?C:HAS_SETNETENT:

?C: This symbol, if defined, indicates that the setnentent() routine is

?C: available.

?C:.

?H:#\$d_setnent HAS_SETNETENT /**/

?H:.

?LINT:set d_setnent

: see if setnent exists

set

setnent d_setnent

eval \$inlibc

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/modified/d_setnent.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_flexfnam.U 1 2006-08-24 12:32:52Z rmanfredi \$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: d_flexfnam.U,v \$

?RCS: Revision 3.0 1993/08/18 12:06:04 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?MAKE:d_flexfnam: cat rm test Setvar

?MAKE: -pick add \$@ %<

?S:d_flexfnam:

?S: This variable conditionally defines the FLEXFILENAMES symbol, which

?S: indicates that the system supports filenames longer than 14 characters.

?S:.

?C:FLEXFILENAMES:

?C: This symbol, if defined, indicates that the system supports filenames

?C: longer than 14

characters.

?C:.

?H:#\$d_flexfnam FLEXFILENAMES /**/

?H:.

?T:first

?LINT:set d_flexfnam

: see if we can have long filenames

echo " "

?X:

?X: We have to test in both /tmp and . because of NFS (remote server may allow

?X: long filenames while the local filesystem cannot support them). If at least

?X: one of those file systems cannot support long filenames, then we assume the

```

?X: whole system can't.
?X:
first=123456789abcdef
$rm -f $first
if (echo hi >$first) 2>/dev/null; then
if $test -f 123456789abcde; then
echo 'You cannot have filenames longer than 14 characters. Sigh.'>&4
val="$undef"
else
echo 'You can have filenames longer than 14 characters.'>&4
val="$define"
fi
else
$cat <<'EOM'
You can't have filenames longer than 14 chars.
You can't even think about them!
EOM
val="$undef"
fi
set d_flexfnam
eval $setvar
$rm -rf 123456789abcde*

```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/modified/d_flexfnam.U
```

No license file was found, but licenses were detected in source scan.

```

?RCS: $Id: modetype.U,v 3.0.1.1 1994/10/29 16:25:07 ram Exp $
?RCS:
?RCS: Copyright (c) 1991-1993, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 3.0.
?RCS:
?RCS: Original Author: Andy Dougherty <doughera@lafcol.lafayette.edu>
?RCS:
?RCS: $Log: modetype.U,v $
?RCS: Revision 3.0.1.1 1994/10/29 16:25:07 ram
?RCS: patch36: created by ADO
?RCS:
?MAKE:modetype: Myread Typedef
?MAKE: -pick add $@ %<
?S:modetype:
?S: This variable defines modetype to be something like mode_t,

```

?S: int, unsigned short, or whatever type is used to declare file
 ?S: modes for system calls.
 ?S:.
 ?C:Mode_t:
 ?C: This symbol holds the type used to declare
 file modes
 ?C: for systems calls. It is usually mode_t, but may be
 ?C: int or unsigned short. It may be necessary to include <sys/types.h>
 ?C: to get any typedef'ed information.
 ?C:.
 ?H:#define Mode_t \$modetype /* file mode parameter for system calls */
 ?H:.
 ?LINT:set modetype
 : see what type is used for mode_t
 rp="What is the type used for file modes for system calls (e.g. fchmod())?"
 set mode_t modetype int stdio.h sys/types.h
 eval \$typedef_ask

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/typedefs/modetype.U

No license file was found, but licenses were detected in source scan.

?RCS: Copyright (c) 1996, Chip Salzenberg
 ?RCS:
 ?RCS: You may distribute under the terms of either the GNU General Public
 ?RCS: License or the Artistic License, as specified in the README file.
 ?RCS:
 ?MAKE:bincompat3 d_bincompat3: Oldconfig Myread Setvar cat \
 patchlevel subversion
 ?MAKE: -pick add \$@ %<
 ?Y:TOP
 ?S:bincompat3:
 ?S: This variable contains y if Perl 5.004 should be binary-compatible
 ?S: with Perl 5.003.
 ?S:.
 ?S:d_bincompat3:
 ?S: This variable conditionally defines BINCOMPAT3 so that embed.h
 ?S: can take special action if Perl 5.004 should be binary-compatible
 ?S: with Perl 5.003. This is impossible for 5.004_50 and later, so
 ?S: it is always \$undef for those versions.
 ?S:.
 ?C:BINCOMPAT3:
 ?C: This symbol, if defined, indicates that Perl 5.004 should be
 ?C: binary-compatible with Perl 5.003. This is impossible for
 ?C: 5.004_50 and later, so it is always undefined for those versions.
 ?C:.
 ?H:#\$d_bincompat3

```
BINCOMPAT3 /**/
```

```
?H:.
```

```
: Binary compatibility with 5.003 is not possible with 5.004_50 and later.
```

```
if test $patchlevel -gt 4 -o $subversion -ge 50; then
```

```
    d_bincompat3=$undef
```

```
else
```

```
$cat <<EOM
```

Perl 5.004 can be compiled for binary compatibility with 5.003.

If you decide to do so, you will be able to continue using any extensions that were compiled for Perl 5.003. However, binary compatibility forces Perl to expose some of its internal symbols in the same way that 5.003 did. So you may have symbol conflicts if you embed a binary-compatible Perl in other programs.

```
EOM
```

```
case "$d_bincompat3" in
```

```
"$undef") dflt=n ;;
```

```
*) dflt=y ;;
```

```
esac
```

```
rp='Binary compatibility with Perl 5.003?'
```

```
. ./myread
```

```
case "$ans" in
```

```
y*) val="$define" ;;
```

```
*) val="$undef" ;;
```

```
esac
```

```
set d_bincompat3
```

```
eval $setvar
```

```
case "$d_bincompat3" in
```

```
"$define") bincompat3=y ;;
```

```
*) bincompat3=n ;;
```

```
esac
```

```
fi
```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/bincompat3.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id$
```

```
?RCS:
```

```
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
```

```
?RCS:
```

```
?RCS: You may redistribute only under the terms of the Artistic License,
```

```
?RCS: as specified in the README file that comes with the distribution.
```

```
?RCS: You may reuse parts of this distribution only within the terms of
```

```
?RCS: that same Artistic License; a copy of which may be found at the root
```

```
?RCS: of the source tree for dist 4.0.
```

?RCS:
?RCS: \$Log: d_fd_set.U,v \$
?RCS: Revision 3.0.1.3 1997/02/28 15:33:16 ram
?RCS: patch61: added ?F: metalint hint
?RCS:
?RCS: Revision 3.0.1.2 1994/06/20 06:57:23 ram
?RCS: patch30: extended scope for fd_set checks (ADO)
?RCS:
?RCS: Revision 3.0.1.1 1994/01/24 14:06:27 ram
?RCS: patch16: comments for HAS_FD_* symbols were not consistent
?RCS:
?RCS: Revision 3.0 1993/08/18 12:06:02 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:d_fd_set d_fd_macros d_fds_bits: cat +cc +ccflags rm Oldconfig
\
d_socket i_systime i_sysselect i_syssock
?MAKE: -pick add \$@ %<
?S:d_fd_set:
?S: This variable contains the eventual value of the HAS_FD_SET symbol,
?S: which indicates if your C compiler knows about the fd_set typedef.
?S:.
?S:d_fd_macros:
?S: This variable contains the eventual value of the HAS_FD_MACROS symbol,
?S: which indicates if your C compiler knows about the macros which
?S: manipulate an fd_set.
?S:.
?S:d_fds_bits:
?S: This variable contains the eventual value of the HAS_FDS_BITS symbol,
?S: which indicates if your fd_set typedef contains the fds_bits member.
?S: If you have an fd_set typedef, but the dweebs who installed it did
?S: a half-fast job and neglected to provide the macros to manipulate
?S: an fd_set, HAS_FDS_BITS will let us know how to fix the gaffe.
?S:.
?C:HAS_FD_SET:
?C: This symbol, when defined, indicates presence of the fd_set typedef
?C: in <sys/types.h>
?C:.
?C:HAS_FD_MACROS:
?C: This symbol, when defined, indicates presence of the macros used
to
?C: manipulate an fd_set.
?C:.
?C:HAS_FDS_BITS:
?C: This symbol, when defined, indicates presence of the fds_bits member in
?C: fd_set. This knowledge is useful if fd_set is available but the macros
?C: aren't.
?C:.

```
?H:#$d_fd_set HAS_FD_SET /**/
?H:#$d_fd_macros HAS_FD_MACROS /**/
?H:#$d_fds_bits HAS_FDS_BITS /**/
?H:.
?F:!fd_set
: check for fd_set items
$cat <<EOM
```

Checking to see how well your C compiler handles fd_set and friends ...

EOM

?X: The FD_SET macros can be in strange places. On some SysV-based

?X: systems, they are in <sys/bsdtypes.h>, which is included (perhaps)

?X: by <sys/socket.h>. We won't force people to include

?X: <sys/bsdtypes.h> because it might introduce other

?X: incompatibilities.

\$cat >fd_set.c <<EOCP

```
#$i_systime I_SYS_TIME
```

```
#$i_sysselect I_SYS_SELECT
```

```
#$d_socket HAS_SOCKET
```

```
#$i_syssock I_SYS_SOCKET
```

```
#include <sys/types.h>
```

```
#ifdef HAS_SOCKET
```

```
#ifdef I_SYS_SOCKET
```

```
#include <sys/socket.h> /* Might include <sys/bsdtypes.h> */
```

```
#endif
```

```
#endif
```

```
#ifdef I_SYS_TIME
```

```
#include
```

```
<sys/time.h>
```

```
#endif
```

```
#ifdef I_SYS_SELECT
```

```
#include <sys/select.h>
```

```
#endif
```

```
int main() {
```

```
fd_set fds;
```

```
#ifdef TRYBITS
```

```
if(fds.fds_bits);
```

```
#endif
```

```
#if defined(FD_SET) && defined(FD_CLR) && defined(FD_ISSET) && defined(FD_ZERO)
```

```
exit(0);
```

```
#else
```

```
exit(1);
```

```
#endif
```

```
}
```

```
EOCP
```

```
if $cc $ccflags -DTRYBITS -o fd_set fd_set.c >fd_set.out 2>&1 ; then
```

```

d_fds_bits="$define"
d_fd_set="$define"
echo "Well, your system knows about the normal fd_set typedef..." >&4
if ./fd_set; then
  echo "and you have the normal fd_set macros (just as I'd expect)." >&4
  d_fd_macros="$define"
else
  $cat >&4 <<'EOM'
but not the normal fd_set macros! Gaaack! I'll have to cover for you.
EOM
  d_fd_macros="$undef"
fi
else
  $cat <<'EOM'
Hmm, your compiler has some difficulty with fd_set. Checking further...
EOM
if $cc $ccflags -o fd_set fd_set.c >fd_set.out 2>&1 ; then
  d_fds_bits="$undef"
  d_fd_set="$define"
  echo "Well, your system has some sort of fd_set available..." >&4
  if ./fd_set; then
    echo "and you have the
normal fd_set macros." >&4
    d_fd_macros="$define"
  else
    $cat <<'EOM'
but not the normal fd_set macros! Gross! More work for me...
EOM
    d_fd_macros="$undef"
  fi
else
  echo "Well, you got zip. That's OK, I can roll my own fd_set stuff." >&4
  d_fd_set="$undef"
  d_fds_bits="$undef"
  d_fd_macros="$undef"
fi
fi
$rm -f fd_set*

```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/d_fd_set.U
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: Options.U 1 2006-08-24 12:32:52Z rmanfredi \$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: \$Log: Options.U,v \$
?RCS: Revision 3.0.1.7 1997/02/28 15:08:15 ram
?RCS: patch61: optdef.sh now starts with a "startsh"
?RCS: patch61: moved some code from Head.U
?RCS:
?RCS: Revision 3.0.1.6 1995/09/25 09:14:46 ram
?RCS: patch59: protected option parsing code against 'echo -*' option failure
?RCS:
?RCS: Revision 3.0.1.5 1995/05/12 12:04:52 ram
?RCS: patch54: added -K option for experts
?RCS:
?RCS: Revision 3.0.1.4 1995/01/30 14:27:52 ram
?RCS:
patch49: this unit now exports file optdef.sh, not a variable
?RCS:
?RCS: Revision 3.0.1.3 1995/01/11 15:19:00 ram
?RCS: patch45: new -O option allowing -D and -U to override config.sh settings
?RCS: patch45: file optdef.sh is no longer removed after sourcing
?RCS:
?RCS: Revision 3.0.1.2 1994/10/29 15:58:06 ram
?RCS: patch36: ensure option definition file is removed before appending
?RCS: patch36: protect variable definitions with spaces in them
?RCS:
?RCS: Revision 3.0.1.1 1994/06/20 06:55:44 ram
?RCS: patch30: now uses new me symbol to tag error messages
?RCS: patch30: new -D and -U options to define/undef symbols (JHI)
?RCS:
?RCS: Revision 3.0 1993/08/18 12:05:14 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?X:
?X: Command line parsing. It is really important that the variables used here
?X: be not listed in the MAKE line, or they will be saved in config.sh and
?X: loading this file to fetch default answers would clobber the values set
?X: herein.
?X:
?MAKE:Options:
startsh
?MAKE: -pick wipe \$@ %<
?V:reuseval alldone error realsilent silent extractsh fastread \
knowitall: config_sh
?T:arg argn symbol config_arg0 config_args config_argc xxx yyy zzz uuu

```

?T:args_exp args_sep arg_exp cflags
?F:!Configure
?F:./optdef.sh ./cmdline.opt ./posthint.sh ./cmdl.opt
: Save command line options in file UU/cmdline.opt for later use in
: generating config.sh.
?X: This temporary file will be read by Oldsym.U. I used a temporary
?X: file to preserve all sorts of potential command line quotes and
?X: also because we don't know in advance how many variables we'll
?X: need, so I can't actually declare them on the MAKE line.
?X: The config_args variable won't be quite correct if Configure is
?X: fed something like ./Configure -Dcc="gcc -B/usr/ccs/bin/"
?X: since the quotes are gone by the time we see them. You'd have to
?X: reconstruct the command line from the config_arg? lines, but since
?X: I don't imagine anyone actually having to do that, I'm not going
?X:
to worry too much.
cat > cmdline.opt <<EOSSH
: Configure command line arguments.
config_arg0='$0'
config_args='$*'
config_argc=$#
EOSSH
argn=1
args_exp=""
args_sep=""
for arg in "$@"; do
cat >>cmdline.opt <<EOSSH
config_arg$argn='$arg'
EOSSH
?X: Extreme backslashitis: replace each ' by """"
cat <<EOC | sed -e "s/'/""""/g" > cmdl.opt
$arg
EOC
arg_exp=`cat cmdl.opt`
args_exp="$args_exp$args_sep'$arg_exp'"
argn=`expr $argn + 1`
args_sep=' '
done
?X: args_exp is good for restarting self: eval "set X $args_exp"; shift; $0 "$@"
?X: used by hints/os2.sh in Perl, for instance
rm -f cmdl.opt

: produce awk script to parse command line options
cat >options.awk <<'EOF'
BEGIN {
optstr = "A:dD:eEf:hKOrsSU:V"; # getopt-style specification

len = length(optstr);

```

```

for (i = 1; i <= len; i++) {
  c = substr(optstr, i, 1);
?X: some older awk's do not have the C ?: construct
  if (i < len) a = substr(optstr, i + 1, 1); else a = "";
  if (a == ":") {
    arg[c] = 1;
    i++;
  }
  opt[c]
= 1;
}
}
{
  expect = 0;
  str = $0;
  if (substr(str, 1, 1) != "-") {
    printf("%s\n", str);
    next;
  }
  len = length($0);
  for (i = 2; i <= len; i++) {
    c = substr(str, i, 1);
    if (!opt[c]) {
      printf("-%s\n", substr(str, i));
      next;
    }
    printf("-%s\n", c);
    if (arg[c]) {
      if (i < len)
        printf("%s\n", substr(str, i + 1));
      else
        expect = 1;
      next;
    }
  }
}
END {
  if (expect)
    print "?";
}
EOF

```

: process the command line options

?X: Use "\$@" to keep arguments with spaces in them from being split apart.

?X: For the same reason, awk will output quoted arguments and the final eval

?X: removes them and sets a proper \$* array. An 'X' is prepended to each

?X: argument before being fed to echo to guard against 'echo -x', where -x

?X: would be understood as an echo option! It is removed before feeding awk.

```
set X `for arg in "$@"; do echo "X$arg"; done |
sed -e s/X// | awk -f options.awk`
eval "set $*"
shift
rm -f options.awk
```

```
: set up default values
fastread=""
reuseval=false
config_sh=""
alldone=""
error=""
silent=""
extractsh=""
knowitall=""
rm
-f optdef.sh posthint.sh
cat >optdef.sh <<EOS
$startsh
EOS
```

?X:

?X: Given that we now have the possibility to execute Configure remotely

?X: thanks to the new src.U support, we have to face the possibility

?X: of having to ask where the source lie, which means we need the Myread.U

?X: stuff and possibly other things that might echo something on the

?X: screen...

?X:

?X: That's not pretty, and might be confusing in 99% of the time. So...

?X: We introduce a new realsilent variable which is set when -s is given,

?X: and we force silent=true if -S is supplied. The Extractall.U unit

?X: will then undo the >&4 redirection based on the value of the

?X: realsilent variable... -- RAM, 18/93/96

?X:

```
: option parsing
```

```
while test $# -gt 0; do
case "$1" in
-d) shift; fastread=yes;;
-e) shift; alldone=cont;;
-f)
shift
cd ..
if test -r "$1"; then
config_sh="$1"
else
echo "$me: cannot read config file $1."
```

```

>&2
  error=true
fi
cd UU
shift;;
--help\
-h) shift; error=true;;
-r) shift; reuseval=true;;
-s) shift; silent=true; realsilent=true;;
-E) shift; alldone=exit;;
-K) shift; knowitall=true;;
-O) shift;;
-S) shift; silent=true; extractsh=true;;
-D)
  shift
  case "$1" in
  *)
    echo "$me: use '-U symbol=', not '-D symbol='." >&2
    echo "$me: ignoring -D $1" >&2
    ;;
  *=*) echo "$1" | \
    sed -e "s//^\""/g" -e "s/=(.*)/=\\1/" >> optdef.sh;;
  *) echo "$1='define'" >> optdef.sh;;
  esac
  shift
  ;;
-U)
  shift
  case "$1" in
  *) echo "$1" >> optdef.sh;;
  *=*)
    echo "$me: use '-D symbol=val', not '-U symbol=val'." >&2
    echo "$me: ignoring -U $1" >&2
    ;;
  *) echo "$1='undef'" >> optdef.sh;;
  esac
  shift
  ;;
-A)
  shift
  xxx=""
  yyy="$1"
  zzz=""
  uuu=undef
  case "$yyy" in
  *=*) zzz=`echo "$yyy"|sed 's!=.*!!'^
    case "$zzz" in
    *:*) zzz="" ;;

```

```

*) xxx=append

zzz=" `echo "$yyy"|sed 's!^[^=]*=!'^
yyy=`echo "$yyy"|sed 's!=.*!!'^ ;;
esac
;;
esac
case "$xxx" in
") case "$yyy" in
*:*) xxx=`echo "$yyy"|sed 's!:.*!!'^
yyy=`echo "$yyy"|sed 's!^[^:]*!!'^
zzz=`echo "$yyy"|sed 's!^[^=]*=!'^
yyy=`echo "$yyy"|sed 's!=.*!!'^ ;;
*) xxx=`echo "$yyy"|sed 's!:.*!!'^
yyy=`echo "$yyy"|sed 's!^[^:]*!!'^ ;;
esac
;;
esac
case "$xxx" in
append)
echo "$yyy=\\"${yyy}$zzz\""" >> posthint.sh ;;
clear)
echo "$yyy="" >> posthint.sh ;;
define)
case "$zzz" in
") zzz=define ;;
esac
echo "$yyy='$zzz'" >> posthint.sh ;;
eval)
echo "eval \\"$yyy=$zzz\""" >> posthint.sh ;;
prepend)
echo "$yyy=\\"$zzz\${yyy}\""" >> posthint.sh ;;
undef)

case "$zzz" in
") zzz="$uuu" ;;
esac
echo "$yyy=$zzz" >> posthint.sh ;;
*) echo "$me: unknown -A command '$xxx', ignoring -A $1" >&2 ;;
esac
shift
;;
-V) echo "$me generated by metaconfig <VERSION> PL<PATCHLEVEL>." >&2
exit 0;;
--) break;;
-*) echo "$me: unknown option $1" >&2; shift; error=true;;
*) break;;
esac

```

done

```
case "$error" in
true)
```

```
cat >&2 <<EOM
```

```
Usage: $me [-dehrsEKOSV] [-f config.sh] [-D symbol] [-D symbol=value]
        [-U symbol] [-U symbol=] [-A command:symbol...]
```

-d : use defaults for all answers.

-e : go on without questioning past the production of config.sh.

-f : specify an alternate default configuration file.

-h : print this help message and exit (with an error status).

-r : reuse C symbols value if possible (skips costly nm extraction).

-s : silent mode, only echoes questions and essential information.

-D : define symbol to have some value:

 -D symbol symbol gets the value

'define'

 -D symbol=value symbol gets the value 'value'

common used examples (see INSTALL for more info):

 -Duse64bitint use 64bit integers

 -Duse64bitall use 64bit integers and pointers

 -Dusetthreads use thread support

 -Dinc_version_list=none do not include older perl trees in @INC

 -DEBUGGING=none DEBUGGING options

 -Dcc=gcc choose your compiler

 -Dprefix=/opt/perl5 choose your destination

-E : stop at the end of questions, after having produced config.sh.

-K : do not use unless you know what you are doing.

-O : ignored for backward compatibility

-S : perform variable substitutions on all .SH files (can mix with -f)

-U : undefine symbol:

 -U symbol symbol gets the value 'undef'

 -U symbol= symbol gets completely empty

e.g.: -Uversiononly

-A : manipulate symbol after the platform specific hints have been applied:

 -A append:symbol=value append value to symbol

 -A symbol=value like append:, but with a separating space

 -A define:symbol=value define symbol to have value

 -A clear:symbol define symbol to be "

 -A define:symbol define symbol to be 'define'

 -A eval:symbol=value define symbol to be eval of value

 -A prepend:symbol=value prepend value to symbol

 -A undef:symbol define symbol to be 'undef'

 -A undef:symbol= define symbol to be "

e.g.: -A prepend:libswanted='cl pthread '

 -A ccflags=-DSOME_MACRO

-V : print version number and exit (with a zero status).

```
EOM
```

```
exit 1
```

```
;;  
esac
```

?X:

?X: Unless they specified either -S or both -d and -e/E, make sure we're

?X: running interactively, i.e. attached to a terminal. Moved from Head.U to

?X: be able to handle batch configurations...

?X:

?X: We have to hardwire the Configure name and cannot use \$me,
since if they

?X: said 'sh <Configure', then \$me is 'sh'...

?X:

: Sanity checks

```
case "$fastread$alldone" in
```

```
yescont|yesexit) ;;
```

```
*)
```

```
case "$extractsh" in
```

```
true) ;;
```

```
*)
```

```
if test ! -t 0; then
```

```
  echo "Say 'sh Configure', not 'sh <Configure'"
```

```
  exit 1
```

```
fi
```

```
;;
```

```
esac
```

```
;;
```

```
esac
```

?X: In silent mode, the standard output is closed. Questions are asked by

?X: outputting on file descriptor #4, which is the original stdout descriptor.

?X: This filters out all the "junk", since all the needed information is written

?X: on #4. Note that ksh will not let us redirect output if the file descriptor

?X: has not be defined yet, unlike sh, hence the following line...--RAM.

```
exec 4>&1
```

```
case "$silent" in
```

```
true) exec 1>/dev/null;;
```

```
esac
```

: run the defines and the undefines, if any, but leave the file out there...

```
touch optdef.sh
```

?X: -q is POSIX

?X: It does not work in SysV (solaris) or old BSD greps.

```
grep '\| optdef.sh >/dev/null 2>&1
```

```
if test $? = 0; then
```

```
  echo "Configure does not support \| in -D arguments"
```

```
  exit 1
```

```
fi
```

```
./optdef.sh
```

: create the posthint manipulation script and leave the file out there...

?X: this file will be perused by Oldconfig.U

touch posthint.sh

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/modified/Options.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_setservent_r.U,v 0RCS:

?RCS: Copyright (c) 2002,2003 Jarkko Hietaniemi

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?RCS: Generated by the reentr.pl from the Perl 5.8 distribution.

?RCS:

?MAKE:d_setservent_r setservent_r_proto: Inlibc Protochk Hasproto i_systypes \
 usethreads i_netdb extern_C

?MAKE: -pick add \$@ %<

?S:d_setservent_r:

?S: This variable conditionally defines the HAS_SETSERVENT_R symbol,

?S: which indicates to the C program that the setservent_r()

?S: routine is available.

?S:.

?S:setservent_r_proto:

?S: This variable encodes the prototype of setservent_r.

?S: It is zero if d_setservent_r is undef, and one of the

?S: REENTRANT_PROTO_T_ABC macros of reentr.h if d_setservent_r

?S: is defined.

?S:.

?C:HAS_SETSERVENT_R:

?C: This symbol, if defined, indicates that the setservent_r routine

?C: is

available to setservent re-entrantly.

?C:.

?C:SETSERVENT_R_PROTO:

?C: This symbol encodes the prototype of setservent_r.

?C: It is zero if d_setservent_r is undef, and one of the

?C: REENTRANT_PROTO_T_ABC macros of reentr.h if d_setservent_r

?C: is defined.

?C:.

?H:#\$d_setservent_r HAS_SETSERVENT_R /**/

?H:#define SETSERVENT_R_PROTO \$setservent_r_proto /**/

?H:.

?T:try hdrs d_setservent_r_proto

: see if setservent_r exists

set setservent_r d_setservent_r

```

eval $inlibc
case "$d_setservent_r" in
"$define")
hdrs="$i_systypes sys/types.h define stdio.h $i_netdb netdb.h"
case "$d_setservent_r_proto:$usetthreads" in
":define") d_setservent_r_proto=define
set d_setservent_r_proto setservent_r $hdrs
eval $hasproto ;;
*) ;;
esac
case "$d_setservent_r_proto" in
define)
case "$setservent_r_proto" in
"|0) try='int setservent_r(int, struct servent_data*);'
./protochk "$extern_C $try" $hdrs && setservent_r_proto=I_ID ;;
esac
case "$setservent_r_proto" in
"|0) try='void
setservent_r(int, struct servent_data*);'
./protochk "$extern_C $try" $hdrs && setservent_r_proto=V_ID ;;
esac
case "$setservent_r_proto" in
"|0) d_setservent_r=undef
setservent_r_proto=0
echo "Disabling setservent_r, cannot determine prototype." >&4 ;;
* ) case "$setservent_r_proto" in
REENTRANT_PROTO*) ;;
*) setservent_r_proto="REENTRANT_PROTO_$setservent_r_proto" ;;
esac
echo "Prototype: $try" ;;
esac
;;
*) case "$usetthreads" in
define) echo "setservent_r has no prototype, not using it." >&4 ;;
esac
d_setservent_r=undef
setservent_r_proto=0
;;
esac
;;
*) setservent_r_proto=0
;;
esac

```

Found in path(s):

```

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/threads/d_setservent_r.U

```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: Prefixup.U 1 2006-08-24 12:32:52Z rmanfredi $
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: $Log: Prefixup.U,v $
?RCS: Revision 3.0.1.1 1995/01/30 14:30:40 ram
?RCS: patch49: created
?RCS:
?X:
?X: Used as: "set dflt; eval $prefixup" to set $dflt to be $prefix/dir
?X: instead of $prefixexp/dir, in case portability was involved somehow
?X: and $prefix uses ~name expansion.
?X:
?MAKE:Prefixup: prefix prefixexp
?MAKE: -pick add $@ %<
?LINT:define prefixup
?S:prefixup:
?S: This shell variable is used internally by Configure to reset
?S: the leading
?S: installation prefix correctly when $prefix uses
?S: ~name expansion.
?S: set dflt
?S: eval $prefixup
?S: That will set $dflt to $prefix/dir if it was $prefixexp/dir and
?S: $prefix differs from $prefixexp.
?S:.
?V:prefixup
: set the prefixup variable, to restore leading tilda escape
prefixup='case "$prefixexp" in
"$prefix") ;;
*) eval "$1=\`echo \$$1 | sed \"s,^$prefixexp,$prefix,\"`";;
esac'
```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/Prefixup.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: d_setruid.U 1 2006-08-24 12:32:52Z rmanfredi $
?RCS:
```

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: \$Log: d_setuid.U,v \$
?RCS: Revision 3.0 1993/08/18 12:07:15 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:d_setuid: Inlibc
?MAKE: -pick add \$@ %<
?S:d_setuid:
?S: This variable conditionally defines the HAS_SETUID symbol, which
?S: indicates to the C program that the setuid() routine is available
?S: to change the real uid of the current program.
?S:.
?C:HAS_SETUID (SETUID):
?C: This symbol, if defined, indicates that the setuid
routine is available
?C: to change the real uid of the current program.
?C:.
?H:#\$d_setuid HAS_SETUID /**/
?H:.
?LINT:set d_setuid
: see if setuid exists
set setuid d_setuid
eval \$inlibc

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/d_setuid.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: \$Log: Signal.U,v \$
?RCS: Revision 3.0.1.1 1997/02/28 15:20:01 ram

?RCS: patch61: created

?RCS:

?X:

?X: This unit produces three files:

?X:

?X: 1- A signal.c file, which, when compiled and run, produces an output like:

?X:

?X: HUP 1

?X: INT 2

?X: QUIT 3

?X: etc...

?X:

?X: 2- A signal.awk script to parse the output of signal.c, fill

?X: in gaps (up to NSIG) and move duplicates to the end.

?X:

?X: 3- A signal_cmd script to compile signal.c and run it

?X: through sort -n -k 2 | uniq | awk -f signal.awk.

?X:

(we try also sort -n +1 since some old hosts don't grok sort -k)

?X: (This is called signal_cmd to avoid OS/2 confusion with

?X: signal.cmd vs. signal.

?X: The signal_cmd script also falls back on checking signals one at a

?X: time in case the signal.c program fails. On at least one version of

?X: Linux 2.1.x, the header file #define'd SIGRTMAX to a symbol that

?X: is not defined by the compiler/linker. :-(. Further, on that same

?X: version of Linux, the user had a defective C-shell that gave an

?X: incorrect list for kill -l, so the fall-back didn't work.

?X:

?X: This unit is then used by sig_name.U.

?X:

?MAKE:Signal: test tr rm awk cat grep startsh eunicefix sed sort uniq \
Findhdr cppstdin +cppflags cppminus Compile trnl run

?MAKE: -pick add \$@ %<

?X:all files declared as "public" since they're used from other units

?F:signal.c signal_cmd signal.lst signal signal.awk

?T: xx xxx xxxfiles

?LINT:use rm run

: Trace out the files included by signal.h, then look for SIGxxx
names.

?X: Remove SIGARRAYSIZE used by HPUX.

?X: Remove SIGSTKSIZE used by Linux.

?X: Remove SIGSTKSZ used by Posix.

?X: Remove SIGTYP void lines used by OS2.

?X: Some cpps, like os390, dont give the file name anywhere

if ["\$\$fieldn" = X]; then

: Just make some guesses. We check them later.

xxx='/usr/include/signal.h /usr/include/sys/signal.h'

else

```

xxx=`echo '#include <signal.h>' |
Scppstdin Scppminus Scppflags 2>/dev/null |
$grep '^[ ]*#.*include' |
$awk '{print \\$\\fieldn}' | $sed 's!'!g' \\
  $sed 's!\\\\\\\\\\\\\\\\!g' | $sort | $uniq`
fi
?X: Check this list of files to be sure we have parsed the cpp output ok.
?X: This will also avoid potentially non-existent files, such
?X: as ../foo/bar.h
xxxfiles=""
?X: Add /dev/null in case the $xxx list is empty.
for xx in $xxx /dev/null ; do
  $test -f "$xx" && xxxfiles="$xxxfiles $xx"
done
?X: If we have found no files, at least try signal.h
case "$xxxfiles" in
") xxxfiles=`./findhdr signal.h` ;;
esac
xxx=`awk '
$1 ~ /^#define$/ &&
$2 ~ /^SIG[A-Z0-9]*$/ && $2 !~ /SIGARRAYSIZE/ && $2 !~ /SIGSTKSIZE/ && $2 !~ /SIGSTKSZ/ && $3 !~
/void/ {
  print substr($2, 4, 20)
}
$1 == "#" && $2 ~ /^define$/ && $3 ~ /^SIG[A-Z0-9]*$/ && $3 !~ /SIGARRAYSIZE/ && $4 !~ /void/ {
  print substr($3, 4, 20)
}' $xxxfiles`
: Append some common names just in case the awk scan failed.
xxx="$xxx ABRT ALRM BUS CANCEL CHLD CLD CONT DIL EMT FPE"
xxx="$xxx FREEZE HUP ILL INT IO IOT KILL LOST LWP PHONE"
xxx="$xxx PIPE POLL PROF PWR QUIT RTMAX RTMIN SEGV STKFLT STOP"
xxx="$xxx SYS TERM THAW TRAP TSTP TTIN TTOU URG USR1 USR2"
xxx="$xxx USR3 USR4 VTALRM WAITING WINCH WIND WINDOW XCPU XFSZ"

: generate a few handy files for later
$cat > signal.c <<'EOCP'
#include <sys/types.h>
#include <signal.h>
#include <stdio.h>
int main() {

/* Strange style to avoid deeply-nested #if/#else/#endif */
#ifdef NSIG
# ifdef _NSIG
#  define NSIG (_NSIG)
# endif
#endif

```

```

#ifndef NSIG
# ifdef SIGMAX
#  define NSIG (SIGMAX+1)
# endif
#endif

#ifndef NSIG
# ifdef SIG_MAX
#
#  define NSIG (SIG_MAX+1)
# endif
#endif

#ifndef NSIG
# ifdef MAXSIG
#  define NSIG (MAXSIG+1)
# endif
#endif

#ifndef NSIG
# ifdef MAX_SIG
#  define NSIG (MAX_SIG+1)
# endif
#endif

#ifndef NSIG
# ifdef SIGARRAYSIZE
#  define NSIG (SIGARRAYSIZE+1) /* Not sure of the +1 */
# endif
#endif

#ifndef NSIG
# ifdef _sys_nsig
#  define NSIG (_sys_nsig) /* Solaris 2.5 */
# endif
#endif

/* Default to some arbitrary number that's big enough to get most
of the common signals.
*/
#ifndef NSIG
#  define NSIG 50
#endif

printf("NSIG %d\n", NSIG);

#ifndef JUST_NSIG

```

EOCP

```
echo $xxx | $tr ' ' $trnl | $sort | $uniq | $awk '
{
printf "#ifdef SIG"; printf $1; printf "\n"
printf "printf(\""; printf $1; printf " %%d\\n\",SIG";
printf $1; printf ");\n"
printf "#endif\n"
}
END {
printf "#endif /* JUST_NSIG */\n";
printf "exit(0);\n}\n";
}
' >>signal.c
$cat >signal.awk <<'EOP'
BEGIN { ndups = 0 }
$1 ~ /^NSIG$/ { nsig = $2 }
($1 !~ /^NSIG$/) && (NF == 2) {
    if ($2 >
maxsig) { maxsig = $2 }
    if (sig_name[$2]) {
dup_name[ndups] = $1
dup_num[ndups] = $2
ndups++
    }
    else {
sig_name[$2] = $1
sig_num[$2] = $2
    }
}
END {
    if (nsig == 0) {
        nsig = maxsig + 1
    }
    printf("NSIG %d\n", nsig);
    for (n = 1; n < nsig; n++) {
if (sig_name[n]) {
        printf("%s %d\n", sig_name[n], sig_num[n])
    }
    else {
        printf("NUM%d %d\n", n, n)
    }
    }
    for (n = 0; n < ndups; n++) {
printf("%s %d\n", dup_name[n], dup_num[n])
    }
}
EOP
```

```

$cat >signal_cmd <<EOS
$startsh
if $test -s signal.lst; then
    echo "Using your existing signal.lst file"
    exit 0
fi
xxx="$xxx"
EOS
?X: Avoid variable interpolation problems, especially with
?X: xxx, which contains newlines.
$cat >>signal_cmd <<'EOS'

```

```

set signal
if eval $compile_ok; then
    $run ./signal$_exe | ($sort -n -k 2 2>/dev/null || $sort -n +1) | \
    $uniq | $awk -f signal.awk >signal.lst
else
    echo "(I can't seem be able to compile the whole test program)" >&4
    echo "(I'll try it in little
    pieces.)" >&4
    set signal -DJUST_NSIG
    if eval $compile_ok; then
        $run ./signal$_exe > signal.nsg
        $cat signal.nsg
    else
        echo "I can't seem to figure out how many signals you have." >&4
        echo "Guessing 50." >&4
        echo 'NSIG 50' > signal.nsg
    fi
    : Now look at all the signal names, one at a time.
    for xx in `echo $xxx | $tr ' ' $trnl | $sort | $uniq`; do
        $cat > signal.c <<EOCP
#include <sys/types.h>
#include <signal.h>
#include <stdio.h>
int main() {
printf("$xx %d\n", SIG${xx});
return 0;
}
EOCP
        set signal
        if eval $compile; then
            echo "SIG${xx} found."
            $run ./signal$_exe >> signal.lst
        else
            echo "SIG${xx} NOT found."
        fi
    done

```

```

if $test -s signal.ls1; then
  $cat signal.nsg signal.ls1 |
  $sort -n | $uniq | $awk -f signal.awk >signal.lst
fi

fi
if $test -s signal.lst; then
:
else
echo "(AAK! I can't compile the test programs -- Guessing)" >&4
echo 'kill -l' >signal
set X `csh -f <signal`
$rm -f signal
shift
case $# in
0) set HUP INT QUIT ILL TRAP ABRT
EMT FPE KILL BUS SEGV SYS PIPE ALRM TERM;;
esac
echo $@ | $tr ' ' $trnl | \
  $awk '{ printf "%s %d\n", $1, ++s; }
  END { printf "NSIG %d\n", ++s }' >signal.lst
fi
$rm -f signal.c signal$_exe signal$_o signal.nsg signal.ls1
EOS
chmod a+x signal_cmd
$eunicefix signal_cmd

```

Found in path(s):

```

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/Signal.U

```

No license file was found, but licenses were detected in source scan.

```

?RCS: $Id: Csym.U,v 3.0.1.4 1995/07/25 13:36:29 ram Exp $
?RCS:
?RCS: Copyright (c) 1991-1993, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 3.0.
?RCS:
?RCS: $Log: Csym.U,v $
?RCS: Revision 3.0.1.4 1995/07/25 13:36:29 ram
?RCS: patch56: re-arranged compile line to include ldflags before objects
?RCS: patch56: added quotes for OS/2 support
?RCS:
?RCS: Revision 3.0.1.3 1995/05/12 12:00:33 ram

```

?RCS: patch54: fixed C test program to bypass gcc builtin type checks (ADO)

?RCS:

?RCS: Revision 3.0.1.2 1994/10/31 09:34:13 ram

?RCS: patch44: added Options to the MAKE line since it's no longer in Init.U

?RCS:

?RCS: Revision

3.0.1.1 1993/08/25 14:00:05 ram

?RCS: patch6: added ldflags as a conditional dependency and to compile line

?RCS: patch6: a final double quote was missing in csym variable after eval

?RCS:

?RCS: Revision 3.0 1993/08/18 12:04:50 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?MAKE:Csym mistrustnm extern_C: Options contains libc libs runnm test \
+cc +optimize +ccflags +ldflags run rm_try_exe d_cplusplus

?MAKE: -pick add \$@ %<

?LINT:define csym

?LINT:use libc

?LINT:extern mistrustnm

?LINT:set mistrustnm

?S:csym:

?S: This shell variable is used internally by Configure to check

?S: whether a given C symbol is defined or not. A typical use is:

?S: set symbol result [-fva] [previous]

?S: eval \$csym

?S: That will set result to 'true' if the function [-f], variable [-v]

?S: or array [-a] is defined, 'false' otherwise. If a previous value is

?S: given and the -r flag was provided on the command line, that value

?S: is reused without questioning.

?S:.

?S:extern_C:

?S: ANSI C

requires 'extern' where C++ requires 'extern "C"'. This

?S: variable can be used in Configure to do the right thing.

?S:.

?S:mistrustnm:

?S: This variable can be used to establish a fallback for the cases

?S: where nm fails to find a symbol. If usenm is false or usenm is true

?S: and mistrustnm is false, this variable has no effect. If usenm is true

?S: and mistrustnm is "compile", a test program will be compiled to try to

?S: find any symbol that can't be located via nm lookup. If mistrustnm is

?S: "run", the test program will be run as well as being compiled.

?S:.

?V:csym

?T:tval tx tlook tf tdc

?F:!try

: is a C symbol defined?

csym='tlook=\$1;

```

case "$3" in
-v) tf=libc.tmp; tdc="";;
-a) tf=libc.tmp; tdc="[]";;
*) tlook="^$1\$"; tf=libc.list; tdc="()";;
esac;
case "$d_cplusplus" in
  $define) extern_C="extern \"C\"";;
  *) extern_C="extern";;
esac;
tx=yes;
case "$reusel-$4" in
true-);;
true-*) tx=no; eval "tval=\$4"; case "$tval" in "") tx=yes;; esac;;
esac;
case
"$tx" in
yes)
?X:
?X: Put symbol inside a printf to fool optimizing compilers...
?X:
?X: We use 'short' instead of 'int' to try to circumvent overzealous
?X: optimizing compilers using built-in prototypes for commonly used
?X: routines to complain when seeing a different external declaration. For
?X: instance, gcc 2.6.3 fails if we use 'int' and we attempt a test against
?X: memcpy() on machines where sizeof(int) == sizeof(char *) (the usual return
?X: type), the compiler assuming it's a built-in declaration given that the
?X: returned size matches. At least with 'short' we are safe! -- RAM, for ADO
?X:
?X: Let's thank GNU cc for making our lives so easy! :-)
?X: (An alternative for the future would be to use our knowledge about gcc
?X: to force a -fno-builtin option in the compile test, in case the 'short'
?X: trick is obsoleted by future gcc releases). -- RAM
?X:
tval=false;
if $test "$runnm" = true; then
if $contains $tlook $tf >/dev/null 2>&1; then
  tval=true;
elif $test
"$mistrustnm" = compile -o "$mistrustnm" = run; then
  echo "$extern_C void *$1$tdc; void (*(p()))$tdc { return &$1; } int main(int argc, char **argv) { if(p() && p() !=
(void *)argv[0]) return(0); else return(1); }"> try.c;
  $cc -o try $optimize $ccflags $ldflags try.c >/dev/null 2>&1 $libs && tval=true;
  $test "$mistrustnm" = run -a -x try && { $run ./try$_exe >/dev/null 2>&1 || tval=false; };
  $rm_try;
fi;
else
  echo "$extern_C void *$1$tdc; void (*(p()))$tdc { return &$1; } int main(int argc, char **argv) { if(p() && p() !=
(void *)argv[0]) return(0); else return(1); }"> try.c;

```

```

$cc -o try $optimize $ccflags $ldflags try.c $libs >/dev/null 2>&1 && tval=true;
$rm_try;
fi;
;;
*)
case "$tval" in
$define) tval=true;;
*) tval=false;;
esac;
;;
esac;
eval "$2=$tval"

```

Found in path(s):

```

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/compline/Csym.U

```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 2000 Jarkko Hietaniemi

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?MAKE:d_finitel: Inlibc

?MAKE: -pick add \$@ %<

?S:d_finitel:

?S: This variable conditionally defines the HAS_FINITEL symbol, which

?S: indicates to the C program that the finitel() routine is available.

?S:.

?C:HAS_FINITEL:

?C: This symbol, if defined, indicates that the finitel routine is

?C: available to check whether a long double is finite

?C: (non-infinity non-NaN).

?C:.

?H:#\$d_finitel HAS_FINITEL /**/

?H:.

?LINT:set d_finitel

: see if finitel exists

set finitel d_finitel

eval \$inlibc

Found in path(s):

```

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/perl/d_finitel.U

```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_gnulibc.U,v 3.0.1.1 1997/02/28 15:34:33 ram Exp \$

?RCS:

?RCS: Copyright (c) 1996,1998 Andy Dougherty

?RCS: Copyright (c) 1996, Sven Verdoolaege

?RCS: Copyright (c) 1991-1993, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 3.0.

?RCS:

?RCS: \$Log: d_gnulibc.U,v \$

?RCS: Revision 3.0.1.1 1997/02/28 15:34:33 ram

?RCS: patch61: created

?RCS:

?MAKE:d_gnulibc gnulibc_version: Myread Oldconfig Setvar rm_try \
 cat Compile run

?MAKE:-pick add \$@ %<

?S:d_gnulibc:

?S: Defined if we're dealing with the GNU C Library.

?S:.

?S:gnulibc_version:

?S: This variable contains the version number of the GNU C library.

?S: It is

usually something like '2.2.5'. It is a plain " if this

?S: is not the GNU C library, or if the version is unknown.

?S:.

?C:HAS_GNULIBC:

?C: This symbol, if defined, indicates to the C program that

?C: the GNU C library is being used. A better check is to use

?C: the __GLIBC__ and __GLIBC_MINOR__ symbols supplied with glibc.

?C:.

?H:#\$d_gnulibc HAS_GNULIBC /**/
 ?H:?%<:#if defined(HAS_GNULIBC) && !defined(_GNU_SOURCE)
 ?H:?%<:# define _GNU_SOURCE
 ?H:?%<:#endif
 ?H:.

?F:!glibc.ver !try

?LINT: set d_gnulibc

?X: gnulibc can be executed by calling __libc_main().

?X: Ulrich Drepper doesn't think any other libc does that,

?X: but we check if it says 'GNU C Library' to be sure.

?X:

?X: Alas, as of 3/1998 glibc 2.0.7 reportedly isn't going to

?X: have __libc_main() anymore. :-(. Fortunately, all released

?X: versions of glibc 2.x.x _do_ have CPP variables. For 2.0.6,

?X: they are:

```

?X: #define __GLIBC__ 2
?X: #define __GLIBC_MINOR__ 0.
?X: (The '6' isn't available :-(.
?X: glibc2.1 will
also have
?X: extern const char * __gnu_get_libc_release(void);
?X: extern const char * __gnu_get_libc_version(void);
?X: functions. --thanks to Andreas Jaeger. --AD 6/1998.
?X: Although the exact format isn't documented, __gnu_get_libc_version()
?X: returns a simple string '2.1.3' in glibc 2.1.3.
?X:
: Check if we are using the GNU C library
echo " "
echo "Checking for GNU C Library..." >&4
cat >try.c <<'EOCP'
/* Find out version of GNU C library. __GLIBC__ and __GLIBC_MINOR__
alone are insufficient to distinguish different versions, such as
2.0.6 and 2.0.7. The function gnu_get_libc_version() appeared in
libc version 2.1.0. A. Dougherty, June 3, 2002.
*/
#include <stdio.h>
int main(void)
{
#ifdef __GLIBC__
# ifdef __GLIBC_MINOR__
# if __GLIBC__ >= 2 && __GLIBC_MINOR__ >= 1 && !defined(__cplusplus)
# include <gnu/libc-version.h>
printf("%s\n", gnu_get_libc_version());
# else
printf("%d.%d\n", __GLIBC__, __GLIBC_MINOR__);
#
endif
# else
printf("%d\n", __GLIBC__);
# endif
return 0;
#else
return 1;
#endif
}
EOCP
set try
if eval $compile_ok && $run ./try > glibc.ver; then
val="$define"
gnulibc_version=`$cat glibc.ver`
echo "You are using the GNU C Library version $gnulibc_version"
else
val="$undef"

```

```
gnulibc_version="
echo "You are not using the GNU C Library"
fi
$rm_try glibc.ver
set d_gnulibc
eval $setvar
```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/compline/d_gnulibc.U
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: groupstypе.U 1 2006-08-24 12:32:52Z rmanfredi \$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic Licence,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic Licence; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: Original Author: Andy Dougherty <doughera@lafcol.lafayette.edu>

?RCS:

?RCS: \$Log: groupstypе.U,v \$

?RCS: Revision 3.0.1.2 1994/10/29 16:18:08 ram

?RCS: patch36: no longer uses Setvar to set 'groupstypе' (ADO)

?RCS: patch36: typo fix in the word 'argument' (ADO)

?RCS:

?RCS: Revision 3.0.1.1 1994/06/20 07:00:18 ram

?RCS: patch30: created by ADO

?RCS:

?MAKE:groupstypе: gidtype d_getgrps Myread Oldconfig Findhdr cat d_setgrps

?MAKE: -pick add \$@ %<

?INIT:groupstypе="

?S:groupstypе:

?S: This

variable defines Groups_t to be something like gid_t, int,

?S: ushort, or whatever type is used for the second argument to

?S: getgroups() and setgroups(). Usually, this is the same as

?S: gidtype (gid_t), but sometimes it isn't.

?S:.

?C:Groups_t (GROUPSTYPЕ):

?C: This symbol holds the type used for the second argument to

?C: getgroups() and setgroups(). Usually, this is the same as

?C: gidtype (gid_t) , but sometimes it isn't.

?C: It can be int, ushort, gid_t, etc...

?C: It may be necessary to include <sys/types.h> to get any

?C: typedef'ed information. This is only required if you have

?C: getgroups() or setgroups()..

?C:.

?H:??<:#if defined(HAS_GETGROUPS) || defined(HAS_SETGROUPS)

?H:??<:#define Groups_t \$groupstype /* Type for 2nd arg to [sg]etgroups() */

?H:??<:#endif

?H:.

?W:??<:getgroups HAS_GETGROUPS setgroups HAS_SETGROUPS

: Find type of 2nd arg to 'getgroups()' and 'setgroups()'

echo " "

case "\$d_getgrps\$d_setgrps" in

define)

case

"\$groupstype" in

") dflt="\$gidtype" ;;

*) dflt="\$groupstype" ;;

esac

\$cat <<EOM

What type of pointer is the second argument to getgroups() and setgroups()?

Usually this is the same as group ids, \$gidtype, but not always.

EOM

rp='What type pointer is the second argument to getgroups() and setgroups()?'

. ./myread

groupstype="\$ans"

::

*) groupstype="\$gidtype";;

esac

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/groupstype.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1998 Jarkko Hietaniemi

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?MAKE:d_sendmsg: Inlibc

?MAKE:-pick add \$@ %<

?S:d_sendmsg:

?S: This variable conditionally defines the HAS_SENDMSG symbol, which

?S: indicates to the C program that the sendmsg() routine is available.

?S:.

?C:HAS_SENDMSG:

?C: This symbol, if defined, indicates that the sendmsg routine is

?C: available to send structured socket messages.

?C:.

?H:#\$d_sendmsg HAS_SENDMSG /**/

?H:.

?LINT:set d_sendmsg

: see if sendmsg exists

set sendmsg d_sendmsg

eval \$inlibc

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_sendmsg.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1999 Jarkko Hietaniemi

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?MAKE:d_sqrtl: Inlibc

?MAKE: -pick add \$@ %<

?S:d_sqrtl:

?S: This variable conditionally defines the HAS_SQRTL symbol, which

?S: indicates to the C program that the sqrtl() routine is available.

?S:.

?C:HAS_SQRTL:

?C: This symbol, if defined, indicates that the sqrtl routine is

?C: available to do long double square roots.

?C:.

?H:#\$d_sqrtl HAS_SQRTL /**/

?H:.

?LINT:set d_sqrtl

: see if sqrtl exists

set sqrtl d_sqrtl

eval \$inlibc

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_sqrtl.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 2000 Jarkko Hietaniemi

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public
?RCS: License or the Artistic License, as specified in the README file.
?RCS:
?MAKE:d_unordered: Inlibc
?MAKE: -pick add \$@ %<
?S:d_unordered:
?S: This variable conditionally defines the HAS_UNORDERED symbol, which
?S: indicates to the C program that the unordered() routine is available.
?S:.
?C:HAS_UNORDERED:
?C: This symbol, if defined, indicates that the unordered routine is
?C: available to check whether two doubles are unordered
?C: (effectively: whether either of them is NaN)
?C:.
?H:#\$d_unordered HAS_UNORDERED /**/
?H:.
?LINT:set d_unordered
: see if unordered exists
set unordered d_unordered
eval \$inlibc

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_unordered.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: \$Log: d_gethent.U,v \$
?RCS: Revision 3.0 1993/08/18 12:06:09 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:d_gethent: Inlibc
?MAKE: -pick add \$@ %<
?S:d_gethent:
?S: This variable conditionally defines HAS_GETHOSTENT if gethostent() is
?S: available to dup file descriptors.
?S:.
?C:HAS_GETHOSTENT (GETHOSTENT):
?C: This symbol, if defined, indicates that the gethostent routine is

?C: available to lookup host names in some data base or other.

?C:.

?H:#\$d_gethent HAS_GETHOSTENT /**/

?H:.

?LINT:set

d_gethent

: see if gethostent exists

set gethostent d_gethent

eval \$inlibc

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/d_gethent.U

No license file was found, but licenses were detected in source scan.

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?MAKE:d_truncl: Inlibc

?MAKE: -pick add \$@ %<

?S:d_truncl:

?S: This variable conditionally defines the HAS_TRUNCL symbol, which

?S: indicates to the C program that the truncl() routine is available

?S: to round long doubles towards zero. If copysignl is also present,

?S: we can emulate modfl.

?S:.

?C:HAS_TRUNCL :

?C: This symbol, if defined, indicates that the truncl routine is

?C: available. If copysignl is also present we can emulate modfl.

?C:.

?H:#\$d_truncl HAS_TRUNCL /**/

?H:.

?LINT:set d_truncl

: see if truncl exists

set truncl d_truncl

eval \$inlibc

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_truncl.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_dup2.U 1 2006-08-24 12:32:52Z rmanfredi \$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic Licence,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: d_dup2.U,v \$

?RCS: Revision 3.0 1993/08/18 12:05:56 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?MAKE:d_dup2: Inlibc

?MAKE: -pick add \$@ %<

?S:d_dup2:

?S: This variable conditionally defines HAS_DUP2 if dup2() is

?S: available to duplicate file descriptors.

?S:.

?C:HAS_DUP2 (DUP2):

?C: This symbol, if defined, indicates that the dup2 routine is

?C: available to duplicate file descriptors.

?C:.

?H:#\$d_dup2 HAS_DUP2 /**/

?H:.

?LINT:set d_dup2

:

see if dup2 exists

set dup2 d_dup2

eval \$inlibc

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/d_dup2.U

No license file was found, but licenses were detected in source scan.

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?MAKE:d_tgamma: Inlibc

?MAKE: -pick add \$@ %<

?S:d_tgamma:

?S: This variable conditionally defines the HAS_TGAMMA symbol, which

?S: indicates to the C program that the tgamma() routine is available

?S: for the gamma function. See also d_lgamma.

?S:.

?C:HAS_TGAMMA:

?C: This symbol, if defined, indicates that the tgamma routine is

?C: available to do the gamma function. See also HAS_LGAMMA.

?C:.

?H:#\$d_tgamma HAS_TGAMMA /**/

?H:.

?LINT:set d_tgamma

```
: see if tgamma exists
set tgamma d_tgamma
eval $inlibc
```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/perl/d_tgamma.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: lintlib.U 1 2006-08-24 12:32:52Z rmanfredi $
```

```
?RCS:
```

```
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
```

```
?RCS:
```

```
?RCS: You may redistribute only under the terms of the Artistic Licence,
```

```
?RCS: as specified in the README file that comes with the distribution.
```

```
?RCS: You may reuse parts of this distribution only within the terms of
```

```
?RCS: that same Artistic Licence; a copy of which may be found at the root
```

```
?RCS: of the source tree for dist 4.0.
```

```
?RCS:
```

```
?RCS: $Log: lintlib.U,v $
```

```
?RCS: Revision 3.0 1993/08/18 12:09:05 ram
```

```
?RCS: Baseline for dist 3.0 netwide release.
```

```
?RCS:
```

```
?MAKE:lintlib lintlibexp: Getfile Loc Oldconfig
```

```
?MAKE: -pick add $@ %<
```

```
?S:lintlib:
```

```
?S: This variable holds the name of the directory in which the user wants
```

```
?S: to put public lint-library files for the package in question. It is
```

```
?S: most often a local directory such as /usr/local/lib/lint. Programs using
```

```
?S: this variable must be prepared to
```

```
deal with ~name expansion.
```

```
?S:.
```

```
?S:lintlibexp:
```

```
?S: This variable is the same as the lintlib variable, but is filename
```

```
?S: expanded at configuration time, for convenient use in your makefiles.
```

```
?S:.
```

```
: determine where public lint libraries go
```

```
case "$lintlib" in
```

```
) dflt=`./loc . ." /usr/local/lib/lint /usr/lib/lint /usr/lib`;;
```

```
*) dflt="$lintlib" ;;
```

```
esac
```

```
echo " "
```

```
fn=d~
```

```
rp='Where do you want to put the public lint libraries?'
```

```
./getfile
```

```
lintlib="$ans"
```

```
lintlibexp="$ansexp"
```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/lintlib.U
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_readdir64_r.U,v 0RCS:

?RCS: Copyright (c) 2002,2003 Jarkko Hietaniemi

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?RCS: Generated by the reentr.pl from the Perl 5.8 distribution.

?RCS:

?MAKE:d_readdir64_r readdir64_r_proto: Inlibc Protochk Hasproto i_systypes \
 usethreads i_dirent extern_C

?MAKE: -pick add \$@ %<

?S:d_readdir64_r:

?S: This variable conditionally defines the HAS_READDIR64_R symbol,

?S: which indicates to the C program that the readdir64_r()

?S: routine is available.

?S:.

?S:readdir64_r_proto:

?S: This variable encodes the prototype of readdir64_r.

?S: It is zero if d_readdir64_r is undef, and one of the

?S: REENTRANT_PROTO_T_ABC macros of reentr.h if d_readdir64_r

?S: is defined.

?S:.

?C:HAS_READDIR64_R:

?C: This symbol, if defined, indicates that the readdir64_r routine

?C: is

available to readdir64 re-entrantly.

?C:.

?C:READDIR64_R_PROTO:

?C: This symbol encodes the prototype of readdir64_r.

?C: It is zero if d_readdir64_r is undef, and one of the

?C: REENTRANT_PROTO_T_ABC macros of reentr.h if d_readdir64_r

?C: is defined.

?C:.

?H:#\$d_readdir64_r HAS_READDIR64_R /**/

?H:#define READDIR64_R_PROTO \$readdir64_r_proto /**/

?H:.

?T:try hdrs d_readdir64_r_proto

: see if readdir64_r exists

set readdir64_r d_readdir64_r

eval \$inlibc

case "\$d_readdir64_r" in

"\$define")

hdrs="\$i_systypes sys/types.h define stdio.h \$i_dirent dirent.h"

```

case "$d_readdir64_r_proto:$susethreads" in
":define") d_readdir64_r_proto=define
set d_readdir64_r_proto readdir64_r $hdrs
eval $hasproto ;;
*) ;;
esac
case "$d_readdir64_r_proto" in
define)
case "$readdir64_r_proto" in
"|0) try='int readdir64_r(DIR*, struct dirent64*, struct dirent64**);'
./protochk "$extern_C $try" $hdrs && readdir64_r_proto=I_TSR ;;
esac
case "$readdir64_r_proto" in
"|0) try='int readdir64_r(DIR*,
struct dirent64*);'
./protochk "$extern_C $try" $hdrs && readdir64_r_proto=I_TS ;;
esac
case "$readdir64_r_proto" in
"|0) d_readdir64_r=undef
readdir64_r_proto=0
echo "Disabling readdir64_r, cannot determine prototype." >&4 ;;
*) case "$readdir64_r_proto" in
REENTRANT_PROTO*) ;;
*) readdir64_r_proto="REENTRANT_PROTO_${readdir64_r_proto}" ;;
esac
echo "Prototype: $try" ;;
esac
;;
*) case "$susethreads" in
define) echo "readdir64_r has no prototype, not using it." >&4 ;;
esac
d_readdir64_r=undef
readdir64_r_proto=0
;;
esac
;;
*) readdir64_r_proto=0
;;
esac

```

Found in path(s):

```

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/threads/d_readdir64_r.U

```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: basicshell.U 1 2006-08-24 12:32:52Z rmanfredi \$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

```

?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: $Log: basicshell.U,v $
?RCS: Revision 3.0 1993/08/18 12:05:25 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:basicshell: Getfile Oldconfig bash csh ksh sh
?MAKE: -pick add $@ %<
?S:basicshell:
?S: This variable contains the eventual value of the BASICSHELL symbol,
?S: which contains the full name of the basic script shell on this
?S: system. Usual values are /bin/sh, /bin/ksh, /bin/csh.
?S:.
?C:BASICSHELL:
?C: This symbol contains the
full name of the basic script shell on this
?C: system. Usual values are /bin/sh, /bin/ksh, /bin/csh.
?C:.
?H:#define BASICSHELL "$basicshell" /**/
?H:.
: find the most basic shell for scripts
echo " "
case "$basicshell" in
")
case "$sh $bash $csh $ksh" in
*/sh*) dflt="$sh" ;;
*/ksh*) dflt="$ksh" ;;
*/csh*) dflt="$csh" ;;
*/bash*) dflt="$bash" ;;
*) dflt='/bin/sh' ;;
esac
;;
*)
dflt="$basicshell";;
esac
fn=f
rp="Give the full path name of the most basic shell used on your system"
./getfile
basicshell=$ans

```

Found in path(s):

```

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/basicshell.U

```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id$
?RCS:
?RCS: Copyright (c) 2003, Jarkko Hietaniemi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 3.0.
?RCS:
?MAKE:d_thread_attr_setscope: Inlibc
?MAKE: -pick add $@ %<
?S:d_thread_attr_setscope:
?S: This variable conditionally defines HAS_PTHREAD_ATTR_SETSCOPE if
?S: pthread_attr_setscope() is available to set the contention scope
?S: attribute of a thread attribute object.
?S:.
?C:HAS_PTHREAD_ATTR_SETSCOPE:
?C: This symbol, if defined, indicates that the pthread_attr_setscope
?C: system call is available to set the contention scope attribute of
?C: a thread attribute object.
?C:.
?H:#$d_thread_attr_setscope HAS_PTHREAD_ATTR_SETSCOPE /**/
?H:.
?LINT:set
d_thread_attr_setscope
: see if pthread_attr_setscope exists
set pthread_attr_setscope d_thread_attr_setscope
eval $inlibc
```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/perl/d_thread_attr_ss.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: Inlibc.U 1 2006-08-24 12:32:52Z rmanfredi $
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: $Log: Inlibc.U,v $
```

?RCS: Revision 3.0.1.1 1994/10/29 15:55:08 ram

?RCS: patch36: call ./whoa explicitly instead of relying on PATH

?RCS:

?RCS: Revision 3.0 1993/08/18 12:05:03 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?X:

?X: This unit checks for the definition of a given function.

?X:

?X: To use it, say:

?X: set function d_func

?X: eval \$inlibc

?X:

?MAKE:Inlibc: Csym Whoa Oldconfig

?MAKE: -pick add \$@ %<

?LINT:define inlibc

?V:inlibc

?S:inlibc:

?S: This

shell variable is used internally by Configure to check

?S: wether a given function is defined or not. A typical use is:

?S: set function d_func

?S: eval \$inlibc

?S: That will print a message, saying wether function was found or

?S: not and set d_func accordingly.

?S:.

?T:was tx sym tres td tu var

: define an is-in-libc? function

inlibc='echo " "; td=\$define; tu=\$undef;

sym=\$1; var=\$2; eval "was=\\$2";

tx=yes;

case "\$reuseval\$was" in

true) ;;

true*) tx=no;;

esac;

case "\$tx" in

yes)

set \$sym tres -f;

eval \$csym;

case "\$tres" in

true)

echo "\$sym() found." >&4;

case "\$was" in \$undef) ./whoa; esac; eval "\$var=\\$td";

*)

echo "\$sym() NOT found." >&4;

case "\$was" in \$define) ./whoa; esac; eval "\$var=\\$tu";

esac;;

*)

```
case "$was" in
$define) echo "$sym() found." >&4;;
*) echo "$sym() NOT found." >&4;;
esac;;
esac'
```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/Inlibc.U
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: i_poll.U,v \$

?RCS:

?RCS: Copyright (c) 1998 Jarkko Hietaniemi

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?MAKE:i_poll: Inhdr Hasfield

?MAKE: -pick add \$@ %<

?S:i_poll:

?S: This variable conditionally defines the I_POLL symbol, and indicates

?S: whether a C program should include <poll.h>.

?S:.

?C:I_POLL:

?C: This symbol, if defined, indicates that <poll.h> exists and

?C: should be included. (see also HAS_POLL)

?C:.

?H:#\$i_poll I_POLL /**/

?H:.

?LINT:set i_poll

: see if this is a poll.h system

set poll.h i_poll

eval \$inhdr

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/perl/i_poll.U
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: ipc.U 1 2006-08-24 12:32:52Z rmanfredi \$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic Licence,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic Licence; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: \$Log: ipc.U,v \$
?RCS: Revision 3.0 1993/08/18 12:08:53 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:ipc serve_shm serve_msg serve_inet_udp serve_inet_tcp serve_unix_udp \
serve_unix_tcp: test Myread Oldconfig d_socket d_msg d_shm d_sem
?MAKE: -pick add \$@ %<
?LINT:use d_msg d_sem
?S:ipc:
?S: This variable holds the type of IPC service we'll be using. Values
?S: include "ip", "shm", "msg", "cms" and "os9". We don't worry about
?S: cms or os9
here, because Configure doesn't run in those places--HMS.
?S:.
?S:serve_shm:
?S: This variable controls the definition of SERVE_SHM, which tells the
?S: C program to use USG shared memory for IPC.
?S:.
?S:serve_msg:
?S: This variable controls the definition of SERVE_MSG, which tells the
?S: C program to use USG message queues for IPC.
?S:.
?S:serve_inet_udp:
?S: This variable controls the definition of SERVE_INET_UDP, which tells
?S: the C program to enable InterNet-domain UDP support for IPC.
?S:.
?S:serve_inet_tcp:
?S: This variable controls the definition of SERVE_INET_TCP, which tells
?S: the C program to enable InterNet-domain TCP support for IPC.
?S:.
?S:serve_unix_udp:
?S: This variable controls the definition of SERVE_UNIX_UDP, which tells
?S: the C program to enable Unix-domain UDP support for IPC.
?S:.
?S:serve_unix_tcp:
?S: This variable controls the definition of SERVE_UNIX_TCP, which tells
?S: the C program to enable Unix-domain TCP support for IPC.
?S:.
?C:SERVE_SHM:
?C: If
defined, tells the C program to use USG shared memory for IPC.
?C:.
?C:SERVE_MSG:
?C: If defined, tells the C program to use USG message queues for IPC.
?C:.
?C:SERVE_INET_UDP:

```

?C: If defined, tells the C program to enable InterNet-domain UDP
?C: support for IPC.
?C:.
?C:SERVE_INET_TCP:
?C: If defined, tells the C program to enable InterNet-domain TCP
?C: support for IPC.
?C:.
?C:SERVE_UNIX_UDP:
?C: If defined, tells the C program to enable Unix-domain UDP
?C: support for IPC.
?C:.
?C:SERVE_UNIX_TCP:
?C: If defined, tells the C program to enable Unix-domain TCP
?C: support for IPC.
?C:.
?H:#$serve_shm SERVE_SHM /**/
?H:#$serve_msg SERVE_MSG /**/
?H:#$serve_inet_udp SERVE_INET_UDP /**/
?H:#$serve_inet_tcp SERVE_INET_TCP /**/
?H:#$serve_unix_udp SERVE_UNIX_UDP /**/
?H:#$serve_unix_tcp SERVE_UNIX_TCP /**/
?H:.
?X: FIXME -- RAM
?INIT:serve_shm=""
?INIT:serve_msg="$undef"
?INIT:serve_inet_udp=""
?INIT:serve_inet_tcp=""
?INIT:serve_unix_udp=""
?INIT:serve_unix_tcp=""
: get IPC mechanism
echo
" "
ipc=""
while $test -z "$ipc"
do
if $test "$ipc" != "shm" -a "$d_socket" = "$define"; then
ipc=""
if $test "$serve_inet_udp" = "$undef"; then
dflt=n
else
dflt=y
fi
rp='Provide InterNet-domain UDP service?'
./myread
dflt=""
case "$ans" in
n*) serve_inet_udp="$undef";;
*)

```

```

serve_inet_udp="$define"
ipc='ip'
;;
esac

if $test "$serve_inet_tcp" = "$define"; then
  dflt=y
else
  dflt=n
fi
rp='Provide InterNet-domain TCP service?'
./myread
dflt=""
case "$ans" in
n*) serve_inet_tcp="$undef";;
*)
  serve_inet_tcp="$define"
  ipc='ip'
  ;;
esac

if $test "$serve_unix_udp" = "$define"; then
  dflt=y
else
  dflt=n
fi
rp='Provide Unix-domain UDP service?'
./myread
dflt=""
case "$ans" in
n*) serve_unix_udp="$undef";;
*)
  serve_unix_udp="$define"
  ipc='ip'
  ;;
esac

if $test "$serve_unix_tcp" = "$define"; then
  dflt=y
else
  dflt=n
fi
rp='Provide Unix-domain TCP service?'
./myread
dflt=""
case
"$ans" in
n*) serve_unix_tcp="$undef";;

```

```

*)
  serve_unix_tcp="$define"
  ipc='ip'
  ;;
esac
else
  serve_inet_udp="$undef"
  serve_inet_tcp="$undef"
  serve_unix_udp="$undef"
  serve_unix_tcp="$undef"
fi
if $test "$ipc" != "ip" -a "$d_shm" = "$define"; then
  echo "Providing USG shared memory IPC support." >&4
  serve_shm="$define"
  ipc='shm'
else
  serve_shm="$undef"
fi
if $test -z "$ipc"; then
  echo "You must select an IPC mechanism." >&4
fi
done

```

Found in path(s):

```

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/ipc.U

```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1999 Jarkko Hietaniemi

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?MAKE:d_msghdr_s: Hasstruct i_systypes d_socket i_sysuio Setvar

?MAKE: -pick add \$@ %<

?S:d_msghdr_s:

?S: This variable conditionally defines the HAS_STRUCTURE_MSGHDR symbol,

?S: which indicates that the struct msghdr is supported.

?S:.

?C:HAS_STRUCTURE_MSGHDR:

?C: This symbol, if defined, indicates that the struct msghdr

?C: is supported.

?C:.

?H:#\$d_msghdr_s HAS_STRUCTURE_MSGHDR /**/

?H:.

?LINT:set d_msghdr_s

```

: Check for msghdr_s
echo " "
echo "Checking to see if your system supports struct msghdr..." >&4
set d_msghdr_s msghdr $i_systypes sys/types.h $d_socket sys/socket.h $i_sysuio sys/uio.h
eval $hasstruct
case "$d_msghdr_s" in
"$define") echo "Yes, it does." ;;
*) echo "No, it doesn't."
;;
esac

```

Found in path(s):

```

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/perl/d_msghdr_s.U

```

No license file was found, but licenses were detected in source scan.

```

?RCS: $Id: Instruct.U,v 3.0.1.3 1997/02/28 15:02:55 ram Exp $
?RCS:
?RCS: Copyright (c) 1991-1993, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 3.0.
?RCS:
?RCS: $Log: Instruct.U,v $
?RCS: Revision 3.0.1.3 1997/02/28 15:02:55 ram
?RCS: patch61: logname / whoami sequence rewritten to use case
?RCS:
?RCS: Revision 3.0.1.2 1995/02/15 14:11:34 ram
?RCS: patch51: author name now appears at the end of the paragraph (WED)
?RCS:
?RCS: Revision 3.0.1.1 1995/01/11 15:12:05 ram
?RCS: patch45: now documents the & escape to turn -d on at the read prompt
?RCS:
?RCS: Revision 3.0 1993/08/18 12:05:04 ram
?RCS: Baseline for
?RCS: dist 3.0 netwide release.
?RCS:
?X:
?X: This unit spew out the directions that we want everyone to read. I try to
?X: keep the first "pagefull" much less than a page since they don't know it
?X: isn't going to go shooting off the top of the screen, and we don't want
?X: to panic them yet.
?X:
?MAKE:Instruct: Myread Configdir Devel contains
?MAKE: -pick wipe $@ %<

```

```

?T:user needman firsttime
: general instructions
needman=true
firsttime=true
user=`(logname) 2>/dev/null`
case "$user" in
") user=`whoami 2>&1`;
esac
if $contains "^$user$" ../.config/instruct >/dev/null 2>&1; then
firsttime=false
echo " "
rp='Would you like to see the instructions?'
dflt=n
. ./myread
case "$ans" in
[yY]*) ;;
*) needman=false;;
esac
fi
if $needman; then
cat <<EOH

```

This installation shell script will examine your system and ask you questions to determine how the <PACKAGENAME> package should be installed. If you get stuck on a question, you may use a ! shell escape to start a subshell or execute a command. Many of the questions will have default answers in square brackets; typing carriage return will give you the default.

On some of the questions which ask for file or directory names you are allowed to use the ~name construct to specify the login directory belonging to "name", even if you don't have a shell which knows about that. Questions where this is allowed will be marked "(~name ok)".

```

EOH
rp="
dflt='Type carriage return to continue'
. ./myread
cat <<'EOH'

```

The prompter used in this script allows you to use shell variables and backticks in your answers. You may use \$1, \$2, etc... to refer to the words in the default answer, as if the default line was a set of arguments given to a script shell. This means you may also use \$* to repeat the whole default line, so you do not have to re-type everything to add something to the default.

Every time there is a substitution, you will have to confirm. If there is an error (e.g. an unmatched backtick), the default answer

will remain unchanged
and you will be prompted again.

If you are in a hurry, you may run 'Configure -d'. This will bypass nearly all the questions and use the computed defaults (or the previous answers if there was already a config.sh file). Type 'Configure -h' for a list of options. You may also start interactively and then answer '& -d' at any prompt to turn on the non-interactive behaviour for the remainder of the execution.

EOH

```
. ./myread  
cat <<EOH
```

Much effort has been expended to ensure that this shell script will run on any Unix system. If despite that it blows up on yours, your best bet is to edit Configure and run it again. If you can't run Configure for some reason, you'll have to generate a config.sh file by hand. Whatever problems you have, let me (<MAINTLOC>) know how I blew it.

This installation script affects things in two ways:

- 1) it may do direct variable substitutions on some of the files included in this kit.
- 2) it builds a config.h file for inclusion in C programs. You may edit any of these files as the need arises after running this script.

If you make a mistake on a question, there is no easy way to back up to it currently. The easiest thing to do is to edit config.sh and rerun all the SH files. Configure will offer to let you do this before it runs the SH files.

EOH

```
?X: In case they played with the prompter...  
dflt='Type carriage return to continue'  
. ./myread  
case "$firsttime" in  
true) echo $user >>../config/instruct;;  
esac  
fi
```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/modified/Instruct.U
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1999 Jarkko Hietaniemi

```

?RCS:
?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 3.0.
?RCS:
?MAKE:d_mprotect: Inlibc
?MAKE: -pick add $@ %<
?S:d_mprotect:
?S: This variable conditionally defines HAS_MPROTECT if mprotect() is
?S: available to modify the access protection of a memory mapped file.
?S:.
?C:HAS_MPROTECT:
?C: This symbol, if defined, indicates that the mprotect system call is
?C: available to modify the access protection of a memory mapped file.
?C:.
?H:#$d_mprotect HAS_MPROTECT /**/
?H:.
?LINT:set d_mprotect
: see if mprotect exists
set mprotect d_mprotect
eval $inlibc

```

Found in path(s):

```

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/perl/d_mprotect.U

```

No license file was found, but licenses were detected in source scan.

```

?RCS: $Id: d_memcpy.U 1 2006-08-24 12:32:52Z rmanfredi $
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: $Log: d_memcpy.U,v $
?RCS: Revision 3.0.1.1 1993/09/13 16:02:58 ram
?RCS: patch10: removed text recommending bcopy over memcpy (WAD)
?RCS:
?RCS: Revision 3.0 1993/08/18 12:06:34 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:d_memcpy: Inlibc
?MAKE: -pick add $@ %<

```

?S:d_memcpy:
?S: This variable conditionally defines the HAS_MEMCPY symbol, which
?S: indicates to the C program that the memcpy() routine is available
?S: to copy blocks of
memory.
?S:.
?C:HAS_MEMCPY (MEMCPY):
?C: This symbol, if defined, indicates that the memcpy routine is available
?C: to copy blocks of memory.
?C:.
?H:#\$d_memcpy HAS_MEMCPY /**/
?H:.
?LINT:set d_memcpy
: see if memcpy exists
set memcpy d_memcpy
eval \$inlibc

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/d_memcpy.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: \$Log: libs.U,v \$
?RCS: Revision 3.0.1.6 1997/02/28 16:09:11 ram
?RCS: patch61: replaced .a with \$_a all over the place
?RCS:
?RCS: Revision 3.0.1.5 1995/07/25 14:12:05 ram
?RCS: patch56: now knows about OS/2 platforms
?RCS:
?RCS: Revision 3.0.1.4 1994/10/29 16:24:22 ram
?RCS: patch36: removed old broken thislib/thatlib processing (ADO)
?RCS:
?RCS: Revision 3.0.1.3 1994/06/20 07:05:44 ram
?RCS: patch30: code cleanup with if/elif by ADO and RAM
?RCS: patch30: undone patch23 for libswanted default
setting
?RCS:
?RCS: Revision 3.0.1.2 1994/05/06 15:08:45 ram

?RCS: patch23: now includes ordered default libswanted variable (ADO)

?RCS: patch23: major cleanup for library lookups (ADO)

?RCS:

?RCS: Revision 3.0.1.1 1993/08/25 14:02:31 ram

?RCS: patch6: added default for libs

?RCS:

?RCS: Revision 3.0 1993/08/18 12:09:03 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?MAKE:libs libsfound libsfiles libsdirs libspath libscheck: \
test cat Myread Oldconfig Loc libpth package xlibpth so _a \
+usesocks sed +cc +ccflags +ldflags rm

?MAKE: -pick add \$@ %<

?S:libs:

?S: This variable holds the additional libraries we want to use.

?S: It is up to the Makefile to deal with it. The list can be empty.

?S:.

?S:libsfound:

?S: This variable holds the full pathnames of the libraries

?S: we found and accepted.

?S:.

?S:libsfiles:

?S: This variable holds the filenames aka basenames of the libraries

?S: we found and accepted.

?S:.

?S:libsdirs:

?S: This variable holds the directory
names aka dirnames of the libraries

?S: we found and accepted, duplicates are removed.

?S:.

?S:libspath:

?S: This variable holds the directory names probed for libraries.

?S:.

?S:libscheck:

?S: This variable is intended to be set by hint files, if needed.

?S: It should contain shell code that will be eval'ed with \$xxx holding

?S: some library file. It may change \$xxx if needed.

?S: For instance, on an Irix platform, you may make sure the right

?S: library file is used depending on the cc command line, so that the

?S: correct library is used depending on the selected ABI (for 32 and

?S: 64-bit compilations).

?S:

?S: Here is an example of code that could be found in a hint file on Irix

?S: when the selected compiler was for 32-bit -- that code is put in the

?S: cc.cbu call-back unit to be invoked AFTER the C compiler and its

?S: flags have been chosen:

?S:

?S: libscheck='case "\$xxx" in

```

?S: *.a) /bin/ar p $xxx `/bin/ar t $xxx | sed q` >$$o;
?S: case "/usr/bin/file $$o`" in
?S: *N32*)
rm -f $$o ;;
?S: *) rm -f $$o; xxx=/no/n32$xxx ;;
?S: esac ;;
?S: *) case "/usr/bin/file $xxx`" in
?S: *N32*) ;;
?S: *) xxx=/no/n32$xxx ;;
?S: esac ;;
?S: esac'
?S:.
?D:libs="
?LINT:extern libswanted
?LINT:change libswanted
?INIT:: default library list
?INIT:libswanted="
?X: This order is chosen so that libraries -lndir, -ldir, -lucb, -lbsd,
?X: -lBSD, -lPW, and -lx only get used if there are unresolved
?X: routines at link time. Usually, these are backwards compatability
?X: libraries, and may not be as reliable as the standard c library.
?X:
?X: The -lsocket -linet -lnsl order has been reported to be necessary
?X: for at least one SVR4 implementation.
?X: -lc must proceed -lucb or -lbsd for most Solaris applications.
?X: -lc_s proceeds -lc so we pick up the shared library version, if
?X: it is available.
?X:
?X: The ordering of c, posix, and cposix is a guess and almost
?X: certainly wrong on about half of all systems.
?X:
?X: Set proper libswanted in your private
Myinit.U if needed.
?X:
?X:: default ordered library list
?X:libswanted='net socket inet bind nsl nm sdbm gdbm ndbm dbm malloc dl'
?X:libswanted="$libswanted dld sun m c_s c posix cposix ndir dir ucb"
?X:libswanted="$libswanted bsd BSD PW x"
?X:
?INIT:: should be set by hint files if needed
?INIT:libscheck="
?T:xxx yyy thislib thisdir libstyle linkmsg
?F:lt.c lt
: Looking for optional libraries
echo " "
echo "Checking for optional libraries..." >&4
case "$libs" in
'|") dflt="";;

```

```

*) dflt="$libs";;
esac
case "$libswanted" in
") libswanted='c_s';;
esac
?X: libsocks has nasty naming scheme.
?X: This does not work if somebody wants SOCKS 4.
case "$susesocks" in
"$define") libswanted="$libswanted socks5 socks5_sh" ;;
esac
?X: Used later for link checks
echo "extern char printf(); int main() { printf(); return 0; }" > lt.c
libsfound=""
libsfiles=""
libsdirs=""
libspath=""
for thisdir in $libpth $xlibpth; do
test -d $thisdir && libspath="$libspath $thisdir"
done
for thislib in $libswanted;
do
for thisdir in $libspath; do
xxx=""
if test ! -f "$xxx" ; then
xxx=`ls $thisdir/lib$thislib.$so.[0-9]* 2>/dev/null | $sed -n '1p'`
$test -f "$xxx" && eval $libscheck
$test -f "$xxx" && libstyle=shared
fi
if test ! -f "$xxx"; then
xxx=$thisdir/lib$thislib.$so
$test -f "$xxx" && eval $libscheck
$test -f "$xxx" && libstyle=shared
fi
if test ! -f "$xxx"; then
xxx=$thisdir/lib$thislib$_a
$test -f "$xxx" && eval $libscheck
$test -f "$xxx" && libstyle=static
fi
if test ! -f "$xxx"; then
xxx=$thisdir/$thislib$_a
$test -f "$xxx" && eval $libscheck
$test -f "$xxx" && libstyle=static
fi
if test ! -f "$xxx"; then
xxx=$thisdir/lib${thislib}_s$_a
$test -f "$xxx" && eval $libscheck
$test -f "$xxx" && libstyle=static
$test -f "$xxx" && thislib=${thislib}_s

```

```

fi
if test ! -f "$xxx"; then
xxx=$thisdir/Slib$thislib$_a
    $test -f "$xxx" && eval $libscheck
$test
-f "$xxx" && libstyle=static
fi
if $test -f "$xxx"; then
?X:
?X: It is not sufficient to find a .so on the disk. We must make sure
?X: that we can indeed supply the -lfoo line on the cc line to link against
?X: that library. On Linux for instance, a versioned .so will not be
?X: implicitly linked against, whereas it will work fine on Solaris 2.6.
?X: --RAM, 10/10/2003
?X:
if $cc -o lt $ccflags $ldflags lt.c -l$thislib >/dev/null 2>&1;
then
linkmsg=""
else
linkmsg=" but I can't link against it"
fi
case "$libstyle" in
shared) echo "Found -l$thislib (shared)$linkmsg." ;;
static) echo "Found -l$thislib$linkmsg." ;;
*) echo "Found -l$thislib ($libstyle)$linkmsg." ;;
esac
case " $dflt " in
*" -l$thislib "*) ;;
*)
case "$linkmsg" in
")
dflt="$dflt -l$thislib"
libsfound="$libsfound $xxx"
yyy=`basename $xxx`
libsfiles="$libsfiles $yyy"
yyy=`echo $xxx|sed -e "s%/$yyy%\\$%%"`
case " $libsdirs
" in
*" $yyy "*) ;;
*) libsdirs="$libsdirs $yyy" ;;
esac
;;
esac
;;
esac
break
fi
done

```

```

if $test ! -f "$xxx"; then
    echo "No -l$thislib."
fi
done
set X $dflt
shift
dflt="$*"
case "$libs" in
") dflt="$dflt";;
*) dflt="$libs";;
esac
case "$dflt" in
'|') dflt='none';;
esac
$rm -f lt.c lt

$cat <<EOM

```

In order to compile \$package on your machine, a number of libraries are usually needed. Include any other special libraries here as well. Say "none" for none. The default list is almost always right.
EOM

```

echo " "
rp="Which libraries to use?"
./myread
case "$ans" in
none) libs='';;
*) libs="$ans";;
esac

```

Found in path(s):

```

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/libs.U

```

No license file was found, but licenses were detected in source scan.

```

?RCS: $Id: d_usleep.U 1 2006-08-24 12:32:52Z rmanfredi $
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: $Log: d_usleep.U,v $
?RCS: Revision 3.0 1993/08/18 12:07:53 ram

```

?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:d_usleep: Inlibc
?MAKE: -pick add \$@ %<
?S:d_usleep:
?S: This variable conditionally defines HAS_USLEEP if usleep() is
?S: available to do high granularity sleeps.
?S:.
?C:HAS_USLEEP (USLEEP):
?C: This symbol, if defined, indicates that the usleep routine is
?C: available to let the process sleep on a sub-second accuracy.
?C:.
?H:#\$d_usleep
HAS_USLEEP /**/
?H:.
?LINT:set d_usleep
: see if usleep exists
set usleep d_usleep
eval \$inlibc

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/d_usleep.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: mboxchar.U 1 2006-08-24 12:32:52Z rmanfredi \$
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: \$Log: mboxchar.U,v \$
?RCS: Revision 3.0.1.2 1995/07/25 14:13:12 ram
?RCS: patch56: ensure ctrl-A characters are visible in prompt (WED)
?RCS:
?RCS: Revision 3.0.1.1 1994/05/06 15:11:22 ram
?RCS: patch23: added support for MMDF mailboxes (WED)
?RCS:
?RCS: Revision 3.0 1993/08/18 12:09:15 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:mboxchar: cat package shsharp Myread Oldconfig
?MAKE: -pick add \$@ %<
?S:mboxchar:

?S: This variable
contains the eventual value of the MBOXCHAR symbol,
?S: which is how a C program can identify a file as a mailbox.
?S:.
?C:MBOXCHAR:
?C: This symbol contains a character which will match the beginning
?C: of a mailbox file.
?C:.
?H:#define MBOXCHAR '\$mboxchar' /**/
?H:.
?T:CTRLA
?INIT:CTRLA=`echo a | tr a '\001`
: determine how to determine when a file is a mailbox
case "\$mboxchar" in
") dflt=F;;
?X: The following ^A is two-chars to ensure it will print out -- WED
"\$CTRLA") dflt='^A';;
*) dflt="\$mboxchar";;
esac
\$cat <<EOM

In saving articles, \$package wants to differentiate between saving to mailbox format files and normal files. It does this by examining the first character of the file in question. On most systems the first line starts with "From ...", so the first character is an F. Other systems use magic cookies like control codes between articles, so one of those would be first. For example, MMDF messages are separated with lines of four control-A's (you may specify one as ^A, i.e. caret A).

```
EOM
rp="What's the first character of a mailbox file?"
./myread
mboxchar="$ans"
case "$mboxchar" in
'F') ;;
"$CTRLA") ;;
'^A|^a') mboxchar="$CTRLA";;
*) cat <<'EOM'
```

You will need to edit the shell script mbox.saver to properly append an article to a mailbox. The arguments to the script are documented in

```
EOM
case "$shsharp" in
false) echo "comments in mbox.saver.std.";
true) echo "comments in the shell script itself.";
esac
esac
```

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/mboxchar.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1999, Jarkko Hietaniemi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 3.0.

?RCS:

?MAKE:d_mq_getattr: Inlibc

?MAKE: -pick add \$@ %<

?S:d_mq_getattr:

?S: This variable conditionally defines HAS_MQ_GETATTR if mq_getattr() is

?S: available to get the attributes and status of a POSIX message queue.

?S:.

?C:HAS_MQ_GETATTR:

?C: This symbol, if defined, indicates that the mq_getattr system call is

?C: available to get the attributes and status of a POSIX message queue.

?C:.

?H:#\$d_mq_getattr HAS_MQ_GETATTR /**/

?H:.

?LINT:set d_mq_getattr

: see if mq_getattr exists

set mq_getattr d_mq_getattr

eval \$inlibc

Found

in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_mq_getattr.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

```

?RCS:
?RCS: Original Author: Andy Dougherty <doughera@lafcol.lafayette.edu>
?RCS:
?RCS: $Log: d_closedir.U,v $
?RCS: Revision 3.0.1.3 1997/02/28 15:31:26 ram
?RCS: patch61: added ?F: metalint hint
?RCS:
?RCS: Revision 3.0.1.2 1994/10/29 16:11:18 ram
?RCS: patch36: added 'ldflags' to the test compile line (ADO)
?RCS:
?RCS: Revision 3.0.1.1 1994/08/29 16:07:21 ram
?RCS: patch32: created by ADO
?RCS:
?MAKE:d_closedir d_void_closedir: Inlibc i_dirent i_sysdir i_sysndir \
cc cflags ldflags libs Setvar rm
?MAKE: -pick
add $@ %<
?S:d_closedir:
?S: This variable conditionally defines HAS_CLOSEDIR if closedir() is
?S: available.
?S:.
?C:HAS_CLOSEDIR:
?C: This symbol, if defined, indicates that the closedir() routine is
?C: available.
?C:.
?H:#$d_closedir HAS_CLOSEDIR /**/
?H:.
?S:d_void_closedir:
?S: This variable conditionally defines VOID_CLOSEDIR if closedir()
?S: does not return a value.
?S:.
?C:VOID_CLOSEDIR:
?C: This symbol, if defined, indicates that the closedir() routine
?C: does not return a value.
?C:.
?H:#$d_void_closedir VOID_CLOSEDIR /**/
?H:.
?F:!closedir
?LINT:set d_closedir d_void_closedir
: see if closedir exists
set closedir d_closedir
eval $inlibc

@if VOID_CLOSEDIR || d_void_closedir
?X: The following contortions are designed so we can call closedir()
?X: and check whether it returns a value. The contortions are designed
?X: to portably pick up the correct directory header, for those
?X: systems that support various mutually incompatible directory functions.

```

```

?X: This
is from perl5's perl.h
case "$d_closedir" in
"$define")
echo " "
echo "Checking whether closedir() returns a status..." >&4
cat > closedir.c <<EOM
#$i_dirent I_DIRENT /**/
#$i_sysdir I_SYS_DIR /**/
#$i_sysndir I_SYS_NDIR /**/

#if defined(I_DIRENT)
#include <dirent.h>
#if defined(NeXT) && defined(I_SYS_DIR) /* NeXT needs dirent + sys/dir.h */
#include <sys/dir.h>
#endif
#else
#ifdef I_SYS_NDIR
#include <sys/ndir.h>
#else
#ifdef I_SYS_DIR
#ifdef hp9000s500
#include <ndir.h> /* may be wrong in the future */
#else
#include <sys/dir.h>
#endif
#endif
#endif
#endif
#endif
int main() { return closedir(opendir(".")); }
EOM
if $cc $ccflags $ldflags -o closedir closedir.c $libs > /dev/null 2>&1; then
if ./closedir > /dev/null 2>&1 ; then
echo "Yes, it does."
val="$undef"
else
echo "No, it doesn't."
val="$define"
fi
else
echo "(I can't seem to compile the test program--assuming it doesn't)"
val="$define"
fi
;;
*)
val="$undef";
;;
esac

```

```
set d_void_closedir
eval $setvar
$rm
-f closedir*
@end
```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/d_closedir.U
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: Csym.U,v \$

?RCS: Revision 3.0.1.4 1995/07/25 13:36:29 ram

?RCS: patch56: re-arranged compile line to include ldflags before objects

?RCS: patch56: added quotes for OS/2 support

?RCS:

?RCS: Revision 3.0.1.3 1995/05/12 12:00:33 ram

?RCS: patch54: fixed C test program to bypass gcc builtin type checks (ADO)

?RCS:

?RCS: Revision 3.0.1.2 1994/10/31 09:34:13 ram

?RCS: patch44: added Options to the MAKE line since it's no longer in Init.U

?RCS:

?RCS: Revision 3.0.1.1 1993/08/25 14:00:05 ram

?RCS:

patch6: added ldflags as a conditional dependency and to compile line

?RCS: patch6: a final double quote was missing in csym variable after eval

?RCS:

?RCS: Revision 3.0 1993/08/18 12:04:50 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?MAKE:Csym: Options contains libc libs runnm +cc +ccflags +ldflags rm

?MAKE: -pick add \$@ %<

?LINT:define csym

?LINT:use libc

?S:csym:

?S: This shell variable is used internally by Configure to check

?S: wether a given C symbol is defined or not. A typical use is:

?S: set symbol result [-fva] [previous]

?S: eval \$csym
 ?S: That will set result to 'true' if the function [-f], variable [-v]
 ?S: or array [-a] is defined, 'false' otherwise. If a previous value is
 ?S: given and the -r flag was provided on the command line, that value
 ?S: is reused without questioning.
 ?S:.
 ?V:csym
 ?T:tval tx tlook tf tdc tc
 : is a C symbol defined?
 csym='tlook=\$1;
 case "\$3" in
 -v) tf=libc.tmp; tc=""; tdc="";;
 -a) tf=libc.tmp; tc="[0]"; tdc="[]";;
 *) tlook="^\\$1\\$";
 tf=libc.list; tc=""; tdc="()";;
 esac;
 tx=yes;
 case "\$reuseval-\$4" in
 true-) ;;
 true-*) tx=no; eval "tval=\\$4"; case "\$tval" in "") tx=yes;; esac;;
 esac;
 case "\$tx" in
 yes)
 case "\$runnm" in
 true)
 if \$contains \$tlook \$tf >/dev/null 2>&1;
 then tval=true;
 else tval=false;
 fi;;
 *)
 ?X:
 ?X: We use 'char' instead of 'int' to try to circumvent overzealous
 ?X: optimizing compilers using built-in prototypes for commonly used
 ?X: routines to complain when seeing a different external declaration. For
 ?X: instance, gcc 2.6.3 fails if we use 'int' and we attempt a test against
 ?X: memcpy() on machines where sizeof(int) == sizeof(char *) (the usual return
 ?X: type), the compiler assuming it's a built-in declaration given that the
 ?X: returned size matches. At least with 'char' we are safe! -- RAM, for ADO
 ?X:
 ?X: Let's thank GNU cc for making our lifes so easy! :-)
 ?X: (An alternative for the future would be to use our knowledge about gcc
 ?X: to force a -fno-builtin option in the
 ?X: compile test, in case the 'char'
 ?X: trick is obsoleted by future gcc releases). -- RAM
 ?X:
 ?X: Lastly, gcc 3.4 otimizes &missing == 0 away, so we use + 2 instead now.
 ?X: The GNU folks like to do weird things, don't they? -- RAM, 2004-06-05
 ?X:

```

echo "extern char $1$tdc; int main() { return &$1$tc + 2; }" > t.c;
if $cc $ccflags $ldflags -o t t.c $libs >/dev/null 2>&1;
then tval=true;
else tval=false;
fi;
$rm -f t t.c;;
esac;;
*)
case "$tval" in
$define) tval=true;;
*) tval=false;;
esac;;
esac;
eval "$2=$tval"

```

Found in path(s):

```

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/Csym.U

```

No license file was found, but licenses were detected in source scan.

```

?RCS: $Id: packadmin.U 1 2006-08-24 12:32:52Z rmanfredi $
?RCS:
?RCS: Copyright (c) 1996, Andy Dougherty
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?MAKE:packadmin: cf_email Oldconfig Myread cat spackage package
?MAKE: -pick add $@ %<
?Y:TOP
?S:packadmin:
?S: Electronic mail address of the package administrator.
?S:.
: check wehther they will act as local admin for the package
$cat <<EOM

```

If you or somebody else will be maintaining \$package at your site, please fill in the correct e-mail address here so that they may be contacted if necessary. You may enter "none" for no administrator.

EOM

```

case "$packadmin" in
") dflt="$cf_email";;

```

```
*) dflt="$packadmin";;
esac
rp="$spackage administrator e-mail address"
. ./myread
packadmin="$ans"
```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/packadmin.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: d_getnent.U,v 3.0 1993/08/18 12:06:09 ram Exp $
```

```
?RCS:
```

```
?RCS: Copyright (c) 1991-1993, Raphael Manfredi
```

```
?RCS:
```

```
?RCS: You may redistribute only under the terms of the Artistic License,
```

```
?RCS: as specified in the README file that comes with the distribution.
```

```
?RCS: You may reuse parts of this distribution only within the terms of
```

```
?RCS: that same Artistic License; a copy of which may be found at the root
```

```
?RCS: of the source tree for dist 3.0.
```

```
?RCS:
```

```
?RCS: $Log: d_getnent.U,v $
```

```
?RCS: Revision 3.0 1993/08/18 12:06:09 ram
```

```
?RCS: Baseline for dist 3.0 netwide release.
```

```
?RCS:
```

```
?MAKE:d_getnent: Inlibc
```

```
?MAKE: -pick add $@ %<
```

```
?S:d_getnent:
```

```
?S: This variable conditionally defines HAS_GETNETENT if getnetent() is
```

```
?S: available to look up network names in some data base or another.
```

```
?S:.
```

```
?C:HAS_GETNETENT:
```

```
?C: This symbol, if defined, indicates that the getnetent() routine is
```

```
?C: available to look up network names in some data base
```

```
or another.
```

```
?C:.
```

```
?H:#$d_getnent HAS_GETNETENT /**/
```

```
?H:.
```

```
?LINT:set d_getnent
```

```
: see if getnetent exists
```

```
set getnetent d_getnent
```

```
eval $inlibc
```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/modified/d_getnent.U
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: i_assert.U,v \$
 ?RCS:
 ?RCS: Copyright (c) 2007 H.Merijn Brand
 ?RCS:
 ?RCS: You may distribute under the terms of either the GNU General Public
 ?RCS: License or the Artistic License, as specified in the README file.
 ?RCS:
 ?MAKE:i_assert: Inhdr Hasfield
 ?MAKE: -pick add \$@ %<
 ?S:i_assert:
 ?S: This variable conditionally defines the I_ASSERT symbol, which
 ?S: indicates to the C program that <assert.h> exists and could be
 ?S: included.
 ?S:.
 ?C:I_ASSERT:
 ?C: This symbol, if defined, indicates that <assert.h> exists and
 ?C: could be included by the C program to get the assert() macro.
 ?C:.
 ?H:#\$i_assert I_ASSERT /**/
 ?H:.
 ?LINT:set i_assert
 : see if this is a assert.h system
 set assert.h i_assert
 eval \$inhdr

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/i_assert.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$
 ?RCS:
 ?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
 ?RCS:
 ?RCS: You may redistribute only under the terms of the Artistic License,
 ?RCS: as specified in the README file that comes with the distribution.
 ?RCS: You may reuse parts of this distribution only within the terms of
 ?RCS: that same Artistic License; a copy of which may be found at the root
 ?RCS: of the source tree for dist 4.0.
 ?RCS:
 ?RCS: Copyright (c) 1999 Jarkko Hietaniemi
 ?RCS:
 ?MAKE:usesocks: Myread Oldconfig Setvar spackage package
 ?MAKE: -pick add \$@ %<
 ?Y:TOP
 ?S:usesocks:
 ?S: This variable conditionally defines the USE_SOCKS symbol,
 ?S: and indicates that Perl should be built to use SOCKS.

?S:
?C:USE_SOCKS:
?C: This symbol, if defined, indicates that Perl should
?C: be built to use socks.

?C:
?H:%<:#\$usesocks USE_SOCKS /**/
?H:
?D:usesocks="
?LINT:set usesocks
: check for requested SOCKS support
case "\$usesocks" in
\$define|true|[yY]*) dflt='y';
*)
dflt='n';
esac
cat <<EOM

\$package can be built to use the SOCKS proxy protocol library.
If this doesn't make any sense to you, just accept the default '\$dflt'.

EOM
rp="Build \$package for SOCKS?"
./myread
case "\$ans" in
y|Y) val="\$define" ;;
*) val="\$undef" ;;
esac
set usesocks
eval \$setvar

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/usesocks.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: End.U,v 3.0 1993/08/18 12:04:51 ram Exp \$
?RCS:
?RCS: Copyright (c) 1991-1993, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 3.0.
?RCS:
?RCS: \$Log: End.U,v \$
?RCS: Revision 3.0 1993/08/18 12:04:51 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:

?X:

?X: This unit serves as the goal which forces make to choose all the units that

?X: ask questions. The \$W on the ?MAKE: line is the list of all symbols wanted.

?X: To force any unit to be included, copy this unit to your private U directory

?X: and add the name of the unit desired to the ?MAKE: dependency line.

?X:

```
?MAKE:End perllibs: $W cppstdin gzip zip
```

```
libs usedl osname osvers
```

```
?MAKE: -pick add $@ %<
```

```
?S:perllibs:
```

```
?S: The list of libraries needed by Perl only (any libraries needed
```

```
?S: by extensions only will be dropped, if using dynamic loading).
```

```
?S:.
```

```
?INIT:perllibs="
```

```
?LINT:use $W
```

```
?LINT:use gzip zip
```

```
?LINT:change cppstdin
```

```
: Remove libraries needed only for extensions
```

```
: The appropriate ext/Foo/Makefile.PL will add them back in, if necessary.
```

```
: The exception is SunOS 4.x, which needs them.
```

```
case "${osname}X${osvers}" in
```

```
sunos*X4*)
```

```
    perllibs="$libs"
```

```
    ;;
```

```
*) case "$usedl" in
```

```
    $define|true[[yY]*)
```

```
        set X `echo " $libs " | sed -e 's@ -lndbm @ @' -e 's@ -lgdbm @ @' -e 's@ -lgdbm_compat @ @' -e 's@ -ldb @ @' -e 's@ -ldb @ @`
```

```
        shift
```

```
        perllibs="$*"
```

```
        ;;
```

```
*) perllibs="$libs"
```

```
        ;;
```

```
esac
```

```
;;
```

```
esac
```

?X: If the user has the cppstdin wrapper, perl.c will try to call

?X: CPPSTDIN, but that will point to a location in the build

?X: directory, not the installed version!. Here, we'll just strip the

?X: name down to 'cppstdin',

and rely on the fact that perl.c will

?X: then call SCRIPTDIR/cppstdin, but local things like 'make depend'

?X: will continue to work.

```
: Remove build directory name from cppstdin so it can be used from
```

```
: either the present location or the final installed location.
```

```
echo " "
```

```
: Get out of the UU directory to get correct path name.
```

```
cd ..
case "$cppstdin" in
`pwd`/cppstdin)
echo "Stripping down cppstdin path name"
cppstdin=cppstdin
;;
esac
cd UU
```

```
: end of configuration questions
echo " "
echo "End of configuration questions."
echo " "
```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/perl/End.U
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: libperl.U,v \$

?RCS:

?RCS: Copyright (c) 1996-1998, Andy Dougherty

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?MAKE:libperl useshrplib shrpenv ldlibpthname: \
Myread Oldconfig archlibexp awk cat libc \
_a osname osvers so patchlevel subversion usedl ld \
ccdflags installarchlib userlocatableinc

?MAKE: -pick wipe \$@ %<

?S:libperl:

?S: The perl executable is obtained by linking perlmain.c with

?S: libperl, any static extensions (usually just DynaLoader),

?S: and any other libraries needed on this system. libperl

?S: is usually libperl.a, but can also be libperl.so.xxx if

?S: the user wishes to build a perl executable with a shared

?S: library.

?S:.

?S:useshrplib:

?S: This variable is set to 'true' if the user wishes

?S: to build a shared libperl, and 'false' otherwise.

?S:.

?S:shrpenv:

?S: If

the user builds a shared libperl.so, then we need to tell the

?S: 'perl' executable where it will be able to find the installed libperl.so.

?S: One way to do this on some systems is to set the environment variable

?S: LD_RUN_PATH to the directory that will be the final location of the
 ?S: shared libperl.so. The makefile can use this with something like
 ?S: \$shrpenv \$(CC) -o perl perlmain.o \$libperl \$libs
 ?S: Typical values are
 ?S: shrpenv="env LD_RUN_PATH=\$archlibexp/CORE"
 ?S: or
 ?S: shrpenv=""
 ?S: See the main perl Makefile.SH for actual working usage.
 ?S: Alternatively, we might be able to use a command line option such
 ?S: as -R \$archlibexp/CORE (Solaris) or -Wl,-rpath
 ?S: \$archlibexp/CORE (Linux).
 ?S:.
 ?S:ldlibpthname:
 ?S: This variable holds the name of the shared library
 ?S: search path, often LD_LIBRARY_PATH. To get an empty
 ?S: string, the hints file must set this to 'none'.
 ?S:.
 ?T:shrpdir majonly majmin also xxx tmp_shrpenv
 ?X: metalint gets confused and thinks we're
 actually setting LDOPTS
 ?X: and LD_RUN_PATH.
 ?LINT:extern LDOPTS
 ?LINT:change LDOPTS
 ?LINT:extern LD_RUN_PATH
 ?LINT:change LD_RUN_PATH
 ?LINT:change ccdlflags
 ?LINT:extern maintloc maintname
 ?Y:top
 : Do we want a shared libperl?
 also=""
 case "\$usedl" in
 \$undef)
 # No dynamic loading being used, so don't bother even to prompt.
 useshrplib='false'
 ;;
 *) case "\$useshrplib" in
 ") case "\$osname" in
 svr4*|nonstopux|dgux|dynixptx|esix|powerux|haiku|cygwin*)
 dflt=y
 also='Building a shared libperl is required for dynamic loading to work on your system.'
 ;;
 *) dflt=n
 ;;
 esac
 ;;
 \$define|true|[Yy]*)
 dflt=y
 ;;

```

*) dflt=n
;;
esac
$cat << EOM

```

The perl executable is normally obtained by linking perlmain.c with libperl\${_a}, any static extensions (usually just DynaLoader), and any other libraries needed on this system (such as -lm, etc.). Since your system supports dynamic loading, it is probably possible to build a shared libperl.\$so. If you will have more than one executable linked to libperl.\$so, this will significantly reduce the size of each executable, but it may have a noticeable effect on performance. The default is probably sensible for your system.

\$also

EOM

```

rp="Build a shared libperl.$so (y/n)"
. ./myread
case "$ans" in
true|define|[Yy]*)
  useshrplib='true' ;;
*) useshrplib='false' ;;
esac
;;
esac

case "$useshrplib" in
true)
  case "$userelocatableinc" in
true|define)
    echo "Cannot build with both -Duserelocatableinc and -Duseshrplib" >&4
    echo "See INSTALL for an explanation why that won't work." >&4
    exit 4
    ;;
esac
case "$libperl" in
")
  # Figure out a good name for libperl.so. Since it gets stored in
  # a version-specific architecture-dependent library, the version
  # number isn't really that important, except for making cc/ld happy.
  #
  # A name such as libperl.so.10.1
  majmin="libperl.$so.$patchlevel.$subversion"
  # A name such as libperl.so.100
  majonly=`echo $patchlevel $subversion |
  $awk '{printf

```

```

"%d%02d", $1, $2}"
majonly=libperl.$so.$majonly
# I'd prefer to keep the os-specific stuff here to a minimum, and
# rely on figuring it out from the naming of libc.
case "${osname}${osvers}" in
*linux*[gnu]*) # ld won't link with a bare -lperl otherwise.
dflt=libperl.$so
;;
cygwin*) # ld links now against the dll directly
majmin="cygperl5_${patchlevel}_${subversion}.${so}"
majonly=`echo $patchlevel $subversion |
$awk '{printf "%03d%03d", $1, $2}'`
majonly=cygperl5.$majonly.$so
dflt=$majmin
;;
*) # Try to guess based on whether libc has major.minor.
case "$libc" in
*libc.$so.[0-9]*.[0-9]*) dflt=$majmin ;;
*libc.$so.[0-9]*) dflt=$majonly ;;
*) dflt=libperl.$so ;;
esac
;;
esac
;;
*) dflt=$libperl
;;
esac
cat << EOM

```

I need to select a good name for the shared libperl. If your system uses library names with major and minor numbers, then you might want something like \$majmin. Alternatively, if your system uses a single version number for shared libraries, then you might want to use \$majonly. Or, your system might be quite happy with a simple libperl.\$so.

Since the shared libperl will get installed into a version-specific architecture-dependent directory, the version number of the shared perl library probably isn't important, so the default should be o.k.

```

EOM
rp='What name do you want to give to the shared libperl?'
./myread
libperl=$ans
echo "Ok, I'll use $libperl"
;;
*)
libperl="libperl${_a}"

```

```
::
esac
```

```
# Detect old use of shrpdir via undocumented Configure -Dshrpdir
```

```
case "$shrpdir" in
```

```
) ;;
```

```
*) $cat >&4 <<EOM
```

```
WARNING: Use of the shrpdir variable for the installation location of
the shared $libperl is not supported. It was never documented and
will not work in this version. Let me (<$maintloc>)
know of any problems this may cause.
```

```
EOM
```

```
case "$shrpdir" in
```

```
"$archlibexp/CORE")
```

```
$cat >&4 <<EOM
```

```
But your current setting of $shrpdir is
the default anyway, so it's harmless.
```

```
EOM
```

```
::
```

```
*)
```

```
$cat >&4
```

```
<<EOM
```

```
Further, your current attempted setting of $shrpdir
conflicts with the value of $archlibexp/CORE
that installperl will use.
```

```
EOM
```

```
::
```

```
esac
```

```
::
```

```
esac
```

```
# How will the perl executable find the installed shared $libperl?
```

```
# Add $xxx to ccdlflags.
```

```
# If we can't figure out a command-line option, use $shrpdir to
```

```
# set env LD_RUN_PATH. The main perl makefile uses this.
```

```
shrpdir=$archlibexp/CORE
```

```
xxx=""
```

```
tmp_shrpdir=""
```

```
if "$useshrplib"; then
```

```
  case "$osname" in
```

```
    aix)
```

```
      # We'll set it in Makefile.SH...
```

```
      ::
```

```
    solaris)
```

```
      xxx="-R $shrpdir"
```

```
      ::
```

```
    freebsd|mirbsd|netbsd|openbsd|interix|dragonfly|bitrig)
```

```

xxx="-Wl,-R$shrpdir"
;;
bsdos|linux|irix*|dec_osf|gnu*|haiku)
xxx="-Wl,-rpath,$shrpdir"
;;
hpux*)
# hpux doesn't like the default, either.
tmp_shrpenv="env LDOPTS=\"+s +b${shrpdir}\""
;;
cygwin)
# cygwin needs only ldlibpth
;;
*)
tmp_shrpenv="env LD_RUN_PATH=$shrpdir"
;;
esac
case "$xxx" in
") ;;
*)
# Only add $xxx if it isn't already in ccdlflags.
case " $ccdlflags
" in
*" $xxx "*) ;;
*) ccdlflags="$ccdlflags $xxx"
cat <<EOM >&4

```

Adding \$xxx to the flags
passed to \$ld so that the perl executable will find the
installed shared \$libperl.

```

EOM
;;
esac
;;
esac
fi
# Fix ccdlflags in AIX for building external extensions.
# (For building Perl itself bare -bE:perl.exp is needed,
# Makefile.SH takes care of this.)
case "$osname" in
aix) ccdlflags="$ccdlflags -bE:$installarchlib/CORE/perl.exp" ;;
esac
# Respect a hint or command-line value.
case "$shrpenv" in
") shrpenv="$tmp_shrpenv" ;;
esac
case "$ldlibpthname" in
") ldlibpthname=LD_LIBRARY_PATH ;;

```

```
none) ldlbpthname=" ;;
esac
```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/perl/libperl.U
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1998 Jarkko Hietaniemi

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?MAKE:d_readv: Inlibc

?MAKE: -pick add \$@ %<

?S:d_readv:

?S: This variable conditionally defines the HAS_READV symbol, which

?S: indicates to the C program that the readv() routine is available.

?S:.

?C:HAS_READV:

?C: This symbol, if defined, indicates that the readv routine is

?C: available to do gather reads. You will also need <sys/uio.h>

?C: and there I_SYSUIO.

?C:.

?H:#\$d_readv HAS_READV /**/

?H:.

?LINT:set d_readv

: see if readv exists

set readv d_readv

eval \$inlibc

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/perl/d_readv.U
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 2001 Jarkko Hietaniemi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 3.0.

?RCS:

```
?MAKE:d_sresgproto: Hasproto i_unistd
?MAKE: -pick add $@ %<
?S:d_sresgproto:
?S: This variable conditionally defines the HAS_SETRESGID_PROTO symbol,
?S: which indicates to the C program that the system provides
?S: a prototype for the setresgid() function. Otherwise, it is
?S: up to the program to supply one.
?S:.
?C:HAS_SETRESGID_PROTO:
?C: This symbol, if defined, indicates that the system provides
?C: a prototype for the setresgid() function. Otherwise, it is up
?C: to the program to supply one. Good guesses are
?C: extern
int setresgid(uid_t ruid, uid_t euid, uid_t suid);
?C:.
?H:#$d_sresgproto HAS_SETRESGID_PROTO /**/
?H:.
?LINT:set d_sresgproto
: see if prototype for setresgid is available
echo " "
set d_sresgproto setresgid $i_unistd unistd.h
eval $hasproto
```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/perl/d_sresgproto.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: d_seteuid.U 1 2006-08-24 12:32:52Z rmanfredi $
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: $Log: d_seteuid.U,v $
?RCS: Revision 3.0 1993/08/18 12:07:08 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:d_seteuid: Inlibc
?MAKE: -pick add $@ %<
?S:d_seteuid:
?S: This variable conditionally defines the HAS_SETEUID symbol, which
?S: indicates to the C program that the seteuid() routine is available
?S: to change the effective uid of the current program.
```

?S:.
?C:HAS_SETEUID (SETEUID):
?C: This symbol, if defined, indicates that the seteuid routine is available
?C: to change the effective uid of the current program.
?C:.
?H:#\$d_seteuid HAS_SETEUID /**/
?H:.
?LINT:set d_seteuid
: see if seteuid exists
set seteuid d_seteuid
eval \$inlibc

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/d_seteuid.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$
?RCS:
?RCS: Copyright (c) 1999 Jarkko Hietaniemi
?RCS:
?RCS: You may distribute under the terms of either the GNU General Public
?RCS: License or the Artistic License, as specified in the README file.
?RCS:
?MAKE:d_hasmntopt: Inlibc
?MAKE: -pick add \$@ %<
?S:d_hasmntopt:
?S: This variable conditionally defines the HAS_HASMNTOPT symbol, which
?S: indicates to the C program that the hasmntopt() routine is available
?S: to query the mount options of file systems.
?S:.
?C:HAS_HASMNTOPT:
?C: This symbol, if defined, indicates that the hasmntopt routine is
?C: available to query the mount options of file systems.
?C:.
?H:#\$d_hasmntopt HAS_HASMNTOPT /**/
?H:.
?LINT:set d_hasmntopt
: see if hasmntopt exists
set hasmntopt d_hasmntopt
eval \$inlibc

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_hasmntopt.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: Cppsym.U,v 3.0.1.5 1995/05/12 11:59:11 ram Exp \$

?RCS:

?RCS: Copyright (c) 1991-1993, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 3.0.

?RCS:

?RCS: \$Log: Cppsym.U,v \$

?RCS: Revision 3.0.1.5 1995/05/12 11:59:11 ram

?RCS: patch54: split awk command onto two lines for older awk's (ADO)

?RCS:

?RCS: Revision 3.0.1.4 1995/01/11 14:55:57 ram

?RCS: patch45: new cc vs. cpp symbol checking suggested by JHI

?RCS: patch45: added more cpp symbols (JHI)

?RCS:

?RCS: Revision 3.0.1.3 1994/10/29 15:51:32 ram

?RCS: patch36: added ?F: line for metalint file checking

?RCS: patch36: new symbols ardent and titan (ADO)

?RCS:

?RCS:

Revision 3.0.1.2 1994/06/20 06:53:32 ram

?RCS: patch30: extended cpp symbol lookup list (JHI)

?RCS: patch30: renamed attrlist symbol into al for brevity

?RCS:

?RCS: Revision 3.0.1.1 1993/12/15 08:14:14 ram

?RCS: patch15: added new cpp symbols __bsdi__ and BSD_NET2

?RCS:

?RCS: Revision 3.0 1993/08/18 12:04:50 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?X: This unit produces a shell script called Cppsym, which can be used to
?X: determine whether any in a list of symbols is defined by the C compilation
?X: chain (C preprocessor symbols plus C compiler native ones).
?X: It can determine the status of any symbol, though the symbols in \$al
?X: are more easily determined. If you want to add to \$al you can do
?X: it in Myinit.U.

?MAKE:Cppsym ccsymbols cppsymbols cppccsymbols: run \
eunicefix Guess awk cat tr sed sort rm rm_try startsh osname \
+cc +gccversion test comm uniq echo Options trnl \
optimize cflags ldflags libs cpp_stuff cpp

?MAKE: -pick add \$@ %<

?T:also

symbols i postprocess_cc_v tHdrH

?X:

?X: The symbol list is in alpha order for ease of maintenance...

?X:
?X: Lots of new symbols (mostly rummaged from gcc), courtesy of
?X: Jarkko Hietaniemi <jhi@snakemail.hut.fi> -- RAM, 06/06/94
?X:
?S:ccsymbols:
?S: The variable contains the symbols defined by the C compiler alone.
?S: The symbols defined by cpp or by cc when it calls cpp are not in
?S: this list, see cppsymbols and cppcsymbols.
?S: The list is a space-separated list of symbol=value tokens.
?S:.
?S:cppsymbols:
?S: The variable contains the symbols defined by the C preprocessor
?S: alone. The symbols defined by cc or by cc when it calls cpp are
?S: not in this list, see ccymbols and cppcsymbols.
?S: The list is a space-separated list of symbol=value tokens.
?S:.
?S:cppcsymbols:
?S: The variable contains the symbols defined by the C compiler
?S: when it calls cpp. The symbols defined by the cc alone or cpp
?S: alone are not in this list, see ccymbols and cppsymbols.
?S: The
list is a space-separated list of symbol=value tokens.
?S:.
?F:./Cppsym
?F:./Cppsym.know
?F:!Cppsym.true
?F:!ccsym.com
?F:!ccsym.cpp
?F:!ccsym.own
?X: fake LINT hints
?LINT:change ccflags
?LINT:extern s
?LINT:extern s__
: Preprocessor symbols
echo " "
\$echo "Guessing which symbols your C compiler and preprocessor define..." >&4
?X: If your symbol is mixed case, just add it as-is.
?X: All symbols will be transformed to both all-lower and all-upper.
?X: Also drop any leading/trailing underscores, the scan will try all those.
\$cat <<'EOSH' > Cppsym.know
a29k aarch64 ABI64 aegis AES_SOURCE AIX AIX32 AIX370 AIX41 AIX42
AIX43 aixpc AIX_SOURCE alliant ALL_SOURCE alpha AM29000 am29000
AMD64 amd64 amiga AMIGAOS AMIX ansi ANSI_C_SOURCE apollo arch_ppc
arch_pwr ardent ARM ARM32 atarist att386 att3b
BeOS BIG_ENDIAN BIT_MSF BSD bsd bsd43 bsd4_2 BSD4_3 bsd4_3 bsd4_4
BSDCOMPAT bsdi BSD_4_3 BSD_4_4 BSD_NET2 BSD_TIME BSD_TYPES bull
byteorder byte_order
c cadmus clang clipper CMU COFF COMPILER_VERSION

concurrent
convex cpu CRAY cray CRAYMPP ctix CX_UX CYGWIN
DECC DGUX DGUX_SOURCE DJGPP dmert DOLPHIN DPX2 DSO Dynix DynixPTX
ELF encore EPI EXTENSIONS
FAVOR_BSD FILE_OFFSET_BITS FORTIFY_SOURCE FreeBSD
GCC_NEW_VARARGS gcos gcx gimpel GLIBC GLIBC_MINOR GNUC GNUMINOR
GNU_LIBRARY GNU_SOURCE GO32 gould GOULD_PN
H3050R H3050RX hbullx20 hcx host_mips hp200 hp300 HP700 hp700
hp800 hp9000 hp9000s200 hp9000s300 hp9000s400 hp9000s500
hp9000s700 hp9000s800 hp9k8 hppa hpux HPUX_SOURCE hp_osf
i186 i286 i386 i486 i586 i686 i8086 i80960 i860 I960 IA32 IA64
iAPX286 ibm ibm032 ibmesa IBMR2 ibmrt ILP32 ILP64
INLINE_INTRINSICS INT64 INTEL interdata INTRINSICS is68k titanium
ksr1
LANGUAGE_C LARGEFILE64_SOURCE LARGEFILE_SOURCE LARGE_FILE_API
LFS64_LARGEFILE LFS_LARGEFILE LIBCATAMOUNT Linux LITTLE_ENDIAN
LONG64 LONGDOUBLE LONGLONG LONG_DOUBLE LONG_LONG LP64 luna
luna88k Lynx
M68000 m68k m88100 m88k M88KBCS_TARGET MACH machine MachTen
MATH_HAS_NO_SIDE_EFFECTS mc300 mc500 mc68000 mc68010 mc68020
mc68030
mc68040 mc68060 mc68k mc68k32 mc700 mc88000 mc88100
merlin mert MiNT mips MIPSEB MIPSEL MIPS_FPSET MIPS_ISA MIPS_SIM
MIPS_SZINT MIPS_SZLONG MIPS_SZPTR MODERN_C motorola mpeix MSDOS
MTXINU MULTIMAX MVS mvs M_AMD64 M_ARM M_ARMT M_COFF M_I186 M_I286
M_I386 M_I8086 M_I86 M_I86SM M_IA64 M_IX86 M_PPC M_SYS3 M_SYS5
M_SYSIII M_SYSV M_UNIX M_X86 M_XENIX
n16 ncl_el ncl_mr NetBSD news1500 news1700 news1800 news1900
news3700 news700 news800 news900 NeXT NLS nonstopux ns16000
ns32000 ns32016 ns32332 ns32k nsc32000
OCS88 OEMVS OpenBSD os OS2 OS390 osf OSF1 OSF_SOURCE
PARAGON parisc pa_risc PA_RISC1_1 PA_RISC2_0 pc532 pdp11 PGC PIC
plexus PORTAR posix POSIX1B_SOURCE POSIX2_SOURCE POSIX4_SOURCE
POSIX_C_SOURCE POSIX_SOURCE POWER powerpc ppc PROTOTYPES PWB pyr
QK_USER QNX
R3000 REENTRANT RES Rhapsody RISC6000 riscix riscos RT
S390 S390x SA110 SCO scs sequent sgi SGI_SOURCE SH SH3 sinix
SIZE_INT SIZE_LONG SIZE_PTR SOCKETS_SOURCE SOCKET_SOURCE sony
sonyrisc sony_news sparc sparclite sparcv8 sparcv9 spectrum
stardent
stdc STDC_EXT stratos sun sun3 sun386 Sun386i svr3 svr4
SVR4_2 SVR4_SOURCE svr5 SX system SYSTYPE_BSD SYSTYPE_BSD43
SYSTYPE_BSD44 SYSTYPE_SVR4 SYSTYPE_SVR5 SYSTYPE_SYSV SYSV SYSV3
SYSV4 SYSV5 sysV68 sysV88
Tek4132 Tek4300 thumb thw_370 thw_intel thw_rs6000 titan TM3200
TM5400 TM5600 tower tower32 tower32_200 tower32_600 tower32_700
tower32_800 tower32_850 tss
u370 u3b u3b2 u3b20 u3b200 u3b20d u3b5 ultrix UMAXV UnicomPBB

```

UnicomPBD UNICOS UNICOSMK unix UNIX95 UNIX99 unixpc unos USE_BSD
USE_FILE_OFFSET64 USE_GNU USE_ISOC9X USE_LARGEFILE
USE_LARGEFILE64 USE_MISC USE_POSIX USE_POSIX199309
USE_POSIX199506 USE_POSIX2 USE_REENTRANT USE_SVID USE_UNIX98
USE_XOPEN USE_XOPEN_EXTENDED USGr4 USGr4_2 UTek Utek UTS UWIN
uxpm uxps
vax venix VMESA vms
x86_64 xenix Xenix286 XOPEN_SOURCE XOPEN_SOURCE_EXTENDED XPG2
XPG2_EXTENDED XPG3 XPG3_EXTENDED XPG4 XPG4_EXTENDED
z8000 zarch
EOSH
# Maybe put other stuff here too.
?X:Some OS's will have a dash in their $osname
?X:e.g. Android is known as linux-android
?X:The
preprocessor will interpret the dash as a minus
./tr '-' '_' <<EOSH >>Cppsym.know
$osname
EOSH
./tr '[a-z]' '[A-Z]' < Cppsym.know > Cppsym.a
./tr '[A-Z]' '[a-z]' < Cppsym.know > Cppsym.b
$cat Cppsym.know > Cppsym.c
$cat Cppsym.a Cppsym.b Cppsym.c | $tr ' ' $trnl | $sort | $uniq > Cppsym.know
$rm -f Cppsym.a Cppsym.b Cppsym.c
cat <<EOSH > Cppsym
$startsh
if $test $# -gt 0; then
    echo $* | $tr " " "$trnl" | ./Cppsym.try > Cppsym.got
    if $test -s Cppsym.got; then
        $rm -f Cppsym.got
    exit 0
    fi
    $rm -f Cppsym.got
    exit 1
else
    $tr " " "$trnl" | ./Cppsym.try
    exit 0
fi
EOSH
chmod +x Cppsym
$eunicefix Cppsym
?X: The below awk script will die a horrible death if
?X: some of the tested symbols are not long ints.
?X: Also, we do not make difference between just defined and defined zero.
cat <<EOSH > Cppsym.try
$startsh
cat <<'EOCP' > try.c
#include <stdio.h>

```

```

#if cpp_stuff == 1
#define STRINGIFY(a)  "a"
#endif
#if cpp_stuff == 42
#define StGiFy(a) #a
#define
  STRINGIFY(a)  StGiFy(a)
#endif
#if $cpp_stuff != 1 && $cpp_stuff != 42
# include "Bleech: How does this C preprocessor stringify macros?"
#endif
int main() {
EOCP
?X: The length($1) command guards against possible empty entries.
?X: The awk snippet is know to give heartburn to UNICOS/mk awk.
$awk \\
EOSH
cat <<'EOSH' >> Cppsym.try
'length($1) > 0 {
  printf "#ifdef %s\nprintf(\"%s=%s\n\", STRINGIFY(%s));\n#endif\n", $1, $1, $1
  printf "#ifdef _%s\nprintf(\"_%s=%s\n\", STRINGIFY(_%s));\n#endif\n", $1, $1, $1
  printf "#ifdef __%s\nprintf(\"__%s=%s\n\", STRINGIFY(__%s));\n#endif\n", $1, $1, $1
  printf "#ifdef __%s__\nprintf(\"__%s__=%s\n\", STRINGIFY(__%s__));\n#endif\n", $1, $1, $1
}' >> try.c
echo 'return 0;}' >> try.c
EOSH
cat <<'EOSH' >> Cppsym.try
cflags="$ccflags"
case "$osname-$gccversion" in
irix-) cflags="\$ccflags -woff 1178" ;;
os2-*) cflags="\$ccflags -Zlinker /PM:VIO" ;;
esac
$cc -o try -Dcpp_stuff=$cpp_stuff $optimize \$cflags $ldflags try.c
$libs 2>/dev/null && $run ./try | $sed 's/ ^\\\\ /g'
EOSH
chmod +x Cppsym.try
$eunicefix Cppsym.try
./Cppsym < Cppsym.know | $sort | $uniq > Cppsym.true
: Add in any Linux cpp "predefined macros":
case "$osname::$gccversion" in
*linux*:*:*|*gnukfreebsd*:*:*|gnu:*:**)
  tHdrH=_tmpHdr
  rm -f $tHdrH.h' $tHdrH
  touch $tHdrH.h'
  # Filter out macro arguments, such as Linux's __INT8_C(c)
  if $cpp -dM $tHdrH.h' > $tHdrH'_cppsym.h' && [ -s $tHdrH'_cppsym.h' ]; then
    sed -e 's/#define[\\ ]*//;s/[\\ ]*$/' -e 's/(.*) <$tHdrH'_cppsym.h' >$tHdrH'_cppsym.real'
    if [ -s $tHdrH'_cppsym.real' ]; then

```

```

cat $tHdrH'_cppsypm.real' Cppsypm.know | sort | uniq | ./Cppsypm | sort | uniq > Cppsypm.true
fi
fi
rm -f $tHdrH'.h' $tHdrH'_cppsypm.h' $tHdrH'_cppsypm.real'
;;
esac
: now check the C compiler for additional symbols
?X: suggested by Jarkko Hietaniemi <jhi@snakemail.hut.fi>, thanks!
postprocess_cc_v="
case "$osname" in
aix) postprocess_cc_v="|str , '
" ;;
esac
$cat >ccsym <<EOS
$startsh
$cat >tmp.c <<EOF
extern int foo;
EOF
for i in ` $cc -v -c tmp.c 2>&1 $postprocess_cc_v `
do
case "$i" in
-D*) echo "$i" | $sed 's/^-D//';;
-A*) $test "$gccversion" && echo "$i" | $sed 's/^-A//' | $sed 's/^(.*)((.*))\1=2/';;
esac
done
$rm_try
EOS
postprocess_cc_v="
chmod +x ccsym
$unicefix ccsym
./ccsym > ccsym1.raw
?X: AIX complains if $uniq is passed an empty file. ($sort apparently
?X: doesn't care.) --AD 14 July 1998
if $test -s ccsym1.raw; then
    $sort ccsym1.raw | $uniq >ccsym.raw
else
    mv ccsym1.raw ccsym.raw
fi

?X: canonicalize symbols for easier sort/uniq/comm usage: append =1 if no = sign
?X: the awk script must be on two lines for older awk programs, sigh! -- ADO
$awk '^=/ { print $0; next }
{ print $0 "=1" }' ccsym.raw >ccsym.list
$comm -13 Cppsypm.true ccsym.list >ccsym.own
$comm -12 Cppsypm.true ccsym.list >ccsym.com
$comm -23 Cppsypm.true ccsym.list >ccsym.cpp
also="
if $test -z ccsym.raw; then

```

```

echo "Your C compiler
doesn't seem to define any symbols!" >&4
echo " "
echo "However, your C preprocessor defines the following symbols:"
$cat Cppsym.true
ccsymbols="
cppsymbols=`$cat Cppsym.true`
cppsymbols=`echo $cppsymbols`
cppccsymbols="$cppsymbols"
else
if $test -s ccsym.com; then
echo "Your C compiler and pre-processor define these symbols:"
$sed -e 's/(.*)=.*/1/' ccsym.com
also='also '
symbols='ones'
cppccsymbols=`$cat ccsym.com`
cppccsymbols=`echo $cppccsymbols`
$test "$$silent" || sleep 1
fi
if $test -s ccsym.cpp; then
$test "$$also" && echo " "
echo "Your C pre-processor ${also}defines the following symbols:"
$sed -e 's/(.*)=.*/1/' ccsym.cpp
also='further '
cppsymbols=`$cat ccsym.cpp`
cppsymbols=`echo $cppsymbols`
$test "$$silent" || sleep 1
fi
if $test -s ccsym.own; then
$test "$$also" && echo " "
echo "Your C compiler ${also}defines the following cpp symbols:"
$sed -e 's/(.*)=1/1/' ccsym.own
$sed -e 's/(.*)=.*/1/' ccsym.own | $uniq
>>Cppsym.true
ccsymbols=`$cat ccsym.own`
ccsymbols=`echo $ccsymbols`
$test "$$silent" || sleep 1
fi
fi

: add -D_FORTIFY_SOURCE if feasible and not already there
case "$gccversion" in
[4567].*) case "$optimize$ccflags" in
*-O*) case "$ccflags$cppsymbols" in
*_FORTIFY_SOURCE=*) # Don't add it again.
echo "You seem to have -D_FORTIFY_SOURCE already, not adding it." >&4
;;
*) echo "Adding -D_FORTIFY_SOURCE=2 to ccflags..." >&4

```

```

ccflags="$ccflags -D_FORTIFY_SOURCE=2"
;;
esac
;;
*) echo "You have gcc 4.* or later but not optimizing, not adding -D_FORTIFY_SOURCE." >&4
;;
esac
;;
*) echo "You seem not to have gcc 4.* or later, not adding -D_FORTIFY_SOURCE." >&4
;;
esac

```

Found in path(s):

```

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/modified/Cppsym.U

```

No license file was found, but licenses were detected in source scan.

```

?RCS: $Id: d_drem.U 1 2006-08-24 12:32:52Z rmanfredi $
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: Original Author: Andy Dougherty <doughera@lafcol.lafayette.edu>
?RCS:
?RCS: $Log: d_drem.U,v $
?RCS: Revision 3.0.1.1 1994/10/29 16:12:14 ram
?RCS: patch36: created by ADO
?RCS:
?MAKE:d_drem: Inlibc
?MAKE:-pick add $@ %<
?S:d_drem:
?S: This variable conditionally defines the HAS_DREM symbol, which
?S: indicates to the C program that the drem() routine is available.
?S:.
?C:HAS_DREM :
?C: This symbol, if defined, indicates that the drem routine is
?C: available.
?C: This routine is roughly the same as fmod, i.e. it
?C: computes the remainder r=x-n*y, where n=rint(x/y), whereas fmod
?C: uses n=trunc(x/y).
?C:.
?H:#$d_drem HAS_DREM /**/
?H:.

```

```
?LINT:set d_drem
: see if drem exists
set drem d_drem
eval $inlibc
```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/d_drem.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: d_tmpnam_r.U,v 0RCS:
```

```
?RCS: Copyright (c) 2002,2003 Jarkko Hietaniemi
```

```
?RCS:
```

```
?RCS: You may distribute under the terms of either the GNU General Public
```

```
?RCS: License or the Artistic License, as specified in the README file.
```

```
?RCS:
```

```
?RCS: Generated by the reentr.pl from the Perl 5.8 distribution.
```

```
?RCS:
```

```
?MAKE:d_tmpnam_r tmpnam_r_proto: Inlibc Protochk Hasproto i_systypes \
  usethreads extern_C
```

```
?MAKE: -pick add $@ %<
```

```
?S:d_tmpnam_r:
```

```
?S: This variable conditionally defines the HAS_TMPNAM_R symbol,
```

```
?S: which indicates to the C program that the tmpnam_r()
```

```
?S: routine is available.
```

```
?S:.
```

```
?S:tmpnam_r_proto:
```

```
?S: This variable encodes the prototype of tmpnam_r.
```

```
?S: It is zero if d_tmpnam_r is undef, and one of the
```

```
?S: REENTRANT_PROTO_T_ABC macros of reentr.h if d_tmpnam_r
```

```
?S: is defined.
```

```
?S:.
```

```
?C:HAS_TMPNAM_R:
```

```
?C: This symbol, if defined, indicates that the tmpnam_r routine
```

```
?C: is available to tmpnam re-entrantly.
```

```
?C:.
```

```
?C:TMPNAM_R_PROTO:
```

```
?C: This
```

```
symbol encodes the prototype of tmpnam_r.
```

```
?C: It is zero if d_tmpnam_r is undef, and one of the
```

```
?C: REENTRANT_PROTO_T_ABC macros of reentr.h if d_tmpnam_r
```

```
?C: is defined.
```

```
?C:.
```

```
?H:#$d_tmpnam_r HAS_TMPNAM_R /**/
```

```
?H:#define TMPNAM_R_PROTO $tmpnam_r_proto /**/
```

```
?H:.
```

```
?T:try hdrs d_tmpnam_r_proto
```

```
: see if tmpnam_r exists
```

```

set tmpnam_r d_tmpnam_r
eval $inlibc
case "$d_tmpnam_r" in
"$define")
hdrs="$i_systypes sys/types.h define stdio.h "
case "$d_tmpnam_r_proto:$usethreads" in
":define") d_tmpnam_r_proto=define
set d_tmpnam_r_proto tmpnam_r $hdrs
eval $hasproto ;;
*) ;;
esac
case "$d_tmpnam_r_proto" in
define)
case "$tmpnam_r_proto" in
"|0) try='char* tmpnam_r(char*);'
./protochk "$extern_C $try" $hdrs && tmpnam_r_proto=B_B ;;
esac
case "$tmpnam_r_proto" in
"|0) d_tmpnam_r=undef
tmpnam_r_proto=0
echo "Disabling tmpnam_r, cannot determine prototype." >&4 ;;
* ) case "$tmpnam_r_proto" in
REENTRANT_PROTO*) ;;
*) tmpnam_r_proto="REENTRANT_PROTO_$tmpnam_r_proto"
;;
esac
echo "Prototype: $try" ;;
esac
;;
*) case "$usethreads" in
define) echo "tmpnam_r has no prototype, not using it." >&4 ;;
esac
d_tmpnam_r=undef
tmpnam_r_proto=0
;;
esac
;;
*) tmpnam_r_proto=0
;;
esac

```

Found in path(s):

```

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/threads/d_tmpnam_r.U

```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_getopt.U 1 2006-08-24 12:32:52Z rmanfredi \$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: \$Log: d_getopt.U,v \$
?RCS: Revision 3.0 1993/08/18 12:06:13 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:d_getopt: Inlibc
?MAKE: -pick add \$@ %<
?S:d_getopt:
?S: This variable conditionally defines the HAS_GETOPT symbol, which
?S: indicates that the getopt() routine exists. The getopt() routine
?S: parses command line options in a standard fashion.
?S:.
?C:HAS_GETOPT (GETOPT):
?C: This symbol, if defined, indicates that the getopt() routine
exists.
?C:.
?H:#\$d_getopt HAS_GETOPT /**/
?H:.
?LINT:set d_getopt
: see if getopt exists
set getopt d_getopt
eval \$inlibc

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/d_getopt.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: spitshell.U 1 2006-08-24 12:32:52Z rmanfredi \$
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: \$Log: spitshell.U,v \$
?RCS: Revision 3.0.1.4 1997/02/28 16:22:12 ram
?RCS: patch61: removed useless chatter as this is now done very early

```

?RCS:
?RCS: Revision 3.0.1.3 1995/01/11 15:37:01 ram
?RCS: patch45: use 'test -f' instead of 'test -r' for exec-only cat progs (WED)
?RCS: patch45: protected "sh -c" within backquotes for Linux and SGI
?RCS:
?RCS: Revision 3.0.1.2 1994/08/29 16:33:00 ram
?RCS: patch32: don't create spitshell under the UU directory
?RCS:
patch32: allow for cat in /bin or /usr/bin
?RCS:
?RCS: Revision 3.0.1.1 1993/09/13 16:12:58 ram
?RCS: patch10: made #-failure message more friendly (WAD)
?RCS:
?RCS: Revision 3.0 1993/08/18 12:09:49 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:spitshell shsharp sharpbang: eunicefix sh Head
?MAKE: -pick add $@ %<
?S:spitshell:
?S: This variable contains the command necessary to spit out a runnable
?S: shell on this system. It is either cat or a grep -v for # comments.
?S:.
?S:shsharp:
?S: This variable tells further Configure units whether your sh can
?S: handle # comments.
?S:.
?S:sharpbang:
?S: This variable contains the string #! if this system supports that
?S: construct.
?S:.
?F:!sharp
?T:xcat p
?X: "paths" comes from Head
?LINT:extern paths _exe
: see if sh knows # comments
?X: This is loaded up early, so avoid being chatty.
?X: echo " "
?X: echo "Checking your $sh to see if it knows about # comments..." >&2
if ` $sh -c '#' >/dev/null 2>&1` ; then
?X: echo
"Your $sh handles # comments correctly."
shsharp=true
spitshell=cat
?X: echo " "
?X: echo "Okay, let's see if #! works on this system..."
xcat=/bin/cat
test -f $xcat$_exe || xcat=/usr/bin/cat
if test ! -f $xcat$_exe; then

```

```

for p in `echo $PATH | sed -e "s/$p_/ /g"` $paths; do
  if test -f $p/cat$_exe; then
    xcat=$p/cat
    break
  fi
done
if test ! -f $xcat$_exe; then
  echo "Can't find cat anywhere!"
  exit 1
fi
fi
echo "#!$xcat" >sharp
$unicefix sharp
chmod +x sharp
./sharp > today 2>/dev/null
if test -s today; then
?X: echo "It does."
  sharpbang=#!'
else
  echo "#! $xcat" > sharp
  $unicefix sharp
  chmod +x sharp
  ./sharp > today 2>/dev/null
  if test -s today; then
?X: echo "It does."
    sharpbang=#!'
  else
?X: echo "Okay, let's see if #! works on this system..."
?X: echo "It's just a comment."
    sharpbang=: use '
  fi
fi
else
  echo " "
  echo "Your $sh doesn't grok # comments--I will strip them later on."
  shsharp=false
?X: The
  spitshell script will be perused, so leave it out the UU directory
  cd ..
  echo "exec grep -v '^[ ]*#' >spitshell
  chmod +x spitshell
  $unicefix spitshell
  spitshell=`pwd`/spitshell
  cd UU
  echo "I presume that if # doesn't work, #! won't work either!"
  sharpbang=: use '
fi
rm -f sharp today

```

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/spitshell.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_setlocale.U 1 2006-08-24 12:32:52Z rmanfredi \$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic Licence,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic Licence; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: Original Author: Andy Dougherty <doughera@lafcol.lafayette.edu>

?RCS:

?RCS: \$Log: d_setlocale.U,v \$

?RCS: Revision 3.0.1.1 1994/06/20 06:57:51 ram

?RCS: patch30: created

?RCS:

?MAKE:d_setlocale: Inlibc

?MAKE: -pick add \$@ %<

?S:d_setlocale:

?S: This variable conditionally defines HAS_SETLOCALE if setlocale() is

?S: available to handle locale-specific ctype implementations.

?S:.

?C:HAS_SETLOCALE:

?C: This symbol, if defined, indicates that the setlocale
routine is

?C: available to handle locale-specific ctype implementations.

?C:.

?H:#\$d_setlocale HAS_SETLOCALE /**/

?H:.

?LINT:set d_setlocale

: see if setlocale exists

set setlocale d_setlocale

eval \$inlibc

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/d_setlocale.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: Setvar.U 1 2006-08-24 12:32:52Z rmanfredi \$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: \$Log: Setvar.U,v \$
?RCS: Revision 3.0.1.1 1994/10/29 15:58:28 ram
?RCS: patch36: call ./whoa explicitly instead of relying on PATH
?RCS:
?RCS: Revision 3.0 1993/08/18 12:05:16 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?X:
?X: This unit produces a variable that is intended to be eval'ed in
?X: order to define/undefine a symbol. A consistency check is made
?X: regarding any previous value and a warning is issued if there
?X: is any discrepancy.
?X:
?X:
To use it, say:
?X: val=<value>
?X: set d_variable
?X: eval \$setvar
?X:
?MAKE:Setvar: Whoa
?MAKE: -pick add \$@ %<
?LINT:define setvar
?S:setvar:
?S: This shell variable is used internally by Configure to set a value
?S: to a given symbol that is defined or not. A typical use is:
?S: val=<value computed>
?S: set d_variable
?S: eval \$setvar
?S: That will print a message in case the \$val value is not the same
?S: as the previous value of \$d_variable.
?S:.
?V:setvar:val
?T:var was td tu
: function used to set '\$1' to '\$val'
setvar='var=\$1; eval "was=\\$1"; td=\$define; tu=\$undef;
case "\$val\$was" in
\$define\$undef) . ./whoa; eval "\$var=\\$td";;
\$undef\$define) . ./whoa; eval "\$var=\\$tu";;
*) eval "\$var=\$val";;
esac'

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/Setvar.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: i_socks.U,v \$

?RCS:

?RCS: Copyright (c) 1999 Jarkko Hietaniemi

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?MAKE:i_socks: Inhdr Hasfield

?MAKE: -pick add \$@ %<

?S:i_socks:

?S: This variable conditionally defines the I_SOCKS symbol, and indicates

?S: whether a C program should include <socks.h>.

?S:.

?C:I_SOCKS:

?C: This symbol, if defined, indicates that <socks.h> exists and

?C: should be included.

?C:.

?H:#\$i_socks I_SOCKS /**/

?H:.

?LINT:set i_socks

: see if this is a socks.h system

set socks.h i_socks

eval \$inhdr

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/i_socks.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_msgsnd.U 1 2006-08-24 12:32:52Z rmanfredi \$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic Licence,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic Licence; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: d_msgsnd.U,v \$

?RCS: Revision 3.0 1993/08/18 12:06:41 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?MAKE:d_msgsnd: Inlibc
?MAKE: -pick add \$@ %<
?S:d_msgsnd:
?S: This variable conditionally defines the HAS_MSGSND symbol, which
?S: indicates to the C program that the msgsnd() routine is available.
?S:.
?C:HAS_MSGSND:
?C: This symbol, if defined, indicates that the msgsnd() routine is
?C: available to send a message into the message queue.
?C:.
?H:#\$d_msgsnd
HAS_MSGSND /**/
?H:.
?LINT:set d_msgsnd
: see if msgsnd exists
set msgsnd d_msgsnd
eval \$inlibc

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/d_msgsnd.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$
?RCS:
?RCS: Copyright (c) 2000 Jarkko Hietaniemi
?RCS:
?RCS: You may distribute under the terms of either the GNU General Public
?RCS: License or the Artistic License, as specified in the README file.
?RCS:
?MAKE:d_isnanl: Inlibc
?MAKE: -pick add \$@ %<
?S:d_isnanl:
?S: This variable conditionally defines the HAS_ISNANL symbol, which
?S: indicates to the C program that the isnanl() routine is available.
?S:.
?C:HAS_ISNANL:
?C: This symbol, if defined, indicates that the isnanl routine is
?C: available to check whether a long double is a NaN.
?C:.
?H:#\$d_isnanl HAS_ISNANL /**/
?H:.
?LINT:set d_isnanl
: see if isnanl exists
set isnanl d_isnanl
eval \$inlibc

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_isnanl.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: manfmt.U 1 2006-08-24 12:32:52Z rmanfredi \$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic Licence,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic Licence; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: manfmt.U,v \$

?RCS: Revision 3.0.1.5 1997/02/28 16:11:57 ram

?RCS: patch61: don't ask for AFS when they choose to not install pages

?RCS:

?RCS: Revision 3.0.1.4 1995/09/25 09:16:52 ram

?RCS: patch59: unit is now forced to the top of Configure, if possible

?RCS:

?RCS: Revision 3.0.1.3 1995/01/30 14:39:20 ram

?RCS: patch49: new installmanfmt and AFS-lookup for formatted man pages

?RCS: patch49: can now handle installation prefix changes (from WED)

?RCS:

?RCS:

Revision 3.0.1.2 1994/08/29 16:30:31 ram

?RCS: patch32: now uses installation prefix for default setting

?RCS:

?RCS: Revision 3.0.1.1 1993/09/13 16:09:22 ram

?RCS: patch10: allows for L1 man page extension (WAD)

?RCS:

?RCS: Revision 3.0 1993/08/18 12:09:13 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?MAKE:manfmt manfmtexp installmanfmt: Getfile Loc Oldconfig cat manext \

spackage Prefixit prefixexp Prefixup afs test

?MAKE: -pick add \$@ %<

?Y:TOP

?S:manfmt:

?S: This variable contains the name of the directory in which formatted

?S: manual pages are to be put. It is the responsibility of the

?S: Makefile.SH to get the value of this into the proper command. Note

?S: that you may have to do ~name substitution. Use manfmtexp otherwise.

?S:.

?S:manfmtexp:

?S: This is the same as the manfmt variable, but is filename expanded

?S: at configuration time, for programs not willing to deal with it at

?S: run-time.

?S:.

?S:installmanfmt:

?S: This variable is really

the same as manfmtexp, unless you are using

?S: AFS in which case it points to the read/write location whereas

?S: mansrcexp only points to the read-only access location. For extra

?S: portability, you should only use this variable within your makefiles.

?S:.

?LINT:change manext

?T:lookpath

: determine where manual pages go

set manfmt manfmt

eval \$prefixit

\$cat <<EOM

\$spackage has pre-formatted manual pages. If you don't want these installed, answer 'none' to the next question.

EOM

case "\$manfmt" in

")

lookpath="\$prefixexp/catman/man1 \$prefixexp/man/cat1"

lookpath="\$lookpath \$prefixexp/catman/u_man/man1"

lookpath="\$lookpath \$prefixexp/catman/l_man/man1"

lookpath="\$lookpath \$prefixexp/catman/cat1 /usr/catman/local/man1"

lookpath="\$lookpath /usr/catman/man1 /usr/man/cat1"

lookpath="\$lookpath /usr/catman/mann /usr/catman/l_man/man1"

lookpath="\$lookpath /usr/catman/u_man/man1 /usr/catman/man1"

dflt=`./loc . none \$lookpath`

set dflt

eval \$prefixup

::

*) dflt="\$manfmt"

::

esac

fn=dn~

rp='Where

do pre-formatted manual pages go?'

./getfile

if test "X\$manfmtexp" != "X\$ansexp"; then

installmanfmt="

fi

manfmt="\$ans"

manfmtexp="\$ansexp"

if \$afs && \$test "\$manfmt"; then

\$cat <<EOM

Since you are running AFS, I need to distinguish the directory in which manual pages reside from the directory in which they are installed (and from which they are presumably copied to the former directory by occult means).

EOM

```
case "$installmanfmt" in
") dflt=`echo $manfmtexp | sed 's#^/afs/#/afs/#^';
*) dflt="$installmanfmt";
esac
fn=de~
rp='Where will pre-formatted man pages be installed?'
./getfile
installmanfmt="$ans"
else
installmanfmt="$manfmtexp"
fi
```

```
case "$manfmt" in
") manext='0';
*l) manext=l;;
*n) manext=n;;
*o) manext=l;;
*p) manext=n;;
*C) manext=C;;
*L) manext=L;;
*L1) manext=L1;;
*) manext=l;;
esac
```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/manfmt.U
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_fchmod.U 1 2006-08-24 12:32:52Z rmanfredi \$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic Licence,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic Licence; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: d_fchmod.U,v \$

?RCS: Revision 3.0 1993/08/18 12:05:59 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?MAKE:d_fchmod: Inlibc
?MAKE: -pick add \$@ %<
?S:d_fchmod:
?S: This variable conditionally defines the HAS_FCHMOD symbol, which
?S: indicates to the C program that the fchmod() routine is available
?S: to change mode of opened files.
?S:.
?C:HAS_FCHMOD (FCHMOD):
?C: This symbol, if defined, indicates that the fchmod routine is available
?C: to
change mode of opened files. If unavailable, use chmod().
?C:.
?H:#\$d_fchmod HAS_FCHMOD /**/
?H:.
?LINT:set d_fchmod
: see if fchmod exists
set fchmod d_fchmod
eval \$inlibc

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/d_fchmod.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: maildir.U 1 2006-08-24 12:32:52Z rmanfredi \$
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: \$Log: maildir.U,v \$
?RCS: Revision 3.0.1.1 1993/12/15 08:21:56 ram
?RCS: patch15: now also looks under /var/mail for BSD/386
?RCS:
?RCS: Revision 3.0 1993/08/18 12:09:09 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:maildir maildirexp: Getfile Loc Oldconfig
?MAKE: -pick add \$@ %<
?S:maildir:
?S: This variable contains the name of the directory in which mail is
?S: spooled. Programs using this variable must be prepared to deal with
?S: ~name

substitutions.

?S:.

?S:mailedir:

?S: This is the same as the maildir variable, but is filename expanded

?S: at configuration time, for programs not willing to deal with it at

?S: run-time.

?S:.

: determine where mail is spooled

case "\$maildir" in

) dflt=`./loc . /usr/spool/mail /usr/spool/mail /usr/mail /var/mail`;;

*) dflt="\$maildir";;

esac

echo " "

fn=d~

rp='Where is yet-to-be-read mail spooled?'

./getfile

maildir="\$ans"

mailedir="\$ansexp"

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/maildir.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1999 Jarkko Hietaniemi

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?MAKE:uidformat: uidsize uidsign ivsize uvsize longsize intsize shortsize \
ivdformat uvuformat test echo

?MAKE: -pick add \$@ %<

?S:uidformat:

?S: This variable contains the format string used for printing a Uid_t.

?S:.

?C:Uid_t_f:

?C: This symbol defines the format string used for printing a Uid_t.

?C:.

?H:#define Uid_t_f \$uidformat /**/

?H:.

: Check format string for UID

echo " "

\$echo "Checking the format string to be used for uids..." >&4

case "\$uidsign" in

-1) if \$test X"\$uidsize" = X"\$ivsize"; then

```

uidformat="$ivdformat"
else
if $test X"$uidsizsize" = X"$longsize"; then
uidformat="ld"
else
if $test X"$uidsizsize" = X"$sintsize"; then
uidformat="d"
else
if $test X"$uidsizsize"
= X"$shortsize"; then
uidformat="hd"
fi
fi
fi
fi
;;
*) if $test X"$uidsizsize" = X"$suvsize"; then
uidformat="$suvuformat"
else
if $test X"$uidsizsize" = X"$longsize"; then
uidformat="lu"
else
if $test X"$uidsizsize" = X"$sintsize"; then
uidformat="u"
else
if $test X"$uidsizsize" = X"$shortsize"; then
uidformat="hu"
fi
fi
fi
fi
;;
esac

```

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/typedefs/uidf.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: Extras.U,v\$

?RCS:

?RCS: Copyright (c) 2001, Jarkko Hietaniemi

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?MAKE:extras: Myread Oldconfig Setvar rm

?MAKE: -pick add \$@ %<

```

?Y:TOP
?S:extras:
?S: This variable holds a list of extra modules to install.
?S:.
: See if we want extra modules installed
echo " "
case "$extras" in
") dflt='n';;
*) dflt='y';;
esac
cat <<EOM

```

Perl can be built with extra modules or bundles of modules which will be fetched from the CPAN and installed alongside Perl.

Notice that you will need access to the CPAN; either via the Internet, or a local copy, for example a CD-ROM or a local CPAN mirror. (You will be asked later to configure the CPAN.pm module which will in turn do the installation of the rest of the extra modules or bundles.)

Notice also that if the modules require any external software such as libraries and headers (the libz library and the zlib.h header for the Compress::Zlib module, for example) you MUST have any such software already installed, this configuration process will NOT install such things for you.

If this doesn't make any sense to you, just accept the default '\$dflt'.

```

EOM
rp='Install any extra modules (y or n)?'
./myread
case "$ans" in
y|Y)
cat <<EOM

```

Please list any extra modules or bundles to be installed from CPAN, with spaces between the names. The names can be in any format the 'install' command of CPAN.pm will understand. (Answer 'none', without the quotes, to install no extra modules or bundles.)

```

EOM
rp='Extras?'
dflt="$extras"
./myread
extras="$ans"
esac
case "$extras" in
'|none')
val=""
$rm -f ../extras.lst

```

```

;;
*) echo "(Saving the list of extras for later...)"
echo "$extras" > ../extras.lst
val="$extras"
;;
esac
set extras
eval $setvar
echo " "

```

Found in path(s):

```

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/perl/Extras.U

```

No license file was found, but licenses were detected in source scan.

```

?RCS: $Id: models.U 1 2006-08-24 12:32:52Z rmanfredi $

```

```

?RCS:

```

```

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

```

```

?RCS:

```

```

?RCS: You may redistribute only under the terms of the Artistic License,

```

```

?RCS: as specified in the README file that comes with the distribution.

```

```

?RCS: You may reuse parts of this distribution only within the terms of

```

```

?RCS: that same Artistic License; a copy of which may be found at the root

```

```

?RCS: of the source tree for dist 4.0.

```

```

?RCS:

```

```

?RCS: $Log: models.U,v $

```

```

?RCS: Revision 3.0.1.2 1997/02/28 16:13:17 ram

```

```

?RCS: patch61: added ?F: metalint hint

```

```

?RCS:

```

```

?RCS: Revision 3.0.1.1 1993/08/25 14:02:39 ram

```

```

?RCS: patch6: added default for large

```

```

?RCS:

```

```

?RCS: Revision 3.0 1993/08/18 12:09:17 ram

```

```

?RCS: Baseline for dist 3.0 netwide release.

```

```

?RCS:

```

```

?MAKE:models split small medium large huge: test cat Myread sysman Oldconfig \

```

```

Loc contains rm

```

```

?MAKE: -pick add $@ %<

```

```

?S:models:

```

```

?S: This variable contains

```

```

the list of memory models supported by this

```

```

?S: system. Possible component values are none, split, unsplit, small,

```

```

?S: medium, large, and huge. The component values are space separated.

```

```

?S:.

```

```

?S:split:

```

```

?S: This variable contains a flag which will tell the C compiler and loader

```

```

?S: to produce a program that will run in separate I and D space, for those

```

```

?S: machines that support separation of instruction and data space. It is

```

?S: up to the Makefile to use this.

?S:.

?S:small:

?S: This variable contains a flag which will tell the C compiler and loader

?S: to produce a program running with a small memory model. It is up to

?S: the Makefile to use this.

?S:.

?S:medium:

?S: This variable contains a flag which will tell the C compiler and loader

?S: to produce a program running with a medium memory model. If the

?S: medium model is not supported, contains the flag to produce large

?S: model programs. It is up to the Makefile to use this.

?S:.

?S:large:

?S: This variable contains a flag

which will tell the C compiler and loader

?S: to produce a program running with a large memory model. It is up to

?S: the Makefile to use this.

?S:.

?S:huge:

?S: This variable contains a flag which will tell the C compiler and loader

?S: to produce a program running with a huge memory model. If the

?S: huge model is not supported, contains the flag to produce large

?S: model programs. It is up to the Makefile to use this.

?S:.

?T:unsplit tans modelcc

?F:!pdp11

?D:large="

?LINT:extern cc

: see what memory models we can support

case "\$models" in

")

?X: We may not use Cppsym or we get a circular dependency through cc.

?X: But this should work regardless of which cc we eventually use.

```
$cat >pdp11.c <<'EOP'
```

```
int main() {
```

```
#ifdef pdp11
```

```
exit(0);
```

```
#else
```

```
exit(1);
```

```
#endif
```

```
}
```

```
EOP
```

?X: Run cc in a subshell in case they don't have a 'cc' command.

?X: Presumably they do have gcc or something.

```
case "$cc" in
```

```
") modelcc="$cc" ;;
```

```
*) modelcc="cc" ;;
```

```

esac
( $modelcc -o pdp11 pdp11.c ) >/dev/null 2>&1
if
$test -f pdp11 && ./pdp11 2>/dev/null; then
  dflt='unsplit split'
else
  tans=`./loc . X /lib/small /lib/large /usr/lib/small /usr/lib/large /lib/medium /usr/lib/medium /lib/huge`
  case "$tans" in
  X) dflt='none';;
  *) if $test -d /lib/small || $test -d /usr/lib/small; then
      dflt='small'
    else
      dflt=""
    fi
    if $test -d /lib/medium || $test -d /usr/lib/medium; then
      dflt="$dflt medium"
    fi
    if $test -d /lib/large || $test -d /usr/lib/large; then
      dflt="$dflt large"
    fi
    if $test -d /lib/huge || $test -d /usr/lib/huge; then
      dflt="$dflt huge"
    fi
  esac
fi;;
*) dflt="$models";;
esac
$cat <<EOM

```

Some systems have different model sizes. On most systems they are called small, medium, large, and huge. On the PDP11 they are called unsplit and split. If your system doesn't support different memory models, say "none". If you wish to force everything to one memory model, say "none" here and put the appropriate flags later when it asks you for other cc and ld flags.

Venix systems may wish to put "none" and let the compiler figure things out. (In the following question multiple model names should be space separated.)

The default for most systems is "none".

```

EOM
rp="Which memory models are supported?"
./myread
models="$ans"

case "$models" in
none)
small=""

```

```

medium="
large="
huge="
unsplit="
split="
;;
*split)
case "$split" in
") if $contains '\-i' $sysman/ld.1 >/dev/null 2>&1 || \
  $contains '\-i' $sysman/cc.1 >/dev/null 2>&1; then
  dflt='-i'
else
  dflt='none'
fi;;
*) dflt="$split";;
esac
rp="What flag indicates separate I and D space?"
./myread
tans="$ans"
case "$tans" in
none) tans="";;
esac
split="$tans"
unsplit="";;
*large*|*small*|*medium*|*huge*)
case "$models" in
*large*)
case "$large" in
") dflt='-Ml';;
*) dflt="$large";;
esac
rp="What flag indicates large model?"
./myread
tans="$ans"
case "$tans" in
none) tans="";;
esac
large="$tans";;
*) large="";;
esac
case "$models"
in
*huge*) case "$huge" in
") dflt='-Mh';;
*) dflt="$huge";;
esac
rp="What flag indicates huge model?"
./myread

```

```

tans="$ans"
case "$tans" in
none) tans="";
esac
huge="$tans";;
*) huge="$large";;
esac
case "$models" in
*medium*) case "$medium" in
") dflt='-Mm';;
*) dflt="$medium";;
esac
rp="What flag indicates medium model?"
./myread
tans="$ans"
case "$tans" in
none) tans="";
esac
medium="$tans";;
*) medium="$large";;
esac
case "$models" in
*small*) case "$small" in
") dflt='none';;
*) dflt="$small";;
esac
rp="What flag indicates small model?"
./myread
tans="$ans"
case "$tans" in
none) tans="";
esac
small="$tans";;
*) small="";;
esac
;;
*)
echo "Unrecognized memory models--you may have to edit Makefile.SH" >&4
;;
esac
$rm -f pdp11.* pdp11

```

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/modified/models.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: Init.U,v 3.0.1.1 1994/10/31 09:45:59 ram Exp \$

?RCS:
?RCS: Copyright (c) 1991-1993, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 3.0.
?RCS:
?RCS: \$Log: Init.U,v \$
?RCS: Revision 3.0.1.1 1994/10/31 09:45:59 ram
?RCS: patch44: removed Options from MAKE to prevent Init overrides
?RCS: patch44: option processing now done after Myinit thanks to new Begin.U
?RCS: patch44: moved "Beginning of configuration questions" to Begin.U
?RCS: patch44: moved signal trapping instruction to Begin.U as well
?RCS:
?RCS: Revision 3.0 1993/08/18 12:05:02 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?X:
?X: This file
initializes certain default variables used by Configure. They
?X: may be overridden or added to by definitions in Myinit.U.
?X:
?MAKE:Init eunicefix: Null
?MAKE: -pick add \$@ %<
?MAKE: -pick weed \$@ ./Init
?S:eunicefix:
?S: When running under Eunice this variable contains a command which will
?S: convert a shell script to the proper form of text file for it to be
?S: executable by the shell. On other systems it is a no-op.
?S:.
?V:define undef smallmach:rmlist
?X:
?X: Throughout the units, one may make use of \$define and \$undef to reference
?X: a defined symbol or an undefined one. There is no need to add them in
?X: the dependency line since this unit makes them visible via ?V:, and
?X: everyone inherits from those symbols since by convention Init.U is the
?X: root dependency.
?X:
?LINT:extern DJGPP
?LINT:extern _exe
?LINT:change _exe
?LINT:extern is_os2
: Detect odd OSs
define='define'
undef='undef'
smallmach='pdp11 i8086 z8000 i80286 iAPX286'

rmlist="

: We must find out about

Eunice early

eunicefix=':'

if test -f /etc/unixtovms; then

eunicefix=/etc/unixtovms

fi

if test -f /etc/unixtovms.exe; then

eunicefix=/etc/unixtovms.exe

fi

: Set executable suffix now -- needed before hints available

if test -f "/libs/version.library"; then

: Amiga OS

_exe=""

elif test -f "/system/gnu_library/bin/ar.pm"; then

: Stratus VOS

_exe=".pm"

elif test -n "\$DJGPP"; then

: DOS DJGPP

_exe=".exe"

elif test -f /kern/cookiejar; then

: MiNT

_exe=""

elif test -d c:/ -o -n "\$is_os2" ; then

: OS/2 or cygwin

_exe=".exe"

fi

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/modified/Init.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 2000 Jarkko Hietaniemi

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?MAKE:d_getcwd: Inlibc

?MAKE: -pick add \$@ %<

?S:d_getcwd:

?S: This variable conditionally defines the HAS_GETCWD symbol, which

?S: indicates to the C program that the getcwd() routine is available

?S: to get the current working directory.

?S:
?C:HAS_GETCWD :
?C: This symbol, if defined, indicates that the getcwd routine is
?C: available to get the current working directory.

?C:
?H:#\$d_getcwd HAS_GETCWD /**/

?H:
?LINT:set d_getcwd
: see if getcwd exists
set getcwd d_getcwd
eval \$inlibc

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_getcwd.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_getspnam_r.U,v 0RCS:

?RCS: Copyright (c) 2002,2003 Jarkko Hietaniemi

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?RCS: Generated by the reentr.pl from the Perl 5.8 distribution.

?RCS:

?MAKE:d_getspnam_r getspnam_r_proto: Inlibc Protochk Hasproto i_systypes \
usethreads i_shadow extern_C

?MAKE: -pick add \$@ %<

?S:d_getspnam_r:

?S: This variable conditionally defines the HAS_GETSPNAM_R symbol,

?S: which indicates to the C program that the getspnam_r()

?S: routine is available.

?S:

?S:getspnam_r_proto:

?S: This variable encodes the prototype of getspnam_r.

?S: It is zero if d_getspnam_r is undef, and one of the

?S: REENTRANT_PROTO_T_ABC macros of reentr.h if d_getspnam_r

?S: is defined.

?S:

?C:HAS_GETSPNAM_R:

?C: This symbol, if defined, indicates that the getspnam_r routine

?C: is available

to getspnam re-entrantly.

?C:

?C:GETSPNAM_R_PROTO:

?C: This symbol encodes the prototype of getspnam_r.

?C: It is zero if d_getspnam_r is undef, and one of the

?C: REENTRANT_PROTO_T_ABC macros of reentr.h if d_getspnam_r

```

?C: is defined.
?C:.
?H:#$d_getspnam_r HAS_GETSPNAM_R /**/
?H:#define GETSPNAM_R_PROTO $getspnam_r_proto /**/
?H:.
?T:try hdrs d_getspnam_r_proto
: see if getspnam_r exists
set getspnam_r d_getspnam_r
eval $inlibc
case "$d_getspnam_r" in
"$define")
hdrs="$i_systypes sys/types.h define stdio.h $i_shadow shadow.h"
case "$d_getspnam_r_proto:$usetthreads" in
":define") d_getspnam_r_proto=define
set d_getspnam_r_proto getspnam_r $hdrs
eval $hasproto ;;
*) ;;
esac
case "$d_getspnam_r_proto" in
define)
case "$getspnam_r_proto" in
"|0) try='int getspnam_r(const char*, struct spwd*, char*, size_t, struct spwd**);'
./protochk "$extern_C $try" $hdrs && getspnam_r_proto=I_CSBWR ;;
esac
case "$getspnam_r_proto" in
"|0) try='struct spwd* getspnam_r(const char*,
struct spwd*, char*, int);'
./protochk "$extern_C $try" $hdrs && getspnam_r_proto=S_CSBI ;;
esac
case "$getspnam_r_proto" in
"|0) d_getspnam_r=undef
getspnam_r_proto=0
echo "Disabling getspnam_r, cannot determine prototype." >&4 ;;
* ) case "$getspnam_r_proto" in
REENTRANT_PROTO*) ;;
*) getspnam_r_proto="REENTRANT_PROTO_$getspnam_r_proto" ;;
esac
echo "Prototype: $try" ;;
esac
;;
*) case "$usetthreads" in
define) echo "getspnam_r has no prototype, not using it." >&4 ;;
esac
d_getspnam_r=undef
getspnam_r_proto=0
;;
esac
;;

```

```
*) getspname_r_proto=0
```

```
::
```

```
esac
```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/threads/d_getspnam_r.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: d_tzmin.U 1 2006-08-24 12:32:52Z rmanfredi $
```

```
?RCS:
```

```
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
```

```
?RCS:
```

```
?RCS: You may redistribute only under the terms of the Artistic Licence,
```

```
?RCS: as specified in the README file that comes with the distribution.
```

```
?RCS: You may reuse parts of this distribution only within the terms of
```

```
?RCS: that same Artistic Licence; a copy of which may be found at the root
```

```
?RCS: of the source tree for dist 4.0.
```

```
?RCS:
```

```
?RCS: $Log: d_tzmin.U,v $
```

```
?RCS: Revision 3.0.1.1 1994/10/29 16:16:58 ram
```

```
?RCS: patch36: call ./bsd explicitly instead of relying on PATH
```

```
?RCS:
```

```
?RCS: Revision 3.0 1993/08/18 12:07:49 ram
```

```
?RCS: Baseline for dist 3.0 netwide release.
```

```
?RCS:
```

```
?MAKE:d_tzmin: contains cppstdin cppminus timeincl rm Setvar Guess
```

```
?MAKE: -pick add $@ %<
```

```
?S:d_tzmin:
```

```
?S: This symbol conditionally defines TZ_MINUTESWEST if the system uses
```

```
?S: tz_minuteswest in time header instead of timezone.
```

```
?S:.
```

```
?C:TZ_MINUTESWEST:
```

```
?C: This
```

```
symbol is defined if this system uses tz_minuteswest
```

```
?C: in time header instead of timezone.
```

```
?C: If not defined, you may have to use struct timeb and ftime() rather
```

```
?C: than the new gettimeofday() system call.
```

```
?C:.
```

```
?H:#$d_tzmin TZ_MINUTESWEST /**/
```

```
?H:.
```

```
?LINT:set d_tzmin
```

```
: see if tz_minuteswest is defined in time header
```

```
echo " "
```

```
val="$undef"
```

```
$cppstdin $cppminus < $timeincl > try 2>&1
```

```
if $contains 'tz_minuteswest' try >/dev/null 2>&1; then
```

```
echo "You have tz_minuteswest defined in $timeincl rather than timezone." >&4
```

```

val="$define"
elif $contains 'timezone' try >/dev/null 2>&1; then
echo "You have timezone defined in $timeincl rather than tz_minuteswest." >&4
else
echo "Your $timeincl file looks strange." >&4
fi
if ./bsd; then
case "$d_tzmin" in
"$undef") echo "(Maybe your system is an USG one after all?)";;
esac
fi
set d_tzmin
eval $setvar
$rm -f try

```

Found in path(s):

```

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/d_tzmin.U

```

No license file was found, but licenses were detected in source scan.

?RCS:

?RCS: Copyright (c) 2012 Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic Licence,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic Licence; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?MAKE:ilp d_ilp32 d_ilp64 d_lp64 d_can64: Assert Myread Setvar \

cat rm +cc +ccflags echo n c intsize longsize ptrsize

?MAKE: -pick add \$@ %<

?S:ilp:

?S: This variable contains the largest amount of bits that the CPU supports,

?S: from the compiler's point of view. Typically 32 or 64.

?S:.

?S:d_ilp32:

?S: This variable conditionally defines the CPU_IS_ILP32.

?S:.

?S:d_ilp64:

?S: This variable conditionally defines the CPU_IS_ILP64.

?S:.

?S:d_lp64:

?S: This variable conditionally defines the CPU_IS_LP64.

?S:.

?S:d_can64:

?S: This variable

conditionally defines CAN_HANDLE_64BITS.

?S:.

?C:CPU_ILP_MAXBITS:

?C: This symbol contains the largest amount of bits that the CPU natively supports from the compiler's point of view. Typically 32 or 64.

?C:.

?C:CPU_IS_ILP32:

?C: When defined, this indicates that the integer, long and pointer variables hold 32-bit values.

?C:.

?C:CPU_IS_ILP64:

?C: When defined, this indicates that the integer, long and pointer variables hold 64-bit values.

?C:.

?C:CPU_IS_LP64:

?C: When defined, this indicates that the long and pointer variables hold 64-bit values but integers are smaller (probably only 32-bit wide).

?C:.

?C:CAN_HANDLE_64BITS:

?C: When defined, this indicates that the compiler can handle 64-bit values despite the CPU having only 32-bit registers. These are available using the "long long" C type. It is only defined for ILP32 machines, since 64-bit support is naturally available on ILP64 and LP64 machines.

?C:.

?H:#define CPU_ILP_MAXBITS \$ilp

?H:#\$d_ilp32

CPU_IS_ILP32 /**/

?H:#\$d_ilp64 CPU_IS_ILP64 /**/

?H:#\$d_lp64 CPU_IS_LP64 /**/

?H:#\$d_can64 CAN_HANDLE_64BITS /**/

?H:.

?LINT: set d_ilp32 d_ilp64 d_lp64 d_can64

: check for architecture type

echo " "

\$echo \$n "Computing CPU architecture type...\$c" >&4

ilp=`expr \$longsize * 8`

case "\$ptrsize" in

8)

val=\$undef; set d_ilp32; eval \$setvar

case "\$intsize" in

8)

echo " ILP64." >&4

val=\$define; set d_ilp64; eval \$setvar

val=\$undef; set d_lp64; eval \$setvar

::

*)

echo " LP64." >&4

val=\$define; set d_lp64; eval \$setvar

```

    val=$undef; set d_ilp64; eval $setvar
    ;;
esac
;;
*)
echo " ILP${ilp}." >&4
case "$ilp" in
32) val=$define;;
*) val=$undef;;
esac
set d_ilp32; eval $setvar
val=$undef; set d_ilp64; eval $setvar
val=$undef; set d_lp64; eval $setvar
;;
esac

@if CAN_HANDLE_64BITS || d_can64
: see whether compiler supports 64-bit emulation
val=$undef
case "$ilp" in
64) val=$define;;
*)
$cat >try.c <<EOCP
#include "static_assert.h"
long long foo;
int main()
{
    STATIC_ASSERT(8
    == sizeof(foo));
    return 0;
}
EOCP
if $cc -c $ccflags try.c >/dev/null 2>&1; then
    echo " "
    echo "Your compiler also supports 64-bit emulation." >&4
    val=$define
fi
$rm -f try.*
;;
esac
set d_can64
eval $setvar

@end

```

Found in path(s):

```

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/ilp.U

```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: d_setpwent.U,v $
?RCS:
?RCS: Copyright (c) 1998 Andy Dougherty
?RCS:
?RCS: You may distribute under the terms of either the GNU General Public
?RCS: License or the Artistic License, as specified in the README file.
?RCS:
?RCS: $Log: d_setpwent.U,v $
?RCS:
?MAKE:d_setpwent: Inlibc
?MAKE: -pick add $@ %<
?S:d_setpwent:
?S: This variable conditionally defines the HAS_SETPWENT symbol, which
?S: indicates to the C program that the setpwent() routine is available
?S: for initializing sequential access to the passwd database.
?S:.
?C:HAS_SETPWENT:
?C: This symbol, if defined, indicates that the setpwent routine is
?C: available for initializing sequential access of the passwd database.
?C:.
?H:#$d_setpwent HAS_SETPWENT /**/
?H:.
?LINT:set d_setpwent
: see if setpwent exists
set setpwent d_setpwent
eval $inlibc
```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/modified/d_setpwent.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: i_unistd.U 1 2006-08-24 12:32:52Z rmanfredi $
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: $Log: i_unistd.U,v $
?RCS: Revision 3.0 1993/08/18 12:08:46 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
```

?MAKE:i_unistd: Inhdr
?MAKE: -pick add \$@ %<
?S:i_unistd:
?S: This variable conditionally defines the I_UNISTD symbol, and indicates
?S: whether a C program should include <unistd.h>.
?S:.
?C:I_UNISTD:
?C: This symbol, if defined, indicates to the C program that it should
?C: include <unistd.h>.
?C:.
?H:#\$i_unistd I_UNISTD /**/
?H:.
?LINT:set
i_unistd
: see if this is a unistd.h system
set unistd.h i_unistd
eval \$inhdr

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/i_unistd.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: install.U 1 2006-08-24 12:32:52Z rmanfredi \$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic Licence,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic Licence; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: install.U,v \$

?RCS: Revision 3.0.1.2 1995/09/25 09:16:37 ram

?RCS: patch59: all possible install programs are now looked for

?RCS:

?RCS: Revision 3.0.1.1 1995/01/11 15:30:41 ram

?RCS: patch45: created

?RCS:

?MAKE:install installdir: Loc Oldconfig Getfile cat test startsh rm +cc \
eunicefix package contains mkdir echo n c

?MAKE: -pick add \$@ %<

?S:install:

?S: This variable contains the name of an install program that can accept

?S: BSD-style arguments.

It must correctly support -c, -s, and -m at least.

?S: It is a fully qualified pathname when found. If you have a local

?S: install.SH file at the root directory of your package, it is assumed to
?S: be the default script emulating a BSD install and the variable will be
?S: set to ./install. Otherwise, it is set to plain 'install', relying on
?S: the user's PATH to perform miracles.

?S:.

?S:installdir:

?S: This variable contains the name of a program that can install nested
?S: directories. Often set to 'mkdir -p', it can also be 'install -d' if
?S: you have such a beast and lack the former. If you have an install.SH
?S: file at the root directory of your package, it will be used in last
?S: resort, setting the variable to './install -d'. Otherwise, it is set to
?S: plain 'mkdir', and cross your fingers!

?S:.

?T:dir file tryit prog creatdir either

?F:!tryinst

: locate a BSD compatible install program

echo " "

echo "Looking for a BSD-compatible install program..." >&4

@if installdir

creatdir="

@end

case

"\$install" in

")

tryit="

for dir in \$pth; do

for file in ginstall installbsd scoinst install; do

if \$test -f \$dir/\$file; then

tryit="\$stryit \$dir/\$file"

fi

done

done

\$cat >try.c <<EOC

int main()

{

printf("OK\n");

exit(0);

}

EOC

if \$cc -o try try.c >/dev/null 2>&1; then

cp try try.ns

strip try >/dev/null 2>&1

else

echo "(I can't seem to compile a trivial C program -- bypassing.)"

echo "try" >try

cp try try.ns

fi

\$cat >tryinst <<EOS

```

$startsh
$rm -rf foo d
@if installdir
\ $1 -d foo/bar
@end
$mkdir d
\ $1 -c -m 764 try.ns d
\ $1 -c -s -m 642 try.ns d/try
EOS
chmod +x tryinst
$eunicefix tryinst
dflt=""
either=""
for prog in $tryit; do
  $echo $n "Checking $prog... $c"
  ./tryinst $prog >/dev/null 2>&1
@if installdir
  if $test -d foo/bar; then
    creatdir="$prog -d"
  fi
@end
  (ls -l d/try >try.ls; ls -l d/try.ns >tryno.ls) 2>/dev/null
  if (cmp -s d/try try && cmp -s d/try.ns try.ns && \
    $contains 'rwxrw-r--' tryno.ls && \
    \
    $contains 'rw-r---w-' try.ls) >/dev/null 2>&1
  then
    dflt="$prog"
    echo "ok, that will do."
    break
  fi
  echo "not good$either."
  either='either'
  $rm -f try*.ls
done
$rm -rf foo d tryinst try try*.ls try.*
case "$dflt" in
  ")
@if { test -f ../install.SH }
  echo "Hopefully, $package comes with its own install script!"
  dflt='./install'
@else
  dflt='install'
@end
  ;;
esac
  ;;
*) dflt="$install";;

```

```
esac
$cat <<EOM
```

I will be requiring a BSD-compatible install program (one that allows options like -s to strip executables or -m to specify a file mode) to install \$package.

If the question below contains a fully qualified default path, then it is probably ok. If it is an unqualified name such as 'install', then it means I was unable to find out a good install program I could use. If

```
@if {test -f ../install.SH}
```

you know of one, please tell me about it. If the default is './install', then I shall be using the install script supplied with \$package.

```
@else
```

you know of one,

please tell me about it.

```
@end
```

```
EOM
```

```
@if {test -f ../install.SH}
```

```
fn='/fe~(install,./install)'
```

```
@else
```

```
fn='/fe~(install)'
```

```
@end
```

```
rp='Which install program shall I use?'
```

```
./getfile
```

```
install="$ans"
```

```
@if installdir
```

```
: how can we create nested directories?
```

```
echo " "
```

```
echo "Ok, let's see how we can create nested directories..." >&4
```

```
case "$installdir" in
```

```
  ")
```

```
?X: First time, maybe we already found out a working one in $creatdir above...
```

```
?X: Prefer "mkdir -p" because of bugs in GNU install when not running as root
```

```
$mkdir -p foo/bar >/dev/null 2>&1
```

```
if $test -d foo/bar; then
```

```
  echo "Great, we can build them using 'mkdir -p'."
```

```
  creatdir='mkdir -p'
```

```
else
```

```
  case "$creatdir" in
```

```
    ")
```

```
    if eval "$install -d foo/bar"; $test -d foo/bar; then
```

```
      creatdir="install -d"
```

```
      echo "It looks like '$creatdir' will do it for us."
```

```
    fi
```

```
  ;;
```

```

*)
eval "$creatdir foo/bar" >/dev/null 2>&1
if $test -d foo/bar; then
    echo "Ah! We can use '$creatdir' to do just that."
else
    creatdir="
fi
;;
esac
fi
$rm
-rf foo
case "$creatdir" in
")
    echo "Heck! Another ancient system lacking the comfort of modern ones!"
@if {test -f ../install.SH}
    echo "You can thank $package for bringing you its own install script!"
    installdir='./install -d'
@else
    echo "We have no choice but to use plain old 'mkdir' -- wish me luck!"
    installdir=mkdir
@end
;;
*) installdir="$creatdir";;
esac
;;
*) echo "As you already told me, '$installdir' should work.";;
esac

@end

```

Found in path(s):

```

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/install.U

```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1999 Jarkko Hietaniemi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 3.0.

?RCS:

?MAKE:siteman1 siteman1exp installsiteman1: test Getfile Setprefixvar \

prefix siteprefix man1dir sed

```

?MAKE: -pick add $@ %<
?Y:TOP
?D:siteman1="
?S:siteman1:
?S: This variable contains the name of the directory in which site-specific
?S: manual source pages are to be put. It is the responsibility of the
?S: Makefile.SH to get the value of this into the proper command.
?S: You must be prepared to do the ~name expansion yourself.
?S: The standard distribution will put nothing in this directory.
?S: After perl has been installed,
    users may install their own local
?S: man1 pages in this directory with
?S: MakeMaker Makefile.PL
?S: or equivalent. See INSTALL for details.
?S:.
?D:siteman1exp="
?S:siteman1exp:
?S: This variable is the same as the siteman1 variable, but is filename
?S: expanded at configuration time, for convenient use in makefiles.
?S:.
?D:installsiteman1="
?S:installsiteman1:
?S: This variable is really the same as siteman1exp, unless you are using
?S: AFS in which case it points to the read/write location whereas
?S: man1direxp only points to the read-only access location. For extra
?S: portability, you should only use this variable within your makefiles.
?S:.
?LINT:change prefixvar
?LINT:set installsiteman1
?LINT:set siteman1exp
: determine where add-on manual pages go
case "$siteman1" in
") dflt=`echo "$man1dir" | $sed "s#^$prefix#$siteprefix#" ` ;;
*) dflt=$siteman1 ;;
esac
case "$dflt" in
"| ") dflt=none ;;
esac
fn=dn+~
rp='Pathname where the site-specific manual pages should
be installed?'
./getfile
prefixvar=siteman1
./setprefixvar
: Use ' ' for none so value is preserved next time through Configure
$test X"$siteman1" = "X" && siteman1=' '

```

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/installdirs/siteman1.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: Findhdr.U,v 3.0.1.2 1994/10/29 15:53:08 ram Exp \$

?RCS:

?RCS: Copyright (c) 1991-1993, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 3.0.

?RCS:

?RCS: Original Author: Thomas Neumann <tom@smart.bo.open.de>

?RCS:

?RCS: \$Log: Findhdr.U,v \$

?RCS: Revision 3.0.1.2 1994/10/29 15:53:08 ram

?RCS: patch36: added ?F: line for metalint file checking

?RCS:

?RCS: Revision 3.0.1.1 1994/05/06 14:03:56 ram

?RCS: patch23: cppminus must be after other cppflags, not before

?RCS:

?RCS: Revision 3.0 1993/08/18 12:04:54 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?X:

?X: This unit produces a findhdr script which

is used to locate the header

?X: files in \$usrinc or other stranger places using cpp capabilities. The

?X: script is given an include file base name, like 'stdio.h' or 'sys/file.h'

?X: and it returns the full path of the include file and a zero status or an

?X: empty string with an error status if the file could not be located.

?X:

?MAKE:Findhdr: grep test tr rm incpth awk cat startsh \
cppstdin cppminus +cppflags osname

?MAKE: -pick add \$@ %<

?MAKE: -pick add \$@ %<

?LINT:extern cppfilter

?LINT:define fieldn

?S:fieldn:

?S: This variable is used internally by Configure. It contains the position

?S: of the included file name in cpp output. That is to say, when cpp

?S: pre-processes a #include <file> line, it replaces it by a # line which

?S: contains the original position in the input file and the full name of

?S: included file, between "quotes".

?S:.

?V:fieldn

?F:./findhdr !fieldn

```

?T:cline pos wanted name awkprg usrinmdir status testaccess
: determine filename position in cpp output
echo " "
echo "Computing
filename position in cpp output for #include directives..." >&4
case "$osname" in
amigaos) fieldn=3 ;; # Workaround for a bug in abc (pdksh).
esac
case "$fieldn" in
")
case "$osname" in
vos) testaccess=-e ;;
*) testaccess=-r ;;
esac
echo '#include <stdio.h>' > foo.c
$cat >fieldn <<EOF
$startsh
$cppstdin $cppflags $cppminus <foo.c 2>/dev/null | \
$grep '^[ ]*#.*stdio.h' | \
while read cline; do
pos=1
set \ $cline
while $test \ $# -gt 0; do
if $test $testaccess \ `echo \ $1 | $tr -d ""`; then
echo "\ $pos"
exit 0
fi
shift
pos=\ `expr \ $pos + 1`
done
done
EOF
chmod +x fieldn
fieldn=`./fieldn`
$rm -f foo.c fieldn
;;
esac
case $fieldn in
") pos='???';;
1) pos=first;;
2) pos=second;;
3) pos=third;;
*) pos="{fieldn}th";;
esac
echo "Your cpp writes the filename in the $pos field of the line."

```

?X: To locate a header file, we cannot simply check for \$usrinc/file.h, since
?X: some machine have the headers in weird places and our only hope is that

```

?X: the C pre-processor
will know how to find those headers. Thank you Next!
: locate header file
$cat >findhdr <<EOF
$startsh
wanted=\$1
name=""
for usrinmdir in $incpth
do
if test -f \$usrinmdir/\$wanted; then
echo "\$usrinmdir/\$wanted"
exit 0
fi
done
awkprg='{ print \$$fieldn }'
echo "#include <\$wanted>" > foo\$\$.c
$cpptest $cpptestminus $cpptestflags < foo\$\$.c 2>/dev/null | \
$cpptestfilter $grep "^[ ]*#.*\$wanted" | \
while read cline; do
name=\`echo \$cline | $awk "\$awkprg" | $str -d ""\`
case "\$name" in
*[\|\\]\$wanted) echo "\$name"; exit 1;;
*[\|\\]\$wanted) echo "\$name"; exit 1;;
*) exit 2;;
esac;
done;
#
# status = 0: grep returned 0 lines, case statement not executed
# status = 1: headerfile found
# status = 2: while loop executed, no headerfile found
#
status=\$?
$rm -f foo\$\$.c;
if test \$status -eq 1; then
exit 0;
fi
exit 1
EOF
chmod +x findhdr

```

Found in path(s):

```

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/modified/Findhdr.U

```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_gethbyad.U,v \$

?RCS:

?RCS: Copyright (c) 1998 Andy Dougherty

?RCS:
?RCS: You may distribute under the terms of either the GNU General Public
?RCS: License or the Artistic License, as specified in the README file.
?RCS:
?MAKE:d_gethbyaddr: Inlibc
?MAKE: -pick add \$@ %<
?S:d_gethbyaddr:
?S: This variable conditionally defines the HAS_GETHOSTBYADDR symbol, which
?S: indicates to the C program that the gethostbyaddr() routine is available
?S: to look up hosts by their IP addresses.
?S:.
?C:HAS_GETHOSTBYADDR:
?C: This symbol, if defined, indicates that the gethostbyaddr() routine is
?C: available to look up hosts by their IP addresses.
?C:.
?H:#\$d_gethbyaddr HAS_GETHOSTBYADDR /**/
?H:.
?LINT:set d_gethbyaddr
: see if gethostbyaddr exists
set gethostbyaddr d_gethbyaddr
eval \$inlibc

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/modified/d_gethbyad.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$
?RCS:
?RCS: Copyright (c) 1999, Jarkko Hietaniemi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 3.0.
?RCS:
?MAKE:d_timer_gettime: Inlibc
?MAKE: -pick add \$@ %<
?S:d_timer_gettime:
?S: This variable conditionally defines HAS_TIMER_GETTIME
?S: if timer_gettime() is available to get the time of a POSIX timer.
?S:.
?C:HAS_TIMER_GETTIME:
?C: This symbol, if defined, indicates that the timer_gettime
?C: system call is available to get the time of a POSIX timer.
?C:.
?H:#\$d_timer_gettime HAS_TIMER_GETTIME /**/

```
?H:
?LINT:set d_timer_gettime
: see if timer_gettime exists
set timer_gettime d_timer_gettime
eval $inlibc
```

Found in path(s):

*

```
/opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/perl/d_timer_gettime.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: bin.U,v 3.1 1999/07/09 18:20:13 doughera Exp doughera $
?RCS:
?RCS: Copyright (c) 1991-1993, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 3.0.
?RCS:
?RCS: $Log: bin.U,v $
?RCS: Revision 3.1 1999/07/09 18:20:13 doughera
?RCS: Updated for installprefix
?RCS:
?RCS: Revision 3.0.1.4 1995/09/25 09:15:32 ram
?RCS: patch59: unit is now forced to the top of Configure, if possible
?RCS:
?RCS: Revision 3.0.1.3 1995/01/30 14:32:40 ram
?RCS: patch49: can now handle installation prefix changes (from WED)
?RCS:
?RCS: Revision 3.0.1.2 1994/08/29 16:05:28 ram
?RCS: patch32: now uses installation prefix
?RCS:
?RCS:
Revision 3.0.1.1 1993/09/13 15:56:51 ram
?RCS: patch10: made prompting more explicit (WAD)
?RCS:
?RCS: Revision 3.0 1993/08/18 12:05:26 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:bin binexp installbin userelocatableinc initialinstalllocation: \
Myread Prefixit Getfile Setvar Setprefixvar Oldconfig \
test prefix prefixexp
?MAKE: -pick add $@ %<
?Y:TOP
?D:bin="
```

?S:bin:
 ?S: This variable holds the name of the directory in which the user wants
 ?S: to put publicly executable images for the package in question. It
 ?S: is most often a local directory such as /usr/local/bin. Programs using
 ?S: this variable must be prepared to deal with ~name substitution.
 ?S:.
 ?D:binexp="
 ?S:binexp:
 ?S: This is the same as the bin variable, but is filename expanded at
 ?S: configuration time, for use in your makefiles.
 ?S:.
 ?D:installbin="
 ?S:installbin:
 ?S: This variable is the same as binexp unless AFS is running in which case
 ?S: the user is explicitly prompted for it. This variable
 should always
 ?S: be used in your makefiles for maximum portability.
 ?S:.
 ?D:userrelocatableinc="
 ?S:userrelocatableinc:
 ?S: This variable is set to true to indicate that perl should relocate
 ?S: @INC entries at runtime based on the path to the perl binary.
 ?S: Any @INC paths starting ".../" are relocated relative to the directory
 ?S: containing the perl binary, and a logical cleanup of the path is then
 ?S: made around the join point (removing "dir/.." pairs)
 ?S:.
 ?S:initialinstalllocation:
 ?S: When userrelocatableinc is true, this variable holds the location
 ?S: that make install should copy the perl binary to, with all the
 ?S: run-time relocatable paths calculated from this at install time.
 ?S: When used, it is initialized to the original value of binexp, and
 ?S: then binexp is set to '.../', as the other binaries are found
 ?S: relative to the perl binary.
 ?S:.
 ?C:BIN:
 ?C: This symbol holds the path of the bin directory where the package will
 ?C: be installed. Program must
 be prepared to deal with ~name substitution.
 ?C:.
 ?C:BIN_EXP:
 ?C: This symbol is the filename expanded version of the BIN symbol, for
 ?C: programs that do not want to deal with that at run-time.
 ?C:.
 ?C:PERL_RELOCATABLE_INC:
 ?C: This symbol, if defined, indicates that we'd like to relocate entries
 ?C: in @INC at run time based on the location of the perl binary.
 ?C:.
 ?H:#define BIN "\$bin" /**/

```

?H:#define BIN_EXP "$binexp" /**/
?H:#define PERL_RELOCATABLE_INC "$userlocatableinc" /**/
?H:
?D:bin='/usr/local/bin'
?LINT:change prefix
?LINT:change prefixexp
?LINT:change prefixvar
?LINT:change installprefixexp
?LINT:set userlocatableinc
: determine where public executables go
echo " "
set dflt bin bin
eval $prefixit
fn=d~
rp='Pathname where the public executables will reside?'
./getfile
if $test "X$sansexp" != "X$binexp"; then
  installbin="
fi
prefixvar=bin
: XXX Bug? -- ignores Configure -Dinstallprefix setting.
: XXX If this is fixed, also fix the "start perl" hunk below, which relies
on
: this via initialinstalllocation
./setprefixvar

case "$userlocatableinc" in
$define|true|[yY]*) dflt='y' ;;
*) dflt='n' ;;
esac
cat <<EOM

```

Would you like to build Perl so that the installation is relocatable, so that library paths in @INC are determined relative to the path of the perl binary? This is not advised for system Perl installs, or if you need to run setid scripts or scripts under taint mode.

If this doesn't make any sense to you, just accept the default '\$dflt'.

```

EOM
rp='Use relocatable @INC?'
./myread
case "$ans" in
y|Y) val="$define" ;;
*) val="$undef" ;;
esac
set userlocatableinc
eval $setvar

```

```

initialinstalllocation="$binexp"
: Default prefix is now "up one level from where the binaries are"
case "$user relocatable inc" in
$define|true|[yY]*)
  bin="..."
  binexp="..."
  prefix="..."
  prefixexp="..."
  installprefixexp="..."
  ;;
esac

```

Found in path(s):

```

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/installdirs/bin.U

```

No license file was found, but licenses were detected in source scan.

```

?RCS: $Id$
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: $Log: stdchar.U,v $
?RCS: Revision 3.0 1993/08/18 12:09:52 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:stdchar: contains Findhdr cppstdin cppminus rm
?MAKE: -pick add $@ %<
?S:stdchar:
?S: This variable conditionally defines STDCHAR to be the type of char
?S: used in stdio.h. It has the values "unsigned char" or "char".
?S:
?C:STDCHAR:
?C: This symbol is defined to be the type of char used in stdio.h.
?C: It has the values "unsigned char" or "char".
?C:
?H:#define STDCHAR $stdchar /**/
?H:
?F:!stdioh
:
  see what type of char stdio uses.
echo " "
?X: untangle the #include nest

```

```

echo '#include <stdio.h>' | $cpstdin $cppminus > stdioh
if $contains 'unsigned.*char.*_ptr;' stdioh >/dev/null 2>&1 ; then
echo "Your stdio uses unsigned chars." >&4
stdchar="unsigned char"
else
echo "Your stdio uses signed chars." >&4
stdchar="char"
fi
$rm -f stdioh

```

Found in path(s):

```

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/stdchar.U

```

No license file was found, but licenses were detected in source scan.

```

?RCS: $Id: i_db.U,v 3.0.1.3 1995/07/25 14:10:22 ram Exp $
?RCS:
?RCS: Copyright (c) 1991-1993, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 3.0.
?RCS:
?RCS: Original Author: Andy Dougherty <doughera@lafcol.lafayette.edu>
?RCS:
?RCS: $Log: i_db.U,v $
?RCS: Revision 3.0.1.3 1995/07/25 14:10:22 ram
?RCS: patch56: conditionally use const in test programs (ADO)
?RCS:
?RCS: Revision 3.0.1.2 1995/05/12 12:14:42 ram
?RCS: patch54: extended for more intimate DB probing (ADO)
?RCS:
?RCS: Revision 3.0.1.1 1994/08/29 16:21:50 ram
?RCS: patch32: created by ADO
?RCS:
?MAKE:i_db db_hashtype db_prefixtype \
db_version_major
db_version_minor db_version_patch : \
Inhdr +cc +ccflags rm_try contains cat \
Compile d_const libs sed run i_stdlib
?MAKE: -pick add $@ %<
?S:i_db:
?S: This variable conditionally defines the I_DB symbol, and indicates
?S: whether a C program may include Berkeley's DB include file <db.h>.
?S:.
?S:db_hashtype:

```

?S: This variable contains the type of the hash structure element
?S: in the <db.h> header file. In older versions of DB, it was
?S: int, while in newer ones it is u_int32_t.
?S:.
?S:db_prefixtype:
?S: This variable contains the type of the prefix structure element
?S: in the <db.h> header file. In older versions of DB, it was
?S: int, while in newer ones it is size_t.
?S:.
?S:db_version_major:
?S: This variable contains the major version number of
?S: Berkeley DB found in the <db.h> header file.
?S:.
?S:db_version_minor:
?S: This variable contains the minor version number of
?S: Berkeley DB found in the <db.h> header file.
?S: For DB version 1 this is always 0.
?S:.
?S:db_version_patch:
?S: This
variable contains the patch version number of
?S: Berkeley DB found in the <db.h> header file.
?S: For DB version 1 this is always 0.
?S:.
?C:I_DB:
?C: This symbol, if defined, indicates to the C program that it should
?C: include Berkeley's DB include file <db.h>.
?C:.
?C:DB_Prefix_t:
?C: This symbol contains the type of the prefix structure element
?C: in the <db.h> header file. In older versions of DB, it was
?C: int, while in newer ones it is u_int32_t.
?C:.
?C:DB_Hash_t:
?C: This symbol contains the type of the prefix structure element
?C: in the <db.h> header file. In older versions of DB, it was
?C: int, while in newer ones it is size_t.
?C:.
?C:DB_VERSION_MAJOR_CFG:
?C: This symbol, if defined, defines the major version number of
?C: Berkeley DB found in the <db.h> header when Perl was configured.
?C:.
?C:DB_VERSION_MINOR_CFG:
?C: This symbol, if defined, defines the minor version number of
?C: Berkeley DB found in the <db.h> header when Perl was configured.
?C: For
DB version 1 this is always 0.
?C:.

```

?C:DB_VERSION_PATCH_CFG:
?C: This symbol, if defined, defines the patch version number of
?C: Berkeley DB found in the <db.h> header when Perl was configured.
?C: For DB version 1 this is always 0.
?C:.
?H:#$i_db I_DB /**/
?H:#define DB_Hash_t $db_hashtype /**/
?H:#define DB_Prefix_t $db_prefixtype /**/
?H:#define DB_VERSION_MAJOR_CFG $db_version_major /**/
?H:#define DB_VERSION_MINOR_CFG $db_version_minor /**/
?H:#define DB_VERSION_PATCH_CFG $db_version_patch /**/
?H:.
?F:!try
?LINT:change libs
: see if this is a db.h system
set db.h i_db
eval $inhdr

case "$i_db" in
$define)
: Check db version.
echo " "
echo "Checking Berkeley DB version ..." >&4
$cat >try.c <<EOCP
#$d_const HASCONST
#ifndef HASCONST
#define const
#endif
#include <sys/types.h>
#include <stdio.h>
#$i_stdlib I_STDLIB
#ifdef I_STDLIB
#include <stdlib.h>
#endif
#include <db.h>
int main(int argc, char *argv[])
{
#ifdef DB_VERSION_MAJOR /* DB version >= 2 */

int Major, Minor, Patch ;
unsigned long Version ;
(void)db_version(&Major, &Minor, &Patch) ;
if (argc == 2) {
printf("%d %d %d %d %d %d\n",
DB_VERSION_MAJOR, DB_VERSION_MINOR, DB_VERSION_PATCH,
Major, Minor, Patch);
exit(0);
}
}

```

```

printf("You have Berkeley DB Version 2 or greater.\n");

printf("db.h is from Berkeley DB Version %d.%d.%d\n",
DB_VERSION_MAJOR, DB_VERSION_MINOR, DB_VERSION_PATCH);
printf("libdb is from Berkeley DB Version %d.%d.%d\n",
Major, Minor, Patch) ;

/* check that db.h & libdb are compatible */
if (DB_VERSION_MAJOR != Major || DB_VERSION_MINOR != Minor || DB_VERSION_PATCH != Patch) {
printf("db.h and libdb are incompatible.\n") ;
    exit(3);
}

printf("db.h and libdb are compatible.\n") ;

Version = DB_VERSION_MAJOR * 1000000 + DB_VERSION_MINOR * 1000
+ DB_VERSION_PATCH ;

/* needs to be >= 2.3.4 */
if (Version < 2003004) {
/* if (DB_VERSION_MAJOR ==
2 && DB_VERSION_MINOR == 0 && DB_VERSION_PATCH < 5) { */
printf("Perl needs Berkeley DB 2.3.4 or greater.\n") ;
    exit(2);
}

    exit(0);
#else
#if defined(_DB_H_) && defined(BTREEMAGIC) && defined(HASHMAGIC)
    if (argc == 2) {
        printf("1 0 0\n");
        exit(0);
    }
    printf("You have Berkeley DB Version 1.\n");
    exit(0); /* DB version < 2: the coast is clear. */
#else
    exit(1); /* <db.h> not Berkeley DB? */
#endif
#endif
}
EOCP
set try
if eval $compile_ok && $run ./try; then
    echo 'Looks OK.' >&4
    set ` $run ./try 1 `
    db_version_major=$1
    db_version_minor=$2
    db_version_patch=$3

```

```

else
echo "I can't use Berkeley DB with your <db.h>. I'll disable Berkeley DB." >&4
i_db=$undef
case " $libs " in
*" -ldb "*)
: Remove db from list of libraries to use
echo "Removing unusable -ldb from library list" >&4
set `echo X $libs | $sed -e 's/-ldb //' -e 's/-ldb$/'`
shift
libs="$*"
echo "libs = $libs" >&4
;;
esac
fi
$rm_try
;;
esac

@if
DB_Hash_t
case "$i_db" in
define)
: Check the return type needed for hash
echo " "
echo "Checking return type needed for hash for Berkeley DB ..." >&4
$cat >try.c <<EOCP
#$d_const HASCONST
#ifndef HASCONST
#define const
#endif
#include <sys/types.h>
#include <db.h>

#ifndef DB_VERSION_MAJOR
u_int32_t hash_cb (const void* ptr, size_t size)
{
}
HASHINFO info;
int main()
{
info.hash = hash_cb;
}
#endif
EOCP
if $cc $cflags -c try.c >try.out 2>&1 ; then
if $contains warning try.out >>/dev/null 2>&1 ; then
db_hashtype='int'
else

```

```

    db_hashtype='u_int32_t'
fi
else
: XXXX Maybe we should just give up here.
db_hashtype=u_int32_t
$cat try.out >&4
echo "Help: I can't seem to compile the db test program." >&4
echo "Something's wrong, but I'll assume you use $db_hashtype." >&4
fi
$rm_try
echo "Your version of Berkeley DB uses $db_hashtype for hash."
;;
*) db_hashtype=u_int32_t
;;
esac
@end
@if DB_Prefix_t
case "$i_db" in
define)
: Check the return type needed
for prefix
echo " "
echo "Checking return type needed for prefix for Berkeley DB ..." >&4
cat >try.c <<EOCP
#$d_const HASCONST
#ifndef HASCONST
#define const
#endif
#include <sys/types.h>
#include <db.h>

#ifndef DB_VERSION_MAJOR
size_t prefix_cb (const DBT *key1, const DBT *key2)
{
}
BTREEINFO info;
int main()
{
    info.prefix = prefix_cb;
}
#endif
EOCP
if $cc $ccflags -c try.c >try.out 2>&1 ; then
if $contains warning try.out >>/dev/null 2>&1 ; then
    db_prefixtype='int'
else
    db_prefixtype='size_t'
fi

```

```

else
db_prefixtype='size_t'
: XXX Maybe we should just give up here.
$cat try.out >&4
echo "Help: I can't seem to compile the db test program." >&4
echo "Something's wrong, but I'll assume you use $db_prefixtype." >&4
fi
$rm_try
echo "Your version of Berkeley DB uses $db_prefixtype for prefix."
;;
*) db_prefixtype='size_t'
;;
esac
@end

```

Found in path(s):

```

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/perl/i_db.U

```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: i_sysun.U,v \$

?RCS: Revision 3.0 1993/08/18 12:08:42 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?X:

?X: This unit looks wether <inttypes.h> is available or not

?X:

?MAKE:i_inttypes: Inhdr

?MAKE: -pick add \$@ %<

?S:i_inttypes:

?S: This variable conditionally defines I_INTTYPES, which indicates

?S: to the C program that it should include <inttypes.h> to get

?S: format conversions of integer types.

?S:.

?C:I_INTTYPES:

?C: This symbol, if defined, indicates to the C program that it should

?C: include

<inttypes.h> to get format conversions of integer types.

?C:.

?H:#\$i_inttypes I_INTTYPES /**/

?H:.

?LINT:set i_inttypes

: see if this is a inttypes.h system

set inttypes.h i_inttypes

eval \$inhdr

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/i_inttypes.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: usrinc.U,v 1.1 2000/06/27 00:20:28 jhi Exp \$

?RCS:

?RCS: Copyright (c) 1991-1993, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 3.0.

?RCS:

?RCS: \$Log: usrinc.U,v \$

?RCS: Revision 1.1 2000/06/27 00:20:28 jhi

?RCS: Initial revision

?RCS:

?RCS: Revision 3.0.1.3 1997/02/28 16:27:12 ram

?RCS: patch61: don't ask for the include path unless they are on a MIPS

?RCS:

?RCS: Revision 3.0.1.2 1995/05/12 12:24:36 ram

?RCS: patch54: ensure that ./mips always exists (ADO)

?RCS:

?RCS: Revision 3.0.1.1 1994/05/06 15:18:31 ram

?RCS: patch23: ensure usrinc value is preserved across sessions (WED)

?RCS:

?RCS: Revision

3.0 1993/08/18 12:09:58 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?MAKE:usrinc incpath mips_type: test cat echo n c Getfile Guess \

Oldconfig eunicefix contains rm sysroot cc

?MAKE: -pick add \$@ %<

?S:usrinc:

?S: This variable holds the path of the include files, which is

?S: usually /usr/include. It is mainly used by other Configure units.

?S:.

?S:incpath:

?S: This variable must precede the normal include path to get the

?S: right one, as in "\$incpath/usr/include" or "\$incpath/usr/lib".

?S: Value can be "" or "/bsd43" on mips.

?S:.

?S:mips_type:

?S: This variable holds the environment type for the mips system.

?S: Possible values are "BSD 4.3" and "System V".

?S:.

?D:usrinc='/usr/include'

?LINT:extern cppflags

?LINT:create mips

?T:xxx_prompt

?F:./mips

: What should the include directory be ?

: Use sysroot if set, so findhdr looks in the right place.

echo " "

\$echo \$n "Hmm... \$c"

dflt="\$sysroot/usr/include"

incpath=""

?X: mips_type is used later, to add -DSYSTYPE_BSD43

to cppflags if needed.

mips_type=""

?X:

?X: Cannot put the following in Guess, or we get a circular dependency.

?X:

if \$test -f /bin/mips && /bin/mips; then

echo "Looks like a MIPS system..."

\$cat >usr.c <<'EOCP'

#ifdef SYSTYPE_BSD43

/bsd43

#endif

EOCP

if \$cc \$cppflags -E usr.c > usr.out && \$contains /usr.out >/dev/null 2>&1; then

dflt='/bsd43/usr/include'

incpath='/bsd43'

mips_type='BSD 4.3'

else

mips_type='System V'

fi

\$rm -f usr.c usr.out

echo "and you're compiling with the \$mips_type compiler and libraries."

xxx_prompt=y

echo "exit 0" >mips

else

echo "Doesn't look like a MIPS system."

xxx_prompt=n

echo "exit 1" >mips

```

fi
chmod +x mips
$unicefix mips
case "$usrinc" in
") ;;
*) dflt="$usrinc";;
esac
case "$xxx_prompt" in
y) fn=d/
echo " "
rp='Where are the include files you want to use?'
./getfile
usrinc="$ans"
;;
*) usrinc="$dflt"
;;
esac

```

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/modified/usrinc.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: Extract.U,v \$

?RCS: Revision 3.0.1.2 1997/02/28 14:58:52 ram

?RCS: patch61: added support for src.U

?RCS:

?RCS: Revision 3.0.1.1 1994/10/29 15:51:46 ram

?RCS: patch36: added ?F: line for metalint file checking

?RCS:

?RCS: Revision 3.0 1993/08/18 12:04:52 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?X:

?X: This unit produces a shell script which can be doted in order to extract

?X: .SH files with variable substitutions.

?X:

?X: When running Configure from a remote directory (\$src

```

is not '),
?X: then the files will be created in that directory, so beware!
?X:
?MAKE:Extract: Mkdirp src
?MAKE: -pick add $@ %<
?F:./extract
?T:CONFIG SRC dir file
: script used to extract .SH files with variable substitutions
cat >extract <<EOS
CONFIG=true
SRC="$src"
EOS
cat >>extract <<'EOS'
echo "Doing variable substitutions on .SH files..."
if test -f "$SRC/MANIFEST"; then
  set x `awk '{print $1}' <$SRC/MANIFEST | grep \.SH`
else
  echo "(Looking for .SH files under the source directory.)"
  set x `(cd "$SRC"; find . -name "*.SH" -print)`
fi
shift
case $# in
0) set x `(cd "$SRC"; echo *.SH)`; shift;;
esac
if test ! -f "$SRC/$1"; then
  shift
fi
for file in $*; do
  case "$SRC" in
".")
  case "$file" in
*/*)
  dir=`expr X$file : 'X\(.*)/'`
  file=`expr X$file : 'X.*\^(.*)'`
  (cd $dir && ./$file)
  ;;
*)
  ./$file
  ;;
esac
;;
*)

```

?X:

?X: When running Configure remotely (\$src is not '.'), we cannot source the files directly, since that would wrongly cause the extraction

?X: where the source lie instead of withing the current directory. Therefore,

?X: we need to 'sh <file' then, which is okay since they will source the

?X: existing config.sh file. It's not possible to use:
?X: ../src/Configure -S -O -Dsomething
?X: unfortunately since no new config.sh with the -Dsomething override
?X: will be created before running the .SH files. A minor buglet.
?X:
?X: Note that we must create the directory hierarchy ourselves if it does
?X: not exist already, and that is done through a shell emulation of the
?X: 'mkdir -p' command. We don't want to use the \$installdir metaconfig
?X: symbol here since that would require too much to be configured for
?X: this simple extraction task that may happen quickly with 'Configure -S'.
?X: -- RAM, 18/03/96

```
?X:
case "$file" in
  */)
    dir=`expr X$file : 'X\(.*)/'`
    file=`expr X$file : 'X.*\(.*)'`
    ./mkdirp $dir
    sh <"$SRC/$dir/$file"
    ;;
  *)
    sh <"$SRC/$file"
    ;;
esac
;;
esac
done
if
  test -f "$SRC/config_h.SH"; then
  if test ! -f config.h; then
?X: oops, they left it out of MANIFEST, probably, so do it anyway.
    sh <"$SRC/config_h.SH"
  fi
fi
EOS
```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/Extract.U
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_dLError.U 1 2006-08-24 12:32:52Z rmanfredi \$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic Licence,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic Licence; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: Original Author: Andy Dougherty <doughera@lafcol.lafayette.edu>
?RCS:
?RCS: \$Log: d_dlerror.U,v \$
?RCS: Revision 3.0.1.2 1995/07/25 13:52:49 ram
?RCS: patch56: force compile-link test since symbol might lie in crt0.o (ADO)
?RCS:
?RCS: Revision 3.0.1.1 1994/10/29 16:11:23 ram
?RCS: patch36: created by ADO
?RCS:
?MAKE:d_dlerror: Inlibc runnm
?MAKE: -pick add \$@ %<
?S:d_dlerror:
?S: This variable conditionally defines the HAS_DLERROR symbol, which
?S: indicates
to the C program that the dlerror() routine is available.
?S:.
?C:HAS_DLERROR :
?C: This symbol, if defined, indicates that the dlerror routine is
?C: available to return a string describing the last error that
?C: occurred from a call to dlopen(), dlclose() or dlsym().
?C:.
?H:#\$d_dlerror HAS_DLERROR /**/
?H:.
?T: xxx_runnm
?LINT:set d_dlerror
?X: We don't permanently change runnm, but we do temporarily.
?LINT: change runnm
: see if dlerror exists
?X: On NetBSD and FreeBSD, dlerror might be available, but it is in
?X: /usr/lib/crt0.o, not in any of the libraries. Therefore, do not
?X: use the nm extraction, but use a real compile and link test instead.
xxx_runnm="\$runnm"
runnm=false
set dlerror d_dlerror
eval \$inlibc
runnm="\$xxx_runnm"

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/d_dlerror.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$
?RCS:
?RCS: Copyright (c) 2001 Jarkko Hietaniemi
?RCS:

?RCS: You may distribute under the terms of either the GNU General Public
?RCS: License or the Artistic License, as specified in the README file.
?RCS:
?MAKE:d_socketmark: Inlibc
?MAKE: -pick add \$@ %<
?S:d_socketmark:
?S: This variable conditionally defines the HAS_SOCKETMARK symbol, which
?S: indicates to the C program that the socketmark() routine is available.
?S:.
?C:HAS_SOCKETMARK:
?C: This symbol, if defined, indicates that the socketmark routine is
?C: available to test whether a socket is at the out-of-band mark.
?C:.
?H:#\$d_socketmark HAS_SOCKETMARK /**/
?H:.
?LINT:set d_socketmark
: see if socketmark exists
set socketmark d_socketmark
eval \$inlibc

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/perl/d_socketmark.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: \$Log: so.U,v \$
?RCS: Revision 3.0.1.2 1994/10/29 16:30:04 ram
?RCS: patch36: now tells user how he can suppress shared lib lookup (ADO)
?RCS: patch36: removed echo at the top, since it's now in the here-doc (ADO)
?RCS:
?RCS: Revision 3.0.1.1 1994/06/20 07:07:02 ram
?RCS: patch30: created
?RCS:
?X:
?X: This unit computes the shared-object / shared-lib extension
?X:
?MAKE:so: test libpth Loc Myread Oldconfig cat
?MAKE: -pick add \$@ %<

```

?S:so:
?S: This variable holds the extension used to identify
shared libraries
?S: (also known as shared objects) on the system. Usually set to 'so'.
?S:.
?T: xxx
: compute shared library extension
case "$so" in
")
if xxx=`./loc libc.sl X $libpth`; $test -f "$xxx"; then
dflt='sl'
else
dflt='so'
fi
;;
*) dflt="$so";;
esac
$cat <<EOM

```

On some systems, shared libraries may be available. Answer 'none' if you want to suppress searching of shared libraries for the remainder of this configuration.

```

EOM
rp='What is the file extension used for shared libraries?'
./myread
so="$ans"

```

```

Found in path(s):
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/so.U
No license file was found, but licenses were detected in source scan.

```

```

?RCS: $Id$
?RCS:
?RCS: Copyright (c) 2000, Jarkko Hietaniemi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 3.0.
?RCS:
?MAKE:d_lseekproto: Hasproto i_systypes i_unistd
?MAKE: -pick add $@ %<
?S:d_lseekproto:
?S: This variable conditionally defines the HAS_LSEEK_PROTO symbol,
?S: which indicates to the C program that the system provides

```

?S: a prototype for the lseek() function. Otherwise, it is
 ?S: up to the program to supply one.
 ?S:.
 ?C:HAS_LSEEK_PROTO:
 ?C: This symbol, if defined, indicates that the system provides
 ?C: a prototype for the lseek() function. Otherwise, it is up
 ?C: to the program to supply one. A good guess is
 ?C: extern
 off_t lseek(int, off_t, int);
 ?C:.
 ?H:#\$d_lseekproto HAS_LSEEK_PROTO /**/
 ?H:.
 ?LINT:set d_lseekproto
 : see if prototype for lseek is available
 echo " "
 set d_lseekproto lseek \$i_systypes sys/types.h \$i_unistd unistd.h
 eval \$hasproto

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/protos/d_lseekproto.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: yacc.U,v 3.0.1.1 1994/05/13 15:28:48 ram Exp \$

?RCS:

?RCS: Copyright (c) 1991-1993, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 3.0.

?RCS:

?RCS: \$Log: yacc.U,v \$

?RCS: Revision 3.0.1.1 1994/05/13 15:28:48 ram

?RCS: patch27: added byacc as another alternative (ADO)

?RCS:

?RCS: Revision 3.0 1993/08/18 12:10:03 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?MAKE:yacc yaccflags: Guess Myread Oldconfig byacc bison cat test _exe

?MAKE: -pick add \$@ %<

?S:yacc:

?S: This variable holds the name of the compiler compiler we

?S: want to use in the Makefile. It can be yacc, byacc, or bison -y.

?S:.

?S:yaccflags:

?S: This

variable contains any additional yacc flags desired by the

?S: user. It is up to the Makefile to use this.

?S:.

?T:comp

: determine compiler compiler

case "\$yacc" in

")

dflt=yacc;;

*)

dflt="\$yacc";;

esac

echo " "

comp='yacc'

if \$test -f "\$byacc\$_exe"; then

dflt="\$byacc"

comp="byacc or \$comp"

fi

if \$test -f "\$bison\$_exe"; then

comp="\$comp or bison -y"

fi

rp="Which compiler compiler (\$comp) shall I use?"

./myread

yacc="\$ans"

case "\$yacc" in

bis)

case "\$yacc" in

-y) ;;

*)

yacc="\$yacc -y"

echo "(Adding -y option to bison to get yacc-compatible behavior.)"

::

esac

::

esac

@if yaccflags

: see if we need extra yacc flags

dflt="\$yaccflags"

case "\$dflt" in

") dflt=none;;

esac

\$cat <<EOH

Your yacc program may need extra flags to normally process the parser sources.

Do NOT specify any -d or -v flags here, since those are explicitly known

by the various Makefiles. However, if your machine has strange/undocumented

options (like -Sr# on SCO to specify the

maximum number of grammar rules), then
please add them here. To use no flags, specify the word "none".

EOH

```
rp="Any additional yacc flags?"
```

```
./myread
```

```
case "$ans" in
```

```
none) yaccflags="";;
```

```
*) yaccflags="$ans";;
```

```
esac
```

```
@end
```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/modified/yacc.U
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: Original Author: Thomas Neumann <tom@smart.bo.open.de>

?RCS:

?RCS: \$Log: Findhdr.U,v \$

?RCS: Revision 3.0.1.2 1994/10/29 15:53:08 ram

?RCS: patch36: added ?F: line for metalint file checking

?RCS:

?RCS: Revision 3.0.1.1 1994/05/06 14:03:56 ram

?RCS: patch23: cppminus must be after other cppflags, not before

?RCS:

?RCS: Revision 3.0 1993/08/18 12:04:54 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?X:

?X: This unit produces a findhdr script which is used to locate the header

?X: files

in \$usrinc or other stranger places using cpp capabilities. The

?X: script is given an include file base name, like 'stdio.h' or 'sys/file.h'

?X: and it returns the full path of the include file and a zero status or an

?X: empty string with an error status if the file could not be located.

?X:

```

?MAKE:Findhdr: grep test tr rm +usrinc awk cat startsh \
  cppstdin cppminus +cppflags eunicefix osname
?MAKE: -pick add $@ %<
?LINT:define fieldn
?S:fieldn:
?S: This variable is used internally by Configure. It contains the position
?S: of the included file name in cpp output. That is to say, when cpp
?S: pre-processes a #include <file> line, it replaces it by a # line which
?S: contains the original position in the input file and the full name of
?S: included file, between "quotes".
?S:.
?V:fieldn
?F:./findhdr !fieldn
?T:cline pos wanted name awkprg cppfilter testaccess status usrincdir
: determine filename position in cpp output
echo " "
echo "Computing filename position in cpp output for #include
  directives..." >&4
echo '#include <stdio.h>' > foo.c
case "$osname" in
vos)
  testaccess=-e
?X: VOS: path component separator is >
  cppfilter="tr '\\\\>' '/' |"
  ;;
*)
  testaccess=-r
  cppfilter="
  ;;
esac
$cat >fieldn <<EOF
$startsh
$cppstdin $cppflags $cppminus <foo.c 2>/dev/null | \
$grep '^[ ]*#.*stdio.h'| \
while read cline; do
  pos=1
  set $cline
  while $test $# -gt 0; do
    if $test $testaccess `echo $1 | $tr -d ""`; then
      echo "$pos"
      exit 0
    fi
    shift
    pos=`expr $pos + 1`
  done
done
EOF
chmod +x fieldn

```

```

fieldn=`./fieldn`
$rm -f foo.c fieldn
case $fieldn in
") pos='???';;
1) pos=first;;
2) pos=second;;
3) pos=third;;
*) pos="$fieldn th";;
esac
echo "Your cpp writes the filename in the $pos field of the line."

```

?X: To locate a header file, we cannot simply check for \$usrinc/file.h, since
?X: some machine have the headers in weird places and our only hope is that
?X: the C pre-processor will know how to find those headers. Thank you Next!

: locate header file

```

$cat
>findhdr <<EOF
$startsh
wanted=\$1
name=""
for usrincdir in $usrinc; do
if test -f \$usrincdir/\$wanted; then
echo "\$usrincdir/\$wanted"
exit 0
fi
done
awkprg='{ print \$fieldn }'
echo "#include <\$wanted>" > foo\$\$.c
$cppstdin $cppminus $cppflags < foo\$\$.c 2>/dev/null | \
$cppfilter $grep "^[ ]*#.*\$wanted" | \
while read cline; do
name=\`echo \$cline | $awk "\$awkprg" | $tr -d ""`\
case "\$name" in
*[\|\\]\$wanted) echo "\$name"; exit 1;;
*[\|\\]\$wanted) echo "\$name"; exit 1;;
*) exit 2;;
esac
done
?X: status = 0: grep returned 0 lines, case statement not executed
?X: status = 1: headerfile found
?X: status = 2: while loop executed, no headerfile found
status=\$?
$rm -f foo\$\$.c
if test \$status -eq 1; then
exit 0
fi
exit 1
EOF

```

```
chmod +x findhdr
$eunicefix findhdr
```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/Findhdr.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: d_getlogin.U 1 2006-08-24 12:32:52Z rmanfredi $
```

```
?RCS:
```

```
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
```

```
?RCS:
```

```
?RCS: You may redistribute only under the terms of the Artistic Licence,
```

```
?RCS: as specified in the README file that comes with the distribution.
```

```
?RCS: You may reuse parts of this distribution only within the terms of
```

```
?RCS: that same Artistic Licence; a copy of which may be found at the root
```

```
?RCS: of the source tree for dist 4.0.
```

```
?RCS:
```

```
?RCS: Original Author: Andy Dougherty <doughera@lafcol.lafayette.edu>
```

```
?RCS:
```

```
?RCS: $Log: d_getlogin.U,v $
```

```
?RCS: Revision 3.0.1.1 1994/08/29 16:07:41 ram
```

```
?RCS: patch32: created by ADO
```

```
?RCS:
```

```
?MAKE:d_getlogin: Inlibc
```

```
?MAKE: -pick add $@ %<
```

```
?S:d_getlogin:
```

```
?S: This variable conditionally defines the HAS_GETLOGIN symbol, which
```

```
?S: indicates to the C program that the getlogin() routine is available
```

```
?S: to get the login name.
```

```
?S:.
```

```
?C:HAS_GETLOGIN :
```

```
?C: This symbol,
```

```
if defined, indicates that the getlogin routine is
```

```
?C: available to get the login name.
```

```
?C:.
```

```
?H:#$d_getlogin HAS_GETLOGIN /**/
```

```
?H:.
```

```
?LINT:set d_getlogin
```

```
: see if getlogin exists
```

```
set getlogin d_getlogin
```

```
eval $inlibc
```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/d_getlogin.U
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$
?RCS:
?RCS: Copyright (c) 1999, Jarkko Hietaniemi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 3.0.
?RCS:
?MAKE:d_sched_get_priority_min: Inlibc
?MAKE: -pick add \$@ %<
?S:d_sched_get_priority_min:
?S: This variable conditionally defines HAS_SCHED_GET_PRIORITY_MIN if
?S: sched_get_priority_min() is available to get the minimum scheduling
?S: priority.
?S:.
?C:HAS_SCHED_GET_PRIORITY_MIN:
?C: This symbol, if defined, indicates that the sched_get_priority_min
?C: system call is available to get the minimum scheduling priority.
?C:.
?H:#\$d_sched_get_priority_min HAS_SCHED_GET_PRIORITY_MIN /**/
?H:.
?LINT:set d_sched_get_priority_min
:
see if sched_get_priority_min exists
set sched_get_priority_min d_sched_get_priority_min
eval \$inlibc

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_sched_gpmin.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$
?RCS:
?RCS: Copyright (c) 2001 Jarkko Hietaniemi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 3.0.
?RCS:
?MAKE:d_usleepproto: Hasproto i_unistd
?MAKE: -pick add \$@ %<
?S:d_usleepproto:
?S: This variable conditionally defines the HAS_USLEEP_PROTO symbol,

?S: which indicates to the C program that the system provides

?S: a prototype for the usleep() function. Otherwise, it is

?S: up to the program to supply one.

?S:.

?C:HAS_USLEEP_PROTO:

?C: This symbol, if defined, indicates that the system provides

?C: a prototype for the usleep() function. Otherwise, it is up

?C: to the program to supply one. A good guess is

?C: extern int

```
usleep(useconds_t);
```

?C:.

?H:#\$d_usleepproto HAS_USLEEP_PROTO /**/

?H:.

?LINT:set d_usleepproto

: see if prototype for usleep is available

```
echo " "
```

```
set d_usleepproto usleep $i_unistd unistd.h
```

```
eval $hasproto
```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_usleepproto.U
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_group.U 1 2006-08-24 12:32:52Z rmanfredi \$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic Licence,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic Licence; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: Original Author: Andy Dougherty <doughera@lafcol.lafayette.edu>

?RCS:

?RCS: \$Log: d_group.U,v \$

?RCS: Revision 3.0.1.2 1997/02/28 15:34:52 ram

?RCS: patch61: useless unit dropped.

?RCS:

?RCS: Revision 3.0.1.1 1994/08/29 16:07:48 ram

?RCS: patch32: created by ADO

?RCS:

?X:

?X: Useless unit dropped.

?X:

?LINT:empty

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/d_group.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_static_inline.U,v \$

?RCS:

?RCS: Copyright (c) 2010 Andrew Dougherty

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 3.0.

?RCS:

?RCS: Original Author: Andy Dougherty <doughera@lafayette.edu>

?RCS:

?MAKE:d_static_inline perl_static_inline: Compile Setvar gccversion \
cat echo run hint rm rm_try

?MAKE: -pick add \$@ %<

?S:d_static_inline:

?S: This variable conditionally defines the HAS_STATIC_INLINE symbol,

?S: which indicates that the C compiler supports C99-style static

?S: inline. That is, the function can't be called from another

?S: translation unit.

?S:.

?S:perl_static_inline:

?S: This variable defines the PERL_STATIC_INLINE
symbol to

?S: the best-guess incantation to use for static inline functions.

?S: Possibilities include

?S: static inline (c99)

?S: static __inline__ (gcc -ansi)

?S: static __inline (MSVC)

?S: static _inline (older MSVC)

?S: static (c89 compilers)

?S:.

?C:HAS_STATIC_INLINE :

?C: This symbol, if defined, indicates that the C compiler supports

?C: C99-style static inline. That is, the function can't be called

?C: from another translation unit.

?C:.

?C:PERL_STATIC_INLINE:

?C: This symbol gives the best-guess incantation to use for static

?C: inline functions. If HAS_STATIC_INLINE is defined, this will

?C: give C99-style inline. If HAS_STATIC_INLINE is not defined,

?C: this will give a plain 'static'. It will always be defined

?C: to something that gives static linkage.

```

?C: Possibilities include
?C: static inline    (c99)
?C: static __inline__ (gcc -ansi)
?C: static __inline  (MSVC)
?C: static _inline   (older MSVC)
?C: static
      (c89 compilers)
?C:.
?H:#$d_static_inline HAS_STATIC_INLINE  /**/
?H:#define PERL_STATIC_INLINE $perl_static_inline /**/
?H:.
?LINT:set d_static_inline
?T:inline xxx
?F:!try
: see what flavor, if any, of static inline is supported
echo " "
echo "Checking to see if your system supports static inline..."
?X: Build two programs.  The first uses static inline in file a.c and
?X: should work.  The second also includes b.c which tries to link against
?X: the static function in a.c.  This should fail.
?X:.
$cat > try.c <<'EOCP'
#include <stdlib.h>
extern int f_via_a(int x);
extern int f_via_b(int x);
int main(int argc, char **argv)
{
    int y;

    y = f_via_a(0);
#ifdef USE_B
    y = f_via_b(0);
#endif
    if (y == 42) {
        return EXIT_SUCCESS;
    }
    else {
        return EXIT_FAILURE;
    }
}
EOCP
$cat > a.c <<'EOCP'
static INLINE int f(int x) {
    int y;
    y = x + 42;
    return y;
}

```

```
int f_via_a(int x)
{
    return f(x);
}
```

EOCP

```
$cat > b.c <<'EOCP'
```

```
extern int f(int x);
```

```
int
```

```
f_via_b(int x)
```

```
{
    return f(x);
}
```

EOCP

```
# Respect a hint (or previous) value for perl_static_inline, if there is one.
```

```
case "$perl_static_inline" in
```

```
) # Check the various possibilities, and break out on success.
```

```
# For gcc, prefer __inline__, which will still permit
```

```
# cflags.SH to add in -ansi.
```

```
case "$gccversion" in
```

```
) xxx="__inline__ __inline__";;
```

```
*) xxx="__inline__ inline __inline__";;
```

```
esac
```

```
for inline in $xxx; do
```

```
set try -DINLINE=$inline a.c
```

```
if eval $compile && $run ./try; then
```

```
# Now make sure there is no external linkage of static
```

```
# functions
```

```
set try -DINLINE=$inline -DUSE_B a.c b.c
```

```
if eval $compile && $run ./try; then
```

```
$echo "Your compiler supports static $inline, " >&4
```

```
$echo "but it also creates an external definition," >&4
```

```
$echo "so I won't use it." >&4
```

```
val=$undef
```

```
else
```

```
$echo "Your compiler supports static $inline." >&4
```

```
val=$define
```

```
perl_static_inline="static $inline";
```

```
break;
```

```
fi
```

```
else
```

```
$echo
```

```
"Your compiler does NOT support static $inline." >&4
```

```
val="$undef"
```

```
fi
```

```
done
```

```
::
```

```

*inline*) # Some variant of inline exists.
echo "Keeping your $hint value of $perl_static_inline."
val=$define
;;
static) # No inline capabilities
echo "Keeping your $hint value of $perl_static_inline."
val=$undef
;;
*) # Unrecognized previous value -- blindly trust the supplied
# value and hope it makes sense. Use old value for
# d_static_inline, if there is one.
echo "Keeping your $hint value of $perl_static_inline."
case "$d_static_inline" in
  ") val=$define ;;
  *) val=$d_static_inline ;;
esac
;;
esac
# Fallback to plain 'static' if nothing worked.
case "$perl_static_inline" in
  ")
perl_static_inline="static"
val=$undef
;;
esac
set d_static_inline
eval $setvar
$rm -f a.[co] b.[co]
$rm_try

```

Found in path(s):

```

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/compline/d_static_inline.U

```

No license file was found, but licenses were detected in source scan.

```

?RCS: $Id: nblock_io.U,v 3.0.1.2 1997/02/28 16:17:14 ram Exp $
?RCS:
?RCS: Copyright (c) 1991-1993, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 3.0.
?RCS:
?RCS: $Log: nblock_io.U,v $
?RCS: Revision 3.0.1.2 1997/02/28 16:17:14 ram
?RCS: patch61: simplify here document for shells that can't handle them well

```

?RCS: patch61: force use of "startsh" at the head of the generated script

?RCS: patch61: added new files to the ?F: metalint hint

?RCS:

?RCS: Revision 3.0.1.1 1995/07/25 14:13:22 ram

?RCS: patch56: created

?RCS:

?X:

?X: Simplify here document for shells that can't handle them well.

?X: (Problem reported on FreeBSD;
it's unclear if this helps.) --AD

?X:

?MAKE:o_nonblock eagain rd_nodata d_eofnblk: cat rm_try Compile run \
d_open3 h_sysfile h_fcntl signal_t hint Oldconfig Setvar \
startsh i_unistd i_string i_fcntl i_stdlib d_fork d_pipe d_alarm

?MAKE: -pick add \$@ %<

?S:o_nonblock:

?S: This variable bears the symbol value to be used during open() or fcntl()
?S: to turn on non-blocking I/O for a file descriptor. If you wish to switch
?S: between blocking and non-blocking, you may try ioctl(FIOSNBIO) instead,
?S: but that is only supported by some devices.

?S:.

?S:eagain:

?S: This variable bears the symbolic errno code set by read() when no
?S: data is present on the file and non-blocking I/O was enabled (otherwise,
?S: read() blocks naturally).

?S:.

?S:rd_nodata:

?S: This variable holds the return code from read() when no data is
?S: present. It should be -1, but some systems return 0 when O_NDELAY is
?S: used, which is a shame because you cannot make the difference between
?S: no data and an
EOF.. Sigh!

?S:.

?S:d_eofnblk:

?S: This variable conditionally defines EOF_NONBLOCK if EOF can be seen
?S: when reading from a non-blocking I/O source.

?S:.

?C:VAL_O_NONBLOCK:

?C: This symbol is to be used during open() or fcntl(F_SETFL) to turn on
?C: non-blocking I/O for the file descriptor. Note that there is no way
?C: back, i.e. you cannot turn it blocking again this way. If you wish to
?C: alternatively switch between blocking and non-blocking, use the
?C: ioctl(FIOSNBIO) call instead, but that is not supported by all devices.

?C:.

?C:VAL_EAGAIN:

?C: This symbol holds the errno error code set by read() when no data was
?C: present on the non-blocking file descriptor.

?C:.

?C:RD_NODATA:

?C: This symbol holds the return code from read() when no data is present

?C: on the non-blocking file descriptor. Be careful! If EOF_NONBLOCK is

?C: not defined, then you can't distinguish between no data and EOF by

?C: issuing a read(). You'll have to find another way to tell for sure!

?C:.

?C:EOF_NONBLOCK:

?C: This

symbol, if defined, indicates to the C program that a read() on

?C: a non-blocking file descriptor will return 0 on EOF, and not the value

?C: held in RD_NODATA (-1 usually, in that case!).

?C:.

?H:#define VAL_O_NONBLOCK \$o_nonblock

?H:#define VAL_EAGAIN \$again

?H:#define RD_NODATA \$rd_nodata

?H:#\$d_eofnblk EOF_NONBLOCK

?H:.

?T:status

?F:!try.out !try.ret !try.err !try !mtry

?LINT:use d_open3

: check for non-blocking I/O stuff

case "\$h_sysfile" in

true) echo "#include <sys/file.h>" > head.c;;

*)

case "\$h_fcntl" in

true) echo "#include <fcntl.h>" > head.c;;

*) echo "#include <sys/fcntl.h>" > head.c;;

esac

;;

esac

echo " "

echo "Figuring out the flag used by open() for non-blocking I/O..." >&4

case "\$o_nonblock" in

")

\$cat head.c > try.c

\$cat >>try.c <<EOCP

#include <stdio.h>

#\$i_stdlib I_STDLIB

#ifdef I_STDLIB

#include <stdlib.h>

#endif

#\$i_fcntl I_FCNTL

#ifdef I_FCNTL

#include <fcntl.h>

#endif

int main() {

#ifdef O_NONBLOCK

printf("O_NONBLOCK\n");

```

exit(0);
#endif
#ifdef
O_NDELAY
printf("O_NDELAY\n");
exit(0);
#endif
?X: Stevens "Advanced Programming in the UNIX Environment" page 364 mentions
?X: the FNDELAY symbol, used in 4.3BSD (source: Paul Marquess).
#ifdef FNDELAY
printf("FNDELAY\n");
exit(0);
#endif
exit(0);
}
EOCP
set try
if eval $compile_ok; then
o_nonblock=`$run ./try`
case "$o_nonblock" in
") echo "I can't figure it out, assuming O_NONBLOCK will do.";;
*) echo "Seems like we can use $o_nonblock.";;
esac
else
echo "(I can't compile the test program; pray O_NONBLOCK is right!)"
fi
;;
*) echo "Using $hint value $o_nonblock.";;
esac
$rm_try

echo " "
echo "Let's see what value errno gets from read() on a $o_nonblock file..." >&4
case "$again" in
")
case "$d_fork:$d_pipe:$d_alarm" in
define:define:define)
$cat head.c > try.c
$cat >>try.c <<EOCP
#include <errno.h>
#include <sys/types.h>
#include <signal.h>
#include <stdio.h>
#$i_stdlib I_STDLIB
#ifdef I_STDLIB
#include <stdlib.h>
#endif
#$i_fcntl

```

```

I_FCNTL
#ifdef I_FCNTL
#include <fcntl.h>
#endif
#define MY_O_NONBLOCK $o_nonblock
#ifndef errno /* XXX need better Configure test */
extern int errno;
#endif
#ifdef I_UNISTD
#include <unistd.h>
#endif
#ifdef I_STRING
#include <string.h>
#else
#include <strings.h>
#endif
$signal_t blech(int x) { exit(3); }
EOCP
$cat >> try.c <<'EOCP'
int main()
{
int pd[2];
int pu[2];
char buf[1];
char string[100];
int ret;

ret = pipe(pd); /* Down: child -> parent */
if (ret != 0)
exit(3);
ret = pipe(pu); /* Up: parent -> child */
if (ret != 0)
exit(3);
if (0 != fork()) {
close(pd[1]); /* Parent reads from pd[0] */
close(pu[0]); /* Parent writes (blocking) to pu[1] */
#ifdef F_SETFL
if (-1 == fcntl(pd[0], F_SETFL, MY_O_NONBLOCK))
exit(1);
#else
exit(4);
#endif
signal(SIGALRM, blech);
alarm(5);
if ((ret = read(pd[0], buf, 1)) > 0) /* Nothing to read! */
exit(2);

```

```

sprintf(string, "%d\n", ret);
ret =
write(2, string, strlen(string));
if (ret != strlen(string))
    exit(3);
alarm(0);
#ifdef EAGAIN
if (errno == EAGAIN) {
    printf("EAGAIN\n");
    goto ok;
}
#endif
#ifdef EWOULDBLOCK
if (errno == EWOULDBLOCK)
    printf("EWOULDBLOCK\n");
#endif
ok:
ret = write(pu[1], buf, 1); /* Unblocks child, tell it to close our pipe */
if (ret != 1)
    exit(3);
sleep(2); /* Give it time to close our pipe */
alarm(5);
ret = read(pd[0], buf, 1); /* Should read EOF */
alarm(0);
sprintf(string, "%d\n", ret);
ret = write(4, string, strlen(string));
if (ret != strlen(string))
    exit(3);
exit(0);
}

close(pd[0]); /* We write to pd[1] */
close(pu[1]); /* We read from pu[0] */
ret = read(pu[0], buf, 1); /* Wait for parent to signal us we may continue */
if (ret != 1)
    exit(3);
close(pd[1]); /* Pipe pd is now fully closed! */
exit(0); /* Bye bye, thank you for playing! */
}
EOCP
set try
if eval $compile_ok; then
?X: Use script to avoid the possible 'alarm
call' message
echo "$startsh" >mtry
echo "$run ./try >try.out 2>try.ret 4>try.err || exit 4" >>mtry
chmod +x mtry
$run ./mtry >/dev/null 2>&1

```

```

case $? in
0) eagain=`$cat try.out`;
1) echo "Could not perform non-blocking setting!";
2) echo "I did a successful read() for something that was not there!";
3) echo "Hmm... non-blocking I/O does not seem to be working!";
4) echo "Could not find F_SETFL!";
*) echo "Something terribly wrong happened during testing.";
esac
rd_nodata=`$cat try.ret`
echo "A read() system call with no data present returns $rd_nodata."
case "$rd_nodata" in
0|-1) ;;
*)
echo "(That's peculiar, fixing that to be -1.)"
rd_nodata=-1
;;
esac
case "$eagain" in
")
echo "Forcing errno EAGAIN on read() with no data available."
eagain=EAGAIN
;;
*)
echo "Your read() sets errno to $eagain when no data is available."
;;
esac
status=`$cat try.err`
case "$status" in
0) echo "And it correctly returns 0 to
signal EOF.";
-1) echo "But it also returns -1 to signal EOF, so be careful!";
*) echo "However, your read() returns '$status' on EOF?";
esac
val="$define"
if test "$status" = "$rd_nodata"; then
echo "WARNING: you can't distinguish between EOF and no data!"
val="$undef"
fi
else
echo "I can't compile the test program--assuming errno EAGAIN will do."
eagain=EAGAIN
fi
;;
*) echo "Can't figure out how to test this--assuming errno EAGAIN will do."
eagain=EAGAIN
val="$define"
;;
esac

```

```

set d_eofnblk
eval $setvar
;;
*)
echo "Using $hint value $again."
echo "Your read() returns $rd_nodata when no data is present."
case "$d_eofnblk" in
"$define") echo "And you can see EOF because read() returns 0.";;
"$undef") echo "But you can't see EOF status from read() returned value.";;
*)
?X: Should not happen, but if it does, assume the worst!
echo "(Assuming you can't see EOF status from read anyway.)"
d_eofnblk=$undef
;;
esac
;;
esac
$rm_try head.c
mtry

```

Found in path(s):

```

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/compline/nblock_io.U

```

No license file was found, but licenses were detected in source scan.

```

?RCS: $Id: i_utime.U 1 2006-08-24 12:32:52Z rmanfredi $
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: $Log: i_utime.U,v $
?RCS: Revision 3.0 1993/08/18 12:08:47 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:i_utime: Inhdr
?MAKE: -pick add $@ %<
?S:i_utime:
?S: This variable conditionally defines the I_UTIME symbol, and indicates
?S: whether a C program should include <utime.h>.
?S:.
?C:I_UTIME:
?C: This symbol, if defined, indicates to the C program that it should
?C: include <utime.h>.

```

```
?C:.
?H:#$i_utime I_UTIME /**/
?H:.
?LINT:set i_utime
:
  see if this is an utime system
set utime.h i_utime
eval $inhdr
```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/i_utime.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id$
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: $Log: d_strftime.U,v $
?RCS: Revision 3.0 1993/08/18 12:07:36 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:d_strftime: Inlibc
?MAKE: -pick add $@ %<
?S:d_strftime:
?S: This variable conditionally defines HAS_STRFTIME if strftime() is
?S: available to format locale-specific times.
?S:.
?C:HAS_STRFTIME:
?C: This symbol, if defined, indicates that the strftime routine is
?C: available to format locale-specific times.
?C:.
?H:#$d_strftime HAS_STRFTIME /**/
?H:.
?LINT:set d_strftime
: see
  if strftime exists
set strftime d_strftime
eval $inlibc
```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
```

debian-perl-5.26.1/dist/U/d_strftime.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: i_syssock.U 1 2006-08-24 12:32:52Z rmanfredi \$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic Licence,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic Licence; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: i_syssock.U,v \$

?RCS: Revision 3.0 1993/08/18 12:08:36 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?MAKE:i_syssock: Inhdr

?MAKE: -pick add \$@ %<

?S:i_syssock:

?S: This variable conditionally defines the I_SYS_SOCKET symbol, and indicates

?S: whether a C program should include <sys/socket.h> before performing socket

?S: operations.

?S:.

?C:I_SYS_SOCKET:

?C: This symbol, if defined, indicates to the C program that it should

?C: include

<sys/socket.h> before performing socket calls.

?C:.

?H:#\$i_syssock I_SYS_SOCKET /**/

?H:.

?LINT:set i_syssock

: see if this is a sys/socket.h system

set sys/socket.h i_syssock

eval \$inhdr

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-

debian-perl-5.26.1/dist/U/i_syssock.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: Typedef.U,v 3.0.1.3 1995/07/25 13:42:07 ram Exp \$

?RCS:

?RCS: Copyright (c) 1991-1993, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root
 ?RCS: of the source tree for dist 3.0.
 ?RCS:
 ?RCS: \$Log: Typedef.U,v \$
 ?RCS: Revision 3.0.1.3 1995/07/25 13:42:07 ram
 ?RCS: patch56: added backslash escapes within evals to prevent space problems
 ?RCS:
 ?RCS: Revision 3.0.1.2 1994/10/29 16:01:16 ram
 ?RCS: patch36: don't clobber visible 'val' variable, use 'varval' instead
 ?RCS:
 ?RCS: Revision 3.0.1.1 1994/08/29 16:05:14 ram
 ?RCS: patch32: created
 ?RCS:
 ?X:
 ?X: This unit checks for the definition of a given typedef.
 ?X:
 ?X: To use it, say:
 ?X: set typedef
 val_t default [includes]
 ?X: eval \$typedef
 ?X:
 ?MAKE:Typedef: cppstdin cppminus cppflags rm sed contains Oldconfig Myread
 ?MAKE: -pick add \$@ %<
 ?LINT:define typedef
 ?LINT:define typedef_ask
 ?V:typedef typedef_ask
 ?S:typedef:
 ?S: This shell variable is used internally by Configure to check
 ?S: whether a given typedef is defined or not. A typical use is:
 ?S: set typedef val_t default [includes]
 ?S: eval \$typedef
 ?S: That will return val_t set to default if the typedef was not found,
 ?S: to typedef otherwise. If no includes are specified, look in sys/types.h.
 ?S:.
 ?S:typedef_ask:
 ?S: This shell variable is used internally by Configure to check
 ?S: whether a given typedef is defined or not. If it is not defined,
 ?S: this will call the ./myread script to prompt for an answer.
 ?S: It is intended to be used to avoid unnecessary prompts.
 ?S: A typical use is
 ?S: rp="What is the type for file position used by fsetpos()?"
 ?S: set fpos_t fpostype long stdio.h sys/types.h
 ?S: eval \$typedef_ask
 ?S: This
 will set fpostype=fpos_t, if fpos_t is available. Otherwise
 ?S: it will call myread with a default of 'long', and a prompt of \$rp.
 ?S:.
 ?T:type var def inclist varval inc

```

?F:!temp.c
: define an is-a-typedef? function
typedef='type=$1; var=$2; def=$3; shift; shift; shift; inclist=$@;
case "$inclist" in
"" ) inclist="sys/types.h";;
esac;
eval "varval=\$$var";
case "$varval" in
"" )
$rm -f temp.c;
for inc in $inclist; do
echo "#include <$inc>" >>temp.c;
done;
?X: Maybe it's a #define instead of a typedef.
echo "#ifdef $type" >> temp.c;
echo "printf(\"We have $type\");" >> temp.c;
echo "#endif" >> temp.c;
$cpstdin $cppflags $cppminus < temp.c >temp.E 2>/dev/null;
if $contains $type temp.E >/dev/null 2>&1; then
eval "$var=$type";
else
eval "$var=\$def";
fi;
$rm -f temp.?.;
*) eval "$var=\$varval";;
esac'

```

?X: Originally, I eval'd \$typedef and then checked the results against

?X: \$type. Unfortunately, it then became complicated to check

?X: whether you are re-using

an old config.sh value, and the logic got

?X: so convoluted it became easier to just copy the function above

?X: and alter it slightly. A.D. 3/1998

: define an is-a-typedef? function that prompts if the type is not available.

```

typedef_ask='type=$1; var=$2; def=$3; shift; shift; shift; inclist=$@;

```

```

case "$inclist" in

```

```

"" ) inclist="sys/types.h";;

```

```

esac;

```

```

eval "varval=\$$var";

```

```

case "$varval" in

```

```

"" )

```

```

$rm -f temp.c;

```

```

for inc in $inclist; do

```

```

echo "#include <$inc>" >>temp.c;

```

```

done;

```

?X: Maybe it's a #define instead of a typedef.

```

echo "#ifdef $type" >> temp.c;

```

```

echo "printf(\"We have $type\");" >> temp.c;

```

```

echo "#endif" >> temp.c;
$ccpstdin $ccpflags $ccpminus < temp.c >temp.E 2>/dev/null;
echo " " ;
echo "$rp" | $sed -e "s/What is/Looking for/" -e "s/?/./";
if $contains $type temp.E >/dev/null 2>&1; then
echo "$type found." >&4;
eval "$var=\$type";
else
echo "$type NOT found." >&4;
dflt="$def";
. ./myread ;
eval "$var=\$ans";
fi;
$rm -f temp.?;;
*) eval "$var=\$varval";;
esac'

```

Found

in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/typedefs/Typedef.U
```

No license file was found, but licenses were detected in source scan.

```

?RCS: $Id: d_setvbuf.U,v 3.0.1.1 1994/08/29 16:11:57 ram Exp $
?RCS:
?RCS: Copyright (c) 1998 Andy Dougherty
?RCS:
?RCS: You may distribute under the terms of either the GNU General Public
?RCS: License or the Artistic License, as specified in the README file.
?RCS:
?RCS: Original Author: Andy Dougherty <doughera@lafcol.lafayette.edu>
?RCS:
?RCS: $Log: d_setvbuf.U,v $
?RCS:
?MAKE:d_setvbuf: Inlibc
?MAKE: -pick add $@ %<
?S:d_setvbuf:
?S: This variable conditionally defines the HAS_SETVBUF symbol, which
?S: indicates to the C program that the setvbuf() routine is available
?S: to change buffering on an open stdio stream.
?S:
?C:HAS_SETVBUF :
?C: This symbol, if defined, indicates that the setvbuf routine is
?C: available to change buffering on an open stdio stream.
?C: to a line-buffered mode.
?C:
?H:#$d_setvbuf HAS_SETVBUF /**/
?H:

```

```
?LINT:set d_setvbuf
: see if setvbuf exists
set setvbuf d_setvbuf
eval $inlibc
```

Found

in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/modified/d_setvbuf.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: i_arpainet.U 1 2006-08-24 12:32:52Z rmanfredi $
```

```
?RCS:
```

```
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
```

```
?RCS:
```

```
?RCS: You may redistribute only under the terms of the Artistic Licence,
```

```
?RCS: as specified in the README file that comes with the distribution.
```

```
?RCS: You may reuse parts of this distribution only within the terms of
```

```
?RCS: that same Artistic Licence; a copy of which may be found at the root
```

```
?RCS: of the source tree for dist 4.0.
```

```
?RCS:
```

```
?RCS: $Log: i_arpainet.U,v $
```

```
?RCS: Revision 3.0 1993/08/18 12:08:15 ram
```

```
?RCS: Baseline for dist 3.0 netwide release.
```

```
?RCS:
```

```
?MAKE:i_arpainet: Inhdr
```

```
?MAKE: -pick add $@ %<
```

```
?S:i_arpainet:
```

```
?S: This variable conditionally defines the I_ARPA_INET symbol,
```

```
?S: and indicates whether a C program should include <arpa/inet.h>.
```

```
?S:.
```

```
?C:I_ARPA_INET:
```

```
?C: This symbol, if defined, indicates to the C program that it should
```

```
?C: include <arpa/inet.h> to get inet_addr and friends
```

```
declarations.
```

```
?C:.
```

```
?H:#$i_arpainet I_ARPA_INET /**/
```

```
?H:.
```

```
?LINT:set i_arpainet
```

```
: see if arpa/inet.h has to be included
```

```
set arpa/inet.h i_arpainet
```

```
eval $inhdr
```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/i_arpainet.U
```

No license file was found, but licenses were detected in source scan.

```

?RCS: $Id$
?RCS:
?RCS: Copyright (c) 2000 Jarkko Hietaniemi
?RCS:
?RCS: You may distribute under the terms of either the GNU General Public
?RCS: License or the Artistic License, as specified in the README file.
?RCS:
?MAKE:d_getfsstat : Inlibc
?MAKE: -pick add $@ %<
?S:d_getfsstat:
?S: This variable conditionally defines the HAS_GETFSSTAT symbol, which
?S: indicates to the C program that the getfsstat() routine is available.
?S:.
?C:HAS_GETFSSTAT:
?C: This symbol, if defined, indicates that the getfsstat routine is
?C: available to stat filesystems in bulk.
?C:.
?H:#$d_getfsstat HAS_GETFSSTAT /**/
?H:.
?LINT:set d_getfsstat
: see if getfsstat exists
set getfsstat d_getfsstat
eval $inlibc

```

Found in path(s):

```

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/perl/d_getfsstat.U

```

No license file was found, but licenses were detected in source scan.

```

?RCS: $Id: d_getgrent_r.U,v 0RCS:
?RCS: Copyright (c) 2002,2003 Jarkko Hietaniemi
?RCS:
?RCS: You may distribute under the terms of either the GNU General Public
?RCS: License or the Artistic License, as specified in the README file.
?RCS:
?RCS: Generated by the reentr.pl from the Perl 5.8 distribution.
?RCS:
?MAKE:d_getgrent_r getgrent_r_proto: Inlibc Protochk Hasproto i_systypes \
  usethreads i_grp extern_C
?MAKE: -pick add $@ %<
?S:d_getgrent_r:
?S: This variable conditionally defines the HAS_GETGRENT_R symbol,
?S: which indicates to the C program that the getgrent_r()
?S: routine is available.
?S:.
?S:getgrent_r_proto:
?S: This variable encodes the prototype of getgrent_r.
?S: It is zero if d_getgrent_r is undef, and one of the

```

?S: REENTRANT_PROTO_T_ABC macros of reentr.h if d_getgrent_r

?S: is defined.

?S:.

?C:HAS_GETGRENTR:

?C: This symbol, if defined, indicates that the getgrent_r routine

?C: is available to

getgrent re-entrantly.

?C:.

?C:GETGRENTR_PROTO:

?C: This symbol encodes the prototype of getgrent_r.

?C: It is zero if d_getgrent_r is undef, and one of the

?C: REENTRANT_PROTO_T_ABC macros of reentr.h if d_getgrent_r

?C: is defined.

?C:.

?H:#\$d_getgrent_r HAS_GETGRENTR /**/

?H:#define GETGRENTR_PROTO \$getgrent_r_proto /**/

?H:.

?T:try hdrs d_getgrent_r_proto

: see if getgrent_r exists

set getgrent_r d_getgrent_r

eval \$inlibc

case "\$d_getgrent_r" in

"\$define")

hdrs="\$i_systypes sys/types.h define stdio.h \$i_grp grp.h"

case "\$d_getgrent_r_proto:\$usetthreads" in

":define") d_getgrent_r_proto=define

set d_getgrent_r_proto getgrent_r \$hdrs

eval \$hasproto ;;

*) ;;

esac

case "\$d_getgrent_r_proto" in

define)

case "\$getgrent_r_proto" in

"|0) try='int getgrent_r(struct group*, char*, size_t, struct group**);'

./protochk "\$extern_C \$try" \$hdrs && getgrent_r_proto=I_SBWR ;;

esac

case "\$getgrent_r_proto" in

"|0) try='int getgrent_r(struct group*, char*, int, struct group**);'

./protochk

"\$extern_C \$try" \$hdrs && getgrent_r_proto=I_SBIR ;;

esac

case "\$getgrent_r_proto" in

"|0) try='struct group* getgrent_r(struct group*, char*, size_t);'

./protochk "\$extern_C \$try" \$hdrs && getgrent_r_proto=S_SBW ;;

esac

case "\$getgrent_r_proto" in

"|0) try='struct group* getgrent_r(struct group*, char*, int);'

./protochk "\$extern_C \$try" \$hdrs && getgrent_r_proto=S_SBI ;;

```

esac
case "$getgrent_r_proto" in
"|0) try='int getgrent_r(struct group*, char*, int);'
./protochk "$extern_C $try" $hdrs && getgrent_r_proto=I_SBI ;;
esac
case "$getgrent_r_proto" in
"|0) try='int getgrent_r(struct group*, char*, int, FILE**);'
./protochk "$extern_C $try" $hdrs && getgrent_r_proto=I_SBIH ;;
esac
case "$getgrent_r_proto" in
"|0) d_getgrent_r=undef
    getgrent_r_proto=0
    echo "Disabling getgrent_r, cannot determine prototype." >&4 ;;
*) case "$getgrent_r_proto" in
    REENTRANT_PROTO*) ;;
    *) getgrent_r_proto="REENTRANT_PROTO_$getgrent_r_proto" ;;
esac
echo
"Prototype: $try" ;;
esac
;;
*) case "$usethreads" in
define) echo "getgrent_r has no prototype, not using it." >&4 ;;
esac
d_getgrent_r=undef
getgrent_r_proto=0
;;
esac
;;
*) getgrent_r_proto=0
;;
esac

```

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/threads/d_getgrent_r.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: i_ieefp.U,v \$

?RCS:

?RCS: Copyright (c) 1998 Jarkko Hietaniemi

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?MAKE:i_ieefp: Inhdr Hasfield

?MAKE: -pick add \$@ %<

?S:i_ieefp:

?S: This variable conditionally defines the I_IEEEFP symbol, and indicates

?S: whether a C program should include <iieee.h>.

?S:.

?C:I_IEEEFP:

?C: This symbol, if defined, indicates that <iieee.h> exists and

?C: should be included.

?C:.

?H:#\$i_ieefp I_IEEEFP /**/

?H:.

?LINT:set i_ieefp

: see if this is a iieee.h system

case "\$i_ieefp" in

") set iieee.h i_ieefp

eval \$inhdr

;;

esac

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/i_ieefp.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_gethname.U 1 2006-08-24 12:32:52Z rmanfredi \$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: d_gethname.U,v \$

?RCS: Revision 3.0.1.1 1994/10/29 16:13:00 ram

?RCS: patch36: call ./xenix explicitly instead of relying on PATH

?RCS:

?RCS: Revision 3.0 1993/08/18 12:06:11 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?MAKE:d_gethname d_uname d_phostname aphostname: phostname cat \

myhostname package d_portable Loc echo n c +i_whoami +usrinc \

Myread Guess Oldconfig Csym

?MAKE: -pick add \$@ %<

?S:d_gethname:

?S: This variable conditionally

defines the HAS_GETHOSTNAME symbol, which

?S: indicates to the C program that the gethostname() routine may be

?S: used to derive the host name.

?S:.

?S:d_uname:

?S: This variable conditionally defines the HAS_UNAME symbol, which

?S: indicates to the C program that the uname() routine may be

?S: used to derive the host name.

?S:.

?S:d_phostname:

?S: This variable conditionally defines the HAS_PHOSTNAME symbol, which

?S: contains the shell command which, when fed to popen(), may be

?S: used to derive the host name.

?S:.

?S:aphostname:

?S: This variable contains the command which can be used to compute the

?S: host name. The command is fully qualified by its absolute path, to make

?S: it safe when used by a process with super-user privileges.

?S:.

?C:HAS_GETHOSTNAME (GETHOSTNAME):

?C: This symbol, if defined, indicates that the C program may use the

?C: gethostname() routine to derive the host name. See also HAS_UNAME

?C: and PHOSTNAME.

?C:.

?C:HAS_UNAME (UNAME):

?C: This symbol,

if defined, indicates that the C program may use the

?C: uname() routine to derive the host name. See also HAS_GETHOSTNAME

?C: and PHOSTNAME.

?C:.

?C:PHOSTNAME:

?C: This symbol, if defined, indicates the command to feed to the

?C: popen() routine to derive the host name. See also HAS_GETHOSTNAME

?C: and HAS_UNAME. Note that the command uses a fully qualified path,

?C: so that it is safe even if used by a process with super-user

?C: privileges.

?C:.

?C:HAS_PHOSTNAME:

?C: This symbol, if defined, indicates that the C program may use the

?C: contents of PHOSTNAME as a command to feed to the popen() routine

?C: to derive the host name.

?C:.

?H:%<:#\$d_gethname HAS_GETHOSTNAME /**/
?H:%<:#\$d_uname HAS_UNAME /**/
?H:%<:#\$d_phostname HAS_PHOSTNAME /**/
?H:%<:#ifdef HAS_PHOSTNAME
?H:%<:#define PHOSTNAME "\$aphostname" /* How to get the host name */
?H:%<:#endif
?H:.

?T:file val call

?LINT:change i_whoami

```

: see how we will look up host name
echo " "
call="
@if HAS_GETHOSTNAME
if
set gethostname val -f d_gethname; eval $csym; $val; then
echo 'gethostname() found.' >&4
d_gethname="$define"
call=gethostname
fi
@end
@if HAS_UNAME
if set uname val -f d_uname; eval $csym; $val; then
if ./xenix; then
$cat <<'EOM'
uname() was found, but you're running xenix, and older versions of xenix
have a broken uname(). If you don't really know whether your xenix is old
enough to have a broken system call, use the default answer.

```

```

EOM
dflt=y
case "$d_uname" in
"$define") dflt=n;;
esac
rp='Is your uname() broken?'
./myread
case "$ans" in
n*) d_uname="$define"; call=uname;;
esac
else
echo 'uname() found.' >&4
d_uname="$define"
case "$call" in
") call=uname ;;
esac
fi
fi
@end
case "$d_gethname" in
") d_gethname="$undef";;
esac
case "$d_uname" in
") d_uname="$undef";;
esac
@if PHOSTNAME || MYHOSTNAME
case "$d_uname$d_gethname" in
*define*)
dflt=n

```

```
cat <<EOM
```

Every now and then someone has a \$call() that lies about the hostname but can't be fixed

for political or economic reasons. If you wish, I can

```
@if MYHOSTNAME && PHOSTNAME
```

pretend \$call() isn't there and maybe compile in the hostname or compute it from the '\$phostname' command at run-time.

```
@elsif MYHOSTNAME
```

pretend \$call() isn't there and maybe compile in the hostname.

```
@elsif PHOSTNAME
```

pretend \$call() isn't there and maybe compute hostname at run-time thanks to the '\$phostname' command.

```
@elsif WHOAMI
```

get the hostname from whomai.h (provided you have one).

```
@else
```

simply ignore your host name and use something like "noname" instead.

```
@end
```

```
EOM
```

```
rp="Shall I ignore $call() from now on?"
```

```
. ./myread
```

```
case "$ans" in
```

```
y*) d_uname="$undef" d_gethname="$undef"; $echo $n "Okay...$c";;
```

```
esac;;
```

```
esac
```

```
@end
```

```
@if PHOSTNAME || aphostname
```

?X: Compute the full path name for the command

```
case "$phostname" in
```

```
") aphostname="";;
```

```
*) case "$aphostname" in
```

```
/*) ;;
```

```
*) set X $phostname
```

```
shift
```

```
file=$1
```

```
shift
```

```
file=`./loc $file $file $pth`
```

```
aphostname=`echo $file $*`
```

```
::
```

```
esac
```

```
::
```

```
esac
```

```
@end
```

```
@if
```

```
PHOSTNAME && MYHOSTNAME
```

```
case "$d_uname$d_gethname" in
```

```
*define*) ;;
```

```

*)
case "$phostname" in
") ;;
*)
$cat <<EOT

```

There is no gethostname() or uname() on this system. You have two possibilities at this point:

- 1) You can have your host name (\$myhostname) compiled into \$package, which lets \$package start up faster, but makes your binaries non-portable, or
- 2) you can have \$package use a

```
popen("$aphostname","r")
```

which will start slower but be more portable.

```
@ if WHOAMI
```

Option 1 will give you the option of using whoami.h if you have one.

```
@ end
```

If you want option 2 but with a different command, you can edit config.sh at the end of this shell script.

```
EOT
```

```

case "$d_phostname" in
"$define") dflt=n;;
"$undef") dflt=y;;
")
case "$d_portable" in
"$define") dflt=n ;;
*) dflt=y ;;
esac;;
esac
rp="Do you want your host name compiled in?"
./myread
case "$ans" in
n*) d_phostname="$define" ;;
*) aphostname=""; d_phostname="$undef";;
esac;;
esac
case
"$aphostname" in
")
@ if WHOAMI
case "$i_whoami" in
"$define")
dflt=y
$cat <<EOM

```

No hostname function--you can either use the whoami.h file, which has this line:

```
`grep sysname $usrinc/whoami.h`
```

or you can have the name we came up with earlier (\$myhostname) hardwired in.

EOM

```
rp="Use whoami.h to get hostname?"  
. ./myread  
case "$ans" in  
n*) i_whoami="$undef";;  
esac  
;;  
"$undef")  
$cat <<EOM
```

No hostname function and no whoami.h -- hardwiring "\$myhostname".

EOM

```
;;  
esac;;  
@ else  
echo 'No hostname function -- hardwiring "$myhostname"! '>&4;;  
@ end  
esac;;  
esac  
@elsif PHOSTNAME  
case "$d_uname$d_gethname" in  
*define*) ;;  
*)  
case "$phostname" in  
")  
@ if WHOAMI  
case "$i_whoami" in  
"$define")  
$cat <<EOM
```

No hostname function--we'll use the whoami.h file, which has this line:

```
`grep sysname $usrinc/whoami.h`
```

EOM

```
;;  
*) echo "There will be no way for $package to get your hostname." >&4;;  
esac;;  
@ else  
echo "There will be no way  
for $package to get your hostname." >&4;;  
@ end  
*)
```

```

echo "I'll use 'popen(\"\"$aphostname\", \"r\")\" to get your hostname." >&4
;;
esac;;
esac
@elseif MYHOSTNAME
case "$d_underscore$d_gethostname" in
*define*);;
*)
@ if WHOAMI
case "$i_whoami" in
"$define")
dflt=y
$cat <<EOM

```

No hostname function--you can either use the whoami.h file, which has this line:

```
`grep sysname $usrinc/whoami.h`
```

or you can have the name we came up with earlier (\$myhostname) hardwired in.

EOM

```

rp="Use whoami.h to get hostname?"
. ./myread
case "$ans" in
n*) i_whoami="$undef";;
esac
;;
"$undef")
echo 'No whoami.h--hardwiring "$myhostname".' >&4;;
esac;;
@ else
echo 'Hardwiring "$myhostname".' >&4;;
@ end
esac
@end
case "$d_phostname" in
") d_phostname="$undef";;
esac

```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/modified/d_gethostname.U
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_voidsig.U,v 3.0.1.3 1995/05/12 12:12:46 ram Exp \$

?RCS:

?RCS: Copyright (c) 1991-1993, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 3.0.

?RCS:

?RCS: \$Log: d_voidsig.U,v \$

?RCS: Revision 3.0.1.3 1995/05/12 12:12:46 ram

?RCS: patch54: made cppflags dependency optional

?RCS:

?RCS: Revision 3.0.1.2 1994/08/29 16:20:35 ram

?RCS: patch32: now sets signal_t only once d_voidsig is known (WED)

?RCS:

?RCS: Revision 3.0.1.1 1994/06/20 06:59:54 ram

?RCS: patch30: now properly sets signal_t when re-using previous value

?RCS:

?RCS: Revision 3.0 1993/08/18 12:07:56 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?MAKE:d_voidsig

signal_t: rm contains cppstdin cppminus +cppflags test Myread \
Oldconfig Setvar Findhdr

?MAKE: -pick add \$@ %<

?S:d_voidsig:

?S: This variable conditionally defines VOIDSIG if this system

?S: declares "void (*signal(...))()" in signal.h. The old way was to

?S: declare it as "int (*signal(...))()".

?S:.

?S:signal_t:

?S: This variable holds the type of the signal handler (void or int).

?S:.

?C:VOIDSIG:

?C: This symbol is defined if this system declares "void (*signal(...))()" in

?C: signal.h. The old way was to declare it as "int (*signal(...))()". It

?C: is up to the package author to declare things correctly based on the

?C: symbol.

?C:.

?C:Signal_t (SIGNAL_T):

?C: This symbol's value is either "void" or "int", corresponding to the

?C: appropriate return type of a signal handler. Thus, you can declare

?C: a signal handler using "Signal_t (*handler)()", and define the

?C: handler using "Signal_t handler(sig)".

?C:.

?H:#\$d_voidsig VOIDSIG /**/
?H:#define
Signal_t \$signal_t /* Signal handler's return type */

?H:.

?T:xxx

?LINT:set d_voidsig

```

: see if signal is declared as pointer to function returning int or void
echo " "
xxx=`./findhdr signal.h`
$test "$xxx" && $cppstdin $cppminus $cppflags < $xxx >$$.tmp 2>/dev/null
if $contains 'int.*\*[ ]*signal' $$$.tmp >/dev/null 2>&1 ; then
  echo "You have int (*signal())() instead of void." >&4
  val="$undef"
elif $contains 'void.*\*[ ]*signal' $$$.tmp >/dev/null 2>&1 ; then
  echo "You have void (*signal())()." >&4
  val="$define"
elif $contains 'extern[ ]*[ ]*signal' $$$.tmp >/dev/null 2>&1 ; then
  echo "You have int (*signal())() instead of void." >&4
  val="$undef"
?X: This next test is kind of sloppy, but it catches Linux
?X: which has a
?X: typedef void (*__sig_handler_t) (int) ;
?X: A better fix would be to compile a C program with the proper
?X: prototype, but since nearly everyone uses void, we'll just go with
?X: this.
elif $contains 'void.*\*.*sig' $$$.tmp >/dev/null 2>&1 ; then
  echo "You
  have void (*signal())()." >&4
  val="$define"
else
  case "$d_voidsig" in
  ")
  echo "I can't determine whether signal handler returns void or int..." >&4
  dflt=void
  rp="What type does your signal handler return?"
  . ./myread
  case "$ans" in
  v*) val="$define";;
  *) val="$undef";;
  esac;;
  "$define")
  echo "As you already told me, signal handler returns void." >&4
  val="$define"
  ;;
  *) echo "As you already told me, signal handler returns int." >&4
  val="$undef"
  ;;
  esac
fi
set d_voidsig
eval $setvar
case "$d_voidsig" in
"$define") signal_t="void";;
*) signal_t="int";;

```

```
esac
$rm -f $$tmp
```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-  
debian-perl-5.26.1/U/modified/d_voidsig.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id$
```

```
?RCS:
```

```
?RCS: Copyright (c) 1998, Jarkko Hietaniemi
```

```
?RCS:
```

```
?RCS: You may redistribute only under the terms of the Artistic License,
```

```
?RCS: as specified in the README file that comes with the distribution.
```

```
?RCS: You may reuse parts of this distribution only within the terms of
```

```
?RCS: that same Artistic License; a copy of which may be found at the root
```

```
?RCS: of the source tree for dist 3.0.
```

```
?RCS:
```

```
?MAKE:i_syssecrets: Inhdr
```

```
?MAKE: -pick add $@ %<
```

```
?S:i_syssecrets:
```

```
?S: This variable conditionally defines the I_SYS_SECURITY symbol,
```

```
?S: and indicates whether a C program should include <sys/security.h>.
```

```
?S:.
```

```
?C:I_SYS_SECURITY:
```

```
?C: This symbol, if defined, indicates to the C program that it should
```

```
?C: include <sys/security.h>.
```

```
?C:.
```

```
?H:#$i_syssecrets I_SYS_SECURITY /**/
```

```
?H:.
```

```
?LINT:set i_syssecrets
```

```
: see if sys/security.h is available
```

```
set sys/security.h i_syssecrets
```

```
eval $inhdr
```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-  
debian-perl-5.26.1/U/acl/i_syssecrets.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: d_setgrent.U,v $
```

```
?RCS:
```

```
?RCS: Copyright (c) 1998 Andy Dougherty
```

```
?RCS:
```

```
?RCS: You may distribute under the terms of either the GNU General Public
```

```
?RCS: License or the Artistic License, as specified in the README file.
```

```
?RCS:
```

```
?RCS: $Log: d_setgrent.U,v $
```

?RCS:
?MAKE:d_setgrent: Inlibc
?MAKE: -pick add \$@ %<
?S:d_setgrent:
?S: This variable conditionally defines the HAS_SETGRENТ symbol, which
?S: indicates to the C program that the setgrent() routine is available
?S: for initializing sequential access to the group database.
?S:.
?C:HAS_SETGRENТ:
?C: This symbol, if defined, indicates that the setgrent routine is
?C: available for initializing sequential access of the group database.
?C:.
?H:#\$d_setgrent HAS_SETGRENТ /**/
?H:.
?LINT:set d_setgrent
: see if setgrent exists
set setgrent d_setgrent
eval \$inlibc

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/modified/d_setgrent.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$
?RCS:
?RCS: Copyright (c) 1999, Jarkko Hietaniemi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 3.0.
?RCS:
?MAKE:d_sem_open: Inlibc
?MAKE: -pick add \$@ %<
?S:d_sem_open:
?S: This variable conditionally defines HAS_SEM_OPEN if sem_open() is
?S: available to open a POSIX semaphore.
?S:.
?C:HAS_SEM_OPEN:
?C: This symbol, if defined, indicates that the sem_open system call is
?C: available to open a POSIX semaphore.
?C:.
?H:#\$d_sem_open HAS_SEM_OPEN /**/
?H:.
?LINT:set d_sem_open
: see if sem_open exists

```
set sem_open d_sem_open
eval $inlibc
```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/perl/d_sem_open.U
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: Oldconfig.U,v \$

?RCS: Revision 3.0.1.10 1997/02/28 15:06:39 ram

?RCS: patch61: added support for src.U

?RCS: patch61: new OSNAME define

?RCS: patch61: can now sense new OSes

?RCS:

?RCS: Revision 3.0.1.9 1995/07/25 13:40:51 ram

?RCS: patch56: now knows about OS/2 platforms

?RCS:

?RCS: Revision 3.0.1.8 1995/05/12 12:04:18 ram

?RCS: patch54: config.sh reload logic now knows about new -K switch

?RCS: patch54: cleaned up and extended osvers for DEC OSF/1 (ADO)

?RCS: patch54: added MachTen detection

(ADO)

?RCS:

?RCS: Revision 3.0.1.7 1995/02/15 14:13:41 ram

?RCS: patch51: adapted osvers computation for AIX (ADO)

?RCS:

?RCS: Revision 3.0.1.6 1995/01/30 14:27:15 ram

?RCS: patch49: unit Options.U now exports file optdef.sh, not a variable

?RCS: patch49: update code for myuname changed (WED)

?RCS:

?RCS: Revision 3.0.1.5 1995/01/11 15:15:36 ram

?RCS: patch45: added quotes around the INITPROG variable (ADO)

?RCS: patch45: allows variable overriding after config file loading

?RCS:

?RCS: Revision 3.0.1.4 1994/10/29 15:57:05 ram

?RCS: patch36: added ?F: line for metalint file checking

?RCS: patch36: merged with the version used for perl5's Configure (ADO)

?RCS:

?RCS: Revision 3.0.1.3 1994/05/06 14:24:17 ram

?RCS: patch23: added support for osf1 hints

?RCS: patch23: new support for solaris and i386 systems (ADO)

?RCS:

?RCS: Revision 3.0.1.2 1994/01/24 14:05:02 ram

?RCS: patch16: added post-processing on myuname for Xenix targets

?RCS: patch16: message proposing config.sh defaults made consistent

?RCS:

?RCS: Revision 3.0.1.1 1993/09/13 15:56:32 ram

?RCS: patch10: force use of config.sh when -d option is used (WAD)

?RCS: patch10: complain about non-existent hint files (WAD)

?RCS: patch10: added Options dependency for fastread variable

?RCS:

?RCS: Revision 3.0 1993/08/18 12:05:12 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?X:

?X: This unit tries to remember what we did last time we ran Configure, mostly

?X: for the sake of setting defaults.

?X:

?MAKE:Oldconfig hint myuname osname osvers: Instruct Myread Checkcc \
Mksymlinks Loc Options Tr src trnl ln uname sh awk sed test cat grep \
rm lns tr n c contains targetarch

?MAKE: -pick wipe \$@ %<

?S:myuname:

?S: The output of 'uname -a' if available, otherwise the hostname. On Xenix,

?S: pseudo variables assignments in the output are stripped, thank you. The

?S: whole thing is then lower-cased.

?S:.

?S:hint:

?S: Gives the type of hints used for previous answers. May be one of

?S: "default",

"recommended" or "previous".

?S:.

?S:osname:

?S: This variable contains the operating system name (e.g. sunos,

?S: solaris, hpux, etc.). It can be useful later on for setting

?S: defaults. Any spaces are replaced with underscores. It is set

?S: to a null string if we can't figure it out.

?S:.

?S:osvers:

?S: This variable contains the operating system version (e.g.

?S: 4.1.3, 5.2, etc.). It is primarily used for helping select

?S: an appropriate hints file, but might be useful elsewhere for

?S: setting defaults. It is set to " if we can't figure it out.

?S: We try to be flexible about how much of the version number

?S: to keep, e.g. if 4.1.1, 4.1.2, and 4.1.3 are essentially the

?S: same for this package, hints files might just be os_4.0 or
?S: os_4.1, etc., not keeping separate files for each little release.
?S:.
?C:OSNAME:
?C: This symbol contains the name of the operating system, as determined
?C: by Configure. You shouldn't rely on it too much; the specific
?C: feature tests from Configure are generally more reliable.
?C:.
?C:OSVERS:
?C: This symbol contains the version of the operating system, as determined
?C: by Configure. You shouldn't rely on it too much; the specific
?C: feature tests from Configure are generally more reliable.
?C:.
?H:#define OSNAME "\$osname" /**/
?H:#define OSVERS "\$osvers" /**/
?H:.
?F:!config.sh
?T:tmp tmp_n tmp_c tmp_sh file
?T:xxxxfile xxxfile xxfile xfile hintfile newmyuname
?T:tans _ isesix INITPROG DJGPP has_uname
?D:osname="
?LINT:change n c sh
?LINT:extern hostarch
?LINT:change hostarch
: Determine the name of the machine
myuname=`\$uname -a 2>/dev/null`
\$test -z "\$myuname" && myuname=`hostname 2>/dev/null`
?X: Special mention for Xenix, whose 'uname -a' gives us output like this:
?X: sysname=XENIX
?X: nodename=whatever
?X: release=2.3.2 .. etc...
?X: Therefore, we strip all this variable assignment junk and remove all the
?X: new lines to keep the myuname variable sane... --RAM
myuname=`echo \$myuname | \$sed -e
's/^[^=]*=/' -e 's/\\//g' | \
./tr '[A-Z]' '[a-z]' | \$tr \$trnl ' '`
?X: Save the value we just computed to reset myuname after we get done here.
newmyuname="\$myuname"
\$test -f "\$uname\$_exe" && has_uname=y

: Guessing of the OS name -- half the following guesses are probably wrong...
: If you have better tests or hints, please send them to the metaconfig
: authors and to <MAINTLOC>
\$test -f /irix && osname=irix
\$test -f /xenix && osname=sco_xenix
\$test -f /dynix && osname=dynix
\$test -f /dnix && osname=dnix

```

$test -f /lynx.os && osname=lynxos
$test -f /unicos && osname=unicos && osvers=`$uname -r`
$test -f /unicosmk && osname=unicosmk && osvers=`$uname -r`
$test -f /unicosmk.ar && osname=unicosmk && osvers=`$uname -r`
$test -f /bin/mips && /bin/mips && osname=mips
$test -d /NextApps && set X `hostinfo | $grep 'NeXT Mach.*:' | \
  $sed -e 's://' -e 's\./_/'` && osname=next && osvers=$4
$test -d /usr/apollo/bin && osname=apollo
$test -f /etc/saf/_sactab && osname=svr4
$test -d /usr/include/minix
  && osname=minix
$test -f /system/gnu_library/bin/ar.pm && osname=vos
if $test -d /MachTen -o -d /MachTen_Folder; then
?X: MachTen uname -a output looks like
?X: xxx 4 0.0 Macintosh
?X: MachTen /sbin/version output looks like
?X: MachTen 4.0 Mon Aug 28 10:18:00 1995
?X: MachTen 3.x had the 'version' command in /usr/etc/version.
  osname=machten
  if $test -x /sbin/version; then
    osvers=`/sbin/version | $awk '{print $2}' |
    $sed -e 's/[A-Za-z]$/'`
  elif $test -x /usr/etc/version; then
    osvers=`/usr/etc/version | $awk '{print $2}' |
    $sed -e 's/[A-Za-z]$/'`
  else
    osvers="$2.$3"
  fi
fi
$test -f /sys/posix.dll &&
$test -f /usr/bin/what &&
set X `usr/bin/what /sys/posix.dll` &&
$test "$3" = UWIN &&
osname=uwin &&
osvers="$5"
?X: If we have uname, we already computed a suitable uname -a output, correctly
?X: formatted for Xenix, and it lies in $myuname.
if $test "X$has_uname" != X; then
  set X $myuname
  shift
  case "$5" in
  fps*) osname=fps ;;
  mips*)
  case "$4"
  in
  umips) osname=umips ;;
  *) osname=mips ;;
  esac;;

```

```

[23]100) osname=mips ;;
next*) osname=next ;;
?X: Interactive Unix.
i386*)
tmp=`/bin/uname -X 2>/dev/null|awk '/3\.2v[45]/{ print $(NF) }`
if $test "$tmp" != "" -a "$3" = "3.2" -a -f /etc/systemid; then
  osname='sco'
  osvers=$tmp
elif $test -f /etc/kconfig; then
  osname=isc
if $test "$lns" = "$ln -s"; then
  osvers=4
elif $contains _SYSV3 /usr/include/stdio.h > /dev/null 2>&1 ; then
  osvers=3
elif $contains _POSIX_SOURCE /usr/include/stdio.h > /dev/null 2>&1 ; then
  osvers=2
fi
fi
tmp=""
;;

```

?X: MS-DOS djgpp uname -a output looks like:

?X: ms-dos xxx 6 22 pc

?X: \$1 is the "dos flavor" (need not be "ms-dos").

?X: \$2 is the node name

?X: \$3 and \$4 are version/subversion

?X: \$5 is always "pc", but that might not be unique to DJGPP.

?X: (e.g. Solaris_x86 has \$5 = i86pc, which doesn't actually conflict,

?X: but it's close enough that I can easily imagine other vendors also

?X: using variants

of pc* in \$5.)

?X: The "DJGPP" environment variable is always set when djgpp is active.

pc*)

```
if $test -n "$DJGPP"; then
```

```
  osname=dos
```

```
  osvers=djgpp
```

```
fi
```

```
;;
```

```
esac
```

```
case "$1" in
```

```
  aix) osname=aix
```

?X: aix 4.1 uname -a output looks like

?X: AIX foo 1 4 000123456789

?X: where \$4 is the major release number and \$3 is the (minor) version.

?X: More detail on the version is available with the oslevel command.

?X: in 3.2.x, it output a string (see case statements below). In 4.1,

?X: it puts out something like 4.1.1.0

```
tmp=`( oslevel) 2>/dev/null || echo "not found") 2>&1`
```

```
case "$tmp" in
```

```

'not found') osvers="$4"."$3" ;;
'<3240'|<>3240') osvers=3.2.0 ;;
'=3240'|>3240'|<3250'|<>3250') osvers=3.2.4 ;;
'=3250'|>3250') osvers=3.2.5 ;;
*) osvers=$tmp;;
esac
;;
bsd386) osname=bsd386
osvers=`$uname -r`
;;
cygwin*) osname=cygwin
osvers="$3"
;;
*dc.osx) osname=dcosx
osvers="$3"
;;
dnix) osname=dnix
osvers="$3"
;;
domainos) osname=apollo
osvers="$3"
;;
dgux)
osname=dgux
osvers="$3"
;;
?X: uname -a returns
?X: DYNIX/ptx xxx 4.0 V4.1.2 i386
dynixptx*) osname=dynixptx
osvers=`echo "$4"|sed 's/^v//'^`
;;
freebsd) osname=freebsd
osvers="$3" ;;
genix) osname=genix ;;
?X: HP-UX uname -a gives something like
?X: HP-UX foobar B.10.20 A 9000/735 2016483812 two-user license
?X: Preserve the full 10.20 string instead of the previous plain '10'.
?X: Thanks to Graham Barr. --AD 6/30/1998
hp*) osname=hpux
osvers=`echo "$3" | $sed 's,.*\.[0-9]*\.[0-9]*),\1,`
;;
irix*) osname=irix
case "$3" in
4*) osvers=4 ;;
5*) osvers=5 ;;
*) osvers="$3" ;;
esac
;;

```

```

linux) osname=linux
case "$3" in
*) osvers="$3" ;;
esac
;;
MiNT) osname=mint
;;
netbsd*) osname=netbsd
osvers="$3"
;;
news-os) osvers="$3"
case "$3" in
4*) osname=newsos4 ;;
*) osname=newsos ;;
esac
;;
next*) osname=next ;;
nonstop-ux) osname=nonstopux ;;
openbsd) osname=openbsd
osvers="$3"
;;
POSIX-BC | posix-bc
) osname=posix-bc
osvers="$3"
;;
powerux | power_ux | powermax_os | powermaxos | \
powerunix | power_unix) osname=powerux
osvers="$3"
;;
qnx) osname=qnx
osvers="$4"
;;
solaris) osname=solaris
case "$3" in
5*) osvers=`echo $3 | $sed 's/^5/2/g'` ;;
*) osvers="$3" ;;
esac
;;
sunos) osname=sunos
case "$3" in
5*) osname=solaris
osvers=`echo $3 | $sed 's/^5/2/g'` ;;
*) osvers="$3" ;;
esac
;;
titanos) osname=titanos
case "$3" in
1*) osvers=1 ;;

```

```

2*) osvers=2 ;;
3*) osvers=3 ;;
4*) osvers=4 ;;
*) osvers="$3" ;;
esac
;;
ultrix) osname=ultrix
osvers="$3"
;;
osf1|m1s+) case "$5" in
alpha)
?X: DEC OSF/1 myuname -a output looks like: osf1 xxxx t3.2 123.4 alpha
?X: where the version number can be something like [xvt]n.n
osname=dec_osf
?X: sizer knows the minor minor version: the letter
osvers=`sizer -v | awk '{print $3}' | \
./tr '[A-Z]' '[a-z]' | sed 's/^[xvt]//'^
case "$osvers" in
[1-9].[0-9]*) ;;
*) osvers=`echo
"$3" | sed 's/^[xvt]//'^ ;;
esac
;;
hp*) osname=hp_osf1 ;;
mips) osname=mips_osf1 ;;
?X: hp and mips were unsupported Technology Releases -- ADO, 24/10/94
esac
;;
unixware) osname=svr5
osvers="$4"
;;
uts) osname=uts
osvers="$3"
;;
vos) osvers="$3"
;;
$2) case "$osname" in
*isc*) ;;
*freebsd*) ;;
svr*)
: svr4.x or possibly later
case "svr$3" in
${osname}*)
osname=svr$3
osvers=$4
;;
esac
case "$osname" in

```

```

svr4.0)
: Check for ESIX
if $test -f /stand/boot ; then
    eval ` $grep '^INITPROG=[a-z/0-9]*$' /stand/boot `
    if $test -n "$INITPROG" -a -f "$INITPROG"; then
        isesix=`strings -a $INITPROG | \
            $grep 'ESIX SYSTEM V/386 Release 4.0`
        if $test -n "$isesix"; then
            osname=esix4
        fi
    fi
fi
;;
esac
;;
*) if $test -f /etc/systemid; then
    osname=sco
    set `echo $3 | $sed 's/./ /g` $4
    if $test -f $src/hints/sco_$1_$2_$3.sh; then
        osvers=$1.$2.$3
    elif $test
-f $src/hints/sco_$1_$2.sh; then
        osvers=$1.$2
    elif $test -f $src/hints/sco_$1.sh; then
        osvers=$1
    fi
else
    case "$osname" in
        ") : Still unknown. Probably a generic Sys V.
        osname="sysv"
        osvers="$3"
        ;;
    esac
fi
;;
esac
;;
*) case "$osname" in
        ") : Still unknown. Probably a generic BSD.
        osname="$1"
        osvers="$3"
        ;;
    esac
;;
esac
else
?X: Try to identify sony's NEWS-OS (BSD unix)
if $test -f /vmunix -a -f $src/hints/news_os.sh; then

```

```

(what /vmunix | UU/tr '[A-Z]' '[a-z]') > UU/kernel.what 2>&1
if $contains news-os UU/kernel.what >/dev/null 2>&1; then
    osname=news_os
fi
$rm -f UU/kernel.what
?X: Maybe it's OS/2 or DOS or something similar
elif $test -d c:/.; then
    set X $myuname
    osname=os2
    osvers="$5"
fi
fi

```

: Try to determine whether config.sh was made on this system

```

case "$config_sh" in
")
?X: indentation wrong on purpose--RAM
dflt=n
case "$knowitall" in
")
if test -f ../config.sh; then
    if $contains
myuname= ../config.sh >/dev/null 2>&1; then
    eval "$grep myuname= ../config.sh`"
fi
if test "X$myuname" = "X$newmyuname"; then
    dflt=y
fi
fi
;;
*) dflt=y;;
esac

```

: Get old answers from config file if it was generated on the same system

```

hint=default
if $test -f ../config.sh; then
    echo " "
    rp="I see a config.sh file. Shall I use it to set the defaults?"
    . ./myread
    case "$ans" in
n*|N*) echo "OK, I'll ignore it."
mv ../config.sh ../config.sh.old
myuname="$newmyuname"
;;
*) echo "Fetching default answers from your old config.sh file..." >&4
tmp_n="$n"
tmp_c="$c"
tmp_sh="$sh"

```

```

../config.sh
cp ../config.sh .
n="$tmp_n"
c="$tmp_c"
hint=previous
;;
esac
fi
?X: remember, case indentation is wrong--RAM
;;
*)
echo " "
echo "Fetching default answers from $config_sh..." >&4
tmp_n="$n"
tmp_c="$c"
tmp_sh="$sh"
cd ..
?X: preserve symbolic links, if any
cp $config_sh config.sh 2>/dev/null
chmod +w config.sh
. ./config.sh
cd UU
cp ../config.sh
.
n="$tmp_n"
c="$tmp_c"
hint=previous
;;
esac
?X: Older versions did not always set $sh.
case "$sh" in
") sh="$tmp_sh" ;;
esac
$test "$soverride" && . ./optdef.sh

: Restore computed paths
for file in $loclist $strylist; do
eval $file="\$_$file"
done

./checkcc
?X: Cross-compiling support
case "$targetarch" in
") ;;
*) hostarch=$osname
osname=`echo $targetarch|sed 's,^[^-]*-,`
osvers="
;;

```

esac

```
@if { test -d ../hints }
: Offer them some hints based on their OS
cd ..
?X: Since we are now at the root of the source tree, we must use $src
?X: to access the sources and not $src. See src.U for details...
if $test ! -f config.sh; then
$cat <<EOM
```

First time through, eh? I have some defaults handy for some systems that need some extra help getting the Configure answers right:

EOM

```
(cd $src/hints; ls -C *.sh) | $sed 's/\./ /g' >&4
dflt=""
```

```
: Now look for a hint file osname_osvers, unless one has been
: specified already.
```

```
case "$hintfile" in
"|' ')
file=`echo "${osname}_${osvers}"
| $sed -e 's%\.\%_ %g' -e 's%_ %%%`
: Also try without trailing minor version numbers.
xfile=`echo $file | $sed -e 's%[_]*$%%`
xxfile=`echo $xfile | $sed -e 's%[_]*$%%`
xxxfile=`echo $xxfile | $sed -e 's%[_]*$%%`
xxxxfile=`echo $xxxfile | $sed -e 's%[_]*$%%`
case "$file" in
") dflt=none ;;
*) case "$osvers" in
") dflt=$file
;;
*) if $test -f $src/hints/$file.sh ; then
dflt=$file
elif $test -f $src/hints/$xfile.sh ; then
dflt=$xfile
elif $test -f $src/hints/$xxfile.sh ; then
dflt=$xxfile
elif $test -f $src/hints/$xxxfile.sh ; then
dflt=$xxxfile
elif $test -f $src/hints/$xxxxfile.sh ; then
dflt=$xxxxfile
elif $test -f "$src/hints/${osname}.sh" ; then
dflt="${osname}"
else
dflt=none
fi
```

```

;;
esac
;;
esac
if $test -f Policy.sh ; then
case "$dflt" in
*Policy*) ;;
none) dflt="Policy" ;;
*) dflt="Policy $dflt" ;;
esac
fi
;;
*)
dflt=`echo
$hintfile | $sed 's/\.sh$/'^
;;
esac

```

```

if $test -f Policy.sh ; then
$cat <<EOM

```

There's also a Policy hint file available, which should make the site-specific (policy) questions easier to answer.

EOM

```

fi

```

```

$cat <<EOM

```

You may give one or more space-separated answers, or "none" if appropriate. A well-behaved OS will have no hints, so answering "none" or just "Policy" is a good thing. DO NOT give a wrong version or a wrong OS.

EOM

```

rp="Which of these apply, if any?"
. UU/myread
tans=$ans
for file in $tans; do
if $test X$file = XPolicy -a -f Policy.sh; then
. Policy.sh
$cat Policy.sh >> UU/config.sh
elif $test -f $src/hints/$file.sh; then
. $src/hints/$file.sh
$cat $src/hints/$file.sh >> UU/config.sh
elif $test X"$tans" = X -o X"$tans" = Xnone ; then
: nothing
else

```

```

: Give one chance to correct a possible typo.
echo "$file.sh does not exist"
dflt=$file
rp="hint to use instead?"
. UU/myread
for file in $ans; do
  if $test -f "$src/hints/$file.sh";
then
  . $src/hints/$file.sh
  $cat $src/hints/$file.sh >> UU/config.sh
  elif $test X$ans = X -o X$ans = Xnone ; then
  : nothing
  else
  echo "$file.sh does not exist -- ignored."
  fi
done
fi
done

hint=recommended
: Remember our hint file for later.
if $test -f "$src/hints/$file.sh" ; then
  hintfile="$file"
else
  hintfile=""
fi
fi
cd UU
?X: From here on, we must use $rsrc instead of $src

@end
: Process their -A options
. ./posthint.sh

@if osname || osvers
: Ask them to confirm the OS name
cat << EOM

```

Configure uses the operating system name and version to set some defaults. The default value is probably right if the name rings a bell. Otherwise, since spelling matters for me, either accept the default or answer "none" to leave it blank.

```

EOM
@end
@if osname
case "$osname" in
"|" )

```

```

case "$hintfile" in
"| " |none) dflt=none ;;
*) dflt=`echo $hintfile | $sed -e 's/\.sh$//' -e 's/_.*$//'^` ;;
esac
;;
*) dflt="$osname" ;;
esac
rp="Operating
system name?"
./myread
case "$ans" in
none) osname="" ;;
*) osname=`echo "$ans" | $sed -e 's/[ ][ ]*/_/g' | ./tr '[A-Z]' '[a-z]'^` ;;
esac
@end
@if osvers
@if osname
echo " "
@end
case "$osvers" in
"| ')
case "$hintfile" in
"| " |none) dflt=none ;;
*) dflt=`echo $hintfile | $sed -e 's/\.sh$//' -e 's/^[^_]*//'^`
dflt=`echo $dflt | $sed -e 's/^\_/' -e 's/_./g'^`
case "$dflt" in
"| ') dflt=none ;;
esac
;;
esac
;;
*) dflt="$osvers" ;;
esac
rp="Operating system version?"
./myread
case "$ans" in
none) osvers="" ;;
*) osvers="$ans" ;;
esac

@end

```

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/Oldconfig.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

```

?RCS:
?RCS: Copyright (c) 2001 Jarkko Hietaniemi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 3.0.
?RCS:
?MAKE:d_sresuproto: Hasproto i_unistd
?MAKE: -pick add $@ %<
?S:d_sresuproto:
?S: This variable conditionally defines the HAS_SETRESUID_PROTO symbol,
?S: which indicates to the C program that the system provides
?S: a prototype for the setresuid() function. Otherwise, it is
?S: up to the program to supply one.
?S:.
?C:HAS_SETRESUID_PROTO:
?C: This symbol, if defined, indicates that the system provides
?C: a prototype for the setresuid() function. Otherwise, it is up
?C: to the program to supply one. Good guesses are
?C: extern
int setresuid(uid_t ruid, uid_t euid, uid_t suid);
?C:.
?H:#$d_sresuproto HAS_SETRESUID_PROTO /**/
?H:.
?LINT:set d_sresuproto
: see if prototype for setresuid is available
echo " "
set d_sresuproto setresuid $i_unistd unistd.h
eval $hasproto

```

Found in path(s):

```

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/perl/d_sresuproto.U

```

No license file was found, but licenses were detected in source scan.

```

?RCS: $Id$
?RCS:
?RCS: Copyright (c) 2008 H.Merijn Brand
?RCS:
?RCS: You may distribute under the terms of either the GNU General Public
?RCS: License or the Artistic License, as specified in the README file.
?RCS:
?MAKE:d_ctime64 d_localtime64 d_gmtime64 d_mktime64 d_diffime64 d_asctime64: Inlibc
?MAKE: -pick add $@ %<
?S:d_ctime64:
?S: This variable conditionally defines the HAS_CTIME64 symbol, which

```

?S: indicates to the C program that the ctime64 () routine is available.
?S:.
?S:d_localtime64:
?S: This variable conditionally defines the HAS_LOCALTIME64 symbol, which
?S: indicates to the C program that the localtime64 () routine is available.
?S:.
?S:d_gmtime64:
?S: This variable conditionally defines the HAS_GMTIME64 symbol, which
?S: indicates to the C program that the gmtime64 () routine is available.
?S:.
?S:d_mktime64:
?S: This variable conditionally defines the HAS_MKTIME64 symbol, which
?S: indicates to the
C program that the mktime64 () routine is available.
?S:.
?S:d_difftime64:
?S: This variable conditionally defines the HAS_DIFFTIME64 symbol, which
?S: indicates to the C program that the difftime64 () routine is available.
?S:.
?S:d_asctime64:
?S: This variable conditionally defines the HAS_ASCTIME64 symbol, which
?S: indicates to the C program that the asctime64 () routine is available.
?S:.
?C:HAS_CTIME64:
?C: This symbol, if defined, indicates that the ctime64 () routine is
?C: available to do the 64bit variant of ctime ()
?C:.
?C:HAS_LOCALTIME64:
?C: This symbol, if defined, indicates that the localtime64 () routine is
?C: available to do the 64bit variant of localtime ()
?C:.
?C:HAS_GMTIME64:
?C: This symbol, if defined, indicates that the gmtime64 () routine is
?C: available to do the 64bit variant of gmtime ()
?C:.
?C:HAS_MKTIME64:
?C: This symbol, if defined, indicates that the mktime64 () routine is
?C: available to do the 64bit variant of mktime ()
?C:.
?C:HAS_DIFFTIME64:
?C: This
symbol, if defined, indicates that the difftime64 () routine is
?C: available to do the 64bit variant of difftime ()
?C:.
?C:HAS_ASCTIME64:
?C: This symbol, if defined, indicates that the asctime64 () routine is
?C: available to do the 64bit variant of asctime ()
?C:.

```
?H:#$d_ctime64 HAS_CTIME64 /**/  
?H:#$d_localtime64 HAS_LOCALTIME64 /**/  
?H:#$d_gmtime64 HAS_GMTIME64 /**/  
?H:#$d_mktime64 HAS_MKTIME64 /**/  
?H:#$d_difftime64 HAS_DIFFTIME64 /**/  
?H:#$d_asctime64 HAS_ASCTIME64 /**/  
?H:  
?LINT:set d_ctime64 d_localtime64 d_gmtime64 d_mktime64 d_difftime64 d_asctime64  
: see if 64bit time functions exists
```

```
set ctime64 d_ctime64  
eval $inlibc
```

```
set localtime64 d_localtime64  
eval $inlibc
```

```
set gmtime64 d_gmtime64  
eval $inlibc
```

```
set mktime64 d_mktime64  
eval $inlibc
```

```
set difftime64 d_difftime64  
eval $inlibc
```

```
set asctime64 d_asctime64  
eval $inlibc
```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-  
debian-perl-5.26.1/U/perl/d_timefuncs64.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: i_malloc.U,v 3.5 2008/03/29 14:06:51 merijn Exp $
```

```
?RCS:
```

```
?RCS: Copyright (c) 2008, H.Merijn Brand
```

```
?RCS:
```

```
?RCS: You may redistribute only under the terms of the Artistic License,
```

```
?RCS: as specified in the README file that comes with the distribution.
```

```
?RCS: You may reuse parts of this distribution only within the terms of
```

```
?RCS: that same Artistic License; a copy of which may be found at the root
```

```
?RCS: of the source tree for dist 3.5.
```

```
?RCS:
```

```
?MAKE:i_mallocmalloc: Inhdr
```

```
?MAKE: -pick add $@ %<
```

```
?S:i_mallocmalloc:
```

```
?S: This variable conditionally defines the I_MALLOCMALLOC symbol,
```

```
?S: and indicates whether a C program should include <malloc/malloc.h>.
```

?S:
?C:I_MALLOCMALLOC:
?C: This symbol, if defined, indicates to the C program that it should
?C: include <malloc/malloc.h>.

?C:
?H:#\$i_mallocmalloc I_MALLOCMALLOC /**/
?H:
?LINT:set i_mallocmalloc
: see if malloc/malloc.h has to be included
set malloc/malloc.h i_mallocmalloc
eval
\$inhdr

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/i_mallocmalloc.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: Oldsym.U 1 2006-08-24 12:32:52Z rmanfredi \$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: Oldsym.U,v \$

?RCS: Revision 3.0.1.1 1997/02/28 15:06:58 ram

?RCS: patch61: added support for src.U

?RCS:

?RCS: Revision 3.0 1993/08/18 12:05:13 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?X:

?X: This unit follows the creation of the config.sh file. It adds some

?X: special symbols: defines from patchlevel.h file if any and PERL_CONFIG_SH,

?X: which is set to true. Then, we try to keep all the new symbols that

?X: may come from a hint

file or a previous config.sh file.

?X:

?MAKE:Oldsym: Config_sh cat test hint src sed sort uniq perl_patchlevel

?MAKE: -pick add \$@ %<

?T:PERL_CONFIG_SH PERL_PATCHLEVEL sym tmp

?F:!UU

: add special variables

\$test -f \$src/patchlevel.h && \

```
awk '/^#define[ ]+PERL_/ {printf "%s=%s\n", $2, $3}' $src/patchlevel.h >>config.sh
echo "PERL_PATCHLEVEL='$perl_patchlevel'" >>config.sh
echo "PERL_CONFIG_SH=true" >>config.sh
```

: propagate old symbols

if \$test -f UU/config.sh; then

?X: Make sure each symbol is unique in oldconfig.sh

```
<UU/config.sh $sort | $uniq >UU/oldconfig.sh
```

?X:

?X: All the symbols that appear twice come only from config.sh (hence the

?X: two config.sh in the command line). These symbols will be removed by

?X: the uniq -u command. The oldsyms file thus contains all the symbols

?X: that did not appear in the produced config.sh (Larry Wall).

?X:

?X: Do not touch the -u flag of uniq. This means you too, Jarkko.

?X:

```
$sed -n 's/^\([a-zA-Z_0-9]*\)=.*/\1/p' \
config.sh config.sh UU/oldconfig.sh
```

```
|\
```

```
$sort | $uniq -u >UU/oldsyms
```

```
set X ` $cat UU/oldsyms `
```

```
shift
```

```
case $# in
```

```
0) ;;
```

```
*)
```

```
$cat <<EOM
```

Hmm...You had some extra variables I don't know about...I'll try to keep 'em...

EOM

```
echo ": Variables propagated from previous config.sh file." >>config.sh
```

```
for sym in ` $cat UU/oldsyms `; do
```

```
echo " Propagating $hint variable ""$sym..."
```

```
eval 'tmp=""${sym}""'
```

```
echo "$tmp" |\
```

```
sed -e "s/^\\""/g" -e "s/^\$sym=/'" -e "s/\/'" >>config.sh
```

```
done
```

```
::
```

```
esac
```

fi

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/modified/Oldsym.U
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: vendorhtml3dir.U,v 1.1 1999/07/08 18:32:57 doughera Exp doughera \$

?RCS:

?RCS: Copyright (c) 1999, Andy Dougherty

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 3.0.
?RCS:
?RCS: \$Log: vendorhtml3dir.U,v \$
?RCS: Revision 1.1 1999/07/08 18:32:57 doughera
?RCS: Initial revision
?RCS:
?MAKE:vendorhtml3dir vendorhtml3direxp installvendorhtml3dir: html3dir Getfile \
Oldconfig Setprefixvar Prefixit test vendorprefix prefix sed
?MAKE: -pick add \$@ %<
?Y:TOP
?S:vendorhtml3dir:
?S: This variable contains the name of the directory for html
?S: library pages. It may have a ~ on the front.
?S: The standard distribution will put nothing
in this directory.
?S: Vendors who distribute perl may wish to place their own
?S: html pages for modules and extensions in this directory with
?S: MakeMaker Makefile.PL INSTALLDIRS=vendor
?S: or equivalent. See INSTALL for details.
?S:.
?S:vendorhtml3direxp:
?S: This variable is the ~name expanded version of vendorhtml3dir, so that you
?S: may use it directly in Makefiles or shell scripts.
?S:.
?D:installvendorhtml3dir="
?S:installvendorhtml3dir:
?S: This variable is really the same as vendorhtml3direxp but may differ on
?S: those systems using AFS. For extra portability, only this variable
?S: should be used in makefiles.
?S:.
?LINT:change prefixvar
?LINT:set installvendorhtml3dir
: Set the vendorhtml3dir variables
case "\$vendorprefix" in
") vendorhtml3dir="
vendorhtml3direxp="
;;
*) : determine where vendor-supplied module html pages go.
: There is no standard location, so try to copy the previously-selected
: directory structure for the core html pages.
: XXX Better default
suggestions would be welcome.
case "\$vendorhtml3dir" in
") dflt=`echo "\$html3dir" | \$sed "s#^\$prefix#\$vendorprefix#"` ;;

```

*) dflt=$vendorhtml3dir ;;
esac
case "$dflt" in
'|' ) dflt=none ;;
esac
fn=dn+~
rp='Pathname for the vendor-supplied html pages?'
./getfile
vendorhtml3dir="$ans"
vendorhtml3direxp="$ansexp"
;;
esac
: Use ' ' for none so value is preserved next time through Configure
$test X"$vendorhtml3dir" = "X" && vendorhtml3dir=' '
prefixvar=vendorhtml3dir
./installprefix

```

Found in path(s):

```

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/installdirs/vendorhtml3dir.U

```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1999, Jarkko Hietaniemi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 3.0.

?RCS:

?MAKE:inotype: Myread Typedef

?MAKE: -pick add \$@ %<

?S:inotype:

?S: This variable defines Ino_t to be something like ino_t, long,

?S: int, or whatever type is used to declare inode numbers.

?S:.

?C:Ino_t:

?C: This symbol holds the type used to declare inode numbers.

?C: It can be int, long, ino_t, etc...

?C: It may be necessary to include <sys/types.h> to get any

?C: typedef'ed information.

?C:.

?H:#define Ino_t \$inotype /* <inode> type */

?H:.

?LINT: set inotype

: see what type is used for inodes

```
rp="What is the type used
for inode numbers on this system?"
set ino_t inotype long stdio.h sys/types.h
eval $typedef_ask
```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/typedefs/inotype.U
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 2003 Jarkko Hietaniemi

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?MAKE:d_faststdio: Setvar \

d_stdstdio d_stdio_ptr_lval d_stdio_cnt_lval d_stdio_ptr_lval_sets_cnt

?MAKE: -pick add \$@ %<

?S:d_faststdio:

?S: This variable conditionally defines the HAS_FAST_STDIO symbol,

?S: which indicates to the C program that the "fast stdio" is available

?S: to manipulate the stdio buffers directly.

?S:.

?C:HAS_FAST_STDIO:

?C: This symbol, if defined, indicates that the "fast stdio"

?C: is available to manipulate the stdio buffers directly.

?C:.

?H:#\$d_faststdio HAS_FAST_STDIO /**/

?H:.

?LINT:set d_faststdio

: see if fast_stdio exists

val="\$undef"

case "\$d_stdstdio:\$d_stdio_ptr_lval" in

"\$define:\$define")

case "\$d_stdio_cnt_lval\$d_stdio_ptr_lval_sets_cnt" in

\$define)

echo "You

seem to have 'fast stdio' to directly manipulate the stdio buffers." >& 4

val="\$define"

::

esac

::

esac

set d_faststdio

eval \$setvar

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_faststdio.U
```

No license file was found, but licenses were detected in source scan.

Perl5 Metaconfig Units

Copyright (c) 1996-1998, Andy Dougherty

Copyright (c) 1999-2011, H.Merijn Brand

All rights reserved.

These units are the ones I used to build Configure and config_h.SH in the Perl5 distribution.

The Configure script and config_h.SH file in the Perl distribution are generated by a program called metaconfig. To run metaconfig, you will need the full dist 3.0 distribution, maintained by Raphael Manfredi. As of this writing, the current version is dist3.0, patchlevel 70. Dist version dist-3.0@70.tar.gz is available on CPAN (the Comprehensive Perl Archive Network) as <http://www.perl.com/perl/CPAN/authors/id/RAM/dist-3.0@70.tar.gz>.

Instructions:

1. Unpack the full perl5 sources. Execute the following command

```
chmod +w Configure config_h.SH Porting/Glossary Porting/config*
```

2. Unpack the archive containing this file in the perl5 source directory. This will create a directory 'U' under the perl5 sources. That directory will contain the metaconfig units for perl5. This will also create two files in the perl5 source tree: MANIFEST.new and .package.
3. Apply any patches to perl in the perl_patches/ directory. (This may well be empty.)
4. Obtain and install dist-3.0pl70.
4. Apply any patches to dist under the dist_patches subdirectory.
5. From your main perl5 source directory, run packinit to regenerate the .package file. **IMPORTANT:** Change the name and address of the maintainer to your own name and address. I don't want bug reports intended for you coming to me.
6. From your main perl5 source directory, run

metalint (or mlint)

and repair every failure it reports.

7. From your main perl5 source directory, run

metaconfig -m (or mconfig -m)

8. Edit U/mkglossary and/or U/mkgloss.pl to point to your dist-3.0pl70 location. (See comments at the top.)

9. Run the U/mksample script to update the contents of the Porting/ subdirectory, or run all parts by hand. (see README)

10. Let me know about any changes, corrections, or enhancements.

Things to watch out for:

1. The Configure in 5.005 is a hand-patched version of that supplied with perl5.004_74 or so. Most of the patches had to do with supporting MPE/iX and EBCDIC systems. I have re-integrated most of the changes back into metaconfig, but I don't really understand why MPE/iX needed some of the patches, so I may have missed something important. I did try to flag questionable changes in the individual units.

The Configure as generated in the 5.9.x branch leading towards 5.10, is also used exactly as is without changes in the 5.8.x and 5.6.x branches, so do not remove support for features that are available in those branches, but are removed from devel (e.g. perl5005threads).

2. Future support of better random number generators should probably start with the randfunc.U unit included here. It's currently broken, but well commented and probably a good place to start.

Descriptions:

The units and other related files have been broken up into the following directories:

acl/

This is an old patch to begin to detect and use ACL (access control list) file protection schemes.

compline/

These are similar to the standard units, but I have modified them to have a more uniform compile command line, usually using the new Compile.U unit. I have submitted these for inclusion into the regular dist distribution. (The cflags.U unit is actually perl-specific since it mentions -DDEBUGGING and -DPOSIX_SOURCE, but that's the only place it is perl-specific.)

dist_patches/

These are patches to dist that must be applied before it is built and installed. I have submitted these for inclusion in the regular dist distribution.

modified/

These are modified versions of the standard units. Also included in this directory are new units that are clearly derived from existing units. I have submitted these for inclusion in the regular dist distribution.

perl/

These are specific to perl. Some are heavily derived from original dist units, and are marked as such. Others are original.

perl_patches/

These are patches to the perl source. This directory should ordinarily be empty, but there may have been drift between the standard version of perl and the one associated with these units.

protos/

These are units modified to use the new Hasproto.U or Protochk.U units to check for prototypes. I have submitted these for inclusion into the regular dist distribution.

target/

This is the very, very beginning of cross-compiler support. It doesn't work yet, and many standard units will need modification.

typedefs/

These are standard units modified to use the modified Typedef.U unit to check for typedefs. (The modified Typedef.U includes a function to avoid unnecessary prompts if the typedef being searched for exists.) I have submitted these for inclusion into the regular dist distribution.

threads/

These are specific to threading perl.

Copyright Information:

Unless otherwise indicated, the files contained in this distribution are:

Copyright (c) 1996-1998, Andy Dougherty

The following licensing terms apply to all files contained in this distribution:

You may distribute the files contained in this distribution under the terms of either

- a) the "Artistic License" which comes with Perl, or
- b) the "Artistic License" which comes with dist, or
- c) the GNU General Public License as published by the Free Software Foundation; either version 1, or (at your option) any later version (see the file "Copying" that comes with the Perl distribution).

Which one to use is your choice.

The units in the "modified" directory have been derived from units associated with the metaconfig program of Raphael

Manfredi's "dist"

distribution. These units list Raphael Manfredi as the Copyright holder. dist is distributed under a modified version of the Perl Artistic License. Clause 7 of this modified license as contained in dist-3.0-pl60 provides:

7. You may reuse parts of this Package in your own programs, provided that you explicitly state where you got them from, in the source code (and, left to your courtesy, in the documentation), duplicating all the associated copyright notices and disclaimers. Besides your changes, if any, must be clearly marked as such. Parts reused that way will no longer fall under this license if, and only if, the name of your program(s) have no immediate connection with the name of the Package itself or its associated programs. You may then apply whatever restrictions you wish on the reused parts or choose to place them in the Public Domain--this will apply only within the context of your package.

In accordance with this clause, the versions of these units contained here are made available under the same terms as the

rest of the units.

If you have any questions about the use of these units or about the differences between these units and the standard versions, please feel free to ask.

Andy Dougherty doughera@lafayette.edu
Dept. of Physics
Lafayette College
Easton, PA 18042-1782

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/README.dist

No license file was found, but licenses were detected in source scan.

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?MAKE:d_log2: Inlibc

?MAKE: -pick add \$@ %<

?S:d_log2:

?S: This variable conditionally defines the HAS_LOG2 symbol, which

?S: indicates to the C program that the log2() routine is available

?S: to compute log base two.

?S:.

?C:HAS_LOG2:

?C: This symbol, if defined, indicates that the log2 routine is

?C: available to do the log2 function.

?C:.

?H:#\$d_log2 HAS_LOG2 /**/

?H:.

?LINT:set d_log2

: see if log2 exists

set log2 d_log2

eval \$inlibc

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_log2.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_getservent_r.U,v 0RCS:

?RCS: Copyright (c) 2002,2003 Jarkko Hietaniemi

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?RCS: Generated by the reentr.pl from the Perl 5.8 distribution.

?RCS:

?MAKE:d_getservent_r getservent_r_proto: Inlibc Protochk Hasproto i_systypes \
 usethreads i_netdb extern_C

?MAKE: -pick add \$@ %<

?S:d_getservent_r:

?S: This variable conditionally defines the HAS_GETSERVENT_R symbol,
 ?S: which indicates to the C program that the getservent_r()
 ?S: routine is available.

?S:.

?S:getservent_r_proto:

?S: This variable encodes the prototype of getservent_r.
 ?S: It is zero if d_getservent_r is undef, and one of the
 ?S: REENTRANT_PROTO_T_ABC macros of reentr.h if d_getservent_r
 ?S: is defined.

?S:.

?C:HAS_GETSERVENT_R:

?C: This symbol, if defined, indicates that the getservent_r routine
 ?C: is
 available to getservent re-entrantly.

?C:.

?C:GETSERVENT_R_PROTO:

?C: This symbol encodes the prototype of getservent_r.
 ?C: It is zero if d_getservent_r is undef, and one of the
 ?C: REENTRANT_PROTO_T_ABC macros of reentr.h if d_getservent_r
 ?C: is defined.

?C:.

?H:#\$d_getservent_r HAS_GETSERVENT_R /**/
 ?H:#define GETSERVENT_R_PROTO \$getservent_r_proto /**/
 ?H:.

?T:try hdrs d_getservent_r_proto
 : see if getservent_r exists
 set getservent_r d_getservent_r
 eval \$inlibc
 case "\$d_getservent_r" in
 "\$define")
 hdrs="\$i_systypes sys/types.h define stdio.h \$i_netdb netdb.h"
 case "\$d_getservent_r_proto:\$usethreads" in
 ":define") d_getservent_r_proto=define
 set d_getservent_r_proto getservent_r \$hdrs
 eval \$hasproto ;;
 *) ;;
 esac
 case "\$d_getservent_r_proto" in
 define)
 case "\$getservent_r_proto" in
 "|0) try='int getservent_r(struct servent*, char*, size_t, struct servent**);'
 ./protochk "\$extern_C \$try" \$hdrs && getservent_r_proto=I_SBWR ;;

```

esac
case "$getservent_r_proto"
in
"|0) try='int getservent_r(struct servent*, char*, int);'
./prochck "$extern_C $try" $hdrs && getservent_r_proto=I_SBI ;;
esac
case "$getservent_r_proto" in
"|0) try='struct servent* getservent_r(struct servent*, char*, int);'
./prochck "$extern_C $try" $hdrs && getservent_r_proto=S_SBI ;;
esac
case "$getservent_r_proto" in
"|0) try='int getservent_r(struct servent*, struct servent_data*);'
./prochck "$extern_C $try" $hdrs && getservent_r_proto=I_SD ;;
esac
case "$getservent_r_proto" in
"|0) d_getservent_r=undef
    getservent_r_proto=0
    echo "Disabling getservent_r, cannot determine prototype." >&4 ;;
*) case "$getservent_r_proto" in
REENTRANT_PROTO*) ;;
*) getservent_r_proto="REENTRANT_PROTO_${getservent_r_proto}" ;;
esac
echo "Prototype: $try" ;;
esac
;;
*) case "$usethreads" in
define) echo "getservent_r has no prototype, not using it." >&4 ;;
esac
d_getservent_r=undef
getservent_r_proto=0
;;
esac
;;
*) getservent_r_proto=0
;;
esac

```

Found

in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/threads/d_getservent_r.U

No license file was found, but licenses were detected in source scan.

?RCS: Copyright (c) 2000,2014 Jarkko Hietaniemi

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?MAKE:d_fpclassify d_fp_classify: Inlibc cat i_math Compile rm_try Setvar
?MAKE: -pick add \$@ %<
?X:the short story is that C99 says use fpclassify. But the story is confused
?X:by systems "partially C99" (or fully "pre C99") which either user fpclassify
?X:but with different return values, or they use fp_classify (with the expected)
?X:return values, or they use some other spelling of *fp*class* (sometimes even
?X:without the *fp* part), with yet another set(s) of return values ...
?S:d_fpclassify:
?S: This variable conditionally defines the HAS_FPCLASSIFY symbol, which
?S: indicates to the C program that the fpclassify() routine is available.
?S:.
?S:d_fp_classify:
?S: This variable conditionally defines the HAS_FP_CLASSIFY
symbol, which
?S: indicates to the C program that the fp_classify() routine is available.
?S:.
?C:HAS_FPCLASSIFY:
?C: This symbol, if defined, indicates that the fpclassify routine is
?C: available to classify doubles. Available for example in HP-UX.
?C: The returned values are defined in <math.h> and are
?C:
?C: FP_NORMAL Normalized
?C: FP_ZERO Zero
?C: FP_INFINITE Infinity
?C: FP_SUBNORMAL Denormalized
?C: FP_NAN NaN
?C:
?C:.
?C:HAS_FP_CLASSIFY:
?C: This symbol, if defined, indicates that the fp_classify routine is
?C: available to classify doubles. The values are defined in <math.h>
?C:
?C: FP_NORMAL Normalized
?C: FP_ZERO Zero
?C: FP_INFINITE Infinity
?C: FP_SUBNORMAL Denormalized
?C: FP_NAN NaN
?C:
?C:.
?H:#\$d_fpclassify HAS_FPCLASSIFY /**/
?H:#\$d_fp_classify HAS_FP_CLASSIFY /**/
?H:.
?LINT:set d_fpclassify
?LINT:set d_fp_classify
:
check for fpclassify
?X:classified (Comment by jhi)
?X:fpclassify i_math

```

?X:fp_classify i_math
?X:fpclass i_math i_jeefp i_fp
?X:fp_class i_math i_fp_class
?X: No i_fp_class yet. But the systems that have
?X: this (Tru64 and IRIX) both had <fp_class.h>
?X:class i_math
echo "Checking to see if you have fpclassify..." >&4
$cat >try.c <<EOCP
#i_math I_MATH
#ifdef I_MATH
#include <math.h>
#endif
int main() { return fpclassify(1.0) == FP_NORMAL ? 0 : 1; }
EOCP
set try
if eval $compile; then
val="$define"
echo "You have fpclassify."
else
val="$undef"
echo "You do not have fpclassify."
fi
$rm_try
set d_fpclassify
eval $setvar

```

```

: see if fp_classify exists
set fp_classify d_fp_classify
eval $inlibc

```

Found in path(s):

```

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/perl/d_fpclassify.U

```

No license file was found, but licenses were detected in source scan.

```

?RCS: $Id: d_difftime.U 1 2006-08-24 12:32:52Z rmanfredi $
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: Original Author: Andy Dougherty <doughera@lafcol.lafayette.edu>
?RCS:
?RCS: $Log: d_difftime.U,v $

```

?RCS: Revision 3.0.1.1 1994/08/29 16:07:31 ram
?RCS: patch32: created by ADO
?RCS:
?MAKE:d_difftime: Inlibc
?MAKE: -pick add \$@ %<
?S:d_difftime:
?S: This variable conditionally defines the HAS_DIFFTIME symbol, which
?S: indicates to the C program that the difftime() routine is available.
?S:.
?C:HAS_DIFFTIME :
?C: This symbol, if defined, indicates that
the difftime routine is
?C: available.
?C:.
?H:#\$d_difftime HAS_DIFFTIME /**/
?H:.
?LINT:set d_difftime
: see if difftime exists
set difftime d_difftime
eval \$inlibc

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/d_difftime.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$
?RCS:
?RCS: Copyright (c) 2004 H.Merijn Brand
?RCS:
?RCS: You may distribute under the terms of either the GNU General Public
?RCS: License or the Artistic License, as specified in the README file.
?RCS:
?MAKE:d_strlcpy: Inlibc
?MAKE: -pick add \$@ %<
?S:d_strlcpy:
?S: This variable conditionally defines the HAS_STRLCPY symbol, which
?S: indicates to the C program that the strlcpy () routine is available.
?S:.
?C:HAS_STRLCPY:
?C: This symbol, if defined, indicates that the strlcpy () routine is
?C: available to do string copying.
?C:.
?H:#\$d_strlcpy HAS_STRLCPY /**/
?H:.
?LINT:set d_strlcpy
: see if strlcpy exists
set strlcpy d_strlcpy

eval \$inlibc

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_strncpy.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_getnetprotos.U,v \$

?RCS:

?RCS: Copyright (c) 1991-1993, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 3.0.

?RCS:

?MAKE:d_getnetprotos : Hasproto i_netdb

?MAKE: -pick add \$@ %<

?S:d_getnetprotos:

?S: This variable conditionally defines the HAS_GETNET_PROTOS symbol,

?S: which indicates to the C program that <netdb.h> supplies

?S: prototypes for the various getnet*() functions.

?S: See also netdbtype.U for probing for various netdb types.

?S:.

?C:HAS_GETNET_PROTOS:

?C: This symbol, if defined, indicates that <netdb.h> includes

?C: prototypes for getnetent(), getnetbyname(), and

?C: getnetbyaddr(). Otherwise,

it is up to the program to guess

?C: them. See netdbtype.U for probing for various Netdb_xxx_t types.

?C:.

?H:#\$d_getnetprotos HAS_GETNET_PROTOS /**/

?H:.

?LINT:set d_getnetprotos

: see if prototypes for various getnetxxx netdb.h functions are available

echo " "

set d_getnetprotos getnetent \$i_netdb netdb.h

eval \$hasproto

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/protos/d_getnetprotos.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: etc.U 1 2006-08-24 12:32:52Z rmanfredi \$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.

?RCS:
?RCS: \$Log: etc.U,v \$
?RCS: Revision 3.0 1993/08/18 12:08:07 ram
?RCS: Baseline for dist 3.0 netwide release.

?RCS:
?MAKE:etc etcexp: Getfile Loc Oldconfig

?MAKE: -pick add \$@ %<

?S:etc:
?S: This variable holds the name of the directory in which the user wants
?S: to put "administrative" executable images for the package in question.
?S: It is most often a local directory such as /usr/local/etc. Programs
?S: relying on this variable must be prepared to deal with

~name

?S: substitutions.

?S:.

?S:etcexp:

?S: This is the same as the etc variable, but is filename expanded at

?S: configuration time, for convenient use in makefiles.

?S:.

: determine where administrative executables go

case "\$etc" in

")

dflt=`./loc ./local/etc /usr/local/etc /local/etc /usr/etc /etc`

::

*)

dflt="\$etc"

::

esac

fn=d~

rp='Where should the administrative executables go?'

./getfile

etc="\$ans"

etcexp="\$ansexp"

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/etc.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 2000 Jarkko Hietaniemi

```

?RCS:
?RCS: You may distribute under the terms of either the GNU General Public
?RCS: License or the Artistic License, as specified in the README file.
?RCS:
?MAKE:d_lutimes: Inlibc
?MAKE: -pick add $@ %<
?S:d_lutimes:
?S: This variable conditionally defines the HAS_LUTIMES symbol, which
?S: indicates to the C program that the lutimes() routine is available.
?S:.
?C:HAS_LUTIMES:
?C: This symbol, if defined, indicates that the lutimes routine is
?C: available to change symbolic link timestamps with struct timevals.
?C:.
?H:#$d_lutimes HAS_LUTIMES /**/
?H:.
?LINT:set d_lutimes
: see if lutimes exists
set lutimes d_lutimes
eval $inlibc

```

Found in path(s):

```

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/perl/d_lutimes.U

```

No license file was found, but licenses were detected in source scan.

```

?RCS: $Id: ansi2knr.U,v 3.0.1.3 1994/05/06 15:11:49 ram Exp $
?RCS:
?RCS: Copyright (c) 1998 Andy Dougherty
?RCS:
?RCS: You may distribute under the terms of either the GNU General Public
?RCS: License or the Artistic License, as specified in the README file.
?RCS:
?MAKE:ansi2knr: prototype +cc +ccflags package
?MAKE: -pick add $@ %<
?S:ansi2knr:
?S: This variable is set if the user needs to run ansi2knr.
?S: Currently, this is not supported, so we just abort.
?S:.
?Y:TOP
: Check if ansi2knr is required
case "$prototype" in
"$define") ;;
*) ansi2knr='ansi2knr'
echo " "
cat <<EOM >&4

```

\$me: FATAL ERROR:

This version of \$package can only be compiled by a compiler that understands function prototypes. Unfortunately, your C compiler \$cc \$ccflags doesn't seem to understand them. Sorry about that.

If GNU cc is available for your system, perhaps you could try that instead.

Eventually, we hope to support building Perl with pre-ANSI compilers. If you would like to help in that effort, please contact <perlbug@perl.org>.

Aborting Configure now.

```
EOM
exit 2
;;
esac
```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/ansi2knr.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: d_setgrps.U 1 2006-08-24 12:32:52Z rmanfredi $
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: $Log: d_setgrps.U,v $
?RCS: Revision 3.0 1993/08/18 12:06:08 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:d_setgrps: Inlibc
?MAKE: -pick add $@ %<
?S:d_setgrps:
?S: This variable conditionally defines the HAS_SETGROUPS symbol, which
?S: indicates to the C program that the setgroups() routine is available
?S: to set the list of process groups.
?S:.
?C:HAS_SETGROUPS:
?C: This symbol, if defined, indicates that the setgroups() routine is
?C: available
to set the list of process groups. If unavailable, multiple
?C: groups are probably not supported.
```

```
?C:.
?H:#$d_setgrps HAS_SETGROUPS /**/
?H:.
?LINT:set d_setgrps
: see if setgroups exists
set setgroups d_setgrps
eval $inlibc
```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/d_setgrps.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id$
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: $Log: d_memchr.U,v $
?RCS: Revision 3.0 1993/08/18 12:06:32 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:d_memchr: Inlibc
?MAKE: -pick add $@ %<
?S:d_memchr:
?S: This variable conditionally defines the HAS_MEMCHR symbol, which
?S: indicates to the C program that the memchr() routine is available
?S: to scan a block of memory for a character.
?S:.
?C:HAS_MEMCHR:
?C: This symbol, if defined, indicates that the memchr routine is available
?C: to scan a block of memory for a character.
  If undefined, roll your own.
?C:.
?H:#$d_memchr HAS_MEMCHR /**/
?H:.
?LINT:set d_memchr
: see if memchr exists
set memchr d_memchr
eval $inlibc
```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
```

debian-perl-5.26.1/dist/U/d_memchr.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: archname.U,v 3.0.1.3 1997/02/28 15:24:32 ram Exp \$

?RCS:

?RCS: Copyright (c) 1991-1993, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 3.0.

?RCS:

?RCS: \$Log: archname.U,v \$

?RCS: Revision 3.0.1.3 1997/02/28 15:24:32 ram

?RCS: patch61: changed the way the archname is mangled from uname

?RCS:

?RCS: Revision 3.0.1.2 1995/05/12 12:05:24 ram

?RCS: patch54: protect against spaces in "uname -m" output (ADO)

?RCS:

?RCS: Revision 3.0.1.1 1995/02/15 14:14:21 ram

?RCS: patch51: created

?RCS:

?MAKE:archname myarchname useversionedarchname: sed Loc Myread Oldconfig \

osname test rm usethreads usemultiplicity use64bitint

use64bitall \

archname64 uselongdouble longdblsize doublesize targetarch Setvar \

api_versionstring usequadmath

?MAKE: -pick add \$@ %<

?S:archname:

?S: This variable is a short name to characterize the current

?S: architecture. It is used mainly to construct the default archlib.

?S:.

?S:myarchname:

?S: This variable holds the architecture name computed by Configure in

?S: a previous run. It is not intended to be perused by any user and

?S: should never be set in a hint file.

?S:.

?S:useversionedarchname:

?S: This variable indicates whether to include the \$api_versionstring

?S: as a component of the \$archname.

?S:.

?C:ARCHNAME:

?C: This symbol holds a string representing the architecture name.

?C: It may be used to construct an architecture-dependant pathname

?C: where library files may be held under a private library, for

?C: instance.

?C:.

```

?H:#define ARCHNAME "$archname" /**/
?H:.
?T:xxx tarch
?F:!archname.cbu
?INIT:archname="
: determine the architecture name
echo " "
?X:
  We always recompute archname in case osname changes. However, we need
?X: to be careful since, as ADO rightfully pointed out, some systems pick
?X: silly architecture names (0001307135000-aix on AIX or 9000/715-ux under
?X: HP-UX). Therefore, we allow hint files to superseed our guess and ask
?X: the user for confirmation.
if xxx=`./loc arch blurfl $pth`; $test -f "$xxx"; then
  tarch=`arch`-"$osname"
elif xxx=`./loc uname blurfl $pth`; $test -f "$xxx" ; then
  if uname -m > tmparch 2>&1 ; then
    tarch=`$sed -e 's/ *$//' -e 's/ /_/g' \
      -e 's/$/"-$osname/" tmparch`
  else
    tarch="$osname"
  fi
  $rm -f tmparch
else
  tarch="$osname"
fi
case "$myarchname" in
"$tarch") ;;
*)
  echo "(Your architecture name used to be $myarchname.)"
  archname="
  ;;
esac
case "$targetarch" in
") ;;
?X: Very GCCian.
*) archname=`echo $targetarch|sed 's,^[^-]*-,^` ;;
esac
myarchname="$tarch"
case "$sarchname" in
") dflt="$tarch";;
*) dflt="$sarchname";;
esac
rp='What is your architecture name'
./myread
archname="$ans"

:

```

```

optionally add API version to the architecture for versioned archlibs
case "$useversionedarchname" in
$define|true|[yY]*) dflt='y';
*)          dflt='n';;
esac
rp='Add the Perl API version to your archname?'
./myread
case "$ans" in
y|Y) useversionedarchname="$define" ;;
*)   useversionedarchname="$undef" ;;
esac
case "$useversionedarchname" in
$define)
case "$archname" in
*-$api_versionstring)
echo "...and architecture name already has -$api_versionstring" >&4
;;
*)
archname="$archname-$api_versionstring"
echo "...setting architecture name to $archname." >&4
;;
esac
;;
esac

@if usethreads
case "$usethreads" in
$define)
echo "Threads selected." >&4
case "$archname" in
*-$thread*) echo "...and architecture name already has -$thread." >&4
;;
*)   archname="$archname-$thread"
echo "...setting architecture name to $archname." >&4
;;
esac
;;
esac
@end
@if usemultiplicity
case "$usemultiplicity" in
$define)
echo "Multiplicity selected."
>&4
case "$archname" in
*-$multi*) echo "...and architecture name already has -$multi." >&4
;;
*)   archname="$archname-$multi"

```

```

echo "...setting architecture name to $archname." >&4
;;
esac
;;
esac
@end
@if use64bitint
case "$use64bitint$use64bitall" in
*$define*)
case "$archname64" in
")
echo "This architecture is naturally 64-bit, not changing architecture name." >&4
;;
*)
case "$use64bitint" in
"$define") echo "64 bit integers selected." >&4 ;;
esac
case "$use64bitall" in
"$define") echo "Maximal 64 bitness selected." >&4 ;;
esac
case "$archname" in
*-$archname64*) echo "...and architecture name already has $archname64." >&4
;;
*) archname="$archname-$archname64"
echo "...setting architecture name to $archname." >&4
;;
esac
;;
esac
esac
esac
@end
@if uselongdouble
case "$uselongdouble" in
$define)
echo "Long doubles selected." >&4
case "$longdblsize" in
$doublesize)
echo "...but long doubles are equal to doubles, not
changing architecture name." >&4
;;
*)
case "$archname" in
*-ld*) echo "...and architecture name already has -ld." >&4
;;
*) archname="$archname-ld"
echo "...setting architecture name to $archname." >&4
;;
esac

```

```

;;
esac
;;
esac
@end
@if usequadmath
case "$usequadmath" in
$define)
echo "quadmath selected." >&4
case "$archname" in
*-quadmath*) echo "...and architecture name already has -quadmath." >&4
;;
*) archname="$archname-quadmath"
echo "...setting architecture name to $archname." >&4
;;
esac
;;
esac
@end
if $test -f archname.cbu; then
echo "Your platform has some specific hints for architecture name, using them..."
. ./archname.cbu
fi

```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/threads/archname.U
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1999 Jarkko Hietaniemi

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?MAKE:d_rand_r: Inlibc

?MAKE: -pick add \$@ %<

?S:d_rand_r:

?S: This variable conditionally defines the HAS_RANDOM_R symbol,

?S: which indicates to the C program that the rand_r()

?S: routine is available.

?S:.

?C:HAS_RANDOM_R:

?C: This symbol, if defined, indicates that the rand_r routine

?C: is available to rand re-entrantly.

?C:.

?H:#\$d_rand_r HAS_RANDOM_R /**/

?H:
?LINT:set d_rand_r
: see if rand_r exists
set rand_r d_rand_r
eval \$inlibc

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/threads/d_rand_r.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1999 Jarkko Hietaniemi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 3.0.

?RCS:

?MAKE:siteman3dir siteman3direxp installsiteman3dir: Getfile \

Setprefixvar prefix siteprefix man3dir sed

?MAKE: -pick add \$@ %<

?Y:TOP

?D:siteman3dir="

?S:siteman3dir:

?S: This variable contains the name of the directory in which site-specific

?S: library man source pages are to be put. It is the responsibility of the

?S: Makefile.SH to get the value of this into the proper command.

?S: You must be prepared to do the ~name expansion yourself.

?S: The standard distribution will put nothing in this directory.

?S: After

perl has been installed, users may install their own local

?S: man3 pages in this directory with

?S: MakeMaker Makefile.PL

?S: or equivalent. See INSTALL for details.

?S:.

?D:siteman3direxp="

?S:siteman3direxp:

?S: This variable is the same as the siteman3dir variable, but is filename

?S: expanded at configuration time, for convenient use in makefiles.

?S:.

?D:installsiteman3dir="

?S:installsiteman3dir:

?S: This variable is really the same as siteman3direxp, unless you are using

?S: AFS in which case it points to the read/write location whereas

?S: man3direxp only points to the read-only access location. For extra

?S: portability, you should only use this variable within your makefiles.

?S:.

?LINT:change prefixvar

?LINT:set installsiteman3dir

?LINT:set siteman3dir

?LINT:set siteman3direxp

: determine where add-on library man pages go

case "\$siteman3dir" in

) dflt=`echo \$man3dir | \$sed "s#^\$prefix#\$siteprefix#"` ;;

*) dflt=\$siteman3dir ;;

esac

case "\$dflt" in

"|' ') dflt=none ;;

esac

fn=dn+~

rp='Pathname

where the site-specific library manual pages should be installed?'

./getfile

prefixvar=siteman3dir

./setprefixvar

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/installdirs/siteman3dir.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: Warn_v7EXT.U 1 2006-08-24 12:32:52Z rmanfredi \$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic Licence,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic Licence; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: Warn_v7EXT.U,v \$

?RCS: Revision 3.0.1.1 1994/10/29 16:01:42 ram

?RCS: patch36: call ./v7 explicitly instead of relying on PATH

?RCS:

?RCS: Revision 3.0 1993/08/18 12:05:17 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?X:

?X: This unit issues warnings to V7 sites that they are living dangerously.

?X: This unit needs to get mentioned in End.U to get included.

?X:

?MAKE:Warn_v7EXT: package Guess

```
?MAKE: -pick add $@ %<
: Warnings
if ./v7;
then
cat <<EOM
```

NOTE: the V7 compiler may ignore some #undefs that \$package uses. If so, you may get messages about redefining EXT. Some V7 compilers also have difficulties with #defines near buffer boundaries, so beware. You may have to play with the spacing in some .h files, believe it or not.

```
EOM
fi
```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/Warn_v7EXT.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id$
```

```
?RCS:
```

```
?RCS: Copyright (c) 2000 Jarkko Hietaniemi
```

```
?RCS:
```

```
?RCS: You may distribute under the terms of either the GNU General Public
```

```
?RCS: License or the Artistic License, as specified in the README file.
```

```
?RCS:
```

```
?MAKE:d_isinfl: Inlibc
```

```
?MAKE: -pick add $@ %<
```

```
?S:d_isinfl:
```

```
?S: This variable conditionally defines the HAS_ISINFL symbol, which
```

```
?S: indicates to the C program that the isinfl() routine is available.
```

```
?S:.
```

```
?C:HAS_ISINFL:
```

```
?C: This symbol, if defined, indicates that the isinfl routine is
```

```
?C: available to check whether a long double is an infinity.
```

```
?C:.
```

```
?H:#$d_isinfl HAS_ISINFL /**/
```

```
?H:.
```

```
?LINT:set d_isinfl
```

```
: see if isinfl exists
```

```
set isinfl d_isinfl
```

```
eval $inlibc
```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_isinfl.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: d_rmdir.U 1 2006-08-24 12:32:52Z rmanfredi $
```

```

?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: $Log: d_rmdir.U,v $
?RCS: Revision 3.0 1993/08/18 12:06:56 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:d_rmdir: Inlibc
?MAKE: -pick add $@ %<
?S:d_rmdir:
?S: This variable conditionally defines HAS_RMDIR if rmdir() is
?S: available to remove directories.
?S:.
?C:HAS_RMDIR (RMDIR):
?C: This symbol, if defined, indicates that the rmdir routine is
?C: available to remove directories. Otherwise you should fork off a
?C: new process to exec
/bin/rmdir.
?C:.
?H:#$d_rmdir HAS_RMDIR /**/
?H:.
?LINT:set d_rmdir
: see if rmdir exists
set rmdir d_rmdir
eval $inlibc

```

Found in path(s):

```

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/d_rmdir.U

```

No license file was found, but licenses were detected in source scan.

```

?RCS: $Id: d_readdir.U 1 2006-08-24 12:32:52Z rmanfredi $
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: $Log: d_readdir.U,v $

```

?RCS: Revision 3.0.1.1 1994/05/06 14:46:37 ram
?RCS: patch23: added support for seekdir, telldir and rewinddir (ADO)
?RCS:
?RCS: Revision 3.0 1993/08/18 12:06:52 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?X: Force checking for <dirent.h> inclusion
?X:INC: i_dirent
?MAKE:d_readdir d_seekdir d_telldir d_rewinddir: Inlibc
?MAKE: -pick add \$@ %<
?S:d_readdir:
?S: This variable conditionally defines HAS_READDIR if readdir()
is
?S: available to read directory entries.
?S:.
?C:HAS_READDIR (READDIR):
?C: This symbol, if defined, indicates that the readdir routine is
?C: available to read directory entries. You may have to include
?C: <dirent.h>. See I_DIRENT.
?C:.
?H:#\$d_readdir HAS_READDIR /**/
?H:.
?S:d_seekdir:
?S: This variable conditionally defines HAS_SEEKDIR if seekdir() is
?S: available.
?S:.
?C:HAS_SEEKDIR:
?C: This symbol, if defined, indicates that the seekdir routine is
?C: available. You may have to include <dirent.h>. See I_DIRENT.
?C:.
?H:#\$d_seekdir HAS_SEEKDIR /**/
?H:.
?S:d_telldir:
?S: This variable conditionally defines HAS_TELLDIR if telldir() is
?S: available.
?S:.
?C:HAS_TELLDIR:
?C: This symbol, if defined, indicates that the telldir routine is
?C: available. You may have to include <dirent.h>. See I_DIRENT.
?C:.
?H:#\$d_telldir HAS_TELLDIR /**/
?H:.
?S:d_rewinddir:
?S: This variable conditionally defines HAS_REWINDDIR if rewinddir() is
?S: available.
?S:.
?C:HAS_REWINDDIR:
?C: This

symbol, if defined, indicates that the rewinddir routine is
?C: available. You may have to include <dirent.h>. See I_DIRENT.

?C:.

?H:#\$d_rewinddir HAS_REWINDDIR /**/

?H:.

?LINT:set d_readdir d_seekdir d_telldir d_rewinddir

: see if readdir and friends exist

set readdir d_readdir

eval \$inlibc

@if d_seekdir || HAS_SEEKDIR

set seekdir d_seekdir

eval \$inlibc

@end

@if d_telldir || HAS_TELLDIR

set telldir d_telldir

eval \$inlibc

@end

@if d_rewinddir || HAS_REWINDDIR

set rewinddir d_rewinddir

eval \$inlibc

@end

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/d_readdir.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_getpwent.U,v \$

?RCS:

?RCS: Copyright (c) 1998 Andy Dougherty

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?RCS: \$Log: d_getpwent.U,v \$

?RCS:

?MAKE:d_getpwent: Inlibc

?MAKE: -pick add \$@ %<

?S:d_getpwent:

?S: This variable conditionally defines the HAS_GETPWENT symbol, which

?S: indicates to the C program that the getpwent() routine is available

?S: for sequential access of the passwd database.

?S:.

?C:HAS_GETPWENT:

?C: This symbol, if defined, indicates that the getpwent routine is

?C: available for sequential access of the passwd database.

?C: If this is not available, the older getpw() function may be available.

?C:.

?H:#\$d_getpwent HAS_GETPWENT /**/

?H:.

?LINT:set d_getpwent

: see if getpwent exists

set getpwent d_getpwent

eval \$inlibc

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/modified/d_getpwent.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: i_float.U 1 2006-08-24 12:32:52Z rmanfredi \$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic Licence,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic Licence; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: Original Author: Andy Dougherty <doughera@lafcol.lafayette.edu>

?RCS:

?RCS: \$Log: i_float.U,v \$

?RCS: Revision 3.0.1.1 1994/08/29 16:21:57 ram

?RCS: patch32: created by ADO

?RCS:

?MAKE:i_float: Inhdr

?MAKE: -pick add \$@ %<

?S:i_float:

?S: This variable conditionally defines the I_FLOAT symbol, and indicates

?S: whether a C program may include <float.h> to get symbols like DBL_MAX

?S: or DBL_MIN, i.e. machine dependent floating point values.

?S:.

?C:I_FLOAT:

?C: This

symbol, if defined, indicates to the C program that it should

?C: include <float.h> to get definition of symbols like DBL_MAX or

?C: DBL_MIN, i.e. machine dependent floating point values.

?C:.

?H:#\$i_float I_FLOAT /**/

?H:.

?LINT:set i_float

: see if this is a float.h system

set float.h i_float

eval \$inhdr

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/i_float.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1999, Jarkko Hietaniemi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 3.0.

?RCS:

?MAKE:d_ustat: Inlibc

?MAKE: -pick add \$@ %<

?S:d_ustat:

?S: This variable conditionally defines HAS_USTAT if ustat() is

?S: available to query file system statistics by dev_t.

?S:.

?C:HAS_USTAT:

?C: This symbol, if defined, indicates that the ustat system call is

?C: available to query file system statistics by dev_t.

?C:.

?H:#\$d_ustat HAS_USTAT /**/

?H:.

?LINT:set d_ustat

: see if ustat exists

set ustat d_ustat

eval \$inlibc

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_ustat.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 2000 Jarkko Hietaniemi

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?MAKE:d_socks5_init: Inlibc

?MAKE: -pick add \$@ %<

?S:d_socks5_init:

?S: This variable conditionally defines the HAS_SOCKS5_INIT symbol, which

?S: indicates to the C program that the socks5_init() routine is available.

?S:.

?C:HAS_SOCKS5_INIT:

?C: This symbol, if defined, indicates that the socks5_init routine is

?C: available to initialize SOCKS 5.

?C:.

?H:#\$d_socks5_init HAS_SOCKS5_INIT /**/

?H:.

?LINT:set d_socks5_init

: see if socks5_init exists

set socks5_init d_socks5_init

eval \$inlibc

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_socks5_init.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: dlsrc.U,v\$

?RCS:

?RCS: Copyright (c) 1996-1998, Andy Dougherty

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?RCS: \$Log: dlex.t,U,v \$

?RCS:

?X: hpux support thanks to Jeff Okamoto <okamoto@hpcc101.corp.hp.com>

?X:

?X: To create a shared library, you must compile ALL source files in the

?X: library with +z (or possibly +Z if the library is whopping huge),

?X: then link the library with -b. Example:

?X: cc -c +z module_a.c

?X: cc -c +z module_b.c

?X: ld -b module_a.o module_b.o -o module.sl

?X:

?MAKE:dlex.t: \

Getfile Myread cat usedl so

?MAKE: -pick add \$@ %<

?Y:BOTTOM

?S:dlex.t:

?S: This variable contains the extension that is to be used for the

?S: dynamically loaded modules that perl generates.

?S:.

: Check what extension to use for shared libs

case "\$usedl" in

\$define|y|true)

\$cat <<

EOM

On a few systems, the dynamically loaded modules that perl generates and uses will need a different extension than shared libs. The default will probably be appropriate.

EOM

```
case "$dlext" in
  ") dflt="$so" ;;
  *) dflt="$dlext" ;;
esac
rp='What is the extension of dynamically loaded modules'
. ./myread
dlext="$ans"
;;
*)
dlext="none"
;;
esac
```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/dlext.U
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: i_grp.U,v 3.0 1993/08/18 12:08:20 ram Exp \$

?RCS:

?RCS: Copyright (c) 1991-1993, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 3.0.

?RCS:

?RCS: GRPASSWD detection added by Andy Dougherty July 14, 1998.

?RCS:

?RCS: \$Log: i_grp.U,v \$

?RCS: Revision 3.0 1993/08/18 12:08:20 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?MAKE:i_grp d_grpasswd: \

contains rm cppstdin cppflags cppminus Inhdr Findhdr Setvar

?MAKE: -pick add \$@ %<

?S:i_grp:

?S: This variable conditionally defines the I_GRP symbol, and indicates

?S: whether a C program should include <grp.h>.

?S:.

```

?S:d_grpasswd:
?S: This variable conditionally
    defines GRPASSWORD, which indicates
?S: that struct group in <grp.h> contains gr_passwd.
?S:.
?C:I_GRP:
?C: This symbol, if defined, indicates to the C program that it should
?C: include <grp.h>.
?C:.
?C:GRPASSWORD:
?C: This symbol, if defined, indicates to the C program that struct group
?C: in <grp.h> contains gr_passwd.
?C:.
?H:#$i_grp I_GRP /**/
?H:#$d_grpasswd GRPASSWORD /**/
?H:.
?LINT:set i_grp d_grpasswd
?T: xxx
: see if this is an grp system
set grp.h i_grp
eval $inhdr

case "$i_grp" in
$define)
xxx=`./findhdr grp.h`
Scppstdin Scppflags Scppminus < $xxx >$$h

if $contains 'gr_passwd' $$h >/dev/null 2>&1; then
    val="$define"
else
    val="$undef"
fi
set d_grpasswd
eval $setvar

$rm -f $$h
;;
*)
val="$undef";
set d_grpasswd; eval $setvar
;;
esac

```

Found in path(s):

```

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/modified/i_grp.U

```

No license file was found, but licenses were detected in source scan.

```

?RCS: $Id$
?RCS:
?RCS: Copyright (c) 2003 Jarkko Hietaniemi
?RCS:
?RCS: You may distribute under the terms of either the GNU General Public
?RCS: License or the Artistic License, as specified in the README file.
?RCS:
?MAKE:usefaststdio: Myread Oldconfig Setvar rsrc
?MAKE: -pick add $@ %<
?Y:TOP
?S:usefaststdio:
?S: This variable conditionally defines the USE_FAST_STDIO symbol,
?S: and indicates that Perl should be built to use 'fast stdio'.
?S: Defaults to define in Perls 5.8 and earlier, to undef later.
?S:.
?C:USE_FAST_STDIO:
?C: This symbol, if defined, indicates that Perl should
?C: be built to use 'fast stdio'.
?C: Defaults to define in Perls 5.8 and earlier, to undef later.
?C:.
?H:?%<:#ifndef USE_FAST_STDIO
?H:?%<:#$usefaststdio USE_FAST_STDIO /**/
?H:?%<:#endif
?H:.
?T:xversion
?LINT:set usefaststdio
: Check if faststdio is requested and available
case "$usefaststdio" in
$define|true|[yY]*)
xversion=`awk
'/define[ ]+PERL_VERSION/ {print $3}' $rsrc/patchlevel.h`
case "$xversion" in
[68]) dflt='y' ;;
*) dflt='n' ;;
esac
;;
*) dflt='n';;
esac
cat <<EOM

```

Perl can be built to use 'fast stdio', which means using the stdio library but also directly manipulating the stdio buffers to enable faster I/O. Using stdio is better for backward compatibility (especially for Perl extensions), but on the other hand since Perl 5.8 the 'perlio' interface has been preferred instead of stdio.

If this doesn't make any sense to you, just accept the default '\$dflt'.
EOM

rp='Use the "fast stdio" if available?'

```
./myread
case "$ans" in
y|Y) val="$define" ;;
*)   val="$undef" ;;
esac
set usefaststdio
eval $setvar
```

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/usefaststdio.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: cpp_stuff.U,v \$

?RCS: Revision 3.0.1.2 1997/02/28 15:30:48 ram

?RCS: patch61: added cute quoting trick for wild stringify support

?RCS:

?RCS: Revision 3.0.1.1 1994/10/29 16:08:24 ram

?RCS: patch36: now uses cppstdin instead of plain cpp for consistency (ADO)

?RCS: patch36: remove temporary files when done

?RCS:

?RCS: Revision 3.0 1993/08/18 12:05:36 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?MAKE:cpp_stuff cpp_quote: cat contains cppstdin cppflags cppminus rm Warn \
package

?MAKE: -pick

add \$@ %<

?S:cpp_stuff:

?S: This variable contains an identification of the catenation mechanism

?S: used by the C preprocessor.

?S:.

?S:cpp_quote:

?S: This variable is set to either "" or " depending on whether the

?S: pre-processor pre-dates ANSI or not. It is used in the production of

?S: the SQuoTe() and EQuoTe() macros, and was introduced to overcome a bug

?S: in gcc 3.x whereby the pre-processor complained loudly about the

?S: unterminated strings.

?S:.

?C:CAT2:

?C: This macro catenates 2 tokens together.

?C:.

?C:CAT3:

?C: This macro catenates 3 tokens together.

?C:.

?C:CAT4:

?C: This macro catenates 4 tokens together.

?C:.

?C:CAT5:

?C: This macro catenates 5 tokens together.

?C:.

?C:STRINGIFY:

?C: This macro surrounds its token with double quotes.

?C:.

?C:SCAT2:

?C: This macro catenates 2 tokens together and stringifies the result.

?C:.

?C:SCAT3:

?C: This macro catenates 3 tokens together and stringifies the result.

?C:.

?C:SCAT4:

?C: This macro catenates 4 tokens together and stringifies the result.

?C:.

?C:SCAT5:

?C: This macro catenates 5 tokens together and stringifies the result.

?C:.

?H:??<:#if \$cpp_stuff == 1

?H:CAT2:#define CAT2(a,b)a/**/b

?H:CAT3:#define CAT3(a,b,c)a/**/b/**/c

?H:CAT4:#define CAT4(a,b,c,d)a/**/b/**/c/**/d

?H:CAT5:#define CAT5(a,b,c,d,e)a/**/b/**/c/**/d/**/e

?H:STRINGIFY:#define STRINGIFY(a)"a"

?H:??<:#define SQuote(a){cpp_quote}a

?H:??<:#define EQuote(a)a\${cpp_quote}

?H:SCAT2:#define SCAT2(a,b)EQuote(SQuote(a)b)

?H:SCAT3:#define SCAT3(a,b,c)EQuote(SQuote(a)b/**/c)

?H:SCAT4:#define SCAT4(a,b,c,d)EQuote(SQuote(a)b/**/c/**/d)

?H:SCAT5:#define SCAT5(a,b,c,d,e)EQuote(SQuote(a)b/**/c/**/d/**/e)

?H:??<:#endif

?H:??<:#if \$cpp_stuff == 42

?X: The additional level of indirection enables these macros to be

?X: used as arguments to other macros. See K&R 2nd ed., page 231.

?H:??<:#define CaTiFy(a,b) a ## b

?H:??<:#define CAT2(a,b) CaTiFy(a,b)

```

?H:?CAT3:#define CAT3(a,b,c) CAT2(CaTiFy(a,b),c)
?H:?CAT4:#define CAT4(a,b,c,d)
CAT2(CaTiFy(a,b), CaTiFy(c,d))
?H:?CAT5:#define CAT5(a,b,c,d,e) CAT2(CAT2(CaTiFy(a,b), CaTiFy(c,d)), e)
?H:?%<:#define StGiFy(a)# a
?H:?STRINGIFY:#define STRINGIFY(a)StGiFy(a)
?H:?SCAT2:#define SCAT2(a,b)StGiFy(a) StGiFy(b)
?H:?SCAT3:#define SCAT3(a,b,c)StGiFy(a) StGiFy(b) StGiFy(c)
?H:?SCAT4:#define SCAT4(a,b,c,d)StGiFy(a) StGiFy(b) StGiFy(c) StGiFy(d)
?H:?SCAT5:#define SCAT5(a,b,c,d,e)StGiFy(a) StGiFy(b) StGiFy(c) StGiFy(d) StGiFy(e)
?H:?%<:#endif
?H:?%<:#if $cpp_stuff != 1 && $cpp_stuff != 42
?H:?%<:#include "Bleth: How does this C preprocessor catenate tokens?"
?H:?%<:#endif
?H:.
?W:%<:CAT2 CAT3 CAT4 CAT5 STRINGIFY SCAT2 SCAT3 SCAT4 SCAT5
?F:!cpp_stuff.c
?LINT:known StGiFy EQuoTe SQuoTe CaTiFy
: how do we catenate cpp tokens here?
echo " "
echo "Checking to see how your cpp does stuff like catenate tokens..." >&4
cpp_quote="
$cat >cpp_stuff.c <<'EOCP'
#define RCAT(a,b)a/**/b
#define ACAT(a,b)a ## b
RCAT(Rei,ser)
ACAT(Cir,cus)
EOCP
$cppstdin $cppflags $cppminus <cpp_stuff.c >cpp_stuff.out
2>&1
if $contains 'Circus' cpp_stuff.out >/dev/null 2>&1; then
echo "Oh! Smells like ANSI's been here."
echo "We can catify or stringify, separately or together!"
cpp_stuff=42
elif $contains 'Reiser' cpp_stuff.out >/dev/null 2>&1; then
echo "Ah, yes! The good old days!"
cpp_stuff=1
$cat >cpp_stuff.c <<'EOCP'
#define SQuoTe(a)"a
#define EQuoTe(a)a"
#define CAT2(a,b)EQuoTe(SQuoTe(a)b)
CAT2(Vic,tory)
EOCP
$cppstdin $cppflags $cppminus <cpp_stuff.c >cpp_stuff.out 2>&1
if $contains ""Victory"" cpp_stuff.out >/dev/null 2>&1; then
echo "I'll resort to a cute trick to also be able to stringify."
cpp_quote=""
else

```

```
$cat <<EOM
```

However, in the good old days we don't know how to stringify and catify at the same time...

```
@if SCAT2 || SCAT3 || SCAT4 || SCAT5
```

You might have to edit the values of the SCAT[2-5] macros in config.h...

```
@else
```

Hopefully, \$package does not need this feature.

```
@end
```

```
EOM
```

```
fi
```

```
else
```

```
./warn <<EOM
```

I can't seem to be able to catenate tokens with your cpp.

```
@if
```

```
CAT2 || CAT3 || CAT4 || CAT5 || SCAT2 || SCAT3 || SCAT4 || SCAT5
```

You're going to have to edit the values of the following macros in config.h:

```
@if CAT2 || CAT3 || CAT4 || CAT5
```

```
CAT[2-5]
```

```
@end
```

```
@if SCAT2 || SCAT3 || SCAT4 || SCAT5
```

```
SCAT[2-5]
```

```
@end
```

in order to let me compile.

```
@end
```

```
EOM
```

```
cpp_stuff="/* Help! How do we handle cpp_stuff? *//"
```

```
fi
```

```
$rm -f cpp_stuff.*
```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/cpp_stuff.U
```

No license file was found, but licenses were detected in source scan.

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?MAKE:d_nan: Inlibc

?MAKE: -pick add \$@ %<

?S:d_nan:

?S: This variable conditionally defines HAS_NAN if nan() is

?S: available to generate NaN.

?S:.

?C:HAS_NAN:

?C: This symbol, if defined, indicates that the nan routine is

?C: available to generate NaN.

?C:.

?H:#\$d_nan HAS_NAN /**/

?H:.

?LINT:set d_nan

: see if nan exists

set nan d_nan

eval \$inlibc

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_nan.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_usendir.U 1 2006-08-24 12:32:52Z rmanfredi \$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic Licence,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic Licence; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: d_usendir.U,v \$

?RCS: Revision 3.0.1.1 1997/02/28 15:47:34 ram

?RCS: patch61: replaced .a with \$_a all over the place

?RCS: patch61: likewise for .o replaced by \$_o

?RCS:

?RCS: Revision 3.0 1993/08/18 12:07:52 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?MAKE:d_usendir i_ndir ndirlib: test Setvar Findhdr d_readdir _a

?MAKE: -pick add \$@ %<

?S:d_usendir:

?S: This variable conditionally defines the EMULATE_NDIR symbol, which

?S: indicates

to the C program that it should compile the ndir.c code

?S: provided with the package.

?S:.

?S:i_ndir (d_libndir):

?S: This variable conditionally defines the I_NDIR symbol, which

?S: indicates to the C program that it should include the system's

?S: version of ndir.h, rather than the one with this package.

?S:.

?S:ndirlib:

?S: The name of the library to include at linking stage to resolve ndir

?S: symbols. It is up to the makefile to use this value.

?S:.

?C:EMULATE_NDIR (USENDIR):

?C: This symbol, if defined, indicates that the program should compile

?C: the ndir.c code provided with the package.

?C:.

?C:I_NDIR (LIBNDIR):

?C: This symbol, if defined, indicates that the program should include the

?C: system's version of ndir.h, rather than the one with this package.

?C:.

?H:#\$d_usendir EMULATE_NDIR /**/

?H:#\$i_ndir I_NDIR /**/

?H:.

?T:val2

?LINT: set d_usendir i_ndir

: see if there are directory access routines out there

echo " "

if \$test `./findhdr ndir.h` && \

(\$test -r /usr/lib/libndir\$_a

|| \$test -r /usr/local/lib/libndir\$_a); then

echo "Ndir library found." >&4

if \$test -r /usr/lib/libndir\$_a; then

ndirlib='-lndir'

else

ndirlib="/usr/local/lib/libndir\$_a"

fi

val2="\$define"

val="\$undef"

else

ndirlib=""

val2="\$undef"

case "\$d_readdir" in

"\$define")

echo "No ndir library found, but you have readdir() so we'll use that." >&4

val="\$undef";

::

*)

echo "No ndir library found." >&4

val="\$define"

::

esac

fi

set d_usendir

eval \$setvar

val="\$val2"

set i_ndir

eval \$setvar

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-  
debian-perl-5.26.1/dist/U/d_usendir.U
```

No license file was found, but licenses were detected in source scan.

```
case $CONFIG in  
")  
if test -f config.sh; then TOP=.;  
elif test -f ../config.sh; then TOP=..;  
elif test -f ../../config.sh; then TOP=../../;  
elif test -f ../../../config.sh; then TOP=../../../;  
elif test -f ../../../../config.sh; then TOP=../../../../;  
else  
echo "Can't find config.sh."; exit 1  
fi  
. $TOP/config.sh  
;;  
esac  
case "$0" in  
*/*) cd `expr X$0 : 'X\(.*/'` ;;  
esac  
echo "Extracting makedepend (with variable substitutions)"  
$spitshell >makedepend <<!GROK!THIS!  
$startsh  
# $Id: makedepend.sh,v 3.0.1.1 1994/01/24 14:00:05 ram Exp ram $  
#  
# Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi  
#  
# You may redistribute only under the terms of the Artistic Licence,  
# as specified in the README file that comes with the distribution.  
# You may reuse parts of this distribution only within the terms of  
# that same Artistic Licence; a copy of which may be found at the root  
# of the source tree for dist 4.0.  
#  
#  
Original Author: Larry Wall <lwall@netlabs.com>  
#  
# $Log: makedepend.sh,v $  
# Revision 3.0.1.1 1994/01/24 14:00:05 ram  
# patch16: changed top ln-style config.sh lookup into test-style one  
#  
# Revision 3.0 1993/08/18 12:04:37 ram  
# Baseline for dist 3.0 netwide release.  
#  
  
export PATH || (echo "OOPS, this isn't sh. Desperation time. I will feed myself to sh."; sh $0; kill \$$)  
  
cat='Scat'  
cppflags='$cppflags'
```

```

cp='$cp'
cpp='$cppstdin'
echo='$echo'
egrep='$egrep'
expr='$expr'
mv='$mv'
rm='$rm'
sed='$sed'
sort='$sort'
test='$test'
tr='$tr'
uniq='$uniq'
!GROK!THIS!

```

```
$spitshell >>makedepend <<!NO!SUBS!
```

```

$cat /dev/null >.deptmp
$rm -f *.c.c c/*.*c
if test -f Makefile; then
    mf=Makefile
else
    mf=makefile
fi
if test -f $mf; then
    defrule=`<$mf sed -n \
-e '/^\.c\.o:.*;/{' \
-e 's/^\$*\c//' \
-e 's/^[^;]*[ ]*/p' \
-e q \
-e }' \
-e '/^\.c\.o: *$/{' \
-e N \
-e 's/^\$*\c//' \
-e 's/^\.*\n[ ]*/p' \
-e q \
-e }`
fi
case
"$defrule" in
") defrule='$(CC) -c $(CFLAGS)' ;;
esac

```

```

make clist || ($echo "Searching for .c files..."; \
$echo *.c | $tr ' ' '\012' | $egrep -v '*' >.clist)
gotnone=true
for file in `cat .clist`; do
# for file in `cat /dev/null`; do
    case "$file" in

```

```

*.c) filebase=`basename $file .c` ;;
*.y) filebase=`basename $file .c` ;;
") continue ;;
esac
gotnone=false
$echo "Finding dependencies for $filebase.o."
$sed -n <$file >$file.c \
-e "/^${filebase}_init(/q" \
-e '/^#/{' \
-e 's|^*.*$||' \
-e 's\\$||' \
-e p \
-e '}'
$cpp -I/usr/local/include -I. $cppflags $file.c | \
$sed \
-e '/^# *[0-9]!/d' \
-e 's/^.*"(.*)" .*$/"$filebase'.o: \1' \
-e 's: \./: |' \
-e 's\\.c\\.c|.c'| \
$uniq | $sort | $uniq >> .deptmp
done

$sed <Makefile >Makefile.new -e '1,/^# AUTOMATICALLY!/d'

make shlist || ($echo "Searching for .SH files..."; \
$echo *.SH | $tr ' ' '\012' | $grep -v '*' >.shlist)
if $gotnone || $test -s .deptmp; then

    for file in `cat .shlist`; do
$echo `$expr X$file : 'X(.*)\.SH` : $file config.sh \; \
/bin/sh $file >> .deptmp
    done
$echo "Updating Makefile..."
$echo "# If this runs make out of memory, delete /usr/include lines." \
>> Makefile.new
$sed 's/^(.*\o:) *(.*\c) *$|1 \2; ""$defrule \2|' .deptmp \
>>Makefile.new
else
    make hlist || ($echo "Searching for .h files..."; \
$echo *.h | $tr ' ' '\012' | $grep -v '*' >.hlist)
$echo "You don't seem to have a proper C preprocessor. Using grep instead."
$grep '^#include ' `cat .clist` `cat .hlist` >.deptmp
$echo "Updating Makefile..."
<.clist $sed -n \
-e '//{' \
-e 's/^(.*)^(.*)\c|2.o: \1\2.c; ""$defrule \1\2.c|p' \
-e d \
-e '}' \

```

```

-e 's/^(.*)\.c\1.o: \1.c|p' >> Makefile.new
<.hlist $sed -n 's|(.*^)(.*)|s= \2= \1\2=|p' >.hsed
<.deptmp $sed -n 's|c:#include "(.*)".*$|o: \1|p' | \
    $sed 's^[^;]*/||' | \
    $sed -f
.hsed >> Makefile.new
<.deptmp $sed -n 's|c:#include <(.*>.*$|o: /usr/include/\1|p' \
    >> Makefile.new
<.deptmp $sed -n 's|h:#include "(.*)".*$|h: \1|p' | \
    $sed -f .hsed >> Makefile.new
<.deptmp $sed -n 's|h:#include <(.*>.*$|h: /usr/include/\1|p' \
    >> Makefile.new
for file in `scat .shlist`; do
Secho `sexpr X$file : 'X(.*).SH`: $file config.sh \; \
    /bin/sh $file >> Makefile.new
done
fi
$rm -f Makefile.old
$cp Makefile Makefile.old
$cp Makefile.new Makefile
$rm Makefile.new
Secho "# WARNING: Put nothing here or make depend will gobble it up!" >> Makefile
$rm -f .deptmp `sed 's/\,c/c.c/' .clist` .shlist .clist .hlist .hsed

```

```

!NO!SUBS!
$eunicefix makedepend
chmod +x makedepend
case `pwd` in
*SH)
    $rm -f ./makedepend
    ln makedepend ./makedepend
    ;;
esac

```

Found in path(s):

```

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/lib/makedepend.SH

```

No license file was found, but licenses were detected in source scan.

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?MAKE:d_llrint: Inlibc

?MAKE: -pick add \$@ %<

?S:d_llrint:

?S: This variable conditionally defines the HAS_LLRLINT symbol, which

?S: indicates to the C program that the llrint() routine is available

?S: to return the long long value closest to a double (according

?S: to the current rounding mode).

?S:.

?C:HAS_LLRRINT:

?C: This symbol, if defined, indicates that the llrint routine is

?C: available to return the long long value closest to a double

?C: (according to the current rounding mode).

?C:.

?H:#\$d_llrint HAS_LLRRINT /**/

?H:.

?LINT:set d_llrint

: see if llrint exists

set llrint d_llrint

eval \$inlibc

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_llrint.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: i_sysmount.U,v \$

?RCS:

?RCS: Copyright (c) 1999 Jarkko Hietaniemi

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?MAKE:i_sysmount: Inhdr Hasfield

?MAKE: -pick add \$@ %<

?S:i_sysmount:

?S: This variable conditionally defines the I_SYSMOUNT symbol,

?S: and indicates whether a C program should include <sys/mount.h>.

?S:.

?C:I_SYS_MOUNT:

?C: This symbol, if defined, indicates that <sys/mount.h> exists and

?C: should be included.

?C:.

?H:#\$i_sysmount I_SYS_MOUNT /**/

?H:.

?LINT:set i_sysmount

: see if this is a sys/mount.h system

set sys/mount.h i_sysmount

eval \$inhdr

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/i_sysmount.U

No license file was found, but licenses were detected in source scan.

```

?RCS: $Id: d_gethostent_r.U,v 0RCS:
?RCS: Copyright (c) 2002,2003 Jarkko Hietaniemi
?RCS:
?RCS: You may distribute under the terms of either the GNU General Public
?RCS: License or the Artistic License, as specified in the README file.
?RCS:
?RCS: Generated by the reentr.pl from the Perl 5.8 distribution.
?RCS:
?MAKE:d_gethostent_r gethostent_r_proto: Inlibc Protochk Hasproto i_systypes \
  usethreads i_netdb extern_C
?MAKE: -pick add $@ %<
?S:d_gethostent_r:
?S: This variable conditionally defines the HAS_GETHOSTENT_R symbol,
?S: which indicates to the C program that the gethostent_r()
?S: routine is available.
?S:.
?S:gethostent_r_proto:
?S: This variable encodes the prototype of gethostent_r.
?S: It is zero if d_gethostent_r is undef, and one of the
?S: REENTRANT_PROTO_T_ABC macros of reentr.h if d_gethostent_r
?S: is defined.
?S:.
?C:HAS_GETHOSTENT_R:
?C: This symbol, if defined, indicates that the gethostent_r routine
?C: is
  available to gethostent re-entrantly.
?C:.
?C:GETHOSTENT_R_PROTO:
?C: This symbol encodes the prototype of gethostent_r.
?C: It is zero if d_gethostent_r is undef, and one of the
?C: REENTRANT_PROTO_T_ABC macros of reentr.h if d_gethostent_r
?C: is defined.
?C:.
?H:#$d_gethostent_r HAS_GETHOSTENT_R  /**/
?H:#define GETHOSTENT_R_PROTO $gethostent_r_proto  /**/
?H:.
?T:try hdrs d_gethostent_r_proto
: see if gethostent_r exists
set gethostent_r d_gethostent_r
eval $inlibc
case "$d_gethostent_r" in
"$define")
  hdrs="$i_systypes sys/types.h define stdio.h $i_netdb netdb.h"
  case "$d_gethostent_r_proto:$usethreads" in
  ":define") d_gethostent_r_proto=define
    set d_gethostent_r_proto gethostent_r $hdrs
    eval $hasproto ;;
  *) ;;

```

```

esac
case "$d_gethostent_r_proto" in
define)
case "$gethostent_r_proto" in
"|0) try='int gethostent_r(struct hostent*, char*, size_t, struct hostent**, int*);'
./protochk "$extern_C $try" $hdrs && gethostent_r_proto=I_SBWRE ;;
esac
case "$gethostent_r_proto"
in
"|0) try='int gethostent_r(struct hostent*, char*, int, int*);'
./protochk "$extern_C $try" $hdrs && gethostent_r_proto=I_SBIE ;;
esac
case "$gethostent_r_proto" in
"|0) try='struct hostent* gethostent_r(struct hostent*, char*, int, int*);'
./protochk "$extern_C $try" $hdrs && gethostent_r_proto=S_SBIE ;;
esac
case "$gethostent_r_proto" in
"|0) try='struct hostent* gethostent_r(struct hostent*, char*, int);'
./protochk "$extern_C $try" $hdrs && gethostent_r_proto=S_SBI ;;
esac
case "$gethostent_r_proto" in
"|0) try='int gethostent_r(struct hostent*, char*, int);'
./protochk "$extern_C $try" $hdrs && gethostent_r_proto=I_SBI ;;
esac
case "$gethostent_r_proto" in
"|0) try='struct hostent* gethostent_r(struct hostent*, struct hostent_data*);'
./protochk "$extern_C $try" $hdrs && gethostent_r_proto=I_SD ;;
esac
case "$gethostent_r_proto" in
"|0) d_gethostent_r=undef
    gethostent_r_proto=0
    echo "Disabling gethostent_r, cannot determine prototype."
    >&4 ;;
*) case "$gethostent_r_proto" in
REENTRANT_PROTO*) ;;
*) gethostent_r_proto="REENTRANT_PROTO_${gethostent_r_proto}" ;;
esac
echo "Prototype: $try" ;;
esac
;;
*) case "$usethreads" in
define) echo "gethostent_r has no prototype, not using it." >&4 ;;
esac
d_gethostent_r=undef
gethostent_r_proto=0
;;
esac
;;

```

```
*) gethostent_r_proto=0
```

```
::
```

```
esac
```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/threads/d_gethostent_r.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: d_getpent.U,v 3.0 1993/08/18 12:06:09 ram Exp $
```

```
?RCS:
```

```
?RCS: Copyright (c) 1991-1993, Raphael Manfredi
```

```
?RCS:
```

```
?RCS: You may redistribute only under the terms of the Artistic License,
```

```
?RCS: as specified in the README file that comes with the distribution.
```

```
?RCS: You may reuse parts of this distribution only within the terms of
```

```
?RCS: that same Artistic License; a copy of which may be found at the root
```

```
?RCS: of the source tree for dist 3.0.
```

```
?RCS:
```

```
?RCS: $Log: d_getpent.U,v $
```

```
?RCS: Revision 3.0 1993/08/18 12:06:09 ram
```

```
?RCS: Baseline for dist 3.0 netwide release.
```

```
?RCS:
```

```
?MAKE:d_getpent: Inlibc
```

```
?MAKE: -pick add $@ %<
```

```
?S:d_getpent:
```

```
?S: This variable conditionally defines HAS_GETPROTOENT if getprotoent() is
```

```
?S: available to look up protocols in some data base or another.
```

```
?S:.
```

```
?C:HAS_GETPROTOENT:
```

```
?C: This symbol, if defined, indicates that the getprotoent() routine is
```

```
?C: available to look up protocols in some data base
```

```
or another.
```

```
?C:.
```

```
?H:#$d_getpent HAS_GETPROTOENT /**/
```

```
?H:.
```

```
?LINT:set d_getpent
```

```
: see if getprotoent exists
```

```
set getprotoent d_getpent
```

```
eval $inlibc
```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/modified/d_getpent.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: You may distribute under the terms of either the GNU General Public
```

```
?RCS: License or the Artistic License, as specified in the README file.
```

?RCS:
?MAKE:d_fdclose: Inlibc
?MAKE: -pick add \$@ %<
?S:d_fdclose:
?S: This variable conditionally defines the HAS_FDCLOSE symbol, which
?S: indicates to the C program that the fdclose() routine is available.
?S:.
?C:HAS_FDCLOSE:
?C: This symbol, if defined, indicates that the fdclose routine is
?C: available to free a FILE structure without closing the underlying
?C: file descriptor. This function appeared in FreeBSD 10.2.
?C:.
?H:#\$d_fdclose HAS_FDCLOSE /**/
?H:.
?LINT:set d_fdclose
: see if fdclose exists
set fdclose d_fdclose
eval \$inlibc

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_fdclose.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: contains.U 1 2006-08-24 12:32:52Z rmanfredi \$
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: \$Log: contains.U,v \$
?RCS: Revision 3.0 1993/08/18 12:05:35 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:contains: Nothing
?MAKE: -pick add \$@ %<
?S:contains:
?S: This variable holds the command to do a grep with a proper return
?S: status. On most sane systems it is simply "grep". On insane systems
?S: it is a grep followed by a cat followed by a test. This variable
?S: is primarily for the use of other Configure units.
?S:.
: Some

```

greps do not return status, grrr.
echo "grimblepritz" >grimble
if grep blurfldyick grimble >/dev/null 2>&1 ; then
contains=contains
elif grep grimblepritz grimble >/dev/null 2>&1 ; then
contains=grep
else
contains=contains
fi
rm -f grimble
: the following should work in any shell
case "$contains" in
contains*)
echo " "
echo "AGH! Grep doesn't return a status. Attempting remedial action."
cat >contains <<'EOSS'
grep "$1" "$2" >.greptmp && cat .greptmp && test -s .greptmp
EOSS
chmod +x contains
esac

```

Found in path(s):

```

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/contains.U

```

No license file was found, but licenses were detected in source scan.

```

?RCS: $Id: i_dirent.U,v 3.0.1.4 1994/10/29 16:20:01 ram Exp $
?RCS:
?RCS: Copyright (c) 1991-1993, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 3.0.
?RCS:
?RCS: $Log: i_dirent.U,v $
?RCS: Revision 3.0.1.4 1994/10/29 16:20:01 ram
?RCS: patch36: failed scanning for 'd_namlen' with missing <dirent.h> (ADO)
?RCS:
?RCS: Revision 3.0.1.3 1994/06/20 07:01:25 ram
?RCS: patch30: added direntrytype for hints, merely for NeXT (ADO)
?RCS: patch30: now checks for both struct dirent and direct (ADO)
?RCS:
?RCS: Revision 3.0.1.2 1994/05/13 15:22:37 ram
?RCS: patch27: new variable direntrytype for proper type setting (ADO)
?RCS:
?RCS:

```

Revision 3.0.1.1 1994/01/24 14:11:15 ram

?RCS: patch16: added new Direntry_t pseudo-type for directory entries

?RCS:

?RCS: Revision 3.0 1993/08/18 12:08:17 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?X:

?X: This unit looks whether there is a dirent system or not

?X:

?MAKE:i_dirent d_dirnamlen direntrytype: test contains Setvar \
 Myread Findhdr cppstdin cppflags cppminus rm_try

?MAKE: -pick add \$@ %<

?S:i_dirent:

?S: This variable conditionally defines I_DIRENT, which indicates

?S: to the C program that it should include <dirent.h>.

?S:.

?S:d_dirnamlen:

?S: This variable conditionally defines DIRNAMLEN, which indicates

?S: to the C program that the length of directory entry names is

?S: provided by a d_namelen field.

?S:.

?S:direntrytype:

?S: This symbol is set to 'struct direct' or 'struct dirent' depending on

?S: whether dirent is available or not. You should use this pseudo type to

?S: portably declare your directory entries.

?S:.

?C:I_DIRENT:

?C: This symbol,

if defined, indicates to the C program that it should

?C: include <dirent.h>. Using this symbol also triggers the definition

?C: of the Direntry_t define which ends up being 'struct dirent' or

?C: 'struct direct' depending on the availability of <dirent.h>.

?C:.

?C:DIRNAMLEN:

?C: This symbol, if defined, indicates to the C program that the length

?C: of directory entry names is provided by a d_namlen field. Otherwise

?C: you need to do strlen() on the d_name field.

?C:.

?C:Direntry_t:

?C: This symbol is set to 'struct direct' or 'struct dirent' depending on

?C: whether dirent is available or not. You should use this pseudo type to

?C: portably declare your directory entries.

?C:.

?H:#\$i_dirent I_DIRENT /**/
 ?H:#\$d_dirnamlen DIRNAMLEN /**/
 ?H:%<:@if I_DIRENT && Direntry_t
 ?H:%<:#define Direntry_t \$direntrytype
 ?H:%<:@end

```

?H:
?T:xinc guess1 guess2
?LINT:set i_dirent d_dirnamlen
: see if this is a dirent system
echo " "
if xinc=`./findhdr dirent.h`; $test "$xinc"; then
  val="$define"
  echo
  "<dirent.h> found." >&4
else
  val="$undef"
  if xinc=`./findhdr sys/dir.h`; $test "$xinc"; then
    echo "<sys/dir.h> found." >&4
    echo " "
  else
    xinc=`./findhdr sys/ndir.h`
  fi
  echo "<dirent.h> NOT found." >&4
fi
set i_dirent
eval $setvar

```

?X: Use struct dirent or struct direct? If we're using dirent.h,
 ?X: it's probably struct dirent, but apparently not always.
 ?X: Assume \$xinc still contains the name of the header file we're using.
 @if direntrytype || Direntry_t
 : Look for type of directory structure.
 echo " "
 \$cppstdin \$cppflags \$cppminus < "\$xinc" > try.c

```

case "$direntrytype" in
'| ')
  case "$i_dirent" in
$define) guess1='struct dirent' ;;
*) guess1='struct direct' ;;
esac
;;
*) guess1="$direntrytype"
;;
esac

```

```

case "$guess1" in
'struct dirent') guess2='struct direct' ;;
*) guess2='struct dirent' ;;
esac

```

```

if $contains "$guess1" try.c >/dev/null 2>&1; then
  direntrytype="$guess1"

```

```

echo "Your directory entries are $direntrytype." >&4
elif $contains "$guess2"
try.c >/dev/null 2>&1; then
direntrytype="$guess2"
echo "Your directory entries seem to be $direntrytype." >&4
else
echo "I don't recognize your system's directory entries." >&4
rp="What type is used for directory entries on this system?"
dflt="$guess1"
./myread
direntrytype="$ans"
fi
$rm_try

@end
@if d_dirnamlen || DIRNAMLEN
: see if the directory entry stores field length
echo " "
$cppstdin $cppflags $cppminus < "$xinc" > try.c
if $contains 'd_namlen' try.c >/dev/null 2>&1; then
echo "Good, your directory entry keeps length information in d_namlen." >&4
val="$define"
else
echo "Your directory entry does not know about the d_namlen field." >&4
val="$undef"
fi
set d_dirnamlen
eval $setvar
$rm_try

@end

```

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/modified/i_dirent.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: man3dir.U,v 3.1 1999/07/08 20:52:19 doughera Exp doughera \$

?RCS:

?RCS: Copyright (c) 1996-1999, Andy Dougherty

?RCS: Copyright (c) 1991-1993, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 3.0.

?RCS:

?RCS: \$Log: man3dir.U,v \$

?RCS: Revision 3.1 1999/07/08 20:52:19 doughera

?RCS: Updated for perl5.005_5x

?RCS:

?RCS: Revision 3.0.1.1 1997/02/28 16:10:34 ram

?RCS: patch61: created

?RCS:

?X: This was originally specific to perl5. Since perl5 has man pages that

?X: go in both man1/ and man3/ directories, we need both man1dir

?X: and man3dir. This unit is basically dist's mansrc.U with

?X: man3 used instead

of man everywhere.

?X: I then added various tests because perl5 has *lots* of man3

?X: pages with long file names. -- ADO

?X:

?MAKE:man3dir man3direxp man3ext installman3dir: cat nroff Loc Oldconfig \
 sed man1dir spackage package Getfile Setprefixvar Prefixit Prefixup \
 d_flexfnam privlib Myread test

?MAKE: -pick add \$@ %<

?Y:TOP

?D:man3dir="

?S:man3dir:

?S: This variable contains the name of the directory in which manual

?S: source pages are to be put. It is the responsibility of the

?S: Makefile.SH to get the value of this into the proper command.

?S: You must be prepared to do the ~name expansion yourself.

?S:.

?D:man3direxp="

?S:man3direxp:

?S: This variable is the same as the man3dir variable, but is filename

?S: expanded at configuration time, for convenient use in makefiles.

?S:.

?D:installman3dir="

?S:installman3dir:

?S: This variable is really the same as man3direxp, unless you are using

?S: AFS in which case it points to the read/write location whereas

?S: man3direxp only

points to the read-only access location. For extra

?S: portability, you should only use this variable within your makefiles.

?S:.

?S:man3ext:

?S: This variable contains the extension that the manual page should

?S: have: one of 'n', 'l', or '3'. The Makefile must supply the 'l'.

?S: See man3dir.

?S:.

?T:prog tdfit

?LINT:change prefixvar

?LINT:set man3direxp

```
: determine where library module manual pages go
set man3dir man3dir none
eval $prefixit
$cat <<EOM
```

\$spackage has manual pages for many of the library modules.
EOM

```
case "$nroff" in
nroff)
$cat <<'EOM'
```

However, you don't have nroff, so they're probably useless to you.
EOM

```
case "$man3dir" in
") man3dir="none";;
esac;;
esac
```

```
case "$d_flexfnam" in
undef)
$cat <<'EOM'
```

However, your system can't handle the long file names like File::Basename.3.
EOM

```
case "$man3dir" in
") man3dir="none";;
esac;;
esac
```

echo "If you don't want the manual sources installed, answer 'none'."

?X: In 5.005_57 and earlier, I had the following notes:

?X:

We do not use /usr/local/man/man3 because some man programs will

?X: only show the /usr/local/man/man3 contents, and not the system ones,

?X: thus man less will show the perl module less.pm, but not the system

?X: less command. We might also conflict with Tcl man pages.

?X: However, something like /opt/perl/man/man3 is fine.

?X:

?X: However, opinion seems to be shifting such that 'man POSIX' ought

?X: to just work. -- Andy Dougherty July 8, 1999

?X:

?X: remove any trailing -3.0 or other version indication from \$package

```
prog=`echo $package | $sed 's/-*[0-9.]*$//'
```

```
case "$man3dir" in
```

```
) dflt=`echo "$man1dir" | $sed -e 's/man1/man3/g' -e 's/man\./man\./g'`
```

```
if $test -d "$privlib/man/man3"; then
```

```
cat <<EOM >&4
```

WARNING: Previous versions of perl installed man3 pages into

\$privlib/man/man3. This version will suggest a new default of \$dflt.

EOM

```
tdflt=$dflt
dflt='n'
rp='Do you wish to preserve the old behavior?(y/n)'
./myread
case "$ans" in
y*) dflt="$privlib/man/man3"
;;
*) dflt=$tdflt ;;
esac
fi
;;
*) dflt="$man3dir" ;;
esac
case "$dflt" in
') dflt=none ;;
esac
echo " "
fn=dn+~
rp="Where do the $package library man pages (source) go?"
./getfile
prefixvar=man3dir
./setprefixvar

case "$man3dir" in
") man3dir=' '
installman3dir="";;
esac

: What suffix to use on installed man pages
case "$man3dir" in
')
man3ext='0'
;;
*)
rp="What suffix should be used for the $package library man pages?"
case "$man3ext" in
") case "$man3dir" in
*3) dflt=3 ;;
*3p) dflt=3p ;;
*3pm) dflt=3pm ;;
*1) dflt=1;;
*n) dflt=n;;
*o) dflt=o;;
*p) dflt=p;;
*C) dflt=C;;
```

```
*L) dflt=L;;
*L3) dflt=L3;;
*) dflt=3;;
esac
;;
*) dflt="$man3ext";;
esac
./myread
man3ext="$ans"
;;
esac
```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/installdirs/man3dir.U
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: bin.U,v \$

?RCS: Revision 3.0.1.4 1995/09/25 09:15:32 ram

?RCS: patch59: unit is now forced to the top of Configure, if possible

?RCS:

?RCS: Revision 3.0.1.3 1995/01/30 14:32:40 ram

?RCS: patch49: can now handle installation prefix changes (from WED)

?RCS:

?RCS: Revision 3.0.1.2 1994/08/29 16:05:28 ram

?RCS: patch32: now uses installation prefix

?RCS:

?RCS: Revision 3.0.1.1 1993/09/13 15:56:51 ram

?RCS: patch10: made prompting more explicit (WAD)

?RCS:

?RCS: Revision 3.0 1993/08/18

12:05:26 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?MAKE:bin binexp installbin: Prefixit Getfile Oldconfig afs cat test

?MAKE: -pick add \$@ %<

?Y:TOP

?S:bin:

?S: This variable holds the name of the directory in which the user wants
?S: to put publicly executable images for the package in question. It
?S: is most often a local directory such as /usr/local/bin. Programs using
?S: this variable must be prepared to deal with ~name substitution.

?S:.

?S:binexp:

?S: This is the same as the bin variable, but is filename expanded at
?S: configuration time, for use in your makefiles.

?S:.

?S:installbin:

?S: This variable is the same as binexp unless AFS is running in which case
?S: the user is explicitly prompted for it. This variable should always
?S: be used in your makefiles for maximum portability.

?S:.

?C:BIN:

?C: This symbol holds the path of the bin directory where the package will
?C: be installed. Program must be prepared to deal with ~name substitution.

?C:.

?C:BIN_EXP:

?C: This
symbol is the filename expanded version of the BIN symbol, for
?C: programs that do not want to deal with that at run-time.

?C:.

?H:#define BIN "\$bin" /**/

?H:#define BIN_EXP "\$binexp" /**/

?H:.

?D:bin='/usr/local/bin'

: determine where public executables go

echo " "

set dflt bin bin

eval \$prefixit

fn=d~

rp='Pathname where the public executables will reside?'

./getfile

if \$test "X\$sansexp" != "X\$binexp"; then

installbin="

fi

bin="\$ans"

binexp="\$sansexp"

if \$afs; then

\$cat <<EOM

Since you are running AFS, I need to distinguish the directory in which
executables reside from the directory in which they are installed (and from
which they are presumably copied to the former directory by occult means).

EOM

case "\$installbin" in

```

") dflt=`echo $binexp | sed 's#^/afs/#/afs/.#`;;
*) dflt="$installbin";;
esac
fn=de~
rp='Where will public executables be installed?'
./getfile
installbin="$ans"
else
installbin="$binexp"
fi

```

Found in path(s):

```

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/bin.U

```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: Original Author: Andy Dougherty <doughera@lafcol.lafayette.edu>

?RCS:

?RCS: \$Log: d_gconvert.U,v \$

?RCS: Revision 3.0.1.3 1997/02/28 15:33:38 ram

?RCS: patch61: integrated new unit from perl5

?RCS:

?RCS: Revision 3.0.1.2 1995/07/25 13:55:59 ram

?RCS: patch56: improved comments about the Gconvert macro (ADO)

?RCS: patch56: force compile-link test since it may exist but be unusable (ADO)

?RCS:

?RCS: Revision 3.0.1.1 1994/10/29 16:12:51 ram

?RCS: patch36: created by ADO

?RCS:

?MAKE:d_Gconvert:

cat cc cflags ldflags libs rm_try _o

?MAKE: -pick add \$@ %<

?S:d_Gconvert:

?S: This variable holds what Gconvert is defined as to convert

?S: floating point numbers into strings. It could be 'gconvert'

?S: or a more complex macro emulating gconvert with gcvt() or sprintf.

?S:.

?C:Gconvert:

?C: This preprocessor macro is defined to convert a floating point
?C: number to a string without a trailing decimal point. This
?C: emulates the behavior of sprintf("%g"), but is sometimes much more
?C: efficient. If gconvert() is not available, but gcvt() drops the
?C: trailing decimal point, then gcvt() is used. If all else fails,
?C: a macro using sprintf("%g") is used. Arguments for the Gconvert
?C: macro are: value, number of digits, whether trailing zeros should
?C: be retained, and the output buffer.
?C: Possible values are:
?C: d_Gconvert='gconvert((x),(n),(t),(b))'
?C: d_Gconvert='gcvt((x),(n),(b))'
?C: d_Gconvert='sprintf((b),"%.*g",(n),(x))'
?C: The last two assume trailing zeros should
not be kept.
?C:.
?H:#define Gconvert(x,n,t,b) \$d_Gconvert
?H:.
?T: xxx_list xxx_convert
?F:!try
?X:
: Check how to convert floats to strings.
echo " "
echo "Checking for an efficient way to convert floats to strings."
?X: We want to be sure to drop trailing decimal points (perl5
?X: needs this).
\$cat >try.c <<'EOP'
#ifdef TRY_gconvert
#define Gconvert(x,n,t,b) gconvert((x),(n),(t),(b))
char *myname = "gconvert";
#endif
#ifdef TRY_gcvt
#define Gconvert(x,n,t,b) gcvt((x),(n),(b))
char *myname = "gcvt";
#endif
#ifdef TRY_sprintf
#define Gconvert(x,n,t,b) sprintf((b),"%.*g",(n),(x))
char *myname = "sprintf";
#endif

#include <stdio.h>

int
checkit(expect, got)
char *expect;
char *got;
{
if (strcmp(expect, got)) {
printf("%s oddity: Expected %s, got %s\n",

```

    myname, expect, got);
    exit(1);
}
}

int
int main()
{
    char buf[64];
    buf[63] = '\0';

    /* This must be 1st test on (which?) platform */
    /* Alan Burlison <AlanBurlsin@unn.unisys.com> */
    Gconvert(0.1, 8, 0, buf);
    checkit("0.1",
    buf);

    Gconvert(1.0, 8, 0, buf);
    checkit("1", buf);

    Gconvert(0.0, 8, 0, buf);
    checkit("0", buf);

    Gconvert(-1.0, 8, 0, buf);
    checkit("-1", buf);

    /* Some Linux gcvt's give 1.e+5 here. */
    Gconvert(100000.0, 8, 0, buf);
    checkit("100000", buf);

    /* Some Linux gcvt's give -1.e+5 here. */
    Gconvert(-100000.0, 8, 0, buf);
    checkit("-100000", buf);

    exit(0);
}
EOP
?X: List of order in which to search for functions.
?X: Usual order of efficiency is gconvert gcvt printf
?X: Respect a previous or hinted value.
case "$d_Gconvert" in
gconvert*) xxx_list='gconvert gcvt printf' ;;
gcvt*) xxx_list='gcvt gconvert printf' ;;
printf*) xxx_list='printf gconvert gcvt' ;;
*) xxx_list='gconvert gcvt printf' ;;
esac

for xxx_convert in $xxx_list; do

```

```

echo "Trying $xxx_convert"
$rm_try
if $cc $cflags -DTRY_$xxx_convert $ldflags -o try \
try.c $libs > /dev/null 2>&1 ; then
echo "$xxx_convert" found. >&4
if ./try; then
echo "I'll use $xxx_convert to convert floats
into a string." >&4
break;
else
echo "...But $xxx_convert didn't work as I expected."
fi
else
echo "$xxx_convert NOT found." >&4
fi
done

case "$xxx_convert" in
gconvert) d_Gconvert='gconvert((x),(n),(t),(b))' ;;
gcvt) d_Gconvert='gcvt((x),(n),(b))' ;;
*) d_Gconvert='sprintf((b),"%.*g",(n),(x))' ;;
esac

```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/d_gconvert.U
```

No license file was found, but licenses were detected in source scan.

```

?RCS: $Id: d_table.U 1 2006-08-24 12:32:52Z rmanfredi $
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: $Log: d_table.U,v $
?RCS: Revision 3.0.1.2 1993/11/10 17:34:14 ram
?RCS: patch14: wrongly mentionned an obsolete symbol
?RCS:
?RCS: Revision 3.0.1.1 1993/10/16 13:49:29 ram
?RCS: patch12: created
?RCS:
?MAKE:d_table: Inlibc
?MAKE:-pick add $@ %<
?S:d_table:

```

?S: This variable conditionally defines HAS_TABLE if table() is

?S: available to examine/update elements from a system table.

?S:.

?C:HAS_TABLE:

?C: This symbol, if defined, indicates that the OSF/1

table() system

?C: call is available to examine/update items from a system table.

?C:.

?H:#\$d_table HAS_TABLE /**/

?H:.

?LINT:set d_table

: see if table exists

set table d_table

eval \$inlibc

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/d_table.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_sigblock.U 1 2006-08-24 12:32:52Z rmanfredi \$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic Licence,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic Licence; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: d_sigblock.U,v \$

?RCS: Revision 3.0 1993/08/18 12:07:21 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?MAKE:d_sigblock: Inlibc

?MAKE: -pick add \$@ %<

?S:d_sigblock:

?S: This variable conditionally defines HAS_SIGBLOCK if sigblock() is

?S: available to block signal reception.

?S:.

?C:HAS_SIGBLOCK:

?C: This symbol, if defined, indicates that the sigblock routine is

?C: available to block signal reception.

?C:.

?H:#\$d_sigblock HAS_SIGBLOCK /**/

?H:.

?LINT:set

d_sigblock
: see if sigblock exists
set sigblock d_sigblock
eval \$inlibc

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/d_sigblock.U

No license file was found, but licenses were detected in source scan.

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?MAKE:d_expm1: Inlibc

?MAKE: -pick add \$@ %<

?S:d_expm1:

?S: This variable conditionally defines the HAS_EXPM1 symbol, which

?S: indicates to the C program that the expm1() routine is available.

?S:.

?C:HAS_EXPM1:

?C: This symbol, if defined, indicates that the expm1 routine is

?C: available to do the exp(x) - 1 when x is near 1 function.

?C:.

?H:#\$d_expm1 HAS_EXPM1 /**/

?H:.

?LINT:set d_expm1

: see if expm1 exists

set expm1 d_expm1

eval \$inlibc

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_expm1.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_gethostbyname_r.U,v 0RCS:

?RCS: Copyright (c) 2002,2003 Jarkko Hietaniemi

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?RCS: Generated by the reentr.pl from the Perl 5.8 distribution.

?RCS:

?MAKE:d_gethostbyname_r gethostbyname_r_proto: Inlibc Protochk Hasproto \
i_systypes usethreads i_netdb extern_C

?MAKE: -pick add \$@ %<

?S:d_gethostbyname_r:

?S: This variable conditionally defines the HAS_GETHOSTBYNAME_R symbol,

?S: which indicates to the C program that the gethostbyname_r()
?S: routine is available.
?S:.
?S:gethostbyname_r_proto:
?S: This variable encodes the prototype of gethostbyname_r.
?S: It is zero if d_gethostbyname_r is undef, and one of the
?S: REENTRANT_PROTO_T_ABC macros of reentr.h if d_gethostbyname_r
?S: is defined.
?S:.
?C:HAS_GETHOSTBYNAME_R:
?C: This symbol, if defined, indicates
that the gethostbyname_r routine
?C: is available to gethostbyname re-entrantly.
?C:.
?C:GETHOSTBYNAME_R_PROTO:
?C: This symbol encodes the prototype of gethostbyname_r.
?C: It is zero if d_gethostbyname_r is undef, and one of the
?C: REENTRANT_PROTO_T_ABC macros of reentr.h if d_gethostbyname_r
?C: is defined.
?C:.
?H:#\$d_gethostbyname_r HAS_GETHOSTBYNAME_R /**/
?H:#define GETHOSTBYNAME_R_PROTO \$gethostbyname_r_proto /**/
?H:.
?T:try hdrs d_gethostbyname_r_proto
: see if gethostbyname_r exists
set gethostbyname_r d_gethostbyname_r
eval \$inlibc
case "\$d_gethostbyname_r" in
"\$define")
hdrs="\$i_systypes sys/types.h define stdio.h \$i_netdb netdb.h"
case "\$d_gethostbyname_r_proto:\$usetthreads" in
":define") d_gethostbyname_r_proto=define
set d_gethostbyname_r_proto gethostbyname_r \$hdrs
eval \$hasproto ;;
*) ;;
esac
case "\$d_gethostbyname_r_proto" in
define)
case "\$gethostbyname_r_proto" in
"|0) try='int gethostbyname_r(const char*, struct hostent*, char*, size_t,
struct hostent**, int*);'
./protochk "\$extern_C \$try" \$hdrs && gethostbyname_r_proto=I_CSBWRE ;;
esac
case "\$gethostbyname_r_proto" in
"|0) try='struct hostent* gethostbyname_r(const char*, struct hostent*, char*, int, int*);'
./protochk "\$extern_C \$try" \$hdrs && gethostbyname_r_proto=S_CSBIE ;;
esac
case "\$gethostbyname_r_proto" in

```

"|0) try='int gethostbyname_r(const char*, struct hostent*, struct hostent_data*);'
./protochk "$extern_C $try" $hdrs && gethostbyname_r_proto=I_CSD ;;
esac
case "$gethostbyname_r_proto" in
"|0) d_gethostbyname_r=undef
    gethostbyname_r_proto=0
    echo "Disabling gethostbyname_r, cannot determine prototype." >&4 ;;
* ) case "$gethostbyname_r_proto" in
REENTRANT_PROTO*) ;;
*) gethostbyname_r_proto="REENTRANT_PROTO_$gethostbyname_r_proto" ;;
esac
echo "Prototype: $try" ;;
esac
;;
*) case "$usetthreads" in
define) echo "gethostbyname_r has no prototype, not using it." >&4 ;;
esac
d_gethostbyname_r=undef
gethostbyname_r_proto=0
;;
esac
;;
*) gethostbyname_r_proto=0
;;
esac

```

Found

in path(s):

```

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/threads/d_gethostbyname_r.U

```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: Tr.U,v 3.0.1.2 1994/10/29 18:00:54 ram Exp \$

?RCS:

?RCS: Copyright (c) 1991-1993, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 3.0.

?RCS:

?RCS: \$Log: Tr.U,v \$

?RCS: Revision 3.0.1.2 1994/10/29 18:00:54 ram

?RCS: patch43: forgot to quote \$@ to protect against "evil" characters

?RCS:

?RCS: Revision 3.0.1.1 1994/10/29 15:58:35 ram

?RCS: patch36: created

?RCS:
?X:
?X: This unit produces a bit of shell code that must be dotted in in order
?X: to do a character translation. It catches translations to uppercase or
?X: to lowercase, and then invokes the real tr to perform the job.
?X:
?X: This unit is necessary
on HP machines (HP strikes again!) with non-ascii
?X: ROMAN8-charset, where normal letters are not arranged in a row, so a-z
?X: covers not the whole alphabet but lots of special chars. This was reported
?X: by Andreas Sahlbach <a.sahlbach@tu-bs.de>.
?X:
?X: Units performing a tr '[A-Z]' '[a-z]' or the other way round should include
?X: us in their dependency and use ./tr instead.
?X:
?MAKE:Tr: startsh tr eunicefix
?MAKE: -pick add \$@ %<
?F:./tr
?T:up low
: see whether [:lower:] and [:upper:] are supported character classes
echo " "
case ""echo AbyZ | \$tr '[:lower:]' '[:upper:]' 2>/dev/null`"-`"echo AbyZ | \$tr '[:upper:]' '[:lower:]' 2>/dev/null`" in
ABYZ-abyz)
echo "Good, your tr supports [:lower:] and [:upper:] to convert case." >&4
up='[:upper:]'
low='[:lower:]'
;;
*) # There is a discontinuity in EBCDIC between 'R' and 'S'
(0xd9 and 0xe2), therefore that is a nice testing point.
if test "X\$up" = X -o "X\$low" = X; then
case ""echo RS | \$tr '[R-S]' '[r-s]' 2>/dev/null`"
in
rs) up='[A-Z]'
low='[a-z]'
;;
esac
fi
if test "X\$up" = X -o "X\$low" = X; then
case ""echo RS | \$tr R-S r-s 2>/dev/null`" in
rs) up='A-Z'
low='a-z'
;;
esac
fi
if test "X\$up" = X -o "X\$low" = X; then
case ""echo RS | od -x 2>/dev/null`"
D9E2|*d9e2*)
echo "Hey, this might be EBCDIC." >&4

```

if test "X$up" = X -o "X$low" = X; then
  case "`echo RS | $tr '[A-IJ-RS-Z]' '[a-ij-rs-z]' 2>/dev/null`" in
    rs) up='[A-IJ-RS-Z]'
        low='[a-ij-rs-z]'
        ;;
    esac
fi
if test "X$up" = X -o "X$low" = X; then
  case "`echo RS | $tr A-IJ-RS-Z a-ij-rs-z 2>/dev/null`" in
    rs) up='A-IJ-RS-Z'
        low='a-ij-rs-z'
        ;;
    esac
fi
;;
esac
fi
esac
case "`echo RS | $tr \"\$up\" \"\$low\" 2>/dev/null`" in
rs)
  echo "Using $up and $low to convert case." >&4
  ;;
*)
  echo "I don't know how to translate letters from upper to lower case." >&4
  echo "Your tr is not acting any way I know of." >&4
  exit 1
  ;;
esac
:
set up the translation script tr, must be called with ./tr of course
cat >tr <<EOESC
$startsh
case "\$1\$2" in
[A-Z][a-z]) exec $tr '$up' '$low';;
[a-z][A-Z]) exec $tr '$low' '$up';;
esac
exec $tr "\$@"
EOESC
chmod +x tr
$unicefix tr

```

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/modified/Tr.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: Signal.U 1 2006-08-24 12:32:52Z rmanfredi \$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: Signal.U,v \$

?RCS: Revision 3.0.1.1 1997/02/28 15:20:01 ram

?RCS: patch61: created

?RCS:

?X:

?X: This unit produces three files:

?X: 1- A signal.c file, which, when compiled and run, produces an output like:

?X:

?X: HUP 1

?X: INT 2

?X: QUIT 3

?X: etc...

?X:

?X: 2- A signal.awk script to parse the output of signal.c, fill
?X: in gaps (up to NSIG) and move duplicates to the end.

?X: 3- A signal_cmd script to compile signal.c and run it
?X: through

sort -n -k 2 | uniq | awk -f signal.awk.

?X: (we try also sort -n +1 since some old hosts don't grok sort -k)

?X: (This is called signal_cmd to avoid OS/2 confusion with
?X: signal.cmd vs. signal.

?X: The signal_cmd script also falls back on checking signals one at a
?X: time in case the signal.c program fails. On at least one version of
?X: Linux 2.1.x, the header file #define'd SIGRTMAX to a symbol that
?X: is not defined by the compiler/linker. :-(. Further, on that same
?X: version of Linux, the user had a defective C-shell that gave an
?X: incorrect list for kill -l, so the fall-back didn't work.

?X:

?X: This unit is then used by sig_name.U.

?X:

?MAKE:Signal: test tr rm awk cat grep startsh eunicefix sed sort uniq \
Findhdr cppstdin +cppflags cppminus Compile _o _exe trnl run i_stdlib \
sysroot

?MAKE: -pick add \$@ %<

?X:all files declared as "public" since they're used from other units

?F:signal.c signal_cmd signal.lst signal signal.awk

?T: xx xxx xxxfiles

?LINT:use rm run
_o _exe

?LINT:extern sig_num_init

```

: Trace out the files included by signal.h, then look for SIGxxx names.
?X: Remove SIGARRAYSIZE used by HPUX.
?X: Remove SIGSTKSIZE used by Linux.
?X: Remove SIGSTKSZ used by POSIX.
?X: Remove SIGTYP void lines used by OS2.
?X: Some cpps, like os390, do not give the file name anywhere
case "$sig_num_init" in
")
if [ "X$fieldn" = X ]; then
: Just make some guesses. We check them later.
xxx="$sysroot/usr/include/signal.h $sysroot/usr/include/sys/signal.h"
else
xxx=`echo '#include <signal.h>' |
$cpstdin $cppminus $cppflags 2>/dev/null |
$grep '^[ ]*#.*include' |
$awk '{print \\$fieldn}' | $sed 's!'!g' \\
$sed 's!\\\\\\\\\\\\\\\\!g' | $sort | $uniq`
fi
?X: Check this list of files to be sure we have parsed the cpp output ok.
?X: This will also avoid potentially non-existent files, such
?X: as ../foo/bar.h
xxxfiles=""
?X: Add /dev/null in case the $xxx list is empty.
for xx in $xxx /dev/null ; do
$test -f "$xx" && xxxfiles="$xxxfiles $xx"
done
?X:
If we have found no files, at least try signal.h
case "$xxxfiles" in
") xxxfiles=`findhdr signal.h` ;;
esac
xxx=`awk '
$1 ~ /^#define$/ && $2 ~ /^SIG[A-Z0-9]*$/ && $2 !~ /SIGARRAYSIZE/ && $2 !~ /SIGSTKSIZE/ && $2 !~ /SIGSTKSZ/ && $3 !~ /void/ {
print substr($2, 4, 20)
}
$1 == "#" && $2 ~ /^define$/ && $3 ~ /^SIG[A-Z0-9]*$/ && $3 !~ /SIGARRAYSIZE/ && $4 !~ /void/ {
print substr($3, 4, 20)
}' $xxxfiles`
: Append some common names just in case the awk scan failed.
xxx="$xxx ABRT ALRM BUS CANCEL CHLD CLD CONT DIL EMT FPE"
xxx="$xxx FREEZE HUP ILL INT IO IOT KILL LOST LWP PHONE"
xxx="$xxx PIPE POLL PROF PWR QUIT RTMAX RTMIN SEGV STKFLT STOP"
xxx="$xxx SYS TERM THAW TRAP TSTP TTIN TTOU URG USR1 USR2"
xxx="$xxx USR3 USR4 VTALRM WAITING WINCH WIND WINDOW XCPU XFSZ"

: generate a few handy files for later
$cat > signal.c <<EOCP

```

```

#include <sys/types.h>
#include <signal.h>
#ifdef _STDLIB
#include <stdlib.h>
#endif
#include <stdio.h>
int main() {

/* Strange style to avoid
deeply-nested #if/#else/#endif */
#ifdef NSIG
# ifdef _NSIG
#  define NSIG (_NSIG)
# endif
#endif

#ifdef NSIG
# ifdef SIGMAX
#  define NSIG (SIGMAX+1)
# endif
#endif

#ifdef NSIG
# ifdef SIG_MAX
#  define NSIG (SIG_MAX+1)
# endif
#endif

#ifdef NSIG
# ifdef _SIG_MAX
#  define NSIG (_SIG_MAX+1)
# endif
#endif

#ifdef NSIG
# ifdef MAXSIG
#  define NSIG (MAXSIG+1)
# endif
#endif

#ifdef NSIG
# ifdef MAX_SIG
#  define NSIG (MAX_SIG+1)
# endif
#endif

#ifdef NSIG

```

```

# ifdef SIGARRAYSIZE
#  define NSIG SIGARRAYSIZE /* Assume ary[SIGARRAYSIZE] */
# endif
#endif

#ifndef NSIG
# ifdef _sys_nsig
#  define NSIG (_sys_nsig) /* Solaris 2.5 */
# endif
#endif

/* Default to some arbitrary number that's big enough to get most
   of the common signals.
*/
#ifndef NSIG
#  define NSIG 50
#endif

printf("NSIG %d\n", NSIG);

#ifndef JUST_NSIG

EOCP

echo $xxx | $tr ' ' $trnl | $sort | $uniq | $awk '
{
printf "#ifdef SIG"; printf $1; printf "\n"
printf "printf(\"";
printf $1; printf " %%d\n\",SIG";
printf $1; printf ");\n"
printf "#endif\n"
}
END {
printf "#endif /* JUST_NSIG *\n";
printf "exit(0);\n}\n";
}
' >>signal.c
$cat >signal.awk <<'EOP'
BEGIN { ndups = 0 }
$1 ~ /^NSIG$/ { nsig = $2 }
($1 !~ /^NSIG$/) && (NF == 2) && ($2 ~ /^[0-9][0-9]*$/) {
  if ($2 > maxsig) { maxsig = $2 }
  if (sig_name[$2]) {
dup_name[ndups] = $1
dup_num[ndups] = $2
ndups++
  }
  else {

```

```

sig_name[$2] = $1
sig_num[$2] = $2
}
}
END {
  if (nsig == 0) {
    nsig = maxsig + 1
  }
  printf("NSIG %d\n", nsig);
  for (n = 1; n < nsig; n++) {
  if (sig_name[n]) {
    printf("%s %d\n", sig_name[n], sig_num[n])
  }
  else {
    printf("NUM%d %d\n", n, n)
  }
  }
  for (n = 0; n < ndups; n++) {
  printf("%s %d\n", dup_name[n], dup_num[n])
  }
}
EOP
$cat >signal_cmd <<EOS
$startsh
if $test -s signal.lst; then
  echo "Using your existing signal.lst file"
  exit 0
fi
xxx="$xxx"
EOS
?X: Avoid variable interpolation problems, especially with
?X:
xxx, which contains newlines.
$cat >>signal_cmd <<'EOS'

set signal
if eval $compile_ok; then
  $run ./signal$_exe | ($sort -n -k 2 2>/dev/null || $sort -n +1) |\
  $uniq | $awk -f signal.awk >signal.lst
else
  echo "(I can't seem be able to compile the whole test program)" >&4
  echo "(I'll try it in little pieces.)" >&4
  set signal -DJUST_NSIG
  if eval $compile_ok; then
    $run ./signal$_exe > signal.nsg
    $cat signal.nsg
  else
    echo "I can't seem to figure out how many signals you have." >&4

```

```

echo "Guessing 50." >&4
echo 'NSIG 50' > signal.nsg
fi
: Now look at all the signal names, one at a time.
for xx in `echo $xxx | $tr ' ' $trnl | $sort | $uniq`; do
  $cat > signal.c <<EOCP
#include <sys/types.h>
#include <signal.h>
#include <stdio.h>
int main() {
printf("$xx %d\n", SIG${xx});
return 0;
}
EOCP
set signal
if eval $compile; then
echo "SIG${xx} found."
$run ./signal$_exe >> signal.ls1
else
echo "SIG${xx} NOT found."
fi
done
if $test -s signal.ls1; then
$cat
signal.nsg signal.ls1 |
$sort -n | $uniq | $awk -f signal.awk >signal.lst
fi

fi
if $test -s signal.lst; then
:
else
echo "(AAK! I can't compile the test programs -- Guessing)" >&4
echo 'kill -l' >signal
set X `csh -f <signal`
$rm -f signal
shift
case $# in
0) set HUP INT QUIT ILL TRAP ABRT EMT FPE KILL BUS SEGV SYS PIPE ALRM TERM;;
esac
echo $@ | $tr ' ' $trnl | \
  $awk '{ printf "%s %d\n", $1, ++s; }
  END { printf "NSIG %d\n", ++s }' >signal.lst
fi
$rm -f signal.c signal$_exe signal$_o signal.nsg signal.ls1
EOS
chmod a+x signal_cmd
$unicefix signal_cmd

```

```
::  
esac
```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/modified/Signal.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: d_sbrk.U 1 2006-08-24 12:32:52Z rmanfredi $
```

```
?RCS:
```

```
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
```

```
?RCS:
```

```
?RCS: You may redistribute only under the terms of the Artistic Licence,
```

```
?RCS: as specified in the README file that comes with the distribution.
```

```
?RCS: You may reuse parts of this distribution only within the terms of
```

```
?RCS: that same Artistic Licence; a copy of which may be found at the root
```

```
?RCS: of the source tree for dist 4.0.
```

```
?RCS:
```

```
?RCS: $Log: d_sbrk.U,v $
```

```
?RCS: Revision 3.0.1.1 1994/01/24 14:06:31 ram
```

```
?RCS: patch16: created
```

```
?RCS:
```

```
?MAKE:d_sbrk: Inlibc
```

```
?MAKE: -pick add $@ %<
```

```
?S:d_sbrk:
```

```
?S: This variable conditionally defines HAS_SBRK if sbrk() is
```

```
?S: available to add more core to the process.
```

```
?S:.
```

```
?C:HAS_SBRK:
```

```
?C: This symbol, if defined, indicates that the sbrk system call is
```

```
?C: available to add/relase core. Always true on Unix.
```

```
?C:.
```

```
?H:#$d_sbrk HAS_SBRK /**/
```

```
?H:.
```

```
?LINT:set d_sbrk
```

```
: see
```

```
if sbrk exists
```

```
set sbrk d_sbrk
```

```
eval $inlibc
```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/d_sbrk.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: charorder.U,v 3.0.1.1 1994/10/29 16:07:08 ram Exp $
```

```
?RCS:
```

```
?RCS: Copyright (c) 1991-1993, Raphael Manfredi
```

?RCS:
?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 3.0.
?RCS:
?RCS: \$Log: charorder.U,v \$
?RCS: Revision 3.0.1.1 1994/10/29 16:07:08 ram
?RCS: patch36: added ?F: line for metalint file checking
?RCS:
?RCS: Revision 3.0 1993/08/18 12:05:33 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:chorder_int chorder_short chorder_long: Myread cat Compile rm
?MAKE: -pick add \$@ %<
?S:chorder_short (d_cos d_bos):
?S: Holds the value describing the byte ordering of characters in a short.
?S: On a Big-Endian machine, that
would be "c0c1".
?S:.
?S:chorder_int (charoder):
?S: Holds the value describing the byte ordering of characters in an int.
?S: For instance, on a Big-Endian machine, this would be: "c0c1c2c3".
?S:.
?S:chorder_long (d_col d_bol):
?S: Holds the value describing the byte ordering of characters in a long.
?S: On a 64 bits Big-Endian machine, that would yield: "c0c1c2c3c4c5c6c7".
?S:.
?C:CHAR_ORDER_SHORT:
?C: Holds the byte ordering of characters in a short. It's a string
?C: value like "c0c1" on a Big-Endian machine.
?C:.
?C:CHAR_ORDER_INT:
?C: Holds the byte ordering of characters in an int. It's a string
?C: value like "c0c1c2c3" on a Big-Endian machine.
?C:.
?C:CHAR_ORDER_LONG:
?C: Holds the byte ordering of characters in a long. It's a string
?C: value like "c0c1c2c3c4c5c6c7" on a 64 bits Big-Endian machine.
?C:.
?H:#define CHAR_ORDER_SHORT "\$chorder_short" /* byte order in a short */
?H:#define CHAR_ORDER_INT "\$chorder_int" /* byte order in an int */
?H:#define CHAR_ORDER_LONG "\$chorder_long"
/* byte order in a long */
?H:.
?F:!byteorder
: check for character ordering

```

echo " "
echo "Checking out byte order..." >&4
$cat >byteorder.c <<'EOCP'
#include <stdio.h>

int main(argc, argv)
int argc;
char *argv[]; {
int i;
int max;
union {
short u_s;
int u_i;
long u_l;
char u_c[sizeof(long)];
} u;
switch (argv[1][0]) {
case 'l':
u.u_l = 0L;
/* HMS: ASSERT: sizeof(long) < 10. */
for(i = 0; i < sizeof(long); ++i) {
u.u_l *= 0x100L;
u.u_l += (0xc0 + i);
}
max = sizeof(long);
break;
case 's':
u.u_s = 0;
/* HMS: ASSERT: sizeof(short) < 10. */
for(i = 0; i < sizeof(short); ++i) {
u.u_s *= 0x100L;
u.u_s += (0xc0 + i);
}
max = sizeof(short);
break;
case 'i':
u.u_i = 0;
/* RAM: ASSERT: sizeof(int) < 10. */
for(i = 0; i < sizeof(int); ++i) {
u.u_l *= 0x100L;
u.u_l += (0xc0 + i);
}
max = sizeof(int);
break;
default:
max = 0;
break;
}
}

```

```

for(i = 0; i < max; i++) {
    printf("%x", u.u_c[i] & 0x00FF);
}
printf("\n");
exit(0);
}
EOCP
set
byteorder
if eval $compile_ok ; then
: null statement
@if chorder_short
    chorder_short=`./byteorder s`
@end
@if chorder_int
    chorder_int=`./byteorder i`
@end
@if chorder_long
    chorder_long=`./byteorder l`
@end
else
$cat <<EOM
(I can't seem to get my test program to work. Guessing 32 bits big-endian.)
EOM
    chorder_short="c0c1"
    chorder_int="c0c1c2c3"
    chorder_long="c0c1c2c3"
fi
@if chorder_short
dflt=$chorder_short
rp='What is the order of characters in a short?'
./myread
chorder_short="$ans"
@end
@if chorder_int
dflt=$chorder_int
rp='What is the order of characters in an int?'
./myread
chorder_int="$ans"
@end
@if chorder_long
dflt=$chorder_long
rp='What is the order of characters in a long?'
./myread
chorder_long="$ans"
@end
$rm -f byteorder* core

```

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/compline/charorder.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_msync.U 1 2006-08-24 12:32:52Z rmanfredi \$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic Licence,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic Licence; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: d_msync.U,v \$

?RCS: Revision 3.0.1.1 1993/12/15 08:19:17 ram

?RCS: patch15: created

?RCS:

?MAKE:d_msync: Inlibc

?MAKE: -pick add @\$ %<

?S:d_msync:

?S: This variable conditionally defines HAS_MSYNCR if msync() is

?S: available to synchronize a mapped file.

?S:.

?C:HAS_MSYNCR:

?C: This symbol, if defined, indicates that the msync system call is

?C: available to synchronize a mapped file.

?C:.

?H:#\$d_msync HAS_MSYNCR /**/

?H:.

?LINT:set d_msync

: see if

msync exists

set msync d_msync

eval \$inlibc

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/d_msync.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_setprior.U 1 2006-08-24 12:32:52Z rmanfredi \$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic Licence,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: \$Log: d_setprior.U,v \$
?RCS: Revision 3.0 1993/08/18 12:07:11 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:d_setprior: Inlibc
?MAKE: -pick add \$@ %<
?S:d_setprior:
?S: This variable conditionally defines HAS_SETPRIORITY if setpriority()
?S: is available to set a process's priority.
?S:.
?C:HAS_SETPRIORITY (SETPRIORITY):
?C: This symbol, if defined, indicates that the setpriority routine is
?C: available to set a process's priority.
?C:.
?H:#\$d_setprior
HAS_SETPRIORITY /**/
?H:.
?LINT:set d_setprior
: see if setpriority exists
set setpriority d_setprior
eval \$inlibc

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/d_setprior.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1999, Jarkko Hietaniemi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 3.0.

?RCS:

?MAKE:d_sem_post: Inlibc

?MAKE: -pick add \$@ %<

?S:d_sem_post:

?S: This variable conditionally defines HAS_SEM_POST if sem_post() is

?S: available to post (release, unlock) a POSIX semaphore.

?S:.

?C:HAS_SEM_POST:

?C: This symbol, if defined, indicates that the sem_post system call is

?C: available to post (release, unlock) a POSIX semaphore.

?C:.

?H:#\$d_sem_post HAS_SEM_POST /**/

?H:.

?LINT:set d_sem_post

: see if sem_post exists

set sem_post d_sem_post

eval \$inlibc

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_sem_post.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: perl5.U,v \$

?RCS:

?RCS: Copyright (c) 2000 Andrew Dougherty

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?RCS: \$Log: perl5.U,v \$

?RCS:

?X:

?X: The purpose of this unit is to locate a previously installed

?X: version of perl5 suitable for running inc_version_list.U.

?X: We check for 5.005 and later because inc_version_list is

?X: irrelevant for earlier versions.

?X:

?MAKE:perl5: path_sep binexp test sed exe_ext

?MAKE: -pick add \$@ %<

?Y:TOP

?S:perl5:

?S: This variable contains the full path (if any) to a previously

?S: installed perl5.005 or later suitable for running the script

?S: to determine inc_version_list.

?S:.

?T: tdir

: Find perl5.005 or later.

echo "Looking for a previously installed perl5.005 or later... "

case "\$perl5" in

) for tdir in `echo "\$binexp\$path_sep\$PATH" | \$sed "s/\$path_sep/

/g"; do

: Check if this perl is recent and can load a simple module

if \$test -x \$tdir/perl\$exe_ext && \$tdir/perl -Mless -e 'use 5.005;' >/dev/null 2>&1; then

perl5=\$tdir/perl

break;

```

elif $test -x $tdir/perl5$exe_ext && $tdir/perl5 -Mless -e 'use 5.005;' >/dev/null 2>&1; then
    perl5=$tdir/perl5
    break;
fi
done
;;
*) perl5="$perl5"
;;
esac
case "$perl5" in
") echo "None found. That's ok.";;
*) echo "Using $perl5." ;;
esac

```

Found in path(s):

```

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/installdirs/perl5.U

```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: orgname.U 1 2006-08-24 12:32:52Z rmanfredi \$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic Licence,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic Licence; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: orgname.U,v \$

?RCS: Revision 3.0.1.1 1993/09/13 16:10:25 ram

?RCS: patch10: added support for /local/src to the search (WAD)

?RCS:

?RCS: Revision 3.0 1993/08/18 12:09:27 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?MAKE:orgname: sed cat Myread Loc Oldconfig

?MAKE: -pick add \$@ %<

?S:orgname:

?S: This variable contains the eventual value of the ORGNAME symbol,

?S: which contains either the organization name or the full pathname

?S: of

a file containing the organization name.

?S:.

?C:ORGNAME:

?C: This symbol contains either the organization name or the full pathname

?C: of a file containing the organization name, which the program must

?C: be prepared to open and substitute the contents of.

```

?C:.
?H:#define ORGNAME "$orgname" /**/
?H:.
?T:longshots xxx
: get organization name
longshots='/local/src /usr/src/new /usr/src/local /usr/local/src'
case "$orgname" in
") if xxx=`./loc news/src/defs.h x $longshots`; then
  dflt=`$sed -n 's/^. *MYORG[ ]*"(.*)" .*$/\1/p' $xxx`
  else
  dflt=""
  fi
;;
*) dflt="$orgname";;
esac
$cat << 'EOH'

```

Please type the name of your organization as you want it to appear on the Organization line of outgoing articles. (It's nice if this also specifies your location. Your city name is probably sufficient if well known.)

For example:

```

University of Southern North Dakota, Hoople

```

You may also put the name of a file, as long as it begins with a slash.

For example:

```

/etc/organization

```

```

EOH
orgname=""
while
test "X$orgname" = "X"; do
rp='Organization:'
. ./myread
orgname="$ans"
done

```

Found in path(s):

```

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/orgname.U

```

No license file was found, but licenses were detected in source scan.

```

?RCS: $Id$

```

```

?RCS:

```

```

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

```

```

?RCS:

```

```

?RCS: You may redistribute only under the terms of the Artistic License,

```

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: orderlib.U,v \$

?RCS: Revision 3.0.1.4 1997/02/28 16:18:18 ram

?RCS: patch61: replaced .a with \$_a all over the place

?RCS: patch61: likewise for .o replaced by \$_o

?RCS: patch61: now uses the ar located by Loc.U

?RCS:

?RCS: Revision 3.0.1.3 1995/01/11 15:33:04 ram

?RCS: patch45: allows hint files to specify their own value for 'ranlib'

?RCS:

?RCS: Revision 3.0.1.2 1994/10/29 16:26:48 ram

?RCS: patch36: now performs a real small compile for accurate checks (ADO)

?RCS:

?RCS: Revision 3.0.1.1

1994/08/29 16:31:17 ram

?RCS: patch32: use cc variable instead of hardwired 'cc' in 1st compile

?RCS:

?RCS: Revision 3.0 1993/08/18 12:09:26 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?MAKE:orderlib ranlib: Loc ar cat test rm +cc +ccflags +ldflags +libs _a _o

?MAKE: -pick add \$@ %<

?S:orderlib:

?S: This variable is "true" if the components of libraries must be ordered

?S: (with `lorder \$* | tsort`) before placing them in an archive. Set to

?S: "false" if ranlib or ar can generate random libraries.

?S:.

?S:ranlib:

?S: This variable is set to the pathname of the ranlib program, if it is

?S: needed to generate random libraries. Set to ":" if ar can generate

?S: random libraries or if random libraries are not supported

?S:.

?F:!foobar

: see if ar generates random libraries by itself

echo " "

echo "Checking how to generate random libraries on your machine..." >&4

?X: Some systems (like MIPS) complain when running ar... Others like Ultrix

?X: need an explicit 'ar ts'

to add the table of contents.

?X: Still others like Linux run ar ts successfully, but still need ranlib.

?X: This set of tests seems the minimum necessary to check out Linux.

?X: We need to explicitly put the entries in out-of-order so that Sun's ld

?X: will fail. (Otherwise it complains, but gives an exit status of 0.)

echo 'int bar1() { return bar2(); }' > bar1.c

```

echo 'int bar2() { return 2; }' > bar2.c
$cat > foo.c <<'EOP'
int main() { printf("%d\n", bar1()); exit(0); }
EOP
$cc $ccflags -c bar1.c >/dev/null 2>&1
$cc $ccflags -c bar2.c >/dev/null 2>&1
$cc $ccflags -c foo.c >/dev/null 2>&1
$ar rc bar$_a bar2$_o bar1$_o >/dev/null 2>&1
if $cc $ccflags $ldflags -o foobar foo$_o bar$_a $libs > /dev/null 2>&1 &&
./foobar >/dev/null 2>&1; then
echo "ar appears to generate random libraries itself."
orderlib=false
ranlib=":"
elif $ar ts bar$_a >/dev/null 2>&1 &&
$cc $ccflags $ldflags -o foobar foo$_o bar$_a $libs > /dev/null 2>&1 &&
./foobar >/dev/null 2>&1; then
echo "a table of contents
needs to be added with 'ar ts'."
orderlib=false
ranlib="$ar ts"
else
?X: Allow hints to specify their own ranlib "script". For instance, on
?X: some NeXT machines, the timestamp put by ranlib is not correct, and this
?X: may raise tedious recompiles for nothing. Therefore, NeXT may add the
?X: ranlib='sleep 5; /bin/ranlib' line in their hints to "fix" that.
?X: (reported by Andreas Koenig <k@franz.ww.tu-berlin.de>)
case "$ranlib" in
:) ranlib="";
")
ranlib=`./loc ranlib X /usr/bin /bin /usr/local/bin`
$test -f $ranlib || ranlib="
;;
esac
if $test -n "$ranlib"; then
echo "your system has '$ranlib'; we'll use that."
orderlib=false
else
echo "your system doesn't seem to support random libraries"
echo "so we'll use lorder and tsort to order the libraries."
orderlib=true
ranlib=":"
fi
fi
$rm -f foo* bar*

```

Found in path(s):

```

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/orderlib.U

```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: cpp_trad.U 1 2006-08-24 12:32:52Z rmanfredi $
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: $Log: cpp_stuff.U,v $
?MAKE:cpp_trad: cpp cat contains rm
?MAKE: -pick add $@ %<
?S:cpp_trad:
?S: This variable contains the program to run to get traditional C
?S: preprocessor semantics and not ISO C semantics: we want something
?S: that knows as little about C as possible to use as a more general
?S: purpose preprocessor.
?S:.
?F:!foo.c !foo.cpp
: how do we get traditional cpp semantics?
echo " "
echo "Checking to see how to get traditional cpp semantics..."
>&4
$cat >foo.c <<'EOF'
#define A(x) x
#define B(y) y
A(a)B(b)
EOF
if $cpp foo.c >foo.cpp; $contains ab foo.cpp >/dev/null 2>&1; then
echo "Plain '$cpp' works just fine."
cpp_trad="$cpp"
elif $cpp -traditional foo.c >foo.cpp; \
$contains ab foo.cpp >/dev/null 2>&1; then
echo "We'll use '$cpp -traditional' to get proper semantics."
cpp_trad="$cpp -traditional"
else
echo "I don't know how to get traditional semantics with '$cpp'." >&4
cpp_trad="$cpp"
fi
$rm -f foo.c foo.cpp

Found in path(s):
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/cpp_trad.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: devtype.U,v 3.0.1.1 1994/08/29 16:31:27 ram Exp $
?RCS:
?RCS: Copyright (c) 1991-1993, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 3.0.
?RCS:
?RCS: $Log: devtype.U,v $
?RCS: Revision 3.0.1.1 1994/08/29 16:31:27 ram
?RCS: patch32: now uses new Typedef unit to compute type information
?RCS:
?RCS: Revision 3.0 1993/08/18 12:09:33 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:devtype: Myread Typedef
?MAKE: -pick add $@ %<
?S:devtype:
?S: This variable defines Dev_t to be something like dev_t, long,
?S: int, or whatever type is used to declare device numbers.
?S: This is usually the same as
?S: the type of the third argument
?S: to mknod(2).
?S:.
?C:Dev_t:
?C: This symbol holds the type used to declare device numbers.
?C: It can be int, long, dev_t, etc... This is usually the same
?C: as the type of the third argument to mknod(2).
?C: It may be necessary to include <sys/types.h> to get any
?C: typedef'ed information.
?C:.
?H:#define Dev_t $devtype /* <device> type */
?H:.
?LINT: set devtype
: see what type is used for devices
rp="What is the type used for device numbers on this system?"
set dev_t devtype long stdio.h sys/types.h
eval $typedef_ask
```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/typedefs/devtype.U
```

No license file was found, but licenses were detected in source scan.

?RCS: You may distribute under the terms of either the GNU General Public

Found in path(s):

- * /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_stats3.U
- * /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/threads/d_pthreadj.U
- * /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_isless.U
- * /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_strtouq.U
- * /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/ebcdic/ebcdic.U
- * /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_ptrdiff_t.U
- *
- /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_isfinite.U
- * /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_fpos64_t.U
- * /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_isnan.U
- * /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/threads/d_pthread_y.U
- * /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_strtoll.U
- * /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_prctl.U
- * /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/time_size.U
- *
- /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_stats4.U
- * /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/modified/d_union_semun.U
- * /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/modified/d_longlong.U
- * /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_signbit.U
- * /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_off64_t.U
- * /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_printfd.U
- * /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_isinf.U
- *
- /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_cplusplus.U

```

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/perl/d_sprintf_len.U
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/perl/d_isnormal.U
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/perl/d_strtoull.U
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/perl/i_stdbool.U
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/perl/d_futimes.U
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/threads/d_pthread_atfork.U
*
/opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/perl/d_dlsymun.U
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/threads/d_pthratrj.U
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/perl/d_fcntl_can_lock.U
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/perl/d_libm_lib_version.U
No license file was found, but licenses were detected in source scan.

```

```

?RCS: $Id: d_select.U 1 2006-08-24 12:32:52Z rmanfredi $
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: $Log: d_select.U,v $
?RCS: Revision 3.0 1993/08/18 12:07:02 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:d_select: Inlibc
?MAKE: -pick add $@ %<
?S:d_select:
?S: This variable conditionally defines HAS_SELECT if select() is
?S: available to select active file descriptors. A <sys/time.h>
?S: inclusion may be necessary for the timeout field.
?S:.
?C:HAS_SELECT:
?C: This symbol, if defined, indicates that the select routine is
?C: available

```

to select active file descriptors. If the timeout field

?C: is used, <sys/time.h> may need to be included.

?C:.

?H:#\$d_select HAS_SELECT /**/

?H:.

?LINT:set d_select

: see if select exists

set select d_select

eval \$inlibc

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/d_select.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1999, Jarkko Hietaniemi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 3.0.

?RCS:

?MAKE:d_posix_mq: Setvar d_mq_open d_mq_unlink d_mq_close d_mq_send d_mq_receive d_mq_notify

d_mq_setattr d_mq_getattr i_mqueue

?MAKE: -pick add \$@ %<

?S:d_posix_mq:

?S: This variable conditionally defines the HAS_POSIX_MQ symbol, which

?S: indicates that the entire POSIX mq_*(2) library is present.

?S:.

?C:HAS_POSIX_MQ:

?C: This symbol, if defined, indicates that the entire POSIX mq_*(2)

?C: library is supported.

?C:.

?H:#\$d_posix_mq HAS_POSIX_MQ /**/

?H:.

?LINT:set d_posix_mq

: see how much of the 'POSIX mq_*(2)' library

is present.

echo " "

case

"\$i_mqueue\$d_mq_open\$d_mq_close\$d_mq_send\$d_mq_receive\$d_mq_notify\$d_mq_setattr\$d_mq_getattr\$d_mq_unlink" in

"\$undef") val="\$undef" ;;

*) val="\$define" ;;

esac

```

case "$val" in
"$define") echo "You have the full POSIX mq_*(2) library." >&4 ;;
"$undef")  echo "You don't have the full POSIX mq_*(2) library." >&4 ;;
esac
set d_posix_mq
eval $setvar

```

Found in path(s):

```

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/perl/d_posix_mq.U

```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: sig_name.U,v \$

?RCS: Revision 3.0.1.5 1997/02/28 16:21:25 ram

?RCS: patch61: brand new algorithm for sig_name and (new!) sig_num

?RCS:

?RCS: Revision 3.0.1.4 1995/07/25 14:14:54 ram

?RCS: patch56: added <asm/signal.h> lookup for linux

?RCS:

?RCS: Revision 3.0.1.3 1995/05/12 12:24:11 ram

?RCS: patch54: now looks for <linux/signal.h> too (ADO)

?RCS:

?RCS: Revision 3.0.1.2 1994/06/20 07:06:57 ram

?RCS: patch30: final echo was missing to close awk-printed string

?RCS:

?RCS: Revision 3.0.1.1

1994/05/06 15:17:55 ram

?RCS: patch23: signal list now formatted to avoid scroll-ups (ADO)

?RCS:

?RCS: Revision 3.0 1993/08/18 12:09:47 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?MAKE:sig_name sig_name_init sig_num sig_num_init sig_count sig_size: \

awk Signal Oldconfig rm

?MAKE: -pick add \$@ %<

?S:sig_name:

?S: This variable holds the signal names, space separated. The leading

?S: SIG in signal name is removed. A ZERO is prepended to the

?S: list. This is currently not used.

?S:.

?S: sig_name_init:

?S: This variable holds the signal names, enclosed in double quotes and

?S: separated by commas, suitable for use in the SIG_NAME definition

?S: below. A "ZERO" is prepended to the list, and the list is

?S: terminated with a plain 0. The leading SIG in signal names

?S: is removed. See sig_num.

?S:.

?S: sig_num:

?S: This variable holds the signal numbers, space separated. A ZERO is

?S: prepended to the list (corresponding to the fake SIGZERO), and

?S: the list is terminated

with a 0. Those numbers correspond to

?S: the value of the signal listed in the same place within the

?S: sig_name list.

?S:.

?S: sig_num_init:

?S: This variable holds the signal numbers, enclosed in double quotes and

?S: separated by commas, suitable for use in the SIG_NUM definition

?S: below. A "ZERO" is prepended to the list, and the list is

?S: terminated with a plain 0.

?S:.

?S: sig_count (sig_name.U):

?S: This variable holds a number larger than the largest valid

?S: signal number. This is usually the same as the NSIG macro.

?S:.

?S: sig_size:

?S: This variable contains the number of elements of the sig_name

?S: and sig_num arrays, excluding the final NULL entry.

?S:.

?C: SIG_NAME:

?C: This symbol contains a list of signal names in order of

?C: signal number. This is intended

?C: to be used as a static array initialization, like this:

?C: char *sig_name[] = { SIG_NAME };

?C: The signals in the list are separated with commas, and each signal

?C: is surrounded by double

quotes. There is no leading SIG in the signal

?C: name, i.e. SIGQUIT is known as "QUIT".

?C: Gaps in the signal numbers (up to NSIG) are filled in with NUMnn,

?C: etc., where nn is the actual signal number (e.g. NUM37).

?C: The signal number for sig_name[i] is stored in sig_num[i].

?C: The last element is 0 to terminate the list with a NULL. This

?C: corresponds to the 0 at the end of the sig_num list.

?C:.

?C: SIG_NUM:

?C: This symbol contains a list of signal numbers, in the same order as the

?C: SIG_NAME list. It is suitable for static array initialization, as in:

```
?C: int sig_num[] = { SIG_NUM };
```

?C: The signals in the list are separated with commas, and the indices
?C: within that list and the SIG_NAME list match, so it's easy to compute
?C: the signal name from a number or vice versa at the price of a small
?C: dynamic linear lookup.

?C: Duplicates are allowed, but are moved to the end of the list.

?C: The signal number corresponding to sig_name[i] is sig_number[i].

```
?C: if (i
    < NSIG) then sig_number[i] == i.
```

?C: The last element is 0, corresponding to the 0 at the end of
?C: the sig_name list.

?C:.

?C:SIG_COUNT:

?C: This variable contains a number larger than the largest
?C: signal number. This is usually the same as the NSIG macro.

?C:.

?C:SIG_SIZE:

?C: This variable contains the number of elements of the sig_name
?C: and sig_num arrays, excluding the final NULL entry.

?C:.

```
?H:#define SIG_NAME $sig_name_init /**/
?H:#define SIG_NUM $sig_num_init /**/
?H:#define SIG_COUNT $sig_count /**/
?H:#define SIG_SIZE $sig_size /**/
?H:.
```

```
?T:i doinit
?F:!= !signal_cmd
?X: signal.cmd creates a file signal.lst which has two columns:
?X: NAME number, e.g.
?X: HUP 1
?X: The list is sorted on signal number, with duplicates moved to
?X: the end..
: generate list of signal names
echo " "
case "$sig_name_init" in
") doinit=yes ;;
*) case "$sig_num_init" in
    "*,*) doinit=yes ;;
    esac ;;
esac
case "$doinit" in
yes)
echo "Generating a list of signal names and
numbers..." >&4
./signal_cmd
sig_count=`$awk '/^NSIG/ { printf "%d", $2 }' signal.lst`
sig_name=`$awk 'BEGIN { printf "ZERO " }
```

```

    !/^NSIG/ { printf "%s ", $1 } signal.lst`
sig_num=`$awk 'BEGIN { printf "0 " }
    !/^NSIG/ { printf "%d ", $2 }' signal.lst`
sig_name_init=`$awk 'BEGIN { printf "\"ZERO\\", " }
    !/^NSIG/ { printf "\"%s\\", ", $1 }
    END { printf "0\\n" }' signal.lst`
sig_num_init=`$awk 'BEGIN { printf "0, " }
    !/^NSIG/ { printf "%d, ", $2 }
    END { printf "0\\n" }' signal.lst`
;;
esac
echo "The following $sig_count signals are available:"
echo " "
echo $sig_name | $awk \
'BEGIN { linelen = 0 }
{
for (i = 1; i <= NF; i++) {
name = "SIG" $i " "
linelen = linelen + length(name)
if (linelen > 70) {
printf "\\n"
linelen = length(name)
}
printf "%s", name
}
printf "\\n"
}'
sig_size=`echo $sig_name | awk '{print NF}'`
$rm -f signal signal.c signal.awk signal.lst signal_cmd

```

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/sig_name.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: errnolist.U,v 3.0.1.2 1997/02/28 15:48:01 ram Exp \$

?RCS:

?RCS: Copyright (c) 1991-1993, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 3.0.

?RCS:

?RCS: \$Log: errnolist.U,v \$

?RCS: Revision 3.0.1.2 1997/02/28 15:48:01 ram

?RCS: patch61: replaced .a with \$_a all over the place

```

?RCS: patch61: likewise for .o replaced by $_o
?RCS:
?RCS: Revision 3.0.1.1 1994/01/24 14:10:54 ram
?RCS: patch16: created
?RCS:
?MAKE:errnolist errnolist_SH errnolist_a errnolist_c errnolist_o: cat \
  Compile +d_sysernlst _a _o
?MAKE: -pick add $@ %<
?S:errnolist:
?S: This variable holds the base name of a file containing the
?S: definition
  of the sys_errnolist array, if the C library
?S: doesn't provide it already. Otherwise, its value is empty.
?S: The following lines should be included in your Makefile.SH:
?S:
?S: case "$serrnolist" in
?S: ") ;;
?S: *)
?S: $spitshell >>Makefile <<!GROK!THIS!
?S: $serrnolist_c: $serrnolist_SH $serrnolist_a
?S: sh ./serrnolist_SH
?S:
?S: !GROK!THIS!
?S: ;;
?S: esac
?S:
?S: You may define the 'errnolist' variable in your Myinit.U if you
?S: wish to override its default value "errnolist".
?S:.
?S:errnolist_SH:
?S: This is the name of a file which will generate errnolistic.
?S:.
?S:errnolist_a:
?S: This is the name of the awk script called by errnolist_SH.
?S:.
?S:errnolist_c:
?S: This is the name of a generated C file which provides the
?S: definition of the sys_errnolist array.
?S:.
?S:errnolist_o:
?S: This is the name of the object file which provides the
?S: definition of the sys_errnolist array, if the C library
?S: doesn't provide it already. Otherwise, its value is
  empty.
?S:.
?INIT:errnolist=errnolist
: check for sys_errnolist
@if d_sysernlst || HAS_SYS_ERRNOLIST

```

```

case "$d_sysernlst" in
"$define")
    errnolist="
    errnolist_SH="
    errnolist_a="
    errnolist_c="
    errnolist_o="
;;
*)
echo " "
echo "I'll make sure your Makefile provides sys_errnolist in $errnolist.c"
    errnolist_SH=$errnolist.SH
    errnolist_a=$errnolist$_a
    errnolist_c=$errnolist.c
    errnolist_o=$errnolist$_o
;;
esac
@else
echo " "
$cat <<EOM
Checking to see if your C library provides us with sys_errnolist[...
EOM
$cat >errnolist.c <<'EOCP'
extern char *sys_errnolist[];
int main() {
    char *p0 = sys_errnolist[0];
    char *p1 = sys_errnolist[1];

    return (p0 == p1); /* Make sure they're not optimized away */
}
EOCP
set errnolist
if eval $compile; then
    echo "It does."
    errnolist="
    errnolist_SH="
    errnolist_a="
    errnolist_c="
    errnolist_o="
else
echo "I'll make sure your Makefile provides sys_errnolist in $errnolist.c"
    errnolist_SH=$errnolist.SH
    errnolist_a=$errnolist$_a
    errnolist_c=$errnolist.c
    errnolist_o=$errnolist$_o
fi
@end

```

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/compline/errnolist.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_gconvert.U,v 3.0.1.3 1997/02/28 15:33:38 ram Exp \$

?RCS:

?RCS: Copyright (c) 1991-1993, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 3.0.

?RCS:

?RCS: Original Author: Andy Dougherty <doughera@lafcol.lafayette.edu>

?RCS:

?RCS: \$Log: d_gconvert.U,v \$

?RCS: Revision 3.0.1.3 1997/02/28 15:33:38 ram

?RCS: patch61: integrated new unit from perl5

?RCS:

?RCS: Revision 3.0.1.2 1995/07/25 13:55:59 ram

?RCS: patch56: improved comments about the Gconvert macro (ADO)

?RCS: patch56: force compile-link test since it may exist but be unusable (ADO)

?RCS:

?RCS: Revision 3.0.1.1 1994/10/29 16:12:51 ram

?RCS: patch36:

created by ADO

?RCS:

?MAKE:d_Gconvert: \

Compile cat Inlibc rm _o rm_try i_stdlib i_string d_qgcvt run \
uselongdouble d_longdbl d_PRIgldbl sPRIgldbl

?MAKE: -pick add \$@ %<

?S:d_Gconvert:

?S: This variable holds what Gconvert is defined as to convert

?S: floating point numbers into strings. By default, Configure

?S: sets this macro to use the first of gconvert, gcvt, or sprintf

?S: that pass sprintf-%g-like behavior tests. If perl is using

?S: long doubles, the macro uses the first of the following

?S: functions that pass Configure's tests: qgcvt, sprintf (if

?S: Configure knows how to make sprintf format long doubles--see

?S: sPRIgldbl), gconvert, gcvt, and sprintf (casting to double).

?S: The gconvert_preference and gconvert_ld_preference variables

?S: can be used to alter Configure's preferences, for doubles and

?S: long doubles, respectively. If present, they contain a

?S: space-separated list of one or more of the above function

?S: names in the order they should be tried.

?S:

?S: d_Gconvert
 may be set to override Configure with a platform-
 ?S: specific function. If this function expects a double, a
 ?S: different value may need to be set by the uselongdouble.cbu
 ?S: call-back unit so that long doubles can be formatted without
 ?S: loss of precision.
 ?S:.
 ?C:Gconvert:
 ?C: This preprocessor macro is defined to convert a floating point
 ?C: number to a string without a trailing decimal point. This
 ?C: emulates the behavior of sprintf("%g"), but is sometimes much more
 ?C: efficient. If gconvert() is not available, but gcvt() drops the
 ?C: trailing decimal point, then gcvt() is used. If all else fails,
 ?C: a macro using sprintf("%g") is used. Arguments for the Gconvert
 ?C: macro are: value, number of digits, whether trailing zeros should
 ?C: be retained, and the output buffer.
 ?C: The usual values are:
 ?C: d_Gconvert='gconvert((x),(n),(t),(b))'
 ?C: d_Gconvert='gcvt((x),(n),(b))'
 ?C: d_Gconvert='sprintf((b),"%.*g",(n),(x))'
 ?C: The last two assume trailing
 zeros should not be kept.
 ?C:.
 ?H:#define Gconvert(x,n,t,b) \$d_Gconvert
 ?H:.
 ?T: xxx_list xxx_convert xxx_ld_list
 ?F:!try
 ?LINT:extern gconvert_preference
 ?LINT:extern gconvert_ld_preference
 : Check how to convert floats to strings.

```

if test "X$d_Gconvert" = X; then

echo " "
echo "Checking for an efficient way to convert floats to strings."
echo " " > try.c
case "$uselongdouble" in
"$define") echo "#define USE_LONG_DOUBLE" >>try.c ;;
esac
case "$d_longdbl" in
"$define") echo "#define HAS_LONG_DOUBLE" >>try.c ;;
esac
case "$d_PRIgdbl" in
"$define") echo "#define HAS_PRIgdbl" >>try.c ;;
esac
$cat >>try.c <<EOP
#endif TRY_gconvert
#define Gconvert(x,n,t,b) gconvert((x),(n),(t),(b))

```

```

char *myname = "gconvert";
#endif
#ifdef TRY_gcvt
#define Gconvert(x,n,t,b) gcvt((x),(n),(b))
char *myname = "gcvt";
#endif
#ifdef TRY_qgcvt
#define Gconvert(x,n,t,b) qgcvt((x),(n),(b))
char *myname = "qgcvt";
#define DOUBLETYP long double
#endif
#ifdef TRY_sprintf
#if defined(USE_LONG_DOUBLE) && defined(HAS_LONG_DOUBLE)
#ifdef
HAS_PRIgldbl
#define Gconvert(x,n,t,b) sprintf((b),"%.*$sPRIgldbl,(n),(x))
#else
#define Gconvert(x,n,t,b) sprintf((b),"%.*g",(n),(double)(x))
#endif
#else
#define Gconvert(x,n,t,b) sprintf((b),"%.*g",(n),(x))
#endif
char *myname = "sprintf";
#endif

#ifdef DOUBLETYP
#if defined(USE_LONG_DOUBLE) && defined(HAS_LONG_DOUBLE)
#define DOUBLETYP long double
#else
#define DOUBLETYP double
#endif
#endif

#include <stdio.h>

#ifdef I_STDLIB
#include <stdlib.h>
#endif
#ifdef I_STRING
#include <string.h>
#else
#include <strings.h>
#endif

int checkit(char *expect, char *got)
{

```

```

    if (strcmp(expect, got)) {
        printf("%s oddity: Expected %s, got %s\n",
            myname, expect, got);
        exit(1);
    }
}

int main()
{
    char buf[64];
    buf[63] = '\0';

    /* This must be 1st test on (which?) platform */
    /* Alan Burlison <AlanBurlsin@unn.unisys.com> */
    Gconvert((DOUBLETTYPE)0.1, 8, 0, buf);
    checkit("0.1", buf);

    Gconvert((DOUBLETTYPE)0.01,
        8, 0, buf);
    checkit("0.01", buf);

    Gconvert((DOUBLETTYPE)0.001, 8, 0, buf);
    checkit("0.001", buf);

    Gconvert((DOUBLETTYPE)0.0001, 8, 0, buf);
    checkit("0.0001", buf);

    Gconvert((DOUBLETTYPE)0.00009, 8, 0, buf);
    if (strlen(buf) > 5)
        checkit("9e-005", buf); /* for Microsoft ?? */
    else
        checkit("9e-05", buf);

    Gconvert((DOUBLETTYPE)1.0, 8, 0, buf);
    checkit("1", buf);

    Gconvert((DOUBLETTYPE)1.1, 8, 0, buf);
    checkit("1.1", buf);

    Gconvert((DOUBLETTYPE)1.01, 8, 0, buf);
    checkit("1.01", buf);

    Gconvert((DOUBLETTYPE)1.001, 8, 0, buf);
    checkit("1.001", buf);

    Gconvert((DOUBLETTYPE)1.0001, 8, 0, buf);
    checkit("1.0001", buf);

```

```
Gconvert((DOUBLETTYPE)1.00001, 8, 0, buf);
checkit("1.00001", buf);
```

```
Gconvert((DOUBLETTYPE)1.000001, 8, 0, buf);
checkit("1.000001", buf);
```

```
Gconvert((DOUBLETTYPE)0.0, 8, 0, buf);
checkit("0", buf);
```

```
Gconvert((DOUBLETTYPE)-1.0, 8, 0, buf);
checkit("-1", buf);
```

```
/* Some Linux gcvt's give 1.e+5 here. */
Gconvert((DOUBLETTYPE)100000.0, 8, 0, buf);
checkit("100000",
buf);
```

```
/* Some Linux gcvt's give -1.e+5 here. */
Gconvert((DOUBLETTYPE)-100000.0, 8, 0, buf);
checkit("-100000", buf);
```

```
Gconvert((DOUBLETTYPE)123.456, 8, 0, buf);
checkit("123.456", buf);
```

```
/* Testing of 1e+129 in bigintpm.t must not get extra '.' here. */
Gconvert((DOUBLETTYPE)1e34, 8, 0, buf);
/* 34 should be enough to scare even long double
 * places into using the e notation. */
if (strlen(buf) > 5)
    checkit("1e+034", buf); /* for Microsoft */
else
    checkit("1e+34", buf);
```

```
/* For Perl, if you add additional tests here, also add them to
 * t/base/num.t for benefit of platforms not using Configure or
 * overriding d_Gconvert */
```

```
exit(0);
}
```

EOP

?X: List of order in which to search for functions.

?X: Usual order of efficiency is gconvert gcvt sprintf

?X: If a hint file sets a d_Gconvert="gconvert" or "gcvt" or "sprintf",

?X: then that is taken as a hint for which function to try first.

?X: (e.g. that function may be in a problematic /usr/ucblib library,
and

?X: the user may or may not choose to use -lucb stuff.)

?X: Any other hint file (or previous config.sh) setting is left intact.

```

: first add preferred functions to our list
xxx_list=""
for xxx_convert in $gconvert_preference; do
    case $xxx_convert in
        gcvt|gconvert|sprintf) xxx_list="$xxx_list $xxx_convert" ;;
        *) echo "Discarding unrecognized gconvert_preference $xxx_convert" >&4 ;;
    esac
done
: then add any others
for xxx_convert in gconvert gcvt sprintf; do
    case "$xxx_list" in
        *$xxx_convert*) ;;
        *) xxx_list="$xxx_list $xxx_convert" ;;
    esac
done

case "$d_longdbl$uselongdouble" in
"$define$define")
    : again, add preferred functions to our list first
    xxx_ld_list=""
    for xxx_convert in $gconvert_ld_preference; do
        case $xxx_convert in
            qgcvt|gcvt|gconvert|sprintf) xxx_ld_list="$xxx_ld_list $xxx_convert" ;;
            *) echo "Discarding unrecognized gconvert_ld_preference $xxx_convert" ;;
        esac
    done
    : then add qgcvt, sprintf--then,
in xxx_list order, gconvert and gcvt
    for xxx_convert in qgcvt sprintf $xxx_list; do
        case "$xxx_ld_list" in
            $xxx_convert*|*" $xxx_convert"*) ;;
            *) xxx_ld_list="$xxx_ld_list $xxx_convert" ;;
        esac
    done
    : if sprintf cannot do long doubles, move it to the end
    if test "$d_PRIgldbl" != "$define"; then
        xxx_ld_list=""echo $xxx_ld_list|sed s/sprintf/^ sprintf"
    fi
    : if no qgcvt, remove it
    if test "$d_qgcvt" != "$define"; then
        xxx_ld_list=""echo $xxx_ld_list|sed s/qgcvt/^"
    fi
    : use the ld_list
    xxx_list="$xxx_ld_list"
    ;;
esac

for xxx_convert in $xxx_list; do

```

```

echo "Trying $xxx_convert..."
?X: Do NOT use $rm_try here, as we need to keep try.c
$rm -f try try$_o core
set try -DTRY_$xxx_convert
if eval $compile; then
echo "$xxx_convert() found." >&4
if $run ./try; then
echo "I'll use $xxx_convert to convert floats into a string." >&4
break;
else
echo "...But $xxx_convert didn't
work as I expected."
xxx_convert="
fi
else
echo "$xxx_convert NOT found." >&4
fi
done

if test X$xxx_convert = X; then
echo "*** WHOA THERE!!! ***" >&4
echo "None of ($xxx_list) seemed to work properly. I'll use sprintf." >&4
xxx_convert=sprintf
fi

case "$xxx_convert" in
gconvert) d_Gconvert='gconvert((x),(n),(t),(b))' ;;
gcvt) d_Gconvert='gcvt((x),(n),(b))' ;;
qgcvt) d_Gconvert='qgcvt((x),(n),(b))' ;;
*) case "$uselongsdouble$d_longdbl$d_PRIgldbl" in
"$define$define$define")
d_Gconvert="sprintf((b),\"%.*\"$sPRIgldbl,(n),(x))" ;;
"$define$define$undef")
d_Gconvert='sprintf((b),"%.*g",(n),(double)(x))' ;;
*) d_Gconvert='sprintf((b),"%.*g",(n),(x))' ;;
esac
;;
esac

fi
$rm_try

```

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/compline/d_gconvert.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_siglist.U 1 2006-08-24 12:32:52Z rmanfredi \$

```

?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: $Log: d_siglist.U,v $
?RCS: Revision 3.0 1993/08/18 12:07:22 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:d_siglist: Csym Setvar
?MAKE: -pick add $@ %<
?S:d_siglist:
?S: This variable conditionally defines HAS_SYS_SIGLIST if sys_siglist[] is
?S: available to translate signal numbers to strings.
?S:.
?C:HAS_SYS_SIGLIST (SYS_SIGLIST):
?C: This symbol, if defined, indicates that the sys_siglist array is
?C: available to translate signal numbers
to strings.
?C:.
?H:#$d_siglist HAS_SYS_SIGLIST /**/
?H:.
?LINT:set d_siglist
: see if sys_siglist[] exist
echo " "
if set sys_siglist val -a d_siglist; eval $csym; $val; then
echo "You have sys_siglist[] for signal description." >&4
val="$define"
else
echo "You don't have sys_siglist[]." >&4
val="$undef"
fi
set d_siglist
eval $setvar

```

Found in path(s):

```

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/d_siglist.U

```

No license file was found, but licenses were detected in source scan.

```

?RCS: $Id: Obsol_sh.U 1 2006-08-24 12:32:52Z rmanfredi $
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:

```

```
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: $Log: Obsol_sh.U,v $
?RCS: Revision 3.0 1993/08/18 12:05:11 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?X:
?X: This file is prepended to .MT/Obsol_sh if that file is not empty. That file
?X: contains the necessary mappings of new symbols to obsolete ones.
?X:
?MAKE:Obsol_sh:
?MAKE: -pick prepend $@ ./Obsol_sh
?LINT:nocomment
#
# The following symbols are obsolete. They are mapped to the the new
# symbols only to ease the transition process.
# The sources should be
# updated so as to use the new symbols only, since supporting of those
# obsolete symbols may end without notice.
#

Found in path(s):
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/Obsol_sh.U
No license file was found, but licenses were detected in source scan.

?RCS: $Id$
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: Original Author: Andy Dougherty <doughera@lafcol.lafayette.edu>
?RCS:
?RCS: $Log: Ins.U,v $
?RCS: Revision 3.0.1.1 1994/06/20 07:05:52 ram
?RCS: patch30: created by ADO
?RCS:
?MAKE:issymlink: Ins test rm
?MAKE: -pick add $@ %<
```

```

?S:issymlink:
?S: This variable holds the test command to test for a symbolic link
?S: (if they are supported). Typical values include 'test -h' and
?S: 'test -L'.
?S:.
?T:pth p
?LINT:change PATH test
?LINT:extern newsh
: determine whether symbolic links are supported
echo
" "
case "$lns" in
*"ln*" -s")
echo "Checking how to test for symbolic links..." >&4
$lns blurfl sym
if $test "$X$issymlink" = X; then
?X:
?X: In some AIX 4 versions the (ksh) builtin test (-h) is broken.
?X:
case "$newsh" in
") sh -c "PATH= test -h sym" >/dev/null 2>&1 ;;
*) $newsh -c "PATH= test -h sym" >/dev/null 2>&1 ;;
esac
if test $? = 0; then
issymlink="test -h"
else
echo "Your builtin 'test -h' may be broken." >&4
case "$stest" in
/*) ;;
*) pth=`echo $PATH | sed -e "s/$p_/ /g"`
for p in $pth
do
if test -f "$p/$stest"; then
test="$p/$stest"
break
fi
done
;;
esac
case "$stest" in
/*)
echo "Trying external '$stest -h'." >&4
issymlink="$stest -h"
if $stest ! -h sym >/dev/null 2>&1; then
echo "External '$stest -h' is broken, too." >&4
issymlink="
fi
;;

```

```

*) issymblink=" ;;
esac
fi
fi
if $test "X$issymblink" = X; then
if $test -L sym 2>/dev/null; then
issymblink="$test
-L"
echo "The builtin '$test -L' worked." >&4
fi
fi
if $test "X$issymblink" != X; then
echo "You can test for symbolic links with '$issymblink'." >&4
else
echo "I do not know how you can test for symbolic links." >&4
fi
$rm -f blurfl sym
;;
*) echo "No symbolic links, so not testing for their testing..." >&4
;;
esac

```

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/issymblink.U

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/issymblink.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_setpwent_r.U,v 0RCS:

?RCS: Copyright (c) 2002,2003 Jarkko Hietaniemi

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?RCS: Generated by the reentr.pl from the Perl 5.8 distribution.

?RCS:

?MAKE:d_setpwent_r setpwent_r_proto: Inlibc Protochk Hasproto i_systypes \
 usethreads i_pwd extern_C

?MAKE: -pick add \$@ %<

?S:d_setpwent_r:

?S: This variable conditionally defines the HAS_SETPWENT_R symbol,

?S: which indicates to the C program that the setpwent_r()

?S: routine is available.

?S:.

?S:setpwent_r_proto:

?S: This variable encodes the prototype of setpwent_r.

?S: It is zero if d_setpwent_r is undef, and one of the

?S: REENTRANT_PROTO_T_ABC macros of reentr.h if d_setpwent_r
?S: is defined.
?S:.
?C:HAS_SETPWENT_R:
?C: This symbol, if defined, indicates that the setpwent_r routine
?C: is available to
setpwent re-entrantly.
?C:.
?C:SETPWENT_R_PROTO:
?C: This symbol encodes the prototype of setpwent_r.
?C: It is zero if d_setpwent_r is undef, and one of the
?C: REENTRANT_PROTO_T_ABC macros of reentr.h if d_setpwent_r
?C: is defined.
?C:.
?H:#\$d_setpwent_r HAS_SETPWENT_R /**/
?H:#define SETPWENT_R_PROTO \$setpwent_r_proto /**/
?H:.
?T:try hdrs d_setpwent_r_proto
: see if setpwent_r exists
set setpwent_r d_setpwent_r
eval \$inlibc
case "\$d_setpwent_r" in
"\$define")
hdrs="\$i_systypes sys/types.h define stdio.h \$i_pwd pwd.h"
case "\$d_setpwent_r_proto:\$usethreads" in
":define") d_setpwent_r_proto=define
set d_setpwent_r_proto setpwent_r \$hdrs
eval \$hasproto ;;
*) ;;
esac
case "\$d_setpwent_r_proto" in
define)
case "\$setpwent_r_proto" in
"|0) try='int setpwent_r(FILE**);'
./protochk "\$extern_C \$try" \$hdrs && setpwent_r_proto=I_H ;;
esac
case "\$setpwent_r_proto" in
"|0) try='void setpwent_r(FILE**);'
./protochk "\$extern_C \$try" \$hdrs && setpwent_r_proto=V_H ;;
esac
case
"\$setpwent_r_proto" in
"|0) d_setpwent_r=undef
setpwent_r_proto=0
echo "Disabling setpwent_r, cannot determine prototype." >&4 ;;
*) case "\$setpwent_r_proto" in
REENTRANT_PROTO*) ;;
*) setpwent_r_proto="REENTRANT_PROTO_\$setpwent_r_proto" ;;

```

esac
echo "Prototype: $try" ;;
esac
;;
*) case "$usethreads" in
define) echo "setpwent_r has no prototype, not using it." >&4 ;;
esac
d_setpwent_r=undef
setpwent_r_proto=0
;;
esac
;;
*) setpwent_r_proto=0
;;
esac

```

Found in path(s):

```

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/threads/d_setpwent_r.U

```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 2001 Jarkko Hietaniemi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 3.0.

?RCS:

?MAKE:d_socketmarkproto: Hasproto d_socket

?MAKE: -pick add \$@ %<

?S:d_socketmarkproto:

?S: This variable conditionally defines the HAS_SOCKETMARK_PROTO symbol,

?S: which indicates to the C program that the system provides

?S: a prototype for the socketmark() function. Otherwise, it is

?S: up to the program to supply one.

?S:.

?C:HAS_SOCKETMARK_PROTO:

?C: This symbol, if defined, indicates that the system provides

?C: a prototype for the socketmark() function. Otherwise, it is up

?C: to the program to supply one. A good

guess is

?C: extern int socketmark(int);

?C:.

?H:#\$d_socketmarkproto HAS_SOCKETMARK_PROTO /**/

?H:.

```
?LINT:set d_socketmarkproto
: see if prototype for socketmark is available
echo " "
set d_socketmarkproto socketmark $d_socket sys/socket.h
eval $hasproto
```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/perl/d_socketmarkproto.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: d_xdrs.U 1 2006-08-24 12:32:52Z rmanfredi $
```

```
?RCS:
```

```
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
```

```
?RCS:
```

```
?RCS: You may redistribute only under the terms of the Artistic Licence,
```

```
?RCS: as specified in the README file that comes with the distribution.
```

```
?RCS: You may reuse parts of this distribution only within the terms of
```

```
?RCS: that same Artistic Licence; a copy of which may be found at the root
```

```
?RCS: of the source tree for dist 4.0.
```

```
?RCS:
```

```
?RCS: $Log: d_xdrs.U,v $
```

```
?RCS: Revision 3.0 1993/08/18 12:08:04 ram
```

```
?RCS: Baseline for dist 3.0 netwide release.
```

```
?RCS:
```

```
?MAKE:d_xdrs: cat Csym Setvar
```

```
?MAKE: -pick add $@ %<
```

```
?S:d_xdrs:
```

```
?S: This symbol conditionally defines HAS_XDRS which indicates to the C
```

```
?S: program that XDR serialization routines are available.
```

```
?S:.
```

```
?C:HAS_XDRS (XDRS):
```

```
?C: This symbol if defined indicates to the C program that the XDR
```

```
?C: serialization routines are available to transfer data
```

```
across
```

```
?C: various architectures.
```

```
?C:.
```

```
?H:#$d_xdrs HAS_XDRS /**/
```

```
?H:.
```

```
?LINT:set d_xdrs
```

```
: see if XDR is available
```

```
echo " "
```

```
if set xdr_int val -f d_xdrs; eval $csym; $val; then
```

```
echo "Ahh! You have XDR routines for network communications." >&4
```

```
val="$define"
```

```
else
```

```
$cat >&4 <<EOM
```

```
Sigh! You do not have XDR routines -- Network communications may be hazardous.
```

```
EOM
val="$undef"
fi
set d_xdrs
eval $setvar
```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/d_xdrs.U
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_ftime.U 1 2006-08-24 12:32:52Z rmanfredi \$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic Licence,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic Licence; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: d_ftime.U,v \$

?RCS: Revision 3.0 1993/08/18 12:06:06 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?MAKE:d_ftime d_gettimeod: Inlibc Setvar

?MAKE: -pick add \$@ %<

?S:d_ftime:

?S: This variable conditionally defines the HAS_FTIME symbol, which indicates

?S: that the ftime() routine exists. The ftime() routine is basically

?S: a sub-second accuracy clock.

?S:.

?S:d_gettimeod:

?S: This variable conditionally defines the HAS_GETTIMEOFDAY symbol,
which

?S: indicates that the gettimeofday() system call exists (to obtain a

?S: sub-second accuracy clock). You should probably include <sys/resource.h>.

?S:.

?C:HAS_FTIME (FTIMER):

?C: This symbol, if defined, indicates that the ftime() routine exists.

?C: It is basically a sub-second accuracy clock, but is less accurate

?C: than gettimeofday(2) anyway. The type "Timeval" should be used to

?C: refer to "struct timeb".

?C:.

?C:HAS_GETTIMEOFDAY (GETTIMEOFDAY):

?C: This symbol, if defined, indicates that the gettimeofday() system

?C: call is available for a sub-second accuracy clock. Usually, the file

?C: <sys/resource.h> needs to be included (see I_SYS_RESOURCE).

```

?C: The type "Timeval" should be used to refer to "struct timeval".
?C:.
?H:#$d_ftime HAS_FTIME /**/
?H:#$d_gettimeod HAS_GETTIMEOFDAY /**/
?H:?%<:@if HAS_FTIME
?H:?%<:#ifdef HAS_FTIME
?H:?%<:#define Timeval struct timeb /* Structure used by ftime() */
?H:?%<:#endif
?H:?%<:@end
?H:?%<:@if HAS_GETTIMEOFDAY
?H:?%<:#ifdef HAS_GETTIMEOFDAY
?H:?%<:#define
    Timeval struct timeval /* Structure used by gettimeofday() */
?H:?%<:#endif
?H:?%<:@end
?H:.
?X:FIXME
?X:?I:?d_ftime:i_systimeb
?X:?I:?d_gettimeod:i_sysresrc
?LINT:set d_gettimeod d_ftime
?LINT:known Timeval
: see if gettimeofday or ftime exists
?X:
?X: Give priority to gettimeofday(2) because timing is more accurate
?X:
set gettimeofday d_gettimeod
eval $inlibc
case "$d_gettimeod" in
"$undef")
    set ftime d_ftime
    eval $inlibc
    ;;
*)
    val="$undef"; set d_ftime; eval $setvar
    ;;
esac
case "$d_gettimeod$d_ftime" in
"$undef$undef")
    echo " "
    echo 'No ftime() nor gettimeofday() -- timing may be less accurate.' >&4
    ;;
esac

```

Found in path(s):

```

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/d_ftime.U

```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$
?RCS:
?RCS: Copyright (c) 2001 Jarkko Hietaniemi
?RCS:
?RCS: You may distribute under the terms of either the GNU General Public
?RCS: License or the Artistic License, as specified in the README file.
?RCS:
?MAKE:d_nl_langinfo: Inlibc i_langinfo
?MAKE: -pick add \$@ %<
?S:d_nl_langinfo:
?S: This variable conditionally defines the HAS_NL_LANGINFO symbol, which
?S: indicates to the C program that the nl_langinfo() routine is available.
?S:.
?C:HAS_NL_LANGINFO:
?C: This symbol, if defined, indicates that the nl_langinfo routine is
?C: available to return local data. You will also need <langinfo.h>
?C: and therefore I_LANGINFO.
?C:.
?H:#\$d_nl_langinfo HAS_NL_LANGINFO /**/
?H:.
?LINT:set d_nl_langinfo
?LINT:use i_langinfo
: see if nl_langinfo exists
set nl_langinfo d_nl_langinfo
eval \$inlibc

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_nl_langinfo.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$
?RCS:
?RCS: Copyright (c) 1998 Jarkko Hietaniemi
?RCS:
?RCS: You may distribute under the terms of either the GNU General Public
?RCS: License or the Artistic License, as specified in the README file.
?RCS:
?MAKE:d_eaccess: Inlibc
?MAKE: -pick add \$@ %<
?S:d_eaccess:
?S: This variable conditionally defines the HAS_EACCESS symbol, which
?S: indicates to the C program that the eaccess() routine is available.
?S:.
?C:HAS_EACCESS :
?C: This symbol, if defined, indicates that the eaccess routine is
?C: available to do extended access checks.
?C:.

?H:#\$d_eaccess HAS_EACCESS /**/

?H:.

?LINT:set d_eaccess

: see if eaccess exists

set eaccess d_eaccess

eval \$inlibc

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/acl/d_eaccess.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: i_time.U,v 3.0 1993/08/18 12:08:45 ram Exp \$

?RCS:

?RCS: Copyright (c) 1991-1993, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 3.0.

?RCS:

?RCS: \$Log: i_time.U,v \$

?RCS: Revision 3.0 1993/08/18 12:08:45 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?X:

?X: This unit finds which "time" include to use. If 'timezone' is used by the

?X: program, we also try to find which header should be included. Eventually,

?X: we look for <sys/select.h> if I_SYSSSELECT is used, to get struct timeval.

?X:

?MAKE:i_time i_systime i_systimek timeincl d_tm_tm_zone d_tm_tm_gmtoff: \

Compile cat \

contains rm_try echo n

c +i_sysselect Findhdr Hasfield i_stdlib

?MAKE: -pick add \$@ %<

?S:i_time:

?S: This variable conditionally defines I_TIME, which indicates

?S: to the C program that it should include <time.h>.

?S:.

?S:i_systime:

?S: This variable conditionally defines I_SYS_TIME, which indicates

?S: to the C program that it should include <sys/time.h>.

?S:.

?S:i_systimek:

?S: This variable conditionally defines I_SYS_TIME_KERNEL, which

?S: indicates to the C program that it should include <sys/time.h>

?S: with KERNEL defined.

?S:.

?S:timeincl:

?S: This variable holds the full path of the included time header(s).

?S:.

?S:d_tm_tm_zone:

?S: This variable conditionally defines HAS_TM_TM_ZONE, which indicates

?S: indicates to the C program that the struct tm has the tm_zone field.

?S:.

?S:d_tm_tm_gmtimeoff:

?S: This variable conditionally defines HAS_TM_TM_GMTIMEOFF, which indicates

?S: indicates to the C program that the struct tm has the tm_gmtimeoff field.

?S:.

?C:I_TIME (USE_TIME_H):

?C: This symbol, if defined,

indicates to the C program that it should

?C: include <time.h>.

?C:.

?C:I_SYS_TIME (I_SYSTIME USE_SYS_TIME_H NO_TIME_WITH_SYS_TIME):

?C: This symbol, if defined, indicates to the C program that it should

?C: include <sys/time.h>.

?C:.

?C:I_SYS_TIME_KERNEL (I_SYSTIMEKERNEL):

?C: This symbol, if defined, indicates to the C program that it should

?C: include <sys/time.h> with KERNEL defined.

?C:.

?C:HAS_TM_TM_ZONE:

?C: This symbol, if defined, indicates to the C program that

?C: the struct tm has a tm_zone field.

?C:.

?C:HAS_TM_TM_GMTIMEOFF:

?C: This symbol, if defined, indicates to the C program that

?C: the struct tm has a tm_gmtimeoff field.

?C:.

?H:#\$i_time I_TIME /**/

?H:#\$i_systime I_SYS_TIME /**/

?H:#\$i_systimek I_SYS_TIME_KERNEL /**/

?H:#\$d_tm_tm_zone HAS_TM_TM_ZONE /**/

?H:#\$d_tm_tm_gmtimeoff HAS_TM_TM_GMTIMEOFF /**/

?H:.

?W::timezone

?T:xselect flags sysselect s_timeval s_timezone

?LINT:change i_sysselect

?LINT:set d_tm_tm_zone

?LINT:set d_tm_tm_gmtimeoff

: see if we should include time.h,

sys/time.h, or both

echo " "

if test "X\$timeincl" = X; then

```

echo "Testing to see if we should include <time.h>, <sys/time.h> or both." >&4
$echo $n "I'm now running the test program...$c"
$cat >try.c <<EOCP
#include <sys/types.h>
#ifdef I_TIME
#include <time.h>
#endif
#ifdef I_SYSTIME
#ifdef SYSTIMEKERNEL
#define KERNEL
#endif
#include <sys/time.h>
#endif
#ifdef I_SYSSELECT
#include <sys/select.h>
#endif
#ifdef I_STDLIB
#include <stdlib.h>
#endif
int main()
{
    struct tm foo;
#ifdef S_TIMEVAL
    struct timeval bar;
#endif
#ifdef S_TIMEZONE
    struct timezone tzp;
#endif
    if (foo.tm_sec == foo.tm_sec)
        exit(0);
#ifdef S_TIMEVAL
    if (bar.tv_sec == bar.tv_sec)
        exit(0);
#endif
    exit(1);
}
EOCP
flags="
@if I_SYSSELECT
if $contains 'timeval.*{`./findhdr sys/select.h` >/dev/null 2>&1; then
xselect='-DI_SYSSELECT'
else
xselect="
fi
@end
@if timezone
for s_timezone in '-DS_TIMEZONE' "; do

```

```

@else
s_timezone=""
@end
?X: Every package is given a try with 'struct
timeval'
@if I_SYSSELECT
for sysselect in $xselect "; do
@else
sysselect=""
@end
for s_timeval in '-DS_TIMEVAL' "; do
for i_systimek in "'-DSYSTIMEKERNEL'; do
for i_time in "'-DI_TIME'; do
for i_systime in '-DI_SYSTIME' "; do
case "$flags" in
") $echo $n ".$c"
set try $i_time $i_systime $i_systimek $sysselect $s_timeval $s_timezone
if eval $compile; then
set X $i_time $i_systime $i_systimek $sysselect $s_timeval
shift
flags="$*"
echo " "
$echo $n "Succeeded with $flags$c"
fi
;;
esac
done
done
done
done
done
@if I_SYSSELECT
done
@end
@if timezone
done
@end
timeincl=""
echo " "
case "$flags" in
*SYSTIMEKERNEL*) i_systimek="$define"
timeincl=`./findhdr sys/time.h`
echo "We'll include <sys/time.h> with KERNEL defined." >&4;;
*) i_systimek="$undef";;
esac
case "$flags" in
*I_TIME*) i_time="$define"
timeincl=`./findhdr time.h` "$timeincl"
echo "We'll include <time.h>." >&4;;

```

```

*) i_time="$undef";;
esac
case "$flags" in
*_I_SYSTIME*)
i_systime="$define"
timeincl=`./findhdr sys/time.h` $timeincl"
echo "We'll include <sys/time.h>." >&4;;
*) i_systime="$undef";;
esac
@if I_SYSSSELECT
case "$flags" in
*_I_SYSSSELECT*) i_syssselct="$define"
timeincl=`./findhdr sys/select.h` $timeincl"
echo "We'll also include <sys/select.h> to get struct timeval." >&4;;
*) case "$i_syssselct" in
") i_syssselct="$undef";;
esac
esac
@end
$rm_try
fi
: see if struct tm knows about tm_zone
case "$i_systime$i_time" in
*$define*)
echo " "
echo "Checking to see if your struct tm has tm_zone field..." >&4
set d_tm_tm_zone tm tm_zone $i_systime sys/time.h $i_time time.h
eval $hasfield
;;
*) val="$undef"
set d_tm_tm_zone
eval $setvar
;;
esac
case "$d_tm_tm_zone" in
"$define") echo "Yes, it does." ;;
*) echo "No, it doesn't." ;;
esac
: see if struct tm knows about tm_gmtoff
case "$i_systime$i_time" in
*$define*)
echo " "

echo "Checking to see if your struct tm has tm_gmtoff field..." >&4
set d_tm_tm_gmtoff tm tm_gmtoff $i_systime sys/time.h $i_time time.h
eval $hasfield
;;
*) val="$undef"

```

```

    set d_tm_tm_gmtoff
    eval $setvar
    ;;
esac
case "$d_tm_tm_gmtoff" in
"$define")    echo "Yes, it does." ;;
*)           echo "No, it doesn't." ;;
esac

```

Found in path(s):

```

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/compline/i_time.U

```

No license file was found, but licenses were detected in source scan.

```

?RCS: $Id: i_vfork.U 1 2006-08-24 12:32:52Z rmanfredi $
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: $Log: i_vfork.U,v $
?RCS: Revision 3.0.1.1 1994/05/06 15:05:44 ram
?RCS: patch23: avoid inclusion of <vfork.h> if no vfork() used (ADO)
?RCS:
?RCS: Revision 3.0 1993/08/18 12:08:50 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:i_vfork: Inhdr d_vfork
?MAKE: -pick add $@ %<
?S:i_vfork:
?S: This variable conditionally defines the I_VFORK symbol, and indicates
?S: whether a C program should include vfork.h.
?S:.
?C:I_VFORK:
?C: This symbol,
    if defined, indicates to the C program that it should
?C: include vfork.h.
?C:.
?H:#$i_vfork I_VFORK /**/
?H:.
: see if this is a vfork system
case "$d_vfork" in
"$define")
    set vfork.h i_vfork

```

```
eval $inhdr
;;
*)
i_vfork="$undef"
;;
esac
```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/i_vfork.U
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: newslib.U 1 2006-08-24 12:32:52Z rmanfredi \$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic Licence,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic Licence; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: newslib.U,v \$

?RCS: Revision 3.0 1993/08/18 12:09:23 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?MAKE:newslib newslibexp: test inews Oldconfig Getfile

?MAKE: -pick add \$@ %<

?S:newslib:

?S: This variable contains the eventual value of the NEWSLIB symbol,

?S: which holds the name of the directory serving as the news library.

?S: It may have a ~ on the front. See newslibexp for expanded version.

?S:.

?S:newslibexp:

?S: This variable contains

the ~ expanded name of the news library

?S: directory. See newslib.

?S:.

?C:NEWSLIB:

?C: This symbol contains the name of the directory serving as the news

?C: library. The program must be prepared to do ~ expansion on it.

?C:.

?C:NEWSLIB_EXP:

?C: This symbol is the ~ expanded version of NEWSLIB, for programs that

?C: do not wish to deal with it at run-time.

?C:.

?H:#define NEWSLIB "\$newslib" /**/

?H:#define NEWSLIB_EXP "\$newslibexp" /**/

```

?H:
?LINT:change inews
: figure out news library
case "$newslib" in
")
dflt=/usr/lib/news
;;
*) dflt=$newslib ;;
esac
echo " "
fn=d~
rp="Where is your news library?"
./getfile
newslib="$ans"
newslibexp="$ansexp"
if $test -f $newslibexp/inews; then
echo "Aha! Inews is really in $newslibexp! Maybe this is 2.10.2..." >&4
case "$inews" in
inews)
: null
;;
*) echo "(Make sure $inews isn't an old version.)";;
esac
inews=$newslibexp/inews
fi

```

Found in path(s):

```

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/newslib.U

```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: patchlevel.U,v \$

?RCS: Revision 3.0.1.1 1997/02/28 16:18:41 ram

?RCS: patch61: added support for src.U

?RCS:

?RCS: Revision 3.0 1993/08/18 12:09:31 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

```
?MAKE:patchlevel: package baserev test rsrc
?MAKE: -pick add $@ %<
?T:Revision
?S:patchlevel:
?S: The patchlevel level of this package.
?S: The value of patchlevel comes from the patchlevel.h file.
?S:.
: get the patchlevel
echo " "
echo "Getting the current patchlevel..." >&4
if $test -r
  $rsrc/patchlevel.h;then
  patchlevel=`awk \
    '/^#[ ]*define[ ][*]PATCHLEVEL/ {print $3}' \
    < $rsrc/patchlevel.h`
else
  patchlevel=0
fi
echo "(You have $package $baserev PL$patchlevel.)"
```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/patchlevel.U
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1999, Jarkko Hietaniemi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 3.0.

?RCS:

?MAKE:d_clock_settime: Inlibc

?MAKE: -pick add \$@ %<

?S:d_clock_settime:

?S: This variable conditionally defines HAS_CLOCK_SETTIME

?S: if clock_settime() is available to set the time of a POSIX clock.

?S:.

?C:HAS_CLOCK_SETTIME:

?C: This symbol, if defined, indicates that the clock_settime

?C: system call is available to set the time of a POSIX clock.

?C:.

?H:#\$d_clock_settime HAS_CLOCK_SETTIME /**/

?H:.

?LINT:set d_clock_settime

```
: see if clock_gettime exists
set clock_gettime d_clock_gettime
eval $inlibc
```

Found in path(s):

*

```
/opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/perl/d_clock_gettime.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: i_semaphore.U,v $
```

```
?RCS:
```

```
?RCS: Copyright (c) 1999 Jarkko Hietaniemi
```

```
?RCS:
```

```
?RCS: You may distribute under the terms of either the GNU General Public
```

```
?RCS: License or the Artistic License, as specified in the README file.
```

```
?RCS:
```

```
?MAKE:i_semaphore: Inhdr Hasfield
```

```
?MAKE: -pick add $@ %<
```

```
?S:i_semaphore:
```

```
?S: This variable conditionally defines the I_SEMAPHORE symbol, and indicates
```

```
?S: whether a C program should include <semaphore.h>.
```

```
?S:.
```

```
?C:I_SEMAPHORE:
```

```
?C: This symbol, if defined, indicates that <semaphore.h> exists and
```

```
?C: should be included.
```

```
?C:.
```

```
?H:#$i_semaphore I_SEMAPHORE /**/
```

```
?H:.
```

```
?LINT:set i_semaphore
```

```
: see if this is a semaphore.h system
```

```
set semaphore.h i_semaphore
```

```
eval $inhdr
```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/perl/i_semaphore.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: cppstdin.U 1 2006-08-24 12:32:52Z rmanfredi $
```

```
?RCS:
```

```
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
```

```
?RCS:
```

```
?RCS: You may redistribute only under the terms of the Artistic License,
```

```
?RCS: as specified in the README file that comes with the distribution.
```

```
?RCS: You may reuse parts of this distribution only within the terms of
```

```
?RCS: that same Artistic License; a copy of which may be found at the root
```

```
?RCS: of the source tree for dist 4.0.
```

?RCS:
?RCS: \$Log: cppstdin.U,v \$
?RCS: Revision 3.0.1.4 1994/10/29 16:08:34 ram
?RCS: patch36: added ?F: line for metalint file checking
?RCS:
?RCS: Revision 3.0.1.3 1994/01/24 14:05:38 ram
?RCS: patch16: comment for CPPLAST was missing
?RCS:
?RCS: Revision 3.0.1.2 1993/12/15 08:18:58 ram
?RCS: patch15: new variables cprun and cpplast, guaranteed wrapper-free
?RCS: patch15: cppstdin now tries to use cc, even at the cost of a wrapper
?RCS:
?RCS: Revision 3.0.1.1
1993/08/25 14:00:53 ram
?RCS: patch6: remove wrapper when not actually used
?RCS:
?RCS: Revision 3.0 1993/08/18 12:05:38 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:cppstdin cppminus cprun cpplast: contains test \
Myread Oldconfig Loc cpp +cc rm hint osname gccversion
?MAKE: -pick add \$@ %<
?S:cppstdin:
?S: This variable contains the command which will invoke the C
?S: preprocessor on standard input and put the output to stdout.
?S: It is primarily used by other Configure units that ask about
?S: preprocessor symbols.
?S:.
?S:cppminus:
?S: This variable contains the second part of the string which will invoke
?S: the C preprocessor on the standard input and produce to standard
?S: output. This variable will have the value "-" if cppstdin needs
?S: a minus to specify standard input, otherwise the value is "".
?S:.
?S:cprun:
?S: This variable contains the command which will invoke a C preprocessor
?S: on standard input and put the output to stdout. It is guaranteed
not
?S: to be a wrapper and may be a null string if no preprocessor can be
?S: made directly available. This preprocessor might be different from the
?S: one used by the C compiler. Don't forget to append cpplast after the
?S: preprocessor options.
?S:.
?S:cpplast:
?S: This variable has the same functionality as cppminus, only it applies
?S: to cprun and not cppstdin.
?S:.
?C:CPPSTDIN:

?C: This symbol contains the first part of the string which will invoke
?C: the C preprocessor on the standard input and produce to standard
?C: output. Typical value of "cc -E" or "/lib/cpp", but it can also
?C: call a wrapper. See CPPRUN.
?C:.
?C:CPPMINUS:
?C: This symbol contains the second part of the string which will invoke
?C: the C preprocessor on the standard input and produce to standard
?C: output. This symbol will have the value "-" if CPPSTDIN needs a minus
?C: to specify standard input, otherwise the value is "".
?C:.
?C:CPPRUN:
?C: This symbol contains the string which will invoke
a C preprocessor on
?C: the standard input and produce to standard output. It needs to end
?C: with CPPLAST, after all other preprocessor flags have been specified.
?C: The main difference with CPPSTDIN is that this program will never be a
?C: pointer to a shell wrapper, i.e. it will be empty if no preprocessor is
?C: available directly to the user. Note that it may well be different from
?C: the preprocessor used to compile the C program.
?C:.
?C:CPPLAST:
?C: This symbol is intended to be used along with CPPRUN in the same manner
?C: symbol CPPMINUS is used with CPPSTDIN. It contains either "-" or "".
?C:.
?H:#define CPPSTDIN "\$cppstdin"
?H:#define CPPMINUS "\$cppminus"
?H:#define CPPRUN "\$cpprun"
?H:#define CPPLAST "\$cpplast"
?H:.
?F:cppstdin !testcpp.out !testcpp.c
?T:wrapper x_cpp x_minus ok
?LINT:extern cppflags
: see how we invoke the C preprocessor
echo " "
echo "Now, how can we feed standard input to your C preprocessor..." >&4
cat <<'EOT' >testcpp.c
#define ABC abc
#define
XYZ xyz
ABC.XYZ
EOT
cd ..
if test ! -f cppstdin; then
if test "X\$osname" = "Xaix" -a "X\$gccversion" = X; then
AIX cc -E doesn't show the absolute headerfile
locations but we'll cheat by using the -M flag.
echo 'cat >.\$\$.c; rm -f .\$\$.u; ""\$cc" "\${1+"\$@"} -M -c .\$\$.c 2>/dev/null; test -s .\$\$.u && awk ""\$2 ~ /\.h\$/ { print

```

"# 0 \\"$2\" } "" .$.u; rm -f .$.o .$.u; ""$cc" -E ${1+"$@"} .$.c; rm .$.c' > cppstdin
else
  echo 'cat >.$$.c; ""$cc $cppflags" -E ${1+"$@"} .$.c; rm .$.c' >cppstdin
fi
else
  echo "Keeping your $hint cppstdin wrapper."
fi
chmod 755 cppstdin
wrapper=`pwd`/cppstdin
ok='false'
cd UU

?X:
?X: We'll run the cpp tests again if we don't have any valid C preprocessor
?X: yet or don't know how to proceed without a wrapper (in which case cprun
?X: is empty and that's really annoying...)
?X:
if $test "X$cppstdin" != "X" && \
  $cppstdin $cppminus <testcpp.c >testcpp.out 2>&1 && \
  $contains 'abc.*xyz' testcpp.out >/dev/null 2>&1
then
  echo "You used
  to use $cppstdin $cppminus so we'll use that again."
  case "$cprun" in
  ") echo "But let's see if we can live without a wrapper..." ;;
  *)
  if $cprun $cpplast <testcpp.c >testcpp.out 2>&1 && \
    $contains 'abc.*xyz' testcpp.out >/dev/null 2>&1
  then
    echo "(And we'll use $cprun $cpplast to preprocess directly.)"
    ok='true'
  else
    echo "(However, $cprun $cpplast does not work, let's see...)"
  fi
  ;;
  esac
else
  case "$cppstdin" in
  ") ;;
  *)
  echo "Good old $cppstdin $cppminus does not seem to be of any help..."
  ;;
  esac
fi

if $ok; then
  : nothing
elif echo 'Maybe ""$cc" -E" will work...'; \

```

```

$cc -E <testcpp.c >testcpp.out 2>&1; \
$contains 'abc.*xyz' testcpp.out >/dev/null 2>&1 ; then
echo "Yup, it does."
x_cpp="$cc $cppflags -E"
x_minus="";
elif echo 'Nope...maybe ""$cc"" -E -" will work...'; \
$cc -E - <testcpp.c >testcpp.out 2>&1; \
$contains 'abc.*xyz' testcpp.out >/dev/null 2>&1 ; then
echo "Yup, it does."
x_cpp="$cc $cppflags -E"
x_minus='-';
elif
echo 'Nope...maybe ""$cc"" -P" will work...'; \
$cc -P <testcpp.c >testcpp.out 2>&1; \
$contains 'abc.*xyz' testcpp.out >/dev/null 2>&1 ; then
echo "Yipee, that works!"
x_cpp="$cc $cppflags -P"
x_minus="";
elif echo 'Nope...maybe ""$cc"" -P -" will work...'; \
$cc -P - <testcpp.c >testcpp.out 2>&1; \
$contains 'abc.*xyz' testcpp.out >/dev/null 2>&1 ; then
echo "At long last!"
x_cpp="$cc $cppflags -P"
x_minus='-';
elif echo 'No such luck, maybe "$cpp" will work...'; \
$cpp <testcpp.c >testcpp.out 2>&1; \
$contains 'abc.*xyz' testcpp.out >/dev/null 2>&1 ; then
echo "It works!"
x_cpp="$cpp $cppflags"
x_minus="";
elif echo 'Nixed again...maybe "$cpp" -" will work...'; \
$cpp - <testcpp.c >testcpp.out 2>&1; \
$contains 'abc.*xyz' testcpp.out >/dev/null 2>&1 ; then
echo "Hooray, it works! I was beginning to wonder."
x_cpp="$cpp $cppflags"
x_minus='-';
elif echo 'Uh-uh. Time to get fancy. Trying a wrapper...'; \
$wrapper <testcpp.c >testcpp.out 2>&1; \
$contains
'abc.*xyz' testcpp.out >/dev/null 2>&1 ; then
x_cpp="$wrapper"
x_minus=""
echo "Eureka!"
else
dflt=""
rp="No dice. I can't find a C preprocessor. Name one:"
./myread
x_cpp="$ans"

```

```

x_minus="
$x_cpp <testcpp.c >testcpp.out 2>&1
if $contains 'abc.*xyz' testcpp.out >/dev/null 2>&1 ; then
  echo "OK, that will do." >&4
else
  echo "Sorry, I can't get that to work. Go find one and rerun Configure." >&4
  exit 1
fi
fi

case "$ok" in
false)
  cppstdin="$x_cpp"
  cppminus="$x_minus"
  cpprun="$x_cpp"
  cpplast="$x_minus"
  ?X:
  ?X: If /lib/cpp is used, try using a wrapper to increase our chances to have
  ?X: the C compiler and our $cppstdin agree on the same symbols... However,
  ?X: since cpprun is guaranteed not to be a wrapper, we must clear it if the
  ?X: only preprocessor we found was a wrapper, with all our luck...
  ?X:
  set X $x_cpp
  shift
  case "$1" in
"$cpp")
  echo "Perhaps can we force $cc -E using a wrapper..."
  if $wrapper <testcpp.c >testcpp.out 2>&1; \
  $contains 'abc.*xyz'
testcpp.out >/dev/null 2>&1
  then
    echo "Yup, we can."
    cppstdin="$wrapper"
    cppminus="";
  else
    echo "Nope, we'll have to live without it..."
  fi
  ;;
esac
case "$cpprun" in
"$wrapper")
  cpprun="
  cpplast="
  ;;
esac
;;
esac

```

```
case "$cppstdin" in
"$wrapper"|'cppstdin') ;;
*) $rm -f $wrapper;;
esac
$rm -f testcpp.c testcpp.out
```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/modified/cppstdin.U
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: d_time.U,v \$

?RCS: Revision 3.0.1.2 1995/07/25 14:07:43 ram

?RCS: patch56: typo fix, sytem -> system

?RCS:

?RCS: Revision 3.0.1.1 1994/10/29 16:16:38 ram

?RCS: patch36: now uses new Typedef unit to compute type information (ADO)

?RCS:

?RCS: Revision 3.0 1993/08/18 12:07:45 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?X: Maybe <sys/types.h> should be included?

?X:INC: i_systypes

?MAKE:d_time timetype: Csym Setvar Findhdr Myread Typedef

?MAKE: -pick add \$@ %<

?S:d_time:

?S: This

variable conditionally defines the HAS_TIME symbol, which indicates

?S: that the time() routine exists. The time() routine is normally

?S: provided on UNIX systems.

?S:.

?S:timetype:

?S: This variable holds the type returned by time(). It can be long,

?S: or time_t on BSD sites (in which case <sys/types.h> should be

?S: included). Anyway, the type Time_t should be used.

?S:.

?C:HAS_TIME (TIMER):

?C: This symbol, if defined, indicates that the time() routine exists.

```

?C:.
?C:Time_t (TIMETYPE):
?C: This symbol holds the type returned by time(). It can be long,
?C: or time_t on BSD sites (in which case <sys/types.h> should be
?C: included).
?C:.
?H:#$d_time HAS_TIME /**/
?H:#define Time_t $timetype /* Time type */
?H:.
?LINT:set d_time
: see if time exists
echo " "
if set time val -f d_time; eval $csym; $val; then
echo 'time() found.' >&4
val="$define"
set time_t timetype long stdio.h sys/types.h
eval $typedef
dflt="$timetype"
echo " "
rp="What type is returned by time() on this
system?"
./myread
timetype="$ans"
else
echo 'time() not found, hope that will do.' >&4
val="$undef"
timetype='int';
fi
set d_time
eval $setvar

```

Found in path(s):

```

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/d_time.U

```

No license file was found, but licenses were detected in source scan.

```

?RCS: $Id: lseektype.U,v 3.0.1.1 1994/08/29 16:30:10 ram Exp $
?RCS:
?RCS: Copyright (c) 1991-1993, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 3.0.
?RCS:
?RCS: $Log: lseektype.U,v $
?RCS: Revision 3.0.1.1 1994/08/29 16:30:10 ram

```

```

?RCS: patch32: now uses new Typedef unit to compute type information
?RCS:
?RCS: Revision 3.0 1993/08/18 12:09:08 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:lseektype lseeksize: Myread Typedef cat Compile rm_try longsize run
?MAKE: -pick add $@ %<
?S:lseektype:
?S: This variable defines lseektype to be something like off_t, long,
?S: or whatever type is used to declare
lseek offset's type in the
?S: kernel (which also appears to be lseek's return type).
?S:.
?S:lseeksize:
?S: This variable defines lseeksize to be something like off_t, long,
?S: or whatever type is used to declare lseek offset's type in the
?S: kernel (which also appears to be lseek's return type).
?S:.
?C:Off_t (LSEEKTYPE):
?C: This symbol holds the type used to declare offsets in the kernel.
?C: It can be int, long, off_t, etc... It may be necessary to include
?C: <sys/types.h> to get any typedef'ed information.
?C:.
?C:LSEEKSIZE:
?C: This symbol holds the number of bytes used by the Off_t.
?C:.
?C:Off_t_size:
?C: This symbol holds the number of bytes used by the Off_t.
?C:.
?H:#define Off_t $lseektype /* <offset> type */
?H:#define LSEEKSIZE $lseeksize /* <offset> size */
?H:#define Off_t_size $lseeksize /* <offset> size */
?H:.
?F:!try
?LINT:set lseektype
: see what type lseek is declared as in the kernel
rp="What is the type used for lseek's offset on this system?"
set off_t lseektype
long stdio.h sys/types.h
eval $typedef_ask

echo " "
echo "Checking to see how big your file offsets are..." >&4
$cat >try.c <<EOCP
#include <sys/types.h>
#include <stdio.h>
int main()
{

```

```

    printf("%d\n", (int)sizeof($lseektype));
    return(0);
}
EOCP
set try
if eval $compile_ok; then
    lseeksize=`$run ./try`
    echo "Your file offsets are $lseeksize bytes long."
else
    dflt=$longsize
    echo " "
    echo "(I can't seem to compile the test program. Guessing...)"
    rp="What is the size of your file offsets (in bytes)?"
    ./myread
    lseeksize="$ans"
fi
$rm_try

```

Found in path(s):

```

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/typedefs/lseektype.U

```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1999, Jarkko Hietaniemi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 3.0.

?RCS:

?MAKE:fflushNULL fflushall: Compile cat rm rm_try test osname run to from \

Oldconfig Myread Setvar echo targethost \

d_sysconf i_unistd d_stdio_stream_array stdio_stream_array i_stdlib

?MAKE: -pick add \$@ %<

?S:fflushNULL:

?S: This symbol, if defined, tells that fflush(NULL) correctly

?S: flushes all pending stdio output without side effects. In

?S: particular, on some platforms calling fflush(NULL) *still*

?S: corrupts STDIN if it is a pipe.

?S:.

?S:fflushall:

?S: This symbol, if defined, tells that to flush

?S: all

pending stdio output one must loop through all

?S: the stdio file handles stored in an array and fflush them.

?S: Note that if fflushNULL is defined, fflushall will not
 ?S: even be probed for and will be left undefined.
 ?S:.
 ?C:FFLUSH_NULL:
 ?C: This symbol, if defined, tells that fflush(NULL) correctly
 ?C: flushes all pending stdio output without side effects. In
 ?C: particular, on some platforms calling fflush(NULL) *still*
 ?C: corrupts STDIN if it is a pipe.
 ?C:.
 ?C:FFLUSH_ALL:
 ?C: This symbol, if defined, tells that to flush
 ?C: all pending stdio output one must loop through all
 ?C: the stdio file handles stored in an array and fflush them.
 ?C: Note that if fflushNULL is defined, fflushall will not
 ?C: even be probed for and will be left undefined.
 ?C:.
 ?H:#\$fflushNULL FFLUSH_NULL /**/
 ?H:#\$fflushall FFLUSH_ALL /**/
 ?H:.
 ?T:output code
 ?F:!try.out !try !tryp
 : Check how to flush
 echo " "
 \$cat >&4 <<EOM
 Checking how to flush all pending stdio output...
 EOM
 # I only know how to find
 the first 32 possibly open files on SunOS.
 # See also hints/sunos_4_1.sh and util.c --AD
 case "\$osname" in
 sunos) \$echo '#define PERL_FFLUSH_ALL_FOPEN_MAX 32' > try.c ;;
 esac
 \$cat >>try.c <<EOCP
 #include <stdio.h>
 #ifdef I_STDLIB
 #include <stdlib.h>
 #endif
 #ifdef I_UNISTD
 #include <unistd.h>
 #endif
 #ifdef HAS_SYSCONF
 #define STDIO_STREAM_ARRAY \$stdio_stream_array
 #endif
 int main() {

```

FILE* p;
unlink("try.out");
p = fopen("try.out", "w");
#ifdef TRY_FPUTC
    fputc('x', p);
#else
# ifdef TRY_FPRINTF
    fprintf(p, "x");
# endif
#endif
#ifdef TRY_FFLUSH_NULL
    fflush(NULL);
#endif
#ifdef TRY_FFLUSH_ALL
    {
        long open_max = -1;
# ifdef PERL_FFLUSH_ALL_FOPEN_MAX
        open_max = PERL_FFLUSH_ALL_FOPEN_MAX;
# else
# if defined(HAS_SYSCONF) && defined(_SC_OPEN_MAX)
        open_max = sysconf(_SC_OPEN_MAX);
# else
#  ifdef FOPEN_MAX
        open_max = FOPEN_MAX;
#  else
#   ifdef OPEN_MAX
        open_max = OPEN_MAX;
#   else
#    ifdef _NFILE
        open_max = _NFILE;
#    endif
#   endif
#  endif
# endif
# endif
# endif
# endif
# ifdef HAS_STDIO_STREAM_ARRAY
    if (open_max > 0) {
        long i;
        for (i = 0; i < open_max; i++)
            if (STDIO_STREAM_ARRAY[i]._file >= 0 &&
                STDIO_STREAM_ARRAY[i]._file < open_max &&
                STDIO_STREAM_ARRAY[i]._flag)
                fflush(&STDIO_STREAM_ARRAY[i]);
    }
}
# endif
#endif

```

```

_exit(42);
}
EOCP
: first we have to find out how _not_ to flush
$to try.c
if $test "X$fflushNULL" = X -o "X$fflushall" = X; then
  output="
  set try -DTRY_FPUTC
  if eval $compile; then
    $run ./try 2>/dev/null
    code="$?"
    $from try.out
    if $test ! -s try.out -a "X$code" = X42; then
output=-DTRY_FPUTC
    fi
  fi
  case "$output" in
  ")
    set try -DTRY_FPRINTF
    if eval $compile; then
      $run ./try 2>/dev/null
      code="$?"
      $from try.out
      if $test ! -s try.out -a "X$code" = X42; then
output=-DTRY_FPRINTF
    fi
  fi
  ;;
  esac
fi
: check for fflush NULL behavior
case "$fflushNULL" in
") set try -DTRY_FFLUSH_NULL $output
if eval $compile; then
  $run ./try 2>/dev/null
  code="$?"
  $from try.out
  if $test -s try.out -a "X$code" = X42; then
    fflushNULL="$cat try.out`"
  else
    if $test "X$code" != X42; then
      $cat >&4 <<EOM
(If this test failed, don't worry, we'll try another method shortly.)
EOM
  fi
fi
fi

```

```
$rm -f core.try.core.core.try.*
```

```
case "$fflushNULL" in
```

```
x) $cat >&4 <<EOM
```

Your fflush(NULL) works okay for output streams.

Let's see if it clobbers input pipes...

```
EOM
```

```
# As of mid-March 2000 all versions of Solaris appear to have a stdio
```

```
# bug that improperly flushes the input end of pipes. So we avoid the
```

```
# autoflush on fork/system/exec support for now. :-(
```

```
$cat >tryp.c <<EOCP
```

```
#include <stdio.h>
```

```
int
```

```
main(int argc, char **argv)
```

```
{
```

```
    char buf[1024];
```

```
    int i;
```

```
    char *bp = buf;
```

```
    while (1) {
```

```
while ((i = getc(stdin)) != -1
```

```
    && (*bp++ = i) != '\n'
```

```
    && bp < &buf[1024])
```

```
/* DO NOTHING */;
```

```
*bp = '\0';
```

```
fprintf(stdout, "%s", buf);
```

```
fflush(NULL);
```

```
if (i == -1)
```

```
    return 0;
```

```
bp = buf;
```

```
}
```

```
}
```

```
EOCP
```

```
fflushNULL="$define"
```

```
set tryp
```

```
if eval $compile; then
```

```
    $rm -f tryp.out
```

```
    # Copy the .c file to the remote host ($to is an ssh-alike if targethost is set)
```

```
    if $test "X$targethost" != X; then
```

```
    $to tryp.c
```

```
    $to tryp
```

```
$run "cat tryp.c | ./tryp " 2>/dev/null > tryp.out
```

```
    else
```

```
$cat tryp.c | $run ./tryp 2>/dev/null > tryp.out
```

```
    fi
```

```
    if cmp tryp.c tryp.out >/dev/null 2>&1; then
```

```
        $cat >&4 <<EOM
```

fflush(NULL) seems to behave okay with input streams.

```
EOM
```

```
fflushNULL="$define"
else
$cat >&4 <<EOM
Ouch, fflush(NULL) clobbers input pipes! We will not use it.
EOM
```

```
fflushNULL="$undef"
fi
fi
$rm -f core tryp.c tryp.core core.tryp.*
;;
") $cat >&4 <<EOM
Your fflush(NULL) isn't working (contrary to ANSI C).
EOM
```

```
fflushNULL="$undef"
;;
*) $cat >&4 <<EOM
Cannot figure out whether
your fflush(NULL) works or not.
I'm assuming it doesn't (contrary to ANSI C).
EOM
```

```
fflushNULL="$undef"
;;
esac
;;
$define|true|[yY]*)
fflushNULL="$define"
;;
*)
fflushNULL="$undef"
;;
esac
: check explicit looping only if NULL did not work, and if the pipe
: bug does not show up on an explicit flush too
case "$fflushNULL" in
"$undef")
$cat >tryp.c <<EOCP
#include <stdio.h>
int
main(int argc, char **argv)
{
char buf[1024];
int i;
char *bp = buf;
while (1) {
while ((i = getc(stdin)) != -1
&& (*bp++ = i) != '\n'
&& bp < &buf[1024])
/* DO NOTHING */ ;
```

```

*bp = '\0';
fprintf(stdout, "%s", buf);
fflush(stdin);
if (i == -1)
    return 0;
bp = buf;
}
}
EOCP
set tryp
if eval $compile; then
    $rm -f tryp.out
    if $test "X$targethost" != X; then
        $to tryp.c
        $to tryp
        $run "cat tryp.c | ./tryp " 2>/dev/null > tryp.out
        else
        $cat tryp.c | $run ./tryp 2>/dev/null > tryp.out
        fi
        if cmp tryp.c tryp.out >/dev/null 2>&1;
        then
            $cat >&4 <<EOM

```

Good, at least fflush(stdin) seems to behave okay when stdin is a pipe.

EOM

```

: now check for fflushall behaviour
case "$fflushall" in
") set try -DTRY_FFLUSH_ALL $output
if eval $compile; then
    $cat >&4 <<EOM

```

(Now testing the other method--but note that this also may fail.)

EOM

```

    $run ./try 2>/dev/null
    code=$?
    $from try.out
    if $test -s try.out -a "X$code" = X42; then
        fflushall="$cat try.out`"
    fi
fi
$rm_try
case "$fflushall" in
x) $cat >&4 <<EOM

```

Whew. Flushing explicitly all the stdio streams works.

EOM

```

    fflushall="$define"
;;
") $cat >&4 <<EOM

```

Sigh. Flushing explicitly all the stdio streams doesn't work.

EOM

```
fflushall="$undef"
```

```
::
```

```
*) $cat >&4 <<EOM
```

Cannot figure out whether flushing stdio streams explicitly works or not.

I'm assuming it doesn't.

```
EOM
```

```
fflushall="$undef"
```

```
::
```

```
esac
```

```
::
```

```
"$define"|true[[yY]*)
```

```
fflushall="$define"
```

```
::
```

```
*)
```

```
fflushall="$undef"
```

```
::
```

```
esac
```

```
else
```

```
$cat >&4 <<EOM
```

All is futile. Even fflush(stdin) clobbers input pipes!

```
EOM
```

```
fflushall="$undef"
```

```
fi
```

```
else
```

```
fflushall="$undef"
```

```
fi
```

```
$rm -f core tryp.c tryp.core core.tryp.*
```

```
::
```

```
*) fflushall="$undef"
```

```
::
```

```
esac
```

```
case "$fflushNULL$fflushall" in
```

```
undefundef)
```

```
$cat <<EOM
```

OK, I give up. I cannot figure out how to flush pending stdio output.

We won't be flushing handles at all before fork/exec/popen.

```
EOM
```

```
::
```

```
esac
```

```
$rm_try tryp
```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/fflushall.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id$
?RCS:
?RCS: Copyright (c) 1999, Jarkko Hietaniemi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 3.0.
?RCS:
?MAKE:d_mq_send: Inlibc
?MAKE: -pick add $@ %<
?S:d_mq_send:
?S: This variable conditionally defines HAS_MQ_SEND if mq_send() is
?S: available to send a message to a POSIX message queue.
?S:.
?C:HAS_MQ_SEND:
?C: This symbol, if defined, indicates that the mq_send system call is
?C: available to send a message to a POSIX message queue.
?C:.
?H:#$d_mq_send HAS_MQ_SEND /**/
?H:.
?LINT:set d_mq_send
: see if mq_send exists
set mq_send d_mq_send
eval $inlibc
```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/perl/d_mq_send.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: cppfilecom.U 1 2006-08-24 12:32:52Z rmanfredi $
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: Original Author: Graham Stoney <greyham@research.canon.oz.au>
?RCS:
?RCS: $Log: cppfilecom.U,v $
?RCS: Revision 3.0 1993/08/18 12:05:37 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
```

```

?MAKE:cppfilecom cppstdinflags d_cppignhdrs d_cppcanstdin: \
contains package test Myread Oldconfig Loc Setvar cpp cc cat rm
?MAKE: -pick add $@ %<
?S:cppfilecom:
?S: This variable contains the first part of the string which will invoke
?S: the C preprocessor a file
and produce to standard output, preserving
?S: comments. Typical value of "cc -E -C" or "/lib/cpp -C".
?S:.
?S:cppstdinflags:
?S: This variable contains any flags necessary to get cppfilecom to read
?S: from the standard input.
?S:.
?S:d_cppignhdrs:
?S: This symbol conditionally defines CPP_IGN_HDRS if CPP_FILE_COM ignores
?S: *.h files.
?S:.
?S:d_cppcanstdin:
?S: This symbol conditionally defines CPP_CAN_STDIN if CPP_FILE_COM can
?S: read standard input directly.
?S:.
?C:CPP_FILE_COM (CPPFILECOM):
?C: This symbol contains the first part of the string which will invoke
?C: the C preprocessor a file and produce to standard output, preserving
?C: comments. Typical value of "cc -E -C" or "/lib/cpp -C".
?C:.
?C:CPP_STDIN_FLAGS (CPPSTDINFLAGS):
?C: This variable contains any flags necessary to get CPP_FILE_COM to
?C: read from the standard input.
?C:.
?C:CPP_IGN_HDRS (CPPIGNHDRS):
?C: This symbol is defined if CPP_FILE_COM ignores *.h files.
?C:.
?C:CPP_CAN_STDIN (CPPCANSTDIN):
?C: This
symbol is defined if CPP_FILE_COM can read standard input
?C: directly.
?C:.
?H:#define CPP_FILE_COM "$cppfilecom"
?H:#define CPP_STDIN_FLAGS "$cppstdinflags"
?H:#$d_cppignhdrs CPP_IGN_HDRS /* does CPP ignore .h files? */
?H:#$d_cppcanstdin CPP_CAN_STDIN /* can CPP read stdin directly? */
?H:.
?T:cont
?F:!testcpp.c !testcpp.h !testcpp.out
?LINT:set d_cppcanstdin d_cppignhdrs
?LINT:usefile testcpp.c testcpp.out
: see how we invoke the C preprocessor

```

\$cat <<EOM

\$package needs to be able to preprocess its input files in a mode which preserves comments, which is often not the default behaviour. It should run the C preprocessor you will use when compiling your own source code, which should be ISO/ANSI C compliant if you want \$package to handle the latest standard C. I will try to guess, but I might guess wrongly because it is not necessarily the same preprocessor used to build \$package.

EOM

```
$cat <<'EOT' >testcpp.c
#define ABC abc
#define XYZ xyz
ABC.XYZ
/* comment */
EOT
:
if $test "X$cppfilecom"
  != "X" && \
  $cppfilecom testcpp.c </dev/null >testcpp.out 2>/dev/null && \
  $contains 'abc.*xyz' testcpp.out >/dev/null 2>&1 && \
  $contains comment testcpp.out >/dev/null 2>&1
then
  echo "You used to use $cppfilecom so we'll use that again."
elif echo 'Maybe ""$cc' -E -C" will work...' && \
  $cc -E -C testcpp.c </dev/null >testcpp.out 2>/dev/null && \
  $contains 'abc.*xyz' testcpp.out >/dev/null 2>&1 && \
  $contains comment testcpp.out >/dev/null 2>&1
then
  echo "It works!"
  cppfilecom="$cc -E -C"
elif echo 'Nope...maybe ""$cc"' -P -C" will work...' && \
  $cc -P -C testcpp.c </dev/null >testcpp.out 2>/dev/null && \
  $contains 'abc.*xyz' testcpp.out >/dev/null 2>&1 && \
  $contains comment testcpp.out >/dev/null 2>&1
then
  echo "Yup, that does."
  cppfilecom="$cc -P -C"
elif echo 'No such luck, maybe ""$cpp"' -C" will work...' && \
  $cpp -C testcpp.c </dev/null >testcpp.out 2>/dev/null && \
  $contains 'abc.*xyz' testcpp.out >/dev/null 2>&1 && \
  $contains comment testcpp.out
  >/dev/null 2>&1
then
  echo "Yup, it does."
  cppfilecom="$cpp -C"
else
  cppfilecom="
```

```
$cat <<'EOM'
```

I can't find a C preprocessor that will preserve comments. Please name one.

```
EOM
```

```
fi
```

```
:
```

```
dflt="$cppfilecom"
```

```
cont=true
```

```
while $test "$cont" ; do
```

```
echo " "
```

```
rp="How should $package run your preprocessor preserving comments?"
```

```
. ./myread
```

```
cppfilecom="$ans"
```

```
$cppfilecom testcpp.c >testcpp.out 2>&1
```

```
if $contains 'abc.*xyz' testcpp.out >/dev/null 2>&1 && \
```

```
$contains comment testcpp.out >/dev/null 2>&1
```

```
then
```

```
echo "OK, that will do."
```

```
cont=""
```

```
else
```

```
echo "Sorry, I can't get that to work."
```

```
fi
```

```
done
```

```
@if CPP_IGN_HDRS || d_cppignhdrs
```

```
: Now see if it ignores header files.
```

```
cp testcpp.c testcpp.h
```

```
$cppfilecom testcpp.h >testcpp.out 2>&1
```

```
if $contains 'abc.*xyz' testcpp.out >/dev/null 2>&1 && \
```

```
$contains comment testcpp.out >/dev/null 2>&1
```

```
then
```

```
echo "Terrific; it processes .h files passed on the command line too."
```

```
val="$undef"
```

```
else
```

```
echo "It ignores .h files on the command line; pity."
```

```
val="$define"
```

```
fi
```

```
set
```

```
d_cppignhdrs
```

```
eval $setvar
```

```
@end
```

```
@if CPP_STDIN_FLAGS || CPP_CAN_STDIN || cppstdinflags || d_cppcanstdin
```

```
: Now see how to send stdin to it.
```

```
echo " "
```

```
cp testcpp.c testcpp.h
```

```
$cppfilecom <testcpp.h >testcpp.out 2>&1
```

```
if $contains 'abc.*xyz' testcpp.out >/dev/null 2>&1 && \
```

```
$contains comment testcpp.out >/dev/null 2>&1
```

```

then
echo "Great; and it will read stdin if passed no arguments."
val="$define"
cppstdinflags=""
else
$cpptestcom - <testcpp.h >testcpp.out 2>&1
if $contains 'abc.*xyz' testcpp.out >/dev/null 2>&1 && \
$contains comment testcpp.out >/dev/null 2>&1
then
echo "Great; and it can read stdin by passing it '-'."
val="$define"
cppstdinflags='- '
else
$cat <<FOO
Unfortunately, I can't find an easy way to get that preprocessor to read from
standard input. Do you know any flags I can pass it to get it to do so?
If that preprocessor can't read directly from standard input, answer 'none'.

```

```

FOO
val='dunno'
while $test "$val" = "dunno"; do
rp='Flags to get preprocessor
to read stdin?'
dflt='none'
. ./myread
if $test $ans = 'none'; then
echo "Oh well, if $package wants it done, it will do it for itself."
val="$undef"
else
$cpptestcom $ans <testcpp.h >testcpp.out 2>&1
if $contains 'abc.*xyz' testcpp.out >/dev/null 2>&1 && \
$contains comment testcpp.out >/dev/null 2>&1
then
echo "Good; that works fine."
val="$define"
cppstdinflags="$ans"
else
echo "Sorry, I couldn't get that to work."
fi
fi
done
fi
fi
set d_cppteststdin
eval $setvar

@end
: cleanup cpp test files anyway

```

\$rm -f testcpp.*

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/cppfilecom.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_crypt_r.U,v 0RCS:

?RCS: Copyright (c) 2002,2003 Jarkko Hietaniemi

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?RCS: Generated by the reentr.pl from the Perl 5.8 distribution.

?RCS:

?MAKE:d_crypt_r crypt_r_proto: Inlibc Protochk Hasproto i_systypes \
 usethreads i_crypt extern_C

?MAKE: -pick add \$@ %<

?S:d_crypt_r:

?S: This variable conditionally defines the HAS_CRYPT_R symbol,

?S: which indicates to the C program that the crypt_r()

?S: routine is available.

?S:.

?S:crypt_r_proto:

?S: This variable encodes the prototype of crypt_r.

?S: It is zero if d_crypt_r is undef, and one of the

?S: REENTRANT_PROTO_T_ABC macros of reentr.h if d_crypt_r

?S: is defined.

?S:.

?C:HAS_CRYPT_R:

?C: This symbol, if defined, indicates that the crypt_r routine

?C: is available to crypt re-entrantly.

?C:.

?C:CRYPT_R_PROTO:

?C: This

symbol encodes the prototype of crypt_r.

?C: It is zero if d_crypt_r is undef, and one of the

?C: REENTRANT_PROTO_T_ABC macros of reentr.h if d_crypt_r

?C: is defined.

?C:.

?H:#\$d_crypt_r HAS_CRYPT_R /**/

?H:#define CRYPT_R_PROTO \$crypt_r_proto /**/

?H:.

?T:try hdrs d_crypt_r_proto

: see if crypt_r exists

set crypt_r d_crypt_r

eval \$inlibc

case "\$d_crypt_r" in

```

"$define")
hdrs="$i_systypes sys/types.h define stdio.h $i_crypt crypt.h"
case "$d_crypt_r_proto:$usethreads" in
":define") d_crypt_r_proto=define
set d_crypt_r_proto crypt_r $hdrs
eval $hasproto ;;
*) ;;
esac
case "$d_crypt_r_proto" in
define)
case "$crypt_r_proto" in
"|0) try='char* crypt_r(const char*, const char*, struct crypt_data*);'
./prochck "$extern_C $try" $hdrs && crypt_r_proto=B_CCS ;;
esac
case "$crypt_r_proto" in
"|0) try='char* crypt_r(const char*, const char*, CRYPTD*);'
./prochck "$extern_C $try" $hdrs && crypt_r_proto=B_CCD ;;
esac
case "$crypt_r_proto" in
"|0) d_crypt_r=undef
crypt_r_proto=0
echo "Disabling crypt_r, cannot determine prototype." >&4 ;;
* ) case "$crypt_r_proto" in
REENTRANT_PROTO*) ;;
*) crypt_r_proto="REENTRANT_PROTO_$crypt_r_proto" ;;
esac
echo "Prototype: $try" ;;
esac
;;
*) case "$usethreads" in
define) echo "crypt_r has no prototype, not using it." >&4 ;;
esac
d_crypt_r=undef
crypt_r_proto=0
;;
esac
;;
*) crypt_r_proto=0
;;
esac

```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/threads/d_crypt_r.U
```

No license file was found, but licenses were detected in source scan.

You may redistribute only under the terms of the Artistic Licence,

Found in path(s):

- * /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/lib/errnolist.mk
- * /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/files/fixcpp
- * /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/bindex
- * /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/makegloss

No license file was found, but licenses were detected in source scan.

?RCS: You may redistribute only under the terms of the Artistic License,

Found in path(s):

- * /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_ldbl_dig.U
- * /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/floatsize.U
- * /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_isblank.U
- * /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/d_const.U
- * /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/typedefs/gidsign.U
- * /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_gai_strerror.U
- *
- /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/ssizetype.U
- * /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_builtin.U
- * /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/d_volatile.U
- * /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/intsize.U
- * /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/i_neterrno.U
- * /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/d_sigaction.U
- * /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/typedefs/uidsize.U
- *
- /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_wscmp.U
- * /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/compline/d_sanemcmp.U
- * /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_u32align.U

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/d_eofpipe.U

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/fpossize.U

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/typedefs/sizesize.U

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/abortsig.U

*

/opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/compline/sunscanf.U

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/typedefs/pidsize.U

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/i_inttypes.U

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/d_casti32.U

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/d_strctcpy.U

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/compline/d_sgndchr.U

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_lc_monetary_2008.U

*

/opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/d_open3.U

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/d_getpagsz.U

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/d_attribut.U

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/d_sanemcmp.U

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/compline/sbrksmart.U

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/startperl.U

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/gccvers.U

*

/opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/compline/charsize.U

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/compline/bitpbyte.U

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/compline/d_eofpipe.U

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/modified/d_access.U

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-

debian-perl-5.26.1/dist/U/d_vprintf.U
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/bitpbyte.U
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/d_getpgrp.U
*
/opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/compline/floatsize.U
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/d_access.U
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/ebcdic.U
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/typedefs/ssize.U
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_wcsxfrm.U
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/modified/d_getpgrp.U
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/byteorder.U
*
/opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/compline/d_scannl.U
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/d_isascii.U
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/sunscanf.U
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/doublesize.U
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/sbrksmart.U
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/alignbytes.U
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/compline/abortsig.U
*
/opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/compline/doublesize.U
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/ptrsize.U
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/d_keepsig.U
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_dir_dd_fd.U
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/compline/ptrsize.U
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/compline/d_sigaction.U

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/d_sgnchr.U
*
/opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/Checkcc.U
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/compline/sockopt.U
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/compline/d_casti32.U
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_snprintf.U
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/nullified/fpu.U
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/sockopt.U
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_c99_variadic.U
*
/opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/randbits.U
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/modified/d_strtoul.U
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/compline/d_keepsig.U
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/compline/d_open3.U
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/modified/d_const.U
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/compline/ssizetype.U
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/st_ino_def.U
*
/opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/modified/i_malloc.U
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/gccvers.U
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/modified/d_mmap.U
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/modified/d_volatile.U
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/need_va_copy.U
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/fpu.U
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/compline/d_isascii.U
*

```

/opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/d_scannl.U
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/perl/d_dirfd.U
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/perl/selectminbits.U
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/perl/stdio_streams.U
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/charsize.U
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/typedefs/pidsign.U
*
/opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/perl/d_socklen_t.U
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/typedefs/uidsign.U
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/compline/alignbytes.U
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/typedefs/gidsize.U
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/modified/i_neterrno.U
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/perl/d_int64_t.U
No license file was found, but licenses were detected in source scan.

```

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1999, Jarkko Hietaniemi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 3.0.

?RCS:

?MAKE:d_sigqueue: Inlibc

?MAKE: -pick add \$@ %<

?S:d_sigqueue:

?S: This variable conditionally defines HAS_SIGQUEUE

?S: if sigqueue() is available to queue a signal and data to a process.

?S:.

?C:HAS_SIGQUEUE:

?C: This symbol, if defined, indicates that the sigqueue

?C: system call is available to queue a signal and data to a process.

?C:.

?H:#\$d_sigqueue HAS_SIGQUEUE /**/

```
?H:
?LINT:set d_sigqueue
: see if sigqueue exists
set sigqueue d_sigqueue
eval $inlibc
```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/perl/d_sigqueue.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: d_endnent.U,v 3.0 1993/08/18 12:06:09 ram Exp $
```

```
?RCS:
```

```
?RCS: Copyright (c) 1991-1993, Raphael Manfredi
```

```
?RCS:
```

```
?RCS: You may redistribute only under the terms of the Artistic License,
```

```
?RCS: as specified in the README file that comes with the distribution.
```

```
?RCS: You may reuse parts of this distribution only within the terms of
```

```
?RCS: that same Artistic License; a copy of which may be found at the root
```

```
?RCS: of the source tree for dist 3.0.
```

```
?RCS:
```

```
?RCS: $Log: d_endnent.U,v $
```

```
?RCS: Revision 3.0 1993/08/18 12:06:09 ram
```

```
?RCS: Baseline for dist 3.0 netwide release.
```

```
?RCS:
```

```
?MAKE:d_endnent: Inlibc
```

```
?MAKE: -pick add $@ %<
```

```
?S:d_endnent:
```

```
?S: This variable conditionally defines HAS_ENDNETENT if endnetent() is
```

```
?S: available to close whatever was being used for network queries.
```

```
?S:.
```

```
?C:HAS_ENDNETENT:
```

```
?C: This symbol, if defined, indicates that the endnetent() routine is
```

```
?C: available to close whatever was being used for network
```

```
queries.
```

```
?C:.
```

```
?H:#$d_endnent HAS_ENDNETENT /**/
```

```
?H:.
```

```
?LINT:set d_endnent
```

```
: see if endnetent exists
```

```
set endnetent d_endnent
```

```
eval $inlibc
```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/modified/d_endnent.U
```

No license file was found, but licenses were detected in source scan.

```

?RCS: $Id: d_readdir_r.U,v 0RCS:
?RCS: Copyright (c) 2002,2003 Jarkko Hietaniemi
?RCS:
?RCS: You may distribute under the terms of either the GNU General Public
?RCS: License or the Artistic License, as specified in the README file.
?RCS:
?RCS: Generated by the reentr.pl from the Perl 5.8 distribution.
?RCS:
?MAKE:d_readdir_r readdir_r_proto: Inlibc Protochk Hasproto i_systypes \
  usethreads i_dirent extern_C
?MAKE: -pick add $@ %<
?S:d_readdir_r:
?S: This variable conditionally defines the HAS_READDIR_R symbol,
?S: which indicates to the C program that the readdir_r()
?S: routine is available.
?S:.
?S:readdir_r_proto:
?S: This variable encodes the prototype of readdir_r.
?S: It is zero if d_readdir_r is undef, and one of the
?S: REENTRANT_PROTO_T_ABC macros of reentr.h if d_readdir_r
?S: is defined.
?S:.
?C:HAS_READDIR_R:
?C: This symbol, if defined, indicates that the readdir_r routine
?C: is available to readdir re-entrantly.
?C:.
?C:READDIR_R_PROTO:
?C: This
?C: symbol encodes the prototype of readdir_r.
?C: It is zero if d_readdir_r is undef, and one of the
?C: REENTRANT_PROTO_T_ABC macros of reentr.h if d_readdir_r
?C: is defined.
?C:.
?H:#$d_readdir_r HAS_READDIR_R /**/
?H:#define READDIR_R_PROTO $readdir_r_proto /**/
?H:.
?T:try hdrs d_readdir_r_proto
: see if readdir_r exists
set readdir_r d_readdir_r
eval $inlibc
case "$d_readdir_r" in
"$define")
  hdrs="$i_systypes sys/types.h define stdio.h $i_dirent dirent.h"
  case "$d_readdir_r_proto:$usethreads" in
  ":define") d_readdir_r_proto=define
  set d_readdir_r_proto readdir_r $hdrs
  eval $hasproto ;;
  *) ;;

```

```

esac
case "$d_readdir_r_proto" in
define)
case "$readdir_r_proto" in
"|0) try='int readdir_r(DIR*, struct dirent*, struct dirent**);'
./protochk "$extern_C $try" $hdrs && readdir_r_proto=I_TSR ;;
esac
case "$readdir_r_proto" in
"|0) try='int readdir_r(DIR*, struct dirent*);'
./protochk "$extern_C $try" $hdrs && readdir_r_proto=I_TS
;;
esac
case "$readdir_r_proto" in
"|0) d_readdir_r=undef
readdir_r_proto=0
echo "Disabling readdir_r, cannot determine prototype." >&4 ;;
* ) case "$readdir_r_proto" in
REENTRANT_PROTO*) ;;
*) readdir_r_proto="REENTRANT_PROTO_${readdir_r_proto}" ;;
esac
echo "Prototype: $try" ;;
esac
;;
*) case "$usethreads" in
define) echo "readdir_r has no prototype, not using it." >&4 ;;
esac
d_readdir_r=undef
readdir_r_proto=0
;;
esac
;;
*) readdir_r_proto=0
;;
esac

```

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/threads/d_readdir_r.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1999 Jarkko Hietaniemi

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?MAKE:d_dirname_r: Inlibc

?MAKE: -pick add \$@ %<
?S:d_dirname_r:
?S: This variable conditionally defines the HAS_DIRNAME_R symbol,
?S: which indicates to the C program that the dirname_r()
?S: routine is available.
?S:.
?C:HAS_DIRNAME_R:
?C: This symbol, if defined, indicates that the dirname_r routine
?C: is available to dirname re-entrantly.
?C:.
?H:#\$d_dirname_r HAS_DIRNAME_R /**/
?H:.
?LINT:set d_dirname_r
: see if dirname_r exists
set dirname_r d_dirname_r
eval \$inlibc

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/threads/d_dirname_r.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_getpgrp2.U 1 2006-08-24 12:32:52Z rmanfredi \$
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: \$Log: d_getpgrp2.U,v \$
?RCS: Revision 3.0 1993/08/18 12:06:15 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:d_getpgrp2: Inlibc
?MAKE: -pick add \$@ %<
?S:d_getpgrp2:
?S: This variable conditionally defines the HAS_GETPGRP2 symbol, which
?S: indicates to the C program that the getpgrp2() (as in DG/UX) routine
?S: is available to get the current process group.
?S:.
?C:HAS_GETPGRP2 (GETPGRP2):
?C: This symbol, if defined, indicates that the
getpgrp2() (as in DG/UX)
?C: routine is available to get the current process group.
?C:.

```
?H:#$d_getpgrp2 HAS_GETPGRP2 /**/  
?H.:  
?LINT:set d_getpgrp2  
: see if getpgrp2 exists  
set getpgrp2 d_getpgrp2  
eval $inlibc
```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-  
debian-perl-5.26.1/dist/U/d_getpgrp2.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id$  
?RCS:  
?RCS: Copyright (c) 2000 Jarkko Hietaniemi  
?RCS:  
?RCS: You may distribute under the terms of either the GNU General Public  
?RCS: License or the Artistic License, as specified in the README file.  
?RCS:  
?MAKE:d_setproctitle: Inlibc  
?MAKE: -pick add $@ %<  
?S:d_setproctitle:  
?S: This variable conditionally defines the HAS_SETPROCTITLE symbol,  
?S: which indicates to the C program that the setproctitle() routine  
?S: is available.  
?S.:  
?C:HAS_SETPROCTITLE:  
?C: This symbol, if defined, indicates that the setproctitle routine is  
?C: available to set process title.  
?C.:  
?H:#$d_setproctitle HAS_SETPROCTITLE /**/  
?H.:  
?LINT:set d_setproctitle  
: see if setproctitle exists  
set setproctitle d_setproctitle  
eval $inlibc
```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-  
debian-perl-5.26.1/U/perl/d_setproctitle.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: Begin.U 1 2006-08-24 12:32:52Z rmanfredi $  
?RCS:  
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi  
?RCS:  
?RCS: You may redistribute only under the terms of the Artistic Licence,  
?RCS: as specified in the README file that comes with the distribution.
```

?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: Begin.U,v \$

?RCS: Revision 3.0.1.3 1997/02/28 14:56:35 ram

?RCS: patch61: added Extractall dependency

?RCS:

?RCS: Revision 3.0.1.2 1995/01/30 14:25:08 ram

?RCS: patch49: avoid an empty rmlist: systems might choke on it (WED)

?RCS:

?RCS: Revision 3.0.1.1 1994/10/31 09:32:20 ram

?RCS: patch44: created

?RCS:

?X:

?X: This file comes after option processing had been done and after all
?X: the default values have been set up. It marks the beginning
of questions.

?X: It is important that Options be listed *after* Myinit to ensure that the

?X: default initializations performed by Init and Myinit will not clobber

?X: any setting done on the command line via -D or -U.

?X:

?MAKE:Begin: Myinit Options package Extractall

?MAKE: -pick add \$@ %<

: Eunice requires " " instead of """, can you believe it

echo " "

: Here we go...

echo "Beginning of configuration questions for \$package."

?X: Make sure the rm below is given a non-empty list for some systems.

?X: This is run only when within the UU directory, hence we can safely

?X: attempt to rm a non-existent 'X' file...

trap 'echo " "; test -d ../UU && rm -rf X \$rmlist; exit 1' 1 2 3 15

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/Begin.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1999 Jarkko Hietaniemi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 3.0.

```

?RCS:
?MAKE:sitehtml1 sitehtml1exp installsitehtml1: Getfile Setprefixvar \
prefix siteprefix html1dir sed
?MAKE: -pick add $@ %<
?Y:TOP
?D:sitehtml1="
?S:sitehtml1:
?S: This variable contains the name of the directory in which site-specific
?S: html source pages are to be put. It is the responsibility of the
?S: Makefile.SH to get the value of this into the proper command.
?S: You must be prepared to do the ~name expansion yourself.
?S: The standard distribution will put nothing in this directory.
?S: After perl has been installed,
users may install their own local
?S: html pages in this directory with
?S: MakeMaker Makefile.PL
?S: or equivalent. See INSTALL for details.
?S:.
?D:sitehtml1exp="
?S:sitehtml1exp:
?S: This variable is the same as the sitehtml1 variable, but is filename
?S: expanded at configuration time, for convenient use in makefiles.
?S:.
?D:installsitehtml1="
?S:installsitehtml1:
?S: This variable is really the same as sitehtml1exp, unless you are using
?S: AFS in which case it points to the read/write location whereas
?S: html1direxp only points to the read-only access location. For extra
?S: portability, you should only use this variable within your makefiles.
?S:.
?LINT:change prefixvar
?LINT:set installsitehtml1
?LINT:set sitehtml1
?LINT:set sitehtml1exp
: determine where add-on html pages go
: There is no standard location, so try to copy the previously-selected
: directory structure for the core html pages.
case "$sitehtml1" in
") dflt=`echo "$html1dir" | $sed "s#^$prefix#$siteprefix#"`
;;
*) dflt=$sitehtml1 ;;
esac
case "$dflt" in
"| ") dflt=none ;;
esac
fn=dn+~
rp='Pathname where the site-specific html pages should be installed?'
../getfile

```

prefixvar=sitehtml

./setprefixvar

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/installldirs/sitehtml.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: d_sem.U,v \$

?RCS: Revision 3.0 1993/08/18 12:07:03 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?MAKE:d_sem: test d_semctl d_semget d_semop Setvar Findhdr osname

?MAKE: -pick add \$@ %<

?S:d_sem:

?S: This variable conditionally defines the HAS_SEM symbol, which

?S: indicates that the entire sem*(2) library is present.

?S:.

?C:HAS_SEM:

?C: This symbol, if defined, indicates that the entire sem*(2) library is

?C: supported.

?C:.

?H:#\$d_sem HAS_SEM /**/

?H:.

?T:h_sem

?LINT:set d_sem

:

see how much of the 'sem*(2)' library is present.

h_sem=true

echo " "

case "\$d_semctl\$d_semget\$d_semop" in

"\$undef") h_sem=false;;

esac

case "\$osname" in

freebsd)

case "`ipcs 2>&1`" in

"SVID messages"*"not configured"*)

echo "Your \$osname does not have the sem*(2) configured." >&4

```

    h_sem=false
val="$undef"
set semctl d_semctl
eval $setvar
set semget d_semget
eval $setvar
set semop d_semop
eval $setvar
;;
    esac
;;
esac
: we could also check for sys/ipc.h ...
if $h_sem && $stest `./findhdr sys/sem.h`; then
echo "You have the full sem*(2) library." >&4
val="$define"
else
echo "You don't have the full sem*(2) library." >&4
val="$undef"
fi
set d_sem
eval $setvar

```

Found in path(s):

```

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/modified/d_sem.U
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/d_sem.U

```

No license file was found, but licenses were detected in source scan.

```

?RCS: $Id: d_htonl.U 1 2006-08-24 12:32:52Z rmanfredi $
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: $Log: d_htonl.U,v $
?RCS: Revision 3.0.1.2 1994/08/29 16:09:25 ram
?RCS: patch32: now properly handles htonl() and friends when macros (ADO)
?RCS:
?RCS: Revision 3.0.1.1 1994/05/06 14:45:00 ram
?RCS: patch23: now also check for htonl() macro (ADO)
?RCS:
?RCS: Revision 3.0 1993/08/18 12:06:22 ram

```

```

?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:d_htonl: Inlibc Setvar i_niin i_sysin i_arpainet cat rm contains \
  cppstdin cppflags cppminus
?MAKE: -pick
  add $@ %<
?S:d_htonl:
?S: This variable conditionally defines HAS_HTONL if htonl() and its
?S: friends are available to do network order byte swapping.
?S:.
?C:HAS_HTONL (HTONL):
?C: This symbol, if defined, indicates that the htonl() routine (and
?C: friends htons() ntohl() ntohs()) are available to do network
?C: order byte swapping.
?C:.
?C:HAS_HTONS (HTONS):
?C: This symbol, if defined, indicates that the htons() routine (and
?C: friends htonl() ntohl() ntohs()) are available to do network
?C: order byte swapping.
?C:.
?C:HAS_NTOHL (NTOHL):
?C: This symbol, if defined, indicates that the ntohl() routine (and
?C: friends htonl() htons() ntohs()) are available to do network
?C: order byte swapping.
?C:.
?C:HAS_NTOHS (NTOHS):
?C: This symbol, if defined, indicates that the ntohs() routine (and
?C: friends htonl() htons() ntohl()) are available to do network
?C: order byte swapping.
?C:.
?H:#$d_htonl HAS_HTONL /**/
?H:#$d_htonl HAS_HTONS /**/
?H:#$d_htonl HAS_NTOHL /**/
?H:#$d_htonl
  HAS_NTOHS /**/
?H:.
?F:!htonl.c
?LINT:set d_htonl
: see if htonl --and friends-- exists
val="
set htonl val
eval $inlibc

: Maybe they are macros.
case "$val" in
$undef)
  $cat >htonl.c <<EOM
#include <stdio.h>

```

```

#include <sys/types.h>
#include I_NETINET_IN
#include I_SYS_IN
#include I_ARPA_INET
#ifdef I_NETINET_IN
#include <netinet/in.h>
#endif
#ifdef I_SYS_IN
#include <sys/in.h>
#endif
#ifdef I_ARPA_INET
#include <arpa/inet.h>
#endif
#ifdef htonl
printf("Defined as a macro.");
#endif
EOM
Scppstdin Scppflags Scppminus < htonl.c >htonl.E 2>/dev/null
if $contains 'Defined as a macro' htonl.E >/dev/null 2>&1; then
    val="$define"
    echo "But it seems to be defined as a macro." >&4
fi
$rm -f htonl.?
;;
esac
set d_htonl
eval $setvar

```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/modified/d_htonl.U
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 2008 H.Merijn Brand

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?MAKE:d_timegm: Inlibc

?MAKE: -pick add \$@ %<

?S:d_timegm:

?S: This variable conditionally defines the HAS_TIMEGM symbol, which

?S: indicates to the C program that the timegm () routine is available.

?S:.

?C:HAS_TIMEGM:

?C: This symbol, if defined, indicates that the timegm routine is

?C: available to do the opposite of gmtime ()

?C:.

?H:#\$d_timegm HAS_TIMEGM /**/

?H:.

?LINT:set d_timegm

: see if timegm exists

set timegm d_timegm

eval \$inlibc

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_timegm.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: libpth.U,v \$

?RCS: Revision 3.0.1.6 1997/02/28 16:08:49 ram

?RCS: patch61: new loclibpth variable

?RCS:

?RCS: Revision 3.0.1.5 1995/01/11 15:31:30 ram

?RCS: patch45: call ./mips instead of just mips (WED)

?RCS:

?RCS: Revision 3.0.1.4 1994/08/29 16:29:15 ram

?RCS: patch32: added /lib/pa1.1 for HP-UX specially tuned PA-RISC libs (ADO)

?RCS: patch32: fixed information message, making it clearer (ADO)

?RCS:

?RCS: Revision 3.0.1.3 1994/06/20 07:03:54 ram

?RCS: patch30: added /usr/shlib to
glibpth for shared-only libraries

?RCS:

?RCS: Revision 3.0.1.2 1994/05/13 15:26:57 ram

?RCS: patch27: fixed a typo (libpth -> glibpth)

?RCS:

?RCS: Revision 3.0.1.1 1994/05/06 15:07:53 ram

?RCS: patch23: now asks for library directories to be searched (ADO)

?RCS:

?RCS: Revision 3.0 1993/08/18 12:09:02 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?X:

?X: This unit initializes the path for C library lookup.

?X:

?MAKE:libpth glibpth xlibpth plibpth loclibpth: \
 usrinc incpath test cat Myread Oldconfig

?MAKE: -pick add \$@ %<

?S:libpth:

?S: This variable holds the general path (space-separated) used to find
 ?S: libraries. It is intended to be used by other units.

?S:.

?S:glibpth:

?S: This variable holds the general path (space-separated) used to
 ?S: find libraries. It may contain directories that do not exist on
 ?S: this platform, libpth is the cleaned-up version.

?S:.

?S:xlibpth:

?S: This variable holds extra path (space-separated) used to find
 ?S: libraries on this platform,
 for example CPU-specific libraries
 ?S: (on multi-CPU platforms) may be listed here.

?S:.

?S:loclibpth:

?S: This variable holds the paths (space-separated) used to find local
 ?S: libraries. It is prepended to libpth, and is intended to be easily
 ?S: set from the command line.

?S:.

?S:plibpth:

?S: Holds the private path used by Configure to find out the libraries.
 ?S: Its value is prepend to libpth. This variable takes care of special
 ?S: machines, like the mips. Usually, it should be empty.

?S:.

?T: xxx dlist

?LINT:use usrinc

?INIT:: change the next line if compiling for Xenix/286 on Xenix/386

?INIT:xlibpth="/usr/lib/386 /lib/386"

?INIT:: Possible local library directories to search.

?INIT:loclibpth="/usr/local/lib /opt/local/lib /usr/gnu/lib"

?INIT:loclibpth="\$loclibpth /opt/gnu/lib /usr/GNU/lib /opt/GNU/lib"

?INIT:

?INIT:: general looking path for locating libraries

?INIT:glibpth="/lib /usr/lib \$xlibpth"

?INIT:glibpth="\$glibpth /usr/ccs/lib /usr/ucblib /usr/local/lib"

?X: /shlib

is for Digital Unix 4.0

?X: /usr/shlib is for OSF/1 systems.

?INIT:test -f /usr/shlib/libc.so && glibpth="/usr/shlib \$glibpth"

?INIT:test -f /shlib/libc.so && glibpth="/shlib \$glibpth"

?INIT:

```

?INIT:: Private path used by Configure to find libraries. Its value
?INIT:: is prepended to libpth. This variable takes care of special
?INIT:: machines, like the mips. Usually, it should be empty.
?INIT:plibpth="
?INIT:
: Set private lib path
case "$plibpth" in
") if ./mips; then
?X: on mips, we DO NOT want /lib, and we want $incpath/usr/lib
  plibpth="$incpath/usr/lib /usr/local/lib /usr/ccs/lib"
  fi;;
esac
case "$libpth" in
' ') dlist="";;
") dlist="$loclibpth $plibpth $glibpth";;
*) dlist="$libpth";;
esac

: Now check and see which directories actually exist, avoiding duplicates
libpth="
for xxx in $dlist
do
  if $test -d $xxx; then
    case " $libpth " in
    *" $xxx "*) ;;
    *) libpth="$libpth $xxx";;
    esac
  fi
done
$cat <<'EOM'

```

Some systems have incompatible or broken versions of libraries. Among the directories listed in the question below, please remove any you know not to be holding relevant libraries, and add any that are needed. Say "none" for none.

```

EOM
case "$libpth" in
") dflt='none';;
*)
?X: strip leading space
  set X $libpth
  shift
  dflt=${1+"$@"}
  ;;
esac
rp="Directories to use for library searches?"

```

```
./myread
case "$ans" in
none) libpth='';
*) libpth="$ans";;
esac
```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/libpth.U
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1996, Cygnus Support

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: Original Author: Tom Tromeey <tromeey@cygnus.com>

?RCS:

?RCS: \$Log: src.U,v \$

?RCS: Revision 3.0.1.1 1997/02/28 16:23:54 ram

?RCS: patch61: created

?RCS:

?MAKE:src +rsrc: Options package contains

?MAKE: -pick add \$@ %<

?Y:TOP

?S:src (srcdir):

?S: This variable holds the (possibly relative) path of the package source.

?S: It is up to the Makefile to use this variable and set VPATH accordingly

?S: to find the sources remotely. Use \$pkgsrc to have an absolute path.

?S:.

?S:rsrc

(relsrcdir):

?S: This variable holds a potentially relative path to the package

?S: source. The contents are correct for the configuration environment,

?S: i.e. there might be an extra .. prepended to get out of the UU dir.

?S: Configure units should use this, not the src variable.

?S:.

: Find the path to the source tree

case "\$src" in

") case "\$0" in

```
*/*) src=`echo $0 | sed -e 's%/[^/][^/]*$%`
```

```
case "$src" in
```

```

/*) ;;
.) ;;
*) src=`cd ../$src && pwd` ;;
esac
;;
*) src='.';;
esac;;
esac
case "$src" in
") src=/
rsrc=/
;;
/*) rsrc="$src";;
*) rsrc="../$src";;
esac
?X:
?X: Now check whether we have found the right source tree (i.e. the one for the
?X: package we're about to configure). The original unit from Tom Tromeu forced
?X: the user to pick a unique file from his distribution, and we were merely
?X: checking the existence of that file. I prefer to rely on Configure (which
?X: we know *is* present since this unit is
?X: part of it!) and look for the
?X: definition of the package variable, making sure it's the same as ours.
?X: If it matches, we know we found the right source tree. -- RAM, 15/03/96
?X:
if test -f $rsrc/Configure && \
$contains "^package='$package'" $rsrc/Configure >/dev/null 2>&1
then
: found it, so we are ok.
else
?X: Otherwise try "." and up to 4 parent directories...
?X: Note that we prepend a ".." to get out of the configuration environment.
rsrc="
for src in . .. ../.. ../../.. ../../../..; do
if test -f ../$src/Configure && \
$contains "^package=$package" ../$src/Configure >/dev/null 2>&1
then
rsrc=../$src
break
fi
done
fi
case "$rsrc" in
")
cat <<EOM >&4

```

Sorry, I can't seem to locate the source dir for \$package. Please start Configure with an explicit path -- i.e. /some/path/Configure.

```

EOM
exit 1
;;
?X: Don't echo anything if the sources are in . -- they should know already ;-)
?X: In that case, rsrc is ../. since we lookup from within UU
../.) rsrc='.';
*)
echo
" "
echo "Sources for $package found in \"${src}\"." >&4
;;
esac

```

Found in path(s):

```

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/src.U

```

No license file was found, but licenses were detected in source scan.

```

?RCS: $Id$
?RCS:
?RCS: Copyright (c) 1998, Jarkko Hietaniemi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 3.0.
?RCS:
?MAKE:i_thread: Inhdr
?MAKE:-pick add $@ %<
?S:i_thread:
?S: This variable conditionally defines the I_PTHREAD symbol,
?S: and indicates whether a C program should include <pthread.h>.
?S:
?C:I_PTHREAD:
?C: This symbol, if defined, indicates to the C program that it should
?C: include <pthread.h>.
?C:
?H:#$i_thread I_PTHREAD /**/
?H:
?LINT:set i_thread
: see if POSIX threads are available
set pthread.h i_thread
eval $inhdr

```

Found in path(s):

```

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-

```

debian-perl-5.26.1/U/threads/i_pthread.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: lib.U,v \$

?RCS: Revision 3.0.1.3 1995/09/25 09:16:47 ram

?RCS: patch59: unit is now forced to the top of Configure, if possible

?RCS:

?RCS: Revision 3.0.1.2 1995/01/30 14:38:08 ram

?RCS: patch49: can now handle installation prefix changes (from WED)

?RCS:

?RCS: Revision 3.0.1.1 1994/08/29 16:27:40 ram

?RCS: patch32: now uses installation prefix to set the default

?RCS:

?RCS: Revision 3.0 1993/08/18 12:08:56 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?MAKE:lib libexp: Getfile

Loc Oldconfig Prefixit Prefixup prefixexp

?MAKE: -pick add \$@ %<

?Y:TOP

?S:lib:

?S: This variable holds the name of the directory in which the user wants

?S: to put public library files for the package in question. It is most

?S: often a local directory such as /usr/local/lib. Programs using this

?S: variable must be prepared to deal with filename expansion.

?S:.

?S:libexp:

?S: This variable is the same as the lib variable, but is filename expanded

?S: at configuration time, for convenient use in your makefiles.

?S:.

: determine where public libraries go

set lib lib

eval \$prefixit

case "\$lib" in

")

dflt=`./loc . ." \$prefixexp/lib /usr/local/lib /usr/lib /lib`

set dflt

eval \$prefixup

```
;;
*) dflt="$lib";;
esac
echo " "
fn=d~
rp="Where do you want to put the public libraries?"
./getfile
lib="$ans"
libexp="$ansexp"
```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/lib.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: d_wifstat.U,v 3.0.1.3 1997/02/28 15:47:43 ram Exp $
?RCS:
?RCS: Copyright (c) 1991-1993, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 3.0.
?RCS:
?RCS: $Log: d_wifstat.U,v $
?RCS: Revision 3.0.1.3 1997/02/28 15:47:43 ram
?RCS: patch61: added a ?F: metalint hint
?RCS:
?RCS: Revision 3.0.1.2 1995/07/25 14:09:10 ram
?RCS: patch56: re-arranged compile line to include ldflags before objects
?RCS:
?RCS: Revision 3.0.1.1 1995/03/21 08:47:46 ram
?RCS: patch52: created
?RCS:
?MAKE:d_wifstat: Compile d_uwait Oldconfig cat rm
?MAKE: -pick add $@ %<
?S:d_wifstat:
?S: This symbol conditionally defines USE_WIFSTAT
if the C program can
?S: safely use the WIFxxx macros with the kind of wait() parameter
?S: declared in the program (see UNION_WAIT), or if it can't. Should
?S: only matter on HP-UX, where the macros are incorrectly written and
?S: therefore cause programs using them with an 'union wait' variable
?S: to not compile properly.
?S:.
?C:USE_WIFSTAT:
?C: This symbol, if defined, indicates to the C program that the argument
```

?C: for the WIFxxx set of macros such as WIFSIGNALED or WIFEXITED can
?C: be of the same kind as the one used to hold the wait() status. Should
?C: only matter on HP-UX, where the macros are incorrectly written and
?C: therefore cause programs using them with an 'union wait' variable
?C: to not compile properly. See also UNION_WAIT.
?C:.
?H:#\$d_wifstat USE_WIFSTAT /**/
?H:.
?T:type
?F:!foo
: see if we can use WIFxxx macros
echo " "
case "\$d_wifstat" in
"\$define") echo "As before, you can safely use WIFEXITED and friends!" >&4;;
"\$undef") echo "You still can't use WIFEXITED
and friends!" >&4;;
*)
echo "Let's see whether you can use the WIFEXITED(status) macro and its"
case "\$d_uwait" in
"\$define") type='union wait';;
*) type='int';;
esac
echo "friends with status declared as '\$type status'..."
\$cat >foo.c <<EOCP
#include <sys/types.h>
#include <sys/wait.h>

int main()
{
\$type status;
int e = 0;

#ifdef WIFEXITED
if (WIFEXITED(status))
printf("\n");
exit(0);
#else
exit(2);
#endif
}
EOCP
d_wifstat="\$undef"
set foo
if eval \$compile; then
if ./foo >/dev/null; then
echo "Great! Looks like we can use the WIFxxx macros." >&4
d_wifstat="\$define"
else

```

    echo "You don't seem to have WIFxxx macros, but that's ok." >&4
fi
else
    echo "Apparently you can't use WIFxxx macros properly." >&4
fi
$rm -f foo.* foo core
;;
esac

```

Found in path(s):

```

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/compline/d_wifstat.U

```

No license file was found, but licenses were detected in source scan.

```

?RCS: $Id$
?RCS:
?RCS: Copyright (c) 1999 Jarkko Hietaniemi
?RCS:
?RCS: You may distribute under the terms of either the GNU General Public
?RCS: License or the Artistic License, as specified in the README file.
?RCS:
?MAKE:d_getmntinfo_r: Inlibc
?MAKE:-pick add $@ %<
?S:d_getmntinfo_r:
?S: This variable conditionally defines the HAS_GETMNTINFO_R symbol,
?S: which indicates to the C program that the getmntinfo_r()
?S: routine is available.
?S:.
?C:HAS_GETMNTINFO_R:
?C: This symbol, if defined, indicates that the getmntinfo_r routine
?C: is available to getmntinfo re-entrantly.
?C:.
?H:#$d_getmntinfo_r HAS_GETMNTINFO_R /**/
?H:.
?LINT:set d_getmntinfo_r
: see if getmntinfo_r exists
set getmntinfo_r d_getmntinfo_r
eval $inlibc

```

Found in path(s):

```

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/threads/d_getmntinfo_r.U

```

No license file was found, but licenses were detected in source scan.

```

?RCS: $Id$
?RCS:
?RCS: Copyright (c) 1998, Jarkko Hietaniemi
?RCS:

```

?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 3.0.

?RCS:

?MAKE:i_machcth: Inhdr usethreads

?MAKE: -pick add \$@ %<

?S:i_machcth:

?S: This variable conditionally defines the I_MACH_CTHREADS symbol,

?S: and indicates whether a C program should include <mach/cthreads.h>.

?S:.

?C:I_MACH_CTHREADS:

?C: This symbol, if defined, indicates to the C program that it should

?C: include <mach/cthreads.h>.

?C:.

?H:#\$i_machcth I_MACH_CTHREADS /**/

?H:.

: see if mach cthreads are available

if test "X\$usethreads" = "X\$define"; then

set mach/cthreads.h i_machcth

eval \$inhdr

else

i_machcth="\$undef"

fi

Found

in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/threads/i_machcth.U

No license file was found, but licenses were detected in source scan.

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?MAKE:d_asinh: Inlibc

?MAKE: -pick add \$@ %<

?S:d_asinh:

?S: This variable conditionally defines the HAS_ASINH symbol, which

?S: indicates to the C program that the asinh() routine is available.

?S:.

?C:HAS_ASINH:

?C: This symbol, if defined, indicates that the asinh routine is

?C: available to do the inverse hyperbolic sine function.

?C:.

?H:#\$d_asinh HAS_ASINH /**/

?H:.

?LINT:set d_asinh

```
: see if asinh exists
set asinh d_asinh
eval $inlibc
```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/perl/d_asinh.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: myhostname.U,v 3.0.1.3 1997/02/28 16:15:55 ram Exp $
```

```
?RCS:
```

```
?RCS: Copyright (c) 1991-1993, Raphael Manfredi
```

```
?RCS:
```

```
?RCS: You may redistribute only under the terms of the Artistic License,
```

```
?RCS: as specified in the README file that comes with the distribution.
```

```
?RCS: You may reuse parts of this distribution only within the terms of
```

```
?RCS: that same Artistic License; a copy of which may be found at the root
```

```
?RCS: of the source tree for dist 3.0.
```

```
?RCS:
```

```
?RCS: $Log: myhostname.U,v $
```

```
?RCS: Revision 3.0.1.3 1997/02/28 16:15:55 ram
```

```
?RCS: patch61: improved hostname lookup by using ypmatch when NIS is used
```

```
?RCS:
```

```
?RCS: Revision 3.0.1.2 1994/10/29 16:25:43 ram
```

```
?RCS: patch36: call ./xenix explicitly instead of relying on PATH
```

```
?RCS: patch36: now uses new Tr unit to convert to/from lowercase
```

```
?RCS:
```

```
?RCS: Revision 3.0.1.1 1994/06/20 07:06:20 ram
```

```
?RCS: patch30: now a little more clever for domain name guessing
```

```
?RCS:
```

```
?RCS:
```

```
Revision 3.0 1993/08/18 12:09:18 ram
```

```
?RCS: Baseline for dist 3.0 netwide release.
```

```
?RCS:
```

```
?MAKE:myhostname phostname mydomain: contains sed test Myread Oldconfig \
```

```
Guess Loc awk echo sort uniq +usrinc rm hostcat Tr
```

```
?MAKE: -pick add $@ %<
```

```
?S:myhostname (hostname):
```

```
?S: This variable contains the eventual value of the MYHOSTNAME symbol,
```

```
?S: which is the name of the host the program is going to run on.
```

```
?S: The domain is not kept with hostname, but must be gotten from mydomain.
```

```
?S: The dot comes with mydomain, and need not be supplied by the program.
```

```
?S:.
```

```
?S:mydomain:
```

```
?S: This variable contains the eventual value of the MYDOMAIN symbol,
```

```
?S: which is the domain of the host the program is going to run on.
```

```
?S: The domain must be appended to myhostname to form a complete host name.
```

```
?S: The dot comes with mydomain, and need not be supplied by the program.
```

?S:.

?S:phostname:

?S: This variable contains the eventual value of the PHOSTNAME symbol,
 ?S: which is a command that can be fed to popen()
 to get the host name.

?S: The program should probably not presume that the domain is or isn't
 ?S: there already.

?S:.

?C:MYHOSTNAME (HOSTNAME):

?C: This symbol contains name of the host the program is going to run on.
 ?C: The domain is not kept with hostname, but must be gotten from MYDOMAIN.
 ?C: The dot comes with MYDOMAIN, and need not be supplied by the program.
 ?C: If gethostname() or uname() exist, MYHOSTNAME may be ignored. If MYDOMAIN
 ?C: is not used, MYHOSTNAME will hold the name derived from PHOSTNAME.

?C:.

?C:MYDOMAIN:

?C: This symbol contains the domain of the host the program is going to
 ?C: run on. The domain must be appended to HOSTNAME to form a complete
 ?C: host name. The dot comes with MYDOMAIN, and need not be supplied by
 ?C: the program. If the host name is derived from PHOSTNAME, the domain
 ?C: may or may not already be there, and the program should check.

?C:.

```
?H:#define MYHOSTNAME "$myhostname" /**/
?H:#define MYDOMAIN "$mydomain" /**/
?H:.
```

?LINT:extern osname

?T:cont

```
i tans tmp_re
: now get the host name
echo " "
echo "Figuring out host name..." >&4
case "$myhostname" in
") cont=true
echo 'Maybe "hostname" will work...'
if tans=`sh -c hostname 2>&1` ; then
myhostname=$tans
phostname=hostname
cont="
fi
;;
*) cont="";;
esac
if $test "$cont"; then
if ./xenix; then
echo 'Oh, dear. Maybe "/etc/systemid" is the key...'
if tans=`cat /etc/systemid 2>&1` ; then
myhostname=$tans
phostname='cat /etc/systemid'
```

```

echo "Whadyaknow. Xenix always was a bit strange..."
cont=""
fi
elif $test -r /etc/systemid; then
echo "(What is a non-Xenix system doing with /etc/systemid?)"
fi
fi
if $test "$cont"; then
echo 'No, maybe "uuname -l" will work...'
if tans=`sh -c 'uuname -l 2>&1` ; then
myhostname=$tans
phostname='uuname -l'
else
echo 'Strange. Maybe "uname -n" will work...'
if tans=`sh -c 'uname -n 2>&1` ; then
myhostname=$tans
phostname='uname -n'
else
echo 'Oh well, maybe I can mine it out of whoami.h...'
if
tans=`sh -c $contains' sysname $usrinc/whoami.h' 2>&1` ; then
myhostname=`echo "$tans" | $sed 's/^\.*(.*?)\^1/^\^
phostname="sed -n -e ""'/sysname/s/^\.*(.*?)\^1/{"" -e p -e q -e }' <$usrinc/whoami.h"
else
case "$myhostname" in
") echo "Does this machine have an identity crisis or something?"
phostname="";
*)
echo "Well, you said $myhostname before..."
phostname='echo $myhostname';;
esac
fi
fi
fi
fi
case "$myhostname" in
") myhostname=noname ;;
esac
: you do not want to know about this
set $myhostname
myhostname=$1

: verify guess
if $test "$myhostname" ; then
dflt=y
rp='Your host name appears to be "$myhostname"." Right?'
./myread
case "$ans" in

```

```

y*) ;;
*) myhostname=";;
esac
fi

```

```

: bad guess or no guess
while $test "X$myhostname" = X ; do
dflt="
rp="Please type the (one word) name of your host:"
./myread
myhostname="$ans"
done

```

```

: translate upper to lower if necessary
case "$myhostname" in
*[A-Z]*)
echo
"(Normalizing case in your host name)"
myhostname=`echo $myhostname | ./tr '[A-Z]' '[a-z]'`
;;
esac

```

?X: Do not ask for domain name if this is not used later on. In that

?X: case, the hostname may keep its domain name, but it doesn't matter.

@if MYDOMAIN || mydomain

```

case "$myhostname" in
*.*)
dflt=`expr "X$myhostname" : "X[^\.]*\(\..*\)"`
myhostname=`expr "X$myhostname" : "X\([^\.]*\)\"`
echo "(Trimming domain name from host name--host name is now $myhostname)"
;;
*) case "$mydomain" in
)

```

?X:

?X: There is currently no way to say we do not want hostcat if mydomain is not

?X: used. One way to achieve that would be to put that code in a mydomain.U

?X: unit. However, we want to stick the sanity checks right after the domain

?X: name computation, or if none is done, right after the hostname computation.

?X:

```
{
```

?X: If we use NIS, try ypmatch.

```

test "X$hostcat" = "Xypcat hosts" &&
ypmatch "$myhostname" hosts 2>/dev/null \
$sed -e 's/[ ]*#.*//; s/$/ /' > hosts
&& \
$test -s hosts
} || {

```

?X: Extract only the relevant hosts, reducing file size,

?X: remove comments, insert trailing space for later use.

?X: Test to be sure we *have* a hostcat command. os390 doesn't.

```
test "X$hostcat" != "X" &&
    $hostcat | $sed -n -e "s/[ ]*#.*//; s^$/ /
/[ ]$myhostname[ . ]/p" > hosts
}
tmp_re="[ .]"
if $test -f hosts; then
$stest x`$awk "/[0-9].*[ ]$myhostname$tmp_re/ { sum++ }
    END { print sum }" hosts` = x1 || tmp_re="[ ]"
dflt=`$awk "/[0-9].*[ ]$myhostname$tmp_re/ {for(i=2; i<=NF;i++) print \\|\\$i}" \
hosts | $sort | $uniq | \
$sed -n -e "s/$myhostname\\.([-a-zA-Z0-9_\\.])^1/p"
case `$echo X$dflt` in
X*\ *) echo "(Several hosts in the database matched hostname)"
dflt=.
;;
X.) echo "(You do not have fully-qualified names in the hosts database)"
;;
esac
else
echo "(I cannot locate a hosts database anywhere)"
dflt=.
fi
case "$dflt" in
.)
tans=`./loc resolv.conf X /etc
/usr/etc`
if $test -f "$tans"; then
echo "(Attempting domain name extraction from $tans)"
?X: Look for either a search or a domain directive.
dflt=`$sed -n -e 's// /g' \
-e 's/^search *([^\ ]*).*/1/p' $tans \
-e 1q 2>/dev/null`
case "$dflt" in
.) dflt=`$sed -n -e 's// /g' \
-e 's/^domain *([^\ ]*).*/1/p' $tans \
-e 1q 2>/dev/null`
;;
esac
fi
;;
esac
case "$dflt" in
.) echo "(No help from resolv.conf either -- attempting clever guess)"
dflt=`sh -c domainname 2>/dev/null`
case "$dflt" in
") dflt='.';;
```

```

.nis.*|.yp.*|.main.*) dflt=`echo $dflt | $sed -e 's/^\.[^.]*/^/';
esac
;;
esac
case "$dflt$osname" in
.os390) echo "(Attempting domain name extraction from //SYS1.TCPPARMS(TCPDATA))"
dflt=`awk '/^DOMAINORIGIN/ {print $2}' "//SYS1.TCPPARMS(TCPDATA)" 2>/dev/null`
;;
esac
case "$dflt" in
.) echo "(Lost all hope -- silly guess then)"
dflt='.nonet'
;;
esac
$rm
-f hosts
;;
*) dflt="$mydomain";;
esac;;
esac
echo " "
rp="What is your domain name?"
./myread
tans="$ans"
case "$ans" in
") ;;
.*) ;;
*) tans=".${ans}";;
esac
mydomain="$stans"

: translate upper to lower if necessary
case "$mydomain" in
*[A-Z]*)
echo "(Normalizing case in your domain name)"
mydomain=`echo $mydomain | ./tr '[A-Z]' '[a-z]'`
;;
esac

@end
: a little sanity check here
case "$phostname" in
") ;;
*)
case ` $phostname | ./tr '[A-Z]' '[a-z]^` in
$myhostname$mydomain|$myhostname) ;;
*)
case "$phostname" in

```

```

sed*)
echo "(That doesn't agree with your whoami.h file, by the way.)"
;;
*)
echo "(That doesn't agree with your $phostname command, by the way.)"
;;
esac
;;
esac
;;
esac

```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/modified/myhostname.U
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_drاند48_r.U,v 0RCS:

?RCS: Copyright (c) 2002,2003 Jarkko Hietaniemi

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?RCS: Generated by the reentr.pl from the Perl 5.8 distribution.

?RCS:

?MAKE:d_drاند48_r drاند48_r_proto: Inlibc Protochk Hasproto i_systypes \
 usethreads i_stdlib extern_C

?MAKE: -pick add \$@ %<

?S:d_drاند48_r:

?S: This variable conditionally defines the HAS_DRAND48_R symbol,

?S: which indicates to the C program that the drاند48_r()

?S: routine is available.

?S:.

?S:drاند48_r_proto:

?S: This variable encodes the prototype of drاند48_r.

?S: It is zero if d_drاند48_r is undef, and one of the

?S: REENTRANT_PROTO_T_ABC macros of reentr.h if d_drاند48_r

?S: is defined.

?S:.

?C:HAS_DRAND48_R:

?C: This symbol, if defined, indicates that the drاند48_r routine

?C: is available to drاند48 re-entrantly.

?C:.

?C:DRAND48_R_PROTO:

?C: This

symbol encodes the prototype of drاند48_r.

?C: It is zero if d_drاند48_r is undef, and one of the

?C: REENTRANT_PROTO_T_ABC macros of reentr.h if d_drاند48_r

```

?C: is defined.
?C:.
?H:#$d_drand48_r HAS_DRAND48_R /**/
?H:#define DRAND48_R_PROTO $drand48_r_proto /**/
?H:.
?T:try hdrs d_drand48_r_proto
: see if drand48_r exists
set drand48_r d_drand48_r
eval $inlibc
case "$d_drand48_r" in
"$define")
hdrs="$i_systypes sys/types.h define stdio.h $i_stdlib stdlib.h"
case "$d_drand48_r_proto:$usethreads" in
":define") d_drand48_r_proto=define
set d_drand48_r_proto drand48_r $hdrs
eval $hasproto ;;
*) ;;
esac
case "$d_drand48_r_proto" in
define)
case "$drand48_r_proto" in
"|0) try='int drand48_r(struct drand48_data*, double*);'
./protochk "$extern_C $try" $hdrs && drand48_r_proto=I_ST ;;
esac
case "$drand48_r_proto" in
"|0) d_drand48_r=undef
drand48_r_proto=0
echo "Disabling drand48_r, cannot determine prototype."
>&4 ;;
* ) case "$drand48_r_proto" in
REENTRANT_PROTO*) ;;
*) drand48_r_proto="REENTRANT_PROTO_$drand48_r_proto" ;;
esac
echo "Prototype: $try" ;;
esac
;;
*) case "$usethreads" in
define) echo "drand48_r has no prototype, not using it." >&4 ;;
esac
d_drand48_r=undef
drand48_r_proto=0
;;
esac
;;
*) drand48_r_proto=0
;;
esac

```

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/threads/d_drاند48_r.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: xs_apiversion.U \$

?RCS:

?RCS: Copyright (c) 1999 Andy Dougherty

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 3.0.

?RCS:

?RCS: \$Log: xs_apiversion.U,v \$

?RCS:

?MAKE:xs_apiversion pm_apiversion: version

?MAKE: -pick add \$@ %<

?S:xs_apiversion:

?S: This variable contains the version of the oldest perl binary

?S: compatible with the present perl. perl.c:incpush() and

?S: lib/lib.pm will automatically search in \$sitearch for older

?S: directories across major versions back to xs_apiversion.

?S: This is only useful if you have a perl library directory tree

?S: structured like the default one.

?S: See INSTALL for how this works.

?S: The

versioned site_perl directory was introduced in 5.005,

?S: so that is the lowest possible value.

?S: Since this can depend on compile time options

?S: it is set by Configure. Other non-default sources

?S: of potential incompatibility, such as multiplicity, threads,

?S: debugging, 64bits, sfio, etc., are not checked for currently,

?S: though in principle we could go snooping around in old

?S: Config.pm files.

?S:.

?S:pm_apiversion:

?S: This variable contains the version of the oldest perl

?S: compatible with the present perl. (That is, pure perl modules

?S: written for \$pm_apiversion will still work for the current

?S: version). perl.c:incpush() and lib/lib.pm will automatically

?S: search in \$sitelib for older directories across major versions

?S: back to pm_apiversion. This is only useful if you have a perl

?S: library directory tree structured like the default one. The

?S: versioned site_perl library was introduced in 5.005, so that's

?S: the default setting for this variable.

It's hard to imagine

?S: it changing before Perl6. It is included here for symmetry

?S: with `xs_apiveprson --` the searching algorithms will

?S: (presumably) be similar.

?S: See the INSTALL file for how this works.

?S:.

?C:PERL_XS_APIVERSION:

?C: This variable contains the version of the oldest perl binary

?C: compatible with the present perl. `perl.c:incpush()` and

?C: `lib/lib.pm` will automatically search in `$sitearch` for older

?C: directories across major versions back to `xs_apiversion`.

?C: This is only useful if you have a perl library directory tree

?C: structured like the default one.

?C: See INSTALL for how this works.

?C: The versioned `site_perl` directory was introduced in 5.005,

?C: so that is the lowest possible value.

?C: Since this can depend on compile time options

?C: it is set by Configre. Other non-default sources

?C: of potential incompatibility, such as multiplicity, threads,

?C: debugging, 64bits, `sfio`, etc., are not checked for currently,

?C: though in principle

we could go snooping around in old

?C: `Config.pm` files.

?C:.

?C:PERL_PM_APIVERSION:

?C: This variable contains the version of the oldest perl

?C: compatible with the present perl. (That is, pure perl modules

?C: written for `pm_apiversion` will still work for the current

?C: version). `perl.c:incpush()` and `lib/lib.pm` will automatically

?C: search in `$sitelib` for older directories across major versions

?C: back to `pm_apiversion`. This is only useful if you have a perl

?C: library directory tree structured like the default one. The

?C: versioned `site_perl` library was introduced in 5.005, so that's

?C: the default setting for this variable. It's hard to imagine

?C: it changing before Perl6. It is included here for symmetry

?C: with `xs_apiveprson --` the searching algorithms will

?C: (presumably) be similar.

?C: See the INSTALL file for how this works.

?C:.

?H:#define PERL_XS_APIVERSION "\$xs_apiversion"

?H:#define PERL_PM_APIVERSION "\$pm_apiversion"

?H:.

: Find earliest binary compatible

`site_perl` subdirectory perl can use.

`xs_apiversion=$version #` The current `site_perl` version.

: Find earliest pure perl `site_perl` subdirectory perl can use.

: The versioned directories started at 5.005.

`pm_apiversion='5.005'`

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/xs_apiversion.U
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1999 Jarkko Hietaniemi

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?MAKE:gidformat: gidsize gidsign ivsize uvsize longsize intsize shortsize \
ivdformat uvuformat test echo

?MAKE: -pick add \$@ %<

?S:gidformat:

?S: This variable contains the format string used for printing a Gid_t.

?S:.

?C:Gid_t_f:

?C: This symbol defines the format string used for printing a Gid_t.

?C:.

?H:#define Gid_t_f \$gidformat /**/

?H:.

: Check format string for GID

echo " "

\$echo "Checking the format string to be used for gids..." >&4

case "\$gidsign" in

-1) if \$test X"\$gidsize" = X"\$ivsize"; then
gidformat="\$ivdformat"

else

if \$test X"\$gidsize" = X"\$longsize"; then
gidformat=""ld""

else

if \$test X"\$gidsize" = X"\$intsize"; then
gidformat=""d""

else

if \$test X"\$gidsize"
= X"\$shortsize"; then
gidformat=""hd""

fi

fi

fi

fi

;;

*) if \$test X"\$gidsize" = X"\$uvsize"; then

```

gidformat="$Suvuformat"
else
if $test X"$gidsize" = X"$longsize"; then
gidformat="lu"
else
if $test X"$gidsize" = X"$intsize"; then
gidformat="u"
else
if $test X"$gidsize" = X"$shortsize"; then
gidformat="hu"
fi
fi
fi
fi
;;
esac

```

Found in path(s):

```

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/typedefs/gidf.U

```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1999, Jarkko Hietaniemi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 3.0.

?RCS:

?MAKE:d_sched_get_priority_max: Inlibc

?MAKE: -pick add \$@ %<

?S:d_sched_get_priority_max:

?S: This variable conditionally defines HAS_SCHED_GET_PRIORITY_MAX if

?S: sched_get_priority_max() is available to get the maximum scheduling

?S: priority.

?S:.

?C:HAS_SCHED_GET_PRIORITY_MAX:

?C: This symbol, if defined, indicates that the sched_get_priority_max

?C: system call is available to get the maximum scheduling priority.

?C:.

?H:#\$d_sched_get_priority_max HAS_SCHED_GET_PRIORITY_MAX /**/

?H:.

?LINT:set d_sched_get_priority_max

:

```
see if sched_get_priority_max exists
set sched_get_priority_max d_sched_get_priority_max
eval $inlibc
```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/perl/d_sched_gpmax.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: startsh.U 1 2006-08-24 12:32:52Z rmanfredi $
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: $Log: startsh.U,v $
?RCS: Revision 3.0.1.1 1997/02/28 16:25:31 ram
?RCS: patch61: avoid needless chatter since this is now done very early
?RCS:
?RCS: Revision 3.0 1993/08/18 12:09:51 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:startsh: sh sharpbang eunicefix
?MAKE: -pick add $@ %<
?S:startsh:
?S: This variable contains the string to put on the front of a shell
?S: script to make sure (hopefully) that it runs with sh and not some
?S: other
shell.
?S:.
?F:!sharp
: figure out how to guarantee sh startup
?X: Avoid needless chatter since this is now done very early.
?X: echo " "
?X: echo "Checking out how to guarantee sh startup..." >&2
case "$startsh" in
") startsh=${sharpbang}${sh} ;;
*)
?X: echo "Let's see if '$startsh' works..." ;;
esac
cat >sharp <<EOSS
$startsh
set abc
test "$?abc" != 1
```

EOSS

```
chmod +x sharp
$unicefix sharp
if ./sharp; then
: echo "Yup, it does."
else
echo "Hmm... '$startsh' does not guarantee sh startup..."
echo "You may have to fix up the shell scripts to make sure $sh runs them."
fi
rm -f sharp
```

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/startsh.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 2000 Jarkko Hietaniemi

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?MAKE:d_isfinitel: Inlibc

?MAKE: -pick add \$@ %<

?S:d_isfinitel:

?S: This variable conditionally defines the HAS_ISFINITEL symbol, which

?S: indicates to the C program that the isfinitel() routine is available.

?S:.

?C:HAS_ISFINITEL:

?C: This symbol, if defined, indicates that the isfinitel routine is

?C: available to check whether a long double is finite.

?C: (non-infinity non-NaN).

?C:.

?H:#\$d_isfinitel HAS_ISFINITEL /**/

?H:.

?LINT:set d_isfinitel

: see if isfinitel exists

set isfinitel d_isfinitel

eval \$inlibc

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_isfinitel.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: filexp.U 1 2006-08-24 12:32:52Z rmanfredi \$

?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: \$Log: filexp.U,v \$
?RCS: Revision 3.0 1993/08/18 12:08:08 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:filexp: privlib
?MAKE: -pick add \$@ %<
?S:filexp:
?S: This symbol contains the full pathname of the filexp script, in case we
?S: are saving the script for posterity.
?S:.
: must not allow self reference
case "\$privlib" in
/*)
filexp=\$privlib/filexp
;;
*)
filexp=`pwd`/filexp
;;
esac

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/filexp.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: \$Log: Tr.U,v \$
?RCS: Revision 3.0.1.2 1994/10/29 18:00:54 ram
?RCS: patch43: forgot to quote \$@ to protect against "evil" characters
?RCS:

```

?RCS: Revision 3.0.1.1 1994/10/29 15:58:35 ram
?RCS: patch36: created
?RCS:
?X:
?X: This unit produces a bit of shell code that must be dotted in in order
?X: to do a character translation. It catches translations to uppercase or
?X: to lowercase, and then invokes the real tr to perform the job.
?X:
?X: This unit is necessary on HP machines (HP strikes again!)
with non-ascii
?X: ROMAN8-charset, where normal letters are not arranged in a row, so a-z
?X: covers not the whole alphabet but lots of special chars. This was reported
?X: by Andreas Sahlbach <a.sahlbach@tu-bs.de>.
?X:
?X: Units performing a tr '[A-Z]' '[a-z]' or the other way round should include
?X: us in their dependency and use ./tr instead.
?X:
?MAKE:Tr: startsh tr eunicefix
?MAKE:-pick add $@ %<
?F:./tr
?T:up low LC_ALL
: see whether [:lower:] and [:upper:] are supported character classes
echo " "
case ""echo AbyZ | LC_ALL=C $tr '[:lower:]' '[:upper:]' 2>/dev/null`" in
ABYZ)
echo "Good, your tr supports [:lower:] and [:upper:] to convert case." >&4
up='[:upper:]'
low='[:lower:]'
;;
*) # There is a discontinuity in EBCDIC between 'I' and 'J'
# (0xc9 and 0xd1), therefore that is a nice testing point.
if test "X$up" = X -o "X$low" = X; then
case ""echo IJ | LC_ALL=C $tr 'I-J' 'i-j' 2>/dev/null`" in
ij) up='A-Z'
low='a-z'
;;
esac
fi
if test "X$up" = X -o "X$low" = X; then
case ""echo IJ | LC_ALL=C $tr I-J i-j 2>/dev/null`" in
ij) up='A-Z'
low='a-z'
;;
esac
fi
if test "X$up" = X -o "X$low" = X; then
case ""echo IJ | od -x 2>/dev/null`" in

```

```

*C9D1*|*c9d1*)
echo "Hey, this might be EBCDIC." >&4
if test "X$up" = X -o "X$low" = X; then
    case "`echo IJ | \
LC_ALL=C $tr '[A-IJ-RS-Z]' '[a-ij-rs-z]' 2>/dev/null`" in
        ij) up='[A-IJ-RS-Z]'
            low='[a-ij-rs-z]'
        ;;
    esac
fi
if test "X$up" = X -o "X$low" = X; then
    case "`echo IJ | LC_ALL=C $tr A-IJ-RS-Z a-ij-rs-z 2>/dev/null`" in
        ij) up='A-IJ-RS-Z'
            low='a-ij-rs-z'
        ;;
    esac
fi
;;
esac
fi
case "`echo IJ | LC_ALL=C $tr \"\$up\" \"\$low\" 2>/dev/null`" in
ij)
    echo "Using $up and $low to convert case." >&4
    ;;
*)
    echo "I don't know how to translate letters from upper to lower case." >&4
    echo "Your tr is not acting any way I know of." >&4
    exit 1
    ;;
esac
: set up the translation script tr, must be called with ./tr of course
cat >tr <<EOSC
$startsh
case "\$1\$2" in
[A-Z][a-z]) LC_ALL=C exec $tr '$up' '$low';;
[a-z][A-Z]) LC_ALL=C exec $tr '$low' '$up';;
esac
LC_ALL=C exec $tr "\$@"
EOSC
chmod +x tr
$unicefix tr

```

Found in path(s):

```

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/Tr.U

```

No license file was found, but licenses were detected in source scan.

```

?RCS: $Id$
?RCS:
?RCS: Copyright (c) 2000 Jarkko Hietaniemi
?RCS:
?RCS: You may distribute under the terms of either the GNU General Public
?RCS: License or the Artistic License, as specified in the README file.
?RCS:
?MAKE:d_mkdtemp: Inlibc
?MAKE: -pick add $@ %<
?S:d_mkdtemp:
?S: This variable conditionally defines the HAS_MKDTEMP symbol, which
?S: indicates to the C program that the mkdtemp() routine is available
?S: to exclusively create a uniquely named temporary directory.
?S:.
?C:HAS_MKDTEMP :
?C: This symbol, if defined, indicates that the mkdtemp routine is
?C: available to exclusively create a uniquely named temporary directory.
?C:.
?H:#$d_mkdtemp HAS_MKDTEMP /**/
?H:.
?LINT:set d_mkdtemp
: see if mkdtemp exists
set mkdtemp d_mkdtemp
eval $inlibc

```

Found in path(s):

```

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/perl/d_mkdtemp.U

```

No license file was found, but licenses were detected in source scan.

```

?RCS: $Id: libyacc.U 1 2006-08-24 12:32:52Z rmanfredi $
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: $Log: libyacc.U,v $
?RCS: Revision 3.0.1.4 1997/02/28 16:09:19 ram
?RCS: patch61: replaced .a with $_a all over the place
?RCS:
?RCS: Revision 3.0.1.3 1994/05/13 15:27:12 ram
?RCS: patch27: added byacc case (ADO)
?RCS:
?RCS: Revision 3.0.1.2 1994/05/06 15:09:01 ram

```

```

?RCS: patch23: now uses full library path instead of -l notation
?RCS:
?RCS: Revision 3.0.1.1 1994/01/24 14:13:49 ram
?RCS: patch16: un-obsolete this unit for smooth yacc compilations
?RCS:
?RCS:
Revision 3.0 1993/08/18 12:09:04 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:libyacc: Loc yacc libpth _a
?MAKE: -pick add $@ %<
?S:libyacc:
?S: This variable contains the argument to pass to the loader in order
?S: to get the yacc library routines. If there is no yacc or yacc
?S: library, it is null.
?S:.
?T:xxx
: see if we should include -ly
echo " "
case "$yacc" in
*byacc*)
echo "You are using byacc, so I won't look for a yacc library." >&4
libyacc="
;;
*yacc)
xxx=`./loc liby$_a x $libpth`
case "$xxx" in
x)
echo "No yacc library found." >&4
libyacc="
;;
*)
echo "yacc library found in $xxx." >&4
libyacc="$xxx"
;;
esac
;;
*bison*)
echo "You are using bison, so I won't look for a yacc library." >&4
libyacc="
;;
*)
echo "You don't seem to have yacc, so I won't look for the yacc library." >&4
libyacc="
;;
esac

```

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/libyacc.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: i_values.U 1 2006-08-24 12:32:52Z rmanfredi \$

?RCS:

?RCS: Copyright (c) 1996, Andy Dougherty

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic Licence,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic Licence; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: i_values.U,v \$

?RCS: Revision 3.0.1.1 1997/02/28 15:48:34 ram

?RCS: patch61: created

?RCS:

?MAKE:i_values: Inhdr

?MAKE: -pick add \$@ %<

?S:i_values:

?S: This variable conditionally defines the I_VALUES symbol, and indicates

?S: whether a C program may include <values.h> to get symbols like MAXLONG

?S: and friends.

?S:.

?C:I_VALUES:

?C: This symbol, if defined, indicates to the C program that it should

?C: include

<values.h> to get definition of symbols like MINFLOAT or

?C: MAXLONG, i.e. machine dependant limitations. Probably, you

?C: should use <limits.h> instead, if it is available.

?C:.

?H:#\$i_values I_VALUES /**/

?H:.

?LINT:set i_values

: see if this is a values.h system

set values.h i_values

eval \$inhdr

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/i_values.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1999 Jarkko Hietaniemi

```

?RCS:
?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 3.0.
?RCS:
?MAKE:siteman3 siteman3exp installsiteman3: test Getfile Setprefixvar \
prefix siteprefix man3dir sed
?MAKE: -pick add $@ %<
?Y:TOP
?D:siteman3="
?S:siteman3:
?S: This variable contains the name of the directory in which site-specific
?S: library man source pages are to be put. It is the responsibility of the
?S: Makefile.SH to get the value of this into the proper command.
?S: You must be prepared to do the ~name expansion yourself.
?S: The standard distribution will put nothing in this directory.
?S: After perl has been
installed, users may install their own local
?S: man3 pages in this directory with
?S: MakeMaker Makefile.PL
?S: or equivalent. See INSTALL for details.
?S:.
?D:siteman3exp="
?S:siteman3exp:
?S: This variable is the same as the siteman3 variable, but is filename
?S: expanded at configuration time, for convenient use in makefiles.
?S:.
?D:installsiteman3="
?S:installsiteman3:
?S: This variable is really the same as siteman3exp, unless you are using
?S: AFS in which case it points to the read/write location whereas
?S: man3direxp only points to the read-only access location. For extra
?S: portability, you should only use this variable within your makefiles.
?S:.
?LINT:change prefixvar
?LINT:set installsiteman3
?LINT:set siteman3exp
: determine where add-on library man pages go
case "$siteman3" in
") dflt=`echo "$man3dir" | $sed "s#^$prefix#$siteprefix#"` ;;
*) dflt=$siteman3 ;;
esac
case "$dflt" in
"|" ") dflt=none ;;
esac
fn=dn+~

```

```
rp='Pathname where the site-specific library manual
pages should be installed?'
./getfile
prefixvar=siteman3
./setprefixvar
: Use ' ' for none so value is preserved next time through Configure
$test X"$siteman3" = "X" && siteman3=' '
```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/installdirs/siteman3.U
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 2004 H.Merijn Brand

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?MAKE:d_strlcat: Inlibc

?MAKE: -pick add \$@ %<

?S:d_strlcat:

?S: This variable conditionally defines the HAS_STRLCAT symbol, which

?S: indicates to the C program that the strlcat () routine is available.

?S:.

?C:HAS_STRLCAT:

?C: This symbol, if defined, indicates that the strlcat () routine is

?C: available to do string concatenation.

?C:.

?H:#\$d_strlcat HAS_STRLCAT /**/

?H:.

?LINT:set d_strlcat

: see if strlcat exists

set strlcat d_strlcat

eval \$inlibc

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/perl/d_strlcat.U
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_pwritev.U 1 2006-08-24 12:32:52Z rmanfredi \$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic Licence,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: d_pwritev.U,v \$

?RCS:

?MAKE:d_pwritev: Inlibc

?MAKE: -pick add \$@ %<

?S:d_pwritev:

?S: This variable conditionally defines the HAS_PWRITEV symbol, which

?S: indicates to the C program that the pwritev() routine is available.

?S:.

?C:HAS_PWRITEV :

?C: This symbol, if defined, indicates that the pwritev routine is

?C: available to perform vectored writes on a file descriptor at a

?C: given offset.

?C:.

?H:#\$d_pwritev HAS_PWRITEV /**/

?H:.

?LINT:set

d_pwritev

: see if pwritev exists

set pwritev d_pwritev

eval \$inlibc

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/d_pwritev.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: i_iconv.U,v \$

?RCS:

?RCS: Copyright (c) 2000 Jarkko Hietaniemi

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?MAKE:i_iconv: Inhdr Hasfield

?MAKE: -pick add \$@ %<

?S:i_iconv:

?S: This variable conditionally defines the I_ICONV symbol, and indicates

?S: whether a C program should include <iiconv.h>.

?S:.

?C:I_ICONV:

?C: This symbol, if defined, indicates that <iiconv.h> exists and

?C: should be included.

?C:.

?H:#\$i_iconv I_ICONV /**/

```
?H:
?LINT:set i_iconv
: see if this is a iconv.h system
set iconv.h i_iconv
eval $inhdr
```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/perl/i_iconv.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id$
```

```
?RCS:
```

```
?RCS: Copyright (c) 1999, Jarkko Hietaniemi
```

```
?RCS:
```

```
?RCS: You may redistribute only under the terms of the Artistic License,
```

```
?RCS: as specified in the README file that comes with the distribution.
```

```
?RCS: You may reuse parts of this distribution only within the terms of
```

```
?RCS: that same Artistic License; a copy of which may be found at the root
```

```
?RCS: of the source tree for dist 3.0.
```

```
?RCS:
```

```
?MAKE:full_ar: ar
```

```
?MAKE:-pick add $@ %<
```

```
?S:full_ar:
```

```
?S: This variable contains the full pathname to 'ar', whether or
```

```
?S: not the user has specified 'portability'. This is only used
```

```
?S: in the Makefile.SH.
```

```
?S:.
```

```
: Store the full pathname to the ar program for use in the C program
```

```
: Respect a hint or command line value for full_ar.
```

```
case "$full_ar" in
```

```
) full_ar=$ar ;;
```

```
esac
```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/perl/Loc_ar.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: d_fcntl.U 1 2006-08-24 12:32:52Z rmanfredi $
```

```
?RCS:
```

```
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
```

```
?RCS:
```

```
?RCS: You may redistribute only under the terms of the Artistic Licence,
```

```
?RCS: as specified in the README file that comes with the distribution.
```

```
?RCS: You may reuse parts of this distribution only within the terms of
```

```
?RCS: that same Artistic Licence; a copy of which may be found at the root
```

```
?RCS: of the source tree for dist 4.0.
```

?RCS:
?RCS: \$Log: d_fcntl.U,v \$
?RCS: Revision 3.0 1993/08/18 12:06:01 ram
?RCS: Baseline for dist 3.0 worldwide release.
?RCS:
?MAKE:d_fcntl: Inlibc
?MAKE: -pick add \$@ %<
?S:d_fcntl:
?S: This variable conditionally defines the HAS_FCNTL symbol, and indicates
?S: whether the fcntl() function exists
?S:.
?C:HAS_FCNTL:
?C: This symbol, if defined, indicates to the C program that
?C: the fcntl() function exists.
?C:.
?H:#\$d_fcntl HAS_FCNTL /**/
?H:.
?LINT:set d_fcntl
:
see if this is an fcntl system
set fcntl d_fcntl
eval \$inlibc

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/d_fcntl.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$
?RCS:
?RCS: Copyright (c) 1999, Jarkko Hietaniemi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 3.0.
?RCS:
?MAKE:d_madvise: Inlibc
?MAKE: -pick add \$@ %<
?S:d_madvise:
?S: This variable conditionally defines HAS_MADVISE if madvise() is
?S: available to map a file into memory.
?S:.
?C:HAS_MADVISE:
?C: This symbol, if defined, indicates that the madvise system call is
?C: available to map a file into memory.
?C:.

?H:#\$d_madvise HAS_MADVISE /**/

?H:.

?LINT:set d_madvise

: see if madvise exists

set madvise d_madvise

eval \$inlibc

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_madvise.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_setegid.U 1 2006-08-24 12:32:52Z rmanfredi \$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic Licence,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic Licence; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: d_setegid.U,v \$

?RCS: Revision 3.0 1993/08/18 12:07:07 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?MAKE:d_setegid: Inlibc

?MAKE: -pick add \$@ %<

?S:d_setegid:

?S: This variable conditionally defines the HAS_SETEGID symbol, which

?S: indicates to the C program that the setegid() routine is available

?S: to change the effective gid of the current program.

?S:.

?C:HAS_SETEGID (SETEGID):

?C: This symbol, if defined, indicates that the setegid routine is available

?C: to change the effective gid of the current program.

?C:.

?H:#\$d_setegid HAS_SETEGID /**/

?H:.

?LINT:set d_setegid

: see if setegid exists

set setegid d_setegid

eval \$inlibc

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/d_setegid.U

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: d_gethid.U 1 2006-08-24 12:32:52Z rmanfredi $
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: $Log: d_gethid.U,v $
?RCS: Revision 3.0 1993/08/18 12:06:10 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:d_gethid: Inlibc
?MAKE: -pick add $@ %<
?S:d_gethid:
?S: This variable conditionally defines HAS_GETHOSTID if gethostid() is
?S: available to get the host id.
?S:.
?C:HAS_GETHOSTID (GETHOSTID):
?C: This symbol, if defined, indicates that the gethostid system call is
?C: available to get the host id.
?C:.
?H:#$d_gethid HAS_GETHOSTID /**/
?H:.
?LINT:set
d_gethid
: see if gethid exists
set gethostid d_gethid
eval $inlibc
```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/d_gethid.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: archlib.U,v 3.1 1999/07/08 18:32:29 doughera Exp doughera $
?RCS:
?RCS: Copyright (c) 1991-1993, Raphael Manfredi
?RCS:
?RCS: This file is included with or a derivative work of a file included
?RCS: with the metaconfig program of Raphael Manfredi's "dist" distribution.
?RCS: In accordance with clause 7 of dist's modified Artistic License:
?RCS:
?RCS: You may distribute under the terms of either the GNU General Public
```

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?RCS: Original Author: Andy Dougherty <doughera@lafcol.lafayette.edu>

?RCS:

?RCS: \$Log: archlib.U,v \$

?RCS: Revision 3.1 1999/07/08 18:32:29 doughera

?RCS: Updated for perl5.005_5x

?RCS:

?RCS:

?RCS: Revision 3.0.1.4 1995/09/25 09:15:18 ram

?RCS: patch59: unit is now forced to the top of Configure, if possible

?RCS:

?RCS: Revision 3.0.1.3 1995/02/15 14:14:14 ram

?RCS: patch51: architecture name is now
computed by a separate unit

?RCS:

?RCS: Revision 3.0.1.2 1995/01/30 14:32:22 ram

?RCS: patch49: archname is now systematically recomputed

?RCS: patch49: can now handle installation prefix changes (from WED)

?RCS:

?RCS: Revision 3.0.1.1 1994/10/29 16:02:36 ram

?RCS: patch36: created by ADO

?RCS:

?MAKE:d_archlib archlib archlibexp installarchlib: \
cat Getfile Setprefixvar Loc Oldconfig archname spackage \
privlib sed test Prefixit Prefixup binexp

?MAKE: -pick add \$@ %<

?Y:TOP

?S:d_archlib:

?S: This variable conditionally defines ARCHLIB to hold the pathname
?S: of architecture-dependent library files for \$package. If
?S: \$archlib is the same as \$privlib, then this is set to undef.

?S:.

?D:archlib=""

?S:archlib:

?S: This variable holds the name of the directory in which the user wants
?S: to put architecture-dependent public library files for \$package.
?S: It is most often a local directory such as /usr/local/lib.
?S: Programs using this variable must be prepared to deal
?S: with
filename expansion.

?S:.

?D:archlibexp=""

?S:archlibexp:

?S: This variable is the same as the archlib variable, but is
?S: filename expanded at configuration time, for convenient use.

?S:.

?D:installarchlib=""

?S:installarchlib:

?S: This variable is really the same as archlibexp but may differ on

?S: those systems using AFS. For extra portability, only this variable

?S: should be used in makefiles.

?S:.

?C:ARCHLIB:

?C: This variable, if defined, holds the name of the directory in

?C: which the user wants to put architecture-dependent public

?C: library files for \$package. It is most often a local directory

?C: such as /usr/local/lib. Programs using this variable must be

?C: prepared to deal with filename expansion. If ARCHLIB is the

?C: same as PRIVLIB, it is not defined, since presumably the

?C: program already searches PRIVLIB.

?C:.

?C:ARCHLIB_EXP:

?C: This symbol contains the ~name expanded version of ARCHLIB, to be used

?C: in programs that are not prepared to deal with ~ expansion

at run-time.

?C:.

?H:#\$d_archlib ARCHLIB "\$sarchlib" /**/

?H:#\$d_archlib ARCHLIB_EXP "\$sarchlibexp" /**/

?H:.

?T: tdfit

?LINT:change prefixvar

?LINT:set archlib

?LINT:set archlibexp

?LINT:set installarchlib

: determine where public architecture dependent libraries go

set archlib archlib

eval \$prefixit

: privlib default is /usr/local/lib/\$package/\$version

: archlib default is /usr/local/lib/\$package/\$version/\$sarchname

: privlib may have an optional trailing /share.

tdflt=`echo \$privlib | \$sed 's,/share\$,,'`

tdflt=\$tdflt/\$sarchname

case "\$sarchlib" in

*) dflt=\$tdflt

::

*) dflt="\$sarchlib"

::

esac

\$cat <<EOM

\$spackage contains architecture-dependent library files. If you are sharing libraries in a heterogeneous environment, you might store these files in a separate location. Otherwise, you can just include them with the rest of the public library files.

```

EOM
?X: Force dependency on bin.U
fn=$binexp
fn=d+~
rp='Where do you want to put the public architecture-dependent libraries?'
.
./getfile
prefixvar=archlib
./setprefixvar
if $test X"$sarchlib" = X"$sprivlib"; then
d_archlib="$undef"
else
d_archlib="$define"
fi

```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/installdirs/archlib.U
```

No license file was found, but licenses were detected in source scan.

```

?RCS: $Id: d_tminsys.U 1 2006-08-24 12:32:52Z rmanfredi $
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: $Log: d_tminsys.U,v $
?RCS: Revision 3.0 1993/08/18 12:07:47 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:d_tminsys: contains Setvar Findhdr
?MAKE: -pick add $@ %<
?S:d_tminsys:
?S: This variable conditionally defines TM_IN_SYS if this system
?S: declares "struct tm" in <sys/time.h> rather than <time.h>.
?S:.
?C:TM_IN_SYS (TMINSYS):
?C: This symbol is defined if this system declares "struct tm" in
?C: in <sys/time.h> rather than <time.h>.
We can't just say
?C: -I/usr/include/sys because some systems have both time files, and
?C: the -I trick gets the wrong one.
?C:.
?H:#$d_tminsys TM_IN_SYS /**/

```

```

?H:
?LINT:set d_tminsys
: see if struct tm is defined in sys/time.h
echo " "
if $contains 'struct tm' `./findhdr time.h` >/dev/null 2>&1 ; then
  echo "You have struct tm defined in <time.h> rather than <sys/time.h>." >&4
  val="$undef"
else
  echo "You have struct tm defined in <sys/time.h> rather than <time.h>." >&4
  val="$define"
fi
set d_tminsys
eval $setvar

```

Found in path(s):

```

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/d_tminsys.U

```

No license file was found, but licenses were detected in source scan.

```

?RCS: $Id: d_semctl.U 1 2006-08-24 12:32:52Z rmanfredi $
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: $Log: d_semctl.U,v $
?RCS: Revision 3.0 1993/08/18 12:07:04 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:d_semctl: Inlibc
?MAKE: -pick add $@ %<
?S:d_semctl:
?S: This variable conditionally defines the HAS_SEMCTL symbol, which
?S: indicates to the C program that the semctl() routine is available.
?S:
?C:HAS_SEMCTL:
?C: This symbol, if defined, indicates that the semctl() routine is
?C: available to perform semaphore control operations.
?C:
?H:#$d_semctl
HAS_SEMCTL /**/
?H:
?LINT:set d_semctl
: see if semctl exists

```

```
set semctl d_semctl
eval $inlibc
```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/d_semctl.U
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: nis.U,v \$

?RCS: Revision 3.0.1.3 1997/02/28 16:17:38 ram

?RCS: patch61: ensure suitable defaults for hostcat and friends

?RCS:

?RCS: Revision 3.0.1.2 1995/03/21 08:48:34 ram

?RCS: patch52: continued fix for NeXT NIS/NetInfo handling

?RCS:

?RCS: Revision 3.0.1.1 1995/02/15 14:16:23 ram

?RCS: patch51: now correctly handles NeXT using NIS rather than NetInfo

?RCS:

?RCS: Revision 3.0 1993/08/18 12:09:24 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?MAKE:passcat groupcat hostcat:

Myread Oldconfig test contains

?MAKE: -pick add \$@ %<

?S:passcat:

?S: This variable contains a command that produces the text of the

?S: /etc/passwd file. This is normally "cat /etc/passwd", but can be

?S: "ypcat passwd" when NIS is used.

?S:.

?S:groupcat:

?S: This variable contains a command that produces the text of the

?S: /etc/group file. This is normally "cat /etc/group", but can be

?S: "ypcat group" when NIS is used.

?S:.

?S:hostcat:

?S: This variable contains a command that produces the text of the

?S: /etc/hosts file. This is normally "cat /etc/hosts", but can be

?S: "ypcat hosts" when NIS is used.

?S:.

: see if we have to deal with yellow pages, now NIS.

?X: NeXT gives us some fun here, as always, by having both NIS (former YP)

?X: and NetInfo. But since it has both, it's ok to put the test inside the if.

?X: Contributed by Thomas Neumann <tom@smart.bo.open.de>.

```
if $test -d /usr/etc/yp || $test -d /etc/yp || $test -d /usr/lib/yp; then
```

```
if $test -f /usr/etc/nibindd; then
```

```
echo
```

```
" "
```

```
echo "I'm fairly confident you're on a NeXT."
```

```
@if passcat || groupcat
```

```
echo " "
```

```
rp='Do you get the passwd file via NetInfo?'
```

```
dflt=y
```

```
case "$passcat" in
```

```
nidump*) ;;
```

```
");;
```

```
*) dflt=n;;
```

```
esac
```

```
./myread
```

```
case "$ans" in
```

```
y*) passcat='nidump passwd .'
```

```
@if groupcat
```

```
echo "(Assuming /etc/group is also distributed.)"
```

```
groupcat='nidump group .'
```

```
@end
```

```
::
```

```
*) echo "You told me, so don't blame me."
```

```
case "$passcat" in
```

```
nidump*) passcat="
```

```
@if groupcat
```

```
groupcat="";;
```

```
@end
```

```
esac
```

```
@if groupcat
```

```
echo "(Assuming /etc/group is handled the same way.)"
```

```
@end
```

```
::
```

```
esac
```

```
@end
```

```
@if hostcat
```

```
echo " "
```

```
rp='Do you get the hosts file via NetInfo?'
```

```
dflt=y
```

```
case "$hostcat" in
```

```
nidump*) ;;
```

```
");;
```

```
*) dflt=n;;
```

```

esac
./myread
case "$ans" in
y*) hostcat='nidump hosts .';;
*) case "$hostcat" in
nidump*) hostcat="";;
esac
;;
esac
@end
fi
@if passcat || groupcat
case "$passcat" in
nidump*) ;;
*)
case "$passcat" in
*yocat*) dflt=y;;
")
if $contains '^+' /etc/passwd >/dev/null 2>&1; then
dflt=y
else
dflt=n
fi;;
*) dflt=n;;
esac
echo " "
rp='Are you getting the passwd file via yellow pages?'
./myread
case "$ans" in
y*) passcat='yocat passwd'
@if groupcat
echo "(Assuming /etc/group is also distributed.)"
groupcat='yocat group'
@end
;;
*) passcat='cat /etc/passwd'
@if groupcat
echo "(Assuming /etc/group is also local.)"
groupcat='cat /etc/group'
@end
;;
esac
;;
esac
@end
@if hostcat
case "$hostcat" in
nidump*) ;;

```

```

*)
case "$hostcat" in
*ypcat*) dflt=y;;
") if $contains '^\\+' /etc/passwd >/dev/null 2>&1; then
    dflt=y
    else
        dflt=n
    fi;;
*) dflt=n;;
esac
echo " "
rp='Are you getting the hosts file via yellow pages?'
./myread
case "$ans" in
y*) hostcat='ypcat hosts';;
*) hostcat='cat /etc/hosts';;
esac
;;
esac
@end
fi

```

?X: Ensure suitable default -- Manoj Srivastava

```

case "$hostcat" in
") hostcat=:
    $test -f /etc/hosts && hostcat='cat
/etc/hosts';;
esac
case "$groupcat" in
") groupcat=:
    $test -f /etc/group && groupcat='cat /etc/group';;
esac
case "$passcat" in
") passcat=:
    $test -f /etc/passwd && passcat='cat /etc/passwd';;
esac

```

Found in path(s):

```

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/nis.U

```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_cbrt.U 1 2006-08-24 12:32:52Z rmanfredi \$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic Licence,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic Licence; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: d_cbrt.U,v \$

?RCS: Revision 3.0 1993/08/18 12:05:48 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?MAKE:d_cbrt: Inlibc

?MAKE: -pick add \$@ %<

?S:d_cbrt:

?S: This variable conditionally defines the HAS_CBRT symbol, which

?S: indicates to the C program that the cbrt() (cube root) function

?S: is available.

?S:.

?C:HAS_CBRT (CBRT):

?C: This symbol, if defined, indicates that the cbrt() (cube root)

?C: function is available.

?C:.

?H:#\$d_cbrt HAS_CBRT /**/

?H:.

?LINT:set

d_cbrt

: see if cbrt exists

set cbrt d_cbrt

eval \$inlibc

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/d_cbrt.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 2000 Jarkko Hietaniemi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 3.0.

?RCS:

?MAKE:d_getespwnam: Inlibc

?MAKE: -pick add \$@ %<

?S:d_getespwnam:

?S: This variable conditionally defines HAS_GETESPWNAM if getespwnam() is

?S: available to retrieve enhanced (shadow) password entries by name.

?S:.

?C:HAS_GETESPWNAM:

?C: This symbol, if defined, indicates that the getespwnam system call is

?C: available to retrieve enhanced (shadow) password entries by name.

?C:.

?H:#\$d_getespwnam HAS_GETESPWNAM /**/

?H:.

?LINT:set d_getespwnam

: see if getespwnam exists

set getespwnam d_getespwnam

eval \$inlibc

Found in

path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_getespwnam.U

No license file was found, but licenses were detected in source scan.

?RCS: You may redistribute only under the terms of the Artistic Licence,

?RCS: as specified in the README file that comes with the distribution.

?RCS:

?MAKE:i_stdint: Inhdr

?MAKE: -pick add \$@ %<

?S:i_stdint:

?S: This variable conditionally defines the I_STDINT symbol, which

?S: indicates to the C program that <stdint.h> exists and should

?S: be included.

?S:.

?C:I_STDINT:

?C: This symbol, if defined, indicates that <stdint.h> exists and

?C: should be included.

?C:.

?H:#\$i_stdint I_STDINT /**/

?H:.

?LINT:set i_stdint

: see if stdint is available

set stdint.h i_stdint

eval \$inhdr

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/i_stdint.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_shmat.U,v 3.0.1.3 1995/07/25 14:04:23 ram Exp \$

?RCS:

?RCS: Copyright (c) 1991-1993, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 3.0.

?RCS:
?RCS: \$Log: d_shmat.U,v \$
?RCS: Revision 3.0.1.3 1995/07/25 14:04:23 ram
?RCS: patch56: use findhdr to find <sys/shm.h>, to get the right one (ADO)
?RCS:
?RCS: Revision 3.0.1.2 1994/05/13 15:18:56 ram
?RCS: patch27: added new symbol HAS_SHMAT_PROTOTYPE (ADO)
?RCS:
?RCS: Revision 3.0.1.1 1994/05/06 14:54:18 ram
?RCS: patch23: new Shmat_t symbol to declare return type of shmat()
?RCS:
?RCS: Revision 3.0 1993/08/18 12:07:18 ram
?RCS: Baseline for dist 3.0 netwide
release.
?RCS:
?MAKE:d_shmat shmattype d_shmatprototype: Inlibc cat +cc +ccflags \
rm cppstdin cppflags cppminus Findhdr Setvar contains
?MAKE: -pick add \$@ %<
?S:d_shmat:
?S: This variable conditionally defines the HAS_SHMAT symbol, which
?S: indicates to the C program that the shmat() routine is available.
?S:.
?S:shmattype:
?S: This symbol contains the type of pointer returned by shmat().
?S: It can be 'void *' or 'char *'.
?S:.
?S:d_shmatprototype:
?S: This variable conditionally defines the HAS_SHMAT_PROTOTYPE
?S: symbol, which indicates that sys/shm.h has a prototype for
?S: shmat.
?S:.
?C:HAS_SHMAT:
?C: This symbol, if defined, indicates that the shmat() routine is
?C: available to attach a shared memory segment to the process space.
?C:.
?C:Shmat_t:
?C: This symbol holds the return type of the shmat() system call.
?C: Usually set to 'void *' or 'char *'.
?C:.
?C:HAS_SHMAT_PROTOTYPE:
?C: This symbol, if defined, indicates that the sys/shm.h includes
?C: a prototype for shmat().
Otherwise, it is up to the program to
?C: guess one. Shmat_t shmat(int, Shmat_t, int) is a good guess,
?C: but not always right so it should be emitted by the program only

?C: when HAS_SHMAT_PROTOTYPE is not defined to avoid conflicting defs.

?C:.

?H:#\$d_shmat HAS_SHMAT /**/

?H:#define Shmat_t \$shmattype /**/

?H:#\$d_shmatprototype HAS_SHMAT_PROTOTYPE /**/

?H:.

?LINT:set d_shmat d_shmatprototype

?T:xxx

: see if shmat exists

set shmat d_shmat

eval \$inlibc

: see what shmat returns

case "\$d_shmat" in

"\$define")

\$cat >shmat.c <<'END'

#include <sys/shm.h>

void *shmat();

END

if \$cc \$ccflags -c shmat.c >/dev/null 2>&1; then

shmattype='void *'

else

shmattype='char *'

fi

echo "and it returns (\$shmattype)." >&4

: see if a prototype for shmat is available

xxx=`./findhdr sys/shm.h`

\$cppstdin \$cppflags \$cppminus < \$xxx > shmat.c 2>/dev/null

if \$contains 'shmat.*(' shmat.c >/dev/null 2>&1; then

val="\$define"

else

val="\$undef"

fi

\$rm -f shmat.[co]

::

*)

val="\$undef"

::

esac

set

d_shmatprototype

eval \$setvar

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/modified/d_shmat.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_bcmp.U 1 2006-08-24 12:32:52Z rmanfredi \$

```

?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: $Log: d_bcmp.U,v $
?RCS: Revision 3.0.1.2 1993/10/16 13:47:52 ram
?RCS: patch12: added magic support for bcmp()
?RCS:
?RCS: Revision 3.0.1.1 1993/09/13 16:00:44 ram
?RCS: patch10: now only defines HAS_BCMP, no macro remap on memcmp (WAD)
?RCS:
?RCS: Revision 3.0 1993/08/18 12:05:42 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:d_bcmp: Inlibc
?MAKE: -pick add $@ %<
?S:d_bcmp:
?S: This variable conditionally defines the HAS_BCMP symbol
if
?S: the bcmp() routine is available to compare strings.
?S:.
?C:HAS_BCMP:
?C: This symbol is defined if the bcmp() routine is available to
?C: compare blocks of memory.
?C:.
?H:#$d_bcmp HAS_BCMP /**/
?H:.
?M:bcmp: HAS_BCMP
?M:#ifndef HAS_BCMP
?M:#ifndef bcmp
?M:#define bcmp(s,d,l) memcmp((s),(d),(l))
?M:#endif
?M:#endif
?M:.
?LINT:set d_bcmp
: see if bcmp exists
set bcmp d_bcmp
eval $inlibc

```

Found in path(s):

```

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/d_bcmp.U

```

No license file was found, but licenses were detected in source scan.

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?MAKE:usequadmath: Setvar cat uselongdouble

?MAKE: -pick add \$@ %<

?S:usequadmath:

?S: This variable conditionally defines the USE_QUADMATH symbol,

?S: and indicates that the quadmath library __float128 long doubles

?S: should be used when available.

?S:.

?C:USE_QUADMATH:

?C: This symbol, if defined, indicates that the quadmath library should

?C: be used when available.

?C:.

?H:?%<:#ifndef USE_QUADMATH

?H:?%<:#\$usequadmath USE_QUADMATH /**/

?H:?%<:#endif

?H:.

: Check if quadmath is requested

case "\$usequadmath" in

"\$define"|true[|yY]*) usequadmath="\$define" ;;

*) usequadmath="\$undef" ;;

esac

: Fail if both uselongdouble and usequadmath are requested

case "\$usequadmath:\$uselongdouble" in

define:define)

\$cat <<EOM >&4

*** You requested the use of

the quadmath library and use

*** of long doubles.

*** Please select one or the other.

EOM

exit 1

::

esac

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/usequadmath.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1996, Andy Dougherty
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: \$Log: sitelib.U,v \$
?RCS: Revision 3.0.1.1 1997/02/28 16:21:35 ram
?RCS: patch61: created
?RCS:
?MAKE:sitelib sitelibexp installsitelib: afs cat Getfile \
Oldconfig Prefixit test privlib package sed
?MAKE: -pick add \$@ %<
?Y:TOP
?S:sitelib:
?S: This variable contains the eventual value of the SITELIB symbol,
?S: which is the name of the private library for this package. It may
?S: have a ~ on the front. It is up to the makefile to eventually create
?S: this
directory while performing installation (with ~ substitution).
?S:.
?S:sitelibexp:
?S: This variable is the ~name expanded version of sitelib, so that you
?S: may use it directly in Makefiles or shell scripts.
?S:.
?S:installsitelib:
?S: This variable is really the same as sitelibexp but may differ on
?S: those systems using AFS. For extra portability, only this variable
?S: should be used in makefiles.
?S:.
?C:SITELIB:
?C: This symbol contains the name of the private library for this package.
?C: The library is private in the sense that it needn't be in anyone's
?C: execution path, but it should be accessible by the world. The program
?C: should be prepared to do ~ expansion.
?C: The standard distribution will put nothing in this directory.
?C: Individual sites may place their own extensions and modules in
?C: this directory.
?C:.
?C:SITELIB_EXP:
?C: This symbol contains the ~name expanded version of SITELIB, to be used
?C: in programs that are not prepared to deal with ~ expansion
at run-time.
?C:.
?H:#define SITELIB "\$sitelib" /**/

```

?H:#define SITELIB_EXP "$sitelibexp" /**/
?H:.
?T:prog
: determine where site specific libraries go.
set sitelib sitelib
eval $prefixit
case "$sitelib" in
")
?X: remove any trailing -3.0 or other version identification
prog=`echo $package | $sed 's/-*[0-9.]*$//`
dflt="$privlib/site_$prog" ;;
*) dflt="$sitelib" ;;
esac
$cat <<EOM

```

The installation process will also create a directory for site-specific extensions and modules. Some users find it convenient to place all local files in this directory rather than in the main distribution directory.

```

EOM
fn=d~+
rp='Pathname for the site-specific library files?'
./getfile
if $test "X$sitelibexp" != "X$sansexp"; then
installsitelib="
fi
sitelib="$ans"
sitelibexp="$sansexp"
if $afs; then
$cat <<EOM

```

Since you are running AFS, I need to distinguish the directory in which private files reside from the directory in which they are installed (and from which they are presumably copied to the former directory by occult means).

```

EOM
case "$installsitelib" in
") dflt=`echo $sitelibexp | sed 's#^/afs/#/afs/.#` ;;
*) dflt="$installsitelib";;
esac
fn=de~
rp='Where will private files be installed?'
./getfile
installsitelib="$ans"
else
installsitelib="$sitelibexp"

```

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/sitelib.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1996, Andy Dougherty

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: man3dir.U,v \$

?RCS: Revision 3.0.1.1 1997/02/28 16:10:34 ram

?RCS: patch61: created

?RCS:

?X:

?X: This was originally specific to perl5. Since perl5 has man pages that

?X: go in both man1/ and man3/ directories, we need both man1dir

?X: and man3dir. This unit is basically dist's mansrc.U with

?X: man3 used instead of man everywhere.

?X: I then added various tests because perl5 has *lots* of man3

?X: pages with long file names. -- ADO

?X:

?MAKE:man3dir

man3direxp man3ext installman3dir: afs cat nroff Loc Oldconfig \

sed man1dir spackage package Getfile prefix Prefixit Prefixup \

d_flexfnam privlib Myread

?MAKE: -pick add \$@ %<

?Y:TOP

?S:man3dir:

?S: This variable contains the name of the directory in which manual

?S: source pages are to be put. It is the responsibility of the

?S: Makefile.SH to get the value of this into the proper command.

?S: You must be prepared to do the ~name expansion yourself.

?S:.

?S:man3direxp:

?S: This variable is the same as the man3dir variable, but is filename

?S: expanded at configuration time, for convenient use in makefiles.

?S:.

?S:installman3dir:

?S: This variable is really the same as man3direxp, unless you are using

?S: AFS in which case it points to the read/write location whereas
 ?S: man3direxp only points to the read-only access location. For extra
 ?S: portability, you should only use this variable within your makefiles.
 ?S:.
 ?S:man3ext:
 ?S: This variable contains the extension that the manual
 page should
 ?S: have: one of 'n', 'l', or '3'. The Makefile must supply the '.'.
 ?S: See man3dir.
 ?S:.
 : determine where library module manual pages go
 set man3dir man3dir none
 eval \$prefixit
 \$cat <<EOM

\$spackage has manual pages for many of the library modules.
 EOM

```
case "$nroff" in
nroff)
$cat <<'EOM'
```

However, you don't have nroff, so they're probably useless to you.
 EOM

```
case "$man3dir" in
") man3dir="none";;
esac;;
esac
```

```
case "$d_flexfnam" in
undef)
$cat <<'EOM'
```

However, your system can't handle the long file names like File::Basename.3.
 EOM

```
case "$man3dir" in
") man3dir="none";;
esac;;
esac
```

echo "If you don't want the manual sources installed, answer 'none'."
 ?X: We dont use /usr/local/man/man3 because some man programs will
 ?X: only show the /usr/local/man/man3 contents, and not the system ones,
 ?X: thus man less will show the perl module less.pm, but not the system
 ?X: less command. We might also conflict with TCL man pages.
 ?X: However, something like /opt/perl/man/man3
 is fine.

```
case "$man3dir" in
") case "$prefix" in
*$package*) dflt=`echo $man1dir |
```

```

    $sed -e 's/man1/man3/g' -e 's/man\.1/man\.3/g' ;;
*) dflt="$privlib/man/man3" ;;
esac
;;
') dflt=none;;
*) dflt="$man3dir" ;;
esac
echo " "

fn=dn+~
rp="Where do the $package library man pages (source) go?"
./getfile
if test "X$man3direxp" != "X$ansexp"; then
    installman3dir="
fi

man3dir="$ans"
man3direxp="$ansexp"
case "$man3dir" in
    ") man3dir=' '
    installman3dir=";;
esac
if $afs; then
    $cat <<EOM

```

Since you are running AFS, I need to distinguish the directory in which manual pages reside from the directory in which they are installed (and from which they are presumably copied to the former directory by occult means).

```

EOM
case "$installman3dir" in
    ") dflt=`echo $man3direxp | sed 's#^/afs/#/afs/.#`";;
*) dflt="$installman3dir";;
esac
fn=de~
rp='Where will man pages be installed?'
./getfile
installman3dir="$ans"
else
    installman3dir="$man3direxp"
fi

```

: What suffix
to use on installed man pages

```

case "$man3dir" in
    ')
    man3ext='0'

```

```

;;
*)
rp="What suffix should be used for the $package library man pages?"
case "$man3ext" in
") case "$man3dir" in
*3) dflt=3 ;;
*3p) dflt=3p ;;
*3pm) dflt=3pm ;;
*1) dflt=1;;
*n) dflt=n;;
*o) dflt=o;;
*p) dflt=p;;
*C) dflt=C;;
*L) dflt=L;;
*L3) dflt=L3;;
*) dflt=3;;
esac
;;
*) dflt="$man3ext";;
esac
./myread
man3ext="$ans"
;;
esac

```

Found in path(s):

```

*/opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/man3dir.U

```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1999 Jarkko Hietaniemi

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?MAKE:d_getmntent: Inlibc

?MAKE: -pick add \$@ %<

?S:d_getmntent:

?S: This variable conditionally defines the HAS_GETMNTENT symbol, which

?S: indicates to the C program that the getmntent() routine is available

?S: to iterate through mounted files to get their mount info.

?S:.

?C:HAS_GETMNTENT:

?C: This symbol, if defined, indicates that the getmntent routine is

?C: available to iterate through mounted file systems to get their info.

?C:.

```
?H:#$d_getmntent HAS_GETMNTENT /**/  
?H.:  
?LINT:set d_getmntent  
: see if getmntent exists  
set getmntent d_getmntent  
eval $inlibc
```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_getmntent.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: d_endpent.U,v 3.0 1993/08/18 12:06:09 ram Exp $  
?RCS:  
?RCS: Copyright (c) 1991-1993, Raphael Manfredi  
?RCS:  
?RCS: You may redistribute only under the terms of the Artistic License,  
?RCS: as specified in the README file that comes with the distribution.  
?RCS: You may reuse parts of this distribution only within the terms of  
?RCS: that same Artistic License; a copy of which may be found at the root  
?RCS: of the source tree for dist 3.0.  
?RCS:  
?RCS: $Log: d_endpent.U,v $  
?RCS: Revision 3.0 1993/08/18 12:06:09 ram  
?RCS: Baseline for dist 3.0 netwide release.  
?RCS:  
?MAKE:d_endpent: Inlibc  
?MAKE: -pick add $@ %<  
?S:d_endpent:  
?S: This variable conditionally defines HAS_ENDPROTOENT if endprotoent() is  
?S: available to close whatever was being used for protocol queries.  
?S.:  
?C:HAS_ENDPROTOENT:  
?C: This symbol, if defined, indicates that the endprotoent() routine is  
?C: available to close whatever was being used  
for protocol queries.  
?C.:  
?H:#$d_endpent HAS_ENDPROTOENT /**/  
?H.:  
?LINT:set d_endpent  
: see if endprotoent exists  
set endprotoent d_endpent  
eval $inlibc
```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/modified/d_endpent.U
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: Guess.U,v 3.0.1.5 1995/07/25 13:37:14 ram Exp \$
?RCS:
?RCS: Copyright (c) 1991-1993, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 3.0.
?RCS:
?RCS: \$Log: Guess.U,v \$
?RCS: Revision 3.0.1.5 1995/07/25 13:37:14 ram
?RCS: patch56: now knows about OS/2 platforms
?RCS:
?RCS: Revision 3.0.1.4 1994/10/29 15:53:55 ram
?RCS: patch36: added ?F: line for metalint file checking
?RCS: patch36: call ./xenix explicitly instead of relying on PATH
?RCS:
?RCS: Revision 3.0.1.3 1993/12/15 08:14:35 ram
?RCS: patch15: variable d_bsd was not always set properly
?RCS:
?RCS: Revision 3.0.1.2 1993/08/30 08:57:14 ram
?RCS:
patch8: fixed comment which wrongly attributed the usrinc symbol
?RCS: patch8: no more ugly messages when no /usr/include/ctype.h
?RCS:
?RCS: Revision 3.0.1.1 1993/08/27 14:37:37 ram
?RCS: patch7: added support for OSF/1 machines
?RCS:
?RCS: Revision 3.0 1993/08/18 12:04:57 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?X:
?X: This unit hazards some guesses as to what the general nature of the system
?X: is. The information it collects here is used primarily to establish default
?X: answers to other questions.
?X:
?MAKE:Guess d_eunice d_xenix d_bsd: cat test echo n c contains \
rm Loc eunicefix tr sysroot
?MAKE: -pick add \$@ %<
?S:d_eunice:
?S: This variable conditionally defines the symbols EUNICE and VAX, which
?S: alerts the C program that it must deal with idiosyncrasies of VMS.
?S:.
?S:d_xenix:
?S: This variable conditionally defines the symbol XENIX, which alerts

?S: the C program that it runs under Xenix.

?S:.

?S:d_bsd:

?S: This symbol conditionally defines the
symbol BSD when running on a
?S: BSD system.

?S:.

?C:EUNICE:

?C: This symbol, if defined, indicates that the program is being compiled
?C: under the EUNICE package under VMS. The program will need to handle
?C: things like files that don't go away the first time you unlink them,
?C: due to version numbering. It will also need to compensate for lack
?C: of a respectable link() command.

?C:.

?X: Should we define VMS here? Is Eunice actually used anymore?

?X:?C:VMS:

?X:?C: This symbol, if defined, indicates that the program is running under
?X:?C: VMS. It is currently only set in conjunction with the EUNICE symbol.

?X:?C:.

?C:XENIX:

?C: This symbol, if defined, indicates that the program is running under
?C: Xenix (at least 3.0 ?).

?C:.

?X: We don't use BSD in the perl source. It's too vague, and already
?X: defined in some header files anyway (e.g. NetBSD). This just gives
?X: us a spurious redefinition error upon compilation.

?X: --Andy Dougherty Feb 11, 1998

?X: ?C:BSD:

?X:

?C: This symbol, if defined, indicates that the program is running under
?X: ?C: a BSD system.

?X: ?C:.

?H:#\$d_eunice EUNICE /**/
?X:?H:#\$d_eunice VMS /**/
?H:#\$d_xenix XENIX /**/
?X: ?H:#\$d_bsd BSD /**/
?H:.

?F:./bsd ./usg ./v7 ./osf1 ./eunice ./xenix ./venix ./os2

?T:xxx

: make some quick guesses about what we are up against

echo " "

\$echo \$n "Hmm... \$c"

echo exit 1 >bsd

echo exit 1 >usg

echo exit 1 >v7

echo exit 1 >osf1

echo exit 1 >eunice

echo exit 1 >xenix

```

echo exit 1 >venix
echo exit 1 >os2
d_bsd="$undef"
?X:
?X: Do not use 'usrinc', or we get a circular dependency. because
?X: usrinc is defined in usrinc.U, which relies on us...
?X:
$cat $sysroot/usr/include/signal.h $sysroot/usr/include/sys/signal.h >foo 2>/dev/null
if test -f /osf_boot || $contains 'OSF/1' $sysroot/usr/include/ctype.h >/dev/null 2>&1
then
echo "Looks kind of like an OSF/1 system, but we'll see..."
echo exit 0 >osf1
elif test `echo abc | $tr a-z A-Z` = Abc ; then
xxx=`./loc addbib blurfl $pth`
if $test
-f $xxx; then
echo "Looks kind of like a USG system with BSD features, but we'll see..."
echo exit 0 >bsd
echo exit 0 >usg
else
if $contains SIGTSTP foo >/dev/null 2>&1 ; then
echo "Looks kind of like an extended USG system, but we'll see..."
else
echo "Looks kind of like a USG system, but we'll see..."
fi
echo exit 0 >usg
fi
elif $contains SIGTSTP foo >/dev/null 2>&1 ; then
echo "Looks kind of like a BSD system, but we'll see..."
d_bsd="$define"
echo exit 0 >bsd
else
echo "Looks kind of like a Version 7 system, but we'll see..."
echo exit 0 >v7
fi
case "$eunicefix" in
*unixtovms*)
$cat <<'EOI'
There is, however, a strange, musty smell in the air that reminds me of
something...hmm...yes...I've got it...there's a VMS nearby, or I'm a Blit.
EOI
echo exit 0 >eunice
d_eunice="$define"
: it so happens the Eunice I know will not run shell scripts in Unix format
;;
*)
echo " "
echo "Congratulations. You aren't running Eunice."

```

```

d_eunice="$undef"
;;
esac
: Detect
OS2. The p_ variable is set above in the Head.U unit.
: Note that this also -- wrongly -- detects e.g. dos-djgpp, which also uses
: semicolon as a patch separator
case "$p_" in
:) ;;
*)
$cat <<'EOI'

```

I have the feeling something is not exactly right, however...don't tell me...
lemme think...does HAL ring a bell?...no, of course, you're only running OS/2!
(Or you may be running DOS with DJGPP.)

```

EOI
echo exit 0 >os2
;;
esac
if test -f /xenix; then
echo "Actually, this looks more like a XENIX system..."
echo exit 0 >xenix
d_xenix="$define"
else
echo " "
echo "It's not Xenix..."
d_xenix="$undef"
fi
chmod +x xenix
$eunicefix xenix
if test -f /venix; then
echo "Actually, this looks more like a VENIX system..."
echo exit 0 >venix
else
echo " "
if ./xenix; then
: null
else
echo "Nor is it Venix..."
fi
fi
chmod +x bsd usg v7 osf1 eunice xenix venix os2
$eunicefix bsd usg v7 osf1 eunice xenix venix os2
$rm -f foo

```

Found in path(s):

```

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/modified/Guess.U

```

No license file was found, but licenses were detected in source scan.

```
?RCS:
?RCS: Copyright (c) 2012 Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?MAKE:Assert: cat
?MAKE: -pick add $@ %<
?F:./static_assert.h
: static assertion checking include file
?X:
?X: C programs can include this file to perform STATIC_ASSERT() checks
?X: which are done at compile-time and cause the compilation to fail when
?X: the expression is false.
?X:
?X: It is sufficient to compile with: $cc -c $ccflags try.c
?X: There is no need to link the file to spot the assertion failure.
?X:
$cat >static_assert.h <<'EOC'
#define STATIC_ASSERT(expr) \
do { switch (0) { case ((expr) ? 1 : 0): case 0: break; } }
while(0)
EOC
```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/Assert.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: d_strerror.U 1 2006-08-24 12:32:52Z rmanfredi $
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: $Log: d_strerror.U,v $
?RCS: Revision 3.0 1993/08/18 12:07:33 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
```

?MAKE:d_strcspn: Inlibc
?MAKE: -pick add \$@ %<
?S:d_strcspn:
?S: This variable conditionally defines the HAS_STRCSPN symbol, which
?S: indicates to the C program that the strcspn() routine is available
?S: to scan strings.
?S:.
?C:HAS_STRCSPN (STRCSPN):
?C: This symbol, if defined, indicates that the strcspn routine is
?C: available to scan
strings.
?C:.
?H:#\$d_strcspn HAS_STRCSPN /**/
?H:.
?LINT:set d_strcspn
: see if strcspn exists
set strcspn d_strcspn
eval \$inlibc

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/d_strcspn.U

No license file was found, but licenses were detected in source scan.

?RCS: Copyright (c) 2016 Dagfinn Ilmari Mannsker & H.Merijn Brand

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?MAKE:d_siginfo_si_errno d_siginfo_si_pid d_siginfo_si_uid d_siginfo_si_addr d_siginfo_si_status
d_siginfo_si_band d_siginfo_si_value d_siginfo_si_fd: d_sigaction pidtype uidtype Hasfield_t

?MAKE: -pick add \$@ %<

?S:d_siginfo_si_errno:

?S: This variable conditionally defines the HAS_SIGINFO_SI_ERRNO symbol,

?S: which indicates that the siginfo_t struct has the si_errno member.

?S:.

?S:d_siginfo_si_pid:

?S: This variable conditionally defines the HAS_SIGINFO_SI_PID symbol,

?S: which indicates that the siginfo_t struct has the si_pid member.

?S:.

?S:d_siginfo_si_uid:

?S: This variable conditionally defines the HAS_SIGINFO_SI_UID symbol,

?S: which indicates that the siginfo_t struct has the si_uid member.

?S:.

?S:d_siginfo_si_addr:

?S: This

variable conditionally defines the HAS_SIGINFO_SI_ADDR symbol,

?S: which indicates that the siginfo_t struct has the si_addr member.

?S:.

?S:d_siginfo_si_status:

?S: This variable conditionally defines the HAS_SIGINFO_SI_STATUS symbol,

?S: which indicates that the siginfo_t struct has the si_status member.

?S:.

?S:d_siginfo_si_band:

?S: This variable conditionally defines the HAS_SIGINFO_SI_BAND symbol,

?S: which indicates that the siginfo_t struct has the si_band member.

?S:.

?S:d_siginfo_si_value:

?S: This variable conditionally defines the HAS_SIGINFO_SI_VALUE symbol,

?S: which indicates that the siginfo_t struct has the si_value member.

?S:.

?S:d_siginfo_si_fd:

?S: This variable conditionally defines the HAS_SIGINFO_SI_FD symbol,

?S: which indicates that the siginfo_t struct has the si_fd member.

?S:.

?C:HAS_SIGINFO_SI_ERRNO:

?C: This symbol, if defined, indicates that siginfo_t has the

?C: si_errno member

?C:.

?C:HAS_SIGINFO_SI_PID:

?C: This

symbol, if defined, indicates that siginfo_t has the

?C: si_pid member

?C:.

?C:HAS_SIGINFO_SI_UID:

?C: This symbol, if defined, indicates that siginfo_t has the

?C: si_uid member

?C:.

?C:HAS_SIGINFO_SI_ADDR:

?C: This symbol, if defined, indicates that siginfo_t has the

?C: si_addr member

?C:.

?C:HAS_SIGINFO_SI_STATUS:

?C: This symbol, if defined, indicates that siginfo_t has the

?C: si_status member

?C:.

?C:HAS_SIGINFO_SI_BAND:

?C: This symbol, if defined, indicates that siginfo_t has the

?C: si_band member

?C:.

?C:HAS_SIGINFO_SI_VALUE:

?C: This symbol, if defined, indicates that siginfo_t has the

?C: si_value member

?C:.

?C:HAS_SIGINFO_SI_FD:

?C: This symbol, if defined, indicates that siginfo_t has the

```

?C: si_fd member
?C:.
?H:#$d_siginfo_si_errno HAS_SIGINFO_SI_ERRNO /**/
?H:#$d_siginfo_si_pid HAS_SIGINFO_SI_PID /**/
?H:#$d_siginfo_si_uid HAS_SIGINFO_SI_UID /**/
?H:#$d_siginfo_si_addr HAS_SIGINFO_SI_ADDR /**/
?H:#$d_siginfo_si_status HAS_SIGINFO_SI_STATUS /**/
?H:#$d_siginfo_si_band HAS_SIGINFO_SI_BAND /**/
?H:#$d_siginfo_si_value HAS_SIGINFO_SI_VALUE /**/
?H:#$d_siginfo_si_fd HAS_SIGINFO_SI_FD /**/
?H:.
:
see what siginfo fields we have
case "$d_sigaction" in
"$define")
echo "Checking if your siginfo_t has si_errno field...">&4
set d_siginfo_si_errno siginfo_t int si_errno $d_sigaction signal.h
eval $hasfield_t;

echo "Checking if your siginfo_t has si_pid field...">&4
set d_siginfo_si_pid siginfo_t $pidtype si_pid $d_sigaction signal.h
eval $hasfield_t;

echo "Checking if your siginfo_t has si_uid field...">&4
set d_siginfo_si_uid siginfo_t $uidtype si_uid $d_sigaction signal.h
eval $hasfield_t;

echo "Checking if your siginfo_t has si_addr field...">&4
set d_siginfo_si_addr siginfo_t "void *" si_addr $d_sigaction signal.h
eval $hasfield_t;

echo "Checking if your siginfo_t has si_status field...">&4
set d_siginfo_si_status siginfo_t int si_status $d_sigaction signal.h
eval $hasfield_t;

echo "Checking if your siginfo_t has si_band field...">&4
set
d_siginfo_si_band siginfo_t long si_band $d_sigaction signal.h
eval $hasfield_t;

echo "Checking if your siginfo_t has si_value field...">&4
set d_siginfo_si_value siginfo_t "union sigval" si_value $d_sigaction signal.h
eval $hasfield_t;

echo "Checking if your siginfo_t has si_fd field...">&4
set d_siginfo_si_fd siginfo_t int si_fd $d_sigaction signal.h
eval $hasfield_t;

```

```
::
*)
d_siginfo_si_errno="$undef"
d_siginfo_si_pid="$undef"
d_siginfo_si_uid="$undef"
d_siginfo_si_addr="$undef"
d_siginfo_si_status="$undef"
d_siginfo_si_band="$undef"
d_siginfo_si_value="$undef"
d_siginfo_si_fd="$undef"
::
esac
```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/compline/d_siginfo_si.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: i_sysndir.U 1 2006-08-24 12:32:52Z rmanfredi $
```

```
?RCS:
```

```
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
```

```
?RCS:
```

```
?RCS: You may redistribute only under the terms of the Artistic Licence,
```

```
?RCS: as specified in the README file that comes with the distribution.
```

```
?RCS: You may reuse parts of this distribution only within the terms of
```

```
?RCS: that same Artistic Licence; a copy of which may be found at the root
```

```
?RCS: of the source tree for dist 4.0.
```

```
?RCS:
```

```
?RCS: $Log: i_sysndir.U,v $
```

```
?RCS: Revision 3.0 1993/08/18 12:08:33 ram
```

```
?RCS: Baseline for dist 3.0 netwide release.
```

```
?RCS:
```

```
?MAKE:i_sysndir: Inhdr
```

```
?MAKE: -pick add $@ %<
```

```
?S:i_sysndir:
```

```
?S: This variable conditionally defines the I_SYS_NDIR symbol, and indicates
```

```
?S: whether a C program should include <sys/ndir.h>.
```

```
?S:.
```

```
?C:I_SYS_NDIR (I_SYSNDIR):
```

```
?C: This symbol, if defined, indicates to the C program that it should
```

```
?C: include <sys/ndir.h>.
```

```
?C:.
```

```
?H:#$i_sysndir
```

```
I_SYS_NDIR /**/
```

```
?H:.
```

```
?LINT:set i_sysndir
```

```
: see if this is an sysndir system
```

```
set sys/ndir.h i_sysndir
```

eval \$inhdr

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/i_sysndir.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: MailAuthor.U 1 2006-08-24 12:32:52Z rmanfredi \$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic Licence,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic Licence; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: Original Author: Graham Stoney <greyham@research.canon.oz.au>

?RCS:

?RCS: \$Log: MailAuthor.U,v \$

?RCS: Revision 3.0.1.5 1997/02/28 15:04:41 ram

?RCS: patch61: added support for src.U

?RCS:

?RCS: Revision 3.0.1.4 1994/08/29 16:05:09 ram

?RCS: patch32: avoid message sending if they said no previously

?RCS:

?RCS: Revision 3.0.1.3 1993/10/16 13:47:30 ram

?RCS: patch12: now makes sure user-specified address is in Internet format

?RCS:

?RCS: Revision

3.0.1.2 1993/09/13 15:48:49 ram

?RCS: patch10: reverted to original intent by the Author himself

?RCS:

?RCS: Revision 3.0.1.1 1993/08/27 14:38:38 ram

?RCS: patch7: now prompts user for its e-mail address

?RCS: patch7: no longer silent when mail has been sent

?RCS:

?RCS: Revision 3.0 1993/08/18 12:05:06 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?RCS:

?X:

?X: This unit asks the user to please send a message to the author.

?X: To force inclusion of this unit, you must add it's name to the

?X: dependancies on the MAKE line in your private copy of End.U.

?X: This allows a smart mailagent program to automatically let users know

?X: when their package is out of date, and to allow users to be notified of

?X: any future patches.

```

?X:
?MAKE:MailAuthor mailpatches notifypatches usermail: test cat mailer \
package Myread patchlevel baserev rm rsrc Oldconfig Configdir
?MAKE: -pick wipe $@ %<
?S:mailpatches:
?S: Indicates whether the user would like future patches to be mailed
?S: directly
to them.
?S:.
?S:notifypatches:
?S: Indicates whether the user would like notification of future patches
?S: mailed to them.
?S:.
?S:usermail:
?S: This variable is used internally by Configure to keep track of the
?S: user e-mail address, where notifications or patches should be sent.
?S: A '-' value means the return address will be extracted by parsing
?S: the mail headers.
?S:.
?T:opt mailpatches notifypatches atsh status
: notify author that his package is used
if $test -f ../config/mailauthor &&
cmp $rsrc/patchlevel.h ../config/mailauthor >/dev/null 2>&1
then
status="say that you're using $package";
case "$mailpatches" in
true) status='have patches mailed to you as they are issued';;
esac
case "$notifypatches" in
true) status='be notified when new patches are issued';;
esac
$cat <<EOM

```

You have already sent the author of \$package (<MAINTLOC>) mail to \$status. If you wish, you may modify your previous request by sending a new mail with different options.

```

EOM
rp='Should
I send a status update to <MAINTLOC>?'
dflt=n
else
$cat <<EOM

```

If you are able to send mail to the Internet, the author of \$package would really appreciate you letting me send off a quick note, just to say that you've tried it. The author is more likely to spend time maintaining \$package if it's known that many people are using it, and you can even ask to get sent new

patches automagically this way if you wish. To protect your privacy, all I'll say in the mail is the version of \$package that you're using.

EOM

```
rp='Should I send mail to <MAINTLOC>?'
dflt=y
?X: Ensure default is 'n' if question has been asked already, in case they
?X: run Configure -d next time and answered 'n' the first time. Therefore,
?X: an empty nomail will be created later on even if no mail is sent.
$test -f ../.config/nomail && dflt=n
fi
./myread
case "$ans" in
[yY]*)
echo " "
echo "Great! Your cooperation is really appreciated."
$cat <<EOM
```

Some braindead sites do not set a proper return address in the From: header of their outgoing mail, making it impossible to reply to mail they generate. If your site is broken in this way, write to your system administrator and get it fixed!!! In the mean time, you can manually specify the Internet e-mail address by which the author can get back to you, should there be a need to do so. If manually specified, it should be something like "user@domain.top". If your mail system generates addresses correctly, specify "none".

EOM

```
case "$usermail" in
'|') dflt=none;;
*) dflt="$usermail";;
esac
rp='Manually specify a return address to use:'
./myread
case "$ans" in
none|*@*.*)
case "$ans" in
none) usermail='-';;
*) usermail="$ans";;
esac
;;
*)
echo "(Address does not look like an Internet one -- ignoring it.)"
?X:
?X: If we can't trust their mailer or their return address, it's highly
?X: suggested that they only register and don't ask to get anything from
?X: the author, since it's likely to bounce in null-land --
```

```

RAM.
?X:
  usermail='- '
  mailpatches=false
  notifypatches=false
  ;;
esac
echo " "
opt=""
rp='Would you like to have new patches automatically mailed to you?'
case "$mailpatches" in
true) dflt=y;;
*) dflt=n;;
esac
. ./myread
case "$ans" in
[yY]*) opt=' mailpatches'; mailpatches=true;;
*)
  mailpatches=false
  echo " "
  rp='Ok, would you like to simply be notified of new patches?'
  case "$notifypatches" in
  false) dflt=n;;
  *) dflt=y;;
  esac
  . ./myread
  echo " "
  case "$ans" in
  [yY]*) opt=' notifypatches'; notifypatches=true;;
  *)
    echo "Fine, I'll simply say that you've tried it then."
    notifypatches=false
    ;;
  esac
  ;;
esac
echo "Sending mail to <MAINTLOC>..." >&4
?X: Bizarre hack here. We can't just put @SH in the hereis lines below, because
?X: metaconfig will interpret it as a command, and there's no quoting mechanism.
?X: Do it via a variable instead.
atsh='@SH'
$mailer <MAINTLOC> <<EOM >/dev/null 2>&1
Subject: Command
Precedence: junk
To: <MAINTLOC>

$atsh

```

```

package $usermail $package $baserev $patchlevel$opt
EOM
$rm -f ../config/mailauthor ../config/nomail
cp $src/patchlevel.h ../config/mailauthor
;;
*)
case "$dfmt" in
"y")
echo "Oh well, maybe next time."
cp /dev/null ../config/nomail
;;
esac
;;
esac

```

Found in path(s):

```

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/MailAuthor.U

```

No license file was found, but licenses were detected in source scan.

```

?RCS: $Id$
?RCS:
?RCS: Copyright (c) 2016 H.Merijn Brand & Todd Rinaldo
?RCS:
?RCS: You may distribute under the terms of either the GNU General Public
?RCS: License or the Artistic License, as specified in the README file.
?RCS:
?MAKE:default_inc_excludes_dot: Myread cat
?MAKE: -pick add $@ %<
?S:default_inc_excludes_dot:
?S: When defined, remove the legacy '.' from @INC
?S:.
?C:DEFAULT_INC_EXCLUDES_DOT:
?C: This symbol, if defined, removes the legacy default behavior of
?C: including '.' at the end of @INC.
?C:.
?H:#$default_inc_excludes_dot DEFAULT_INC_EXCLUDES_DOT /**/
?H:.
: Include . in @INC
$cat <<EOM

```

Historically Perl has provided a final fallback of the current working directory '.' when searching for a library. This, however, can lead to problems when a Perl program which loads optional modules is called from a shared directory. This can lead to executing unexpected code.

EOM

```

# When changing to exclude by
default:
case "$default_inc_excludes_dot" in
  $undef|false|[nN]*) dflt="n" ;;
  *)                  dflt="y" ;;
esac
# To turn exclude off by default:
#case "$default_inc_excludes_dot" in
#  $define|true|[yY]*) dflt="y" ;;
#  *)                  dflt="n" ;;
#esac

```

```

rp='Exclude '.' from @INC by default? '
./myread
case "$ans" in
  [nN]|undef) default_inc_excludes_dot="$undef" ;;
  *)         default_inc_excludes_dot="$define" ;;
esac

```

Found in path(s):

```

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/perl/defaultincdot.U

```

No license file was found, but licenses were detected in source scan.

```

?RCS: $Id: d_getprotoent_r.U,v 0RCS:
?RCS: Copyright (c) 2002,2003 Jarkko Hietaniemi
?RCS:
?RCS: You may distribute under the terms of either the GNU General Public
?RCS: License or the Artistic License, as specified in the README file.
?RCS:
?RCS: Generated by the reentr.pl from the Perl 5.8 distribution.
?RCS:
?MAKE:d_getprotoent_r getprotoent_r_proto: Inlibc Protochk Hasproto \
i_systypes usethreads i_netdb extern_C
?MAKE: -pick add $@ %<
?S:d_getprotoent_r:
?S: This variable conditionally defines the HAS_GETPROTOENT_R symbol,
?S: which indicates to the C program that the getprotoent_r()
?S: routine is available.
?S:.
?S:getprotoent_r_proto:
?S: This variable encodes the prototype of getprotoent_r.
?S: It is zero if d_getprotoent_r is undef, and one of the
?S: REENTRANT_PROTO_T_ABC macros of reentr.h if d_getprotoent_r
?S: is defined.
?S:.
?C:HAS_GETPROTOENT_R:
?C: This symbol, if defined, indicates that the getprotoent_r

```

```

routine
?C: is available to getprotoent re-entrantly.
?C:.
?C:GETPROTOENT_R_PROTO:
?C: This symbol encodes the prototype of getprotoent_r.
?C: It is zero if d_getprotoent_r is undef, and one of the
?C: REENTRANT_PROTO_T_ABC macros of reentr.h if d_getprotoent_r
?C: is defined.
?C:.
?H:#$d_getprotoent_r HAS_GETPROTOENT_R /**/
?H:#define GETPROTOENT_R_PROTO $getprotoent_r_proto /**/
?H:.
?T:try hdrs d_getprotoent_r_proto
: see if getprotoent_r exists
set getprotoent_r d_getprotoent_r
eval $inlibc
case "$d_getprotoent_r" in
"$define")
hdrs="$i_systypes sys/types.h define stdio.h $i_netdb netdb.h"
case "$d_getprotoent_r_proto:$usethreads" in
":define") d_getprotoent_r_proto=define
set d_getprotoent_r_proto getprotoent_r $hdrs
eval $hasproto ;;
*) ;;
esac
case "$d_getprotoent_r_proto" in
define)
case "$getprotoent_r_proto" in
"|0) try='int getprotoent_r(struct protoent*, char*, size_t, struct protoent**);'
./protochk "$extern_C $try" $hdrs && getprotoent_r_proto=I_SBWR
;;
esac
case "$getprotoent_r_proto" in
"|0) try='int getprotoent_r(struct protoent*, char*, int);'
./protochk "$extern_C $try" $hdrs && getprotoent_r_proto=I_SBI ;;
esac
case "$getprotoent_r_proto" in
"|0) try='struct protoent* getprotoent_r(struct protoent*, char*, int);'
./protochk "$extern_C $try" $hdrs && getprotoent_r_proto=S_SBI ;;
esac
case "$getprotoent_r_proto" in
"|0) try='int getprotoent_r(struct protoent*, struct protoent_data*);'
./protochk "$extern_C $try" $hdrs && getprotoent_r_proto=I_SD ;;
esac
case "$getprotoent_r_proto" in
"|0) d_getprotoent_r=undef
getprotoent_r_proto=0
echo "Disabling getprotoent_r, cannot determine prototype." >&4 ;;

```

```

*) case "$getprotoent_r_proto" in
REENTRANT_PROTO*) ;;
*) getprotoent_r_proto="REENTRANT_PROTO_${getprotoent_r_proto}" ;;
esac
echo "Prototype: $try" ;;
esac
;;
*) case "$usetreads" in
define) echo "getprotoent_r has no prototype, not using it." >&4 ;;
esac
d_getprotoent_r=undef
getprotoent_r_proto=0
;;
esac
;;
*) getprotoent_r_proto=0
;;
esac

```

Found

in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/threads/d_getprotoent_r.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_getnetbyname_r.U,v 0RCS:

?RCS: Copyright (c) 2002,2003 Jarkko Hietaniemi

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?RCS: Generated by the reentr.pl from the Perl 5.8 distribution.

?RCS:

?MAKE:d_getnetbyname_r getnetbyname_r_proto: Inlibc Protochk Hasproto \
i_systypes usethreads i_netdb extern_C

?MAKE: -pick add \$@ %<

?S:d_getnetbyname_r:

?S: This variable conditionally defines the HAS_GETNETBYNAME_R symbol,

?S: which indicates to the C program that the getnetbyname_r()

?S: routine is available.

?S:.

?S:getnetbyname_r_proto:

?S: This variable encodes the prototype of getnetbyname_r.

?S: It is zero if d_getnetbyname_r is undef, and one of the

?S: REENTRANT_PROTO_T_ABC macros of reentr.h if d_getnetbyname_r

?S: is defined.

?S:.

?C:HAS_GETNETBYNAME_R:

```

?C: This symbol, if defined, indicates that
the getnetbyname_r routine
?C: is available to getnetbyname re-entrantly.
?C:.
?C:GETNETBYNAME_R_PROTO:
?C: This symbol encodes the prototype of getnetbyname_r.
?C: It is zero if d_getnetbyname_r is undef, and one of the
?C: REENTRANT_PROTO_T_ABC macros of reentr.h if d_getnetbyname_r
?C: is defined.
?C:.
?H:#$d_getnetbyname_r HAS_GETNETBYNAME_R /**/
?H:#define GETNETBYNAME_R_PROTO $getnetbyname_r_proto /**/
?H:.
?T:try hdrs d_getnetbyname_r_proto
: see if getnetbyname_r exists
set getnetbyname_r d_getnetbyname_r
eval $inlibc
case "$d_getnetbyname_r" in
"$define")
hdrs="$i_systypes sys/types.h define stdio.h $i_netdb netdb.h"
case "$d_getnetbyname_r_proto:$usethreads" in
":define") d_getnetbyname_r_proto=define
set d_getnetbyname_r_proto getnetbyname_r $hdrs
eval $hasproto ;;
*) ;;
esac
case "$d_getnetbyname_r_proto" in
define)
case "$getnetbyname_r_proto" in
"|0) try='int getnetbyname_r(const char*, struct netent*, char*, size_t, struct netent**, int*);'
./protochk
"$extern_C $try" $hdrs && getnetbyname_r_proto=I_CSBWRE ;;
esac
case "$getnetbyname_r_proto" in
"|0) try='int getnetbyname_r(const char*, struct netent*, char*, int);'
./protochk "$extern_C $try" $hdrs && getnetbyname_r_proto=I_CSBI ;;
esac
case "$getnetbyname_r_proto" in
"|0) try='struct netent* getnetbyname_r(const char*, struct netent*, char*, int);'
./protochk "$extern_C $try" $hdrs && getnetbyname_r_proto=S_CSBI ;;
esac
case "$getnetbyname_r_proto" in
"|0) try='int getnetbyname_r(const char*, struct netent*, struct netent_data*);'
./protochk "$extern_C $try" $hdrs && getnetbyname_r_proto=I_CSD ;;
esac
case "$getnetbyname_r_proto" in
"|0) d_getnetbyname_r=undef
getnetbyname_r_proto=0

```

```

echo "Disabling getnetbyname_r, cannot determine prototype." >&4 ;;
*) case "$getnetbyname_r_proto" in
REENTRANT_PROTO*) ;;
*) getnetbyname_r_proto="REENTRANT_PROTO_$getnetbyname_r_proto" ;;
esac
echo "Prototype: $try" ;;
esac
;;
*) case "$usetthreads" in
define)
echo "getnetbyname_r has no prototype, not using it." >&4 ;;
esac
d_getnetbyname_r=undef
getnetbyname_r_proto=0
;;
esac
;;
*) getnetbyname_r_proto=0
;;
esac

```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/threads/d_getnetbyname_r.U
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_pathconf.U 1 2006-08-24 12:32:52Z rmanfredi \$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic Licence,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic Licence; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: Original Author: Andy Dougherty <doughera@lafcol.lafayette.edu>

?RCS:

?RCS: \$Log: d_pathconf.U,v \$

?RCS: Revision 3.0.1.1 1994/10/29 16:14:54 ram

?RCS: patch36: created by ADO

?RCS:

?MAKE:d_pathconf d_fpathconf: Inlibc

?MAKE: -pick add \$@ %<

?S:d_pathconf:

?S: This variable conditionally defines the HAS_PATHCONF symbol, which

?S: indicates to the C program that the pathconf() routine is available

?S: to determine file-system related limits and options

associated

?S: with a given filename.

?S:.

?S:d_fpathconf:

?S: This variable conditionally defines the HAS_FPATHCONF symbol, which

?S: indicates to the C program that the pathconf() routine is available

?S: to determine file-system related limits and options associated

?S: with a given open file descriptor.

?S:.

?C:HAS_PATHCONF:

?C: This symbol, if defined, indicates that pathconf() is available

?C: to determine file-system related limits and options associated

?C: with a given filename.

?C:.

?C:HAS_FPATHCONF:

?C: This symbol, if defined, indicates that pathconf() is available

?C: to determine file-system related limits and options associated

?C: with a given open file descriptor.

?C:.

?H:#\$d_pathconf HAS_PATHCONF /**/

?H:#\$d_fpathconf HAS_FPATHCONF /**/

?H:.

?LINT:set d_pathconf

?LINT:set d_fpathconf

: see if pathconf exists

set pathconf d_pathconf

eval \$inlibc

@if d_fpathconf || HAS_FPATHCONF

: see if fpathconf exists

set fpathconf d_fpathconf

eval \$inlibc

@end

Found in path(s):

*

/opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/d_pathconf.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: scriptdir.U,v 3.1 1999/07/09 18:20:13 doughera Exp doughera \$

?RCS:

?RCS: Copyright (c) 1991-1993, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 3.0.
?RCS:
?RCS: \$Log: scriptdir.U,v \$
?RCS: Revision 3.1 1999/07/09 18:20:13 doughera
?RCS: Updated for installprefix
?RCS:
?RCS: Revision 3.0.1.3 1995/09/25 09:17:15 ram
?RCS: patch59: unit is now forced to the top of Configure, if possible
?RCS:
?RCS: Revision 3.0.1.2 1995/01/30 14:46:13 ram
?RCS: patch49: can now handle installation prefix changes (from WED)
?RCS:
?RCS: Revision 3.0.1.1 1994/08/29 16:32:04 ram
?RCS: patch32: now uses installation prefix
?RCS:
?RCS:
Revision 3.0 1993/08/18 12:09:45 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:scriptdir scriptdirexp installscript: cat test Getfile Loc \
Oldconfig +bin Prefixit Setprefixvar prefixexp Prefixup
?MAKE: -pick add \$@ %<
?Y:TOP
?D:scriptdir="
?S:scriptdir:
?S: This variable holds the name of the directory in which the user wants
?S: to put publicly scripts for the package in question. It is either
?S: the same directory as for binaries, or a special one that can be
?S: mounted across different architectures, like /usr/share. Programs
?S: must be prepared to deal with ~name expansion.
?S:.
?D:scriptdirexp="
?S:scriptdirexp:
?S: This variable is the same as scriptdir, but is filename expanded
?S: at configuration time, for programs not wanting to bother with it.
?S:.
?S:installscript:
?S: This variable is usually the same as scriptdirexp, unless you are on
?S: a system running AFS, in which case they may differ slightly. You
?S: should always use this variable
within your makefiles for portability.
?S:.
?C:SCRIPTDIR:
?C: This symbol holds the name of the directory in which the user wants
?C: to put publicly executable scripts for the package in question. It
?C: is often a directory that is mounted across diverse architectures.
?C: Programs must be prepared to deal with ~name expansion.

```

?C:.
?C:SCRIPTDIR_EXP:
?C: This is the same as SCRIPTDIR, but is filename expanded at
?C: configuration time, for use in programs not prepared to do
?C: ~name substitutions at run-time.
?C:.
?H:#define SCRIPTDIR "$scriptdir" /**/
?H:#define SCRIPTDIR_EXP "$scriptdirexp" /**/
?H:.
?T:installscriptdir
?LINT:change prefixvar
?LINT:set scriptdir
?LINT:set scriptdirexp
: determine where public executable scripts go
set scriptdir scriptdir
eval $prefixit
case "$scriptdir" in
")
dflt="$bin"
: guess some guesses
$test -d /usr/share/scripts && dflt=/usr/share/scripts
$test -d /usr/share/bin && dflt=/usr/share/bin
$test -d /usr/local/script && dflt=/usr/local/script
$test
-d /usr/local/scripts && dflt=/usr/local/scripts
$test -d $prefixexp/script && dflt=$prefixexp/script
set dflt
eval $prefixup
;;
*) dflt="$scriptdir"
;;
esac
$cat <<EOM

```

Some installations have a separate directory just for executable scripts so that they can mount it across multiple architectures but keep the scripts in one spot. You might, for example, have a subdirectory of /usr/share for this. Or you might just lump your scripts in with all your other executables.

```

EOM
fn=d~
rp='Where do you keep publicly executable scripts?'
./getfile
if $test "X$ansexp" != "X$scriptdirexp"; then
installscript="
fi
installscriptdir="
prefixvar=scriptdir

```

./setprefixvar

: A little fix up for an irregularly named variable.

installscript="\$installscriptdir"

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/installdirs/scriptdir.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_inetd.U 1 2006-08-24 12:32:52Z rmanfredi \$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic Licence,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic Licence; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: d_inetd.U,v \$

?RCS: Revision 3.0 1993/08/18 12:06:23 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?MAKE:d_inetd: cat test package Myread Setvar

?MAKE: -pick add \$@ %<

?S:d_inetd:

?S: This symbol conditionally defines USE_INETD which indicates to the C

?S: program that the initial socket connection will be done via inetd.

?S:.

?C:USE_INETD (INETD):

?C: This symbol if defined indicates to the C program that inetd will be

?C: in charge of the

initial socket connection. The file descriptors 0 and

?C: 1 have been dup()ed from the original connected socket descriptor and

?C: are ready for send() and recv().

?C:.

?H:#\$d_inetd USE_INETD /**/

?H:.

?LINT:set d_inetd

: ask whether initial socket connection is to be done via inetd

echo " "

dflt=n

case "\$d_inetd" in

") if \$test -f /etc/inetd.conf; then

 \$cat <<EOM

Your system provides a so called "Internet super-server", the inetd daemon.

Network services like ftp or rlogin are usually handled via ftpd and rlogind

daemons. Without inetd, these daemons must always be running for the service

to be on. On the contrary, inetd listens to specific ports defined in file /etc/inetd.conf and will run the appropriate daemon upon request. This scheme avoids eating up the process table and memory with useless daemons.

I can set up things so that internet connections for \$package will be done using inetd, in which case you will have to edit /etc/inetd.conf to add some specific informations.

```
EOM
dflt=y
else
$cat
<<EOM
```

I do not see any trace of a configuration file for inetd, hence I assume your system does not support the so called "Internet super-server". This means \$package will need to have a daemon process running on this machine to allow network connections.

```
EOM
fi;;
*) case "$d_inetd" in
"$define") dflt=y;;
esac;;
esac
rp='Do you wish to use inetd for network connections?'
./myread
val="$undef"
case "$ans" in
y*|Y*) val="$define";;
esac
set d_inetd
eval $setvar
```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/d_inetd.U
```

No license file was found, but licenses were detected in source scan.

```
/*
* $Id: dup2.C,v 3.0.1.1 1994/01/24 13:58:37 ram Exp ram $
*
* Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
*
* You may redistribute only under the terms of the Artistic Licence,
* as specified in the README file that comes with the distribution.
* You may reuse parts of this distribution only within the terms of
* that same Artistic Licence; a copy of which may be found at the root
* of the source tree for dist 4.0.
```

*
* Original Author: Larry Wall <lwall@netlabs.com>
*
* \$Log: dup2.C,v \$
* Revision 3.0.1.1 1994/01/24 13:58:37 ram
* patch16: created
*
*/

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/lib/C/fake/dup2.C

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_strstr.U 1 2006-08-24 12:32:52Z rmanfredi \$
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: \$Log: d_strstr.U,v \$
?RCS: Revision 3.0 1993/08/18 12:07:37 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:d_strstr: Inlibc
?MAKE: -pick add \$@ %<
?S:d_strstr:
?S: This variable conditionally defines HAS_STRSTR if strstr() is
?S: available to find substrings.
?S:.
?C:HAS_STRSTR (STRSTR):
?C: This symbol, if defined, indicates that the strstr routine is
?C: available to find substrings.
?C:.
?H:#\$d_strstr HAS_STRSTR /**/
?H:.
?LINT:set d_strstr
:
see if strstr exists
set strstr d_strstr
eval \$inlibc

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-

debian-perl-5.26.1/dist/U/d_strstr.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: vendorhtml3.U,v 1.1 1999/07/08 18:32:57 doughera Exp doughera \$

?RCS:

?RCS: Copyright (c) 1999, Andy Dougherty

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 3.0.

?RCS:

?RCS: \$Log: vendorhtml3.U,v \$

?RCS: Revision 1.1 1999/07/08 18:32:57 doughera

?RCS: Initial revision

?RCS:

?MAKE:vendorhtml3 vendorhtml3exp installvendorhtml3: html3dir Getfile \

Oldconfig Setprefixvar Prefixit test vendorprefix prefix sed

?MAKE: -pick add \$@ %<

?Y:TOP

?S:vendorhtml3:

?S: This variable contains the name of the directory for html

?S: library pages. It may have a ~ on the front.

?S: The standard distribution will put nothing in this directory.

?S: Vendors

who distribute perl may wish to place their own

?S: html pages for modules and extensions in this directory with

?S: MakeMaker Makefile.PL INSTALLDIRS=vendor

?S: or equivalent. See INSTALL for details.

?S:.

?S:vendorhtml3exp:

?S: This variable is the ~name expanded version of vendorhtml3, so that you

?S: may use it directly in Makefiles or shell scripts.

?S:.

?D:installvendorhtml3="

?S:installvendorhtml3:

?S: This variable is really the same as vendorhtml3exp but may differ on

?S: those systems using AFS. For extra portability, only this variable

?S: should be used in makefiles.

?S:.

?LINT:change prefixvar

?LINT:set installvendorhtml3

: Set the vendorhtml3 variables

case "\$vendorprefix" in

") vendorhtml3="

vendorhtml3exp="

::

*) : determine where vendor-supplied module html pages go.
: There is no standard location, so try to copy the previously-selected
: directory structure for the core html pages.
: XXX Better default suggestions would be welcome.

```
case "$vendorhtml3"
in
") dflt=`echo "$html3dir" | $sed "s#^$prefix#$vendorprefix#" ` ;;
*) dflt=$vendorhtml3 ;;
esac
case "$dflt" in
"|") dflt=none ;;
esac
fn=dn+~
rp='Pathname for the vendor-supplied html pages?'
./getfile
vendorhtml3="$ans"
vendorhtml3exp="$ansexp"
;;
esac
: Use ' ' for none so value is preserved next time through Configure
$test X"$vendorhtml3" = "X" && vendorhtml3=' '
prefixvar=vendorhtml3
./installprefix
```

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/installdirs/vendorhtml3.U

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: d_killpg.U 1 2006-08-24 12:32:52Z rmanfredi $
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: $Log: d_killpg.U,v $
?RCS: Revision 3.0 1993/08/18 12:06:27 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:d_killpg: Inlibc
?MAKE: -pick add $@ %<
?S:d_killpg:
?S: This variable conditionally defines the HAS_KILLPG symbol, which
?S: indicates to the C program that the killpg() routine is available
```

?S: to kill process groups.
?S:.
?C:HAS_KILLPG (KILLPG):
?C: This symbol, if defined, indicates that the killpg routine is available
?C: to kill
process groups. If unavailable, you probably should use kill
?C: with a negative process number.
?C:.
?H:#\$d_killpg HAS_KILLPG /**/
?H:.
?LINT:set d_killpg
: see if killpg exists
set killpg d_killpg
eval \$inlibc

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/d_killpg.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: byteorder.U,v 3.0.1.2 1997/02/28 15:24:55 ram Exp \$
?RCS:
?RCS: Copyright (c) 1991-1993, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 3.0.
?RCS:
?RCS: \$Log: byteorder.U,v \$
?RCS: Revision 3.0.1.2 1997/02/28 15:24:55 ram
?RCS: patch61: no longer ask the user if the test runs ok
?RCS:
?RCS: Revision 3.0.1.1 1994/10/29 16:02:58 ram
?RCS: patch36: added ?F: line for metalint file checking
?RCS:
?RCS: Revision 3.0 1993/08/18 12:05:28 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:byteorder: cat Myread Oldconfig Loc Compile rm_try run \
multiarch uvtype uvsize i_stdlib
?MAKE: -pick add \$@ %<
?S:byteorder:
?S: This
variable holds the byte order in a UV. In the following,
?S: larger digits indicate more significance. The variable byteorder
?S: is either 4321 on a big-endian machine, or 1234 on a little-endian,

?S: or 87654321 on a Cray ... or 3412 with weird order !

?S:.

?C:BYTEORDER:

?C: This symbol holds the hexadecimal constant defined in byteorder,

?C: in a UV, i.e. 0x1234 or 0x4321 or 0x12345678, etc...

?C: If the compiler supports cross-compiling or multiple-architecture

?C: binaries, use compiler-defined macros to

?C: determine the byte order.

?C:.

```
?H:%<:#if defined(MULTIARCH)
?H:%<:# ifdef __LITTLE_ENDIAN__
?H:%<:# if LONGSIZE == 4
?H:%<:# define BYTEORDER 0x1234
?H:%<:# else
?H:%<:# if LONGSIZE == 8
?H:%<:# define BYTEORDER 0x12345678
?H:%<:# endif
?H:%<:# endif
?H:%<:# else
?H:%<:# ifdef __BIG_ENDIAN__
?H:%<:# if LONGSIZE == 4
?H:%<:# define BYTEORDER 0x4321
?H:%<:# else
?H:%<:# if LONGSIZE
== 8
?H:%<:# define BYTEORDER 0x87654321
?H:%<:# endif
?H:%<:# endif
?H:%<:# endif
?H:%<:# endif
?H:%<:#endif
?H:%<:#define BYTEORDER 0x$byteorder /* large digits for MSB */
?H:%<:#endif
?H:.
```

?T:xxx_prompt

?F:!try

: check for ordering of bytes in a UV

```
echo " "
case "$multiarch" in
*$define*)
$cat <<EOM
```

You seem to be doing a multiarchitecture build,
skipping the byteorder check.

EOM

```
byteorder='ffff'
;;
*)
```

```
case "$byteorder" in
")
```

```
$cat <<'EOM'
```

In the following, larger digits indicate more significance. A big-endian machine like a Pyramid or a Motorola 680?0 chip will come out to 4321. A little-endian machine like a Vax or an Intel 80?86 chip would be 1234. Other machines may have weird orders like 3412. A Cray will report 87654321, an Alpha will report 12345678. If the test program works the default is probably right.

I'm now running the test program...

```
EOM
```

```
$cat >try.c <<EOCP
```

```
#include <stdio.h>
```

```
#$i_stdlib I_STDLIB
```

```
#ifdef I_STDLIB
```

```
#include <stdlib.h>
```

```
#endif
```

```
#include
```

```
<sys/types.h>
```

```
typedef $uvtype UV;
```

```
int main()
```

```
{
```

```
int i;
```

```
union {
```

```
UV l;
```

```
char c[$uvsize];
```

```
} u;
```

```
if ($uvsize > 4)
```

```
u.l = (((UV)0x08070605) << 32) | (UV)0x04030201;
```

```
else
```

```
u.l = (UV)0x04030201;
```

```
for (i = 0; i < $uvsize; i++)
```

```
printf("%c", u.c[i]+'0');
```

```
printf("\n");
```

```
exit(0);
```

```
}
```

```
EOCP
```

```
xxx_prompt=y
```

```
set try
```

```
if eval $compile && $run ./try > /dev/null; then
```

```
dflt=`$run ./try`
```

```
case "$dflt" in
```

```
[1-4][1-4][1-4][1-4]|12345678|87654321)
```

```
echo "(The test program ran ok.)"
```

```
echo "byteorder=$dflt"
```

```
xxx_prompt=n
```

```
::
```

```
????|?????) echo "(The test program ran ok.)" ;;
*) echo "(The test program didn't run right for some reason.)" ;;
esac
else
dflt='4321'
cat <<'EOM'
```

(I can't seem to compile the test program. Guessing big-endian...)

EOM

```
fi
case "$xxx_prompt" in
y)
rp="What is the order of bytes in $svtype?"
./myread
byteorder="$sans"
;;
*) byteorder=$dflt
;;
esac
;;
esac
$rm_try
;;
esac
```

Found in path(s):

*

/opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/compline/byteorder.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_setlnbuf.U 1 2006-08-24 12:32:52Z rmanfredi \$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic Licence,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic Licence; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: Original Author: Andy Dougherty <doughera@lafcol.lafayette.edu>

?RCS:

?RCS: \$Log: d_setlnbuf.U,v \$

?RCS: Revision 3.0.1.1 1994/08/29 16:11:57 ram

?RCS: patch32: created by ADO

?RCS:

?MAKE:d_setlinebuf: Inlibc

?MAKE: -pick add \$@ %<

?S:d_setlinebuf:

?S: This variable conditionally defines the HAS_SETLINEBUF symbol, which

?S: indicates to the C program that the setlinebuf() routine is available

?S: to change stderr or stdout from block-buffered or unbuffered

to a

?S: line-buffered mode.

?S:.

?C:HAS_SETLINEBUF :

?C: This symbol, if defined, indicates that the setlinebuf routine is

?C: available to change stderr or stdout from block-buffered or unbuffered

?C: to a line-buffered mode.

?C:.

?H:#\$d_setlinebuf HAS_SETLINEBUF /**/

?H:.

?LINT:set d_setlinebuf

: see if setlinebuf exists

set setlinebuf d_setlinebuf

eval \$inlibc

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/d_setlnbuf.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: d_gethbynm.U,v \$

?RCS: Revision 3.0 1993/08/18 12:06:08 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?MAKE:d_gethbynm: Inlibc

?MAKE: -pick add \$@ %<

?S:d_gethbynm (d_gethstby):

?S: This variable conditionally defines the HAS_GETHOSTBYNAME symbol, which

?S: indicates to the C program that the gethostbyname() routine is available

?S: to lookup host names in some data base or other.

?S:.

?C:HAS_GETHOSTBYNAME (GETHOSTBYNAME):

?C: This symbol, if defined, indicates that the gethostbyname()

routine is
?C: available to lookup host names in some data base or other.
?C:.
?H:#\$d_gethbynm HAS_GETHOSTBYNAME /**/
?H:.
?LINT:set d_gethbynm
: see if gethostbyname exists
set gethostbyname d_gethbynm
eval \$inlibc

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/d_gethbynm.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_getlogin_r.U,v 0RCS:
?RCS: Copyright (c) 2002,2003 Jarkko Hietaniemi
?RCS:
?RCS: You may distribute under the terms of either the GNU General Public
?RCS: License or the Artistic License, as specified in the README file.
?RCS:
?RCS: Generated by the reentr.pl from the Perl 5.8 distribution.
?RCS:
?MAKE:d_getlogin_r getlogin_r_proto: Inlibc Protochk Hasproto i_systypes \
usethreads i_unistd extern_C
?MAKE: -pick add \$@ %<
?S:d_getlogin_r:
?S: This variable conditionally defines the HAS_GETLOGIN_R symbol,
?S: which indicates to the C program that the getlogin_r()
?S: routine is available.
?S:.
?S:getlogin_r_proto:
?S: This variable encodes the prototype of getlogin_r.
?S: It is zero if d_getlogin_r is undef, and one of the
?S: REENTRANT_PROTO_T_ABC macros of reentr.h if d_getlogin_r
?S: is defined.
?S:.
?C:HAS_GETLOGIN_R:
?C: This symbol, if defined, indicates that the getlogin_r routine
?C: is available
to getlogin re-entrantly.
?C:.
?C:GETLOGIN_R_PROTO:
?C: This symbol encodes the prototype of getlogin_r.
?C: It is zero if d_getlogin_r is undef, and one of the
?C: REENTRANT_PROTO_T_ABC macros of reentr.h if d_getlogin_r
?C: is defined.
?C:.

```

?H:#$d_getlogin_r HAS_GETLOGIN_R  /**/
?H:#define GETLOGIN_R_PROTO $getlogin_r_proto  /**/
?H:.
?T:try hdrs d_getlogin_r_proto
: see if getlogin_r exists
set getlogin_r d_getlogin_r
eval $inlibc
case "$d_getlogin_r" in
"$define")
hdrs="$i_systypes sys/types.h define stdio.h $i_unistd unistd.h"
case "$d_getlogin_r_proto:$usethreads" in
":define") d_getlogin_r_proto=define
set d_getlogin_r_proto getlogin_r $hdrs
eval $hasproto ;;
*) ;;
esac
case "$d_getlogin_r_proto" in
define)
case "$getlogin_r_proto" in
"|0) try='int getlogin_r(char*, size_t);'
./protochk "$extern_C $try" $hdrs && getlogin_r_proto=I_BW ;;
esac
case "$getlogin_r_proto" in
"|0) try='int getlogin_r(char*, int);'
./protochk "$extern_C $try" $hdrs && getlogin_r_proto=I_BI
;;
esac
case "$getlogin_r_proto" in
"|0) try='char* getlogin_r(char*, size_t);'
./protochk "$extern_C $try" $hdrs && getlogin_r_proto=B_BW ;;
esac
case "$getlogin_r_proto" in
"|0) try='char* getlogin_r(char*, int);'
./protochk "$extern_C $try" $hdrs && getlogin_r_proto=B_BI ;;
esac
case "$getlogin_r_proto" in
"|0) d_getlogin_r=undef
getlogin_r_proto=0
echo "Disabling getlogin_r, cannot determine prototype." >&4 ;;
* ) case "$getlogin_r_proto" in
REENTRANT_PROTO*) ;;
*) getlogin_r_proto="REENTRANT_PROTO_$getlogin_r_proto" ;;
esac
echo "Prototype: $try" ;;
esac
;;
*) case "$usethreads" in
define) echo "getlogin_r has no prototype, not using it." >&4 ;;

```

```
esac
d_getlogin_r=undef
getlogin_r_proto=0
;;
esac
;;
*) getlogin_r_proto=0
;;
esac
```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/threads/d_getlogin_r.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: d_setpent.U,v 3.0 1993/08/18 12:06:09 ram Exp $
```

```
?RCS:
```

```
?RCS: Copyright (c) 1991-1993, Raphael Manfredi
```

```
?RCS:
```

```
?RCS: You may redistribute only under the terms of the Artistic License,
```

```
?RCS: as specified in the README file that comes with the distribution.
```

```
?RCS: You may reuse parts of this distribution only within the terms of
```

```
?RCS: that same Artistic License; a copy of which may be found at the root
```

```
?RCS: of the source tree for dist 3.0.
```

```
?RCS:
```

```
?RCS: $Log: d_setpent.U,v $
```

```
?RCS: Revision 3.0 1993/08/18 12:06:09 ram
```

```
?RCS: Baseline for dist 3.0 netwide release.
```

```
?RCS:
```

```
?MAKE:d_setpent: Inlibc
```

```
?MAKE: -pick add $@ %<
```

```
?S:d_setpent:
```

```
?S: This variable conditionally defines HAS_SETPROTOENT if setprotoent() is
```

```
?S: available.
```

```
?S:.
```

```
?C:HAS_SETPROTOENT:
```

```
?C: This symbol, if defined, indicates that the setprotoent() routine is
```

```
?C: available.
```

```
?C:.
```

```
?H:#$d_setpent HAS_SETPROTOENT /**/
```

```
?H:.
```

```
?LINT:set d_setpent
```

```
: see if setprotoent
```

```
exists
```

```
set setprotoent d_setpent
```

```
eval $inlibc
```

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/modified/d_setpent.U

No license file was found, but licenses were detected in source scan.

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?MAKE:d_j0 d_j0l: Inlibc

?MAKE: -pick add \$@ %<

?S:d_j0:

?S: This variable conditionally defines the HAS_J0 symbol, which

?S: indicates to the C program that the j0() routine is available.

?S:.

?S:d_j0l:

?S: This variable conditionally defines the HAS_J0L symbol, which

?S: indicates to the C program that the j0l() routine is available.

?S:.

?C:HAS_J0:

?C: This symbol, if defined, indicates to the C program that the

?C: j0() function is available for Bessel functions of the first

?C: kind of the order zero, for doubles.

?C:.

?C:HAS_J0L:

?C: This symbol, if defined, indicates to the C program that the

?C: j0l() function is available for Bessel functions of the first

?C: kind of the order zero, for long doubles.

?C:.

?H:#\$d_j0 HAS_J0 /**/

?H:#\$d_j0l HAS_J0L /**/

?H:.

?LINT:set

d_j0

?LINT:set d_j0l

: see if j0 exists

set j0 d_j0

eval \$inlibc

: see if j0l exists

set j0l d_j0l

eval \$inlibc

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_j0.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: sitescript.U,v \$

?RCS:

```

?RCS: Copyright (c) 1999 Andy Dougherty
?RCS:
?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 3.0.
?RCS:
?RCS: $Log: sitescript.U,v $
?RCS:
?MAKE:sitescript sitescriptexp installsitescript : Getfile Oldconfig test \
  Setprefixvar sitebin siteprefix
?MAKE: -pick add $@ %<
?Y:TOP
?D:sitescript="
?S:sitescript:
?S: This variable holds the name of the directory in which the user wants
?S: to put add-on publicly executable files for the package in question. It
?S: is most often a local directory such as /usr/local/bin. Programs using
?S: this variable must be prepared to deal with ~name substitution.
?S: The standard
  distribution will put nothing in this directory.
?S: After perl has been installed, users may install their own local
?S: scripts in this directory with
?S: MakeMaker Makefile.PL
?S: or equivalent. See INSTALL for details.
?S:.
?D:sitescriptexp="
?S:sitescriptexp:
?S: This is the same as the sitescript variable, but is filename expanded at
?S: configuration time, for use in your makefiles.
?S:.
?D:installsitescript="
?S:installsitescript:
?S: This variable is usually the same as sitescriptexp, unless you are on
?S: a system running AFS, in which case they may differ slightly. You
?S: should always use this variable within your makefiles for portability.
?S:.
?LINT:change prefixvar
?LINT:set installsitescript
?LINT:set sitescript
?LINT:set sitescriptexp
: determine where add-on public executable scripts go
case "$sitescript" in
") dflt=$siteprefix/script
  $test -d $dflt || dflt=$sitebin ;;
*) dflt="$sitescript" ;;
esac

```

```
fn=d~+
rp='Pathname where add-on public executable scripts
should be installed?'
./getfile
prefixvar=sitescript
./setprefixvar
```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/installdirs/sitescript.U
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: randfunc.U,v \$

?RCS: Revision 3.0 1993/08/18 12:09:39 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?X:

?X: This is the new unit that should be used when random

?X: functions are to be used. It thus makes randbits.U obsolete.

?X:

?MAKE:randfunc mrand seedfunc nrandbits: cat +cc rm test Myread Csym

?MAKE: -pick add \$@ %<

?S:randfunc:

?S: Indicates the name of the random number function to use.

?S: Values include drand48, random, and rand. In C programs,

?S: the 'nrand' macro is defined

to generate uniformly distributed

?S: random numbers over the range [0., 1.] (see mrand and nrand).

?S:.

?S:mrand:

?S: Indicates the macro to be used to generate normalized

?S: random numbers. Uses randfunc, often divided by

?S: (double) ((1 << nrandbits) -1) in order to normalize the result.

?S: In C programs, the macro 'nrand' is mapped on mrand.

?S:.

?S:seedfunc:

?S: Indicates the random number generating seed function.

?S: Values include srand48, srandom, and srand.

?S:
?S:nrandbits:
?S: Indicates how many bits are produced by the function used to
?S: generate normalized random numbers.
?S:
?C:nrand:
?C: This macro is to be used to generate uniformly distributed
?C: random numbers over the range [0., 1.].
?C:
?C:seednrand:
?C: This symbol defines the macro to be used in seeding the
?C: random number generator (see nrand).
?C:
?H:#define nrand() \$mrand /**/
?H:#define seednrand(x) \$seedfunc(x) /**/
?H:
?T:cont val
?LINT:nothere \$nrandbits)
: How can we generate normalized
random numbers ?
echo " "
case "\$randfunc" in
")
if set drand48 val -f; eval \$csym; \$val; then
dflt="drand48"
echo "Good, found drand48()." >&4
elif set random val -f; eval \$csym; \$val; then
dflt="random"
echo "OK, found random()." >&4
else
dflt="rand"
echo "Yick, looks like I have to use rand()." >&4
fi
echo " "
;;
*)
dflt="\$randfunc"
;;
esac
cont=true
while \$test "\$cont"; do
rp="Use which function to generate random numbers?"
. ./myread
?X: Invalidates nrandbits if the answer is not the default so
?X: that the value stored in config.sh will not be used when
?X: we change our random function.
if \$test "\$ans" = "\$dflt"; then
: null

```

else
  nrandbits="
fi
randfunc="$ans"
if set $ans val -f; eval $csym; $val; then
  cont="
else
  dflt=n
  rp="Function $ans does not exists. Use that name anyway?"
  ./myread
  dflt=rand
  case "$ans" in
    [yY]*) cont=";;
  esac
fi
case "$cont" in
  ")
    case "$randfunc" in
      drand48)
        mrand="drand48()"
        seedfunc="srand48"
        ;;
      rand*)
        case
"$nrandbits" in
  ")
echo "Checking to see how many bits your $randfunc() function produces..." >&4
  $cat >try.c <<EOCP
#include <stdio.h>
int main()
{
  register int i;
  register unsigned long tmp;
  register unsigned long max = 0L;
  extern long random();

  for (i = 1000; i; i--) {
    tmp = (unsigned long)$randfunc();
    if (tmp > max) max = tmp;
  }
  for (i = 0; max; i++)
    max /= 2;
  printf("%d\n",i);
}
EOCP
if $cc -o try try.c >/dev/null 2>&1 ; then
  dflt=`try`
else

```

```

dflt='?
echo "(I can't seem to compile the test program...)"
fi
;;
*)
dflt="$nrandbits"
;;
esac
rp="How many bits does your $randfunc() function produce?"
./myread
nrandbits="$ans"
$rm -f try.c try
mrand="($randfunc() / (double) ((1 << $nrandbits) - 1))"
seedfunc="srand"
;;
?X: The following is provided just in case...
*)
dflt="31"
rp="How many bits does your $randfunc() function produce?"
./myread
nrandbits="$ans"
seedfunc="s$randfunc"
mrand="($randfunc()
/ (double) ((1 << $nrandbits) - 1))"
if set $seedfunc val -f; eval $csym; $val; then
echo "(Using $seedfunc() to seed random generator)"
else
echo "(Warning: no $seedfunc() to seed random generator)"
seedfunc=rand
fi
;;
esac
;;
esac
done

```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/randfunc.U
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: i_syswait.U 1 2006-08-24 12:32:52Z rmanfredi \$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic Licence,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

```

?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: $Log: i_syswait.U,v $
?RCS: Revision 3.0 1993/08/18 12:08:42 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?X:
?X: This unit looks wether <sys/wait.h> is available or not
?X:
?MAKE:i_syswait: Inhdr
?MAKE: -pick add $@ %<
?S:i_syswait:
?S: This variable conditionally defines I_SYS_WAIT, which indicates
?S: to the C program that it should include <sys/wait.h>.
?S:.
?C:I_SYS_WAIT (I_SYSWAIT):
?C: This symbol, if defined, indicates to the C program
that it should
?C: include <sys/wait.h>.
?C:.
?H:#$i_syswait I_SYS_WAIT /**/
?H:.
?LINT:set i_syswait
: see if this is a syswait system
set sys/wait.h i_syswait
eval $inhdr

```

Found in path(s):

```

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/i_syswait.U

```

No license file was found, but licenses were detected in source scan.

```

?RCS: $Id: vendorman3.U,v 1.1 1999/07/08 18:32:57 doughera Exp doughera $
?RCS:
?RCS: Copyright (c) 1999-2000, Andy Dougherty
?RCS:
?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 3.0.
?RCS:
?RCS: $Log: vendorman3.U,v $
?RCS: Revision 1.1 1999/07/08 18:32:57 doughera
?RCS: Initial revision
?RCS:
?MAKE:vendorman3 vendorman3exp installvendorman3: man3dir Getfile \

```

```

Oldconfig Setprefixvar Prefixit test vendorprefix prefix sed
?MAKE: -pick add $@ %<
?Y:TOP
?S:vendorman3:
?S: This variable contains the name of the directory for man3
?S: pages. It may have a ~ on the front.
?S: The standard distribution will put nothing in this directory.
?S: Vendors
    who distribute perl may wish to place their own
?S: man3 pages in this directory with
?S: MakeMaker Makefile.PL INSTALLDIRS=vendor
?S: or equivalent. See INSTALL for details.
?S:.
?S:vendorman3exp:
?S: This variable is the ~name expanded version of vendorman3, so that you
?S: may use it directly in Makefiles or shell scripts.
?S:.
?D:installvendorman3="
?S:installvendorman3:
?S: This variable is really the same as vendorman3exp but may differ on
?S: those systems using AFS. For extra portability, only this variable
?S: should be used in makefiles.
?S:.
?LINT:change prefixvar
?LINT:set installvendorman3
: Set the vendorman3 variables
case "$vendorprefix" in
") vendorman3="
    vendorman3exp="
;;
*) : determine where vendor-supplied module manual pages go.
    case "$vendorman3" in
    ") dflt=`echo "$man3dir" | $sed "s#^$prefix#$vendorprefix#" ` ;;
    *) dflt=$vendorman3 ;;
    esac
case "$dflt" in
"| ") dflt=none ;;
    esac
fn=nd~+
rp='Pathname for the vendor-supplied manual section 3
pages?'
./getfile
vendorman3="$ans"
vendorman3exp="$ansexp"
;;
esac
: Use ' ' for none so value is preserved next time through Configure
$test X"$vendorman3" = "X" && vendorman3=' '

```

prefixvar=vendorman3

./installprefix

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/installdirs/vendorman3.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: ccflags.U,v \$

?RCS: Revision 3.0.1.9 1997/02/28 15:27:07 ram

?RCS: patch61: removed support for NO_PROTOTYPE detection on SCO

?RCS: patch61: new locincpth variable

?RCS: patch61: added info on the "additional ld flags" question

?RCS:

?RCS: Revision 3.0.1.8 1995/07/25 13:48:54 ram

?RCS: patch56: re-arranged compile line to include ldflags before objects

?RCS:

?RCS: Revision 3.0.1.7 1995/05/12 12:08:33 ram

?RCS: patch54: now checks for cc/ccflags/ldflags coherency

?RCS:

?RCS: Revision 3.0.1.6

1994/10/29 16:07:02 ram

?RCS: patch36: gcc versioning no longer relies on the C compiler's name

?RCS: patch36: simplified check for gcc version checking (ADO)

?RCS:

?RCS: Revision 3.0.1.5 1994/08/29 16:06:35 ram

?RCS: patch32: propagate -posix flag from ccflags to ldflags

?RCS:

?RCS: Revision 3.0.1.4 1994/05/06 14:28:45 ram

?RCS: patch23: -fpcc-struct-return only needed in gcc 1.x (ADO)

?RCS: patch23: cppflags now computed on an option-by-option basis

?RCS: patch23: magically added cc flags now only done the first time

?RCS:

?RCS: Revision 3.0.1.3 1993/09/13 15:58:29 ram

?RCS: patch10: explicitly mention -DDEBUG just in case they need it (WAD)

?RCS: patch10: removed all the "tans" variable usage (WAD)

?RCS:

?RCS: Revision 3.0.1.2 1993/08/27 14:39:38 ram

?RCS: patch7: added support for OSF/1 machines

?RCS:

?RCS: Revision 3.0.1.1 1993/08/25 14:00:24 ram

?RCS: patch6: added defaults for cppflags, ccflags and ldflags

?RCS:

?RCS: Revision 3.0 1993/08/18 12:05:31 ram

?RCS:

Baseline for dist 3.0 netwide release.

?RCS:

?MAKE:ccflags ldflags lkflags cppflags optimize locincpth: test cat \
 Myread Guess Options Oldconfig gccversion mips_type +usrinc \
 package contains rm rm_try +cc cppstdin cppminus cprun cpplast libpth \
 loclibpth hint

?MAKE: -pick add \$@ %<

?S:ccflags:

?S: This variable contains any additional C compiler flags desired by
 ?S: the user. It is up to the Makefile to use this.

?S:.

?S:cppflags:

?S: This variable holds the flags that will be passed to the C pre-
 ?S: processor. It is up to the Makefile to use it.

?S:.

?S:optimize:

?S: This variable contains any optimizer/debugger flag that should be used.
 ?S: It is up to the Makefile to use it.

?S:.

?S:ldflags:

?S: This variable contains any additional C loader flags desired by
 ?S: the user. It is up to the Makefile to use this.

?S:.

?S:lkflags:

?S: This variable contains any additional C partial linker flags desired by
 ?S: the user. It is up to the Makefile to use this.

?S:.

?S:locincpth:

?S: This
 variable contains a list of additional directories to be
 ?S: searched by the compiler. The appropriate -I directives will
 ?S: be added to ccflags. This is intended to simplify setting
 ?S: local directories from the Configure command line.
 ?S: It's not much, but it parallels the loclibpth stuff in libpth.U.

?S:.

?T:inctest thisincl xxx flag inclwanted ftry previous thislibdir

?F:!cpp.c

?D:cppflags=""

?D:ccflags=""

?D:ldflags=""

?D:optimize=""

```

?INIT:: Possible local include directories to search.
?INIT:: Set locincpth to "" in a hint file to defeat local include searches.
?INIT:locincpth="/usr/local/include /opt/local/include /usr/gnu/include"
?INIT:locincpth="$locincpth /opt/gnu/include /usr/GNU/include /opt/GNU/include"
?INIT::
?INIT:: no include file wanted by default
?INIT:inclwanted=""
?INIT:
: determine optimize, if desired, or use for debug flag also
case "$optimize" in
'|$undef) dflt='none';;
")
case "$gccversion" in
") dflt='-O';;
*) dflt='-O2 -g';;
esac
;;
*)
dflt="$optimize";;
esac
case "$gccversion" in
") $cat <<EOH

```

Some C compilers have problems with their optimizers. By default, \$package compiles with the -O flag to use the optimizer. Alternately, you might want to use the symbolic debugger, which uses the -g flag (on traditional Unix systems). Either flag can be specified here. To use neither flag, specify the word "none".

```

EOH
;;
*) $cat <<EOH

```

With the GNU C compiler, it is possible to supply both -O2 and -g flags, to be able to reasonably optimize, whilst retaining the ability to use a symbolic debugger. Either flag can be specified here. To use neither flag, specify the word "none".

```

EOH
;;
esac
rp="What optimizer/debugger flag should be used?"
. ./myread
optimize="$ans"
case "$optimize" in
'none') optimize="" ;;
esac

```

```

dflt="
: We will not override a previous value, but we might want to
: augment a hint file
case "$hint" in
default|recommended)
case "$gccversion" in
1*) dflt='-fpcc-struct-return' ;;
esac
?X:
check for POSIXized ISC
case "$gccversion" in
2*) if test -d /etc/conf/kconfig.d &&
    $contains _POSIX_VERSION $usrinc/sys/unistd.h >/dev/null 2>&1
then
    dflt="$dflt -posix"
fi
;;
esac
?X: turn warnings on if they're using gcc
case "$gccversion" in
1*|2*) dflt="$dflt -Wall";;
?X: starting with version 3, add "-W -Wall -Wformat=2 -Wshadow" by default
*) dflt="$dflt -W -Wall -Wformat=2 -Wshadow";;
esac
;;
esac

```

?X: In USG mode, a MIPS system may need some BSD includes

```

case "$mips_type" in
*BSD*|") inclwanted="$locincpth $usrinc";;
*) inclwanted="$locincpth $inclwanted $usrinc/bsd";;
esac
for thisincl in $inclwanted; do
if $test -d $thisincl; then
if $test x$thisincl != x$usrinc; then
case "$dflt" in
*$thisincl*);;
*) dflt="$dflt -I$thisincl";;
esac
fi
fi
done

```

?X: Include test function (header, symbol)

```

inctest=if $contains $2 $usrinc/$1 >/dev/null 2>&1; then
xxx=true;
elif $contains $2 $usrinc/sys/$1 >/dev/null 2>&1; then
xxx=true;

```

```

else
  xxx=false;
fi;
if
  $xxx; then
  case "$dflt" in
  *$2*);;
  *) dflt="$dflt -D$2";;
  esac;
fi'

?X:
?X: OSF/1 uses __LANGUAGE_C__ instead of LANGUAGE_C
?X:
if ./osf1; then
  set signal.h __LANGUAGE_C__; eval $inctest
else
  set signal.h LANGUAGE_C; eval $inctest
fi

case "$hint" in
default|recommended) dflt="$ccflags $dflt" ;;
*) dflt="$ccflags";;
esac

case "$dflt" in
'| ') dflt=none;;
esac
$cat <<EOH

```

Your C compiler may want other flags. For this question you should include -I/whatever and -DWHATEVER flags and any other flags used by the C compiler, but you should NOT include libraries or ld flags like -lwhatever.

To use no flags, specify the word "none".

```

EOH
?X: strip leading space
set X $dflt
shift
dflt=${1+"$@"}
rp="Any additional cc flags?"
./myread
case "$ans" in
none) ccflags="";;
*) ccflags="$ans";;
esac

```

: the following weeds options from ccflags that are of no interest to cpp

```
cppflags="$ccflags"
case "$gccversion" in
1*) cppflags="$cppflags -D__GNUC__"
esac
case "$mips_type" in
");;
*BSD*)
  cppflags="$cppflags -DSYSTYPE_BSD43";;
esac
case "$cppflags" in
");;
*)
  echo " "
  echo "Let me guess what the preprocessor flags are..." >&4
  set X $cppflags
  shift
  cppflags="
  $cat >cpp.c <<'EOM'
#define BLURFL foo
```

```
BLURFL xx LFRULB
```

```
EOM
```

```
?X:
```

?X: For each cc flag, try it out with both cppstdn and cprun, since the

?X: first is almost surely a cc wrapper. We have to try both in case

?X: of cc flags like '-Olimit 2900' that are actually two words...

```
?X:
```

```
previous="
```

```
for flag in $*
```

```
do
```

```
  case "$flag" in
```

```
  -*) ftry="$flag";;
```

```
  *) ftry="$previous $flag";;
```

```
  esac
```

```
  if $cppstdn -DLFRULB=bar $ftry $cppminus <cpp.c \
```

```
  >cpp1.out 2>/dev/null && \
```

```
  $cprun -DLFRULB=bar $ftry $cplast <cpp.c \
```

```
  >cpp2.out 2>/dev/null && \
```

```
  $contains 'foo.*xx.*bar' cpp1.out >/dev/null 2>&1 && \
```

```
  $contains 'foo.*xx.*bar' cpp2.out >/dev/null 2>&1
```

```
  then
```

```
    cppflags="$cppflags $ftry"
```

```
    previous="
```

```
  else
```

```
    previous="$flag"
```

```
  fi
```

```
done
```

```

set X $cppflags
shift
cppflags=${1+"$@"}
case "$cppflags"
in
*-* ) echo "They appear to be: $cppflags";;
esac
$rm -f cpp.c cpp?.out
;;
esac

```

: flags used in final linking phase

```

case "$ldflags" in
*) if ./venix; then
    dflt='-i -z'
  else
    dflt=""
  fi
case "$ccflags" in
*-*posix*) dflt="$dflt -posix" ;;
esac
;;
*) dflt="$ldflags";;
esac

```

: Try to guess additional flags to pick up local libraries.

```

for thislibdir in $libpth; do
case " $loclibpth " in
*" $thislibdir ")
case "$dflt " in
*"-L$thislibdir ") ;;
*) dflt="$dflt -L$thislibdir" ;;
esac
;;
esac
done

```

```

case "$dflt" in
*) dflt='none' ;;
*) set X $dflt; shift; dflt="$@" ;;
esac

```

```
$cat <<EOH
```

Your C linker may need flags. For this question you should include -L/whatever and any other flags used by the C linker, but you should NOT include libraries like -lwhatever.

Make sure you include the appropriate -L/path flags if your C linker does not normally search all of the directories you specified above, namely \$libpth
To use no flags, specify the word "none".

EOH

```
rp="Any
additional ld flags (NOT including libraries)?"
./myread
case "$ans" in
none) ldflags="";;
*) ldflags="$ans";;
esac
rmlist="$rmlist pdp11"

@if lkflags
: partial linking may need other flags
case "$lkflags" in
") case "$ldflags" in
") dflt='none';;
*) dflt="$ldflags";;
esac;;
*) dflt="$lkflags";;
esac
echo " "
rp="Partial linking flags to be used (NOT including -r)?"
./myread
case "$ans" in
none) lkflags="";;
*) lkflags="$ans";;
esac

@end
?X:
?X: If the user changes compilers after selecting a hint file, it's
?X: possible that the suggested ccflags/ldflags will be wrong. Try to
?X: compile and run a simple test program. Let the user see all the
?X: error messages. -- ADO and RAM
?X:
: coherency check
echo " "
echo "Checking your choice of C compiler and flags for coherency..." >&4
?X: Strip extra blanks in case some of the following variables are empty
set X $cc $optimize $ccflags $ldflags -o try try.c
shift
$cat >try.msg <<EOM
```

I've tried to compile and run a simple program

with:

```
$*  
./try
```

and I got the following output:

EOM

```
$cat > try.c <<'EOF'  
#include <stdio.h>  
int main() { exit(0); }  
EOF  
dflt=y  
?X: Use "sh -c" to avoid error messages tagged with leading "Configure:".  
?X: We need to try the resulting executable, because cc might yield a 0 status  
?X: even when ld failed, in which case the executable will not run properly,  
?X: if its x bit is set at all...  
if sh -c "$cc $optimize $ccflags $ldflags -o try try.c" >>try.msg 2>&1; then  
if sh -c './try' >>try.msg 2>&1; then  
  dflt=n  
else  
  echo "The program compiled OK, but exited with status $?." >>try.msg  
  rp="You have a problem. Shall I abort Configure"  
  dflt=y  
fi  
else  
  echo "I can't compile the test program." >>try.msg  
  rp="You have a BIG problem. Shall I abort Configure"  
  dflt=y  
fi  
case "$dflt" in  
y)  
  $cat try.msg >&4  
  ?X: using -K will prevent default aborting--maybe they're cross compiling?  
  case "$knowitall" in  
  ")  
    echo "(The supplied flags might be incorrect with this C compiler.)"  
    ;;  
  *)  
    dflt=n;;  
  esac  
  echo " "  
  ./myread  
  case "$ans" in  
  n*|N*) ;;  
  *) echo "Ok. Stopping Configure." >&4  
  exit 1
```

```
;;
esac
;;
n) echo "OK, that should do.";;
esac
$rm_try
```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/ccflags.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: Config_sh.U 1 2006-08-24 12:32:52Z rmanfredi $
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: $Log: Config_sh.U,v $
?RCS: Revision 3.0.1.3 1997/02/28 14:57:53 ram
?RCS: patch61: added support for src.U
?RCS:
?RCS: Revision 3.0.1.2 1995/01/11 14:53:31 ram
?RCS: patch45: moved path stripping from d_portable.U to end of Configure
?RCS:
?RCS: Revision 3.0.1.1 1994/10/29 15:50:37 ram
?RCS: patch36: added ?F: line for metalint file checking
?RCS:
?RCS: Revision 3.0 1993/08/18 12:04:48 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?X:
?X:
This unit ends up producing the config.sh script, which contains all the
?X: definitions figured out by Configure. The add.Config_sh command knows
?X: which variables need to be remembered. It also adds the EOT (ends the
?X: here document redirection with variable substitution).
?X:
?MAKE:Config_sh: cf_time cf_by test spitshell startsh myuname Myread \
End Obsol_sh Loc +d_portable package src cat
?MAKE: -pick add.Config_sh $@ %<
?MAKE: -pick add $@ ./Obsol_sh
?MAKE: -pick close.Config_sh $@ %<
?F:!config.over !config.arch
```

```

?T:file temp
?LINT:unclosed EOT
: back to where it started
if test -d ../UU; then
  cd ..
fi

: configuration may be unconditionally patched via a 'config.arch' file
if $test -f config.arch; then
  echo "I see a config.arch file, loading it." >&4
  . ./config.arch
fi

: configuration may be patched via a 'config.over' file
if $test -f config.over; then
  echo " "
  dflt=y
  rp='I see a config.over file. Do you wish to load it?'
  . UU/myread
  case "$ans" in
  n*) echo
  "OK, I'll ignore it.";;
  *) . ./config.over
  echo "Configuration override changes have been loaded."
  ;;
  esac
fi

@if d_portable
: in case they want portability, strip down executable paths
?X:
?X: Strip down paths in located executables. For each file, e.g. vi, there
?X: is a $vi variable whose value is for instance '/usr/bin/vi'. By resetting
?X: $vi to 'vi', we rely on the PATH variable to locate the executable...
?X:
case "$d_portable" in
"$define")
  echo " "
  echo "Stripping down executable paths..." >&4
?X:
?X: Previously, we used to do eval $file="\$file" but in order
?X: to handle things like sh Configure -Dmake=gmake, we can't do
?X: that. What we *really* want is to strip away the absolute path
?X: and rely on the end user's $PATH to correctly find the executable.
?X: This method assumes there is a "basename" command available. If
?X: not, replace it with the following expr-based command:
?X: expr $temp : '.*\(^.*\)\' \| $temp
?X: Since this preserves the actual

```

```

command name, we can now drop the
?X: OS/2 specific code.
?X: --Andy Dougherty August 1999
?X:
?X: On OS/2, a special $ar command not even named 'ar' is required,
?X: so we don't strip that name.
?X: Also, on DOS-ish systems, there might not be a ln command, but we
?X: might have ln='cp'.
?X: However, we can't set d_portable=undef on such systems since
?X: Unix-ish tools don't have standard locations there. Thus we
?X: MUST rely on the user's $PATH.
?X: --Andy Dougherty 4/1998
?X:
for file in $loclist $trylist; do
    eval temp=\\$file
    eval $file=`basename $temp`
done
;;
esac

@end
: create config.sh file
echo " "
echo "Creating config.sh..." >&4
$spitshell <<EOT >config.sh
$startsh
#
# This file was produced by running the Configure script. It holds all the
# definitions figured out by Configure. Should you modify one of these values,
# do not forget to propagate your changes by running "Configure -der". You may
# instead choose to run each of the .SH files by yourself, or "Configure
-S".
#

# Package name    : $package
# Source directory : $src
# Configuration time: $cf_time
# Configured by   : $cf_by
# Target system   : $myuname

EOT
?X: Command line options are saved by the Options.U unit in the
?X: temporary file UU/cmdline.opt
: Add in command line options if available
$test -f UU/cmdline.opt && $cat UU/cmdline.opt >> config.sh

$spitshell <<EOT >>config.sh

```

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/modified/Config_sh.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_semget.U 1 2006-08-24 12:32:52Z rmanfredi \$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic Licence,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic Licence; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: d_semget.U,v \$

?RCS: Revision 3.0 1993/08/18 12:07:05 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?MAKE:d_semget: Inlibc

?MAKE: -pick add @\$ %<

?S:d_semget:

?S: This variable conditionally defines the HAS_SEMGET symbol, which

?S: indicates to the C program that the semget() routine is available.

?S:.

?C:HAS_SEMGET:

?C: This symbol, if defined, indicates that the semget() routine is

?C: available to get a set of semaphores.

?C:.

?H:#\$d_semget

HAS_SEMGET /**/

?H:.

?LINT:set d_semget

: see if semget exists

set semget d_semget

eval \$inlibc

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/d_semget.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.

?RCS:
?RCS: \$Log: d_shmat.U,v \$
?RCS: Revision 3.0.1.3 1995/07/25 14:04:23 ram
?RCS: patch56: use findhdr to find <sys/shm.h>, to get the right one (ADO)
?RCS:
?RCS: Revision 3.0.1.2 1994/05/13 15:18:56 ram
?RCS: patch27: added new symbol HAS_SHMAT_PROTOTYPE (ADO)
?RCS:
?RCS: Revision 3.0.1.1 1994/05/06 14:54:18 ram
?RCS: patch23: new Shmat_t symbol to declare return type of shmat()
?RCS:
?RCS: Revision 3.0 1993/08/18 12:07:18 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:

?MAKE:d_shmat shmattype
d_shmatprototype: Inlibc cat +cc +ccflags \
rm cppstdin cppflags cppminus Findhdr Setvar contains
?MAKE: -pick add \$@ %<
?S:d_shmat:
?S: This variable conditionally defines the HAS_SHMAT symbol, which
?S: indicates to the C program that the shmat() routine is available.
?S:.
?S:shmattype:
?S: This symbol contains the type of pointer returned by shmat().
?S: It can be 'void *' or 'char *'.
?S:.
?S:d_shmatprototype:
?S: This variable conditionally defines the HAS_SHMAT_PROTOTYPE
?S: symbol, which indicates that sys/shm.h has a prototype for
?S: shmat.
?S:.
?C:HAS_SHMAT:
?C: This symbol, if defined, indicates that the shmat() routine is
?C: available to attach a shared memory segment to the process space.
?C:.
?C:Shmat_t:
?C: This symbol holds the return type of the shmat() system call.
?C: Usually set to 'void *' or 'char *'.
?C:.
?C:HAS_SHMAT_PROTOTYPE:
?C: This symbol, if defined, indicates that the sys/shm.h includes
?C: a prototype for shmat(). Otherwise, it is up to the program
?C: to
?C: guess one. Shmat_t shmat_((int, Shmat_t, int)) is a good guess,
?C: but not always right so it should be emitted by the program only

?C: when HAS_SHMAT_PROTOTYPE is not defined to avoid conflicting defs.

?C:.

?H:#\$d_shmat HAS_SHMAT /**/

?H:#define Shmat_t \$shmattype /**/

?H:#\$d_shmatprototype HAS_SHMAT_PROTOTYPE /**/

?H:.

?LINT:set d_shmat d_shmatprototype

?T:xxx

: see if shmat exists

set shmat d_shmat

eval \$inlibc

: see what shmat returns

case "\$d_shmat" in

"\$define")

\$cat >shmat.c <<'END'

#include <sys/shm.h>

void *shmat();

END

if \$cc \$ccflags -c shmat.c >/dev/null 2>&1; then

shmattype='void *'

else

shmattype='char *'

fi

echo "and it returns (\$shmattype)." >&4

: see if a prototype for shmat is available

xxx=`./findhdr sys/shm.h`

\$cppstdin \$cppflags \$cppminus < \$xxx > shmat.c 2>/dev/null

if \$contains 'shmat.*(' shmat.c >/dev/null 2>&1; then

val="\$define"

else

val="\$undef"

fi

\$rm -f shmat.[co]

::

*)

val="\$undef"

::

esac

set d_shmatprototype

eval \$setvar

Found

in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/d_shmat.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_getsent.U,v 3.0 1993/08/18 12:06:09 ram Exp \$

```

?RCS:
?RCS: Copyright (c) 1991-1993, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 3.0.
?RCS:
?RCS: $Log: d_getsent.U,v $
?RCS: Revision 3.0 1993/08/18 12:06:09 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:d_getsent: Inlibc
?MAKE: -pick add $@ %<
?S:d_getsent:
?S: This variable conditionally defines HAS_GETSERVENT if getservernt() is
?S: available to look up network services in some data base or another.
?S:.
?C:HAS_GETSERVENT:
?C: This symbol, if defined, indicates that the getservernt() routine is
?C: available to look up network services in some
?C: data base or another.
?C:.
?H:#$d_getsent HAS_GETSERVENT /**/
?H:.
?LINT:set d_getsent
: see if getservernt exists
set getservernt d_getsent
eval $inlibc

```

Found in path(s):

```

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/modified/d_getsent.U

```

No license file was found, but licenses were detected in source scan.

```

?RCS: $Id: d_bcopy.U 1 2006-08-24 12:32:52Z rmanfredi $
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: $Log: d_bcopy.U,v $
?RCS: Revision 3.0.1.2 1993/10/16 13:48:04 ram

```

```

?RCS: patch12: added magic support for bcopy()
?RCS:
?RCS: Revision 3.0.1.1 1993/09/13 16:01:11 ram
?RCS: patch10: now only defines HAS_BCOPY, no macro remap on memcpy (WAD)
?RCS:
?RCS: Revision 3.0 1993/08/18 12:05:44 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:d_bcopy: Inlibc
?MAKE: -pick add $@ %<
?S:d_bcopy:
?S: This variable conditionally defines the HAS_BCOPY
symbol if
?S: the bcopy() routine is available to copy strings.
?S:.
?C:HAS_BCOPY:
?C: This symbol is defined if the bcopy() routine is available to
?C: copy blocks of memory.
?C:.
?H:#$d_bcopy HAS_BCOPY /**/
?H:.
?M:bcopy: HAS_BCOPY
?M:#ifndef HAS_BCOPY
?M:#ifndef bcopy
?M:#define bcopy(s,d,l) memcpy((d),(s),(l))
?M:#endif
?M:#endif
?M:.
?LINT:set d_bcopy
: see if bcopy exists
set bcopy d_bcopy
eval $inlibc

```

Found in path(s):

```

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/d_bcopy.U

```

No license file was found, but licenses were detected in source scan.

```

?RCS: $Id$
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:

```

```

?RCS: $Log: d_portable.U,v $
?RCS: Revision 3.0.1.2 1995/01/11 15:28:52 ram
?RCS: patch45: executable path stripping moved to the end in Config_sh.U
?RCS:
?RCS: Revision 3.0.1.1 1993/12/15 08:21:17 ram
?RCS: patch15: did not strip variables properly when needed
?RCS: patch15: now also strips down variables from trylist
?RCS:
?RCS: Revision 3.0 1993/08/18 12:06:48 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?X:
?X: The Loc unit is wanted to get the definition of all the locating variables.
?X:
?MAKE:d_portable:
cat Loc Myread Oldconfig
?MAKE: -pick add $@ %<
?S:d_portable:
?S: This variable conditionally defines the PORTABLE symbol, which
?S: indicates to the C program that it should not assume that it is
?S: running on the machine it was compiled on.
?S:.
?C:PORTABLE:
?C: This symbol, if defined, indicates to the C program that it should
?C: not assume that it is running on the machine it was compiled on.
?C: The program should be prepared to look up the host name, translate
?C: generic filenames, use PATH, etc.
?C:.
?H:#$d_portable PORTABLE /**/
?H:.
?D:d_portable="
: decide how portable to be
case "$d_portable" in
"$define") dflt=y;;
*) dflt=n;;
esac
$cat <<'EOH'

```

I can set things up so that your shell scripts and binaries are more portable, at what may be a noticable cost in performance. In particular, if you ask to be portable, the following happens:

- 1) Shell scripts will rely on the PATH variable rather than using the paths derived above.
 - 2) ~username interpretations will be done at run time rather than by Configure.
- @if PHOSTNAME

3) The system name will be determined at run time, if at all possible.

@end

EOH

```
rp="Do you expect to run these scripts and binaries on multiple machines?"
```

```
./myread
```

```
case "$ans" in
```

```
  y*) d_portable="$define"
```

```
?X:
```

```
?X: Paths will be stripped down (/usr/bin/vi -> vi) in Config_sh.U if needed.
```

```
?X:
```

```
;;
```

```
  *) d_portable="$undef" ;;
```

```
esac
```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/d_portable.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: cc.U 1 2006-08-24 12:32:52Z rmanfredi $
```

```
?RCS:
```

```
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
```

```
?RCS:
```

```
?RCS: You may redistribute only under the terms of the Artistic Licence,
```

```
?RCS: as specified in the README file that comes with the distribution.
```

```
?RCS: You may reuse parts of this distribution only within the terms of
```

```
?RCS: that same Artistic Licence; a copy of which may be found at the root
```

```
?RCS: of the source tree for dist 4.0.
```

```
?RCS:
```

```
?RCS: $Log: cc.U,v $
```

```
?RCS: Revision 3.0.1.4 1995/05/12 12:06:47 ram
```

```
?RCS: patch54: may now abort Configure when cc does not work
```

```
?RCS:
```

```
?RCS: Revision 3.0.1.3 1995/01/11 15:20:11 ram
```

```
?RCS: patch45: changed gcc checking message to a more explicit one (WED)
```

```
?RCS:
```

```
?RCS: Revision 3.0.1.2 1994/10/29 16:04:29 ram
```

```
?RCS: patch36: detect gcc even when not called as 'gcc' (ADO)
```

```
?RCS: patch36: simplified gcc version checking (ADO)
```

```
?RCS: patch36: added ?F: line for metalint
```

```
file checking
```

```
?RCS:
```

```
?RCS: Revision 3.0.1.1 1994/05/06 14:26:06 ram
```

```
?RCS: patch23: added support for gcc version (ADO)
```

```
?RCS:
```

```
?RCS: Revision 3.0 1993/08/18 12:05:30 ram
```

```
?RCS: Baseline for dist 3.0 netwide release.
```

```

?RCS:
?MAKE:cc: Myread Oldconfig Checkcc test
?MAKE: -pick add $@ %<
?S:cc:
?S: This variable holds the name of a command to execute a C compiler which
?S: can resolve multiple global references that happen to have the same
?S: name. Usual values are 'cc' and 'gcc'.
?S: Fervent ANSI compilers may be called 'c89'. AIX has xlc.
?S:.
?F:!cc.cbu
?D:cc='cc'
: Determine the C compiler to be used
echo " "
case "$cc" in
") dflt=cc;;
*) dflt="$cc";;
esac
rp="Use which C compiler?"
./myread
cc="$ans"

```

```

: See whether they have no cc but they do have gcc
./trygcc
?X: Look for a hint-file generated 'call-back-unit'. Now that the
?X: user has specified the compiler, we may need to set or change some
?X: other defaults.
if $test -f cc.cbu; then
./cc.cbu
fi
./checkcc

```

```

Found
in path(s):
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/cc.U
No license file was found, but licenses were detected in source scan.

```

```

?RCS: $Id: i_termio.U 1 2006-08-24 12:32:52Z rmanfredi $
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: $Log: i_termio.U,v $

```

?RCS: Revision 3.0.1.4 1994/10/29 16:20:54 ram

?RCS: patch36: call ./usg and ./Cpplib explicitly instead of relying on PATH

?RCS:

?RCS: Revision 3.0.1.3 1994/08/29 16:26:38 ram

?RCS: patch32: don't include all three I_* symbols in config.h

?RCS: patch32: (had forgotten to undo this part last time)

?RCS:

?RCS: Revision 3.0.1.2 1994/05/13 15:25:03 ram

?RCS: patch27: undone ADO's fix in previous patch since it was useless

?RCS:

?RCS:

Revision 3.0.1.1 1994/05/06 15:05:23 ram

?RCS: patch23: now include all three defines in config.h (ADO)

?RCS:

?RCS: Revision 3.0 1993/08/18 12:08:44 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?MAKE:i_termio i_sgty i_termios: test Inlibc Cpplib Guess Setvar Findhdr Warn run

?MAKE: -pick add \$@ %<

?S:i_termio:

?S: This variable conditionally defines the I_TERMIO symbol, which

?S: indicates to the C program that it should include <termio.h> rather

?S: than <sgty.h>.

?S:.

?S:i_termios:

?S: This variable conditionally defines the I_TERMIOS symbol, which

?S: indicates to the C program that the POSIX <termios.h> file is

?S: to be included.

?S:.

?S:i_sgty:

?S: This variable conditionally defines the I_SGTTY symbol, which

?S: indicates to the C program that it should include <sgty.h> rather

?S: than <termio.h>.

?S:.

?C:I_TERMIO:

?C: This symbol, if defined, indicates that the program should include

?C: <termio.h> rather than <sgty.h>. There are also differences in

?C: the

ioctl() calls that depend on the value of this symbol.

?C:.

?C:I_TERMIOS:

?C: This symbol, if defined, indicates that the program should include

?C: the POSIX termios.h rather than sgty.h or termio.h.

?C: There are also differences in the ioctl() calls that depend on the

?C: value of this symbol.

?C:.

?C:I_SGTTY:

?C: This symbol, if defined, indicates that the program should include

?C: <sgtty.h> rather than <termio.h>. There are also differences in

?C: the ioctl() calls that depend on the value of this symbol.

?C:.

?H:#\$i_termio I_TERMIO /**/

?H:#\$i_termios I_TERMIOS /**/

?H:#\$i_sgtty I_SGTTY /**/

?H:.

?T:val2 val3

?LINT:set i_termio i_sgtty i_termios

: see if this is a termio system

val="\$undef"

val2="\$undef"

val3="\$undef"

?X: Prefer POSIX-approved termios.h over all else

if \$test `./findhdr termios.h`; then

set tcsetattr i_termios

eval \$inlibc

val3="\$i_termios"

fi

echo " "

case "\$val3" in

"\$define") echo "You have POSIX termios.h... good!" >&4;;

*)

if ./Cppsymb pyr; then

case "`\$run /bin/universe`" in

ucb) if \$test `./findhdr sgtty.h`; then

val2="\$define"

echo "<sgtty.h> found." >&4

else

echo "System is pyramid with BSD universe."

./warn "<sgtty.h> not found--you could have problems."

fi;;

*) if \$test `./findhdr termio.h`; then

val="\$define"

echo "<termio.h> found." >&4

else

echo "System is pyramid with USG universe."

./warn "<termio.h> not found--you could have problems."

fi;;

esac

?X: Start with USG to avoid problems if both usg/bsd was guessed

elif ./usg; then

if \$test `./findhdr termio.h`; then

echo "<termio.h> found." >&4

val="\$define"

elif \$test `./findhdr sgtty.h`; then

echo "<sgtty.h> found." >&4

val2="\$define"

```

else
./warn "Neither <termio.h> nor <sgtty.h> found--cross fingers!"
fi
else
if $test `./findhdr sgtty.h`; then
echo "<sgtty.h> found." >&4
val2="$define"
elif $test `./findhdr termio.h`; then
echo "<termio.h>
found." >&4
val="$define"
else
./warn "Neither <sgtty.h> nor <termio.h> found--cross fingers!"
fi
fi;;
esac
set i_termio; eval $setvar
val=$val2; set i_sgtty; eval $setvar
val=$val3; set i_termios; eval $setvar

```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/modified/i_termio.U
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: localarch.U,v 1.1 1999/07/08 18:32:57 doughera Exp doughera \$

?RCS:

?RCS: Copyright (c) 1999, Jarkko Hietaniemi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 3.0.

?RCS:

?RCS:

?MAKE:localarch localarchexp installlocalarch installlocalarchexp: \

afs cat Getfile \

Oldconfig Prefixit test archname uselocallib locallib sitearch

?MAKE: -pick add \$@ %<

?Y:TOP

?S:localarch:

?S: This variable contains the eventual value of the LOCALARCH symbol,

?S: which is the name of the private library for this package. It may

?S: have a ~ on the front. It is up to the makefile to eventually create

?S: this directory while performing installation

(with ~ substitution).

?S: This differs from \$sitarsearch in that \$sitarsearch is often

?S: a shared network directory while \$localarch is
 ?S: at a local disk, because of policy/administrative issues
 ?S: like for example caching (performance), licensing, or security.
 ?S:.
 ?S:localarchexp:
 ?S: This variable is the ~name expanded version of localarch, so that you
 ?S: may use it directly in Makefiles or shell scripts.
 ?S:.
 ?S:installlocalarch:
 ?S: This variable is really the same as localarchexp but may differ on
 ?S: those systems using AFS. For extra portability, only this variable
 ?S: should be used in makefiles.
 ?S:.
 ?S:installlocalarchexp:
 ?S: This variable is the ~name expanded version of installlocalarch,
 ?S: so that you may use it directly in Makefiles or shell scripts.
 ?S:.
 ?C:LOCALARCH:
 ?C: This symbol contains the name of the private library for this package.
 ?C: The library is private in the sense that it needn't be in anyone's
 ?C: execution path, but it should be accessible by the
 world. The program
 ?C: should be prepared to do ~ expansion.
 ?C: The standard distribution will put nothing in this directory.
 ?C: Local administration may place extensions and modules in
 ?C: this directory.
 ?C: This differs from SITEARCH in that SITEARCH is often
 ?C: a shared network directory while LOCALARCH is
 ?C: at a local disk, because of policy/administrative issues
 ?C: like for example caching (performance), licensing, or security.
 ?C:.
 ?C:LOCALARCH_EXP:
 ?C: This symbol contains the ~name expanded version of LOCALARCH,
 ?C: to be used in programs that are not prepared to deal with ~
 ?C: expansion at run-time.
 ?C:.
 ?H:#define LOCALARCH "\$localarch" /**/
 ?H:#define LOCALARCH_EXP "\$localarchexp" /**/
 ?H:.
 ?T:tdflt
 ?LINT:extern sitearch
 : Set the localarch variables
 case "\$uselocallib" in
 "\$define")
 case "\$sitearch" in
 ") tdflt="\$tdflt/\$archname"
 set sitearch sitearch none
 eval \$prefixit

```

dflt="$stdflt" ;;
*) dflt="$sitearch" ;;
esac
$cat <<EOM

```

The installation process will also create a directory for architecture-dependent extensions and modules to be installed alongside \$locallib.

```

EOM
fn=nd~+
rp='Pathname for local architecture-dependent library files?'
./getfile
if $test "X$localarchexp" != "X$ansexp"; then
installlocalarch="
fi
localarch="$ans"
localarchexp="$ansexp"
if $afs; then
$cat <<EOM

```

Since you are running AFS, I need to distinguish the directory in which locally installed architecture-dependent library files reside from the directory in which they are installed (and from which they are presumably copied to the former directory by occult means).

```

EOM
case "$installlocalarch" in
*) dflt=`echo $localarchexp | sed 's#^/afs/#/afs/.#` ;;
*) dflt="$installlocalarch" ;;
esac
fn=de~
rp='Where will local architecture-dependent files be installed?'
./getfile
installlocalarch="$ans"
else
installlocalarch="$localarchexp"
fi
;;
*)
localarch=""
localarchexp=""
installlocalarch=""
installlocalarchexp=""
;;
esac

```

Found

in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/installdirs/localarch.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: usethreads.U,v \$

?RCS:

?RCS: Copyright (c) 1998-2000 Andy Dougherty

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?RCS: \$Log: usethreads.U,v \$

?RCS:

?MAKE:usethreads useithreads use5005threads d_oldpthreads usereentrant: \
Myread Oldconfig Setvar test cat patchlevel

?MAKE: -pick add \$@ %<

?Y:TOP

?S:usethreads:

?S: This variable conditionally defines the USE_THREADS symbol,

?S: and indicates that Perl should be built to use threads.

?S:.

?S:useithreads:

?S: This variable conditionally defines the USE_ITHREADS symbol,

?S: and indicates that Perl should be built to use the interpreter-based

?S: threading implementation.

?S:.

?S:use5005threads:

?S: This variable conditionally defines the USE_5005THREADS symbol,

?S: and indicates that Perl should be built to use the 5.005-based

?S: threading implementation.

Only valid up to 5.8.x.

?S:.

?X: I'm putting old_pthreads in this unit because it might eventually

?X: be part of an automatic determination to see if we can use threads

?X: at all.

?S:d_oldpthreads:

?S: This variable conditionally defines the OLD_PTHREADS_API symbol,

?S: and indicates that Perl should be built to use the old

?S: draft POSIX threads API. This is only potentially meaningful if

?S: usethreads is set.

?S:.

?S:usereentrant:

?S: This variable conditionally defines the USE_REENTRANT_API symbol,

?S: which indicates that the thread code may try to use the various

?S: _r versions of library functions. This is only potentially

?S: meaningful if usethreads is set and is very experimental, it is

?S: not even prompted for.

?S:.

?C:USE_ITHREADS:

?C: This symbol, if defined, indicates that Perl should be built to use the interpreter-based threading implementation.

?C:.

?C:USE_5005THREADS:

?C: This symbol, if defined, indicates that Perl should be built to use the 5.005-based threading implementation.

?C: Only valid up to 5.8.x.

?C:.

?C:USE_THREADS:

?C: This symbol, if defined, indicates that Perl should be built to use threads. At present, it is a synonym for USE_5005THREADS for perl older than 5.8 and USE_ITHREADS for 5.8.x and newer, but eventually the source ought to be changed to use this to mean `_any_` threading implementation.

?C:.

?C:OLD_PTHREADS_API:

?C: This symbol, if defined, indicates that Perl should be built to use the old draft POSIX threads API.

?C:.

?C:USE_REENTRANT_API:

?C: This symbol, if defined, indicates that Perl should try to use the various `_r` versions of library functions.

?C: This is extremely experimental.

?C:.

```
?H:#$use5005threads USE_5005THREADS /**/
?H:#$useithreads USE_ITHREADS /**/
?H:?%<:#if defined(USE_5005THREADS) && !defined(USE_ITHREADS)
?H:?%<:#define USE_THREADS /* until src is revised*/
?H:?%<:#endif
?H:#$d_oldpthreads OLD_PTHREADS_API /**/
?H:#$usereentrant USE_REENTRANT_API /**/
?H:.
```

?X:

[hmb] Removed LINT for use5005threads, useithreads, and usereentrant, as LINT is only run on blead

?LINT:set usethreads d_oldpthreads

?INIT:: set usethreads on the Configure command line to enable threads.

?INIT:usereentrant='undef'

?F:!usethreads.cbu

: Do we want threads support and if so, what type

?X: We should really have some explanatory text here, and some automatic setting of sensible defaults.

```
case "$usethreads" in
$define|true|[yY]*) dflt='y';;
```

```

*) # Catch case where user specified ithreads or 5005threads but
# forgot -Dusetthreads (A.D. 4/2002)
case "$useithreads$use5005threads" in
*$define*) dflt='y';
*) dflt='n';;
esac
;;
esac
cat <<EOM

```

Perl can be built to offer a form of threading support on some systems
To do so, Configure can be run with -Dusetthreads.

Note that Perl built with threading support runs slightly slower
and uses slightly more memory than plain Perl.

If this doesn't make
any sense to you, just accept the default '\$dflt'.

```

EOM
rp='Build a threading Perl?'
./myread
case "$ans" in
y|Y) val="$define" ;;
*) val="$undef" ;;
esac
set usethreads
eval $setvar

```

```

if $test $patchlevel -lt 9; then
case "$usetthreads" in
$define)
: Default to ithreads unless overridden on command line or with
: old config.sh
dflt='y'
case "$use5005threads" in
$define|true|[yY]*)
echo "5.005 threads are no longer supported"
exit 1
;;
esac
case "$useithreads" in
$undef|false|[nN]*) dflt='n';;
esac
rp='Use the newer interpreter-based ithreads?'
./myread
case "$ans" in
y|Y) val="$define" ;;
*) val="$undef" ;;

```

```

esac
set useithreads
eval $setvar
: Now set use5005threads to the opposite value.
case "$useithreads" in
$define) val="$undef" ;;
*) val="$define" ;;
esac
set use5005threads
eval $setvar
;;
*)
useithreads="$undef"
use5005threads="$undef"
;;
esac

```

?X: This is not supposed to be possible but with some trickery, maybe.

```

case "$useithreads$use5005threads" in
"$define$define")
$cat >&4 <<EOM

```

You cannot have both the itreads and the 5.005 threads enabled at the same time. Disabling the 5.005 threads since they are much less stable than the itreads.

```

EOM
use5005threads="$undef"
;;
esac

```

```

else
: perl-5.9.x and later

```

```

if test X"$usetreads" = "X$define"; then
case "$use5005threads" in
$define|true|[yY]*)
$cat >&4 <<EOM

```

5.005 threads has been removed for 5.10. Perl will be built using itreads.

```

EOM
;;
esac
fi

use5005threads="$undef"

```

```
useithreads="$usethreads"
fi
```

```
?X: Check out what kind of threads API we have
case "$d_oldpthreads" in
") : Configure tests would be welcome here. For now, assume undef.
val="$undef" ;;
*) val="$d_oldpthreads" ;;
esac
set d_oldpthreads
eval $setvar
```

```
?X: In general, -lpthread needs to come before -lc but after other
?X: libraries such as -lgdbm and such like. We assume here that -lc
?X: is present in libswanted. If that
fails to be true, then this
?X: can be changed to add pthread to the very end of libswanted.
```

```
: Look for a hint-file generated 'call-back-unit'. If the
: user has specified that a threading perl is to be built,
: we may need to set or change some other defaults.
if $test -f usethreads.cbu; then
    echo "Your platform has some specific hints regarding threaded builds, using them..."
    . ./usethreads.cbu
else
    case "$usethreads" in
"$define"|true|[yY]*)
    $cat <<EOM
(Your platform does not have any specific hints for threaded builds.
Assuming POSIX threads, then.)
EOM
    ;;
    esac
fi
```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/threads/usethreads.U
```

No license file was found, but licenses were detected in source scan.

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?MAKE:d_lgamma_r: Inlibc

?MAKE: -pick add \$@ %<

?S:d_lgamma_r:

?S: This variable conditionally defines the HAS_LGAMMA_R symbol, which

?S: indicates to the C program that the lgamma_r() routine is available

?S: for the log gamma function, without using the global signgam variable.

?S:.

?C:HAS_LGAMMA_R:

?C: This symbol, if defined, indicates that the lgamma_r routine is

?C: available to do the log gamma function without using the global

?C: signgam variable.

?C:.

?H:#\$d_lgamma_r HAS_LGAMMA_R /**/

?H:.

?LINT:set d_lgamma_r

: see if lgamma_r exists

set lgamma_r d_lgamma_r

eval \$inlibc

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_lgamma_r.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: sh.U,v 3.0.1.1 1997/02/28 16:20:13 ram Exp \$

?RCS:

?RCS: Copyright (c) 1997, Chip Salzenberg

?RCS: Copyright (c) 1991-1993, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 3.0.

?RCS:

?RCS: \$Log: sh.U,v \$

?RCS: Revision 3.0.1.1 1997/02/28 16:20:13 ram

?RCS: patch61: created

?RCS:

?MAKE:sh targetsh: Head

?MAKE: -pick wipe \$@ %<

?S:sh:

?S: This variable contains the full pathname of the shell used

?S: on this system to execute Bourne shell scripts. Usually, this will be

?S: /bin/sh, though it's possible that some systems will have /bin/ksh,

?S: /bin/pdksh, /bin/ash, /bin/bash, or even something such as

?S: D:/bin/sh.exe.

?S: This

unit comes before Options.U, so you can't set sh with a -D

?S: option, though you can override this (and startsh)

?S: with -O -Dsh=/bin/whatever -Dstartsh=whatever

?S:.

?S:targetsh:

?S: If cross-compiling, this variable contains the location of sh on the

?S: target system.

?S: If not, this will be the same as \$sh.

?S:.

?C:SH_PATH:

?C: This symbol contains the full pathname to the shell used on this

?C: on this system to execute Bourne shell scripts. Usually, this will be

?C: /bin/sh, though it's possible that some systems will have /bin/ksh,

?C: /bin/pdksh, /bin/ash, /bin/bash, or even something such as

?C: D:/bin/sh.exe.

?C:.

?H:#define SH_PATH "\$targetsh" /**/

?H:.

?T:xxx try pth p SYSTYPE

?LINT:extern maintloc maintname _exe

?X:

?X: Be quiet unless something unusual happens because this gets

?X: loaded up even before options are processed.

?X: Can't use ./loc because that depends on startsh, which, in turn

?X: depends on this unit.

?X:

: Find the basic shell for

Bourne shell scripts

case "\$sh" in

*)

?X: SYSTYPE is for some older MIPS systems.

?X: I do not know if it is still needed.

case "\$SYSTYPE" in

bsd|sys5*) xxx="/\$SYSTYPE/bin/sh";;

*) xxx="/bin/sh";;

esac

if test -f "\$xxx"; then

sh="\$xxx"

else

: Build up a list and do a single loop so we can 'break' out.

pth=`echo \$PATH | sed -e "s/\$p_/ /g"`

for xxx in sh bash ksh pdksh ash; do

for p in \$pth; do

try="\$try \${p}/\${xxx}"

done

done

for xxx in \$try; do

if test -f "\$xxx"; then

sh="\$xxx";

break

elif test "X\$_exe" != X -a -f "\$xxx\$_exe"; then

sh="\$xxx";

break

```
elif test -f "$xxx.exe"; then
  sh="$xxx";
  break
fi
done
fi
;;
esac
```

?X: fd 4 isn't open yet...

```
case "$sh" in
```

```
) cat >&2 <<EOM
```

```
$me: Fatal Error: I can't find a Bourne Shell anywhere.
```

Usually it's in /bin/sh. How did you even get this far?

Please contact me (<\$maintname>) at <\$maintloc> and we'll try to straighten this all out.

```
EOM
```

```
exit 1
```

```
;;
```

```
esac
```

: When cross-compiling

we need to separate the sh-to-run-Configure-with from the sh-to-use-in-Perl

: default both to the same thing, cross-compilers can then set targetsh differently if they like
targetsh=\$sh

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/modified/sh.U
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 2000 Jarkko Hietaniemi

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?MAKE:d_fpclass: Inlibc

?MAKE: -pick add \$@ %<

?S:d_fpclass:

?S: This variable conditionally defines the HAS_FPCLASS symbol, which

?S: indicates to the C program that the fpclass() routine is available.

?S:.

?C:HAS_FPCLASS:

?C: This symbol, if defined, indicates that the fpclass routine is

?C: available to classify doubles. Available for example in Solaris/SVR4.

?C: The returned values are defined in <ieeefp.h> and are:

?C:

?C: FP_SNAN signaling NaN

?C: FP_QNAN quiet NaN

?C: FP_NINF negative infinity

?C: FP_PINF positive infinity

?C: FP_NDENORM negative denormalized non-zero

?C: FP_PDENORM positive denormalized non-zero

?C: FP_NZERO negative zero

?C: FP_PZERO positive zero

?C: FP_NNORM negative normalized

non-zero

?C: FP_PNORM positive normalized non-zero

?C:.

?H:#\$d_fpclass HAS_FPCLASS /**/

?H:.

?LINT:set d_fpclass

: see if fpclass exists

set fpclass d_fpclass

eval \$inlibc

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_fpclass.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: Extensions.U,v\$

?RCS:

?RCS: Copyright (c) 1996-1998, Andy Dougherty

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?RCS: \$Log: Extensions.U,v \$

?RCS:

?MAKE:known_extensions extensions dynamic_ext static_ext nonxs_ext \

useposix useopcode : \

Myread hint usedl d_sem d_socket i_db i_dbm i_rpcsvdbm i_gdbm \

d_ndbm usethreads use5005threads package test cat rsrc \

d_msg d_shm osname use64bitint i_langinfo d_nl_langinfo \

libs d_cplusplus sed ls rm contains trnl sort

?MAKE: -pick add \$@ %<

?Y:BOTTOM

?S:known_extensions:

?S: This variable holds a list of all extensions (both XS and non-xs)

?S: included in the package source distribution. This information is

?S: only really of use during the Perl build, as the list makes no

?S: distinction between extensions which were build and installed, and

?S: those
 which where not. See "extensions" for the list of extensions

?S: actually built and available.

?S:.

?S:dynamic_ext:
 ?S: This variable holds a list of XS extension files we want to
 ?S: link dynamically into the package. It is used by Makefile.

?S:.

?S:static_ext:
 ?S: This variable holds a list of XS extension files we want to
 ?S: link statically into the package. It is used by Makefile.

?S:.

?S:nonxs_ext:
 ?S: This variable holds a list of all non-xs extensions built and
 ?S: installed by the package. By default, all non-xs extensions
 ?S: distributed will be built, with the exception of platform-specific
 ?S: extensions (currently only one VMS specific extension).

?S:.

?S:extensions:
 ?S: This variable holds a list of all extension files (both XS and
 ?S: non-xs) installed with the package. It is propagated to Config.pm
 ?S: and is typically used to test whether a particular extension
 ?S: is available.

?S:.

?S:useposix:
 ?S: This variable holds either 'true' or 'false' to indicate
 ?S: whether
 ?S: the POSIX extension should be used. The sole
 ?S: use for this currently is to allow an easy mechanism
 ?S: for hints files to indicate that POSIX will not compile
 ?S: on a particular system.

?S:.

?S:useopcode:
 ?S: This variable holds either 'true' or 'false' to indicate
 ?S: whether the Opcode extension should be used. The sole
 ?S: use for this currently is to allow an easy mechanism
 ?S: for users to skip the Opcode extension from the Configure
 ?S: command line.

?S:.

?T:xxx avail_ext this_ext tdir xs_extensions nonxs_extensions find_extensions
 ?INIT:: set useposix=false in your hint file to disable the POSIX extension.
 ?INIT:useposix=true
 ?INIT:: set useopcode=false in your hint file to disable the Opcode extension.
 ?INIT:useopcode=true
 ?LINT:extern noextensions
 ?LINT:extern onlyextensions
 ?T:keepextensions i
 : Check extensions

```

echo " "
echo "Looking for extensions..." >&4
: If we are using the old config.sh, nonxs_extensions and xs_extensions may
: contain old or inaccurate
or duplicate values.
nonxs_extensions="
xs_extensions="
: We do not use find because it might not be available.
: We do not just use MANIFEST because the user may have dropped
: some additional extensions into the source tree and expect them
: to be built.

: Function to recursively find available extensions, ignoring DynaLoader
: NOTE: recursion limit of 10 to prevent runaway in case of symlink madness
: In 5.10.1 and later, extensions are stored in directories
: like File-Glob instead of the older File/Glob/.
find_extensions='
  for xxx in *; do
case "$xxx" in
  DynaLoader|dynaload) ;;
  *)
  this_ext=`echo "$xxx" | $sed -e s/-/\\/g`;
  case "$this_ext" in
Scalar/List/Utils) this_ext="List/Util" ;;
PathTools)      this_ext="Cwd" ;;
  esac;
  echo " $xs_extensions $nonxs_extensions" > "$tdir/$.tmp";
  if $contains " $this_ext " "$tdir/$.tmp"; then
echo >&4;
echo "Duplicate directories detected for extension $xxx" >&4;
echo "Configure cannot
correctly recover from this - shall I abort?" >&4;
case "$knowitall" in
  "") dflt=y;;
  *) dflt=n;;
  esac;
  ../UU/myread;
case "$ans" in
n*|N*) ;;
*) echo >&4;
  echo "Ok. Stopping Configure." >&4;
  echo "Please remove the duplicate directory (e.g. using git clean) and then re-run Configure" >&4;
  exit 1;;
  esac;
echo "Ok. You will need to correct config.sh before running make." >&4;
fi;
$ls -l "$xxx" > "$tdir/$.tmp";
if $contains "\.xs$" "$tdir/$.tmp" > /dev/null 2>&1; then

```

```

xs_extensions="$xs_extensions $this_ext";
  elif $contains "\.c$" "$tdir/$$.tmp" > /dev/null 2>&1; then
xs_extensions="$xs_extensions $this_ext";
  elif $test -d "$xxx"; then
nonxs_extensions="$nonxs_extensions $this_ext";
  fi;
  $rm -f "$tdir/$$.tmp";
  ;;
esac;
done'
tdir=`pwd`
cd "$rsrc/cpan"
set X
shift
eval $find_extensions
cd "$rsrc/dist"
set X
shift
eval $find_extensions
cd "$rsrc/ext"
set X
shift
eval $find_extensions
set X $xs_extensions
shift
xs_extensions=`echo
"$*" | tr ' ' $trnl | $sort | tr $trnl ' '`
set X $nonxs_extensions
shift
nonxs_extensions=`echo "$*" | tr ' ' $trnl | $sort | tr $trnl ' '`
cd "$tdir"
known_extensions=`echo $nonxs_extensions $xs_extensions | tr ' ' $trnl | $sort | tr $trnl ' `

```

: Now see which are supported on this system.

?X: avail_ext lists available XS extensions.

```
avail_ext="
```

```
for xxx in $xs_extensions ; do
```

```
  case "$xxx" in
```

?X: Handle possible DOS 8.3 filename and case alterations

```
  Amiga*)
```

```
    case "$osname" in
```

```
      amigaos) avail_ext="$savail_ext $xxx" ;;
```

```
    esac
```

```
  ;;
```

```
  DB_File|db_file)
```

```
    case "$i_db" in
```

```
      $define) avail_ext="$savail_ext $xxx" ;;
```

```
    esac
```

```

;;
GDBM_File|gdbm_fil)
case "$i_gdbm" in
$define) avail_ext="$avail_ext $xxx" ;;
esac
;;
I18N/Langinfo|i18n_lan)
case "$i_langinfo$d_nl_langinfo" in
$define$define) avail_ext="$avail_ext $xxx" ;;
esac
;;
IPC/SysV|ipc/sysv)
: XXX Do we need a useipcsysv variable here
case "${d_msg}${d_sem}${d_shm}" in
*${define}*)
avail_ext="$avail_ext $xxx" ;;
esac
;;
NDBM_File|ndbm_fil)
case "$d_ndbm" in
$define)
case "$osname-$use64bitint" in
hpux-define)
case "$libs" in
*-lndbm*) avail_ext="$avail_ext $xxx" ;;
esac
;;
*) avail_ext="$avail_ext $xxx" ;;
esac
;;
esac
;;
ODBM_File|odbm_fil)
case "${i_dbm}${i_rpcsvcdbm}" in
*${define}*)
case "$d_cplusplus" in
define) ;; # delete as a function name will not work
*) case "$osname-$use64bitint" in
hpux-define)
case "$libs" in
*-ldb*) avail_ext="$avail_ext $xxx" ;;
esac
;;
*) avail_ext="$avail_ext $xxx" ;;
esac
;;
esac
;;

```

```

esac
;;
Opcode|opcode)
case "$useopcode" in
true|define|y) avail_ext="$avail_ext $xxx" ;;
esac
;;
POSIX|posix)
case "$useposix" in
true|define|y) avail_ext="$avail_ext $xxx" ;;
esac
;;
Socket|socket)
case "$d_socket" in
true|$define|y) avail_ext="$avail_ext $xxx" ;;
esac
;;
Sys/Syslog|sys/syslog)
case
$osname in
  amigaos) ;; # not really very useful on AmigaOS
  *)
  : XXX syslog requires socket
  case "$d_socket" in
true|$define|y) avail_ext="$avail_ext $xxx" ;;
esac
;;
esac
;;
Thread|thread)
  case "$sethreads" in
true|$define|y)
  case "$use5005threads" in
$define|true|[yY]*) avail_ext="$avail_ext $xxx" ;;
esac
esac
;;
threads|threads/shared)
# threads and threads::shared are special cases.
# To stop people from asking "Perl 5.8.0 was supposed
# to have this new fancy threads implementation but my
# perl doesn't have it" and from people trying to
# (re)install the threads module using CPAN.pm and
# CPAN.pm then offering to reinstall Perl 5.8.0,
# the threads.pm and threads/shared.pm will always be
# there, croaking informatively ("you need to rebuild
# all of Perl with threads, sorry") when threads haven't
# been

```

```

compiled in.
# --jhi
avail_ext="$savail_ext $xxx"
;;
VMS*)
;;
Win32*)
case "$osname" in
cygwin) avail_ext="$savail_ext $xxx" ;;
esac
;;
XS/APItest|xs/apitest)
# This is just for testing. Skip it unless we have dynamic loading.

case "$usedl" in
$define) avail_ext="$savail_ext $xxx" ;;
esac
;;
XS/Typemap|xs/typemap)
# This is just for testing. Skip it unless we have dynamic loading.
case "$usedl" in
$define) avail_ext="$savail_ext $xxx" ;;
esac
;;
*) avail_ext="$savail_ext $xxx"
;;
esac
done

set X $savail_ext
shift
avail_ext="$*"

case "$onlyextensions" in
") ;;
*) keepextensions="
echo "You have requested that only certain extensions be included..." >&4
for i in $onlyextensions; do
case " $savail_ext " in
*" $i "*)
echo "Keeping extension $i."
keepextensions="$keepextensions $i"
;;
*) echo "Ignoring extension $i." ;;
esac
done
avail_ext="$keepextensions"
;;

```

```

esac

case
"$noextensions" in
") ;;
*) keepextensions="
    echo "You have requested that certain extensions be ignored..." >&4
    for i in $avail_ext; do
        case " $noextensions " in
            *" $i "*) echo "Ignoring extension $i." ;;
            *) echo "Keeping extension $i.";
                keepextensions="$keepextensions $i"
                ;;
        esac
    done
    avail_ext="$keepextensions"
    ;;
esac

```

: Now see which nonxs extensions are supported on this system.

: For now assume all are.

```

nonxs_ext="
for xxx in $nonxs_extensions ; do
case "$xxx" in
VMS*)
    ;;
*) nonxs_ext="$nonxs_ext $xxx"
    ;;
esac
done

```

```

set X $nonxs_ext
shift
nonxs_ext="$*"

```

```

case $usedl in
$define)
$cat <<EOM

```

A number of extensions are supplied with \$package. You may choose to compile these extensions for dynamic loading (the default), compile them into the \$package executable (static loading), or not include them at all. Answer "none" to include no extensions.

Note that DynaLoader is always built and need not be mentioned here.

```

EOM
case "$dynamic_ext" in
")

```

```

: Exclude those listed in static_ext
dflt=""
for xxx in $avail_ext; do
  case " $static_ext " in
    *" $xxx *) ;;
    *) dflt="$dflt $xxx" ;;
  esac
done
set X $dflt
shift
dflt="$*"
;;
*) dflt="$dynamic_ext"
# Perhaps we are reusing an old out-of-date config.sh.
case "$hint" in
previous)
  if test X"$dynamic_ext" != X"$avail_ext"; then
    $cat <<EOM
NOTICE: Your previous config.sh list may be incorrect.
The extensions now available to you are
${avail_ext}
but the default list from your previous config.sh is
${dynamic_ext}

```

EOM

```

  fi
  ;;
esac
;;
esac
case "$dflt" in
") dflt=none;;
esac
rp="What extensions do you wish to load dynamically?"
. ./myread
case "$ans" in
?X: Use ' ' so a subsequent Configure will preserve that value.
none) dynamic_ext=' ' ;;
*) dynamic_ext="$ans" ;;
esac

case "$static_ext" in
")
: Exclude those already listed in dynamic linking
dflt=""
for
xxx in $avail_ext; do
  case " $dynamic_ext " in

```

```

*) $xxx *) ;;
*) dflt="$dflt $xxx" ;;
esac
done
set X $dflt
shift
dflt="$*"
;;
*) dflt="$static_ext"
;;
esac

case "$dflt" in
") dflt=none;;
esac
rp="What extensions do you wish to load statically?"
./myread
case "$ans" in
?X: Use ' ' so a subsequent Configure will preserve that value.
none) static_ext=' ' ;;
*) static_ext="$ans" ;;
esac
;;
*)
$cat <<EOM
A number of extensions are supplied with $package. Answer "none"
to include no extensions.
Note that DynaLoader is always built and need not be mentioned here.

```

```

EOM
case "$static_ext" in
") dflt="$avail_ext" ;;
*) dflt="$static_ext"
# Perhaps we are reusing an old out-of-date config.sh.
case "$hint" in
previous)
if test X"$static_ext" != X"$avail_ext"; then
$cat <<EOM
NOTICE: Your previous config.sh list may be incorrect.
The extensions now available to you are
${avail_ext}
but the default list from your previous config.sh is
${static_ext}

```

```

EOM
fi
;;
esac

```

```

;;
esac
:
Exclude those that are not xs extensions
case "$dflt" in
") dflt=none;;
esac
rp="What extensions do you wish to include?"
. ./myread
case "$ans" in
?X: Use ' ' so a subsequent Configure will preserve that value.
none) static_ext=' ' ;;
*) static_ext="$ans" ;;
esac
;;
esac
#
# Encode is a special case. If we are building Encode as a static
# extension, we need to explicitly list its subextensions as well.
# For other nested extensions, this is handled automatically by
# the appropriate Makefile.PL.
case " $static_ext " in
*" Encode "*) # Add the subextensions of Encode
cd "$src/cpan"
for xxx in `ls Encode/*/Makefile.PL|awk -F/ '{print $2}'`; do
static_ext="$static_ext Encode/$xxx"
known_extensions="$known_extensions Encode/$xxx"
done
cd "$dir"
;;
esac

set X $dynamic_ext $static_ext $nonxs_ext
shift
extensions="$*"

# Sanity check: We require an extension suitable for use with
# AnyDBM_File, as well as Fcntl and
# IO. (Failure to have these
# should show up as failures in the test suite, but it's helpful to
# catch them now.) The 'extensions' list is normally sorted
# alphabetically, so we need to accept either
# DB_File ... Fcntl ... IO ....
# or something like
# Fcntl ... NDBM_File ... IO ....
case "$extensions" in
*_File "*" Fcntl "*" IO "*) ;; # DB_File
*_File "*" IO "*) ;; # GDBM_File

```

```

*" Fcntl "*" IO "*" _File "*" ) ;; # NDBM_File
*) echo "WARNING: Extensions DB_File or *DBM_File, Fcntl, and IO not configured." >&4
  echo "WARNING: The Perl you are building will be quite crippled." >& 4
  ;;
esac

```

Found in path(s):

```

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/perl/Extensions.U

```

No license file was found, but licenses were detected in source scan.

```

?RCS: $Id: Oldconfig.U,v 3.0.1.10 1997/02/28 15:06:39 ram Exp $
?RCS:
?RCS: Copyright (c) 1991-1993, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 3.0.
?RCS:
?RCS: $Log: Oldconfig.U,v $
?RCS: Revision 3.0.1.10 1997/02/28 15:06:39 ram
?RCS: patch61: added support for src.U
?RCS: patch61: new OSNAME define
?RCS: patch61: can now sense new OSes
?RCS:
?RCS: Revision 3.0.1.9 1995/07/25 13:40:51 ram
?RCS: patch56: now knows about OS/2 platforms
?RCS:
?RCS: Revision 3.0.1.8 1995/05/12 12:04:18 ram
?RCS: patch54: config.sh reload logic now knows about new -K switch
?RCS: patch54: cleaned up and extended osvers for DEC
OSF/1 (ADO)
?RCS: patch54: added MachTen detection (ADO)
?RCS:
?RCS: Revision 3.0.1.7 1995/02/15 14:13:41 ram
?RCS: patch51: adapted osvers computation for AIX (ADO)
?RCS:
?RCS: Revision 3.0.1.6 1995/01/30 14:27:15 ram
?RCS: patch49: unit Options.U now exports file optdef.sh, not a variable
?RCS: patch49: update code for myuname changed (WED)
?RCS:
?RCS: Revision 3.0.1.5 1995/01/11 15:15:36 ram
?RCS: patch45: added quotes around the INITPROG variable (ADO)
?RCS: patch45: allows variable overriding after config file loading
?RCS:
?RCS: Revision 3.0.1.4 1994/10/29 15:57:05 ram

```

?RCS: patch36: added ?F: line for metalint file checking

?RCS: patch36: merged with the version used for perl5's Configure (ADO)

?RCS:

?RCS: Revision 3.0.1.3 1994/05/06 14:24:17 ram

?RCS: patch23: added support for osf1 hints

?RCS: patch23: new support for solaris and i386 systems (ADO)

?RCS:

?RCS: Revision 3.0.1.2 1994/01/24 14:05:02 ram

?RCS: patch16: added post-processing on myuname for Xenix targets

?RCS:

patch16: message proposing config.sh defaults made consistent

?RCS:

?RCS: Revision 3.0.1.1 1993/09/13 15:56:32 ram

?RCS: patch10: force use of config.sh when -d option is used (WAD)

?RCS: patch10: complain about non-existent hint files (WAD)

?RCS: patch10: added Options dependency for fastread variable

?RCS:

?RCS: Revision 3.0 1993/08/18 12:05:12 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?X:

?X: This unit tries to remember what we did last time we ran Configure, mostly

?X: for the sake of setting defaults.

?X:

?MAKE:Oldconfig hint myuname osname osvers: Instruct Myread uname \
 Checkcc Mksymlinks run \
 sh awk sed test cat rm lns tr n c contains Loc Options Tr src trnl ln

?MAKE: -pick wipe \$@ %<

?S:myuname:

?S: The output of 'uname -a' if available, otherwise the hostname.

?S: The whole thing is then lower-cased and slashes and single quotes are

?S: removed.

?S:.

?S:hint:

?S: Gives the type of hints used for previous answers. May be one of

?S: "default",

"recommended" or "previous".

?S:.

?S:osname:

?S: This variable contains the operating system name (e.g. sunos,

?S: solaris, hpux, etc.). It can be useful later on for setting

?S: defaults. Any spaces are replaced with underscores. It is set

?S: to a null string if we can't figure it out.

?S:.

?S:osvers:

?S: This variable contains the operating system version (e.g.

?S: 4.1.3, 5.2, etc.). It is primarily used for helping select

?S: an appropriate hints file, but might be useful elsewhere for

?S: setting defaults. It is set to " if we can't figure it out.

?S: We try to be flexible about how much of the version number

?S: to keep, e.g. if 4.1.1, 4.1.2, and 4.1.3 are essentially the

?S: same for this package, hints files might just be os_4.0 or

?S: os_4.1, etc., not keeping separate files for each little release.

?S:.

?C:OSNAME:

?C: This symbol contains the name of the operating system, as determined

?C: by Configure. You shouldn't rely on it too much; the specific

?C: feature tests

from Configure are generally more reliable.

?C:.

?C:OSVERS:

?C: This symbol contains the version of the operating system, as determined

?C: by Configure. You shouldn't rely on it too much; the specific

?C: feature tests from Configure are generally more reliable.

?C:.

?H:#define OSNAME "\$osname" /**/

?H:#define OSVERS "\$osvers" /**/

?H:.

?F:!config.sh

?T:tmp tmp_n tmp_c tmp_sh file

?T:xxxxfile xxxfile xxfile xfile hintfile newmyuname

?T:tans _ isesix INITPROG DJGPP

?D:osname="

?LINT:change n c sh

?LINT:extern targetarch

?LINT:extern hostarch

?LINT:change hostarch

?LINT:extern is_os2

: Try to determine whether config.sh was made on this system

case "\$config_sh" in

)

?X: indentation wrong on purpose--RAM

?X: Leave a white space between first two '(' for ksh. The sub-shell is needed

?X: on some machines to avoid the error message when uname is not found; e.g.

?X: old SUN-OS 3.2 would not execute hostname in (uname -a || hostname). Sigh!

?X: Now not using a subshell but instead \$test.

myuname=`\$uname

-a 2>/dev/null`

\$test -z "\$myuname" && myuname=`hostname 2>/dev/null`

Downcase everything to avoid ambiguity.

Remove slashes and single quotes so we can use parts of this in

directory and file names.

Remove newlines so myuname is sane to use elsewhere.

tr '[A-Z]' '[a-z]' would not work in EBCDIC

because the A-Z/a-z are not consecutive.

myuname=`echo \$myuname | \$sed -e "s,[/],g" | \

```

./tr '[A-Z]' '[a-z]' | $tr $trnl ' `
?X: Save the value we just computed to reset myuname after we get done here.
newmyuname="$myuname"
dflt=n
case "$knowitall" in
")
if test -f ../config.sh; then
if $contains myuname= ../config.sh >/dev/null 2>&1; then
eval "`grep myuname= ../config.sh`"
fi
if test "X$myuname" = "X$newmyuname"; then
dflt=y
fi
fi
;;
*) dflt=y;;
esac

```

```

@if {test -d ../hints}
: Get old answers from old config file if Configure was run on the
: same system, otherwise use the hints.
hint=default
cd ..
?X: Since we are now at the root of the source
tree, we must use $src
?X: to access the sources and not $src. See src.U for details...
if test -f config.sh; then
echo " "
rp="I see a config.sh file. Shall I use it to set the defaults?"
. UU/myread
case "$ans" in
n*|N*) echo "OK, I'll ignore it."
mv config.sh config.sh.old
myuname="$newmyuname"
;;
*) echo "Fetching default answers from your old config.sh file..." >&4
tmp_n="$n"
tmp_c="$c"
tmp_sh="$sh"
. ./config.sh
cp config.sh UU
n="$tmp_n"
c="$tmp_c"
: Older versions did not always set $sh. Catch re-use of such
: an old config.sh.
case "$sh" in
") sh="$tmp_sh" ;;
esac

```

```

hint=previous
;;
esac
fi
./UU/checkcc
if test ! -f config.sh; then
$cat <<EOM

```

First time through, eh? I have some defaults handy for some systems that need some extra help getting the Configure answers right:

EOM

```

(cd $src/hints; ls -C *.sh) | $sed 's/\./ /g' >&4
dflt="
: Half the following guesses are probably wrong... If you have better
: tests or hints,
please send them to <MAINTLOC>
: The metaconfig authors would also appreciate a copy...
$test -f /irix && osname=irix
$test -f /xenix && osname=sco_xenix
$test -f /dynix && osname=dynix
$test -f /dnix && osname=dnix
$test -f /lynx.os && osname=lynxos
$test -f /unicos && osname=unicos && osvers=`$uname -r`
$test -f /unicosmk && osname=unicosmk && osvers=`$uname -r`
$test -f /unicosmk.ar && osname=unicosmk && osvers=`$uname -r`
$test -f /bin/mips && /bin/mips && osname=mips
$test -d /usr/apollo/bin && osname=apollo
$test -f /etc/saf/_sactab && osname=svr4
$test -d /usr/include/minix && osname=minix && osvers=`$uname -r`
$test -f /system/gnu_library/bin/ar.pm && osname=vos
$test -f /sys/utilities/MultiView && osname=amigaos
if $test -d /MachTen -o -d /MachTen_Folder; then
?X: MachTen uname -a output looks like
?X: xxx 4 0.0 Macintosh
?X: MachTen /sbin/version output looks like
?X: MachTen 4.0 Mon Aug 28 10:18:00 1995
?X: MachTen 3.x had the 'version' command in /usr/etc/version.
osname=machten
if
$test -x /sbin/version; then
osvers=`/sbin/version | $awk '{print $2}' |
$sed -e 's/[A-Za-z]$//`
elif $test -x /usr/etc/version; then
osvers=`/usr/etc/version | $awk '{print $2}' |
$sed -e 's/[A-Za-z]$//`
else
osvers="$2.$3"

```

fi

fi

```
$test -f /sys/posix.dll &&  
$test -f /usr/bin/what &&  
set X `usr/bin/what /sys/posix.dll` &&  
$test "$3" = UWIN &&  
osname=uwin &&  
osvers="$5"
```

?X: If we have uname, we already computed a suitable uname -a output,

?X: and it lies in \$myuname.

```
if $test -f $uname; then  
set X $myuname  
shift
```

```
case "$5" in  
fps*) osname=fps ;;  
mips*)  
case "$4" in  
umips) osname=umips ;;  
*) osname=mips ;;  
esac;;  
[23]100) osname=mips ;;
```

?X: Interactive Unix.

i386*)

```
tmp=`/bin/uname -X 2>/dev/null|awk '/3\.2v[45]/{ print $(NF) }`  
if $test "$tmp" != "" -a "$3" = "3.2" -a -f /etc/systemid; then  
osname='sco'  
osvers=$tmp  
elif $test -f /etc/kconfig; then  
osname=isc  
if  
test "$lns" = "$ln -s"; then  
osvers=4  
elif $contains _SYSV3 /usr/include/stdio.h > /dev/null 2>&1 ; then  
osvers=3  
elif $contains _POSIX_SOURCE /usr/include/stdio.h > /dev/null 2>&1 ; then  
osvers=2  
fi  
fi  
tmp=""  
;;
```

?X: MS-DOS djgpp uname -a output looks like:

?X: ms-dos xxx 6 22 pc

?X: \$1 is the "dos flavor" (need not be "ms-dos").

?X: \$2 is the node name

?X: \$3 and \$4 are version/subversion

?X: \$5 is always "pc", but that might not be unique to DJGPP.

?X: (e.g. Solaris_x86 has \$5 = i86pc, which doesn't actually conflict,

?X: but it's close enough that I can easily imagine other vendors also

?X: using variants of pc* in \$5.)

?X: The "DJGPP" environment variable is always set when djgpp is active.

pc*)

```
if test -n "$DJGPP"; then
```

```
  osname=dos
```

```
  osvers=djgpp
```

```
fi
```

```
::
```

```
esac
```

```
case "$1" in
```

```
  aix) osname=aix
```

?X: aix 4.1 uname -a output looks like

?X: AIX foo 1 4 000123456789

?X: where \$4 is the major release number and \$3 is the (minor) version.

?X: More detail on the version is available with the oslevel command.

?X: in 3.2.x, it output a string (see case statements below). In 4.1,

?X: it puts out something like 4.1.1.0

```
tmp=`( oslevel) 2>/dev/null || echo "not found") 2>&1`
```

```
case "$tmp" in
```

```
  # oslevel can fail with:
```

```
  # oslevel: Unable to acquire lock.
```

```
  *not\ found) osvers="$4"."$3" ;;
```

```
  '<3240'|<>3240') osvers=3.2.0 ;;
```

```
  '=3240'|>3240'|<3250'|<>3250') osvers=3.2.4 ;;
```

```
  '=3250'|>3250') osvers=3.2.5 ;;
```

```
  *) osvers=$tmp;;
```

```
esac
```

```
::
```

```
bitrig) osname=bitrig
```

```
  osvers="$3"
```

```
::
```

```
bsd386) osname=bsd386
```

```
  osvers=`$uname -r`
```

```
::
```

```
cygwin*) osname=cygwin
```

```
  osvers="$3"
```

```
::
```

```
*dc.osx) osname=dcosx
```

```
  osvers="$3"
```

```
::
```

```
dnix) osname=dnix
```

```
  osvers="$3"
```

```
::
```

```

domains) osname=apollo
osvers="$3"
;;
dgux) osname=dgux
osvers="$3"
;;
dragonfly) osname=dragonfly
osvers="$3"
;;
?X: uname -a returns
?X: DYNIX/ptx xxx 4.0 V4.1.2 i386
dynixptx*) osname=dynixptx
osvers=`echo
"$4"|sed 's/^v//'^
;;
freebsd) osname=freebsd
osvers="$3" ;;
genix) osname=genix ;;
?X: GNU/Hurd uname -a gives something like:
?X: GNU foo 0.3 GNU-Mach 1.4/Hurd-0.3 i386-AT386 GNU
?X: GNU gnu 0.3 GNUmach-1.2/Hurd-0.3 i386-AT386 GNU
?X: Note the hostname on the second one, which will fool Configure
?X: into using the SysV case!
gnu) osname=gnu
osvers="$3" ;;
?X: HP-UX uname -a gives something like
?X: HP-UX foobar B.10.20 A 9000/735 2016483812 two-user license
?X: Preserve the full 10.20 string instead of the previous plain '10'.
?X: Thanks to Graham Barr. --AD 6/30/1998
hp*) osname=hpux
osvers=`echo "$3" | $sed 's,.*\.[0-9]*\.[0-9]*\),1,^
;;
irix*) osname=irix
case "$3" in
4*) osvers=4 ;;
5*) osvers=5 ;;
*) osvers="$3" ;;
esac
;;
linux) osname=linux
case "$3" in
*) osvers="$3" ;;
esac
$test -f /system/lib/libandroid.so && osname=linux-android
;;
MiNT) osname=mint
;;
netbsd*) osname=netbsd

```

```

osvers="$3"
;;
news-os)
osvers="$3"
case "$3" in
4*) osname=newsos4 ;;
*) osname=newsos ;;
esac
;;
nonstop-ux) osname=nonstopux ;;
openbsd) osname=openbsd
osvers="$3"
;;
os2) osname=os2
osvers="$4"
;;
POSIX-BC | posix-bc ) osname=posix-bc
osvers="$3"
;;
powerux | power_ux | powermax_os | powermaxos | \
powerunix | power_unix) osname=powerux
osvers="$3"
;;
qnx) osname=qnx
osvers="$4"
;;
solaris) osname=solaris
case "$3" in
5*) osvers=`echo $3 | $sed 's/^5/2/g` ;;
*) osvers="$3" ;;
esac
;;
sunos) osname=sunos
case "$3" in
5*) osname=solaris
osvers=`echo $3 | $sed 's/^5/2/g` ;;
*) osvers="$3" ;;
esac
;;
titanos) osname=titanos
case "$3" in
1*) osvers=1 ;;
2*) osvers=2 ;;
3*) osvers=3 ;;
4*) osvers=4 ;;
*) osvers="$3" ;;
esac
;;

```

```

ultrix) osname=ultrix
osvers="$3"
;;
osf1|m1s+) case "$5" in
alpha)
?X: DEC OSF/1 myuname -a output looks like:
osf1 xxxx t3.2 123.4 alpha
?X: where the version number can be something like [xvt]n.n
osname=dec_osf
?X: sizer knows the minor minor version: the letter
osvers=`sizer -v | awk -FUNIX '{print $2}' | awk '{print $1}' | tr '[A-Z]' '[a-z]' | sed 's/^[xvt]//'^
case "$osvers" in
[1-9].[0-9]*) ;;
*) osvers=`echo "$3" | sed 's/^[xvt]//'^ ;;
esac
;;
hp*) osname=hp_osf1 ;;
mips) osname=mips_osf1 ;;
?X: hp and mips were unsupported Technology Releases -- ADO, 24/10/94
esac
;;
# UnixWare 7.1.2 is known as Open UNIX 8
openunix|unixware) osname=svr5
osvers="$4"
;;
uts) osname=uts
osvers="$3"
;;
vos) osvers="$3"
;;
$2) case "$osname" in
*isc*) ;;
*freebsd*) ;;
svr*)
: svr4.x or possibly later
case "svr$3" in
${osname}*)
osname=svr$3
osvers=$4
;;
esac
case "$osname" in
svr4.0)
: Check for ESIX
if test -f /stand/boot ; then
eval `grep '^INITPROG=[a-z/0-9]*$' /stand/boot`
if

```

```

test -n "$INITPROG" -a -f "$INITPROG"; then
isesix=`strings -a $INITPROG|grep 'ESIX SYSTEM V/386 Release 4.0`
  if test -n "$isesix"; then
    osname=esix4
  fi
fi
fi
;;
esac
;;
*) if test -f /etc/systemid; then
  osname=sco
  set `echo $3 | $sed 's/\./ /g` $4
  if $test -f $src/hints/sco_$1_$2_$3.sh; then
    osvers=$1.$2.$3
  elif $test -f $src/hints/sco_$1_$2.sh; then
    osvers=$1.$2
  elif $test -f $src/hints/sco_$1.sh; then
    osvers=$1
  fi
else
  case "$osname" in
  ") : Still unknown. Probably a generic Sys V.
    osname="sysv"
    osvers="$3"
    ;;
  esac
fi
;;
esac
;;
*) case "$osname" in
  ") : Still unknown. Probably a generic BSD.
    osname="$1"
    osvers="$3"
    ;;
  esac
;;
esac
else
?X: Try to identify sony's NEWS-OS (BSD unix)
if test -f /vmunix -a -f $src/hints/news_os.sh; then
  (what /vmunix | UU/tr '[A-Z]' '[a-z]') > UU/kernel.what
2>&1
if $contains news-os UU/kernel.what >/dev/null 2>&1; then
  osname=news_os
fi
$rm -f UU/kernel.what

```

?X: Maybe it's OS/2 or DOS or something similar

```
elif test -d c:/ . -o -n "$is_os2" ; then
  set X $myuname
  osname=os2
  osvers="$5"
fi
fi

case "$targetarch" in
  *) ;;
  *) hostarch=$osname
     case "$targetarch" in
       nto*|*-nto-*)
         # Will load qnx.sh, which should change osname to nto
         osname=qnx
         osvers=""
         ;;
       *linux-android*)
         # Catch arm-linux-androideabi, mipsel-linux-android,
         # and i686-linux-android
         osname=linux-android
         osvers=""
         ;;
       *linux*)
         # Something like arm-linux-gnueabi is really just
         # plain linux.
         osname=linux
         osvers=""
         ;;
       *solaris*|*sunos*)
         osname=solaris
         # XXX perhaps we should just assume
         # osvers to be 2, or maybe take the value
         # from targetarch. Using $run before the
         # hints are run is somewhat icky.
         set X ` $run $uname -a 2>/dev/null `
         shift
         case "$3" in
           5*) osvers=`echo $3 | $sed 's/^5/2/g'` ;;
           *) osvers="$3" ;;
         esac
         ;;
       *)
         osname=`echo $targetarch|sed 's,^[^-]*-,`
         osvers=""
         ;;
     esac
  ;;
;;
```

esac

: Now look for a hint file osname_osvers, unless one has been
: specified already.

```
case "$hintfile" in
"|' )
file=`echo "${osname}_${osvers}" | $sed -e 's%\.\%_ \%g' -e 's%_ \%`"
: Also try without trailing minor version numbers.
xfile=`echo
$file | $sed -e 's%_[^_]*$%%`
xxfile=`echo $xfile | $sed -e 's%_[^_]*$%%`
xxxfile=`echo $xxxfile | $sed -e 's%_[^_]*$%%`
xxxxfile=`echo $xxxxfile | $sed -e 's%_[^_]*$%%`
case "$file" in
") dflt=none ;;
*) case "$osvers" in
") dflt=$file
;;
*) if $test -f $src/hints/$file.sh ; then
dflt=$file
elif $test -f $src/hints/$xfile.sh ; then
dflt=$xfile
elif $test -f $src/hints/$xxxfile.sh ; then
dflt=$xxxfile
elif $test -f $src/hints/$xxxxfile.sh ; then
dflt=$xxxxfile
elif $test -f "$src/hints/${osname}.sh" ; then
dflt="${osname}"
else
dflt=none
fi
;;
esac
;;
esac
if $test -f Policy.sh ; then
case "$dflt" in
*Policy*) ;;
none) dflt="Policy" ;;
*) dflt="Policy $dflt" ;;
esac
fi
;;
*)
dflt=`echo $hintfile | $sed 's/\.sh$//`"
;;
```

```
esac
```

```
if $test -f Policy.sh ; then  
$cat <<EOM
```

There's also a Policy hint file available, which should make the site-specific (policy) questions easier to answer.
EOM

```
fi
```

```
$cat <<EOM
```

You may give one or more space-separated answers, or "none" if appropriate. If you have a handcrafted Policy.sh file or a Policy.sh file generated by a previous run of Configure, you may specify it as well as or instead of OS-specific hints. If hints are provided for your OS, you should use them: although Perl can probably be built without hints on many platforms, using hints often improve performance and may enable features that Configure can't set up on its own. If there are no hints that match your OS, specify "none"; DO NOT give a wrong version or a wrong OS.

```
EOM
```

```
rp="Which of these apply, if any?"  
. UU/myread  
tans=$ans  
for file in $ans; do  
if $test X$file = XPolicy -a -f Policy.sh; then  
. Policy.sh  
$cat Policy.sh >> UU/config.sh  
elif $test -f $src/hints/$file.sh; then  
. $src/hints/$file.sh  
$cat $src/hints/$file.sh >> UU/config.sh  
elif $test X"$ans" =  
X -o X"$ans" = Xnone ; then  
: nothing  
else  
: Give one chance to correct a possible typo.  
echo "$file.sh does not exist"  
dflt=$file  
rp="hint to use instead?"  
. UU/myread  
for file in $ans; do  
if $test -f "$src/hints/$file.sh"; then  
. $src/hints/$file.sh  
$cat $src/hints/$file.sh >> UU/config.sh
```

```

elif $test X$ans = X -o X$ans = Xnone ; then
    : nothing
else
    echo "$file.sh does not exist -- ignored."
fi
done
fi
done

hint=recommended
: Remember our hint file for later.
if $test -f "$src/hints/$file.sh" ; then
    hintfile="$file"
else
    hintfile=""
fi
fi
cd UU
?X: From here on, we must use $src instead of $src
@else
: Get old answers, if there is a config file out there
hint=default
hintfile=""
if test -f ../config.sh; then
    echo " "
    rp="I see a config.sh file. Shall I use it to set the defaults?"
    . ./myread
    case "$ans" in
n*|N*) echo "OK, I'll ignore it.";;
*) echo "Fetching default answers from your old config.sh file..."
>&4
    tmp_n="$n"
    tmp_c="$c"
    . ../config.sh
    cp ../config.sh .
    n="$tmp_n"
    c="$tmp_c"
    hint=previous
    ;;
esac
fi
@end
?X: remember, indentation is wrong--RAM
;;
*)
echo " "
echo "Fetching default answers from $config_sh..." >&4
tmp_n="$n"

```

```

tmp_c="$c"
cd ..
?X: preserve symbolic links, if any
cp $config_sh config.sh 2>/dev/null
chmod +w config.sh
./config.sh
cd UU
cp ../config.sh .
n="$tmp_n"
c="$tmp_c"
hint=previous
;;
esac
./optdef.sh

```

```

: Restore computed paths
for file in $loclist $strylist; do
eval $file="\$_$file"
done

```

```

@if osname || osvers
cat << EOM

```

Configure uses the operating system name and version to set some defaults. The default value is probably right if the name rings a bell. Otherwise, since spelling matters for me, either accept the default or answer "none" to leave it blank.

```

EOM
@end
@if osname
case "$osname" in
'| ')
case "$hintfile" in
'| '(none) dflt=none ;;
*) dflt=`echo $hintfile | $sed -e 's/\,sh$//' -e 's/_.*$//'^`
;;
esac
;;
*) dflt="$osname" ;;
esac
rp="Operating system name?"
./myread
case "$ans" in
none) osname="";;
*) osname=`echo "$ans" | $sed -e 's/[ ][ ]*/_/g' | ./tr '[A-Z]' '[a-z]'^`;
esac
@end

```

```

@if osvers
@if osname
echo " "
@end
case "$osvers" in
'| ')
case "$hintfile" in
'| |none) dflt=none ;;
*) dflt=`echo $hintfile | $sed -e 's/\.sh$//' -e 's/^[^_]*//'^
dflt=`echo $dflt | $sed -e 's/^[^_]*//'^ -e 's/_/./g'^
case "$dflt" in
'| ') dflt=none ;;
esac
;;
esac
;;
*) dflt="$osvers" ;;
esac
rp="Operating system version?"
./myread
case "$ans" in
none) osvers="" ;;
*) osvers="$ans" ;;
esac

@end

./posthint.sh

```

Found in path(s):

```

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/modified/Oldconfig.U

```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 2003 Jarkko Hietaniemi

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?MAKE:d_copysignl: Inlibc

?MAKE: -pick add \$@ %<

?S:d_copysignl:

?S: This variable conditionally defines the HAS_COPYSIGNL symbol, which

?S: indicates to the C program that the copysignl() routine is available.

?S: If aintl is also present we can emulate modfl.

?S:.

?C:HAS_COPYSIGNL:

?C: This symbol, if defined, indicates that the copysignl routine is

?C: available. If aintl is also present we can emulate modfl.

?C:.

?H:#\$d_copysignl HAS_COPYSIGNL /**/

?H:.

?LINT:set d_copysignl

: see if copysignl exists

set copysignl d_copysignl

eval \$inlibc

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_copysignl.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_wait3.U 1 2006-08-24 12:32:52Z rmanfredi \$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic Licence,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic Licence; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: d_wait3.U,v \$

?RCS: Revision 3.0 1993/08/18 12:08:01 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?MAKE:d_wait3: Inlibc

?MAKE: -pick add \$@ %<

?S:d_wait3:

?S: This variable conditionally defines the HAS_WAIT3 symbol, which

?S: indicates to the C program that the wait3() subroutine exists.

?S:.

?C:HAS_WAIT3:

?C: This symbol, if defined, indicates that the wait3() subroutine

?C: exists.

?C:.

?H:#\$d_wait3 HAS_WAIT3 /**/

?H:.

?LINT:set d_wait3

:

see if 'wait3()' exists

set wait3 d_wait3

eval \$inlibc

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/d_wait3.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 2014, H.Merijn Brand

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: d_dladdr.U,v \$

?RCS:

?MAKE:d_dladdr: Inlibc

?MAKE: -pick add \$@ %<

?S:d_dladdr:

?S: This variable conditionally defines the HAS_DLADDR symbol, which

?S: indicates to the C program that the dladdr() routine is available

?S: to get a stack trace.

?S:.

?C:HAS_DLADDR:

?C: This symbol, if defined, indicates that the dladdr() routine is

?C: available to query dynamic linker information for an address.

?C: The <dlfcn.h> header must be included to use this routine.

?C:.

?H:#\$d_dladdr HAS_DLADDR /**/

?H:.

?LINT:set d_dladdr

:

see if dladdr exists

set dladdr d_dladdr

eval \$inlibc

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/modified/d_dladdr.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: vendorman1.U,v 1.1 1999/07/08 18:32:57 doughera Exp doughera \$

?RCS:

?RCS: Copyright (c) 1999, Andy Dougherty

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 3.0.
?RCS:
?RCS: \$Log: vendorman1.U,v \$
?RCS: Revision 1.1 1999/07/08 18:32:57 doughera
?RCS: Initial revision
?RCS:
?MAKE:vendorman1 vendorman1exp installvendorman1: man1dir Getfile \
Oldconfig Setprefixvar Prefixit test vendorprefix prefix sed
?MAKE: -pick add \$@ %<
?Y:TOP
?S:vendorman1:
?S: This variable contains the name of the directory for man1
?S: pages. It may have a ~ on the front.
?S: The standard distribution will put nothing in this directory.
?S: Vendors who
distribute perl may wish to place their own
?S: man1 pages in this directory with
?S: MakeMaker Makefile.PL INSTALLDIRS=vendor
?S: or equivalent. See INSTALL for details.
?S:.
?S:vendorman1exp:
?S: This variable is the ~name expanded version of vendorman1, so that you
?S: may use it directly in Makefiles or shell scripts.
?S:.
?D:installvendorman1="
?S:installvendorman1:
?S: This variable is really the same as vendorman1exp but may differ on
?S: those systems using AFS. For extra portability, only this variable
?S: should be used in makefiles.
?S:.
?LINT:change prefixvar
?LINT:set installvendorman1
: Set the vendorman1 variables
case "\$vendorprefix" in
") vendorman1="
vendorman1exp="
;;
*) : determine where vendor-supplied manual pages go.
case "\$vendorman1" in
") dflt=`echo "\$man1dir" | \$sed "s#^\$prefix#\$vendorprefix#"` ;;
*) dflt=\$vendorman1 ;;
esac
case "\$dflt" in
"| ") dflt=none ;;
esac
fn=nd~+

```

rp='Pathname for the vendor-supplied manual section 1 pages?'
.
./getfile
vendorman1="$ans"
vendorman1exp="$ansexp"
;;
esac
: Use ' ' for none so value is preserved next time through Configure
$test X"$vendorman1" = "X" && vendorman1=' '
prefixvar=vendorman1
. ./installprefix

```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/installdirs/vendorman1.U
```

No license file was found, but licenses were detected in source scan.

```

?RCS: $Id: libc.U 1 2006-08-24 12:32:52Z rmanfredi $
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: $Log: libc.U,v $
?RCS: Revision 3.0.1.10 1997/02/28 15:56:48 ram
?RCS: patch61: replaced .a with $_a all over the place
?RCS: patch61: added support for HPUX-10 nm output
?RCS:
?RCS: Revision 3.0.1.9 1995/07/25 14:11:56 ram
?RCS: patch56: now knows about OS/2 platforms
?RCS:
?RCS: Revision 3.0.1.8 1995/05/12 12:20:47 ram
?RCS: patch54: made sure only most recent version of shared lib is picked
?RCS: patch54: final "nm -p" check now uses xscan and xrun
like everybody
?RCS: patch54: can now grok Linux nm output with lead __IO (ADO)
?RCS: patch54: added support for Linux ELF output, using 'W' for alias (ADO)
?RCS:
?RCS: Revision 3.0.1.7 1994/10/29 16:23:40 ram
?RCS: patch36: now looks for shared libraries before anything else (ADO)
?RCS: patch36: added new nm output format (ADO)
?RCS:
?RCS: Revision 3.0.1.6 1994/08/29 16:28:10 ram
?RCS: patch32: added I-type symbols for nm output parsing on Linux

```

```

?RCS:
?RCS: Revision 3.0.1.5 1994/06/20 07:03:24 ram
?RCS: patch30: checks are now presented by succession of if/elif
?RCS: patch30: uniformized checks for shared objects with new so symbol
?RCS:
?RCS: Revision 3.0.1.4 1994/05/06 15:06:33 ram
?RCS: patch23: added shared library knowledge (ADO and WED)
?RCS:
?RCS: Revision 3.0.1.3 1994/01/24 14:12:17 ram
?RCS: patch16: can now export nm_extract as an internal-use only variable
?RCS:
?RCS: Revision 3.0.1.2 1993/09/13 16:09:03 ram
?RCS: patch10: added special handling for Apollo
systems (WAD)
?RCS:
?RCS: Revision 3.0.1.1 1993/08/27 14:40:03 ram
?RCS: patch7: added entry for /usr/shlib/libc.so (OSF/1 machines)
?RCS:
?RCS: Revision 3.0 1993/08/18 12:08:57 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:libc +nm_extract: echo n c rm test grep Getfile Myread Oldconfig Loc \
sed libs incpath libpth ar runnm nm nm_opt nm_so_opt contains xlibpth \
so _a _o osname trnl tr sort uniq sysroot
?MAKE: -pick add $@ %<
?S:libc:
?S: This variable contains the location of the C library.
?S:.
?S:nm_extract:
?S: This variable holds the name of the extraction command used to process
?S: the output of nm and yield the list of defined symbols. It is used
?S: internally by Configure.
?S:.
?T:thislib try libnames xxx xscan xrun thisname com tans file
?F:!libnames !libc.tmp !tmp.imp
?LINT:extern PASE
?LINT:extern libnames
?LINT:change nm_opt
?INIT:libnames="
: Figure out where the libc is located
case "$runnm" in
true)
?X: indentation is wrong on purpose--RAM
:
get list of predefined functions in a handy place
echo " "
case "$libc" in
") libc=unknown

```

```

case "$libs" in
*-lc_s*) libc=`./loc libc_s$_a $libc $libpth`
esac
;;
esac
case "$libs" in
") ;;
*) for thislib in $libs; do
case "$thislib" in
-lc|lc_s)
: Handle C library specially below.
;;
-l*)
thislib=`echo $thislib | $sed -e 's/^-l//`
if try=`./loc lib$thislib.$so.*' X $libpth`; $test -f "$try"; then
:
elif try=`./loc lib$thislib.$so X $libpth`; $test -f "$try"; then
:
elif try=`./loc lib$thislib$_a X $libpth`; $test -f "$try"; then
:
elif try=`./loc $thislib$_a X $libpth`; $test -f "$try"; then
:
elif try=`./loc lib$thislib X $libpth`; $test -f "$try"; then
:
elif try=`./loc $thislib X $libpth`; $test -f "$try"; then
:
elif try=`./loc $lib$thislib$_a X $libpth`; $test -f "$try"; then
:
else
try="
fi
libnames="$libnames $try"
;;
*) libnames="$libnames $thislib" ;;
esac
done
;;
esac
?X:
?X: Some systems (e.g. DG/UX) use
"environmental" links, which make the test
?X: -f fail. Ditto for symbolic links. So in order to reliably check the
?X: existence of a file, we use test -r. It will still fail with DG/UX links
?X: though, but at least it will detect symbolic links. At some strategic
?X: points, we make use of (test -h), using a sub-shell in case builtin test
?X: does not implement the -h check for symbolic links. This makes it
?X: possible to preset libc in a hint file for instance and have it show up
?X: as-is in the question.

```

?X:

```
xxx=normal
case "$libc" in
unknown)
```

?X:

?X: The sed below transforms .so.9 .so.12 into something like .so.0009 .so.0012,

?X: then sorts on it to allow keeping .so.12 instead of .so.9 as the latest

?X: up-to-date library. The initial filename (before sed munging, saved in hold

?X: space via 'h') is appended via 'G' before sorting, then the leading munged

?X: part is removed after sorting. Nice efficient work from Tye McQueen.

?X: The initial blurfl is here to prevent the trailing

pipe from producing an

?X: empty string, causing Configure to output all its set variables!

?X:

```
set /lib/libc.$so
for xxx in $libpth; do
$test -r $1 || set $xxx/libc.$so
: The messy sed command sorts on library version numbers.
$test -r $1 || \
set `echo blurfl; echo $xxx/libc.$so.[0-9]* | \
tr ' ' $trnl | egrep -v \.[A-Za-z]*$' | $sed -e '
h
s/[0-9][0-9]*/0000&/g
s/0*\([0-9][0-9][0-9][0-9][0-9]\)^1/g
G
s^n/' | \
$sort | $sed -e 's/^.* //'^
eval set `set`
done
$test -r $1 || set $sysroot/usr/ccs/lib/libc.$so
$test -r $1 || set $sysroot/lib/libsys_s$a
;;
*)
```

?X: ensure the test below for the (shared) C library will fail

```
set blurfl
```

```
::
```

```
esac
```

```
if $test -r "$1"; then
```

```
echo "Your (shared) C library seems to be in $1."
```

```
libc="$1"
```

```
elif $test -r /lib/libc && $test -r /lib/clib; then
```

?X:

?X: Apollo has its C library in /lib/clib AND /lib/libc

?X: not to mention its math library in /lib/syslib...

?X:

```
echo "Your C library seems to be in both /lib/clib
and /lib/libc."
```

```
xxx=apollo
```

```

libc=/lib/club /lib/libc'
if $test -r /lib/syslib; then
  echo "(Your math library is in /lib/syslib.)"
?X: Put syslib in libc -- not quite right, but won't hurt
  libc="$libc /lib/syslib"
fi
elif $test -r "$libc" || (test -h "$libc") >/dev/null 2>&1; then
  echo "Your C library seems to be in $libc, as you said before."
?X: For mips, and...
elif $test -r $incpath/usr/lib/libc$_a; then
  libc=$incpath/usr/lib/libc$_a;
  echo "Your C library seems to be in $libc. That's fine."
elif $test -r /lib/libc$_a; then
  libc=/lib/libc$_a;
  echo "Your C library seems to be in $libc. You're normal."
else
if tans=`./loc libc$_a blurfl/dyick $libpth`; $test -r "$stans"; then
  :
elif tans=`./loc libc blurfl/dyick $libpth`; $test -r "$stans"; then
  libnames="$libnames "`./loc club blurfl/dyick $libpth`
elif tans=`./loc club blurfl/dyick $libpth`; $test -r "$stans"; then
  :
elif tans=`./loc Slibc$_a blurfl/dyick $xlibpth`; $test -r "$stans"; then
  :
elif tans=`./loc
Mlibc$_a blurfl/dyick $xlibpth`; $test -r "$stans"; then
  :
else
  tans=`./loc Llibc$_a blurfl/dyick $xlibpth`
fi
if $test -r "$stans"; then
  echo "Your C library seems to be in $stans, of all places."
  libc=$stans
else
  libc='blurfl'
fi
fi
if $test $xxx = apollo -o -r "$libc" || (test -h "$libc") >/dev/null 2>&1; then
  dflt="$libc"
cat <<EOM

```

If the guess above is wrong (which it might be if you're using a strange compiler, or your machine supports multiple models), you can override it here.

```

EOM
else
dflt="
echo $libpth | $tr ' ' $trnl | $sort | $uniq > libpath

```

```
cat >&4 <<EOM
```

I can't seem to find your C library. I've looked in the following places:

```
EOM
```

```
$sed 's/^/ /' libpath
```

```
cat <<EOM
```

None of these seems to contain your C library. I need to get its name...

```
EOM
```

```
fi
```

```
fn=f
```

```
rp='Where is your C library?'
```

```
./getfile
```

```
libc="$ans"
```

```
echo " "
```

```
echo $libc $libnames | $tr ' ' $trnl | $sort | $uniq > libnames
```

```
set X `cat libnames`
```

```
shift
```

```
xxx=files
```

```
case $# in 1) xxx=file; esac
```

```
echo
```

```
"Extracting names from the following $xxx for later perusal:" >&4
```

```
echo " "
```

```
$sed 's/^/ /' libnames >&4
```

```
echo " "
```

```
$echo $n "This may take a while...$c" >&4
```

```
?X:
```

?X: Linux may need the special Dynamic option to nm for shared libraries.

?X: In general, this is stored in the nm_so_opt variable.

?X: Unfortunately, that option may be fatal on non-shared libraries.

```
?X:
```

```
for file in $*; do
```

```
case $file in
```

```
*$so*) $nm $nm_so_opt $nm_opt $file 2>/dev/null;;
```

```
*) $nm $nm_opt $file 2>/dev/null;;
```

```
esac
```

```
done >libc.tmp
```

```
$echo $n ".$c"
```

```
?X:
```

?X: To accelerate processing, we look at the correct 'sed' command

?X: by using a small subset of libc.tmp, i.e. fprintf function.

?X: When we know which sed command to use, do the name extraction

```
?X:
```

```
$grep fprintf libc.tmp > libc.ptf
```

?X:

?X: In order to enhance readability and save some space, we define

?X: some variables that will be "eval"ed.

?X:

```
xscan='eval "<libc.ptf $com >libc.list"; $echo $n ".$c" >&4'
```

```
xrun='eval "<libc.tmp $com >libc.list"; echo "done." >&4'
```

?X:

BSD-like output, I and W types added for Linux

?X: Some versions of Linux include a leading __IO in the symbol name.

?X: HP-UX 10 reportedly has trailing spaces, though I'm surprised it has

?X: BSD-like output. (AD).

?X: GNU extension: i is "indirect function"

```
xxx='[ADTSIW]'
```

```
if com="$sed -n -e 's/__IO//' -e 's/^. *$xxx */p';\
```

```
eval $xscan;\
```

```
$contains '^fprintf$' libc.list >/dev/null 2>&1; then
```

```
eval $xrun
```

?X: SYSV-like output

```
elif com="$sed -n -e 's/___ */' -e 's/^\([a-zA-Z_0-9$]*\).*xtern.*\1/p';\
```

```
eval $xscan;\
```

```
$contains '^fprintf$' libc.list >/dev/null 2>&1; then
```

```
eval $xrun
```

```
elif com="$sed -n -e '/|UNDEF/d' -e '/FUNC..GL/s/^. *|___ */p';\
```

```
eval $xscan;\
```

```
$contains '^fprintf$' libc.list >/dev/null 2>&1; then
```

```
eval $xrun
```

```
elif com="$sed -n -e 's/^. *D ___ */p' -e 's/^. *D //p';\
```

```
eval $xscan;\
```

```
$contains '^fprintf$' libc.list >/dev/null 2>&1; then
```

```
eval $xrun
```

```
elif com="$sed -n -e 's/_/' -e 's/^\([a-zA-Z_0-9$]*\).*xtern.*text.*\1/p';\
```

```
eval $xscan;\
```

```
$contains '^fprintf$'
```

```
libc.list >/dev/null 2>&1; then
```

```
eval $xrun
```

```
elif com="$sed -n -e 's/^. *|FUNC |GLOB .*/p';\
```

```
eval $xscan;\
```

```
$contains '^fprintf$' libc.list >/dev/null 2>&1; then
```

```
eval $xrun
```

```
elif com="$grep '|' $sed -n -e '/|COMMON/d' -e '/|DATA/d' \
```

```
-e '/ file/d' -e 's/^\([ ^ ]*\).*\1/p';\
```

```
eval $xscan;\
```

```
$contains '^fprintf$' libc.list >/dev/null 2>&1; then
```

```
eval $xrun
```

```
elif com="$sed -n -e 's/^. *|FUNC |GLOB .*/p' -e 's/^. *|FUNC |WEAK .*/p';\
```

```
eval $xscan;\
```

```
$contains '^fprintf$' libc.list >/dev/null 2>&1; then
```

```
eval $xrun
```

```

?X: mips nm output (sysV)
elif com="$sed -n -e 's/^__/' -e '/|Undef/d' -e '/|Proc/s/ .*//p'";\
eval $xscan;\
$contains '^fprintf$' libc.list >/dev/null 2>&1; then
eval $xrun
elif com="$sed -n -e 's/^.*|Proc .*|Text *| *//p'";\
eval $xscan;\
$contains '^fprintf$' libc.list >/dev/null 2>&1; then
eval $xrun
elif com="$sed -n -e '/Def. Text/s/.* \([^ ]*\)\$/\1/p'";\
eval $xscan;\
$contains '^fprintf$' libc.list >/dev/null 2>&1; then
eval $xrun
?X: OS/2
nm output
elif com="$sed -n -e 's/^[-0-9a-f ]*_\(.*)=.*\1/p'";\
eval $xscan;\
$contains '^fprintf$' libc.list >/dev/null 2>&1; then
eval $xrun
elif com="$sed -n -e 's/.*\text n\ \ \ \.//p'";\
eval $xscan;\
$contains '^fprintf$' libc.list >/dev/null 2>&1; then
eval $xrun
?X: AIX nm output
elif com="sed -n -e 's/^__.*// -e 's/[ ]*D[ ]*[0-9]*.*//p'";\
eval $xscan;\
$contains '^fprintf$' libc.list >/dev/null 2>&1; then
eval $xrun
else
$nm -p $* 2>/dev/null >libc.tmp
$grep fprintf libc.tmp > libc.ptf
if com="$sed -n -e 's/.* [ADTSIW] *[_.]*/p' -e 's/.* [ADTSIW] //p'";\
eval $xscan; $contains '^fprintf$' libc.list >/dev/null 2>&1
then
nm_opt='-p'
eval $xrun
else
echo " "
echo "$nm didn't seem to work right. Trying $ar instead..." >&4
com="
if $ar t $libc > libc.tmp && \
$contains '^fprintf$' libc.tmp >/dev/null 2>&1
then
for thisname in $libnames $libc; do
$ar t $thisname >>libc.tmp
done
$sed -e "s/\$_o\$//" < libc.tmp > libc.list
echo

```

```

"Ok." >&4
elif test "X$osname" = "Xos2" && $ar tv $libc > libc.tmp; then
?X: Repeat libc to extract forwarders to DLL entries too
  for thisname in $libnames $libc; do
    $ar tv $thisname >>libc.tmp
?X: Revision 50 of EMX has bug in ar: it will not extract forwarders
?X: to DLL entries. Use emximp which will extract exactly them.
    emximp -o tmp.imp $thisname \
      2>/dev/null && \
      $sed -e 's/^\([_a-zA-Z0-9]*\) .*$/1/p' \
      < tmp.imp >>libc.tmp
    $rm -f tmp.imp
  done
  $sed -e "s/^\$_o\$//" -e 's/^\ |+/ ' < libc.tmp > libc.list
  echo "Ok." >&4
else
  echo "$ar didn't seem to work right." >&4
  echo "Maybe this is a Cray...trying bld instead..." >&4
  if bld t $libc | \
    $sed -e 's/.*\///' -e "s/^\$_o:.*\$//" > libc.list &&
    $test -s libc.list
  then
    for thisname in $libnames; do
      bld t $libnames | \
        $sed -e 's/.*\///' -e "s/^\$_o:.*\$//" >>libc.list
      $ar t $thisname >>libc.tmp
    done
    echo "Ok." >&4
  else
    echo
    "That didn't work either. Giving up." >&4
    exit 1
  fi
fi
fi
fi
nm_extract="$com"
case "$PASE" in
define)
  echo " "
  echo "Since you are compiling for PASE, extracting more symbols from libc.a ..." >&4
  dump -Tv /lib/libc.a | awk '$7 == "/unix" {print $5 " " $8}' | grep "^SV" | awk '{print $2}' >> libc.list
  ;;
*) if $test -f /lib/syscalls.exp; then
  echo " "
  echo "Also extracting names from /lib/syscalls.exp for good ole AIX..." >&4
  $sed -n 's/^\([^\ ]*\)[ \]*syscall[0-9]*[ \]*$/1/p' \
    /lib/syscalls.exp >>libc.list

```

```
fi
;;
esac
;;
esac
$rm -f libnames libpath
```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/modified/libc.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: d_tzname.U 1 2006-08-24 12:32:52Z rmanfredi $
```

```
?RCS:
```

```
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
```

```
?RCS:
```

```
?RCS: You may redistribute only under the terms of the Artistic Licence,
```

```
?RCS: as specified in the README file that comes with the distribution.
```

```
?RCS: You may reuse parts of this distribution only within the terms of
```

```
?RCS: that same Artistic Licence; a copy of which may be found at the root
```

```
?RCS: of the source tree for dist 4.0.
```

```
?RCS:
```

```
?RCS: $Log: d_tzname.U,v $
```

```
?RCS: Revision 3.0.1.2 1994/08/29 16:14:43 ram
```

```
?RCS: patch32: forgot to set proper value in the val variable
```

```
?RCS:
```

```
?RCS: Revision 3.0.1.1 1994/06/20 06:57:55 ram
```

```
?RCS: patch30: created
```

```
?RCS:
```

```
?MAKE:d_tzname: Csym Setvar
```

```
?MAKE: -pick add $@ %<
```

```
?S:d_tzname:
```

```
?S: This variable conditionally defines HAS_TZNAME if tzname[] is
```

```
?S: available to access timezone names.
```

```
?S:.
```

```
?C:HAS_TZNAME:
```

```
?C: This symbol, if defined, indicates that the tzname[]
```

```
array is
```

```
?C: available to access timezone names.
```

```
?C:.
```

```
?H:#$d_tzname HAS_TZNAME /**/
```

```
?H:.
```

```
?LINT:set d_tzname
```

```
: see if tzname[] exists
```

```
echo " "
```

```
if set tzname val -a d_tzname; eval $csym; $val; then
```

```
val="$define"
```

```
echo 'tzname[] found.' >&4
```

```
else
val="$undef"
echo 'tzname[] NOT found.' >&4
fi
set d_tzname
eval $setvar
```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/d_tzname.U
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: Copyright (c) 1998 Andy Dougherty

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?RCS:

?X:

?X: This unit is just a quick shorthand for the compile command

?X: to be used in all the other metaconfig units.

?X:

?MAKE:Compile: +cc +optimize +ccflags +ldflags +libs

?MAKE: -pick add \$@ %<

?LINT:define compile compile_ok

?V:compile compile_ok mc_file

?S:compile:

?S: This shell variable is used internally

by Configure to provide

?S: a convenient shorthand for the typical compile command, namely

?S: \$cc \$optimize \$ccflags \$ldflags -o \$1 \$1.c \$libs > /dev/null 2>&1

?S: Note that the output filename does not include the _exe

?S: extension. Instead we assume that the linker will be

?S: "helpful" and automatically appending the correct suffix.

?S: OS/2 users will apparently need to supply the -Zexe flag to

?S: get this behavior.

?S:

?S: To use this variable, say something like:

```

?S: echo 'int main() { exit(0); }' > try.c
?S: set try
?S: if eval $compile; then
?S: echo "success" # and do whatever . . .
?S: else
?S: echo "failure" # and do whatever . . .
?S: fi
?S: To add extra flags cc flags (e.g. -DWHATEVER) just put them
?S: in $*, e.g.
?S: set try -DTRY_THIS_FLAG
?S:.
?S:compile_ok:
?S: This shell variable is used internally by Configure to provide
?S: a convenient shorthand for the typical compile command that you
?S: expect to work ok. It is the same as $compile,
?S: except we
?S: deliberately let the user see any error messages.
?S:.
: define a shorthand compile call
compile='
mc_file=$1;
shift;
$cc -o ${mc_file} $optimize $ccflags $ldflags $* ${mc_file}.c $libs > /dev/null 2>&1;'
: define a shorthand compile call for compilations that should be ok.
compile_ok='
mc_file=$1;
shift;
$cc -o ${mc_file} $optimize $ccflags $ldflags $* ${mc_file}.c $libs;'

```

Found in path(s):

```

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/Compile.U

```

No license file was found, but licenses were detected in source scan.

```

?RCS: $Id: libnlist.U 1 2006-08-24 12:32:52Z rmanfredi $
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: $Log: libnlist.U,v $
?RCS: Revision 3.0.1.1 1997/02/28 16:08:02 ram
?RCS: patch61: added usrinc and mips on the dependency line
?RCS: patch61: make sure we call ./mips

```

```

?RCS: patch61: added a ?LINT: hint
?RCS:
?RCS: Revision 3.0 1993/08/18 12:09:00 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:libnlist: Loc libpth Guess us rinc _a
?MAKE: -pick add $@ %<
?S:libnlist (libmld):
?S: This variable contains the name of the library required to
get the
?S: definition of the nlist() function. On a MIPS RISC/OS box, it is -lml.
?S: Under Sys Vr4, it is -lelf. Otherwise, its value is empty.
?S:.
?T:xxx
?LINT:use us rinc
: see if we need a special library for 'nlist()'
echo " "
: How about doing this if nlist is not in libc...
if ./mips ; then
libnlist='-lml'
else
xxx=`./loc libelf$_a x $libpth`
case "$xxx" in
x) ;;
*)
libnlist="$xxx"
;;
esac
fi
case "$libnlist" in
") echo "No special library for nlist() seems necessary." >&4
;;
*) echo "nlist() can be found in $libnlist." >&4
;;
esac

```

Found in path(s):

```

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/libnlist.U

```

No license file was found, but licenses were detected in source scan.

```

?RCS: $Id: uidtype.U,v 3.0.1.3 1994/08/29 16:33:25 ram Exp $

```

```

?RCS:

```

```

?RCS: Copyright (c) 1991-1993, Raphael Manfredi

```

```

?RCS:

```

```

?RCS: You may redistribute only under the terms of the Artistic License,

```

```

?RCS: as specified in the README file that comes with the distribution.

```

```

?RCS: You may reuse parts of this distribution only within the terms of

```

?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 3.0.
?RCS:
?RCS: \$Log: uidtype.U,v \$
?RCS: Revision 3.0.1.3 1994/08/29 16:33:25 ram
?RCS: patch32: now uses new Typedef unit to compute type information
?RCS:
?RCS: Revision 3.0.1.2 1994/06/20 07:09:36 ram
?RCS: patch30: comment for uidtype referred to the obsoleted symbol
?RCS:
?RCS: Revision 3.0.1.1 1994/05/13 15:28:27 ram
?RCS: patch27: made conformant to its gidtype.U companion
?RCS: patch27: question now explicitly mentions getuid()
?RCS:
?RCS: Revision 3.0 1993/08/18
12:09:56 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:uidtype: Myread Typedef Findhdr
?MAKE: -pick add \$@ %<
?S:uidtype:
?S: This variable defines Uid_t to be something like uid_t, int,
?S: ushort, or whatever type is used to declare user ids in the kernel.
?S:.
?C:Uid_t (UIDTYPE):
?C: This symbol holds the type used to declare user ids in the kernel.
?C: It can be int, ushort, uid_t, etc... It may be necessary to include
?C: <sys/types.h> to get any typedef'ed information.
?C:.
?H:#define Uid_t \$uidtype /* UID type */
?H:.
?T:xxx
: see what type uids are declared as in the kernel
echo " "
echo "Looking for the type for user ids returned by getuid()."
set uid_t uidtype xxx stdio.h sys/types.h
eval \$typedef
case "\$uidtype" in
xxx)
xxx=`./findhdr sys/user.h`
set `grep '_ruid;' "\$xxx" 2>/dev/null` unsigned short
case \$1 in
unsigned) dflt="\$1 \$2" ;;
*) dflt="\$1" ;;
esac
;;
*) dflt="\$uidtype";;
esac

```
case "$uidtype" in
uid_t) echo "uid_t found." ;;
*) rp="What
is the type for user ids returned by getuid()?"
./myread
uidtype="$ans"
;;
esac
```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/typedefs/uidtype.U
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: Head.U,v \$

?RCS: Revision 3.0.1.9 1997/02/28 15:02:09 ram

?RCS: patch61: make sure we unset CDPATH for shells that support this

?RCS: patch61: improved Korn shell detection and handling

?RCS:

?RCS: Revision 3.0.1.8 1995/07/25 13:40:02 ram

?RCS: patch56: added SVR4-ish /opt directories to path list (ADO)

?RCS: patch56: OS/2 platforms are using another path separator

?RCS:

?RCS: Revision 3.0.1.7 1995/03/21 08:46:15 ram

?RCS: patch52: definition of paths wrongly added spurious ':' chars

?RCS:

?RCS:

Revision 3.0.1.6 1994/10/29 15:54:19 ram

?RCS: patch36: make sure ENV is unset before calling /bin/ksh

?RCS:

?RCS: Revision 3.0.1.5 1994/08/29 16:03:44 ram

?RCS: patch32: now sets PATH only using existing directories

?RCS:

?RCS: Revision 3.0.1.4 1994/06/20 06:54:28 ram

?RCS: patch30: now computes its invocation name into 'me'

?RCS: patch30: symbol me is made visible to all units read-only

?RCS:

?RCS: Revision 3.0.1.3 1993/12/15 08:15:07 ram

```

?RCS: patch15: added /sbin:/usr/sbin:/usr/libexec in PATH for BSD/386
?RCS:
?RCS: Revision 3.0.1.2 1993/11/10 17:32:35 ram
?RCS: patch14: ensure PATH is reset to '.' before testing for alias
?RCS:
?RCS: Revision 3.0.1.1 1993/08/27 14:38:07 ram
?RCS: patch7: not all 'test' programs support the -x option
?RCS:
?RCS: Revision 3.0 1993/08/18 12:04:58 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?X:
?X: This is the very first unit in the Configure script. It is mostly just
?X: things to keep people from getting
?X: into a tizzy right off the bat.
?X:
?MAKE:Head:
?MAKE: -pick wipe $@ %<
?V:PATH p__exe me newsh
?T:argv Id p paths OS2_SHELL DJGPP
?T:inksh needksh avoidksh newsh changesh reason
?F:!*
?LINT:extern ENV CDPATH SHELL MACHTYPE
?LINT:change ENV CDPATH
?LINT:nocomment
#!/bin/sh
#
# If these # comments don't work, trim them. Don't worry about any other
# shell scripts, Configure will trim # comments from them for you.
#
# (If you are trying to port this package to a machine without sh,
# I would suggest you have a look at the prototypical config_h.SH file
# and edit it to reflect your system. Some packages may include samples
# of config.h for certain machines, so you might look for one of those.)
#
?X:
?X: NOTE THAT A CONFIGURE SCRIPT IS IN THE PUBLIC DOMAIN (whether or not
?X: the software which uses it is in the public domain).
?X:
# Yes, you may rip this off to use in other distribution packages. This
# script belongs to the public domain and cannot be copyrighted.
#
?X:
?X: WE ASK YOU
NOT TO REMOVE OR ALTER THE FOLLOWING PARAGRAPH, PLEASE:
?X:
# Note: this Configure script was generated automatically. Rather than
# working with this copy of Configure, you may wish to get metaconfig.

```

```
# The dist package (which contains metaconfig) is available via SVN:
#   svn co https://svn.code.sf.net/p/dist/code/trunk/dist
?X:
?X: NOTA BENE:
?X: If you develop you own version of metaconfig based on this work,
?X: you have to add some comments telling that the script was generated
?X: by your version, not mine: It credits your work.
?X:
```

```
# $Id: Head.U 6 2006-08-25 22:21:46Z rmanfredi $
#
# Generated on <DATE> [metaconfig <VERSION> PL<PATCHLEVEL>]
```

```
cat >c1$$ <<EOF
ARGGGHHHH!!!!
```

SCO csh still thinks true is false. Write to SCO today and tell them that next year Configure ought to "rm /bin/csh" unless they fix their blasted shell. :-)

(Actually, Configure ought to just patch csh in place. Hmm. Hmmmmm. All we'd have to do is go in and swap the && and || tokens, wherever they are.)

```
[End
of diatribe. We now return you to your regularly scheduled programming...]
EOF
cat >c2$$ <<EOF
```

```
OOPS! You naughty creature! You didn't run Configure with sh!
I will attempt to remedy the situation by running sh for you...
EOF
```

```
true || cat c1$$ c2$$
true || exec sh $0 $argv:q
```

```
(exit $?0) || cat c2$$
(exit $?0) || exec sh $0 $argv:q
rm -f c1$$ c2$$
```

```
: compute my invocation name
me=$0
case "$0" in
*/*)
me=`echo $0 | sed -e 's!.*\!(.*)!\1!' 2>/dev/null`
test "$me" || me=$0
;;
esac
```

```
?X:
```

?X: To be able to run under OS/2, we must detect that early enough to use

?X: the proper path separator, stored in \$p_. It is : on UNIX and ; on

?X: DOSish systems such as OS/2.

?X:

: Proper separator for the PATH environment variable

p_=:

: On OS/2 this directory should exist if this is not floppy only system ":-]"

if test -d c:/.; then

if test -n "\$OS2_SHELL"; then

p_=\;

PATH=`cmd /c "echo %PATH%" | tr '\\\` /`

?X: That's a bug in ksh5.22

OS2_SHELL=`cmd /c "echo %OS2_SHELL%" | tr

'\\\' / | tr '[A-Z]' [a-z]`

elif test -n "\$DJGPP"; then

case "X\${MACHTYPE:-nonosuchmach}" in

*cygwin) ;;

*) p_=\; ;;

esac

fi

fi

?X:

?X: There are two schools of thoughts here. Some people correctly argue that

?X: the user has a better chance than we do of setting a reasonable PATH and

?X: others argue that Configure is the best place there is to set up a suitable

?X: PATH. Well, here we try to compromise by keeping the user's PATH and

?X: appending some directories which are known to work on some machine or the

?X: other. The rationale behind this being that a novice user might not have a

?X: proper environment variable set, and some directories like /etc (where

?X: chown is located on some BSD systems) may be missing--RAM.

?X:

?X: SVR4 adds an /opt directory for optional packages. Some sites use

?X: various permutations on /opt as opposed to /usr or /usr/local.-- ADO

?X:

?X: We only add directories that are not already in the PATH of the

?X: user and the directories must

exist also.

?X:

: Proper PATH setting

paths=/bin /usr/bin /usr/local/bin /usr/ucb /usr/local /usr/lbin'

paths="\$paths /opt/bin /opt/local/bin /opt/local /opt/lbin"

paths="\$paths /usr/5bin /etc /usr/gnu/bin /usr/new /usr/new/bin /usr/nbin"

paths="\$paths /opt/gnu/bin /opt/new /opt/new/bin /opt/nbin"

paths="\$paths /sys5.3/bin /sys5.3/usr/bin /bsd4.3/bin /bsd4.3/usr/ucb"

paths="\$paths /bsd4.3/usr/bin /usr/bsd /bsd43/bin /usr/ccs/bin"

paths="\$paths /etc /usr/lib /usr/ucb/lib /lib /usr/ccs/lib"

paths="\$paths /sbin /usr/sbin /usr/libexec"

```
paths="$paths /system/gnu_library/bin"
```

```
for p in $paths
do
case "$p_${PATH}$p_" in
*$p_${p}$p_*) ;;
*) test -d $p && PATH=${PATH}$p_${p} ;;
esac
done
```

```
PATH=.$p_${PATH}
export PATH
```

: shall we be using ksh?

```
inksh=""
```

```
needksh=""
```

```
avoidksh=""
```

```
newsh=/bin/ksh
```

```
changesh=""
```

?X: Use (alias -x) and not (alias) since zsh and bash recognize the alias

?X: builtin but not the -x option which is typically ksh...

?X: We need to set up PATH before calling the "alias" built-in since
some

?X: systems like HP-UX have a binary called /bin/alias.

```
if (PATH=.; alias -x) >/dev/null 2>&1; then
```

```
inksh=true
```

```
fi
```

?X: On HP-UX, large Configure scripts may exercise a bug in /bin/sh, use ksh

```
if test -f /hp-ux -a -f /bin/ksh; then
```

```
needksh='to avoid sh bug in "here document" expansion'
```

```
fi
```

?X: On AIX4, /bin/sh is really ksh and it causes problems, use sh

```
if test -d /usr/lpp -a -f /usr/bin/bsh -a -f /usr/bin/uname; then
```

```
if test X`/usr/bin/uname -v` = X4; then
```

```
avoidksh="to avoid AIX 4's /bin/sh"
```

```
newsh=/usr/bin/bsh
```

```
fi
```

```
fi
```

?X: On Digital UNIX, /bin/sh may start up buggy /bin/ksh, use sh

```
if test -f /osf_boot -a -f /usr/sbin/setld; then
```

```
if test X`/usr/bin/uname -s` = XOSF1; then
```

```
avoidksh="to avoid Digital UNIX' ksh"
```

```
newsh=/bin/sh
```

?X: if BIN_SH is set to 'xpg4', sh will start up ksh

```
unset BIN_SH
```

```
fi
```

```
fi
```

?X: If we are not in ksh and need it, then feed us back to it

```

case "$sinksh/$needksh" in
/[a-z]*)
?X: Clear ENV to avoid any ~/.kshrc that could alias cd or whatever...
?X: Don't
use "unset ENV", that is not portable enough
ENV="
changesh=true
reason="$needksh"
;;
esac
?X: If we are in ksh and must avoid it, then feed us back to a new shell
case "$sinksh/$avoidksh" in
true/[a-z]*)
changesh=true
reason="$avoidksh"
;;
esac
?X: Warn them if they use ksh on other systems, which are those where
?X: we don't need ksh nor want to avoid it explicitly, yet are using it.
case "$sinksh/$needksh-$avoidksh-" in
true/--)
cat <<EOM
(I see you are using the Korn shell. Some ksh's blow up on $me,
mainly on older exotic systems. If yours does, try the Bourne shell instead.)
EOM
;;
esac
case "$changesh" in
true)
export newsh
echo "(Feeding myself to $newsh $reason.)"
?X: Make sure they didn't say sh <Configure by checking whether $0 ends
?X: with Configure or not. If they did say sh <././Configure, then too
?X: bad for them anyway, since we lost that path indication...
?X: Otherwise, execing $0 ensures we keep the full remote source dir
?X: indication for src.U.
case
"$0" in
Configure|*/Configure) exec $newsh $0 "$@";;
*) exec $newsh Configure "$@";;
esac
;;
esac
?X: Unset CDPATH to avoid surprises when using cd under some shells
?X: Can't unset it because that's not portable to very old shells.
?X: Can't set it to " because then bash 2.02 won't do "cd UU" --AD 6/98.
?X: Don't want to set it to '.' because then ksh prints out the

```

```
?X: name of the directory every time you cd to it. --AD 6/98
?X: In order to inflict the least harm, change it only if it's set.
: if needed, set CDPATH to a harmless value that is not chatty
case "$CDPATH" in
") ;;
*) case "$SHELL" in
*bash*) CDPATH='.' ;;
*) CDPATH="" ;;
esac
;;
esac
```

```
: Configure runs within the UU subdirectory
test -d UU || mkdir UU
?X: Use ./* to avoid any confirmation prompts from enhanced shells -- WED
cd UU && rm -f ./*
```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/Head.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: i_sched.U,v $
?RCS:
?RCS: Copyright (c) 1999 Jarkko Hietaniemi
?RCS:
?RCS: You may distribute under the terms of either the GNU General Public
?RCS: License or the Artistic License, as specified in the README file.
?RCS:
?MAKE:i_sched: Inhdr Hasfield
?MAKE:-pick add $@ %<
?S:i_sched:
?S: This variable conditionally defines the I_SCHED symbol, and indicates
?S: whether a C program should include <sched.h>.
?S:.
?C:I_SCHED:
?C: This symbol, if defined, indicates that <sched.h> exists and
?C: should be included.
?C:.
?H:#$i_sched I_SCHED /**/
?H:.
?LINT:set i_sched
: see if this is a sched.h system
set sched.h i_sched
eval $inhdr
```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
```

debian-perl-5.26.1/U/perl/i_sched.U

No license file was found, but licenses were detected in source scan.

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?MAKE:d_memmem: Inlibc

?MAKE: -pick add \$@ %<

?S:d_memmem:

?S: This variable conditionally defines the HAS_MEMMEM symbol, which

?S: indicates to the C program that the memmem() routine is available

?S: to return a pointer to the start of the first occurrence of a

?S: substring in a memory area (or NULL if not found).

?S:.

?C:HAS_MEMMEM:

?C: This symbol, if defined, indicates that the memmem routine is

?C: available to return a pointer to the start of the first occurrence

?C: of a substring in a memory area (or NULL if not found).

?C:.

?H:#\$d_memmem HAS_MEMMEM /**/

?H:.

?LINT:set d_memmem

: see if memmem exists

set memmem d_memmem

eval \$inlibc

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-

debian-perl-5.26.1/U/perl/d_memmem.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: i_sysuio.U,v \$

?RCS:

?RCS: Copyright (c) 1998 Jarkko Hietaniemi

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?MAKE:i_sysuio: Inhdr

?MAKE: -pick add \$@ %<

?S:i_sysuio:

?S: This variable conditionally defines the I_SYSUIO symbol, and indicates

?S: whether a C program should include <sys/uio.h>.

?S:.

?C:I_SYSUIO:

?C: This symbol, if defined, indicates that <sys/uio.h> exists and

?C: should be included.

?C:.

?H:#\$i_sysuio L_SYSUIO /**/

?H:.

?LINT:set i_sysuio

: see if this is a sys/uio.h system

set sys/uio.h i_sysuio

eval \$inhdr

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/modified/i_sysuio.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 2000 Jarkko Hietaniemi

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?MAKE:d_setrlimit: Inlibc

?MAKE: -pick add \$@ %<

?S:d_setrlimit:

?S: This variable conditionally defines the HAS_SETRLIMIT symbol, which

?S: indicates to the C program that the setrlimit() routine is available.

?S:.

?C:HAS_SETRLIMIT:

?C: This symbol, if defined, indicates that the setrlimit routine is

?C: available to set process resource limits.

?C:.

?H:#\$d_setrlimit HAS_SETRLIMIT /**/

?H:.

?LINT:set d_setrlimit

: see if setrlimit exists

set setrlimit d_setrlimit

eval \$inlibc

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_setrlimit.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1999, Jarkko Hietaniemi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 3.0.

?RCS:

?MAKE:d_sem_init: Inlibc

?MAKE: -pick add \$@ %<

?S:d_sem_init:

?S: This variable conditionally defines HAS_SEM_INIT if sem_init() is

?S: available to initialize a POSIX semaphore.

?S:.

?C:HAS_SEM_INIT:

?C: This symbol, if defined, indicates that the sem_init system call is

?C: available to initialize a POSIX semaphore.

?C:.

?H:#\$d_sem_init HAS_SEM_INIT /**/

?H:.

?LINT:set d_sem_init

: see if sem_init exists

set sem_init d_sem_init

eval \$inlibc

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_sem_init.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: Config_sh.U,v \$

?RCS: Revision 3.0.1.3 1997/02/28 14:57:53 ram

?RCS: patch61: added support for src.U

?RCS:

?RCS: Revision 3.0.1.2 1995/01/11 14:53:31 ram

?RCS: patch45: moved path stripping from d_portable.U to end of Configure

?RCS:

?RCS: Revision 3.0.1.1 1994/10/29 15:50:37 ram

?RCS: patch36: added ?F: line for metalint file checking

?RCS:

?RCS: Revision 3.0 1993/08/18 12:04:48 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

```

?X:
?X: This unit ends up producing the config.sh
    script, which contains all the
?X: definitions figured out by Configure. The add.Config_sh command knows
?X: which variables need to be remembered. It also adds the EOT (ends the
?X: here document redirection with variable substitution).
?X:
?MAKE:Config_sh: cf_time cf_by test spitshell startsh myuname Myread \
    End Obsol_sh Loc +d_portable package src cat sed
?MAKE: -pick add.Config_sh $@ %<
?MAKE: -pick add $@ ./Obsol_sh
?MAKE: -pick close.Config_sh $@ %<
?F:!config.over !config.arch
?T:file sfile xsed
?LINT:unclosed EOT
: back to where it started
if test -d ../UU; then
    cd ..
fi

```

```

: configuration may be unconditionally patched via a 'config.arch' file
if $test -f config.arch; then
    echo "I see a config.arch file, loading it." >&4
    . ./config.arch
fi

```

```

: configuration may be patched via a 'config.over' file
if $test -f config.over; then
    echo " "
    dflt=y
    rp='I see a config.over file. Do you wish to load it?'
    . UU/myread
    case "$ans" in
    n*) echo "OK, I'll ignore it.";;
    *) . ./config.over
        echo
        "Configuration override changes have been loaded."
        ;;
    esac
fi

```

```

@if d_portable
: in case they want portability, strip down executable paths
?X:
?X: Strip down paths in located executables. For each file, e.g. vi, there
?X: is a $vi variable whose value is for instance '/usr/bin/vi'. By resetting
?X: $vi to 'vi', we rely on the PATH variable to locate the executable...
?X: In order to allow vi='/usr/bin/nvi' which will strip down to vi='nvi',

```

?X: we can't just say 'eval \$file="\\$file"', we have to recourse to sed.

?X: We don't use basename since it is less portable than sed.

?X:

```
case "$d_portable" in
"$define")
echo " "
echo "Stripping down executable paths..." >&4
xsed=$sed
for file in $loclist $trylist; do
eval sfile="\$file"
sfile=`echo $sfile | $xsed -e 's,.*^(.*)\,1,`
eval $file="$sfile"
done
;;
esac
```

@end

: create config.sh file

echo " "

echo "Creating config.sh..." >&4

\$spitshell <<EOT >config.sh

\$startsh

#

This file was produced by running the

Configure script. It holds all the

definitions figured out by Configure. Should you modify one of these values,

do not forget to propagate your changes by running "Configure -der". You may

instead choose to run each of the .SH files by yourself, or "Configure -S".

#

Package name : \$package

Source directory : \$src

Configuration time: \$cf_time

Configured by : \$cf_by

Target system : \$myuname

EOT

?X: Command line options are saved by the Options.U unit in the

?X: temporary file UU/cmdline.opt

\$stest -f UU/cmdline.opt && \$cat UU/cmdline.opt >> config.sh

\$spitshell <<EOT >>config.sh

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/Config_sh.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

```

?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: $Log: d_wifstat.U,v $
?RCS: Revision 3.0.1.3 1997/02/28 15:47:43 ram
?RCS: patch61: added a ?F: metalint hint
?RCS:
?RCS: Revision 3.0.1.2 1995/07/25 14:09:10 ram
?RCS: patch56: re-arranged compile line to include ldflags before objects
?RCS:
?RCS: Revision 3.0.1.1 1995/03/21 08:47:46 ram
?RCS: patch52: created
?RCS:
?MAKE:d_wifstat: d_uwait +cc +ccflags +ldflags +libs Oldconfig cat rm
?MAKE: -pick add $@ %<
?S:d_wifstat:
?S: This symbol conditionally defines USE_WIFSTAT if the C program can
?S: safely
?S: use the WIFxxx macros with the kind of wait() parameter
?S: declared in the program (see UNION_WAIT), or if it can't. Should
?S: only matter on HP-UX, where the macros are incorrectly written and
?S: therefore cause programs using them with an 'union wait' variable
?S: to not compile properly.
?S:.
?C:USE_WIFSTAT:
?C: This symbol, if defined, indicates to the C program that the argument
?C: for the WIFxxx set of macros such as WIFSIGNALED or WIFEXITED can
?C: be of the same kind as the one used to hold the wait() status. Should
?C: only matter on HP-UX, where the macros are incorrectly written and
?C: therefore cause programs using them with an 'union wait' variable
?C: to not compile properly. See also UNION_WAIT.
?C:.
?H:#$d_wifstat USE_WIFSTAT /**/
?H:.
?T:type
?F:!foo
: see if we can use WIFxxx macros
echo " "
case "$d_wifstat" in
"$define") echo "As before, you can safely use WIFEXITED and friends!" >&4;;
"$undef") echo "You still can't use WIFEXITED and friends!" >&4;;
*)

```

```

echo
"Let's see whether you can use the WIFEXITED(status) macro and its"
case "$d_uwait" in
"$define") type='union wait';
*) type='int';;
esac
echo "friends with status declared as '$type status'..."
$cat >foo.c <<EOCP
#include <sys/types.h>
#include <sys/wait.h>

int main()
{
$type status;
int e = 0;

#ifdef WIFEXITED
if (WIFEXITED(status))
printf("\n");
exit(0);
#else
exit(2);
#endif
}
EOCP
d_wifstat="$undef"
if $cc $ccflags $ldflags -o foo foo.c $libs >/dev/null 2>&1; then
if ./foo >/dev/null; then
echo "Great! Looks like we can use the WIFxxx macros." >&4
d_wifstat="$define"
else
echo "You don't seem to have WIFxxx macros, but that's ok." >&4
fi
else
echo "Apparently you can't use WIFxxx macros properly." >&4
fi
$rm -f foo.* foo core
;;
esac

```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/d_wifstat.U
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:
?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: \$Log: archname.U,v \$
?RCS: Revision 3.0.1.3 1997/02/28 15:24:32 ram
?RCS: patch61: changed the way the archname is mangled from uname
?RCS:
?RCS: Revision 3.0.1.2 1995/05/12 12:05:24 ram
?RCS: patch54: protect against spaces in "uname -m" output (ADO)
?RCS:
?RCS: Revision 3.0.1.1 1995/02/15 14:14:21 ram
?RCS: patch51: created
?RCS:
?MAKE:archname myarchname: sed Loc Myread Oldconfig osname test rm
?MAKE: -pick add \$@ %<
?S:archname:
?S: This variable is a short name to characterize the current
?S: architecture.
It is used mainly to construct the default archlib.
?S:.
?S:myarchname:
?S: This variable holds the architecture name computed by Configure in
?S: a previous run. It is not intended to be perused by any user and
?S: should never be set in a hint file.
?S:.
?C:ARCHNAME:
?C: This symbol holds a string representing the architecture name.
?C: It may be used to construct an architecture-dependant pathname
?C: where library files may be held under a private library, for
?C: instance.
?C:.
?H:#define ARCHNAME "\$archname" /**/
?H:.
?T:xxx tarch
: determine the architecture name
echo " "
?X: We always recompute archname in case osname changes. However, we need
?X: to be careful since, as ADO rightfully pointed out, some systems pick
?X: silly architecture names (0001307135000-aix on AIX or 9000/715-ux under
?X: HP-UX). Therefore, we allow hint files to superseed our guess and ask
?X: the user for confirmation.
if xxx=`./loc arch blurfl \$pth`; \$test -f "\$xxx"; then
tarch=`arch`-"-\$osname"
elif

```

xxx=`./loc uname blurfl $pth`; $test -f "$xxx" ; then
if uname -m > tmparch 2>&1 ; then
tarch=`$sed -e 's/ *$//' -e 's/ /_/g' \
-e 's/$/"-$osname/" tmparch`
else
tarch="$osname"
fi
$rm -f tmparch
else
tarch="$osname"
fi
case "$myarchname" in
|"|$tarch") ;;
*)
echo "(Your architecture name used to be $myarchname.)"
archname="
;;
esac
case "$sarchname" in
") dflt="$tarch";;
*) dflt="$sarchname";;
esac
rp='What is your architecture name'
./myread
archname="$ans"
myarchname="$tarch"

```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/archname.U
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_strncmp.U 1 2006-08-24 12:32:52Z rmanfredi \$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic Licence,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic Licence; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: d_strncmp.U,v \$

?RCS: Revision 3.0.1.2 1994/05/06 14:54:34 ram

?RCS: patch23: fixed a typo (WED)

?RCS:

?RCS: Revision 3.0.1.1 1993/09/13 16:04:39 ram

?RCS: patch10: created (WAD)

?RCS:
?RCS: Revision 3.0 1993/08/18 12:06:24 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:d_strncmp: Inlibc
?MAKE: -pick add \$@ %<
?S:d_strncmp:
?S: This variable conditionally defines the HAS_STRCASECMP symbol, which
?S: indicates to the C program
that the strcasecmp() routine is available
?S: for case-insensitive string compares.
?S:.
?C:HAS_STRCASECMP:
?C: This symbol, if defined, indicates that the strcasecmp() routine is
?C: available for case-insensitive string compares.
?C:.
?H:#\$d_strncmp HAS_STRCASECMP /**/
?H:.
?LINT:set d_strncmp
: see if strcasecmp exists
set strcasecmp d_strncmp
eval \$inlibc

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/d_strncmp.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$
?RCS:
?RCS: Copyright (c) 2005 H.Merijn Brand
?RCS:
?RCS: You may distribute under the terms of either the GNU General Public
?RCS: License or the Artistic License, as specified in the README file.
?RCS:
?MAKE:d_unsetenv: Inlibc
?MAKE: -pick add \$@ %<
?S:d_unsetenv:
?S: This variable conditionally defines the HAS_UNSETENV symbol, which
?S: indicates to the C program that the unsetenv () routine is available.
?S:.
?C:HAS_UNSETENV:
?C: This symbol, if defined, indicates that the unsetenv () routine is
?C: available for use.
?C:.
?H:#\$d_unsetenv HAS_UNSETENV /**/
?H:.
?LINT:set d_unsetenv

```
: see if unsetenv exists
set unsetenv d_unsetenv
eval $inlibc
```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/perl/d_unsetenv.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: MailList.U 1 2006-08-24 12:32:52Z rmanfredi $
```

```
?RCS:
```

```
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
```

```
?RCS:
```

```
?RCS: You may redistribute only under the terms of the Artistic Licence,
```

```
?RCS: as specified in the README file that comes with the distribution.
```

```
?RCS: You may reuse parts of this distribution only within the terms of
```

```
?RCS: that same Artistic Licence; a copy of which may be found at the root
```

```
?RCS: of the source tree for dist 4.0.
```

```
?RCS:
```

```
?RCS: Original Author: Graham Stoney <greyham@research.canon.oz.au>
```

```
?RCS:
```

```
?RCS: $Log: MailList.U,v $
```

```
?RCS: Revision 3.0.1.1 1994/01/24 14:01:49 ram
```

```
?RCS: patch16: created
```

```
?RCS:
```

```
?RCS:
```

```
?X:
```

```
?X: This unit offers the user the option of subscribing to the mailing
```

```
?X: list. To force inclusion of this unit, you must add it's name to the
```

```
?X: dependancies on the MAKE line in your private copy of End.U.
```

```
?X: The address of the mailing list server must be set via a "list_request=..."
```

```
?X:
```

```
entry in the .package file. This is usually done by running packinit and
```

```
?X: answering the proper questions.
```

```
?X:
```

```
?MAKE:MailList: cat mailer package Myread cf_name cf_email
```

```
?MAKE: -pick wipe $@ %<
```

```
?T:list_request list_sub list_unsub list_name
```

```
?X:
```

```
?X: The cf_name dependency is used through list_sub when the mailing list
```

```
?X: manager happens to be listserv, whereas cf_email is used whith majordomo
```

```
?X: or when the mailing list request address is scanned by a human. Since
```

```
?X: they do not appear within the unit itself, we need a lint hint.
```

```
?X:
```

```
?LINT:use cf_name cf_email
```

```
: offer to join the mailing list
```

```
list_request='<${list_request}>'
```

```
list_sub="<${list_sub}>"
```

```
list_unsub="<$list_unsub>"
list_name="<$list_name>"
$cat <<EOM
```

There is a mailing list for discussion about \$package and related issues. This is the preferred place to ask questions about the program and discuss modifications and additions with the author and other users. If you are able to send mail to the Internet, you are encouraged to subscribe. You need only ever subscribe once, and you can unsubscribe automatically at any time in the future. If you have already subscribed and you wish to unsubscribe now, you may do so by answering "unsubscribe". Answer "subscribe" to subscribe to the list.

```
EOM
rp="Subscribe to or unsubscribe from the $list_name mailing list?"
dflt=neither
. ./myread
case "$ans" in
[sS]*) $cat <<EOM
```

You will be sent a message from the list server to let you know when your subscription has been successful and telling you how to submit articles and how to unsubscribe again when necessary. You may also unsubscribe by running this script again and asking it to do so for you.

```
EOM
echo "Sending mail to subscribe you to the $list_name list..." >&4
$mailler $list_request <<EOM >/dev/null 2>&1
Precedence: junk
To: $list_request
```

```
$list_sub
EOM
;;
[uU]*) echo "Sending mail to unsubscribe you from the $list_name list..." >&4
$mailler $list_request <<EOM >/dev/null 2>&1
Precedence: junk
To:
$list_request
```

```
$list_unsub
EOM
;;
esac
```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
```

debian-perl-5.26.1/dist/U/MailList.U

No license file was found, but licenses were detected in source scan.

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?MAKE:d_atanh: Inlibc

?MAKE: -pick add \$@ %<

?S:d_atanh:

?S: This variable conditionally defines the HAS_ATANH symbol, which

?S: indicates to the C program that the atanh() routine is available.

?S:.

?C:HAS_ATANH:

?C: This symbol, if defined, indicates that the atanh routine is

?C: available to do the inverse hyperbolic tangent function.

?C:.

?H:#\$d_atanh HAS_ATANH /**/

?H:.

?LINT:set d_atanh

: see if atanh exists

set atanh d_atanh

eval \$inlibc

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-

debian-perl-5.26.1/U/perl/d_atanh.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1999, Jarkko Hietaniemi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 3.0.

?RCS:

?MAKE:d_sem_wait: Inlibc

?MAKE: -pick add \$@ %<

?S:d_sem_wait:

?S: This variable conditionally defines HAS_SEM_WAIT if sem_wait() is

?S: available to wait (grab, lock) a POSIX semaphore.

?S:.

?C:HAS_SEM_WAIT:

?C: This symbol, if defined, indicates that the sem_wait system call is

?C: available to wait (grab, lock) a POSIX semaphore.

?C:.

```
?H:#$d_sem_wait HAS_SEM_WAIT /**/  
?H:.  
?LINT:set d_sem_wait  
: see if sem_wait exists  
set sem_wait d_sem_wait  
eval $inlibc
```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-  
debian-perl-5.26.1/U/perl/d_sem_wait.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: d_getpgid.U 1 2006-08-24 12:32:52Z rmanfredi $  
?RCS:  
?RCS: Copyright (c) 1996, Andy Dougherty  
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi  
?RCS:  
?RCS: You may redistribute only under the terms of the Artistic Licence,  
?RCS: as specified in the README file that comes with the distribution.  
?RCS: You may reuse parts of this distribution only within the terms of  
?RCS: that same Artistic Licence; a copy of which may be found at the root  
?RCS: of the source tree for dist 4.0.  
?RCS:  
?RCS: $Log: d_getpgid.U,v $  
?RCS: Revision 3.0.1.1 1997/02/28 15:33:44 ram  
?RCS: patch61: created  
?RCS:  
?MAKE:d_getpgid: Inlibc  
?MAKE: -pick add $@ %<  
?S:d_getpgid:  
?S: This variable conditionally defines the HAS_GETPGID symbol, which  
?S: indicates to the C program that the getpgid(pid) function  
?S: is available to get the process group id.  
?S:.  
?C:HAS_GETPGID:  
?C: This symbol, if defined, indicates to the C program  
?C: that  
?C: the getpgid(pid) function is available to get the  
?C: process group id.  
?C:.  
?H:#$d_getpgid HAS_GETPGID /**/  
?H:.  
?LINT:set d_getpgid  
: see if getpgid exists  
set getpgid d_getpgid  
eval $inlibc
```

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/d_getpgid.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_gethostprotos.U,v \$

?RCS:

?RCS: Copyright (c) 1991-1993, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 3.0.

?RCS:

?MAKE:d_gethostprotos : Hasproto i_netdb

?MAKE: -pick add \$@ %<

?S:d_gethostprotos:

?S: This variable conditionally defines the HAS_GETHOST_PROTOS symbol,

?S: which indicates to the C program that <netdb.h> supplies

?S: prototypes for the various gethost*() functions.

?S: See also netdbtype.U for probing for various netdb types.

?S:.

?C:HAS_GETHOST_PROTOS:

?C: This symbol, if defined, indicates that <netdb.h> includes

?C: prototypes for gethostent(), gethostbyname(), and

?C: gethostbyaddr(). Otherwise,

it is up to the program to guess

?C: them. See netdbtype.U for probing for various Netdb_xxx_t types.

?C:.

?H:#\$d_gethostprotos HAS_GETHOST_PROTOS /**/

?H:.

?LINT:set d_gethostprotos

?X: This test actually only checks for gethostent() and assumes the

?X: others follow suit. This test fails for ChorusOS, which has

?X: gethostbyname and gethostbyaddr, but not gethostent.

: see if prototypes for various gethostxxx netdb.h functions are available

echo " "

set d_gethostprotos gethostent \$i_netdb netdb.h

eval \$hasproto

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/protos/d_gethostprotos.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:
?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: Original Author: Andy Dougherty <doughera@lafcol.lafayette.edu>
?RCS:
?RCS: \$Log: selecttype.U,v \$
?RCS: Revision 3.0.1.3 1997/02/28 16:20:09 ram
?RCS: patch61: always include <sys/select.h> when available for test
?RCS:
?RCS: Revision 3.0.1.2 1995/07/25 14:14:06 ram
?RCS: patch56: removed harmful spaces in assignment
?RCS:
?RCS: Revision 3.0.1.1 1994/06/20 07:06:31 ram
?RCS: patch30: created by ADO
?RCS:
?MAKE:selecttype: cat +cc +ccflags rm Oldconfig Myread \
d_fd_set d_select d_socket i_systeme
i_sysselect
?MAKE: -pick add \$@ %<
?S:selecttype:
?S: This variable holds the type used for the 2nd, 3rd, and 4th
?S: arguments to select. Usually, this is 'fd_set *', if HAS_FD_SET
?S: is defined, and 'int *' otherwise. This is only useful if you
?S: have select(), naturally.
?S:.
?C:Select_fd_set_t:
?C: This symbol holds the type used for the 2nd, 3rd, and 4th
?C: arguments to select. Usually, this is 'fd_set *', if HAS_FD_SET
?C: is defined, and 'int *' otherwise. This is only useful if you
?C: have select(), of course.
?C:.
?H:#define Select_fd_set_t \$selecttype /**/
?H:.
?T:xxx yyy
: check for type of arguments to select. This will only really
: work if the system supports prototypes and provides one for
: select.
case "\$d_select" in
\$define)
: Make initial guess
case "\$selecttype" in
"|")
case "\$d_fd_set" in
\$define) xxx='fd_set *' ;;

```

*) xxx='int *' ;;
esac
;;
*) xxx="$selecttype"
;;
esac
: backup guess
case "$xxx" in
'fd_set *') yyy='int *'
;;
'int *') yyy='fd_set *' ;;
esac

$cat <<EOM

```

Checking to see what type of arguments are expected by select().

EOM

```

$cat >try.c <<EOCP
#i_systime I_SYS_TIME
#i_sysselect I_SYS_SELECT
#d_socket HAS_SOCKET
#include <sys/types.h>
#ifdef HAS_SOCKET
#include <sys/socket.h> /* Might include <sys/bsdtypes.h> */
#endif
#ifdef I_SYS_TIME
#include <sys/time.h>
#endif
#ifdef I_SYS_SELECT
#include <sys/select.h>
#endif
int main()
{
int width;
Select_fd_set_t readfds;
Select_fd_set_t writefds;
Select_fd_set_t exceptfds;
struct timeval timeout;
select(width, readfds, writefds, exceptfds, &timeout);
exit(0);
}
EOCP
if $cc $ccflags -c -DSelect_fd_set_t="$xxx" try.c >/dev/null 2>&1 ; then
selecttype="$xxx"
echo "Your system uses $xxx for the arguments to select." >&4
elif $cc $ccflags -c -DSelect_fd_set_t="$yyy" try.c >/dev/null 2>&1 ; then
selecttype="$yyy"
echo "Your system uses $yyy for the arguments to select." >&4

```

```

else
rp='What is the type for the 2nd, 3rd, and 4th arguments
to select?'
dflt="$xxx"
. ./myread
selecttype="$sans"
fi
$rm -f try.[co]
;;
*) selecttype='int *'
;;
esac

```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/selecttype.U
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: locdist.U 1 2006-08-24 12:32:52Z rmanfredi \$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic Licence,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic Licence; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: locdist.U,v \$

?RCS: Revision 3.0.1.1 1994/05/06 15:09:20 ram

?RCS: patch23: added support for multi-state regions (WED)

?RCS:

?RCS: Revision 3.0 1993/08/18 12:09:06 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?MAKE:locdist orgdist citydist statedist multistatedist centrydist contdist: \

test newslibexp cat Myread Oldconfig

?MAKE: -pick add \$@ %<

?S:locdist:

?S: This variable contains the eventual value of the LOCDIST symbol,

?S: which

is the local organization's distribution name for news.

?S:.

?S:orgdist:

?S: This variable contains the eventual value of the ORGDIST symbol,

?S: which is the organization's distribution name for news.

?S:.

?S:citydist:

?S: This variable contains the eventual value of the CITYDIST symbol,

?S: which is the city's distribution name for news.

?S:.

?S:statedist:

?S: This variable contains the eventual value of the STATEDIST symbol,

?S: which is the state's or province's distribution name for news.

?S:.

?S:multistatedist:

?S: This variable contains the eventual value of the MULTISTATEDIST symbol,

?S: which is the news distribution code for multi-state region.

?S:.

?S:centrydist:

?S: This variable contains the eventual value of the CNTRYDIST symbol,

?S: which is the country's distribution name for news.

?S:.

?S:contdist:

?S: This variable contains the eventual value of the CONTDIST symbol,

?S: which is the continent's distribution name for news.

?S:.

?C:LOCDIST:

?C: This symbol contains the
distribution name for the news system that

?C: restricts article distribution to the local organization.

?C:.

?C:ORGDIST:

?C: This symbol contains the distribution name for the news system that

?C: restricts article distribution to the organization.

?C:.

?C:CITYDIST:

?C: This symbol contains the distribution name for the news system that

?C: restricts article distribution to the city.

?C:.

?C:STATEDIST:

?C: This symbol contains the distribution name for the news system that

?C: restricts article distribution to the state or province.

?C:.

?C:MULTISTATEDIST:

?C: This symbol contains the distribution name for the news system that

?C: restricts article distribution to a multi-state region.

?C:.

?C:CNTRYDIST:

?C: This symbol contains the distribution name for the news system that

?C: restricts article distribution to the country.

?C:.

?C:CONTDIST:

?C: This symbol contains the distribution name for the news system that

?C: restricts article distribution to the continent.

?C:.

```

?H:#define LOCDIST
"$locdist" /**/
?H:#define ORGDIST "$orgdist" /**/
?H:#define CITYDIST "$citydist" /**/
?H:#define MULTISTATEDIST "$multistatedist" /**/
?H:#define STATEDIST "$statedist" /**/
?H:#define CNTRYDIST "$cntrydist" /**/
?H:#define CONTDIST "$contdist" /**/
?H:
: get the local distributions
$cat <<'EOH'

```

Distribution groups are the things you use on the Distribution line to limit where an article will go to. You are likely to be a member of several distribution groups, such as organization, city, state, province, country, continent, etc. For example, Los Angeles has the distribution code "la", New Jersey has the code "nj", and Europe has the code "eunet".

The categories you will be asked are:

```

local organization (Could be just one machine or a cluster or an office)
organization att, dec, kgb, ...
city la, ny, mosc, ...
state/province ca, nj, bc, ...
multi-state region pnw, ne, ...
country usa, can, rok, whatever
continent na (North America), asia, etc.

```

```

EOH
if $test
-f $newslibexp/distributions; then
case "$silent" in
true) ;;
*) dflt='Hit return to continue'
rp="
./myread
;;
esac
echo "Here is your distributions file:" >&4
echo " " >&4
$cat >&4 $newslibexp/distributions
echo " " >&4
fi
echo "Use 'none' for any distributions you don't have."
echo " "
case "$locdist" in
") dflt="none";;
*) dflt="$locdist";;

```

```

esac
rp="What is the distribution code for your local organization?"
./myread
locdist="$ans"
case "$orgdist" in
") dflt="none";;
*) dflt="$orgdist";;
esac
rp="What is the distribution code for your organization?"
./myread
orgdist="$ans"
case "$citydist" in
") dflt="none";;
*) dflt="$citydist";;
esac
rp="What is the distribution code for your city?"
./myread
citydist="$ans"
case "$statedist" in
") dflt="none";;
*) dflt="$statedist";;
esac
rp="What is the distribution code for your state/province?"
./myread
statedist="$ans"
case "$multistatedist" in
") dflt="none";;
*) dflt="$multistatedist";;
esac
rp="What is the
distribution code for your multi-state region?"
./myread
multistatedist="$ans"
case "$cntrydist" in
") dflt="none";;
*) dflt="$cntrydist";;
esac
rp="What is the distribution code for your country?"
./myread
cntrydist="$ans"
case "$contdist" in
") dflt="none";;
*) dflt="$contdist";;
esac
rp="What is the distribution code for your continent?"
./myread
contdist="$ans"
$cat <<'EOM'

```

If you have any other distribution groups you will need to edit Pnews and newsetup to add them.

EOM

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/locdist.U
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: mandirstyle.U,v 3.1 1999/07/08 20:52:19 doughera Exp doughera \$

?RCS:

?RCS: Copyright (c) 2000, Andy Dougherty

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 3.0.

?RCS:

?RCS: \$Log: mandirstyle.U,v \$

?RCS:

?MAKE:mandirstyle: test

?MAKE: -pick add \$@ %<

?S:mandirstyle:

?S: This variable indicates the style of man page directory layout

?S: used on this system. Current possible values are sysv, svr4, and

?S: bsd. This information is used for determining where to put various

?S: man pages. Configure uses the BSD convention internally (we've got

?S: to give *some* name to the variables).

?S:

?S: BSD SVR4 Description

Example

?S: Number Number man page

?S: 1 1 Commands cat

?S: 2 2 system calls creat

?S: 3 3 library functions fread

?S: 4 7 special files fd

?S: 5 4 file formats magic

?S: 6 6 games and demos magic

?S: 7 5 miscellany eqnchar

?S: 8 1M Administrative commands mount

?S:

?S: The SysV style is almost the same as SVR4, but instead of

?S: /usr/man/man1, there is /usr/man/u_man/man1.

?S:.

: determine style of existing man page installation

if \$test "\$mandirstyle" = ""; then

```

if $test -d /usr/man/u_man/man1; then
    mandirstyle=sysv
elif $test -d /usr/man/man1m; then
    mandirstyle=svr4
elif $test -d /usr/share/man/man1m; then
    mandirstyle=svr4
elif $test -d /usr/share/man/sman1m; then
    mandirstyle=svr4 # Solaris 8 and beyond
else
    # We could work a lot harder here, but there isn't
    # really
    much point.
    mandirstyle=bsd
fi
fi
echo "You appear to have $mandirstyle style man page directories."

```

Found in path(s):

```

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/perl/mandirstyle.U

```

No license file was found, but licenses were detected in source scan.

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?MAKE:d_erb: Inlibc

?MAKE: -pick add \$@ %<

?S:d_erb:

?S: This variable conditionally defines the HAS_ERF symbol, which

?S: indicates to the C program that the erf() routine is available.

?S:.

?C:HAS_ERF:

?C: This symbol, if defined, indicates that the erf routine is

?C: available to do the error function.

?C:.

?H:#\$d_erb HAS_ERF /**/

?H:.

?LINT:set d_erb

: see if erf exists

set erf d_erb

eval \$inlibc

Found in path(s):

```

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/perl/d_erb.U

```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: sig_name.U 1 2006-08-24 12:32:52Z rmanfredi \$

?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: \$Log: sig_name.U,v \$
?RCS: Revision 3.0.1.5 1997/02/28 16:21:25 ram
?RCS: patch61: brand new algorithm for sig_name and (new!) sig_num
?RCS:
?RCS: Revision 3.0.1.4 1995/07/25 14:14:54 ram
?RCS: patch56: added <asm/signal.h> lookup for Linux
?RCS:
?RCS: Revision 3.0.1.3 1995/05/12 12:24:11 ram
?RCS: patch54: now looks for <linux/signal.h> too (ADO)
?RCS:
?RCS: Revision 3.0.1.2 1994/06/20 07:06:57 ram
?RCS: patch30: final echo was missing to close
awk-printed string
?RCS:
?RCS: Revision 3.0.1.1 1994/05/06 15:17:55 ram
?RCS: patch23: signal list now formatted to avoid scroll-ups (ADO)
?RCS:
?RCS: Revision 3.0 1993/08/18 12:09:47 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:sig_name sig_name_init sig_num sig_num_init sig_count sig_size: \
awk Signal Oldconfig rm
?MAKE: -pick add \$@ %<
?S:sig_name:
?S: This variable holds the signal names, space separated. The leading
?S: SIG in signal name is removed. A ZERO is prepended to the list.
?S: This is currently not used, sig_name_init is used instead.
?S:.
?S:sig_name_init:
?S: This variable holds the signal names, enclosed in double quotes and
?S: separated by commas, suitable for use in the SIG_NAME definition
?S: below. A "ZERO" is prepended to the list, and the list is
?S: terminated with a plain 0. The leading SIG in signal names
?S: is removed. See sig_num.
?S:.
?S:sig_num:
?S: This variable holds the signal numbers, space separated. A ZERO is
?S: prepended

to the list (corresponding to the fake SIGZERO).

?S: Those numbers correspond to the value of the signal listed

?S: in the same place within the sig_name list.

?S: This is currently not used, sig_num_init is used instead.

?S:.

?S:sig_num_init:

?S: This variable holds the signal numbers, enclosed in double quotes and

?S: separated by commas, suitable for use in the SIG_NUM definition

?S: below. A "ZERO" is prepended to the list, and the list is

?S: terminated with a plain 0.

?S:.

?S:sig_count (sig_name.U):

?S: This variable holds a number larger than the largest valid

?S: signal number. This is usually the same as the NSIG macro.

?S:.

?S:sig_size:

?S: This variable contains the number of elements of the sig_name

?S: and sig_num arrays.

?S:.

?C:SIG_NAME:

?C: This symbol contains a list of signal names in order of

?C: signal number. This is intended

?C: to be used as a static array initialization, like this:

?C: char *sig_name[] = { SIG_NAME };

?C: The signals in the list are

separated with commas, and each signal

?C: is surrounded by double quotes. There is no leading SIG in the signal

?C: name, i.e. SIGQUIT is known as "QUIT".

?C: Gaps in the signal numbers (up to NSIG) are filled in with NUMnn,

?C: etc., where nn is the actual signal number (e.g. NUM37).

?C: The signal number for sig_name[i] is stored in sig_num[i].

?C: The last element is 0 to terminate the list with a NULL. This

?C: corresponds to the 0 at the end of the sig_name_init list.

?C: Note that this variable is initialized from the sig_name_init,

?C: not from sig_name (which is unused).

?C:.

?C:SIG_NUM:

?C: This symbol contains a list of signal numbers, in the same order as the

?C: SIG_NAME list. It is suitable for static array initialization, as in:

?C: int sig_num[] = { SIG_NUM };

?C: The signals in the list are separated with commas, and the indices

?C: within that list and the SIG_NAME list match, so it's easy to compute

?C: the signal name from a number or vice versa at the price of

a small

?C: dynamic linear lookup.

?C: Duplicates are allowed, but are moved to the end of the list.

?C: The signal number corresponding to sig_name[i] is sig_number[i].

?C: if (i < NSIG) then sig_number[i] == i.

?C: The last element is 0, corresponding to the 0 at the end of
?C: the sig_name_init list.
?C: Note that this variable is initialized from the sig_num_init,
?C: not from sig_num (which is unused).
?C:.
?C:SIG_COUNT:
?C: This variable contains a number larger than the largest
?C: signal number. This is usually the same as the NSIG macro.
?C:.
?C:SIG_SIZE:
?C: This variable contains the number of elements of the SIG_NAME
?C: and SIG_NUM arrays, excluding the final NULL entry.
?C:.
?H:#define SIG_NAME \$sig_name_init /**/
?H:#define SIG_NUM \$sig_num_init /**/
?H:#define SIG_COUNT \$sig_count /**/
?H:#define SIG_SIZE \$sig_size /**/
?H:.
?T:i doinit
?F:!= !signal_cmd
?X: signal.cmd creates a file signal.lst which has two columns:
?X: NAME number, e.g.
?X: HUP 1
?X: The list
is sorted on signal number, with duplicates moved to
?X: the end..
: generate list of signal names
case "\$sig_num_init" in
")
echo " "
case "\$sig_name_init" in
") doinit=yes ;;
*) case "\$sig_num_init" in
"*) doinit=yes ;;
esac ;;
esac
case "\$doinit" in
yes)
echo "Generating a list of signal names and numbers..." >&4
./signal_cmd
sig_count=`\$awk '/^NSIG/ { printf "%d", \$2 }' signal.lst`
sig_name=`\$awk 'BEGIN { printf "ZERO " }
!/^NSIG/ { printf "%s ", \$1 }' signal.lst`
sig_num=`\$awk 'BEGIN { printf "0 " }
!/^NSIG/ { printf "%d ", \$2 }' signal.lst`
sig_name_init=`\$awk 'BEGIN { printf "\"ZERO\", " }
!/^NSIG/ { printf "\"%s\", ", \$1 }
END { printf "0\n" }' signal.lst`

```

sig_num_init=`$awk 'BEGIN { printf "0, " }
    !/^NSIG/ { printf "%d, ", $2}
    END { printf "0\n"}' signal.lst`
;;
esac
echo "The following $sig_count signals are available:"
echo " "
echo $sig_name | $awk \
'BEGIN { linelen = 0 }
{
for (i = 1; i <= NF;
i++) {
name = "SIG" $i " "
linelen = linelen + length(name)
if (linelen > 70) {
printf "\n"
linelen = length(name)
}
printf "%s", name
}
printf "\n"
}'
sig_size=`echo $sig_name | awk '{print NF}'`
$rm -f signal signal.c signal.awk signal.lst signal_cmd
;;
esac

```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/modified/sig_name.U
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: d_voidsig.U,v \$

?RCS: Revision 3.0.1.3 1995/05/12 12:12:46 ram

?RCS: patch54: made cppflags dependency optional

?RCS:

?RCS: Revision 3.0.1.2 1994/08/29 16:20:35 ram

?RCS: patch32: now sets signal_t only once d_voidsig is known (WED)

```

?RCS:
?RCS: Revision 3.0.1.1 1994/06/20 06:59:54 ram
?RCS: patch30: now properly sets signal_t when re-using previous value
?RCS:
?RCS: Revision 3.0 1993/08/18 12:07:56 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:d_voidsig signal_t: rm contains
cppstdin cppminus +cppflags test Myread \
Oldconfig Setvar Findhdr
?MAKE:-pick add $@ %<
?S:d_voidsig:
?S: This variable conditionally defines VOIDSIG if this system
?S: declares "void (*signal(...))()" in signal.h. The old way was to
?S: declare it as "int (*signal(...))()".
?S:.
?S:signal_t:
?S: This variable holds the type of the signal handler (void or int).
?S:.
?C:VOIDSIG:
?C: This symbol is defined if this system declares "void (*signal(...))()" in
?C: signal.h. The old way was to declare it as "int (*signal(...))()". It
?C: is up to the package author to declare things correctly based on the
?C: symbol.
?C:.
?C:Signal_t (SIGNAL_T):
?C: This symbol's value is either "void" or "int", corresponding to the
?C: appropriate return type of a signal handler. Thus, you can declare
?C: a signal handler using "Signal_t (*handler())", and define the
?C: handler using "Signal_t handler(sig)".
?C:.
?H:#$d_voidsig VOIDSIG /**/
?H:#define Signal_t $signal_t /* Signal handler's return
type */
?H:.
?T:xxx
?LINT:set d_voidsig
: see if signal is declared as pointer to function returning int or void
echo " "
xxx=`./findhdr signal.h`
$test "$xxx" && $cppstdin $cppminus $cppflags < $xxx >$.tmp 2>/dev/null
if $contains 'int.*\[ ]*signal' $.tmp >/dev/null 2>&1 ; then
echo "You have int (*signal())() instead of void." >&4
val="$undef"
elif $contains 'void.*\[ ]*signal' $.tmp >/dev/null 2>&1 ; then
echo "You have void (*signal())() instead of int." >&4
val="$define"
elif $contains 'extern[ ]*\[ \]*signal' $.tmp >/dev/null 2>&1 ; then

```

```

echo "You have int (*signal())() instead of void." >&4
val="$undef"
else
case "$d_voidsig" in
")
echo "I can't determine whether signal handler returns void or int..." >&4
dflt=void
rp="What type does your signal handler return?"
./myread
case "$ans" in
v*) val="$define";;
*) val="$undef";;
esac;;
"$define")
echo "As you already told me, signal handler returns void." >&4;;
*)
echo "As you already told
me, signal handler returns int." >&4;;
esac
fi
set d_voidsig
eval $setvar
case "$d_voidsig" in
"$define") signal_t="void";;
*) signal_t="int";;
esac
$rm -f $$tmp

```

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/d_voidsig.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: yacc.U,v \$

?RCS: Revision 3.0.1.1 1994/05/13 15:28:48 ram

?RCS: patch27: added byacc as another alternative (ADO)

?RCS:

?RCS: Revision 3.0 1993/08/18 12:10:03 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?MAKE:yacc yaccflags: Guess Myread Loc Oldconfig byacc bison cat test

?MAKE: -pick add \$@ %<

?S:yacc:

?S: This variable holds the name of the compiler compiler we

?S: want to use in the Makefile. It can be yacc, byacc, or bison -y.

?S:.

?S:yaccflags:

?S: This variable contains any

additional yacc flags desired by the

?S: user. It is up to the Makefile to use this.

?S:.

?T:comp

: determine compiler compiler

echo " "

comp='yacc'

if \$test -f "\$byacc\$_exe"; then

comp="byacc or \$comp"

fi

if \$test -f "\$bison\$_exe"; then

comp="\$comp or bison -y"

fi

case "\$yacc" in

)

yacc=`./loc yacc yacc \$pth`

if \$test -f "\$yacc\$_exe"; then

dflt='yacc'

elif \$test -f "\$byacc\$_exe"; then

dflt='byacc'

elif \$test -f "\$bison\$_exe"; then

dflt='bison'

else

dflt=""

fi

::

*) dflt="\$yacc";;

esac

rp="Which compiler compiler (\$comp) shall I use?"

./myread

yacc="\$ans"

case "\$yacc" in

bis)

case "\$yacc" in

-y) ;;

*)

yacc="\$yacc -y"

echo "(Adding -y option to bison to get yacc-compatible behaviour.)"

```
;;
esac
;;
esac
```

```
@if yaccflags
: see if we need extra yacc flags
dflt="$yaccflags"
case "$dflt" in
") dflt=none;;
esac
$cat <<EOH
```

Your yacc program may need extra flags to normally process the parser sources. Do NOT specify any -d or -v flags here, since those are explicitly known by the various Makefiles. However, if your machine has strange/undocumented options (like -Sr# on SCO to specify the maximum number of grammar rules), then please add them here. To use no flags, specify the word "none".

```
EOH
rp="Any additional yacc flags?"
./myread
case "$ans" in
none) yaccflags="";;
*) yaccflags="$ans";;
esac
```

```
@end
```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/yacc.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id$
```

```
?RCS:
```

```
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
```

```
?RCS:
```

```
?RCS: You may redistribute only under the terms of the Artistic License,
```

```
?RCS: as specified in the README file that comes with the distribution.
```

```
?RCS: You may reuse parts of this distribution only within the terms of
```

```
?RCS: that same Artistic License; a copy of which may be found at the root
```

```
?RCS: of the source tree for dist 4.0.
```

```
?RCS:
```

```
?RCS: Original Author: Andy Dougherty <doughera@lafcol.lafayette.edu>
```

```
?RCS:
```

```
?RCS: $Log: Ins.U,v $
```

?RCS: Revision 3.0.1.1 1994/06/20 07:05:52 ram

?RCS: patch30: created by ADO

?RCS:

?X:

?X: This unit checks whether symbolic links are really supported.

?X: We can't rely on d_symlink because that may be listed in the

?X: C library but unimplemented.

?X:

?MAKE:lns: ln rm touch test

?MAKE: -pick add \$@ %<

?S:lns:

?S: This variable holds the name of the command to make

?S: symbolic links (if they are supported).

It can be used

?S: in the Makefile. It is either 'ln -s' or 'ln'

?S:.

: determine whether symbolic links are supported

echo " "

\$rm -f blurfl sym

\$touch blurfl

if \$ln -s blurfl sym > /dev/null 2>&1 && \$test -f sym; then

echo "Symbolic links are supported." >&4

lns="\$ln -s"

else

echo "Symbolic links are NOT supported." >&4

lns="\$ln"

fi

\$rm -f blurfl sym

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/lns.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: Loc.U 14 2006-08-28 16:51:14Z rmanfredi \$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: Loc.U,v \$

?RCS: Revision 3.0.1.10 1997/02/28 15:04:16 ram

?RCS: patch61: allow users to specify paths on the command line

?RCS: patch61: will now substitute cp for ln if not supported

?RCS:
?RCS: Revision 3.0.1.9 1995/09/25 09:11:24 ram
?RCS: patch59: commented the purpose of the #un-def directive
?RCS: patch59: abort Configure run when mandatory command is missing
?RCS:
?RCS: Revision 3.0.1.8 1995/07/25 13:40:40 ram
?RCS: patch56: now knows about
OS/2 platforms
?RCS:
?RCS: Revision 3.0.1.7 1995/01/11 15:13:37 ram
?RCS: patch45: protected "sh -c" within backquotes for Linux and SGI
?RCS: patch45: added path lookup for the 'comm' program
?RCS:
?RCS: Revision 3.0.1.6 1994/10/29 15:56:14 ram
?RCS: patch36: added ?F: line for metalint file checking
?RCS: patch36: be careful and guard against wildcard searching (ADO)
?RCS:
?RCS: Revision 3.0.1.5 1994/06/20 06:54:55 ram
?RCS: patch30: now locates find
?RCS:
?RCS: Revision 3.0.1.4 1994/05/13 15:18:15 ram
?RCS: patch27: added byacc to the trylist (ADO)
?RCS: patch27: lint lines reformatted (ADO)
?RCS:
?RCS: Revision 3.0.1.3 1994/01/24 14:01:44 ram
?RCS: patch16: added metalint hint on changed PATH variable
?RCS:
?RCS: Revision 3.0.1.2 1993/12/15 08:16:52 ram
?RCS: patch15: now set _test variable when test is built-in
?RCS: patch15: fixed rare cases where echo is not needed
?RCS:
?RCS: Revision 3.0.1.1 1993/09/13 15:47:13 ram
?RCS: patch10: test program not always
in /bin/test (WAD)
?RCS:
?RCS: Revision 3.0 1993/08/18 12:05:05 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?X:
?X: This unit produces a shell script "loc" which can be used to find out
?X: where in a list of directories something is. It then uses loc to
?X: determine the location of commonly used programs. It leaves loc sitting
?X: around for other Configure units to use, but arranges for its demise
?X: at the end of Configure.
?X:
?X: To add a new program to find, add it both to the ?MAKE: line and to either
?X: the loclist or trylist variable.
?X:

?X: I put startsh at the end of the dependency list, in order to avoid the

?X: loading of the spitshell unit before the instructions.

?X:

```
?MAKE:Loc awk ar bash bison byacc cat chgrp chmod chown \  
comm compress cp cpio cpp csh date echo egrep emacs expr find flex \  
gmake gzip grep inews ksh less line lint ln lp lpr ls mail mailx \  
make mkdir more mv nm nroff perl pg pmake pr rm rmail sed sendmail \  
shar sleep smail sort  
submit tail tar tbl tee test touch tr troff \  
uname uniq uuname vi zcat zip: eunicefix n c startsh Instruct sysroot
```

?MAKE: -pick weed \$@ %<

```
?LINT:describe awk ar bash bison byacc cat chgrp chmod chown \  
comm compress cp cpio cpp csh date echo egrep emacs expr find flex \  
gmake gzip grep inews ksh less line lint ln lp lpr ls mail mailx \  
make mkdir more mv nm nroff perl pg pmake pr rm rmail sed sendmail \  
shar sleep smail sort submit tail tar tbl tee test touch tr troff \  
uname uniq uuname vi zcat zip
```

?V::pth loclist trylist

?F:./loc test_h

?T:thisthing thing xxx dir file say _test DJGPP

?LINT:change PATH _egrep _ln _make _less

?LINT:extern _exe

: find out where common programs are

echo " "

echo "Locating common programs..." >&4

cat <<EOOSC >loc

\$startsh

case \$# in

0) exit 1;;

esac

thing=\${\$1

shift

dflt=\${\$1

shift

for dir in *; do

case "\\$thing" in

.)

if test -d \\$dir/\\$thing; then

echo \\$dir

exit 0

fi

::

*)

?X: Be careful in case thing includes wildcards that might expand
to multiple

?X: files. Choose the last one. This happens when searching for shared

?X: libraries with version numbers. How to choose which one we want is

?X: probably an insoluble problem, in general.

```

?X: Some folks leave things like libc.so.orig around w/o read
?X: permission. A -r test would handle that, but since ./loc is
?X: also used to find executables (which are installed w/o read
?X: permission on SCO ODT 3.0, we can't include the -r test.
?X: If you need to use an _exe that is different from .exe
?X: you need to set it in Head.U.
for thisthing in \${dir}\$thing; do
: just loop through to pick last item
done
if test -f \${thisthing}; then
echo \${thisthing}
exit 0
elif test "X$_exe" != X -a -f \${thisthing}$_exe; then
echo \${thisthing}
exit 0
elif test -f \${dir}\$thing.exe; then
if test -n "$DJGPP"; then
echo \${dir}\$thing.exe
elif test "$eunicefix" != ":"; then
: on Eunice apparently
echo \${dir}\$thing
fi
fi
exit 0
fi
;;
esac
done
echo \${dflt}
exit
1
EOSC
chmod +x loc
$eunicefix loc
loclist=""
?awk:awk
?cat:cat
?chgrp:chgrp
?chmod:chmod
?chown:chown
?comm:comm
?cp:cp
?echo:echo
?expr:expr
?find:find
?grep:grep
?ls:ls
?mkdir:mkdir
?mv:mv

```

?rm:rm
?sed:sed
?sleep:sleep
?sort:sort
?tail:tail
?touch:touch
?tr:tr
?uniq:uniq
"
trylist="
?Mcc:Mcc
?ar:ar
?bash:bash
?bison:bison
?byacc:byacc
?compress:compress
?cpio:cpio
?cpp:cpp
?csh:csh
?date:date
?egrep:egrep
?emacs:emacs
?flex:flex
?gmake:gmake
?gzip:gzip
?inews:inews
?ksh:ksh
?less:less
?line:line
?lint:lint
?ln:ln
?lp:lp
?lpr:lpr
?mail:mail
?mailx:mailx
?make:make
?more:more
?nm:nm
?nroff:nroff
?perl:perl
?pg:pg
?pmake:pmake
?pr:pr
?rmail:rmail
?sendmail:sendmail
?shar:shar
?smail:smail
?submit:submit

```

?tar:tar
?tbl:tbl
?tee:tee
?test:test
?troff:troff
?uname:uname
?uuname:uuname
?vi:vi
?zcat:zcat
?zip:zip
"
?LINT:set awk ar bash bison byacc cat chgrp chmod chown \
comm compress cp cpio cpp csh date echo emacs expr find flex \
gmake gzip grep inews ksh line lint lp lpr ls mail mailx
\
mkdir more mv nm nroff perl pg pmake pr rm rmail sed sendmail \
shar sleep smail sort submit tail tar tbl tee touch tr troff \
uname uniq uuname vi zcat zip
pth=`echo $PATH | sed -e "s/$p_/ /g"`
pth="$pth $sysroot/lib $sysroot/usr/lib"
for file in $loclist; do
?X:
?X: Allow them to -Dmake=pmake on the command line for instance...
?X: If the file is not fully qualified, as in -Dmake=pmake, then we
?X: look the for the specified command (pmake here). If they say
?X: -Dmake=/sbin/make for instance, then we make sure the file
?X: exists, or we die...
?X:
eval xxx=\$$file
case "$xxx" in
/*|?:[\\]*)
if test -f "$xxx"; then
: ok
else
echo "WARNING: no $xxx -- ignoring your setting for $file." >&4
xxx=`./loc $file $file $pth`
fi
;;
*) xxx=`./loc $file $file $pth`;
*) xxx=`./loc $xxx $xxx $pth`;
esac
eval $file=$xxx$_exe
eval _$file=$xxx
case "$xxx" in
/*)
echo $file is in $xxx.
;;
?X: Under OS/2, we have PC-like paths

```

```

?:[\\]*)
echo $file is in $xxx.
;;
*)
echo
"I don't know where '$file' is, and my life depends on it." >&4
echo "Go find a public domain implementation or fix your PATH setting!" >&4
exit 1
;;
esac
done
echo " "
echo "Don't worry if any of the following aren't found..."
say=offhand
for file in $trylist; do
?X: Allow them to -Dmake=pmake on the command line for instance (see above)
eval xxx=\\$file
case "$xxx" in
/*|?:[\\]*)
if test -f "$xxx"; then
: ok
else
echo "WARNING: no $xxx -- ignoring your setting for $file." >&4
xxx=`./loc $file $file $pth`
fi
;;
") xxx=`./loc $file $file $pth`;
*) xxx=`./loc $xxx $xxx $pth`;
esac
eval $file=$xxx$_exe
eval _$file=$xxx
case "$xxx" in
/*)
echo $file is in $xxx.
;;
?X: Under OS/2, we have PC-like paths
?:[\\]*)
echo $file is in $xxx.
;;
*)
echo "I don't see $file out there, $say."
say=either
;;
esac
done
case "$egrep" in
egrep)
echo "Substituting grep for egrep."

```

```

egrep=$grep
_egrep=$grep
;;
esac
@if less
case "$less"
in
") ;;
*) if $less -R </dev/null >/dev/null 2>&1; then
    echo "Substituting less -R for less."
    less="$less -R"
    _less=$less
fi
;;
esac
@end
@if ln
case "$ln" in
ln)
    echo "Substituting cp for ln."
    ln=$cp
    _ln=$cp
    ;;
esac
@end
@if make || gmake
case "$make" in
make)
case "$gmake" in
gmake)
    echo "I can't find make or gmake, and my life depends on it." >&4
    echo "Go find a public domain implementation or fix your PATH setting!" >&4
    exit 1
    ;;
esac
;;
esac
case "$gmake" in
gmake) ;;
*) # We can't have osname yet.
if test -f "/system/gnu_library/bin/ar.pm"; then # Stratus VOS
    # Assume that gmake, if found, is definitely GNU make
    # and prefer it over the system make.
    echo "Substituting gmake for make."
    make=$gmake
    _make=$gmake
fi
;;

```

```

esac
@end
case "$test" in
test)
echo "Hopefully test is built into your sh."
;;
*)
if `sh -c "PATH= test true" >/dev/null 2>&1`; then
echo "Using the test built into your sh."
?X:
?X: We need to set both test
and _test, since Oldconfig.U will use the _test
?X: value to systematically restore computed paths, which may be wrong if
?X: we choose to load an old config.sh generated on another platform.
?X:
test=test
_test=test
fi
;;
esac
?LINT:change n c
case "$echo" in
echo)
echo "Hopefully echo is built into your sh."
;;
?X: For those rare cases where we don't need $echo...
") ;;
*)
echo " "
echo "Checking compatibility between $echo and builtin echo (if any)..." >&4
$echo $n "hi there$c" >foo1
echo $n "hi there$c" >foo2
if cmp foo1 foo2 >/dev/null 2>&1; then
echo "They are compatible. In fact, they may be identical."
else
case "$n" in
'-n') n=" c='\c';;
*) n='-n' c="";;
esac
cat <<FOO
They are not compatible! You are probably running ksh on a non-USG system.
I'll have to use $echo instead of the builtin, since Bourne shell doesn't
have echo built in and we may have to run some Bourne shell scripts. That
means I'll have to use '$n$c' to suppress newlines now.
Life is ridiculous.

FOO
$echo $n "The star should be here-->$c"

```

```
$echo "*"
fi
$rm -f foo1 foo2
;;
esac
```

```
?X: The next part is irrelevant to the real process
# This question was auctioned at YAPC::Europe-2007 in Vienna
# I never promised you could answer it. I only auctioned the question.
cat <<FOO
The following message is sponsored by
```

Dresden.pm<--The stars should be here.

Dear Perl user, system administrator or package maintainer, the Perl community sends greetings to you. Do you (emblematical) greet back [Y/n]? n

FOO

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/modified/Loc.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: d_perror.U 1 2006-08-24 12:32:52Z rmanfredi $
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: $Log: d_perror.U,v $
?RCS: Revision 3.0.1.1 1994/08/29 16:11:38 ram
?RCS: patch32: always define HAS_PERROR even when not used in C code
?RCS:
?RCS: Revision 3.0 1993/08/18 12:06:45 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:d_perror: Inlibc
?MAKE: -pick add $@ %<
?S:d_perror:
?S: This variable conditionally remaps perror to a null action and
?S: defines the symbol HAS_PERROR, which indicates to the C program
?S: that the perror()
```

```

routine is not available to print system
?S: error messages.
?S:.
?C:HAS_PERROR ~ %<:
?C: This symbol, if defined, indicates that the perror() routine is
?C: available to print system error messages. If not defined, you should
?C: use your own diagnostic routine...
?C:.
?C:perror ~ %<:
?C: This symbol is mapped to null if the perror() routine is not
?C: available to print system error messages.
?C:.
?H:?%<:#$d_perror HAS_PERROR /**/
?H:?%<:#ifndef HAS_PERROR
?H:?%<:#define perror(s) ; /* mapped to a null statement */
?H:?%<:#endif
?H:.
?LINT:set d_perror
: see if perror exists
set perror d_perror
eval $inlibc

```

Found in path(s):

```

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/d_perror.U

```

No license file was found, but licenses were detected in source scan.

```

?RCS: $Id: d_vprintf.U,v 3.0 1993/08/18 12:07:59 ram Exp $
?RCS:
?RCS: Copyright (c) 1991-1993, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 3.0.
?RCS:
?RCS: $Log: d_vprintf.U,v $
?RCS: Revision 3.0 1993/08/18 12:07:59 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:d_vprintf d_charvspr: Compile Guess cat Csym Setvar run rm_try \
i_stdlib i_unistd i_stdarg i_varargs
?MAKE: -pick add $@ %<
?S:d_vprintf:
?S: This variable conditionally defines the HAS_VPRINTF symbol, which
?S: indicates to the C program that the vprintf() routine is available
?S: to printf with a pointer to an argument list.

```

```

?S:.
?S:d_charvspr:
?S: This
    variable conditionally defines CHARVSPRINTF if this system
?S: has vsprintf returning type (char*). The trend seems to be to
?S: declare it as "int vsprintf()".
?S:.
?C:HAS_VPRINTF (VPRINTF):
?C: This symbol, if defined, indicates that the vprintf routine is available
?C: to printf with a pointer to an argument list. If unavailable, you
?C: may need to write your own, probably in terms of _doprnt().
?C:.
?C:USE_CHAR_VSPRINTF (CHARVSPRINTF):
?C: This symbol is defined if this system has vsprintf() returning type
?C: (char*). The trend seems to be to declare it as "int vsprintf()". It
?C: is up to the package author to declare vsprintf correctly based on the
?C: symbol.
?C:.
?H:#$d_vprintf HAS_VPRINTF /**/
?H:#$d_charvspr USE_CHAR_VSPRINTF /**/
?H:.
?T:val2
?F:!try
?LINT:set d_vprintf d_charvspr
: see if vprintf exists
echo " "
if set vprintf val -f d_vprintf; eval $csym; $val; then
echo 'vprintf() found.'>&4
val="$define"
$cat >try.c <<EOF
#$i_stdarg I_STDARG
/* Only one of these can be defined by i_varhrd */
#$i_varargs I_VARARGS

#$i_stdlib I_STDLIB
#$i_unistd I_UNISTD

#ifdef I_STDARG
# include <stdarg.h>
#else /* I_VARARGS */
# include <varargs.h>
#endif

#ifdef I_UNISTD
# include <unistd.h>
#endif

#ifdef I_STDLIB

```

```

# include <stdlib.h>
#endif

#include <stdio.h> /* vsprintf prototype */

#ifdef I_STDARG
void xxx(int n, ...)
{
    va_list args;
    char buf[10];
    va_start(args, n);
    exit(((unsigned long)vsprintf(buf,"%s",args) > 10L);
}
int main() { xxx(1, "foo"); }

#else /* I_VARARGS */

xxx(va_alist)
va_dcl
{
    va_list args;
    char buf[10];
    va_start(args);
    exit(((unsigned long)vsprintf(buf,"%s",args) > 10L);
}
int main() { xxx("foo"); }

#endif

EOF
set try
if eval $compile_ok; then
if $run ./try; then
    echo "Your vsprintf() returns (int)." >&4
    val2="$undef"
else
    echo "Your vsprintf() returns (char*)." >&4
    val2="$define"
fi
else
echo 'I am unable to compile the vsprintf() test program.' >&4
#
We shouldn't get here. If we do, assume the standard signature,
# not the old BSD one.
echo 'Guessing that vsprintf() returns (int).' >&4
val2="$undef"
fi
else

```

```
echo 'vprintf() NOT found.' >&4
val="$undef"
val2="$undef"
fi
$rm_try
set d_vprintf
eval $setvar
val=$val2
set d_charvspr
eval $setvar
```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/compline/d_vprintf.U
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1999, Jarkko Hietaniemi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 3.0.

?RCS:

?MAKE:d_nanosleep: Inlibc

?MAKE: -pick add \$@ %<

?S:d_nanosleep:

?S: This variable conditionally defines HAS_NANOSLEEP

?S: if nanosleep() is available to sleep with 1E-9 sec accuracy.

?S:.

?C:HAS_NANOSLEEP:

?C: This symbol, if defined, indicates that the nanosleep

?C: system call is available to sleep with 1E-9 sec accuracy.

?C:.

?H:#\$d_nanosleep HAS_NANOSLEEP /**/

?H:.

?LINT:set d_nanosleep

: see if nanosleep exists

set nanosleep d_nanosleep

eval \$inlibc

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/perl/d_nanosleep.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: i_sysutsname.U,v $
?RCS:
?RCS: Copyright (c) 2000 Jarkko Hietaniemi
?RCS:
?RCS: You may distribute under the terms of either the GNU General Public
?RCS: License or the Artistic License, as specified in the README file.
?RCS:
?MAKE:i_sysutsname: Inhdr Hasfield
?MAKE: -pick add $@ %<
?S:i_sysutsname:
?S: This variable conditionally defines the I_SYSUTSNAME symbol,
?S: and indicates whether a C program should include <sys/utsname.h>.
?S:.
?C:I_SYSUTSNAME:
?C: This symbol, if defined, indicates that <sys/utsname.h> exists and
?C: should be included.
?C:.
?H:#$i_sysutsname I_SYSUTSNAME /**/
?H:.
?LINT:set i_sysutsname
: see if this is a sys/utsname.h system
set sys/utsname.h i_sysutsname
eval $inhdr
```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/perl/i_sysutsname.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: d_getwd.U 1 2006-08-24 12:32:52Z rmanfredi $
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: $Log: d_getwd.U,v $
?RCS: Revision 3.0 1993/08/18 12:06:18 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:d_getwd: Csym Setvar
?MAKE: -pick add $@ %<
?S:d_getwd:
?S: This variable conditionally defines HAS_GETWD if getwd() is
?S: available to get working directory. If not, you should
```

?S: probably use getcwd().
?S:.
?C:HAS_GETWD (GETWD):
?C: This symbol, if defined, indicates that the getwd routine is
?C: available to get working directory.

If not, you should

?C: probably use getcwd().

?C:.

?H:#\$d_getwd HAS_GETWD /**/

?H:.

?LINT:set d_getwd

: see if getwd exists

echo " "

if set getwd val -f d_getwd; eval \$csym; \$val; then

echo 'getwd() found.'>&4

val="\$define"

else

echo 'getwd() not found. Assuming getcwd() exists.'>&4

val="\$undef"

fi

set d_getwd

eval \$setvar

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/d_getwd.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_getprotobynumber_r.U,v 0RCS:

?RCS: Copyright (c) 2002,2003 Jarkko Hietaniemi

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?RCS: Generated by the reentr.pl from the Perl 5.8 distribution.

?RCS:

?MAKE:d_getprotobynumber_r getprotobynumber_r_proto: Inlibc Protochk \

Hasproto i_systypes usethreads i_netdb extern_C

?MAKE: -pick add \$@ %<

?S:d_getprotobynumber_r:

?S: This variable conditionally defines the HAS_GETPROTOBYNUMBER_R symbol,

?S: which indicates to the C program that the getprotobynumber_r()

?S: routine is available.

?S:.

?S:getprotobynumber_r_proto:

?S: This variable encodes the prototype of getprotobynumber_r.

?S: It is zero if d_getprotobynumber_r is undef, and one of the

?S: REENTRANT_PROTO_T_ABC macros of reentr.h if d_getprotobynumber_r

?S: is defined.

?S:.

?C:HAS_GETPROTOBYNUMBER_R:

?C: This
symbol, if defined, indicates that the getprotobynumber_r routine
?C: is available to getprotobynumber re-entrantly.

?C:.

?C:GETPROTOBYNUMBER_R_PROTO:

?C: This symbol encodes the prototype of getprotobynumber_r.

?C: It is zero if d_getprotobynumber_r is undef, and one of the
?C: REENTRANT_PROTO_T_ABC macros of reentr.h if d_getprotobynumber_r
?C: is defined.

?C:.

?H:#\$d_getprotobynumber_r HAS_GETPROTOBYNUMBER_R /**/
?H:#define GETPROTOBYNUMBER_R_PROTO \$getprotobynumber_r_proto /**/
?H:.

?T:try hdrs d_getprotobynumber_r_proto
: see if getprotobynumber_r exists
set getprotobynumber_r d_getprotobynumber_r
eval \$inlibc
case "\$d_getprotobynumber_r" in
"\$define")
hdrs="\$i_systypes sys/types.h define stdio.h \$i_netdb netdb.h"
case "\$d_getprotobynumber_r_proto:\$usetthreads" in
":define") d_getprotobynumber_r_proto=define
set d_getprotobynumber_r_proto getprotobynumber_r \$hdrs
eval \$hasproto ;;
*) ;;
esac
case "\$d_getprotobynumber_r_proto" in
define)
case "\$getprotobynumber_r_proto"
in
"|0) try='int getprotobynumber_r(int, struct protoent*, char*, size_t, struct protoent**);'
./protochk "\$extern_C \$try" \$hdrs && getprotobynumber_r_proto=I_ISBWR ;;
esac
case "\$getprotobynumber_r_proto" in
"|0) try='struct protoent* getprotobynumber_r(int, struct protoent*, char*, int);'
./protochk "\$extern_C \$try" \$hdrs && getprotobynumber_r_proto=S_ISBI ;;
esac
case "\$getprotobynumber_r_proto" in
"|0) try='int getprotobynumber_r(int, struct protoent*, struct protoent_data*);'
./protochk "\$extern_C \$try" \$hdrs && getprotobynumber_r_proto=I_ISD ;;
esac
case "\$getprotobynumber_r_proto" in
"|0) d_getprotobynumber_r=undef
getprotobynumber_r_proto=0
echo "Disabling getprotobynumber_r, cannot determine prototype." >&4 ;;

```

*) case "$getprotobynumber_r_proto" in
REENTRANT_PROTO*) ;;
*) getprotobynumber_r_proto="REENTRANT_PROTO_${getprotobynumber_r_proto}" ;;
esac
echo "Prototype: $try" ;;
esac
;;
*) case "$susetheads" in
define) echo
"getprotobynumber_r has no prototype, not using it." >&4 ;;
esac
d_getprotobynumber_r=undef
getprotobynumber_r_proto=0
;;
esac
;;
*) getprotobynumber_r_proto=0
;;
esac

```

Found in path(s):

```

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/threads/d_getprotobynumber_r.U

```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1999, Jarkko Hietaniemi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 3.0.

?RCS:

?MAKE:d_posix_sem: Setvar d_sem_open d_sem_unlink d_sem_close d_sem_destroy d_sem_getvalue d_sem_post
d_sem_wait d_sem_init d_sem_trywait i_semaphore

?MAKE: -pick add \$@ %<

?S:d_posix_sem:

?S: This variable conditionally defines the HAS_POSIX_SEM symbol, which

?S: indicates that the entire sem*(2) library is present.

?S:.

?C:HAS_POSIX_SEM:

?C: This symbol, if defined, indicates that the entire POSIX sem_*(2)

?C: library is supported.

?C:.

?H:#\$d_posix_sem HAS_POSIX_SEM /**/

?H:.

```

?LINT:set d_posix_sem
: see how much of the
'POSIX sem_*(2)' library is present.
echo " "
case
"$i_semaphore$d_sem_open$d_sem_close$d_sem_destroy$d_sem_getvalue$d_sem_post$d_sem_wait$d_sem_try
wait$d_sem_init$d_sem_unlink" in
*"$undef"*) val="$undef" ;;
*) val="$define" ;;
esac
case "$val" in
"$define") echo "You have the full POSIX sem_*(2) library." >&4 ;;
"$undef") echo "You don't have the full POSIX sem_*(2) library." >&4 ;;
esac
set d_posix_sem
eval $setvar

```

Found in path(s):

```

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/perl/d_posix_sem.U

```

No license file was found, but licenses were detected in source scan.

```

?RCS: $Id: libpth.U 1 2006-08-24 12:32:52Z rmanfredi $
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: $Log: libpth.U,v $
?RCS: Revision 3.0.1.6 1997/02/28 16:08:49 ram
?RCS: patch61: new loclibpth variable
?RCS:
?RCS: Revision 3.0.1.5 1995/01/11 15:31:30 ram
?RCS: patch45: call ./mips instead of just mips (WED)
?RCS:
?RCS: Revision 3.0.1.4 1994/08/29 16:29:15 ram
?RCS: patch32: added /lib/pa1.1 for HP-UX specially tuned PA-RISC libs (ADO)
?RCS: patch32: fixed information message, making it clearer (ADO)
?RCS:
?RCS: Revision 3.0.1.3 1994/06/20 07:03:54
ram
?RCS: patch30: added /usr/shlib to glibpth for shared-only libraries
?RCS:
?RCS: Revision 3.0.1.2 1994/05/13 15:26:57 ram

```

?RCS: patch27: fixed a typo (libpth -> glibpth)
?RCS:
?RCS: Revision 3.0.1.1 1994/05/06 15:07:53 ram
?RCS: patch23: now asks for library directories to be searched (ADO)
?RCS:
?RCS: Revision 3.0 1993/08/18 12:09:02 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?X:
?X: This unit initializes the path for C library lookup.
?X:
?MAKE:libpth glibpth xlibpth plibpth loclibpth incpth: \
usrinc incpath test cat Myread Oldconfig sysroot osname \
ccname echo cppstdin awk grep sed rm usecrosscompile
?MAKE: -pick add \$@ %<
?S:libpth:
?S: This variable holds the general path (space-separated) used to find
?S: libraries. It is intended to be used by other units.
?S:.
?S:glibpth:
?S: This variable holds the general path (space-separated) used to
?S: find libraries. It may contain directories that do not exist on
?S: this platform, libpth is the cleaned-up
version.
?S:.
?S:xlibpth:
?S: This variable holds extra path (space-separated) used to find
?S: libraries on this platform, for example CPU-specific libraries
?S: (on multi-CPU platforms) may be listed here.
?S:.
?S:loclibpth:
?S: This variable holds the paths (space-separated) used to find local
?S: libraries. It is prepended to libpth, and is intended to be easily
?S: set from the command line.
?S:.
?S:plibpth:
?S: Holds the private path used by Configure to find out the libraries.
?S: Its value is prepend to libpth. This variable takes care of special
?S: machines, like the mips. Usually, it should be empty.
?S:.
?S:incpth:
?S: This variable must precede the normal include path to get the
?S: right one, as in "\$incpath/usr/include" or "\$incpath/usr/lib".
?S: Value can be "" or "/bsd43" on mips.
?S:.
?T: xxx dlist i j croak
?LINT:extern incpth
?LINT:change usrinc


```

done
libpth=""$echo $libpth|sed 's/^ //'
for xxx in $libpth $loclibpth $plibpth $glibpth; do
if $test -d $xxx; then
  case " $libpth " in
    *" $xxx ") ;;
    *) libpth="$libpth $xxx";;
  esac
fi

done
fi
$rm -f try.c
case "$usrinc" in
") for i in $incpth; do
if $test -f $i/errno.h -a -f $i/stdio.h -a -f $i/time.h; then
  usrinc="$i"
  break
fi
done
;;
esac

case "$usecrosscompile" in
$define[true[|yY]*)
  case "$incpth" in
") echo "Incpth not defined." >&4; croak=y ;;
*) echo "Using incpth '$incpth'." >&4 ;;
  esac
  case "$libpth" in
") echo "Libpth not defined." >&4; croak=y ;;
*) echo "Using libpth '$libpth'." >&4 ;;
  esac
  case "$usrinc" in
") echo "Usrinc not defined." >&4; croak=y ;;
*) echo "Using usrinc $usrinc." >&4 ;;
  esac
  case "$croak" in
y)
if test "X$sysroot" = X; then
  echo "Cannot continue, aborting." >&4; exit 1
else
  echo "Cross-compiling using sysroot $sysroot, failing to guess inc/lib paths is not fatal" >&4
fi
;;
esac
;;
esac

```

```
;;
esac
```

```
: Default value for incpth is just usrinc
```

```
case "$incpth" in
") incpth="$usrinc";;
esac
```

```
: Set private lib path
```

```
case
"$plibpth" in
") if ./mips; then
?X: on mips, we DO NOT want /lib, and we want $incpath/usr/lib
plibpth="$incpath/usr/lib $sysroot/usr/local/lib $sysroot/usr/ccs/lib"
fi;;
esac
case "$libpth" in
' ') dlist="";;
") dlist="$loclibpth $plibpth $glibpth";;
*) dlist="$libpth";;
esac
```

```
: Now check and see which directories actually exist, avoiding duplicates
```

```
for xxx in $dlist
```

```
do
```

```
if $test -d $xxx; then
case " $libpth " in
*" $xxx "*) ;;
*) libpth="$libpth $xxx";;
```

```
esac
```

```
fi
```

```
done
```

```
$cat <<'EOM'
```

Some systems have incompatible or broken versions of libraries. Among the directories listed in the question below, please remove any you know not to be holding relevant libraries, and add any that are needed. Say "none" for none.

```
EOM
```

```
if test "X$sysroot" != X; then
```

```
$cat <<EOM
```

You have set sysroot to \$sysroot, please supply the directories excluding sysroot

```
EOM
```

```
fi
```

```

case "$libpth" in
") dflt='none';;
*)
?X: strip leading space
set X $libpth
shift
dflt=${1+"$@"}
;;
esac
rp="Directories
to use for library searches?"
./myread
case "$ans" in
none) libpth='';;
*) libpth="$ans";;
esac

```

Found in path(s):

```

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/modified/libpth.U

```

No license file was found, but licenses were detected in source scan.

```

?RCS: $Id: d_memset.U 1 2006-08-24 12:32:52Z rmanfredi $
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: $Log: d_memset.U,v $
?RCS: Revision 3.0.1.1 1993/09/13 16:03:11 ram
?RCS: patch10: removed text recommending bzero over memset (WAD)
?RCS:
?RCS: Revision 3.0 1993/08/18 12:06:36 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:d_memset: Inlibc
?MAKE: -pick add $@ %<
?S:d_memset:
?S: This variable conditionally defines the HAS_MEMSET symbol, which
?S: indicates to the C program that the memset() routine is available
?S: to set blocks of memory.
?S:.
?C:HAS_MEMSET

```

(MEMSET):

?C: This symbol, if defined, indicates that the memset routine is available

?C: to set blocks of memory.

?C:.

?H:#\$d_memset HAS_MEMSET /**/

?H:.

?LINT:set d_memset

: see if memset exists

set memset d_memset

eval \$inlibc

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/d_memset.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 2000 Jarkko Hietaniemi

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?MAKE:d_ualarm: Inlibc

?MAKE: -pick add \$@ %<

?S:d_ualarm:

?S: This variable conditionally defines the HAS_UALARM symbol, which

?S: indicates to the C program that the ualarm() routine is available.

?S:.

?C:HAS_UALARM:

?C: This symbol, if defined, indicates that the ualarm routine is

?C: available to do alarms with microsecond granularity.

?C:.

?H:#\$d_ualarm HAS_UALARM /**/

?H:.

?LINT:set d_ualarm

: see if ualarm exists

set ualarm d_ualarm

eval \$inlibc

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_ualarm.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_getprotby.U,v \$

?RCS:

?RCS: Copyright (c) 1998 Andy Dougherty

?RCS:
?RCS: You may distribute under the terms of either the GNU General Public
?RCS: License or the Artistic License, as specified in the README file.
?RCS:
?MAKE:d_getpbyname d_getpbynumber: Inlibc
?MAKE: -pick add \$@ %<
?S:d_getpbyname:
?S: This variable conditionally defines the HAS_GETPROTOBYNAME
?S: symbol, which indicates to the C program that the
?S: getprotobyname() routine is available to look up protocols
?S: by their name.
?S:.
?S:d_getpbynumber:
?S: This variable conditionally defines the HAS_GETPROTOBYNUMBER
?S: symbol, which indicates to the C program that the
?S: getprotobynumber() routine is available to look up protocols
?S: by their number.
?S:.
?C:HAS_GETPROTOBYNAME:
?C: This symbol, if defined, indicates that the getprotobyname()
?C: routine is available to look up protocols by their name.
?C:.
?C:HAS_GETPROTOBYNUMBER:
?C: This
symbol, if defined, indicates that the getprotobynumber()
?C: routine is available to look up protocols by their number.
?C:.
?H:#\$d_getpbyname HAS_GETPROTOBYNAME /**/
?H:#\$d_getpbynumber HAS_GETPROTOBYNUMBER /**/
?H:.
?LINT:set d_getpbyname d_getpbynumber
: Optional checks for getprotobyname and getprotobynumber

```
@if d_getpbyname || HAS_GETPROTOBYNAME
: see if getprotobyname exists
set getprotobyname d_getpbyname
eval $inlibc
@end
```

```
@if d_getpbynumber || HAS_GETPROTOBYNUMBER
: see if getprotobynumber exists
set getprotobynumber d_getpbynumber
eval $inlibc
@end
```

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/modified/d_getprotby.U

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id$
?RCS:
?RCS: Copyright (c) 1999 Jarkko Hietaniemi
?RCS:
?RCS: You may distribute under the terms of either the GNU General Public
?RCS: License or the Artistic License, as specified in the README file.
?RCS:
?MAKE:d_llseek: Inlibc
?MAKE: -pick add $@ %<
?S:d_llseek:
?S: This variable conditionally defines the HAS_LLSEEK symbol, which
?S: indicates to the C program that the llseek() routine is available.
?S:.
?C:HAS_LLSEEK:
?C: This symbol, if defined, indicates that the llseek routine is
?C: available to seek files larger than 2 gigabytes.
?C:.
?H:#$d_llseek HAS_LLSEEK /**/
?H:.
?LINT:set d_llseek
: see if llseek exists
set llseek d_llseek
eval $inlibc
```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/perl/d_llseek.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id$
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: $Log: privlib.U,v $
?RCS: Revision 3.0.1.4 1995/09/25 09:17:09 ram
?RCS: patch59: unit is now forced to the top of Configure, if possible
?RCS:
?RCS: Revision 3.0.1.3 1995/01/30 14:44:23 ram
?RCS: patch49: can now handle installation prefix changes (from WED)
?RCS:
```

?RCS: Revision 3.0.1.2 1994/08/29 16:31:52 ram
?RCS: patch32: now uses installation prefix
?RCS:
?RCS: Revision 3.0.1.1 1993/09/13 16:12:34 ram
?RCS: patch10: added support for /local/lib (WED)
?RCS: patch10: prompt phrasing made
more explicit (WED)
?RCS:
?RCS: Revision 3.0 1993/08/18 12:09:35 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:privlib privlibexp installprivlib: afs package cat Getfile \
Oldconfig Prefixit test
?MAKE: -pick add \$@ %<
?Y:TOP
?S:privlib:
?S: This variable contains the eventual value of the PRIVLIB symbol,
?S: which is the name of the private library for this package. It may
?S: have a ~ on the front. It is up to the makefile to eventually create
?S: this directory while performing installation (with ~ substitution).
?S:.
?S:privlibexp:
?S: This variable is the ~name expanded version of privlib, so that you
?S: may use it directly in Makefiles or shell scripts.
?S:.
?S:installprivlib:
?S: This variable is really the same as privlibexp but may differ on
?S: those systems using AFS. For extra portability, only this variable
?S: should be used in makefiles.
?S:.
?C:PRIVLIB:
?C: This symbol contains the name of the private library for this package.
?C: The library is
private in the sense that it needn't be in anyone's
?C: execution path, but it should be accessible by the world. The program
?C: should be prepared to do ~ expansion.
?C:.
?C:PRIVLIB_EXP:
?C: This symbol contains the ~name expanded version of PRIVLIB, to be used
?C: in programs that are not prepared to deal with ~ expansion at run-time.
?C:.
?H:#define PRIVLIB "\$privlib" /**/
?H:#define PRIVLIB_EXP "\$privlibexp" /**/
?H:.
: determine where private executables go
set dflt privlib lib/\$package
eval \$prefixit
\$cat <<EOM

There are some auxiliary files for \$package that need to be put into a private library directory that is accessible by everyone.

```
EOM
fn=d~+
rp='Pathname where the private library files will reside?'
./getfile
if $test "X$privlibexp" != "X$ansexp"; then
  installprivlib="
fi
privlib="$ans"
privlibexp="$ansexp"
if $afs; then
  $cat <<EOM
```

Since you are running AFS, I need to distinguish the directory in which private files reside from the directory in which they are installed (and from which they are presumably copied to the former directory by occult means).

```
EOM
case "$installprivlib" in
  *) dflt=`echo $privlibexp | sed 's#^/afs/#/afs/#`";
  *) dflt="$installprivlib";;
esac
fn=de~
rp='Where will private files be installed?'
./getfile
installprivlib="$ans"
else
  installprivlib="$privlibexp"
fi
```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/privlib.U
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1999 Jarkko Hietaniemi

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

```
?MAKE:d_quad quadtype uquadtype quadkind: \
longsize intsize d_longlong longlongsize d_int64_t \
```

```

Inhdr Setvar
?MAKE: -pick add $@ %<
?S:d_quad:
?S: This variable, if defined, tells that there's a 64-bit integer type,
?S: quadtype.
?S:.
?S:quadtype:
?S: This variable defines Quad_t to be something like long, int,
?S: long long, int64_t, or whatever type is used for 64-bit integers.
?S:.
?S:quadkind:
?S: This variable, if defined, encodes the type of a quad:
?S: 1 = int, 2 = long, 3 = long long, 4 = int64_t.
?S:.
?S:uquadtype:
?S: This variable defines Uquad_t to be something like unsigned long,
?S: unsigned int, unsigned long long, uint64_t, or whatever type is
?S: used for 64-bit integers.
?S:.
?C:HAS_QUAD:
?C: This
symbol, if defined, tells that there's a 64-bit integer type,
?C: Quad_t, and its unsigned counterpart, Uquad_t. QUADKIND will be one
?C: of QUAD_IS_INT, QUAD_IS_LONG, QUAD_IS_LONG_LONG, QUAD_IS_INT64_T,
?C: or QUAD_IS___INT64.
?C:.
?H:#$d_quad HAS_QUAD /**/
?H:%<:#ifdef HAS_QUAD
?H:%<:# define Quad_t $quadtype /**/
?H:%<:# define Uquad_t $uquadtype /**/
?H:%<:# define QUADKIND $quadkind /**/
?H:%<:# define QUAD_IS_INT 1
?H:%<:# define QUAD_IS_LONG 2
?H:%<:# define QUAD_IS_LONG_LONG 3
?H:%<:# define QUAD_IS_INT64_T 4
?H:%<:# define QUAD_IS___INT64 5
?H:%<:#endif
?H:.
?LINT:set quadtype
?LINT:set uquadtype
: Check if 64bit ints have a quad type
echo " "
echo "Checking which 64-bit integer type we could use..." >&4
?X: We prefer quad types in order of int, long, long long, int64_t.

case "$intsize" in
8) val=int
set quadtype

```

```

eval $setvar
val="unsigned int"
set uquadtype
eval $setvar
quadkind=1
;;
*) case "$longsize" in
8)
val=long
set quadtype
eval $setvar
val="unsigned long"
set uquadtype
eval $setvar
quadkind=2
;;
*) case "$d_longlong:$longlongsize" in
define:8)
val="long long"
set quadtype
eval $setvar
val="unsigned long long"
set uquadtype
eval $setvar
quadkind=3
;;
*) case "$d_int64_t" in
define)
val=int64_t
set quadtype
eval $setvar
val=uint64_t
set uquadtype
eval $setvar
quadkind=4
;;
esac
;;
esac
;;
esac
;;
esac
;;
esac

case "$quadtype" in
") echo "Alas, no 64-bit integer types in sight." >&4
d_quad="$undef"
;;

```

```
*) echo "We could use 'Squadtype' for 64-bit integers." >&4
d_quad="$define"
;;
esac
```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/a_dvisory/quadtype.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: i_whoami.U 1 2006-08-24 12:32:52Z rmanfredi $
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: $Log: i_whoami.U,v $
?RCS: Revision 3.0.1.1 1993/08/25 14:02:21 ram
?RCS: patch6: added default for i_whoami
?RCS:
?RCS: Revision 3.0 1993/08/18 12:08:50 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:i_whoami: Inhdr
?MAKE: -pick add $@ %<
?S:i_whoami (d_whoami):
?S: This variable conditionally defines the I_WHOAMI symbol, which
?S: indicates to the C program that it should include <whoami.h>.
?S:.
?C:I_WHOAMI (WHOAMI):
?C: This symbol,
if defined, indicates that the program may include
?C: <whoami.h>.
?C:.
?H:#$i_whoami I_WHOAMI /**/
?H:.
?D:i_whoami="
?LINT:set i_whoami
: see if there is a whoami.h file
set whoami.h i_whoami
eval $inhdr
```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
```

debian-perl-5.26.1/dist/U/i_whoami.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 2000 Jarkko Hietaniemi

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?MAKE:d_fp_classl: Inlibc

?MAKE: -pick add \$@ %<

?S:d_fp_classl:

?S: This variable conditionally defines the HAS_FP_CLASSL symbol, which

?S: indicates to the C program that the fp_classl() routine is available.

?S:.

?C:HAS_FP_CLASSL:

?C: This symbol, if defined, indicates that the fp_classl routine is

?C: available to classify long doubles. Available for example in

?C: Digital UNIX. See for possible values HAS_FP_CLASS.

?C:.

?H:#\$d_fp_classl HAS_FP_CLASSL /**/

?H:.

?LINT:set d_fp_classl

: see if fp_classl exists

set fp_classl d_fp_classl

eval \$inlibc

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-

debian-perl-5.26.1/U/perl/d_fp_classl.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_link.U 1 2006-08-24 12:32:52Z rmanfredi \$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic Licence,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic Licence; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: d_link.U,v \$

?RCS: Revision 3.0.1.1 1993/08/25 14:01:13 ram

?RCS: patch6: created for completeness

?RCS:

?MAKE:d_link: Inlibc

?MAKE: -pick add \$@ %<
?S:d_link:
?S: This variable conditionally defines HAS_LINK if link() is
?S: available to create hard links.
?S:.
?C:HAS_LINK:
?C: This symbol, if defined, indicates that the link routine is
?C: available to create hard links.
?C:.
?H:#\$d_link HAS_LINK /**/
?H:.
?LINT:set d_link
: see if link exists
set
link d_link
eval \$inlibc

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/d_link.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$
?RCS:
?RCS: Copyright (c) 1999 Jarkko Hietaniemi
?RCS:
?RCS: You may distribute under the terms of either the GNU General Public
?RCS: License or the Artistic License, as specified in the README file.
?RCS:
?MAKE:d_PRI64 d_PRIi64 d_PRIu64 d_PRIO64 d_PRIx64 d_PRIXU64 \
sPRI64 sPRIi64 sPRIu64 sPRIO64 sPRIx64 sPRIXU64: \
quadtype i_inttypes test cat rm_try Setvar Compile run
?MAKE: -pick add \$@ %<
?S:d_PRI64:
?S: This variable conditionally defines the PERL_PRI64 symbol, which
?S: indicates that stdio has a symbol to print 64-bit decimal numbers.
?S:.
?S:d_PRIi64:
?S: This variable conditionally defines the PERL_PRIi64 symbol, which
?S: indicates that stdio has a symbol to print 64-bit decimal numbers.
?S:.
?S:d_PRIu64:
?S: This variable conditionally defines the PERL_PRIu64 symbol, which
?S: indicates that stdio has a symbol to print 64-bit unsigned decimal
?S: numbers.
?S:.
?S:d_PRIO64:
?S: This variable

conditionally defines the PERL_PRIo64 symbol, which
?S: indicates that stdio has a symbol to print 64-bit octal numbers.
?S:.
?S:d_PRIx64:
?S: This variable conditionally defines the PERL_PRIx64 symbol, which
?S: indicates that stdio has a symbol to print 64-bit hexadecimal numbers.
?S:.
?S:d_PRiXU64:
?S: This variable conditionally defines the PERL_PRiXU64 symbol, which
?S: indicates that stdio has a symbol to print 64-bit hExADECimAl numbers.
?S: The 'U' in the name is to separate this from d_PRIx64 so that even
?S: case-blind systems can see the difference.
?S:.
?S:sPRId64:
?S: This variable, if defined, contains the string used by stdio to
?S: format 64-bit decimal numbers (format 'd') for output.
?S:.
?S:sPRIi64:
?S: This variable, if defined, contains the string used by stdio to
?S: format 64-bit decimal numbers (format 'i') for output.
?S:.
?S:sPRIu64:
?S: This variable, if defined, contains the string used by stdio to
?S: format 64-bit unsigned decimal numbers (format 'u')
for output.
?S:.
?S:sPRIo64:
?S: This variable, if defined, contains the string used by stdio to
?S: format 64-bit octal numbers (format 'o') for output.
?S:.
?S:sPRIx64:
?S: This variable, if defined, contains the string used by stdio to
?S: format 64-bit hexadecimal numbers (format 'x') for output.
?S:.
?S:sPRiXU64:
?S: This variable, if defined, contains the string used by stdio to
?S: format 64-bit hExADECimAl numbers (format 'X') for output.
?S: The 'U' in the name is to separate this from sPRIx64 so that even
?S: case-blind systems can see the difference.
?S:.
?C:PERL_PRId64:
?C: This symbol, if defined, contains the string used by stdio to
?C: format 64-bit decimal numbers (format 'd') for output.
?C:.
?C:PERL_PRIi64:
?C: This symbol, if defined, contains the string used by stdio to
?C: format 64-bit decimal numbers (format 'i') for output.
?C:.

```

?C:PERL_PRIu64:
?C: This symbol, if defined, contains the string used by stdio to
?C: format 64-bit unsigned decimal numbers (format 'u')
for output.
?C:.
?C:PERL_PRIo64:
?C: This symbol, if defined, contains the string used by stdio to
?C: format 64-bit octal numbers (format 'o') for output.
?C:.
?C:PERL_PRIx64:
?C: This symbol, if defined, contains the string used by stdio to
?C: format 64-bit hexadecimal numbers (format 'x') for output.
?C:.
?C:PERL_PRiXU64:
?C: This symbol, if defined, contains the string used by stdio to
?C: format 64-bit hExADECimAl numbers (format 'X') for output.
?C:.
?H:#$d_PRIId64 PERL_PRIId64 $sPRIId64 /**/
?H:#$d_PRIi64 PERL_PRIi64 $sPRIi64 /**/
?H:#$d_PRIu64 PERL_PRIu64 $sPRIu64 /**/
?H:#$d_PRIo64 PERL_PRIo64 $sPRIo64 /**/
?H:#$d_PRIx64 PERL_PRIx64 $sPRIx64 /**/
?H:#$d_PRIx64 PERL_PRiXU64 $sPRiXU64 /**/
?H:.
?T:yyy
?F:!try
: Check 64bit sizes
echo " "

if $test X"$quadtype" != X; then

echo "Checking how to print 64-bit integers..." >&4

if $test X"$sPRIId64" = X -a X"$quadtype" = Xint; then
$cat >try.c <<'EOCP'
#include <sys/types.h>
#include <stdio.h>
int main() {
int q = 12345678901;

printf("%ld\n", q);
}
EOCP
set try
if eval $compile; then
yyy=`$run ./try`
case "$yyy" in
12345678901)

```

```

sPRId64=""d""; sPRIi64=""i""; sPRIu64=""u"";
    sPRIo64=""o""; sPRIx64=""x""; sPRIXU64=""X"";
echo "We will use %d."
;;
esac
fi
fi

if $test X"$sPRId64" = X -a X"$squadtype" = Xlong; then
$cat >try.c <<'EOCP'
#include <sys/types.h>
#include <stdio.h>
int main() {
    long q = 12345678901;
    printf("%ld\n", q);
}
EOCP
set try
if eval $compile; then
yyy=`$run ./try`
case "$yyy" in
12345678901)
sPRId64=""ld""; sPRIi64=""li""; sPRIu64=""lu"";
    sPRIo64=""lo""; sPRIx64=""lx""; sPRIXU64=""lX"";
echo "We will use %ld."
;;
esac
fi
fi

```

```

if $test X"$sPRId64" = X -a X"$si_inttypes" = X"$define" -a X"$squadtype" = Xint64_t; then
$cat >try.c <<'EOCP'
#include <sys/types.h>
#include <inttypes.h>
#include <stdio.h>
int main() {
    int64_t q = 12345678901;
    printf("%" PRId64 "\n", q);
}
EOCP
set try
if eval $compile; then
yyy=`$run
./try`
case "$yyy" in
12345678901)
sPRId64=PRId64; sPRIi64=PRIi64; sPRIu64=PRIu64;
    sPRIo64=PRIo64; sPRIx64=PRIx64; sPRIXU64=PRIXU64;

```

```

    echo "We will use the C9X style."
    ;;
esac
fi
fi

if $test X"$sPRId64" = X -a X"$squadtype" != X; then
    $cat >try.c <<EOCP
#include <sys/types.h>
#include <stdio.h>
int main() {
    $squadtype q = 12345678901;
    printf("%Ld\n", q);
}
EOCP
set try
if eval $compile; then
    yyy=`$run ./try`
    case "$yyy" in
        12345678901)
            sPRId64="Ld"; sPRIi64="Li"; sPRIu64="Lu";
            sPRIo64="Lo"; sPRIx64="Lx"; sPRIXU64="LX";
            echo "We will use %Ld."
            ;;
        esac
    fi
fi

if $test X"$sPRId64" = X -a X"$squadtype" = X"long long"; then
    $cat >try.c <<'EOCP'
#include <sys/types.h>
#include <stdio.h>
int main() {
    long long q = 12345678901LL; /* AIX cc requires the LL suffix. */
    printf("%lld\n", q);
}
EOCP
set try
if eval $compile; then
    yyy=`$run ./try`
    case "$yyy" in
        12345678901)
            sPRId64="lld"; sPRIi64="lli";
            sPRIu64="llu";
            sPRIo64="llo"; sPRIx64="llx"; sPRIXU64="lIX";
            echo "We will use the %lld style."
            ;;
        esac
    fi
fi

```

fi

fi

```
if $test X"$sPRId64" = X -a X"$quadtype" != X; then
```

```
  $cat >try.c <<EOCP
```

```
#include <sys/types.h>
```

```
#include <stdio.h>
```

```
int main() {
```

```
  $quadtype q = 12345678901;
```

```
  printf("%qd\n", q);
```

```
}
```

```
EOCP
```

```
set try
```

```
if eval $compile; then
```

```
  yyy=`$run ./try`
```

```
  case "$yyy" in
```

```
    12345678901)
```

```
      sPRId64="qd"; sPRi64="qi"; sPRi64="qu";
```

```
        sPRi64="qo"; sPRix64="qx"; sPRix64="qX";
```

```
      echo "We will use %qd."
```

```
    ;;
```

```
  esac
```

```
fi
```

```
fi
```

```
if $test X"$sPRId64" = X; then
```

```
  echo "Cannot figure out how to print 64-bit integers." >&4
```

```
fi
```

```
$rm_try
```

```
fi
```

```
case "$sPRId64" in
```

```
  *) d_PRId64="$undef"; d_PRi64="$undef"; d_PRi64="$undef";
```

```
    d_PRi64="$undef"; d_PRix64="$undef"; d_PRix64="$undef";
```

```
    ;;
```

```
  *) d_PRId64="$define"; d_PRi64="$define"; d_PRi64="$define";
```

```
    d_PRi64="$define"; d_PRix64="$define"; d_PRix64="$define";
```

```
    ;;
```

```
esac
```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/quadfio.U
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

```

?RCS: Copyright (c) 1999 Jarkko Hietaniemi
?RCS:
?RCS: You may distribute under the terms of either the GNU General Public
?RCS: License or the Artistic License, as specified in the README file.
?RCS:
?MAKE:d_iovec_s: i_sysuio Hasfield
?MAKE: -pick add $@ %<
?S:d_iovec_s:
?S: This variable conditionally defines the HAS_STRUCT_IOVEC symbol,
?S: which indicates that the struct iovec is supported.
?S:.
?C:HAS_STRUCT_IOVEC:
?C: This symbol, if defined, indicates that the struct iovec
?C: to do scatter writes/gather reads is supported.
?C:.
?H:#$d_iovec_s HAS_STRUCT_IOVEC /**/
?H:.
?LINT:set d_iovec_s
: Check for iovec_s
echo "Checking to see if your system supports struct iovec..." >&4
set d_iovec_s iovec iov_base $i_sysuio sys/uio.h
eval $hasfield
case "$d_iovec_s" in
"$define") echo "Yup, it does." ;;
*) echo "Nope, it doesn't." ;;
esac

```

Found in path(s):

```

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/perl/d_iovec_s.U

```

No license file was found, but licenses were detected in source scan.

```

?RCS: $Id: d_shmdt.U 1 2006-08-24 12:32:52Z rmanfredi $
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: $Log: d_shmdt.U,v $
?RCS: Revision 3.0 1993/08/18 12:07:19 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:d_shmdt: Inlibc
?MAKE: -pick add $@ %<

```

?S:d_shmmt:

?S: This variable conditionally defines the HAS_SHMMDT symbol, which

?S: indicates to the C program that the shmmt() routine is available.

?S:.

?C:HAS_SHMMDT:

?C: This symbol, if defined, indicates that the shmmt() routine is

?C: available to detach a shared memory segment from the process space.

?C:.

?H:#\$d_shmmt HAS_SHMMDT /**/

?H:.

?LINT:set d_shmmt

: see if shmmt exists

set shmmt d_shmmt

eval \$inlibc

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/d_shmmt.U

No license file was found, but licenses were detected in source scan.

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?MAKE:d_lroundl: Inlibc

?MAKE: -pick add \$@ %<

?S:d_lroundl:

?S: This variable conditionally defines the HAS_LROUNDL symbol, which

?S: indicates to the C program that the lroundl() routine is available

?S: to return the integral value nearest to x away from zero.

?S:.

?C:HAS_LROUNDL:

?C: This symbol, if defined, indicates that the lroundl routine is

?C: available to return the nearest integral value away from zero of

?C: the long double argument value.

?C:.

?H:#\$d_lroundl HAS_LROUNDL /**/

?H:.

?LINT:set d_lroundl

: see if lroundl exists

set lroundl d_lroundl

eval \$inlibc

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_lroundl.U

No license file was found, but licenses were detected in source scan.

```

?RCS: $Id: i_sysmode.U,v $
?RCS:
?RCS: Copyright (c) 2000 Jarkko Hietaniemi
?RCS:
?RCS: You may distribute under the terms of either the GNU General Public
?RCS: License or the Artistic License, as specified in the README file.
?RCS:
?MAKE:i_sysmode: Inhdr Hasfield
?MAKE: -pick add $@ %<
?S:i_sysmode:
?S: This variable conditionally defines the I_SYSMODE symbol,
?S: and indicates whether a C program should include <sys/mode.h>.
?S:.
?C:I_SYSMODE:
?C: This symbol, if defined, indicates that <sys/mode.h> exists and
?C: should be included.
?C:.
?H:#$i_sysmode I_SYSMODE /**/
?H:.
?LINT:set i_sysmode
: see if this is a sys/mode.h system
set sys/mode.h i_sysmode
eval $inhdr

```

Found in path(s):

```

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/perl/i_sysmode.U

```

No license file was found, but licenses were detected in source scan.

```

?RCS: $Id: d_mkdir.U 1 2006-08-24 12:32:52Z rmanfredi $
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: $Log: d_mkdir.U,v $
?RCS: Revision 3.0 1993/08/18 12:06:37 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:d_mkdir: Inlibc
?MAKE: -pick add $@ %<
?S:d_mkdir:
?S: This variable conditionally defines the HAS_MKDIR symbol, which
?S: indicates to the C program that the mkdir() routine is available

```

?S: to create directories..

?S:.

?C:HAS_MKDIR (MKDIR):

?C: This symbol, if defined, indicates that the mkdir routine is available

?C: to create directories.

Otherwise you should fork off a new process to

?C: exec /bin/mkdir.

?C:.

?H:#\$d_mkdir HAS_MKDIR /**/

?H:.

?LINT:set d_mkdir

: see if mkdir exists

set mkdir d_mkdir

eval \$inlibc

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/d_mkdir.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_shm.U,v 3.0 1993/08/18 12:07:17 ram Exp \$

?RCS:

?RCS: Copyright (c) 1991-1993, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 3.0.

?RCS:

?RCS: \$Log: d_shm.U,v \$

?RCS: Revision 3.0 1993/08/18 12:07:17 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?MAKE:d_shm: test d_shmctl d_shmget d_shmat d_shmdt Setvar Findhdr osname

?MAKE: -pick add \$@ %<

?S:d_shm:

?S: This variable conditionally defines the HAS_SHM symbol, which

?S: indicates that the entire shm*(2) library is present.

?S:.

?C:HAS_SHM:

?C: This symbol, if defined, indicates that the entire shm*(2) library is

?C: supported.

?C:.

?H:#\$d_shm HAS_SHM /**/

?H:.

?T:h_shm

?LINT:set

```

d_shm
: see how much of the 'shm*(2)' library is present.
h_shm=true
echo " "
case "$d_shmctl$d_shmget$d_shmat$d_shmdt" in
*"${undef}*" ) h_shm=false;;
esac
case "$osname" in
freebsd)
  case "`ipcs 2>&1`" in
  "SVID shared memory"*"not configured"*)
  echo "Your $osname does not have the shm*(2) configured." >&4
    h_shm=false
  val="${undef}"
  set shmctl d_shmctl
  eval $setvar
  set shmget d_shmget
  eval $setvar
  set shmat d_shmat
  eval $setvar
  set shmdt d_shmdt
  eval $setvar
  ;;
  esac
  ;;
esac
: we could also check for sys/ipc.h ...
if $h_shm && $test `./findhdr sys/shm.h`; then
  echo "You have the full shm*(2) library." >&4
  val="$define"
else
  echo "You don't have the full shm*(2) library." >&4
  val="${undef}"
fi
set d_shm
eval $setvar

```

Found in path(s):

```

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/modified/d_shm.U

```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_internet.U 1 2006-08-24 12:32:52Z rmanfredi \$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic Licence,

?RCS: as specified in the README file that comes with the distribution.

```

?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: $Log: d_internet.U,v $
?RCS: Revision 3.0.1.1 1993/09/13 16:02:04 ram
?RCS: patch10: most mailers support Internet addresses nowadays (WAD)
?RCS:
?RCS: Revision 3.0 1993/08/18 12:06:24 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:d_internet: Myread Oldconfig Setvar
?MAKE: -pick add $@ %<
?S:d_internet:
?S: This variable conditionally defines the INTERNET symbol, which
?S: indicates to the C program that there is a mailer available
    which
?S: supports internet-style addresses (user@site.domain).
?S:.
?C:INTERNET:
?C: This symbol, if defined, indicates that there is a mailer available
?C: which supports internet-style addresses (user@site.domain).
?C:.
?H:#$d_internet INTERNET /**/
?H:.
?LINT:set d_internet
: check for internet mailer
dflt=y
case "$d_internet" in
"$undef") dflt=n;;
esac
cat <<EOM

```

Most mailers can deliver mail to addresses of the INTERNET persuasion, such as user@host.edu. Some older mailers, however, require the complete path to the destination to be specified in the address.

```

EOM
rp="Does your mailer understand INTERNET addresses?"
./myread
case "$ans" in
y*) val="$define";;
*) val="$undef";;
esac
set d_internet
eval $setvar

```

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/d_internet.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1999 Jarkko Hietaniemi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 3.0.

?RCS:

?MAKE:siteman1dir siteman1direxp installsiteman1dir: Getfile \

Setprefixvar prefix siteprefix man1dir sed

?MAKE: -pick add \$@ %<

?Y:TOP

?D:siteman1dir="

?S:siteman1dir:

?S: This variable contains the name of the directory in which site-specific

?S: manual source pages are to be put. It is the responsibility of the

?S: Makefile.SH to get the value of this into the proper command.

?S: You must be prepared to do the ~name expansion yourself.

?S: The standard distribution will put nothing in this directory.

?S: After perl

has been installed, users may install their own local

?S: man1 pages in this directory with

?S: MakeMaker Makefile.PL

?S: or equivalent. See INSTALL for details.

?S:.

?D:siteman1direxp="

?S:siteman1direxp:

?S: This variable is the same as the siteman1dir variable, but is filename

?S: expanded at configuration time, for convenient use in makefiles.

?S:.

?D:installsiteman1dir="

?S:installsiteman1dir:

?S: This variable is really the same as siteman1direxp, unless you are using

?S: AFS in which case it points to the read/write location whereas

?S: man1direxp only points to the read-only access location. For extra

?S: portability, you should only use this variable within your makefiles.

?S:.

?LINT:change prefixvar

?LINT:set installsiteman1dir

?LINT:set siteman1dir

?LINT:set siteman1direxp

: determine where add-on manual pages go

```

case "$siteman1dir" in
") dflt=`echo $man1dir | $sed "s#^$prefix#$siteprefix#"` ;;
*) dflt=$siteman1dir ;;
esac
case "$dflt" in
"|' ') dflt=none ;;
esac
fn=dn+~
rp='Pathname
where the site-specific manual pages should be installed?'
./getfile
prefixvar=siteman1dir
./setprefixvar

```

Found in path(s):

```

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/installdirs/siteman1dir.U

```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: AAAAA.U 1 2006-08-24 12:32:52Z rmanfredi \$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic Licence,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic Licence; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: AAAAA.U,v \$

?RCS: Revision 3.0.1.4 1994/06/20 06:50:26 ram

?RCS: patch30: changes from Jarkko Hietaniemi are tagged with JHI

?RCS:

?RCS: Revision 3.0.1.3 1994/05/06 14:01:39 ram

?RCS: patch23: initials for Wayne Davison are now WED

?RCS: patch23: added initials for new unit contributor Andy Dougherty

?RCS:

?RCS: Revision 3.0.1.2 1994/01/24 14:01:09 ram

?RCS: patch16: make metalint shut up on special unit definition for All target

?RCS:

?RCS: Revision

3.0.1.1 1993/09/13 15:43:57 ram

?RCS: patch10: documents initials used for Wayne Davison's contributions

?RCS:

?RCS: Revision 3.0 1993/08/18 12:04:44 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?X:

?X: The purpose of this file is to supply the head of the Makefile created
?X: by metaconfig. For this reason it must be first in alphabetical order.
?X: The leading '+' in front of the unit name is a hint for metalint, since
?X: the use of that special unit name as a "made" unit is legitimate here.
?X:
?MAKE:+All: Finish
?X:
?X: Throughout the units, the following initials are used to identify comments:
?X:
?X: HMS: Harlan Stenn
?X: RAM: Raphael Manfredi
?X: WED: Wayne Davison (was WAD by mistake--RAM)
?X: ADO: Andy Dougherty
?X: JHI: Jarkko Hietaniemi
?X:
?X: Agreed, this is a weird place to document it, but I couldn't find a better
?X: place to do so. I've bet on the curiosity of users, who would probably
?X: want to know what's in this strangely-named file--RAM.

Found

in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/AAAAA.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_getpwuid_r.U,v 0RCS:
?RCS: Copyright (c) 2002,2003 Jarkko Hietaniemi
?RCS:
?RCS: You may distribute under the terms of either the GNU General Public
?RCS: License or the Artistic License, as specified in the README file.
?RCS:
?RCS: Generated by the reentr.pl from the Perl 5.8 distribution.
?RCS:
?MAKE:d_getpwuid_r getpwuid_r_proto: Inlibc Protochk Hasproto i_systypes \
usethreads i_pwd extern_C
?MAKE: -pick add \$@ %<
?S:d_getpwuid_r:
?S: This variable conditionally defines the HAS_GETPWUID_R symbol,
?S: which indicates to the C program that the getpwuid_r()
?S: routine is available.
?S:.
?S:getpwuid_r_proto:
?S: This variable encodes the prototype of getpwuid_r.
?S: It is zero if d_getpwuid_r is undef, and one of the
?S: REENTRANT_PROTO_T_ABC macros of reentr.h if d_getpwuid_r
?S: is defined.
?S:.
?C:HAS_GETPWUID_R:

```

?C: This symbol, if defined, indicates that the getpwuid_r routine
?C: is available to
getpwuid re-entrantly.
?C:.
?C:GETPWUID_R_PROTO:
?C: This symbol encodes the prototype of getpwuid_r.
?C: It is zero if d_getpwuid_r is undef, and one of the
?C: REENTRANT_PROTO_T_ABC macros of reentr.h if d_getpwuid_r
?C: is defined.
?C:.
?H:#$d_getpwuid_r HAS_GETPWUID_R /**/
?H:#define GETPWUID_R_PROTO $getpwuid_r_proto /**/
?H:.
?T:try hdrs d_getpwuid_r_proto
: see if getpwuid_r exists
set getpwuid_r d_getpwuid_r
eval $inlibc
case "$d_getpwuid_r" in
"$define")
hdrs="$i_systypes sys/types.h define stdio.h $i_pwd pwd.h"
case "$d_getpwuid_r_proto:$usetthreads" in
":define") d_getpwuid_r_proto=define
set d_getpwuid_r_proto getpwuid_r $hdrs
eval $hasproto ;;
*) ;;
esac
case "$d_getpwuid_r_proto" in
define)
case "$getpwuid_r_proto" in
"|0) try='int getpwuid_r(uid_t, struct passwd*, char*, size_t, struct passwd**);'
./protochk "$extern_C $try" $hdrs && getpwuid_r_proto=I_TSBWR ;;
esac
case "$getpwuid_r_proto" in
"|0) try='int getpwuid_r(uid_t, struct passwd*, char*,
int, struct passwd**);'
./protochk "$extern_C $try" $hdrs && getpwuid_r_proto=I_TSBIR ;;
esac
case "$getpwuid_r_proto" in
"|0) try='int getpwuid_r(uid_t, struct passwd*, char*, int);'
./protochk "$extern_C $try" $hdrs && getpwuid_r_proto=I_TSBI ;;
esac
case "$getpwuid_r_proto" in
"|0) try='struct passwd* getpwuid_r(uid_t, struct passwd*, char*, int);'
./protochk "$extern_C $try" $hdrs && getpwuid_r_proto=S_TSBI ;;
esac
case "$getpwuid_r_proto" in
"|0) d_getpwuid_r=undef
getpwuid_r_proto=0

```

```

echo "Disabling getpwuid_r, cannot determine prototype." >&4 ;;
*) case "$getpwuid_r_proto" in
REENTRANT_PROTO*) ;;
*) getpwuid_r_proto="REENTRANT_PROTO_${getpwuid_r_proto}" ;;
esac
echo "Prototype: $try" ;;
esac
;;
*) case "$usetthreads" in
define) echo "getpwuid_r has no prototype, not using it." >&4 ;;
esac
d_getpwuid_r=undef
getpwuid_r_proto=0
;;
esac
;;
*) getpwuid_r_proto=0
;;
esac

```

Found in path(s):

```

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/threads/d_getpwuid_r.U

```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: Getfile.U 1 2006-08-24 12:32:52Z rmanfredi \$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic Licence,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic Licence; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: Getfile.U,v \$

?RCS: Revision 3.0.1.7 1997/02/28 15:01:06 ram

?RCS: patch61: getfile script now begins with "startsh"

?RCS:

?RCS: Revision 3.0.1.6 1995/02/15 14:11:00 ram

?RCS: patch51: was not working if ~'s allowed with d_portable on (WED)

?RCS:

?RCS: Revision 3.0.1.5 1995/01/11 15:11:25 ram

?RCS: patch45: added support for escaping answers to skip various checks

?RCS: patch45: modified message issued after file expansion

?RCS:

?RCS: Revision

3.0.1.4 1994/10/29 15:53:19 ram

?RCS: patch36: added ?F: line for metalint file checking

?RCS:

?RCS: Revision 3.0.1.3 1994/05/06 14:23:36 ram

?RCS: patch23: getfile could be confused by file name in "locate" requests

?RCS: patch23: new 'p' directive to assume file is in people's path (WED)

?RCS:

?RCS: Revision 3.0.1.2 1994/01/24 14:01:31 ram

?RCS: patch16: added metalint hint on changed 'ans' variable

?RCS:

?RCS: Revision 3.0.1.1 1993/09/13 15:46:27 ram

?RCS: patch10: minor format problems and misspellings fixed

?RCS: patch10: now performs from package dir and not from UU subdir

?RCS:

?RCS: Revision 3.0 1993/08/18 12:04:56 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?X:

?X: This unit produces a bit of shell code that must be dotted in in order

?X: to get a file name and make some sanity checks. Optionally, a ~name

?X: expansion is performed.

?X:

?X: To use this unit, \$rp and \$dflt must hold the question and the

?X: default answer, which will be passed as-is

to the myread script.

?X: The \$fn variable must hold the file type (f or d, for file/directory).

?X: If \$gfpth is set to a list of space-separated list of directories,

?X: those are prefixes for the filename. Unless \$gfpthkeep is set to 'y',

?X: gfpth is cleared on return from Getfile.

?X:

?X: If is is followed by a ~, then ~name substitution will occur. Upon return,

?X: \$ans is set with the filename value. If a / is specified, then only a full

?X: path name is accepted (but ~ substitution occurs before, if needed). The

?X: expanded path name is returned in that case.

?X:

?X: If a + is specified, the existence checks are skipped. This usually means

?X: the file/directory is under the full control of the program.

?X:

?X: If the 'n' (none) type is used, then the user may answer none.

?X: The 'e' (expand) switch may be used to bypass d_portable, expanding ~name.

?X:

?X: If the 'l' (locate) type is used, then it must end with a ':' and then a

?X: file name. If the answer is a directory,

the file name will be appended

?X: before testing for file existence. This is useful in locate-style

?X: questions like "where is the active file?". In that case, one should

?X: use:

?X:

```

?X: dflt=~news/lib'
?X: fn=l~:active'
?X: rp='Where is the active file?'
?X: . ./getfile
?X: active="$ans"
?X:
?X: If the 'p' (path) letter is specified along with 'l', then an answer
?X: without a leading / will be expected to be found in everyone's path.
?X:
?X: It is also possible to include a comma-separated list of items within
?X: parentheses to specify which items should be accepted as-is with no
?X: further checks. This is useful when for instance a full path is expected
?X: but the user may escape out via "magical" answers.
?X:
?X: If the answer to the question is 'none', then the existence checks are
?X: skipped and the empty string is returned.
?X:
?MAKE:Getfile: d_portable contains startsh Myread Filexp tr trnl
?MAKE: -pick add $@ %<
?V:ansexp:fn gfpth gfpthkeep
?F:./getfile
?T:tilde
type what orig_rp orig_dflt fullpath already redo skip none_ok \
value exp_file nopath_ok loc_file fp pf dir direxp
?LINT:change ans
?LINT:change gfpth
: now set up to get a file name
cat <<EOS >getfile
$startsh
EOS
cat <<'EOSC' >>getfile
tilde="
fullpath="
already="
skip="
none_ok="
exp_file="
nopath_ok="
orig_rp="$rp"
orig_dflt="$dflt"
case "$gfpth" in
") gfpth='.' ;;
esac

?X: Begin by stripping out any (...) grouping.
case "$fn" in
*\(*)
: getfile will accept an answer from the comma-separated list

```

: enclosed in parentheses even if it does not meet other criteria.

```
expr "$fn" : '.*\(\(.*\)).*' | $str '$' $trnl >getfile.ok
```

```
fn=`echo $fn | sed 's/(.*)//`
```

```
::
```

```
esac
```

?X: Catch up 'locate' requests early, so that we may strip the file name

?X: before looking at the one-letter commands, in case the file name contains

?X: one of them. Reported by Wayne Davison <davison@borland.com>.

```
case "$fn" in
```

```
 *.* )
```

```
  loc_file=`expr $fn : '.*:\(.*\)`
```

```
  fn=`expr $fn : '\(.*\):.*`
```

```
::
```

```
esac
```

```
case
```

```
 "$fn" in
```

```
 *~*) tilde=true;;
```

```
esac
```

```
case "$fn" in
```

```
 */*) fullpath=true;;
```

```
esac
```

```
case "$fn" in
```

```
 *+*) skip=true;;
```

```
esac
```

```
case "$fn" in
```

```
 *n*) none_ok=true;;
```

```
esac
```

```
case "$fn" in
```

```
 *e*) exp_file=true;;
```

```
esac
```

```
case "$fn" in
```

```
 *p*) nopath_ok=true;;
```

```
esac
```

```
case "$fn" in
```

```
 *f*) type='File';;
```

```
 *d*) type='Directory';;
```

```
 *l*) type='Locate';;
```

```
esac
```

```
what="$stype"
```

```
case "$what" in
```

```
 Locate) what='File';;
```

```
esac
```

```
case "$exp_file" in
```

```

")
case "$d_portable" in
"$define") ;;
*) exp_file=true;;
esac
;;
esac

cd ..
while test "$type"; do
redo="
rp="$orig_rp"
dflt="$orig_dflt"
case "$tilde" in
true) rp="$rp (~name ok)";;
esac
. UU/myread
?X: check for allowed escape sequence which may be accepted verbatim.
if test -f UU/getfile.ok && \
$contains "^$ans\$" UU/getfile.ok >/dev/null 2>&1
then
value="$ans"
ansexp="$ans"
break
fi
case "$ans" in
none)
value="
ansexp="
case "$none_ok" in
true) type="";;
esac
;;
*)
case "$tilde" in
") value="$ans"
ansexp="$ans";;
*)
value=`UU/filexp $ans`
case
$? in
0)
if test "$ans" != "$value"; then
echo "(That expands to $value on this system.)"
fi
;;
*) value="$ans";;
esac

```

```

ansexp="$value"
case "$sexp_file" in
") value="$ans";;
esac
;;
esac
case "$fullpath" in
true)
?X: Perform all the checks on ansexp and not value since when d_portable
?X: is defined, the original un-expanded answer which is stored in value
?X: would lead to "non-existent" error messages whilst ansexp has been
?X: properly expanded. -- Fixed by Jan.Djarv@sa.erisoft.se (Jan Djarv)
?X: Always expand ~user if '/' was requested
case "$sansexp" in
/*) value="$sansexp" ;;
?X: Allow for c:/some/path
[a-zA-Z]:/*) value="$sansexp" ;;
*)
redo=true
case "$already" in
true)
echo "I shall only accept a full path name, as in /bin/lis." >&4
echo "Use a ! shell escape if you wish to check pathnames." >&4
;;
*)
echo "Please give a full path name, starting with slash." >&4
case "$stilde"
in
true)
echo "Note that using ~name is ok provided it expands well." >&4
already=true
;;
esac
esac
;;
esac
;;
esac
case "$redo" in
")
case "$styp" in
File)
for fp in $gfpth; do
if test "X$fp" = X.; then
pf="$sansexp"
else
pf="$fp/$sansexp"
fi

```

```

if test -f "$pf"; then
    type="
elif test -r "$pf" || (test -h "$pf") >/dev/null 2>&1
then
    echo "($value is not a plain file, but that's ok.)"
    type="
fi
if test X"$type" = X; then
    value="$pf"
    break
fi
done
;;
Directory)
for fp in $gfpth; do
if test "X$fp" = X.; then
    dir="$ans"
    direxp="$ansexp"
else
    dir="$fp/$ansexp"
    direxp="$fp/$ansexp"
fi
if test -d "$direxp"; then
    type="
    value="$dir"
    break
fi
done
;;
Locate)
if test -d "$ansexp"; then
    echo "(Looking for $loc_file in directory
$value.)"
    value="$value/$loc_file"
    ansexp="$ansexp/$loc_file"
fi
if test -f "$ansexp"; then
    type="
fi
case "$nopath_ok" in
true) case "$value" in
*/*) ;;
*) echo "Assuming $value will be in people's path."
    type="
;;
esac
;;
esac

```

```

;;
esac

case "$skip" in
true) type=";
esac

case "$type" in
") ;;
*)
if test "$fastread" = yes; then
dflt=y
else
dflt=n
fi
rp="$what $value doesn't exist. Use that name anyway?"
. UU/myread
dflt="
case "$ans" in
y*) type=";
*) echo " ";
esac
;;
esac
;;
esac
;;
esac
done
cd UU
ans="$value"
rp="$orig_rp"
dflt="$orig_dflt"
rm -f getfile.ok
test "X$gfpthkeep" != Xy && gfpth=""
EOSC

```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/Getfile.U
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1998 Jarkko Hietaniemi

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

```

?RCS:
?MAKE:usemultiplicity: useithreads Myread Oldconfig Setvar
?MAKE: -pick add $@ %<
?Y:TOP
?S:usemultiplicity:
?S: This variable conditionally defines the MULTIPLICITY symbol,
?S: and indicates that Perl should be built to use multiplicity.
?S:.
?C:MULTIPLICITY:
?C: This symbol, if defined, indicates that Perl should
?C: be built to use multiplicity.
?C:.
?H:?%<:#ifndef MULTIPLICITY
?H:?%<:#$usemultiplicity MULTIPLICITY /**/
?H:?%<:#endif
?H:.
?LINT:set usemultiplicity
?INIT:: set usemultiplicity on the Configure command line to enable multiplicity.
: Check if multiplicity is required
?X: We should really have some explanatory text here, and some
?X: automatic setting of sensible defaults.
cat <<EOM

```

Perl

can be built so that multiple Perl interpreters can coexist
within the same Perl executable.

EOM

```

case "$useithreads" in
$define)
cat <<EOM
This multiple interpreter support is required for interpreter-based threads.
EOM
val="$define"
;;
*) case "$usemultiplicity" in
$define|true|[yY]*) dflt='y';;
*) dflt='n';;
esac
echo " "
echo "If this doesn't make any sense to you, just accept the default '$dflt'."
rp='Build Perl for multiplicity?'
./myread
case "$ans" in
y|Y) val="$define" ;;
*) val="$undef" ;;
esac
;;

```

```
esac
set usemultiplicity
eval $setvar
```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/perl/usemultiplicity.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: d_msgget.U 1 2006-08-24 12:32:52Z rmanfredi $
```

```
?RCS:
```

```
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
```

```
?RCS:
```

```
?RCS: You may redistribute only under the terms of the Artistic Licence,
```

```
?RCS: as specified in the README file that comes with the distribution.
```

```
?RCS: You may reuse parts of this distribution only within the terms of
```

```
?RCS: that same Artistic Licence; a copy of which may be found at the root
```

```
?RCS: of the source tree for dist 4.0.
```

```
?RCS:
```

```
?RCS: $Log: d_msgget.U,v $
```

```
?RCS: Revision 3.0 1993/08/18 12:06:39 ram
```

```
?RCS: Baseline for dist 3.0 netwide release.
```

```
?RCS:
```

```
?MAKE:d_msgget: Inlibc
```

```
?MAKE: -pick add $@ %<
```

```
?S:d_msgget:
```

```
?S: This variable conditionally defines the HAS_MSGGET symbol, which
```

```
?S: indicates to the C program that the msgget() routine is available.
```

```
?S:.
```

```
?C:HAS_MSGGET:
```

```
?C: This symbol, if defined, indicates that the msgget() routine is
```

```
?C: available to get a new message queue.
```

```
?C:.
```

```
?H:#$d_msgget
```

```
HAS_MSGGET /**/
```

```
?H:.
```

```
?LINT:set d_msgget
```

```
: see if msgget exists
```

```
set msgget d_msgget
```

```
eval $inlibc
```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/d_msgget.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: d_dosuid.U 1 2006-08-24 12:32:52Z rmanfredi $
```

```
?RCS:
```

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: Tye McQueen <tye@metronet.com> added safe setuid script checks.

?RCS:

?RCS: \$Log: d_dosuid.U,v \$

?RCS: Revision 3.0.1.2 1997/02/28 15:33:03 ram

?RCS: patch61: moved unit to TOP via a ?Y: layout directive

?RCS: patch61: tell them /dev/fd is not about floppy disks

?RCS:

?RCS: Revision 3.0.1.1 1994/10/29 16:12:08 ram

?RCS: patch36: added checks for secure setuid scripts (Tye McQueen)

?RCS:

?RCS: Revision 3.0 1993/08/18 12:05:55 ram

?RCS: Baseline for
dist 3.0 netwide release.

?RCS:

?MAKE:d_dosuid d_suidsaf: cat contains ls rm test Myread Setvar \
Oldconfig Guess package hint patchlevel

?MAKE: -pick add \$@ %<

?S:d_suidsaf:

?S: This variable conditionally defines SETUID_SCRIPTS_ARE_SECURE_NOW
?S: if setuid scripts can be secure. This test looks in /dev/fd/.

?S:.

?S:d_dosuid:

?S: This variable conditionally defines the symbol DOSUID, which
?S: tells the C program that it should insert setuid emulation code
?S: on hosts which have setuid #! scripts disabled.

?S:.

?C:SETUID_SCRIPTS_ARE_SECURE_NOW:

?C: This symbol, if defined, indicates that the bug that prevents
?C: setuid scripts from being secure is not present in this kernel.

?C:.

?C:DOSUID:

?C: This symbol, if defined, indicates that the C program should
?C: check the script that it is executing for setuid/setgid bits, and
?C: attempt to emulate setuid/setgid on systems that have disabled
?C: setuid #! scripts because the kernel can't do it securely.

?C: It is up to the package
designer to make sure that this emulation
?C: is done securely. Among other things, it should do an fstat on
?C: the script it just opened to make sure it really is a setuid/setgid
?C: script, it should make sure the arguments passed correspond exactly

```

?C: to the argument on the #! line, and it should not trust any
?C: subprocesses to which it must pass the filename rather than the
?C: file descriptor of the script to be executed.
?C:.
?H:#$d_suidsaf SETUID_SCRIPTS_ARE_SECURE_NOW /***/
?H:#$d_dosuid DOSUID /***/
?H:.
?Y:TOP
?F:!reflect
?LINT: set d_suidsaf
: see if setuid scripts can be secure
$cat <<EOM

```

Some kernels have a bug that prevents setuid #! scripts from being secure. Some sites have disabled setuid #! scripts because of this.

First let's decide if your kernel supports secure setuid #! scripts. (If setuid #! scripts would be secure but have been disabled anyway, don't say that they are secure if asked.)

EOM

```

val="$undef"
if $test -d /dev/fd; then
echo "#!$ls" >reflect
chmod
+x,u+s reflect
./reflect >flect 2>&1
if $contains "/dev/fd" flect >/dev/null; then
echo "Congratulations, your kernel has secure setuid scripts!" >&4
val="$define"
else
$cat <<EOM

```

If you are not sure if they are secure, I can check but I'll need a username and password different from the one you are using right now. If you don't have such a username or don't want me to test, simply enter 'none'.

EOM

```

rp='Other username to test security of setuid scripts with?'
dflt='none'
. ./myread
case "$ans" in
n|none)
case "$d_suidsaf" in
") echo "I'll assume setuid scripts are *not* secure." >&4
dflt=n;;
"$undef")

```

```

echo "Well, the $hint value is *not* secure." >&4
dflt=n;;
*) echo "Well, the $hint value *is* secure." >&4
dflt=y;;
esac
;;
*)
$rm -f reflect flect
echo "#!$ls" >reflect
chmod +x,u+s reflect
echo >flect
chmod a+w flect
echo "'su" will (probably) prompt you for "'$ans's password."
su $ans -c './reflect
>flect'
if $contains "/dev/fd" flect >/dev/null; then
echo "Okay, it looks like setuid scripts are secure." >&4
dflt=y
else
echo "I don't think setuid scripts are secure." >&4
dflt=n
fi
;;
esac
rp='Does your kernel have *secure* setuid scripts?'
./myread
case "$ans" in
[yY]*) val="$define";;
*) val="$undef";;
esac
fi
else
echo "I don't think setuid scripts are secure (no /dev/fd directory)." >&4
echo "(That's for file descriptors, not floppy disks.)"
val="$undef"
fi
set d_suidsafef
eval $setvar

$rm -f reflect flect

: now see if they want to do setuid emulation
if $test $patchlevel -lt 11; then
echo " "
val="$undef"
case "$d_suidsafef" in
"$define")
val="$undef"

```

```
echo "No need to emulate SUID scripts since they are secure here." >&4
;;
*)
$cat <<EOM
Some systems have disabled setuid scripts, especially systems where
setuid scripts cannot be secure. On systems where setuid scripts have
been disabled, the setuid/setgid bits on scripts are
currently
useless. It is possible for $package to detect those bits and emulate
setuid/setgid in a secure fashion. This emulation will only work if
setuid scripts have been disabled in your kernel.
```

```
EOM
case "$d_dosuid" in
"$define") dflt=y ;;
*) dflt=n ;;
esac
rp="Do you want to do setuid/setgid emulation?"
. ./myread
case "$ans" in
[yY]*) val="$define";;
*) val="$undef";;
esac
;;
esac
set d_dosuid
eval $setvar
else
case "$d_dosuid" in
"$define")
cat >&4 <<EOH
```

SUID emulation has been removed for 5.12
Please re-run Configure without -Dd_dosuid

```
EOH
exit 1;
;;
esac
d_dosuid=undef
fi
```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/modified/d_dosuid.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: d_rusage.U 1 2006-08-24 12:32:52Z rmanfredi $
```

?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: \$Log: d_rusage.U,v \$
?RCS: Revision 3.0 1993/08/18 12:06:57 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?X: We may need to include <sys/resource.h> and <sys/time.h> FIXME
?X:INC: i_sysresrc i_systime
?MAKE:d_rusage: Inlibc
?MAKE: -pick add \$@ %<
?S:d_rusage (d_getrusg):
?S: This variable conditionally defines the HAS_GETRUSAGE symbol, which
?S: indicates that the getrusage() routine exists. The getrusage() routine
?S: supports sub-second accuracy
?S: for process cpu accounting. You may need
?S: to include <sys/resource.h> and <sys/time.h>.
?S:.
?C:HAS_GETRUSAGE (RUSAGE GETRUSAGE):
?C: This symbol, if defined, indicates that the getrusage() routine is
?C: available to get process statistics with a sub-second accuracy.
?C: Inclusion of <sys/resource.h> and <sys/time.h> may be necessary.
?C:.
?H:#\$d_rusage HAS_GETRUSAGE /**/
?H:.
?LINT:set d_rusage
: see if getrusage exists
set getrusage d_rusage
eval \$inlibc

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/d_rusage.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$
?RCS:
?RCS: Copyright (c) 1999 Jarkko Hietaniemi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 3.0.

?RCS:

?MAKE:sitehtml1dir sitehtml1direxp installsitehtml1dir: Getfile \
Setprefixvar prefix siteprefix html1dir sed

?MAKE: -pick add \$@ %<

?Y:TOP

?D:sitehtml1dir="

?S:sitehtml1dir:

?S: This variable contains the name of the directory in which site-specific
?S: html source pages are to be put. It is the responsibility of the
?S: Makefile.SH to get the value of this into the proper command.
?S: You must be prepared to do the ~name expansion yourself.
?S: The standard distribution will put nothing in this directory.
?S: After perl
has been installed, users may install their own local
?S: html pages in this directory with
?S: MakeMaker Makefile.PL
?S: or equivalent. See INSTALL for details.

?S:.

?D:sitehtml1direxp="

?S:sitehtml1direxp:

?S: This variable is the same as the sitehtml1dir variable, but is filename
?S: expanded at configuration time, for convenient use in makefiles.

?S:.

?D:installsitehtml1dir="

?S:installsitehtml1dir:

?S: This variable is really the same as sitehtml1direxp, unless you are using
?S: AFS in which case it points to the read/write location whereas
?S: html1direxp only points to the read-only access location. For extra
?S: portability, you should only use this variable within your makefiles.

?S:.

?LINT:change prefixvar
?LINT:set installsitehtml1dir
?LINT:set sitehtml1dir
?LINT:set sitehtml1direxp
: determine where add-on html pages go
: There is no standard location, so try to copy the previously-selected
: directory structure for the core html pages.
case "\$sitehtml1dir" in
")
dflt=`echo "\$html1dir" | \$sed "s#^\$prefix#\$siteprefix#"` ;;
*) dflt=\$sitehtml1dir ;;
esac
case "\$dflt" in
"| ") dflt=none ;;
esac
fn=dn+~

rp='Pathname where the site-specific html pages should be installed?'

./getfile

prefixvar=sitehtml1dir

./setprefixvar

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/installdirs/sitehtml1dir.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: vendorman3dir.U,v 1.1 1999/07/08 18:32:57 doughera Exp doughera \$

?RCS:

?RCS: Copyright (c) 1999-2000, Andy Dougherty

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 3.0.

?RCS:

?RCS: \$Log: vendorman3dir.U,v \$

?RCS: Revision 1.1 1999/07/08 18:32:57 doughera

?RCS: Initial revision

?RCS:

?MAKE:vendorman3dir vendorman3direxp installvendorman3dir: man3dir Getfile \

Oldconfig Setprefixvar Prefixit test vendorprefix prefix sed

?MAKE: -pick add \$@ %<

?Y:TOP

?S:vendorman3dir:

?S: This variable contains the name of the directory for man3

?S: pages. It may have a ~ on the front.

?S: The standard distribution will put nothing in this directory.

?S: Vendors

who distribute perl may wish to place their own

?S: man3 pages in this directory with

?S: MakeMaker Makefile.PL INSTALLDIRS=vendor

?S: or equivalent. See INSTALL for details.

?S:.

?S:vendorman3direxp:

?S: This variable is the ~name expanded version of vendorman3dir, so that you

?S: may use it directly in Makefiles or shell scripts.

?S:.

?D:installvendorman3dir="

?S:installvendorman3dir:

?S: This variable is really the same as vendorman3direxp but may differ on

?S: those systems using AFS. For extra portability, only this variable

?S: should be used in makefiles.

?S:.

```

?LINT:change prefixvar
?LINT:set installvendorman3dir
: Set the vendorman3dir variables
case "$vendorprefix" in
") vendorman3dir="
vendorman3direxp="
;;
*) : determine where vendor-supplied module manual pages go.
case "$vendorman3dir" in
") dflt=`echo "$man3dir" | $sed "s#^$prefix#$vendorprefix#"` ;;
*) dflt=$vendorman3dir ;;
esac
case "$dflt" in
"|' ') dflt=none ;;
esac
fn=nd~+
rp='Pathname
for the vendor-supplied manual section 3 pages?'
./getfile
vendorman3dir="$ans"
vendorman3direxp="$ansexp"
;;
esac
: Use ' ' for none so value is preserved next time through Configure
$test X"$vendorman3dir" = "X" && vendorman3dir=' '
prefixvar=vendorman3dir
./installprefix

```

Found in path(s):

```

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/installdirs/vendorman3dir.U

```

No license file was found, but licenses were detected in source scan.

```

?RCS: $Id: Hasproto.U $

```

```

?RCS:

```

```

?RCS: Copyright (c) 1998 Andy Dougherty

```

```

?RCS:

```

```

?RCS: You may distribute under the terms of either the GNU General Public

```

```

?RCS: License or the Artistic License, as specified in the README file.

```

```

?RCS:

```

```

?X: This unit generates a $hasproto string that is used internally

```

```

?X: by Configure to check if this system has a prototype for a

```

```

?X: particular function

```

```

?X:

```

```

?X: To use it, say something like:

```

```

?X: set d_getnetent_proto getnetent $i_netdb netdb.h

```

```

?X: eval $hasproto

```

```

?X: Or, for more complicated sets of headers, do something like

```

```

?X: hdrs="$define sys/types.h
?X: $i_systime sys/time.h
?X: $i_sysselect sys/select.h
?X: $i_netdb netdb.h"
?X: set d_getnetent_proto getnetent $hdrs
?X: eval $hasproto
?X:
?MAKE:Hasproto: Setvar cppstdin cppflags cppminus contains rm_try test
?MAKE: -pick add $@ %<
?T:func varname
?F:!try.c
?V:hasproto
: Define hasproto macro for Configure internal use
hasproto='varname=$1;
func=$2; shift; shift;
while $test $# -ge 2; do
case "$1" in
$define) echo "#include <$2>;";
esac ;
shift 2;
done > try.c;
$cppstdin $cppflags $cppminus < try.c > tryout.c 2>/dev/null;
if $contains "$func.*( " tryout.c >/dev/null 2>&1; then
echo "$func() prototype found.";
val="$define";
else
echo "$func() prototype NOT found.";
val="$undef";
fi;
set $varname;
eval $setvar;
$rm_try tryout.c'

```

Found in path(s):

```

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/protos/Hasproto.U

```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

```

?RCS: $Log: d_csh.U,v $
?RCS: Revision 3.0.1.1 1997/02/28 15:32:18 ram
?RCS: patch61: added full_csh to preserve the full path even when portable
?RCS:
?RCS: Revision 3.0 1993/08/18 12:05:53 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:d_csh full_csh: csh Setvar
?MAKE: -pick add $@ %<
?S:d_csh:
?S: This variable conditionally defines the CSH symbol, which
?S: indicates to the C program that the C-shell exists.
?S:.
?S:full_csh:
?S: This variable contains the full pathname to 'csh', whether
or
?S: not the user has specified 'portability'. This is only used
?S: in the compiled C program, and we assume that all systems which
?S: can share this executable will have the same full pathname to
?S: 'csh.'
?S:.
?X: Yes, I know about the C symbol PORTABLE, but I think csh
?X: is unlikely to move, and I'm too lazy to add all the
?X: #ifdef PORTABLE sections to the perl source.
?X:
?C:HAS_CSH:
?C: This symbol, if defined, indicates that the C-shell exists.
?C:.
?C:CSH:
?C: This symbol, if defined, contains the full pathname of csh.
?C:.
?X: Previously, I just did $d_csh CSH "$full_csh", but that caused
?X: problems on VMS where the config.sh extraction program changes
?X: $undef to a real cpp undef, and they then had #undef CSH ""
?X: which the compiler didn't like. It's easy to work around this,
?X: so I did. --AD 3/1998.
?X: And we don't want to define CSH if !HAS_CSH, but we don't want
?X: those lines in config.h if they don't need CSH, so protect with ?CSH
?X: and not
?%<. --RAM, 15/02/2004
?H:?%<:#$d_csh HAS_CSH /**/
?H:?CSH:#ifdef HAS_CSH
?H:?CSH:#define CSH "$full_csh" /**/
?H:?CSH:#endif
?H:.
?LINT:set d_csh
: get csh whereabouts
case "$csh" in

```

```
'csh') val="$undef" ;;
*) val="$define" ;;
esac
set d_csh
eval $setvar
: Respect a hint or command line value for full_csh.
case "$full_csh" in
") full_csh=$csh ;;
esac
```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/modified/d_csh.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: d_NOFILE.U,v 3.0.1.1 1994/10/29 16:08:38 ram Exp $
?RCS:
?RCS: Copyright (c) 1991-1993, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 3.0.
?RCS:
?RCS: $Log: d_NOFILE.U,v $
?RCS: Revision 3.0.1.1 1994/10/29 16:08:38 ram
?RCS: patch36: added ?F: line for metalint file checking
?RCS:
?RCS: Revision 3.0 1993/08/18 12:05:39 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:nofile d_gettblsz tablesize: Compile Myread Guess cat \
test rm Csym +cc +cflags +optimize +ldflags +libs
?MAKE: -pick add $@ %<
?S:nofile:
?S: This variable contains the number of file descriptors available to the
?S: process.
?S:.
?S:d_gettblsz:
?S: This
variable conditionally handles remapping of the getdtablesize()
?S: subroutine to ulimit(4,0), or the NOFILE manifest constant.
?S:.
?S:tablesize:
?S: This variable contains either the 'NOFILE' constant or 'ulimit(4, 0L)'
?S: and is used as the remapped value for the getdtablesize() macro.
?S:.
```

```

?C:getdtablesize:
?C: This catches use of the getdtablesize() subroutine, and remaps it
?C: to either ulimit(4,0) or NOFILE, if getdtablesize() isn't available.
?C:.
?C:VAL_NOFILE:
?C: This symbol contains the number of file descriptors available to the
?C: process, as determined at configuration time. Unless a static constant
?C: is needed, you should rely on getdtablesize() to obtain that number.
?C:.
?H:#$d_gettblsz getdtablesize() $tablesize /**/
?H:#define VAL_NOFILE $nofile /* Number of file descriptors */
?H:.
?F:!nofile
?T:d_ulimit4 val
: see if getdtablesize exists
echo " "
?X: Revert logical value (d_gettblsz is undef if getdtablesize is present)
case "$d_gettblsz"
in
$define) d_gettblsz="$undef";;
$undef) d_gettblsz="$define";;
esac
if set getdtablesize val -f d_gettblsz; eval $csym; $val; then
echo 'getdtablesize() found.' >&4
d_gettblsz="$undef"
tablesize="
@if VAL_NOFILE || nofile
$cat >nofile.c <<'EOCP'
#include <stdio.h>
int main()
{
printf("%d\n", getdtablesize());
}
EOCP
nofile="
set nofile
if eval $compile_ok; then
nofile=`./nofile 2>/dev/null`
fi
if $test "$nofile"; then
echo "(You have $nofile file descriptors available per process.)"
else
nofile='20'
if ./bsd; then
nofile='64'
fi
echo "(Hmm... Let's say you have $nofile file descriptors available.)"
fi

```

```

@end
else
echo 'getdtablesize() NOT found...' >&4
if set ulimit val -f; eval $csym; $val; then
echo 'Maybe ulimit(4,0) will work...'
$cat >nofile.c <<'EOCP'
#include <stdio.h>
#ifdef GETPARAM_H
#include <sys/param.h>
#endif
int main()
{
printf("%d %d\n",
#ifdef NOFILE
NOFILE,
#else
0,
#endif
ulimit(4,0));
exit(0);
}
EOCP
if $cc $optimize
$ccflags -DGETPARAM_H $ldflags -o nofile nofile.c $libs >/dev/null 2>&1 \
|| $cc $optimize $ccflags $ldflags -o nofile nofile.c $libs >/dev/null 2>&1 ; then
set `./nofile`
d_gettblsz=$1
d_ulimit4=$2
if $test "$d_ulimit4" -lt 0; then
echo "Your ulimit() call doesn't tell me what I want to know."
echo "We'll just use NOFILE in this case."
nofile=$d_gettblsz
d_gettblsz="$define"
tablesize='NOFILE'
else
if $test "$d_gettblsz" -gt 0; then
echo "Your system defines NOFILE to be $d_gettblsz, and" >&4
else
echo "I had trouble getting NOFILE from your system, but" >&4
fi
echo "ulimit returns $d_ulimit4 as the number of available file descriptors." >&4
dflt='y';
echo " "
rp='Should I use ulimit to get the number of available file descriptors?'
./myread
case "$ans" in
y*)
nofile=$d_ulimit4

```

```

d_gettblsz="$define"
tablesize='ulimit(4, 0L)'
echo "Using ulimit(4,0)."
;;
*)
nofile=$d_gettblsz
d_gettblsz="$define"
tablesize='NOFILE'
echo
"Using NOFILE."
;;
esac
fi
else
echo "Strange, I couldn't get my test program to compile."
echo "We'll just use NOFILE in this case."
d_gettblsz="$define"
tablesize='NOFILE'
nofile=""
fi
else
echo 'Using NOFILE instead.'
d_gettblsz="$define"
tablesize='NOFILE'
nofile=""
fi
fi
@if VAL_NOFILE || nofile
case "$nofile" in
")
$cat >nofile.c <<'EOCP'
#include <stdio.h>
#ifdef GETPARAM_H
#include <sys/param.h>
#endif
int main()
{
printf("%d\n",
#ifdef NOFILE
NOFILE,
#else
0,
#endif
);
exit(0);
}
EOCP
if $cc $ccflags -DGETPARAM_H nofile.c -o nofile $libs >/dev/null 2>&1 \

```

```

|| $cc $ccflags nofile.c -o nofile $libs >/dev/null 2>&1 ; then
nofile=`./nofile 2>/dev/null`
fi
if $test "$nofile"; then
echo "(You have $nofile file descriptors available per process.)"
else
nofile='20'
if ./bsd; then
nofile='64'
fi
echo "(Hmm... Let's say you have $nofile file descriptors
available.)"
fi
;;
esac
@end
$rm -f nofile*

```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/compline/d_NOFILE.U
```

No license file was found, but licenses were detected in source scan.

?RCS: You may redistribute only under the terms of the Artistic Licence,

?RCS: as specified in the README file that comes with the distribution.

?RCS:

?MAKE:i_fenv: Inhdr

?MAKE: -pick add \$@ %<

?S:i_fenv:

?S: This variable conditionally defines the I_FENV symbol, which

?S: indicates to the C program that <fenv.h> exists and should

?S: be included.

?S:.

?C:I_FENV:

?C: This symbol, if defined, indicates to the C program that it should

?C: include <fenv.h> to get the floating point environment definitions.

?C:.

?H:#\$i_fenv I_FENV /**/

?H:.

?LINT:set i_fenv

: see if this is a fenv.h system

set fenv.h i_fenv

eval \$inhdr

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/perl/i_fenv.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: i_poll.U,v $
?RCS:
?RCS: Copyright (c) 2001 Jarkko Hietaniemi
?RCS:
?RCS: You may distribute under the terms of either the GNU General Public
?RCS: License or the Artistic License, as specified in the README file.
?RCS:
?MAKE:i_langinfo: Inhdr Hasfield
?MAKE:-pick add $@ %<
?S:i_langinfo:
?S: This variable conditionally defines the I_LANGINFO symbol,
?S: and indicates whether a C program should include <langinfo.h>.
?S:.
?C:I_LANGINFO:
?C: This symbol, if defined, indicates that <langinfo.h> exists and
?C: should be included.
?C:.
?H:#$i_langinfo I_LANGINFO /**/
?H:.
?LINT:set i_langinfo
: see if this is a langinfo.h system
set langinfo.h i_langinfo
eval $inhdr
```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/perl/i_langinfo.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id$
?RCS:
?RCS: Copyright (c) 2000 Jarkko Hietaniemi
?RCS:
?RCS: You may distribute under the terms of either the GNU General Public
?RCS: License or the Artistic License, as specified in the README file.
?RCS:
?MAKE:d_getrlimit: Inlibc
?MAKE:-pick add $@ %<
?S:d_getrlimit:
?S: This variable conditionally defines the HAS_GETRLIMIT symbol, which
?S: indicates to the C program that the getrlimit() routine is available.
?S:.
?C:HAS_GETRLIMIT:
?C: This symbol, if defined, indicates that the getrlimit routine is
?C: available to get process resource limits.
?C:.
```

?H:#\$d_getrlimit HAS_GETRLIMIT /**/

?H:.

?LINT:set d_getrlimit

: see if getrlimit exists

set getrlimit d_getrlimit

eval \$inlibc

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_getrlimit.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: libnm.U 1 2006-08-24 12:32:52Z rmanfredi \$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic Licence,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic Licence; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: libnm.U,v \$

?RCS: Revision 3.0.1.1 1997/02/28 16:08:26 ram

?RCS: patch61: replaced .a with \$_a all over the place

?RCS:

?RCS: Revision 3.0 1993/08/18 12:09:01 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?MAKE:libnm: test Loc libpth _a

?MAKE: -pick add \$@ %<

?S:libnm:

?S: This variable contains the argument to pass to the loader in order

?S: to get the new math library routines. If there is no new math

?S: library, it is null.

?S:.

?T:ans

?O:

use libswanted='-lnm' instead (see libs.U).

: see if we should include -lnm

echo " "

if \$test -r /usr/lib/libnm\$_a || \$test -r /usr/local/lib/libnm\$_a ; then

echo "New math library found." >&4

libnm='-lnm'

else

ans=`./loc libnm\$_a x \$libpth`

case "\$ans" in

x)

```

echo "No nm library found--the normal math library will have to do." >&4
libnm=""
;;
*)
echo "New math library found in $ans." >&4
libnm="$ans"
;;
esac
fi

```

Found in path(s):

```

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/libnm.U

```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: d_socket.U,v \$

?RCS: Revision 3.0.1.2 1997/02/28 15:46:00 ram

?RCS: patch61: replaced .a with \$_a all over the place

?RCS:

?RCS: Revision 3.0.1.1 1994/01/24 14:08:04 ram

?RCS: patch16: can now safely declare private nm_extract in dependencies

?RCS:

?RCS: Revision 3.0 1993/08/18 12:07:26 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?MAKE:d_socket d_oldsock d_sockpair socketlib sockethdr: contains libc \

echo n c nm_opt nm_extract Inlibc Csym _a

?MAKE: -pick add \$@ %<

?S:d_socket:

?S: This

variable conditionally defines HAS_SOCKET, which indicates

?S: that the BSD socket interface is supported.

?S:.

?S:d_sockpair:

?S: This variable conditionally defines the HAS_SOCKETPAIR symbol, which

?S: indicates that the BSD socketpair() is supported.

?S:.

?S:d_oldsock:

?S: This variable conditionally defines the OLDSOCKET symbol, which
?S: indicates that the BSD socket interface is based on 4.1c and not 4.2.
?S:.
?S:socketlib:
?S: This variable has the names of any libraries needed for socket support.
?S:.
?S:sockethdr:
?S: This variable has any cpp -I flags needed for socket support.
?S:.
?C:HAS_SOCKET (SOCKET):
?C: This symbol, if defined, indicates that the BSD socket interface is
?C: supported.
?C:.
?C:HAS_SOCKETPAIR (SOCKETPAIR):
?C: This symbol, if defined, indicates that the BSD socketpair() call is
?C: supported.
?C:.
?C:USE_OLDSOCKET (OLDSOCKET):
?C: This symbol, if defined, indicates that the 4.1c BSD socket interface
?C: is supported instead of the 4.2/4.3 BSD
socket interface. For instance,
?C: there is no setsockopt() call.
?C:.
?H:#\$d_socket HAS_SOCKET /**/
?H:#\$d_sockpair HAS_SOCKETPAIR /**/
?H:#\$d_oldsock USE_OLDSOCKET /**/
?H:.
?T:val
?LINT:use libc
?LINT:set d_sockpair
: see whether socket exists
socketlib="
sockethdr="
echo " "
\$echo \$n "Hmm... \$c" >&4
if set socket val -f d_socket; eval \$csym; \$val; then
echo "Looks like you have Berkeley networking support." >&4
d_socket="\$define"
?X: now check for advanced features
if set setsockopt val -f; eval \$csym; \$val; then
d_oldsock="\$undef"
else
echo "...but it uses the old 4.1c interface, rather than 4.2" >&4
d_oldsock="\$define"
fi
else
?X: HP-UX, for one, puts all the socket stuff in socklib.o. Note that if we
?X: come here on HP-UX, then we must have used nm to get symbols, or we really

```

?X: don't have sockets anyway...
if $contains socklib libc.list >/dev/null 2>&1; then
  echo "Looks like you have Berkeley networking support." >&4
  d_socket="$define"
  : we will have
  to assume that it supports the 4.2 BSD interface
  d_oldsock="$undef"
else
  echo "You don't have Berkeley networking in libc$_a..." >&4
?X: look for an optional networking library
  if test -f /usr/lib/libnet$_a; then
?X: space between two '(' needed for ksh
  ( (nm $nm_opt /usr/lib/libnet$_a | eval $nm_extract) || \
  ar t /usr/lib/libnet$_a) 2>/dev/null >> libc.list
  if $contains socket libc.list >/dev/null 2>&1; then
  echo "...but the Wollongong group seems to have hacked it in." >&4
  socketlib="-lnet"
  sockethdr="-I/usr/netinclude"
  d_socket="$define"
?X: now check for advanced features
  if $contains setsockopt libc.list >/dev/null 2>&1; then
  d_oldsock="$undef"
  else
  echo "...using the old 4.1c interface, rather than 4.2" >&4
  d_oldsock="$define"
  fi
  else
  echo "or even in libnet$_a, which is peculiar." >&4
  d_socket="$undef"
  d_oldsock="$undef"
  fi
  else
  echo "or anywhere else I see." >&4
  d_socket="$undef"
  d_oldsock="$undef"
  fi
  fi
  fi
  fi

@if
HAS_SOCKETPAIR || d_socketpair
: see if socketpair exists
set socketpair d_socketpair
eval $inlibc

@end

```

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/d_socket.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1999, Jarkko Hietaniemi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 3.0.

?RCS:

?MAKE:d_sem_unlink: Inlibc

?MAKE: -pick add \$@ %<

?S:d_sem_unlink:

?S: This variable conditionally defines HAS_SEM_UNLINK if sem_unlink() is

?S: available to unlink a POSIX semaphore.

?S:.

?C:HAS_SEM_UNLINK:

?C: This symbol, if defined, indicates that the sem_unlink system call is

?C: available to unlink a POSIX semaphore.

?C:.

?H:#\$d_sem_unlink HAS_SEM_UNLINK /**/

?H:.

?LINT:set d_sem_unlink

: see if sem_unlink exists

set sem_unlink d_sem_unlink

eval \$inlibc

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_sem_unlink.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: i_ulimit.U,v \$

?RCS:

?RCS: Copyright (c) 1998 Jarkko Hietaniemi

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?MAKE:i_ulimit: Inhdr Hasfield

?MAKE: -pick add \$@ %<

?S:i_ulimit:

?S: This variable conditionally defines the I_ULIMIT symbol, and indicates

?S: whether a C program should include <ulimit.h>.

?S:.
?C:I_ULIMIT:
?C: This symbol, if defined, indicates that <ulimit.h> exists and
?C: should be included.

?C:.
?H:#\$i_ulimit I_ULIMIT /**/
?H:.
?LINT:set i_ulimit
: see if this is a ulimit.h system
set ulimit.h i_ulimit
eval \$inhdr

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/i_ulimit.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: libflex.U 1 2006-08-24 12:32:52Z rmanfredi \$
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: \$Log: libflex.U,v \$
?RCS: Revision 3.0.1.3 1997/02/28 15:57:48 ram
?RCS: patch61: replaced .a with \$_a all over the place
?RCS:
?RCS: Revision 3.0.1.2 1994/05/06 15:07:02 ram
?RCS: patch23: now uses full library path instead of -l notation
?RCS:
?RCS: Revision 3.0.1.1 1994/01/24 14:13:25 ram
?RCS: patch16: un-obsolete this unit to allow smooth lex/flex compilations
?RCS:
?RCS: Revision 3.0 1993/08/18 12:08:59 ram
?RCS: Baseline for dist 3.0 netwide
release.
?RCS:
?MAKE:libflex: Loc lex libpth _a
?MAKE: -pick add \$@ %<
?S:libflex:
?S: This variable contains the argument to pass to the loader in order
?S: to get the flex/lex library routines. If there is no flex or flex
?S: library, it is null.
?S:.

```

?T:xxx
: see if we should include -lfl
echo " "
case "$lex" in
*flex)
xxx=`./loc libl$_a x $libpth`
case "$xxx" in
x)
echo "No flex library found." >&4
libflex="
;;
*)
echo "flex library found in $xxx." >&4
libflex="$xxx"
;;
esac
;;
*lex)
xxx=`./loc libl$_a x $libpth`
case "$xxx" in
x)
echo "No lex library found." >&4
libflex="
;;
*)
echo "lex library found in $xxx." >&4
libflex="$xxx"
;;
esac
;;
*)
echo "You don't seem to have lex or flex, so I won't look for libraries." >&4
;;
esac

```

Found in path(s):

```

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/libflex.U

```

No license file was found, but licenses were detected in source scan.

```

?RCS: $Id: d_semop.U 1 2006-08-24 12:32:52Z rmanfredi $

```

```

?RCS:

```

```

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

```

```

?RCS:

```

```

?RCS: You may redistribute only under the terms of the Artistic Licence,

```

```

?RCS: as specified in the README file that comes with the distribution.

```

```

?RCS: You may reuse parts of this distribution only within the terms of

```

```

?RCS: that same Artistic Licence; a copy of which may be found at the root

```

?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: \$Log: d_semop.U,v \$
?RCS: Revision 3.0 1993/08/18 12:07:05 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:d_semop: Inlibc
?MAKE: -pick add \$@ %<
?S:d_semop:
?S: This variable conditionally defines the HAS_SEMOP symbol, which
?S: indicates to the C program that the semop() routine is available.
?S:.
?C:HAS_SEMOP:
?C: This symbol, if defined, indicates that the semop() routine is
?C: available to execute semaphore operations.
?C:.
?H:#\$d_semop
HAS_SEMOP /**/
?H:.
?LINT:set d_semop
: see if semop exists
set semop d_semop
eval \$inlibc

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/d_semop.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$
?RCS:
?RCS: Copyright (c) 2000 Jarkko Hietaniemi
?RCS:
?RCS: You may distribute under the terms of either the GNU General Public
?RCS: License or the Artistic License, as specified in the README file.
?RCS:
?MAKE:d_lchmod: Inlibc
?MAKE: -pick add \$@ %<
?S:d_lchmod:
?S: This variable conditionally defines the HAS_LCHMOD symbol, which
?S: indicates to the C program that the lchmod() routine is available.
?S:.
?C:HAS_LCHMOD:
?C: This symbol, if defined, indicates that the lchmod routine is
?C: available to change symbolic link modes.
?C:.
?H:#\$d_lchmod HAS_LCHMOD /**/
?H:.

```
?LINT:set d_lchmod
: see if lchmod exists
set lchmod d_lchmod
eval $inlibc
```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/perl/d_lchmod.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id$
```

```
?RCS:
```

```
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
```

```
?RCS:
```

```
?RCS: You may redistribute only under the terms of the Artistic License,
```

```
?RCS: as specified in the README file that comes with the distribution.
```

```
?RCS: You may reuse parts of this distribution only within the terms of
```

```
?RCS: that same Artistic License; a copy of which may be found at the root
```

```
?RCS: of the source tree for dist 4.0.
```

```
?RCS:
```

```
?RCS: $Log: prototype.U,v $
```

```
?RCS: Revision 3.0.1.3 1994/05/06 15:11:49 ram
```

```
?RCS: patch23: ensure cc flags used when looking for prototype support
```

```
?RCS:
```

```
?RCS: Revision 3.0.1.2 1994/01/24 14:15:36 ram
```

```
?RCS: patch16: prototype handling macros now appear only when needed
```

```
?RCS:
```

```
?RCS: Revision 3.0.1.1 1993/08/25 14:03:12 ram
```

```
?RCS: patch6: defines were referring to non-existent VOID symbol
```

```
?RCS:
```

```
?RCS: Revision 3.0 1993/08/18 12:09:36 ram
```

```
?RCS: Baseline for dist 3.0 netwide release.
```

```
?RCS:
```

```
?MAKE:prototype:
```

```
Myread Oldconfig cat +cc +ccflags rm Setvar
```

```
?MAKE: -pick add $@ %<
```

```
?S:prototype:
```

```
?S: This variable holds the eventual value of CAN_PROTOTYPE, which
```

```
?S: indicates the C compiler can handle function prototypes.
```

```
?S:.
```

```
?C:CAN_PROTOTYPE ~ %<:
```

```
?C: If defined, this macro indicates that the C compiler can handle
```

```
?C: function prototypes.
```

```
?C:.
```

```
?C:DOTS:
```

```
?C: This macro is used to specify the ... in function prototypes which
```

```
?C: have arbitrary additional arguments.
```

```
?C:.
```

?C:NXT_ARG:

?C: This macro is used to separate arguments in the declared argument list.

?C:.

?C:P_FUNC:

?C: This macro is used to declare "private" (static) functions.

?C: It takes three arguments: the function type and name, a parenthesized

?C: traditional (comma separated) argument list, and the declared argument

?C: list (in which arguments are separated with NXT_ARG, and additional

?C: arbitrary arguments are specified with DOTS). For example:

?C:

?C: P_FUNC(int foo, (bar, baz), int bar NXT_ARG char *baz[])

?C:.

?C:P_FUNC_VOID:

?C: This

macro is used to declare "private" (static) functions that have

?C: no arguments. The macro takes one argument: the function type and name.

?C: For example:

?C:

?C: P_FUNC_VOID(int subr)

?C:.

?C:V_FUNC:

?C: This macro is used to declare "public" (non-static) functions.

?C: It takes three arguments: the function type and name, a parenthesized

?C: traditional (comma separated) argument list, and the declared argument

?C: list (in which arguments are separated with NXT_ARG, and additional

?C: arbitrary arguments are specified with DOTS). For example:

?C:

?C: V_FUNC(int main, (argc, argv), int argc NXT_ARG char *argv[])

?C:.

?C:V_FUNC_VOID:

?C: This macro is used to declare "public" (non-static) functions that have

?C: no arguments. The macro takes one argument: the function type and name.

?C: For example:

?C:

?C: V_FUNC_VOID(int fork)

?C:.

?C:_(P):

?C: This macro is used to declare function parameters for folks who want

?C: to make declarations with prototypes using a different style than

?C: the above macros. Use double parentheses. For example:

?C:

?C: int main _((int argc, char *argv[]));

?C:.

?H:%<:#\$prototype CAN_PROTOTYPE /**/

?H:%<:#ifdef CAN_PROTOTYPE

?H:%NXT_ARG:#define NXT_ARG ,

?H:%DOTS:#define DOTS , ...

```

?H:?V_FUNC:#define V_FUNC(name, arglist, args)name(args)
?H:?P_FUNC:#define P_FUNC(name, arglist, args)static name(args)
?H:?V_FUNC_VOID:#define V_FUNC_VOID(name)name(void)
?H:?P_FUNC_VOID:#define P_FUNC_VOID(name)static name(void)
?H:?_:#define _(args) args
?H:?%<:#else
?H:?NXT_ARG:#define NXT_ARG ;
?H:?DOTS:#define DOTS
?H:?V_FUNC:#define V_FUNC(name, arglist, args)name arglist args;
?H:?P_FUNC:#define P_FUNC(name, arglist, args)static name arglist args;
?H:?V_FUNC_VOID:#define V_FUNC_VOID(name)name()
?H:?P_FUNC_VOID:#define P_FUNC_VOID(name)static name()
?H:?_:#define _(args) ()
?H:?%<:#endif
?H:.
?W:%<:NXT_ARG DOTS V_FUNC P_FUNC V_FUNC_VOID P_FUNC_VOID _
?LINT:set prototype
: Cruising for prototypes
echo " "
echo "Checking out
function prototypes..." >&4
$cat >prototype.c <<'EOCP'
int main(int argc, char *argv[]) {
    exit(0);}
EOCP
if $cc $ccflags -c prototype.c >prototype.out 2>&1 ; then
    echo "Your C compiler appears to support function prototypes."
    val="$define"
else
    echo "Your C compiler doesn't seem to understand function prototypes."
    val="$undef"
fi
set prototype
eval $setvar
$rm -f prototype*

```

Found in path(s):

```

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/prototype.U

```

No license file was found, but licenses were detected in source scan.

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?MAKE:d_fegetround: Inlibc

?MAKE: -pick add \$@ %<

?S:d_fegetround:

?S: This variable conditionally defines HAS_FEGETROUND if fegetround() is

?S: available to get the floating point rounding mode.
?S:.
?C:HAS_FEGETROUND:
?C: This symbol, if defined, indicates that the fegetround routine is
?C: available to return the macro corresponding to the current rounding
?C: mode.
?C:.
?H:#\$d_fegetround HAS_FEGETROUND /**/
?H:.
?LINT:set d_fegetround
: see if fegetround exists
set fegetround d_fegetround
eval \$inlibc

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_fegetround.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: \$Log: pager.U,v \$
?RCS: Revision 3.0.1.2 1995/01/30 14:41:26 ram
?RCS: patch49: ensure dflt gets initialized in case no pagers are found (WED)
?RCS:
?RCS: Revision 3.0.1.1 1994/10/29 16:27:45 ram
?RCS: patch36: replaced Myread by Getfile in the dependency line
?RCS:
?RCS: Revision 3.0 1993/08/18 12:09:30 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:pager: pg more less Getfile Oldconfig
?MAKE: -pick add \$@ %<
?S:pager:
?S: This variable contains the name of the preferred pager
on the system.
?S: Usual values are (the full pathnames of) more, less, pg, or cat.
?S:.
: locate the preferred pager for this system
fn=f/

```

case "$pager" in
")
dflt="
case "$pg" in
/*) dflt=$pg;;
[a-zA-Z]:/*) dflt=$pg;;
esac
case "$more" in
/*) dflt=$more;;
[a-zA-Z]:/*) dflt=$more;;
esac
case "$less" in
/*) dflt=$less;;
[a-zA-Z]:/*) dflt=$less;;
esac
case "$dflt" in
") dflt=/usr/ucb/more;;
esac
;;
*) dflt="$pager"
;;
esac
?X: Instruct ./getfile to trust the default pager value,
?X: even if it does not begin with a slash. For example, on os2,
?X: pager might be cmd /c more. Also, it might include some options,
?X: such as '/usr/bin/less -R'. ./getfile would report that
?X: "/usr/bin/less -R" doesn't exist.
?X: See comments in Getfile.U.
fn="f/($dflt)"
echo " "
rp='What pager is used on your system?'
./getfile
pager="$ans"

```

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/pager.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:
 ?RCS: \$Log: mallocsrc.U,v \$
 ?RCS: Revision 3.0.1.2 1997/02/28 16:10:26 ram
 ?RCS: patch61: added support for Free_t, the type of free()
 ?RCS: patch61: replaced .o with \$_o all over the place
 ?RCS:
 ?RCS: Revision 3.0.1.1 1994/05/06 15:10:46 ram
 ?RCS: patch23: added support for MYMALLOC, mainly for perl5 (ADO)
 ?RCS:
 ?RCS: Revision 3.0 1993/08/18 12:09:12 ram
 ?RCS: Baseline for dist 3.0 netwide release.
 ?RCS:
 ?MAKE:mallocsrc mallocobj usemymalloc malloctype d_mymalloc \
 freetype: Myread \
 Oldconfig
 package Guess Setvar rm cat +cc +ccflags Findhdr \
 i_malloc i_stdlib sed libs _o ptrsize
 ?MAKE: -pick add \$@ %<
 ?X: Put near top so that other tests don't erroneously include
 ?X: -lmalloc. --AD 22 June 1998
 ?Y:TOP
 ?S:usemymalloc:
 ?S: This variable contains y if the malloc that comes with this package
 ?S: is desired over the system's version of malloc. People often include
 ?S: special versions of malloc for efficiency, but such versions are often
 ?S: less portable. See also mallocsrc and mallocobj.
 ?S: If this is 'y', then -lmalloc is removed from \$libs.
 ?S:.
 ?S:mallocsrc:
 ?S: This variable contains the name of the malloc.c that comes with
 ?S: the package, if that malloc.c is preferred over the system malloc.
 ?S: Otherwise the value is null. This variable is intended for generating
 ?S: Makefiles.
 ?S:.
 ?S:d_mymalloc:
 ?S: This variable conditionally defines MYMALLOC in case other parts
 ?S: of the source want to take special action if MYMALLOC is used.
 ?S: This may include different sorts
 ?S: of profiling or error detection.
 ?S:.
 ?S:mallocobj:
 ?S: This variable contains the name of the malloc.o that this package
 ?S: generates, if that malloc.o is preferred over the system malloc.
 ?S: Otherwise the value is null. This variable is intended for generating
 ?S: Makefiles. See mallocsrc.
 ?S:.
 ?S:freetype:
 ?S: This variable contains the return type of free(). It is usually

?S: void, but occasionally int.

?S:.

?S:malloctype:

?S: This variable contains the kind of ptr returned by malloc and realloc.

?S:.

?C:Free_t:

?C: This variable contains the return type of free(). It is usually

?C: void, but occasionally int.

?C:.

?C:Malloc_t (MALLOC_PTRTYPE):

?C: This symbol is the type of pointer returned by malloc and realloc.

?C:.

?H:#define Malloc_t \$malloctype /**/

?H:#define Free_t \$freetype /**/

?H:.

?C:MYMALLOC:

?C: This symbol, if defined, indicates that we're using our own malloc.

?C:.

?H:\$d_mymalloc MYMALLOC /**/

?H:.

?LINT:change libs

?X: Cannot test for malloctx; it

is the unit's name and there is a bug in

?X: the interpreter which defines all the names, even though they are not used.

@if malloctx

: determine which malloc to compile in

echo " "

case "\$usemymalloc" in

[yY]*|true|\$define) dflt='y' ;;

[nN]*|false|\$undef) dflt='n' ;;

*)

case "\$ptrsize" in

4) dflt='y' ;;

*) dflt='n' ;;

esac

;;

esac

rp="Do you wish to attempt to use the malloc that comes with \$package?"

./myread

usemymalloc="\$ans"

case "\$ans" in

y*|true)

usemymalloc='y'

malloctx='malloc.c'

malloctx="\$malloctx_o"

d_mymalloc="\$define"

?X: Maybe libs.U should be dependent on malloctx.U, but then

?X: most packages that use dist probably don't supply their own

```

?X: malloc, so this is probably an o.k. compromise
case "$libs" in
*-lmalloc*)
: Remove malloc from list of libraries to use
echo "Removing unneeded -lmalloc from library list" >&4
set `echo X $libs | $sed -e 's/-lmalloc / /' -e 's/-lmalloc$/'^
shift
libs="$*"
echo "libs = $libs" >&4
;;
esac
;;
*)
usemymalloc='n'
malloclsrc=""
malloclobj=""
d_mymalloc="$undef"
;;
esac

@end
@if
MALLOCPTRTYPE || Malloc_t || Free_t
: compute the return types of malloc and free
echo " "
$cat >malloc.c <<END
#$i_malloc I_MALLOC
#$i_stdlib I_STDLIB
#include <stdio.h>
#include <sys/types.h>
#ifdef I_MALLOC
#include <malloc.h>
#endif
#ifdef I_STDLIB
#include <stdlib.h>
#endif
#ifdef TRY_MALLOC
void *malloc();
#endif
#ifdef TRY_FREE
void free();
#endif
END
@if MALLOCPTRTYPE || Malloc_t
case "$malloctype" in
")
if $cc $cflags -c -DTRY_MALLOC malloc.c >/dev/null 2>&1; then
malloctype='void *'

```

```

else
  malloctype='char *'
fi
;;
esac
echo "Your system wants malloc to return '$malloctype', it would seem." >&4
@end

@if Free_t
case "$freetype" in
")
if $cc $ccflags -c -DTRY_FREE malloc.c >/dev/null 2>&1; then
  freetype='void'
else
  freetype='int'
fi
;;
esac
echo "Your system uses $freetype free(), it would seem." >&4
@end
$rm -f malloc.[co]
@end

```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/mallocsrc.U
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1999, Jarkko Hietaniemi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 3.0.

?RCS:

?MAKE:d_mq_unlink: Inlibc

?MAKE: -pick add \$@ %<

?S:d_mq_unlink:

?S: This variable conditionally defines HAS_MQ_UNLINK if mq_unlink() is

?S: available to unlink a POSIX message queue.

?S:.

?C:HAS_MQ_UNLINK:

?C: This symbol, if defined, indicates that the mq_unlink system call is

?C: available to unlink a POSIX message queue.

?C:.

?H:#\$d_mq_unlink HAS_MQ_UNLINK /**/

?H:.

?LINT:set d_mq_unlink

: see if mq_unlink exists

set mq_unlink d_mq_unlink

eval \$inlibc

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_mq_unlink.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: registers.U 1 2006-08-24 12:32:52Z rmanfredi \$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic Licence,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic Licence; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: registers.U,v \$

?RCS: Revision 3.0.1.2 1997/02/28 16:19:41 ram

?RCS: patch61: removed empty ?LINT lines

?RCS:

?RCS: Revision 3.0.1.1 1994/10/29 16:28:33 ram

?RCS: patch36: call ./Cpplib explicitly instead of relying on PATH

?RCS:

?RCS: Revision 3.0 1993/08/18 12:09:41 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?MAKE:registers reg1 reg2 reg3 reg4 reg5 reg6 reg7 reg8 reg9 reg10 reg11 \
reg12 reg13 reg14 reg15 reg16: awk rm Cpplib

Myread Oldconfig

?MAKE: -pick add \$@ %<

?S:registers:

?S: This variable contains the number of register declarations paid

?S: attention to by the C compiler.

?S:.

?S:reg1:

?S: This variable, along with reg2, reg3, etc. contains the eventual

?S: value for the symbols register1, register2, register3, etc. It has

?S: either the value "register" or is null.

?S:.

?C:register1:

?C: This symbol, along with register2, register3, etc. is either the word

?C: "register" or null, depending on whether the C compiler pays attention

?C: to this many register declarations. The intent is that you don't have
?C: to order your register declarations in the order of importance, so you
?C: can freely declare register variables in sub-blocks of code and as
?C: function parameters. Do not use register<n> more than once per routine.
?C:.

?LINT:describe reg2 reg3 reg4 reg5 reg6 reg7 reg8 reg9 reg10 reg11

?LINT:describe reg12 reg13 reg14 reg15 reg16

?LINT:known register2 register3 register4 register5 register6
register7

?LINT:known register8 register9 register10 register11 register12 register13

?LINT:known register14 register15 register16

?H:#define register1 \$reg1 /**/

?H:#define register2 \$reg2 /**/

?H:#define register3 \$reg3 /**/

?H:#define register4 \$reg4 /**/

?H:#define register5 \$reg5 /**/

?H:#define register6 \$reg6 /**/

?H:#define register7 \$reg7 /**/

?H:#define register8 \$reg8 /**/

?H:#define register9 \$reg9 /**/

?H:#define register10 \$reg10 /**/

?H:#define register11 \$reg11 /**/

?H:#define register12 \$reg12 /**/

?H:#define register13 \$reg13 /**/

?H:#define register14 \$reg14 /**/

?H:#define register15 \$reg15 /**/

?H:#define register16 \$reg16 /**/

?H:.

?F:!.foo

: see how many register declarations we want to use

case "\$registers" in

")

if ./Cppsym vax; then

 dflt=6

elif ./Cppsym sun mc68000 mips; then

 dflt=10

elif ./Cppsym pyr; then

 dflt=14

elif ./Cppsym ns32000 ns16000; then

 dflt=5

elif ./Cppsym \$smallmach; then

 dflt=3

else

 : if you have any other numbers

 for me, please send them in

 dflt=6

fi;;

*) dflt=\$registers ;;

```
esac
?LINT:set reg2 reg3 reg4 reg5 reg6 reg7 reg8 reg9 reg10 reg11
?LINT:set reg12 reg13 reg14 reg15 reg16
cat <<EOM
```

Different C compilers on different machines pay attention to different numbers of register declarations. About how many register declarations in each routine does your C compiler pay attention to? (OK to guess)

```
EOM
rp="Maximum register declarations?"
./myread
registers=$ans
reg1="
$awk "BEGIN { for (i=1; i<=16; i++) printf \"reg%d=\\n\\\", i} \" \
</dev/null >.foo
./foo
$awk "BEGIN { for (i=1; i<=$registers; i++) printf \"reg%d=register\\n\\\", i} \" \
</dev/null >.foo
./foo
$rm -f .foo
```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/registers.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: i_stddef.U 1 2006-08-24 12:32:52Z rmanfredi $
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: $Log: i_stddef.U,v $
?RCS: Revision 3.0 1993/08/18 12:08:27 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:i_stddef: Inhdr
?MAKE:-pick add $@ %<
?S:i_stddef:
?S: This variable conditionally defines the I_STDDEF symbol, which
?S: indicates to the C program that <stddef.h> exists and should
?S: be included.
?S:.
```

?C:I_STDDEF:

?C: This symbol, if defined, indicates that <stddef.h> exists and should

?C: be included.

?C:.

?H:#\$i_stddef I_STDDEF /**/

?H:.

?LINT:set

i_stddef

: see if stddef is available

set stddef.h i_stddef

eval \$inhdr

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/i_stddef.U

No license file was found, but licenses were detected in source scan.

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?MAKE:d_newlocale d_freelocale d_uselocale d_duplocale d_querylocale i_xlocale: Inlibc Inhdr

?MAKE: -pick add \$@ %<

?S:d_newlocale:

?S: This variable conditionally defines the HAS_NEWLOCALE symbol, which

?S: indicates to the C program that the newlocale() routine is available

?S: to return a new locale object or modify an existing locale object.

?S:.

?S:d_freelocale:

?S: This variable conditionally defines the HAS_FREELOCALE symbol, which

?S: indicates to the C program that the freelocale() routine is available

?S: to deallocate the resources associated with a locale object.

?S:.

?S:d_uselocale:

?S: This variable conditionally defines the HAS_USELOCALE symbol, which

?S: indicates to the C program that the uselocale() routine is available

?S: to set the current locale

for the calling thread.

?S:.

?S:d_duplocale:

?S: This variable conditionally defines the HAS_DUPLOCALE symbol, which

?S: indicates to the C program that the duplocale() routine is available

?S: to duplicate a locale object.

?S:.

?S:d_querylocale:

?S: This variable conditionally defines the HAS_QUERYLOCALE symbol, which

?S: indicates to the C program that the querylocale() routine is available

?S: to return the name of the locale for a category mask.

?S:.

?S:i_xlocale:
 ?S: This symbol, if defined, indicates to the C program that it should
 ?S: include <xlocale.h> to get uselocale() and its friends
 ?S:.
 ?C:HAS_NEWLOCALE:
 ?C: This symbol, if defined, indicates that the newlocale routine is
 ?C: available to return a new locale object or modify an existing
 ?C: locale object.
 ?C:.
 ?C:HAS_FREELOCALE:
 ?C: This symbol, if defined, indicates that the freelocale routine is
 ?C: available to deallocates the resources associated with a locale object.
 ?C:.
 ?C:HAS_USELOCALE:
 ?C: This symbol, if defined,
 indicates that the uselocale routine is
 ?C: available to set the current locale for the calling thread.
 ?C:.
 ?C:HAS_DUPLOCALE:
 ?C: This symbol, if defined, indicates that the duplocale routine is
 ?C: available to duplicate a locale object.
 ?C:.
 ?C:HAS_QUERYLOCALE:
 ?C: This symbol, if defined, indicates that the querylocale routine is
 ?C: available to return the name of the locale for a category mask.
 ?C:.
 ?C:I_XLOCALE:
 ?C: This symbol, if defined, indicates to the C program that it should
 ?C: include <xlocale.h> to get uselocale() and its friends.
 ?C:.
 ?H:#\$d_newlocale HAS_NEWLOCALE /**/
 ?H:#\$d_freelocale HAS_FREELOCALE /**/
 ?H:#\$d_uselocale HAS_USELOCALE /**/
 ?H:#\$d_duplocale HAS_DUPLOCALE /**/
 ?H:#\$d_querylocale HAS_QUERYLOCALE /**/
 ?H:#\$i_xlocale I_XLOCALE /**/
 ?H:.
 ?LINT:set i_xlocale
 ?LINT:set d_newlocale
 ?LINT:set d_freelocale
 ?LINT:set d_uselocale
 ?LINT:set d_duplocale
 ?LINT:set d_querylocale
 : see if this is an xlocale.h system
 set xlocale.h i_xlocale
 eval \$inhdr
 :

see if newlocale exists
set newlocale d_newlocale
eval \$inlibc

: see if freelocale exists
set freelocale d_freelocale
eval \$inlibc

: see if uselocale exists
set uselocale d_uselocale
eval \$inlibc

: see if duplocale exists
set duplocale d_duplocale
eval \$inlibc

: see if querylocale exists
set querylocale d_querylocale
eval \$inlibc

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_newlocale.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: i_systwgcf.U 1 2006-08-24 12:32:52Z rmanfredi \$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic Licence,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic Licence; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: i_systwgcf.U,v \$

?RCS: Revision 3.0 1993/08/18 12:08:39 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?MAKE:i_systwgcf: Inhdr

?MAKE: -pick add \$@ %<

?S:i_systwgcf:

?S: This variable conditionally defines the I_SYS_TWG_CF symbol, and

?S: indicates whether a C program should include sys/twg_config.h.

?S:.

?C:I_SYS_TWG_CF:

?C: This symbol, if defined, indicates to the C program that it should

?C: include sys/twg_config.h.

```
?C:.
?H:#$i_systwgcF
I_SYS_TWG_CF /**/
?H:.
?LINT:set i_systwgcF
: see if this is a sys/twg_config.h system
set sys/twg_config.h i_systwgcF
eval $inhdr
```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/i_systwgcF.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: d_getnbyname.U,v $
?RCS:
?RCS: Copyright (c) 1998 Andy Dougherty
?RCS:
?RCS: You may distribute under the terms of either the GNU General Public
?RCS: License or the Artistic License, as specified in the README file.
?RCS:
?MAKE:d_getnbyname: Inlibc
?MAKE:-pick add $@ %<
?S:d_getnbyname:
?S: This variable conditionally defines the HAS_GETNETBYNAME symbol, which
?S: indicates to the C program that the getnetbyname() routine is available
?S: to look up networks by their names.
?S:.
?C:HAS_GETNETBYNAME:
?C: This symbol, if defined, indicates that the getnetbyname() routine is
?C: available to look up networks by their names.
?C:.
?H:#$d_getnbyname HAS_GETNETBYNAME /**/
?H:.
?LINT:set d_getnbyname
: see if getnetbyname exists
set getnetbyname d_getnbyname
eval $inlibc
```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/modified/d_getnbynm.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id$
?RCS:
?RCS: Copyright (c) 1999 Jarkko Hietaniemi
?RCS:
```

?RCS: You may distribute under the terms of either the GNU General Public
?RCS: License or the Artistic License, as specified in the README file.
?RCS:
?MAKE:d_statfs_s: \
Hasstruct i_sysparam i_sysmount i_systypes \
i_sysvfs i_sysstatfs Setvar
?MAKE: -pick add \$@ %<
?S:d_statfs_s:
?S: This variable conditionally defines the HAS_STRUCTURE_STATFS symbol,
?S: which indicates that the struct statfs is supported.
?S:.
?C:HAS_STRUCTURE_STATFS:
?C: This symbol, if defined, indicates that the struct statfs
?C: to do statfs() is supported.
?C:.
?H:#\$d_statfs_s HAS_STRUCTURE_STATFS /**/
?H:.
?LINT:set d_statfs_s
: Check for statfs_s
echo " "
echo "Checking to see if your system supports struct statfs..." >&4
set d_statfs_s statfs \$i_systypes sys/types.h \$i_sysparam sys/param.h \$i_sysmount sys/mount.h \$i_sysvfs sys/vfs.h
\$i_sysstatfs sys/statfs.h
eval \$hasstruct
case "\$d_statfs_s"
in
"\$define") echo "Yes, it does." ;;
*) echo "No, it doesn't." ;;
esac

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_statfs_s.U

No license file was found, but licenses were detected in source scan.

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?MAKE:d_ilogb: Inlibc

?MAKE: -pick add \$@ %<

?S:d_ilogb:

?S: This variable conditionally defines the HAS_ILOGB symbol, which

?S: indicates to the C program that the ilogb() routine is available

?S: for extracting the exponent of double x as a signed integer.

?S:.

?C:HAS_ILOGB:

?C: This symbol, if defined, indicates that the ilogb routine is

?C: available to get integer exponent of a floating-point value.

```
?C:.
?H:#$d_ilogb HAS_ILOGB /**/
?H:.
?LINT:set d_ilogb
: see if ilogb exists
set ilogb d_ilogb
eval $inlibc
```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/perl/d_ilogb.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id$
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: $Log: errnolist.U,v $
?RCS: Revision 3.0.1.2 1997/02/28 15:48:01 ram
?RCS: patch61: replaced .a with $_a all over the place
?RCS: patch61: likewise for .o replaced by $_o
?RCS:
?RCS: Revision 3.0.1.1 1994/01/24 14:10:54 ram
?RCS: patch16: created
?RCS:
?MAKE:errnolist errnolist_SH errnolist_a errnolist_c errnolist_o: cat +cc \
+ccflags +libs +d_sysernlst_a_o
?MAKE: -pick add $@ %<
?S:errnolist:
?S: This variable holds the base name of a file containing the
?S: definition of the sys_errnolist
?S: array, if the C library
?S: doesn't provide it already. Otherwise, its value is empty.
?S: The following lines should be included in your Makefile.SH:
?S:
?S: case "$serrnolist" in
?S: ") ;;
?S: *)
?S: $spitshell >>Makefile <<!GROK!THIS!
?S: $serrnolist_c: $serrnolist_SH $serrnolist_a
?S: sh ./$serrnolist_SH
?S:
```

```

?S: !GROK!THIS!
?S: ;;
?S: esac
?S:
?S: You may define the 'errnolist' variable in your Myinit.U if you
?S: wish to override its default value "errnolist".
?S:.
?S:errnolist_SH:
?S: This is the name of a file which will generate errnolistc.
?S:.
?S:errnolist_a:
?S: This is the name of the awk script called by errnolist_SH.
?S:.
?S:errnolist_c:
?S: This is the name of a generated C file which provides the
?S: definition of the sys_errnolist array.
?S:.
?S:errnolist_o:
?S: This is the name of the object file which provides the
?S: definition of the sys_errnolist array, if the C library
?S: doesn't provide it already. Otherwise, its value is empty.
?S:.
?INIT:errnolist=errnolist
:
check for sys_errnolist
@if d_sysernlst || HAS_SYS_ERRNOLIST
case "$d_sysernlst" in
"$define")
errnolist="
errnolist_SH="
errnolist_a="
errnolist_c="
errnolist_o="
;;
*)
echo " "
echo "I'll make sure your Makefile provides sys_errnolist in $errnolist.c"
errnolist_SH=$errnolist.SH
errnolist_a=$errnolist$_a
errnolist_c=$errnolist.c
errnolist_o=$errnolist$_o
;;
esac
@else
echo " "
$cat <<EOM
Checking to see if your C library provides us with sys_errnolist[...]
EOM

```

```

$cat >errnolist.c <<'EOCP'
extern char *sys_errnolist[];
int main() {
    char *p0 = sys_errnolist[0];
    char *p1 = sys_errnolist[1];

    return (p0 == p1); /* Make sure they're not optimized away */
}
EOCP
if $cc $ccflags -o errnolist errnolist.c $libs >/dev/null 2>&1 ; then
    echo "It does."
    errnolist="
    errnolist_SH="
    errnolist_a="
    errnolist_c="
    errnolist_o="
else
    echo "I'll make sure your Makefile provides sys_errnolist in $errnolist.c"

    errnolist_SH=$errnolist.SH
    errnolist_a=$errnolist$_a
    errnolist_c=$errnolist.c
    errnolist_o=$errnolist$_o
fi
@end

```

Found in path(s):

```

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/errnolist.U

```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: i_netdb.U,v \$

?RCS:

?RCS: Copyright (c) 1998 Andy Dougherty

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?MAKE:i_netdb: Inhdr

?MAKE: -pick add \$@ %<

?S:i_netdb:

?S: This variable conditionally defines the I_NETDB symbol, and indicates

?S: whether a C program should include <netdb.h>.

?S:.

?C:I_NETDB:

?C: This symbol, if defined, indicates that <netdb.h> exists and

?C: should be included.

?C:.

```
?H:#$i_netdb I_NETDB /**/  
?H.:  
?LINT:set i_netdb  
: see if this is a netdb.h system  
set netdb.h i_netdb  
eval $inhdr
```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-  
debian-perl-5.26.1/U/modified/i_netdb.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id$
```

```
?RCS:
```

```
?RCS: Copyright (c) 1999 Jarkko Hietaniemi
```

```
?RCS:
```

```
?RCS: You may redistribute only under the terms of the Artistic License,
```

```
?RCS: as specified in the README file that comes with the distribution.
```

```
?RCS: You may reuse parts of this distribution only within the terms of
```

```
?RCS: that same Artistic License; a copy of which may be found at the root
```

```
?RCS: of the source tree for dist 3.0.
```

```
?RCS:
```

```
?MAKE:sitehtml3dir sitehtml3direxp installsitehtml3dir: Getfile \  
Setprefixvar prefix siteprefix html3dir sed
```

```
?MAKE: -pick add $@ %<
```

```
?Y:TOP
```

```
?D:sitehtml3dir="
```

```
?S:sitehtml3dir:
```

```
?S: This variable contains the name of the directory in which site-specific  
?S: library html source pages are to be put. It is the responsibility of the
```

```
?S: Makefile.SH to get the value of this into the proper command.
```

```
?S: You must be prepared to do the ~name expansion yourself.
```

```
?S: The standard distribution will put nothing in this directory.
```

```
?S: After
```

```
perl has been installed, users may install their own local
```

```
?S: library html pages in this directory with
```

```
?S: MakeMaker Makefile.PL
```

```
?S: or equivalent. See INSTALL for details.
```

```
?S:.
```

```
?D:sitehtml3direxp="
```

```
?S:sitehtml3direxp:
```

```
?S: This variable is the same as the sitehtml3dir variable, but is filename
```

```
?S: expanded at configuration time, for convenient use in makefiles.
```

```
?S:.
```

```
?D:installsitehtml3dir="
```

```
?S:installsitehtml3dir:
```

```
?S: This variable is really the same as sitehtml3direxp, unless you are using
```

```
?S: AFS in which case it points to the read/write location whereas
```

?S: html3direxp only points to the read-only access location. For extra
?S: portability, you should only use this variable within your makefiles.

?S:.

?LINT:change prefixvar

?LINT:set installsitehtml3dir

?LINT:set sitehtml3dir

?LINT:set sitehtml3direxp

: determine where add-on library html pages go

: There is no standard location, so try to copy the previously-selected

: directory structure for the core html pages.

case

"\$sitehtml3dir" in

) dflt=`echo "\$html3dir" | \$sed "s#^\$prefix#\$siteprefix#"` ;;

*) dflt=\$sitehtml3dir ;;

esac

case "\$dflt" in

"|" ') dflt=none ;;

esac

fn=dn+~

rp='Pathname where the site-specific library html pages should be installed?'

./getfile

prefixvar=sitehtml3dir

./setprefixvar

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/installdirs/sitehtml3dir.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: lex.U 1 2006-08-24 12:32:52Z rmanfredi \$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic Licence,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic Licence; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: Original Author: Graham Stoney <greyham@research.canon.oz.au>

?RCS:

?RCS: \$Log: lex.U,v \$

?RCS: Revision 3.0.1.3 1994/10/29 16:22:50 ram

?RCS: patch36: spurious single quote could cause Configure to crash

?RCS: patch36: (reported by Xavier Le Vourch <xavierl@eiffel.com>.)

?RCS:

?RCS: Revision 3.0.1.2 1994/08/29 16:27:09 ram

?RCS: patch32: added lexflags variable for lex flags setting

```

?RCS:
?RCS: Revision 3.0.1.1 1994/05/06 15:06:01 ram
?RCS: patch23: added
trailing blank line for metalint
?RCS:
?RCS: Revision 3.0 1993/08/18 12:08:55 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:lex lexflags: Guess Myread Oldconfig flex test
?MAKE: -pick add $@ %<
?S:lex:
?S: This variable holds the name of the lexical analyser generator we
?S: want to use in the Makefile. It can be lex or flex.
?S:.
?S:lexflags:
?S: This variable holds any flags that should be passed to the lexical
?S: analyzer. It is up to the Makefile to use it.
?S:.
: determine lexical analyser generator
case "$lex" in
")
dflt=lex;;
*)
dflt="$lex";;
esac
echo " "
if $test -f "$flex"; then
rp='Which lexical analyser generator (lex or flex) shall I use?'
else
rp='Which lexical analyser generator shall I use?'
fi
./myread
lex="$ans"

@if lexflags
: if using lex this will normally be useless, but flex frequently takes args
echo " "
case "$lexflags" in
") dflt='none';;
*) dflt="$lexflags";;
esac
rp="What flags should be given to $lex?"
./myread
case "$ans"
in
none) lexflags="";;
*) lexflags="$ans";;
esac

```

@end

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/lex.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: gidtype.U,v \$

?RCS: Revision 3.0.1.3 1994/08/29 16:21:44 ram

?RCS: patch32: now uses new Typedef unit to compute type information

?RCS: patch32: removed useless usage of Setvar (for now)

?RCS:

?RCS: Revision 3.0.1.2 1994/05/13 15:21:07 ram

?RCS: patch27: added lint hint

?RCS:

?RCS: Revision 3.0.1.1 1994/05/06 15:01:51 ram

?RCS: patch23: protected gidtype setting via setvar (ADO)

?RCS: patch23: made Gid_t comment more explicit (ADO)

?RCS:

?RCS: Revision 3.0 1993/08/18 12:08:11 ram

?RCS:

Baseline for dist 3.0 netwide release.

?RCS:

?MAKE:gidtype: Myread Typedef Findhdr

?MAKE: -pick add \$@ %<

?S:gidtype:

?S: This variable defines Gid_t to be something like gid_t, int,

?S: ushort, or whatever type is used to declare the return type

?S: of getgid(). Typically, it is the type of group ids in the kernel.

?S:.

?C:Gid_t (GIDTYPE):

?C: This symbol holds the return type of getgid() and the type of

?C: argument to setrgid() and related functions. Typically,

?C: it is the type of group ids in the kernel. It can be int, ushort,

?C: uid_t, etc... It may be necessary to include <sys/types.h> to get

?C: any typedef'ed information.

?C:.

```

?H:#define Gid_t $gidtype /* Type for getgid(), etc... */
?H:.
?T:xxx
: see what type gids are declared as in the kernel
set gid_t gidtype xxx stdio.h sys/types.h
eval $typedef
case "$gidtype" in
xxx)
xxx=`./findhdr sys/user.h`
set `grep 'groups\[NGROUPS\];' "$xxx" 2>/dev/null` unsigned short
case $1 in
unsigned) dflt="$1 $2" ;;
*) dflt="$1"
;;
esac
;;
*) dflt="$gidtype";;
esac
echo " "
rp="What is the type for group ids returned by getgid()?"
./myread
gidtype="$ans"

```

Found in path(s):

```

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/gidtype.U

```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1999, Jarkko Hietaniemi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 3.0.

?RCS:

?MAKE:d_timer_create: Inlibc

?MAKE: -pick add \$@ %<

?S:d_timer_create:

?S: This variable conditionally defines HAS_TIMER_CREATE if timer_create()

?S: is available to create a POSIX timer.

?S:.

?C:HAS_TIMER_CREATE:

?C: This symbol, if defined, indicates that the timer_create system call is

?C: available to create a POSIX timer.

?C:.

?H:#\$d_timer_create HAS_TIMER_CREATE /**/

?H:.

?LINT:set d_timer_create

: see if timer_create exists

set timer_create d_timer_create

eval \$inlibc

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_timer_create.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1998 Andy Dougherty

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?MAKE:use64bitint use64bitall archname64: Myread Oldconfig Setvar test \
usemorebits longsize ccflags d_quad uquadtype Compile rm_try run

?MAKE: -pick add \$@ %<

?Y:TOP

?S:use64bitint:

?S: This variable conditionally defines the USE_64_BIT_INT symbol,

?S: and indicates that 64-bit integer types should be used

?S: when available. The minimal possible 64-bitness

?S: is employed, just enough to get 64-bit integers into Perl.

?S: This may mean using for example "long longs", while your memory

?S: may still be limited to 2 gigabytes.

?S:.

?S:use64bitall:

?S: This variable conditionally defines the USE_64_BIT_ALL symbol,

?S: and indicates that 64-bit integer types should be used

?S: when available. The maximal

possible

?S: 64-bitness is employed: LP64 or ILP64, meaning that you will

?S: be able to use more than 2 gigabytes of memory. This mode is

?S: even more binary incompatible than USE_64_BIT_INT. You may not

?S: be able to run the resulting executable in a 32-bit CPU at all or

?S: you may need at least to reboot your OS to 64-bit mode.

?S:.

?S:archname64:

?S: This variable is used for the 64-bitness part of \$archname.

?S:.

?C:USE_64_BIT_INT:

?C: This symbol, if defined, indicates that 64-bit integers should

?C: be used when available. If not defined, the native integers

```

?C: will be employed (be they 32 or 64 bits). The minimal possible
?C: 64-bitness is used, just enough to get 64-bit integers into Perl.
?C: This may mean using for example "long longs", while your memory
?C: may still be limited to 2 gigabytes.
?C:.
?C:USE_64_BIT_ALL:
?C: This symbol, if defined, indicates that 64-bit integers should
?C: be used when available. If not defined, the native integers
?C: will be used (be
they 32 or 64 bits). The maximal possible
?C: 64-bitness is employed: LP64 or ILP64, meaning that you will
?C: be able to use more than 2 gigabytes of memory. This mode is
?C: even more binary incompatible than USE_64_BIT_INT. You may not
?C: be able to run the resulting executable in a 32-bit CPU at all or
?C: you may need at least to reboot your OS to 64-bit mode.
?C:.
?H:%<:#ifndef USE_64_BIT_INT
?H:%<:#$use64bitint USE_64_BIT_INT /**/
?H:%<:#endif
?H:%<:#ifndef USE_64_BIT_ALL
?H:%<:#$use64bitall USE_64_BIT_ALL /**/
?H:%<:#endif
?H:.
?INIT:archname64="
?LINT:extern ccflags
?LINT:use usemorebits
?LINT:extern use64bits
?LINT:extern uselonglong
?LINT:extern uselonglongs
?LINT:extern use64bitints
?LINT:extern use64bitsint
?LINT:extern use64bitsall
?T:libcquad
?F:!try
?F:!use64bitint.cbu
?F:!use64bitall.cbu
: Do we want 64bit support
case "$uselonglong" in
"$define"|true|[yY]*)
cat <<EOM >&4

*** Configure -Duselonglong is deprecated, using -Duse64bitint instead.
EOM
use64bitint="$define"
;;
esac
case

```

```
"$use64bits" in
"$define"|true|[yY]*)
cat <<EOM >&4
```

*** Configure -Duse64bits is deprecated, using -Duse64bitint instead.

```
EOM
use64bitint="$define"
;;
esac
case "$use64bitints" in
"$define"|true|[yY]*)
cat <<EOM >&4
```

*** There is no Configure -Duse64bitints, using -Duse64bitint instead.

```
EOM
use64bitint="$define"
;;
esac
case "$use64bitsint" in
"$define"|true|[yY]*)
cat <<EOM >&4
```

*** There is no Configure -Duse64bitsint, using -Duse64bitint instead.

```
EOM
use64bitint="$define"
;;
esac
case "$uselongs" in
"$define"|true|[yY]*)
cat <<EOM >&4
```

*** There is no Configure -Duselongs, using -Duse64bitint instead.

```
EOM
use64bitint="$define"
;;
esac
case "$use64bitsall" in
"$define"|true|[yY]*)
cat <<EOM >&4
```

*** There is no Configure -Duse64bitsall, using -Duse64bitall instead.

```
EOM
use64bitall="$define"
;;
esac
```

```
case "$ccflags" in
*-DUSE_LONG_LONG*|*-DUSE_64_BIT_INT*|*-DUSE_64_BIT_ALL*) use64bitint="$define";;
```

```

esac
case "$use64bitall" in
"$define"|true|[yY]*)
use64bitint="$define" ;;
esac

```

```

case "$longsize" in
8) cat <<EOM

```

You have natively 64-bit long integers.

```

EOM
val="$define"
;;
*) case "$use64bitint" in
"$define"|true|[yY]*) dflt='y';;
*) dflt='n';;
esac
case "$d_quad" in
"$define") ;;
*) dflt='n' ;;
esac
cat <<EOM

```

Perl can be built to take advantage of 64-bit integer types on some systems. To do so, Configure can be run with `-Duse64bitint`. Choosing this option will most probably introduce binary incompatibilities.

If this doesn't make any sense to you, just accept the default `'$dflt'`. (The default has been chosen based on your configuration.)

```

EOM
rp='Try to use 64-bit integers, if available?'
./myread
case "$ans" in
[yY]*) val="$define" ;;
*) val="$undef" ;;
esac
;;
esac
set use64bitint
eval $setvar

case "$use64bitall" in
"$define"|true|[yY]*) dflt='y' ;;
*) case "$longsize" in
8) dflt='y' ;;
*) dflt='n' ;;
esac
;;

```

```
esac
cat <<EOM
```

You may also

choose to try maximal 64-bitness. It means using as much 64-bitness as possible on the platform. This in turn means even more binary incompatibilities. On the other hand, your platform may not have any more 64-bitness available than what you already have chosen.

If this doesn't make any sense to you, just accept the default '\$dflt'. (The default has been chosen based on your configuration.)

EOM

```
rp="Try to use maximal 64-bit support, if available?"
. ./myread
case "$ans" in
[yY]*) val="$define" ;;
*)    val="$undef" ;;
esac
set use64bitall
eval $setvar
case "$use64bitall" in
"$define")
case "$use64bitint" in
"$undef")
cat <<EOM
```

Since you have chosen a maximally 64-bit build, I'm also turning on the use of 64-bit integers.

EOM

```
use64bitint="$define" ;;
esac
;;
esac
```

```
: Look for a hint-file generated 'call-back-unit'. If the
: user has specified that a 64-bit perl is to be built,
: we may need to set or change some other defaults.
if $test -f use64bitint.cbu; then
echo "Your
platform has some specific hints regarding 64-bit integers, using them..."
. ./use64bitint.cbu
fi
```

```
case "$use64bitint" in
"$define"|true[[yY]*)
: This test was common to all the OpenBSD forks, and seems harmless for
: other platforms:
echo " "
echo "Checking if your C library has broken 64-bit functions..." >&4
```

```

cat >try.c <<EOCP
#include <stdio.h>
typedef $uquadtype myULL;
int main (void)
{
    struct {
    double d;
    myULL u;
    } *p, test[] = {
    {4294967303.15, 4294967303ULL},
    {4294967294.2, 4294967294ULL},
    {4294967295.7, 4294967295ULL},
    {0.0, 0ULL}
    };
    for (p = test; p->u; p++) {
    myULL x = (myULL)p->d;
    if (x != p->u) {
        printf("buggy\n");
        return 0;
    }
    }
    printf("ok\n");
    return 0;
}
EOCP
set try
if eval $compile_ok; then
    libcquad=`$run ./try`
    echo "Your C library's 64-bit functions are $libcquad."
else
    echo "(I can't seem to compile the test program.)"
    echo "Assuming that your C library's 64-bit functions are ok."
    libcquad="ok"
fi
$rm_try

case
"$libcquad" in
    buggy*)
        cat >&4 <<EOM

```

```

*** You have a C library with broken 64-bit functions.
*** 64-bit support does not work reliably in this configuration.
*** Please rerun Configure without -Duse64bitint and/or -Dusemorebits.
*** Cannot continue, aborting.

```

```

EOM
exit 1

```

```

;;
esac
case "$longsize" in
4) case "$archname64" in
    ") archname64=64int ;;
    esac
    ;;
esac
;;
esac

```

```

: Look for a hint-file generated 'call-back-unit'. If the
: user has specified that a maximally 64-bit perl is to be built,
: we may need to set or change some other defaults.
if $test -f use64bitall.cbu; then
echo "Your platform has some specific hints regarding 64-bit builds, using them..."
. ./use64bitall.cbu
fi

```

```

case "$use64bitall" in
"$define"|true|[yY]*)
case "$longsize" in
4) case "$archname64" in
    "|64int) archname64=64all ;;
    esac
    ;;
esac
;;
esac

```

```

case "$d_quad:$use64bitint" in
$undef:$define)
cat >&4 <<EOF

```

```

*** You have chosen to use 64-bit
integers,
*** but none can be found.
*** Please rerun Configure without -Duse64bitint and/or -Dusemorebits.
*** Cannot continue, aborting.

```

```

EOF
exit 1
;;
esac

```

Found in path(s):

```

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/perl/use64bits.U

```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: libdbm.U 1 2006-08-24 12:32:52Z rmanfredi $
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: $Log: libdbm.U,v $
?RCS: Revision 3.0.1.1 1997/02/28 15:56:57 ram
?RCS: patch61: replaced .a with $_a all over the place
?RCS:
?RCS: Revision 3.0 1993/08/18 12:08:58 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:libdbm: test Loc libpth _a
?MAKE: -pick add $@ %<
?S:libdbm:
?S: This variable contains the argument to pass to the loader in order
?S: to get the dbm library routines. If there is no dbm or ndbm
?S: library, it is null.
?S:.
?T:xxx
:
see if we should include -ldbm
echo " "
if $test -r /usr/lib/libndbm$_a || $test -r /usr/local/lib/libndbm$_a ; then
echo "-ldbm found." >&4
libdbm='-ldbm'
elif $test -r /usr/lib/libdbm$_a || $test -r /usr/local/lib/libdbm$_a ; then
echo "-ldbm found." >&4
libdbm='-ldbm'
else
xxx=`./loc libdbm$_a x $libpth`
case "$xxx" in
x)
echo "No dbm library found." >&4
libdbm=""
;;
*)
echo "DBM library found in $xxx." >&4
libdbm="$xxx"
;;
esac
```

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/libdbm.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 2000 Jarkko Hietaniemi

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?MAKE:d_fp_class: Inlibc

?MAKE: -pick add \$@ %<

?S:d_fp_class:

?S: This variable conditionally defines the HAS_FP_CLASS symbol, which

?S: indicates to the C program that the fp_class() routine is available.

?S:.

?C:HAS_FP_CLASS:

?C: This symbol, if defined, indicates that the fp_class routine is

?C: available to classify doubles. Available for example in Digital UNIX.

?C: The returned values are defined in <math.h> and are:

?C:

?C: FP_SNAN Signaling NaN (Not-a-Number)

?C: FP_QNAN Quiet NaN (Not-a-Number)

?C: FP_POS_INF +infinity

?C: FP_NEG_INF -infinity

?C: FP_POS_NORM Positive normalized

?C: FP_NEG_NORM Negative normalized

?C: FP_POS_DENORM Positive denormalized

?C: FP_NEG_DENORM
Negative denormalized

?C: FP_POS_ZERO +0.0 (positive zero)

?C: FP_NEG_ZERO -0.0 (negative zero)

?C:.

?H:#\$d_fp_class HAS_FP_CLASS /**/

?H:.

?LINT:set d_fp_class

: see if fp_class exists

set fp_class d_fp_class

eval \$inlibc

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_fp_class.U

No license file was found, but licenses were detected in source scan.

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?MAKE:d_fmin: Inlibc

?MAKE: -pick add \$@ %<

?S:d_fmin:

?S: This variable conditionally defines the HAS_FMIN symbol, which

?S: indicates to the C program that the fmin() routine is available.

?S:.

?C:HAS_FMIN:

?C: This symbol, if defined, indicates that the fmin routine is

?C: available to do the minimum function.

?C:.

?H:#\$d_fmin HAS_FMIN /**/

?H:.

?LINT:set d_fmin

: see if fmin exists

set fmin d_fmin

eval \$inlibc

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_fmin.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: vendorarch.U,v 1.1 1999/07/08 18:32:57 doughera Exp doughera \$

?RCS:

?RCS: Copyright (c) 1999, Andy Dougherty

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 3.0.

?RCS:

?RCS: \$Log: vendorarch.U,v \$

?RCS: Revision 1.1 1999/07/08 18:32:57 doughera

?RCS: Initial revision

?RCS:

?MAKE:d_vendorarch vendorarch vendorarchexp installvendorarch: sed Getfile \

Setprefixvar Oldconfig Prefixit archname vendorlib vendorprefix test

?MAKE: -pick add \$@ %<

?Y:TOP

?S:vendorarch:

?S: This variable contains the value of the PERL_VENDORARCH symbol.

?S: It may have a ~ on the front.

?S: The standard distribution will put nothing in this directory.

?S: Vendors
 who distribute perl may wish to place their own

?S: architecture-dependent modules and extensions in this directory with

?S: MakeMaker Makefile.PL INSTALLDIRS=vendor

?S: or equivalent. See INSTALL for details.

?S:.

?S:vendorarchexp:

?S: This variable is the ~name expanded version of vendorarch, so that you

?S: may use it directly in Makefiles or shell scripts.

?S:.

?D:installvendorarch="

?S:installvendorarch:

?S: This variable is really the same as vendorarchexp but may differ on

?S: those systems using AFS. For extra portability, only this variable

?S: should be used in makefiles.

?S:.

?S:d_vendorarch:

?S: This variable conditionally defined PERL_VENDORARCH.

?S:.

?C:PERL_VENDORARCH:

?C: If defined, this symbol contains the name of a private library.

?C: The library is private in the sense that it needn't be in anyone's

?C: execution path, but it should be accessible by the world.

?C: It may have a ~ on the front.

?C: The standard distribution will put nothing in this
 directory.

?C: Vendors who distribute perl may wish to place their own

?C: architecture-dependent modules and extensions in this directory with

?C: MakeMaker Makefile.PL INSTALLDIRS=vendor

?C: or equivalent. See INSTALL for details.

?C:.

?C:PERL_VENDORARCH_EXP:

?C: This symbol contains the ~name expanded version of PERL_VENDORARCH, to be used

?C: in programs that are not prepared to deal with ~ expansion at run-time.

?C:.

?H:#\$d_vendorarch PERL_VENDORARCH "\$vendorarch" /**/
 ?H:#\$d_vendorarch PERL_VENDORARCH_EXP "\$vendorarchexp" /**/
 ?H:.

?LINT:change prefixvar

?LINT:set installvendorarch

: Set the vendorarch variables

case "\$vendorprefix" in

*) d_vendorarch="\$undef"

vendorarch="

vendorarchexp="

;;

*) d_vendorarch="\$define"

```

: determine where vendor-supplied architecture-dependent libraries go.
: vendorlib default is /usr/local/lib/perl5/vendor_perl/$version
: vendorarch default is /usr/local/lib/perl5/vendor_perl/$version/$archname
: vendorlib may have an optional trailing
/share.
case "$vendorarch" in
") dflt=`echo $vendorlib | $sed 's,/share$,,'`
  dflt="$dflt/$archname"
;;
*) dflt="$vendorarch" ;;
esac
fn=d~+
rp='Pathname for vendor-supplied architecture-dependent files?'
./getfile
vendorarch="$ans"
vendorarchexp="$ansexp"
;;
esac
prefixvar=vendorarch
./installprefix
if $test X"$vendorarch" = X"$vendorlib"; then
  d_vendorarch="$undef"
else
  d_vendorarch="$define"
fi

```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/installdirs/vendorarch.U
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: d_getpwent.U,v \$

?RCS: Revision 3.0 1993/08/18 12:06:17 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?MAKE:d_getpwent: Csym Setvar

?MAKE: -pick add \$@ %<

?S:d_getpwent:

?S: This variable conditionally defines the HAS_GETPWENT symbol, which

?S: indicates to the C program that it should use the getpwent()

?S: routine instead of the getpw() routine.

?S:.

?C:HAS_GETPWENT (GETPWENT):

?C: This symbol, if defined, indicates that the getpwent() routine

?C: should be used instead of the getpw()

routine.

?C:.

?H:#\$d_getpwent HAS_GETPWENT /**/

?H:.

?LINT:set d_getpwent

: see if there is a getpwent

echo " "

if set getpwent val -f d_getpwent; eval \$csym; \$val; then

echo "getpwent() found." >&4

val="\$define"

else

echo "No getpwent() found -- will use getpw() instead." >&4

val="\$undef"

fi

set d_getpwent

eval \$setvar

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/d_getpwent.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_gethbynm.U 1 2006-08-24 12:32:52Z rmanfredi \$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: d_gethbynm.U,v \$

?RCS: Revision 3.0 1993/08/18 12:06:08 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?MAKE:d_gethbyname: Inlibc

?MAKE:-pick add \$@ %<

?S:d_gethbyname (d_gethbynm d_gethstby):

?S: This variable conditionally defines the HAS_GETHOSTBYNAME symbol, which

?S: indicates to the C program that the gethostbyname() routine is available

?S: to look up host names in some data base or other.

?S:.

?C:HAS_GETHOSTBYNAME (GETHOSTBYNAME):

?C: This

symbol, if defined, indicates that the gethostbyname() routine is

?C: available to look up host names in some data base or other.

?C:.

?H:#\$d_ gethbyname HAS_GETHOSTBYNAME /**/

?H:.

?LINT:set d_ gethbyname

: see if gethostbyname exists

set gethostbyname d_ gethbyname

eval \$inlibc

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/modified/d_ gethbynm.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: i_termio.U,v \$

?RCS: Revision 3.0.1.4 1994/10/29 16:20:54 ram

?RCS: patch36: call ./usg and ./Cpplib explicitly instead of relying on PATH

?RCS:

?RCS: Revision 3.0.1.3 1994/08/29 16:26:38 ram

?RCS: patch32: don't include all three I_* symbols in config.h

?RCS: patch32: (had forgotten to undo this part last time)

?RCS:

?RCS: Revision 3.0.1.2 1994/05/13 15:25:03 ram

?RCS: patch27: undone ADO's fix in previous patch since it was useless

?RCS:

?RCS: Revision 3.0.1.1 1994/05/06 15:05:23

ram

?RCS: patch23: now include all three defines in config.h (ADO)

?RCS:

?RCS: Revision 3.0 1993/08/18 12:08:44 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?MAKE:i_termio i_sgty i_termios: test Inlibc Cpplib Guess Setvar Findhdr Warn

```

?MAKE: -pick add $@ %<
?S:i_termio:
?S: This variable conditionally defines the I_TERMIO symbol, which
?S: indicates to the C program that it should include <termio.h> rather
?S: than <sgtty.h>.
?S:.
?S:i_termios:
?S: This variable conditionally defines the I_TERMIOS symbol, which
?S: indicates to the C program that the POSIX <termios.h> file is
?S: to be included.
?S:.
?S:i_sgtty:
?S: This variable conditionally defines the I_SGTTY symbol, which
?S: indicates to the C program that it should include <sgtty.h> rather
?S: than <termio.h>.
?S:.
?C:I_TERMIO:
?C: This symbol, if defined, indicates that the program should include
?C: <termio.h> rather than <sgtty.h>. There are also differences in
?C: the ioctl() calls that depend on the value of
?C: this symbol.
?C:.
?C:I_TERMIOS:
?C: This symbol, if defined, indicates that the program should include
?C: the POSIX termios.h rather than sgtty.h or termio.h.
?C: There are also differences in the ioctl() calls that depend on the
?C: value of this symbol.
?C:.
?C:I_SGTTY:
?C: This symbol, if defined, indicates that the program should include
?C: <sgtty.h> rather than <termio.h>. There are also differences in
?C: the ioctl() calls that depend on the value of this symbol.
?C:.
?H:#$i_termio I_TERMIO /**/
?H:#$i_termios I_TERMIOS /**/
?H:#$i_sgtty I_SGTTY /**/
?H:.
?T:val2 val3
?LINT:set i_termio i_sgtty i_termios
: see if this is a termio system
val="$undef"
val2="$undef"
val3="$undef"
?X: Prefer POSIX-approved termios.h over all else
if $test `./findhdr termios.h`; then
set tcsetattr i_termios
eval $inlibc
val3="$i_termios"

```

```

fi
echo " "
case "$val3" in
"$define") echo "You have POSIX termios.h... good!" >&4;;
*) if ./Cpplib.py; then
case "`/bin/universe`" in
ucb) if $test `./findhdr
sgtty.h`; then
val2="$define"
echo "<sgtty.h> found." >&4
else
echo "System is pyramid with BSD universe."
./warn "<sgtty.h> not found--you could have problems."
fi;;
*) if $test `./findhdr termio.h`; then
val="$define"
echo "<termio.h> found." >&4
else
echo "System is pyramid with USG universe."
./warn "<termio.h> not found--you could have problems."
fi;;
esac
?X: Start with USG to avoid problems if both usg/bsd was guessed
elif ./usg; then
if $test `./findhdr termio.h`; then
echo "<termio.h> found." >&4
val="$define"
elif $test `./findhdr sgtty.h`; then
echo "<sgtty.h> found." >&4
val2="$define"
else
./warn "Neither <termio.h> nor <sgtty.h> found--cross fingers!"
fi
else
if $test `./findhdr sgtty.h`; then
echo "<sgtty.h> found." >&4
val2="$define"
elif $test `./findhdr termio.h`; then
echo "<termio.h> found." >&4
val="$define"
else
./warn "Neither <sgtty.h> nor <termio.h> found--cross
fingers!"
fi
fi;;
esac
set i_termio; eval $setvar
val=$val2; set i_sgtty; eval $setvar

```

```
val=$val3; set i_termios; eval $setvar
```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/i_termio.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: d_fd_set.U,v 3.0.1.3 1997/02/28 15:33:16 ram Exp $
```

```
?RCS:
```

```
?RCS: Copyright (c) 1991-1993, Raphael Manfredi
```

```
?RCS:
```

```
?RCS: You may redistribute only under the terms of the Artistic License,
```

```
?RCS: as specified in the README file that comes with the distribution.
```

```
?RCS: You may reuse parts of this distribution only within the terms of
```

```
?RCS: that same Artistic License; a copy of which may be found at the root
```

```
?RCS: of the source tree for dist 3.0.
```

```
?RCS:
```

```
?RCS: $Log: d_fd_set.U,v $
```

```
?RCS: Revision 3.0.1.3 1997/02/28 15:33:16 ram
```

```
?RCS: patch61: added ?F: metalint hint
```

```
?RCS:
```

```
?RCS: Revision 3.0.1.2 1994/06/20 06:57:23 ram
```

```
?RCS: patch30: extended scope for fd_set checks (ADO)
```

```
?RCS:
```

```
?RCS: Revision 3.0.1.1 1994/01/24 14:06:27 ram
```

```
?RCS: patch16: comments for HAS_FD_* symbols were not consistent
```

```
?RCS:
```

```
?RCS: Revision 3.0 1993/08/18 12:06:02 ram
```

```
?RCS: Baseline for dist 3.0 netwide release.
```

```
?RCS:
```

```
?MAKE:d_fd_set d_fd_macros
```

```
d_fds_bits: Compile cat rm_try Oldconfig \
```

```
d_socket i_systime i_sysselect i_stdlib run
```

```
?MAKE: -pick add $@ %<
```

```
?S:d_fd_set:
```

```
?S: This variable contains the eventual value of the HAS_FD_SET symbol,
```

```
?S: which indicates if your C compiler knows about the fd_set typedef.
```

```
?S:.
```

```
?S:d_fd_macros:
```

```
?S: This variable contains the eventual value of the HAS_FD_MACROS symbol,
```

```
?S: which indicates if your C compiler knows about the macros which
```

```
?S: manipulate an fd_set.
```

```
?S:.
```

```
?S:d_fds_bits:
```

```
?S: This variable contains the eventual value of the HAS_FDS_BITS symbol,
```

```
?S: which indicates if your fd_set typedef contains the fds_bits member.
```

```
?S: If you have an fd_set typedef, but the dweebs who installed it did
```

```
?S: a half-fast job and neglected to provide the macros to manipulate
```

?S: an fd_set, HAS_FDS_BITS will let us know how to fix the gaffe.

?S:.

?C:HAS_FD_SET:

?C: This symbol, when defined, indicates presence of the fd_set typedef

?C: in <sys/types.h>

?C:.

?C:HAS_FD_MACROS:

?C: This symbol, when defined,

indicates presence of the macros used to

?C: manipulate an fd_set.

?C:.

?C:HAS_FDS_BITS:

?C: This symbol, when defined, indicates presence of the fds_bits member in

?C: fd_set. This knowledge is useful if fd_set is available but the macros

?C: aren't.

?C:.

?H:#\$d_fd_set HAS_FD_SET /**/

?H:#\$d_fd_macros HAS_FD_MACROS /**/

?H:#\$d_fds_bits HAS_FDS_BITS /**/

?H:.

?F:!try

: check for fd_set items

\$cat <<EOM

Checking to see how well your C compiler handles fd_set and friends ...

EOM

?X: The FD_SET macros can be in strange places. On some SysV-based

?X: systems, they are in <sys/bsdtypes.h>, which is included (perhaps)

?X: by <sys/socket.h>. We won't force people to include

?X: <sys/bsdtypes.h> because it might introduce other

?X: incompatibilities.

\$cat >try.c <<EOCP

```
#$i_stdlib I_STDLIB
```

```
#ifdef I_STDLIB
```

```
#include <stdlib.h>
```

```
#endif
```

```
#$i_systime I_SYS_TIME
```

```
#$i_sysselect I_SYS_SELECT
```

```
#$d_socket HAS_SOCKET
```

```
#include <sys/types.h>
```

```
#ifdef HAS_SOCKET
```

```
#include <sys/socket.h> /* Might include <sys/bsdtypes.h>
```

```
*/
```

```
#endif
```

```
#ifdef I_SYS_TIME
```

```
#include <sys/time.h>
```

```
#endif
```

```
#ifdef I_SYS_SELECT
```

```

#include <sys/select.h>
#endif
int main() {
    fd_set fds;

#ifdef TRYBITS
    if(fds.fds_bits);
#endif

#if defined(FD_SET) && defined(FD_CLR) && defined(FD_ISSET) && defined(FD_ZERO)
    exit(0);
#else
    exit(1);
#endif
}
EOCP
set try -DTRYBITS
if eval $compile; then
    d_fds_bits="$define"
    d_fd_set="$define"
    echo "Well, your system knows about the normal fd_set typedef..." >&4
    if $run ./try; then
        echo "and you have the normal fd_set macros (just as I'd expect)." >&4
        d_fd_macros="$define"
    else
        $cat >&4 <<'EOM'
but not the normal fd_set macros! Gaaack! I'll have to cover for you.
EOM
    d_fd_macros="$undef"
    fi
    else
        $cat <<'EOM'
Hmm, your compiler has some difficulty with fd_set. Checking further...
EOM
    set try
    if eval $compile; then
        d_fds_bits="$undef"
        d_fd_set="$define"
        echo "Well, your system has some sort of fd_set available..." >&4
        if $run ./try; then
            echo "and you have the normal
fd_set macros." >&4
            d_fd_macros="$define"
        else
            $cat <<'EOM'
but not the normal fd_set macros! Gross! More work for me...
EOM
            d_fd_macros="$undef"

```

```

fi
else
echo "Well, you got zip. That's OK, I can roll my own fd_set stuff." >&4
d_fd_set="$sundef"
d_fds_bits="$sundef"
d_fd_macros="$sundef"
fi
fi
$rm_try

```

Found in path(s):

```

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/compline/d_fd_set.U

```

No license file was found, but licenses were detected in source scan.

```

?RCS: $Id: d_alarm.U 1 2006-08-24 12:32:52Z rmanfredi $
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: Original Author: Andy Dougherty <doughera@lafcol.lafayette.edu>
?RCS:
?RCS: $Log: d_alarm.U,v $
?RCS: Revision 3.0.1.1 1994/08/29 16:06:58 ram
?RCS: patch32: created by ADO
?RCS:
?MAKE:d_alarm: Inlibc
?MAKE: -pick add $@ %<
?S:d_alarm:
?S: This variable conditionally defines the HAS_ALARM symbol, which
?S: indicates to the C program that the alarm() routine is available.
?S:.
?C:HAS_ALARM :
?C: This symbol, if defined, indicates that the alarm routine is
?C: available.
?C:.
?H:#$d_alarm
HAS_ALARM /**/
?H:.
?LINT:set d_alarm
: see if alarm exists
set alarm d_alarm
eval $inlibc

```

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/d_alarm.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_gethent.U 1 2006-08-24 12:32:52Z rmanfredi \$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: d_gethent.U,v \$

?RCS: Revision 3.0 1993/08/18 12:06:09 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?MAKE:d_gethent: Inlibc

?MAKE: -pick add \$@ %<

?S:d_gethent:

?S: This variable conditionally defines HAS_GETHOSTENT if gethostent() is

?S: available to look up host names in some data base or another.

?S:.

?C:HAS_GETHOSTENT:

?C: This symbol, if defined, indicates that the gethostent() routine is

?C: available to look up host names in some
data base or another.

?C:.

?H:#\$d_gethent HAS_GETHOSTENT /**/

?H:.

?LINT:set d_gethent

: see if gethostent exists

set gethostent d_gethent

eval \$inlibc

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/modified/d_gethent.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: d_flexfnam.U,v \$

?RCS: Revision 3.0 1993/08/18 12:06:04 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?MAKE:d_flexfnam: cat rm test Setvar

?MAKE: -pick add \$@ %<

?S:d_flexfnam:

?S: This variable conditionally defines the FLEXFILENAMES symbol, which

?S: indicates that the system supports filenames longer than 14 characters.

?S:.

?C:FLEXFILENAMES:

?C: This symbol, if defined, indicates that the system supports filenames

?C: longer than 14 characters.

?C:.

?H:#\$d_flexfnam FLEXFILENAMES /**/

?H:.

?T:first

second

?LINT:set d_flexfnam

: see if we can have long filenames

echo " "

?X:

?X: We have to test in both /tmp and . because of NFS (remote server may allow

?X: long filenames while the local filesystem cannot support them). If at least

?X: one of those file systems cannot support long filenames, then we assume the

?X: whole system can't.

?X:

```

rmlist="$rmlist /tmp/cf$$"
$test -d /tmp/cf$$ || mkdir /tmp/cf$$
first=123456789abcdef
second=/tmp/cf$$/$first
$rm -f $first $second
if (echo hi >$first) 2>/dev/null; then
if $test -f 123456789abcde; then
echo 'You cannot have filenames longer than 14 characters. Sigh.'>&4
val="$undef"
else
if (echo hi >$second) 2>/dev/null; then
if $test -f /tmp/cf$$/123456789abcde; then
$cat <<'EOM'
```

That's peculiar... You can have filenames longer than 14 characters, but only on some of the filesystems. Maybe you are using NFS. Anyway, to avoid problems I shall consider your system cannot support long filenames at all.

EOM

```
val="$undef"  
else  
echo  
'You can have filenames longer than 14 characters.' >&4  
val="$define"  
fi  
else  
$cat <<'EOM'
```

How confusing! Some of your filesystems are sane enough to allow filenames longer than 14 characters but some others like /tmp can't even think about them. So, for now on, I shall assume your kernel does not allow them at all.

EOM

```
val="$undef"  
fi  
fi  
else  
$cat <<'EOM'
```

You can't have filenames longer than 14 chars. You can't even think about them!

EOM

```
val="$undef"  
fi  
set d_flexfnam  
eval $setvar  
$rm -rf /tmp/cf$$ 123456789abcde*
```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/d_flexfnam.U
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_sitecustomize.U,v \$

?RCS:

?RCS: Copyright (c) 2005-2006 H.Merijn Brand

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?RCS: \$Log: d_sitecustomize.U,v \$

?RCS:

?MAKE:usesitecustomize: Oldconfig Setvar

?MAKE: -pick add \$@ %<

?S:usesitecustomize:

?S: This variable is set to true when the user requires a mechanism that

?S: allows the sysadmin to add entries to @INC at runtime. This variable

?S: being set, makes perl run '\$sitelib/sitecustomize.pl' at startup.

?S:.

?C:USE_SITECUSTOMIZE:

?C: This symbol, if defined, indicates that sitecustomize should

?C: be used.

?C:.

?H:??<:@if USE_SITECUSTOMIZE

?H:??<:#ifndef USE_SITECUSTOMIZE

?H:??<:#\$usesitecustomize USE_SITECUSTOMIZE /**/

?H:??<:#endif

?H:??<:@end

?H:.

: Check if site customization support was requested

case "\$usesitecustomize" in

 \$define|true|[Yy]*)

 usesitecustomize="\$define"

;;

 *)

 usesitecustomize="\$undef"

;;

 esac

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_sitecustomize.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_endgrent.U,v \$

?RCS:

?RCS: Copyright (c) 1998 Andy Dougherty

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?RCS: \$Log: d_endgrent.U,v \$

?RCS:

?MAKE:d_endgrent: Inlibc

?MAKE: -pick add \$@ %<

?S:d_endgrent:

?S: This variable conditionally defines the HAS_ENDGRENT symbol, which

?S: indicates to the C program that the endgrent() routine is available

?S: for sequential access of the group database.

?S:.

?C:HAS_ENDGRENT:

?C: This symbol, if defined, indicates that the getgrent routine is

?C: available for finalizing sequential access of the group database.

?C:.

?H:#\$d_endgrent HAS_ENDGRENT /**/

?H:.

?LINT:set d_endgrent

: see if endgrent exists

```
set endgrent d_endgrent
eval $inlibc
```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/modified/d_endgrent.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: i_mqueue.U,v $
```

```
?RCS:
```

```
?RCS: Copyright (c) 1999 Jarkko Hietaniemi
```

```
?RCS:
```

```
?RCS: You may distribute under the terms of either the GNU General Public
```

```
?RCS: License or the Artistic License, as specified in the README file.
```

```
?RCS:
```

```
?MAKE:i_mqueue: Inhdr Hasfield
```

```
?MAKE: -pick add $@ %<
```

```
?S:i_mqueue:
```

```
?S: This variable conditionally defines the I_MQUEUE symbol, and indicates
```

```
?S: whether a C program should include <mqueue.h>.
```

```
?S:.
```

```
?C:I_MQUEUE:
```

```
?C: This symbol, if defined, indicates that <mqueue.h> exists and
```

```
?C: should be included.
```

```
?C:.
```

```
?H:#$i_mqueue I_MQUEUE /**/
```

```
?H:.
```

```
?LINT:set i_mqueue
```

```
: see if this is a mqueue.h system
```

```
set mqueue.h i_mqueue
```

```
eval $inhdr
```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/perl/i_mqueue.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id$
```

```
?RCS:
```

```
?RCS: Copyright (c) 1998 Jarkko Hietaniemi
```

```
?RCS:
```

```
?RCS: You may distribute under the terms of either the GNU General Public
```

```
?RCS: License or the Artistic License, as specified in the README file.
```

```
?RCS:
```

```
?MAKE:d_ftello: Inlibc longsize
```

```
?MAKE: -pick add $@ %<
```

```
?S:d_ftello:
```

```
?S: This variable conditionally defines the HAS_FTELLO symbol, which
```

?S: indicates to the C program that the ftello() routine is available.

?S:.

?C:HAS_FTELLO:

?C: This symbol, if defined, indicates that the ftello routine is

?C: available to ftell beyond 32 bits (useful for ILP32 hosts).

?C:.

?H:#\$d_ftello HAS_FTELLO /**/

?H:.

?LINT:set d_ftello

: see if ftello exists

set ftello d_ftello

eval \$inlibc

case "\$longsize" in

8) echo "(Your long is 64 bits, so you could use ftell.)" ;;

esac

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_ftello.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: usenm.U,v 3.0.1.1 1997/02/28 16:26:40 ram Exp \$

?RCS:

?RCS: Copyright (c) 1991-1993, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 3.0.

?RCS:

?RCS: \$Log: usenm.U,v \$

?RCS: Revision 3.0.1.1 1997/02/28 16:26:40 ram

?RCS: patch61: don't use nm with the GNU C library

?RCS: patch61: added support for Linux shared libs

?RCS:

?RCS: Revision 3.0 1993/08/18 12:09:57 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?MAKE:usenm runnm nm_opt nm_so_opt: cat test Myread Oldconfig myuname grep \
nm d_gnulibc osname egrep rsrc

?MAKE: -pick add \$@ %<

?S:usenm:

?S: This variable contains 'true' or 'false' depending
whether the

?S: nm extraction is wanted or not.

?S:.

?S:runnm:

?S: This variable contains 'true' or 'false' depending whether the
 ?S: nm extraction should be performed or not, according to the value
 ?S: of usenm and the flags on the Configure command line.
 ?S:.
 ?S:nm_opt:
 ?S: This variable holds the options that may be necessary for nm.
 ?S:.
 ?S:nm_so_opt:
 ?S: This variable holds the options that may be necessary for nm
 ?S: to work on a shared library but that can not be used on an
 ?S: archive library. Currently, this is only used by Linux, where
 ?S: nm --dynamic is *required* to get symbols from an ELF library which
 ?S: has been stripped, but nm --dynamic is *fatal* on an archive library.
 ?S: Maybe Linux should just always set usenm=false.
 ?S:.

: see if nm is to be used to determine whether a symbol is defined or not

?X: If there is enough inquiries, it might be worth to wait for the nm

?X: extraction. Otherwise, the C compilations might be a better deal.

?X:

?X: Don't bother if we're
 using GNU libc -- skimo

?LINT:extern PASE

case "\$usenm" in

")

dflt="

case "\$d_gnulibc" in

"\$define")

echo " "

echo "nm probably won't work on the GNU C Library." >&4

dflt=n

::

esac

case "\$dflt" in

")

if \$test "\$osname" = aix -a "\$PASE" != "Xdefine" -a ! -f /lib/syscalls.exp; then

echo " "

echo "Whoops! This is an AIX system without /lib/syscalls.exp!" >&4

echo "'nm' won't be sufficient on this system." >&4

dflt=n

fi

::

esac

case "\$dflt" in

") dflt=`\$egrep 'inlibc|csym' \$src/Configure | wc -l 2>/dev/null`

if \$test \$dflt -gt 20; then

dflt=y

else

dflt=n

```

fi
;;
esac
;;
*)
case "$usenm" in
true|$define) dflt=y;;
*) dflt=n;;
esac
;;
esac
$cat <<EOM

```

I can use \$nm to extract the symbols from your C libraries. This is a time consuming task which may generate huge output on the disk (up to 3 megabytes) but that should make the symbols extraction faster. The alternative is to skip the 'nm' extraction part and to compile a small test program instead to determine whether each symbol is present. If you have a fast C compiler and/or if your 'nm' output cannot be parsed, this may be the best solution.

You probably shouldn't let me use 'nm' if you are using the GNU C Library.

```

EOM
rp="Shall I use $nm to extract C symbols from the libraries?"
./myread
case "$ans" in
[Nn]*) usenm=false;;
*) usenm=true;;
esac

```

?X: Name extraction is to be run if 'nm' usage is wanted and if no -r flag
?X: was provided to configure (in which case we simply re-use the previous
?X: values).

```

runnm=$usenm
case "$reuseval" in
true) runnm=false;;
esac

```

```

: nm options which may be necessary
case "$nm_opt" in
") if $test -f /mach_boot; then
nm_opt="#" # Mach
elif $test -d /usr/ccs/lib; then
nm_opt='-p' # Solaris (and SunOS?)
elif $test -f /dgux; then
nm_opt='-p' # DG-UX

```

```
elif $test -f /lib64/rld; then
  nm_opt='-p' # 64-bit Irix
else
  nm_opt=""
fi;;
esac
```

: nm options which may be necessary for shared libraries but illegal

: for archive

libraries. Thank you, Linux.

```
case "$nm_so_opt" in
```

```
) case "$myuname" in
```

```
*linux*|gnu*)
```

```
if $nm --help | $grep 'dynamic' > /dev/null 2>&1; then
```

```
  nm_so_opt='--dynamic'
```

```
fi
```

```
::
```

```
esac
```

```
::
```

```
esac
```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-  
debian-perl-5.26.1/U/modified/usenm.U
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_byacc.U 1 2006-08-24 12:32:52Z rmanfredi \$

?RCS:

?RCS: Copyright (c) 1996, Andy Dougherty

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic Licence,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic Licence; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: d_byacc.U,v \$

?RCS: Revision 3.0.1.1 1997/02/28 15:31:14 ram

?RCS: patch61: created

?RCS:

?MAKE:d_byacc: byacc Setvar

?MAKE: -pick add \$@ %<

?S:d_byacc:

?S: This variable indicates whether byacc is available.

?S: If the user has specified 'portability', then Makefile.SH

?S: sees \$byacc='byacc' whether or not the user actually has

?S: byacc. This variable allows us to determine in a makefile

```
?S: if we really
have byacc.
?S:.
?LINT:set d_byacc
: Check if we really have byacc
case "$byacc" in
"|"byacc') val="$undef" ;;
*) val="$define" ;;
esac
set d_byacc
eval $setvar
```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/d_byacc.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id$
?RCS:
?RCS: Copyright (c) 1999, Jarkko Hietaniemi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 3.0.
?RCS:
?MAKE:d_shm_open: Inlibc
?MAKE: -pick add $@ %<
?S:d_shm_open:
?S: This variable conditionally defines HAS_SHM_OPEN if shm_open() is
?S: available to open a POSIX shared memory object.
?S:.
?C:HAS_SHM_OPEN:
?C: This symbol, if defined, indicates that the shm_open system call is
?C: available to open a POSIX shared memory object.
?C:.
?H:#$d_shm_open HAS_SHM_OPEN /**/
?H:.
?LINT:set d_shm_open
: see if shm_open exists
set shm_open d_shm_open
eval $inlibc
```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/perl/d_shm_open.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: d_getpwnam_r.U,v 0RCS:
?RCS: Copyright (c) 2002,2003 Jarkko Hietaniemi
?RCS:
?RCS: You may distribute under the terms of either the GNU General Public
?RCS: License or the Artistic License, as specified in the README file.
?RCS:
?RCS: Generated by the reentr.pl from the Perl 5.8 distribution.
?RCS:
?MAKE:d_getpwnam_r getpwnam_r_proto: Inlibc Protochk Hasproto i_systypes \
  usethreads i_pwd extern_C
?MAKE: -pick add $@ %<
?S:d_getpwnam_r:
?S: This variable conditionally defines the HAS_GETPWNAM_R symbol,
?S: which indicates to the C program that the getpwnam_r()
?S: routine is available.
?S:.
?S:getpwnam_r_proto:
?S: This variable encodes the prototype of getpwnam_r.
?S: It is zero if d_getpwnam_r is undef, and one of the
?S: REENTRANT_PROTO_T_ABC macros of reentr.h if d_getpwnam_r
?S: is defined.
?S:.
?C:HAS_GETPWNAM_R:
?C: This symbol, if defined, indicates that the getpwnam_r routine
?C: is available to
  getpwnam re-entrantly.
?C:.
?C:GETPWNAM_R_PROTO:
?C: This symbol encodes the prototype of getpwnam_r.
?C: It is zero if d_getpwnam_r is undef, and one of the
?C: REENTRANT_PROTO_T_ABC macros of reentr.h if d_getpwnam_r
?C: is defined.
?C:.
?H:#$d_getpwnam_r HAS_GETPWNAM_R /**/
?H:#define GETPWNAM_R_PROTO $getpwnam_r_proto /**/
?H:.
?T:try hdrs d_getpwnam_r_proto
: see if getpwnam_r exists
set getpwnam_r d_getpwnam_r
eval $inlibc
case "$d_getpwnam_r" in
"$define")
  hdrs="$i_systypes sys/types.h define stdio.h $i_pwd pwd.h"
  case "$d_getpwnam_r_proto:$usethreads" in
  ":define") d_getpwnam_r_proto=define
    set d_getpwnam_r_proto getpwnam_r $hdrs
```

```

eval $hasproto ;;
*) ;;
esac
case "$d_getpwnam_r_proto" in
define)
case "$getpwnam_r_proto" in
"|0) try='int getpwnam_r(const char*, struct passwd*, char*, size_t, struct passwd**);'
./prochck "$extern_C $try" $hdrs && getpwnam_r_proto=I_CSBWR ;;
esac
case "$getpwnam_r_proto" in
"|0) try='int getpwnam_r(const char*, struct passwd*,
char*, int, struct passwd**);'
./prochck "$extern_C $try" $hdrs && getpwnam_r_proto=I_CSBIR ;;
esac
case "$getpwnam_r_proto" in
"|0) try='struct passwd* getpwnam_r(const char*, struct passwd*, char*, int);'
./prochck "$extern_C $try" $hdrs && getpwnam_r_proto=S_CSBI ;;
esac
case "$getpwnam_r_proto" in
"|0) try='int getpwnam_r(const char*, struct passwd*, char*, int);'
./prochck "$extern_C $try" $hdrs && getpwnam_r_proto=I_CSBI ;;
esac
case "$getpwnam_r_proto" in
"|0) d_getpwnam_r=undef
    getpwnam_r_proto=0
    echo "Disabling getpwnam_r, cannot determine prototype." >&4 ;;
*) case "$getpwnam_r_proto" in
REENTRANT_PROTO*) ;;
*) getpwnam_r_proto="REENTRANT_PROTO_$getpwnam_r_proto" ;;
esac
echo "Prototype: $try" ;;
esac
;;
*) case "$susethreads" in
define) echo "getpwnam_r has no prototype, not using it." >&4 ;;
esac
d_getpwnam_r=undef
getpwnam_r_proto=0
;;
esac
;;
*) getpwnam_r_proto=0
;;
esac

```

Found in path(s):

```

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/threads/d_getpwnam_r.U

```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: rootid.U 1 2006-08-24 12:32:52Z rmanfredi $
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: $Log: rootid.U,v $
?RCS: Revision 3.0.1.1 1995/01/30 14:45:36 ram
?RCS: patch49: now only prints a single empty line when outputting something
?RCS:
?RCS: Revision 3.0 1993/08/18 12:09:42 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:rootid: sed
?MAKE: -pick add $@ %<
?S:rootid:
?S: This variable contains the eventual value of the ROOTID symbol,
?S: which is the uid of root.
?S:.
?C:ROOTID:
?C: This symbol contains the uid of root, normally
0.
?C:.
?H:#define ROOTID $rootid /**/
?H:.
: determine root id
rootid=`$sed -e "/^root:/{s/^[^:]*:[^:]*:([[:^:]]*).*$"/\1/" -e "q" -e "}" -e "d" </etc/passwd`
case "$rootid" in
") rootid=0 ;;
*) echo " "; echo "Root uid = $rootid" >&4 ;;
esac
```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/rootid.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id$
?RCS:
?RCS: Copyright (c) 1996, Andy Dougherty
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
```

?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: You may distribute under the terms of either the GNU General Public
?RCS: License or the Artistic License, as specified in the README file.
?RCS:
?RCS: \$Log: d_sigsetjmp.U,v \$
?RCS: Revision 3.0.1.1 1997/02/28 15:44:33 ram
?RCS: patch61: created
?RCS:
?MAKE:d_sigsetjmp: Setvar cat +cc +ccflags +ldflags libs rm
?MAKE: -pick add \$@ %<
?S:d_sigsetjmp:
?S: This variable conditionally defines the HAS_SIGSETJMP symbol,
?S: which indicates that the sigsetjmp() routine
is available to
?S: call setjmp() and optionally save the process's signal mask.
?S:.
?C:HAS_SIGSETJMP:
?C: This variable indicates to the C program that the sigsetjmp()
?C: routine is available to save the calling process's registers
?C: and stack environment for later use by siglongjmp(), and
?C: to optionally save the process's signal mask. See
?C: Sigjmp_buf, Sigsetjmp, and Siglongjmp.
?C:.
?C:Sigjmp_buf:
?C: This is the buffer type to be used with Sigsetjmp and Siglongjmp.
?C:.
?C:Sigsetjmp:
?C: This macro is used in the same way as sigsetjmp(), but will invoke
?C: traditional setjmp() if sigsetjmp isn't available.
?C: See HAS_SIGSETJMP.
?C:.
?C:Siglongjmp:
?C: This macro is used in the same way as siglongjmp(), but will invoke
?C: traditional longjmp() if siglongjmp isn't available.
?C: See HAS_SIGSETJMP.
?C:.
?H:%<:#\$d_sigsetjmp HAS_SIGSETJMP /**/
?H:%<:#ifdef HAS_SIGSETJMP
?H:%<:#define Sigjmp_buf sigjmp_buf
?H:%<:#define Sigsetjmp(buf,save_mask) sigsetjmp((buf),(save_mask))
?H:%<:#define
Siglongjmp(buf,retval) siglongjmp((buf),(retval))
?H:%<:#else

```

?H:?%<:#define Sigjmp_buf jmp_buf
?H:?%<:#define Sigsetjmp(buf,save_mask) setjmp((buf))
?H:?%<:#define Siglongjmp(buf,retval) longjmp((buf),(retval))
?H:?%<:#endif
?H:.
?W:%<:Sigjmp_buf Sigsetjmp Siglongjmp
?F:!set
?LINT:set d_sigsetjmp
: see if sigsetjmp exists
?X: We can't check for these symbols with Inlibc because sigsetjmp
?X: is (sometimes? always?) a macro under GCC
echo " "
case "$d_sigsetjmp" in
")
$cat >set.c <<'EOP'
#include <setjmp.h>
sigjmp_buf env;
int set = 1;
int main()
{
if (sigsetjmp(env,1))
exit(set);
set = 0;
siglongjmp(env, 1);
exit(1);
}
EOP
if $cc $ccflags $ldflags -o set set.c $libs > /dev/null 2>&1 ; then
if ./set >/dev/null 2>&1; then
echo "POSIX sigsetjmp found." >&4
val="$define"
else
$cat >&4 <<EOM
Uh-Oh! You have POSIX sigsetjmp and siglongjmp, but they do not work properly!!
I'll ignore them.
EOM
val="$undef"
fi
else
echo "sigsetjmp not found."
>&4
val="$undef"
fi
;;
*) val="$d_sigsetjmp"
case "$d_sigsetjmp" in
$define) echo "POSIX sigsetjmp found." >&4;;
$undef) echo "sigsetjmp not found." >&4;;

```

```
esac
;;
esac
set d_sigsetjmp
eval $setvar
$rm -f set.c set
```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-  
debian-perl-5.26.1/dist/U/d_sigsetjmp.U
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 2005, H.Merijn Brand

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 3.0.

?RCS:

?MAKE:d_malloc_size d_malloc_good_size: Inlibc

?MAKE: -pick add \$@ %<

?S:d_malloc_size:

?S: This symbol, if defined, indicates that the malloc_size

?S: routine is available for use.

?S:.

?S:d_malloc_good_size:

?S: This symbol, if defined, indicates that the malloc_good_size

?S: routine is available for use.

?S:.

?C:HAS_MALLOC_SIZE:

?C: This symbol, if defined, indicates that the malloc_size

?C: routine is available for use.

?C:.

?H:#\$d_malloc_size HAS_MALLOC_SIZE /**/

?H:.

?C:HAS_MALLOC_GOOD_SIZE:

?C: This symbol, if defined,

indicates that the malloc_good_size

?C: routine is available for use.

?C:.

?H:#\$d_malloc_good_size HAS_MALLOC_GOOD_SIZE /**/

?H:.

?LINT:set d_malloc_size

?LINT:set d_malloc_good_size

: see if malloc_size exists

```
set malloc_size d_malloc_size
```

```
eval $inlibc
```

```
: see if malloc_size_good exists
```

```
set malloc_good_size d_malloc_good_size
```

```
eval $inlibc
```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_malloc_size.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: Myinit.U,v 3.0 1993/08/18 12:05:07 ram Exp $
```

```
?RCS:
```

```
?RCS: Copyright (c) 1991-1993, Raphael Manfredi
```

```
?RCS:
```

```
?RCS: This file is included with or a derivative work of a file included
```

```
?RCS: with the metaconfig program of Raphael Manfredi's "dist" distribution.
```

```
?RCS: In accordance with clause 7 of dist's modified Artistic License:
```

```
?RCS:
```

```
?RCS: You may distribute under the terms of either the GNU General Public
```

```
?RCS: License or the Artistic License, as specified in the README file.
```

```
?RCS:
```

```
?RCS: $Log: Myinit.U,v $
```

```
?RCS: Revision 3.0 1993/08/18 12:05:07 ram
```

```
?RCS: Baseline for dist 3.0 netwide release.
```

```
?RCS:
```

```
?X:
```

```
?X: If you want to initialize any default values, copy this unit to your
```

```
?X: personal U directory and add the assignments to the end. This file
```

```
?X: is included after variables are initialized but before any old
```

```
?X: config.sh file is read in and before any Configure switch processing.
```

```
?X:
```

```
?MAKE:Myinit
```

```
libswanted: Init
```

```
?MAKE: -pick add $@ %<
```

```
?S:libswanted:
```

```
?S: This variable holds a list of all the libraries we want to
```

```
?S: search. The order is chosen to pick up the c library
```

```
?S: ahead of ucb or bsd libraries for SVR4.
```

```
?S:.
```

```
?LINT:extern usevfork glibpth
```

```
?LINT:change usevfork glibpth
```

```
: List of libraries we want.
```

```
?X: Put crypt here, even though I should really fix d_crypt.U to look
```

```
?X: for it correctly, including possible shared library versions.
```

```
: If anyone needs extra -lxxx, put those in a hint file.
```

```
libswanted="cl pthread socket bind inet nsl ndbm gdbm dbm db malloc dl ld"
```

```
libswanted="$libswanted sun m crypt sec util c posix posix ucb bsd BSD"
: We probably want to search /usr/shlib before most other libraries.
: This is only used by the lib/ExtUtils/MakeMaker.pm routine extliblist.
glibpth=`echo " $glibpth " | sed -e 's! /usr/shlib ! !'`
glibpth="/usr/shlib $glibpth"
: Do not use vfork unless overridden by a hint file.
usevfork=false
```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/modified/Myinit.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: prefshell.U 1 2006-08-24 12:32:52Z rmanfredi $
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: $Log: prefshell.U,v $
?RCS: Revision 3.0.1.2 1994/10/29 16:28:13 ram
?RCS: patch36: added SHELL temporary since metalint now sees ${SHELL}
?RCS:
?RCS: Revision 3.0.1.1 1993/09/13 16:11:47 ram
?RCS: patch10: non-portable var substitution was used (WAD)
?RCS:
?RCS: Revision 3.0 1993/08/18 12:09:34 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:prefshell: cat package Getfile Oldconfig ksh csh bash
?MAKE: -pick add $@ %<
?S:prefshell:
?S: This
variable contains the eventual value of the PREFSHELL symbol,
?S: which contains the full name of the preferred user shell on this
?S: system. Usual values are /bin/csh, /bin/ksh, /bin/sh.
?S:.
?C:PREFSHELL:
?C: This symbol contains the full name of the preferred user shell on this
?C: system. Usual values are /bin/csh, /bin/ksh, /bin/sh.
?C:.
?H:#define PREFSHELL "$prefshell" /**/
?H:.
?T:SHELL
```

```

: find out which shell people like to use most
case "$prefshell" in
")
case "$ksh $bash $csh" in
*/ksh*) dflt="$ksh" ;;
*/bash*) dflt="$bash" ;;
*/csh*) dflt="$csh" ;;
*) dflt='/bin/sh' ;;
esac
;;
*) dflt="$prefshell";;
esac
?X: Some shells (Ultrix) do not understand ${SHELL:-/bin/sh}, sigh!
$cat <<EOM

```

Give the full path name of the shell most people like to use on your system. This will be used by \$package whenever the user wants to get a shell escape (for instance) and is not necessarily the same as the shell you are currently using (\${SHELL:-/bin/sh}).

```

EOM
fn=f/~
rp='Preferred
shell to be used?'
./getfile
prefshell=$ans

```

```

Found in path(s):
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/prefshell.U
No license file was found, but licenses were detected in source scan.

```

```

?RCS: $Id: vendorman1dir.U,v 1.1 1999/07/08 18:32:57 doughera Exp doughera $
?RCS:
?RCS: Copyright (c) 1999, Andy Dougherty
?RCS:
?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 3.0.
?RCS:
?RCS: $Log: vendorman1dir.U,v $
?RCS: Revision 1.1 1999/07/08 18:32:57 doughera
?RCS: Initial revision
?RCS:
?MAKE:vendorman1dir vendorman1direxp installvendorman1dir: man1dir Getfile \
Oldconfig Setprefixvar Prefixit test vendorprefix prefix sed

```

```

?MAKE: -pick add $@ %<
?Y:TOP
?S:vendorman1dir:
?S: This variable contains the name of the directory for man1
?S: pages. It may have a ~ on the front.
?S: The standard distribution will put nothing in this directory.
?S: Vendors
    who distribute perl may wish to place their own
?S: man1 pages in this directory with
?S: MakeMaker Makefile.PL INSTALLDIRS=vendor
?S: or equivalent. See INSTALL for details.
?S:.
?S:vendorman1direxp:
?S: This variable is the ~name expanded version of vendorman1dir, so that you
?S: may use it directly in Makefiles or shell scripts.
?S:.
?D:installvendorman1dir="
?S:installvendorman1dir:
?S: This variable is really the same as vendorman1direxp but may differ on
?S: those systems using AFS. For extra portability, only this variable
?S: should be used in makefiles.
?S:.
?LINT:change prefixvar
?LINT:set installvendorman1dir
: Set the vendorman1dir variables
case "$vendorprefix" in
") vendorman1dir="
    vendorman1direxp="
;;
*) : determine where vendor-supplied manual pages go.
    case "$vendorman1dir" in
    ") dflt=`echo "$man1dir" | $sed "s#^$prefix#$vendorprefix#"` ;;
    *) dflt=$vendorman1dir ;;
    esac
case "$dflt" in
"|' ') dflt=none ;;
esac
fn=nd~+
rp='Pathname for
the vendor-supplied manual section 1 pages?'
./getfile
vendorman1dir="$ans"
vendorman1direxp="$ansexp"
;;
esac
: Use ' ' for none so value is preserved next time through Configure
$test X"$vendorman1dir" = "X" && vendorman1dir=' '
prefixvar=vendorman1dir

```

./installprefix

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/installdirs/vendorsman1dir.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_waitpid.U 1 2006-08-24 12:32:52Z rmanfredi \$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic Licence,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic Licence; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: d_waitpid.U,v \$

?RCS: Revision 3.0 1993/08/18 12:08:02 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?MAKE:d_waitpid: Inlibc

?MAKE: -pick add \$@ %<

?S:d_waitpid:

?S: This variable conditionally defines HAS_WAITPID if waitpid() is

?S: available to wait for child process.

?S:.

?C:HAS_WAITPID (WAITPID):

?C: This symbol, if defined, indicates that the waitpid routine is

?C: available to wait for child process.

?C:.

?H:#\$d_waitpid HAS_WAITPID /**/

?H:.

?LINT:set

d_waitpid

: see if waitpid exists

set waitpid d_waitpid

eval \$inlibc

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/d_waitpid.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1999, Jarkko Hietaniemi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 3.0.
?RCS:
?MAKE:d_sched_rr_get_interval: Inlibc
?MAKE: -pick add \$@ %<
?S:d_sched_rr_get_interval:
?S: This variable conditionally defines HAS_SCHED_RR_GET_INTERVAL if
?S: sched_rr_get_interval() is available to get the time quantum
?S: of the round robin scheduling.
?S:.
?C:HAS_SCHED_RR_GET_INTERVAL:
?C: This symbol, if defined, indicates that the sched_rr_get_interval
?C: system call is available to get the time quantum
?C: of the round robin scheduling.
?C:.
?H:#\$d_sched_rr_get_interval HAS_SCHED_RR_GET_INTERVAL /**/
?H:.
?LINT:set
d_sched_rr_get_interval
: see if sched_rr_get_interval exists
set sched_rr_get_interval d_sched_rr_get_interval
eval \$inlibc

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_sched_rrgi.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1999 Jarkko Hietaniemi

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?MAKE:d_statvfs d_fstatvfs: Inlibc

?MAKE: -pick add \$@ %<

?S:d_statvfs:

?S: This variable conditionally defines the HAS_STATVFS symbol, which

?S: indicates to the C program that the statvfs() routine is available.

?S:.

?S:d_fstatvfs:

?S: This variable conditionally defines the HAS_FSTATVFS symbol, which

?S: indicates to the C program that the fstatvfs() routine is available.

?S:.

?C:HAS_STATVFS:

?C: This symbol, if defined, indicates that the statvfs routine is

?C: available to stat filesystems by filenames.

?C:.

?C:HAS_FSTATVFS:

?C: This symbol, if defined, indicates that the fstatvfs routine is

?C: available to stat filesystems by file descriptors.

?C:.

?H:#\$d_statvfs HAS_STATVFS /**/

?H:#\$d_fstatvfs

HAS_FSTATVFS /**/

?H:.

?LINT:set d_statvfs

?LINT:set d_fstatvfs

: see if statvfs exists

set statvfs d_statvfs

eval \$inlibc

: see if fstatvfs exists

set fstatvfs d_fstatvfs

eval \$inlibc

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_statvfs.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: d_mmap.U,v \$

?RCS: Revision 3.0.1.1 1993/12/15 08:19:12 ram

?RCS: patch15: created

?RCS:

?MAKE:d_mmap: Inlibc

?MAKE: -pick add \$@ %<

?S:d_mmap:

?S: This variable conditionally defines HAS_MMAP if mmap() is

?S: available to map a file into memory.

?S:.

?C:HAS_MMAP:

?C: This symbol, if defined, indicates that the mmap system call is

?C: available to map a file into memory.

?C:.

?H:#\$d_mmap HAS_MMAP /**/

?H:.

?LINT:set d_mmap

: see if mmap exists

set mmap d_mmap

eval \$inlibc

Found in path(s):

*

/opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/d_mmap.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: d_shm.U,v \$

?RCS: Revision 3.0 1993/08/18 12:07:17 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?MAKE:d_shm: test d_shmctl d_shmget d_shmat d_shmdt Setvar Findhdr

?MAKE: -pick add \$@ %<

?S:d_shm:

?S: This variable conditionally defines the HAS_SHM symbol, which

?S: indicates that the entire shm*(2) library is present.

?S:.

?C:HAS_SHM:

?C: This symbol, if defined, indicates that the entire shm*(2) library is

?C: supported.

?C:.

?H:#\$d_shm HAS_SHM /**/

?H:.

?T:h_shm

?LINT:set d_shm

:

see how much of the 'shm*(2)' library is present.

h_shm=true

echo " "

```

case "$d_shmctl$d_shmget$d_shmat$d_shmdt" in
*"$undef"*) h_shm=false;;
esac
: we could also check for sys/ipc.h ...
if $h_shm && $test `./findhdr sys/shm.h`; then
echo "You have the full shm*(2) library." >&4
val="$define"
else
echo "You don't have the full shm*(2) library." >&4
val="$undef"
fi
set d_shm
eval $setvar

```

Found in path(s):

```

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/d_shm.U

```

No license file was found, but licenses were detected in source scan.

```

?RCS: $Id: d_sigsetmk.U 1 2006-08-24 12:32:52Z rmanfredi $
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: $Log: d_sigsetmk.U,v $
?RCS: Revision 3.0 1993/08/18 12:07:23 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:d_sigsetmk: Csym Setvar
?MAKE: -pick add $@ %<
?S:d_sigsetmk:
?S: This variable conditionally defines the HAS_SIGSETMASK symbol, which
?S: indicates to the C program that the sigsetmask() routine is available
?S: to set current signal mask.
?S:.
?C:HAS_SIGSETMASK (SIGSETMASK):
?C: This symbol, if defined, indicates that the sigsetmask()
routine is
?C: available to set current signal mask. Otherwise, you should probably
?C: emulate this by using signal(), but fear race conditions...
?C:.
?H:#$d_sigsetmk HAS_SIGSETMASK /**/
?H:.

```

```
?LINT:set d_sigsetmk
: see if sigsetmask exists
echo " "
if set sigsetmask val -f d_sigsetmk; eval $csym; $val; then
echo 'sigsetmask() found.' >&4
val="$define"
else
echo "sigsetmask() not found -- We'll use signal()." >&4
val="$undef"
fi
set d_sigsetmk
eval $setvar
```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/d_sigsetmk.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: i_sysfile.U 1 2006-08-24 12:32:52Z rmanfredi $
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: $Log: i_sysfile.U,v $
?RCS: Revision 3.0.1.2 1995/07/25 14:11:36 ram
?RCS: patch56: removed <> characters from comment, per metalint suggestion
?RCS:
?RCS: Revision 3.0.1.1 1993/08/25 14:01:23 ram
?RCS: patch6: added default for i_sysfile
?RCS:
?RCS: Revision 3.0 1993/08/18 12:08:31 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:i_sysfile: h_sysfile Inhdr Setvar
?MAKE: -pick add $@ %<
?S:i_sysfile:
?S: This variable conditionally defines
the I_SYS_FILE symbol, and indicates
?S: whether a C program should include <sys/file.h> to get R_OK and friends.
?S:.
?C:I_SYS_FILE (I_SYSFILE):
?C: This symbol, if defined, indicates to the C program that it should
?C: include <sys/file.h> to get definition of R_OK and friends.
```

```

?C:.
?H:#$i_sysfile I_SYS_FILE /**/
?H:.
?T:val
?D:i_sysfile="
?LINT:change h_sysfile
?LINT:set i_sysfile
: see if this is a sys/file.h system
val="
set sys/file.h val
eval $inhdr

: do we need to include sys/file.h ?
case "$val" in
"$define")
echo " "
if $h_sysfile; then
val="$define"
echo "We'll be including <sys/file.h>." >&4
else
val="$undef"
echo "We won't be including <sys/file.h>." >&4
fi
;;
*)
h_sysfile=false
;;
esac
set i_sysfile
eval $setvar

```

Found in path(s):

```

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/i_sysfile.U

```

No license file was found, but licenses were detected in source scan.

```

?RCS: $Id: d_lstat.U 1 2006-08-24 12:32:52Z rmanfredi $
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: $Log: d_lstat.U,v $
?RCS: Revision 3.0 1993/08/18 12:06:28 ram

```

?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:d_lstat: Inlibc
?MAKE: -pick add \$@ %<
?S:d_lstat:
?S: This variable conditionally defines HAS_LSTAT if lstat() is
?S: available to do file stats on symbolic links.
?S:.
?C:HAS_LSTAT (LSTAT):
?C: This symbol, if defined, indicates that the lstat routine is
?C: available to do file stats on symbolic links.
?C:.
?H:#\$d_lstat HAS_LSTAT /**/
?H:.
?LINT:set
d_lstat
: see if lstat exists
set lstat d_lstat
eval \$inlibc

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/d_lstat.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: \$Log: d_setpgrp.U,v \$
?RCS: Revision 3.0.1.3 1997/02/28 15:44:16 ram
?RCS: patch61: obsoleted USE_BSDGRP in favor of USE_BSD_SETPGRP
?RCS: patch61: another unit now also defines a USE_BSD_GETPGRP
?RCS: patch61: fallback for test program failure improved
?RCS:
?RCS: Revision 3.0.1.2 1995/07/25 13:59:30 ram
?RCS: patch56: re-arranged compile line to include ldflags before objects
?RCS:
?RCS: Revision 3.0.1.1 1994/10/29 16:15:37 ram
?RCS: patch36: added 'ldflags' to the test compile line (ADO)
?RCS:

```

patch36: call ./usg explicitly instead of relying on PATH
?RCS:
?RCS: Revision 3.0 1993/08/18 12:07:09 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:d_setpgrp d_bsdsetpgrp: cat rm +cc +libs +ccflags \
+ldflags Inlibc Guess Setvar i_unistd
?MAKE: -pick add $@ %<
?S:d_setpgrp:
?S: This variable conditionally defines HAS_SETPGRP if setpgrp() is
?S: available to set the current process group.
?S:.
?S:d_bsdsetpgrp (d_bsdpggrp):
?S: This variable conditionally defines USE_BSD_SETPGRP if
?S: setpgrp needs two arguments whereas USG one needs none.
?S: See also d_setpgid for a POSIX interface.
?S:.
?C:HAS_SETPGRP (SETPGRP):
?C: This symbol, if defined, indicates that the setpgrp routine is
?C: available to set the current process group.
?C:.
?C:USE_BSD_SETPGRP (USE_BSDPGRP BSDPGRP):
?C: This symbol, if defined, indicates that setpgrp needs two
?C: arguments whereas USG one needs none. See also HAS_SETPGID
?C: for a POSIX interface.
?C:.
?H:#$d_setpgrp HAS_SETPGRP /**/
?H:#$d_bsdsetpgrp
USE_BSD_SETPGRP /**/
?H:.
?F:!set.c !set
?T:xxx
?LINT:set d_setpgrp d_bsdsetpgrp
: see if setpgrp exists
set setpgrp d_setpgrp
eval $inlibc

@if USE_BSD_SETPGRP || d_bsdsetpgrp
case "$d_setpgrp" in
"$define")
echo " "
echo "Checking to see which flavor of setpgrp is in use..."
$cat >set.c <<EOP
#$i_unistd I_UNISTD
#include <sys/types.h>
#ifdef I_UNISTD
# include <unistd.h>
#endif

```

```

int main()
{
if (getuid() == 0) {
printf("(I see you are running Configure as super-user...)\n");
setuid(1);
}
#ifdef TRY_BSD_PGRP
if (-1 == setpgrp(1, 1))
exit(0);
#else
if (setpgrp() != -1)
exit(0);
#endif
exit(1);
}
EOP
if $cc -DTRY_BSD_PGRP $ccflags $ldflags -o set set.c $libs >/dev/null 2>&1 && ./set; then
echo 'You have to use setpgrp(pid,pgrp) instead of setpgrp().' >&4
val="$define"
elif $cc $ccflags $ldflags -o set set.c $libs >/dev/null 2>&1 && ./set; then
echo 'You have to use setpgrp() instead of setpgrp(pid,pgrp).' >&4
val="$undef"
else
echo "(I can't
seem to compile and run the test program.)"
if ./usg; then
xxx="a USG one, i.e. you use setpgrp()."
else
# SVR4 systems can appear rather BSD-ish.
case "$i_unistd" in
$undef)
xxx="a BSD one, i.e. you use setpgrp(pid,pgrp)."
val="$define"
;;
$define)
xxx="probably a USG one, i.e. you use setpgrp()."
val="$undef"
;;
esac
fi
echo "Assuming your setpgrp is $xxx" >&4
fi
;;
*) val="$undef";;
esac
set d_bsdsetpgrp
eval $setvar
$rm -f set set.c

```

@end

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/d_setpgrp.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: i_time.U,v \$

?RCS: Revision 3.0 1993/08/18 12:08:45 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?X:

?X: This unit finds which "time" include to use. If 'timezone' is used by the

?X: program, we also try to find which header should be included. Eventually,

?X: we look for <sys/select.h> if I_SYSSSELECT is used, to get struct timeval.

?X:

?MAKE:i_time i_systime i_systimek timeincl: cat cc cflags contains rm_try \
echo n c +i_sysselect Findhdr

?MAKE: -pick add \$@ %<

?S:i_time:

?S: This

variable conditionally defines I_TIME, which indicates

?S: to the C program that it should include <time.h>.

?S:.

?S:i_systime:

?S: This variable conditionally defines I_SYS_TIME, which indicates

?S: to the C program that it should include <sys/time.h>.

?S:.

?S:i_systimek:

?S: This variable conditionally defines I_SYS_TIME_KERNEL, which

?S: indicates to the C program that it should include <sys/time.h>

?S: with KERNEL defined.

?S:.

?S:timeincl:

?S: This variable holds the full path of the included time header(s).

?S:.

?C:I_TIME (USE_TIME_H):

?C: This symbol, if defined, indicates to the C program that it should

```

?C: include <time.h>.
?C:.
?C:I_SYS_TIME (I_SYSTIME USE_SYS_TIME_H NO_TIME_WITH_SYS_TIME):
?C: This symbol, if defined, indicates to the C program that it should
?C: include <sys/time.h>.
?C:.
?C:I_SYS_TIME_KERNEL (I_SYSTIMEKERNEL):
?C: This symbol, if defined, indicates to the C program that it should
?C: include <sys/time.h> with KERNEL defined.
?C:.
?H:#$i_time I_TIME /**/
?H:#$i_systime
I_SYS_TIME /**/
?H:#$i_systimek I_SYS_TIME_KERNEL /**/
?H:.
?W::timezone
?T:xselect flags sysselect s_timeval s_timezone
?LINT:change i_sysselect
: see if we should include time.h, sys/time.h, or both
echo " "
echo "Testing to see if we should include <time.h>, <sys/time.h> or both." >&4
$echo $n "I'm now running the test program...$c"
$cat >try.c <<'EOCP'
#include <sys/types.h>
#ifdef I_TIME
#include <time.h>
#endif
#ifdef I_SYSTIME
#ifdef SYSTIMEKERNEL
#define KERNEL
#endif
#include <sys/time.h>
#endif
#ifdef I_SYSSSELECT
#include <sys/select.h>
#endif
int main()
{
    struct tm foo;
#ifdef S_TIMEVAL
    struct timeval bar;
#endif
#ifdef S_TIMEZONE
    struct timezone tzp;
#endif
    if (foo.tm_sec == foo.tm_sec)
        exit(0);
#ifdef S_TIMEVAL

```

```

if (bar.tv_sec == bar.tv_nsec)
    exit(0);
#endif
exit(1);
}
EOCP
flags=""
@if I_SYSSELECT
if $contains 'timeval.*{' `./findhdr sys/select.h` >/dev/null 2>&1; then
    xselect='-DI_SYSSELECT'
else
    xselect=""
fi
@end
@if timezone
for s_timezone
in '-DS_TIMEZONE' "; do
@else
s_timezone=""
@end
?X: Every package is given a try with 'struct timeval'
@if I_SYSSELECT
for sysselect in $xselect "; do
@else
sysselect=""
@end
for s_timeval in '-DS_TIMEVAL' "; do
for i_systimek in "-DSYSTEMEKERNEL'; do
for i_time in "-DI_TIME'; do
for i_systime in '-DI_SYSTIME' "; do
case "$flags" in
") $echo $n ".$.c"
if $cc $ccflags \
    $i_time $i_systime $i_systimek $sysselect $s_timeval $s_timezone \
-o try try.c >/dev/null 2>&1 ; then
    set X $i_time $i_systime $i_systimek $sysselect $s_timeval
    shift
    flags="$*"
    echo " "
    $echo $n "Succeeded with $flags$.c"
fi
;;
esac
done
done
done
done
@if I_SYSSELECT

```

```

done
@end
@if timezone
done
@end
timeincl=""
echo " "
case "$flags" in
*SYSTIMEKERNEL*) i_systimek="$define"
timeincl=`./findhdr sys/time.h`
echo "We'll include <sys/time.h> with KERNEL defined." >&4;;
*) i_systimek="$undef";;
esac
case "$flags" in
*I_TIME*) i_time="$define"
timeincl=`./findhdr time.h`" $timeincl"
echo
"We'll include <time.h>." >&4;;
*) i_time="$undef";;
esac
case "$flags" in
*I_SYSTIME*) i_systime="$define"
timeincl=`./findhdr sys/time.h`" $timeincl"
echo "We'll include <sys/time.h>." >&4;;
*) i_systime="$undef";;
esac
@if I_SYSSSELECT
case "$flags" in
*I_SYSSSELECT*) i_syssselct="$define"
timeincl=`./findhdr sys/select.h`" $timeincl"
echo "We'll also include <sys/select.h> to get struct timeval." >&4;;
*) case "$i_syssselct" in
") i_syssselct="$undef";;
esac
esac
@end
$rm_try

```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/i_time.U
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1999, Jarkko Hietaniemi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.
 ?RCS: You may reuse parts of this distribution only within the terms of
 ?RCS: that same Artistic License; a copy of which may be found at the root
 ?RCS: of the source tree for dist 3.0.
 ?RCS:
 ?MAKE:d_sem_destroy: Inlibc
 ?MAKE: -pick add \$@ %<
 ?S:d_sem_destroy:
 ?S: This variable conditionally defines HAS_SEM_DESTROY if sem_destroy() is
 ?S: available to destroy a POSIX semaphore.
 ?S:.
 ?C:HAS_SEM_DESTROY:
 ?C: This symbol, if defined, indicates that the sem_destroy system call is
 ?C: available to destroy a POSIX semaphore.
 ?C:.
 ?H:#\$d_sem_destroy HAS_SEM_DESTROY /**/
 ?H:.
 ?LINT:set d_sem_destroy
 : see if sem_destroy exists
 set sem_destroy d_sem_destroy
 eval \$inlibc

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_sem_destroy.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: baserev.U 1 2006-08-24 12:32:52Z rmanfredi \$
 ?RCS:
 ?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
 ?RCS:
 ?RCS: You may redistribute only under the terms of the Artistic Licence,
 ?RCS: as specified in the README file that comes with the distribution.
 ?RCS: You may reuse parts of this distribution only within the terms of
 ?RCS: that same Artistic Licence; a copy of which may be found at the root
 ?RCS: of the source tree for dist 4.0.
 ?RCS:
 ?RCS: \$Log: baserev.U,v \$
 ?RCS: Revision 3.0 1993/08/18 12:05:24 ram
 ?RCS: Baseline for dist 3.0 netwide release.
 ?RCS:
 ?MAKE:baserev: Null
 ?MAKE: -pick wipe \$@ %<
 ?S:baserev:
 ?S: The base revision level of this package, from the .package file.
 ?S:.
 : set the base revision
 baserev=<BASEREV>

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/baserev.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: fpostype.U,v 3.0.1.2 1994/08/29 16:20:52 ram Exp $
```

```
?RCS:
```

```
?RCS: Copyright (c) 1991-1993, Raphael Manfredi
```

```
?RCS:
```

```
?RCS: You may redistribute only under the terms of the Artistic License,
```

```
?RCS: as specified in the README file that comes with the distribution.
```

```
?RCS: You may reuse parts of this distribution only within the terms of
```

```
?RCS: that same Artistic License; a copy of which may be found at the root
```

```
?RCS: of the source tree for dist 3.0.
```

```
?RCS:
```

```
?RCS: $Log: fpostype.U,v $
```

```
?RCS: Revision 3.0.1.2 1994/08/29 16:20:52 ram
```

```
?RCS: patch32: now uses new Typedef unit to compute type information
```

```
?RCS:
```

```
?RCS: Revision 3.0.1.1 1994/06/20 06:59:59 ram
```

```
?RCS: patch30: created
```

```
?RCS:
```

```
?MAKE:fpostype: Myread Typedef
```

```
?MAKE: -pick add $@ %<
```

```
?S:fpostype:
```

```
?S: This variable defines Fpos_t to be something like fpos_t, long,
```

```
?S: uint, or whatever type is used to declare file positions in libc.
```

```
?S:.
```

```
?C:Fpos_t:
```

```
?C: This symbol holds
```

```
the type used to declare file positions in libc.
```

```
?C: It can be fpos_t, long, uint, etc... It may be necessary to include
```

```
?C: <sys/types.h> to get any typedef'ed information.
```

```
?C:.
```

```
?H:#define Fpos_t $fpostype /* File position type */
```

```
?H:.
```

```
?LINT:set fpostype
```

```
: see what type file positions are declared as in the library
```

```
rp="What is the type for file position used by fsetpos()?"
```

```
set fpos_t fpostype long stdio.h sys/types.h
```

```
eval $typedef_ask
```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/typedefs/fpostype.U
```

No license file was found, but licenses were detected in source scan.

```

?RCS: $Id: d_ctermid_r.U,v ORCS:
?RCS: Copyright (c) 2002,2003 Jarkko Hietaniemi
?RCS:
?RCS: You may distribute under the terms of either the GNU General Public
?RCS: License or the Artistic License, as specified in the README file.
?RCS:
?RCS: Generated by the reentr.pl from the Perl 5.8 distribution.
?RCS:
?MAKE:d_ctermid_r ctermid_r_proto: Inlibc Protochk Hasproto i_systypes \
  usethreads extern_C
?MAKE: -pick add $@ %<
?S:d_ctermid_r:
?S: This variable conditionally defines the HAS_CTERMID_R symbol,
?S: which indicates to the C program that the ctermid_r()
?S: routine is available.
?S:.
?S:ctermid_r_proto:
?S: This variable encodes the prototype of ctermid_r.
?S: It is zero if d_ctermid_r is undef, and one of the
?S: REENTRANT_PROTO_T_ABC macros of reentr.h if d_ctermid_r
?S: is defined.
?S:.
?C:HAS_CTERMID_R:
?C: This symbol, if defined, indicates that the ctermid_r routine
?C: is available to ctermid re-entrantly.
?C:.
?C:CTERMID_R_PROTO:
?C: This
  symbol encodes the prototype of ctermid_r.
?C: It is zero if d_ctermid_r is undef, and one of the
?C: REENTRANT_PROTO_T_ABC macros of reentr.h if d_ctermid_r
?C: is defined.
?C:.
?H:#$d_ctermid_r HAS_CTERMID_R /**/
?H:#define CTERMID_R_PROTO $ctermid_r_proto /**/
?H:.
?T:try hdrs d_ctermid_r_proto
: see if ctermid_r exists
set ctermid_r d_ctermid_r
eval $inlibc
case "$d_ctermid_r" in
"$define")
  hdrs="$i_systypes sys/types.h define stdio.h "
  case "$d_ctermid_r_proto:$usethreads" in
":define") d_ctermid_r_proto=define
  set d_ctermid_r_proto ctermid_r $hdrs
  eval $hasproto ;;
*) ;;

```

```

esac
case "$d_ctermid_r_proto" in
define)
case "$ctermid_r_proto" in
"|0) try='char* ctermid_r(char*);'
./protochk "$extern_C $try" $hdrs && ctermid_r_proto=B_B ;;
esac
case "$ctermid_r_proto" in
"|0) d_ctermid_r=undef
ctermid_r_proto=0
echo "Disabling ctermid_r, cannot determine prototype." >&4 ;;
* ) case "$ctermid_r_proto" in
REENTRANT_PROTO*)
;;
*) ctermid_r_proto="REENTRANT_PROTO_${ctermid_r_proto}" ;;
esac
echo "Prototype: $try" ;;
esac
;;
*) case "$usethreads" in
define) echo "ctermid_r has no prototype, not using it." >&4 ;;
esac
d_ctermid_r=undef
ctermid_r_proto=0
;;
esac
;;
*) ctermid_r_proto=0
;;
esac

```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/threads/d_ctermid_r.U
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_endservent_r.U,v ORCS:

?RCS: Copyright (c) 2002,2003 Jarkko Hietaniemi

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?RCS: Generated by the reentr.pl from the Perl 5.8 distribution.

?RCS:

?MAKE:d_endservent_r endservent_r_proto: Inlibc Protochk Hasproto i_systypes \

usethreads i_netdb extern_C

?MAKE: -pick add \$@ %<

?S:d_endservent_r:

?S: This variable conditionally defines the HAS_ENDSERVENT_R symbol,
?S: which indicates to the C program that the endservent_r()
?S: routine is available.
?S:.
?S:endservent_r_proto:
?S: This variable encodes the prototype of endservent_r.
?S: It is zero if d_endservent_r is undef, and one of the
?S: REENTRANT_PROTO_T_ABC macros of reentr.h if d_endservent_r
?S: is defined.
?S:.
?C:HAS_ENDSERVENT_R:
?C: This symbol, if defined, indicates that the endservent_r routine
?C: is
available to endservent re-entrantly.
?C:.
?C:ENDSERVENT_R_PROTO:
?C: This symbol encodes the prototype of endservent_r.
?C: It is zero if d_endservent_r is undef, and one of the
?C: REENTRANT_PROTO_T_ABC macros of reentr.h if d_endservent_r
?C: is defined.
?C:.
?H:#\$d_endservent_r HAS_ENDSERVENT_R /**/
?H:#define ENDSERVENT_R_PROTO \$endservent_r_proto /**/
?H:.
?T:try hdrs d_endservent_r_proto
: see if endservent_r exists
set endservent_r d_endservent_r
eval \$inlibc
case "\$d_endservent_r" in
"\$define")
hdrs="\$i_systypes sys/types.h define stdio.h \$i_netdb netdb.h"
case "\$d_endservent_r_proto:\$usetthreads" in
":define") d_endservent_r_proto=define
set d_endservent_r_proto endservent_r \$hdrs
eval \$hasproto ;;
*) ;;
esac
case "\$d_endservent_r_proto" in
define)
case "\$endservent_r_proto" in
"|0) try='int endservent_r(struct servent_data*);'
./protochk "\$extern_C \$try" \$hdrs && endservent_r_proto=I_D ;;
esac
case "\$endservent_r_proto" in
"|0) try='void
endservent_r(struct servent_data*);'
./protochk "\$extern_C \$try" \$hdrs && endservent_r_proto=V_D ;;
esac

```

case "$endservent_r_proto" in
|0) d_endservent_r=undef
    endservent_r_proto=0
    echo "Disabling endservent_r, cannot determine prototype." >&4 ;;
*) case "$endservent_r_proto" in
REENTRANT_PROTO*) ;;
*) endservent_r_proto="REENTRANT_PROTO_$endservent_r_proto" ;;
esac
echo "Prototype: $try" ;;
esac
;;
*) case "$susetthreads" in
define) echo "endservent_r has no prototype, not using it." >&4 ;;
esac
d_endservent_r=undef
endservent_r_proto=0
;;
esac
;;
*) endservent_r_proto=0
;;
esac

```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/threads/d_endservent_r.U
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_longdbl.U,v \$

?RCS:

?RCS: Copyright (c) 1998 Andy Dougherty

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?RCS: \$Log: d_longdbl.U,v \$

?RCS:

```
?MAKE:d_longdbl longdblsize d_ldexpl longdblkind \
d_long_double_style_ieee d_long_double_style_ieee_doubledouble \
d_long_double_style_ieee_extended d_long_double_style_ieee_std \
d_long_double_style_vax: Compile Setvar Myread \
Inlibc run echo cat rm_try test doublesize i_stdlib i_float
```

?MAKE: -pick add \$@ %<

?S:d_longdbl:

?S: This variable conditionally defines HAS_LONG_DOUBLE if

?S: the long double type is supported.

?S:.

?S:d_ldexpl:

?S: This variable conditionally defines the HAS_LDEXPL symbol, which indicates to the C program that the ldexpl() routine is available.

?S:.

?S:longdblsize:

?S: This variable contains the value of the LONG_DOUBLESIZE symbol, which indicates to the C program how many bytes there are in a long double, if this system supports long doubles. Note that this is sizeof(long double), which may include unused bytes.

?S:.

?S:longdblkind:

?S: This variable, if defined, encodes the type of a long double:

?S: 0 = double,

?S: 1 = IEEE 754 128-bit little endian,

?S: 2 = IEEE 754 128-bit big endian,

?S: 3 = x86 80-bit little endian,

?S: 4 = x86 80-bit big endian,

?S: 5 = double-double 128-bit little endian,

?S: 6 = double-double 128-bit big endian,

?S: 7 = 128-bit mixed-endian double-double (64-bit LEs in BE),

?S: 8 = 128-bit mixed-endian double-double (64-bit BEs in LE),

?S: 9 = 128-bit PDP-style mixed-endian long doubles,

?S: -1 = unknown format.

?S:.

?S:d_long_double_style_ieee:

?S: This variable conditionally defines LONG_DOUBLE_STYLE_IEEE if the long double is any of the IEEE 754 style long doubles:

?S: LONG_DOUBLE_STYLE_IEEE_STD, LONG_DOUBLE_STYLE_IEEE_EXTENDED,

?S: LONG_DOUBLE_STYLE_IEEE_DOUBLEDDOUBLE.

?S:.

?S:d_long_double_style_ieee_doubledouble:

?S: This variable conditionally defines LONG_DOUBLE_STYLE_IEEE_DOUBLEDDOUBLE if the long double is the 128-bit IEEE 754 double-double.

?S:.

?S:d_long_double_style_ieee_extended:

?S: This variable conditionally defines LONG_DOUBLE_STYLE_IEEE_EXTENDED if the long double is the 80-bit IEEE 754 extended precision.

?S: Note that despite the 'extended' this is less than the 'std', since this is an extension of the double precision.

?S:.

?S:d_long_double_style_ieee_std:

?S: This variable conditionally defines LONG_DOUBLE_STYLE_IEEE_STD if the long double is the 128-bit IEEE 754.

?S:.

?S:d_long_double_style_vax:

?S: This variable conditionally defines LONG_DOUBLE_STYLE_VAX if the long double is the 128-bit VAX format H.

?S:.

?C:HAS_LONG_DOUBLE:

?C: This symbol will be defined if the C compiler supports long

?C: doubles.

?C:.

?C:LONG_DOUBLE_SIZE:

?C: This symbol contains the size of a long double, so that the

?C: C

preprocessor can make decisions based on it. It is only

?C: defined if the system supports long doubles. Note that this

?C: is sizeof(long double), which may include unused bytes.

?C:.

?C:HAS_LDEXPL:

?C: This symbol, if defined, indicates that the ldexpl routine is

?C: available to shift a long double floating-point number

?C: by an integral power of 2.

?C:.

?C:LONG_DOUBLE_KIND:

?C: LONG_DOUBLE_KIND will be one of

?C: LONG_DOUBLE_IS_DOUBLE

?C: LONG_DOUBLE_IS_IEEE_754_128_BIT_LITTLE_ENDIAN

?C: LONG_DOUBLE_IS_IEEE_754_128_BIT_BIG_ENDIAN

?C: LONG_DOUBLE_IS_X86_80_BIT_LITTLE_ENDIAN

?C: LONG_DOUBLE_IS_X86_80_BIT_BIG_ENDIAN

?C: LONG_DOUBLE_IS_DOUBLEDDOUBLE_128_BIT_LE_LE

?C: LONG_DOUBLE_IS_DOUBLEDDOUBLE_128_BIT_BE_BE

?C: LONG_DOUBLE_IS_DOUBLEDDOUBLE_128_BIT_LE_BE

?C: LONG_DOUBLE_IS_DOUBLEDDOUBLE_128_BIT_BE_LE

?C: LONG_DOUBLE_IS_VAX_H_FLOAT

?C: LONG_DOUBLE_IS_UNKNOWN_FORMAT

?C: It is only defined if the system supports long doubles.

?C:.

?C:LONG_DOUBLE_STYLE_IEEE:

?C: This symbol, if defined,

indicates that the long double

?C: is any of the IEEE 754 style long doubles:

?C: LONG_DOUBLE_STYLE_IEEE_STD, LONG_DOUBLE_STYLE_IEEE_EXTENDED,

?C: LONG_DOUBLE_STYLE_IEEE_DOUBLEDDOUBLE.

?C:.

?C:LONG_DOUBLE_STYLE_IEEE_DOUBLEDDOUBLE:

?C: This symbol, if defined, indicates that the long double is

?C: the 128-bit double-double.

?C:.

?C:LONG_DOUBLE_STYLE_IEEE_EXTENDED:

?C: This symbol, if defined, indicates that the long double is

?C: the 80-bit IEEE 754. Note that despite the 'extended' this

?C: is less than the 'std', since this is an extension of

?C: the double precision.

```

?C:.
?C:LONG_DOUBLE_STYLE_IEEE_STD:
?C: This symbol, if defined, indicates that the long double is
?C: the 128-bit IEEE 754.
?C:.
?C:LONG_DOUBLE_STYLE_VAX:
?C: This symbol, if defined, indicates that the long double is
?C: the 128-bit VAX format H.
?C:.
?H:#$d_ldexpl HAS_LDEXPL /**/
?H:#$d_longdbl HAS_LONG_DOUBLE /**/
?H:?LONG_DOUBLE_SIZE:#ifdef HAS_LONG_DOUBLE
?H:?LONG_DOUBLE_SIZE:#define LONG_DOUBLE_SIZE $longdblsize /**/
?H:?LONG_DOUBLE_SIZE:#define
LONG_DOUBLE_KIND $longdblkind /**/
?H:?LONG_DOUBLE_SIZE:#define LONG_DOUBLE_IS_DOUBLE 0
?H:?LONG_DOUBLE_SIZE:#define LONG_DOUBLE_IS_IEEE_754_128_BIT_LITTLE_ENDIAN 1
?H:?LONG_DOUBLE_SIZE:#define LONG_DOUBLE_IS_IEEE_754_128_BIT_BIG_ENDIAN 2
?H:?LONG_DOUBLE_SIZE:#define LONG_DOUBLE_IS_X86_80_BIT_LITTLE_ENDIAN 3
?H:?LONG_DOUBLE_SIZE:#define LONG_DOUBLE_IS_X86_80_BIT_BIG_ENDIAN 4
?H:?LONG_DOUBLE_SIZE:#define LONG_DOUBLE_IS_DOUBLEDDOUBLE_128_BIT_LE_LE 5
?H:?LONG_DOUBLE_SIZE:#define LONG_DOUBLE_IS_DOUBLEDDOUBLE_128_BIT_BE_BE 6
?H:?LONG_DOUBLE_SIZE:#define LONG_DOUBLE_IS_DOUBLEDDOUBLE_128_BIT_LE_BE 7
?H:?LONG_DOUBLE_SIZE:#define LONG_DOUBLE_IS_DOUBLEDDOUBLE_128_BIT_BE_LE 8
?H:?LONG_DOUBLE_SIZE:#define LONG_DOUBLE_IS_VAX_H_FLOAT 9
?H:?LONG_DOUBLE_SIZE:#define LONG_DOUBLE_IS_UNKNOWN_FORMAT -1
?H:?LONG_DOUBLE_SIZE:#define LONG_DOUBLE_IS_DOUBLEDDOUBLE_128_BIT_LITTLE_ENDIAN
LONG_DOUBLE_IS_DOUBLEDDOUBLE_128_BIT_LE_LE /* back-compat */
?H:?LONG_DOUBLE_SIZE:#define LONG_DOUBLE_IS_DOUBLEDDOUBLE_128_BIT_BIG_ENDIAN
LONG_DOUBLE_IS_DOUBLEDDOUBLE_128_BIT_BE_BE
/* back-compat */
?H:?LONG_DOUBLE_SIZE:#$d_long_double_style_ieee LONG_DOUBLE_STYLE_IEEE
?H:?LONG_DOUBLE_SIZE:#$d_long_double_style_ieee_doubledouble
LONG_DOUBLE_STYLE_IEEE_DOUBLEDDOUBLE
?H:?LONG_DOUBLE_SIZE:#$d_long_double_style_ieee_extended
LONG_DOUBLE_STYLE_IEEE_EXTENDED
?H:?LONG_DOUBLE_SIZE:#$d_long_double_style_ieee_std LONG_DOUBLE_STYLE_IEEE_STD
?H:?LONG_DOUBLE_SIZE:#$d_long_double_style_vax LONG_DOUBLE_STYLE_VAX
?H:?LONG_DOUBLE_SIZE:#endif
?H:.
?F:!try
?LINT:known LONG_DOUBLE_IS_DOUBLE LONG_DOUBLE_IS_IEEE_754_128_BIT_LITTLE_ENDIAN
?LINT:known LONG_DOUBLE_IS_IEEE_754_128_BIT_BIG_ENDIAN
LONG_DOUBLE_IS_X86_80_BIT_LITTLE_ENDIAN
?LINT:known LONG_DOUBLE_IS_X86_80_BIT_BIG_ENDIAN
LONG_DOUBLE_IS_DOUBLEDDOUBLE_128_BIT_LITTLE_ENDIAN
?LINT:known LONG_DOUBLE_IS_DOUBLEDDOUBLE_128_BIT_BIG_ENDIAN
LONG_DOUBLE_IS_UNKNOWN_FORMAT

```

```

?LINT:known LONG_DOUBLE_IS_DOUBLEDDOUBLE_128_BIT_LE_LE
?LINT:known LONG_DOUBLE_IS_DOUBLEDDOUBLE_128_BIT_BE_BE
?LINT:known
LONG_DOUBLE_IS_DOUBLEDDOUBLE_128_BIT_LE_BE
?LINT:known LONG_DOUBLE_IS_DOUBLEDDOUBLE_128_BIT_BE_LE
?LINT:known LONG_DOUBLE_IS_VAX_H_FLOAT
?LINT:set d_longdbl
?LINT:set d_ldexpl
: check for long doubles
echo " "
echo "Checking to see if you have long double..." >&4
echo 'int main() { long double x = 7.0; }' > try.c
set try
if eval $compile; then
  val="$define"
  echo "You have long double."
else
  val="$undef"
  echo "You do not have long double."
fi
$rm_try
set d_longdbl
eval $setvar

: see if ldexpl exists
set ldexpl d_ldexpl
eval $inlibc

@if LONG_DOUBLESIZE || longdblsize
: check for length of long double
?X: Check only if d_longdbl and if longdblsize is not already set.
case "${d_longdbl}${longdblsize}" in
$define)
  echo " "
  echo "Checking to see how big your long doubles are..." >&4
  $cat >try.c <<'EOCP'
#include <stdio.h>
int main()
{
  printf("%d\n", sizeof(long double));
}
EOCP
set try
?X: Don't use compile_ok because some compilers warn you that they have
?X: 'long
double' as just 'double'.
set try
if eval $compile; then

```

```

longdblsize=`$run ./try`
echo "Your long doubles are $longdblsize bytes long."
else
dflt='8'
echo " "
echo "(I can't seem to compile the test program. Guessing...)" >&4
rp="What is the size of a long double (in bytes)?"
./myread
longdblsize="$ans"
fi
if $test "X$doublesize" = "X$longdblsize"; then
echo "That isn't any different from an ordinary double."
echo "I'll keep your setting anyway, but you may see some"
echo "harmless compilation warnings."
fi
;;
esac
$rm_try
@end

$echo "Checking the kind of long doubles you have..." >&4
case "$d_longdbl" in
define)
$cat <<EOP >try.c
#$i_float I_FLOAT
#$i_stdlib I_STDLIB
#define LONGDBLSIZE $longdblsize
#define DOUBLESIZE $doublesize
#ifdef I_FLOAT
#include <float.h>
#endif
#ifdef I_STDLIB
#include <stdlib.h>
#endif
#include <stdio.h>
static const long double d = -0.1L;
int main() {
    unsigned const char* b = (unsigned const char*)&d;
#ifdef DOUBLESIZE
    == LONGDBLSIZE
    printf("0\n"); /* if it floats like double */
    exit(0);
#endif
#ifdef (LDBL_MANT_DIG == 113 || FLT128_MANT_DIG == 113) && LONGDBLSIZE == 16
    if (b[0] == 0x9A && b[1] == 0x99 && b[15] == 0xBF) {
        /* IEEE 754 128-bit little-endian */
        printf("1\n");
        exit(0);
    }

```

```

}
if (b[0] == 0xBF && b[14] == 0x99 && b[15] == 0x9A) {
    /* IEEE 128-bit big-endian, e.g. solaris sparc */
    printf("2\n");
    exit(0);
}
#endif
/* For alignment 32-bit platforms have the 80 bits in 12 bytes,
 * while 64-bits platforms have it in 16 bytes. The trailing bytes
 * cannot be trusted. */
#if LDBL_MANT_DIG == 64 && (LONGDBLSIZE == 16 || LONGDBLSIZE == 12)
if (b[0] == 0xCD && b[9] == 0xBF) {
    /* x86 80-bit little-endian, sizeof 12 (ILP32, Solaris x86)
     * or 16 (LP64, Linux and OS X), 4 or 6 bytes of padding.
     * Also known as "extended precision". */
    printf("3\n");
    exit(0);
}
if (b[0] == 0xBF && b[9] == 0xCD) {
    /* Is there ever big-endian 80-bit, really?

     *
     * The Motorola 68881 had another "extended precision" format:
     * sign:1 exp:15 zero:16 integer:1 mantissa:63
     * for total of 96 bits of bytes. The zero bits were unused.
     * See "M68000 FAMILY PROGRAMMER'S REFERENCE MANUAL" for more details.
     * If it ever becomes relevant, this format should be allocated
     * a new doublekind code since it's quite different from the Intel x87.
     */
    printf("4\n");
    exit(0);
}
#endif
#if (LDBL_MANT_DIG == 106 || LDBL_MANT_DIG == 107) && LONGDBLSIZE == 16
/* software "double double", the 106 is 53+53.
 * but irix thinks it is 107. */
if (b[0] == 0x9A && b[7] == 0x3C && b[8] == 0x9A && b[15] == 0xBF) {
    /* double double 128-bit fully little-endian,
     * little-endian doubles in little-endian order,
     * 9a 99 99 99 99 99 59 3c 9a 99 99 99 99 99 b9 bf */
    printf("5\n");
    exit(0);
}
if (b[0] == 0xBF && b[7] == 0x9A && b[8] == 0x3C && b[15] == 0x9A) {
    /* double double 128-bit fully big-endian,
     * big-endian doubles in big-endian order,
     * e.g. PPC/Power and MIPS:
     * bf b9 99 99 99 99 9a 3c 59 99 99 99 99 99 9a */

```

```

printf("6\n");
exit(0);
}
if (b[0] == 0x9A && b[7] == 0xBF && b[8] == 0x9A && b[15] == 0x3C) {
/* double double 128-bit mixed endian.
* little-endian doubles in big-endian order,
* e.g. ppc64el,
* 9a 99 99 99 99 99 b9 bf 9a 99 99 99 99 59 3c */
printf("7\n");
exit(0);
}
if (b[0] == 0x3C && b[7] == 0x9A && b[8] == 0xBF && b[15] == 0x9A) {
/* double double 128-bit mixed endian,
* big-endian doubles in little-endian order,
* 3c 59 99 99 99 99 99 9a bf b9 99 99 99 99 9a */
printf("8\n");
exit(0);
}
#endif
/* We are largely making this up because it may well be
* that the VAX format H was never made available to C,
* only to Fortran. */
#if LONGDBLSIZE == 16 && defined(__vax__)
if (b[0] == 0xFD && b[15] == 0x99) {
/* VAX format H, PDP-11 mixed endian. */
printf("9\n");

exit(0);
}
#endif
printf("-1\n"); /* unknown */
exit(0);
}
EOP
set try
if eval $compile; then
longdblkind=`$run ./try`
else
longdblkind=-1
fi
;;
*) longdblkind=0 ;;
esac
case "$longdblkind" in
0) echo "Your long doubles are doubles." >&4 ;;
1) echo "You have IEEE 754 128-bit little endian long doubles." >&4 ;;
2) echo "You have IEEE 754 128-bit big endian long doubles." >&4 ;;
3) echo "You have x86 80-bit little endian long doubles." >& 4 ;;

```

```

4) echo "You have x86 80-bit big endian long doubles." >& 4 ;;
5) echo "You have 128-bit fully little-endian double-double long doubles (64-bit LEs in LE)." >& 4 ;;
6) echo "You have 128-bit fully big-endian double-double long doubles (64-bit BEs in BE)." >& 4 ;;
7) echo "You have 128-bit mixed-endian double-double long doubles (64-bit LEs in BE)." >& 4 ;;
8) echo "You have 128-bit mixed-endian double-double long doubles (64-bit BEs in LE)." >& 4 ;;
9) echo "You have 128-bit PDP-style mixed-endian long doubles (VAX format H)." >& 4 ;;
*)
    echo "Cannot figure out your long double." >&4 ;;
esac
d_long_double_style_ieee=$undef
d_long_double_style_ieee_std=$undef
d_long_double_style_ieee_extended=$undef
d_long_double_style_ieee_doubledouble=$undef
d_long_double_style_vax=$undef
case "$longdblkind" in
1|2|3|4|5|6|7|8) d_long_double_style_ieee=$define ;;
esac
case "$longdblkind" in
1|2) d_long_double_style_ieee_std=$define ;;
esac
case "$longdblkind" in
3|4) d_long_double_style_ieee_extended=$define ;;
esac
case "$longdblkind" in
5|6|7|8) d_long_double_style_ieee_doubledouble=$define ;;
esac
case "$longdblkind" in
9) d_long_double_style_vax=$define ;;
esac
$rm_try

```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/modified/d_longdbl.U
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_time.U,v 3.0.1.2 1995/07/25 14:07:43 ram Exp \$

?RCS:

?RCS: Copyright (c) 1991-1993, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 3.0.

?RCS:

?RCS: \$Log: d_time.U,v \$

?RCS: Revision 3.0.1.2 1995/07/25 14:07:43 ram

```

?RCS: patch56: typo fix, sytem -> system
?RCS:
?RCS: Revision 3.0.1.1 1994/10/29 16:16:38 ram
?RCS: patch36: now uses new Typedef unit to compute type information (ADO)
?RCS:
?RCS: Revision 3.0 1993/08/18 12:07:45 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?X: Maybe <sys/types.h> should be included?
?X:INC: i_systypes
?MAKE:d_time timetype: Csym Setvar Findhdr Myread Typedef
?MAKE: -pick
add $@ %<
?S:d_time:
?S: This variable conditionally defines the HAS_TIME symbol, which indicates
?S: that the time() routine exists. The time() routine is normally
?S: provided on UNIX systems.
?S:.
?S:timetype:
?S: This variable holds the type returned by time(). It can be long,
?S: or time_t on BSD sites (in which case <sys/types.h> should be
?S: included). Anyway, the type Time_t should be used.
?S:.
?C:HAS_TIME (TIMER):
?C: This symbol, if defined, indicates that the time() routine exists.
?C:.
?C:Time_t (TIMETYPE):
?C: This symbol holds the type returned by time(). It can be long,
?C: or time_t on BSD sites (in which case <sys/types.h> should be
?C: included).
?C:.
?H:#$d_time HAS_TIME /**/
?H:#define Time_t $timetype /* Time type */
?H:.
?LINT:set d_time
: see if time exists
echo " "
?X: MPE/iX needs this protection of hint values.
?X: See d_sterror.U for more explanation.
if test "$d_time" = X -o X"$timetype" = X; then
    if set time val -f d_time; eval $csym; $val;
then
    echo 'time() found.' >&4
    val="$define"
    rp="What is the type returned by time() on this system?"
    set time_t timetype long stdio.h sys/types.h
    eval $typedef_ask
else

```

```
echo 'time() not found, hope that will do.' >&4
val="$undef"
timetype='int';
fi
set d_time
eval $setvar
fi
```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/typedefs/d_time.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: d_syscall.U 1 2006-08-24 12:32:52Z rmanfredi $
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: $Log: d_syscall.U,v $
?RCS: Revision 3.0 1993/08/18 12:07:42 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:d_syscall: Inlibc
?MAKE: -pick add $@ %<
?S:d_syscall:
?S: This variable conditionally defines HAS_SYSCALL if syscall() is
?S: available call arbitrary system calls.
?S:
?C:HAS_SYSCALL (SYSCALL):
?C: This symbol, if defined, indicates that the syscall routine is
?C: available to call arbitrary system calls. If undefined, that's tough.
?C:
?H:#$d_syscall
HAS_SYSCALL /**/
?H:
?LINT:set d_syscall
: see if syscall exists
set syscall d_syscall
eval $inlibc
```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/d_syscall.U
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: vendorlib.U,v 1.1 1999/07/08 18:32:57 doughera Exp doughera \$

?RCS:

?RCS: Copyright (c) 1999, Andy Dougherty

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 3.0.

?RCS:

?RCS: \$Log: vendorlib.U,v \$

?RCS: Revision 1.1 1999/07/08 18:32:57 doughera

?RCS: Initial revision

?RCS:

?MAKE:d_vendorlib vendorlib vendorlibexp installvendorlib vendorlib_stem: \

Getfile Setprefixvar Oldconfig Prefixit package vendorprefix sed \

installstyle version

?MAKE: -pick add \$@ %<

?Y:TOP

?S:vendorlib:

?S: This variable contains the eventual value of the VENDORLIB symbol,

?S: which is the name of the private library for this package.

?S: The standard

distribution will put nothing in this directory.

?S: Vendors who distribute perl may wish to place their own

?S: modules in this directory with

?S: MakeMaker Makefile.PL INSTALLDIRS=vendor

?S: or equivalent. See INSTALL for details.

?S:.

?S:vendorlibexp:

?S: This variable is the ~name expanded version of vendorlib, so that you

?S: may use it directly in Makefiles or shell scripts.

?S:.

?D:installvendorlib="

?S:installvendorlib:

?S: This variable is really the same as vendorlibexp but may differ on

?S: those systems using AFS. For extra portability, only this variable

?S: should be used in makefiles.

?S:.

?S:d_vendorlib:

?S: This variable conditionally defines PERL_VENDORLIB.

?S:.

?S:vendorlib_stem:

?S: This variable is \$vendorlibexp with any trailing version-specific component

?S: removed. The elements in inc_version_list (inc_version_list.U) can

?S: be tacked onto this variable to generate a list of directories to search.

?S:.

?C:PERL_VENDORLIB:

?C: If defined, this symbol contains
the name of a private library.

?C: The library is private in the sense that it needn't be in anyone's
?C: execution path, but it should be accessible by the world. The program
?C: should be prepared to do ~ expansion.

?C: The standard distribution will put nothing in this directory.

?C: Vendors who distribute perl may wish to place their own
?C: modules in this directory with
?C: MakeMaker Makefile.PL INSTALLDIRS=vendor
?C: or equivalent. See INSTALL for details.

?C:.

?C:PERL_VENDORLIB_EXP:

?C: This symbol contains the ~name expanded version of VENDORLIB, to be used
?C: in programs that are not prepared to deal with ~ expansion at run-time.

?C:.

?C:PERL_VENDORLIB_STEM:

?C: This define is PERL_VENDORLIB_EXP with any trailing version-specific component
?C: removed. The elements in inc_version_list (inc_version_list.U) can
?C: be tacked onto this variable to generate a list of directories to search.

?C:.

?H:#\$d_vendorlib PERL_VENDORLIB "\$vendorlib" /**/
?H:#\$d_vendorlib PERL_VENDORLIB_EXP
"\$vendorlibexp" /**/
?H:#\$d_vendorlib PERL_VENDORLIB_STEM "\$vendorlib_stem" /**/
?H:.

?T:prog

?LINT:change prefixvar
?LINT:set installvendorlib
: Set the vendorlib variables
case "\$vendorprefix" in
") d_vendorlib="\$undef"
vendorlib="
vendorlibexp="
;;
*) d_vendorlib="\$define"
: determine where vendor-supplied modules go.
: Usual default is /usr/local/lib/perl5/vendor_perl/\$version
case "\$vendorlib" in
")
?X: remove any trailing -3.0 or other version identification
prog=`echo \$package | \$sed 's/-*[0-9.]*\$/'^
case "\$installstyle" in
lib/perl5) dflt=\$vendorprefix/lib/\$package/vendor_\$prog/\$version ;;
*) dflt=\$vendorprefix/lib/vendor_\$prog/\$version ;;
esac
;;

```

*) dflt="$vendorlib"
;;
esac
fn=d~+
rp='Pathname for the vendor-supplied library files?'
./getfile
vendorlib="$ans"
vendorlibexp="$ansexp"
;;
esac
vendorlib_stem=`echo "$vendorlibexp" | sed "s,/$version$,,"`
prefixvar=vendorlib
./installprefix

```

Found in path(s):

```

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/installdirs/vendorlib.U

```

No license file was found, but licenses were detected in source scan.

```

?RCS: $Id: d_umask.U 1 2006-08-24 12:32:52Z rmanfredi $
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: Original Author: Andy Dougherty <doughera@lafcol.lafayette.edu>
?RCS:
?RCS: $Log: d_umask.U,v $
?RCS: Revision 3.0.1.1 1994/08/29 16:14:50 ram
?RCS: patch32: created by ADO
?RCS:
?MAKE:d_umask: Inlibc
?MAKE: -pick add $@ %<
?S:d_umask:
?S: This variable conditionally defines the HAS_UMASK symbol, which
?S: indicates to the C program that the umask() routine is available.
?S: to set and get the value of the file creation mask.
?S:.
?C:HAS_UMASK :
?C: This
symbol, if defined, indicates that the umask routine is
?C: available to set and get the value of the file creation mask.
?C:.
?H:#$d_umask HAS_UMASK /**/

```

```
?H:
?LINT:set d_umask
: see if umask exists
set umask d_umask
eval $inlibc
```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/d_umask.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id$
```

```
?RCS:
```

```
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
```

```
?RCS:
```

```
?RCS: You may redistribute only under the terms of the Artistic License,
```

```
?RCS: as specified in the README file that comes with the distribution.
```

```
?RCS: You may reuse parts of this distribution only within the terms of
```

```
?RCS: that same Artistic License; a copy of which may be found at the root
```

```
?RCS: of the source tree for dist 4.0.
```

```
?RCS:
```

```
?RCS: $Log: d_times.U,v $
```

```
?RCS: Revision 3.0.1.2 1995/07/25 14:07:50 ram
```

```
?RCS: patch56: typo fix, sytem -> system
```

```
?RCS:
```

```
?RCS: Revision 3.0.1.1 1994/08/29 16:14:00 ram
```

```
?RCS: patch32: now uses new Typedef unit to compute type information
```

```
?RCS:
```

```
?RCS: Revision 3.0 1993/08/18 12:07:46 ram
```

```
?RCS: Baseline for dist 3.0 netwide release.
```

```
?RCS:
```

```
?X:
```

```
?X: What is the type returned by times() ?
```

```
?X:
```

```
?X: Force inclusion of <sys/types.h>
```

```
?X:INC: i_systypes
```

```
?MAKE:d_times clocktype: Csym Myread Typedef i_systimes
```

```
?MAKE: -pick
```

```
add $@ %<
```

```
?S:d_times:
```

```
?S: This variable conditionally defines the HAS_TIMES symbol, which indicates
```

```
?S: that the times() routine exists. The times() routine is normally
```

```
?S: provided on UNIX systems. You may have to include <sys/times.h>.
```

```
?S:.
```

```
?S:clocktype:
```

```
?S: This variable holds the type returned by times(). It can be long,
```

```
?S: or clock_t on BSD sites (in which case <sys/types.h> should be
```

```
?S: included).
```

```

?S:.
?C:HAS_TIMES (TIMES):
?C: This symbol, if defined, indicates that the times() routine exists.
?C: Note that this became obsolete on some systems (SUNOS), which now
?C: use getrusage(). It may be necessary to include <sys/times.h>.
?C:.
?C:Clock_t (CLOCKTYPE):
?C: This symbol holds the type returned by times(). It can be long,
?C: or clock_t on BSD sites (in which case <sys/types.h> should be
?C: included).
?C:.
?H:#$d_times HAS_TIMES /**/
?H:#define Clock_t $clocktype /* Clock time */
?H:.
?T:val inc
: see if times exists
echo " "
if set times val -f d_times; eval $csym;
$val; then
echo 'times() found.' >&4
d_times="$define"
inc="
case "$i_systimes" in
"$define") inc='sys/times.h';
esac
set clock_t clocktype long stdio.h sys/types.h $inc
eval $typedef
dflt="$clocktype"
echo " "
rp="What type is returned by times() on this system?"
./myread
clocktype="$ans"
else
echo 'times() NOT found, hope that will do.' >&4
d_times="$undef"
?X: The following is needed for typedef (won't like an empty variable)
clocktype='int'
fi

```

Found in path(s):

```

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/d_times.U

```

No license file was found, but licenses were detected in source scan.

```

?RCS: $Id: i_ndbm.U,v 3.0.1.1 1995/05/12 12:16:53 ram Exp $

```

```

?RCS:

```

```

?RCS: Copyright (c) 1991-1993, Raphael Manfredi

```

```

?RCS:

```

?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 3.0.
?RCS:
?RCS: \$Log: i_ndbm.U,v \$
?RCS: Revision 3.0.1.1 1995/05/12 12:16:53 ram
?RCS: patch54: made more robust by checking both header and lib (ADO)
?RCS:
?RCS: Revision 3.0 1993/08/18 12:08:23 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:i_ndbm i_gdbmndbm i_gdbm_ndbm d_ndbm d_ndbm_h_uses_prototypes \
d_gdbmndbm_h_uses_prototypes d_gdbm_ndbm_h_uses_prototypes: \
Inhdr Inlibc Setvar test d_cplusplus extern_C echo Protochk
?MAKE: -pick add \$@ %<
?S:i_ndbm:
?S: This
variable conditionally defines the I_NDBM symbol, which
?S: indicates to the C program that <ndbm.h> exists and should
?S: be included.
?S:.
?C:I_NDBM:
?C: This symbol, if defined, indicates that <ndbm.h> exists and should
?C: be included.
?C:.
?S:i_gdbmndbm:
?S: This variable conditionally defines the I_GDBMNDBM symbol, which
?S: indicates to the C program that <gdbm/ndbm.h> exists and should
?S: be included. This was the location of the ndbm.h compatibility file
?S: in RedHat 7.1.
?S:.
?C:I_GDBMNDBM:
?C: This symbol, if defined, indicates that <gdbm/ndbm.h> exists and should
?C: be included. This was the location of the ndbm.h compatibility file
?C: in RedHat 7.1.
?C:.
?S:i_gdbm_ndbm:
?S: This variable conditionally defines the I_GDBM_NDBM symbol, which
?S: indicates to the C program that <gdbm-ndbm.h> exists and should
?S: be included. This is the location of the ndbm.h compatibility file
?S: in Debian 4.0.
?S:.
?C:I_GDBM_NDBM:
?C: This symbol, if defined, indicates
that <gdbm-ndbm.h> exists and should
?C: be included. This is the location of the ndbm.h compatibility file

?C: in Debian 4.0.

?C:.

?S:d_ndbm:

?S: This variable conditionally defines the HAS_NDBM symbol, which

?S: indicates that both the ndbm.h include file and an appropriate ndbm

?S: library exist. Consult the different i_*ndbm variables

?S: to find out the actual include location. Sometimes, a system has the

?S: header file but not the library. This variable will only be set if

?S: the system has both.

?S:.

?C:HAS_NDBM:

?C: This symbol, if defined, indicates that some form of ndbm.h or compatibility

?C: include exists, along with the appropriate library.

?C:.

?S:d_ndbm_h_uses_prototypes:

?S: This variable conditionally defines the NDBM_H_USES_PROTOTYPES symbol,

?S: which indicates that the ndbm.h include file uses real ANSI C

?S: prototypes instead of K&R style function declarations. K&R style

?S: declarations are unsupported in C++, so the include file requires

?S: special handling

when using a C++ compiler and this variable is

?S: undefined. Consult the different d_*ndbm_h_uses_prototypes variables

?S: to get the same information for alternative ndbm.h include files.

?S:.

?C:NDBM_H_USES_PROTOTYPES:

?C: This symbol, if defined, indicates that <ndbm.h> uses real ANSI C

?C: prototypes instead of K&R style function declarations without any

?C: parameter information. While ANSI C prototypes are supported in C++,

?C: K&R style function declarations will yield errors.

?C:.

?S:d_gdbmndbm_h_uses_prototypes:

?S: This variable conditionally defines the NDBM_H_USES_PROTOTYPES symbol,

?S: which indicates that the gdbm/ndbm.h include file uses real ANSI C

?S: prototypes instead of K&R style function declarations. K&R style

?S: declarations are unsupported in C++, so the include file requires

?S: special handling when using a C++ compiler and this variable is

?S: undefined. Consult the different d_*ndbm_h_uses_prototypes variables

?S: to get the same information for alternative

ndbm.h include files.

?S:.

?C:GDBMNDBM_H_USES_PROTOTYPES:

?C: This symbol, if defined, indicates that <gdbm/ndbm.h> uses real ANSI C

?C: prototypes instead of K&R style function declarations without any

?C: parameter information. While ANSI C prototypes are supported in C++,

?C: K&R style function declarations will yield errors.

?C:.

?S:d_gdbm_ndbm_h_uses_prototypes:

?S: This variable conditionally defines the NDBM_H_USES_PROTOTYPES symbol,

?S: which indicates that the gdbm-ndbm.h include file uses real ANSI C
?S: prototypes instead of K&R style function declarations. K&R style
?S: declarations are unsupported in C++, so the include file requires
?S: special handling when using a C++ compiler and this variable is
?S: undefined. Consult the different d_*ndbm_h_uses_prototypes variables
?S: to get the same information for alternative ndbm.h include files.
?S:.

?C:GDBM_NDBM_H_USES_PROTOTYPES:
?C: This symbol, if defined, indicates that <gdbm-ndbm.h> uses real ANSI C
?C: prototypes
instead of K&R style function declarations without any
?C: parameter information. While ANSI C prototypes are supported in C++,
?C: K&R style function declarations will yield errors.
?C:.

?H:#\$i_ndbm I_NDBM /**/
?H:#\$i_gdbmndbm I_GDBMNDBM /**/
?H:#\$i_gdbm_ndbm I_GDBM_NDBM /**/
?H:#\$d_ndbm HAS_NDBM /**/
?H:#\$d_ndbm_h_uses_prototypes NDBM_H_USES_PROTOTYPES /**/
?H:#\$d_gdbmndbm_h_uses_prototypes GDBMNDBM_H_USES_PROTOTYPES /**/
?H:#\$d_gdbm_ndbm_h_uses_prototypes GDBM_NDBM_H_USES_PROTOTYPES /**/
?H:.

?T:d_dbm_open name hdr ihdr ndbm_hdr_protochk
?LINT:set d_ndbm d_gdbmndbm_h_uses_prototypes d_gdbm_ndbm_h_uses_prototypes
d_ndbm_h_uses_prototypes
: see if ndbm.h is available
set ndbm.h i_ndbm
eval \$inhdr
: Compatibility location for RedHat 7.1
set gdbm/ndbm.h i_gdbmndbm
eval \$inhdr
: Compatibility location for Debian 4.0
set gdbm-ndbm.h i_gdbm_ndbm
eval \$inhdr

val="\$undef"
if \$test "\$i_ndbm" = "\$define" -o "\$i_gdbmndbm" = "\$define" -o "\$i_gdbm_ndbm" = "\$define"; then
: see if dbm_open exists
set
dbm_open d_dbm_open
eval \$inlibc
case "\$d_dbm_open" in
\$undef)
i_ndbm="\$undef"
i_gdbmndbm="\$undef"
i_gdbm_ndbm="\$undef"
echo "We won't be including <ndbm.h>"
val="\$undef"

```

;;
*) val="$define"
;;
esac
fi
set d_ndbm
eval $setvar

ndbm_hdr_protochk='name=$1; hdr=$2;
eval "ihdr=\${i}_$name";
val="$undef";
if $test "$ihdr" = "$define"; then
$echo "Checking if your <$hdr> uses prototypes..." >&4;
case "$d_cplusplus" in
$define) ./protochk "$extern_C void dbm_close(DBM *);" literal "extern \"C\" {" $ihdr $hdr literal "}" &&
val="$define" ;;
*) ./protochk "$extern_C void dbm_close(int, int);" $ihdr $hdr || val="$define" ;;
esac;
case "$val" in
$define) $echo "Your <$hdr> seems to have prototypes";;
*) $echo "Your <$hdr> does not seem to have prototypes";;
esac;
fi;
set "d_${name}_h_uses_prototypes";
eval $setvar'

set ndbm ndbm.h
eval $ndbm_hdr_protochk
set gdbmndbm gdbm/ndbm.h
eval $ndbm_hdr_protochk
set gdbm_ndbm gdbm-ndbm.h
eval $ndbm_hdr_protochk

```

Found

in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/modified/i_ndbm.U

No license file was found, but licenses were detected in source scan.

```

# $Id: errnolist.sh,v 3.0.1.1 1994/01/24 14:00:00 ram Exp ram $
#
# Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
#
# You may redistribute only under the terms of the Artistic Licence,
# as specified in the README file that comes with the distribution.
# You may reuse parts of this distribution only within the terms of
# that same Artistic Licence; a copy of which may be found at the root
# of the source tree for dist 4.0.

```

```

#
# Original Author: Harlan Stenn <harlan@mumps.pfcs.com>
#
# $Log: errnolist.sh,v $
# Revision 3.0.1.1 1994/01/24 14:00:00 ram
# patch16: changed top ln-style config.sh lookup into test-style one
#
# Revision 3.0 1993/08/18 12:04:36 ram
# Baseline for dist 3.0 netwide release.
#

case $CONFIG in
")
if test -f config.sh; then TOP=.;
elif test -f ../config.sh; then TOP=..;
elif test -f ../../config.sh; then TOP=../../;
elif test -f ../../../config.sh; then TOP=../../../;
elif
test -f ../../../../config.sh; then TOP=../../../../;
else
echo "Can't find config.sh."; exit 1
fi
. $TOP/config.sh
;;
esac
case "$0" in
*/*) cd `expr X$0 : 'X\(.*/'` ;;
esac
case "$Serrnolistic" in
") ;;
*)
echo "Making $Serrnolistic ..."
awk -f errnolist.a < /usr/include/sys/errno.h > $Serrnolistic
echo "It would be a good idea to make sure that $Serrnolistic is correct."
esac

```

Found in path(s):

```

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/lib/errnolist.SH

```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: Copyright (c) 2000, Jarkko Hietaniemi

?RCS:

?X:

?X: This unit allows the duplication of the source tree to the current

?X: directory via symbolic links. This must be requested explicitly

?X: by them issuing a -Dmksymlinks on the command line.

?X:

?MAKE:Mksymlinks: Mkdirp lns issymlink src rsrc pkgsrc

?MAKE: -pick add \$@ %<

?F:!UU

?T: dir filename tmppwd filelist

?LINT:extern mksymlinks

@if {test -f ../MANIFEST}

: Duplicate the tree with symbolic links if -Dmksymlinks was supplied

case "\$mksymlinks"

in

\$define|true|[yY]*)

echo " "

case "\$src" in

"|.") echo "Cannot create symlinks in the original directory." >&4

exit 1

::

*) case "\$lns:\$issymlink" in

"ln"" -s:"*"test -"?)

echo "Creating the symbolic links..." >&4

echo "(First creating the subdirectories..." >&4

cd ..

awk '{print \$1}' \$src/MANIFEST | grep / | sed 's:[^/]*\$::' | \

sort -u | while true

do

read dir

test -z "\$dir" && break

./UU/mkdirp \$dir 2>/dev/null

if test -d \$dir; then

: ok

else

echo "Failed to create '\$dir'. Aborting." >&4

exit 1

fi

done

echo "(Now creating the symlinks..." >&4

awk '{print \$1}' \$src/MANIFEST | while true; do

read filename

test -z "\$filename" && break

if test -f \$filename; then

```

    if $issymmlink $filename; then
        rm -f $filename
    fi
fi
if test -f $filename; then
    echo "$filename already exists, not symlinking."
else
?X: Note that the following works because "$pkgsrc" is absolute
    ln
-s $pkgsrc/$filename $filename
    fi
done
?X: Check that everything was correctly copied
    echo "(Checking current directory...)" >&4
cd UU
awk '$1 !~ /PACK[A-Z]+/ {print $1}' "$rsrc/MANIFEST" | \
(split -1 50 2>/dev/null || split -50)
rm -f missing
tmppwd=`pwd`
for filelist in x??.; do
    (cd ..; ls `cat "$tmppwd/$filelist" ` \
    >/dev/null 2>>"$tmppwd/missing")
done
if test -s missing; then
    echo "Failed duplication of source tree. Aborting." >&4
    exit 1
fi
;;
*) echo "(I cannot figure out how to do symbolic links, ignoring!)" >&4
;;
esac
;;
esac
;;
esac
;;
esac
@end

```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/Mksymlinks.U
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_setsid.U 1 2006-08-24 12:32:52Z rmanfredi \$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic Licence,

?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: \$Log: d_setsid.U,v \$
?RCS: Revision 3.0.1.1 1994/01/24 14:06:49 ram
?RCS: patch16: created
?RCS:
?RCS: Revision 3.0 1993/08/18 12:05:56 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:d_setsid: Inlibc
?MAKE: -pick add \$@ %<
?S:d_setsid:
?S: This variable conditionally defines HAS_SETSID if setsid() is
?S: available to set the process group ID.
?S:.
?C:HAS_SETSID:
?C: This symbol, if defined, indicates that the setsid routine is
?C: available
to set the process group ID.
?C:.
?H:#\$d_setsid HAS_SETSID /**/
?H:.
?LINT:set d_setsid
: see if setsid exists
set setsid d_setsid
eval \$inlibc

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/d_setsid.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: i_dlfcn.U 1 2006-08-24 12:32:52Z rmanfredi \$
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: Original Author: Andy Dougherty <doughera@lafcol.lafayette.edu>
?RCS:
?RCS: \$Log: i_dlfcn.U,v \$

?RCS: Revision 3.0.1.1 1994/08/29 16:21:53 ram
?RCS: patch32: created by ADO
?RCS:
?MAKE:i_dlfcn: Inhdr
?MAKE: -pick add \$@ %<
?S:i_dlfcn:
?S: This variable conditionally defines the I_DLFCN symbol, which
?S: indicates to the C program that <dlfcn.h> exists and should
?S: be included.
?S:.
?C:I_DLFCN:
?C: This symbol, if defined, indicates that <dlfcn.h> exists
and should
?C: be included.
?C:.
?H:#\$i_dlfcn I_DLFCN /**/
?H:.
?LINT:set i_dlfcn
: see if dlfcn is available
set dlfcn.h i_dlfcn
eval \$inhdr

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/i_dlfcn.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: Original Author: Tye McQueen <tye@metronet.com>
?RCS:
?RCS: \$Log: d_stdstdio.U,v \$
?RCS: Revision 3.0.1.3 1997/02/28 15:46:32 ram
?RCS: patch61: merged with perl5's unit
?RCS:
?RCS: Revision 3.0.1.2 1995/07/25 14:06:54 ram
?RCS: patch56: typo fix on ?C: line for FILE_bufsiz
?RCS: patch56: fixed unbalanced parenthesis (ADO)
?RCS: patch56: check whether FILE_cnt and FILE_ptr can be assigned to (ADO)
?RCS:

?RCS: Revision 3.0.1.1 1995/05/12 12:12:11 ram

?RCS: patch54: complete rewrite by Tye McQueen
to fit modern systems

?RCS:

?RCS: Revision 3.0 1993/08/18 12:07:31 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?MAKE:d_stdstdio d_stdiobase stdio_ptr stdio_cnt stdio_base \
stdio_bufsiz d_stdio_cnt_lval d_stdio_ptr_lval stdio_filbuf: cat \
+cc +ccflags contains +ldflags +libs rm_try \
Setvar Findhdr Oldconfig

?MAKE: -pick add \$@ %<

?S:d_stdstdio:

?S: This variable conditionally defines USE_STDIO_PTR if this system
?S: has a FILE structure declaring usable _ptr and _cnt fields (or
?S: equivalent) in stdio.h.

?S:.

?S:stdio_ptr:

?S: This variable defines how, given a FILE pointer, fp, to access the
?S: _ptr field (or equivalent) of stdio.h's FILE structure. This will
?S: be used to define the macro FILE_ptr(fp).

?S:.

?S:d_stdio_ptr_lval:

?S: This variable conditionally defines STDIO_PTR_LVALUE if the
?S: FILE_ptr macro can be used as an lvalue.

?S:.

?S:stdio_cnt:

?S: This variable defines how, given a FILE pointer, fp, to access the
?S: _cnt field (or equivalent) of
stdio.h's FILE structure. This will
?S: be used to define the macro FILE_cnt(fp).

?S:.

?S:d_stdio_cnt_lval:

?S: This variable conditionally defines STDIO_CNT_LVALUE if the
?S: FILE_cnt macro can be used as an lvalue.

?S:.

?S:stdio_filbuf:

?S: This variable defines how, given a FILE pointer, fp, to tell
?S: stdio to refill it's internal buffers (?). This will
?S: be used to define the macro FILE_filbuf(fp).

?S:.

?S:d_stdiobase:

?S: This variable conditionally defines USE_STDIO_BASE if this system
?S: has a FILE structure declaring a usable _base field (or equivalent)
?S: in stdio.h.

?S:.

?S:stdio_base:

?S: This variable defines how, given a FILE pointer, fp, to access the

?S: `_base` field (or equivalent) of `stdio.h`'s `FILE` structure. This will
 ?S: be used to define the macro `FILE_base(fp)`.

?S:.

?S:`stdio_bufsiz`:

?S: This variable defines how, given a `FILE` pointer, `fp`, to determine
 ?S: the number of bytes store in the I/O buffer pointer to by the
 ?S: `_base` field (or equivalent) of `stdio.h`'s
 FILE structure. This will
 ?S: be used to define the macro `FILE_bufsiz(fp)`.

?S:.

?C:`USE_STDIO_PTR ~ d_stdstdio (USE_STD_STDIO STDSTDIO)`:

?C: This symbol is defined if the `_ptr` and `_cnt` fields (or similar)
 ?C: of the `stdio` `FILE` structure can be used to access the `stdio` buffer
 ?C: for a file handle. If this is defined, then the `FILE_ptr(fp)`
 ?C: and `FILE_cnt(fp)` macros will also be defined and should be used
 ?C: to access these fields.

?C:.

?C:`FILE_ptr`:

?C: This macro is used to access the `_ptr` field (or equivalent) of the
 ?C: `FILE` structure pointed to by its argument. This macro will always be
 ?C: defined if `USE_STDIO_PTR` is defined.

?C:.

?C:`STDIO_PTR_LVALUE`:

?C: This symbol is defined if the `FILE_ptr` macro can be used as an
 ?C: lvalue.

?C:.

?C:`FILE_cnt`:

?C: This macro is used to access the `_cnt` field (or equivalent) of the
 ?C: `FILE` structure pointed to by its argument. This macro will always be
 ?C: defined if `USE_STDIO_PTR` is defined.

?C:.

?C:`STDIO_CNT_LVALUE`:

?C: This symbol is defined
 if the `FILE_cnt` macro can be used as an
 ?C: lvalue.

?C:.

?C:`FILE_filbuf`:

?C: This macro is used to access the internal `stdio_filbuf` function
 ?C: (or equivalent), if `STDIO_CNT_LVALUE` and `STDIO_PTR_LVALUE`
 ?C: are defined. It is typically either `_filbuf` or `__filbuf`.
 ?C: This macro will only be defined if both `STDIO_CNT_LVALUE` and
 ?C: `STDIO_PTR_LVALUE` are defined.

?C:.

```
?H:?d_stdstdio:#$d_stdstdio USE_STDIO_PTR /**/
?H:?d_stdstdio:#ifdef USE_STDIO_PTR
?H:#define FILE_ptr(fp) $stdio_ptr
?H:#$d_stdio_ptr_lval STDIO_PTR_LVALUE /**/
?H:#define FILE_cnt(fp) $stdio_cnt
```

```

?H:#$d_stdio_cnt_lval STDIO_CNT_LVALUE /**/
?H:?d_stdstdio:#if defined(STDIO_PTR_LVALUE) && defined(STDIO_CNT_LVALUE)
?H:#define FILE_filbuf(fp) $stdio_filbuf /**/
?H:?d_stdstdio:#endif
?H:?d_stdstdio:#endif
?H:.
?W:d_stdstdio:FILE_ptr FILE_cnt FILE_filbuf
?C:USE_STDIO_BASE ~ d_stdibase:
?C: This symbol is defined if the _base field (or similar) of the
?C: stdio FILE structure can be used to access the stdio buffer
for
?C: a file handle. If this is defined, then the FILE_base(fp) macro
?C: will also be defined and should be used to access this field.
?C: Also, the FILE_bufsiz(fp) macro will be defined and should be used
?C: to determine the number of bytes in the buffer. USE_STDIO_BASE
?C: will never be defined unless USE_STDIO_PTR is.
?C:.
?C:FILE_base:
?C: This macro is used to access the _base field (or equivalent) of the
?C: FILE structure pointed to by its argument. This macro will always be
?C: defined if USE_STDIO_BASE is defined.
?C:.
?C:FILE_bufsiz:
?C: This macro is used to determine the number of bytes in the I/O
?C: buffer pointed to by _base field (or equivalent) of the FILE
?C: structure pointed to its argument. This macro will always be defined
?C: if USE_STDIO_BASE is defined.
?C:.
?H:?d_stdibase:#$d_stdibase USE_STDIO_BASE /**/
?H:?d_stdibase:#ifdef USE_STDIO_BASE
?H:#define FILE_base(fp) $stdio_base
?H:#define FILE_bufsiz(fp) $stdio_bufsiz
?H:?d_stdibase:#endif
?H:.
?W:d_stdibase:FILE_base
FILE_bufsiz
?LINT:set d_stdstdio d_stdibase
?T:ptr_lval cnt_lval filbuf xxx
?F:!try
: see if _ptr and _cnt from stdio act std
echo " "
if $contains '_IO_fpos_t' `./findhdr stdio.h` >/dev/null 2>&1 ; then
echo "(Looks like you have stdio.h from Linux.)"
case "$stdio_ptr" in
") stdio_ptr='((fp)->_IO_read_ptr)'
ptr_lval=$define
;;
*) ptr_lval=$d_stdio_ptr_lval;;

```

```

esac
case "$stdio_cnt" in
") stdio_cnt='((fp)->_IO_read_end - (fp)->_IO_read_ptr)'
cnt_lval=$undef
;;
*) cnt_lval=$d_stdio_cnt_lval;;
esac
case "$stdio_base" in
") stdio_base='((fp)->_IO_read_base)';;
esac
case "$stdio_bufsiz" in
") stdio_bufsiz='((fp)->_IO_read_end - (fp)->_IO_read_base)';;
esac
else
case "$stdio_ptr" in
") stdio_ptr='((fp)->_ptr)'
ptr_lval=$define
;;
*) ptr_lval=$d_stdio_ptr_lval;;
esac
case "$stdio_cnt" in
") stdio_cnt='((fp)->_cnt)'
cnt_lval=$define
;;
*) cnt_lval=$d_stdio_cnt_lval;;
esac
case "$stdio_base" in
") stdio_base='((fp)->_base)';;
esac
case
"$stdio_bufsiz" in
") stdio_bufsiz='((fp)->_cnt + (fp)->_ptr - (fp)->_base)';;
esac
fi
: test whether _ptr and _cnt really work
echo "Checking how std your stdio is..." >&4
$cat >try.c <<EOP
#include <stdio.h>
#define FILE_ptr(fp) $stdio_ptr
#define FILE_cnt(fp) $stdio_cnt
int main() {
FILE *fp = fopen("try.c", "r");
char c = getc(fp);
if (
18 <= FILE_cnt(fp) &&
strncmp(FILE_ptr(fp), "include <stdio.h>\n", 18) == 0
)
exit(0);

```

```

exit(1);
}
EOP
val="$undef"
if $cc $ccflags $ldflags -o try try.c $libs >/dev/null 2>&1; then
if ./try; then
echo "Your stdio acts pretty std."
val="$define"
else
echo "Your stdio isn't very std."
fi
else
echo "Your stdio doesn't appear very std."
fi
$rm_try
set d_stdstdio
eval $setvar

@if STDIO_PTR_LVALUE || d_stdio_ptr_lval
: Can _ptr be used as an lvalue?
?X: Only makes sense if we have a known stdio implementation.
case "$d_stdstdio$_ptr_lval" in
$define$define) val=$define ;;
*) val=$undef ;;
esac
set d_stdio_ptr_lval
eval
$setvar

@end

@if STDIO_CNT_LVALUE || d_stdio_cnt_lval
: Can _cnt be used as an lvalue?
?X: Only makes sense if we have a known stdio implementation.
case "$d_stdstdio$_cnt_lval" in
$define$define) val=$define ;;
*) val=$undef ;;
esac
set d_stdio_cnt_lval
eval $setvar

@end

@if FILE_filbuf
: How to access the stdio _filbuf or __filbuf function.
: If this fails, check how the getc macro in stdio.h works.
case "${d_stdio_ptr_lval}${d_stdio_cnt_lval}" in
${define}${define})
: Try hint value, if any, then _filbuf, __filbuf, _fill, then punt.
: _fill is for OS/2.

```

```

xxx='notok'
for filbuf in $stdio_filbuf '_filbuf(fp)' '__filbuf(fp)' '_fill(fp)' ; do
  $cat >try.c <<EOP
#include <stdio.h>
#define FILE_ptr(fp) $stdio_ptr
#define FILE_cnt(fp) $stdio_cnt
#define FILE_filbuf(fp) $filbuf
int main() {
  FILE *fp = fopen("try.c", "r");
  int c;
  c = getc(fp);
  c = FILE_filbuf(fp); /* Just looking for linker errors.*/
  exit(0);
}
EOP
if $cc $ccflags $ldflags -o try try.c $libs >/dev/null 2>&1 &&
./try; then
  echo "Your stdio appears to use $filbuf"
  stdio_filbuf="$filbuf"
  xxx='ok'
  break
else
  echo "Hmm. $filbuf doesn't seem to work."
fi
$rm_try
done
case "$xxx" in
notok) echo "I can't figure out how to access _filbuf"
  echo "I'll just have to work around it."
  d_stdio_ptr_lval="$undef"
  d_stdio_cnt_lval="$undef"
  ;;
esac
;;
esac
@end
@if d_stdibase || USE_STDIO_BASE || FILE_base || FILE_bufsiz
: see if _base is also standard
val="$undef"
case "$d_stdstdio" in
$define)
  $cat >try.c <<EOP
#include <stdio.h>
#define FILE_base(fp) $stdio_base
#define FILE_bufsiz(fp) $stdio_bufsiz
int main() {
  FILE *fp = fopen("try.c", "r");
  char c = getc(fp);

```

```

if (
  19 <= FILE_bufsiz(fp) &&
  strncmp(FILE_base(fp), "#include <stdio.h>\n", 19) == 0
)
  exit(0);
exit(1);
}
EOP
if $cc $ccflags $ldflags -o try try.c $libs > /dev/null 2>&1; then
  if ./try; then
    echo "And its _base field acts std."
    val="$define"
  else
    echo "But its _base field isn't std."
  fi
else
  echo
  "However, it seems to be lacking the _base field."
fi
$rm_try
;;
esac
set d_stdibase
eval $setvar

@end

```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/d_stdstdio.U
```

No license file was found, but licenses were detected in source scan.

```

?RCS: $Id: d_mblen.U 1 2006-08-24 12:32:52Z rmanfredi $
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: Original Author: Andy Dougherty <doughera@lafcol.lafayette.edu>
?RCS:
?RCS: $Log: d_mblen.U,v $
?RCS: Revision 3.0.1.1 1994/08/29 16:09:40 ram
?RCS: patch32: created by ADO
?RCS:

```

?MAKE:d_mblen: Inlibc
?MAKE: -pick add \$@ %<
?S:d_mblen:
?S: This variable conditionally defines the HAS_MBLEN symbol, which
?S: indicates to the C program that the mblen() routine is available
?S: to find the number of bytes in a multibyte character.
?S:.
?C:HAS_MBLEN:
?C: This
symbol, if defined, indicates that the mblen routine is available
?C: to find the number of bytes in a multibyte character.
?C:.
?H:#\$d_mblen HAS_MBLEN /**/
?H:.
?LINT:set d_mblen
: see if mblen exists
set mblen d_mblen
eval \$inlibc

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/d_mblen.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: usedtrace.U,v \$
?RCS:
?RCS: Copyright (c) 2008 H.Merijn Brand
?RCS:
?RCS: You may distribute under the terms of either the GNU General Public
?RCS: License or the Artistic License, as specified in the README file.
?RCS:
?RCS: \$Log: usedtrace.U,v \$
?RCS:
?MAKE:usedtrace dtrace: Myread Oldconfig Setvar Getfile test
?MAKE: -pick add \$@ %<
?Y:TOP
?S:usedtrace:
?S: This variable indicates whether we are compiling with dtrace
?S: support. See also dtrace.
?S:.
?S:dtrace:
?S: This variable holds the location of the dtrace executable.
?S:.
?C:USE_DTRACE:
?C: This symbol, if defined, indicates that Perl should
?C: be built with support for DTrace.
?C:.
?H:#\$usedtrace USE_DTRACE /**/

```
?H:
?T:dflt_dtrace
?LINT:set usedtrace
?LINT:set dtrace
: DTrace support
dflt_dtrace='/usr/sbin/dtrace'
$test -x /usr/bin/dtrace && dflt_dtrace='/usr/bin/dtrace'
```

```
cat <<EOM
```

Perl can be built to support DTrace on platforms that support it.
DTrace is a diagnosis and performance analysis tool from Sun.

If this doesn't make any sense to you, just accept the default.

```
EOM
```

```
while $test 1 ; do
case "$usedtrace" in
$define|true|[yY]*)
dflt='y'
;;
?*)
dflt='y'
dflt_dtrace=$usedtrace
;;
*)
dflt='n'
;;
esac
```

```
rp='Support DTrace if available?'
./myread
case "$ans" in
y|Y) val="$define" ;;
*) val="$undef" ;;
esac
set usedtrace
eval $setvar

test "X$usedtrace" != "X$define" && break
```

```
echo " "
rp='Where is the dtrace executable?'
dflt=$dflt_dtrace
./getfile
val="$ans"
set dtrace
```

```
eval $setvar
```

```
if $test -f $dtrace
then
if $dtrace -h -s ../perldtrace.d \
-o perldtrace.tmp >/dev/null 2>&1 \
&& rm -f perldtrace.tmp
then
echo " "
echo "Good: your $dtrace knows about the -h flag."
else
cat >&2 <<EOM
```

```
*** $me: Fatal Error: $dtrace doesn't support -h flag
***
*** Your installed dtrace doesn't support the -h switch to compile a D
*** program into a C header. Can't continue.
```

```
EOM
```

```
exit
1
fi
break;
fi
```

```
case "$fastread" in
yes)
cat >&2 <<EOM
```

```
*** $me: Fatal Error: $dtrace not found.
*** Can't continue.
```

```
EOM
```

```
exit 1
;;
*)
echo "*** $dtrace was not found."
echo " "
;;
esac
done
```

```
Found in path(s):
```

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/perl/usedtrace.U
```

```
No license file was found, but licenses were detected in source scan.
```

```
?RCS: $Id: d_random_r.U,v 0RCS:
```

```

?RCS: Copyright (c) 2002,2003 Jarkko Hietaniemi
?RCS:
?RCS: You may distribute under the terms of either the GNU General Public
?RCS: License or the Artistic License, as specified in the README file.
?RCS:
?RCS: Generated by the reentr.pl from the Perl 5.8 distribution.
?RCS:
?MAKE:d_random_r random_r_proto: Inlibc Protochk Hasproto i_systypes \
  usethreads i_stdlib extern_C
?MAKE: -pick add $@ %<
?S:d_random_r:
?S: This variable conditionally defines the HAS_RANDOM_R symbol,
?S: which indicates to the C program that the random_r()
?S: routine is available.
?S:.
?S:random_r_proto:
?S: This variable encodes the prototype of random_r.
?S: It is zero if d_random_r is undef, and one of the
?S: REENTRANT_PROTO_T_ABC macros of reentr.h if d_random_r
?S: is defined.
?S:.
?C:HAS_RANDOM_R:
?C: This symbol, if defined, indicates that the random_r routine
?C: is available to random re-entrantly.
?C:.
?C:RANDOM_R_PROTO:
?C: This
?C: symbol encodes the prototype of random_r.
?C: It is zero if d_random_r is undef, and one of the
?C: REENTRANT_PROTO_T_ABC macros of reentr.h if d_random_r
?C: is defined.
?C:.
?H:#$d_random_r HAS_RANDOM_R /**/
?H:#define RANDOM_R_PROTO $random_r_proto /**/
?H:.
?T:try hdrs d_random_r_proto
: see if random_r exists
set random_r d_random_r
eval $inlibc
case "$d_random_r" in
"$define")
  hdrs="$i_systypes sys/types.h define stdio.h $i_stdlib stdlib.h"
  case "$d_random_r_proto:$usethreads" in
  ":define") d_random_r_proto=define
    set d_random_r_proto random_r $hdrs
    eval $hasproto ;;
  *) ;;
  esac

```

```

case "$d_random_r_proto" in
define)
case "$random_r_proto" in
"|0) try='int random_r(int*, struct random_data*);'
./protochk "$extern_C $try" $hdrs && random_r_proto=I_iS ;;
esac
case "$random_r_proto" in
"|0) try='int random_r(long*, struct random_data*);'
./protochk "$extern_C $try" $hdrs && random_r_proto=I_lS ;;
esac
case "$random_r_proto" in
"|0)
try='int random_r(struct random_data*, int32_t*);'
./protochk "$extern_C $try" $hdrs && random_r_proto=I_St ;;
esac
case "$random_r_proto" in
"|0) d_random_r=undef
random_r_proto=0
echo "Disabling random_r, cannot determine prototype." >&4 ;;
*) case "$random_r_proto" in
REENTRANT_PROTO*) ;;
*) random_r_proto="REENTRANT_PROTO_$random_r_proto" ;;
esac
echo "Prototype: $try" ;;
esac
;;
*) case "$usetthreads" in
define) echo "random_r has no prototype, not using it." >&4 ;;
esac
d_random_r=undef
random_r_proto=0
;;
esac
;;
*) random_r_proto=0
;;
esac

```

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/threads/d_random_r.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1999 Jarkko Hietaniemi

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?MAKE:d_statfs_f_flags: \
Hasfield i_sysparam i_sysmount i_systypes \
i_sysvfs i_sysstatfs Setvar d_statfs_s

?MAKE: -pick add \$@ %<

?S:d_statfs_f_flags:

?S: This variable conditionally defines the HAS_STRUCT_STATFS_F_FLAGS

?S: symbol, which indicates to struct statfs from has f_flags member.

?S: This kind of struct statfs is coming from sys/mount.h (BSD),

?S: not from sys/statfs.h (SYSV).

?S:.

?C:HAS_STRUCT_STATFS_F_FLAGS:

?C: This symbol, if defined, indicates that the struct statfs

?C: does have the f_flags member containing the mount flags of

?C: the filesystem containing the file.

?C: This kind of struct statfs is coming from <sys/mount.h> (BSD 4.3),

?C: not from <sys/statfs.h> (SYSV). Older BSDs

(like Ultrix) do not

?C: have statfs() and struct statfs, they have ustat() and getmnt()

?C: with struct ustat and struct fs_data.

?C:.

?H:#\$d_statfs_f_flags HAS_STRUCT_STATFS_F_FLAGS /**/

?H:.

?LINT:set d_statfs_f_flags

: see if struct statfs knows about f_flags

case "\$d_statfs_s" in

define)

echo " "

echo "Checking to see if your struct statfs has f_flags field..." >&4

set d_statfs_f_flags statfs f_flags \$i_systypes sys/types.h \$i_sysparam sys/param.h \$i_sysmount sys/mount.h

\$i_sysvfs sys/vfs.h \$i_sysstatfs sys/statfs.h

eval \$hasfield

::

*) val="\$undef"

set d_statfs_f_flags

eval \$setvar

::

esac

case "\$d_statfs_f_flags" in

"\$define") echo "Yes, it does." ;;

*) echo "No, it doesn't." ;;

esac

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_statfs_f_flags.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: man1dir.U,v 3.2 1999/07/08 20:57:21 doughera Exp doughera \$

?RCS:

?RCS: Copyright (c) 1996, 1999 Andy Dougherty

?RCS: Copyright (c) 1991-1993, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 3.0.

?RCS:

?RCS: \$Log: man1dir.U,v \$

?RCS: Revision 3.2 1999/07/08 20:57:21 doughera

?RCS: Used installprefix.

?RCS:

?RCS: Revision 3.1 1999/07/08 20:52:19 doughera

?RCS: Updated for perl5.005_5x

?RCS:

?RCS: Revision 3.0.1.1 1997/02/28 16:10:29 ram

?RCS: patch61: created

?RCS:

?X: This was originally specific to perl5. Since perl5 has man pages that

?X: go in both man1/ and man3/ directories, we need both man1dir

?X: and

man3dir. This unit is basically dist's mansrc.U with

?X: man1 used instead of man everywhere.

?X:

?MAKE:man1dir man1direxp man1ext installman1dir: cat nroff Loc Oldconfig \

spackage test Getfile Setprefixvar Prefixit Prefixup sysman Myread \

prefixexp

?MAKE: -pick add \$@ %<

?Y:TOP

?D:man1dir="

?S:man1dir:

?S: This variable contains the name of the directory in which manual

?S: source pages are to be put. It is the responsibility of the

?S: Makefile.SH to get the value of this into the proper command.

?S: You must be prepared to do the ~name expansion yourself.

?S:.

?D:man1direxp="

?S:man1direxp:

?S: This variable is the same as the man1dir variable, but is filename

?S: expanded at configuration time, for convenient use in makefiles.

?S:.

?D:installman1dir="

?S:installman1dir:

?S: This variable is really the same as man1direxp, unless you are using

?S: AFS in which case it points to the read/write location whereas

?S: man1direxp only points to the read-only access location.

For extra

?S: portability, you should only use this variable within your makefiles.

?S:.

?S:man1ext:

?S: This variable contains the extension that the manual page should

?S: have: one of 'n', 'l', or '1'. The Makefile must supply the 'l'.

?S: See man1dir.

?S:.

?T:lookpath

?LINT:change prefixvar

?LINT:set man1direxp

: determine where manual pages go

set man1dir man1dir none

eval \$prefixit

\$cat <<EOM

\$spackage has manual pages available in source form.

EOM

case "\$nroff" in

nroff)

echo "However, you don't have nroff, so they're probably useless to you."

case "\$man1dir" in

") man1dir="none";;

esac;;

esac

echo "If you don't want the manual sources installed, answer 'none'."

case "\$man1dir" in

' ') dflt=none

::

")

lookpath="\$prefixexp/share/man/man1"

lookpath="\$lookpath \$prefixexp/man/man1 \$prefixexp/man/l_man/man1"

lookpath="\$lookpath \$prefixexp/man/p_man/man1"

lookpath="\$lookpath \$prefixexp/man/u_man/man1"

lookpath="\$lookpath \$prefixexp/man/man.1"

?X: Experience has shown people

expect man1dir to be under prefix,

?X: so we now always put it there. Users who want other behavior

?X: can answer interactively or use a command line option.

?X: Does user have System V-style man paths.

case "\$sysman" in

*/*_man*) dflt=`./loc . \$prefixexp/l_man/man1 \$lookpath` ;;

*) dflt=`./loc . \$prefixexp/man/man1 \$lookpath` ;;

esac

set dflt

```

eval $prefixup
;;
*) dflt="$man1dir"
;;
esac
echo " "
fn=dn+~
rp="Where do the main $spackage manual pages (source) go?"
./getfile
if $test "X$man1direxp" != "X$ansexp"; then
installman1dir="
fi
prefixvar=man1dir
./setprefixvar

```

```

case "$man1dir" in
") man1dir='
installman1dir=";;
esac

```

: What suffix to use on installed man pages

```

case "$man1dir" in
')
man1ext='0'
;;
*)
rp="What suffix should be used for the main $spackage man pages?"
case "$man1ext" in
") case "$man1dir" in
*1) dflt=1 ;;
*1p) dflt=1p ;;
*1pm) dflt=1pm ;;
*1) dflt=1;;
*n) dflt=n;;
*o) dflt=o;;
*p) dflt=p;;
*C) dflt=C;;
*L) dflt=L;;
*L1)
dflt=L1;;
*) dflt=1;;
esac
;;
*) dflt="$man1ext";;
esac
./myread
man1ext="$ans"

```

```
;;  
esac
```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/installldirs/man1dir.U
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: libc.U,v \$

?RCS: Revision 3.0.1.10 1997/02/28 15:56:48 ram

?RCS: patch61: replaced .a with \$_a all over the place

?RCS: patch61: added support for HPUX-10 nm output

?RCS:

?RCS: Revision 3.0.1.9 1995/07/25 14:11:56 ram

?RCS: patch56: now knows about OS/2 platforms

?RCS:

?RCS: Revision 3.0.1.8 1995/05/12 12:20:47 ram

?RCS: patch54: made sure only most recent version of shared lib is picked

?RCS: patch54: final "nm -p" check now uses xscan and xrun like everybody

?RCS: patch54: can now grok

linux nm output with lead __IO (ADO)

?RCS: patch54: added support for linux ELF output, using 'W' for alias (ADO)

?RCS:

?RCS: Revision 3.0.1.7 1994/10/29 16:23:40 ram

?RCS: patch36: now looks for shared libraries before anything else (ADO)

?RCS: patch36: added new nm output format (ADO)

?RCS:

?RCS: Revision 3.0.1.6 1994/08/29 16:28:10 ram

?RCS: patch32: added I-type symbols for nm output parsing on Linux

?RCS:

?RCS: Revision 3.0.1.5 1994/06/20 07:03:24 ram

?RCS: patch30: checks are now presented by succession of if/elif

?RCS: patch30: uniformized checks for shared objects with new so symbol

?RCS:

?RCS: Revision 3.0.1.4 1994/05/06 15:06:33 ram

?RCS: patch23: added shared library knowledge (ADO and WED)

?RCS:

?RCS: Revision 3.0.1.3 1994/01/24 14:12:17 ram

```

?RCS: patch16: can now export nm_extract as an internal-use only variable
?RCS:
?RCS: Revision 3.0.1.2 1993/09/13 16:09:03 ram
?RCS: patch10: added special handling for Apollo systems (WAD)
?RCS:
?RCS: Revision 3.0.1.1
1993/08/27 14:40:03 ram
?RCS: patch7: added entry for /usr/shlib/libc.so (OSF/1 machines)
?RCS:
?RCS: Revision 3.0 1993/08/18 12:08:57 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:libc libnames +nm_extract: echo n c rm test grep Getfile Myread \
Oldconfig Loc sed libs incpath libpth ar runnm nm nm_opt nm_so_opt \
contains xlibpth so osname trnl tr sort uniq _o _a
?MAKE: -pick add $@ %<
?S:libc:
?S: This variable contains the location of the C library.
?S:.
?S:libnames:
?S: The constructed list of library names. Normally empty, but hint files
?S: may set this for later perusal by Configure.
?S:.
?S:nm_extract:
?S: This variable holds the name of the extraction command used to process
?S: the output of nm and yield the list of defined symbols. It is used
?S: internally by Configure.
?S:.
?T:thislib try libnames xxx xscan xrun thisname com tans file
?F:!libnames !libc.tmp !tmp.imp
?LINT:change nm_opt runnm
?INIT:libnames=""
: Figure out where the libc is located
case
"$runnm" in
true)
?X: indentation is wrong on purpose--RAM
: get list of predefined functions in a handy place
echo " "
case "$libc" in
") libc=unknown
case "$libs" in
*-lc_s*) libc=`./loc libc_s$_a $libc $libpth`
esac
;;
esac
case "$libs" in
") ;;

```

```

*) for thislib in $libs; do
case "$thislib" in
-|c|-|c_s)
: Handle C library specially below.
;;
-|*)
thislib=`echo $thislib | $sed -e 's/^-|//'^
if try=`. /loc lib$thislib.$so.*' X $libpth`; $test -f "$stry"; then
:
elif try=`. /loc lib$thislib.$so X $libpth`; $test -f "$stry"; then
:
elif try=`. /loc lib$thislib$_a X $libpth`; $test -f "$stry"; then
:
elif try=`. /loc $thislib$_a X $libpth`; $test -f "$stry"; then
:
elif try=`. /loc lib$thislib X $libpth`; $test -f "$stry"; then
:
elif try=`. /loc $thislib X $libpth`; $test -f "$stry"; then
:
elif try=`. /loc $lib$thislib$_a X $xlibpth`; $test -f "$stry"; then
:
else
try="
fi
libnames="$libnames $stry"
;;
*) libnames="$libnames $thislib"
;;
esac
done
;;
esac
?X:
?X: Some systems (e.g. DG/UX) use "environmental" links, which make the test
?X: -f fail. Ditto for symbolic links. So in order to reliably check the
?X: existence of a file, we use test -r. It will still fail with DG/UX links
?X: though, but at least it will detect symbolic links. At some strategic
?X: points, we make use of (test -h), using a sub-shell in case builtin test
?X: does not implement the -h check for symbolic links. This makes it
?X: possible to preset libc in a hint file for instance and have it show up
?X: as-is in the question.
?X:
xxx=normal
case "$libc" in
unknown)
?X:
?X: The sed below transforms .so.9 .so.12 into something like .so.0009 .so.0012,
?X: then sorts on it to allow keeping .so.12 instead of .so.9 as the latest

```

?X: up-to-date library. The initial filename (before sed munging, saved in hold
?X: space via 'h') is appended via 'G' before sorting, then the leading munged
?X: part is removed after sorting. Nice efficient work
from Tye McQueen.

?X: The initial blurfl is here to prevent the trailing pipe from producing an

?X: empty string, causing Configure to output all its set variables!

?X:

```
set /lib/libc.$so
for xxx in $libpth; do
  $test -r $1 || set $xxx/libc.$so
  : The messy sed command sorts on library version numbers.
  $test -r $1 || \
  set `echo blurfl; echo $xxx/libc.$so.[0-9]* | \
  tr ' ' $trnl | egrep -v \.[A-Za-z]*$' | $sed -e '
  h
  s/[0-9][0-9]*/0000&/g
  s/0*\([0-9][0-9][0-9][0-9]\)\^1/g
  G
  s/\n/ / | \
  $sort | $sed -e 's/^\.* //'^
eval set \$$#
done
$test -r $1 || set /usr/ccs/lib/libc.$so
$test -r $1 || set /lib/libsys_s$_a
;;
*)
```

?X: ensure the test below for the (shared) C library will fail

```
set blurfl
;;
esac
if $test -r "$1"; then
  echo "Your (shared) C library seems to be in $1."
  libc="$1"
  elif $test -r /lib/libc && $test -r /lib/clib; then
?X:
?X: Apollo has its C library in /lib/clib AND /lib/libc
?X: not to mention its math library in /lib/syslib...
?X:
echo
"Your C library seems to be in both /lib/clib and /lib/libc."
xxx=apollo
libc='/lib/clib /lib/libc'
if $test -r /lib/syslib; then
  echo "(Your math library is in /lib/syslib.)"
?X: Put syslib in libc -- not quite right, but won't hurt
  libc="$libc /lib/syslib"
fi
elif $test -r "$libc" || (test -h "$libc") >/dev/null 2>&1; then
```

```

echo "Your C library seems to be in $libc, as you said before."
?X: For mips, and...
elif $test -r $incpath/usr/lib/libc$_a; then
  libc=$incpath/usr/lib/libc$_a;
  echo "Your C library seems to be in $libc. That's fine."
elif $test -r /lib/libc$_a; then
  libc=/lib/libc$_a;
  echo "Your C library seems to be in $libc. You're normal."
else
  if tans=`./loc libc$_a blurfl/dyick $libpth`; $test -r "$stans"; then
    :
  elif tans=`./loc libc blurfl/dyick $libpth`; $test -r "$stans"; then
    libnames="$libnames "`./loc clib blurfl/dyick $libpth`
  elif tans=`./loc clib blurfl/dyick $libpth`; $test -r "$stans"; then
    :
  elif tans=`./loc Slibc$_a blurfl/dyick
  $xlibpth`; $test -r "$stans"; then
    :
  elif tans=`./loc Mlibc$_a blurfl/dyick $xlibpth`; $test -r "$stans"; then
    :
  else
    tans=`./loc Llibc$_a blurfl/dyick $xlibpth`
  fi
  if $test -r "$stans"; then
    echo "Your C library seems to be in $stans, of all places."
    libc=$stans
  else
    libc='blurfl'
  fi
fi
if $test $xxx = apollo -o -r "$libc" || (test -h "$libc") >/dev/null 2>&1; then
  dflt="$libc"
cat <<EOM

```

If the guess above is wrong (which it might be if you're using a strange compiler, or your machine supports multiple models), you can override it here.

```

EOM
else
  dflt=""
echo $libpth | $tr ' ' $trnl | $sort | $uniq > libpath
cat >&4 <<EOM

```

I can't seem to find your C library. I've looked in the following places:

```

EOM
$sed 's/^/' libpath
cat <<EOM

```

None of these seems to contain your C library. I need to get its name...

```
EOM
fi
fn=f
rp="Where is your C library?"
./getfile
libc="$sans"

echo " "
echo $libc $libnames | $tr ' ' $trnl | $sort | $uniq > libnames
set X `cat libnames`
shift
xxx=files
case
  $# in 1) xxx=file; esac
echo "Extracting names from the following $xxx for later perusal:" >&4
echo " "
$sed 's/^/ /' libnames >&4
echo " "
$echo $n "This may take a while...$c" >&4

?X:
?X: Linux may need the special Dynamic option to nm for shared libraries.
?X: In general, this is stored in the nm_so_opt variable.
?X: Unfortunately, that option may be fatal on non-shared libraries.
?X:
for file in $*; do
  case $file in
    *$so*) $nm $nm_so_opt $nm_opt $file 2>/dev/null;;
    *) $nm $nm_opt $file 2>/dev/null;;
  esac
done >libc.tmp

$echo $n ".$c"
?X:
?X: To accelerate processing, we look at the correct 'sed' command
?X: by using a small subset of libc.tmp, i.e. fprintf function.
?X: When we know which sed command to use, do the name extraction
?X:
$grep fprintf libc.tmp > libc.ptf
?X:
?X: In order to enhance readability and save some space, we define
?X: some variables that will be "eval"ed.
?X:
xscan='eval "<libc.ptf $com >libc.list"; $echo $n ".$c" >&4'
xrun='eval
```

```

"<libc.tmp $com >libc.list"; echo "done." >&4'
?X: BSD-like output, I and W types added for Linux
?X: Some versions of Linux include a leading __IO in the symbol name.
?X: HPUX10 reportedly has trailing spaces, though I'm surprised it has
?X: BSD-like output. (AD).
xxx=[ADTSIW]
if com="$sed -n -e 's/___IO//' -e 's/^. * $xxx *[_.]*/p' -e 's/^. * $xxx */p'";\
eval $xscan;\
$contains '^fprintf$' libc.list >/dev/null 2>&1; then
eval $xrun
?X: SYSV-like output
elif com="$sed -n -e 's/^__ */' -e 's/^\([a-zA-Z_0-9$]*\).*xtern.*\1/p'";\
eval $xscan;\
$contains '^fprintf$' libc.list >/dev/null 2>&1; then
eval $xrun
elif com="$sed -n -e '/|UNDEF/d' -e '/FUNC..GL/s/^. *|__ */p'";\
eval $xscan;\
$contains '^fprintf$' libc.list >/dev/null 2>&1; then
eval $xrun
elif com="$sed -n -e 's/^. * D __ */p' -e 's/^. * D //p'";\
eval $xscan;\
$contains '^fprintf$' libc.list >/dev/null 2>&1; then
eval $xrun
elif com="$sed -n -e 's/^_/ ' -e 's/^\([a-zA-Z_0-9$]*\).*xtern.*text.*\1/p'";\
eval
$xscan;\
$contains '^fprintf$' libc.list >/dev/null 2>&1; then
eval $xrun
elif com="$sed -n -e 's/^. *|FUNC |GLOB . */p'";\
eval $xscan;\
$contains '^fprintf$' libc.list >/dev/null 2>&1; then
eval $xrun
elif com="$grep '|' | $sed -n -e '/|COMMON/d' -e '/|DATA/d' \
-e '/file/d' -e 's/^\([ ^ ]*\).*\1/p'";\
eval $xscan;\
$contains '^fprintf$' libc.list >/dev/null 2>&1; then
eval $xrun
elif com="$sed -n -e 's/^. *|FUNC |GLOB . */p' -e 's/^. *|FUNC |WEAK . */p'";\
eval $xscan;\
$contains '^fprintf$' libc.list >/dev/null 2>&1; then
eval $xrun
?X: mips nm output (sysV)
elif com="$sed -n -e 's/^__/' -e '/|Undef/d' -e '/|Proc/s/ . */p'";\
eval $xscan;\
$contains '^fprintf$' libc.list >/dev/null 2>&1; then
eval $xrun
elif com="$sed -n -e 's/^. *|Proc . *|Text *| */p'";\
eval $xscan;\

```

```

$contains '^fprintf$' libc.list >/dev/null 2>&1; then
    eval $xrun
elif com="$sed -n -e '/Def. Text/s/.*/ \([^\ ]*\)\$/1/p''";\
eval $xscan;\
$contains '^fprintf$' libc.list >/dev/null
2>&1; then
    eval $xrun
?X: OS/2 nm output
elif com="$sed -n -e 's/^-0-9a-f ]*_\(.*)=.*\1/p''";\
eval $xscan;\
$contains '^fprintf$' libc.list >/dev/null 2>&1; then
    eval $xrun
elif com="$sed -n -e 's/.*\.text n\ \ \ \./p''";\
eval $xscan;\
$contains '^fprintf$' libc.list >/dev/null 2>&1; then
    eval $xrun
?X: AIX nm output
elif com="sed -n -e 's/^\_.*//' -e 's/[ \ ]*D[ \ ]*[0-9]*.*//p''";\
eval $xscan;\
$contains '^fprintf$' libc.list >/dev/null 2>&1; then
    eval $xrun
else
$nm -p $* 2>/dev/null >libc.tmp
$grep fprintf libc.tmp > libc.ptf
if com="$sed -n -e 's/^\. [ADTSIW] *_[_.]*/p' -e 's/^\. [ADTSIW] //p''";\
eval $xscan; $contains '^fprintf$' libc.list >/dev/null 2>&1
then
    nm_opt='-p'
    eval $xrun
else
    echo " "
    echo "$nm didn't seem to work right. Trying $ar instead..." >&4
    com="
if $ar t $libc > libc.tmp && \
    $contains '^fprintf$' libc.tmp >/dev/null 2>&1
then
    for thisname in $libnames $libc; do
        $ar t $thisname >>libc.tmp
    done
    $sed
-e "s/\\$_o\$//" < libc.tmp > libc.list
    echo "Ok." >&4
    elif test "X$osname" = "Xos2" && $ar tv $libc > libc.tmp; then
?X: Repeat libc to extract forwarders to DLL entries too
    for thisname in $libnames $libc; do
        $ar tv $thisname >>libc.tmp
?X: Revision 50 of EMX has bug in ar: it will not extract forwarders
?X: to DLL entries. Use emximp which will extract exactly them.

```

```

emximp -o tmp.imp $thisname \
  2>/dev/null && \
  $sed -e 's/^(\[_a-zA-Z0-9]*\) .*$/1/p' \
  < tmp.imp >>libc.tmp
$rm -f tmp.imp
done
$sed -e "s/\$_o$//" -e 's/^ \+//' < libc.tmp > libc.list
echo "Ok." >&4
else
echo "$ar didn't seem to work right." >&4
echo "Maybe this is a Cray...trying bld instead..." >&4
if
  bld t $libc | \
  $sed -e 's/.*\+//' -e "s/\$_o:.*$//" > libc.list &&
  $test -s libc.list
then
  for thisname in $libnames; do
    bld t $libnames | \
    $sed -e 's/.*\+//' -e "s/\$_o:.*$//" >>libc.list
    $ar t $thisname >>libc.tmp
  done
  echo
  "Ok." >&4
else
  echo "That didn't work either." >&4
  echo "No problem, I'll be compiling test programs then..." >&4
  runnm=false
fi
fi
fi
fi
nm_extract="$com"
if $test -f /lib/syscalls.exp; then
  echo " "
  echo "Also extracting names from /lib/syscalls.exp for good ole AIX..." >&4
  $sed -n 's/^\([^\ ]*\)[ \]*syscall[0-9]*[ \]*$/1/p' \
  /lib/syscalls.exp >>libc.list
fi
?X: remember, indentation is wrong on purpose--RAM
;;
esac
$rm -f libnames libpath

```

Found in path(s):

```

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/libc.U

```

No license file was found, but licenses were detected in source scan.

```

?RCS: $Id: cf_name.U 1 2006-08-24 12:32:52Z rmanfredi $
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: Original Author: Graham Stoney <greyham@research.canon.oz.au>
?RCS:
?RCS: $Log: cf_name.U,v $
?RCS: Revision 3.0.1.2 1994/05/06 14:29:36 ram
?RCS: patch23: fixed user name computation from /etc/passwd in bsd systems
?RCS:
?RCS: Revision 3.0.1.1 1994/01/24 14:05:11 ram
?RCS: patch16: created
?RCS:
?RCS:
?MAKE:+cf_name: cf_by passcat Filexp nametype cat test
?MAKE: -pick add $@ %<
?S:cf_name:
?S: Full name of the person who ran the Configure script and
answered the
?S: questions. This can be used by units that require the user's full name.
?S: This variable is for internal use only.
?S:.
?T:xxx fn NAME
: figure out their full name
case "$NAME" in
") case "$nametype" in
other)
fn=`./filexp ~/.fullname`
xxx=usg
$test -f $fn && xxx=other
;;
*)
xxx="$nametype"
;;
esac

case "$xxx" in
bsd)
cf_name=`$passcat | grep "^$cf_by:" | \
sed -e 's/^[^:]*:[^:]*:[^:]*:[^:]*\([^:]*\):.*\1/' \
-e 's/,.*//'^
;;

```

```

usg)
cf_name=`$passcat | grep "^$cf_by:" | \
sed -e 's/^[^:]*:[^:]*:[^:]*:[^:]*\([^:]*\):.*\1/' \
-e 's/[^-]*-\([^.*\)(.*)\1/'
;;
*)
cf_name=`$cat $fn`
;;
esac
;;
*)
cf_name="$NAME"
;;
esac
?X:
?X: In the original unit, Graham asked for the user name, in case the above
?X: code was unable to figure it out correctly. Since now cf_name has been
?X: made an internal variable only (i.e. it is not saved in config.sh), letting
?X: the user override the computed default each time would be a pain.
?X:
Therefore, I have decided to trust the above code to get it right, and for
?X: those rare cases where it will fail, too bad :-)--RAM.
?X:
echo " "
echo "Pleased to meet you, $cf_name."

```

Found in path(s):

```

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/cf_name.U

```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 2000 Jarkko Hietaniemi

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?MAKE:d_unorderedl: Inlibc

?MAKE: -pick add \$@ %<

?S:d_unorderedl:

?S: This variable conditionally defines the HAS_UNORDEREDL symbol, which

?S: indicates to the C program that the unorderedl() routine is available.

?S:.

?C:HAS_UNORDEREDL:

?C: This symbol, if defined, indicates that the unorderedl routine is

?C: available to check whether two long doubles are unorderedl

?C: (effectively: whether either of them is NaN)

```
?C:.
?H:#$d_unorderedl HAS_UNORDEREDL /**/
?H:.
?LINT:set d_unorderedl
: see if unorderedl exists
set unorderedl d_unorderedl
eval $inlibc
```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/perl/d_unorderedl.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: d_msem_lck.U 1 2006-08-24 12:32:52Z rmanfredi $
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: $Log: d_msem_lck.U,v $
?MAKE:d_msem_lck: Inlibc
?MAKE: -pick add $@ %<
?S:d_msem_lck:
?S: This variable conditionally defines HAS_MSEM_LOCK if msem_lock() is
?S: available, thereby indicating kernel support for memory semaphores.
?S:.
?C:HAS_MSEM_LOCK:
?C: This symbol, if defined, indicates that memory semaphores are
?C: available to protect mmap()'ed regions.
?C:.
?H:#$d_msem_lck HAS_MSEM_LOCK /**/
?H:.
?LINT:set d_msem_lck
: see if msem_lock exists
set
  msem_lock d_msem_lck
eval $inlibc
```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/d_msem_lck.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id$
```

```

?RCS:
?RCS: Copyright (c) 2001 Jarkko Hietaniemi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 3.0.
?RCS:
?MAKE:d_syscallproto: Hasproto i_unistd
?MAKE: -pick add $@ %<
?S:d_syscallproto:
?S: This variable conditionally defines the HAS_SYSCALL_PROTO symbol,
?S: which indicates to the C program that the system provides
?S: a prototype for the syscall() function. Otherwise, it is
?S: up to the program to supply one.
?S:.
?C:HAS_SYSCALL_PROTO:
?C: This symbol, if defined, indicates that the system provides
?C: a prototype for the syscall() function. Otherwise, it is up
?C: to the program to supply one. Good guesses are
?C: extern
?C: int syscall(int, ...);
?C: extern int syscall(long, ...);
?C:.
?H:#$d_syscallproto HAS_SYSCALL_PROTO /**/
?H:.
?LINT:set d_syscallproto
: see if prototype for syscall is available
echo " "
set d_syscallproto syscall $i_unistd unistd.h
eval $hasproto

```

Found in path(s):

```

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/perl/d_syscallproto.U

```

No license file was found, but licenses were detected in source scan.

```

?RCS: $Id: d_setgrp.U,v 3.0.1.3 1997/02/28 15:44:16 ram Exp $
?RCS:
?RCS: Copyright (c) 1991-1993, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 3.0.
?RCS:

```

?RCS: \$Log: d_setpgrp.U,v \$

?RCS: Revision 3.0.1.3 1997/02/28 15:44:16 ram

?RCS: patch61: obsoleted USE_BSDGRP in favor of USE_BSD_SETPGRP

?RCS: patch61: another unit now also defines a USE_BSD_GETPGRP

?RCS: patch61: fallback for test program failure improved

?RCS:

?RCS: Revision 3.0.1.2 1995/07/25 13:59:30 ram

?RCS: patch56: re-arranged compile line to include ldflags before objects

?RCS:

?RCS: Revision 3.0.1.1 1994/10/29 16:15:37 ram

?RCS: patch36: added

'ldflags' to the test compile line (ADO)

?RCS: patch36: call ./usg explicitly instead of relying on PATH

?RCS:

?RCS: Revision 3.0 1993/08/18 12:07:09 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?MAKE:d_setpgrp d_bsdsetpgrp: cat rm_try +cc +libs +ccflags \
+ldflags Inlibc Guess Setvar i_unistd i_stdlib run

?MAKE: -pick add \$@ %<

?S:d_setpgrp:

?S: This variable conditionally defines HAS_SETPGRP if setpgrp() is

?S: available to set the current process group.

?S:.

?S:d_bsdsetpgrp (d_bsdgrp):

?S: This variable conditionally defines USE_BSD_SETPGRP if

?S: setpgrp needs two arguments whereas USG one needs none.

?S: See also d_setpgid for a POSIX interface.

?S:.

?C:HAS_SETPGRP (SETPGRP):

?C: This symbol, if defined, indicates that the setpgrp routine is

?C: available to set the current process group.

?C:.

?C:USE_BSD_SETPGRP (USE_BSDPGRP BSDPGRP):

?C: This symbol, if defined, indicates that setpgrp needs two

?C: arguments whereas USG one needs none. See also HAS_SETPGID

?C: for

a POSIX interface.

?C:.

?H:#\$d_setpgrp HAS_SETPGRP /**/

?H:#\$d_bsdsetpgrp USE_BSD_SETPGRP /**/

?H:.

?T:xxx

?F:!try

?LINT:set d_setpgrp d_bsdsetpgrp

: see if setpgrp exists

set setpgrp d_setpgrp

eval \$inlibc

```

@if USE_BSD_SETPGRP || d_bsdsetpgrp
case "$d_setpgrp" in
"$define")
echo " "
echo "Checking to see which flavor of setpgrp is in use..."
$cat >try.c <<EOP
#$i_unistd I_UNISTD
#include <sys/types.h>
#ifdef I_UNISTD
# include <unistd.h>
#endif
#$i_stdlib I_STDLIB
#ifdef I_STDLIB
#include <stdlib.h>
#endif
int main()
{
if (getuid() == 0) {
printf("(I see you are running Configure as super-user...)\n");
setuid(1);
}
#ifdef TRY_BSD_PGRP
if (-1 == setpgrp(1, 1))
exit(0);
#else
if (setpgrp() != -1)
exit(0);
#endif
exit(1);
}
EOP
if $cc -o try -DTRY_BSD_PGRP $ccflags $ldflags try.c $libs >/dev/null 2>&1 && $run ./try; then
echo 'You have to use setpgrp(pid,pgrp) instead of setpgrp().' >&4
val="$define"
elif $cc -o try $ccflags $ldflags try.c $libs >/dev/null 2>&1 &&
$run ./try; then
echo 'You have to use setpgrp() instead of setpgrp(pid,pgrp).' >&4
val="$undef"
else
echo "(I can't seem to compile and run the test program.)"
if ./usg; then
xxx="a USG one, i.e. you use setpgrp()."
else
# SVR4 systems can appear rather BSD-ish.
case "$i_unistd" in
$undef)
xxx="a BSD one, i.e. you use setpgrp(pid,pgrp)."

```

```

val="$define"
;;
$define)
xxx="probably a USG one, i.e. you use setpgrp()."
val="$undef"
;;
esac
fi
echo "Assuming your setpgrp is $xxx" >&4
fi
;;
*) val="$undef";;
esac
set d_bsdsetpgrp
eval $setvar
$rm_try
@end

```

Found in path(s):

```

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/modified/d_setpgrp.U

```

No license file was found, but licenses were detected in source scan.

```

?RCS: $Id: i_varhdr.U 1 2006-08-24 12:32:52Z rmanfredi $
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: $Log: i_varhdr.U,v $
?RCS: Revision 3.0.1.3 1997/02/28 15:54:42 ram
?RCS: patch61: varargs script now starts with leading "startsh"
?RCS:
?RCS: Revision 3.0.1.2 1994/10/29 16:21:02 ram
?RCS: patch36: added ?F: line for metalint file checking
?RCS:
?RCS: Revision 3.0.1.1 1994/05/13 15:26:05 ram
?RCS: patch27: this unit now supersedes old i_stdarg.U and i_varargs.U
?RCS: patch27: modified to avoid spurious Whoa warnings (ADO)
?RCS:
?RCS: Revision 3.0
1993/08/18 12:08:49 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:

```

```

?MAKE:i_stdarg i_varargs i_varhdr: cat +cc +ccflags rm test Setvar \
Findhdr startsh _o
?MAKE: -pick add $@ %<
?S:i_stdarg:
?S: This variable conditionally defines the I_STDARG symbol, which
?S: indicates to the C program that <stdarg.h> exists and should
?S: be included.
?S:.
?S:i_varargs:
?S: This variable conditionally defines I_VARARGS, which indicates
?S: to the C program that it should include <varargs.h>.
?S:.
?S:i_varhdr:
?S: Contains the name of the header to be included to get va_dcl definition.
?S: Typically one of varargs.h or stdarg.h.
?S:.
?C:I_STDARG:
?C: This symbol, if defined, indicates that <stdarg.h> exists and should
?C: be included.
?C:.
?C:I_VARARGS:
?C: This symbol, if defined, indicates to the C program that it should
?C: include <varargs.h>.
?C:.
?H:#$i_stdarg I_STDARG /**/
?H:#$i_varargs I_VARARGS /**/
?H:.
?W:%<:va_dcl
?F:!varargs
?T:valstd
?LINT:set i_stdarg i_varargs
?X:
?X:
Don't use setvar because the varargs test below might override these.
?X: Actually, the messages here are just informative. We don't wish to set
?X: i_varargs or i_stdarg to their final value before knowing which of the
?X: two we'll include.
?X:
: see if stdarg is available
echo " "
if $test `./findhdr stdarg.h`; then
echo "<stdarg.h> found." >&4
valstd="$define"
else
echo "<stdarg.h> NOT found." >&4
valstd="$undef"
fi

```

```

: see if varargs is available
echo " "
if $test `./findhdr varargs.h`; then
  echo "<varargs.h> found." >&4
else
  echo "<varargs.h> NOT found, but that's ok (I hope)." >&4
fi

```

?X:

?X: if you have stdarg.h, you need to support prototypes to actually use it;

?X: but if stdarg.h exists and the compiler doesn't support prototypes (for some

?X: bizarre reason), we'll fall back to varargs.h anyway so it's not so bad.

?X:

: set up the varargs testing programs

```
$cat > varargs.c <<EOP
```

```
#ifdef I_STDARG
```

```
#include <stdarg.h>
```

```
#endif
```

```
#ifdef I_VARARGS
```

```
#include <varargs.h>
```

```
#endif
```

```
#ifdef
```

```
  I_STDARG
```

```
int f(char *p, ...)
```

```
#else
```

```
int f(va_alist)
```

```
va_dcl
```

```
#endif
```

```
{
```

```
  va_list ap;
```

```
#ifndef I_STDARG
```

```
  char *p;
```

```
#endif
```

```
#ifdef I_STDARG
```

```
  va_start(ap,p);
```

```
#else
```

```
  va_start(ap);
```

```
  p = va_arg(ap, char *);
```

```
#endif
```

```
  va_end(ap);
```

```
  return 0;
```

```
}
```

```
EOP
```

```
$cat > varargs <<EOP
```

```
$startsh
```

```
if $cc -c $ccflags -D$I1 varargs.c >/dev/null 2>&1; then
```

```
  echo "true"
```

```

else
  echo "false"
fi
$rm -f varargs$_o
EOP
chmod +x varargs

: now check which varargs header should be included
echo " "
i_varhdr="
val="
case "$valstd" in
"$define")
  if `./varargs I_STDARG`; then
    val='stdarg.h'
  elif `./varargs I_VARARGS`; then
    val='varargs.h'
  fi
  ;;
*)
  if `./varargs I_VARARGS`; then
    val='varargs.h'
  fi
  ;;
esac
case "$val" in
")
  echo " "
  echo "**** WHOA THERE!!! ****" >&4
  echo "  Your C compiler \"\$cc\" doesn't seem to support stdarg or varargs!" >&4
  case "$knowitall" in
  ")
    echo "  I'm giving up; maybe you can try again with a different compiler?" >&4
    exit 1
    ;;
  esac
echo "I could not find the definition for va_dcl...
You have problems..." >&4
val="$undef"; set i_stdarg; eval $setvar
val="$undef"; set i_varargs; eval $setvar
;;
*)
set i_varhdr
eval $setvar
case "$i_varhdr" in
stdarg.h)
  val="$define"; set i_stdarg; eval $setvar
  val="$undef"; set i_varargs; eval $setvar

```

```

;;
varargs.h)
val="$undef"; set i_stdarg; eval $setvar
val="$define"; set i_varargs; eval $setvar
;;
esac
echo "We'll include <${i_varhdr}> to get va_dcl definition." >&4;;
esac
$rm -f varargs*

```

Found in path(s):

```

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/modified/i_varhdr.U

```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: usrinc.U,v \$

?RCS: Revision 3.0.1.3 1997/02/28 16:27:12 ram

?RCS: patch61: don't ask for the include path unless they are on a MIPS

?RCS:

?RCS: Revision 3.0.1.2 1995/05/12 12:24:36 ram

?RCS: patch54: ensure that ./mips always exists (ADO)

?RCS:

?RCS: Revision 3.0.1.1 1994/05/06 15:18:31 ram

?RCS: patch23: ensure usrinc value is preserved across sessions (WED)

?RCS:

?RCS: Revision 3.0 1993/08/18 12:09:58 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?MAKE:usrinc incpath mips_type:

test cat echo n c Getfile Guess \

Oldconfig eunicefix contains rm

?MAKE: -pick add \$@ %<

?S:usrinc:

?S: This variable holds the path of the include files, which is

?S: usually /usr/include. It is mainly used by other Configure units.

?S:.

?S:incpath:

?S: This variable must precede the normal include path to get hte

```

?S: right one, as in "$incpath/usr/include" or "$incpath/usr/lib".
?S: Value can be "" or "/bsd43" on mips.
?S:.
?S:mips_type:
?S: This variable holds the environment type for the mips system.
?S: Possible values are "BSD 4.3" and "System V".
?S:.
?D:usrinc='/usr/include'
?LINT:create mips
?T:xxx_prompt
?F:./mips
: What should the include directory be ?
echo " "
$echo $n "Hmm... $c"
dflt='/usr/include'
incpath=""
?X: mips_type is used later, to add -DSYSTYPE_BSD43 to cppflags if needed.
mips_type=""
?X:
?X: Cannot put the following in Guess, or we get a circular dependency.
?X:
if $test -f /bin/mips && /bin/mips; then
echo "Looks like a MIPS system..."
$cat >usr.c
<<'EOCP'
#ifdef SYSTYPE_BSD43
/bsd43
#endif
EOCP
if cc -E usr.c > usr.out && $contains / usr.out >/dev/null 2>&1; then
dflt='/bsd43/usr/include'
incpath='/bsd43'
mips_type='BSD 4.3'
else
mips_type='System V'
fi
$rm -f usr.c usr.out
echo "and you're compiling with the $mips_type compiler and libraries."
xxx_prompt=y
echo "exit 0" >mips
else
echo "Doesn't look like a MIPS system."
xxx_prompt=n
echo "exit 1" >mips
fi
chmod +x mips
$unicefix mips
case "$usrinc" in

```

```

") ;;
*) dflt="$usrinc";;
esac
case "$xxx_prompt" in
y) fn=d/
echo " "
rp='Where are the include files you want to use?'
./getfile
usrinc="$ans"
;;
*) usrinc="$dflt"
;;
esac

```

Found in path(s):

```

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/usrinc.U

```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1996, Andy Dougherty

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: sitearch.U,v \$

?RCS: Revision 3.0.1.1 1997/02/28 16:21:30 ram

?RCS: patch61: created

?RCS:

?MAKE:sitearch sitearchexp installsitearch: afs cat Getfile \

Oldconfig Prefixit prefix test archname sitelib

?MAKE: -pick add \$@ %<

?Y:TOP

?S:sitearch:

?S: This variable contains the eventual value of the SITEARCH symbol,

?S: which is the name of the private library for this package. It may

?S: have a ~ on the front. It is up to the makefile to eventually create

?S: this

directory while performing installation (with ~ substitution).

?S:.

?S:sitearchexp:

?S: This variable is the ~name expanded version of sitearch, so that you

?S: may use it directly in Makefiles or shell scripts.

?S:.

?S:installsitearch:

?S: This variable is really the same as sitearchexp but may differ on

?S: those systems using AFS. For extra portability, only this variable

?S: should be used in makefiles.

?S:.

?C:SITEARCH:

?C: This symbol contains the name of the private library for this package.

?C: The library is private in the sense that it needn't be in anyone's

?C: execution path, but it should be accessible by the world. The program

?C: should be prepared to do ~ expansion.

?C: The standard distribution will put nothing in this directory.

?C: Individual sites may place their own extensions and modules in

?C: this directory.

?C:.

?C:SITEARCH_EXP:

?C: This symbol contains the ~name expanded version of SITEARCH, to be used

?C: in programs that are not prepared to deal

with ~ expansion at run-time.

?C:.

```
?H:#define SITEARCH "$sitearch" /**/
```

```
?H:#define SITEARCH_EXP "$sitearchexp" /**/
```

?H:.

?T:xxx

: determine where site specific architecture-dependent libraries go.

```
xxx=`echo $sitelib/$sarchname | sed 's!^$prefix!!'`
```

: xxx is usually lib/site_perl/archname.

```
set sitearch sitearch none
```

```
eval $prefixit
```

```
case "$sitearch" in
```

```
) dflt="$sitelib/$sarchname" ;;
```

```
*) dflt="$sitearch" ;;
```

```
esac
```

```
$cat <<EOM
```

The installation process will also create a directory for architecture-dependent site-specific extensions and modules.

EOM

```
fn=nd~+
```

```
rp='Pathname for the site-specific architecture-dependent library files?'
```

```
./getfile
```

```
if $test "X$sitearchexp" != "X$sansexp"; then
```

```
installsitearch="
```

```
fi
```

```
sitearch="$ans"
```

```
sitearchexp="$sansexp"
```

```
if $afs; then
```

\$cat <<EOM

Since you are running AFS, I need to distinguish the directory in which private files reside from the directory in which they are installed (and from which they are presumably copied to the former directory by occult means).

EOM

```
case
"$installsitearch" in
*) dflt=`echo $sitearchexp | sed 's#^/afs/#/afs/.#`;;
*) dflt="$installsitearch";;
esac
fn=de~
rp='Where will private files be installed?'
./getfile
installsitearch="$ans"
else
installsitearch="$sitearchexp"
fi
```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/sitearch.U
```

No license file was found, but licenses were detected in source scan.

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?MAKE:d_hypot: Inlibc

?MAKE: -pick add \$@ %<

?S:d_hypot:

?S: This variable conditionally defines HAS_HYPOT if hypot is available

?S: for numerically stable hypotenuse function.

?S:.

?C:HAS_HYPOT:

?C: This symbol, if defined, indicates that the hypot routine is

?C: available to do the hypotenuse function.

?C:.

?H:#\$d_hypot HAS_HYPOT /**/

?H:.

?LINT:set d_hypot

: see if hypot exists

set hypot d_hypot

eval \$inlibc

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_hypot.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id$
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: Original Author: Andy Dougherty <doughera@lafcol.lafayette.edu>
?RCS:
?RCS: $Log: sizetype.U,v $
?RCS: Revision 3.0.1.1 1994/08/29 16:32:10 ram
?RCS: patch32: created by ADO
?RCS:
?MAKE:sizetype: Myread Typedef
?MAKE: -pick add $@ %<
?S:sizetype:
?S: This variable defines sizetype to be something like size_t,
?S: unsigned long, or whatever type is used to declare length
?S: parameters for string functions.
?S:.
?C:Size_t:
?C: This symbol holds the type used to declare length parameters
?C: for string
?C: functions. It is usually size_t, but may be
?C: unsigned long, int, etc. It may be necessary to include
?C: <sys/types.h> to get any typedef'ed information.
?C:.
?H:#define Size_t $sizetype /* length paramater for string functions */
?H:.
: see what type is used for size_t
set size_t sizetype 'unsigned int' stdio.h sys/types.h
eval $typedef
dflt="$sizetype"
echo " "
rp="What type is used for the length parameter for string functions?"
./myread
sizetype="$ans"
```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/sizetype.U
```

No license file was found, but licenses were detected in source scan.

```

?RCS: $Id: d_cuserid.U 1 2006-08-24 12:32:52Z rmanfredi $
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: Original Author: Andy Dougherty <doughera@lafcol.lafayette.edu>
?RCS:
?RCS: $Log: d_cuserid.U,v $
?RCS: Revision 3.0.1.1 1994/08/29 16:07:25 ram
?RCS: patch32: created by ADO
?RCS:
?MAKE:d_cuserid: Inlibc
?MAKE: -pick add $@ %<
?S:d_cuserid:
?S: This variable conditionally defines the HAS_CUSERID symbol, which
?S: indicates to the C program that the cuserid() routine is available
?S: to get character login names.
?S:.
?C:HAS_CUSERID :
?C: This symbol,
if defined, indicates that the cuserid routine is
?C: available to get character login names.
?C:.
?H:#$d_cuserid HAS_CUSERID /**/
?H:.
?LINT:set d_cuserid
: see if cuserid exists
set cuserid d_cuserid
eval $inlibc

```

Found in path(s):

```

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/d_cuserid.U

```

No license file was found, but licenses were detected in source scan.

```

?RCS: $Id: d_mknod.U,v 3.0.1.1 1994/10/29 16:14:17 ram Exp $
?RCS:
?RCS: Copyright (c) 1998 Andy Dougherty
?RCS:
?RCS: You may distribute under the terms of either the GNU General Public
?RCS: License or the Artistic License, as specified in the README file.
?RCS:
?RCS: Original Author: Andy Dougherty <doughera@lafayette.edu>

```

?RCS:
?RCS: \$Log: d_mknod.U,v \$
?RCS:
?MAKE:d_mknod: Inlibc
?MAKE: -pick add \$@ %<
?S:d_mknod:
?S: This variable conditionally defines the HAS_MKNOD symbol, which
?S: indicates to the C program that the mknod() routine is available.
?S:.
?C:HAS_MKNOD :
?C: This symbol, if defined, indicates that the mknod routine is
?C: available. If you just want to create FIFOs, you should try
?C: to use mkfifo instead. mknod might require super-user privileges.
?C:.
?H:#\$d_mknod HAS_MKNOD /**/
?H:.
?LINT:set d_mknod
: see if mknod exists
set mknod d_mknod
eval \$inlibc

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/modified/d_mknod.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_sighold.U 1 2006-08-24 12:32:52Z rmanfredi \$
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: \$Log: d_sighold.U,v \$
?RCS: Revision 3.0 1993/08/18 12:07:21 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:d_sighold: Inlibc
?MAKE: -pick add \$@ %<
?S:d_sighold:
?S: This variable conditionally defines HAS_SIGHOLD if sighold() is
?S: available to hold signals.
?S:.
?C:HAS_SIGHOLD:
?C: This symbol, if defined, indicates that the sighold routine is

```
?C: available to hold signals.
?C:.
?H:#$d_sighold HAS_SIGHOLD /**/
?H:.
?LINT:set d_sighold
:
  see if sighold exists
set sighold d_sighold
eval $inlibc
```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/d_sighold.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: d_SHM_MAC.U 1 2006-08-24 12:32:52Z rmanfredi $
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: $Log: d_SHM_MAC.U,v $
?RCS: Revision 3.0 1993/08/18 12:05:41 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:d_SHM_MAC d_SHM_PRM d_SHM_SEG d_SHM_IMMU: cat d_shm test rm +cc +ccflags
?MAKE: -pick add $@ %<
?S:d_SHM_MAC:
?S: Sometimes, the SHMLBA manifest needs sys/sysmacros.h, usually for
?S: the ctob() macro.
?S:.
?S:d_SHM_PRM:
?S: Sometimes, the SHMLBA manifest needs sys/param.h, usually for the
?S: NBPC constant.
?S:.
?S:d_SHM_SEG:
?S: Sometimes,
  the SHMLBA manifest needs sys/seg.h, usually for the
?S: SNUMSHFT constant.
?S:.
?S:d_SHM_IMMU:
?S: Sometimes, the SHMLBA manifest needs sys/immu.h, usually for the
?S: stob() macro.
?S:.
```

?C:SHMLBA_WANTS_SYSMACROS:

?C: This value tells us to include <sys/sysmacros.h> because SHMLBA

?C: needs something from there, probably the ctob() macro.

?C:.

?C:SHMLBA_WANTS_PARAM:

?C: This value tells us to include <sys/param.h> because SHMLBA needs

?C: something from there, probably the NBPC constant.

?C:.

?C:SHMLBA_WANTS_SEG:

?C: This value tells us to include <sys/seg.h> because SHMLBA needs

?C: something from there, probably the SNUMSHFT constant.

?C:.

?C:SHMLBA_WANTS_IMMU:

?C: This value tells us to include <sys/immu.h> because SHMLBA needs

?C: something from there, probably the stob() macro. (tower_600 only?)

?C:.

?H:#\$d_SHM_MAC SHMLBA_WANTS_SYSMACROS /* SHMLBA wants ctob()? */

?H:#\$d_SHM_PRM SHMLBA_WANTS_PARAM /* SHMLBA wants NBPC? */

?H:#\$d_SHM_SEG SHMLBA_WANTS_SEG /* SHMLBA wants

SNUMSHFT? */

?H:#\$d_SHM_IMMU SHMLBA_WANTS_IMMU /* SHMLBA wants stob()? */

?H:.

?T:flags D_sys_immu D_sys_seg D_sys_sysmacros D_sys_param

: check for SHMLBA braindamage

d_SHM_MAC="\$undef"

d_SHM_PRM="\$undef"

d_SHM_SEG="\$undef"

d_SHM_IMMU="\$undef"

if \$test "\$d_shm" = "\$define" ; then

echo " "

\$cat >&4 <<EOM

Checking to see if SHMLBA needs additional headers.

The headers I'll be checking are:

sys/macros.h (for the ctob() macro)

sys/param.h (for NBPC)

sys/seg.h (for SNUMSHFT)

sys/immu.h (for the stob() macro)

EOM

\$cat >shm_mac.c <<'EOCP'

#include <sys/types.h>

#include <sys/ipc.h>

#include <sys/shm.h>

#ifdef I_SYS_IMMU

#include <sys/immu.h>

#endif

#ifdef I_SYS_SYSMACROS

```

#include <sys/sysmacros.h>
#endif
#ifdef I_SYS_PARAM
#include <sys/param.h>
#endif
#ifdef I_SYS_SEG
#include <sys/seg.h>
#endif

int main() {
int foo = SHMLBA ;
}
EOCP
flags='xxx'
for D_sys_immu in "'-DI_SYS_IMMU'; do
for D_sys_seg in "'-DI_SYS_SEG'; do
for D_sys_sysmacros in "'-DI_SYS_SYSMACROS';
do
for D_sys_param in "'-DI_SYS_PARAM'; do
case "$flags" in
'xxx')
case "$D_sys_immu$D_sys_param$D_sys_sysmacros$D_sys_seg" in
")
echo "Trying it normally..."
;;
*)
echo "Trying $D_sys_immu $D_sys_param $D_sys_sysmacros $D_sys_seg"
;;
esac
if $cc $ccflags \
$D_sys_immu $D_sys_param $D_sys_sysmacros $D_sys_seg \
-o shm_mac shm_mac.c >/dev/null 2>&1 ; then
set X $D_sys_immu $D_sys_param $D_sys_sysmacros $D_sys_seg
shift
flags="$*"
echo "Succeeded with $flags"
fi
;;
esac
done
done
done
done
done
case "$flags" in
xxx)
echo "I don't know how to keep SHMLBA happy. Good luck!"
;;
esac

```

```

case "$flags" in
*I_SYS_PARAM*) d_SHM_PRM="$define";;
esac
case "$flags" in
*I_SYS_SYSMACROS*) d_SHM_MAC="$define";;
esac
case "$flags" in
*I_SYS_SEG*) d_SHM_SEG="$define";;
esac
case "$flags" in
*I_SYS_IMMU*) d_SHM_IMMU="$define";;
esac
fi
$rm -f shm_mac*

```

Found in path(s):

```

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/d_SHM_MAC.U

```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_getgrent.U,v \$

?RCS:

?RCS: Copyright (c) 1998 Andy Dougherty

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?RCS: \$Log: d_getgrent.U,v \$

?RCS:

?MAKE:d_getgrent: Inlibc

?MAKE: -pick add \$@ %<

?S:d_getgrent:

?S: This variable conditionally defines the HAS_GETGRENТ symbol, which

?S: indicates to the C program that the getgrent() routine is available

?S: for sequential access of the group database.

?S:.

?C:HAS_GETGRENТ:

?C: This symbol, if defined, indicates that the getgrent routine is

?C: available for sequential access of the group database.

?C:.

?H:#\$d_getgrent HAS_GETGRENТ /**/

?H:.

?LINT:set d_getgrent

: see if getgrent exists

set getgrent d_getgrent

eval \$inlibc

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/modified/d_getgrent.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: Loc_sed.U 1 2006-08-24 12:32:52Z rmanfredi \$

?RCS:

?RCS: Copyright (c) 1996, Andy Dougherty

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic Licence,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic Licence; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?X: This is used in perl.c.

?MAKE:full_sed: sed

?MAKE: -pick add \$@ %<

?S:full_sed:

?S: This variable contains the full pathname to 'sed', whether or

?S: not the user has specified 'portability'. This is only used

?S: in the compiled C program, and we assume that all systems which

?S: can share this executable will have the same full pathname to

?S: 'sed.'

?S:.

?X: Yes, I know about the C symbol PORTABLE, but I think sed

?X: is

unlikely to move, and I'm too lazy to add all the

?X: #ifdef PORTABLE sections to the perl source.

?X:

?C:LOC_SED:

?C: This symbol holds the complete pathname to the sed program.

?C:.

?H:#define LOC_SED "\$full_sed" /**/

?H:.

: Store the full pathname to the sed program for use in the C program

full_sed=\$sed

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/Loc_sed.U

No license file was found, but licenses were detected in source scan.

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?MAKE:d_fma: Inlibc

?MAKE: -pick add \$@ %<

?S:d_fma:
?S: This variable conditionally defines the HAS_FMA symbol, which
?S: indicates to the C program that the fma() routine is available.
?S:.
?C:HAS_FMA:
?C: This symbol, if defined, indicates that the fma routine is
?C: available to do the multiply-add function.
?C:.
?H:#\$d_fma HAS_FMA /**/
?H:.
?LINT:set d_fma
: see if fma exists
set fma d_fma
eval \$inlibc

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_fma.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: so.U 1 2006-08-24 12:32:52Z rmanfredi \$
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: \$Log: so.U,v \$
?RCS: Revision 3.0.1.2 1994/10/29 16:30:04 ram
?RCS: patch36: now tells user how he can suppress shared lib lookup (ADO)
?RCS: patch36: removed echo at the top, since it's now in the here-doc (ADO)
?RCS:
?RCS: Revision 3.0.1.1 1994/06/20 07:07:02 ram
?RCS: patch30: created
?RCS:
?X:
?X: This unit computes the shared-object / shared-lib extension
?X:
?MAKE:so d_libname_unique: test libpth Loc Myread Oldconfig cat Setvar
?MAKE:-pick add \$@ %<
?S:so:
?S: This
variable holds the extension used to identify shared libraries
?S: (also known as shared objects) on the system. Usually set to 'so'.
?S:.

```

?S:d_libname_unique:
?S: This variable is defined if the target system insists on unique
?S: basenames for shared library files. This is currently true on Android,
?S: false everywhere else we know of.
?S: Defaults to 'undef'.
?S:.
?LINT:set d_libname_unique
?T: xxx
: compute shared library extension
case "$so" in
")
if xxx=`./loc libc.sl X $libpth`; $test -f "$xxx"; then
  dflt='sl'
else
  dflt='so'
fi
;;
*) dflt="$so";;
esac
$cat <<EOM

```

On some systems, shared libraries may be available. Answer 'none' if you want to suppress searching of shared libraries for the remainder of this configuration.

```

EOM
rp='What is the file extension used for shared libraries?'
./myread
so="$ans"

```

```

: Does target system insist that shared library basenames are unique
$cat << EOM

```

Some dynamic loaders assume that the *basename* of shared library filenames are globally unique. We'll default this to undef as we assume your system is not this weird. Set to defined if you're on one of them.

```

EOM

dflt='n'
rp='Make shared library basenames unique?'
./myread
case "$ans" in
y|Y) val="$define" ;;
*) val="$undef" ;;
esac
set d_libname_unique

```

eval \$setvar

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/modified/so.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 2000 Jarkko Hietaniemi

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?MAKE:d_iconv: Inlibc

?MAKE: -pick add \$@ %<

?S:d_iconv:

?S: This variable conditionally defines the HAS_ICONV symbol, which

?S: indicates to the C program that the iconv() routine is available.

?S:.

?C:HAS_ICONV:

?C: This symbol, if defined, indicates that the iconv routine is

?C: available to do character set conversions.

?C:.

?H:#\$d_iconv HAS_ICONV /**/

?H:.

?LINT:set d_iconv

: see if iconv exists

set iconv d_iconv

eval \$inlibc

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_iconv.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_endprotoent_r.U,v 0RCS:

?RCS: Copyright (c) 2002,2003 Jarkko Hietaniemi

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?RCS: Generated by the reentr.pl from the Perl 5.8 distribution.

?RCS:

?MAKE:d_endprotoent_r endprotoent_r_proto: Inlibc Protochk Hasproto \
i_systypes usethreads i_netdb extern_C

?MAKE: -pick add \$@ %<

?S:d_endprotoent_r:

?S: This variable conditionally defines the HAS_ENDPROTOENT_R symbol,
 ?S: which indicates to the C program that the endprotoent_r()
 ?S: routine is available.
 ?S:.
 ?S:endprotoent_r_proto:
 ?S: This variable encodes the prototype of endprotoent_r.
 ?S: It is zero if d_endprotoent_r is undef, and one of the
 ?S: REENTRANT_PROTO_T_ABC macros of reentr.h if d_endprotoent_r
 ?S: is defined.
 ?S:.
 ?C:HAS_ENDPROTOENT_R:
 ?C: This symbol, if defined, indicates that the endprotoent_r
 routine
 ?C: is available to endprotoent re-entrantly.
 ?C:.
 ?C:ENDPROTOENT_R_PROTO:
 ?C: This symbol encodes the prototype of endprotoent_r.
 ?C: It is zero if d_endprotoent_r is undef, and one of the
 ?C: REENTRANT_PROTO_T_ABC macros of reentr.h if d_endprotoent_r
 ?C: is defined.
 ?C:.
 ?H:#\$d_endprotoent_r HAS_ENDPROTOENT_R /**/
 ?H:#define ENDPROTOENT_R_PROTO \$endprotoent_r_proto /**/
 ?H:.
 ?T:try hdrs d_endprotoent_r_proto
 : see if endprotoent_r exists
 set endprotoent_r d_endprotoent_r
 eval \$inlibc
 case "\$d_endprotoent_r" in
 "\$define")
 hdrs="\$i_systypes sys/types.h define stdio.h \$i_netdb netdb.h"
 case "\$d_endprotoent_r_proto:\$susetheads" in
 ":define") d_endprotoent_r_proto=define
 set d_endprotoent_r_proto endprotoent_r \$hdrs
 eval \$hasproto ;;
 *) ;;
 esac
 case "\$d_endprotoent_r_proto" in
 define)
 case "\$endprotoent_r_proto" in
 "|0) try='int endprotoent_r(struct protoent_data*);'
 ./protochk "\$extern_C \$try" \$hdrs && endprotoent_r_proto=I_D ;;
 esac
 case "\$endprotoent_r_proto"
 in
 "|0) try='void endprotoent_r(struct protoent_data*);'
 ./protochk "\$extern_C \$try" \$hdrs && endprotoent_r_proto=V_D ;;
 esac

```

case "$endprotoent_r_proto" in
"|0) d_endprotoent_r=undef
    endprotoent_r_proto=0
    echo "Disabling endprotoent_r, cannot determine prototype." >&4 ;;
*) case "$endprotoent_r_proto" in
REENTRANT_PROTO*) ;;
*) endprotoent_r_proto="REENTRANT_PROTO_$endprotoent_r_proto" ;;
esac
echo "Prototype: $try" ;;
esac
;;
*) case "$usethreads" in
define) echo "endprotoent_r has no prototype, not using it." >&4 ;;
esac
d_endprotoent_r=undef
endprotoent_r_proto=0
;;
esac
;;
*) endprotoent_r_proto=0
;;
esac

```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/threads/d_endprotoent_r.U
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: Unix.U,v 3.0.1.1 1997/02/28 15:20:06 ram Exp \$

?RCS:

?RCS: Copyright (c) 1991-1993, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 3.0.

?RCS:

?RCS: \$Log: Unix.U,v \$

?RCS: Revision 3.0.1.1 1997/02/28 15:20:06 ram

?RCS: patch61: created

?RCS:

?X:

?X: The purpose of this unit is to define things that are common across all

?X: known UNIX platforms. If Configure is ported/used on a non-UNIX

?X: environment, then some of the following variables can be redefined in hint

?X: files.

?X:

?MAKE:Unix _exe _a _o exe_ext lib_ext obj_ext path_sep \
firstmakefile archobjs rm_try: Oldconfig rm

?MAKE: -pick add \$@ %<

?S: _exe:

?S: This
variable defines the extension used for executable files.

?S: DJGPP, Cygwin and OS/2 use '.exe'. Stratus VOS uses '.pm'.

?S: On operating systems which do not require a specific extension

?S: for executable files, this variable is empty.

?S:.

?S: _a:

?S: This variable defines the extension used for ordinary library files.

?S: For unix, it is '.a'. The '.' is included. Other possible

?S: values include '.lib'.

?S:.

?S: _o:

?S: This variable defines the extension used for object files.

?S: For unix, it is '.o'. The '.' is included. Other possible

?S: values include '.obj'.

?S:.

?S: firstmakefile:

?S: This variable defines the first file searched by make. On unix,

?S: it is makefile (then Makefile). On case-insensitive systems,

?S: it might be something else. This is only used to deal with

?S: convoluted make depend tricks.

?S:.

?S: archobjs:

?S: This variable defines any additional objects that must be linked

?S: in with the program on this architecture. On unix, it is usually

?S: empty.

It is typically used to include emulations of unix calls

?S: or other facilities. For perl on OS/2, for example, this would

?S: include os2/os2.obj.

?S:.

?X: Metaconfig's Obsolete symbol stuff is too over-eager. In the

?X: perl sources, it picks up things like "P" and "FLOCK" that are

?X: not used in the way Metaconfig thinks they are. Thus I can't

?X: just declare these obsolete and then run metaconfig -o.

?X: Instead, I'll just handle them here.

?X: Sadly, history has conspired to give us a web of definitions;

?X: this could have been much simpler.

?S: lib_ext:

?S: This is an old synonym for _a.

?S:.

?S: exe_ext:

?S: This is an old synonym for _exe.

?S:.

?S: obj_ext:

?S: This is an old synonym for _o.

?S:.

?S:path_sep:

?S: This is an old synonym for p_ in Head.U, the character

?S: used to separate elements in the command shell search PATH.

?S:.

?S:rm_try:

?S: This is a cleanup variable for try test programs.

?S: Internal Configure use only.

?S:.

?LINT: change p_

?INIT::

Trailing extension. Override this in a hint file, if needed.

?INIT:: Extra object files, if any, needed on this platform.

?INIT:archobjs="

: Define several unixisms.

: Hints files or command line option can be used to override them.

: The convoluted testing is in case hints files set either the old

: or the new name.

case "\$_exe" in

) case "\$exe_ext" in

) ;;

*) _exe="\$exe_ext" ;;

esac

;;

esac

case "\$_a" in

) case "\$lib_ext" in

) _a='.a';;

*) _a="\$lib_ext" ;;

esac

;;

esac

case "\$_o" in

) case "\$obj_ext" in

) _o='.o';;

*) _o="\$obj_ext";;

esac

;;

esac

case "\$p_" in

) case "\$path_sep" in

) p_=':':;

*) p_="\$path_sep";;

esac

;;

esac

exe_ext=\$_exe

```
lib_ext=$_a
obj_ext=$_o
path_sep=$p_
```

```
rm_try="$rm -f try try$_exe a.out .out try.[cho] try.$_o core core.try* try.core*"
```

```
@if firstmakefile
: Which makefile gets called first. This is used by make depend.
case "$firstmakefile" in
") firstmakefile='makefile';;
esac

@end
```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/modified/Unix.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: d_regcmp.U 1 2006-08-24 12:32:52Z rmanfredi $
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: $Log: d_regcmp.U,v $
?RCS: Revision 3.0.1.1 1995/01/30 14:34:45 ram
?RCS: patch49: now looks for POSIX regcomp() routine
?RCS:
?RCS: Revision 3.0 1993/08/18 12:06:53 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:d_regcmp d_re_comp d_regcomp: Csym cat
?MAKE: -pick add $@ %<
?S:d_regcomp:
?S: This variable conditionally defines the HAS_REGCOMP symbol, which
?S: indicates to the C program that the regcomp() routine is available
?S: for regular
?S: pattern matching (usually on POSIX.2 conforming systems).
?S:.
?S:d_regcmp:
?S: This variable conditionally defines the HAS_REGCMP symbol, which
?S: indicates to the C program that the regcmp() routine is available
?S: for regular pattern matching (usually on System V).
```

?S:
?S:d_re_comp:
?S: This variable conditionally defines the HAS_RECOMP symbol, which
?S: indicates to the C program that the re_comp() routine is available
?S: for regular pattern matching (usually on BSD). If so, it is likely that
?S: re_exec() exists.
?S:
?C:HAS_REGCOMP (REGCOMP):
?C: This symbol, if defined, indicates that the regcomp() routine is
?C: available to do some regular pattern matching (usually on POSIX.2
?C: conforming systems).
?C:
?C:HAS_REGCMP (REGCMP):
?C: This symbol, if defined, indicates that the regcmp() routine is
?C: available to do some regular pattern matching (usually on System V).
?C:
?C:HAS_RECOMP (RECOMP):
?C: This symbol, if defined, indicates that the re_comp() routine is
?C: available
to do some regular pattern matching (usually on BSD). If so,
?C: it is likely that re_exec() be available.
?C:
?H:#\$d_regcomp HAS_REGCOMP /* POSIX.2 */
?H:#\$d_regcmp HAS_REGCMP /* sysV */
?H:#\$d_re_comp HAS_RECOMP /* BSD */
?H:
?T:val
: see if regcomp, regcmp, or re_comp exist, for regular pattern matching
echo " "
if set regcomp val -f d_regcomp; eval \$csym; \$val; then
echo 'regcomp() found.' >&4
d_regcomp="\$define"
d_regcmp="\$undef"
d_re_comp="\$undef"
elif set regcmp val -f d_regcmp; eval \$csym; \$val; then
echo 'regcmp() found.' >&4
d_regcomp="\$define"
d_regcmp="\$undef"
d_re_comp="\$undef"
elif set re_comp val -f d_re_comp; eval \$csym; \$val; then
echo 're_comp() found, assuming re_exec() also exists.' >&4
d_re_comp="\$define"
d_regcomp="\$undef"
d_regcmp="\$undef"
else
\$cat >&4 <<EOM
No regcomp(), regcmp() nor re_comp() found !! No regular pattern matching.
EOM

```
d_regcmp="$undef"
d_re_comp="$undef"
d_regcomp="$undef"
fi
```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/d_regcmp.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: d_normsig.U 1 2006-08-24 12:32:52Z rmanfredi $
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: $Log: d_normsig.U,v $
?RCS: Revision 3.0.1.2 1997/02/28 15:37:03 ram
?RCS: patch61: replaced .a with $_a all over the place
?RCS:
?RCS: Revision 3.0.1.1 1994/10/29 16:14:48 ram
?RCS: patch36: call ./bsd explicitly instead of relying on PATH
?RCS:
?RCS: Revision 3.0 1993/08/18 12:06:44 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:d_normsig joblib: test Setvar Guess _a
?MAKE: -pick add $@ %<
?S:d_normsig:
?S: This variable conditionally
?S: defines the NORMSIG symbol, which
?S: indicates to the C program that the normal signal handling routines
?S: should be used, as opposed to the ones in 4.1bsd (sigset, etc.).
?S:.
?S:joblib:
?S: This variable holds the argument to be passed to the loader to include
?S: the strange signal handling routines from 4.1bsd. On systems that
?S: have NORMSIG defined this variable is null.
?S:.
?C:NORMSIG:
?C: This symbol, if defined, indicates that normal signal handling routines
?C: should be used, as opposed to the ones in 4.1bsd (sigset, etc.).
?C:.
?H:#$d_normsig NORMSIG /**/
```

```

?H:
?LINT:set d_normsig
: see if we need -ljobs and if we have sigset, etc.
echo " "
if $test -r /usr/lib/libjobs$_a || $test -r /usr/local/lib/libjobs$_a ; then
echo "Jobs library found." >&4
val="$undef"
jobslib='-ljobs'
else
if ./bsd; then
echo "No jobs library found. (I suppose this is at least 4.2...)" >&4
else
echo "No jobs library found. (That's okay, we all have our faults.)" >&4
fi
val="$define"
jobslib=""
fi
set
d_normsig
eval $setvar

```

Found in path(s):

```

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/d_normsig.U

```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_sethostent_r.U,v 0RCS:

?RCS: Copyright (c) 2002,2003 Jarkko Hietaniemi

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?RCS: Generated by the reentr.pl from the Perl 5.8 distribution.

?RCS:

?MAKE:d_sethostent_r sethostent_r_proto: Inlibc Protochk Hasproto i_systypes \
 usethreads i_netdb extern_C

?MAKE: -pick add \$@ %<

?S:d_sethostent_r:

?S: This variable conditionally defines the HAS_SETHOSTENT_R symbol,

?S: which indicates to the C program that the sethostent_r()

?S: routine is available.

?S:.

?S:sethostent_r_proto:

?S: This variable encodes the prototype of sethostent_r.

?S: It is zero if d_sethostent_r is undef, and one of the

?S: REENTRANT_PROTO_T_ABC macros of reentr.h if d_sethostent_r

?S: is defined.

?S:.

```

?C:HAS_SETHOSTENT_R:
?C: This symbol, if defined, indicates that the sethostent_r routine
?C: is
    available to sethostent re-entrantly.
?C:.
?C:SETHOSTENT_R_PROTO:
?C: This symbol encodes the prototype of sethostent_r.
?C: It is zero if d_sethostent_r is undef, and one of the
?C: REENTRANT_PROTO_T_ABC macros of reentr.h if d_sethostent_r
?C: is defined.
?C:.
?H:#$d_sethostent_r HAS_SETHOSTENT_R  /**/
?H:#define SETHOSTENT_R_PROTO $sethostent_r_proto  /**/
?H:.
?T:try hdrs d_sethostent_r_proto
: see if sethostent_r exists
set sethostent_r d_sethostent_r
eval $inlibc
case "$d_sethostent_r" in
"$define")
    hdrs="$i_systypes sys/types.h define stdio.h $i_netdb netdb.h"
    case "$d_sethostent_r_proto:$susethreads" in
":define") d_sethostent_r_proto=define
        set d_sethostent_r_proto sethostent_r $hdrs
        eval $hasproto ;;
*) ;;
esac
case "$d_sethostent_r_proto" in
define)
    case "$sethostent_r_proto" in
"|0) try='int sethostent_r(int, struct hostent_data*);'
./protochk "$extern_C $try" $hdrs && sethostent_r_proto=I_ID ;;
esac
case "$sethostent_r_proto" in
"|0) try='void
sethostent_r(int, struct hostent_data*);'
./protochk "$extern_C $try" $hdrs && sethostent_r_proto=V_ID ;;
esac
case "$sethostent_r_proto" in
"|0) d_sethostent_r=undef
        sethostent_r_proto=0
        echo "Disabling sethostent_r, cannot determine prototype." >&4 ;;
* ) case "$sethostent_r_proto" in
REENTRANT_PROTO*) ;;
*) sethostent_r_proto="REENTRANT_PROTO_$sethostent_r_proto" ;;
esac
echo "Prototype: $try" ;;
esac

```

```

;;
*) case "$susetthreads" in
define) echo "sethostent_r has no prototype, not using it." >&4 ;;
esac
d_sethostent_r=undef
sethostent_r_proto=0
;;
esac
;;
*) sethostent_r_proto=0
;;
esac

```

Found in path(s):

```

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/threads/d_sethostent_r.U

```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: d_statblks.U,v \$

?RCS: Revision 3.0 1993/08/18 12:07:29 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?MAKE:d_statblks: contains Setvar Findhdr

?MAKE: -pick add \$@ %<

?S:d_statblks:

?S: This variable conditionally defines USE_STAT_BLOCKS if this system

?S: has a stat structure declaring st_blksize and st_blocks.

?S:.

?C:USE_STAT_BLOCKS (STATBLOCKS):

?C: This symbol is defined if this system has a stat structure declaring

?C: st_blksize and st_blocks.

?C:.

?H:#\$d_statblks USE_STAT_BLOCKS

/**/

?H:.

?T:xxx

?LINT:set d_statblks

: see if stat knows about block sizes

```

echo " "
xxx=`./findhdr sys/stat.h`
if $contains 'st_blocks;' "$xxx" >/dev/null 2>&1 ; then
if $contains 'st_blksize;' "$xxx" >/dev/null 2>&1 ; then
echo "Your stat() knows about block sizes." >&4
val="$define"
else
echo "Your stat() doesn't know about block sizes." >&4
val="$undef"
fi
else
echo "Your stat() doesn't know about block sizes." >&4
val="$undef"
fi
set d_statblks
eval $setvar

```

Found in path(s):

```

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/d_statblks.U

```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_endhent.U,v 3.0 1993/08/18 12:06:09 ram Exp \$

?RCS:

?RCS: Copyright (c) 1991-1993, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 3.0.

?RCS:

?RCS: \$Log: d_endhent.U,v \$

?RCS: Revision 3.0 1993/08/18 12:06:09 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?MAKE:d_endhent: Inlibc

?MAKE: -pick add \$@ %<

?S:d_endhent:

?S: This variable conditionally defines HAS_ENDHOSTENT if endhostent() is

?S: available to close whatever was being used for host queries.

?S:.

?C:HAS_ENDHOSTENT:

?C: This symbol, if defined, indicates that the endhostent() routine is

?C: available to close whatever was being used for host

queries.

?C:.

?H:#\$d_endhent HAS_ENDHOSTENT /**/

?H:
?LINT:set d_endhent
: see if endhostent exists
set endhostent d_endhent
eval \$inlibc

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/modified/d_endhent.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 2000 Jarkko Hietaniemi

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?MAKE:d_class: Inlibc

?MAKE: -pick add \$@ %<

?S:d_class:

?S: This variable conditionally defines the HAS_CLASS symbol, which

?S: indicates to the C program that the class() routine is available.

?S:.

?C:HAS_CLASS:

?C: This symbol, if defined, indicates that the class routine is

?C: available to classify doubles. Available for example in AIX.

?C: The returned values are defined in <float.h> and are:

?C:

?C: FP_PLUS_NORM Positive normalized, nonzero

?C: FP_MINUS_NORM Negative normalized, nonzero

?C: FP_PLUS_DENORM Positive denormalized, nonzero

?C: FP_MINUS_DENORM Negative denormalized, nonzero

?C: FP_PLUS_ZERO +0.0

?C: FP_MINUS_ZERO -0.0

?C: FP_PLUS_INF +INF

?C: FP_MINUS_INF -INF

?C: FP_NANS Signaling

Not a Number (NaNS)

?C: FP_NANQ Quiet Not a Number (NaNQ)

?C:.

?H:#\$d_class HAS_CLASS /**/

?H:.

?LINT:set d_class

: see if class exists

set class d_class

eval \$inlibc

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_class.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1998 Jarkko Hietaniemi

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?MAKE:d_atoll: Inlibc

?MAKE: -pick add \$@ %<

?S:d_atoll:

?S: This variable conditionally defines the HAS_ATOLL symbol, which

?S: indicates to the C program that the atoll() routine is available.

?S:.

?C:HAS_ATOLL:

?C: This symbol, if defined, indicates that the atoll routine is

?C: available to convert strings into long longs.

?C:.

?H:#\$d_atoll HAS_ATOLL /**/

?H:.

?LINT:set d_atoll

: see if atoll exists

set atoll d_atoll

eval \$inlibc

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/atoll.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1999, Jarkko Hietaniemi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 3.0.

?RCS:

?MAKE:d_timer_getoverrun: Inlibc

?MAKE: -pick add \$@ %<

?S:d_timer_getoverrun:

?S: This variable conditionally defines HAS_TIMER_GETOVERRUN

?S: if timer_getoverrun() is available to get the number of

?S: overruns of a POSIX timer.

?S:.

?C:HAS_TIMER_GETOVERRUN:

?C: This symbol, if defined, indicates that the timer_getoverrun

?C: system call is available to get the number of overruns of

?C: a POSIX timer.

?C:.

?H:#\$d_timer_getoverrun HAS_TIMER_GETOVERRUN /**/

?H:.

?LINT:set d_timer_getoverrun

: see if timer_getoverrun exists

set

timer_getoverrun d_timer_getoverrun

eval \$inlibc

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_timer_getoverrun.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_gethostbyaddr_r.U,v 0RCS:

?RCS: Copyright (c) 2002,2003 Jarkko Hietaniemi

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?RCS: Generated by the reentr.pl from the Perl 5.8 distribution.

?RCS:

?MAKE:d_gethostbyaddr_r gethostbyaddr_r_proto: Inlibc Protochk Hasproto \
i_systypes usethreads i_netdb extern_C

?MAKE: -pick add \$@ %<

?S:d_gethostbyaddr_r:

?S: This variable conditionally defines the HAS_GETHOSTBYADDR_R symbol,

?S: which indicates to the C program that the gethostbyaddr_r()

?S: routine is available.

?S:.

?S:gethostbyaddr_r_proto:

?S: This variable encodes the prototype of gethostbyaddr_r.

?S: It is zero if d_gethostbyaddr_r is undef, and one of the

?S: REENTRANT_PROTO_T_ABC macros of reentr.h if d_gethostbyaddr_r

?S: is defined.

?S:.

?C:HAS_GETHOSTBYADDR_R:

?C: This symbol, if defined, indicates

that the gethostbyaddr_r routine

?C: is available to gethostbyaddr re-entrantly.

?C:.

```

?C:GETHOSTBYADDR_R_PROTO:
?C: This symbol encodes the prototype of gethostbyaddr_r.
?C: It is zero if d_gethostbyaddr_r is undef, and one of the
?C: REENTRANT_PROTO_T_ABC macros of reentr.h if d_gethostbyaddr_r
?C: is defined.
?C:.
?H:#$d_gethostbyaddr_r HAS_GETHOSTBYADDR_R /**/
?H:#define GETHOSTBYADDR_R_PROTO $gethostbyaddr_r_proto /**/
?H:.
?T:try hdrs d_gethostbyaddr_r_proto
: see if gethostbyaddr_r exists
set gethostbyaddr_r d_gethostbyaddr_r
eval $inlibc
case "$d_gethostbyaddr_r" in
"$define")
hdrs="$i_systypes sys/types.h define stdio.h $i_netdb netdb.h"
case "$d_gethostbyaddr_r_proto:$usethreads" in
":define") d_gethostbyaddr_r_proto=define
set d_gethostbyaddr_r_proto gethostbyaddr_r $hdrs
eval $hasproto ;;
*) ;;
esac
case "$d_gethostbyaddr_r_proto" in
define)
case "$gethostbyaddr_r_proto" in
"|0) try='int gethostbyaddr_r(const char*, size_t, int, struct hostent*,
char*, size_t, struct hostent**, int*);'
./protochk "$extern_C $try" $hdrs && gethostbyaddr_r_proto=I_CWISBWRE ;;
esac
case "$gethostbyaddr_r_proto" in
"|0) try='struct hostent* gethostbyaddr_r(const char*, size_t, int, struct hostent*, char*, size_t, int, int*);'
./protochk "$extern_C $try" $hdrs && gethostbyaddr_r_proto=S_CWISBWIE ;;
esac
case "$gethostbyaddr_r_proto" in
"|0) try='struct hostent* gethostbyaddr_r(const char*, size_t, int, struct hostent*, char*, int, int*);'
./protochk "$extern_C $try" $hdrs && gethostbyaddr_r_proto=S_CWISBIE ;;
esac
case "$gethostbyaddr_r_proto" in
"|0) try='struct hostent* gethostbyaddr_r(const void*, size_t, int, struct hostent*, char*, int, int*);'
./protochk "$extern_C $try" $hdrs && gethostbyaddr_r_proto=S_TWISBIE ;;
esac
case "$gethostbyaddr_r_proto" in
"|0) try='struct hostent* gethostbyaddr_r(const char*, int, int, struct hostent*, char*, int, int*);'
./protochk "$extern_C $try" $hdrs && gethostbyaddr_r_proto=S_CIISBIE ;;
esac
case
"$gethostbyaddr_r_proto" in
"|0) try='struct hostent* gethostbyaddr_r(const char*, struct hostent*, char*, int, int*);'

```

```

./protochk "$extern_C $try" $hdrs && gethostbyaddr_r_proto=S_CSBIE ;;
esac
case "$gethostbyaddr_r_proto" in
"|0) try='struct hostent* gethostbyaddr_r(const void*, struct hostent*, char*, int, int*);'
./protochk "$extern_C $try" $hdrs && gethostbyaddr_r_proto=S_TSBIE ;;
esac
case "$gethostbyaddr_r_proto" in
"|0) try='int gethostbyaddr_r(const char*, size_t, int, struct hostent*, struct hostent_data*);'
./protochk "$extern_C $try" $hdrs && gethostbyaddr_r_proto=I_CWISD ;;
esac
case "$gethostbyaddr_r_proto" in
"|0) try='int gethostbyaddr_r(const char*, int, int, struct hostent*, struct hostent_data*);'
./protochk "$extern_C $try" $hdrs && gethostbyaddr_r_proto=I_CISD ;;
esac
case "$gethostbyaddr_r_proto" in
"|0) try='int gethostbyaddr_r(const char*, int, int);'
./protochk "$extern_C $try" $hdrs && gethostbyaddr_r_proto=I_CII ;;
esac
case
"$gethostbyaddr_r_proto" in
"|0) try='int gethostbyaddr_r(const void*, socklen_t, int, struct hostent*, char*, size_t, struct hostent**, int*);'
./protochk "$extern_C $try" $hdrs && gethostbyaddr_r_proto=I_TsISBWRE ;;
esac
case "$gethostbyaddr_r_proto" in
"|0) d_gethostbyaddr_r=undef
    gethostbyaddr_r_proto=0
    echo "Disabling gethostbyaddr_r, cannot determine prototype." >&4 ;;
*) case "$gethostbyaddr_r_proto" in
REENTRANT_PROTO*) ;;
*) gethostbyaddr_r_proto="REENTRANT_PROTO_$gethostbyaddr_r_proto" ;;
esac
echo "Prototype: $try" ;;
esac
;;
*) case "$usetthreads" in
define) echo "gethostbyaddr_r has no prototype, not using it." >&4 ;;
esac
d_gethostbyaddr_r=undef
gethostbyaddr_r_proto=0
;;
esac
;;
*) gethostbyaddr_r_proto=0
;;
esac

```

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-

debian-perl-5.26.1/U/threads/d_gethostbyaddr_r.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: End.U,v \$

?RCS: Revision 3.0 1993/08/18 12:04:51 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?X:

?X: This unit serves as the goal which forces make to choose all the units that

?X: ask questions. The \$W on the ?MAKE: line is the list of all symbols wanted.

?X: To force any unit to be included, copy this unit to your private U directory

?X: and add the name of the unit desired to the ?MAKE: dependency line.

?X:

?MAKE:End: \$W

?MAKE: -pick add \$@ %<

?LINT:use \$W

: end of configuration

questions

echo " "

echo "End of configuration questions."

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-

debian-perl-5.26.1/dist/U/End.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: Chk_MANI.U 1 2006-08-24 12:32:52Z rmanfredi \$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic Licence,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic Licence; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: Chk_MANI.U,v \$

?RCS: Revision 3.0.1.2 1997/02/28 14:57:25 ram

?RCS: patch61: added support for src.U

?RCS:

?RCS: Revision 3.0.1.1 1994/10/31 09:33:14 ram

?RCS: patch44: now lists Begin instead of Myinit in its dependencies

?RCS: patch44: leading comment now explains how this unit is included

?RCS:

?RCS: Revision 3.0 1993/08/18 12:04:45 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?X:

?X: This unit checks the package by making sure every file listed in MANIFEST

?X: is present. It is systematically "included" via the Finish unit (which

?X: is always present in every Configure script), although it may result in

?X: an empty inclusion when no MANIFEST is present.

?X:

?MAKE:Chk_MANI: Begin c n rsrc

?MAKE: -pick wipe \$@ %<

?T:filelist ans tmppwd

?X: This check happens at metaconfig-time, so it's ok to hard-code the path.

```
@if {test -f ../MANIFEST}
: Now test for existence of everything in MANIFEST
echo " "
if test -f "$rsrc/MANIFEST"; then
echo "First let's make sure your kit is complete. Checking..." >&4
?X:
?X: Files spelled uppercased and beginning with PACK are produced by the
?X: shell archive builder and may be removed by the user. Usually, they are
?X: not listed in the MANIFEST file, but you never know...
?X:
?X: "split -l" is the new way of running a split, but we also try the older way
?X:
awk '$1 !~ /PACK[A-Z]+/ {print $1}' "$rsrc/MANIFEST" | \
(split -l 50 2>/dev/null || split -50)
rm -f missing
tmppwd=`pwd`
for
filelist in x??: do
(cd "$rsrc"; ls `cat "$tmppwd/$filelist"` \
>/dev/null 2>>"$tmppwd/missing")
done
if test -s missing; then
cat missing >&4
cat >&4 <<'EOM'
```

THIS PACKAGE SEEMS TO BE INCOMPLETE.

You have the option of continuing the configuration process, despite the

distinct possibility that your kit is damaged, by typing 'y'es. If you do, don't blame me if something goes wrong. I advise you to type 'n'o and contact the author (<MAINTLOC>).

EOM

?X: Can't use \$echo at this early stage

```
echo $n "Continue? [n] $c" >&4
```

```
read ans
```

```
case "$ans" in
```

```
y*)
```

```
echo "Continuing..." >&4
```

```
rm -f missing
```

```
::
```

```
*)
```

?X:

?X: Use kill and not exit, so that the trap gets executed to clean up

?X:

```
echo "ABORTING..." >&4
```

```
kill $$
```

```
::
```

```
esac
```

```
else
```

```
echo "Looks good..."
```

```
fi
```

```
else
```

```
echo "There is no MANIFEST file. I hope your kit is complete !"
```

```
fi
```

```
rm -f missing x??
```

@end

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/Chk_MANI.U
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1999 Jarkko Hietaniemi

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?MAKE:d_fstatfs : Inlibc

?MAKE: -pick add \$@ %<

?S:d_fstatfs:

?S: This variable conditionally defines the HAS_FSTATFS symbol, which

?S: indicates to the C program that the fstatfs() routine is available.

?S:
?C:HAS_FSTATFS:
?C: This symbol, if defined, indicates that the fstatfs routine is
?C: available to stat filesystems by file descriptors.

?C:
?H:#\$d_fstatfs HAS_FSTATFS /**/

?H:
?LINT:set d_fstatfs
: see if fstatfs exists
set fstatfs d_fstatfs
eval \$inlibc

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_fstatfs.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: i_systimeb.U 1 2006-08-24 12:32:52Z rmanfredi \$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic Licence,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic Licence; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: i_systimeb.U,v \$

?RCS: Revision 3.0 1993/08/18 12:08:37 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?X:

?X: This unit looks wether <sys/timeb.h> should be included

?X: or not when using ftime() (for struct timeb definition).

?X:

?X: Force looking for <sys/time.h> for struct timeb.

?X:INC: i_systime

?MAKE:i_systimeb: test contains Loc Setvar Findhdr

?MAKE:-pick add \$@ %<

?S:i_systimeb:

?S: This variable conditionally defines I_SYS_TIMEB,
which indicates

?S: to the C program that it should include <sys/timeb.h>.

?S:.

?C:I_SYS_TIMEB (I_SYSTIMEB):

?C: This symbol, if defined, indicates to the C program that it should

?C: include <sys/timeb.h>, in order to define struct timeb (some systems

?C: define this in <sys/time.h>). This is useful when using ftime().

```

?C: You should include <sys/time.h> if I_SYS_TIMEB is not defined,
?C: nor is I_SYS_TIME.
?C:.
?H:#$i_systimeb I_SYS_TIMEB /**/
?H:.
?T:xxx
?LINT:set i_systimeb
: see where struct timeb is defined
echo " "
xxx=`./findhdr sys/timeb.h`
if $test "$xxx"; then
if $contains 'struct timeb' $xxx >/dev/null 2>&1; then
val="$define"
echo "You have struct timeb defined in <sys/timeb.h>." >&4
else
val="$undef"
echo "Assuming struct timeb is defined in <sys/time.h>." >&4
fi
else
val="$undef"
echo "No <sys/timeb.h> -- Assuming struct timeb is defined in <sys/time.h>." >&4
fi
set i_systimeb
eval $setvar

```

Found in path(s):

```

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/i_systimeb.U

```

No license file was found, but licenses were detected in source scan.

```

?RCS: $Id: d_strtod.U 1 2006-08-24 12:32:52Z rmanfredi $
?RCS:
?RCS: Copyright (c) 1996, Andy Dougherty
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: $Log: d_strtod.U,v $
?RCS: Revision 3.0.1.1 1997/02/28 15:46:36 ram
?RCS: patch61: created
?RCS:
?RCS:
?MAKE:d_strtod: Inlibc
?MAKE: -pick add $@ %<

```

?S:d_strtod:

?S: This variable conditionally defines the HAS_STRTOD symbol, which

?S: indicates to the C program that the strtod() routine is available

?S: to provide better numeric string conversion than atof().

?S:.

?C:HAS_STRTOD (STRTOD):

?C: This symbol, if defined,

indicates that the strtod routine is

?C: available to provide better numeric string conversion than atof().

?C:.

?H:#\$d_strtod HAS_STRTOD /**/

?H:.

?LINT:set d_strtod

: see if strtod exists

set strtod d_strtod

eval \$inlibc

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/d_strtod.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: make.U 1 2006-08-24 12:32:52Z rmanfredi \$

?RCS:

?RCS: Copyright (c) 1996, Andy Dougherty

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic Licence,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic Licence; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: make.U,v \$

?RCS: Revision 3.0.1.1 1997/02/28 16:09:40 ram

?RCS: patch61: created

?RCS:

?MAKE:make_set_make : Loc rm sed make

?MAKE: -pick add \$@ %<

?S:make_set_make:

?S: Some versions of 'make' set the variable MAKE. Others do not.

?S: This variable contains the string to be included in Makefile.SH

?S: so that MAKE is set if needed, and not if not needed.

?S: Possible values are:

?S:

?S: make_set_make='#' #

If your make program handles this for you,

?S:

```

?S: make_set_make="MAKE=$make" # if it doesn't.
?S:
?S: This uses a comment character so that we can distinguish a
?S: 'set' value (from a previous config.sh or Configure -D option)
?S: from an uncomputed value.
?S:.
?LINT: extern MAKE
?LINT: change MAKE
?X: This test is based on one from an autoconf-generated configure
?X: script. Autoconf stole a lot from Configure, but now it's our
?X: turn to do so... ;-) -- RAM, 21/02/97
: check whether make sets MAKE
echo " "
echo "Checking if your $make program sets \$(MAKE)..." >&4
case "$make_set_make" in
")
?X: Use sed so we don't have a line beginning with @echo. Metaconfig
?X: will think that's a command like @if or @end.
$sed 's/^X //' > testmake.mak << 'EOF'
Xall:
X @echo 'maketemp="\$(MAKE)'"
EOF
?X: GNU make sometimes prints "make[1]: Entering...", which would confuse us
case "$make -f testmake.mak 2>/dev/null" in
*maketemp=*) make_set_make='#' ;;
*) make_set_make="MAKE=$make" ;;
esac
$rm
-f testmake.mak
;;
esac
case "$make_set_make" in
'#') echo "Yup, it does.";;
*) echo "Nope, it doesn't.";;
esac

```

Found in path(s):

```

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/make.U

```

No license file was found, but licenses were detected in source scan.

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?MAKE:d_llround: Inlibc

?MAKE: -pick add \$@ %<

?S:d_llround:

?S: This variable conditionally defines the HAS_LLROUND symbol, which

?S: indicates to the C program that the llround() routine is available

?S: to return the long long value nearest to x.

?S:.

?C:HAS_LLROUND:

?C: This symbol, if defined, indicates that the llround routine is

?C: available to return the nearest long long value.

?C:.

?H:#\$d_llround HAS_LLROUND /**/

?H:.

?LINT:set d_llround

: see if llround exists

set llround d_llround

eval \$inlibc

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_llround.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: Original Author: Andy Dougherty <doughera@lafcol.lafayette.edu>

?RCS:

?RCS: \$Log: i_db.U,v \$

?RCS: Revision 3.0.1.3 1995/07/25 14:10:22 ram

?RCS: patch56: conditionally use const in test programs (ADO)

?RCS:

?RCS: Revision 3.0.1.2 1995/05/12 12:14:42 ram

?RCS: patch54: extended for more intimate DB probing (ADO)

?RCS:

?RCS: Revision 3.0.1.1 1994/08/29 16:21:50 ram

?RCS: patch32: created by ADO

?RCS:

?MAKE:i_db db_hashtype db_prefixtype: Inhdr +cc +ccflags rm_try contains cat \
d_const

?MAKE: -pick

add \$@ %<

?S:i_db:

?S: This variable conditionally defines the I_DB symbol, and indicates

?S: whether a C program may include Berkeley's DB include file <db.h>.

```

?S:.
?S:db_hashtype:
?S: This variable contains the type of the hash structure element
?S: in the <db.h> header file. In older versions of DB, it was
?S: int, while in newer ones it is u_int32_t.
?S:.
?S:db_prefixtype:
?S: This variable contains the type of the prefix structure element
?S: in the <db.h> header file. In older versions of DB, it was
?S: int, while in newer ones it is size_t.
?S:.
?C:I_DB:
?C: This symbol, if defined, indicates to the C program that it should
?C: include Berkeley's DB include file <db.h>.
?C:.
?C:DB_Prefix_t:
?C: This symbol contains the type of the prefix structure element
?C: in the <db.h> header file. In older versions of DB, it was
?C: int, while in newer ones it is u_int32_t.
?C:.
?C:DB_Hash_t:
?C: This symbol contains the type of the prefix structure element
?C: in the <db.h> header
file. In older versions of DB, it was
?C: int, while in newer ones it is size_t.
?C:.
?H:#$i_db I_DB /**/
?H:#define DB_Hash_t $db_hashtype /**/
?H:#define DB_Prefix_t $db_prefixtype /**/
?H:.
?LINT:set i_db
: see if this is a db.h system
set db.h i_db
eval $inhdr

@if DB_Hash_t
case "$i_db" in
define)
: Check the return type needed for hash
echo " "
echo "Checking return type needed for hash for Berkeley DB ..." >&4
$cat >try.c <<EOCP
#$d_const HASCONST
#ifndef HASCONST
#define const
#endif
#include <sys/types.h>
#include <db.h>

```

```

u_int32_t hash_cb (ptr, size)
const void *ptr;
size_t size;
{
}
HASHINFO info;
int main()
{
info.hash = hash_cb;
}
EOCP
if $cc $ccflags -c try.c >try.out 2>&1 ; then
if $contains warning try.out >>/dev/null 2>&1 ; then
db_hashtype='int'
else
db_hashtype='u_int32_t'
fi
else
echo "I can't seem to compile the test program." >&4
db_hashtype=int
fi
$rm_try
echo "Your version of Berkeley DB uses $db_hashtype for hash."
;;
*) db_hashtype=int
;;
esac

@end
@if
DB_Prefix_t
case "$i_db" in
define)
: Check the return type needed for prefix
echo " "
echo "Checking return type needed for prefix for Berkeley DB ..." >&4
cat >try.c <<EOCP
#$d_const HASCONST
#ifndef HASCONST
#define const
#endif
#include <sys/types.h>
#include <db.h>
size_t prefix_cb (key1, key2)
const DBT *key1;
const DBT *key2;
{
}

```

```

BTREEINFO info;
int main()
{
    info.prefix = prefix_cb;
}
EOCP
if $cc $cflags -c try.c >try.out 2>&1 ; then
    if $contains warning try.out >>/dev/null 2>&1 ; then
        db_prefixtype='int'
    else
        db_prefixtype='size_t'
    fi
else
    echo "I can't seem to compile the test program." >&4
    db_prefixtype='int'
fi
$rm_try
echo "Your version of Berkeley DB uses $db_prefixtype for prefix."
;;
*) db_prefixtype='int'
;;
esac

@end

```

Found in path(s):

```

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/i_db.U

```

No license file was found, but licenses were detected in source scan.

```

?RCS: $Id: i_ustat.U,v $
?RCS:
?RCS: Copyright (c) 1998 Jarkko Hietaniemi
?RCS:
?RCS: You may distribute under the terms of either the GNU General Public
?RCS: License or the Artistic License, as specified in the README file.
?RCS:
?MAKE:i_ustat: Inhdr Hasfield
?MAKE: -pick add $@ %<
?S:i_ustat:
?S: This variable conditionally defines the I_USTAT symbol, and indicates
?S: whether a C program should include <ustat.h>.
?S:.
?C:I_USTAT:
?C: This symbol, if defined, indicates that <ustat.h> exists and
?C: should be included.
?C:.
?H:#$i_ustat I_USTAT /**/

```

```
?H:
?LINT:set i_ustat
: see if this is a ustat.h system
set ustat.h i_ustat
eval $inhdr
```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/perl/i_ustat.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id$
```

```
?RCS:
```

```
?RCS: Copyright (c) 2015 Jarkko Hietaniemi, H.Merijn Brand
```

```
?RCS:
```

```
?RCS: You may distribute under the terms of either the GNU General Public
```

```
?RCS: License or the Artistic License, as specified in the README file.
```

```
?RCS:
```

```
?MAKE:longdblmanbits doublemanbits nvmanbits: Inlibc cat Compile run \
rm_try Setvar echo i_float i_sunmath usequadmath \
d_longdbl longdblkind nvszie doublesize longdblsize
```

```
?MAKE: -pick add $@ %<
```

```
?S:doublemanbits:
```

```
?S: This symbol, if defined, tells how many mantissa bits
```

```
?S: there are in double precision floating point format.
```

```
?S: Note that this is usually DBL_MANT_DIG minus one, since
```

```
?S: with the standard IEEE 754 formats DBL_MANT_DIG includes
```

```
?S: the implicit bit which doesn't really exist.
```

```
?S:.
```

```
?S:longdblmanbits:
```

```
?S: This symbol, if defined, tells how many mantissa bits
```

```
?S: there are in long double precision floating point format.
```

```
?S: Note that this can be LDBL_MANT_DIG minus
```

```
one,
```

```
?S: since LDBL_MANT_DIG can include the IEEE 754 implicit bit.
```

```
?S: The common x86-style 80-bit long double does not have
```

```
?S: an implicit bit.
```

```
?S:.
```

```
?S:nvmanbits:
```

```
?S: This variable tells how many bits the mantissa of a Perl NV has,
```

```
?S: not including the possible implicit bit.
```

```
?S:.
```

```
?C:DOUBLEMANTBITS:
```

```
?C: This symbol, if defined, tells how many mantissa bits
```

```
?C: there are in double precision floating point format.
```

```
?C: Note that this is usually DBL_MANT_DIG minus one, since
```

```
?C: with the standard IEEE 754 formats DBL_MANT_DIG includes
```

```
?C: the implicit bit, which doesn't really exist.
```

?C:.

?C:LONGDBLMANTBITS:

?C: This symbol, if defined, tells how many mantissa bits

?C: there are in long double precision floating point format.

?C: Note that this can be LDBL_MANT_DIG minus one,

?C: since LDBL_MANT_DIG can include the IEEE 754 implicit bit.

?C: The common x86-style 80-bit long double does not have

?C: an implicit bit.

?C:.

?C:NVMANTBITS:

?C: This symbol, if defined, tells how many mantissa

bits

?C: (not including implicit bit) there are in a Perl NV.

?C: This depends on which floating point type was chosen.

?C:.

?H:#define DOUBLEMANTBITS \$doublemantbits

?H:#define LONGDBLMANTBITS \$longdblmantbits

?H:#define NVMANTBITS \$nvmantbits

?H:.

?F:!try

: Check the length of the double mantissa

\$echo "Checking how many mantissa bits your doubles have..." >&4

\$cat >try.c <<EOP

```
#$i_float I_FLOAT
```

```
#$i_sunmath I_SUNMATH
```

```
#ifdef I_FLOAT
```

```
# include <float.h>
```

```
#endif
```

```
#ifdef I_SUNMATH
```

```
# include <sunmath.h>
```

```
#endif
```

```
#ifdef DBL_MANT_DIG
```

```
# define BITS (DBL_MANT_DIG - 1) /* the implicit bit does not count */
```

```
#endif
```

```
#include <stdio.h>
```

```
int main(int argc, char *argv[]) {
```

```
  #ifdef BITS
```

```
    printf("%d\n", BITS);
```

```
  #endif
```

```
  return 0;
```

```
}
```

```
EOP
```

```
set try
```

```
if eval $compile; then
```

```
  doublemantbits=`$run ./try`
```

```
else
```

```
  doublemantbits="$undef"
```

```
fi
```

\$rm_try

: Check the length of the longdouble mantissa

\$echo "Checking how many mantissa bits your long doubles have..." >&4

\$cat >try.c <<EOP

```
#$i_float I_FLOAT
```

```
#$i_sunmath
```

```
I_SUNMATH
```

```
#ifdef I_FLOAT
```

```
# include <float.h>
```

```
#endif
```

```
#ifdef I_SUNMATH
```

```
# include <sunmath.h>
```

```
#endif
```

```
#$d_longdbl HAS_LONG_DOUBLE
```

```
#if defined(HAS_LONG_DOUBLE) && defined(LDBL_MANT_DIG)
```

```
# if ($longdblkind == 3) || ($longdblkind == 4) /* 80-bit extended precision */
```

```
/* This format has no implicit bit. Beware, however, that for
```

```
* this format the bare LDBL_MANT_DIG is misleading for inf/nan:
```

```
* the top three bits are used for inf (100) / qnan (11x) / snan (101),
```

```
* and the top bit must have been one since 387, zero is plain invalid.
```

```
* For normal fp values, the LDBL_MANT_DIG is fine, though. */
```

```
# define BITS LDBL_MANT_DIG
```

```
# elif ($longdblkind == 5 || $longdblkind == 6 || $longdblkind == 7 || $longdblkind == 8) /* double double */
```

```
/* LDBL_MANT_DIG of 106 (twice 53) would be logical, but for some
```

```
* reason e.g. Irix thinks 107. But in any case, we want only
```

```
* the number of real bits, the implicit bits are of no interest. */
```

```
# define BITS 2 * (DBL_MANT_DIG - 1)
```

```
# else
```

```
# define BITS (LDBL_MANT_DIG
```

```
- 1) /* the implicit bit does not count */
```

```
# endif
```

```
#endif
```

```
#include <stdio.h>
```

```
int main(int argc, char *argv[]) {
```

```
#ifdef BITS
```

```
printf("%d\n", BITS);
```

```
#endif
```

```
return 0;
```

```
}
```

```
EOP
```

```
set try
```

```
if eval $compile; then
```

```
    longdblmantbits=`$run ./try`
```

```
else
```

```
    longdblmantbits="$undef"
```

```
fi
```

\$rm_try

```

: Check the length of the NV mantissa
$echo "Checking how many mantissa bits your NVs have..." >&4
if test "$usequadmath" = "$define"; then
  nvmantbits=112 # 128-1-15
else
  if test "$nvsize" = "$doublesize"; then
    nvmantbits="$doublemantbits"
  else
    if test "$nvsize" = "$longdblsize"; then
      nvmantbits="$longdblmantbits"
    else
      nvmantbits="$undef"
    fi
  fi
fi

```

Found in path(s):

```

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/perl/mantbits.U

```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: privlib.U,v 3.1 1999/07/08 18:32:29 doughera Exp doughera \$

?RCS:

?RCS: Copyright (c) 1991-1993, Raphael Manfredi

?RCS:

?RCS: This file is included with or a derivative work of a file included

?RCS: with the metaconfig program of Raphael Manfredi's "dist" distribution.

?RCS: In accordance with clause 7 of dist's modified Artistic License:

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?RCS: \$Log: privlib.U,v \$

?RCS: Revision 3.1 1999/07/08 18:32:29 doughera

?RCS: Updated for perl5.005_5x

?RCS:

?RCS: Revision 3.0.1.4 1995/09/25 09:17:09 ram

?RCS: patch59: unit is now forced to the top of Configure, if possible

?RCS:

?RCS: Revision 3.0.1.3 1995/01/30 14:44:23 ram

?RCS: patch49: can now handle installation prefix changes (from WED)

?RCS:

?RCS: Revision 3.0.1.2 1994/08/29 16:31:52 ram

?RCS:

patch32: now uses installation prefix

?RCS:

?RCS: Revision 3.0.1.1 1993/09/13 16:12:34 ram

?RCS: patch10: added support for /local/lib (WED)
?RCS: patch10: prompt phrasing made more explicit (WED)
?RCS:
?RCS: Revision 3.0 1993/08/18 12:09:35 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:privlib privlibexp installprivlib: package cat Getfile Oldconfig \
Setprefixvar Prefixit version installstyle binexp
?MAKE: -pick add \$@ %<
?Y:TOP
?D:privlib="
?S:privlib:
?S: This variable contains the eventual value of the PRIVLIB symbol,
?S: which is the name of the private library for this package. It may
?S: have a ~ on the front. It is up to the makefile to eventually create
?S: this directory while performing installation (with ~ substitution).
?S:.
?D:privlibexp="
?S:privlibexp:
?S: This variable is the ~name expanded version of privlib, so that you
?S: may use it directly in Makefiles or shell scripts.
?S:.
?D:installprivlib="
?S:installprivlib:
?S: This variable
is really the same as privlibexp but may differ on
?S: those systems using AFS. For extra portability, only this variable
?S: should be used in makefiles.
?S:.
?C:PRIVLIB:
?C: This symbol contains the name of the private library for this package.
?C: The library is private in the sense that it needn't be in anyone's
?C: execution path, but it should be accessible by the world. The program
?C: should be prepared to do ~ expansion.
?C:.
?C:PRIVLIB_EXP:
?C: This symbol contains the ~name expanded version of PRIVLIB, to be used
?C: in programs that are not prepared to deal with ~ expansion at run-time.
?C:.
?H:#define PRIVLIB "\$privlib" /**/
?H:#define PRIVLIB_EXP "\$privlibexp" /**/
?H:.
?LINT:change prefixvar
?LINT:set installprivlib
?LINT:set privlib
?LINT:set privlibexp
: determine where private library files go
: Usual default is /usr/local/lib/perl5/\$version.

```

: Also allow things like /opt/perl/lib/$version, since
: /opt/perl/lib/perl5... would be redundant.
: The default "style"
  setting is made in installstyle.U
case "$installstyle" in
*lib/perl5*) set dflt privlib lib/$package/$version ;;
*) set dflt privlib lib/$version ;;
esac
eval $prefixit
$cat <<EOM

```

There are some auxiliary files for \$package that need to be put into a private library directory that is accessible by everyone.

```

EOM
?X: Force dependency on bin.U
fn=$binexp
fn=d~+
rp='Pathname where the private library files will reside?'
./getfile
prefixvar=privlib
./setprefixvar

```

Found in path(s):

```

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/installdirs/privlib.U

```

No license file was found, but licenses were detected in source scan.

```

?RCS: $Id: d_srand48_r.U,v 0RCS:
?RCS: Copyright (c) 2002,2003 Jarkko Hietaniemi
?RCS:
?RCS: You may distribute under the terms of either the GNU General Public
?RCS: License or the Artistic License, as specified in the README file.
?RCS:
?RCS: Generated by the reentr.pl from the Perl 5.8 distribution.
?RCS:
?MAKE:d_srand48_r srand48_r_proto: Inlibc Protochk Hasproto i_systypes \
  usethreads i_stdlib extern_C
?MAKE: -pick add $@ %<
?S:d_srand48_r:
?S: This variable conditionally defines the HAS_SRAND48_R symbol,
?S: which indicates to the C program that the srand48_r()
?S: routine is available.
?S:.
?S:srand48_r_proto:
?S: This variable encodes the prototype of srand48_r.
?S: It is zero if d_srand48_r is undef, and one of the
?S: REENTRANT_PROTO_T_ABC macros of reentr.h if d_srand48_r

```

```

?S: is defined.
?S:.
?C:HAS_SRAND48_R:
?C: This symbol, if defined, indicates that the srand48_r routine
?C: is available to srand48 re-entrantly.
?C:.
?C:SRAND48_R_PROTO:
?C: This
symbol encodes the prototype of srand48_r.
?C: It is zero if d_srand48_r is undef, and one of the
?C: REENTRANT_PROTO_T_ABC macros of reentr.h if d_srand48_r
?C: is defined.
?C:.
?H:#$d_srand48_r HAS_SRAND48_R /**/
?H:#define SRAND48_R_PROTO $srand48_r_proto /**/
?H:.
?T:try hdrs d_srand48_r_proto
: see if srand48_r exists
set srand48_r d_srand48_r
eval $inlibc
case "$d_srand48_r" in
"$define")
hdrs="$i_systypes sys/types.h define stdio.h $i_stdlib stdlib.h"
case "$d_srand48_r_proto:$usethreads" in
":define") d_srand48_r_proto=define
set d_srand48_r_proto srand48_r $hdrs
eval $hasproto ;;
*) ;;
esac
case "$d_srand48_r_proto" in
define)
case "$srand48_r_proto" in
"|0) try='int srand48_r(long, struct drand48_data*);'
./protochk "$extern_C $try" $hdrs && srand48_r_proto=I_LS ;;
esac
case "$srand48_r_proto" in
"|0) d_srand48_r=undef
srand48_r_proto=0
echo "Disabling srand48_r, cannot determine prototype." >&4
;;
* ) case "$srand48_r_proto" in
REENTRANT_PROTO*) ;;
*) srand48_r_proto="REENTRANT_PROTO_$srand48_r_proto" ;;
esac
echo "Prototype: $try" ;;
esac
;;
*) case "$usethreads" in

```

```

define) echo "srand48_r has no prototype, not using it." >&4 ;;
esac
d_srand48_r=undef
srand48_r_proto=0
;;
esac
;;
*) srand48_r_proto=0
;;
esac

```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/threads/d_srand48_r.U
```

No license file was found, but licenses were detected in source scan.

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?MAKE:d_lgamma: Inlibc

?MAKE: -pick add \$@ %<

?S:d_lgamma:

?S: This variable conditionally defines the HAS_LGAMMA symbol, which

?S: indicates to the C program that the lgamma() routine is available

?S: for the log gamma function. See also d_tgamma and d_lgamma_r.

?S:.

?C:HAS_LGAMMA:

?C: This symbol, if defined, indicates that the lgamma routine is

?C: available to do the log gamma function. See also HAS_TGAMMA and

?C: HAS_LGAMMA_R.

?C:.

?H:#\$d_lgamma HAS_LGAMMA /**/

?H:.

?LINT:set d_lgamma

: see if lgamma exists

set lgamma d_lgamma

eval \$inlibc

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/perl/d_lgamma.U
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_memccpy.U 1 2006-08-24 12:32:52Z rmanfredi \$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic Licence,

?RCS: as specified in the README file that comes with the distribution.
 ?RCS: You may reuse parts of this distribution only within the terms of
 ?RCS: that same Artistic Licence; a copy of which may be found at the root
 ?RCS: of the source tree for dist 4.0.
 ?RCS:
 ?RCS: \$Log: d_memccpy.U,v \$
 ?RCS: Revision 3.0 1993/08/18 12:06:31 ram
 ?RCS: Baseline for dist 3.0 netwide release.
 ?RCS:
 ?MAKE:d_memccpy: Inlibc
 ?MAKE: -pick add \$@ %<
 ?S:d_memccpy:
 ?S: This variable conditionally defines the HAS_MEMCCPY symbol, which
 ?S: indicates to the C program that the memccpy() routine is available
 ?S: to copy a character into a block of memory.
 ?S:.
 ?C:HAS_MEMCCPY (MEMCCPY):
 ?C: This symbol, if defined, indicates that the memccpy routine
 is available
 ?C: to copy a character into a block of memory. Otherwise you should
 ?C: roll your own.
 ?C:.
 ?H:#\$d_memccpy HAS_MEMCCPY /**/
 ?H:.
 ?LINT:set d_memccpy
 : see if memccpy exists
 set memccpy d_memccpy
 eval \$inlibc

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/d_memccpy.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: Ins.U,v 3.0.1.1 1994/06/20 07:05:52 ram Exp \$
 ?RCS:
 ?RCS: Copyright (c) 1991-1993, Raphael Manfredi
 ?RCS:
 ?RCS: You may redistribute only under the terms of the Artistic License,
 ?RCS: as specified in the README file that comes with the distribution.
 ?RCS: You may reuse parts of this distribution only within the terms of
 ?RCS: that same Artistic License; a copy of which may be found at the root
 ?RCS: of the source tree for dist 3.0.
 ?RCS:
 ?RCS: Original Author: Andy Dougherty <doughera@lafcol.lafayette.edu>
 ?RCS:
 ?RCS: \$Log: Ins.U,v \$
 ?RCS: Revision 3.0.1.1 1994/06/20 07:05:52 ram

```

?RCS: patch30: created by ADO
?RCS:
?X:
?X: This unit checks whether symbolic links are really supported.
?X: We can't rely on d_symlink because that may be listed in the
?X: C library but unimplemented.
?X:
?MAKE:lns: ln rm touch
?MAKE: -pick add $@ %<
?S:lns:
?S: This variable holds the name of the command to make
?S: symbolic
links (if they are supported). It can be used
?S: in the Makefile. It is either 'ln -s' or 'ln'
?S:.
: determine whether symbolic links are supported
echo " "
$touch blurfl
if $ln -s blurfl sym > /dev/null 2>&1 ; then
echo "Symbolic links are supported." >&4
lns="$ln -s"
else
echo "Symbolic links are NOT supported." >&4
lns="$ln"
fi
$rm -f blurfl sym

```

Found in path(s):

```

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/modified/lns.U

```

No license file was found, but licenses were detected in source scan.

```

?RCS: $Id: Extract.U,v 3.0.1.2 1997/02/28 14:58:52 ram Exp $
?RCS:
?RCS: Copyright (c) 1991-1993, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 3.0.
?RCS:
?RCS: $Log: Extract.U,v $
?RCS: Revision 3.0.1.2 1997/02/28 14:58:52 ram
?RCS: patch61: added support for src.U
?RCS:
?RCS: Revision 3.0.1.1 1994/10/29 15:51:46 ram
?RCS: patch36: added ?F: line for metalint file checking

```

```

?RCS:
?RCS: Revision 3.0 1993/08/18 12:04:52 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?X:
?X: This unit produces a shell script which can be doted in order to extract
?X: .SH files with variable substitutions.
?X:
?X: When running
?X: Configure from a remote directory ($src is not '.'),
?X: then the files will be created in that directory, so beware!
?X:
?MAKE:Extract: src
?MAKE: -pick add $@ %<
?F:./extract
?T:PERL_CONFIG_SH dir file name create mkdir_p
: script used to extract .SH files with variable substitutions
cat >extract <<'EOS'
PERL_CONFIG_SH=true
echo "Doing variable substitutions on .SH files..."
if test -f MANIFEST; then
  set x `awk '{print $1}' < MANIFEST | grep /\.SH$`
else
  echo "(Looking for .SH files under the source directory.)"
  set x `(cd "$src"; find . -name "*.SH" -print)`
fi
shift
case $# in
0) set x `(cd "$src"; echo *.SH)`; shift;;
esac
if test ! -f "$src/$1"; then
  shift
fi
?X: script to emulate mkdir -p
mkdir_p='
name=$1;
create="";
while test $name; do
if test ! -d "$name"; then
  create="$name $create";
  name=`echo $name | sed -e "s|^[^/]*$||"`;
  name=`echo $name | sed -e "s|(.*).*/.*\|1|"`;
else
  name="";
fi;
done;
for file in $create; do
  mkdir $file;

```

```

done
'
for file in $*;
do
case "$src" in
".")
case "$file" in
*/*)
dir=`expr X$file : 'X\(.*)/'`
file=`expr X$file : 'X.*\^(.*)'`
(cd "$dir" && ./$file)
;;
*)
./$file
;;
esac
;;
*)
?X:
?X: When running Configure remotely ($src is not '.'), we cannot source
?X: the files directly, since that would wrongly cause the extraction
?X: where the source lie instead of withing the current directory. Therefore,
?X: we need to 'sh <file' then, which is okay since they will source the
?X: existing config.sh file. It's not possible to use:
?X: ../src/Configure -S -O -Dsomething
?X: unfortunately since no new config.sh with the -Dsomething override
?X: will be created before running the .SH files. A minor buglet.
?X:
?X: Note that we must create the directory hierarchy ourselves if it does
?X: not exist already, and that is done through a shell emulation of the
?X: 'mkdir -p' command. We don't want to use the $installdir metaconfig
?X: symbol here since that would require too much to
be configured for
?X: this simple extraction task that may happen quickly with 'Configure -S'.
?X: -- RAM, 18/03/96
?X:
case "$file" in
*/*)
dir=`expr X$file : 'X\(.*)/'`
file=`expr X$file : 'X.*\^(.*)'`
(set x $dir; shift; eval $mkdir_p)
sh <"$src/$dir/$file"
;;
*)
sh <"$src/$file"
;;
esac
;;

```

```

esac
done
if test -f "$src/config_h.SH"; then
if test ! -f config.h; then
: oops, they left it out of MANIFEST, probably, so do it anyway.
. "$src/config_h.SH"
fi
fi
EOS

```

Found in path(s):

```

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/modified/Extract.U

```

No license file was found, but licenses were detected in source scan.

```

?RCS: $Id: Mkdirp.U 1 2006-08-24 12:32:52Z rmanfredi $
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: $Log: Extract.U,v $
?RCS: Revision 3.0.1.2 1997/02/28 14:58:52 ram
?RCS: patch61: added support for src.U
?RCS:
?RCS: Revision 3.0.1.1 1994/10/29 15:51:46 ram
?RCS: patch36: added ?F: line for metalint file checking
?RCS:
?RCS: Revision 3.0 1993/08/18 12:04:52 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?X:
?X: This unit produces a shell script which can launched to create a
?X: directory path like "mkdir -p" would do.
?X:
?MAKE:Mkdirp:
eunicefix startsh
?MAKE: -pick add $@ %<
?F:./mkdirp
?T:name create file
: script used to emulate mkdir -p
cat >mkdirp <<EOS
$startsh
EOS

```

```

cat >>mkdirp <<'EOS'
name=$1;
create="";
while test $name; do
if test ! -d "$name"; then
create="$name $create"
name=`echo $name | sed -e "s|^[^/]*$||"``
name=`echo $name | sed -e "s|\\(.*\\)/.*|1|"``
else
name=""
fi
done
for file in $create; do
mkdir $file
done
EOS
chmod +x mkdirp
$unicefix mkdirp

```

Found in path(s):

```

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/Mkdirp.U

```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_sigvec.U 1 2006-08-24 12:32:52Z rmanfredi \$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic Licence,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic Licence; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: d_sigvec.U,v \$

?RCS: Revision 3.0.1.1 1997/02/28 15:45:37 ram

?RCS: patch61: there is now a separate routine for sigaction()

?RCS:

?RCS: Revision 3.0 1993/08/18 12:07:24 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?X: d_sigvec.U, from d_ftime.U 1.0

?X:

?MAKE:d_sigvec d_sigvectr d_sigintrp: Csym Inlibc Setvar

?MAKE: -pick add \$@ %<

?S:d_sigvec:

?S: This variable conditionally defines the HAS_SIGVEC symbol, which indicates

?S: that BSD

reliable signals are supported.

?S:.

?S:d_sigvectr:

?S: This variable conditionally defines the HAS_SIGVECTOR symbol, which

?S: indicates that the sigvec() routine is called sigvector() instead, for

?S: reasons known only to Hewlett-Packard.

?S:.

?S:d_sigintrp:

?S: This variable conditionally defines the HAS_SIGINTRP symbol, which

?S: indicates that the siginterrupt() routine is available.

?S:.

?C:HAS_SIGVEC (SIGVEC):

?C: This symbol, if defined, indicates that BSD reliable signals are

?C: supported.

?C:.

?C:HAS_SIGVECTOR (SIGVECTOR):

?C: This symbol, if defined, indicates that the sigvec() routine is called

?C: sigvector() instead, and that sigspace() is provided instead of

?C: sigstack(). This is probably only true for HP-UX.

?C:.

?C:HAS_SIGINTRP (SIGINTRP):

?C: This symbol, if defined, indicates that the siginterrupt() routine

?C: is available.

?C:.

?H:#\$d_sigvec HAS_SIGVEC /**/

?H:#\$d_sigvectr HAS_SIGVECTOR /**/

?H:#\$d_sigintrp HAS_SIGINTRP /**/

?H:.

?T:val

?LINT:set d_sigvec d_sigintrp

@if

d_sigvectr || d_sigvec || HAS_SIGVEC || HAS_SIGVECTOR

: see if sigvector exists -- since sigvec will match the substring

echo " "

if set sigvector val -f d_sigvectr; eval \$csym; \$val; then

echo 'sigvector() found--you must be running HP-UX.' >&4

val="\$define"; set d_sigvectr; eval \$setvar

val="\$define"; set d_sigvec; eval \$setvar

else

: try the original name

d_sigvectr="\$undef"

if set sigvec val -f d_sigvec; eval \$csym; \$val; then

echo 'sigvec() found.' >&4

val="\$define"; set d_sigvec; eval \$setvar

else

echo 'sigvec() not found--race conditions with signals may occur.' >&4

val="\$undef"; set d_sigvec; eval \$setvar

fi

fi

```
@end
@if d_sigintpr || HAS_SIGINTRP
: see if we have siginterrupt
set siginterrupt d_sigintpr
eval $inlibc
```

```
@end
```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/d_sigvec.U
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: Original Author: Andy Dougherty <doughera@lafcol.lafayette.edu>

?RCS:

?RCS: \$Log: prefix.U,v \$

?RCS: Revision 3.0.1.2 1995/01/30 14:44:05 ram

?RCS: patch49: new prefixexp variable holding a fully expanded prefix

?RCS: patch49: save off previous prefix value in oldprefix if changed (WED)

?RCS: patch49: added the INSTALLPREFIX define for C programs to use (WED)

?RCS:

?RCS: Revision 3.0.1.1 1994/08/29 16:31:34 ram

?RCS: patch32: created by ADO

?RCS:

?MAKE:prefix prefixexp +oldprefix: Getfile Loc Oldconfig

cat package

?MAKE: -pick add \$@ %<

?S:prefix:

?S: This variable holds the name of the directory below which the

?S: user will install the package. Usually, this is /usr/local, and

?S: executables go in /usr/local/bin, library stuff in /usr/local/lib,

?S: man pages in /usr/local/man, etc. It is only used to set defaults

?S: for things in bin.U, mansrc.U, privlib.U, or scriptdir.U.

?S:.

?S:prefixexp:

?S: This variable holds the full absolute path of the directory below

?S: which the user will install the package. Derived from prefix.
 ?S:.
 ?S:oldprefix:
 ?S: This variable is set non-null if the prefix was previously defined
 ?S: and gets set to a new value. Used internally by Configure only.
 ?S:.
 ?C:INSTALLPREFIX:
 ?C: This symbol contains the name of the install prefix for this package.
 ?C:.
 ?H:#define INSTALLPREFIX "\$prefix" /**/
 ?H:.
 : determine root of directory hierarchy where package will be installed.
 case "\$prefix" in
 ")
 dflt=`./loc . /usr/local /usr/local /local /opt
 /usr`
 ;;
 *)
 dflt="\$prefix"
 ;;
 esac
 \$cat <<EOM

By default, \$package will be installed in \$dflt/bin, manual pages under \$dflt/man, etc..., i.e. with \$dflt as prefix for all installation directories. Typically set to /usr/local, but you may choose /usr if you wish to install \$package among your system binaries. If you wish to have binaries under /bin but manual pages under /usr/local/man, that's ok: you will be prompted separately for each of the installation directories, the prefix being only used to set the defaults.

```
EOM
fn=d~
rp='Installation prefix to use?'
./getfile
oldprefix=""
case "$prefix" in
") ;;
*)
case "$ans" in
"$prefix") ;;
*) oldprefix="$prefix";;
esac
;;
esac
prefix="$ans"
prefixexp="$ansexp"
```

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/prefix.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_sysconf.U 1 2006-08-24 12:32:52Z rmanfredi \$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic Licence,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic Licence; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: Original Author: Andy Dougherty <doughera@lafcol.lafayette.edu>

?RCS:

?RCS: \$Log: d_sysconf.U,v \$

?RCS: Revision 3.0.1.1 1994/10/29 16:15:57 ram

?RCS: patch36: created by ADO

?RCS:

?MAKE:d_sysconf: Inlibc

?MAKE: -pick add \$@ %<

?S:d_sysconf:

?S: This variable conditionally defines the HAS_SYSCONF symbol, which

?S: indicates to the C program that the sysconf() routine is available

?S: to determine system related limits and options.

?S:.

?C:HAS_SYSCONF:

?C: This

symbol, if defined, indicates that sysconf() is available

?C: to determine system related limits and options.

?C:.

?H:#\$d_sysconf HAS_SYSCONF /**/

?H:.

?LINT:set d_sysconf

: see if sysconf exists

set sysconf d_sysconf

eval \$inlibc

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/d_sysconf.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_shmget.U 1 2006-08-24 12:32:52Z rmanfredi \$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: \$Log: d_shmget.U,v \$
?RCS: Revision 3.0 1993/08/18 12:07:20 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:d_shmget: Inlibc
?MAKE: -pick add \$@ %<
?S:d_shmget:
?S: This variable conditionally defines the HAS_SHMGET symbol, which
?S: indicates to the C program that the shmget() routine is available.
?S:.
?C:HAS_SHMGET:
?C: This symbol, if defined, indicates that the shmget() routine is
?C: available to request a shared memory segment from
the kernel.
?C:.
?H:#\$d_shmget HAS_SHMGET /**/
?H:.
?LINT:set d_shmget
: see if shmget exists
set shmget d_shmget
eval \$inlibc

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/d_shmget.U

No license file was found, but licenses were detected in source scan.

?RCS: You may distribute under the terms of either the GNU General Public
?RCS: License or the Artistic License, as specified in the README file.
?RCS:
?MAKE:d_fpgetround: Inlibc
?MAKE: -pick add \$@ %<
?S:d_fpgetround:
?S: This variable conditionally defines HAS_FPGETROUND if fpgetround()
?S: is available to get the floating point rounding mode.
?S:.
?C:HAS_FPGETROUND:
?C: This symbol, if defined, indicates that the fpgetround routine is
?C: available to get the floating point rounding mode.
?C:.

?H:#\$d_fpgetround HAS_FPGETROUND /**/

?H:.

?LINT:set d_fpgetround

: see if fpgetround exists

set fpgetround d_fpgetround

eval \$inlibc

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_fpgetround.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: i_limits.U 1 2006-08-24 12:32:52Z rmanfredi \$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic Licence,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic Licence; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: i_limits.U,v \$

?RCS: Revision 3.0 1993/08/18 12:08:20 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?MAKE:i_limits: Inhdr

?MAKE: -pick add \$@ %<

?S:i_limits:

?S: This variable conditionally defines the I_LIMITS symbol, and indicates

?S: whether a C program may include <limits.h> to get symbols like WORD_BIT

?S: and friends.

?S:.

?C:I_LIMITS:

?C: This symbol, if defined, indicates to the C program that it should

?C: include <limits.h> to

get definition of symbols like WORD_BIT or

?C: LONG_MAX, i.e. machine dependant limitations.

?C:.

?H:#\$i_limits I_LIMITS /**/

?H:.

?LINT:set i_limits

: see if this is a limits.h system

set limits.h i_limits

eval \$inhdr

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-

debian-perl-5.26.1/dist/U/i_limits.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: Nothing.U 1 2006-08-24 12:32:52Z rmanfredi \$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic Licence,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic Licence; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: Nothing.U,v \$

?RCS: Revision 3.0 1993/08/18 12:05:09 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?X:

?X: The purpose of this file is to supply an empty target for the private

?X: Makefile built by metaconfig to order the units.

?X:

?MAKE:Nothing: Head

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-

debian-perl-5.26.1/dist/U/Nothing.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1998, Jarkko Hietaniemi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 3.0.

?RCS:

?MAKE:i_sysaccess: Inhdr

?MAKE: -pick add \$@ %<

?S:i_sysaccess:

?S: This variable conditionally defines the I_SYS_ACCESS symbol,

?S: and indicates whether a C program should include <sys/access.h>.

?S:.

?C:I_SYS_ACCESS:

?C: This symbol, if defined, indicates to the C program that it should

?C: include <sys/access.h>.

?C:.

```
?H:#$i_sysaccess  L_SYS_ACCESS      /**/  
?H:.  
?LINT:set i_sysaccess  
: see if sys/access.h is available  
set sys/access.h i_sysaccess  
eval $inhdr
```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/acl/i_sysaccess.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: gidtype.U,v 3.0.1.3 1994/08/29 16:21:44 ram Exp $  
?RCS:  
?RCS: Copyright (c) 1991-1993, Raphael Manfredi  
?RCS:  
?RCS: You may redistribute only under the terms of the Artistic License,  
?RCS: as specified in the README file that comes with the distribution.  
?RCS: You may reuse parts of this distribution only within the terms of  
?RCS: that same Artistic License; a copy of which may be found at the root  
?RCS: of the source tree for dist 3.0.  
?RCS:  
?RCS: $Log: gidtype.U,v $  
?RCS: Revision 3.0.1.3 1994/08/29 16:21:44 ram  
?RCS: patch32: now uses new Typedef unit to compute type information  
?RCS: patch32: removed useless usage of Setvar (for now)  
?RCS:  
?RCS: Revision 3.0.1.2 1994/05/13 15:21:07 ram  
?RCS: patch27: added lint hint  
?RCS:  
?RCS: Revision 3.0.1.1 1994/05/06 15:01:51 ram  
?RCS: patch23: protected gidtype setting via setvar (ADO)  
?RCS: patch23: made Gid_t comment more explicit (ADO)  
?RCS:  
?RCS: Revision  
3.0 1993/08/18 12:08:11 ram  
?RCS: Baseline for dist 3.0 netwide release.  
?RCS:  
?MAKE:gidtype: Myread Typedef Findhdr  
?MAKE: -pick add $@ %<  
?S:gidtype:  
?S: This variable defines Gid_t to be something like gid_t, int,  
?S: ushort, or whatever type is used to declare the return type  
?S: of getgid(). Typically, it is the type of group ids in the kernel.  
?S:.  
?C:Gid_t (GIDTYPE):  
?C: This symbol holds the return type of getgid() and the type of  
?C: argument to setrgid() and related functions. Typically,
```

?C: it is the type of group ids in the kernel. It can be int, ushort,
?C: gid_t, etc... It may be necessary to include <sys/types.h> to get
?C: any typedef'ed information.

?C:.

?H:#define Gid_t \$gidtype /* Type for getgid(), etc... */

?H:.

?T:xxx

: see what type gids are declared as in the kernel

echo " "

echo "Looking for the type for group ids returned by getgid()."

set gid_t gidtype xxx stdio.h sys/types.h

eval \$typedef

case "\$gidtype" in

xxx)

xxx=`./findhdr sys/user.h`

set `grep

'groups[NGROUPS\];' "\$xxx" 2>/dev/null` unsigned short

case \$1 in

unsigned) dflt="\$1 \$2" ;;

*) dflt="\$1" ;;

esac

::

*) dflt="\$gidtype";;

esac

case "\$gidtype" in

gid_t) echo "gid_t found." ;;

*) rp="What is the type for group ids returned by getgid()?"

. ./myread

gidtype="\$ans"

::

esac

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/typedefs/gidtype.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: d_safemcpy.U,v \$

```

?RCS: Revision 3.0.1.5 1997/02/28 15:41:12 ram
?RCS: patch61: improved overlapping copy check
?RCS: patch61: comfort them if they have memmove
?RCS: patch61: added ?F: metalint hint
?RCS:
?RCS: Revision 3.0.1.4 1995/07/25 13:58:46 ram
?RCS: patch56: re-arranged compile line to include ldflags before objects
?RCS:
?RCS: Revision 3.0.1.3 1995/03/21 08:47:26 ram
?RCS: patch52: swapped two first arguments of memcpy() calls
?RCS:
?RCS: Revision 3.0.1.2 1994/10/29 16:15:10
    ram
?RCS: patch36: added 'ldflags' to the test compile line (ADO)
?RCS:
?RCS: Revision 3.0.1.1 1994/05/06 14:53:12 ram
?RCS: patch23: ensure string is not optimized in read-only memory (ADO)
?RCS:
?RCS: Revision 3.0 1993/08/18 12:06:58 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:d_safemcpy: cat d_memcpy +cc +optimize +ccflags +libs +ldflags rm \
    d_memmove i_memory i_stdlib i_string i_unistd Oldconfig Setvar
?MAKE: -pick add $@ %<
?S:d_safemcpy:
?S: This variable conditionally defines the HAS_SAFE_MEMCPY symbol if
?S: the memcpy() routine can do overlapping copies.
?S:.
?C:HAS_SAFE_MEMCPY (SAFE_MEMCPY):
?C: This symbol, if defined, indicates that the memcpy routine is available
?C: to copy potentially overlapping memory blocks. Otherwise you should
?C: probably use memmove() or memcpy(). If neither is defined, roll your
?C: own version.
?C:.
?H:#$d_safemcpy HAS_SAFE_MEMCPY /**/
?H:.
?F:!safemcpy
?LINT: set d_safemcpy
: can memcpy handle overlapping blocks?
?X:
    assume the worst
    val="$undef"
    case "$d_memcpy" in
"$define")
    echo " "
    echo "Checking to see if your memcpy() can do overlapping copies..." >&4
    $cat >foo.c <<EOCP
#$i_memory I_MEMORY

```

```

#$i_stdlib I_STDLIB
#$i_string I_STRING
#$i_unistd I_UNISTD
EOCP
$cat >>foo.c <<'EOCP'
#include <stdio.h>
#ifdef I_MEMORY
# include <memory.h>
#endif
#ifdef I_STDLIB
# include <stdlib.h>
#endif
#ifdef I_STRING
# include <string.h>
#else
# include <strings.h>
#endif
#ifdef I_UNISTD
# include <unistd.h> /* Needed for NetBSD */
#endif
int main()
{
char buf[128], abc[128];
char *b;
int len;
int off;
int align;

/* Copy "abcde..." string to char abc[] so that gcc doesn't
   try to store the string in read-only memory. */
memcpy(abc, "abcdefghijklmnopqrstuvwxy0123456789", 36);

for (align = 7; align >= 0; align--) {
for (len = 36; len; len--) {
b = buf+align;
memcpy(b, abc, len);
for (off = 1; off <= len; off++) {
memcpy(b+off, b, len);
memcpy(b, b+off, len);
if (memcmp(b, abc, len))
exit(1);
}
}
}
exit(0);
}
EOCP
if

```

```

$cc $optimize $ccflags $ldflags \
  -o safemcpy foo.c $libs >/dev/null 2>&1; then
if ./safemcpy 2>/dev/null; then
  echo "Yes, it can."
  val="$define"
else
  echo "It can't, sorry."
  case "$d_memmove" in
"$define") echo "But that's Ok since you have memmove()." ;;
  esac
fi
else
  echo "(I can't compile the test program, so we'll assume not...)"
  case "$d_memmove" in
"$define") echo "But that's Ok since you have memmove()." ;;
  esac
fi
;;
esac
$rm -f foo.* safemcpy core
set d_safemcpy
eval $setvar

```

Found in path(s):

```

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/d_safemcpy.U

```

No license file was found, but licenses were detected in source scan.

```

?RCS: $Id: d_popen.U 1 2006-08-24 12:32:52Z rmanfredi $
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: $Log: d_popen.U,v $
?RCS: Revision 3.0 1993/08/18 12:06:47 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:d_popen: Inlibc
?MAKE: -pick add $@ %<
?S:d_popen:
?S: This variable conditionally defines HAS_POPEN if popen() is
?S: available to open a pipe from a process.
?S:..

```

?C:HAS_POPEN (POPEN):

?C: This symbol, if defined, indicates that the popen routine is

?C: available to open a pipe from a process.

?C:.

?H:#\$d_popen HAS_POPEN /**/

?H:.

?LINT:set

d_popen

: see if popen exists

set popen d_popen

eval \$inlibc

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/d_popen.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_getpwent_r.U,v 0RCS:

?RCS: Copyright (c) 2002,2003 Jarkko Hietaniemi

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?RCS: Generated by the reentr.pl from the Perl 5.8 distribution.

?RCS:

?MAKE:d_getpwent_r getpwent_r_proto: Inlibc Protochk Hasproto i_systypes \
usethreads i_pwd extern_C

?MAKE: -pick add \$@ %<

?S:d_getpwent_r:

?S: This variable conditionally defines the HAS_GETPWENT_R symbol,

?S: which indicates to the C program that the getpwent_r()

?S: routine is available.

?S:.

?S:getpwent_r_proto:

?S: This variable encodes the prototype of getpwent_r.

?S: It is zero if d_getpwent_r is undef, and one of the

?S: REENTRANT_PROTO_T_ABC macros of reentr.h if d_getpwent_r

?S: is defined.

?S:.

?C:HAS_GETPWENT_R:

?C: This symbol, if defined, indicates that the getpwent_r routine

?C: is available to

getpwent re-entrantly.

?C:.

?C:GETPWENT_R_PROTO:

?C: This symbol encodes the prototype of getpwent_r.

?C: It is zero if d_getpwent_r is undef, and one of the

?C: REENTRANT_PROTO_T_ABC macros of reentr.h if d_getpwent_r

```

?C: is defined.
?C:.
?H:#$d_getpwent_r HAS_GETPWENT_R /**/
?H:#define GETPWENT_R_PROTO $getpwent_r_proto /**/
?H:.
?T:try hdrs d_getpwent_r_proto
: see if getpwent_r exists
set getpwent_r d_getpwent_r
eval $inlibc
case "$d_getpwent_r" in
"$define")
hdrs="$i_systypes sys/types.h define stdio.h $i_pwd pwd.h"
case "$d_getpwent_r_proto:$usetthreads" in
":define") d_getpwent_r_proto=define
set d_getpwent_r_proto getpwent_r $hdrs
eval $hasproto ;;
*) ;;
esac
case "$d_getpwent_r_proto" in
define)
case "$getpwent_r_proto" in
"|0) try='int getpwent_r(struct passwd*, char*, size_t, struct passwd**);'
./protochk "$extern_C $try" $hdrs && getpwent_r_proto=I_SBWR ;;
esac
case "$getpwent_r_proto" in
"|0) try='int getpwent_r(struct passwd*, char*, int, struct passwd**);'
./protochk
"$extern_C $try" $hdrs && getpwent_r_proto=I_SBIR ;;
esac
case "$getpwent_r_proto" in
"|0) try='struct passwd* getpwent_r(struct passwd*, char*, size_t);'
./protochk "$extern_C $try" $hdrs && getpwent_r_proto=S_SBW ;;
esac
case "$getpwent_r_proto" in
"|0) try='struct passwd* getpwent_r(struct passwd*, char*, int);'
./protochk "$extern_C $try" $hdrs && getpwent_r_proto=S_SBI ;;
esac
case "$getpwent_r_proto" in
"|0) try='int getpwent_r(struct passwd*, char*, int);'
./protochk "$extern_C $try" $hdrs && getpwent_r_proto=I_SBI ;;
esac
case "$getpwent_r_proto" in
"|0) try='int getpwent_r(struct passwd*, char*, int, FILE**);'
./protochk "$extern_C $try" $hdrs && getpwent_r_proto=I_SBIH ;;
esac
case "$getpwent_r_proto" in
"|0) d_getpwent_r=undef
getpwent_r_proto=0

```

```

echo "Disabling getpwent_r, cannot determine prototype." >&4 ;;
*) case "$getpwent_r_proto" in
REENTRANT_PROTO*) ;;
*) getpwent_r_proto="REENTRANT_PROTO_${getpwent_r_proto}"
;;
esac
echo "Prototype: $try" ;;
esac
;;
*) case "$usetthreads" in
define) echo "getpwent_r has no prototype, not using it." >&4 ;;
esac
d_getpwent_r=undef
getpwent_r_proto=0
;;
esac
;;
*) getpwent_r_proto=0
;;
esac

```

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/threads/d_getpwent_r.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_lockf.U 1 2006-08-24 12:32:52Z rmanfredi \$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic Licence,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic Licence; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: Original Author: Andy Dougherty <doughera@lafcol.lafayette.edu>

?RCS:

?RCS: \$Log: d_lockf.U,v \$

?RCS: Revision 3.0.1.1 1994/08/29 16:09:36 ram

?RCS: patch32: created by ADO

?RCS:

?MAKE:d_lockf: Inlibc

?MAKE: -pick add \$@ %<

?S:d_lockf:

?S: This variable conditionally defines HAS_LOCKF if lockf() is

?S: available to do file locking.

?S:.

?C:HAS_LOCKF (LOCKF):

?C: This symbol, if defined, indicates that the lockf routine is

?C: available to do file locking.

?C:.

?H:#\$d_lockf

```
HAS_LOCKF /**/
```

?H:.

?LINT:set d_lockf

: see if lockf exists

```
set lockf d_lockf
```

```
eval $inlibc
```

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/d_lockf.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: Myread.U 1 2006-08-24 12:32:52Z rmanfredi \$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic Licence,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic Licence; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: Myread.U,v \$

?RCS: Revision 3.0.1.6 1997/02/28 15:05:39 ram

?RCS: patch61: myread script now starts with a "startsh"

?RCS: patch61: miscellaneous fixes

?RCS:

?RCS: Revision 3.0.1.5 1995/01/11 15:14:22 ram

?RCS: patch45: added & escape allowing user to turn on -d from the prompt

?RCS:

?RCS: Revision 3.0.1.4 1994/10/31 09:48:04 ram

?RCS: patch44: added Options to the MAKE line since it's no longer in Init.U

?RCS:

?RCS: Revision 3.0.1.3 1994/10/29

15:56:20 ram

?RCS: patch36: added ?F: line for metalint file checking

?RCS:

?RCS: Revision 3.0.1.2 1993/08/30 08:57:59 ram

?RCS: patch8: added new visible 'nostick' symbol, mainly for Finish.U

?RCS:

?RCS: Revision 3.0.1.1 1993/08/27 14:39:20 ram

?RCS: patch7: now sticks to the question when no default and empty answer

?RCS:

?RCS: Revision 3.0 1993/08/18 12:05:08 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?X:

?X: This unit produces a bit of shell code that must be dotted in in order

?X: to do a read. It allows for shell escapes, default assignment and

?X: parameter evaluation.

?X:

?X: To use this unit, \$rp and \$dflt must hold the question and the

?X: default answer. The question will be printed by the script itself.

?X: Neither \$rp nor \$dflt is altered by the script.

?X:

?X: The myread script will stick to the question if no default is proposed

?X: and the user answer is empty, which prevents mistakes. However, at the

?X: end of Configure, there is an exception

to this rule (Finish.U) where we

?X: set nostick to a non-empty value to allow the Return key to play its role!

?X:

?MAKE:Myread: Options startsh n c trnl

?MAKE: -pick add \$@ %<

?V:ans:dflt rp nostick

?F:./myread

?T:COLUMNS xxxm rp dflt answ aok myecho

?LINT:change fastread

?X: Some shells (Ultrix) do not understand \${COLUMNS:-80}, sigh!

: compute the number of columns on the terminal for proper question formatting

case "\$COLUMNS" in

) COLUMNS='80';;

esac

: set up the echo used in my read

?X:

?X: This variable is intended to be eval'ed. It will echo the two

?X: variables \$rp and \$dflt (provided this latter has a non null value).

?X: It is mainly used by the myread script to echo the questions.

?X:

?X: The \$n and \$c below are substituted before Loc does its silly echo check

?X: so don't put a \$ on the echo below so we get builtin, even if \$echo is

?X: pointing to /bin/echo.

?X:

myecho="case \"\\$xxxm\" in

) echo \$n \"\\$rp \$c\" >&4;;

*) case \"\\$rp\" in

) echo \$n \"[\"\$xxxm] \$c\";;

*)

if

test `echo \"\\$rp [\"\$xxxm] \" | wc -c` -ge \$COLUMNS; then

echo \"\\$rp\" >&4

```

    echo $n \"[\$xxm] $c\" >&4
else
    echo $n \"\$rp [\$xxm] $c\" >&4
fi
;;
esac;;
esac"

```

: now set up to do reads with possible shell escape and default assignment

```
cat <<EOESC >myread
```

```
$startsh
```

```
?X:
```

```
?X: Save value of default -- do not alter original in case of eval
```

```
?X:
```

```
xxm=\$dflt
```

```
$myecho
```

```
?X:
```

```
?X: If there is no default, then stop, regardless of the value in fastread.
```

```
?X: In silent mode, no new-line is to be echoed if the question is empty,
```

```
?X: since this is used to wait for the "return" key.
```

```
?X:
```

```
ans=''
```

```
case \"\$fastread\" in
```

```
yes) case \"\$dflt\" in
```

```
) ;;
```

```
*) ans=";
```

```
case \"\$silent-\$rp\" in
```

```
true-) ;;
```

```
*) echo " " >&4;;
```

```
esac;;
```

```
esac;;
```

```
*) case \"\$silent\" in
```

```
true) case \"\$rp\" in
```

```
) ans=";;
```

```
esac;;
```

```
esac;;
```

```
esac
```

```
while expr "X\$ans" : "X!" >/dev/null; do
```

```
read answ
```

```
?X:
```

```
?X: Run 'eval' on the answer, in order to do variable substitution, in case
```

```
?X: the user types $HOME or $WHATEVER.
```

```
Variables must be evaluated now.
```

```
?X: Typing \"\$HOME\" won't currently prevent from substitution -- use \"\$HOME'
```

```
?X: The $1 .. $9 and $*, as well as $@, are available to refer to the
```

```
?X: default value.
```

```
?X:
```

```
set x \$xxm
```

```

shift
aok="; eval "ans=\\\"$answ\\\" && aok=y
case \"$answ\" in
?X:
?X: Use "!" and not a plain ! because of a bug in BSD 4.4 shell
?X: (reported by Wayne Davison)
?X: We must handle the shell escapes before dealing with possible variable
?X: substitution, since the shell we're launching in that case will be able
?X: to do it as well as we can -- RAM, 15/03/96
?X
"!")
sh 1>&4
echo " "
$myecho
;;
!*)
set x `expr "X$ans" : "X!(.*)\$" `
shift
sh 1>&4 -c "\$*"
echo " "
$myecho
;;
"$ans")
case "$ans" in
?X:
?X: Answers starting with & are hooks allowing to dynamically turn on/off
?X: some Configure options. That's for the future. -- RAM, 09/01/95
?X: Today, we only recognize '& -d' to mean 'go on as if Configure -d, which
?X: is a hardwired
behaviour compatible with our general scheme.
?X:
\\&*)
set x `expr "X$ans" : "X&(.*?)\$" `
shift
case "\$1" in
-d)
fastread=yes
echo "(OK, I'll run with -d after this question.)" >&4
;;
-*)
echo "*** Sorry, \$1 not supported yet." >&4
;;
esac
$myecho
ans=!
;;
esac;;
*)

```

```

case "$sak" in
y)
echo "*** Substitution done -- please confirm."
xxxm="$ans"
ans=`echo $n "$ans$c" | tr 'trnl' '\`
xxxm="$ans"
ans=!
;;
*)
echo "*** Error -- try again."
ans=!
;;
esac
$myecho
;;
esac
?X: Stick in myread if no default answer and nothing was answered
case "$ans$xxxm$nostick" in
")
ans=!
$myecho
;;
esac
done
case "$ans" in
") ans="$xxxm";;
esac
EOSC

```

Found in path(s):

```

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/Myread.U

```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_sigsetjmp.U,v 3.0.1.1 1997/02/28 15:44:33 ram Exp \$

?RCS:

?RCS: Copyright (c) 1996,1998 Andy Dougherty

?RCS: Copyright (c) 1991-1993, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 3.0.

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

```

?RCS: $Log: d_sigsetjmp.U,v $
?RCS: Revision 3.0.1.1 1997/02/28 15:44:33 ram
?RCS: patch61: created
?RCS:
?MAKE:d_sigsetjmp: Compile Setvar cat rm_try run i_stdlib
?MAKE: -pick add $@ %<
?S:d_sigsetjmp:
?S: This variable conditionally defines the HAS_SIGSETJMP symbol,
?S: which
    indicates that the sigsetjmp() routine is available to
?S: call setjmp() and optionally save the process's signal mask.
?S:.
?C:HAS_SIGSETJMP:
?C: This variable indicates to the C program that the sigsetjmp()
?C: routine is available to save the calling process's registers
?C: and stack environment for later use by siglongjmp(), and
?C: to optionally save the process's signal mask. See
?C: Sigjmp_buf, Sigsetjmp, and Siglongjmp.
?C:.
?C:Sigjmp_buf:
?C: This is the buffer type to be used with Sigsetjmp and Siglongjmp.
?C:.
?C:Sigsetjmp:
?C: This macro is used in the same way as sigsetjmp(), but will invoke
?C: traditional setjmp() if sigsetjmp isn't available.
?C: See HAS_SIGSETJMP.
?C:.
?C:Siglongjmp:
?C: This macro is used in the same way as siglongjmp(), but will invoke
?C: traditional longjmp() if siglongjmp isn't available.
?C: See HAS_SIGSETJMP.
?C:.
?H:%<:#$d_sigsetjmp HAS_SIGSETJMP /**/
?H:%<:#ifdef HAS_SIGSETJMP
?H:%<:#define Sigjmp_buf sigjmp_buf
?H:%<:#define Sigsetjmp(buf,save_mask)
    sigsetjmp((buf),(save_mask))
?H:%<:#define Siglongjmp(buf,retval) siglongjmp((buf),(retval))
?H:%<:#else
?H:%<:#define Sigjmp_buf jmp_buf
?H:%<:#define Sigsetjmp(buf,save_mask) setjmp((buf))
?H:%<:#define Siglongjmp(buf,retval) longjmp((buf),(retval))
?H:%<:#endif
?H:.
?W:%<:Sigjmp_buf Sigsetjmp Siglongjmp
?F:!try
?LINT:set d_sigsetjmp
: see if sigsetjmp exists

```

?X: We can't check for these symbols with Inlibc because sigsetjmp

?X: is (sometimes? always?) a macro under GCC

echo " "

case "\$d_sigsetjmp" in

")

\$cat >try.c <<EOP

#include <setjmp.h>

#\$i_stdlib I_STDLIB

#ifdef I_STDLIB

#include <stdlib.h>

#endif

sigjmp_buf env;

int set = 1;

int main()

{

if (sigsetjmp(env,1))

exit(set);

set = 0;

siglongjmp(env, 1);

exit(1);

}

EOP

set try

if eval \$compile; then

if \$run ./try >/dev/null 2>&1; then

echo "POSIX sigsetjmp found." >&4

val="\$define"

else

\$cat >&4 <<EOM

Uh-Oh! You have POSIX sigsetjmp and siglongjmp, but they do not work properly!!

I'll

ignore them.

EOM

val="\$undef"

fi

else

echo "sigsetjmp not found." >&4

val="\$undef"

fi

::

*) val="\$d_sigsetjmp"

case "\$d_sigsetjmp" in

\$define) echo "POSIX sigsetjmp found." >&4;;

\$undef) echo "sigsetjmp not found." >&4;;

esac

::

esac

set d_sigsetjmp

```
eval $setvar
$rm_try
```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/compline/d_sigsetjmp.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: d_strtok.U 1 2006-08-24 12:32:52Z rmanfredi $
```

```
?RCS:
```

```
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
```

```
?RCS:
```

```
?RCS: You may redistribute only under the terms of the Artistic Licence,
```

```
?RCS: as specified in the README file that comes with the distribution.
```

```
?RCS: You may reuse parts of this distribution only within the terms of
```

```
?RCS: that same Artistic Licence; a copy of which may be found at the root
```

```
?RCS: of the source tree for dist 4.0.
```

```
?RCS:
```

```
?RCS: $Log: d_strtok.U,v $
```

```
?RCS: Revision 3.0 1993/08/18 12:07:38 ram
```

```
?RCS: Baseline for dist 3.0 netwide release.
```

```
?RCS:
```

```
?X:
```

```
?X: The strtok routine now appears to be a standard one, but it was
```

```
?X: missing in early BSD systems.
```

```
?X:
```

```
?MAKE:d_strtok: Inlibc
```

```
?MAKE: -pick add $@ %<
```

```
?S:d_strtok:
```

```
?S: This variable conditionally defines HAS_STRTOK if strtok() is
```

```
?S: available to scan strings for tokens.
```

```
?S:.
```

```
?C:HAS_STRTOK (STRTOK):
```

```
?C: This symbol, if defined, indicates
```

```
that the strtok routine is
```

```
?C: available to scan strings for tokens.
```

```
?C:.
```

```
?H:#$d_strtok HAS_STRTOK /**/
```

```
?H:.
```

```
?LINT:set d_strtok
```

```
: see if strtok exists
```

```
set strtok d_strtok
```

```
eval $inlibc
```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/d_strtok.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: Inhdr.U 1 2006-08-24 12:32:52Z rmanfredi $
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: $Log: Inhdr.U,v $
?RCS: Revision 3.0.1.2 1995/05/12 12:01:31 ram
?RCS: patch54: deleted tabs that caused some /bin/sh to core dump (ADO)
?RCS:
?RCS: Revision 3.0.1.1 1994/10/29 15:55:01 ram
?RCS: patch36: call ./whoa explicitly instead of relying on PATH
?RCS:
?RCS: Revision 3.0 1993/08/18 12:05:01 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?X:
?X: This unit checks wether a set of header files exists or not.
?X: If the first header is not
?X: found, the function tries to locate
?X: the next header, and so on, until one is found or there is no
?X: more header in the list.
?X:
?X: To use it, say:
?X: set header i_header [ header2 i_header2 ... ]
?X: eval $inhdr
?X:
?MAKE:Inhdr: test Findhdr Whoa
?MAKE:-pick add $@ %<
?LINT:define inhdr
?V:inhdr
?S:inhdr:
?S: This shell variable is used internally by Configure to check
?S: wether a set of headers exist or not. A typical use is:
?S: set header i_header [ header2 i_header2 ... ]
?S: eval $inhdr
?S: That will print a message, saying wether header was found or
?S: not and set i_header* accordingly. If the first header is not
?S: found, we try the next one, until the list is empty or one is found.
?S:.
?T:xxx xxf var td xxnf tu yyy instead was cont
: define an alternate in-header-list? function
```

```

inhdr='echo " "; td=$define; tu=$undef; yyy=$@;
cont=true; xxf="echo \"<\\$1> found.\" >&4";
case $# in 2) xxnf="echo \"<\\$1> NOT found.\" >&4";;
*) xxnf="echo \"<\\$1> NOT found, ...\" >&4";;
esac;
case
  $# in 4) instead=instead;; *) instead="at last";; esac;
while $test "$cont"; do
  xxx=`./findhdr $1`
  var=$2; eval "was=\\$2";
  if $test "$xxx" && $test -r "$xxx";
  then eval $xxf;
  ?X: Next line shifted left 1 tabstop to avoid sh core dump on MachTen 2.1.1.
  eval "case \"\\$var\" in $undef) . /whoa; esac"; eval "$var=\\$td";
  cont="";
  else eval $xxnf;
  ?X: Likewise, the next line has been shifted left 1 tabstop -- ADO, 08/03/95
  eval "case \"\\$var\" in $define) . /whoa; esac"; eval "$var=\\$tu"; fi;
  set $yyy; shift; shift; yyy=$@;
  case $# in 0) cont="";;
  2) xxf="echo \"but I found <\\$1> $instead.\" >&4";
    xxnf="echo \"and I did not find <\\$1> either.\" >&4";;
  *) xxf="echo \"but I found <\\$1> instead.\" >&4";
    xxnf="echo \"there is no <\\$1>, ...\" >&4";;
  esac;
done;
?X: Remaining values are set to 'undef'
while $test "$yyy";
do set $yyy; var=$2; eval "was=\\$2";
  eval "case \"\\$var\" in $define) . /whoa; esac"; eval "$var=\\$tu";
  set $yyy; shift; shift; yyy=$@;
done'

```

Found

in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/Inhdr.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: siteprefix.U,v 1.1 1999/07/08 18:32:57 doughera Exp doughera \$

?RCS:

?RCS: Copyright (c) 1999 Andy Dougherty

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 3.0.

```

?RCS:
?RCS: $Log: siteprefix.U,v $
?RCS: Revision 1.1 1999/07/08 18:32:57 doughera
?RCS: Initial revision
?RCS:
?MAKE:siteprefix siteprefixexp +oldsiteprefix: Getfile Loc Oldconfig cat package prefix
?MAKE: -pick add $@ %<
?S:siteprefix:
?S: This variable holds the full absolute path of the directory below
?S: which the user will install add-on packages.
?S: See INSTALL for usage and examples.
?S:.
?S:siteprefixexp:
?S: This variable holds the full absolute path of the
directory below
?S: which the user will install add-on packages. Derived from siteprefix.
?S:.
?S:oldsiteprefix:
?S: This variable is set non-null if the siteprefix was previously defined
?S: and gets set to a new value. Used internally by Configure only.
?S:.
: Set the siteprefix variables
$cat <<EOM

```

After \$package is installed, you may wish to install various add-on modules and utilities. Typically, these add-ons will be installed under \$prefix with the rest of this package. However, you may wish to install such add-ons elsewhere under a different prefix.

If you do not wish to put everything under a single prefix, that's ok. You will be prompted for the individual locations; this siteprefix is only used to suggest the defaults.

The default should be fine for most people.

```

EOM
fn=d~+
rp='Installation prefix to use for add-on modules and utilities?'
: XXX Here might be another good place for an installstyle setting.
case "$siteprefix" in
") dflt=$prefix ;;
*) dflt=$siteprefix
;;
esac
../getfile
: XXX Prefixit unit does not yet support siteprefix and vendorprefix
oldsiteprefix="

```

```

case "$siteprefix" in
") ;;
*) case "$ans" in
"$prefix") ;;
*) oldsiteprefix="$prefix";;
esac
;;
esac
siteprefix="$ans"
siteprefixexp="$ansexp"

```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/installdirs/siteprefix.U
```

No license file was found, but licenses were detected in source scan.

```

?RCS: $Id: d_flock.U 1 2006-08-24 12:32:52Z rmanfredi $
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: $Log: d_flock.U,v $
?RCS: Revision 3.0 1993/08/18 12:06:05 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:d_flock: Inlibc
?MAKE: -pick add $@ %<
?S:d_flock:
?S: This variable conditionally defines HAS_FLOCK if flock() is
?S: available to do file locking.
?S:.
?C:HAS_FLOCK (FLOCK):
?C: This symbol, if defined, indicates that the flock routine is
?C: available to do file locking.
?C:.
?H:#$d_flock HAS_FLOCK /**/
?H:.
?LINT:set d_flock
: see
if flock exists
set flock d_flock
eval $inlibc

```

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/d_flock.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: sitebin.U,v \$

?RCS:

?RCS: Copyright (c) 1999 Andy Dougherty

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 3.0.

?RCS:

?RCS: \$Log: sitebin.U,v \$

?RCS:

?MAKE:sitebin sitebinexp installsitebin : Getfile Oldconfig \
Setprefixvar siteprefix

Setprefixvar siteprefix

?MAKE: -pick add \$@ %<

?Y:TOP

?D:sitebin="

?S:sitebin:

?S: This variable holds the name of the directory in which the user wants

?S: to put add-on publicly executable files for the package in question. It

?S: is most often a local directory such as /usr/local/bin. Programs using

?S: this variable must be prepared to deal with ~name substitution.

?S: The standard distribution will put nothing

in this directory.

?S: After perl has been installed, users may install their own local

?S: executables in this directory with

?S: MakeMaker Makefile.PL

?S: or equivalent. See INSTALL for details.

?S:.

?D:sitebinexp="

?S:sitebinexp:

?S: This is the same as the sitebin variable, but is filename expanded at

?S: configuration time, for use in your makefiles.

?S:.

?D:installsitebin="

?S:installsitebin:

?S: This variable is usually the same as sitebinexp, unless you are on

?S: a system running AFS, in which case they may differ slightly. You

?S: should always use this variable within your makefiles for portability.

?S:.

?LINT:change prefixvar

?LINT:set installsitebin

?LINT:set sitebin

```
?LINT:set sitebinexp
: determine where add-on public executables go
case "$sitebin" in
") dflt=$siteprefix/bin ;;
*) dflt=$sitebin ;;
esac
fn=d~
rp='Pathname where the add-on public executables should be installed?'
./getfile
prefixvar=sitebin
./setprefixvar
```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/installdirs/sitebin.U
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 2003 Jarkko Hietaniemi

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?MAKE:d_aintl: Inlibc

?MAKE: -pick add \$@ %<

?S:d_aintl:

?S: This variable conditionally defines the HAS_AINTL symbol, which

?S: indicates to the C program that the aintl() routine is available.

?S: If copysignl is also present we can emulate modfl.

?S:.

?C:HAS_AINTL:

?C: This symbol, if defined, indicates that the aintl routine is

?C: available. If copysignl is also present we can emulate modfl.

?C:.

?H:#\$d_aintl HAS_AINTL /**/

?H:.

?LINT:set d_aintl

: see if aintl exists

set aintl d_aintl

eval \$inlibc

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_aintl.U
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:
?RCS: Copyright (c) 1999 Jarkko Hietaniemi
?RCS:
?RCS: You may distribute under the terms of either the GNU General Public
?RCS: License or the Artistic License, as specified in the README file.
?RCS:
?MAKE:d_statfs: Inlibc
?MAKE: -pick add \$@ %<
?S:d_statfs:
?S: This variable conditionally defines the HAS_STATFS symbol, which
?S: indicates to the C program that the statfs() routine is available.
?S:.
?C:HAS_STATFS:
?C: This symbol, if defined, indicates that the statfs routine is
?C: available to stat filesystems by filenames.
?C:.
?H:#\$d_statfs HAS_STATFS /**/
?H:.
?LINT:set d_statfs
: see if statfs exists
set statfs d_statfs
eval \$inlibc

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_statfs.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: Extractall.U 1 2006-08-24 12:32:52Z rmanfredi \$
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: \$Log: Extractall.U,v \$
?RCS: Revision 3.0.1.1 1997/02/28 15:00:43 ram
?RCS: patch61: created
?RCS:
?X:
?X: If extraction has been requested, load the configuration file, perform
?X: the extraction and exit.
?X:
?X: This unit was originally a part of Options.U. It had to be removed from
?X: it to prevent a dependency cycle: Extract -> src -> Options -> Extract

?X: The Begin.U unit now requires us before beginning to do anything

?X: interesting, to ensure proper semantics. -- RAM, 15/03/96

?X:

?MAKE:Extractall: Extract Options

?MAKE: -pick wipe \$@ %<

: extract files and exit if asked to do so

```

case "$extractsh" in
true)
?X: Undo the forced silent=true when -S was supplied, by probing realsilent
?X: which was set iff -s was also given. See Options.U for details.
case "$realsilent" in
true) ;;
*) exec 1>&4;;
esac
case "$config_sh" in
") config_sh='config.sh';;
esac
echo " "
echo "Fetching answers from $config_sh..."
cd ..
. $config_sh
?X: extract has to be run from the top directory, not within UU.
. UU/optdef.sh
echo " "
?X: extract has to be run from the top directory, not within UU.
. UU/extract
rm -rf UU
echo "Extraction done."
exit 0
;;
esac

```

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/modified/Extractall.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: inc_version_list.U,v \$

?RCS:

?RCS: Copyright (c) 2000 Andy Dougherty

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 3.0.

?RCS:

```

?RCS: $Log: inc_version_list.U,v $
?RCS:
?MAKE:inc_version_list inc_version_list_init d_inc_version_list: cat sed \
  Getfile perl5 version api_versionstring rm Myread archname \
  prefix sitelib_stem exe_ext
?MAKE: -pick add $@ %<
?Y:TOP
?S:inc_version_list:
?S: This variable specifies the list of subdirectories in over
?S: which perl.c:incpush() and lib/lib.pm will automatically
?S: search when adding directories to @INC. The elements in
?S: the list are separated by spaces. This is only useful
?S: if
  you have a perl library directory tree structured like the
?S: default one. See INSTALL for how this works. The versioned
?S: site_perl directory was introduced in 5.005, so that is the
?S: lowest possible value.
?S:
?S: This list includes architecture-dependent directories back to
?S: version $api_versionstring (e.g. 5.5.640) and
?S: architecture-independent directories all the way back to
?S: 5.005.
?S:.
?S:inc_version_list_init:
?S: This variable holds the same list as inc_version_list, but
?S: each item is enclosed in double quotes and separated by commas,
?S: suitable for use in the PERL_INC_VERSION_LIST initialization.
?S:.
?S:d_inc_version_list:
?S: This variable conditionally defines PERL_INC_VERSION_LIST.
?S: It is set to undef when PERL_INC_VERSION_LIST is empty.
?S:.
?C:PERL_INC_VERSION_LIST:
?C: This variable specifies the list of subdirectories in over
?C: which perl.c:incpush() and lib/lib.pm will automatically
?C: search when adding directories to @INC, in a format
  suitable
?C: for a C initialization string. See the inc_version_list entry
?C: in Porting/Glossary for more details.
?C:.
?H:#$d_inc_version_list PERL_INC_VERSION_LIST $inc_version_list_init /**/
?H:.
?T:stem
: Determine list of previous versions to include in @INC
$cat > getverlist <<EOPL
# !$perl5 -w
use File::Basename;
\ $api_versionstring = "$api_versionstring";

```

```

\ $version = "$version";
\ $stem = "$sitelib_stem";
\ $archname = "$archname";
EOPL
$cat >> getverlist <<'EOPL'
# The list found is store twice for each entry: the original name, and
# the binary broken down version as pack "sss", so sorting is easy and
# unambiguous. This will work for all versions that have a maximum of
# three digit groups, separate by '.'s or '_'s. Names are extended with
# ".0.0" to ensure at least three elements for the pack.
# -- H.Merijn Brand (m)'06 23-10-2006

# Can't have leading @ because metaconfig interprets it as a command!
;@inc_version_list=();
# XXX Redo to do opendir/readdir?
if (-d
$stem) {
    chdir($stem);
    ;@candidates = map {
[ $_, pack "sss", split m/[. _]/, "$_.0.0" ] } glob("5.*");
    ;@candidates = sort { $a->[1] cmp $b->[1]} @candidates;
}
else {
    ;@candidates = ();
}

($pversion, $aversion, $vsn5005) = map {
    pack "sss", split m/[. _]/, "$_.0.0" } $version, $api_versionstring, "5.005";
foreach $d (@candidates) {
    if ($d->[1] lt $pversion) {
    if ($d->[1] ge $aversion) {
        unshift(@inc_version_list, grep { -d } $d->[0]."/$archname", $d->[0]);
    }
    elsif ($d->[1] ge $vsn5005) {
        unshift(@inc_version_list, grep { -d } $d->[0]);
    }
    }
    else {
# Skip newer version. I.e. don't look in
# 5.7.0 if we're installing 5.6.1.
    }
}

if (@inc_version_list) {
    print join(' ', @inc_version_list);
}
else {
    # Blank space to preserve value for next Configure run.

```

```

    print " ";
}
EOPL
chmod +x getverlist
case "$inc_version_list" in
") if test -x "$perl5$exe_ext"; then
    dflt=`$perl5 getverlist`
else
    dflt='none'
fi
;;
$undef) dflt='none'
;;
?X:  Configure -Dinc_version_list='5.6.0/$archname 5.6.0' ...
*) eval dflt=\"\$inc_version_list\" ;;
esac
case "$dflt" in
'| ') dflt=none ;;
esac
case "$dflt" in
5.005) dflt=none ;;
esac
$cat <<EOM

```

In order to ease the process of upgrading, this version of perl can be configured to use modules built and installed with earlier versions of perl that were installed under \$prefix. Specify here the list of earlier versions that this version of perl should check. If Configure detected no earlier versions of perl installed under \$prefix, then the list will be empty. Answer 'none' to tell perl to not search earlier versions.

The default should almost always be sensible, so if you're not sure, just accept the default.

EOM

```

rp='List of earlier versions to include in @INC?'
./myread
case "$ans" in
[Nn]one|'| '$undef) inc_version_list=' ' ;;
*) inc_version_list="$ans" ;;
esac
case "$inc_version_list" in
'| ')
    inc_version_list_init='0'
    d_inc_version_list="$undef"
;;
*) inc_version_list_init=`echo

```

```
$inc_version_list |
$sed -e 's/^\//' -e 's/ /","/g' -e 's/$/"0/'
d_inc_version_list="$define"
;;
esac
$rm -f getverlist
```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/installdirs/inc_version_list.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: d_getprior.U 1 2006-08-24 12:32:52Z rmanfredi $
```

```
?RCS:
```

```
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
```

```
?RCS:
```

```
?RCS: You may redistribute only under the terms of the Artistic Licence,
```

```
?RCS: as specified in the README file that comes with the distribution.
```

```
?RCS: You may reuse parts of this distribution only within the terms of
```

```
?RCS: that same Artistic Licence; a copy of which may be found at the root
```

```
?RCS: of the source tree for dist 4.0.
```

```
?RCS:
```

```
?RCS: $Log: d_getprior.U,v $
```

```
?RCS: Revision 3.0 1993/08/18 12:06:16 ram
```

```
?RCS: Baseline for dist 3.0 netwide release.
```

```
?RCS:
```

```
?MAKE:d_getprior: Inlibc
```

```
?MAKE: -pick add $@ %<
```

```
?S:d_getprior:
```

```
?S: This variable conditionally defines HAS_GETPRIORITY if getpriority()
```

```
?S: is available to get a process's priority.
```

```
?S:.
```

```
?C:HAS_GETPRIORITY (GETPRIORITY):
```

```
?C: This symbol, if defined, indicates that the getpriority routine is
```

```
?C: available to get a process's priority.
```

```
?C:.
```

```
?H:#$d_getprior
```

```
HAS_GETPRIORITY /**/
```

```
?H:.
```

```
: see if getpriority exists
```

```
?LINT:set d_getprior
```

```
set getpriority d_getprior
```

```
eval $inlibc
```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/d_getprior.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: d_perlio.U,v $
?RCS:
?RCS: Copyright (c) 1998 Andy Dougherty
?RCS:
?RCS: You may distribute under the terms of either the GNU General Public
?RCS: License or the Artistic License, as specified in the README file.
?RCS:
?RCS: $Log: d_perlio.U,v $
?RCS:
?MAKE:useperlio: Myread Oldconfig Setvar
?MAKE: -pick add $@ %<
?Y:TOP
?S:useperlio:
?S: This variable conditionally defines the USE_PERLIO symbol,
?S: and indicates that the PerlIO abstraction should be
?S: used throughout.
?S:.
?C:USE_PERLIO:
?C: This symbol, if defined, indicates that the PerlIO abstraction should
?C: be used throughout. If not defined, stdio should be
?C: used in a fully backward compatible manner.
?C:.
?H:%<:#ifndef USE_PERLIO
?H:%<:#$useperlio USE_PERLIO /**/
?H:%<:#endif
?H:.
: Check if we want perlio
useperlio="$define"
```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/perl/useperlio.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: d_nice.U 1 2006-08-24 12:32:52Z rmanfredi $
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: Original Author: Andy Dougherty <doughera@lafcol.lafayette.edu>
?RCS:
```

```

?RCS: $Log: d_nice.U,v $
?RCS: Revision 3.0.1.1 1994/08/29 16:09:48 ram
?RCS: patch32: created by ADO
?RCS:
?MAKE:d_nice: Inlibc
?MAKE: -pick add $@ %<
?S:d_nice:
?S: This variable conditionally defines the HAS_NICE symbol, which
?S: indicates to the C program that the nice() routine is available.
?S:.
?C:HAS_NICE :
?C: This symbol, if defined, indicates that the nice routine is
?C: available.
?C:.
?H:#$d_nice
HAS_NICE /**/
?H:.
?LINT:set d_nice
: see if nice exists
set nice d_nice
eval $inlibc

```

Found in path(s):

```

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/d_nice.U

```

No license file was found, but licenses were detected in source scan.

```

?RCS: $Id: d_endhostent_r.U,v 0RCS:
?RCS: Copyright (c) 2002,2003 Jarkko Hietaniemi
?RCS:
?RCS: You may distribute under the terms of either the GNU General Public
?RCS: License or the Artistic License, as specified in the README file.
?RCS:
?RCS: Generated by the reentr.pl from the Perl 5.8 distribution.
?RCS:
?MAKE:d_endhostent_r endhostent_r_proto: Inlibc Protochk Hasproto i_systypes \
  usethreads i_netdb extern_C
?MAKE: -pick add $@ %<
?S:d_endhostent_r:
?S: This variable conditionally defines the HAS_ENDHOSTENT_R symbol,
?S: which indicates to the C program that the endhostent_r()
?S: routine is available.
?S:.
?S:endhostent_r_proto:
?S: This variable encodes the prototype of endhostent_r.
?S: It is zero if d_endhostent_r is undef, and one of the
?S: REENTRANT_PROTO_T_ABC macros of reentr.h if d_endhostent_r
?S: is defined.

```

```

?S:.
?C:HAS_ENDHOSTENT_R:
?C: This symbol, if defined, indicates that the endhostent_r routine
?C: is
    available to endhostent re-entrantly.
?C:.
?C:ENDHOSTENT_R_PROTO:
?C: This symbol encodes the prototype of endhostent_r.
?C: It is zero if d_endhostent_r is undef, and one of the
?C: REENTRANT_PROTO_T_ABC macros of reentr.h if d_endhostent_r
?C: is defined.
?C:.
?H:#$d_endhostent_r HAS_ENDHOSTENT_R  /**/
?H:#define ENDHOSTENT_R_PROTO $endhostent_r_proto  /**/
?H:.
?T:try hdrs d_endhostent_r_proto
: see if endhostent_r exists
set endhostent_r d_endhostent_r
eval $inlibc
case "$d_endhostent_r" in
"$define")
    hdrs="$i_systypes sys/types.h define stdio.h $i_netdb netdb.h"
    case "$d_endhostent_r_proto:$usethreads" in
":define") d_endhostent_r_proto=define
        set d_endhostent_r_proto endhostent_r $hdrs
        eval $hasproto ;;
*) ;;
esac
case "$d_endhostent_r_proto" in
define)
    case "$endhostent_r_proto" in
"|0) try='int endhostent_r(struct hostent_data*);'
./prochck "$extern_C $try" $hdrs && endhostent_r_proto=I_D ;;
esac
case "$endhostent_r_proto" in
"|0) try='void
endhostent_r(struct hostent_data*);'
./prochck "$extern_C $try" $hdrs && endhostent_r_proto=V_D ;;
esac
case "$endhostent_r_proto" in
"|0) d_endhostent_r=undef
        endhostent_r_proto=0
        echo "Disabling endhostent_r, cannot determine prototype." >&4 ;;
*) case "$endhostent_r_proto" in
REENTRANT_PROTO*) ;;
*) endhostent_r_proto="REENTRANT_PROTO_$endhostent_r_proto" ;;
esac
echo "Prototype: $try" ;;

```

```

esac
;;
*) case "$usethreads" in
define) echo "endhostent_r has no prototype, not using it." >&4 ;;
esac
d_endhostent_r=undef
endhostent_r_proto=0
;;
esac
;;
*) endhostent_r_proto=0
;;
esac

```

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/threads/d_endhostent_r.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: sitearch.U,v 3.1 1999/07/08 18:32:29 doughera Exp doughera \$

?RCS:

?RCS: Copyright (c) 1996-1998, Andy Dougherty

?RCS: Copyright (c) 1991-1993, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 3.0.

?RCS:

?RCS: \$Log: sitearch.U,v \$

?RCS: Revision 3.1 1999/07/08 18:32:29 doughera

?RCS: Updated for perl5.005_5x

?RCS:

?RCS: Revision 3.0.1.1 1997/02/28 16:21:30 ram

?RCS: patch61: created

?RCS:

?MAKE:sitearch sitearchexp installsitearch d_sitearch: cat sed Getfile \

Oldconfig Setprefixvar Prefixit test archname sitelib

?MAKE: -pick add \$@ %<

?Y:TOP

?D:sitearch="

?S:sitearch:

?S: This variable contains the eventual

value of the SITEARCH symbol,

?S: which is the name of the private library for this package. It may

?S: have a ~ on the front. It is up to the makefile to eventually create

?S: this directory while performing installation (with ~ substitution).

?S: The standard distribution will put nothing in this directory.

?S: After perl has been installed, users may install their own local

?S: architecture-dependent modules in this directory with

?S: MakeMaker Makefile.PL

?S: or equivalent. See INSTALL for details.

?S:.

?D:sitearchexp="

?S:sitearchexp:

?S: This variable is the ~name expanded version of sitearch, so that you

?S: may use it directly in Makefiles or shell scripts.

?S:.

?D:installsitearch="

?S:installsitearch:

?S: This variable is really the same as sitearchexp but may differ on

?S: those systems using AFS. For extra portability, only this variable

?S: should be used in makefiles.

?S:.

?D:d_sitearch="

?S:d_sitearch:

?S: This variable conditionally defines SITEARCH to hold the

pathname

?S: of architecture-dependent library files for \$package. If

?S: \$sitearch is the same as \$archlib, then this is set to undef.

?S:.

?C:SITEARCH:

?C: This symbol contains the name of the private library for this package.

?C: The library is private in the sense that it needn't be in anyone's

?C: execution path, but it should be accessible by the world. The program

?C: should be prepared to do ~ expansion.

?C: The standard distribution will put nothing in this directory.

?C: After perl has been installed, users may install their own local

?C: architecture-dependent modules in this directory with

?C: MakeMaker Makefile.PL

?C: or equivalent. See INSTALL for details.

?C:.

?C:SITEARCH_EXP:

?C: This symbol contains the ~name expanded version of SITEARCH, to be used

?C: in programs that are not prepared to deal with ~ expansion at run-time.

?C:.

?H:#\$d_sitearch SITEARCH "\$sitearch" /**/

?H:#\$d_sitearch SITEARCH_EXP "\$sitearchexp" /**/

?H:.

?LINT:change prefixvar

?LINT:set installsitearch

?LINT:set

sitearch

?LINT:set sitearchexp

: determine where site specific architecture-dependent libraries go.

```

: sitelib default is /usr/local/lib/perl5/site_perl/$version
: sitearch default is /usr/local/lib/perl5/site_perl/$version/$archname
: sitelib may have an optional trailing /share.
case "$sitearch" in
*) dflt=`echo $sitelib | $sed 's,/share$,,'`
   dflt="$dflt/$archname"
;;
*) dflt="$sitearch"
;;
esac
set sitearch sitearch none
eval $prefixit
$cat <<EOM

```

The installation process will also create a directory for architecture-dependent site-specific extensions and modules.

```

EOM
fn=d~+
rp='Pathname for the site-specific architecture-dependent library files?'
./getfile
prefixvar=sitearch
./setprefixvar
if $test X"$sitearch" = X"$sitelib"; then
  d_sitearch="$undef"
else
  d_sitearch="$define"
fi

```

Found in path(s):

```

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/installdirs/sitearch.U

```

No license file was found, but licenses were detected in source scan.

```

?RCS: $Id: d_psignal.U 1 2006-08-24 12:32:52Z rmanfredi $
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: $Log: d_psignal.U,v $
?RCS: Revision 3.0 1993/08/18 12:06:49 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:

```

?MAKE:d_psignal: Inlibc
?MAKE: -pick add \$@ %<
?S:d_psignal:
?S: This variable conditionally defines the HAS_P SIGNAL symbol, which
?S: indicates that the psignal() routine exists. The psignal() routine
?S: prints a description of a signal on the standard error output.
?S:.
?C:HAS_P SIGNAL (PSIGNAL):
?C: This symbol, if defined, indicates
that the psignal() routine exists.
?C:.
?H:#\$d_psignal HAS_P SIGNAL /**/
?H:.
?LINT:set d_psignal
: see if psignal exists
set psignal d_psignal
eval \$inlibc

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/d_psignal.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_mktime.U 1 2006-08-24 12:32:52Z rmanfredi \$
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: Original Author: Andy Dougherty <doughera@lafcol.lafayette.edu>
?RCS:
?RCS: \$Log: d_mktime.U,v \$
?RCS: Revision 3.0.1.1 1994/08/29 16:09:44 ram
?RCS: patch32: created by ADO
?RCS:
?MAKE:d_mktime: Inlibc
?MAKE: -pick add \$@ %<
?S:d_mktime:
?S: This variable conditionally defines the HAS_MKTIME symbol, which
?S: indicates to the C program that the mktime() routine is available.
?S:.
?C:HAS_MKTIME :
?C: This symbol, if defined, indicates that the mktime routine

is
?C: available.
?C:.
?H:#\$d_mktime HAS_MKTIME /**/
?H:.
?LINT:set d_mktime
: see if mktime exists
set mktime d_mktime
eval \$inlibc

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/d_mktime.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_endgrent_r.U,v 0RCS:
?RCS: Copyright (c) 2002,2003 Jarkko Hietaniemi
?RCS:
?RCS: You may distribute under the terms of either the GNU General Public
?RCS: License or the Artistic License, as specified in the README file.
?RCS:
?RCS: Generated by the reentr.pl from the Perl 5.8 distribution.
?RCS:
?MAKE:d_endgrent_r endgrent_r_proto: Inlibc Protochk Hasproto i_systypes \
usethreads i_grp extern_C
?MAKE: -pick add \$@ %<
?S:d_endgrent_r:
?S: This variable conditionally defines the HAS_ENDGRENT_R symbol,
?S: which indicates to the C program that the endgrent_r()
?S: routine is available.
?S:.
?S:endgrent_r_proto:
?S: This variable encodes the prototype of endgrent_r.
?S: It is zero if d_endgrent_r is undef, and one of the
?S: REENTRANT_PROTO_T_ABC macros of reentr.h if d_endgrent_r
?S: is defined.
?S:.
?C:HAS_ENDGRENT_R:
?C: This symbol, if defined, indicates that the endgrent_r routine
?C: is available to
endgrent re-entrantly.
?C:.
?C:ENDGRENT_R_PROTO:
?C: This symbol encodes the prototype of endgrent_r.
?C: It is zero if d_endgrent_r is undef, and one of the
?C: REENTRANT_PROTO_T_ABC macros of reentr.h if d_endgrent_r
?C: is defined.
?C:.

```

?H:#$d_endgrent_r HAS_ENDGRENT_R  /**/
?H:#define ENDGRENT_R_PROTO $endgrent_r_proto  /**/
?H:.
?T:try hdrs d_endgrent_r_proto
: see if endgrent_r exists
set endgrent_r d_endgrent_r
eval $inlibc
case "$d_endgrent_r" in
"$define")
hdrs="$i_systypes sys/types.h define stdio.h $i_grp grp.h"
case "$d_endgrent_r_proto:$susetheads" in
":define") d_endgrent_r_proto=define
set d_endgrent_r_proto endgrent_r $hdrs
eval $hasproto ;;
*) ;;
esac
case "$d_endgrent_r_proto" in
define)
case "$endgrent_r_proto" in
"|0) try='int endgrent_r(FILE**);'
./prochck "$sextern_C $try" $hdrs && endgrent_r_proto=I_H ;;
esac
case "$endgrent_r_proto" in
"|0) try='void endgrent_r(FILE**);'
./prochck "$sextern_C $try" $hdrs && endgrent_r_proto=V_H ;;
esac
case
"$endgrent_r_proto" in
"|0) d_endgrent_r=undef
endgrent_r_proto=0
echo "Disabling endgrent_r, cannot determine prototype." >&4 ;;
* ) case "$endgrent_r_proto" in
REENTRANT_PROTO*) ;;
*) endgrent_r_proto="REENTRANT_PROTO_$endgrent_r_proto" ;;
esac
echo "Prototype: $try" ;;
esac
;;
*) case "$susetheads" in
define) echo "endgrent_r has no prototype, not using it." >&4 ;;
esac
d_endgrent_r=undef
endgrent_r_proto=0
;;
esac
;;
*) endgrent_r_proto=0
;;

```

esac

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/threads/d_endgrent_r.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: i_nlist.U,v \$

?RCS:

?RCS: Copyright (c) 1998 Jarkko Hietaniemi

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?MAKE:i_nlist: Inhdr Hasfield

?MAKE: -pick add \$@ %<

?S:i_nlist:

?S: This variable conditionally defines the I_NLIST symbol, and indicates

?S: whether a C program should include <nlist.h>.

?S:.

?C:I_NLIST:

?C: This symbol, if defined, indicates that <nlist.h> exists and

?C: should be included.

?C:.

?H:#\$i_nlist I_NLIST /**/

?H:.

?LINT:set i_nlist

: see if this is a nlist.h system

set nlist.h i_nlist

eval \$inhdr

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/i_nlist.U

No license file was found, but licenses were detected in source scan.

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?MAKE:d_fdim: Inlibc

?MAKE: -pick add \$@ %<

?S:d_fdim:

?S: This variable conditionally defines the HAS_FDIM symbol, which

?S: indicates to the C program that the fdim() routine is available.

?S:.

?C:HAS_FDIM:

?C: This symbol, if defined, indicates that the fdim routine is

?C: available to do the positive difference function.

?C:
?H:#\$d_fdim HAS_FDIM /**/
?H:
?LINT:set d_fdim
: see if fdim exists
set fdim d_fdim
eval \$inlibc

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_fdim.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: \$Log: Init.U,v \$
?RCS: Revision 3.0.1.1 1994/10/31 09:45:59 ram
?RCS: patch44: removed Options from MAKE to prevent Init overrides
?RCS: patch44: option processing now done after Myinit thanks to new Begin.U
?RCS: patch44: moved "Beginning of configuration questions" to Begin.U
?RCS: patch44: moved signal trapping instruction to Begin.U as well
?RCS:
?RCS: Revision 3.0 1993/08/18 12:05:02 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?X:
?X: This file initializes certain default variables
used by Configure. They
?X: may be overridden or added to by definitions in Myinit.U.
?X:
?MAKE:Init eunicefix _exe: Null
?MAKE: -pick add \$@ %<
?MAKE: -pick weed \$@ ./Init
?S:eunicefix:
?S: When running under Eunice this variable contains a command which will
?S: convert a shell script to the proper form of text file for it to be
?S: executable by the shell. On other systems it is a no-op.
?S:.
?S:_exe (exe_ext):
?S: This variable defines the extension used for executable files.

?S: For unix it is empty. Other possible values include '.exe'.

?S: DJGPP, Cygwin and OS/2 use '.exe'. Stratus VOS uses '.pm'.

?S: On operating systems which do not require a specific extension

?S: for executable files, this variable is empty.

?S:.

?V:define undef smallmach:rmlist

?X:

?X: Throughout the units, one may make use of \$define and \$undef to reference

?X: a defined symbol or an undefined one. There is no need to add them in

?X: the dependency line since this unit makes them visible via ?V:, and

?X:

everyone inherits from those symbols since by convention Init.U is the

?X: root dependency.

?X:

?T: DJGPP

: Initialize wide constants

define='define'

undef='undef'

smallmach='pdp11 i8086 z8000 i80286 iAPX286'

rmlist=""

: We must find out about Eunice early

eunicefix=':'

if test -f /etc/unixtovms; then

eunicefix=/etc/unixtovms

fi

if test -f /etc/unixtovms.exe; then

eunicefix=/etc/unixtovms.exe

fi

: Set executable suffix now -- needed before hints available

if test -f "/libs/version.library"; then

: Amiga OS

_exe=""

elif test -f "/system/gnu_library/bin/ar.pm"; then

: Stratus VOS

_exe=".pm"

elif test -n "\$DJGPP"; then

: DOS DJGPP

_exe=".exe"

elif test -d c:/.; then

: OS/2 or cygwin

_exe=".exe"

else

: All other UNIX systems

_exe=""

fi

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/Init.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: libs.U,v 3.0.1.6 1997/02/28 16:09:11 ram Exp \$

?RCS:

?RCS: Copyright (c) 1991-1993, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 3.0.

?RCS:

?RCS: \$Log: libs.U,v \$

?RCS: Revision 3.0.1.6 1997/02/28 16:09:11 ram

?RCS: patch61: replaced .a with \$_a all over the place

?RCS:

?RCS: Revision 3.0.1.5 1995/07/25 14:12:05 ram

?RCS: patch56: now knows about OS/2 platforms

?RCS:

?RCS: Revision 3.0.1.4 1994/10/29 16:24:22 ram

?RCS: patch36: removed old broken thislib/thatlib processing (ADO)

?RCS:

?RCS: Revision 3.0.1.3 1994/06/20 07:05:44 ram

?RCS: patch30: code cleanup with if/elif by ADO and RAM

?RCS: patch30:

undone patch23 for libswanted default setting

?RCS:

?RCS: Revision 3.0.1.2 1994/05/06 15:08:45 ram

?RCS: patch23: now includes ordered default libswanted variable (ADO)

?RCS: patch23: major cleanup for library lookups (ADO)

?RCS:

?RCS: Revision 3.0.1.1 1993/08/25 14:02:31 ram

?RCS: patch6: added default for libs

?RCS:

?RCS: Revision 3.0 1993/08/18 12:09:03 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?MAKE:libs ignore_versioned_solibs libsfound libsfiles libsdirs libspath: \

test cat Myread Oldconfig Loc libpth package xlibpth so _a \

usesocks sed uselongdouble usequadmath

?MAKE: -pick add \$@ %<

?S:libs:

?S: This variable holds the additional libraries we want to use.

?S: It is up to the Makefile to deal with it. The list can be empty.

?S:.

?S:libsfound:
 ?S: This variable holds the full pathnames of the libraries
 ?S: we found and accepted.
 ?S:.

?S:libsfiles:
 ?S: This variable holds the filenames aka basenames of the libraries
 ?S: we found and accepted.
 ?S:.

?S:libsdirs:
 ?S: This
 variable holds the directory names aka dirnames of the libraries
 ?S: we found and accepted, duplicates are removed.
 ?S:.

?S:libspath:
 ?S: This variable holds the directory names probed for libraries.
 ?S:.

?S:ignore_versioned_solibs:
 ?S: This variable should be non-empty if non-versioned shared
 ?S: libraries (libfoo.so.x.y) are to be ignored (because they
 ?S: cannot be linked against).
 ?S:.

?T:xxx yyy thislib thisdir libswanted libstyle
 ?D:libs="

?X:
 ?X: This order is chosen so that libraries -lndir, -ldir, -lucb, -lbsd,
 ?X: -lBSD, -lPW, and -lx only get used if there are unresolved
 ?X: routines at link time. Usually, these are backwards compatibility
 ?X: libraries, and may not be as reliable as the standard c library.
 ?X:
 ?X: The -lsocket -linet -lnsl order has been reported to be necessary
 ?X: for at least one SVR4 implementation.
 ?X: -lc must proceed -lucb or -lbsd for most Solaris applications.
 ?X: -lc_s proceeds -lc so we pick up the shared library version,
 if
 ?X: it is available.
 ?X:
 ?X: The ordering of c, posix, and cposix is a guess and almost
 ?X: certainly wrong on about half of all systems.
 ?X:
 ?X: Set proper libswanted in your private Myinit.U if needed.
 ?X:
 ?X:: default ordered library list
 ?X:libswanted='net socket inet bind nsl nm sdbm gdbm ndbm dbm malloc dl'
 ?X:libswanted="\$libswanted dld sun m c_s c posix cposix ndir dir ucb"
 ?X:libswanted="\$libswanted bsd BSD PW x"
 ?X:
 ?INIT:: default library list
 ?INIT:libswanted="

```

?INIT:: some systems want to use only the non-versioned libso:s
?INIT:ignore_versioned_solibs="
?LINT:extern usecbacktrace
?LINT:extern libscheck
?LINT:extern p
?LINT:use uselongdouble
: Looking for optional libraries
echo " "
echo "Checking for optional libraries..." >&4
case "$libs" in
'|') dflt="";
*) dflt="$libs";;
esac
case "$libswanted" in
') libswanted='c_s';;
esac
?X: libsocks has nasty naming scheme.
?X: This does not work if somebody wants SOCKS 4.
case "$usesocks" in
"$define") libswanted="$libswanted
socks5 socks5_sh" ;;
esac
case "$usecbacktrace" in
"$define") libswanted="$libswanted bfd" ;;
esac
case "$usequadmath" in
"$define") libswanted="$libswanted quadmath" ;;
esac
libsfound="
libsfiles="
libsdirs="
libspath="
for thisdir in $libpth $xlibpth; do
test -d $thisdir && libspath="$libspath $thisdir"
done
for thislib in $libswanted; do
for thisdir in $libspath; do
xxx="
if $test ! -f "$xxx" -a "X$ignore_versioned_solibs" = "X"; then
xxx=`ls $thisdir/lib$thislib.$so.[0-9] 2>/dev/null|sed -n '$p`
$test -f "$xxx" && eval $libscheck
$test -f "$xxx" && libstyle=shared
xxx=`ls $thisdir/lib$thislib.[0-9].$so 2>/dev/null|sed -n '$p`
$test -f "$xxx" && eval $libscheck
$test -f "$xxx" && libstyle=shared
fi
if test ! -f "$xxx"; then
xxx=$thisdir/lib$thislib.$so

```

```

    $test -f "$xxx" && eval $libscheck
$test -f "$xxx" && libstyle=shared
    fi
    if test ! -f "$xxx"; then
xxx=$thisdir/lib$thislib$_a
        $test -f "$xxx"
&& eval $libscheck
$test -f "$xxx" && libstyle=static
    fi
    if test ! -f "$xxx"; then
xxx=$thisdir/$thislib$_a
        $test -f "$xxx" && eval $libscheck
$test -f "$xxx" && libstyle=static
    fi
    if test ! -f "$xxx"; then
xxx=$thisdir/lib${thislib}_s$_a
        $test -f "$xxx" && eval $libscheck
$test -f "$xxx" && libstyle=static
$test -f "$xxx" && thislib=${thislib}_s
    fi
    if test ! -f "$xxx"; then
xxx=$thisdir/Slib$thislib$_a
        $test -f "$xxx" && eval $libscheck
$test -f "$xxx" && libstyle=static
    fi
    if $test -f "$xxx"; then
case "$libstyle" in
shared) echo "Found -l$thislib (shared)." ;;
static) echo "Found -l$thislib." ;;
*)     echo "Found -l$thislib ($libstyle)." ;;
esac
case " $dflt " in
*"-l$thislib "*);;
*) dflt="$dflt -l$thislib"
    libsfound="$libsfound $xxx"
    yyy=`basename $xxx`
    libsfiles="$libsfiles $yyy"
    yyy=`echo $xxx|sed -e
"s%/$yyy\\|%%"`
    case " $libsdirs " in
*" $yyy "*);;
*) libsdirs="$libsdirs $yyy" ;;
esac

;;
esac
break
    fi
done

```

```

if $test ! -f "$xxx"; then
    echo "No -l$thislib."
fi
done
set X $dflt
shift
dflt="$*"
case "$libs" in
") dflt="$dflt";;
*) dflt="$libs";;
esac
case "$dflt" in
'|') dflt='none';;
esac

```

\$cat <<EOM

In order to compile \$package on your machine, a number of libraries are usually needed. Include any other special libraries here as well. Say "none" for none. The default list is almost always right.
EOM

```

echo " "
rp="What libraries to use?"
./myread
case "$ans" in
none) libs=' ';;
*) libs="$ans";;
esac

```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/modified/libs.U
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_endpwent.U,v \$

?RCS:

?RCS: Copyright (c) 1998 Andy Dougherty

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?RCS: \$Log: d_endpwent.U,v \$

?RCS:

?MAKE:d_endpwent: Inlibc

?MAKE: -pick add \$@ %<

?S:d_endpwent:

?S: This variable conditionally defines the HAS_ENDPWENT symbol, which

?S: indicates to the C program that the endpwent() routine is available

?S: for sequential access of the passwd database.

?S:.

?C:HAS_ENDPWENT:

?C: This symbol, if defined, indicates that the getgrent routine is

?C: available for finalizing sequential access of the passwd database.

?C:.

?H:#\$d_endpwent HAS_ENDPWENT /**/

?H:.

?LINT:set d_endpwent

: see if endpwent exists

set endpwent d_endpwent

eval \$inlibc

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/modified/d_endpwent.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: ccflags.U,v 3.0.1.9 1997/02/28 15:27:07 ram Exp \$

?RCS:

?RCS: Copyright (c) 1991-1993, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 3.0.

?RCS:

?RCS: \$Log: ccflags.U,v \$

?RCS: Revision 3.0.1.9 1997/02/28 15:27:07 ram

?RCS: patch61: removed support for NO_PROTOTYPE detection on SCO

?RCS: patch61: new locincpth variable

?RCS: patch61: added info on the "additional ld flags" question

?RCS:

?RCS: Revision 3.0.1.8 1995/07/25 13:48:54 ram

?RCS: patch56: re-arranged compile line to include ldflags before objects

?RCS:

?RCS: Revision 3.0.1.7 1995/05/12 12:08:33 ram

?RCS: patch54: now checks for cc/ccflags/ldflags

coherency

?RCS:

?RCS: Revision 3.0.1.6 1994/10/29 16:07:02 ram

?RCS: patch36: gcc versioning no longer relies on the C compiler's name

?RCS: patch36: simplified check for gcc version checking (ADO)

?RCS:

?RCS: Revision 3.0.1.5 1994/08/29 16:06:35 ram

?RCS: patch32: propagate -posix flag from ccflags to ldflags

?RCS:
 ?RCS: Revision 3.0.1.4 1994/05/06 14:28:45 ram
 ?RCS: patch23: -fpcc-struct-return only needed in gcc 1.x (ADO)
 ?RCS: patch23: cppflags now computed on an option-by-option basis
 ?RCS: patch23: magically added cc flags now only done the first time
 ?RCS:
 ?RCS: Revision 3.0.1.3 1993/09/13 15:58:29 ram
 ?RCS: patch10: explicitly mention -DDEBUG just in case they need it (WAD)
 ?RCS: patch10: removed all the "tans" variable usage (WAD)
 ?RCS:
 ?RCS: Revision 3.0.1.2 1993/08/27 14:39:38 ram
 ?RCS: patch7: added support for OSF/1 machines
 ?RCS:
 ?RCS: Revision 3.0.1.1 1993/08/25 14:00:24 ram
 ?RCS: patch6: added defaults for cppflags, ccflags and ldflags
 ?RCS:
 ?RCS:
 Revision 3.0 1993/08/18 12:05:31 ram
 ?RCS: Baseline for dist 3.0 netwide release.
 ?RCS:
 ?MAKE:ccflags ldflags lkflags cppflags optimize locincpth: test cat osname \
 Myread Guess Options Oldconfig +gccversion mips_type +usrinc \
 package contains rm +cc cppstdin cppminus cprun cpplast libpth \
 libs loclibpth hint usesocks sh run rm_try sysroot
 ?MAKE: -pick add \$@ %<
 ?S:ccflags:
 ?S: This variable contains any additional C compiler flags desired by
 ?S: the user. It is up to the Makefile to use this.
 ?S:.
 ?S:cppflags:
 ?S: This variable holds the flags that will be passed to the C pre-
 ?S: processor. It is up to the Makefile to use it.
 ?S:.
 ?S:optimize:
 ?S: This variable contains any optimizer/debugger flag that should be used.
 ?S: It is up to the Makefile to use it.
 ?S:.
 ?S:ldflags:
 ?S: This variable contains any additional C loader flags desired by
 ?S: the user. It is up to the Makefile to use this.
 ?S:.
 ?S:lkflags:
 ?S: This variable contains any additional C partial linker flags
 desired by
 ?S: the user. It is up to the Makefile to use this.
 ?S:.
 ?S:locincpth:
 ?S: This variable contains a list of additional directories to be

```

?S: searched by the compiler. The appropriate '-I' directives will
?S: be added to cflags. This is intended to simplify setting
?S: local directories from the Configure command line.
?S: It's not much, but it parallels the loclibpth stuff in libpth.U.
?S:.
?T:inctest thisincl xxx inclwanted ftry previous thislibdir
?T:EBUGGING DEBUGGING
?T:check flag callback checkccflag
?F:!cpp.c !gcctest !try
?D:cppflags=""
?D:cflags=""
?D:ldflags=""
?D:optimize=""
?LINT:extern _sysroot
?INIT:: Possible local include directories to search.
?INIT:: Set locincpth to "" in a hint file to defeat local include searches.
?INIT:locincpth="/usr/local/include /opt/local/include /usr/gnu/include"
?INIT:locincpth="$locincpth /opt/gnu/include /usr/GNU/include /opt/GNU/include"
?INIT::
?INIT:: no include file wanted by default
?INIT:inclwanted=""
?INIT:
?INIT:
    Enable -DEBUGGING and -DDEBUGGING from the command line
?INIT:EBUGGING=""
?INIT:DEBUGGING=""
?INIT:
: determine optimization, if desired, or use for debug flag also
?X: Allow for Configure -Uoptimize -- it's not strictly sensible, but
?X: it has happened and we know what they mean. AD 2/16/98
case "$optimize" in
'|$undef) dflt='none';
") dflt='-O';;
*) dflt="$optimize";;
esac
$cat <<EOH

```

By default, \$package compiles with the -O flag to use the optimizer. Alternately, you might want to use the symbolic debugger, which uses the -g flag (on traditional Unix systems). Either flag can be specified here. To use neither flag, specify the word "none".

```

EOH
rp="What optimizer/debugger flag should be used?"
./myread
optimize="$ans"
case "$optimize" in
'none') optimize=" ";;

```

esac

```
: Check what DEBUGGING is required from the command line
: -DEBUGGING or -DDEBUGGING or
: -DEBUGGING=both = -g + -DDEBUGGING
: -DEBUGGING=-g or -Doptimize=-g = -g
: -DEBUGGING=none or -UDEBUGGING =
:
: -DEBUGGING=old or -DEBUGGING=default = ? $optimize
case "$EDEBUGGING" in
") ;;
*) DEBUGGING=$EDEBUGGING ;;
esac
```

```
case "$DDEBUGGING" in
-g|both|$define)
  case "$optimize" in
*_g*) ;;
*) optimize="$optimize -g" ;;
  esac ;;
none|$undef)
  case "$optimize" in
*_g*) set `echo "X $optimize " | sed 's/ -g / /'`
  shift
  optimize="$*"
  ;;
  esac ;;
esac
```

```
dflt="
case "$DDEBUGGING" in
both|$define) dflt='-DDEBUGGING'
esac
```

```
: argument order is deliberate, as the flag will start with - which set could
: think is an option
checkccflag='check=$1; flag=$2; callback=$3;
echo " ";
echo "Checking if your compiler accepts $flag" 2>&1;
[ "X$sysroot" != "X" ] && echo "For sysroot = $sysroot";
echo "int main(void) { return 0; }" > gcctest.c;
if $cc $_sysroot -O2 $flag -o gcctest gcctest.c 2>gcctest.out && $run ./gcctest; then
  echo "Yes, it does." 2>&1;
  if $test -s gcctest.out ; then
    echo "But your platform does not like it:";
    cat gcctest.out;
  else
  case "$ccflags"
```

```

in
*$check*)
    echo "Leaving current flags $ccflags alone." 2>&1
    ;;
*) dflt="$dflt $flag";
    eval $callback
    ;;
esac
fi
else
    echo "Nope, it does not, but that is ok." 2>&1;
fi
'

```

: We will not override a previous value, but we might want to

: augment a hint file

```

case "$hint" in
default|recommended)
case "$gccversion" in
1*) dflt="$dflt -fpcc-struct-return" ;;
esac
case "$optimize:$DEBUGGING" in
*-g*:old) dflt="$dflt -DDEBUGGING";;
esac
?X: check for POSIXized ISC
case "$gccversion" in
2*) if $test -d /etc/conf/kconfig.d &&
    $contains _POSIX_VERSION $usrinc/sys/unistd.h >/dev/null 2>&1
then
    # Interactive Systems (ISC) POSIX mode.
    dflt="$dflt -posix"
fi
;;
esac
?X: If the user has gcc-2.95 or greater, try adding -fno-strict-alias.
?X: Since the gcc "version" can be non-numeric, e.g.
?X: "2.95.1 19990809 (prerelease)" , we'll do the test on any version
?X: greater than 2.8.
?X: --Andy Dougherty 27 Aug 1999
case "$gccversion" in
1*) ;;
2.[0-8]*)
;;
?*) set strict-aliasing -fno-strict-aliasing
eval $checkccflag
;;
esac
?X: HMB 200405

```

?X: -pipe has shown a compile time speedup of about 40% on Linux and HP-UX

?X: and also worked on cygwin-1.5.9

?X: If a system fails, disable it in the hints. 99% of gcc uses binutils

```
# For gcc, adding -pipe speeds up compilations for some, but apparently
# some assemblers can't read from stdin. (It also slows down compilations
# in other cases, but those are apparently rarer these days.) AD 5/2004.
```

```
case "$gccversion" in
```

```
?) set pipe -pipe
```

```
eval $checkccflag
```

```
::
```

```
esac
```

?X: NWC 200712

```
# on x86_64 (at least) we require an extra library (libssp) in the
# link command line. This library is not named, so I infer that it is
# an implementation detail that may change. Hence the safest approach
# is to add the flag to the flags passed to the compiler at link time,
# as that way the compiler can do the right implementation dependant
# thing. (NWC)
```

```
case "$osname" in
```

```
amigaos)
```

```
:: # -fstack-protector builds but doesn't work
```

```
*) case "$gccversion" in
```

```
?) set stack-protector-strong -fstack-protector-strong
```

```
eval $checkccflag
```

```
case "$dflt" in
```

```
*-fstack-protector-strong*) ;; # It got added.
```

```
*) # Try the plain/older -fstack-protector.
```

```
set stack-protector -fstack-protector
```

```
eval $checkccflag
```

```
::
```

```
esac
```

?X: In USG mode, a MIPS system may need some BSD includes

```
case "$mips_type" in
```

```
*BSD*) inclwanted="$locincpth $usrinc";;
```

```
*) inclwanted="$locincpth $inclwanted $usrinc/bsd";;
```

```
esac
```

```
for thisincl in $inclwanted; do
```

```
if $test -d $thisincl; then
```

```
if $test x$thisincl != x$usrinc; then
```

```
case "$dflt" in
```

```

*) -I$thisincl "*);;
*) dflt="$dflt -I$thisincl ";;
esac
fi
fi
done

?X: Include test function (header, symbol)
inctest='if $contains $2 $usrinc/$1 >/dev/null 2>&1; then
xxx=true;
elif $contains $2 $usrinc/sys/$1 >/dev/null 2>&1; then
xxx=true;
else
xxx=false;
fi;
if $xxx; then
case "$dflt" in
*$2*)
*)
dflt="$dflt -D$2";;
esac;
fi'

```

```
set signal.h LANGUAGE_C; eval $inctest
```

```

case "$usesocks" in
$define)
ccflags="$ccflags -DSOCKS"
;;
esac

```

```

case "$hint" in
default|recommended) dflt="$ccflags $dflt" ;;
*) dflt="$ccflags";;
esac

```

```

case "$dflt" in
'| ') dflt=none;;
esac

```

```
$cat <<EOH
```

Your C compiler may want other flags. For this question you should include `-I/whatever` and `-DWHATEVER` flags and any other flags used by the C compiler, but you should NOT include libraries or ld flags like `-lwhatever`. If you want \$package to honor its debug switch, you should include `-DDEBUGGING` here. Your C compiler might also need additional flags, such as `-D_POSIX_SOURCE`.

To use no flags, specify the word "none".

EOH

?X: strip leading space

set X \$dflt

shift

dflt=\${1+"\$@"}

rp="Any additional cc flags?"

./myread

case "\$ans" in

none) ccflags=";;

*) ccflags="\$ans";;

esac

: the following weeds options from ccflags that are of no interest to cpp

case "\$cppflags" in

") cppflags="\$ccflags"

::

*) set X \$ccflags; shift

case " \$cppflags " in

" \$1 "" ;; # Try to avoid doubling the cppflags.

*) cppflags="\$cppflags \$ccflags" ;;

esac

::

esac

case "\$gccversion" in

1*) cppflags="\$cppflags -D__GNUC__"

esac

case "\$mips_type" in

");;

BSD) cppflags="\$cppflags -DSYSTYPE_BSD43";;

esac

case "\$cppflags" in

");;

*)

echo " "

echo "Let me guess what the preprocessor flags are..." >&4

set X \$cppflags

shift

cppflags="

\$cat >cpp.c <<'EOM'

#define BLURFL foo

BLURFL xx LFRULB

EOM

?X:

?X: For each cc flag, try it out with both cppstdin and cprun, since the

?X: first is almost surely a cc wrapper. We have to try both in case

?X: of cc flags like '-Olimit 2900' that are actually two words...

?X:

```
previous=""
for flag in $*
do
  case "$flag" in
  -*) ftry="$flag";;
  *) ftry="$previous $flag";;
  esac
  if $cpcstdin -DLFRULB=bar $cpcflags $ftry $cpcminus <cpp.c \
  >cpp1.out 2>/dev/null && \
  $cpcrun -DLFRULB=bar $cpcflags $ftry $cplast <cpp.c \
  >cpp2.out
  2>/dev/null && \
  $contains 'foo.*xx.*bar' cpp1.out >/dev/null 2>&1 && \
  $contains 'foo.*xx.*bar' cpp2.out >/dev/null 2>&1
  then
    cpcflags="$cpcflags $ftry"
    previous=""
  else
    previous="$flag"
  fi
done
set X $cpcflags
shift
cpcflags=${1+"$@"}
case "$cpcflags" in
*-* ) echo "They appear to be: $cpcflags";;
esac
$rm -f cpp.c cpp?.out
;;
esac
```

: flags used in final linking phase

```
case "$ldflags" in
") if ./venix; then
  dflt='-i -z'
else
  dflt=""
fi
case "$ccflags" in
*-posix*) dflt="$dflt -posix" ;;
esac
;;
*) dflt="$ldflags";;
esac
# See note above about -fstack-protector
case "$ccflags" in
```

```

*-fstack-protector-strong*)
case "$dflt" in
*-fstack-protector-strong*) ;; # Don't add it again
*) dflt="$dflt -fstack-protector-strong" ;;
esac
;;
*-fstack-protector*)
case "$dflt" in
*-fstack-protector*) ;; # Don't add it again
*) dflt="$dflt -fstack-protector" ;;
esac
;;
esac

```

: Try to guess additional flags to pick up local libraries.

```

for thislibdir in $libpth;
do
case " $loclibpth " in
*" $thislibdir "*)
case "$dflt " in
*" -L$thislibdir "*) ;;
*) dflt="$dflt -L$thislibdir" ;;
esac
;;
esac
done

case "$dflt" in
") dflt='none' ;;
esac

```

\$cat <<EOH

Your C linker may need flags. For this question you should include -L/whatever and any other flags used by the C linker, but you should NOT include libraries like -lwhatever.

Make sure you include the appropriate -L/path flags if your C linker does not normally search all of the directories you specified above, namely

\$libpth

To use no flags, specify the word "none".

EOH

```

rp="Any additional ld flags (NOT including libraries)?"
. ./myread
case "$ans" in

```

```

none) ldflags=";;
*) ldflags="$sans";;
esac
rmlist="$rmlist pdp11"

```

```

@if lkflags
: partial linking may need other flags
case "$lkflags" in
") case "$ldflags" in
") dflt='none';;
*) dflt="$ldflags";;
esac;;
*) dflt="$lkflags";;
esac
echo " "
rp="Partial linking flags to be used (NOT including -r)?"
./myread
case "$sans" in
none)
lkflags=";;
*) lkflags="$sans";;
esac

```

```

@end
?X:
?X: If the user changes compilers after selecting a hint file, it's
?X: possible that the suggested ccflags/ldflags will be wrong. Try to
?X: compile and run a simple test program. Let the user see all the
?X: error messages. -- ADO and RAM
?X: Sometimes, particularly on Linux systems, there is a bad library
?X: (e.g. a dangling symlink or incompatible library or a "run-time"
?X: version but not a "development" version of a library). This test
?X: will catch those sorts of problems too, though how to fix them
?X: may not be obvious.
?X:
: coherency check
echo " "
echo "Checking your choice of C compiler and flags for coherency..." >&4
$cat >try.c <<'EOF'
#include <stdio.h>
int main() { printf("Ok\n"); return(0); }
EOF
?X: Strip extra blanks in case some of the following variables are empty
set X $cc -o try $optimize $ccflags $ldflags try.c $libs
shift
$cat >try.msg <<'EOM'
I've tried to compile and run the following simple program:

```

EOM

\$cat

```
try.c >> try.msg
```

\$cat >> try.msg <<EOM

I used the command:

\$*

```
$run ./try
```

and I got the following output:

EOM

dflt=y

?X: Use "sh -c" to avoid error messages tagged with leading "Configure:".

?X: We need to try the resulting executable, because cc might yield a 0 status

?X: even when ld failed, in which case the executable will not run properly,

?X: if its x bit is set at all...

```
if $sh -c "$cc -o try $optimize $ccflags $ldflags try.c $libs" >>try.msg 2>&1; then
```

```
if $sh -c "$run ./try " >>try.msg 2>&1; then
```

```
xxx=`$run ./try`
```

```
case "$xxx" in
```

```
"Ok") dflt=n ;;
```

```
*) echo "The program compiled OK, but produced no output." >> try.msg ;;
```

```
esac
```

```
else
```

```
echo "The program compiled OK, but exited with status $?." >>try.msg
```

```
rp="You have a problem. Shall I abort Configure"
```

```
dflt=y
```

```
fi
```

```
else
```

```
echo "I can't compile the test program." >>try.msg
```

```
rp="You have a BIG problem. Shall I abort Configure"
```

```
dflt=y
```

```
fi
```

```
case "$dflt" in
```

```
y)
```

```
$cat try.msg >&4
```

?X: using -K will prevent

default aborting--maybe they're cross compiling?

```
case "$knowitall" in
```

```
")
```

```
echo "(The supplied flags or libraries might be incorrect.)"
```

```
::
```

```
*) dflt=n;;
```

```
esac
```

```
echo " "
```

```

./myread
case "$ans" in
n*|N*) ;;
*) echo "Ok. Stopping Configure." >&4
exit 1
;;
esac
;;
n) echo "OK, that should do.";;
esac
$rm_try gcctest gcctest.out

```

Found in path(s):

```

*/opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/compline/ccflags.U

```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: Cppsym.U,v \$

?RCS: Revision 3.0.1.5 1995/05/12 11:59:11 ram

?RCS: patch54: split awk command onto two lines for older awks (ADO)

?RCS:

?RCS: Revision 3.0.1.4 1995/01/11 14:55:57 ram

?RCS: patch45: new cc vs. cpp symbol checking suggested by JHI

?RCS: patch45: added more cpp symbols (JHI)

?RCS:

?RCS: Revision 3.0.1.3 1994/10/29 15:51:32 ram

?RCS: patch36: added ?F: line for metalint file checking

?RCS: patch36: new symbols ardent and titan (ADO)

?RCS:

?RCS: Revision 3.0.1.2 1994/06/20

06:53:32 ram

?RCS: patch30: extended cpp symbol lookup list (JHI)

?RCS: patch30: renamed attrlist symbol into al for brevity

?RCS:

?RCS: Revision 3.0.1.1 1993/12/15 08:14:14 ram

?RCS: patch15: added new cpp symbols __bsdi__ and BSD_NET2

?RCS:

?RCS: Revision 3.0 1993/08/18 12:04:50 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?X:

?X: This unit produces a shell script called Cppsym, which can be used to

?X: determine whether any in a list of symbols is defined by the C compilation

?X: chain (C preprocessor symbols plus C compiler native ones).

?X: It can determine the status of any symbol, though the symbols in \$al

?X: are more easily determined. If you want to add to \$al you can do

?X: it in Myinit.U.

?X:

?MAKE:Cppsym ccsymbols cppsymbols cppccsymbols: run \

eunicefix Guess awk cat tr sed sort rm startsh osname \

+cc gccversion test comm uniq echo Options trnl \

optimize cflags ldflags libs

?MAKE: -pick add \$@ %<

?S:ccsymbols:

?S: The variable contains the symbols

defined by the C compiler alone.

?S: The symbols defined by cpp or by cc when it calls cpp are not in

?S: this list, see cppsymbols and cppccsymbols.

?S: The list is a space-separated list of symbol=value tokens.

?S:.

?S:cppsymbols:

?S: The variable contains the symbols defined by the C preprocessor

?S: alone. The symbols defined by cc or by cc when it calls cpp are

?S: not in this list, see ccsymbols and cppccsymbols.

?S: The list is a space-separated list of symbol=value tokens.

?S:.

?S:cppccsymbols:

?S: The variable contains the symbols defined by the C compiler

?S: when it calls cpp. The symbols defined by the cc alone or cpp

?S: alone are not in this list, see ccsymbols and cppsymbols.

?S: The list is a space-separated list of symbol=value tokens.

?S:.

?T:also symbols i postprocess_cc_v flags

?F:./Cppsym

?F:!Cppsym.true !Cppsym.know !ccsym.com !ccsym.cpp !ccsym.own

: determine known pre-processor and compiler symbols

echo " "

\$echo "Guessing which symbols your C compiler and preprocessor

define..." >&4

?X:

?X: The symbol list is in alpha order for ease of maintenance...

?X:

?X: Lots of new symbols (mostly rummaged from gcc), courtesy of

?X: Jarkko Hietaniemi <jhi@snakemail.hut.fi> -- RAM, 06/06/94

?X:

?X: If your symbol is mixed case, just add it as-is.

?X: All symbols will be transformed to both all-lower and all-upper.

?X: Also drop any leading/trailing underscores, the scan will try all those.

?X:

\$cat <<'EOSH' > Cppsym.know

a29k ABI64 aegis AES_SOURCE AIX AIX32 AIX370

AIX41 AIX42 AIX43 AIX_SOURCE aixpc ALL_SOURCE

alliant alpha am29000 AM29000 AMD64 amiga AMIGAOS AMIX

ansi ANSI_C_SOURCE apollo ardent ARM32 atarist att386 att3b

BeOS BIG_ENDIAN BIT_MSF bsd BSD bsd43 bsd4_2 bsd4_3 BSD4_3 bsd4_4

BSD_4_3 BSD_4_4 BSD_NET2 BSD_TIME BSD_TYPES BSDCOMPAT bsdI

bull c cadmus clipper CMU COFF COMPILER_VERSION

concurrent convex cpu cray CRAY CRAYMPP ctix CX_UX

CYGWIN DGUX DGUX_SOURCE DJGPP dmert DOLPHIN DPX2 DSO

Dynix DynixPTX ELF encore EPI EXTENSIONS FAVOR_BSD

FILE_OFFSET_BITS

FreeBSD GCC_NEW_VARARGS gcos gcx gimpel

GLIBC GLIBC_MINOR

GNU_SOURCE GNUC GNUC_MINOR GNU_LIBRARY GO32 gould GOULD_PN

H3050R H3050RX hbullx20 hcx host_mips

hp200 hp300 hp700 HP700 hp800 hp9000

hp9000s200 hp9000s300 hp9000s400 hp9000s500

hp9000s700 hp9000s800 hp9k8 hp_osf hppa hpux HPUX_SOURCE

i186 i286 i386 i486 i586 i686 i8086 i80960 i860 I960

IA64 iAPX286 ibm ibm032 ibmesa IBMR2 ibmrt ILP32 ILP64

INLINE_INTRINSICS INTRINSICS INT64 interdata is68k ksr1

LANGUAGE_C LARGE_FILE_API LARGEFILE64_SOURCE

LARGEFILE_SOURCE LFS64_LARGEFILE LFS_LARGEFILE

Linux LITTLE_ENDIAN LONG64 LONG_DOUBLE LONG_LONG

LONGDOUBLE LONGLONG LP64 luna luna88k Lynx

M68000 m68k m88100 m88k M88KBCS_TARGET M_COFF

M_I186 M_I286 M_I386 M_I8086 M_I86 M_I86SM M_SYS3

M_SYS5 M_SYSIII M_SYSV M_UNIX M_XENIX MACH machine MachTen

MATH_HAS_NO_SIDE_EFFECTS

mc300 mc500 mc68000 mc68010 mc68020 mc68030 mc68040

mc68060 mc68k mc68k32 mc700 mc88000 mc88100 merlin

mert MiNT mips MIPS_FPSET MIPS_ISA MIPS_SIM MIPS_SZINT

MIPS_SZLONG

MIPS_SZPTR MIPSEB MIPSEL MODERN_C motorola

mpeix MSDOS MTXINU MULTIMAX mvs MVS n16 ncl_el ncl_mr

NetBSD news1500 news1700 news1800 news1900 news3700

news700 news800 news900 NeXT NLS nonstopux ns16000 ns32000

ns32016 ns32332 ns32k nsc32000

OCS88 OEMVS OpenBSD os OS2 OS390 osf OSF1 OSF_SOURCE

pa_risc PA_RISC1_1 PA_RISC2_0 PARAGON parisc

pc532 pdp11 PGC PIC plexus PORTAR posix

POSIX1B_SOURCE POSIX2_SOURCE POSIX4_SOURCE

POSIX_C_SOURCE POSIX_SOURCE POWER

PROTOTYPES PWB pyr QNX R3000 REENTRANT RES Rhapsody RISC6000

```

riscix riscos RT S390 SA110 scs SCO sequent sgi SGI_SOURCE SH3 sinix
SIZE_INT SIZE_LONG SIZE_PTR SOCKET_SOURCE SOCKETS_SOURCE
sony sony_news sonyrisc sparc sparclite spectrum
stardent stdc STDC_EXT stratos sun sun3 sun386
Sun386i svr3 svr4 SVR4_2 SVR4_SOURCE svr5
SX system SYSTYPE_BSD SYSTYPE_BSD43 SYSTYPE_BSD44
SYSTYPE_SVR4 SYSTYPE_SVR5 SYSTYPE_SYSV SYSV SYSV3 SYSV4 SYSV5
sysV68 sysV88 Tek4132 Tek4300 titan
TM3200 TM5400 TM5600
tower tower32 tower32_200 tower32_600 tower32_700
tower32_800
tower32_850 tss
u370 u3b u3b2 u3b20 u3b200 u3b20d u3b5
ultrix UMAXV UnicomPBB UnicomPBD UNICOS UNICOSMK
unix UNIX95 UNIX99 unixpc unos
USE_BSD USE_FILE_OFFSET64 USE_GNU USE_ISOC9X USE_LARGEFILE USE_LARGEFILE64
USE_MISC USE_POSIX USE_POSIX199309 USE_POSIX199506 USE_POSIX2
USE_REENTRANT USE_SVID USE_UNIX98 USE_XOPEN USE_XOPEN_EXTENDED
USGr4 USGr4_2
Utek Utek UTS UWIN uxpm uxps vax venix VMESA vms xenix Xenix286
XOPEN_SOURCE XOPEN_SOURCE_EXTENDED XPG2 XPG2_EXTENDED
XPG3 XPG3_EXTENDED XPG4 XPG4_EXTENDED
z8000
EOSH
?X: Maybe put other stuff here too.
cat <<EOSH >>Cppsym.know
$osname
EOSH
./tr '[a-z]' '[A-Z]' < Cppsym.know > Cppsym.a
./tr '[A-Z]' '[a-z]' < Cppsym.know > Cppsym.b
$cat Cppsym.know > Cppsym.c
$cat Cppsym.a Cppsym.b Cppsym.c | $tr ' ' $trnl | $sort | $uniq > Cppsym.know
$rm -f Cppsym.a Cppsym.b Cppsym.c
cat <<EOSH > Cppsym
$startsh
if $test $# -gt 0; then
    echo \$* | $tr " " "$trnl" | ./Cppsym.try > Cppsym.got
    if $test -s Cppsym.got; then
        $rm -f Cppsym.got
        exit 0
    fi
    $rm -f Cppsym.got
    exit 1
else
    $tr " " "$trnl" | ./Cppsym.try
    exit 0
fi
EOSH

```

```

chmod +x Cppsym
$unicefix Cppsym
?X: The below awk script will die a horrible death if
?X: some of the tested symbols are not long ints.
?X: Also, we do not make difference between just defined and defined zero.
cat <<EOSH > Cppsym.try
$startsh
cat <<'EOCP' > try.c
#include <stdio.h>
int main() {
EOCP
?X: The length($1) command guards against possible empty entries.
?X: The awk snippet is know to give heartburn to UNICOS/mk awk.
$awk \\
EOSH
cat <<'EOSH' >> Cppsym.try
'length($1) > 0 {
    printf "#ifdef %s\n#if %s+0\nprintf(\"%s=%ld\n\", (long)%s);\n#else\nprintf(\"%s\n\");\n#endif\n#endif\n", $1,
$1, $1, $1, $1
    printf "#ifdef __s\n#if __s+0\nprintf(\"__s=%ld\n\",
(long)__s);\n#else\nprintf(\"__s\n\");\n#endif\n#endif\n", $1, $1, $1, $1, $1
    printf "#ifdef __s\n#if __s+0\nprintf(\"__s=%ld\n\",
(long)__s);\n#else\nprintf(\"__s\n\");\n#endif\n#endif\n",
$1, $1, $1, $1, $1
    printf "#ifdef __s__\n#if __s__+0\nprintf(\"__s__=%ld\n\",
(long)__s__); \n#else\nprintf(\"__s__\n\");\n#endif\n#endif\n", $1, $1, $1, $1, $1
}' >> try.c
echo 'return 0;}' >> try.c
EOSH
cat <<EOSH >> Cppsym.try
flags="$ccflags"
case "$osname-$gccversion" in
irix-) flags="$flags -woff 1178" ;;
os2-*) flags="$flags -Zlinker /PM:VIO" ;;
esac
$cc -o try $optimize \ $flags $ldflags try.c $libs && $run ./try
EOSH
chmod +x Cppsym.try
$unicefix Cppsym.try
./Cppsym < Cppsym.know > Cppsym.true
: now check the C compiler for additional symbols
?X: suggested by Jarkko Hietaniemi <jhi@snakemail.hut.fi>, thanks!
postprocess_cc_v="
case "$osname" in
aix) postprocess_cc_v="|$tr , ' "' ;;
esac
$cat >ccsym <<EOS
$startsh

```

```

$cat >tmp.c <<EOF
extern int foo;
EOF
for i in ` $cc -v -c tmp.c 2>&1 $postprocess_cc_v `
do
case "$i" in
-D*) echo "$i" | $sed 's/^-D//';;
-A*) $test "$gccversion" && echo "$i" | $sed 's/^-A//' | $sed 's/(.*)/(.*)\^1=\2/';;
esac
done
$rm
-f try.c
EOS
postprocess_cc_v="
chmod +x ccsym
$unicefix ccsym
./ccsym > ccsym1.raw
?X: AIX complains if $uniq is passed an empty file. ($sort apparently
?X: doesn't care.) --AD 14 July 1998
if $test -s ccsym1.raw; then
    $sort ccsym1.raw | $uniq >ccsym.raw
else
    mv ccsym1.raw ccsym.raw
fi

?X: canonicalize symbols for easier sort/uniq/comm usage: append =1 if no = sign
?X: the awk script must be on two lines for older awk programs, sigh! -- ADO
$awk '/^=/ { print $0; next }
{ print $0"=1" }' ccsym.raw >ccsym.list
$awk '/^=/ { print $0; next }
{ print $0"=1" }' Cppsym.true >ccsym.true
$comm -13 ccsym.true ccsym.list >ccsym.own
$comm -12 ccsym.true ccsym.list >ccsym.com
$comm -23 ccsym.true ccsym.list >ccsym.cpp
also="
if $test -z ccsym.raw; then
echo "Your C compiler doesn't seem to define any symbols!" >&4
echo " "
echo "However, your C preprocessor defines the following symbols:"
$cat Cppsym.true
    ccsymbols="
cppsymbols=`$cat Cppsym.true`
    cppsymbols=`echo
$cppsymbols`
cppcsymbols="$cppsymbols"
else
if $test -s ccsym.com; then
    echo "Your C compiler and pre-processor define these symbols:"

```

```

$sed -e 's/(.*)=.*/\1/' ccsym.com
also='also '
symbols='ones'
cppccsymbols=`$cat ccsym.com`
cppccsymbols=`echo $cppccsymbols`
$test "$$silent" || sleep 1
fi
if $test -s ccsym.cpp; then
$test "$also" && echo " "
echo "Your C pre-processor ${also} defines the following symbols:"
$sed -e 's/(.*)=.*/\1/' ccsym.cpp
also='further '
cppsymbols=`$cat ccsym.cpp`
cppsymbols=`echo $cppsymbols`
$test "$$silent" || sleep 1
fi
if $test -s ccsym.own; then
$test "$also" && echo " "
echo "Your C compiler ${also} defines the following cpp symbols:"
$sed -e 's/(.*)=1/\1/' ccsym.own
$sed -e 's/(.*)=.*/\1/' ccsym.own | $uniq >>Cppsym.true
    ccsymbols=`$cat ccsym.own`
    ccsymbols=`echo $ccsymbols`
$test "$$silent" || sleep 1
fi
fi
$rm -f Cppsym.know Cppsym.true

```

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/Cppsym.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_times.U,v 3.0.1.2 1995/07/25 14:07:50 ram Exp \$

?RCS:

?RCS: Copyright (c) 1991-1993, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 3.0.

?RCS:

?RCS: \$Log: d_times.U,v \$

?RCS: Revision 3.0.1.2 1995/07/25 14:07:50 ram

?RCS: patch56: typo fix, sytem -> system

?RCS:

?RCS: Revision 3.0.1.1 1994/08/29 16:14:00 ram

```

?RCS: patch32: now uses new Typedef unit to compute type information
?RCS:
?RCS: Revision 3.0 1993/08/18 12:07:46 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?X:
?X: What is the type returned by times() ?
?X:
?X: Force inclusion of <sys/types.h>
?X:INC: i_systypes
?MAKE:d_times clocktype:
    Csym Myread Typedef i_systimes
?MAKE: -pick add $@ %<
?S:d_times:
?S: This variable conditionally defines the HAS_TIMES symbol, which indicates
?S: that the times() routine exists. The times() routine is normally
?S: provided on UNIX systems. You may have to include <sys/times.h>.
?S:.
?S:clocktype:
?S: This variable holds the type returned by times(). It can be long,
?S: or clock_t on BSD sites (in which case <sys/types.h> should be
?S: included).
?S:.
?C:HAS_TIMES (TIMES):
?C: This symbol, if defined, indicates that the times() routine exists.
?C: Note that this became obsolete on some systems (SUNOS), which now
?C: use getrusage(). It may be necessary to include <sys/times.h>.
?C:.
?C:Clock_t (CLOCKTYPE):
?C: This symbol holds the type returned by times(). It can be long,
?C: or clock_t on BSD sites (in which case <sys/types.h> should be
?C: included).
?C:.
?H:#$d_times HAS_TIMES /**/
?H:#define Clock_t $clocktype /* Clock time */
?H:.
?T:val inc
: see if times exists
echo "
"
if set times val -f d_times; eval $csym; $val; then
echo 'times() found.' >&4
d_times="$define"
inc="
case "$i_systimes" in
"$define") inc='sys/times.h';
esac
rp="What is the type returned by times() on this system?"

```

```

set clock_t clocktype long stdio.h sys/types.h $inc
eval $typedef_ask
else
echo 'times() NOT found, hope that will do.' >&4
d_times="$undef"
?X: The following is needed for typedef (won't like an empty variable)
clocktype='int'
fi

```

Found in path(s):

```

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/typedefs/d_times.U

```

No license file was found, but licenses were detected in source scan.

```

?RCS: $Id: intsize.U,v 3.0.1.2 1997/02/28 15:55:26 ram Exp $
?RCS:
?RCS: Copyright (c) 1991-1993, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 3.0.
?RCS:
?RCS: $Log: intsize.U,v $
?RCS: Revision 3.0.1.2 1997/02/28 15:55:26 ram
?RCS: patch61: avoid prompting the user if the test runs ok
?RCS: patch61: moved code from longsize.U into there
?RCS: patch61: new tests for shortsize as well
?RCS:
?RCS: Revision 3.0.1.1 1994/10/29 16:21:06 ram
?RCS: patch36: added ?F: line for metalint file checking
?RCS:
?RCS: Revision 3.0 1993/08/18 12:08:52 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:intsize longsize
shortsize: Compile Myread cat run i_stdlib rm_try
?MAKE: -pick add $@ %<
?S:intsize:
?S: This variable contains the value of the INTSIZE symbol, which
?S: indicates to the C program how many bytes there are in an int.
?S:.
?S:longsize:
?S: This variable contains the value of the LONGSIZE symbol, which
?S: indicates to the C program how many bytes there are in a long.
?S:.
?S:shortsize:

```

?S: This variable contains the value of the SHORTSIZE symbol which

?S: indicates to the C program how many bytes there are in a short.

?S:.

?C:INTSIZE:

?C: This symbol contains the value of sizeof(int) so that the C

?C: preprocessor can make decisions based on it.

?C:.

?C:LONGSIZE:

?C: This symbol contains the value of sizeof(long) so that the C

?C: preprocessor can make decisions based on it.

?C:.

?C:SHORTSIZE:

?C: This symbol contains the value of sizeof(short) so that the C

?C: preprocessor can make decisions based on it.

?C:.

```
?H:#define INTSIZE $intsize /**/
```

```
?H:#define LONGSIZE $longsize /**/
```

```
?H:#define
```

```
SHORTSIZE $shortsize /**/
```

```
?H:.
```

```
?F:!try
```

```
: check for lengths of integral types
```

```
echo " "
```

```
case "$intsize" in
```

```
")
```

```
echo "Checking to see how big your integers are..." >&4
```

```
$cat >try.c <<EOCP
```

```
#include <stdio.h>
```

```
#$i_stdlib I_STDLIB
```

```
#ifdef I_STDLIB
```

```
#include <stdlib.h>
```

```
#endif
```

```
int main()
```

```
{
```

```
@if INTSIZE || intsize
```

```
printf("intsize=%d;\n", (int)sizeof(int));
```

```
@end
```

```
@if LONGSIZE || longsize
```

```
printf("longsize=%d;\n", (int)sizeof(long));
```

```
@end
```

```
@if SHORTSIZE || shortsize
```

```
printf("shortsize=%d;\n", (int)sizeof(short));
```

```
@end
```

```
exit(0);
```

```
}
```

```
EOCP
```

```
set try
```

```
if eval $compile_ok && $run ./try > /dev/null; then
```

```

eval `$run ./try`
@if INTSIZE || intsize
  echo "Your integers are $intsize bytes long."
@end
@if LONGSIZE || longsize
  echo "Your long integers are $longsize bytes long."
@end
@if SHORTSIZE || shortsize
  echo "Your short integers are $shortsize bytes long."
@end
else
  $cat >&4 <<EOM
!
Help! I can't compile and run the intsize test program: please enlighten me!
(This is probably a misconfiguration
in your system or libraries, and
you really ought to fix it. Still, I'll try anyway.)
!
EOM
@if INTSIZE || intsize
  dflt=4
  rp="What is the size of an integer (in bytes)?"
  ./myread
  intsize="$ans"
@end
@if LONGSIZE || longsize
  dflt=$intsize
  rp="What is the size of a long integer (in bytes)?"
  ./myread
  longsize="$ans"
@end
@if SHORTSIZE || shortsize
  dflt=2
  rp="What is the size of a short integer (in bytes)?"
  ./myread
  shortsize="$ans"
@end
fi
;;
esac
$rm_try

```

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/a_dvisory/intsize.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_strerror.U,v 3.0.1.3 1994/05/13 15:20:27 ram Exp \$

?RCS:
?RCS: Copyright (c) 1991-1993, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 3.0.
?RCS:
?RCS: \$Log: d_strerror.U,v \$
?RCS: Revision 3.0.1.3 1994/05/13 15:20:27 ram
?RCS: patch27: now uses new macro support for cleaner Strerror def
?RCS:
?RCS: Revision 3.0.1.2 1994/05/06 14:58:26 ram
?RCS: patch23: renamed strerror into Strerror to protect name space (ADO)
?RCS:
?RCS: Revision 3.0.1.1 1994/01/24 14:08:56 ram
?RCS: patch16: protected code looking for sys_errnolist[] with @if
?RCS: patch16: added default value for d_syserrlst
?RCS:
?RCS: Revision
3.0 1993/08/18 12:07:35 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:d_strerror d_syserrlst d_syserrlst d_strerror: contains Csym Findhdr
?MAKE: -pick add \$@ %<
?S:d_strerror:
?S: This variable conditionally defines HAS_STRERROR if strerror() is
?S: available to translate error numbers to strings.
?S:.
?S:d_syserrlst:
?S: This variable conditionally defines HAS_SYS_ERRLIST if sys_errlist[] is
?S: available to translate error numbers to strings.
?S:.
?S:d_syserrlst:
?S: This variable conditionally defines HAS_SYS_ERRNOLIST if sys_errnolist[]
?S: is available to translate error numbers to the symbolic name.
?S:.
?S:d_strerror:
?S: This variable holds what Strerror is defined as to translate an error
?S: code condition into an error message string. It could be 'strerror'
?S: or a more complex macro emulating strerror with sys_errlist[], or the
?S: "unknown" string when both strerror and sys_errlist are missing.
?S:.
?C:HAS_STRERROR (STRERROR):
?C: This symbol, if defined,
indicates that the strerror routine is
?C: available to translate error numbers to strings. See the writeup

?C: of Strerror() in this file before you try to define your own.

?C:.

?C:HAS_SYS_ERRLIST (SYSERRLIST):

?C: This symbol, if defined, indicates that the sys_errlist array is

?C: available to translate error numbers to strings. The extern int

?C: sys_nerr gives the size of that table.

?C:.

?C:HAS_SYS_ERRNOLIST (SYSERRNOLIST):

?C: This symbol, if defined, indicates that the sys_errnolist array is

?C: available to translate an errno code into its symbolic name (e.g.

?C: ENOENT). The extern int sys_nerrno gives the size of that table.

?C:.

?C:Strerror:

?C: This preprocessor symbol is defined as a macro if strerror() is

?C: not available to translate error numbers to strings but sys_errlist[]

?C: array is there.

?C:.

```
?H:#$d_strerror HAS_STRERROR /**/
?H:#$d_syserrlst HAS_SYS_ERRLIST /**/
?H:#$d_sysernlst HAS_SYS_ERRNOLIST /**/
?H:#define Strerror(e) $d_strerrorm
?H:
?D:d_sysernlst="
?T:xxx
val
: see if strerror and/or sys_errlist[] exist
echo " "
?X: MPE/iX needs this protection of hint values.
?X: Background: strerror exists in kernel but not in libc.
?X: Scanning the kernel for symbols would be a bad idea, however,
?X: because many symbols that look unix-ish exist in the kernel.
?X: The stress is on the 'look'.
?X: --jhi 9/1998
if test "X$d_strerror" = X -o "X$d_syserrlst" = X; then
    if set strerror val -f d_strerror; eval $csym; $val; then
        echo 'strerror() found.' >&4
        d_strerror="$define"
        d_strerrorm='strerror(e)'
    if set sys_errlist val -a d_syserrlst; eval $csym; $val; then
        echo "(You also have sys_errlist[], so we could roll our own strerror.)"
        d_syserrlst="$define"
    else
        echo "(Since you don't have sys_errlist[], strerror() is welcome.)"
        d_syserrlst="$undef"
    fi
elif xxx=`./findhdr string.h`; test "$xxx" || xxx=`./findhdr strings.h`; \
$contains '#[ ]*define.*strerror' "$xxx" >/dev/null 2>&1; then
echo 'strerror() found in
```

```

string header.' >&4
d_strerror="$define"
d_strerrorr='strerror(e)'
if set sys_errlist val -a d_syserrlst; eval $csym; $val; then
echo "(Most probably, strerror() uses sys_errlist[] for descriptions.)"
d_syserrlst="$define"
else
echo "(You don't appear to have any sys_errlist[], how can this be?)"
d_syserrlst="$undef"
fi
elif set sys_errlist val -a d_syserrlst; eval $csym; $val; then
echo "strerror() not found, but you have sys_errlist[] so we'll use that." >&4
d_strerror="$undef"
d_syserrlst="$define"
d_strerrorr='((e)<0||(e)>=sys_nerr?"unknown":sys_errlist[e])'
else
echo 'strerror() and sys_errlist[] NOT found.' >&4
d_strerror="$undef"
d_syserrlst="$undef"
d_strerrorr=""unknown""
fi
fi
@if d_syserrlst || HAS_SYS_ERRNOLIST
if set sys_errnolist val -a d_syserrlst; eval $csym; $val; then
echo "(Symbolic error codes can be fetched via the sys_errnolist[] array.)"
d_syserrlst="$define"
else
echo "(However, I can't extract the symbolic error code
out of errno.)"
d_syserrlst="$undef"
fi
@end

```

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/modified/d_strerror.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: nametype.U 1 2006-08-24 12:32:52Z rmanfredi \$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic Licence,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic Licence; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: nametype.U,v \$

?RCS: Revision 3.0.1.3 1994/10/29 16:26:09 ram

?RCS: patch36: call ./usg and ./bsd explicitly instead of relying on PATH

?RCS:

?RCS: Revision 3.0.1.2 1994/08/29 16:36:48 ram

?RCS: patch32: fixed typo: /etc/password -> /etc/passwd (WED)

?RCS:

?RCS: Revision 3.0.1.1 1993/09/13 16:10:09 ram

?RCS: patch10: made questions more explicit for 'Configure -s' prompting (WAD)

?RCS:

?RCS: Revision 3.0 1993/08/18 12:09:20 ram

?RCS: Baseline

for dist 3.0 netwide release.

?RCS:

?MAKE:nametype d_passnames d_berknames d_usgnames: Myread Guess Oldconfig cat

?MAKE: -pick add \$@ %<

?S:nametype:

?S: This variable indicates how full names are stored on this system.

?S: Values are bsd, usg, and other.

?S:.

?S:d_passnames:

?S: This variable conditionally defines the PASSNAMES symbol,

?S: which indicates to the C program that full names are stored in

?S: the /etc/passwd file.

?S:.

?S:d_berknames:

?S: This variable conditionally defines the PASSNAMES symbol,

?S: which indicates to the C program that full names are stored in

?S: the /etc/passwd file in Berkeley format.

?S:.

?S:d_usgnames:

?S: This variable conditionally defines the PASSNAMES symbol,

?S: which indicates to the C program that full names are stored in

?S: the /etc/passwd file in USG format.

?S:.

?C:PASSNAMES:

?C: This symbol, if defined, indicates that full names are stored in

?C: the /etc/passwd file.

?C:.

?C:BERKNAMES:

?C: This symbol, if defined, indicates that full

names are stored in

?C: the /etc/passwd file in Berkeley format (name first thing, everything

?C: up to first comma, with & replaced by capitalized login id, yuck).

?C:.

?C:USGNAMES:

?C: This symbol, if defined, indicates that full names are stored in

?C: the /etc/passwd file in USG format (everything after - and before (is

```

?C: the name).
?C:.
?H:#$d_passnames PASSNAMES /* (undef to take name from ~/.fullname) */
?H:#$d_berknames BERKNAMES /* (that is, ":name,stuff:") */
?H:#$d_usgnames USGNAMES /* (that is, ":stuff-name(stuff):") */
?H:.
: find out how to find out full name
case "$d_berknames" in
"$define")
dflt=y;;
"$undef")
dflt=n;;
*)
if ./bsd; then
dflt=y
elif ./xenix; then
dflt=y
else
dflt=n
fi
;;
esac
$cat <<'EOM'

```

Does your /etc/passwd file keep full names in Berkeley/V7 format (name first thing after ':' in GCOS field)? In that case, a typical entry in the password file looks like this:

```

guest:**password**:10:100:Mister Guest User:/usr/users:/bin/sh

```

```

^^^^^^^^^^^^^^^^^^^^^^

```

```

EOM
rp="Berkeley/V7 format for full name in /etc/passwd?"
./myread
case "$ans" in
y*) d_passnames="$define"
d_berknames="$define"
d_usgnames="$undef"
nametype=bsd
;;
*)
case "$d_usgnames" in
"$define") dflt=y;;
"$undef") dflt=n;;
*)
if ./usg; then
dflt=y
else

```

```

    dflt=n
fi
;;
esac
$cat <<'EOM'

```

Does your passwd file keep full names in USG format (name sandwiched between a '-' and a '(')? In that case, a typical entry in the password file looks like this:

```

    guest:**password**:10:100:000-Mister Guest User(000):usr/users:/bin/sh
                ^^^^^^^^^^^^^^^^^^^^^^^

```

EOM

```

rp="USG format for full name in /etc/passwd?"
. ./myread
case "$ans" in
n*) echo "Full name will be taken from ~/.fullname"
    d_passnames="$undef"
    d_berknames="$undef"
    d_usgnames="$undef"
    nametype=other
    ;;
*)
    d_passnames="$define"
    d_berknames="$undef"
    d_usgnames="$define"
    nametype=usg
    ;;
esac;;
esac

```

Found in path(s):

```

*
/opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/nametype.U

```

No license file was found, but licenses were detected in source scan.

```

?RCS: $Id: d_setprotoent_r.U,v 0RCS:
?RCS: Copyright (c) 2002,2003 Jarkko Hietaniemi
?RCS:
?RCS: You may distribute under the terms of either the GNU General Public
?RCS: License or the Artistic License, as specified in the README file.
?RCS:
?RCS: Generated by the reentr.pl from the Perl 5.8 distribution.
?RCS:
?MAKE:d_setprotoent_r setprotoent_r_proto: Inlibc Protochk Hasproto \
i_systypes usethreads i_netdb extern_C
?MAKE: -pick add $@ %<

```

?S:d_setprotoent_r:
 ?S: This variable conditionally defines the HAS_SETPROTOENT_R symbol,
 ?S: which indicates to the C program that the setprotoent_r()
 ?S: routine is available.
 ?S:.
 ?S:setprotoent_r_proto:
 ?S: This variable encodes the prototype of setprotoent_r.
 ?S: It is zero if d_setprotoent_r is undef, and one of the
 ?S: REENTRANT_PROTO_T_ABC macros of reentr.h if d_setprotoent_r
 ?S: is defined.
 ?S:.
 ?C:HAS_SETPROTOENT_R:
 ?C: This symbol, if defined, indicates that the setprotoent_r
 routine
 ?C: is available to setprotoent re-entrantly.
 ?C:.
 ?C:SETPROTOENT_R_PROTO:
 ?C: This symbol encodes the prototype of setprotoent_r.
 ?C: It is zero if d_setprotoent_r is undef, and one of the
 ?C: REENTRANT_PROTO_T_ABC macros of reentr.h if d_setprotoent_r
 ?C: is defined.
 ?C:.
 ?H:#\$d_setprotoent_r HAS_SETPROTOENT_R /**/
 ?H:#define SETPROTOENT_R_PROTO \$setprotoent_r_proto /**/
 ?H:.
 ?T:try hdrs d_setprotoent_r_proto
 : see if setprotoent_r exists
 set setprotoent_r d_setprotoent_r
 eval \$inlibc
 case "\$d_setprotoent_r" in
 "\$define")
 hdrs="\$i_systypes sys/types.h define stdio.h \$i_netdb netdb.h"
 case "\$d_setprotoent_r_proto:\$usethreads" in
 ":define") d_setprotoent_r_proto=define
 set d_setprotoent_r_proto setprotoent_r \$hdrs
 eval \$hasproto ;;
 *) ;;
 esac
 case "\$d_setprotoent_r_proto" in
 define)
 case "\$setprotoent_r_proto" in
 "|0) try='int setprotoent_r(int, struct protoent_data*);'
 ./protochk "\$extern_C \$try" \$hdrs && setprotoent_r_proto=I_ID ;;
 esac
 case "\$setprotoent_r_proto"
 in
 "|0) try='void setprotoent_r(int, struct protoent_data*);'
 ./protochk "\$extern_C \$try" \$hdrs && setprotoent_r_proto=V_ID ;;

```

esac
case "$setprotoent_r_proto" in
|(0) d_setprotoent_r=undef
    setprotoent_r_proto=0
echo "Disabling setprotoent_r, cannot determine prototype." >&4 ;;
*) case "$setprotoent_r_proto" in
REENTRANT_PROTO*) ;;
*) setprotoent_r_proto="REENTRANT_PROTO_${setprotoent_r_proto}" ;;
esac
echo "Prototype: $try" ;;
esac
;;
*) case "$usethreads" in
define) echo "setprotoent_r has no prototype, not using it." >&4 ;;
esac
d_setprotoent_r=undef
setprotoent_r_proto=0
;;
esac
;;
*) setprotoent_r_proto=0
;;
esac

```

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/threads/d_setprotoent_r.U

No license file was found, but licenses were detected in source scan.

```

?RCS: $Id: d_getgrgid_r.U,v 0RCS:
?RCS: Copyright (c) 2002,2003 Jarkko Hietaniemi
?RCS:
?RCS: You may distribute under the terms of either the GNU General Public
?RCS: License or the Artistic License, as specified in the README file.
?RCS:
?RCS: Generated by the reentr.pl from the Perl 5.8 distribution.
?RCS:
?MAKE:d_getgrgid_r getgrgid_r_proto: Inlibc Protochk Hasproto i_systypes \
usethreads i_grp extern_C
?MAKE: -pick add $@ %<
?S:d_getgrgid_r:
?S: This variable conditionally defines the HAS_GETGRGRID_R symbol,
?S: which indicates to the C program that the getgrgid_r()
?S: routine is available.
?S:.
?S:getgrgid_r_proto:
?S: This variable encodes the prototype of getgrgid_r.
?S: It is zero if d_getgrgid_r is undef, and one of the

```

?S: REENTRANT_PROTO_T_ABC macros of reentr.h if d_getgrgid_r

?S: is defined.

?S:.

?C:HAS_GETGRGID_R:

?C: This symbol, if defined, indicates that the getgrgid_r routine

?C: is available to

getgrgid re-entrantly.

?C:.

?C:GETGRGID_R_PROTO:

?C: This symbol encodes the prototype of getgrgid_r.

?C: It is zero if d_getgrgid_r is undef, and one of the

?C: REENTRANT_PROTO_T_ABC macros of reentr.h if d_getgrgid_r

?C: is defined.

?C:.

?H:#\$d_getgrgid_r HAS_GETGRGID_R /**/

?H:#define GETGRGID_R_PROTO \$getgrgid_r_proto /**/

?H:.

?T:try hdrs d_getgrgid_r_proto

: see if getgrgid_r exists

set getgrgid_r d_getgrgid_r

eval \$inlibc

case "\$d_getgrgid_r" in

"\$define")

hdrs="\$i_systypes sys/types.h define stdio.h \$i_grp grp.h"

case "\$d_getgrgid_r_proto:\$usetthreads" in

":define") d_getgrgid_r_proto=define

set d_getgrgid_r_proto getgrgid_r \$hdrs

eval \$hasproto ;;

*) ;;

esac

case "\$d_getgrgid_r_proto" in

define)

case "\$getgrgid_r_proto" in

"|0) try='int getgrgid_r(gid_t, struct group*, char*, size_t, struct group**);'

./protochk "\$extern_C \$try" \$hdrs && getgrgid_r_proto=L_TSBWR ;;

esac

case "\$getgrgid_r_proto" in

"|0) try='int getgrgid_r(gid_t, struct group*, char*, int,

struct group**);'

./protochk "\$extern_C \$try" \$hdrs && getgrgid_r_proto=L_TSBIR ;;

esac

case "\$getgrgid_r_proto" in

"|0) try='int getgrgid_r(gid_t, struct group*, char*, int);'

./protochk "\$extern_C \$try" \$hdrs && getgrgid_r_proto=L_TSBI ;;

esac

case "\$getgrgid_r_proto" in

"|0) try='struct group* getgrgid_r(gid_t, struct group*, char*, int);'

./protochk "\$extern_C \$try" \$hdrs && getgrgid_r_proto=S_TSBI ;;

```

esac
case "$getgrgid_r_proto" in
"(0) d_getgrgid_r=undef
    getgrgid_r_proto=0
echo "Disabling getgrgid_r, cannot determine prototype." >&4 ;;
*) case "$getgrgid_r_proto" in
REENTRANT_PROTO*) ;;
*) getgrgid_r_proto="REENTRANT_PROTO_${getgrgid_r_proto}" ;;
esac
echo "Prototype: $try" ;;
esac
;;
*) case "$usetthreads" in
define) echo "getgrgid_r has no prototype, not using it." >&4 ;;
esac
d_getgrgid_r=undef
getgrgid_r_proto=0
;;
esac
;;
*) getgrgid_r_proto=0
;;
esac

```

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/threads/d_getgrgid_r.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 2001, Jarkko Hietaniemi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 3.0.

?RCS:

?MAKE:d_sigprocmask: Inlibc

?MAKE: -pick add \$@ %<

?S:d_sigprocmask:

?S: This variable conditionally defines HAS_SIGPROCMASK

?S: if sigprocmask() is available to examine or change the signal mask

?S: of the calling process.

?S:.

?C:HAS_SIGPROCMASK:

?C: This symbol, if defined, indicates that the sigprocmask

?C: system call is available to examine or change the signal mask

?C: of the calling process.

?C:.

?H:#\$d_sigprocmask HAS_SIGPROCMAK /**/

?H:.

?LINT:set d_sigprocmask

: see if sigprocmask exists

set sigprocmask d_sigprocmask

eval

\$inlibc

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_sigprocmask.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_hidnet.U 1 2006-08-24 12:32:52Z rmanfredi \$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic Licence,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic Licence; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: d_hidnet.U,v \$

?RCS: Revision 3.0 1993/08/18 12:06:20 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?MAKE:d_hidnet hiddennet: cat sed myhostname mydomain Myread Oldconfig

?MAKE: -pick add \$@ %<

?S:d_hidnet:

?S: This variable conditionally defines the symbol HIDDEN_NET, which

?S: tells the C program that it should pretend it is on a different

?S: host for purposes of advertising a mailing address.

?S:.

?S:hiddennet:

?S: This variable contains

the value eventually given to the symbol

?S: HIDDEN_NET, if d_hidnet defines it. If defined, it's the name

?S: of the host which serves as the mail server for a network that

?S: is invisible to the outside world.

?S:.

?C:HIDDEN_NET (HIDDENNET):

?C: This symbol, if defined, contains the host name that you want to

?C: advertise to the outside world. This name can be different from

?C: your actual host name, as long as the machine you specify knows

```
?C: how to forward mail to you.
?C:.
?H:#$d_hidnet HIDDEN_NET "$hiddennet" /**/
?H:.
: now get the host name to advertise as our mailing address
case "$hiddennet" in
") dflt=n;;
*) dflt=y;;
esac
$cat <<EOM
```

Some sites are on "hidden" networks, in the sense that the network appears to the outside world as a single machine. The advertised name of any host on this hidden network is the name of one machine on the local network which knows how to forward mail to any other host on the hidden network.

Do you wish to advertise a different hostname to the world than the one your own host (\$myhostname\$mydomain) has?

```
EOM
rp="Use "hidden" network?"
./myread
case "$ans" in
n*) d_hidnet="$undef" hiddennet="";
*)
d_hidnet="$define"
echo " "
case "$hiddennet" in
") dflt=`echo $mydomain | $sed -e 's/^\./'`;
*) dflt="$hiddennet";
esac
rp='What hostname do you wish to advertise?'
./myread
hiddennet="$ans"
;;
esac
```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/d_hidnet.U
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_ttyname_r.U,v 0RCS:

?RCS: Copyright (c) 2002,2003 Jarkko Hietaniemi

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:
?RCS: Generated by the reentr.pl from the Perl 5.8 distribution.
?RCS:
?MAKE:d_ttyname_r ttyname_r_proto: Inlibc Protochk Hasproto i_systypes \
usethreads i_unistd extern_C
?MAKE: -pick add \$@ %<
?S:d_ttyname_r:
?S: This variable conditionally defines the HAS_TTYNAME_R symbol,
?S: which indicates to the C program that the ttyname_r()
?S: routine is available.
?S:.
?S:ttyname_r_proto:
?S: This variable encodes the prototype of ttyname_r.
?S: It is zero if d_ttyname_r is undef, and one of the
?S: REENTRANT_PROTO_T_ABC macros of reentr.h if d_ttyname_r
?S: is defined.
?S:.
?C:HAS_TTYNAME_R:
?C: This symbol, if defined, indicates that the ttyname_r routine
?C: is available to ttyname re-entrantly.
?C:.
?C:TTYNAME_R_PROTO:
?C: This
symbol encodes the prototype of ttyname_r.
?C: It is zero if d_ttyname_r is undef, and one of the
?C: REENTRANT_PROTO_T_ABC macros of reentr.h if d_ttyname_r
?C: is defined.
?C:.
?H:#\$d_ttyname_r HAS_TTYNAME_R /**/
?H:#define TTYNAME_R_PROTO \$ttyname_r_proto /**/
?H:.
?T:try hdrs d_ttyname_r_proto
: see if ttyname_r exists
set ttyname_r d_ttyname_r
eval \$inlibc
case "\$d_ttyname_r" in
"\$define")
hdrs="\$i_systypes sys/types.h define stdio.h \$i_unistd unistd.h"
case "\$d_ttyname_r_proto:\$usethreads" in
":define") d_ttyname_r_proto=define
set d_ttyname_r_proto ttyname_r \$hdrs
eval \$hasproto ;;
*) ;;
esac
case "\$d_ttyname_r_proto" in
define)
case "\$ttyname_r_proto" in
"|0) try='int ttyname_r(int, char*, size_t);'

```

./protochk "$extern_C $try" $hdrs && ttyname_r_proto=I_IBW ;;
esac
case "$ttyname_r_proto" in
"|0) try='int ttyname_r(int, char*, int);'
./protochk "$extern_C $try" $hdrs && ttyname_r_proto=I_IBI ;;
esac
case
"$ttyname_r_proto" in
"|0) try='char* ttyname_r(int, char*, int);'
./protochk "$extern_C $try" $hdrs && ttyname_r_proto=B_IBI ;;
esac
case "$ttyname_r_proto" in
"|0) d_ttyname_r=undef
      ttyname_r_proto=0
      echo "Disabling ttyname_r, cannot determine prototype." >&4 ;;
*) case "$ttyname_r_proto" in
REENTRANT_PROTO*) ;;
*) ttyname_r_proto="REENTRANT_PROTO_${ttyname_r_proto}" ;;
esac
echo "Prototype: $try" ;;
esac
;;
*) case "$usetthreads" in
define) echo "ttyname_r has no prototype, not using it." >&4 ;;
esac
d_ttyname_r=undef
ttyname_r_proto=0
;;
esac
;;
*) ttyname_r_proto=0
;;
esac

```

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/threads/d_ttyname_r.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_mkfifo.U 1 2006-08-24 12:32:52Z rmanfredi \$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic Licence,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic Licence; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:
?RCS: Original Author: Andy Dougherty <doughera@lafcol.lafayette.edu>
?RCS:
?RCS: \$Log: d_mkfifo.U,v \$
?RCS: Revision 3.0.1.1 1994/10/29 16:14:17 ram
?RCS: patch36: created by ADO
?RCS:
?RCS:
?MAKE:d_mkfifo: Inlibc
?MAKE: -pick add \$@ %<
?S:d_mkfifo:
?S: This variable conditionally defines the HAS_MKFIFO symbol, which
?S: indicates to the C program that the mkfifo() routine is available.
?S:.
?C:HAS_MKFIFO :
?C: This symbol, if defined, indicates that the mkfifo
routine is
?C: available to create FIFOs. Otherwise, mknod should be able to
?C: do it for you. However, if mkfifo is there, mknod might require
?C: super-user privileges which mkfifo will not.
?C:.
?H:#\$d_mkfifo HAS_MKFIFO /**/
?H:.
?LINT:set d_mkfifo
: see if mkfifo exists
set mkfifo d_mkfifo
eval \$inlibc

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/d_mkfifo.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: i_systypes.U 1 2006-08-24 12:32:52Z rmanfredi \$
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: \$Log: i_systypes.U,v \$
?RCS: Revision 3.0 1993/08/18 12:08:41 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?X:

?X: Look whether <sys/types.h> needs to be included.
?X:
?MAKE:i_systypes: Inhdr
?MAKE: -pick add \$@ %<
?S:i_systypes:
?S: This variable conditionally defines the I_SYS_TYPES symbol,
?S: and indicates whether a C program should include <sys/types.h>.
?S:.
?C:I_SYS_TYPES (I_SYSTYPES):
?C: This symbol, if defined, indicates to the C program
that it should
?C: include <sys/types.h>.
?C:.
?H:#\$i_systypes I_SYS_TYPES /**/
?H:.
?LINT:set i_systypes
: see if sys/types.h has to be included
set sys/types.h i_systypes
eval \$inhdr

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/i_systypes.U

No license file was found, but licenses were detected in source scan.

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?MAKE:d_round: Inlibc

?MAKE: -pick add \$@ %<

?S:d_round:

?S: This variable conditionally defines the HAS_ROUND symbol, which

?S: indicates to the C program that the round() routine is available.

?S:.

?C:HAS_ROUND:

?C: This symbol, if defined, indicates that the round routine is

?C: available to round to nearest integer, away from zero.

?C:.

?H:#\$d_round HAS_ROUND /**/
?H:.

?LINT:set d_round

: see if round exists

set round d_round

eval \$inlibc

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_round.U

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: i_stdlib.U 1 2006-08-24 12:32:52Z rmanfredi $
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: $Log: i_stdlib.U,v $
?RCS: Revision 3.0 1993/08/18 12:08:27 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:i_stdlib: Inhdr
?MAKE: -pick add $@ %<
?S:i_stdlib:
?S: This variable conditionally defines the I_STDLIB symbol, which
?S: indicates to the C program that <stdlib.h> exists and should
?S: be included.
?S:.
?C:I_STDLIB:
?C: This symbol, if defined, indicates that <stdlib.h> exists and should
?C: be included.
?C:.
?H:#$i_stdlib I_STDLIB /**/
?H:.
?LINT:set
i_stdlib
: see if stdlib is available
set stdlib.h i_stdlib
eval $inhdr
```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/i_stdlib.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: d_shmctl.U 1 2006-08-24 12:32:52Z rmanfredi $
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
```

?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: \$Log: d_shmctl.U,v \$
?RCS: Revision 3.0 1993/08/18 12:07:18 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:d_shmctl: Inlibc
?MAKE: -pick add \$@ %<
?S:d_shmctl:
?S: This variable conditionally defines the HAS_SHMCTL symbol, which
?S: indicates to the C program that the shmctl() routine is available.
?S:.
?C:HAS_SHMCTL:
?C: This symbol, if defined, indicates that the shmctl() routine is
?C: available to perform shared memory control operations.
?C:.
?H:#\$d_shmctl
HAS_SHMCTL /**/
?H:.
?LINT:set d_shmctl
: see if shmctl exists
set shmctl d_shmctl
eval \$inlibc

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/d_shmctl.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: \$Log: d_htonl.U,v \$
?RCS: Revision 3.0.1.2 1994/08/29 16:09:25 ram
?RCS: patch32: now properly handles htonl() and friends when macros (ADO)
?RCS:
?RCS: Revision 3.0.1.1 1994/05/06 14:45:00 ram
?RCS: patch23: now also check for htonl() macro (ADO)
?RCS:
?RCS: Revision 3.0 1993/08/18 12:06:22 ram
?RCS: Baseline for dist 3.0 netwide release.

```

?RCS:
?MAKE:d_htonl: Inlibc Setvar i_niin i_sysin cat rm contains \
  cppstdin cppflags cppminus
?MAKE: -pick add $@ %<
?S:d_htonl:
?S: This variable conditionally
  defines HAS_HTONL if htonl() and its
?S: friends are available to do network order byte swapping.
?S:.
?C:HAS_HTONL (HTONL):
?C: This symbol, if defined, indicates that the htonl() routine (and
?C: friends htons() ntohl() ntohs()) are available to do network
?C: order byte swapping.
?C:.
?C:HAS_HTONS (HTONS):
?C: This symbol, if defined, indicates that the htons() routine (and
?C: friends htonl() ntohl() ntohs()) are available to do network
?C: order byte swapping.
?C:.
?C:HAS_NTOHL (NTOHL):
?C: This symbol, if defined, indicates that the ntohl() routine (and
?C: friends htonl() htons() ntohs()) are available to do network
?C: order byte swapping.
?C:.
?C:HAS_NTOHS (NTOHS):
?C: This symbol, if defined, indicates that the ntohs() routine (and
?C: friends htonl() htons() ntohl()) are available to do network
?C: order byte swapping.
?C:.
?H:#$d_htonl HAS_HTONL /**/
?H:#$d_htonl HAS_HTONS /**/
?H:#$d_htonl HAS_NTOHL /**/
?H:#$d_htonl HAS_NTOHS /**/
?H:.
?F:!htonl.c
?LINT:set d_htonl
:
  see if htonl --and friends-- exists
val="
set htonl val
eval $inlibc

: Maybe they are macros.
case "$val" in
$undef)
  $cat >htonl.c <<EOM
#include <stdio.h>
#include <sys/types.h>

```

```

#$i_niin I_NETINET_IN
#$i_sysin I_SYS_IN
#ifdef I_NETINET_IN
#include <netinet/in.h>
#endif
#ifdef I_SYS_IN
#include <sys/in.h>
#endif
#ifdef htonl
printf("Defined as a macro.");
#endif
EOM
$cpptest $cpptest $cpptest < htonl.c >htonl.E 2>/dev/null
if $contains 'Defined as a macro' htonl.E >/dev/null 2>&1; then
    val="$define"
    echo "But it seems to be defined as a macro." >&4
fi
$rm -f htonl.?
;;
esac
set d_htonl
eval $setvar

```

Found in path(s):

```

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/d_htonl.U

```

No license file was found, but licenses were detected in source scan.

```

?RCS: $Id: voidflags.U,v 3.0.1.2 1997/02/28 16:27:58 ram Exp $
?RCS:
?RCS: Copyright (c) 1991-1993, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 3.0.
?RCS:
?RCS: $Log: voidflags.U,v $
?RCS: Revision 3.0.1.2 1997/02/28 16:27:58 ram
?RCS: patch61: don't prompt them if the void support is high enough for us
?RCS:
?RCS: Revision 3.0.1.1 1995/01/11 15:37:44 ram
?RCS: patch45: cosmetic change to avoid spurious blank lines when using -s
?RCS:
?RCS: Revision 3.0 1993/08/18 12:10:01 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:

```

```

?MAKE:voidflags defvoidused: cat rm_try contains +cc +ccflags package \
Oldconfig
Myread i_stdlib
?MAKE: -pick add $@ %<
?S:voidflags:
?S: This variable contains the eventual value of the VOIDFLAGS symbol,
?S: which indicates how much support of the void type is given by this
?S: compiler. See VOIDFLAGS for more info.
?S:.
?S:defvoidused:
?S: This variable contains the default value of the VOIDUSED symbol (15).
?S:.
?X: Exceptionally, we have to explicitly alias the symbol name for
?X: config_h.SH, otherwise the comment would not appear.
?C:VOIDFLAGS ~ %<:
?C: This symbol indicates how much support of the void type is given by this
?C: compiler. What various bits mean:
?C:
?C: 1 = supports declaration of void
?C: 2 = supports arrays of pointers to functions returning void
?C: 4 = supports comparisons between pointers to void functions and
?C: addresses of void functions
?C: 8 = supports declaration of generic void pointers
?C:
?C: The package designer should define VOIDUSED to indicate the requirements
?C: of the package. This can be done either
?C: by #defining VOIDUSED before
?C: including config.h, or by defining defvoidused in Myinit.U. If the
?C: latter approach is taken, only those flags will be tested. If the
?C: level of void support necessary is not present, defines void to int.
?C:.
?H:%<:#ifndef VOIDUSED
?H:%<:#define VOIDUSED $defvoidused
?H:%<:#endif
?H:%<:#define VOIDFLAGS $voidflags
?H:%<:#if (VOIDFLAGS & VOIDUSED) != VOIDUSED
?H:%<:#define void int /* is void to be avoided? */
?H:%<:#define M_VOID /* Xenix strikes again */
?H:%<:#endif
?H:.
?INIT:: full support for void wanted by default
?INIT:defvoidused=15
?INIT:
?LINT:known void M_VOID VOIDUSED
: check for void type
echo " "
echo "Checking to see how well your C compiler groks the void type..." >&4
case "$voidflags" in

```

```

")
$cat >try.c <<EOCP
#$i_stdlib I_STDLIB
#ifdef I_STDLIB
#include <stdlib.h>
#endif
#if TRY & 1
void sub() {
#else
sub() {
#endif
extern void moo(); /* function returning void */
void (*goo)(); /* ptr to func returning void
*/
#if TRY & 8
void *hue; /* generic ptr */
#endif
#if TRY & 2
void (*foo[10])();
#endif

#if TRY & 4
if(goo == moo) {
    exit(0);
}
#endif
exit(0);
}
int main() { sub(); }
EOCP
?X: This unit used to use cc -S in those tests to try to speed up things, but
?X: unfortunately, AIX 3.2 does not support this option.
if $cc $ccflags -c -DTRY=$defvoidused try.c >.out 2>&1 ; then
    voidflags=$defvoidused
    echo "Good. It appears to support void to the level $package wants.">&4
    if $contains warning .out >/dev/null 2>&1; then
        echo "However, you might get some warnings that look like this:"
        $cat .out
    fi
else
echo "Hmm, your compiler has some difficulty with void. Checking further..." >&4
if $cc $ccflags -c -DTRY=1 try.c >/dev/null 2>&1; then
    echo "It supports 1..."
if $cc $ccflags -c -DTRY=3 try.c >/dev/null 2>&1; then
    echo "It also supports 2..."
if $cc $ccflags -c -DTRY=7 try.c >/dev/null 2>&1; then
    voidflags=7
    echo "And it supports 4 but not 8 definitely."

```

```

else
echo
"It doesn't support 4..."
if $cc $ccflags -c -DTRY=11 try.c >/dev/null 2>&1; then
voidflags=11
echo "But it supports 8."
else
voidflags=3
echo "Neither does it support 8."
fi
fi
else
echo "It does not support 2..."
if $cc $ccflags -c -DTRY=13 try.c >/dev/null 2>&1; then
voidflags=13
echo "But it supports 4 and 8."
else
if $cc $ccflags -c -DTRY=5 try.c >/dev/null 2>&1; then
voidflags=5
echo "And it supports 4 but has not heard about 8."
else
echo "However it supports 8 but not 4."
fi
fi
fi
else
echo "There is no support at all for void."
voidflags=0
fi
fi
esac
?X: Only prompt user if support does not match the level we want
case "$voidflags" in
"$defvoidused") ;;
*) $cat >&4 <<'EOM'
Support flag bits are:
1: basic void declarations.
2: arrays of pointers to functions returning void.
4: operations between pointers to and addresses of
void functions.
8: generic void pointers.
EOM
dflt="$voidflags";
rp="Your void support flags add up to what?"
./myread
voidflags="$ans"
;;
esac

```

\$rm_try

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/modified/voidflags.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: Warn_v7ND.U 1 2006-08-24 12:32:52Z rmanfredi \$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic Licence,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic Licence; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: Warn_v7ND.U,v \$

?RCS: Revision 3.0.1.1 1994/10/29 16:01:46 ram

?RCS: patch36: call ./v7 explicitly instead of relying on PATH

?RCS:

?RCS: Revision 3.0 1993/08/18 12:05:18 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?X:

?X: This unit warns V7 sites that they may not have a non-blocking read.

?X: This unit needs to be mentioned in End.U to get included.

?X:

?MAKE:Warn_v7ND: package Guess

?MAKE: -pick add \$@ %<

: Warnings

if ./v7; then

cat

<<EOM

NOTE: many V7 systems do not have a way to do a non-blocking read. If you don't have any of FIONREAD, O_NDELAY, or rdchk(), the \$package package may not work as well as it might. It might not work at all.

EOM

fi

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/Warn_v7ND.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: package.U 1 2006-08-24 12:32:52Z rmanfredi \$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: package.U,v \$

?RCS: Revision 3.0.1.3 1994/10/29 16:27:21 ram

?RCS: patch36: beware of non-ascii character sets when translating case

?RCS:

?RCS: Revision 3.0.1.2 1993/11/10 17:37:02 ram

?RCS: patch14: skip definition of spackage if not otherwise used

?RCS:

?RCS: Revision 3.0.1.1 1993/09/13 16:11:10 ram

?RCS: patch10: added spackage, suitable for starting sentences

?RCS:

?RCS: Revision 3.0 1993/08/18 12:09:28 ram

?RCS: Baseline for dist 3.0
netwide release.

?RCS:

?MAKE:package spackage: Nothing

?MAKE: -pick wipe \$@ %<

?S:package:

?S: This variable contains the name of the package being constructed.
?S: It is primarily intended for the use of later Configure units.

?S:.

?S:spackage:

?S: This variable contains the name of the package being constructed,
?S: with the first letter uppcased, i.e. suitable for starting
?S: sentences.

?S:.

?X: dist-4 has defined PACKAGE: here, which clashes with perl.h
?X: as package is a reserved keyword in perl

?T:first last
: set package name
package='<PACKAGENAME>'
@if spackage
first=`echo \$package | sed -e 's/^(.).*\1/'
last=`echo \$package | sed -e 's/^(.*)\1/'

?X:

?X: So early in the Configure script, we don't have ./tr set up and can't
?X: include Tr in our dependency or that would create a cycle. Therefore,
?X: we have to somehow duplicate the work done in Tr. That's life.

?X:
case ``echo AbyZ | tr '[:lower:]' '[:upper:]' 2>/dev/null``-``echo AbyZ | tr '[:upper:]' '[:lower:]'

```
2>/dev/null" in
ABYZ-abyz) spackage=`echo $first | tr '[:lower:]' '[:upper:]'`$last;;
*) spackage=`echo $first | tr '[a-z]' '[A-Z]'`$last;;
esac
@end
```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/modified/package.U
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1998 Jarkko Hietaniemi

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?MAKE:d_atolf: Inlibc

?MAKE: -pick add \$@ %<

?S:d_atolf:

?S: This variable conditionally defines the HAS_ATOLF symbol, which

?S: indicates to the C program that the atolf() routine is available.

?S:.

?C:HAS_ATOLF:

?C: This symbol, if defined, indicates that the atolf routine is

?C: available to convert strings into long doubles.

?C:.

?H:#\$d_atolf HAS_ATOLF /**/

?H:.

?LINT:set d_atolf

: see if atolf exists

set atolf d_atolf

eval \$inlibc

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/perl/atolf.U
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_scorfl.U 1 2006-08-24 12:32:52Z rmanfredi \$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic Licence,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic Licence; a copy of which may be found at the root

```

?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: $Log: d_scorfl.U,v $
?RCS: Revision 3.0 1993/08/18 12:07:01 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:d_scorfl: cat Myread Oldconfig nametype Setvar
?MAKE: -pick add $@ %<
?S:d_scorfl:
?S: This variable conditionally defines the SCOREFULL symbol, which
?S: indicates to the C program that any scoreboard kept by the program
?S: should be kept on the basis of the user's full name as opposed to
?S: the user's login name.
?S:.
?C:SCOREFULL:
?C: This
symbol, if defined, indicates that any scoreboard kept by the
?C: program should be kept on the basis of the user's full name as opposed
?C: to the user's login name. If the user can change his full name he
?C: can enter multiple scores if this is defined.
?C:.
?H:#$d_scorfl SCOREFULL /**/
?H:.
?LINT:set d_scorfl
: see how they want the scoreboard kept
case "$d_scorfl" in
"$define") dflt=y ;;
*) dflt=n ;;
esac
case "$nametype" in
other) val="$undef" ;;
*)
$cat <<'EOM'

```

The scoreboard can be kept with one score per login name, or one score per full name. If users can change their full name, or if there is more than one person on your system with the same full name, you should keep the score by login name (the full name is still printed).

EOM

```

rp='Do you want the scoreboard kept by full name?'
. ./myread
case "$ans" in
y*) val="$define" ;;
*) val="$undef" ;;
esac
;;
esac

```

```
set d_scorfl
eval $setvar
```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/d_scorfl.U
```

No license file was found, but licenses were detected in source scan.

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?MAKE:d_lrintl: Inlibc

?MAKE: -pick add \$@ %<

?S:d_lrintl:

?S: This variable conditionally defines the HAS_LRINTL symbol, which

?S: indicates to the C program that the lrintl() routine is available

?S: to return the integral value closest to a long double (according

?S: to the current rounding mode).

?S:.

?C:HAS_LRINTL:

?C: This symbol, if defined, indicates that the lrintl routine is

?C: available to return the integral value closest to a long double

?C: (according to the current rounding mode).

?C:.

?H:#\$d_lrintl HAS_LRINTL /**/

?H:.

?LINT:set d_lrintl

: see if lrintl exists

set lrintl d_lrintl

eval \$inlibc

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/perl/d_lrintl.U
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: Warn.U 1 2006-08-24 12:32:52Z rmanfredi \$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic Licence,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic Licence; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: Extract.U,v \$

?X:

?X: This unit produces a shell script which can be run in order to emit
?X: an important warning to the user, which will be remembered and shown
?X: at the end of the Configure run as well.
?X:
?X: A typical use would be:
?X:
?X: ./warn <<EOM
?X: Problem with your C compiler: can't turn debugging on.
?X: EOM
?X:
?X: or:
?X:
?X: ./warn "Problem with your C compiler: can't turn debugging on."
?X:
?X: Which will both display to the user:
?X:
?X: ***
WARNING:
?X: *** Problem with your C compiler: can't turn debugging on.
?X: ***
?X:
?MAKE:Warn: startsh eunicefix
?MAKE: -pick add \$@ %<
?F:./warn
: script used to emit important warnings
cat >warn <<EOS
\$startsh
?X: Read the whole warning message from stdin into a temporary file
?X: when no argument was supplied.
if test \$# -gt 0; then
echo "\\$@" >msg
else
cat >msg
fi
?X: Emit the warning, prefixing all lines with '*** '
echo "*** WARNING:" >&4
sed -e 's/^/*** /' <msg >&4
echo "*** " >&4
?X: Save the warning in the logs, which will be shown again at the end
cat msg >>config.msg
echo " " >>config.msg
rm -f msg
EOS
chmod +x warn
\$eunicefix warn

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-

debian-perl-5.26.1/dist/U/Warn.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: Protochk.U,v \$

?RCS:

?RCS: Copyright (c) 1998 Andy Dougherty

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?X: This unit generates a ./protochk script that is used internally

?X: by Configure to check if this system will accept a particular

?X: prototype.

?X:

?X: To use it, say something like:

?X: hdrs="\$define sys/types.h

?X: \$i_systime sys/time.h

?X: \$i_sysselect sys/select.h

?X: \$d_socket sys/socket.h"

?X: \$xxx='fd_set *'

?X: try='extern int select _((int, \$xxx, \$xxx, \$xxx, struct timeval *));'

?X: if ./protochk "\$try" \$hdrs; then

?X: echo "Your system accepts \$xxx for the arguments to select."

?X: fi

?X: (Of course select is harder, since the first arg can be int,

?X: size_t, or unsigned long, and the last arg may or may not have a

?X: 'const' before the 'struct timeval' :-(. Also SunOS

4.1.3 doesn't

?X: provide a select prototype so the compiler accepts anything :-).

?X:

?X: The C compiler on QNX warns about invalid pointer types, but

?X: still exits with a 0 exit status, so it's not much help here.

?X: (It does correctly detect incorrect non-pointer arguments).

?X: Still, since QNX is a POSIX-ish system, just make your first

?X: a POSIX-ish one, and QNX will probably accept it.

?X:

?X: For determining argument types, your compiler must support

?X: prototypes, and the header files must use them. Determining

?X: return types, however, is easier. Just give an ridiculous

?X: return type, something like

?X: ./protochk 'extern int atof _((void));' \$i_stdlib stdlib.h

?X: that should surely fail if atof() is defined in <stdlib.h>

?X:

?X: There is also an 'escape' hatch built in. If you have a pair

?X: of args 'literal 'stuff' then 'stuff' gets included literally

?X: into the test program. This could be useful for doing something

?X: like

?X: hdrs="\$define stdio.h

```

?X: $define
    sys/types.h"
?X: ./protochk 'extern int fsetpos(FILE *, Fpos_t);' $args \
?X: 'literal' #define Fpos_t long long'
?X: but you have to be really careful about the spaces in "literal".
?X:
?X: Andy Dougherty Feb. 1998
?MAKE:Protochk: cat rm_try startsh eunicefix +cc +optimize +ccflags \
    prototype i_pthread usethreads
?MAKE: -pick add $@ %<
?F:./protochk
?X: Comfort metalint. All these are actually used in the protochk script.
?T:foo status pthread_h_done
?LINT: change cc optimize ccflags prototype define rm_try
?LINT: extern pthread_h_first
?LINT: change pthread_h_first
?LINT: change usethreads
?LINT: change i_pthread
: define a function to check prototypes
$cat > protochk <<EOSH
$startsh
cc="$cc"
optimize="$optimize"
ccflags="$ccflags"
prototype="$prototype"
define="$define"
rm_try="$rm_try"
usethreads=$usethreads
i_pthread=$i_pthread
pthread_h_first=$pthread_h_first
EOSH

$cat >> protochk <<'EOSH'

$rm_try
foo="$1"
shift
while test $# -ge 2; do
    case "$1" in
        $define)
            echo "#include <$2>" >> try.c ;;
        literal) echo "$2" >> try.c ;;
    esac
    # Extra magic for the benefit of systems that need pthread.h
    # to be included early to correctly detect threadsafe functions.
    # Such functions must guarantee themselves, though, that the usethreads
    # and i_pthread have been defined, before calling protochk.
    if test "$usethreads" = "$define" -a "$i_pthread" = "$define" -a "$pthread_h_first" = "$define" -a

```

```

"$pthread_h_done" = ""; then
echo "#include <pthread.h>" >> try.c
pthread_h_done=yes
fi
shift 2
done
test "$prototype" = "$define" && echo '#define CAN_PROTOTYPE' >> try.c
cat >> try.c <<'EOCP'
#ifdef CAN_PROTOTYPE
#define _(args) args
#else
#define _(args) ()
#endif
EOCP
echo "$foo" >> try.c
?X: Just so we have something to compile.
echo 'int no_real_function_has_this_name _((void)) { return 0; }' >> try.c
$cc $optimize $ccflags -c try.c > /dev/null 2>&1
status=$?
$rm_try
exit $status
EOSSH
chmod +x protochk
$unicefix protochk

```

Found

in path(s):

```

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/protos/Protochk.U

```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 2000 Jarkko Hietaniemi

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?MAKE:d_utimes: Inlibc

?MAKE: -pick add \$@ %<

?S:d_utimes:

?S: This variable conditionally defines the HAS_UTIMES symbol, which

?S: indicates to the C program that the utimes() routine is available.

?S:.

?C:HAS_UTIMES:

?C: This symbol, if defined, indicates that the utimes routine is

?C: available to do change file time stamps using struct timevals.

?C:.

?H:#\$d_utimes HAS_UTIMES /**/

?H:.

?LINT:set d_utimes

: see if utimes exists

set utimes d_utimes

eval \$inlibc

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_utimes.U

No license file was found, but licenses were detected in source scan.

* Feel free to modify any of this as the need arises. Note, however,

Found in path(s):

* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/metaconfig.html

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 2002 Jarkko Hietaniemi

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?MAKE:usecjk: Myread Oldconfig Setvar

?MAKE: -pick add \$@ %<

?Y:TOP

?S:usecjk:

?S: This variable conditionally defines the USE_CJK symbol,

?S: and indicates that Perl should be built to use CJK.

?S:.

?C:USE_CJK:

?C: This symbol, if defined, indicates that Perl should

?C: be built to use the CJK support of Encode.

?C:.

?H:%<:#ifndef USE_CJK

?H:%<:#\$usecjk USE_CJK /**/

?H:%<:#endif

?H:.

?LINT:set usecjk

?INIT:: set usecjk on the Configure command line to enable cjk.

?X: We should really have some explanatory text here, and some

?X: automatic setting of sensible defaults.

: Check for CJK support

case "\$usecjk" in

"|\$define|true|[yY]*) dflt='y';;

```
*) dflt='n';;
esac
cat <<EOM
```

Starting from 5.8.0 Perl comes

with encoding support for the CJK languages (Chinese-Japanese-Korean, CN/JP/KR/TW). Normally shared libraries are used, which means that the (relatively large, a few megabytes total) CJK encodings are loaded on demand (not consuming any memory if they are unused). However, if you are building Perl statically, and/or are space-constrained, and if you are certain you won't be needing CJK support, you may consider leaving it out. Note that the CJK support will always be built, but if you choose not to have it, it will be skipped in the installation phase.

If this doesn't make any sense to you, just accept the default '\$dflt'.

EOM

```
rp='Build Perl for CJK?'
./myread
case "$ans" in
y*|Y*) val="$define" ;;
*)    val="$undef" ;;
esac
set usecjk
eval $setvar
```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/usecjk.U
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 2000 Jarkko Hietaniemi

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?MAKE:d_mkstemp: Inlibc

?MAKE: -pick add \$@ %<

?S:d_mkstemp:

?S: This variable conditionally defines the HAS_MKSTEMPS symbol, which

?S: indicates to the C program that the mkstemp() routine is available

?S: to exclusively create and open a uniquely named (with a suffix)

?S: temporary file.

?S:.

?C:HAS_MKSTEMPS :

?C: This symbol, if defined, indicates that the mkstemp routine is

?C: available to exclusively create and open a uniquely named

```
?C: (with a suffix) temporary file.
?C:.
?H:#$d_mkstemp HAS_MKSTEMPS /**/
?H:.
?LINT:set d_mkstemp
: see if mkstemp exists
set mkstemp d_mkstemp
eval $inlibc
```

Found in path(s):

```
* /opt/cola/permits/1446828411_1666316498.6193252/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/perl/d_mkstemp.U
```

1.94 perl-base 5.26.1-6ubuntu0.6

1.94.1 Available under license :

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id$
?RCS:
?RCS: Copyright (c) 2004 H.Merijn Brand
?RCS:
?RCS: You may distribute under the terms of either the GNU General Public
?RCS: License or the Artistic License, as specified in the README file.
?RCS:
?MAKE:d_strlcpy: Inlibc
?MAKE: -pick add $@ %<
?S:d_strlcpy:
?S: This variable conditionally defines the HAS_STRLCPY symbol, which
?S: indicates to the C program that the strlcpy () routine is available.
?S:.
?C:HAS_STRLCPY:
?C: This symbol, if defined, indicates that the strlcpy () routine is
?C: available to do string copying.
?C:.
?H:#$d_strlcpy HAS_STRLCPY /**/
?H:.
?LINT:set d_strlcpy
: see if strlcpy exists
set strlcpy d_strlcpy
eval $inlibc
```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/perl/d_strlcpy.U
```

No license file was found, but licenses were detected in source scan.

```

?RCS: $Id: i_vfork.U 1 2006-08-24 12:32:52Z rmanfredi $
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: $Log: i_vfork.U,v $
?RCS: Revision 3.0.1.1 1994/05/06 15:05:44 ram
?RCS: patch23: avoid inclusion of <vfork.h> if no vfork() used (ADO)
?RCS:
?RCS: Revision 3.0 1993/08/18 12:08:50 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:i_vfork: Inhdr d_vfork
?MAKE:-pick add $@ %<
?S:i_vfork:
?S: This variable conditionally defines the I_VFORK symbol, and indicates
?S: whether a C program should include vfork.h.
?S:.
?C:I_VFORK:
?C: This symbol,
if defined, indicates to the C program that it should
?C: include vfork.h.
?C:.
?H:#$i_vfork I_VFORK /**/
?H:.
: see if this is a vfork system
case "$d_vfork" in
"$define")
set vfork.h i_vfork
eval $inhdr
;;
*)
i_vfork="$undef"
;;
esac

```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/i_vfork.U
```

No license file was found, but licenses were detected in source scan.

```

?RCS: $Id: d_mbtowc.U 1 2006-08-24 12:32:52Z rmanfredi $
?RCS:

```

```

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: $Log: d_mbtowc.U,v $
?RCS: Revision 3.0 1993/08/18 12:06:30 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:d_mbtowc: Inlibc
?MAKE: -pick add $@ %<
?S:d_mbtowc:
?S: This variable conditionally defines the HAS_MBTOWC symbol, which
?S: indicates to the C program that the mbtowc() routine is available
?S: to convert multibyte to a wide character.
?S:.
?C:HAS_MBTOWC (MBTOWC):
?C: This symbol, if defined, indicates that the mbtowc routine is available
?C: to
convert a multibyte to a wide character.
?C:.
?H:#$d_mbtowc HAS_MBTOWC /**/
?H:.
?LINT:set d_mbtowc
: see if mbtowc exists
set mbtowc d_mbtowc
eval $inlibc

```

Found in path(s):

```

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/d_mbtowc.U

```

No license file was found, but licenses were detected in source scan.

```

?RCS: $Id: d_mktime.U 1 2006-08-24 12:32:52Z rmanfredi $
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: Original Author: Andy Dougherty <doughera@lafcol.lafayette.edu>
?RCS:

```

?RCS: \$Log: d_mktime.U,v \$
?RCS: Revision 3.0.1.1 1994/08/29 16:09:44 ram
?RCS: patch32: created by ADO
?RCS:
?MAKE:d_mktime: Inlibc
?MAKE: -pick add \$@ %<
?S:d_mktime:
?S: This variable conditionally defines the HAS_MKTIME symbol, which
?S: indicates to the C program that the mktime() routine is available.
?S:.
?C:HAS_MKTIME :
?C: This symbol, if defined, indicates that the mktime routine
is
?C: available.
?C:.
?H:#\$d_mktime HAS_MKTIME /**/
?H:.
?LINT:set d_mktime
: see if mktime exists
set mktime d_mktime
eval \$inlibc

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/d_mktime.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$
?RCS:
?RCS: Copyright (c) 2000 Jarkko Hietaniemi
?RCS:
?RCS: You may distribute under the terms of either the GNU General Public
?RCS: License or the Artistic License, as specified in the README file.
?RCS:
?MAKE:d_setitimer: Inlibc
?MAKE: -pick add \$@ %<
?S:d_setitimer:
?S: This variable conditionally defines the HAS_SETTIMER symbol, which
?S: indicates to the C program that the setitimer() routine is available.
?S:.
?C:HAS_SETTIMER:
?C: This symbol, if defined, indicates that the setitimer routine is
?C: available to set interval timers.
?C:.
?H:#\$d_setitimer HAS_SETTIMER /**/
?H:.
?LINT:set d_setitimer
: see if setitimer exists

```
set setitimer d_setitimer
eval $inlibc
```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/perl/d_setitimer.U
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1999, Jarkko Hietaniemi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 3.0.

?RCS:

?MAKE:d_sem_close: Inlibc

?MAKE: -pick add \$@ %<

?S:d_sem_close:

?S: This variable conditionally defines HAS_SEM_CLOSE if sem_close() is

?S: available to close a POSIX semaphore.

?S:.

?C:HAS_SEM_CLOSE:

?C: This symbol, if defined, indicates that the sem_close system call is

?C: available to close a POSIX semaphore.

?C:.

?H:#\$d_sem_close HAS_SEM_CLOSE /**/

?H:.

?LINT:set d_sem_close

: see if sem_close exists

set sem_close d_sem_close

eval \$inlibc

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/perl/d_sem_close.U
```

No license file was found, but licenses were detected in source scan.

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?MAKE:d_fmin: Inlibc

?MAKE: -pick add \$@ %<

?S:d_fmin:

?S: This variable conditionally defines the HAS_FMIN symbol, which

?S: indicates to the C program that the fmin() routine is available.

?S:
?C:HAS_FMIN:
?C: This symbol, if defined, indicates that the fmin routine is
?C: available to do the minimum function.

?C:
?H:#\$d_fmin HAS_FMIN /**/

?H:
?LINT:set d_fmin
: see if fmin exists
set fmin d_fmin
eval \$inlibc

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_fmin.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: \$Log: so.U,v \$
?RCS: Revision 3.0.1.2 1994/10/29 16:30:04 ram
?RCS: patch36: now tells user how he can suppress shared lib lookup (ADO)
?RCS: patch36: removed echo at the top, since it's now in the here-doc (ADO)
?RCS:
?RCS: Revision 3.0.1.1 1994/06/20 07:07:02 ram
?RCS: patch30: created
?RCS:
?X:
?X: This unit computes the shared-object / shared-lib extension
?X:
?MAKE:so: test libpth Loc Myread Oldconfig cat
?MAKE: -pick add \$@ %<
?S:so:
?S: This variable holds the extension used to identify
shared libraries
?S: (also known as shared objects) on the system. Usually set to 'so'.
?S:
?T: xxx
: compute shared library extension
case "\$so" in

```

")
if xxx=`./loc libc.sl X $libpth`; $test -f "$xxx"; then
  dflt='sl'
else
  dflt='so'
fi
;;
*) dflt="$so";;
esac
$cat <<EOM

```

On some systems, shared libraries may be available. Answer 'none' if you want to suppress searching of shared libraries for the remainder of this configuration.

```

EOM
rp='What is the file extension used for shared libraries?'
./myread
so="$ans"

```

Found in path(s):

```

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/so.U

```

No license file was found, but licenses were detected in source scan.

?RCS: Copyright (c) 2016 Dagfinn Ilmari Mannsker & H.Merijn Brand

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

```

?MAKE:d_siginfo_si_errno d_siginfo_si_pid d_siginfo_si_uid d_siginfo_si_addr d_siginfo_si_status
d_siginfo_si_band d_siginfo_si_value d_siginfo_si_fd: d_sigaction pidtype uidtype Hasfield_t

```

?MAKE: -pick add \$@ %<

?S:d_siginfo_si_errno:

?S: This variable conditionally defines the HAS_SIGINFO_SI_ERRNO symbol,

?S: which indicates that the siginfo_t struct has the si_errno member.

?S:.

?S:d_siginfo_si_pid:

?S: This variable conditionally defines the HAS_SIGINFO_SI_PID symbol,

?S: which indicates that the siginfo_t struct has the si_pid member.

?S:.

?S:d_siginfo_si_uid:

?S: This variable conditionally defines the HAS_SIGINFO_SI_UID symbol,

?S: which indicates that the siginfo_t struct has the si_uid member.

?S:.

?S:d_siginfo_si_addr:

?S: This

variable conditionally defines the HAS_SIGINFO_SI_ADDR symbol,
?S: which indicates that the siginfo_t struct has the si_addr member.
?S:.
?S:d_siginfo_si_status:
?S: This variable conditionally defines the HAS_SIGINFO_SI_STATUS symbol,
?S: which indicates that the siginfo_t struct has the si_status member.
?S:.
?S:d_siginfo_si_band:
?S: This variable conditionally defines the HAS_SIGINFO_SI_BAND symbol,
?S: which indicates that the siginfo_t struct has the si_band member.
?S:.
?S:d_siginfo_si_value:
?S: This variable conditionally defines the HAS_SIGINFO_SI_VALUE symbol,
?S: which indicates that the siginfo_t struct has the si_value member.
?S:.
?S:d_siginfo_si_fd:
?S: This variable conditionally defines the HAS_SIGINFO_SI_FD symbol,
?S: which indicates that the siginfo_t struct has the si_fd member.
?S:.
?C:HAS_SIGINFO_SI_ERRNO:
?C: This symbol, if defined, indicates that siginfo_t has the
?C: si_errno member
?C:.
?C:HAS_SIGINFO_SI_PID:
?C: This
symbol, if defined, indicates that siginfo_t has the
?C: si_pid member
?C:.
?C:HAS_SIGINFO_SI_UID:
?C: This symbol, if defined, indicates that siginfo_t has the
?C: si_uid member
?C:.
?C:HAS_SIGINFO_SI_ADDR:
?C: This symbol, if defined, indicates that siginfo_t has the
?C: si_addr member
?C:.
?C:HAS_SIGINFO_SI_STATUS:
?C: This symbol, if defined, indicates that siginfo_t has the
?C: si_status member
?C:.
?C:HAS_SIGINFO_SI_BAND:
?C: This symbol, if defined, indicates that siginfo_t has the
?C: si_band member
?C:.
?C:HAS_SIGINFO_SI_VALUE:
?C: This symbol, if defined, indicates that siginfo_t has the
?C: si_value member
?C:.

?C:HAS_SIGINFO_SI_FD:

?C: This symbol, if defined, indicates that siginfo_t has the

?C: si_fd member

?C:.

?H:#\$d_siginfo_si_errno HAS_SIGINFO_SI_ERRNO /**/

?H:#\$d_siginfo_si_pid HAS_SIGINFO_SI_PID /**/

?H:#\$d_siginfo_si_uid HAS_SIGINFO_SI_UID /**/

?H:#\$d_siginfo_si_addr HAS_SIGINFO_SI_ADDR /**/

?H:#\$d_siginfo_si_status HAS_SIGINFO_SI_STATUS /**/

?H:#\$d_siginfo_si_band HAS_SIGINFO_SI_BAND /**/

?H:#\$d_siginfo_si_value HAS_SIGINFO_SI_VALUE /**/

?H:#\$d_siginfo_si_fd HAS_SIGINFO_SI_FD /**/

?H:.

:

see what siginfo fields we have

case "\$d_sigaction" in

"\$define")

echo "Checking if your siginfo_t has si_errno field...">&4

set d_siginfo_si_errno siginfo_t int si_errno \$d_sigaction signal.h

eval \$hasfield_t;

echo "Checking if your siginfo_t has si_pid field...">&4

set d_siginfo_si_pid siginfo_t \$pidtype si_pid \$d_sigaction signal.h

eval \$hasfield_t;

echo "Checking if your siginfo_t has si_uid field...">&4

set d_siginfo_si_uid siginfo_t \$uidtype si_uid \$d_sigaction signal.h

eval \$hasfield_t;

echo "Checking if your siginfo_t has si_addr field...">&4

set d_siginfo_si_addr siginfo_t "void *" si_addr \$d_sigaction signal.h

eval \$hasfield_t;

echo "Checking if your siginfo_t has si_status field...">&4

set d_siginfo_si_status siginfo_t int si_status \$d_sigaction signal.h

eval \$hasfield_t;

echo "Checking if your siginfo_t has si_band field...">&4

set

d_siginfo_si_band siginfo_t long si_band \$d_sigaction signal.h

eval \$hasfield_t;

echo "Checking if your siginfo_t has si_value field...">&4

set d_siginfo_si_value siginfo_t "union sigval" si_value \$d_sigaction signal.h

eval \$hasfield_t;

echo "Checking if your siginfo_t has si_fd field...">&4

set d_siginfo_si_fd siginfo_t int si_fd \$d_sigaction signal.h

```
eval $hasfield_t;

;;
*)
d_siginfo_si_errno="$undef"
d_siginfo_si_pid="$undef"
d_siginfo_si_uid="$undef"
d_siginfo_si_addr="$undef"
d_siginfo_si_status="$undef"
d_siginfo_si_band="$undef"
d_siginfo_si_value="$undef"
d_siginfo_si_fd="$undef"
;;
esac
```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/compline/d_siginfo_si.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: i_sysuio.U,v $
?RCS:
?RCS: Copyright (c) 1998 Jarkko Hietaniemi
?RCS:
?RCS: You may distribute under the terms of either the GNU General Public
?RCS: License or the Artistic License, as specified in the README file.
?RCS:
?MAKE:i_sysuio: Inhdr
?MAKE: -pick add $@ %<
?S:i_sysuio:
?S: This variable conditionally defines the I_SYSUIO symbol, and indicates
?S: whether a C program should include <sys/uio.h>.
?S:.
?C:I_SYSUIO:
?C: This symbol, if defined, indicates that <sys/uio.h> exists and
?C: should be included.
?C:.
?H:#$i_sysuio I_SYSUIO /**/
?H:.
?LINT:set i_sysuio
: see if this is a sys/uio.h system
set sys/uio.h i_sysuio
eval $inhdr
```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/modified/i_sysuio.U
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: cpp_stuff.U,v \$

?RCS: Revision 3.0.1.2 1997/02/28 15:30:48 ram

?RCS: patch61: added cute quoting trick for wild stringify support

?RCS:

?RCS: Revision 3.0.1.1 1994/10/29 16:08:24 ram

?RCS: patch36: now uses cppstdin instead of plain cpp for consistency (ADO)

?RCS: patch36: remove temporary files when done

?RCS:

?RCS: Revision 3.0 1993/08/18 12:05:36 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?MAKE:cpp_stuff cpp_quote: cat contains cppstdin cppflags cppminus rm Warn \
package

?MAKE: -pick

add \$@ %<

?S:cpp_stuff:

?S: This variable contains an identification of the catenation mechanism

?S: used by the C preprocessor.

?S:.

?S:cpp_quote:

?S: This variable is set to either "" or " depending on whether the

?S: pre-processor pre-dates ANSI or not. It is used in the production of

?S: the SQuoTe() and EQuoTe() macros, and was introduced to overcome a bug

?S: in gcc 3.x whereby the pre-processor complained loudly about the

?S: unterminated strings.

?S:.

?C:CAT2:

?C: This macro catenates 2 tokens together.

?C:.

?C:CAT3:

?C: This macro catenates 3 tokens together.

?C:.

?C:CAT4:

?C: This macro catenates 4 tokens together.

?C:.

?C:CAT5:

?C: This macro catenates 5 tokens together.

?C:.

?C:STRINGIFY:

?C: This macro surrounds its token with double quotes.

?C:.

?C:SCAT2:

?C: This macro catenates 2 tokens together and stringifies the result.

?C:.

?C:SCAT3:

?C: This macro catenates 3 tokens together and stringifies the result.

?C:.

?C:SCAT4:

?C: This macro catenates 4 tokens together and stringifies the result.

?C:.

?C:SCAT5:

?C: This macro catenates 5 tokens together and stringifies the result.

?C:.

```
?H:%<:#if $cpp_stuff == 1
?H:?CAT2:#define CAT2(a,b)a/**/b
?H:?CAT3:#define CAT3(a,b,c)a/**/b/**/c
?H:?CAT4:#define CAT4(a,b,c,d)a/**/b/**/c/**/d
?H:?CAT5:#define CAT5(a,b,c,d,e)a/**/b/**/c/**/d/**/e
?H:?STRINGIFY:#define STRINGIFY(a)"a"
?H:%<:#define SQuoTe(a){cpp_quote}a
?H:%<:#define EQuoTe(a)a${cpp_quote}
?H:?SCAT2:#define SCAT2(a,b)EQuoTe(SQuoTe(a)b)
?H:?SCAT3:#define SCAT3(a,b,c)EQuoTe(SQuoTe(a)b/**/c)
?H:?SCAT4:#define SCAT4(a,b,c,d)EQuoTe(SQuoTe(a)b/**/c/**/d)
?H:?SCAT5:#define SCAT5(a,b,c,d,e)EQuoTe(SQuoTe(a)b/**/c/**/d/**/e)
?H:%<:#endif
?H:%<:#if $cpp_stuff == 42
?X: The additional level of indirection enables these macros to be
?X: used as arguments to other macros. See K&R 2nd ed., page 231.
?H:%<:#define CaTiFy(a,b) a ## b
?H:%<:#define CAT2(a,b) CaTiFy(a,b)
?H:?CAT3:#define CAT3(a,b,c) CAT2(CaTiFy(a,b),c)
?H:?CAT4:#define CAT4(a,b,c,d)
CAT2(CaTiFy(a,b), CaTiFy(c,d))
?H:?CAT5:#define CAT5(a,b,c,d,e) CAT2(CAT2(CaTiFy(a,b), CaTiFy(c,d)), e)
?H:%<:#define StGiFy(a)# a
?H:?STRINGIFY:#define STRINGIFY(a)StGiFy(a)
?H:?SCAT2:#define SCAT2(a,b)StGiFy(a) StGiFy(b)
?H:?SCAT3:#define SCAT3(a,b,c)StGiFy(a) StGiFy(b) StGiFy(c)
?H:?SCAT4:#define SCAT4(a,b,c,d)StGiFy(a) StGiFy(b) StGiFy(c) StGiFy(d)
?H:?SCAT5:#define SCAT5(a,b,c,d,e)StGiFy(a) StGiFy(b) StGiFy(c) StGiFy(d) StGiFy(e)
?H:%<:#endif
?H:%<:#if $cpp_stuff != 1 && $cpp_stuff != 42
```

```

?H:?%<:#include "Bleth: How does this C preprocessor catenate tokens?"
?H:?%<:#endif
?H:.
?W:%<:CAT2 CAT3 CAT4 CAT5 STRINGIFY SCAT2 SCAT3 SCAT4 SCAT5
?F:!cpp_stuff.c
?LINT:known StGiFy EQuoTe SQuoTe CaTiFy
: how do we catenate cpp tokens here?
echo " "
echo "Checking to see how your cpp does stuff like catenate tokens..." >&4
cpp_quote="
$cat >cpp_stuff.c <<'EOCP'
#define RCAT(a,b)a/**/b
#define ACAT(a,b)a ## b
RCAT(Rei,ser)
ACAT(Cir,cus)
EOCP
$cppstdin $cppflags $cppminus <cpp_stuff.c >cpp_stuff.out
2>&1
if $contains 'Circus' cpp_stuff.out >/dev/null 2>&1; then
echo "Oh! Smells like ANSI's been here."
echo "We can catify or stringify, separately or together!"
cpp_stuff=42
elif $contains 'Reiser' cpp_stuff.out >/dev/null 2>&1; then
echo "Ah, yes! The good old days!"
cpp_stuff=1
$cat >cpp_stuff.c <<'EOCP'
#define SQuoTe(a)"a
#define EQuoTe(a)a"
#define CAT2(a,b)EQuoTe(SQuoTe(a)b)
CAT2(Vic,tory)
EOCP
$cppstdin $cppflags $cppminus <cpp_stuff.c >cpp_stuff.out 2>&1
if $contains ""Victory"" cpp_stuff.out >/dev/null 2>&1; then
echo "I'll resort to a cute trick to also be able to stringify."
cpp_quote=""
else
$cat <<EOM
However, in the good old days we don't know how to stringify and
catify at the same time...
@if SCAT2 || SCAT3 || SCAT4 || SCAT5
You might have to edit the values of the SCAT[2-5] macros in config.h...
@else
Hopefully, $package does not need this feature.
@end
EOM
fi
else
./warn <<EOM

```

I can't seem to be able to concatenate tokens with your cpp.

```
@if
```

```
CAT2 || CAT3 || CAT4 || CAT5 || SCAT2 || SCAT3 || SCAT4 || SCAT5
```

You're going to have to edit the values of the following macros in config.h:

```
@if CAT2 || CAT3 || CAT4 || CAT5
```

```
CAT[2-5]
```

```
@end
```

```
@if SCAT2 || SCAT3 || SCAT4 || SCAT5
```

```
SCAT[2-5]
```

```
@end
```

in order to let me compile.

```
@end
```

EOM

```
cpp_stuff="/* Help! How do we handle cpp_stuff? *//"
```

```
fi
```

```
$rm -f cpp_stuff.*
```

Found in path(s):

```
*/opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/cpp_stuff.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: d_dup2.U 1 2006-08-24 12:32:52Z rmanfredi $
```

```
?RCS:
```

```
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
```

```
?RCS:
```

```
?RCS: You may redistribute only under the terms of the Artistic Licence,
```

```
?RCS: as specified in the README file that comes with the distribution.
```

```
?RCS: You may reuse parts of this distribution only within the terms of
```

```
?RCS: that same Artistic Licence; a copy of which may be found at the root
```

```
?RCS: of the source tree for dist 4.0.
```

```
?RCS:
```

```
?RCS: $Log: d_dup2.U,v $
```

```
?RCS: Revision 3.0 1993/08/18 12:05:56 ram
```

```
?RCS: Baseline for dist 3.0 netwide release.
```

```
?RCS:
```

```
?MAKE:d_dup2: Inlibc
```

```
?MAKE: -pick add $@ %<
```

```
?S:d_dup2:
```

```
?S: This variable conditionally defines HAS_DUP2 if dup2() is
```

```
?S: available to duplicate file descriptors.
```

```
?S:.
```

```
?C:HAS_DUP2 (DUP2):
```

```
?C: This symbol, if defined, indicates that the dup2 routine is
```

```
?C: available to duplicate file descriptors.
```

```
?C:.
?H:#$d_dup2 HAS_DUP2 /**/
?H:.
?LINT:set d_dup2
:
  see if dup2 exists
set dup2 d_dup2
eval $inlibc
```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/d_dup2.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: i_grp.U,v 3.0 1993/08/18 12:08:20 ram Exp $
?RCS:
?RCS: Copyright (c) 1991-1993, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 3.0.
?RCS:
?RCS: GRPASSWD detection added by Andy Dougherty July 14, 1998.
?RCS:
?RCS: $Log: i_grp.U,v $
?RCS: Revision 3.0 1993/08/18 12:08:20 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:i_grp d_grpasswd: \
  contains rm cppstdin cppflags cppminus Inhdr Findhdr Setvar
?MAKE: -pick add $@ %<
?S:i_grp:
?S: This variable conditionally defines the I_GRP symbol, and indicates
?S: whether a C program should include <grp.h>.
?S:.
?S:d_grpasswd:
?S: This variable conditionally
  defines GRPASSWD, which indicates
?S: that struct group in <grp.h> contains gr_passwd.
?S:.
?C:I_GRP:
?C: This symbol, if defined, indicates to the C program that it should
?C: include <grp.h>.
?C:.
?C:GRPASSWD:
?C: This symbol, if defined, indicates to the C program that struct group
```

```

?C: in <grp.h> contains gr_passwd.
?C:.
?H:#$i_grp I_GRP /**/
?H:#$d_grpasswd GRPASSWD /**/
?H:.
?LINT:set i_grp d_grpasswd
?T: xxx
: see if this is an grp system
set grp.h i_grp
eval $inhdr

case "$i_grp" in
$define)
xxx=`./findhdr grp.h`
$cpstdin $cppflags $cppminus < $xxx >$$.h

if $contains 'gr_passwd' $$.h >/dev/null 2>&1; then
val="$define"
else
val="$undef"
fi
set d_grpasswd
eval $setvar

$rm -f $$.h
;;
*)
val="$undef";
set d_grpasswd; eval $setvar
;;
esac

```

Found in path(s):

```

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/modified/i_grp.U

```

No license file was found, but licenses were detected in source scan.

```

# $Id: errnolist.sh,v 3.0.1.1 1994/01/24 14:00:00 ram Exp ram $
#
# Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
#
# You may redistribute only under the terms of the Artistic Licence,
# as specified in the README file that comes with the distribution.
# You may reuse parts of this distribution only within the terms of
# that same Artistic Licence; a copy of which may be found at the root
# of the source tree for dist 4.0.
#
# Original Author: Harlan Stenn <harlan@mumps.pfcs.com>

```

```

#
# $Log: errnolist.sh,v $
# Revision 3.0.1.1 1994/01/24 14:00:00 ram
# patch16: changed top ln-style config.sh lookup into test-style one
#
# Revision 3.0 1993/08/18 12:04:36 ram
# Baseline for dist 3.0 netwide release.
#

case $CONFIG in
")
if test -f config.sh; then TOP=.;
elif test -f ../config.sh; then TOP=../.;
elif test -f ../../config.sh; then TOP=../../.;
elif test -f ../../../config.sh; then TOP=../../../.;
elif
test -f ../../../../config.sh; then TOP=../../../../.;
else
echo "Can't find config.sh."; exit 1
fi
. $TOP/config.sh
;;
esac
case "$0" in
*/*) cd `expr X$0 : 'X\(.*/'` ;;
esac
case "$Serrnolistic" in
") ;;
*)
echo "Making $Serrnolistic ..."
awk -f errnolist.a < /usr/include/sys/errno.h > $Serrnolistic
echo "It would be a good idea to make sure that $Serrnolistic is correct."
esac

```

Found in path(s):

```

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/lib/errnolist.SH

```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_usendir.U 1 2006-08-24 12:32:52Z rmanfredi \$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic Licence,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic Licence; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

```

?RCS:
?RCS: $Log: d_usendir.U,v $
?RCS: Revision 3.0.1.1 1997/02/28 15:47:34 ram
?RCS: patch61: replaced .a with $_a all over the place
?RCS: patch61: likewise for .o replaced by $_o
?RCS:
?RCS: Revision 3.0 1993/08/18 12:07:52 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:d_usendir i_ndir ndirlib: test Setvar Findhdr d_readdir _a
?MAKE: -pick add $@ %<
?S:d_usendir:
?S: This variable conditionally defines the EMULATE_NDIR symbol, which
?S: indicates
to the C program that it should compile the ndir.c code
?S: provided with the package.
?S:.
?S:i_ndir (d_libndir):
?S: This variable conditionally defines the I_NDIR symbol, which
?S: indicates to the C program that it should include the system's
?S: version of ndir.h, rather than the one with this package.
?S:.
?S:ndirlib:
?S: The name of the library to include at linking stage to resolve ndir
?S: symbols. It is up to the makefile to use this value.
?S:.
?C:EMULATE_NDIR (USENDIR):
?C: This symbol, if defined, indicates that the program should compile
?C: the ndir.c code provided with the package.
?C:.
?C:I_NDIR (LIBNDIR):
?C: This symbol, if defined, indicates that the program should include the
?C: system's version of ndir.h, rather than the one with this package.
?C:.
?H:#$d_usendir EMULATE_NDIR /**/
?H:#$i_ndir I_NDIR /**/
?H:.
?T:val2
?LINT: set d_usendir i_ndir
: see if there are directory access routines out there
echo " "
if $test `./findhdr ndir.h` && \
( $test -r /usr/lib/libndir$_a
|| $test -r /usr/local/lib/libndir$_a ); then
echo "Ndir library found." >&4
if $test -r /usr/lib/libndir$_a; then
ndirlib='-lndir'
else

```

```

ndirlib="/usr/local/lib/libndir$_a"
fi
val2="$define"
val="$undef"
else
ndirlib="
val2="$undef"
case "$d_readdir" in
"$define")
echo "No ndir library found, but you have readdir() so we'll use that." >&4
val="$undef";
;;
*)
echo "No ndir library found." >&4
val="$define"
;;
esac
fi
set d_usendir
eval $setvar
val="$val2"
set i_ndir
eval $setvar

```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/d_usendir.U
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: Ins.U,v 3.0.1.1 1994/06/20 07:05:52 ram Exp \$

?RCS:

?RCS: Copyright (c) 1991-1993, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 3.0.

?RCS:

?RCS: Original Author: Andy Dougherty <doughera@lafcol.lafayette.edu>

?RCS:

?RCS: \$Log: Ins.U,v \$

?RCS: Revision 3.0.1.1 1994/06/20 07:05:52 ram

?RCS: patch30: created by ADO

?RCS:

?X:

?X: This unit checks whether symbolic links are really supported.

?X: We can't rely on d_symlink because that may be listed in the

```

?X: C library but unimplemented.
?X:
?MAKE:lns: ln rm touch
?MAKE: -pick add $@ %<
?S:lns:
?S: This variable holds the name of the command to make
?S: symbolic
links (if they are supported). It can be used
?S: in the Makefile. It is either 'ln -s' or 'ln'
?S:.
: determine whether symbolic links are supported
echo " "
$touch blurfl
if $ln -s blurfl sym > /dev/null 2>&1 ; then
echo "Symbolic links are supported." >&4
lns="$ln -s"
else
echo "Symbolic links are NOT supported." >&4
lns="$ln"
fi
$rm -f blurfl sym

```

Found in path(s):

```

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/modified/lns.U

```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: i_malloc.U,v \$

?RCS: Revision 3.0 1993/08/18 12:08:21 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?MAKE:i_malloc: Inhdr

?MAKE: -pick add \$@ %<

?S:i_malloc:

?S: This variable conditionally defines the I_MALLOC symbol, and indicates

?S: whether a C program should include <malloc.h>.

?S:.

?C:I_MALLOC:

?C: This symbol, if defined, indicates to the C program that it should

?C: include <malloc.h>.

?C:.

?H:#\$i_malloc I_MALLOC /**/

?H:.

?LINT:set i_malloc

: see if this is a malloc.h system

set

malloc.h i_malloc

eval \$inhdr

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/i_malloc.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_table.U 1 2006-08-24 12:32:52Z rmanfredi \$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic Licence,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic Licence; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: d_table.U,v \$

?RCS: Revision 3.0.1.2 1993/11/10 17:34:14 ram

?RCS: patch14: wrongly mentionned an obsolete symbol

?RCS:

?RCS: Revision 3.0.1.1 1993/10/16 13:49:29 ram

?RCS: patch12: created

?RCS:

?MAKE:d_table: Inlibc

?MAKE:-pick add \$@ %<

?S:d_table:

?S: This variable conditionally defines HAS_TABLE if table() is

?S: available to examine/update elements from a system table.

?S:.

?C:HAS_TABLE:

?C: This symbol, if defined, indicates that the OSF/1

table() system

?C: call is available to examine/update items from a system table.

?C:.

?H:#\$d_table HAS_TABLE /**/

?H:.

?LINT:set d_table

: see if table exists

```
set table d_table
eval $inlibc
```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/d_table.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: d_ftime.U 1 2006-08-24 12:32:52Z rmanfredi $
```

```
?RCS:
```

```
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
```

```
?RCS:
```

```
?RCS: You may redistribute only under the terms of the Artistic Licence,
```

```
?RCS: as specified in the README file that comes with the distribution.
```

```
?RCS: You may reuse parts of this distribution only within the terms of
```

```
?RCS: that same Artistic Licence; a copy of which may be found at the root
```

```
?RCS: of the source tree for dist 4.0.
```

```
?RCS:
```

```
?RCS: $Log: d_ftime.U,v $
```

```
?RCS: Revision 3.0 1993/08/18 12:06:06 ram
```

```
?RCS: Baseline for dist 3.0 netwide release.
```

```
?RCS:
```

```
?MAKE:d_ftime d_gettimeod: Inlibc Setvar
```

```
?MAKE: -pick add $@ %<
```

```
?S:d_ftime:
```

```
?S: This variable conditionally defines the HAS_FTIME symbol, which indicates
```

```
?S: that the ftime() routine exists. The ftime() routine is basically
```

```
?S: a sub-second accuracy clock.
```

```
?S:.
```

```
?S:d_gettimeod:
```

```
?S: This variable conditionally defines the HAS_GETTIMEOFDAY symbol,
which
```

```
?S: indicates that the gettimeofday() system call exists (to obtain a
```

```
?S: sub-second accuracy clock). You should probably include <sys/resource.h>.
```

```
?S:.
```

```
?C:HAS_FTIME (FTIMER):
```

```
?C: This symbol, if defined, indicates that the ftime() routine exists.
```

```
?C: It is basically a sub-second accuracy clock, but is less accurate
```

```
?C: than gettimeofday(2) anyway. The type "Timeval" should be used to
```

```
?C: refer to "struct timeb".
```

```
?C:.
```

```
?C:HAS_GETTIMEOFDAY (GETTIMEOFDAY):
```

```
?C: This symbol, if defined, indicates that the gettimeofday() system
```

```
?C: call is available for a sub-second accuracy clock. Usually, the file
```

```
?C: <sys/resource.h> needs to be included (see I_SYS_RESOURCE).
```

```
?C: The type "Timeval" should be used to refer to "struct timeval".
```

```
?C:.
```

```
?H:#$d_ftime HAS_FTIME /**/
```

```

?H:#$d_gettimeod HAS_GETTIMEOFDAY /**/
?H:?%<:@if HAS_FTIME
?H:?%<:#ifdef HAS_FTIME
?H:?%<:#define Timeval struct timeb /* Structure used by ftime() */
?H:?%<:#endif
?H:?%<:@end
?H:?%<:@if HAS_GETTIMEOFDAY
?H:?%<:#ifdef HAS_GETTIMEOFDAY
?H:?%<:#define
Timeval struct timeval /* Structure used by gettimeofday() */
?H:?%<:#endif
?H:?%<:@end
?H:
?X:FIXME
?X:?I:?d_ftime:i_systimeb
?X:?I:?d_gettimeod:i_sysresrc
?LINT:set d_gettimeod d_ftime
?LINT:known Timeval
: see if gettimeofday or ftime exists
?X:
?X: Give priority to gettimeofday(2) because timing is more accurate
?X:
set gettimeofday d_gettimeod
eval $inlibc
case "$d_gettimeod" in
"$undef")
set ftime d_ftime
eval $inlibc
;;
*)
val="$undef"; set d_ftime; eval $setvar
;;
esac
case "$d_gettimeod$d_ftime" in
"$undef$undef")
echo " "
echo 'No ftime() nor gettimeofday() -- timing may be less accurate.' >&4
;;
esac

```

Found in path(s):

```

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/d_ftime.U

```

No license file was found, but licenses were detected in source scan.

```

?RCS: $Id: installprefix.U,v 1.1 1999/07/08 18:32:57 doughera Exp doughera $

```

```

?RCS:

```

```

?RCS: Copyright (c) 1999 Andy Dougherty

```

```

?RCS:
?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 3.0.
?RCS:
?RCS: Original Author: Andy Dougherty <doughera@lafcol.lafayette.edu>
?RCS:
?RCS: $Log: installprefix.U,v $
?RCS: Revision 1.1 1999/07/08 18:32:57 doughera
?RCS: Initial revision
?RCS:
?RCS:
?MAKE:installprefix installprefixexp: Getfile Loc \
Oldconfig afs cat package prefix
?MAKE: -pick add $@ %<
?S:installprefix:
?S: This variable holds the name of the directory below which
?S: "make install" will install the package. For most users, this
?S: is the same
as prefix. However, it is useful for
?S: installing the software into a different (usually temporary)
?S: location after which it can be bundled up and moved somehow
?S: to the final location specified by prefix.
?S:.
?S:installprefixexp:
?S: This variable holds the full absolute path of installprefix
?S: with all ~-expansion done.
?S:.
: determine installation prefix for where package is to be installed.
if $afs; then
$cat <<EOM

```

Since you are running AFS, I need to distinguish the directory in which files will reside from the directory in which they are installed (and from which they are presumably copied to the former directory by occult means).

```

EOM
case "$installprefix" in
*) dflt=`echo $prefix | sed 's#^/afs/#/afs/.#`;;
*) dflt="$installprefix";;
esac
else
$cat <<EOM

```

In some special cases, particularly when building \$package for distribution, it is convenient to distinguish the directory in which files should be

installed from the directory (\$prefix) in which they will eventually reside. For most users, these two directories are the same.

EOM

```
case "$installprefix" in
  ") dflt=$prefix ;;
  *) dflt=$installprefix;;
esac
fi
fn=d~
rp='What installation prefix should I use for installing files?'
./getfile
installprefix="$ans"
installprefixexp="$ansexp"
```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/installdirs/installprefix.U
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_readdir.U 1 2006-08-24 12:32:52Z rmanfredi \$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic Licence,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic Licence; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: d_readdir.U,v \$

?RCS: Revision 3.0.1.1 1994/05/06 14:46:37 ram

?RCS: patch23: added support for seekdir, telldir and rewinddir (ADO)

?RCS:

?RCS: Revision 3.0 1993/08/18 12:06:52 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?X: Force checking for <dirent.h> inclusion

?X:INC: i_dirent

?MAKE:d_readdir d_seekdir d_telldir d_rewinddir: Inlibc

?MAKE: -pick add \$@ %<

?S:d_readdir:

?S: This variable conditionally defines HAS_READDIR if readdir()

is

?S: available to read directory entries.

?S:.

?C:HAS_READDIR (READDIR):

?C: This symbol, if defined, indicates that the readdir routine is available to read directory entries. You may have to include <dirent.h>. See I_DIRENT.

?C:.

?H:#\$d_readdir HAS_READDIR /**/
?H:.

?S:d_seekdir:
?S: This variable conditionally defines HAS_SEEKDIR if seekdir() is available.

?S:.

?C:HAS_SEEKDIR:
?C: This symbol, if defined, indicates that the seekdir routine is available. You may have to include <dirent.h>. See I_DIRENT.

?C:.

?H:#\$d_seekdir HAS_SEEKDIR /**/
?H:.

?S:d_telldir:
?S: This variable conditionally defines HAS_TELLDIR if telldir() is available.

?S:.

?C:HAS_TELLDIR:
?C: This symbol, if defined, indicates that the telldir routine is available. You may have to include <dirent.h>. See I_DIRENT.

?C:.

?H:#\$d_telldir HAS_TELLDIR /**/
?H:.

?S:d_rewinddir:
?S: This variable conditionally defines HAS_REWINDDIR if rewinddir() is available.

?S:.

?C:HAS_REWINDDIR:
?C: This symbol, if defined, indicates that the rewinddir routine is available. You may have to include <dirent.h>. See I_DIRENT.

?C:.

?H:#\$d_rewinddir HAS_REWINDDIR /**/
?H:.

?LINT:set d_readdir d_seekdir d_telldir d_rewinddir
: see if readdir and friends exist
set readdir d_readdir
eval \$inlibc
@if d_seekdir || HAS_SEEKDIR
set seekdir d_seekdir
eval \$inlibc
@end
@if d_telldir || HAS_TELLDIR
set telldir d_telldir
eval \$inlibc

```
@end
@if d_rewinddir || HAS_REWINDDIR
set rewinddir d_rewinddir
eval $inlibc
@end
```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/d_readdir.U
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_crypt_r.U,v 0RCS:

?RCS: Copyright (c) 2002,2003 Jarkko Hietaniemi

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?RCS: Generated by the reentr.pl from the Perl 5.8 distribution.

?RCS:

?MAKE:d_crypt_r crypt_r_proto: Inlibc Protochk Hasproto i_systypes \
 usethreads i_crypt extern_C

?MAKE: -pick add \$@ %<

?S:d_crypt_r:

?S: This variable conditionally defines the HAS_CRYPT_R symbol,

?S: which indicates to the C program that the crypt_r()

?S: routine is available.

?S:.

?S:crypt_r_proto:

?S: This variable encodes the prototype of crypt_r.

?S: It is zero if d_crypt_r is undef, and one of the

?S: REENTRANT_PROTO_T_ABC macros of reentr.h if d_crypt_r

?S: is defined.

?S:.

?C:HAS_CRYPT_R:

?C: This symbol, if defined, indicates that the crypt_r routine

?C: is available to crypt re-entrantly.

?C:.

?C:CRYPT_R_PROTO:

?C: This

symbol encodes the prototype of crypt_r.

?C: It is zero if d_crypt_r is undef, and one of the

?C: REENTRANT_PROTO_T_ABC macros of reentr.h if d_crypt_r

?C: is defined.

?C:.

?H:#\$d_crypt_r HAS_CRYPT_R /**/

?H:#define CRYPT_R_PROTO \$crypt_r_proto /**/

?H:.

?T:try hdrs d_crypt_r_proto

```

: see if crypt_r exists
set crypt_r d_crypt_r
eval $inlibc
case "$d_crypt_r" in
"$define")
hdrs="$i_systypes sys/types.h define stdio.h $i_crypt crypt.h"
case "$d_crypt_r_proto:$usethreads" in
":define") d_crypt_r_proto=define
set d_crypt_r_proto crypt_r $hdrs
eval $hasproto ;;
*) ;;
esac
case "$d_crypt_r_proto" in
define)
case "$crypt_r_proto" in
"|0) try='char* crypt_r(const char*, const char*, struct crypt_data*);'
./prochck "$extern_C $try" $hdrs && crypt_r_proto=B_CCS ;;
esac
case "$crypt_r_proto" in
"|0) try='char* crypt_r(const char*, const char*, CRYPTD*);'
./prochck "$extern_C $try" $hdrs && crypt_r_proto=B_CCD ;;
esac
case "$crypt_r_proto" in
"|0) d_crypt_r=undef
crypt_r_proto=0
echo "Disabling crypt_r, cannot determine prototype." >&4 ;;
* ) case "$crypt_r_proto" in
REENTRANT_PROTO*) ;;
*) crypt_r_proto="REENTRANT_PROTO_$crypt_r_proto" ;;
esac
echo "Prototype: $try" ;;
esac
;;
*) case "$usethreads" in
define) echo "crypt_r has no prototype, not using it." >&4 ;;
esac
d_crypt_r=undef
crypt_r_proto=0
;;
esac
;;
*) crypt_r_proto=0
;;
esac

```

Found in path(s):

```

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/threads/d_crypt_r.U

```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: install.U 1 2006-08-24 12:32:52Z rmanfredi $
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: $Log: install.U,v $
?RCS: Revision 3.0.1.2 1995/09/25 09:16:37 ram
?RCS: patch59: all possible install programs are now looked for
?RCS:
?RCS: Revision 3.0.1.1 1995/01/11 15:30:41 ram
?RCS: patch45: created
?RCS:
?MAKE:install installdir: Loc Oldconfig Getfile cat test startsh rm +cc \
eunicefix package contains mkdir echo n c
?MAKE: -pick add $@ %<
?S:install:
?S: This variable contains the name of an install program that can accept
?S: BSD-style arguments.
It must correctly support -c, -s, and -m at least.
?S: It is a fully qualified pathname when found. If you have a local
?S: install.SH file at the root directory of your package, it is assumed to
?S: be the default script emulating a BSD install and the variable will be
?S: set to ./install. Otherwise, it is set to plain 'install', relying on
?S: the user's PATH to perform miracles.
?S:.
?S:installdir:
?S: This variable contains the name of a program that can install nested
?S: directories. Often set to 'mkdir -p', it can also be 'install -d' if
?S: you have such a beast and lack the former. If you have an install.SH
?S: file at the root directory of your package, it will be used in last
?S: resort, setting the variable to './install -d'. Otherwise, it is set to
?S: plain 'mkdir', and cross your fingers!
?S:.
?T:dir file tryit prog creatdir either
?F:!tryinst
: locate a BSD compatible install program
echo " "
echo "Looking for a BSD-compatible install program..." >&4
@if installdir
creatdir="
@end
```

```

case
"$install" in
")
tryit="
for dir in $pth; do
for file in ginstall installbsd scoinst install; do
if $test -f $dir/$file; then
tryit="$stryit $dir/$file"
fi
done
done
$cat >try.c <<EOC
int main()
{
printf("OK\n");
exit(0);
}
EOC
if $cc -o try try.c >/dev/null 2>&1; then
cp try try.ns
strip try >/dev/null 2>&1
else
echo "(I can't seem to compile a trivial C program -- bypassing.)"
echo "try" >try
cp try try.ns
fi
$cat >tryinst <<EOS
$startsh
$rm -rf foo d
@if installdir
\ $1 -d foo/bar
@end
$mkdir d
\ $1 -c -m 764 try.ns d
\ $1 -c -s -m 642 try.ns d/try
EOS
chmod +x tryinst
$unicefix tryinst
dflt="
either="
for prog in $stryit; do
$echo $n "Checking $prog... $c"
./tryinst $prog >/dev/null 2>&1
@if installdir
if $test -d foo/bar; then
creatdir="$prog -d"
fi
@end

```

```

(ls -l d/try >try.ls; ls -l d/try.ns >tryno.ls) 2>/dev/null
if (cmp -s d/try try && cmp -s d/try.ns try.ns && \
  $contains 'rwxrw-r--' tryno.ls && \
  \
  $contains 'rw-r---w-' try.ls) >/dev/null 2>&1
then
  dflt="$prog"
  echo "ok, that will do."
  break
fi
echo "not good$either."
either=' either'
$rm -f try*.ls
done
$rm -rf foo d tryinst try try*.ls try.*
case "$dflt" in
  *)
@if {test -f ../install.SH}
  echo "Hopefully, $package comes with its own install script!"
  dflt='../install'
@else
  dflt='install'
@end
  ;;
esac
  ;;
*) dflt="$install";;
esac
$cat <<EOM

```

I will be requiring a BSD-compatible install program (one that allows options like -s to strip executables or -m to specify a file mode) to install \$package.

If the question below contains a fully qualified default path, then it is probably ok. If it is an unqualified name such as 'install', then it means I was unable to find out a good install program I could use. If

```
@if {test -f ../install.SH}
```

you know of one, please tell me about it. If the default is './install', then I shall be using the install script supplied with \$package.

```
@else
```

you know of one,

please tell me about it.

```
@end
```

EOM

```
@if {test -f ../install.SH}
```

```
fn='/fe~(install,./install)'
```

```

@else
fn='/fe~(install)'
@end
rp='Which install program shall I use?'
./getfile
install="$ans"

@if installdir
: how can we create nested directories?
echo " "
echo "Ok, let's see how we can create nested directories..." >&4
case "$installdir" in
")
?X: First time, maybe we already found out a working one in $creatdir above...
?X: Prefer "mkdir -p" because of bugs in GNU install when not running as root
$mkdir -p foo/bar >/dev/null 2>&1
if $test -d foo/bar; then
echo "Great, we can build them using 'mkdir -p'."
creatdir='mkdir -p'
else
case "$creatdir" in
")
if eval "$install -d foo/bar"; $test -d foo/bar; then
creatdir="install -d"
echo "It looks like '$creatdir' will do it for us."
fi
;;
*)
eval "$creatdir foo/bar" >/dev/null 2>&1
if $test -d foo/bar; then
echo "Ah! We can use '$creatdir' to do just that."
else
creatdir="
fi
;;
esac
fi
$rm
-rf foo
case "$creatdir" in
")
echo "Heck! Another ancient system lacking the comfort of modern ones!"
@if { test -f ../install.SH }
echo "You can thank $package for bringing you its own install script!"
installdir='./install -d'
@else
echo "We have no choice but to use plain old 'mkdir' -- wish me luck!"
installdir=mkdir

```

```
@end
;;
*) installdir="$creatdir";;
esac
;;
*) echo "As you already told me, '$installdir' should work.";;
esac
```

@end

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/install.U
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: cppstdin.U 1 2006-08-24 12:32:52Z rmanfredi \$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: cppstdin.U,v \$

?RCS: Revision 3.0.1.4 1994/10/29 16:08:34 ram

?RCS: patch36: added ?F: line for metalint file checking

?RCS:

?RCS: Revision 3.0.1.3 1994/01/24 14:05:38 ram

?RCS: patch16: comment for CPPLAST was missing

?RCS:

?RCS: Revision 3.0.1.2 1993/12/15 08:18:58 ram

?RCS: patch15: new variables cprun and cpplast, guaranteed wrapper-free

?RCS: patch15: cppstdin now tries to use cc, even at the cost of a wrapper

?RCS:

?RCS: Revision 3.0.1.1

1993/08/25 14:00:53 ram

?RCS: patch6: remove wrapper when not actually used

?RCS:

?RCS: Revision 3.0 1993/08/18 12:05:38 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?MAKE:cppstdin cppminus cprun cpplast: contains test \

Myread Oldconfig Loc cpp +cc rm hint osname gccversion

?MAKE: -pick add \$@ %<

?S:cppstdin:

?S: This variable contains the command which will invoke the C

?S: preprocessor on standard input and put the output to stdout.
?S: It is primarily used by other Configure units that ask about
?S: preprocessor symbols.
?S:.
?S:cppminus:
?S: This variable contains the second part of the string which will invoke
?S: the C preprocessor on the standard input and produce to standard
?S: output. This variable will have the value "-" if cppstdin needs
?S: a minus to specify standard input, otherwise the value is "".
?S:.
?S:cprun:
?S: This variable contains the command which will invoke a C preprocessor
?S: on standard input and put the output to stdout. It is guaranteed
not
?S: to be a wrapper and may be a null string if no preprocessor can be
?S: made directly available. This preprocessor might be different from the
?S: one used by the C compiler. Don't forget to append cpplast after the
?S: preprocessor options.
?S:.
?S:cpplast:
?S: This variable has the same functionality as cppminus, only it applies
?S: to cprun and not cppstdin.
?S:.
?C:CPPSTDIN:
?C: This symbol contains the first part of the string which will invoke
?C: the C preprocessor on the standard input and produce to standard
?C: output. Typical value of "cc -E" or "/lib/cpp", but it can also
?C: call a wrapper. See CPPRUN.
?C:.
?C:CPPMINUS:
?C: This symbol contains the second part of the string which will invoke
?C: the C preprocessor on the standard input and produce to standard
?C: output. This symbol will have the value "-" if CPPSTDIN needs a minus
?C: to specify standard input, otherwise the value is "".
?C:.
?C:CPPRUN:
?C: This symbol contains the string which will invoke
a C preprocessor on
?C: the standard input and produce to standard output. It needs to end
?C: with CPPLAST, after all other preprocessor flags have been specified.
?C: The main difference with CPPSTDIN is that this program will never be a
?C: pointer to a shell wrapper, i.e. it will be empty if no preprocessor is
?C: available directly to the user. Note that it may well be different from
?C: the preprocessor used to compile the C program.
?C:.
?C:CPPLAST:
?C: This symbol is intended to be used along with CPPRUN in the same manner
?C: symbol CPPMINUS is used with CPPSTDIN. It contains either "-" or "".

```

?C:.
?H:#define CPPSTDIN "$cppstd"
?H:#define CPPMINUS "$cppminus"
?H:#define CPPRUN "$cpprun"
?H:#define CPPLAST "$cpplast"
?H:.
?F:cppstd !testcpp.out !testcpp.c
?T:wrapper x_cpp x_minus ok
?LINT:extern cppflags
: see how we invoke the C preprocessor
echo " "
echo "Now, how can we feed standard input to your C preprocessor..." >&4
cat <<'EOT' >testcpp.c
#define ABC abc
#define
XYZ xyz
ABC.XYZ
EOT
cd ..
if test ! -f cppstd; then
if test "X$osname" = "Xaix" -a "X$gccversion" = X; then
# AIX cc -E doesn't show the absolute headerfile
# locations but we'll cheat by using the -M flag.
echo 'cat >.$$.c; rm -f .$$.u; ""$cc" ${1+"$@"} -M -c .$$.c 2>/dev/null; test -s .$$.u && awk ""$2 ~ /\.h$/ { print
"# 0 \\"$2\\"" } "" .$$ .u; rm -f .$$.o .$$.u; ""$cc" -E ${1+"$@"} .$$ .c; rm .$$.c' > cppstd
else
echo 'cat >.$$.c; ""$cc $cppflags" -E ${1+"$@"} .$$ .c; rm .$$.c' > cppstd
fi
else
echo "Keeping your $hint cppstd wrapper."
fi
chmod 755 cppstd
wrapper=`pwd`/cppstd
ok='false'
cd UU

?X:
?X: We'll run the cpp tests again if we don't have any valid C preprocessor
?X: yet or don't know how to proceed without a wrapper (in which case cpprun
?X: is empty and that's really annoying...)
?X:
if $test "X$cppstd" != "X" && \
$cppstd $cppminus <testcpp.c >testcpp.out 2>&1 && \
$contains 'abc.*xyz' testcpp.out >/dev/null 2>&1
then
echo "You used
to use $cppstd $cppminus so we'll use that again."
case "$cpprun" in

```

```

") echo "But let's see if we can live without a wrapper..." ;;
*)
if $cprun $cpplast <testcpp.c >testcpp.out 2>&1 && \
  $contains 'abc.*xyz' testcpp.out >/dev/null 2>&1
then
  echo "(And we'll use $cprun $cpplast to preprocess directly.)"
  ok='true'
else
  echo "(However, $cprun $cpplast does not work, let's see...)"
fi
;;
esac
else
case "$cppstdin" in
") ;;
*)
  echo "Good old $cppstdin $cppminus does not seem to be of any help..."
  ;;
esac
fi

if $ok; then
  : nothing
elif echo 'Maybe ""$cc" -E" will work...'; \
  $cc -E <testcpp.c >testcpp.out 2>&1; \
  $contains 'abc.*xyz' testcpp.out >/dev/null 2>&1 ; then
  echo "Yup, it does."
  x_cpp="$cc $cppflags -E"
  x_minus="";
elif echo 'Nope...maybe ""$cc" -E -" will work...'; \
  $cc -E - <testcpp.c >testcpp.out 2>&1; \
  $contains 'abc.*xyz' testcpp.out >/dev/null 2>&1 ; then
  echo "Yup, it does."
  x_cpp="$cc $cppflags -E"
  x_minus='-';
elif
  echo 'Nope...maybe ""$cc" -P" will work...'; \
  $cc -P <testcpp.c >testcpp.out 2>&1; \
  $contains 'abc.*xyz' testcpp.out >/dev/null 2>&1 ; then
  echo "Yipee, that works!"
  x_cpp="$cc $cppflags -P"
  x_minus="";
elif echo 'Nope...maybe ""$cc" -P -" will work...'; \
  $cc -P - <testcpp.c >testcpp.out 2>&1; \
  $contains 'abc.*xyz' testcpp.out >/dev/null 2>&1 ; then
  echo "At long last!"
  x_cpp="$cc $cppflags -P"
  x_minus='-';

```

```

elif echo 'No such luck, maybe "$cpp" will work...'; \
$cpp <testcpp.c >testcpp.out 2>&1; \
$contains 'abc.*xyz' testcpp.out >/dev/null 2>&1 ; then
echo "It works!"
x_cpp="$cpp $cppflags"
x_minus="";
elif echo 'Nixed again...maybe "$cpp' -" will work...'; \
$cpp - <testcpp.c >testcpp.out 2>&1; \
$contains 'abc.*xyz' testcpp.out >/dev/null 2>&1 ; then
echo "Hooray, it works! I was beginning to wonder."
x_cpp="$cpp $cppflags"
x_minus='-';
elif echo 'Uh-uh. Time to get fancy. Trying a wrapper...'; \
$wrapper <testcpp.c >testcpp.out 2>&1; \
$contains
'abc.*xyz' testcpp.out >/dev/null 2>&1 ; then
x_cpp="$wrapper"
x_minus=""
echo "Eureka!"
else
dflt=""
rp="No dice. I can't find a C preprocessor. Name one:"
./myread
x_cpp="$ans"
x_minus=""
$x_cpp <testcpp.c >testcpp.out 2>&1
if $contains 'abc.*xyz' testcpp.out >/dev/null 2>&1 ; then
echo "OK, that will do." >&4
else
echo "Sorry, I can't get that to work. Go find one and rerun Configure." >&4
exit 1
fi
fi

case "$ok" in
false)
cppstdin="$x_cpp"
cppminus="$x_minus"
cpprun="$x_cpp"
cpplast="$x_minus"
?X:
?X: If /lib/cpp is used, try using a wrapper to increase our chances to have
?X: the C compiler and our $cppstdin agree on the same symbols... However,
?X: since cpprun is guaranteed not to be a wrapper, we must clear it if the
?X: only preprocessor we found was a wrapper, with all our luck...
?X:
set X $x_cpp
shift

```

```

case "$1" in
"$cpp")
echo "Perhaps can we force $cc -E using a wrapper..."
if $wrapper <testcpp.c >testcpp.out 2>&1; \
$contains 'abc.*xyz'
testcpp.out >/dev/null 2>&1
then
echo "Yup, we can."
cppstdin="$wrapper"
cppminus="";
else
echo "Nope, we'll have to live without it..."
fi
;;
esac
case "$cpprun" in
"$wrapper")
cpprun="
cpplast="
;;
esac
;;
esac

case "$cppstdin" in
"$wrapper"|"cppstdin") ;;
*) $rm -f $wrapper;;
esac
$rm -f testcpp.c testcpp.out

```

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/modified/cppstdin.U

No license file was found, but licenses were detected in source scan.

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?MAKE:d_ercf: Inlibc

?MAKE: -pick add \$@ %<

?S:d_ercf:

?S: This variable conditionally defines the HAS_ERFC symbol, which

?S: indicates to the C program that the erfc() routine is available.

?S:.

?C:HAS_ERFC:

?C: This symbol, if defined, indicates that the erfc routine is

?C: available to do the complementary error function.

?C:.

?H:#\$d_erfc HAS_ERFC /**/

?H:.

?LINT:set d_erfc

: see if erfc exists

set erfc d_erfc

eval \$inlibc

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_erfc.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_flock.U 1 2006-08-24 12:32:52Z rmanfredi \$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic Licence,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic Licence; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: d_flock.U,v \$

?RCS: Revision 3.0 1993/08/18 12:06:05 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?MAKE:d_flock: Inlibc

?MAKE: -pick add \$@ %<

?S:d_flock:

?S: This variable conditionally defines HAS_FLOCK if flock() is

?S: available to do file locking.

?S:.

?C:HAS_FLOCK (FLOCK):

?C: This symbol, if defined, indicates that the flock routine is

?C: available to do file locking.

?C:.

?H:#\$d_flock HAS_FLOCK /**/

?H:.

?LINT:set d_flock

: see

if flock exists

set flock d_flock

eval \$inlibc

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/d_flock.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: Oldconfig.U,v 3.0.1.10 1997/02/28 15:06:39 ram Exp \$
?RCS:
?RCS: Copyright (c) 1991-1993, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 3.0.
?RCS:
?RCS: \$Log: Oldconfig.U,v \$
?RCS: Revision 3.0.1.10 1997/02/28 15:06:39 ram
?RCS: patch61: added support for src.U
?RCS: patch61: new OSNAME define
?RCS: patch61: can now sense new OSes
?RCS:
?RCS: Revision 3.0.1.9 1995/07/25 13:40:51 ram
?RCS: patch56: now knows about OS/2 platforms
?RCS:
?RCS: Revision 3.0.1.8 1995/05/12 12:04:18 ram
?RCS: patch54: config.sh reload logic now knows about new -K switch
?RCS: patch54: cleaned up and extended osvers for DEC
OSF/1 (ADO)
?RCS: patch54: added MachTen detection (ADO)
?RCS:
?RCS: Revision 3.0.1.7 1995/02/15 14:13:41 ram
?RCS: patch51: adapted osvers computation for AIX (ADO)
?RCS:
?RCS: Revision 3.0.1.6 1995/01/30 14:27:15 ram
?RCS: patch49: unit Options.U now exports file optdef.sh, not a variable
?RCS: patch49: update code for myuname changed (WED)
?RCS:
?RCS: Revision 3.0.1.5 1995/01/11 15:15:36 ram
?RCS: patch45: added quotes around the INITPROG variable (ADO)
?RCS: patch45: allows variable overriding after config file loading
?RCS:
?RCS: Revision 3.0.1.4 1994/10/29 15:57:05 ram
?RCS: patch36: added ?F: line for metalint file checking
?RCS: patch36: merged with the version used for perl5's Configure (ADO)
?RCS:
?RCS: Revision 3.0.1.3 1994/05/06 14:24:17 ram
?RCS: patch23: added support for osf1 hints
?RCS: patch23: new support for solaris and i386 systems (ADO)
?RCS:
?RCS: Revision 3.0.1.2 1994/01/24 14:05:02 ram
?RCS: patch16: added post-processing on myuname for Xenix targets

?RCS:
 patch16: message proposing config.sh defaults made consistent

?RCS:
 ?RCS: Revision 3.0.1.1 1993/09/13 15:56:32 ram

?RCS: patch10: force use of config.sh when -d option is used (WAD)

?RCS: patch10: complain about non-existent hint files (WAD)

?RCS: patch10: added Options dependency for fastread variable

?RCS:
 ?RCS: Revision 3.0 1993/08/18 12:05:12 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:
 ?X:
 ?X: This unit tries to remember what we did last time we ran Configure, mostly
 ?X: for the sake of setting defaults.

?X:
 ?MAKE:Oldconfig hint myuname osname osvers: Instruct Myread uname \
 Checkcc Mksymlinks run \
 sh awk sed test cat rm lns tr n c contains Loc Options Tr src trnl ln

?MAKE: -pick wipe \$@ %<

?S:myuname:
 ?S: The output of 'uname -a' if available, otherwise the hostname.
 ?S: The whole thing is then lower-cased and slashes and single quotes are
 ?S: removed.

?S:.
 ?S:hint:
 ?S: Gives the type of hints used for previous answers. May be one of
 ?S: "default",
 "recommended" or "previous".

?S:.
 ?S:osname:
 ?S: This variable contains the operating system name (e.g. sunos,
 ?S: solaris, hpux, etc.). It can be useful later on for setting
 ?S: defaults. Any spaces are replaced with underscores. It is set
 ?S: to a null string if we can't figure it out.

?S:.
 ?S:osvers:
 ?S: This variable contains the operating system version (e.g.
 ?S: 4.1.3, 5.2, etc.). It is primarily used for helping select
 ?S: an appropriate hints file, but might be useful elsewhere for
 ?S: setting defaults. It is set to " if we can't figure it out.
 ?S: We try to be flexible about how much of the version number
 ?S: to keep, e.g. if 4.1.1, 4.1.2, and 4.1.3 are essentially the
 ?S: same for this package, hints files might just be os_4.0 or
 ?S: os_4.1, etc., not keeping separate files for each little release.

?S:.
 ?C:OSNAME:
 ?C: This symbol contains the name of the operating system, as determined
 ?C: by Configure. You shouldn't rely on it too much; the specific

?C: feature tests
 from Configure are generally more reliable.

?C:.

?C:OSVERS:

?C: This symbol contains the version of the operating system, as determined
 ?C: by Configure. You shouldn't rely on it too much; the specific
 ?C: feature tests from Configure are generally more reliable.

?C:.

?H:#define OSNAME "\$osname" /**/
 ?H:#define OSVERS "\$osvers" /**/
 ?H:.

?F:!config.sh

?T:tmp tmp_n tmp_c tmp_sh file

?T:xxxxfile xxxfile xxfile xfile hintfile newmyuname

?T:tans _ isesix INITPROG DJGPP

?D:osname="

?LINT:change n c sh

?LINT:extern targetarch

?LINT:extern hostarch

?LINT:change hostarch

?LINT:extern is_os2

: Try to determine whether config.sh was made on this system
 case "\$config_sh" in
 ")
 ?X: indentation wrong on purpose--RAM
 ?X: Leave a white space between first two '(' for ksh. The sub-shell is needed
 ?X: on some machines to avoid the error message when uname is not found; e.g.
 ?X: old SUN-OS 3.2 would not execute hostname in (uname -a || hostname). Sigh!
 ?X: Now not using a subshell but instead \$stest.
 myuname=`\$uname
 -a 2>/dev/null`
 \$stest -z "\$myuname" && myuname=`hostname 2>/dev/null`
 # Downcase everything to avoid ambiguity.
 # Remove slashes and single quotes so we can use parts of this in
 # directory and file names.
 # Remove newlines so myuname is sane to use elsewhere.
 # tr '[A-Z]' '[a-z]' would not work in EBCDIC
 # because the A-Z/a-z are not consecutive.
 myuname=`echo \$myuname | \$sed -e "s,[/],,g" | \
 ./tr '[A-Z]' '[a-z]' | \$tr \$trnl ' '`
 ?X: Save the value we just computed to reset myuname after we get done here.
 newmyuname="\$myuname"
 dflt=n
 case "\$knowitall" in
 ")
 if test -f ../config.sh; then
 if \$contains myuname= ../config.sh >/dev/null 2>&1; then
 eval "`grep myuname= ../config.sh`"

```

fi
if test "X$myuname" = "X$newmyuname"; then
  dflt=y
fi
fi
;;
*) dflt=y;;
esac

@if {test -d ../hints}
: Get old answers from old config file if Configure was run on the
: same system, otherwise use the hints.
hint=default
cd ..
?X: Since we are now at the root of the source
tree, we must use $src
?X: to access the sources and not $src. See src.U for details...
if test -f config.sh; then
  echo " "
  rp="I see a config.sh file. Shall I use it to set the defaults?"
  . UU/myread
  case "$ans" in
  n*|N*) echo "OK, I'll ignore it."
    mv config.sh config.sh.old
    myuname="$newmyuname"
    ;;
  *) echo "Fetching default answers from your old config.sh file..." >&4
    tmp_n="$n"
    tmp_c="$c"
    tmp_sh="$sh"
    ./config.sh
    cp config.sh UU
    n="$tmp_n"
    c="$tmp_c"
    : Older versions did not always set $sh. Catch re-use of such
    : an old config.sh.
    case "$sh" in
    ") sh="$tmp_sh" ;;
    esac
    hint=previous
    ;;
  esac
fi
./UU/checkcc
if test ! -f config.sh; then
$cat <<EOM

```

First time through, eh? I have some defaults handy for some systems

that need some extra help getting the Configure answers right:

EOM

```
(cd $src/hints; ls -C *.sh) | $sed 's/\.sh/ /g' >&4
dflt="
: Half the following guesses are probably wrong... If you have better
: tests or hints,
please send them to <MAINTLOC>
: The metaconfig authors would also appreciate a copy...
$test -f /irix && osname=irix
$test -f /xenix && osname=sco_xenix
$test -f /dynix && osname=dynix
$test -f /dnix && osname=dnix
$test -f /lynx.os && osname=lynxos
$test -f /unicos && osname=unicos && osvers=`$uname -r`
$test -f /unicosmk && osname=unicosmk && osvers=`$uname -r`
$test -f /unicosmk.ar && osname=unicosmk && osvers=`$uname -r`
$test -f /bin/mips && /bin/mips && osname=mips
$test -d /usr/apollo/bin && osname=apollo
$test -f /etc/saf/_sactab && osname=svr4
$test -d /usr/include/minix && osname=minix && osvers=`$uname -r`
$test -f /system/gnu_library/bin/ar.pm && osname=vos
$test -f /sys/utilities/MultiView && osname=amigaos
if $test -d /MachTen -o -d /MachTen_Folder; then
?X: MachTen uname -a output looks like
?X: xxx 4 0.0 Macintosh
?X: MachTen /sbin/version output looks like
?X: MachTen 4.0 Mon Aug 28 10:18:00 1995
?X: MachTen 3.x had the 'version' command in /usr/etc/version.
osname=machten
if
$test -x /sbin/version; then
osvers=`/sbin/version | $awk '{print $2}' |
$sed -e 's/[A-Za-z]$/'`
elif $test -x /usr/etc/version; then
osvers=`/usr/etc/version | $awk '{print $2}' |
$sed -e 's/[A-Za-z]$/'`
else
osvers="$2.$3"
fi
fi

$test -f /sys/posix.dll &&
$test -f /usr/bin/what &&
set X `usr/bin/what /sys/posix.dll` &&
$test "$3" = UWIN &&
osname=uwin &&
osvers="$5"
```

?X: If we have uname, we already computed a suitable uname -a output,

?X: and it lies in \$myuname.

```
if $test -f $uname; then
  set X $myuname
  shift
```

```
case "$5" in
  fps*) osname=fps ;;
  mips*)
  case "$4" in
    umips) osname=umips ;;
    *) osname=mips ;;
  esac;;
  [23]100) osname=mips ;;
```

?X: Interactive Unix.

```
i386*)
  tmp=`/bin/uname -X 2>/dev/null|awk '/3\.2v[45]/{ print $(NF) }`
  if $test "$tmp" != "" -a "$3" = "3.2" -a -f '/etc/systemid'; then
    osname='sco'
    osvers=$tmp
  elif $test -f /etc/kconfig; then
    osname=isc
  if
  test "$lns" = "$ln -s"; then
    osvers=4
  elif $contains _SYSV3 /usr/include/stdio.h > /dev/null 2>&1 ; then
    osvers=3
  elif $contains _POSIX_SOURCE /usr/include/stdio.h > /dev/null 2>&1 ; then
    osvers=2
  fi
fi
tmp=""
;;
```

?X: MS-DOS djgpp uname -a output looks like:

?X: ms-dos xxx 6 22 pc

?X: \$1 is the "dos flavor" (need not be "ms-dos").

?X: \$2 is the node name

?X: \$3 and \$4 are version/subversion

?X: \$5 is always "pc", but that might not be unique to DJGPP.

?X: (e.g. Solaris_x86 has \$5 = i86pc, which doesn't actually conflict,

?X: but it's close enough that I can easily imagine other vendors also

?X: using variants of pc* in \$5.)

?X: The "DJGPP" environment variable is always set when djgpp is active.

```
pc*)
  if test -n "$DJGPP"; then
    osname=dos
    osvers=djgpp
```

```
fi
;;
esac
```

```
case "$1" in
```

```
  aix) osname=aix
```

?X: aix 4.1 uname -a output looks like

?X: AIX foo 1 4 000123456789

?X: where \$4 is the major release number and \$3 is the (minor) version.

?X: More detail on the version is available with the oslevel command.

?X: in 3.2.x, it output a string (see case statements below). In 4.1,

?X: it puts out something like 4.1.1.0

```
  tmp=`( oslevel) 2>/dev/null || echo "not found") 2>&1`
```

```
  case "$tmp" in
```

```
    # oslevel can fail with:
```

```
    # oslevel: Unable to acquire lock.
```

```
    *not\ found) osvers="$4"."$3" ;;
```

```
    '<3240'|<>3240') osvers=3.2.0 ;;
```

```
    '=3240'|>3240'|<3250'|<>3250') osvers=3.2.4 ;;
```

```
    '=3250'|>3250') osvers=3.2.5 ;;
```

```
    *) osvers=$tmp;;
```

```
  esac
```

```
;;
```

```
bitrig) osname=bitrig
```

```
  osvers="$3"
```

```
;;
```

```
bsd386) osname=bsd386
```

```
  osvers=`$uname -r`
```

```
;;
```

```
cygwin*) osname=cygwin
```

```
  osvers="$3"
```

```
;;
```

```
*dc.osx) osname=dcosx
```

```
  osvers="$3"
```

```
;;
```

```
dnix) osname=dnix
```

```
  osvers="$3"
```

```
;;
```

```
domainos) osname=apollo
```

```
  osvers="$3"
```

```
;;
```

```
dgux) osname=dgux
```

```
  osvers="$3"
```

```
;;
```

```
dragonfly) osname=dragonfly
```

```
  osvers="$3"
```

```
;;
```

```

?X: uname -a returns
?X: DYNIX/ptx xxx 4.0 V4.1.2 i386
dynixptx*) osname=dynixptx
osvers=`echo
"$4"|sed 's/^v//'^
;;
freebsd) osname=freebsd
osvers="$3" ;;
genix) osname=genix ;;
?X: GNU/Hurd uname -a gives something like:
?X: GNU foo 0.3 GNU-Mach 1.4/Hurd-0.3 i386-AT386 GNU
?X: GNU gnu 0.3 GNUmach-1.2/Hurd-0.3 i386-AT386 GNU
?X: Note the hostname on the second one, which will fool Configure
?X: into using the SysV case!
gnu) osname=gnu
osvers="$3" ;;
?X: HP-UX uname -a gives something like
?X: HP-UX foobar B.10.20 A 9000/735 2016483812 two-user license
?X: Preserve the full 10.20 string instead of the previous plain '10'.
?X: Thanks to Graham Barr. --AD 6/30/1998
hp*) osname=hpx
osvers=`echo "$3" | $sed 's,.*\.[0-9]*\.[0-9]*\),\1,'
;;
irix*) osname=irix
case "$3" in
4*) osvers=4 ;;
5*) osvers=5 ;;
*) osvers="$3" ;;
esac
;;
linux) osname=linux
case "$3" in
*) osvers="$3" ;;
esac
$test -f /system/lib/libandroid.so && osname=linux-android
;;
MiNT) osname=mint
;;
netbsd*) osname=netbsd
osvers="$3"
;;
news-os)
osvers="$3"
case "$3" in
4*) osname=newsos4 ;;
*) osname=newsos ;;
esac
;;

```

```

nonstop-ux) osname=nonstopux ;;
openbsd) osname=openbsd
    osvers="$3"
    ;;
os2) osname=os2
    osvers="$4"
    ;;
POSIX-BC | posix-bc ) osname=posix-bc
    osvers="$3"
    ;;
powerux | power_ux | powermax_os | powermaxos | \
powerunix | power_unix) osname=powerux
    osvers="$3"
    ;;
qnx) osname=qnx
    osvers="$4"
    ;;
solaris) osname=solaris
    case "$3" in
    5*) osvers=`echo $3 | $sed 's/^5/2/g` ;;
    *) osvers="$3" ;;
    esac
    ;;
sunos) osname=sunos
    case "$3" in
    5*) osname=solaris
        osvers=`echo $3 | $sed 's/^5/2/g` ;;
    *) osvers="$3" ;;
    esac
    ;;
titanos) osname=titanos
    case "$3" in
    1*) osvers=1 ;;
    2*) osvers=2 ;;
    3*) osvers=3 ;;
    4*) osvers=4 ;;
    *) osvers="$3" ;;
    esac
    ;;
ultrix) osname=ultrix
    osvers="$3"
    ;;
osf1|mls+) case "$5" in
    alpha)
?X: DEC OSF/1 myuname -a output looks like:
    osf1 xxxx t3.2 123.4 alpha
?X: where the version number can be something like [xvt]n.n
        osname=dec_osf

```

```

?X: sizer knows the minor minor version: the letter
  osvers=`sizer -v | awk -FUNIX '{print $2}' | awk '{print $1}' | tr '[A-Z]' '[a-z]' | sed 's/^[xvt]//'^
  case "$osvers" in
  [1-9].[0-9]*) ;;
  *) osvers=`echo "$3" | sed 's/^[xvt]//'^ ;;
  esac
  ;;
hp*) osname=hp_osf1 ;;
mips) osname=mips_osf1 ;;
?X: hp and mips were unsupported Technology Releases -- ADO, 24/10/94
  esac
  ;;
# UnixWare 7.1.2 is known as Open UNIX 8
openunix|unixware) osname=svr5
osvers="$4"
  ;;
uts) osname=uts
osvers="$3"
  ;;
vos) osvers="$3"
  ;;
$2) case "$osname" in
*isc*) ;;
*freebsd*) ;;
svr*)
: svr4.x or possibly later
case "svr$3" in
${osname}*)
osname=svr$3
osvers=$4
  ;;
esac
case "$osname" in
svr4.0)
: Check for ESIX
if test -f /stand/boot ; then
eval `grep '^INITPROG=[a-z/0-9]*$' /stand/boot`
if
test -n "$INITPROG" -a -f "$INITPROG"; then
isesix=`strings -a $INITPROG|grep 'ESIX SYSTEM V/386 Release 4.0`
if test -n "$isesix"; then
osname=esix4
fi
fi
fi
  ;;
esac
  ;;

```

```

*) if test -f /etc/systemid; then
  osname=sco
  set `echo $3 | $sed 's/\./ /g` $4
  if $test -f $src/hints/sco_$1_$2_$3.sh; then
    osvers=$1.$2.$3
  elif $test -f $src/hints/sco_$1_$2.sh; then
    osvers=$1.$2
  elif $test -f $src/hints/sco_$1.sh; then
    osvers=$1
  fi
else
  case "$osname" in
    ") : Still unknown. Probably a generic Sys V.
    osname="sysv"
    osvers="$3"
    ;;
  esac
fi
;;
esac
;;
*) case "$osname" in
    ") : Still unknown. Probably a generic BSD.
    osname="$1"
    osvers="$3"
    ;;
  esac
;;
else
?X: Try to identify sony's NEWS-OS (BSD unix)
if test -f /vmunix -a -f $src/hints/news_os.sh; then
  (what /vmunix | UU/tr '[A-Z]' '[a-z]') > UU/kernel.what
2>&1
  if $contains news-os UU/kernel.what >/dev/null 2>&1; then
    osname=news_os
  fi
  $rm -f UU/kernel.what
?X: Maybe it's OS/2 or DOS or something similar
elif test -d c:/ -o -n "$is_os2" ; then
  set X $myuname
  osname=os2
  osvers="$5"
fi
fi

  case "$targetarch" in
    ") ;;

```

```

*) hostarch=$osname
case "$targetarch" in
  nto*|*-nto-*)
    # Will load qnx.sh, which should change osname to nto
    osname=qnx
    osvers=""
    ;;
  *linux-android*)
    # Catch arm-linux-androideabi, mipsel-linux-android,
    # and i686-linux-android
    osname=linux-android
    osvers=""
    ;;
  *linux*)
    # Something like arm-linux-gnueabi is really just
    # plain linux.
    osname=linux
    osvers=""
    ;;
  *solaris*|*sunos*)
    osname=solaris
    # XXX perhaps we should just assume
    # osvers to be 2, or maybe take the value
    # from targetarch. Using $run before the
    # hints are run is somewhat icky.
    set X ` $run $uname -a 2>/dev/null `
    shift
    case "$3" in
      5*) osvers=`echo $3 | $sed 's/^5/2/g'` ;;
      *) osvers="$3" ;;
    esac
    ;;
  *)
    osname=`echo $targetarch|sed 's,^[^-]*-,`
    osvers=""
    ;;
esac
;;
esac
;;
esac

```

: Now look for a hint file osname_osvers, unless one has been specified already.

```

case "$hintfile" in
  '|')
    file=`echo "${osname}_${osvers}" | $sed -e 's%\.\%_g' -e 's%_$$%'`
    : Also try without trailing minor version numbers.
    xfile=`echo

```

```

$file | $sed -e 's%_[^_]*$%%'^
xxfile=`echo $xfile | $sed -e 's%_[^_]*$%%'^
xxxfile=`echo $xxfile | $sed -e 's%_[^_]*$%%'^
xxxxfile=`echo $xxxfile | $sed -e 's%_[^_]*$%%'^
case "$file" in
") dflt=none ;;
*) case "$osvers" in
") dflt=$file
;;
*) if $test -f $src/hints/$file.sh ; then
dflt=$file
elif $test -f $src/hints/$xfile.sh ; then
dflt=$xfile
elif $test -f $src/hints/$xxfile.sh ; then
dflt=$xxfile
elif $test -f $src/hints/$xxxfile.sh ; then
dflt=$xxxfile
elif $test -f $src/hints/$xxxxfile.sh ; then
dflt=$xxxxfile
elif $test -f "$src/hints/${osname}.sh" ; then
dflt="${osname}"
else
dflt=none
fi
;;
esac
;;
esac
if $test -f Policy.sh ; then
case "$dflt" in
*Policy*) ;;
none) dflt="Policy" ;;
*) dflt="Policy $dflt" ;;
esac
fi
;;
*)
dflt=`echo $hintfile | $sed 's/\,sh$/'^
;;
esac

if $test -f Policy.sh ; then
$cat <<EOM

```

There's also a Policy hint file available, which should make the site-specific (policy) questions easier to answer.
EOM

fi

\$cat <<EOM

You may give one or more space-separated answers, or "none" if appropriate. If you have a handcrafted Policy.sh file or a Policy.sh file generated by a previous run of Configure, you may specify it as well as or instead of OS-specific hints. If hints are provided for your OS, you should use them: although Perl can probably be built without hints on many platforms, using hints often improve performance and may enable features that Configure can't set up on its own. If there are no hints that match your OS, specify "none"; DO NOT give a wrong version or a wrong OS.

EOM

```
rp="Which of these apply, if any?"
. UU/myread
tans=$ans
for file in $stans; do
if $test X$file = XPolicy -a -f Policy.sh; then
. Policy.sh
$cat Policy.sh >> UU/config.sh
elif $test -f $src/hints/$file.sh; then
. $src/hints/$file.sh
$cat $src/hints/$file.sh >> UU/config.sh
elif $test X"$stans" =
X -o X"$stans" = Xnone ; then
: nothing
else
: Give one chance to correct a possible typo.
echo "$file.sh does not exist"
dflt=$file
rp="hint to use instead?"
. UU/myread
for file in $ans; do
if $test -f "$src/hints/$file.sh"; then
. $src/hints/$file.sh
$cat $src/hints/$file.sh >> UU/config.sh
elif $test X$ans = X -o X$ans = Xnone ; then
: nothing
else
echo "$file.sh does not exist -- ignored."
fi
done
fi
done
```

```

hint=recommended
: Remember our hint file for later.
if $test -f "$src/hints/$file.sh" ; then
  hintfile="$file"
else
  hintfile=""
fi
fi
cd UU
?X: From here on, we must use $rsrc instead of $src
@else
: Get old answers, if there is a config file out there
hint=default
hintfile=""
if test -f ../config.sh; then
  echo " "
  rp="I see a config.sh file. Shall I use it to set the defaults?"
  . ./myread
  case "$ans" in
  n*|N*) echo "OK, I'll ignore it.";;
  *) echo "Fetching default answers from your old config.sh file..."
  >&4
  tmp_n="$n"
  tmp_c="$c"
  ../config.sh
  cp ../config.sh .
  n="$tmp_n"
  c="$tmp_c"
  hint=previous
  ;;
  esac
fi
@end
?X: remember, indentation is wrong--RAM
;;
*)
echo " "
echo "Fetching default answers from $config_sh..." >&4
tmp_n="$n"
tmp_c="$c"
cd ..
?X: preserve symbolic links, if any
cp $config_sh config.sh 2>/dev/null
chmod +w config.sh
. ./config.sh
cd UU
cp ../config.sh .
n="$tmp_n"

```

```

c="$tmp_c"
hint=previous
;;
esac
./optdef.sh

```

```

: Restore computed paths
for file in $loclist $strylist; do
eval $file="\$_$file"
done

```

```

@if osname || osvers
cat << EOM

```

Configure uses the operating system name and version to set some defaults. The default value is probably right if the name rings a bell. Otherwise, since spelling matters for me, either accept the default or answer "none" to leave it blank.

```

EOM
@end
@if osname
case "$osname" in
'| ')
case "$hintfile" in
'| |none) dflt=none ;;
*) dflt=`echo $hintfile | $sed -e 's/\.sh$//' -e 's/[_].*$//'^
;;
esac
;;
*) dflt="$osname" ;;
esac
rp="Operating system name?"
./myread
case "$ans" in
none) osname="" ;;
*) osname=`echo "$ans" | $sed -e 's/[ ][ ]*/_/g' | ./tr '[A-Z]' '[a-z]'^
esac
@end
@if osvers
@if osname
echo " "
@end
case "$osvers" in
'| ')
case "$hintfile" in
'| |none) dflt=none ;;
*) dflt=`echo $hintfile | $sed -e 's/\.sh$//' -e 's/^[^_]*//'^

```

```

dflt=`echo $dflt | $sed -e 's/^_/' -e 's/_./g`
case "$dflt" in
'| ') dflt=none ;;
esac
;;
esac
;;
*) dflt="$osvers" ;;
esac
rp="Operating system version?"
./myread
case "$ans" in
none) osvers="" ;;
*) osvers="$ans" ;;
esac

@end

./posthint.sh

```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/modified/Oldconfig.U
```

No license file was found, but licenses were detected in source scan.

```

?RCS: $Id: d_memset.U 1 2006-08-24 12:32:52Z rmanfredi $
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: $Log: d_memset.U,v $
?RCS: Revision 3.0.1.1 1993/09/13 16:03:11 ram
?RCS: patch10: removed text recommending bzero over memset (WAD)
?RCS:
?RCS: Revision 3.0 1993/08/18 12:06:36 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:d_memset: Inlibc
?MAKE: -pick add $@ %<
?S:d_memset:
?S: This variable conditionally defines the HAS_MEMSET symbol, which
?S: indicates to the C program that the memset() routine is available
?S: to set blocks of memory.

```

```
?S:
?C:HAS_MEMSET
(MEMSET):
?C: This symbol, if defined, indicates that the memset routine is available
?C: to set blocks of memory.
?C:
?H:#$d_memset HAS_MEMSET /**/
?H:
?LINT:set d_memset
: see if memset exists
set memset d_memset
eval $inlibc
```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/d_memset.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: Extras.U,v$
?RCS:
?RCS: Copyright (c) 2001, Jarkko Hietaniemi
?RCS:
?RCS: You may distribute under the terms of either the GNU General Public
?RCS: License or the Artistic License, as specified in the README file.
?RCS:
?MAKE:extras: Myread Oldconfig Setvar rm
?MAKE: -pick add $@ %<
?Y:TOP
?S:extras:
?S: This variable holds a list of extra modules to install.
?S:
: See if we want extra modules installed
echo " "
case "$extras" in
") dflt='n';;
*) dflt='y';;
esac
cat <<EOM
Perl can be built with extra modules or bundles of modules which
will be fetched from the CPAN and installed alongside Perl.
```

Notice that you will need access to the CPAN; either via the Internet, or a local copy, for example a CD-ROM or a local CPAN mirror. (You will be asked later to configure the CPAN.pm module which will in turn do the installation of the rest of the extra modules or bundles.)

Notice also that if the modules require

any external software such as libraries and headers (the libz library and the zlib.h header for the Compress::Zlib module, for example) you MUST have any such software already installed, this configuration process will NOT install such things for you.

If this doesn't make any sense to you, just accept the default '\$dflt'.

EOM

```
rp='Install any extra modules (y or n)?'
./myread
case "$ans" in
y|Y)
cat <<EOM
```

Please list any extra modules or bundles to be installed from CPAN, with spaces between the names. The names can be in any format the 'install' command of CPAN.pm will understand. (Answer 'none', without the quotes, to install no extra modules or bundles.)

EOM

```
rp='Extras?'
dflt="$extras"
./myread
extras="$ans"
esac
case "$extras" in
'|none')
val=""
$rm -f ../extras.lst
;;
*) echo "(Saving the list of extras for later...)"
echo "$extras" > ../extras.lst
val="$extras"
;;
esac
set extras
eval $setvar
echo " "
```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/Extras.U
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: i_utime.U 1 2006-08-24 12:32:52Z rmanfredi \$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic Licence,

?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: \$Log: i_utime.U,v \$
?RCS: Revision 3.0 1993/08/18 12:08:47 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:i_utime: Inhdr
?MAKE: -pick add \$@ %<
?S:i_utime:
?S: This variable conditionally defines the I_UTIME symbol, and indicates
?S: whether a C program should include <utime.h>.
?S:.
?C:I_UTIME:
?C: This symbol, if defined, indicates to the C program that it should
?C: include <utime.h>.
?C:.
?H:#\$i_utime I_UTIME /**/
?H:.
?LINT:set i_utime
:
see if this is an utime system
set utime.h i_utime
eval \$inhdr

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/i_utime.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: man1dir.U,v 3.2 1999/07/08 20:57:21 doughera Exp doughera \$
?RCS:
?RCS: Copyright (c) 1996, 1999 Andy Dougherty
?RCS: Copyright (c) 1991-1993, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 3.0.
?RCS:
?RCS: \$Log: man1dir.U,v \$
?RCS: Revision 3.2 1999/07/08 20:57:21 doughera
?RCS: Used installprefix.
?RCS:
?RCS: Revision 3.1 1999/07/08 20:52:19 doughera

```

?RCS: Updated for perl5.005_5x
?RCS:
?RCS: Revision 3.0.1.1 1997/02/28 16:10:29 ram
?RCS: patch61: created
?RCS:
?X: This was originally specific to perl5. Since perl5 has man pages that
?X: go in both man1/ and man3/ directories, we need both man1dir
?X: and
man3dir. This unit is basically dist's mansrc.U with
?X: man1 used instead of man everywhere.
?X:
?MAKE:man1dir man1direxp man1ext installman1dir: cat nroff Loc Oldconfig \
package test Getfile Setprefixvar Prefixit Prefixup sysman Myread \
prefixexp
?MAKE: -pick add $@ %<
?Y:TOP
?D:man1dir="
?S:man1dir:
?S: This variable contains the name of the directory in which manual
?S: source pages are to be put. It is the responsibility of the
?S: Makefile.SH to get the value of this into the proper command.
?S: You must be prepared to do the ~name expansion yourself.
?S:.
?D:man1direxp="
?S:man1direxp:
?S: This variable is the same as the man1dir variable, but is filename
?S: expanded at configuration time, for convenient use in makefiles.
?S:.
?D:installman1dir="
?S:installman1dir:
?S: This variable is really the same as man1direxp, unless you are using
?S: AFS in which case it points to the read/write location whereas
?S: man1direxp only points to the read-only access location.
For extra
?S: portability, you should only use this variable within your makefiles.
?S:.
?S:man1ext:
?S: This variable contains the extension that the manual page should
?S: have: one of 'n', 'l', or '1'. The Makefile must supply the '.'.
?S: See man1dir.
?S:.
?T:lookpath
?LINT:change prefixvar
?LINT:set man1direxp
: determine where manual pages go
set man1dir man1dir none
eval $prefixit
$cat <<EOM

```

```

$spackage has manual pages available in source form.
EOM
case "$nroff" in
nroff)
    echo "However, you don't have nroff, so they're probably useless to you."
    case "$man1dir" in
    *) man1dir="none";;
    esac;;
esac
echo "If you don't want the manual sources installed, answer 'none'."
case "$man1dir" in
'') dflt=none
;;
")
    lookpath="$prefixexp/share/man/man1"
    lookpath="$lookpath $prefixexp/man/man1 $prefixexp/man/l_man/man1"
    lookpath="$lookpath $prefixexp/man/p_man/man1"
    lookpath="$lookpath $prefixexp/man/u_man/man1"
    lookpath="$lookpath $prefixexp/man/man.1"
    ?X: Experience has shown people
    expect man1dir to be under prefix,
    ?X: so we now always put it there. Users who want other behavior
    ?X: can answer interactively or use a command line option.
    ?X: Does user have System V-style man paths.
    case "$sysman" in
    */*_man*) dflt=`./loc . $prefixexp/l_man/man1 $lookpath` ;;
    *) dflt=`./loc . $prefixexp/man/man1 $lookpath` ;;
    esac
    set dflt
    eval $prefixup
    ;;
    *) dflt="$man1dir"
    ;;
    esac
    echo " "
    fn=dn+~
    rp="Where do the main $spackage manual pages (source) go?"
    ./getfile
    if $test "X$man1direxp" != "X$ansexp"; then
        installman1dir="
    fi
    prefixvar=man1dir
    ./setprefixvar

    case "$man1dir" in
    *) man1dir=' '
        installman1dir="";;

```

esac

: What suffix to use on installed man pages

```
case "$man1dir" in
' ')
man1ext='0'
;;
*)
rp="What suffix should be used for the main $spackage man pages?"
case "$man1ext" in
") case "$man1dir" in
*1) dflt=1 ;;
*1p) dflt=1p ;;
*1pm) dflt=1pm ;;
*1) dflt=1;;
*n) dflt=n;;
*o) dflt=o;;
*p) dflt=p;;
*C) dflt=C;;
*L) dflt=L;;
*L1)
dflt=L1;;
*) dflt=1;;
esac
;;
*) dflt="$man1ext";;
esac
./myread
man1ext="$ans"
;;
esac
```

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/installdirs/man1dir.U

No license file was found, but licenses were detected in source scan.

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?MAKE:d_nan: Inlibc

?MAKE: -pick add \$@ %<

?S:d_nan:

?S: This variable conditionally defines HAS_NAN if nan() is

?S: available to generate NaN.

?S:.

?C:HAS_NAN:

?C: This symbol, if defined, indicates that the nan routine is

?C: available to generate NaN.

?C:.

?H:#\$d_nan HAS_NAN /**/

?H:.

?LINT:set d_nan

: see if nan exists

set nan d_nan

eval \$inlibc

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_nan.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: Original Author: Tye McQueen <tye@metronet.com>

?RCS:

?RCS: \$Log: d_stdstdio.U,v \$

?RCS: Revision 3.0.1.3 1997/02/28 15:46:32 ram

?RCS: patch61: merged with perl5's unit

?RCS:

?RCS: Revision 3.0.1.2 1995/07/25 14:06:54 ram

?RCS: patch56: typo fix on ?C: line for FILE_bufsiz

?RCS: patch56: fixed unbalanced parenthesis (ADO)

?RCS: patch56: check whether FILE_cnt and FILE_ptr can be assigned to (ADO)

?RCS:

?RCS: Revision 3.0.1.1 1995/05/12 12:12:11 ram

?RCS: patch54: complete rewrite by Tye McQueen
to fit modern systems

?RCS:

?RCS: Revision 3.0 1993/08/18 12:07:31 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?MAKE:d_stdstdio d_stdibase stdio_ptr stdio_cnt stdio_base \
stdio_bufsiz d_stdio_cnt_lval d_stdio_ptr_lval stdio_filbuf: cat \
+cc +ccflags contains +ldflags +libs rm_try \
Setvar Findhdr Oldconfig

?MAKE: -pick add \$@ %<

?S:d_stdstdio:
 ?S: This variable conditionally defines USE_STDIO_PTR if this system
 ?S: has a FILE structure declaring usable _ptr and _cnt fields (or
 ?S: equivalent) in stdio.h.
 ?S:.

?S:stdio_ptr:
 ?S: This variable defines how, given a FILE pointer, fp, to access the
 ?S: _ptr field (or equivalent) of stdio.h's FILE structure. This will
 ?S: be used to define the macro FILE_ptr(fp).
 ?S:.

?S:d_stdio_ptr_lval:
 ?S: This variable conditionally defines STDIO_PTR_LVALUE if the
 ?S: FILE_ptr macro can be used as an lvalue.
 ?S:.

?S:stdio_cnt:
 ?S: This variable defines how, given a FILE pointer, fp, to access the
 ?S: _cnt field (or equivalent) of
 ?S: stdio.h's FILE structure. This will
 ?S: be used to define the macro FILE_cnt(fp).
 ?S:.

?S:d_stdio_cnt_lval:
 ?S: This variable conditionally defines STDIO_CNT_LVALUE if the
 ?S: FILE_cnt macro can be used as an lvalue.
 ?S:.

?S:stdio_filbuf:
 ?S: This variable defines how, given a FILE pointer, fp, to tell
 ?S: stdio to refill it's internal buffers (?). This will
 ?S: be used to define the macro FILE_filbuf(fp).
 ?S:.

?S:d_stdibase:
 ?S: This variable conditionally defines USE_STDIO_BASE if this system
 ?S: has a FILE structure declaring a usable _base field (or equivalent)
 ?S: in stdio.h.
 ?S:.

?S:stdio_base:
 ?S: This variable defines how, given a FILE pointer, fp, to access the
 ?S: _base field (or equivalent) of stdio.h's FILE structure. This will
 ?S: be used to define the macro FILE_base(fp).
 ?S:.

?S:stdio_bufsiz:
 ?S: This variable defines how, given a FILE pointer, fp, to determine
 ?S: the number of bytes store in the I/O buffer pointer to by the
 ?S: _base field (or equivalent) of stdio.h's
 ?S: FILE structure. This will
 ?S: be used to define the macro FILE_bufsiz(fp).
 ?S:.

?C:USE_STDIO_PTR ~ d_stdstdio (USE_STD_STDIO STDSTDIO):
 ?C: This symbol is defined if the _ptr and _cnt fields (or similar)

?C: of the stdio FILE structure can be used to access the stdio buffer
?C: for a file handle. If this is defined, then the FILE_ptr(fp)
?C: and FILE_cnt(fp) macros will also be defined and should be used
?C: to access these fields.
?C:.
?C:FILE_ptr:
?C: This macro is used to access the _ptr field (or equivalent) of the
?C: FILE structure pointed to by its argument. This macro will always be
?C: defined if USE_STDIO_PTR is defined.
?C:.
?C:STDIO_PTR_LVALUE:
?C: This symbol is defined if the FILE_ptr macro can be used as an
?C: lvalue.
?C:.
?C:FILE_cnt:
?C: This macro is used to access the _cnt field (or equivalent) of the
?C: FILE structure pointed to by its argument. This macro will always be
?C: defined if USE_STDIO_PTR is defined.
?C:.
?C:STDIO_CNT_LVALUE:
?C: This symbol is defined
if the FILE_cnt macro can be used as an
?C: lvalue.
?C:.
?C:FILE_filbuf:
?C: This macro is used to access the internal stdio _filbuf function
?C: (or equivalent), if STDIO_CNT_LVALUE and STDIO_PTR_LVALUE
?C: are defined. It is typically either _filbuf or __filbuf.
?C: This macro will only be defined if both STDIO_CNT_LVALUE and
?C: STDIO_PTR_LVALUE are defined.
?C:.
?H:?d_stdstdio:#\$d_stdstdio USE_STDIO_PTR /**/
?H:?d_stdstdio:#ifdef USE_STDIO_PTR
?H:#define FILE_ptr(fp) \$stdio_ptr
?H:#\$d_stdio_ptr_lval STDIO_PTR_LVALUE /**/
?H:#define FILE_cnt(fp) \$stdio_cnt
?H:#\$d_stdio_cnt_lval STDIO_CNT_LVALUE /**/
?H:?d_stdstdio:#if defined(STDIO_PTR_LVALUE) && defined(STDIO_CNT_LVALUE)
?H:#define FILE_filbuf(fp) \$stdio_filbuf /**/
?H:?d_stdstdio:#endif
?H:?d_stdstdio:#endif
?H:.
?W:d_stdstdio:FILE_ptr FILE_cnt FILE_filbuf
?C:USE_STDIO_BASE ~ d_stdibase:
?C: This symbol is defined if the _base field (or similar) of the
?C: stdio FILE structure can be used to access the stdio buffer
for
?C: a file handle. If this is defined, then the FILE_base(fp) macro

?C: will also be defined and should be used to access this field.

?C: Also, the FILE_bufsiz(fp) macro will be defined and should be used

?C: to determine the number of bytes in the buffer. USE_STDIO_BASE

?C: will never be defined unless USE_STDIO_PTR is.

?C:.

?C:FILE_base:

?C: This macro is used to access the _base field (or equivalent) of the

?C: FILE structure pointed to by its argument. This macro will always be

?C: defined if USE_STDIO_BASE is defined.

?C:.

?C:FILE_bufsiz:

?C: This macro is used to determine the number of bytes in the I/O

?C: buffer pointed to by _base field (or equivalent) of the FILE

?C: structure pointed to its argument. This macro will always be defined

?C: if USE_STDIO_BASE is defined.

?C:.

```
?H:?d_stdibase:#$d_stdibase USE_STDIO_BASE /**/
?H:?d_stdibase:#ifdef USE_STDIO_BASE
?H:#define FILE_base(fp) $stdio_base
?H:#define FILE_bufsiz(fp) $stdio_bufsiz
?H:?d_stdibase:#endif
?H:
?W:d_stdibase:FILE_base
FILE_bufsiz
?LINT:set d_stdstdio d_stdibase
?T:ptr_lval cnt_lval filbuf xxx
?F:!try
: see if _ptr and _cnt from stdio act std
echo " "
if $contains '_IO_fpos_t' `./findhdr stdio.h` >/dev/null 2>&1 ; then
echo "(Looks like you have stdio.h from Linux.)"
case "$stdio_ptr" in
") stdio_ptr='((fp)->_IO_read_ptr)'
ptr_lval=$define
;;
*) ptr_lval=$d_stdio_ptr_lval;;
esac
case "$stdio_cnt" in
") stdio_cnt='((fp)->_IO_read_end - (fp)->_IO_read_ptr)'
cnt_lval=$undef
;;
*) cnt_lval=$d_stdio_cnt_lval;;
esac
case "$stdio_base" in
") stdio_base='((fp)->_IO_read_base)';;
esac
case "$stdio_bufsiz" in
") stdio_bufsiz='((fp)->_IO_read_end - (fp)->_IO_read_base)';;
```

```

esac
else
case "$stdio_ptr" in
") stdio_ptr='((fp)->_ptr)'
ptr_lval=$define
;;
*) ptr_lval=$d_stdio_ptr_lval;;
esac
case "$stdio_cnt" in
") stdio_cnt='((fp)->_cnt)'
cnt_lval=$define
;;
*) cnt_lval=$d_stdio_cnt_lval;;
esac
case "$stdio_base" in
") stdio_base='((fp)->_base)';;
esac
case
"$stdio_bufsiz" in
") stdio_bufsiz='((fp)->_cnt + (fp)->_ptr - (fp)->_base)';;
esac
fi
: test whether _ptr and _cnt really work
echo "Checking how std your stdio is..." >&4
$cat >try.c <<EOP
#include <stdio.h>
#define FILE_ptr(fp) $stdio_ptr
#define FILE_cnt(fp) $stdio_cnt
int main() {
FILE *fp = fopen("try.c", "r");
char c = getc(fp);
if (
18 <= FILE_cnt(fp) &&
strncmp(FILE_ptr(fp), "include <stdio.h>\n", 18) == 0
)
exit(0);
exit(1);
}
EOP
val="$undef"
if $cc $ccflags $ldflags -o try try.c $libs >/dev/null 2>&1; then
if ./try; then
echo "Your stdio acts pretty std."
val="$define"
else
echo "Your stdio isn't very std."
fi
else

```

```

echo "Your stdio doesn't appear very std."
fi
$rm_try
set d_stdstdio
eval $setvar

@if STDIO_PTR_LVALUE || d_stdio_ptr_lval
: Can _ptr be used as an lvalue?
?X: Only makes sense if we have a known stdio implementation.
case "$d_stdstdio$ptr_lval" in
$define$define) val=$define ;;
*) val=$undef ;;
esac
set d_stdio_ptr_lval
eval
$setvar

@end

@if STDIO_CNT_LVALUE || d_stdio_cnt_lval
: Can _cnt be used as an lvalue?
?X: Only makes sense if we have a known stdio implementation.
case "$d_stdstdio$cnt_lval" in
$define$define) val=$define ;;
*) val=$undef ;;
esac
set d_stdio_cnt_lval
eval $setvar

@end

@if FILE_filbuf
: How to access the stdio _filbuf or __filbuf function.
: If this fails, check how the getc macro in stdio.h works.
case "${d_stdio_ptr_lval}${d_stdio_cnt_lval}" in
${define}${define})
: Try hint value, if any, then _filbuf, __filbuf, _fill, then punt.
: _fill is for OS/2.
xxx='notok'
for filbuf in $stdio_filbuf '_filbuf(fp)' '__filbuf(fp)' '_fill(fp)'; do
$cat >try.c <<EOP
#include <stdio.h>
#define FILE_ptr(fp) $stdio_ptr
#define FILE_cnt(fp) $stdio_cnt
#define FILE_filbuf(fp) $filbuf
int main() {
FILE *fp = fopen("try.c", "r");
int c;
c = getc(fp);
c = FILE_filbuf(fp); /* Just looking for linker errors.*/

```

```

exit(0);
}
EOP
if $cc $cflags $ldflags -o try try.c $libs >/dev/null 2>&1 &&
./try; then
echo "Your stdio appears to use $filbuf"
stdio_filbuf="$filbuf"
xxx='ok'
break
else
echo "Hmm. $filbuf doesn't seem to work."
fi
$rm_try
done
case "$xxx" in
notok) echo "I can't figure out how to access _filbuf"
echo "I'll just have to work around it."
d_stdio_ptr_lval="$undef"
d_stdio_cnt_lval="$undef"
;;
esac
;;
esac
@end
@if d_stdibase || USE_STDIO_BASE || FILE_base || FILE_bufsiz
: see if _base is also standard
val="$undef"
case "$d_stdstdio" in
$define)
$cat >try.c <<EOP
#include <stdio.h>
#define FILE_base(fp) $stdio_base
#define FILE_bufsiz(fp) $stdio_bufsiz
int main() {
FILE *fp = fopen("try.c", "r");
char c = getc(fp);
if (
19 <= FILE_bufsiz(fp) &&
strncmp(FILE_base(fp), "#include <stdio.h>\n", 19) == 0
)
exit(0);
exit(1);
}
EOP
if $cc $cflags $ldflags -o try try.c $libs > /dev/null 2>&1; then
if ./try; then
echo "And its _base field acts std."
val="$define"

```

```

else
  echo "But its _base field isn't std."
fi
else
  echo
  "However, it seems to be lacking the _base field."
fi
$rm_try
;;
esac
set d_stdibase
eval $setvar

@end

```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/d_stdstdio.U
```

No license file was found, but licenses were detected in source scan.

```

?RCS: $Id: Whoa.U,v 3.0.1.2 1997/02/28 15:21:21 ram Exp $
?RCS:
?RCS: Copyright (c) 1991-1993, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 3.0.
?RCS:
?RCS: $Log: Whoa.U,v $
?RCS: Revision 3.0.1.2 1997/02/28 15:21:21 ram
?RCS: patch61: whoa script now starts with leading "startsh"
?RCS:
?RCS: Revision 3.0.1.1 1994/10/29 16:02:01 ram
?RCS: patch36: added ?F: line for metalint file checking
?RCS:
?RCS: Revision 3.0 1993/08/18 12:05:19 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?X:
?X: This unit produces a bit of shell code that must be dotted in in order
?X: to warn the user in case a change into a variable
?X: is noticed.
?X:
?X: To use this unit, $was must hold the old value that has changed. Upon
?X: exit, the two variables $td and $tu are set to the correct value for
?X: respectively defining or undefining a variable. For instance, if $vas was

```

```

?X: $undef, but now $var is $define, after calling . whoa, you should use
?X: eval "$var=\$tu" to finally set $var to the correct value. See unit Inlibc.
?X:
?MAKE:Whoa: Myread startsh hint
?MAKE: -pick add $@ %<
?F:./whoa
?T:var was td tu hintfile
: set up the script used to warn in case of inconsistency
cat <<EOS >whoa
$startsh
EOS
cat <<'EOSC' >>whoa
dflt=y
case "$hint" in
    recommended)
case "$hintfile" in
    *) echo "The $hint value for \$$var on this machine was \"\$was\!" ">&4
    ;;
    *) echo "Hmm. Based on the hints in hints/$hintfile.sh, " ">&4
    echo "the $hint value for \$$var on this machine was \"\$was\!" ">&4
    ;;
esac
;;
*) echo " "
echo "**** WHOA THERE!!! ****" ">&4
echo " The $hint value for \$$var on this machine was
\"$was\!" ">&4
;;
esac
rp=" Keep the $hint value?"
./myread
case "$ans" in
y) td=$was; tu=$was;;
esac
EOSC

```

Found in path(s):

```

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/modified/Whoa.U

```

No license file was found, but licenses were detected in source scan.

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?MAKE:d_fma: Inlibc

?MAKE: -pick add \$@ %<

?S:d_fma:

?S: This variable conditionally defines the HAS_FMA symbol, which

?S: indicates to the C program that the fma() routine is available.

?S:.

?C:HAS_FMA:

?C: This symbol, if defined, indicates that the fma routine is

?C: available to do the multiply-add function.

?C:.

?H:#\$d_fma HAS_FMA /**/

?H:.

?LINT:set d_fma

: see if fma exists

set fma d_fma

eval \$inlibc

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_fma.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_perror.U 1 2006-08-24 12:32:52Z rmanfredi \$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic Licence,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic Licence; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: d_perror.U,v \$

?RCS: Revision 3.0.1.1 1994/08/29 16:11:38 ram

?RCS: patch32: always define HAS_PERROR even when not used in C code

?RCS:

?RCS: Revision 3.0 1993/08/18 12:06:45 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?MAKE:d_perror: Inlibc

?MAKE: -pick add \$@ %<

?S:d_perror:

?S: This variable conditionally remaps perror to a null action and

?S: defines the symbol HAS_PERROR, which indicates to the C program

?S: that the perror()

routine is not available to print system

?S: error messages.

?S:.

?C:HAS_PERROR ~ %<:

?C: This symbol, if defined, indicates that the perror() routine is

?C: available to print system error messages. If not defined, you should

?C: use your own diagnostic routine...

```

?C:.
?C:perror ~ %<:
?C: This symbol is mapped to null if the perror() routine is not
?C: available to print system error messages.
?C:.
?H:?%<:#$d_perror HAS_PERROR /**/
?H:?%<:#ifndef HAS_PERROR
?H:?%<:#define perror(s) ; /* mapped to a null statement */
?H:?%<:#endif
?H:.
?LINT:set d_perror
: see if perror exists
set perror d_perror
eval $inlibc

```

Found in path(s):

```

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/d_perror.U

```

No license file was found, but licenses were detected in source scan.

```

?RCS: $Id$
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: $Log: patchlevel.U,v $
?RCS: Revision 3.0.1.1 1997/02/28 16:18:41 ram
?RCS: patch61: added support for src.U
?RCS:
?RCS: Revision 3.0 1993/08/18 12:09:31 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:patchlevel: package baserev test rsrc
?MAKE: -pick add $@ %<
?T:Revision
?S:patchlevel:
?S: The patchlevel level of this package.
?S: The value of patchlevel comes from the patchlevel.h file.
?S:.
: get the patchlevel
echo " "
echo "Getting the current patchlevel..." >&4
if $test -r

```

```

$src/patchlevel.h;then
patchlevel=`awk \
  '/^#[ ]*define[ ][*]PATCHLEVEL/ {print $3}' \
  < $src/patchlevel.h`
else
patchlevel=0
fi
echo "(You have $package $baserev PL,$patchlevel.)"

```

Found in path(s):

```

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/patchlevel.U

```

No license file was found, but licenses were detected in source scan.

```

?RCS: $Id: d_endprotoent_r.U,v ORCS:
?RCS: Copyright (c) 2002,2003 Jarkko Hietaniemi
?RCS:
?RCS: You may distribute under the terms of either the GNU General Public
?RCS: License or the Artistic License, as specified in the README file.
?RCS:
?RCS: Generated by the reentr.pl from the Perl 5.8 distribution.
?RCS:
?MAKE:d_endprotoent_r endprotoent_r_proto: Inlibc Protochk Hasproto \
i_systypes usethreads i_netdb extern_C
?MAKE: -pick add $@ %<
?S:d_endprotoent_r:
?S: This variable conditionally defines the HAS_ENDPROTOENT_R symbol,
?S: which indicates to the C program that the endprotoent_r()
?S: routine is available.
?S:.
?S:endprotoent_r_proto:
?S: This variable encodes the prototype of endprotoent_r.
?S: It is zero if d_endprotoent_r is undef, and one of the
?S: REENTRANT_PROTO_T_ABC macros of reentr.h if d_endprotoent_r
?S: is defined.
?S:.
?C:HAS_ENDPROTOENT_R:
?C: This symbol, if defined, indicates that the endprotoent_r
routine
?C: is available to endprotoent re-entrantly.
?C:.
?C:ENDPROTOENT_R_PROTO:
?C: This symbol encodes the prototype of endprotoent_r.
?C: It is zero if d_endprotoent_r is undef, and one of the
?C: REENTRANT_PROTO_T_ABC macros of reentr.h if d_endprotoent_r
?C: is defined.
?C:.
?H:#$d_endprotoent_r HAS_ENDPROTOENT_R /**/

```

```

?H:#define ENDPROTOENT_R_PROTO $endprotoent_r_proto  /**/
?H:.
?T:try hdrs d_endprotoent_r_proto
: see if endprotoent_r exists
set endprotoent_r d_endprotoent_r
eval $inlibc
case "$d_endprotoent_r" in
"$define")
hdrs="$i_systypes sys/types.h define stdio.h $i_netdb netdb.h"
case "$d_endprotoent_r_proto:$susetheads" in
":define") d_endprotoent_r_proto=define
set d_endprotoent_r_proto endprotoent_r $hdrs
eval $hasproto ;;
*) ;;
esac
case "$d_endprotoent_r_proto" in
define)
case "$endprotoent_r_proto" in
"|0) try='int endprotoent_r(struct protoent_data*);'
./prochck "$sextern_C $try" $hdrs && endprotoent_r_proto=I_D ;;
esac
case "$endprotoent_r_proto"
in
"|0) try='void endprotoent_r(struct protoent_data*);'
./prochck "$sextern_C $try" $hdrs && endprotoent_r_proto=V_D ;;
esac
case "$endprotoent_r_proto" in
"|0) d_endprotoent_r=undef
endprotoent_r_proto=0
echo "Disabling endprotoent_r, cannot determine prototype." >&4 ;;
* ) case "$endprotoent_r_proto" in
REENTRANT_PROTO*) ;;
*) endprotoent_r_proto="REENTRANT_PROTO_$endprotoent_r_proto" ;;
esac
echo "Prototype: $try" ;;
esac
;;
*) case "$susetheads" in
define) echo "endprotoent_r has no prototype, not using it." >&4 ;;
esac
d_endprotoent_r=undef
endprotoent_r_proto=0
;;
esac
;;
*) endprotoent_r_proto=0
;;
esac

```

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/threads/d_endprotoent_r.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_stdstdio.U,v 3.0.1.3 1997/02/28 15:46:32 ram Exp \$

?RCS:

?RCS: Copyright (c) 1991-1993, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 3.0.

?RCS:

?RCS: Original Author: Tye McQueen <tye@metronet.com>

?RCS:

?RCS: \$Log: d_stdstdio.U,v \$

?RCS: Revision 3.0.1.3 1997/02/28 15:46:32 ram

?RCS: patch61: merged with perl5's unit

?RCS:

?RCS: Revision 3.0.1.2 1995/07/25 14:06:54 ram

?RCS: patch56: typo fix on ?C: line for FILE_bufsiz

?RCS: patch56: fixed unbalanced parenthesis (ADO)

?RCS: patch56: check whether FILE_cnt and FILE_ptr can be assigned to (ADO)

?RCS:

?RCS: Revision 3.0.1.1 1995/05/12 12:12:11 ram

?RCS:

patch54: complete rewrite by Tye McQueen to fit modern systems

?RCS:

?RCS: Revision 3.0 1993/08/18 12:07:31 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?MAKE:d_stdstdio d_stdiobase stdio_ptr stdio_cnt \
d_stdio_ptr_lval_sets_cnt d_stdio_ptr_lval_nochange_cnt stdio_base \
stdio_bufsiz d_stdio_cnt_lval d_stdio_ptr_lval stdio_filbuf: cat \
Compile contains rm_try d_gnulibc gnulibc_version i_stdlib \
Setvar Findhdr Oldconfig run to

?MAKE: -pick weed \$@ %<

?S:d_stdstdio:

?S: This variable conditionally defines USE_STDIO_PTR if this system

?S: has a FILE structure declaring usable _ptr and _cnt fields (or

?S: equivalent) in stdio.h.

?S:.

?S:stdio_ptr:

?S: This variable defines how, given a FILE pointer, fp, to access the

?S: _ptr field (or equivalent) of stdio.h's FILE structure. This will

?S: be used to define the macro FILE_ptr(fp).
 ?S:.
 ?S:d_stdio_ptr_lval:
 ?S: This variable conditionally defines STDIO_PTR_LVALUE if the
 ?S: FILE_ptr macro can be used as an lvalue.
 ?S:.
 ?S:stdio_cnt:
 ?S: This
 variable defines how, given a FILE pointer, fp, to access the
 ?S: _cnt field (or equivalent) of stdio.h's FILE structure. This will
 ?S: be used to define the macro FILE_cnt(fp).
 ?S:.
 ?S:d_stdio_cnt_lval:
 ?S: This variable conditionally defines STDIO_CNT_LVALUE if the
 ?S: FILE_cnt macro can be used as an lvalue.
 ?S:.
 ?S:d_stdio_ptr_lval_sets_cnt:
 ?S: This symbol is defined if using the FILE_ptr macro as an lvalue
 ?S: to increase the pointer by n has the side effect of decreasing the
 ?S: value of File_cnt(fp) by n.
 ?S:.
 ?S:d_stdio_ptr_lval_nochange_cnt:
 ?S: This symbol is defined if using the FILE_ptr macro as an lvalue
 ?S: to increase the pointer by n leaves File_cnt(fp) unchanged.
 ?S:.
 ?S:stdio_filbuf:
 ?S: This variable defines how, given a FILE pointer, fp, to tell
 ?S: stdio to refill its internal buffers (?). This will
 ?S: be used to define the macro FILE_filbuf(fp).
 ?S:.
 ?S:d_stdibase:
 ?S: This variable conditionally defines USE_STDIO_BASE if this system
 ?S: has
 a FILE structure declaring a usable _base field (or equivalent)
 ?S: in stdio.h.
 ?S:.
 ?S:stdio_base:
 ?S: This variable defines how, given a FILE pointer, fp, to access the
 ?S: _base field (or equivalent) of stdio.h's FILE structure. This will
 ?S: be used to define the macro FILE_base(fp).
 ?S:.
 ?S:stdio_bufsiz:
 ?S: This variable defines how, given a FILE pointer, fp, to determine
 ?S: the number of bytes store in the I/O buffer pointer to by the
 ?S: _base field (or equivalent) of stdio.h's FILE structure. This will
 ?S: be used to define the macro FILE_bufsiz(fp).
 ?S:.
 ?C:USE_STDIO_PTR ~ d_stdstdio (USE_STD_STDIO STDSTDIO):

?C: This symbol is defined if the `_ptr` and `_cnt` fields (or similar) of the `stdio FILE` structure can be used to access the `stdio` buffer for a file handle. If this is defined, then the `FILE_ptr(fp)` and `FILE_cnt(fp)` macros will also be defined and should be used to access these fields.

?C:.

?C:FILE_ptr:

?C: This macro is used to access the `_ptr` field (or equivalent) of the `FILE` structure pointed to by its argument. This macro will always be defined if `USE_STDIO_PTR` is defined.

?C:.

?C:STDIO_PTR_LVALUE:

?C: This symbol is defined if the `FILE_ptr` macro can be used as an lvalue.

?C:.

?C:FILE_cnt:

?C: This macro is used to access the `_cnt` field (or equivalent) of the `FILE` structure pointed to by its argument. This macro will always be defined if `USE_STDIO_PTR` is defined.

?C:.

?C:STDIO_CNT_LVALUE:

?C: This symbol is defined if the `FILE_cnt` macro can be used as an lvalue.

?C:.

?C:STDIO_PTR_LVAL_SETS_CNT:

?C: This symbol is defined if using the `FILE_ptr` macro as an lvalue to increase the pointer by `n` has the side effect of decreasing the value of `File_cnt(fp)` by `n`.

?C:.

?C:STDIO_PTR_LVAL_NOCHANGE_CNT:

?C: This symbol is defined if using the `FILE_ptr` macro as an lvalue to increase the pointer by `n` leaves `File_cnt(fp)` unchanged.

?C:.

?C:FILE_filbuf:

?C: This macro is used to access the internal `stdio _filbuf` function (or equivalent), if `STDIO_CNT_LVALUE` and `STDIO_PTR_LVALUE` are defined. It is typically either `_filbuf` or `__filbuf`.

?C: This macro will only be defined if both `STDIO_CNT_LVALUE` and `STDIO_PTR_LVALUE` are defined.

?C:.

```
?H:?d_stdstdio:#$d_stdstdio USE_STDIO_PTR /**/
?H:?d_stdstdio:#ifdef USE_STDIO_PTR
?H:#define FILE_ptr(fp) $stdio_ptr
?H:#$d_stdstdio_ptr_lval STDIO_PTR_LVALUE /**/
?H:#define FILE_cnt(fp) $stdio_cnt
?H:#$d_stdstdio_cnt_lval STDIO_CNT_LVALUE /**/
```

```

?H:#$d_stdio_ptr_lval_sets_cnt STDIO_PTR_LVAL_SETS_CNT /**/
?H:#$d_stdio_ptr_lval_nochange_cnt STDIO_PTR_LVAL_NOCHANGE_CNT /**/
?H:?FILE_filbuf:#if defined(STDIO_PTR_LVALUE) && defined(STDIO_CNT_LVALUE)
?H:?FILE_filbuf:#define FILE_filbuf(fp) $stdio_filbuf /**/
?H:?FILE_filbuf:#endif
?H:?d_stdstdio:#endif
?H:.
?W:d_stdstdio:FILE_ptr FILE_cnt FILE_filbuf
?C:USE_STDIO_BASE ~ d_stdibase:
?C: This symbol is defined if the _base field (or similar) of the
?C: stdio FILE structure can be used to access
the stdio buffer for
?C: a file handle. If this is defined, then the FILE_base(fp) macro
?C: will also be defined and should be used to access this field.
?C: Also, the FILE_bufsiz(fp) macro will be defined and should be used
?C: to determine the number of bytes in the buffer. USE_STDIO_BASE
?C: will never be defined unless USE_STDIO_PTR is.
?C:.
?C:FILE_base:
?C: This macro is used to access the _base field (or equivalent) of the
?C: FILE structure pointed to by its argument. This macro will always be
?C: defined if USE_STDIO_BASE is defined.
?C:.
?C:FILE_bufsiz:
?C: This macro is used to determine the number of bytes in the I/O
?C: buffer pointed to by _base field (or equivalent) of the FILE
?C: structure pointed to its argument. This macro will always be defined
?C: if USE_STDIO_BASE is defined.
?C:.
?H:?d_stdibase:#$d_stdibase USE_STDIO_BASE /**/
?H:?d_stdibase:#ifdef USE_STDIO_BASE
?H:#define FILE_base(fp) $stdio_base
?H:#define FILE_bufsiz(fp) $stdio_bufsiz
?H:?d_stdibase:#endif
?H:.
?W:d_stdibase:FILE_base
FILE_bufsiz
?T:ptr_lval cnt_lval filbuf xxx
?F:!try
?LINT:set d_stdstdio d_stdibase
: see if _ptr and _cnt from stdio act std
echo " "

if $contains '_lbfsize' `./findhdr stdio.h` >/dev/null 2>&1 ; then
echo "(Looks like you have stdio.h from BSD.)"
case "$stdio_ptr" in
") stdio_ptr='((fp)->_p)'
ptr_lval=$define

```

```

;;
*) ptr_lval=$d_stdio_ptr_lval;;
esac
case "$stdio_cnt" in
") stdio_cnt='((fp)->_r)'
cnt_lval=$define
;;
*) cnt_lval=$d_stdio_cnt_lval;;
esac
case "$stdio_base" in
") stdio_base='((fp)->_ub._base ? (fp)->_ub._base : (fp)->_bf._base)';;
esac
case "$stdio_bufsiz" in
") stdio_bufsiz='((fp)->_ub._base ? (fp)->_ub._size : (fp)->_bf._size)';;
esac
elif $contains '_IO_fpos_t' `./findhdr stdio.h` `./findhdr libio.h` >/dev/null 2>&1 ; then
echo "(Looks like you have stdio.h from Linux.)"
case "$stdio_ptr" in
") stdio_ptr='((fp)->_IO_read_ptr)'
ptr_lval=$define
;;
*) ptr_lval=$d_stdio_ptr_lval;;
esac
case "$stdio_cnt"
in
") stdio_cnt='((fp)->_IO_read_end - (fp)->_IO_read_ptr)'
cnt_lval=$undef
;;
*) cnt_lval=$d_stdio_cnt_lval;;
esac
case "$stdio_base" in
") stdio_base='((fp)->_IO_read_base)';;
esac
case "$stdio_bufsiz" in
") stdio_bufsiz='((fp)->_IO_read_end - (fp)->_IO_read_base)';;
esac
else
case "$stdio_ptr" in
") stdio_ptr='((fp)->_ptr)'
ptr_lval=$define
;;
*) ptr_lval=$d_stdio_ptr_lval;;
esac
case "$stdio_cnt" in
") stdio_cnt='((fp)->_cnt)'
cnt_lval=$define
;;
*) cnt_lval=$d_stdio_cnt_lval;;

```

```

esac
case "$stdio_base" in
") stdio_base='((fp)->_base)';;
esac
case "$stdio_bufsiz" in
") stdio_bufsiz='((fp)->_cnt + (fp)->_ptr - (fp)->_base)';;
esac
fi

```

: test whether _ptr and _cnt really work

```
echo "Checking how std your stdio is..." >&4
```

```
$cat >try.c <<EOP
```

```
#include <stdio.h>
```

```
#i_stdlib I_STDLIB
```

```
#ifdef I_STDLIB
```

```
#include <stdlib.h>
```

```
#endif
```

```
#define FILE_ptr(fp) $stdio_ptr
```

```
#define FILE_cnt(fp) $stdio_cnt
```

```
int main() {
```

```
FILE *fp = fopen("try.c", "r");
```

```
char c =
```

```
getc(fp);
```

```
if (
```

```
18 <= FILE_cnt(fp) &&
```

```
strcmp(FILE_ptr(fp), "include <stdio.h>\n", 18) == 0
```

```
)
```

```
exit(0);
```

```
exit(1);
```

```
}
```

```
EOP
```

```
val="$undef"
```

```
set try
```

```
if eval $compile && $to try.c; then
```

```
if $run ./try; then
```

```
echo "Your stdio acts pretty std."
```

```
val="$define"
```

```
else
```

```
echo "Your stdio isn't very std."
```

```
fi
```

```
else
```

```
echo "Your stdio doesn't appear very std."
```

```
fi
```

```
$rm_try
```

```
# glibc 2.2.90 and above apparently change stdio streams so Perl's
```

```
# direct buffer manipulation no longer works. The Configure tests
```

```
# should be changed to correctly detect this, but until then,
```

```

# the following check should at least let perl compile and run.
# (This quick fix should be updated before 5.8.1.)
# To be defensive, reject all unknown versions, and all versions > 2.2.9.
# A. Dougherty, June 3, 2002.
case "$d_gnulibc" in
$define)
case "$gnulibc_version" in
2.[01]*) ;;
2.2) ;;
2.2.[0-9]) ;;
*) echo "But I will not snoop inside glibc $gnulibc_version stdio buffers."
val="$undef"
;;
esac
;;
esac
set d_stdstdio
eval
$setvar

```

```

@if STDIO_PTR_LVALUE || d_stdio_ptr_lval
: Can _ptr be used as an lvalue?
?X: Only makes sense if we have a known stdio implementation.
case "$d_stdstdio$ptr_lval" in
$define$define) val=$define ;;
*) val=$undef ;;
esac
set d_stdio_ptr_lval
eval $setvar
@end

```

```

@if STDIO_CNT_LVALUE || d_stdio_cnt_lval
: Can _cnt be used as an lvalue?
?X: Only makes sense if we have a known stdio implementation.
case "$d_stdstdio$cnt_lval" in
$define$define) val=$define ;;
*) val=$undef ;;
esac
set d_stdio_cnt_lval
eval $setvar
@end

```

```

@if FILE_filbuf
: How to access the stdio _filbuf or __filbuf function.
: If this fails, check how the getc macro in stdio.h works.
case "${d_stdio_ptr_lval}${d_stdio_cnt_lval}" in
${define}${define})
: Try $hint value, if any, then _filbuf, __filbuf, _fill, then punt.

```

```

: _fill is for os/2.
xxx='notok'
for filbuf in $stdio_filbuf '_filbuf(fp)' '__filbuf(fp)' '_fill(fp)' ; do
  $cat >try.c <<EOP
#include <stdio.h>
#i_stdlib I_STDLIB
#ifdef I_STDLIB
#include
  <stdlib.h>
#endif
#define FILE_ptr(fp) $stdio_ptr
#define FILE_cnt(fp) $stdio_cnt
#define FILE_filbuf(fp) $filbuf
int main() {
  FILE *fp = fopen("try.c", "r");
  int c;
  c = getc(fp);
  c = FILE_filbuf(fp); /* Just looking for linker errors.*/
  exit(0);
}
EOP
set try
if eval $compile && $to try.c && $run ./try; then
  echo "Your stdio appears to use $filbuf"
  stdio_filbuf="$filbuf"
  xxx='ok'
  break
else
  echo "Hmm. $filbuf doesn't seem to work."
fi
$rm_try
done
case "$xxx" in
notok) echo "I can't figure out how to access _filbuf"
  echo "I'll just have to work around it."
  d_stdio_ptr_lval="$undef"
  d_stdio_cnt_lval="$undef"
  ;;
esac
;;
esac
@end

@if STDIO_PTR_LVALUE
: test whether setting _ptr sets _cnt as a side effect
d_stdio_ptr_lval_sets_cnt="$undef"
d_stdio_ptr_lval_nochange_cnt="$undef"
case "$d_stdio_ptr_lval$d_stdstdio" in

```

```

$define$define)
echo "Checking to see what happens if we set the stdio ptr..." >&4
$cat >try.c <<EOP
#include <stdio.h>
/*
Can we scream? */
/* Eat dust sed :-) */
/* In the buffer space, no one can hear you scream. */
#$i_stdlib I_STDLIB
#ifdef I_STDLIB
#include <stdlib.h>
#endif
#define FILE_ptr(fp) $stdio_ptr
#define FILE_cnt(fp) $stdio_cnt
#include <sys/types.h>
int main() {
FILE *fp = fopen("try.c", "r");
int c;
char *ptr;
size_t cnt;
if (!fp) {
puts("Fail even to read");
exit(1);
}
c = getc(fp); /* Read away the first # */
if (c == EOF) {
puts("Fail even to read");
exit(1);
}
if (!(
18 <= FILE_cnt(fp) &&
strcmp(FILE_ptr(fp), "include <stdio.h>\n", 18) == 0
)) {
puts("Fail even to read");
exit (1);
}
ptr = (char*) FILE_ptr(fp);
cnt = (size_t)FILE_cnt(fp);

FILE_ptr(fp) += 42;

if ((char*)FILE_ptr(fp) != (ptr + 42)) {
printf("Fail ptr check %p != %p", FILE_ptr(fp), (ptr + 42));
exit (1);
}
if (FILE_cnt(fp) <= 20) {
printf ("Fail (<20 chars to test)");
exit (1);
}

```

```

}
if (strncmp(FILE_ptr(fp), "Eat dust sed :-) */\n", 20) != 0) {
    puts("Fail compare");
    exit
(1);
}
if (cnt == FILE_cnt(fp)) {
    puts("Pass_unchanged");
    exit (0);
}
if (FILE_cnt(fp) == (cnt - 42)) {
    puts("Pass_changed");
    exit (0);
}
printf("Fail count was %d now %d\n", cnt, FILE_cnt(fp));
return 1;

}
EOP
set try
if eval $compile && $to try.c; then
    case ` $run ./try ` in
        Pass_changed)
            echo "Increasing ptr in your stdio decreases cnt by the same amount. Good." >&4
            d_stdio_ptr_lval_sets_cnt="$define" ;;
        Pass_unchanged)
            echo "Increasing ptr in your stdio leaves cnt unchanged. Good." >&4
            d_stdio_ptr_lval_nochange_cnt="$define" ;;
        Fail*)
            echo "Increasing ptr in your stdio didn't do exactly what I expected. We'll not be doing that then." >&4 ;;
        *)
            echo "It appears attempting to set ptr in your stdio is a bad plan." >&4 ;;
    esac
else
    echo "It seems we can't set ptr in your stdio. Nevermind." >&4
fi
$rm_try
;;
esac
@end

@if d_stdibase || USE_STDIO_BASE || FILE_base || FILE_bufsiz
: see if _base is also standard
val="$undef"
case
"$d_stdstdio" in
$define)
$cat >try.c <<EOP

```

```

#include <stdio.h>
#i_stdlib I_STDLIB
#ifdef I_STDLIB
#include <stdlib.h>
#endif
#define FILE_base(fp) $stdio_base
#define FILE_bufsiz(fp) $stdio_bufsiz
int main() {
FILE *fp = fopen("try.c", "r");
char c =getc(fp);
if (
19 <= FILE_bufsiz(fp) &&
strncmp(FILE_base(fp), "#include <stdio.h>\n", 19) == 0
)
exit(0);
exit(1);
}
EOP
set try
if eval $compile && $to try.c; then
if $run ./try; then
echo "And its _base field acts std."
val="$define"
else
echo "But its _base field isn't std."
fi
else
echo "However, it seems to be lacking the _base field."
fi
$rm_try
;;
esac
set d_stdibase
eval $setvar

@end

```

Found in path(s):

```

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/compline/d_stdstdio.U

```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_siglist.U 1 2006-08-24 12:32:52Z rmanfredi \$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic Licence,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: d_siglist.U,v \$

?RCS: Revision 3.0 1993/08/18 12:07:22 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?MAKE:d_siglist: Csym Setvar

?MAKE: -pick add \$@ %<

?S:d_siglist:

?S: This variable conditionally defines HAS_SYS_SIGLIST if sys_siglist[] is

?S: available to translate signal numbers to strings.

?S:.

?C:HAS_SYS_SIGLIST (SYS_SIGLIST):

?C: This symbol, if defined, indicates that the sys_siglist array is

?C: available to translate signal numbers

to strings.

?C:.

?H:#\$d_siglist HAS_SYS_SIGLIST /**/

?H:.

?LINT:set d_siglist

: see if sys_siglist[] exist

echo " "

if set sys_siglist val -a d_siglist; eval \$csym; \$val; then

echo "You have sys_siglist[] for signal description." >&4

val="\$define"

else

echo "You don't have sys_siglist[]." >&4

val="\$undef"

fi

set d_siglist

eval \$setvar

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/d_siglist.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1999, Jarkko Hietaniemi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 3.0.

```

?RCS:
?MAKE:d_mq_notify: Inlibc
?MAKE: -pick add $@ %<
?S:d_mq_notify:
?S: This variable conditionally defines HAS_MQ_NOTIFY if mq_notify() is
?S: available to ask for a notification from a POSIX message queue.
?S:.
?C:HAS_MQ_NOTIFY:
?C: This symbol, if defined, indicates that the mq_notify system call is
?C: available to ask for a notification from a POSIX message queue.
?C:.
?H:#$d_mq_notify HAS_MQ_NOTIFY /**/
?H:.
?LINT:set d_mq_notify
: see if mq_notify exists
set mq_notify d_mq_notify
eval $inlibc

```

Found in path(s):

```

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/perl/d_mq_notify.U

```

No license file was found, but licenses were detected in source scan.

```

?RCS: $Id: spitshell.U 1 2006-08-24 12:32:52Z rmanfredi $
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: $Log: spitshell.U,v $
?RCS: Revision 3.0.1.4 1997/02/28 16:22:12 ram
?RCS: patch61: removed useless chatter as this is now done very early
?RCS:
?RCS: Revision 3.0.1.3 1995/01/11 15:37:01 ram
?RCS: patch45: use 'test -f' instead of 'test -r' for exec-only cat progs (WED)
?RCS: patch45: protected "sh -c" within backquotes for Linux and SGI
?RCS:
?RCS: Revision 3.0.1.2 1994/08/29 16:33:00 ram
?RCS: patch32: don't create spitshell under the UU directory
?RCS:
?RCS: patch32: allow for cat in /bin or /usr/bin
?RCS:
?RCS: Revision 3.0.1.1 1993/09/13 16:12:58 ram
?RCS: patch10: made #-failure message more friendly (WAD)

```

```

?RCS:
?RCS: Revision 3.0 1993/08/18 12:09:49 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:spitshell shsharp sharpbang: eunicefix sh Head
?MAKE: -pick add $@ %<
?S:spitshell:
?S: This variable contains the command necessary to spit out a runnable
?S: shell on this system. It is either cat or a grep -v for # comments.
?S:.
?S:shsharp:
?S: This variable tells further Configure units whether your sh can
?S: handle # comments.
?S:.
?S:sharpbang:
?S: This variable contains the string #! if this system supports that
?S: construct.
?S:.
?F:!sharp
?T:xcat p
?X: "paths" comes from Head
?LINT:extern paths _exe
: see if sh knows # comments
?X: This is loaded up early, so avoid being chatty.
?X: echo " "
?X: echo "Checking your $sh to see if it knows about # comments..." >&2
if ` $sh -c '#' >/dev/null 2>&1`; then
?X: echo
"Your $sh handles # comments correctly."
shsharp=true
spitshell=cat
?X: echo " "
?X: echo "Okay, let's see if #! works on this system..."
xcat=/bin/cat
test -f $xcat$_exe || xcat=/usr/bin/cat
if test ! -f $xcat$_exe; then
for p in `echo $PATH | sed -e "s/$p_/ /g"` $paths; do
if test -f $p/cat$_exe; then
xcat=$p/cat
break
fi
done
if test ! -f $xcat$_exe; then
echo "Can't find cat anywhere!"
exit 1
fi
fi
echo "#!$xcat" >sharp

```

```

$unicefix sharp
chmod +x sharp
./sharp > today 2>/dev/null
if test -s today; then
?X: echo "It does."
  sharpbang=#!'
else
  echo "#! $xcat" > sharp
$unicefix sharp
chmod +x sharp
./sharp > today 2>/dev/null
if test -s today; then
?X: echo "It does."
  sharpbang=#! '
else
?X: echo "Okay, let's see if #! works on this system..."
?X: echo "It's just a comment."
  sharpbang=: use '
fi
fi
else
echo " "
echo "Your $sh doesn't grok # comments--I will strip them later on."
shsharp=false
?X: The
spitshell script will be perused, so leave it out the UU directory
cd ..
echo "exec grep -v '^[ ]*#' >spitshell
chmod +x spitshell
$unicefix spitshell
spitshell=`pwd`/spitshell
cd UU
echo "I presume that if # doesn't work, #! won't work either!"
sharpbang=: use '
fi
rm -f sharp today

```

Found in path(s):

```

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/spitshell.U

```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 2001 Jarkko Hietaniemi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 3.0.
?RCS:
?MAKE:d_syscallproto: Hasproto i_unistd
?MAKE: -pick add \$@ %<
?S:d_syscallproto:
?S: This variable conditionally defines the HAS_SYSCALL_PROTO symbol,
?S: which indicates to the C program that the system provides
?S: a prototype for the syscall() function. Otherwise, it is
?S: up to the program to supply one.
?S:.
?C:HAS_SYSCALL_PROTO:
?C: This symbol, if defined, indicates that the system provides
?C: a prototype for the syscall() function. Otherwise, it is up
?C: to the program to supply one. Good guesses are
?C: extern
int syscall(int, ...);
?C: extern int syscall(long, ...);
?C:.
?H:#\$d_syscallproto HAS_SYSCALL_PROTO /**/
?H:.
?LINT:set d_syscallproto
: see if prototype for syscall is available
echo " "
set d_syscallproto syscall \$i_unistd unistd.h
eval \$hasproto

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_syscallproto.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_getservprotos.U,v \$
?RCS:
?RCS: Copyright (c) 1991-1993, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 3.0.
?RCS:
?MAKE:d_getservprotos : Hasproto i_netdb
?MAKE: -pick add \$@ %<
?S:d_getservprotos:
?S: This variable conditionally defines the HAS_GETSERV_PROTOS symbol,
?S: which indicates to the C program that <netdb.h> supplies

?S: prototypes for the various getserv*() functions.
 ?S: See also netdbtype.U for probing for various netdb types.
 ?S:.
 ?C:HAS_GETSERV_PROTOS:
 ?C: This symbol, if defined, indicates that <netdb.h> includes
 ?C: prototypes for getservent(), getservbyname(), and
 ?C: getservbyaddr(). Otherwise,
 it is up to the program to guess
 ?C: them. See netdbtype.U for probing for various Netdb_xxx_t types.
 ?C:.
 ?H:#\$d_getservprotos HAS_GETSERV_PROTOS /**/
 ?H:.
 ?LINT:set d_getservprotos
 : see if prototypes for various getservxxx netdb.h functions are available
 echo " "
 set d_getservprotos getservent \$i_netdb netdb.h
 eval \$hasproto

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/protos/d_getservprotos.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: pidtype.U,v 3.0.1.1 1994/08/29 16:31:27 ram Exp \$
 ?RCS:
 ?RCS: Copyright (c) 1991-1993, Raphael Manfredi
 ?RCS:
 ?RCS: You may redistribute only under the terms of the Artistic License,
 ?RCS: as specified in the README file that comes with the distribution.
 ?RCS: You may reuse parts of this distribution only within the terms of
 ?RCS: that same Artistic License; a copy of which may be found at the root
 ?RCS: of the source tree for dist 3.0.
 ?RCS:
 ?RCS: \$Log: pidtype.U,v \$
 ?RCS: Revision 3.0.1.1 1994/08/29 16:31:27 ram
 ?RCS: patch32: now uses new Typedef unit to compute type information
 ?RCS:
 ?RCS: Revision 3.0 1993/08/18 12:09:33 ram
 ?RCS: Baseline for dist 3.0 netwide release.
 ?RCS:
 ?MAKE:pidtype: Myread Typedef
 ?MAKE: -pick add \$@ %<
 ?S:pidtype:
 ?S: This variable defines PIDTYPE to be something like pid_t, int,
 ?S: ushort, or whatever type is used to declare process ids in the kernel.
 ?S:.
 ?C:Pid_t (PIDTYPE):
 ?C: This

symbol holds the type used to declare process ids in the kernel.
?C: It can be int, uint, pid_t, etc... It may be necessary to include
?C: <sys/types.h> to get any typedef'ed information.
?C:.
?H:#define Pid_t \$pidtype /* PID type */
?H:.
?LINT: set pidtype
: see what type pids are declared as in the kernel
rp="What is the type of process ids on this system?"
set pid_t pidtype int stdio.h sys/types.h
eval \$typedef_ask

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/typedefs/pidtype.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_group.U 1 2006-08-24 12:32:52Z rmanfredi \$
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: Original Author: Andy Dougherty <doughera@lafcol.lafayette.edu>
?RCS:
?RCS: \$Log: d_group.U,v \$
?RCS: Revision 3.0.1.2 1997/02/28 15:34:52 ram
?RCS: patch61: useless unit dropped.
?RCS:
?RCS: Revision 3.0.1.1 1994/08/29 16:07:48 ram
?RCS: patch32: created by ADO
?RCS:
?X:
?X: Useless unit dropped.
?X:
?LINT:empty

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/d_group.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_system.U 1 2006-08-24 12:32:52Z rmanfredi \$
?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: \$Log: d_system.U,v \$
?RCS: Revision 3.0 1993/08/18 12:07:44 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:d_system: Inlibc
?MAKE: -pick add \$@ %<
?S:d_system:
?S: This variable conditionally defines HAS_SYSTEM if system() is
?S: available to issue a shell command.
?S:.
?C:HAS_SYSTEM (SYSTEM):
?C: This symbol, if defined, indicates that the system routine is
?C: available to issue a shell command.
?C:.
?H:#\$d_system HAS_SYSTEM /**/
?H:.
?LINT:set
d_system
: see if system exists
set system d_system
eval \$inlibc

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/d_system.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_vfork.U,v 3.0.1.6 1994/08/29 16:18:21 ram Exp \$
?RCS:
?RCS: Copyright (c) 1991-1993, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 3.0.
?RCS:
?RCS: \$Log: d_vfork.U,v \$
?RCS: Revision 3.0.1.6 1994/08/29 16:18:21 ram
?RCS: patch32: set default to 'y' the first time

?RCS:
?RCS: Revision 3.0.1.5 1994/06/20 06:59:14 ram
?RCS: patch30: usevfork was not always properly set
?RCS:
?RCS: Revision 3.0.1.4 1994/05/13 15:20:56 ram
?RCS: patch27: modified to avoid spurious Whoa warnings (ADO)
?RCS:
?RCS: Revision 3.0.1.3 1994/05/06 14:59:09 ram
?RCS: patch23: now explicitly ask whether vfork() should be used
(ADO)
?RCS:
?RCS: Revision 3.0.1.2 1993/10/16 13:49:39 ram
?RCS: patch12: added magic for vfork()
?RCS:
?RCS: Revision 3.0.1.1 1993/09/13 16:06:57 ram
?RCS: patch10: removed automatic remapping of vfork on fork (WAD)
?RCS: patch10: added compatibility code for older config.sh (WAD)
?RCS:
?RCS: Revision 3.0 1993/08/18 12:07:55 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:d_vfork usevfork d_pseudofork: Inlibc Myread Oldconfig Setvar
?MAKE:-pick add \$@ %<
?S:d_vfork:
?S: This variable conditionally defines the HAS_VFORK symbol, which
?S: indicates the vfork() routine is available.
?S:.
?S:usevfork:
?S: This variable is set to true when the user accepts to use vfork.
?S: It is set to false when no vfork is available or when the user
?S: explicitly requests not to use vfork.
?S:.
?S:d_pseudofork:
?S: This variable conditionally defines the HAS_PSEUDOFORK symbol,
?S: which indicates that an emulation of the fork routine is available.
?S:.
?C:HAS_VFORK (VFORK):
?C: This
symbol, if defined, indicates that vfork() exists.
?C:.
?H:#\$d_vfork HAS_VFORK /**/
?H:.
?C:HAS_PSEUDOFORK:
?C: This symbol, if defined, indicates that an emulation of the
?C: fork routine is available.
?C:.
?H:#\$d_pseudofork HAS_PSEUDOFORK /**/
?H:.

```

?M:vfork: HAS_VFORK
?M:#ifndef HAS_VFORK
?M:#define vfork fork
?M:#endif
?M:.
?T:d_hvfork
: backward compatibility for d_hvfork
if test X$d_hvfork != X; then
d_vfork="$d_hvfork"
d_hvfork=""
fi
?X:=====
: see if there is a vfork
val=""
set vfork val
eval $inlibc

d_pseudofork=$undef

: Ok, but do we want to use it. vfork is reportedly unreliable in
: perl on Solaris 2.x, and probably elsewhere.
case "$val" in
$define)
echo " "
case "$usevfork" in
false) dflt='n';;
*) dflt='y';;
esac
cat <<'EOM'

```

Perl can only use a vfork() that doesn't suffer from strict restrictions on calling functions or modifying global data in the child. For example, glibc-2.1 contains such a vfork() that is unsuitable. If your system provides a proper fork() call, chances are that you do NOT want perl to use vfork().

```

EOM
rp="Do you still want to use vfork()?"
./myread
case "$ans" in
y|Y) ;;
*)
echo "Ok, we won't use vfork()."
val="$undef"
;;
esac
;;

```

```
esac
?X:
?X: Only set it when final value is known to avoid spurious Whoa's
?X: Then set usevfork accordingly to the current value, for next run
?X:
set d_vfork
eval $setvar
case "$d_vfork" in
$define) usevfork='true';;
*) usevfork='false';;
esac
```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/modified/d_vfork.U
```

No license file was found, but licenses were detected in source scan.

?RCS:

?RCS: Copyright (c) 2012 Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic Licence,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic Licence; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?MAKE:Assert: cat

?MAKE: -pick add \$@ %<

?F:./static_assert.h

: static assertion checking include file

?X:

?X: C programs can include this file to perform STATIC_ASSERT() checks

?X: which are done at compile-time and cause the compilation to fail when

?X: the expression is false.

?X:

?X: It is sufficient to compile with: \$cc -c \$cflags try.c

?X: There is no need to link the file to spot the assertion failure.

?X:

```
$cat >static_assert.h <<'EOC'
```

```
#define STATIC_ASSERT(expr) \
```

```
do { switch (0) { case ((expr) ? 1 : 0): case 0: break; } }
```

```
while(0)
```

```
EOC
```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/Assert.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id$
?RCS:
?RCS: Copyright (c) 1998, Jarkko Hietaniemi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 3.0.
?RCS:
?MAKE:i_netinettcp: Inhdr
?MAKE: -pick add $@ %<
?S:i_netinettcp:
?S: This variable conditionally defines the I_NETINET_TCP symbol,
?S: and indicates whether a C program should include <netinet/tcp.h>.
?S:.
?C:I_NETINET_TCP:
?C: This symbol, if defined, indicates to the C program that it should
?C: include <netinet/tcp.h>.
?C:.
?H:#$i_netinettcp I_NETINET_TCP /**/
?H:.
?LINT:set i_netinettcp
: see if netinet/tcp.h is available
set netinet/tcp.h i_netinettcp
eval $inhdr
```

Found in path(s):

*

/opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/i_netinettcp.U

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id$
?RCS:
?RCS: Copyright (c) 2014, H.Merijn Brand
?RCS:
?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: $Log: d_dladdr.U,v $
?RCS:
?MAKE:d_dladdr: Inlibc
```

?MAKE: -pick add \$@ %<
 ?S:d_dladdr:
 ?S: This variable conditionally defines the HAS_DLADDR symbol, which
 ?S: indicates to the C program that the dladdr() routine is available
 ?S: to get a stack trace.
 ?S:.
 ?C:HAS_DLADDR:
 ?C: This symbol, if defined, indicates that the dladdr() routine is
 ?C: available to query dynamic linker information for an address.
 ?C: The <dlfcn.h> header must be included to use this routine.
 ?C:.
 ?H:#\$d_dladdr HAS_DLADDR /**/
 ?H:.
 ?LINT:set d_dladdr
 :
 see if dladdr exists
 set dladdr d_dladdr
 eval \$inlibc

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/modified/d_dladdr.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_ctermid_r.U,v ORCS:
 ?RCS: Copyright (c) 2002,2003 Jarkko Hietaniemi
 ?RCS:
 ?RCS: You may distribute under the terms of either the GNU General Public
 ?RCS: License or the Artistic License, as specified in the README file.
 ?RCS:
 ?RCS: Generated by the reentr.pl from the Perl 5.8 distribution.
 ?RCS:
 ?MAKE:d_ctermid_r ctermid_r_proto: Inlibc Protochk Hasproto i_systypes \
 usethreads extern_C
 ?MAKE: -pick add \$@ %<
 ?S:d_ctermid_r:
 ?S: This variable conditionally defines the HAS_CTERMID_R symbol,
 ?S: which indicates to the C program that the ctermid_r()
 ?S: routine is available.
 ?S:.
 ?S:ctermid_r_proto:
 ?S: This variable encodes the prototype of ctermid_r.
 ?S: It is zero if d_ctermid_r is undef, and one of the
 ?S: REENTRANT_PROTO_T_ABC macros of reentr.h if d_ctermid_r
 ?S: is defined.
 ?S:.
 ?C:HAS_CTERMID_R:
 ?C: This symbol, if defined, indicates that the ctermid_r routine

```

?C: is available to ctermid re-entrantly.
?C:.
?C:CTERMID_R_PROTO:
?C: This
symbol encodes the prototype of ctermid_r.
?C: It is zero if d_ctermid_r is undef, and one of the
?C: REENTRANT_PROTO_T_ABC macros of reentr.h if d_ctermid_r
?C: is defined.
?C:.
?H:#$d_ctermid_r HAS_CTERMID_R /**/
?H:#define CTERMID_R_PROTO $ctermid_r_proto /**/
?H:.
?T:try hdrs d_ctermid_r_proto
: see if ctermid_r exists
set ctermid_r d_ctermid_r
eval $inlibc
case "$d_ctermid_r" in
"$define")
hdrs="$i_systypes sys/types.h define stdio.h "
case "$d_ctermid_r_proto:$usethreads" in
":define") d_ctermid_r_proto=define
set d_ctermid_r_proto ctermid_r $hdrs
eval $hasproto ;;
*) ;;
esac
case "$d_ctermid_r_proto" in
define)
case "$ctermid_r_proto" in
"|0) try='char* ctermid_r(char*);'
./protochk "$extern_C $try" $hdrs && ctermid_r_proto=B_B ;;
esac
case "$ctermid_r_proto" in
"|0) d_ctermid_r=undef
ctermid_r_proto=0
echo "Disabling ctermid_r, cannot determine prototype." >&4 ;;
*) case "$ctermid_r_proto" in
REENTRANT_PROTO*)
;;
*) ctermid_r_proto="REENTRANT_PROTO_$ctermid_r_proto" ;;
esac
echo "Prototype: $try" ;;
esac
;;
*) case "$usethreads" in
define) echo "ctermid_r has no prototype, not using it." >&4 ;;
esac
d_ctermid_r=undef
ctermid_r_proto=0

```

```
;;
esac
;;
*) ctermid_r_proto=0
;;
esac
```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/threads/d_ctermid_r.U
```

No license file was found, but licenses were detected in source scan.

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?MAKE:d_expm1: Inlibc

?MAKE: -pick add \$@ %<

?S:d_expm1:

?S: This variable conditionally defines the HAS_EXPM1 symbol, which

?S: indicates to the C program that the expm1() routine is available.

?S:.

?C:HAS_EXPM1:

?C: This symbol, if defined, indicates that the expm1 routine is

?C: available to do the exp(x) - 1 when x is near 1 function.

?C:.

?H:#\$d_expm1 HAS_EXPM1 /**/

?H:.

?LINT:set d_expm1

: see if expm1 exists

set expm1 d_expm1

eval \$inlibc

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_expm1.U
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 2000 Jarkko Hietaniemi

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?MAKE:d_strtoq: Inlibc

?MAKE: -pick add \$@ %<

?S:d_strtoq:

?S: This variable conditionally defines the HAS_STRTOQ symbol, which

?S: indicates to the C program that the strtouq() routine is available.

?S:.

?C:HAS_STRTOQ:

?C: This symbol, if defined, indicates that the strtouq routine is

?C: available to convert strings to long longs (quads).

?C:.

?H:#\$d_strtouq HAS_STRTOQ /**/

?H:.

?LINT:set d_strtouq

: see if strtouq exists

set strtouq d_strtouq

eval \$inlibc

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_strtouq.U

No license file was found, but licenses were detected in source scan.

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?MAKE:d_fmax: Inlibc

?MAKE: -pick add \$@ %<

?S:d_fmax:

?S: This variable conditionally defines the HAS_FMAX symbol, which

?S: indicates to the C program that the fmax() routine is available.

?S:.

?C:HAS_FMAX:

?C: This symbol, if defined, indicates that the fmax routine is

?C: available to do the maximum function.

?C:.

?H:#\$d_fmax HAS_FMAX /**/

?H:.

?LINT:set d_fmax

: see if fmax exists

set fmax d_fmax

eval \$inlibc

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_fmax.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_su_chown.U 1 2006-08-24 12:32:52Z rmanfredi \$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic Licence,

?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: d_su_chown.U,v \$

?RCS: Revision 3.0 1993/08/18 12:07:40 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?MAKE:d_su_chown: Csym Setvar

?MAKE: -pick add \$@ %<

?S:d_su_chown (d_rootchown):

?S: This variable conditionally defines the SU_CHOWN symbol, which

?S: indicates to the C program that only root can chown() the owner

?S: of a file.

?S:.

?C:SU_CHOWN (ROOT_CHOWN):

?C: This symbol, if defined, indicates that the system allows only root

?C: can

change the owner of a file with chown().

?C:.

?H:#\$d_su_chown SU_CHOWN /**/

?H:.

?LINT:set d_su_chown

: see if 'chown()' is restricted.

: but not too hard, as it is late and I am tired. -- HMS

echo " "

if set setreuid val -f d_su_chown; eval \$csym; \$val; then

echo 'It looks like only root can chown() the owner of a file.' >&4

val="\$define"

else

echo 'It looks like root or the owner can chown() a file away.' >&4

val="\$undef"

fi

set d_su_chown

eval \$setvar

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/d_su_chown.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_drem.U 1 2006-08-24 12:32:52Z rmanfredi \$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic Licence,

?RCS: as specified in the README file that comes with the distribution.

```

?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: Original Author: Andy Dougherty <doughera@lafcol.lafayette.edu>
?RCS:
?RCS: $Log: d_drem.U,v $
?RCS: Revision 3.0.1.1 1994/10/29 16:12:14 ram
?RCS: patch36: created by ADO
?RCS:
?MAKE:d_drem: Inlibc
?MAKE: -pick add $@ %<
?S:d_drem:
?S: This variable conditionally defines the HAS_DREM symbol, which
?S: indicates to the C program that the drem() routine is available.
?S:.
?C:HAS_DREM :
?C: This symbol, if defined, indicates that the drem routine is
?C: available.
    This routine is roughly the same as fmod, i.e. it
?C: computes the remainder  $r=x-n*y$ , where  $n=\text{rint}(x/y)$ , whereas fmod
?C: uses  $n=\text{trunc}(x/y)$ .
?C:.
?H:#$d_drem HAS_DREM /**/
?H:.
?LINT:set d_drem
: see if drem exists
set drem d_drem
eval $inlibc

```

Found in path(s):

```

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/d_drem.U

```

No license file was found, but licenses were detected in source scan.

```

?RCS: $Id$
?RCS:
?RCS: Copyright (c) 1998, Jarkko Hietaniemi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 3.0.
?RCS:
?MAKE:i_syssecre: Inhdr
?MAKE: -pick add $@ %<
?S:i_syssecre:

```

?S: This variable conditionally defines the I_SYS_SECURITY symbol,
?S: and indicates whether a C program should include <sys/security.h>.
?S:.
?C:I_SYS_SECURITY:
?C: This symbol, if defined, indicates to the C program that it should
?C: include <sys/security.h>.
?C:.
?H:#\$i_syssecre I_SYS_SECURITY /**/
?H:.
?LINT:set i_syssecre
: see if sys/security.h is available
set sys/security.h i_syssecre
eval \$inhdr

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/acl/i_syssecre.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: i_sfio.U 1 2006-08-24 12:32:52Z rmanfredi \$
?RCS:
?RCS: Copyright (c) 1996, Andy Dougherty
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: \$Log: i_sfio.U,v \$
?RCS: Revision 3.0.1.1 1997/02/28 15:48:27 ram
?RCS: patch61: created
?RCS:
?MAKE:i_sfio: Inhdr Setvar
?MAKE: -pick add \$@ %<
?S:i_sfio:
?S: This variable conditionally defines the I_SFIO symbol,
?S: and indicates whether a C program should include <sfio.h>.
?S:.
?C:I_SFIO:
?C: This symbol, if defined, indicates to the C program that it should
?C: include <sfio.h>.
?C:.
?H:#\$i_sfio I_SFIO /**/
?H:.
?LINT:set

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: d_endgrent_r.U,v 0RCS:
?RCS: Copyright (c) 2002,2003 Jarkko Hietaniemi
?RCS:
?RCS: You may distribute under the terms of either the GNU General Public
?RCS: License or the Artistic License, as specified in the README file.
?RCS:
?RCS: Generated by the reentr.pl from the Perl 5.8 distribution.
?RCS:
?MAKE:d_endgrent_r endgrent_r_proto: Inlibc Protochk Hasproto i_systypes \
  usethreads i_grp extern_C
?MAKE: -pick add $@ %<
?S:d_endgrent_r:
?S: This variable conditionally defines the HAS_ENDGRENT_R symbol,
?S: which indicates to the C program that the endgrent_r()
?S: routine is available.
?S:.
?S:endgrent_r_proto:
?S: This variable encodes the prototype of endgrent_r.
?S: It is zero if d_endgrent_r is undef, and one of the
?S: REENTRANT_PROTO_T_ABC macros of reentr.h if d_endgrent_r
?S: is defined.
?S:.
?C:HAS_ENDGRENT_R:
?C: This symbol, if defined, indicates that the endgrent_r routine
?C: is available to
  endgrent re-entrantly.
?C:.
?C:ENDGRENT_R_PROTO:
?C: This symbol encodes the prototype of endgrent_r.
?C: It is zero if d_endgrent_r is undef, and one of the
?C: REENTRANT_PROTO_T_ABC macros of reentr.h if d_endgrent_r
?C: is defined.
?C:.
?H:#$d_endgrent_r HAS_ENDGRENT_R /**/
?H:#define ENDGRENT_R_PROTO $endgrent_r_proto /**/
?H:.
?T:try hdrs d_endgrent_r_proto
: see if endgrent_r exists
set endgrent_r d_endgrent_r
eval $inlibc
case "$d_endgrent_r" in
"$define")
  hdrs="$i_systypes sys/types.h define stdio.h $i_grp grp.h"
  case "$d_endgrent_r_proto:$usethreads" in
  ":define") d_endgrent_r_proto=define
  set d_endgrent_r_proto endgrent_r $hdrs
```

```

eval $hasproto ;;
*) ;;
esac
case "$d_endgrent_r_proto" in
define)
case "$endgrent_r_proto" in
"|0) try='int endgrent_r(FILE**);'
./protochk "$extern_C $try" $hdrs && endgrent_r_proto=I_H ;;
esac
case "$endgrent_r_proto" in
"|0) try='void endgrent_r(FILE**);'
./protochk "$extern_C $try" $hdrs && endgrent_r_proto=V_H ;;
esac
case
"$endgrent_r_proto" in
"|0) d_endgrent_r=undef
endgrent_r_proto=0
echo "Disabling endgrent_r, cannot determine prototype." >&4 ;;
* ) case "$endgrent_r_proto" in
REENTRANT_PROTO*) ;;
*) endgrent_r_proto="REENTRANT_PROTO_$endgrent_r_proto" ;;
esac
echo "Prototype: $try" ;;
esac
;;
*) case "$usethreads" in
define) echo "endgrent_r has no prototype, not using it." >&4 ;;
esac
d_endgrent_r=undef
endgrent_r_proto=0
;;
esac
;;
*) endgrent_r_proto=0
;;
esac

```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/threads/d_endgrent_r.U
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: newslib.U 1 2006-08-24 12:32:52Z rmanfredi \$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic Licence,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.

?RCS:
?RCS: \$Log: newslib.U,v \$
?RCS: Revision 3.0 1993/08/18 12:09:23 ram
?RCS: Baseline for dist 3.0 netwide release.

?RCS:
?MAKE:newslib newslibexp: test inews Oldconfig Getfile
?MAKE: -pick add \$@ %<
?S:newslib:
?S: This variable contains the eventual value of the NEWSLIB symbol,
?S: which holds the name of the directory serving as the news library.
?S: It may have a ~ on the front. See newslibexp for expanded version.
?S:.
?S:newslibexp:
?S: This variable contains
the ~ expanded name of the news library
?S: directory. See newslib.
?S:.
?C:NEWSLIB:
?C: This symbol contains the name of the directory serving as the news
?C: library. The program must be prepared to do ~ expansion on it.
?C:.
?C:NEWSLIB_EXP:
?C: This symbol is the ~ expanded version of NEWSLIB, for programs that
?C: do not wish to deal with it at run-time.
?C:.
?H:#define NEWSLIB "\$newslib" /**/
?H:#define NEWSLIB_EXP "\$newslibexp" /**/
?H:.
?LINT:change inews
: figure out news library
case "\$newslib" in
")
dflt=/usr/lib/news
;;
*) dflt=\$newslib ;;
esac
echo " "
fn=d~
rp="Where is your news library?"
./getfile
newslib="\$ans"
newslibexp="\$ansexp"
if \$test -f \$newslibexp/inews; then
echo "Aha! Inews is really in \$newslibexp! Maybe this is 2.10.2..." >&4
case "\$inews" in

```

inews)
: null
;;
*) echo "(Make sure $inews isn't an old version.)";;
esac
inews=$newslibexp/inews
fi

```

Found in path(s):

```

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/newslib.U

```

No license file was found, but licenses were detected in source scan.

```

?RCS: $Id: Prefixup.U 1 2006-08-24 12:32:52Z rmanfredi $
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: $Log: Prefixup.U,v $
?RCS: Revision 3.0.1.1 1995/01/30 14:30:40 ram
?RCS: patch49: created
?RCS:
?X:
?X: Used as: "set dflt; eval $prefixup" to set $dflt to be $prefix/dir
?X: instead of $prefixexp/dir, in case portability was involved somehow
?X: and $prefix uses ~name expansion.
?X:
?MAKE:Prefixup: prefix prefixexp
?MAKE: -pick add $@ %<
?LINT:define prefixup
?S:prefixup:
?S: This shell variable is used internally by Configure to reset
?S: the leading
?S: installation prefix correctly when $prefix uses
?S: ~name expansion.
?S: set dflt
?S: eval $prefixup
?S: That will set $dflt to $prefix/dir if it was $prefixexp/dir and
?S: $prefix differs from $prefixexp.
?S:.
?V:prefixup
: set the prefixup variable, to restore leading tilda escape
prefixup='case "$prefixexp" in

```

```
"$prefix") ;;
*) eval "$1=\`echo \$$1 | sed \`s,^$prefixexp,$prefix,\`";;
esac'
```

Found in path(s):

```
*/opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/Prefixup.U
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1997, Chip Salzenberg

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: sh.U,v \$

?RCS: Revision 3.0.1.1 1997/02/28 16:20:13 ram

?RCS: patch61: created

?RCS:

?MAKE:sh: Head

?MAKE: -pick wipe \$@ %<

?S:sh:

?S: This variable contains the full pathname of the shell used

?S: on this system to execute Bourne shell scripts. Usually, this will be

?S: /bin/sh, though it's possible that some systems will have /bin/ksh,

?S: /bin/pdksh, /bin/ash, /bin/bash, or even something such as

?S: D:/bin/sh.exe.

?S: This unit comes before Options.U,

so you can't set sh with a -D

?S: option, though you can override this (and startsh)

?S: with -O -Dsh=/bin/whatever -Dstartsh=whatever

?S:.

?C:SH_PATH:

?C: This symbol contains the full pathname to the shell used on this

?C: on this system to execute Bourne shell scripts. Usually, this will be

?C: /bin/sh, though it's possible that some systems will have /bin/ksh,

?C: /bin/pdksh, /bin/ash, /bin/bash, or even something such as

?C: D:/bin/sh.exe.

?C:.

?H:#define SH_PATH "\$sh" /**/

?H:.

?T:xxx try pth p SYSTYPE

?LINT:extern maintloc maintname

?X:

?X: Be quiet unless something unusual happens because this gets

?X: loaded up even before options are processed.

?X: Can't use ./loc because that depends on startsh, which, in turn

?X: depends on this unit.

?X:

: Find the basic shell for Bourne shell scripts

```
case "$sh" in
```

```
)
```

?X: SYSTYPE is for some older MIPS systems.

?X: I do not know if it is still needed.

```
case "$SYSTYPE" in
```

```
*bsd*|sys5*) xxx="/$SYSTYPE/bin/sh";;
```

```
*) xxx="/bin/sh";;
```

```
esac
```

```
if
```

```
test -f "$xxx"; then
```

```
sh="$xxx"
```

```
else
```

: Build up a list and do a single loop so we can 'break' out.

```
pth=`echo $PATH | sed -e "s/$p_/ /g"``
```

```
for xxx in sh bash ksh pdksh ash; do
```

```
for p in $pth; do
```

```
try="$try ${p}/${xxx}"
```

```
done
```

```
done
```

```
for xxx in $try; do
```

```
if test -f "$xxx"; then
```

```
sh="$xxx"
```

```
break
```

```
elif test -f "$xxx$_exe"; then
```

```
sh="$xxx"
```

```
break
```

```
elif test -f "$xxx.exe"; then
```

```
sh="$xxx"
```

```
break
```

```
fi
```

```
done
```

```
fi
```

```
::
```

```
esac
```

?X: fd 4 isn't open yet...

```
case "$sh" in
```

```
) cat >&2 <<EOM
```

\$me: Fatal Error: I can't find a Bourne Shell anywhere.

Usually it's in /bin/sh. How did you even get this far?

Please contact me (<\$maintname>) at <\$maintloc> and we'll try to straighten this all out.

```
EOM
exit 1
;;
esac
```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/sh.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: i_mntent.U,v $
?RCS:
?RCS: Copyright (c) 1999 Jarkko Hietaniemi
?RCS:
?RCS: You may distribute under the terms of either the GNU General Public
?RCS: License or the Artistic License, as specified in the README file.
?RCS:
?MAKE:i_mntent: Inhdr Hasfield
?MAKE: -pick add $@ %<
?S:i_mntent:
?S: This variable conditionally defines the I_MNTENT symbol, and indicates
?S: whether a C program should include <mntent.h>.
?S:
?C:I_MNTENT:
?C: This symbol, if defined, indicates that <mntent.h> exists and
?C: should be included.
?C:
?H:#$i_mntent I_MNTENT /**/
?H:
?LINT:set i_mntent
: see if this is a mntent.h system
set mntent.h i_mntent
eval $inhdr
```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/i_mntent.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id$
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
```

?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: \$Log: d_fd_set.U,v \$
?RCS: Revision 3.0.1.3 1997/02/28 15:33:16 ram
?RCS: patch61: added ?F: metalint hint
?RCS:
?RCS: Revision 3.0.1.2 1994/06/20 06:57:23 ram
?RCS: patch30: extended scope for fd_set checks (ADO)
?RCS:
?RCS: Revision 3.0.1.1 1994/01/24 14:06:27 ram
?RCS: patch16: comments for HAS_FD_* symbols were not consistent
?RCS:
?RCS: Revision 3.0 1993/08/18 12:06:02 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:d_fd_set d_fd_macros d_fds_bits: cat +cc +ccflags rm Oldconfig
\
d_socket i_systime i_sysselect i_syssock
?MAKE: -pick add \$@ %<
?S:d_fd_set:
?S: This variable contains the eventual value of the HAS_FD_SET symbol,
?S: which indicates if your C compiler knows about the fd_set typedef.
?S:.
?S:d_fd_macros:
?S: This variable contains the eventual value of the HAS_FD_MACROS symbol,
?S: which indicates if your C compiler knows about the macros which
?S: manipulate an fd_set.
?S:.
?S:d_fds_bits:
?S: This variable contains the eventual value of the HAS_FDS_BITS symbol,
?S: which indicates if your fd_set typedef contains the fds_bits member.
?S: If you have an fd_set typedef, but the dweebs who installed it did
?S: a half-fast job and neglected to provide the macros to manipulate
?S: an fd_set, HAS_FDS_BITS will let us know how to fix the gaffe.
?S:.
?C:HAS_FD_SET:
?C: This symbol, when defined, indicates presence of the fd_set typedef
?C: in <sys/types.h>
?C:.
?C:HAS_FD_MACROS:
?C: This symbol, when defined, indicates presence of the macros used
to
?C: manipulate an fd_set.
?C:.
?C:HAS_FDS_BITS:
?C: This symbol, when defined, indicates presence of the fds_bits member in
?C: fd_set. This knowledge is useful if fd_set is available but the macros

```

?C: aren't.
?C:.
?H:#$d_fd_set HAS_FD_SET /**/
?H:#$d_fd_macros HAS_FD_MACROS /**/
?H:#$d_fds_bits HAS_FDS_BITS /**/
?H:.
?F:!fd_set
: check for fd_set items
$cat <<EOM

```

Checking to see how well your C compiler handles fd_set and friends ...

EOM

?X: The FD_SET macros can be in strange places. On some SysV-based

?X: systems, they are in <sys/bsdtypes.h>, which is included (perhaps)

?X: by <sys/socket.h>. We won't force people to include

?X: <sys/bsdtypes.h> because it might introduce other

?X: incompatibilities.

```
$cat >fd_set.c <<EOCP
```

```
#$i_systime I_SYS_TIME
```

```
#$i_sysselect I_SYS_SELECT
```

```
#$d_socket HAS_SOCKET
```

```
#$i_syssock I_SYS_SOCKET
```

```
#include <sys/types.h>
```

```
#ifdef HAS_SOCKET
```

```
#ifdef I_SYS_SOCKET
```

```
#include <sys/socket.h> /* Might include <sys/bsdtypes.h> */
```

```
#endif
```

```
#endif
```

```
#ifdef I_SYS_TIME
```

```
#include
```

```
<sys/time.h>
```

```
#endif
```

```
#ifdef I_SYS_SELECT
```

```
#include <sys/select.h>
```

```
#endif
```

```
int main() {
```

```
fd_set fds;
```

```
#ifdef TRYBITS
```

```
if(fds.fds_bits);
```

```
#endif
```

```
#if defined(FD_SET) && defined(FD_CLR) && defined(FD_ISSET) && defined(FD_ZERO)
```

```
exit(0);
```

```
#else
```

```
exit(1);
```

```
#endif
```

```
}
```

EOCP

```
if $cc $ccflags -DTRYBITS -o fd_set fd_set.c >fd_set.out 2>&1 ; then
d_fds_bits="$define"
d_fd_set="$define"
echo "Well, your system knows about the normal fd_set typedef..." >&4
if ./fd_set; then
echo "and you have the normal fd_set macros (just as I'd expect)." >&4
d_fd_macros="$define"
else
$cat >&4 <<'EOM'
```

but not the normal fd_set macros! Gaaack! I'll have to cover for you.

EOM

```
d_fd_macros="$undef"
fi
else
$cat <<'EOM'
```

Hmm, your compiler has some difficulty with fd_set. Checking further...

EOM

```
if $cc $ccflags -o fd_set fd_set.c >fd_set.out 2>&1 ; then
d_fds_bits="$undef"
d_fd_set="$define"
echo "Well, your system has some sort of fd_set available..." >&4
if ./fd_set; then
echo "and you have the
normal fd_set macros." >&4
d_fd_macros="$define"
else
$cat <<'EOM'
```

but not the normal fd_set macros! Gross! More work for me...

EOM

```
d_fd_macros="$undef"
fi
else
echo "Well, you got zip. That's OK, I can roll my own fd_set stuff." >&4
d_fd_set="$undef"
d_fds_bits="$undef"
d_fd_macros="$undef"
fi
fi
$rm -f fd_set*
```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/d_fd_set.U
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 2000 Jarkko Hietaniemi
?RCS:
?RCS: You may distribute under the terms of either the GNU General Public
?RCS: License or the Artistic License, as specified in the README file.
?RCS:
?MAKE:d_class: Inlibc
?MAKE: -pick add \$@ %<
?S:d_class:
?S: This variable conditionally defines the HAS_CLASS symbol, which
?S: indicates to the C program that the class() routine is available.
?S:.
?C:HAS_CLASS:
?C: This symbol, if defined, indicates that the class routine is
?C: available to classify doubles. Available for example in AIX.
?C: The returned values are defined in <float.h> and are:
?C:
?C: FP_PLUS_NORM Positive normalized, nonzero
?C: FP_MINUS_NORM Negative normalized, nonzero
?C: FP_PLUS_DENORM Positive denormalized, nonzero
?C: FP_MINUS_DENORM Negative denormalized, nonzero
?C: FP_PLUS_ZERO +0.0
?C: FP_MINUS_ZERO -0.0
?C: FP_PLUS_INF +INF
?C: FP_MINUS_INF -INF
?C: FP_NANS Signaling
Not a Number (NaNS)
?C: FP_NANQ Quiet Not a Number (NaNQ)
?C:.
?H:#\$d_class HAS_CLASS /**/
?H:.
?LINT:set d_class
: see if class exists
set class d_class
eval \$inlibc

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_class.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: \$Log: libc.U,v \$
?RCS: Revision 3.0.1.10 1997/02/28 15:56:48 ram
?RCS: patch61: replaced .a with \$_a all over the place
?RCS: patch61: added support for HPUX-10 nm output
?RCS:
?RCS: Revision 3.0.1.9 1995/07/25 14:11:56 ram
?RCS: patch56: now knows about OS/2 platforms
?RCS:
?RCS: Revision 3.0.1.8 1995/05/12 12:20:47 ram
?RCS: patch54: made sure only most recent version of shared lib is picked
?RCS: patch54: final "nm -p" check now uses xscan and xrun like everybody
?RCS: patch54: can now grok
linux nm output with lead __IO (ADO)
?RCS: patch54: added support for linux ELF output, using 'W' for alias (ADO)
?RCS:
?RCS: Revision 3.0.1.7 1994/10/29 16:23:40 ram
?RCS: patch36: now looks for shared libraries before anything else (ADO)
?RCS: patch36: added new nm output format (ADO)
?RCS:
?RCS: Revision 3.0.1.6 1994/08/29 16:28:10 ram
?RCS: patch32: added I-type symbols for nm output parsing on Linux
?RCS:
?RCS: Revision 3.0.1.5 1994/06/20 07:03:24 ram
?RCS: patch30: checks are now presented by succession of if/elif
?RCS: patch30: uniformized checks for shared objects with new so symbol
?RCS:
?RCS: Revision 3.0.1.4 1994/05/06 15:06:33 ram
?RCS: patch23: added shared library knowledge (ADO and WED)
?RCS:
?RCS: Revision 3.0.1.3 1994/01/24 14:12:17 ram
?RCS: patch16: can now export nm_extract as an internal-use only variable
?RCS:
?RCS: Revision 3.0.1.2 1993/09/13 16:09:03 ram
?RCS: patch10: added special handling for Apollo systems (WAD)
?RCS:
?RCS: Revision 3.0.1.1
1993/08/27 14:40:03 ram
?RCS: patch7: added entry for /usr/shlib/libc.so (OSF/1 machines)
?RCS:
?RCS: Revision 3.0 1993/08/18 12:08:57 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:libc libnames +nm_extract: echo n c rm test grep Getfile Myread \
Oldconfig Loc sed libs incpath libpth ar runnm nm nm_opt nm_so_opt \
contains xlibpth so osname trnl tr sort uniq _o _a
?MAKE: -pick add \$@ %<

```

?S:libc:
?S: This variable contains the location of the C library.
?S:.
?S:libnames:
?S: The constructed list of library names. Normally empty, but hint files
?S: may set this for later perusal by Configure.
?S:.
?S:nm_extract:
?S: This variable holds the name of the extraction command used to process
?S: the output of nm and yield the list of defined symbols. It is used
?S: internally by Configure.
?S:.
?T:thislib try libnames xxx xscan xrun thisname com tans file
?F:!libnames !libc.tmp !tmp.imp
?LINT:change nm_opt runnm
?INIT:libnames=""
: Figure out where the libc is located
case
"$runnm" in
true)
?X: indentation is wrong on purpose--RAM
: get list of predefined functions in a handy place
echo " "
case "$libc" in
") libc=unknown
case "$libs" in
*-lc_s*) libc=`./loc libc_s$_a $libc $libpth`
esac
;;
esac
case "$libs" in
") ;;
*) for thislib in $libs; do
case "$thislib" in
-lc|-lc_s)
: Handle C library specially below.
;;
-l*)
thislib=`echo $thislib | $sed -e 's/^-l//`
if try=`./loc lib$thislib.$so.*' X $libpth`; $test -f "$try"; then
:
elif try=`./loc lib$thislib.$so X $libpth`; $test -f "$try"; then
:
elif try=`./loc lib$thislib$_a X $libpth`; $test -f "$try"; then
:
elif try=`./loc $thislib$_a X $libpth`; $test -f "$try"; then
:
elif try=`./loc lib$thislib X $libpth`; $test -f "$try"; then

```

```

:
elif try=`./loc $thislib X $libpth`; $test -f "$stry"; then
:
elif try=`./loc $lib$thislib$_a X $xlibpth`; $test -f "$stry"; then
:
else
  try=""
fi
libnames="$libnames $stry"
;;
*) libnames="$libnames $thislib"
;;
esac
done
;;
esac
?X:
?X: Some systems (e.g. DG/UX) use "environmental" links, which make the test
?X: -f fail. Ditto for symbolic links. So in order to reliably check the
?X: existence of a file, we use test -r. It will still fail with DG/UX links
?X: though, but at least it will detect symbolic links. At some strategic
?X: points, we make use of (test -h), using a sub-shell in case builtin test
?X: does not implement the -h check for symbolic links. This makes it
?X: possible to preset libc in a hint file for instance and have it show up
?X: as-is in the question.
?X:
xxx=normal
case "$libc" in
unknown)
?X:
?X: The sed below transforms .so.9 .so.12 into something like .so.0009 .so.0012,
?X: then sorts on it to allow keeping .so.12 instead of .so.9 as the latest
?X: up-to-date library. The initial filename (before sed munging, saved in hold
?X: space via 'h') is appended via 'G' before sorting, then the leading munged
?X: part is removed after sorting. Nice efficient work
?X: from Tye McQueen.
?X: The initial blurfl is here to prevent the trailing pipe from producing an
?X: empty string, causing Configure to output all its set variables!
?X:
set /lib/libc.$so
for xxx in $libpth; do
  $test -r $1 || set $xxx/libc.$so
  : The messy sed command sorts on library version numbers.
  $test -r $1 || \
  set `echo blurfl; echo $xxx/libc.$so.[0-9]* | \
  tr ' ' $trnl | egrep -v \.[A-Za-z]*$' | $sed -e '
  h
  s/[0-9][0-9]*/0000&/g

```

```

s/0*([0-9][0-9][0-9][0-9][0-9])\^1/g
G
s^n/'|\
$sort | $sed -e 's/^\.* //'^
eval set \$$#
done
$test -r $1 || set /usr/ccs/lib/libc.$so
$test -r $1 || set /lib/libsys_s$_a
;;
*)
?X: ensure the test below for the (shared) C library will fail
set blurfl
;;
esac
if $test -r "$1"; then
echo "Your (shared) C library seems to be in $1."
libc="$1"
elif $test -r /lib/libc && $test -r /lib/clib; then
?X:
?X: Apollo has its C library in /lib/clib AND /lib/libc
?X: not to mention its math library in /lib/syslib...
?X:
echo
"Your C library seems to be in both /lib/clib and /lib/libc."
xxx=apollo
libc='/lib/clib /lib/libc'
if $test -r /lib/syslib; then
echo "(Your math library is in /lib/syslib.)"
?X: Put syslib in libc -- not quite right, but won't hurt
libc="$libc /lib/syslib"
fi
elif $test -r "$libc" || (test -h "$libc") >/dev/null 2>&1; then
echo "Your C library seems to be in $libc, as you said before."
?X: For mips, and...
elif $test -r $incpath/usr/lib/libc$_a; then
libc=$incpath/usr/lib/libc$_a;
echo "Your C library seems to be in $libc. That's fine."
elif $test -r /lib/libc$_a; then
libc=/lib/libc$_a;
echo "Your C library seems to be in $libc. You're normal."
else
if tans=`./loc libc$_a blurfl/dyick $libpth`; $test -r "$stans"; then
:
elif tans=`./loc libc blurfl/dyick $libpth`; $test -r "$stans"; then
libnames="$libnames "`./loc clib blurfl/dyick $libpth`
elif tans=`./loc clib blurfl/dyick $libpth`; $test -r "$stans"; then
:
elif tans=`./loc Slibc$_a blurfl/dyick

```

```

$xlabelph`; $test -r "$stans"; then
:
elif tans=`./loc Mlibc$_a blurfl/dyick $xlabelph`; $test -r "$stans"; then
:
else
tans=`./loc Llibc$_a blurfl/dyick $xlabelph`
fi
if $test -r "$stans"; then
echo "Your C library seems to be in $stans, of all places."
libc=$stans
else
libc='blurfl'
fi
fi
if $test $xxx = apollo -o -r "$libc" || (test -h "$libc") >/dev/null 2>&1; then
dflt="$libc"
cat <<EOM

```

If the guess above is wrong (which it might be if you're using a strange compiler, or your machine supports multiple models), you can override it here.

```

EOM
else
dflt="
echo $libph | $tr ' ' $trnl | $sort | $uniq > libpath
cat >&4 <<EOM

```

I can't seem to find your C library. I've looked in the following places:

```

EOM
$sed 's/^/ /' libpath
cat <<EOM

```

None of these seems to contain your C library. I need to get its name...

```

EOM
fi
fn=f
rp='Where is your C library?'
./getfile
libc="$ans"

echo " "
echo $libc $libnames | $tr ' ' $trnl | $sort | $uniq > libnames
set X `cat libnames`
shift
xxx=files
case

```

```

$# in 1) xxx=file; esac
echo "Extracting names from the following $xxx for later perusal:" >&4
echo " "
$sed 's/^/ /' libnames >&4
echo " "
$echo $n "This may take a while...$c" >&4

```

?X:

?X: Linux may need the special Dynamic option to nm for shared libraries.

?X: In general, this is stored in the nm_so_opt variable.

?X: Unfortunately, that option may be fatal on non-shared libraries.

?X:

```

for file in $*; do
case $file in
*$so*) $nm $nm_so_opt $nm_opt $file 2>/dev/null;;
*) $nm $nm_opt $file 2>/dev/null;;
esac
done >libc.tmp

```

```

$echo $n ".$c"

```

?X:

?X: To accelerate processing, we look at the correct 'sed' command

?X: by using a small subset of libc.tmp, i.e. fprintf function.

?X: When we know which sed command to use, do the name extraction

?X:

```

$grep fprintf libc.tmp > libc.ptf

```

?X:

?X: In order to enhance readability and save some space, we define

?X: some variables that will be "eval"ed.

?X:

```

xscan='eval "<libc.ptf $com >libc.list"; $echo $n ".$c" >&4'

```

```

xrun='eval

```

```

"<libc.tmp $com >libc.list"; echo "done." >&4'

```

?X: BSD-like output, I and W types added for Linux

?X: Some versions of Linux include a leading __IO in the symbol name.

?X: HPUX10 reportedly has trailing spaces, though I'm surprised it has

?X: BSD-like output. (AD).

```

xxx='[ADTSIW]'

```

```

if com="$sed -n -e 's/__IO//' -e 's/^. *$xxx *[_.]*/p' -e 's/^. *$xxx */p'";\

```

```

eval $xscan;\

```

```

$contains '^fprintf$' libc.list >/dev/null 2>&1; then

```

```

eval $xrun

```

?X: SYSV-like output

```

elif com="$sed -n -e 's/^_*/' -e 's/^\([a-zA-Z_0-9$]*\).*xtern.*\1/p'";\

```

```

eval $xscan;\

```

```

$contains '^fprintf$' libc.list >/dev/null 2>&1; then

```

```

eval $xrun

```

```

elif com="$sed -n -e '/UNDEF/d' -e '/FUNC..GL/s/^. *|_*/p'";\

```



```

?X: AIX nm output
elif com="sed -n -e 's/^__.*//' -e 's/[ ]*D[ ]*[0-9]*.*//p';\
eval $xscan;\
$contains '^fprintf$' libc.list >/dev/null 2>&1; then
eval $xrun
else
$nm -p $* 2>/dev/null >libc.tmp
$grep fprintf libc.tmp > libc.ptf
if com="$sed -n -e 's/^[ADTSIW] *[_\.]*//p' -e 's/^[ADTSIW] //p';\
eval $xscan; $contains '^fprintf$' libc.list >/dev/null 2>&1
then
nm_opt='-p'
eval $xrun
else
echo " "
echo "$nm didn't seem to work right. Trying $ar instead..." >&4
com="
if $ar t $libc > libc.tmp && \
$contains '^fprintf$' libc.tmp >/dev/null 2>&1
then
for thisname in $libnames $libc; do
$ar t $thisname >>libc.tmp
done
$sed
-e "s/\\$_o\$/" < libc.tmp > libc.list
echo "Ok." >&4
elif test "X$osname" = "Xos2" && $ar tv $libc > libc.tmp; then
?X: Repeat libc to extract forwarders to DLL entries too
for thisname in $libnames $libc; do
$ar tv $thisname >>libc.tmp
?X: Revision 50 of EMX has bug in ar: it will not extract forwarders
?X: to DLL entries. Use emximp which will extract exactly them.
emximp -o tmp.imp $thisname \
2>/dev/null && \
$sed -e 's/^\([_a-zA-Z0-9]*\) .*$/1/p' \
< tmp.imp >>libc.tmp
$rm -f tmp.imp
done
$sed -e "s/\\$_o\$/" -e 's/^\ +//' < libc.tmp > libc.list
echo "Ok." >&4
else
echo "$ar didn't seem to work right." >&4
echo "Maybe this is a Cray...trying bld instead..." >&4
if
bld t $libc | \
$sed -e 's/.*\///' -e "s/\\$_o:.*\///" > libc.list &&
$test -s libc.list
then

```

```

for thisname in $libnames; do
  bld t $libnames | \
  $sed -e 's/.*\///' -e "s/\$_o:.*\$/'" >>libc.list
  $ar t $thisname >>libc.tmp
done
echo
"Ok." >&4
else
  echo "That didn't work either." >&4
  echo "No problem, I'll be compiling test programs then..." >&4
  runnm=false
fi
fi
fi
fi
nm_extract="$com"
if $test -f /lib/syscalls.exp; then
  echo " "
  echo "Also extracting names from /lib/syscalls.exp for good ole AIX..." >&4
  $sed -n 's/^\([^ ]*\)[ ]*syscall[0-9]*[ ]*$/\1/p' \
  /lib/syscalls.exp >>libc.list
fi
?X: remember, indentation is wrong on purpose--RAM
;;
esac
$rm -f libnames libpath

```

Found in path(s):

```

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/libc.U

```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: d_gethbynm.U,v \$

?RCS: Revision 3.0 1993/08/18 12:06:08 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?MAKE:d_gethbynm: Inlibc

?MAKE: -pick add \$@ %<

?S:d_gethbynm (d_gethstby):

?S: This variable conditionally defines the HAS_GETHOSTBYNAME symbol, which

?S: indicates to the C program that the gethostbyname() routine is available

?S: to lookup host names in some data base or other.

?S:.

?C:HAS_GETHOSTBYNAME (GETHOSTBYNAME):

?C: This symbol, if defined, indicates that the gethostbyname()
routine is

?C: available to lookup host names in some data base or other.

?C:.

?H:#\$d_gethbynm HAS_GETHOSTBYNAME /**/

?H:.

?LINT:set d_gethbynm

: see if gethostbyname exists

set gethostbyname d_gethbynm

eval \$inlibc

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/d_gethbynm.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 2000 Jarkko Hietaniemi

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?MAKE:d_fp_class_l: Inlibc

?MAKE:-pick add \$@ %<

?S:d_fp_class_l:

?S: This variable conditionally defines the HAS_FP_CLASS_L symbol, which

?S: indicates to the C program that the fp_class_l() routine is available.

?S:.

?C:HAS_FP_CLASS_L:

?C: This symbol, if defined, indicates that the fp_class_l routine is

?C: available to classify long doubles. Available for example in IRIX.

?C: The returned values are defined in <fp_class.h> and are:

?C:

?C: FP_SNAN Signaling NaN (Not-a-Number)

?C: FP_QNAN Quiet NaN (Not-a-Number)

?C: FP_POS_INF +infinity

?C: FP_NEG_INF -infinity

?C: FP_POS_NORM Positive normalized

?C: FP_NEG_NORM Negative normalized

?C: FP_POS_DENORM

```
Positive denormalized
?C: FP_NEG_DENORM Negative denormalized
?C: FP_POS_ZERO +0.0 (positive zero)
?C: FP_NEG_ZERO -0.0 (negative zero)
?C:.
?H:#$d_fp_class_1 HAS_FP_CLASS_L /**/
?H:.
?LINT:set d_fp_class_1
: see if fp_class_1 exists
set fp_class_1 d_fp_class_1
eval $inlibc
```

Found in path(s):

```
*/opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/perl/d_fp_class_1.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: d_msgrcv.U 1 2006-08-24 12:32:52Z rmanfredi $
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: $Log: d_msgrcv.U,v $
?RCS: Revision 3.0 1993/08/18 12:06:40 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:d_msgrcv: Inlibc
?MAKE: -pick add $@ %<
?S:d_msgrcv:
?S: This variable conditionally defines the HAS_MSGRCV symbol, which
?S: indicates to the C program that the msgrcv() routine is available.
?S:.
?C:HAS_MSGRCV:
?C: This symbol, if defined, indicates that the msgrcv() routine is
?C: available to extract a message from the message queue.
?C:.
?H:#$d_msgrcv
HAS_MSGRCV /**/
?H:.
?LINT:set d_msgrcv
: see if msgrcv exists
set msgrcv d_msgrcv
eval $inlibc
```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/d_msgrcv.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: i_unistd.U 1 2006-08-24 12:32:52Z rmanfredi $
```

```
?RCS:
```

```
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
```

```
?RCS:
```

```
?RCS: You may redistribute only under the terms of the Artistic Licence,
```

```
?RCS: as specified in the README file that comes with the distribution.
```

```
?RCS: You may reuse parts of this distribution only within the terms of
```

```
?RCS: that same Artistic Licence; a copy of which may be found at the root
```

```
?RCS: of the source tree for dist 4.0.
```

```
?RCS:
```

```
?RCS: $Log: i_unistd.U,v $
```

```
?RCS: Revision 3.0 1993/08/18 12:08:46 ram
```

```
?RCS: Baseline for dist 3.0 netwide release.
```

```
?RCS:
```

```
?MAKE:i_unistd: Inhdr
```

```
?MAKE: -pick add $@ %<
```

```
?S:i_unistd:
```

```
?S: This variable conditionally defines the I_UNISTD symbol, and indicates
```

```
?S: whether a C program should include <unistd.h>.
```

```
?S:.
```

```
?C:I_UNISTD:
```

```
?C: This symbol, if defined, indicates to the C program that it should
```

```
?C: include <unistd.h>.
```

```
?C:.
```

```
?H:#$i_unistd I_UNISTD /**/
```

```
?H:.
```

```
?LINT:set
```

```
i_unistd
```

```
: see if this is a unistd.h system
```

```
set unistd.h i_unistd
```

```
eval $inhdr
```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/i_unistd.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: d_mblen.U 1 2006-08-24 12:32:52Z rmanfredi $
```

```
?RCS:
```

```
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
```

```
?RCS:
```

```
?RCS: You may redistribute only under the terms of the Artistic Licence,
```

?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: Original Author: Andy Dougherty <doughera@lafcol.lafayette.edu>
?RCS:
?RCS: \$Log: d_mblen.U,v \$
?RCS: Revision 3.0.1.1 1994/08/29 16:09:40 ram
?RCS: patch32: created by ADO
?RCS:
?MAKE:d_mblen: Inlibc
?MAKE: -pick add \$@ %<
?S:d_mblen:
?S: This variable conditionally defines the HAS_MBLEN symbol, which
?S: indicates to the C program that the mblen() routine is available
?S: to find the number of bytes in a multibyte character.
?S:.
?C:HAS_MBLEN:
?C: This
symbol, if defined, indicates that the mblen routine is available
?C: to find the number of bytes in a multibyte character.
?C:.
?H:#\$d_mblen HAS_MBLEN /**/
?H:.
?LINT:set d_mblen
: see if mblen exists
set mblen d_mblen
eval \$inlibc

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/d_mblen.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_syslog.U 1 2006-08-24 12:32:52Z rmanfredi \$
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: \$Log: d_syslog.U,v \$
?RCS: Revision 3.0.1.1 1997/02/28 15:46:56 ram
?RCS: patch61: replaced .o with \$_o all over the place

?RCS:
?RCS: Revision 3.0 1993/08/18 12:07:43 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:d_syslog: test Csym Setvar Findhdr
?MAKE: -pick add \$@ %<
?S:d_syslog:
?S: This variable conditionally defines the HAS_SYSLOG symbol, which
?S: indicates to the C program that syslog() exists on this system.
?S:.

?C:HAS_SYSLOG
(LIBSYSLOG):
?C: This symbol, if defined, indicates that the program can rely on the
?C: system providing syslog(). Otherwise, the syslog code provided by
?C: the package should be used.

?C:.
?H:#\$d_syslog HAS_SYSLOG /**/

?H:.
?LINT:set d_syslog
: see if syslog is available
echo " "
if \$test `./findhdr syslog.h` && \
(set syslog val -f d_syslog; eval \$csym; \$val); then
echo "syslog() found." >&4
val="\$define"
else
echo "syslog() not found in your C library." >&4
val="\$undef"
fi
set d_syslog
eval \$setvar

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/d_syslog.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_readdir64_r.U,v 0RCS:
?RCS: Copyright (c) 2002,2003 Jarkko Hietaniemi
?RCS:
?RCS: You may distribute under the terms of either the GNU General Public
?RCS: License or the Artistic License, as specified in the README file.
?RCS:
?RCS: Generated by the reentr.pl from the Perl 5.8 distribution.
?RCS:
?MAKE:d_readdir64_r readdir64_r_proto: Inlibc Protochk Hasproto i_systypes \
usethreads i_dirent extern_C
?MAKE: -pick add \$@ %<

?S:d_readdir64_r:
 ?S: This variable conditionally defines the HAS_READDIR64_R symbol,
 ?S: which indicates to the C program that the readdir64_r()
 ?S: routine is available.
 ?S:.
 ?S:readdir64_r_proto:
 ?S: This variable encodes the prototype of readdir64_r.
 ?S: It is zero if d_readdir64_r is undef, and one of the
 ?S: REENTRANT_PROTO_T_ABC macros of reentr.h if d_readdir64_r
 ?S: is defined.
 ?S:.
 ?C:HAS_READDIR64_R:
 ?C: This symbol, if defined, indicates that the readdir64_r routine
 ?C: is
 available to readdir64 re-entrantly.
 ?C:.
 ?C:READDIR64_R_PROTO:
 ?C: This symbol encodes the prototype of readdir64_r.
 ?C: It is zero if d_readdir64_r is undef, and one of the
 ?C: REENTRANT_PROTO_T_ABC macros of reentr.h if d_readdir64_r
 ?C: is defined.
 ?C:.
 ?H:#\$d_readdir64_r HAS_READDIR64_R /**/
 ?H:#define READDIR64_R_PROTO \$readdir64_r_proto /**/
 ?H:.
 ?T:try hdrs d_readdir64_r_proto
 : see if readdir64_r exists
 set readdir64_r d_readdir64_r
 eval \$inlibc
 case "\$d_readdir64_r" in
 "\$define")
 hdrs="\$i_systypes sys/types.h define stdio.h \$i_dirent dirent.h"
 case "\$d_readdir64_r_proto:\$usetreads" in
 ":define") d_readdir64_r_proto=define
 set d_readdir64_r_proto readdir64_r \$hdrs
 eval \$hasproto ;;
 *) ;;
 esac
 case "\$d_readdir64_r_proto" in
 define)
 case "\$readdir64_r_proto" in
 "|0) try='int readdir64_r(DIR*, struct dirent64*, struct dirent64**);'
 ./protochk "\$extern_C \$try" \$hdrs && readdir64_r_proto=I_TSR ;;
 esac
 case "\$readdir64_r_proto" in
 "|0) try='int readdir64_r(DIR*,
 struct dirent64*);'
 ./protochk "\$extern_C \$try" \$hdrs && readdir64_r_proto=I_TS ;;

```

esac
case "$readdir64_r_proto" in
|(0) d_readdir64_r=undef
    readdir64_r_proto=0
echo "Disabling readdir64_r, cannot determine prototype." >&4 ;;
*) case "$readdir64_r_proto" in
REENTRANT_PROTO*) ;;
*) readdir64_r_proto="REENTRANT_PROTO_${readdir64_r_proto}" ;;
esac
echo "Prototype: $try" ;;
esac
;;
*) case "$usethreads" in
define) echo "readdir64_r has no prototype, not using it." >&4 ;;
esac
d_readdir64_r=undef
readdir64_r_proto=0
;;
esac
;;
*) readdir64_r_proto=0
;;
esac

```

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/threads/d_readdir64_r.U

No license file was found, but licenses were detected in source scan.

```

?RCS: $Id: d_rusage.U 1 2006-08-24 12:32:52Z rmanfredi $
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: $Log: d_rusage.U,v $
?RCS: Revision 3.0 1993/08/18 12:06:57 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?X: We may need to include <sys/resource.h> and <sys/time.h> FIXME
?X:INC: i_sysresrc i_systime
?MAKE:d_rusage: Inlibc
?MAKE: -pick add $@ %<
?S:d_rusage (d_getrusage):

```

?S: This variable conditionally defines the HAS_GETRUSAGE symbol, which
?S: indicates that the getrusage() routine exists. The getrusage() routine
?S: supports sub-second accuracy
for process cpu accounting. You may need
?S: to include <sys/resource.h> and <sys/time.h>.

?S:.

?C:HAS_GETRUSAGE (RUSAGE_GETRUSAGE):

?C: This symbol, if defined, indicates that the getrusage() routine is

?C: available to get process statistics with a sub-second accuracy.

?C: Inclusion of <sys/resource.h> and <sys/time.h> may be necessary.

?C:.

?H:#\$d_rusage HAS_GETRUSAGE /**/

?H:.

?LINT:set d_rusage

: see if getrusage exists

set getrusage d_rusage

eval \$inlibc

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/d_rusage.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_setgrps.U 1 2006-08-24 12:32:52Z rmanfredi \$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic Licence,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic Licence; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: d_setgrps.U,v \$

?RCS: Revision 3.0 1993/08/18 12:06:08 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?MAKE:d_setgrps: Inlibc

?MAKE: -pick add \$@ %<

?S:d_setgrps:

?S: This variable conditionally defines the HAS_SETGROUPS symbol, which

?S: indicates to the C program that the setgroups() routine is available

?S: to set the list of process groups.

?S:.

?C:HAS_SETGROUPS:

?C: This symbol, if defined, indicates that the setgroups() routine is

?C: available

to set the list of process groups. If unavailable, multiple

?C: groups are probably not supported.

?C:.

?H:#\$d_setgrps HAS_SETGROUPS /**/

?H:.

?LINT:set d_setgrps

: see if setgroups exists

set setgroups d_setgrps

eval \$inlibc

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/d_setgrps.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_setlnbuf.U 1 2006-08-24 12:32:52Z rmanfredi \$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic Licence,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic Licence; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: Original Author: Andy Dougherty <doughera@lafcol.lafayette.edu>

?RCS:

?RCS: \$Log: d_setlnbuf.U,v \$

?RCS: Revision 3.0.1.1 1994/08/29 16:11:57 ram

?RCS: patch32: created by ADO

?RCS:

?MAKE:d_setlinebuf: Inlibc

?MAKE: -pick add \$@ %<

?S:d_setlinebuf:

?S: This variable conditionally defines the HAS_SETLINEBUF symbol, which

?S: indicates to the C program that the setlinebuf() routine is available

?S: to change stderr or stdout from block-buffered or unbuffered

to a

?S: line-buffered mode.

?S:.

?C:HAS_SETLINEBUF :

?C: This symbol, if defined, indicates that the setlinebuf routine is

?C: available to change stderr or stdout from block-buffered or unbuffered

?C: to a line-buffered mode.

?C:.

?H:#\$d_setlinebuf HAS_SETLINEBUF /**/

?H:.

?LINT:set d_setlinebuf

```
: see if setlinebuf exists
set setlinebuf d_setlinebuf
eval $inlibc
```

Found in path(s):

```
*/opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/d_setlnbuf.U
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1999 Jarkko Hietaniemi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 3.0.

?RCS:

?MAKE:sitehtml1 sitehtml1exp installsitehtml1: Getfile Setprefixvar \
prefix siteprefix html1dir sed

?MAKE: -pick add \$@ %<

?Y:TOP

?D:sitehtml1="

?S:sitehtml1:

?S: This variable contains the name of the directory in which site-specific

?S: html source pages are to be put. It is the responsibility of the

?S: Makefile.SH to get the value of this into the proper command.

?S: You must be prepared to do the ~name expansion yourself.

?S: The standard distribution will put nothing in this directory.

?S: After perl has been installed,
users may install their own local

?S: html pages in this directory with

?S: MakeMaker Makefile.PL

?S: or equivalent. See INSTALL for details.

?S:.

?D:sitehtml1exp="

?S:sitehtml1exp:

?S: This variable is the same as the sitehtml1 variable, but is filename

?S: expanded at configuration time, for convenient use in makefiles.

?S:.

?D:installsitehtml1="

?S:installsitehtml1:

?S: This variable is really the same as sitehtml1exp, unless you are using

?S: AFS in which case it points to the read/write location whereas

?S: html1direxp only points to the read-only access location. For extra

?S: portability, you should only use this variable within your makefiles.

?S:.

```

?LINT:change prefixvar
?LINT:set installsitehtml
?LINT:set sitehtml
?LINT:set sitehtml1exp
: determine where add-on html pages go
: There is no standard location, so try to copy the previously-selected
: directory structure for the core html pages.
case "$sitehtml1" in
") dflt=`echo "$html1dir" | $sed "s#^$prefix#$siteprefix#"`
;;
*) dflt=$sitehtml1 ;;
esac
case "$dflt" in
"|' ') dflt=none ;;
esac
fn=dn+~
rp='Pathname where the site-specific html pages should be installed?'
./getfile
prefixvar=sitehtml1
./setprefixvar

```

Found in path(s):

```

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/installdirs/sitehtml1.U

```

No license file was found, but licenses were detected in source scan.

```

?RCS: $Id: vendorhtml1dir.U,v 1.1 1999/07/08 18:32:57 doughera Exp doughera $

```

```

?RCS:

```

```

?RCS: Copyright (c) 1999, Andy Dougherty

```

```

?RCS:

```

```

?RCS: You may redistribute only under the terms of the Artistic License,

```

```

?RCS: as specified in the README file that comes with the distribution.

```

```

?RCS: You may reuse parts of this distribution only within the terms of

```

```

?RCS: that same Artistic License; a copy of which may be found at the root

```

```

?RCS: of the source tree for dist 3.0.

```

```

?RCS:

```

```

?RCS: $Log: vendorhtml1dir.U,v $

```

```

?RCS: Revision 1.1 1999/07/08 18:32:57 doughera

```

```

?RCS: Initial revision

```

```

?RCS:

```

```

?MAKE:vendorhtml1dir vendorhtml1direxp installvendorhtml1dir: html1dir Getfile \

```

```

Setprefixvar Oldconfig Prefixit test vendorprefix prefix sed

```

```

?MAKE: -pick add $@ %<

```

```

?Y:TOP

```

```

?S:vendorhtml1dir:

```

```

?S: This variable contains the name of the directory for html

```

```

?S: pages. It may have a ~ on the front.

```

```

?S: The standard distribution will put nothing in this

```

directory.

?S: Vendors who distribute perl may wish to place their own

?S: html pages in this directory with

?S: MakeMaker Makefile.PL INSTALLDIRS=vendor

?S: or equivalent. See INSTALL for details.

?S:.

?S:vendorhtml1direxp:

?S: This variable is the ~name expanded version of vendorhtml1dir, so that you

?S: may use it directly in Makefiles or shell scripts.

?S:.

?D:installvendorhtml1dir="

?S:installvendorhtml1dir:

?S: This variable is really the same as vendorhtml1direxp but may differ on

?S: those systems using AFS. For extra portability, only this variable

?S: should be used in makefiles.

?S:.

?LINT:change prefixvar

?LINT:set installvendorhtml1dir

: Set the vendorhtml1dir variables

case "\$vendorprefix" in

) vendorhtml1dir="

vendorhtml1direxp="

;;

*) : determine where vendor-supplied html pages go.

: There is no standard location, so try to copy the previously-selected

: directory structure for the core html pages.

: XXX Better default suggestions would be welcome.

case "\$vendorhtml1dir"

in

) dflt=`echo "\$html1dir" | \$sed "s#^\$prefix#\$vendorprefix#"` ;;

*) dflt=\$vendorhtml1dir ;;

esac

case "\$dflt" in

"|") dflt=none ;;

esac

fn=dn+~

rp='Pathname for the vendor-supplied html pages?'

./getfile

vendorhtml1dir="\$ans"

vendorhtml1direxp="\$ansexp"

;;

esac

: Use ' ' for none so value is preserved next time through Configure

\$test X"\$vendorhtml1dir" = "X" && vendorhtml1dir=' '

prefixvar=vendorhtml1dir

./installprefix

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/installdirs/vendorhtml1.dir.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: Original Author: Andy Dougherty <doughera@lafcol.lafayette.edu>

?RCS:

?RCS: \$Log: d_gconvert.U,v \$

?RCS: Revision 3.0.1.3 1997/02/28 15:33:38 ram

?RCS: patch61: integrated new unit from perl5

?RCS:

?RCS: Revision 3.0.1.2 1995/07/25 13:55:59 ram

?RCS: patch56: improved comments about the Gconvert macro (ADO)

?RCS: patch56: force compile-link test since it may exist but be unusable (ADO)

?RCS:

?RCS: Revision 3.0.1.1 1994/10/29 16:12:51 ram

?RCS: patch36: created by ADO

?RCS:

?MAKE:d_Gconvert:

cat cc cflags ldflags libs rm_try _o

?MAKE: -pick add \$@ %<

?S:d_Gconvert:

?S: This variable holds what Gconvert is defined as to convert

?S: floating point numbers into strings. It could be 'gconvert'

?S: or a more complex macro emulating gconvert with gcvt() or sprintf.

?S:.

?C:Gconvert:

?C: This preprocessor macro is defined to convert a floating point

?C: number to a string without a trailing decimal point. This

?C: emulates the behavior of sprintf("%g"), but is sometimes much more

?C: efficient. If gconvert() is not available, but gcvt() drops the

?C: trailing decimal point, then gcvt() is used. If all else fails,

?C: a macro using sprintf("%g") is used. Arguments for the Gconvert

?C: macro are: value, number of digits, whether trailing zeros should

?C: be retained, and the output buffer.

?C: Possible values are:

?C: d_Gconvert='gconvert((x),(n),(t),(b))'

?C: d_Gconvert='gcvt((x),(n),(b))'

?C: d_Gconvert='sprintf((b),"%.*g",(n),(x))'

```

?C: The last two assume trailing zeros should
not be kept.
?C:.
?H:#define Gconvert(x,n,t,b) $d_Gconvert
?H:.
?T: xxx_list xxx_convert
?F:!try
?X:
: Check how to convert floats to strings.
echo " "
echo "Checking for an efficient way to convert floats to strings."
?X: We want to be sure to drop trailing decimal points (perl5
?X: needs this).
$cat >try.c <<'EOP'
#ifdef TRY_gconvert
#define Gconvert(x,n,t,b) gconvert((x),(n),(t),(b))
char *myname = "gconvert";
#endif
#ifdef TRY_gcvt
#define Gconvert(x,n,t,b) gcvt((x),(n),(b))
char *myname = "gcvt";
#endif
#ifdef TRY_sprintf
#define Gconvert(x,n,t,b) sprintf((b),"%.*g", (n),(x))
char *myname = "sprintf";
#endif

#include <stdio.h>

int
checkit(expect, got)
char *expect;
char *got;
{
    if (strcmp(expect, got) {
        printf("%s oddity: Expected %s, got %s\n",
            myname, expect, got);
        exit(1);
    }
}

int
main()
{
    char buf[64];
    buf[63] = '\0';

    /* This must be 1st test on (which?) platform */

```

```
/* Alan Burlison <AlanBurlsin@unn.unisys.com> */
```

```
Gconvert(0.1, 8, 0, buf);  
checkit("0.1",  
buf);
```

```
Gconvert(1.0, 8, 0, buf);  
checkit("1", buf);
```

```
Gconvert(0.0, 8, 0, buf);  
checkit("0", buf);
```

```
Gconvert(-1.0, 8, 0, buf);  
checkit("-1", buf);
```

```
/* Some Linux gcvt's give 1.e+5 here. */
```

```
Gconvert(100000.0, 8, 0, buf);  
checkit("100000", buf);
```

```
/* Some Linux gcvt's give -1.e+5 here. */
```

```
Gconvert(-100000.0, 8, 0, buf);  
checkit("-100000", buf);
```

```
exit(0);
```

```
}
```

EOP

?X: List of order in which to search for functions.

?X: Usual order of efficiency is gconvert gcvt printf

?X: Respect a previous or hinted value.

```
case "$d_Gconvert" in  
gconvert*) xxx_list='gconvert gcvt printf' ;;  
gcvt*) xxx_list='gcvt gconvert printf' ;;  
printf*) xxx_list='printf gconvert gcvt' ;;  
*) xxx_list='gconvert gcvt printf' ;;  
esac
```

```
for xxx_convert in $xxx_list; do  
echo "Trying $xxx_convert"  
$rm_try  
if $cc $ccflags -DTRY_$xxx_convert $ldflags -o try \  
try.c $libs > /dev/null 2>&1 ; then  
echo "$xxx_convert" found. >&4  
if ./try; then  
echo "I'll use $xxx_convert to convert floats  
into a string." >&4  
break;  
else  
echo "...But $xxx_convert didn't work as I expected."  
fi  
fi
```

```

else
  echo "$xxx_convert NOT found." >&4
fi
done

case "$xxx_convert" in
gconvert) d_Gconvert='gconvert((x),(n),(t),(b))' ;;
gcvt) d_Gconvert='gcvt((x),(n),(b))' ;;
*) d_Gconvert='sprintf((b),"%.*g",(n),(x))' ;;
esac

```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/d_gconvert.U
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_setpent.U,v 3.0 1993/08/18 12:06:09 ram Exp \$

?RCS:

?RCS: Copyright (c) 1991-1993, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 3.0.

?RCS:

?RCS: \$Log: d_setpent.U,v \$

?RCS: Revision 3.0 1993/08/18 12:06:09 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?MAKE:d_setpent: Inlibc

?MAKE: -pick add \$@ %<

?S:d_setpent:

?S: This variable conditionally defines HAS_SETPROTOENT if setprotoent() is

?S: available.

?S:.

?C:HAS_SETPROTOENT:

?C: This symbol, if defined, indicates that the setprotoent() routine is

?C: available.

?C:.

?H:#\$d_setpent HAS_SETPROTOENT /**/

?H:.

?LINT:set d_setpent

: see if setprotoent

exists

set setprotoent d_setpent

eval \$inlibc

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/modified/d_setpent.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1999, Jarkko Hietaniemi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 3.0.

?RCS:

?MAKE:d_sigwaitinfo: Inlibc

?MAKE: -pick add \$@ %<

?S:d_sigwaitinfo:

?S: This variable conditionally defines HAS_SIGWAITINFO

?S: if sigwaitinfo() is available to wait a signal and additional

?S: information.

?S:.

?C:HAS_SIGWAITINFO:

?C: This symbol, if defined, indicates that the sigwaitinfo

?C: system call is available to wait a signal and additional information.

?C:.

?H:#\$d_sigwaitinfo HAS_SIGWAITINFO /**/

?H:.

?LINT:set d_sigwaitinfo

: see if sigwaitinfo exists

set sigwaitinfo d_sigwaitinfo

eval \$inlibc

Found in path(s):

*

/opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_sigwaitinfo.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_sigblock.U 1 2006-08-24 12:32:52Z rmanfredi \$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic Licence,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic Licence; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

```

?RCS:
?RCS: $Log: d_sigblock.U,v $
?RCS: Revision 3.0 1993/08/18 12:07:21 ram
?RCS: Baseline for dist 3.0 worldwide release.
?RCS:
?MAKE:d_sigblock: Inlibc
?MAKE: -pick add $@ %<
?S:d_sigblock:
?S: This variable conditionally defines HAS_SIGBLOCK if sigblock() is
?S: available to block signal reception.
?S:.
?C:HAS_SIGBLOCK:
?C: This symbol, if defined, indicates that the sigblock routine is
?C: available to block signal reception.
?C:.
?H:#$d_sigblock HAS_SIGBLOCK /**/
?H:.
?LINT:set
d_sigblock
: see if sigblock exists
set sigblock d_sigblock
eval $inlibc

```

Found in path(s):

```

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/d_sigblock.U

```

No license file was found, but licenses were detected in source scan.

```

?RCS: $Id: d_umask.U 1 2006-08-24 12:32:52Z rmanfredi $
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: Original Author: Andy Dougherty <doughera@lafcol.lafayette.edu>
?RCS:
?RCS: $Log: d_umask.U,v $
?RCS: Revision 3.0.1.1 1994/08/29 16:14:50 ram
?RCS: patch32: created by ADO
?RCS:
?MAKE:d_umask: Inlibc
?MAKE: -pick add $@ %<
?S:d_umask:
?S: This variable conditionally defines the HAS_UMASK symbol, which

```

?S: indicates to the C program that the umask() routine is available.

?S: to set and get the value of the file creation mask.

?S:.

?C:HAS_UMASK :

?C: This

symbol, if defined, indicates that the umask routine is

?C: available to set and get the value of the file creation mask.

?C:.

?H:#\$d_umask HAS_UMASK /**/

?H:.

?LINT:set d_umask

: see if umask exists

set umask d_umask

eval \$inlibc

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/d_umask.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: Instruct.U,v 3.0.1.3 1997/02/28 15:02:55 ram Exp \$

?RCS:

?RCS: Copyright (c) 1991-1993, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 3.0.

?RCS:

?RCS: \$Log: Instruct.U,v \$

?RCS: Revision 3.0.1.3 1997/02/28 15:02:55 ram

?RCS: patch61: logname / whoami sequence rewritten to use case

?RCS:

?RCS: Revision 3.0.1.2 1995/02/15 14:11:34 ram

?RCS: patch51: author name now appears at the end of the paragraph (WED)

?RCS:

?RCS: Revision 3.0.1.1 1995/01/11 15:12:05 ram

?RCS: patch45: now documents the & escape to turn -d on at the read prompt

?RCS:

?RCS: Revision 3.0 1993/08/18 12:05:04 ram

?RCS: Baseline for

dist 3.0 netwide release.

?RCS:

?X:

?X: This unit spew out the directions that we want everyone to read. I try to

?X: keep the first "pagefull" much less than a page since they don't know it

?X: isn't going to go shooting off the top of the screen, and we don't want

```

?X: to panic them yet.
?X:
?MAKE:Instruct: Myread Configdir Devel contains
?MAKE: -pick wipe $@ %<
?T:user needman firsttime
: general instructions
needman=true
firsttime=true
user=`(logname) 2>/dev/null`
case "$user" in
") user=`whoami 2>&1`;;
esac
if $contains "^$user$" ../.config/instruct >/dev/null 2>&1; then
firsttime=false
echo " "
rp='Would you like to see the instructions?'
dflt=n
. ./myread
case "$ans" in
[yY]*) ;;
*) needman=false;;
esac
fi
if $needman; then
cat <<EOH

```

This installation shell script will examine your system and ask you questions to determine how the <PACKAGENAME> package should be installed. If you get stuck on a question, you may use a ! shell escape to start a subshell or execute a command. Many of the questions will have default answers in square brackets; typing carriage return will give you the default.

On some of the questions which ask for file or directory names you are allowed to use the ~name construct to specify the login directory belonging to "name", even if you don't have a shell which knows about that. Questions where this is allowed will be marked "(~name ok)".

```

EOH
rp="
dflt='Type carriage return to continue'
. ./myread
cat <<'EOH'

```

The prompter used in this script allows you to use shell variables and backticks in your answers. You may use \$1, \$2, etc... to refer to the words in the default answer, as if the default line was a set of arguments given to a script shell. This means you may also use \$* to repeat the whole default line,

so you do not have to re-type everything to add something to the default.

Every time there is a substitution, you will have to confirm. If there is an error (e.g. an unmatched backtick), the default answer will remain unchanged and you will be prompted again.

If you are in a hurry, you may run 'Configure -d'. This will bypass nearly all the questions and use the computed defaults (or the previous answers if there was already a config.sh file). Type 'Configure -h' for a list of options. You may also start interactively and then answer '& -d' at any prompt to turn on the non-interactive behaviour for the remainder of the execution.

EOH

```
. ./myread  
cat <<EOH
```

Much effort has been expended to ensure that this shell script will run on any Unix system. If despite that it blows up on yours, your best bet is to edit Configure and run it again. If you can't run Configure for some reason, you'll have to generate a config.sh file by hand. Whatever problems you have, let me (<MAINTLOC>) know how I blew it.

This installation script affects things in two ways:

- 1) it may do direct variable substitutions on some of the files included in this kit.
- 2) it builds a config.h file for inclusion in C programs. You may edit any of these files as the need arises after running this script.

If you make a mistake on a question, there is no easy way to back up to it currently. The easiest thing to do is to edit config.sh and rerun all the SH files. Configure will offer to let you do this before it runs the SH files.

EOH

```
?X: In case they played with the prompter...  
dflt='Type carriage return to continue'  
. ./myread  
case "$firsttime" in  
true) echo $user >>../.config/instruct;;  
esac  
fi
```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/modified/Instruct.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: d_getservbyport_r.U,v 0RCS:
?RCS: Copyright (c) 2002,2003 Jarkko Hietaniemi
?RCS:
?RCS: You may distribute under the terms of either the GNU General Public
?RCS: License or the Artistic License, as specified in the README file.
?RCS:
?RCS: Generated by the reentr.pl from the Perl 5.8 distribution.
?RCS:
?MAKE:d_getservbyport_r getservbyport_r_proto: Inlibc Protochk Hasproto \
i_systypes usethreads i_netdb extern_C
?MAKE: -pick add $@ %<
?S:d_getservbyport_r:
?S: This variable conditionally defines the HAS_GETSERVBYPORTR symbol,
?S: which indicates to the C program that the getservbyport_r()
?S: routine is available.
?S:.
?S:getservbyport_r_proto:
?S: This variable encodes the prototype of getservbyport_r.
?S: It is zero if d_getservbyport_r is undef, and one of the
?S: REENTRANT_PROTO_T_ABC macros of reentr.h if d_getservbyport_r
?S: is defined.
?S:.
?C:HAS_GETSERVBYPORTR:
?C: This symbol, if defined, indicates
?C: that the getservbyport_r routine
?C: is available to getservbyport re-entrantly.
?C:.
?C:GETSERVBYPORTR_PROTO:
?C: This symbol encodes the prototype of getservbyport_r.
?C: It is zero if d_getservbyport_r is undef, and one of the
?C: REENTRANT_PROTO_T_ABC macros of reentr.h if d_getservbyport_r
?C: is defined.
?C:.
?H:#$d_getservbyport_r HAS_GETSERVBYPORTR /**/
?H:#define GETSERVBYPORTR_PROTO $getservbyport_r_proto /**/
?H:.
?T:try hdrs d_getservbyport_r_proto
: see if getservbyport_r exists
set getservbyport_r d_getservbyport_r
eval $inlibc
case "$d_getservbyport_r" in
"$define")
hdrs="$i_systypes sys/types.h define stdio.h $i_netdb netdb.h"
case "$d_getservbyport_r_proto:$usethreads" in
":define") d_getservbyport_r_proto=define
set d_getservbyport_r_proto getservbyport_r $hdrs
```

```

eval $hasproto ;;
*) ;;
esac
case "$d_getservbyport_r_proto" in
define)
case "$getservbyport_r_proto" in
"|0) try='int getservbyport_r(int, const char*, struct servent*, char*, size_t,
struct servent**);'
./prochck "$extern_C $try" $hdrs && getservbyport_r_proto=I_ICSBWR ;;
esac
case "$getservbyport_r_proto" in
"|0) try='struct servent* getservbyport_r(int, const char*, struct servent*, char*, int);'
./prochck "$extern_C $try" $hdrs && getservbyport_r_proto=S_ICSBFI ;;
esac
case "$getservbyport_r_proto" in
"|0) try='int getservbyport_r(int, const char*, struct servent*, struct servent_data*);'
./prochck "$extern_C $try" $hdrs && getservbyport_r_proto=I_ICSD ;;
esac
case "$getservbyport_r_proto" in
"|0) d_getservbyport_r=undef
    getservbyport_r_proto=0
    echo "Disabling getservbyport_r, cannot determine prototype." >&4 ;;
* ) case "$getservbyport_r_proto" in
REENTRANT_PROTO*) ;;
*) getservbyport_r_proto="REENTRANT_PROTO_$getservbyport_r_proto" ;;
esac
echo "Prototype: $try" ;;
esac
;;
*) case "$usethreads" in
define) echo "getservbyport_r has no prototype, not using it." >&4 ;;
esac
d_getservbyport_r=undef
getservbyport_r_proto=0
;;
esac
;;
*) getservbyport_r_proto=0
;;
esac

```

Found

in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/threads/d_getservbyport_r.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: \$Log: i_varhdr.U,v \$
?RCS: Revision 3.0.1.3 1997/02/28 15:54:42 ram
?RCS: patch61: varargs script now starts with leading "startsh"
?RCS:
?RCS: Revision 3.0.1.2 1994/10/29 16:21:02 ram
?RCS: patch36: added ?F: line for metalint file checking
?RCS:
?RCS: Revision 3.0.1.1 1994/05/13 15:26:05 ram
?RCS: patch27: this unit now supersedes old i_stdarg.U and i_varargs.U
?RCS: patch27: modified to avoid spurious Whoa warnings (ADO)
?RCS:
?RCS: Revision 3.0 1993/08/18 12:08:49 ram
?RCS: Baseline for
dist 3.0 netwide release.
?RCS:
?MAKE:i_stdarg i_varargs i_varhdr: cat +cc +ccflags rm test Setvar \
Findhdr Warn startsh _o
?MAKE: -pick add \$@ %<
?S:i_stdarg:
?S: This variable conditionally defines the I_STDARG symbol, which
?S: indicates to the C program that <stdarg.h> exists and should
?S: be included.
?S:.
?S:i_varargs:
?S: This variable conditionally defines I_VARARGS, which indicates
?S: to the C program that it should include <varargs.h>.
?S:.
?S:i_varhdr:
?S: Contains the name of the header to be included to get va_dcl definition.
?S: Typically one of varargs.h or stdarg.h.
?S:.
?C:I_STDARG:
?C: This symbol, if defined, indicates that <stdarg.h> exists and should
?C: be included.
?C:.
?C:I_VARARGS:
?C: This symbol, if defined, indicates to the C program that it should
?C: include <varargs.h>.
?C:.

```

?H:#$i_stdarg I_STDARG /**/
?H:#$i_varargs I_VARARGS /**/
?H:
?W:%<:va_dcl
?F:!varargs
?T:valstd
?LINT:set i_stdarg i_varargs
?X:
?X: Don't use setvar because the varargs test
    below might override these.
?X: Actually, the messages here are just informative. We don't wish to set
?X: i_varargs or i_stdarg to their final value before knowing which of the
?X: two we'll include.
?X:
: see if stdarg is available
echo " "
if $test `./findhdr stdarg.h`; then
    echo "<stdarg.h> found." >&4
    valstd="$define"
else
    echo "<stdarg.h> NOT found." >&4
    valstd="$undef"
fi

: see if varargs is available
echo " "
if $test `./findhdr varargs.h`; then
    echo "<varargs.h> found." >&4
else
    echo "<varargs.h> NOT found, but that's ok (I hope)." >&4
fi

?X:
?X: if you have stdarg.h, you need to support prototypes to actually use it;
?X: but if stdarg.h exists and the compiler doesn't support prototypes (for some
?X: bizarre reason), we'll fall back to varargs.h anyway so it's not so bad.
?X:
: set up the varargs testing programs
$cat > varargs.c <<EOP
#ifdef I_STDARG
#include <stdarg.h>
#endif
#ifdef I_VARARGS
#include <varargs.h>
#endif

#ifdef I_STDARG
int f(char *p, ...)

```

```

#else
int
f(va_alist)
va_dcl
#endif
{
va_list ap;
#ifndef I_STDARG
char *p;
#endif
#ifdef I_STDARG
va_start(ap,p);
#else
va_start(ap);
p = va_arg(ap, char *);
#endif
va_end(ap);
}
EOP
$cat > varargs <<EOP
$startsh
if $cc -c $ccflags -D\${1} varargs.c >/dev/null 2>&1; then
echo "true"
else
echo "false"
fi
$rm -f varargs$_o
EOP
chmod +x varargs

```

: now check which varargs header should be included

```

echo " "
i_varhdr="
case "$valstd" in
"$define")
if `./varargs I_STDARG`; then
val='stdarg.h'
elif `./varargs I_VARARGS`; then
val='varargs.h'
fi
;;
*)
if `./varargs I_VARARGS`; then
val='varargs.h'
fi
;;
esac
case "$val" in

```

```

")
./warn "I could not find the definition for va_dcl... You have problems..."
val="$undef"; set i_stdarg; eval $setvar
val="$undef"; set i_varargs; eval $setvar
;;
*)
set i_varhdr
eval $setvar
case "$i_varhdr" in
stdarg.h)
val="$define"; set i_stdarg; eval $setvar
val="$undef"; set i_varargs; eval $setvar
;;
varargs.h)
val="$undef"; set i_stdarg;
eval $setvar
val="$define"; set i_varargs; eval $setvar
;;
esac
echo "We'll include <$i_varhdr> to get va_dcl definition." >&4;;
esac
$rm -f varargs*

```

Found in path(s):

```

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/i_varhdr.U

```

No license file was found, but licenses were detected in source scan.

```

?RCS: $Id: d_gethent.U 1 2006-08-24 12:32:52Z rmanfredi $
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: $Log: d_gethent.U,v $
?RCS: Revision 3.0 1993/08/18 12:06:09 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:d_gethent: Inlibc
?MAKE: -pick add $@ %<
?S:d_gethent:
?S: This variable conditionally defines HAS_GETHOSTENT if gethostent() is
?S: available to look up host names in some data base or another.
?S:..

```

?C:HAS_GETHOSTENT:

?C: This symbol, if defined, indicates that the gethostent() routine is

?C: available to look up host names in some
data base or another.

?C:.

?H:#\$d_gethent HAS_GETHOSTENT /**/

?H:.

?LINT:set d_gethent

: see if gethostent exists

set gethostent d_gethent

eval \$inlibc

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/modified/d_gethent.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 2000 Jarkko Hietaniemi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 3.0.

?RCS:

?MAKE:d_getespwnam: Inlibc

?MAKE: -pick add \$@ %<

?S:d_getespwnam:

?S: This variable conditionally defines HAS_GETESPWNAM if getespwnam() is

?S: available to retrieve enhanced (shadow) password entries by name.

?S:.

?C:HAS_GETESPWNAM:

?C: This symbol, if defined, indicates that the getespwnam system call is

?C: available to retrieve enhanced (shadow) password entries by name.

?C:.

?H:#\$d_getespwnam HAS_GETESPWNAM /**/

?H:.

?LINT:set d_getespwnam

: see if getespwnam exists

set getespwnam d_getespwnam

eval \$inlibc

Found in

path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_getespwnam.U

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id$
?RCS:
?RCS: Copyright (c) 1999 Jarkko Hietaniemi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 3.0.
?RCS:
?MAKE:siteman3 siteman3exp installsiteman3: test Getfile Setprefixvar \
prefix siteprefix man3dir sed
?MAKE: -pick add $@ %<
?Y:TOP
?D:siteman3="
?S:siteman3:
?S: This variable contains the name of the directory in which site-specific
?S: library man source pages are to be put. It is the responsibility of the
?S: Makefile.SH to get the value of this into the proper command.
?S: You must be prepared to do the ~name expansion yourself.
?S: The standard distribution will put nothing in this directory.
?S: After perl has been
installed, users may install their own local
?S: man3 pages in this directory with
?S: MakeMaker Makefile.PL
?S: or equivalent. See INSTALL for details.
?S:.
?D:siteman3exp="
?S:siteman3exp:
?S: This variable is the same as the siteman3 variable, but is filename
?S: expanded at configuration time, for convenient use in makefiles.
?S:.
?D:installsiteman3="
?S:installsiteman3:
?S: This variable is really the same as siteman3exp, unless you are using
?S: AFS in which case it points to the read/write location whereas
?S: man3direxp only points to the read-only access location. For extra
?S: portability, you should only use this variable within your makefiles.
?S:.
?LINT:change prefixvar
?LINT:set installsiteman3
?LINT:set siteman3exp
: determine where add-on library man pages go
case "$siteman3" in
") dflt=`echo "$man3dir" | $sed "s#^$prefix#$siteprefix#"` ;;
*) dflt=$siteman3 ;;
```

```

esac
case "$dflt" in
'|' ) dflt=none ;;
esac
fn=dn+~
rp='Pathname where the site-specific library manual
pages should be installed?'
./getfile
prefixvar=siteman3
./setprefixvar
: Use ' ' for none so value is preserved next time through Configure
$test X"$siteman3" = "X" && siteman3=' '

```

Found in path(s):

```

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/installdirs/siteman3.U

```

No license file was found, but licenses were detected in source scan.

```

?RCS: $Id: d_preadv.U 1 2006-08-24 12:32:52Z rmanfredi $
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: $Log: d_preadv.U,v $
?RCS:
?MAKE:d_preadv: Inlibc
?MAKE: -pick add $@ %<
?S:d_preadv:
?S: This variable conditionally defines the HAS_PREADV symbol, which
?S: indicates to the C program that the preadv() routine is available.
?S:.
?C:HAS_PREADV :
?C: This symbol, if defined, indicates that the preadv routine is
?C: available to perform vectored reads on a file descriptor at a
?C: given offset.
?C:.
?H:#$d_preadv HAS_PREADV /**/
?H:.
?LINT:set d_preadv
:
see if preadv exists
set preadv d_preadv
eval $inlibc

```

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/d_preadv.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: scriptdir.U,v 3.1 1999/07/09 18:20:13 doughera Exp doughera \$

?RCS:

?RCS: Copyright (c) 1991-1993, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 3.0.

?RCS:

?RCS: \$Log: scriptdir.U,v \$

?RCS: Revision 3.1 1999/07/09 18:20:13 doughera

?RCS: Updated for installprefix

?RCS:

?RCS: Revision 3.0.1.3 1995/09/25 09:17:15 ram

?RCS: patch59: unit is now forced to the top of Configure, if possible

?RCS:

?RCS: Revision 3.0.1.2 1995/01/30 14:46:13 ram

?RCS: patch49: can now handle installation prefix changes (from WED)

?RCS:

?RCS: Revision 3.0.1.1 1994/08/29 16:32:04 ram

?RCS: patch32: now uses installation prefix

?RCS:

?RCS:

Revision 3.0 1993/08/18 12:09:45 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?MAKE:scriptdir scriptdirexp installscript: cat test Getfile Loc \

Oldconfig +bin Prefixit Setprefixvar prefixexp Prefixup

?MAKE: -pick add \$@ %<

?Y:TOP

?D:scriptdir="

?S:scriptdir:

?S: This variable holds the name of the directory in which the user wants

?S: to put publicly scripts for the package in question. It is either

?S: the same directory as for binaries, or a special one that can be

?S: mounted across different architectures, like /usr/share. Programs

?S: must be prepared to deal with ~name expansion.

?S:.

?D:scriptdirexp="

?S:scriptdirexp:

?S: This variable is the same as scriptdir, but is filename expanded

?S: at configuration time, for programs not wanting to bother with it.

?S:.

?S:installscript:

?S: This variable is usually the same as scriptdirexp, unless you are on

?S: a system running AFS, in which case they may differ slightly. You

?S: should always use this variable

within your makefiles for portability.

?S:.

?C:SCRIPTDIR:

?C: This symbol holds the name of the directory in which the user wants

?C: to put publicly executable scripts for the package in question. It

?C: is often a directory that is mounted across diverse architectures.

?C: Programs must be prepared to deal with ~name expansion.

?C:.

?C:SCRIPTDIR_EXP:

?C: This is the same as SCRIPTDIR, but is filename expanded at

?C: configuration time, for use in programs not prepared to do

?C: ~name substitutions at run-time.

?C:.

?H:#define SCRIPTDIR "\$scriptdir" /**/

?H:#define SCRIPTDIR_EXP "\$scriptdirexp" /**/

?H:.

?T:installscriptdir

?LINT:change prefixvar

?LINT:set scriptdir

?LINT:set scriptdirexp

: determine where public executable scripts go

set scriptdir scriptdir

eval \$prefixit

case "\$scriptdir" in

*)

dflt="\$bin"

: guess some guesses

\$test -d /usr/share/scripts && dflt=/usr/share/scripts

\$test -d /usr/share/bin && dflt=/usr/share/bin

\$test -d /usr/local/script && dflt=/usr/local/script

\$test

-d /usr/local/scripts && dflt=/usr/local/scripts

\$test -d \$prefixexp/script && dflt=\$prefixexp/script

set dflt

eval \$prefixup

::

*) dflt="\$scriptdir"

::

esac

\$cat <<EOM

Some installations have a separate directory just for executable scripts so

that they can mount it across multiple architectures but keep the scripts in one spot. You might, for example, have a subdirectory of /usr/share for this. Or you might just lump your scripts in with all your other executables.

EOM

fn=d~

rp='Where do you keep publicly executable scripts?'

./getfile

if \$test "X\$ansexp" != "X\$scriptdirexp"; then

installscript="

fi

installscriptdir="

prefixvar=scriptdir

./setprefixvar

: A little fix up for an irregularly named variable.

installscript="\$installscriptdir"

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/installdirs/scriptdir.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: siteprefix.U,v 1.1 1999/07/08 18:32:57 doughera Exp doughera \$

?RCS:

?RCS: Copyright (c) 1999 Andy Dougherty

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 3.0.

?RCS:

?RCS: \$Log: siteprefix.U,v \$

?RCS: Revision 1.1 1999/07/08 18:32:57 doughera

?RCS: Initial revision

?RCS:

?MAKE:siteprefix siteprefixexp +oldsiteprefix: Getfile Loc Oldconfig cat package prefix

?MAKE: -pick add \$@ %<

?S:siteprefix:

?S: This variable holds the full absolute path of the directory below

?S: which the user will install add-on packages.

?S: See INSTALL for usage and examples.

?S:.

?S:siteprefixexp:

?S: This variable holds the full absolute path of the

directory below

?S: which the user will install add-on packages. Derived from siteprefix.

?S:.

?S:oldsiteprefix:

?S: This variable is set non-null if the siteprefix was previously defined

?S: and gets set to a new value. Used internally by Configure only.

?S:.

: Set the siteprefix variables

\$cat <<EOM

After \$package is installed, you may wish to install various add-on modules and utilities. Typically, these add-ons will be installed under \$prefix with the rest of this package. However, you may wish to install such add-ons elsewhere under a different prefix.

If you do not wish to put everything under a single prefix, that's ok. You will be prompted for the individual locations; this siteprefix is only used to suggest the defaults.

The default should be fine for most people.

EOM

fn=d~+

rp='Installation prefix to use for add-on modules and utilities?'

: XXX Here might be another good place for an installstyle setting.

case "\$siteprefix" in

") dflt=\$prefix ;;

*) dflt=\$siteprefix

;;

esac

./getfile

: XXX Prefixit unit does not yet support siteprefix and vendorprefix

oldsiteprefix="

case "\$siteprefix" in

") ;;

*) case "\$ans" in

"\$prefix") ;;

*) oldsiteprefix="\$prefix";;

esac

;;

esac

siteprefix="\$ans"

siteprefixexp="\$ansexp"

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/installdirs/siteprefix.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: packadmin.U 1 2006-08-24 12:32:52Z rmanfredi \$

?RCS:
 ?RCS: Copyright (c) 1996, Andy Dougherty
 ?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
 ?RCS:
 ?RCS: You may redistribute only under the terms of the Artistic Licence,
 ?RCS: as specified in the README file that comes with the distribution.
 ?RCS: You may reuse parts of this distribution only within the terms of
 ?RCS: that same Artistic Licence; a copy of which may be found at the root
 ?RCS: of the source tree for dist 4.0.
 ?RCS:
 ?MAKE:packadmin: cf_email Oldconfig Myread cat spackage package
 ?MAKE: -pick add \$@ %<
 ?Y:TOP
 ?S:packadmin:
 ?S: Electronic mail address of the package administrator.
 ?S:.
 : check wehther they will act as local admin for the package
 \$cat <<EOM

If you or somebody else will be maintaining \$package at your site, please
 fill in the correct e-mail address here so that they may be contacted
 if necessary. You may enter "none"
 for no administrator.

```
EOM
case "$packadmin" in
  *) dflt="$cf_email";;
  *) dflt="$packadmin";;
esac
rp="$spackage administrator e-mail address"
./myread
packadmin="$ans"
```

Found in path(s):
 * /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
 debian-perl-5.26.1/dist/U/packadmin.U
 No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$
 ?RCS:
 ?RCS: Copyright (c) 1999, Jarkko Hietaniemi
 ?RCS:
 ?RCS: You may redistribute only under the terms of the Artistic License,
 ?RCS: as specified in the README file that comes with the distribution.
 ?RCS: You may reuse parts of this distribution only within the terms of
 ?RCS: that same Artistic License; a copy of which may be found at the root
 ?RCS: of the source tree for dist 3.0.
 ?RCS:

?MAKE:d_sem_open: Inlibc
?MAKE: -pick add \$@ %<
?S:d_sem_open:
?S: This variable conditionally defines HAS_SEM_OPEN if sem_open() is
?S: available to open a POSIX semaphore.
?S:.
?C:HAS_SEM_OPEN:
?C: This symbol, if defined, indicates that the sem_open system call is
?C: available to open a POSIX semaphore.
?C:.
?H:#\$d_sem_open HAS_SEM_OPEN /**/
?H:.
?LINT:set d_sem_open
: see if sem_open exists
set sem_open d_sem_open
eval \$inlibc

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_sem_open.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_msgget.U 1 2006-08-24 12:32:52Z rmanfredi \$
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: \$Log: d_msgget.U,v \$
?RCS: Revision 3.0 1993/08/18 12:06:39 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:d_msgget: Inlibc
?MAKE: -pick add \$@ %<
?S:d_msgget:
?S: This variable conditionally defines the HAS_MSGGET symbol, which
?S: indicates to the C program that the msgget() routine is available.
?S:.
?C:HAS_MSGGET:
?C: This symbol, if defined, indicates that the msgget() routine is
?C: available to get a new message queue.
?C:.
?H:#\$d_msgget

```
HAS_MSGGET /**/  
?H.:  
?LINT:set d_msgget  
: see if msgget exists  
set msgget d_msgget  
eval $inlibc
```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-  
debian-perl-5.26.1/dist/U/d_msgget.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id$  
?RCS:  
?RCS: Copyright (c) 2002 Jarkko Hietaniemi  
?RCS:  
?RCS: You may distribute under the terms of either the GNU General Public  
?RCS: License or the Artistic License, as specified in the README file.  
?RCS:  
?MAKE:usecjk: Myread Oldconfig Setvar  
?MAKE: -pick add $@ %<  
?Y:TOP  
?S:usecjk:  
?S: This variable conditionally defines the USE_CJK symbol,  
?S: and indicates that Perl should be built to use CJK.  
?S.:  
?C:USE_CJK:  
?C: This symbol, if defined, indicates that Perl should  
?C: be built to use the CJK support of Encode.  
?C.:  
?H:?%<:#ifndef USE_CJK  
?H:?%<:#$usecjk USE_CJK /**/  
?H:?%<:#endif  
?H.:  
?LINT:set usecjk  
?INIT:: set usecjk on the Configure command line to enable cjk.  
?X: We should really have some explanatory text here, and some  
?X: automatic setting of sensible defaults.  
: Check for CJK support  
case "$usecjk" in  
"|$define|true|[yY]*) dflt='y';;  
*) dflt='n';;  
esac  
cat <<EOM
```

Starting from 5.8.0 Perl comes

with encoding support for the CJK languages

(Chinese-Japanese-Korean, CN/JP/KR/TW). Normally shared libraries are used,

which means that the (relatively large, a few megabytes total) CJK encodings are loaded on demand (not consuming any memory if they are unused). However, if you are building Perl statically, and/or are space-constrained, and if you are certain you won't be needing CJK support, you may consider leaving it out. Note that the CJK support will always be built, but if you choose not to have it, it will be skipped in the installation phase.

If this doesn't make any sense to you, just accept the default '\$dflt'.

EOM

```
rp='Build Perl for CJK?'
```

```
./myread
```

```
case "$ans" in
```

```
y*|Y*) val="$define" ;;
```

```
*) val="$undef" ;;
```

```
esac
```

```
set usecjk
```

```
eval $setvar
```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/usecjk.U
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: Instruct.U,v \$

?RCS: Revision 3.0.1.3 1997/02/28 15:02:55 ram

?RCS: patch61: logname / whoami sequence rewritten to use case

?RCS:

?RCS: Revision 3.0.1.2 1995/02/15 14:11:34 ram

?RCS: patch51: author name now appears at the end of the paragraph (WED)

?RCS:

?RCS: Revision 3.0.1.1 1995/01/11 15:12:05 ram

?RCS: patch45: now documents the & escape to turn -d on at the read prompt

?RCS:

?RCS: Revision 3.0 1993/08/18 12:05:04 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?X:

?X:

This unit spew out the directions that we want everyone to read. I try to
?X: keep the first "pagefull" much less than a page since they don't know it
?X: isn't going to go shooting off the top of the screen, and we don't want
?X: to panic them yet.

?X:

?MAKE:Instruct: Begin Myread Configdir contains

?MAKE: -pick wipe \$@ %<

?T:user needman firsttime

: general instructions

needman=true

firsttime=true

user=`(logname) 2>/dev/null`

case "\$user" in

") user=`whoami 2>&1`;;

esac

if \$contains "^\$user\$" ../.config/instruct >/dev/null 2>&1; then

firsttime=false

echo " "

rp='Would you like to see the instructions?'

dflt=n

. ./myread

case "\$ans" in

[yY]*) ;;

*) needman=false;;

esac

fi

if \$needman; then

cat <<EOH

This installation shell script will examine your system and ask you questions to determine how the <PACKAGENAME> package should be installed. If you get stuck on a question, you may use a ! shell escape to start a subshell or execute a command. Many of the questions will have default answers in square brackets; typing carriage return will give you the default.

On some of the questions which ask for file or directory names you are allowed to use the ~name construct to specify the login directory belonging to "name", even if you don't have a shell which knows about that. Questions where this is allowed will be marked "(~name ok)".

EOH

rp="

dflt='Type carriage return to continue'

. ./myread

cat <<'EOH'

The prompter used in this script allows you to use shell variables and

backticks in your answers. You may use \$1, \$2, etc... to refer to the words in the default answer, as if the default line was a set of arguments given to a script shell. This means you may also use \$* to repeat the whole default line, so you do not have to re-type everything to add something to the default.

Everytime there is a substitution, you will have to confirm. If there is an error (e.g. an unmatched backtick), the default answer will remain unchanged and you will be prompted again.

If you are in a hurry, you may run 'Configure -d'. This will bypass nearly all the questions and use the computed defaults (or the previous answers if there was already a config.sh file). Type 'Configure -h' for a list of options. You may also start interactively and then answer '& -d' at any prompt to turn on the non-interactive behaviour for the remainder of the execution.

EOH

```
. ./myread  
cat <<EOH
```

Much effort has been expended to ensure that this shell script will run on any Unix system. If despite that it blows up on yours, your best bet is to edit Configure and run it again. If you can't run Configure for some reason, you'll have to generate a config.sh file by hand. Whatever problems you have, let me (<MAINTLOC>) know how I blew it.

This installation script affects things in two ways:

- 1) it may do direct variable substitutions on some of the files included in this kit.
- 2) it builds a config.h file for inclusion in C programs. You may edit any of these files as the need arises after running this script.

If you make a mistake on a question, there is no easy way to back up to it currently. The easiest thing to do is to edit config.sh and rerun all the SH files. Configure will offer to let you do this before it runs the SH files.

EOH

```
?X: In case they played with the promptper...  
dfilt="Type carriage return to continue"  
. ./myread  
case "$firsttime" in  
true) echo $user >>../.config/instruct;;  
esac  
fi
```

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/Instruct.U

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: d_difftime.U 1 2006-08-24 12:32:52Z rmanfredi $
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: Original Author: Andy Dougherty <doughera@lafcol.lafayette.edu>
?RCS:
?RCS: $Log: d_difftime.U,v $
?RCS: Revision 3.0.1.1 1994/08/29 16:07:31 ram
?RCS: patch32: created by ADO
?RCS:
?MAKE:d_difftime: Inlibc
?MAKE: -pick add $@ %<
?S:d_difftime:
?S: This variable conditionally defines the HAS_DIFFTIME symbol, which
?S: indicates to the C program that the difftime() routine is available.
?S:.
?C:HAS_DIFFTIME :
?C: This symbol, if defined, indicates that
the difftime routine is
?C: available.
?C:.
?H:#$d_difftime HAS_DIFFTIME /**/
?H:.
?LINT:set d_difftime
: see if difftime exists
set difftime d_difftime
eval $inlibc
```

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/d_difftime.U

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id$
?RCS:
?RCS: Copyright (c) 1996, Andy Dougherty
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
```

?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: \$Log: sitelib.U,v \$
?RCS: Revision 3.0.1.1 1997/02/28 16:21:35 ram
?RCS: patch61: created
?RCS:
?MAKE:sitelib sitelibexp installsitelib: afs cat Getfile \
Oldconfig Prefixit test privlib package sed
?MAKE: -pick add \$@ %<
?Y:TOP
?S:sitelib:
?S: This variable contains the eventual value of the SITELIB symbol,
?S: which is the name of the private library for this package. It may
?S: have a ~ on the front. It is up to the makefile to eventually create
?S: this
directory while performing installation (with ~ substitution).
?S:.
?S:sitelibexp:
?S: This variable is the ~name expanded version of sitelib, so that you
?S: may use it directly in Makefiles or shell scripts.
?S:.
?S:installsitelib:
?S: This variable is really the same as sitelibexp but may differ on
?S: those systems using AFS. For extra portability, only this variable
?S: should be used in makefiles.
?S:.
?C:SITELIB:
?C: This symbol contains the name of the private library for this package.
?C: The library is private in the sense that it needn't be in anyone's
?C: execution path, but it should be accessible by the world. The program
?C: should be prepared to do ~ expansion.
?C: The standard distribution will put nothing in this directory.
?C: Individual sites may place their own extensions and modules in
?C: this directory.
?C:.
?C:SITELIB_EXP:
?C: This symbol contains the ~name expanded version of SITELIB, to be used
?C: in programs that are not prepared to deal with ~ expansion
at run-time.
?C:.
?H:#define SITELIB "\$sitelib" /**/
?H:#define SITELIB_EXP "\$sitelibexp" /**/
?H:.
?T:prog

```

: determine where site specific libraries go.
set sitelib sitelib
eval $prefixit
case "$sitelib" in
")
?X: remove any trailing -3.0 or other version identification
prog=`echo $package | $sed 's/-*[0-9.]*$//`
dflt="$privlib/site_`prog`" ;;
*) dflt="$sitelib" ;;
esac
$cat <<EOM

```

The installation process will also create a directory for site-specific extensions and modules. Some users find it convenient to place all local files in this directory rather than in the main distribution directory.

```

EOM
fn=d~+
rp='Pathname for the site-specific library files?'
./getfile
if $test "X$sitelibexp" != "X$sansexp"; then
installsitelib="
fi
sitelib="$ans"
sitelibexp="$sansexp"
if $afs; then
$cat <<EOM

```

Since you are running AFS, I need to distinguish the directory in which private files reside from the directory in which they are installed (and from which they are presumably copied to the former directory by occult means).

```

EOM
case "$installsitelib" in
") dflt=`echo $sitelibexp | sed 's#^/afs/#/afs/.#` ;;
*) dflt="$installsitelib" ;;
esac
fn=de~
rp='Where will private files be installed?'
./getfile
installsitelib="$ans"
else
installsitelib="$sitelibexp"
fi

```

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/sitelib.U

No license file was found, but licenses were detected in source scan.

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?MAKE:d_remquo: Inlibc

?MAKE: -pick add \$@ %<

?S:d_remquo:

?S: This variable conditionally defines the HAS_REMQUO symbol, which

?S: indicates to the C program that the remquo() routine is available.

?S:.

?C:HAS_REMQUO:

?C: This symbol, if defined, indicates that the remquo routine is

?C: available to return the remainder and part of quotient.

?C:.

?H:#\$d_remquo HAS_REMQUO /**/

?H:.

?LINT:set d_remquo

: see if remquo exists

set remquo d_remquo

eval \$inlibc

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_remquo.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_strtod.U 1 2006-08-24 12:32:52Z rmanfredi \$

?RCS:

?RCS: Copyright (c) 1996, Andy Dougherty

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic Licence,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic Licence; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: d_strtod.U,v \$

?RCS: Revision 3.0.1.1 1997/02/28 15:46:36 ram

?RCS: patch61: created

?RCS:

?RCS:

?MAKE:d_strtod: Inlibc

?MAKE: -pick add \$@ %<

?S:d_strtod:

?S: This variable conditionally defines the HAS_STRTOD symbol, which

?S: indicates to the C program that the strtod() routine is available

?S: to provide better numeric string conversion than atof().

?S:.

?C:HAS_STRTOD (STRTOD):

?C: This symbol, if defined,

indicates that the strtod routine is

?C: available to provide better numeric string conversion than atof().

?C:.

?H:#\$d_strtod HAS_STRTOD /**/

?H:.

?LINT:set d_strtod

: see if strtod exists

set strtod d_strtod

eval \$inlibc

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/d_strtod.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: Unix.U,v 3.0.1.1 1997/02/28 15:20:06 ram Exp \$

?RCS:

?RCS: Copyright (c) 1991-1993, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 3.0.

?RCS:

?RCS: \$Log: Unix.U,v \$

?RCS: Revision 3.0.1.1 1997/02/28 15:20:06 ram

?RCS: patch61: created

?RCS:

?X:

?X: The purpose of this unit is to define things that are common across all

?X: known UNIX platforms. If Configure is ported/used on a non-UNIX

?X: environment, then some of the following variables can be redefined in hint

?X: files.

?X:

?MAKE:Unix _exe _a _o exe_ext lib_ext obj_ext path_sep \

firstmakefile archobjs rm_try: Oldconfig rm

?MAKE: -pick add \$@ %<

?S:_exe:

?S: This

variable defines the extension used for executable files.

?S: DJGPP, Cygwin and OS/2 use '.exe'. Stratus VOS uses '.pm'.

?S: On operating systems which do not require a specific extension
?S: for executable files, this variable is empty.
?S:.
?S:_a:
?S: This variable defines the extension used for ordinary library files.
?S: For unix, it is '.a'. The '.' is included. Other possible
?S: values include '.lib'.
?S:.
?S:_o:
?S: This variable defines the extension used for object files.
?S: For unix, it is '.o'. The '.' is included. Other possible
?S: values include '.obj'.
?S:.
?S:firstmakefile:
?S: This variable defines the first file searched by make. On unix,
?S: it is makefile (then Makefile). On case-insensitive systems,
?S: it might be something else. This is only used to deal with
?S: convoluted make depend tricks.
?S:.
?S:archobjs:
?S: This variable defines any additional objects that must be linked
?S: in with the program on this architecture. On unix, it is usually
?S: empty.
It is typically used to include emulations of unix calls
?S: or other facilities. For perl on OS/2, for example, this would
?S: include os2/os2.obj.
?S:.
?X: Metaconfig's Obsolete symbol stuff is too over-eager. In the
?X: perl sources, it picks up things like "P" and "FLOCK" that are
?X: not used in the way Metaconfig thinks they are. Thus I can't
?X: just declare these obsolete and then run metaconfig -o.
?X: Instead, I'll just handle them here.
?X: Sadly, history has conspired to give us a web of definitions;
?X: this could have been much simpler.
?S:lib_ext:
?S: This is an old synonym for _a.
?S:.
?S:exe_ext:
?S: This is an old synonym for _exe.
?S:.
?S:obj_ext:
?S: This is an old synonym for _o.
?S:.
?S:path_sep:
?S: This is an old synonym for p_ in Head.U, the character
?S: used to separate elements in the command shell search PATH.
?S:.
?S:rm_try:

?S: This is a cleanup variable for try test programs.

?S: Internal Configure use only.

?S:.

?LINT: change p_

?INIT:.

Trailing extension. Override this in a hint file, if needed.

?INIT: Extra object files, if any, needed on this platform.

?INIT:archobjs="

: Define several unixisms.

: Hints files or command line option can be used to override them.

: The convoluted testing is in case hints files set either the old

: or the new name.

```

case "$_exe" in
") case "$exe_ext" in
") ;;
*) _exe="$exe_ext" ;;
esac
;;
esac
case "$_a" in
") case "$lib_ext" in
") _a='.a';;
*) _a="$lib_ext" ;;
esac
;;
esac
case "$_o" in
") case "$obj_ext" in
") _o='.o';;
*) _o="$obj_ext";;
esac
;;
esac
case "$p_" in
") case "$path_sep" in
") p_=':':;
*) p_="$path_sep";;
esac
;;
esac
exe_ext=$_exe
lib_ext=$_a
obj_ext=$_o
path_sep=$p_

rm_try="$rm -f try try$_exe a.out .out try.[cho] try.$_o core core.try* try.core*"

@if firstmakefile

```

: Which makefile gets called first. This is used by make depend.

```
case "$firstmakefile" in
") firstmakefile='makefile';;
esac
```

@end

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-  
debian-perl-5.26.1/U/modified/Unix.U
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_getnetbyname_r.U,v 0RCS:

?RCS: Copyright (c) 2002,2003 Jarkko Hietaniemi

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?RCS: Generated by the reentr.pl from the Perl 5.8 distribution.

?RCS:

?MAKE:d_getnetbyname_r getnetbyname_r_proto: Inlibc Protochk Hasproto \
i_systypes usethreads i_netdb extern_C

?MAKE: -pick add \$@ %<

?S:d_getnetbyname_r:

?S: This variable conditionally defines the HAS_GETNETBYNAME_R symbol,

?S: which indicates to the C program that the getnetbyname_r()

?S: routine is available.

?S:.

?S:getnetbyname_r_proto:

?S: This variable encodes the prototype of getnetbyname_r.

?S: It is zero if d_getnetbyname_r is undef, and one of the

?S: REENTRANT_PROTO_T_ABC macros of reentr.h if d_getnetbyname_r

?S: is defined.

?S:.

?C:HAS_GETNETBYNAME_R:

?C: This symbol, if defined, indicates that

the getnetbyname_r routine

?C: is available to getnetbyname re-entrantly.

?C:.

?C:GETNETBYNAME_R_PROTO:

?C: This symbol encodes the prototype of getnetbyname_r.

?C: It is zero if d_getnetbyname_r is undef, and one of the

?C: REENTRANT_PROTO_T_ABC macros of reentr.h if d_getnetbyname_r

?C: is defined.

?C:.

?H:#d_getnetbyname_r HAS_GETNETBYNAME_R /**/

?H:#define GETNETBYNAME_R_PROTO \$getnetbyname_r_proto /**/

?H:.

```

?T:try hdrs d_getnetbyname_r_proto
: see if getnetbyname_r exists
set getnetbyname_r d_getnetbyname_r
eval $inlibc
case "$d_getnetbyname_r" in
"$define")
hdrs="$i_systypes sys/types.h define stdio.h $i_netdb netdb.h"
case "$d_getnetbyname_r_proto:$usethreads" in
":define") d_getnetbyname_r_proto=define
set d_getnetbyname_r_proto getnetbyname_r $hdrs
eval $hasproto ;;
*) ;;
esac
case "$d_getnetbyname_r_proto" in
define)
case "$getnetbyname_r_proto" in
"|0) try='int getnetbyname_r(const char*, struct netent*, char*, size_t, struct netent**, int*);'
./protochk
"$extern_C $try" $hdrs && getnetbyname_r_proto=I_CSBWRE ;;
esac
case "$getnetbyname_r_proto" in
"|0) try='int getnetbyname_r(const char*, struct netent*, char*, int);'
./protochk "$extern_C $try" $hdrs && getnetbyname_r_proto=I_CSBI ;;
esac
case "$getnetbyname_r_proto" in
"|0) try='struct netent* getnetbyname_r(const char*, struct netent*, char*, int);'
./protochk "$extern_C $try" $hdrs && getnetbyname_r_proto=S_CSBI ;;
esac
case "$getnetbyname_r_proto" in
"|0) try='int getnetbyname_r(const char*, struct netent*, struct netent_data*);'
./protochk "$extern_C $try" $hdrs && getnetbyname_r_proto=I_CSD ;;
esac
case "$getnetbyname_r_proto" in
"|0) d_getnetbyname_r=undef
getnetbyname_r_proto=0
echo "Disabling getnetbyname_r, cannot determine prototype." >&4 ;;
*) case "$getnetbyname_r_proto" in
REENTRANT_PROTO*) ;;
*) getnetbyname_r_proto="REENTRANT_PROTO_$getnetbyname_r_proto" ;;
esac
echo "Prototype: $try" ;;
esac
;;
*) case "$usethreads" in
define)
echo "getnetbyname_r has no prototype, not using it." >&4 ;;
esac
d_getnetbyname_r=undef

```

```
getnetbyname_r_proto=0
;;
esac
;;
*) getnetbyname_r_proto=0
;;
esac
```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/threads/d_getnetbyname_r.U
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_rename.U 1 2006-08-24 12:32:52Z rmanfredi \$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic Licence,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic Licence; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: d_rename.U,v \$

?RCS: Revision 3.0 1993/08/18 12:06:54 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?MAKE:d_rename: Inlibc

?MAKE: -pick add \$@ %<

?S:d_rename:

?S: This variable conditionally defines the HAS_RENAME symbol, which

?S: indicates to the C program that the rename() routine is available

?S: to rename files.

?S:.

?C:HAS_RENAME (RENAME):

?C: This symbol, if defined, indicates that the rename routine is available

?C: to rename files.

Otherwise you should do the unlink(), link(), unlink()

?C: trick.

?C:.

?H:#\$d_rename HAS_RENAME /**/

?H:.

?LINT:set d_rename

: see if rename exists

set rename d_rename

eval \$inlibc

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/d_rename.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: sh.U,v 3.0.1.1 1997/02/28 16:20:13 ram Exp \$

?RCS:

?RCS: Copyright (c) 1997, Chip Salzenberg

?RCS: Copyright (c) 1991-1993, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 3.0.

?RCS:

?RCS: \$Log: sh.U,v \$

?RCS: Revision 3.0.1.1 1997/02/28 16:20:13 ram

?RCS: patch61: created

?RCS:

?MAKE:sh targetsh: Head

?MAKE: -pick wipe \$@ %<

?S:sh:

?S: This variable contains the full pathname of the shell used

?S: on this system to execute Bourne shell scripts. Usually, this will be

?S: /bin/sh, though it's possible that some systems will have /bin/ksh,

?S: /bin/pdksh, /bin/ash, /bin/bash, or even something such as

?S: D:/bin/sh.exe.

?S: This

unit comes before Options.U, so you can't set sh with a -D

?S: option, though you can override this (and startsh)

?S: with -O -Dsh=/bin/whatever -Dstartsh=whatever

?S:.

?S:targetsh:

?S: If cross-compiling, this variable contains the location of sh on the

?S: target system.

?S: If not, this will be the same as \$sh.

?S:.

?C:SH_PATH:

?C: This symbol contains the full pathname to the shell used on this

?C: on this system to execute Bourne shell scripts. Usually, this will be

?C: /bin/sh, though it's possible that some systems will have /bin/ksh,

?C: /bin/pdksh, /bin/ash, /bin/bash, or even something such as

?C: D:/bin/sh.exe.

?C:.

?H:#define SH_PATH "\$targetsh" /**/

?H:.

?T:xxx try pth p SYSTYPE

?LINT:extern maintloc maintname _exe

?X:

?X: Be quiet unless something unusual happens because this gets

?X: loaded up even before options are processed.

?X: Can't use ./loc because that depends on startsh, which, in turn

?X: depends on this unit.

?X:

: Find the basic shell for

Bourne shell scripts

case "\$sh" in

")

?X: SYSTYPE is for some older MIPS systems.

?X: I do not know if it is still needed.

case "\$SYSTYPE" in

bsd|sys5*) xxx="/\$SYSTYPE/bin/sh";;

*) xxx='/bin/sh';;

esac

if test -f "\$xxx"; then

sh="\$xxx"

else

: Build up a list and do a single loop so we can 'break' out.

pth=`echo \$PATH | sed -e "s/\$p_/ /g"``

for xxx in sh bash ksh pdksh ash; do

for p in \$pth; do

try="\$try \${p}/\${xxx}"

done

done

for xxx in \$try; do

if test -f "\$xxx"; then

sh="\$xxx";

break

elif test "X\$_exe" != X -a -f "\$xxx\$_exe"; then

sh="\$xxx";

break

elif test -f "\$xxx.exe"; then

sh="\$xxx";

break

fi

done

fi

::

esac

?X: fd 4 isn't open yet...

case "\$sh" in

") cat >&2 <<EOM

\$me: Fatal Error: I can't find a Bourne Shell anywhere.

Usually it's in /bin/sh. How did you even get this far?

Please contact me (<\$maintname>) at <\$maintloc> and
we'll try to straighten this all out.

EOM

exit 1

::

esac

: When cross-compiling

we need to separate the sh-to-run-Configure-with from the sh-to-use-in-Perl

: default both to the same thing, cross-compilers can then set targetsh differently if they like
targetsh=\$sh

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/modified/sh.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_link.U 1 2006-08-24 12:32:52Z rmanfredi \$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic Licence,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic Licence; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: d_link.U,v \$

?RCS: Revision 3.0.1.1 1993/08/25 14:01:13 ram

?RCS: patch6: created for completeness

?RCS:

?MAKE:d_link: Inlibc

?MAKE: -pick add \$@ %<

?S:d_link:

?S: This variable conditionally defines HAS_LINK if link() is

?S: available to create hard links.

?S:.

?C:HAS_LINK:

?C: This symbol, if defined, indicates that the link routine is

?C: available to create hard links.

?C:.

?H:#\$d_link HAS_LINK /**/

?H:.

?LINT:set d_link

: see if link exists

set

link d_link

eval \$inlibc

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/d_link.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_fchown.U 1 2006-08-24 12:32:52Z rmanfredi \$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic Licence,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic Licence; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: d_fchown.U,v \$

?RCS: Revision 3.0 1993/08/18 12:06:01 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?MAKE:d_fchown: Inlibc

?MAKE: -pick add \$@ %<

?S:d_fchown:

?S: This variable conditionally defines the HAS_FCHOWN symbol, which

?S: indicates to the C program that the fchown() routine is available

?S: to change ownership of opened files.

?S:.

?C:HAS_FCHOWN (FCHOWN):

?C: This symbol, if defined, indicates that the fchown routine is available

?C: to

change ownership of opened files. If unavailable, use chown().

?C:.

?H:#\$d_fchown HAS_FCHOWN /**/

?H:.

?LINT:set d_fchown

: see if fchown exists

set fchown d_fchown

eval \$inlibc

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/d_fchown.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: vendorhtml1.U,v 1.1 1999/07/08 18:32:57 doughera Exp doughera \$

?RCS:

?RCS: Copyright (c) 1999, Andy Dougherty

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 3.0.
?RCS:
?RCS: \$Log: vendorhtml1.U,v \$
?RCS: Revision 1.1 1999/07/08 18:32:57 doughera
?RCS: Initial revision
?RCS:
?MAKE:vendorhtml1 vendorhtml1exp installvendorhtml1: html1dir Getfile \
Oldconfig Setprefixvar Prefixit test vendorprefix prefix sed
?MAKE: -pick add \$@ %<
?Y:TOP
?S:vendorhtml1:
?S: This variable contains the name of the directory for html
?S: pages. It may have a ~ on the front.
?S: The standard distribution will put nothing in this directory.
?S: Vendors
who distribute perl may wish to place their own
?S: html pages in this directory with
?S: MakeMaker Makefile.PL INSTALLDIRS=vendor
?S: or equivalent. See INSTALL for details.
?S:.
?S:vendorhtml1exp:
?S: This variable is the ~name expanded version of vendorhtml1, so that you
?S: may use it directly in Makefiles or shell scripts.
?S:.
?D:installvendorhtml1="
?S:installvendorhtml1:
?S: This variable is really the same as vendorhtml1exp but may differ on
?S: those systems using AFS. For extra portability, only this variable
?S: should be used in makefiles.
?S:.
?LINT:change prefixvar
?LINT:set installvendorhtml1
: Set the vendorhtml1 variables
case "\$vendorprefix" in
") vendorhtml1="
vendorhtml1exp="
;;
*) : determine where vendor-supplied html pages go.
: There is no standard location, so try to copy the previously-selected
: directory structure for the core html pages.
: XXX Better default suggestions would be welcome.
case "\$vendorhtml1" in
") dflt=`echo "\$html1dir"

```

| $sed "s#^$prefix#$vendorprefix#"` ;;
*) dflt=$vendorhtml1 ;;
esac
case "$dflt" in
"|' ') dflt=none ;;
esac
fn=dn+~
rp='Pathname for the vendor-supplied html pages?'
./getfile
vendorhtml1="$ans"
vendorhtml1exp="$ansexp"
;;
esac
: Use ' ' for none so value is preserved next time through Configure
$test X"$vendorhtml1" = "X" && vendorhtml1=' '
prefixvar=vendorhtml1
./installprefix

```

Found in path(s):

```

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/installdirs/vendorhtml1.U

```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1999, Jarkko Hietaniemi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 3.0.

?RCS:

?MAKE:d_timer_gettime: Inlibc

?MAKE: -pick add \$@ %<

?S:d_timer_gettime:

?S: This variable conditionally defines HAS_TIMER_GETTIME

?S: if timer_gettime() is available to get the time of a POSIX timer.

?S:.

?C:HAS_TIMER_GETTIME:

?C: This symbol, if defined, indicates that the timer_gettime

?C: system call is available to get the time of a POSIX timer.

?C:.

?H:#\$d_timer_gettime HAS_TIMER_GETTIME /**/

?H:.

?LINT:set d_timer_gettime

: see if timer_gettime exists

set timer_gettime d_timer_gettime

eval \$inlibc

Found in path(s):

*

/opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_timer_gettime.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_getgrgid_r.U,v 0RCS:

?RCS: Copyright (c) 2002,2003 Jarkko Hietaniemi

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?RCS: Generated by the reentr.pl from the Perl 5.8 distribution.

?RCS:

?MAKE:d_getgrgid_r getgrgid_r_proto: Inlibc Protochk Hasproto i_systypes \
usethreads i_grp extern_C

?MAKE: -pick add \$@ %<

?S:d_getgrgid_r:

?S: This variable conditionally defines the HAS_GETGRGID_R symbol,

?S: which indicates to the C program that the getgrgid_r()

?S: routine is available.

?S:.

?S:getgrgid_r_proto:

?S: This variable encodes the prototype of getgrgid_r.

?S: It is zero if d_getgrgid_r is undef, and one of the

?S: REENTRANT_PROTO_T_ABC macros of reentr.h if d_getgrgid_r

?S: is defined.

?S:.

?C:HAS_GETGRGID_R:

?C: This symbol, if defined, indicates that the getgrgid_r routine

?C: is available to

getgrgid re-entrantly.

?C:.

?C:GETGRGID_R_PROTO:

?C: This symbol encodes the prototype of getgrgid_r.

?C: It is zero if d_getgrgid_r is undef, and one of the

?C: REENTRANT_PROTO_T_ABC macros of reentr.h if d_getgrgid_r

?C: is defined.

?C:.

?H:#\$d_getgrgid_r HAS_GETGRGID_R /**/

?H:#define GETGRGID_R_PROTO \$getgrgid_r_proto /**/

?H:.

?T:try hdrs d_getgrgid_r_proto

: see if getgrgid_r exists

set getgrgid_r d_getgrgid_r

eval \$inlibc

```

case "$d_getgrgid_r" in
"$define")
hdrs="$i_systypes sys/types.h define stdio.h $i_grp grp.h"
case "$d_getgrgid_r_proto:$usethreads" in
":define") d_getgrgid_r_proto=define
set d_getgrgid_r_proto getgrgid_r $hdrs
eval $hasproto ;;
*) ;;
esac
case "$d_getgrgid_r_proto" in
define)
case "$getgrgid_r_proto" in
"$getgrgid_r_proto" in
"|0) try='int getgrgid_r(gid_t, struct group*, char*, size_t, struct group**);'
./protochk "$extern_C $try" $hdrs && getgrgid_r_proto=I_TSBWR ;;
esac
case "$getgrgid_r_proto" in
"|0) try='int getgrgid_r(gid_t, struct group*, char*, int,
struct group**);'
./protochk "$extern_C $try" $hdrs && getgrgid_r_proto=I_TSBIR ;;
esac
case "$getgrgid_r_proto" in
"|0) try='int getgrgid_r(gid_t, struct group*, char*, int);'
./protochk "$extern_C $try" $hdrs && getgrgid_r_proto=I_TSB I ;;
esac
case "$getgrgid_r_proto" in
"|0) try='struct group* getgrgid_r(gid_t, struct group*, char*, int);'
./protochk "$extern_C $try" $hdrs && getgrgid_r_proto=S_TSB I ;;
esac
case "$getgrgid_r_proto" in
"|0) d_getgrgid_r=undef
getgrgid_r_proto=0
echo "Disabling getgrgid_r, cannot determine prototype." >&4 ;;
*) case "$getgrgid_r_proto" in
REENTRANT_PROTO*) ;;
*) getgrgid_r_proto="REENTRANT_PROTO_$getgrgid_r_proto" ;;
esac
echo "Prototype: $try" ;;
esac
;;
*) case "$usethreads" in
define) echo "getgrgid_r has no prototype, not using it." >&4 ;;
esac
d_getgrgid_r=undef
getgrgid_r_proto=0
;;
esac
;;
*) getgrgid_r_proto=0

```

```
;;
esac
```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/threads/d_getgrgid_r.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: i_stddef.U 1 2006-08-24 12:32:52Z rmanfredi $
```

```
?RCS:
```

```
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
```

```
?RCS:
```

```
?RCS: You may redistribute only under the terms of the Artistic Licence,
```

```
?RCS: as specified in the README file that comes with the distribution.
```

```
?RCS: You may reuse parts of this distribution only within the terms of
```

```
?RCS: that same Artistic Licence; a copy of which may be found at the root
```

```
?RCS: of the source tree for dist 4.0.
```

```
?RCS:
```

```
?RCS: $Log: i_stddef.U,v $
```

```
?RCS: Revision 3.0 1993/08/18 12:08:27 ram
```

```
?RCS: Baseline for dist 3.0 netwide release.
```

```
?RCS:
```

```
?MAKE:i_stddef: Inhdr
```

```
?MAKE: -pick add $@ %<
```

```
?S:i_stddef:
```

```
?S: This variable conditionally defines the I_STDDEF symbol, which
```

```
?S: indicates to the C program that <stddef.h> exists and should
```

```
?S: be included.
```

```
?S:.
```

```
?C:I_STDDEF:
```

```
?C: This symbol, if defined, indicates that <stddef.h> exists and should
```

```
?C: be included.
```

```
?C:.
```

```
?H:#$i_stddef I_STDDEF /**/
```

```
?H:.
```

```
?LINT:set
```

```
  i_stddef
```

```
  : see if stddef is available
```

```
  set stddef.h i_stddef
```

```
  eval $inhdr
```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/i_stddef.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: d_rmdir.U 1 2006-08-24 12:32:52Z rmanfredi $
```

```
?RCS:
```

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: d_rmdir.U,v \$

?RCS: Revision 3.0 1993/08/18 12:06:56 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?MAKE:d_rmdir: Inlibc

?MAKE: -pick add \$@ %<

?S:d_rmdir:

?S: This variable conditionally defines HAS_RMDIR if rmdir() is
?S: available to remove directories.

?S:.

?C:HAS_RMDIR (RMDIR):

?C: This symbol, if defined, indicates that the rmdir routine is
?C: available to remove directories. Otherwise you should fork off a
?C: new process to exec
/bin/rmdir.

?C:.

?H:#\$d_rmdir HAS_RMDIR /**/

?H:.

?LINT:set d_rmdir
: see if rmdir exists
set rmdir d_rmdir
eval \$inlibc

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/d_rmdir.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 2000 Jarkko Hietaniemi

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public
?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?MAKE:d_fpclassl: Inlibc

?MAKE: -pick add \$@ %<

?S:d_fpclassl:

?S: This variable conditionally defines the HAS_FPCLASSL symbol, which
?S: indicates to the C program that the fpclassl() routine is available.

```

?S:.
?C:HAS_FPCLASSL:
?C: This symbol, if defined, indicates that the fpclassl routine is
?C: available to classify long doubles. Available for example in IRIX.
?C: The returned values are defined in <ieeefp.h> and are:
?C:
?C: FP_SNAN signaling NaN
?C: FP_QNAN quiet NaN
?C: FP_NINF negative infinity
?C: FP_PINF positive infinity
?C: FP_NDENORM negative denormalized non-zero
?C: FP_PDENORM positive denormalized non-zero
?C: FP_NZERO negative zero
?C: FP_PZERO positive zero
?C: FP_NNORM negative
normalized non-zero
?C: FP_PNORM positive normalized non-zero
?C:.
?H:#$d_fpclassl HAS_FPCLASSL /**/
?H:.
?LINT:set d_fpclassl
: see if fpclassl exists
set fpclassl d_fpclassl
eval $inlibc

```

Found in path(s):

```

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/perl/d_fpclassl.U

```

No license file was found, but licenses were detected in source scan.

```

?RCS: $Id$
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: Original Author: Andy Dougherty <doughera@lafcol.lafayette.edu>
?RCS:
?RCS: $Log: Ins.U,v $
?RCS: Revision 3.0.1.1 1994/06/20 07:05:52 ram
?RCS: patch30: created by ADO
?RCS:
?MAKE:issymlink: Ins test rm
?MAKE: -pick add $@ %<

```

```

?S:issymLink:
?S: This variable holds the test command to test for a symbolic link
?S: (if they are supported). Typical values include 'test -h' and
?S: 'test -L'.
?S:.
?T:pth p
?LINT:change PATH test
?LINT:extern newsh
: determine whether symbolic links are supported
echo
" "
case "$lns" in
*"ln*" -s")
echo "Checking how to test for symbolic links..." >&4
$lns blurfl sym
if $test "X$issymLink" = X; then
?X:
?X: In some AIX 4 versions the (ksh) builtin test (-h) is broken.
?X:
case "$newsh" in
") sh -c "PATH= test -h sym" >/dev/null 2>&1 ;;
*) $newsh -c "PATH= test -h sym" >/dev/null 2>&1 ;;
esac
if test $? = 0; then
issymLink="test -h"
else
echo "Your builtin 'test -h' may be broken." >&4
case "$stest" in
/*) ;;
*) pth=`echo $PATH | sed -e "s/$p_/ /g"`
for p in $pth
do
if test -f "$p/$stest"; then
test="$p/$stest"
break
fi
done
;;
esac
case "$stest" in
/*)
echo "Trying external '$stest -h'." >&4
issymLink="$stest -h"
if $stest ! -h sym >/dev/null 2>&1; then
echo "External '$stest -h' is broken, too." >&4
issymLink="
fi
;;

```

```

*) issymLink=" ;;
esac
fi
fi
if $test "X$issymLink" = X; then
if $test -L sym 2>/dev/null; then
issymLink="$test
-L"
echo "The builtin '$test -L' worked." >&4
fi
fi
if $test "X$issymLink" != X; then
echo "You can test for symbolic links with '$issymLink'." >&4
else
echo "I do not know how you can test for symbolic links." >&4
fi
$rm -f blurfl sym
;;
*) echo "No symbolic links, so not testing for their testing..." >&4
;;
esac

```

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/issymLink.U

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/issymLink.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: oldarchlib.U,v \$

?RCS:

?RCS: Copyright (c) 1996-1998, Andy Dougherty

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?MAKE:d_oldarchlib oldarchlib oldarchlibexp : archname privlib \

archlib sitearch Getfile test Setvar Prefixit

?MAKE: -pick add \$@ %<

?Y:TOP

?S:d_oldarchlib:

?S: This variable conditionally defines OLDARCHLIB to hold the pathname

?S: of architecture-dependent library files for a previous

?S: version of \$package.

?S:.

?S:oldarchlib:

?S: This variable holds the name of the directory in which perl5.000

?S: and perl5.001 stored

?S: architecture-dependent public library files.

?S:.

?S:oldarchlibexp:

?S: This variable is the same as the oldarchlib variable, but is

?S: filename expanded at configuration time, for convenient use.

?S:.

?C:OLDARCHLIB:

?C: This variable, if defined, holds the

name of the directory in

?C: which the user has perl5.000 or perl5.001 architecture-dependent

?C: public library files for \$package. For the most part, these

?C: files will work with 5.002 (and later), but that is not

?C: guaranteed.

?C:.

?C:OLDARCHLIB_EXP:

?C: This symbol contains the ~name expanded version of OLDARCHLIB, to be

?C: used in programs that are not prepared to deal with ~ expansion at

?C: run-time.

?C:.

?H:#\$d_oldarchlib OLDARCHLIB "\$soldarchlib" /**/

?H:#\$d_oldarchlib OLDARCHLIB_EXP "\$soldarchlibexp" /**/

?H:.

?LINT:set d_oldarchlib

: determine where old public architecture dependent libraries might be

case "\$soldarchlib" in

) case "\$privlib" in

) ;;

*) dflt="\$privlib/\$sarchname"

;;

esac

;;

*) dflt="\$soldarchlib"

;;

esac

if \$test ! -d "\$dflt/auto"; then

dflt=none

fi

cat <<EOM

In 5.001, Perl stored architecture-dependent library files in a directory with a name such as \$privlib/\$sarchname, and this directory contained files from the standard extensions and files from any additional extensions you might have added. Starting with version 5.002, all the architecture-dependent standard extensions will go into a version-specific directory such as \$sarchlib, while locally-added extensions will go into

\$sitearch.

If you wish Perl to continue to search the old architecture-dependent library for your local extensions, give the path to that directory.

If you do not wish to use your old architecture-dependent library files, answer 'none'.

EOM

fn=dn~

rp='Directory for your old 5.001 architecture-dependent libraries?'

./getfile

oldarchlib="\$ans"

oldarchlibexp="\$ansexp"

case "\$oldarchlib" in

"|' ') val="\$undef" ;;

*) val="\$define" ;;

esac

set d_oldarchlib

eval \$setvar

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/oldarchlib.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: Begin.U 1 2006-08-24 12:32:52Z rmanfredi \$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic Licence,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic Licence; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: Begin.U,v \$

?RCS: Revision 3.0.1.3 1997/02/28 14:56:35 ram

?RCS: patch61: added Extractall dependency

?RCS:

?RCS: Revision 3.0.1.2 1995/01/30 14:25:08 ram

?RCS: patch49: avoid an empty rmlist: systems might choke on it (WED)

?RCS:

?RCS: Revision 3.0.1.1 1994/10/31 09:32:20 ram

?RCS: patch44: created

?RCS:

?X:

?X: This file comes after option processing had been done and after all

?X: the default values have been set up. It marks the beginning

of questions.

?X: It is important that Options be listed *after* Myinit to ensure that the

?X: default initializations performed by Init and Myinit will not clobber

?X: any setting done on the command line via -D or -U.

?X:

?MAKE:Begin: Myinit Options package Extractall

?MAKE: -pick add \$@ %<

: Eunice requires " " instead of "", can you believe it

echo " "

: Here we go...

echo "Beginning of configuration questions for \$package."

?X: Make sure the rm below is given a non-empty list for some systems.

?X: This is run only when within the UU directory, hence we can safely

?X: attempt to rm a non-existent 'X' file...

trap 'echo " "; test -d ../UU && rm -rf X \$rmlist; exit 1' 1 2 3 15

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/Begin.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_wcstombs.U 1 2006-08-24 12:32:52Z rmanfredi \$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic Licence,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic Licence; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: d_wcstombs.U,v \$

?RCS: Revision 3.0 1993/08/18 12:08:03 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?MAKE:d_wcstombs: Inlibc

?MAKE: -pick add \$@ %<

?S:d_wcstombs:

?S: This variable conditionally defines the HAS_WCSTOMBS symbol, which

?S: indicates to the C program that the wcstombs() routine is available

?S: to convert wide character strings to multibyte strings.

?S:.

?C:HAS_WCSTOMBS:

?C: This symbol, if defined, indicates that the wcstombs

routine is

?C: available to convert wide character strings to multibyte strings.

?C:.

?H:#\$d_wcstombs HAS_WCSTOMBS /**/

?H:.

?LINT:set d_wcstombs

: see if wcstombs exists

set wcstombs d_wcstombs

eval \$inlibc

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/d_wcstombs.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1999 Jarkko Hietaniemi

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?MAKE:d_hasmntopt: Inlibc

?MAKE: -pick add \$@ %<

?S:d_hasmntopt:

?S: This variable conditionally defines the HAS_HASMNTOPT symbol, which

?S: indicates to the C program that the hasmntopt() routine is available

?S: to query the mount options of file systems.

?S:.

?C:HAS_HASMNTOPT:

?C: This symbol, if defined, indicates that the hasmntopt routine is

?C: available to query the mount options of file systems.

?C:.

?H:#\$d_hasmntopt HAS_HASMNTOPT /**/

?H:.

?LINT:set d_hasmntopt

: see if hasmntopt exists

set hasmntopt d_hasmntopt

eval \$inlibc

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_hasmntopt.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: \$Log: usnm.U,v \$
?RCS: Revision 3.0.1.1 1997/02/28 16:26:40 ram
?RCS: patch61: don't use nm with the GNU C library
?RCS: patch61: added support for Linux shared libs
?RCS:
?RCS: Revision 3.0 1993/08/18 12:09:57 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:usnm runnm nm_opt nm_so_opt: cat test Myread Oldconfig grep \
d_gnulibc nm egrep rsrc osname Guess
?MAKE: -pick add \$@ %<
?S:usnm:
?S: This variable contains 'true' or 'false' depending whether the
?S: nm extraction is wanted
or not.
?S:.
?S:runnm:
?S: This variable contains 'true' or 'false' depending whether the
?S: nm extraction should be performed or not, according to the value
?S: of usnm and the flags on the Configure command line.
?S:.
?S:nm_opt:
?S: This variable holds the options that may be necessary for nm.
?S:.
?S:nm_so_opt:
?S: This variable holds the options that may be necessary for nm
?S: to work on a shared library but that can not be used on an
?S: archive library. Currently, this is only used by Linux, where
?S: nm --dynamic is *required* to get symbols from an ELF library which
?S: has been stripped, but nm --dynamic is *fatal* on an archive library.
?S: Maybe Linux should just always set usnm=false.
?S:.
: see if nm is to be used to determine whether a symbol is defined or not
?X: If there is enough inquiries, it might be worth to wait for the nm
?X: extraction. Otherwise, the C compilations might be a better deal.
?X:
?X: Don't bother if we're using GNU libc -- skimo
case "\$usnm"
in
")
dflt="
case "\$d_gnulibc" in
"\$define")
echo " "

```

echo "$nm probably won't work on the GNU C Library." >&4
dflt=n
;;
esac
case "$dflt" in
")
if $test "$osname" = aix -a ! -f /lib/syscalls.exp; then
echo " "
echo "Whoops! This is an AIX system without /lib/syscalls.exp!" >&4
echo "'nm' won't be sufficient on this system." >&4
dflt=n
fi
;;
esac
case "$dflt" in
")
if ./gnu; then
echo " "
echo "Hmm... A GNU system without a GNU C Library? Weird..." >&4
dflt=n
else
dflt=`$grep 'inlibc|csym' $src/Configure | wc -l 2>/dev/null`
if $test $dflt -gt 20; then
dflt=y
else
dflt=n
fi
fi
;;
esac
*)
case "$usenm" in
true|$define) dflt=y;;
*) dflt=n;;
esac
;;
esac
$cat <<EOM

```

I can use \$nm to extract the symbols from your C libraries. This is a time consuming task which may generate huge output on the disk (up to 3 megabytes) but that should make the symbols extraction faster. The alternative is to skip the 'nm' extraction part and to compile a small test program instead to determine whether each symbol is present. If you have a fast C compiler and/or if your 'nm' output cannot be parsed, this may be the best solution.

EOM

```
rp='Shall I use nm to extract C symbols from the libraries?'
./myread
case "$ans" in
[Nn]*) usenm=false;;
*) usenm=true;;
esac
```

?X: Name extraction is to be run if 'nm' usage is wanted and if no -r flag
?X: was provided to configure (in which case we simply re-use the previous
?X: values).

```
runnm=$usenm
case "$reusval" in
true) runnm=false;;
esac
```

: nm options which may be necessary

```
case "$nm_opt" in
") if $test -f /mach_boot; then
nm_opt=" # Mach
elif $test -d /usr/ccs/lib; then
nm_opt='-p' # Solaris (and SunOS?)
elif $test -f /dgux; then
nm_opt='-p' # DG-UX
elif $test -f /lib64/rld; then
nm_opt='-p' # 64-bit Irix
else
nm_opt="
fi;;
esac
```

?X: nm options which may be necessary for shared libraries but illegal

?X: for archive libraries. Thank you,

Linux.

```
case "$nm_so_opt" in
") case "$osname" in
*linux*)
if $nm --help | $grep 'dynamic' > /dev/null 2>&1; then
nm_so_opt='--dynamic'
fi
;;
esac
;;
esac
```

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-

debian-perl-5.26.1/dist/U/usenm.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: sitelib.U,v 1.1 1999/07/08 18:32:57 doughera Exp doughera \$

?RCS:

?RCS: Copyright (c) 1996-1998, Andy Dougherty

?RCS: Copyright (c) 1991-1993, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 3.0.

?RCS:

?RCS: \$Log: sitelib.U,v \$

?RCS: Revision 1.1 1999/07/08 18:32:57 doughera

?RCS: Initial revision

?RCS:

?RCS: Revision 3.0.1.1 1997/02/28 16:21:35 ram

?RCS: patch61: created

?RCS:

?MAKE:sitelib sitelibexp installsitelib sitelib_stem: cat Getfile Oldconfig \

Setprefixvar Prefixit package version sed installstyle siteprefix

?MAKE: -pick add \$@ %<

?Y:TOP

?D:sitelib="

?S:sitelib:

?S: This variable contains the

eventual value of the SITELIB symbol,

?S: which is the name of the private library for this package. It may

?S: have a ~ on the front. It is up to the makefile to eventually create

?S: this directory while performing installation (with ~ substitution).

?S: The standard distribution will put nothing in this directory.

?S: After perl has been installed, users may install their own local

?S: architecture-independent modules in this directory with

?S: MakeMaker Makefile.PL

?S: or equivalent. See INSTALL for details.

?S:.

?D:sitelibexp="

?S:sitelibexp:

?S: This variable is the ~name expanded version of sitelib, so that you

?S: may use it directly in Makefiles or shell scripts.

?S:.

?D:installsitelib="

?S:installsitelib:

?S: This variable is really the same as sitelibexp but may differ on

?S: those systems using AFS. For extra portability, only this variable

?S: should be used in makefiles.

?S:.

?S:sitelib_stem:

?S: This variable is \$sitelibexp with any trailing version-specific component

?S: removed.

The elements in inc_version_list (inc_version_list.U) can

?S: be tacked onto this variable to generate a list of directories to search.

?S:.

?C:SITELIB:

?C: This symbol contains the name of the private library for this package.

?C: The library is private in the sense that it needn't be in anyone's

?C: execution path, but it should be accessible by the world. The program

?C: should be prepared to do ~ expansion.

?C: The standard distribution will put nothing in this directory.

?C: After perl has been installed, users may install their own local

?C: architecture-independent modules in this directory with

?C: MakeMaker Makefile.PL

?C: or equivalent. See INSTALL for details.

?C:.

?C:SITELIB_EXP:

?C: This symbol contains the ~name expanded version of SITELIB, to be used

?C: in programs that are not prepared to deal with ~ expansion at run-time.

?C:.

?C:SITELIB_STEM:

?C: This define is SITELIB_EXP with any trailing version-specific component

?C: removed. The elements in

inc_version_list (inc_version_list.U) can

?C: be tacked onto this variable to generate a list of directories to search.

?C:.

?H:#define SITELIB "\$sitelib" /**/

?H:#define SITELIB_EXP "\$sitelibexp" /**/

?H:#define SITELIB_STEM "\$sitelib_stem" /**/

?H:.

?T:prog

?LINT:change prefixvar

?LINT:set installsitelib

?LINT:set sitelib

?LINT:set sitelibexp

: determine where site specific libraries go.

: Usual default is /usr/local/lib/perl5/site_perl/\$version

: The default "style" setting is made in installstyle.U

: XXX No longer works with Prefixit stuff.

?X: remove any trailing -3.0 or other version identification

```
prog=`echo $package | $sed 's/-[0-9.]*$//`
case "$sitelib" in
") case "$installstyle" in
*lib/perl5*) dflt=$siteprefix/lib/$package/site_$prog/$version ;;
*) dflt=$siteprefix/lib/site_$prog/$version ;;
esac
```

```

;;
*) dflt="$sitelib"
;;
esac
$cat <<EOM

```

The installation process will create a directory for site-specific extensions and modules. Most users find it convenient to place all site-specific files in this directory rather than in the main distribution directory.

```

EOM
fn=d~+
rp='Pathname for the site-specific library files?'
./getfile
prefixvar=sitelib
./setprefixvar
sitelib_stem=`echo "$sitelibexp" | sed "s,/$version$,,"`

```

Found in path(s):

```

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/installdirs/sitelib.U

```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_getservbyname_r.U,v 0RCS:

?RCS: Copyright (c) 2002,2003 Jarkko Hietaniemi

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?RCS: Generated by the reentr.pl from the Perl 5.8 distribution.

?RCS:

?MAKE:d_getservbyname_r getservbyname_r_proto: Inlibc Protochk Hasproto \

i_systypes usethreads i_netdb extern_C

?MAKE: -pick add \$@ %<

?S:d_getservbyname_r:

?S: This variable conditionally defines the HAS_GETSERVBYNAME_R symbol,

?S: which indicates to the C program that the getservbyname_r()

?S: routine is available.

?S:.

?S:getservbyname_r_proto:

?S: This variable encodes the prototype of getservbyname_r.

?S: It is zero if d_getservbyname_r is undef, and one of the

?S: REENTRANT_PROTO_T_ABC macros of reentr.h if d_getservbyname_r

?S: is defined.

?S:.

?C:HAS_GETSERVBYNAME_R:

```

?C: This symbol, if defined, indicates
that the getservbyname_r routine
?C: is available to getservbyname re-entrantly.
?C:.
?C:GETSERVBYNAME_R_PROTO:
?C: This symbol encodes the prototype of getservbyname_r.
?C: It is zero if d_getservbyname_r is undef, and one of the
?C: REENTRANT_PROTO_T_ABC macros of reentr.h if d_getservbyname_r
?C: is defined.
?C:.
?H:#$d_getservbyname_r HAS_GETSERVBYNAME_R  /**/
?H:#define GETSERVBYNAME_R_PROTO $getservbyname_r_proto  /**/
?H:.
?T:try hdrs d_getservbyname_r_proto
: see if getservbyname_r exists
set getservbyname_r d_getservbyname_r
eval $inlibc
case "$d_getservbyname_r" in
"$define")
hdrs="$i_systypes sys/types.h define stdio.h $i_netdb netdb.h"
case "$d_getservbyname_r_proto:$usetthreads" in
":define") d_getservbyname_r_proto=define
set d_getservbyname_r_proto getservbyname_r $hdrs
eval $hasproto ;;
*) ;;
esac
case "$d_getservbyname_r_proto" in
define)
case "$getservbyname_r_proto" in
"|0) try='int getservbyname_r(const char*, const char*, struct servent*,
char*, size_t, struct servent**);'
./protochk "$extern_C $try" $hdrs && getservbyname_r_proto=I_CCBSWR ;;
esac
case "$getservbyname_r_proto" in
"|0) try='struct servent* getservbyname_r(const char*, const char*, struct servent*, char*, int);'
./protochk "$extern_C $try" $hdrs && getservbyname_r_proto=S_CCBSBI ;;
esac
case "$getservbyname_r_proto" in
"|0) try='int getservbyname_r(const char*, const char*, struct servent*, struct servent_data*);'
./protochk "$extern_C $try" $hdrs && getservbyname_r_proto=I_CCSD ;;
esac
case "$getservbyname_r_proto" in
"|0) d_getservbyname_r=undef
getservbyname_r_proto=0
echo "Disabling getservbyname_r, cannot determine prototype." >&4 ;;
*) case "$getservbyname_r_proto" in
REENTRANT_PROTO*) ;;
*) getservbyname_r_proto="REENTRANT_PROTO_$getservbyname_r_proto" ;;

```

```

esac
echo "Prototype: $try" ;;
esac
;;
*) case "$usetreads" in
define) echo "getservbyname_r has no prototype, not using it." >&4 ;;
esac
d_getservbyname_r=undef
getservbyname_r_proto=0
;;
esac
;;
*) getservbyname_r_proto=0
;;
esac

```

Found

in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/threads/d_getservbyname_r.U
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_closedir.U,v 3.0.1.3 1997/02/28 15:31:26 ram Exp \$

?RCS:

?RCS: Copyright (c) 1991-1993, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 3.0.

?RCS:

?RCS: Original Author: Andy Dougherty <doughera@lafcol.lafayette.edu>

?RCS:

?RCS: \$Log: d_closedir.U,v \$

?RCS: Revision 3.0.1.3 1997/02/28 15:31:26 ram

?RCS: patch61: added ?F: metalint hint

?RCS:

?RCS: Revision 3.0.1.2 1994/10/29 16:11:18 ram

?RCS: patch36: added 'ldflags' to the test compile line (ADO)

?RCS:

?RCS: Revision 3.0.1.1 1994/08/29 16:07:21 ram

?RCS: patch32: created by ADO

?RCS:

?MAKE:d_closedir d_void_closedir: Inlibc i_dirent i_sysdir i_sysndir

\

i_systypes Compile Setvar rm_try run

?MAKE: -pick add \$@ %<

?S:d_closedir:
?S: This variable conditionally defines HAS_CLOSEDIR if closedir() is
?S: available.
?S:.
?C:HAS_CLOSEDIR:
?C: This symbol, if defined, indicates that the closedir() routine is
?C: available.
?C:.
?H:#\$d_closedir HAS_CLOSEDIR /**/
?H:.
?S:d_void_closedir:
?S: This variable conditionally defines VOID_CLOSEDIR if closedir()
?S: does not return a value.
?S:.
?C:VOID_CLOSEDIR:
?C: This symbol, if defined, indicates that the closedir() routine
?C: does not return a value.
?C:.
?H:#\$d_void_closedir VOID_CLOSEDIR /**/
?H:.
?F:!try
?LINT:set d_closedir d_void_closedir
: see if closedir exists
set closedir d_closedir
eval \$inlibc

@if VOID_CLOSEDIR || d_void_closedir
?X: The following contortions are designed so we can call closedir()
?X: and check whether it returns a value. The contortions are designed
?X: to portably pick up the correct directory header, for those
?X: systems that support various mutually incompatible
directory functions.
?X: This is from perl5's perl.h
case "\$d_closedir" in
"\$define")
echo " "
echo "Checking whether closedir() returns a status..." >&4
cat > try.c <<EOM
#\$i_dirent I_DIRENT /**/
#\$i_sysdir I_SYS_DIR /**/
#\$i_sysndir I_SYS_NDIR /**/
#\$i_systypes I_SYS_TYPES /**/

#if defined(I_SYS_TYPES)
#include <sys/types.h>
#endif
#if defined(I_DIRENT)
#include <dirent.h>

```

#else
#ifdef I_SYS_NDIR
#include <sys/ndir.h>
#else
#ifdef I_SYS_DIR
#ifdef hp9000s500
#include <ndir.h> /* may be wrong in the future */
#else
#include <sys/dir.h>
#endif
#endif
#endif
#endif
int main() { return closedir(opendir(".")); }
EOM
set try
if eval $compile_ok; then
if $run ./try > /dev/null 2>&1 ; then
echo "Yes, it does."
val="$undef"
else
echo "No, it doesn't."
val="$define"
fi
else
echo "(I can't seem to compile the test program--assuming it doesn't)"
val="$define"
fi
;;
*)
val="$undef";
;;
esac
set d_void_closedir
eval $setvar
$rm_try
@end

```

Found in path(s):

*

/opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/compline/d_closedir.U

No license file was found, but licenses were detected in source scan.

You may redistribute only under the terms of the Artistic Licence,

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-

debian-perl-5.26.1/dist/lib/errnolist.mk

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-

debian-perl-5.26.1/dist/bindex

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-

debian-perl-5.26.1/dist/makegloss

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-

debian-perl-5.26.1/dist/files/fixcpp

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: Protochk.U,v \$

?RCS:

?RCS: Copyright (c) 1998 Andy Dougherty

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?X: This unit generates a ./protochk script that is used internally

?X: by Configure to check if this system will accept a particular

?X: prototype.

?X:

?X: To use it, say something like:

?X: hdrs="\$define sys/types.h

?X: \$i_systime sys/time.h

?X: \$i_sysselect sys/select.h

?X: \$d_socket sys/socket.h"

?X: \$xxx='fd_set *'

?X: try='extern int select _((int, \$xxx, \$xxx, \$xxx, struct timeval *));'

?X: if ./protochk "\$try" \$hdrs; then

?X: echo "Your system accepts \$xxx for the arguments to select."

?X: fi

?X: (Of course select is harder, since the first arg can be int,

?X: size_t, or unsigned long, and the last arg may or may not have a

?X: 'const' before the 'struct timeval' :-(. Also SunOS

4.1.3 doesn't

?X: provide a select prototype so the compiler accepts anything :-).

?X:

?X: The C compiler on QNX warns about invalid pointer types, but

?X: still exits with a 0 exit status, so it's not much help here.

?X: (It does correctly detect incorrect non-pointer arguments).

?X: Still, since QNX is a POSIX-ish system, just make your first

?X: a POSIX-ish one, and QNX will probably accept it.

?X:

?X: For determining argument types, your compiler must support

?X: prototypes, and the header files must use them. Determining

?X: return types, however, is easier. Just give an ridiculous

?X: return type, something like

?X: ./protochk 'extern int atof _((void));' \$i_stdlib stdlib.h

?X: that should surely fail if atof() is defined in <stdlib.h>

?X:
 ?X: There is also an 'escape' hatch built in. If you have a pair
 ?X: of args 'literal 'stuff' then 'stuff' gets included literally
 ?X: into the test program. This could be useful for doing something
 ?X: like
 ?X: hdrs="\$define stdio.h
 ?X: \$define
 sys/types.h"
 ?X: ./protochk 'extern int fsetpos(FILE *, Fpos_t);' \$args \
 ?X: 'literal' '#define Fpos_t long long'
 ?X: but you have to be really careful about the spaces in "literal".
 ?X:
 ?X: Andy Dougherty Feb. 1998
 ?MAKE:Protochk: cat rm_try startsh eunicefix +cc +optimize +ccflags \
 prototype i_thread usethreads
 ?MAKE: -pick add \$@ %<
 ?F:./protochk
 ?X: Comfort metalint. All these are actually used in the protochk script.
 ?T:foo status pthread_h_done
 ?LINT: change cc optimize ccflags prototype define rm_try
 ?LINT: extern pthread_h_first
 ?LINT: change pthread_h_first
 ?LINT: change usethreads
 ?LINT: change i_thread
 : define a function to check prototypes
 \$cat > protochk <<EOSH
 \$startsh
 cc="\$cc"
 optimize="\$optimize"
 ccflags="\$ccflags"
 prototype="\$prototype"
 define="\$define"
 rm_try="\$rm_try"
 usethreads=\$usethreads
 i_thread=\$i_thread
 pthread_h_first=\$pthread_h_first
 EOSH

 \$cat >> protochk <<'EOSH'

 \$rm_try
 foo="\$1"
 shift
 while test \$# -ge 2; do
 case "\$1" in
 \$define)
 echo "#include <\$2>" >> try.c ;;
 literal) echo "\$2" >> try.c ;;

```

esac
# Extra magic for the benefit of systems that need pthread.h
# to be included early to correctly detect threadsafe functions.
# Such functions must guarantee themselves, though, that the usethreads
# and i_pthread have been defined, before calling protochk.
if test "$usethreads" = "$define" -a "$i_pthread" = "$define" -a "$pthread_h_first" = "$define" -a
"$pthread_h_done" = ""; then
echo "#include <pthread.h>" >> try.c
pthread_h_done=yes
fi
shift 2
done
test "$prototype" = "$define" && echo '#define CAN_PROTOTYPE' >> try.c
cat >> try.c <<'EOCP'
#ifdef CAN_PROTOTYPE
#define _(args) args
#else
#define _(args) ()
#endif
EOCP
echo "$foo" >> try.c
?X: Just so we have something to compile.
echo 'int no_real_function_has_this_name _((void)) { return 0; }' >> try.c
$cc $optimize $ccflags -c try.c > /dev/null 2>&1
status=$?
$rm_try
exit $status
EOSH
chmod +x protochk
$unicefix protochk

```

Found

in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/protos/Protochk.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: vendorman1.U,v 1.1 1999/07/08 18:32:57 doughera Exp doughera \$

?RCS:

?RCS: Copyright (c) 1999, Andy Dougherty

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 3.0.

?RCS:

?RCS: \$Log: vendorman1.U,v \$

```

?RCS: Revision 1.1 1999/07/08 18:32:57 doughera
?RCS: Initial revision
?RCS:
?MAKE:vendorman1 vendorman1exp installvendorman1: man1dir Getfile \
  Oldconfig Setprefixvar Prefixit test vendorprefix prefix sed
?MAKE: -pick add $@ %<
?Y:TOP
?S:vendorman1:
?S: This variable contains the name of the directory for man1
?S: pages. It may have a ~ on the front.
?S: The standard distribution will put nothing in this directory.
?S: Vendors who
  distribute perl may wish to place their own
?S: man1 pages in this directory with
?S: MakeMaker Makefile.PL INSTALLDIRS=vendor
?S: or equivalent. See INSTALL for details.
?S:.
?S:vendorman1exp:
?S: This variable is the ~name expanded version of vendorman1, so that you
?S: may use it directly in Makefiles or shell scripts.
?S:.
?D:installvendorman1="
?S:installvendorman1:
?S: This variable is really the same as vendorman1exp but may differ on
?S: those systems using AFS. For extra portability, only this variable
?S: should be used in makefiles.
?S:.
?LINT:change prefixvar
?LINT:set installvendorman1
: Set the vendorman1 variables
case "$vendorprefix" in
  ") vendorman1="
  vendorman1exp="
  ;;
  *) : determine where vendor-supplied manual pages go.
  case "$vendorman1" in
    ") dflt=`echo "$man1dir" | $sed "s#^$prefix#$vendorprefix#" ` ;;
    *) dflt=$vendorman1 ;;
  esac
  case "$dflt" in
    "|" ) dflt=none ;;
  esac
  fn=nd~+
  rp='Pathname for the vendor-supplied manual section 1 pages?'
  .
  ./getfile
  vendorman1="$ans"
  vendorman1exp="$ansexp"

```

```
;;
esac
: Use ' ' for none so value is preserved next time through Configure
$test X"$vendorman1" = "X" && vendorman1=' '
prefixvar=vendorman1
./installprefix
```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/installdirs/vendorman1.U
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: i_poll.U,v \$

?RCS:

?RCS: Copyright (c) 2001 Jarkko Hietaniemi

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?MAKE:i_langinfo: Inhdr Hasfield

?MAKE: -pick add \$@ %<

?S:i_langinfo:

?S: This variable conditionally defines the I_LANGINFO symbol,

?S: and indicates whether a C program should include <langinfo.h>.

?S:.

?C:I_LANGINFO:

?C: This symbol, if defined, indicates that <langinfo.h> exists and

?C: should be included.

?C:.

?H:#\$i_langinfo I_LANGINFO /**/

?H:.

?LINT:set i_langinfo

: see if this is a langinfo.h system

set langinfo.h i_langinfo

eval \$inhdr

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/perl/i_langinfo.U
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 2004 H.Merijn Brand

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?MAKE:d_strlcat: Inlibc
?MAKE: -pick add \$@ %<
?S:d_strlcat:
?S: This variable conditionally defines the HAS_STRLCAT symbol, which
?S: indicates to the C program that the strlcat () routine is available.
?S:.
?C:HAS_STRLCAT:
?C: This symbol, if defined, indicates that the strlcat () routine is
?C: available to do string concatenation.
?C:.
?H:#\$d_strlcat HAS_STRLCAT /**/
?H:.
?LINT:set d_strlcat
: see if strlcat exists
set strlcat d_strlcat
eval \$inlibc

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_strlcat.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: \$Log: i_sysun.U,v \$
?RCS: Revision 3.0 1993/08/18 12:08:42 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?X:
?X: This unit looks wether <inttypes.h> is available or not
?X:
?MAKE:i_inttypes: Inhdr
?MAKE: -pick add \$@ %<
?S:i_inttypes:
?S: This variable conditionally defines I_INTTYPES, which indicates
?S: to the C program that it should include <inttypes.h> to get
?S: format conversions of integer types.
?S:.
?C:I_INTTYPES:
?C: This symbol, if defined, indicates to the C program that it should

```
?C: include
<inttypes.h> to get format conversions of integer types.
?C:.
?H:#$i_inttypes I_INTTYPES /**/
?H:.
?LINT:set i_inttypes
: see if this is a inttypes.h system
set inttypes.h i_inttypes
eval $inhdr
```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/i_inttypes.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: d_wifstat.U,v 3.0.1.3 1997/02/28 15:47:43 ram Exp $
?RCS:
?RCS: Copyright (c) 1991-1993, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 3.0.
?RCS:
?RCS: $Log: d_wifstat.U,v $
?RCS: Revision 3.0.1.3 1997/02/28 15:47:43 ram
?RCS: patch61: added a ?F: metalint hint
?RCS:
?RCS: Revision 3.0.1.2 1995/07/25 14:09:10 ram
?RCS: patch56: re-arranged compile line to include ldflags before objects
?RCS:
?RCS: Revision 3.0.1.1 1995/03/21 08:47:46 ram
?RCS: patch52: created
?RCS:
?MAKE:d_wifstat: Compile d_uwait Oldconfig cat rm
?MAKE: -pick add $@ %<
?S:d_wifstat:
?S: This symbol conditionally defines USE_WIFSTAT
if the C program can
?S: safely use the WIFxxx macros with the kind of wait() parameter
?S: declared in the program (see UNION_WAIT), or if it can't. Should
?S: only matter on HP-UX, where the macros are incorrectly written and
?S: therefore cause programs using them with an 'union wait' variable
?S: to not compile properly.
?S:.
?C:USE_WIFSTAT:
?C: This symbol, if defined, indicates to the C program that the argument
```

?C: for the WIFxxx set of macros such as WIFSIGNALED or WIFEXITED can
?C: be of the same kind as the one used to hold the wait() status. Should
?C: only matter on HP-UX, where the macros are incorrectly written and
?C: therefore cause programs using them with an 'union wait' variable
?C: to not compile properly. See also UNION_WAIT.

?C:.

```
?H:#$d_wifstat USE_WIFSTAT /**/
```

?H:.

?T:type

?F:!foo

: see if we can use WIFxxx macros

```
echo " "
```

```
case "$d_wifstat" in
```

```
"$define") echo "As before, you can safely use WIFEXITED and friends!" >&4;;
```

```
"$undef") echo "You still can't use WIFEXITED
```

```
and friends!" >&4;;
```

```
*)
```

```
echo "Let's see whether you can use the WIFEXITED(status) macro and its"
```

```
case "$d_uwait" in
```

```
"$define") type='union wait';;
```

```
*) type='int';;
```

```
esac
```

```
echo "friends with status declared as '$type status'..."
```

```
$cat >foo.c <<EOCP
```

```
#include <sys/types.h>
```

```
#include <sys/wait.h>
```

```
int main()
```

```
{
```

```
    $type status;
```

```
    int e = 0;
```

```
#ifdef WIFEXITED
```

```
    if (WIFEXITED(status))
```

```
        printf("\n");
```

```
        exit(0);
```

```
#else
```

```
    exit(2);
```

```
#endif
```

```
}
```

```
EOCP
```

```
d_wifstat="$undef"
```

```
set foo
```

```
if eval $compile; then
```

```
    if ./foo >/dev/null; then
```

```
        echo "Great! Looks like we can use the WIFxxx macros." >&4
```

```
        d_wifstat="$define"
```

```
    else
```

```

    echo "You don't seem to have WIFxxx macros, but that's ok." >&4
fi
else
    echo "Apparently you can't use WIFxxx macros properly." >&4
fi
$rm -f foo.* foo core
;;
esac

```

Found in path(s):

```

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/compline/d_wifstat.U

```

No license file was found, but licenses were detected in source scan.

```

?RCS: $Id: d_sethent.U,v 3.0 1993/08/18 12:06:09 ram Exp $
?RCS:
?RCS: Copyright (c) 1991-1993, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 3.0.
?RCS:
?RCS: $Log: d_sethent.U,v $
?RCS: Revision 3.0 1993/08/18 12:06:09 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:d_sethent: Inlibc
?MAKE: -pick add $@ %<
?S:d_sethent:
?S: This variable conditionally defines HAS_SETHOSTENT if sethostent() is
?S: available.
?S:.
?C:HAS_SETHOSTENT:
?C: This symbol, if defined, indicates that the sethostent() routine is
?C: available.
?C:.
?H:#$d_sethent HAS_SETHOSTENT /**/
?H:.
?LINT:set d_sethent
: see if sethostent exists
set
    sethostent d_sethent
eval $inlibc

```

Found in path(s):

```

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-

```

debian-perl-5.26.1/U/modified/d_sethenth.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: mallocsrc.U,v 3.0.1.2 1997/02/28 16:10:26 ram Exp \$
?RCS:
?RCS: Copyright (c) 1991-1993, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 3.0.
?RCS:
?RCS: \$Log: mallocsrc.U,v \$
?RCS: Revision 3.0.1.2 1997/02/28 16:10:26 ram
?RCS: patch61: added support for Free_t, the type of free()
?RCS: patch61: replaced .o with \$_o all over the place
?RCS:
?RCS: Revision 3.0.1.1 1994/05/06 15:10:46 ram
?RCS: patch23: added support for MYMALLOC, mainly for perl5 (ADO)
?RCS:
?RCS: Revision 3.0 1993/08/18 12:09:12 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:mallocsrc mallocobj usemallocwrap usemymalloc
malloctype d_mymalloc \
freetype: Myread \
Oldconfig package Guess Setvar rm cat +cc +ccflags Findhdr \
i_malloc i_stdlib sed libs _o ptrsize useithreads
?MAKE: -pick add \$@ %<
?X: Put near top so that other tests don't erroneously include
?X: -lmalloc. --AD 22 June 1998
?Y:TOP
?S:usemymalloc:
?S: This variable contains y if the malloc that comes with this package
?S: is desired over the system's version of malloc. People often include
?S: special versions of malloc for efficiency, but such versions are often
?S: less portable. See also mallocsrc and mallocobj.
?S: If this is 'y', then -lmalloc is removed from \$libs.
?S:.
?S:usemallocwrap:
?S: This variable contains y if we are wrapping malloc to prevent
?S: integer overflow during size calculations.
?S:.
?S:mallocsrc:
?S: This variable contains the name of the malloc.c that comes with
?S: the package, if that malloc.c is preferred over the system malloc.
?S: Otherwise the value is null. This variable is intended for generating

?S: Makefiles.

?S:.

?S:d_mymalloc:

?S: This variable conditionally defines MYMALLOC in case other parts of the source want to take special action if MYMALLOC is used.

?S: This may include different sorts of profiling or error detection.

?S:.

?S:mallocobj:

?S: This variable contains the name of the malloc.o that this package generates, if that malloc.o is preferred over the system malloc.

?S: Otherwise the value is null. This variable is intended for generating Makefiles. See mallocsrc.

?S:.

?S:freetype:

?S: This variable contains the return type of free(). It is usually void, but occasionally int.

?S:.

?S:malloctype:

?S: This variable contains the kind of ptr returned by malloc and realloc.

?S:.

?C:Free_t:

?C: This variable contains the return type of free(). It is usually void, but occasionally int.

?C:.

?C:Malloc_t (MALLOC_PTRTYPE):

?C: This symbol is the type of pointer returned by malloc and realloc.

?C:.

?H:#define Malloc_t \$malloctype /**/

?H:#define Free_t \$freetype /**/

?H:.

?C:PERL_MALLOC_WRAP:

?C: This symbol, if defined, indicates that we'd like malloc wrap checks.

?C:.

?H:#\$usemallocwrap PERL_MALLOC_WRAP /**/

?H:.

?C:MYMALLOC:

?C: This symbol, if defined, indicates that we're using our own malloc.

?C:.

?H:#\$d_mymalloc MYMALLOC /**/

?H:.

?LINT:extern usedevel

?LINT:change libs

?X: Cannot test for mallocsrc; it is the unit's name and there is a bug in the interpreter which defines all the names, even though they are not used.

@if mallocobj

: determine whether to use malloc wrapping

```

echo " "
case "$usemallocwrap" in
[yY]*|true|$define) dflt='y' ;;
[nN]*|false|$undef) dflt='n' ;;
*) case "$usedevel" in
[yY]*|true|$define) dflt='y' ;;
*) dflt='n' ;;
esac
;;
esac
rp="Do you wish to wrap malloc calls to protect against potential overflows?"
./myread
usemallocwrap="$ans"
case "$ans" in
y*|true)
usemallocwrap="$define" ;;
*)
usemallocwrap="$undef" ;;
esac

```

: determine which malloc to compile in

```

echo " "
case "$usemymalloc"
in
[yY]*|true|$define) dflt='y' ;;
[nN]*|false|$undef) dflt='n' ;;
*) case "$ptrsize" in
4) dflt='y' ;;
*) dflt='n' ;;
esac
if test "$useithreads" = "$define"; then dflt='n'; fi
;;
esac
rp="Do you wish to attempt to use the malloc that comes with $package?"
./myread
usemymalloc="$ans"
case "$ans" in
y*|true)
usemymalloc='y'
mallosrc='malloc.c'
mallocobj="malloc$_o"
d_mymalloc="$define"
?X: Maybe libs.U should be dependent on mallosrc.U, but then
?X: most packages that use dist probably don't supply their own
?X: malloc, so this is probably an o.k. compromise
case "$libs" in
*-lmalloc*)
: Remove malloc from list of libraries to use

```

```

echo "Removing unneeded -lmalloc from library list" >&4
set `echo X $libs | $sed -e 's/-lmalloc / /' -e 's/-lmalloc$//`
shift
libs="$*"
echo "libs = $libs" >&4
;;
esac
;;
*)
usemymalloc='n'
malloclsrc=""
malloclobj=""
d_mymalloc="$undef"
;;
esac

@end
@if MALLOC_PTRTYPE || Malloc_t || Free_t
: compute the return types of
malloc and free
echo " "
$cat >malloc.c <<END
#$i_malloc I_MALLOC
#$i_stdlib I_STDLIB
#include <stdio.h>
#include <sys/types.h>
#ifdef I_MALLOC
#include <malloc.h>
#endif
#ifdef I_STDLIB
#include <stdlib.h>
#endif
#ifdef TRY_MALLOC
void *malloc();
#endif
#ifdef TRY_FREE
void free();
#endif
END
@if MALLOC_PTRTYPE || Malloc_t
case "$malloctype" in
")
if $cc $cflags -c -DTRY_MALLOC malloc.c >/dev/null 2>&1; then
malloctype='void *'
else
malloctype='char *'
fi
;;

```

```

esac
echo "Your system wants malloc to return '$malloctype', it would seem." >&4
@end

@if Free_t
case "$freetype" in
")
if $cc $ccflags -c -DTRY_FREE malloc.c >/dev/null 2>&1; then
freetype='void'
else
freetype='int'
fi
;;
esac
echo "Your system uses $freetype free(), it would seem." >&4
@end
$rm -f malloc.[co]
@end

```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/modified/mallocsrc.U
```

No license file was found, but licenses were detected in source scan.

```

?RCS: $Id: d_strcspn.U 1 2006-08-24 12:32:52Z rmanfredi $
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: $Log: d_strcspn.U,v $
?RCS: Revision 3.0 1993/08/18 12:07:33 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:d_strcspn: Inlibc
?MAKE: -pick add $@ %<
?S:d_strcspn:
?S: This variable conditionally defines the HAS_STRCSPN symbol, which
?S: indicates to the C program that the strcspn() routine is available
?S: to scan strings.
?S:.
?C:HAS_STRCSPN (STRCSPN):
?C: This symbol, if defined, indicates that the strcspn routine is
?C: available to scan

```

```
strings.  
?C:.  
?H:#$d_strcspn HAS_STRCSPN /**/  
?H:.  
?LINT:set d_strcspn  
: see if strcspn exists  
set strcspn d_strcspn  
eval $inlibc
```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/d_strcspn.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id$  
?RCS:  
?RCS: Copyright (c) 1999 Jarkko Hietaniemi  
?RCS:  
?RCS: You may redistribute only under the terms of the Artistic License,  
?RCS: as specified in the README file that comes with the distribution.  
?RCS: You may reuse parts of this distribution only within the terms of  
?RCS: that same Artistic License; a copy of which may be found at the root  
?RCS: of the source tree for dist 3.0.  
?RCS:  
?MAKE:d_telldirproto: Hasproto i_systypes i_dirent  
?MAKE: -pick add $@ %<  
?S:d_telldirproto:  
?S: This variable conditionally defines the HAS_TELLDIR_PROTO symbol,  
?S: which indicates to the C program that the system provides  
?S: a prototype for the telldir() function. Otherwise, it is  
?S: up to the program to supply one.  
?S:.  
?C:HAS_TELLDIR_PROTO:  
?C: This symbol, if defined, indicates that the system provides  
?C: a prototype for the telldir() function. Otherwise, it is up  
?C: to the program to supply one. A good guess  
is  
?C: extern long telldir(DIR*);  
?C:.  
?H:#$d_telldirproto HAS_TELLDIR_PROTO /**/  
?H:.  
?LINT:set d_telldirproto  
: see if prototype for telldir is available  
echo " "  
set d_telldirproto telldir $i_systypes sys/types.h $i_dirent dirent.h  
eval $hasproto
```

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_telldirproto.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: d_gethent.U,v \$

?RCS: Revision 3.0 1993/08/18 12:06:09 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?MAKE:d_gethent: Inlibc

?MAKE: -pick add \$@ %<

?S:d_gethent:

?S: This variable conditionally defines HAS_GETHOSTENT if gethostent() is

?S: available to dup file descriptors.

?S:.

?C:HAS_GETHOSTENT (GETHOSTENT):

?C: This symbol, if defined, indicates that the gethostent routine is

?C: available to lookup host names in some data base or other.

?C:.

?H:#\$d_gethent HAS_GETHOSTENT /**/

?H:.

?LINT:set

d_gethent

: see if gethostent exists

set gethostent d_gethent

eval \$inlibc

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/d_gethent.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: Options.U 1 2006-08-24 12:32:52Z rmanfredi \$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root
 ?RCS: of the source tree for dist 4.0.
 ?RCS:
 ?RCS: \$Log: Options.U,v \$
 ?RCS: Revision 3.0.1.7 1997/02/28 15:08:15 ram
 ?RCS: patch61: optdef.sh now starts with a "startsh"
 ?RCS: patch61: moved some code from Head.U
 ?RCS:
 ?RCS: Revision 3.0.1.6 1995/09/25 09:14:46 ram
 ?RCS: patch59: protected option parsing code against 'echo -*' option failure
 ?RCS:
 ?RCS: Revision 3.0.1.5 1995/05/12 12:04:52 ram
 ?RCS: patch54: added -K option for experts
 ?RCS:
 ?RCS: Revision 3.0.1.4 1995/01/30 14:27:52 ram
 ?RCS:
 patch49: this unit now exports file optdef.sh, not a variable
 ?RCS:
 ?RCS: Revision 3.0.1.3 1995/01/11 15:19:00 ram
 ?RCS: patch45: new -O option allowing -D and -U to override config.sh settings
 ?RCS: patch45: file optdef.sh is no longer removed after sourcing
 ?RCS:
 ?RCS: Revision 3.0.1.2 1994/10/29 15:58:06 ram
 ?RCS: patch36: ensure option definition file is removed before appending
 ?RCS: patch36: protect variable definitions with spaces in them
 ?RCS:
 ?RCS: Revision 3.0.1.1 1994/06/20 06:55:44 ram
 ?RCS: patch30: now uses new me symbol to tag error messages
 ?RCS: patch30: new -D and -U options to define/undef symbols (JHI)
 ?RCS:
 ?RCS: Revision 3.0 1993/08/18 12:05:14 ram
 ?RCS: Baseline for dist 3.0 netwide release.
 ?RCS:
 ?X:
 ?X: Command line parsing. It is really important that the variables used here
 ?X: be not listed in the MAKE line, or they will be saved in config.sh and
 ?X: loading this file to fetch default answers would clobber the values set
 ?X: herein.
 ?X:
 ?MAKE:Options:
 startsh
 ?MAKE: -pick wipe \$@ %<
 ?V:reuseval alldone error realsilent silent extractsh fastread \
 knowitall: config_sh
 ?T:arg argn symbol config_arg0 config_args config_argc xxx yyy zzz uuu
 ?T:args_exp args_sep arg_exp ccflags
 ?F:!Configure
 ?F:./optdef.sh ./cmdline.opt ./posthint.sh ./cmdl.opt

```

: Save command line options in file UU/cmdline.opt for later use in
: generating config.sh.
?X: This temporary file will be read by Oldsym.U. I used a temporary
?X: file to preserve all sorts of potential command line quotes and
?X: also because we don't know in advance how many variables we'll
?X: need, so I can't actually declare them on the MAKE line.
?X: The config_args variable won't be quite correct if Configure is
?X: fed something like ./Configure -Dcc="gcc -B/usr/ccs/bin/"
?X: since the quotes are gone by the time we see them. You'd have to
?X: reconstruct the command line from the config_arg? lines, but since
?X: I don't imagine anyone actually having to do that, I'm not going
?X:
to worry too much.
cat > cmdline.opt <<EOSH
: Configure command line arguments.
config_arg0='$0'
config_args='$*'
config_argc=$#
EOSH
argn=1
args_exp=""
args_sep=""
for arg in "$@"; do
cat >>cmdline.opt <<EOSH
config_arg$argn='$arg'
EOSH
?X: Extreme backslashitis: replace each ' by """"
cat <<EOC | sed -e "s/'/""""/g" > cmdl.opt
$arg
EOC
arg_exp=`cat cmdl.opt`
args_exp="$args_exp$args_sep'$arg_exp'"
argn=`expr $argn + 1`
args_sep=' '
done
?X: args_exp is good for restarting self: eval "set X $args_exp"; shift; $0 "$@"
?X: used by hints/os2.sh in Perl, for instance
rm -f cmdl.opt

```

```

: produce awk script to parse command line options
cat >options.awk <<'EOF'
BEGIN {
optstr = "A:dD:eEf:hKOrsSU:V"; # getopt-style specification

len = length(optstr);
for (i = 1; i <= len; i++) {
c = substr(optstr, i, 1);
?X: some older awk's do not have the C ?: construct

```

```

if (i < len) a = substr(optstr, i + 1, 1); else a = "";
if (a == ":") {
    arg[c] = 1;
    i++;
}
opt[c]
= 1;
}
}
{
    expect = 0;
    str = $0;
    if (substr(str, 1, 1) != "-") {
        printf("%s\n", str);
        next;
    }
    len = length($0);
    for (i = 2; i <= len; i++) {
        c = substr(str, i, 1);
        if (!opt[c]) {
            printf("-%s\n", substr(str, i));
            next;
        }
        printf("-%s\n", c);
        if (arg[c]) {
            if (i < len)
                printf("%s\n", substr(str, i + 1));
            else
                expect = 1;
            next;
        }
    }
}
END {
    if (expect)
        print "?";
}
EOF

```

: process the command line options

?X: Use "\$@" to keep arguments with spaces in them from being split apart.

?X: For the same reason, awk will output quoted arguments and the final eval

?X: removes them and sets a proper \$* array. An 'X' is prepended to each

?X: argument before being fed to echo to guard against 'echo -x', where -x

?X: would be understood as an echo option! It is removed before feeding awk.

```
set X `for arg in "$@"; do echo "X$arg"; done |
```

```
sed -e s/X// | awk -f options.awk`
```

```
eval "set $*"
```

```

shift
rm -f options.awk

: set up default values
fastread=""
reuseval=false
config_sh=""
alldone=""
error=""
silent=""
extractsh=""
knowitall=""
rm
-f optdef.sh posthint.sh
cat >optdef.sh <<EOS
$startsh
EOS

```

?X:

?X: Given that we now have the possibility to execute Configure remotely
?X: thanks to the new src.U support, we have to face the possibility
?X: of having to ask where the source lie, which means we need the Myread.U
?X: stuff and possibly other things that might echo something on the
?X: screen...

?X:

?X: That's not pretty, and might be confusing in 99% of the time. So...
?X: We introduce a new realsilent variable which is set when -s is given,
?X: and we force silent=true if -S is supplied. The Extractall.U unit
?X: will then undo the >&4 redirection based on the value of the
?X: realsilent variable... -- RAM, 18/93/96

?X:

```

: option parsing
while test $# -gt 0; do
case "$1" in
-d) shift; fastread=yes;;
-e) shift; alldone=cont;;
-f)
shift
cd ..
if test -r "$1"; then
config_sh="$1"
else
echo "$me: cannot read config file $1."
>&2
error=true
fi
cd UU

```

```

shift;;
--help\
-h) shift; error=true;;
-r) shift; reuseval=true;;
-s) shift; silent=true; realsilent=true;;
-E) shift; alldone=exit;;
-K) shift; knowitall=true;;
-O) shift;;
-S) shift; silent=true; extractsh=true;;
-D)
shift
case "$1" in
*)
echo "$me: use '-U symbol=', not '-D symbol='." >&2
echo "$me: ignoring -D $1" >&2
;;
*=*) echo "$1" | \
sed -e "s/^\\""/g" -e "s/=(.*)/=\\1/" >> optdef.sh;;
*) echo "$1='define'" >> optdef.sh;;
esac
shift
;;
-U)
shift
case "$1" in
*) echo "$1" >> optdef.sh;;
*=*)
echo "$me: use '-D symbol=val', not '-U symbol=val'." >&2
echo "$me: ignoring -U $1" >&2
;;
*) echo "$1='undef'" >> optdef.sh;;
esac
shift
;;
-A)
shift
xxx=""
yyy="$1"
zzz=""
uuu=undef
case "$yyy" in
*=*) zzz=`echo "$yyy"|sed 's!=.*!!'^
case "$zzz" in
*:* ) zzz="" ;;
*) xxx=append

zzz="" ``echo "$yyy"|sed 's!^[^=]*=!!'^
yyy=`echo "$yyy"|sed 's!=.*!!'^` ;;

```

```

        esac
        ;;
    esac
    case "$xxx" in
    *) case "$yyy" in
        *.* ) xxx=`echo "$yyy"|sed 's!:.*!!'^
            yyy=`echo "$yyy"|sed 's!^[^:]*!!'^
            zzz=`echo "$yyy"|sed 's!^[^=]*!!'^
            yyy=`echo "$yyy"|sed 's!=.*!!'^ ;;
        *) xxx=`echo "$yyy"|sed 's!:.*!!'^
            yyy=`echo "$yyy"|sed 's!^[^:]*!!'^ ;;
        esac
        ;;
    esac
    case "$xxx" in
    append)
    echo "$yyy=\\"${yyy}$zzz\""" >> posthint.sh ;;
    clear)
    echo "$yyy="" >> posthint.sh ;;
    define)
        case "$zzz" in
        *) zzz=define ;;
        esac
        echo "$yyy='$zzz'" >> posthint.sh ;;
        eval)
        echo "eval \\"$yyy=$zzz\""" >> posthint.sh ;;
        prepend)
        echo "$yyy=\\"$zzz${yyy}\""" >> posthint.sh ;;
        undef)

        case "$zzz" in
        *) zzz="$uuu" ;;
        esac
        echo "$yyy=$zzz" >> posthint.sh ;;
        *) echo "$me: unknown -A command '$xxx', ignoring -A $1" >&2 ;;
        esac
        shift
        ;;
    -V) echo "$me generated by metaconfig <VERSION> PL<PATCHLEVEL>." >&2
        exit 0;;
    --) break;;
    -*) echo "$me: unknown option $1" >&2; shift; error=true;;
    *) break;;
    esac
done

case "$error" in
true)

```

cat >&2 <<EOM

Usage: \$me [-dehrsEKOSV] [-f config.sh] [-D symbol] [-D symbol=value]

[-U symbol] [-U symbol=] [-A command:symbol...]

-d : use defaults for all answers.

-e : go on without questioning past the production of config.sh.

-f : specify an alternate default configuration file.

-h : print this help message and exit (with an error status).

-r : reuse C symbols value if possible (skips costly nm extraction).

-s : silent mode, only echoes questions and essential information.

-D : define symbol to have some value:

-D symbol symbol gets the value

'define'

-D symbol=value symbol gets the value 'value'

common used examples (see INSTALL for more info):

-Duse64bitint use 64bit integers

-Duse64bitall use 64bit integers and pointers

-Dusetthreads use thread support

-Dinc_version_list=none do not include older perl trees in @INC

-DEBUGGING=none DEBUGGING options

-Dcc=gcc choose your compiler

-Dprefix=/opt/perl5 choose your destination

-E : stop at the end of questions, after having produced config.sh.

-K : do not use unless you know what you are doing.

-O : ignored for backward compatibility

-S : perform variable substitutions on all .SH files (can mix with -f)

-U : undefine symbol:

-U symbol symbol gets the value 'undef'

-U symbol= symbol gets completely empty

e.g.: -Uversiononly

-A : manipulate symbol after the platform specific hints have been applied:

-A append:symbol=value append value to symbol

-A symbol=value like append:, but with a separating space

-A define:symbol=value define symbol to have value

-A clear:symbol define symbol to be "

-A define:symbol define symbol to be 'define'

-A eval:symbol=value define symbol to be eval of value

-A prepend:symbol=value prepend value to symbol

-A undef:symbol define symbol to be 'undef'

-A undef:symbol= define symbol to be "

e.g.: -A prepend:libswanted='cl pthread '

-A ccflags=-DSOME_MACRO

-V : print version number and exit (with a zero status).

EOM

exit 1

::

esac

?X:

?X: Unless they specified either -S or both -d and -e/E, make sure we're
?X: running interactively, i.e. attached to a terminal. Moved from Head.U to
?X: be able to handle batch configurations...

?X:

?X: We have to hardwire the Configure name and cannot use \$me,
since if they

?X: said 'sh <Configure', then \$me is 'sh'...

?X:

: Sanity checks

```
case "$fastread$alldone" in
```

```
yescont|yesexit) ;;
```

```
*)
```

```
case "$extractsh" in
```

```
true) ;;
```

```
*)
```

```
if test ! -t 0; then
```

```
    echo "Say 'sh Configure', not 'sh <Configure'"
```

```
    exit 1
```

```
fi
```

```
::
```

```
esac
```

```
::
```

```
esac
```

?X: In silent mode, the standard output is closed. Questions are asked by

?X: outputting on file descriptor #4, which is the original stdout descriptor.

?X: This filters out all the "junk", since all the needed information is written

?X: on #4. Note that ksh will not let us redirect output if the file descriptor

?X: has not be defined yet, unlike sh, hence the following line...--RAM.

```
exec 4>&1
```

```
case "$silent" in
```

```
true) exec 1>/dev/null;;
```

```
esac
```

: run the defines and the undefines, if any, but leave the file out there...

```
touch optdef.sh
```

?X: -q is POSIX

?X: It does not work in SysV (solaris) or old BSD greps.

```
grep '\\ optdef.sh >/dev/null 2>&1
```

```
if test $? = 0; then
```

```
    echo "Configure does not support \\ in -D arguments"
```

```
    exit 1
```

```
fi
```

```
./optdef.sh
```

: create the posthint manipulation script and leave the file out there...

?X: this file will be perused by Oldconfig.U

```
touch posthint.sh
```

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/modified/Options.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: i_values.U 1 2006-08-24 12:32:52Z rmanfredi \$

?RCS:

?RCS: Copyright (c) 1996, Andy Dougherty

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic Licence,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic Licence; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: i_values.U,v \$

?RCS: Revision 3.0.1.1 1997/02/28 15:48:34 ram

?RCS: patch61: created

?RCS:

?MAKE:i_values: Inhdr

?MAKE: -pick add \$@ %<

?S:i_values:

?S: This variable conditionally defines the I_VALUES symbol, and indicates

?S: whether a C program may include <values.h> to get symbols like MAXLONG

?S: and friends.

?S:.

?C:I_VALUES:

?C: This symbol, if defined, indicates to the C program that it should

?C: include

<values.h> to get definition of symbols like MINFLOAT or

?C: MAXLONG, i.e. machine dependant limitations. Probably, you

?C: should use <limits.h> instead, if it is available.

?C:.

?H:#\$i_values I_VALUES /**/

?H:.

?LINT:set i_values

: see if this is a values.h system

set values.h i_values

eval \$inhdr

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/i_values.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_strncmp.U 1 2006-08-24 12:32:52Z rmanfredi \$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: \$Log: d_strncmp.U,v \$
?RCS: Revision 3.0.1.2 1994/05/06 14:54:34 ram
?RCS: patch23: fixed a typo (WED)
?RCS:
?RCS: Revision 3.0.1.1 1993/09/13 16:04:39 ram
?RCS: patch10: created (WAD)
?RCS:
?RCS: Revision 3.0 1993/08/18 12:06:24 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:d_strncmp: Inlibc
?MAKE: -pick add \$@ %<
?S:d_strncmp:
?S: This variable conditionally defines the HAS_STRCASECMP symbol, which
?S: indicates to the C program
that the strcasecmp() routine is available
?S: for case-insensitive string compares.
?S:.
?C:HAS_STRCASECMP:
?C: This symbol, if defined, indicates that the strcasecmp() routine is
?C: available for case-insensitive string compares.
?C:.
?H:#\$d_strncmp HAS_STRCASECMP /**/
?H:.
?LINT:set d_strncmp
: see if strcasecmp exists
set strcasecmp d_strncmp
eval \$inlibc

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/d_strncmp.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_endhostent_r.U,v ORCS:
?RCS: Copyright (c) 2002,2003 Jarkko Hietaniemi
?RCS:
?RCS: You may distribute under the terms of either the GNU General Public
?RCS: License or the Artistic License, as specified in the README file.
?RCS:

```

?RCS: Generated by the reentr.pl from the Perl 5.8 distribution.
?RCS:
?MAKE:d_endhostent_r endhostent_r_proto: Inlibc Protochk Hasproto i_systypes \
  usethreads i_netdb extern_C
?MAKE: -pick add $@ %<
?S:d_endhostent_r:
?S: This variable conditionally defines the HAS_ENDHOSTENT_R symbol,
?S: which indicates to the C program that the endhostent_r()
?S: routine is available.
?S:.
?S:endhostent_r_proto:
?S: This variable encodes the prototype of endhostent_r.
?S: It is zero if d_endhostent_r is undef, and one of the
?S: REENTRANT_PROTO_T_ABC macros of reentr.h if d_endhostent_r
?S: is defined.
?S:.
?C:HAS_ENDHOSTENT_R:
?C: This symbol, if defined, indicates that the endhostent_r routine
?C: is
  available to endhostent re-entrantly.
?C:.
?C:ENDHOSTENT_R_PROTO:
?C: This symbol encodes the prototype of endhostent_r.
?C: It is zero if d_endhostent_r is undef, and one of the
?C: REENTRANT_PROTO_T_ABC macros of reentr.h if d_endhostent_r
?C: is defined.
?C:.
?H:#$d_endhostent_r HAS_ENDHOSTENT_R  /**/
?H:#define ENDHOSTENT_R_PROTO $endhostent_r_proto  /**/
?H:.
?T:try hdrs d_endhostent_r_proto
: see if endhostent_r exists
set endhostent_r d_endhostent_r
eval $inlibc
case "$d_endhostent_r" in
"$define")
  hdrs="$i_systypes sys/types.h define stdio.h $i_netdb netdb.h"
  case "$d_endhostent_r_proto:$usethreads" in
  ":define") d_endhostent_r_proto=define
    set d_endhostent_r_proto endhostent_r $hdrs
    eval $hasproto ;;
  *) ;;
  esac
  case "$d_endhostent_r_proto" in
  define)
    case "$endhostent_r_proto" in
    "|0) try='int endhostent_r(struct hostent_data*);'
./protochk "$extern_C $try" $hdrs && endhostent_r_proto=I_D ;;

```

```

esac
case "$endhostent_r_proto" in
"|0) try='void
endhostent_r(struct hostent_data*);'
./prochck "$extern_C $try" $hdrs && endhostent_r_proto=V_D ;;
esac
case "$endhostent_r_proto" in
"|0) d_endhostent_r=undef
    endhostent_r_proto=0
    echo "Disabling endhostent_r, cannot determine prototype." >&4 ;;
*) case "$endhostent_r_proto" in
REENTRANT_PROTO*) ;;
*) endhostent_r_proto="REENTRANT_PROTO_$endhostent_r_proto" ;;
esac
echo "Prototype: $try" ;;
esac
;;
*) case "$usetthreads" in
define) echo "endhostent_r has no prototype, not using it." >&4 ;;
esac
d_endhostent_r=undef
endhostent_r_proto=0
;;
esac
;;
*) endhostent_r_proto=0
;;
esac

```

Found in path(s):

```

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/threads/d_endhostent_r.U

```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_regcmp.U 1 2006-08-24 12:32:52Z rmanfredi \$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic Licence,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic Licence; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: d_regcmp.U,v \$

?RCS: Revision 3.0.1.1 1995/01/30 14:34:45 ram

?RCS: patch49: now looks for POSIX regcomp() routine

?RCS:

```

?RCS: Revision 3.0 1993/08/18 12:06:53 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:d_regcmp d_re_comp d_regcomp: Csym cat
?MAKE: -pick add $@ %<
?S:d_regcomp:
?S: This variable conditionally defines the HAS_REGCOMP symbol, which
?S: indicates to the C program that the regcomp() routine is available
?S: for regular
pattern matching (usally on POSIX.2 conforming systems).
?S:.
?S:d_regcmp:
?S: This variable conditionally defines the HAS_REGCMP symbol, which
?S: indicates to the C program that the regcmp() routine is available
?S: for regular patern matching (usally on System V).
?S:.
?S:d_re_comp:
?S: This variable conditionally defines the HAS_RECOMP symbol, which
?S: indicates to the C program that the re_comp() routine is available
?S: for regular patern matching (usally on BSD). If so, it is likely that
?S: re_exec() exists.
?S:.
?C:HAS_REGCOMP (REGCOMP):
?C: This symbol, if defined, indicates that the regcomp() routine is
?C: available to do some regular patern matching (usually on POSIX.2
?C: conforming systems).
?C:.
?C:HAS_REGCMP (REGCMP):
?C: This symbol, if defined, indicates that the regcmp() routine is
?C: available to do some regular patern matching (usually on System V).
?C:.
?C:HAS_RECOMP (RECOMP):
?C: This symbol, if defined, indicates that the re_comp() routine is
?C: available
to do some regular patern matching (usually on BSD). If so,
?C: it is likely that re_exec() be available.
?C:.
?H:#$d_regcomp HAS_REGCOMP /* POSIX.2 */
?H:#$d_regcmp HAS_REGCMP /* sysV */
?H:#$d_re_comp HAS_RECOMP /* BSD */
?H:.
?T:val
: see if regcomp, regcmp, or re_comp exist, for regular pattern matching
echo " "
if set regcomp val -f d_regcomp; eval $csym; $val; then
echo 'regcomp() found.' >&4
d_regcomp="$define"
d_regcmp="$undef"

```

```

d_re_comp="$undef"
elif set regcmp val -f d_regcmp; eval $csym; $val; then
echo 'regcmp() found.' >&4
d_regcmp="$define"
d_re_comp="$undef"
d_re_comp="$undef"
elif set re_comp val -f d_re_comp; eval $csym; $val; then
echo 're_comp() found, assuming re_exec() also exists.' >&4
d_re_comp="$define"
d_regcomp="$undef"
d_regcomp="$undef"
else
$cat >&4 <<EOM
No regcomp(), regcmp() nor re_comp() found !! No regular pattern matching.
EOM
d_regcomp="$undef"
d_re_comp="$undef"
d_regcomp="$undef"
fi

```

Found in path(s):

```

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/d_regcomp.U

```

No license file was found, but licenses were detected in source scan.

```

?RCS: $Id: gidtype.U,v 3.0.1.3 1994/08/29 16:21:44 ram Exp $
?RCS:
?RCS: Copyright (c) 1991-1993, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 3.0.
?RCS:
?RCS: $Log: gidtype.U,v $
?RCS: Revision 3.0.1.3 1994/08/29 16:21:44 ram
?RCS: patch32: now uses new Typedef unit to compute type information
?RCS: patch32: removed useless usage of Setvar (for now)
?RCS:
?RCS: Revision 3.0.1.2 1994/05/13 15:21:07 ram
?RCS: patch27: added lint hint
?RCS:
?RCS: Revision 3.0.1.1 1994/05/06 15:01:51 ram
?RCS: patch23: protected gidtype setting via setvar (ADO)
?RCS: patch23: made Gid_t comment more explicit (ADO)
?RCS:
?RCS: Revision

```

3.0 1993/08/18 12:08:11 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?MAKE:gidtype: Myread Typedef Findhdr

?MAKE: -pick add \$@ %<

?S:gidtype:

?S: This variable defines Gid_t to be something like gid_t, int,

?S: ushort, or whatever type is used to declare the return type

?S: of getgid(). Typically, it is the type of group ids in the kernel.

?S:.

?C:Gid_t (GIDTYPE):

?C: This symbol holds the return type of getgid() and the type of

?C: argument to setrgid() and related functions. Typically,

?C: it is the type of group ids in the kernel. It can be int, ushort,

?C: gid_t, etc... It may be necessary to include <sys/types.h> to get

?C: any typedef'ed information.

?C:.

?H:#define Gid_t \$gidtype /* Type for getgid(), etc... */

?H:.

?T:xxx

: see what type gids are declared as in the kernel

echo " "

echo "Looking for the type for group ids returned by getgid()."

set gid_t gidtype xxx stdio.h sys/types.h

eval \$typedef

case "\$gidtype" in

xxx)

xxx=`./findhdr sys/user.h`

set `grep

'groups\[NGROUPS\];' "\$xxx" 2>/dev/null` unsigned short

case \$1 in

unsigned) dflt="\$1 \$2" ;;

*) dflt="\$1" ;;

esac

;;

*) dflt="\$gidtype";;

esac

case "\$gidtype" in

gid_t) echo "gid_t found." ;;

*) rp="What is the type for group ids returned by getgid()?"

. ./myread

gidtype="\$ans"

;;

esac

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-

debian-perl-5.26.1/U/typedefs/gidtype.U

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: d_msgctl.U 1 2006-08-24 12:32:52Z rmanfredi $
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: $Log: d_msgctl.U,v $
?RCS: Revision 3.0 1993/08/18 12:06:38 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:d_msgctl: Inlibc
?MAKE: -pick add $@ %<
?S:d_msgctl:
?S: This variable conditionally defines the HAS_MSGCTL symbol, which
?S: indicates to the C program that the msgctl() routine is available.
?S:.
?C:HAS_MSGCTL:
?C: This symbol, if defined, indicates that the msgctl() routine is
?C: available to perform message control operations.
?C:.
?H:#$d_msgctl
HAS_MSGCTL /**/
?H:.
?LINT:set d_msgctl
: see if msgctl exists
set msgctl d_msgctl
eval $inlibc
```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/d_msgctl.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: i_arpainet.U 1 2006-08-24 12:32:52Z rmanfredi $
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
```

```
?RCS:
?RCS: $Log: i_arpainet.U,v $
?RCS: Revision 3.0 1993/08/18 12:08:15 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:i_arpainet: Inhdr
?MAKE: -pick add $@ %<
?S:i_arpainet:
?S: This variable conditionally defines the I_ARPA_INET symbol,
?S: and indicates whether a C program should include <arpa/inet.h>.
?S:.
?C:I_ARPA_INET:
?C: This symbol, if defined, indicates to the C program that it should
?C: include <arpa/inet.h> to get inet_addr and friends
declarations.
?C:.
?H:#$i_arpainet I_ARPA_INET /**/
?H:.
?LINT:set i_arpainet
: see if arpa/inet.h has to be included
set arpa/inet.h i_arpainet
eval $inhdr
```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/i_arpainet.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: i_sysndir.U 1 2006-08-24 12:32:52Z rmanfredi $
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: $Log: i_sysndir.U,v $
?RCS: Revision 3.0 1993/08/18 12:08:33 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:i_sysndir: Inhdr
?MAKE: -pick add $@ %<
?S:i_sysndir:
?S: This variable conditionally defines the I_SYS_NDIR symbol, and indicates
?S: whether a C program should include <sys/ndir.h>.
?S:.
```

?C:I_SYS_NDIR (I_SYSNDIR):

?C: This symbol, if defined, indicates to the C program that it should

?C: include <sys/ndir.h>.

?C:.

?H:#\$i_sysndir

I_SYS_NDIR /**/

?H:.

?LINT:set i_sysndir

: see if this is an sysndir system

set sys/ndir.h i_sysndir

eval \$inhdr

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/i_sysndir.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: Hasproto.U \$

?RCS:

?RCS: Copyright (c) 1998 Andy Dougherty

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?X: This unit generates a \$hasproto string that is used internally

?X: by Configure to check if this system has a prototype for a

?X: particular function

?X:

?X: To use it, say something like:

?X: set d_getnetent_proto getnetent \$i_netdb netdb.h

?X: eval \$hasproto

?X: Or, for more complicated sets of headers, do something like

?X: hdrs="\$define sys/types.h

?X: \$i_system sys/time.h

?X: \$i_sysselect sys/select.h

?X: \$i_netdb netdb.h"

?X: set d_getnetent_proto getnetent \$hdrs

?X: eval \$hasproto

?X:

?MAKE:Hasproto: Setvar cppstdin cppflags cppminus contains rm_try test

?MAKE: -pick add \$@ %<

?T:func varname

?F:!try.c

?V:hasproto

: Define hasproto macro for Configure internal use

hasproto='varname=\$1;

func=\$2; shift; shift;

while \$test \$# -ge 2; do

```

case "$1" in
$define) echo "#include <$2>";;
esac ;
  shift 2;
done > try.c;
$cppstdin $cppflags $cppminus < try.c > tryout.c 2>/dev/null;
if $contains "$func.*(" tryout.c >/dev/null 2>&1; then
  echo "$func() prototype found.";
  val="$define";
else
  echo "$func() prototype NOT found.";
  val="$undef";
fi;
set $varname;
eval $setvar;
$rm_try tryout.c'

```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/protos/Hasproto.U
```

No license file was found, but licenses were detected in source scan.

```

?RCS: $Id: d_setpgrp.U,v 3.0.1.3 1997/02/28 15:44:16 ram Exp $
?RCS:
?RCS: Copyright (c) 1991-1993, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 3.0.
?RCS:
?RCS: $Log: d_setpgrp.U,v $
?RCS: Revision 3.0.1.3 1997/02/28 15:44:16 ram
?RCS: patch61: obsoleted USE_BSDGRP in favor of USE_BSD_SETPGRP
?RCS: patch61: another unit now also defines a USE_BSD_GETPGRP
?RCS: patch61: fallback for test program failure improved
?RCS:
?RCS: Revision 3.0.1.2 1995/07/25 13:59:30 ram
?RCS: patch56: re-arranged compile line to include ldflags before objects
?RCS:
?RCS: Revision 3.0.1.1 1994/10/29 16:15:37 ram
?RCS: patch36: added
'ldflags' to the test compile line (ADO)
?RCS: patch36: call ./usg explicitly instead of relying on PATH
?RCS:
?RCS: Revision 3.0 1993/08/18 12:07:09 ram
?RCS: Baseline for dist 3.0 netwide release.

```

```

?RCS:
?MAKE:d_setpgrp d_bsdsetpgrp: cat rm_try +cc +libs +ccflags \
+ldflags Inlibc Guess Setvar i_unistd i_stdlib run
?MAKE: -pick add $@ %<
?S:d_setpgrp:
?S: This variable conditionally defines HAS_SETPGRP if setpgrp() is
?S: available to set the current process group.
?S:.
?S:d_bsdsetpgrp (d_bsdpgrp):
?S: This variable conditionally defines USE_BSD_SETPGRP if
?S: setpgrp needs two arguments whereas USG one needs none.
?S: See also d_setpgid for a POSIX interface.
?S:.
?C:HAS_SETPGRP (SETPGRP):
?C: This symbol, if defined, indicates that the setpgrp routine is
?C: available to set the current process group.
?C:.
?C:USE_BSD_SETPGRP (USE_BSDPGRP BSDPGRP):
?C: This symbol, if defined, indicates that setpgrp needs two
?C: arguments whereas USG one needs none. See also HAS_SETPGID
?C: for
a POSIX interface.
?C:.
?H:#$d_setpgrp HAS_SETPGRP /**/
?H:#$d_bsdsetpgrp USE_BSD_SETPGRP /**/
?H:.
?T:xxx
?F:!try
?LINT:set d_setpgrp d_bsdsetpgrp
: see if setpgrp exists
set setpgrp d_setpgrp
eval $inlibc

@if USE_BSD_SETPGRP || d_bsdsetpgrp
case "$d_setpgrp" in
"$define")
echo " "
echo "Checking to see which flavor of setpgrp is in use..."
$cat >try.c <<EOP
#$i_unistd I_UNISTD
#include <sys/types.h>
#ifdef I_UNISTD
# include <unistd.h>
#endif
#$i_stdlib I_STDLIB
#ifdef I_STDLIB
#include <stdlib.h>
#endif

```

```

int main()
{
if (getuid() == 0) {
printf("(I see you are running Configure as super-user...)\n");
setuid(1);
}
#ifdef TRY_BSD_PGRP
if (-1 == setpgrp(1, 1))
exit(0);
#else
if (setpgrp() != -1)
exit(0);
#endif
exit(1);
}
EOP
if $cc -o try -DTRY_BSD_PGRP $ccflags $ldflags try.c $libs >/dev/null 2>&1 && $run ./try; then
echo 'You have to use setpgrp(pid,pgrp) instead of setpgrp().' >&4
val="$define"
elif $cc -o try $ccflags $ldflags try.c $libs >/dev/null 2>&1 &&
$run ./try; then
echo 'You have to use setpgrp() instead of setpgrp(pid,pgrp).' >&4
val="$undef"
else
echo "(I can't seem to compile and run the test program.)"
if ./usg; then
xxx="a USG one, i.e. you use setpgrp()."
else
# SVR4 systems can appear rather BSD-ish.
case "$i_unistd" in
$undef)
xxx="a BSD one, i.e. you use setpgrp(pid,pgrp)."
val="$define"
;;
$define)
xxx="probably a USG one, i.e. you use setpgrp()."
val="$undef"
;;
esac
fi
echo "Assuming your setpgrp is $xxx" >&4
fi
;;
*) val="$undef";;
esac
set d_bsdsetpgrp
eval $setvar
$rm_try

```

@end

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/modified/d_setpgrp.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: startsh.U 1 2006-08-24 12:32:52Z rmanfredi \$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic Licence,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic Licence; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: startsh.U,v \$

?RCS: Revision 3.0.1.1 1997/02/28 16:25:31 ram

?RCS: patch61: avoid needless chatter since this is now done very early

?RCS:

?RCS: Revision 3.0 1993/08/18 12:09:51 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?MAKE:startsh: sh sharpbang eunicefix

?MAKE: -pick add \$@ %<

?S:startsh:

?S: This variable contains the string to put on the front of a shell

?S: script to make sure (hopefully) that it runs with sh and not some

?S: other

shell.

?S:.

?F:!sharp

: figure out how to guarantee sh startup

?X: Avoid needless chatter since this is now done very early.

?X: echo " "

?X: echo "Checking out how to guarantee sh startup..." >&2

case "\$startsh" in

") startsh=\${sharpbang}\${sh} ;;

*)

?X: echo "Let's see if '\$startsh' works..." ;;

esac

cat >sharp <<EOSS

\$startsh

set abc

test "\$?abc" != 1

EOSS

```

chmod +x sharp
$unicefix sharp
if ./sharp; then
: echo "Yup, it does."
else
echo "Hmm... '$startsh' does not guarantee sh startup..."
echo "You may have to fix up the shell scripts to make sure $sh runs them."
fi
rm -f sharp

```

Found in path(s):

```

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/startsh.U

```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: vendorarch.U,v 1.1 1999/07/08 18:32:57 doughera Exp doughera \$

?RCS:

?RCS: Copyright (c) 1999, Andy Dougherty

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 3.0.

?RCS:

?RCS: \$Log: vendorarch.U,v \$

?RCS: Revision 1.1 1999/07/08 18:32:57 doughera

?RCS: Initial revision

?RCS:

?MAKE:d_vendorarch vendorarch vendorarchexp installvendorarch: sed Getfile \

Setprefixvar Oldconfig Prefixit archname vendorlib vendorprefix test

?MAKE: -pick add \$@ %<

?Y:TOP

?S:vendorarch:

?S: This variable contains the value of the PERL_VENDORARCH symbol.

?S: It may have a ~ on the front.

?S: The standard distribution will put nothing in this directory.

?S: Vendors

who distribute perl may wish to place their own

?S: architecture-dependent modules and extensions in this directory with

?S: MakeMaker Makefile.PL INSTALLDIRS=vendor

?S: or equivalent. See INSTALL for details.

?S:.

?S:vendorarchexp:

?S: This variable is the ~name expanded version of vendorarch, so that you

?S: may use it directly in Makefiles or shell scripts.

?S:.

?D:installvendorarch="

?S:installvendorarch:
 ?S: This variable is really the same as vendorarchexp but may differ on
 ?S: those systems using AFS. For extra portability, only this variable
 ?S: should be used in makefiles.
 ?S:.
 ?S:d_vendorarch:
 ?S: This variable conditionally defined PERL_VENDORARCH.
 ?S:.
 ?C:PERL_VENDORARCH:
 ?C: If defined, this symbol contains the name of a private library.
 ?C: The library is private in the sense that it needn't be in anyone's
 ?C: execution path, but it should be accessible by the world.
 ?C: It may have a ~ on the front.
 ?C: The standard distribution will put nothing in this
 directory.
 ?C: Vendors who distribute perl may wish to place their own
 ?C: architecture-dependent modules and extensions in this directory with
 ?C: MakeMaker Makefile.PL INSTALLDIRS=vendor
 ?C: or equivalent. See INSTALL for details.
 ?C:.
 ?C:PERL_VENDORARCH_EXP:
 ?C: This symbol contains the ~name expanded version of PERL_VENDORARCH, to be used
 ?C: in programs that are not prepared to deal with ~ expansion at run-time.
 ?C:.
 ?H:#\$d_vendorarch PERL_VENDORARCH "\$vendorarch" /**/
 ?H:#\$d_vendorarch PERL_VENDORARCH_EXP "\$vendorarchexp" /**/
 ?H:.
 ?LINT:change prefixvar
 ?LINT:set installvendorarch
 : Set the vendorarch variables
 case "\$vendorprefix" in
 ") d_vendorarch="\$undef"
 vendorarch="
 vendorarchexp="
 ;;
 *) d_vendorarch="\$define"
 : determine where vendor-supplied architecture-dependent libraries go.
 : vendorlib default is /usr/local/lib/perl5/vendor_perl/\$version
 : vendorarch default is /usr/local/lib/perl5/vendor_perl/\$version/\$archname
 : vendorlib may have an optional trailing
 /share.
 case "\$vendorarch" in
 ") dflt=`echo \$vendorlib | \$sed 's,/share\$,,'`
 dflt="\$dflt/\$archname"
 ;;
 *) dflt="\$vendorarch" ;;
 esac
 fn=d~+

```

rp='Pathname for vendor-supplied architecture-dependent files?'
./getfile
vendorarch="$ans"
vendorarchexp="$ansexp"
;;
esac
prefixvar=vendorarch
./installprefix
if $test X"$vendorarch" = X"$vendorlib"; then
d_vendorarch="$undef"
else
d_vendorarch="$define"
fi

```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/installdirs/vendorarch.U
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1999, Jarkko Hietaniemi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 3.0.

?RCS:

?MAKE:d_shm_open: Inlibc

?MAKE: -pick add \$@ %<

?S:d_shm_open:

?S: This variable conditionally defines HAS_SHM_OPEN if shm_open() is

?S: available to open a POSIX shared memory object.

?S:.

?C:HAS_SHM_OPEN:

?C: This symbol, if defined, indicates that the shm_open system call is

?C: available to open a POSIX shared memory object.

?C:.

?H:#\$d_shm_open HAS_SHM_OPEN /**/

?H:.

?LINT:set d_shm_open

: see if shm_open exists

set shm_open d_shm_open

eval \$inlibc

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
```

debian-perl-5.26.1/U/perl/d_shm_open.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: i_dirent.U,v \$

?RCS: Revision 3.0.1.4 1994/10/29 16:20:01 ram

?RCS: patch36: failed scanning for 'd_namlen' with missing <dirent.h> (ADO)

?RCS:

?RCS: Revision 3.0.1.3 1994/06/20 07:01:25 ram

?RCS: patch30: added direntrytype for hints, merely for NeXT (ADO)

?RCS: patch30: now checks for both struct dirent and direct (ADO)

?RCS:

?RCS: Revision 3.0.1.2 1994/05/13 15:22:37 ram

?RCS: patch27: new variable direntrytype for proper type setting (ADO)

?RCS:

?RCS: Revision 3.0.1.1 1994/01/24

14:11:15 ram

?RCS: patch16: added new Direntry_t pseudo-type for directory entries

?RCS:

?RCS: Revision 3.0 1993/08/18 12:08:17 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?X:

?X: This unit looks whether there is a dirent system or not

?X:

?MAKE:i_dirent d_dirnamlen direntrytype: test contains Setvar \

Myread Findhdr cppstdin cppflags cppminus rm_try

?MAKE: -pick add \$@ %<

?S:i_dirent:

?S: This variable conditionally defines I_DIRENT, which indicates

?S: to the C program that it should include <dirent.h>.

?S:.

?S:d_dirnamlen:

?S: This variable conditionally defines DIRNAMLEN, which indicates

?S: to the C program that the length of directory entry names is

?S: provided by a d_namelen field.

?S:.

?S:direntrytype:

?S: This symbol is set to 'struct direct' or 'struct dirent' depending on

?S: whether dirent is available or not. You should use this pseudo type to

?S: portably declare your directory entries.

?S:.

?C:I_DIRENT:

?C: This symbol, if defined, indicates to the C program that it should

?C: include <dirent.h>. Using this symbol also triggers the definition

?C: of the Direntry_t define which ends up being 'struct dirent' or

?C: 'struct direct' depending on the availability of <dirent.h>.

?C:.

?C:DIRNAMLEN:

?C: This symbol, if defined, indicates to the C program that the length

?C: of directory entry names is provided by a d_namlen field. Otherwise

?C: you need to do strlen() on the d_name field.

?C:.

?C:Direntry_t:

?C: This symbol is set to 'struct direct' or 'struct dirent' depending on

?C: whether dirent is available or not. You should use this pseudo type to

?C: portably declare your directory entries.

?C:.

?H:#\$i_dirent I_DIRENT /**/

?H:#\$d_dirnamlen DIRNAMLEN /**/

?H:?%<:@if I_DIRENT && Direntry_t

?H:?%<:#define Direntry_t \$direntrytype

?H:?%<:@end

?H:.

?T:xinc guess1 guess2

?LINT:set i_dirent d_dirnamlen

: see if this is a dirent system

echo " "

if xinc=`./findhdr dirent.h`; \$test "\$xinc"; then

val="\$define"

echo "<dirent.h> found." >&4

else

val="\$undef"

if

xinc=`./findhdr sys/dir.h`; \$test "\$xinc"; then

echo "<sys/dir.h> found." >&4

echo " "

else

xinc=`./findhdr sys/ndir.h`

fi

echo "<dirent.h> NOT found." >&4

fi

set i_dirent

eval \$setvar

?X: Use struct dirent or struct direct? If we're using dirent.h,

```

?X: it's probably struct dirent, but apparently not always.
?X: Assume $xinc still contains the name of the header file we're using.
@if direntrytype || Direntry_t
: Look for type of directory structure.
echo " "
$cppstdin $cppflags $cppminus < "$xinc" > try.c

case "$direntrytype" in
'|')
case "$i_dirent" in
$define) guess1='struct dirent' ;;
*) guess1='struct direct' ;;
esac
;;
*) guess1="$direntrytype"
;;
esac

case "$guess1" in
'struct dirent') guess2='struct direct' ;;
*) guess2='struct dirent' ;;
esac

if $contains "$guess1" try.c >/dev/null 2>&1; then
direntrytype="$guess1"
echo "Your directory entries are $direntrytype." >&4
elif $contains "$guess2" try.c >/dev/null 2>&1; then
direntrytype="$guess2"
echo
"Your directory entries seem to be $direntrytype." >&4
else
echo "I don't recognize your system's directory entries." >&4
rp="What type is used for directory entries on this system?"
dflt="$guess1"
./myread
direntrytype="$ans"
fi
$rm_try

@end

@if d_dirnamlen || DIRNAMLEN
: see if the directory entry stores field length
echo " "
$cppstdin $cppflags $cppminus < "$xinc" > try.c
if $contains 'd_namlen' try.c >/dev/null 2>&1; then
echo "Good, your directory entry keeps length information in d_namlen." >&4
val="$define"

```

```
else
echo "Your directory entry does not know about the d_namlen field." >&4
val="$undef"
fi
set d_dirnamlen
eval $setvar
$rm_try

@end
```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/i_dirent.U
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: Extractall.U,v \$

?RCS: Revision 3.0.1.1 1997/02/28 15:00:43 ram

?RCS: patch61: created

?RCS:

?X:

?X: If extraction has been requested, load the configuration file, perform

?X: the extraction and exit.

?X:

?X: This unit was originally a part of Options.U. It had to be removed from

?X: it to prevent a dependency cycle: Extract -> src -> Options -> Extract

?X: The Begin.U unit now requires us before beginning to do anything

?X: interesting, to ensure proper semantics. -- RAM, 15/03/96

?X:

?MAKE:Extractall:

Extract Options

?MAKE: -pick wipe \$@ %<

: extract files and exit if asked to do so

case "\$extractsh" in

true)

?X: Undo the forced silent=true when -S was supplied, by probing realsilent

?X: which was set iff -s was also given. See Options.U for details.

case "\$realsilent" in

true) ;;

```

*) exec 1>&4;;
esac
case "$config_sh" in
") config_sh='config.sh';;
esac
echo " "
echo "Fetching answers from $config_sh..."
cd ..
. $config_sh
test "$override" && . ./optdef.sh
echo " "
?X: extract has to be run from the top directory, not within UU.
. UU/extract
rm -rf UU
echo "Extraction done."
exit 0
;;
esac

```

Found in path(s):

```

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/Extractall.U

```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: i_time.U,v 3.0 1993/08/18 12:08:45 ram Exp \$

?RCS:

?RCS: Copyright (c) 1991-1993, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 3.0.

?RCS:

?RCS: \$Log: i_time.U,v \$

?RCS: Revision 3.0 1993/08/18 12:08:45 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?X:

?X: This unit finds which "time" include to use. If 'timezone' is used by the

?X: program, we also try to find which header should be included. Eventually,

?X: we look for <sys/select.h> if I_SYSSELECT is used, to get struct timeval.

?X:

?MAKE:i_time i_systime i_systimek timeincl d_tm_tm_zone d_tm_tm_gmtoff: \

Compile cat \

contains rm_try echo n

c +i_sysselect Findhdr Hasfield i_stdlib

?MAKE: -pick add \$@ %<

?S:i_time:
?S: This variable conditionally defines I_TIME, which indicates
?S: to the C program that it should include <time.h>.
?S:.

?S:i_systime:
?S: This variable conditionally defines I_SYS_TIME, which indicates
?S: to the C program that it should include <sys/time.h>.
?S:.

?S:i_systimek:
?S: This variable conditionally defines I_SYS_TIME_KERNEL, which
?S: indicates to the C program that it should include <sys/time.h>
?S: with KERNEL defined.
?S:.

?S:timeincl:
?S: This variable holds the full path of the included time header(s).
?S:.

?S:d_tm_tm_zone:
?S: This variable conditionally defines HAS_TM_TM_ZONE, which indicates
?S: indicates to the C program that the struct tm has the tm_zone field.
?S:.

?S:d_tm_tm_gmtoff:
?S: This variable conditionally defines HAS_TM_TM_GMTOFF, which indicates
?S: indicates to the C program that the struct tm has the tm_gmtoff field.
?S:.

?C:I_TIME (USE_TIME_H):
?C: This symbol, if defined,
indicates to the C program that it should
?C: include <time.h>.
?C:.

?C:I_SYS_TIME (I_SYSTIME USE_SYS_TIME_H NO_TIME_WITH_SYS_TIME):
?C: This symbol, if defined, indicates to the C program that it should
?C: include <sys/time.h>.
?C:.

?C:I_SYS_TIME_KERNEL (I_SYSTIMEKERNEL):
?C: This symbol, if defined, indicates to the C program that it should
?C: include <sys/time.h> with KERNEL defined.
?C:.

?C:HAS_TM_TM_ZONE:
?C: This symbol, if defined, indicates to the C program that
?C: the struct tm has a tm_zone field.
?C:.

?C:HAS_TM_TM_GMTOFF:
?C: This symbol, if defined, indicates to the C program that
?C: the struct tm has a tm_gmtoff field.
?C:.

?H:#\$i_time I_TIME /**/
?H:#\$i_systime I_SYS_TIME /**/
?H:#\$i_systimek I_SYS_TIME_KERNEL /**/

```

?H:#$d_tm_tm_zone HAS_TM_TM_ZONE /**/
?H:#$d_tm_tm_gmtoff HAS_TM_TM_GMTOFF /**/
?H:
?W::timezone
?T:xselect flags sysselect s_timeval s_timezone
?LINT:change i_sysselect
?LINT:set d_tm_tm_zone
?LINT:set d_tm_tm_gmtoff
: see if we should include time.h,
  sys/time.h, or both
echo " "
if test "X$timeincl" = X; then
echo "Testing to see if we should include <time.h>, <sys/time.h> or both." >&4
$echo $n "I'm now running the test program...$c"
$cat >try.c <<EOCP
#include <sys/types.h>
#ifdef I_TIME
#include <time.h>
#endif
#ifdef I_SYSTIME
#ifdef SYSTIMEKERNEL
#define KERNEL
#endif
#include <sys/time.h>
#endif
#ifdef I_SYSSELECT
#include <sys/select.h>
#endif
#$i_stdlib I_STDLIB
#ifdef I_STDLIB
#include <stdlib.h>
#endif
int main()
{
  struct tm foo;
#ifdef S_TIMEVAL
  struct timeval bar;
#endif
#ifdef S_TIMEZONE
  struct timezone tzp;
#endif
  if (foo.tm_sec == foo.tm_sec)
    exit(0);
#ifdef S_TIMEVAL
  if (bar.tv_sec == bar.tv_sec)
    exit(0);
#endif
  exit(1);
}

```

```

}
EOCP
flags="
@if I_SYSSELECT
if $contains 'timeval.*{'`./findhdr sys/select.h` >/dev/null 2>&1; then
  xselect='-DI_SYSSELECT'
else
  xselect=""
fi
@end
@if timezone
for s_timezone in '-DS_TIMEZONE' "; do
@else
s_timezone=""
@end
?X: Every package is given a try with 'struct
timeval'
@if I_SYSSELECT
for sysselect in $xselect "; do
@else
sysselect=""
@end
for s_timeval in '-DS_TIMEVAL' "; do
for i_systimek in "'-DSYSTIMEKERNEL'; do
for i_time in "'-DI_TIME'; do
for i_systime in '-DI_SYSTIME' "; do
case "$flags" in
") $echo $n ".$c"
set try $i_time $i_systime $i_systimek $sysselect $s_timeval $s_timezone
if eval $compile; then
set X $i_time $i_systime $i_systimek $sysselect $s_timeval
shift
flags="$*"
echo " "
$echo $n "Succeeded with $flags$c"
fi
;;
esac
done
done
done
done
done
@if I_SYSSELECT
done
@end
@if timezone
done
@end

```

```

timeincl="
echo " "
case "$flags" in
*SYSTIMEKERNEL*) i_systimek="$define"
timeincl=`./findhdr sys/time.h`
echo "We'll include <sys/time.h> with KERNEL defined." >&4;;
*) i_systimek="$undef";;
esac
case "$flags" in
*I_TIME*) i_time="$define"
timeincl=`./findhdr time.h` $timeincl
echo "We'll include <time.h>." >&4;;
*) i_time="$undef";;
esac
case "$flags" in
*I_SYSTIME*)
i_systime="$define"
timeincl=`./findhdr sys/time.h` $timeincl
echo "We'll include <sys/time.h>." >&4;;
*) i_systime="$undef";;
esac
@if I_SYSSSELECT
case "$flags" in
*I_SYSSSELECT*) i_syssselct="$define"
timeincl=`./findhdr sys/select.h` $timeincl
echo "We'll also include <sys/select.h> to get struct timeval." >&4;;
*) case "$i_syssselct" in
") i_syssselct="$undef";;
esac
esac
@end
$rm_try
fi
: see if struct tm knows about tm_zone
case "$i_systime$i_time" in
*$define*)
echo " "
echo "Checking to see if your struct tm has tm_zone field..." >&4
set d_tm_tm_zone tm tm_zone $i_systime sys/time.h $i_time time.h
eval $hasfield
;;
*) val="$undef"
set d_tm_tm_zone
eval $setvar
;;
esac
case "$d_tm_tm_zone" in
"$define") echo "Yes, it does." ;;

```

```

*)      echo "No, it doesn't." ;;
esac
: see if struct tm knows about tm_gmtoff
case "$i_systime$i_time" in
*$define*)
    echo " "

    echo "Checking to see if your struct tm has tm_gmtoff field..." >&4
    set d_tm_tm_gmtoff tm tm_gmtoff $i_systime sys/time.h $i_time time.h
    eval $hasfield
    ;;
*)      val="$undef"
    set d_tm_tm_gmtoff
    eval $setvar
    ;;
esac
case "$d_tm_tm_gmtoff" in
"$define")      echo "Yes, it does." ;;
*)              echo "No, it doesn't." ;;
esac

```

Found in path(s):

```

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/compline/i_time.U

```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: Head.U,v \$

?RCS: Revision 3.0.1.9 1997/02/28 15:02:09 ram

?RCS: patch61: make sure we unset CDPATH for shells that support this

?RCS: patch61: improved Korn shell detection and handling

?RCS:

?RCS: Revision 3.0.1.8 1995/07/25 13:40:02 ram

?RCS: patch56: added SVR4-ish /opt directories to path list (ADO)

?RCS: patch56: OS/2 platforms are using another path separator

?RCS:

?RCS: Revision 3.0.1.7 1995/03/21 08:46:15 ram

?RCS: patch52: definition of paths wrongly added spurious ':' chars

?RCS:

?RCS:
Revision 3.0.1.6 1994/10/29 15:54:19 ram
?RCS: patch36: make sure ENV is unset before calling /bin/ksh
?RCS:
?RCS: Revision 3.0.1.5 1994/08/29 16:03:44 ram
?RCS: patch32: now sets PATH only using existing directories
?RCS:
?RCS: Revision 3.0.1.4 1994/06/20 06:54:28 ram
?RCS: patch30: now computes its invocation name into 'me'
?RCS: patch30: symbol me is made visible to all units read-only
?RCS:
?RCS: Revision 3.0.1.3 1993/12/15 08:15:07 ram
?RCS: patch15: added /sbin:/usr/sbin:/usr/libexec in PATH for BSD/386
?RCS:
?RCS: Revision 3.0.1.2 1993/11/10 17:32:35 ram
?RCS: patch14: ensure PATH is reset to '.' before testing for alias
?RCS:
?RCS: Revision 3.0.1.1 1993/08/27 14:38:07 ram
?RCS: patch7: not all 'test' programs support the -x option
?RCS:
?RCS: Revision 3.0 1993/08/18 12:04:58 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?X:
?X: This is the very first unit in the Configure script. It is mostly just
?X: things to keep people from getting
into a tizzy right off the bat.
?X:
?MAKE:Head:
?MAKE: -pick wipe \$@ %<
?V:PATH p_ _exe me newsh
?T:argv Id p paths OS2_SHELL DJGPP
?T:inksh needksh avoidksh newsh changesh reason
?F:!*
?LINT:extern ENV CDPATH SHELL MACHTYPE
?LINT:change ENV CDPATH
?LINT:nocomment
#!/bin/sh

If these # comments don't work, trim them. Don't worry about any other
shell scripts, Configure will trim # comments from them for you.

(If you are trying to port this package to a machine without sh,
I would suggest you have a look at the prototypical config_h.SH file
and edit it to reflect your system. Some packages may include samples
of config.h for certain machines, so you might look for one of those.)

?X:

?X: NOTE THAT A CONFIGURE SCRIPT IS IN THE PUBLIC DOMAIN (whether or not

?X: the software which uses it is in the public domain).

?X:

Yes, you may rip this off to use in other distribution packages. This

script belongs to the public domain and cannot be copyrighted.

#

?X:

?X: WE ASK YOU

NOT TO REMOVE OR ALTER THE FOLLOWING PARAGRAPH, PLEASE:

?X:

Note: this Configure script was generated automatically. Rather than

working with this copy of Configure, you may wish to get metaconfig.

The dist package (which contains metaconfig) is available via SVN:

svn co <https://svn.code.sf.net/p/dist/code/trunk/dist>

?X:

?X: NOTA BENE:

?X: If you develop your own version of metaconfig based on this work,

?X: you have to add some comments telling that the script was generated

?X: by your version, not mine: It credits your work.

?X:

\$Id: Head.U 6 2006-08-25 22:21:46Z rmanfredi \$

#

Generated on <DATE> [metaconfig <VERSION> PL<PATCHLEVEL>]

cat >c1\$\$ <<EOF

ARGGGHHHH!!!!

SCO csh still thinks true is false. Write to SCO today and tell them that next year Configure ought to "rm /bin/csh" unless they fix their blasted shell. :-)

(Actually, Configure ought to just patch csh in place. Hmm. Hmmmmm. All we'd have to do is go in and swap the && and || tokens, wherever they are.)

[End

of diatribe. We now return you to your regularly scheduled programming...]

EOF

cat >c2\$\$ <<EOF

OOPS! You naughty creature! You didn't run Configure with sh!

I will attempt to remedy the situation by running sh for you...

EOF

true || cat c1\$\$ c2\$\$

true || exec sh \$0 \$argv:q

(exit \$?0) || cat c2\$\$

(exit \$?0) || exec sh \$0 \$argv:q

```
rm -f c1$$ c2$$
```

```
: compute my invocation name
```

```
me=$0
```

```
case "$0" in
```

```
*/*)
```

```
me=`echo $0 | sed -e 's!.*\^(.*)!\1!' 2>/dev/null`
```

```
test "$me" || me=$0
```

```
::
```

```
esac
```

```
?X:
```

```
?X: To be able to run under OS/2, we must detect that early enough to use
```

```
?X: the proper path separator, stored in $p_. It is : on UNIX and ; on
```

```
?X: DOSish systems such as OS/2.
```

```
?X:
```

```
: Proper separator for the PATH environment variable
```

```
p_=:
```

```
: On OS/2 this directory should exist if this is not floppy only system ":-]"
```

```
if test -d c:/ ; then
```

```
if test -n "$OS2_SHELL"; then
```

```
  p_=\;
```

```
  PATH=`cmd /c "echo %PATH%" | tr '\\\\' /`
```

```
?X: That's a bug in ksh5.22
```

```
  OS2_SHELL=`cmd /c "echo %OS2_SHELL%" | tr
```

```
  '\\\\' / | tr '[A-Z]' [a-z]`
```

```
elif test -n "$DJGPP"; then
```

```
  case "X${MACHTYPE:-nonesuchmach}" in
```

```
  *cygwin) ;;
```

```
  *) p_=\; ; ;
```

```
  esac
```

```
fi
```

```
fi
```

```
?X:
```

```
?X: There are two schools of thoughts here. Some people correctly argue that
```

```
?X: the user has a better chance than we do of setting a reasonable PATH and
```

```
?X: others argue that Configure is the best place there is to set up a suitable
```

```
?X: PATH. Well, here we try to compromise by keeping the user's PATH and
```

```
?X: appending some directories which are known to work on some machine or the
```

```
?X: other. The rationale behind this being that a novice user might not have a
```

```
?X: proper environment variable set, and some directories like /etc (where
```

```
?X: chown is located on some BSD systems) may be missing--RAM.
```

```
?X:
```

```
?X: SVR4 adds an /opt directory for optional packages. Some sites use
```

```
?X: various permutations on /opt as opposed to /usr or /usr/local.-- ADO
```

```
?X:
```

```
?X: We only add directories that are not already in the PATH of the
```

?X: user and the directories must

exist also.

?X:

: Proper PATH setting

```
paths="/bin /usr/bin /usr/local/bin /usr/ucb /usr/local /usr/sbin"
```

```
paths="$paths /opt/bin /opt/local/bin /opt/local /opt/sbin"
```

```
paths="$paths /usr/5bin /etc /usr/gnu/bin /usr/new /usr/new/bin /usr/nbin"
```

```
paths="$paths /opt/gnu/bin /opt/new /opt/new/bin /opt/nbin"
```

```
paths="$paths /sys5.3/bin /sys5.3/usr/bin /bsd4.3/bin /bsd4.3/usr/ucb"
```

```
paths="$paths /bsd4.3/usr/bin /usr/bsd /bsd43/bin /usr/ccs/bin"
```

```
paths="$paths /etc /usr/lib /usr/ucblib /lib /usr/ccs/lib"
```

```
paths="$paths /sbin /usr/sbin /usr/libexec"
```

```
paths="$paths /system/gnu_library/bin"
```

```
for p in $paths
```

```
do
```

```
case "$p_${PATH}$p_" in
```

```
*$p_${PATH}$p_*) ;;
```

```
*) test -d $p && PATH=${PATH}$p_$p ;;
```

```
esac
```

```
done
```

```
PATH=.$p_${PATH}
```

```
export PATH
```

: shall we be using ksh?

```
inksh=""
```

```
needksh=""
```

```
avoidksh=""
```

```
newsh=/bin/ksh
```

```
changesh=""
```

?X: Use (alias -x) and not (alias) since zsh and bash recognize the alias

?X: builtin but not the -x option which is typically ksh...

?X: We need to set up PATH before calling the "alias" built-in since

some

?X: systems like HP-UX have a binary called /bin/alias.

```
if (PATH=.; alias -x) >/dev/null 2>&1; then
```

```
inksh=true
```

```
fi
```

?X: On HP-UX, large Configure scripts may exercise a bug in /bin/sh, use ksh

```
if test -f /hp-ux -a -f /bin/ksh; then
```

```
needksh='to avoid sh bug in "here document" expansion'
```

```
fi
```

?X: On AIX4, /bin/sh is really ksh and it causes problems, use sh

```
if test -d /usr/lpp -a -f /usr/bin/bsh -a -f /usr/bin/uname; then
```

```
if test X`/usr/bin/uname -v` = X4; then
```

```
avoidksh="to avoid AIX 4's /bin/sh"
```

```
newsh=/usr/bin/bsh
```

```

fi
fi
?X: On Digital UNIX, /bin/sh may start up buggy /bin/ksh, use sh
if test -f /osf_boot -a -f /usr/sbin/setld; then
if test X`/usr/bin/uname -s` = XOSF1; then
  avoidksh="to avoid Digital UNIX' ksh"
  newsh=/bin/sh
?X: if BIN_SH is set to 'xpg4', sh will start up ksh
  unset BIN_SH
fi
fi
?X: If we are not in ksh and need it, then feed us back to it
case "$inksh/$needksh" in
/[a-z]*)
?X: Clear ENV to avoid any ~/.kshrc that could alias cd or whatever...
?X: Don't
  use "unset ENV", that is not portable enough
  ENV=""
  changesh=true
  reason="$needksh"
  ;;
esac
?X: If we are in ksh and must avoid it, then feed us back to a new shell
case "$inksh/$avoidksh" in
true/[a-z]*)
  changesh=true
  reason="$avoidksh"
  ;;
esac
?X: Warn them if they use ksh on other systems, which are those where
?X: we don't need ksh nor want to avoid it explicitly, yet are using it.
case "$inksh/$needksh-$avoidksh-" in
true/--)
  cat <<EOM
(I see you are using the Korn shell. Some ksh's blow up on $me,
mainly on older exotic systems. If yours does, try the Bourne shell instead.)
EOM
  ;;
esac
case "$changesh" in
true)
  export newsh
  echo "(Feeding myself to $newsh $reason.)"
?X: Make sure they didn't say sh <Configure by checking whether $0 ends
?X: with Configure or not. If they did say sh <././Configure, then too
?X: bad for them anyway, since we lost that path indication...
?X: Otherwise, execing $0 ensures we keep the full remote source dir
?X: indication for src.U.

```

```

case
"$0" in
Configure|*/Configure) exec $newsh $0 "$@";;
*) exec $newsh Configure "$@";;
esac
;;
esac

```

?X: Unset CDPATH to avoid surprises when using cd under some shells
?X: Can't unset it because that's not portable to very old shells.
?X: Can't set it to " because then bash 2.02 won't do "cd UU" --AD 6/98.
?X: Don't want to set it to '.' because then ksh prints out the
?X: name of the directory every time you cd to it. --AD 6/98
?X: In order to inflict the least harm, change it only if it's set.
: if needed, set CDPATH to a harmless value that is not chatty

```

case "$CDPATH" in
") ;;
*) case "$SHELL" in
*bash*) CDPATH='.' ;;
*) CDPATH="" ;;
esac
;;
esac

```

: Configure runs within the UU subdirectory
test -d UU || mkdir UU
?X: Use ./* to avoid any confirmation prompts from enhanced shells -- WED
cd UU && rm -f ./*

Found in path(s):

```

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/Head.U

```

No license file was found, but licenses were detected in source scan.

```

?RCS: $Id$
?RCS:
?RCS: Copyright (c) 1998 Jarkko Hietaniemi
?RCS:
?RCS: You may distribute under the terms of either the GNU General Public
?RCS: License or the Artistic License, as specified in the README file.
?RCS:
?MAKE:d_dbm64 d_dbmclose64 d_fetch64 d_store64 d_delete64 \
d_firstkey64 d_nextkey64: Inlibc use64bitint Setvar test
?MAKE: -pick add $@ %<
?S:d_dbm64:
?S: This variable conditionally defines the HAS_DBM64 symbol, which
?S: indicates to the C program that the dbm64() routine is available.
?S:

```

?S:d_dbmclose64:

?S: This variable conditionally defines the HAS_DBMCLOSE64 symbol, which

?S: indicates to the C program that the dbmclose64() routine is available.

?S:.

?S:d_fetch64:

?S: This variable conditionally defines the HAS_FETCH64 symbol, which

?S: indicates to the C program that the fetch64() routine is available.

?S:.

?S:d_delete64:

?S: This variable conditionally defines the HAS_DELETE64

symbol, which

?S: indicates to the C program that the delete64() routine is available.

?S:.

?S:d_store64:

?S: This variable conditionally defines the HAS_STORE64 symbol, which

?S: indicates to the C program that the store64() routine is available.

?S:.

?S:d_firstkey64:

?S: This variable conditionally defines the HAS_FIRSTKEY64 symbol, which

?S: indicates to the C program that the firstkey64() routine is available.

?S:.

?S:d_nextkey64:

?S: This variable conditionally defines the HAS_NEXTKEY64 symbol, which

?S: indicates to the C program that the nextkey64() routine is available.

?S:.

?C:HAS_DBMINIT64:

?C: This symbol, if defined, indicates that the dbmininit64 routine is

?C: available to open dbm files larger than 2 gigabytes.

?C:.

?C:HAS_DBMCLOSE64:

?C: This symbol, if defined, indicates that the dbmclose64 routine is

?C: available to close dbm files larger than 2 gigabytes.

?C:.

?C:HAS_FETCH64:

?C: This symbol, if defined, indicates that the fetch64 routine is

?C: available to fetch

from dbm files larger than 2 gigabytes.

?C:.

?C:HAS_STORE64:

?C: This symbol, if defined, indicates that the store64 routine is

?C: available to store to dbm files larger than 2 gigabytes.

?C:.

?C:HAS_DELETE64:

?C: This symbol, if defined, indicates that the delete64 routine is

?C: available to delete from dbm files larger than 2 gigabytes.

?C:.

?C:HAS_FIRSTKEY64:

?C: This symbol, if defined, indicates that the firstkey64 routine is

```

?C: available to firstkey in dbm files larger than 2 gigabytes.
?C:.
?C:HAS_NEXTKEY64:
?C: This symbol, if defined, indicates that the nextkey64 routine is
?C: available to nextkey in dbm files larger than 2 gigabytes.
?C:.
?H:#$d_dbminit64 HAS_DBMINIT64 /**/
?H:#$d_dbmclose64 HAS_DBMCLOSE64 /**/
?H:#$d_fetch64 HAS_FETCH64 /**/
?H:#$d_store64 HAS_STORE64 /**/
?H:#$d_delete64 HAS_DELETE64 /**/
?H:#$d_firstkey64 HAS_FIRSTKEY64 /**/
?H:#$d_nextkey64 HAS_NEXTKEY64 /**/
?H:.
?T:xxx
?LINT:set d_dbminit64
?LINT:set d_dbmclose64
?LINT:set d_fetch64
?LINT:set
d_store64
?LINT:set d_delete64
?LINT:set d_firstkey64
?LINT:set d_nextkey64
: Check if DBM has 64bit functions
if $test X"$use64bitint" = X"$define"; then
: see if dbminit64 exists
set dbminit64 d_dbminit64
eval $inlibc

: see if dbmclose64 exists
set dbmclose64 d_dbmclose64
eval $inlibc

: see if fetch64 exists
set fetch64 d_fetch64
eval $inlibc

: see if store64 exists
set store64 d_store64
eval $inlibc

: see if delete64 exists
set delete64 d_delete64
eval $inlibc

: see if firstkey64 exists
set firstkey64 d_firstkey64
eval $inlibc

```

```

: see if nextkey64 exists
set nextkey64 d_nextkey64
eval $inlibc
else
val="$undef"
for xxx in d_dbminit64 d_dbmclose64 d_fetch64 d_store64 d_delete64 d_firstkey64 d_nextkey64
do
set $xxx
eval $setvar
done
fi

```

Found in path(s):

```

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/perl/dbm64.U

```

No license file was found, but licenses were detected in source scan.

```

?RCS: $Id: package.U 1 2006-08-24 12:32:52Z rmanfredi $
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: $Log: package.U,v $
?RCS: Revision 3.0.1.3 1994/10/29 16:27:21 ram
?RCS: patch36: beware of non-ascii character sets when translating case
?RCS:
?RCS: Revision 3.0.1.2 1993/11/10 17:37:02 ram
?RCS: patch14: skip definition of spackage if not otherwise used
?RCS:
?RCS: Revision 3.0.1.1 1993/09/13 16:11:10 ram
?RCS: patch10: added spackage, suitable for starting sentences
?RCS:
?RCS: Revision 3.0 1993/08/18 12:09:28 ram
?RCS: Baseline for dist 3.0
netwide release.
?RCS:
?MAKE:package spackage: Nothing
?MAKE: -pick wipe $@ %<
?S:package:
?S: This variable contains the name of the package being constructed.
?S: It is primarily intended for the use of later Configure units.
?S:.

```

```

?S:spackage:
?S: This variable contains the name of the package being constructed,
?S: with the first letter uppcased, i.e. suitable for starting
?S: sentences.
?S:.
?X: dist-4 has defined PACKAGE: here, which clashes with perly.h
?X: as package is a reserved keyword in perl
?T:first last
: set package name
package='<PACKAGENAME>'
@if spackage
first=`echo $package | sed -e 's/^(.).*\1/'`
last=`echo $package | sed -e 's/^(.*)\1/'`
?X:
?X: So early in the Configure script, we don't have ./tr set up and can't
?X: include Tr in our dependency or that would create a cycle. Therefore,
?X: we have to somehow duplicate the work done in Tr. That's life.
?X:
case "`echo AbyZ | tr '[:lower:]' '[:upper:]' 2>/dev/null`"-`echo AbyZ | tr '[:upper:]' '[:lower:]'
2>/dev/null`" in
ABYZ-abyz) spackage=`echo $first | tr '[:lower:]' '[:upper:]'`$last;;
*) spackage=`echo $first | tr '[a-z]' '[A-Z]'`$last;;
esac
@end

```

Found in path(s):

```

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/modified/package.U

```

No license file was found, but licenses were detected in source scan.

```

?RCS: $Id: Inlibc.U 1 2006-08-24 12:32:52Z rmanfredi $
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: $Log: Inlibc.U,v $
?RCS: Revision 3.0.1.1 1994/10/29 15:55:08 ram
?RCS: patch36: call ./whoa explicitly instead of relying on PATH
?RCS:
?RCS: Revision 3.0 1993/08/18 12:05:03 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?X:

```

?X: This unit checks for the definition of a given function.

?X:

?X: To use it, say:

?X: set function d_func

?X: eval \$inlibc

?X:

?MAKE:Inlibc: Csym Whoa Oldconfig

?MAKE: -pick add \$@ %<

?LINT:define inlibc

?V:inlibc

?S:inlibc:

?S: This

shell variable is used internally by Configure to check

?S: whether a given function is defined or not. A typical use is:

?S: set function d_func

?S: eval \$inlibc

?S: That will print a message, saying whether function was found or

?S: not and set d_func accordingly.

?S:.

?T:was tx sym tres td tu var

: define an is-in-libc? function

inlibc='echo " "; td=\$define; tu=\$undef;

sym=\$1; var=\$2; eval "was=\\$2";

tx=yes;

case "\$reuseval\$was" in

true) ;;

true*) tx=no;;

esac;

case "\$tx" in

yes)

set \$sym tres -f;

eval \$csym;

case "\$tres" in

true)

echo "\$sym() found." >&4;

case "\$was" in \$undef) ./whoa; esac; eval "\$var=\\$td";;

*)

echo "\$sym() NOT found." >&4;

case "\$was" in \$define) ./whoa; esac; eval "\$var=\\$tu";;

esac;;

*)

case "\$was" in

\$define) echo "\$sym() found." >&4;;

*) echo "\$sym() NOT found." >&4;;

esac;;

esac'

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/Inlibc.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: sbrktype.U 1 2006-08-24 12:32:52Z rmanfredi $
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: $Log: sbrktype.U,v $
?RCS: Revision 3.0 1993/08/18 12:09:43 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:sbrktype: Myread Oldconfig Loc contains Findhdr
?MAKE: -pick add $@ %<
?S:sbrktype:
?S: This variable defines sbrktype to be something like caddr_t, char *,
?S: or whatever type is used to declare sbrk() in the kernel.
?S:.
?C:Caddr_t (SBRKTYPE):
?C: This symbol holds the type of a core address. It is intended to be used
?C: to safely
?C: declare the return type of system calls like sbrk(). It might
?C: be necessary to include <sys/types.h> as well.
?C:.
?H:#define Caddr_t $sbrktype /* <core address> type */
?H:.
: see what type sbrk is declared as in the kernel
case "$sbrktype" in
")
if $contains 'caddr_t;' `./findhdr sys/types.h` >/dev/null 2>&1 ; then
dflt='caddr_t';
else
dflt='char *';
fi
;;
*) dflt="$sbrktype"
;;
esac
echo " "
rp="What is the return type of sbrk() on this system?"
./myread
sbrktype="$ans"
```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/sbrktype.U
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_gethostent_r.U,v 0RCS:

?RCS: Copyright (c) 2002,2003 Jarkko Hietaniemi

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?RCS: Generated by the reentr.pl from the Perl 5.8 distribution.

?RCS:

?MAKE:d_gethostent_r gethostent_r_proto: Inlibc Protochk Hasproto i_systypes \
 usethreads i_netdb extern_C

?MAKE: -pick add \$@ %<

?S:d_gethostent_r:

?S: This variable conditionally defines the HAS_GETHOSTENT_R symbol,

?S: which indicates to the C program that the gethostent_r()

?S: routine is available.

?S:.

?S:gethostent_r_proto:

?S: This variable encodes the prototype of gethostent_r.

?S: It is zero if d_gethostent_r is undef, and one of the

?S: REENTRANT_PROTO_T_ABC macros of reentr.h if d_gethostent_r

?S: is defined.

?S:.

?C:HAS_GETHOSTENT_R:

?C: This symbol, if defined, indicates that the gethostent_r routine

?C: is

available to gethostent re-entrantly.

?C:.

?C:GETHOSTENT_R_PROTO:

?C: This symbol encodes the prototype of gethostent_r.

?C: It is zero if d_gethostent_r is undef, and one of the

?C: REENTRANT_PROTO_T_ABC macros of reentr.h if d_gethostent_r

?C: is defined.

?C:.

?H:#\$d_gethostent_r HAS_GETHOSTENT_R /**/

?H:#define GETHOSTENT_R_PROTO \$gethostent_r_proto /**/

?H:.

?T:try hdrs d_gethostent_r_proto

: see if gethostent_r exists

set gethostent_r d_gethostent_r

eval \$inlibc

case "\$d_gethostent_r" in

"\$define")

```

hdrs="$i_systypes sys/types.h define stdio.h $i_netdb netdb.h"
case "$d_gethostent_r_proto:$usethreads" in
":define") d_gethostent_r_proto=define
set d_gethostent_r_proto gethostent_r $hdrs
eval $hasproto ;;
*) ;;
esac
case "$d_gethostent_r_proto" in
define)
case "$gethostent_r_proto" in
"|0) try='int gethostent_r(struct hostent*, char*, size_t, struct hostent**, int*);'
./prochck "$extern_C $try" $hdrs && gethostent_r_proto=I_SBWRE ;;
esac
case "$gethostent_r_proto"
in
"|0) try='int gethostent_r(struct hostent*, char*, int, int*);'
./prochck "$extern_C $try" $hdrs && gethostent_r_proto=I_SBIE ;;
esac
case "$gethostent_r_proto" in
"|0) try='struct hostent* gethostent_r(struct hostent*, char*, int, int*);'
./prochck "$extern_C $try" $hdrs && gethostent_r_proto=S_SBIE ;;
esac
case "$gethostent_r_proto" in
"|0) try='struct hostent* gethostent_r(struct hostent*, char*, int);'
./prochck "$extern_C $try" $hdrs && gethostent_r_proto=S_SBI ;;
esac
case "$gethostent_r_proto" in
"|0) try='int gethostent_r(struct hostent*, char*, int);'
./prochck "$extern_C $try" $hdrs && gethostent_r_proto=I_SBI ;;
esac
case "$gethostent_r_proto" in
"|0) try='int gethostent_r(struct hostent*, struct hostent_data*);'
./prochck "$extern_C $try" $hdrs && gethostent_r_proto=I_SD ;;
esac
case "$gethostent_r_proto" in
"|0) d_gethostent_r=undef
gethostent_r_proto=0
echo "Disabling gethostent_r, cannot determine prototype."
>&4 ;;
*) case "$gethostent_r_proto" in
REENTRANT_PROTO*) ;;
*) gethostent_r_proto="REENTRANT_PROTO_$gethostent_r_proto" ;;
esac
echo "Prototype: $try" ;;
esac
;;
*) case "$usethreads" in
define) echo "gethostent_r has no prototype, not using it." >&4 ;;

```

```

esac
d_gethostent_r=undef
gethostent_r_proto=0
;;
esac
;;
*) gethostent_r_proto=0
;;
esac

```

Found in path(s):

```

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/threads/d_gethostent_r.U

```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: d_sem.U,v \$

?RCS: Revision 3.0 1993/08/18 12:07:03 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?MAKE:d_sem: test d_semctl d_semget d_semop Setvar Findhdr osname

?MAKE: -pick add \$@ %<

?S:d_sem:

?S: This variable conditionally defines the HAS_SEM symbol, which

?S: indicates that the entire sem*(2) library is present.

?S:.

?C:HAS_SEM:

?C: This symbol, if defined, indicates that the entire sem*(2) library is

?C: supported.

?C:.

?H:#\$d_sem HAS_SEM /**/

?H:.

?T:h_sem

?LINT:set d_sem

:

see how much of the 'sem*(2)' library is present.

h_sem=true

echo " "

case "\$d_semctl\$d_semget\$d_semop" in

```

*$undef*) h_sem=false;;
esac
case "$osname" in
freebsd)
  case "`ipcs 2>&1`" in
  "SVID messages"*"not configured"*)
echo "Your $osname does not have the sem*(2) configured." >&4
  h_sem=false
val="$undef"
set semctl d_semctl
eval $setvar
set semget d_semget
eval $setvar
set semop d_semop
eval $setvar
;;
  esac
;;
esac
: we could also check for sys/ipc.h ...
if $h_sem && $test `./findhdr sys/sem.h`; then
echo "You have the full sem*(2) library." >&4
val="$define"
else
echo "You don't have the full sem*(2) library." >&4
val="$undef"
fi
set d_sem
eval $setvar

```

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/modified/d_sem.U

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/d_sem.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 2000 Jarkko Hietaniemi

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?MAKE:d_utimes: Inlibc

?MAKE: -pick add \$@ %<

?S:d_utimes:

?S: This variable conditionally defines the HAS_UTIMES symbol, which

?S: indicates to the C program that the utimes() routine is available.

?S:.

?C:HAS_UTIMES:

?C: This symbol, if defined, indicates that the utimes routine is

?C: available to do change file time stamps using struct timevals.

?C:.

?H:#\$d_utimes HAS_UTIMES /**/

?H:.

?LINT:set d_utimes

: see if utimes exists

set utimes d_utimes

eval \$inlibc

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_utimes.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: i_fcntl.U 1 2006-08-24 12:32:52Z rmanfredi \$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic Licence,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic Licence; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: i_fcntl.U,v \$

?RCS: Revision 3.0 1993/08/18 12:08:18 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?MAKE:i_fcntl: h_fcntl h_sysfile +i_sysfile Inhdr Setvar

?MAKE: -pick add \$@ %<

?S:i_fcntl:

?S: This variable controls the value of I_FCNTL (which tells

?S: the C program to include <fcntl.h>).

?S:.

?C:I_FCNTL (HDR_O_STUFF FCNTL):

?C: This manifest constant tells the C program to include <fcntl.h>.

?C:.

?H:#\$i_fcntl I_FCNTL /**/

?H:.

?T:val

?X:

Make line lists +i_sysfile to ensure tests for <sys/file.h> will be

?X: conducted prior tests for <fcntl.h>, hence making sure the h_sysfile

?X: variable is correctly set when we reach that unit.

```

?LINT:set i_fcctl
?LINT:use i_sysfile
?LINT:change h_fcctl
: see if fcctl.h is there
val=""
set fcctl.h val
eval $inhdr

: see if we can include fcctl.h
case "$val" in
"$define")
echo " "
if $h_fcctl; then
val="$define"
echo "We'll be including <fcctl.h>." >&4
else
val="$undef"
if $h_sysfile; then
echo "We don't need to include <fcctl.h> if we include <sys/file.h>." >&4
else
echo "We won't be including <fcctl.h>." >&4
fi
fi
;;
*)
h_fcctl=false
val="$undef"
;;
esac
set i_fcctl
eval $setvar

```

Found in path(s):

```

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/i_fcctl.U

```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: Original Author: Andy Dougherty <doughera@lafcol.lafayette.edu>

```

?RCS:
?RCS: $Log: d_dlopen.U,v $
?RCS: Revision 3.0.1.2 1995/07/25 13:52:56 ram
?RCS: patch56: force compile-link test since symbol might lie in crt0.o (ADO)
?RCS:
?RCS: Revision 3.0.1.1 1994/08/29 16:07:34 ram
?RCS: patch32: created by ADO
?RCS:
?MAKE:d_dlopen: Inlibc runnm
?MAKE: -pick add $@ %<
?S:d_dlopen:
?S: This variable conditionally defines the HAS_DLOPEN symbol, which
?S: indicates to the C program that the dlopen() routine
is available.
?S:.
?C:HAS_DLOPEN :
?C: This symbol, if defined, indicates that the dlopen routine is
?C: available.
?C:.
?H:#$d_dlopen HAS_DLOPEN /**/
?H:.
?T: xxx_runnm
?LINT:set d_dlopen
?X: We don't permanently change runnm, but we do temporarily.
?LINT: change runnm
: see if dlopen exists
?X: On NetBSD and FreeBSD, dlopen is available, but it is in
?X: /usr/lib/crt0.o, not in any of the libraries. Therefore, do not
?X: use the nm extraction, but use a real compile and link test instead.
xxx_runnm="$runnm"
runnm=false
set dlopen d_dlopen
eval $inlibc
runnm="$xxx_runnm"

```

Found in path(s):

```

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/d_dlopen.U

```

No license file was found, but licenses were detected in source scan.

```

?RCS: $Id$
?RCS:
?RCS: Copyright (c) 1999, Jarkko Hietaniemi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root

```

?RCS: of the source tree for dist 3.0.
?RCS:
?MAKE:d_sem_getvalue: Inlibc
?MAKE: -pick add \$@ %<
?S:d_sem_getvalue:
?S: This variable conditionally defines HAS_SEM_GETVALUE if sem_getvalue()
?S: is available to get the value of a POSIX semaphore.
?S:.
?C:HAS_SEM_GETVALUE:
?C: This symbol, if defined, indicates that the sem_getvalue system call is
?C: available to get the value of a POSIX semaphore.
?C:.
?H:#\$d_sem_getvalue HAS_SEM_GETVALUE /**/
?H:.
?LINT:set d_sem_getvalue
: see if sem_getvalue exists
set sem_getvalue d_sem_getvalue
eval \$inlibc

Found in path(s):

*

/opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_sem_getvalue.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$
?RCS:
?RCS: Copyright (c) 1999, Jarkko Hietaniemi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 3.0.
?RCS:
?MAKE:d_mq_send: Inlibc
?MAKE: -pick add \$@ %<
?S:d_mq_send:
?S: This variable conditionally defines HAS_MQ_SEND if mq_send() is
?S: available to send a message to a POSIX message queue.
?S:.
?C:HAS_MQ_SEND:
?C: This symbol, if defined, indicates that the mq_send system call is
?C: available to send a message to a POSIX message queue.
?C:.
?H:#\$d_mq_send HAS_MQ_SEND /**/
?H:.
?LINT:set d_mq_send

```
: see if mq_send exists
set mq_send d_mq_send
eval $inlibc
```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/perl/d_mq_send.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: d_cbrt.U 1 2006-08-24 12:32:52Z rmanfredi $
```

```
?RCS:
```

```
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
```

```
?RCS:
```

```
?RCS: You may redistribute only under the terms of the Artistic Licence,
```

```
?RCS: as specified in the README file that comes with the distribution.
```

```
?RCS: You may reuse parts of this distribution only within the terms of
```

```
?RCS: that same Artistic Licence; a copy of which may be found at the root
```

```
?RCS: of the source tree for dist 4.0.
```

```
?RCS:
```

```
?RCS: $Log: d_cbrt.U,v $
```

```
?RCS: Revision 3.0 1993/08/18 12:05:48 ram
```

```
?RCS: Baseline for dist 3.0 netwide release.
```

```
?RCS:
```

```
?MAKE:d_cbrt: Inlibc
```

```
?MAKE: -pick add $@ %<
```

```
?S:d_cbrt:
```

```
?S: This variable conditionally defines the HAS_CBRT symbol, which
```

```
?S: indicates to the C program that the cbrt() (cube root) function
```

```
?S: is available.
```

```
?S:.
```

```
?C:HAS_CBRT (CBRT):
```

```
?C: This symbol, if defined, indicates that the cbrt() (cube root)
```

```
?C: function is available.
```

```
?C:.
```

```
?H:#$d_cbrt HAS_CBRT /**/
```

```
?H:.
```

```
?LINT:set
```

```
  d_cbrt
```

```
: see if cbrt exists
```

```
set cbrt d_cbrt
```

```
eval $inlibc
```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/d_cbrt.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: Findhdr.U,v 3.0.1.2 1994/10/29 15:53:08 ram Exp $
```

```

?RCS:
?RCS: Copyright (c) 1991-1993, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 3.0.
?RCS:
?RCS: Original Author: Thomas Neumann <tom@smart.bo.open.de>
?RCS:
?RCS: $Log: Findhdr.U,v $
?RCS: Revision 3.0.1.2 1994/10/29 15:53:08 ram
?RCS: patch36: added ?F: line for metalint file checking
?RCS:
?RCS: Revision 3.0.1.1 1994/05/06 14:03:56 ram
?RCS: patch23: cppminus must be after other cppflags, not before
?RCS:
?RCS: Revision 3.0 1993/08/18 12:04:54 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?X:
?X: This unit produces a findhdr script which
is used to locate the header
?X: files in $usrinc or other stranger places using cpp capabilities. The
?X: script is given an include file base name, like 'stdio.h' or 'sys/file.h'
?X: and it returns the full path of the include file and a zero status or an
?X: empty string with an error status if the file could not be located.
?X:
?MAKE:Findhdr: grep test tr rm incpth awk cat startsh \
cppstdin cppminus +cppflags osname
?MAKE: -pick add $@ %<
?LINT:extern cppfilter
?LINT:define fieldn
?S:fieldn:
?S: This variable is used internally by Configure. It contains the position
?S: of the included file name in cpp output. That is to say, when cpp
?S: pre-processes a #include <file> line, it replaces it by a # line which
?S: contains the original position in the input file and the full name of
?S: included file, between "quotes".
?S:.
?V:fieldn
?F:./findhdr !fieldn
?T:cline pos wanted name awkprg usrincdir status testaccess
:determine filename position in cpp output
echo " "
echo "Computing

```

```

filename position in cpp output for #include directives..." >&4
case "$osname" in
amigaos) fieldn=3 ;; # Workaround for a bug in abc (pdksh).
esac
case "$fieldn" in
")
case "$osname" in
vos) testaccess=-e ;;
*) testaccess=-r ;;
esac
echo '#include <stdio.h>' > foo.c
$cat >fieldn <<EOF
$startsh
$cpptest $cpptest $cpptest <foo.c 2>/dev/null | \
$grep '^[ ]*#.*stdio.h' | \
while read cline; do
pos=1
set \ $cline
while $test $# -gt 0; do
if $test $testaccess \ `echo \ $1 | $tr -d ""`; then
echo "\ $pos"
exit 0
fi
shift
pos=\ `expr \ $pos + 1`
done
done
EOF
chmod +x fieldn
fieldn=`./fieldn`
$rm -f foo.c fieldn
;;
esac
case $fieldn in
") pos='???';;
1) pos=first;;
2) pos=second;;
3) pos=third;;
*) pos="{fieldn}th";;
esac
echo "Your cpp writes the filename in the $pos field of the line."

```

?X: To locate a header file, we cannot simply check for \$usrinc/file.h, since
?X: some machine have the headers in weird places and our only hope is that
?X: the C pre-processor
will know how to find those headers. Thank you Next!
: locate header file
\$cat >findhdr <<EOF

```

$startsh
wanted=\$1
name=""
for usrinmdir in $incpth
do
if test -f \$usrinmdir/\$wanted; then
echo "\$usrinmdir/\$wanted"
exit 0
fi
done
awkprg='{ print \$$fieldn }'
echo "#include <\$wanted>" > foo\$\$.c
$cpptest $cpptestminus $cpptestflags < foo\$\$.c 2>/dev/null | \
$cpptestfilter $grep "^[ ]*#.*\$wanted" | \
while read cline; do
name=\`echo \$cline | $awk "\$awkprg" | $str -d ""\`
case "\$name" in
*[\^\\]\$wanted) echo "\$name"; exit 1;;
*[\^\\]\$wanted) echo "\$name"; exit 1;;
*) exit 2;;
esac;
done;
#
# status = 0: grep returned 0 lines, case statement not executed
# status = 1: headerfile found
# status = 2: while loop executed, no headerfile found
#
status=\$?
$rm -f foo\$\$.c;
if test \$status -eq 1; then
exit 0;
fi
exit 1
EOF
chmod +x findhdr

```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/modified/Findhdr.U
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: orgname.U 1 2006-08-24 12:32:52Z rmanfredi \$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic Licence,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: \$Log: orgname.U,v \$
?RCS: Revision 3.0.1.1 1993/09/13 16:10:25 ram
?RCS: patch10: added support for /local/src to the search (WAD)
?RCS:
?RCS: Revision 3.0 1993/08/18 12:09:27 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:orgname: sed cat Myread Loc Oldconfig
?MAKE: -pick add \$@ %<
?S:orgname:
?S: This variable contains the eventual value of the ORGNAME symbol,
?S: which contains either the organization name or the full pathname
?S: of
a file containing the organization name.
?S:.
?C:ORGNAME:
?C: This symbol contains either the organization name or the full pathname
?C: of a file containing the organization name, which the program must
?C: be prepared to open and substitute the contents of.
?C:.
?H:#define ORGNAME "\$orgname" /**/
?H:.
?T:longshots xxx
: get organization name
longshots='/local/src /usr/src/new /usr/src/local /usr/local/src'
case "\$orgname" in
*) if xxx=`./loc news/src/defs.h x \$longshots`; then
dflt=`\$sed -n 's/^.*MYORG[]*"(.*)"'.*/\1/p' \$xxx`
else
dflt="
fi
;;
*) dflt="\$orgname";;
esac
\$cat << 'EOH'

Please type the name of your organization as you want it to appear on the
Organization line of outgoing articles. (It's nice if this also specifies
your location. Your city name is probably sufficient if well known.)
For example:

University of Southern North Dakota, Hoople

You may also put the name of a file, as long as it begins with a slash.
For example:

/etc/organization

EOH

```
orgname=""
while
test "X$orgname" = "X"; do
rp='Organization:'
. ./myread
orgname="$ans"
done
```

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/orgname.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: i_sysutsname.U,v \$

?RCS:

?RCS: Copyright (c) 2000 Jarkko Hietaniemi

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?MAKE:i_sysutsname: Inhdr Hasfield

?MAKE: -pick add \$@ %<

?S:i_sysutsname:

?S: This variable conditionally defines the I_SYSUTSNAME symbol,

?S: and indicates whether a C program should include <sys/utsname.h>.

?S:.

?C:I_SYSUTSNAME:

?C: This symbol, if defined, indicates that <sys/utsname.h> exists and

?C: should be included.

?C:.

?H:#\$i_sysutsname I_SYSUTSNAME /**/

?H:.

?LINT:set i_sysutsname

: see if this is a sys/utsname.h system

set sys/utsname.h i_sysutsname

eval \$inhdr

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/i_sysutsname.U

No license file was found, but licenses were detected in source scan.

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:
?MAKE:d_lrintl: Inlibc
?MAKE: -pick add \$@ %<
?S:d_lrintl:
?S: This variable conditionally defines the HAS_LRINTL symbol, which
?S: indicates to the C program that the lrintl() routine is available
?S: to return the integral value closest to a long double (according
?S: to the current rounding mode).
?S:.
?C:HAS_LRINTL:
?C: This symbol, if defined, indicates that the lrintl routine is
?C: available to return the integral value closest to a long double
?C: (according to the current rounding mode).
?C:.
?H:#\$d_lrintl HAS_LRINTL /**/
?H:.
?LINT:set d_lrintl
: see if lrintl exists
set lrintl d_lrintl
eval \$inlibc

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_lrintl.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: vendorman3.U,v 1.1 1999/07/08 18:32:57 doughera Exp doughera \$

?RCS:

?RCS: Copyright (c) 1999-2000, Andy Dougherty

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 3.0.

?RCS:

?RCS: \$Log: vendorman3.U,v \$

?RCS: Revision 1.1 1999/07/08 18:32:57 doughera

?RCS: Initial revision

?RCS:

?MAKE:vendorman3 vendorman3exp installvendorman3: man3dir Getfile \

Oldconfig Setprefixvar Prefixit test vendorprefix prefix sed

?MAKE: -pick add \$@ %<

?Y:TOP

?S:vendorman3:

?S: This variable contains the name of the directory for man3

?S: pages. It may have a ~ on the front.

?S: The standard distribution will put nothing in this directory.

?S: Vendors
 who distribute perl may wish to place their own
 ?S: man3 pages in this directory with
 ?S: MakeMaker Makefile.PL INSTALLDIRS=vendor
 ?S: or equivalent. See INSTALL for details.
 ?S:.
 ?S:vendorman3exp:
 ?S: This variable is the ~name expanded version of vendorman3, so that you
 ?S: may use it directly in Makefiles or shell scripts.
 ?S:.
 ?D:installvendorman3="
 ?S:installvendorman3:
 ?S: This variable is really the same as vendorman3exp but may differ on
 ?S: those systems using AFS. For extra portability, only this variable
 ?S: should be used in makefiles.
 ?S:.
 ?LINT:change prefixvar
 ?LINT:set installvendorman3
 : Set the vendorman3 variables
 case "\$vendorprefix" in
 ") vendorman3="
 vendorman3exp="
 ;;
 *) : determine where vendor-supplied module manual pages go.
 case "\$vendorman3" in
 ") dflt=`echo "\$man3dir" | \$sed "s#^\$prefix#\$vendorprefix#"` ;;
 *) dflt=\$vendorman3 ;;
 esac
 case "\$dflt" in
 "|") dflt=none ;;
 esac
 fn=nd~+
 rp='Pathname for the vendor-supplied manual section 3
 pages'
 ./getfile
 vendorman3="\$ans"
 vendorman3exp="\$ansexp"
 ;;
 esac
 : Use ' ' for none so value is preserved next time through Configure
 \$test X"\$vendorman3" = "X" && vendorman3=' '
 prefixvar=vendorman3
 ./installprefix

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/installdirs/vendorman3.U

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id$
?RCS:
?RCS: Copyright (c) 1998 Jarkko Hietaniemi
?RCS:
?RCS: You may distribute under the terms of either the GNU General Public
?RCS: License or the Artistic License, as specified in the README file.
?RCS:
?MAKE:usemultiplicity: useithreads Myread Oldconfig Setvar
?MAKE: -pick add $@ %<
?Y:TOP
?S:usemultiplicity:
?S: This variable conditionally defines the MULTIPLICITY symbol,
?S: and indicates that Perl should be built to use multiplicity.
?S:.
?C:MULTIPLICITY:
?C: This symbol, if defined, indicates that Perl should
?C: be built to use multiplicity.
?C:.
?H:?%<:#ifndef MULTIPLICITY
?H:?%<:#$usemultiplicity MULTIPLICITY /**/
?H:?%<:#endif
?H:.
?LINT:set usemultiplicity
?INIT:: set usemultiplicity on the Configure command line to enable multiplicity.
: Check if multiplicity is required
?X: We should really have some explanatory text here, and some
?X: automatic setting of sensible defaults.
cat <<EOM
```

Perl

can be built so that multiple Perl interpreters can coexist
within the same Perl executable.

EOM

```
case "$useithreads" in
```

```
$define)
```

```
cat <<EOM
```

This multiple interpreter support is required for interpreter-based threads.

EOM

```
val="$define"
```

```
::
```

```
*) case "$usemultiplicity" in
```

```
$define[true|[yY]*) dflt='y';;
```

```
*) dflt='n';;
```

```
esac
```

```
echo " "
```

```
echo "If this doesn't make any sense to you, just accept the default '$dflt'."
rp='Build Perl for multiplicity?'
. ./myread
case "$ans" in
y|Y) val="$define" ;;
*)   val="$undef" ;;
esac
;;
esac
set usemultiplicity
eval $setvar
```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/usemultiplicity.U
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 2000 Jarkko Hietaniemi

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?MAKE:d_lutimes: Inlibc

?MAKE: -pick add \$@ %<

?S:d_lutimes:

?S: This variable conditionally defines the HAS_LUTIMES symbol, which

?S: indicates to the C program that the lutimes() routine is available.

?S:.

?C:HAS_LUTIMES:

?C: This symbol, if defined, indicates that the lutimes routine is

?C: available to change symbolic link timestamps with struct timevals.

?C:.

?H:#\$d_lutimes HAS_LUTIMES /**/

?H:.

?LINT:set d_lutimes

: see if lutimes exists

set lutimes d_lutimes

eval \$inlibc

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_lutimes.U
```

No license file was found, but licenses were detected in source scan.

/*

* \$Id: setsid.C,v 3.0.1.1 1994/01/24 13:58:47 ram Exp ram \$

```

*
* Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
*
* You may redistribute only under the terms of the Artistic Licence,
* as specified in the README file that comes with the distribution.
* You may reuse parts of this distribution only within the terms of
* that same Artistic Licence; a copy of which may be found at the root
* of the source tree for dist 4.0.
*
* $Log: setsid.C,v $
* Revision 3.0.1.1 1994/01/24 13:58:47 ram
* patch16: created
*
*/

```

Found in path(s):

```

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/lib/C/fake/setsid.C

```

No license file was found, but licenses were detected in source scan.

```

?RCS: $Id: byteorder.U,v 3.0.1.2 1997/02/28 15:24:55 ram Exp $
?RCS:
?RCS: Copyright (c) 1991-1993, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 3.0.
?RCS:
?RCS: $Log: byteorder.U,v $
?RCS: Revision 3.0.1.2 1997/02/28 15:24:55 ram
?RCS: patch61: no longer ask the user if the test runs ok
?RCS:
?RCS: Revision 3.0.1.1 1994/10/29 16:02:58 ram
?RCS: patch36: added ?F: line for metalint file checking
?RCS:
?RCS: Revision 3.0 1993/08/18 12:05:28 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:byteorder: cat Myread Oldconfig Loc Compile rm_try run \
multiarch uvtype uvsize i_stdlib
?MAKE: -pick add $@ %<
?S:byteorder:
?S: This
variable holds the byte order in a UV. In the following,
?S: larger digits indicate more significance. The variable byteorder
?S: is either 4321 on a big-endian machine, or 1234 on a little-endian,

```

?S: or 87654321 on a Cray ... or 3412 with weird order !

?S:.

?C:BYTEORDER:

?C: This symbol holds the hexadecimal constant defined in byteorder,

?C: in a UV, i.e. 0x1234 or 0x4321 or 0x12345678, etc...

?C: If the compiler supports cross-compiling or multiple-architecture

?C: binaries, use compiler-defined macros to

?C: determine the byte order.

?C:.

```
?H:%<:#if defined(MULTIARCH)
?H:%<:# ifdef __LITTLE_ENDIAN__
?H:%<:# if LONGSIZE == 4
?H:%<:# define BYTEORDER 0x1234
?H:%<:# else
?H:%<:# if LONGSIZE == 8
?H:%<:# define BYTEORDER 0x12345678
?H:%<:# endif
?H:%<:# endif
?H:%<:# else
?H:%<:# ifdef __BIG_ENDIAN__
?H:%<:# if LONGSIZE == 4
?H:%<:# define BYTEORDER 0x4321
?H:%<:# else
?H:%<:# if LONGSIZE
== 8
?H:%<:# define BYTEORDER 0x87654321
?H:%<:# endif
?H:%<:# endif
?H:%<:# endif
?H:%<:#endif
?H:.
```

?T:xxx_prompt

?F:!try

: check for ordering of bytes in a UV

```
echo " "
case "$multiarch" in
*$define*)
$cat <<EOM
```

You seem to be doing a multiarchitecture build,
skipping the byteorder check.

```
EOM
byteorder='ffff'
;;
*)
```

```
case "$byteorder" in
")
```

```
$cat <<'EOM'
```

In the following, larger digits indicate more significance. A big-endian machine like a Pyramid or a Motorola 680?0 chip will come out to 4321. A little-endian machine like a Vax or an Intel 80?86 chip would be 1234. Other machines may have weird orders like 3412. A Cray will report 87654321, an Alpha will report 12345678. If the test program works the default is probably right.

I'm now running the test program...

```
EOM
```

```
$cat >try.c <<EOCP
```

```
#include <stdio.h>
```

```
#$i_stdlib I_STDLIB
```

```
#ifdef I_STDLIB
```

```
#include <stdlib.h>
```

```
#endif
```

```
#include
```

```
<sys/types.h>
```

```
typedef $uvtype UV;
```

```
int main()
```

```
{
```

```
int i;
```

```
union {
```

```
UV l;
```

```
char c[$uvsize];
```

```
} u;
```

```
if ($uvsize > 4)
```

```
u.l = (((UV)0x08070605) << 32) | (UV)0x04030201;
```

```
else
```

```
u.l = (UV)0x04030201;
```

```
for (i = 0; i < $uvsize; i++)
```

```
printf("%c", u.c[i]+'0');
```

```
printf("\n");
```

```
exit(0);
```

```
}
```

```
EOCP
```

```
xxx_prompt=y
```

```
set try
```

```
if eval $compile && $run ./try > /dev/null; then
```

```
dflt=`$run ./try`
```

```
case "$dflt" in
```

```
[1-4][1-4][1-4][1-4]|12345678|87654321)
```

```
echo "(The test program ran ok.)"
```

```
echo "byteorder=$dflt"
```

```
xxx_prompt=n
```

```
::
```

```

????|?????) echo "(The test program ran ok.)" ;;
*) echo "(The test program didn't run right for some reason.)" ;;
esac
else
dflt='4321'
cat <<'EOM'

```

(I can't seem to compile the test program. Guessing big-endian...)

```

EOM
fi
case "$xxx_prompt" in
y)
rp="What is the order of bytes in $svtype?"
./myread
byteorder="$ans"
;;
*) byteorder=$dflt
;;
esac
;;
esac
$rm_try
;;
esac

```

Found in path(s):

*

/opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/compline/byteorder.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 2001 Jarkko Hietaniemi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 3.0.

?RCS:

?MAKE:d_sresgproto: Hasproto i_unistd

?MAKE: -pick add \$@ %<

?S:d_sresgproto:

?S: This variable conditionally defines the HAS_SETRESGID_PROTO symbol,

?S: which indicates to the C program that the system provides

?S: a prototype for the setresgid() function. Otherwise, it is

?S: up to the program to supply one.

?S:.

?C:HAS_SETRESGID_PROTO:
 ?C: This symbol, if defined, indicates that the system provides
 ?C: a prototype for the setresgid() function. Otherwise, it is up
 ?C: to the program to supply one. Good guesses are
 ?C: extern
 int setresgid(uid_t ruid, uid_t euid, uid_t suid);
 ?C:.
 ?H:#\$d_sresgproto HAS_SETRESGID_PROTO /**/
 ?H:.
 ?LINT:set d_sresgproto
 : see if prototype for setresgid is available
 echo " "
 set d_sresgproto setresgid \$i_unistd unistd.h
 eval \$hasproto

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_sresgproto.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$
 ?RCS:
 ?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
 ?RCS:
 ?RCS: You may redistribute only under the terms of the Artistic License,
 ?RCS: as specified in the README file that comes with the distribution.
 ?RCS: You may reuse parts of this distribution only within the terms of
 ?RCS: that same Artistic License; a copy of which may be found at the root
 ?RCS: of the source tree for dist 4.0.
 ?RCS:
 ?RCS: \$Log: d_setpgrp.U,v \$
 ?RCS: Revision 3.0.1.3 1997/02/28 15:44:16 ram
 ?RCS: patch61: obsoleted USE_BSDGRP in favor of USE_BSD_SETPGRP
 ?RCS: patch61: another unit now also defines a USE_BSD_GETPGRP
 ?RCS: patch61: fallback for test program failure improved
 ?RCS:
 ?RCS: Revision 3.0.1.2 1995/07/25 13:59:30 ram
 ?RCS: patch56: re-arranged compile line to include ldflags before objects
 ?RCS:
 ?RCS: Revision 3.0.1.1 1994/10/29 16:15:37 ram
 ?RCS: patch36: added 'ldflags' to the test compile line (ADO)
 ?RCS:
 patch36: call ./usg explicitly instead of relying on PATH
 ?RCS:
 ?RCS: Revision 3.0 1993/08/18 12:07:09 ram
 ?RCS: Baseline for dist 3.0 netwide release.
 ?RCS:
 ?MAKE:d_setpgrp d_bsdsetpgrp: cat rm +cc +libs +ccflags \

```

+ldflags Inlibc Guess Setvar i_unistd
?MAKE: -pick add $@ %<
?S:d_setpgrp:
?S: This variable conditionally defines HAS_SETPGRP if setpgrp() is
?S: available to set the current process group.
?S:.
?S:d_bsdsetpgrp (d_bsdpgrp):
?S: This variable conditionally defines USE_BSD_SETPGRP if
?S: setpgrp needs two arguments whereas USG one needs none.
?S: See also d_setpgid for a POSIX interface.
?S:.
?C:HAS_SETPGRP (SETPGRP):
?C: This symbol, if defined, indicates that the setpgrp routine is
?C: available to set the current process group.
?C:.
?C:USE_BSD_SETPGRP (USE_BSDPGRP BSDPGRP):
?C: This symbol, if defined, indicates that setpgrp needs two
?C: arguments whereas USG one needs none. See also HAS_SETPGID
?C: for a POSIX interface.
?C:.
?H:#$d_setpgrp HAS_SETPGRP /**/
?H:#$d_bsdsetpgrp
USE_BSD_SETPGRP /**/
?H:.
?F:!set.c !set
?T:xxx
?LINT:set d_setpgrp d_bsdsetpgrp
: see if setpgrp exists
set setpgrp d_setpgrp
eval $inlibc

@if USE_BSD_SETPGRP || d_bsdsetpgrp
case "$d_setpgrp" in
"$define")
echo " "
echo "Checking to see which flavor of setpgrp is in use..."
$cat >set.c <<EOP
#$_unistd I_UNISTD
#include <sys/types.h>
#ifdef I_UNISTD
# include <unistd.h>
#endif
int main()
{
if (getuid() == 0) {
printf("(I see you are running Configure as super-user...)\n");
setuid(1);
}
}

```

```

#ifdef TRY_BSD_PGRP
if (-1 == setpgrp(1, 1))
    exit(0);
#else
if (setpgrp() != -1)
    exit(0);
#endif
exit(1);
}
EOP
if $cc -DTRY_BSD_PGRP $ccflags $ldflags -o set set.c $libs >/dev/null 2>&1 && ./set; then
    echo 'You have to use setpgrp(pid,pgrp) instead of setpgrp().' >&4
    val="$define"
elif $cc $ccflags $ldflags -o set set.c $libs >/dev/null 2>&1 && ./set; then
    echo 'You have to use setpgrp() instead of setpgrp(pid,pgrp).' >&4
    val="$undef"
else
    echo "(I can't
    seem to compile and run the test program.)"
    if ./usg; then
        xxx="a USG one, i.e. you use setpgrp()."
    else
        # SVR4 systems can appear rather BSD-ish.
        case "$i_unistd" in
        $undef)
            xxx="a BSD one, i.e. you use setpgrp(pid,pgrp)."
            val="$define"
            ;;
        $define)
            xxx="probably a USG one, i.e. you use setpgrp()."
            val="$undef"
            ;;
        esac
    fi
    echo "Assuming your setpgrp is $xxx" >&4
fi
;;
*) val="$undef";;
esac
set d_bsdsetpgrp
eval $setvar
$rm -f set set.c
@end

```

Found in path(s):

```

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/d_setpgrp.U

```

No license file was found, but licenses were detected in source scan.

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?MAKE:d_round: Inlibc

?MAKE: -pick add \$@ %<

?S:d_round:

?S: This variable conditionally defines the HAS_ROUND symbol, which

?S: indicates to the C program that the round() routine is available.

?S:.

?C:HAS_ROUND:

?C: This symbol, if defined, indicates that the round routine is

?C: available to round to nearest integer, away from zero.

?C:.

?H:#\$d_round HAS_ROUND /**/

?H:.

?LINT:set d_round

: see if round exists

set round d_round

eval \$inlibc

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_round.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_static_inline.U,v \$

?RCS:

?RCS: Copyright (c) 2010 Andrew Dougherty

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 3.0.

?RCS:

?RCS: Original Author: Andy Dougherty <doughera@lafayette.edu>

?RCS:

?MAKE:d_static_inline perl_static_inline: Compile Setvar gccversion \

cat echo run hint rm rm_try

?MAKE: -pick add \$@ %<

?S:d_static_inline:

?S: This variable conditionally defines the HAS_STATIC_INLINE symbol,

?S: which indicates that the C compiler supports C99-style static

?S: inline. That is, the function can't be called from another

?S: translation unit.

?S:.

?S:perl_static_inline:
 ?S: This variable defines the PERL_STATIC_INLINE symbol to
 ?S: the best-guess incantation to use for static inline functions.
 ?S: Possibilities include
 ?S: static inline (c99)
 ?S: static __inline__ (gcc -ansi)
 ?S: static __inline (MSVC)
 ?S: static _inline (older MSVC)
 ?S: static (c89 compilers)
 ?S:.
 ?C:HAS_STATIC_INLINE :
 ?C: This symbol, if defined, indicates that the C compiler supports
 ?C: C99-style static inline. That is, the function can't be called
 ?C: from another translation unit.
 ?C:.
 ?C:PERL_STATIC_INLINE:
 ?C: This symbol gives the best-guess incantation to use for static
 ?C: inline functions. If HAS_STATIC_INLINE is defined, this will
 ?C: give C99-style inline. If HAS_STATIC_INLINE is not defined,
 ?C: this will give a plain 'static'. It will always be defined
 ?C: to something that gives static linkage.
 ?C: Possibilities include
 ?C: static inline (c99)
 ?C: static __inline__ (gcc -ansi)
 ?C: static __inline (MSVC)
 ?C: static _inline (older MSVC)
 ?C: static
 (c89 compilers)
 ?C:.
 ?H:#\$d_static_inline HAS_STATIC_INLINE /**/
 ?H:#define PERL_STATIC_INLINE \$perl_static_inline /**/
 ?H:.
 ?LINT:set d_static_inline
 ?T:inline xxx
 ?F:!try
 : see what flavor, if any, of static inline is supported
 echo " "
 echo "Checking to see if your system supports static inline..."
 ?X: Build two programs. The first uses static inline in file a.c and
 ?X: should work. The second also includes b.c which tries to link against
 ?X: the static function in a.c. This should fail.
 ?X:.
 \$cat > try.c <<'EOCP'
 #include <stdlib.h>
 extern int f_via_a(int x);
 extern int f_via_b(int x);
 int main(int argc, char **argv)

```

{
    int y;

    y = f_via_a(0);
#ifdef USE_B
    y = f_via_b(0);
#endif
    if (y == 42) {
        return EXIT_SUCCESS;
    }
    else {
        return EXIT_FAILURE;
    }
}
EOCP
$cat > a.c <<'EOCP'
static INLINE int f(int x) {
    int y;
    y = x + 42;
    return y;
}

int f_via_a(int x)
{
    return f(x);
}
EOCP
$cat > b.c <<'EOCP'
extern int f(int x);

int
f_via_b(int x)
{
    return f(x);
}
EOCP

# Respect a hint (or previous) value for perl_static_inline, if there is one.
case "$perl_static_inline" in
") # Check the various possibilities, and break out on success.
# For gcc, prefer __inline__, which will still permit
# cflags.SH to add in -ansi.
case "$gccversion" in
") xxx="__inline__ __inline__ __inline__ __inline__";
*) xxx="__inline__ inline __inline__ inline";
esac
for inline in $xxx; do
set try -DINLINE=$inline a.c

```

```

if eval $compile && $run ./try; then
# Now make sure there is no external linkage of static
# functions
set try -DINLINE=$inline -DUSE_B a.c b.c
if eval $compile && $run ./try; then
$echo "Your compiler supports static $inline, " >&4
$echo "but it also creates an external definition," >&4
$echo "so I won't use it." >&4
val=$undef
else
$echo "Your compiler supports static $inline." >&4
val=$define
perl_static_inline="static $inline";
break;
fi
else
$echo
"Your compiler does NOT support static $inline." >&4
val="$undef"
fi
done
;;
*inline*) # Some variant of inline exists.
echo "Keeping your $hint value of $perl_static_inline."
val=$define
;;
static) # No inline capabilities
echo "Keeping your $hint value of $perl_static_inline."
val=$undef
;;
*) # Unrecognized previous value -- blindly trust the supplied
# value and hope it makes sense. Use old value for
# d_static_inline, if there is one.
echo "Keeping your $hint value of $perl_static_inline."
case "$d_static_inline" in
") val=$define ;;
*) val=$d_static_inline ;;
esac
;;
esac
# Fallback to plain 'static' if nothing worked.
case "$perl_static_inline" in
")
perl_static_inline="static"
val=$undef
;;
esac
set d_static_inline

```

```
eval $setvar
$rm -f a.[co] b.[co]
$rm_try
```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/compline/d_static_inline.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: Loc_sed.U 1 2006-08-24 12:32:52Z rmanfredi $
```

```
?RCS:
```

```
?RCS: Copyright (c) 1996, Andy Dougherty
```

```
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
```

```
?RCS:
```

```
?RCS: You may redistribute only under the terms of the Artistic Licence,
```

```
?RCS: as specified in the README file that comes with the distribution.
```

```
?RCS: You may reuse parts of this distribution only within the terms of
```

```
?RCS: that same Artistic Licence; a copy of which may be found at the root
```

```
?RCS: of the source tree for dist 4.0.
```

```
?RCS:
```

```
?X: This is used in perl.c.
```

```
?MAKE:full_sed: sed
```

```
?MAKE:-pick add $@ %<
```

```
?S:full_sed:
```

```
?S: This variable contains the full pathname to 'sed', whether or
```

```
?S: not the user has specified 'portability'. This is only used
```

```
?S: in the compiled C program, and we assume that all systems which
```

```
?S: can share this executable will have the same full pathname to
```

```
?S: 'sed.'
```

```
?S:.
```

```
?X: Yes, I know about the C symbol PORTABLE, but I think sed
```

```
?X: is
```

```
unlikely to move, and I'm too lazy to add all the
```

```
?X: #ifdef PORTABLE sections to the perl source.
```

```
?X:
```

```
?C:LOC_SED:
```

```
?C: This symbol holds the complete pathname to the sed program.
```

```
?C:.
```

```
?H:#define LOC_SED "$full_sed" /**/
```

```
?H:.
```

```
: Store the full pathname to the sed program for use in the C program
```

```
full_sed=$sed
```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/Loc_sed.U
```

No license file was found, but licenses were detected in source scan.

```

?RCS: $Id: d_setpwent_r.U,v 0RCS:
?RCS: Copyright (c) 2002,2003 Jarkko Hietaniemi
?RCS:
?RCS: You may distribute under the terms of either the GNU General Public
?RCS: License or the Artistic License, as specified in the README file.
?RCS:
?RCS: Generated by the reentr.pl from the Perl 5.8 distribution.
?RCS:
?MAKE:d_setpwent_r setpwent_r_proto: Inlibc Protochk Hasproto i_systypes \
  usethreads i_pwd extern_C
?MAKE: -pick add $@ %<
?S:d_setpwent_r:
?S: This variable conditionally defines the HAS_SETPWENT_R symbol,
?S: which indicates to the C program that the setpwent_r()
?S: routine is available.
?S:.
?S:setpwent_r_proto:
?S: This variable encodes the prototype of setpwent_r.
?S: It is zero if d_setpwent_r is undef, and one of the
?S: REENTRANT_PROTO_T_ABC macros of reentr.h if d_setpwent_r
?S: is defined.
?S:.
?C:HAS_SETPWENT_R:
?C: This symbol, if defined, indicates that the setpwent_r routine
?C: is available to
?C: setpwent re-entrantly.
?C:.
?C:SETPWENT_R_PROTO:
?C: This symbol encodes the prototype of setpwent_r.
?C: It is zero if d_setpwent_r is undef, and one of the
?C: REENTRANT_PROTO_T_ABC macros of reentr.h if d_setpwent_r
?C: is defined.
?C:.
?H:#$d_setpwent_r HAS_SETPWENT_R /**/
?H:#define SETPWENT_R_PROTO $setpwent_r_proto /**/
?H:.
?T:try hdrs d_setpwent_r_proto
: see if setpwent_r exists
set setpwent_r d_setpwent_r
eval $inlibc
case "$d_setpwent_r" in
"$define")
  hdrs="$i_systypes sys/types.h define stdio.h $i_pwd pwd.h"
  case "$d_setpwent_r_proto:$usethreads" in
  ":define") d_setpwent_r_proto=define
  set d_setpwent_r_proto setpwent_r $hdrs
  eval $hasproto ;;
  *) ;;

```

```

esac
case "$d_setpwent_r_proto" in
define)
case "$setpwent_r_proto" in
"|0) try='int setpwent_r(FILE**);'
./protochk "$extern_C $try" $hdrs && setpwent_r_proto=I_H ;;
esac
case "$setpwent_r_proto" in
"|0) try='void setpwent_r(FILE**);'
./protochk "$extern_C $try" $hdrs && setpwent_r_proto=V_H ;;
esac
case
"$setpwent_r_proto" in
"|0) d_setpwent_r=undef
    setpwent_r_proto=0
    echo "Disabling setpwent_r, cannot determine prototype." >&4 ;;
*) case "$setpwent_r_proto" in
REENTRANT_PROTO*) ;;
*) setpwent_r_proto="REENTRANT_PROTO_$setpwent_r_proto" ;;
esac
echo "Prototype: $try" ;;
esac
;;
*) case "$susethreads" in
define) echo "setpwent_r has no prototype, not using it." >&4 ;;
esac
d_setpwent_r=undef
setpwent_r_proto=0
;;
esac
;;
*) setpwent_r_proto=0
;;
esac

```

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/threads/d_setpwent_r.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: selecttype.U,v 3.0.1.3 1997/02/28 16:20:09 ram Exp \$

?RCS:

?RCS: Copyright (c) 1991-1993, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

```

?RCS: of the source tree for dist 3.0.
?RCS:
?RCS: Original Author: Andy Dougherty <doughera@lafcol.lafayette.edu>
?RCS:
?RCS: $Log: selecttype.U,v $
?RCS: Revision 3.0.1.3 1997/02/28 16:20:09 ram
?RCS: patch61: always include <sys/select.h> when available for test
?RCS:
?RCS: Revision 3.0.1.2 1995/07/25 14:14:06 ram
?RCS: patch56: removed harmful spaces in assignment
?RCS:
?RCS: Revision 3.0.1.1 1994/06/20 07:06:31 ram
?RCS: patch30: created by ADO
?RCS:
?MAKE:selecttype: Protochk Oldconfig Myread cat
\
d_fd_set d_select d_socket i_systime i_sysselect extern_C
?MAKE: -pick add $@ %<
?S:selecttype:
?S: This variable holds the type used for the 2nd, 3rd, and 4th
?S: arguments to select. Usually, this is 'fd_set *', if HAS_FD_SET
?S: is defined, and 'int *' otherwise. This is only useful if you
?S: have select(), naturally.
?S:.
?C:Select_fd_set_t:
?C: This symbol holds the type used for the 2nd, 3rd, and 4th
?C: arguments to select. Usually, this is 'fd_set *', if HAS_FD_SET
?C: is defined, and 'int *' otherwise. This is only useful if you
?C: have select(), of course.
?C:.
?H:#define Select_fd_set_t $selecttype /**/
?H:.
?T:xxx nfd tmo try hdrs val
: check for type of arguments to select.
case "$selecttype" in
") case "$d_select" in
$define)
echo " "
$cat <<EOM
Checking to see what type of arguments are accepted by select().
EOM
hdrs="$define sys/types.h
$i_systime sys/time.h
$i_sysselect sys/select.h
$d_socket sys/socket.h"
: The first arg can be int, unsigned,
or size_t
: The last arg may or may not be 'const'

```

```

val="
: void pointer has been seen but using that
: breaks the selectminbits test
for xxx in 'fd_set *' 'int *'; do
for nfd in 'int' 'size_t' 'unsigned long' 'unsigned' ; do
for tmo in 'struct timeval *' 'const struct timeval *'; do
case "$val" in
") try="$extern_C select _(($nfd, $xxx, $xxx, $xxx, $tmo));"
if ./protochk "$stry" $hdrs; then
echo "Your system accepts $xxx."
val="$xxx"
fi
;;
esac
done
done
done

```

?X: In the unlikely event that none of those worked, prompt the user.

```

case "$val" in
") rp='What is the type for the 2nd, 3rd, and 4th arguments to select?'
case "$d_fd_set" in
$define) dflt="fd_set *" ;;
*) dflt="int *" ;;
esac
. ./myread
val=$ans
;;
esac
selecttype="$val"
;;
*) : no select, so pick a harmless default
selecttype='int *'
;;
esac
;;
esac

```

Found in path(s):

```

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/protos/selecttype.U

```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: i_sysfile.U 1 2006-08-24 12:32:52Z rmanfredi \$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic Licence,

?RCS: as specified in the README file that comes with the distribution.

```

?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: $Log: i_sysfile.U,v $
?RCS: Revision 3.0.1.2 1995/07/25 14:11:36 ram
?RCS: patch56: removed <> characters from comment, per metalint suggestion
?RCS:
?RCS: Revision 3.0.1.1 1993/08/25 14:01:23 ram
?RCS: patch6: added default for i_sysfile
?RCS:
?RCS: Revision 3.0 1993/08/18 12:08:31 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:i_sysfile: h_sysfile Inhdr Setvar
?MAKE: -pick add $@ %<
?S:i_sysfile:
?S: This variable conditionally defines
the I_SYS_FILE symbol, and indicates
?S: whether a C program should include <sys/file.h> to get R_OK and friends.
?S:.
?C:I_SYS_FILE (I_SYSFILE):
?C: This symbol, if defined, indicates to the C program that it should
?C: include <sys/file.h> to get definition of R_OK and friends.
?C:.
?H:#$i_sysfile I_SYS_FILE /**/
?H:.
?T:val
?D:i_sysfile="
?LINT:change h_sysfile
?LINT:set i_sysfile
: see if this is a sys/file.h system
val="
set sys/file.h val
eval $inhdr

: do we need to include sys/file.h ?
case "$val" in
"$define")
echo " "
if $h_sysfile; then
val="$define"
echo "We'll be including <sys/file.h>." >&4
else
val="$undef"
echo "We won't be including <sys/file.h>." >&4
fi
;;

```

```
*)  
h_sysfile=false  
;;  
esac  
set i_sysfile  
eval $setvar
```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/i_sysfile.U
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: i_sysioctl.U 1 2006-08-24 12:32:52Z rmanfredi \$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic Licence,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic Licence; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: i_sysioctl.U,v \$

?RCS: Revision 3.0.1.2 1994/05/06 15:04:57 ram

?RCS: patch23: added knowledge for <sys/filio.h> (WED)

?RCS: patch23: optimized amount of findhdr calls

?RCS:

?RCS: Revision 3.0.1.1 1993/11/10 17:36:09 ram

?RCS: patch14: now use a compiler check for TIOCNOTTY because of HP-UX 9.x

?RCS:

?RCS: Revision 3.0 1993/08/18 12:08:32 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?MAKE:i_sysioctl i_bsdioclt i_sysfilio i_syssockio

d_voidtty: test contains \

cat i_termio i_termios i_sgTTY Setvar Findhdr +cc rm Inhdr

?MAKE: -pick add \$@ %<

?S:i_sysioctl:

?S: This variable conditionally defines the I_SYS_IOCTL symbol, which

?S: indicates to the C program that <sys/ioctl.h> exists and should

?S: be included.

?S:.

?S:i_sysfilio:

?S: This variable conditionally defines the I_SYS_FILIO symbol, which

?S: indicates to the C program that <sys/filio.h> exists and should

?S: be included in preference to <sys/ioctl.h>.

?S:.

?S:i_bsdioclt:

?S: This variable conditionally defines the I_SYS_BSDIOCTL symbol, which
?S: indicates to the C program that <sys/bsdioclt.h> exists and should
?S: be included.
?S:.

?S:i_syssockio:
?S: This variable conditionally defines I_SYS SOCKIO to indicate to the
?S: C program that socket ioctl codes may be found in <sys/sockio.h>
?S: instead of <sys/ioctl.h>.
?S:.

?S:d_voidtty:
?S: This variable conditionally defines USE_IOCTLNOTTY to indicate that the
?S: ioctl() call with TIOCNOTTY should be used
to void tty association.
?S: Otherwise (on USG probably), it is enough to close the standard file
?S: descriptors and do a setpgrp().
?S:.

?C:I_SYS_IOCTL (I_SYS_IOCTL):
?C: This symbol, if defined, indicates that <sys/ioctl.h> exists and should
?C: be included. Otherwise, include <sgtty.h> or <termio.h>.
?C:.

?C:I_SYS_FILIO:
?C: This symbol, if defined, indicates that <sys/filio.h> exists and
?C: should be included instead of <sys/ioctl.h>.
?C:.

?C:I_SYS_BSDIOCTL (I_BSDIOCTL):
?C: This symbol, if defined, indicates that <sys/bsdioclt.h> exists and should
?C: be included. Otherwise, try <sys/ioctl.h>. This is primarily intended for
?C: definitions of sockets options, like SIOCATMARK.
?C:.

?C:I_SYS SOCKIO (I_SYSSOCKIO):
?C: This symbol, if defined, indicates the <sys/sockio.h> should be included
?C: to get socket ioctl options, like SIOCATMARK.
?C:.

?C:USE_IOCTLNOTTY (VOIDTTY):
?C: This symbol, if defined indicate to the C program that the ioctl()
?C: call with TIOCNOTTY should be used
to void tty association.
?C: Otherwise (on USG probably), it is enough to close the standard file
?C: descriptors and do a setpgrp().
?C:.

?H:#\$i_sysioctl I_SYS_IOCTL /**/
?H:#\$i_sysfilio I_SYS_FILIO /**/
?H:#\$i_bsdioclt I_SYS_BSDIOCTL /**/
?H:#\$i_syssockio I_SYS SOCKIO /**/
?H:#\$d_voidtty USE_IOCTLNOTTY /**/
?H:.

?T:xxx
: see if ioctl defs are in sgtty, termio, sys/filio or sys/ioctl

```

?LINT:set i_sysfilio
set sys/filio.h i_sysfilio
eval $inhdr
echo " "
if $test `./findhdr sys/ioctl.h`; then
    val="$define"
    echo '<sys/ioctl.h> found.' >&4
else
    val="$undef"
    if $test $i_sysfilio = "$define"; then
        echo '<sys/ioctl.h> NOT found.' >&4
    else
        $test $i_sgty = "$define" && xxx="sgtty.h"
        $test $i_termio = "$define" && xxx="termio.h"
        $test $i_termios = "$define" && xxx="termios.h"
    echo "No <sys/ioctl.h> found, assuming ioctl args are defined in <$xxx>." >&4
    fi
fi
?LINT:set i_sysioctl
set i_sysioctl
eval $setvar

@if I_BSDIOCTL || i_bsdioclt
?X:
?X: The only machine I know where this
inclusion was necessary is a
?X: BULL DPX 5000 (a French machine).
?X:
: see if socket ioctl defs are in sys/bsdioclt or sys/ioctl
echo " "
xxx=`./findhdr sys/bsdioclt.h`
if $test "$xxx"; then
    if $contains SIOCATMARK $xxx >/dev/null 2>&1; then
        val="$define"
        echo "You have socket ioctls defined in <sys/bsdioclt.h>." >&4
    else
        val="$undef"
        echo "No socket ioctls found in <sys/bsdioclt.h>." >&4
    fi
else
    val="$undef"
    echo "<sys/bsdioclt.h> not found, but that's ok." >&4
fi
?LINT:set i_bsdioclt
set i_bsdioclt
eval $setvar

@end

```

```

@if I_SYSSOCKIO || i_syssockio
: see if socket ioctl defs are in sys/sockio.h
echo " "
xxx=`./findhdr sys/sockio.h`
if $test "$xxx"; then
if $contains SIOCATMARK $xxx >/dev/null 2>&1; then
val="$define"
echo "You have socket ioctls defined in <sys/sockio.h>." >&4
else
val="$undef"
echo "No socket ioctls found in <sys/sockio.h>." >&4
fi
else
val="$undef"
@if I_BSDIOCTL
case "$i_bsdiocntl" in
"$define") $cat <<EOM
<sys/sockio.h> not found, using
ioctls from <sys/bsdiocntl.h>.
EOM
;;
*) $cat <<EOM
<sys/sockio.h> not found, assuming socket ioctls are in <sys/ioctl.h>.
EOM
;;
esac
@else
$cat <<EOM
<sys/sockio.h> not found, assuming socket ioctls are in <sys/ioctl.h>.
EOM
@end
fi
?LINT:set i_syssockio
set i_syssockio
eval $setvar

@end
@if VOIDTTY || d_voidtty
: check how to void tty association
echo " "
case "$i_sysiocntl" in
"$define") xxx='sys/ioctl.h';
?X: otherwise $xxx was set during the determination of i_sysiocntl, above.
esac
?X:
?X: Can't use $contains here since HP-UX 9.x has TIOCNNOTTY between a pair
?X: of #ifdef/#endif and is never actually defined. Oh well...
?X:

```

```

$cat > tcio.c <<EOM
#include <sys/types.h> /* Just in case */
#include <$xxx>

int main()
{
#ifdef TIOCNOTTY
    exit(0);
#else
    exit(1);
#endif
}
EOM
if ($cc -o tcio tcio.c && ./tcio) >/dev/null 2>&1; then
    val="$define"
    echo "TIOCNOTTY found in <$xxx>." >&4
    echo "Using ioctl() call on /dev/tty to void tty association." >&4
else
    val="$undef"
    echo "Closing
standard file descriptors should void tty association." >&4
fi
?LINT:set d_voidtty
set d_voidtty
eval $setvar
$rm -f tcio tcio.? core

@end

```

Found in path(s):

```

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/i_sysioctl.U

```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: libpth.U,v \$

?RCS: Revision 3.0.1.6 1997/02/28 16:08:49 ram

?RCS: patch61: new loclibpth variable

?RCS:

?RCS: Revision 3.0.1.5 1995/01/11 15:31:30 ram
?RCS: patch45: call ./mips instead of just mips (WED)
?RCS:
?RCS: Revision 3.0.1.4 1994/08/29 16:29:15 ram
?RCS: patch32: added /lib/pa1.1 for HP-UX specially tuned PA-RISC libs (ADO)
?RCS: patch32: fixed information message, making it clearer (ADO)
?RCS:
?RCS: Revision 3.0.1.3 1994/06/20 07:03:54 ram
?RCS: patch30: added /usr/shlib to
glibpth for shared-only libraries
?RCS:
?RCS: Revision 3.0.1.2 1994/05/13 15:26:57 ram
?RCS: patch27: fixed a typo (libpth -> glibpth)
?RCS:
?RCS: Revision 3.0.1.1 1994/05/06 15:07:53 ram
?RCS: patch23: now asks for library directories to be searched (ADO)
?RCS:
?RCS: Revision 3.0 1993/08/18 12:09:02 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?X:
?X: This unit initializes the path for C library lookup.
?X:
?MAKE:libpth glibpth xlibpth plibpth loclibpth: \
usrinc incpath test cat Myread Oldconfig
?MAKE: -pick add \$@ %<
?S:libpth:
?S: This variable holds the general path (space-separated) used to find
?S: libraries. It is intended to be used by other units.
?S:.
?S:glibpth:
?S: This variable holds the general path (space-separated) used to
?S: find libraries. It may contain directories that do not exist on
?S: this platform, libpth is the cleaned-up version.
?S:.
?S:xlibpth:
?S: This variable holds extra path (space-separated) used to find
?S: libraries on this platform,
?S: for example CPU-specific libraries
?S: (on multi-CPU platforms) may be listed here.
?S:.
?S:loclibpth:
?S: This variable holds the paths (space-separated) used to find local
?S: libraries. It is prepended to libpth, and is intended to be easily
?S: set from the command line.
?S:.
?S:plibpth:
?S: Holds the private path used by Configure to find out the libraries.

```

?S: Its value is prepend to libpth. This variable takes care of special
?S: machines, like the mips. Usually, it should be empty.
?S:.
?T: xxx dlist
?LINT:use usrinc
?INIT:: change the next line if compiling for Xenix/286 on Xenix/386
?INIT:xlibpth="/usr/lib/386 /lib/386"
?INIT:: Possible local library directories to search.
?INIT:loclibpth="/usr/local/lib /opt/local/lib /usr/gnu/lib"
?INIT:loclibpth="$loclibpth /opt/gnu/lib /usr/GNU/lib /opt/GNU/lib"
?INIT:
?INIT:: general looking path for locating libraries
?INIT:glibpth="/lib /usr/lib $xlibpth"
?INIT:glibpth="$glibpth /usr/ccs/lib /usr/ucblib /usr/local/lib"
?X: /shlib
is for Digital Unix 4.0
?X: /usr/shlib is for OSF/1 systems.
?INIT:test -f /usr/shlib/libc.so && glibpth="/usr/shlib $glibpth"
?INIT:test -f /shlib/libc.so && glibpth="/shlib $glibpth"
?INIT:
?INIT:: Private path used by Configure to find libraries. Its value
?INIT:: is prepended to libpth. This variable takes care of special
?INIT:: machines, like the mips. Usually, it should be empty.
?INIT:plibpth=""
?INIT:
: Set private lib path
case "$plibpth" in
") if ./mips; then
?X: on mips, we DO NOT want /lib, and we want $incpath/usr/lib
plibpth="$incpath/usr/lib /usr/local/lib /usr/ccs/lib"
fi;;
esac
case "$libpth" in
' ') dlist="";;
") dlist="$loclibpth $plibpth $glibpth";;
*) dlist="$libpth";;
esac

: Now check and see which directories actually exist, avoiding duplicates
libpth=""
for xxx in $dlist
do
if $test -d $xxx; then
case " $libpth " in
*" $xxx "*) ;;
*) libpth="$libpth $xxx";;
esac
fi

```

```
done
$cat <<'EOM'
```

Some systems have incompatible or broken versions of libraries. Among the directories listed in the question below, please remove any you know not to be holding relevant libraries, and add any that are needed. Say "none" for none.

```
EOM
case "$libpth" in
") dflt='none';;
*)
?X: strip leading space
set X $libpth
shift
dflt=${1+"$@"}
;;
esac
rp="Directories to use for library searches?"
./myread
case "$ans" in
none) libpth=' ';;
*) libpth="$ans";;
esac
```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/libpth.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: vendorhtml3dir.U,v 1.1 1999/07/08 18:32:57 doughera Exp doughera $
```

```
?RCS:
```

```
?RCS: Copyright (c) 1999, Andy Dougherty
```

```
?RCS:
```

```
?RCS: You may redistribute only under the terms of the Artistic License,
```

```
?RCS: as specified in the README file that comes with the distribution.
```

```
?RCS: You may reuse parts of this distribution only within the terms of
```

```
?RCS: that same Artistic License; a copy of which may be found at the root
```

```
?RCS: of the source tree for dist 3.0.
```

```
?RCS:
```

```
?RCS: $Log: vendorhtml3dir.U,v $
```

```
?RCS: Revision 1.1 1999/07/08 18:32:57 doughera
```

```
?RCS: Initial revision
```

```
?RCS:
```

```
?MAKE:vendorhtml3dir vendorhtml3direxp installvendorhtml3dir: html3dir Getfile \
```

```
Oldconfig Setprefixvar Prefixit test vendorprefix prefix sed
```

```
?MAKE: -pick add $@ %<
```

?Y:TOP

?S:vendorhtml3dir:

?S: This variable contains the name of the directory for html

?S: library pages. It may have a ~ on the front.

?S: The standard distribution will put nothing
in this directory.

?S: Vendors who distribute perl may wish to place their own

?S: html pages for modules and extensions in this directory with

?S: MakeMaker Makefile.PL INSTALLDIRS=vendor

?S: or equivalent. See INSTALL for details.

?S:.

?S:vendorhtml3direxp:

?S: This variable is the ~name expanded version of vendorhtml3dir, so that you

?S: may use it directly in Makefiles or shell scripts.

?S:.

?D:installvendorhtml3dir="

?S:installvendorhtml3dir:

?S: This variable is really the same as vendorhtml3direxp but may differ on

?S: those systems using AFS. For extra portability, only this variable

?S: should be used in makefiles.

?S:.

?LINT:change prefixvar

?LINT:set installvendorhtml3dir

: Set the vendorhtml3dir variables

case "\$vendorprefix" in

") vendorhtml3dir="

vendorhtml3direxp="

;;

*) : determine where vendor-supplied module html pages go.

: There is no standard location, so try to copy the previously-selected

: directory structure for the core html pages.

: XXX Better default

suggestions would be welcome.

case "\$vendorhtml3dir" in

") dflt=`echo "\$html3dir" | \$sed "s#^\$prefix#\$vendorprefix#"` ;;

*) dflt=\$vendorhtml3dir ;;

esac

case "\$dflt" in

"|") dflt=none ;;

esac

fn=dn+~

rp='Pathname for the vendor-supplied html pages?'

./getfile

vendorhtml3dir="\$ans"

vendorhtml3direxp="\$ansexp"

;;

esac

: Use ' ' for none so value is preserved next time through Configure

```
$test X"$vendorhtml3dir" = "X" && vendorhtml3dir=' '
```

```
prefixvar=vendorhtml3dir
```

```
./installprefix
```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/installdirs/vendorhtml3dir.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: d_tminsys.U 1 2006-08-24 12:32:52Z rmanfredi $
```

```
?RCS:
```

```
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
```

```
?RCS:
```

```
?RCS: You may redistribute only under the terms of the Artistic Licence,
```

```
?RCS: as specified in the README file that comes with the distribution.
```

```
?RCS: You may reuse parts of this distribution only within the terms of
```

```
?RCS: that same Artistic Licence; a copy of which may be found at the root
```

```
?RCS: of the source tree for dist 4.0.
```

```
?RCS:
```

```
?RCS: $Log: d_tminsys.U,v $
```

```
?RCS: Revision 3.0 1993/08/18 12:07:47 ram
```

```
?RCS: Baseline for dist 3.0 netwide release.
```

```
?RCS:
```

```
?MAKE:d_tminsys: contains Setvar Findhdr
```

```
?MAKE: -pick add $@ %<
```

```
?S:d_tminsys:
```

```
?S: This variable conditionally defines TM_IN_SYS if this system
```

```
?S: declares "struct tm" in <sys/time.h> rather than <time.h>.
```

```
?S:.
```

```
?C:TM_IN_SYS (TMINSYS):
```

```
?C: This symbol is defined if this system declares "struct tm" in
```

```
?C: in <sys/time.h> rather than <time.h>.
```

We can't just say

```
?C: -I/usr/include/sys because some systems have both time files, and
```

```
?C: the -I trick gets the wrong one.
```

```
?C:.
```

```
?H:#$d_tminsys TM_IN_SYS /**/
```

```
?H:.
```

```
?LINT:set d_tminsys
```

```
: see if struct tm is defined in sys/time.h
```

```
echo " "
```

```
if $contains 'struct tm' `./findhdr time.h` >/dev/null 2>&1 ; then
```

```
echo "You have struct tm defined in <time.h> rather than <sys/time.h>." >&4
```

```
val="$undef"
```

```
else
```

```
echo "You have struct tm defined in <sys/time.h> rather than <time.h>." >&4
```

```
val="$define"
```

```
fi
```

```
set d_tminsys
eval $setvar
```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/d_tminsys.U
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1999, Jarkko Hietaniemi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 3.0.

?RCS:

?MAKE:d_sigqueue: Inlibc

?MAKE: -pick add \$@ %<

?S:d_sigqueue:

?S: This variable conditionally defines HAS_SIGQUEUE

?S: if sigqueue() is available to queue a signal and data to a process.

?S:.

?C:HAS_SIGQUEUE:

?C: This symbol, if defined, indicates that the sigqueue

?C: system call is available to queue a signal and data to a process.

?C:.

?H:#\$d_sigqueue HAS_SIGQUEUE /**/

?H:.

?LINT:set d_sigqueue

: see if sigqueue exists

set sigqueue d_sigqueue

eval \$inlibc

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/perl/d_sigqueue.U
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_pwritev.U 1 2006-08-24 12:32:52Z rmanfredi \$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic Licence,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic Licence; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: \$Log: d_pwritev.U,v \$
?RCS:
?MAKE:d_pwritev: Inlibc
?MAKE: -pick add \$@ %<
?S:d_pwritev:
?S: This variable conditionally defines the HAS_PWRITEV symbol, which
?S: indicates to the C program that the pwritev() routine is available.
?S:.
?C:HAS_PWRITEV :
?C: This symbol, if defined, indicates that the pwritev routine is
?C: available to perform vectored writes on a file descriptor at a
?C: given offset.
?C:.
?H:#\$d_pwritev HAS_PWRITEV /**/
?H:.
?LINT:set
d_pwritev
: see if pwritev exists
set pwritev d_pwritev
eval \$inlibc

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/d_pwritev.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_hidnet.U 1 2006-08-24 12:32:52Z rmanfredi \$
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: \$Log: d_hidnet.U,v \$
?RCS: Revision 3.0 1993/08/18 12:06:20 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:d_hidnet hiddennet: cat sed myhostname mydomain Myread Oldconfig
?MAKE: -pick add \$@ %<
?S:d_hidnet:
?S: This variable conditionally defines the symbol HIDDEN_NET, which
?S: tells the C program that it should pretend it is on a different
?S: host for purposes of advertising a mailing address.

```

?S:.
?S:hidennet:
?S: This variable contains
the value eventually given to the symbol
?S: HIDDEN_NET, if d_hidnet defines it. If defined, it's the name
?S: of the host which serves as the mail server for a network that
?S: is invisible to the outside world.
?S:.
?C:HIDDEN_NET (HIDDENNET):
?C: This symbol, if defined, contains the host name that you want to
?C: advertise to the outside world. This name can be different from
?C: your actual host name, as long as the machine you specify knows
?C: how to forward mail to you.
?C:.
?H:#$d_hidnet HIDDEN_NET "$hidennet" /**/
?H:.
: now get the host name to advertise as our mailing address
case "$hidennet" in
") dflt=n;;
*) dflt=y;;
esac
$cat <<EOM

```

Some sites are on "hidden" networks, in the sense that the network appears to the outside world as a single machine. The advertised name of any host on this hidden network is the name of one machine on the local network which knows how to forward mail to any other host on the hidden network.

Do you wish to advertise a different hostname to the world than the one your own host (\$myhostname\$mydomain) has?

```

EOM
rp="Use "hidden" network?"
./myread
case "$ans" in
n*) d_hidnet="$undef" hidennet="";
*)
d_hidnet="$define"
echo " "
case "$hidennet" in
") dflt=`echo $mydomain | $sed -e 's/^\./'`;
*) dflt="$hidennet";
esac
rp='What hostname do you wish to advertise?'
./myread
hidennet="$ans"
;;

```

esac

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/d_hidnet.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: i_systimeb.U 1 2006-08-24 12:32:52Z rmanfredi \$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic Licence,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic Licence; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: i_systimeb.U,v \$

?RCS: Revision 3.0 1993/08/18 12:08:37 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?X:

?X: This unit looks wether <sys/timeb.h> should be included

?X: or not when using ftime() (for struct timeb definition).

?X:

?X: Force looking for <sys/time.h> for struct timeb.

?X:INC: i_systime

?MAKE:i_systimeb: test contains Loc Setvar Findhdr

?MAKE: -pick add \$@ %<

?S:i_systimeb:

?S: This variable conditionally defines I_SYS_TIMEB,
which indicates

?S: to the C program that it should include <sys/timeb.h>.

?S:.

?C:I_SYS_TIMEB (I_SYSTIMEB):

?C: This symbol, if defined, indicates to the C program that it should

?C: include <sys/timeb.h>, in order to define struct timeb (some systems

?C: define this in <sys/time.h>). This is useful when using ftime().

?C: You should include <sys/time.h> if I_SYS_TIMEB is not defined,

?C: nor is I_SYS_TIME.

?C:.

?H:#\$i_systimeb I_SYS_TIMEB /**/

?H:.

?T:xxx

?LINT:set i_systimeb

: see where struct timeb is defined

echo " "

xxx=`./findhdr sys/timeb.h`

```

if $test "$xxx"; then
if $contains 'struct timeb' $xxx >/dev/null 2>&1; then
val="$define"
echo "You have struct timeb defined in <sys/timeb.h>." >&4
else
val="$undef"
echo "Assuming struct timeb is defined in <sys/time.h>." >&4
fi
else
val="$undef"
echo "No <sys/timeb.h> -- Assuming struct timeb is defined in <sys/time.h>." >&4
fi
set i_systimeb
eval $setvar

```

Found in path(s):

```

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/i_systimeb.U

```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: mallocsrc.U,v \$

?RCS: Revision 3.0.1.2 1997/02/28 16:10:26 ram

?RCS: patch61: added support for Free_t, the type of free()

?RCS: patch61: replaced .o with \$_o all over the place

?RCS:

?RCS: Revision 3.0.1.1 1994/05/06 15:10:46 ram

?RCS: patch23: added support for MYMALLOC, mainly for perl5 (ADO)

?RCS:

?RCS: Revision 3.0 1993/08/18 12:09:12 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?MAKE:mallocsrc mallocobj usemymalloc mallocotype d_mymalloc \

freetype: Myread \

Oldconfig

package Guess Setvar rm cat +cc +ccflags Findhdr \

i_malloc i_stdlib sed libs _o ptrsize

?MAKE: -pick add \$@ %<

?X: Put near top so that other tests don't erroneously include

?X: -lmalloc. --AD 22 June 1998

?Y:TOP

?S:usemymalloc:

?S: This variable contains y if the malloc that comes with this package

?S: is desired over the system's version of malloc. People often include

?S: special versions of malloc for efficiency, but such versions are often

?S: less portable. See also malloclib and mallocobj.

?S: If this is 'y', then -lmalloc is removed from \$libs.

?S:.

?S:malloclib:

?S: This variable contains the name of the malloc.c that comes with

?S: the package, if that malloc.c is preferred over the system malloc.

?S: Otherwise the value is null. This variable is intended for generating

?S: Makefiles.

?S:.

?S:d_mymalloc:

?S: This variable conditionally defines MYMALLOC in case other parts

?S: of the source want to take special action if MYMALLOC is used.

?S: This may include different sorts

?S: of profiling or error detection.

?S:.

?S:mallocobj:

?S: This variable contains the name of the malloc.o that this package

?S: generates, if that malloc.o is preferred over the system malloc.

?S: Otherwise the value is null. This variable is intended for generating

?S: Makefiles. See malloclib.

?S:.

?S:freetype:

?S: This variable contains the return type of free(). It is usually

?S: void, but occasionally int.

?S:.

?S:malloctype:

?S: This variable contains the kind of ptr returned by malloc and realloc.

?S:.

?C:Free_t:

?C: This variable contains the return type of free(). It is usually

?C: void, but occasionally int.

?C:.

?C:Malloc_t (MALLOCPTRTYPE):

?C: This symbol is the type of pointer returned by malloc and realloc.

?C:.

?H:#define Malloc_t \$malloctype /**/

?H:#define Free_t \$freetype /**/

?H:.

?C:MYMALLOC:

?C: This symbol, if defined, indicates that we're using our own malloc.

?C:.

?H:#\$d_mymalloc MYMALLOC /**/

```

?H:
?LINT:change libs
?X: Cannot test for malloclib; it
is the unit's name and there is a bug in
?X: the interpreter which defines all the names, even though they are not used.
@if malloclib
: determine which malloc to compile in
echo " "
case "$usemymalloc" in
[yY]*|true|$define) dflt='y' ;;
[nN]*|false|$undef) dflt='n' ;;
*)
case "$ptrsize" in
4) dflt='y' ;;
*) dflt='n' ;;
esac
;;
esac
rp="Do you wish to attempt to use the malloc that comes with $package?"
. ./myread
usemymalloc="$ans"
case "$ans" in
y*|true)
usemymalloc='y'
malloclib='malloc.c'
malloclib="$malloclib_o"
d_mymalloc="$define"
?X: Maybe libs.U should be dependent on malloclib.U, but then
?X: most packages that use dist probably don't supply their own
?X: malloc, so this is probably an o.k. compromise
case "$libs" in
*-lmalloc*)
: Remove malloc from list of libraries to use
echo "Removing unneeded -lmalloc from library list" >&4
set `echo X $libs | $sed -e 's/-lmalloc //' -e 's/-lmalloc$/'`
shift
libs="$*"
echo "libs = $libs" >&4
;;
esac
;;
*)
usemymalloc='n'
malloclib=""
malloclib=""
d_mymalloc="$undef"
;;
esac

```

```

@end
@if
  MALLOCPTRTYPE || Malloc_t || Free_t
: compute the return types of malloc and free
echo " "
$cat >malloc.c <<END
#$i_malloc I_MALLOC
#$i_stdlib I_STDLIB
#include <stdio.h>
#include <sys/types.h>
#ifdef I_MALLOC
#include <malloc.h>
#endif
#ifdef I_STDLIB
#include <stdlib.h>
#endif
#ifdef TRY_MALLOC
void *malloc();
#endif
#ifdef TRY_FREE
void free();
#endif
END
@if MALLOCPTRTYPE || Malloc_t
case "$malloctype" in
")
if $cc $cflags -c -DTRY_MALLOC malloc.c >/dev/null 2>&1; then
  malloctype='void *'
else
  malloctype='char *'
fi
;;
esac
echo "Your system wants malloc to return '$malloctype', it would seem." >&4
@end

@if Free_t
case "$freetype" in
")
if $cc $cflags -c -DTRY_FREE malloc.c >/dev/null 2>&1; then
  freetype='void'
else
  freetype='int'
fi
;;
esac
echo "Your system uses $freetype free(), it would seem." >&4

```

```
@end
$rm -f malloc.[co]
@end
```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/mallocsrc.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: d_chroot.U 1 2006-08-24 12:32:52Z rmanfredi $
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: Original Author: Andy Dougherty <doughera@lafcol.lafayette.edu>
?RCS:
?RCS: $Log: d_chroot.U,v $
?RCS: Revision 3.0.1.1 1994/08/29 16:07:17 ram
?RCS: patch32: created by ADO
?RCS:
?MAKE:d_chroot: Inlibc
?MAKE: -pick add $@ %<
?S:d_chroot:
?S: This variable conditionally defines the HAS_CHROOT symbol, which
?S: indicates to the C program that the chroot() routine is available.
?S:.
?C:HAS_CHROOT :
?C: This symbol, if defined, indicates that the chroot routine
is
?C: available.
?C:.
?H:#$d_chroot HAS_CHROOT /**/
?H:.
?LINT:set d_chroot
: see if chroot exists
set chroot d_chroot
eval $inlibc
```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/d_chroot.U
```

No license file was found, but licenses were detected in source scan.

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?MAKE:d_truncl: Inlibc

?MAKE: -pick add \$@ %<

?S:d_truncl:

?S: This variable conditionally defines the HAS_TRUNCL symbol, which

?S: indicates to the C program that the truncl() routine is available

?S: to round long doubles towards zero. If copysignl is also present,

?S: we can emulate modfl.

?S:.

?C:HAS_TRUNCL :

?C: This symbol, if defined, indicates that the truncl routine is

?C: available. If copysignl is also present we can emulate modfl.

?C:.

?H:#\$d_truncl HAS_TRUNCL /**/

?H:.

?LINT:set d_truncl

: see if truncl exists

set truncl d_truncl

eval \$inlibc

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_truncl.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_getservent_r.U,v 0RCS:

?RCS: Copyright (c) 2002,2003 Jarkko Hietaniemi

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?RCS: Generated by the reentr.pl from the Perl 5.8 distribution.

?RCS:

?MAKE:d_getservent_r getservent_r_proto: Inlibc Protochk Hasproto i_systypes \
usethreads i_netdb extern_C

?MAKE: -pick add \$@ %<

?S:d_getservent_r:

?S: This variable conditionally defines the HAS_GETSERVENT_R symbol,

?S: which indicates to the C program that the getservent_r()

?S: routine is available.

?S:.

?S:getservent_r_proto:

?S: This variable encodes the prototype of getservent_r.

?S: It is zero if d_getservent_r is undef, and one of the

?S: REENTRANT_PROTO_T_ABC macros of reentr.h if d_getservent_r

?S: is defined.

?S:.

?C:HAS_GETSERVENT_R:

?C: This symbol, if defined, indicates that the getservent_r routine

?C: is

available to getservent re-entrantly.

?C:.

?C:GETSERVENT_R_PROTO:

?C: This symbol encodes the prototype of getservent_r.

?C: It is zero if d_getservent_r is undef, and one of the

?C: REENTRANT_PROTO_T_ABC macros of reentr.h if d_getservent_r

?C: is defined.

?C:.

?H:#\$d_getservent_r HAS_GETSERVENT_R /**/

?H:#define GETSERVENT_R_PROTO \$getservent_r_proto /**/

?H:.

?T:try hdrs d_getservent_r_proto

: see if getservent_r exists

set getservent_r d_getservent_r

eval \$inlibc

case "\$d_getservent_r" in

"\$define")

hdrs="\$i_systypes sys/types.h define stdio.h \$i_netdb netdb.h"

case "\$d_getservent_r_proto:\$usetthreads" in

":define") d_getservent_r_proto=define

set d_getservent_r_proto getservent_r \$hdrs

eval \$hasproto ;;

*) ;;

esac

case "\$d_getservent_r_proto" in

define)

case "\$getservent_r_proto" in

"|0) try='int getservent_r(struct servent*, char*, size_t, struct servent**);'

./protochk "\$extern_C \$try" \$hdrs && getservent_r_proto=I_SBWR ;;

esac

case "\$getservent_r_proto"

in

"|0) try='int getservent_r(struct servent*, char*, int);'

./protochk "\$extern_C \$try" \$hdrs && getservent_r_proto=I_SBI ;;

esac

case "\$getservent_r_proto" in

"|0) try='struct servent* getservent_r(struct servent*, char*, int);'

./protochk "\$extern_C \$try" \$hdrs && getservent_r_proto=S_SBI ;;

esac

case "\$getservent_r_proto" in

"|0) try='int getservent_r(struct servent*, struct servent_data*);'

./protochk "\$extern_C \$try" \$hdrs && getservent_r_proto=I_SD ;;

esac

case "\$getservent_r_proto" in

```

"|0) d_getservent_r=undef
    getservent_r_proto=0
    echo "Disabling getservent_r, cannot determine prototype." >&4 ;;
*) case "$getservent_r_proto" in
    REENTRANT_PROTO*) ;;
*) getservent_r_proto="REENTRANT_PROTO_$getservent_r_proto" ;;
esac
    echo "Prototype: $try" ;;
esac
;;
*) case "$usetthreads" in
    define) echo "getservent_r has no prototype, not using it." >&4 ;;
esac
    d_getservent_r=undef
    getservent_r_proto=0
    ;;
esac
;;
*) getservent_r_proto=0
    ;;
esac

```

Found

in path(s):

```

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/threads/d_getservent_r.U

```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: i_shadow.U,v \$

?RCS:

?RCS: Copyright (c) 1998 Jarkko Hietaniemi

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?MAKE:i_shadow: Inhdr Hasfield

?MAKE: -pick add \$@ %<

?S:i_shadow:

?S: This variable conditionally defines the I_SHADOW symbol, and indicates

?S: whether a C program should include <shadow.h>.

?S:.

?C:I_SHADOW:

?C: This symbol, if defined, indicates that <shadow.h> exists and

?C: should be included.

?C:.

?H:#\$i_shadow I_SHADOW /**/

?H:.

?LINT:set i_shadow

: see if this is a shadow.h system

set shadow.h i_shadow

eval \$inhdr

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/i_shadow.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: Guess.U,v 3.0.1.5 1995/07/25 13:37:14 ram Exp \$

?RCS:

?RCS: Copyright (c) 1991-1993, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 3.0.

?RCS:

?RCS: \$Log: Guess.U,v \$

?RCS: Revision 3.0.1.5 1995/07/25 13:37:14 ram

?RCS: patch56: now knows about OS/2 platforms

?RCS:

?RCS: Revision 3.0.1.4 1994/10/29 15:53:55 ram

?RCS: patch36: added ?F: line for metalint file checking

?RCS: patch36: call ./xenix explicitly instead of relying on PATH

?RCS:

?RCS: Revision 3.0.1.3 1993/12/15 08:14:35 ram

?RCS: patch15: variable d_bsd was not always set properly

?RCS:

?RCS: Revision 3.0.1.2 1993/08/30 08:57:14 ram

?RCS:

patch8: fixed comment which wrongly attributed the usrinc symbol

?RCS: patch8: no more ugly messages when no /usr/include/ctype.h

?RCS:

?RCS: Revision 3.0.1.1 1993/08/27 14:37:37 ram

?RCS: patch7: added support for OSF/1 machines

?RCS:

?RCS: Revision 3.0 1993/08/18 12:04:57 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?X:

?X: This unit hazards some guesses as to what the general nature of the system

?X: is. The information it collects here is used primarily to establish default

?X: answers to other questions.

?X:

?MAKE:Guess d_eunice d_xenix d_bsd: cat test echo n c contains \

rm Loc eunicefix tr sysroot

```

?MAKE: -pick add $@ %<
?S:d_eunice:
?S: This variable conditionally defines the symbols EUNICE and VAX, which
?S: alerts the C program that it must deal with idiosyncrasies of VMS.
?S:.
?S:d_xenix:
?S: This variable conditionally defines the symbol XENIX, which alerts
?S: the C program that it runs under Xenix.
?S:.
?S:d_bsd:
?S: This symbol conditionally defines the
symbol BSD when running on a
?S: BSD system.
?S:.
?C:EUNICE:
?C: This symbol, if defined, indicates that the program is being compiled
?C: under the EUNICE package under VMS. The program will need to handle
?C: things like files that don't go away the first time you unlink them,
?C: due to version numbering. It will also need to compensate for lack
?C: of a respectable link() command.
?C:.
?X: Should we define VMS here? Is Eunice actually used anymore?
?X:?C:VMS:
?X:?C: This symbol, if defined, indicates that the program is running under
?X:?C: VMS. It is currently only set in conjunction with the EUNICE symbol.
?X:?C:.
?C:XENIX:
?C: This symbol, if defined, indicates that the program is running under
?C: Xenix (at least 3.0 ?).
?C:.
?X: We don't use BSD in the perl source. It's too vague, and already
?X: defined in some header files anyway (e.g. NetBSD). This just gives
?X: us a spurious redefinition error upon compilation.
?X: --Andy Dougherty Feb 11, 1998
?X: ?C:BSD:
?X:
?C: This symbol, if defined, indicates that the program is running under
?X: ?C: a BSD system.
?X: ?C:.
?H:#$d_eunice EUNICE /**/
?X:?H:#$d_eunice VMS /**/
?H:#$d_xenix XENIX /**/
?X: ?H:#$d_bsd BSD /**/
?H:.
?F:./bsd ./usg ./v7 ./osf1 ./eunice ./xenix ./venix ./os2
?T:xxx
: make some quick guesses about what we are up against
echo " "

```

```

$echo $n "Hmm... $c"
echo exit 1 >bsd
echo exit 1 >usg
echo exit 1 >v7
echo exit 1 >osf1
echo exit 1 >eunice
echo exit 1 >xenix
echo exit 1 >venix
echo exit 1 >os2
d_bsd="$undef"
?X:
?X: Do not use 'usrinc', or we get a circular dependency. because
?X: usrinc is defined in usrinc.U, which relies on us...
?X:
$cat $sysroot/usr/include/signal.h $sysroot/usr/include/sys/signal.h >foo 2>/dev/null
if test -f /osf_boot || $contains 'OSF/1' $sysroot/usr/include/ctype.h >/dev/null 2>&1
then
echo "Looks kind of like an OSF/1 system, but we'll see..."
echo exit 0 >osf1
elif test `echo abc | $tr a-z A-Z` = Abc ; then
xxx=`./loc addbib blurfl $pth`
if $test
-f $xxx; then
echo "Looks kind of like a USG system with BSD features, but we'll see..."
echo exit 0 >bsd
echo exit 0 >usg
else
if $contains SIGTSTP foo >/dev/null 2>&1 ; then
echo "Looks kind of like an extended USG system, but we'll see..."
else
echo "Looks kind of like a USG system, but we'll see..."
fi
echo exit 0 >usg
fi
elif $contains SIGTSTP foo >/dev/null 2>&1 ; then
echo "Looks kind of like a BSD system, but we'll see..."
d_bsd="$define"
echo exit 0 >bsd
else
echo "Looks kind of like a Version 7 system, but we'll see..."
echo exit 0 >v7
fi
case "$eunicefix" in
*unixtovms*)
$cat <<'EOI'

```

There is, however, a strange, musty smell in the air that reminds me of something...hmm...yes...I've got it...there's a VMS nearby, or I'm a Blit.

```
EOI
```

```

echo exit 0 >eunice
d_eunice="$define"
: it so happens the Eunice I know will not run shell scripts in Unix format
;;
*)
echo " "
echo "Congratulations. You aren't running Eunice."
d_eunice="$undef"
;;
esac
: Detect
OS2. The p_ variable is set above in the Head.U unit.
: Note that this also -- wrongly -- detects e.g. dos-djgpp, which also uses
: semicolon as a patch separator
case "$p_" in
:) ;;
*)
$cat <<'EOI'
I have the feeling something is not exactly right, however...don't tell me...
lemme think...does HAL ring a bell?...no, of course, you're only running OS/2!
(Or you may be running DOS with DJGPP.)
EOI
echo exit 0 >os2
;;
esac
if test -f /xenix; then
echo "Actually, this looks more like a XENIX system..."
echo exit 0 >xenix
d_xenix="$define"
else
echo " "
echo "It's not Xenix..."
d_xenix="$undef"
fi
chmod +x xenix
$eunicefix xenix
if test -f /venix; then
echo "Actually, this looks more like a VENIX system..."
echo exit 0 >venix
else
echo " "
if ./xenix; then
: null
else
echo "Nor is it Venix..."
fi
fi
chmod +x bsd usg v7 osf1 eunice xenix venix os2

```

\$eunicefix bsd usg v7 osf1 eunice xenix venix os2

\$rm -f foo

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/modified/Guess.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: libs.U,v 3.0.1.6 1997/02/28 16:09:11 ram Exp \$

?RCS:

?RCS: Copyright (c) 1991-1993, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 3.0.

?RCS:

?RCS: \$Log: libs.U,v \$

?RCS: Revision 3.0.1.6 1997/02/28 16:09:11 ram

?RCS: patch61: replaced .a with \$_a all over the place

?RCS:

?RCS: Revision 3.0.1.5 1995/07/25 14:12:05 ram

?RCS: patch56: now knows about OS/2 platforms

?RCS:

?RCS: Revision 3.0.1.4 1994/10/29 16:24:22 ram

?RCS: patch36: removed old broken thislib/thatlib processing (ADO)

?RCS:

?RCS: Revision 3.0.1.3 1994/06/20 07:05:44 ram

?RCS: patch30: code cleanup with if/elif by ADO and RAM

?RCS: patch30:

undone patch23 for libswanted default setting

?RCS:

?RCS: Revision 3.0.1.2 1994/05/06 15:08:45 ram

?RCS: patch23: now includes ordered default libswanted variable (ADO)

?RCS: patch23: major cleanup for library lookups (ADO)

?RCS:

?RCS: Revision 3.0.1.1 1993/08/25 14:02:31 ram

?RCS: patch6: added default for libs

?RCS:

?RCS: Revision 3.0 1993/08/18 12:09:03 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?MAKE:libs ignore_versioned_solibs libsfound libsfiles libsdirs libspath: \

test cat Myread Oldconfig Loc libpth package xlibpth so _a \

usesocks sed uselongdouble usequadmath

?MAKE: -pick add \$@ %<

?S:libs:

?S: This variable holds the additional libraries we want to use.

?S: It is up to the Makefile to deal with it. The list can be empty.

?S:.

?S:libsfound:

?S: This variable holds the full pathnames of the libraries

?S: we found and accepted.

?S:.

?S:libsfiles:

?S: This variable holds the filenames aka basenames of the libraries

?S: we found and accepted.

?S:.

?S:libsdirs:

?S: This variable holds the directory names aka dirnames of the libraries

?S: we found and accepted, duplicates are removed.

?S:.

?S:libspath:

?S: This variable holds the directory names probed for libraries.

?S:.

?S:ignore_versioned_solibs:

?S: This variable should be non-empty if non-versioned shared

?S: libraries (libfoo.so.x.y) are to be ignored (because they

?S: cannot be linked against).

?S:.

?T:xxx yyy thislib thisdir libswanted libstyle

?D:libs="

?X:

?X: This order is chosen so that libraries -lndir, -ldir, -lucb, -lbsd,

?X: -lBSD, -lPW, and -lx only get used if there are unresolved

?X: routines at link time. Usually, these are backwards compatibility

?X: libraries, and may not be as reliable as the standard c library.

?X:

?X: The -lsocket -linet -lnsl order has been reported to be necessary

?X: for at least one SVR4 implementation.

?X: -lc must proceed -lucb or -lbsd for most Solaris applications.

?X: -lc_s proceeds -lc so we pick up the shared library version,

if

?X: it is available.

?X:

?X: The ordering of c, posix, and cposix is a guess and almost

?X: certainly wrong on about half of all systems.

?X:

?X: Set proper libswanted in your private Myinit.U if needed.

?X:

?X:: default ordered library list

?X:libswanted='net socket inet bind nsl nm sdbm gdbm ndbm dbm malloc dl'

?X:libswanted="\$libswanted dld sun m c_s c posix cposix ndir dir ucb"

?X:libswanted="\$libswanted bsd BSD PW x"

```

?X:
?INIT:: default library list
?INIT:libswanted="
?INIT:: some systems want to use only the non-versioned libso:s
?INIT:ignore_versioned_solibs="
?LINT:extern usecbacktrace
?LINT:extern libscheck
?LINT:extern p
?LINT:use uselongdouble
: Looking for optional libraries
echo " "
echo "Checking for optional libraries..." >&4
case "$libs" in
'|') dflt="";;
*) dflt="$libs";;
esac
case "$libswanted" in
") libswanted='c_s';;
esac
?X: libsocks has nasty naming scheme.
?X: This does not work if somebody wants SOCKS 4.
case "$usesocks" in
"$define") libswanted="$libswanted
socks5 socks5_sh" ;;
esac
case "$usecbacktrace" in
"$define") libswanted="$libswanted bfd" ;;
esac
case "$usequadmath" in
"$define") libswanted="$libswanted quadmath" ;;
esac
libsfound="
libsfiles="
libsdirs="
libspath="
for thisdir in $libpth $xlibpth; do
test -d $thisdir && libspath="$libspath $thisdir"
done
for thislib in $libswanted; do
for thisdir in $libspath; do
xxx="
if $test ! -f "$xxx" -a "X$ignore_versioned_solibs" = "X"; then
xxx=`ls $thisdir/lib$thislib.$so.[0-9] 2>/dev/null|sed -n '$p`
test -f "$xxx" && eval $libscheck
$test -f "$xxx" && libstyle=shared
xxx=`ls $thisdir/lib$thislib.[0-9].$so 2>/dev/null|sed -n '$p`
test -f "$xxx" && eval $libscheck
$test -f "$xxx" && libstyle=shared

```

```

fi
if test ! -f "$xxx"; then
xxx=${thisdir/lib$thislib.$so}
    $test -f "$xxx" && eval $libscheck
$test -f "$xxx" && libstyle=shared
fi
if test ! -f "$xxx"; then
xxx=${thisdir/lib$thislib$_a}
    $test -f "$xxx"
&& eval $libscheck
$test -f "$xxx" && libstyle=static
fi
if test ! -f "$xxx"; then
xxx=${thisdir/$thislib$_a}
    $test -f "$xxx" && eval $libscheck
$test -f "$xxx" && libstyle=static
fi
if test ! -f "$xxx"; then
xxx=${thisdir/lib${thislib}_s$_a}
    $test -f "$xxx" && eval $libscheck
$test -f "$xxx" && libstyle=static
$test -f "$xxx" && thislib=${thislib}_s
fi
if test ! -f "$xxx"; then
xxx=${thisdir/Slib$thislib$_a}
    $test -f "$xxx" && eval $libscheck
$test -f "$xxx" && libstyle=static
fi
if $test -f "$xxx"; then
case "$libstyle" in
shared) echo "Found -l$thislib (shared)." ;;
static) echo "Found -l$thislib." ;;
*)    echo "Found -l$thislib ($libstyle)." ;;
esac
case " $dflt " in
*"-l$thislib "*);;
*) dflt="$dflt -l$thislib"
    libsfound="$libsfound $xxx"
    yyy=`basename $xxx`
    libsfiles="$libsfiles $yyy"
    yyy=`echo $xxx|sed -e
"s%/$yyy\\|%%"`
    case " $libsdirs " in
    *" $yyy "*) ;;
    *) libsdirs="$libsdirs $yyy" ;;
    esac
;;
esac

```

```

break
fi
done
if $test ! -f "$xxx"; then
    echo "No -l$thislib."
fi
done
set X $dflt
shift
dflt="$*"
case "$libs" in
") dflt="$dflt";;
*) dflt="$libs";;
esac
case "$dflt" in
'|') dflt='none';;
esac

$cat <<EOM

```

In order to compile \$package on your machine, a number of libraries are usually needed. Include any other special libraries here as well. Say "none" for none. The default list is almost always right.
EOM

```

echo " "
rp="What libraries to use?"
./myread
case "$ans" in
none) libs=' ';;
*) libs="$ans";;
esac

```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/modified/libs.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: d_getprotoprotos.U,v $
```

```
?RCS:
```

```
?RCS: Copyright (c) 1991-1993, Raphael Manfredi
```

```
?RCS:
```

```
?RCS: You may redistribute only under the terms of the Artistic License,
```

```
?RCS: as specified in the README file that comes with the distribution.
```

```
?RCS: You may reuse parts of this distribution only within the terms of
```

```
?RCS: that same Artistic License; a copy of which may be found at the root
```

```
?RCS: of the source tree for dist 3.0.
```

```
?RCS:
```

?MAKE:d_getprotoprotos : Hasproto i_netdb
?MAKE: -pick add \$@ %<
?S:d_getprotoprotos:
?S: This variable conditionally defines the HAS_GETPROTO_PROTOS symbol,
?S: which indicates to the C program that <netdb.h> supplies
?S: prototypes for the various getproto*() functions.
?S: See also netdbtype.U for probing for various netdb types.
?S:.
?C:HAS_GETPROTO_PROTOS:
?C: This symbol, if defined, indicates that <netdb.h> includes
?C: prototypes for getprotoent(), getprotobyname(), and
?C: getprotobyaddr().
Otherwise, it is up to the program to guess
?C: them. See netdbtype.U for probing for various Netdb_XXX_t types.
?C:.
?H:#\$d_getprotoprotos HAS_GETPROTO_PROTOS /**/
?H:.
?LINT:set d_getprotoprotos
: see if prototypes for various getprotoxxx netdb.h functions are available
echo " "
set d_getprotoprotos getprotoent \$i_netdb netdb.h
eval \$hasproto

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/protos/d_getprotoprotos.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_lchown.U,v 3.0.1.1 1994/08/29 16:07:14 ram Exp \$
?RCS:
?RCS: Copyright (c) 1991-1993, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 3.0.
?RCS:
?RCS: Original Author: Andy Dougherty <doughera@lafcol.lafayette.edu>
?RCS:
?RCS: \$Log: d_lchown.U,v \$
?RCS: Revision 3.0.1.1 1994/08/29 16:07:14 ram
?RCS: patch32: created by ADO
?RCS:
?MAKE:d_lchown: Compile Setvar cat echo
?MAKE: -pick add \$@ %<
?S:d_lchown:
?S: This variable conditionally defines the HAS_LCHOWN symbol, which

?S: indicates to the C program that the lchown() routine is available

?S: to operate on a symbolic link (instead of following the link).

?S:.

?C:HAS_LCHOWN

:

?C: This symbol, if defined, indicates that the lchown routine is

?C: available to operate on a symbolic link (instead of following the

?C: link).

?C:.

?H:#\$d_lchown HAS_LCHOWN /**/

?H:.

?LINT:set d_lchown

: see if lchown exists

echo " "

?X: Some functions (such as lchown()) are present in libc, but are

?X: unimplemented. That is, they always fail and set errno=ENOSYS.

?X:

?X: Thomas Bushnell provided the following sample code and the explanation

?X: that follows.

?X:

?X: The choice of <assert.h> is essentially arbitrary. The GNU libc

?X: macros are found in <gnu/stubs.h>. You can include that file instead

?X: of <assert.h> (which itself includes <gnu/stubs.h>) if you test for

?X: its existence first. <assert.h> is assumed to exist on every system,

?X: which is why it's used here. Any GNU libc header file will include

?X: the stubs macros. If either __stub_NAME or __stub__NAME is defined,

?X: then the function doesn't actually exist. Tests using <assert.h>

work

?X: on every system around.

?X:

?X: The declaration of FOO is there to override builtin prototypes for

?X: ANSI C functions.

?X:

?X: I really ought to enhance the inlibc test to check for this, but

?X: I don't have time now. --A.D. 5/1998

?X:

```
$cat > try.c <<'EOCP'
/* System header to define __stub macros and hopefully few prototypes,
   which can conflict with char lchown(); below. */
#include <assert.h>
/* Override any gcc2 internal prototype to avoid an error. */
/* We use char because int might match the return type of a gcc2
   builtin and then its argument prototype would still apply. */
char lchown();
int main() {
    /* The GNU C library defines this for functions which it implements
       to always fail with ENOSYS. Some functions are actually named
       something starting with __ and the normal name is an alias. */
```

```

#if defined (__stub_lchown) || defined (__stub___lchown)
choke me
#else
lchown();
#endif
; return 0; }
EOCP
set try
if eval $compile; then
    $echo
    "lchown() found." >&4
    val="$define"
else
    $echo "lchown() NOT found." >&4
    val="$undef"
fi
set d_lchown
eval $setvar

```

Found in path(s):

```

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/compline/d_lchown.U

```

No license file was found, but licenses were detected in source scan.

```

?RCS: $Id: charorder.U,v 3.0.1.1 1994/10/29 16:07:08 ram Exp $
?RCS:
?RCS: Copyright (c) 1991-1993, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 3.0.
?RCS:
?RCS: $Log: charorder.U,v $
?RCS: Revision 3.0.1.1 1994/10/29 16:07:08 ram
?RCS: patch36: added ?F: line for metalint file checking
?RCS:
?RCS: Revision 3.0 1993/08/18 12:05:33 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:chorder_int chorder_short chorder_long: Myread cat Compile rm
?MAKE: -pick add $@ %<
?S:chorder_short (d_cos d_bos):
?S: Holds the value describing the byte ordering of characters in a short.
?S: On a Big-Endian machine, that
    would be "c0c1".
?S:..

```

?S:chorder_int (charoder):

?S: Holds the value describing the byte ordering of characters in an int.

?S: For instance, on a Big-Endian machine, this would be: "c0c1c2c3".

?S:.

?S:chorder_long (d_col d_bol):

?S: Holds the value describing the byte ordering of characters in a long.

?S: On a 64 bits Big-Endian machine, that would yield: "c0c1c2c3c4c5c6c7".

?S:.

?C:CHAR_ORDER_SHORT:

?C: Holds the byte ordering of characters in a short. It's a string

?C: value like "c0c1" on a Big-Endian machine.

?C:.

?C:CHAR_ORDER_INT:

?C: Holds the byte ordering of characters in an int. It's a string

?C: value like "c0c1c2c3" on a Big-Endian machine.

?C:.

?C:CHAR_ORDER_LONG:

?C: Holds the byte ordering of characters in a long. It's a string

?C: value like "c0c1c2c3c4c5c6c7" on a 64 bits Big-Endian machine.

?C:.

?H:#define CHAR_ORDER_SHORT "\$chorder_short" /* byte order in a short */

?H:#define CHAR_ORDER_INT "\$chorder_int" /* byte order in an int */

?H:#define CHAR_ORDER_LONG "\$chorder_long"

/* byte order in a long */

?H:.

?F:!byteorder

: check for character ordering

echo " "

echo "Checking out byte order..." >&4

\$cat >byteorder.c <<'EOCP'

#include <stdio.h>

```
int main(argc, argv)
```

```
int argc;
```

```
char *argv[]; {
```

```
int i;
```

```
int max;
```

```
union {
```

```
short u_s;
```

```
int u_i;
```

```
long u_l;
```

```
char u_c[sizeof(long)];
```

```
} u;
```

```
switch (argv[1][0]) {
```

```
case 'l':
```

```
u.u_l = 0L;
```

```
/* HMS: ASSERT: sizeof(long) < 10. */
```

```
for(i = 0; i < sizeof(long); ++i) {
```

```

    u.u_l *= 0x100L;
    u.u_l += (0xc0 + i);
}
max = sizeof(long);
break;
case 's':
    u.u_s = 0;
    /* HMS: ASSERT: sizeof(short) < 10. */
    for(i = 0; i < sizeof(short); ++i) {
        u.u_s *= 0x100L;
        u.u_s += (0xc0 + i);
    }
    max = sizeof(short);
    break;
case 'i':
    u.u_i = 0;
    /* RAM: ASSERT: sizeof(int) < 10. */
    for(i = 0; i < sizeof(int); ++i) {
        u.u_l *= 0x100L;
        u.u_l += (0xc0 + i);
    }
    max = sizeof(int);
    break;
default:
    max = 0;
    break;
}
for(i = 0; i < max; i++) {
    printf("%x", u.u_c[i] & 0x00FF);
}
printf("\n");
exit(0);
}
EOCP
set
byteorder
if eval $compile_ok ; then
: null statement
@if chorder_short
    chorder_short=`./byteorder s`
@end
@if chorder_int
    chorder_int=`./byteorder i`
@end
@if chorder_long
    chorder_long=`./byteorder l`
@end
else

```

\$cat <<EOM

(I can't seem to get my test program to work. Guessing 32 bits big-endian.)

EOM

```
  chorder_short="c0c1"
  chorder_int="c0c1c2c3"
  chorder_long="c0c1c2c3"
fi
@if chorder_short
dflt=$chorder_short
rp="What is the order of characters in a short?"
./myread
chorder_short="$ans"
@end
@if chorder_int
dflt=$chorder_int
rp="What is the order of characters in an int?"
./myread
chorder_int="$ans"
@end
@if chorder_long
dflt=$chorder_long
rp="What is the order of characters in a long?"
./myread
chorder_long="$ans"
@end
$rm -f byteorder* core
```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/compline/charorder.U
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1999, Jarkko Hietaniemi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 3.0.

?RCS:

?MAKE:d_sem_trywait: Inlibc

?MAKE: -pick add \$@ %<

?S:d_sem_trywait:

?S: This variable conditionally defines HAS_SEM_TRYWAIT if sem_trywait() is

?S: available to attempt to wait (grab, lock) a POSIX semaphore.

?S:.

?C:HAS_SEM_TRYWAIT:

?C: This symbol, if defined, indicates that the sem_trywait system call is

?C: available to attempt to wait (grab, lock) a POSIX semaphore.

?C:.

?H:#\$d_sem_trywait HAS_SEM_TRYWAIT /**/

?H:.

?LINT:set d_sem_trywait

: see if sem_trywait exists

set sem_trywait d_sem_trywait

eval \$inlibc

Found

in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_sem_trywait.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_getsent.U,v 3.0 1993/08/18 12:06:09 ram Exp \$

?RCS:

?RCS: Copyright (c) 1991-1993, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 3.0.

?RCS:

?RCS: \$Log: d_getsent.U,v \$

?RCS: Revision 3.0 1993/08/18 12:06:09 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?MAKE:d_getsent: Inlibc

?MAKE: -pick add \$@ %<

?S:d_getsent:

?S: This variable conditionally defines HAS_GETSERVENT if getservent() is

?S: available to look up network services in some data base or another.

?S:.

?C:HAS_GETSERVENT:

?C: This symbol, if defined, indicates that the getservent() routine is

?C: available to look up network services in some
data base or another.

?C:.

?H:#\$d_getsent HAS_GETSERVENT /**/

?H:.

?LINT:set d_getsent

: see if getservent exists

set getservent d_getsent

eval \$inlibc

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/modified/d_getsent.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_msync.U 1 2006-08-24 12:32:52Z rmanfredi \$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic Licence,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic Licence; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: d_msync.U,v \$

?RCS: Revision 3.0.1.1 1993/12/15 08:19:17 ram

?RCS: patch15: created

?RCS:

?MAKE:d_msync: Inlibc

?MAKE: -pick add \$@ %<

?S:d_msync:

?S: This variable conditionally defines HAS_MSYNCR if msync() is

?S: available to synchronize a mapped file.

?S:.

?C:HAS_MSYNCR:

?C: This symbol, if defined, indicates that the msync system call is

?C: available to synchronize a mapped file.

?C:.

?H:#\$d_msync HAS_MSYNCR /**/

?H:.

?LINT:set d_msync

: see if

msync exists

set msync d_msync

eval \$inlibc

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/d_msync.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: i_whoami.U 1 2006-08-24 12:32:52Z rmanfredi \$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic Licence,

?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: \$Log: i_whoami.U,v \$
?RCS: Revision 3.0.1.1 1993/08/25 14:02:21 ram
?RCS: patch6: added default for i_whoami
?RCS:
?RCS: Revision 3.0 1993/08/18 12:08:50 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:i_whoami: Inhdr
?MAKE: -pick add \$@ %<
?S:i_whoami (d_whoami):
?S: This variable conditionally defines the I_WHOAMI symbol, which
?S: indicates to the C program that it should include <whoami.h>.
?S:.
?C:I_WHOAMI (WHOAMI):
?C: This symbol,
if defined, indicates that the program may include
?C: <whoami.h>.
?C:.
?H:#\$i_whoami I_WHOAMI /**/
?H:.
?D:i_whoami="
?LINT:set i_whoami
: see if there is a whoami.h file
set whoami.h i_whoami
eval \$inhdr

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/i_whoami.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_tzmin.U 1 2006-08-24 12:32:52Z rmanfredi \$
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: \$Log: d_tzmin.U,v \$
?RCS: Revision 3.0.1.1 1994/10/29 16:16:58 ram

```

?RCS: patch36: call ./bsd explicitly instead of relying on PATH
?RCS:
?RCS: Revision 3.0 1993/08/18 12:07:49 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:d_tzmin: contains cppstdin cppminus timeincl rm Setvar Guess
?MAKE: -pick add $@ %<
?S:d_tzmin:
?S: This symbol conditionally defines TZ_MINUTESWEST if the system uses
?S: tz_minuteswest in time header instead of timezone.
?S:.
?C:TZ_MINUTESWEST:
?C: This
symbol is defined if this system uses tz_minuteswest
?C: in time header instead of timezone.
?C: If not defined, you may have to use struct timeb and ftime() rather
?C: than the new gettimeofday() system call.
?C:.
?H:#$d_tzmin TZ_MINUTESWEST /**/
?H:.
?LINT:set d_tzmin
: see if tz_minuteswest is defined in time header
echo " "
val="$undef"
$cppstdin $cppminus < $timeincl > try 2>&1
if $contains 'tz_minuteswest' try >/dev/null 2>&1; then
echo "You have tz_minuteswest defined in $timeincl rather than timezone." >&4
val="$define"
elif $contains 'timezone' try >/dev/null 2>&1; then
echo "You have timezone defined in $timeincl rather than tz_minuteswest." >&4
else
echo "Your $timeincl file looks strange." >&4
fi
if ./bsd; then
case "$d_tzmin" in
"$undef") echo "(Maybe your system is an USG one after all?)";;
esac
fi
set d_tzmin
eval $setvar
$rm -f try

```

Found in path(s):

```

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/d_tzmin.U

```

No license file was found, but licenses were detected in source scan.

```

?RCS: $Id: Signal.U 1 2006-08-24 12:32:52Z rmanfredi $

```

?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: \$Log: Signal.U,v \$
?RCS: Revision 3.0.1.1 1997/02/28 15:20:01 ram
?RCS: patch61: created
?RCS:
?X:
?X: This unit produces three files:
?X: 1- A signal.c file, which, when compiled and run, produces an output like:
?X:
?X: HUP 1
?X: INT 2
?X: QUIT 3
?X: etc...
?X:
?X: 2- A signal.awk script to parse the output of signal.c, fill
?X: in gaps (up to NSIG) and move duplicates to the end.
?X: 3- A signal_cmd script to compile signal.c and run it
?X: through
sort -n -k 2 | uniq | awk -f signal.awk.
?X: (we try also sort -n +1 since some old hosts don't grok sort -k)
?X: (This is called signal_cmd to avoid OS/2 confusion with
?X: signal.cmd vs. signal.
?X: The signal_cmd script also falls back on checking signals one at a
?X: time in case the signal.c program fails. On at least one version of
?X: Linux 2.1.x, the header file #define'd SIGRTMAX to a symbol that
?X: is not defined by the compiler/linker. :-(. Further, on that same
?X: version of Linux, the user had a defective C-shell that gave an
?X: incorrect list for kill -l, so the fall-back didn't work.
?X:
?X: This unit is then used by sig_name.U.
?X:
?MAKE:Signal: test tr rm awk cat grep startsh eunicefix sed sort uniq \
Findhdr cppstdin +cppflags cppminus Compile _o _exe trnl run i_stdlib \
sysroot
?MAKE: -pick add \$@ %<
?X:all files declared as "public" since they're used from other units
?F:signal.c signal_cmd signal.lst signal signal.awk
?T: xx xxx xxxfiles
?LINT:use rm run

```

_o _exe
?LINT:extern sig_num_init
: Trace out the files included by signal.h, then look for SIGxxx names.
?X: Remove SIGARRAYSIZE used by HPUX.
?X: Remove SIGSTKSIZE used by Linux.
?X: Remove SIGSTKSZ used by POSIX.
?X: Remove SIGTYP void lines used by OS2.
?X: Some cpps, like os390, do not give the file name anywhere
case "$sig_num_init" in
")
if [ "$fieldn" = X ]; then
: Just make some guesses. We check them later.
xxx="$sysroot/usr/include/signal.h $sysroot/usr/include/sys/signal.h"
else
xxx=`echo '#include <signal.h>' |
$cppstdin $cppminus $cppflags 2>/dev/null |
$grep '^[ ]*#.*include' |
$awk '{print \\$fieldn}' | $sed 's!'!g' \\
$sed 's!\\\\\\\\\\\\\\\\!g' | $sort | $uniq`
fi
?X: Check this list of files to be sure we have parsed the cpp output ok.
?X: This will also avoid potentially non-existent files, such
?X: as ../foo/bar.h
xxxfiles=""
?X: Add /dev/null in case the $xxx list is empty.
for xx in $xxx /dev/null ; do
$test -f "$xx" && xxxfiles="$xxxfiles $xx"
done
?X:
If we have found no files, at least try signal.h
case "$xxxfiles" in
") xxxfiles=`./findhdr signal.h` ;;
esac
xxx=`awk '
$1 ~ /^#define$/ && $2 ~ /^SIG[A-Z0-9]*$/ && $2 !~ /SIGARRAYSIZE/ && $2 !~ /SIGSTKSIZE/ && $2 !~ /SIGSTKSZ/ && $3 !~ /void/ {
print substr($2, 4, 20)
}
$1 == "#" && $2 ~ /^define$/ && $3 ~ /^SIG[A-Z0-9]*$/ && $3 !~ /SIGARRAYSIZE/ && $4 !~ /void/ {
print substr($3, 4, 20)
}' $xxxfiles`
: Append some common names just in case the awk scan failed.
xxx="$xxx ABRT ALRM BUS CANCEL CHLD CLD CONT DIL EMT FPE"
xxx="$xxx FREEZE HUP ILL INT IO IOT KILL LOST LWP PHONE"
xxx="$xxx PIPE POLL PROF PWR QUIT RTMAX RTMIN SEGV STKFLT STOP"
xxx="$xxx SYS TERM THAW TRAP TSTP TTIN TTOU URG USR1 USR2"
xxx="$xxx USR3 USR4 VTALRM WAITING WINCH WIND WINDOW XCPU XFSZ"

```

: generate a few handy files for later

```
$cat > signal.c <<EOCP
#include <sys/types.h>
#include <signal.h>
#ifdef _stdlib
#include <stdlib.h>
#endif
#include <stdio.h>
int main() {

/* Strange style to avoid
   deeply-nested #if/#else/#endif */
#ifndef NSIG
# ifdef _NSIG
#  define NSIG (_NSIG)
# endif
#endif

#ifndef NSIG
# ifdef SIGMAX
#  define NSIG (SIGMAX+1)
# endif
#endif

#ifndef NSIG
# ifdef SIG_MAX
#  define NSIG (SIG_MAX+1)
# endif
#endif

#ifndef NSIG
# ifdef _SIG_MAX
#  define NSIG (_SIG_MAX+1)
# endif
#endif

#ifndef NSIG
# ifdef MAXSIG
#  define NSIG (MAXSIG+1)
# endif
#endif

#ifndef NSIG
# ifdef MAX_SIG
#  define NSIG (MAX_SIG+1)
# endif
#endif
}
```

```

#ifndef NSIG
# ifdef SIGARRAYSIZE
#  define NSIG SIGARRAYSIZE /* Assume ary[SIGARRAYSIZE] */
# endif
#endif

```

```

#ifndef NSIG
# ifdef _sys_nsig
#  define NSIG (_sys_nsig) /* Solaris 2.5 */
# endif
#endif

```

```

/* Default to some arbitrary number that's big enough to get most
of the common signals.
*/

```

```

#ifndef NSIG
#  define NSIG 50
#endif

```

```
printf("NSIG %d\n", NSIG);
```

```

#ifndef JUST_NSIG

```

```
EOCP
```

```
echo $xxx | $tr ' ' $trnl | $sort | $uniq | $awk '
```

```

{
printf "#ifndef SIG"; printf $1; printf "\n"
printf "printf(\"";
printf $1; printf " %%d\n",SIG";
printf $1; printf ");\n"
printf "#endif\n"
}

```

```

END {
printf "#endif /* JUST_NSIG */\n";
printf "exit(0);\n}\n";
}

```

```
' >>signal.c
```

```
$cat >signal.awk <<'EOP'
```

```
BEGIN { ndups = 0 }
```

```
$1 ~ /^NSIG$/ { nsig = $2 }
```

```
($1 !~ /^NSIG$/) && (NF == 2) && ($2 ~ /^[0-9][0-9]*$/) {
```

```
    if ($2 > maxsig) { maxsig = $2 }
```

```
    if (sig_name[$2]) {
```

```
        dup_name[ndups] = $1
```

```
        dup_num[ndups] = $2
```

```
        ndups++
```

```

    }
    else {
sig_name[$2] = $1
sig_num[$2] = $2
    }
}
END {
    if (nsig == 0) {
        nsig = maxsig + 1
    }
    printf("NSIG %d\n", nsig);
    for (n = 1; n < nsig; n++) {
if (sig_name[n]) {
        printf("%s %d\n", sig_name[n], sig_num[n])
    }
    else {
        printf("NUM%d %d\n", n, n)
    }
    }
    for (n = 0; n < ndups; n++) {
printf("%s %d\n", dup_name[n], dup_num[n])
    }
}
EOP
$cat >signal_cmd <<EOS
$startsh
if $test -s signal.lst; then
    echo "Using your existing signal.lst file"
    exit 0
fi
xxx="$xxx"
EOS
?X: Avoid variable interpolation problems, especially with
?X:
    xxx, which contains newlines.
$cat >>signal_cmd <<'EOS'

set signal
if eval $compile_ok; then
    $run ./signal$_exe | ($sort -n -k 2 2>/dev/null || $sort -n +1) | \
    $uniq | $awk -f signal.awk >signal.lst
else
    echo "(I can't seem be able to compile the whole test program)" >&4
    echo "(I'll try it in little pieces.)" >&4
    set signal -DJUST_NSIG
    if eval $compile_ok; then
        $run ./signal$_exe > signal.nsg
        $cat signal.nsg

```

```

else
  echo "I can't seem to figure out how many signals you have." >&4
  echo "Guessing 50." >&4
  echo 'NSIG 50' > signal.nsg
fi
: Now look at all the signal names, one at a time.
for xx in `echo $xxx | $tr ' ' $trnl | $sort | $uniq`; do
  $cat > signal.c <<EOCP
#include <sys/types.h>
#include <signal.h>
#include <stdio.h>
int main() {
printf("$xx %d\n", SIG${xx});
return 0;
}
EOCP
  set signal
  if eval $compile; then
    echo "SIG${xx} found."
    $run ./signal$_exe >> signal.ls1
  else
    echo "SIG${xx} NOT found."
  fi
done
if $test -s signal.ls1; then
  $cat
signal.nsg signal.ls1 |
  $sort -n | $uniq | $awk -f signal.awk >signal.lst
fi

fi
if $test -s signal.lst; then
:
else
  echo "(AAK! I can't compile the test programs -- Guessing)" >&4
  echo 'kill -l' >signal
  set X `csh -f <signal`
  $rm -f signal
  shift
  case $# in
0) set HUP INT QUIT ILL TRAP ABRT EMT FPE KILL BUS SEGV SYS PIPE ALRM TERM;;
esac
  echo $@ | $tr ' ' $trnl | \
    $awk '{ printf "%s %d\n", $1, ++s; }
  END { printf "NSIG %d\n", ++s }' >signal.lst
fi
$rm -f signal.c signal$_exe signal$_o signal.nsg signal.ls1
EOS

```

```
chmod a+x signal_cmd
$unicefix signal_cmd
;;
esac
```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/modified/Signal.U
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1999, Jarkko Hietaniemi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 3.0.

?RCS:

?MAKE:d_clock_settime: Inlibc

?MAKE: -pick add \$@ %<

?S:d_clock_settime:

?S: This variable conditionally defines HAS_CLOCK_SETTIME

?S: if clock_settime() is available to set the time of a POSIX clock.

?S:.

?C:HAS_CLOCK_SETTIME:

?C: This symbol, if defined, indicates that the clock_settime

?C: system call is available to set the time of a POSIX clock.

?C:.

?H:#\$d_clock_settime HAS_CLOCK_SETTIME /**/

?H:.

?LINT:set d_clock_settime

: see if clock_settime exists

set clock_settime d_clock_settime

eval \$inlibc

Found in path(s):

```
*
```

```
/opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/perl/d_clock_settime.U
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_gmtime_r.U,v 0RCS:

?RCS: Copyright (c) 2002,2003 Jarkko Hietaniemi

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

```

?RCS:
?RCS: Generated by the reentr.pl from the Perl 5.8 distribution.
?RCS:
?MAKE:d_gmtime_r gmtime_r_proto: Inlibc Protochk Hasproto i_systypes \
  usethreads i_time i_systime extern_C
?MAKE: -pick add $@ %<
?S:d_gmtime_r:
?S: This variable conditionally defines the HAS_GMTIME_R symbol,
?S: which indicates to the C program that the gmtime_r()
?S: routine is available.
?S:.
?S:gmtime_r_proto:
?S: This variable encodes the prototype of gmtime_r.
?S: It is zero if d_gmtime_r is undef, and one of the
?S: REENTRANT_PROTO_T_ABC macros of reentr.h if d_gmtime_r
?S: is defined.
?S:.
?C:HAS_GMTIME_R:
?C: This symbol, if defined, indicates that the gmtime_r routine
?C: is available to gmtime re-entrantly.
?C:.
?C:GMTIME_R_PROTO:
?C: This
  symbol encodes the prototype of gmtime_r.
?C: It is zero if d_gmtime_r is undef, and one of the
?C: REENTRANT_PROTO_T_ABC macros of reentr.h if d_gmtime_r
?C: is defined.
?C:.
?H:#$d_gmtime_r HAS_GMTIME_R  /**/
?H:#define GMTIME_R_PROTO $gmtime_r_proto  /**/
?H:.
?T:try hdrs d_gmtime_r_proto
: see if gmtime_r exists
set gmtime_r d_gmtime_r
eval $inlibc
case "$d_gmtime_r" in
"$define")
  hdrs="$i_systypes sys/types.h define stdio.h $i_time time.h $i_systime sys/time.h"
  case "$d_gmtime_r_proto:$usethreads" in
  ":define") d_gmtime_r_proto=define
    set d_gmtime_r_proto gmtime_r $hdrs
    eval $hasproto ;;
  *) ;;
  esac
case "$d_gmtime_r_proto" in
define)
  case "$gmtime_r_proto" in
  "|0) try='struct tm* gmtime_r(const time_t*, struct tm*);'

```

```

./prochck "$extern_C $try" $hdrs && gmtime_r_proto=S_TS ;;
esac
case "$gmtime_r_proto" in
"|0) try='int gmtime_r(const time_t*, struct tm*);'
./prochck "$extern_C $try" $hdrs && gmtime_r_proto=I_TS ;;
esac
case
"$gmtime_r_proto" in
"|0) d_gmtime_r=undef
    gmtime_r_proto=0
    echo "Disabling gmtime_r, cannot determine prototype." >&4 ;;
*) case "$gmtime_r_proto" in
REENTRANT_PROTO*) ;;
*) gmtime_r_proto="REENTRANT_PROTO_$gmtime_r_proto" ;;
esac
echo "Prototype: $try" ;;
esac
;;
*) case "$usethreads" in
define) echo "gmtime_r has no prototype, not using it." >&4 ;;
esac
d_gmtime_r=undef
gmtime_r_proto=0
;;
esac
;;
*) gmtime_r_proto=0
;;
esac

```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/threads/d_gmtime_r.U
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1999-2016 Jarkko Hietaniemi

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

```
?MAKE:d_PRIfldbl sPRIfldbl d_PRIgldbl d_PRIFUldbl sPRIGUldbl d_PRIEUldbl \
sPRIgldbl d_PRIeldbl sPRIeldbl sPRIFUldbl d_PRIGUldbl sPRIEUldbl \
d_SCNfldbl d_double_style_vax d_double_style_ieee \
d_double_style_ibm d_double_style_cray d_double_has_subnormals \
d_double_has_inf d_double_has_nan d_double_has_negative_zero \
sSCNfldbl doublekind: \
```

d_longdbl longdblsize doublesize uselongdouble test echo cat rm_try \
Setvar Compile run i_stdlib osname gccversion cflags
?MAKE: -pick add \$@ %<
?S:doublekind:
?S: This variable, if defined, encodes the type of a double:
?S: 1 = IEEE 754 32-bit little endian,
?S: 2 = IEEE 754 32-bit big endian,
?S: 3 = IEEE 754 64-bit little endian,
?S: 4 = IEEE
754 64-bit big endian,
?S: 5 = IEEE 754 128-bit little endian,
?S: 6 = IEEE 754 128-bit big endian,
?S: 7 = IEEE 754 64-bit mixed endian le-be,
?S: 8 = IEEE 754 64-bit mixed endian be-le,
?S: 9 = VAX 32bit little endian F float format
?S: 10 = VAX 64bit little endian D float format
?S: 11 = VAX 64bit little endian G float format
?S: 12 = IBM 32bit format
?S: 13 = IBM 64bit format
?S: 14 = Cray 64bit format
?S: -1 = unknown format.
?S:.
?S:d_PRIldbl:
?S: This variable conditionally defines the PERL_PRIldbl symbol, which
?S: indicates that stdio has a symbol to print long doubles.
?S:.
?S:d_PRIgldbl:
?S: This variable conditionally defines the PERL_PRIldbl symbol, which
?S: indicates that stdio has a symbol to print long doubles.
?S:.
?S:d_PRIldbl:
?S: This variable conditionally defines the PERL_PRIldbl symbol, which
?S: indicates that stdio has a symbol to print long doubles.
?S:.
?S:d_PRIFUldbl:
?S: This variable conditionally defines the PERL_PRIldbl symbol, which
?S: indicates
that stdio has a symbol to print long doubles.
?S: The 'U' in the name is to separate this from d_PRIldbl so that even
?S: case-blind systems can see the difference.
?S:.
?S:d_PRIGUldbl:
?S: This variable conditionally defines the PERL_PRIldbl symbol, which
?S: indicates that stdio has a symbol to print long doubles.
?S: The 'U' in the name is to separate this from d_PRIgldbl so that even
?S: case-blind systems can see the difference.
?S:.
?S:d_PRIEUldbl:

?S: This variable conditionally defines the PERL_PRIfldbl symbol, which

?S: indicates that stdio has a symbol to print long doubles.

?S: The 'U' in the name is to separate this from d_PRIldbl so that even

?S: case-blind systems can see the difference.

?S:.

?S:d_SCNfldbl:

?S: This variable conditionally defines the PERL_PRIfldbl symbol, which

?S: indicates that stdio has a symbol to scan long doubles.

?S:.

?S:sPRIfldbl:

?S: This variable, if defined, contains the string used by stdio to

?S: format long doubles (format 'f') for

output.

?S:.

?S:sPRIgldbl:

?S: This variable, if defined, contains the string used by stdio to

?S: format long doubles (format 'g') for output.

?S:.

?S:sPRIldbl:

?S: This variable, if defined, contains the string used by stdio to

?S: format long doubles (format 'e') for output.

?S:.

?S:sPRIFUldbl:

?S: This variable, if defined, contains the string used by stdio to

?S: format long doubles (format 'F') for output.

?S: The 'U' in the name is to separate this from sPRIfldbl so that even

?S: case-blind systems can see the difference.

?S:.

?S:sPRIGUldbl:

?S: This variable, if defined, contains the string used by stdio to

?S: format long doubles (format 'G') for output.

?S: The 'U' in the name is to separate this from sPRIgldbl so that even

?S: case-blind systems can see the difference.

?S:.

?S:sPRIEUldbl:

?S: This variable, if defined, contains the string used by stdio to

?S: format long doubles (format 'E') for output.

?S: The 'U' in the name is to separate this from sPRIldbl so that even

?S: case-blind

systems can see the difference.

?S:.

?S:sSCNfldbl:

?S: This variable, if defined, contains the string used by stdio to

?S: format long doubles (format 'f') for input.

?S:.

?S:d_double_has_inf:

?S: This variable conditionally defines the symbol DOUBLE_HAS_INF

?S: which indicates that the double type has an infinity.

?S:.

?S:d_double_has_nan:

?S: This variable conditionally defines the symbol DOUBLE_HAS_INF

?S: which indicates that the double type has a not-a-number.

?S:.

?S:d_double_has_negative_zero:

?S: This variable conditionally defines the symbol DOUBLE_HAS_NEGATIVE_ZERO

?S: which indicates that the double type has a negative zero.

?S:.

?S:d_double_has_subnormals:

?S: This variable conditionally defines the symbol DOUBLE_HAS_SUBNORMALS

?S: which indicates that the double type has subnormals (denormals).

?S:.

?S:d_double_style_cray:

?S: This variable conditionally defines the symbol DOUBLE_STYLE_CRAY

?S: which indicates that the double is the 64-bit CRAY mainframe
format.

?S:.

?S:d_double_style_ibm:

?S: This variable conditionally defines the symbol DOUBLE_STYLE_IBM,

?S: which indicates that the double is the 64-bit IBM mainframe format.

?S:.

?S:d_double_style_ieee:

?S: This variable conditionally defines the symbol DOUBLE_STYLE_IEEE,

?S: which indicates that the double is the 64-bit IEEE 754.

?S:.

?S:d_double_style_vax:

?S: This variable conditionally defines the symbol DOUBLE_STYLE_VAX,

?S: which indicates that the double is the 64-bit VAX format D or G.

?S:.

?C:PERL_PRIldbl:

?C: This symbol, if defined, contains the string used by stdio to

?C: format long doubles (format 'f') for output.

?C:.

?C:PERL_PRIgldbl:

?C: This symbol, if defined, contains the string used by stdio to

?C: format long doubles (format 'g') for output.

?C:.

?C:PERL_PRIeldbl:

?C: This symbol, if defined, contains the string used by stdio to

?C: format long doubles (format 'e') for output.

?C:.

?C:PERL_PRIFldbl:

?C: This symbol, if defined, contains the string used by stdio
to

?C: format long doubles (format 'F') for output.

?C:.

?C:PERL_PRIGldbl:

?C: This symbol, if defined, contains the string used by stdio to
?C: format long doubles (format 'g') for output.
?C:.
?C:PERL_PRIEdbl:
?C: This symbol, if defined, contains the string used by stdio to
?C: format long doubles (format 'e') for output.
?C:.
?C:PERL_SCNfldbl:
?C: This symbol, if defined, contains the string used by stdio to
?C: format long doubles (format 'f') for input.
?C:.
?C:DOUBLEKIND:
?C: DOUBLEKIND will be one of
?C: DOUBLE_IS_IEEE_754_32_BIT_LITTLE_ENDIAN
?C: DOUBLE_IS_IEEE_754_32_BIT_BIG_ENDIAN
?C: DOUBLE_IS_IEEE_754_64_BIT_LITTLE_ENDIAN
?C: DOUBLE_IS_IEEE_754_64_BIT_BIG_ENDIAN
?C: DOUBLE_IS_IEEE_754_128_BIT_LITTLE_ENDIAN
?C: DOUBLE_IS_IEEE_754_128_BIT_BIG_ENDIAN
?C: DOUBLE_IS_IEEE_754_64_BIT_MIXED_ENDIAN_LE_BE
?C: DOUBLE_IS_IEEE_754_64_BIT_MIXED_ENDIAN_BE_LE
?C: DOUBLE_IS_VAX_F_FLOAT
?C: DOUBLE_IS_VAX_D_FLOAT
?C: DOUBLE_IS_VAX_G_FLOAT
?C: DOUBLE_IS_IBM_SINGLE_32_BIT
?C: DOUBLE_IS_IBM_DOUBLE_64_BIT
?C: DOUBLE_IS_CRAY_SINGLE_64_BIT
?C: DOUBLE_IS_UNKNOWN_FORMAT
?C:.
?C:DOUBLE_HAS_INF:
?C: This
symbol, if defined, indicates that the double has
?C: the infinity.
?C:.
?C:DOUBLE_HAS_NAN:
?C: This symbol, if defined, indicates that the double has
?C: the not-a-number.
?C:.
?C:DOUBLE_HAS_NEGATIVE_ZERO:
?C: This symbol, if defined, indicates that the double has
?C: the negative_zero.
?C:.
?C:DOUBLE_HAS_SUBNORMALS:
?C: This symbol, if defined, indicates that the double has
?C: the subnormals (denormals).
?C:.
?C:DOUBLE_STYLE_CRAY:
?C: This symbol, if defined, indicates that the double is

?C: the 64-bit CRAY mainframe format.

?C:.

?C:DOUBLE_STYLE_IBM:

?C: This symbol, if defined, indicates that the double is

?C: the 64-bit IBM mainframe format.

?C:.

?C:DOUBLE_STYLE_IEEE:

?C: This symbol, if defined, indicates that the double is

?C: the 64-bit IEEE 754.

?C:.

?C:DOUBLE_STYLE_VAX:

?C: This symbol, if defined, indicates that the double is

?C: the 64-bit VAX format D or G.

?C:.

?LINT:known

DOUBLE_IS_IEEE_754_32_BIT_LITTLE_ENDIAN

?LINT:known DOUBLE_IS_IEEE_754_32_BIT_BIG_ENDIAN

?LINT:known DOUBLE_IS_IEEE_754_64_BIT_LITTLE_ENDIAN

?LINT:known DOUBLE_IS_IEEE_754_64_BIT_BIG_ENDIAN

?LINT:known DOUBLE_IS_IEEE_754_128_BIT_LITTLE_ENDIAN

?LINT:known DOUBLE_IS_IEEE_754_128_BIT_BIG_ENDIAN

?LINT:known DOUBLE_IS_IEEE_754_64_BIT_MIXED_ENDIAN_LE_BE

?LINT:known DOUBLE_IS_IEEE_754_64_BIT_MIXED_ENDIAN_BE_LE

?LINT:known DOUBLE_IS_VAX_F_FLOAT

?LINT:known DOUBLE_IS_VAX_D_FLOAT

?LINT:known DOUBLE_IS_VAX_G_FLOAT

?LINT:known DOUBLE_IS_IBM_SINGLE_32_BIT

?LINT:known DOUBLE_IS_IBM_DOUBLE_64_BIT

?LINT:known DOUBLE_IS_CRAY_SINGLE_64_BIT

?LINT:known DOUBLE_IS_UNKNOWN_FORMAT

?H:#define DOUBLEKIND \$doublekind /**/

?H:?DOUBLEKIND:#define DOUBLE_IS_IEEE_754_32_BIT_LITTLE_ENDIAN 1

?H:?DOUBLEKIND:#define DOUBLE_IS_IEEE_754_32_BIT_BIG_ENDIAN 2

?H:?DOUBLEKIND:#define DOUBLE_IS_IEEE_754_64_BIT_LITTLE_ENDIAN 3

?H:?DOUBLEKIND:#define DOUBLE_IS_IEEE_754_64_BIT_BIG_ENDIAN 4

?H:?DOUBLEKIND:#define DOUBLE_IS_IEEE_754_128_BIT_LITTLE_ENDIAN 5

?H:?DOUBLEKIND:#define

DOUBLE_IS_IEEE_754_128_BIT_BIG_ENDIAN 6

?H:?DOUBLEKIND:#define DOUBLE_IS_IEEE_754_64_BIT_MIXED_ENDIAN_LE_BE 7

?H:?DOUBLEKIND:#define DOUBLE_IS_IEEE_754_64_BIT_MIXED_ENDIAN_BE_LE 8

?H:?DOUBLEKIND:#define DOUBLE_IS_VAX_F_FLOAT 9

?H:?DOUBLEKIND:#define DOUBLE_IS_VAX_D_FLOAT 10

?H:?DOUBLEKIND:#define DOUBLE_IS_VAX_G_FLOAT 11

?H:?DOUBLEKIND:#define DOUBLE_IS_IBM_SINGLE_32_BIT 12

?H:?DOUBLEKIND:#define DOUBLE_IS_IBM_DOUBLE_64_BIT 13

?H:?DOUBLEKIND:#define DOUBLE_IS_CRAY_SINGLE_64_BIT 14

?H:?DOUBLEKIND:#define DOUBLE_IS_UNKNOWN_FORMAT -1

?H:#\$d_PRIfldbl PERL_PRIfldbl \$\$PRIfldbl /**/

```

?H:#$d_PRIgldbl PERL_PRIgldbl $$PRIgldbl /**/
?H:#$d_PRIeldbl PERL_PRIeldbl $$PRIeldbl /**/
?H:#$d_PRIFUdbl PERL_PRIFldbl $$PRIFUdbl /**/
?H:#$d_PRIGUdbl PERL_PRIGldbl $$PRIGUdbl /**/
?H:#$d_PRIEUdbl PERL_PRIeldbl $$PRIEUdbl /**/
?H:#$d_SCNFldbl PERL_SCNFldbl $$SCNFldbl /**/
?H:#$d_double_has_inf DOUBLE_HAS_INF
?H:#$d_double_has_nan DOUBLE_HAS_NAN
?H:#$d_double_has_negative_zero
DOUBLE_HAS_NEGATIVE_ZERO
?H:#$d_double_has_subnormals DOUBLE_HAS_SUBNORMALS
?H:#$d_double_style_cray DOUBLE_STYLE_CRAY
?H:#$d_double_style_ibm DOUBLE_STYLE_IBM
?H:#$d_double_style_ieee DOUBLE_STYLE_IEEE
?H:#$d_double_style_vax DOUBLE_STYLE_VAX
?H:.
?T:yyy message saveccflags
?F:!try
?LINT:change ccflags
?LINT:change uselongdouble
: Check what kind of doubles your system has
$echo "Checking the kind of doubles you have..." >&4
$cat >try.c <<EOP
#$i_stdlib I_STDLIB
#define DOUBLESIZE $doublesize
#ifdef I_STDLIB
#include <stdlib.h>
#endif
#include <stdio.h>
static const double d = -0.1;
int main() {
    unsigned const char* b = (unsigned const char*)&d;
    #if DOUBLESIZE == 4
    if (b[0] == 0xCD && b[3] == 0xBD) {
        /* IEEE 754 32-bit little-endian */
        printf("1\n");
        exit(0);
    }
    if (b[0] == 0xBD && b[3] == 0xCD) {
        /* IEEE 754 32-bit big-endian */
        printf("2\n");
        exit(0);
    }
    if (b[0] == 0xCC && b[3] == 0xCC) {
        /* VAX format F, 32-bit
        PDP-style mixed endian. */
        printf("9\n");
        exit(0);
    }

```

```

}
if (b[0] == 0xC0 && b[3] == 0x9A) {
    /* IBM single 32-bit */
    printf("12\n");
    exit(0);
}
#endif
#if DOUBLESIZE == 8
if (b[0] == 0x9A && b[7] == 0xBF) {
    /* IEEE 754 64-bit little-endian */
    printf("3\n");
    exit(0);
}
if (b[0] == 0xBF && b[7] == 0x9A) {
    /* IEEE 754 64-bit big-endian */
    printf("4\n");
    exit(0);
}
if (b[0] == 0x99 && b[3] == 0xBF && b[4] == 0x9A && b[7] == 0x99) {
    /* ARM mixed endian: two little-endian 32-bit floats, in big endian order:
    * 4 5 6 7 0 1 2 3 (MSB = 7, LSB = 0)
    * 99 99 b9 bf 9a 99 99 99 */
    printf("7\n");
    exit(0);
}
if (b[0] == 0x99 && b[3] == 0x9A && b[4] == 0xBF && b[7] == 0x99) {
    /* The opposite of case 7, mixed endian: two big-endian 32-bit floats,
    * in little endian order: 3 2 1 0 7 6 5 4 (MSB = 7, LSB = 0)
    * 99 99 99 9a bf b9 99 99 */
    printf("8\n");
    exit(0);
}
if (b[0] == 0xCC && b[7] == 0xCC) {
    /* VAX
    format D, 64-bit PDP-style mixed endian. */
    printf("10\n");
    exit(0);
}
if (b[0] == 0xD9 && b[7] == 0x99) {
    /* VAX format G, 64-bit PDP-style mixed endian. */
    printf("11\n");
    exit(0);
}
if (b[0] == 0xC0 && b[7] == 0x9A) {
    /* IBM double 64-bit */
    printf("13\n");
    exit(0);
}
}

```

```

if (b[0] == 0xBF && b[7] == 0xCD) {
    /* CRAY single 64-bit */
    printf("14\n");
    exit(0);
}
#endif
#if DOUBLESIZE == 16
if (b[0] == 0x9A && b[15] == 0xBF) {
    /* IEEE 754 128-bit little-endian */
    printf("5\n");
    exit(0);
}
if (b[0] == 0xBF && b[15] == 0x9A) {
    /* IEEE 754 128-bit big-endian */
    printf("6\n");
    exit(0);
}
#endif
/* Then there are old mainframe/miniframe formats like IBM and CRAY.
 * Whether those environments can still build Perl is debatable. */
printf("-1\n"); /* unknown */
exit(0);
}
EOP
set try
if eval $compile; then
    doublekind=`$run ./try`
else
    doublekind=-1
fi
case "$doublekind" in
1) echo "You have IEEE
754 32-bit little endian doubles." >&4 ;;
2) echo "You have IEEE 754 32-bit big endian doubles." >&4 ;;
3) echo "You have IEEE 754 64-bit little endian doubles." >&4 ;;
4) echo "You have IEEE 754 64-bit big endian doubles." >&4 ;;
5) echo "You have IEEE 754 128-bit little endian doubles." >&4 ;;
6) echo "You have IEEE 754 128-bit big endian doubles." >&4 ;;
7) echo "You have IEEE 754 64-bit mixed endian doubles (32-bit LEs in BE)." >&4 ;;
8) echo "You have IEEE 754 64-bit mixed endian doubles (32-bit BEs in LE)." >&4 ;;
9) echo "You have VAX format F 32-bit PDP-style mixed endian doubles." >&4 ;;
10) echo "You have VAX format D 64-bit PDP-style mixed endian doubles." >&4 ;;
11) echo "You have VAX format G 64-bit PDP-style mixed endian doubles." >&4 ;;
12) echo "You have IBM short 32-bit doubles." >&4 ;;
13) echo "You have IBM long 64-bit doubles." >&4 ;;
14) echo "You have Cray single 64-bit doubles." >&4 ;;
*) echo "Cannot figure out your double. You Cyber, or something?" >&4 ;;
esac

```

```

d_double_style_ieee=$undef
d_double_style_vax=$undef
d_double_style_ibm=$undef
d_double_style_cray=$undef
case
"$doublekind" in
1|2|3|4|5|6|7|8) d_double_style_ieee=$define ;;
9|10|11) d_double_style_vax=$define ;;
12|13) d_double_style_ibm=$define ;;
14) d_double_style_cray=$define ;;
esac
case "$d_double_style_ieee" in
$define)
    d_double_has_inf=$define
    d_double_has_nan=$define
    d_double_has_negative_zero=$define
    d_double_has_subnormals=$define
    ;;
*)
    d_double_has_inf=$undef
    d_double_has_nan=$undef
    d_double_has_negative_zero=$undef
    d_double_has_subnormals=$undef
    ;;
esac
$rm_try

: Check print/scan long double stuff
echo " "

if $test X"$d_longdbl" = X"$define"; then

echo "Checking how to print long doubles..." >&4

if $test X"$sPRIfldbl" = X -a X"$doublesize" = X"$longdblsize"; then
    $cat >try.c <<'EOCP'
#include <sys/types.h>
#include <stdio.h>
int main() {
    double d = 123.456;
    printf("%.3f\n", d);
}
EOCP
set try
if eval $compile; then
    yyy=`$run
./try`
    case "$yyy" in

```

```

123.456)
sPRIfldbl="f"; sPRIgldbl="g"; sPRIeldbl="e";
sPRIFUldbl="F"; sPRIGUldbl="G"; sPRIEUldbl="E";
echo "We will use %f."
;;
esac
fi
fi

if $test X"$sPRIfldbl" = X; then
$cat >try.c <<'EOCP'
#include <sys/types.h>
#include <stdio.h>
int main() {
long double d = 123.456;
printf("%.3Lf\n", d);
}
EOCP
set try
if eval $compile; then
yyy=`$run ./try`
case "$yyy" in
123.456)
sPRIfldbl="Lf"; sPRIgldbl="Lg"; sPRIeldbl="Le";
sPRIFUldbl="LF"; sPRIGUldbl="LG"; sPRIEUldbl="LE";
echo "We will use %Lf."
;;
esac
fi
fi

if $test X"$sPRIfldbl" = X; then
$cat >try.c <<'EOCP'
#include <sys/types.h>
#include <stdio.h>
int main() {
long double d = 123.456;
printf("%.3llf\n", d);
}
EOCP
set try
if eval $compile; then
yyy=`$run ./try`
case "$yyy" in
123.456)
sPRIfldbl="llf"; sPRIgldbl="llg"; sPRIeldbl="lle";
sPRIFUldbl="llF"; sPRIGUldbl="llG"; sPRIEUldbl="llE";
echo "We

```

```

will use %lf."
;;
esac
fi
fi

if $test X"$sPRIfdbl" = X; then
$cat >try.c <<'EOCP'
#include <sys/types.h>
#include <stdio.h>
int main() {
long double d = 123.456;
printf("%.3lf\n", d);
}
EOCP
set try
if eval $compile; then
yyy=`$run ./try`
case "$yyy" in
123.456)
sPRIfdbl="'lf"; sPRIgldbl="'lg"; sPRIeldbl="'le";
sPRIFUdbl="'lF"; sPRIGUdbl="'lG"; sPRIEUdbl="'lE";
echo "We will use %lf."
;;
esac
fi
fi

if $test X"$sPRIfdbl" = X; then
echo "Cannot figure out how to print long doubles." >&4
else
sSCNfdbl=$sPRIfdbl # expect consistency
fi

$rm_try

fi # d_longdbl

case "$sPRIfdbl" in
") d_PRIfdbl="$sundef"; d_PRIGldbl="$sundef"; d_PRIeldbl="$sundef";
d_PRIFUdbl="$sundef"; d_PRIGUdbl="$sundef"; d_PRIEUdbl="$sundef";
d_SCNfdbl="$sundef";
;;
*) d_PRIfdbl="$sdefine"; d_PRIGldbl="$sdefine"; d_PRIeldbl="$sdefine";
d_PRIFUdbl="$sdefine"; d_PRIGUdbl="$sdefine"; d_PRIEUdbl="$sdefine";
d_SCNfdbl="$sdefine";
;;
esac

```

```

: Before committing on uselongdouble,
see whether that looks sane.
if $test "$uselongdouble" = "$define"; then
  message=""
  echo " "
  echo "Checking if your long double math functions work right..." >&4
  $cat > try.c <<EOF
#include <math.h>
#include <stdio.h>
int main() {
  printf("%$sPRIgldbl"\n", sqrtl(logl(expl(cosl(sinl(0.0L)))))+powl(2.0L, 3.0L));
}
EOF
  case "$osname:$gccversion" in
  aix:*) saveccflags="$ccflags"
ccflags="$ccflags -qlongdouble" ;; # to avoid core dump
  esac
  set try
  if eval $compile_ok; then
    yyy=`$run ./try`
  fi
  case "$yyy" in
  3) echo "Your long double math functions are working correctly." >&4 ;;
  *) echo "Your long double math functions are broken, not using long doubles." >&4
    uselongdouble=$undef
    ;;
  esac
  $rm_try
  case "$osname:$gccversion" in
  aix:*) ccflags="$saveccflags" ;; # restore
  esac
fi

```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/longdblfi.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: i_sysselect.U 1 2006-08-24 12:32:52Z rmanfredi $
```

```
?RCS:
```

```
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
```

```
?RCS:
```

```
?RCS: You may redistribute only under the terms of the Artistic Licence,
```

```
?RCS: as specified in the README file that comes with the distribution.
```

```
?RCS: You may reuse parts of this distribution only within the terms of
```

```
?RCS: that same Artistic Licence; a copy of which may be found at the root
```

```
?RCS: of the source tree for dist 4.0.
```

```

?RCS:
?RCS: $Log: i_syssselct.U,v $
?RCS: Revision 3.0.1.1 1993/08/25 14:01:33 ram
?RCS: patch6: added default for i_syssselct
?RCS:
?RCS: Revision 3.0 1993/08/18 12:08:35 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?X:
?X: Look wether <sys/select.h> exists
?X:
?MAKE:i_syssselct: Inhdr
?MAKE: -pick add $@ %<
?S:i_syssselct:
?S: This variable conditionally defines I_SYS_SELECT, which indicates
?S: to the C program that it should include <sys/select.h> in
order to
?S: get the definition of struct timeval.
?S:.
?C:I_SYS_SELECT (I_SYSSELECT):
?C: This symbol, if defined, indicates to the C program that it should
?C: include <sys/select.h> in order to get definition of struct timeval.
?C:.
?H:#$i_syssselct I_SYS_SELECT /**/
?H:.
?D:i_syssselct=""
?LINT:set i_syssselct
: see if sys/select.h has to be included
set sys/select.h i_syssselct
eval $inhdr

```

Found in path(s):

```

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/i_syssselct.U

```

No license file was found, but licenses were detected in source scan.

```

?RCS: $Id$
?RCS:
?RCS: Copyright (c) 1999, Jarkko Hietaniemi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 3.0.
?RCS:
?MAKE:d_timer_create: Inlibc
?MAKE: -pick add $@ %<

```

?S:d_timer_create:

?S: This variable conditionally defines HAS_TIMER_CREATE if timer_create()

?S: is available to create a POSIX timer.

?S:.

?C:HAS_TIMER_CREATE:

?C: This symbol, if defined, indicates that the timer_create system call is

?C: available to create a POSIX timer.

?C:.

?H:#\$d_timer_create HAS_TIMER_CREATE /**/

?H:.

?LINT:set d_timer_create

: see if timer_create exists

set timer_create d_timer_create

eval \$inlibc

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_timer_create.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: maildir.U 1 2006-08-24 12:32:52Z rmanfredi \$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic Licence,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic Licence; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: maildir.U,v \$

?RCS: Revision 3.0.1.1 1993/12/15 08:21:56 ram

?RCS: patch15: now also looks under /var/mail for BSD/386

?RCS:

?RCS: Revision 3.0 1993/08/18 12:09:09 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?MAKE:maildir maildirexp: Getfile Loc Oldconfig

?MAKE: -pick add \$@ %<

?S:maildir:

?S: This variable contains the name of the directory in which mail is

?S: spooled. Programs using this variable must be prepared to deal with

?S: ~name

substitutions.

?S:.

?S:maildirexp:

?S: This is the same as the maildir variable, but is filename expanded

?S: at configuration time, for programs not willing to deal with it at

```

?S: run-time.
?S:.
: determine where mail is spooled
case "$maildir" in
") dflt=`./loc . /usr/spool/mail /usr/spool/mail /usr/mail /var/mail`;;
*) dflt="$maildir";;
esac
echo " "
fn=d~
rp="Where is yet-to-be-read mail spooled?"
./getfile
maildir="$ans"
maildircp="$anscp"

```

Found in path(s):

```

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/maildir.U

```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 2003 Jarkko Hietaniemi

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?MAKE:d_ilogbl: Inlibc

?MAKE: -pick add \$@ %<

?S:d_ilogbl:

?S: This variable conditionally defines the HAS_ILOGBL symbol, which

?S: indicates to the C program that the ilogbl() routine is available

?S: for extracting the exponent of long double x as a signed integer.

?S: If scalbnl is also present we can emulate frexpl.

?S:.

?C:HAS_ILOGBL:

?C: This symbol, if defined, indicates that the ilogbl routine is

?C: available. If scalbnl is also present we can emulate frexpl.

?C:.

?H:#\$d_ilogbl HAS_ILOGBL /**/

?H:.

?LINT:set d_ilogbl

: see if ilogbl exists

set ilogbl d_ilogbl

eval \$inlibc

Found in path(s):

```

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/perl/d_ilogbl.U

```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id$
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: Original Author: Thomas Neumann <tom@smart.bo.open.de>
?RCS:
?RCS: $Log: Findhdr.U,v $
?RCS: Revision 3.0.1.2 1994/10/29 15:53:08 ram
?RCS: patch36: added ?F: line for metalint file checking
?RCS:
?RCS: Revision 3.0.1.1 1994/05/06 14:03:56 ram
?RCS: patch23: cppminus must be after other cppflags, not before
?RCS:
?RCS: Revision 3.0 1993/08/18 12:04:54 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?X:
?X: This unit produces a findhdr script which is used to locate the header
?X: files
?X: in $usrinc or other stranger places using cpp capabilities. The
?X: script is given an include file base name, like 'stdio.h' or 'sys/file.h'
?X: and it returns the full path of the include file and a zero status or an
?X: empty string with an error status if the file could not be located.
?X:
?MAKE:Findhdr: grep test tr rm +usrinc awk cat startsh \
cppstdin cppminus +cppflags eunicefix osname
?MAKE: -pick add $@ %<
?LINT:define fieldn
?S:fieldn:
?S: This variable is used internally by Configure. It contains the position
?S: of the included file name in cpp output. That is to say, when cpp
?S: pre-processes a #include <file> line, it replaces it by a # line which
?S: contains the original position in the input file and the full name of
?S: included file, between "quotes".
?S:.
?V:fieldn
?F:./findhdr !fieldn
?T:cline pos wanted name awkprg cppfilter testaccess status usrincdir
:determine filename position in cpp output
echo " "
```

```

echo "Computing filename position in cpp output for #include
directives..." >&4
echo '#include <stdio.h>' > foo.c
case "$osname" in
vos)
testaccess=-e
?X: VOS: path component separator is >
cppfilter="tr '\\\>' '/' |"
;;
*)
testaccess=-r
cppfilter=""
;;
esac
$cat >fieldn <<EOF
$startsh
$cpptest $cpptest $cpptest <foo.c 2>/dev/null | \
$grep '^[ ]*#.*stdio.h' | \
while read cline; do
pos=1
set $cline
while $test $# -gt 0; do
if $test $testaccess `echo $1 | $tr -d ""`; then
echo "$pos"
exit 0
fi
shift
pos=`expr $pos + 1`
done
done
EOF
chmod +x fieldn
fieldn=`./fieldn`
$rm -f foo.c fieldn
case $fieldn in
") pos='???';;
1) pos=first;;
2) pos=second;;
3) pos=third;;
*) pos="{fieldn}th";;
esac
echo "Your cpp writes the filename in the $pos field of the line."

?X: To locate a header file, we cannot simply check for $usrinc/file.h, since
?X: some machine have the headers in weird places and our only hope is that
?X: the C pre-processor will know how to find those headers. Thank you Next!
: locate header file
$cat

```

```

>findhdr <<EOF
$startsh
wanted=\$1
name=""
for usrinmdir in $usrinc; do
  if test -f \$usrinmdir/\$wanted; then
    echo "\$usrinmdir/\$wanted"
    exit 0
  fi
done
awkprg='{ print \$$fieldn }'
echo "#include <\"$wanted>" > foo\$\$.c
$cppstdin $cppminus $cppflags < foo\$\$.c 2>/dev/null | \
$cppfilter $grep "^[ ]*#.*\$wanted" | \
while read cline; do
  name=\`echo \$cline | $awk "\$awkprg" | $tr -d ""\`
  case "\$name" in
    *[\|\\]\$wanted) echo "\$name"; exit 1;;
    *[\|\\]\$wanted) echo "\$name"; exit 1;;
    *) exit 2;;
  esac
done
?X: status = 0: grep returned 0 lines, case statement not executed
?X: status = 1: headerfile found
?X: status = 2: while loop executed, no headerfile found
status=\$?
$rm -f foo\$\$.c
if test \$status -eq 1; then
  exit 0
fi
exit 1
EOF
chmod +x findhdr
$unicefix findhdr

```

Found in path(s):

```

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/Findhdr.U

```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: i_sysresrc.U 1 2006-08-24 12:32:52Z rmanfredi $
```

```
?RCS:
```

```
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
```

```
?RCS:
```

```
?RCS: You may redistribute only under the terms of the Artistic Licence,
```

```
?RCS: as specified in the README file that comes with the distribution.
```

```
?RCS: You may reuse parts of this distribution only within the terms of
```

```
?RCS: that same Artistic Licence; a copy of which may be found at the root
```

?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: \$Log: i_sysresrc.U,v \$
?RCS: Revision 3.0 1993/08/18 12:08:34 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?X:
?X: Look wether <sys/resource.h> needs to be included
?X:
?MAKE:i_sysresrc: Inhdr
?MAKE: -pick add \$@ %<
?S:i_sysresrc:
?S: This variable conditionally defines the I_SYS_RESOURCE symbol,
?S: and indicates whether a C program should include <sys/resource.h>.
?S:.
?C:I_SYS_RESOURCE (I_SYSRESOURCE):
?C: This symbol, if defined, indicates
to the C program that it should
?C: include <sys/resource.h>.
?C:.
?H:#\$i_sysresrc I_SYS_RESOURCE /**/
?H:.
?LINT:set i_sysresrc
: see if sys/resource.h has to be included
set sys/resource.h i_sysresrc
eval \$inhdr

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/i_sysresrc.U

No license file was found, but licenses were detected in source scan.

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?MAKE:i_quadmath: Inhdr

?MAKE: -pick add \$@ %<

?S:i_quadmath:

?S: This variable conditionally defines I_QUADMATH, which indicates

?S: to the C program that it should include <quadmath.h>.

?S:.

?C:I_QUADMATH:

?C: This symbol, if defined, indicates that <quadmath.h> exists and

?C: should be included.

?C:.

?H:#\$i_quadmath I_QUADMATH /**/
?H:.

?LINT:set i_quadmath

```
: see if this is a quadmath.h system
set quadmath.h i_quadmath
eval $inhdr
```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/perl/i_quadmath.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: i_sysmman.U,v $
```

```
?RCS:
```

```
?RCS: Copyright (c) 1999 Jarkko Hietaniemi
```

```
?RCS:
```

```
?RCS: You may distribute under the terms of either the GNU General Public
```

```
?RCS: License or the Artistic License, as specified in the README file.
```

```
?RCS:
```

```
?MAKE:i_sysmman: Inhdr Hasfield
```

```
?MAKE: -pick add $@ %<
```

```
?S:i_sysmman:
```

```
?S: This variable conditionally defines the I_SYS_MMAN symbol, and
```

```
?S: indicates whether a C program should include <sys/mman.h>.
```

```
?S:.
```

```
?C:I_SYS_MMAN:
```

```
?C: This symbol, if defined, indicates that <sys/mman.h> exists and
```

```
?C: should be included.
```

```
?C:.
```

```
?H:#$i_sysmman I_SYS_MMAN /**/
```

```
?H:.
```

```
?LINT:set i_sysmman
```

```
: see if this is a sys/mman.h system
```

```
set sys/mman.h i_sysmman
```

```
eval $inhdr
```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/perl/i_sysmman.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: d_endpent.U,v 3.0 1993/08/18 12:06:09 ram Exp $
```

```
?RCS:
```

```
?RCS: Copyright (c) 1991-1993, Raphael Manfredi
```

```
?RCS:
```

```
?RCS: You may redistribute only under the terms of the Artistic License,
```

```
?RCS: as specified in the README file that comes with the distribution.
```

```
?RCS: You may reuse parts of this distribution only within the terms of
```

```
?RCS: that same Artistic License; a copy of which may be found at the root
```

```
?RCS: of the source tree for dist 3.0.
```

```
?RCS:
```

?RCS: \$Log: d_endpent.U,v \$
?RCS: Revision 3.0 1993/08/18 12:06:09 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:d_endpent: Inlibc
?MAKE: -pick add \$@ %<
?S:d_endpent:
?S: This variable conditionally defines HAS_ENDPROTOENT if endprotoent() is
?S: available to close whatever was being used for protocol queries.
?S:.
?C:HAS_ENDPROTOENT:
?C: This symbol, if defined, indicates that the endprotoent() routine is
?C: available to close whatever was being used
for protocol queries.
?C:.
?H:#\$d_endpent HAS_ENDPROTOENT /**/
?H:.
?LINT:set d_endpent
: see if endprotoent exists
set endprotoent d_endpent
eval \$inlibc

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/modified/d_endpent.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: \$Log: errnolist.U,v \$
?RCS: Revision 3.0.1.2 1997/02/28 15:48:01 ram
?RCS: patch61: replaced .a with \$_a all over the place
?RCS: patch61: likewise for .o replaced by \$_o
?RCS:
?RCS: Revision 3.0.1.1 1994/01/24 14:10:54 ram
?RCS: patch16: created
?RCS:
?MAKE:errnolist errnolist_SH errnolist_a errnolist_c errnolist_o: cat +cc \
+ccflags +libs +d_sysernlst_a_o
?MAKE: -pick add \$@ %<

```

?S:errnolist:
?S: This variable holds the base name of a file containing the
?S: definition of the sys_errnolist
?S: array, if the C library
?S: doesn't provide it already. Otherwise, its value is empty.
?S: The following lines should be included in your Makefile.SH:
?S:
?S: case "$serrnolist" in
?S: ") ;;
?S: *)
?S: $spitshell >>Makefile <<!GROK!THIS!
?S: $serrnolist_c: $serrnolist_SH $serrnolist_a
?S: sh ./$serrnolist_SH
?S:
?S: !GROK!THIS!
?S: ;;
?S: esac
?S:
?S: You may define the 'errnolist' variable in your Myinit.U if you
?S: wish to override its default value "errnolist".
?S:.
?S:errnolist_SH:
?S: This is the name of a file which will generate errnolistc.
?S:.
?S:errnolist_a:
?S: This is the name of the awk script called by errnolist_SH.
?S:.
?S:errnolist_c:
?S: This is the name of a generated C file which provides the
?S: definition of the sys_errnolist array.
?S:.
?S:errnolist_o:
?S: This is the name of the object file which provides the
?S: definition of the sys_errnolist array, if the C library
?S: doesn't provide it already. Otherwise, its value is empty.
?S:.
?INIT:errnolist=errnolist
:
check for sys_errnolist
@if d_sysernlist || HAS_SYS_ERRNOLIST
case "$d_sysernlist" in
"$define")
errnolist="
errnolist_SH="
errnolist_a="
errnolist_c="
errnolist_o="
;;

```

```

*)
echo " "
echo "I'll make sure your Makefile provides sys_errnolist in $errnolist.c"
  errnolist_SH=$errnolist.SH
  errnolist_a=$errnolist$_a
  errnolist_c=$errnolist.c
  errnolist_o=$errnolist$_o
;;
esac
@else
echo " "
$cat <<EOM
Checking to see if your C library provides us with sys_errnolist[...
EOM
$cat >errnolist.c <<'EOCP'
extern char *sys_errnolist[];
int main() {
  char *p0 = sys_errnolist[0];
  char *p1 = sys_errnolist[1];

  return (p0 == p1); /* Make sure they're not optimized away */
}
EOCP
if $cc $ccflags -o errnolist errnolist.c $libs >/dev/null 2>&1 ; then
  echo "It does."
  errnolist="
  errnolist_SH="
  errnolist_a="
  errnolist_c="
  errnolist_o="
else
echo "I'll make sure your Makefile provides sys_errnolist in $errnolist.c"

  errnolist_SH=$errnolist.SH
  errnolist_a=$errnolist$_a
  errnolist_c=$errnolist.c
  errnolist_o=$errnolist$_o
fi
@end

```

Found in path(s):

```

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/errnolist.U

```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: i_ustat.U,v \$

?RCS:

?RCS: Copyright (c) 1998 Jarkko Hietaniemi

?RCS:
?RCS: You may distribute under the terms of either the GNU General Public
?RCS: License or the Artistic License, as specified in the README file.
?RCS:
?MAKE:i_ustat: Inhdr Hasfield
?MAKE: -pick add \$@ %<
?S:i_ustat:
?S: This variable conditionally defines the I_USTAT symbol, and indicates
?S: whether a C program should include <ustat.h>.
?S:.
?C:I_USTAT:
?C: This symbol, if defined, indicates that <ustat.h> exists and
?C: should be included.
?C:.
?H:#\$i_ustat I_USTAT /**/
?H:.
?LINT:set i_ustat
: see if this is a ustat.h system
set ustat.h i_ustat
eval \$inhdr

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/i_ustat.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$
?RCS:
?RCS: Copyright (c) 1999, Jarkko Hietaniemi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 3.0.
?RCS:
?MAKE:d_timer_delete: Inlibc
?MAKE: -pick add \$@ %<
?S:d_timer_delete:
?S: This variable conditionally defines HAS_TIMER_DELETE if timer_delete()
?S: is available to delete a POSIX timer.
?S:.
?C:HAS_TIMER_DELETE:
?C: This symbol, if defined, indicates that the timer_delete system call is
?C: available to delete a POSIX timer.
?C:.
?H:#\$d_timer_delete HAS_TIMER_DELETE /**/
?H:.

```
?LINT:set d_timer_delete
: see if timer_delete exists
set timer_delete d_timer_delete
eval $inlibc
```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/perl/d_timer_delete.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: d_uwait.U 1 2006-08-24 12:32:52Z rmanfredi $
```

```
?RCS:
```

```
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
```

```
?RCS:
```

```
?RCS: You may redistribute only under the terms of the Artistic Licence,
```

```
?RCS: as specified in the README file that comes with the distribution.
```

```
?RCS: You may reuse parts of this distribution only within the terms of
```

```
?RCS: that same Artistic Licence; a copy of which may be found at the root
```

```
?RCS: of the source tree for dist 4.0.
```

```
?RCS:
```

```
?RCS: $Log: d_uwait.U,v $
```

```
?RCS: Revision 3.0.1.1 1994/01/24 14:10:49 ram
```

```
?RCS: patch16: added knowledge about wait3()
```

```
?RCS: patch16: revised 'union wait' look-up algorithm
```

```
?RCS: patch16: fixed make dependency line accordingly
```

```
?RCS:
```

```
?RCS: Revision 3.0 1993/08/18 12:07:54 ram
```

```
?RCS: Baseline for dist 3.0 netwide release.
```

```
?RCS:
```

```
?MAKE:d_uwait d_uwait3: cat contains cppstdin cppminus +cppflags rm \
Setvar Findhdr
```

```
?MAKE: -pick add $@ %<
```

```
?S:d_uwait:
```

```
?S: This symbol
```

```
conditionally defines UNION_WAIT which indicates to the C
```

```
?S: program that argument for the wait() system call should be declared as
```

```
?S: 'union wait status' instead of 'int status'.
```

```
?S:.
```

```
?S:d_uwait3:
```

```
?S: This symbol conditionally defines UNION_WAIT3 which indicates to the C
```

```
?S: program that the first argument for the wait3() system call should be
```

```
?S: declared as 'union wait status' instead of 'int status'.
```

```
?S:.
```

```
?C:UNION_WAIT:
```

```
?C: This symbol if defined indicates to the C program that the argument
```

```
?C: for the wait() system call should be declared as 'union wait status'
```

```
?C: instead of 'int status'. You probably need to include <sys/wait.h>
```

```
?C: in the former case (see I_SYSWAIT).
```

```

?C:.
?C:UNION_WAIT3:
?C: This symbol if defined indicates to the C program that the first argument
?C: for the wait3() system call should be declared as 'union wait status'
?C: instead of 'int status'. You probably need to include <sys/wait.h>
?C: in the former case (see I_SYSWAIT). It seems safe to assume that
the
?C: same rule applies to the second parameter of wait4().
?C:.
?H:#$d_uwait UNION_WAIT /**/
?H:#$d_uwait3 UNION_WAIT3 /**/
?H:.
?T:val2 flags f also
?LINT:set d_uwait d_uwait3
: see if union wait is available
echo " "
?X:
?X: Unfortunately, we can't just grep <sys/wait.h> for "union wait" because
?X: some weird systems (did I hear HP-UX?) define union wait only when _BSD
?X: is defined. The same thing happens on OSF/1, who is pushing weirdness to
?X: its limits by requiring wait() to use (int *) but wait3() to use
?X: (union wait *), unless _BSD is defined and -lbsd is used, in which case
?X: wait() also expects (union wait *). Aaargh!--RAM
?X:
set X $cppflags
shift
flags="
also="
for f in $*; do
case "$f" in
*NO_PROTO*) ;;
*) flags="$flags $f";;
esac
done
$cat `./findhdr sys/wait.h` /dev/null | \
$cppstdin $flags $cppminus >wait.out 2>/dev/null
if $contains 'union.*wait.*{' wait.out >/dev/null 2>&1 ; then
echo "Looks like your <sys/wait.h> knows about 'union wait'..."
>&4
val="$define"
@if UNION_WAIT
also='also '
if $contains 'extern.*wait[ ]*([ ]*int' wait.out >/dev/null 2>&1
then
echo "But wait() seems to expect an 'int' pointer (POSIX way)." >&4
val="$undef"
also="
elif $contains 'extern.*wait[ ]*([ ]*union' wait.out >/dev/null 2>&1

```

```

then
  echo "And indeed wait() expects an 'union wait' pointer (BSD way)." >&4
else
  echo "So we'll use that for wait()." >&4
fi
@end
@if UNION_WAIT3 || d_uwait3
  val2="$define"
@end
@if UNION_WAIT3
  if $contains 'extern.*wait3[ ]*([ ]*int' wait.out >/dev/null 2>&1
  then
    echo "However wait3() seems to expect an 'int' pointer, weird." >&4
    val2="$undef"
  elif $contains 'extern.*wait3[ ]*([ ]*union' wait.out >/dev/null 2>&1
  then
    echo "And wait3() ${also}expects an 'union wait' pointer, fine." >&4
  else
    echo "As expected, wait3() ${also}uses an 'union wait' pointer." >&4
  fi
@end
else
  echo "No trace of 'union wait' in <sys/wait.h>..." >&4
  val="$undef"
@if UNION_WAIT && UNION_WAIT3
  echo
  "Both wait() and wait3() will use a plain 'int' pointer then." >&4
@elseif UNION_WAIT
  echo "Your wait() should be happy with a plain 'int' pointer." >&4
@elseif UNION_WAIT3
  echo "Your wait3() should be happy with a plain 'int' pointer." >&4
@end
fi
set d_uwait
eval $setvar
@if UNION_WAIT3 || d_uwait3
  val="$val2"; set d_uwait3
  eval $setvar
@end
$rm -f wait.out

```

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/d_uwait.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: \$Log: Oldconfig.U,v \$
?RCS: Revision 3.0.1.10 1997/02/28 15:06:39 ram
?RCS: patch61: added support for src.U
?RCS: patch61: new OSNAME define
?RCS: patch61: can now sense new OSes
?RCS:
?RCS: Revision 3.0.1.9 1995/07/25 13:40:51 ram
?RCS: patch56: now knows about OS/2 platforms
?RCS:
?RCS: Revision 3.0.1.8 1995/05/12 12:04:18 ram
?RCS: patch54: config.sh reload logic now knows about new -K switch
?RCS: patch54: cleaned up and extended osvers for DEC OSF/1 (ADO)
?RCS: patch54: added MachTen detection
(ADO)
?RCS:
?RCS: Revision 3.0.1.7 1995/02/15 14:13:41 ram
?RCS: patch51: adapted osvers computation for AIX (ADO)
?RCS:
?RCS: Revision 3.0.1.6 1995/01/30 14:27:15 ram
?RCS: patch49: unit Options.U now exports file optdef.sh, not a variable
?RCS: patch49: update code for myuname changed (WED)
?RCS:
?RCS: Revision 3.0.1.5 1995/01/11 15:15:36 ram
?RCS: patch45: added quotes around the INITPROG variable (ADO)
?RCS: patch45: allows variable overriding after config file loading
?RCS:
?RCS: Revision 3.0.1.4 1994/10/29 15:57:05 ram
?RCS: patch36: added ?F: line for metalint file checking
?RCS: patch36: merged with the version used for perl5's Configure (ADO)
?RCS:
?RCS: Revision 3.0.1.3 1994/05/06 14:24:17 ram
?RCS: patch23: added support for osf1 hints
?RCS: patch23: new support for solaris and i386 systems (ADO)
?RCS:
?RCS: Revision 3.0.1.2 1994/01/24 14:05:02 ram
?RCS: patch16: added post-processing on myuname for Xenix targets
?RCS: patch16: message proposing config.sh
defaults made consistent
?RCS:
?RCS: Revision 3.0.1.1 1993/09/13 15:56:32 ram

?RCS: patch10: force use of config.sh when -d option is used (WAD)

?RCS: patch10: complain about non-existent hint files (WAD)

?RCS: patch10: added Options dependency for fastread variable

?RCS:

?RCS: Revision 3.0 1993/08/18 12:05:12 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?X:

?X: This unit tries to remember what we did last time we ran Configure, mostly

?X: for the sake of setting defaults.

?X:

?MAKE:Oldconfig hint myuname osname osvers: Instruct Myread Checkcc \
Mksymlinks Loc Options Tr src trnl ln uname sh awk sed test cat grep \
rm lns tr n c contains targetarch

?MAKE: -pick wipe \$@ %<

?S:myuname:

?S: The output of 'uname -a' if available, otherwise the hostname. On Xenix,

?S: pseudo variables assignments in the output are stripped, thank you. The

?S: whole thing is then lower-cased.

?S:.

?S:hint:

?S: Gives the type of hints used for previous answers. May be one of

?S: "default",

"recommended" or "previous".

?S:.

?S:osname:

?S: This variable contains the operating system name (e.g. sunos,

?S: solaris, hpux, etc.). It can be useful later on for setting

?S: defaults. Any spaces are replaced with underscores. It is set

?S: to a null string if we can't figure it out.

?S:.

?S:osvers:

?S: This variable contains the operating system version (e.g.

?S: 4.1.3, 5.2, etc.). It is primarily used for helping select

?S: an appropriate hints file, but might be useful elsewhere for

?S: setting defaults. It is set to " if we can't figure it out.

?S: We try to be flexible about how much of the version number

?S: to keep, e.g. if 4.1.1, 4.1.2, and 4.1.3 are essentially the

?S: same for this package, hints files might just be os_4.0 or

?S: os_4.1, etc., not keeping separate files for each little release.

?S:.

?C:OSNAME:

?C: This symbol contains the name of the operating system, as determined

?C: by Configure. You shouldn't rely on it too much; the specific

?C: feature

tests from Configure are generally more reliable.

?C:.

?C:OSVERS:

```

?C: This symbol contains the version of the operating system, as determined
?C: by Configure. You shouldn't rely on it too much; the specific
?C: feature tests from Configure are generally more reliable.
?C:.
?H:#define OSNAME "$osname" /**/
?H:#define OSVERS "$osvers" /**/
?H:.
?F:!config.sh
?T:tmp tmp_n tmp_c tmp_sh file
?T:xxxxfile xxxfile xxfile xfile hintfile newmyuname
?T:tans _ isesix INITPROG DJGPP has_uname
?D:osname=""
?LINT:change n c sh
?LINT:extern hostarch
?LINT:change hostarch
: Determine the name of the machine
myuname=`$uname -a 2>/dev/null`
$test -z "$myuname" && myuname=`hostname 2>/dev/null`
?X: Special mention for Xenix, whose 'uname -a' gives us output like this:
?X: sysname=XENIX
?X: nodename=whatever
?X: release=2.3.2 .. etc...
?X: Therefore, we strip all this variable assignment junk and remove all the
?X: new lines to keep the myuname variable sane... --RAM
myuname=`echo $myuname | $sed -e
's/^[^=]*=/' -e 's/\\//g' | \
./tr '[A-Z]' '[a-z]' | $tr $trnl ' '`
?X: Save the value we just computed to reset myuname after we get done here.
newmyuname="$myuname"
$test -f "$uname$_exe" && has_uname=y

: Guessing of the OS name -- half the following guesses are probably wrong...
: If you have better tests or hints, please send them to the metaconfig
: authors and to <MAINTLOC>
$test -f /irix && osname=irix
$test -f /xenix && osname=sco_xenix
$test -f /dynix && osname=dynix
$test -f /dnix && osname=dnix
$test -f /lynx.os && osname=lynxos
$test -f /unicos && osname=unicos && osvers=`$uname -r`
$test -f /unicosmk && osname=unicosmk && osvers=`$uname -r`
$test -f /unicosmk.ar && osname=unicosmk && osvers=`$uname -r`
$test -f /bin/mips && /bin/mips && osname=mips
$test -d /NextApps && set X `hostinfo | $grep 'NeXT Mach.*:' | \
$sed -e 's://' -e 's/\./_/' && osname=next && osvers=$4
$test -d /usr/apollo/bin && osname=apollo
$test -f /etc/saf/_sactab && osname=svr4
$test -d /usr/include/minix

```

```

&& osname=minix
$test -f /system/gnu_library/bin/ar.pm && osname=vos
if $test -d /MachTen -o -d /MachTen_Folder; then
?X: MachTen uname -a output looks like
?X: xxx 4 0.0 Macintosh
?X: MachTen /sbin/version output looks like
?X: MachTen 4.0 Mon Aug 28 10:18:00 1995
?X: MachTen 3.x had the 'version' command in /usr/etc/version.
osname=machten
if $test -x /sbin/version; then
osvers=`/sbin/version | $awk '{print $2}' |
$sed -e 's/[A-Za-z]$//`
elif $test -x /usr/etc/version; then
osvers=`/usr/etc/version | $awk '{print $2}' |
$sed -e 's/[A-Za-z]$//`
else
osvers="$2.$3"
fi
fi
$test -f /sys/posix.dll &&
$test -f /usr/bin/what &&
set X `usr/bin/what /sys/posix.dll` &&
$test "$3" = UWIN &&
osname=uwin &&
osvers="$5"
?X: If we have uname, we already computed a suitable uname -a output, correctly
?X: formatted for Xenix, and it lies in $myuname.
if $test "X$has_uname" != X; then
set X $myuname
shift
case "$5" in
fps*) osname=fps ;;
mips*)
case "$4"
in
umips) osname=umips ;;
*) osname=mips ;;
esac;;
[23]100) osname=mips ;;
next*) osname=next ;;
?X: Interactive Unix.
i386*)
tmp=`/bin/uname -X 2>/dev/null|awk '3\,2v[45]/{ print $(NF) }`
if $test "$tmp" != "" -a "$3" = "3.2" -a -f /etc/systemid; then
osname='sco'
osvers=$tmp
elif $test -f /etc/kconfig; then
osname=isc

```

```

if $test "$lns" = "$ln -s"; then
    osvers=4
elif $contains _SYSV3 /usr/include/stdio.h > /dev/null 2>&1 ; then
    osvers=3
elif $contains _POSIX_SOURCE /usr/include/stdio.h > /dev/null 2>&1 ; then
    osvers=2
fi
fi
tmp=""
;;
?X: MS-DOS djgpp uname -a output looks like:
?X: ms-dos xxx 6 22 pc
?X: $1 is the "dos flavor" (need not be "ms-dos").
?X: $2 is the node name
?X: $3 and $4 are version/subversion
?X: $5 is always "pc", but that might not be unique to DJGPP.
?X: (e.g. Solaris_x86 has $5 = i86pc, which doesn't actually conflict,
?X: but it's close enough that I can easily imagine other vendors also
?X: using variants
of pc* in $5.)
?X: The "DJGPP" environment variable is always set when djgpp is active.
pc*)
if $test -n "$DJGPP"; then
    osname=dos
    osvers=djgpp
fi
;;
esac
case "$1" in
aix) osname=aix
?X: aix 4.1 uname -a output looks like
?X: AIX foo 1 4 000123456789
?X: where $4 is the major release number and $3 is the (minor) version.
?X: More detail on the version is available with the oslevel command.
?X: in 3.2.x, it output a string (see case statements below). In 4.1,
?X: it puts out something like 4.1.1.0
tmp=`( oslevel) 2>/dev/null || echo "not found") 2>&1`
case "$tmp" in
'not found') osvers="$4"."$3" ;;
'<3240'|<>3240') osvers=3.2.0 ;;
'=3240'|>3240'|<3250'|<>3250') osvers=3.2.4 ;;
'=3250'|>3250') osvers=3.2.5 ;;
*) osvers=$tmp;;
esac
;;
bsd386) osname=bsd386
osvers=`$uname -r`
;;

```

```

cygwin*) osname=cygwin
osvers="$3"
;;
*dc.osx) osname=dcosx
osvers="$3"
;;
dnix) osname=dnix
osvers="$3"
;;
domainos) osname=apollo
osvers="$3"
;;
dgux)
osname=dgux
osvers="$3"
;;
?X: uname -a returns
?X: DYNIX/ptx xxx 4.0 V4.1.2 i386
dynixptx*) osname=dynixptx
osvers=`echo "$4"|sed 's/^v//'^
;;
freebsd) osname=freebsd
osvers="$3" ;;
genix) osname=genix ;;
?X: HP-UX uname -a gives something like
?X: HP-UX foobar B.10.20 A 9000/735 2016483812 two-user license
?X: Preserve the full 10.20 string instead of the previous plain '10'.
?X: Thanks to Graham Barr. --AD 6/30/1998
hp*) osname=hpux
osvers=`echo "$3" | $sed 's,.*\.[0-9]*\.[0-9]*),\1,^
;;
irix*) osname=irix
case "$3" in
4*) osvers=4 ;;
5*) osvers=5 ;;
*) osvers="$3" ;;
esac
;;
linux) osname=linux
case "$3" in
*) osvers="$3" ;;
esac
;;
MiNT) osname=mint
;;
netbsd*) osname=netbsd
osvers="$3"
;;

```

```

news-os) osvers="$3"
case "$3" in
4*) osname=newsos4 ;;
*) osname=newsos ;;
esac
;;
next*) osname=next ;;
nonstop-ux) osname=nonstopux ;;
openbsd) osname=openbsd
osvers="$3"
;;
POSIX-BC | posix-bc
) osname=posix-bc
osvers="$3"
;;
powerux | power_ux | powermax_os | powermaxos | \
powerunix | power_unix) osname=powerux
osvers="$3"
;;
qnx) osname=qnx
osvers="$4"
;;
solaris) osname=solaris
case "$3" in
5*) osvers=`echo $3 | $sed 's/^5/2/g'` ;;
*) osvers="$3" ;;
esac
;;
sunos) osname=sunos
case "$3" in
5*) osname=solaris
osvers=`echo $3 | $sed 's/^5/2/g'` ;;
*) osvers="$3" ;;
esac
;;
titanos) osname=titanos
case "$3" in
1*) osvers=1 ;;
2*) osvers=2 ;;
3*) osvers=3 ;;
4*) osvers=4 ;;
*) osvers="$3" ;;
esac
;;
ultrix) osname=ultrix
osvers="$3"
;;
osf1|mls+) case "$5" in

```

alpha)

?X: DEC OSF/1 myuname -a output looks like: osf1 xxxx t3.2 123.4 alpha

?X: where the version number can be something like [xvt]n.n

```
osname=dec_osf
```

?X: sizer knows the minor minor version: the letter

```
osvers=`sizer -v | awk '{print $3}' | \
```

```
./tr '[A-Z]' '[a-z]' | sed 's/^[xvt]//'
```

```
case "$osvers" in
```

```
[1-9].[0-9]*) ;;
```

```
*) osvers=`echo
```

```
"$3" | sed 's/^[xvt]//'
```

```
esac
```

```
::
```

```
hp*) osname=hp_osf1 ;;
```

```
mips) osname=mips_osf1 ;;
```

?X: hp and mips were unsupported Technology Releases -- ADO, 24/10/94

```
esac
```

```
::
```

```
unixware) osname=svr5
```

```
osvers="$4"
```

```
::
```

```
uts) osname=uts
```

```
osvers="$3"
```

```
::
```

```
vos) osvers="$3"
```

```
::
```

```
$2) case "$osname" in
```

```
*isc*) ;;
```

```
*freebsd*) ;;
```

```
svr*)
```

```
: svr4.x or possibly later
```

```
case "svr$3" in
```

```
${osname}*)
```

```
osname=svr$3
```

```
osvers=$4
```

```
::
```

```
esac
```

```
case "$osname" in
```

```
svr4.0)
```

```
: Check for ESIX
```

```
if $test -f /stand/boot ; then
```

```
eval `$grep '^INITPROG=[a-z/0-9]*$' /stand/boot`
```

```
if $test -n "$INITPROG" -a -f "$INITPROG"; then
```

```
isesix=`strings -a $INITPROG | \
```

```
$grep 'ESIX SYSTEM V/386 Release 4.0`
```

```
if $test -n "$isesix"; then
```

```
osname=esix4
```

```
fi
```

```

fi
fi
;;
esac
;;
*) if $test -f /etc/systemid; then
    osname=sco
    set `echo $3 | $sed 's/./ /g' $4
    if $test -f $src/hints/sco_$1_$2_$3.sh; then
        osvers=$1.$2.$3
    elif $test
-f $src/hints/sco_$1_$2.sh; then
        osvers=$1.$2
    elif $test -f $src/hints/sco_$1.sh; then
        osvers=$1
    fi
else
    case "$osname" in
        ") : Still unknown. Probably a generic Sys V.
        osname="sysv"
        osvers="$3"
        ;;
    esac
fi
;;
esac
;;
*) case "$osname" in
        ") : Still unknown. Probably a generic BSD.
        osname="$1"
        osvers="$3"
        ;;
    esac
;;
esac
else
?X: Try to identify sony's NEWS-OS (BSD unix)
if $test -f /vmunix -a -f $src/hints/news_os.sh; then
(what /vmunix | UU/tr '[A-Z]' '[a-z]') > UU/kernel.what 2>&1
if $contains news-os UU/kernel.what >/dev/null 2>&1; then
    osname=news_os
fi
$rm -f UU/kernel.what
?X: Maybe it's OS/2 or DOS or something similar
elif $test -d c:/.; then
    set X $myuname
    osname=os2
    osvers="$5"

```

```
fi
```

```
fi
```

```
: Try to determine whether config.sh was made on this system
```

```
case "$config_sh" in
```

```
)
```

```
?X: indentation wrong on purpose--RAM
```

```
dflt=n
```

```
case "$knowitall" in
```

```
)
```

```
if test -f ../config.sh; then
```

```
if $contains
```

```
myuname= ../config.sh >/dev/null 2>&1; then
```

```
eval "`$grep myuname= ../config.sh`"
```

```
fi
```

```
if test "X$myuname" = "X$newmyuname"; then
```

```
dflt=y
```

```
fi
```

```
fi
```

```
::
```

```
*) dflt=y;;
```

```
esac
```

```
: Get old answers from config file if it was generated on the same system
```

```
hint=default
```

```
if $test -f ../config.sh; then
```

```
echo " "
```

```
rp="I see a config.sh file. Shall I use it to set the defaults?"
```

```
. ./myread
```

```
case "$ans" in
```

```
n*|N*) echo "OK, I'll ignore it."
```

```
mv ../config.sh ../config.sh.old
```

```
myuname="$newmyuname"
```

```
::
```

```
*) echo "Fetching default answers from your old config.sh file..." >&4
```

```
tmp_n="$n"
```

```
tmp_c="$c"
```

```
tmp_sh="$sh"
```

```
../config.sh
```

```
cp ../config.sh .
```

```
n="$tmp_n"
```

```
c="$tmp_c"
```

```
hint=previous
```

```
::
```

```
esac
```

```
fi
```

```
?X: remember, case indentation is wrong--RAM
```

```
::
```

```

*)
echo " "
echo "Fetching default answers from $config_sh..." >&4
tmp_n="$n"
tmp_c="$c"
tmp_sh="$sh"
cd ..
?X: preserve symbolic links, if any
cp $config_sh config.sh 2>/dev/null
chmod +w config.sh
. ./config.sh
cd UU
cp ../config.sh
.
n="$tmp_n"
c="$tmp_c"
hint=previous
;;
esac
?X: Older versions did not always set $sh.
case "$sh" in
") sh="$tmp_sh" ;;
esac
$test "$soverride" && . ./optdef.sh

: Restore computed paths
for file in $loclist $strylist; do
eval $file="\$_$file"
done

. ./checkcc
?X: Cross-compiling support
case "$targetarch" in
") ;;
*) hostarch=$osname
osname=`echo $targetarch|sed 's,^[^-]*-,`
osvers=""
;;
esac

@if { test -d ../hints }
: Offer them some hints based on their OS
cd ..
?X: Since we are now at the root of the source tree, we must use $src
?X: to access the sources and not $rsrc. See src.U for details...
if $test ! -f config.sh; then
$cat <<EOM

```

First time through, eh? I have some defaults handy for some systems that need some extra help getting the Configure answers right:

EOM

```
(cd $src/hints; ls -C *.sh) | $sed 's/\./ /g' >&4  
dflt=""
```

: Now look for a hint file `osname_osvers`, unless one has been
: specified already.

```
case "$hintfile" in  
"| ' )  
file=`echo "${osname}_${osvers}"  
| $sed -e 's%\.\%_ %g' -e 's%_ %%'`  
: Also try without trailing minor version numbers.  
xfile=`echo $file | $sed -e 's%[_]*$%'`  
xxfile=`echo $xfile | $sed -e 's%[_]*$%'`  
xxxfile=`echo $xxfile | $sed -e 's%[_]*$%'`  
xxxxfile=`echo $xxxfile | $sed -e 's%[_]*$%'`  
case "$file" in  
") dflt=none ;;  
*) case "$osvers" in  
") dflt=$file  
;;  
*) if $test -f $src/hints/$file.sh ; then  
dflt=$file  
elif $test -f $src/hints/$xfile.sh ; then  
dflt=$xfile  
elif $test -f $src/hints/$xxfile.sh ; then  
dflt=$xxfile  
elif $test -f $src/hints/$xxxfile.sh ; then  
dflt=$xxxfile  
elif $test -f $src/hints/$xxxxfile.sh ; then  
dflt=$xxxxfile  
elif $test -f "$src/hints/${osname}.sh" ; then  
dflt="${osname}"  
else  
dflt=none  
fi  
;;  
esac  
;;  
esac  
if $test -f Policy.sh ; then  
case "$dflt" in  
*Policy*) ;;  
none) dflt="Policy" ;;  
*) dflt="Policy $dflt" ;;  
esac
```

```

fi
;;
*)
dflt=`echo
$hintfile | $sed 's/\.sh$/'^
;;
esac

```

```

if $test -f Policy.sh ; then
$cat <<EOM

```

There's also a Policy hint file available, which should make the site-specific (policy) questions easier to answer.

EOM

```

fi

```

```

$cat <<EOM

```

You may give one or more space-separated answers, or "none" if appropriate. A well-behaved OS will have no hints, so answering "none" or just "Policy" is a good thing. DO NOT give a wrong version or a wrong OS.

EOM

```

rp="Which of these apply, if any?"
. UU/myread
tans=$ans
for file in $tans; do
if $test X$file = XPolicy -a -f Policy.sh; then
. Policy.sh
$cat Policy.sh >> UU/config.sh
elif $test -f $src/hints/$file.sh; then
. $src/hints/$file.sh
$cat $src/hints/$file.sh >> UU/config.sh
elif $test X"$tans" = X -o X"$tans" = Xnone ; then
: nothing
else
: Give one chance to correct a possible typo.
echo "$file.sh does not exist"
dflt=$file
rp="hint to use instead?"
. UU/myread
for file in $ans; do
if $test -f "$src/hints/$file.sh";
then
. $src/hints/$file.sh
$cat $src/hints/$file.sh >> UU/config.sh

```

```

elif $test X$sans = X -o X$sans = Xnone ; then
    : nothing
else
    echo "$file.sh does not exist -- ignored."
fi
done
fi
done

hint=recommended
: Remember our hint file for later.
if $test -f "$src/hints/$file.sh" ; then
    hintfile="$file"
else
    hintfile=""
fi
fi
cd UU
?X: From here on, we must use $src instead of $src

```

```

@end
: Process their -A options
./posthint.sh

```

```

@if osname || osvers
: Ask them to confirm the OS name
cat << EOM

```

Configure uses the operating system name and version to set some defaults. The default value is probably right if the name rings a bell. Otherwise, since spelling matters for me, either accept the default or answer "none" to leave it blank.

```

EOM
@end
@if osname
case "$osname" in
    '| ')
        case "$hintfile" in
            '| |none) dflt=none ;;
            *) dflt=`echo $hintfile | $sed -e 's/\.sh$//' -e 's/_.*$//'^` ;;
        esac
        ;;
        *) dflt="$osname" ;;
    esac
rp="Operating
system name?"
./myread

```

```

case "$ans" in
none) osname="";
*) osname=`echo "$ans" | $sed -e 's/[ ][ ]*/_/g' | ./tr '[A-Z]' '[a-z]`;
esac
@end
@if osvers
@if osname
echo " "
@end
case "$osvers" in
'| ')
case "$hintfile" in
'| |none) dflt=none ;;
*) dflt=`echo $hintfile | $sed -e 's/\.sh$/' -e 's/^[^_]*//`
dflt=`echo $dflt | $sed -e 's/^\_/ ' -e 's/_/./g`
case "$dflt" in
'| ') dflt=none ;;
esac
;;
esac
;;
*) dflt="$osvers" ;;
esac
rp="Operating system version?"
./myread
case "$ans" in
none) osvers="";
*) osvers="$ans" ;;
esac

@end

```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/Oldconfig.U
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: Null.U 1 2006-08-24 12:32:52Z rmanfredi \$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic Licence,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic Licence; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: Null.U,v \$

?RCS: Revision 3.0 1993/08/18 12:05:10 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?X:
?X: This unit ends up producing shell code to set all variables to ". This
?X: probably isn't necessary, but I'm paranoid. About certain things.
?X:
?MAKE:Null: Head
?MAKE: -pick add.Null \$@ %<

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/Null.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$
?RCS:
?RCS: Copyright (c) 1999 Jarkko Hietaniemi
?RCS:
?RCS: You may distribute under the terms of either the GNU General Public
?RCS: License or the Artistic License, as specified in the README file.
?RCS:
?MAKE:ivdformat uvuformat uvoformat uvxformat uvXUformat \
nvEUformat nvFUformat nvGUformat \
nveformat nvfformat nvgformat: \
ivsize longsize intsize shortsize \
sPRId64 sPRIu64 sPRIo64 sPRIx64 sPRIXU64 \
uselongdouble d_longdbl usequadmath d_PRIgldbl \
sPRIEUdbl sPRIFUdbl sPRIGUdbl sPRIeldbl sPRIfldbl sPRIgldbl \
test echo
?MAKE: -pick add \$@ %<
?S:ivdformat:
?S: This variable contains the format string used for printing
?S: a Perl IV as a signed decimal integer.
?S:.
?S:uvuformat:
?S: This variable contains the format string used for printing
?S: a Perl UV as an unsigned decimal integer.
?S:.
?S:uvoformat:
?S: This variable contains the format string used for printing
?S: a Perl UV as an unsigned
octal integer.
?S:.
?S:uvxformat:
?S: This variable contains the format string used for printing
?S: a Perl UV as an unsigned hexadecimal integer in lowercase abcdef.
?S:.

?S:uvXUformat:

?S: This variable contains the format string used for printing

?S: a Perl UV as an unsigned hexadecimal integer in uppercase ABCDEF.

?S:.

?S:nveformat:

?S: This variable contains the format string used for printing

?S: a Perl NV using %e-ish floating point format.

?S:.

?S:nvffformat:

?S: This variable contains the format string used for printing

?S: a Perl NV using %f-ish floating point format.

?S:.

?S:nvgformat:

?S: This variable contains the format string used for printing

?S: a Perl NV using %g-ish floating point format.

?S:.

?S:nvEUformat:

?S: This variable contains the format string used for printing

?S: a Perl NV using %E-ish floating point format.

?S:.

?S:nvFUformat:

?S: This variable contains the format string used for printing

?S: a Perl NV using %F-ish floating point format.

?S:.

?S:nvGUformat:

?S: This

variable contains the format string used for printing

?S: a Perl NV using %G-ish floating point format.

?S:.

?C:IVdf:

?C: This symbol defines the format string used for printing a Perl IV

?C: as a signed decimal integer.

?C:.

?C:UVuf:

?C: This symbol defines the format string used for printing a Perl UV

?C: as an unsigned decimal integer.

?C:.

?C:UVof:

?C: This symbol defines the format string used for printing a Perl UV

?C: as an unsigned octal integer.

?C:.

?C:UVxf:

?C: This symbol defines the format string used for printing a Perl UV

?C: as an unsigned hexadecimal integer in lowercase abcdef.

?C:.

?C:UVXf:

?C: This symbol defines the format string used for printing a Perl UV

?C: as an unsigned hexadecimal integer in uppercase ABCDEF.

```

?C:.
?C:NVef:
?C: This symbol defines the format string used for printing a Perl NV
?C: using %e-ish floating point format.
?C:.
?C:NVff:
?C: This symbol defines the format string used for printing a Perl NV
?C: using %f-ish floating point
format.
?C:.
?C:NVgf:
?C: This symbol defines the format string used for printing a Perl NV
?C: using %g-ish floating point format.
?C:.
?C:NVEf:
?C: This symbol defines the format string used for printing a Perl NV
?C: using %E-ish floating point format.
?C:.
?C:NVff:
?C: This symbol defines the format string used for printing a Perl NV
?C: using %F-ish floating point format.
?C:.
?C:NVGf:
?C: This symbol defines the format string used for printing a Perl NV
?C: using %G-ish floating point format.
?C:.
?H:#define IVdf $ivdformat /**/
?H:#define UVuf $uvuformat /**/
?H:#define UVof $uvoformat /**/
?H:#define UVxf $uvxf format /**/
?H:#define UVXf $uvXUformat /**/
?H:#define NVef $nveformat /**/
?H:#define NVff $nvffformat /**/
?H:#define NVgf $nvformat /**/
?H:#define NVEf $nvEUformat /**/
?H:#define NVFf $nvFUformat /**/
?H:#define NVGf $nvGUformat /**/
?H:.
: Check format strings for internal types
echo " "
$echo "Checking the format strings to be used for Perl's
internal types..." >&4

if $test X"$ivsize" = X8; then
ivdformat="$sPRId64"
uvuformat="$sPRIu64"
uvoformat="$sPRIO64"
uvxf format="$sPRIx64"

```

```

uvXUformat="$sPRIXU64"
else
if $test X"$ivsize" = X"$longsize"; then
ivdformat="ld"
uvuformat="lu"
uvoformat="lo"
uvxformat="lx"
uvXUformat="lX"
else
if $test X"$ivsize" = X"$intsize"; then
ivdformat="d"
uvuformat="u"
uvoformat="o"
uvxformat="x"
uvXUformat="X"
else
: far out
if $test X"$ivsize" = X"$shortsize"; then
ivdformat="hd"
uvuformat="hu"
uvoformat="ho"
uvxformat="hx"
uvXUformat="hX"
fi
fi
fi
fi

if $test X"$usequadmath" = X"$define"; then
nveformat="Qe"
nvffformat="Qf"
nvgformat="Qg"
nvEUformat="QE"
nvFUformat="QF"
nvGUformat="QG"
else
if $test X"$uselongdouble" = X"$define" -a X"$d_longdbl" = X"$define" -a X"$d_PRIGldbl" = X"$define"; then
nveformat="$sPRIEldbl"
nvffformat="$sPRIFldbl"
nvgformat="$sPRIGldbl"
nvEUformat="$sPRIEUldbl"
nvFUformat="$sPRIFUldbl"
nvGUformat="$sPRIGUldbl"
else
nveformat="e"
nvffformat="f"
nvgformat="g"
nvEUformat="E"

```

```
nvFUformat="F"  
nvGUformat="G"  
fi  
fi
```

```
case "$svdformat" in  
) echo "$0: Fatal: failed to find format strings, cannot continue." >&4  
  exit 1  
  ;;  
esac
```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-  
debian-perl-5.26.1/U/perl/perlxf.U
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_getnetbyaddr_r.U,v 0RCS:

?RCS: Copyright (c) 2002,2003 Jarkko Hietaniemi

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?RCS: Generated by the reentr.pl from the Perl 5.8 distribution.

?RCS:

?MAKE:d_getnetbyaddr_r getnetbyaddr_r_proto: Inlibc Protochk Hasproto \
i_systypes usethreads i_netdb extern_C

?MAKE: -pick add \$@ %<

?S:d_getnetbyaddr_r:

?S: This variable conditionally defines the HAS_GETNETBYADDR_R symbol,

?S: which indicates to the C program that the getnetbyaddr_r()

?S: routine is available.

?S:.

?S:getnetbyaddr_r_proto:

?S: This variable encodes the prototype of getnetbyaddr_r.

?S: It is zero if d_getnetbyaddr_r is undef, and one of the

?S: REENTRANT_PROTO_T_ABC macros of reentr.h if d_getnetbyaddr_r

?S: is defined.

?S:.

?C:HAS_GETNETBYADDR_R:

?C: This symbol, if defined, indicates that
the getnetbyaddr_r routine

?C: is available to getnetbyaddr re-entrantly.

?C:.

?C:GETNETBYADDR_R_PROTO:

?C: This symbol encodes the prototype of getnetbyaddr_r.

?C: It is zero if d_getnetbyaddr_r is undef, and one of the

?C: REENTRANT_PROTO_T_ABC macros of reentr.h if d_getnetbyaddr_r

?C: is defined.

```

?C:.
?H:#$d_getnetbyaddr_r HAS_GETNETBYADDR_R /**/
?H:#define GETNETBYADDR_R_PROTO $getnetbyaddr_r_proto /**/
?H:.
?T:try hdrs d_getnetbyaddr_r_proto
: see if getnetbyaddr_r exists
set getnetbyaddr_r d_getnetbyaddr_r
eval $inlibc
case "$d_getnetbyaddr_r" in
"$define")
hdrs="$i_systypes sys/types.h define stdio.h $i_netdb netdb.h"
case "$d_getnetbyaddr_r_proto:$usethreads" in
":define") d_getnetbyaddr_r_proto=define
set d_getnetbyaddr_r_proto getnetbyaddr_r $hdrs
eval $hasproto ;;
*) ;;
esac
case "$d_getnetbyaddr_r_proto" in
define)
case "$getnetbyaddr_r_proto" in
"|0) try='int getnetbyaddr_r(unsigned long, int, struct netent*, char*, size_t, struct netent**, int*);'
./protochk
"$extern_C $try" $hdrs && getnetbyaddr_r_proto=I_UISBWRE ;;
esac
case "$getnetbyaddr_r_proto" in
"|0) try='int getnetbyaddr_r(long, int, struct netent*, char*, int);'
./protochk "$extern_C $try" $hdrs && getnetbyaddr_r_proto=I_LISBI ;;
esac
case "$getnetbyaddr_r_proto" in
"|0) try='struct netent* getnetbyaddr_r(in_addr_t, int, struct netent*, char*, int);'
./protochk "$extern_C $try" $hdrs && getnetbyaddr_r_proto=S_TISBI ;;
esac
case "$getnetbyaddr_r_proto" in
"|0) try='struct netent* getnetbyaddr_r(long, int, struct netent*, char*, int);'
./protochk "$extern_C $try" $hdrs && getnetbyaddr_r_proto=S_LISBI ;;
esac
case "$getnetbyaddr_r_proto" in
"|0) try='int getnetbyaddr_r(in_addr_t, int, struct netent*, struct netent_data*);'
./protochk "$extern_C $try" $hdrs && getnetbyaddr_r_proto=I_TISD ;;
esac
case "$getnetbyaddr_r_proto" in
"|0) try='int getnetbyaddr_r(long, int, struct netent*, struct netent_data*);'
./protochk "$extern_C $try" $hdrs && getnetbyaddr_r_proto=I_LISD
;;
esac
case "$getnetbyaddr_r_proto" in
"|0) try='int getnetbyaddr_r(int, int, struct netent*, struct netent_data*);'
./protochk "$extern_C $try" $hdrs && getnetbyaddr_r_proto=I_IISD ;;

```

```

esac
case "$getnetbyaddr_r_proto" in
"(0) try='int getnetbyaddr_r(uint32_t, int, struct netent*, char*, size_t, struct netent**, int*);'
./protochk "$extern_C $try" $hdrs && getnetbyaddr_r_proto=I_uISBWRE ;;
esac
case "$getnetbyaddr_r_proto" in
"(0) d_getnetbyaddr_r=undef
    getnetbyaddr_r_proto=0
    echo "Disabling getnetbyaddr_r, cannot determine prototype." >&4 ;;
*) case "$getnetbyaddr_r_proto" in
    REENTRANT_PROTO*) ;;
    *) getnetbyaddr_r_proto="REENTRANT_PROTO_$getnetbyaddr_r_proto" ;;
esac
echo "Prototype: $try" ;;
esac
;;
*) case "$usetreads" in
define) echo "getnetbyaddr_r has no prototype, not using it." >&4 ;;
esac
d_getnetbyaddr_r=undef
getnetbyaddr_r_proto=0
;;
esac
;;
*) getnetbyaddr_r_proto=0
;;
esac

```

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/threads/d_getnetbyaddr_r.U

No license file was found, but licenses were detected in source scan.

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?MAKE:d_erf: Inlibc

?MAKE: -pick add \$@ %<

?S:d_erf:

?S: This variable conditionally defines the HAS_ERF symbol, which

?S: indicates to the C program that the erf() routine is available.

?S:.

?C:HAS_ERF:

?C: This symbol, if defined, indicates that the erf routine is

?C: available to do the error function.

?C:.

?H:#\$d_erf HAS_ERF /**/

?H:.

```
?LINT:set d_erf
: see if erf exists
set erf d_erf
eval $inlibc
```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/perl/d_erf.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id$
```

```
?RCS:
```

```
?RCS: Copyright (c) 1999, Jarkko Hietaniemi
```

```
?RCS:
```

```
?RCS: You may redistribute only under the terms of the Artistic License,
```

```
?RCS: as specified in the README file that comes with the distribution.
```

```
?RCS: You may reuse parts of this distribution only within the terms of
```

```
?RCS: that same Artistic License; a copy of which may be found at the root
```

```
?RCS: of the source tree for dist 3.0.
```

```
?RCS:
```

```
?MAKE:d_madvise: Inlibc
```

```
?MAKE: -pick add $@ %<
```

```
?S:d_madvise:
```

```
?S: This variable conditionally defines HAS_MADVISE if madvise() is
```

```
?S: available to map a file into memory.
```

```
?S:.
```

```
?C:HAS_MADVISE:
```

```
?C: This symbol, if defined, indicates that the madvise system call is
```

```
?C: available to map a file into memory.
```

```
?C:.
```

```
?H:#$d_madvise HAS_MADVISE /**/
```

```
?H:.
```

```
?LINT:set d_madvise
```

```
: see if madvise exists
```

```
set madvise d_madvise
```

```
eval $inlibc
```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/perl/d_madvise.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: ipc.U 1 2006-08-24 12:32:52Z rmanfredi $
```

```
?RCS:
```

```
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
```

```
?RCS:
```

```
?RCS: You may redistribute only under the terms of the Artistic Licence,
```

```
?RCS: as specified in the README file that comes with the distribution.
```

?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: \$Log: ipc.U,v \$
?RCS: Revision 3.0 1993/08/18 12:08:53 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:ipc serve_shm serve_msg serve_inet_udp serve_inet_tcp serve_unix_udp \
serve_unix_tcp: test Myread Oldconfig d_socket d_msg d_shm d_sem
?MAKE: -pick add \$@ %<
?LINT:use d_msg d_sem
?S:ipc:
?S: This variable holds the type of IPC service we'll be using. Values
?S: include "ip", "shm", "msg", "cms" and "os9". We don't worry about
?S: cms or os9
here, because Configure doesn't run in those places--HMS.
?S:.
?S:serve_shm:
?S: This variable controls the definition of SERVE_SHM, which tells the
?S: C program to use USG shared memory for IPC.
?S:.
?S:serve_msg:
?S: This variable controls the definition of SERVE_MSG, which tells the
?S: C program to use USG message queues for IPC.
?S:.
?S:serve_inet_udp:
?S: This variable controls the definition of SERVE_INET_UDP, which tells
?S: the C program to enable InterNet-domain UDP support for IPC.
?S:.
?S:serve_inet_tcp:
?S: This variable controls the definition of SERVE_INET_TCP, which tells
?S: the C program to enable InterNet-domain TCP support for IPC.
?S:.
?S:serve_unix_udp:
?S: This variable controls the definition of SERVE_UNIX_UDP, which tells
?S: the C program to enable Unix-domain UDP support for IPC.
?S:.
?S:serve_unix_tcp:
?S: This variable controls the definition of SERVE_UNIX_TCP, which tells
?S: the C program to enable Unix-domain TCP support for IPC.
?S:.
?C:SERVE_SHM:
?C: If
defined, tells the C program to use USG shared memory for IPC.
?C:.
?C:SERVE_MSG:
?C: If defined, tells the C program to use USG message queues for IPC.

```

?C:.
?C:SERVE_INET_UDP:
?C: If defined, tells the C program to enable InterNet-domain UDP
?C: support for IPC.
?C:.
?C:SERVE_INET_TCP:
?C: If defined, tells the C program to enable InterNet-domain TCP
?C: support for IPC.
?C:.
?C:SERVE_UNIX_UDP:
?C: If defined, tells the C program to enable Unix-domain UDP
?C: support for IPC.
?C:.
?C:SERVE_UNIX_TCP:
?C: If defined, tells the C program to enable Unix-domain TCP
?C: support for IPC.
?C:.
?H:#$serve_shm SERVE_SHM /**/
?H:#$serve_msg SERVE_MSG /**/
?H:#$serve_inet_udp SERVE_INET_UDP /**/
?H:#$serve_inet_tcp SERVE_INET_TCP /**/
?H:#$serve_unix_udp SERVE_UNIX_UDP /**/
?H:#$serve_unix_tcp SERVE_UNIX_TCP /**/
?H:.
?X: FIXME -- RAM
?INIT:serve_shm=""
?INIT:serve_msg="$undef"
?INIT:serve_inet_udp=""
?INIT:serve_inet_tcp=""
?INIT:serve_unix_udp=""
?INIT:serve_unix_tcp=""
: get IPC mechanism
echo
" "
ipc=""
while $test -z "$ipc"
do
if $test "$ipc" != "shm" -a "$d_socket" = "$define"; then
ipc=""
if $test "$serve_inet_udp" = "$undef"; then
dflt=n
else
dflt=y
fi
rp='Provide InterNet-domain UDP service?'
./myread
dflt=""
case "$ans" in

```

```

n*) serve_inet_udp="$undef";;
*)
serve_inet_udp="$define"
ipc='ip'
;;
esac

if $test "$serve_inet_tcp" = "$define"; then
dflt=y
else
dflt=n
fi
rp='Provide InterNet-domain TCP service?'
./myread
dflt=""
case "$ans" in
n*) serve_inet_tcp="$undef";;
*)
serve_inet_tcp="$define"
ipc='ip'
;;
esac

if $test "$serve_unix_udp" = "$define"; then
dflt=y
else
dflt=n
fi
rp='Provide Unix-domain UDP service?'
./myread
dflt=""
case "$ans" in
n*) serve_unix_udp="$undef";;
*)
serve_unix_udp="$define"
ipc='ip'
;;
esac

if $test "$serve_unix_tcp" = "$define"; then
dflt=y
else
dflt=n
fi
rp='Provide Unix-domain TCP service?'
./myread
dflt=""
case

```

```

"$ans" in
n*) serve_unix_tcp="$undef";;
*)
  serve_unix_tcp="$define"
  ipc='ip'
  ;;
esac
else
  serve_inet_udp="$undef"
  serve_inet_tcp="$undef"
  serve_unix_udp="$undef"
  serve_unix_tcp="$undef"
fi
if $test "$ipc" != "ip" -a "$d_shm" = "$define"; then
  echo "Providing USG shared memory IPC support." >&4
  serve_shm="$define"
  ipc='shm'
else
  serve_shm="$undef"
fi
if $test -z "$ipc"; then
  echo "You must select an IPC mechanism." >&4
fi
done

```

Found in path(s):

```

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/ipc.U

```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: End.U,v \$

?RCS: Revision 3.0 1993/08/18 12:04:51 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?X:

?X: This unit serves as the goal which forces make to choose all the units that

?X: ask questions. The \$W on the ?MAKE: line is the list of all symbols wanted.

?X: To force any unit to be included, copy this unit to your private U directory

?X: and add the name of the unit desired to the ?MAKE: dependency line.

?X:

?MAKE:End: \$W

?MAKE: -pick add \$@ %<

?LINT:use \$W

: end of configuration

questions

echo " "

echo "End of configuration questions."

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/End.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: i_float.U 1 2006-08-24 12:32:52Z rmanfredi \$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic Licence,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic Licence; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: Original Author: Andy Dougherty <doughera@lafcol.lafayette.edu>

?RCS:

?RCS: \$Log: i_float.U,v \$

?RCS: Revision 3.0.1.1 1994/08/29 16:21:57 ram

?RCS: patch32: created by ADO

?RCS:

?MAKE:i_float: Inhdr

?MAKE: -pick add \$@ %<

?S:i_float:

?S: This variable conditionally defines the I_FLOAT symbol, and indicates

?S: whether a C program may include <float.h> to get symbols like DBL_MAX

?S: or DBL_MIN, i.e. machine dependent floating point values.

?S:.

?C:I_FLOAT:

?C: This

symbol, if defined, indicates to the C program that it should

?C: include <float.h> to get definition of symbols like DBL_MAX or

?C: DBL_MIN, i.e. machine dependent floating point values.

?C:.

?H:#\$i_float I_FLOAT /**/

?H:.

?LINT:set i_float

: see if this is a float.h system

```
set float.h i_float
eval $inhdr
```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/i_float.U
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1999 Jarkko Hietaniemi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 3.0.

?RCS:

?MAKE:sitehtml1dir sitehtml1direxp installsitehtml1dir: Getfile \

Setprefixvar prefix siteprefix html1dir sed

?MAKE: -pick add \$@ %<

?Y:TOP

?D:sitehtml1dir="

?S:sitehtml1dir:

?S: This variable contains the name of the directory in which site-specific

?S: html source pages are to be put. It is the responsibility of the

?S: Makefile.SH to get the value of this into the proper command.

?S: You must be prepared to do the ~name expansion yourself.

?S: The standard distribution will put nothing in this directory.

?S: After perl

has been installed, users may install their own local

?S: html pages in this directory with

?S: MakeMaker Makefile.PL

?S: or equivalent. See INSTALL for details.

?S:.

?D:sitehtml1direxp="

?S:sitehtml1direxp:

?S: This variable is the same as the sitehtml1dir variable, but is filename

?S: expanded at configuration time, for convenient use in makefiles.

?S:.

?D:installsitehtml1dir="

?S:installsitehtml1dir:

?S: This variable is really the same as sitehtml1direxp, unless you are using

?S: AFS in which case it points to the read/write location whereas

?S: html1direxp only points to the read-only access location. For extra

?S: portability, you should only use this variable within your makefiles.

?S:.

?LINT:change prefixvar

```

?LINT:set installsitehtml dir
?LINT:set sitehtml dir
?LINT:set sitehtml direxp
: determine where add-on html pages go
: There is no standard location, so try to copy the previously-selected
: directory structure for the core html pages.
case "$sitehtml dir" in
")
  dflt=`echo "$html dir" | $sed "s#^$prefix#$siteprefix#" ` ;;
*) dflt=$sitehtml dir ;;
esac
case "$dflt" in
"|' ') dflt=none ;;
esac
fn=dn+~
rp='Pathname where the site-specific html pages should be installed?'
./getfile
prefixvar=sitehtml dir
./setprefixvar

```

Found in path(s):

```

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/installdirs/sitehtml dir.U

```

No license file was found, but licenses were detected in source scan.

```

?RCS: $Id: d_time.U,v 3.0.1.2 1995/07/25 14:07:43 ram Exp $
?RCS:
?RCS: Copyright (c) 1991-1993, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 3.0.
?RCS:
?RCS: $Log: d_time.U,v $
?RCS: Revision 3.0.1.2 1995/07/25 14:07:43 ram
?RCS: patch56: typo fix, sytem -> system
?RCS:
?RCS: Revision 3.0.1.1 1994/10/29 16:16:38 ram
?RCS: patch36: now uses new Typedef unit to compute type information (ADO)
?RCS:
?RCS: Revision 3.0 1993/08/18 12:07:45 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?X: Maybe <sys/types.h> should be included?
?X:INC: i_systypes
?MAKE:d_time timetype: Csym Setvar Findhdr Myread Typedef

```

```

?MAKE: -pick
add $@ %<
?S:d_time:
?S: This variable conditionally defines the HAS_TIME symbol, which indicates
?S: that the time() routine exists. The time() routine is normally
?S: provided on UNIX systems.
?S:.
?S:timetype:
?S: This variable holds the type returned by time(). It can be long,
?S: or time_t on BSD sites (in which case <sys/types.h> should be
?S: included). Anyway, the type Time_t should be used.
?S:.
?C:HAS_TIME (TIMER):
?C: This symbol, if defined, indicates that the time() routine exists.
?C:.
?C:Time_t (TIMETYPE):
?C: This symbol holds the type returned by time(). It can be long,
?C: or time_t on BSD sites (in which case <sys/types.h> should be
?C: included).
?C:.
?H:#$d_time HAS_TIME /**/
?H:#define Time_t $timetype /* Time type */
?H:.
?LINT:set d_time
: see if time exists
echo " "
?X: MPE/iX needs this protection of hint values.
?X: See d_sterror.U for more explanation.
if test "$d_time" = X -o X"$timetype" = X; then
    if set time val -f d_time; eval $csym; $val;
then
    echo 'time() found.' >&4
    val="$define"
    rp="What is the type returned by time() on this system?"
    set time_t timetype long stdio.h sys/types.h
    eval $typedef_ask
    else
    echo 'time() not found, hope that will do.' >&4
    val="$undef"
    timetype='int';
    fi
    set d_time
    eval $setvar
fi

```

Found in path(s):

```

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/typedefs/d_time.U

```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: d_alarm.U 1 2006-08-24 12:32:52Z rmanfredi $
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: Original Author: Andy Dougherty <doughera@lafcol.lafayette.edu>
?RCS:
?RCS: $Log: d_alarm.U,v $
?RCS: Revision 3.0.1.1 1994/08/29 16:06:58 ram
?RCS: patch32: created by ADO
?RCS:
?MAKE:d_alarm: Inlibc
?MAKE: -pick add $@ %<
?S:d_alarm:
?S: This variable conditionally defines the HAS_ALARM symbol, which
?S: indicates to the C program that the alarm() routine is available.
?S:.
?C:HAS_ALARM :
?C: This symbol, if defined, indicates that the alarm routine is
?C: available.
?C:.
?H:#$d_alarm
HAS_ALARM /**/
?H:.
?LINT:set d_alarm
: see if alarm exists
set alarm d_alarm
eval $inlibc
```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/d_alarm.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: d_setvbuf.U,v 3.0.1.1 1994/08/29 16:11:57 ram Exp $
?RCS:
?RCS: Copyright (c) 1998 Andy Dougherty
?RCS:
?RCS: You may distribute under the terms of either the GNU General Public
?RCS: License or the Artistic License, as specified in the README file.
?RCS:
```

?RCS: Original Author: Andy Dougherty <doughera@lafcol.lafayette.edu>

?RCS:

?RCS: \$Log: d_setvbuf.U,v \$

?RCS:

?MAKE:d_setvbuf: Inlibc

?MAKE: -pick add \$@ %<

?S:d_setvbuf:

?S: This variable conditionally defines the HAS_SETVBUF symbol, which

?S: indicates to the C program that the setvbuf() routine is available

?S: to change buffering on an open stdio stream.

?S:.

?C:HAS_SETVBUF :

?C: This symbol, if defined, indicates that the setvbuf routine is

?C: available to change buffering on an open stdio stream.

?C: to a line-buffered mode.

?C:.

?H:#\$d_setvbuf HAS_SETVBUF /**/

?H:.

?LINT:set d_setvbuf

: see if setvbuf exists

set setvbuf d_setvbuf

eval \$inlibc

Found

in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/modified/d_setvbuf.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1999, Jarkko Hietaniemi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 3.0.

?RCS:

?MAKE:d_sched_get_priority_min: Inlibc

?MAKE: -pick add \$@ %<

?S:d_sched_get_priority_min:

?S: This variable conditionally defines HAS_SCHED_GET_PRIORITY_MIN if

?S: sched_get_priority_min() is available to get the minimum scheduling

?S: priority.

?S:.

?C:HAS_SCHED_GET_PRIORITY_MIN:

?C: This symbol, if defined, indicates that the sched_get_priority_min

```
?C: system call is available to get the minimum scheduling priority.
?C:.
?H:#$d_sched_get_priority_min HAS_SCHED_GET_PRIORITY_MIN /**/
?H:.
?LINT:set d_sched_get_priority_min
:
  see if sched_get_priority_min exists
set sched_get_priority_min d_sched_get_priority_min
eval $inlibc
```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/perl/d_sched_gpmin.U
No license file was found, but licenses were detected in source scan.
```

```
?RCS: $Id: d_setregid.U 1 2006-08-24 12:32:52Z rmanfredi $
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: $Log: d_setregid.U,v $
?RCS: Revision 3.0 1993/08/18 12:07:12 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:d_setregid d_setresgid: Inlibc
?MAKE: -pick add $@ %<
?S:d_setregid:
?S: This variable conditionally defines HAS_SETREGID if setregid() is
?S: available to change the real and effective gid of the current
?S: process.
?S:.
?S:d_setresgid:
?S: This variable conditionally defines HAS_SETRESGID if setresgid() is
?S: available to change
?S: the real, effective and saved gid of the current
?S: process.
?S:.
?C:HAS_SETREGID (SETREGID):
?C: This symbol, if defined, indicates that the setregid routine is
?C: available to change the real and effective gid of the current
?C: process.
?C:.
?C:HAS_SETRESGID (SETRESGID):
```

?C: This symbol, if defined, indicates that the setresgid routine is
?C: available to change the real, effective and saved gid of the current
?C: process.
?C:.
?H:#\$d_setregid HAS_SETREGID /**/
?H:#\$d_setresgid HAS_SETRESGID /**/
?H:.
?LINT: set d_setregid d_setresgid
: see if setregid exists
set setregid d_setregid
eval \$inlibc
set setresgid d_setresgid
eval \$inlibc

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/d_setregid.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: i_sysvfs.U,v \$
?RCS:
?RCS: Copyright (c) 1999 Jarkko Hietaniemi
?RCS:
?RCS: You may distribute under the terms of either the GNU General Public
?RCS: License or the Artistic License, as specified in the README file.
?RCS:
?MAKE:i_sysvfs: Inhdr Hasfield
?MAKE: -pick add \$@ %<
?S:i_sysvfs:
?S: This variable conditionally defines the I_SYSVFS symbol,
?S: and indicates whether a C program should include <sys/vfs.h>.
?S:.
?C:I_SYS_VFS:
?C: This symbol, if defined, indicates that <sys/vfs.h> exists and
?C: should be included.
?C:.
?H:#\$i_sysvfs I_SYS_VFS /**/
?H:.
?LINT:set i_sysvfs
: see if this is a sys/vfs.h system
set sys/vfs.h i_sysvfs
eval \$inhdr

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/i_sysvfs.U

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: d_stat.U 1 2006-08-24 12:32:52Z rmanfredi $
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: $Log: d_stat.U,v $
?RCS: Revision 3.0 1993/08/18 12:07:28 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:d_stat: Inlibc
?MAKE: -pick add $@ %<
?S:d_stat:
?S: This variable conditionally defines HAS_STAT if stat() is
?S: available to get file status.
?S:.
?C:HAS_STAT (STAT):
?C: This symbol, if defined, indicates that the stat routine is
?C: available to get file status.
?C:.
?H:#$d_stat HAS_STAT /**/
?H:.
?LINT:set d_stat
: see if stat exists
set
stat d_stat
eval $inlibc
```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/d_stat.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: newsspool.U 1 2006-08-24 12:32:52Z rmanfredi $
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: $Log: newsspool.U,v $
```

?RCS: Revision 3.0 1993/08/18 12:09:24 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?MAKE:newsspool newsspoolexp: Getfile Oldconfig

?MAKE: -pick add \$@ %<

?S:newsspool:

?S: This variable contains the eventual value of the NEWSSPOOL symbol,

?S: which is the directory name where news articles are spooled. It

?S: may have a ~ on the front of it.

?S:.

?S:newsspoolexp:

?S: This is the same as the newsspool variable, but is
filename expanded

?S: at configuration time, for programs not wanting to deal with it at

?S: run-time.

?S:.

?C:NEWSSPOOL:

?C: This symbol contains the directory name where news articles are

?C: spooled. The program must be prepared to do ~ expansion on it.

?C:.

?C:NEWSSPOOL_EXP:

?C: This is the same as NEWSSPOOL, but is filename expanded at

?C: configuration time, for use in programs not willing to do so

?C: at run-time.

?C:.

?H:#define NEWSSPOOL "\$newsspool" /**/

?H:#define NEWSSPOOL_EXP "\$newsspoolexp" /**/

?H:.

: locate news spool directory

case "\$newsspool" in

)

dflt=/usr/spool/news

;;

*) dflt="\$newsspool";;

esac

echo " "

fn=d~

rp='Where are news spooled?'

./getfile

newsspool="\$ans"

newsspoolexp="\$ansexp"

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/newsspool.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:
 ?RCS: Copyright (c) 1999, Jarkko Hietaniemi
 ?RCS:
 ?RCS: You may redistribute only under the terms of the Artistic License,
 ?RCS: as specified in the README file that comes with the distribution.
 ?RCS: You may reuse parts of this distribution only within the terms of
 ?RCS: that same Artistic License; a copy of which may be found at the root
 ?RCS: of the source tree for dist 3.0.
 ?RCS:
 ?MAKE:d_shm_unlink: Inlibc
 ?MAKE: -pick add \$@ %<
 ?S:d_shm_unlink:
 ?S: This variable conditionally defines HAS_SHM_UNLINK if shm_unlink() is
 ?S: available to unlink a POSIX shared memory object.
 ?S:.
 ?C:HAS_SHM_UNLINK:
 ?C: This symbol, if defined, indicates that the shm_unlink system call is
 ?C: available to unlink a POSIX shared memory object.
 ?C:.
 ?H:#\$d_shm_unlink HAS_SHM_UNLINK /**/
 ?H:.
 ?LINT:set d_shm_unlink
 : see if shm_unlink exists
 set shm_unlink d_shm_unlink
 eval \$inlibc

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_shm_unlink.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$
 ?RCS:
 ?RCS: Copyright (c) 2000 Jarkko Hietaniemi
 ?RCS:
 ?RCS: You may redistribute only under the terms of the Artistic License,
 ?RCS: as specified in the README file that comes with the distribution.
 ?RCS: You may reuse parts of this distribution only within the terms of
 ?RCS: that same Artistic License; a copy of which may be found at the root
 ?RCS: of the source tree for dist 3.0.
 ?RCS:
 ?MAKE:d_sbrkproto: Hasproto i_unistd
 ?MAKE: -pick add \$@ %<
 ?S:d_sbrkproto:
 ?S: This variable conditionally defines the HAS_SBRK_PROTO symbol,
 ?S: which indicates to the C program that the system provides
 ?S: a prototype for the sbrk() function. Otherwise, it is
 ?S: up to the program to supply one.

?S:
?C:HAS_SBRK_PROTO:
?C: This symbol, if defined, indicates that the system provides
?C: a prototype for the sbrk() function. Otherwise, it is up
?C: to the program to supply one. Good guesses are
?C: extern void* sbrk(int);
?C: extern
void* sbrk(size_t);
?C:.

?H:#\$d_sbrkproto HAS_SBRK_PROTO /**/

?H:.

?LINT:set d_sbrkproto

: see if prototype for sbrk is available

echo " "

set d_sbrkproto sbrk \$i_unistd unistd.h

eval \$hasproto

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_sbrkproto.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: randfunc.U,v \$

?RCS: Revision 3.0 1993/08/18 12:09:39 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?X:

?X: This is the new unit that should be used when random

?X: functions are to be used. It thus makes randbits.U obsolete.

?X:

?MAKE:randfunc mrand seedfunc nrandbits: cat +cc rm test Myread Csym

?MAKE: -pick add \$@ %<

?S:randfunc:

?S: Indicates the name of the random number function to use.

?S: Values include drand48, random, and rand. In C programs,

?S: the 'nrand' macro is defined

to generate uniformly distributed

?S: random numbers over the range [0., 1.] (see mrand and nrand).

?S:.

?S:mrnd:

?S: Indicates the macro to be used to generate normalized
 ?S: random numbers. Uses randfunc, often divided by
 ?S: (double) ((1 << nrandbits) -1) in order to normalize the result.
 ?S: In C programs, the macro 'nrand' is mapped on mrnd.
 ?S:.

?S:seedfunc:

?S: Indicates the random number generating seed function.
 ?S: Values include srand48, srandom, and srand.
 ?S:.

?S:nrandbits:

?S: Indicates how many bits are produced by the function used to
 ?S: generate normalized random numbers.
 ?S:.

?C:nrand:

?C: This macro is to be used to generate uniformly distributed
 ?C: random numbers over the range [0., 1.].
 ?C:.

?C:seednrand:

?C: This symbol defines the macro to be used in seeding the
 ?C: random number generator (see nrand).
 ?C:.

?H:#define nrand() \$mrnd /**/
 ?H:#define seednrand(x) \$seedfunc(x) /**/
 ?H:.

?T:cont val

?LINT:nothere \$nrandbits)

: How can we generate normalized
 random numbers ?
 echo " "
 case "\$randfunc" in
 ")
 if set drand48 val -f; eval \$csym; \$val; then
 dflt="drand48"
 echo "Good, found drand48()." >&4
 elif set random val -f; eval \$csym; \$val; then
 dflt="random"
 echo "OK, found random()." >&4
 else
 dflt="rand"
 echo "Yick, looks like I have to use rand()." >&4
 fi
 echo " "
 ;;
 *)
 dflt="\$randfunc"
 ;;

```

esac
cont=true
while $test "$cont"; do
    rp="Use which function to generate random numbers?"
    . ./myread
    ?X: Invalidates nrandbits if the answer is not the default so
    ?X: that the value stored in config.sh will not be used when
    ?X: we change our random function.
    if $test "$ans" = "$dflt"; then
        : null
    else
        nrandbits="
    fi
    randfunc="$ans"
    if set $ans val -f; eval $csym; $val; then
        cont="
    else
        dflt=n
        rp="Function $ans does not exists. Use that name anyway?"
        . ./myread
        dflt=rand
        case "$ans" in
            [yY]*) cont=";;
        esac
    fi
    case "$cont" in
        ")
        case "$randfunc" in
            drand48)
                mrand="drand48()"
                seedfunc="srand48"
                ;;
            rand*)
                case
                    "$nrandbits" in
                        ")
echo "Checking to see how many bits your $randfunc() function produces..." >&4
    $cat >try.c <<EOCP
#include <stdio.h>
int main()
{
    register int i;
    register unsigned long tmp;
    register unsigned long max = 0L;
    extern long random();

    for (i = 1000; i; i--) {
        tmp = (unsigned long)$randfunc();

```

```

if (tmp > max) max = tmp;
}
for (i = 0; max; i++)
    max /= 2;
printf("%d\n",i);
}
EOCP
if $cc -o try try.c >/dev/null 2>&1 ; then
dflt=`try`
else
dflt=?
echo "(I can't seem to compile the test program...)"
fi
;;
*)
dflt="$nrandbits"
;;
esac
rp="How many bits does your $randfunc() function produce?"
. ./myread
nrandbits="$ans"
$rm -f try.c try
mrand="($randfunc() / (double) ((1 << $nrandbits) - 1))"
seedfunc="srand"
;;
?X: The following is provided just in case...
*)
dflt="31"
rp="How many bits does your $randfunc() function produce?"
. ./myread
nrandbits="$ans"
seedfunc="s$randfunc"
mrand="($randfunc()
/ (double) ((1 << $nrandbits) - 1))"
if set $seedfunc val -f; eval $csym; $val; then
    echo "(Using $seedfunc() to seed random generator)"
else
    echo "(Warning: no $seedfunc() to seed random generator)"
    seedfunc=rand
fi
;;
esac
;;
esac
done

```

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-

debian-perl-5.26.1/dist/U/randfunc.U

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: d_tzname.U 1 2006-08-24 12:32:52Z rmanfredi $
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: $Log: d_tzname.U,v $
?RCS: Revision 3.0.1.2 1994/08/29 16:14:43 ram
?RCS: patch32: forgot to set proper value in the val variable
?RCS:
?RCS: Revision 3.0.1.1 1994/06/20 06:57:55 ram
?RCS: patch30: created
?RCS:
?MAKE:d_tzname: Csym Setvar
?MAKE: -pick add $@ %<
?S:d_tzname:
?S: This variable conditionally defines HAS_TZNAME if tzname[] is
?S: available to access timezone names.
?S:.
?C:HAS_TZNAME:
?C: This symbol, if defined, indicates that the tzname[]
array is
?C: available to access timezone names.
?C:.
?H:#$d_tzname HAS_TZNAME /**/
?H:.
?LINT:set d_tzname
: see if tzname[] exists
echo " "
if set tzname val -a d_tzname; eval $csym; $val; then
val="$define"
echo 'tzname[] found.' >&4
else
val="$undef"
echo 'tzname[] NOT found.' >&4
fi
set d_tzname
eval $setvar
```

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-

debian-perl-5.26.1/dist/U/d_tzname.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: vaproto.U 1 2006-08-24 12:32:52Z rmanfredi \$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic Licence,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic Licence; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: Original Author: Graham Stoney <greyham@research.canon.oz.au>

?RCS:

?RCS: \$Log: vaproto.U,v \$

?RCS: Revision 3.0.1.1 1994/01/24 14:17:16 ram

?RCS: patch16: definition of _V now appears only when needed

?RCS:

?RCS: Revision 3.0 1993/08/18 12:09:59 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?MAKE:vaproto: prototype i_stdarg Setvar

?MAKE: -pick add \$@ %<

?S:vaproto:

?S: This variable conditionally defines CAN_VAPROTO on systems supporting

?S: prototype

declaration of functions with a variable number of

?S: arguments. See also prototype.

?S:.

?C:CAN_VAPROTO ~ %<:

?C: This variable is defined on systems supporting prototype declaration

?C: of functions with a variable number of arguments.

?C:.

?C:_V:

?C: This macro is used to declare function parameters in prototypes for

?C: functions with a variable number of parameters. Use double parentheses.

?C: For example:

?C:

?C: int printf _V((char *fmt, ...));

?C:

?C: Remember to use the plain simple _() macro when declaring a function

?C: with no variable number of arguments, since it might be possible to

?C: have a non-effect _V() macro and still get prototypes via _().

?C:.

?H:?%<:#\$vaproto CAN_VAPROTO /**/

?H:?_V:#ifdef CAN_VAPROTO

?H:?_V:#define _V(args) args

```

?H:?_V:#else
?H:?_V:#define _V(args) ()
?H:?_V:#endif
?H:.
?W:%<:_V
?LINT:set vaproto
: see if prototypes support variable argument declarations
echo " "
case "$prototype$i_stdarg" in
$define$define)
echo "It appears we'll
be able to prototype varargs functions." >&4
val="$define"
;;
*)
echo "Too bad... We won't be using prototyped varargs functions..." >&4
val="$undef"
;;
esac
set vaproto
eval $setvar

```

Found in path(s):

```

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/vaproto.U

```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 2001 Jarkko Hietaniemi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 3.0.

?RCS:

?MAKE:d_usleepproto: Hasproto i_unistd

?MAKE: -pick add \$@ %<

?S:d_usleepproto:

?S: This variable conditionally defines the HAS_USLEEP_PROTO symbol,

?S: which indicates to the C program that the system provides

?S: a prototype for the usleep() function. Otherwise, it is

?S: up to the program to supply one.

?S:.

?C:HAS_USLEEP_PROTO:

?C: This symbol, if defined, indicates that the system provides

?C: a prototype for the usleep() function. Otherwise, it is up

?C: to the program to supply one. A good guess is

?C: extern int

usleep(useconds_t);

?C:.

?H:#\$d_usleepproto HAS_USLEEP_PROTO /**/

?H:.

?LINT:set d_usleepproto

: see if prototype for usleep is available

echo " "

set d_usleepproto usleep \$i_unistd unistd.h

eval \$hasproto

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_usleepproto.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: gidtype.U,v \$

?RCS: Revision 3.0.1.3 1994/08/29 16:21:44 ram

?RCS: patch32: now uses new Typedef unit to compute type information

?RCS: patch32: removed useless usage of Setvar (for now)

?RCS:

?RCS: Revision 3.0.1.2 1994/05/13 15:21:07 ram

?RCS: patch27: added lint hint

?RCS:

?RCS: Revision 3.0.1.1 1994/05/06 15:01:51 ram

?RCS: patch23: protected gidtype setting via setvar (ADO)

?RCS: patch23: made Gid_t comment more explicit (ADO)

?RCS:

?RCS: Revision 3.0 1993/08/18 12:08:11 ram

?RCS:

Baseline for dist 3.0 netwide release.

?RCS:

?MAKE:gidtype: Myread Typedef Findhdr

?MAKE: -pick add \$@ %<

?S:gidtype:

?S: This variable defines Gid_t to be something like gid_t, int,

?S: ushort, or whatever type is used to declare the return type

?S: of getgid(). Typically, it is the type of group ids in the kernel.

?S:.

?C:Gid_t (GIDTYPE):

?C: This symbol holds the return type of getgid() and the type of

?C: argument to setrgid() and related functions. Typically,

?C: it is the type of group ids in the kernel. It can be int, ushort,

?C: uid_t, etc... It may be necessary to include <sys/types.h> to get

?C: any typedef'ed information.

?C:.

?H:#define Gid_t \$gidtype /* Type for getgid(), etc... */

?H:.

?T:xxx

: see what type gids are declared as in the kernel

```
set gid_t gidtype xxx stdio.h sys/types.h
```

```
eval $typedef
```

```
case "$gidtype" in
```

```
xxx)
```

```
xxx=`./findhdr sys/user.h`
```

```
set `grep 'groups\[NGROUPS\]; "$xxx" 2>/dev/null` unsigned short
```

```
case $1 in
```

```
unsigned) dflt="$1 $2" ;;
```

```
*) dflt="$1"
```

```
::
```

```
esac
```

```
::
```

```
*) dflt="$gidtype";;
```

```
esac
```

```
echo " "
```

```
rp="What is the type for group ids returned by getgid()?"
```

```
./myread
```

```
gidtype="$ans"
```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/gidtype.U
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_pipe.U 1 2006-08-24 12:32:52Z rmanfredi \$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic Licence,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic Licence; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: Original Author: Andy Dougherty <doughera@lafcol.lafayette.edu>

?RCS:
?RCS: \$Log: d_pipe.U,v \$
?RCS: Revision 3.0.1.1 1994/08/29 16:11:44 ram
?RCS: patch32: created by ADO
?RCS:
?MAKE:d_pipe: Inlibc
?MAKE: -pick add \$@ %<
?S:d_pipe:
?S: This variable conditionally defines the HAS_PIPE symbol, which
?S: indicates to the C program that the pipe() routine is available
?S: to create an inter-process channel.
?S:.
?C:HAS_PIPE :
?C: This symbol, if defined, indicates
that the pipe routine is
?C: available to create an inter-process channel.
?C:.
?H:#\$d_pipe HAS_PIPE /**/
?H:.
?LINT:set d_pipe
: see if pipe exists
set pipe d_pipe
eval \$inlibc

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/d_pipe.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_voidsig.U,v 3.0.1.3 1995/05/12 12:12:46 ram Exp \$
?RCS:
?RCS: Copyright (c) 1991-1993, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 3.0.
?RCS:
?RCS: \$Log: d_voidsig.U,v \$
?RCS: Revision 3.0.1.3 1995/05/12 12:12:46 ram
?RCS: patch54: made cppflags dependency optional
?RCS:
?RCS: Revision 3.0.1.2 1994/08/29 16:20:35 ram
?RCS: patch32: now sets signal_t only once d_voidsig is known (WED)
?RCS:
?RCS: Revision 3.0.1.1 1994/06/20 06:59:54 ram
?RCS: patch30: now properly sets signal_t when re-using previous value

```

?RCS:
?RCS: Revision 3.0 1993/08/18 12:07:56 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:d_voidsig
signal_t: rm contains cppstdin cppminus +cppflags test Myread \
Oldconfig Setvar Findhdr
?MAKE: -pick add $@ %<
?S:d_voidsig:
?S: This variable conditionally defines VOIDSIG if this system
?S: declares "void (*signal(...))()" in signal.h. The old way was to
?S: declare it as "int (*signal(...))()".
?S:.
?S:signal_t:
?S: This variable holds the type of the signal handler (void or int).
?S:.
?C:VOIDSIG:
?C: This symbol is defined if this system declares "void (*signal(...))()" in
?C: signal.h. The old way was to declare it as "int (*signal(...))()". It
?C: is up to the package author to declare things correctly based on the
?C: symbol.
?C:.
?C:Signal_t (SIGNAL_T):
?C: This symbol's value is either "void" or "int", corresponding to the
?C: appropriate return type of a signal handler. Thus, you can declare
?C: a signal handler using "Signal_t (*handler())", and define the
?C: handler using "Signal_t handler(sig)".
?C:.
?H:#$d_voidsig VOIDSIG /**/
?H:#define
Signal_t $signal_t /* Signal handler's return type */
?H:.
?T:xxx
?LINT:set d_voidsig
: see if signal is declared as pointer to function returning int or void
echo " "
xxx=`./findhdr signal.h`
$test "$xxx" && $cppstdin $cppminus $cppflags < $xxx >$$.tmp 2>/dev/null
if $contains 'int.*\[ \]*signal' $$.tmp >/dev/null 2>&1 ; then
echo "You have int (*signal())() instead of void." >&4
val="$undef"
elif $contains 'void.*\[ \]*signal' $$.tmp >/dev/null 2>&1 ; then
echo "You have void (*signal())()." >&4
val="$define"
elif $contains 'extern[ \]*\[ \]*signal' $$.tmp >/dev/null 2>&1 ; then
echo "You have int (*signal())() instead of void." >&4
val="$undef"
?X: This next test is kind of sloppy, but it catches Linux

```

```

?X: which has a
?X: typedef void (*__sighandler_t) (int) ;
?X: A better fix would be to compile a C program with the proper
?X: prototype, but since nearly everyone uses void, we'll just go with
?X: this.
elif $contains 'void.*\*.*sig' $$tmp >/dev/null 2>&1 ; then
echo "You
have void (*signal())()." >&4
val="$define"
else
case "$d_voidsig" in
")
echo "I can't determine whether signal handler returns void or int..." >&4
dflt=void
rp="What type does your signal handler return?"
./myread
case "$ans" in
v*) val="$define";;
*) val="$undef";;
esac;;
"$define")
echo "As you already told me, signal handler returns void." >&4
val="$define"
;;
*) echo "As you already told me, signal handler returns int." >&4
val="$undef"
;;
esac
fi
set d_voidsig
eval $setvar
case "$d_voidsig" in
"$define") signal_t="void";;
*) signal_t="int";;
esac
$rm -f $$tmp

```

Found in path(s):

```

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/modified/d_voidsig.U

```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 2000 Jarkko Hietaniemi

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:
?MAKE:d_mkstemp: Inlibc
?MAKE: -pick add \$@ %<
?S:d_mkstemp:
?S: This variable conditionally defines the HAS_MKSTEMPS symbol, which
?S: indicates to the C program that the mkstemp() routine is available
?S: to exclusively create and open a uniquely named (with a suffix)
?S: temporary file.
?S:.
?C:HAS_MKSTEMPS :
?C: This symbol, if defined, indicates that the mkstemp routine is
?C: available to exclusively create and open a uniquely named
?C: (with a suffix) temporary file.
?C:.
?H:#\$d_mkstemp HAS_MKSTEMPS /**/
?H:.
?LINT:set d_mkstemp
: see if mkstemp exists
set mkstemp d_mkstemp
eval \$inlibc

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_mkstemp.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: Mkdirp.U 1 2006-08-24 12:32:52Z rmanfredi \$
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: \$Log: Extract.U,v \$
?RCS: Revision 3.0.1.2 1997/02/28 14:58:52 ram
?RCS: patch61: added support for src.U
?RCS:
?RCS: Revision 3.0.1.1 1994/10/29 15:51:46 ram
?RCS: patch36: added ?F: line for metalint file checking
?RCS:
?RCS: Revision 3.0 1993/08/18 12:04:52 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?X:
?X: This unit produces a shell script which can launched to create a

?X: directory path like "mkdir -p" would do.

?X:

?MAKE:Mkdirp:

eunicefix startsh

?MAKE: -pick add \$@ %<

?F:./mkdirp

?T:name create file

: script used to emulate mkdir -p

cat >mkdirp <<EOS

\$startsh

EOS

cat >>mkdirp <<'EOS'

name=\$1;

create="";

while test \$name; do

if test ! -d "\$name"; then

create="\$name \$create"

name=`echo \$name | sed -e "s|^[^/]*\$||"``

name=`echo \$name | sed -e "s|(.*).*/.*|1|"``

else

name=""

fi

done

for file in \$create; do

mkdir \$file

done

EOS

chmod +x mkdirp

\$eunicefix mkdirp

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/Mkdirp.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: libflex.U 1 2006-08-24 12:32:52Z rmanfredi \$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic Licence,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic Licence; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: libflex.U,v \$

?RCS: Revision 3.0.1.3 1997/02/28 15:57:48 ram

?RCS: patch61: replaced .a with \$_a all over the place

```

?RCS:
?RCS: Revision 3.0.1.2 1994/05/06 15:07:02 ram
?RCS: patch23: now uses full library path instead of -l notation
?RCS:
?RCS: Revision 3.0.1.1 1994/01/24 14:13:25 ram
?RCS: patch16: un-obsolete this unit to allow smooth lex/flex compilations
?RCS:
?RCS: Revision 3.0 1993/08/18 12:08:59 ram
?RCS: Baseline for dist 3.0 netwide
release.
?RCS:
?MAKE:libflex: Loc lex libpth _a
?MAKE: -pick add $@ %<
?S:libflex:
?S: This variable contains the argument to pass to the loader in order
?S: to get the flex/lex library routines. If there is no flex or flex
?S: library, it is null.
?S:.
?T:xxx
: see if we should include -lfl
echo " "
case "$lex" in
*flex)
xxx=`./loc libfl$_a x $libpth`
case "$xxx" in
x)
echo "No flex library found." >&4
libflex=""
;;
*)
echo "flex library found in $xxx." >&4
libflex="$xxx"
;;
esac
;;
*lex)
xxx=`./loc libl$_a x $libpth`
case "$xxx" in
x)
echo "No lex library found." >&4
libflex=""
;;
*)
echo "lex library found in $xxx." >&4
libflex="$xxx"
;;
esac
;;

```

```
*)
echo "You don't seem to have lex or flex, so I won't look for libraries." >&4
;;
esac
```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/libflex.U
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 2000 Jarkko Hietaniemi

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?MAKE:d_frexp! Inlibc

?MAKE: -pick add \$@ %<

?S:d_frexp!:

?S: This variable conditionally defines the HAS_FREXP! symbol, which

?S: indicates to the C program that the frexp() routine is available.

?S:.

?C:HAS_FREXP!:

?C: This symbol, if defined, indicates that the frexp routine is

?C: available to break a long double floating-point number into

?C: a normalized fraction and an integral power of 2.

?C:.

?H:#\$d_frexp! HAS_FREXP! /**/

?H:.

?LINT:set d_frexp!

: see if frexp! exists

set frexp! d_frexp!

eval \$inlibc

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/perl/d_frexp!.U
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: lib.U,v 3.0.1.3 1995/09/25 09:16:47 ram Exp \$

?RCS:

?RCS: Copyright (c) 1991-1993, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

```

?RCS: of the source tree for dist 3.0.
?RCS:
?RCS: $Log: lib.U,v $
?RCS: Revision 3.0.1.3 1995/09/25 09:16:47 ram
?RCS: patch59: unit is now forced to the top of Configure, if possible
?RCS:
?RCS: Revision 3.0.1.2 1995/01/30 14:38:08 ram
?RCS: patch49: can now handle installation prefix changes (from WED)
?RCS:
?RCS: Revision 3.0.1.1 1994/08/29 16:27:40 ram
?RCS: patch32: now uses installation prefix to set the default
?RCS:
?RCS: Revision 3.0 1993/08/18 12:08:56 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?LINT:
empty
?X:?MAKE:lib libexp: Getfile Loc Oldconfig Prefixit Prefixup prefixexp
?X:?MAKE: -pick add $@ %<
?X:?Y:TOP
?X:?S:lib:
?X:?S: This variable holds the name of the directory in which the user wants
?X:?S: to put public library files for the package in question. It is most
?X:?S: often a local directory such as /usr/local/lib. Programs using this
?X:?S: variable must be prepared to deal with filename expansion.
?X:?S:.
?X:?S:libexp:
?X:?S: This variable is the same as the lib variable, but is filename expanded
?X:?S: at configuration time, for convenient use in your makefiles.
?X:?S:.
?X:: determine where public libraries go
?X:set lib lib
?X:eval $prefixit
?X:case "$lib" in
?X:")
?X: dflt=`./loc . ." $prefixexp/lib /usr/local/lib /usr/lib /lib`
?X: set dflt
?X: eval $prefixup
?X: ;;
?X:*) dflt="$lib";;
?X:esac
?X:echo " "
?X:fn=d~
?X:rp='Where do you want to put the public libraries?'
?X: ./getfile
?X:lib="$ans"
?X:libexp="$ansexp"

```

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/nullified/lib.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: i_systypes.U 1 2006-08-24 12:32:52Z rmanfredi \$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic Licence,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic Licence; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: i_systypes.U,v \$

?RCS: Revision 3.0 1993/08/18 12:08:41 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?X:

?X: Look wether <sys/types.h> needs to be included.

?X:

?MAKE:i_systypes: Inhdr

?MAKE: -pick add \$@ %<

?S:i_systypes:

?S: This variable conditionally defines the I_SYS_TYPES symbol,

?S: and indicates whether a C program should include <sys/types.h>.

?S:.

?C:I_SYS_TYPES (I_SYSTYPES):

?C: This symbol, if defined, indicates to the C program
that it should

?C: include <sys/types.h>.

?C:.

?H:#\$i_systypes I_SYS_TYPES /**/

?H:.

?LINT:set i_systypes

: see if sys/types.h has to be included

set sys/types.h i_systypes

eval \$inhdr

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/i_systypes.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

```

?RCS:
?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: $Log: Filexp.U,v $
?RCS: Revision 3.0.1.2 1994/10/29 15:52:53 ram
?RCS: patch36: added ?F: line for metalint file checking
?RCS: patch36: added HOME to the ?T: line since metalint now checks ${HOME}
?RCS:
?RCS: Revision 3.0.1.1 1994/05/06 14:03:00 ram
?RCS: patch23: made sure error status from csh is propagated (WED)
?RCS:
?RCS: Revision 3.0 1993/08/18 12:04:53 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?X:
?X: This unit produces a shell script which will expand filenames beginning
?X:
with tildes. The script is deleted at the end of Configure.
?X:
?MAKE:Filexp: startsh sed test expr eunicefix
?MAKE: -pick add $@ %<
?F:./filexp
?T:HOME LOGDIR dir me name failed
: set up shell script to do ~ expansion
cat >filexp <<EOSS
$startsh
: expand filename
?X:
?X: The case entries below escape the ~ as some shells have shown expansion
?X: of the ~ during here-doc processing.
?X:
case "$1" in
|~/*/~)
echo \ $1 | $sed "s|~|${HOME-\\$LOGDIR}|"
;;
|~*)
if $test -f /bin/csh; then
/bin/csh -f -c "glob $1"
failed=$?
echo ""
exit \ $failed
else
name=`$expr x$1 : '.*\([^*]*\)`
dir=`$sed -n -e "/^\${name}:/ {s/^[^:]*:[^:]*:[^:]*:[^:]*:[^:]*:\([^*]*\).*$""$/1/" -e p -e q -e '}' </etc/passwd`

```

```

if $test ! -d "\$dir"; then
  me=\`basename \$0\`
  echo "\$me: can't locate home directory for: \$name" >&2
  exit 1
fi
case "\$1" in
*/*)
  echo \$dir/\`expr x\$1 : '[^/]*^(.*)\`
  ;;
*)
  echo \$dir
  ;;
esac
fi
;;
*)
echo \$1
;;
esac
EOSS
chmod
+x filexp
$unicefix filexp

```

Found in path(s):

```

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/Filexp.U

```

No license file was found, but licenses were detected in source scan.

```

?RCS: $Id$
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: $Log: nblock_io.U,v $
?RCS: Revision 3.0.1.2 1997/02/28 16:17:14 ram
?RCS: patch61: simplify here document for shells that can't handle them well
?RCS: patch61: force use of "startsh" at the head of the generated script
?RCS: patch61: added new files to the ?F: metalint hint
?RCS:
?RCS: Revision 3.0.1.1 1995/07/25 14:13:22 ram
?RCS: patch56: created
?RCS:

```

?X:

?X: Simplify here document for shells that can't handle them well.

?X: (Problem reported on FreeBSD; it's unclear if this helps.) --AD

?X:

?MAKE:o_nonblock

eagain rd_nodata d_eofnblk: cat rm_try +cc +ccflags +ldflags \
d_open3 h_sysfile h_fcntl signal_t hint Oldconfig Setvar startsh Warn

?MAKE: -pick add \$@ %<

?S:o_nonblock:

?S: This variable bears the symbol value to be used during open() or fcntl()

?S: to turn on non-blocking I/O for a file descriptor. If you wish to switch

?S: between blocking and non-blocking, you may try ioctl(FIOSNBIO) instead,

?S: but that is only supported by some devices.

?S:.

?S:eagain:

?S: This variable bears the symbolic errno code set by read() when no

?S: data is present on the file and non-blocking I/O was enabled (otherwise,

?S: read() blocks naturally).

?S:.

?S:rd_nodata:

?S: This variable holds the return code from read() when no data is

?S: present. It should be -1, but some systems return 0 when O_NDELAY is

?S: used, which is a shame because you cannot make the difference between

?S: no data and an EOF.. Sigh!

?S:.

?S:d_eofnblk:

?S: This variable conditionally defines EOF_NONBLOCK

if EOF can be seen

?S: when reading from a non-blocking I/O source.

?S:.

?C:VAL_O_NONBLOCK:

?C: This symbol is to be used during open() or fcntl(F_SETFL) to turn on

?C: non-blocking I/O for the file descriptor. Note that there is no way

?C: back, i.e. you cannot turn it blocking again this way. If you wish to

?C: alternatively switch between blocking and non-blocking, use the

?C: ioctl(FIOSNBIO) call instead, but that is not supported by all devices.

?C:.

?C:VAL_EAGAIN:

?C: This symbol holds the errno error code set by read() when no data was

?C: present on the non-blocking file descriptor.

?C:.

?C:RD_NODATA:

?C: This symbol holds the return code from read() when no data is present

?C: on the non-blocking file descriptor. Be careful! If EOF_NONBLOCK is

?C: not defined, then you can't distinguish between no data and EOF by

?C: issuing a read(). You'll have to find another way to tell for sure!

?C:.

?C:EOF_NONBLOCK:

?C: This symbol, if defined, indicates to the C program that a read() on

?C: a

non-blocking file descriptor will return 0 on EOF, and not the value

?C: held in RD_NODATA (-1 usually, in that case!).

?C:.

?H:#define VAL_O_NONBLOCK \$o_nonblock

?H:#define VAL_EAGAIN \$eagain

?H:#define RD_NODATA \$rd_nodata

?H:\$d_eofnblk EOF_NONBLOCK

?H:.

?F:!try !try.out !try.ret !try.err !mtry

?T:status

?LINT:use d_open3

: check for non-blocking I/O stuff

case "\$h_sysfile" in

true) echo "#include <sys/file.h>" > head.c;;

*)

case "\$h_fcntl" in

true) echo "#include <fcntl.h>" > head.c;;

*) echo "#include <sys/fcntl.h>" > head.c;;

esac

::

esac

echo " "

echo "Figuring out the flag used by open() for non-blocking I/O..." >&4

case "\$o_nonblock" in

")

\$cat head.c > try.c

\$cat >>try.c <<'EOCP'

int main() {

#ifdef O_NONBLOCK

printf("O_NONBLOCK\n");

exit(0);

#endif

#ifdef O_NDELAY

printf("O_NDELAY\n");

exit(0);

#endif

?X: Stevens "Advanced Programming in the UNIX Environment" page 364 mentions

?X: the FNDELAY symbol, used in 4.33BSD (source: Paul Marquess).

#ifdef FNDELAY

printf("FNDELAY\n");

exit(0);

#endif

exit(0);

}

EOCP

if

```

$cc $ccflags $ldflags -o try try.c >/dev/null 2>&1; then
o_nonblock=`./try`
case "$o_nonblock" in
") echo "I can't figure it out, assuming O_NONBLOCK will do.";;
*) echo "Seems like we can use $o_nonblock.";;
esac
else
echo "(I can't compile the test program; pray O_NONBLOCK is right!)"
fi
;;
*) echo "Using $hint value $o_nonblock.";;
esac
$rm_try

echo " "
echo "Let's see what value errno gets from read() on a $o_nonblock file..." >&4
case "$$again" in
")
$cat head.c > try.c
$cat >>try.c <<EOCP
#include <errno.h>
#include <sys/types.h>
#include <signal.h>
#define MY_O_NONBLOCK $o_nonblock
extern int errno;
$signal_t blech(x) int x; { exit(3); }
EOCP
$cat >> try.c <<'EOCP'
int main()
{
int pd[2];
int pu[2];
char buf[1];
char string[100];

pipe(pd); /* Down: child -> parent */
pipe(pu); /* Up: parent -> child */
if (0 != fork()) {
int ret;
close(pd[1]); /* Parent reads from pd[0] */
close(pu[0]); /*
Parent writes (blocking) to pu[1] */
if (-1 == fcntl(pd[0], F_SETFL, MY_O_NONBLOCK))
exit(1);
signal(SIGALRM, blech);
alarm(5);
if ((ret = read(pd[0], buf, 1)) > 0) /* Nothing to read! */
exit(2);

```

```

sprintf(string, "%d\n", ret);
write(2, string, strlen(string));
alarm(0);
#ifdef EAGAIN
if (errno == EAGAIN) {
    printf("EAGAIN\n");
    goto ok;
}
#endif
#ifdef EWOULDBLOCK
if (errno == EWOULDBLOCK)
    printf("EWOULDBLOCK\n");
#endif
ok:
write(pu[1], buf, 1); /* Unblocks child, tell it to close our pipe */
sleep(2); /* Give it time to close our pipe */
alarm(5);
ret = read(pd[0], buf, 1); /* Should read EOF */
alarm(0);
sprintf(string, "%d\n", ret);
write(3, string, strlen(string));
exit(0);
}

close(pd[0]); /* We write to pd[1] */
close(pu[1]); /* We read from pu[0] */
read(pu[0], buf, 1); /* Wait for parent to signal us we may continue */
close(pd[1]); /* Pipe pd is now fully closed! */
exit(0); /* Bye bye, thank you for playing!
*/
}
EOCP
if $cc $cflags $ldflags -o try try.c >/dev/null 2>&1; then
?X: Use script to avoid the possible 'alarm call' message
echo "$startsh" >mtry
echo "./try >try.out 2>try.ret 3>try.err || exit 4" >>mtry
chmod +x mtry
./mtry >/dev/null 2>&1
case $? in
0) eagain=`$cat try.out`;
1) echo "Could not perform non-blocking setting!";
2) echo "I did a successful read() for something that was not there!";
3) echo "Hmm... non-blocking I/O does not seem to be working!";
*) echo "Something terribly wrong happened during testing.";;
esac
rd_nodata=`$cat try.ret`
echo "A read() system call with no data present returns $rd_nodata."
case "$rd_nodata" in

```

```

0|-1) ;;
*)
echo "(That's peculiar, fixing that to be -1.)"
rd_nodata=-1
;;
esac
case "$eagain" in
")
echo "Forcing errno EAGAIN on read() with no data available."
eagain=EAGAIN
;;
*)
echo "Your read() sets errno to $eagain when no data is available."
;;
esac
status=`$cat
try.err`
case "$status" in
0) echo "And it correctly returns 0 to signal EOF.";;
-1) echo "But it also returns -1 to signal EOF, so be careful!";;
*) echo "However, your read() returns '$status' on EOF??";;
esac
val="$define"
if test "$status" = "$rd_nodata"; then
./warn "your read() can't distinguish between EOF and no data!"
val="$undef"
fi
else
echo "I can't compile the test program--assuming errno EAGAIN will do."
eagain=EAGAIN
fi
set d_eofnblk
eval $setvar
;;
*)
echo "Using $hint value $eagain."
echo "Your read() returns $rd_nodata when no data is present."
case "$d_eofnblk" in
"$define") echo "And you can see EOF because read() returns 0.";;
"$undef") echo "But you can't see EOF status from read() returned value.";;
*)
?X: Should not happen, but if it does, assume the worst!
echo "(Assuming you can't see EOF status from read anyway.)"
d_eofnblk=$undef
;;
esac
;;
esac

```

\$rm_try head.c mtry

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/nblock_io.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: warnflags.U 1 2006-08-24 12:32:52Z rmanfredi \$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic Licence,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic Licence; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: Original Author: Graham Stoney <greyham@research.canon.oz.au>

?RCS:

?RCS: \$Log: warnflags.U,v \$

?RCS: Revision 3.0 1993/08/18 12:10:02 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?MAKE:warnflags: cat cc contains Myread Guess Oldconfig Findhdr

?MAKE: -pick add \$@ %<

?S:warnflags:

?S: This variable contains any additional C compiler flags to generate

?S: warnings from the compiler. It is up to the Makefile to use this.

?S:.

: offer additional

warning flags for compilation

\$cat <<EOH

You may wish to compile with extra compiler warnings enabled.

Note that doing so enhances your chance of receiving your free set of steak knives, particularly if you find any bugs and report them.

If you don't want extra warnings, answer "none".

EOH

case "\$warnflags" in

") case "\$cc" in

gcc)

dflt="-Wall -Wno-comment"

if \$contains 'fprintf' `./findhdr stdio.h` >/dev/null 2>&1; then

:

else

dflt="\$dflt -Wno-implicit"

fi

```
;;
*) dflt="none";;
esac
;;
') dflt="none";;
*) dflt="$warnflags";;
esac
```

rp="Any \$cc flags to enable warnings?"

```
./myread
case "$ans" in
none) warnflags=' ';;
*) warnflags="$ans";;
esac
```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/warnflags.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: intsize.U,v 3.0.1.2 1997/02/28 15:55:26 ram Exp $
?RCS:
?RCS: Copyright (c) 1991-1993, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 3.0.
?RCS:
?RCS: $Log: intsize.U,v $
?RCS: Revision 3.0.1.2 1997/02/28 15:55:26 ram
?RCS: patch61: avoid prompting the user if the test runs ok
?RCS: patch61: moved code from longsize.U into there
?RCS: patch61: new tests for shortsize as well
?RCS:
?RCS: Revision 3.0.1.1 1994/10/29 16:21:06 ram
?RCS: patch36: added ?F: line for metalint file checking
?RCS:
?RCS: Revision 3.0 1993/08/18 12:08:52 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:intsize longsize
shortsize: Compile Myread cat run i_stdlib rm_try
?MAKE: -pick add $@ %<
?S:intsize:
?S: This variable contains the value of the INTSIZE symbol, which
?S: indicates to the C program how many bytes there are in an int.
```

?S:.

?S:longsize:

?S: This variable contains the value of the LONGSIZE symbol, which

?S: indicates to the C program how many bytes there are in a long.

?S:.

?S:shortsize:

?S: This variable contains the value of the SHORTSIZE symbol which

?S: indicates to the C program how many bytes there are in a short.

?S:.

?C:INTSIZE:

?C: This symbol contains the value of sizeof(int) so that the C

?C: preprocessor can make decisions based on it.

?C:.

?C:LONGSIZE:

?C: This symbol contains the value of sizeof(long) so that the C

?C: preprocessor can make decisions based on it.

?C:.

?C:SHORTSIZE:

?C: This symbol contains the value of sizeof(short) so that the C

?C: preprocessor can make decisions based on it.

?C:.

?H:#define INTSIZE \$intsize /**/

?H:#define LONGSIZE \$longsize /**/

?H:#define

SHORTSIZE \$shortsize /**/

?H:.

?F:!try

: check for lengths of integral types

echo " "

case "\$intsize" in

")

echo "Checking to see how big your integers are..." >&4

\$cat >try.c <<EOCP

#include <stdio.h>

#\$i_stdlib I_STDLIB

#ifdef I_STDLIB

#include <stdlib.h>

#endif

int main()

{

@if INTSIZE || intsize

printf("intsize=%d;\n", (int)sizeof(int));

@end

@if LONGSIZE || longsize

printf("longsize=%d;\n", (int)sizeof(long));

@end

@if SHORTSIZE || shortsize

printf("shortsize=%d;\n", (int)sizeof(short));

```

@end
exit(0);
}
EOCP
set try
if eval $compile_ok && $run ./try > /dev/null; then
    eval ` $run ./try `
@if INTSIZE || intsize
    echo "Your integers are $intsize bytes long."
@end
@if LONGSIZE || longsize
    echo "Your long integers are $longsize bytes long."
@end
@if SHORTSIZE || shortsize
    echo "Your short integers are $shortsize bytes long."
@end
else
    $cat >&4 <<EOM
!
Help! I can't compile and run the intsize test program: please enlighten me!
(This is probably a misconfiguration
in your system or libraries, and
you really ought to fix it. Still, I'll try anyway.)
!
EOM
@if INTSIZE || intsize
    dflt=4
    rp="What is the size of an integer (in bytes)?"
    ./myread
    intsize="$ans"
@end
@if LONGSIZE || longsize
    dflt=$intsize
    rp="What is the size of a long integer (in bytes)?"
    ./myread
    longsize="$ans"
@end
@if SHORTSIZE || shortsize
    dflt=2
    rp="What is the size of a short integer (in bytes)?"
    ./myread
    shortsize="$ans"
@end
fi
;;
esac
$rm_try

```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/a_dvisory/intsize.U
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_sethostent_r.U,v 0RCS:

?RCS: Copyright (c) 2002,2003 Jarkko Hietaniemi

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?RCS: Generated by the reentr.pl from the Perl 5.8 distribution.

?RCS:

?MAKE:d_sethostent_r sethostent_r_proto: Inlibc Protochk Hasproto i_systypes \
 usethreads i_netdb extern_C

?MAKE: -pick add \$@ %<

?S:d_sethostent_r:

?S: This variable conditionally defines the HAS_SETHOSTENT_R symbol,

?S: which indicates to the C program that the sethostent_r()

?S: routine is available.

?S:.

?S:sethostent_r_proto:

?S: This variable encodes the prototype of sethostent_r.

?S: It is zero if d_sethostent_r is undef, and one of the

?S: REENTRANT_PROTO_T_ABC macros of reentr.h if d_sethostent_r

?S: is defined.

?S:.

?C:HAS_SETHOSTENT_R:

?C: This symbol, if defined, indicates that the sethostent_r routine

?C: is

available to sethostent re-entrantly.

?C:.

?C:SETHOSTENT_R_PROTO:

?C: This symbol encodes the prototype of sethostent_r.

?C: It is zero if d_sethostent_r is undef, and one of the

?C: REENTRANT_PROTO_T_ABC macros of reentr.h if d_sethostent_r

?C: is defined.

?C:.

?H:#\$d_sethostent_r HAS_SETHOSTENT_R /**/

?H:#define SETHOSTENT_R_PROTO \$sethostent_r_proto /**/

?H:.

?T:try hdrs d_sethostent_r_proto

: see if sethostent_r exists

set sethostent_r d_sethostent_r

eval \$inlibc

case "\$d_sethostent_r" in

"\$define")

hdrs="\$i_systypes sys/types.h define stdio.h \$i_netdb netdb.h"

```

case "$d_sethostent_r_proto:$susethreads" in
":define") d_sethostent_r_proto=define
set d_sethostent_r_proto sethostent_r $hdrs
eval $hasproto ;;
*) ;;
esac
case "$d_sethostent_r_proto" in
define)
case "$sethostent_r_proto" in
"|0) try='int sethostent_r(int, struct hostent_data*);'
./protochk "$extern_C $try" $hdrs && sethostent_r_proto=I_ID ;;
esac
case "$sethostent_r_proto" in
"|0) try='void
sethostent_r(int, struct hostent_data*);'
./protochk "$extern_C $try" $hdrs && sethostent_r_proto=V_ID ;;
esac
case "$sethostent_r_proto" in
"|0) d_sethostent_r=undef
sethostent_r_proto=0
echo "Disabling sethostent_r, cannot determine prototype." >&4 ;;
* ) case "$sethostent_r_proto" in
REENTRANT_PROTO*) ;;
*) sethostent_r_proto="REENTRANT_PROTO_${sethostent_r_proto}" ;;
esac
echo "Prototype: $try" ;;
esac
;;
*) case "$susethreads" in
define) echo "sethostent_r has no prototype, not using it." >&4 ;;
esac
d_sethostent_r=undef
sethostent_r_proto=0
;;
esac
;;
*) sethostent_r_proto=0
;;
esac

```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/threads/d_sethostent_r.U
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: longsize.U 1 2006-08-24 12:32:52Z rmanfredi \$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: \$Log: longsize.U,v \$
?RCS: Revision 3.0.1.2 1997/02/28 16:09:35 ram
?RCS: patch61: code moved to intsize.U
?RCS:
?RCS: Revision 3.0.1.1 1994/10/29 16:24:31 ram
?RCS: patch36: added ?F: line for metalint file checking
?RCS:
?RCS: Revision 3.0 1993/08/18 12:09:07 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?X:
?X: 'longsize' is now defined within intsize.U
?X:
?LINT: empty

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/longsize.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_msgsnd.U 1 2006-08-24 12:32:52Z rmanfredi \$
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: \$Log: d_msgsnd.U,v \$
?RCS: Revision 3.0 1993/08/18 12:06:41 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:d_msgsnd: Inlibc
?MAKE: -pick add \$@ %<
?S:d_msgsnd:
?S: This variable conditionally defines the HAS_MSGSND symbol, which
?S: indicates to the C program that the msgsnd() routine is available.
?S:.
?C:HAS_MSGSND:

?C: This symbol, if defined, indicates that the msgsnd() routine is

?C: available to send a message into the message queue.

?C:.

?H:#\$d_msgsnd

HAS_MSGSND /**/

?H:.

?LINT:set d_msgsnd

: see if msgsnd exists

set msgsnd d_msgsnd

eval \$inlibc

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/d_msgsnd.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_nice.U 1 2006-08-24 12:32:52Z rmanfredi \$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic Licence,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic Licence; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: Original Author: Andy Dougherty <doughera@lafcol.lafayette.edu>

?RCS:

?RCS: \$Log: d_nice.U,v \$

?RCS: Revision 3.0.1.1 1994/08/29 16:09:48 ram

?RCS: patch32: created by ADO

?RCS:

?MAKE:d_nice: Inlibc

?MAKE: -pick add \$@ %<

?S:d_nice:

?S: This variable conditionally defines the HAS_NICE symbol, which

?S: indicates to the C program that the nice() routine is available.

?S:.

?C:HAS_NICE :

?C: This symbol, if defined, indicates that the nice routine is

?C: available.

?C:.

?H:#\$d_nice

HAS_NICE /**/

?H:.

?LINT:set d_nice

: see if nice exists

set nice d_nice

eval \$inlibc

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/d_nice.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_endgrent.U,v \$

?RCS:

?RCS: Copyright (c) 1998 Andy Dougherty

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?RCS: \$Log: d_endgrent.U,v \$

?RCS:

?MAKE:d_endgrent: Inlibc

?MAKE: -pick add \$@ %<

?S:d_endgrent:

?S: This variable conditionally defines the HAS_ENDGRENT symbol, which

?S: indicates to the C program that the endgrent() routine is available

?S: for sequential access of the group database.

?S:.

?C:HAS_ENDGRENT:

?C: This symbol, if defined, indicates that the getgrent routine is

?C: available for finalizing sequential access of the group database.

?C:.

?H:#\$d_endgrent HAS_ENDGRENT /**/

?H:.

?LINT:set d_endgrent

: see if endgrent exists

set endgrent d_endgrent

eval \$inlibc

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/modified/d_endgrent.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: so.U 1 2006-08-24 12:32:52Z rmanfredi \$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic Licence,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic Licence; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

```

?RCS:
?RCS: $Log: so.U,v $
?RCS: Revision 3.0.1.2 1994/10/29 16:30:04 ram
?RCS: patch36: now tells user how he can suppress shared lib lookup (ADO)
?RCS: patch36: removed echo at the top, since it's now in the here-doc (ADO)
?RCS:
?RCS: Revision 3.0.1.1 1994/06/20 07:07:02 ram
?RCS: patch30: created
?RCS:
?X:
?X: This unit computes the shared-object / shared-lib extension
?X:
?MAKE:so d_libname_unique: test libpth Loc Myread Oldconfig cat Setvar
?MAKE: -pick add $@ %<
?S:so:
?S: This
    variable holds the extension used to identify shared libraries
?S: (also known as shared objects) on the system. Usually set to 'so'.
?S:.
?S:d_libname_unique:
?S: This variable is defined if the target system insists on unique
?S: basenames for shared library files. This is currently true on Android,
?S: false everywhere else we know of.
?S: Defaults to 'undef'.
?S:.
?LINT:set d_libname_unique
?T: xxx
: compute shared library extension
case "$so" in
")
if xxx=`./loc libc.sl X $libpth`; $test -f "$xxx"; then
    dflt='sl'
else
    dflt='so'
fi
;;
*) dflt="$so";;
esac
$cat <<EOM

```

On some systems, shared libraries may be available. Answer 'none' if you want to suppress searching of shared libraries for the remainder of this configuration.

```

EOM
rp='What is the file extension used for shared libraries?'
. ./myread
so="$ans"

```

: Does target system insist that shared library basenames are unique
\$cat << EOM

Some dynamic loaders assume that the *basename* of shared library
filenames
are globally unique. We'll default this to undef as we assume your system
is not this weird. Set to defined if you're on one of them.

EOM

```
dflt='n'  
rp='Make shared library basenames unique?'  
./myread  
case "$ans" in  
y|Y) val="$define" ;;  
*) val="$undef" ;;  
esac  
set d_libname_unique  
eval $setvar
```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-  
debian-perl-5.26.1/U/modified/so.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: mboxchar.U 1 2006-08-24 12:32:52Z rmanfredi $  
?RCS:  
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi  
?RCS:  
?RCS: You may redistribute only under the terms of the Artistic Licence,  
?RCS: as specified in the README file that comes with the distribution.  
?RCS: You may reuse parts of this distribution only within the terms of  
?RCS: that same Artistic Licence; a copy of which may be found at the root  
?RCS: of the source tree for dist 4.0.  
?RCS:  
?RCS: $Log: mboxchar.U,v $  
?RCS: Revision 3.0.1.2 1995/07/25 14:13:12 ram  
?RCS: patch56: ensure ctrl-A characters are visible in prompt (WED)  
?RCS:  
?RCS: Revision 3.0.1.1 1994/05/06 15:11:22 ram  
?RCS: patch23: added support for MMDF mailboxes (WED)  
?RCS:  
?RCS: Revision 3.0 1993/08/18 12:09:15 ram  
?RCS: Baseline for dist 3.0 netwide release.  
?RCS:  
?MAKE:mboxchar: cat package shsharp Myread Oldconfig  
?MAKE: -pick add $@ %<
```

```

?S:mboxchar:
?S: This variable
    contains the eventual value of the MBOXCHAR symbol,
?S: which is how a C program can identify a file as a mailbox.
?S:.
?C:MBOXCHAR:
?C: This symbol contains a character which will match the beginning
?C: of a mailbox file.
?C:.
?H:#define MBOXCHAR '$mboxchar' /**/
?H:.
?T:CTRLA
?INIT:CTRLA=`echo a | tr a '\001`
: determine how to determine when a file is a mailbox
case "$mboxchar" in
") dflt=F;;
?X: The following ^A is two-chars to ensure it will print out -- WED
"$CTRLA") dflt='^A';;
*) dflt="$mboxchar";;
esac
$cat <<EOM

```

In saving articles, \$package wants to differentiate between saving to mailbox format files and normal files. It does this by examining the first character of the file in question. On most systems the first line starts with "From ...", so the first character is an F. Other systems use magic cookies like control codes between articles, so one of those would be first. For example, MMDF messages are separated with lines of four control-A's (you may specify one as ^A, i.e. caret A).

```

EOM
rp="What's the first character of a mailbox file?"
./myread
mboxchar="$ans"
case "$mboxchar" in
F) ;;
"$CTRLA") ;;
^A|^a) mboxchar="$CTRLA";;
*) cat <<'EOM'

```

You will need to edit the shell script mbox.saver to properly append an article to a mailbox. The arguments to the script are documented in

```

EOM
case "$shsharp" in
false) echo "comments in mbox.saver.std.";
true) echo "comments in the shell script itself.";
esac

```

esac

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/mboxchar.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: i_ieefp.U,v \$

?RCS:

?RCS: Copyright (c) 1998 Jarkko Hietaniemi

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?MAKE:i_ieefp: Inhdr Hasfield

?MAKE: -pick add \$@ %<

?S:i_ieefp:

?S: This variable conditionally defines the I_IEEEFP symbol, and indicates

?S: whether a C program should include <ieefp.h>.

?S:.

?C:I_IEEEFP:

?C: This symbol, if defined, indicates that <ieefp.h> exists and

?C: should be included.

?C:.

?H:#\$i_ieefp I_IEEEFP /**/

?H:.

?LINT:set i_ieefp

: see if this is a ieefp.h system

case "\$i_ieefp" in

") set ieefp.h i_ieefp

eval \$inhdr

::

esac

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/i_ieefp.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: startperl.U,v 3.0 1993/08/18 12:09:50 ram Exp \$

?RCS:

?RCS: Copyright (c) 1991-1993, Raphael Manfredi

?RCS:

?RCS: This file is included with or a derivative work of a file included

?RCS: with the metaconfig program of Raphael Manfredi's "dist" distribution.

?RCS: In accordance with clause 7 of dist's modified Artistic License:

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

```

?RCS: License or the Artistic License, as specified in the README file.
?RCS:
?RCS: $Log: startperl.U,v $
?RCS: Perl5 version -- I always have d_portable=define.
?RCS:
?RCS: Revision 3.0 1993/08/18 12:09:50 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:startperl: cat Myread sharpbang initialinstalllocation test \
versiononly version
?MAKE: -pick add $@ %<
?Y:TOP
?X: This is different from dist's standard startperl.U unit because
?X: we can't directly test #!/usr/local/bin/perl (or
whatever) because
?X: we haven't built and installed perl yet.
?S:startperl:
?S: This variable contains the string to put on the front of a perl
?S: script to make sure (hopefully) that it runs with perl and not some
?S: shell. Of course, that leading line must be followed by the classical
?S: perl idiom:
?S: eval 'exec perl -S $0 ${1+"$@"}'
?S: if $running_under_some_shell;
?S: to guarantee perl startup should the shell execute the script. Note
?S: that this magic incantation is not understood by csh.
?S:.
?C:STARTPERL:
?C: This variable contains the string to put in front of a perl
?C: script to make sure (one hopes) that it runs with perl and not
?C: some shell.
?C:.
?H:#define STARTPERL "$startperl" /**/
?H:.
: figure out how to guarantee perl startup
: XXX Note that this currently takes advantage of the bug that binexp ignores
: the Configure -Dinstallprefix setting, which in turn means that under
: relocatable @INC, initialinstalllocation is what binexp started as.
case
"$startperl" in
")
case "$sharpbang" in
*!)
$cat <<EOH

```

I can use the #! construct to start perl on your system. This will make startup of perl scripts faster, but may cause problems if you want to share those scripts and perl is not in a standard place (\$initialinstalllocation/perl) on all your platforms. The alternative

is to force a shell by starting the script with a single '!' character.

EOH

```
case "$versiononly" in
  "$define") dflt="$initialinstalllocation/perl$version";;
  *) dflt="$initialinstalllocation/perl";;
esac
rp='What shall I put after the #! to start up perl ("none" to not use #!)?'
./myread
case "$ans" in
  none) startperl=": # use perl";;
  *) startperl="#!$ans"
  if $test 30 -lt `echo "$ans" | wc -c`; then
    $cat >&4 <<EOM
```

WARNING: Some systems limit the #! command to 32 characters.
If you experience difficulty running Perl scripts with #!, try
installing Perl in a directory with a shorter pathname.

EOM

```
fi ;;
esac
;;
*)
startperl=": # use perl"
;;
esac
;;
esac
echo "I'll use $startperl to start perl scripts."
```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-  
debian-perl-5.26.1/U/perl/startperl.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: lseektype.U,v 3.0.1.1 1994/08/29 16:30:10 ram Exp $
?RCS:
?RCS: Copyright (c) 1991-1993, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 3.0.
?RCS:
?RCS: $Log: lseektype.U,v $
?RCS: Revision 3.0.1.1 1994/08/29 16:30:10 ram
```

```

?RCS: patch32: now uses new Typedef unit to compute type information
?RCS:
?RCS: Revision 3.0 1993/08/18 12:09:08 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:lseektype lseeksize: Myread Typedef cat Compile rm_try longsize run
?MAKE: -pick add $@ %<
?S:lseektype:
?S: This variable defines lseektype to be something like off_t, long,
?S: or whatever type is used to declare
lseek offset's type in the
?S: kernel (which also appears to be lseek's return type).
?S:.
?S:lseeksize:
?S: This variable defines lseeksize to be something like off_t, long,
?S: or whatever type is used to declare lseek offset's type in the
?S: kernel (which also appears to be lseek's return type).
?S:.
?C:Off_t (LSEEKTYPE):
?C: This symbol holds the type used to declare offsets in the kernel.
?C: It can be int, long, off_t, etc... It may be necessary to include
?C: <sys/types.h> to get any typedef'ed information.
?C:.
?C:LSEEKSIZE:
?C: This symbol holds the number of bytes used by the Off_t.
?C:.
?C:Off_t_size:
?C: This symbol holds the number of bytes used by the Off_t.
?C:.
?H:#define Off_t $lseektype /* <offset> type */
?H:#define LSEEKSIZE $lseeksize /* <offset> size */
?H:#define Off_t_size $lseeksize /* <offset> size */
?H:.
?F:!try
?LINT:set lseektype
: see what type lseek is declared as in the kernel
rp="What is the type used for lseek's offset on this system?"
set off_t lseektype
long stdio.h sys/types.h
eval $typedef_ask

echo " "
echo "Checking to see how big your file offsets are..." >&4
$cat >try.c <<EOCP
#include <sys/types.h>
#include <stdio.h>
int main()
{

```

```

printf("%d\n", (int)sizeof($lseektype));
return(0);
}
EOCP
set try
if eval $compile_ok; then
lseeksize=`$run ./try`
echo "Your file offsets are $lseeksize bytes long."
else
dflt=$longsize
echo " "
echo "(I can't seem to compile the test program. Guessing...)"
rp="What is the size of your file offsets (in bytes)?"
./myread
lseeksize="$ans"
fi
$rm_try

```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/typedefs/lseektype.U
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: voidflags.U,v \$

?RCS: Revision 3.0.1.2 1997/02/28 16:27:58 ram

?RCS: patch61: don't prompt them if the void support is high enough for us

?RCS:

?RCS: Revision 3.0.1.1 1995/01/11 15:37:44 ram

?RCS: patch45: cosmetic change to avoid spurious blank lines when using -s

?RCS:

?RCS: Revision 3.0 1993/08/18 12:10:01 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?MAKE:voidflags defvoidused: cat sed rm rm_try contains +cc +ccflags package \

Oldconfig Myread

?MAKE: -pick add \$@ %<

?S:voidflags:

?S: This

variable contains the eventual value of the VOIDFLAGS symbol,
 ?S: which indicates how much support of the void type is given by this
 ?S: compiler. See VOIDFLAGS for more info.
 ?S:.
 ?S:defvoidused:
 ?S: This variable contains the default value of the VOIDUSED symbol (15).
 ?S:.
 ?X: Exceptionally, we have to explicitly alias the symbol name for
 ?X: config_h.SH, otherwise the comment would not appear.
 ?C:VOIDFLAGS ~ %<:
 ?C: This symbol indicates how much support of the void type is given by this
 ?C: compiler. What various bits mean:
 ?C:
 ?C: 1 = supports declaration of void
 ?C: 2 = supports arrays of pointers to functions returning void
 ?C: 4 = supports comparisons between pointers to void functions and
 ?C: addresses of void functions
 ?C: 8 = supports declaration of generic void pointers
 ?C:
 ?C: The package designer should define VOIDUSED to indicate the requirements
 ?C: of the package. This can be done either by #defining VOIDUSED before
 ?C: including
 config.h, or by defining defvoidused in Myinit.U. If the
 ?C: latter approach is taken, only those flags will be tested. If the
 ?C: level of void support necessary is not present, defines void to int.
 ?C:.
 ?H:%<:#ifndef VOIDUSED
 ?H:%<:#define VOIDUSED \$defvoidused
 ?H:%<:#endif
 ?H:%<:#define VOIDFLAGS \$voidflags
 ?H:%<:#if (VOIDFLAGS & VOIDUSED) != VOIDUSED
 ?H:%<:#define void int /* is void to be avoided? */
 ?H:%<:#define M_VOID /* Xenix strikes again */
 ?H:%<:#endif
 ?H:.
 ?W:%<:void
 ?F:!.out !try.c !flags
 ?LINT:usefile .out flags try.c
 ?INIT:: full support for void wanted by default
 ?INIT:defvoidused=15
 ?INIT:
 ?LINT:known void M_VOID VOIDUSED
 : check for void type
 echo " "
 echo "Checking to see how well your C compiler groks the void type..." >&4
 \$cat >flags <<EOM

Support flag bits are:

- 1: basic void declarations.
- 2: arrays of pointers to functions returning void.
- 4: operations between pointers to and addresses of void functions.
- 8: generic void pointers.

EOM

case

"\$voidflags" in

")

\$cat >try.c <<'EOCP'

#if TRY & 1

void sub() {

#else

sub() {

#endif

extern void moo(); /* function returning void */

void (*goo)(); /* ptr to func returning void */

#if TRY & 8

void *hue; /* generic ptr */

#endif

#if TRY & 2

void (*foo[10])();

#endif

#if TRY & 4

if(goo == moo) {

exit(0);

}

#endif

exit(0);

}

int main() { sub(); }

EOCP

?X: This unit used to use cc -S in those tests to try to speed up things, but

?X: unfortunately, AIX 3.2 does not support this option.

if \$cc \$cflags -c -DTRY=\$defvoidused try.c >.out 2>&1 ; then

voidflags=\$defvoidused

echo "Good. It appears to support void to the level \$package wants."

if \$contains warning .out >/dev/null 2>&1; then

echo "However, you might get some warnings that look like this:"

\$sed -e 's/^/ ' .out

fi

else

echo "Hmm, your compiler has some difficulty with void. Checking further..." >&4

\$cat >&4 flags

\$rm -f flags

if \$cc \$cflags -c -DTRY=1 try.c >/dev/null 2>&1; then

echo

```

"It supports 1..."
if $cc $ccflags -c -DTRY=3 try.c >/dev/null 2>&1; then
echo "It also supports 2..."
if $cc $ccflags -c -DTRY=7 try.c >/dev/null 2>&1; then
voidflags=7
echo "And it supports 4 but not 8 definitely."
else
echo "It doesn't support 4..."
if $cc $ccflags -c -DTRY=11 try.c >/dev/null 2>&1; then
voidflags=11
echo "But it supports 8."
else
voidflags=3
echo "Neither does it support 8."
fi
fi
else
echo "It does not support 2..."
if $cc $ccflags -c -DTRY=13 try.c >/dev/null 2>&1; then
voidflags=13
echo "But it supports 4 and 8."
else
if $cc $ccflags -c -DTRY=5 try.c >/dev/null 2>&1; then
voidflags=5
echo "And it supports 4 but has not heard about 8."
else
echo "However it supports 8 but not 4."
fi
fi
fi
else
echo "There is no support at all for void."
voidflags=0
fi
fi
esac
?X: Only prompt user if support does not match the
level we want
case "$voidflags" in
"$defvoidused")
echo "Good. I already know it supports void to the level $package wants."
;;
*)
dflt="$voidflags";
test -f flags && $cat flags
rp="Your void support flags add up to what?"
./myread
voidflags="$ans"

```

```
;;
esac
$rm_try flags
```

Found in path(s):

```
*/opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/voidflags.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: d_ttyname_r.U,v 0RCS:
?RCS: Copyright (c) 2002,2003 Jarkko Hietaniemi
?RCS:
?RCS: You may distribute under the terms of either the GNU General Public
?RCS: License or the Artistic License, as specified in the README file.
?RCS:
?RCS: Generated by the reentr.pl from the Perl 5.8 distribution.
?RCS:
?MAKE:d_ttyname_r ttyname_r_proto: Inlibc Protochk Hasproto i_systypes \
  usethreads i_unistd extern_C
?MAKE: -pick add $@ %<
?S:d_ttyname_r:
?S: This variable conditionally defines the HAS_TTYNAME_R symbol,
?S: which indicates to the C program that the ttyname_r()
?S: routine is available.
?S:
?S: ttyname_r_proto:
?S: This variable encodes the prototype of ttyname_r.
?S: It is zero if d_ttyname_r is undef, and one of the
?S: REENTRANT_PROTO_T_ABC macros of reentr.h if d_ttyname_r
?S: is defined.
?S:
?C:HAS_TTYNAME_R:
?C: This symbol, if defined, indicates that the ttyname_r routine
?C: is available to ttyname re-entrantly.
?C:
?C:TTYNAME_R_PROTO:
?C: This
  symbol encodes the prototype of ttyname_r.
?C: It is zero if d_ttyname_r is undef, and one of the
?C: REENTRANT_PROTO_T_ABC macros of reentr.h if d_ttyname_r
?C: is defined.
?C:
?H:#$d_ttyname_r HAS_TTYNAME_R /**/
?H:#define TTYNAME_R_PROTO $ttyname_r_proto /**/
?H:
?T:try hdrs d_ttyname_r_proto
: see if ttyname_r exists
set ttyname_r d_ttyname_r
```

```

eval $inlibc
case "$d_ttyname_r" in
"$define")
hdrs="$i_systypes sys/types.h define stdio.h $i_unistd unistd.h"
case "$d_ttyname_r_proto:$usethreads" in
":define") d_ttyname_r_proto=define
set d_ttyname_r_proto ttyname_r $hdrs
eval $hasproto ;;
*) ;;
esac
case "$d_ttyname_r_proto" in
define)
case "$ttyname_r_proto" in
"|0) try='int ttyname_r(int, char*, size_t);'
./protochk "$$extern_C $try" $hdrs && ttyname_r_proto=I_IBW ;;
esac
case "$ttyname_r_proto" in
"|0) try='int ttyname_r(int, char*, int);'
./protochk "$$extern_C $try" $hdrs && ttyname_r_proto=I_IBI ;;
esac
case
"$ttyname_r_proto" in
"|0) try='char* ttyname_r(int, char*, int);'
./protochk "$$extern_C $try" $hdrs && ttyname_r_proto=B_IBI ;;
esac
case "$ttyname_r_proto" in
"|0) d_ttyname_r=undef
ttyname_r_proto=0
echo "Disabling ttyname_r, cannot determine prototype." >&4 ;;
* ) case "$ttyname_r_proto" in
REENTRANT_PROTO*) ;;
*) ttyname_r_proto="REENTRANT_PROTO_$ttyname_r_proto" ;;
esac
echo "Prototype: $try" ;;
esac
;;
*) case "$usethreads" in
define) echo "ttyname_r has no prototype, not using it." >&4 ;;
esac
d_ttyname_r=undef
ttyname_r_proto=0
;;
esac
;;
*) ttyname_r_proto=0
;;
esac

```

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/threads/d_ttyname_r.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1996,1998 Andy Dougherty

?RCS: Copyright (c) 1996, Sven Verdoolaege

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?MAKE:d_gnulibc gnulibc_version: Myread Oldconfig Setvar rm_try \
cat Compile run

?MAKE: -pick add \$@ %<

?S:d_gnulibc:

?S: Defined if we're dealing with the GNU C Library.

?S:.

?S:gnulibc_version:

?S: This variable contains the version number of the GNU C library.

?S: It is usually something like '2.2.5'. It is a plain " if this

?S: is not the GNU C library, or if the version is unknown.

?S:.

?C:HAS_GNULIBC ~ %<:

?C: This

symbol, if defined, indicates to the C program that

?C: the GNU C library is being used. A better check is to use

?C: the __GLIBC__ and __GLIBC_MINOR__ symbols supplied with glibc.

?C:.

?H:%<:#\$d_gnulibc HAS_GNULIBC /**/

?H:%<:#if defined(HAS_GNULIBC) && !defined(_GNU_SOURCE)

?H:%<:#define _GNU_SOURCE

?H:%<:#endif

?H:.

?F:!glibc.ver !try.c !try

?LINT: set d_gnulibc

?LINT: usefile try.c

?LINT: known _GNU_SOURCE

?X: gnulibc can be executed by calling __libc_main().

?X: Ulrich Drepper doesn't think any other libc does that,

?X: but we check if it says 'GNU C Library' to be sure.

?X:

?X: Alas, as of 3/1998 glibc 2.0.7 reportedly isn't going to

?X: have `__libc_main()` anymore. :-(. Fortunately, all released
?X: versions of `glibc 2.x.x _do_` have CPP variables. For 2.0.6,
?X: they are:
?X: `#define __GLIBC__ 2`
?X: `#define __GLIBC_MINOR__ 0.`
?X: (The '6' isn't available :-(.
?X: `glibc2.1` will also have
?X: `extern const char * __gnu_get_libc_release(void);`
?X: `extern const char *`
?X: `__gnu_get_libc_version(void);`
?X: functions. --thanks to Andreas Jaeger. --AD 6/1998.
?X: Although the exact format isn't documented, `__gnu_get_libc_version()`
?X: returns a simple string '2.1.3' in `glibc 2.1.3`.
?X:
: determine whether we are using a GNU C library
echo " "
echo "Checking for GNU C Library..." >&4
cat >try.c <<'EOCP'
/* Find out version of GNU C library. __GLIBC__ and __GLIBC_MINOR__
alone are insufficient to distinguish different versions, such as
2.0.6 and 2.0.7. The function `gnu_get_libc_version()` appeared in
libc version 2.1.0. A. Dougherty, June 3, 2002.
*/
#include <stdio.h>
int main(void)
{
#ifdef __GLIBC__
ifdef __GLIBC_MINOR__
if __GLIBC__ >= 2 && __GLIBC_MINOR__ >= 1
include <gnu/libc-version.h>
printf("%s\n", gnu_get_libc_version());
else
printf("%d.%d\n", __GLIBC__, __GLIBC_MINOR__);
endif
else
printf("%d\n", __GLIBC__);
endif
return 0;
#else
return 1;
#endif
}
EOCP
set
try
if eval \$compile_ok && \$run ./try > glibc.ver; then
val="\$define"
gnulibc_version=`\$cat glibc.ver`

```
echo "You are using the GNU C Library version $gnulibc_version"
else
val="$undef"
gnulibc_version="
echo "You are not using the GNU C Library"
fi
$rm_try glibc.ver
set d_gnulibc
eval $setvar
```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/d_gnulibc.U
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: i_sched.U,v \$

?RCS:

?RCS: Copyright (c) 1999 Jarkko Hietaniemi

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?MAKE:i_sched: Inhdr Hasfield

?MAKE: -pick add \$@ %<

?S:i_sched:

?S: This variable conditionally defines the I_SCHED symbol, and indicates

?S: whether a C program should include <sched.h>.

?S:.

?C:I_SCHED:

?C: This symbol, if defined, indicates that <sched.h> exists and

?C: should be included.

?C:.

?H:#\$i_sched I_SCHED /**/

?H:.

?LINT:set i_sched

: see if this is a sched.h system

set sched.h i_sched

eval \$inhdr

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/perl/i_sched.U
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1999 Jarkko Hietaniemi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 3.0.
?RCS:
?MAKE:sitehtml3dir sitehtml3direxp installsitehtml3dir: Getfile \
Setprefixvar prefix siteprefix html3dir sed
?MAKE: -pick add \$@ %<
?Y:TOP
?D:sitehtml3dir="
?S:sitehtml3dir:
?S: This variable contains the name of the directory in which site-specific
?S: library html source pages are to be put. It is the responsibility of the
?S: Makefile.SH to get the value of this into the proper command.
?S: You must be prepared to do the ~name expansion yourself.
?S: The standard distribution will put nothing in this directory.
?S: After
perl has been installed, users may install their own local
?S: library html pages in this directory with
?S: MakeMaker Makefile.PL
?S: or equivalent. See INSTALL for details.
?S:.
?D:sitehtml3direxp="
?S:sitehtml3direxp:
?S: This variable is the same as the sitehtml3dir variable, but is filename
?S: expanded at configuration time, for convenient use in makefiles.
?S:.
?D:installsitehtml3dir="
?S:installsitehtml3dir:
?S: This variable is really the same as sitehtml3direxp, unless you are using
?S: AFS in which case it points to the read/write location whereas
?S: html3direxp only points to the read-only access location. For extra
?S: portability, you should only use this variable within your makefiles.
?S:.
?LINT:change prefixvar
?LINT:set installsitehtml3dir
?LINT:set sitehtml3dir
?LINT:set sitehtml3direxp
: determine where add-on library html pages go
: There is no standard location, so try to copy the previously-selected
: directory structure for the core html pages.
case
"\$sitehtml3dir" in
") dflt=`echo "\$html3dir" | \$sed "s#^\$prefix#\$siteprefix#"` ;;
*) dflt=\$sitehtml3dir ;;
esac
case "\$dflt" in

```
"|' ') dflt=none ;;
esac
fn=dn+~
rp='Pathname where the site-specific library html pages should be installed?'
./getfile
prefixvar=sitehtml3dir
./setprefixvar
```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/installdirs/sitehtml3dir.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: voidflags.U,v 3.0.1.2 1997/02/28 16:27:58 ram Exp $
?RCS:
?RCS: Copyright (c) 1991-1993, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 3.0.
?RCS:
?RCS: $Log: voidflags.U,v $
?RCS: Revision 3.0.1.2 1997/02/28 16:27:58 ram
?RCS: patch61: don't prompt them if the void support is high enough for us
?RCS:
?RCS: Revision 3.0.1.1 1995/01/11 15:37:44 ram
?RCS: patch45: cosmetic change to avoid spurious blank lines when using -s
?RCS:
?RCS: Revision 3.0 1993/08/18 12:10:01 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:voidflags defvoidused: cat rm_try contains +cc +ccflags package \
Oldconfig
Myread i_stdlib
?MAKE: -pick add $@ %<
?S:voidflags:
?S: This variable contains the eventual value of the VOIDFLAGS symbol,
?S: which indicates how much support of the void type is given by this
?S: compiler. See VOIDFLAGS for more info.
?S:.
?S:defvoidused:
?S: This variable contains the default value of the VOIDUSED symbol (15).
?S:.
?X: Exceptionally, we have to explicitly alias the symbol name for
?X: config_h.SH, otherwise the comment would not appear.
?C:VOIDFLAGS ~ %<
```

?C: This symbol indicates how much support of the void type is given by this
?C: compiler. What various bits mean:
?C:
?C: 1 = supports declaration of void
?C: 2 = supports arrays of pointers to functions returning void
?C: 4 = supports comparisons between pointers to void functions and
?C: addresses of void functions
?C: 8 = supports declaration of generic void pointers
?C:
?C: The package designer should define VOIDUSED to indicate the requirements
?C: of the package. This can be done either
?C: by #defining VOIDUSED before
?C: including config.h, or by defining defvoidused in Myinit.U. If the
?C: latter approach is taken, only those flags will be tested. If the
?C: level of void support necessary is not present, defines void to int.
?C:.

```
?H:%<:#ifndef VOIDUSED
?H:%<:#define VOIDUSED $defvoidused
?H:%<:#endif
?H:%<:#define VOIDFLAGS $voidflags
?H:%<:#if (VOIDFLAGS & VOIDUSED) != VOIDUSED
?H:%<:#define void int /* is void to be avoided? */
?H:%<:#define M_VOID /* Xenix strikes again */
?H:%<:#endif
?H:.
```

?INIT:: full support for void wanted by default
?INIT: defvoidused=15
?INIT:
?LINT: known void M_VOID VOIDUSED
: check for void type
echo " "
echo "Checking to see how well your C compiler groks the void type..." >&4
case "\$voidflags" in
")
\$cat >try.c <<EOCP
#\$i_stdlib I_STDLIB
#ifdef I_STDLIB
#include <stdlib.h>
#endif
#if TRY & 1
void sub() {
#else
sub() {
#endif
extern void moo(); /* function returning void */
void (*goo)(); /* ptr to func returning void
*/
#if TRY & 8

```

void *hue; /* generic ptr */
#endif
#if TRY & 2
void (*foo[10])();
#endif

```

```

#if TRY & 4
if(goo == moo) {
    exit(0);
}
#endif
exit(0);
}
int main() { sub(); }

```

EOCP

?X: This unit used to use cc -S in those tests to try to speed up things, but

?X: unfortunately, AIX 3.2 does not support this option.

```

if $cc $ccflags -c -DTRY=$defvoidused try.c >.out 2>&1 ; then
    voidflags=$defvoidused
    echo "Good. It appears to support void to the level $package wants.">&4
    if $contains warning .out >/dev/null 2>&1; then
        echo "However, you might get some warnings that look like this:"
        $cat .out
    fi
else
    echo "Hmm, your compiler has some difficulty with void. Checking further..." >&4
    if $cc $ccflags -c -DTRY=1 try.c >/dev/null 2>&1; then
        echo "It supports 1..."
    if $cc $ccflags -c -DTRY=3 try.c >/dev/null 2>&1; then
        echo "It also supports 2..."
    if $cc $ccflags -c -DTRY=7 try.c >/dev/null 2>&1; then
        voidflags=7
        echo "And it supports 4 but not 8 definitely."
    else
        echo
        "It doesn't support 4..."
        if $cc $ccflags -c -DTRY=11 try.c >/dev/null 2>&1; then
            voidflags=11
            echo "But it supports 8."
        else
            voidflags=3
            echo "Neither does it support 8."
        fi
    fi
else
    echo "It does not support 2..."
    if $cc $ccflags -c -DTRY=13 try.c >/dev/null 2>&1; then
        voidflags=13

```

```

echo "But it supports 4 and 8."
else
if $cc $ccflags -c -DTRY=5 try.c >/dev/null 2>&1; then
voidflags=5
echo "And it supports 4 but has not heard about 8."
else
echo "However it supports 8 but not 4."
fi
fi
fi
else
echo "There is no support at all for void."
voidflags=0
fi
fi
esac
?X: Only prompt user if support does not match the level we want
case "$voidflags" in
"$defvoidused") ;;
*) $cat >&4 <<'EOM'
Support flag bits are:
1: basic void declarations.
2: arrays of pointers to functions returning void.
4: operations between pointers to and addresses of
void functions.
8: generic void pointers.
EOM
dflt="$voidflags";
rp="Your void support flags add up to what?"
./myread
voidflags="$ans"
;;
esac
$rm_try

```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/modified/voidflags.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: i_syswait.U 1 2006-08-24 12:32:52Z rmanfredi $
```

```
?RCS:
```

```
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
```

```
?RCS:
```

```
?RCS: You may redistribute only under the terms of the Artistic Licence,
```

```
?RCS: as specified in the README file that comes with the distribution.
```

```
?RCS: You may reuse parts of this distribution only within the terms of
```

```
?RCS: that same Artistic Licence; a copy of which may be found at the root
```

```

?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: $Log: i_syswait.U,v $
?RCS: Revision 3.0 1993/08/18 12:08:42 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?X:
?X: This unit looks wether <sys/wait.h> is available or not
?X:
?MAKE:i_syswait: Inhdr
?MAKE: -pick add $@ %<
?S:i_syswait:
?S: This variable conditionally defines I_SYS_WAIT, which indicates
?S: to the C program that it should include <sys/wait.h>.
?S:.
?C:I_SYS_WAIT (I_SYSWAIT):
?C: This symbol, if defined, indicates to the C program
that it should
?C: include <sys/wait.h>.
?C:.
?H:#$i_syswait I_SYS_WAIT /**/
?H:.
?LINT:set i_syswait
: see if this is a syswait system
set sys/wait.h i_syswait
eval $inhdr

```

Found in path(s):

```

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/i_syswait.U

```

No license file was found, but licenses were detected in source scan.

```

# $Id: errnolist.a,v 3.0 1993/08/18 12:04:35 ram Exp ram $
#
# Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
#
# You may redistribute only under the terms of the Artistic Licence,
# as specified in the README file that comes with the distribution.
# You may reuse parts of this distribution only within the terms of
# that same Artistic Licence; a copy of which may be found at the root
# of the source tree for dist 4.0.
#
# Original Author: Harlan Stenn <harlan@mumps.pfcs.com>
#
# $Log: errnolist.a,v $
# Revision 3.0 1993/08/18 12:04:35 ram
# Baseline for dist 3.0 netwide release.
#

```

```

#
# This is a simple-minded awk script to generate an initialization for
# sys_errnolist on systems that don't have it.
# This file now depends only on sys/errno.h error numbers under maxerr being
# in order. It will complain and die if not. NOTE: It will still produce
# a compilable output file, even with errors, so you
# must check the output.

BEGIN {
    format = "\t\"%s\", \n"
    printf("/*\n** This is a generated file. Do NOT edit it unless you really have to...\n*/\n\n")
    printf("char *sys_errnolist[] = {\n")
    maxerr = 89
}

$1=="#define" {
    if(count > maxerr || substr($2,1,1) != "E")
        next # we're not interested
    if($3 < count) { # this is bad
        printf("Fatal error: %s out of order at %s\n", \
            FILENAME, $2)>"/dev/tty"
        exit 1
    }
    # fill in the blanks
    while($3 > count) {
        dummy=sprintf("EDUMMY%d",count)
        printf(format,dummy)
        count++
    }
    printf(format,$2)
    count++
}

END {
    printf("\t0\n"); \n
}

```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/lib/errnolist.a
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_endservent_r.U,v 0RCS:

?RCS: Copyright (c) 2002,2003 Jarkko Hietaniemi

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:
?RCS: Generated by the reentr.pl from the Perl 5.8 distribution.
?RCS:
?MAKE:d_endservent_r_endservent_r_proto: Inlibc Protochk Hasproto i_systypes \
usethreads i_netdb extern_C
?MAKE: -pick add \$@ %<
?S:d_endservent_r:
?S: This variable conditionally defines the HAS_ENDSERVENT_R symbol,
?S: which indicates to the C program that the endservent_r()
?S: routine is available.
?S:.
?S:endservent_r_proto:
?S: This variable encodes the prototype of endservent_r.
?S: It is zero if d_endservent_r is undef, and one of the
?S: REENTRANT_PROTO_T_ABC macros of reentr.h if d_endservent_r
?S: is defined.
?S:.
?C:HAS_ENDSERVENT_R:
?C: This symbol, if defined, indicates that the endservent_r routine
?C: is
available to endservent re-entrantly.
?C:.
?C:ENDSERVENT_R_PROTO:
?C: This symbol encodes the prototype of endservent_r.
?C: It is zero if d_endservent_r is undef, and one of the
?C: REENTRANT_PROTO_T_ABC macros of reentr.h if d_endservent_r
?C: is defined.
?C:.
?H:#\$d_endservent_r HAS_ENDSERVENT_R /**/
?H:#define ENDSERVENT_R_PROTO \$endservent_r_proto /**/
?H:.
?T:try hdrs d_endservent_r_proto
: see if endservent_r exists
set endservent_r d_endservent_r
eval \$inlibc
case "\$d_endservent_r" in
"\$define")
hdrs="\$i_systypes sys/types.h define stdio.h \$i_netdb netdb.h"
case "\$d_endservent_r_proto:\$usethreads" in
":define") d_endservent_r_proto=define
set d_endservent_r_proto endservent_r \$hdrs
eval \$hasproto ;;
*) ;;
esac
case "\$d_endservent_r_proto" in
define)
case "\$endservent_r_proto" in
"|0) try='int endservent_r(struct servent_data*);'

```

./protochk "$extern_C $try" $hdrs && endservent_r_proto=I_D ;;
esac
case "$endservent_r_proto" in
"|0) try='void
endservent_r(struct servent_data*);'
./protochk "$extern_C $try" $hdrs && endservent_r_proto=V_D ;;
esac
case "$endservent_r_proto" in
"|0) d_endservent_r=undef
endservent_r_proto=0
echo "Disabling endservent_r, cannot determine prototype." >&4 ;;
*) case "$endservent_r_proto" in
REENTRANT_PROTO*) ;;
*) endservent_r_proto="REENTRANT_PROTO_$endservent_r_proto" ;;
esac
echo "Prototype: $try" ;;
esac
;;
*) case "$usethreads" in
define) echo "endservent_r has no prototype, not using it." >&4 ;;
esac
d_endservent_r=undef
endservent_r_proto=0
;;
esac
;;
*) endservent_r_proto=0
;;
esac

```

Found in path(s):

```

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/threads/d_endservent_r.U

```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_sbrk.U 1 2006-08-24 12:32:52Z rmanfredi \$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic Licence,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic Licence; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: d_sbrk.U,v \$

?RCS: Revision 3.0.1.1 1994/01/24 14:06:31 ram

?RCS: patch16: created

?RCS:
?MAKE:d_sbrk: Inlibc
?MAKE: -pick add \$@ %<
?S:d_sbrk:
?S: This variable conditionally defines HAS_SBRK if sbrk() is
?S: available to add more core to the process.
?S:.
?C:HAS_SBRK:
?C: This symbol, if defined, indicates that the sbrk system call is
?C: available to add/release core. Always true on Unix.
?C:.
?H:#\$d_sbrk HAS_SBRK /**/
?H:.
?LINT:set d_sbrk
: see
if sbrk exists
set sbrk d_sbrk
eval \$inlibc

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/d_sbrk.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: \$Log: lib.U,v \$
?RCS: Revision 3.0.1.3 1995/09/25 09:16:47 ram
?RCS: patch59: unit is now forced to the top of Configure, if possible
?RCS:
?RCS: Revision 3.0.1.2 1995/01/30 14:38:08 ram
?RCS: patch49: can now handle installation prefix changes (from WED)
?RCS:
?RCS: Revision 3.0.1.1 1994/08/29 16:27:40 ram
?RCS: patch32: now uses installation prefix to set the default
?RCS:
?RCS: Revision 3.0 1993/08/18 12:08:56 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:lib libexp: Getfile

```

Loc Oldconfig Prefixit Prefixup prefixexp
?MAKE: -pick add $@ %<
?Y:TOP
?S:lib:
?S: This variable holds the name of the directory in which the user wants
?S: to put public library files for the package in question. It is most
?S: often a local directory such as /usr/local/lib. Programs using this
?S: variable must be prepared to deal with filename expansion.
?S:.
?S:libexp:
?S: This variable is the same as the lib variable, but is filename expanded
?S: at configuration time, for convenient use in your makefiles.
?S:.
: determine where public libraries go
set lib lib
eval $prefixit
case "$lib" in
")
dflt=`./loc . ." $prefixexp/lib /usr/local/lib /usr/lib /lib`
set dflt
eval $prefixup
;;
*) dflt="$lib";;
esac
echo " "
fn=d~
rp='Where do you want to put the public libraries?'
./getfile
lib="$ans"
libexp="$ansexp"

```

Found in path(s):

```

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/lib.U

```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_getnetent_r.U,v ORCS:

?RCS: Copyright (c) 2002,2003 Jarkko Hietaniemi

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?RCS: Generated by the reentr.pl from the Perl 5.8 distribution.

?RCS:

```

?MAKE:d_getnetent_r getnetent_r_proto: Inlibc Protochk Hasproto i_systypes \
  usethreads i_netdb extern_C

```

?MAKE: -pick add \$@ %<

?S:d_getnetent_r:

?S: This variable conditionally defines the HAS_GETNETENT_R symbol,
 ?S: which indicates to the C program that the getnetent_r()
 ?S: routine is available.
 ?S:.
 ?S:getnetent_r_proto:
 ?S: This variable encodes the prototype of getnetent_r.
 ?S: It is zero if d_getnetent_r is undef, and one of the
 ?S: REENTRANT_PROTO_T_ABC macros of reentr.h if d_getnetent_r
 ?S: is defined.
 ?S:.
 ?C:HAS_GETNETENT_R:
 ?C: This symbol, if defined, indicates that the getnetent_r routine
 ?C: is
 available to getnetent re-entrantly.
 ?C:.
 ?C:GETNETENT_R_PROTO:
 ?C: This symbol encodes the prototype of getnetent_r.
 ?C: It is zero if d_getnetent_r is undef, and one of the
 ?C: REENTRANT_PROTO_T_ABC macros of reentr.h if d_getnetent_r
 ?C: is defined.
 ?C:.
 ?H:#\$d_getnetent_r HAS_GETNETENT_R /**/
 ?H:#define GETNETENT_R_PROTO \$getnetent_r_proto /**/
 ?H:.
 ?T:try hdrs d_getnetent_r_proto
 : see if getnetent_r exists
 set getnetent_r d_getnetent_r
 eval \$inlibc
 case "\$d_getnetent_r" in
 "\$define")
 hdrs="\$i_systypes sys/types.h define stdio.h \$i_netdb netdb.h"
 case "\$d_getnetent_r_proto:\$usetreads" in
 ":define") d_getnetent_r_proto=define
 set d_getnetent_r_proto getnetent_r \$hdrs
 eval \$hasproto ;;
 *) ;;
 esac
 case "\$d_getnetent_r_proto" in
 define)
 case "\$getnetent_r_proto" in
 "|0) try='int getnetent_r(struct netent*, char*, size_t, struct netent**, int*);'
 ./protochk "\$extern_C \$try" \$hdrs && getnetent_r_proto=I_SBWRE ;;
 esac
 case "\$getnetent_r_proto" in
 "|0) try='int
 getnetent_r(struct netent*, char*, int, int*);'
 ./protochk "\$extern_C \$try" \$hdrs && getnetent_r_proto=I_SBIE ;;
 esac

```

case "$getnetent_r_proto" in
"|0) try='struct netent* getnetent_r(struct netent*, char*, int, int*);'
./protochk "$extern_C $try" $hdrs && getnetent_r_proto=S_SBIE ;;
esac
case "$getnetent_r_proto" in
"|0) try='struct netent* getnetent_r(struct netent*, char*, int);'
./protochk "$extern_C $try" $hdrs && getnetent_r_proto=S_SBI ;;
esac
case "$getnetent_r_proto" in
"|0) try='int getnetent_r(struct netent*, char*, int);'
./protochk "$extern_C $try" $hdrs && getnetent_r_proto=I_SBI ;;
esac
case "$getnetent_r_proto" in
"|0) try='int getnetent_r(struct netent*, struct netent_data*);'
./protochk "$extern_C $try" $hdrs && getnetent_r_proto=I_SD ;;
esac
case "$getnetent_r_proto" in
"|0) d_getnetent_r=undef
    getnetent_r_proto=0
    echo "Disabling getnetent_r, cannot determine prototype." >&4 ;;
*) case "$getnetent_r_proto" in
    REENTRANT_PROTO*)
;;
*) getnetent_r_proto="REENTRANT_PROTO_$getnetent_r_proto" ;;
esac
echo "Prototype: $try" ;;
esac
;;
*) case "$usethreads" in
define) echo "getnetent_r has no prototype, not using it." >&4 ;;
esac
d_getnetent_r=undef
getnetent_r_proto=0
;;
esac
;;
*) getnetent_r_proto=0
;;
esac

```

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/threads/d_getnetent_r.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1998, Jarkko Hietaniemi

?RCS:
?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 3.0.

?RCS:
?MAKE:i_sysaccess: Inhdr
?MAKE: -pick add \$@ %<
?S:i_sysaccess:
?S: This variable conditionally defines the I_SYS_ACCESS symbol,
?S: and indicates whether a C program should include <sys/access.h>.
?S:.

?C:I_SYS_ACCESS:
?C: This symbol, if defined, indicates to the C program that it should
?C: include <sys/access.h>.
?C:.

?H:#\$i_sysaccess I_SYS_ACCESS /**/
?H:.

?LINT:set i_sysaccess
: see if sys/access.h is available
set sys/access.h i_sysaccess
eval \$inhdr

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/acl/i_sysaccess.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$
?RCS:
?RCS: Copyright (c) 2000 Jarkko Hietaniemi
?RCS:
?RCS: You may distribute under the terms of either the GNU General Public
?RCS: License or the Artistic License, as specified in the README file.
?RCS:

?MAKE:d_getitimer: Inlibc
?MAKE: -pick add \$@ %<
?S:d_getitimer:
?S: This variable conditionally defines the HAS_GETITIMER symbol, which
?S: indicates to the C program that the getitimer() routine is available.
?S:.
?C:HAS_GETITIMER:
?C: This symbol, if defined, indicates that the getitimer routine is
?C: available to return interval timers.
?C:.
?H:#\$d_getitimer HAS_GETITIMER /**/
?H:.

?LINT:set d_getitimer
: see if getitimer exists
set getitimer d_getitimer
eval \$inlibc

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_getitimer.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_dlopen.U,v 3.0.1.2 1995/07/25 13:52:56 ram Exp \$
?RCS:
?RCS: Copyright (c) 1991-1993, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 3.0.
?RCS:
?RCS: Original Author: Andy Dougherty <doughera@lafcol.lafayette.edu>
?RCS:
?RCS: \$Log: d_dlopen.U,v \$
?RCS: Revision 3.0.1.2 1995/07/25 13:52:56 ram
?RCS: patch56: force compile-link test since symbol might lie in crt0.o (ADO)
?RCS:
?RCS: Revision 3.0.1.1 1994/08/29 16:07:34 ram
?RCS: patch32: created by ADO
?RCS:
?MAKE:d_dlopen: Inlibc runnm d_cplusplus ccflags gccversion
?MAKE: -pick add \$@ %<
?S:d_dlopen:
?S: This variable conditionally defines the HAS_DLOPEN
symbol, which
?S: indicates to the C program that the dlopen() routine is available.
?S:.
?C:HAS_DLOPEN :
?C: This symbol, if defined, indicates that the dlopen routine is
?C: available.
?C:.
?H:#\$d_dlopen HAS_DLOPEN /**/
?H:.
?T: xxx_runnm
?T: xxx_ccflags
?LINT:set d_dlopen
?X: We don't permanently change runnm and ccflags, but we do temporarily.
?LINT: change runnm
?LINT: change ccflags

```

: see if dlopen exists
?X: On NetBSD and FreeBSD, dlopen is available, but it is in
?X: /usr/lib/crt0.o, not in any of the libraries. Therefore, do not
?X: use the nm extraction, but use a real compile and link test instead.
xxx_runnm="$runnm"
xxx_ccflags="$ccflags"
runnm=false
: with g++ one needs -shared to get is-in-libc to work for dlopen
case "$gccversion" in
") ;;
*Clang*) ;;
*) case "$d_cplusplus" in
"$define") ccflags="$ccflags -shared" ;;
esac
;;
esac
set dlopen d_dlopen
eval $inlibc
runnm="$xxx_runnm"
ccflags="$xxx_ccflags"

```

Found in path(s):

```

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/modified/d_dlopen.U

```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1996, Andy Dougherty

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: man1dir.U,v \$

?RCS: Revision 3.0.1.1 1997/02/28 16:10:29 ram

?RCS: patch61: created

?RCS:

?X:

?X: This was originally specific to perl5. Since perl5 has man pages that

?X: go in both man1/ and man3/ directories, we need both man1dir

?X: and man3dir. This unit is basically dist's mansrc.U with

?X: man1 used instead of man everywhere.

?X:

?MAKE:man1dir man1direxp man1ext installman1dir: afs cat nroff Loc Oldconfig \

```

package test Getfile Prefixit prefixexp
Prefixup sysman Myread
?MAKE: -pick add $@ %<
?Y:TOP
?S:man1dir:
?S: This variable contains the name of the directory in which manual
?S: source pages are to be put. It is the responsibility of the
?S: Makefile.SH to get the value of this into the proper command.
?S: You must be prepared to do the ~name expansion yourself.
?S:.
?S:man1direxp:
?S: This variable is the same as the man1dir variable, but is filename
?S: expanded at configuration time, for convenient use in makefiles.
?S:.
?S:installman1dir:
?S: This variable is really the same as man1direxp, unless you are using
?S: AFS in which case it points to the read/write location whereas
?S: man1direxp only points to the read-only access location. For extra
?S: portability, you should only use this variable within your makefiles.
?S:.
?S:man1ext:
?S: This variable contains the extension that the manual page should
?S: have: one of 'n', 'l', or '1'. The Makefile must supply the '!'.
?S: See man1dir.
?S:.
?T:lookpath
: determine
  where manual pages go
set man1dir man1dir none
eval $prefixit
$cat <<EOM

$package has manual pages available in source form.
EOM
case "$nroff" in
nroff)
echo "However, you don't have nroff, so they're probably useless to you."
case "$man1dir" in
") man1dir="none";;
esac;;
esac
echo "If you don't want the manual sources installed, answer 'none'."
case "$man1dir" in
' ) dflt=none
;;
")
lookpath="$prefixexp/man/man1 $prefixexp/man/l_man/man1"
lookpath="$lookpath $prefixexp/man/p_man/man1"

```

```

lookpath="$lookpath $prefixexp/man/u_man/man1"
lookpath="$lookpath $prefixexp/man/man.1"
?X: Experience has shown people expect man1dir to be under prefix,
?X: so we now always put it there. Users who want other behavior
?X: can answer interactively or use a command line option.
?X: Does user have System V-style man paths.
case "$sysman" in
*/?_man*) dflt=`./loc . $prefixexp/l_man/man1 $lookpath` ;;
*) dflt=`./loc . $prefixexp/man/man1 $lookpath` ;;
esac
set dflt
eval $prefixup
;;
*)
  dflt="$man1dir"
  ;;
esac
echo " "
fn=dn+~
rp="Where do the main $spackge manual pages (source) go?"
./getfile
if $test "X$man1direxp" != "X$sansexp"; then
  installman1dir="
fi
man1dir="$ans"
man1direxp="$sansexp"
case "$man1dir" in
") man1dir=' '
  installman1dir="";;
esac
if $afs; then
  $cat <<EOM

```

Since you are running AFS, I need to distinguish the directory in which manual pages reside from the directory in which they are installed (and from which they are presumably copied to the former directory by occult means).

```

EOM
case "$installman1dir" in
") dflt=`echo $man1direxp | sed 's#^/afs/#/afs/.#`";;
*) dflt="$installman1dir";;
esac
fn=de~
rp='Where will man pages be installed?'
./getfile
installman1dir="$ans"
else
  installman1dir="$man1direxp"

```

fi

: What suffix to use on installed man pages

```
case "$man1dir" in
' ')
man1ext='0'
;;
*)
rp="What suffix should be used for the main $spackage man pages?"
case "$man1ext" in
") case "$man1dir" in
*1) dflt=1 ;;
*1p)
dflt=1p ;;
*1pm) dflt=1pm ;;
*1) dflt=1;;
*n) dflt=n;;
*o) dflt=o;;
*p) dflt=p;;
*C) dflt=C;;
*L) dflt=L;;
*L1) dflt=L1;;
*) dflt=1;;
esac
;;
*) dflt="$man1ext";;
esac
./myread
man1ext="$ans"
;;
esac
```

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/man1dir.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 2000 Jarkko Hietaniemi

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?MAKE:d_getcwd: Inlibc

?MAKE:-pick add \$@ %<

?S:d_getcwd:

?S: This variable conditionally defines the HAS_GETCWD symbol, which
?S: indicates to the C program that the getcwd() routine is available
?S: to get the current working directory.
?S:.
?C:HAS_GETCWD :
?C: This symbol, if defined, indicates that the getcwd routine is
?C: available to get the current working directory.
?C:.
?H:#\$d_getcwd HAS_GETCWD /**/
?H:.
?LINT:set d_getcwd
: see if getcwd exists
set getcwd d_getcwd
eval \$inlibc

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_getcwd.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$
?RCS:
?RCS: Copyright (c) 1999, Jarkko Hietaniemi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 3.0.
?RCS:
?MAKE:d_sem_wait: Inlibc
?MAKE: -pick add \$@ %<
?S:d_sem_wait:
?S: This variable conditionally defines HAS_SEM_WAIT if sem_wait() is
?S: available to wait (grab, lock) a POSIX semaphore.
?S:.
?C:HAS_SEM_WAIT:
?C: This symbol, if defined, indicates that the sem_wait system call is
?C: available to wait (grab, lock) a POSIX semaphore.
?C:.
?H:#\$d_sem_wait HAS_SEM_WAIT /**/
?H:.
?LINT:set d_sem_wait
: see if sem_wait exists
set sem_wait d_sem_wait
eval \$inlibc

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_sem_wait.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_endpwent.U,v \$

?RCS:

?RCS: Copyright (c) 1998 Andy Dougherty

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?RCS: \$Log: d_endpwent.U,v \$

?RCS:

?MAKE:d_endpwent: Inlibc

?MAKE: -pick add \$@ %<

?S:d_endpwent:

?S: This variable conditionally defines the HAS_ENDPWENT symbol, which

?S: indicates to the C program that the endpwent() routine is available

?S: for sequential access of the passwd database.

?S:.

?C:HAS_ENDPWENT:

?C: This symbol, if defined, indicates that the getgrent routine is

?C: available for finalizing sequential access of the passwd database.

?C:.

?H:#\$d_endpwent HAS_ENDPWENT /**/

?H:.

?LINT:set d_endpwent

: see if endpwent exists

set endpwent d_endpwent

eval \$inlibc

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/modified/d_endpwent.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_poll.U 15 2006-08-30 18:21:51Z rmanfredi \$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic Licence,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic Licence; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: d_poll.U,v \$

?RCS: Revision 3.0.1.2 1997/02/28 15:38:17 ram

?RCS: patch61: mention that <poll.h> can be included if HAS_POLL defined

?RCS:

?RCS: Revision 3.0.1.1 1995/01/11 15:26:31 ram

?RCS: patch45: created

?RCS:

?MAKE:d_poll: Inlibc

?MAKE: -pick add \$@ %<

?S:d_poll:

?S: This variable conditionally defines the HAS_POLL symbol, which

?S: indicates to the C program that the poll() routine is available

?S: to poll active file descriptors.

?S:.

?C:HAS_POLL

:

?C: This symbol, if defined, indicates that the poll routine is

?C: available to poll active file descriptors. Please check I_POLL and

?C: I_SYS_POLL to know which header should be included as well.

?C:.

?H:#\$d_poll HAS_POLL /**/

?H:.

?LINT:set d_poll

: see if poll exists

set poll d_poll

eval \$inlibc

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/d_poll.U

No license file was found, but licenses were detected in source scan.

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?MAKE:d_lrint: Inlibc

?MAKE: -pick add \$@ %<

?S:d_lrint:

?S: This variable conditionally defines the HAS_LRINT symbol, which

?S: indicates to the C program that the lrint() routine is available

?S: to return the integral value closest to a double (according

?S: to the current rounding mode).

?S:.

?C:HAS_LRINT:

?C: This symbol, if defined, indicates that the lrint routine is

?C: available to return the integral value closest to a double

?C: (according to the current rounding mode).

?C:.

?H:#\$d_lrint HAS_LRINT /**/

?H:.

```
?LINT:set d_lrint
: see if lrint exists
set lrint d_lrint
eval $inlibc
```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/perl/d_lrint.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id$
```

```
?RCS:
```

```
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
```

```
?RCS:
```

```
?RCS: You may redistribute only under the terms of the Artistic License,
```

```
?RCS: as specified in the README file that comes with the distribution.
```

```
?RCS: You may reuse parts of this distribution only within the terms of
```

```
?RCS: that same Artistic License; a copy of which may be found at the root
```

```
?RCS: of the source tree for dist 4.0.
```

```
?RCS:
```

```
?RCS: $Log: Config_sh.U,v $
```

```
?RCS: Revision 3.0.1.3 1997/02/28 14:57:53 ram
```

```
?RCS: patch61: added support for src.U
```

```
?RCS:
```

```
?RCS: Revision 3.0.1.2 1995/01/11 14:53:31 ram
```

```
?RCS: patch45: moved path stripping from d_portable.U to end of Configure
```

```
?RCS:
```

```
?RCS: Revision 3.0.1.1 1994/10/29 15:50:37 ram
```

```
?RCS: patch36: added ?F: line for metalint file checking
```

```
?RCS:
```

```
?RCS: Revision 3.0 1993/08/18 12:04:48 ram
```

```
?RCS: Baseline for dist 3.0 netwide release.
```

```
?RCS:
```

```
?X:
```

```
?X: This unit ends up producing the config.sh
```

```
script, which contains all the
```

```
?X: definitions figured out by Configure. The add.Config_sh command knows
```

```
?X: which variables need to be remembered. It also adds the EOT (ends the
```

```
?X: here document redirection with variable substitution).
```

```
?X:
```

```
?MAKE:Config_sh: cf_time cf_by test spitshell startsh myuname Myread \
```

```
End Obsol_sh Loc +d_portable package src cat sed
```

```
?MAKE: -pick add.Config_sh $@ %<
```

```
?MAKE: -pick add $@ ./Obsol_sh
```

```
?MAKE: -pick close.Config_sh $@ %<
```

```
?F:!config.over !config.arch
```

```
?T:file sfile xsed
```

```
?LINT:unclosed EOT
```

```

: back to where it started
if test -d ../UU; then
  cd ..
fi

: configuration may be unconditionally patched via a 'config.arch' file
if $test -f config.arch; then
  echo "I see a config.arch file, loading it." >&4
  . ./config.arch
fi

```

```

: configuration may be patched via a 'config.over' file
if $test -f config.over; then
  echo " "
  dflt=y
  rp='I see a config.over file. Do you wish to load it?'
  . UU/myread
  case "$ans" in
  n*) echo "OK, I'll ignore it.;;"
  *) . ./config.over
  echo
  "Configuration override changes have been loaded."
  ;;
  esac
fi

```

```

@if d_portable
: in case they want portability, strip down executable paths
?X:
?X: Strip down paths in located executables. For each file, e.g. vi, there
?X: is a $vi variable whose value is for instance '/usr/bin/vi'. By resetting
?X: $vi to 'vi', we rely on the PATH variable to locate the executable...
?X: In order to allow vi='/usr/bin/nvi' which will strip down to vi='nvi',
?X: we can't just say 'eval $file="\$file"', we have to recourse to sed.
?X: We don't use basename since it is less portable than sed.
?X:
case "$d_portable" in
"$define")
  echo " "
  echo "Stripping down executable paths..." >&4
  xsed=$sed
  for file in $loclist $trylist; do
    eval sfile="\$file"
    sfile=`echo $sfile | $xsed -e 's,.*^(.*)\,1,'`
    eval $file="$sfile"
  done
  ;;
esac

```

```
@end
: create config.sh file
echo " "
echo "Creating config.sh..." >&4
$spitshell <<EOT >config.sh
$startsh
#
# This file was produced by running the
# Configure script. It holds all the
# definitions figured out by Configure. Should you modify one of these values,
# do not forget to propagate your changes by running "Configure -der". You may
# instead choose to run each of the .SH files by yourself, or "Configure -S".
#

# Package name    : $package
# Source directory : $src
# Configuration time: $cf_time
# Configured by   : $cf_by
# Target system   : $myuname
```

EOT

```
?X: Command line options are saved by the Options.U unit in the
?X: temporary file UU/cmdline.opt
$test -f UU/cmdline.opt && $cat UU/cmdline.opt >> config.sh
$spitshell <<EOT >>config.sh
```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/Config_sh.U
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: d_memchr.U,v \$

?RCS: Revision 3.0 1993/08/18 12:06:32 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?MAKE:d_memchr: Inlibc

?MAKE: -pick add \$@ %<

?S:d_memchr:

?S: This variable conditionally defines the HAS_MEMCHR symbol, which

?S: indicates to the C program that the memchr() routine is available

?S: to scan a block of memory for a character.

?S:.

?C:HAS_MEMCHR:

?C: This symbol, if defined, indicates that the memchr routine is available

?C: to scan a block of memory for a character.

If undefined, roll your own.

?C:.

?H:#\$d_memchr HAS_MEMCHR /**/

?H:.

?LINT:set d_memchr

: see if memchr exists

set memchr d_memchr

eval \$inlibc

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/d_memchr.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: privlib.U,v \$

?RCS: Revision 3.0.1.4 1995/09/25 09:17:09 ram

?RCS: patch59: unit is now forced to the top of Configure, if possible

?RCS:

?RCS: Revision 3.0.1.3 1995/01/30 14:44:23 ram

?RCS: patch49: can now handle installation prefix changes (from WED)

?RCS:

?RCS: Revision 3.0.1.2 1994/08/29 16:31:52 ram

?RCS: patch32: now uses installation prefix

?RCS:

?RCS: Revision 3.0.1.1 1993/09/13 16:12:34 ram

?RCS: patch10: added support for /local/lib (WED)

?RCS: patch10: prompt phrasing made

more explicit (WED)

?RCS:

?RCS: Revision 3.0 1993/08/18 12:09:35 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?MAKE:privlib privlibexp installprivlib: afs package cat Getfile \
Oldconfig Prefixit test

?MAKE: -pick add \$@ %<

?Y:TOP

?S:privlib:

?S: This variable contains the eventual value of the PRIVLIB symbol,

?S: which is the name of the private library for this package. It may

?S: have a ~ on the front. It is up to the makefile to eventually create

?S: this directory while performing installation (with ~ substitution).

?S:.

?S:privlibexp:

?S: This variable is the ~name expanded version of privlib, so that you

?S: may use it directly in Makefiles or shell scripts.

?S:.

?S:installprivlib:

?S: This variable is really the same as privlibexp but may differ on

?S: those systems using AFS. For extra portability, only this variable

?S: should be used in makefiles.

?S:.

?C:PRIVLIB:

?C: This symbol contains the name of the private library for this package.

?C: The library is

private in the sense that it needn't be in anyone's

?C: execution path, but it should be accessible by the world. The program

?C: should be prepared to do ~ expansion.

?C:.

?C:PRIVLIB_EXP:

?C: This symbol contains the ~name expanded version of PRIVLIB, to be used

?C: in programs that are not prepared to deal with ~ expansion at run-time.

?C:.

?H:#define PRIVLIB "\$privlib" /**/

?H:#define PRIVLIB_EXP "\$privlibexp" /**/

?H:.

: determine where private executables go

set dflt privlib lib/\$package

eval \$prefixit

\$cat <<EOM

There are some auxiliary files for \$package that need to be put into a
private library directory that is accessible by everyone.

EOM

fn=d~+

rp='Pathname where the private library files will reside?'

./getfile

if \$test "X\$privlibexp" != "X\$sansexp"; then

```

installprivlib="
fi
privlib="$ans"
privlibexp="$ansexp"
if $afs; then
$cat <<EOM

```

Since you are running AFS, I need to distinguish the directory in which private files reside from the directory in which they are installed (and from which they are presumably copied to the former directory by occult means).

```

EOM
case "$installprivlib" in
") dflt=`echo $privlibexp | sed 's#^/afs/#/afs/#^`;;
*) dflt="$installprivlib";;
esac
fn=de~
rp='Where will private files be installed?'
./getfile
installprivlib="$ans"
else
installprivlib="$privlibexp"
fi

```

Found in path(s):

```

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/privlib.U

```

No license file was found, but licenses were detected in source scan.

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?MAKE:d_lgamma_r: Inlibc

?MAKE: -pick add \$@ %<

?S:d_lgamma_r:

?S: This variable conditionally defines the HAS_LGAMMA_R symbol, which

?S: indicates to the C program that the lgamma_r() routine is available

?S: for the log gamma function, without using the global signgam variable.

?S:.

?C:HAS_LGAMMA_R:

?C: This symbol, if defined, indicates that the lgamma_r routine is

?C: available to do the log gamma function without using the global

?C: signgam variable.

?C:.

?H:#\$d_lgamma_r HAS_LGAMMA_R /**/

?H:.

?LINT:set d_lgamma_r

```
: see if lgamma_r exists
set lgamma_r d_lgamma_r
eval $inlibc
```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/perl/d_lgamma_r.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: vendorbin.U,v 1.1 1999/07/08 18:32:57 doughera Exp doughera $
```

```
?RCS:
```

```
?RCS: Copyright (c) 1999, Andy Dougherty
```

```
?RCS:
```

```
?RCS: You may redistribute only under the terms of the Artistic License,
```

```
?RCS: as specified in the README file that comes with the distribution.
```

```
?RCS: You may reuse parts of this distribution only within the terms of
```

```
?RCS: that same Artistic License; a copy of which may be found at the root
```

```
?RCS: of the source tree for dist 3.0.
```

```
?RCS:
```

```
?RCS: $Log: vendorbin.U,v $
```

```
?RCS: Revision 1.1 1999/07/08 18:32:57 doughera
```

```
?RCS: Initial revision
```

```
?RCS:
```

```
?MAKE:d_vendorbin vendorbin vendorbinexp installvendorbin: Getfile \
```

```
Setprefixvar Oldconfig Prefixit vendorprefix
```

```
?MAKE: -pick add $@ %<
```

```
?Y:TOP
```

```
?S:vendorbin:
```

```
?S: This variable contains the eventual value of the VENDORBIN symbol.
```

```
?S: It may have a ~ on the front.
```

```
?S: The standard distribution will put nothing in this directory.
```

```
?S: Vendors who distribute perl
```

```
may wish to place additional
```

```
?S: binaries in this directory with
```

```
?S: MakeMaker Makefile.PL INSTALLDIRS=vendor
```

```
?S: or equivalent. See INSTALL for details.
```

```
?S:.
```

```
?S:vendorbinexp:
```

```
?S: This variable is the ~name expanded version of vendorbin, so that you
```

```
?S: may use it directly in Makefiles or shell scripts.
```

```
?S:.
```

```
?D:installvendorbin="
```

```
?S:installvendorbin:
```

```
?S: This variable is really the same as vendorbinexp but may differ on
```

```
?S: those systems using AFS. For extra portability, only this variable
```

```
?S: should be used in makefiles.
```

```
?S:.
```

```
?S:d_vendorbin:
```

?S: This variable conditionally defines PERL_VENDORBIN.

?S:.

?C:PERL_VENDORBIN:

?C: If defined, this symbol contains the name of a directory

?C: for holding vendor-supplied executables.

?C: It may have a ~ on the front.

?C: The standard distribution will put nothing in this directory.

?C: Vendors who distribute perl may wish to place additional

?C: binaries in this directory with

?C: MakeMaker Makefile.PL INSTALLDIRS=vendor

?C: or equivalent.

See INSTALL for details.

?C:.

?C:PERL_VENDORBIN_EXP:

?C: This symbol contains the ~name expanded version of VENDORBIN, to be used

?C: in programs that are not prepared to deal with ~ expansion at run-time.

?C:.

?H:#\$d_vendorbin PERL_VENDORBIN "\$vendorbin" /**/

?H:#\$d_vendorbin PERL_VENDORBIN_EXP "\$vendorbinexp" /**/

?H:.

?LINT:change prefixvar

?LINT:set installvendorbin

: Set the vendorbin variables

case "\$vendorprefix" in

) d_vendorbin="\$undef"

vendorbin="

vendorbinexp="

::

*) d_vendorbin="\$define"

: determine where vendor-supplied executables go.

case "\$vendorbin" in

) dflt=\$vendorprefix/bin ;;

*) dflt="\$vendorbin" ;;

esac

fn=d~+

rp='Pathname for the vendor-supplied executables directory?'

./getfile

vendorbin="\$ans"

vendorbinexp="\$ansexp"

::

esac

prefixvar=vendorbin

./installprefix

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/installdirs/vendorbin.U

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: html3dir.U,v $
?RCS:
?RCS: Copyright (c) 1999 Andy Dougherty
?RCS:
?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 3.0.
?RCS:
?RCS: $Log: html3dir.U,v $
?RCS:
?MAKE:html3dir html3direxp installhtml3dir: cat sed Loc Myread \
  spackage test Getfile Setprefixvar Prefixit Prefixup html1dir
?MAKE: -pick add $@ %<
?Y:TOP
?D:html3dir="
?S:html3dir:
?S: This variable contains the name of the directory in which html
?S: source pages are to be put. This directory is for pages
?S: that describe libraries or modules. It is intended to
?S: correspond roughly to section 3 of the Unix manuals.
?S:
?D:html3direxp="
?S:html3direxp:
?S: This variable
?S: is the same as the html3dir variable, but is filename
?S: expanded at configuration time, for convenient use in makefiles.
?S:
?D:installhtml3dir="
?S:installhtml3dir:
?S: This variable is really the same as html3direxp, unless you are
?S: using a different installprefix. For extra portability, you
?S: should only use this variable within your makefiles.
?S:
?LINT:change prefixvar
?LINT:set html3direxp
?LINT:set installhtml3dir
: determine where html pages for libraries and modules go
set html3dir html3dir none
eval $prefixit
$cat <<EOM
```

If you wish to install html files for modules associated with \$spackage, indicate the appropriate directory here. To skip installing html files, answer "none".

EOM

: There is no obvious default. If they have specified html1dir, then

: try to key off that, possibly changing ../html1 into ../html3.

case "\$html3dir" in

) html3dir=`echo "\$html1dir" | \$sed 's/1\$/3\$/'` ;;

*) dflt=\$html3dir ;;

esac

fn=dn+~

rp="Directory for the \$spackage module

html pages?"

./getfile

prefixvar=html3dir

./setprefixvar

: Use ' ' for none so value is preserved next time through Configure

\$test X"\$html3dir" = "X" && html3dir=' '

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/installdirs/html3dir.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_memmove.U 1 2006-08-24 12:32:52Z rmanfredi \$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic Licence,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic Licence; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: d_memmove.U,v \$

?RCS: Revision 3.0 1993/08/18 12:06:35 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?MAKE:d_memmove: Inlibc

?MAKE: -pick add \$@ %<

?S:d_memmove:

?S: This variable conditionally defines the HAS_MEMMOVE symbol, which

?S: indicates to the C program that the memmove() routine is available

?S: to copy potentially overlapping blocks of memory.

?S:.

?C:HAS_MEMMOVE:

?C: This symbol, if defined, indicates that the memmove routine
is available

?C: to copy potentially overlapping blocks of memory. This should be used

?C: only when HAS_SAFE_BCOPY is not defined. If neither is there, roll your

?C: own version.

```
?C:
?H:#$d_memmove HAS_MEMMOVE /**/
?H:
?LINT:set d_memmove
: see if memmove exists
set memmove d_memmove
eval $inlibc
```

Found in path(s):

```
*/opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/d_memmove.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: netdbtype.U,v $
?RCS:
?RCS: Copyright (c) 1998 Andy Dougherty
?RCS:
?RCS: You may distribute under the terms of either the GNU General Public
?RCS: License or the Artistic License, as specified in the README file.
?RCS:
?RCS: Original Author: Andy Dougherty <doughera@lafcol.lafayette.edu>
?RCS:
?RCS: $Log: netdbtype.U,v $
?RCS:
?MAKE:netdb_host_type netdb_hlen_type netdb_name_type netdb_net_type: \
Protochk Oldconfig Myread cat \
d_gethbyaddr d_gethbyname d_getnbyaddr \
i_niin i_netdb i_unistd d_socket sizetype extern_C
?MAKE: -pick add $@ %<
?S:netdb_host_type:
?S: This variable holds the type used for the 1st argument to
?S: gethostbyaddr(). Usually, this is char * or void *, possibly
?S: with or without a const prefix.
?S: This is only useful if you have gethostbyaddr(), naturally.
?S:
?S:netdb_hlen_type:
?S: This variable holds the type used for the 2nd argument to
?S: gethostbyaddr(). Usually,
?S: this is int or size_t or unsigned.
?S: This is only useful if you have gethostbyaddr(), naturally.
?S:
?S:netdb_name_type:
?S: This variable holds the type used for the argument to
?S: gethostbyname(). Usually, this is char * or const char *.
?S: This is only useful if you have gethostbyname(), naturally.
?S:
?S:netdb_net_type:
?S: This variable holds the type used for the 1st argument to
```

?S: getnetbyaddr(). Usually, this is int or long.
 ?S: This is only useful if you have getnetbyaddr(), naturally.
 ?S:.
 ?C:Netdb_host_t:
 ?C: This symbol holds the type used for the 1st argument
 ?C: to gethostbyaddr().
 ?C:.
 ?C:Netdb_hlen_t:
 ?C: This symbol holds the type used for the 2nd argument
 ?C: to gethostbyaddr().
 ?C:.
 ?C:Netdb_name_t:
 ?C: This symbol holds the type used for the argument to
 ?C: gethostbyname().
 ?C:.
 ?C:Netdb_net_t:
 ?C: This symbol holds the type used for the 1st argument to
 ?C: getnetbyaddr().
 ?C:.
 ?H:#define Netdb_host_t \$netdb_host_type /**/
 ?H:#define Netdb_hlen_t \$netdb_hlen_type
 /**/
 ?H:#define Netdb_name_t \$netdb_name_type /**/
 ?H:#define Netdb_net_t \$netdb_net_type /**/
 ?H:.
 ?T:xxx yyy try hdrs
 @if netdb_host_type || Netdb_host_t || netdb_hlen_type || Netdb_hlen_t
 : check for type of arguments to gethostbyaddr.
 if test "X\$netdb_host_type" = X -o "X\$netdb_hlen_type" = X; then
 case "\$d_gethbyaddr" in
 \$define)
 \$cat <<EOM

Checking to see what type of arguments are accepted by gethostbyaddr().

EOM

```
hdrs="$define sys/types.h
$d_socket sys/socket.h
$i_niin netinet/in.h
$i_netdb netdb.h
$i_unistd unistd.h"
: The first arg can 'char *' or 'void *'
: The second arg is some of integral type
for xxx in in_addr_t 'const void *' 'const char *' 'void *' 'char *'; do
for yyy in size_t long int; do
case "$netdb_host_type" in
") try="$xextern_C struct hostent *gethostbyaddr($xxx, $yyy, int);"
if ./protochk "$try" $hdrs; then
echo "Your system accepts $xxx for the first arg."
```

```

    echo "...and $yyy for the second arg."
    netdb_host_type="$xxx"
    netdb_hlen_type="$yyy"
fi
;;
esac
done
done
:
In case none of those worked, prompt the user.
case "$netdb_host_type" in
") rp='What is the type for the 1st argument to gethostbyaddr?'
dflt='char *'
./myread
netdb_host_type=$ans
rp='What is the type for the 2nd argument to gethostbyaddr?'
dflt="$sizetype"
./myread
netdb_hlen_type=$ans
;;
esac
;;
*) : no gethostbyaddr, so pick harmless defaults
netdb_host_type='char *'
netdb_hlen_type="$sizetype"
;;
esac
# Remove the "const" if needed. -- but then we'll have a
# prototype clash!
# netdb_host_type=`echo "$netdb_host_type" | sed 's/^const //'`
fi
@end

@if netdb_name_type || Netdb_name_t
: check for type of argument to gethostbyname.
if test "X$netdb_name_type" = X ; then
case "$d_gethbyname" in
$define)
$cat <<EOM

Checking to see what type of argument is accepted by gethostbyname().
EOM
hdrs="$define sys/types.h
$d_socket sys/socket.h
$i_niin
netinet/in.h
$i_netdb netdb.h
$i_unistd unistd.h"

```

```

for xxx in "const char *" "char *"; do
case "$netdb_name_type" in
") try="$xtern_C struct hostent *gethostbyname($xxx);"
if ./protochk "$stry" $hdrs; then
echo "Your system accepts $xxx."
netdb_name_type="$xxx"
fi
;;
esac
done
: In case none of those worked, prompt the user.
case "$netdb_name_type" in
") rp='What is the type for the 1st argument to gethostbyname?'
dflt='char *'
./myread
netdb_name_type=$ans
;;
esac
*) : no gethostbyname, so pick harmless default
netdb_name_type='char *'
;;
esac
fi
@end

```

```

@if netdb_net_type || Netdb_net_t
: check for type of 1st argument to getnetbyaddr.
if test "X$netdb_net_type" = X ; then
case "$d_getnbyaddr" in
$define)
$cat <<EOM

```

Checking to see what type of 1st argument is accepted by getnetbyaddr().

EOM

```

hdrs="$define sys/types.h
$d_socket sys/socket.h
$i_niin netinet/in.h
$i_netdb netdb.h
$i_unistd
unistd.h"
for xxx in in_addr_t "unsigned long" long "unsigned int" int; do
case "$netdb_net_type" in
") try="$xtern_C struct netent *getnetbyaddr($xxx, int);"
if ./protochk "$stry" $hdrs; then
echo "Your system accepts $xxx."
netdb_net_type="$xxx"
fi

```

```

;;
esac
done
: In case none of those worked, prompt the user.
case "$netdb_net_type" in
") rp='What is the type for the 1st argument to getnetbyaddr?'
dflt='long'
./myread
netdb_net_type=$ans
;;
esac
;;
*) : no getnetbyaddr, so pick harmless default
netdb_net_type='long'
;;
esac
fi
@end

```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/protos/netdbtype.U
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: localtime.U,v 1.1 1999/07/08 18:32:57 doughera Exp doughera \$

?RCS:

?RCS: Copyright (c) 1999, Jarkko Hietaniemi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 3.0.

?RCS:

?RCS:

?MAKE:uselocallib locallib locallibexp installlocallib installlocallibexp: \

cat Getfile Oldconfig Prefixit test afs sitelib

?MAKE: -pick add \$@ %<

?Y:TOP

?S:uselocallib:

?S: This variable tells whether the USELOCALLIB is defined.

?S:.

?S:locallib:

?S: This variable contains the eventual value of the LOCALLIB symbol,

?S: which is the name of the private library for this package. It may

?S: have a ~ on the front. It is up to the makefile to eventually create

?S: this

directory while performing installation (with ~ substitution).

?S: This differs from \$sitelib in that \$sitelib is often

?S: a shared network directory while \$locallib is

?S: at a local disk, because of policy/administrative issues

?S: like for example caching (performance), licensing, or security.

?S:.

?S:locallibexp:

?S: This variable is the ~name expanded version of locallib, so that you

?S: may use it directly in Makefiles or shell scripts.

?S:.

?S:installlocallib:

?S: This variable is really the same as locallibexp but may differ on

?S: those systems using AFS. For extra portability, only this variable

?S: should be used in makefiles.

?S:.

?S:installlocallibexp:

?S: This variable is the ~name expanded version of installlocallib,

?S: so that you may use it directly in Makefiles or shell scripts.

?S:.

?C:USELOCALLIB:

?C: This symbol, if defined, tells that the directories

?C: LOCALLIB, LOCALLIB_EXP, LOCALARCH, and LOCALARCH_EXP,

?C: are used in this installation.

?C:.

?C:LOCALLIB:

?C: This

symbol contains the name of the private library for this package.

?C: The library is private in the sense that it needn't be in anyone's

?C: execution path, but it should be accessible by the world. The program

?C: should be prepared to do ~ expansion.

?C: The standard distribution will put nothing in this directory.

?C: Local administration may place extensions and modules in

?C: this directory.

?C: This differs from SITELIB in that SITELIB is often

?C: a shared network directory while LOCALLIB is

?C: at a local disk, because of policy/administrative issues

?C: like for example caching (performance), licensing, or security.

?C:.

?C:LOCALLIB_EXP:

?C: This symbol contains the ~name expanded version of LOCALLIB, to be used

?C: in programs that are not prepared to deal with ~ expansion at run-time.

?C:.

?H:#\$uselocallib USELOCALLIB /**/

?H:#define LOCALLIB "\$locallib" /**/

?H:#define LOCALLIB_EXP "\$locallibexp" /**/

?H:.

: determine where local libraries go.

case

```

"$locallib" in
") dflt=none ;;
*) dflt=$locallib ;;
esac
$cat <<EOM

```

For various local software administration reasons and especially if \$sitelib happens to be a shared network resource, you may want to have a directory for extensions and modules that resides on a possibly local disk. If this scenario doesn't sound applicable, accept the default 'none'.

```

EOM
fn=nd~+
rp='Pathname for such local library files?'
./getfile
if $test "X$sans" = X; then
  uselocallib="$undef"
  locallib=""
  locallibexp=""
  installlocallib=""
  installlocallibexp=""
else
  uselocallib="$define"
  if $test "X$locallibexp" != "X$sansexp"; then
    installlocallib="
  fi
  locallib="$sans"
  locallibexp="$sansexp"
  if $afs; then
    $cat <<EOM

```

Since you are running AFS, I need to distinguish the directory in which locally installed files reside from the directory in which they are installed (and from which they are presumably copied to the former directory by occult means).

```

EOM
  case "$installlocallib" in
    ") dflt=`echo
$locallibexp | sed 's#^/afs/#/afs/.#^';
    *) dflt="$installlocallib";;
  esac
  fn=de~
  rp='Where will the locally installed files be installed?'
  ./getfile
  installlocallib="$sans"
else

```

```
installlocallibexp="$locallibexp"
```

```
fi
```

```
fi
```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/installdirs/locallib.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: d_dlerror.U 1 2006-08-24 12:32:52Z rmanfredi $
```

```
?RCS:
```

```
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
```

```
?RCS:
```

```
?RCS: You may redistribute only under the terms of the Artistic Licence,
```

```
?RCS: as specified in the README file that comes with the distribution.
```

```
?RCS: You may reuse parts of this distribution only within the terms of
```

```
?RCS: that same Artistic Licence; a copy of which may be found at the root
```

```
?RCS: of the source tree for dist 4.0.
```

```
?RCS:
```

```
?RCS: Original Author: Andy Dougherty <doughera@lafcol.lafayette.edu>
```

```
?RCS:
```

```
?RCS: $Log: d_dlerror.U,v $
```

```
?RCS: Revision 3.0.1.2 1995/07/25 13:52:49 ram
```

```
?RCS: patch56: force compile-link test since symbol might lie in crt0.o (ADO)
```

```
?RCS:
```

```
?RCS: Revision 3.0.1.1 1994/10/29 16:11:23 ram
```

```
?RCS: patch36: created by ADO
```

```
?RCS:
```

```
?MAKE:d_dlerror: Inlibc runnm
```

```
?MAKE: -pick add $@ %<
```

```
?S:d_dlerror:
```

```
?S: This variable conditionally defines the HAS_DLERROR symbol, which
```

```
?S: indicates
```

```
to the C program that the dlerror() routine is available.
```

```
?S:.
```

```
?C:HAS_DLERROR :
```

```
?C: This symbol, if defined, indicates that the dlerror routine is
```

```
?C: available to return a string describing the last error that
```

```
?C: occurred from a call to dlopen(), dlclose() or dlsym().
```

```
?C:.
```

```
?H:#$d_dlerror HAS_DLERROR /**/
```

```
?H:.
```

```
?T: xxx_runnm
```

```
?LINT:set d_dlerror
```

```
?X: We don't permanently change runnm, but we do temporarily.
```

```
?LINT: change runnm
```

```
: see if dlerror exists
```

```
?X: On NetBSD and FreeBSD, dlerror might be available, but it is in
```

```
?X: /usr/lib/crt0.o, not in any of the libraries. Therefore, do not
?X: use the nm extraction, but use a real compile and link test instead.
xxx_runnm="$runnm"
runnm=false
set dlderror d_dlderror
eval $inlibc
runnm="$xxx_runnm"
```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/d_dlderror.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: d_symlink.U 1 2006-08-24 12:32:52Z rmanfredi $
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: $Log: d_symlink.U,v $
?RCS: Revision 3.0 1993/08/18 12:07:41 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:d_symlink: Inlibc
?MAKE: -pick add $@ %<
?S:d_symlink:
?S: This variable conditionally defines the HAS_SYMLINK symbol, which
?S: indicates to the C program that the symlink() routine is available
?S: to create symbolic links.
?S:.
?C:HAS_SYMLINK (SYMLINK):
?C: This symbol, if defined, indicates that the symlink routine is available
?C: to
create symbolic links.
?C:.
?H:#$d_symlink HAS_SYMLINK /**/
?H:.
?LINT:set d_symlink
: see if symlink exists
set symlink d_symlink
eval $inlibc
```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
```

debian-perl-5.26.1/dist/U/d_symlink.U

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: d_crypt.U 1 2006-08-24 12:32:52Z rmanfredi $
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: $Log: d_crypt.U,v $
?RCS: Revision 3.0.1.1 1997/02/28 15:31:47 ram
?RCS: patch61: replaced .a with $_a all over the place
?RCS:
?RCS: Revision 3.0 1993/08/18 12:05:52 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:d_crypt cryptlib: Loc test xlibpth libpth Csym Setvar _a Inlibc
?MAKE: -pick add $@ %<
?S:d_crypt:
?S: This variable conditionally defines the CRYPT symbol, which
?S: indicates to the C program that the crypt() routine is available
?S: to
encrypt passwords and the like.
?S:.
?S:cryptlib:
?S: This variable holds -lcrypt or the path to a libcrypt.a archive if
?S: the crypt() function is not defined in the standard C library. It is
?S: up to the Makefile to use this.
?S:.
?C:HAS_CRYPT (CRYPT):
?C: This symbol, if defined, indicates that the crypt routine is available
?C: to encrypt passwords and the like.
?C:.
?H:#$d_crypt HAS_CRYPT /**/
?H:.
?LINT:set d_crypt
?T:val
: see if crypt exists
echo " "
set crypt d_crypt
eval $inlibc
case "$d_crypt" in
$define) cryptlib=" ;;
*) if set crypt val -f d_crypt; eval $csym; $val; then
```

```

echo 'crypt() found.' >&4
val="$define"
cryptlib=""
else
cryptlib=`./loc Slibcrypt$_a "" $xlibpth`
if $test -z "$cryptlib"; then
  cryptlib=`./loc Mlibcrypt$_a "" $xlibpth`
else
  cryptlib=-lcrypt
fi
if $test -z "$cryptlib"; then
  cryptlib=`./loc Llibcrypt$_a "" $xlibpth`
else
  cryptlib=-lcrypt
fi
if $test -z "$cryptlib"; then
  cryptlib=`./loc libcrypt$_a ""
$libpth`
else
  cryptlib=-lcrypt
fi
if $test -z "$cryptlib"; then
  echo 'crypt() NOT found.' >&4
  val="$undef"
else
  val="$define"
fi
fi
set d_crypt
eval $setvar
;;
esac

```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/d_crypt.U
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: errnolist.U,v 3.0.1.2 1997/02/28 15:48:01 ram Exp \$

?RCS:

?RCS: Copyright (c) 1991-1993, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 3.0.

?RCS:

?RCS: \$Log: errnolist.U,v \$

?RCS: Revision 3.0.1.2 1997/02/28 15:48:01 ram

?RCS: patch61: replaced .a with \$_a all over the place

?RCS: patch61: likewise for .o replaced by \$_o

?RCS:

?RCS: Revision 3.0.1.1 1994/01/24 14:10:54 ram

?RCS: patch16: created

?RCS:

?MAKE:errnolist errnolist_SH errnolist_a errnolist_c errnolist_o: cat \
 Compile +d_sysernlst_a_o

?MAKE: -pick add \$@ %<

?S:errnolist:

?S: This variable holds the base name of a file containing the
 ?S: definition
 of the sys_errnolist array, if the C library
 ?S: doesn't provide it already. Otherwise, its value is empty.
 ?S: The following lines should be included in your Makefile.SH:
 ?S:
 ?S: case "\$serrnolist" in
 ?S: ") ;;
 ?S: *)
 ?S: \$spitshell >>Makefile <<!GROK!THIS!
 ?S: \$serrnolist_c: \$serrnolist_SH \$serrnolist_a
 ?S: sh ./serrnolist_SH
 ?S:
 ?S: !GROK!THIS!
 ?S: ;;
 ?S: esac
 ?S:
 ?S: You may define the 'errnolist' variable in your Myinit.U if you
 ?S: wish to override its default value "errnolist".
 ?S:.
 ?S:errnolist_SH:
 ?S: This is the name of a file which will generate errnolistic.
 ?S:.
 ?S:errnolist_a:
 ?S: This is the name of the awk script called by errnolist_SH.
 ?S:.
 ?S:errnolist_c:
 ?S: This is the name of a generated C file which provides the
 ?S: definition of the sys_errnolist array.
 ?S:.
 ?S:errnolist_o:
 ?S: This is the name of the object file which provides the
 ?S: definition of the sys_errnolist array, if the C library
 ?S: doesn't provide it already. Otherwise, its value is
 empty.
 ?S:.

```

?INIT:errnolist=errnolist
: check for sys_errnolist
@if d_sysernlst || HAS_SYS_ERRNOLIST
case "$d_sysernlst" in
"$define")
    errnolist="
    errnolist_SH="
    errnolist_a="
    errnolist_c="
    errnolist_o="
;;
*)
echo " "
echo "I'll make sure your Makefile provides sys_errnolist in $errnolist.c"
    errnolist_SH=$errnolist.SH
    errnolist_a=$errnolist$_a
    errnolist_c=$errnolist.c
    errnolist_o=$errnolist$_o
;;
esac
@else
echo " "
$cat <<EOM
Checking to see if your C library provides us with sys_errnolist[...]
EOM
$cat >errnolist.c <<'EOCP'
extern char *sys_errnolist[];
int main() {
    char *p0 = sys_errnolist[0];
    char *p1 = sys_errnolist[1];

    return (p0 == p1); /* Make sure they're not optimized away */
}
EOCP
set errnolist
if eval $compile; then
    echo "It does."
    errnolist="
    errnolist_SH="
    errnolist_a="
    errnolist_c="
    errnolist_o="
else
echo "I'll make sure your Makefile provides sys_errnolist in $errnolist.c"
    errnolist_SH=$errnolist.SH
    errnolist_a=$errnolist$_a
    errnolist_c=$errnolist.c
    errnolist_o=$errnolist$_o

```

fi

@end

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/compline/errnolist.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: i_memory.U 1 2006-08-24 12:32:52Z rmanfredi \$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic Licence,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic Licence; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: i_memory.U,v \$

?RCS: Revision 3.0.1.3 1994/06/20 07:01:55 ram

?RCS: patch30: cosmetic changes

?RCS:

?RCS: Revision 3.0.1.2 1994/05/13 15:23:56 ram

?RCS: patch27: modified to avoid spurious Whoa warnings (ADO)

?RCS:

?RCS: Revision 3.0.1.1 1994/05/06 15:02:25 ram

?RCS: patch23: avoid conflicts with <string.h>

?RCS:

?RCS: Revision 3.0 1993/08/18 12:08:22 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?MAKE:i_memory: Inhdr strings cppstdin

cppflags cppminus contains rm Setvar

?MAKE: -pick add \$@ %<

?S:i_memory:

?S: This variable conditionally defines the I_MEMORY symbol, and indicates

?S: whether a C program should include <memory.h>.

?S:.

?C:I_MEMORY:

?C: This symbol, if defined, indicates to the C program that it should

?C: include <memory.h>.

?C:.

?H:#\$i_memory I_MEMORY /**/

?H:.

?LINT:set i_memory

?X:

?X: Unfortunately, the definitions of memory functions sometimes

?X: conflict with those in <string.h>. We'll assume that if

?X: <string.h> contains memcpy, then we don't need memory.h

?X:

: see if memory.h is available.

val="

set memory.h val

eval \$inhdr

: See if it conflicts with string.h

case "\$sval" in

\$define)

case "\$strings" in

") ;;

*)

\$cppstdin \$cppflags \$cppminus < \$strings > mem.h

if \$contains 'memcpy' mem.h >/dev/null 2>&1; then

echo " "

echo "We won't be including <memory.h>."

val="\$undef"

fi

\$rm -f mem.h

::

esac

esac

set i_memory

eval \$setvar

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/i_memory.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1999 Jarkko Hietaniemi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 3.0.

?RCS:

?MAKE:siteman1 siteman1exp installsiteman1: test Getfile Setprefixvar \

prefix siteprefix man1dir sed

?MAKE: -pick add \$@ %<

?Y:TOP

?D:siteman1="

?S:siteman1:

?S: This variable contains the name of the directory in which site-specific

?S: manual source pages are to be put. It is the responsibility of the
?S: Makefile.SH to get the value of this into the proper command.
?S: You must be prepared to do the ~name expansion yourself.
?S: The standard distribution will put nothing in this directory.
?S: After perl has been installed,
users may install their own local
?S: man1 pages in this directory with
?S: MakeMaker Makefile.PL
?S: or equivalent. See INSTALL for details.
?S:.
?D:siteman1exp="
?S:siteman1exp:
?S: This variable is the same as the siteman1 variable, but is filename
?S: expanded at configuration time, for convenient use in makefiles.
?S:.
?D:installsiteman1="
?S:installsiteman1:
?S: This variable is really the same as siteman1exp, unless you are using
?S: AFS in which case it points to the read/write location whereas
?S: man1direxp only points to the read-only access location. For extra
?S: portability, you should only use this variable within your makefiles.
?S:.
?LINT:change prefixvar
?LINT:set installsiteman1
?LINT:set siteman1exp
: determine where add-on manual pages go
case "\$siteman1" in
") dflt=`echo "\$man1dir" | \$sed "s#^\$prefix#\$siteprefix#"` ;;
*) dflt=\$siteman1 ;;
esac
case "\$dflt" in
"| ") dflt=none ;;
esac
fn=dn+~
rp='Pathname where the site-specific manual pages should
be installed?'
./getfile
prefixvar=siteman1
./setprefixvar
: Use ' ' for none so value is preserved next time through Configure
\$test X"\$siteman1" = "X" && siteman1=' '

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/installdirs/siteman1.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

```

?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: $Log: i_sysmman.U,v $
?RCS: Revision 3.0.1.1 1994/01/24 14:11:20 ram
?RCS: patch16: created
?RCS:
?X:
?X: Look wether <sys/mman.h> needs to be included.
?X:
?MAKE:i_sysmman: Inhdr
?MAKE: -pick add $@ %<
?S:i_sysmman:
?S: This variable conditionally defines the I_SYS_MMAN symbol,
?S: and indicates whether a C program should include <sys/mman.h>.
?S:.
?C:I_SYS_MMAN:
?C: This symbol, if defined, indicates to the C program that it should
?C: include <sys/mman.h>.
?C:.
?H:#$i_sysmman I_SYS_MMAN /**/
?H:.
?LINT:set
i_sysmman
: see if sys/mman.h has to be included
set sys/mman.h i_sysmman
eval $inhdr

```

Found in path(s):

```

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/i_sysmman.U

```

No license file was found, but licenses were detected in source scan.

```

?RCS: $Id: Extractall.U 1 2006-08-24 12:32:52Z rmanfredi $
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.

```

```

?RCS:
?RCS: $Log: Extractall.U,v $
?RCS: Revision 3.0.1.1 1997/02/28 15:00:43 ram
?RCS: patch61: created
?RCS:
?X:
?X: If extraction has been requested, load the configuration file, perform
?X: the extraction and exit.
?X:
?X: This unit was originally a part of Options.U. It had to be removed from
?X: it to prevent a dependency cycle: Extract -> src -> Options -> Extract
?X: The Begin.U unit now requires us before beginning to do anything
?X: interesting, to ensure
proper semantics. -- RAM, 15/03/96
?X:
?MAKE:Extractall: Extract Options
?MAKE: -pick wipe $@ %<
: extract files and exit if asked to do so
case "$extractsh" in
true)
?X: Undo the forced silent=true when -S was supplied, by probing realsilent
?X: which was set iff -s was also given. See Options.U for details.
case "$realsilent" in
true) ;;
*) exec 1>&4;;
esac
case "$config_sh" in
") config_sh='config.sh';;
esac
echo " "
echo "Fetching answers from $config_sh..."
cd ..
. $config_sh
?X: extract has to be run from the top directory, not within UU.
. UU/optdef.sh
echo " "
?X: extract has to be run from the top directory, not within UU.
. UU/extract
rm -rf UU
echo "Extraction done."
exit 0
;;
esac

```

Found in path(s):

```

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/modified/Extractall.U

```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: Original Author: Andy Dougherty <doughera@lafcol.lafayette.edu>
?RCS:
?RCS: \$Log: i_db.U,v \$
?RCS: Revision 3.0.1.3 1995/07/25 14:10:22 ram
?RCS: patch56: conditionally use const in test programs (ADO)
?RCS:
?RCS: Revision 3.0.1.2 1995/05/12 12:14:42 ram
?RCS: patch54: extended for more intimate DB probing (ADO)
?RCS:
?RCS: Revision 3.0.1.1 1994/08/29 16:21:50 ram
?RCS: patch32: created by ADO
?RCS:
?MAKE:i_db db_hashtype db_prefixtype: Inhdr +cc +ccflags rm_try contains cat \
d_const
?MAKE: -pick
add \$@ %<
?S:i_db:
?S: This variable conditionally defines the I_DB symbol, and indicates
?S: whether a C program may include Berkeley's DB include file <db.h>.
?S:.
?S:db_hashtype:
?S: This variable contains the type of the hash structure element
?S: in the <db.h> header file. In older versions of DB, it was
?S: int, while in newer ones it is u_int32_t.
?S:.
?S:db_prefixtype:
?S: This variable contains the type of the prefix structure element
?S: in the <db.h> header file. In older versions of DB, it was
?S: int, while in newer ones it is size_t.
?S:.
?C:I_DB:
?C: This symbol, if defined, indicates to the C program that it should
?C: include Berkeley's DB include file <db.h>.
?C:.
?C:DB_Prefix_t:
?C: This symbol contains the type of the prefix structure element

?C: in the <db.h> header file. In older versions of DB, it was

?C: int, while in newer ones it is u_int32_t.

?C:.

?C:DB_Hash_t:

?C: This symbol contains the type of the prefix structure element

?C: in the <db.h> header

file. In older versions of DB, it was

?C: int, while in newer ones it is size_t.

?C:.

?H:#\$i_db I_DB /**/

?H:#define DB_Hash_t \$db_hashtype /**/

?H:#define DB_Prefix_t \$db_prefixtype /**/

?H:.

?LINT:set i_db

: see if this is a db.h system

set db.h i_db

eval \$inhdr

@if DB_Hash_t

case "\$i_db" in

define)

: Check the return type needed for hash

echo " "

echo "Checking return type needed for hash for Berkeley DB ..." >&4

\$cat >try.c <<EOCP

#\$d_const HASCONST

#ifndef HASCONST

#define const

#endif

#include <sys/types.h>

#include <db.h>

u_int32_t hash_cb (ptr, size)

const void *ptr;

size_t size;

{

}

HASHINFO info;

int main()

{

info.hash = hash_cb;

}

EOCP

if \$cc \$cflags -c try.c >try.out 2>&1 ; then

if \$contains warning try.out >>/dev/null 2>&1 ; then

db_hashtype='int'

else

db_hashtype='u_int32_t'

fi

```

else
  echo "I can't seem to compile the test program." >&4
  db_hashtype=int
fi
$rm_try
echo "Your version of Berkeley DB uses $db_hashtype for hash."
;;
*) db_hashtype=int
;;
esac

@end
@if
  DB_Prefix_t
  case "$i_db" in
  define)
    : Check the return type needed for prefix
    echo " "
    echo "Checking return type needed for prefix for Berkeley DB ..." >&4
    cat >try.c <<EOCP
#$d_const HASCONST
#ifndef HASCONST
#define const
#endif
#include <sys/types.h>
#include <db.h>
size_t prefix_cb (key1, key2)
const DBT *key1;
const DBT *key2;
{
}
BTREEINFO info;
int main()
{
  info.prefix = prefix_cb;
}
EOCP
if $cc $ccflags -c try.c >try.out 2>&1 ; then
  if $contains warning try.out >>/dev/null 2>&1 ; then
    db_prefixtype='int'
  else
    db_prefixtype='size_t'
  fi
else
  echo "I can't seem to compile the test program." >&4
  db_prefixtype='int'
fi
$rm_try

```

```
echo "Your version of Berkeley DB uses $db_prefixtype for prefix."  
;;  
*) db_prefixtype='int'  
;;  
esac
```

@end

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/i_db.U
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: archlib.U,v 3.1 1999/07/08 18:32:29 doughera Exp doughera \$

?RCS:

?RCS: Copyright (c) 1991-1993, Raphael Manfredi

?RCS:

?RCS: This file is included with or a derivative work of a file included

?RCS: with the metaconfig program of Raphael Manfredi's "dist" distribution.

?RCS: In accordance with clause 7 of dist's modified Artistic License:

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?RCS: Original Author: Andy Dougherty <doughera@lafcol.lafayette.edu>

?RCS:

?RCS: \$Log: archlib.U,v \$

?RCS: Revision 3.1 1999/07/08 18:32:29 doughera

?RCS: Updated for perl5.005_5x

?RCS:

?RCS:

?RCS: Revision 3.0.1.4 1995/09/25 09:15:18 ram

?RCS: patch59: unit is now forced to the top of Configure, if possible

?RCS:

?RCS: Revision 3.0.1.3 1995/02/15 14:14:14 ram

?RCS: patch51: architecture name is now

computed by a separate unit

?RCS:

?RCS: Revision 3.0.1.2 1995/01/30 14:32:22 ram

?RCS: patch49: archname is now systematically recomputed

?RCS: patch49: can now handle installation prefix changes (from WED)

?RCS:

?RCS: Revision 3.0.1.1 1994/10/29 16:02:36 ram

?RCS: patch36: created by ADO

?RCS:

?MAKE:d_archlib archlib archlibexp installarchlib: \
cat Getfile Setprefixvar Loc Oldconfig archname spackage \
privlib sed test Prefixit Prefixup binexp

?MAKE: -pick add \$@ %<

?Y:TOP

?S:d_archlib:

?S: This variable conditionally defines ARCHLIB to hold the pathname
of architecture-dependent library files for \$package. If
\$archlib is the same as \$privlib, then this is set to undef.

?S:.

?D:archlib="

?S:archlib:

?S: This variable holds the name of the directory in which the user wants
to put architecture-dependent public library files for \$package.
It is most often a local directory such as /usr/local/lib.
Programs using this variable must be prepared to deal
with
filename expansion.

?S:.

?D:archlibexp="

?S:archlibexp:

?S: This variable is the same as the archlib variable, but is
filename expanded at configuration time, for convenient use.

?S:.

?D:installarchlib="

?S:installarchlib:

?S: This variable is really the same as archlibexp but may differ on
those systems using AFS. For extra portability, only this variable
should be used in makefiles.

?S:.

?C:ARCHLIB:

?C: This variable, if defined, holds the name of the directory in
which the user wants to put architecture-dependent public
library files for \$package. It is most often a local directory
such as /usr/local/lib. Programs using this variable must be
prepared to deal with filename expansion. If ARCHLIB is the
same as PRIVLIB, it is not defined, since presumably the
program already searches PRIVLIB.

?C:.

?C:ARCHLIB_EXP:

?C: This symbol contains the ~name expanded version of ARCHLIB, to be used
in programs that are not prepared to deal with ~ expansion
at run-time.

?C:.

?H:#\$d_archlib ARCHLIB "\$archlib" /**/
?H:#\$d_archlib ARCHLIB_EXP "\$archlibexp" /**/
?H:.

?T: tdfit

?LINT:change prefixvar

?LINT:set archlib

?LINT:set archlibexp

```

?LINT:set installarchlib
: determine where public architecture dependent libraries go
set archlib archlib
eval $prefixit
: privlib default is /usr/local/lib/$package/$version
: archlib default is /usr/local/lib/$package/$version/$archname
: privlib may have an optional trailing /share.
tdflt=`echo $privlib | $sed 's,/share$,,'`
tdflt=${tdflt/$archname}
case "$archlib" in
") dflt=${tdflt}
;;
*) dflt="$archlib"
;;
esac
$cat <<EOM

```

\$package contains architecture-dependent library files. If you are sharing libraries in a heterogeneous environment, you might store these files in a separate location. Otherwise, you can just include them with the rest of the public library files.

```

EOM
?X: Force dependency on bin.U
fn=$binexp
fn=d+~
rp='Where do you want to put the public architecture-dependent libraries?'
.
./getfile
prefixvar=archlib
./setprefixvar
if $test X"$archlib" = X"$privlib"; then
d_archlib="$undef"
else
d_archlib="$define"
fi

```

Found in path(s):

```

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/installdirs/archlib.U

```

No license file was found, but licenses were detected in source scan.

```

?RCS: $Id$
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.

```

?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: \$Log: d_safemcpy.U,v \$
?RCS: Revision 3.0.1.5 1997/02/28 15:41:12 ram
?RCS: patch61: improved overlapping copy check
?RCS: patch61: comfort them if they have memmove
?RCS: patch61: added ?F: metalint hint
?RCS:
?RCS: Revision 3.0.1.4 1995/07/25 13:58:46 ram
?RCS: patch56: re-arranged compile line to include ldflags before objects
?RCS:
?RCS: Revision 3.0.1.3 1995/03/21 08:47:26 ram
?RCS: patch52: swapped two first arguments of memcpy() calls
?RCS:
?RCS: Revision 3.0.1.2 1994/10/29 16:15:10
ram
?RCS: patch36: added 'ldflags' to the test compile line (ADO)
?RCS:
?RCS: Revision 3.0.1.1 1994/05/06 14:53:12 ram
?RCS: patch23: ensure string is not optimized in read-only memory (ADO)
?RCS:
?RCS: Revision 3.0 1993/08/18 12:06:58 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:d_safemcpy: cat d_memcpy +cc +optimize +ccflags +libs +ldflags rm \
d_memmove i_memory i_stdlib i_string i_unistd Oldconfig Setvar
?MAKE: -pick add \$@ %<
?S:d_safemcpy:
?S: This variable conditionally defines the HAS_SAFE_MEMCPY symbol if
?S: the memcpy() routine can do overlapping copies.
?S:.
?C:HAS_SAFE_MEMCPY (SAFE_MEMCPY):
?C: This symbol, if defined, indicates that the memcpy routine is available
?C: to copy potentially overlapping memory blocks. Otherwise you should
?C: probably use memmove() or memcpy(). If neither is defined, roll your
?C: own version.
?C:.
?H:#\$d_safemcpy HAS_SAFE_MEMCPY /**/
?H:.
?F:!safemcpy
?LINT: set d_safemcpy
: can memcpy handle overlapping blocks?
?X:
assume the worst
val="\$undef"
case "\$d_memcpy" in

```

"$define")
echo " "
echo "Checking to see if your memcpy() can do overlapping copies..." >&4
$cat >foo.c <<EOCP
#$i_memory I_MEMORY
#$i_stdlib I_STDLIB
#$i_string I_STRING
#$i_unistd I_UNISTD
EOCP
$cat >>foo.c <<'EOCP'
#include <stdio.h>
#ifdef I_MEMORY
# include <memory.h>
#endif
#ifdef I_STDLIB
# include <stdlib.h>
#endif
#ifdef I_STRING
# include <string.h>
#else
# include <strings.h>
#endif
#ifdef I_UNISTD
# include <unistd.h> /* Needed for NetBSD */
#endif
int main()
{
char buf[128], abc[128];
char *b;
int len;
int off;
int align;

/* Copy "abcde..." string to char abc[] so that gcc doesn't
try to store the string in read-only memory. */
memcpy(abc, "abcdefghijklmnopqrstuvwxy0123456789", 36);

for (align = 7; align >= 0; align--) {
for (len = 36; len; len--) {
b = buf+align;
memcpy(b, abc, len);
for (off = 1; off <= len; off++) {
memcpy(b+off, b, len);
memcpy(b, b+off, len);
if (memcmp(b, abc, len))
exit(1);
}
}
}

```

```

}
exit(0);
}
EOCP
if
$cc $optimize $ccflags $ldflags \
    -o safemcpy foo.c $libs >/dev/null 2>&1; then
if ./safemcpy 2>/dev/null; then
    echo "Yes, it can."
    val="$define"
else
    echo "It can't, sorry."
    case "$d_memmove" in
"$define") echo "But that's Ok since you have memmove()." ;;
    esac
fi
else
    echo "(I can't compile the test program, so we'll assume not...)"
    case "$d_memmove" in
"$define") echo "But that's Ok since you have memmove()." ;;
    esac
fi
;;
esac
$rm -f foo.* safemcpy core
set d_safemcpy
eval $setvar

```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/d_safemcpy.U
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: i_execinfo.U 34 2010-11-27 11:55:39Z rmanfredi \$

?RCS:

?RCS: Copyright (c) 2011, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?MAKE:i_execinfo: Inhdr

?MAKE: -pick add \$@ %<

?S:i_execinfo:

?S: This variable conditionally defines the I_EXECINFO symbol, and indicates

?S: whether a C program may include <execinfo.h>, for backtrace() support.

?S:
?C:I_EXECINFO:
?C: This symbol, if defined, indicates to the C program that it should
?C: include <execinfo.h> for backtrace() support.
?C:
?H:#\$i_execinfo I_EXECINFO /**/
?H:
?LINT:set i_execinfo
: see if this is an execinfo.h system
set execinfo.h i_execinfo
eval
\$inhdr

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/modified/i_execinfo.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: \$Log: Cppsym.U,v \$
?RCS: Revision 3.0.1.5 1995/05/12 11:59:11 ram
?RCS: patch54: split awk command onto two lines for older awks (ADO)
?RCS:
?RCS: Revision 3.0.1.4 1995/01/11 14:55:57 ram
?RCS: patch45: new cc vs. cpp symbol checking suggested by JHI
?RCS: patch45: added more cpp symbols (JHI)
?RCS:
?RCS: Revision 3.0.1.3 1994/10/29 15:51:32 ram
?RCS: patch36: added ?F: line for metalint file checking
?RCS: patch36: new symbols ardent and titan (ADO)
?RCS:
?RCS: Revision 3.0.1.2 1994/06/20
06:53:32 ram
?RCS: patch30: extended cpp symbol lookup list (JHI)
?RCS: patch30: renamed attrlist symbol into al for brevity
?RCS:
?RCS: Revision 3.0.1.1 1993/12/15 08:14:14 ram
?RCS: patch15: added new cpp symbols __bsdi__ and BSD_NET2
?RCS:

?RCS: Revision 3.0 1993/08/18 12:04:50 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?X:

?X: This unit produces a shell script called Cppsym, which can be used to

?X: determine whether any in a list of symbols is defined by the C compilation

?X: chain (C preprocessor symbols plus C compiler native ones).

?X: It can determine the status of any symbol, though the symbols in \$al

?X: are more easily determined. If you want to add to \$al you can do

?X: it in Myinit.U.

?X:

?MAKE:Cppsym ccsymbols cppsymbols cppccsymbols: run \
eunicefix Guess awk cat tr sed sort rm startsh osname \
+cc gccversion test comm uniq echo Options trnl \
optimize ccflags ldflags libs

?MAKE: -pick add \$@ %<

?S:ccsymbols:

?S: The variable contains the symbols
defined by the C compiler alone.

?S: The symbols defined by cpp or by cc when it calls cpp are not in

?S: this list, see cppsymbols and cppccsymbols.

?S: The list is a space-separated list of symbol=value tokens.

?S:.

?S:cppsymbols:

?S: The variable contains the symbols defined by the C preprocessor

?S: alone. The symbols defined by cc or by cc when it calls cpp are

?S: not in this list, see ccsymbols and cppccsymbols.

?S: The list is a space-separated list of symbol=value tokens.

?S:.

?S:cppccsymbols:

?S: The variable contains the symbols defined by the C compiler

?S: when it calls cpp. The symbols defined by the cc alone or cpp

?S: alone are not in this list, see ccsymbols and cppsymbols.

?S: The list is a space-separated list of symbol=value tokens.

?S:.

?T:also symbols i postprocess_cc_v flags

?F:./Cppsym

?F:!Cppsym.true !Cppsym.know !ccsym.com !ccsym.cpp !ccsym.own

: determine known pre-processor and compiler symbols

echo " "

\$echo "Guessing which symbols your C compiler and preprocessor
define...">&4

?X:

?X: The symbol list is in alpha order for ease of maintenance...

?X:

?X: Lots of new symbols (mostly rummaged from gcc), courtesy of

?X: Jarkko Hietaniemi <jhi@snakemail.hut.fi> -- RAM, 06/06/94

?X:

?X: If your symbol is mixed case, just add it as-is.
?X: All symbols will be transformed to both all-lower and all-upper.
?X: Also drop any leading/trailing underscores, the scan will try all those.
?X:

```
$cat <<'EOSH' > Cppsym.know
a29k ABI64 aegis AES_SOURCE AIX AIX32 AIX370
AIX41 AIX42 AIX43 AIX_SOURCE aixpc ALL_SOURCE
alliant alpha am29000 AM29000 AMD64 amiga AMIGAOS AMIX
ansi ANSI_C_SOURCE apollo ardent ARM32 atarist att386 att3b
BeOS BIG_ENDIAN BIT_MSF bsd BSD bsd43 bsd4_2 bsd4_3 BSD4_3 bsd4_4
BSD_4_3 BSD_4_4 BSD_NET2 BSD_TIME BSD_TYPES BSDCOMPAT bsdi
bull c cadmus clipper CMU COFF COMPILER_VERSION
concurrent convex cpu cray CRAY CRAYMPP ctix CX_UX
CYGWIN DGUX DGUX_SOURCE DJGPP dmert DOLPHIN DPX2 DSO
Dynix DynixPTX ELF encore EPI EXTENSIONS FAVOR_BSD
FILE_OFFSET_BITS
FreeBSD GCC_NEW_VARARGS gcos gcx gimpel
GLIBC GLIBC_MINOR
GNU_SOURCE GNUC GNUC_MINOR GNU_LIBRARY GO32 gould GOULD_PN
H3050R H3050RX hbullx20 hcx host_mips
hp200 hp300 hp700 HP700 hp800 hp9000
hp9000s200 hp9000s300 hp9000s400 hp9000s500
hp9000s700 hp9000s800 hp9k8 hp_osf hppa hpux HPUX_SOURCE
i186 i286 i386 i486 i586 i686 i8086 i80960 i860 I960
IA64 iAPX286 ibm ibm032 ibmesa IBMR2 ibmrt ILP32 ILP64
INLINE_INTRINSICS INTRINSICS INT64 interdata is68k ksr1
LANGUAGE_C LARGE_FILE_API LARGEFILE64_SOURCE
LARGEFILE_SOURCE LFS64_LARGEFILE LFS_LARGEFILE
Linux LITTLE_ENDIAN LONG64 LONG_DOUBLE LONG_LONG
LONGDOUBLE LONGLONG LP64 luna luna88k Lynx
M68000 m68k m88100 m88k M88KBCS_TARGET M_COFF
M_I186 M_I286 M_I386 M_I8086 M_I86 M_I86SM M_SYS3
M_SYS5 M_SYSIII M_SYSV M_UNIX M_XENIX MACH machine MachTen
MATH_HAS_NO_SIDE_EFFECTS
mc300 mc500 mc68000 mc68010 mc68020 mc68030 mc68040
mc68060 mc68k mc68k32 mc700 mc88000 mc88100 merlin
mert MiNT mips MIPS_FPSET MIPS_ISA MIPS_SIM MIPS_SZINT
MIPS_SZLONG
MIPS_SZPTR MIPSEB MIPSEL MODERN_C motorola
mpeix MSDOS MTXINU MULTIMAX mvs MVS n16 ncl_el ncl_mr
NetBSD news1500 news1700 news1800 news1900 news3700
news700 news800 news900 NeXT NLS nonstopux ns16000 ns32000
ns32016 ns32332 ns32k nsc32000
OCS88 OEMVS OpenBSD os OS2 OS390 osf OSF1 OSF_SOURCE
pa_risc PA_RISC1_1 PA_RISC2_0 PARAGON parisc
pc532 pdp11 PGC PIC plexus PORTAR posix
POSIX1B_SOURCE POSIX2_SOURCE POSIX4_SOURCE
POSIX_C_SOURCE POSIX_SOURCE POWER
```

PROTOTYPES PWB pyr QNX R3000 REENTRANT RES Rhapsody RISC6000
 riscix riscos RT S390 SA110 scs SCO sequent sgi SGI_SOURCE SH3 sinix
 SIZE_INT SIZE_LONG SIZE_PTR SOCKET_SOURCE SOCKETS_SOURCE
 sony sony_news sonyrisc sparac sparclite spectrum
 stardent stdc STDC_EXT stratos sun sun3 sun386
 Sun386i svr3 svr4 SVR4_2 SVR4_SOURCE svr5
 SX system SYSTYPE_BSD SYSTYPE_BSD43 SYSTYPE_BSD44
 SYSTYPE_SVR4 SYSTYPE_SVR5 SYSTYPE_SYSV SYSV SYSV3 SYSV4 SYSV5
 sysV68 sysV88 Tek4132 Tek4300 titan
 TM3200 TM5400 TM5600
 tower tower32 tower32_200 tower32_600 tower32_700
 tower32_800
 tower32_850 tss
 u370 u3b u3b2 u3b20 u3b200 u3b20d u3b5
 ultrix UMAXV UnicomPBB UnicomPBD UNICOS UNICOSMK
 unix UNIX95 UNIX99 unixpc unos
 USE_BSD USE_FILE_OFFSET64 USE_GNU USE_ISOC9X USE_LARGEFILE USE_LARGEFILE64
 USE_MISC USE_POSIX USE_POSIX199309 USE_POSIX199506 USE_POSIX2
 USE_REENTRANT USE_SVID USE_UNIX98 USE_XOPEN USE_XOPEN_EXTENDED
 USGr4 USGr4_2
 Utek UTeK UTS UWIN uxpm uxps vax venix VMESA vms xenix Xenix286
 XOPEN_SOURCE XOPEN_SOURCE_EXTENDED XPG2 XPG2_EXTENDED
 XPG3 XPG3_EXTENDED XPG4 XPG4_EXTENDED
 z8000
 EOSH
 ?X: Maybe put other stuff here too.
 cat <<EOSH >>Cppsym.know
 \$osname
 EOSH
 ./tr '[a-z]' '[A-Z]' < Cppsym.know > Cppsym.a
 ./tr '[A-Z]' '[a-z]' < Cppsym.know > Cppsym.b
 \$cat Cppsym.know > Cppsym.c
 \$cat Cppsym.a Cppsym.b Cppsym.c | \$tr ' ' \$trnl | \$sort | \$uniq > Cppsym.know
 \$rm -f Cppsym.a Cppsym.b Cppsym.c
 cat <<EOSH > Cppsym
 \$startsh
 if \$test \ \$# -gt 0; then
 echo \ \$* | \$tr " " "\$trnl" | ./Cppsym.try > Cppsym.got
 if \$test -s Cppsym.got; then
 \$rm -f Cppsym.got
 exit 0
 fi
 \$rm -f Cppsym.got
 exit 1
 else
 \$tr " " "\$trnl" | ./Cppsym.try
 exit 0
 fi

EOSH

```
chmod +x Cppsym
```

```
$unicefix Cppsym
```

?X: The below awk script will die a horrible death if

?X: some of the tested symbols are not long ints.

?X: Also, we do not make difference between just defined and defined zero.

```
cat <<EOSH > Cppsym.try
```

```
$startsh
```

```
cat <<'EOCP' > try.c
```

```
#include <stdio.h>
```

```
int main() {
```

EOCP

?X: The length(\$1) command guards against possible empty entries.

?X: The awk snippet is know to give heartburn to UNICOS/mk awk.

```
$awk \\  
EOSH
```

```
cat <<'EOSH' >> Cppsym.try
```

```
'length($1) > 0 {
```

```
    printf "#ifdef %s\n#if %s+0\nprintf(\"%s=%ld\n\", (long)%s);\n#else\nprintf(\"%s\n\");\n#endif\n#endif\n", $1,
```

```
    printf "#ifdef _%s\n#if _%s+0\nprintf(\"_%s=%ld\n\",
```

```
(long)_%s);\n#else\nprintf(\"_%s\n\");\n#endif\n#endif\n", $1, $1, $1, $1, $1
```

```
    printf "#ifdef __%s\n#if __%s+0\nprintf(\"__%s=%ld\n\",
```

```
(long)_%s);\n#else\nprintf(\"__%s\n\");\n#endif\n#endif\n",
```

```
    $1, $1, $1, $1, $1
```

```
    printf "#ifdef __%s_\n#if __%s__+0\nprintf(\"__%s__=%ld\n\",
```

```
(long)_%s__);\n#else\nprintf(\"__%s__\n\");\n#endif\n#endif\n", $1, $1, $1, $1, $1
```

```
} ' >> try.c
```

```
echo 'return 0;}' >> try.c
```

EOSH

```
cat <<EOSH >> Cppsym.try
```

```
flags="$ccflags"
```

```
case "$osname-$gccversion" in
```

```
irix-) flags="$flags -woff 1178" ;;
```

```
os2-*) flags="$flags -Zlinker /PM:VIO" ;;
```

```
esac
```

```
$cc -o try $optimize \ $flags $ldflags try.c $libs && $run ./try
```

EOSH

```
chmod +x Cppsym.try
```

```
$unicefix Cppsym.try
```

```
./Cppsym < Cppsym.know > Cppsym.true
```

: now check the C compiler for additional symbols

?X: suggested by Jarkko Hietaniemi <jhi@snakemail.hut.fi>, thanks!

```
postprocess_cc_v="
```

```
case "$osname" in
```

```
aix) postprocess_cc_v="|str , ' "' ;;
```

```
esac
```

```
$cat >ccsym <<EOS
```

```

$startsh
$cat >tmp.c <<EOF
extern int foo;
EOF
for i in ` $cc -v -c tmp.c 2>&1 $postprocess_cc_v `
do
case "$i" in
-D*) echo "$i" | $sed 's/^-D//';;
-A*) $test "$gccversion" && echo "$i" | $sed 's/^-A// | $sed 's/^(.*)/(.*)/1=2/';;
esac
done
$rm
-f try.c
EOS
postprocess_cc_v="
chmod +x ccsym
$eunicefix ccsym
./ccsym > ccsym1.raw
?X: AIX complains if $uniq is passed an empty file. ($sort apparently
?X: doesn't care.) --AD 14 July 1998
if $test -s ccsym1.raw; then
    $sort ccsym1.raw | $uniq >ccsym.raw
else
    mv ccsym1.raw ccsym.raw
fi

?X: canonicalize symbols for easier sort/uniq/comm usage: append =1 if no = sign
?X: the awk script must be on two lines for older awk programs, sigh! -- ADO
$awk '/^=/ { print $0; next }
{ print $0"=1" }' ccsym.raw >ccsym.list
$awk '/^=/ { print $0; next }
{ print $0"=1" }' Cppsym.true >ccsym.true
$comm -13 ccsym.true ccsym.list >ccsym.own
$comm -12 ccsym.true ccsym.list >ccsym.com
$comm -23 ccsym.true ccsym.list >ccsym.cpp
also="
if $test -z ccsym.raw; then
echo "Your C compiler doesn't seem to define any symbols!" >&4
echo " "
echo "However, your C preprocessor defines the following symbols:"
$cat Cppsym.true
    ccsymbols="
cppsymbols=`$cat Cppsym.true`
    cppsymbols=`echo
$cppsymbols`
cppcsymbols="$cppsymbols"
else
if $test -s ccsym.com; then

```

```

echo "Your C compiler and pre-processor define these symbols:"
$sed -e 's/(.*)=.*\1/' ccsym.com
also='also '
symbols='ones'
cppccsymbols=`$cat ccsym.com`
cppccsymbols=`echo $cppccsymbols`
$test "$silent" || sleep 1
fi
if $test -s ccsym.cpp; then
$test "$also" && echo " "
echo "Your C pre-processor ${also}defines the following symbols:"
$sed -e 's/(.*)=.*\1/' ccsym.cpp
also='further '
cppsymbols=`$cat ccsym.cpp`
cppsymbols=`echo $cppsymbols`
$test "$silent" || sleep 1
fi
if $test -s ccsym.own; then
$test "$also" && echo " "
echo "Your C compiler ${also}defines the following cpp symbols:"
$sed -e 's/(.*)=1\1/' ccsym.own
$sed -e 's/(.*)=.*\1/' ccsym.own | $uniq >>Cppsym.true
    ccsymbols=`$cat ccsym.own`
    ccsymbols=`echo $ccsymbols`
$test "$silent" || sleep 1
fi
fi
$rm -f Cppsym.know Cppsym.true

```

Found in path(s):

```

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/Cppsym.U

```

No license file was found, but licenses were detected in source scan.

```

case $CONFIG in
")
if test -f config.sh; then TOP=.;
elif test -f ../config.sh; then TOP=..;
elif test -f ../../config.sh; then TOP=../../.;
elif test -f ../../../config.sh; then TOP=../../../.;
elif test -f ../../../../config.sh; then TOP=../../../../.;
else
echo "Can't find config.sh."; exit 1
fi
. $TOP/config.sh
;;
esac
case "$0" in

```

```

*/*) cd `expr X$0 : 'X\(.*/)` ;;
esac
echo "Extracting makedepend (with variable substitutions)"
$spitshell >makedepend <<!GROK!THIS!
$startsh
# $Id: makedepend.sh,v 3.0.1.1 1994/01/24 14:00:05 ram Exp ram $
#
# Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
#
# You may redistribute only under the terms of the Artistic Licence,
# as specified in the README file that comes with the distribution.
# You may reuse parts of this distribution only within the terms of
# that same Artistic Licence; a copy of which may be found at the root
# of the source tree for dist 4.0.
#
#
Original Author: Larry Wall <lwall@netlabs.com>
#
# $Log: makedepend.sh,v $
# Revision 3.0.1.1 1994/01/24 14:00:05 ram
# patch16: changed top ln-style config.sh lookup into test-style one
#
# Revision 3.0 1993/08/18 12:04:37 ram
# Baseline for dist 3.0 netwide release.
#

export PATH || (echo "OOPS, this isn't sh. Desperation time. I will feed myself to sh."; sh \${0}; kill \${0})

cat='$cat'
cppflags='$cppflags'
cp='$cp'
cpp='$cppstdin'
echo='$echo'
egrep='$egrep'
expr='$expr'
mv='$mv'
rm='$rm'
sed='$sed'
sort='$sort'
test='$test'
tr='$tr'
uniq='$uniq'
!GROK!THIS!

$spitshell >>makedepend <<!NO!SUBS!

$cat /dev/null >.deptmp
$rm -f *.c.c /*.c.c

```

```

if test -f Makefile; then
    mf=Makefile
else
    mf=makefile
fi
if test -f $mf; then
    defrule=`<$mf sed -n \
-e '/^\.c\.o:.*;/{' \
-e 's/^\$*\c//' \
-e 's/^[^;]*[ ]*//p' \
-e q \
-e }' \
-e '/^\.c\.o: *$/{' \
-e N \
-e 's/^\$*\c//' \
-e 's/^\.*\n[ ]*//p' \
-e q \
-e }`
fi
case
"$defrule" in
") defrule=$(CC) -c $(CFLAGS) ;;
esac

make clist || ($echo "Searching for .c files..."; \
$echo *.c | $tr '\012' | $egrep -v '*' >.clist)
gotnone=true
for file in `scat .clist`; do
# for file in `cat /dev/null`; do
    case "$file" in
*.c) filebase=`basename $file .c` ;;
*.y) filebase=`basename $file .c` ;;
") continue ;;
esac
gotnone=false
$echo "Finding dependencies for $filebase.o."
$sed -n <$file >$file.c \
-e "/^${filebase}_init(/q" \
-e '/^#/{' \
-e 's/^\.*$|' \
-e 's\\\$|' \
-e p \
-e }'
$cpp -I/usr/local/include -I. $cppflags $file.c | \
$sed \
-e '/^# *[0-9]!/d' \
-e 's/^\.*\(\.*\).*$/filebase'.o: \1/' \
-e 's: \./: |' \

```

```

-e 's|\.c\.c|.c'| \
  $uniq | $sort | $uniq >> .deptmp
done

$sed <Makefile >Makefile.new -e '1,/^# AUTOMATICALLY/!d'

make shlist || ($echo "Searching for .SH files..."; \
  $echo *.SH | $tr ' ' '\012' | $grep -v '*' >.shlist)
if $gotnone || $test -s .deptmp; then

  for file in `cat .shlist`; do
  $echo `sexpr X$file : 'X\(.*)\.SH` : $file config.sh \; \
    /bin/sh $file >> .deptmp
  done
  $echo "Updating Makefile..."
  $echo "# If this runs make out of memory, delete /usr/include lines." \
  >> Makefile.new
  $sed 's/^\(.*\.\o:) *(.*\.*\c) *$|1 \2; ""$defrule \2|" .deptmp \
    >>Makefile.new
else
  make hlist || ($echo "Searching for .h files..."; \
  $echo *.h | $tr ' ' '\012' | $grep -v '*' >.hlist)
  $echo "You don't seem to have a proper C preprocessor. Using grep instead."
  $grep '^#include ' `cat .clist` `cat .hlist` >.deptmp
  $echo "Updating Makefile..."
  <.clist $sed -n \
  -e '/\{ \
  -e 's/^\(.*\)\(.*\)\c|2.o: \1\2.c; ""$defrule \1\2.c|p' \
  -e d \
  -e '}' \
  -e 's/^\(.*\)\c|1.o: \1.c|p' >> Makefile.new
  <.hlist $sed -n 's/^\(.*\)\(.*\)|s= \2= \1\2=|p' >.hsed
  <.deptmp $sed -n 's|c:#include "(.*)".*$|o: \1|p' | \
    $sed 's/^[^;]*/|' | \
    $sed -f
.hsed >> Makefile.new
<.deptmp $sed -n 's|c:#include <(.*)>.*$|o: /usr/include/\1|p' \
  >> Makefile.new
<.deptmp $sed -n 's|h:#include "(.*)".*$|h: \1|p' | \
  $sed -f .hsed >> Makefile.new
<.deptmp $sed -n 's|h:#include <(.*)>.*$|h: /usr/include/\1|p' \
  >> Makefile.new
  for file in `cat .shlist`; do
  $echo `sexpr X$file : 'X\(.*)\.SH` : $file config.sh \; \
    /bin/sh $file >> Makefile.new
  done
fi
$rm -f Makefile.old

```

```
$cp Makefile Makefile.old
$cp Makefile.new Makefile
$rm Makefile.new
$echo "# WARNING: Put nothing here or make depend will gobble it up!" >> Makefile
$rm -f .deptmp `sed 's/\./c.c/' .clist` .shlist .clist .hlist .hsed
```

```
!NO!SUBS!
$unicefix makedepend
chmod +x makedepend
case `pwd` in
*SH)
    $rm -f ./makedepend
    ln makedepend ./makedepend
    ;;
esac
```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/lib/makedepend.SH
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id$
?RCS:
?RCS: Copyright (c) 2003 Jarkko Hietaniemi
?RCS:
?RCS: You may distribute under the terms of either the GNU General Public
?RCS: License or the Artistic License, as specified in the README file.
?RCS:
?MAKE:usefaststdio: Myread Oldconfig Setvar rsrc
?MAKE: -pick add $@ %<
?Y:TOP
?S:usefaststdio:
?S: This variable conditionally defines the USE_FAST_STDIO symbol,
?S: and indicates that Perl should be built to use 'fast stdio'.
?S: Defaults to define in Perls 5.8 and earlier, to undef later.
?S:.
?C:USE_FAST_STDIO:
?C: This symbol, if defined, indicates that Perl should
?C: be built to use 'fast stdio'.
?C: Defaults to define in Perls 5.8 and earlier, to undef later.
?C:.
?H:%<:#ifndef USE_FAST_STDIO
?H:%<:#$usefaststdio USE_FAST_STDIO /**/
?H:%<:#endif
?H:.
?T:xversion
?LINT:set usefaststdio
: Check if faststdio is requested and available
```

```

case "$usefaststdio" in
$define|true|[yY]*|")
xversion=`awk
'/define[ ]+PERL_VERSION/ {print $3}' $src/patchlevel.h`
case "$xversion" in
[68]) dflt='y' ;;
*) dflt='n' ;;
esac
;;
*) dflt='n';;
esac
cat <<EOM

```

Perl can be built to use 'fast stdio', which means using the stdio library but also directly manipulating the stdio buffers to enable faster I/O. Using stdio is better for backward compatibility (especially for Perl extensions), but on the other hand since Perl 5.8 the 'perlio' interface has been preferred instead of stdio.

If this doesn't make any sense to you, just accept the default '\$dflt'.

EOM

```
rp="Use the "fast stdio" if available?"
```

```

./myread
case "$ans" in
y|Y) val="$define" ;;
*) val="$undef" ;;
esac
set usefaststdio
eval $setvar

```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/usefaststdio.U
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: Typedef.U,v \$

?RCS: Revision 3.0.1.3 1995/07/25 13:42:07 ram

?RCS: patch56: added backslash escapes within evals to prevent space problems

?RCS:
?RCS: Revision 3.0.1.2 1994/10/29 16:01:16 ram
?RCS: patch36: don't clobber visible 'val' variable, use 'varval' instead
?RCS:
?RCS: Revision 3.0.1.1 1994/08/29 16:05:14 ram
?RCS: patch32: created
?RCS:
?X:
?X: This unit checks for the definition of a given typedef.
?X:
?X: To use it, say:
?X: set typedef val_t default [includes]
?X: eval \$typedef
?X:
?MAKE:Typedef:
cppstdin cppminus cppflags rm contains Oldconfig
?MAKE: -pick add \$@ %<
?F:!temp.c
?LINT:define typedef
?V:typedef
?S:typedef:
?S: This shell variable is used internally by Configure to check
?S: whether a given typedef is defined or not. A typical use is:
?S: set typedef val_t default [includes]
?S: eval \$typedef
?S: That will return val_t set to default if the typedef was not found,
?S: to typedef otherwise. If no includes are specified, look in sys/types.h.
?S:.
?T:type var def inclist varval inc
: define an is-a-typedef? function
typedef='type=\$1; var=\$2; def=\$3; shift; shift; shift; inclist=\$@;
case "\$inclist" in
"") inclist="sys/types.h";;
esac;
eval "varval=\\$\$var";
case "\$varval" in
"")
\$rm -f temp.c;
for inc in \$inclist; do
echo "#include <\$inc>" >>temp.c;
done;
\$cpstdin \$cppflags \$cppminus < temp.c >temp.E 2>/dev/null;
if \$contains \$type temp.E >/dev/null 2>&1; then
eval "\$var=\\$type";
else
eval "\$var=\\$def";
fi;
\$rm -f temp.?.;

```
*) eval
"$var=\$varval";;
esac'
```

Found in path(s):

```
*/opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/Typedef.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id$
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: $Log: d_shm.U,v $
?RCS: Revision 3.0 1993/08/18 12:07:17 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:d_shm: test d_shmctl d_shmget d_shmat d_shmdt Setvar Findhdr
?MAKE: -pick add $@ %<
?S:d_shm:
?S: This variable conditionally defines the HAS_SHM symbol, which
?S: indicates that the entire shm*(2) library is present.
?S:.
?C:HAS_SHM:
?C: This symbol, if defined, indicates that the entire shm*(2) library is
?C: supported.
?C:.
?H:#$d_shm HAS_SHM /**/
?H:.
?T:h_shm
?LINT:set d_shm
:
see how much of the 'shm*(2)' library is present.
h_shm=true
echo " "
case "$d_shmctl$d_shmget$d_shmat$d_shmdt" in
*"$undef"*) h_shm=false;;
esac
: we could also check for sys/ipc.h ...
if $h_shm && $test `./findhdr sys/shm.h`; then
echo "You have the full shm*(2) library." >&4
val="$define"
```

```
else
echo "You don't have the full shm*(2) library." >&4
val="$undef"
fi
set d_shm
eval $setvar
```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/d_shm.U
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: models.U,v \$

?RCS: Revision 3.0.1.2 1997/02/28 16:13:17 ram

?RCS: patch61: added ?F: metalint hint

?RCS:

?RCS: Revision 3.0.1.1 1993/08/25 14:02:39 ram

?RCS: patch6: added default for large

?RCS:

?RCS: Revision 3.0 1993/08/18 12:09:17 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?MAKE:models split small medium large huge: test cat Myread sysman Oldconfig \

Loc Warn contains rm

?MAKE: -pick add \$@ %<

?S:models:

?S: This variable contains the list of memory models supported by

this

?S: system. Possible component values are none, split, unsplit, small,

?S: medium, large, and huge. The component values are space separated.

?S:.

?S:split:

?S: This variable contains a flag which will tell the C compiler and loader

?S: to produce a program that will run in separate I and D space, for those

?S: machines that support separation of instruction and data space. It is

?S: up to the Makefile to use this.

?S:.

?S:small:

?S: This variable contains a flag which will tell the C compiler and loader
?S: to produce a program running with a small memory model. It is up to
?S: the Makefile to use this.
?S:.
?S:medium:
?S: This variable contains a flag which will tell the C compiler and loader
?S: to produce a program running with a medium memory model. If the
?S: medium model is not supported, contains the flag to produce large
?S: model programs. It is up to the Makefile to use this.
?S:.
?S:large:
?S: This variable contains a flag which will tell the C compiler and loader
?S: to
produce a program running with a large memory model. It is up to
?S: the Makefile to use this.
?S:.
?S:huge:
?S: This variable contains a flag which will tell the C compiler and loader
?S: to produce a program running with a huge memory model. If the
?S: huge model is not supported, contains the flag to produce large
?S: model programs. It is up to the Makefile to use this.
?S:.
?T:unsplit tans modelcc
?F!:pdp11
?D:large="
?LINT:extern cc
: see what memory models we can support
case "\$models" in
")
?X: We may not use Cppsym or we get a circular dependency through cc.
?X: But this should work regardless of which cc we eventually use.
\$cat >pdp11.c <<'EOP'
int main() {
#ifdef pdp11
exit(0);
#else
exit(1);
#endif
}
EOP
?X: Run cc in a subshell in case they don't have a 'cc' command.
?X: Presumably they do have gcc or something.
case "\$cc" in
") modelcc="\$cc" ;;
*) modelcc="cc" ;;
esac
(\$modelcc -o pdp11 pdp11.c) >/dev/null 2>&1
if \$test -f pdp11 && ./pdp11 2>/dev/null;

```

then
  dflt='unsplit split'
else
  tans=`./loc . X /lib/small /lib/large /usr/lib/small /usr/lib/large /lib/medium /usr/lib/medium /lib/huge`
  case "$tans" in
  X) dflt='none';;
  *) if $test -d /lib/small || $test -d /usr/lib/small; then
      dflt='small'
    else
      dflt=""
    fi
    if $test -d /lib/medium || $test -d /usr/lib/medium; then
      dflt="$dflt medium"
    fi
    if $test -d /lib/large || $test -d /usr/lib/large; then
      dflt="$dflt large"
    fi
    if $test -d /lib/huge || $test -d /usr/lib/huge; then
      dflt="$dflt huge"
    fi
  esac
fi;;
*) dflt="$models";;
esac
$cat <<EOM

```

Some systems have different model sizes. On most systems they are called small, medium, large, and huge. On the PDP11 they are called unsplit and split. If your system doesn't support different memory models, say "none". If you wish to force everything to one memory model, say "none" here and put the appropriate flags later when it asks you for other cc and ld flags.

Venix systems may wish

to put "none" and let the compiler figure things out.

(In the following question multiple model names should be space separated.)

The default for most systems is "none".

EOM

rp="Which memory models are supported?"

./myread

models="\$ans"

case "\$models" in

none)

small="

medium="

large="

huge="

```

unsplit="
split="
;;
*split)
case "$split" in
") if $contains '\-i' $sysman/ld.1 >/dev/null 2>&1 || \
  $contains '\-i' $sysman/cc.1 >/dev/null 2>&1; then
  dflt='-i'
else
  dflt='none'
fi;;
*) dflt="$split";;
esac
rp="What flag indicates separate I and D space?"
./myread
tans="$ans"
case "$tans" in
none) tans="";;
esac
split="$tans"
unsplit="";;
*large*|*small*|*medium*|*huge*)
case "$models" in
*large*)
case "$large" in
") dflt='-Ml';;
*) dflt="$large";;
esac
rp="What flag indicates large model?"
./myread
tans="$ans"
case "$tans" in
none) tans="";;
esac
large="$tans";;
*) large="";;
esac
case "$models" in
*huge*) case "$huge" in
")
dflt='-Mh';;
*) dflt="$huge";;
esac
rp="What flag indicates huge model?"
./myread
tans="$ans"
case "$tans" in
none) tans="";;

```

```

esac
huge="$stans";;
*) huge="$large";;
esac
case "$models" in
*medium*) case "$medium" in
") dflt='-Mm';;
*) dflt="$medium";;
esac
rp="What flag indicates medium model?"
./myread
tans="$sans"
case "$stans" in
none) tans="";
esac
medium="$stans";;
*) medium="$large";;
esac
case "$models" in
*small*) case "$small" in
") dflt='none';;
*) dflt="$small";;
esac
rp="What flag indicates small model?"
./myread
tans="$sans"
case "$stans" in
none) tans="";
esac
small="$stans";;
*) small="";;
esac
;;
*)
./warn "Unrecognized memory models--you may have to edit Makefile.SH"
;;
esac
$rm -f pdp11.* pdp11

```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/models.U
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_mkstemp.U,v 3.0.1.1 1994/08/29 16:11:57 ram Exp \$

?RCS:

?RCS: Copyright (c) 1998 Andy Dougherty

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public
?RCS: License or the Artistic License, as specified in the README file.
?RCS:
?RCS: Original Author: Andy Dougherty <doughera@lafcol.lafayette.edu>
?RCS:
?RCS: \$Log: d_mkstemp.U,v \$
?RCS:
?MAKE:d_mkstemp: Inlibc
?MAKE: -pick add \$@ %<
?S:d_mkstemp:
?S: This variable conditionally defines the HAS_MKSTEMP symbol, which
?S: indicates to the C program that the mkstemp() routine is available
?S: to exclusively create and open a uniquely named temporary file.
?S:.
?C:HAS_MKSTEMP :
?C: This symbol, if defined, indicates that the mkstemp routine is
?C: available to exclusively create and open a uniquely named
?C: temporary file.
?C:.
?H:#\$d_mkstemp HAS_MKSTEMP /**/
?H:.
?LINT:set d_mkstemp
: see if mkstemp exists
set mkstemp d_mkstemp
eval
\$inlibc

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/modified/d_mkstemp.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: sysman.U,v 3.0.1.2 1994/06/20 07:08:43 ram Exp \$
?RCS:
?RCS: Copyright (c) 1991-1993, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 3.0.
?RCS:
?RCS: \$Log: sysman.U,v \$
?RCS: Revision 3.0.1.2 1994/06/20 07:08:43 ram
?RCS: patch30: now explicitly states that /usr/man/man1 is the default
?RCS: patch30: added /usr/local/man/man1 to the search list
?RCS:
?RCS: Revision 3.0.1.1 1993/09/13 16:13:50 ram

```

?RCS: patch10: added support for /local/man/man1 (WAD)
?RCS: patch10: added temporary syspath variable to cut down on line length
?RCS:
?RCS: Revision 3.0 1993/08/18 12:09:55 ram
?RCS: Baseline for dist 3.0 netwide
release.
?RCS:
?MAKE:sysman: test Loc Oldconfig
?MAKE: -pick add $@ %<
?S:sysman:
?S: This variable holds the place where the manual is located on this
?S: system. It is not the place where the user wants to put his manual
?S: pages. Rather it is the place where Configure may look to find manual
?S: for unix commands (section 1 of the manual usually). See mansrc.
?S:.
?T:syspath
: determine where manual pages are on this system
echo " "
case "$sysman" in
")
syspath="/usr/share/man/man1 /usr/man/man1"
syspath="$syspath /usr/man/mann /usr/man/man1 /usr/man/local/man1"
syspath="$syspath /usr/man/u_man/man1"
syspath="$syspath /usr/catman/u_man/man1 /usr/man/l_man/man1"
syspath="$syspath /usr/local/man/u_man/man1 /usr/local/man/l_man/man1"
syspath="$syspath /usr/man/man.L /local/man/man1 /usr/local/man/man1"
sysman=`./loc . /usr/man/man1 $syspath`
;;
esac
if $test -d "$sysman"; then
echo "System manual is in $sysman." >&4
else
echo "Could not find manual pages in source form."
>&4
fi

```

Found in path(s):

```

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/modified/sysman.U

```

No license file was found, but licenses were detected in source scan.

```

?RCS: $Id$

```

```

?RCS:

```

```

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

```

```

?RCS:

```

```

?RCS: You may redistribute only under the terms of the Artistic License,

```

```

?RCS: as specified in the README file that comes with the distribution.

```

```

?RCS: You may reuse parts of this distribution only within the terms of

```

?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: \$Log: Options.U,v \$
?RCS: Revision 3.0.1.7 1997/02/28 15:08:15 ram
?RCS: patch61: optdef.sh now starts with a "startsh"
?RCS: patch61: moved some code from Head.U
?RCS:
?RCS: Revision 3.0.1.6 1995/09/25 09:14:46 ram
?RCS: patch59: protected option parsing code against 'echo -*' option failure
?RCS:
?RCS: Revision 3.0.1.5 1995/05/12 12:04:52 ram
?RCS: patch54: added -K option for experts
?RCS:
?RCS: Revision 3.0.1.4 1995/01/30 14:27:52 ram
?RCS: patch49: this unit now exports file optdef.sh,
not a variable
?RCS:
?RCS: Revision 3.0.1.3 1995/01/11 15:19:00 ram
?RCS: patch45: new -O option allowing -D and -U to override config.sh settings
?RCS: patch45: file optdef.sh is no longer removed after sourcing
?RCS:
?RCS: Revision 3.0.1.2 1994/10/29 15:58:06 ram
?RCS: patch36: ensure option definition file is removed before appending
?RCS: patch36: protect variable definitions with spaces in them
?RCS:
?RCS: Revision 3.0.1.1 1994/06/20 06:55:44 ram
?RCS: patch30: now uses new me symbol to tag error messages
?RCS: patch30: new -D and -U options to define/undef symbols (JHI)
?RCS:
?RCS: Revision 3.0 1993/08/18 12:05:14 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?X:
?X: Command line parsing. It is really important that the variables used here
?X: be not listed in the MAKE line, or they will be saved in config.sh and
?X: loading this file to fetch default answers would clobber the values set
?X: herein.
?X:
?MAKE:Options: startsh
?MAKE: -pick wipe \$@ %<
?V:reuseval
alldone error realsilent silent extractsh fastread \
override knowitall: config_sh
?T:arg argn symbol config_arg0 config_args config_argc xxx yyy zzz uuu
?T:args_exp args_sep arg_exp
?F:!Configure
?F:./optdef.sh ./cmdline.opt ./posthint.sh ./cmdl.opt

```

: Save command line options in file UU/cmdline.opt for later use in
: generating config.sh.
?X: This temporary file will be read by Oldsym.U. I used a temporary
?X: file to preserve all sorts of potential command line quotes and
?X: also because we don't know in advance how many variables we'll
?X: need, so I can't actually declare them on the MAKE line.
?X: The config_args variable won't be quite correct if Configure is
?X: fed something like ./Configure -Dcc="gcc -B/usr/ccs/bin/"
?X: since the quotes are gone by the time we see them. You'd have to
?X: reconstruct the command line from the config_arg? lines, but since
?X: I don't imagine anyone actually having to do that, I'm not going
?X: to worry too much.
cat > cmdline.opt
<<EOSH
: Configure command line arguments.
config_arg0='$0'
config_args='$*'
config_argc=$#
EOSH
argn=1
args_exp=""
args_sep=""
for arg in "$@"; do
  cat >>cmdline.opt <<EOSH
  config_arg$argn='$arg'
EOSH
?X: Extreme backslashitis: replace each ' by """"
  cat <<EOC | sed -e "s/'/""""/g" > cmdl.opt
  $arg
EOC
  arg_exp=`cat cmdl.opt`
  args_exp="$args_exp$args_sep'$arg_exp'"
  argn=`expr $argn + 1`
  args_sep=' '
done
?X: args_exp is good for restarting self: eval "set X $args_exp"; shift; $0 "$@"
?X: used by hints/os2.sh in Perl, for instance
rm -f cmdl.opt

```

```

: produce awk script to parse command line options
cat >options.awk <<'EOF'
BEGIN {
  optstr = "A:dD:eEf:hKOrsSU:V"; # getopt-style specification

  len = length(optstr);
  for (i = 1; i <= len; i++) {
    c = substr(optstr, i, 1);
?X: some older awk's do not have the C ?: construct

```

```

if (i < len) a = substr(optstr, i + 1, 1); else a = "";
if (a == ":") {
    arg[c] = 1;
    i++;
}
opt[c] = 1;
}
}
{
    expect = 0;
    str = $0;
    if (substr(str,
1, 1) != "-") {
        printf("%s\n", str);
        next;
    }
    len = length($0);
    for (i = 2; i <= len; i++) {
        c = substr(str, i, 1);
        if (!opt[c]) {
            printf("-%s\n", substr(str, i));
            next;
        }
        printf("-%s\n", c);
        if (arg[c]) {
            if (i < len)
                printf("%s\n", substr(str, i + 1));
            else
                expect = 1;
            next;
        }
    }
}
END {
    if (expect)
        print "?";
}
EOF

```

: process the command line options

?X: Use "\$@" to keep arguments with spaces in them from being split apart.

?X: For the same reason, awk will output quoted arguments and the final eval

?X: removes them and sets a proper \$* array. An 'X' is prepended to each

?X: argument before being fed to echo to guard against 'echo -x', where -x

?X: would be understood as an echo option! It is removed before feeding awk.

set X `for arg in "\$@"; do echo "X\$arg"; done |

sed -e s/X// | awk -f options.awk`

eval "set \$*"

```

shift
rm -f options.awk

: set up default values
fastread=""
reuseval=false
config_sh=""
alldone=""
error=""
silent=""
extractsh=""
override=""
knowitall=""
rm
-f optdef.sh posthint.sh
cat >optdef.sh <<EOS
$startsh
EOS

```

?X:

?X: Given that we now have the possibility to execute Configure remotely
?X: thanks to the new src.U support, we have to face the possibility
?X: of having to ask where the source lie, which means we need the Myread.U
?X: stuff and possibly other things that might echo something on the
?X: screen...

?X:

?X: That's not pretty, and might be confusing in 99% of the time. So...
?X: We introduce a new realsilent variable which is set when -s is given,
?X: and we force silent=true if -S is supplied. The Extractall.U unit
?X: will then undo the >&4 redirection based on the value of the
?X: realsilent variable... -- RAM, 18/93/96

?X:

```

: option parsing
while test $# -gt 0; do
case "$1" in
-d) shift; fastread=yes;;
-e) shift; alldone=cont;;
-f)
shift
cd ..
if test -r "$1"; then
config_sh="$1"
else
echo "$me: cannot read config file $1." >&2
error=true
fi
cd UU

```

```

shift;;
-h)
shift; error=true;;
-r) shift; reuseval=true;;
-s) shift; silent=true; realsilent=true;;
-E) shift; alldone=exit;;
-K) shift; knowitall=true;;
-O) shift; override=true;;
-S) shift; silent=true; extractsh=true;;
-D)
shift
case "$1" in
*)
echo "$me: use '-U symbol=', not '-D symbol='." >&2
echo "$me: ignoring -D $1" >&2
;;
*=*) echo "$1" | \
sed -e "s/^\\"/g" -e "s/=(.*)/=\\1/" >> optdef.sh;;
*) echo "$1='define'" >> optdef.sh;;
esac
shift
;;
-U)
shift
case "$1" in
*) echo "$1" >> optdef.sh;;
*=*)
echo "$me: use '-D symbol=val', not '-U symbol=val'." >&2
echo "$me: ignoring -U $1" >&2
;;
*) echo "$1='undef'" >> optdef.sh;;
esac
shift
;;
-A)
shift
xxx=""
yyy="$1"
zzz=""
uuu=undef
case "$yyy" in
*=*) zzz=`echo "$yyy"|sed 's!=.*!!'^
case "$zzz" in
*:* ) zzz="" ;;
*) xxx=append
zzz=" "`echo
"$yyy"|sed 's!^[^=]*!!'^
yyy=`echo "$yyy"|sed 's!=.*!!'^` ;;

```

```

        esac
        ;;
    esac
    case "$xxx" in
    ") case "$yyy" in
        *.* ) xxx=`echo "$yyy"|sed 's!:.*!!'^
            yyy=`echo "$yyy"|sed 's!^[^:]*!!'^
            zzz=`echo "$yyy"|sed 's!^[^=]*!!'^
            yyy=`echo "$yyy"|sed 's!=.*!!'^ ;;
        *) xxx=`echo "$yyy"|sed 's!:.*!!'^
            yyy=`echo "$yyy"|sed 's!^[^:]*!!'^ ;;
    esac
    ;;
    esac
    case "$xxx" in
    append)
    echo "$yyy=\\"${$yyy}$zzz\""" >> posthint.sh ;;
    clear)
    echo "$yyy="" >> posthint.sh ;;
    define)
        case "$zzz" in
        ") zzz=define ;;
    esac
    echo "$yyy='$zzz'" >> posthint.sh ;;
    eval)
    echo "eval \\"$yyy=$zzz\""" >> posthint.sh ;;
    prepend)
    echo "$yyy=\\"$zzz\${$yyy}\""" >> posthint.sh ;;
    undef)
        case "$zzz" in
        ")
        zzz="$uuu" ;;
    esac
    echo "$yyy=$zzz" >> posthint.sh ;;
        *) echo "$me: unknown -A command '$xxx', ignoring -A $1" >&2 ;;
    esac
    shift
    ;;
-V) echo "$me generated by metaconfig <VERSION> PL<PATCHLEVEL>." >&2
    exit 0;;
--) break;;
-*) echo "$me: unknown option $1" >&2; shift; error=true;;
*) break;;
    esac
done

case "$error" in
true)

```

```
cat >&2 <<EOM
```

```
Usage: $me [-dehrsEKOSV] [-f config.sh] [-D symbol] [-D symbol=value]
```

```
[-U symbol] [-U symbol=] [-A command:symbol...]
```

-d : use defaults for all answers.

-e : go on without questioning past the production of config.sh.

-f : specify an alternate default configuration file.

-h : print this help message and exit (with an error status).

-r : reuse C symbols value if possible (skips costly nm extraction).

-s : silent mode, only echoes questions and essential information.

-D : define symbol to have some value:

```
-D symbol    symbol gets the value 'define'
```

```
-D symbol=value
```

```
symbol gets the value 'value'
```

-E : stop at the end of questions, after having produced config.sh.

-K : do not use unless you know what you are doing.

-O : let -D and -U override definitions from loaded configuration file.

-S : perform variable substitutions on all .SH files (can mix with -f)

-U : undefine symbol:

```
-U symbol    symbol gets the value 'undef'
```

```
-U symbol=    symbol gets completely empty
```

-A : manipulate symbol after the platform specific hints have been applied:

```
-A symbol=value append " "value to symbol
```

```
-A append:symbol=value append value to symbol
```

```
-A define:symbol=value define symbol to have value
```

```
-A clear:symbol define symbol to be "
```

```
-A define:symbol define symbol to be 'define'
```

```
-A eval:symbol=value define symbol to be eval of value
```

```
-A prepend:symbol=value prepend value to symbol
```

```
-A undef:symbol define symbol to be 'undef'
```

```
-A undef:symbol= define symbol to be "
```

-V : print version number and exit (with
a zero status).

```
EOM
```

```
exit 1
```

```
::
```

```
esac
```

```
?X:
```

```
?X: Unless they specified either -S or both -d and -e/E, make sure we're
```

```
?X: running interactively, i.e. attached to a terminal. Moved from Head.U to
```

```
?X: be able to handle batch configurations...
```

```
?X:
```

```
?X: We have to hardwire the Configure name and cannot use $me, since if they
```

```
?X: said 'sh <Configure', then $me is 'sh'...
```

```
?X:
```

```
: Sanity checks
```

```
case "$fastread$alldone" in
```

```
yescont|yesexit) ;;
```

```

*)
case "$extractsh" in
true) ;;
*)
if test ! -t 0; then
echo "Say 'sh Configure', not 'sh <Configure'"
exit 1
fi
;;
esac
;;
esac

```

?X: In silent mode, the standard output is closed. Questions are asked by
?X: outputting on file descriptor #4, which is the original stdout descriptor.
?X: This filters out all the "junk", since all the needed information is written
?X: on #4. Note that ksh will not let us redirect output if the file descriptor
?X: has not be defined yet, unlike sh, hence the following line...--RAM.

```

exec 4>&1
case "$silent" in
true)
exec 1>/dev/null;;
esac

```

: run the defines and the undefines, if any, but leave the file out there...

```

touch optdef.sh
./optdef.sh

```

: create the posthint manipulation script and leave the file out there...

```

?X: this file will be perused by Oldconfig.U
touch posthint.sh

```

Found in path(s):

```

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/Options.U

```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: Copyright (c) 1999 Jarkko Hietaniemi

?RCS:

?MAKE:usesocks: Myread Oldconfig Setvar spackage package

?MAKE: -pick add \$@ %<

?Y:TOP

?S:usesocks:

?S: This variable conditionally defines the USE_SOCKS symbol,

?S: and indicates that Perl should be built to use SOCKS.

?S:.

?C:USE_SOCKS:

?C: This symbol, if defined, indicates that Perl should

?C: be built to use socks.

?C:.

?H:?%<:#\$usesocks USE_SOCKS /**/

?H:.

?D:usesocks="

?LINT:set usesocks

: check for requested SOCKS support

case "\$usesocks" in

\$define|true|[yY]*) dflt='y';

*)

dflt='n';

esac

cat <<EOM

\$spackage can be built to use the SOCKS proxy protocol library.

If this doesn't make any sense to you, just accept the default '\$dflt'.

EOM

rp="Build \$package for SOCKS?"

./myread

case "\$ans" in

y|Y) val="\$define" ;;

*) val="\$undef" ;;

esac

set usesocks

eval \$setvar

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/usesocks.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: html1dir.U,v \$

?RCS:

?RCS: Copyright (c) 1999 Andy Dougherty

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

```

?RCS: of the source tree for dist 3.0.
?RCS:
?RCS: $Log: html1dir.U,v $
?RCS:
?MAKE:html1dir html1direxp installhtml1dir: cat Loc Myread \
  spackage test Getfile Setprefixvar Prefixit Prefixup
?MAKE: -pick add $@ %<
?Y:TOP
?D:html1dir="
?S:html1dir:
?S: This variable contains the name of the directory in which html
?S: source pages are to be put. This directory is for pages
?S: that describe whole programs, not libraries or modules. It
?S: is intended to correspond roughly to section 1 of the Unix
?S: manuals.
?S:.
?D:html1direxp="
?S:html1direxp:
?S: This
  variable is the same as the html1dir variable, but is filename
?S: expanded at configuration time, for convenient use in makefiles.
?S:.
?D:installhtml1dir="
?S:installhtml1dir:
?S: This variable is really the same as html1direxp, unless you are
?S: using a different installprefix. For extra portability, you
?S: should only use this variable within your makefiles.
?S:.
?LINT:change prefixvar
?LINT:set html1direxp
?LINT:set installhtml1dir
: determine where html pages for programs go
set html1dir html1dir none
eval $prefixit
$cat <<EOM

```

If you wish to install html files for programs in \$spackage, indicate the appropriate directory here. To skip installing html files, answer "none".

```

EOM
case "$html1dir" in
  "|none|$undef|' ) dflt=none ;;
  *) dflt=$html1dir ;;
esac
fn=dn+~
rp="Directory for the main $spackage html pages?"
./getfile
prefixvar=html1dir

```

```
./setprefixvar
: Use ' ' for none so value is preserved next time through Configure
$test X"$html1dir" = "X" && html1dir=' '
```

Found

in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/installdirs/html1dir.U
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1999, Jarkko Hietaniemi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 3.0.

?RCS:

?MAKE:d_sem_init: Inlibc

?MAKE: -pick add \$@ %<

?S:d_sem_init:

?S: This variable conditionally defines HAS_SEM_INIT if sem_init() is

?S: available to initialize a POSIX semaphore.

?S:.

?C:HAS_SEM_INIT:

?C: This symbol, if defined, indicates that the sem_init system call is

?C: available to initialize a POSIX semaphore.

?C:.

?H:#\$d_sem_init HAS_SEM_INIT /**/

?H:.

?LINT:set d_sem_init

: see if sem_init exists

set sem_init d_sem_init

eval \$inlibc

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/perl/d_sem_init.U
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_setlocale.U 1 2006-08-24 12:32:52Z rmanfredi \$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic Licence,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: Original Author: Andy Dougherty <doughera@lafcol.lafayette.edu>

?RCS:

?RCS: \$Log: d_setlocale.U,v \$

?RCS: Revision 3.0.1.1 1994/06/20 06:57:51 ram

?RCS: patch30: created

?RCS:

?MAKE:d_setlocale: Inlibc

?MAKE: -pick add \$@ %<

?S:d_setlocale:

?S: This variable conditionally defines HAS_SETLOCALE if setlocale() is

?S: available to handle locale-specific ctype implementations.

?S:.

?C:HAS_SETLOCALE:

?C: This symbol, if defined, indicates that the setlocale
routine is

?C: available to handle locale-specific ctype implementations.

?C:.

?H:#\$d_setlocale HAS_SETLOCALE /**/

?H:.

?LINT:set d_setlocale

: see if setlocale exists

set setlocale d_setlocale

eval \$inlibc

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/d_setlocale.U

No license file was found, but licenses were detected in source scan.

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?MAKE:d_scalbn: Inlibc

?MAKE: -pick add \$@ %<

?S:d_scalbn:

?S: This variable conditionally defines the HAS_SCALBN symbol, which

?S: indicates to the C program that the scalbn() routine is available.

?S:.

?C:HAS_SCALBN:

?C: This symbol, if defined, indicates that the scalbn routine is

?C: available to multiply floating-point number by integral power

?C: of radix.

?C:.

?H:#\$d_scalbn HAS_SCALBN /**/

```
?H:
?LINT:set d_scalbn
: see if scalbn exists
set scalbn d_scalbn
eval $inlibc
```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/perl/d_scalbn.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: Copyright (c) 1996, Chip Salzenberg
```

```
?RCS:
```

```
?RCS: You may distribute under the terms of either the GNU General Public
```

```
?RCS: License or the Artistic License, as specified in the README file.
```

```
?RCS:
```

```
?MAKE:bincompat5005 d_bincompat5005: Oldconfig Myread Setvar cat \
  usethreads usemultiplicity
```

```
?MAKE: -pick add $@ %<
```

```
?Y:TOP
```

```
?S:bincompat5005:
```

```
?S: This variable contains y if this version of Perl should be
```

```
?S: binary-compatible with Perl 5.005.
```

```
?S:.
```

```
?S:d_bincompat5005:
```

```
?S: This variable conditionally defines BINCOMPAT5005 so that embed.h
```

```
?S: can take special action if this version of Perl should be
```

```
?S: binary-compatible with Perl 5.005. This is impossible for builds
```

```
?S: that use features like threads and multiplicity it is always $undef
```

```
?S: for those versions.
```

```
?S:.
```

```
?C:PERL_BINCOMPAT_5005:
```

```
?C: This symbol, if defined, indicates that this version of Perl should be
```

```
?C: binary-compatible with Perl 5.005. This is impossible
```

```
for builds
```

```
?C: that use features like threads and multiplicity it is always $undef
```

```
?C: for those versions.
```

```
?C:.
```

```
?H:#$d_bincompat5005 PERL_BINCOMPAT_5005 /**/
```

```
?H:
```

```
: Binary compatibility with 5.005 is not possible for builds
```

```
: with advanced features
```

```
case "$usethreads$usemultiplicity" in
```

```
*define*)
```

```
  bincompat5005="$undef"
```

```
  d_bincompat5005="$undef"
```

```
;;
```

```
*) $cat <<EOM
```

This version of Perl can be compiled for binary compatibility with 5.005.
If you decide to do so, you will be able to continue using most of the
extensions that were compiled for Perl 5.005.

EOM

```
case "$bincompat5005$d_bincompat5005" in
*) $undef*) dflt=n ;;
*) dflt=y ;;
esac
rp='Binary compatibility with Perl 5.005?'
./myread
case "$ans" in
y*) val="$define" ;;
*) val="$undef" ;;
esac
set d_bincompat5005
eval $setvar
case "$d_bincompat5005" in
"$define")
bincompat5005="$define"
;;
*) bincompat5005="$undef"
d_bincompat5005="$undef"
;;
esac
;;
esac
```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-  
debian-perl-5.26.1/U/perl/bincompat5005.U
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: i_sysrusage.U,v \$

?RCS:

?RCS: Copyright (c) 2000 Jarkko Hietaniemi

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?MAKE:i_sysrusage: Inhdr Hasfield

?MAKE: -pick add \$@ %<

?S:i_sysrusage:

?S: This variable conditionally defines the I_SYSRUSAGE symbol,

?S: and indicates whether a C program should include <sys/rusage.h>.

?S:.

?C:I_SYSRUSAGE:

?C: This symbol, if defined, indicates that <sys/rusage.h> exists and

?C: should be included.

?C:.

?H:#\$i_sysrusage I_SYSRUSAGE /**/

?H:.

?LINT:set i_sysrusage

: see if this is a sys/rusage.h system

set sys/rusage.h i_sysrusage

eval \$inhdr

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/i_sysrusage.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: sitescript.U,v \$

?RCS:

?RCS: Copyright (c) 1999 Andy Dougherty

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 3.0.

?RCS:

?RCS: \$Log: sitescript.U,v \$

?RCS:

?MAKE:sitescript sitescriptexp installsitescript : Getfile Oldconfig test \

Setprefixvar sitebin siteprefix

?MAKE: -pick add \$@ %<

?Y:TOP

?D:sitescript="

?S:sitescript:

?S: This variable holds the name of the directory in which the user wants

?S: to put add-on publicly executable files for the package in question. It

?S: is most often a local directory such as /usr/local/bin. Programs using

?S: this variable must be prepared to deal with ~name substitution.

?S: The standard

distribution will put nothing in this directory.

?S: After perl has been installed, users may install their own local

?S: scripts in this directory with

?S: MakeMaker Makefile.PL

?S: or equivalent. See INSTALL for details.

?S:.

?D:sitescriptexp="

?S:sitescriptexp:

?S: This is the same as the sitescript variable, but is filename expanded at

?S: configuration time, for use in your makefiles.

```

?S:.
?D:installsitescript="
?S:installsitescript:
?S: This variable is usually the same as sitescriptexp, unless you are on
?S: a system running AFS, in which case they may differ slightly. You
?S: should always use this variable within your makefiles for portability.
?S:.
?LINT:change prefixvar
?LINT:set installsitescript
?LINT:set sitescript
?LINT:set sitescriptexp
: determine where add-on public executable scripts go
case "$sitescript" in
") dflt=$siteprefix/script
  $test -d $dflt || dflt=$sitebin ;;
*) dflt="$sitescript" ;;
esac
fn=d~+
rp='Pathname where add-on public executable scripts
  should be installed?'
./getfile
prefixvar=sitescript
./setprefixvar

```

Found in path(s):

```

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/installdirs/sitescript.U

```

No license file was found, but licenses were detected in source scan.

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?MAKE:d_log2: Inlibc

?MAKE: -pick add \$@ %<

?S:d_log2:

?S: This variable conditionally defines the HAS_LOG2 symbol, which

?S: indicates to the C program that the log2() routine is available

?S: to compute log base two.

?S:.

?C:HAS_LOG2:

?C: This symbol, if defined, indicates that the log2 routine is

?C: available to do the log2 function.

?C:.

?H:#\$d_log2 HAS_LOG2 /**/

?H:.

?LINT:set d_log2

: see if log2 exists

set log2 d_log2

eval \$inlibc

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_log2.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 2000 Jarkko Hietaniemi

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?MAKE:d_fsync: Inlibc

?MAKE: -pick add \$@ %<

?S:d_fsync:

?S: This variable conditionally defines the HAS_FSYNC symbol, which

?S: indicates to the C program that the fsync() routine is available.

?S:.

?C:HAS_FSYNC:

?C: This symbol, if defined, indicates that the fsync routine is

?C: available to write a file's modified data and attributes to

?C: permanent storage.

?C:.

?H:#\$d_fsync HAS_FSYNC /**/

?H:.

?LINT:set d_fsync

: see if fsync exists

set fsync d_fsync

eval \$inlibc

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_fsync.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_strdup.U 1 2006-08-24 12:32:52Z rmanfredi \$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic Licence,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic Licence; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: d_strdup.U,v \$

?RCS: Revision 3.0.1.1 1993/12/15 08:21:41 ram
?RCS: patch15: created
?RCS:
?MAKE:d_strdup: Inlibc
?MAKE: -pick add \$@ %<
?S:d_strdup:
?S: This variable conditionally defines HAS_STRDUP if strdup() is
?S: available to duplicate strings in memory.
?S:.
?C:HAS_STRDUP:
?C: This symbol, if defined, indicates that the strdup routine is
?C: available to duplicate strings in memory. Otherwise, roll up
?C: your own...
?C:.
?H:#\$d_strdup HAS_STRDUP /**/
?H:.
?LINT:set
d_strdup
: see if strdup exists
set strdup d_strdup
eval \$inlibc

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/d_strdup.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_ulimit.U 1 2006-08-24 12:32:52Z rmanfredi \$
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: \$Log: d_ulimit.U,v \$
?RCS: Revision 3.0 1993/08/18 12:07:51 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:d_ulimit: Inlibc
?MAKE: -pick add \$@ %<
?S:d_ulimit:
?S: This variable conditionally defines HAS_ULIMIT if ulimit() is
?S: available to get the user limits.
?S:.
?C:HAS_ULIMIT (ULIMIT):

?C: This symbol, if defined, indicates that the ulimit system call is

?C: available to get the user limits.

?C:.

?H:#\$d_ulimit HAS_ULIMIT /**/

?H:.

?LINT:set

d_ulimit

: see if ulimit exists

set ulimit d_ulimit

eval \$inlibc

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/d_ulimit.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_ctermid.U 1 2006-08-24 12:32:52Z rmanfredi \$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic Licence,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic Licence; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: d_ctermid.U,v \$

?RCS: Revision 3.0 1993/08/18 12:05:54 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?MAKE:d_ctermid: Inlibc

?MAKE: -pick add \$@ %<

?S:d_ctermid:

?S: This variable conditionally defines CTERMID if ctermid() is

?S: available to generate filename for terminal.

?S:.

?C:HAS_CTERMID (CTERMID):

?C: This symbol, if defined, indicates that the ctermid routine is

?C: available to generate filename for terminal.

?C:.

?H:#\$d_ctermid

HAS_CTERMID /**/

?H:.

?LINT:set d_ctermid

: see if ctermid exists

set ctermid d_ctermid

eval \$inlibc

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/d_ctermid.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_shmat.U,v 3.0.1.3 1995/07/25 14:04:23 ram Exp \$

?RCS:

?RCS: Copyright (c) 1991-1993, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 3.0.

?RCS:

?RCS: \$Log: d_shmat.U,v \$

?RCS: Revision 3.0.1.3 1995/07/25 14:04:23 ram

?RCS: patch56: use findhdr to find <sys/shm.h>, to get the right one (ADO)

?RCS:

?RCS: Revision 3.0.1.2 1994/05/13 15:18:56 ram

?RCS: patch27: added new symbol HAS_SHMAT_PROTOTYPE (ADO)

?RCS:

?RCS: Revision 3.0.1.1 1994/05/06 14:54:18 ram

?RCS: patch23: new Shmat_t symbol to declare return type of shmat()

?RCS:

?RCS: Revision 3.0 1993/08/18 12:07:18 ram

?RCS: Baseline for dist 3.0 netwide

release.

?RCS:

?MAKE:d_shmat shmattype d_shmatprototype: Inlibc cat +cc +ccflags \
rm cppstdin cppflags cppminus Findhdr Setvar contains

?MAKE: -pick add \$@ %<

?S:d_shmat:

?S: This variable conditionally defines the HAS_SHMAT symbol, which

?S: indicates to the C program that the shmat() routine is available.

?S:.

?S:shmattype:

?S: This symbol contains the type of pointer returned by shmat().

?S: It can be 'void *' or 'char *'.

?S:.

?S:d_shmatprototype:

?S: This variable conditionally defines the HAS_SHMAT_PROTOTYPE

?S: symbol, which indicates that sys/shm.h has a prototype for

?S: shmat.

?S:.

?C:HAS_SHMAT:

?C: This symbol, if defined, indicates that the shmat() routine is

?C: available to attach a shared memory segment to the process space.

?C:.

?C:Shmat_t:

?C: This symbol holds the return type of the shmat() system call.

?C: Usually set to 'void *' or 'char *'.

?C:.

?C:HAS_SHMAT_PROTOTYPE:

?C: This symbol, if defined, indicates that the sys/shm.h includes

?C: a prototype for shmat().

Otherwise, it is up to the program to

?C: guess one. Shmat_t shmat(int, Shmat_t, int) is a good guess,

?C: but not always right so it should be emitted by the program only

?C: when HAS_SHMAT_PROTOTYPE is not defined to avoid conflicting defs.

?C:.

```
?H:#$d_shmat HAS_SHMAT /**/
```

```
?H:#define Shmat_t $shmattype /**/
```

```
?H:#$d_shmatprototype HAS_SHMAT_PROTOTYPE /**/
```

?H:.

```
?LINT:set d_shmat d_shmatprototype
```

```
?T:xxx
```

```
: see if shmat exists
```

```
set shmat d_shmat
```

```
eval $inlibc
```

```
: see what shmat returns
```

```
case "$d_shmat" in
```

```
"$define")
```

```
$cat >shmat.c <<'END'
```

```
#include <sys/shm.h>
```

```
void *shmat();
```

```
END
```

```
if $cc $ccflags -c shmat.c >/dev/null 2>&1; then
```

```
shmattype='void *'
```

```
else
```

```
shmattype='char *'
```

```
fi
```

```
echo "and it returns ($shmattype)." >&4
```

```
: see if a prototype for shmat is available
```

```
xxx=`./findhdr sys/shm.h`
```

```
$cppstdin $cppflags $cppminus < $xxx > shmat.c 2>/dev/null
```

```
if $contains 'shmat.*(' shmat.c >/dev/null 2>&1; then
```

```
val="$define"
```

```
else
```

```
val="$undef"
```

```
fi
```

```
$rm -f shmat.[co]
```

```
::
```

```
*)
```

```
val="$undef"
```

```
::
```

```
esac
set
d_shmatprototype
eval $setvar
```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/modified/d_shmat.U
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 2000 Jarkko Hietaniemi

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?MAKE:d_qgcvt: Inlibc

?MAKE:-pick add \$@ %<

?S:d_qgcvt:

?S: This variable conditionally defines the HAS_QGCVT symbol, which

?S: indicates to the C program that the qgcvt() routine is available.

?S:.

?C:HAS_QGCVT:

?C: This symbol, if defined, indicates that the qgcvt routine is

?C: available to convert long doubles ("quad doubles") to strings.

?C: This is a low-level routine hopefully faster than sprintf.

?C:.

?H:#\$d_qgcvt HAS_QGCVT /**/

?H:.

?LINT:set d_qgcvt

: see if qgcvt exists

set qgcvt d_qgcvt

eval \$inlibc

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/perl/d_qgcvt.U
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1999, Jarkko Hietaniemi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 3.0.
?RCS:
?MAKE:d_mq_open: Inlibc
?MAKE: -pick add \$@ %<
?S:d_mq_open:
?S: This variable conditionally defines HAS_MQ_OPEN if mq_open() is
?S: available to open a POSIX message queue.
?S:.
?C:HAS_MQ_OPEN:
?C: This symbol, if defined, indicates that the mq_open system call is
?C: available to open a POSIX message queue.
?C:.
?H:#\$d_mq_open HAS_MQ_OPEN /**/
?H:.
?LINT:set d_mq_open
: see if mq_open exists
set mq_open d_mq_open
eval \$inlibc

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_mq_open.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_pwrite.U 1 2006-08-24 12:32:52Z rmanfredi \$
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: \$Log: d_pwrite.U,v \$
?RCS:
?MAKE:d_pwrite: Inlibc
?MAKE: -pick add \$@ %<
?S:d_pwrite:
?S: This variable conditionally defines the HAS_PWRITE symbol, which
?S: indicates to the C program that the pwrite() routine is available.
?S:.
?C:HAS_PWRITE :
?C: This symbol, if defined, indicates that the pwrite routine is
?C: available to perform writes on a file descriptor at a given offset.
?C:.
?H:#\$d_pwrite HAS_PWRITE /**/
?H:.

?LINT:set d_pwrite
: see if pwrite
exists
set pwrite d_pwrite
eval \$inlibc

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/d_pwrite.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: Myread.U 1 2006-08-24 12:32:52Z rmanfredi \$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic Licence,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic Licence; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: Myread.U,v \$

?RCS: Revision 3.0.1.6 1997/02/28 15:05:39 ram

?RCS: patch61: myread script now starts with a "startsh"

?RCS: patch61: miscellaneous fixes

?RCS:

?RCS: Revision 3.0.1.5 1995/01/11 15:14:22 ram

?RCS: patch45: added & escape allowing user to turn on -d from the prompt

?RCS:

?RCS: Revision 3.0.1.4 1994/10/31 09:48:04 ram

?RCS: patch44: added Options to the MAKE line since it's no longer in Init.U

?RCS:

?RCS: Revision 3.0.1.3 1994/10/29

15:56:20 ram

?RCS: patch36: added ?F: line for metalint file checking

?RCS:

?RCS: Revision 3.0.1.2 1993/08/30 08:57:59 ram

?RCS: patch8: added new visible 'nostick' symbol, mainly for Finish.U

?RCS:

?RCS: Revision 3.0.1.1 1993/08/27 14:39:20 ram

?RCS: patch7: now sticks to the question when no default and empty answer

?RCS:

?RCS: Revision 3.0 1993/08/18 12:05:08 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?X:

?X: This unit produces a bit of shell code that must be dotted in in order

?X: to do a read. It allows for shell escapes, default assignment and

?X: parameter evaluation.

?X:

?X: To use this unit, \$rp and \$dflt must hold the question and the

?X: default answer. The question will be printed by the script itself.

?X: Neither \$rp nor \$dflt is altered by the script.

?X:

?X: The myread script will stick to the question if no default is proposed

?X: and the user answer is empty, which prevents mistakes. However, at the

?X: end of Configure, there is an exception

to this rule (Finish.U) where we

?X: set nostick to a non-empty value to allow the Return key to play its role!

?X:

?MAKE:Myread: Options startsh n c trnl

?MAKE: -pick add \$@ %<

?V:ans:dflt rp nostick

?F:./myread

?T:COLUMNS xxxm rp dflt answ aok myecho

?LINT:change fastread

?X: Some shells (Ultrix) do not understand \${COLUMNS:-80}, sigh!

: compute the number of columns on the terminal for proper question formatting

case "\$COLUMNS" in

") COLUMNS='80';;

esac

: set up the echo used in my read

?X:

?X: This variable is intended to be eval'ed. It will echo the two

?X: variables \$rp and \$dflt (provided this latter has a non null value).

?X: It is mainly used by the myread script to echo the questions.

?X:

?X: The \$n and \$c below are substituted before Loc does its silly echo check

?X: so don't put a \$ on the echo below so we get builtin, even if \$echo is

?X: pointing to /bin/echo.

?X:

```
myecho="case \"\$xxxm\" in
```

```
) echo $n \"\$rp $c\" >&4;;
```

```
*) case \"\$rp\" in
```

```
) echo $n \"[\$xxxm] $c\";;
```

```
*)
```

```
if
```

```
test `echo \"\$rp [\$xxxm] \" | wc -c` -ge $COLUMNS; then
```

```
echo \"\$rp\" >&4
```

```
echo $n \"[\$xxxm] $c\" >&4
```

```
else
```

```
echo $n \"\$rp [\$xxxm] $c\" >&4
```

```
fi
```

```
::
```

```
esac;;
```

esac"

: now set up to do reads with possible shell escape and default assignment

```
cat <<EOESC >myread
```

```
$startsh
```

```
?X:
```

```
?X: Save value of default -- do not alter original in case of eval
```

```
?X:
```

```
xxxm=\$dflt
```

```
$myecho
```

```
?X:
```

```
?X: If there is no default, then stop, regardless of the value in fastread.
```

```
?X: In silent mode, no new-line is to be echoed if the question is empty,
```

```
?X: since this is used to wait for the "return" key.
```

```
?X:
```

```
ans='!
```

```
case "\$fastread" in
```

```
yes) case "\$dflt" in
```

```
) ;;
```

```
*) ans=";
```

```
case "\$silent-\$rp" in
```

```
true-) ;;
```

```
*) echo " " >&4;;
```

```
esac;;
```

```
esac;;
```

```
*) case "\$silent" in
```

```
true) case "\$rp" in
```

```
) ans="";;
```

```
esac;;
```

```
esac;;
```

```
esac
```

```
while expr "X\$ans" : "X!" >/dev/null; do
```

```
read answ
```

```
?X:
```

```
?X: Run 'eval' on the answer, in order to do variable substitution, in case
```

```
?X: the user types $HOME or $WHATEVER.
```

```
Variables must be evaluated now.
```

```
?X: Typing '\$HOME' won't currently prevent from substitution -- use '\\$HOME'
```

```
?X: The $1 .. $9 and $*, as well as $@, are available to refer to the
```

```
?X: default value.
```

```
?X:
```

```
set x \$xxxm
```

```
shift
```

```
aok="; eval "ans=\\\"\$answ\\\""" && aok=y
```

```
case "\$answ" in
```

```
?X:
```

```
?X: Use "!" and not a plain ! because of a bug in BSD 4.4 shell
```

```
?X: (reported by Wayne Davison)
```

?X: We must handle the shell escapes before dealing with possible variable

?X: substitution, since the shell we're launching in that case will be able

?X: to do it as well as we can -- RAM, 15/03/96

?X

```
"!")
sh 1>&4
echo " "
$myecho
;;
!*)
set x `expr "X\${ans}" : "X!(.*)\$"`
shift
sh 1>&4 -c "\${*}"
echo " "
$myecho
;;
"\${ans}")
case "\${ans}" in
```

?X:

?X: Answers starting with & are hooks allowing to dynamically turn on/off

?X: some Configure options. That's for the future. -- RAM, 09/01/95

?X: Today, we only recognize '& -d' to mean 'go on as if Configure -d, which

?X: is a hardwired

behaviour compatible with our general scheme.

?X:

```
\\&*)
set x `expr "X\${ans}" : "X&(.*?)\$"`
shift
case "\$1" in
-d)
fastread=yes
echo "(OK, I'll run with -d after this question.)" >&4
;;
-*)
echo "*** Sorry, \$1 not supported yet." >&4
;;
esac
$myecho
ans=!
;;
esac;;
*)
case "\${aok}" in
y)
echo "*** Substitution done -- please confirm."
xxxm="\${ans}"
ans=`echo $n "\${ans}$c" | tr '$trnl' '\`
xxxm="\${ans}"
```

```

ans=!
;;
*)
echo "*** Error -- try again."
ans=!
;;
esac
$myecho
;;
esac
?X: Stick in myread if no default answer and nothing was answered
case "\$ans\$xxxm\$nostick" in
")
ans=!
$myecho
;;
esac
done
case "\$ans" in
") ans="\$xxxm";;
esac
EOSC

```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/Myread.U
```

No license file was found, but licenses were detected in source scan.

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?MAKE:d_trunc: Inlibc

?MAKE: -pick add \$@ %<

?S:d_trunc:

?S: This variable conditionally defines the HAS_TRUNC symbol, which

?S: indicates to the C program that the trunc() routine is available

?S: to round doubles towards zero.

?S:.

?C:HAS_TRUNC:

?C: This symbol, if defined, indicates that the trunc routine is

?C: available to round doubles towards zero.

?C:.

?H:#\$d_trunc HAS_TRUNC /**/

?H:.

?LINT:set d_trunc

: see if trunc exists

set trunc d_trunc

eval \$inlibc

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_trunc.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1999, Jarkko Hietaniemi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 3.0.

?RCS:

?MAKE:d_mq_receive: Inlibc

?MAKE: -pick add \$@ %<

?S:d_mq_receive:

?S: This variable conditionally defines HAS_MQ_RECEIVE if mq_receive() is

?S: available to receive a message from a POSIX message queue.

?S:.

?C:HAS_MQ_RECEIVE:

?C: This symbol, if defined, indicates that the mq_receive system call is

?C: available to receive a message from a POSIX message queue.

?C:.

?H:#\$d_mq_receive HAS_MQ_RECEIVE /**/

?H:.

?LINT:set d_mq_receive

: see if mq_receive exists

set mq_receive d_mq_receive

eval \$inlibc

Found in path(s):

*

/opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_mq_receive.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: Config_h.U 1 2006-08-24 12:32:52Z rmanfredi \$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

```

?RCS:
?RCS: $Log: Config_h.U,v $
?RCS: Revision 3.0.1.5 1997/02/28 14:57:43 ram
?RCS: patch61: added support for src.U
?RCS:
?RCS: Revision 3.0.1.4 1995/09/25 09:10:49 ram
?RCS: patch59: commented the purpose of the #un-def directive
?RCS:
?RCS: Revision 3.0.1.3 1995/01/30 14:25:39 ram
?RCS: patch49: typo fixes in leading config.h comment (WED)
?RCS:
?RCS: Revision 3.0.1.2 1993/08/24 12:13:20 ram
?RCS: patch3: added TOP as a local shell temporary variable
?RCS:
?RCS:
Revision 3.0.1.1 1993/08/19 06:42:20 ram
?RCS: patch1: leading config.sh searching was not aborting properly
?RCS:
?RCS: Revision 3.0 1993/08/18 12:04:47 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?X:
?X: This file ends up producing the config_h.SH script, which is run to produce
?X: the config.h file. The file ./Config_h below contains all the ?H: lines
?X: extracted out of all the units. Metaconfig itself adds the !GROK!THIS!.
?X: Note that this code isn't included into Configure, but must be shipped with.
?X:
?X: For those who wish to know why the file is config_h.SH instead of the more
?X: natural config.h.SH, well... it is to support systems like MS-DOG. Only one
?X: 'dot' is allowed within the file name, as it is part of the "extension" of
?X: the file. MS-DOG will not let you have two 'dots' because that would mean
?X: two "extensions".
?X:
?MAKE:Config_h: Id End Config_sh Obsol_h myuname cf_time cf_by package src
?MAKE: -pick c_h_weed $@ %<
?MAKE: -pick
c_h_weed $@ ./Config_h
?MAKE: -pick c_h_weed $@ ./Obsol_h
?T:PERL_CONFIG_SH TOP
?LINT:unclosed !GROK!THIS!
?LINT:extern CONFIG_H CONFIG_SH
?LINT:change CONFIG_H CONFIG_SH
?X:?LINT:nocomment
: Set up for generating config_h.SH
case "$CONFIG_SH" in
") CONFIG_SH=config.sh;;
esac
case "$CONFIG_H" in

```

```

") CONFIG_H=config.h;;
esac
case $PERL_CONFIG_SH in
")
if test -f $CONFIG_SH; then TOP=.;
elif test -f ../$CONFIG_SH; then TOP=..;
elif test -f ../../$CONFIG_SH; then TOP=../.;
elif test -f ../../../$CONFIG_SH; then TOP=../../.;
elif test -f ../../../../$CONFIG_SH; then TOP=../../../.;
else
echo "Can't find $CONFIG_SH."; exit 1
fi
. $TOP/$CONFIG_SH
;;
esac
?X: Make sure we are in the directory where the .SH file is located.
case "$0" in
*/*) cd `expr X$0 : 'X\(.*/\)^'` ;;
esac
echo "Extracting $CONFIG_H (with variable substitutions)"
?X:
?X: Since we unconditionally translate leading #undef into /*#define, we're
?X: stuck when we really want to have a #undef in $CONFIG_H.
That's why there
?X: is provision here for #un-def, which is translated back into #undef after
?X: all original #undef have been processed.
?X:
?X: Previously, we changed all
?X: #undef FOO /**/
?X: into
?X: /*#define FOO /**/
?X: The xlc compiler (available on IBM's AIX) complains that this is
?X: an illegal attempt to write a nested comment, and warns against it.
?X: There's apparently no way to shut the compiler up, either.
?X: This sed command from Hallvard B Furuseth <h.b.furuseth@usit.uio.no>
?X: changes it to
?X: /*#define FOO /**/
sed <<!GROK!THIS!>$CONFIG_H -e 's!^#undef\(.*/\)^!/*#define\1 \!' -e 's!^#un-def!#undef!'
/* This file was produced by running the config_h.SH script, which
* gets its values from $CONFIG_SH, which is generally produced by
* running Configure.
*
* Feel free to modify any of this as the need arises. Note, however,
* that running config_h.SH again will wipe out any changes you've made.
* For a more permanent change edit $CONFIG_SH and
* rerun config_h.SH.
*/

```

```
/* Package name   : $package
 * Source directory : $src
 * Configuration time: $cf_time
 * Configured by   : $cf_by
 * Target system   : $myuname
 */
```

```
#ifndef _config_h_
#define _config_h_
```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/modified/Config_h.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: d_msem_lck.U 1 2006-08-24 12:32:52Z rmanfredi $
```

```
?RCS:
```

```
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
```

```
?RCS:
```

```
?RCS: You may redistribute only under the terms of the Artistic Licence,
```

```
?RCS: as specified in the README file that comes with the distribution.
```

```
?RCS: You may reuse parts of this distribution only within the terms of
```

```
?RCS: that same Artistic Licence; a copy of which may be found at the root
```

```
?RCS: of the source tree for dist 4.0.
```

```
?RCS:
```

```
?RCS: $Log: d_msem_lck.U,v $
```

```
?MAKE:d_msem_lck: Inlibc
```

```
?MAKE: -pick add $@ %<
```

```
?S:d_msem_lck:
```

```
?S: This variable conditionally defines HAS_MSEM_LOCK if msem_lock() is
```

```
?S: available, thereby indicating kernel support for memory semaphores.
```

```
?S:.
```

```
?C:HAS_MSEM_LOCK:
```

```
?C: This symbol, if defined, indicates that memory semaphores are
```

```
?C: available to protect mmap()'ed regions.
```

```
?C:.
```

```
?H:#$d_msem_lck HAS_MSEM_LOCK /**/
```

```
?H:.
```

```
?LINT:set d_msem_lck
```

```
: see if msem_lock exists
```

```
set
```

```
  msem_lock d_msem_lck
```

```
eval $inlibc
```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/d_msem_lck.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: d_strerror_r.U,v 0RCS:
?RCS: Copyright (c) 2002,2003 Jarkko Hietaniemi
?RCS:
?RCS: You may distribute under the terms of either the GNU General Public
?RCS: License or the Artistic License, as specified in the README file.
?RCS:
?RCS: Generated by the reentr.pl from the Perl 5.8 distribution.
?RCS:
?MAKE:d_strerror_r strerror_r_proto: Inlibc Protochk Hasproto i_systypes \
  usethreads i_string extern_C
?MAKE: -pick add $@ %<
?S:d_strerror_r:
?S: This variable conditionally defines the HAS_STRERROR_R symbol,
?S: which indicates to the C program that the strerror_r()
?S: routine is available.
?S:.
?S:strerror_r_proto:
?S: This variable encodes the prototype of strerror_r.
?S: It is zero if d_strerror_r is undef, and one of the
?S: REENTRANT_PROTO_T_ABC macros of reentr.h if d_strerror_r
?S: is defined.
?S:.
?C:HAS_STRERROR_R:
?C: This symbol, if defined, indicates that the strerror_r routine
?C: is available
?C: to strerror re-entrantly.
?C:.
?C:STRERROR_R_PROTO:
?C: This symbol encodes the prototype of strerror_r.
?C: It is zero if d_strerror_r is undef, and one of the
?C: REENTRANT_PROTO_T_ABC macros of reentr.h if d_strerror_r
?C: is defined.
?C:.
?H:#$d_strerror_r HAS_STRERROR_R /**/
?H:#define STRERROR_R_PROTO $strerror_r_proto /**/
?H:.
?T:try hdrs d_strerror_r_proto
: see if strerror_r exists
set strerror_r d_strerror_r
eval $inlibc
case "$d_strerror_r" in
"$define")
hdrs="$i_systypes sys/types.h define stdio.h $i_string string.h"
case "$d_strerror_r_proto:$usethreads" in
":define") d_strerror_r_proto=define
set d_strerror_r_proto strerror_r $hdrs
```

```

eval $hasproto ;;
*) ;;
esac
case "$d_strerror_r_proto" in
define)
case "$strerror_r_proto" in
"|0) try='int strerror_r(int, char*, size_t);'
./protochk "$extern_C $try" $hdrs && strerror_r_proto=I_IBW ;;
esac
case "$strerror_r_proto" in
"|0) try='int strerror_r(int, char*, int);'
./protochk "$extern_C $try" $hdrs &&
strerror_r_proto=I_IBI ;;
esac
case "$strerror_r_proto" in
"|0) try='char* strerror_r(int, char*, size_t);'
./protochk "$extern_C $try" $hdrs && strerror_r_proto=B_IBW ;;
esac
case "$strerror_r_proto" in
"|0) d_strerror_r=undef
strerror_r_proto=0
echo "Disabling strerror_r, cannot determine prototype." >&4 ;;
* ) case "$strerror_r_proto" in
REENTRANT_PROTO*) ;;
*) strerror_r_proto="REENTRANT_PROTO_${strerror_r_proto}" ;;
esac
echo "Prototype: $try" ;;
esac
;;
*) case "$usethreads" in
define) echo "strerror_r has no prototype, not using it." >&4 ;;
esac
d_strerror_r=undef
strerror_r_proto=0
;;
esac
;;
*) strerror_r_proto=0
;;
esac

```

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/threads/d_strerror_r.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: d_times.U,v \$

?RCS: Revision 3.0.1.2 1995/07/25 14:07:50 ram

?RCS: patch56: typo fix, sytem -> system

?RCS:

?RCS: Revision 3.0.1.1 1994/08/29 16:14:00 ram

?RCS: patch32: now uses new Typedef unit to compute type information

?RCS:

?RCS: Revision 3.0 1993/08/18 12:07:46 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?X:

?X: What is the type returned by times() ?

?X:

?X: Force inclusion of <sys/types.h>

?X:INC: i_systypes

?MAKE:d_times clocktype: Csym Myread Typedef i_systimes

?MAKE: -pick

add \$@ %<

?S:d_times:

?S: This variable conditionally defines the HAS_TIMES symbol, which indicates
?S: that the times() routine exists. The times() routine is normally
?S: provided on UNIX systems. You may have to include <sys/times.h>.

?S:.

?S:clocktype:

?S: This variable holds the type returned by times(). It can be long,
?S: or clock_t on BSD sites (in which case <sys/types.h> should be
?S: included).

?S:.

?C:HAS_TIMES (TIMES):

?C: This symbol, if defined, indicates that the times() routine exists.
?C: Note that this became obsolete on some systems (SUNOS), which now
?C: use getrusage(). It may be necessary to include <sys/times.h>.

?C:.

?C:Clock_t (CLOCKTYPE):

?C: This symbol holds the type returned by times(). It can be long,
?C: or clock_t on BSD sites (in which case <sys/types.h> should be
?C: included).

?C:.

?H:#\$d_times HAS_TIMES /**/
?H:#define Clock_t \$clocktype /* Clock time */

```

?H:
?T:val inc
: see if times exists
echo " "
if set times val -f d_times; eval $csym;
$val; then
echo 'times() found.' >&4
d_times="$define"
inc="
case "$i_systimes" in
"$define") inc='sys/times.h';
esac
set clock_t clocktype long stdio.h sys/types.h $inc
eval $typedef
dflt="$clocktype"
echo " "
rp="What type is returned by times() on this system?"
./myread
clocktype="$ans"
else
echo 'times() NOT found, hope that will do.' >&4
d_times="$undef"
?X: The following is needed for typedef (won't like an empty variable)
clocktype='int'
fi

```

Found in path(s):

```

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/d_times.U

```

No license file was found, but licenses were detected in source scan.

```

?RCS: $Id: d_usleep.U 1 2006-08-24 12:32:52Z rmanfredi $
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: $Log: d_usleep.U,v $
?RCS: Revision 3.0 1993/08/18 12:07:53 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:d_usleep: Inlibc
?MAKE: -pick add $@ %<
?S:d_usleep:

```

?S: This variable conditionally defines HAS_USLEEP if usleep() is

?S: available to do high granularity sleeps.

?S:.

?C:HAS_USLEEP (USLEEP):

?C: This symbol, if defined, indicates that the usleep routine is

?C: available to let the process sleep on a sub-second accuracy.

?C:.

?H:#\$d_usleep

```
HAS_USLEEP /**/
```

?H:.

?LINT:set d_usleep

: see if usleep exists

set usleep d_usleep

eval \$inlibc

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-  
debian-perl-5.26.1/dist/U/d_usleep.U
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: i_systable.U 1 2006-08-24 12:32:52Z rmanfredi \$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic Licence,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic Licence; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: i_systable.U,v \$

?RCS: Revision 3.0.1.1 1993/10/16 13:50:20 ram

?RCS: patch12: created

?RCS:

?RCS:

?MAKE:i_systable: Inhdr

?MAKE: -pick add \$@ %<

?S:i_systable:

?S: This variable conditionally defines the I_SYS_TABLE symbol, and

?S: indicates whether a C program should include <sys/table.h>.

?S:.

?C:I_SYS_TABLE:

?C: This symbol, if defined, indicates to the C program that it should

?C: include <sys/table.h> for the OSF/1 table() system call.

?C:.

?H:#\$i_systable

```
I_SYS_TABLE /**/
```

?H:.

```
?LINT:set i_systable
: see if this is an OSF sys/table system
set sys/table.h i_systable
eval $inhdr
```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/i_systable.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: d_srand48_r.U,v 0RCS:
```

```
?RCS: Copyright (c) 2002,2003 Jarkko Hietaniemi
```

```
?RCS:
```

```
?RCS: You may distribute under the terms of either the GNU General Public
```

```
?RCS: License or the Artistic License, as specified in the README file.
```

```
?RCS:
```

```
?RCS: Generated by the reentr.pl from the Perl 5.8 distribution.
```

```
?RCS:
```

```
?MAKE:d_srand48_r srand48_r_proto: Inlibc Protochk Hasproto i_systypes \
  usethreads i_stdlib extern_C
```

```
?MAKE: -pick add $@ %<
```

```
?S:d_srand48_r:
```

```
?S: This variable conditionally defines the HAS_SRAND48_R symbol,
```

```
?S: which indicates to the C program that the srand48_r()
```

```
?S: routine is available.
```

```
?S:.
```

```
?S:srand48_r_proto:
```

```
?S: This variable encodes the prototype of srand48_r.
```

```
?S: It is zero if d_srand48_r is undef, and one of the
```

```
?S: REENTRANT_PROTO_T_ABC macros of reentr.h if d_srand48_r
```

```
?S: is defined.
```

```
?S:.
```

```
?C:HAS_SRAND48_R:
```

```
?C: This symbol, if defined, indicates that the srand48_r routine
```

```
?C: is available to srand48 re-entrantly.
```

```
?C:.
```

```
?C:SRAND48_R_PROTO:
```

```
?C: This
```

```
symbol encodes the prototype of srand48_r.
```

```
?C: It is zero if d_srand48_r is undef, and one of the
```

```
?C: REENTRANT_PROTO_T_ABC macros of reentr.h if d_srand48_r
```

```
?C: is defined.
```

```
?C:.
```

```
?H:#$d_srand48_r HAS_SRAND48_R /**/
```

```
?H:#define SRAND48_R_PROTO $srand48_r_proto /**/
```

```
?H:.
```

```
?T:try hdrs d_srand48_r_proto
```

```
: see if srand48_r exists
```

```

set srand48_r d_srand48_r
eval $inlibc
case "$d_srand48_r" in
"$define")
hdrs="$i_systypes sys/types.h define stdio.h $i_stdlib stdlib.h"
case "$d_srand48_r_proto:$usethreads" in
":define") d_srand48_r_proto=define
set d_srand48_r_proto srand48_r $hdrs
eval $hasproto ;;
*) ;;
esac
case "$d_srand48_r_proto" in
define)
case "$srand48_r_proto" in
"|0) try='int srand48_r(long, struct drand48_data*);'
./protochk "$extern_C $try" $hdrs && srand48_r_proto=I_LS ;;
esac
case "$srand48_r_proto" in
"|0) d_srand48_r=undef
srand48_r_proto=0
echo "Disabling srand48_r, cannot determine prototype." >&4
;;
* ) case "$srand48_r_proto" in
REENTRANT_PROTO*) ;;
*) srand48_r_proto="REENTRANT_PROTO_$$srand48_r_proto" ;;
esac
echo "Prototype: $try" ;;
esac
;;
*) case "$usethreads" in
define) echo "srand48_r has no prototype, not using it." >&4 ;;
esac
d_srand48_r=undef
srand48_r_proto=0
;;
esac
;;
*) srand48_r_proto=0
;;
esac

```

Found in path(s):

```

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/threads/d_srand48_r.U

```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1996, Andy Dougherty
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: \$Log: man3dir.U,v \$
?RCS: Revision 3.0.1.1 1997/02/28 16:10:34 ram
?RCS: patch61: created
?RCS:
?X:
?X: This was originally specific to perl5. Since perl5 has man pages that
?X: go in both man1/ and man3/ directories, we need both man1dir
?X: and man3dir. This unit is basically dist's mansrc.U with
?X: man3 used instead of man everywhere.
?X: I then added various tests because perl5 has *lots* of man3
?X: pages with long file names. -- ADO
?X:
?MAKE:man3dir
man3direxp man3ext installman3dir: afs cat nroff Loc Oldconfig \
sed man1dir spackage package Getfile prefix Prefixit Prefixup \
d_flexfnam privlib Myread
?MAKE: -pick add \$@ %<
?Y:TOP
?S:man3dir:
?S: This variable contains the name of the directory in which manual
?S: source pages are to be put. It is the responsibility of the
?S: Makefile.SH to get the value of this into the proper command.
?S: You must be prepared to do the ~name expansion yourself.
?S:.
?S:man3direxp:
?S: This variable is the same as the man3dir variable, but is filename
?S: expanded at configuration time, for convenient use in makefiles.
?S:.
?S:installman3dir:
?S: This variable is really the same as man3direxp, unless you are using
?S: AFS in which case it points to the read/write location whereas
?S: man3direxp only points to the read-only access location. For extra
?S: portability, you should only use this variable within your makefiles.
?S:.
?S:man3ext:
?S: This variable contains the extension that the manual
page should
?S: have: one of 'n', 'l', or '3'. The Makefile must supply the '!'.
?S: See man3dir.

?S:.

: determine where library module manual pages go

```
set man3dir man3dir none
```

```
eval $prefixit
```

```
$cat <<EOM
```

\$spackage has manual pages for many of the library modules.

```
EOM
```

```
case "$nroff" in
```

```
nroff)
```

```
$cat <<'EOM'
```

However, you don't have nroff, so they're probably useless to you.

```
EOM
```

```
case "$man3dir" in
```

```
") man3dir="none";;
```

```
esac;;
```

```
esac
```

```
case "$d_flexfnam" in
```

```
undef)
```

```
$cat <<'EOM'
```

However, your system can't handle the long file names like File::Basename.3.

```
EOM
```

```
case "$man3dir" in
```

```
") man3dir="none";;
```

```
esac;;
```

```
esac
```

```
echo "If you don't want the manual sources installed, answer 'none'."
```

```
?X: We dont use /usr/local/man/man3 because some man programs will
```

```
?X: only show the /usr/local/man/man3 contents, and not the system ones,
```

```
?X: thus man less will show the perl module less.pm, but not the system
```

```
?X: less command. We might also conflict with TCL man pages.
```

```
?X: However, something like /opt/perl/man/man3
```

```
is fine.
```

```
case "$man3dir" in
```

```
") case "$prefix" in
```

```
*$package*) dflt=`echo $man1dir |
```

```
$sed -e 's/man1/man3/g' -e 's/man\./man\./3/g'` ;;
```

```
*) dflt="$privlib/man/man3" ;;
```

```
esac
```

```
;;
```

```
' ') dflt=none;;
```

```
*) dflt="$man3dir" ;;
```

```
esac
```

```
echo " "
```

```

fn=dn+~
rp="Where do the $package library man pages (source) go?"
./getfile
if test "X$man3direxp" != "X$ansexp"; then
installman3dir="
fi

man3dir="$ans"
man3direxp="$ansexp"
case "$man3dir" in
") man3dir=' '
installman3dir="";;
esac
if $afs; then
$cat <<EOM

```

Since you are running AFS, I need to distinguish the directory in which manual pages reside from the directory in which they are installed (and from which they are presumably copied to the former directory by occult means).

```

EOM
case "$installman3dir" in
") dflt=`echo $man3direxp | sed 's#^/afs/#/afs/.#`";;
*) dflt="$installman3dir";;
esac
fn=de~
rp='Where will man pages be installed?'
./getfile
installman3dir="$ans"
else
installman3dir="$man3direxp"
fi

```

: What suffix
to use on installed man pages

```

case "$man3dir" in
')
man3ext='0'
;;
*)
rp="What suffix should be used for the $package library man pages?"
case "$man3ext" in
") case "$man3dir" in
*3) dflt=3 ;;
*3p) dflt=3p ;;
*3pm) dflt=3pm ;;
*1) dflt=1;;

```

```

*n) dflt=n;;
*o) dflt=o;;
*p) dflt=p;;
*C) dflt=C;;
*L) dflt=L;;
*L3) dflt=L3;;
*) dflt=3;;
esac
;;
*) dflt="$man3ext";;
esac
./myread
man3ext="$ans"
;;
esac

```

Found in path(s):

```

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/man3dir.U

```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 2001 Jarkko Hietaniemi

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?MAKE:d_strftime: Inlibc

?MAKE: -pick add \$@ %<

?S:d_strftime:

?S: This variable conditionally defines the HAS_STRFTIME symbol, which

?S: indicates to the C program that the strftime() routine is available.

?S:.

?C:HAS_STRFTIME:

?C: This symbol, if defined, indicates that the strftime routine is

?C: available to do time formatting.

?C:.

?H:#\$d_strftime HAS_STRFTIME /**/

?H:.

?LINT:set d_strftime

: see if strftime exists

set strftime d_strftime

eval \$inlibc

Found in path(s):

```

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/perl/d_strftime.U

```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id$
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: $Log: d_strftime.U,v $
?RCS: Revision 3.0 1993/08/18 12:07:36 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:d_strftime: Inlibc
?MAKE: -pick add $@ %<
?S:d_strftime:
?S: This variable conditionally defines HAS_STRFTIME if strftime() is
?S: available to format locale-specific times.
?S:.
?C:HAS_STRFTIME:
?C: This symbol, if defined, indicates that the strftime routine is
?C: available to format locale-specific times.
?C:.
?H:#$d_strftime HAS_STRFTIME /**/
?H:.
?LINT:set d_strftime
: see
if strftime exists
set strftime d_strftime
eval $inlibc
```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/d_strftime.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id$
?RCS:
?RCS: Copyright (c) 1999, Jarkko Hietaniemi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 3.0.
```

```

?RCS:
?MAKE:d_sched_get_priority_max: Inlibc
?MAKE: -pick add $@ %<
?S:d_sched_get_priority_max:
?S: This variable conditionally defines HAS_SCHED_GET_PRIORITY_MAX if
?S: sched_get_priority_max() is available to get the maximum scheduling
?S: priority.
?S:.
?C:HAS_SCHED_GET_PRIORITY_MAX:
?C: This symbol, if defined, indicates that the sched_get_priority_max
?C: system call is available to get the maximum scheduling priority.
?C:.
?H:#$d_sched_get_priority_max HAS_SCHED_GET_PRIORITY_MAX /**/
?H:.
?LINT:set d_sched_get_priority_max
:
  see if sched_get_priority_max exists
  set sched_get_priority_max d_sched_get_priority_max
  eval $inlibc

```

Found in path(s):

```

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/perl/d_sched_gpmax.U

```

No license file was found, but licenses were detected in source scan.

```

?RCS: $Id: xs_apiversion.U $
?RCS:
?RCS: Copyright (c) 1999 Andy Dougherty
?RCS:
?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 3.0.
?RCS:
?RCS: $Log: xs_apiversion.U,v $
?RCS:
?MAKE:xs_apiversion pm_apiversion: version
?MAKE: -pick add $@ %<
?S:xs_apiversion:
?S: This variable contains the version of the oldest perl binary
?S: compatible with the present perl. perl.c:incpush() and
?S: lib/lib.pm will automatically search in $sitearch for older
?S: directories across major versions back to xs_apiversion.
?S: This is only useful if you have a perl library directory tree
?S: structured like the default one.
?S: See INSTALL for how this works.
?S: The

```

versioned site_perl directory was introduced in 5.005,

?S: so that is the lowest possible value.

?S: Since this can depend on compile time options

?S: it is set by Configure. Other non-default sources

?S: of potential incompatibility, such as multiplicity, threads,

?S: debugging, 64bits, sfio, etc., are not checked for currently,

?S: though in principle we could go snooping around in old

?S: Config.pm files.

?S:.

?S:pm_apiversion:

?S: This variable contains the version of the oldest perl

?S: compatible with the present perl. (That is, pure perl modules

?S: written for \$pm_apiversion will still work for the current

?S: version). perl.c:incpush() and lib/lib.pm will automatically

?S: search in \$sitelib for older directories across major versions

?S: back to pm_apiversion. This is only useful if you have a perl

?S: library directory tree structured like the default one. The

?S: versioned site_perl library was introduced in 5.005, so that's

?S: the default setting for this variable.

It's hard to imagine

?S: it changing before Perl6. It is included here for symmetry

?S: with xs_apiveprSION -- the searching algorithms will

?S: (presumably) be similar.

?S: See the INSTALL file for how this works.

?S:.

?C:PERL_XS_APIVERSION:

?C: This variable contains the version of the oldest perl binary

?C: compatible with the present perl. perl.c:incpush() and

?C: lib/lib.pm will automatically search in \$sitearch for older

?C: directories across major versions back to xs_apiversion.

?C: This is only useful if you have a perl library directory tree

?C: structured like the default one.

?C: See INSTALL for how this works.

?C: The versioned site_perl directory was introduced in 5.005,

?C: so that is the lowest possible value.

?C: Since this can depend on compile time options

?C: it is set by Configure. Other non-default sources

?C: of potential incompatibility, such as multiplicity, threads,

?C: debugging, 64bits, sfio, etc., are not checked for currently,

?C: though in principle

we could go snooping around in old

?C: Config.pm files.

?C:.

?C:PERL_PM_APIVERSION:

?C: This variable contains the version of the oldest perl

?C: compatible with the present perl. (That is, pure perl modules

?C: written for pm_apiversion will still work for the current

?C: version). perl.c:incpush() and lib/lib.pm will automatically

?C: search in \$sitelib for older directories across major versions
?C: back to pm_apiversion. This is only useful if you have a perl
?C: library directory tree structured like the default one. The
?C: versioned site_perl library was introduced in 5.005, so that's
?C: the default setting for this variable. It's hard to imagine
?C: it changing before Perl6. It is included here for symmetry
?C: with xs_apiveprsion -- the searching algorithms will
?C: (presumably) be similar.
?C: See the INSTALL file for how this works.

?C:.

?H:#define PERL_XS_APIVERSION "\$xs_apiversion"

?H:#define PERL_PM_APIVERSION "\$pm_apiversion"

?H:.

: Find earliest binary compatible

site_perl subdirectory perl can use.

xs_apiversion=\$version # The current site_perl version.

: Find earliest pure perl site_perl subdirectory perl can use.

: The versioned directories started at 5.005.

pm_apiversion='5.005'

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/xs_apiversion.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_strerror.U,v 3.0.1.3 1994/05/13 15:20:27 ram Exp \$

?RCS:

?RCS: Copyright (c) 1991-1993, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 3.0.

?RCS:

?RCS: \$Log: d_strerror.U,v \$

?RCS: Revision 3.0.1.3 1994/05/13 15:20:27 ram

?RCS: patch27: now uses new macro support for cleaner Strerror def

?RCS:

?RCS: Revision 3.0.1.2 1994/05/06 14:58:26 ram

?RCS: patch23: renamed strerror into Strerror to protect name space (ADO)

?RCS:

?RCS: Revision 3.0.1.1 1994/01/24 14:08:56 ram

?RCS: patch16: protected code looking for sys_errnolist[] with @if

?RCS: patch16: added default value for d_sysernlst

?RCS:

?RCS: Revision

3.0 1993/08/18 12:07:35 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?MAKE:d_strerror d_syserrlst d_sysernlst d_strerrorm: contains Csym Findhdr

?MAKE: -pick add \$@ %<

?S:d_strerror:

?S: This variable conditionally defines HAS_STRERROR if strerror() is

?S: available to translate error numbers to strings.

?S:.

?S:d_syserrlst:

?S: This variable conditionally defines HAS_SYS_ERRLIST if sys_errlist[] is

?S: available to translate error numbers to strings.

?S:.

?S:d_sysernlst:

?S: This variable conditionally defines HAS_SYS_ERRNOLIST if sys_errnolist[]

?S: is available to translate error numbers to the symbolic name.

?S:.

?S:d_strerrorm:

?S: This variable holds what Strerror is defined as to translate an error

?S: code condition into an error message string. It could be 'strerror'

?S: or a more complex macro emulating strerror with sys_errlist[], or the

?S: "unknown" string when both strerror and sys_errlist are missing.

?S:.

?C:HAS_STRERROR (STRERROR):

?C: This symbol, if defined,

indicates that the strerror routine is

?C: available to translate error numbers to strings. See the writeup

?C: of Strerror() in this file before you try to define your own.

?C:.

?C:HAS_SYS_ERRLIST (SYSERRLIST):

?C: This symbol, if defined, indicates that the sys_errlist array is

?C: available to translate error numbers to strings. The extern int

?C: sys_nerr gives the size of that table.

?C:.

?C:HAS_SYS_ERRNOLIST (SYSERRNOLIST):

?C: This symbol, if defined, indicates that the sys_errnolist array is

?C: available to translate an errno code into its symbolic name (e.g.

?C: ENOENT). The extern int sys_nerrno gives the size of that table.

?C:.

?C:Strerror:

?C: This preprocessor symbol is defined as a macro if strerror() is

?C: not available to translate error numbers to strings but sys_errlist[]

?C: array is there.

?C:.

?H:#\$d_strerror HAS_STRERROR /**/

?H:#\$d_syserrlst HAS_SYS_ERRLIST /**/

?H:#\$d_sysernlst HAS_SYS_ERRNOLIST /**/

?H:#define Strerror(e) \$d_strerrorm

```

?H:
?D:d_syserrlst="
?T:xxx
val
: see if strerror and/or sys_errlist[] exist
echo " "
?X: MPE/iX needs this protection of hint values.
?X: Background: strerror exists in kernel but not in libc.
?X: Scanning the kernel for symbols would be a bad idea, however,
?X: because many symbols that look unix-ish exist in the kernel.
?X: The stress is on the 'look'.
?X: --jhi 9/1998
if test "X$d_strerror" = X -o "X$d_syserrlst" = X; then
    if set strerror val -f d_strerror; eval $csym; $val; then
        echo 'strerror() found.' >&4
        d_strerror="$define"
        d_strerrorrm='strerror(e)'
        if set sys_errlist val -a d_syserrlst; eval $csym; $val; then
            echo "(You also have sys_errlist[], so we could roll our own strerror.)"
            d_syserrlst="$define"
        else
            echo "(Since you don't have sys_errlist[], strerror() is welcome.)"
            d_syserrlst="$undef"
        fi
        elif xxx=`./findhdr string.h`; test "$xxx" || xxx=`./findhdr strings.h`; \
        $contains '#[ ]*define.*strerror' "$xxx" >/dev/null 2>&1; then
            echo 'strerror() found in
string header.' >&4
            d_strerror="$define"
            d_strerrorrm='strerror(e)'
            if set sys_errlist val -a d_syserrlst; eval $csym; $val; then
                echo "(Most probably, strerror() uses sys_errlist[] for descriptions.)"
                d_syserrlst="$define"
            else
                echo "(You don't appear to have any sys_errlist[], how can this be?)"
                d_syserrlst="$undef"
            fi
            elif set sys_errlist val -a d_syserrlst; eval $csym; $val; then
                echo "strerror() not found, but you have sys_errlist[] so we'll use that." >&4
                d_strerror="$undef"
                d_syserrlst="$define"
                d_strerrorrm='((e)<0||e)>=sys_nerr?"unknown":sys_errlist[e]}'
            else
                echo 'strerror() and sys_errlist[] NOT found.' >&4
                d_strerror="$undef"
                d_syserrlst="$undef"
                d_strerrorrm=""unknown""
            fi

```

```

fi
@if d_sysernlst || HAS_SYS_ERRNOLIST
if set sys_errnolist val -a d_sysernlst; eval $scsym; $val; then
echo "(Symbolic error codes can be fetched via the sys_errnolist[] array.)"
d_sysernlst="$define"
else
echo "(However, I can't extract the symbolic error code
out of errno.)"
d_sysernlst="$undef"
fi
@end

```

Found in path(s):

```

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/modified/d_streerror.U

```

No license file was found, but licenses were detected in source scan.

```

?RCS: $Id: sig_name.U 1 2006-08-24 12:32:52Z rmanfredi $
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: $Log: sig_name.U,v $
?RCS: Revision 3.0.1.5 1997/02/28 16:21:25 ram
?RCS: patch61: brand new algorithm for sig_name and (new!) sig_num
?RCS:
?RCS: Revision 3.0.1.4 1995/07/25 14:14:54 ram
?RCS: patch56: added <asm/signal.h> lookup for Linux
?RCS:
?RCS: Revision 3.0.1.3 1995/05/12 12:24:11 ram
?RCS: patch54: now looks for <linux/signal.h> too (ADO)
?RCS:
?RCS: Revision 3.0.1.2 1994/06/20 07:06:57 ram
?RCS: patch30: final echo was missing to close
awk-printed string
?RCS:
?RCS: Revision 3.0.1.1 1994/05/06 15:17:55 ram
?RCS: patch23: signal list now formatted to avoid scroll-ups (ADO)
?RCS:
?RCS: Revision 3.0 1993/08/18 12:09:47 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:sig_name sig_name_init sig_num sig_num_init sig_count sig_size: \

```

awk Signal Oldconfig rm

?MAKE: -pick add \$@ %<

?S:sig_name:

?S: This variable holds the signal names, space separated. The leading

?S: SIG in signal name is removed. A ZERO is prepended to the list.

?S: This is currently not used, sig_name_init is used instead.

?S:.

?S:sig_name_init:

?S: This variable holds the signal names, enclosed in double quotes and

?S: separated by commas, suitable for use in the SIG_NAME definition

?S: below. A "ZERO" is prepended to the list, and the list is

?S: terminated with a plain 0. The leading SIG in signal names

?S: is removed. See sig_num.

?S:.

?S:sig_num:

?S: This variable holds the signal numbers, space separated. A ZERO is

?S: prepended

to the list (corresponding to the fake SIGZERO).

?S: Those numbers correspond to the value of the signal listed

?S: in the same place within the sig_name list.

?S: This is currently not used, sig_num_init is used instead.

?S:.

?S:sig_num_init:

?S: This variable holds the signal numbers, enclosed in double quotes and

?S: separated by commas, suitable for use in the SIG_NUM definition

?S: below. A "ZERO" is prepended to the list, and the list is

?S: terminated with a plain 0.

?S:.

?S:sig_count (sig_name.U):

?S: This variable holds a number larger than the largest valid

?S: signal number. This is usually the same as the NSIG macro.

?S:.

?S:sig_size:

?S: This variable contains the number of elements of the sig_name

?S: and sig_num arrays.

?S:.

?C:SIG_NAME:

?C: This symbol contains a list of signal names in order of

?C: signal number. This is intended

?C: to be used as a static array initialization, like this:

?C: char *sig_name[] = { SIG_NAME };

?C: The signals in the list are

separated with commas, and each signal

?C: is surrounded by double quotes. There is no leading SIG in the signal

?C: name, i.e. SIGQUIT is known as "QUIT".

?C: Gaps in the signal numbers (up to NSIG) are filled in with NUMnn,

?C: etc., where nn is the actual signal number (e.g. NUM37).

?C: The signal number for sig_name[i] is stored in sig_num[i].

?C: The last element is 0 to terminate the list with a NULL. This
?C: corresponds to the 0 at the end of the sig_name_init list.
?C: Note that this variable is initialized from the sig_name_init,
?C: not from sig_name (which is unused).
?C:.
?C:SIG_NUM:
?C: This symbol contains a list of signal numbers, in the same order as the
?C: SIG_NAME list. It is suitable for static array initialization, as in:
?C: int sig_num[] = { SIG_NUM };
?C: The signals in the list are separated with commas, and the indices
?C: within that list and the SIG_NAME list match, so it's easy to compute
?C: the signal name from a number or vice versa at the price of
a small
?C: dynamic linear lookup.
?C: Duplicates are allowed, but are moved to the end of the list.
?C: The signal number corresponding to sig_name[i] is sig_number[i].
?C: if (i < NSIG) then sig_number[i] == i.
?C: The last element is 0, corresponding to the 0 at the end of
?C: the sig_name_init list.
?C: Note that this variable is initialized from the sig_num_init,
?C: not from sig_num (which is unused).
?C:.
?C:SIG_COUNT:
?C: This variable contains a number larger than the largest
?C: signal number. This is usually the same as the NSIG macro.
?C:.
?C:SIG_SIZE:
?C: This variable contains the number of elements of the SIG_NAME
?C: and SIG_NUM arrays, excluding the final NULL entry.
?C:.
?H:#define SIG_NAME \$sig_name_init /**/
?H:#define SIG_NUM \$sig_num_init /**/
?H:#define SIG_COUNT \$sig_count /**/
?H:#define SIG_SIZE \$sig_size /**/
?H:.
?T:i doinit
?F:!= !signal_cmd
?X: signal.cmd creates a file signal.lst which has two columns:
?X: NAME number, e.g.
?X: HUP 1
?X: The list
is sorted on signal number, with duplicates moved to
?X: the end..
: generate list of signal names
case "\$sig_num_init" in
")
echo " "
case "\$sig_name_init" in

```

") doinit=yes ;;
*) case "$sig_num_init" in
  |*,*) doinit=yes ;;
  esac ;;
esac
case "$doinit" in
yes)
echo "Generating a list of signal names and numbers..." >&4
. ./signal_cmd
sig_count=`$awk '/^NSIG/ { printf "%d", $2 }' signal.lst`
sig_name=`$awk 'BEGIN { printf "ZERO " }
  !/^NSIG/ { printf "%s ", $1 }' signal.lst`
sig_num=`$awk 'BEGIN { printf "0 " }
  !/^NSIG/ { printf "%d ", $2 }' signal.lst`
sig_name_init=`$awk 'BEGIN { printf "\"ZERO\", " }
  !/^NSIG/ { printf "\"%s\", ", $1 }
  END { printf "0\n" }' signal.lst`
sig_num_init=`$awk 'BEGIN { printf "0, " }
  !/^NSIG/ { printf "%d, ", $2 }
  END { printf "0\n" }' signal.lst`
;;
esac
echo "The following $sig_count signals are available:"
echo " "
echo $sig_name | $awk \
'BEGIN { linelen = 0 }
{
for (i = 1; i <= NF;
i++) {
name = "SIG" $i " "
linelen = linelen + length(name)
if (linelen > 70) {
printf "\n"
linelen = length(name)
}
printf "%s", name
}
printf "\n"
}'
sig_size=`echo $sig_name | awk '{print NF}'`
$rm -f signal signal.c signal.awk signal.lst signal_cmd
;;
esac

```

Found in path(s):

```

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/modified/sig_name.U

```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: libnlist.U 1 2006-08-24 12:32:52Z rmanfredi $
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: $Log: libnlist.U,v $
?RCS: Revision 3.0.1.1 1997/02/28 16:08:02 ram
?RCS: patch61: added usrinc and mips on the dependency line
?RCS: patch61: make sure we call ./mips
?RCS: patch61: added a ?LINT: hint
?RCS:
?RCS: Revision 3.0 1993/08/18 12:09:00 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:libnlist: Loc libpth Guess usrinc _a
?MAKE: -pick add $@ %<
?S:libnlist (libmld):
?S: This variable contains the name of the library required to
get the
?S: definition of the nlist() function. On a MIPS RISC/OS box, it is -lml.
?S: Under Sys Vr4, it is -lelf. Otherwise, its value is empty.
?S:.
?T:xxx
?LINT:use usrinc
: see if we need a special library for 'nlist()'
echo " "
: How about doing this if nlist is not in libc...
if ./mips ; then
libnlist='-lml'
else
xxx=`./loc libelf$_a x $libpth`
case "$xxx" in
x) ;;
*)
libnlist="$xxx"
;;
esac
fi
case "$libnlist" in
") echo "No special library for nlist() seems necessary." >&4
;;
```

```
*) echo "nlist() can be found in $libnlist." >&4
```

```
::
```

```
esac
```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/libnlist.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id$
```

```
?RCS:
```

```
?RCS: Copyright (c) 1999 Jarkko Hietaniemi
```

```
?RCS:
```

```
?RCS: You may distribute under the terms of either the GNU General Public
```

```
?RCS: License or the Artistic License, as specified in the README file.
```

```
?RCS:
```

```
?MAKE:d_getmnt: Inlibc
```

```
?MAKE: -pick add $@ %<
```

```
?S:d_getmnt:
```

```
?S: This variable conditionally defines the HAS_GETMNT symbol, which
```

```
?S: indicates to the C program that the getmnt() routine is available
```

```
?S: to retrieve one or more mount info blocks by filename.
```

```
?S:.
```

```
?C:HAS_GETMNT:
```

```
?C: This symbol, if defined, indicates that the getmnt routine is
```

```
?C: available to get filesystem mount info by filename.
```

```
?C:.
```

```
?H:#$d_getmnt HAS_GETMNT /**/
```

```
?H:.
```

```
?LINT:set d_getmnt
```

```
: see if getmnt exists
```

```
set getmnt d_getmnt
```

```
eval $inlibc
```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_getmnt.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id$
```

```
?RCS:
```

```
?RCS: Copyright (c) 1999, Jarkko Hietaniemi
```

```
?RCS:
```

```
?RCS: You may redistribute only under the terms of the Artistic License,
```

```
?RCS: as specified in the README file that comes with the distribution.
```

```
?RCS: You may reuse parts of this distribution only within the terms of
```

```
?RCS: that same Artistic License; a copy of which may be found at the root
```

```
?RCS: of the source tree for dist 3.0.
```

?RCS:
?MAKE:d_sem_destroy: Inlibc
?MAKE: -pick add \$@ %<
?S:d_sem_destroy:
?S: This variable conditionally defines HAS_SEM_DESTROY if sem_destroy() is
?S: available to destroy a POSIX semaphore.
?S:.
?C:HAS_SEM_DESTROY:
?C: This symbol, if defined, indicates that the sem_destroy system call is
?C: available to destroy a POSIX semaphore.
?C:.
?H:#\$d_sem_destroy HAS_SEM_DESTROY /**/
?H:.
?LINT:set d_sem_destroy
: see if sem_destroy exists
set sem_destroy d_sem_destroy
eval \$inlibc

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_sem_destroy.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: \$Log: d_NOFILE.U,v \$
?RCS: Revision 3.0.1.1 1994/10/29 16:08:38 ram
?RCS: patch36: added ?F: line for metalint file checking
?RCS:
?RCS: Revision 3.0 1993/08/18 12:05:39 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:nofile d_gettblsz tablesize: Myread Guess cat +cc +ccflags +libs \
test rm Csym
?MAKE: -pick add \$@ %<
?S:nofile:
?S: This variable contains the number of file descriptors available to the
?S: process.
?S:.
?S:d_gettblsz:

?S: This variable conditionally handles remapping of the getdtablesize() of the getdtablesize() subroutine to ulimit(4,0), or the NOFILE manifest constant.

?S:.

?S:tablesize:

?S: This variable contains either the 'NOFILE' constant or 'ulimit(4, 0L)' and is used as the remapped value for the getdtablesize() macro.

?S:.

?C:getdtablesize:

?C: This catches use of the getdtablesize() subroutine, and remaps it to either ulimit(4,0) or NOFILE, if getdtablesize() isn't available.

?C:.

?C:VAL_NOFILE:

?C: This symbol contains the number of file descriptors available to the process, as determined at configuration time. Unless a static constant is needed, you should rely on getdtablesize() to obtain that number.

?C:.

?H:#\$d_gettblsz getdtablesize() \$tablesize /**/
?H:#define VAL_NOFILE \$nofile /* Number of file descriptors */

?H:.

?F:!nofile

?T:d_ulimit4 val

: see if getdtablesize exists

echo " "

?X: Revert logical value (d_gettblsz is undef iff getdtablesize is present)

```

case "$d_gettblsz" in
$define) d_gettblsz="$undef";;
$undef) d_gettblsz="$define";;
esac
if
set getdtablesize val -f d_gettblsz; eval $csym; $val; then
echo 'getdtablesize() found.' >&4
d_gettblsz="$undef"
tablesize="
@if VAL_NOFILE || nofile
$cat >nofile.c <<'EOCP'
#include <stdio.h>
int main()
{
printf("%d\n", getdtablesize());
}
EOCP
nofile="
if $cc $ccflags -o nofile nofile.c $libs >/dev/null 2>&1; then
nofile=`./nofile 2>/dev/null`
fi
if $test "$nofile"; then
echo "(You have $nofile file descriptors available per process.)"

```

```

else
  nofile='20'
  if ./bsd; then
    nofile='64'
  fi
  echo "(Hmm... Let's say you have $nofile file descriptors available.)"
fi
@end
else
  echo 'getdtablesize() NOT found...' >&4
  if set ulimit val -f; eval $sym; $val; then
    echo 'Maybe ulimit(4,0) will work...'
    $cat >nofile.c <<'EOCP'
#include <stdio.h>
#ifdef GETPARAM_H
#include <sys/param.h>
#endif
int main()
{
  printf("%d %d\n",
#ifdef NOFILE
    NOFILE,
#else
    0,
#endif
    ulimit(4,0));
  exit(0);
}
EOCP
  if $cc $ccflags -DGETPARAM_H -o nofile nofile.c $libs
  >/dev/null 2>&1 \
  || $cc $ccflags -o nofile nofile.c $libs >/dev/null 2>&1 ; then
  set `./nofile`
  d_gettblsz=$1
  d_ulimit4=$2
  if $test "$d_ulimit4" -lt 0; then
    echo "Your ulimit() call doesn't tell me what I want to know."
    echo "We'll just use NOFILE in this case."
    nofile=$d_gettblsz
    d_gettblsz="$define"
    tablesize='NOFILE'
  else
    if $test "$d_gettblsz" -gt 0; then
      echo "Your system defines NOFILE to be $d_gettblsz, and" >&4
    else
      echo "I had trouble getting NOFILE from your system, but" >&4
    fi
  fi
  echo "ulimit returns $d_ulimit4 as the number of available file descriptors." >&4

```

```

dflt='y';
echo " "
rp='Should I use ulimit to get the number of available file descriptors?'
. ./myread
case "$ans" in
y*)
nfile=$d_ulimit4
d_gettblsz="$define"
tablesize='ulimit(4, 0L)'
echo "Using ulimit(4,0)."
;;
*)
nfile=$d_gettblsz
d_gettblsz="$define"
tablesize='NOFILE'
echo "Using NOFILE."
;;
esac
fi
else
echo
"Strange, I couldn't get my test program to compile."
echo "We'll just use NOFILE in this case."
d_gettblsz="$define"
tablesize='NOFILE'
nfile=""
fi
else
echo 'Using NOFILE instead.'
d_gettblsz="$define"
tablesize='NOFILE'
nfile=""
fi
fi
@if VAL_NOFILE || nfile
case "$nfile" in
")
$cat >nfile.c <<'EOCP'
#include <stdio.h>
#ifdef GETPARAM_H
#include <sys/param.h>
#endif
int main()
{
printf("%d\n",
#ifdef NOFILE
NOFILE,
#else

```

```

0,
#endif
);
exit(0);
}
EOCP
if $cc $ccflags -DGETPARAM_H -o nofile nofile.c $libs >/dev/null 2>&1 \
|| $cc $ccflags -o nofile nofile.c $libs >/dev/null 2>&1 ; then
nofile=`./nofile 2>/dev/null`
fi
if $test "$nofile"; then
echo "(You have $nofile file descriptors available per process.)"
else
nofile='20'
if ./bsd; then
nofile='64'
fi
echo "(Hmm... Let's say you have $nofile file descriptors available.)"
fi
;;
esac
@end
$rm -f nofile*

```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/d_NOFILE.U
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1999 Jarkko Hietaniemi

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?MAKE:d_statfs_s: \

Hasstruct i_sysparam i_sysmount i_systypes \

i_sysvfs i_sysstatfs Setvar

?MAKE: -pick add \$@ %<

?S:d_statfs_s:

?S: This variable conditionally defines the HAS_STRUCTURE_STATFS symbol,

?S: which indicates that the struct statfs is supported.

?S:.

?C:HAS_STRUCTURE_STATFS:

?C: This symbol, if defined, indicates that the struct statfs

?C: to do statfs() is supported.

?C:.

```
?H:#$d_statfs_s HAS_STRUCT_STATFS /**/
?H:.
?LINT:set d_statfs_s
: Check for statfs_s
echo " "
echo "Checking to see if your system supports struct statfs..." >&4
set d_statfs_s statfs $i_systypes sys/types.h $i_sysparam sys/param.h $i_sysmount sys/mount.h $i_sysvfs sys/vfs.h
$i_sysstatfs sys/statfs.h
eval $hasstruct
case "$d_statfs_s"
in
"$define") echo "Yes, it does." ;;
*) echo "No, it doesn't." ;;
esac
```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/perl/d_statfs_s.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: d_endhent.U,v 3.0 1993/08/18 12:06:09 ram Exp $
?RCS:
?RCS: Copyright (c) 1991-1993, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 3.0.
?RCS:
?RCS: $Log: d_endhent.U,v $
?RCS: Revision 3.0 1993/08/18 12:06:09 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:d_endhent: Inlibc
?MAKE: -pick add $@ %<
?S:d_endhent:
?S: This variable conditionally defines HAS_ENDHOSTENT if endhostent() is
?S: available to close whatever was being used for host queries.
?S:.
?C:HAS_ENDHOSTENT:
?C: This symbol, if defined, indicates that the endhostent() routine is
?C: available to close whatever was being used for host
queries.
?C:.
?H:#$d_endhent HAS_ENDHOSTENT /**/
?H:.
?LINT:set d_endhent
```

```
: see if endhostent exists
set endhostent d_endhent
eval $inlibc
```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/modified/d_endhent.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: i_systwgcf.U 1 2006-08-24 12:32:52Z rmanfredi $
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: $Log: i_systwgcf.U,v $
?RCS: Revision 3.0 1993/08/18 12:08:39 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:i_systwgcf: Inhdr
?MAKE: -pick add $@ %<
?S:i_systwgcf:
?S: This variable conditionally defines the I_SYS_TWG_CF symbol, and
?S: indicates whether a C program should include sys/twg_config.h.
?S:
?C:I_SYS_TWG_CF:
?C: This symbol, if defined, indicates to the C program that it should
?C: include sys/twg_config.h.
?C:
?H:#$i_systwgcf
I_SYS_TWG_CF /**/
?H:
?LINT:set i_systwgcf
: see if this is a sys/twg_config.h system
set sys/twg_config.h i_systwgcf
eval $inhdr
```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/i_systwgcf.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: d_sigsetmk.U 1 2006-08-24 12:32:52Z rmanfredi $
?RCS:
```

```

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: $Log: d_sigsetmk.U,v $
?RCS: Revision 3.0 1993/08/18 12:07:23 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:d_sigsetmk: Csym Setvar
?MAKE: -pick add $@ %<
?S:d_sigsetmk:
?S: This variable conditionally defines the HAS_SIGSETMASK symbol, which
?S: indicates to the C program that the sigsetmask() routine is available
?S: to set current signal mask.
?S:.
?C:HAS_SIGSETMASK (SIGSETMASK):
?C: This symbol, if defined, indicates that the sigsetmask()
    routine is
?C: available to set current signal mask. Otherwise, you should probably
?C: emulate this by using signal(), but fear race conditions...
?C:.
?H:#$d_sigsetmk HAS_SIGSETMASK /**/
?H:.
?LINT:set d_sigsetmk
: see if sigsetmask exists
echo " "
if set sigsetmask val -f d_sigsetmk; eval $csym; $val; then
echo 'sigsetmask() found.' >&4
val="$define"
else
echo "sigsetmask() not found -- We'll use signal()." >&4
val="$undef"
fi
set d_sigsetmk
eval $setvar

Found in path(s):
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/d_sigsetmk.U
No license file was found, but licenses were detected in source scan.

?RCS: $Id$
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

```

?RCS:
?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: Original Author: Andy Dougherty <doughera@lafcol.lafayette.edu>
?RCS:
?RCS: \$Log: selecttype.U,v \$
?RCS: Revision 3.0.1.3 1997/02/28 16:20:09 ram
?RCS: patch61: always include <sys/select.h> when available for test
?RCS:
?RCS: Revision 3.0.1.2 1995/07/25 14:14:06 ram
?RCS: patch56: removed harmful spaces in assignment
?RCS:
?RCS: Revision 3.0.1.1 1994/06/20 07:06:31 ram
?RCS: patch30: created by ADO
?RCS:
?MAKE:selecttype: cat +cc +ccflags rm Oldconfig Myread \
d_fd_set d_select d_socket i_systeme
i_sysselect
?MAKE: -pick add \$@ %<
?S:selecttype:
?S: This variable holds the type used for the 2nd, 3rd, and 4th
?S: arguments to select. Usually, this is 'fd_set *', if HAS_FD_SET
?S: is defined, and 'int *' otherwise. This is only useful if you
?S: have select(), naturally.
?S:.
?C:Select_fd_set_t:
?C: This symbol holds the type used for the 2nd, 3rd, and 4th
?C: arguments to select. Usually, this is 'fd_set *', if HAS_FD_SET
?C: is defined, and 'int *' otherwise. This is only useful if you
?C: have select(), of course.
?C:.
?H:#define Select_fd_set_t \$selecttype /**/
?H:.
?T:xxx yyy
: check for type of arguments to select. This will only really
: work if the system supports prototypes and provides one for
: select.
case "\$d_select" in
\$define)
: Make initial guess
case "\$selecttype" in
"|')
case "\$d_fd_set" in
\$define) xxx='fd_set *' ;;

```

*) xxx='int *' ;;
esac
;;
*) xxx="$selecttype"
;;
esac
: backup guess
case "$xxx" in
'fd_set *') yyy='int *'
;;
'int *') yyy='fd_set *' ;;
esac

$cat <<EOM

```

Checking to see what type of arguments are expected by select().

EOM

```

$cat >try.c <<EOCP
#$i_systime I_SYS_TIME
#$i_sysselect I_SYS_SELECT
#$d_socket HAS_SOCKET
#include <sys/types.h>
#ifdef HAS_SOCKET
#include <sys/socket.h> /* Might include <sys/bsdtypes.h> */
#endif
#ifdef I_SYS_TIME
#include <sys/time.h>
#endif
#ifdef I_SYS_SELECT
#include <sys/select.h>
#endif
int main()
{
int width;
Select_fd_set_t readfds;
Select_fd_set_t writefds;
Select_fd_set_t exceptfds;
struct timeval timeout;
select(width, readfds, writefds, exceptfds, &timeout);
exit(0);
}
EOCP
if $cc $ccflags -c -DSelect_fd_set_t="$xxx" try.c >/dev/null 2>&1 ; then
selecttype="$xxx"
echo "Your system uses $xxx for the arguments to select." >&4
elif $cc $ccflags -c -DSelect_fd_set_t="$yyy" try.c >/dev/null 2>&1 ; then
selecttype="$yyy"
echo "Your system uses $yyy for the arguments to select." >&4

```

```

else
rp='What is the type for the 2nd, 3rd, and 4th arguments
to select?'
dflt="$xxx"
. ./myread
selecttype="$sans"
fi
$rm -f try.[co]
;;
*) selecttype='int *'
;;
esac

```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/selecttype.U
```

No license file was found, but licenses were detected in source scan.

```

case $CONFIG in
")
if test -f config.sh; then TOP=.;
elif test -f ../config.sh; then TOP=..;
elif test -f ../../config.sh; then TOP=../../.;
elif test -f ../../../config.sh; then TOP=../../../.;
elif test -f ../../../../config.sh; then TOP=../../../../.;
else
echo "Can't find config.sh."; exit 1
fi
. $TOP/config.sh
;;
esac
case "$0" in
*/*) cd `expr X$0 : 'X\(.*/'` ;;
esac
echo "Extracting makedir (with variable substitutions)"
$spitshell >makedir <<!GROK!THIS!
$startsh
# $Id: makedir.sh,v 3.0.1.1 1994/01/24 14:00:08 ram Exp ram $
#
# Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
#
# You may redistribute only under the terms of the Artistic Licence,
# as specified in the README file that comes with the distribution.
# You may reuse parts of this distribution only within the terms of
# that same Artistic Licence; a copy of which may be found at the root
# of the source tree for dist 4.0.
#
# Original

```

```

Author: Larry Wall <lwall@netlabs.com>
#
# $Log: mkdir.sh,v $
# Revision 3.0.1.1 1994/01/24 14:00:08 ram
# patch16: changed top ln-style config.sh lookup into test-style one
#
# Revision 3.0 1993/08/18 12:04:38 ram
# Baseline for dist 3.0 netwide release.
#

export PATH || (echo "OOPS, this isn't sh. Desperation time. I will feed myself to sh."; sh \${0}; kill \${0})

case \ $# in
0)
    $echo "mkdir pathname filenameflag"
    exit 1
    ;;
esac

: guarantee one slash before 1st component
case \ $1 in
/*) ;;
*) set .\ $1 \ $2 ;;
esac

: strip last component if it is to be a filename
case X\ $2 in
X1) set \ $echo \ $1 | $sed 's:\(.*\)/[^]*\ $:1:\` ;;
*) set \ $1 ;;
esac

: return reasonable status if nothing to be created
if $test -d "\ $1" ; then
    exit 0
fi

list=""
while true ; do
    case \ $1 in
    /*/*)
list="\ $1 \ $list"
set \ $echo \ $1 | $sed 's:\(.*\)/:1:\`
    ;;
    *)
break
    ;;
    esac
done

```

```
set \list
```

```
for dir do
```

```
    $mkdir \dir >/dev/null 2>&1
```

```
done
```

```
!GROK!THIS!
```

```
$unicefix
```

```
    mkdir
```

```
chmod +x mkdir
```

```
Found in path(s):
```

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-  
debian-perl-5.26.1/dist/lib/mkdir.SH
```

```
No license file was found, but licenses were detected in source scan.
```

```
?RCS: $Id$
```

```
?RCS:
```

```
?RCS: Copyright (c) 1999 Jarkko Hietaniemi
```

```
?RCS:
```

```
?RCS: You may distribute under the terms of either the GNU General Public
```

```
?RCS: License or the Artistic License, as specified in the README file.
```

```
?RCS:
```

```
?MAKE:usesocks: Myread Oldconfig Setvar
```

```
?MAKE: -pick add $@ %<
```

```
?Y:TOP
```

```
?S:usesocks:
```

```
?S: This variable conditionally defines the USE_SOCKS symbol,
```

```
?S: and indicates that Perl should be built to use SOCKS.
```

```
?S:.
```

```
?C:USE_SOCKS:
```

```
?C: This symbol, if defined, indicates that Perl should
```

```
?C: be built to use socks.
```

```
?C:.
```

```
?H:%<:#ifndef USE_SOCKS
```

```
?H:%<:#$usesocks USE_SOCKS /**/
```

```
?H:%<:#endif
```

```
?H:.
```

```
?LINT:set usesocks
```

```
?INIT:: set usesocks on the Configure command line to enable socks.
```

```
: Check is we will use socks
```

```
?X: We should really have some explanatory text here, and some
```

```
?X: automatic setting of sensible defaults.
```

```
case "$usesocks" in
```

```
$define|true|[yY]*) dflt='y';;
```

```
*) dflt='n';;
```

```
esac
```

```
cat <<EOM
```

Perl can be built to
use the SOCKS proxy protocol library. To do so,
Configure must be run with -Dusesocks. If you use SOCKS you also need
to use the PerlIO abstraction layer, this will be implicitly selected.

If this doesn't make any sense to you, just accept the default '\$dflt'.

EOM

```
rp='Build Perl for SOCKS?'
./myread
case "$ans" in
y|Y) val="$define" ;;
*)   val="$undef" ;;
esac
set usesocks
eval $setvar
```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/perl/usesocks.U
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 2003 Jarkko Hietaniemi

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?MAKE:d_scalbnl: Inlibc

?MAKE: -pick add \$@ %<

?S:d_scalbnl:

?S: This variable conditionally defines the HAS_SCALBNL symbol, which

?S: indicates to the C program that the scalbnl() routine is available.

?S: If ilogbl is also present we can emulate frexpl.

?S:.

?C:HAS_SCALBNL:

?C: This symbol, if defined, indicates that the scalbnl routine is

?C: available. If ilogbl is also present we can emulate frexpl.

?C:.

?H:#\$d_scalbnl HAS_SCALBNL /**/

?H:.

?LINT:set d_scalbnl

: see if scalbnl exists

set scalbnl d_scalbnl

eval \$inlibc

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_scalbnl.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: Inhdr.U 1 2006-08-24 12:32:52Z rmanfredi \$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic Licence,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic Licence; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: Inhdr.U,v \$

?RCS: Revision 3.0.1.2 1995/05/12 12:01:31 ram

?RCS: patch54: deleted tabs that caused some /bin/sh to core dump (ADO)

?RCS:

?RCS: Revision 3.0.1.1 1994/10/29 15:55:01 ram

?RCS: patch36: call ./whoa explicitly instead of relying on PATH

?RCS:

?RCS: Revision 3.0 1993/08/18 12:05:01 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?X:

?X: This unit checks wether a set of header files exists or not.

?X: If the first header is not
found, the function tries to locate

?X: the next header, and so on, until one is found or there is no

?X: more header in the list.

?X:

?X: To use it, say:

?X: set header i_header [header2 i_header2 ...]

?X: eval \$inhdr

?X:

?MAKE:Inhdr: test Findhdr Whoa

?MAKE: -pick add \$@ %<

?LINT:define inhdr

?V:inhdr

?S:inhdr:

?S: This shell variable is used internally by Configure to check

?S: wether a set of headers exist or not. A typical use is:

?S: set header i_header [header2 i_header2 ...]

?S: eval \$inhdr

?S: That will print a message, saying wether header was found or

?S: not and set i_header* accordingly. If the first header is not

?S: found, we try the next one, until the list is empty or one is found.

?S:.

```

?T:xxx xxf var td xxnf tu yyy instead was cont
: define an alternate in-header-list? function
inhdr='echo " "; td=$define; tu=$undef; yyy=$@;
cont=true; xxf="echo \"<\\$1> found.\" >&4";
case $# in 2) xxnf="echo \"<\\$1> NOT found.\" >&4";;
*) xxnf="echo \"<\\$1> NOT found, ...\" >&4";;
esac;
case
$# in 4) instead=instead;; *) instead="at last";; esac;
while $test "$cont"; do
xxx=`./findhdr $1`
var=$2; eval "was=\\$2";
if $test "$xxx" && $test -r "$xxx";
then eval $xxf;
?X: Next line shifted left 1 tabstop to avoid sh core dump on MachTen 2.1.1.
eval "case \"\\$var\" in $undef) ./whoa; esac"; eval "$var=\\$td";
cont="";
else eval $xxnf;
?X: Likewise, the next line has been shifted left 1 tabstop -- ADO, 08/03/95
eval "case \"\\$var\" in $define) ./whoa; esac"; eval "$var=\\$tu"; fi;
set $yyy; shift; shift; yyy=$@;
case $# in 0) cont="";;
2) xxf="echo \"but I found <\\$1> $instead.\" >&4";
xxnf="echo \"and I did not find <\\$1> either.\" >&4";;
*) xxf="echo \"but I found <\\$1> instead.\" >&4";
xxnf="echo \"there is no <\\$1>, ...\" >&4";;
esac;
done;
?X: Remaining values are set to 'undef'
while $test "$yyy";
do set $yyy; var=$2; eval "was=\\$2";
eval "case \"\\$var\" in $define) ./whoa; esac"; eval "$var=\\$tu";
set $yyy; shift; shift; yyy=$@;
done'

```

Found

in path(s):

```

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/Inhdr.U

```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: \$Log: Init.U,v \$
?RCS: Revision 3.0.1.1 1994/10/31 09:45:59 ram
?RCS: patch44: removed Options from MAKE to prevent Init overrides
?RCS: patch44: option processing now done after Myinit thanks to new Begin.U
?RCS: patch44: moved "Beginning of configuration questions" to Begin.U
?RCS: patch44: moved signal trapping instruction to Begin.U as well
?RCS:
?RCS: Revision 3.0 1993/08/18 12:05:02 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?X:
?X: This file initializes certain default variables
used by Configure. They
?X: may be overridden or added to by definitions in Myinit.U.
?X:
?MAKE:Init eunicefix _exe: Null
?MAKE: -pick add \$@ %<
?MAKE: -pick weed \$@ ./Init
?S:eunicefix:
?S: When running under Eunice this variable contains a command which will
?S: convert a shell script to the proper form of text file for it to be
?S: executable by the shell. On other systems it is a no-op.
?S:.
?S:_exe (exe_ext):
?S: This variable defines the extension used for executable files.
?S: For unix it is empty. Other possible values include '.exe'.
?S: DJGPP, Cygwin and OS/2 use '.exe'. Stratus VOS uses '.pm'.
?S: On operating systems which do not require a specific extension
?S: for executable files, this variable is empty.
?S:.
?V:define undef smallmach:rmlist
?X:
?X: Throughout the units, one may make use of \$define and \$undef to reference
?X: a defined symbol or an undefined one. There is no need to add them in
?X: the dependency line since this unit makes them visible via ?V:, and
?X:
everyone inherits from those symbols since by convention Init.U is the
?X: root dependency.
?X:
?T: DJGPP
: Initialize wide constants
define='define'
undef='undef'
smallmach='pdp11 i8086 z8000 i80286 iAPX286'
rmlist=""

```

: We must find out about Eunice early
eunicefix=':
if test -f /etc/unixtovms; then
  eunicefix=/etc/unixtovms
fi
if test -f /etc/unixtovms.exe; then
  eunicefix=/etc/unixtovms.exe
fi

: Set executable suffix now -- needed before hints available
if test -f "/libs/version.library"; then
: Amiga OS
  _exe=""
elif test -f "/system/gnu_library/bin/ar.pm"; then
: Stratus VOS
  _exe=".pm"
elif test -n "$DJGPP"; then
: DOS DJGPP
  _exe=".exe"
elif test -d c:/.; then
: OS/2 or cygwin
  _exe=".exe"
else
: All other UNIX systems
  _exe=""
fi

```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/Init.U
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1999, Jarkko Hietaniemi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 3.0.

?RCS:

?MAKE:d_sem_unlink: Inlibc

?MAKE: -pick add \$@ %<

?S:d_sem_unlink:

?S: This variable conditionally defines HAS_SEM_UNLINK if sem_unlink() is

?S: available to unlink a POSIX semaphore.

?S:
?C:HAS_SEM_UNLINK:
?C: This symbol, if defined, indicates that the sem_unlink system call is
?C: available to unlink a POSIX semaphore.

?C:
?H:#\$d_sem_unlink HAS_SEM_UNLINK /**/
?H.:

?LINT:set d_sem_unlink
: see if sem_unlink exists
set sem_unlink d_sem_unlink
eval \$inlibc

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_sem_unlink.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.

?RCS:
?RCS: \$Log: d_mmap.U,v \$
?RCS: Revision 3.0.1.1 1993/12/15 08:19:12 ram
?RCS: patch15: created

?RCS:
?MAKE:d_mmap: Inlibc
?MAKE: -pick add \$@ %<

?S:d_mmap:
?S: This variable conditionally defines HAS_MMAP if mmap() is
?S: available to map a file into memory.

?S:
?C:HAS_MMAP:
?C: This symbol, if defined, indicates that the mmap system call is
?C: available to map a file into memory.

?C:
?H:#\$d_mmap HAS_MMAP /**/
?H.:

?LINT:set d_mmap
: see if mmap exists
set mmap d_mmap
eval \$inlibc

Found in path(s):

*

/opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/d_mmap.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_NOFILE.U,v 3.0.1.1 1994/10/29 16:08:38 ram Exp \$

?RCS:

?RCS: Copyright (c) 1991-1993, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 3.0.

?RCS:

?RCS: \$Log: d_NOFILE.U,v \$

?RCS: Revision 3.0.1.1 1994/10/29 16:08:38 ram

?RCS: patch36: added ?F: line for metalint file checking

?RCS:

?RCS: Revision 3.0 1993/08/18 12:05:39 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?MAKE:nofile d_gettblsz tablesize: Compile Myread Guess cat \

test rm Csym +cc +ccflags +optimize +ldflags +libs

?MAKE: -pick add \$@ %<

?S:nofile:

?S: This variable contains the number of file descriptors available to the

?S: process.

?S:.

?S:d_gettblsz:

?S: This

variable conditionally handles remapping of the getdtablesize()

?S: subroutine to ulimit(4,0), or the NOFILE manifest constant.

?S:.

?S:tablesize:

?S: This variable contains either the 'NOFILE' constant or 'ulimit(4, 0L)'

?S: and is used as the remapped value for the getdtablesize() macro.

?S:.

?C:getdtablesize:

?C: This catches use of the getdtablesize() subroutine, and remaps it

?C: to either ulimit(4,0) or NOFILE, if getdtablesize() isn't available.

?C:.

?C:VAL_NOFILE:

?C: This symbol contains the number of file descriptors available to the

?C: process, as determined at configuration time. Unless a static constant

?C: is needed, you should rely on getdtablesize() to obtain that number.

?C:.

```

?H:#$d_gettblsz getdtablesize() $tablesize /**/
?H:#define VAL_NOFILE $nofile /* Number of file descriptors */
?H:
?F:!nofile
?T:d_ulimit4 val
: see if getdtablesize exists
echo " "
?X: Revert logical value (d_gettblsz is undef if getdtablesize is present)
case "$d_gettblsz"
in
$define) d_gettblsz="$undef";;
$undef) d_gettblsz="$define";;
esac
if set getdtablesize val -f d_gettblsz; eval $csym; $val; then
echo 'getdtablesize() found.' >&4
d_gettblsz="$undef"
tablesize="
@if VAL_NOFILE || nofile
$cat >nofile.c <<'EOCP'
#include <stdio.h>
int main()
{
printf("%d\n", getdtablesize());
}
EOCP
nofile="
set nofile
if eval $compile_ok; then
nofile=`./nofile 2>/dev/null`
fi
if $test "$nofile"; then
echo "(You have $nofile file descriptors available per process.)"
else
nofile='20'
if ./bsd; then
nofile='64'
fi
echo "(Hmm... Let's say you have $nofile file descriptors available.)"
fi
@end
else
echo 'getdtablesize() NOT found...' >&4
if set ulimit val -f; eval $csym; $val; then
echo 'Maybe ulimit(4,0) will work...'
$cat >nofile.c <<'EOCP'
#include <stdio.h>
#ifdef GETPARAM_H
#include <sys/param.h>

```

```

#endif
int main()
{
    printf("%d %d\n",
#ifdef NOFILE
        NOFILE,
#else
        0,
#endif
    );
    ulimit(4,0);
    exit(0);
}
EOCP
if $cc $optimize
$ccflags -DGETPARAM_H $ldflags -o nofile nofile.c $libs >/dev/null 2>&1 \
|| $cc $optimize $ccflags $ldflags -o nofile nofile.c $libs >/dev/null 2>&1 ; then
set `./nofile`
d_gettblsz=$1
d_ulimit4=$2
if $test "$d_ulimit4" -lt 0; then
    echo "Your ulimit() call doesn't tell me what I want to know."
    echo "We'll just use NOFILE in this case."
    nofile=$d_gettblsz
    d_gettblsz="$define"
    tablesize='NOFILE'
else
    if $test "$d_gettblsz" -gt 0; then
        echo "Your system defines NOFILE to be $d_gettblsz, and" >&4
    else
        echo "I had trouble getting NOFILE from your system, but" >&4
    fi
echo "ulimit returns $d_ulimit4 as the number of available file descriptors." >&4
dflt='y';
echo " "
rp='Should I use ulimit to get the number of available file descriptors?'
. ./myread
case "$ans" in
y*)
    nofile=$d_ulimit4
    d_gettblsz="$define"
    tablesize='ulimit(4, 0L)'
    echo "Using ulimit(4,0)."
    ;;
*)
    nofile=$d_gettblsz
    d_gettblsz="$define"
    tablesize='NOFILE'
    echo

```

```

"Using NOFILE."
;;
esac
fi
else
echo "Strange, I couldn't get my test program to compile."
echo "We'll just use NOFILE in this case."
d_gettblsz="$define"
tablesize='NOFILE'
nofile=""
fi
else
echo 'Using NOFILE instead.'
d_gettblsz="$define"
tablesize='NOFILE'
nofile=""
fi
fi
@if VAL_NOFILE || nofile
case "$nofile" in
")
$cat >nofile.c <<'EOCP'
#include <stdio.h>
#ifdef GETPARAM_H
#include <sys/param.h>
#endif
int main()
{
printf("%d\n",
#ifdef NOFILE
NOFILE,
#else
0,
#endif
);
exit(0);
}
EOCP
if $cc $ccflags -DGETPARAM_H nofile.c -o nofile $libs >/dev/null 2>&1 \
|| $cc $ccflags nofile.c -o nofile $libs >/dev/null 2>&1 ; then
nofile=`./nofile 2>/dev/null`
fi
if $test "$nofile"; then
echo "(You have $nofile file descriptors available per process.)"
else
nofile='20'
if ./bsd; then
nofile='64'

```

```
fi
echo "(Hmm... Let's say you have $nofile file descriptors
available.)"
fi
;;
esac
@end
$rm -f nofile*
```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/compline/d_NOFILE.U
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 2000 Jarkko Hietaniemi

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?MAKE:d_finitel: Inlibc

?MAKE: -pick add \$@ %<

?S:d_finitel:

?S: This variable conditionally defines the HAS_FINITEL symbol, which

?S: indicates to the C program that the finitel() routine is available.

?S:.

?C:HAS_FINITEL:

?C: This symbol, if defined, indicates that the finitel routine is

?C: available to check whether a long double is finite

?C: (non-infinity non-NaN).

?C:.

?H:#\$d_finitel HAS_FINITEL /**/

?H:.

?LINT:set d_finitel

: see if finitel exists

set finitel d_finitel

eval \$inlibc

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/perl/d_finitel.U
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_speedopt.U 1 2006-08-24 12:32:52Z rmanfredi \$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

```

?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: $Log: d_speedopt.U,v $
?RCS: Revision 3.0.1.1 1994/10/29 16:15:51 ram
?RCS: patch36: call ./Cpplib explicitly instead of relying on PATH
?RCS:
?RCS: Revision 3.0 1993/08/18 12:07:27 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:d_speedopt: Myread Cpplib Oldconfig cat models Setvar
?MAKE: -pick add $@ %<
?S:d_speedopt:
?S: This variable conditionally defines the SPEED_OVER_MEM symbol, which
?S: indicates to the C program that it can
    burn memory in order to save
    CPU time.
?S:
?C:SPEED_OVER_MEM (SPEEDOVERMEM):
?C: This symbol, if defined, indicates that the program can use more
?C: memory in order to reduce CPU time. The symbol doesn't say whether
?C: we are more interested in saving text space or data space.
?C:
?H:#$d_speedopt SPEED_OVER_MEM /**/
?H:
?LINT:set d_speedopt
: do we want speed at the expense of memory
$cat <<'EOM'

```

I can try to optimize this package for either speed or memory. If you have limited address space you may wish to optimize for memory. Otherwise you should probably optimize for speed.

```

EOM
case "$d_speedopt" in
") if ./Cpplib $smallmach; then
case "$models" in
*large*|*huge*) dflt=speed;;
*) dflt=memory;;
esac
else
dflt=speed
fi
;;
*define*) dflt=speed;;

```

```

*) dflt=memory;;
esac
rp="What to optimize for?"
. ./myread
case "$ans" in
mem*) val="$undef";;
*) val="$define";;
esac
set d_speedopt
eval $setvar

```

Found in path(s):

```

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/d_speedopt.U

```

No license file was found, but licenses were detected in source scan.

```

?RCS: $Id: d_fmod.U 1 2006-08-24 12:32:52Z rmanfredi $
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: Original Author: Andy Dougherty <doughera@lafcol.lafayette.edu>
?RCS:
?RCS: $Log: d_fmod.U,v $
?RCS: Revision 3.0.1.1 1994/10/29 16:12:46 ram
?RCS: patch36: created by ADO
?RCS:
?MAKE:d_fmod: Inlibc
?MAKE: -pick add $@ %<
?S:d_fmod:
?S: This variable conditionally defines the HAS_FMOD symbol, which
?S: indicates to the C program that the fmod() routine is available.
?S: See also d_drem for the drem() routine which does roughly the same.
?S:.
?C:HAS_FMOD
:
?C: This symbol, if defined, indicates that the fmod routine is
?C: available to compute the remainder r=x-n*y where n=trunc(x/y).
?C:.
?H:#$d_fmod HAS_FMOD /**/
?H:.
?LINT:set d_fmod
: see if fmod exists

```

```
set fmod d_fmod
eval $inlibc
```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/d_fmod.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: d_itimer.U 1 2006-08-24 12:32:52Z rmanfredi $
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: $Log: d_itimer.U,v $
?RCS: Revision 3.0 1993/08/18 12:06:25 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:d_itimer: Inlibc
?MAKE: -pick add $@ %<
?S:d_itimer:
?S: This variable conditionally defines the HAS_ITIMER symbol, which
?S: indicates that the setitimer() routine exists. The setitimer()
?S: routine supports sub-second accuracy for one real-time and two
?S: cpu clocks.
?S:.
?C:HAS_ITIMER (ITIMER):
?C: This symbol, if defined, indicates
that the setitimer() routine exists.
?C:.
?H:#$d_itimer HAS_ITIMER /**/
?H:.
?LINT:set d_itimer
: see if setitimer exists
set setitimer d_itimer
eval $inlibc
```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/d_itimer.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id$
?RCS:
```

?RCS: Copyright (c) 2000 Jarkko Hietaniemi
 ?RCS:
 ?RCS: You may distribute under the terms of either the GNU General Public
 ?RCS: License or the Artistic License, as specified in the README file.
 ?RCS:
 ?MAKE:d_setrlimit: Inlibc
 ?MAKE: -pick add \$@ %<
 ?S:d_setrlimit:
 ?S: This variable conditionally defines the HAS_SETRLIMIT symbol, which
 ?S: indicates to the C program that the setrlimit() routine is available.
 ?S:.
 ?C:HAS_SETRLIMIT:
 ?C: This symbol, if defined, indicates that the setrlimit routine is
 ?C: available to set process resource limits.
 ?C:.
 ?H:#\$d_setrlimit HAS_SETRLIMIT /**/
 ?H:.
 ?LINT:set d_setrlimit
 : see if setrlimit exists
 set setrlimit d_setrlimit
 eval \$inlibc

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_setrlimit.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: Oldsym.U 1 2006-08-24 12:32:52Z rmanfredi \$
 ?RCS:
 ?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
 ?RCS:
 ?RCS: You may redistribute only under the terms of the Artistic License,
 ?RCS: as specified in the README file that comes with the distribution.
 ?RCS: You may reuse parts of this distribution only within the terms of
 ?RCS: that same Artistic License; a copy of which may be found at the root
 ?RCS: of the source tree for dist 4.0.
 ?RCS:
 ?RCS: \$Log: Oldsym.U,v \$
 ?RCS: Revision 3.0.1.1 1997/02/28 15:06:58 ram
 ?RCS: patch61: added support for src.U
 ?RCS:
 ?RCS: Revision 3.0 1993/08/18 12:05:13 ram
 ?RCS: Baseline for dist 3.0 netwide release.
 ?RCS:
 ?X:
 ?X: This unit follows the creation of the config.sh file. It adds some
 ?X: special symbols: defines from patchlevel.h file if any and PERL_CONFIG_SH,
 ?X: which is set to true. Then, we try to keep all the new symbols that

```

?X: may come from a hint
file or a previous config.sh file.
?X:
?MAKE:Oldsym: Config_sh cat test hint src sed sort uniq perl_patchlevel
?MAKE: -pick add $@ %<
?T:PERL_CONFIG_SH PERL_PATCHLEVEL sym tmp
?F:!UU
: add special variables
$test -f $src/patchlevel.h && \
awk '/^#define[ ]+PERL_/ {printf "%s=%s\n", $2, $3}' $src/patchlevel.h >>config.sh
echo "PERL_PATCHLEVEL='$perl_patchlevel'" >>config.sh
echo "PERL_CONFIG_SH=true" >>config.sh

: propagate old symbols
if $test -f UU/config.sh; then
?X: Make sure each symbol is unique in oldconfig.sh
<UU/config.sh $sort | $uniq >UU/oldconfig.sh
?X:
?X: All the symbols that appear twice come only from config.sh (hence the
?X: two config.sh in the command line). These symbols will be removed by
?X: the uniq -u command. The oldsyms file thus contains all the symbols
?X: that did not appear in the produced config.sh (Larry Wall).
?X:
?X: Do not touch the -u flag of uniq. This means you too, Jarkko.
?X:
$sed -n 's/^\([a-zA-Z_0-9]*\)=.*\1/p' \
config.sh config.sh UU/oldconfig.sh
\
$sort | $uniq -u >UU/oldsyms
set X ` $cat UU/oldsyms `
shift
case $# in
0) ;;
*)
$cat <<EOM
Hmm...You had some extra variables I don't know about...I'll try to keep 'em...
EOM
echo ": Variables propagated from previous config.sh file." >>config.sh
for sym in ` $cat UU/oldsyms `; do
echo " Propagating $hint variable ""$""$sym..."
eval 'tmp=""$""${sym}""'
echo "$tmp" | \
sed -e "s/'\"/\"'/g" -e "s/^\$sym=/'" -e "s/$/'" >>config.sh
done
;;
esac
fi

```

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/modified/Oldsym.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: vendorprefix.U,v 1.1 1999/07/08 18:32:57 doughera Exp doughera \$

?RCS:

?RCS: Copyright (c) 1999 Andy Dougherty

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 3.0.

?RCS:

?RCS: \$Log: vendorprefix.U,v \$

?RCS: Revision 1.1 1999/07/08 18:32:57 doughera

?RCS: Initial revision

?RCS:

?MAKE:usevendorprefix vendorprefix vendorprefixexp +oldvendorprefix: \

Getfile Loc Oldconfig cat prefix Myread

?MAKE: -pick add \$@ %<

?S:usevendorprefix:

?S: This variable tells whether the vendorprefix

?S: and consequently other vendor* paths are in use.

?S:.

?S:vendorprefix:

?S: This variable holds the full absolute path of the directory below

?S: which

the vendor will install add-on packages.

?S: See INSTALL for usage and examples.

?S:.

?S:vendorprefixexp:

?S: This variable holds the full absolute path of the directory below

?S: which the vendor will install add-on packages. Derived from vendorprefix.

?S:.

?S:oldvendorprefix:

?S: This variable is set non-null if the vendorprefix was previously defined

?S: and gets set to a new value. Used internally by Configure only.

?S:.

: Set the vendorprefix variables

\$cat <<EOM

The installation process will also create a directory for vendor-supplied add-ons. Vendors who supply perl with their system may find it convenient to place all vendor-supplied files in this directory rather than in the main distribution directory. This will ease upgrades between binary-compatible maintenance versions of perl.

Of course you may also use these directories in whatever way you see fit. For example, you might use them to access modules shared over a company-wide network.

The default answer should be

fine for most people.

This causes further questions about vendor add-ons to be skipped and no vendor-specific directories will be configured for perl.

EOM

```
rp='Do you want to configure vendor-specific add-on directories?'
case "$usevendorprefix" in
define|true|[yY]*) dflt=y ;;
*) : User may have set vendorprefix directly on Configure command line.
case "$vendorprefix" in
"|" ') dflt=n ;;
*) dflt=y ;;
esac
;;
esac
. ./myread
case "$ans" in
[yY]*) fn=d~+
rp='Installation prefix to use for vendor-supplied add-ons?'
case "$vendorprefix" in
") dflt="$prefix" ;;
*) dflt=$vendorprefix ;;
esac
. ./getfile
: XXX Prefixit unit does not yet support siteprefix and vendorprefix
oldvendorprefix="
case "$vendorprefix" in
") ;;
*) case "$ans" in
"$prefix" ) ;;
*) oldvendorprefix="$prefix";;
esac
;;
esac
usevendorprefix="$define"
vendorprefix="$ans"
vendorprefixexp="$ansexp"
;;
*) usevendorprefix="$undef"
vendorprefix="
vendorprefixexp="
;;
```

esac

Found in path(s):

*

/opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/installdirs/vendorprefix.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_getnetprotos.U,v \$

?RCS:

?RCS: Copyright (c) 1991-1993, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 3.0.

?RCS:

?MAKE:d_getnetprotos : Hasproto i_netdb

?MAKE: -pick add \$@ %<

?S:d_getnetprotos:

?S: This variable conditionally defines the HAS_GETNET_PROTOS symbol,

?S: which indicates to the C program that <netdb.h> supplies

?S: prototypes for the various getnet*() functions.

?S: See also netdbtype.U for probing for various netdb types.

?S:.

?C:HAS_GETNET_PROTOS:

?C: This symbol, if defined, indicates that <netdb.h> includes

?C: prototypes for getnetent(), getnetbyname(), and

?C: getnetbyaddr(). Otherwise,

it is up to the program to guess

?C: them. See netdbtype.U for probing for various Netdb_xxx_t types.

?C:.

?H:#\$d_getnetprotos HAS_GETNET_PROTOS /**/

?H:.

?LINT:set d_getnetprotos

: see if prototypes for various getnetxxx netdb.h functions are available

echo " "

set d_getnetprotos getnetent \$i_netdb netdb.h

eval \$hasproto

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/protos/d_getnetprotos.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?MAKE:i_poll: Inhdr
?MAKE: -pick add \$@ %<
?S:i_poll:
?S: This variable conditionally defines the I_POLL symbol, which
?S: indicates to the C program that it should include <poll.h>.
?S:.
?C:I_POLL:
?C: This symbol, if defined, indicates that the program may include
?C: <poll.h>. If there is no <poll.h>, then you may check I_SYS_POLL
?C: instead to see whether there is a <sys/poll.h> to include.
?C:.
?H:#\$i_poll I_POLL /**/
?H:.
?LINT:set i_poll
: see if there is a poll.h file
set poll.h i_poll
eval \$inhdr

Found

in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/i_poll.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: uidtype.U,v \$

?RCS: Revision 3.0.1.3 1994/08/29 16:33:25 ram

?RCS: patch32: now uses new Typedef unit to compute type information

?RCS:

?RCS: Revision 3.0.1.2 1994/06/20 07:09:36 ram

?RCS: patch30: comment for uidtype referred to the obsoleted symbol

```

?RCS:
?RCS: Revision 3.0.1.1 1994/05/13 15:28:27 ram
?RCS: patch27: made conform to its gidtype.U companion
?RCS: patch27: question now explicitly mentions getuid()
?RCS:
?RCS: Revision 3.0 1993/08/18 12:09:56 ram
?RCS: Baseline for dist
3.0 netwide release.
?RCS:
?MAKE:uidtype: Myread Typedef Findhdr
?MAKE: -pick add $@ %<
?S:uidtype:
?S: This variable defines Uid_t to be something like uid_t, int,
?S: ushort, or whatever type is used to declare user ids in the kernel.
?S:.
?C:Uid_t (UIDTYPE):
?C: This symbol holds the type used to declare user ids in the kernel.
?C: It can be int, ushort, uid_t, etc... It may be necessary to include
?C: <sys/types.h> to get any typedef'ed information.
?C:.
?H:#define Uid_t $uidtype /* UID type */
?H:.
?T:xxx
: see what type uids are declared as in the kernel
set uid_t uidtype xxx stdio.h sys/types.h
eval $typedef
case "$uidtype" in
xxx)
xxx=`./findhdr sys/user.h`
set `grep '_ruuid;' "$xxx" 2>/dev/null` unsigned short
case $1 in
unsigned) dflt="$1 $2" ;;
*) dflt="$1" ;;
esac
;;
*) dflt="$uidtype";;
esac
echo " "
rp="What is the type for user ids returned by getuid()?"
./myread
uidtype="$ans"

```

Found in path(s):

```

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/uidtype.U

```

No license file was found, but licenses were detected in source scan.

```

?RCS: $Id$

```



```
else
  if $test X"$gidsize" = X"$shortsize"; then
    gidformat="hu"
  fi
fi
fi
fi
;;
esac
```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/typedefs/gidf.U
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 2001, Jarkko Hietaniemi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 3.0.

?RCS:

?MAKE:d_sigprocmask: Inlibc

?MAKE: -pick add \$@ %<

?S:d_sigprocmask:

?S: This variable conditionally defines HAS_SIGPROCMAK

?S: if sigprocmask() is available to examine or change the signal mask

?S: of the calling process.

?S:.

?C:HAS_SIGPROCMAK:

?C: This symbol, if defined, indicates that the sigprocmask

?C: system call is available to examine or change the signal mask

?C: of the calling process.

?C:.

?H:#\$d_sigprocmask HAS_SIGPROCMAK /**/

?H:.

?LINT:set d_sigprocmask

: see if sigprocmask exists

set sigprocmask d_sigprocmask

eval

\$inlibc

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_sigprocmask.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: d_sjis2jis.U 1 2006-08-24 12:32:52Z rmanfredi $
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: $Log: d_sjis2jis.U,v $
?RCS: Revision 3.0 1993/08/18 12:07:25 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:d_sjis2jis: Inlibc
?MAKE: -pick add $@ %<
?S:d_sjis2jis:
?S: This variable conditionally defines the HAS_SJIS2JIS symbol, which
?S: indicates to the C program that the sjis2jis() routine is available
?S: to convert SJIS to JIS.
?S:.
?C:HAS_SJIS2JIS:
?C: This symbol, if defined, indicates that the sjis2jis routine is
?C: available
?C: to convert SJIS to JIS.
?C:.
?H:#$d_sjis2jis HAS_SJIS2JIS /**/
?H:.
?LINT:set d_sjis2jis
: see if sjis2jis exists
set sjis2jis d_sjis2jis
eval $inlibc
```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/d_sjis2jis.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: d_setgrent_r.U,v 0RCS:
?RCS: Copyright (c) 2002,2003 Jarkko Hietaniemi
?RCS:
?RCS: You may distribute under the terms of either the GNU General Public
?RCS: License or the Artistic License, as specified in the README file.
?RCS:
?RCS: Generated by the reentr.pl from the Perl 5.8 distribution.
?RCS:
```

```

?MAKE:d_setgrent_r setgrent_r_proto: Inlibc Protochk Hasproto i_systypes \
  usethreads i_grp extern_C
?MAKE: -pick add $@ %<
?S:d_setgrent_r:
?S: This variable conditionally defines the HAS_SETGRENTR symbol,
?S: which indicates to the C program that the setgrent_r()
?S: routine is available.
?S:.
?S:setgrent_r_proto:
?S: This variable encodes the prototype of setgrent_r.
?S: It is zero if d_setgrent_r is undef, and one of the
?S: REENTRANT_PROTO_T_ABC macros of reentr.h if d_setgrent_r
?S: is defined.
?S:.
?C:HAS_SETGRENTR:
?C: This symbol, if defined, indicates that the setgrent_r routine
?C: is available to
  setgrent re-entrantly.
?C:.
?C:SETGRENTR_PROTO:
?C: This symbol encodes the prototype of setgrent_r.
?C: It is zero if d_setgrent_r is undef, and one of the
?C: REENTRANT_PROTO_T_ABC macros of reentr.h if d_setgrent_r
?C: is defined.
?C:.
?H:#$d_setgrent_r HAS_SETGRENTR /**/
?H:#define SETGRENTR_PROTO $setgrent_r_proto /**/
?H:.
?T:try hdrs d_setgrent_r_proto
: see if setgrent_r exists
set setgrent_r d_setgrent_r
eval $inlibc
case "$d_setgrent_r" in
"$define")
  hdrs="$i_systypes sys/types.h define stdio.h $i_grp grp.h"
  case "$d_setgrent_r_proto:$usethreads" in
":define") d_setgrent_r_proto=define
    set d_setgrent_r_proto setgrent_r $hdrs
    eval $hasproto ;;
*) ;;
esac
case "$d_setgrent_r_proto" in
define)
  case "$setgrent_r_proto" in
"|0) try='int setgrent_r(FILE**);'
./protochk "$extern_C $try" $hdrs && setgrent_r_proto=I_H ;;
esac
case "$setgrent_r_proto" in

```

```

"|0) try='void setgrent_r(FILE**);'
./protochk "$extern_C $try" $hdrs && setgrent_r_proto=V_H ;;
esac
case
"$setgrent_r_proto" in
"|0) d_setgrent_r=undef
    setgrent_r_proto=0
    echo "Disabling setgrent_r, cannot determine prototype." >&4 ;;
*) case "$setgrent_r_proto" in
    REENTRANT_PROTO*) ;;
    *) setgrent_r_proto="REENTRANT_PROTO_$setgrent_r_proto" ;;
    esac
    echo "Prototype: $try" ;;
    esac
;;
*) case "$susethreads" in
    define) echo "setgrent_r has no prototype, not using it." >&4 ;;
    esac
    d_setgrent_r=undef
    setgrent_r_proto=0
    ;;
    esac
;;
*) setgrent_r_proto=0
;;
esac

```

Found in path(s):

```

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/threads/d_setgrent_r.U

```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: Original Author: Andy Dougherty <doughera@lafcol.lafayette.edu>

?RCS:

?RCS: \$Log: modetype.U,v \$

?RCS: Revision 3.0.1.1 1994/10/29 16:25:07 ram

?RCS: patch36: created by ADO

?RCS:

```

?MAKE:modetype: Myread Typedef
?MAKE: -pick add $@ %<
?S:modetype:
?S: This variable defines modetype to be something like mode_t,
?S: int, unsigned short, or whatever type is used to declare file
?S: modes for system calls.
?S:.
?C:Mode_t:
?C: This symbol holds the type used to declare file modes
?C: for systems calls.
    It is usually mode_t, but may be
?C: int or unsigned short. It may be necessary to include <sys/types.h>
?C: to get any typedef'ed information.
?C:.
?H:#define Mode_t $modetype /* file mode parameter for system calls */
?H:.
: see what type is used for mode_t
set mode_t modetype int stdio.h sys/types.h
eval $typedef
dflt="$modetype"
echo " "
rp="What type is used for file modes?"
. ./myread
modetype="$ans"

```

Found in path(s):

```

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/modetype.U

```

No license file was found, but licenses were detected in source scan.

```

?RCS: $Id: d_raster.U 1 2006-08-24 12:32:52Z rmanfredi $
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: $Log: d_raster.U,v $
?RCS: Revision 3.0 1993/08/18 12:06:50 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:d_raster rasterlib: cat test Setvar Myread Oldconfig
?MAKE: -pick add $@ %<
?S:d_raster:
?S: Conditionally defines RASTER_TEK if this is a raster tech machine.

```

```

?S:.
?S:rasterlib (d_rasterlib):
?S: Set to the needed compile flag if this is a raster tech machine.
?S: It is up to the Makefile to use this variable.
?S:.
?C:RASTER_TEK:
?C: Defined
    if this is a rastertech machine.
?C:.
?H:#$d_raster RASTER_TEK /**/
?H:.
?LINT:set d_raster
: See if this is a raster tech machine.
val="$undef"
rasterlib="
if $test -r /dev/mirage; then
$cat <<'EOM'

```

You seem to have a mirage device... this is normally associated with a raster technologies graphics workstation. If this is right, you may want to use raster tech in this program.

```

EOM
dflt=y
case "$d_raster" in
"$undef") dflt=n;;
esac
rp='Use raster tech?'
./myread
case "$ans" in
y*) val="$define";;
esac
fi
set d_raster
eval $setvar

case "$d_raster" in
"$define") rasterlib='-lphigs';;
esac

```

Found in path(s):

```

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/d_raster.U

```

No license file was found, but licenses were detected in source scan.

```

?RCS: $Id: d_random_r.U,v 0RCS:
?RCS: Copyright (c) 2002,2003 Jarkko Hietaniemi
?RCS:

```

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?RCS: Generated by the reentr.pl from the Perl 5.8 distribution.

?RCS:

?MAKE:d_random_r random_r_proto: Inlibc Protochk Hasproto i_systypes \
 usethreads i_stdlib extern_C

?MAKE: -pick add \$@ %<

?S:d_random_r:

?S: This variable conditionally defines the HAS_RANDOM_R symbol,

?S: which indicates to the C program that the random_r()

?S: routine is available.

?S:.

?S:random_r_proto:

?S: This variable encodes the prototype of random_r.

?S: It is zero if d_random_r is undef, and one of the

?S: REENTRANT_PROTO_T_ABC macros of reentr.h if d_random_r

?S: is defined.

?S:.

?C:HAS_RANDOM_R:

?C: This symbol, if defined, indicates that the random_r routine

?C: is available to random re-entrantly.

?C:.

?C:RANDOM_R_PROTO:

?C: This

symbol encodes the prototype of random_r.

?C: It is zero if d_random_r is undef, and one of the

?C: REENTRANT_PROTO_T_ABC macros of reentr.h if d_random_r

?C: is defined.

?C:.

?H:#\$d_random_r HAS_RANDOM_R /**/

?H:#define RANDOM_R_PROTO \$random_r_proto /**/

?H:.

?T:try hdrs d_random_r_proto

: see if random_r exists

set random_r d_random_r

eval \$inlibc

case "\$d_random_r" in

"\$define")

hdrs="\$i_systypes sys/types.h define stdio.h \$i_stdlib stdlib.h"

case "\$d_random_r_proto:\$usethreads" in

":define") d_random_r_proto=define

set d_random_r_proto random_r \$hdrs

eval \$hasproto ;;

*) ;;

esac

case "\$d_random_r_proto" in

define)

```

case "$random_r_proto" in
"|0) try='int random_r(int*, struct random_data*);'
./protochk "$extern_C $try" $hdrs && random_r_proto=I_iS ;;
esac
case "$random_r_proto" in
"|0) try='int random_r(long*, struct random_data*);'
./protochk "$extern_C $try" $hdrs && random_r_proto=I_lS ;;
esac
case "$random_r_proto" in
"|0)
try='int random_r(struct random_data*, int32_t*);'
./protochk "$extern_C $try" $hdrs && random_r_proto=I_St ;;
esac
case "$random_r_proto" in
"|0) d_random_r=undef
    random_r_proto=0
    echo "Disabling random_r, cannot determine prototype." >&4 ;;
*) case "$random_r_proto" in
REENTRANT_PROTO*) ;;
*) random_r_proto="REENTRANT_PROTO_$random_r_proto" ;;
esac
echo "Prototype: $try" ;;
esac
;;
*) case "$susetheads" in
define) echo "random_r has no prototype, not using it." >&4 ;;
esac
d_random_r=undef
random_r_proto=0
;;
esac
;;
*) random_r_proto=0
;;
esac

```

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/threads/d_random_r.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 2005, H.Merijn Brand

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 3.0.

?RCS:

?MAKE:d_malloc_size d_malloc_good_size: Inlibc

?MAKE: -pick add \$@ %<

?S:d_malloc_size:

?S: This symbol, if defined, indicates that the malloc_size

?S: routine is available for use.

?S:.

?S:d_malloc_good_size:

?S: This symbol, if defined, indicates that the malloc_good_size

?S: routine is available for use.

?S:.

?C:HAS_MALLOC_SIZE:

?C: This symbol, if defined, indicates that the malloc_size

?C: routine is available for use.

?C:.

?H:#\$d_malloc_size HAS_MALLOC_SIZE /**/

?H:.

?C:HAS_MALLOC_GOOD_SIZE:

?C: This symbol, if defined,

indicates that the malloc_good_size

?C: routine is available for use.

?C:.

?H:#\$d_malloc_good_size HAS_MALLOC_GOOD_SIZE /**/

?H:.

?LINT:set d_malloc_size

?LINT:set d_malloc_good_size

: see if malloc_size exists

set malloc_size d_malloc_size

eval \$inlibc

: see if malloc_size_good exists

set malloc_good_size d_malloc_good_size

eval \$inlibc

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_malloc_size.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_strcoll.U 1 2006-08-24 12:32:52Z rmanfredi \$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic Licence,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: Original Author: Andy Dougherty <doughera@lafcol.lafayette.edu>
?RCS:
?RCS: \$Log: d_strcoll.U,v \$
?RCS: Revision 3.0.1.1 1994/08/29 16:12:01 ram
?RCS: patch32: created by ADO
?RCS:
?MAKE:d_strcoll: Inlibc
?MAKE: -pick add \$@ %<
?S:d_strcoll:
?S: This variable conditionally defines HAS_STRCOLL if strcoll() is
?S: available to compare strings using collating information.
?S:.
?C:HAS_STRCOLL:
?C: This symbol, if defined, indicates that the strcoll routine
is
?C: available to compare strings using collating information.
?C:.
?H:#\$d_strcoll HAS_STRCOLL /**/
?H:.
?LINT:set d_strcoll
: see if strcoll exists
set strcoll d_strcoll
eval \$inlibc

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/d_strcoll.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: i_crypt.U,v \$
?RCS:
?RCS: Copyright (c) 2002 Jarkko Hietaniemi
?RCS:
?RCS: You may distribute under the terms of either the GNU General Public
?RCS: License or the Artistic License, as specified in the README file.
?RCS:
?MAKE:i_crypt: Inhdr Hasfield
?MAKE: -pick add \$@ %<
?S:i_crypt:
?S: This variable conditionally defines the I_CRYPT symbol, and indicates
?S: whether a C program should include <crypt.h>.
?S:.
?C:I_CRYPT:
?C: This symbol, if defined, indicates that <crypt.h> exists and
?C: should be included.

```
?C:.
?H:#$i_crypt I_CRYPT /**/
?H:.
?LINT:set i_crypt
: see if this is a crypt.h system
set crypt.h i_crypt
eval $inhdr
```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/perl/i_crypt.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id$
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: $Log: pager.U,v $
?RCS: Revision 3.0.1.2 1995/01/30 14:41:26 ram
?RCS: patch49: ensure dflt gets initialized in case no pagers are found (WED)
?RCS:
?RCS: Revision 3.0.1.1 1994/10/29 16:27:45 ram
?RCS: patch36: replaced Myread by Getfile in the dependency line
?RCS:
?RCS: Revision 3.0 1993/08/18 12:09:30 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:pager: pg more less Getfile Oldconfig
?MAKE: -pick add $@ %<
?S:pager:
?S: This variable contains the name of the preferred pager
on the system.
?S: Usual values are (the full pathnames of) more, less, pg, or cat.
?S:.
: locate the preferred pager for this system
fn=f/
case "$pager" in
")
dflt="
case "$pg" in
/*) dflt=$pg;;
[a-zA-Z]:/*) dflt=$pg;;
```

```

esac
case "$more" in
/*) dflt=$more;;
[a-zA-Z]:/*) dflt=$more;;
esac
case "$less" in
/*) dflt=$less;;
[a-zA-Z]:/*) dflt=$less;;
esac
case "$dflt" in
") dflt=/usr/ucb/more;;
esac
;;
*) dflt="$pager"
;;
esac
?X: Instruct ./getfile to trust the default pager value,
?X: even if it does not begin with a slash. For example, on os2,
?X: pager might be cmd /c more. Also, it might include some options,
?X: such as '/usr/bin/less -R'. ./getfile would report that
?X: "/usr/bin/less -R" doesn't exist.
?X: See comments in Getfile.U
fn="f/($dflt)"
echo " "
rp='What pager is used on your system?'
. ./getfile
pager="$ans"

```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/pager.U
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: mandirstyle.U,v 3.1 1999/07/08 20:52:19 doughera Exp doughera \$

?RCS:

?RCS: Copyright (c) 2000, Andy Dougherty

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 3.0.

?RCS:

?RCS: \$Log: mandirstyle.U,v \$

?RCS:

?MAKE:mandirstyle: test

?MAKE: -pick add \$@ %<

?S:mandirstyle:

?S: This variable indicates the style of man page directory layout
?S: used on this system. Current possible values are sysv, svr4, and
?S: bsd. This information is used for determining where to put various
?S: man pages. Configure uses the BSD convention internally (we've got
?S: to give *some* name to the variables).

?S:

?S: BSD SVR4 Description

Example

?S: Number Number man page

?S: 1 1 Commands cat

?S: 2 2 system calls creat

?S: 3 3 library functions fread

?S: 4 7 special files fd

?S: 5 4 file formats magic

?S: 6 6 games and demos magic

?S: 7 5 miscellany eqnchar

?S: 8 1M Administrative commands mount

?S:

?S: The SysV style is almost the same as SVR4, but instead of

?S: /usr/man/man1, there is /usr/man/u_man/man1.

?S:.

: determine style of existing man page installation

```
if $test "$mandirstyle" = ""; then
```

```
if $test -d /usr/man/u_man/man1; then
```

```
mandirstyle=sysv
```

```
elif $test -d /usr/man/man1m; then
```

```
mandirstyle=svr4
```

```
elif $test -d /usr/share/man/man1m; then
```

```
mandirstyle=svr4
```

```
elif $test -d /usr/share/man/sman1m; then
```

```
mandirstyle=svr4 # Solaris 8 and beyond
```

```
else
```

```
# We could work a lot harder here, but there isn't
```

```
# really
```

```
much point.
```

```
mandirstyle=bsd
```

```
fi
```

```
fi
```

```
echo "You appear to have $mandirstyle style man page directories."
```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/mandirstyle.U
```

No license file was found, but licenses were detected in source scan.

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?MAKE:d_asinh: Inlibc
?MAKE: -pick add \$@ %<
?S:d_asinh:
?S: This variable conditionally defines the HAS_ASINH symbol, which
?S: indicates to the C program that the asinh() routine is available.
?S:.
?C:HAS_ASINH:
?C: This symbol, if defined, indicates that the asinh routine is
?C: available to do the inverse hyperbolic sine function.
?C:.
?H:#\$d_asinh HAS_ASINH /**/
?H:.
?LINT:set d_asinh
: see if asinh exists
set asinh d_asinh
eval \$inlibc

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_asinh.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: libnm.U 1 2006-08-24 12:32:52Z rmanfredi \$
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: \$Log: libnm.U,v \$
?RCS: Revision 3.0.1.1 1997/02/28 16:08:26 ram
?RCS: patch61: replaced .a with \$_a all over the place
?RCS:
?RCS: Revision 3.0 1993/08/18 12:09:01 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:libnm: test Loc libpth _a
?MAKE: -pick add \$@ %<
?S:libnm:
?S: This variable contains the argument to pass to the loader in order
?S: to get the new math library routines. If there is no new math
?S: library, it is null.
?S:.
?T:ans
?O:

```

use libswanted='-lnm' instead (see libs.U).
: see if we should include -lnm
echo " "
if $test -r /usr/lib/libnm$_a || $test -r /usr/local/lib/libnm$_a ; then
echo "New math library found." >&4
libnm='-lnm'
else
ans=`./loc libnm$_a x $libpth`
case "$ans" in
x)
echo "No nm library found--the normal math library will have to do." >&4
libnm=""
;;
*)
echo "New math library found in $ans." >&4
libnm="$ans"
;;
esac
fi

```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/libnm.U
```

No license file was found, but licenses were detected in source scan.

/*

```
* $Id: scandir.C,v 3.0.1.1 1994/01/24 13:58:45 ram Exp ram $
```

*

```
* Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
```

*

```
* You may redistribute only under the terms of the Artistic Licence,
```

```
* as specified in the README file that comes with the distribution.
```

```
* You may reuse parts of this distribution only within the terms of
```

```
* that same Artistic Licence; a copy of which may be found at the root
```

```
* of the source tree for dist 4.0.
```

*

```
* $Log: scandir.C,v $
```

```
* Revision 3.0.1.1 1994/01/24 13:58:45 ram
```

```
* patch16: created
```

*

*/

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/lib/C/fake/scandir.C
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_localtime_r.U,v 0RCS:

?RCS: Copyright (c) 2002,2003 Jarkko Hietaniemi
?RCS: Copyright (c) 2006,2007 H.Merijn Brand
?RCS:
?RCS: You may distribute under the terms of either the GNU General Public
?RCS: License or the Artistic License, as specified in the README file.
?RCS:
?RCS: Generated by the reentr.pl from the Perl 5.8 distribution.
?RCS:
?MAKE:d_localtime_r d_localtime_r_needs_tzset localtime_r_proto: Inlibc \
cat run Protochk Hasproto i_systypes usethreads i_time i_systime \
rm_try Compile extern_C i_stdlib i_unistd i_string i_malloc
?MAKE: -pick add \$@ %<
?S:d_localtime_r:
?S: This variable conditionally defines the HAS_LOCALTIME_R symbol,
?S: which indicates to the C program that the localtime_r()
?S: routine is available.
?S:.
?S:d_localtime_r_needs_tzset:
?S: This variable conditionally defines the LOCALTIME_R_NEEDS_TZSET
?S: symbol, which makes us call tzset before localtime_r()
?S:.
?S:localtime_r_proto:
?S: This
variable encodes the prototype of localtime_r.
?S: It is zero if d_localtime_r is undef, and one of the
?S: REENTRANT_PROTO_T_ABC macros of reentr.h if d_localtime_r
?S: is defined.
?S:.
?C:HAS_LOCALTIME_R:
?C: This symbol, if defined, indicates that the localtime_r routine
?C: is available to localtime re-entrantly.
?C:.
?C:LOCALTIME_R_NEEDS_TZSET:
?C: Many libc's localtime_r implementations do not call tzset,
?C: making them differ from localtime(), and making timezone
?C: changes using \$ENV{TZ} without explicitly calling tzset
?C: impossible. This symbol makes us call tzset before localtime_r
?C:.
?H:%<:#\$d_localtime_r_needs_tzset LOCALTIME_R_NEEDS_TZSET /**/
?H:%<:#ifdef LOCALTIME_R_NEEDS_TZSET
?H:%<:#define L_R_TZSET tzset(),
?H:%<:#else
?H:%<:#define L_R_TZSET
?H:%<:#endif
?H:.
?C:L_R_TZSET:
?C: If localtime_r() needs tzset, it is defined in this define
?C:.

```

?C:LOCALTIME_R_PROTO:
?C: This symbol encodes the prototype of localtime_r.
?C: It is zero if
    d_localtime_r is undef, and one of the
?C: REENTRANT_PROTO_T_ABC macros of reentr.h if d_localtime_r
?C: is defined.
?C:.
?H:#$d_localtime_r HAS_LOCALTIME_R  /**/
?H:#define LOCALTIME_R_PROTO $localtime_r_proto  /**/
?H:.
?T:try hdrs d_localtime_r_proto
?F:!try
: see if localtime_r exists
set localtime_r d_localtime_r
eval $inlibc
case "$d_localtime_r" in
"$define")
hdrs="$i_systypes sys/types.h define stdio.h $i_time time.h $i_systime sys/time.h"
case "$d_localtime_r_proto:$usethreads" in
":define") d_localtime_r_proto=define
set d_localtime_r_proto localtime_r $hdrs
eval $hasproto ;;
*) ;;
esac
case "$d_localtime_r_proto" in
define)
case "$localtime_r_proto" in
"|0) try='struct tm* localtime_r(const time_t*, struct tm*);'
./prochck "$extern_C $try" $hdrs && localtime_r_proto=S_TS ;;
esac
case "$localtime_r_proto" in
"|0) try='int localtime_r(const time_t*, struct tm*);'
./prochck "$extern_C $try" $hdrs && localtime_r_proto=I_TS ;;
esac
case "$localtime_r_proto"
in
"|0) d_localtime_r=undef
localtime_r_proto=0
echo "Disabling localtime_r, cannot determine prototype." >&4 ;;
* ) case "$localtime_r_proto" in
REENTRANT_PROTO*) ;;
*) localtime_r_proto="REENTRANT_PROTO_$localtime_r_proto" ;;
esac
echo "Prototype: $try" ;;
esac
;;
*) case "$usethreads" in
define) echo "localtime_r has no prototype, not using it." >&4 ;;

```

```

esac
d_localtime_r=undef
localtime_r_proto=0
;;
esac
;;
*) localtime_r_proto=0
;;
esac

: see if localtime_r calls tzset
case "$localtime_r_proto" in
REENTRANT_PROTO*)
$cat >try.c <<EOCP
/* Does our libc's localtime_r call tzset ?
* return 0 if so, 1 otherwise.
*/
#ifdef I_SYS_TYPES
#include <sys/types.h>
#endif
#ifdef I_UNISTD
#include <unistd.h>
#endif
#ifdef I_TIME
#include <time.h>
#endif
#ifdef I_STDLIB
#include <stdlib.h>
#endif
#ifdef I_STRING
#include
<string.h>
#else
#include <strings.h>
#endif
#ifdef I_MALLOC
#include <malloc.h>
#endif
int main()
{
time_t t = time(0L);
char w_tz[]="TZ" "=GMT+5",

```

```

e_tz[]="TZ" "=GMT-5",
*tz_e = (char*)malloc(16),
*tz_w = (char*)malloc(16);
struct tm tm_e, tm_w;
memset(&tm_e, '\0', sizeof(struct tm));
memset(&tm_w, '\0', sizeof(struct tm));
strcpy(tz_e, e_tz);
strcpy(tz_w, w_tz);

putenv(tz_e);
localtime_r(&t, &tm_e);

putenv(tz_w);
localtime_r(&t, &tm_w);

if( memcmp(&tm_e, &tm_w, sizeof(struct tm)) == 0 )
return 1;
return 0;
}

```

EOCP

```

set try
if eval $compile; then
  if $run ./try; then
    d_localtime_r_needs_tzset=undef;
  else
    d_localtime_r_needs_tzset=define;
  fi;
else
  d_localtime_r_needs_tzset=undef;
fi;
;;
*)
  d_localtime_r_needs_tzset=undef;
;;
esac
$rm_try

```

Found in path(s):

```

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/threads/d_localtime_r.U

```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_scandir.U 1 2006-08-24 12:32:52Z rmanfredi \$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic Licence,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: d_scandir.U,v \$

?RCS: Revision 3.0.1.1 1994/01/24 14:06:35 ram

?RCS: patch16: created

?RCS:

?MAKE:d_scandir: Inlibc

?MAKE: -pick add \$@ %<

?S:d_scandir:

?S: This variable conditionally defines HAS_SCANDIR if scandir() is

?S: available to scan a directory.

?S:.

?C:HAS_SCANDIR:

?C: This symbol, if defined, indicates that the scandir routine is

?C: available to scan a directory.

?C:.

?H:#\$d_scandir HAS_SCANDIR /**/

?H:.

?LINT:set d_scandir

: see if

scandir exists

set scandir d_scandir

eval \$inlibc

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/d_scandir.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1999, Jarkko Hietaniemi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 3.0.

?RCS:

?MAKE:fflushNULL fflushall: Compile cat rm rm_try test osname run to from \

Oldconfig Myread Setvar echo targethost \

d_sysconf i_unistd d_stdio_stream_array stdio_stream_array i_stdlib

?MAKE: -pick add \$@ %<

?S:fflushNULL:

?S: This symbol, if defined, tells that fflush(NULL) correctly

?S: flushes all pending stdio output without side effects. In

?S: particular, on some platforms calling fflush(NULL) *still*

?S: corrupts STDIN if it is a pipe.

?S:.

?S:fflushall:

?S: This symbol, if defined, tells that to flush

?S: all

pending stdio output one must loop through all

?S: the stdio file handles stored in an array and fflush them.

?S: Note that if fflushNULL is defined, fflushall will not

?S: even be probed for and will be left undefined.

?S:.

?C:FFLUSH_NULL:

?C: This symbol, if defined, tells that fflush(NULL) correctly

?C: flushes all pending stdio output without side effects. In

?C: particular, on some platforms calling fflush(NULL) *still*

?C: corrupts STDIN if it is a pipe.

?C:.

?C:FFLUSH_ALL:

?C: This symbol, if defined, tells that to flush

?C: all pending stdio output one must loop through all

?C: the stdio file handles stored in an array and fflush them.

?C: Note that if fflushNULL is defined, fflushall will not

?C: even be probed for and will be left undefined.

?C:.

?H:#\$fflushNULL FFLUSH_NULL /**/

?H:#\$fflushall FFLUSH_ALL /**/

?H:.

?T:output code

?F:!try.out !try !tryp

: Check how to flush

echo " "

\$cat >&4 <<EOM

Checking how to flush all pending stdio output...

EOM

I only know how to find

the first 32 possibly open files on SunOS.

See also hints/sunos_4_1.sh and util.c --AD

case "\$osname" in

sunos) \$echo '#define PERL_FFLUSH_ALL_FOPEN_MAX 32' > try.c ;;

esac

\$cat >>try.c <<EOCP

#include <stdio.h>

#\$i_stdlib I_STDLIB

#ifdef I_STDLIB

#include <stdlib.h>

#endif

#\$i_unistd I_UNISTD

#ifdef I_UNISTD

```

#include <unistd.h>
#endif
#ifdef _sysconf HAS_SYSCONF
#ifdef _stdio_stream_array HAS_STDIO_STREAM_ARRAY
#ifdef HAS_STDIO_STREAM_ARRAY
#define STDIO_STREAM_ARRAY $stdio_stream_array
#endif
int main() {
FILE* p;
unlink("try.out");
p = fopen("try.out", "w");
#ifdef TRY_FPUTC
fputc('x', p);
#else
#ifdef TRY_FPRINTF
fprintf(p, "x");
#endif
#endif
#ifdef TRY_FFLUSH_NULL
fflush(NULL);
#endif
#ifdef TRY_FFLUSH_ALL
{
long open_max = -1;
#ifdef PERL_FFLUSH_ALL_FOPEN_MAX
open_max = PERL_FFLUSH_ALL_FOPEN_MAX;
#else
if defined(HAS_SYSCONF) && defined(_SC_OPEN_MAX)
open_max = sysconf(_SC_OPEN_MAX);
else
#ifdef FOPEN_MAX
open_max = FOPEN_MAX;
else
#
#ifdef OPEN_MAX
open_max = OPEN_MAX;
else
#ifdef _NFILE
open_max = _NFILE;
endif
endif
endif
endif
#ifdef HAS_STDIO_STREAM_ARRAY
if (open_max > 0) {
long i;
for (i = 0; i < open_max; i++)

```

```

    if (STDIO_STREAM_ARRAY[i]._file >= 0 &&
        STDIO_STREAM_ARRAY[i]._file < open_max &&
        STDIO_STREAM_ARRAY[i]._flag)
        fflush(&STDIO_STREAM_ARRAY[i]);
    }
}
#endif
#endif
_exit(42);
}
EOCP
: first we have to find out how _not_ to flush
$to try.c
if $test "X$fflushNULL" = X -o "X$fflushall" = X; then
    output="
    set try -DTRY_FPUTC
    if eval $compile; then
        $run ./try 2>/dev/null
        code="$?"
        $from try.out
        if $test ! -s try.out -a "X$code" = X42; then
output=-DTRY_FPUTC
        fi
    fi
case "$output" in
")
    set try -DTRY_FPRINTF
    if eval $compile; then
        $run ./try 2>/dev/null
        code="$?"
        $from try.out
        if $test ! -s try.out -a "X$code" = X42; then
output=-DTRY_FPRINTF
        fi
    fi
;;
esac
fi
: check for fflush NULL behavior
case "$fflushNULL" in
") set try -DTRY_FFLUSH_NULL $output
if eval $compile; then
    $run ./try 2>/dev/null
    code="$?"
    $from try.out
    if $test -s try.out -a "X$code" = X42; then
        fflushNULL="$cat try.out`"

```

```

else
  if $test "X$code" != X42; then
    $cat >&4 <<EOM

```

(If this test failed, don't worry, we'll try another method shortly.)

EOM

```

fi
fi
fi

```

```
$rm -f core try.core core.try.*
```

```
case "$fflushNULL" in
```

```
x) $cat >&4 <<EOM
```

Your fflush(NULL) works okay for output streams.

Let's see if it clobbers input pipes...

EOM

```
# As of mid-March 2000 all versions of Solaris appear to have a stdio
```

```
# bug that improperly flushes the input end of pipes. So we avoid the
```

```
# autoflush on fork/system/exec support for now. :-(
```

```
$cat >tryp.c <<EOCP
```

```
#include <stdio.h>
```

```
int
```

```
main(int argc, char **argv)
```

```
{
```

```
    char buf[1024];
```

```
    int i;
```

```
    char *bp = buf;
```

```
    while (1) {
```

```
while ((i = getc(stdin)) != -1
```

```
    && (*bp++ = i) != '\n'
```

```

        && bp < &buf[1024])
```

```
/* DO NOTHING */;
```

```
*bp = '\0';
```

```
fprintf(stdout, "%s", buf);
```

```
fflush(NULL);
```

```
if (i == -1)
```

```
    return 0;
```

```
bp = buf;
```

```
    }
```

```
}
```

EOCP

```
fflushNULL="$define"
```

```
set tryp
```

```
if eval $compile; then
```

```
    $rm -f tryp.out
```

```
    # Copy the .c file to the remote host ($to is an ssh-like if targethost is set)
```

```
    if $test "X$targethost" != X; then
```

```
        $to tryp.c
```

```
        $to tryp
```

```

$run "cat tryp.c | ./tryp " 2>/dev/null > tryp.out
else
$cat tryp.c | $run ./tryp 2>/dev/null > tryp.out
fi
if cmp tryp.c tryp.out >/dev/null 2>&1; then
    $cat >&4 <<EOM
fflush(NULL) seems to behave okay with input streams.
EOM

```

```

fflushNULL="$define"
else
$cat >&4 <<EOM

```

Ouch, fflush(NULL) clobbers input pipes! We will not use it.

```

EOM
fflushNULL="$undef"
fi
fi
$rm -f core tryp.c tryp.core core.tryp.*
;;
") $cat >&4 <<EOM

```

Your fflush(NULL) isn't working (contrary to ANSI C).

```

EOM
fflushNULL="$undef"
;;
*) $cat >&4 <<EOM

```

Cannot figure out whether
your fflush(NULL) works or not.

I'm assuming it doesn't (contrary to ANSI C).

```

EOM
fflushNULL="$undef"
;;
esac
;;
$define|true|[yY]*)
fflushNULL="$define"
;;
*)
fflushNULL="$undef"
;;
esac

```

: check explicit looping only if NULL did not work, and if the pipe

: bug does not show up on an explicit flush too

case "\$fflushNULL" in

"\$undef")

\$cat >tryp.c <<EOCP

#include <stdio.h>

int

main(int argc, char **argv)

{

```

char buf[1024];
int i;
char *bp = buf;
while (1) {
while ((i = getc(stdin)) != -1
    && (*bp++ = i) != '\n'
    && bp < &buf[1024])
/* DO NOTHING */;
*bp = '\0';
fprintf(stdout, "%s", buf);
fflush(stdin);
if (i == -1)
    return 0;
bp = buf;
}
}
EOCP
set tryp
if eval $compile; then
    $rm -f tryp.out
    if $test "X$targethost" != X; then
$to tryp.c
$to tryp
$run "cat tryp.c | ./tryp " 2>/dev/null > tryp.out
    else
$cat tryp.c | $run ./tryp 2>/dev/null > tryp.out
    fi
    if cmp tryp.c tryp.out >/dev/null 2>&1;
then
    $cat >&4 <<EOM

```

Good, at least fflush(stdin) seems to behave okay when stdin is a pipe.

EOM

```

: now check for fflushall behaviour
case "$fflushall" in
") set try -DTRY_FFLUSH_ALL $output
if eval $compile; then
    $cat >&4 <<EOM

```

(Now testing the other method--but note that this also may fail.)

EOM

```

$run ./try 2>/dev/null
code=$?
$from try.out
if $test -s try.out -a "X$code" = X42; then
    fflushall="$cat try.out`"
fi
fi
$rm_try
case "$fflushall" in

```

```
x) $cat >&4 <<EOM
```

Whew. Flushing explicitly all the stdio streams works.

```
EOM
```

```
fflushall="$define"
```

```
::
```

```
") $cat >&4 <<EOM
```

Sigh. Flushing explicitly all the stdio streams doesn't work.

```
EOM
```

```
fflushall="$undef"
```

```
::
```

```
*) $cat >&4 <<EOM
```

Cannot figure out whether flushing stdio streams explicitly works or not.

I'm assuming it doesn't.

```
EOM
```

```
fflushall="$undef"
```

```
::
```

```
esac
```

```
::
```

```
"$define"|true|[yY]*)
```

```
fflushall="$define"
```

```
::
```

```
*)
```

```
fflushall="$undef"
```

```
::
```

```
esac
```

```
else
```

```
$cat >&4 <<EOM
```

All is futile. Even fflush(stdin) clobbers input pipes!

```
EOM
```

```
fflushall="$undef"
```

```
fi
```

```
else
```

```
fflushall="$undef"
```

```
fi
```

```
$rm -f core tryp.c tryp.core core.tryp.*
```

```
::
```

```
*) fflushall="$undef"
```

```
::
```

```
esac
```

```
case "$fflushNULL$fflushall" in
```

```
undefundef)
```

```
$cat <<EOM
```

OK, I give up. I cannot figure out how to flush pending stdio output.

We won't be flushing handles at all before fork/exec/popen.

```
EOM
```

```
::
```

```
esac
$rm_try tryp
```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/perl/flushall.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: uidtype.U,v 3.0.1.3 1994/08/29 16:33:25 ram Exp $
?RCS:
?RCS: Copyright (c) 1991-1993, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 3.0.
?RCS:
?RCS: $Log: uidtype.U,v $
?RCS: Revision 3.0.1.3 1994/08/29 16:33:25 ram
?RCS: patch32: now uses new Typedef unit to compute type information
?RCS:
?RCS: Revision 3.0.1.2 1994/06/20 07:09:36 ram
?RCS: patch30: comment for uidtype referred to the obsoleted symbol
?RCS:
?RCS: Revision 3.0.1.1 1994/05/13 15:28:27 ram
?RCS: patch27: made conformant to its gidtype.U companion
?RCS: patch27: question now explicitly mentions getuid()
?RCS:
?RCS: Revision 3.0 1993/08/18
    12:09:56 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:uidtype: Myread Typedef Findhdr
?MAKE: -pick add $@ %<
?S:uidtype:
?S: This variable defines Uid_t to be something like uid_t, int,
?S: ushort, or whatever type is used to declare user ids in the kernel.
?S:.
?C:Uid_t (UIDTYPE):
?C: This symbol holds the type used to declare user ids in the kernel.
?C: It can be int, ushort, uid_t, etc... It may be necessary to include
?C: <sys/types.h> to get any typedef'ed information.
?C:.
?H:#define Uid_t $uidtype /* UID type */
?H:.
?T:xxx
: see what type uids are declared as in the kernel
```

```

echo " "
echo "Looking for the type for user ids returned by getuid()."
set uid_t uidtype xxx stdio.h sys/types.h
eval $typedef
case "$uidtype" in
xxx)
xxx=`./findhdr sys/user.h`
set `grep '_ruuid;' "$xxx" 2>/dev/null` unsigned short
case $1 in
unsigned) dflt="$1 $2" ;;
*) dflt="$1" ;;
esac
;;
*) dflt="$uidtype";;
esac
case "$uidtype" in
uid_t) echo "uid_t found." ;;
*) rp="What
is the type for user ids returned by getuid()?"
./myread
uidtype="$ans"
;;
esac

```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/typedefs/uidtype.U
```

No license file was found, but licenses were detected in source scan.

```

?RCS: $Id: AAAAA.U 1 2006-08-24 12:32:52Z rmanfredi $
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: $Log: AAAAA.U,v $
?RCS: Revision 3.0.1.4 1994/06/20 06:50:26 ram
?RCS: patch30: changes from Jarkko Hietaniemi are tagged with JHI
?RCS:
?RCS: Revision 3.0.1.3 1994/05/06 14:01:39 ram
?RCS: patch23: initials for Wayne Davison are now WED
?RCS: patch23: added initials for new unit contributor Andy Dougherty
?RCS:
?RCS: Revision 3.0.1.2 1994/01/24 14:01:09 ram

```

?RCS: patch16: make metalint shut up on special unit definition for All target

?RCS:

?RCS: Revision

3.0.1.1 1993/09/13 15:43:57 ram

?RCS: patch10: documents initials used for Wayne Davison's contributions

?RCS:

?RCS: Revision 3.0 1993/08/18 12:04:44 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?X:

?X: The purpose of this file is to supply the head of the Makefile created

?X: by metaconfig. For this reason it must be first in alphabetical order.

?X: The leading '+' in front of the unit name is a hint for metalint, since

?X: the use of that special unit name as a "made" unit is legitimate here.

?X:

?MAKE:+All: Finish

?X:

?X: Throughout the units, the following initials are used to identify comments:

?X:

?X: HMS: Harlan Stenn

?X: RAM: Raphael Manfredi

?X: WED: Wayne Davison (was WAD by mistake--RAM)

?X: ADO: Andy Dougherty

?X: JHI: Jarkko Hietaniemi

?X:

?X: Agreed, this is a weird place to document it, but I couldn't find a better

?X: place to do so. I've bet on the curiosity of users, who would probably

?X: want to know what's in this strangely-named file--RAM.

Found

in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/AAAAA.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: cppfilecom.U 1 2006-08-24 12:32:52Z rmanfredi \$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic Licence,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic Licence; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: Original Author: Graham Stoney <greyham@research.canon.oz.au>

?RCS:

?RCS: \$Log: cppfilecom.U,v \$

?RCS: Revision 3.0 1993/08/18 12:05:37 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?MAKE:cppfilecom cppstdinflags d_cppignhdrs d_cppcanstdin: \
contains package test Myread Oldconfig Loc Setvar cpp cc cat rm

?MAKE: -pick add \$@ %<

?S:cppfilecom:

?S: This variable contains the first part of the string which will invoke
the C preprocessor a file
and produce to standard output, preserving
comments. Typical value of "cc -E -C" or "/lib/cpp -C".

?S:.

?S:cppstdinflags:

?S: This variable contains any flags necessary to get cppfilecom to read
from the standard input.

?S:.

?S:d_cppignhdrs:

?S: This symbol conditionally defines CPP_IGN_HDRS if CPP_FILE_COM ignores
*.h files.

?S:.

?S:d_cppcanstdin:

?S: This symbol conditionally defines CPP_CAN_STDIN if CPP_FILE_COM can
read standard input directly.

?S:.

?C:CPP_FILE_COM (CPPFILECOM):

?C: This symbol contains the first part of the string which will invoke
the C preprocessor a file and produce to standard output, preserving
comments. Typical value of "cc -E -C" or "/lib/cpp -C".

?C:.

?C:CPP_STDIN_FLAGS (CPPSTDINFLAGS):

?C: This variable contains any flags necessary to get CPP_FILE_COM to
read from the standard input.

?C:.

?C:CPP_IGN_HDRS (CPPIGNHDRS):

?C: This symbol is defined if CPP_FILE_COM ignores *.h files.

?C:.

?C:CPP_CAN_STDIN (CPPCANSTDIN):

?C: This
symbol is defined if CPP_FILE_COM can read standard input
directly.

?C:.

?H:#define CPP_FILE_COM "\$cppfilecom"

?H:#define CPP_STDIN_FLAGS "\$cppstdinflags"

?H:#\$d_cppignhdrs CPP_IGN_HDRS /* does CPP ignore .h files? */

?H:#\$d_cppcanstdin CPP_CAN_STDIN /* can CPP read stdin directly? */

?H:.

?T:cont

?F:!testcpp.c !testcpp.h !testcpp.out

```
?LINT:set d_cppcanstdin d_cppignhdrs
?LINT:usefile testcpp.c testcpp.out
: see how we invoke the C preprocessor
$cat <<EOM
```

\$package needs to be able to preprocess its input files in a mode which preserves comments, which is often not the default behaviour. It should run the C preprocessor you will use when compiling your own source code, which should be ISO/ANSI C compliant if you want \$package to handle the latest standard C. I will try to guess, but I might guess wrongly because it is not necessarily the same preprocessor used to build \$package.

```
EOM
$cat <<'EOT' >testcpp.c
#define ABC abc
#define XYZ xyz
ABC.XYZ
/* comment */
EOT
:
if $test "X$cppfilecom"
  != "X" && \
  $cppfilecom testcpp.c </dev/null >testcpp.out 2>/dev/null && \
  $contains 'abc.*xyz' testcpp.out >/dev/null 2>&1 && \
  $contains comment testcpp.out >/dev/null 2>&1
then
  echo "You used to use $cppfilecom so we'll use that again."
elif echo 'Maybe "$cc" -E -C" will work...' && \
  $cc -E -C testcpp.c </dev/null >testcpp.out 2>/dev/null && \
  $contains 'abc.*xyz' testcpp.out >/dev/null 2>&1 && \
  $contains comment testcpp.out >/dev/null 2>&1
then
  echo "It works!"
  cppfilecom="$cc -E -C"
elif echo 'Nope...maybe ""$cc"" -P -C" will work...' && \
  $cc -P -C testcpp.c </dev/null >testcpp.out 2>/dev/null && \
  $contains 'abc.*xyz' testcpp.out >/dev/null 2>&1 && \
  $contains comment testcpp.out >/dev/null 2>&1
then
  echo "Yup, that does."
  cppfilecom="$cc -P -C"
elif echo 'No such luck, maybe ""$cpp"" -C" will work...' && \
  $cpp -C testcpp.c </dev/null >testcpp.out 2>/dev/null && \
  $contains 'abc.*xyz' testcpp.out >/dev/null 2>&1 && \
  $contains comment testcpp.out
  >/dev/null 2>&1
then
  echo "Yup, it does."
```

```

cppfilecom="$cpp -C"
else
cppfilecom="
$cat <<'EOM'
I can't find a C preprocessor that will preserve comments. Please name one.
EOM
fi
:
dflt="$cppfilecom"
cont=true
while $test "$cont" ; do
echo " "
rp="How should $package run your preprocessor preserving comments?"
. ./myread
cppfilecom="$ans"
$cppfilecom testcpp.c >testcpp.out 2>&1
if $contains 'abc.*xyz' testcpp.out >/dev/null 2>&1 && \
$contains comment testcpp.out >/dev/null 2>&1
then
echo "OK, that will do."
cont="
else
echo "Sorry, I can't get that to work."
fi
done

@if CPP_IGN_HDRS || d_cppignhdrs
: Now see if it ignores header files.
cp testcpp.c testcpp.h
$cppfilecom testcpp.h >testcpp.out 2>&1
if $contains 'abc.*xyz' testcpp.out >/dev/null 2>&1 && \
$contains comment testcpp.out >/dev/null 2>&1
then
echo "Terrific; it processes .h files passed on the command line too."
val="$undef"
else
echo "It ignores .h files on the command line; pity."
val="$define"
fi
set
d_cppignhdrs
eval $setvar

@end

@if CPP_STDIN_FLAGS || CPP_CAN_STDIN || cppstdinflags || d_cppcanstdin
: Now see how to send stdin to it.
echo " "
cp testcpp.c testcpp.h

```

```

$cppfilecom <testcpp.h >testcpp.out 2>&1
if $contains 'abc.*xyz' testcpp.out >/dev/null 2>&1 && \
$contains comment testcpp.out >/dev/null 2>&1
then
echo "Great; and it will read stdin if passed no arguments."
val="$define"
cppstdinflags="
else
$cppfilecom - <testcpp.h >testcpp.out 2>&1
if $contains 'abc.*xyz' testcpp.out >/dev/null 2>&1 && \
$contains comment testcpp.out >/dev/null 2>&1
then
echo "Great; and it can read stdin by passing it '-'."
val="$define"
cppstdinflags='- '
else
$cat <<FOO

```

Unfortunately, I can't find an easy way to get that preprocessor to read from standard input. Do you know any flags I can pass it to get it to do so? If that preprocessor can't read directly from standard input, answer 'none'.

```

FOO
val='dunno'
while $test "$val" = "dunno"; do
rp='Flags to get preprocessor
to read stdin?'
dflt='none'
. ./myread
if $test $ans = 'none'; then
echo "Oh well, if $package wants it done, it will do it for itself."
val="$undef"
else
$cppfilecom $ans <testcpp.h >testcpp.out 2>&1
if $contains 'abc.*xyz' testcpp.out >/dev/null 2>&1 && \
$contains comment testcpp.out >/dev/null 2>&1
then
echo "Good; that works fine."
val="$define"
cppstdinflags="$ans"
else
echo "Sorry, I couldn't get that to work."
fi
fi
done
fi
fi
set d_cppcanstdin
eval $setvar

```

```
@end
: cleanup cpp test files anyway
$rm -f testcpp.*
```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/cppfilecom.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: defeditor.U 1 2006-08-24 12:32:52Z rmanfredi $
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: $Log: defeditor.U,v $
?RCS: Revision 3.0.1.1 1995/01/11 15:30:16 ram
?RCS: patch45: can now use the 'vi' variable since path stripping is deferred
?RCS:
?RCS: Revision 3.0 1993/08/18 12:08:05 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:defeditor: Getfile Oldconfig Loc vi
?MAKE: -pick add $@ %<
?S:defeditor:
?S: This variable contains the eventual value of the DEFEDITOR symbol,
?S: which contains the name of the default editor.
?S:.
?C:DEFEDITOR:
?C: This
symbol contains the full pathname of the default editor.
?C:.
?H:#define DEFEDITOR "$defeditor" /**/
?H:.
: determine default editor
echo " "
case "$defeditor" in
")
case "$vi" in
*/*) dflt="$vi";;
*) dflt=/usr/ucb/vi;;
esac
;;
```

```
*) dflt="$defeditor"
;;
esac
fn=f/
rp="What is the default editor on your system?"
./getfile
defeditor="$ans"
```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-  
debian-perl-5.26.1/dist/U/defeditor.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: d_getpgrp2.U 1 2006-08-24 12:32:52Z rmanfredi $
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: $Log: d_getpgrp2.U,v $
?RCS: Revision 3.0 1993/08/18 12:06:15 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:d_getpgrp2: Inlibc
?MAKE: -pick add $@ %<
?S:d_getpgrp2:
?S: This variable conditionally defines the HAS_GETPGRP2 symbol, which
?S: indicates to the C program that the getpgrp2() (as in DG/UX) routine
?S: is available to get the current process group.
?S:.
?C:HAS_GETPGRP2 (GETPGRP2):
?C: This symbol, if defined, indicates that the
?C: getpgrp2() (as in DG/UX)
?C: routine is available to get the current process group.
?C:.
?H:#$d_getpgrp2 HAS_GETPGRP2 /**/
?H:.
?LINT:set d_getpgrp2
: see if getpgrp2 exists
set getpgrp2 d_getpgrp2
eval $inlibc
```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
```

debian-perl-5.26.1/dist/U/d_getpgrp2.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: Extensions.U,v\$

?RCS:

?RCS: Copyright (c) 1996-1998, Andy Dougherty

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?RCS: \$Log: Extensions.U,v \$

?RCS:

?MAKE:known_extensions extensions dynamic_ext static_ext nonxs_ext \
useposix useopcode : \
Myread hint usedl d_sem d_socket i_db i_dbm i_rpcsvdbm i_gdbm \
d_ndbm usethreads use5005threads package test cat rsrc \
d_msg d_shm osname use64bitint i_langinfo d_nl_langinfo \
libs d_cplusplus sed ls rm contains trnl sort

?MAKE: -pick add \$@ %<

?Y:BOTTOM

?S:known_extensions:

?S: This variable holds a list of all extensions (both XS and non-xs)

?S: included in the package source distribution. This information is

?S: only really of use during the Perl build, as the list makes no

?S: distinction between extensions which were build and installed, and

?S: those

?S: which where not. See "extensions" for the list of extensions

?S: actually built and available.

?S:.

?S:dynamic_ext:

?S: This variable holds a list of XS extension files we want to

?S: link dynamically into the package. It is used by Makefile.

?S:.

?S:static_ext:

?S: This variable holds a list of XS extension files we want to

?S: link statically into the package. It is used by Makefile.

?S:.

?S:nonxs_ext:

?S: This variable holds a list of all non-xs extensions built and

?S: installed by the package. By default, all non-xs extensions

?S: distributed will be built, with the exception of platform-specific

?S: extensions (currently only one VMS specific extension).

?S:.

?S:extensions:

?S: This variable holds a list of all extension files (both XS and

?S: non-xs) installed with the package. It is propagated to Config.pm

?S: and is typically used to test whether a particular extension

?S: is available.

?S:.

?S:useposix:

?S: This variable holds either 'true' or 'false' to indicate
 ?S: whether
 the POSIX extension should be used. The sole
 ?S: use for this currently is to allow an easy mechanism
 ?S: for hints files to indicate that POSIX will not compile
 ?S: on a particular system.

?S:.

?S:useopcode:

?S: This variable holds either 'true' or 'false' to indicate
 ?S: whether the Opcode extension should be used. The sole
 ?S: use for this currently is to allow an easy mechanism
 ?S: for users to skip the Opcode extension from the Configure
 ?S: command line.

?S:.

?T:xxx avail_ext this_ext tdir xs_extensions nonxs_extensions find_extensions

?INIT:: set useposix=false in your hint file to disable the POSIX extension.

?INIT:useposix=true

?INIT:: set useopcode=false in your hint file to disable the Opcode extension.

?INIT:useopcode=true

?LINT:extern noextensions

?LINT:extern onlyextensions

?T:keepextensions i

: Check extensions

echo " "

echo "Looking for extensions..." >&4

: If we are using the old config.sh, nonxs_extensions and xs_extensions may
 : contain old or inaccurate
 : or duplicate values.

nonxs_extensions="

xs_extensions="

: We do not use find because it might not be available.

: We do not just use MANIFEST because the user may have dropped
 : some additional extensions into the source tree and expect them
 : to be built.

: Function to recursively find available extensions, ignoring DynaLoader

: NOTE: recursion limit of 10 to prevent runaway in case of symlink madness

: In 5.10.1 and later, extensions are stored in directories
 : like File-Glob instead of the older File/Glob/.

find_extensions='

 for xxx in *; do

 case "\$xxx" in

 DynaLoader|dynaload) ;;

 *)

 this_ext=`echo "\$xxx" | \$sed -e s/-/\\/g`;

 case "\$this_ext" in

```

Scalar/List/Utils) this_ext="List/Util" ;;
PathTools)    this_ext="Cwd" ;;
    esac;
    echo " $xs_extensions $nonxs_extensions" > "$tdir/$$tmp";
    if $contains " $this_ext " "$tdir/$$tmp"; then
echo >&4;
echo "Duplicate directories detected for extension $xxx" >&4;
echo "Configure cannot
correctly recover from this - shall I abort?" >&4;
case "$knowitall" in
    "") dflt=y;;
    *) dflt=n;;
    esac;
    ../UU/myread;
    case "$ans" in
n*|N*) ;;
    *) echo >&4;
        echo "Ok. Stopping Configure." >&4;
        echo "Please remove the duplicate directory (e.g. using git clean) and then re-run Configure" >&4;
        exit 1;;
    esac;
echo "Ok. You will need to correct config.sh before running make." >&4;
    fi;
    $ls -l "$xxx" > "$tdir/$$tmp";
    if $contains "\.xs$" "$tdir/$$tmp" > /dev/null 2>&1; then
xs_extensions="$xs_extensions $this_ext";
    elif $contains "\.c$" "$tdir/$$tmp" > /dev/null 2>&1; then
xs_extensions="$xs_extensions $this_ext";
    elif $test -d "$xxx"; then
nonxs_extensions="$nonxs_extensions $this_ext";
    fi;
    $rm -f "$tdir/$$tmp";
    ;;
    esac;
done'
tdir=`pwd`
cd "$rsrc/cpan"
set X
shift
eval $find_extensions
cd "$rsrc/dist"
set X
shift
eval $find_extensions
cd "$rsrc/ext"
set X
shift
eval $find_extensions

```

```

set X $xs_extensions
shift
xs_extensions=`echo
"$*" | tr ' ' $trnl | $sort | tr $trnl ' '`
set X $nonxs_extensions
shift
nonxs_extensions=`echo "$*" | tr ' ' $trnl | $sort | tr $trnl ' '`
cd "$tdir"
known_extensions=`echo $nonxs_extensions $xs_extensions | tr ' ' $trnl | $sort | tr $trnl ' '`

```

: Now see which are supported on this system.

?X: avail_ext lists available XS extensions.

```
avail_ext="
```

```
for xxx in $xs_extensions ; do
```

```
case "$xxx" in
```

?X: Handle possible DOS 8.3 filename and case alterations

```
Amiga*)
```

```
case "$osname" in
```

```
amigaos) avail_ext="$savail_ext $xxx" ;;
```

```
esac
```

```
::
```

```
DB_File|db_file)
```

```
case "$i_db" in
```

```
$define) avail_ext="$savail_ext $xxx" ;;
```

```
esac
```

```
::
```

```
GDBM_File|gdbm_fil)
```

```
case "$i_gdbm" in
```

```
$define) avail_ext="$savail_ext $xxx" ;;
```

```
esac
```

```
::
```

```
I18N/Langinfo|i18n_lan)
```

```
case "$i_langinfo$d_nl_langinfo" in
```

```
$define$define) avail_ext="$savail_ext $xxx" ;;
```

```
esac
```

```
::
```

```
IPC/SysV|ipc/sysv)
```

: XXX Do we need a useipcsysv variable here

```
case "${d_msg}${d_sem}${d_shm}" in
```

```
*"${define})*
```

```
avail_ext="$savail_ext $xxx" ;;
```

```
esac
```

```
::
```

```
NDBM_File|ndbm_fil)
```

```
case "$d_ndbm" in
```

```
$define)
```

```
case "$osname-$use64bitint" in
```

```
hpux-define)
```

```

case "$libs" in
*-ldb*) avail_ext="$avail_ext $xxx" ;;
esac
;;
*) avail_ext="$avail_ext $xxx" ;;
esac
;;
esac
;;
ODBM_File|odbm_fil)
case "${i_dbm}${i_rpcsvcdbm}" in
*${define}*)
case "$d_cplusplus" in
define) ;; # delete as a function name will not work
*) case "$osname-$use64bitint" in
hpux-define)
case "$libs" in
*-ldb*) avail_ext="$avail_ext $xxx" ;;
esac
;;
*) avail_ext="$avail_ext $xxx" ;;
esac
;;
esac
;;
esac
;;
Opcode|opcode)
case "$useopcode" in
true|define|y) avail_ext="$avail_ext $xxx" ;;
esac
;;
POSIX|posix)
case "$useposix" in
true|define|y) avail_ext="$avail_ext $xxx" ;;
esac
;;
Socket|socket)
case "$d_socket" in
true|$define|y) avail_ext="$avail_ext $xxx" ;;
esac
;;
Sys/Syslog|sys/syslog)
case
$osname in
amigaos) ;; # not really very useful on AmigaOS
*)
: XXX syslog requires socket

```

```

case "$d_socket" in
true|$define|y) avail_ext="$savail_ext $xxx" ;;
esac
;;
esac
;;
Thread|thread)
    case "$usethreads" in
    true|$define|y)
        case "$use5005threads" in
        $define|true|[yY]*) avail_ext="$savail_ext $xxx" ;;
        esac
    esac
    ;;
threads|threads/shared)
    # threads and threads::shared are special cases.
    # To stop people from asking "Perl 5.8.0 was supposed
    # to have this new fancy threads implementation but my
    # perl doesn't have it" and from people trying to
    # (re)install the threads module using CPAN.pm and
    # CPAN.pm then offering to reinstall Perl 5.8.0,
    # the threads.pm and threads/shared.pm will always be
    # there, croaking informatively ("you need to rebuild
    # all of Perl with threads, sorry") when threads haven't
    # been
    compiled in.
    # --jhi
    avail_ext="$savail_ext $xxx"
    ;;
VMS*)
    ;;
Win32*)
    case "$osname" in
    cygwin) avail_ext="$savail_ext $xxx" ;;
    esac
    ;;
XS/APItest|xs/apitest)
    # This is just for testing. Skip it unless we have dynamic loading.

    case "$usedl" in
    $define) avail_ext="$savail_ext $xxx" ;;
    esac
    ;;
XS/Typemap|xs/typemap)
    # This is just for testing. Skip it unless we have dynamic loading.
    case "$usedl" in
    $define) avail_ext="$savail_ext $xxx" ;;
    esac

```

```

;;
*) avail_ext="$avail_ext $xxx"
;;
esac
done

set X $avail_ext
shift
avail_ext="$*"

case "$onlyextensions" in
") ;;
*) keepextensions="
echo "You have requested that only certain extensions be included..." >&4
for i in $onlyextensions; do
case " $avail_ext " in
*" $i "*)
echo "Keeping extension $i."
keepextensions="$keepextensions $i"
;;
*) echo "Ignoring extension $i." ;;
esac
done
avail_ext="$keepextensions"
;;
esac

case
"$noextensions" in
") ;;
*) keepextensions="
echo "You have requested that certain extensions be ignored..." >&4
for i in $avail_ext; do
case " $noextensions " in
*" $i "*) echo "Ignoring extension $i." ;;
*) echo "Keeping extension $i.";
keepextensions="$keepextensions $i"
;;
esac
done
avail_ext="$keepextensions"
;;
esac

: Now see which nonxs extensions are supported on this system.
: For now assume all are.
nonxs_ext="
for xxx in $nonxs_extensions ; do

```

```

case "$xxx" in
VMS*)
;;
*) nonxs_ext="$nonxs_ext $xxx"
;;
esac
done

```

```

set X $nonxs_ext
shift
nonxs_ext="$*"

```

```

case $usedl in
$define)
$cat <<EOM

```

A number of extensions are supplied with \$package. You may choose to compile these extensions for dynamic loading (the default), compile them into the \$package executable (static loading), or not include them at all. Answer "none" to include no extensions.

Note that DynaLoader is always built and need not be mentioned here.

EOM

```

case "$dynamic_ext" in
")
: Exclude those listed in static_ext
dflt="
for xxx in $avail_ext; do
case " $static_ext " in
*" $xxx "*) ;;
*) dflt="$dflt $xxx" ;;
esac
done
set X $dflt
shift
dflt="$*"
;;
*) dflt="$dynamic_ext"
# Perhaps we are reusing an old out-of-date config.sh.
case "$hint" in
previous)
if test X"$dynamic_ext" != X"$avail_ext"; then
$cat <<EOM

```

NOTICE: Your previous config.sh list may be incorrect.

The extensions now available to you are

```

${avail_ext}

```

but the default list from your previous config.sh is

```

${dynamic_ext}

```

```

EOM
    fi
    ;;
esac
;;
esac
case "$dflt" in
") dflt=none;;
esac
rp="What extensions do you wish to load dynamically?"
. ./myread
case "$ans" in
?X: Use ' ' so a subsequent Configure will preserve that value.
none) dynamic_ext=' ' ;;
*) dynamic_ext="$ans" ;;
esac

case "$static_ext" in
")
: Exclude those already listed in dynamic linking
dflt="
for
xxx in $avail_ext; do
    case " $dynamic_ext " in
    *" $xxx "*) ;;
    *) dflt="$dflt $xxx" ;;
    esac
done
set X $dflt
shift
dflt="$*"
;;
*) dflt="$static_ext"
;;
esac

case "$dflt" in
") dflt=none;;
esac
rp="What extensions do you wish to load statically?"
. ./myread
case "$ans" in
?X: Use ' ' so a subsequent Configure will preserve that value.
none) static_ext=' ' ;;
*) static_ext="$ans" ;;
esac
;;

```

*)

```
$cat <<EOM
```

A number of extensions are supplied with \$package. Answer "none" to include no extensions.

Note that DynaLoader is always built and need not be mentioned here.

```
EOM
```

```
case "$static_ext" in
  ") dflt="$avail_ext" ;;
  *) dflt="$static_ext"
  # Perhaps we are reusing an old out-of-date config.sh.
  case "$hint" in
    previous)
      if test X"$static_ext" != X"$avail_ext"; then
        $cat <<EOM
```

NOTICE: Your previous config.sh list may be incorrect.

The extensions now available to you are

```
${avail_ext}
```

but the default list from your previous config.sh is

```
${static_ext}
```

```
EOM
```

```
fi
```

```
::
```

```
esac
```

```
::
```

```
esac
```

```
:
```

Exclude those that are not xs extensions

```
case "$dflt" in
```

```
) dflt=none;;
```

```
esac
```

```
rp="What extensions do you wish to include?"
```

```
. ./myread
```

```
case "$ans" in
```

?X: Use ' ' so a subsequent Configure will preserve that value.

```
none) static_ext=' ';;
```

```
*) static_ext="$ans" ;;
```

```
esac
```

```
::
```

```
esac
```

```
#
```

```
# Encode is a special case. If we are building Encode as a static
```

```
# extension, we need to explicitly list its subextensions as well.
```

```
# For other nested extensions, this is handled automatically by
```

```
# the appropriate Makefile.PL.
```

```
case " $static_ext " in
```

```
*" Encode "*) # Add the subextensions of Encode
```

```

cd "$src/cpan"
for xxx in `ls Encode/*/Makefile.PL|awk -F/ '{print $2}'`; do
  static_ext="$static_ext Encode/$xxx"
  known_extensions="$known_extensions Encode/$xxx"
done
cd "$dir"
;;
esac

set X $dynamic_ext $static_ext $nonxs_ext
shift
extensions="$*"

# Sanity check: We require an extension suitable for use with
# AnyDBM_File, as well as Fcntl and
# IO. (Failure to have these
# should show up as failures in the test suite, but it's helpful to
# catch them now.) The 'extensions' list is normally sorted
# alphabetically, so we need to accept either
# DB_File ... Fcntl ... IO ...
# or something like
# Fcntl ... NDBM_File ... IO ....
case "$extensions" in
  *_File "*" Fcntl "*" IO "*" ) ;; # DB_File
  *_File "*" Fcntl "*" IO "*" ) ;; # GDBM_File
  *_File "*" IO "*" *_File "*" ) ;; # NDBM_File
  *) echo "WARNING: Extensions DB_File or *_DBM_File, Fcntl, and IO not configured." >&4
     echo "WARNING: The Perl you are building will be quite crippled." >& 4
     ;;
esac

```

Found in path(s):

```

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/perl/Extensions.U

```

No license file was found, but licenses were detected in source scan.

```

?RCS: $Id: d_setnetent_r.U,v 0RCS:
?RCS: Copyright (c) 2002,2003 Jarkko Hietaniemi
?RCS:
?RCS: You may distribute under the terms of either the GNU General Public
?RCS: License or the Artistic License, as specified in the README file.
?RCS:
?RCS: Generated by the reentr.pl from the Perl 5.8 distribution.
?RCS:
?MAKE:d_setnetent_r setnetent_r_proto: Inlibc Protochk Hasproto i_systypes \
  usethreads i_netdb extern_C
?MAKE:-pick add $@ %<
?S:d_setnetent_r:

```

?S: This variable conditionally defines the HAS_SETNETENT_R symbol,
 ?S: which indicates to the C program that the setnetent_r()
 ?S: routine is available.
 ?S:.
 ?S:setnetent_r_proto:
 ?S: This variable encodes the prototype of setnetent_r.
 ?S: It is zero if d_setnetent_r is undef, and one of the
 ?S: REENTRANT_PROTO_T_ABC macros of reentr.h if d_setnetent_r
 ?S: is defined.
 ?S:.
 ?C:HAS_SETNETENT_R:
 ?C: This symbol, if defined, indicates that the setnetent_r routine
 ?C: is
 available to setnetent re-entrantly.
 ?C:.
 ?C:SETNETENT_R_PROTO:
 ?C: This symbol encodes the prototype of setnetent_r.
 ?C: It is zero if d_setnetent_r is undef, and one of the
 ?C: REENTRANT_PROTO_T_ABC macros of reentr.h if d_setnetent_r
 ?C: is defined.
 ?C:.
 ?H:#\$d_setnetent_r HAS_SETNETENT_R /**/
 ?H:#define SETNETENT_R_PROTO \$setnetent_r_proto /**/
 ?H:.
 ?T:try hdrs d_setnetent_r_proto
 : see if setnetent_r exists
 set setnetent_r d_setnetent_r
 eval \$inlibc
 case "\$d_setnetent_r" in
 "\$define")
 hdrs="\$i_systypes sys/types.h define stdio.h \$i_netdb netdb.h"
 case "\$d_setnetent_r_proto:\$susetheads" in
 ":define") d_setnetent_r_proto=define
 set d_setnetent_r_proto setnetent_r \$hdrs
 eval \$hasproto ;;
 *) ;;
 esac
 case "\$d_setnetent_r_proto" in
 define)
 case "\$setnetent_r_proto" in
 "|0) try='int setnetent_r(int, struct netent_data*);'
 ./protochk "\$extern_C \$try" \$hdrs && setnetent_r_proto=I_ID ;;
 esac
 case "\$setnetent_r_proto" in
 "|0) try='void setnetent_r(int, struct netent_data*);'
 ./protochk
 "\$extern_C \$try" \$hdrs && setnetent_r_proto=V_ID ;;
 esac

```

case "$setnetent_r_proto" in
"|0) d_setnetent_r=undef
    setnetent_r_proto=0
    echo "Disabling setnetent_r, cannot determine prototype." >&4 ;;
*) case "$setnetent_r_proto" in
REENTRANT_PROTO*) ;;
*) setnetent_r_proto="REENTRANT_PROTO_$setnetent_r_proto" ;;
esac
echo "Prototype: $try" ;;
esac
;;
*) case "$susetthreads" in
define) echo "setnetent_r has no prototype, not using it." >&4 ;;
esac
d_setnetent_r=undef
setnetent_r_proto=0
;;
esac
;;
*) setnetent_r_proto=0
;;
esac

```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/threads/d_setnetent_r.U
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: i_syspoll.U 15 2006-08-30 18:21:51Z rmanfredi \$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic Licence,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic Licence; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?MAKE:i_syspoll: Inhdr

?MAKE: -pick add \$@ %<

?S:i_syspoll:

?S: This variable conditionally defines the I_SYS_POLL symbol, which

?S: indicates to the C program that it should include <sys/poll.h>.

?S:.

?C:I_SYS_POLL:

?C: This symbol, if defined, indicates that the program may include

?C: <sys/poll.h>. When I_POLL is also defined, it's probably safest

?C: to only include <poll.h>.

```
?C:.
?H:#$i_syspoll I_SYS_POLL /**/
?H:.
?LINT:set i_syspoll
: see if there is
  a sys/poll.h file
set sys/poll.h i_syspoll
eval $inhdr
```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/i_syspoll.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id$
?RCS:
?RCS: Copyright (c) 1998 Jarkko Hietaniemi
?RCS:
?RCS: You may distribute under the terms of either the GNU General Public
?RCS: License or the Artistic License, as specified in the README file.
?RCS:
?MAKE:d_recvmsg: Inlibc
?MAKE: -pick add $@ %<
?S:d_recvmsg:
?S: This variable conditionally defines the HAS_RECVMSG symbol, which
?S: indicates to the C program that the recvmsg() routine is available.
?S:.
?C:HAS_RECVMSG:
?C: This symbol, if defined, indicates that the recvmsg routine is
?C: available to send structured socket messages.
?C:.
?H:#$d_recvmsg HAS_RECVMSG /**/
?H:.
?LINT:set d_recvmsg
: see if recvmsg exists
set recvmsg d_recvmsg
eval $inlibc
```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/perl/d_recvmsg.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: i_termio.U 1 2006-08-24 12:32:52Z rmanfredi $
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
```

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic Licence; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: i_termio.U,v \$

?RCS: Revision 3.0.1.4 1994/10/29 16:20:54 ram

?RCS: patch36: call ./usg and ./Cppsymb explicitly instead of relying on PATH

?RCS:

?RCS: Revision 3.0.1.3 1994/08/29 16:26:38 ram

?RCS: patch32: don't include all three I_* symbols in config.h

?RCS: patch32: (had forgotten to undo this part last time)

?RCS:

?RCS: Revision 3.0.1.2 1994/05/13 15:25:03 ram

?RCS: patch27: undone ADO's fix in previous patch since it was useless

?RCS:

?RCS:

Revision 3.0.1.1 1994/05/06 15:05:23 ram

?RCS: patch23: now include all three defines in config.h (ADO)

?RCS:

?RCS: Revision 3.0 1993/08/18 12:08:44 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?MAKE:i_termio i_sgtty i_termios: test Inlibc Cppsymb Guess Setvar Findhdr Warn run

?MAKE: -pick add \$@ %<

?S:i_termio:

?S: This variable conditionally defines the I_TERMIO symbol, which

?S: indicates to the C program that it should include <termio.h> rather

?S: than <sgtty.h>.

?S:.

?S:i_termios:

?S: This variable conditionally defines the I_TERMIOS symbol, which

?S: indicates to the C program that the POSIX <termios.h> file is

?S: to be included.

?S:.

?S:i_sgtty:

?S: This variable conditionally defines the I_SGTTY symbol, which

?S: indicates to the C program that it should include <sgtty.h> rather

?S: than <termio.h>.

?S:.

?C:I_TERMIO:

?C: This symbol, if defined, indicates that the program should include

?C: <termio.h> rather than <sgtty.h>. There are also differences in

?C: the

ioctl() calls that depend on the value of this symbol.

?C:.

?C:I_TERMIOS:

?C: This symbol, if defined, indicates that the program should include

?C: the POSIX termios.h rather than sgtty.h or termio.h.

?C: There are also differences in the ioctl() calls that depend on the

?C: value of this symbol.

?C:.

?C:I_SGTTY:

?C: This symbol, if defined, indicates that the program should include

?C: <sgtty.h> rather than <termio.h>. There are also differences in

?C: the ioctl() calls that depend on the value of this symbol.

?C:.

?H:#\$i_termio I_TERMIO /**/

?H:#\$i_termios I_TERMIOS /**/

?H:#\$i_sgtty I_SGTTY /**/

?H:.

?T:val2 val3

?LINT:set i_termio i_sgtty i_termios

: see if this is a termio system

val="\$undef"

val2="\$undef"

val3="\$undef"

?X: Prefer POSIX-approved termios.h over all else

```

if $test `./findhdr termios.h`; then
    set tcsetattr i_termios
    eval $inlibc
    val3="$i_termios"
fi
echo " "
case "$val3" in
    "$define") echo "You have POSIX termios.h... good!" >&4;
    *)
if ./Cppsymb pyr; then
    case "$run /bin/universe" in
ucb) if $test `./findhdr sgtty.h`; then
        val2="$define"
        echo "<sgtty.h> found." >&4
        else
        echo "System is pyramid with BSD universe."
        ./warn "<sgtty.h> not found--you could have problems."
        fi;;
*) if $test `./findhdr termio.h`; then
        val="$define"
        echo "<termio.h> found." >&4
        else
        echo "System is pyramid with USG universe."
        ./warn "<termio.h> not found--you could have problems."
        fi;;
esac

```

?X: Start with USG to avoid problems if both usg/bsd was guessed

elif ./usg; then

```

    if $test `./findhdr termio.h`; then
    echo "<termio.h> found." >&4
    val="$define"
    elif $test `./findhdr sgtty.h`; then
    echo "<sgtty.h> found." >&4
    val2="$define"
    else
    ./warn "Neither <termio.h> nor <sgtty.h> found--cross fingers!"
    fi
else
    if $test `./findhdr sgtty.h`; then
    echo "<sgtty.h> found." >&4
    val2="$define"
    elif $test `./findhdr termio.h`; then
    echo "<termio.h>
found." >&4
    val="$define"
    else
    ./warn "Neither <sgtty.h> nor <termio.h> found--cross fingers!"
    fi
fi;;
esac
set i_termio; eval $setvar
val=$val2; set i_sgtty; eval $setvar
val=$val3; set i_termios; eval $setvar

```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/modified/i_termio.U
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: usrinc.U,v \$

?RCS: Revision 3.0.1.3 1997/02/28 16:27:12 ram

?RCS: patch61: don't ask for the include path unless they are on a MIPS

?RCS:

?RCS: Revision 3.0.1.2 1995/05/12 12:24:36 ram

?RCS: patch54: ensure that ./mips always exists (ADO)

?RCS:

```

?RCS: Revision 3.0.1.1 1994/05/06 15:18:31 ram
?RCS: patch23: ensure usrinc value is preserved across sessions (WED)
?RCS:
?RCS: Revision 3.0 1993/08/18 12:09:58 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:usrinc incpath mips_type:
test cat echo n c Getfile Guess \
Oldconfig eunicefix contains rm
?MAKE: -pick add $@ %<
?S:usrinc:
?S: This variable holds the path of the include files, which is
?S: usually /usr/include. It is mainly used by other Configure units.
?S:.
?S:incpath:
?S: This variable must precede the normal include path to get the
?S: right one, as in "$incpath/usr/include" or "$incpath/usr/lib".
?S: Value can be "" or "/bsd43" on mips.
?S:.
?S:mips_type:
?S: This variable holds the environment type for the mips system.
?S: Possible values are "BSD 4.3" and "System V".
?S:.
?D:usrinc='/usr/include'
?LINT:create mips
?T:xxx_prompt
?F:./mips
: What should the include directory be ?
echo " "
$echo $n "Hmm... $c"
dflt='/usr/include'
incpath=""
?X: mips_type is used later, to add -DSYSTYPE_BSD43 to cppflags if needed.
mips_type=""
?X:
?X: Cannot put the following in Guess, or we get a circular dependency.
?X:
if $test -f /bin/mips && /bin/mips; then
echo "Looks like a MIPS system..."
$cat >usr.c
<<'EOCP'
#ifdef SYSTYPE_BSD43
/bsd43
#endif
EOCP
if cc -E usr.c > usr.out && $contains /usr.out >/dev/null 2>&1; then
dflt='/bsd43/usr/include'
incpath='/bsd43'

```

```

mips_type='BSD 4.3'
else
mips_type='System V'
fi
$rm -f usr.c usr.out
echo "and you're compiling with the $mips_type compiler and libraries."
xxx_prompt=y
echo "exit 0" >mips
else
echo "Doesn't look like a MIPS system."
xxx_prompt=n
echo "exit 1" >mips
fi
chmod +x mips
$unicefix mips
case "$usrinc" in
") ;;
*) dflt="$usrinc";;
esac
case "$xxx_prompt" in
y) fn=d/
echo " "
rp='Where are the include files you want to use?'
./getfile
usrinc="$ans"
;;
*) usrinc="$dflt"
;;
esac

```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/usrinc.U
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: Warn.U 1 2006-08-24 12:32:52Z rmanfredi \$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic Licence,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic Licence; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: Extract.U,v \$

?X:

?X: This unit produces a shell script which can be run in order to emit

?X: an important warning to the user, which will be remembered and shown

?X: at the end of the Configure run as well.

?X:

?X: A typical use would be:

?X:

?X: ./warn <<EOM

?X: Problem with your C compiler: can't turn debugging on.

?X: EOM

?X:

?X: or:

?X:

?X: ./warn "Problem with your C compiler: can't turn debugging on."

?X:

?X: Which will both display to the user:

?X:

?X: ***

WARNING:

?X: *** Problem with your C compiler: can't turn debugging on.

?X: ***

?X:

?MAKE:Warn: startsh eunicefix

?MAKE: -pick add \$@ %<

?F:./warn

: script used to emit important warnings

cat >warn <<EOS

\$startsh

?X: Read the whole warning message from stdin into a temporary file

?X: when no argument was supplied.

```
if test $# -gt 0; then
```

```
  echo "$@" >msg
```

```
else
```

```
  cat >msg
```

```
fi
```

?X: Emit the warning, prefixing all lines with '*** '

```
echo "*** WARNING:" >&4
```

```
sed -e 's/^/*** /' <msg >&4
```

```
echo "*** " >&4
```

?X: Save the warning in the logs, which will be shown again at the end

```
cat msg >>config.msg
```

```
echo " " >>config.msg
```

```
rm -f msg
```

```
EOS
```

```
chmod +x warn
```

```
$eunicefix warn
```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/Warn.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: d_shmdt.U 1 2006-08-24 12:32:52Z rmanfredi $
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: $Log: d_shmdt.U,v $
?RCS: Revision 3.0 1993/08/18 12:07:19 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:d_shmdt: Inlibc
?MAKE: -pick add $@ %<
?S:d_shmdt:
?S: This variable conditionally defines the HAS_SHMDT symbol, which
?S: indicates to the C program that the shmdt() routine is available.
?S:.
?C:HAS_SHMDT:
?C: This symbol, if defined, indicates that the shmdt() routine is
?C: available to detach a shared memory segment from the process
?C: space.
?C:.
?H:#$d_shmdt HAS_SHMDT /**/
?H:.
?LINT:set d_shmdt
: see if shmdt exists
set shmdt d_shmdt
eval $inlibc
```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/d_shmdt.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: d_dosuid.U 1 2006-08-24 12:32:52Z rmanfredi $
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
```

?RCS:
?RCS: Tye McQueen <tye@metronet.com> added safe setuid script checks.
?RCS:
?RCS: \$Log: d_dosuid.U,v \$
?RCS: Revision 3.0.1.2 1997/02/28 15:33:03 ram
?RCS: patch61: moved unit to TOP via a ?Y: layout directive
?RCS: patch61: tell them /dev/fd is not about floppy disks
?RCS:
?RCS: Revision 3.0.1.1 1994/10/29 16:12:08 ram
?RCS: patch36: added checks for secure setuid scripts (Tye McQueen)
?RCS:
?RCS: Revision 3.0 1993/08/18 12:05:55 ram
?RCS: Baseline for
dist 3.0 netwide release.
?RCS:
?MAKE:d_dosuid d_suidsaf: cat contains ls rm test Myread Setvar \
Oldconfig Guess package hint patchlevel
?MAKE: -pick add \$@ %<
?S:d_suidsaf:
?S: This variable conditionally defines SETUID_SCRIPTS_ARE_SECURE_NOW
?S: if setuid scripts can be secure. This test looks in /dev/fd/.
?S:.
?S:d_dosuid:
?S: This variable conditionally defines the symbol DOSUID, which
?S: tells the C program that it should insert setuid emulation code
?S: on hosts which have setuid #! scripts disabled.
?S:.
?C:SETUID_SCRIPTS_ARE_SECURE_NOW:
?C: This symbol, if defined, indicates that the bug that prevents
?C: setuid scripts from being secure is not present in this kernel.
?C:.
?C:DOSUID:
?C: This symbol, if defined, indicates that the C program should
?C: check the script that it is executing for setuid/setgid bits, and
?C: attempt to emulate setuid/setgid on systems that have disabled
?C: setuid #! scripts because the kernel can't do it securely.
?C: It is up to the package
designer to make sure that this emulation
?C: is done securely. Among other things, it should do an fstat on
?C: the script it just opened to make sure it really is a setuid/setgid
?C: script, it should make sure the arguments passed correspond exactly
?C: to the argument on the #! line, and it should not trust any
?C: subprocesses to which it must pass the filename rather than the
?C: file descriptor of the script to be executed.
?C:.
?H:#\$d_suidsaf SETUID_SCRIPTS_ARE_SECURE_NOW /**/
?H:#\$d_dosuid DOSUID /**/
?H:.

```
?Y:TOP
?F:!reflect
?LINT: set d_suidsaf
: see if setuid scripts can be secure
$cat <<EOM
```

Some kernels have a bug that prevents setuid #! scripts from being secure. Some sites have disabled setuid #! scripts because of this.

First let's decide if your kernel supports secure setuid #! scripts.
(If setuid #! scripts would be secure but have been disabled anyway, don't say that they are secure if asked.)

EOM

```
val="$undef"
if $test -d /dev/fd; then
  echo "#!$ls" >reflect
  chmod
  +x,u+s reflect
  ./reflect >flect 2>&1
  if $contains "/dev/fd" flect >/dev/null; then
    echo "Congratulations, your kernel has secure setuid scripts!" >&4
    val="$define"
  else
    $cat <<EOM
```

If you are not sure if they are secure, I can check but I'll need a username and password different from the one you are using right now.
If you don't have such a username or don't want me to test, simply enter 'none'.

EOM

```
rp='Other username to test security of setuid scripts with?'
dflt='none'
. ./myread
case "$ans" in
n|none)
  case "$d_suidsaf" in
  *) echo "I'll assume setuid scripts are *not* secure." >&4
    dflt=n;;
  "$undef")
    echo "Well, the $hint value is *not* secure." >&4
    dflt=n;;
  *) echo "Well, the $hint value *is* secure." >&4
    dflt=y;;
  esac
;;
*)
```

```

$rm -f reflect flect
echo "#!$ls" >reflect
chmod +x,u+s reflect
echo >flect
chmod a+w flect
echo "'su" will (probably) prompt you for "'$ans's password."
su $ans -c './reflect
>flect'
if $contains "/dev/fd" flect >/dev/null; then
echo "Okay, it looks like setuid scripts are secure." >&4
dflt=y
else
echo "I don't think setuid scripts are secure." >&4
dflt=n
fi
;;
esac
rp='Does your kernel have *secure* setuid scripts?'
./myread
case "$ans" in
[yY]*) val="$define";;
*) val="$undef";;
esac
fi
else
echo "I don't think setuid scripts are secure (no /dev/fd directory)." >&4
echo "(That's for file descriptors, not floppy disks.)"
val="$undef"
fi
set d_suidsaf
eval $setvar
$rm -f reflect flect

```

```

: now see if they want to do setuid emulation
if $test $patchlevel -lt 11; then
echo " "
val="$undef"
case "$d_suidsaf" in
"$define")
val="$undef"
echo "No need to emulate SUID scripts since they are secure here." >&4
;;
*)
$cat <<EOM

```

Some systems have disabled setuid scripts, especially systems where setuid scripts cannot be secure. On systems where setuid scripts have been disabled, the setuid/setgid bits on scripts are

currently
useless. It is possible for \$package to detect those bits and emulate
setuid/setgid in a secure fashion. This emulation will only work if
setuid scripts have been disabled in your kernel.

```
EOM
case "$d_dosuid" in
"$define") dflt=y ;;
*) dflt=n ;;
esac
rp="Do you want to do setuid/setgid emulation?"
. ./myread
case "$ans" in
[yY]*) val="$define";;
*) val="$undef";;
esac
;;
esac
set d_dosuid
eval $setvar
else
  case "$d_dosuid" in
"$define")
cat >&4 <<EOH
```

SUID emulation has been removed for 5.12
Please re-run Configure without -Dd_dosuid

```
EOH
exit 1;
;;
  esac
  d_dosuid=undef
fi
```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/modified/d_dosuid.U
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1999, Jarkko Hietaniemi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 3.0.
?RCS:
?MAKE:d_ustat: Inlibc
?MAKE: -pick add \$@ %<
?S:d_ustat:
?S: This variable conditionally defines HAS_USTAT if ustat() is
?S: available to query file system statistics by dev_t.
?S:.
?C:HAS_USTAT:
?C: This symbol, if defined, indicates that the ustat system call is
?C: available to query file system statistics by dev_t.
?C:.
?H:#\$d_ustat HAS_USTAT /**/
?H:.
?LINT:set d_ustat
: see if ustat exists
set ustat d_ustat
eval \$inlibc

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_ustat.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$
?RCS:
?RCS: Copyright (c) 1998 Jarkko Hietaniemi
?RCS:
?RCS: You may distribute under the terms of either the GNU General Public
?RCS: License or the Artistic License, as specified in the README file.
?RCS:
?MAKE:d_atoll: Inlibc
?MAKE: -pick add \$@ %<
?S:d_atoll:
?S: This variable conditionally defines the HAS_ATOLL symbol, which
?S: indicates to the C program that the atoll() routine is available.
?S:.
?C:HAS_ATOLL:
?C: This symbol, if defined, indicates that the atoll routine is
?C: available to convert strings into long longs.
?C:.
?H:#\$d_atoll HAS_ATOLL /**/
?H:.
?LINT:set d_atoll
: see if atoll exists
set atoll d_atoll
eval \$inlibc

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/atoll.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: i_iconv.U,v \$

?RCS:

?RCS: Copyright (c) 2000 Jarkko Hietaniemi

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?MAKE:i_iconv: Inhdr Hasfield

?MAKE: -pick add \$@ %<

?S:i_iconv:

?S: This variable conditionally defines the I_ICONV symbol, and indicates

?S: whether a C program should include <iconv.h>.

?S:.

?C:I_ICONV:

?C: This symbol, if defined, indicates that <iconv.h> exists and

?C: should be included.

?C:.

?H:#\$i_iconv I_ICONV /**/

?H:.

?LINT:set i_iconv

: see if this is a iconv.h system

set iconv.h i_iconv

eval \$inhdr

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/i_iconv.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: perl5.U,v \$

?RCS:

?RCS: Copyright (c) 2000 Andrew Dougherty

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?RCS: \$Log: perl5.U,v \$

?RCS:

?X:

?X: The purpose of this unit is to locate a previously installed

?X: version of perl5 suitable for running inc_version_list.U.

?X: We check for 5.005 and later because inc_version_list is

?X: irrelevant for earlier versions.

```

?X:
?MAKE:perl5: path_sep binexp test sed exe_ext
?MAKE: -pick add $@ %<
?Y:TOP
?S:perl5:
?S: This variable contains the full path (if any) to a previously
?S: installed perl5.005 or later suitable for running the script
?S: to determine inc_version_list.
?S:.
?T: tdir
: Find perl5.005 or later.
echo "Looking for a previously installed perl5.005 or later... "
case "$perl5" in
") for tdir in `echo "$binexp$path_sep$PATH" | $sed "s/$path_sep/
/g"; do
: Check if this perl is recent and can load a simple module
if $test -x $tdir/perl5$exe_ext && $tdir/perl -Mless -e 'use 5.005;' >/dev/null 2>&1; then
perl5=$tdir/perl
break;
elif $test -x $tdir/perl5$exe_ext && $tdir/perl5 -Mless -e 'use 5.005;' >/dev/null 2>&1; then
perl5=$tdir/perl5
break;
fi
done
;;
*) perl5="$perl5"
;;
esac
case "$perl5" in
") echo "None found. That's ok.";;
*) echo "Using $perl5." ;;
esac

```

Found in path(s):

```

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/installdirs/perl5.U

```

No license file was found, but licenses were detected in source scan.

```

?RCS: $Id$

```

```

?RCS:

```

```

?RCS: Copyright (c) 1998 Jarkko Hietaniemi

```

```

?RCS:

```

```

?RCS: You may distribute under the terms of either the GNU General Public

```

```

?RCS: License or the Artistic License, as specified in the README file.

```

```

?RCS:

```

```

?MAKE:d_sendmsg: Inlibc

```

```

?MAKE: -pick add $@ %<

```

```

?S:d_sendmsg:

```

?S: This variable conditionally defines the HAS_SENDMSG symbol, which

?S: indicates to the C program that the sendmsg() routine is available.

?S:.

?C:HAS_SENDMSG:

?C: This symbol, if defined, indicates that the sendmsg routine is

?C: available to send structured socket messages.

?C:.

?H:#\$d_sendmsg HAS_SENDMSG /**/

?H:.

?LINT:set d_sendmsg

: see if sendmsg exists

set sendmsg d_sendmsg

eval \$inlibc

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_sendmsg.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: Typedef.U,v 3.0.1.3 1995/07/25 13:42:07 ram Exp \$

?RCS:

?RCS: Copyright (c) 1991-1993, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 3.0.

?RCS:

?RCS: \$Log: Typedef.U,v \$

?RCS: Revision 3.0.1.3 1995/07/25 13:42:07 ram

?RCS: patch56: added backslash escapes within evals to prevent space problems

?RCS:

?RCS: Revision 3.0.1.2 1994/10/29 16:01:16 ram

?RCS: patch36: don't clobber visible 'val' variable, use 'varval' instead

?RCS:

?RCS: Revision 3.0.1.1 1994/08/29 16:05:14 ram

?RCS: patch32: created

?RCS:

?X:

?X: This unit checks for the definition of a given typedef.

?X:

?X: To use it, say:

?X: set typedef

val_t default [includes]

?X: eval \$typedef

?X:

?MAKE:Typedef: cppstdin cppminus cppflags rm sed contains Oldconfig Myread

?MAKE: -pick add \$@ %<

?LINT:define typedef

?LINT:define typedef_ask

?V:typedef typedef_ask

?S:typedef:

?S: This shell variable is used internally by Configure to check

?S: whether a given typedef is defined or not. A typical use is:

?S: set typedef val_t default [includes]

?S: eval \$typedef

?S: That will return val_t set to default if the typedef was not found,

?S: to typedef otherwise. If no includes are specified, look in sys/types.h.

?S:.

?S:typedef_ask:

?S: This shell variable is used internally by Configure to check

?S: whether a given typedef is defined or not. If it is not defined,

?S: this will call the ./myread script to prompt for an answer.

?S: It is intended to be used to avoid unnecessary prompts.

?S: A typical use is

?S: rp="What is the type for file position used by fsetpos()?"

?S: set fpos_t fpostype long stdio.h sys/types.h

?S: eval \$typedef_ask

?S: This

will set fpostype=fpos_t, if fpos_t is available. Otherwise

?S: it will call myread with a default of 'long', and a prompt of \$rp.

?S:.

?T:type var def inclist varval inc

?F:!temp.c

: define an is-a-typedef? function

```
typedef='type=$1; var=$2; def=$3; shift; shift; shift; inclist=$@;
case "$inclist" in
"" ) inclist="sys/types.h";;
esac;
eval "varval=\$$var";
case "$varval" in
"" )
$rm -f temp.c;
for inc in $inclist; do
echo "#include <$inc>" >>temp.c;
done;
?X: Maybe it's a #define instead of a typedef.
echo "#ifdef $type" >> temp.c;
echo "printf(\"We have $type\");" >> temp.c;
echo "#endif" >> temp.c;
$cp $stdin $cppflags $cppminus < temp.c >temp.E 2>/dev/null;
if $contains $type temp.E >/dev/null 2>&1; then
eval "$var=\$type";
else
eval "$var=\$def";
```

```

fi;
$rm -f temp.?;;
*) eval "$var=\$varval";;
esac'

```

?X: Originally, I eval'd \$typedef and then checked the results against

?X: \$type. Unfortunately, it then became complicated to check

?X: whether you are re-using

an old config.sh value, and the logic got

?X: so convoluted it became easier to just copy the function above

?X: and alter it slightly. A.D. 3/1998

: define an is-a-typedef? function that prompts if the type is not available.

```

typedef_ask='type=$1; var=$2; def=$3; shift; shift; shift; inclist=$@;

```

```

case "$inclist" in

```

```

"")) inclist="sys/types.h";;

```

```

esac;

```

```

eval "varval=\$$var";

```

```

case "$varval" in

```

```

""))

```

```

$rm -f temp.c;

```

```

for inc in $inclist; do

```

```

    echo "#include <$inc>" >>temp.c;

```

```

done;

```

?X: Maybe it's a #define instead of a typedef.

```

echo "#ifdef $type" >> temp.c;

```

```

echo "printf(\"We have $type\");" >> temp.c;

```

```

echo "#endif" >> temp.c;

```

```

$cpstdin $cppflags $cppminus < temp.c >temp.E 2>/dev/null;

```

```

echo " ";

```

```

echo "$rp" | $sed -e "s/What is/Looking for/" -e "s/?/./";

```

```

if $contains $type temp.E >/dev/null 2>&1; then

```

```

    echo "$type found." >&4;

```

```

    eval "$var=\$type";

```

```

else

```

```

    echo "$type NOT found." >&4;

```

```

    dflt="$def";

```

```

    ./myread ;

```

```

    eval "$var=\$ans";

```

```

fi;

```

```

$rm -f temp.?;;

```

```

*) eval "$var=\$varval";;

```

```

esac'

```

Found

in path(s):

```

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/typedefs/Typedef.U

```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: d_readdir_r.U,v 0RCS:
?RCS: Copyright (c) 2002,2003 Jarkko Hietaniemi
?RCS:
?RCS: You may distribute under the terms of either the GNU General Public
?RCS: License or the Artistic License, as specified in the README file.
?RCS:
?RCS: Generated by the reentr.pl from the Perl 5.8 distribution.
?RCS:
?MAKE:d_readdir_r readdir_r_proto: Inlibc Protochk Hasproto i_systypes \
  usethreads i_dirent extern_C
?MAKE: -pick add $@ %<
?S:d_readdir_r:
?S: This variable conditionally defines the HAS_READDIR_R symbol,
?S: which indicates to the C program that the readdir_r()
?S: routine is available.
?S:.
?S:readdir_r_proto:
?S: This variable encodes the prototype of readdir_r.
?S: It is zero if d_readdir_r is undef, and one of the
?S: REENTRANT_PROTO_T_ABC macros of reentr.h if d_readdir_r
?S: is defined.
?S:.
?C:HAS_READDIR_R:
?C: This symbol, if defined, indicates that the readdir_r routine
?C: is available to readdir re-entrantly.
?C:.
?C:READDIR_R_PROTO:
?C: This
  symbol encodes the prototype of readdir_r.
?C: It is zero if d_readdir_r is undef, and one of the
?C: REENTRANT_PROTO_T_ABC macros of reentr.h if d_readdir_r
?C: is defined.
?C:.
?H:#$d_readdir_r HAS_READDIR_R /**/
?H:#define READDIR_R_PROTO $readdir_r_proto /**/
?H:.
?T:try hdrs d_readdir_r_proto
: see if readdir_r exists
set readdir_r d_readdir_r
eval $inlibc
case "$d_readdir_r" in
"$define")
  hdrs="$i_systypes sys/types.h define stdio.h $i_dirent dirent.h"
  case "$d_readdir_r_proto:$usethreads" in
  ":define") d_readdir_r_proto=define
  set d_readdir_r_proto readdir_r $hdrs
```

```

eval $hasproto ;;
*) ;;
esac
case "$d_readdir_r_proto" in
define)
case "$readdir_r_proto" in
"|0) try='int readdir_r(DIR*, struct dirent*, struct dirent**);'
./protochk "$extern_C $try" $hdrs && readdir_r_proto=I_TSR ;;
esac
case "$readdir_r_proto" in
"|0) try='int readdir_r(DIR*, struct dirent*);'
./protochk "$extern_C $try" $hdrs && readdir_r_proto=I_TS
;;
esac
case "$readdir_r_proto" in
"|0) d_readdir_r=undef
readdir_r_proto=0
echo "Disabling readdir_r, cannot determine prototype." >&4 ;;
* ) case "$readdir_r_proto" in
REENTRANT_PROTO*) ;;
*) readdir_r_proto="REENTRANT_PROTO_${readdir_r_proto}" ;;
esac
echo "Prototype: $try" ;;
esac
;;
*) case "$usethreads" in
define) echo "readdir_r has no prototype, not using it." >&4 ;;
esac
d_readdir_r=undef
readdir_r_proto=0
;;
esac
;;
*) readdir_r_proto=0
;;
esac

```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/threads/d_readdir_r.U
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_memalign.U 1 2006-08-24 12:32:52Z rmanfredi \$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic Licence,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: \$Log: d_memalign.U,v \$
?RCS:
?MAKE:d_memalign: Inlibc
?MAKE: -pick add \$@ %<
?S:d_memalign:
?S: This variable conditionally defines the HAS_MEMALIGN symbol, which
?S: indicates to the C program that the memalign() routine is available.
?S:.
?C:HAS_MEMALIGN :
?C: This symbol, if defined, indicates that the memalign routine is
?C: available to allocate aligned memory.
?C:.
?H:#\$d_memalign HAS_MEMALIGN /**/
?H:.
?LINT:set d_memalign
: see if memalign exists
set
memalign d_memalign
eval \$inlibc

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/d_memalign.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_mkdir.U 1 2006-08-24 12:32:52Z rmanfredi \$
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: \$Log: d_mkdir.U,v \$
?RCS: Revision 3.0 1993/08/18 12:06:37 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:d_mkdir: Inlibc
?MAKE: -pick add \$@ %<
?S:d_mkdir:
?S: This variable conditionally defines the HAS_MKDIR symbol, which
?S: indicates to the C program that the mkdir() routine is available

?S: to create directories..

?S:.

?C:HAS_MKDIR (MKDIR):

?C: This symbol, if defined, indicates that the mkdir routine is available

?C: to create directories.

Otherwise you should fork off a new process to

?C: exec /bin/mkdir.

?C:.

?H:#\$d_mkdir HAS_MKDIR /**/

?H:.

?LINT:set d_mkdir

: see if mkdir exists

set mkdir d_mkdir

eval \$inlibc

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/d_mkdir.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_endnetent_r.U,v 0RCS:

?RCS: Copyright (c) 2002,2003 Jarkko Hietaniemi

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?RCS: Generated by the reentr.pl from the Perl 5.8 distribution.

?RCS:

?MAKE:d_endnetent_r endnetent_r_proto: Inlibc Protochk Hasproto i_systypes \
usethreads i_netdb extern_C

?MAKE: -pick add \$@ %<

?S:d_endnetent_r:

?S: This variable conditionally defines the HAS_ENDNETENT_R symbol,

?S: which indicates to the C program that the endnetent_r()

?S: routine is available.

?S:.

?S:endnetent_r_proto:

?S: This variable encodes the prototype of endnetent_r.

?S: It is zero if d_endnetent_r is undef, and one of the

?S: REENTRANT_PROTO_T_ABC macros of reentr.h if d_endnetent_r

?S: is defined.

?S:.

?C:HAS_ENDNETENT_R:

?C: This symbol, if defined, indicates that the endnetent_r routine

?C: is

available to endnetent re-entrantly.

?C:.

?C:ENDNETENT_R_PROTO:

```

?C: This symbol encodes the prototype of endnetent_r.
?C: It is zero if d_endnetent_r is undef, and one of the
?C: REENTRANT_PROTO_T_ABC macros of reentr.h if d_endnetent_r
?C: is defined.
?C:.
?H:#$d_endnetent_r HAS_ENDNETENT_R /**/
?H:#define ENDNETENT_R_PROTO $endnetent_r_proto /**/
?H:.
?T:try hdrs d_endnetent_r_proto
: see if endnetent_r exists
set endnetent_r d_endnetent_r
eval $inlibc
case "$d_endnetent_r" in
"$define")
hdrs="$i_systypes sys/types.h define stdio.h $i_netdb netdb.h"
case "$d_endnetent_r_proto:$usethreads" in
":define") d_endnetent_r_proto=define
set d_endnetent_r_proto endnetent_r $hdrs
eval $hasproto ;;
*) ;;
esac
case "$d_endnetent_r_proto" in
define)
case "$endnetent_r_proto" in
"|0) try='int endnetent_r(struct netent_data*);'
./protochk "$extern_C $try" $hdrs && endnetent_r_proto=I_D ;;
esac
case "$endnetent_r_proto" in
"|0) try='void endnetent_r(struct netent_data*);'
./protochk
"$extern_C $try" $hdrs && endnetent_r_proto=V_D ;;
esac
case "$endnetent_r_proto" in
"|0) d_endnetent_r=undef
endnetent_r_proto=0
echo "Disabling endnetent_r, cannot determine prototype." >&4 ;;
*) case "$endnetent_r_proto" in
REENTRANT_PROTO*) ;;
*) endnetent_r_proto="REENTRANT_PROTO_$endnetent_r_proto" ;;
esac
echo "Prototype: $try" ;;
esac
;;
*) case "$usethreads" in
define) echo "endnetent_r has no prototype, not using it." >&4 ;;
esac
d_endnetent_r=undef
endnetent_r_proto=0

```

```
;;
esac
;;
*) endnetent_r_proto=0
;;
esac
```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/threads/d_endnetent_r.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: d_strerror.U 1 2006-08-24 12:32:52Z rmanfredi $
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: $Log: d_strerror.U,v $
?RCS: Revision 3.0 1993/08/18 12:07:39 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:d_strerror: Inlibc
?MAKE: -pick add $@ %<
?S:d_strerror:
?S: This variable conditionally defines the HAS_STRTOL symbol, which
?S: indicates to the C program that the strtol() routine is available
?S: to provide better numeric string conversion than atoi() and friends.
?S:.
?C:HAS_STRTOL (STRTOL):
?C: This symbol, if defined, indicates that
?C: the strtol routine is available
?C: to provide better numeric string conversion than atoi() and friends.
?C:.
?H:#$d_strerror HAS_STRTOL /**/
?H:.
?LINT:set d_strerror
: see if strtol exists
set strtol d_strerror
eval $inlibc
```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/d_strerror.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: make.U 1 2006-08-24 12:32:52Z rmanfredi $
?RCS:
?RCS: Copyright (c) 1996, Andy Dougherty
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: $Log: make.U,v $
?RCS: Revision 3.0.1.1 1997/02/28 16:09:40 ram
?RCS: patch61: created
?RCS:
?MAKE:make_set_make : Loc rm sed make
?MAKE: -pick add $@ %<
?S:make_set_make:
?S: Some versions of 'make' set the variable MAKE. Others do not.
?S: This variable contains the string to be included in Makefile.SH
?S: so that MAKE is set if needed, and not if not needed.
?S: Possible values are:
?S:
?S: make_set_make='#' #
If your make program handles this for you,
?S:
?S: make_set_make="MAKE=$make" # if it doesn't.
?S:
?S: This uses a comment character so that we can distinguish a
?S: 'set' value (from a previous config.sh or Configure -D option)
?S: from an uncomputed value.
?S:.
?LINT: extern MAKE
?LINT: change MAKE
?X: This test is based on one from an autoconf-generated configure
?X: script. Autoconf stole a lot from Configure, but now it's our
?X: turn to do so... ;-) -- RAM, 21/02/97
: check whether make sets MAKE
echo " "
echo "Checking if your $make program sets \$(MAKE)..." >&4
case "$make_set_make" in
")
?X: Use sed so we don't have a line begining with @echo. Metaconfig
?X: will think that's a command like @if or @end.
$sed 's/^X //' > testmake.mak << 'EOF'
Xall:
```

```

X @echo 'maketemp="$(MAKE)'"
EOF
?X: GNU make sometimes prints "make[1]: Entering...", which would confuse us
case "$make -f testmake.mak 2>/dev/null`" in
*maketemp=*) make_set_make='#' ;;
*) make_set_make="MAKE=$make" ;;
esac
$rm
-f testmake.mak
;;
esac
case "$make_set_make" in
'#') echo "Yup, it does.";;
*) echo "Nope, it doesn't.";;
esac

```

Found in path(s):

```

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/make.U

```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1999, Jarkko Hietaniemi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 3.0.

?RCS:

?MAKE:d_sched_setscheduler: Inlibc

?MAKE: -pick add \$@ %<

?S:d_sched_setscheduler:

?S: This variable conditionally defines HAS_SCHED_SETSCHEDULER if

?S: sched_setscheduler() is available to set the scheduling policy.

?S:.

?C:HAS_SCHED_SETSCHEDULER:

?C: This symbol, if defined, indicates that the sched_setscheduler

?C: system call is available to set the scheduling policy.

?C:.

?H:#d_sched_setscheduler HAS_SCHED_SETSCHEDULER /**/

?H:.

?LINT:set d_sched_setscheduler

: see if sched_setscheduler exists

set sched_setscheduler

d_sched_setscheduler

eval \$inlibc

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_sched_setscheduler.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: i_time.U,v \$

?RCS: Revision 3.0 1993/08/18 12:08:45 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?X:

?X: This unit finds which "time" include to use. If 'timezone' is used by the

?X: program, we also try to find which header should be included. Eventually,

?X: we look for <sys/select.h> if I_SYSSSELECT is used, to get struct timeval.

?X:

?MAKE:i_time i_systime i_systimek timeincl: cat cc ccflags contains rm_try \
echo n c +i_sysselect Findhdr

?MAKE: -pick add \$@ %<

?S:i_time:

?S: This

variable conditionally defines I_TIME, which indicates

?S: to the C program that it should include <time.h>.

?S:.

?S:i_systime:

?S: This variable conditionally defines I_SYS_TIME, which indicates

?S: to the C program that it should include <sys/time.h>.

?S:.

?S:i_systimek:

?S: This variable conditionally defines I_SYS_TIME_KERNEL, which

?S: indicates to the C program that it should include <sys/time.h>

?S: with KERNEL defined.

?S:.

?S:timeincl:

?S: This variable holds the full path of the included time header(s).

?S:.

?C:I_TIME (USE_TIME_H):

?C: This symbol, if defined, indicates to the C program that it should

?C: include <time.h>.

```

?C:.
?C:I_SYS_TIME (I_SYSTIME USE_SYS_TIME_H NO_TIME_WITH_SYS_TIME):
?C: This symbol, if defined, indicates to the C program that it should
?C: include <sys/time.h>.
?C:.
?C:I_SYS_TIME_KERNEL (I_SYSTIMEKERNEL):
?C: This symbol, if defined, indicates to the C program that it should
?C: include <sys/time.h> with KERNEL defined.
?C:.
?H:#$i_time I_TIME /**/
?H:#$i_systime
I_SYS_TIME /**/
?H:#$i_systimek I_SYS_TIME_KERNEL /**/
?H:.
?W::timezone
?T:xselect flags sysselect s_timeval s_timezone
?LINT:change i_sysselect
: see if we should include time.h, sys/time.h, or both
echo " "
echo "Testing to see if we should include <time.h>, <sys/time.h> or both." >&4
$echo $n "I'm now running the test program...$c"
$cat >try.c <<'EOCP'
#include <sys/types.h>
#ifdef I_TIME
#include <time.h>
#endif
#ifdef I_SYSTIME
#ifdef SYSTIMEKERNEL
#define KERNEL
#endif
#include <sys/time.h>
#endif
#ifdef I_SYSSSELECT
#include <sys/select.h>
#endif
int main()
{
    struct tm foo;
#ifdef S_TIMEVAL
    struct timeval bar;
#endif
#ifdef S_TIMEZONE
    struct timezone tzp;
#endif
    if (foo.tm_sec == foo.tm_sec)
        exit(0);
#ifdef S_TIMEVAL
    if (bar.tv_sec == bar.tv_sec)

```

```

    exit(0);
#endif
    exit(1);
}
EOCP
flags=""
@if I_SYSSELECT
if $contains 'timeval.*{' `./findhdr sys/select.h` >/dev/null 2>&1; then
    xselect='-DI_SYSSELECT'
else
    xselect=""
fi
@end
@if timezone
for s_timezone
in '-DS_TIMEZONE' "; do
@else
s_timezone=""
@end
?X: Every package is given a try with 'struct timeval'
@if I_SYSSELECT
for sysselect in $xselect "; do
@else
sysselect=""
@end
for s_timeval in '-DS_TIMEVAL' "; do
for i_systimek in "-DSYSTIMEKERNEL"; do
for i_time in "-DI_TIME"; do
for i_systime in '-DI_SYSTIME' "; do
case "$flags" in
") $echo $n ".$.c"
if $cc $ccflags \
$i_time $i_systime $i_systimek $sysselect $s_timeval $s_timezone \
-o try try.c >/dev/null 2>&1 ; then
set X $i_time $i_systime $i_systimek $sysselect $s_timeval
shift
flags="$*"
echo " "
$echo $n "Succeeded with $flags$c"
fi
;;
esac
done
done
done
done
done
@if I_SYSSELECT
done

```

```

@end
@if timezone
done
@end
timeincl="
echo " "
case "$flags" in
*SYSTIMEKERNEL*) i_systimek="$define"
timeincl=`./findhdr sys/time.h`
echo "We'll include <sys/time.h> with KERNEL defined." >&4;;
*) i_systimek="$undef";;
esac
case "$flags" in
*I_TIME*) i_time="$define"
timeincl=`./findhdr time.h`" $timeincl"
echo
"We'll include <time.h>." >&4;;
*) i_time="$undef";;
esac
case "$flags" in
*I_SYSTIME*) i_systime="$define"
timeincl=`./findhdr sys/time.h`" $timeincl"
echo "We'll include <sys/time.h>." >&4;;
*) i_systime="$undef";;
esac
@if I_SYSSSELECT
case "$flags" in
*I_SYSSSELECT*) i_syssselct="$define"
timeincl=`./findhdr sys/select.h`" $timeincl"
echo "We'll also include <sys/select.h> to get struct timeval." >&4;;
*) case "$i_syssselct" in
") i_syssselct="$undef";;
esac
esac
@end
$rm_try

```

Found in path(s):

```

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/i_time.U

```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1999 Jarkko Hietaniemi

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

```

?RCS:
?MAKE:uselonglong: Myread Oldconfig Setvar cat test ccflags
?MAKE: -pick add $@ %<
?Y:TOP
?S:uselonglong:
?S: This variable conditionally defines the USE_LONG_LONG symbol,
?S: and indicates that long longs should be used when available.
?S:.
?C:USE_LONG_LONG:
?C: This symbol, if defined, indicates that long longs should
?C: be used when available.
?C:.
?H:?%<:#ifndef USE_LONG_LONG
?H:?%<:#$uselonglong USE_LONG_LONG /**/
?H:?%<:#endif
?H:.
?LINT:extern ccflags
?F:!uselonglong.cbu
: Check for longlong support
case "$uselonglong" in
|true|[yY]*) uselonglong="$define" ;;
*) case "$ccflags" in
*-DUSE_LONG_LONG*) uselonglong="$define" ;;
*) uselonglong="$undef" ;;
esac
;;
esac
case "$uselonglong"
in
$define) dflt='y';;
*) dflt='n';;
esac
cat <<EOM

```

Perl can be built to take advantage of long longs which (if available) may give more range for integer numbers.

If this doesn't make any sense to you, just accept the default '\$dflt'.

```

EOM
rp="Try to use long longs if available?"
. ./myread
case "$ans" in
y|Y) val="$define" ;;
*) val="$undef" ;;
esac
set uselonglong
eval $setvar
case "$uselonglong" in

```

```

$define)
: Look for a hint-file generated 'call-back-unit'. If the
: user has specified that long longs should be used,
: we may need to set or change some other defaults.
if $test -f uselonglong.cbu; then
  echo "Your platform has some specific hints for long longs, using them..."
  . ./uselonglong.cbu
else
  $cat <<EOM
(Your platform doesn't have any specific hints for long longs.)
EOM
fi
;;
esac

```

Found in path(s):

```

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/perl/uselonglong.U

```

No license file was found, but licenses were detected in source scan.

```

?RCS: $Id$
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: $Log: perlpath.U,v $
?RCS: Revision 3.0.1.2 1995/09/25 09:17:04 ram
?RCS: patch59: unit is now forced to the top of Configure, if possible
?RCS:
?RCS: Revision 3.0.1.1 1995/01/11 15:33:53 ram
?RCS: patch45: can now use Loc variables since path stripping is deferred
?RCS:
?RCS: Revision 3.0 1993/08/18 12:09:32 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?X:
?X: The purpose of this unit is to locate perl good enough to construct a #!
?X:
?MAKE:perlpath: Getfile Oldconfig Loc perl
?MAKE: -pick
add $@ %<
?Y:TOP
?S:perlpath:

```

?S: This variable contains the eventual value of the PERLPATH symbol,

?S: which contains the absolute location of the perl interpreter.

?S:.

?C:PERLPATH:

?C: This symbol contains the absolute location of the perl interpreter.

?C:.

?H:#define PERLPATH "\$perlpath" /**/

?H:.

: determine perl absolute location

case "\$perlpath" in

)

if test -f /usr/bin/perl; then

 dflt=/usr/bin/perl

else

 case "\$perl" in

 /) dflt="\$perl";;

 *) dflt=/usr/bin/perl;;

 esac

fi

::

*) dflt="\$perlpath"

::

esac

echo " "

fn=f~/

rp="Where is perl located on your system?"

./getfile

perlpath="\$ans"

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/perlpath.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: Prefixit.U 1 2006-08-24 12:32:52Z rmanfredi \$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic Licence,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic Licence; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: Prefixit.U,v \$

?RCS: Revision 3.0.1.1 1995/01/30 14:29:22 ram

?RCS: patch49: created

?RCS:

?X:

?X: Used as: "set dflt var dir; eval \$prefixit" to set \$dflt to be

?X: \$prefix/dir by default, or the previous \$var depending on certain

?X: conditions:

?X: - If the \$oldprefix variable is empty, then \$prefix holds the same

?X: value as on previous runs. Therefore, reuse \$var if set, otherwise

?X: set \$dflt to \$prefix/dir.

?X: - If \$oldprefix is not

empty, then set \$dflt to \$prefix/dir if \$var

?X: is empty (first run). Otherwise, if \$var is \$oldprefix/dir, then

?X: change it to \$prefix/dir. If none of the above, reuse the old \$var.

?X:

?X: When dir is omitted, the dflt variable is set to \$var if prefix did not

?X: change, to an empty value otherwise. If dir=none, then a single space

?X: in var is kept as-is, even if the prefix changes.

?X:

?MAKE:Prefixit: prefix oldprefix

?MAKE: -pick add \$@ %<

?LINT:define prefixit

?S:prefixit:

?S: This shell variable is used internally by Configure to reset

?S: the leading installation prefix correctly when it is changed.

?S: set dflt var [dir]

?S: eval \$prefixit

?S: That will set \$dflt to \$var or \$prefix/dir depending on the

?S: value of \$var and \$oldprefix.

?S:.

?V:prefixit

?T:tp

: set the prefixit variable, to compute a suitable default value

```
prefixit='case "$3" in
""|none)
case "$oldprefix" in
"" ) eval "$1=\"\$$2\"";;
*)
case "$3" in
"" ) eval "$1="";;
none)
eval "tp=\"\$$2\"";
case
"$tp" in
""|" ") eval "$1=\"\$$2\"";;
*) eval "$1="";;
esac;;
esac;;
esac;;
*)
eval "tp=\"\$oldprefix-\$$2-\""; eval "tp=\"\$tp\"";
```

```

case "$tp" in
--/*--|\~*--) eval "$1=\$prefix/$3\"";;
/*-$oldprefix/*|\~*-$oldprefix/*)
eval "$1=\`echo \$$2 | sed \`s,^$oldprefix,$prefix,\`\"";;
*) eval "$1=\`\"$2\"";;
esac;;
esac'

```

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/Prefixit.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: Myinit.U,v 3.0 1993/08/18 12:05:07 ram Exp \$

?RCS:

?RCS: Copyright (c) 1991-1993, Raphael Manfredi

?RCS:

?RCS: This file is included with or a derivative work of a file included

?RCS: with the metaconfig program of Raphael Manfredi's "dist" distribution.

?RCS: In accordance with clause 7 of dist's modified Artistic License:

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?RCS: \$Log: Myinit.U,v \$

?RCS: Revision 3.0 1993/08/18 12:05:07 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?X:

?X: If you want to initialize any default values, copy this unit to your

?X: personal U directory and add the assignments to the end. This file

?X: is included after variables are initialized but before any old

?X: config.sh file is read in and before any Configure switch processing.

?X:

?MAKE:Myinit

libswanted: Init

?MAKE: -pick add \$@ %<

?S:libswanted:

?S: This variable holds a list of all the libraries we want to

?S: search. The order is chosen to pick up the c library

?S: ahead of ucb or bsd libraries for SVR4.

?S:.

?LINT:extern usevfork glibpth

?LINT:change usevfork glibpth

: List of libraries we want.

?X: Put crypt here, even though I should really fix d_crypt.U to look

?X: for it correctly, including possible shared library versions.

: If anyone needs extra -lxxx, put those in a hint file.

```
libswanted="cl pthread socket bind inet nsl ndbm gdbm dbm db malloc dl ld"
libswanted="$libswanted sun m crypt sec util c cposix posix ucb bsd BSD"
: We probably want to search /usr/shlib before most other libraries.
: This is only used by the lib/ExtUtils/MakeMaker.pm routine extliblist.
glibpth=`echo " $glibpth " | sed -e 's! /usr/shlib ! !'^
glibpth="/usr/shlib $glibpth"
: Do not use vfork unless overridden by a hint file.
usevfork=false
```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/modified/Myinit.U
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: sitebin.U,v \$

?RCS:

?RCS: Copyright (c) 1999 Andy Dougherty

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 3.0.

?RCS:

?RCS: \$Log: sitebin.U,v \$

?RCS:

?MAKE:sitebin sitebinexp installsitebin : Getfile Oldconfig \

Setprefixvar siteprefix

?MAKE: -pick add \$@ %<

?Y:TOP

?D:sitebin="

?S:sitebin:

?S: This variable holds the name of the directory in which the user wants

?S: to put add-on publicly executable files for the package in question. It

?S: is most often a local directory such as /usr/local/bin. Programs using

?S: this variable must be prepared to deal with ~name substitution.

?S: The standard distribution will put nothing

in this directory.

?S: After perl has been installed, users may install their own local

?S: executables in this directory with

?S: MakeMaker Makefile.PL

?S: or equivalent. See INSTALL for details.

?S:.

?D:sitebinexp="

?S:sitebinexp:

?S: This is the same as the sitebin variable, but is filename expanded at

?S: configuration time, for use in your makefiles.

?S:.

```

?D:installsitebin="
?S:installsitebin:
?S: This variable is usually the same as sitebinexp, unless you are on
?S: a system running AFS, in which case they may differ slightly. You
?S: should always use this variable within your makefiles for portability.
?S:.
?LINT:change prefixvar
?LINT:set installsitebin
?LINT:set sitebin
?LINT:set sitebinexp
: determine where add-on public executables go
case "$sitebin" in
") dflt=$siteprefix/bin ;;
*) dflt=$sitebin ;;
esac
fn=d~
rp='Pathname where the add-on public executables should be installed?'
./getfile
prefixvar=sitebin
./setprefixvar

```

Found in path(s):

```

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/installdirs/sitebin.U

```

No license file was found, but licenses were detected in source scan.

```

?RCS: $Id: d_getpwent.U,v $
?RCS:
?RCS: Copyright (c) 1998 Andy Dougherty
?RCS:
?RCS: You may distribute under the terms of either the GNU General Public
?RCS: License or the Artistic License, as specified in the README file.
?RCS:
?RCS: $Log: d_getpwent.U,v $
?RCS:
?MAKE:d_getpwent: Inlibc
?MAKE: -pick add $@ %<
?S:d_getpwent:
?S: This variable conditionally defines the HAS_GETPWENT symbol, which
?S: indicates to the C program that the getpwent() routine is available
?S: for sequential access of the passwd database.
?S:.
?C:HAS_GETPWENT:
?C: This symbol, if defined, indicates that the getpwent routine is
?C: available for sequential access of the passwd database.
?C: If this is not available, the older getpw() function may be available.
?C:.
?H:#$d_getpwent HAS_GETPWENT /**/

```

```
?H:
?LINT:set d_getpwent
: see if getpwent exists
set getpwent d_getpwent
eval $inlibc
```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/modified/d_getpwent.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id$
```

```
?RCS:
```

```
?RCS: Copyright (c) 1999 Jarkko Hietaniemi
```

```
?RCS:
```

```
?RCS: You may distribute under the terms of either the GNU General Public
```

```
?RCS: License or the Artistic License, as specified in the README file.
```

```
?RCS:
```

```
?MAKE:usemorebits: Setvar
```

```
?MAKE: -pick add $@ %<
```

```
?Y:TOP
```

```
?S:usemorebits:
```

```
?S: This variable conditionally defines the USE_MORE_BITS symbol,
```

```
?S: and indicates that explicit 64-bit interfaces and long doubles
```

```
?S: should be used when available.
```

```
?S:.
```

```
?C:USE_MORE_BITS:
```

```
?C: This symbol, if defined, indicates that 64-bit interfaces and
```

```
?C: long doubles should be used when available.
```

```
?C:.
```

```
?H:?%<:#ifndef USE_MORE_BITS
```

```
?H:?%<:#$usemorebits USE_MORE_BITS /**/
```

```
?H:?%<:#endif
```

```
?H:.
```

```
?LINT:extern use64bitint
```

```
?LINT:change use64bitint
```

```
?LINT:extern uselongdouble
```

```
?LINT:change uselongdouble
```

```
: Check if morebits is requested
```

```
case "$usemorebits" in
```

```
"$define"|true|[yY]*)
```

```
use64bitint="$define"
```

```
uselongdouble="$define"
```

```
usemorebits="$define"
```

```
::
```

```
*) usemorebits="$undef"
```

```
::
```

```
esac
```

Found

in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/usemorebits.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: i_dirent.U,v 3.0.1.4 1994/10/29 16:20:01 ram Exp \$

?RCS:

?RCS: Copyright (c) 1991-1993, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 3.0.

?RCS:

?RCS: \$Log: i_dirent.U,v \$

?RCS: Revision 3.0.1.4 1994/10/29 16:20:01 ram

?RCS: patch36: failed scanning for 'd_namlen' with missing <dirent.h> (ADO)

?RCS:

?RCS: Revision 3.0.1.3 1994/06/20 07:01:25 ram

?RCS: patch30: added direntrytype for hints, merely for NeXT (ADO)

?RCS: patch30: now checks for both struct dirent and direct (ADO)

?RCS:

?RCS: Revision 3.0.1.2 1994/05/13 15:22:37 ram

?RCS: patch27: new variable direntrytype for proper type setting (ADO)

?RCS:

?RCS:

Revision 3.0.1.1 1994/01/24 14:11:15 ram

?RCS: patch16: added new Direntry_t pseudo-type for directory entries

?RCS:

?RCS: Revision 3.0 1993/08/18 12:08:17 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?X:

?X: This unit looks whether there is a dirent system or not

?X:

?MAKE:i_dirent d_dirnamlen direntrytype: test contains Setvar \

Myread Findhdr cppstdin cppflags cppminus rm_try

?MAKE: -pick add \$@ %<

?S:i_dirent:

?S: This variable conditionally defines I_DIRENT, which indicates

?S: to the C program that it should include <dirent.h>.

?S:.

?S:d_dirnamlen:

?S: This variable conditionally defines DIRNAMLEN, which indicates

?S: to the C program that the length of directory entry names is

?S: provided by a d_namelen field.

?S:.

?S:direntrytype:

?S: This symbol is set to 'struct direct' or 'struct dirent' depending on
 ?S: whether dirent is available or not. You should use this pseudo type to
 ?S: portably declare your directory entries.

?S:.

?C:I_DIRENT:

?C: This symbol,
 if defined, indicates to the C program that it should
 ?C: include <dirent.h>. Using this symbol also triggers the definition
 ?C: of the Direntry_t define which ends up being 'struct dirent' or
 ?C: 'struct direct' depending on the availability of <dirent.h>.

?C:.

?C:DIRNAMLEN:

?C: This symbol, if defined, indicates to the C program that the length
 ?C: of directory entry names is provided by a d_namlen field. Otherwise
 ?C: you need to do strlen() on the d_name field.

?C:.

?C:Direntry_t:

?C: This symbol is set to 'struct direct' or 'struct dirent' depending on
 ?C: whether dirent is available or not. You should use this pseudo type to
 ?C: portably declare your directory entries.

?C:.

?H:#\$i_dirent I_DIRENT /**/
 ?H:#\$d_dirnamlen DIRNAMLEN /**/
 ?H:%<:@if I_DIRENT && Direntry_t
 ?H:%<:#define Direntry_t \$direntrytype
 ?H:%<:@end

?H:.

?T:xinc guess1 guess2

?LINT:set i_dirent d_dirnamlen
 : see if this is a dirent system
 echo " "
 if xinc=`./findhdr dirent.h`; \$test "\$xinc"; then
 val="\$define"
 echo
 "<dirent.h> found." >&4
 else
 val="\$undef"
 if xinc=`./findhdr sys/dir.h`; \$test "\$xinc"; then
 echo "<sys/dir.h> found." >&4
 echo " "
 else
 xinc=`./findhdr sys/ndir.h`
 fi
 echo "<dirent.h> NOT found." >&4
 fi

```
set i_dirent
eval $setvar
```

?X: Use struct dirent or struct direct? If we're using dirent.h,

?X: it's probably struct dirent, but apparently not always.

?X: Assume \$xinc still contains the name of the header file we're using.

```
@if direntrytype || Direntry_t
```

```
: Look for type of directory structure.
```

```
echo " "
```

```
$cppstdin $cppflags $cppminus < "$xinc" > try.c
```

```
case "$direntrytype" in
```

```
"| ')
```

```
case "$i_dirent" in
```

```
$define) guess1='struct dirent' ;;
```

```
*) guess1='struct direct' ;;
```

```
esac
```

```
::
```

```
*) guess1="$direntrytype"
```

```
::
```

```
esac
```

```
case "$guess1" in
```

```
'struct dirent') guess2='struct direct' ;;
```

```
*) guess2='struct dirent' ;;
```

```
esac
```

```
if $contains "$guess1" try.c >/dev/null 2>&1; then
```

```
direntrytype="$guess1"
```

```
echo "Your directory entries are $direntrytype." >&4
```

```
elif $contains "$guess2"
```

```
try.c >/dev/null 2>&1; then
```

```
direntrytype="$guess2"
```

```
echo "Your directory entries seem to be $direntrytype." >&4
```

```
else
```

```
echo "I don't recognize your system's directory entries." >&4
```

```
rp="What type is used for directory entries on this system?"
```

```
dflt="$guess1"
```

```
. ./myread
```

```
direntrytype="$ans"
```

```
fi
```

```
$rm_try
```

```
@end
```

```
@if d_dirnamlen || DIRNAMLEN
```

```
: see if the directory entry stores field length
```

```
echo " "
```

```
$cppstdin $cppflags $cppminus < "$xinc" > try.c
```

```

if $contains 'd_namlen' try.c >/dev/null 2>&1; then
  echo "Good, your directory entry keeps length information in d_namlen." >&4
  val="$define"
else
  echo "Your directory entry does not know about the d_namlen field." >&4
  val="$undef"
fi
set d_dirnamlen
eval $setvar
$rm_try

@end

```

Found in path(s):

```

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/modified/i_dirent.U

```

No license file was found, but licenses were detected in source scan.

```

?RCS: $Id: d_wait3.U 1 2006-08-24 12:32:52Z rmanfredi $
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: $Log: d_wait3.U,v $
?RCS: Revision 3.0 1993/08/18 12:08:01 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:d_wait3: Inlibc
?MAKE: -pick add $@ %<
?S:d_wait3:
?S: This variable conditionally defines the HAS_WAIT3 symbol, which
?S: indicates to the C program that the wait3() subroutine exists.
?S:.
?C:HAS_WAIT3:
?C: This symbol, if defined, indicates that the wait3() subroutine
?C: exists.
?C:.
?H:#$d_wait3 HAS_WAIT3 /**/
?H:.
?LINT:set d_wait3
:
  see if 'wait3()' exists
set wait3 d_wait3

```

eval \$inlibc

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/d_wait3.U

No license file was found, but licenses were detected in source scan.

?RCS: Copyright (c) 2016 Dagfinn Ilmari Mannsker & H.Merijn Brand

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?X:

?X: This unit produces a variable that is intended to be eval'ed in

?X: order to define/undefine a symbol. A consistency check is made

?X: regarding any previous value and a warning is issued if there

?X: is any discrepancy.

?X:

?X: To use it, say:

?X: set d_siginfo_si_errno siginfo_t int si_errno \$d_sigaction signal.h

?X: eval \$hasfield_t;

?X:

?MAKE:Hasfield_t: test Compile rm_try Setvar

?MAKE: -pick add \$@ %<

?LINT:define hasfield_t

?S:hasfield_t:

?S: Internal macro for Configure

?S:.

?V:hasfield_t:

?T:varname struct type field

: Define hasfield_t macro for Configure internal use

hasfield_t='varname=\$1; struct=\$2; type=\$3; field=\$4; shift; shift; shift; shift;

while \$test \$# -ge 2; do

case

"\$1" in

\$define) echo "#include <\$2>";;

esac ;

shift 2;

done > try.c;

echo "int main () { \$struct foo; \$type bar = foo.\$field; }" >> try.c;

set try;

if eval \$compile; then

val="\$define";

else

val="\$undef";

fi;

set \$varname;

eval \$setvar;

\$rm_try'

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/Hasfield_t.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: mailfile.U 1 2006-08-24 12:32:52Z rmanfredi \$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic Licence,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic Licence; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: mailfile.U,v \$

?RCS: Revision 3.0.1.2 1994/10/29 16:24:57 ram

?RCS: patch36: the Loc unit was missing from the dependency line

?RCS:

?RCS: Revision 3.0.1.1 1993/12/15 08:22:08 ram

?RCS: patch15: now also looks under /var/mail for BSD/386

?RCS:

?RCS: Revision 3.0 1993/08/18 12:09:11 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?MAKE:mailfile: Myread Oldconfig Filexp Loc

?MAKE: -pick add \$@ %<

?S:mailfile:

?S: This variable contains

the eventual value of the MAILFILE symbol,

?S: which contains an interpretable name of the mail spool file for the

?S: current user.

?S:.

?C:MAILFILE:

?C: This symbol contains the interpretable name of the mail spool file

?C: for the current user. The program must be prepared to substitute

?C: the HOME directory for %~, and the login id for %L.

?C:.

?H:#define MAILFILE "\$mailfile" /**/

?H:.

: determine where mail is spooled

case "\$mailfile" in

")

dflt=`./loc . XXX /usr/spool/mail /usr/mail /var/mail`

case "\$dflt" in

XXX) dflt='%~/mailbox';;

```
*) dflt="$dflt/%L";;
esac
;;
*) dflt="$mailfile"
;;
esac
cat <<'EOM'
```

In the following question, you may use %~ to represent the user's home directory, and %L to represent a users name.

EOM

```
rp='In which file is yet-to-be-read mail spooled? (~name ok)'
. ./myread
mailfile=`./filexp "$ans"`
```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/mailfile.U
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: d_flexfnam.U,v \$

?RCS: Revision 3.0 1993/08/18 12:06:04 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?MAKE:d_flexfnam: cat rm test Setvar

?MAKE: -pick add \$@ %<

?S:d_flexfnam:

?S: This variable conditionally defines the FLEXFILENAMES symbol, which

?S: indicates that the system supports filenames longer than 14 characters.

?S:.

?C:FLEXFILENAMES:

?C: This symbol, if defined, indicates that the system supports filenames

?C: longer than 14 characters.

?C:.

?H:#\$d_flexfnam FLEXFILENAMES /**/

?H:.

?T:first

```

second
?LINT:set d_flexfnam
: see if we can have long filenames
echo " "
?X:
?X: We have to test in both /tmp and . because of NFS (remote server may allow
?X: long filenames while the local filesystem cannot support them). If at least
?X: one of those file systems cannot support long filenames, then we assume the
?X: whole system can't.
?X:
rmlist="$rmlist /tmp/cf$$"
$test -d /tmp/cf$$ || mkdir /tmp/cf$$
first=123456789abcdef
second=/tmp/cf$$/$first
$rm -f $first $second
if (echo hi >$first) 2>/dev/null; then
if $test -f 123456789abcde; then
echo 'You cannot have filenames longer than 14 characters. Sigh.' >&4
val="$undef"
else
if (echo hi >$second) 2>/dev/null; then
if $test -f /tmp/cf$$/123456789abcde; then
$cat <<'EOM'

```

That's peculiar... You can have filenames longer than 14 characters, but only on some of the filesystems. Maybe you are using NFS. Anyway, to avoid problems I shall consider your system cannot support long filenames at all.

```

EOM
val="$undef"
else
echo
'You can have filenames longer than 14 characters.' >&4
val="$define"
fi
else
$cat <<'EOM'

```

How confusing! Some of your filesystems are sane enough to allow filenames longer than 14 characters but some others like /tmp can't even think about them. So, for now on, I shall assume your kernel does not allow them at all.

```

EOM
val="$undef"
fi
fi
else
$cat <<'EOM'
You can't have filenames longer than 14 chars. You can't even think about them!
EOM
val="$undef"
fi

```

```
set d_flexnam
eval $setvar
$rm -rf /tmp/cf$$ 123456789abcde*
```

Found in path(s):

```
*/opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/d_flexnam.U
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: ccflags.U,v \$

?RCS: Revision 3.0.1.9 1997/02/28 15:27:07 ram

?RCS: patch61: removed support for NO_PROTOTYPE detection on SCO

?RCS: patch61: new locincpth variable

?RCS: patch61: added info on the "additional ld flags" question

?RCS:

?RCS: Revision 3.0.1.8 1995/07/25 13:48:54 ram

?RCS: patch56: re-arranged compile line to include ldflags before objects

?RCS:

?RCS: Revision 3.0.1.7 1995/05/12 12:08:33 ram

?RCS: patch54: now checks for cc/ccflags/ldflags coherency

?RCS:

?RCS: Revision 3.0.1.6

1994/10/29 16:07:02 ram

?RCS: patch36: gcc versioning no longer relies on the C compiler's name

?RCS: patch36: simplified check for gcc version checking (ADO)

?RCS:

?RCS: Revision 3.0.1.5 1994/08/29 16:06:35 ram

?RCS: patch32: propagate -posix flag from ccflags to ldflags

?RCS:

?RCS: Revision 3.0.1.4 1994/05/06 14:28:45 ram

?RCS: patch23: -fpcc-struct-return only needed in gcc 1.x (ADO)

?RCS: patch23: cppflags now computed on an option-by-option basis

?RCS: patch23: magically added cc flags now only done the first time

?RCS:

?RCS: Revision 3.0.1.3 1993/09/13 15:58:29 ram

?RCS: patch10: explicitly mention -DDEBUG just in case they need it (WAD)

?RCS: patch10: removed all the "tans" variable usage (WAD)

?RCS:

?RCS: Revision 3.0.1.2 1993/08/27 14:39:38 ram
?RCS: patch7: added support for OSF/1 machines
?RCS:
?RCS: Revision 3.0.1.1 1993/08/25 14:00:24 ram
?RCS: patch6: added defaults for cppflags, ccflags and ldflags
?RCS:
?RCS: Revision 3.0 1993/08/18 12:05:31 ram
?RCS:
Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:ccflags ldflags lkflags cppflags optimize locincpth: test cat \
Myread Guess Options Oldconfig gccversion mips_type +usrinc \
package contains rm rm_try +cc cppstdin cppminus cprun cpplast libpth \
loclibpth hint
?MAKE: -pick add \$@ %<
?S:ccflags:
?S: This variable contains any additional C compiler flags desired by
?S: the user. It is up to the Makefile to use this.
?S:.
?S:cppflags:
?S: This variable holds the flags that will be passed to the C pre-
?S: processor. It is up to the Makefile to use it.
?S:.
?S:optimize:
?S: This variable contains any optimizer/debugger flag that should be used.
?S: It is up to the Makefile to use it.
?S:.
?S:ldflags:
?S: This variable contains any additional C loader flags desired by
?S: the user. It is up to the Makefile to use this.
?S:.
?S:lkflags:
?S: This variable contains any additional C partial linker flags desired by
?S: the user. It is up to the Makefile to use this.
?S:.
?S:locincpth:
?S: This
variable contains a list of additional directories to be
?S: searched by the compiler. The appropriate -I directives will
?S: be added to ccflags. This is intended to simplify setting
?S: local directories from the Configure command line.
?S: It's not much, but it parallels the loclibpth stuff in libpth.U.
?S:.
?T:inctest thisincl xxx flag inclwanted ftry previous thislibdir
?F:!cpp.c
?D:cppflags="
?D:ccflags="
?D:ldflags="

```

?D:optimize="
?INIT:: Possible local include directories to search.
?INIT:: Set locincpth to "" in a hint file to defeat local include searches.
?INIT:locincpth="/usr/local/include /opt/local/include /usr/gnu/include"
?INIT:locincpth="$locincpth /opt/gnu/include /usr/GNU/include /opt/GNU/include"
?INIT::
?INIT:: no include file wanted by default
?INIT:inclwanted="
?INIT:
: determine optimize, if desired, or use for debug flag also
case "$optimize" in
'|$undef) dflt='none';;
")
case "$gccversion" in
") dflt='-O';;
*) dflt='-O2 -g';;
esac
;;
*)
dflt="$optimize";;
esac
case "$gccversion" in
") $cat <<EOH

```

Some C compilers have problems with their optimizers. By default, \$package compiles with the -O flag to use the optimizer. Alternately, you might want to use the symbolic debugger, which uses the -g flag (on traditional Unix systems). Either flag can be specified here. To use neither flag, specify the word "none".

```

EOH
;;
*) $cat <<EOH

```

With the GNU C compiler, it is possible to supply both -O2 and -g flags, to be able to reasonably optimize, whilst retaining the ability to use a symbolic debugger. Either flag can be specified here. To use neither flag, specify the word "none".

```

EOH
;;
esac
rp="What optimizer/debugger flag should be used?"
./myread
optimize="$ans"
case "$optimize" in
'none') optimize=" ";;
esac

```

```

dflt="
: We will not override a previous value, but we might want to
: augment a hint file
case "$hint" in
default|recommended)
case "$gccversion" in
1*) dflt='-fpcc-struct-return' ;;
esac
?X:
check for POSIXized ISC
case "$gccversion" in
2*) if test -d /etc/conf/kconfig.d &&
  $contains _POSIX_VERSION $usrinc/sys/unistd.h >/dev/null 2>&1
then
  dflt="$dflt -posix"
fi
;;
esac
?X: turn warnings on if they're using gcc
case "$gccversion" in
1*|2*) dflt="$dflt -Wall";;
?X: starting with version 3, add "-W -Wall -Wformat=2 -Wshadow" by default
*) dflt="$dflt -W -Wall -Wformat=2 -Wshadow";;
esac
;;
esac

```

?X: In USG mode, a MIPS system may need some BSD includes

```

case "$mips_type" in
*BSD*|*) inclwanted="$locincpth $usrinc";;
*) inclwanted="$locincpth $inclwanted $usrinc/bsd";;
esac
for thisincl in $inclwanted; do
if $test -d $thisincl; then
if $test x$thisincl != x$usrinc; then
case "$dflt" in
*$thisincl*);;
*) dflt="$dflt -I$thisincl";;
esac
fi
fi
done

```

?X: Include test function (header, symbol)

```

inctest='if $contains $2 $usrinc/$1 >/dev/null 2>&1; then
xxx=true;
elif $contains $2 $usrinc/sys/$1 >/dev/null 2>&1; then

```

```

xxx=true;
else
xxx=false;
fi;
if
$xxx; then
case "$dflt" in
*$2*);;
*) dflt="$dflt -D$2";;
esac;
fi'

?X:
?X: OSF/1 uses __LANGUAGE_C__ instead of LANGUAGE_C
?X:
if ./osf1; then
set signal.h __LANGUAGE_C__; eval $inctest
else
set signal.h LANGUAGE_C; eval $inctest
fi

case "$hint" in
default|recommended) dflt="$ccflags $dflt" ;;
*) dflt="$ccflags";;
esac

case "$dflt" in
'| ') dflt=none;;
esac
$cat <<EOH

```

Your C compiler may want other flags. For this question you should include -I/whatever and -DWHATEVER flags and any other flags used by the C compiler, but you should NOT include libraries or ld flags like -lwhatever.

To use no flags, specify the word "none".

```

EOH
?X: strip leading space
set X $dflt
shift
dflt=${1+"$@"}
rp="Any additional cc flags?"
./myread
case "$ans" in
none) ccflags="";;
*) ccflags="$ans";;
esac

```

: the following weeds options from ccflags that are of no interest to cpp

```
cppflags="$ccflags"
case "$gccversion" in
1*) cppflags="$cppflags -D__GNUC__"
esac
case "$mips_type" in
");;
*BSD*)
cppflags="$cppflags -DSYSTYPE_BSD43";;
esac
case "$scppflags" in
");;
*)
echo " "
echo "Let me guess what the preprocessor flags are..." >&4
set X $scppflags
shift
cppflags="
$cat >cpp.c <<'EOM'
#define BLURFL foo
```

```
BLURFL xx LFRULB
```

```
EOM
```

```
?X:
```

?X: For each cc flag, try it out with both cppstdin and cprun, since the

?X: first is almost surely a cc wrapper. We have to try both in case

?X: of cc flags like '-Olimit 2900' that are actually two words...

```
?X:
```

```
previous="
for flag in $*
do
case "$flag" in
-*) ftry="$flag";;
*) ftry="$previous $flag";;
esac
if $cppstdin -DLFRULB=bar $ftry $cppminus <cpp.c \
>cpp1.out 2>/dev/null && \
$cprun -DLFRULB=bar $ftry $cpplast <cpp.c \
>cpp2.out 2>/dev/null && \
$contains 'foo.*xx.*bar' cpp1.out >/dev/null 2>&1 && \
$contains 'foo.*xx.*bar' cpp2.out >/dev/null 2>&1
then
cppflags="$cppflags $ftry"
previous="
else
previous="$flag"
fi
```

```

done
set X $cppflags
shift
cppflags=${1+"$@"}
case "$cppflags"
in
*-* ) echo "They appear to be: $cppflags";;
esac
$rm -f cpp.c cpp?.out
;;
esac

```

: flags used in final linking phase

```

case "$ldflags" in
*) if ./venix; then
    dflt='-i -z'
  else
    dflt=""
  fi
case "$ccflags" in
*-posix*) dflt="$dflt -posix" ;;
esac
;;
*) dflt="$ldflags";;
esac

```

: Try to guess additional flags to pick up local libraries.

```

for thislibdir in $libpth; do
case " $loclibpth " in
*" $thislibdir "*)
case "$dflt " in
*" -L$thislibdir "*) ;;
*) dflt="$dflt -L$thislibdir" ;;
esac
;;
esac
done

```

```

case "$dflt" in
") dflt='none' ;;
*) set X $dflt; shift; dflt="$@" ;;
esac

```

```
$cat <<EOH
```

Your C linker may need flags. For this question you should include -L/whatever and any other flags used by the C linker, but you should NOT include libraries like -lwhatever.

Make sure you include the appropriate -L/path flags if your C linker does not normally search all of the directories you specified above, namely

\$libpth

To use no flags, specify the word "none".

EOH

```
rp="Any
additional ld flags (NOT including libraries)?"
```

```
./myread
```

```
case "$ans" in
```

```
none) ldflags=";;
```

```
*) ldflags="$ans";;
```

```
esac
```

```
rmlist="$rmlist pdp11"
```

```
@if lkflags
```

```
: partial linking may need other flags
```

```
case "$lkflags" in
```

```
") case "$ldflags" in
```

```
"") dflt='none';;
```

```
*) dflt="$ldflags";;
```

```
esac;;
```

```
*) dflt="$lkflags";;
```

```
esac
```

```
echo " "
```

```
rp="Partial linking flags to be used (NOT including -r)?"
```

```
./myread
```

```
case "$ans" in
```

```
none) lkflags=";;
```

```
*) lkflags="$ans";;
```

```
esac
```

```
@end
```

```
?X:
```

```
?X: If the user changes compilers after selecting a hint file, it's
```

```
?X: possible that the suggested ccflags/ldflags will be wrong. Try to
```

```
?X: compile and run a simple test program. Let the user see all the
```

```
?X: error messages. -- ADO and RAM
```

```
?X:
```

```
: coherency check
```

```
echo " "
```

```
echo "Checking your choice of C compiler and flags for coherency..." >&4
```

```
?X: Strip extra blanks in case some of the following variables are empty
```

```
set X $cc $optimize $ccflags $ldflags -o try try.c
```

```
shift
```

```
$cat >try.msg <<EOM
```

I've tried to compile and run a simple program
with:

```
$*  
./try
```

and I got the following output:

```
EOM
```

```
$cat > try.c <<'EOF'
```

```
#include <stdio.h>
```

```
int main() { exit(0); }
```

```
EOF
```

```
dflt=y
```

```
?X: Use "sh -c" to avoid error messages tagged with leading "Configure:".
```

```
?X: We need to try the resulting executable, because cc might yield a 0 status
```

```
?X: even when ld failed, in which case the executable will not run properly,
```

```
?X: if its x bit is set at all...
```

```
if sh -c "$cc $optimize $ccflags $ldflags -o try try.c" >>try.msg 2>&1; then
```

```
if sh -c './try' >>try.msg 2>&1; then
```

```
  dflt=n
```

```
else
```

```
  echo "The program compiled OK, but exited with status $?." >>try.msg
```

```
  rp="You have a problem. Shall I abort Configure"
```

```
  dflt=y
```

```
fi
```

```
else
```

```
  echo "I can't compile the test program." >>try.msg
```

```
  rp="You have a BIG problem. Shall I abort Configure"
```

```
  dflt=y
```

```
fi
```

```
case "$dflt" in
```

```
y)
```

```
  $cat try.msg >&4
```

```
?X: using -K will prevent default aborting--maybe they're cross compiling?
```

```
case "$knowitall" in
```

```
")
```

```
  echo "(The supplied flags might be incorrect with this C compiler.)"
```

```
  ;;
```

```
*)
```

```
  dflt=n;;
```

```
esac
```

```
echo " "
```

```
./myread
```

```
case "$ans" in
```

```
n*|N*) ;;
```

```
*) echo "Ok. Stopping Configure." >&4
```

```
exit 1
;;
esac
;;
n) echo "OK, that should do.";;
esac
$rm_try
```

Found in path(s):

```
*/opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/ccflags.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: nis.U,v 3.0.1.3 1997/02/28 16:17:38 ram Exp $
?RCS:
?RCS: Copyright (c) 1991-1993, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 3.0.
?RCS:
?RCS: $Log: nis.U,v $
?RCS: Revision 3.0.1.3 1997/02/28 16:17:38 ram
?RCS: patch61: ensure suitable defaults for hostcat and friends
?RCS:
?RCS: Revision 3.0.1.2 1995/03/21 08:48:34 ram
?RCS: patch52: continued fix for NeXT NIS/NetInfo handling
?RCS:
?RCS: Revision 3.0.1.1 1995/02/15 14:16:23 ram
?RCS: patch51: now correctly handles NeXT using NIS rather than NetInfo
?RCS:
?RCS: Revision 3.0 1993/08/18 12:09:24 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:passcat
groupcat hostcat: Myread Oldconfig test contains
?MAKE: -pick add $@ %<
?S:passcat:
?S: This variable contains a command that produces the text of the
?S: /etc/passwd file. This is normally "cat /etc/passwd", but can be
?S: "ypcat passwd" when NIS is used.
?S: On some systems, such as os390, there may be no equivalent
?S: command, in which case this variable is unset.
?S:.
?S:groupcat:
?S: This variable contains a command that produces the text of the
```

?S: /etc/group file. This is normally "cat /etc/group", but can be
 ?S: "ypcat group" when NIS is used.
 ?S: On some systems, such as os390, there may be no equivalent
 ?S: command, in which case this variable is unset.
 ?S:.
 ?S:hostcat:
 ?S: This variable contains a command that produces the text of the
 ?S: /etc/hosts file. This is normally "cat /etc/hosts", but can be
 ?S: "ypcat hosts" when NIS is used.
 ?S: On some systems, such as os390, there may be no equivalent
 ?S: command, in which case this variable is unset.
 ?S:.
 :
 see if we have to deal with yellow pages, now NIS.
 ?X: NeXT gives us some fun here, as always, by having both NIS (former YP)
 ?X: and NetInfo. But since it has both, it's ok to put the test inside the if.
 ?X: Contributed by Thomas Neumann <tom@smart.bo.open.de>.
 if \$test -d /usr/etc/yp || \$test -d /etc/yp || \$test -d /usr/lib/yp; then
 @if passcat || groupcat
 case "\$passcat" in
 nidump*) ;;
 *)
 case "\$passcat" in
 ypcat) dflt=y;;
 *) if \$contains '\+' /etc/passwd >/dev/null 2>&1; then
 dflt=y
 else
 dflt=n
 fi;;
 *) dflt=n;;
 esac
 echo " "
 rp='Are you getting the passwd file via yellow pages?'
 . ./myread
 case "\$ans" in
 y*) passcat='ypcat passwd'
 @if groupcat
 echo "(Assuming /etc/group is also distributed.)"
 groupcat='ypcat group'
 @end
 ;;
 *) passcat='cat /etc/passwd'
 @if groupcat
 echo "(Assuming /etc/group is also local.)"
 groupcat='cat /etc/group'
 @end
 ;;
 esac

```

;;
esac
@end
@if hostcat
case "$hostcat" in
nidump*) ;;
*)
case
"$hostcat" in
*yocat*) dflt=y;;
") if $contains '\+' /etc/passwd >/dev/null 2>&1; then
dflt=y
else
dflt=n
fi;;
*) dflt=n;;
esac
echo " "
rp='Are you getting the hosts file via yellow pages?'
./myread
case "$ans" in
y*) hostcat='yocat hosts';;
*) hostcat='cat /etc/hosts';;
esac
;;
esac
@end
fi
?X: Ensure suitable default -- Manoj Srivastava
case "$hostcat" in
") test -f /etc/hosts && hostcat='cat /etc/hosts';;
esac
case "$groupcat" in
") test -f /etc/group && groupcat='cat /etc/group';;
esac
case "$passcat" in
") test -f /etc/passwd && passcat='cat /etc/passwd';;
esac

```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/modified/nis.U
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_bcopy.U 1 2006-08-24 12:32:52Z rmanfredi \$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: \$Log: d_bcopy.U,v \$
?RCS: Revision 3.0.1.2 1993/10/16 13:48:04 ram
?RCS: patch12: added magic support for bcopy()
?RCS:
?RCS: Revision 3.0.1.1 1993/09/13 16:01:11 ram
?RCS: patch10: now only defines HAS_BCOPY, no macro remap on memcpy (WAD)
?RCS:
?RCS: Revision 3.0 1993/08/18 12:05:44 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:d_bcopy: Inlibc
?MAKE: -pick add \$@ %<
?S:d_bcopy:
?S: This variable conditionally defines the HAS_BCOPY
symbol if
?S: the bcopy() routine is available to copy strings.
?S:.
?C:HAS_BCOPY:
?C: This symbol is defined if the bcopy() routine is available to
?C: copy blocks of memory.
?C:.
?H:#\$d_bcopy HAS_BCOPY /**/
?H:.
?M:bcopy: HAS_BCOPY
?M:#ifndef HAS_BCOPY
?M:#ifndef bcopy
?M:#define bcopy(s,d,l) memcpy((d),(s),(l))
?M:#endif
?M:#endif
?M:.
?LINT:set d_bcopy
: see if bcopy exists
set bcopy d_bcopy
eval \$inlibc

Found in path(s):
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/d_bcopy.U
No license file was found, but licenses were detected in source scan.

?RCS: \$Id: contains.U 1 2006-08-24 12:32:52Z rmanfredi \$
?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic Licence,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic Licence; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: contains.U,v \$

?RCS: Revision 3.0 1993/08/18 12:05:35 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?MAKE:contains: Nothing

?MAKE: -pick add \$@ %<

?S:contains:

?S: This variable holds the command to do a grep with a proper return

?S: status. On most sane systems it is simply "grep". On insane systems

?S: it is a grep followed by a cat followed by a test. This variable

?S: is primarily for the use of other Configure units.

?S:.

: Some

```
greps do not return status, grrr.
```

```
echo "grimblepritz" >grimble
```

```
if grep blurfldyick grimble >/dev/null 2>&1 ; then
```

```
contains=contains
```

```
elif grep grimblepritz grimble >/dev/null 2>&1 ; then
```

```
contains=grep
```

```
else
```

```
contains=contains
```

```
fi
```

```
rm -f grimble
```

: the following should work in any shell

```
case "$contains" in
```

```
contains*)
```

```
echo " "
```

```
echo "AGH! Grep doesn't return a status. Attempting remedial action."
```

```
cat >contains <<'EOSS'
```

```
grep "$1" "$2" >.greptmp && cat .greptmp && test -s .greptmp
```

```
EOSS
```

```
chmod +x contains
```

```
esac
```

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/contains.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: i_fp_class.U,v \$

```

?RCS:
?RCS: Copyright (c) 1998 Jarkko Hietaniemi
?RCS:
?RCS: You may distribute under the terms of either the GNU General Public
?RCS: License or the Artistic License, as specified in the README file.
?RCS:
?MAKE:i_fp_class: Inhdr Hasfield
?MAKE: -pick add $@ %<
?S:i_fp_class:
?S: This variable conditionally defines the I_FP_CLASS symbol, and indicates
?S: whether a C program should include <fp_class.h>.
?S:.
?C:I_FP_CLASS:
?C: This symbol, if defined, indicates that <fp_class.h> exists and
?C: should be included.
?C:.
?H:#$i_fp_class I_FP_CLASS /**/
?H:.
?LINT:set i_fp_class
: see if this is a fp_class.h system
set fp_class.h i_fp_class
eval $inhdr

```

Found in path(s):

```

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/perl/i_fp_class.U

```

No license file was found, but licenses were detected in source scan.

```

?RCS: $Id$
?RCS:
?RCS: Copyright (c) 1999 Jarkko Hietaniemi
?RCS:
?RCS: You may distribute under the terms of either the GNU General Public
?RCS: License or the Artistic License, as specified in the README file.
?RCS:
?MAKE:d_getspent_r: Inlibc
?MAKE: -pick add $@ %<
?S:d_getspent_r:
?S: This variable conditionally defines the HAS_GETSPENT_R symbol,
?S: which indicates to the C program that the getspent_r()
?S: routine is available.
?S:.
?C:HAS_GETSPENT_R:
?C: This symbol, if defined, indicates that the getspent_r routine
?C: is available to getspent re-entrantly.
?C:.
?H:#$d_getspent_r HAS_GETSPENT_R /**/
?H:.

```

```
?LINT:set d_getspent_r
: see if getspent_r exists
set getspent_r d_getspent_r
eval $inlibc
```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/threads/d_getspent_r.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: d_getgrnam_r.U,v 0RCS:
```

```
?RCS: Copyright (c) 2002,2003 Jarkko Hietaniemi
```

```
?RCS:
```

```
?RCS: You may distribute under the terms of either the GNU General Public
```

```
?RCS: License or the Artistic License, as specified in the README file.
```

```
?RCS:
```

```
?RCS: Generated by the reentr.pl from the Perl 5.8 distribution.
```

```
?RCS:
```

```
?MAKE:d_getgrnam_r getgrnam_r_proto: Inlibc Protochk Hasproto i_systypes \
  usethreads i_grp extern_C
```

```
?MAKE: -pick add $@ %<
```

```
?S:d_getgrnam_r:
```

```
?S: This variable conditionally defines the HAS_GETGRNAM_R symbol,
```

```
?S: which indicates to the C program that the getgrnam_r()
```

```
?S: routine is available.
```

```
?S:.
```

```
?S:getgrnam_r_proto:
```

```
?S: This variable encodes the prototype of getgrnam_r.
```

```
?S: It is zero if d_getgrnam_r is undef, and one of the
```

```
?S: REENTRANT_PROTO_T_ABC macros of reentr.h if d_getgrnam_r
```

```
?S: is defined.
```

```
?S:.
```

```
?C:HAS_GETGRNAM_R:
```

```
?C: This symbol, if defined, indicates that the getgrnam_r routine
```

```
?C: is available to
```

```
  getgrnam re-entrantly.
```

```
?C:.
```

```
?C:GETGRNAM_R_PROTO:
```

```
?C: This symbol encodes the prototype of getgrnam_r.
```

```
?C: It is zero if d_getgrnam_r is undef, and one of the
```

```
?C: REENTRANT_PROTO_T_ABC macros of reentr.h if d_getgrnam_r
```

```
?C: is defined.
```

```
?C:.
```

```
?H:#$d_getgrnam_r HAS_GETGRNAM_R /**/
```

```
?H:#define GETGRNAM_R_PROTO $getgrnam_r_proto /**/
```

```
?H:.
```

```
?T:try hdrs d_getgrnam_r_proto
```

```
: see if getgrnam_r exists
```

```

set getgrnam_r d_getgrnam_r
eval $inlibc
case "$d_getgrnam_r" in
"$define")
hdrs="$i_systypes sys/types.h define stdio.h $i_grp grp.h"
case "$d_getgrnam_r_proto:$susetheads" in
":define") d_getgrnam_r_proto=define
set d_getgrnam_r_proto getgrnam_r $hdrs
eval $hasproto ;;
*) ;;
esac
case "$d_getgrnam_r_proto" in
define)
case "$getgrnam_r_proto" in
"|0) try='int getgrnam_r(const char*, struct group*, char*, size_t, struct group**);'
./prochck "$extern_C $try" $hdrs && getgrnam_r_proto=I_CSBWR ;;
esac
case "$getgrnam_r_proto" in
"|0) try='int getgrnam_r(const char*, struct group*,
char*, int, struct group**);'
./prochck "$extern_C $try" $hdrs && getgrnam_r_proto=I_CSBIR ;;
esac
case "$getgrnam_r_proto" in
"|0) try='struct group* getgrnam_r(const char*, char*, int);'
./prochck "$extern_C $try" $hdrs && getgrnam_r_proto=S_CBI ;;
esac
case "$getgrnam_r_proto" in
"|0) try='int getgrnam_r(const char*, struct group*, char*, int);'
./prochck "$extern_C $try" $hdrs && getgrnam_r_proto=I_CSBI ;;
esac
case "$getgrnam_r_proto" in
"|0) try='struct group* getgrnam_r(const char*, struct group*, char*, int);'
./prochck "$extern_C $try" $hdrs && getgrnam_r_proto=S_CSBI ;;
esac
case "$getgrnam_r_proto" in
"|0) d_getgrnam_r=undef
getgrnam_r_proto=0
echo "Disabling getgrnam_r, cannot determine prototype." >&4 ;;
* ) case "$getgrnam_r_proto" in
REENTRANT_PROTO*) ;;
*) getgrnam_r_proto="REENTRANT_PROTO_${getgrnam_r_proto}" ;;
esac
echo "Prototype: $try" ;;
esac
;;
*) case "$susetheads" in
define) echo "getgrnam_r has no prototype,

```

```

not using it." >&4 ;;
esac
d_getgrnam_r=undef
getgrnam_r_proto=0
;;
esac
;;
*) getgrnam_r_proto=0
;;
esac

```

Found in path(s):

```

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/threads/d_getgrnam_r.U

```

No license file was found, but licenses were detected in source scan.

```

?RCS: $Id: i_sysstat.U 1 2006-08-24 12:32:52Z rmanfredi $
?RCS:
?RCS: Copyright (c) 1996, Andy Dougherty
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: $Log: i_sysstat.U,v $
?RCS: Revision 3.0.1.1 1997/02/28 15:48:30 ram
?RCS: patch61: created
?RCS:
?MAKE:i_sysstat: Inhdr
?MAKE: -pick add $@ %<
?S:i_sysstat:
?S: This variable conditionally defines the I_SYS_STAT symbol,
?S: and indicates whether a C program should include <sys/stat.h>.
?S:.
?C:I_SYS_STAT (I_SYSSTAT):
?C: This symbol, if defined, indicates to the C program that it should
?C: include <sys/stat.h>.
?C:.
?H:#$i_sysstat I_SYS_STAT /**/
?H:.
?LINT:set
i_sysstat
: see if sys/stat.h is available
set sys/stat.h i_sysstat
eval $inhdr

```

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/i_sysstat.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: privlib.U,v 3.1 1999/07/08 18:32:29 doughera Exp doughera \$

?RCS:

?RCS: Copyright (c) 1991-1993, Raphael Manfredi

?RCS:

?RCS: This file is included with or a derivative work of a file included

?RCS: with the metaconfig program of Raphael Manfredi's "dist" distribution.

?RCS: In accordance with clause 7 of dist's modified Artistic License:

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?RCS: \$Log: privlib.U,v \$

?RCS: Revision 3.1 1999/07/08 18:32:29 doughera

?RCS: Updated for perl5.005_5x

?RCS:

?RCS: Revision 3.0.1.4 1995/09/25 09:17:09 ram

?RCS: patch59: unit is now forced to the top of Configure, if possible

?RCS:

?RCS: Revision 3.0.1.3 1995/01/30 14:44:23 ram

?RCS: patch49: can now handle installation prefix changes (from WED)

?RCS:

?RCS: Revision 3.0.1.2 1994/08/29 16:31:52 ram

?RCS:

patch32: now uses installation prefix

?RCS:

?RCS: Revision 3.0.1.1 1993/09/13 16:12:34 ram

?RCS: patch10: added support for /local/lib (WED)

?RCS: patch10: prompt phrasing made more explicit (WED)

?RCS:

?RCS: Revision 3.0 1993/08/18 12:09:35 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?MAKE:privlib privlibexp installprivlib: package cat Getfile Oldconfig \

Setprefixvar Prefixit version installstyle binexp

?MAKE: -pick add \$@ %<

?Y:TOP

?D:privlib="

?S:privlib:

?S: This variable contains the eventual value of the PRIVLIB symbol,

?S: which is the name of the private library for this package. It may

?S: have a ~ on the front. It is up to the makefile to eventually create

?S: this directory while performing installation (with ~ substitution).

```

?S:.
?D:privlibexp="
?S:privlibexp:
?S: This variable is the ~name expanded version of privlib, so that you
?S: may use it directly in Makefiles or shell scripts.
?S:.
?D:installprivlib="
?S:installprivlib:
?S: This variable
is really the same as privlibexp but may differ on
?S: those systems using AFS. For extra portability, only this variable
?S: should be used in makefiles.
?S:.
?C:PRIVLIB:
?C: This symbol contains the name of the private library for this package.
?C: The library is private in the sense that it needn't be in anyone's
?C: execution path, but it should be accessible by the world. The program
?C: should be prepared to do ~ expansion.
?C:.
?C:PRIVLIB_EXP:
?C: This symbol contains the ~name expanded version of PRIVLIB, to be used
?C: in programs that are not prepared to deal with ~ expansion at run-time.
?C:.
?H:#define PRIVLIB "$privlib" /**/
?H:#define PRIVLIB_EXP "$privlibexp" /**/
?H:.
?LINT:change prefixvar
?LINT:set installprivlib
?LINT:set privlib
?LINT:set privlibexp
: determine where private library files go
: Usual default is /usr/local/lib/perl5/$version.
: Also allow things like /opt/perl/lib/$version, since
: /opt/perl/lib/perl5... would be redundant.
: The default "style"
setting is made in installstyle.U
case "$installstyle" in
*lib/perl5*) set dflt privlib lib/$package/$version ;;
*) set dflt privlib lib/$version ;;
esac
eval $prefixit
$cat <<EOM

```

There are some auxiliary files for \$package that need to be put into a private library directory that is accessible by everyone.

EOM

?X: Force dependency on bin.U

```
fn=$binexp
fn=d~+
rp='Pathname where the private library files will reside?'
./getfile
prefixvar=privlib
./setprefixvar
```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/installdirs/privlib.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: i_syssock.U 1 2006-08-24 12:32:52Z rmanfredi $
```

```
?RCS:
```

```
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
```

```
?RCS:
```

```
?RCS: You may redistribute only under the terms of the Artistic Licence,
```

```
?RCS: as specified in the README file that comes with the distribution.
```

```
?RCS: You may reuse parts of this distribution only within the terms of
```

```
?RCS: that same Artistic Licence; a copy of which may be found at the root
```

```
?RCS: of the source tree for dist 4.0.
```

```
?RCS:
```

```
?RCS: $Log: i_syssock.U,v $
```

```
?RCS: Revision 3.0 1993/08/18 12:08:36 ram
```

```
?RCS: Baseline for dist 3.0 netwide release.
```

```
?RCS:
```

```
?MAKE:i_syssock: Inhdr
```

```
?MAKE: -pick add $@ %<
```

```
?S:i_syssock:
```

```
?S: This variable conditionally defines the I_SYS_SOCKET symbol, and indicates
```

```
?S: whether a C program should include <sys/socket.h> before performing socket
```

```
?S: operations.
```

```
?S:.
```

```
?C:I_SYS_SOCKET:
```

```
?C: This symbol, if defined, indicates to the C program that it should
```

```
?C: include
```

```
<sys/socket.h> before performing socket calls.
```

```
?C:.
```

```
?H:#$i_syssock I_SYS_SOCKET /**/
```

```
?H:.
```

```
?LINT:set i_syssock
```

```
: see if this is a sys/socket.h system
```

```
set sys/socket.h i_syssock
```

```
eval $inhdr
```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/i_syssock.U
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_gconvert.U,v 3.0.1.3 1997/02/28 15:33:38 ram Exp \$

?RCS:

?RCS: Copyright (c) 1991-1993, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 3.0.

?RCS:

?RCS: Original Author: Andy Dougherty <doughera@lafcol.lafayette.edu>

?RCS:

?RCS: \$Log: d_gconvert.U,v \$

?RCS: Revision 3.0.1.3 1997/02/28 15:33:38 ram

?RCS: patch61: integrated new unit from perl5

?RCS:

?RCS: Revision 3.0.1.2 1995/07/25 13:55:59 ram

?RCS: patch56: improved comments about the Gconvert macro (ADO)

?RCS: patch56: force compile-link test since it may exist but be unusable (ADO)

?RCS:

?RCS: Revision 3.0.1.1 1994/10/29 16:12:51 ram

?RCS: patch36:

created by ADO

?RCS:

?MAKE:d_Gconvert: \

Compile cat Inlibc rm _o rm_try i_stdlib i_string d_qgcvt run \
uselongdouble d_longdbl d_PRIgldbl sPRIgldbl

?MAKE: -pick add \$@ %<

?S:d_Gconvert:

?S: This variable holds what Gconvert is defined as to convert

?S: floating point numbers into strings. By default, Configure

?S: sets this macro to use the first of gconvert, gcvt, or sprintf

?S: that pass sprintf-%g-like behavior tests. If perl is using

?S: long doubles, the macro uses the first of the following

?S: functions that pass Configure's tests: qgcvt, sprintf (if

?S: Configure knows how to make sprintf format long doubles--see

?S: sPRIgldbl), gconvert, gcvt, and sprintf (casting to double).

?S: The gconvert_preferance and gconvert_Id_preferance variables

?S: can be used to alter Configure's preferences, for doubles and

?S: long doubles, respectively. If present, they contain a

?S: space-separated list of one or more of the above function

?S: names in the order they should be tried.

?S:

?S: d_Gconvert

may be set to override Configure with a platform-

?S: specific function. If this function expects a double, a

?S: different value may need to be set by the uselongdouble.cbu
 ?S: call-back unit so that long doubles can be formatted without
 ?S: loss of precision.
 ?S:.
 ?C:Gconvert:
 ?C: This preprocessor macro is defined to convert a floating point
 ?C: number to a string without a trailing decimal point. This
 ?C: emulates the behavior of sprintf("%g"), but is sometimes much more
 ?C: efficient. If gconvert() is not available, but gcvt() drops the
 ?C: trailing decimal point, then gcvt() is used. If all else fails,
 ?C: a macro using sprintf("%g") is used. Arguments for the Gconvert
 ?C: macro are: value, number of digits, whether trailing zeros should
 ?C: be retained, and the output buffer.
 ?C: The usual values are:
 ?C: d_Gconvert='gconvert((x),(n),(t),(b))'
 ?C: d_Gconvert='gcvt((x),(n),(b))'
 ?C: d_Gconvert='sprintf((b),"%.*g",(n),(x))'
 ?C: The last two assume trailing
 zeros should not be kept.
 ?C:.
 ?H:#define Gconvert(x,n,t,b) \$d_Gconvert
 ?H:.
 ?T: xxx_list xxx_convert xxx_ld_list
 ?F:!try
 ?LINT:extern gconvert_preference
 ?LINT:extern gconvert_ld_preference
 : Check how to convert floats to strings.

if test "X\$d_Gconvert" = X; then

```

echo " "
echo "Checking for an efficient way to convert floats to strings."
echo " " > try.c
case "$uselongdouble" in
"$define") echo "#define USE_LONG_DOUBLE" >>try.c ;;
esac
case "$d_longdbl" in
"$define") echo "#define HAS_LONG_DOUBLE" >>try.c ;;
esac
case "$d_PRIgldbl" in
"$define") echo "#define HAS_PRIgldbl" >>try.c ;;
esac
$cat >>try.c <<EOP
#ifdef TRY_gconvert
#define Gconvert(x,n,t,b) gconvert((x),(n),(t),(b))
char *myname = "gconvert";
#endif
#ifdef TRY_gcvt

```

```

#define Gconvert(x,n,t,b) gcvt((x),(n),(b))
char *myname = "gcvt";
#endif
#ifdef TRY_qgcvt
#define Gconvert(x,n,t,b) qgcvt((x),(n),(b))
char *myname = "qgcvt";
#define DOUBLETYP long double
#endif
#ifdef TRY_sprintf
#if defined(USE_LONG_DOUBLE) && defined(HAS_LONG_DOUBLE)
#ifdef
HAS_PRIgldbl
#define Gconvert(x,n,t,b) sprintf((b),"%.*"$sPRIgldbl,(n),(x))
#else
#define Gconvert(x,n,t,b) sprintf((b),"%.*g", (n),(double)(x))
#endif
#else
#define Gconvert(x,n,t,b) sprintf((b),"%.*g", (n),(x))
#endif
char *myname = "sprintf";
#endif

#ifdef DOUBLETYP
#if defined(USE_LONG_DOUBLE) && defined(HAS_LONG_DOUBLE)
#define DOUBLETYP long double
#else
#define DOUBLETYP double
#endif
#endif

#include <stdio.h>

#ifdef I_STDLIB
#include <stdlib.h>
#endif
#ifdef I_STRING
#include <string.h>
#else
#include <strings.h>
#endif

int checkit(char *expect, char *got)
{
    if (strcmp(expect, got)) {
        printf("%s oddity: Expected %s, got %s\n",
            myname, expect, got);
    }
}

```

```

    exit(1);
}
}

int main()
{
    char buf[64];
    buf[63] = '\0';

    /* This must be 1st test on (which?) platform */
    /* Alan Burlison <AlanBurlsin@unn.unisys.com> */
    Gconvert((DOUBLETTYPE)0.1, 8, 0, buf);
    checkit("0.1", buf);

    Gconvert((DOUBLETTYPE)0.01,
    8, 0, buf);
    checkit("0.01", buf);

    Gconvert((DOUBLETTYPE)0.001, 8, 0, buf);
    checkit("0.001", buf);

    Gconvert((DOUBLETTYPE)0.0001, 8, 0, buf);
    checkit("0.0001", buf);

    Gconvert((DOUBLETTYPE)0.00009, 8, 0, buf);
    if (strlen(buf) > 5)
        checkit("9e-005", buf); /* for Microsoft ?? */
    else
        checkit("9e-05", buf);

    Gconvert((DOUBLETTYPE)1.0, 8, 0, buf);
    checkit("1", buf);

    Gconvert((DOUBLETTYPE)1.1, 8, 0, buf);
    checkit("1.1", buf);

    Gconvert((DOUBLETTYPE)1.01, 8, 0, buf);
    checkit("1.01", buf);

    Gconvert((DOUBLETTYPE)1.001, 8, 0, buf);
    checkit("1.001", buf);

    Gconvert((DOUBLETTYPE)1.0001, 8, 0, buf);
    checkit("1.0001", buf);

    Gconvert((DOUBLETTYPE)1.00001, 8, 0, buf);
    checkit("1.00001", buf);

```

```

Gconvert((DOUBLETYP)1.000001, 8, 0, buf);
checkit("1.000001", buf);

Gconvert((DOUBLETYP)0.0, 8, 0, buf);
checkit("0", buf);

Gconvert((DOUBLETYP)-1.0, 8, 0, buf);
checkit("-1", buf);

/* Some Linux gcvt's give 1.e+5 here. */
Gconvert((DOUBLETYP)100000.0, 8, 0, buf);
checkit("100000",
buf);

/* Some Linux gcvt's give -1.e+5 here. */
Gconvert((DOUBLETYP)-100000.0, 8, 0, buf);
checkit("-100000", buf);

Gconvert((DOUBLETYP)123.456, 8, 0, buf);
checkit("123.456", buf);

/* Testing of 1e+129 in bigintpm.t must not get extra '.' here. */
Gconvert((DOUBLETYP)1e34, 8, 0, buf);
/* 34 should be enough to scare even long double
* places into using the e notation. */
if (strlen(buf) > 5)
    checkit("1e+034", buf); /* for Microsoft */
else
    checkit("1e+34", buf);

/* For Perl, if you add additional tests here, also add them to
* t/base/num.t for benefit of platforms not using Configure or
* overriding d_Gconvert */

exit(0);
}
EOP
?X: List of order in which to search for functions.
?X: Usual order of efficiency is gconvert gcvt sprintf
?X: If a hint file sets a d_Gconvert="gconvert" or "gcvt" or "sprintf",
?X: then that is taken as a hint for which function to try first.
?X: (e.g. that function may be in a problematic /usr/ucblib library,
and
?X: the user may or may not choose to use -luch stuff.)
?X: Any other hint file (or previous config.sh) setting is left intact.
: first add preferred functions to our list
xxx_list=""
for xxx_convert in $gconvert_preference; do

```

```

case $xxx_convert in
  gcvt|gconvert|sprintf) xxx_list="$xxx_list $xxx_convert" ;;
  *) echo "Discarding unrecognized gconvert_preference $xxx_convert" >&4 ;;
esac
done
: then add any others
for xxx_convert in gconvert gcvt sprintf; do
  case "$xxx_list" in
    *$xxx_convert*) ;;
    *) xxx_list="$xxx_list $xxx_convert" ;;
  esac
done

case "$d_longdbl$uselongdouble" in
"$define$define")
  : again, add preferred functions to our list first
  xxx_ld_list=""
  for xxx_convert in $gconvert_ld_preference; do
    case $xxx_convert in
      qgcvt|gcvt|gconvert|sprintf) xxx_ld_list="$xxx_ld_list $xxx_convert" ;;
      *) echo "Discarding unrecognized gconvert_ld_preference $xxx_convert" ;;
    esac
  done
  : then add qgcvt, sprintf--then,
in xxx_list order, gconvert and gcvt
  for xxx_convert in qgcvt sprintf $xxx_list; do
    case "$xxx_ld_list" in
      $xxx_convert*|*" $xxx_convert"*) ;;
      *) xxx_ld_list="$xxx_ld_list $xxx_convert" ;;
    esac
  done
  : if sprintf cannot do long doubles, move it to the end
  if test "$d_PRIgldbl" != "$define"; then
    xxx_ld_list=""echo $xxx_ld_list|sed s/sprintf/^ sprintf"
  fi
  : if no qgcvt, remove it
  if test "$d_qgcvt" != "$define"; then
    xxx_ld_list=""echo $xxx_ld_list|sed s/qgcvt/^"
  fi
  : use the ld_list
  xxx_list="$xxx_ld_list"
  ;;
esac

for xxx_convert in $xxx_list; do
  echo "Trying $xxx_convert..."
?X: Do NOT use $rm_try here, as we need to keep try.c
$rm -f try try$_o core

```

```

set try -DTRY_`$xxx_convert`
if eval $compile; then
  echo "$xxx_convert() found." >&4
  if $run ./try; then
    echo "I'll use $xxx_convert to convert floats into a string." >&4
    break;
  else
    echo "...But $xxx_convert didn't
work as I expected."
    xxx_convert="
  fi
else
  echo "$xxx_convert NOT found." >&4
  fi
done

if test X$xxx_convert = X; then
  echo "*** WHOA THERE!!! ***" >&4
  echo "None of ($xxx_list) seemed to work properly. I'll use sprintf." >&4
  xxx_convert=sprintf
fi

case "$xxx_convert" in
gconvert) d_Gconvert='gconvert((x),(n),(t),(b))' ;;
gcvt) d_Gconvert='gcvt((x),(n),(b))' ;;
qgcvt) d_Gconvert='qgcvt((x),(n),(b))' ;;
*) case "$uselongdouble$d_longdbl$d_PRIgldbl" in
"$define$define$define")
  d_Gconvert="sprintf((b),\"%. *\"$sPRIgldbl,(n),(x))" ;;
"$define$define$undef")
  d_Gconvert='sprintf((b),\"%. *g\",(n),(double)(x))' ;;
*) d_Gconvert='sprintf((b),\"%. *g\",(n),(x))' ;;
esac
;;
esac

fi
$rm_try

```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/compline/d_gconvert.U
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: perlpath.U,v 3.0.1.2 1995/09/25 09:17:04 ram Exp \$

?RCS:

?RCS: Copyright (c) 1991-1993, Raphael Manfredi

?RCS:

?RCS: This file is included with or a derivative work of a file included
?RCS: with the metaconfig program of Raphael Manfredi's "dist" distribution.
?RCS: In accordance with clause 7 of dist's modified Artistic License:
?RCS:
?RCS: You may distribute under the terms of either the GNU General Public
?RCS: License or the Artistic License, as specified in the README file.
?RCS:
?RCS: \$Log: perlpath.U,v \$
?RCS:
?RCS: Special perl5 unit -- we haven't installed perl yet.
?RCS:
?RCS: Revision 3.0.1.2 1995/09/25 09:17:04 ram
?RCS: patch59: unit is now forced to the top of Configure, if possible
?RCS:
?RCS: Revision 3.0.1.1 1995/01/11 15:33:53 ram
?RCS: patch45: can now use Loc variables since path stripping is deferred
?RCS:
?RCS: Revision 3.0 1993/08/18 12:09:32 ram
?RCS: Baseline for dist
3.0 netwide release.
?RCS:
?X:
?X: The purpose of this unit is to locate perl good enough to construct a #!
?X:
?MAKE:perlpath: cat Getfile Loc Myread Oldconfig initialinstalllocation \
startperl version versiononly
?MAKE: -pick add \$@ %<
?Y:TOP
?S:perlpath:
?S: This variable contains the eventual value of the PERLPATH symbol,
?S: which contains the name of the perl interpreter to be used in
?S: shell scripts and in the "eval 'exec'" idiom. This variable is
?S: not necessarily the pathname of the file containing the perl
?S: interpreter; you must append the executable extension (_exe) if
?S: it is not already present. Note that Perl code that runs during
?S: the Perl build process cannot reference this variable, as Perl
?S: may not have been installed, or even if installed, may be a
?S: different version of Perl.
?S:.
?C:PERLPATH:
?C: This symbol contains the name of the perl interpreter to be
?C: used in shell scripts and in the "eval 'exec'" idiom.
?C:.
?H:#define PERLPATH "\$perlpath" /**/
?H:.
:
figure best path for perl in scripts
case "\$perlpath" in

```

")
case "$versiononly" in
"$define") perlpath="$initialinstalllocation/perl$version";;
*) perlpath="$initialinstalllocation/perl";;
esac
case "$startperl" in
*!*) ;;
*)
$cat <<EOH

```

I will use the "eval 'exec'" idiom to start Perl on your system.

I can use the full path of your Perl binary for this purpose, but doing so may cause problems if you want to share those scripts and Perl is not always in a standard place (\$initialinstalllocation/perl).

EOH

```

dflt="$initialinstalllocation/perl"
rp="What path shall I use in \"eval 'exec'\"?"
./myread
perlpath="$ans"
;;
esac
;;
esac
case "$startperl" in
*!*) ;;
*) echo "I'll use $perlpath in \"eval 'exec'\"";;
esac

```

Found in path(s):

```

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/perlpath.U

```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: orderlib.U,v 3.0.1.4 1997/02/28 16:18:18 ram Exp \$

?RCS:

?RCS: Copyright (c) 1991-1993, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 3.0.

?RCS:

?RCS: \$Log: orderlib.U,v \$

?RCS: Revision 3.0.1.4 1997/02/28 16:18:18 ram

?RCS: patch61: replaced .a with \$_a all over the place

?RCS: patch61: likewise for .o replaced by \$_o

?RCS: patch61: now uses the ar located by Loc.U

?RCS:

?RCS: Revision 3.0.1.3 1995/01/11 15:33:04 ram

?RCS: patch45: allows hint files to specify their own value for 'ranlib'

?RCS:

?RCS: Revision 3.0.1.2 1994/10/29 16:26:48 ram

?RCS: patch36: now performs a real small compile for accurate checks (ADO)

?RCS:

?RCS: Revision 3.0.1.1 1994/08/29 16:31:17 ram

?RCS: patch32: use cc variable instead of hardwired 'cc' in 1st compile

?RCS:

?RCS: Revision 3.0 1993/08/18 12:09:26 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?MAKE:orderlib ranlib: Loc ar cat test rm +cc +ccflags +ldflags +libs i_stdlib _a _o run

?MAKE: -pick add \$@ %<

?S:orderlib:

?S: This variable is "true" if the components of libraries must be ordered

?S: (with `lorder \$* | tsort`) before placing them in an archive. Set to

?S: "false" if ranlib or ar can generate random libraries.

?S:.

?S:ranlib:

?S: This variable is set to the pathname of the ranlib program, if it is

?S: needed to generate random libraries. Set to ":" if ar can generate

?S: random libraries or if random libraries are not supported

?S:.

?F:!foobar

: see if ar generates random libraries by itself

echo " "

echo "Checking how to generate random libraries on your machine..." >&4

?X: Some systems (like MIPS) complain when running

ar... Others like Ultrix

?X: need an explicit 'ar ts' to add the table of contents.

?X: Still others like Linux run ar ts successfully, but still need ranlib.

?X: This set of tests seems the minimum necessary to check out Linux.

?X: We need to explicitly put the entries in out-of-order so that Sun's ld

?X: will fail. (Otherwise it complains, but gives an exit status of 0.)

echo 'int bar1() { return bar2(); }' > bar1.c

echo 'int bar2() { return 2; }' > bar2.c

\$cat > foo.c <<EOP

#\$i_stdlib I_STDLIB

#ifdef I_STDLIB

#include <stdlib.h>

#endif

int main() { printf("%d\n", bar1()); exit(0); }

EOP

\$cc \$ccflags -c bar1.c >/dev/null 2>&1

```

$cc $cflags -c bar2.c >/dev/null 2>&1
$cc $cflags -c foo.c >/dev/null 2>&1
$ar rc bar$_a bar2$_o bar1$_o >/dev/null 2>&1
if $cc -o foobar $cflags $ldflags foo$_o bar$_a $libs >/dev/null 2>&1 &&
$run ./foobar >/dev/null 2>&1; then
echo "$ar appears to generate random libraries itself."
orderlib=false
if [ "X$ranlib" = "X" ]; then
    ranlib=":"
fi
elif
$ar s bar$_a >/dev/null 2>&1 &&
$cc -o foobar $cflags $ldflags foo$_o bar$_a $libs >/dev/null 2>&1 &&
$run ./foobar >/dev/null 2>&1; then
    echo "a table of contents needs to be added with '$ar s'."
    orderlib=false
    ranlib="$ar s"
elif $ar ts bar$_a >/dev/null 2>&1 &&
$cc -o foobar $cflags $ldflags foo$_o bar$_a $libs >/dev/null 2>&1 &&
$run ./foobar >/dev/null 2>&1; then
    echo "a table of contents needs to be added with '$ar ts'."
    orderlib=false
    ranlib="$ar ts"
else
?X: Allow hints to specify their own ranlib "script". For instance, on
?X: some NeXT machines, the timestamp put by ranlib is not correct, and this
?X: may raise tedious recompiles for nothing. Therefore, NeXT may add the
?X: ranlib='sleep 5; /bin/ranlib' line in their hints to "fix" that.
?X: (reported by Andreas Koenig <k@franz.ww.tu-berlin.de>)
case "$ranlib" in
:) ranlib=";;
")
    ranlib=`./loc ranlib X /usr/bin /bin /usr/local/bin`
    $test -f $ranlib || ranlib="
;;
esac
if $test -n "$ranlib";
then
echo "your system has '$ranlib'; we'll use that."
orderlib=false
else
echo "your system doesn't seem to support random libraries"
echo "so we'll use lorder and tsort to order the libraries."
orderlib=true
ranlib=":"
fi
fi
$rm -f foo* bar*

```

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/compline/orderlib.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: nis.U,v \$

?RCS: Revision 3.0.1.3 1997/02/28 16:17:38 ram

?RCS: patch61: ensure suitable defaults for hostcat and friends

?RCS:

?RCS: Revision 3.0.1.2 1995/03/21 08:48:34 ram

?RCS: patch52: continued fix for NeXT NIS/NetInfo handling

?RCS:

?RCS: Revision 3.0.1.1 1995/02/15 14:16:23 ram

?RCS: patch51: now correctly handles NeXT using NIS rather than NetInfo

?RCS:

?RCS: Revision 3.0 1993/08/18 12:09:24 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?MAKE:passcat groupcat hostcat:

Myread Oldconfig test contains

?MAKE: -pick add \$@ %<

?S:passcat:

?S: This variable contains a command that produces the text of the

?S: /etc/passwd file. This is normally "cat /etc/passwd", but can be

?S: "ypcat passwd" when NIS is used.

?S:.

?S:groupcat:

?S: This variable contains a command that produces the text of the

?S: /etc/group file. This is normally "cat /etc/group", but can be

?S: "ypcat group" when NIS is used.

?S:.

?S:hostcat:

?S: This variable contains a command that produces the text of the

?S: /etc/hosts file. This is normally "cat /etc/hosts", but can be

?S: "ypcat hosts" when NIS is used.

?S:.

: see if we have to deal with yellow pages, now NIS.

?X: NeXT gives us some fun here, as always, by having both NIS (former YP)

?X: and NetInfo. But since it has both, it's ok to put the test inside the if.

?X: Contributed by Thomas Neumann <tom@smart.bo.open.de>.

```
if $test -d /usr/etc/yp || $test -d /etc/yp || $test -d /usr/lib/yp; then
```

```
if $test -f /usr/etc/nibindd; then
```

```
echo
```

```
" "
```

```
echo "I'm fairly confident you're on a NeXT."
```

```
@if passcat || groupcat
```

```
echo " "
```

```
rp='Do you get the passwd file via NetInfo?'
```

```
dflt=y
```

```
case "$passcat" in
```

```
nidump*) ;;
```

```
");;
```

```
*) dflt=n;;
```

```
esac
```

```
./myread
```

```
case "$ans" in
```

```
y*) passcat='nidump passwd .'
```

```
@if groupcat
```

```
echo "(Assuming /etc/group is also distributed.)"
```

```
groupcat='nidump group .'
```

```
@end
```

```
::
```

```
*) echo "You told me, so don't blame me."
```

```
case "$passcat" in
```

```
nidump*) passcat="
```

```
@if groupcat
```

```
groupcat="";;
```

```
@end
```

```
esac
```

```
@if groupcat
```

```
echo "(Assuming /etc/group is handled the same way.)"
```

```
@end
```

```
::
```

```
esac
```

```
@end
```

```
@if hostcat
```

```
echo " "
```

```
rp='Do you get the hosts file via NetInfo?'
```

```
dflt=y
```

```
case "$hostcat" in
```

```
nidump*) ;;
```

```
");;
```

```
*) dflt=n;;
```

```
esac
```

```
./myread
```

```

case "$ans" in
y*) hostcat='nidump hosts .';;
*) case "$hostcat" in
nidump*) hostcat="";;
esac
;;
esac
@end
fi
@if passcat || groupcat
case "$passcat" in
nidump*) ;;
*)
case "$passcat" in
*yecat*) dflt=y;;
")
if $contains '^\\+' /etc/passwd >/dev/null 2>&1; then
dflt=y
else
dflt=n
fi;;
*) dflt=n;;
esac
echo " "
rp='Are you getting the passwd file via yellow pages?'
./myread
case "$ans" in
y*) passcat='ypcat passwd'
@if groupcat
echo "(Assuming /etc/group is also distributed.)"
groupcat='ypcat group'
@end
;;
*) passcat='cat /etc/passwd'
@if groupcat
echo "(Assuming /etc/group is also local.)"
groupcat='cat /etc/group'
@end
;;
esac
;;
esac
@end
@if hostcat
case "$hostcat" in
nidump*) ;;
*)
case "$hostcat" in

```

```

*ypcat*) dflt=y;;
") if $contains '\+' /etc/passwd >/dev/null 2>&1; then
    dflt=y
else
    dflt=n
fi;;
*) dflt=n;;
esac
echo " "
rp='Are you getting the hosts file via yellow pages?'
./myread
case "$ans" in
y*) hostcat='ypcat hosts';;
*) hostcat='cat /etc/hosts';;
esac
;;
esac
@end
fi
?X: Ensure suitable default -- Manoj Srivastava
case "$hostcat" in
") hostcat=':
$test -f /etc/hosts && hostcat='cat
/etc/hosts';;
esac
case "$groupcat" in
") groupcat=':
$test -f /etc/group && groupcat='cat /etc/group';;
esac
case "$passcat" in
") passcat=':
$test -f /etc/passwd && passcat='cat /etc/passwd';;
esac

```

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/nis.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_longdbl.U,v \$

?RCS:

?RCS: Copyright (c) 1998 Andy Dougherty

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?RCS: \$Log: d_longdbl.U,v \$

?RCS:

```
?MAKE:d_longdbl longdblsize d_ldexpl longdblkind \
d_long_double_style_ieee d_long_double_style_ieee_doubledouble \
d_long_double_style_ieee_extended d_long_double_style_ieee_std \
d_long_double_style_vax: Compile Setvar Myread \
Inlibc run echo cat rm_try test doublesize i_stdlib i_float
?MAKE: -pick add $@ %<
?S:d_longdbl:
?S: This variable conditionally defines HAS_LONG_DOUBLE if
?S: the long double type is supported.
?S:.
?S:d_ldexpl:
?S: This variable conditionally defines the HAS_LDEXPL symbol, which
?S: indicates to the C program that the ldexpl() routine is available.
?S:.
?S:longdblsize:
?S: This variable contains the value of the LONG_DOUBLESIZE
symbol, which
?S: indicates to the C program how many bytes there are in a long double,
?S: if this system supports long doubles. Note that this is
?S: sizeof(long double), which may include unused bytes.
?S:.
?S:longdblkind:
?S: This variable, if defined, encodes the type of a long double:
?S: 0 = double,
?S: 1 = IEEE 754 128-bit little endian,
?S: 2 = IEEE 754 128-bit big endian,
?S: 3 = x86 80-bit little endian,
?S: 4 = x86 80-bit big endian,
?S: 5 = double-double 128-bit little endian,
?S: 6 = double-double 128-bit big endian,
?S: 7 = 128-bit mixed-endian double-double (64-bit LEs in BE),
?S: 8 = 128-bit mixed-endian double-double (64-bit BEs in LE),
?S: 9 = 128-bit PDP-style mixed-endian long doubles,
?S: -1 = unknown format.
?S:.
?S:d_long_double_style_ieee:
?S: This variable conditionally defines LONG_DOUBLE_STYLE_IEEE
?S: if the long double is any of the IEEE 754 style long doubles:
?S: LONG_DOUBLE_STYLE_IEEE_STD, LONG_DOUBLE_STYLE_IEEE_EXTENDED,
?S: LONG_DOUBLE_STYLE_IEEE_DOUBLEDDOUBLE.
?S:.
?S:d_long_double_style_ieee_doubledouble:
?S: This
variable conditionally defines LONG_DOUBLE_STYLE_IEEE_DOUBLEDDOUBLE
?S: if the long double is the 128-bit IEEE 754 double-double.
?S:.
?S:d_long_double_style_ieee_extended:
?S: This variable conditionally defines LONG_DOUBLE_STYLE_IEEE_EXTENDED
```

?S: if the long double is the 80-bit IEEE 754 extended precision.

?S: Note that despite the 'extended' this is less than the 'std',

?S: since this is an extension of the double precision.

?S:.

?S:d_long_double_style_ieee_std:

?S: This variable conditionally defines LONG_DOUBLE_STYLE_IEEE_STD

?S: if the long double is the 128-bit IEEE 754.

?S:.

?S:d_long_double_style_vax:

?S: This variable conditionally defines LONG_DOUBLE_STYLE_VAX

?S: if the long double is the 128-bit VAX format H.

?S:.

?C:HAS_LONG_DOUBLE:

?C: This symbol will be defined if the C compiler supports long

?C: doubles.

?C:.

?C:LONG_DOUBLESIZE:

?C: This symbol contains the size of a long double, so that the

?C: C

preprocessor can make decisions based on it. It is only

?C: defined if the system supports long doubles. Note that this

?C: is sizeof(long double), which may include unused bytes.

?C:.

?C:HAS_LDEXPL:

?C: This symbol, if defined, indicates that the ldexpl routine is

?C: available to shift a long double floating-point number

?C: by an integral power of 2.

?C:.

?C:LONG_DOUBLEKIND:

?C: LONG_DOUBLEKIND will be one of

?C: LONG_DOUBLE_IS_DOUBLE

?C: LONG_DOUBLE_IS_IEEE_754_128_BIT_LITTLE_ENDIAN

?C: LONG_DOUBLE_IS_IEEE_754_128_BIT_BIG_ENDIAN

?C: LONG_DOUBLE_IS_X86_80_BIT_LITTLE_ENDIAN

?C: LONG_DOUBLE_IS_X86_80_BIT_BIG_ENDIAN

?C: LONG_DOUBLE_IS_DOUBLEDDOUBLE_128_BIT_LE_LE

?C: LONG_DOUBLE_IS_DOUBLEDDOUBLE_128_BIT_BE_BE

?C: LONG_DOUBLE_IS_DOUBLEDDOUBLE_128_BIT_LE_BE

?C: LONG_DOUBLE_IS_DOUBLEDDOUBLE_128_BIT_BE_LE

?C: LONG_DOUBLE_IS_VAX_H_FLOAT

?C: LONG_DOUBLE_IS_UNKNOWN_FORMAT

?C: It is only defined if the system supports long doubles.

?C:.

?C:LONG_DOUBLE_STYLE_IEEE:

?C: This symbol, if defined,

indicates that the long double

?C: is any of the IEEE 754 style long doubles:

?C: LONG_DOUBLE_STYLE_IEEE_STD, LONG_DOUBLE_STYLE_IEEE_EXTENDED,

?C: LONG_DOUBLE_STYLE_IEEE_DOUBLEDDOUBLE.
?C:.
?C:LONG_DOUBLE_STYLE_IEEE_DOUBLEDDOUBLE:
?C: This symbol, if defined, indicates that the long double is
?C: the 128-bit double-double.
?C:.
?C:LONG_DOUBLE_STYLE_IEEE_EXTENDED:
?C: This symbol, if defined, indicates that the long double is
?C: the 80-bit IEEE 754. Note that despite the 'extended' this
?C: is less than the 'std', since this is an extension of
?C: the double precision.
?C:.
?C:LONG_DOUBLE_STYLE_IEEE_STD:
?C: This symbol, if defined, indicates that the long double is
?C: the 128-bit IEEE 754.
?C:.
?C:LONG_DOUBLE_STYLE_VAX:
?C: This symbol, if defined, indicates that the long double is
?C: the 128-bit VAX format H.
?C:.
?H:#\$d_ldexpl HAS_LDEXPL /**/
?H:#\$d_longdbl HAS_LONG_DOUBLE /**/
?H:?LONG_DOUBLESIZE:#ifdef HAS_LONG_DOUBLE
?H:?LONG_DOUBLESIZE:#define LONG_DOUBLESIZE \$longdblsize /**/
?H:?LONG_DOUBLESIZE:#define
LONG_DOUBLEKIND \$longdblkind /**/
?H:?LONG_DOUBLESIZE:#define LONG_DOUBLE_IS_DOUBLE 0
?H:?LONG_DOUBLESIZE:#define LONG_DOUBLE_IS_IEEE_754_128_BIT_LITTLE_ENDIAN 1
?H:?LONG_DOUBLESIZE:#define LONG_DOUBLE_IS_IEEE_754_128_BIT_BIG_ENDIAN 2
?H:?LONG_DOUBLESIZE:#define LONG_DOUBLE_IS_X86_80_BIT_LITTLE_ENDIAN 3
?H:?LONG_DOUBLESIZE:#define LONG_DOUBLE_IS_X86_80_BIT_BIG_ENDIAN 4
?H:?LONG_DOUBLESIZE:#define LONG_DOUBLE_IS_DOUBLEDDOUBLE_128_BIT_LE_LE 5
?H:?LONG_DOUBLESIZE:#define LONG_DOUBLE_IS_DOUBLEDDOUBLE_128_BIT_BE_BE 6
?H:?LONG_DOUBLESIZE:#define LONG_DOUBLE_IS_DOUBLEDDOUBLE_128_BIT_LE_BE 7
?H:?LONG_DOUBLESIZE:#define LONG_DOUBLE_IS_DOUBLEDDOUBLE_128_BIT_BE_LE 8
?H:?LONG_DOUBLESIZE:#define LONG_DOUBLE_IS_VAX_H_FLOAT 9
?H:?LONG_DOUBLESIZE:#define LONG_DOUBLE_IS_UNKNOWN_FORMAT -1
?H:?LONG_DOUBLESIZE:#define LONG_DOUBLE_IS_DOUBLEDDOUBLE_128_BIT_LITTLE_ENDIAN
LONG_DOUBLE_IS_DOUBLEDDOUBLE_128_BIT_LE_LE /* back-compat */
?H:?LONG_DOUBLESIZE:#define LONG_DOUBLE_IS_DOUBLEDDOUBLE_128_BIT_BIG_ENDIAN
LONG_DOUBLE_IS_DOUBLEDDOUBLE_128_BIT_BE_BE
/* back-compat */
?H:?LONG_DOUBLESIZE:#\$d_long_double_style_ieee LONG_DOUBLE_STYLE_IEEE
?H:?LONG_DOUBLESIZE:#\$d_long_double_style_ieee_doubledouble
LONG_DOUBLE_STYLE_IEEE_DOUBLEDDOUBLE
?H:?LONG_DOUBLESIZE:#\$d_long_double_style_ieee_extended
LONG_DOUBLE_STYLE_IEEE_EXTENDED
?H:?LONG_DOUBLESIZE:#\$d_long_double_style_ieee_std LONG_DOUBLE_STYLE_IEEE_STD

```

?H:?LONG_DOUBLESIZE:#$d_long_double_style_vax LONG_DOUBLE_STYLE_VAX
?H:?LONG_DOUBLESIZE:#endif
?H:
?F:!try
?LINT:known LONG_DOUBLE_IS_DOUBLE LONG_DOUBLE_IS_IEEE_754_128_BIT_LITTLE_ENDIAN
?LINT:known LONG_DOUBLE_IS_IEEE_754_128_BIT_BIG_ENDIAN
LONG_DOUBLE_IS_X86_80_BIT_LITTLE_ENDIAN
?LINT:known LONG_DOUBLE_IS_X86_80_BIT_BIG_ENDIAN
LONG_DOUBLE_IS_DOUBLEDDOUBLE_128_BIT_LITTLE_ENDIAN
?LINT:known LONG_DOUBLE_IS_DOUBLEDDOUBLE_128_BIT_BIG_ENDIAN
LONG_DOUBLE_IS_UNKNOWN_FORMAT
?LINT:known LONG_DOUBLE_IS_DOUBLEDDOUBLE_128_BIT_LE_LE
?LINT:known LONG_DOUBLE_IS_DOUBLEDDOUBLE_128_BIT_BE_BE
?LINT:known
LONG_DOUBLE_IS_DOUBLEDDOUBLE_128_BIT_LE_BE
?LINT:known LONG_DOUBLE_IS_DOUBLEDDOUBLE_128_BIT_BE_LE
?LINT:known LONG_DOUBLE_IS_VAX_H_FLOAT
?LINT:set d_longdbl
?LINT:set d_ldexpl
: check for long doubles
echo " "
echo "Checking to see if you have long double..." >&4
echo 'int main() { long double x = 7.0; }' > try.c
set try
if eval $compile; then
val="$define"
echo "You have long double."
else
val="$undef"
echo "You do not have long double."
fi
$rm_try
set d_longdbl
eval $setvar

: see if ldexpl exists
set ldexpl d_ldexpl
eval $inlibc

@if LONG_DOUBLESIZE || longdblsize
: check for length of long double
?X: Check only if d_longdbl and if longdblsize is not already set.
case "${d_longdbl}${longdblsize}" in
$define)
echo " "
echo "Checking to see how big your long doubles are..." >&4
$cat >try.c <<'EOCP'
#include <stdio.h>

```

```

int main()
{
    printf("%d\n", sizeof(long double));
}
EOCP
set try
?X: Don't use compile_ok because some compilers warn you that they have
?X: 'long
double' as just 'double'.
set try
if eval $compile; then
    longdblsize=`$run ./try`
    echo "Your long doubles are $longdblsize bytes long."
else
    dflt='8'
    echo " "
    echo "(I can't seem to compile the test program. Guessing...)" >&4
    rp="What is the size of a long double (in bytes)?"
    ./myread
    longdblsize="$ans"
fi
if $test "X$doublesize" = "X$longdblsize"; then
    echo "That isn't any different from an ordinary double."
    echo "I'll keep your setting anyway, but you may see some"
    echo "harmless compilation warnings."
fi
;;
esac
$rm_try
@end

$echo "Checking the kind of long doubles you have..." >&4
case "$d_longdbl" in
define)
$cat <<EOP >try.c
#i_float I_FLOAT
#i_stdlib I_STDLIB
#define LONGDBLSIZE $longdblsize
#define DOUBLESIZE $doublesize
#ifdef I_FLOAT
#include <float.h>
#endif
#ifdef I_STDLIB
#include <stdlib.h>
#endif
#include <stdio.h>
static const long double d = -0.1L;
int main() {

```

```

unsigned const char* b = (unsigned const char*)&d);
#if DOUBLESIZE
== LONGDBLSIZE
printf("0\n"); /* if it floats like double */
exit(0);
#endif
#if (LDBL_MANT_DIG == 113 || FLT128_MANT_DIG == 113) && LONGDBLSIZE == 16
if (b[0] == 0x9A && b[1] == 0x99 && b[15] == 0xBF) {
    /* IEEE 754 128-bit little-endian */
    printf("1\n");
    exit(0);
}
if (b[0] == 0xBF && b[14] == 0x99 && b[15] == 0x9A) {
    /* IEEE 128-bit big-endian, e.g. solaris sparc */
    printf("2\n");
    exit(0);
}
#endif
/* For alignment 32-bit platforms have the 80 bits in 12 bytes,
* while 64-bits platforms have it in 16 bytes. The trailing bytes
* cannot be trusted. */
#if LDBL_MANT_DIG == 64 && (LONGDBLSIZE == 16 || LONGDBLSIZE == 12)
if (b[0] == 0xCD && b[9] == 0xBF) {
    /* x86 80-bit little-endian, sizeof 12 (ILP32, Solaris x86)
    * or 16 (LP64, Linux and OS X), 4 or 6 bytes of padding.
    * Also known as "extended precision". */
    printf("3\n");
    exit(0);
}
if (b[0] == 0xBF && b[9] == 0xCD) {
    /* Is there ever big-endian 80-bit, really?

    *
    * The Motorola 68881 had another "extended precision" format:
    * sign:1 exp:15 zero:16 integer:1 mantissa:63
    * for total of 96 bits of bytes. The zero bits were unused.
    * See "M68000 FAMILY PROGRAMMER'S REFERENCE MANUAL" for more details.
    * If it ever becomes relevant, this format should be allocated
    * a new doublekind code since it's quite different from the Intel x87.
    */
    printf("4\n");
    exit(0);
}
#endif
#if (LDBL_MANT_DIG == 106 || LDBL_MANT_DIG == 107) && LONGDBLSIZE == 16
/* software "double double", the 106 is 53+53.
* but irix thinks it is 107. */
if (b[0] == 0x9A && b[7] == 0x3C && b[8] == 0x9A && b[15] == 0xBF) {

```

```

/* double double 128-bit fully little-endian,
 * little-endian doubles in little-endian order,
 * 9a 99 99 99 99 99 59 3c 9a 99 99 99 99 99 b9 bf */
printf("5\n");
exit(0);
}
if (b[0] == 0xBF && b[7] == 0x9A && b[8] == 0x3C && b[15] == 0x9A) {
/* double double 128-bit fully big-endian,
 * big-endian doubles in big-endian order,
 * e.g. PPC/Power and MIPS:
 * bf b9 99 99 99 99 9a 3c 59 99 99 99 99 9a */
printf("6\n");
exit(0);
}
if (b[0] == 0x9A && b[7] == 0xBF && b[8] == 0x9A && b[15] == 0x3C) {
/* double double 128-bit mixed endian.
 * little-endian doubles in big-endian order,
 * e.g. ppc64el,
 * 9a 99 99 99 99 99 b9 bf 9a 99 99 99 99 59 3c */
printf("7\n");
exit(0);
}
if (b[0] == 0x3C && b[7] == 0x9A && b[8] == 0xBF && b[15] == 0x9A) {
/* double double 128-bit mixed endian,
 * big-endian doubles in little-endian order,
 * 3c 59 99 99 99 99 9a bf b9 99 99 99 99 9a */
printf("8\n");
exit(0);
}
}
#endif
/* We are largely making this up because it may well be
 * that the VAX format H was never made available to C,
 * only to Fortran. */
#if LONGDBLSIZE == 16 && defined(__vax__)
if (b[0] == 0xFD && b[15] == 0x99) {
/* VAX format H, PDP-11 mixed endian. */
printf("9\n");

exit(0);
}
#endif
printf("-1\n"); /* unknown */
exit(0);
}
EOP
set try
if eval $compile; then
longdblkind=`$run ./try`

```

```

else
  longdblkind=-1
fi
;;
*) longdblkind=0 ;;
esac
case "$longdblkind" in
0) echo "Your long doubles are doubles." >&4 ;;
1) echo "You have IEEE 754 128-bit little endian long doubles." >&4 ;;
2) echo "You have IEEE 754 128-bit big endian long doubles." >&4 ;;
3) echo "You have x86 80-bit little endian long doubles." >& 4 ;;
4) echo "You have x86 80-bit big endian long doubles." >& 4 ;;
5) echo "You have 128-bit fully little-endian double-double long doubles (64-bit LEs in LE)." >& 4 ;;
6) echo "You have 128-bit fully big-endian double-double long doubles (64-bit BEs in BE)." >& 4 ;;
7) echo "You have 128-bit mixed-endian double-double long doubles (64-bit LEs in BE)." >& 4 ;;
8) echo "You have 128-bit mixed-endian double-double long doubles (64-bit BEs in LE)." >& 4 ;;
9) echo "You have 128-bit PDP-style mixed-endian long doubles (VAX format H)." >& 4 ;;
*)
  echo "Cannot figure out your long double." >&4 ;;
esac
d_long_double_style_ieee=$undef
d_long_double_style_ieee_std=$undef
d_long_double_style_ieee_extended=$undef
d_long_double_style_ieee_doubledouble=$undef
d_long_double_style_vax=$undef
case "$longdblkind" in
1|2|3|4|5|6|7|8) d_long_double_style_ieee=$define ;;
esac
case "$longdblkind" in
1|2) d_long_double_style_ieee_std=$define ;;
esac
case "$longdblkind" in
3|4) d_long_double_style_ieee_extended=$define ;;
esac
case "$longdblkind" in
5|6|7|8) d_long_double_style_ieee_doubledouble=$define ;;
esac
case "$longdblkind" in
9) d_long_double_style_vax=$define ;;
esac
$rm_try

```

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/modified/d_longdbl.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

```

?RCS:
?RCS: Copyright (c) 1999, Jarkko Hietaniemi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 3.0.
?RCS:
?MAKE:d_posix_mq: Setvar d_mq_open d_mq_unlink d_mq_close d_mq_send d_mq_receive d_mq_notify
d_mq_setattr d_mq_getattr i_mqueue
?MAKE: -pick add $@ %<
?S:d_posix_mq:
?S: This variable conditionally defines the HAS_POSIX_MQ symbol, which
?S: indicates that the entire POSIX mq_*(2) library is present.
?S:.
?C:HAS_POSIX_MQ:
?C: This symbol, if defined, indicates that the entire POSIX mq_*(2)
?C: library is supported.
?C:.
?H:#$d_posix_mq HAS_POSIX_MQ /**/
?H:.
?LINT:set d_posix_mq
: see how much of the 'POSIX mq_*(2)' library
is present.
echo " "
case
"$i_mqueue$d_mq_open$d_mq_close$d_mq_send$d_mq_receive$d_mq_notify$d_mq_setattr$d_mq_getattr$d_mq
_unlink" in
*"${undef}*" val="${undef}" ;;
*) val="${define}" ;;
esac
case "$val" in
"${define}") echo "You have the full POSIX mq_*(2) library." >&4 ;;
"${undef}") echo "You don't have the full POSIX mq_*(2) library." >&4 ;;
esac
set d_posix_mq
eval $setvar

```

Found in path(s):

```

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/perl/d_posix_mq.U

```

No license file was found, but licenses were detected in source scan.

```

?RCS: $Id: d_fd_set.U,v 3.0.1.3 1997/02/28 15:33:16 ram Exp $

```

```

?RCS:

```

```

?RCS: Copyright (c) 1991-1993, Raphael Manfredi

```

```

?RCS:

```

?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 3.0.
?RCS:
?RCS: \$Log: d_fd_set.U,v \$
?RCS: Revision 3.0.1.3 1997/02/28 15:33:16 ram
?RCS: patch61: added ?F: metalint hint
?RCS:
?RCS: Revision 3.0.1.2 1994/06/20 06:57:23 ram
?RCS: patch30: extended scope for fd_set checks (ADO)
?RCS:
?RCS: Revision 3.0.1.1 1994/01/24 14:06:27 ram
?RCS: patch16: comments for HAS_FD_* symbols were not consistent
?RCS:
?RCS: Revision 3.0 1993/08/18 12:06:02 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:d_fd_set d_fd_macros
d_fds_bits: Compile cat rm_try Oldconfig \
d_socket i_systime i_sysselect i_stdlib run
?MAKE: -pick add \$@ %<
?S:d_fd_set:
?S: This variable contains the eventual value of the HAS_FD_SET symbol,
?S: which indicates if your C compiler knows about the fd_set typedef.
?S:.
?S:d_fd_macros:
?S: This variable contains the eventual value of the HAS_FD_MACROS symbol,
?S: which indicates if your C compiler knows about the macros which
?S: manipulate an fd_set.
?S:.
?S:d_fds_bits:
?S: This variable contains the eventual value of the HAS_FDS_BITS symbol,
?S: which indicates if your fd_set typedef contains the fds_bits member.
?S: If you have an fd_set typedef, but the dweebs who installed it did
?S: a half-fast job and neglected to provide the macros to manipulate
?S: an fd_set, HAS_FDS_BITS will let us know how to fix the gaffe.
?S:.
?C:HAS_FD_SET:
?C: This symbol, when defined, indicates presence of the fd_set typedef
?C: in <sys/types.h>
?C:.
?C:HAS_FD_MACROS:
?C: This symbol, when defined,
indicates presence of the macros used to
?C: manipulate an fd_set.
?C:.

```

?C:HAS_FDS_BITS:
?C: This symbol, when defined, indicates presence of the fds_bits member in
?C: fd_set. This knowledge is useful if fd_set is available but the macros
?C: aren't.
?C:.
?H:#$d_fd_set HAS_FD_SET /**/
?H:#$d_fd_macros HAS_FD_MACROS /**/
?H:#$d_fds_bits HAS_FDS_BITS /**/
?H:.
?F:!try
: check for fd_set items
$cat <<EOM

```

Checking to see how well your C compiler handles fd_set and friends ...

EOM

?X: The FD_SET macros can be in strange places. On some SysV-based

?X: systems, they are in <sys/bsdtypes.h>, which is included (perhaps)

?X: by <sys/socket.h>. We won't force people to include

?X: <sys/bsdtypes.h> because it might introduce other

?X: incompatibilities.

```
$cat >try.c <<EOCP
```

```
#$i_stdlib I_STDLIB
```

```
#ifdef I_STDLIB
```

```
#include <stdlib.h>
```

```
#endif
```

```
#$i_systime I_SYS_TIME
```

```
#$i_sysselect I_SYS_SELECT
```

```
#$d_socket HAS_SOCKET
```

```
#include <sys/types.h>
```

```
#ifdef HAS_SOCKET
```

```
#include <sys/socket.h> /* Might include <sys/bsdtypes.h>
```

```
*/
```

```
#endif
```

```
#ifdef I_SYS_TIME
```

```
#include <sys/time.h>
```

```
#endif
```

```
#ifdef I_SYS_SELECT
```

```
#include <sys/select.h>
```

```
#endif
```

```
int main() {
```

```
    fd_set fds;
```

```
#ifdef TRYBITS
```

```
    if(fds.fds_bits);
```

```
#endif
```

```
#if defined(FD_SET) && defined(FD_CLR) && defined(FD_ISSET) && defined(FD_ZERO)
```

```
    exit(0);
```

```

#else
  exit(1);
#endif
}
EOCP
set try -DTRYBITS
if eval $compile; then
  d_fds_bits="$define"
  d_fd_set="$define"
  echo "Well, your system knows about the normal fd_set typedef..." >&4
  if $run ./try; then
    echo "and you have the normal fd_set macros (just as I'd expect)." >&4
    d_fd_macros="$define"
  else
    $cat >&4 <<'EOM'
but not the normal fd_set macros! Gaaack! I'll have to cover for you.
EOM
    d_fd_macros="$undef"
  fi
else
  $cat <<'EOM'
Hmm, your compiler has some difficulty with fd_set. Checking further...
EOM
  set try
  if eval $compile; then
    d_fds_bits="$undef"
    d_fd_set="$define"
    echo "Well, your system has some sort of fd_set available..." >&4
    if $run ./try; then
      echo "and you have the normal
fd_set macros." >&4
      d_fd_macros="$define"
    else
      $cat <<'EOM'
but not the normal fd_set macros! Gross! More work for me...
EOM
      d_fd_macros="$undef"
    fi
  else
    echo "Well, you got zip. That's OK, I can roll my own fd_set stuff." >&4
    d_fd_set="$undef"
    d_fds_bits="$undef"
    d_fd_macros="$undef"
  fi
fi
$rm_try

```

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/compline/d_fd_set.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_getgrent.U,v \$

?RCS:

?RCS: Copyright (c) 1998 Andy Dougherty

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?RCS: \$Log: d_getgrent.U,v \$

?RCS:

?MAKE:d_getgrent: Inlibc

?MAKE: -pick add \$@ %<

?S:d_getgrent:

?S: This variable conditionally defines the HAS_GETGREET symbol, which

?S: indicates to the C program that the getgrent() routine is available

?S: for sequential access of the group database.

?S:.

?C:HAS_GETGREET:

?C: This symbol, if defined, indicates that the getgrent routine is

?C: available for sequential access of the group database.

?C:.

?H:#\$d_getgrent HAS_GETGREET /**/

?H:.

?LINT:set d_getgrent

: see if getgrent exists

set getgrent d_getgrent

eval \$inlibc

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/modified/d_getgrent.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: installstyle.U,v 1.2 1999/07/13 14:56:06 doughera Exp \$

?RCS:

?RCS: Copyright (c) 1999 Andy Dougherty

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 3.0.

?RCS:

?RCS: \$Log: installstyle.U,v \$

?RCS: Revision 1.2 1999/07/13 14:56:06 doughera

?RCS: Fix dependencies. Add more comments.
?RCS:
?RCS: Revision 1.1 1999/07/12 17:30:41 doughera
?RCS: Initial revision
?RCS:
?RCS:
?MAKE:installstyle: prefix Myread
?MAKE: -pick add \$@ %<
?X: Myread dependence is for dflt.
?S:installstyle:
?S: This variable describes the "style" of the perl installation.
?S: This is intended to be useful for tools that need to
?S: manipulate entire perl
distributions. Perl itself doesn't use
?S: this to find its libraries -- the library directories are
?S: stored directly in Config.pm. Currently, there are only two
?S: styles: "lib" and "lib/perl5". The default library locations
?S: (e.g. privlib, sitelib) are either \$prefix/lib or
?S: \$prefix/lib/perl5. The former is useful if \$prefix is a
?S: directory dedicated to perl (e.g. /opt/perl), while the latter
?S: is useful if \$prefix is shared by many packages, e.g. if
?S: \$prefix=/usr/local.
?S:
?S: Unfortunately, while this "style" variable is used to set
?S: defaults for all three directory hierarchies (core, vendor, and
?S: site), there is no guarantee that the same style is actually
?S: appropriate for all those directories. For example, \$prefix
?S: might be /opt/perl, but \$siteprefix might be /usr/local.
?S: (Perhaps, in retrospect, the "lib" style should never have been
?S: supported, but it did seem like a nice idea at the time.)
?S:
?S: The situation is even less clear for
tools such as MakeMaker
?S: that can be used to install additional modules into
?S: non-standard places. For example, if a user intends to install
?S: a module into a private directory (perhaps by setting PREFIX on
?S: the Makefile.PL command line), then there is no reason to
?S: assume that the Configure-time \$installstyle setting will be
?S: relevant for that PREFIX.
?S:
?S: This may later be extended to include other information, so
?S: be careful with pattern-matching on the results.
?S:
?S: For compatibility with perl5.005 and earlier, the default
?S: setting is based on whether or not \$prefix contains the string
?S: "perl".
?S:.
: determine installation style

```
: For now, try to deduce it from prefix unless it is already set.
: Reproduce behavior of 5.005 and earlier, maybe drop that in 5.7.
case "$installstyle" in
") case "$prefix" in
  *perl*) dflt='lib';;
  *) dflt='lib/perl5' ;;
esac
;;
*) dflt="$installstyle" ;;
esac
: Probably not worth prompting for this since we prompt
for all
: the directories individually, and the prompt would be too long and
: confusing anyway.
installstyle=$dflt
```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/installdirs/installstyle.U
```

No license file was found, but licenses were detected in source scan.

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?MAKE:d_around: Inlibc

?MAKE: -pick add \$@ %<

?S:d_around:

?S: This variable conditionally defines the HAS_LROUND symbol, which

?S: indicates to the C program that the lround() routine is available

?S: to return the integral value nearest to x.

?S:.

?C:HAS_LROUND:

?C: This symbol, if defined, indicates that the lround routine is

?C: available to return the nearest integral value.

?C:.

?H:#\$d_around HAS_LROUND /**/

?H:.

?LINT:set d_around

: see if lround exists

set lround d_around

eval \$inlibc

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/perl/d_around.U
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:
?RCS: Copyright (c) 1998 Jarkko Hietaniemi
?RCS:
?RCS: You may distribute under the terms of either the GNU General Public
?RCS: License or the Artistic License, as specified in the README file.
?RCS:
?MAKE:d_atolf: Inlibc
?MAKE: -pick add \$@ %<
?S:d_atolf:
?S: This variable conditionally defines the HAS_ATOLF symbol, which
?S: indicates to the C program that the atolf() routine is available.
?S:.
?C:HAS_ATOLF:
?C: This symbol, if defined, indicates that the atolf routine is
?C: available to convert strings into long doubles.
?C:.
?H:#\$d_atolf HAS_ATOLF /**/
?H:.
?LINT:set d_atolf
: see if atolf exists
set atolf d_atolf
eval \$inlibc

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/atolf.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$
?RCS:
?RCS: Copyright (c) 1999, Jarkko Hietaniemi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 3.0.
?RCS:
?MAKE:d_mq_setattr: Inlibc
?MAKE: -pick add \$@ %<
?S:d_mq_setattr:
?S: This variable conditionally defines HAS_MQ_SETATTR if mq_setattr() is
?S: available to set the attributes of a POSIX message queue.
?S:.
?C:HAS_MQ_SETATTR:
?C: This symbol, if defined, indicates that the mq_setattr system call is
?C: available to set the attributes of a POSIX message queue.
?C:.

?H:#\$d_mq_setattr HAS_MQ_SETATTR /**/

?H:.

?LINT:set d_mq_setattr

: see if mq_setattr exists

set mq_setattr d_mq_setattr

eval \$inlibc

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_mq_setattr.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: Init.U,v 3.0.1.1 1994/10/31 09:45:59 ram Exp \$

?RCS:

?RCS: Copyright (c) 1991-1993, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 3.0.

?RCS:

?RCS: \$Log: Init.U,v \$

?RCS: Revision 3.0.1.1 1994/10/31 09:45:59 ram

?RCS: patch44: removed Options from MAKE to prevent Init overrides

?RCS: patch44: option processing now done after Myinit thanks to new Begin.U

?RCS: patch44: moved "Beginning of configuration questions" to Begin.U

?RCS: patch44: moved signal trapping instruction to Begin.U as well

?RCS:

?RCS: Revision 3.0 1993/08/18 12:05:02 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?X:

?X: This file

initializes certain default variables used by Configure. They

?X: may be overridden or added to by definitions in Myinit.U.

?X:

?MAKE:Init eunicefix: Null

?MAKE:-pick add \$@ %<

?MAKE:-pick weed \$@ ./Init

?S:eunicefix:

?S: When running under Eunice this variable contains a command which will

?S: convert a shell script to the proper form of text file for it to be

?S: executable by the shell. On other systems it is a no-op.

?S:.

?V:define undef smallmach:rmlist

?X:

?X: Throughout the units, one may make use of \$define and \$undef to reference

?X: a defined symbol or an undefined one. There is no need to add them in
?X: the dependency line since this unit makes them visible via ?V:, and
?X: everyone inherits from those symbols since by convention Init.U is the
?X: root dependency.

?X:

?LINT:extern DJGPP

?LINT:extern _exe

?LINT:change _exe

?LINT:extern is_os2

: Detect odd OSs

define='define'

undef='undef'

smallmach='pdp11 i8086 z8000 i80286 iAPX286'

rmlist=""

: We must find out about

Eunice early

eunicefix=':'

if test -f /etc/unixtovms; then

 eunicefix=/etc/unixtovms

fi

if test -f /etc/unixtovms.exe; then

 eunicefix=/etc/unixtovms.exe

fi

: Set executable suffix now -- needed before hints available

if test -f "/libs/version.library"; then

: Amiga OS

 _exe=""

elif test -f "/system/gnu_library/bin/ar.pm"; then

: Stratus VOS

 _exe=".pm"

elif test -n "\$DJGPP"; then

: DOS DJGPP

 _exe=".exe"

elif test -f /kern/cookiejar; then

: MiNT

 _exe=""

elif test -d c:/ -o -n "\$is_os2" ; then

: OS/2 or cygwin

 _exe=".exe"

fi

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/modified/Init.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: d_gethname.U,v \$

?RCS: Revision 3.0.1.1 1994/10/29 16:13:00 ram

?RCS: patch36: call ./xenix explicitly instead of relying on PATH

?RCS:

?RCS: Revision 3.0 1993/08/18 12:06:11 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?MAKE:d_gethname d_uname d_phostname aphostname: phostname cat \
myhostname package d_portable Loc echo n c +i_whoami +usrinc \
Myread Guess Oldconfig Csym

?MAKE: -pick add \$@ %<

?S:d_gethname:

?S: This variable conditionally defines the HAS_GETHOSTNAME symbol,
which

?S: indicates to the C program that the gethostname() routine may be

?S: used to derive the host name.

?S:.

?S:d_uname:

?S: This variable conditionally defines the HAS_UNAME symbol, which

?S: indicates to the C program that the uname() routine may be

?S: used to derive the host name.

?S:.

?S:d_phostname:

?S: This variable conditionally defines the PHOSTNAME symbol, which

?S: contains the shell command which, when fed to popen(), may be

?S: used to derive the host name.

?S:.

?S:aphostname:

?S: This variable contains the command which can be used to compute the
?S: host name. The command is fully qualified by its absolute path, to make
?S: it safe when used by a process with super-user privileges.

?S:.

?C:HAS_GETHOSTNAME (GETHOSTNAME):

?C: This symbol, if defined, indicates that the C program may use the
?C: gethostname() routine to derive the host name. See also HAS_UNAME
?C: and PHOSTNAME.

?C:.

?C:HAS_UNAME (UNAME):

?C: This symbol, if defined, indicates that the C program may use the
 ?C: uname() routine to derive the host name. See also HAS_GETHOSTNAME
 ?C: and PHOSTNAME.
 ?C:.
 ?C:PHOSTNAME:
 ?C: This symbol, if defined, indicates that the C program may use the
 ?C: contents of PHOSTNAME as a command to feed to the popen() routine
 ?C: to derive the host name. See also HAS_GETHOSTNAME and HAS_UNAME.
 ?C: Note that the command uses a fully qualified path, so that it is safe
 ?C: even if used by a process with super-user privileges.
 ?C:.

```
?H:#$d_gethname HAS_GETHOSTNAME /**/  

?H:#$d_uname HAS_UNAME /**/  

?H:#$d_phostname PHOSTNAME "$aphostname" /* How to get the host name */
```

?H:.

?T:file val call

?LINT:change i_whoami

: see how we will look up host name

echo " "

if false; then

 : dummy stub to allow use of elif

@if HAS_GETHOSTNAME

elif set gethostname val -f d_gethname; eval \$csym; \$val; then

 echo 'gethostname() found.' >&4

 d_gethname="\$define"

 call=gethostname

@end

@if HAS_UNAME

elif set uname val -f d_uname; eval \$csym; \$val; then

 if ./xenix; then

 \$cat <<'EOM'

uname()

 was found, but you're running xenix, and older versions of xenix
 have a broken uname(). If you don't really know whether your xenix is old
 enough to have a broken system call, use the default answer.

EOM

 dflt=y

 case "\$d_uname" in

 "\$define") dflt=n;;

 esac

 rp='Is your uname() broken?'

 ./myread

 case "\$ans" in

 n*) d_uname="\$define"; call=uname;;

 esac

 else

```

echo 'uname() found.' >&4
d_uname="$define"
call=uname
fi
@end
fi
case "$d_gethname" in
") d_gethname="$undef";;
esac
case "$d_uname" in
") d_uname="$undef";;
esac
@if PHOSTNAME || MYHOSTNAME
case "$d_uname$d_gethname" in
*define*)
dflt=n
cat <<EOM

```

Every now and then someone has a \$call() that lies about the hostname but can't be fixed for political or economic reasons. If you wish, I can

```

@if MYHOSTNAME && PHOSTNAME
pretend $call() isn't there and maybe compile in the hostname or
compute it from the '$phostname' command at run-time.
@elsif MYHOSTNAME
pretend $call() isn't there and maybe compile
in the hostname.
@elsif PHOSTNAME
pretend $call() isn't there and maybe compute hostname at run-time
thanks to the '$phostname' command.
@elsif WHOAMI
get the hostname from whomai.h (provided you have one).
@else
simply ignore your host name and use something like "noname" instead.
@end

```

```

EOM
rp="Shall I ignore $call() from now on?"
./myread
case "$ans" in
y*) d_uname="$undef" d_gethname="$undef"; $echo $n "Okay...$c";;
esac;;
esac
@end
@if PHOSTNAME || aphostname
?X: Compute the full path name for the command
case "$phostname" in
") aphostname="";;
*) case "$aphostname" in

```

```

/*) ;;
*) set X $phostname
  shift
  file=$1
  shift
  file=`./loc $file $file $pth`
  aphostname=`echo $file $*`
  ;;
esac
;;
esac
@end
@if PHOSTNAME && MYHOSTNAME
case "$d_uname$d_gethname" in
*define*) ;;
*)
case "$phostname" in
") ;;
*)
$cat <<EOT

```

There is no gethostname() or uname() on this system. You have two possibilities at this point:

- 1) You can have your host name (\$myhostname) compiled into \$package, which lets \$package start up faster, but makes your binaries non-portable, or
- 2) you can have \$package use a

```
popen("$aphostname","r")
```

which will start slower but be more portable.

```
@ if WHOAMI
```

Option 1 will give you the option of using whoami.h if you have one.

```
@ end
```

If you want option 2 but with a different command, you can edit config.sh at the end of this shell script.

```
EOT
```

```

case "$d_phostname" in
"$define") dflt=n;;
"$undef") dflt=y;;
")
case "$d_portable" in
"$define") dflt=n ;;
*) dflt=y ;;
esac;;

```

```

esac
rp="Do you want your host name compiled in?"
./myread
case "$ans" in
n*) d_phostname="$define" ;;
*) aphostname=""; d_phostname="$undef";;
esac;;
esac
case "$aphostname" in
")
@ if WHOAMI
case "$i_whoami" in
"$define")
dflt=y
$cat <<EOM

```

No hostname function--you can either use the whoami.h file, which has this line:

```
`grep sysname $usrinc/whoami.h`
```

or you can have the name we came up with earlier
(\$myhostname) hardwired in.

EOM

```

rp="Use whoami.h to get hostname?"
./myread
case "$ans" in
n*) i_whoami="$undef";;
esac
;;
"$undef")
$cat <<EOM

```

No hostname function and no whoami.h -- hardwiring "\$myhostname".

EOM

```

;;
esac;;
@ else
echo 'No hostname function -- hardwiring "$myhostname".' >&4;;
@ end
esac;;
esac
@elsif PHOSTNAME
case "$d_undef$d_gethname" in
*define*) ;;
*)
case "$phostname" in
")
@ if WHOAMI
case "$i_whoami" in

```

```
"$define")
$cat <<EOM
```

No hostname function--we'll use the whoami.h file, which has this line:

```
`grep sysname $usrinc/whoami.h`
```

EOM

```
;;
*) echo "There will be no way for $package to get your hostname." >&4;;
esac;;
@ else
echo "There will be no way for $package to get your hostname." >&4;;
@ end
*)
echo "I'll use 'popen('"'$aphostname"', "r")' to get your hostname." >&4
;;
esac;;
esac
@elsif MYHOSTNAME
case "$d_uname$d_gethname" in
*define*) ;;
*)
@ if WHOAMI
case "$i_whoami" in
"$define")
dflt=y
$cat
<<EOM
```

No hostname function--you can either use the whoami.h file, which has this line:

```
`grep sysname $usrinc/whoami.h`
```

or you can have the name we came up with earlier (\$myhostname) hardwired in.

EOM

```
rp="Use whoami.h to get hostname?"
./myread
case "$ans" in
n*) i_whoami="$undef";;
esac
;;
"$undef")
echo 'No whoami.h--hardwiring "'$myhostname"'.' >&4;;
esac;;
@ else
echo 'Hardwiring "'$myhostname"'.' >&4;;
@ end
```

```
esac
@end
case "$d_phostname" in
") d_phostname="$undef";;
esac
```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/d_gethname.U
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 2003 Jarkko Hietaniemi

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?MAKE:d_aintl: Inlibc

?MAKE: -pick add \$@ %<

?S:d_aintl:

?S: This variable conditionally defines the HAS_AINTL symbol, which

?S: indicates to the C program that the aintl() routine is available.

?S: If copysignl is also present we can emulate modfl.

?S:.

?C:HAS_AINTL:

?C: This symbol, if defined, indicates that the aintl routine is

?C: available. If copysignl is also present we can emulate modfl.

?C:.

?H:#\$d_aintl HAS_AINTL /**/

?H:.

?LINT:set d_aintl

: see if aintl exists

set aintl d_aintl

eval \$inlibc

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/perl/d_aintl.U
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: MailList.U 1 2006-08-24 12:32:52Z rmanfredi \$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic Licence,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic Licence; a copy of which may be found at the root
 ?RCS: of the source tree for dist 4.0.
 ?RCS:
 ?RCS: Original Author: Graham Stoney <greyham@research.canon.oz.au>
 ?RCS:
 ?RCS: \$Log: MailList.U,v \$
 ?RCS: Revision 3.0.1.1 1994/01/24 14:01:49 ram
 ?RCS: patch16: created
 ?RCS:
 ?RCS:
 ?X:
 ?X: This unit offers the user the option of subscribing to the mailing
 ?X: list. To force inclusion of this unit, you must add it's name to the
 ?X: dependancies on the MAKE line in your private copy of End.U.
 ?X: The address of the mailing list server must be set via a "list_request=..."
 ?X:
 entry in the .package file. This is usually done by running packinit and
 ?X: answering the proper questions.
 ?X:
 ?MAKE:MailList: cat mailer package Myread cf_name cf_email
 ?MAKE: -pick wipe \$@ %<
 ?T:list_request list_sub list_unsub list_name
 ?X:
 ?X: The cf_name dependency is used through list_sub when the mailing list
 ?X: manager happens to be listserv, whereas cf_email is used whith majordomo
 ?X: or when the mailing list request address is scanned by a human. Since
 ?X: they do not appear within the unit itself, we need a lint hint.
 ?X:
 ?LINT:use cf_name cf_email
 : offer to join the mailing list
 list_request='<\${list_request}>'
 list_sub="<\${list_sub}>"
 list_unsub="<\${list_unsub}>"
 list_name="<\${list_name}>"
 \$cat <<EOM

There is a mailing list for discussion about \$package and related issues.
 This is the preferred place to ask questions about the program and discuss
 modifications and additions with the author and other users. If you are able
 to send mail to the Internet, you
 are encouraged to subscribe. You need only
 ever subscribe once, and you can unsubscribe automatically at any time in the
 future. If you have already subscribed and you wish to unsubscribe now, you
 may do so by answering "unsubscribe". Answer "subscribe" to subscribe to the
 list.

EOM

rp="Subscribe to or unsubscribe from the \$list_name mailing list?"

```
dflt=neither
./myread
case "$ans" in
[sS]*) $cat <<EOM
```

You will be sent a message from the list server to let you know when your subscription has been successful and telling you how to submit articles and how to unsubscribe again when necessary. You may also unsubscribe by running this script again and asking it to do so for you.

```
EOM
echo "Sending mail to subscribe you to the $list_name list..." >&4
$mailler $list_request <<EOM >/dev/null 2>&1
Precedence: junk
To: $list_request
```

```
$list_sub
EOM
;;
[uU]*) echo "Sending mail to unsubscribe you from the $list_name list..." >&4
$mailler $list_request <<EOM >/dev/null 2>&1
Precedence: junk
To:
$list_request
```

```
$list_unsub
EOM
;;
esac
```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/MailList.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id$
?RCS:
?RCS: Copyright (c) 1999 Jarkko Hietaniemi
?RCS:
?RCS: You may distribute under the terms of either the GNU General Public
?RCS: License or the Artistic License, as specified in the README file.
?RCS:
?MAKE:d_quad quadtype uquadtype quadkind: \
longsize intsize d_longlong longlongsize d_int64_t \
Inhdr Setvar
?MAKE: -pick add $@ %<
?S:d_quad:
?S: This variable, if defined, tells that there's a 64-bit integer type,
```

```

?S: quadtype.
?S:.
?S:quadtype:
?S: This variable defines Quad_t to be something like long, int,
?S: long long, int64_t, or whatever type is used for 64-bit integers.
?S:.
?S:quadkind:
?S: This variable, if defined, encodes the type of a quad:
?S: 1 = int, 2 = long, 3 = long long, 4 = int64_t.
?S:.
?S:uquadtype:
?S: This variable defines Uquad_t to be something like unsigned long,
?S: unsigned int, unsigned long long, uint64_t, or whatever type is
?S: used for 64-bit integers.
?S:.
?C:HAS_QUAD:
?C: This
symbol, if defined, tells that there's a 64-bit integer type,
?C: Quad_t, and its unsigned counterpart, Uquad_t. QUADKIND will be one
?C: of QUAD_IS_INT, QUAD_IS_LONG, QUAD_IS_LONG_LONG, QUAD_IS_INT64_T,
?C: or QUAD_IS__INT64.
?C:.
?H:#$d_quad HAS_QUAD /**/
?H:%<:#ifdef HAS_QUAD
?H:%<:# define Quad_t $quadtype /**/
?H:%<:# define Uquad_t $uquadtype /**/
?H:%<:# define QUADKIND $quadkind /**/
?H:%<:# define QUAD_IS_INT 1
?H:%<:# define QUAD_IS_LONG 2
?H:%<:# define QUAD_IS_LONG_LONG 3
?H:%<:# define QUAD_IS_INT64_T 4
?H:%<:# define QUAD_IS__INT64 5
?H:%<:#endif
?H:.
?LINT:set quadtype
?LINT:set uquadtype
: Check if 64bit ints have a quad type
echo " "
echo "Checking which 64-bit integer type we could use..." >&4
?X: We prefer quad types in order of int, long, long long, int64_t.

case "$intsize" in
8) val=int
set quadtype
eval $setvar
val="unsigned int"
set uquadtype
eval $setvar

```

```

quadkind=1
;;
*) case "$longsize" in
8)
val=long
set quadtype
eval $setvar
val="unsigned long"
set uquadtype
eval $setvar
quadkind=2
;;
*) case "$d_longlong:$longlongsize" in
define:8)
val="long long"
set quadtype
eval $setvar
val="unsigned long long"
set uquadtype
eval $setvar
quadkind=3
;;
*) case "$d_int64_t" in
define)
val=int64_t
set quadtype
eval $setvar
val=uint64_t
set uquadtype
eval $setvar
quadkind=4
;;
esac
;;
esac
;;
esac
;;
esac
;;
esac

case "$quadtype" in
") echo "Alas, no 64-bit integer types in sight." >&4
d_quad="$undef"
;;
*) echo "We could use '$quadtype' for 64-bit integers." >&4
d_quad="$define"
;;
esac

```

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/a_dvisory/quatype.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_vprintf.U,v 3.0 1993/08/18 12:07:59 ram Exp \$

?RCS:

?RCS: Copyright (c) 1991-1993, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 3.0.

?RCS:

?RCS: \$Log: d_vprintf.U,v \$

?RCS: Revision 3.0 1993/08/18 12:07:59 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?MAKE:d_vprintf d_charvspr: Compile Guess cat Csym Setvar run rm_try \
i_stdlib i_unistd i_stdarg i_varargs

?MAKE: -pick add \$@ %<

?S:d_vprintf:

?S: This variable conditionally defines the HAS_VPRINTF symbol, which

?S: indicates to the C program that the vprintf() routine is available

?S: to printf with a pointer to an argument list.

?S:.

?S:d_charvspr:

?S: This

variable conditionally defines CHARVSPRINTF if this system

?S: has vsprintf returning type (char*). The trend seems to be to

?S: declare it as "int vsprintf()".

?S:.

?C:HAS_VPRINTF (VPRINTF):

?C: This symbol, if defined, indicates that the vprintf routine is available

?C: to printf with a pointer to an argument list. If unavailable, you

?C: may need to write your own, probably in terms of _doprnt().

?C:.

?C:USE_CHAR_VSPRINTF (CHARVSPRINTF):

?C: This symbol is defined if this system has vsprintf() returning type

?C: (char*). The trend seems to be to declare it as "int vsprintf()". It

?C: is up to the package author to declare vsprintf correctly based on the

?C: symbol.

?C:.

?H:#\$d_vprintf HAS_VPRINTF /**/

?H:#\$d_charvspr USE_CHAR_VSPRINTF /**/

?H:.

```

?T:val2
?F:!try
?LINT:set d_vprintf d_charvspr
: see if vprintf exists
echo " "
if set vprintf val -f d_vprintf; eval $csym; $val; then
echo 'vprintf() found.' >&4
val="$define"
$cat >try.c <<EOF
#$i_stdarg I_STDARG
/* Only one of these can be defined by i_varhrd */
#$i_varargs I_VARARGS

#$i_stdlib I_STDLIB
#$i_unistd I_UNISTD

#ifdef I_STDARG
# include <stdarg.h>
#else /* I_VARARGS */
# include <varargs.h>
#endif

#ifdef I_UNISTD
# include <unistd.h>
#endif

#ifdef I_STDLIB
# include <stdlib.h>
#endif

#include <stdio.h> /* vsprintf prototype */

#ifdef I_STDARG
void xxx(int n, ...)
{
    va_list args;
    char buf[10];
    va_start(args, n);
    exit(((unsigned long)vsprintf(buf,"%s",args) > 10L));
}
int main() { xxx(1, "foo"); }

#else /* I_VARARGS */

xxx(va_alist)
va_dcl
{
    va_list args;

```

```
char buf[10];
va_start(args);
exit((unsigned long)vsprintf(buf,"%s",args) > 10L);
}
int main() { xxx("foo"); }
```

#endif

EOF

```
set try
if eval $compile_ok; then
if $run ./try; then
echo "Your vsprintf() returns (int)." >&4
val2="$undef"
else
echo "Your vsprintf() returns (char*)." >&4
val2="$define"
fi
else
echo 'I am unable to compile the vsprintf() test program.' >&4
#
We shouldn't get here. If we do, assume the standard signature,
# not the old BSD one.
echo 'Guessing that vsprintf() returns (int).' >&4
val2="$undef"
fi
else
echo 'vprintf() NOT found.' >&4
val="$undef"
val2="$undef"
fi
$rm_try
set d_vprintf
eval $setvar
val=$val2
set d_charvspr
eval $setvar
```

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/compline/d_vprintf.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: i_sysparam.U 1 2006-08-24 12:32:52Z rmanfredi \$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic Licence,

?RCS: as specified in the README file that comes with the distribution.
 ?RCS: You may reuse parts of this distribution only within the terms of
 ?RCS: that same Artistic Licence; a copy of which may be found at the root
 ?RCS: of the source tree for dist 4.0.
 ?RCS:
 ?RCS: \$Log: i_sysparam.U,v \$
 ?RCS: Revision 3.0.1.1 1994/08/29 16:22:43 ram
 ?RCS: patch32: created
 ?RCS:
 ?MAKE:i_sysparam: Inhdr
 ?MAKE: -pick add \$@ %<
 ?S:i_sysparam:
 ?S: This variable conditionally defines the I_SYS_PARAM symbol, and indicates
 ?S: whether a C program should include <sys/param.h>.
 ?S:.
 ?C:I_SYS_PARAM:
 ?C: This symbol, if defined, indicates to the C program that it should
 ?C: include <sys/param.h>.
 ?C:.
 ?H:#\$i_sysparam I_SYS_PARAM /**/
 ?H:.
 ?LINT:set
 i_sysparam
 : see if this is a sys/param system
 set sys/param.h i_sysparam
 eval \$inhdr

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/i_sysparam.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$
 ?RCS:
 ?RCS: Copyright (c) 2001 Jarkko Hietaniemi
 ?RCS:
 ?RCS: You may distribute under the terms of either the GNU General Public
 ?RCS: License or the Artistic License, as specified in the README file.
 ?RCS:
 ?MAKE:run to from targetarch targetdir targetmkdir targethost targetport \
 usecrosscompile hostperl hostgenerate hostosname targetenv: \
 src test rm echo sed mkdir cp chmod make touch
 ?MAKE: -pick add \$@ %<
 ?Y:TOP
 ?S:usecrosscompile:
 ?S: This variable conditionally defines the USE_CROSS_COMPILE symbol,
 ?S: and indicates that Perl has been cross-compiled.
 ?S:.

?S:run:
?S: This variable contains the command used by Configure
?S: to copy and execute a cross-compiled executable in the
?S: target host. Useful and available only during Perl build.
?S: Empty string " if not cross-compiling.
?S:.
?S:from:
?S: This variable contains the command used by Configure
?S: to copy files from the target host. Useful
and available
?S: only during Perl build.
?S: The string ':' if not cross-compiling.
?S:.
?S:to:
?S: This variable contains the command used by Configure
?S: to copy to from the target host. Useful and available
?S: only during Perl build.
?S: The string ':' if not cross-compiling.
?S:.
?S:targetarch:
?S: If cross-compiling, this variable contains the target architecture.
?S: If not, this will be empty.
?S:.
?S:targetdir:
?S: This variable contains a path that will be created on the target
?S: host using targetmkdir, and then used to copy the cross-compiled
?S: executables to. Defaults to '/tmp' if not set.
?S:.
?S:targetmkdir:
?S: This variable contains the command used by Configure to create a
?S: new directory on the target host.
?S:.
?S:targethost:
?S: This variable contains the name of a separate host machine that
?S: can be used to run compiled test programs and perl tests on.
?S: Set to empty string if not in use.
?S:.
?S:targetport:
?S: This variable contains the number
of a network port to be used to
?S: connect to the host in targethost, if unset defaults to 22 for ssh.
?S:.
?S:hostperl:
?S: This variable contains the path to a miniperl binary that can be
?S: run on the host OS when cross-compiling. Useful and available only
?S: during Perl build.
?S: Empty string " if not cross-compiling.
?S:.

?S:hostgenerate:
 ?S: This variable contains the path to a generate_uudmap binary that
 ?S: can be run on the host OS when cross-compiling. Useful and
 ?S: available only during Perl build.
 ?S: Empty string " if not cross-compiling.
 ?S:.

?S:hostosname:
 ?S: This variable contains the original value of '\$^O' for hostperl
 ?S: when cross-compiling. This is useful to pick the proper tools
 ?S: when running build code in the host.
 ?S: Empty string " if not cross-compiling.
 ?S:.

?S:targetenv:
 ?S: If cross-compiling, this variable can be used to modify the
 ?S: environment on the target system.
 ?S: However, how and where it's used, and even if it's used at all, is
 ?S: entirely
 ?S: dependent on both the transport mechanism (targetrun) and
 ?S: what the target system is. Unless the relevant documentation says
 ?S: otherwise, it is generally not useful.
 ?S:.

?C:USE_CROSS_COMPILE:
 ?C: This symbol, if defined, indicates that Perl is being cross-compiled.
 ?C:.

?C:PERL_TARGETARCH:
 ?C: This symbol, if defined, indicates the target architecture
 ?C: Perl has been cross-compiled to. Undefined if not a cross-compile.
 ?C:.

?H:?%<:#ifndef USE_CROSS_COMPILE
 ?H:?%<:#\$usecrosscompile USE_CROSS_COMPILE /**/
 ?H:?%<:#define PERL_TARGETARCH "\$targetarch" /**/
 ?H:?%<:#endif
 ?H:.

?D:targetenv="
 ?D:targethost="
 ?D:targetmkdir="
 ?T:croak pwd exe f q cwd file xxx env
 ?LINT:extern usecrosscompile
 ?LINT:extern cc
 ?LINT:extern ushrc
 ?LINT:change ar
 ?LINT:change nm
 ?LINT:change ranlib
 ?LINT:change src
 ?LINT:extern targetenv
 ?LINT:extern targetport
 ?LINT:extern targetdir
 ?LINT:extern targetuser

```

?LINT:change targetuser
?LINT:extern targetrun
?LINT:extern targetfrom
?LINT:extern
targetto
?LINT:change targetrun
?LINT:change targetfrom
?LINT:change targetto
?LINT:extern incpth
?LINT:extern libpth
?LINT:extern locincpth
?LINT:extern loclibpth
?LINT:change locincpth
?LINT:change loclibpth
?LINT:extern hostperl
?LINT:extern hostgenerate
?LINT:extern before_host
?LINT:change before_host
?LINT:extern hostosname
?LINT:extern multiarch
: Check for Cross-Compilation
?X: targethost and targetenv mainly set to allow ?S: documentation
?X:otherwise it could have been declared extern
if $test "X$targethost" = "X"; then
    targethost=""
fi
if $test "X$targetenv" = "X"; then
    targetenv=""
fi
case "$usecrosscompile" in
$define|true|[yY]*)
    $echo "Cross-compiling..."
    croak="
case "$cc" in
*-gcc*|*-g++*) # A cross-compiling gcc, probably.
    # arm-linux-androideabi-gcc -> arm-linux-androideabi
    # x86_64-w64-mingw32-gcc.exe -> x86_64-w64-mingw32
    targetarch=`$echo $cc|$sed 's/-g[c+][c+].*$/^'
    ar=`$echo $cc|$sed 's/-g[c+][c+]/-ar/^'
    # leave out ld,
choosing it is more complex
    nm=`$echo $cc|$sed 's/-g[c+][c+]/-nm/^'
    ranlib=`$echo $cc|$sed 's/-g[c+][c+]/-ranlib/^'
    # We are in a weird spot. Just before us, some values
    # were 'saved', to be restored after the hints are
    # run. This means that the changes we made to ar,
    # nm and ranlib will get reverted.
    # To avoid that, we hijack the saving mechanism and

```

```

    # have it save our new values.
    for file in ar nm ranlib; do
eval xxx=\$$file
eval $file=$xxx$_exe
eval _$file=$xxx
    done
;;
esac
case "$targetarch" in
") echo "Targetarch not defined." >&4; croak=y ;;
*) echo "Using targetarch $targetarch." >&4 ;;
esac
case "$targethost" in
") echo "Targethost not defined." >&4; croak=n ;;
*) echo "Using targethost $targethost." >&4
esac
locincpth=' '
loclibpth=' '
case "$croak" in
y) echo "Cannot continue, aborting." >&4; exit 1 ;;
esac
: compile a host miniperl and generate_uudmap, unless we got passed them
if
$test "X$hostperl" = X; then
    echo "Building host miniperl and generate_uudmap binaries" >&4
    before_host=`pwd`
    cd ..
    cd $src
    src=`pwd`
    rm -rf $src/host
    mkdir $src/host
    cd $src/host
    $src/Configure -des -Dusedevel -Dmksymlinks
    $make miniperl
    case "$hostgenerate" in
") $make generate_uudmap
        hostgenerate=$src/host/generate_uudmap
        ;;
"$undef") hostgenerate="
        ;;
esac
    hostperl=$src/host/miniperl
    cd $before_host
fi
hostosname=`$hostperl -le 'print $^O`
;;
*)
    usecrosscompile="$undef"

```

```

;;
esac

: Define -Dtargethost=somecomputer to run compiled tests on another machine
case "$targethost" in
  *) echo "Checking for cross-compile" >&4
     case "$usecrosscompile$multiarch" in
       *$define*) echo "Skipping the try tests in the rest of Configure as no targethost was defined when cross-
compiling" >&4
         if [ -f Makefile ]; then
           echo
           " "
           echo "Now you must ensure config.sh, config.h and the generated headers exist and run a $make."
           else
             echo "Configure done."
           fi
         exit 0
       ;;
       *) echo "No targethost for running compiler tests against defined, running locally" >&4
          run="
to=:
from=:
";
     esac
;;
*) echo "Using targethost $targethost." >&4
   case "$src" in
     /*) run=$src/Cross/run
        targetmkdir=$src/Cross/mkdir
        to=$src/Cross/to
        from=$src/Cross/from
        ;;
     *) pwd=`$test -f ../Configure & cd ..; pwd`
        run=$pwd/Cross/run
        targetmkdir=$pwd/Cross/mkdir
        to=$pwd/Cross/to
        from=$pwd/Cross/from
        ;;
   esac
case "$targetrun" in
  *) targetrun=ssh ;;
esac
case "$targetto" in
  *) targetto=scp ;;
esac
case "$targetfrom" in
  *) targetfrom=scp ;;
esac

```

```

run=$run-$targetrun
to=$to-$targetto
from=$from-$targetfrom
case "$targetdir" in
") targetdir=/tmp
    echo "Guessing targetdir $targetdir."
>&4
    ;;
esac
case "$targetuser" in
") targetuser=root
    echo "Guessing targetuser $targetuser." >&4
    ;;
esac
case "$targetport" in
") targetport=22
    echo "Guessing targetport $targetport." >&4
    ;;
esac
case "$targetfrom" in
scp) q=-q ;;
*) q=" " ;;
esac
case "$targetrun" in
ssh|rsh)
    cat >$run <<EOF
#!/bin/sh
env="
case "\$1" in
-cwd)
    shift
    cwd=\$1
    shift
    ;;
esac
case "\$1" in
-env)
    shift
    env=\$1
    shift
    ;;
esac
case "\$cwd" in
") cwd=$targetdir ;;
esac
exe=\$1
shift
$to \$exe

```

```
$targetrun -p $targetport -l $targetuser $targethost "cd \${cwd} && \${env} \${exe} \${@"
```

```
EOF
```

```
;;
```

```
adb)
```

```
  $touch $run
```

```
;;
```

```
*) echo "Unknown targetrun '$targetrun'" >&4
```

```
  exit 1
```

```
;;
```

```
esac
```

```
case "$targetmkdir" in
```

```
*/Cross/mkdir)
```

```
  cat >$targetmkdir <<EOF
```

```
#!/bin/sh
```

```
$targetrun -p $targetport -l $targetuser $targethost "mkdir -p \${@"
```

```
EOF
```

```
  $chmod a+rx $targetmkdir
```

```
;;
```

```
*) echo "Unknown targetmkdir '$targetmkdir'" >&4
```

```
  exit 1
```

```
;;
```

```
esac
```

```
case
```

```
"$targetto" in
```

```
scp|rcp)
```

```
  cat >$to <<EOF
```

```
#!/bin/sh
```

```
for f in \${@"
```

```
do
```

```
  case "\${f}" in
```

```
/*)
```

```
  $targetmkdir \`${dirname} \${f}`
```

```
  $targetto -P $targetport -r $q \${f} $targetuser@$targethost:\${f} 2>/dev/null || exit 1
```

```
  ;;
```

```
*)
```

```
  $targetmkdir $targetdir/\`${dirname} \${f}`
```

```
  $targetto -P $targetport -r $q \${f} $targetuser@$targethost:$targetdir/\${f} 2>/dev/null || exit 1
```

```
  ;;
```

```
esac
```

```
done
```

```
exit 0
```

```
EOF
```

```
;;
```

```
cp) cat >$to <<EOF
```

```
#!/bin/sh
```

```
for f in \${@"
```

```
do
```

```
  case "\${f}" in
```

```

/*)
  $mkdir -p $targetdir/\dirname \$f\
  $cp \$f $targetdir/\$f || exit 1
  ;;
*)
  $targetmkdir $targetdir/\dirname \$f\
  $cp \$f $targetdir/\$f || exit 1
  ;;
esac
done
exit 0
EOF
  ;;
*) echo "Unknown targetto '$targetto'" >&4
  exit 1
  ;;
esac
case "$targetfrom" in
scp|rcp)
  cat >$from <<EOF
#!/bin/sh
for f in \$@
do
  $rm -f \$f
  $targetfrom -P $targetport $q $targetuser@$targethost:$targetdir/\$f . || exit 1
done
exit 0
EOF
  ;;
cp) cat >$from <<EOF
#!/bin/sh
for
f in \$@
do
  $rm -f \$f
  cp $targetdir/\$f . || exit 1
done
exit 0
EOF
  ;;
*) echo "Unknown targetfrom '$targetfrom'" >&4
  exit 1
  ;;
esac
if $test ! -f $run; then
  echo "Target 'run' script '$run' not found." >&4
else
  $chmod a+rx $run

```

```

fi
if $test ! -f $to; then
    echo "Target 'to' script '$to' not found." >&4
else
    $chmod a+rx $to
fi
if $test ! -f $from; then
    echo "Target 'from' script '$from' not found." >&4
else
    $chmod a+rx $from
fi
if $test ! -f $run -o ! -f $to -o ! -f $from; then
    exit 1
fi
cat >&4 <<EOF

```

Using '\$run' for remote execution,
and '\$from' and '\$to'
for remote file transfer.

```

EOF
;;
*) run="
to=:
from=:
usecrosscompile="$undef"
targetarch="
;;
esac

```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/perl/Cross.U
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: otherlibdirs.U,v 1.1 1999/07/08 18:32:57 doughera Exp doughera \$

?RCS:

?RCS: Copyright (c) 1999-2000, Andy Dougherty

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 3.0.

?RCS:

?RCS: \$Log: otherlibdirs.U,v \$

?RCS: Revision 1.1 1999/07/08 18:32:57 doughera

?RCS: Initial revision

?RCS:

?RCS: Revision 1.1 1999/07/08 18:20:26 doughera

```

?RCS: Initial revision
?RCS:
?RCS:
?MAKE:otherlibdirs d_perl_otherlibdirs: Myread cat sitelib sitearch \
vendorarch vendorlib Setvar
?MAKE: -pick add $@ %<
?Y:TOP
?S:otherlibdirs:
?S: This variable contains a colon-separated set of paths for the perl
?S: binary to search for additional library files
or modules.
?S: These directories will be tacked to the end of @INC.
?S: Perl will automatically search below each path for version-
?S: and architecture-specific directories. See inc_version_list
?S: for more details.
?S: A value of '' means 'none' and is used to preserve this value
?S: for the next run through Configure.
?S:.
?S:d_perl_otherlibdirs:
?S: This variable conditionally defines PERL_OTHERLIBDIRS, which
?S: contains a colon-separated set of paths for the perl binary to
?S: include in @INC. See also otherlibdirs.
?S:.
?C:PERL_OTHERLIBDIRS:
?C: This variable contains a colon-separated set of paths for the perl
?C: binary to search for additional library files or modules.
?C: These directories will be tacked to the end of @INC.
?C: Perl will automatically search below each path for version-
?C: and architecture-specific directories. See PERL_INC_VERSION_LIST
?C: for more details.
?C:.
?H:#$d_perl_otherlibdirs PERL_OTHERLIBDIRS "$otherlibdirs" /**/
?H:.
?LINT: set d_perl_otherlibdirs
:
Final catch-all directories to search
$cat <<EOM

```

Lastly, you can have perl look in other directories for extensions and modules in addition to those already specified.

These directories will be searched after

```
$sitearch
```

```
$sitelib
```

```
EOM
```

```
test X"$vendorlib" != "X" && echo ' ' $vendorlib
```

```
test X"$vendorarch" != "X" && echo ' ' $vendorarch
```

```
echo ' '
```

```
case "$otherlibdirs" in
```

```
"|') dflt='none' ;;
*) dflt="$otherlibdirs" ;;
esac
$cat <<EOM
```

Enter a colon-separated set of extra paths to include in perl's @INC search path, or enter 'none' for no extra paths.

EOM

```
rp='Colon-separated list of additional directories for perl to search?'
```

```
./myread
case "$ans" in
'|'|none) otherlibdirs=' ' ;;
*) otherlibdirs="$ans" ;;
esac
case "$otherlibdirs" in
'|') val=$undef ;;
*) val=$define ;;
esac
set d_perl_otherlibdirs
eval $setvar
```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/installdirs/otherlibdirs.U
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: End.U,v 3.0 1993/08/18 12:04:51 ram Exp \$

?RCS:

?RCS: Copyright (c) 1991-1993, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 3.0.

?RCS:

?RCS: \$Log: End.U,v \$

?RCS: Revision 3.0 1993/08/18 12:04:51 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?X:

?X: This unit serves as the goal which forces make to choose all the units that

?X: ask questions. The \$W on the ?MAKE: line is the list of all symbols wanted.

?X: To force any unit to be included, copy this unit to your private U directory

?X: and add the name of the unit desired to the ?MAKE: dependency line.

?X:

?MAKE:End perllibs: \$W cppstdin gzip zip

```

libs usedl osname osvers
?MAKE: -pick add $@ %<
?S:perllibs:
?S: The list of libraries needed by Perl only (any libraries needed
?S: by extensions only will be dropped, if using dynamic loading).
?S:.
?INIT:perllibs="
?LINT:use $W
?LINT:use gzip zip
?LINT:change cppstdinc
: Remove libraries needed only for extensions
: The appropriate ext/Foo/Makefile.PL will add them back in, if necessary.
: The exception is SunOS 4.x, which needs them.
case "${osname}X${osvers}" in
sunos*4*)
    perllibs="$libs"
    ;;
*) case "$usedl" in
    $define|true|[yY]*)
        set X `echo " $libs " | sed -e 's@ -lndbm @ @' -e 's@ -lgdbm @ @' -e 's@ -lgdbm_compat @ @' -e 's@ -ldb @ @'
        shift
        perllibs="$*"
        ;;
    *) perllibs="$libs"
        ;;
    esac
    ;;
esac

```

?X: If the user has the cppstdinc wrapper, perl.c will try to call
?X: CPPSTDINC, but that will point to a location in the build
?X: directory, not the installed version!. Here, we'll just strip the
?X: name down to 'cppstdinc',
and rely on the fact that perl.c will
?X: then call SCRIPTDIR/cppstdinc, but local things like 'make depend'
?X: will continue to work.

: Remove build directory name from cppstdinc so it can be used from
: either the present location or the final installed location.

```
echo " "
```

: Get out of the UU directory to get correct path name.

```
cd ..
```

```
case "$cppstdinc" in
```

```
`pwd`/cppstdinc)
```

```
echo "Stripping down cppstdinc path name"
```

```
cppstdinc=cppstdinc
```

```
;;
```

```
esac
```

cd UU

: end of configuration questions

echo " "

echo "End of configuration questions."

echo " "

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/End.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1998 Jarkko Hietaniemi

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?X: This unit generates a \$hasfield string that is used internally

?X: by Configure to check if this system has a field for a

?X: particular struct (of if this system has a particular struct!)

?X:

?X: To use it, say something like:

?X: set d_statblocks stat st_blocks i_sysstat sys/stat.h

?X: eval \$hasfield

?X: Or, for more complicated sets of headers, do something like

?X: hdrs="\$define sys/foo.h

?X: \$i_sysbar sys/bar.h

?X: \$i_syszot sys/zot.h

?X: \$i_zappa zappa.h"

?X: set d_statblocks stat st_blocks \$hdrs

?X: eval \$hasfield

?X:

?MAKE:Hasfield: Setvar rm_try test Compile

?MAKE: -pick add \$@ %<

?T:varname struct field

?V:hasfield

: Define hasfield macro for Configure internal use

hasfield='varname=\$1;

struct=\$2; field=\$3; shift; shift; shift;

while \$test \$# -ge 2; do

case "\$1" in

\$define) echo "#include <\$2>";;

esac ;

shift 2;

done > try.c;

echo "int main () { struct \$struct foo; char* bar; bar = (char*)foo.\$field; }" >> try.c;

```
set try;
if eval $compile; then
  val="$define";
else
  val="$undef";
fi;
set $varname;
eval $setvar;
$rm_try'
```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/protos/Hasfield.U
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_setreuid.U 1 2006-08-24 12:32:52Z rmanfredi \$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic Licence,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic Licence; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: d_setreuid.U,v \$

?RCS: Revision 3.0 1993/08/18 12:07:13 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?MAKE:d_setreuid d_setresuid: Inlibc

?MAKE: -pick add \$@ %<

?S:d_setreuid:

?S: This variable conditionally defines HAS_SETREUID if setreuid() is

?S: available to change the real and effective uid of the current

?S: process.

?S:.

?S:d_setresuid:

?S: This variable conditionally defines HAS_SETREUID if setresuid() is

?S: available to change

the real, effective and saved uid of the current

?S: process.

?S:.

?C:HAS_SETREUID (SETREUID):

?C: This symbol, if defined, indicates that the setreuid routine is

?C: available to change the real and effective uid of the current

?C: process.

?C:.

?C:HAS_SETRESUID (SETRESUID):

?C: This symbol, if defined, indicates that the setresuid routine is
?C: available to change the real, effective and saved uid of the current
?C: process.
?C:.
?H:#\$d_setreuid HAS_SETREUID /**/
?H:#\$d_setresuid HAS_SETRESUID /**/
?H:.
?LINT:set d_setreuid d_setresuid
: see if setreuid exists
set setreuid d_setreuid
eval \$inlibc
set setresuid d_setresuid
eval \$inlibc

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/d_setreuid.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: package.U,v \$

?RCS: Revision 3.0.1.3 1994/10/29 16:27:21 ram

?RCS: patch36: beware of non-ascii character sets when translating case

?RCS:

?RCS: Revision 3.0.1.2 1993/11/10 17:37:02 ram

?RCS: patch14: skip definition of spackage if not otherwise used

?RCS:

?RCS: Revision 3.0.1.1 1993/09/13 16:11:10 ram

?RCS: patch10: added package, suitable for starting sentences

?RCS:

?RCS: Revision 3.0 1993/08/18 12:09:28 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?MAKE:package spackage:

Nothing

?MAKE: -pick wipe \$@ %<

?S:package:

?S: This variable contains the name of the package being constructed.

?S: It is primarily intended for the use of later Configure units.

?S:
?S:spackage:
?S: This variable contains the name of the package being constructed,
?S: with the first letter uppercased, i.e. suitable for starting
?S: sentences.
?S:
?C:PACKAGE:
?C: This variable contains the name of the package being built.
?C:
?H:#define PACKAGE "\$package"
?H:
?T:first last
: set package name
package='<PACKAGENAME>'
@if spackage
first=`echo \$package | sed -e 's/^(.).*\1/'`
last=`echo \$package | sed -e 's/^(.*)\1/'`
?X:
?X: So early in the Configure script, we don't have ./tr set up and can't
?X: include Tr in our dependency or that would create a cycle. Therefore,
?X: we have to somehow duplicate the work done in Tr. That's life.
?X:
case "`echo AbyZ | tr '[:lower:]' '[:upper:]' 2>/dev/null`" in
ABYZ) spackage=`echo \$first | tr '[:lower:]' '[:upper:]'`\$last;;
*) spackage=`echo
\$first | tr '[a-z]' '[A-Z]'`\$last;;
esac
@end

Found in path(s):
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/package.U
No license file was found, but licenses were detected in source scan.

?RCS: \$Id: Nothing.U 1 2006-08-24 12:32:52Z rmanfredi \$
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: \$Log: Nothing.U,v \$
?RCS: Revision 3.0 1993/08/18 12:05:09 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:

?X:
?X: The purpose of this file is to supply an empty target for the private
?X: Makefile built by metaconfig to order the units.
?X:
?MAKE:Nothing: Head

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/Nothing.U

No license file was found, but licenses were detected in source scan.

?RCS: Copyright (c) 1996, Andy Dougherty

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?MAKE:perladmin: cf_email Oldconfig Myread cat

?MAKE: -pick add \$@ %<

?Y:TOP

?S:perladmin:

?S: Electronic mail address of the perl5 administrator.

?S:.

: Ask e-mail of administrator

\$cat <<EOM

If you or somebody else will be maintaining perl at your site, please fill in the correct e-mail address here so that they may be contacted if necessary. Currently, the "perlbug" program included with perl will send mail to this address in addition to perlbug@perl.org. You may enter "none" for no administrator.

EOM

```
case "$perladmin" in
```

```
) dflt="$cf_email";;
```

```
*) dflt="$perladmin";;
```

```
esac
```

```
rp='Perl administrator e-mail address'
```

```
./myread
```

```
perladmin="$ans"
```

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/perladmin.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1999 Jarkko Hietaniemi

?RCS:
 ?RCS: You may distribute under the terms of either the GNU General Public
 ?RCS: License or the Artistic License, as specified in the README file.
 ?RCS:
 ?MAKE:d_rand_r: Inlibc
 ?MAKE: -pick add \$@ %<
 ?S:d_rand_r:
 ?S: This variable conditionally defines the HAS_RANDOM_R symbol,
 ?S: which indicates to the C program that the rand_r()
 ?S: routine is available.
 ?S:.
 ?C:HAS_RANDOM_R:
 ?C: This symbol, if defined, indicates that the rand_r routine
 ?C: is available to rand re-entrantly.
 ?C:.
 ?H:#\$d_rand_r HAS_RANDOM_R /**/
 ?H:.
 ?LINT:set d_rand_r
 : see if rand_r exists
 set rand_r d_rand_r
 eval \$inlibc

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
 debian-perl-5.26.1/U/threads/d_rand_r.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: randfunc.U,v 3.0 1993/08/18 12:09:39 ram Exp \$
 ?RCS:
 ?RCS: Copyright (c) 1991-1993, Raphael Manfredi
 ?RCS:
 ?RCS: You may redistribute only under the terms of the Artistic License,
 ?RCS: as specified in the README file that comes with the distribution.
 ?RCS: You may reuse parts of this distribution only within the terms of
 ?RCS: that same Artistic License; a copy of which may be found at the root
 ?RCS: of the source tree for dist 3.0.
 ?RCS:
 ?RCS: \$Log: randfunc.U,v \$
 ?RCS: Revision 3.0 1993/08/18 12:09:39 ram
 ?RCS: Baseline for dist 3.0 netwide release.
 ?RCS:
 ?X:
 ?X: This is the new unit that should be used when random
 ?X: functions are to be used. It thus makes randbits.U obsolete.
 ?X:
 ?X: This unit gives a simple #define for Drand01, which produces
 ?X: doubles in the range [0,1) using the "best" random number
 ?X: generator available. The source should just call Drand01

?X: and not worry about the underlying implementation.

?X: Andy Dougherty July 1998

?X:

?MAKE:randfunc drand01 seedfunc randbits randseedtype: \
 Compile Myread Csym cflags

?MAKE: -pick add \$@ %<

?S:randfunc:

?S: Indicates the name of the random number function to use.

?S: Values include drand48, random, and rand. In C programs,

?S: the 'Drand01' macro is defined to generate uniformly distributed

?S: random numbers over the range [0., 1.[(see drand01 and nrand).

?S:.

?S:drand01:

?S: Indicates the macro to be used to generate normalized

?S: random numbers. Uses randfunc, often divided by

?S: (double) (((unsigned long) 1 << randbits)) in order to

?S: normalize the result.

?S: In C programs, the macro 'Drand01' is mapped to drand01.

?S:.

?S:randseedtype:

?S: Indicates the type of the argument of the seedfunc.

?S:.

?S:seedfunc:

?S: Indicates the random number generating seed function.

?S: Values include srand48, srandom, and srand.

?S:.

?S:randbits:

?S: Indicates how many bits are produced by the function used to

?S: generate

normalized random numbers.

?S:.

?C:RANDFUNC:

?C: This symbol defines the random function used to define Drand01().

?C:.

?C:Drand01:

?C: This macro is to be used to generate uniformly distributed

?C: random numbers over the range [0., 1.[. You may have to supply

?C: an 'extern double drand48();' in your program since SunOS 4.1.3

?C: doesn't provide you with anything relevant in its headers.

?C: See HAS_DRAND48_PROTO.

?C:.

?C:Rand_seed_t:

?C: This symbol defines the type of the argument of the

?C: random seed function.

?C:.

?C:seedDrand01:

?C: This symbol defines the macro to be used in seeding the

?C: random number generator (see Drand01).

?C:.

?C:RANDBITS:

?C: This symbol indicates how many bits are produced by the

?C: function used to generate normalized random numbers.

?C: Values include 15, 16, 31, and 48.

?C:.

```
?H:#define RANDFUNC $randfunc /**/
```

```
?H:#define Drand01() $drand01 /**/
```

```
?H:#define Rand_seed_t $randseedtype /**/
```

```
?H:#define seedDrand01(x) $seedfunc((Rand_seed_t)x) /**/
```

```
?H:#define
```

```
  RANDBITS $randbits /**/
```

```
?H:.
```

```
?LINT:change ccflags
```

```
?LINT:unclosed $randbits))"
```

```
: How can we generate normalized random numbers ?
```

```
echo " "
```

```
echo "Using our internal random number implementation..." >&4
```

```
case "$ccflags" in
```

```
*-Dmy_rand=|*-Dmy_srand=*)
```

```
  echo "Removing obsolete -Dmy_rand, -Dmy_srand, and -Drandbits from ccflags." >&4
```

```
  ccflags="`echo $ccflags | sed -e 's/-Dmy_rand=random/ /'"`
```

```
  ccflags="`echo $ccflags | sed -e 's/-Dmy_srand=srandom/ /'"`
```

```
  ccflags="`echo $ccflags | sed -e 's/-Drandbits=[0-9][0-9]*/ /'"`
```

```
;;
```

```
esac
```

```
randfunc=Perl_drand48
```

```
drand01="Perl_drand48()"
```

```
seedfunc="Perl_drand48_init"
```

```
randbits=48
```

```
randseedtype=U32
```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/compline/randfunc.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: ccflags.U,v 3.0.1.9 1997/02/28 15:27:07 ram Exp $
```

```
?RCS:
```

```
?RCS: Copyright (c) 1991-1993, Raphael Manfredi
```

```
?RCS:
```

```
?RCS: You may redistribute only under the terms of the Artistic License,
```

```
?RCS: as specified in the README file that comes with the distribution.
```

```
?RCS: You may reuse parts of this distribution only within the terms of
```

```
?RCS: that same Artistic License; a copy of which may be found at the root
```

?RCS: of the source tree for dist 3.0.

?RCS:

?RCS: \$Log: ccflags.U,v \$

?RCS: Revision 3.0.1.9 1997/02/28 15:27:07 ram

?RCS: patch61: removed support for NO_PROTOTYPE detection on SCO

?RCS: patch61: new locincpth variable

?RCS: patch61: added info on the "additional ld flags" question

?RCS:

?RCS: Revision 3.0.1.8 1995/07/25 13:48:54 ram

?RCS: patch56: re-arranged compile line to include ldflags before objects

?RCS:

?RCS: Revision 3.0.1.7 1995/05/12 12:08:33 ram

?RCS: patch54: now checks for cc/ccflags/ldflags coherency

?RCS:

?RCS: Revision 3.0.1.6 1994/10/29 16:07:02 ram

?RCS: patch36: gcc versioning no longer relies on the C compiler's name

?RCS: patch36: simplified check for gcc version checking (ADO)

?RCS:

?RCS: Revision 3.0.1.5 1994/08/29 16:06:35 ram

?RCS: patch32: propagate -posix flag from ccflags to ldflags

?RCS:

?RCS: Revision 3.0.1.4 1994/05/06 14:28:45 ram

?RCS: patch23: -fpcc-struct-return only needed in gcc 1.x (ADO)

?RCS: patch23: cppflags now computed on an option-by-option basis

?RCS: patch23: magically added cc flags now only done the first time

?RCS:

?RCS: Revision 3.0.1.3 1993/09/13 15:58:29 ram

?RCS: patch10: explicitly mention -DDEBUG just in case they need it (WAD)

?RCS: patch10: removed all the "tans" variable usage (WAD)

?RCS:

?RCS: Revision 3.0.1.2 1993/08/27 14:39:38 ram

?RCS: patch7: added support for OSF/1 machines

?RCS:

?RCS: Revision 3.0.1.1 1993/08/25 14:00:24 ram

?RCS: patch6: added defaults for cppflags, ccflags and ldflags

?RCS:

?RCS:

Revision 3.0 1993/08/18 12:05:31 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?MAKE:ccflags ldflags lkflags cppflags optimize locincpth: test cat osname \
 Myread Guess Options Oldconfig +gccversion mips_type +usrinc \
 package contains rm +cc cppstdin cppminus cprun cpplast libpth \
 libs loclibpth hint usesocks sh run rm_try sysroot

?MAKE: -pick add \$@ %<

?S:ccflags:

?S: This variable contains any additional C compiler flags desired by

?S: the user. It is up to the Makefile to use this.

?S:.

?S:cppflags:

?S: This variable holds the flags that will be passed to the C pre-processor. It is up to the Makefile to use it.

?S:.

?S:optimize:

?S: This variable contains any optimizer/debugger flag that should be used.

?S: It is up to the Makefile to use it.

?S:.

?S:ldflags:

?S: This variable contains any additional C loader flags desired by the user. It is up to the Makefile to use this.

?S:.

?S:lkflags:

?S: This variable contains any additional C partial linker flags desired by the user. It is up to the Makefile to use this.

?S:.

?S:locincpth:

?S: This variable contains a list of additional directories to be searched by the compiler. The appropriate '-I' directives will be added to ccflags. This is intended to simplify setting local directories from the Configure command line.

?S: It's not much, but it parallels the loclibpth stuff in libpth.U.

?S:.

?T:inctest thisincl xxx inclwanted ftry previous thislibdir

?T:EBUGGING DEBUGGING

?T:check flag callback checkccflag

?F:!cpp.c !gcctest !try

?D:cppflags=""

?D:ccflags=""

?D:ldflags=""

?D:optimize=""

?LINT:extern _sysroot

?INIT:: Possible local include directories to search.

?INIT:: Set locincpth to "" in a hint file to defeat local include searches.

?INIT:locincpth="/usr/local/include /opt/local/include /usr/gnu/include"

?INIT:locincpth="\$locincpth /opt/gnu/include /usr/GNU/include /opt/GNU/include"

?INIT::

?INIT:: no include file wanted by default

?INIT:inclwanted=""

?INIT:

?INIT::

Enable -DEBUGGING and -DDEBUGGING from the command line

?INIT:EBUGGING=""

?INIT:DEBUGGING=""

?INIT:

```

: determine optimization, if desired, or use for debug flag also
?X: Allow for Configure -Uoptimize -- it's not strictly sensible, but
?X: it has happened and we know what they mean. AD 2/16/98
case "$optimize" in
'|$undef) dflt='none';;
") dflt='-O';;
*) dflt="$optimize";;
esac
$cat <<EOH

```

By default, \$package compiles with the -O flag to use the optimizer. Alternately, you might want to use the symbolic debugger, which uses the -g flag (on traditional Unix systems). Either flag can be specified here. To use neither flag, specify the word "none".

```

EOH
rp="What optimizer/debugger flag should be used?"
./myread
optimize="$ans"
case "$optimize" in
'none') optimize=" ";;
esac

```

```

: Check what DEBUGGING is required from the command line
: -DEBUGGING or -DDEBUGGING or
: -DEBUGGING=both = -g + -DDEBUGGING
: -DEBUGGING=-g or -Doptimize=-g = -g
: -DEBUGGING=none or -UDEBUGGING =
:
: -DEBUGGING=old or -DEBUGGING=default = ? $optimize
case "$DEBUGGING" in
") ;;
*) DEBUGGING=$DEBUGGING ;;
esac

```

```

case "$DEBUGGING" in
-g|both|$define)
  case "$optimize" in
  *-g*) ;;
  *) optimize="$optimize -g" ;;
  esac ;;
none|$undef)
  case "$optimize" in
  *-g*) set `echo "X $optimize " | sed 's/ -g / /'`
  shift
  optimize="$*"
  ;;
  esac ;;

```

```
esac
```

```
dflt=""  
case "$DEBUGGING" in  
both|$define) dflt='-DDEBUGGING'  
esac
```

```
: argument order is deliberate, as the flag will start with - which set could  
: think is an option  
checkccflag='check=$1; flag=$2; callback=$3;  
echo " ";  
echo "Checking if your compiler accepts $flag" 2>&1;  
[ "X$sysroot" != "X" ] && echo "For sysroot = $sysroot";  
echo "int main(void) { return 0; }" > gcctest.c;  
if $cc $_sysroot -O2 $flag -o gcctest gcctest.c 2>gcctest.out && $run ./gcctest; then  
    echo "Yes, it does." 2>&1;  
    if $test -s gcctest.out ; then  
        echo "But your platform does not like it:";  
        cat gcctest.out;  
    else  
case "$ccflags"  
in  
*$check*)  
    echo "Leaving current flags $ccflags alone." 2>&1  
    ;;  
*) dflt="$dflt $flag";  
    eval $callback  
    ;;  
esac  
fi  
else  
    echo "Nope, it does not, but that is ok." 2>&1;  
fi  
,
```

```
: We will not override a previous value, but we might want to
```

```
: augment a hint file  
case "$hint" in  
default|recommended)  
case "$gccversion" in  
1*) dflt="$dflt -fpcc-struct-return" ;;  
esac  
case "$optimize:$DEBUGGING" in  
*-g*:old) dflt="$dflt -DDEBUGGING";;  
esac  
?X: check for POSIXized ISC  
case "$gccversion" in  
2*) if $test -d /etc/conf/kconfig.d &&
```

```

$contains _POSIX_VERSION $usrinc/sys/unistd.h >/dev/null 2>&1
then
# Interactive Systems (ISC) POSIX mode.
dflt="$dflt -posix"
fi
;;
esac

```

?X: If the user has gcc-2.95 or greater, try adding -fno-strict-alias.
?X: Since the gcc "version" can be non-numeric, e.g.
?X: "2.95.1 19990809 (prerelease)" , we'll do the test on any version
?X: greater than 2.8.

?X: --Andy Dougherty 27 Aug 1999

```

case "$gccversion" in
1*) ;;
2.[0-8]*)
;;
?*) set strict-aliasing -fno-strict-aliasing
eval $checkccflag
;;
esac

```

?X: HMB 200405

?X: -pipe has shown a compile time speedup of about 40% on Linux and HP-UX

?X: and also worked on cygwin-1.5.9

?X: If a system fails, disable it in the hints. 99% of gcc uses binutils

```

# For gcc, adding -pipe speeds up compilations for some, but apparently
# some assemblers can't read from stdin. (It also slows down compilations
# in other cases, but those are apparently rarer these days.) AD 5/2004.

```

```

case "$gccversion" in
?*) set pipe -pipe
eval $checkccflag
;;
esac

```

?X: NWC 200712

```

# on x86_64 (at least) we require an extra library (libssp) in the
# link command line. This library is not named, so I infer that it is
# an implementation detail that may change. Hence the safest approach
# is to add the flag to the flags passed to the compiler at link time,
# as that way the compiler can do the right implementation dependant
# thing. (NWC)

```

```

case "$osname" in
amigaos)
;; # -fstack-protector builds but doesn't work
*) case "$gccversion" in
?*) set stack-protector-strong -fstack-protector-strong
eval $checkccflag
case "$dflt" in
*-fstack-protector-strong*) ;; # It got added.

```

```

*) # Try the plain/older -fstack-protector.
  set stack-protector -fstack-protector
  eval $checkccflag
  ;;
esac
;;
esac
;;
esac
;;
esac

```

?X: In USG mode, a MIPS system may need some BSD includes

```

case "$mips_type" in
*BSD*|*) inclwanted="$locincpth $usrinc";;
*) inclwanted="$locincpth $inclwanted $usrinc/bsd";;
esac
for thisincl in $inclwanted; do
if $test -d $thisincl; then
if $test x$thisincl != x$usrinc; then
  case "$dflt" in
  *" -I$thisincl "*);;
  *) dflt="$dflt -I$thisincl ";;
  esac
fi
fi
done

```

?X: Include test function (header, symbol)

```

inctest='if $contains $2 $usrinc/$1 >/dev/null 2>&1; then
xxx=true;
elif $contains $2 $usrinc/sys/$1 >/dev/null 2>&1; then
xxx=true;
else
xxx=false;
fi;
if $xxx; then
  case "$dflt" in
  *$2*);;
  *)
  dflt="$dflt -D$2";;
  esac;
fi'

```

```

set signal.h LANGUAGE_C; eval $inctest

```

```

case "$usesocks" in
$define)

```

```

ccflags="$ccflags -DSOCKS"
;;
esac

case "$hint" in
default|recommended) dflt="$ccflags $dflt" ;;
*) dflt="$ccflags";;
esac

case "$dflt" in
'| ') dflt=none;;
esac

$cat <<EOH

```

Your C compiler may want other flags. For this question you should include `-I/whatever` and `-DWHATEVER` flags and any other flags used by the C compiler, but you should NOT include libraries or `ld` flags like `-lwhatever`. If you want `$package` to honor its debug switch, you should include `-DDEBUGGING` here. Your C compiler might also need additional flags, such as `-D_POSIX_SOURCE`.

To use no flags, specify the word "none".

```

EOH
?X: strip leading space
set X $dflt
shift
dflt=${1+"$@"}
rp="Any additional cc flags?"
./myread
case "$ans" in
none) ccflags="";;
*) ccflags="$ans";;
esac

```

: the following weeds options from `ccflags` that are of no interest to `cpp`

```

case "$cppflags" in
") cppflags="$ccflags"
;;
*) set X $ccflags; shift
case " $cppflags " in
*" $1 "*" ) ;; # Try to avoid doubling the cppflags.
*) cppflags="$cppflags $ccflags" ;;
esac
;;
esac

case "$gccversion" in
1*) cppflags="$cppflags -D__GNUC__"

```

```

esac
case "$mips_type" in
");;
*BSD*) cppflags="$scppflags -DSYSTYPE_BSD43";;
esac
case "$scppflags" in
");;
*)
echo " "
echo "Let me guess what the preprocessor flags are..." >&4
set X $scppflags
shift
cppflags="
$cat >cpp.c <<'EOM'
#define BLURFL foo

BLURFL xx LFRULB
EOM
?X:
?X: For each cc flag, try it out with both cppstdin and cprun, since the
?X: first is almost surely a cc wrapper. We have to try both in case
?X: of cc flags like '-Olimit 2900' that are actually two words...
?X:
previous="
for flag in $*
do
case "$flag" in
-*) ftry="$flag";;
*) ftry="$previous $flag";;
esac
if $scppstdin -DLFRULB=bar $scppflags $ftry $scppminus <cpp.c \
>cpp1.out 2>/dev/null && \
$scpprun -DLFRULB=bar $scppflags $ftry $scplast <cpp.c \
>cpp2.out
2>/dev/null && \
$contains 'foo.*xx.*bar' cpp1.out >/dev/null 2>&1 && \
$contains 'foo.*xx.*bar' cpp2.out >/dev/null 2>&1
then
cppflags="$scppflags $ftry"
previous="
else
previous="$flag"
fi
done
set X $scppflags
shift
cppflags=${1+"$@"}
case "$scppflags" in

```

```

*~*) echo "They appear to be: $cppflags";;
esac
$rm -f cpp.c cpp?.out
;;
esac

: flags used in final linking phase
case "$ldflags" in
") if ./venix; then
  dflt='-i -z'
else
  dflt=""
fi
case "$ccflags" in
*~posix*) dflt="$dflt -posix" ;;
esac
;;
*) dflt="$ldflags";;
esac
# See note above about -fstack-protector
case "$ccflags" in
*~fstack-protector-strong*)
  case "$dflt" in
*~fstack-protector-strong*) ;; # Don't add it again
*) dflt="$dflt -fstack-protector-strong" ;;
esac
;;
*~fstack-protector*)
  case "$dflt" in
*~fstack-protector*) ;; # Don't add it again
*) dflt="$dflt -fstack-protector" ;;
esac
;;
esac

: Try to guess additional flags to pick up local libraries.
for thislibdir in $libpth;
do
  case " $loclibpth " in
*" $thislibdir ")
  case "$dflt " in
*~L$thislibdir ") ;;
*) dflt="$dflt -L$thislibdir" ;;
esac
;;
esac
done

```

```
case "$dflt" in
") dflt='none' ;;
esac
```

```
$cat <<EOH
```

Your C linker may need flags. For this question you should include -L/whatever and any other flags used by the C linker, but you should NOT include libraries like -lwhatever.

Make sure you include the appropriate -L/path flags if your C linker does not normally search all of the directories you specified above, namely

```
$libpth
```

To use no flags, specify the word "none".

```
EOH
```

```
rp="Any additional ld flags (NOT including libraries)?"
```

```
./myread
```

```
case "$ans" in
```

```
none) ldflags=";;
```

```
*) ldflags="$ans";;
```

```
esac
```

```
rmlist="$rmlist pdp11"
```

```
@if lkflags
```

```
: partial linking may need other flags
```

```
case "$lkflags" in
```

```
") case "$ldflags" in
```

```
) dflt='none';;
```

```
*) dflt="$ldflags";;
```

```
esac;;
```

```
*) dflt="$lkflags";;
```

```
esac
```

```
echo " "
```

```
rp="Partial linking flags to be used (NOT including -r)?"
```

```
./myread
```

```
case "$ans" in
```

```
none)
```

```
lkflags=";;
```

```
*) lkflags="$ans";;
```

```
esac
```

```
@end
```

```
?X:
```

```
?X: If the user changes compilers after selecting a hint file, it's
```

```
?X: possible that the suggested ccflags/ldflags will be wrong. Try to
```

?X: compile and run a simple test program. Let the user see all the
 ?X: error messages. -- ADO and RAM
 ?X: Sometimes, particularly on Linux systems, there is a bad library
 ?X: (e.g. a dangling symlink or incompatible library or a "run-time"
 ?X: version but not a "development" version of a library). This test
 ?X: will catch those sorts of problems too, though how to fix them
 ?X: may not be obvious.
 ?X:
 : coherency check
 echo " "
 echo "Checking your choice of C compiler and flags for coherency..." >&4
 \$cat >try.c <<'EOF'
 #include <stdio.h>
 int main() { printf("Ok\n"); return(0); }
 EOF

?X: Strip extra blanks in case some of the following variables are empty
 set X \$cc -o try \$optimize \$ccflags \$ldflags try.c \$libs
 shift
 \$cat >try.msg <<'EOM'

I've tried to compile and run the following simple program:

```
EOM
$cat
try.c >> try.msg
```

```
$cat >> try.msg <<EOM
```

I used the command:

```
$*
$run ./try
```

and I got the following output:

```
EOM
dflt=y
?X: Use "sh -c" to avoid error messages tagged with leading "Configure:".
?X: We need to try the resulting executable, because cc might yield a 0 status
?X: even when ld failed, in which case the executable will not run properly,
?X: if its x bit is set at all..
if $sh -c "$cc -o try $optimize $ccflags $ldflags try.c $libs" >>try.msg 2>&1; then
if $sh -c "$run ./try " >>try.msg 2>&1; then
xxx=`$run ./try`
case "$xxx" in
"Ok") dflt=n ;;
*) echo 'The program compiled OK, but produced no output.' >> try.msg ;;
esac
else
```

```

echo "The program compiled OK, but exited with status $?." >>try.msg
rp="You have a problem. Shall I abort Configure"
dflt=y
fi
else
echo "I can't compile the test program." >>try.msg
rp="You have a BIG problem. Shall I abort Configure"
dflt=y
fi
case "$dflt" in
y)
$cat try.msg >&4
?X: using -K will prevent
default aborting--maybe they're cross compiling?
case "$knowitall" in
")
echo "(The supplied flags or libraries might be incorrect.)"
;;
*) dflt=n;;
esac
echo " "
. ./myread
case "$ans" in
n*[N*]) ;;
*) echo "Ok. Stopping Configure." >&4
exit 1
;;
esac
;;
n) echo "OK, that should do.";;
esac
$rm_try gcctest gcctest.out

```

Found in path(s):

```

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/compline/ccflags.U

```

No license file was found, but licenses were detected in source scan.

```

;#####

```

```

;# Jmake rules for building libraries, programs, scripts, and data files
;# $Id: Jmake.rules 18 2006-12-27 10:35:09Z rmanfredi $

```

```

/*
* MACHINE-INDEPENDENT RULES -- DO NOT MODIFY
*/

```

```

/* $Id: Jmake.rules 18 2006-12-27 10:35:09Z rmanfredi $
*

```

```

* Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
*
* You may redistribute only under the terms of the Artistic Licence,
* as specified in the README file that comes with the distribution.
* You may reuse parts of this distribution only within the terms of
* that same Artistic Licence; a copy of which may be found at the root
* of the source tree for dist 4.0.
*
* $Log: Jmake.rules,v $
* Revision 3.0.1.7 2004/08/22 08:28:58 ram
* patch71: random cleanup
*
* Revision 3.0.1.6 1997/02/28 14:56:01 ram
* patch61: now handles USRINC for dependencies
* patch61: smarter about dependencies
computation
*
* Revision 3.0.1.5 1995/09/25 09:07:19 ram
* patch59: smarter sed command to strip /usr/include dependencies
*
* Revision 3.0.1.4 1995/07/25 13:33:59 ram
* patch56: install of script man pages can now cope with missing files
* patch56: the clobber target now removes the .config directory as well
*
* Revision 3.0.1.3 1995/03/21 08:35:28 ram
* patch52: suppressed extra argument to NormalProgramTarget call
*
* Revision 3.0.1.2 1995/01/11 14:49:55 ram
* patch45: new macros ShellScriptTargetExt and SimpleShellScriptTargetExt
* patch45: directory installation is now made via INSTALLDIR (Configure)
*
* Revision 3.0.1.1 1994/10/29 15:46:30 ram
* patch36: added RemoteDependency rule
*
* Revision 3.0 1993/08/18 12:04:14 ram
* Baseline for dist 3.0 netwide release.
*
*/

/* Please, edit only with tabstops = 4 (":set ts=4" under vi) */

/*
* AddedByConfigure:
* Gives name of the files generated by Configure that can safely
* be removed
* when a "make clobber" is issued. Not that it is useless
* to name config.h or config.sh because these are already taken care
* of by jmake.

```

```

*/
#define AddedByConfigure(files) @!\
local_clobber::  @@\
$(RM) files

/*
* AddSuffix:
* Adds a suffix to the .SUFFIXES: list.
*/
#define AddSuffix(ext) @!\
|suffix ext

/*
* AllTarget:
* Generate rules to build necessary things during make all.
*/
#define AllTarget(depends) @!\
all:: depends  @!\
    @!\
local_realclean::  @@\
$(RM) depends

/*
* RemoveTargetProgram:
* This is used in some other macros in order to remove the target
* before starting its building (saves disk space). There should be
* no '@!' at the end of the '#define' line, because this macro is
* used *inside* building rules.
*/
#define RemoveTargetProgram(program) \
$(RM) program @@\
if test -f program^^^$_EXE; then \ @@\
$(MV) program^^^$_EXE program^^~^^^$_EXE; fi

/*
* NormalProgramTarget:
* Generate rules to compile and link the
indicated program; since
* it does not use any default object files, it may be used for
* multiple programs in the same Jmakefile.
*/
#define NormalProgramTarget(program,sources,objects) @!\
++OBJECTS objects @!\
++SOURCES sources @!\
NormalObjectRule() @!\
AllTarget(program) @!\
    @!\

```

```

program: objects  @@\
RemoveTargetProgram($@)  @@\
$(CC) -o $@ objects $(JLDFLAGS) $(LIBS) @!\

/*
* SingleProgramTarget:
* Obsolete version of NormalProgramTarget that doesn't have
* deplibs.
*/
#define SingleProgramTarget(program,objects,libs) \
NormalProgramTarget(program,objects,libs)

/*
* SimpleProgramTarget:
* Generate rules for compiling and linking programs that only have
* one C source file. It should only be used in Jmakefiles that
* describe a single program.
*/
#define SimpleProgramTarget(program) @!\
NormalProgramTarget(program,program.c,program.o)

/*
* ComplexProgramTarget:
* Generate rules for compiling and linking the program specified by
* $(OBJS) and
* $(SRCS), installing the program and its man page, and
* generating dependencies. It should only be used in Jmakefiles
* that describe a single program.
*/
#define ComplexProgramTarget(program) @!\
++OBJECTS $(OBJS) @!\
++SOURCES $(SRCS) @!\
NormalObjectRule()  @!\
AllTarget(program)  @!\
    @!\
program: $(OBJS)  @@\
RemoveTargetProgram($@)  @@\
$(CC) -o $@ $(OBJS) $(JLDFLAGS) $(LIBS) @!\
    @!\
InstallProgram(program,$(BINDIR)) @!\
InstallManPage(program,$(MANSRC)) @!\
DependTarget()  @!\
LintTarget()

```

```

/*
* ComplexProgramTarget_1:
* Generate rules for compiling and linking the program specified by
* $(OBJS1) and $(SRCS1), installing the program and its man page,
* and generating dependencies for it and any programs described by
* $(SRCS2) and $(SRCS3). It should be used to build the primary
* program in Jmakefiles that describe multiple programs.
*/
#define ComplexProgramTarget_1(program) @!\
++OBJECTS $(OBJS1) @!\
++SOURCES $(SRCS1) @!\
NormalObjectRule() @!\
AllTarget(program) @!\
    @!\
program:
$(OBJS1) @@\
RemoveTargetProgram($@) @@\
$(CC) -o $@ $(OBJS1) $(JLDFLAGS) $(LIBS) @!\
    @!\
InstallProgram(program,$(BINDIR)) @!\
InstallManPage(program,$(MANSRC)) @!\
    @!\
DependTarget() @!\
LintTarget()

/*
* ComplexProgramTarget_2:
* Generate rules for compiling and linking the program specified by
* $(OBJS2) and $(SRCS2) and installing the program and man page.
* It should be used to build the second program in Jmakefiles
* describing more than one program.
*/
#define ComplexProgramTarget_2(program) @!\
++OBJECTS $(OBJS2) @!\
++SOURCES $(SRCS2) @!\
NormalObjectRule() @!\
AllTarget(program) @!\
    @!\
program: $(OBJS2) @@\
RemoveTargetProgram($@) @@\
$(CC) -o $@ $(OBJS2) $(JLDFLAGS) $(LIBS) @!\
    @!\
InstallProgram(program,$(BINDIR)) @!\
InstallManPage(program,$(MANSRC))

/*

```

```

* ComplexProgramTarget_3:
* Generate rules for compiling and linking the
  program specified by
* $(OBS3) and $(SRCS3) and installing the program and man page. It
* should be used to build the third program in Jmakefiles describing
* more than one program.
*/

```

```

#define ComplexProgramTarget_3(program) @!\
++OBJECTS $(OBS3) @!\
++SOURCES $(SRCS3) @!\
NormalObjectRule() @!\
AllTarget(program) @!\
    @!\
program: $(OBS3) @@\
RemoveTargetProgram($@) @@\
$(CC) -o $@ $(OBS3) $(JLDFLAGS) $(LIBS) @!\
    @!\
InstallProgram(program,$(BINDIR)) @!\
InstallManPage(program,$(MANSRC))

```

```

/*
* ComplexShellManualTarget:
* Builds manual pages that are to be extracted from .SH files into
* $.manext files.
*/

```

```

#define ComplexShellManualTarget(manpages) @!\
++MANPAGE manpages @!\
|once _ShellManualRule_ @!\
|rule:$.SH$.manext: @!\
|rule: /bin/sh $< @!\
|rule: @!\
-once @!\
AddSuffix(.SH) @!\
AddSuffix($.manext) @!\
AllTarget(manpages) @!\
    @!\
local_install.man:: @@\
_MakeInstallDirIgnore($(MANSRC)) \ @@\
for
file in manpages; do \ @@\
(set -x; $(INSTALL) -c -m 444 $$file \ @@\
$(INSTALL_PREFIX)$(MANSRC)) || exit 1; \ @@\
done @!\
    @!\
local_deinstall.man:: @@\
@case '${MFLAGS}' in *[i]*) set +e;; esac; \ @@\
for file in manpages; do \ @@\

```

```
(set -x; $(RM) $(INSTALL_PREFIX)$(MANSRC)/$$file); \ @@\  
done
```

```
/*
```

```
* Initialize:
```

```
* Puts the line symbol = value in the initialization section of
```

```
* Makefile.SH (the one that is subject to parameter substitutions).
```

```
*/
```

```
#define Initialize(symbol,value) @!\
```

```
+symbol = value
```

```
/*
```

```
* InstallLibrary:
```

```
* Generate rules to install the indicated library.
```

```
*/
```

```
#define InstallLibrary(libname,dest) @!\
```

```
local_install:: lib^^libname.a @@\  
_MakeInstallDirIgnore(dest) \ @@\  
$(INSTALL) -c -m 644 lib^^libname.a $(INSTALL_PREFIX)^^dest @@\  
$(RANLIB) dest/lib^^libname.a @@\  
chmod 444 dest/lib^^libname.a @!\
```

```
@!\
```

```
local_deinstall:: @@\  
$(RM) $(INSTALL_PREFIX)^^dest/lib^^libname.a
```

```
/*
```

```
* InstallSharedLibrary:
```

```
* Generate rules to install  
the shared library.
```

```
*/
```

```
#define InstallSharedLibrary(libname,rev,dest) @!\
```

```
local_install:: lib^^libname.so.rev @@\  
_MakeInstallDirIgnore(dest) \ @@\  
$(INSTALL) -c -m 444 lib^^libname.so.rev $(INSTALL_PREFIX)^^dest @!\
```

```
@!\
```

```
local_deinstall:: @@\  
$(RM) $(INSTALL_PREFIX)^^dest/lib^^libname.so.rev
```

```
/*
```

```
* InstallSharedLibraryData:
```

```
* Generate rules to install the shared library data
```

```
*/
```

```
#define InstallSharedLibraryData(libname,rev,dest) @!\
```

```
local_install:: lib^^libname.sa.rev @@\  
_MakeInstallDirIgnore(dest) \ @@\  
$(INSTALL) -c -m 444 lib^^libname.sa.rev $(INSTALL_PREFIX)^^dest @!\
```

```

_MakeInstallDirIgnore(dest) \ @@\
$(INSTALL) -c -m 444 lib^^libname.sa.rev $(INSTALL_PREFIX)^^^dest @!\
    @!\
local_deinstall::  @@\
$(RM) $(INSTALL_PREFIX)^^^dest/lib^^libname.sa.rev

/*
* InstallLibraryAlias:
* Generate rules to create a link from one library name to another
* for the purposes of aliasing.
*/
#define InstallLibraryAlias(libname,alias,dest) @!\
local_install:: lib^^libname.a @@\
$(RM) lib^^alias.a @@\
-(cd dest; $(LN) lib^^libname.a lib^^alias.a)
@!\
    @!\
local_deinstall::  @@\
$(RM) dest/lib^^alias.a

/*
* InstallLintLibrary:
* Generate rules to install the indicated lint library.
*/
#define InstallLintLibrary(libname,dest) @!\
install.ln:: llib-l^^libname.ln  @@\
_MakeInstallDirIgnore(dest) \ @@\
$(INSTALL) -c -m 444 llib-l^^libname.ln $(INSTALL_PREFIX)^^^dest @!\
    @!\
deinstall.ln::  @@\
$(RM) $(INSTALL_PREFIX)^^^dest/llib-l^^libname.ln

/*
* InstallManPageLong:
* Generate rules to install the indicated manual page, giving it an
* alternate name. This is used for installing man pages whose base
* name without the .man suffix would normally be longer than 8
* characters (the limit for using source code control systems on
* files systems with short file names).
*/
#define InstallManPageLong(file,destdir,dest) @!\
local_install.man:: file.man  @@\
_MakeInstallDirIgnore(destdir) \ @@\
$(INSTALL) -c -m 444 file.man $(INSTALL_PREFIX)^^^destdir/dest.$(L) @!\
    @!\

```

```

local_deinstall.man::  @@\
$(RM)
$(INSTALL_PREFIX)^^^destdir/dest.$(L) @!\

/*
* InstallManPage:
* Generate rules to install the indicated manual page.
*/
#define InstallManPage(file,dest) @!\
InstallManPageLong(file,dest,file)

/*
* InstallNonExec:
* Generate rules to install a data file using any special
* install flags.
*/
#define InstallNonExec(file,dest) @!\
local_install:: file  @@\
_MakeInstallDirIgnore(dest) \ @@\
$(INSTALL) -c -m 444 file $(INSTALL_PREFIX)^^^dest @!\
    @!\
local_deinstall::  @@\
$(RM) $(INSTALL_PREFIX)^^^dest/file

/*
* InstallProgramWithFlags:
* Generate rules to install an executable program using given
* install flags.
*/
#define InstallProgramWithFlags(program,dest,flags) @!\
local_install:: program  @@\
_MakeInstallDirIgnore(dest) \ @@\
$(INSTALL) -c -s -m 555 flags program^^^$_EXE $(INSTALL_PREFIX)^^^dest @!\
    @!\
local_deinstall::  @@\
$(RM) $(INSTALL_PREFIX)^^^dest/program^^^$_EXE

/*
* InstallProgramNoStripWithFlags:
* Generate rules to install an executable program using given
* install flags.
*/
#define InstallProgramNoStripWithFlags(program,dest,flags) @!\
local_install:: program  @@\

```

```

_MakeInstallDirIgnore(dest) \ @@\
$(INSTALL) -c -m 555 flags program^^^$_EXE $(INSTALL_PREFIX)^^^dest @!\
    @!\
local_deinstall::  @@\
$(RM) $(INSTALL_PREFIX)^^^dest/program^^^$_EXE

/*
* InstallProgram:
* Generate rules to install an executable program using any special
* install flags set in $(INSTALLFLAGS).
*/
#define InstallProgram(program,dest) @!\
InstallProgramWithFlags(program,dest,^^)

/*
* InstallProgramNoStrip:
* Generate rules to install an executable program using any special
* install flags set in $(INSTALLFLAGS), but without stripping the
* executable from debugging symbols.
*/
#define InstallProgramNoStrip(program,dest) @!\
InstallProgramNoStripWithFlags(program,dest,^^)

/*
* InstallScriptWithFlags:
* Generate rules to install an executable script using given
* install
* flags.
*/
#define InstallScriptWithFlags(script,dest,flags) @!\
local_install:: script  @@\
    _MakeInstallDirIgnore(dest) \ @@\
    $(INSTALL) -c -m 555 flags script $(INSTALL_PREFIX)^^^dest @!\
        @!\
local_deinstall::  @@\
$(RM) $(INSTALL_PREFIX)^^^dest/script

/*
* InstallScript:
* Generate rules to install an executable script using any special
* install flags set in $(INSTALLFLAGS).
*/
#define InstallScript(script,dest) @!\
InstallScriptWithFlags(script,dest,^^)

```

```

/*
* InstallScripts:
* Generate rules to install all the scripts listed in the generated
* $(SCRIPTS) and $(LSCRIPTS) macros.
*/
#define InstallScripts() @!\
|once _InstallScripts_ @!\
local_install:: $(SCRIPTS) $(LSCRIPTS) @@\
_MakeInstallDirIgnore($(SCRIPTDIR)) \ @@\
for file in $(SCRIPTS) $(LSCRIPTS); do \ @@\
(set -x; \ @@\
$(INSTALL) -c -m 555 $$file $(INSTALL_PREFIX)$(SCRIPTDIR) || \ @@\
exit 1; \ @@\
done @!\
@!\
local_deinstall:: @@\
@for file in $(SCRIPTS)
$(LSCRIPTS); do \ @@\
case '${MFLAGS}' in *[i]*) set +e;; esac; \ @@\
(set -x; $(RM) $(INSTALL_PREFIX)$(SCRIPTDIR)/$$file); \ @@\
done @!\
-once

```

```

/*
* InstallManScripts:
* Generate rule to install/deinstall manual pages for scripts listed
* in the automatically generated $(SCRIPTS) macro.
*/
#define InstallManScripts() @!\
|once _InstallManScripts_ @!\
?NOMAN:|skip @!\
local_install.man:: @@\
_MakeInstallDirIgnore($(MANSRC)) \ @@\
for file in $(SCRIPTS); do \ @@\
if test -f $$file.man; then \ @@\
(set -x; \ @@\
$(INSTALL) -c -m 444 $$file.man \ @@\
$(INSTALL_PREFIX)$(MANSRC)/$$file.$(L) || \ @@\
exit 1; \ @@\
fi; \ @@\
done @!\
@!\
local_deinstall.man:: @@\
case '${MFLAGS}' in *[i]*) set +e;; esac; \ @@\
for file in $(SCRIPTS); do \ @@\
(set -x; $(RM) $(INSTALL_PREFIX)$(MANSRC)/$$file.$(L)); \ @@\

```

```
done @!\
    @!\
-skip @!\
-once
```

```
/*
```

```
* LinkFileList:
```

```
* Link a list of list of files from one place to another
```

```
*/
```

```
#define LinkFileList(step,list,dir,sub) @!\
```

```
step:: list    @@\
```

```
@case '${MFLAGS}' in *[i]*) set +e;; esac; \ @@\
```

```
echo " cd" dir; cd dir; for i in list; do (set -x; $(LN) sub/$$i .); done
```

```
/*
```

```
* InstallMultipleDestFlags:
```

```
* Generate rules to install multiple files at once during a particular
```

```
* step in the build using a specific set of install flags.
```

```
*/
```

```
#define InstallMultipleDestFlags(step,list,dest,flags) @!\
```

```
step:: list    @@\
```

```
_MakeInstallDirIgnore(dest) \ @@\
```

```
for i in list; do \    @@\
```

```
(set -x; $(INSTALL) -c flags \ @@\
```

```
 $$i $(INSTALL_PREFIX)^^dest) || exit 1; \ @@\
```

```
done
```

```
/*
```

```
* DeinstallMultipleDest:
```

```
* Generate rules to deinstall multiple files at once during a particular
```

```
* step in the build.
```

```
*/
```

```
#define DeinstallMultipleDest(step,list,dest) @!\
```

```
step::    @@\
```

```
@case '${MFLAGS}' in *[i]*) set +e;; esac; \ @@\
```

```
for i in list; do \    @@\
```

```
(set -x; $(RM) $(INSTALL_PREFIX)^^dest/$$i); \ @@\
```

```
done
```

```
/*
```

```
* InstallMultiple:
```

```
* Generate rules to install multiple
```

```
files at once during the install
```

```
* step of the build using any install flags set in $(INSTALLFLAGS)
```

```
* and deinstall them.
```

```

*/
#define InstallMultiple(list,dest) @!\
InstallMultipleDestFlags(local_install,list,dest,$(INSTALLFLAGS)) @!\
DeinstallMultipleDest(local_deinstall,list,dest)

/*
* InstallMultipleFlags:
* Generate rules to install multiple files at once during the
* install step of the build using the given install flags.
*/
#define InstallMultipleFlags(list,dest,flags) @!\
InstallMultipleDestFlags(local_install,list,dest,flags) @!\
DeinstallMultipleDest(local_deinstall,list,dest)

/*
* InstallMultipleMan:
* Generate rules to install a variety of manual pages
* during the install.man step of the build.
*/
#define InstallMultipleMan(list,dest) @!\
InstallMultipleDestFlags(local_install.man,list,dest,$(INSTALLFLAGS)) @!\
DeinstallMultipleDest(local_deinstall.man,list,dest)

/*
* DependDependency:
* Generate rules to build the makedepend program.
*/
#define DependDependency()
    @!\
depend:: TOPDIR/mkdep    @!\
    @!\
TOPDIR/mkdep:    @!\
?TOP: @echo "You have to run Configure first."; exit 1 @!\
%TOP: @echo "You have to run Configure in $(TOP) first."; exit 1

/*
* DependTarget:
* Generate rules to compute dependencies for all files listed
* in $(SOURCES) (automatically generated macro).
*/
#define DependTarget() @!\
+USRINC = $usrinc @!\
|once _DependTarget_ @!\
DependDependency() @!\

```

```

    @!\
depend::    @@\
$(SED) '/^# DO NOT DELETE/q' Makefile && \ @@\
$(MKDEP) $(SOURCES) | \  @@\
$(SED) -e 's:/usr/lib[^ ]*::g; s:$(USRINC)[^ ]*::g; ' \ @@\
-e '/: / b print' -e '$$ b print' -e 'H; d; n; : print' \ @@\
-e 'x; s/\$\$/; s/\n//g; s/ ^ ^ */ /g; s/ :/:;' -e '/: *$$/d' \ @@\
) > Makefile.new  @@\
cp Makefile Makefile.bak  @@\
cp Makefile.new Makefile  @@\
$(RM) Makefile.new  @!\
    @!\
-once

```

```

/*
* CleanTarget:
* Generate rules to remove any garbage files.
*/
#define CleanTarget()  @!\
?SUBDIRS:clean:
sub_clean local_clean  @!\
%SUBDIRS:clean: local_clean  @!\
?SUBDIRS:realclean: sub_realclean local_realclean @!\
%SUBDIRS:realclean: local_realclean  @!\
?SUBDIRS:clobber: sub_clobber local_clobber  @!\
%SUBDIRS:clobber: local_clobber  @!\
    @!\
local_clean::    @@\
if test -f core; then $(RM) core; fi @@\
$(RM) *~ *.o  @!\
    @!\
local_realclean:: local_clean @!\
?TOP: $(RM) -r UU  @!\
    @!\
local_clobber:: local_realclean @!\
%TOP: $(RM) Makefile config.sh @!\
?TOP: $(RM) config.sh config.h @!\
?TOP: $(RM) -r .config  @!\
?TOP: $(RM) Makefile  @!\

```

```

/*
* InstallTarget:
* Generate rules to recursively install files
*/
#define InstallTarget()  @!\
?SUBDIRS:install:: local_install sub_install  @!\

```

```

%SUBDIRS:install:: local_install    @!\
?SUBDIRS:install.man:: maybe_install.man sub_install.man @!\
%SUBDIRS:install.man:: maybe_install.man    @!\
?SUBDIRS:deinstall:: sub_deinstall local_deinstall    @!\
%SUBDIRS:deinstall::
local_deinstall    @!\
?SUBDIRS:deinstall.man:: sub_deinstall.man maybe_deinstall.man @!\
%SUBDIRS:deinstall.man:: maybe_deinstall.man    @!\
    @!\
?MANSRC:install.man-yes: local_install.man    @!\
install.man-no:        @!\
?MANSRC:deinstall.man-yes: local_deinstall.man    @!\
deinstall.man-no:        @!\

```

```
/*
```

```

* TagsTarget:
* Generate rules to compute tags files for C source code.
*/

```

```

#define TagsTarget() @!\
tags::    @@\
$(CTAGS) -w *.[ch]    @@\
$(CTAGS) -xw *.[ch] > tags    @!\
    @!\
local_clobber::    @@\
$(RM) tags

```

```
/*
```

```

* BuildMakefileSH:
* Generate rules to build a Makefile.SH from an Jmakefile and any
* special jmake flags. This is generally done automatically by the
* template or by any special Jmakefiles.
* This function will simply touch Makefile.SH if no $(TOP)/.package
* exists, assuming the Jmakefile is not in a production environment.
*/

```

```

#define BuildMakefileSH(jmakeflags) @!\
Makefile.SH:
Jmakefile    @@\
-@if test -f $(TOP)/.package; then \ @@\
if test -f Makefile.SH; then \ @@\
echo "$(RM) Makefile.SH~; $(MV) Makefile.SH Makefile.SH~"; \ @@\
$(RM) Makefile.SH~; $(MV) Makefile.SH Makefile.SH~; \ @@\
fi; \    @@\
echo "$(JMAKE) -DTOPDIR=$(TOP) -DCURDIR=$(CURRENT)" jmakeflags; \ @@\
$(JMAKE) -DTOPDIR=$(TOP) -DCURDIR=$(CURRENT) jmakeflags; \ @@\
else touch $@; fi

```

```

/*
* BuildMakefile:
* Generate rules to build a Makefile from a Makefile.SH.
*/
#define BuildMakefile() @!\
Makefile: Makefile.SH  @@\
/bin/sh Makefile.SH

/*
* MakefileTarget:
* Generate rules to build a normal Makefile.
*/
#define MakefileTarget() @!\
BuildMakefileSH(^)  @!\
BuildMakefile()

/*
* NormalObjectRule:
* Generate make rule to build usual object files.
*/
#define NormalObjectRule() @!\
|once _ObjectRule_  @!\
|rule:.c.o:  @!\
|rule: $(CC) -c $(JCFLAGS) $< @!\
|rule:  @!\
-once

/*
* NormalLibraryObjectRule:
* Generate make rules to build
"normal" objects.
*/
#define NormalLibraryObjectRule() @!\
|once _ObjectRule_  @!\
|rule:.c.o:  @!\
|rule: $(RM) $@  @!\
|rule: $(CC) -c $(JCFLAGS) $< @!\
|rule:  @!\
-once

/*
* ProfiledLibraryObjectRule:
* Generate make rules to build both profiled and "normal" objects.
*/

```

```

#define ProfiledLibraryObjectRule() @!\
all::    @@\
    @if [ ! -d profiled ]; then mkdir profiled; fi @!\
        @!\
|rule:.c.o:    @!\
|rule: $(RM) $@ profiled/$@ @!\
|rule: $(CC) -pg -c $(JCFLAGS) $*.c @!\
|rule: $(MV) $*.o profiled/$*.o @!\
|rule: $(CC) -c $(JCFLAGS) $*.c @!\
|rule:    @!\
local_clean::    @@\
-@if [ -d profiled ]; then echo " $(RM) profiled/?*.o"; \ @@\
$(RM) profiled/?*.o; fi

```

/*

```

* DebuggedLibraryObjectRule:
* Generate make rules to build both debuggable and "normal"
* objects.
*/

```

```

#define DebuggedLibraryObjectRule() @!\
all::    @@\
    @if [ ! -d debugger ]; then mkdir debugger; fi @!\
        @!\
|rule:.c.o:    @!\
|rule: $(RM) $@
debugger/$@ @!\
|rule: $(CC) -g -c $(JCFLAGS) $*.c @!\
|rule: $(MV) $*.o debugger/$*.o @!\
|rule: $(CC) -c $(JCFLAGS) $*.c @!\
|rule:    @!\
local_clean::    @@\
-@if [ -d debugger ]; then echo " $(RM) debugger/?*.o"; \ @@\
$(RM) debugger/?*.o; fi

```

/*

```

* DebuggedAndProfiledLibraryObjectRule:
* Generate make rules to build debuggable, profiled, and "normal"
* objects.
*/

```

```

#define DebuggedAndProfiledLibraryObjectRule() @!\
all::    @@\
    @if [ ! -d profiled ]; then mkdir profiled; fi @@\
    @if [ ! -d debugger ]; then mkdir debugger; fi @!\
        @!\
|rule:.c.o:    @!\
|rule: $(RM) $@ profiled/$@ debugger/$@ @!\

```

```

|rule: $(CC) -pg -c $(JCFLAGS) $*.c @!\
|rule: $(MV) $*.o profiled/$*.o @!\
|rule: $(CC) -g -c $(JCFLAGS) $*.c @!\
|rule: $(MV) $*.o debugger/$*.o @!\
|rule: $(CC) -c $(JCFLAGS) $*.c @!\
|rule: @!\
local_clean:: @!\
-@if [ -d profiled ]; then echo " $(RM) profiled/?*.o"; \ @!\
$(RM) profiled/?*.o; fi @!\
-@if [ -d debugger ];
then echo " $(RM) debugger/?*.o"; \ @!\
$(RM) debugger/?*.o; fi

/*
* SharedLibraryObjectRule:
* Generate make rules to build shared and "normal" object files.
*/
#define SharedLibraryObjectRule() @!\
all:: @!\
@if [ ! -d shared ]; then mkdir shared; fi @!\
@!\
|rule:.c.o: @!\
|rule: $(RM) $@ shared/$@ @!\
|rule: $(CC) -pic -c $(SHARED_CODEDEF) $(SHLIBDEF) $(JCFLAGS) $*.c @!\
|rule: $(MV) $*.o shared/$*.o @!\
|rule: $(CC) -c $(SHLIBDEF) $(JCFLAGS) $*.c @!\
|rule: @!\
local_clean:: @!\
-@if [ -d shared ]; then echo " $(RM) shared/?*.o"; \ @!\
$(RM) shared/?*.o; fi

/*
* SharedAndDebuggedLibraryObjectRule:
* Generate make rules to build shared, debuggable, and "normal"
* object files.
*/
#define SharedAndDebuggedLibraryObjectRule() @!\
all:: @!\
@if [ ! -d shared ]; then mkdir shared; fi @!\
@if [ ! -d debugger ]; then mkdir debugger; fi @!\
@!\
|rule:.c.o: @!\
|rule: $(RM) $@ shared/$@ debugger/$@ @!\
|rule:
$(CC) -pic -c $(SHARED_CODEDEF) $(SHLIBDEF) $(JCFLAGS) $*.c @!\
|rule: $(MV) $*.o shared/$*.o @!\
|rule: $(CC) -g -c $(SHLIBDEF) $(JCFLAGS) $*.c @!\

```

```

|rule: $(MV) $*.o debugger/$*.o @!\
|rule: $(CC) -c $(SHLIBDEF) $(JCFLAGS) $*.c @!\
|rule: @!\
local_clean:: @@\
-@if [ -d shared ]; then echo " $(RM) shared/?*.o"; \ @@\
$(RM) shared/?*.o; fi @@\
-@if [ -d debugger ]; then echo " $(RM) debugger/?*.o"; \ @@\
$(RM) debugger/?*.o; fi

/*
* SpecialSharedAndDebuggedObjectRule:
* Generate rules to compile a file with special flags and to make
* shared and debuggable versions.
*/
#define SpecialSharedAndDebuggedObjectRule(objs,depends,options) @!\
all:: @@\
@if [ ! -d shared ]; then mkdir shared; fi @@\
@if [ ! -d debugger ]; then mkdir debugger; fi @!\
@!\
objs: depends @@\
$(RM) $@ shared/$@ debugger/$@ @@\
$(CC) -pic -c $(SHAREDDEF) $(SHLIBDEF) $(JCFLAGS) options $*.c @@\
$(MV) $*.o shared/$*.o @@\
$(CC)
-g -c $(SHLIBDEF) $(JCFLAGS) options $*.c @@\
$(MV) $*.o debugger/$*.o @@\
$(CC) -c $(SHLIBDEF) $(JCFLAGS) options $*.c

/*
* SpecialSharedObjectRule:
* Generate rules to compile a file with special flags and to make
* shared and debuggable versions.
*/
#define SpecialSharedObjectRule(objs,depends,options) @!\
all:: @@\
@if [ ! -d shared ]; then mkdir shared; fi @!\
@!\
objs: depends @@\
$(RM) $@ shared/$@ @@\
$(CC) -pic -c $(SHAREDDEF) $(SHLIBDEF) $(JCFLAGS) options $*.c @@\
$(MV) $*.o shared/$*.o @@\
$(CC) -c $(SHLIBDEF) $(JCFLAGS) options $*.c

/*
* SpecialObjectRule:
* Generate rules to compile a file with special flags.
*/

```

```

#define SpecialObjectRule(objs,depends,options) @!\
objs: depends    @@\
$(RM) $@        @@\
$(CC) -c $(JCFLAGS) options $*.c

/*
* SpecialProfiledObjectRule:
* Generate rules to compile a file with special flags and to make a
* profiled version.
*/
#define SpecialProfiledObjectRule(objs,depends,options) @!\
all::    @@\
@if
[ ! -d profiled ]; then mkdir profiled; fi @!\
    @!\
objs: depends    @@\
$(RM) $@ profiled/$@    @@\
$(CC) -pg -c $(JCFLAGS) options $*.c @@\
$(MV) $*.o profiled/$*.o    @@\
$(CC) -c $(JCFLAGS) options $*.c

/*
* SpecialDebuggedObjectRule:
* Generate rules to compile a file with special flags and to make a
* debuggable version.
*/
#define SpecialDebuggedObjectRule(objs,depends,options) @!\
all::    @@\
@if [ ! -d debugger ]; then mkdir debugger; fi @!\
    @!\
objs: depends    @@\
$(RM) $@ debugger/$@    @@\
$(CC) -g -c $(JCFLAGS) options $*.c @@\
$(MV) $*.o debugger/$*.o    @@\
$(CC) -c $(JCFLAGS) options $*.c

/*
* SpecialDebuggedAndProfiledObjectRule:
* Generate rules to compile a file with special flags and to make
* debuggable and profiled versions.
*/
#define SpecialDebuggedAndProfiledObjectRule(objs,depends,options) @!\
all::    @@\
@if [ ! -d profiled ]; then mkdir profiled; fi @@\
@if [ ! -d

```

```

debugger ]; then mkdir debugger; fi @!\
    @!\
objs: depends    @@\
$(RM) $@ profiled/$@ debugger/$@ @@\
$(CC) -pg -c $(JCFLAGS) options $*.c @@\
$(MV) $*.o profiled/$*.o @@\
$(CC) -g -c $(JCFLAGS) options $*.c @@\
$(MV) $*.o debugger/$*.o @@\
$(CC) -c $(JCFLAGS) options $*.c

/*
* NormalLibraryTarget:
* Generate rules to create a library. The 'srclist' and 'objlist'
* parameters are added to SOURCES and OBJECTS macros. The 'srclist'
* is not otherwise used by this rule, but is necessary for make depend.
*/
#define NormalLibraryTarget(libname,srclist,objlist) @!\
++OBJECTS objlist @!\
++SOURCES srclist @!\
NormalLibraryObjectRule() @!\
AllTarget(lib^^libname.a) @!\
    @!\
lib^^libname.a: objlist  @@\
$(RM) $@  @@\
$(AR) $@ objlist  @@\
$(RANLIB) $@

/*
* NormalSharedLibraryTarget:
* Generate rules to create a shared library; build it into a
* different name so that the we don't hose people by having the
* library gone for long periods.
*/
#define
NormalSharedLibraryTarget(libname,rev,solist) @!\
AllTarget(lib^^libname.so.rev) @!\
    @!\
lib^^libname.so.rev: solist  @@\
$(RM) $@~  @@\
(cd shared; $(LD) -o ../$@~ -assert pure-text solist) @@\
$(RM) $@  @@\
$(MV) $@~ $@

/*
* NormalSharedLibraryDataTarget:
* Generate rules to create shlib data file; build it into a

```

```

* different name so that the we don't hose people by having the
* library gone for long periods.
*/
#define NormalSharedLibraryDataTarget(libname,rev,salist) @!\
AllTarget(lib^^libname.sa.rev) @!\
    @!\
lib^^libname.sa.rev: salist @@\
$(RM) $@  @@\
$(AR) $@ salist  @@\
$(RANLIB) $@

/*
* NormalLibraryTarget2:
* Generate rules to create a library in two steps. This is used to
* create libraries with large numbers of files.
*/
#define NormalLibraryTarget2(libname,srclist,objlist1,objlist2) @!\
++SOURCES srclist @!\
++OBJECTS objlist1 @!\
++OBJECTS objlist2 @!\
NormalLibraryObjectRule() @!\
AllTarget(lib^^libname.a) @!\
    @!\
lib^^libname.a:
objlist1 objlist2 @@\
$(RM) $@  @@\
$(AR) $@ objlist1  @@\
$(AR) $@ objlist2  @@\
$(RANLIB) $@

/*
* ProfiledLibraryTarget:
* Generate rules to create a profiled library.
*/
#define ProfiledLibraryTarget(libname,srclist,objlist) @!\
++SOURCES srclist @!\
++OBJECTS objlist @!\
AllTarget(lib^^libname^^_p.a) @!\
    @!\
lib^^libname^^_p.a: objlist  @@\
$(RM) $@  @@\
cd profiled; $(AR) ../$@ objlist @@\
$(RANLIB) $@

/*

```

```

* DebuggedLibraryTarget:
* Generate rules to create a debuggable library.
*/
#define DebuggedLibraryTarget(libname,srclist,objlist) @!\
++SOURCES srclist @!\
++OBJECTS objlist @!\
AllTarget(lib^^libname^^_d.a) @!\
    @!\
lib^^libname^^_d.a: objlist  @@\
$(RM) $@    @@\
cd debugger; $(AR) ../$@ objlist @@\
$(RANLIB) $@

/*
* AliasedLibraryTarget:
* Generate rules to link one library to another.
*/
#define AliasedLibraryTarget(libname,alias) @!\
AllTarget(lib^^alias.a) @!\
    @!\
lib^^alias.a:
lib^^libname.a @@\
$(RM) $@    @@\
$(LN) lib^^libname.a $@

/*
* PrelinkedRelocatableTarget:
* Generate rules to produce a relocatable object file instead of a
* library.
*/
#define PrelinkedRelocatableTarget(objname,objlist,libs) @!\
AllTarget(objname.o) @!\
    @!\
objname.o: objlist  @@\
$(RM) $@    @@\
$(LD) $(JLDFLAGS) -r objlist -o $@ libs

/*
* NormalObjectTarget:
* Generate rules to produce a single object file.o from a file.c.
*/
#define NormalObjectTarget(file) @!\
++SOURCES file^^.c @!\
AllTarget(file^^.o) @!\
NormalObjectRule()

```

```

/*
* NormalRelocatableTarget:
* Generate rules to produce a relocatable object file instead of a
* library.
*/
#define NormalRelocatableTarget(objname,objlist) @!\
AllTarget(objname.o) @!\
    @!\
objname.o: objlist  @@\
$(RM) $@  @@\
$(LD) $(JLDFLAGS) -r objlist -o $@

```

```

/*
* ProfiledRelocatableTarget:
* Generate rules to produce a profiled relocatable object file
* instead
* of a library.
*/
#define ProfiledRelocatableTarget(objname,objlist) @!\
AllTarget(objname^^_p.o) @!\
    @!\
objname^^_p.o: objlist  @@\
$(RM) $@  @@\
$(LD) -X -r objlist -o $@

```

```

/*
* DebuggedRelocatableTarget:
* Generate rules to produce a debuggable relocatable object file
* instead of a library.
*/
#define DebuggedRelocatableTarget(objname,objlist) @!\
AllTarget(objname^^_d.o) @!\
    @!\
objname^^_d.o: objlist  @@\
$(RM) $@  @@\
$(LD) -X -r objlist -o $@

```

```

/*
* LintLibraryTarget:
* Generate rules to create a lint library. Note that the lint
* library is always forced to be newer than the library itself.
*/
#define LintLibraryTarget(libname,srclist) @!\
lintlib:: llib-l^^libname.ln @!\
    @!\

```

```

lib-1^^libname.In: srclist @@\
$(RM) $@ @@\
$(LINT) $(LINTLIBFLAG)^^libname $(LINTFLAGS) srclist

/*
* NormalLintTarget:
* Generate rules to lint a set of sources.
*/
#define NormalLintTarget(srclist) @!\
lint:    @@\
$(LINT) $(LINTFLAGS) srclist
$(LINTLIBS)

/*
* LintTarget:
* Generate rules to lint $(SOURCES) (automatically generated)
*/
#define LintTarget() @!\
|once _LintTarget_ @!\
NormalLintTarget($(SOURCES)) @!\
-once

/*
* LinkSourceFile:
* Snag source file from some other directory
*/
#define LinkSourceFile(src,dir) @!\
src: dir/src @@\
$(RM) $@ @@\
$(LN) $? $@ @!\

/*
* MakeSubincludesForBuild:
* Make includes in sub directories.
*/
#define MakeSubincludesForBuild(step,dir,srclist) @!\
step:: dir srclist    @@\
@-(list=`echo srclist | sed -e 's/[^ ]*//g^'; \  @@\
set -x; cd dir; $(RM) $$list)  @@\
@for i in srclist; do \    @@\
(set -x; cd dir; $(LN) ../$$i .) || exit 1; \  @@\
done    @!\
    @!\
MakeDirectories(dir,dir)    @!\

```

```

    @!\
local_realclean::    @@\
@-(if [ -d dir ]; then \    @@\
list=`echo srclist | sed -e 's/[^ ]*///g'; \    @@\
set -x; cd dir; $(RM) $$list; fi)

/*
* CommonSubdirsRule:
* Rule for making $(TARGET) in
every subdirectory, with $(VERB) as
* verbose message and $(FLAGS) as additional flags.
*/
#define CommonSubdirsRule(dirs) @!\
subdirs:    @@\
@case '${MFLAGS}' in *[ik]*) set +e;; esac; \    @@\
for i in dirs ;\    @@\
do \    @@\
(cd $$i ; echo $(VERB) "in $(DIR)$$i..."; \    @@\
$(MAKE) $(MFLAGS) $(FLAGS) $(TARGET)) || exit 1; \    @@\
done

/*
* NamedTargetSubdirsRule:
* Recursively make a series of steps in the specified directories.
*/
#define NamedTargetSubdirsRule(dirs,name,verb,flags) @!\
name::    @@\
@case '${MFLAGS}' in *[ik]*) set +e;; esac; \    @@\
for i in dirs ;\    @@\
do \    @@\
(cd $$i ; echo verb "in $(DIR)$$i..."; \    @@\
$(MAKE) $(MFLAGS) flags name) || exit 1; \    @@\
done

/*
* NamedTargetSubdirs:
* Recursively make a series of steps.
*/
#define NamedTargetSubdirs(name,verb,flags) @!\
name::    @@\
@$(MAKE) subdirs TARGET=name VERB=verb FLAGS=flags

/*
* NamedSubTargetSubdirs:

```

```

* Recursively make a series of steps,
like NamedTargetSubdirs.
* However, the supplied "name" has "sub_" prefixed to it.
*/
#define NamedSubTargetSubdirs(name,verb,flags) @!\
sub_^^name::    @@\
    @$(MAKE) subdirs TARGET=name VERB=verb FLAGS=flags

/*
* NamedDepthTargetSubdirs:
* Recursively make a series of steps. We first enter the
* subdirectories, then perform the local entries.
* The supplied "name" has "sub_" prefixed to it.
*/
#define NamedDepthTargetSubdirs(name,verb,flags) @!\
sub_^^name::    @@\
    @$(MAKE) subdirs TARGET=name VERB=verb FLAGS=flags @@\
    @echo "Back to $(CURRENT) for "name^^...

/*
* MakeSubdirs:
* Generate rules to do makes in the given subdirectories.
*/
#define MakeSubdirs() \
NamedTargetSubdirs(all,"Making all",^^)

/*
* DependDirs:
* Generate rules to recursively compute dependencies as part of the
* make depend step.
*/
#define DependDirs(dirs) \
NamedTargetSubdirsRule(dirs,depend,"Depending",^^)

/*
* DependSubdirs:
* Generate rules to recursively compute dependencies
as part of the
* make depend step.
*/
#define DependSubdirs() \
DependDirs($(SUBDIRS))

/*

```

```

* InstallSubdirs:
* Generate rules to recursively install and deinstall programs and
* files.
*/
#define InstallSubdirs() \
NamedSubTargetSubdirs(install,"Installing",^^) @!\
NamedDepthTargetSubdirs(deinstall,"Deinstalling",^^)

/*
* InstallManSubdirs:
* Generate rules to recursively install and deinstall manual pages.
*/
#define InstallManSubdirs() \
NamedSubTargetSubdirs(install.man,"Installing man pages",^^) @!\
NamedDepthTargetSubdirs(deinstall.man,"Deinstalling man pages",^^)

/*
* IncludesSubdirs:
* Generate rules to recursively put include files in build
*/
#define IncludesSubdirs() \
NamedTargetSubdirs(includes,including,^^)

/*
* CleanSubdirs:
* Generate rules to recursively clean out garbage files.
*/
#define CleanSubdirs() \
NamedDepthTargetSubdirs(clean,"Cleaning",^^) @!\
NamedDepthTargetSubdirs(realclean,"Real cleaning",^^) @!\
NamedDepthTargetSubdirs(clobber,"Clobbering",^^)

/*
* TagSubdirs:
* Generate rules to recursively create tags files.
*/
#define TagSubdirs(dirs) \
NamedTargetSubdirsRule(dirs,tag,"Tagging",^^)

/*
* MakeLintSubdirs:
* Generate rules to recursively lint directories as part of the
* named step.
*/

```

```

#define MakeLintSubdirs(dirs,target) \
NamedTargetSubdirsRule(dirs,target,"Linting",^^)

/*
* LintDirs:
* Generate rules to recursively lint directories as part of the
* make lint step.
*/
#define LintDirs(dirs) \
MakeLintSubdirs(dirs,lint)

/*
* LintSubdirs:
* Generate rules to recursively lint directories as part of the
* make lint step.
*/
#define LintSubdirs() \
LintDirs($(SUBDIRS))

/*
* MakeDirs:
* Creates a set of directories, even if some directories in the path
* do not already exist. There should be no '@!' at the end of the
* '#define' line, because this macro is used *inside* building rules.
*/
#define MakeDirs(dirs) \
@case '${MFLAGS}' in *[i]*) set +e;; esac; \  @@\
for dir in dirs;
do \    @@\
(set -x; test -d $$dir || $(INSTALLDIR) $$dir) || \  @@\
exit 1; \  @@\
done

/*
* _MakeInstallDirs:
* Creates a set of intall directories, even if some directories in the path
* do not already exist. There should be no '@!' at the end of the
* '#define' line, because this macro is used *inside* building rules.
*/
#define _MakeInstallDirs(dirs) \
@case '${MFLAGS}' in *[i]*) set +e;; esac; \  @@\
for dir in dirs; do \    @@\
_MakeInstallDir($$dir) \  @@\
done

```

```

/*
* _MakeInstallDir:
* Internal macro to create a missing install directory.
*/
#define _MakeInstallDir(dir) \
(set -x; test -d $(INSTALL_PREFIX)^dir || \ @@\
$(INSTALLDIR) $(INSTALL_PREFIX)^dir);

/*
* _MakeInstallDirIgnore:
* Same as _MakeInstallDir but handles "make -i" as well.
*/
#define _MakeInstallDirIgnore(dir) \
@case '${MFLAGS}' in *[i]*) set +e;; esac; \ @@\
_MakeInstallDir(dir)

/*
* _RmInstallDirs:
* Removes a set of intall directories.
* There should be no '@!'
at the end of the '#define' line, because this
* macro is used *inside* building rules.
*/
#define _RmInstallDirs(dirs) \
@case '${MFLAGS}' in *[i]*) set +e;; esac; \ @@\
for dir in dirs; do \    @@\
(set -x; test -d $$dir && $(RM) -r $(INSTALL_PREFIX)$dir); \ @@\
done

/*
* MakeDirectories:
* Generate rules to create a hierarchy of directories.
*/
#define MakeDirectories(step,dirs) @!\
step::    @@\
MakeDirs(dirs)

/*
* MakeInstallDirectories:
* Generate a rule to create a set of directories at installation
* time (removed by deinstall).
*/
#define MakeInstallDirectories(dirs) @!\
local_install::    @@\
_MakeInstallDirs(dirs) @!\
    @!\
local_deinstall::    @@\

```

`_RmInstallDirs(dirs)`

```
/*
* MakeLintLibSubdirs:
* Generate rules to recursively create lint libraries.
*/
#define MakeLintLibSubdirs(dirs) @!\
MakeLintSubdirs(dirs,lintlib)

/*
* MakeMakeSubdirs:
* Generate rules to recursively recreate target as part of the
* specified step in the build.
  This assumes Makefile.SH has
* already been built (which is the case for a delivery), but does
* not rely on the existence of a Makefile.
*/
#define MakeMakeSubdirs(target) @!\
target::    @@\
  @case '${MFLAGS}' in *[ik]*) set +e;; esac; \ @@\
  for i in $(SUBDIRS); \  @@\
  do \    @@\
  echo "Making "target" in $(DIR)$$i..."; \ @@\
  (cd $$i || exit 1; \  @@\
  if test ! -f Makefile; then /bin/sh Makefile.SH; fi; \ @@\
  $(MAKE) $(MFLAGS) target) || exit 1; \ @@\
done

/*
* MakeMakefilesSH:
* Generate rules to recursively recreate target as part of the
* specified step in the build. If $(TOP) is set to an absolute
* path, don't prepend the ../ prefix. This makes running things
* outside of the source tree to be much easier.
*/
#define MakeMakefilesSH() @!\
Makefiles.SH: Makefile.SH  @@\
  @case '${MFLAGS}' in *[ik]*) set +e;; esac; \ @@\
  for i in $(SUBDIRS); \  @@\
  do \    @@\
  case "$(DIR)$$i/" in \    @@\
  ^^*^^/^^*^^/^^*^^/^^*^^) newtop=../..../;;
  \ @@\
  ^^*^^/^^*^^/^^*^^) newtop=../..../; \  @@\
  ^^*^^/^^*^^) newtop=../..../; \  @@\
```

```

*^)/ newtop=..;; \    @@\
esac; \    @@\
case "$(TOP)" in \    @@\
/^^*) newtop="$(TOP)" ;; \    @@\
esac; \    @@\
echo "Making Makefiles.SH in $(DIR)$Si..."; \    @@\
(cd $Si || exit 1; \    @@\
if test -f Jmakefile; then \    @@\
$(MAKE) $(MFLAGS) -f ../Makefile \    @@\
Makefile TOP=$$newtop CURRENT=$(DIR)$Si && \    @@\
$(MAKE) $(MFLAGS) Makefiles.SH; \    @@\
fi; \    @@\
) || exit 1; \    @@\
done

```

```

/*
* MakefileSubdirs:
* Generate rules to create Makefiles.
*/
#define MakefileSubdirs() @!\
MakeMakeSubdirs(Makefiles) @!\
MakeMakefilesSH()

```

```

/*
* CppScriptTarget:
* Generate rules to create a shell script by running the input
* through cpp.
*/
#define CppScriptTarget(dst,src,defs,deplist) @!\
dst:: src deplist    @@\
$(RM) $@    @@\
$(CPP) defs <src | \    @@\
sed -e '/^# *[0-9][0-9]* *.*$$/d' >$@    @@\
chmod a+x $@

```

```

/*
* MakeScriptFromCpp:
* Generate rules to create a script from a file with a
* .cpp suffix.
*/
#define MakeScriptFromCpp(name,defs) @!\
CppScriptTarget(name,name.cpp,defs,^^)

```

```

/*

```

```

* ShellScriptTargetExt:
* Generate rules to create and install a set of scripts from
* ext files (.sh and .SH are the most common examples). Man pages
* derived from the name of the scripts are also installed unless
* NoManPages() is specified.
*/
#define ShellScriptTargetExt(scripts,ext) @!\
++SCRIPTS scripts @!\
SimpleShellScriptTargetExt(scripts,ext) @!\
InstallScripts() @!\
InstallManScripts()

/*
* ShellScriptTarget:
* Generate rules to create and install a set of scripts from
* .SH files. Man pages derived from the name of the scripts are
* also installed unless NoManPages() is specified.
*/
#define ShellScriptTarget(scripts) @!\
ShellScriptTargetExt(scripts,.SH)

/*
* SimpleShellScriptTargetExt:
* Generate rules to create a set of scripts from ext files where
* ext is usually
* something like .sh or .SH, or whatever file
* extension you like..
*/
#define SimpleShellScriptTargetExt(scripts,ext) @!\
AllTarget(scripts) @!\
    @!\
|expand s!scripts! @!\
!s: !s^^ext @@\
/bin/sh !s^^ext @!\
    @!\
-expand

/*
* SimpleShellScriptTarget:
* Generate rules to create a set of scripts from .SH files.
*/
#define SimpleShellScriptTarget(scripts) @!\
SimpleShellScriptTargetExt(scripts,.SH)

```

```

/*
* ShellScriptLongTarget:
* Generate rules to create a set of scripts from .SH files where
* the name of the generated file is different from the basename of
* the .SH file (when, for instance, the total length with the .SH
* extension would not leave enough space for RCS ,v extension).
*/
#define ShellScriptLongTarget(basename,scriptname) @!\
++LSCRIPTS scriptname @!\
AllTarget(scriptname) @!\
    @!\
scriptname: basename^^.SH @@\
/bin/sh basename^^.SH @!\
    @!\
InstallScripts() @!\
?NOMAN:|skip @!\
InstallManPageLong(basename,$(MANSRC),scriptname) @!\
-skip

/*
* ForceTarget:
* The force target will force reconstruction of all the other
* targets which include .FORCE in their own dependencies.
*/
#define ForceTarget() @!\
|once _force_ @!\
.FORCE: @!\
    @!\
-once

/*
* RemoteTargetDependency:
* A local target may rely on a remote dependency (e.g. a library)
* made in a separate directory. This rule explicits the dependency
* and forces a make of that dependency in the remote directory.
*/
#define RemoteTargetDependency(target,directory,dependency) @!\
RemoteDependency(directory,dependency) @!\
target: directory/^^^dependency @!\

/*
* RemoteDependency:
* Specify rules for making a remote dependency.
*/
#define RemoteDependency(directory,dependency) @!\

```

```

ForceTarget()    @!\
|once =directory/^^^dependency= @!\
directory/^^^dependency: .FORCE  @@\
    @echo "Checking "^^^dependency" in "^^^directory"..." @@\
cd ^^directory; $(MAKE) ^^dependency @@\
    @echo "Continuing in $(CURRENT)..." @!\
    @!\
-once

/*
 * SetSubdirs:
 * Actually forces the definition of SUBDIRS, and lets the user
 * specify what the sub-directories are. This will be added to the
 * customization part.
 */
#define SetSubdirs(subdirs) @!\
>SUBDIRS @!\
+SUBDIRS = subdirs

/*
 * NoManPages:
 * Actually forces the definition of NOMAN, which tells the jmake
 * program to not generate rules for installing manual pages.
 */
#define NoManPages() @!\
>NOMAN

/*
 * Expand:
 * This powerful macro expands the `rule' given a `pattern'. It
 * relies on a built-in command in jmake. The expansion is
 * documented in the short notes file that comes with jmake and
 * gives some insights on the internal syntax.
 */
#define Expand(rule, pattern) @!\
|expand pattern @!\
rule @!\
-expand

/*
 * Lex and yacc stuff.
 */

/*
 * YaccRule:

```

```

* This is the rule which is used to build a .c file from a .y file.
*/
#define YaccRule() @!\
AddSuffix(.y) @!\
|once _YaccRule_ @!\
|rule:.y.c: @!\
|rule: $(YACC) $(JYFLAGS)
$< @!\
|rule: $(MV) y.tab.c $@ @!\
|rule: @!\
-once

/*
* SimpleYaccTarget:
* Declare a yacc base.y file to be used in the building of the
* specified target program. The source file must be given without
* its final .y extension. The name of the .c and .o will be
* derived from the source file basename provided.
*/
#define SimpleYaccTarget(program,base) @!\
++SOURCES base.y @!\
++OBJECTS base.o @!\
YaccRule() @!\
program: base.c @!\
    @!\
local_realclean:: @@\
$(RM) base.c @!\

/*
* ComplexYaccTarget:
* Declare a yacc base.y file to be used in the building of the
* specified target program. The source file must be given without
* its final .y extension. The name of the .c and .o will be
* derived from the source file basename provided.
* The difference with SimpleYaccTarget is the identifying process
* where all the 'yy' are replaced by the specified prefix.
*/
#define ComplexYaccTarget(program,base,prefix) @!\
++SOURCES base.y @!\
++OBJECTS base.o
    @!\
program: base.c @!\
    @!\
base.c: base.y @@\
$(YACC) $(JYFLAGS) base.y @@\
$(SED) -e 's/yy\(.)/prefix\1/g' < y.tab.c > base.c @@\
$(SED) -e 's/yy\(.)/prefix\1/g' < y.tab.h > base.h @@\

```

```
$(RM) y.tab.c y.tab.h @!\
    @!\
local_realclean:: @@\
$(RM) base.c @!\
```

```
/*
```

```
* SimpleYaccInclude:
* Declare that program will need an include file produced by
* the output of yacc on base.y, which typically produces a file
* named y.tab.h, which will be renamed as base.h.
* The only problem is that the dependencies towards base.h have
* to be manually given in the Jmakefile.
```

```
*/
```

```
#define SimpleYaccInclude(base) @!\
base.h: base.c @@\
@if test -f y.tab.h; then \ @@\
    echo " $(MV) y.tab.h $@"; \ @@\
    $(MV) y.tab.h $@; \ @@\
fi    @!\
    @!\
local_realclean::  @@\
$(RM) base.h
```

```
/*
```

```
* ComplexYaccInclude:
* Declare that program will need an include file produced by
* the output of yacc on base.y, which typically produces a file
* named y.tab.h, which will
* be renamed as base.h.
* The difference with SimpleYaccInclude is the identifying process
* of the y.tab.h file where all 'yy' are renamed to prefix.
* The only problem is that the dependencies towards base.h have
* to be manually given in the Jmakefile.
```

```
*/
```

```
#define ComplexYaccInclude(base,prefix) @!\
base.h: base.c @@\
@if test -f y.tab.h; then \ @@\
    echo " $(SED) -e 's/yy\(.)/prefix\1/g' < y.tab.h > base.h"; \ @@\
    $(SED) -e 's/yy\(.)/prefix\1/g' < y.tab.h > base.h; \ @@\
    echo " $(RM) y.tab.h"; \ @@\
    $(RM) y.tab.h; \ @@\
elif test -f base.h; then \ @@\
    echo " $(CP) base.h base.ht"; \ @@\
    $(CP) base.h base.ht; \ @@\
    echo " $(SED) -e 's/yy\(.)/prefix\1/g' < base.ht > base.h"; \ @@\
    $(SED) -e 's/yy\(.)/prefix\1/g' < base.ht > base.h; \ @@\
    echo " $(RM) base.ht"; \ @@\
```

```
$(RM) base.ht; \ @@\
fi @!\
 @!\
local_realclean:: @@\
$(RM) base.h
```

```
/*
 * NormalYaccTarget:
 * Declare a yacc base.y file which should produce a base.c and
 * base.h file
 * as derived from the output of yacc, to be used by
 * the specified program.
 */
#define NormalYaccTarget(program,base) @!\
SimpleYaccTarget(program,base) @!\
SimpleYaccInclude(base)
```

```
/*
 * IdentifiedYaccTarget:
 * Declare a yacc base.y file which should produce a base.c and
 * base.h file as derived from the output of yacc, to be used by
 * the specified program. The specified prefix is used to remplace
 * all the 'yy' in the generated file, for use when more than a
 * single parser is needed in one executable.
 */
#define IdentifiedYaccTarget(program,base,prefix) @!\
ComplexYaccTarget(program,base,prefix) @!\
ComplexYaccInclude(base,prefix)
```

```
/*
 * SimpleLexTarget:
 * This declares a lex base.l file which is to be ran through
 * lex to produce a base.c file.
 */
#define SimpleLexTarget(program,base) @!\
++SOURCES base.l @!\
++OBJECTS base.o @!\
|once _LexRule_ @!\
|rule:.l.c: @!\
|rule:$(LEX)$(JLFLAGS)$< @!\
|rule:$(MV)lex.yy.c$@ @!\
|rule: @!\
-once @!\
AddSuffix(.l) @!\
program:
```

```

base.c @!\
    @!\
local_realclean:: @@\
$(RM) base.c @!\

/*
* IdentifiedLexTarget:
* This declares a lex base.l file which is to be ran through
* lex to produce a base.c file. The prefix is used to replace
* the 'yy', so that the lexical analyzer may be identified.
*/
#define IdentifiedLexTarget(program,base,prefix) @!\
++SOURCES base.l @!\
++OBJECTS base.o @!\
program: base.c @!\
    @!\
base.c: base.l @@\
$(LEX) $(JLFLAGS) base.l @@\
$(SED) -e 's/yy\(.)/prefix\1/g' < lex.yy.c > base.c @@\
$(RM) lex.yy.c @!\
    @!\
local_realclean:: @@\
$(RM) base.c @!\

/*
* NormalLexDependTarget:
* Declare that program will need an include file produced by
* the output of lex on base.l, which typically produces a file
* named lex.yy.c which will be renamed as base.c. Besides, the
* lexical analyzer needs the file parser.h produced by running
* parser.y through yacc and renaming y.tab.h as parser.h.
*/
#define NormalLexDependTarget(program,base,parser)
    @!\
base.o: parser.h @!\
    @!\
SimpleLexTarget(program,base)

/*
* IdentifiedLexDependTarget:
* Declare that program will need an include file produced by
* the output of lex on base.l, which typically produces a file
* named lex.yy.c which will be renamed as base.c. Besides, the
* lexical analyzer needs the file parser.h produced by running
* parser.y through yacc and renaming y.tab.h as parser.h.

```

```

* The lexical analyzer is identified with the supplied prefix,
* which replaces the regular 'yy' prefix in the symbol names.
*/
#define IdentifiedLexDependTarget(program,base,parser,prefix) @!\
base.o: parser.h @!\
    @!\
IdentifiedLexTarget(program,base,prefix)

/*
* NormalParserTarget:
* Specify that program is using the lex/yacc combination to
* produce a parser. The lexic and parser parameters are the
* base name of the .l and .y file, respectively.
*/
#define NormalParserTarget(program,lexic,parser) @!\
NormalLexDependTarget(program,lexic,parser)
    @!\
NormalYaccTarget(program,parser)

/*
* IdentifiedParserTarget:
* Specify that program is using the lex/yacc combination to
* produce a parser. The lexic and parser parameters are the
* base name of the .l and .y file, respectively. The parser
* produced is identified via its prefix, which replaces all
* the normally supplied 'yy' prefix, hence making it possible
* to have multiple parsers in a single executable.
*/
#define IdentifiedParserTarget(program,lexic,parser,prefix) @!\
IdentifiedLexDependTarget(program,lexic,parser,prefix) @!\
IdentifiedYaccTarget(program,parser,prefix)

```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/files/Imake.rules
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_chown.U 1 2006-08-24 12:32:52Z rmanfredi \$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic Licence,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic Licence; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:
?RCS: Original Author: Andy Dougherty <doughera@lafcol.lafayette.edu>
?RCS:
?RCS: \$Log: d_chown.U,v \$
?RCS: Revision 3.0.1.1 1994/08/29 16:07:14 ram
?RCS: patch32: created by ADO
?RCS:
?MAKE:d_chown: Inlibc
?MAKE: -pick add \$@ %<
?S:d_chown:
?S: This variable conditionally defines the HAS_CHOWN symbol, which
?S: indicates to the C program that the chown() routine is available.
?S:.
?C:HAS_CHOWN :
?C: This symbol, if defined, indicates that the chown routine is
?C: available.
?C:.
?H:#\$d_chown
HAS_CHOWN /**/
?H:.
?LINT:set d_chown
: see if chown exists
set chown d_chown
eval \$inlibc

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/d_chown.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: \$Log: d_strerror.U,v \$
?RCS: Revision 3.0.1.3 1994/05/13 15:20:27 ram
?RCS: patch27: now uses new macro support for cleaner Strerror def
?RCS:
?RCS: Revision 3.0.1.2 1994/05/06 14:58:26 ram
?RCS: patch23: renamed strerror into Strerror to protect name space (ADO)
?RCS:
?RCS: Revision 3.0.1.1 1994/01/24 14:08:56 ram

?RCS: patch16: protected code looking for sys_errnolist[] with @if

?RCS: patch16: added default value for d_syserrlst

?RCS:

?RCS: Revision 3.0 1993/08/18 12:07:35 ram

?RCS: Baseline

for dist 3.0 netwide release.

?RCS:

?MAKE:d_strerror d_syserrlst d_syserrlst d_strerror: contains Csym Findhdr

?MAKE: -pick add \$@ %<

?S:d_strerror:

?S: This variable conditionally defines HAS_STRERROR if strerror() is

?S: available to translate error numbers to strings.

?S:.

?S:d_syserrlst:

?S: This variable conditionally defines HAS_SYS_ERRLIST if sys_errlist[] is

?S: available to translate error numbers to strings.

?S:.

?S:d_syserrlst:

?S: This variable conditionally defines HAS_SYS_ERRNOLIST if sys_errnolist[]

?S: is available to translate error numbers to the symbolic name.

?S:.

?S:d_strerror:

?S: This variable holds what Strerrr is defined as to translate an error

?S: code condition into an error message string. It could be 'strerror'

?S: or a more complex macro emulating strrror with sys_errlist[], or the

?S: "unknown" string when both strerror and sys_errlist are missing.

?S:.

?C:HAS_STRERROR (STRERROR):

?C: This symbol, if defined, indicates that the strerror routine is

?C: available

to translate error numbers to strings. See the writeup

?C: of Strerror() in this file before you try to define your own.

?C:.

?C:HAS_SYS_ERRLIST (SYSERRLIST):

?C: This symbol, if defined, indicates that the sys_errlist array is

?C: available to translate error numbers to strings. The extern int

?C: sys_nerr gives the size of that table.

?C:.

?C:HAS_SYS_ERRNOLIST (SYSERRNOLIST):

?C: This symbol, if defined, indicates that the sys_errnolist array is

?C: available to translate an errno code into its symbolic name (e.g.

?C: ENOENT). The extern int sys_nerrno gives the size of that table.

?C:.

?C:Strerror:

?C: This preprocessor symbol is defined as a macro if strerror() is

?C: not available to translate error numbers to strings but sys_errlist[]

?C: array is there.

?C:.

```

?H:#$d_strerror HAS_STRERROR /**/
?H:#$d_syserrlst HAS_SYS_ERRLIST /**/
?H:#$d_syserrnlst HAS_SYS_ERRNOLIST /**/
?H:#define Strerror(e) $d_strerror
?H:
?D:d_syserrnlst=""
?T:xxx val
: see if strerror and/or sys_errlist[]
  exist
  echo " "
  if set strerror val -f d_strerror; eval $scsym; $val; then
    echo 'strerror() found.' >&4
    d_strerror="$define"
    d_strerrorm='strerror(e)'
    if set sys_errlist val -a d_syserrlst; eval $scsym; $val; then
      echo "(You also have sys_errlist[], so we could roll our own strerror.)"
      d_syserrlst="$define"
    else
      echo "(Since you don't have sys_errlist[], sterror() is welcome.)"
      d_syserrlst="$undef"
    fi
  elif xxx=`./findhdr string.h`; test "$xxx" || xxx=`./findhdr strings.h`; \
  $contains '#[ ]*define.*strerror' "$xxx" >/dev/null 2>&1; then
    echo 'strerror() found in string header.' >&4
    d_strerror="$define"
    d_strerrorm='strerror(e)'
    if set sys_errlist val -a d_syserrlst; eval $scsym; $val; then
      echo "(Most probably, strerror() uses sys_errlist[] for descriptions.)"
      d_syserrlst="$define"
    else
      echo "(You don't appear to have any sys_errlist[], how can this be?)"
      d_syserrlst="$undef"
    fi
  elif set sys_errlist val -a d_syserrlst; eval $scsym; $val; then
    echo "strerror()
    not found, but you have sys_errlist[] so we'll use that." >&4
    d_strerror="$undef"
    d_syserrlst="$define"
    d_strerrorm='((e)<0||(e)>=sys_nerr?"unknown":sys_errlist[e])'
  else
    echo 'strerror() and sys_errlist[] NOT found.' >&4
    d_strerror="$undef"
    d_syserrlst="$undef"
    d_strerrorm=""unknown""
  fi
  @if d_syserrnlst || HAS_SYS_ERRNOLIST
  if set sys_errnolist val -a d_syserrnlst; eval $scsym; $val; then
    echo "(Symbolic error codes can be fetched via the sys_errnolist[] array.)"

```

```
d_sysernlst="$define"
else
echo "(However, I can't extract the symbolic error code out of errno.)"
d_sysernlst="$undef"
fi
@end
```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/d_strerror.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: d_euc2jis.U 1 2006-08-24 12:32:52Z rmanfredi $
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: $Log: d_euc2jis.U,v $
?RCS: Revision 3.0 1993/08/18 12:05:58 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:d_euc2jis: Inlibc
?MAKE: -pick add $@ %<
?S:d_euc2jis:
?S: This variable conditionally defines the HAS_EUC2JIS symbol, which
?S: indicates to the C program that the euc2jis() routine is available
?S: to convert EUC to JIS.
?S:.
?C:HAS_EUC2JIS:
?C: This symbol, if defined, indicates that the euc2jis routine is
?C: available to convert
EUC to JIS.
?C:.
?H:#$d_euc2jis HAS_EUC2JIS /**/
?H:.
?LINT:set d_euc2jis
: see if euc2jis exists
set euc2jis d_euc2jis
eval $inlibc
```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/d_euc2jis.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id$
?RCS:
?RCS: Copyright (c) 2000 Jarkko Hietaniemi
?RCS:
?RCS: You may distribute under the terms of either the GNU General Public
?RCS: License or the Artistic License, as specified in the README file.
?RCS:
?MAKE:d_ualarm: Inlibc
?MAKE:-pick add $@ %<
?S:d_ualarm:
?S: This variable conditionally defines the HAS_UALARM symbol, which
?S: indicates to the C program that the ualarm() routine is available.
?S:.
?C:HAS_UALARM:
?C: This symbol, if defined, indicates that the ualarm routine is
?C: available to do alarms with microsecond granularity.
?C:.
?H:#$d_ualarm HAS_UALARM /**/
?H:.
?LINT:set d_ualarm
: see if ualarm exists
set ualarm d_ualarm
eval $inlibc
```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/perl/d_ualarm.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id$
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: Copyright (c) 2000, Jarkko Hietaniemi
?RCS:
?X:
?X: This unit allows the duplication of the source tree to the current
?X: directory via symbolic links. This must be requested explicitly
?X: by them issuing a -Dmksymlinks on the command line.
?X:
```



```

-s $pkgsrc/$filename $filename
fi
done
?X: Check that everything was correctly copied
echo "(Checking current directory...)" >&4
cd UU
awk '$1 !~ /PACK[A-Z]+/ {print $1}' "$rsrc/MANIFEST" | \
(split -l 50 2>/dev/null || split -50)
rm -f missing
tmppwd=`pwd`
for filelist in x??: do
(cd ..; ls `cat "$tmppwd/$filelist" ` \
>/dev/null 2>>"$tmppwd/missing")
done
if test -s missing; then
echo "Failed duplication of source tree. Aborting." >&4
exit 1
fi
;;
*) echo "(I cannot figure out how to do symbolic links, ignoring!)" >&4
;;
esac
;;
esac
;;
esac
@end

```

Found in path(s):

```

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/Mksymlinks.U

```

No license file was found, but licenses were detected in source scan.

```

?RCS: $Id: d_drاند48_r.U,v 0RCS:
?RCS: Copyright (c) 2002,2003 Jarkko Hietaniemi
?RCS:
?RCS: You may distribute under the terms of either the GNU General Public
?RCS: License or the Artistic License, as specified in the README file.
?RCS:
?RCS: Generated by the reentr.pl from the Perl 5.8 distribution.
?RCS:
?MAKE:d_drاند48_r drاند48_r_proto: Inlibc Protochk Hasproto i_systypes \
usethreads i_stdlib extern_C
?MAKE: -pick add $@ %<
?S:d_drاند48_r:
?S: This variable conditionally defines the HAS_DRAND48_R symbol,
?S: which indicates to the C program that the drاند48_r()

```

?S: routine is available.

?S:.

?S:drand48_r_proto:

?S: This variable encodes the prototype of drand48_r.

?S: It is zero if d_drand48_r is undef, and one of the

?S: REENTRANT_PROTO_T_ABC macros of reentr.h if d_drand48_r

?S: is defined.

?S:.

?C:HAS_DRAND48_R:

?C: This symbol, if defined, indicates that the drand48_r routine

?C: is available to drand48 re-entrantly.

?C:.

?C:DRAND48_R_PROTO:

?C: This

symbol encodes the prototype of drand48_r.

?C: It is zero if d_drand48_r is undef, and one of the

?C: REENTRANT_PROTO_T_ABC macros of reentr.h if d_drand48_r

?C: is defined.

?C:.

?H:#\$d_drand48_r HAS_DRAND48_R /**/

?H:#define DRAND48_R_PROTO \$drand48_r_proto /**/

?H:.

?T:try hdrs d_drand48_r_proto

: see if drand48_r exists

set drand48_r d_drand48_r

eval \$inlibc

case "\$d_drand48_r" in

"\$define")

hdrs="\$i_systypes sys/types.h define stdio.h \$i_stdlib stdlib.h"

case "\$d_drand48_r_proto:\$usethreads" in

":define") d_drand48_r_proto=define

set d_drand48_r_proto drand48_r \$hdrs

eval \$hasproto ;;

*) ;;

esac

case "\$d_drand48_r_proto" in

define)

case "\$drand48_r_proto" in

"|0) try='int drand48_r(struct drand48_data*, double*);'

./protochk "\$extern_C \$try" \$hdrs && drand48_r_proto=I_ST ;;

esac

case "\$drand48_r_proto" in

"|0) d_drand48_r=undef

drand48_r_proto=0

echo "Disabling drand48_r, cannot determine prototype."

>&4 ;;

*) case "\$drand48_r_proto" in

REENTRANT_PROTO*) ;;

```

*) drand48_r_proto="REENTRANT_PROTO_${drand48_r_proto}";
esac
echo "Prototype: $try" ;;
esac
;;
*) case "$susetthreads" in
define) echo "drand48_r has no prototype, not using it." >&4 ;;
esac
d_drand48_r=undef
drand48_r_proto=0
;;
esac
;;
*) drand48_r_proto=0
;;
esac

```

Found in path(s):

```

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/threads/d_drand48_r.U

```

No license file was found, but licenses were detected in source scan.

```

?RCS: $Id: d_strxfrm.U 1 2006-08-24 12:32:52Z rmanfredi $
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: Original Author: Andy Dougherty <doughera@lafcol.lafayette.edu>
?RCS:
?RCS: $Log: d_strxfrm.U,v $
?RCS: Revision 3.0.1.1 1994/08/29 16:12:04 ram
?RCS: patch32: created by ADO
?RCS:
?MAKE:d_strxfrm: Inlibc
?MAKE: -pick add $@ %<
?S:d_strxfrm:
?S: This variable conditionally defines HAS_STRXFRM if strxfrm() is
?S: available to transform strings.
?S:.
?C:HAS_STRXFRM:
?C: This symbol, if defined, indicates that the strxfrm() routine is
?C: available to transform

```

```
strings.  
?C:.  
?H:#$d_strxfrm HAS_STRXFRM /**/  
?H:.  
?LINT:set d_strxfrm  
: see if strxfrm exists  
set strxfrm d_strxfrm  
eval $inlibc
```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/d_strxfrm.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id$  
?RCS:  
?RCS: Copyright (c) 1998 Jarkko Hietaniemi  
?RCS:  
?RCS: You may distribute under the terms of either the GNU General Public  
?RCS: License or the Artistic License, as specified in the README file.  
?RCS:  
?MAKE:d_fseeko: Inlibc longsize  
?MAKE:-pick add $@ %<  
?S:d_fseeko:  
?S: This variable conditionally defines the HAS_FSEEKO symbol, which  
?S: indicates to the C program that the fseeko() routine is available.  
?S:.  
?C:HAS_FSEEKO:  
?C: This symbol, if defined, indicates that the fseeko routine is  
?C: available to fseek beyond 32 bits (useful for ILP32 hosts).  
?C:.  
?H:#$d_fseeko HAS_FSEEKO /**/  
?H:.  
?LINT:set d_fseeko  
: see if fseeko exists  
set fseeko d_fseeko  
eval $inlibc  
case "$longsize" in  
8) echo "(Your long is 64 bits, so you could use fseek.)" ;;  
esac
```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_fseeko.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id$  
?RCS:
```

?RCS: Copyright (c) 1999 Jarkko Hietaniemi
?RCS:
?RCS: You may distribute under the terms of either the GNU General Public
?RCS: License or the Artistic License, as specified in the README file.
?RCS:
?MAKE:d_llseek: Inlibc
?MAKE: -pick add \$@ %<
?S:d_llseek:
?S: This variable conditionally defines the HAS_LLSEEK symbol, which
?S: indicates to the C program that the llseek() routine is available.
?S:.
?C:HAS_LLSEEK:
?C: This symbol, if defined, indicates that the llseek routine is
?C: available to seek files larger than 2 gigabytes.
?C:.
?H:#\$d_llseek HAS_LLSEEK /**/
?H:.
?LINT:set d_llseek
: see if llseek exists
set llseek d_llseek
eval \$inlibc

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_llseek.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: i_semaphore.U,v \$
?RCS:
?RCS: Copyright (c) 1999 Jarkko Hietaniemi
?RCS:
?RCS: You may distribute under the terms of either the GNU General Public
?RCS: License or the Artistic License, as specified in the README file.
?RCS:
?MAKE:i_semaphore: Inhdr Hasfield
?MAKE: -pick add \$@ %<
?S:i_semaphore:
?S: This variable conditionally defines the I_SEMAPHORE symbol, and indicates
?S: whether a C program should include <semaphore.h>.
?S:.
?C:I_SEMAPHORE:
?C: This symbol, if defined, indicates that <semaphore.h> exists and
?C: should be included.
?C:.
?H:#\$i_semaphore I_SEMAPHORE /**/
?H:.
?LINT:set i_semaphore
: see if this is a semaphore.h system

```
set semaphore.h i_semaphore
eval $inhdr
```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/perl/i_semaphore.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: d_loconv.U 1 2006-08-24 12:32:52Z rmanfredi $
```

```
?RCS:
```

```
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
```

```
?RCS:
```

```
?RCS: You may redistribute only under the terms of the Artistic Licence,
```

```
?RCS: as specified in the README file that comes with the distribution.
```

```
?RCS: You may reuse parts of this distribution only within the terms of
```

```
?RCS: that same Artistic Licence; a copy of which may be found at the root
```

```
?RCS: of the source tree for dist 4.0.
```

```
?RCS:
```

```
?RCS: Original Author: Andy Dougherty <doughera@lafcol.lafayette.edu>
```

```
?RCS:
```

```
?RCS: $Log: d_loconv.U,v $
```

```
?RCS: Revision 3.0.1.1 1994/10/29 16:14:11 ram
```

```
?RCS: patch36: created by ADO
```

```
?RCS:
```

```
?MAKE:d_loconv: Inlibc
```

```
?MAKE: -pick add $@ %<
```

```
?S:d_loconv:
```

```
?S: This variable conditionally defines HAS_LOCALECONV if localeconv() is
```

```
?S: available for numeric and monetary formatting conventions.
```

```
?S:.
```

```
?C:HAS_LOCALECONV:
```

```
?C: This symbol, if defined, indicates that the localeconv
routine is
```

```
?C: available for numeric and monetary formatting conventions.
```

```
?C:.
```

```
?H:#$d_loconv HAS_LOCALECONV /**/
```

```
?H:.
```

```
?LINT:set d_loconv
```

```
: see if localeconv exists
```

```
set localeconv d_loconv
```

```
eval $inlibc
```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/d_loconv.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: rootid.U 1 2006-08-24 12:32:52Z rmanfredi $
```

```

?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: $Log: rootid.U,v $
?RCS: Revision 3.0.1.1 1995/01/30 14:45:36 ram
?RCS: patch49: now only prints a single empty line when outputting something
?RCS:
?RCS: Revision 3.0 1993/08/18 12:09:42 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:rootid: sed
?MAKE: -pick add $@ %<
?S:rootid:
?S: This variable contains the eventual value of the ROOTID symbol,
?S: which is the uid of root.
?S:.
?C:ROOTID:
?C: This symbol contains the uid of root, normally
0.
?C:.
?H:#define ROOTID $rootid /**/
?H:.
: determine root id
rootid=`$sed -e "/^root:/{s/^[^:]*:[^:]*\([[:^:]]*\).*$""\1/" -e "q" -e "}" -e "d" </etc/passwd
case "$rootid" in
") rootid=0 ;;
*) echo " "; echo "Root uid = $rootid" >&4 ;;
esac

```

Found in path(s):

```

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/rootid.U

```

No license file was found, but licenses were detected in source scan.

```

?RCS: $Id: d_newsadm.U 1 2006-08-24 12:32:52Z rmanfredi $
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root

```

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: d_newsadm.U,v \$

?RCS: Revision 3.0.1.2 1997/02/28 15:36:53 ram

?RCS: patch61: added Guess dependency

?RCS:

?RCS: Revision 3.0.1.1 1994/10/29 16:14:33 ram

?RCS: patch36: call ./eunice explicitly instead of relying on PATH

?RCS:

?RCS: Revision 3.0 1993/08/18 12:06:42 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?MAKE:d_newsadm newsadmin: cat contains Guess Setvar Myread Oldconfig

?MAKE: -pick add \$@ %<

?S:d_newsadm:

?S: This variable
conditionally defines the NEWS_ADMIN symbol, which

?S: indicates to the C program that there is a user who is in charge

?S: of news administration.

?S:.

?S:newsadmin:

?S: This variable holds the login name of the news administrator, if any.

?S:.

?C:NEWS_ADMIN (NEWSADMIN):

?C: This symbol, if defined, contains the login name of the news
administrator.

?C:.

?H:#\$d_newsadm NEWS_ADMIN "\$newsadmin" /**/

?H:.

?LINT:set d_newsadm

```
: get news administrator name
case "$newsadmin" in
")
if $contains "^news:" /etc/passwd >/dev/null 2>&1 ; then
dflt=news
elif $contains "^usenet:" /etc/passwd >/dev/null 2>&1 ; then
dflt=usenet
elif ./eunice; then
dflt=system
else
dflt=root
fi
;;
*)
dflt="$newsadmin"
;;
esac
$cat <<'EOM'
```

Many systems keep their news in a private directory, or have a non-superuser in charge of administering news. (If you don't have such a user, take the default answer.) I need the login name (not directory) which is used for news administration.

EOM

```
rp="News
admin login?"
./myread
newsadmin="$ans"
case "$newsadmin" in
root) val="$undef" ;;
*) val="$define" ;;
esac
set d_newsadm
eval $setvar
```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/d_newsadm.U
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1998 Jarkko Hietaniemi

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

```
?MAKE:d_fgetpos64 d_fopen64 d_freopen64 d_fseek64 d_fseeko64 d_fsetpos64 \
d_ftell64 d_ftello64 d_tmpfile64: Inlibc use64bitint Setvar test
```

```
?MAKE: -pick add $@ %<
```

?S:d_fgetpos64:

?S: This variable conditionally defines the HAS_FGETPOS64 symbol, which

?S: indicates to the C program that the fgetpos64() routine is available.

?S:.

?S:d_fopen64:

?S: This variable conditionally defines the HAS_FOPEN64 symbol, which

?S: indicates to the C program that the fopen64() routine is available.

?S:.

?S:d_freopen64:

?S: This variable conditionally defines the HAS_FREOPEN64 symbol, which

?S: indicates to the C program that the freopen64() routine is available.

?S:.

?S:d_fseek64:

?S: This variable conditionally defines

the HAS_FSEEK64 symbol, which

?S: indicates to the C program that the fseek64() routine is available.

?S:.

?S:d_fseeko64:

?S: This variable conditionally defines the HAS_FSEEKO64 symbol, which

?S: indicates to the C program that the fseeko64() routine is available.

?S:.

?S:d_fsetpos64:

?S: This variable conditionally defines the HAS_FSETPOS64 symbol, which

?S: indicates to the C program that the fsetpos64() routine is available.

?S:.

?S:d_ftell64:

?S: This variable conditionally defines the HAS_FTELL64 symbol, which

?S: indicates to the C program that the ftell64() routine is available.

?S:.

?S:d_ftello64:

?S: This variable conditionally defines the HAS_FTELLO64 symbol, which

?S: indicates to the C program that the ftello64() routine is available.

?S:.

?S:d_tmpfile64:

?S: This variable conditionally defines the HAS_TMPFILE64 symbol, which

?S: indicates to the C program that the tmpfile64() routine is available.

?S:.

?C:HAS_FGETPOS64:

?C: This symbol, if defined, indicates that the fgetpos64 routine is

?C: available to getpos files larger than 2 gigabytes.

?C:.

?C:HAS_FOPEN64:

?C: This symbol, if defined, indicates that the fopen64 routine is

?C: available to open files larger than 2 gigabytes.

?C:.

?C:HAS_FREOPEN64:

?C: This symbol, if defined, indicates that the freopen64 routine is

?C: available to reopen files larger than 2 gigabytes.

?C:.

?C:HAS_FSEEK64:

?C: This symbol, if defined, indicates that the fseek64 routine is

?C: available to seek files larger than 2 gigabytes.

?C:.

?C:HAS_FSEEKO64:

?C: This symbol, if defined, indicates that the fseeko64 routine is

?C: available to seek files larger than 2 gigabytes.

?C:.

?C:HAS_FSETPOS64:

?C: This symbol, if defined, indicates that the fsetpos64 routine is

?C: available to setpos files larger than 2 gigabytes.

?C:.

?C:HAS_FTELL64:

?C: This symbol, if defined, indicates that the ftell64 routine is

?C: available to tell files larger than 2 gigabytes.

?C:.

?C:HAS_FTELLO64:

?C: This symbol, if defined, indicates that the

ftello64 routine is

?C: available to tell files larger than 2 gigabytes.

?C:.

?C:HAS_TMPFILE64:

?C: This symbol, if defined, indicates that the tmpfile64 routine is

?C: available to tmpfile files larger than 2 gigabytes.

?C:.

?H:#\$d_fgetpos64 HAS_FGETPOS64 /**/

?H:#\$d_fopen64 HAS_FOPEN64 /**/

?H:#\$d_freopen64 HAS_FREOPEN64 /**/

?H:#\$d_fseek64 HAS_FSEEK64 /**/

?H:#\$d_fseeko64 HAS_FSEEKO64 /**/

?H:#\$d_fsetpos64 HAS_FSETPOS64 /**/

?H:#\$d_ftell64 HAS_FTELL64 /**/

?H:#\$d_ftello64 HAS_FTELLO64 /**/

?H:#\$d_tmpfile64 HAS_TMPFILE64 /**/

?H:.

?T:xxx

?LINT:set d_fgetpos64

?LINT:set d_fopen64

?LINT:set d_freopen64

?LINT:set d_fseek64

?LINT:set d_fseeko64

?LINT:set d_fsetpos64

?LINT:set d_ftell64

?LINT:set d_ftello64

?LINT:set d_tmpfile64

: Check for 64bit versions of basic file IO

if \$test X"\$use64bitint" = X"\$define"; then

: see if fgetpos64 exists

set fgetpos64 d_fgetpos64

eval \$inlibc

: see if fopen64 exists

set freopen64 d_fopen64

eval \$inlibc

: see if

freopen64 exists

set freopen64 d_freopen64

eval \$inlibc

```
: see if fseek64 exists
set fseek64 d_fseek64
eval $inlibc
```

```
: see if fseeko64 exists
set fseeko64 d_fseeko64
eval $inlibc
```

```
: see if fsetpos64 exists
set fsetpos64 d_fsetpos64
eval $inlibc
```

```
: see if ftell64 exists
set ftell64 d_ftell64
eval $inlibc
```

```
: see if ftello64 exists
set ftello64 d_ftello64
eval $inlibc
```

```
: see if tmpfile64 exists
set tmpfile64 d_tmpfile64
eval $inlibc
else
val="$undef"
for xxx in d_fgetpos64 d_fopen64 d_freopen64 d_fseek64 d_fseeko64 d_fsetpos64 d_ftell64 d_ftello64 d_tmpfile64
do
set $xxx
eval $setvar
done
fi
```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/perl/stdio64.U
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 2000 Jarkko Hietaniemi

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?MAKE:d_setproctitle: Inlibc

?MAKE: -pick add \$@ %<

?S:d_setproctitle:

?S: This variable conditionally defines the HAS_SETPROCTITLE symbol,

?S: which indicates to the C program that the setproctitle() routine

?S: is available.

?S:.

?C:HAS_SETPROCTITLE:

?C: This symbol, if defined, indicates that the setproctitle routine is

?C: available to set process title.

?C:.

?H:#\$d_setproctitle HAS_SETPROCTITLE /**/

?H:.

?LINT:set d_setproctitle

: see if setproctitle exists

set setproctitle d_setproctitle

eval \$inlibc

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_setproctitle.U

No license file was found, but licenses were detected in source scan.

?RCS: Copyright (c) 1996, Chip Salzenberg

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?MAKE:bincompat3 d_bincompat3: Oldconfig Myread Setvar cat \
patchlevel subversion

?MAKE: -pick add \$@ %<

?Y:TOP

?S:bincompat3:

?S: This variable contains y if Perl 5.004 should be binary-compatible

?S: with Perl 5.003.

?S:.

?S:d_bincompat3:

?S: This variable conditionally defines BINCOMPAT3 so that embed.h

?S: can take special action if Perl 5.004 should be binary-compatible

?S: with Perl 5.003. This is impossible for 5.004_50 and later, so

?S: it is always \$undef for those versions.

?S:.

?C:BINCOMPAT3:

?C: This symbol, if defined, indicates that Perl 5.004 should be

?C: binary-compatible with Perl 5.003. This is impossible for

?C: 5.004_50 and later, so it is always undefined for those versions.

?C:.

?H:#\$d_bincompat3

BINCOMPAT3 /**/

?H:.

: Binary compatibility with 5.003 is not possible with 5.004_50 and later.

if test \$patchlevel -gt 4 -o \$subversion -ge 50; then

```
d_bincompat3=$undef
else
$cat <<EOM
```

Perl 5.004 can be compiled for binary compatibility with 5.003. If you decide to do so, you will be able to continue using any extensions that were compiled for Perl 5.003. However, binary compatibility forces Perl to expose some of its internal symbols in the same way that 5.003 did. So you may have symbol conflicts if you embed a binary-compatible Perl in other programs.

```
EOM
case "$d_bincompat3" in
"$undef") dflt=n ;;
*) dflt=y ;;
esac
rp='Binary compatibility with Perl 5.003?'
./myread
case "$ans" in
y*) val="$define" ;;
*) val="$undef" ;;
esac
set d_bincompat3
eval $setvar
case "$d_bincompat3" in
"$define") bincompat3=y ;;
*) bincompat3=n ;;
esac
fi
```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/bincompat3.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: d_castneg.U,v 3.0.1.2 1995/05/12 12:11:21 ram Exp $
?RCS:
?RCS: Copyright (c) 1991-1993, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 3.0.
?RCS:
?RCS: $Log: d_castneg.U,v $
?RCS: Revision 3.0.1.2 1995/05/12 12:11:21 ram
?RCS: patch54: made sure cc and cflags are conditional dependencies
```

```

?RCS: patch54: added improved test case for Interactive Unix
?RCS:
?RCS: Revision 3.0.1.1 1994/10/29 16:10:50 ram
?RCS: patch36: don't forget to tell user about compilation failures (ADO)
?RCS: patch36: declare signal handler correctly using 'signal_t' (ADO)
?RCS:
?RCS: Revision 3.0 1993/08/18 12:05:47 ram
?RCS: Baseline
for dist 3.0 netwide release.
?RCS:
?X:
?X: Can the compiler cast negative / odd floats to unsigned values.
?X:
?MAKE:d_castneg castflags: cat Compile rm_try Setvar signal_t run i_stdlib
?MAKE:-pick add $@ %<
?S:d_castneg:
?S: This variable conditionally defines CASTNEG, which indicates
?S: whether the C compiler can cast negative float to unsigned.
?S:.
?S:castflags:
?S: This variable contains a flag that precise difficulties the
?S: compiler has casting odd floating values to unsigned long:
?S: 0 = ok
?S: 1 = couldn't cast < 0
?S: 2 = couldn't cast >= 0x80000000
?S: 4 = couldn't cast in argument expression list
?S:.
?C:CASTNEGFLOAT:
?C: This symbol is defined if the C compiler can cast negative
?C: numbers to unsigned longs, ints and shorts.
?C:.
?C:CASTFLAGS:
?C: This symbol contains flags that say what difficulties the compiler
?C: has casting odd floating values to unsigned long:
?C: 0 = ok
?C: 1 = couldn't cast < 0
?C: 2 = couldn't cast >= 0x80000000
?C: 4 = couldn't
cast in argument expression list
?C:.
?H:#$d_castneg CASTNEGFLOAT /**/
?H:#define CASTFLAGS $castflags /**/
?H:.
?F:!try
?LINT:set d_castneg
: check for ability to cast negative floats to unsigned
echo " "
echo 'Checking whether your C compiler can cast negative float to unsigned.' >&4

```

```

$cat >try.c <<EOCP
#include <stdio.h>
#$i_stdlib I_STDLIB
#ifdef I_STDLIB
#include <stdlib.h>
#endif
#include <sys/types.h>
#include <signal.h>
$signal_t blech(int s) { exit(7); }
$signal_t blech_in_list(int s) { exit(4); }
unsigned long dummy_long(unsigned long p) { return p; }
unsigned int dummy_int(unsigned int p) { return p; }
unsigned short dummy_short(unsigned short p) { return p; }
int main()
{
double f;
unsigned long along;
unsigned int aint;
unsigned short ashort;
int result = 0;
char str[16];

/* Frustrate gcc-2.7.2's optimizer which failed this test with
   a direct f = -123. assignment. gcc-2.8.0 reportedly
   optimized the whole file away
*/
/* Store the number in a writable
string for gcc to pass to
scanf under HP-UX.
*/
sprintf(str, "-123");
sscanf(str, "%lf", &f); /* f = -123.; */

signal(SIGFPE, blech);
along = (unsigned long)f;
aint = (unsigned int)f;
ashort = (unsigned short)f;
if (along != (unsigned long)-123)
result |= 1;
if (aint != (unsigned int)-123)
result |= 1;
if (ashort != (unsigned short)-123)
result |= 1;
sprintf(str, "1073741824.");
sscanf(str, "%lf", &f); /* f = (double)0x40000000; */
f = f + f;
along = 0;
along = (unsigned long)f;

```

```

if (along != 0x80000000)
    result |= 2;
f -= 1.;
along = 0;
along = (unsigned long)f;
if (along != 0x7fffffff)
    result |= 1;
f += 2.;
along = 0;
along = (unsigned long)f;
if (along != 0x80000001)
    result |= 2;
if (result)
    exit(result);

```

?X:

?X: The following is a test for Interactive Unix Version 4.1, which

?X: has an 'improved' compiler which can correctly cast negative

?X: floats in expression lists, but apparently not in argument lists.

?X: Contributed by Winfried Koenig

<win@incom.rhein-main.de>

?X:

```

signal(SIGFPE, blech_in_list);
sprintf(str, "123.");
sscanf(str, "%lf", &f); /* f = 123.; */
along = dummy_long((unsigned long)f);
aint = dummy_int((unsigned int)f);
ashort = dummy_short((unsigned short)f);
if (along != (unsigned long)123)
    result |= 4;
if (aint != (unsigned int)123)
    result |= 4;
if (ashort != (unsigned short)123)
    result |= 4;
exit(result);

```

}

EOCP

set try

if eval \$compile_ok; then

\$run ./try 2>/dev/null

castflags=\$?

else

echo "(I can't seem to compile the test program--assuming it can't)"

castflags=7

fi

case "\$castflags" in

0) val="\$define"

echo "Yup, it can."

```
;;
*) val="$undef"
echo "Nope, it can't."
;;
esac
set d_castneg
eval $setvar
$rm_try
```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/compline/d_castneg.U
```

No license file was found, but licenses were detected in source scan.

?RCS: Copyright (c) 2012 H.Merijn Brand

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?MAKE:d_strptime: Inlibc

?MAKE: -pick add @\$ %<

?S:d_strptime:

?S: This variable conditionally defines the HAS_STRPTIME symbol, which

?S: indicates to the C program that the strptime() routine is available.

?S:.

?C:HAS_STRPTIME:

?C: This symbol, if defined, indicates that the strptime routine is

?C: available to set process title.

?C:.

?H:#\$d_strptime HAS_STRPTIME /**/

?H:.

?LINT:set d_strptime

: see if strptime exists

set strptime d_strptime

eval \$inlibc

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_strptime.U
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: \$Log: yacc.U,v \$
?RCS: Revision 3.0.1.1 1994/05/13 15:28:48 ram
?RCS: patch27: added byacc as another alternative (ADO)
?RCS:
?RCS: Revision 3.0 1993/08/18 12:10:03 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:yacc yaccflags: Guess Myread Loc Oldconfig byacc bison cat test
?MAKE: -pick add \$@ %<
?S:yacc:
?S: This variable holds the name of the compiler compiler we
?S: want to use in the Makefile. It can be yacc, byacc, or bison -y.
?S:.
?S:yaccflags:
?S: This variable contains any
additional yacc flags desired by the
?S: user. It is up to the Makefile to use this.
?S:.
?T:comp
: determine compiler compiler
echo " "
comp='yacc'
if \$test -f "\$byacc\$_exe"; then
comp="byacc or \$comp"
fi
if \$test -f "\$bison\$_exe"; then
comp="\$comp or bison -y"
fi
case "\$yacc" in
")
yacc=`./loc yacc yacc \$pth`
if \$test -f "\$yacc\$_exe"; then
dflt='yacc'
elif \$test -f "\$byacc\$_exe"; then
dflt='byacc'
elif \$test -f "\$bison\$_exe"; then
dflt='bison'
else
dflt=""
fi
;;
*) dflt="\$yacc";;
esac
rp="Which compiler compiler (\$comp) shall I use?"
./myread

```

yacc="$ans"
case "$yacc" in
*bis*)
case "$yacc" in
*-y*) ;;
*)
yacc="$yacc -y"
echo "(Adding -y option to bison to get yacc-compatible behaviour.)"
;;
esac
;;
esac

```

```

@if yaccflags
: see if we need extra yacc flags
dflt="$yaccflags"
case "$dflt" in
") dflt=none;;
esac
$cat <<EOH

```

Your yacc program may need extra flags to normally process the parser sources. Do NOT specify any -d or -v flags here, since those are explicitly known by the various Makefiles. However, if your machine has strange/undocumented options (like -Sr# on SCO to specify the maximum number of grammar rules), then please add them here. To use no flags, specify the word "none".

```

EOH
rp="Any additional yacc flags?"
./myread
case "$ans" in
none) yaccflags="";;
*) yaccflags="$ans";;
esac

```

@end

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/yacc.U
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 2000 Jarkko Hietaniemi

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?MAKE:d_modfl d_modflproto: Inlibc Compile Hasproto cat \
test ccflags uselongdouble i_math \
d_sqrtl d_aintl d_copysignl d_ilogbl d_scalbnl d_frexp d_ldexpl \
d_truncl

?MAKE: -pick add \$@ %<

?S:d_modfl:

?S: This variable conditionally defines the HAS_MODFL symbol, which

?S: indicates to the C program that the modfl() routine is available.

?S:.

?S:d_modflproto:

?S: This symbol, if defined, indicates that the system provides

?S: a prototype for the modfl() function. Otherwise, it is up

?S: to the program to supply one. C99 says it should be

?S: long double modfl(long double, long double *);

?S:.

?C:HAS_MODFL:

?C: This symbol, if defined, indicates that the modfl routine is

?C: available to split a

long double x into a fractional part f and

?C: an integer part i such that $|f| < 1.0$ and $(f + i) = x$.

?C:.

?C:HAS_MODFL_PROTO:

?C: This symbol, if defined, indicates that the system provides

?C: a prototype for the modfl() function. Otherwise, it is up

?C: to the program to supply one.

?C:.

?H:#\$d_modfl HAS_MODFL /**/

?H:#\$d_modflproto HAS_MODFL_PROTO /**/

?H:.

?T:message

?LINT:set d_modfl

?LINT:set d_modflproto

?LINT:change ccflags

: see if modfl exists

set modfl d_modfl

eval \$inlibc

: see if prototype for modfl is available

echo " "

set d_modflproto modfl \$i_math math.h

eval \$hasproto

if \$test "\$uselongdouble" = "\$define"; then

message=""

if \$test "\$d_sqrtl" != "\$define"; then

message="\$message sqrtl"

```

fi
if $test "$d_modfl" != "$define"; then
if $test "$d_truncl:$d_copysignl" = "$define:$define"; then
    echo "You have both truncl and copysignl, so I can emulate modfl."
else
    if $test "$d_aintl:$d_copysignl" = "$define:$define"; then
    echo "You have both
aintl and copysignl, so I can emulate modfl."
    else
    message="$message modfl"
    fi
fi
fi
if $test "$d_frexp" != "$define"; then
if $test "$d_ilogbl:$d_scalbnl" = "$define:$define"; then
    echo "You have both ilogbl and scalbnl, so I can emulate frexp."
else
    message="$message frexp"
fi
fi
if $test "$d_ldexpl" != "$define"; then
message="$message ldexpl"
fi

if $test "$message" != ""; then
$cat <<EOM >&4

```

```

*** You requested the use of long doubles but you do not seem to have
*** the following mathematical functions needed for long double support:
*** $message
*** Please rerun Configure without -Duselongdouble and/or -Dusemorebits.
*** Cannot continue, aborting.

```

EOM

```

exit 1
fi
fi

```

Found in path(s):

```

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/perl/d_modfl.U

```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: \$Log: archname.U,v \$
?RCS: Revision 3.0.1.3 1997/02/28 15:24:32 ram
?RCS: patch61: changed the way the archname is mangled from uname
?RCS:
?RCS: Revision 3.0.1.2 1995/05/12 12:05:24 ram
?RCS: patch54: protect against spaces in "uname -m" output (ADO)
?RCS:
?RCS: Revision 3.0.1.1 1995/02/15 14:14:21 ram
?RCS: patch51: created
?RCS:
?MAKE:archname myarchname: sed Loc Myread Oldconfig osname test rm
?MAKE: -pick add \$@ %<
?S:archname:
?S: This variable is a short name to characterize the current
?S: architecture.
It is used mainly to construct the default archlib.
?S:.
?S:myarchname:
?S: This variable holds the architecture name computed by Configure in
?S: a previous run. It is not intended to be perused by any user and
?S: should never be set in a hint file.
?S:.
?C:ARCHNAME:
?C: This symbol holds a string representing the architecture name.
?C: It may be used to construct an architecture-dependant pathname
?C: where library files may be held under a private library, for
?C: instance.
?C:.
?H:#define ARCHNAME "\$archname" /**/
?H:.
?T:xxx tarch
: determine the architecture name
echo " "
?X: We always recompute archname in case osname changes. However, we need
?X: to be careful since, as ADO rightfully pointed out, some systems pick
?X: silly architecture names (0001307135000-aix on AIX or 9000/715-ux under
?X: HP-UX). Therefore, we allow hint files to supersede our guess and ask
?X: the user for confirmation.
if xxx=`./loc arch blurfl \$pth`; \$test -f "\$xxx"; then
tarch=`arch`-"-\$osname"
elif

```

xxx=`./loc uname blurfl $pth`; $test -f "$xxx" ; then
if uname -m > tmparch 2>&1 ; then
tarch=`$sed -e 's/ *$//' -e 's/ /_/g' \
-e 's/$/"-$osname/" tmparch`
else
tarch="$osname"
fi
$rm -f tmparch
else
tarch="$osname"
fi
case "$myarchname" in
|$tarch) ;;
*)
echo "(Your architecture name used to be $myarchname.)"
archname="
;;
esac
case "$sarchname" in
") dflt="$tarch";;
*) dflt="$sarchname";;
esac
rp='What is your architecture name'
./myread
archname="$ans"
myarchname="$tarch"

```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/archname.U
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: d_htonl.U,v \$

?RCS: Revision 3.0.1.2 1994/08/29 16:09:25 ram

?RCS: patch32: now properly handles htonl() and friends when macros (ADO)

?RCS:

?RCS: Revision 3.0.1.1 1994/05/06 14:45:00 ram

?RCS: patch23: now also check for htonl() macro (ADO)

```

?RCS:
?RCS: Revision 3.0 1993/08/18 12:06:22 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:d_htonl: Inlibc Setvar i_niin i_sysin cat rm contains \
  cppstdin cppflags cppminus
?MAKE: -pick add $@ %<
?S:d_htonl:
?S: This variable conditionally
  defines HAS_HTONL if htonl() and its
?S: friends are available to do network order byte swapping.
?S:.
?C:HAS_HTONL (HTONL):
?C: This symbol, if defined, indicates that the htonl() routine (and
?C: friends htons() ntohl() ntohs()) are available to do network
?C: order byte swapping.
?C:.
?C:HAS_HTONS (HTONS):
?C: This symbol, if defined, indicates that the htons() routine (and
?C: friends htonl() ntohl() ntohs()) are available to do network
?C: order byte swapping.
?C:.
?C:HAS_NTOHL (NTOHL):
?C: This symbol, if defined, indicates that the ntohl() routine (and
?C: friends htonl() htons() ntohs()) are available to do network
?C: order byte swapping.
?C:.
?C:HAS_NTOHS (NTOHS):
?C: This symbol, if defined, indicates that the ntohs() routine (and
?C: friends htonl() htons() ntohl()) are available to do network
?C: order byte swapping.
?C:.
?H:#$d_htonl HAS_HTONL /**/
?H:#$d_htonl HAS_HTONS /**/
?H:#$d_htonl HAS_NTOHL /**/
?H:#$d_htonl HAS_NTOHS /**/
?H:.
?F:!htonl.c
?LINT:set d_htonl
:
  see if htonl --and friends-- exists
  val="
  set htonl val
  eval $inlibc

: Maybe they are macros.
case "$val" in
$undef)

```

```

$cat >htonl.c <<EOM
#include <stdio.h>
#include <sys/types.h>
#$i_niin I_NETINET_IN
#$i_sysin I_SYS_IN
#ifdef I_NETINET_IN
#include <netinet/in.h>
#endif
#ifdef I_SYS_IN
#include <sys/in.h>
#endif
#ifdef htonl
printf("Defined as a macro.");
#endif
EOM
$cppstdin $cppflags $cppminus < htonl.c >htonl.E 2>/dev/null
if $contains 'Defined as a macro' htonl.E >/dev/null 2>&1; then
  val="$define"
  echo "But it seems to be defined as a macro." >&4
fi
$rm -f htonl.?
;;
esac
set d_htonl
eval $setvar

```

Found in path(s):

```

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/d_htonl.U

```

No license file was found, but licenses were detected in source scan.

```

?RCS: $Id: d_setpgrp2.U 1 2006-08-24 12:32:52Z rmanfredi $
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: $Log: d_setpgrp2.U,v $
?RCS: Revision 3.0 1993/08/18 12:07:10 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:d_setpgrp2: Inlibc
?MAKE:-pick add $@ %<
?S:d_setpgrp2:

```

?S: This variable conditionally defines the HAS_SETPGRP2 symbol, which
?S: indicates to the C program that the setpgrp2() (as in DG/UX) routine
?S: is available to set the current process group.

?S:.

?C:HAS_SETPGRP2 (SETPGRP2):

?C: This symbol, if defined, indicates that the
setpgrp2() (as in DG/UX)

?C: routine is available to set the current process group.

?C:.

?H:#\$d_setpgrp2 HAS_SETPGRP2 /**/

?H:.

?LINT:set d_setpgrp2

: see if setpgrp2 exists

set setpgrp2 d_setpgrp2

eval \$inlibc

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/d_setpgrp2.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: fpostype.U,v 3.0.1.2 1994/08/29 16:20:52 ram Exp \$

?RCS:

?RCS: Copyright (c) 1991-1993, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 3.0.

?RCS:

?RCS: \$Log: fpostype.U,v \$

?RCS: Revision 3.0.1.2 1994/08/29 16:20:52 ram

?RCS: patch32: now uses new Typedef unit to compute type information

?RCS:

?RCS: Revision 3.0.1.1 1994/06/20 06:59:59 ram

?RCS: patch30: created

?RCS:

?MAKE:fpostype: Myread Typedef

?MAKE: -pick add \$@ %<

?S:fpostype:

?S: This variable defines Fpos_t to be something like fpos_t, long,

?S: uint, or whatever type is used to declare file positions in libc.

?S:.

?C:Fpos_t:

?C: This symbol holds

the type used to declare file positions in libc.

?C: It can be fpos_t, long, uint, etc... It may be necessary to include

?C: <sys/types.h> to get any typedef'ed information.

?C:.

?H:#define Fpos_t \$fpostype /* File position type */

?H:.

?LINT:set fpostype

: see what type file positions are declared as in the library

rp="What is the type for file position used by fsetpos()?"

set fpos_t fpostype long stdio.h sys/types.h

eval \$typedef_ask

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/typedefs/fpostype.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: pidtype.U,v \$

?RCS: Revision 3.0.1.1 1994/08/29 16:31:27 ram

?RCS: patch32: now uses new Typedef unit to compute type information

?RCS:

?RCS: Revision 3.0 1993/08/18 12:09:33 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?MAKE:pidtype: Myread Typedef

?MAKE: -pick add \$@ %<

?S:pidtype:

?S: This variable defines PIDTYPE to be something like pid_t, int,

?S: ushort, or whatever type is used to declare process ids in the kernel.

?S:.

?C:Pid_t (PIDTYPE):

?C: This symbol holds the type

used to declare process ids in the kernel.

?C: It can be int, uint, pid_t, etc... It may be necessary to include

?C: <sys/types.h> to get any typedef'ed information.

?C:.

?H:#define Pid_t \$pidtype /* PID type */

?H:.

: see what type pids are declared as in the kernel

set pid_t pidtype int stdio.h sys/types.h

```
eval $stypedef
dflt="$pidtype"
echo " "
rp="What type are process ids on this system declared as?"
./myread
pidtype="$ans"
```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/pidtype.U
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: d_castneg.U,v \$

?RCS: Revision 3.0.1.2 1995/05/12 12:11:21 ram

?RCS: patch54: made sure cc and ccflags are conditional dependencies

?RCS: patch54: added improved test case for Interactive Unix

?RCS:

?RCS: Revision 3.0.1.1 1994/10/29 16:10:50 ram

?RCS: patch36: don't forget to tell user about compilation failures (ADO)

?RCS: patch36: declare signal handler correctly using 'signal_t' (ADO)

?RCS:

?RCS: Revision 3.0 1993/08/18 12:05:47 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?X:

?X: Can

the compiler cast negative / odd floats to unsigned values.

?X:

?MAKE:d_castneg castflags: cat +cc +ccflags rm_try Setvar signal_t

?MAKE: -pick add \$@ %<

?S:d_castneg:

?S: This variable conditionally defines CASTNEG, which indicates

?S: whether the C compiler can cast negative float to unsigned.

?S:.

?S:castflags:

?S: This variable contains a flag that precise difficulties the

?S: compiler has casting odd floating values to unsigned long:

?S: 0 = ok

```

?S: 1 = couldn't cast < 0
?S: 2 = couldn't cast >= 0x80000000
?S: 4 = couldn't cast in argument expression list
?S:.
?C:CASTNEGFloat:
?C: This symbol is defined if the C compiler can cast negative
?C: numbers to unsigned longs, ints and shorts.
?C:.
?C:CASTFLAGS:
?C: This symbol contains flags that say what difficulties the compiler
?C: has casting odd floating values to unsigned long:
?C: 0 = ok
?C: 1 = couldn't cast < 0
?C: 2 = couldn't cast >= 0x80000000
?C: 4 = couldn't cast in argument expression list
?C:.
?H:#$d_castneg CASTNEGFloat /**/
?H:#define
    CASTFLAGS $castflags /**/
?H:.
?F:!try
?LINT:set d_castneg
: check for ability to cast negative floats to unsigned
echo " "
echo 'Checking whether your C compiler can cast negative float to unsigned.' >&4
$cat >try.c <<EOCP
#include <sys/types.h>
#include <signal.h>
$signal_t blech() { exit(7); }
$signal_t blech_in_list() { exit(4); }
unsigned long dummy_long(p) unsigned long p; { return p; }
unsigned int dummy_int(p) unsigned int p; { return p; }
unsigned short dummy_short(p) unsigned short p; { return p; }
int main()
{
    double f = -123.;
    unsigned long along;
    unsigned int aint;
    unsigned short ashort;
    int result = 0;

    signal(SIGFPE, blech);
    along = (unsigned long)f;
    aint = (unsigned int)f;
    ashort = (unsigned short)f;
    if (along != (unsigned long)-123)
        result |= 1;
    if (aint != (unsigned int)-123)

```

```

    result |= 1;
if (ashort != (unsigned short)-123)
    result |= 1;
f = (double)0x40000000;
f = f + f;
along = 0;
along = (unsigned long)f;
if
(along != 0x80000000)
    result |= 2;
f -= 1.;
along = 0;
along = (unsigned long)f;
if (along != 0x7fffffff)
    result |= 1;
f += 2.;
along = 0;
along = (unsigned long)f;
if (along != 0x80000001)
    result |= 2;
if (result)
    exit(result);
?X:
?X: The following is a test for Interactive Unix Version 4.1, which
?X: has an 'improved' compiler which can correctly cast negative
?X: floats in expression lists, but apparently not in argument lists.
?X: Contributed by Winfried Koenig <win@incom.rhein-main.de>
?X:
signal(SIGFPE, blech_in_list);
f = 123.;
along = dummy_long((unsigned long)f);
aint = dummy_int((unsigned int)f);
ashort = dummy_short((unsigned short)f);
if (along != (unsigned long)123)
    result |= 4;
if (aint != (unsigned int)123)
    result |= 4;
if (ashort != (unsigned short)123)
    result |= 4;
exit(result);

}
EOCP
if $cc $ccflags -o try try.c >/dev/null 2>&1; then
./try
castflags=$?
else
echo "(I can't seem to compile the test program--assuming it can't)"

```

```

castflags=7
fi
case
"$castflags" in
0) val="$define"
echo "Yup, it can."
;;
*) val="$undef"
echo "Nope, it can't."
;;
esac
set d_castneg
eval $setvar
$rm_try

```

Found in path(s):

```

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/d_castneg.U

```

No license file was found, but licenses were detected in source scan.

```

?RCS: $Id: i_stdlib.U 1 2006-08-24 12:32:52Z rmanfredi $
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: $Log: i_stdlib.U,v $
?RCS: Revision 3.0 1993/08/18 12:08:27 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:i_stdlib: Inhdr
?MAKE: -pick add $@ %<
?S:i_stdlib:
?S: This variable conditionally defines the I_STDLIB symbol, which
?S: indicates to the C program that <stdlib.h> exists and should
?S: be included.
?S:.
?C:I_STDLIB:
?C: This symbol, if defined, indicates that <stdlib.h> exists and should
?C: be included.
?C:.
?H:#$i_stdlib I_STDLIB /**/
?H:.
?LINT:set

```

i_stdlib
: see if stdlib is available
set stdlib.h i_stdlib
eval \$inhdr

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/i_stdlib.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: bin.U,v 3.1 1999/07/09 18:20:13 doughera Exp doughera \$

?RCS:

?RCS: Copyright (c) 1991-1993, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 3.0.

?RCS:

?RCS: \$Log: bin.U,v \$

?RCS: Revision 3.1 1999/07/09 18:20:13 doughera

?RCS: Updated for installprefix

?RCS:

?RCS: Revision 3.0.1.4 1995/09/25 09:15:32 ram

?RCS: patch59: unit is now forced to the top of Configure, if possible

?RCS:

?RCS: Revision 3.0.1.3 1995/01/30 14:32:40 ram

?RCS: patch49: can now handle installation prefix changes (from WED)

?RCS:

?RCS: Revision 3.0.1.2 1994/08/29 16:05:28 ram

?RCS: patch32: now uses installation prefix

?RCS:

?RCS:

Revision 3.0.1.1 1993/09/13 15:56:51 ram

?RCS: patch10: made prompting more explicit (WAD)

?RCS:

?RCS: Revision 3.0 1993/08/18 12:05:26 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?MAKE:bin binexp installbin userelocatableinc initialinstalllocation: \
Myread Prefixit Getfile Setvar Setprefixvar Oldconfig \
test prefix prefixexp

?MAKE: -pick add \$@ %<

?Y:TOP

?Y:TOP

?Y:TOP

?D:bin="

?S:bin:

?S: This variable holds the name of the directory in which the user wants

?S: to put publicly executable images for the package in question. It
 ?S: is most often a local directory such as /usr/local/bin. Programs using
 ?S: this variable must be prepared to deal with ~name substitution.
 ?S:.
 ?D:binexp="
 ?S:binexp:
 ?S: This is the same as the bin variable, but is filename expanded at
 ?S: configuration time, for use in your makefiles.
 ?S:.
 ?D:installbin="
 ?S:installbin:
 ?S: This variable is the same as binexp unless AFS is running in which case
 ?S: the user is explicitly prompted for it. This variable
 should always
 ?S: be used in your makefiles for maximum portability.
 ?S:.
 ?D:userelocatableinc="
 ?S:userelocatableinc:
 ?S: This variable is set to true to indicate that perl should relocate
 ?S: @INC entries at runtime based on the path to the perl binary.
 ?S: Any @INC paths starting ".../" are relocated relative to the directory
 ?S: containing the perl binary, and a logical cleanup of the path is then
 ?S: made around the join point (removing "dir/.." pairs)
 ?S:.
 ?S:initialinstalllocation:
 ?S: When userelocatableinc is true, this variable holds the location
 ?S: that make install should copy the perl binary to, with all the
 ?S: run-time relocatable paths calculated from this at install time.
 ?S: When used, it is initialized to the original value of binexp, and
 ?S: then binexp is set to '.../', as the other binaries are found
 ?S: relative to the perl binary.
 ?S:.
 ?C:BIN:
 ?C: This symbol holds the path of the bin directory where the package will
 ?C: be installed. Program must
 be prepared to deal with ~name substitution.
 ?C:.
 ?C:BIN_EXP:
 ?C: This symbol is the filename expanded version of the BIN symbol, for
 ?C: programs that do not want to deal with that at run-time.
 ?C:.
 ?C:PERL_RELOCATABLE_INC:
 ?C: This symbol, if defined, indicates that we'd like to relocate entries
 ?C: in @INC at run time based on the location of the perl binary.
 ?C:.
 ?H:#define BIN "\$bin" /**/
 ?H:#define BIN_EXP "\$binexp" /**/
 ?H:#define PERL_RELOCATABLE_INC "\$userelocatableinc" /**/

```

?H:
?D:bin=/usr/local/bin'
?LINT:change prefix
?LINT:change prefixexp
?LINT:change prefixvar
?LINT:change installprefixexp
?LINT:set userelocatableinc
: determine where public executables go
echo " "
set dflt bin bin
eval $prefixit
fn=d~
rp='Pathname where the public executables will reside?'
./getfile
if $test "X$sansexp" != "X$binexp"; then
  installbin="
fi
prefixvar=bin
: XXX Bug? -- ignores Configure -Dinstallprefix setting.
: XXX If this is fixed, also fix the "start perl" hunk below, which relies
on
: this via initialinstalllocation
./setprefixvar

case "$userelocatableinc" in
$define|true|[yY]*) dflt='y' ;;
*) dflt='n' ;;
esac
cat <<EOM

```

Would you like to build Perl so that the installation is relocatable, so that library paths in @INC are determined relative to the path of the perl binary? This is not advised for system Perl installs, or if you need to run setid scripts or scripts under taint mode.

If this doesn't make any sense to you, just accept the default '\$dflt'.

```

EOM
rp='Use relocatable @INC?'
./myread
case "$ans" in
y|Y) val="$define" ;;
*) val="$undef" ;;
esac
set userelocatableinc
eval $setvar

```

```

initialinstalllocation="$binexp"
: Default prefix is now "up one level from where the binaries are"

```

```

case "$user relocatableinc" in
$define|true|[yY]*)
  bin="..."
  binexp="..."
  prefix="..."
  prefixexp="..."
  installprefixexp="..."
  ;;
esac

```

Found in path(s):

```

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/installdirs/bin.U

```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: cppstdin.U,v \$

?RCS: Revision 3.0.1.4 1994/10/29 16:08:34 ram

?RCS: patch36: added ?F: line for metalint file checking

?RCS:

?RCS: Revision 3.0.1.3 1994/01/24 14:05:38 ram

?RCS: patch16: comment for CPPLAST was missing

?RCS:

?RCS: Revision 3.0.1.2 1993/12/15 08:18:58 ram

?RCS: patch15: new variables cprun and cpplast, guaranteed wrapper-free

?RCS: patch15: cppstdin now tries to use cc, even at the cost of a wrapper

?RCS:

?RCS: Revision 3.0.1.1 1993/08/25 14:00:53 ram

?RCS: patch6:

remove wrapper when not actually used

?RCS:

?RCS: Revision 3.0 1993/08/18 12:05:38 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?MAKE:cppstdin cppminus cprun cpplast: contains test Myread Oldconfig Loc \

cpp +cc rm hint osname gccversion startsh eunicefix

?MAKE: -pick add \$@ %<

?S:cppstdin:

?S: This variable contains the command which will invoke the C

?S: preprocessor on standard input and put the output to stdout.

?S: It is primarily used by other Configure units that ask about

?S: preprocessor symbols.

?S:.

?S:cppminus:

?S: This variable contains the second part of the string which will invoke

?S: the C preprocessor on the standard input and produce to standard

?S: output. This variable will have the value "-" if cppstdin needs

?S: a minus to specify standard input, otherwise the value is "".

?S:.

?S:cprun:

?S: This variable contains the command which will invoke a C preprocessor

?S: on standard input and put the output to stdout. It is guaranteed not

?S: to be a wrapper

and may be a null string if no preprocessor can be

?S: made directly available. This preprocessor might be different from the

?S: one used by the C compiler. Don't forget to append cpplast after the

?S: preprocessor options.

?S:.

?S:cpplast:

?S: This variable has the same functionality as cppminus, only it applies to

?S: cprun and not cppstdin.

?S:.

?C:CPPSTDIN:

?C: This symbol contains the first part of the string which will invoke

?C: the C preprocessor on the standard input and produce to standard

?C: output. Typical value of "cc -E" or "/lib/cpp", but it can also

?C: call a wrapper. See CPPRUN.

?C:.

?C:CPPMINUS:

?C: This symbol contains the second part of the string which will invoke

?C: the C preprocessor on the standard input and produce to standard

?C: output. This symbol will have the value "-" if CPPSTDIN needs a minus

?C: to specify standard input, otherwise the value is "".

?C:.

?C:CPPRUN:

?C: This symbol contains the string which will invoke a C preprocessor on

?C: the

standard input and produce to standard output. It needs to end

?C: with CPPLAST, after all other preprocessor flags have been specified.

?C: The main difference with CPPSTDIN is that this program will never be a

?C: pointer to a shell wrapper, i.e. it will be empty if no preprocessor is

?C: available directly to the user. Note that it may well be different from

?C: the preprocessor used to compile the C program.

?C:.

?C:CPPLAST:

?C: This symbol is intended to be used along with CPPRUN in the same manner

?C: symbol CPPMINUS is used with CPPSTDIN. It contains either "-" or "".

```

?C:.
?H:#define CPPSTDIN "$cppstdin"
?H:#define CPPMINUS "$cppminus"
?H:#define CPPRUN "$cpprun"
?H:#define CPPLAST "$cpplast"
?H:.
?F:cppstdin !testcpp.out !testcpp.c
?T:wrapper x_cpp x_minus ok
: see how we invoke the C preprocessor
echo " "
echo "Now, how can we feed standard input to your C preprocessor..." >&4
cat <<'EOT' >testcpp.c
#define ABC abc
#define XYZ xyz
ABC.XYZ
EOT
cd ..
if $test ! -f cppstdin;
then
echo "$startsh" >cppstdin
if $test "X$osname" = "Xaix" -a "X$gccversion" = X; then
?X: AIX cc -E doesn't show the absolute headerfile
?X: locations but we'll cheat by using the -M flag.
echo 'cat >.$$.c; rm -f .$$.u; ""$cc"" ${1+"$@"} -M -c .$$.c 2>/dev/null; \
test -s .$$.u && \
awk """"$2 ~ /\.h$/ { print "# 0 \\""$2\\""" }"""" .$$.u; \
rm -f .$$.o .$$.u; ""$cc"" -E ${1+"$@"} .$$.c; rm .$$.c' >> cppstdin
else
echo 'cat >.$$.c; ""$cc"" -E ${1+"$@"} .$$.c; rm .$$.c' >>cppstdin
fi; else
echo "Keeping your $hint cppstdin wrapper."
fi
chmod 755 cppstdin
$eunicefix cppstdin
wrapper=`pwd`/cppstdin
ok='false'
cd UU

?X:
?X: We'll run the cpp tests again if we don't have any valid C preprocessor
?X: yet or don't know how to proceed without a wrapper (in which case cpprun
?X: is empty and that's really annoying...)
?X:
if $test "X$cppstdin" != "X" && \
$cppstdin $cppminus <testcpp.c >testcpp.out 2>&1 && \
$contains 'abc.*xyz' testcpp.out >/dev/null 2>&1
then
echo "You used to use

```

```

$cppstdin $cppminus so we'll use that again."
case "$cpprun" in
*) echo "But let's see if we can live without a wrapper..." ;;
*)
if $cpprun $cpplast <testcpp.c >testcpp.out 2>&1 && \
  $contains 'abc.*xyz' testcpp.out >/dev/null 2>&1
then
  echo "(And we'll use $cpprun $cpplast to preprocess directly.)"
  ok='true'
else
  echo "(However, $cpprun $cpplast does not work, let's see...)"
fi
;;
esac
else
case "$cppstdin" in
*) ;;
*)
  echo "Good old $cppstdin $cppminus does not seem to be of any help..."
  ;;
esac
fi

if $ok; then
: nothing
elif echo 'Maybe ""$cc" -E" will work...'; \
  $cc -E <testcpp.c >testcpp.out 2>&1; \
  $contains 'abc.*xyz' testcpp.out >/dev/null 2>&1 ; then
  echo "Yup, it does."
  x_cpp="$cc -E"
  x_minus="";
elif echo 'Nope...maybe ""$cc" -E -" will work...'; \
  $cc -E - <testcpp.c >testcpp.out 2>&1; \
  $contains 'abc.*xyz' testcpp.out >/dev/null 2>&1 ; then
  echo "Yup, it does."
  x_cpp="$cc -E"
  x_minus='-';
elif echo 'Nope...maybe ""$cc"
-P" will work...'; \
  $cc -P <testcpp.c >testcpp.out 2>&1; \
  $contains 'abc.*xyz' testcpp.out >/dev/null 2>&1 ; then
  echo "Yipee, that works!"
  x_cpp="$cc -P"
  x_minus="";
elif echo 'Nope...maybe ""$cc" -P -" will work...'; \
  $cc -P - <testcpp.c >testcpp.out 2>&1; \
  $contains 'abc.*xyz' testcpp.out >/dev/null 2>&1 ; then
  echo "At long last!"

```

```

x_cpp="$cc -P"
x_minus='-';
elif echo 'No such luck, maybe "$cpp" will work...'; \
$cpp <testcpp.c >testcpp.out 2>&1; \
$contains 'abc.*xyz' testcpp.out >/dev/null 2>&1 ; then
echo "It works!"
x_cpp="$cpp"
x_minus="";
elif echo 'Nixed again...maybe "$cpp" -" will work...'; \
$cpp - <testcpp.c >testcpp.out 2>&1; \
$contains 'abc.*xyz' testcpp.out >/dev/null 2>&1 ; then
echo "Hooray, it works! I was beginning to wonder."
x_cpp="$cpp"
x_minus='-';
elif echo 'Uh-uh. Time to get fancy. Trying a wrapper...'; \
$wrapper <testcpp.c >testcpp.out 2>&1; \
$contains 'abc.*xyz' testcpp.out >/dev/null 2>&1 ; then
x_cpp="$wrapper"
x_minus="
echo
"Eureka!"
else
dflt="
rp="No dice. I can't find a C preprocessor. Name one:"
./myread
x_cpp="$ans"
x_minus="
$x_cpp <testcpp.c >testcpp.out 2>&1
if $contains 'abc.*xyz' testcpp.out >/dev/null 2>&1 ; then
echo "OK, that will do." >&4
else
echo "Sorry, I can't get that to work. Go find one and rerun Configure." >&4
exit 1
fi
fi

case "$ok" in
false)
cppstdin="$x_cpp"
cppminus="$x_minus"
cpprun="$x_cpp"
cpplast="$x_minus"
?X:
?X: If /lib/cpp is used, try using a wrapper to increase our chances to have
?X: the C compiler and our $cppstdin agree on the same symbols... However,
?X: since cpprun is guaranteed not to be a wrapper, we must clear it if the
?X: only preprocessor we found was a wrapper, with all our luck...
?X:

```

```

set X $x_cpp
shift
case "$1" in
"$cpp")
echo "Perhaps can we force $cc -E using a wrapper..."
if $wrapper <testcpp.c >testcpp.out 2>&1; \
  $contains 'abc.*xyz' testcpp.out >/dev/null 2>&1
then
echo "Yup, we can."
cppstdin="$wrapper"
cppminus=";
else
echo
"Nope, we'll have to live without it..."
fi
;;
esac
case "$cpprun" in
"$wrapper")
cpprun="
cpplast="
;;
esac
;;
esac

case "$cppstdin" in
"$wrapper"|"cppstdin") ;;
*) $rm -f $wrapper;;
esac
$rm -f testcpp.c testcpp.out

```

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/cppstdin.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: bin.U,v \$

?RCS: Revision 3.0.1.4 1995/09/25 09:15:32 ram

?RCS: patch59: unit is now forced to the top of Configure, if possible

?RCS:

?RCS: Revision 3.0.1.3 1995/01/30 14:32:40 ram

?RCS: patch49: can now handle installation prefix changes (from WED)

?RCS:

?RCS: Revision 3.0.1.2 1994/08/29 16:05:28 ram

?RCS: patch32: now uses installation prefix

?RCS:

?RCS: Revision 3.0.1.1 1993/09/13 15:56:51 ram

?RCS: patch10: made prompting more explicit (WAD)

?RCS:

?RCS: Revision 3.0 1993/08/18
12:05:26 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?MAKE:bin binexp installbin: Prefixit Getfile Oldconfig afs cat test

?MAKE: -pick add \$@ %<

?Y:TOP

?S:bin:

?S: This variable holds the name of the directory in which the user wants
?S: to put publicly executable images for the package in question. It
?S: is most often a local directory such as /usr/local/bin. Programs using
?S: this variable must be prepared to deal with ~name substitution.

?S:.

?S:binexp:

?S: This is the same as the bin variable, but is filename expanded at
?S: configuration time, for use in your makefiles.

?S:.

?S:installbin:

?S: This variable is the same as binexp unless AFS is running in which case
?S: the user is explicitly prompted for it. This variable should always
?S: be used in your makefiles for maximum portability.

?S:.

?C:BIN:

?C: This symbol holds the path of the bin directory where the package will
?C: be installed. Program must be prepared to deal with ~name substitution.

?C:.

?C:BIN_EXP:

?C: This
symbol is the filename expanded version of the BIN symbol, for
?C: programs that do not want to deal with that at run-time.

?C:.

?H:#define BIN "\$bin" /**/
?H:#define BIN_EXP "\$binexp" /**/
?H:.

?D:bin='/usr/local/bin'
: determine where public executables go

```

echo " "
set dflt bin bin
eval $prefixit
fn=d~
rp='Pathname where the public executables will reside?'
./getfile
if $test "X$sansexp" != "X$binexp"; then
  installbin="
fi
bin="$ans"
binexp="$sansexp"
if $afs; then
  $cat <<EOM

```

Since you are running AFS, I need to distinguish the directory in which executables reside from the directory in which they are installed (and from which they are presumably copied to the former directory by occult means).

```

EOM
case "$installbin" in
  *) dflt=`echo $binexp | sed 's#^/afs/#/afs/.#`;;
  *) dflt="$installbin";;
esac
fn=de~
rp='Where will public executables be installed?'
./getfile
installbin="$ans"
else
  installbin="$binexp"
fi

```

Found in path(s):

```

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/bin.U

```

No license file was found, but licenses were detected in source scan.

```

?RCS: $Id: Chk_whoami.U 1 2006-08-24 12:32:52Z rmanfredi $
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: $Log: Chk_whoami.U,v $
?RCS: Revision 3.0 1993/08/18 12:04:46 ram

```

```

?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?X:
?X: This unit makes sure we don't try to include whoami.h if uname() exists.
?X:
?MAKE:Chk_whoami: d_uname i_whoami
?MAKE: -pick add $@ %<
?LINT:change i_whoami
: weed out incompatibilities
case "$d_uname" in
"$define") i_whoami="$undef" ;;
esac

```

Found in path(s):

```

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/Chk_whoami.U

```

No license file was found, but licenses were detected in source scan.

```

?RCS: $Id$
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: $Log: scriptdir.U,v $
?RCS: Revision 3.0.1.3 1995/09/25 09:17:15 ram
?RCS: patch59: unit is now forced to the top of Configure, if possible
?RCS:
?RCS: Revision 3.0.1.2 1995/01/30 14:46:13 ram
?RCS: patch49: can now handle installation prefix changes (from WED)
?RCS:
?RCS: Revision 3.0.1.1 1994/08/29 16:32:04 ram
?RCS: patch32: now uses installation prefix
?RCS:
?RCS: Revision 3.0 1993/08/18 12:09:45 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:scriptdir scriptdirexp installscript:
afs cat test Getfile Loc \
Oldconfig +bin Prefixit prefixexp Prefixup
?MAKE: -pick add $@ %<
?Y:TOP
?S:scriptdir:
?S: This variable holds the name of the directory in which the user wants

```

?S: to put publicly scripts for the package in question. It is either
?S: the same directory as for binaries, or a special one that can be
?S: mounted across different architectures, like /usr/share. Programs
?S: must be prepared to deal with ~name expansion.
?S:.
?S:scriptdirexp:
?S: This variable is the same as scriptdir, but is filename expanded
?S: at configuration time, for programs not wanting to bother with it.
?S:.
?S:installscript:
?S: This variable is usually the same as scriptdirexp, unless you are on
?S: a system running AFS, in which case they may differ slightly. You
?S: should always use this variable within your makefiles for portability.
?S:.
?C:SCRIPTDIR:
?C: This symbol holds the name of the directory in which the user wants
?C: to put publicly executable scripts for the
package in question. It
?C: is often a directory that is mounted across diverse architectures.
?C: Programs must be prepared to deal with ~name expansion.
?C:.
?C:SCRIPTDIR_EXP:
?C: This is the same as SCRIPTDIR, but is filename expanded at
?C: configuration time, for use in programs not prepared to do
?C: ~name substitutions at run-time.
?C:.
?H:#define SCRIPTDIR "\$scriptdir" /**/
?H:#define SCRIPTDIR_EXP "\$scriptdirexp" /**/
?H:.
: determine where public executable scripts go
set scriptdir scriptdir
eval \$prefixit
case "\$scriptdir" in
")
dflt="\$bin"
: guess some guesses
\$test -d /usr/share/scripts && dflt=/usr/share/scripts
\$test -d /usr/share/bin && dflt=/usr/share/bin
\$test -d /usr/local/script && dflt=/usr/local/script
\$test -d \$prefixexp/script && dflt=\$prefixexp/script
set dflt
eval \$prefixup
;;
*) dflt="\$scriptdir"
;;
esac
\$cat <<EOM

Some installations have a separate directory just for executable scripts so that they can mount it across multiple architectures but keep the scripts in one spot. You might, for example, have a subdirectory of /usr/share for this. Or you might just lump your scripts in with all your other executables.

```
EOM
fn=d~
rp='Where do you keep publicly executable scripts?'
./getfile
if $test "X$sansexp" != "X$scriptdirexp"; then
installscript="
fi
scriptdir="$sans"
scriptdirexp="$sansexp"
if $afs; then
$cat <<EOM
```

Since you are running AFS, I need to distinguish the directory in which scripts reside from the directory in which they are installed (and from which they are presumably copied to the former directory by occult means).

```
EOM
case "$installscript" in
") dflt=`echo $scriptdirexp | sed 's#^/afs/#/afs/.#`";;
*) dflt="$installscript";;
esac
fn=de~
rp='Where will public scripts be installed?'
./getfile
installscript="$sans"
else
installscript="$scriptdirexp"
fi
```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/scriptdir.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: prefix.U,v 3.1 1999/07/08 18:27:51 doughera Exp doughera $
?RCS:
?RCS: Copyright (c) 1991-1993, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
```

```

?RCS: of the source tree for dist 3.0.
?RCS:
?RCS: Original Author: Andy Dougherty <doughera@lafcol.lafayette.edu>
?RCS:
?RCS: $Log: prefix.U,v $
?RCS: Revision 3.1 1999/07/08 18:27:51 doughera
?RCS: 5.005_5x version -- Andy Dougherty
?RCS:
?RCS: Revision 3.0.1.2 1995/01/30 14:44:05 ram
?RCS: patch49: new prefixexp variable holding a fully expanded prefix
?RCS: patch49: save off previous prefix value in oldprefix if changed (WED)
?RCS: patch49: added the INSTALLPREFIX define for C programs to use (WED)
?RCS:
?RCS:
Revision 3.0.1.1 1994/08/29 16:31:34 ram
?RCS: patch32: created by ADO
?RCS:
?MAKE:prefix prefixexp +oldprefix: Getfile Loc Oldconfig cat package
?MAKE: -pick add $@ %<
?S:prefix:
?S: This variable holds the name of the directory below which the
?S: user will install the package. Usually, this is /usr/local, and
?S: executables go in /usr/local/bin, library stuff in /usr/local/lib,
?S: man pages in /usr/local/man, etc. It is only used to set defaults
?S: for things in bin.U, mansrc.U, privlib.U, or scriptdir.U.
?S:.
?S:prefixexp:
?S: This variable holds the full absolute path of the directory below
?S: which the user will install the package. Derived from prefix.
?S:.
?S:oldprefix:
?S: This variable is set non-null if the prefix was previously defined
?S: and gets set to a new value. Used internally by Configure only.
?S:.
?C:INSTALLPREFIX:
?C: This symbol contains the name of the install prefix for this package.
?C:.
?H:#define INSTALLPREFIX "$prefix" /**/
?H:.
:
determine root of directory hierarchy where package will be installed.
case "$prefix" in
")
dflt=`./loc . /usr/local /usr/local /local /opt /usr`
;;
*?)
dflt=`echo "$prefix" | sed 's/.$//`
;;

```

```

*)
dflt="$prefix"
;;
esac
$cat <<EOM

```

By default, \$package will be installed in \$dflt/bin, manual pages under \$dflt/man, etc..., i.e. with \$dflt as prefix for all installation directories. Typically this is something like /usr/local. If you wish to have binaries under /usr/bin but other parts of the installation under /usr/local, that's ok: you will be prompted separately for each of the installation directories, the prefix being only used to set the defaults.

```

EOM
fn=d~
rp='Installation prefix to use?'
./getfile
oldprefix=""
case "$prefix" in
") ;;
*)
case "$ans" in
"$prefix") ;;
*) oldprefix="$prefix";;
esac
;;
esac
prefix="$ans"
prefixexp="$ansexp"

```

Found in path(s):

```

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/installdirs/prefix.U

```

No license file was found, but licenses were detected in source scan.

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?MAKE:d_fpgetround: Inlibc

?MAKE: -pick add \$@ %<

?S:d_fpgetround:

?S: This variable conditionally defines HAS_FPGETROUND if fpgetround()

?S: is available to get the floating point rounding mode.

?S:.

?C:HAS_FPGETROUND:

?C: This symbol, if defined, indicates that the fpgetround routine is

?C: available to get the floating point rounding mode.

```
?C:
?H:#$d_fpgetround HAS_FPGETROUND /**/
?H:
?LINT:set d_fpgetround
: see if fpgetround exists
set fpgetround d_fpgetround
eval $inlibc
```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/perl/d_fpgetround.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: Setprefixvar.U,v 3.0 2006/04/01 17:25:29 hmbrand $
?RCS:
?RCS: Copyright (c) 2006-2006, H.Merijn Brand & Nicholas Clark
?RCS:
?RCS: This file is included with or a derivative work of a file included
?RCS: with the metaconfig program of Raphael Manfredi's "dist" distribution.
?RCS: In accordance with clause 7 of dist's modified Artistic License:
?RCS:
?RCS: You may distribute under the terms of either the GNU General Public
?RCS: License or the Artistic License, as specified in the README file.
?RCS:
?X:
?X: This unit sets up the scripts installprefix and setprefixvar, so code
?X: in other parts can be more simple and maintainable
?X:
?MAKE:Setprefixvar: Myread Getfile startsh eunicefix test \
prefix prefixexp installprefix installprefixexp
?MAKE: -pick add $@ %<
?LINT:extern prefixvar
?X: metalint still sees "\${prefixvar}exp`" as variable :(
?T:prefixvarexp
?F:./setprefixvar
?F:./installprefix
: Perform
the prefixexp/installprefixexp correction if necessary
cat <<EOS >installprefix
$startsh
EOS
cat <<'EOESC' >>installprefix
: Change installation prefix, if necessary.
if $test X"$prefix" != X"$installprefix"; then
eval "install${prefixvar}=\`echo \${prefixvar}exp | sed \"s#^\${prefixexp#\${installprefixexp#\"`\"
else
eval "install${prefixvar}=\"\${prefixvar}exp\"`\"
fi
```

```
EOSC
chmod +x installprefix
$unicefix installprefix
```

```
: Set variables such as privlib and privlibexp from the output of ./getfile
: performing the prefixexp/installprefixexp correction if necessary.
```

```
cat <<EOS >setprefixvar
$startsh
```

```
EOS
cat <<'EOSC' >>setprefixvar
eval "${prefixvar}=\\"$ans\"
eval "${prefixvar}exp=\\"$ansexp\"
./installprefix
```

```
EOSC
chmod +x setprefixvar
$unicefix setprefixvar
```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/installdirs/Setprefixvar.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: i_sysun.U 1 2006-08-24 12:32:52Z rmanfredi $
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: $Log: i_sysun.U,v $
?RCS: Revision 3.0 1993/08/18 12:08:42 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?X:
?X: This unit looks wether <sys/un.h> is available or not
?X:
?MAKE:i_sysun: Inhdr
?MAKE: -pick add $@ %<
?S:i_sysun:
?S: This variable conditionally defines I_SYS_UN, which indicates
?S: to the C program that it should include <sys/un.h> to get UNIX
?S: domain socket definitions.
?S:.
?C:I_SYS_UN:
?C: This symbol, if defined, indicates
```

to the C program that it should
?C: include <sys/un.h> to get UNIX domain socket definitions.
?C:.
?H:#\$i_sysun I_SYS_UN /**/
?H:.
?LINT:set i_sysun
: see if this is a sys/un.h system
set sys/un.h i_sysun
eval \$inhdr

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/i_sysun.U

No license file was found, but licenses were detected in source scan.

?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.

?RCS:

?MAKE:i_stdint: Inhdr

?MAKE: -pick add \$@ %<

?S:i_stdint:

?S: This variable conditionally defines the I_STDINT symbol, which

?S: indicates to the C program that <stdint.h> exists and should

?S: be included.

?S:.

?C:I_STDINT:

?C: This symbol, if defined, indicates that <stdint.h> exists and

?C: should be included.

?C:.

?H:#\$i_stdint I_STDINT /**/
?H:.

?LINT:set i_stdint

: see if stdint is available

set stdint.h i_stdint

eval \$inhdr

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/i_stdint.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 2000 Jarkko Hietaniemi

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?MAKE:d_getfsstat : Inlibc
?MAKE: -pick add \$@ %<
?S:d_getfsstat:
?S: This variable conditionally defines the HAS_GETFSSTAT symbol, which
?S: indicates to the C program that the getfsstat() routine is available.
?S:.
?C:HAS_GETFSSTAT:
?C: This symbol, if defined, indicates that the getfsstat routine is
?C: available to stat filesystems in bulk.
?C:.
?H:#\$d_getfsstat HAS_GETFSSTAT /**/
?H:.
?LINT:set d_getfsstat
: see if getfsstat exists
set getfsstat d_getfsstat
eval \$inlibc

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_getfsstat.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: \$Log: d_msg.U,v \$
?RCS: Revision 3.0 1993/08/18 12:06:37 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:d_msg: test d_msgctl d_msgget d_msgsnd d_msgrcv Setvar Findhdr osname
?MAKE: -pick add \$@ %<
?S:d_msg:
?S: This variable conditionally defines the HAS_MSG symbol, which
?S: indicates that the entire msg*(2) library is present.
?S:.
?C:HAS_MSG:
?C: This symbol, if defined, indicates that the entire msg*(2) library is
?C: supported (IPC mechanism based on message queues).
?C:.
?H:#\$d_msg

```

HAS_MSG /**/
?H:.
?T:h_msg
?LINT:set d_msg
: see how much of the 'msg*(2)' library is present.
h_msg=true
echo " "
case "$d_msgctl$d_msgget$d_msgsnd$d_msgrcv" in
*$undef*) h_msg=false;;
esac
case "$osname" in
freebsd)
    case "`ipcs 2>&1`" in
    "SVID messages"*"not configured"*)
    echo "Your $osname does not have the msg*(2) configured." >&4
        h_msg=false
    val="$undef"
    set msgctl d_msgctl
    eval $setvar
    set msgget d_msgget
    eval $setvar
    set msgsnd d_msgsnd
    eval $setvar
    set msgrcv d_msgrcv
    eval $setvar
    ;;
    esac
    ;;
esac
: we could also check for sys/ipc.h ...
if $h_msg && $test `./findhdr sys/msg.h`; then
    echo "You have the full msg*(2) library." >&4
    val="$define"
else
    echo "You don't have the full msg*(2) library." >&4
    val="$undef"
fi
set d_msg
eval $setvar

```

Found in path(s):

```

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/modified/d_msg.U
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/d_msg.U

```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

```

?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: $Log: i_grp.U,v $
?RCS: Revision 3.0 1993/08/18 12:08:20 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:i_grp: Inhdr
?MAKE: -pick add $@ %<
?S:i_grp:
?S: This variable conditionally defines the I_GRP symbol, and indicates
?S: whether a C program should include <grp.h>.
?S:.
?C:I_GRP:
?C: This symbol, if defined, indicates to the C program that it should
?C: include <grp.h>.
?C:.
?H:#$i_grp I_GRP /**/
?H:.
?LINT:set i_grp
: see if this is an grp system
set grp.h i_grp
eval $inhdr

```

Found

in path(s):

```

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/i_grp.U

```

No license file was found, but licenses were detected in source scan.

```

?RCS: $Id$
?RCS:
?RCS: Copyright (c) 1999, Jarkko Hietaniemi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 3.0.
?RCS:
?MAKE:d_mq_close: Inlibc
?MAKE: -pick add $@ %<

```

?S:d_mq_close:
?S: This variable conditionally defines HAS_MQ_CLOSE if mq_close() is
?S: available to close a POSIX message queue.
?S:.
?C:HAS_MQ_CLOSE:
?C: This symbol, if defined, indicates that the mq_close system call is
?C: available to close a POSIX message queue.
?C:.
?H:#\$d_mq_close HAS_MQ_CLOSE /**/
?H:.
?LINT:set d_mq_close
: see if mq_close exists
set mq_close d_mq_close
eval \$inlibc

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_mq_close.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_gethid.U 1 2006-08-24 12:32:52Z rmanfredi \$
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: \$Log: d_gethid.U,v \$
?RCS: Revision 3.0 1993/08/18 12:06:10 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:d_gethid: Inlibc
?MAKE: -pick add \$@ %<
?S:d_gethid:
?S: This variable conditionally defines HAS_GETHOSTID if gethostid() is
?S: available to get the host id.
?S:.
?C:HAS_GETHOSTID (GETHOSTID):
?C: This symbol, if defined, indicates that the gethostid system call is
?C: available to get the host id.
?C:.
?H:#\$d_gethid HAS_GETHOSTID /**/
?H:.
?LINT:set

```
d_gethid
: see if gethid exists
set gethostid d_gethid
eval $inlibc
```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/d_gethid.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: d_NeWS.U 1 2006-08-24 12:32:52Z rmanfredi $
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: $Log: d_NeWS.U,v $
?RCS: Revision 3.0 1993/08/18 12:05:39 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:d_news d_news0 d_newshome d_textcan: test rm Myread Getfile
?MAKE: -pick add $@ %<
?S:d_news:
?S: Set if running NeWS 1.1
?S:.
?S:d_news0:
?S: Set if running NeWS 1.0
?S:.
?S:d_newshome:
?S: Path to the top directory of the NeWS structure.
?S:.
?S:d_textcan:
?S: Path to where the textcan.ps stuff is...
?S:.
?C:HAS_NEWS1_1 (NEWS1_1):
?C: This
symbol defined if running NeWS 1.1.
?C:.
?C:HAS_NEWS1_0 (NEWS1_0):
?C: This symbol defined if running NeWS 1.0.
?C:.
?C:TEXTCAN:
?C: Tells path to where the textcan.ps stuff is...
?C:.
```

```

?H:#$d_news HAS_NEWS1_1  /**/
?H:#$d_news0 HAS_NEWS1_0  /**/
?H:#define TEXTCAN $d_textcan /**/
?H:.
?INIT:: default path for NeWS
?INIT:d_newshome="/usr/NeWS"
?INIT:
: Check to see what version of NeWS is being run?
cd ..
echo " "
echo "Now for the interesting stuff... Lets see what kind of NeWS"
echo "they grow round here...."
echo " "
dflt='y'
if $test -d $d_newshome; then
  d_newshome=`(cd $d_newshome ; /bin/pwd)`
  echo "Ah...found myself a NeWS in $d_newshome..."
  dflt='y'
  rp="Is this the NeWS you want your children to grow up with?"
  . UU/myread
fi
while $test $ans = "n"; do
  dflt=$d_newshome
  fn=d
  rp="Path to NeWS you want:"
  . UU/getfile
  d_newshome=$ans

echo " "
if $test ! -d $d_newshome/lib; then
  echo "ARG! No lib directory in $d_newshome!!!"
  : heavy medicine. I wonder what the disease
  is...
  $rm -f kit*isdone
  $rm -rf UU
  : bye bye
  set -t; echo "Sorry... no NeWS is bad news..."
fi

if $test -r $d_newshome/lib/NeWS/colors.ps ; then
  echo 'Ahh... your running NeWS 1.1! Boy... that makes stuff easy....'
  echo " "
  d_news="$define"
  d_news0="$undef"
  if $test -r $d_newshome/lib/NeWS/textcan.ps; then
    d_textcan=$d_newshome/lib/NeWS
    echo "The textcan.ps stuff seems to be in : $d_textcan"
  else

```

```

d_textcan=${d_newshome}/clientsrc/client/nterm
if $test ! -r $d_textcan/textcan.ps; then
  d_news="$undef"
  d_news0="$define"
  echo 'Hmm... must have been fooled... gotta be NeWS 1.1 beta!'
else
  echo "The textcan.ps stuff seems to be in : $d_textcan"
fi
fi
else
echo 'snif... sniff... I smell the dilapidated smell of NeWS 1.0..'
echo 'Some things will not work under NeWS 1.0...!'
d_news="$undef"
d_news0="$define"
fi
cd UU

```

Found in path(s):

```

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/d_NeWS.U

```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: d_statblks.U,v \$

?RCS: Revision 3.0 1993/08/18 12:07:29 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?MAKE:d_statblks: contains Setvar Findhdr

?MAKE: -pick add \$@ %<

?S:d_statblks:

?S: This variable conditionally defines USE_STAT_BLOCKS if this system

?S: has a stat structure declaring st_blksize and st_blocks.

?S:.

?C:USE_STAT_BLOCKS (STATBLOCKS):

?C: This symbol is defined if this system has a stat structure declaring

?C: st_blksize and st_blocks.

?C:.

?H:#\$d_statblks USE_STAT_BLOCKS

```

/`*/
?H:.
?T:xxx
?LINT:set d_statblks
: see if stat knows about block sizes
echo " "
xxx=`./findhdr sys/stat.h`
if $contains 'st_blocks;' "$xxx" >/dev/null 2>&1 ; then
if $contains 'st_blksize;' "$xxx" >/dev/null 2>&1 ; then
echo "Your stat() knows about block sizes." >&4
val="$define"
else
echo "Your stat() doesn't know about block sizes." >&4
val="$undef"
fi
else
echo "Your stat() doesn't know about block sizes." >&4
val="$undef"
fi
set d_statblks
eval $setvar

```

Found in path(s):

```

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/d_statblks.U

```

No license file was found, but licenses were detected in source scan.

```

?RCS: $Id: d_getprior.U 1 2006-08-24 12:32:52Z rmanfredi $
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: $Log: d_getprior.U,v $
?RCS: Revision 3.0 1993/08/18 12:06:16 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:d_getprior: Inlibc
?MAKE:-pick add $@ %<
?S:d_getprior:
?S: This variable conditionally defines HAS_GETPRIORITY if getpriority()
?S: is available to get a process's priority.
?S:.
?C:HAS_GETPRIORITY (GETPRIORITY):

```

?C: This symbol, if defined, indicates that the getpriority routine is

?C: available to get a process's priority.

?C:.

?H:#\$d_getprior

HAS_GETPRIORITY /**/

?H:.

: see if getpriority exists

?LINT:set d_getprior

set getpriority d_getprior

eval \$inlibc

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/d_getprior.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_inetaton.U 1 2006-08-24 12:32:52Z rmanfredi \$

?RCS:

?RCS: Copyright (c) 1996, Spider Boardman

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic Licence,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic Licence; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: d_inetaton.U,v \$

?RCS: Revision 3.0.1.1 1997/02/28 15:36:35 ram

?RCS: patch61: created

?RCS:

?MAKE:d_inetaton: Inlibc

?MAKE: -pick add \$@ %<

?S:d_inetaton:

?S: This variable conditionally defines the HAS_INET_ATON symbol, which

?S: indicates to the C program that the inet_aton() function is available

?S: to parse IP address "dotted-quad" strings.

?S:.

?C:HAS_INET_ATON:

?C: This symbol, if defined, indicates

to the C program that the

?C: inet_aton() function is available to parse IP address "dotted-quad"

?C: strings.

?C:.

?H:#\$d_inetaton HAS_INET_ATON /**/

?H:.

?LINT:set d_inetaton

: check whether inet_aton exists

```
set inet_aton d_inetaton
eval $inlibc
```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/d_inetaton.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: pkgsrc.U 1 2006-08-24 12:32:52Z rmanfredi $
```

```
?RCS:
```

```
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
```

```
?RCS:
```

```
?RCS: You may redistribute only under the terms of the Artistic Licence,
```

```
?RCS: as specified in the README file that comes with the distribution.
```

```
?RCS: You may reuse parts of this distribution only within the terms of
```

```
?RCS: that same Artistic Licence; a copy of which may be found at the root
```

```
?RCS: of the source tree for dist 4.0.
```

```
?RCS:
```

```
?MAKE:pkgsrc: src rsrc
```

```
?MAKE: -pick add $@ %<
```

```
?S:pkgsrc:
```

```
?S: This variable holds the absolute path of the package source.
```

```
?S:.
```

```
?C:PACKAGE_SOURCE_DIR:
```

```
?C: Holds the directory name holding the package source.
```

```
?C:.
```

```
?H:#define PACKAGE_SOURCE_DIR "$pkgsrc"
```

```
?H:.
```

```
: define absolute package source directory
```

```
case "$src" in
```

```
/*) pkgsrc=$src;;
```

```
*) pkgsrc=`cd $rsrc; pwd`;;
```

```
esac
```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/pkgsrc.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: You may distribute under the terms of either the GNU General Public
```

```
?RCS: License or the Artistic License, as specified in the README file.
```

```
?RCS:
```

```
?MAKE:d_hypot: Inlibc
```

```
?MAKE: -pick add $@ %<
```

```
?S:d_hypot:
```

```
?S: This variable conditionally defines HAS_HYPOT if hypot is available
```

```
?S: for numerically stable hypotenuse function.
```

```
?S:.
```

?C:HAS_HYPOT:

?C: This symbol, if defined, indicates that the hypot routine is

?C: available to do the hypotenuse function.

?C:.

?H:#\$d_hypot HAS_HYPOT /**/

?H:.

?LINT:set d_hypot

: see if hypot exists

set hypot d_hypot

eval \$inlibc

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_hypot.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: shm_for.U 1 2006-08-24 12:32:52Z rmanfredi \$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic Licence,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic Licence; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: shm_for.U,v \$

?RCS: Revision 3.0.1.1 1994/10/29 16:28:37 ram

?RCS: patch36: call ./Cpplib explicitly instead of relying on PATH

?RCS:

?RCS: Revision 3.0 1993/08/18 12:09:46 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?MAKE:shm_for shm_att shm_lim: Cpplib Myread ipc uname

?MAKE: -pick add \$@ %<

?S:shm_for:

?S: This variable tells us the type of machine we're expecting the

?S: shared memory code to run on. The value is available to C

programs

?S: in the C_SHM_FOR manifest.

?S:.

?S:shm_att:

?S: This variable tells us where a shared memory segment should be

?S: attached. Good values are HIGH, LOW, and ZERO.

?S:.

?S:shm_lim:

?S: This variable tells us if shared memory attached HIGH should

?S: have an upper limit.

```

?S:.
?X: -----
?X: It's a potential lose to define anything beginning with SHM...
?X: At least we can think that S_ stands for "String version of ..." -- HMS
?X: -----
?C:S_SHM_FOR ~ %<:
?C: This symbol identifies what we chose for the target system's
?C: default shared memory configuration parameters.
?C:.
?C:S_SHM_ATT ~ %<:
?C: This symbol holds the default "place" to attach shared memory.
?C: Values are "HIGH", "ZERO", and "LOW".
?C:.
?C:S_SHM_LIM ~ %<:
?C: This symbol holds the default upper bound address limit if shared
?C: memory is attached HIGH. If zero, there is no upper limit.
?C:.
?H:%<:#ifdef
SERVE_SHM
?H:%<:#define S_SHM_FOR "$shm_for"
?H:%<:#define S_SHM_ATT "$shm_att"
?H:%<:#define S_SHM_LIM "$shm_lim"
?H:%<:#endif
?H:.
?W:%<:S_SHM_FOR S_SHM_ATT S_SHM_LIM
: see how to attach shared memory
echo " "
echo "Deciding how to attach shared memory..." >&4

case "$ipc" in
shm)
shm_for='Default case'
shm_att='HIGH'
shm_lim='0x0'
if ./Cppsym tower32 tower32_600; then
echo "NCR Towers are usually normal..."
: echo "Oh, an NCR Tower."
: This works for the 600
shm_for='NCR Tower 32'
shm_att='LOW'
else
case "$uname" in
*/uname)
case "`uname -m`" in
ACS??68*)
echo "Oh, an Altos 3068."
shm_for='Altos 3068:'
shm_lim='0x800000'

```

```

;;
esac
;;
*)
echo "Looks normal to me..."
;;
esac
fi

dflt="$shm_for"
rp='Description of shared memory configuration?'
./myread
shm_for="$ans"

dflt="$shm_att"
rp='Where should shared memory be attached?'
./myread
shm_att="$ans"

case "$shm_att" in
HIGH)
dflt="$shm_lim"
rp='What is
the upper address limit for shared memory?'
./myread
shm_lim="$ans"
;;
*)
shm_lim=""
;;
esac
;;

*)
echo "but you aren't using shared memory so I won't bother." >&4
shm_for='NOT CONFIGURED'
shm_att='NONE'
shm_lim='-1'
;;
esac

```

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/shm_for.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: i_gdbm.U 1 2006-08-24 12:32:52Z rmanfredi \$

?RCS:

```

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: $Log: i_gdbm.U,v $
?RCS: Revision 3.0.1.1 1995/05/12 12:16:39 ram
?RCS: patch54: made more robust by checking both header and lib (ADO)
?RCS:
?RCS: Revision 3.0 1993/08/18 12:08:19 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:i_gdbm: Inhdr Inlibc Setvar
?MAKE: -pick add $@ %<
?S:i_gdbm (d_gdbm):
?S: This variable conditionally defines the I_GDBM symbol, which
?S: indicates to the C program that <gdbm.h> exists and should
?S: be included.
?S:.
?C:I_GDBM
(HAS_GDBM):
?C: This symbol, if defined, indicates that <gdbm.h> exists and should
?C: be included.
?C:.
?H:#$i_gdbm I_GDBM /**/
?H:.
?T:t_gdbm d_gdbm_open
?LINT:set i_gdbm
: see if gdbm.h is available
?X: t_gdbm is a tentative check. We might just have the .h, not the lib -- ADO
set gdbm.h t_gdbm
eval $inhdr
case "$t_gdbm" in
$define)
: see if gdbm_open exists
set gdbm_open d_gdbm_open
eval $inlibc
case "$d_gdbm_open" in
$undef)
t_gdbm="$undef"
echo "We won't be including <gdbm.h>"
;;
esac
;;
esac

```

```
val="$t_gdbm"  
set i_gdbm  
eval $setvar
```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-  
debian-perl-5.26.1/dist/U/i_gdbm.U
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: nametype.U 1 2006-08-24 12:32:52Z rmanfredi \$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic Licence,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic Licence; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: nametype.U,v \$

?RCS: Revision 3.0.1.3 1994/10/29 16:26:09 ram

?RCS: patch36: call ./usg and ./bsd explicitly instead of relying on PATH

?RCS:

?RCS: Revision 3.0.1.2 1994/08/29 16:36:48 ram

?RCS: patch32: fixed typo: /etc/password -> /etc/passwd (WED)

?RCS:

?RCS: Revision 3.0.1.1 1993/09/13 16:10:09 ram

?RCS: patch10: made questions more explicit for 'Configure -s' prompting (WAD)

?RCS:

?RCS: Revision 3.0 1993/08/18 12:09:20 ram

?RCS: Baseline

for dist 3.0 netwide release.

?RCS:

?MAKE:nametype d_passnames d_berknames d_usgnames: Myread Guess Oldconfig cat

?MAKE: -pick add \$@ %<

?S:nametype:

?S: This variable indicates how full names are stored on this system.

?S: Values are bsd, usg, and other.

?S:.

?S:d_passnames:

?S: This variable conditionally defines the PASSNAMES symbol,

?S: which indicates to the C program that full names are stored in

?S: the /etc/passwd file.

?S:.

?S:d_berknames:

?S: This variable conditionally defines the PASSNAMES symbol,

?S: which indicates to the C program that full names are stored in

?S: the /etc/passwd file in Berkeley format.

?S:.

?S:d_usgnames:

?S: This variable conditionally defines the PASSNAMES symbol,

?S: which indicates to the C program that full names are stored in

?S: the /etc/passwd file in USG format.

?S:.

?C:PASSNAMES:

?C: This symbol, if defined, indicates that full names are stored in

?C: the /etc/passwd file.

?C:.

?C:BERKNAMES:

?C: This symbol, if defined, indicates that full names are stored in

?C: the /etc/passwd file in Berkeley format (name first thing, everything

?C: up to first comma, with & replaced by capitalized login id, yuck).

?C:.

?C:USGNAMES:

?C: This symbol, if defined, indicates that full names are stored in

?C: the /etc/passwd file in USG format (everything after - and before (is

?C: the name).

?C:.

?H:#\$d_passnames PASSNAMES /* (undef to take name from ~/.fullname) */

?H:#\$d_berknames BERKNAMES /* (that is, ":name,stuff:") */

?H:#\$d_usgnames USGNAMES /* (that is, ":stuff-name(stuff):") */

?H:.

: find out how to find out full name

case "\$d_berknames" in

"\$define")

dflt=y;;

"\$undef")

dflt=n;;

*)

if ./bsd; then

dflt=y

elif ./xenix; then

dflt=y

else

dflt=n

fi

::

esac

\$cat <<'EOM'

Does your /etc/passwd file keep full names in Berkeley/V7 format (name first thing after ':' in GCOS field)? In that case, a typical entry in the password file looks like this:

```
guest:**password**:10:100:Mister Guest User:/usr/users:/bin/sh
```

^^^^^^^^^^^^^^^^^^^^

EOM

```
rp="Berkeley/V7 format for full name in /etc/passwd?"
./myread
case "$ans" in
y*) d_passnames="$define"
d_berknames="$define"
d_usgnames="$undef"
nametype=bsd
;;
*)
case "$d_usgnames" in
"$define") dflt=y;;
"$undef") dflt=n;;
*)
if ./usg; then
dflt=y
else
dflt=n
fi
;;
esac
$cat <<'EOM'
```

Does your passwd file keep full names in USG format (name sandwiched between a '-' and a '(')? In that case, a typical entry in the password file looks like this:

```
guest:**password**:10:100:000-Mister Guest User(000):/usr/users:/bin/sh
```

^^^^^^^^^^^^^^^^^^^^

EOM

```
rp="USG format for full name in /etc/passwd?"
./myread
case "$ans" in
n*) echo "Full name will be taken from ~/.fullname"
d_passnames="$undef"
d_berknames="$undef"
d_usgnames="$undef"
nametype=other
;;
*)
d_passnames="$define"
d_berknames="$undef"
d_usgnames="$define"
nametype=usg
;;
esac;;
```

esac

Found in path(s):

*

/opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/nametype.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_getpwuid_r.U,v 0RCS:

?RCS: Copyright (c) 2002,2003 Jarkko Hietaniemi

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?RCS: Generated by the reentr.pl from the Perl 5.8 distribution.

?RCS:

?MAKE:d_getpwuid_r getpwuid_r_proto: Inlibc Protochk Hasproto i_systypes \
usethreads i_pwd extern_C

?MAKE: -pick add \$@ %<

?S:d_getpwuid_r:

?S: This variable conditionally defines the HAS_GETPWUID_R symbol,

?S: which indicates to the C program that the getpwuid_r()

?S: routine is available.

?S:.

?S:getpwuid_r_proto:

?S: This variable encodes the prototype of getpwuid_r.

?S: It is zero if d_getpwuid_r is undef, and one of the

?S: REENTRANT_PROTO_T_ABC macros of reentr.h if d_getpwuid_r

?S: is defined.

?S:.

?C:HAS_GETPWUID_R:

?C: This symbol, if defined, indicates that the getpwuid_r routine

?C: is available to

getpwuid re-entrantly.

?C:.

?C:GETPWUID_R_PROTO:

?C: This symbol encodes the prototype of getpwuid_r.

?C: It is zero if d_getpwuid_r is undef, and one of the

?C: REENTRANT_PROTO_T_ABC macros of reentr.h if d_getpwuid_r

?C: is defined.

?C:.

?H:#\$d_getpwuid_r HAS_GETPWUID_R /**/

?H:#define GETPWUID_R_PROTO \$getpwuid_r_proto /**/

?H:.

?T:try hdrs d_getpwuid_r_proto

: see if getpwuid_r exists

set getpwuid_r d_getpwuid_r

eval \$inlibc

```

case "$d_getpwuid_r" in
"$define")
hdrs="$i_systypes sys/types.h define stdio.h $i_pwd pwd.h"
case "$d_getpwuid_r_proto:$usetthreads" in
":define") d_getpwuid_r_proto=define
set d_getpwuid_r_proto getpwuid_r $hdrs
eval $hasproto ;;
*) ;;
esac
case "$d_getpwuid_r_proto" in
define)
case "$getpwuid_r_proto" in
"|0) try='int getpwuid_r(uid_t, struct passwd*, char*, size_t, struct passwd**);'
./protochk "$extern_C $try" $hdrs && getpwuid_r_proto=I_TSBWR ;;
esac
case "$getpwuid_r_proto" in
"|0) try='int getpwuid_r(uid_t, struct passwd*, char*,
int, struct passwd**);'
./protochk "$extern_C $try" $hdrs && getpwuid_r_proto=I_TSBIR ;;
esac
case "$getpwuid_r_proto" in
"|0) try='int getpwuid_r(uid_t, struct passwd*, char*, int);'
./protochk "$extern_C $try" $hdrs && getpwuid_r_proto=I_TSBI ;;
esac
case "$getpwuid_r_proto" in
"|0) try='struct passwd* getpwuid_r(uid_t, struct passwd*, char*, int);'
./protochk "$extern_C $try" $hdrs && getpwuid_r_proto=S_TSBI ;;
esac
case "$getpwuid_r_proto" in
"|0) d_getpwuid_r=undef
getpwuid_r_proto=0
echo "Disabling getpwuid_r, cannot determine prototype." >&4 ;;
*) case "$getpwuid_r_proto" in
REENTRANT_PROTO*) ;;
*) getpwuid_r_proto="REENTRANT_PROTO_$getpwuid_r_proto" ;;
esac
echo "Prototype: $try" ;;
esac
;;
*) case "$usetthreads" in
define) echo "getpwuid_r has no prototype, not using it." >&4 ;;
esac
d_getpwuid_r=undef
getpwuid_r_proto=0
;;
esac
;;
*) getpwuid_r_proto=0

```

```
;;
esac
```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/threads/d_getpwuid_r.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: d_getpagsz.U,v 3.0.1.1 1994/10/29 16:13:10 ram Exp $
```

```
?RCS:
```

```
?RCS: Copyright (c) 1991-1993, Raphael Manfredi
```

```
?RCS:
```

```
?RCS: You may redistribute only under the terms of the Artistic License,
```

```
?RCS: as specified in the README file that comes with the distribution.
```

```
?RCS: You may reuse parts of this distribution only within the terms of
```

```
?RCS: that same Artistic License; a copy of which may be found at the root
```

```
?RCS: of the source tree for dist 3.0.
```

```
?RCS:
```

```
?RCS: $Log: d_getpagsz.U,v $
```

```
?RCS: Revision 3.0.1.1 1994/10/29 16:13:10 ram
```

```
?RCS: patch36: added ?F: line for metalint file checking
```

```
?RCS:
```

```
?RCS: Revision 3.0 1993/08/18 12:06:14 ram
```

```
?RCS: Baseline for dist 3.0 netwide release.
```

```
?RCS:
```

```
?MAKE:d_getpagsz: Compile Oldconfig Myread Inlibc Findhdr
```

```
?MAKE: -pick add $@ %<
```

```
?S:d_getpagsz:
```

```
?S: This variable conditionally defines HAS_GETPAGESIZE if getpagesize()
```

```
?S: is available to get the system page size.
```

```
?S:.
```

```
?C:HAS_GETPAGESIZE
```

```
(GETPAGESIZE):
```

```
?C: This symbol, if defined, indicates that the getpagesize system call
```

```
?C: is available to get system page size, which is the granularity of
```

```
?C: many memory management calls.
```

```
?C:.
```

```
?H:#$d_getpagsz HAS_GETPAGESIZE /**/
```

```
?H:.
```

```
?LINT:set d_getpagsz
```

```
: see if getpagesize exists
```

```
set getpagesize d_getpagsz
```

```
eval $inlibc
```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/compline/d_getpagsz.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id$
?RCS:
?RCS: Copyright (c) 2003 Jarkko Hietaniemi
?RCS:
?RCS: You may distribute under the terms of either the GNU General Public
?RCS: License or the Artistic License, as specified in the README file.
?RCS:
?MAKE:d_faststdio: Setvar \
d_stdstdio d_stdio_ptr_lval d_stdio_cnt_lval d_stdio_ptr_lval_sets_cnt
?MAKE: -pick add $@ %<
?S:d_faststdio:
?S: This variable conditionally defines the HAS_FAST_STDIO symbol,
?S: which indicates to the C program that the "fast stdio" is available
?S: to manipulate the stdio buffers directly.
?S:.
?C:HAS_FAST_STDIO:
?C: This symbol, if defined, indicates that the "fast stdio"
?C: is available to manipulate the stdio buffers directly.
?C:.
?H:#$d_faststdio HAS_FAST_STDIO /**/
?H:.
?LINT:set d_faststdio
: see if fast_stdio exists
val="$undef"
case "$d_stdstdio:$d_stdio_ptr_lval" in
"$define:$define")
case "$d_stdio_cnt_lval$d_stdio_ptr_lval_sets_cnt" in
*$define*)
echo "You
seem to have 'fast stdio' to directly manipulate the stdio buffers." >& 4
val="$define"
;;
esac
;;
esac
set d_faststdio
eval $setvar
```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/perl/d_faststdio.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id$
?RCS:
?RCS: Copyright (c) 1999, Jarkko Hietaniemi
```

```

?RCS:
?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 3.0.
?RCS:
?MAKE:inotype: Myread Typedef
?MAKE: -pick add $@ %<
?S:inotype:
?S: This variable defines Ino_t to be something like ino_t, long,
?S: int, or whatever type is used to declare inode numbers.
?S:.
?C:Ino_t:
?C: This symbol holds the type used to declare inode numbers.
?C: It can be int, long, ino_t, etc...
?C: It may be necessary to include <sys/types.h> to get any
?C: typedef'ed information.
?C:.
?H:#define Ino_t $inotype /* <inode> type */
?H:.
?LINT: set inotype
: see what type is used for inodes
rp="What is the type used
for inode numbers on this system?"
set ino_t inotype long stdio.h sys/types.h
eval $typedef_ask

```

Found in path(s):

```

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/typedefs/inotype.U

```

No license file was found, but licenses were detected in source scan.

```

?RCS: $Id$
?RCS:
?RCS: Copyright (c) 1999 Jarkko Hietaniemi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 3.0.
?RCS:
?MAKE:d_getspent: Inlibc
?MAKE: -pick add $@ %<
?S:d_getspent:
?S: This variable conditionally defines HAS_GETSPENT if getspent() is
?S: available to retrieve SysV shadow password entries sequentially.

```

?S:.

?C:HAS_GETSPENT:

?C: This symbol, if defined, indicates that the getspent system call is

?C: available to retrieve SysV shadow password entries sequentially.

?C:.

?H:#\$d_getspent HAS_GETSPENT /**/

?H:.

?LINT:set d_getspent

: see if getspent exists

set getspent d_getspent

eval \$inlibc

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_getspent.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: prototype.U,v 3.0.1.3 1994/05/06 15:11:49 ram Exp \$

?RCS:

?RCS: Copyright (c) 1991-1993, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 3.0.

?RCS:

?RCS: \$Log: prototype.U,v \$

?RCS: Revision 3.0.1.3 1994/05/06 15:11:49 ram

?RCS: patch23: ensure cc flags used when looking for prototype support

?RCS:

?RCS: Revision 3.0.1.2 1994/01/24 14:15:36 ram

?RCS: patch16: prototype handling macros now appear only when needed

?RCS:

?RCS: Revision 3.0.1.1 1993/08/25 14:03:12 ram

?RCS: patch6: defines were referring to non-existent VOID symbol

?RCS:

?RCS: Revision 3.0 1993/08/18 12:09:36 ram

?RCS: Baseline for dist

3.0 netwide release.

?RCS:

?MAKE:prototype: Myread Oldconfig cat +cc +cflags rm Setvar i_stdlib

?MAKE: -pick add \$@ %<

?S:prototype:

?S: This variable holds the eventual value of CAN_PROTOTYPE, which

?S: indicates the C compiler can handle function prototypes.

?S:.

?C:CAN_PROTOTYPE ~ %<:

?C: If defined, this macro indicates that the C compiler can handle

?C: function prototypes.

?C:.

?C:DOTS:

?C: This macro is used to specify the ... in function prototypes which

?C: have arbitrary additional arguments.

?C:.

?C:NXT_ARG:

?C: This macro is used to separate arguments in the declared argument list.

?C:.

?C:P_FUNC:

?C: This macro is used to declare "private" (static) functions.

?C: It takes three arguments: the function type and name, a parenthesized

?C: traditional (comma separated) argument list, and the declared argument

?C: list (in which arguments are separated with NXT_ARG, and additional

?C: arbitrary arguments are specified with DOTS). For example:

?C:

```
?C: P_FUNC(int foo, (bar, baz),
```

```
int bar NXT_ARG char *baz[])
```

?C:.

?C:P_FUNC_VOID:

?C: This macro is used to declare "private" (static) functions that have

?C: no arguments. The macro takes one argument: the function type and name.

?C: For example:

?C:

```
?C: P_FUNC_VOID(int subr)
```

?C:.

?C:V_FUNC:

?C: This macro is used to declare "public" (non-static) functions.

?C: It takes three arguments: the function type and name, a parenthesized

?C: traditional (comma separated) argument list, and the declared argument

?C: list (in which arguments are separated with NXT_ARG, and additional

?C: arbitrary arguments are specified with DOTS). For example:

?C:

```
?C: V_FUNC(int main, (argc, argv), int argc NXT_ARG char *argv[])
```

?C:.

?C:V_FUNC_VOID:

?C: This macro is used to declare "public" (non-static) functions that have

?C: no arguments. The macro takes one argument: the function type and name.

?C: For example:

?C:

```
?C: V_FUNC_VOID(int fork)
```

?C:.

?C:_(P):

?C: This macro is used to declare function parameters for folks who want

?C: to

make declarations with prototypes using a different style than

?C: the above macros. Use double parentheses. For example:

```

?C:
?C: int main __((int argc, char *argv[]));
?C:
?H:%<:#$prototype CAN_PROTOTYPE /**/
?H:?_:#ifdef CAN_PROTOTYPE
?H:?NXT_ARG:#define NXT_ARG ,
?H:?DOTS:#define DOTS , ...
?H:?V_FUNC:#define V_FUNC(name, arglist, args)name(args)
?H:?P_FUNC:#define P_FUNC(name, arglist, args)static name(args)
?H:?V_FUNC_VOID:#define V_FUNC_VOID(name)name(void)
?H:?P_FUNC_VOID:#define P_FUNC_VOID(name)static name(void)
?H:?_:#define _(args) args
?H:?_:#else
?H:?NXT_ARG:#define NXT_ARG ;
?H:?DOTS:#define DOTS
?H:?V_FUNC:#define V_FUNC(name, arglist, args)name arglist args;
?H:?P_FUNC:#define P_FUNC(name, arglist, args)static name arglist args;
?H:?V_FUNC_VOID:#define V_FUNC_VOID(name)name()
?H:?P_FUNC_VOID:#define P_FUNC_VOID(name)static name()
?H:?_:#define _(args) ()
?H:?_:#endif
?H:
?W:%<:NXT_ARG DOTS V_FUNC P_FUNC V_FUNC_VOID P_FUNC_VOID _
?LINT:set prototype
: Cruising
  for prototypes
echo " "
echo "Checking out function prototypes..." >&4
$cat >prototype.c <<EOCP
#i_stdlib I_STDLIB
#ifdef I_STDLIB
#include <stdlib.h>
#endif
int main(int argc, char *argv[]) {
  exit(0);}
EOCP
if $cc $ccflags -c prototype.c >prototype.out 2>&1 ; then
  echo "Your C compiler appears to support function prototypes."
  val="$define"
else
  echo "Your C compiler doesn't seem to understand function prototypes."
  val="$undef"
fi
set prototype
eval $setvar
$rm -f prototype*

```

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/modified/prototype.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: i_termio.U,v \$

?RCS: Revision 3.0.1.4 1994/10/29 16:20:54 ram

?RCS: patch36: call ./usg and ./Cpplib explicitly instead of relying on PATH

?RCS:

?RCS: Revision 3.0.1.3 1994/08/29 16:26:38 ram

?RCS: patch32: don't include all three I_* symbols in config.h

?RCS: patch32: (had forgotten to undo this part last time)

?RCS:

?RCS: Revision 3.0.1.2 1994/05/13 15:25:03 ram

?RCS: patch27: undone ADO's fix in previous patch since it was useless

?RCS:

?RCS: Revision 3.0.1.1 1994/05/06 15:05:23

ram

?RCS: patch23: now include all three defines in config.h (ADO)

?RCS:

?RCS: Revision 3.0 1993/08/18 12:08:44 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?MAKE:i_termio i_sgty i_termios: test Inlibc Cpplib Guess Setvar Findhdr Warn

?MAKE: -pick add \$@ %<

?S:i_termio:

?S: This variable conditionally defines the I_TERMIO symbol, which

?S: indicates to the C program that it should include <termio.h> rather

?S: than <sgty.h>.

?S:.

?S:i_termios:

?S: This variable conditionally defines the I_TERMIOS symbol, which

?S: indicates to the C program that the POSIX <termios.h> file is

?S: to be included.

?S:.

?S:i_sgty:

?S: This variable conditionally defines the I_SGTTY symbol, which

?S: indicates to the C program that it should include <sgty.h> rather

?S: than <termio.h>.

?S:.

?C:I_TERMIO:

?C: This symbol, if defined, indicates that the program should include

?C: <termio.h> rather than <sgtty.h>. There are also differences in

?C: the ioctl() calls that depend on the value of

this symbol.

?C:.

?C:I_TERMIOS:

?C: This symbol, if defined, indicates that the program should include

?C: the POSIX termios.h rather than sgty.h or termio.h.

?C: There are also differences in the ioctl() calls that depend on the

?C: value of this symbol.

?C:.

?C:I_SGTTY:

?C: This symbol, if defined, indicates that the program should include

?C: <sgtty.h> rather than <termio.h>. There are also differences in

?C: the ioctl() calls that depend on the value of this symbol.

?C:.

?H:#\$i_termio I_TERMIO /**/

?H:#\$i_termios I_TERMIOS /**/

?H:#\$i_sgty I_SGTTY /**/

?H:.

?T:val2 val3

?LINT:set i_termio i_sgty i_termios

: see if this is a termio system

val="\$undef"

val2="\$undef"

val3="\$undef"

?X: Prefer POSIX-approved termios.h over all else

if \$test `./findhdr termios.h`; then

set tcsetattr i_termios

eval \$inlibc

val3="\$i_termios"

fi

echo " "

case "\$val3" in

"\$define") echo "You have POSIX termios.h... good!" >&4;;

*) if ./Cppsymb pyr; then

case "`/bin/universe`" in

ucb) if \$test `./findhdr

sgtty.h`; then

val2="\$define"

echo "<sgtty.h> found." >&4

else

echo "System is pyramid with BSD universe."

./warn "<sgtty.h> not found--you could have problems."

fi;;

*) if \$test `./findhdr termio.h`; then

```

val="$define"
echo "<termio.h> found." >&4
else
echo "System is pyramid with USG universe."
./warn "<termio.h> not found--you could have problems."
fi;;
esac
?X: Start with USG to avoid problems if both usg/bsd was guessed
elif ./usg; then
if $test `./findhdr termio.h`; then
echo "<termio.h> found." >&4
val="$define"
elif $test `./findhdr sgtty.h`; then
echo "<sgtty.h> found." >&4
val2="$define"
else
./warn "Neither <termio.h> nor <sgtty.h> found--cross fingers!"
fi
else
if $test `./findhdr sgtty.h`; then
echo "<sgtty.h> found." >&4
val2="$define"
elif $test `./findhdr termio.h`; then
echo "<termio.h> found." >&4
val="$define"
else
./warn "Neither <sgtty.h> nor <termio.h> found--cross
fingers!"
fi
fi;;
esac
set i_termio; eval $setvar
val=$val2; set i_sgtty; eval $setvar
val=$val3; set i_termios; eval $setvar

```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/i_termio.U
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1996, Andy Dougherty

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: \$Log: sitearch.U,v \$
?RCS: Revision 3.0.1.1 1997/02/28 16:21:30 ram
?RCS: patch61: created
?RCS:
?MAKE:sitearch sitearchexp installsitearch: afs cat Getfile \
Oldconfig Prefixit prefix test archname sitelib
?MAKE: -pick add \$@ %<
?Y:TOP
?S:sitearch:
?S: This variable contains the eventual value of the SITEARCH symbol,
?S: which is the name of the private library for this package. It may
?S: have a ~ on the front. It is up to the makefile to eventually create
?S: this
directory while performing installation (with ~ substitution).
?S:.
?S:sitearchexp:
?S: This variable is the ~name expanded version of sitearch, so that you
?S: may use it directly in Makefiles or shell scripts.
?S:.
?S:installsitearch:
?S: This variable is really the same as sitearchexp but may differ on
?S: those systems using AFS. For extra portability, only this variable
?S: should be used in makefiles.
?S:.
?C:SITEARCH:
?C: This symbol contains the name of the private library for this package.
?C: The library is private in the sense that it needn't be in anyone's
?C: execution path, but it should be accessible by the world. The program
?C: should be prepared to do ~ expansion.
?C: The standard distribution will put nothing in this directory.
?C: Individual sites may place their own extensions and modules in
?C: this directory.
?C:.
?C:SITEARCH_EXP:
?C: This symbol contains the ~name expanded version of SITEARCH, to be used
?C: in programs that are not prepared to deal
with ~ expansion at run-time.
?C:.
?H:#define SITEARCH "\$sitearch" /**/
?H:#define SITEARCH_EXP "\$sitearchexp" /**/
?H:.
?T:xxx
: determine where site specific architecture-dependent libraries go.
xxx=`echo \$sitelib/\$archname | sed 's!^\$prefix!!'
: xxx is usually lib/site_perl/archname.

```

set sitearch sitearch none
eval $prefixit
case "$sitearch" in
") dflt="$sitelib/$archname" ;;
*) dflt="$sitearch" ;;
esac
$cat <<EOM

```

The installation process will also create a directory for architecture-dependent site-specific extensions and modules.

```

EOM
fn=nd~+
rp='Pathname for the site-specific architecture-dependent library files?'
./getfile
if $test "X$sitearchexp" != "X$sansexp"; then
installsitearch="
fi
sitearch="$ans"
sitearchexp="$sansexp"
if $afs; then
$cat <<EOM

```

Since you are running AFS, I need to distinguish the directory in which private files reside from the directory in which they are installed (and from which they are presumably copied to the former directory by occult means).

```

EOM
case
"$installsitearch" in
") dflt=`echo $sitearchexp | sed 's#~/afs/#/afs/.#^`;;
*) dflt="$installsitearch";;
esac
fn=de~
rp='Where will private files be installed?'
./getfile
installsitearch="$ans"
else
installsitearch="$sitearchexp"
fi

```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/sitearch.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: i_malloc.U,v 3.5 2008/03/29 14:06:51 merijn Exp $
```

```
?RCS:
```

?RCS: Copyright (c) 2008, H.Merijn Brand
?RCS:
?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 3.5.
?RCS:
?MAKE:i_mallocmalloc: Inhdr
?MAKE: -pick add \$@ %<
?S:i_mallocmalloc:
?S: This variable conditionally defines the I_MALLOCMALLOCC symbol,
?S: and indicates whether a C program should include <malloc/malloc.h>.
?S:.
?C:I_MALLOCMALLOCC:
?C: This symbol, if defined, indicates to the C program that it should
?C: include <malloc/malloc.h>.
?C:.
?H:#\$i_mallocmalloc I_MALLOCMALLOCC /**/
?H:.
?LINT:set i_mallocmalloc
: see if malloc/malloc.h has to be included
set malloc/malloc.h i_mallocmalloc
eval
\$inhdr

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/i_mallocmalloc.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: i_dbm.U 1 2006-08-24 12:32:52Z rmanfredi \$
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: \$Log: i_dbm.U,v \$
?RCS: Revision 3.0.1.2 1997/02/28 15:48:20 ram
?RCS: patch61: added I_RPCSVCC_DBM check
?RCS:
?RCS: Revision 3.0.1.1 1995/05/12 12:16:05 ram
?RCS: patch54: made more robust by checking both header and lib (ADO)
?RCS:

```

?RCS: Revision 3.0 1993/08/18 12:08:15 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:i_dbm i_rpcsvcdbm: Inhdr Inlibc Setvar
?MAKE: -pick add $@ %<
?S:i_dbm (d_odbm):
?S: This variable conditionally defines
the I_DBM symbol, which
?S: indicates to the C program that <dbm.h> exists and should
?S: be included.
?S:.
?S:i_rpcsvcdbm:
?S: This variable conditionally defines the I_RPC SVC_DBM symbol, which
?S: indicates to the C program that <rpcsvc/dbm.h> exists and should
?S: be included. Some System V systems might need this instead of <dbm.h>.
?S:.
?C:I_DBM (HAS_ODBM ODBM):
?C: This symbol, if defined, indicates that <dbm.h> exists and should
?C: be included.
?C:.
?C:I_RPC SVC_DBM:
?C: This symbol, if defined, indicates that <rpcsvc/dbm.h> exists and
?C: should be included.
?C:.
?H:#$i_dbm I_DBM /**/
?H:#$i_rpcsvcdbm I_RPC SVC_DBM /**/
?H:.
?T:d_dbmclose
?LINT:set i_dbm i_rpcsvcdbm
: see if dbm.h is available
?X: We might just have the header, not the library.
?X: We look for dbmclose() rather than dbmopen() because
?X: some versions of SCO Unix have -ldb, but are missing dbmclose(). -- ADO
?X: Some System V systems have <rpcsvc/dbm.h> instead of <dbm.h>.
: see if dbmclose exists
set dbmclose
d_dbmclose
eval $inlibc

case "$d_dbmclose" in
$define)
set dbm.h i_dbm
eval $inhdr
case "$i_dbm" in
$define)
val="$undef"
set i_rpcsvcdbm
eval $setvar

```

```

;;
*) set rpcsvc/dbm.h i_rpcsvcdbm
eval $inhdr
;;
esac
;;
*) echo "We won't be including <dbm.h>"
val="$sundef"
set i_dbm
eval $setvar
val="$sundef"
set i_rpcsvcdbm
eval $setvar
;;
esac

```

Found in path(s):

```

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/i_dbm.U

```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1998 Jarkko Hietaniemi

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?MAKE:d_ftello: Inlibc longsize

?MAKE: -pick add \$@ %<

?S:d_ftello:

?S: This variable conditionally defines the HAS_FTELLO symbol, which

?S: indicates to the C program that the ftello() routine is available.

?S:.

?C:HAS_FTELLO:

?C: This symbol, if defined, indicates that the ftello routine is

?C: available to ftell beyond 32 bits (useful for ILP32 hosts).

?C:.

?H:#\$d_ftello HAS_FTELLO /**/

?H:.

?LINT:set d_ftello

: see if ftello exists

set ftello d_ftello

eval \$inlibc

case "\$longsize" in

8) echo "(Your long is 64 bits, so you could use ftell.)" ;;

esac

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_ftello.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: i_mqueue.U,v \$

?RCS:

?RCS: Copyright (c) 1999 Jarkko Hietaniemi

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?MAKE:i_mqueue: Inhdr Hasfield

?MAKE: -pick add \$@ %<

?S:i_mqueue:

?S: This variable conditionally defines the I_MQUEUE symbol, and indicates

?S: whether a C program should include <mqueue.h>.

?S:.

?C:I_MQUEUE:

?C: This symbol, if defined, indicates that <mqueue.h> exists and

?C: should be included.

?C:.

?H:#\$i_mqueue I_MQUEUE /**/

?H:.

?LINT:set i_mqueue

: see if this is a mqueue.h system

set mqueue.h i_mqueue

eval \$inhdr

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/i_mqueue.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: i_pwd.U,v 3.0.1.2 1995/07/25 14:10:57 ram Exp \$

?RCS:

?RCS: Copyright (c) 1991-1993, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 3.0.

?RCS:

?RCS: \$Log: i_pwd.U,v \$

?RCS: Revision 3.0.1.2 1995/07/25 14:10:57 ram

?RCS: patch56: use setvar so hint file values can override our guesses (ADO)

?RCS:

?RCS: Revision 3.0.1.1 1994/05/06 15:03:27 ram

?RCS: patch23: had forgotten cppminus in cppstdin test (ADO)

?RCS:

?RCS: Revision 3.0 1993/08/18 12:08:25 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?X:

?X: This unit checks whether there is a pwd system or not

?X:

?MAKE:i_pwd d_pwquota d_pwage d_pwchange
d_pwclass d_pwexpire \
d_pwgecos d_pwpasswd d_pwcomment: \
contains rm cppstdin cppflags cppminus Inhdr Findhdr Setvar

?MAKE: -pick add \$@ %<

?S:i_pwd:

?S: This variable conditionally defines I_PWD, which indicates
?S: to the C program that it should include <pwd.h>.

?S:.

?S:d_pwquota:

?S: This variable conditionally defines PWQUOTA, which indicates
?S: that struct passwd contains pw_quota.

?S:.

?S:d_pwage:

?S: This variable conditionally defines PWAGE, which indicates
?S: that struct passwd contains pw_age.

?S:.

?S:d_pwchange:

?S: This variable conditionally defines PWCHANGE, which indicates
?S: that struct passwd contains pw_change.

?S:.

?S:d_pwclass:

?S: This variable conditionally defines PWCLASS, which indicates
?S: that struct passwd contains pw_class.

?S:.

?S:d_pwexpire:

?S: This variable conditionally defines PWEXPIRE, which indicates
?S: that struct passwd contains pw_expire.

?S:.

?S:d_pwcomment:

?S: This variable conditionally defines PWCOMMENT, which indicates
?S: that
struct passwd contains pw_comment.

?S:.

?S:d_pwgecos:

?S: This variable conditionally defines PWGECOS, which indicates
?S: that struct passwd contains pw_gecos.

?S:.

?S:d_pwpasswd:

?S: This variable conditionally defines PWPASSWD, which indicates
?S: that struct passwd contains pw_passwd.
?S:.
?C:I_PWD:
?C: This symbol, if defined, indicates to the C program that it should
?C: include <pwd.h>.
?C:.
?C:PWQUOTA:
?C: This symbol, if defined, indicates to the C program that struct passwd
?C: contains pw_quota.
?C:.
?C:PWAGE:
?C: This symbol, if defined, indicates to the C program that struct passwd
?C: contains pw_age.
?C:.
?C:PWCHANGE:
?C: This symbol, if defined, indicates to the C program that struct passwd
?C: contains pw_change.
?C:.
?C:PWCLASS:
?C: This symbol, if defined, indicates to the C program that struct passwd
?C: contains pw_class.
?C:.
?C:PWEXPIRE:
?C: This symbol, if defined, indicates to the C program that struct passwd
?C: contains pw_expire.
?C:.
?C:PWCOMMENT:
?C: This
symbol, if defined, indicates to the C program that struct passwd
?C: contains pw_comment.
?C:.
?C:PWGECOS:
?C: This symbol, if defined, indicates to the C program that struct passwd
?C: contains pw_gecos.
?C:.
?C:PWPASSWD:
?C: This symbol, if defined, indicates to the C program that struct passwd
?C: contains pw_passwd.
?C:.
?H:#\$i_pwd I_PWD /**/
?H:#\$d_pwquota PWQUOTA /**/
?H:#\$d_pwage PWAGE /**/
?H:#\$d_pwchange PWCHANGE /**/
?H:#\$d_pwclass PWCLASS /**/
?H:#\$d_pwexpire PWEXPIRE /**/
?H:#\$d_pwcomment PWCOMMENT /**/
?H:#\$d_pwgecos PWGECOS /**/

```

?H:#$d_pwpasswd PWPASSWD /**/
?H:.
?LINT: set i_pwd d_pwquota d_pwage d_pwchange d_pwclass d_pwexpire d_pwcomment
?LINT: set d_pwgecos d_pwpasswd
?T:xxx
: see if this is a pwd.h system
set pwd.h i_pwd
eval $inhdr

case "$i_pwd" in
$define)
xxx=`./findhdr pwd.h`
$cpstdin $cppflags $cppminus < $xxx >$$.h

if $contains 'pw_quota' $$h >/dev/null 2>&1; then
val="$define"
else
val="$undef"
fi
set d_pwquota
eval $setvar

if $contains 'pw_age'
$$h >/dev/null 2>&1; then
val="$define"
else
val="$undef"
fi
set d_pwage
eval $setvar

if $contains 'pw_change' $$h >/dev/null 2>&1; then
val="$define"
else
val="$undef"
fi
set d_pwchange
eval $setvar

if $contains 'pw_class' $$h >/dev/null 2>&1; then
val="$define"
else
val="$undef"
fi
set d_pwclass
eval $setvar

if $contains 'pw_expire' $$h >/dev/null 2>&1; then

```

```

    val="$define"
else
    val="$undef"
fi
set d_pwexpire
eval $setvar

if $contains 'pw_comment' $$h >/dev/null 2>&1; then
    val="$define"
else
    val="$undef"
fi
set d_pwcomment
eval $setvar

if $contains 'pw_gecos' $$h >/dev/null 2>&1; then
    val="$define"
else
    val="$undef"
fi
set d_pwgecos
eval $setvar

if $contains 'pw_passwd' $$h >/dev/null 2>&1; then
    val="$define"
else
    val="$undef"
fi
set d_pwpasswd
eval $setvar

$rm -f $$h
;;
*)
val="$undef";
set d_pwquota; eval $setvar
set d_pwage; eval $setvar
set d_pwchange; eval $setvar
set d_pwclass; eval $setvar
set
d_pwexpire; eval $setvar
set d_pwcomment; eval $setvar
set d_pwgecos; eval $setvar
set d_pwpasswd; eval $setvar
;;
esac

```

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/modified/i_pwd.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1999 Jarkko Hietaniemi

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?MAKE:d_fstatfs : Inlibc

?MAKE: -pick add \$@ %<

?S:d_fstatfs:

?S: This variable conditionally defines the HAS_FSTATFS symbol, which

?S: indicates to the C program that the fstatfs() routine is available.

?S:.

?C:HAS_FSTATFS:

?C: This symbol, if defined, indicates that the fstatfs routine is

?C: available to stat filesystems by file descriptors.

?C:.

?H:#\$d_fstatfs HAS_FSTATFS /**/

?H:.

?LINT:set d_fstatfs

: see if fstatfs exists

set fstatfs d_fstatfs

eval \$inlibc

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_fstatfs.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: models.U 1 2006-08-24 12:32:52Z rmanfredi \$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: models.U,v \$

?RCS: Revision 3.0.1.2 1997/02/28 16:13:17 ram

?RCS: patch61: added ?F: metalint hint

?RCS:

?RCS: Revision 3.0.1.1 1993/08/25 14:02:39 ram

?RCS: patch6: added default for large
?RCS:
?RCS: Revision 3.0 1993/08/18 12:09:17 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:models split small medium large huge: test cat Myread sysman Oldconfig \
Loc contains rm
?MAKE: -pick add \$@ %<
?S:models:
?S: This variable contains
the list of memory models supported by this
?S: system. Possible component values are none, split, unsplit, small,
?S: medium, large, and huge. The component values are space separated.
?S:.
?S:split:
?S: This variable contains a flag which will tell the C compiler and loader
?S: to produce a program that will run in separate I and D space, for those
?S: machines that support separation of instruction and data space. It is
?S: up to the Makefile to use this.
?S:.
?S:small:
?S: This variable contains a flag which will tell the C compiler and loader
?S: to produce a program running with a small memory model. It is up to
?S: the Makefile to use this.
?S:.
?S:medium:
?S: This variable contains a flag which will tell the C compiler and loader
?S: to produce a program running with a medium memory model. If the
?S: medium model is not supported, contains the flag to produce large
?S: model programs. It is up to the Makefile to use this.
?S:.
?S:large:
?S: This variable contains a flag
which will tell the C compiler and loader
?S: to produce a program running with a large memory model. It is up to
?S: the Makefile to use this.
?S:.
?S:huge:
?S: This variable contains a flag which will tell the C compiler and loader
?S: to produce a program running with a huge memory model. If the
?S: huge model is not supported, contains the flag to produce large
?S: model programs. It is up to the Makefile to use this.
?S:.
?T:unsplit tans modelcc
?F:!pdp11
?D:large=""
?LINT:extern cc
: see what memory models we can support

```
case "$models" in
```

```
)
```

?X: We may not use Cppsym or we get a circular dependency through cc.

?X: But this should work regardless of which cc we eventually use.

```
$cat >pdp11.c <<'EOP'
```

```
int main() {
```

```
#ifdef pdp11
```

```
exit(0);
```

```
#else
```

```
exit(1);
```

```
#endif
```

```
}
```

```
EOP
```

?X: Run cc in a subshell in case they don't have a 'cc' command.

?X: Presumably they do have gcc or something.

```
case "$cc" in
```

```
) modelcc="$cc" ;;
```

```
*) modelcc="cc" ;;
```

```
esac
```

```
( $modelcc -o pdp11 pdp11.c ) >/dev/null 2>&1
```

```
if
```

```
$test -f pdp11 && ./pdp11 2>/dev/null; then
```

```
  dflt='unsplit split'
```

```
else
```

```
tans=`./loc . X /lib/small /lib/large /usr/lib/small /usr/lib/large /lib/medium /usr/lib/medium /lib/huge`
```

```
case "$tans" in
```

```
X) dflt='none';;
```

```
*) if $test -d /lib/small || $test -d /usr/lib/small; then
```

```
  dflt='small'
```

```
else
```

```
  dflt="
```

```
fi
```

```
if $test -d /lib/medium || $test -d /usr/lib/medium; then
```

```
  dflt="$dflt medium"
```

```
fi
```

```
if $test -d /lib/large || $test -d /usr/lib/large; then
```

```
  dflt="$dflt large"
```

```
fi
```

```
if $test -d /lib/huge || $test -d /usr/lib/huge; then
```

```
  dflt="$dflt huge"
```

```
fi
```

```
esac
```

```
fi;;
```

```
*) dflt="$models";;
```

```
esac
```

```
$cat <<EOM
```

Some systems have different model sizes. On most systems they are called

small, medium, large, and huge. On the PDP11 they are called unsplit and split. If your system doesn't support different memory models, say "none". If you wish to force everything to one memory model, say "none" here and put the appropriate flags later when it asks you for other cc and ld flags.

Venix systems may wish to put "none" and let the compiler figure things out. (In the following question multiple model names should be space separated.)

The default for most systems is "none".

EOM

```
rp="Which memory models are supported?"
./myread
models="$ans"

case "$models" in
none)
small="
medium="
large="
huge="
unsplit="
split="
;;
*split)
case "$split" in
") if $contains '-i' $sysman/ld.1 >/dev/null 2>&1 || \
    $contains '-i' $sysman/cc.1 >/dev/null 2>&1; then
dflt='-i'
else
dflt='none'
fi;;
*) dflt="$split";;
esac
rp="What flag indicates separate I and D space?"
./myread
tans="$ans"
case "$tans" in
none) tans="";;
esac
split="$tans"
unsplit="";;
*large*|*small*|*medium*|*huge*)
case "$models" in
*large*)
case "$large" in
") dflt='-M!';;
*) dflt="$large";;
```

```

esac
rp="What flag indicates large model?"
./myread
tans="$ans"
case "$tans" in
none) tans="";
esac
large="$tans";;
*) large="";;
esac
case "$models"
in
*huge*) case "$huge" in
") dflt='-Mh';;
*) dflt="$huge";;
esac
rp="What flag indicates huge model?"
./myread
tans="$ans"
case "$tans" in
none) tans="";
esac
huge="$tans";;
*) huge="$large";;
esac
case "$models" in
*medium*) case "$medium" in
") dflt='-Mm';;
*) dflt="$medium";;
esac
rp="What flag indicates medium model?"
./myread
tans="$ans"
case "$tans" in
none) tans="";
esac
medium="$tans";;
*) medium="$large";;
esac
case "$models" in
*small*) case "$small" in
") dflt='none';;
*) dflt="$small";;
esac
rp="What flag indicates small model?"
./myread
tans="$ans"
case "$tans" in

```

```

none) tans=";
esac
small="$stans";;
*) small=";
esac
;;
*)
echo "Unrecognized memory models--you may have to edit Makefile.SH" >&4
;;
esac
$rm -f pdp11.* pdp11

```

Found in path(s):

```

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/modified/models.U

```

No license file was found, but licenses were detected in source scan.

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?MAKE:d_fdim: Inlibc

?MAKE: -pick add \$@ %<

?S:d_fdim:

?S: This variable conditionally defines the HAS_FDIM symbol, which

?S: indicates to the C program that the fdim() routine is available.

?S:.

?C:HAS_FDIM:

?C: This symbol, if defined, indicates that the fdim routine is

?C: available to do the positive difference function.

?C:.

?H:#\$d_fdim HAS_FDIM /**/

?H:.

?LINT:set d_fdim

: see if fdim exists

set fdim d_fdim

eval \$inlibc

Found in path(s):

```

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/perl/d_fdim.U

```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1999 Jarkko Hietaniemi

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:
?MAKE:d_statfs: Inlibc
?MAKE: -pick add \$@ %<
?S:d_statfs:
?S: This variable conditionally defines the HAS_STATFS symbol, which
?S: indicates to the C program that the statfs() routine is available.
?S:.
?C:HAS_STATFS:
?C: This symbol, if defined, indicates that the statfs routine is
?C: available to stat filesystems by filenames.
?C:.
?H:#\$d_statfs HAS_STATFS /**/
?H:.
?LINT:set d_statfs
: see if statfs exists
set statfs d_statfs
eval \$inlibc

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_statfs.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_fgetpos.U 1 2006-08-24 12:32:52Z rmanfredi \$
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: \$Log: d_fgetpos.U,v \$
?RCS: Revision 3.0.1.1 1994/06/20 06:57:33 ram
?RCS: patch30: created
?RCS:
?MAKE:d_fgetpos: Inlibc
?MAKE: -pick add \$@ %<
?S:d_fgetpos:
?S: This variable conditionally defines HAS_FGETPOS if fgetpos() is
?S: available to get the file position indicator.
?S:.
?C:HAS_FGETPOS:
?C: This symbol, if defined, indicates that the fgetpos routine is
?C: available to get the file position indicator, similar to ftell().
?C:.
?H:#\$d_fgetpos

HAS_FGETPOS /**/

?H:.

?LINT:set d_fgetpos

: see if fgetpos exists

set fgetpos d_fgetpos

eval \$inlibc

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/d_fgetpos.U

No license file was found, but licenses were detected in source scan.

?RCS: You may redistribute only under the terms of the Artistic Licence,

?RCS: as specified in the README file that comes with the distribution.

?RCS:

?MAKE:i_fenv: Inhdr

?MAKE: -pick add \$@ %<

?S:i_fenv:

?S: This variable conditionally defines the I_FENV symbol, which

?S: indicates to the C program that <fenv.h> exists and should

?S: be included.

?S:.

?C:I_FENV:

?C: This symbol, if defined, indicates to the C program that it should

?C: include <fenv.h> to get the floating point environment definitions.

?C:.

?H:#\$i_fenv I_FENV /**/

?H:.

?LINT:set i_fenv

: see if this is a fenv.h system

set fenv.h i_fenv

eval \$inhdr

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/i_fenv.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic Licence,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic Licence; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

```

?RCS: $Log: cf_email.U,v $
?RCS: Revision 3.0.1.1 1994/01/24 14:05:06 ram
?RCS: patch16: created
?RCS:
?RCS:
?MAKE:cf_email: cat cf_by test myhostname mydomain Oldconfig Myread
?MAKE: -pick add $@ %<
?S:cf_email:
?S: Electronic mail address of the person who ran Configure. This can be
?S: used by units that require the user's e-mail, like MailList.U.
?S:.
?T:cont maildomain
?LINT:extern MAILDOMAIN
: determine the e-mail address of the user who is running us
$cat <<EOM

```

I need to get your e-mail address
in Internet format if possible, i.e.
something like user@host.domain. Please answer accurately since I have
no easy means to double check it. The default value provided below
is most probably close to reality but may not be valid from outside
your organization...

EOM

```

cont=x
while test "$cont"; do
case "$MAILDOMAIN" in
")
if $test -s /etc/mailname; then
maildomain=`$cat /etc/mailname`
else
maildomain="$myhostname$mydomain"
fi
;;
*) maildomain="$MAILDOMAIN";;
esac
case "$cf_email" in
") dflt="$cf_by@$maildomain";;
*) dflt="$cf_email";;
esac
rp='What is your e-mail address?'
. ./myread
cf_email="$ans"
case "$cf_email" in
*@*.*) cont="";;
*)
rp='Address does not look like an Internet one. Use it anyway?'
case "$fastread" in

```

```

yes) dflt=y ;;
*) dflt=n ;;
esac
. ./myread
case "$ans" in
y*) cont=" " ;;
*) echo " " ;;
esac
;;
esac
done

```

Found in path(s):

```

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/cf_email.U

```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: Tr.U,v \$

?RCS: Revision 3.0.1.2 1994/10/29 18:00:54 ram

?RCS: patch43: forgot to quote \$@ to protect against "evil" characters

?RCS:

?RCS: Revision 3.0.1.1 1994/10/29 15:58:35 ram

?RCS: patch36: created

?RCS:

?X:

?X: This unit produces a bit of shell code that must be dotted in in order

?X: to do a character translation. It catches translations to uppercase or

?X: to lowercase, and then invokes the real tr to perform the job.

?X:

?X: This unit is necessary on HP machines (HP strikes again!)

with non-ascii

?X: ROMAN8-charset, where normal letters are not arranged in a row, so a-z

?X: covers not the whole alphabet but lots of special chars. This was reported

?X: by Andreas Sahlbach <a.sahlbach@tu-bs.de>.

?X:

?X: Units performing a tr '[A-Z]' '[a-z]' or the other way round should include

?X: us in their dependency and use ./tr instead.

?X:

```

?MAKE:Tr: startsh tr eunicefix
?MAKE: -pick add $@ %<
?F:./tr
?T:up low LC_ALL
: see whether [:lower:] and [:upper:] are supported character classes
echo " "
case "`echo AbyZ | LC_ALL=C $tr '[:lower:]' '[:upper:]' 2>/dev/null`" in
ABYZ)
echo "Good, your tr supports [:lower:] and [:upper:] to convert case." >&4
up='[:upper:]'
low='[:lower:]'
;;
*) # There is a discontinuity in EBCDIC between 'I' and 'J'
# (0xc9 and 0xd1), therefore that is a nice testing point.
if test "X$up" = X -o "X$low" = X; then
case "`echo IJ | LC_ALL=C $tr '[I-J]' '[i-j]' 2>/dev/null`" in
ij) up='[A-Z]'
low='[a-z]'
;;
esac
fi
if test "X$up" = X -o "X$low" = X; then
case "`echo IJ | LC_ALL=C $tr I-J i-j 2>/dev/null`" in
ij) up='A-Z'
low='a-z'
;;
esac
fi
if test "X$up" = X -o "X$low" = X; then
case "`echo IJ | od -x 2>/dev/null`" in
*C9D1*|*c9d1*)
echo "Hey, this might be EBCDIC." >&4
if test "X$up" = X -o "X$low" = X; then
case "`echo IJ | \
LC_ALL=C $tr '[A-IJ-RS-Z]' '[a-ij-rs-z]' 2>/dev/null`" in
ij) up='[A-IJ-RS-Z]'
low='[a-ij-rs-z]'
;;
esac
fi
if test "X$up" = X -o "X$low" = X; then
case "`echo IJ | LC_ALL=C $tr A-IJ-RS-Z a-ij-rs-z 2>/dev/null`" in
ij) up='A-IJ-RS-Z'
low='a-ij-rs-z'
;;
esac
fi

```

```

;;
    esac
fi
esac
case "`echo IJ | LC_ALL=C $tr \"$Sup\" \"$Slow\" 2>/dev/null`" in
ij)
    echo "Using $Sup and $Slow to convert case." >&4
    ;;
*)
    echo "I don't know how to translate letters from upper to lower case." >&4
    echo "Your tr is not acting any way I know of." >&4
    exit 1
    ;;
esac
: set up the translation script tr, must be called with ./tr of course
cat >tr <<EOSC
$startsh
case "$1\"$2" in
[A-Z][a-z]) LC_ALL=C exec $tr '$Sup' '$Slow';;
[a-z][A-Z]) LC_ALL=C exec $tr '$Slow' '$Sup';;
esac
LC_ALL=C exec $tr "\$@"
EOSC
chmod +x tr
$eunicefix tr

```

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/Tr.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1999, Jarkko Hietaniemi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 3.0.

?RCS:

?MAKE:d_timer_settime: Inlibc

?MAKE:-pick add \$@ %<

?S:d_timer_settime:

?S: This variable conditionally defines HAS_TIMER_SETTIME

?S: if timer_settime() is available to set the time of a POSIX timer.

?S:.

?C:HAS_TIMER_SETTIME:

?C: This symbol, if defined, indicates that the timer_settime
?C: system call is available to set the time of a POSIX timer.
?C:.

?H:#\$d_timer_settime HAS_TIMER_SETTIME /**/

?H:.

?LINT:set d_timer_settime

: see if timer_settime exists

set timer_settime d_timer_settime

eval \$inlibc

Found in path(s):

*

/opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/perl/d_timer_settime.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_tmpnam_r.U,v 0RCS:

?RCS: Copyright (c) 2002,2003 Jarkko Hietaniemi

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?RCS: Generated by the reentr.pl from the Perl 5.8 distribution.

?RCS:

?MAKE:d_tmpnam_r tmpnam_r_proto: Inlibc Protochk Hasproto i_systypes \
usethreads extern_C

?MAKE: -pick add \$@ %<

?S:d_tmpnam_r:

?S: This variable conditionally defines the HAS_TMPNAM_R symbol,

?S: which indicates to the C program that the tmpnam_r()

?S: routine is available.

?S:.

?S:tmpnam_r_proto:

?S: This variable encodes the prototype of tmpnam_r.

?S: It is zero if d_tmpnam_r is undef, and one of the

?S: REENTRANT_PROTO_T_ABC macros of reentr.h if d_tmpnam_r

?S: is defined.

?S:.

?C:HAS_TMPNAM_R:

?C: This symbol, if defined, indicates that the tmpnam_r routine

?C: is available to tmpnam re-entrantly.

?C:.

?C:TMPNAM_R_PROTO:

?C: This

symbol encodes the prototype of tmpnam_r.

?C: It is zero if d_tmpnam_r is undef, and one of the

?C: REENTRANT_PROTO_T_ABC macros of reentr.h if d_tmpnam_r

?C: is defined.

```

?C:.
?H:#$d_tmpnam_r HAS_TMPNAM_R  /**/
?H:#define TMPNAM_R_PROTO $tmpnam_r_proto  /**/
?H:.
?T:try hdrs d_tmpnam_r_proto
: see if tmpnam_r exists
set tmpnam_r d_tmpnam_r
eval $inlibc
case "$d_tmpnam_r" in
"$define")
hdrs="$i_systypes sys/types.h define stdio.h "
case "$d_tmpnam_r_proto:$usethreads" in
":define") d_tmpnam_r_proto=define
set d_tmpnam_r_proto tmpnam_r $hdrs
eval $hasproto ;;
*) ;;
esac
case "$d_tmpnam_r_proto" in
define)
case "$tmpnam_r_proto" in
"|0) try='char* tmpnam_r(char*);'
./protochk "$extern_C $try" $hdrs && tmpnam_r_proto=B_B ;;
esac
case "$tmpnam_r_proto" in
"|0) d_tmpnam_r=undef
tmpnam_r_proto=0
echo "Disabling tmpnam_r, cannot determine prototype." >&4 ;;
* ) case "$tmpnam_r_proto" in
REENTRANT_PROTO*) ;;
*) tmpnam_r_proto="REENTRANT_PROTO_$tmpnam_r_proto"
;;
esac
echo "Prototype: $try" ;;
esac
;;
*) case "$usethreads" in
define) echo "tmpnam_r has no prototype, not using it." >&4 ;;
esac
d_tmpnam_r=undef
tmpnam_r_proto=0
;;
esac
;;
*) tmpnam_r_proto=0
;;
esac

```

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/threads/d_tmpnam_r.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1998 Jarkko Hietaniemi

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?MAKE:d_accessx: Inlibc

?MAKE: -pick add \$@ %<

?S:d_accessx:

?S: This variable conditionally defines the HAS_ACCESSX symbol, which

?S: indicates to the C program that the accessx() routine is available.

?S:.

?C:HAS_ACCESSX :

?C: This symbol, if defined, indicates that the accessx routine is

?C: available to do extended access checks.

?C:.

?H:#\$d_accessx HAS_ACCESSX /**/

?H:.

?LINT:set d_accessx

: see if accessx exists

set accessx d_accessx

eval \$inlibc

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/acl/d_accessx.U

No license file was found, but licenses were detected in source scan.

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?MAKE:usequadmath: Setvar cat uselongdouble

?MAKE: -pick add \$@ %<

?S:usequadmath:

?S: This variable conditionally defines the USE_QUADMATH symbol,

?S: and indicates that the quadmath library __float128 long doubles

?S: should be used when available.

?S:.

?C:USE_QUADMATH:

?C: This symbol, if defined, indicates that the quadmath library should

?C: be used when available.

?C:.

?H:??<:#ifndef USE_QUADMATH

```

?H:%<:#$usequadmath USE_QUADMATH /**/
?H:%<:#endif
?H.:
: Check if quadmath is requested
case "$usequadmath" in
"$define"|true|[yY]*) usequadmath="$define" ;;
*) usequadmath="$undef" ;;
esac

: Fail if both uselongdouble and usequadmath are requested
case "$usequadmath:$uselongdouble" in
define:define)
$cat <<EOM >&4

*** You requested the use of
the quadmath library and use
*** of long doubles.
***
*** Please select one or the other.
EOM
exit 1
;;
esac

```

Found in path(s):

```

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/perl/usequadmath.U

```

No license file was found, but licenses were detected in source scan.

```

?RCS: $Id: d_munmap.U 1 2006-08-24 12:32:52Z rmanfredi $
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: $Log: d_munmap.U,v $
?RCS: Revision 3.0.1.1 1993/12/15 08:19:22 ram
?RCS: patch15: created
?RCS:
?MAKE:d_munmap: Inlibc
?MAKE: -pick add $@ %<
?S:d_munmap:
?S: This variable conditionally defines HAS_MUNMAP if munmap() is
?S: available to unmap a region mapped by mmap().

```

?S:.

?C:HAS_MUNMAP:

?C: This symbol, if defined, indicates that the munmap system call is

?C: available to unmap a region, usually mapped by mmap().

?C:.

?H:#\$d_munmap HAS_MUNMAP /**/

?H:.

?LINT:set

d_munmap

: see if munmap exists

set munmap d_munmap

eval \$inlibc

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/d_munmap.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_sigvec.U 1 2006-08-24 12:32:52Z rmanfredi \$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic Licence,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic Licence; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: d_sigvec.U,v \$

?RCS: Revision 3.0.1.1 1997/02/28 15:45:37 ram

?RCS: patch61: there is now a separate routine for sigaction()

?RCS:

?RCS: Revision 3.0 1993/08/18 12:07:24 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?X: d_sigvec.U, from d_ftime.U 1.0

?X:

?MAKE:d_sigvec d_sigvectr d_sigintrp: Csym Inlibc Setvar

?MAKE: -pick add \$@ %<

?S:d_sigvec:

?S: This variable conditionally defines the HAS_SIGVEC symbol, which indicates

?S: that BSD

reliable signals are supported.

?S:.

?S:d_sigvectr:

?S: This variable conditionally defines the HAS_SIGVECTOR symbol, which

?S: indicates that the sigvec() routine is called sigvector() instead, for

?S: reasons known only to Hewlett-Packard.

?S:.

?S:d_sigintrp:

?S: This variable conditionally defines the HAS_SIGINTRP symbol, which
 ?S: indicates that the siginterrupt() routine is available.

?S:.

?C:HAS_SIGVEC (SIGVEC):

?C: This symbol, if defined, indicates that BSD reliable signals are
 ?C: supported.

?C:.

?C:HAS_SIGVECTOR (SIGVECTOR):

?C: This symbol, if defined, indicates that the sigvec() routine is called
 ?C: sigvector() instead, and that sigspace() is provided instead of
 ?C: sigstack(). This is probably only true for HP-UX.

?C:.

?C:HAS_SIGINTRP (SIGINTRP):

?C: This symbol, if defined, indicates that the siginterrupt() routine
 ?C: is available.

?C:.

?H:#\$d_sigvec HAS_SIGVEC /**/
 ?H:#\$d_sigvectr HAS_SIGVECTOR /**/
 ?H:#\$d_sigintrp HAS_SIGINTRP /**/
 ?H:.

?T:val

?LINT:set d_sigvec d_sigintrp

@if

 d_sigvectr || d_sigvec || HAS_SIGVEC || HAS_SIGVECTOR
 : see if sigvector exists -- since sigvec will match the substring
 echo " "

 if set sigvector val -f d_sigvectr; eval \$csym; \$val; then
 echo 'sigvector() found--you must be running HP-UX.' >&4
 val="\$define"; set d_sigvectr; eval \$setvar
 val="\$define"; set d_sigvec; eval \$setvar
 else
 : try the original name
 d_sigvectr="\$undef"
 if set sigvec val -f d_sigvec; eval \$csym; \$val; then
 echo 'sigvec() found.' >&4
 val="\$define"; set d_sigvec; eval \$setvar
 else
 echo 'sigvec() not found--race conditions with signals may occur.' >&4
 val="\$undef"; set d_sigvec; eval \$setvar
 fi
 fi

@end

@if d_sigintrp || HAS_SIGINTRP
 : see if we have siginterrupt
 set siginterrupt d_sigintrp

eval \$inlibc

@end

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/d_sigvec.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_perlio.U,v \$

?RCS:

?RCS: Copyright (c) 1998 Andy Dougherty

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?RCS: \$Log: d_perlio.U,v \$

?RCS:

?MAKE:useperlio: Myread Oldconfig Setvar

?MAKE: -pick add \$@ %<

?Y:TOP

?S:useperlio:

?S: This variable conditionally defines the USE_PERLIO symbol,

?S: and indicates that the PerLIO abstraction should be

?S: used throughout.

?S:.

?C:USE_PERLIO:

?C: This symbol, if defined, indicates that the PerLIO abstraction should

?C: be used throughout. If not defined, stdio should be

?C: used in a fully backward compatible manner.

?C:.

?H:?%<:#ifndef USE_PERLIO

?H:?%<:#\$useperlio USE_PERLIO /**/

?H:?%<:#endif

?H:.

: Check if we want perlio

useperlio="\$define"

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/useperlio.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: Head.U 6 2006-08-25 22:21:46Z rmanfredi \$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: \$Log: Head.U,v \$
?RCS: Revision 3.0.1.9 1997/02/28 15:02:09 ram
?RCS: patch61: make sure we unset CDPATH for shells that support this
?RCS: patch61: improved Korn shell detection and handling
?RCS:
?RCS: Revision 3.0.1.8 1995/07/25 13:40:02 ram
?RCS: patch56: added SVR4-ish /opt directories to path list (ADO)
?RCS: patch56: OS/2 platforms are using another path separator
?RCS:
?RCS: Revision 3.0.1.7 1995/03/21 08:46:15 ram
?RCS: patch52: definition of
paths wrongly added spurious '.' chars
?RCS:
?RCS: Revision 3.0.1.6 1994/10/29 15:54:19 ram
?RCS: patch36: make sure ENV is unset before calling /bin/ksh
?RCS:
?RCS: Revision 3.0.1.5 1994/08/29 16:03:44 ram
?RCS: patch32: now sets PATH only using existing directories
?RCS:
?RCS: Revision 3.0.1.4 1994/06/20 06:54:28 ram
?RCS: patch30: now computes its invocation name into 'me'
?RCS: patch30: symbol me is made visible to all units read-only
?RCS:
?RCS: Revision 3.0.1.3 1993/12/15 08:15:07 ram
?RCS: patch15: added /sbin:/usr/sbin:/usr/libexec in PATH for BSD/386
?RCS:
?RCS: Revision 3.0.1.2 1993/11/10 17:32:35 ram
?RCS: patch14: ensure PATH is reset to '.' before testing for alias
?RCS:
?RCS: Revision 3.0.1.1 1993/08/27 14:38:07 ram
?RCS: patch7: not all 'test' programs support the -x option
?RCS:
?RCS: Revision 3.0 1993/08/18 12:04:58 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?X:
?X: This is the very first unit in the Configure script. It is mostly just
?X:
things to keep people from getting into a tizzy right off the bat.
?X:
?MAKE:Head:
?MAKE: -pick wipe \$@ %<
?V:PATH p_ _exe me newsh

```

?T:argv p paths OS2_SHELL DJGPP
?T:inksh needksh avoidksh newsh changesh reason
?F:!*
?LINT:extern ENV CDPATH SHELL MACHTYPE _exe is_os2
?LINT:change ENV CDPATH is_os2
?LINT:nocomment
#! /bin/sh
#
# If these # comments don't work, trim them. Don't worry about any other
# shell scripts, Configure will trim # comments from them for you.
#
# (If you are trying to port this package to a machine without sh,
# I would suggest you have a look at the prototypical config_h.SH file
# and edit it to reflect your system. Some packages may include samples
# of config.h for certain machines, so you might look for one of those.)
#
?X:
?X: NOTE THAT A CONFIGURE SCRIPT IS IN THE PUBLIC DOMAIN (whether or not
?X: the software which uses it is in the public domain).
?X:
# Yes, you may rip this off to use in other distribution packages. This
# script belongs to the public
# domain and cannot be copyrighted.
#
?X:
?X: WE ASK YOU NOT TO REMOVE OR ALTER THE FOLLOWING PARAGRAPH, PLEASE:
?X:
# Note: this Configure script was generated automatically by the tool
# called "metaconfig". Rather than working with this copy of Configure,
# you may wish to get metaconfig. Perl uses a modified version of this
# tool, available in the "dist" folder in the checkout of the git repo
# $ git clone git://perl5.git.perl.org/metaconfig.git metaconfig
# The original dist package (including metaconfig) is available via SVN:
# $ svn co https://svn.code.sf.net/p/dist/code/trunk/dist
#
?X: OK, I'll not alter, but I'll add to it then ...
# Though this script was generated by metaconfig from metaunits, it is
# OK to send patches against Configure itself. It's up to the Configure
# pumpkin to backport the patch to the metaunits if it is accepted.
# For more information on patching Configure, see pod/perlhack.pod
#
# The metaunits are also available from the public git repository:
#
# http://perl5.git.perl.org/metaconfig.git/ or
# $ git clone git://perl5.git.perl.org/metaconfig.git metaconfig
#
# See Porting/pumpkin.pod for more information on metaconfig.
?X:

```

?X: NOTA BENE:

?X: If you develop your own version of metaconfig based on this work,

?X: you have to add some comments telling that the script was generated

?X: by your version, not mine: It credits your work.

?X:

```
# Generated using [metaconfig <VERSION> PL<PATCHLEVEL>]
```

```
# (with additional metaconfig patches by <MAINTLOC>)
```

```
cat >c1$$ <<EOF
```

```
ARGGGHHHH!!!!
```

SCO csh still thinks true is false. Write to SCO today and tell them that next year Configure ought to "rm /bin/csh" unless they fix their blasted shell. :-)

(Actually, Configure ought to just patch csh in place. Hmm. Hmmmmm. All we'd have to do is go in and swap the && and || tokens, wherever they are.)

[End of diatribe. We now return you to your regularly scheduled programming...]

```
EOF
```

```
cat >c2$$ <<EOF
```

OOPS! You naughty creature! You didn't

run Configure with sh!

I will attempt to remedy the situation by running sh for you...

```
EOF
```

```
true || cat c1$$ c2$$
```

```
true || exec sh $0 $argv:q
```

```
(exit $?0) || cat c2$$
```

```
(exit $?0) || exec sh $0 $argv:q
```

```
rm -f c1$$ c2$$
```

```
if test -f /dev/cputype -a -f /dev/drivers -a -f /dev/osversion; then
```

```
cat <<EOF
```

```
***
```

```
*** I'm sorry but this system looks like Plan 9 and Plan 9 doesn't do
```

```
*** Configure that well. (Plan 9 is close to UNIX but not close enough.)
```

```
*** Please read the README.plan9 for further instructions.
```

```
*** Cannot continue, aborting.
```

```
***
```

```
EOF
```

```
exit 1
```

```
fi
```

```
if test -f /sys/utilities/MultiView ; then
```

```
# AmigaOS, test -c for /dev/null is not useful
```

```

:
elif test ! -c /dev/null ; then
  cat <<EOF
  ***
  *** I'm sorry, but /dev/null appears to be a file rather than a device.
  *** Please consult your operating system's notes for making a device
  *** in /dev.
  *** Cannot continue, aborting.
  ***
EOF
  exit 1
fi

```

```

: compute my invocation name
me=$0
case "$0" in
*/*)
  me=`echo $0 | sed -e 's!.*^\(.*\)!1!' 2>/dev/null`
  test
  "$me" || me=$0
  ;;
esac

```

?X:

?X: To be able to run under OS/2, we must detect that early enough to use

?X: the proper path separator, stored in \$p_. It is : on UNIX and ; on

?X: DOS-ish systems such as OS/2.

?X:

: Proper separator for the PATH environment variable

p_=:

: On OS/2 this directory should exist if this is not floppy only system ":-]"

if test -d c:/ || (uname -a | grep -i 'os\(\|\)2' 2>&1) 2>&1 >/dev/null ; then

if test -n "\$OS2_SHELL"; then

p_=\;

PATH=`cmd /c "echo %PATH%" | tr "\\\\" /`

?X: That's a bug in ksh5.22

OS2_SHELL=`cmd /c "echo %OS2_SHELL%" | tr "\\\\" / | tr '[A-Z]' '[a-z]`

is_os2=yes

elif test -n "\$DJGPP"; then

case "X\${MACHTYPE:-nonesuchmach}" in

*cygwin|*msys) ;;

*) p_=\; ;;

esac

fi

fi

?X:

?X: There are two schools of thoughts here. Some people correctly argue that

?X: the user has a better chance than we do of setting a reasonable PATH and
 ?X: others argue that Configure is the best place there is to set up a suitable
 ?X:
 PATH. Well, here we try to compromise by keeping the user's PATH and
 ?X: appending some directories which are known to work on some machine or the
 ?X: other. The rationale behind this being that a novice user might not have a
 ?X: proper environment variable set, and some directories like /etc (where
 ?X: chown is located on some BSD systems) may be missing--RAM.
 ?X:
 ?X: SVR4 adds an /opt directory for optional packages. Some sites use
 ?X: various permutations on /opt as opposed to /usr or /usr/local.-- ADO
 ?X:
 ?X: We only add directories that are not already in the PATH of the
 ?X: user and the directories must exist also.
 ?X:
 ?X: 20040627, Merijn, HP-UX's ANSI compiler is in /opt/ansic/bin if present
 ?X: and should be before /usr/ccs/bin, where the braindead bundled compiler
 ?X: can be found. The /usr/ccs/bin compiler cannot be used to build perl.
 ?X:

: Proper PATH setting

```
paths='/bin /usr/bin /usr/local/bin /usr/ucb /usr/local /usr/sbin'
paths="$paths /opt/bin /opt/local/bin /opt/local
/opt/sbin"
paths="$paths /usr/5bin /etc /usr/gnu/bin /usr/new /usr/new/bin /usr/sbin"
paths="$paths /opt/gnu/bin /opt/new /opt/new/bin /opt/sbin"
paths="$paths /sys5.3/bin /sys5.3/usr/bin /bsd4.3/bin /bsd4.3/usr/ucb"
paths="$paths /bsd4.3/usr/bin /usr/bsd /bsd43/bin /opt/ansic/bin /usr/ccs/bin"
paths="$paths /etc /usr/lib /usr/ucblib /lib /usr/ccs/lib"
paths="$paths /sbin /usr/sbin /usr/libexec"
paths="$paths /system/gnu_library/bin"
```

```
for p in $paths
do
case "$p_${PATH}$p_" in
*$p_${p}$p_*) ;;
*) test -d $p && PATH=${PATH}$p_$p ;;
esac
done
```

```
PATH=.$p_${PATH}
export PATH
```

```
: shall we be using ksh?
inksh=""
needksh=""
avoidksh=""
newsh=/bin/ksh
changesh=""
```

?X: Use (alias -x) and not (alias) since zsh and bash recognize the alias

?X: builtin but not the -x option which is typically ksh...

?X: We need to set up PATH before calling the "alias" built-in since some

?X: systems like HP-UX have a binary called /bin/alias.

```
if (PATH=.; alias -x) >/dev/null 2>&1; then
    inksh=true
fi
```

?X: On HP-UX,

large Configure scripts may exercise a bug in /bin/sh, use ksh

```
if test -f /hp-ux -a -f /bin/ksh; then
    needksh='to avoid sh bug in "here document" expansion'
fi
```

?X: On AIX4, /bin/sh is really ksh and it causes problems, use sh

```
if test -d /usr/lpp -a -f /usr/bin/bsh -a -f /usr/bin/uname; then
    if test X`/usr/bin/uname -v` = X4; then
        avoidksh="to avoid AIX 4's /bin/sh"
        newsh=/usr/bin/bsh
    fi
fi
```

?X: On Digital UNIX, /bin/sh may start up buggy /bin/ksh, use sh

```
if test -f /osf_boot -a -f /usr/sbin/setld; then
    if test X`/usr/bin/uname -s` = XOSF1; then
        avoidksh="to avoid Digital UNIX' ksh"
        newsh=/bin/sh
    fi
fi
```

?X: if BIN_SH is set to 'xpg4', sh will start up ksh

```
unset BIN_SH
fi
fi
```

?X: If we are not in ksh and need it, then feed us back to it

```
case "$inksh/$needksh" in
/[a-z]*)
```

?X: Clear ENV to avoid any ~/.kshrc that could alias cd or whatever...

?X: Don't use "unset ENV", that is not portable enough

```
ENV="
changesh=true
reason="$needksh"
;;
esac
```

?X: If we are in ksh and must

avoid it, then feed us back to a new shell

```
case "$inksh/$avoidksh" in
true/[a-z]*)
    changesh=true
    reason="$avoidksh"
    ;;
esac
```

?X: Warn them if they use ksh on other systems, which are those where

?X: we don't need ksh nor want to avoid it explicitly, yet are using it.

```

case "$sinksh/$needksh-$avoidksh-" in
true/--)
  cat <<EOM
(I see you are using the Korn shell. Some ksh's blow up on $me,
mainly on older exotic systems. If yours does, try the Bourne shell instead.)
EOM
;;
esac
case "$changelog" in
true)
  export newsh
  echo "(Feeding myself to $newsh $reason.)"
?X: Make sure they didn't say sh <Configure by checking whether $0 ends
?X: with Configure or not. If they did say sh <../Configure, then too
?X: bad for them anyway, since we lost that path indication...
?X: Otherwise, execing $0 ensures we keep the full remote source dir
?X: indication for src.U.
  case "$0" in
Configure|*/Configure) exec $newsh $0 "$@";;
*) exec $newsh Configure "$@";;
  esac
;;
esac
?X: 2004.06.09 rac
?X:
  having $newsh persist as ksh here is bad news if ksh doesn't really
?X: exist. this causes us to toss away a perfectly good working test in
?X: bash in favor of more exotic external options. see bug 42665.
test -x "${newsh}" || unset newsh

?X: Unset CDPATH to avoid surprises when using cd under some shells
?X: Can't unset it because that's not portable to very old shells.
?X: Can't set it to " because then bash 2.02 won't do "cd UU" --AD 6/98.
?X: Don't want to set it to '.' because then ksh prints out the
?X: name of the directory every time you cd to it. --AD 6/98
?X: In order to inflict the least harm, change it only if it's set.
: if needed, set CDPATH to a harmless value that is not chatty
: avoid bash 2.02 problems with empty CDPATH.
case "$CDPATH" in
") ;;
*) case "$SHELL" in
*bash*) CDPATH='.' ;;
*) CDPATH="" ;;
  esac
;;
esac

```

: Configure runs within the UU subdirectory

```
test -d UU || mkdir UU
?X: Use ./* to avoid any confirmation prompts from enhanced shells -- WED
cd
UU && rm -f ./*
```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/modified/Head.U
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_getspnam_r.U,v 0RCS:

?RCS: Copyright (c) 2002,2003 Jarkko Hietaniemi

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?RCS: Generated by the reentr.pl from the Perl 5.8 distribution.

?RCS:

```
?MAKE:d_getspnam_r getsppnam_r_proto: Inlibc Protochk Hasproto i_systypes \
  usethreads i_shadow extern_C
```

```
?MAKE: -pick add $@ %<
```

?S:d_getspnam_r:

?S: This variable conditionally defines the HAS_GETSPNAM_R symbol,

?S: which indicates to the C program that the getsppnam_r()

?S: routine is available.

?S:.

?S:getsppnam_r_proto:

?S: This variable encodes the prototype of getsppnam_r.

?S: It is zero if d_getspnam_r is undef, and one of the

?S: REENTRANT_PROTO_T_ABC macros of reentr.h if d_getspnam_r

?S: is defined.

?S:.

?C:HAS_GETSPNAM_R:

?C: This symbol, if defined, indicates that the getsppnam_r routine

?C: is available

to getsppnam re-entrantly.

?C:.

?C:GETSPNAM_R_PROTO:

?C: This symbol encodes the prototype of getsppnam_r.

?C: It is zero if d_getspnam_r is undef, and one of the

?C: REENTRANT_PROTO_T_ABC macros of reentr.h if d_getspnam_r

?C: is defined.

?C:.

```
?H:#$d_getspnam_r HAS_GETSPNAM_R /**/
```

```
?H:#define GETSPNAM_R_PROTO $getsppnam_r_proto /**/
```

?H:.

?T:try hdrs d_getspnam_r_proto

: see if getsppnam_r exists

```

set getspnam_r d_getspnam_r
eval $inlibc
case "$d_getspnam_r" in
"$define")
hdrs="$i_systypes sys/types.h define stdio.h $i_shadow shadow.h"
case "$d_getspnam_r_proto:$usetthreads" in
":define") d_getspnam_r_proto=define
set d_getspnam_r_proto getspnam_r $hdrs
eval $hasproto ;;
*) ;;
esac
case "$d_getspnam_r_proto" in
define)
case "$getspnam_r_proto" in
"|0) try='int getspnam_r(const char*, struct spwd*, char*, size_t, struct spwd**);'
./protochk "$extern_C $try" $hdrs && getspnam_r_proto=I_CSBWR ;;
esac
case "$getspnam_r_proto" in
"|0) try='struct spwd* getspnam_r(const char*,
struct spwd*, char*, int);'
./protochk "$extern_C $try" $hdrs && getspnam_r_proto=S_CSBI ;;
esac
case "$getspnam_r_proto" in
"|0) d_getspnam_r=undef
getspnam_r_proto=0
echo "Disabling getspnam_r, cannot determine prototype." >&4 ;;
* ) case "$getspnam_r_proto" in
REENTRANT_PROTO*) ;;
*) getspnam_r_proto="REENTRANT_PROTO_$getspnam_r_proto" ;;
esac
echo "Prototype: $try" ;;
esac
;;
*) case "$usetthreads" in
define) echo "getspnam_r has no prototype, not using it." >&4 ;;
esac
d_getspnam_r=undef
getspnam_r_proto=0
;;
esac
;;
*) getspnam_r_proto=0
;;
esac

```

Found in path(s):

```

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/threads/d_getspnam_r.U

```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: i_features.U,v $
?RCS:
?RCS: Copyright (c) 2001 Jarkko Hietaniemi
?RCS:
?RCS: You may distribute under the terms of either the GNU General Public
?RCS: License or the Artistic License, as specified in the README file.
?RCS:
?MAKE:i_features: Inhdr Hasfield
?MAKE: -pick add $@ %<
?S:i_features:
?S: This variable conditionally defines the I_FEATURES symbol,
?S: and indicates whether a C program should include <features.h>.
?S:.
?C:I_FEATURES:
?C: This symbol, if defined, indicates that <features.h> exists and
?C: should be included.
?C:.
?H:#$i_features I_FEATURES /**/
?H:.
?LINT:set i_features
: see if this is a features.h system
set features.h i_features
eval $inhdr
```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/perl/i_features.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: kernel.U 1 2006-08-24 12:32:52Z rmanfredi $
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: $Log: kernel.U,v $
?RCS: Revision 3.0 1993/08/18 12:08:54 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:kernel: Getfile test
?MAKE: -pick add $@ %<
?S:kernel:
```

?S: This variable becomes the (fully rooted) path name of the kernel.

?S:.

: find the name of the kernel.

```
echo " "
```

```
case "$kernel" in
```

```
")
```

```
if $test -r /unix; then
```

```
  dflt=/unix
```

```
elif $test -r /vmunix; then
```

```
  dflt=/vmunix
```

```
elif $test -r /xenix; then
```

```
  dflt=/xenix
```

```
elif $test -r /mach; then
```

```
  dflt=/mach
```

```
elif
```

```
$test -r /dgux; then
```

```
  dflt=/dgux
```

```
elif $test -r /hp-ux; then
```

```
  dflt=/hp-ux
```

```
elif $test -r /syst; then
```

```
  dflt=/syst
```

```
elif $test -r /arix; then
```

```
  dflt=/arix
```

```
elif $test -r /irix; then
```

```
  dflt=/arix
```

```
else
```

```
  dflt='unknown'
```

```
  set X /*x
```

```
  shift
```

```
  case $# in
```

```
  1)
```

```
    if $test -r "$1"; then
```

```
      dflt="$1"
```

```
    fi
```

```
    ;;
```

```
  esac
```

```
fi
```

```
;;
```

```
*)
```

```
  dflt="$kernel"
```

```
;;
```

```
esac
```

```
fn=f
```

```
rp='What is the name of your kernel?'
```

```
./getfile
```

```
kernel="$ans"
```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-  
debian-perl-5.26.1/dist/U/kernel.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id$
```

```
?RCS:
```

```
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
```

```
?RCS:
```

```
?RCS: You may redistribute only under the terms of the Artistic License,
```

```
?RCS: as specified in the README file that comes with the distribution.
```

```
?RCS: You may reuse parts of this distribution only within the terms of
```

```
?RCS: that same Artistic License; a copy of which may be found at the root
```

```
?RCS: of the source tree for dist 4.0.
```

```
?RCS:
```

```
?RCS: $Log: sysman.U,v $
```

```
?RCS: Revision 3.0.1.2 1994/06/20 07:08:43 ram
```

```
?RCS: patch30: now explicitly states that /usr/man/man1 is the default
```

```
?RCS: patch30: added /usr/local/man/man1 to the search list
```

```
?RCS:
```

```
?RCS: Revision 3.0.1.1 1993/09/13 16:13:50 ram
```

```
?RCS: patch10: added support for /local/man/man1 (WAD)
```

```
?RCS: patch10: added temporary syspath variable to cut down on line length
```

```
?RCS:
```

```
?RCS: Revision 3.0 1993/08/18 12:09:55 ram
```

```
?RCS: Baseline for dist 3.0 netwide release.
```

```
?RCS:
```

```
?MAKE:sysman: test
```

```
Loc Oldconfig
```

```
?MAKE: -pick add $@ %<
```

```
?S:sysman:
```

```
?S: This variable holds the place where the manual is located on this
```

```
?S: system. It is not the place where the user wants to put his manual
```

```
?S: pages. Rather it is the place where Configure may look to find manual
```

```
?S: for unix commands (section 1 of the manual usually). See mansrc.
```

```
?S:.
```

```
?T:syspath
```

```
: determine where manual pages are on this system
```

```
echo " "
```

```
case "$sysman" in
```

```
"
```

```
syspath="/usr/share/man/man1 /usr/man/man1"
```

```
syspath="$syspath /usr/man/mann /usr/man/man1 /usr/man/local/man1"
```

```
syspath="$syspath /usr/man/u_man/man1 /usr/share/man/man1"
```

```
syspath="$syspath /usr/catman/u_man/man1 /usr/man/l_man/man1"
```

```
syspath="$syspath /usr/local/man/u_man/man1 /usr/local/man/l_man/man1"
```

```
syspath="$syspath /usr/man/man.L /local/man/man1 /usr/local/man/man1"
```

```
sysman="/loc . /usr/man/man1 $syspath`
```

```
::
```

```
esac
if $test -d "$sysman"; then
  echo "System manual is in $sysman." >&4
else
  echo "Could not find manual pages in source form." >&4
fi
```

Found

in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/sysman.U
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_linuxstd.U 1 2006-08-24 12:32:52Z rmanfredi \$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic Licence,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic Licence; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: Original Author: Andy Dougherty <doughera@lafcol.lafayette.edu>

?RCS:

?RCS: \$Log: d_linuxstd.U,v \$

?RCS: Revision 3.0.1.1 1994/10/29 16:14:05 ram

?RCS: patch36: created by ADO

?RCS:

?MAKE:d_linuxstd: d_stdstdio cppstdin cppflags cppminus \

contains rm Setvar Findhdr

?MAKE: -pick add \$@ %<

?S:d_linuxstd:

?S: This variable conditionally defines USE_LINUX_STDIO if this system

?S: has a FILE structure declaring _IO_read_base, _IO_read_ptr,

?S: and _IO_read_end

in stdio.h.

?S:.

?C:USE_LINUX_STDIO:

?C: This symbol is defined if this system has a FILE structure declaring

?C: _IO_read_base, _IO_read_ptr, and _IO_read_end in stdio.h.

?C:.

?H:#\$d_linuxstd USE_LINUX_STDIO /**/

?H:.

?T:xxx

?LINT:set d_linuxstd

: see if stdio is like that in linux

case "\$d_stdstdio" in

```

"$undef")
echo " "
xxx=`./findhdr stdio.h`
$cppstdin $cppflags $cppminus < "$xxx" > stdio.E
if $contains 'char.*_IO_read_base' stdio.E >/dev/null 2>&1 && \
  $contains '_IO_read_ptr' stdio.E >/dev/null 2>&1 && \
  $contains '_IO_read_end' stdio.E >/dev/null 2>&1 ; then
  echo "Your stdio looks like linux." >&4
  val="$define"
else
  echo "You don't have linux stdio, either." >&4
  val="$undef"
fi
$rm -f stdio.E
;;
*) val="$undef" ;;
esac

```

```

set d_linuxstd
eval $setvar

```

Found in path(s):

```

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/d_linuxstd.U

```

No license file was found, but licenses were detected in source scan.

```

?RCS: $Id: d_seteuid.U 1 2006-08-24 12:32:52Z rmanfredi $
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: $Log: d_seteuid.U,v $
?RCS: Revision 3.0 1993/08/18 12:07:08 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:d_seteuid: Inlibc
?MAKE: -pick add $@ %<
?S:d_seteuid:
?S: This variable conditionally defines the HAS_SETEUID symbol, which
?S: indicates to the C program that the seteuid() routine is available
?S: to change the effective uid of the current program.
?S:.
?C:HAS_SETEUID (SETEUID):

```

?C: This symbol, if defined, indicates that the seteuid routine is available

?C: to change the effective uid of the current program.

?C:.

?H:#\$d_seteuid HAS_SETEUID /**/

?H:.

?LINT:set d_seteuid

: see if seteuid exists

set seteuid d_seteuid

eval \$inlibc

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/d_seteuid.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_tcgetpgrp.U 1 2006-08-24 12:32:52Z rmanfredi \$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic Licence,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic Licence; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: Original Author: Andy Dougherty <doughera@lafcol.lafayette.edu>

?RCS:

?RCS: \$Log: d_tcgetpgrp.U,v \$

?RCS: Revision 3.0.1.1 1994/08/29 16:12:08 ram

?RCS: patch32: created by ADO

?RCS:

?MAKE:d_tcgetpgrp: Inlibc

?MAKE: -pick add \$@ %<

?S:d_tcgetpgrp:

?S: This variable conditionally defines the HAS_TCGETPGRP symbol, which

?S: indicates to the C program that the tcgetpgrp() routine is available.

?S: to get foreground process group ID.

?S:.

?C:HAS_TCGETPGRP

:

?C: This symbol, if defined, indicates that the tcgetpgrp routine is

?C: available to get foreground process group ID.

?C:.

?H:#\$d_tcgetpgrp HAS_TCGETPGRP /**/

?H:.

?LINT:set d_tcgetpgrp

: see if tcgetpgrp exists

```
set tcgetpgrp d_tcgetpgrp
eval $inlibc
```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/d_tcgetpgrp.U
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_sigsetjmp.U,v 3.0.1.1 1997/02/28 15:44:33 ram Exp \$

?RCS:

?RCS: Copyright (c) 1996,1998 Andy Dougherty

?RCS: Copyright (c) 1991-1993, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 3.0.

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?RCS: \$Log: d_sigsetjmp.U,v \$

?RCS: Revision 3.0.1.1 1997/02/28 15:44:33 ram

?RCS: patch61: created

?RCS:

?MAKE:d_sigsetjmp: Compile Setvar cat rm_try run i_stdlib

?MAKE: -pick add \$@ %<

?S:d_sigsetjmp:

?S: This variable conditionally defines the HAS_SIGSETJMP symbol,

?S: which

indicates that the sigsetjmp() routine is available to

?S: call setjmp() and optionally save the process's signal mask.

?S:.

?C:HAS_SIGSETJMP:

?C: This variable indicates to the C program that the sigsetjmp()

?C: routine is available to save the calling process's registers

?C: and stack environment for later use by siglongjmp(), and

?C: to optionally save the process's signal mask. See

?C: Sigjmp_buf, Sigsetjmp, and Siglongjmp.

?C:.

?C:Sigjmp_buf:

?C: This is the buffer type to be used with Sigsetjmp and Siglongjmp.

?C:.

?C:Sigsetjmp:

?C: This macro is used in the same way as sigsetjmp(), but will invoke

?C: traditional setjmp() if sigsetjmp isn't available.

?C: See HAS_SIGSETJMP.

```

?C:.
?C:Siglongjmp:
?C: This macro is used in the same way as siglongjmp(), but will invoke
?C: traditional longjmp() if siglongjmp isn't available.
?C: See HAS_SIGSETJMP.
?C:.
?H:%<:#$d_sigsetjmp HAS_SIGSETJMP /**/
?H:%<:#ifdef HAS_SIGSETJMP
?H:%<:#define Sigjmp_buf sigjmp_buf
?H:%<:#define Sigsetjmp(buf,save_mask)
sigsetjmp((buf),(save_mask))
?H:%<:#define Siglongjmp(buf,retval) siglongjmp((buf),(retval))
?H:%<:#else
?H:%<:#define Sigjmp_buf jmp_buf
?H:%<:#define Sigsetjmp(buf,save_mask) setjmp((buf))
?H:%<:#define Siglongjmp(buf,retval) longjmp((buf),(retval))
?H:%<:#endif
?H:.
?W:%<:Sigjmp_buf Sigsetjmp Siglongjmp
?F:!try
?LINT:set d_sigsetjmp
: see if sigsetjmp exists
?X: We can't check for these symbols with Inlibc because sigsetjmp
?X: is (sometimes? always?) a macro under GCC
echo " "
case "$d_sigsetjmp" in
")
$cat >try.c <<EOP
#include <setjmp.h>
#$i_stdlib I_STDLIB
#ifdef I_STDLIB
#include <stdlib.h>
#endif
sigjmp_buf env;
int set = 1;
int main()
{
if (sigsetjmp(env,1))
exit(set);
set = 0;
siglongjmp(env, 1);
exit(1);
}
EOP
set try
if eval $compile; then
if $run ./try >/dev/null 2>&1; then
echo "POSIX sigsetjmp found." >&4

```

```

    val="$define"
else
    $cat >&4 <<EOM
Uh-Oh! You have POSIX sigsetjmp and siglongjmp, but they do not work properly!!
I'll
ignore them.
EOM
    val="$undef"
fi
else
    echo "sigsetjmp not found." >&4
    val="$undef"
fi
;;
*) val="$d_sigsetjmp"
case "$d_sigsetjmp" in
$define) echo "POSIX sigsetjmp found." >&4;;
$undef) echo "sigsetjmp not found." >&4;;
esac
;;
esac
set d_sigsetjmp
eval $setvar
$rm_try

```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/compline/d_sigsetjmp.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: archname.U,v 3.0.1.3 1997/02/28 15:24:32 ram Exp $
?RCS:
?RCS: Copyright (c) 1991-1993, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 3.0.
?RCS:
?RCS: $Log: archname.U,v $
?RCS: Revision 3.0.1.3 1997/02/28 15:24:32 ram
?RCS: patch61: changed the way the archname is mangled from unname
?RCS:
?RCS: Revision 3.0.1.2 1995/05/12 12:05:24 ram
?RCS: patch54: protect against spaces in "uname -m" output (ADO)
?RCS:
?RCS: Revision 3.0.1.1 1995/02/15 14:14:21 ram
```

```

?RCS: patch51: created
?RCS:
?MAKE:archname myarchname useversionedarchname: sed Loc Myread Oldconfig \
osname test rm usethreads usemultiplicity use64bitint
use64bitall \
archname64 uselongdouble longdblsize doublesize targetarch Setvar \
api_versionstring usequadmath
?MAKE: -pick add $@ %<
?S:archname:
?S: This variable is a short name to characterize the current
?S: architecture. It is used mainly to construct the default archlib.
?S:.
?S:myarchname:
?S: This variable holds the architecture name computed by Configure in
?S: a previous run. It is not intended to be perused by any user and
?S: should never be set in a hint file.
?S:.
?S:useversionedarchname:
?S: This variable indicates whether to include the $api_versionstring
?S: as a component of the $archname.
?S:.
?C:ARCHNAME:
?C: This symbol holds a string representing the architecture name.
?C: It may be used to construct an architecture-dependant pathname
?C: where library files may be held under a private library, for
?C: instance.
?C:.
?H:#define ARCHNAME "$archname" /**/
?H:.
?T:xxx tarch
?F:!archname.cbu
?INIT:archname=""
: determine the architecture name
echo " "
?X:
We always recompute archname in case osname changes. However, we need
?X: to be careful since, as ADO rightfully pointed out, some systems pick
?X: silly architecture names (0001307135000-aix on AIX or 9000/715-ux under
?X: HP-UX). Therefore, we allow hint files to supersede our guess and ask
?X: the user for confirmation.
if xxx=`./loc arch blurfl $pth`; $test -f "$xxx"; then
tarch=`arch`-"-$osname"
elif xxx=`./loc uname blurfl $pth`; $test -f "$xxx" ; then
if uname -m > tmparch 2>&1 ; then
tarch=`$sed -e 's/ *$//' -e 's/ /_/' \
-e 's/"/'"-$osname/'" tmparch`
else
tarch="$osname"

```

```

fi
$rm -f tmparch
else
  tarch="$osname"
fi
case "$myarchname" in
|"|$tarch") ;;
*)
  echo "(Your architecture name used to be $myarchname.)"
  archname=""
  ;;
esac
case "$targetarch" in
") ;;
?X: Very GCCian.
*) archname=`echo $targetarch|sed 's,^[^]*-,` ;;
esac
myarchname="$tarch"
case "$sarchname" in
") dflt="$tarch";;
*) dflt="$sarchname";;
esac
rp='What is your architecture name'
./myread
archname="$ans"

:
  optionally add API version to the architecture for versioned archlibs
case "$useversionedarchname" in
$define|true|[yY]*) dflt='y';;
*)          dflt='n';;
esac
rp='Add the Perl API version to your archname?'
./myread
case "$ans" in
y|Y) useversionedarchname="$define" ;;
*)   useversionedarchname="$undef" ;;
esac
case "$useversionedarchname" in
$define)
case "$sarchname" in
*-$sapi_versionstring)
  echo "...and architecture name already has -$sapi_versionstring" >&4
  ;;
*)
  archname="$sarchname-$sapi_versionstring"
  echo "...setting architecture name to $sarchname." >&4
  ;;

```

```

esac
;;
esac

@if usethreads
case "$usethreads" in
$define)
echo "Threads selected." >&4
case "$archname" in
*-thread*) echo "...and architecture name already has -thread." >&4
;;
*) archname="$archname-thread"
echo "...setting architecture name to $archname." >&4
;;
esac
;;
esac
;;
esac
@end
@if usemultiplicity
case "$usemultiplicity" in
$define)
echo "Multiplicity selected."
>&4
case "$archname" in
*-multi*) echo "...and architecture name already has -multi." >&4
;;
*) archname="$archname-multi"
echo "...setting architecture name to $archname." >&4
;;
esac
;;
esac
@end
@if use64bitint
case "$use64bitint$use64bitall" in
*" $define"*)
case "$archname64" in
")
echo "This architecture is naturally 64-bit, not changing architecture name." >&4
;;
*)
case "$use64bitint" in
"$define") echo "64 bit integers selected." >&4 ;;
esac
case "$use64bitall" in
"$define") echo "Maximal 64 bitness selected." >&4 ;;
esac
case "$archname" in

```

```

*-$sarchname64*) echo "...and architecture name already has $sarchname64." >&4
;;
*)   archname="$sarchname-$sarchname64"
     echo "...setting architecture name to $sarchname." >&4
;;
esac
;;
esac
esac
@end
@if uselongdouble
case "$uselongdouble" in
$define)
echo "Long doubles selected." >&4
case "$longdblsize" in
$doublesize)
echo "...but long doubles are equal to doubles, not
changing architecture name." >&4
;;
*)
case "$sarchname" in
*-ld*) echo "...and architecture name already has -ld." >&4
;;
*)   archname="$sarchname-ld"
     echo "...setting architecture name to $sarchname." >&4
;;
esac
;;
esac
;;
esac
@end
@if usequadmath
case "$usequadmath" in
$define)
echo "quadmath selected." >&4
case "$sarchname" in
*-quadmath*) echo "...and architecture name already has -quadmath." >&4
;;
*)   archname="$sarchname-quadmath"
     echo "...setting architecture name to $sarchname." >&4
;;
esac
;;
esac
@end
if $test -f archname.cbu; then
echo "Your platform has some specific hints for architecture name, using them..."

```

./archname.cbu

fi

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/threads/archname.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_ffs.U 1 2006-08-24 12:32:52Z rmanfredi \$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic Licence,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic Licence; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: d_ffs.U,v \$

?RCS: Revision 3.0 1993/08/18 12:06:03 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?MAKE:d_ffs: Inlibc

?MAKE: -pick add \$@ %<

?S:d_ffs:

?S: This variable conditionally defines the HAS_FFS symbol, which

?S: indicates to the C program that the ffs() routine is available

?S: to find the first bit which is set in its integer argument.

?S:.

?C:HAS_FFS:

?C: This symbol, if defined, indicates that the ffs routine is available

?C: to

find the first bit set in its argument. If it's not available,

?C: roll your own.

?C:.

?H:#\$d_ffs HAS_FFS /**/

?H:.

?LINT:set d_ffs

: see if ffs exists

set ffs d_ffs

eval \$inlibc

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/d_ffs.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

```

?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: $Log: Oldsym.U,v $
?RCS: Revision 3.0.1.1 1997/02/28 15:06:58 ram
?RCS: patch61: added support for src.U
?RCS:
?RCS: Revision 3.0 1993/08/18 12:05:13 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?X:
?X: This unit follows the creation of the config.sh file. It adds some
?X: special symbols: defines from patchlevel.h file if any and CONFIG,
?X: which is set to true. Then, we try to keep all the new symbols that
?X: may come from a hint file or a previous config.sh file.
?X:
?MAKE:Oldsym:
Config_sh Options test hint src sed sort uniq
?MAKE: -pick add $@ %<
?T:CONFIG sym tmp
?F:!UU
: add special variables
$test -f $src/patchlevel.h && \
awk '/^#define/ {printf "%s=%s\n", $2, $3}' $src/patchlevel.h >>config.sh
echo "CONFIG=true" >>config.sh

: propagate old symbols
if $test -f UU/config.sh; then
?X: Make sure each symbol is unique in oldconfig.sh
<UU/config.sh $sort | $uniq >UU/oldconfig.sh
?X:
?X: All the symbols that appear twice come only from config.sh (hence the
?X: two config.sh in the command line). These symbols will be removed by
?X: the uniq -u command. The oldsyms file thus contains all the symbols
?X: that did not appear in the produced config.sh (Larry Wall).
?X:
?X: Do not touch the -u flag of uniq. This means you too, Jarkko.
?X:
$sed -n 's/^\([a-zA-Z_0-9]*\)=.*/\1/p' \
config.sh config.sh UU/oldconfig.sh |
$sort | $uniq -u >UU/oldsyms
set X `cat UU/oldsyms`

```

```

shift
case $# in
0) ;;
*)
cat <<EOM
Hmm... You had some extra variables I don't know about...I'll
try to keep 'em...
EOM
echo ": Variables propagated from previous config.sh file." >>config.sh
for sym in `cat UU/oldsyms`; do
echo " Propagating $hint variable ""$""$sym..."
eval `tmp=""${sym}""`
echo "$tmp" | \
sed -e "s/^\\""/g" -e "s/^\$sym=/'" -e "s/\/'" >>config.sh
done
;;
esac
fi

```

Found in path(s):

```

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/Oldsym.U

```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: Original Author: Andy Dougherty <doughera@lafcol.lafayette.edu>

?RCS:

?RCS: \$Log: prefix.U,v \$

?RCS: Revision 3.0.1.2 1995/01/30 14:44:05 ram

?RCS: patch49: new prefixexp variable holding a fully expanded prefix

?RCS: patch49: save off previous prefix value in oldprefix if changed (WED)

?RCS: patch49: added the INSTALLPREFIX define for C programs to use (WED)

?RCS:

?RCS: Revision 3.0.1.1 1994/08/29 16:31:34 ram

?RCS: patch32: created by ADO

?RCS:

?MAKE:prefix prefixexp +oldprefix: Getfile Loc Oldconfig

cat package

?MAKE: -pick add \$@ %<

?S:prefix:

?S: This variable holds the name of the directory below which the
?S: user will install the package. Usually, this is /usr/local, and
?S: executables go in /usr/local/bin, library stuff in /usr/local/lib,
?S: man pages in /usr/local/man, etc. It is only used to set defaults
?S: for things in bin.U, mansrc.U, privlib.U, or scriptdir.U.

?S:.

?S:prefixexp:

?S: This variable holds the full absolute path of the directory below
?S: which the user will install the package. Derived from prefix.

?S:.

?S:oldprefix:

?S: This variable is set non-null if the prefix was previously defined
?S: and gets set to a new value. Used internally by Configure only.

?S:.

?C:INSTALLPREFIX:

?C: This symbol contains the name of the install prefix for this package.

?C:.

```
?H:#define INSTALLPREFIX "$prefix" /**/
```

?H:.

: determine root of directory hierarchy where package will be installed.

```
case "$prefix" in
```

```
)
```

```
  dflt=`./loc . /usr/local /usr/local /local /opt
```

```
  /usr`
```

```
  ;;
```

```
*)
```

```
  dflt="$prefix"
```

```
  ;;
```

```
esac
```

```
$cat <<EOM
```

By default, \$package will be installed in \$dflt/bin, manual
pages under \$dflt/man, etc..., i.e. with \$dflt as prefix for
all installation directories. Typically set to /usr/local, but you
may choose /usr if you wish to install \$package among your system
binaries. If you wish to have binaries under /bin but manual pages
under /usr/local/man, that's ok: you will be prompted separately
for each of the installation directories, the prefix being only used
to set the defaults.

EOM

```
fn=d~
```

```
rp='Installation prefix to use?'
```

```
./getfile
```

```
oldprefix=""
```

```
case "$prefix" in
```

```
) ;;
```

```

*)
case "$ans" in
"$prefix") ;;
*) oldprefix="$prefix";;
esac
;;
esac
prefix="$ans"
prefixexp="$ansexp"

```

Found in path(s):

```

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/prefix.U

```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: lseektype.U,v \$

?RCS: Revision 3.0.1.1 1994/08/29 16:30:10 ram

?RCS: patch32: now uses new Typedef unit to compute type information

?RCS:

?RCS: Revision 3.0 1993/08/18 12:09:08 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?MAKE:lseektype: Myread Typedef

?MAKE: -pick add \$@ %<

?S:lseektype:

?S: This variable defines lseektype to be something like off_t, long,

?S: or whatever type is used to declare lseek offset's type in the

?S: kernel (which also appears to be lseek's return type).

?S:.

?C:Off_t

(LSEEKTYPE):

?C: This symbol holds the type used to declare offsets in the kernel.

?C: It can be int, long, off_t, etc... It may be necessary to include

?C: <sys/types.h> to get any typedef'ed information.

?C:.

?H:#define Off_t \$lseektype /* <offset> type */

?H:.

: see what type lseek is declared as in the kernel

```
set off_t lseektype long stdio.h sys/types.h
eval $stypedef
echo " "
dflt="$lseektype"
rp="What type is lseek's offset on this system declared as?"
./myread
lseektype="$ans"
```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/lseektype.U
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: Whoa.U,v \$

?RCS: Revision 3.0.1.2 1997/02/28 15:21:21 ram

?RCS: patch61: whoa script now starts with leading "startsh"

?RCS:

?RCS: Revision 3.0.1.1 1994/10/29 16:02:01 ram

?RCS: patch36: added ?F: line for metalint file checking

?RCS:

?RCS: Revision 3.0 1993/08/18 12:05:19 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?X:

?X: This unit produces a bit of shell code that must be dotted in in order

?X: to warn the user in case a change into a variable is noticed.

?X:

?X: To use this

unit, \$was must hold the old value that has changed. Upon

?X: exit, the two variables \$td and \$tu are set to the correct value for

?X: respectively defining or undefining a variable. For instance, if \$was was

?X: \$undef, but now \$var is \$define, after calling . whoa, you should use

?X: eval "\$var=\\$tu" to finally set \$var to the correct value. See unit Inlibc.

?X:

?MAKE:Whoa: Myread startsh hint

?MAKE: -pick add \$@ %<

?F:./whoa

?T:var was

```

?LINT:change td tu
: set up the script used to warn in case of inconsistency
cat <<EOS >whoa
$startsh
EOS
cat <<'EOSC' >>whoa
dflt=y
echo " "
echo "*** WHOA THERE!!! ***" >&4
echo " The $hint value for \$$var on this machine was \"$was\!" >&4
rp=" Keep the $hint value?"
./myread
case "$ans" in
y) td=$was; tu=$was;;
esac
EOSC

```

Found in path(s):

```

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/Whoa.U

```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 2015 Jarkko Hietaniemi, H.Merijn Brand

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?MAKE:longdblifbytes longdblmanbytes doubleifbytes doublenanbytes: Inlibc \

cat i_math i_string Compile run rm_try Setvar echo d_longdbl \

doublekind doublesize longdblkind longdblsize

?MAKE: -pick add \$@ %<

?S:longdblifbytes:

?S: This variable contains comma-separated list of hexadecimal bytes

?S: for the long double precision infinity.

?S:.

?S:longdblmanbytes:

?S: This variable contains comma-separated list of hexadecimal bytes

?S: for the long double precision not-a-number.

?S:.

?S:doubleifbytes:

?S: This variable contains comma-separated list of hexadecimal bytes

?S: for the double precision infinity.

?S:.

?S:doublenanbytes:

?S: This variable contains comma-separated list of hexadecimal

```

bytes
?S: for the double precision not-a-number.
?S:.
?C:DOUBLEINFBYTES:
?C: This symbol, if defined, is a comma-separated list of
?C: hexadecimal bytes for the double precision infinity.
?C:.
?C:DOUBLENANBYTES:
?C: This symbol, if defined, is a comma-separated list of
?C: hexadecimal bytes (0xHH) for the double precision not-a-number.
?C:.
?C:LONGDBLINFBYTES:
?C: This symbol, if defined, is a comma-separated list of
?C: hexadecimal bytes for the long double precision infinity.
?C:.
?C:LONGDBLNANBYTES:
?C: This symbol, if defined, is a comma-separated list of
?C: hexadecimal bytes (0xHH) for the long double precision not-a-number.
?C:.
?H:#define DOUBLEINFBYTES $doubleinfbytes /**/
?H:#define DOUBLENANBYTES $doublenanbytes /**/
?H:#define LONGDBLINFBYTES $longdblinfbytes /**/
?H:#define LONGDBLNANBYTES $longdbl nanbytes /**/
?H:.
?F:!try
: Check what kind of inf/nan your system has
$echo "Checking the kind of infinities and nans you have..." >&4
$echo "(The following tests
may crash. That's okay.)" >&4
$cat >try.c <<EOP
#define DOUBLESIZE $doublesize
#$d_longdbl HAS_LONG_DOUBLE
#ifdef HAS_LONG_DOUBLE
#define LONG_DOUBLESIZE $longdblsize
#define LONG_DOUBLEKIND $longdblkind
#endif
#$i_math I_MATH
#$i_string I_STRING
#ifdef I_MATH
#include <math.h>
#endif
#ifdef I_STRING
# include <string.h>
#endif
#include <stdio.h>
/* Note that whether the sign bit is on or off
* for NaN depends on the CPU/FPU, and possibly
* can be affected by the build toolchain.

```

*
 * For example for older MIPS and HP-PA 2.0 the quiet NaN is:
 * 0x7f, 0xf7, 0xff, 0xff, 0xff, 0xff, 0xff, 0xff
 * 0x7f, 0xf4, 0x00, 0x00, 0x00, 0x00, 0x00, 0x00
 * (respectively) as opposed to the more usual
 * 0x7f, 0xf8, 0x00, 0x00, 0x00, 0x00, 0x00, 0x00
 *
 * Pre-IEEE-754 floating point format do not even have inf/nan support
 * at all. They might have a "max" value (DBL_MAX), which may be deadly
 * to even mention, causing immediate SIGFPE or equivalent: this is
 * the case with VAX floating point,
 for example.
 */

```
static void bytes(void *v, unsigned int n) {
    unsigned char *p = (unsigned char *)v;
    int i;
    for (i = 0; i < n; i++) {
        printf("0x%02x%s", p[i], i < n - 1 ? ", " : "\n");
    }
}

int main(int argc, char *argv[]) {
    /* We cannot use 1.0/0.0 and 0.0/0.0 (with L suffixes for long double)
     * because some compilers are 'smart' and not only warn but refuse to
     * compile such 'illegal' values. */
    double dinf = exp(1e9);
    double dnan = sqrt(-1.0);
#ifdef HAS_LONG_DOUBLE
    long double ldinf = (long double)exp(1e9);
    long double ldnan = (long double)sqrt(-1.0);
# if LONG_DOUBLEKIND == 3 || LONG_DOUBLEKIND == 4
/* the 80-bit long doubles might have garbage in their excess bytes */
    memset((char *)&ldinf + 10, '\0', LONG_DOUBLESIZE - 10);
    memset((char *)&ldnan + 10, '\0', LONG_DOUBLESIZE - 10);
#endif
    if (argc == 2) {
        switch (argv[1][0]) {
            case '1': bytes(&dinf, sizeof(dinf)); break;
            case '2': bytes(&dnan, sizeof(dnan)); break;

            case '3': bytes(&ldinf, sizeof(ldinf)); break;
            case '4': bytes(&ldnan, sizeof(ldnan)); break;
        }
    }
    return 0;
}
EOP
set try
```

```

if eval $compile; then
  doubleinfbytes=`$run ./try 1`
  doublenanbytes=`$run ./try 2`
  case "$d_longdbl" in
  $define)
    longdblifbytes=`$run ./try 3`
    longdbl nanbytes=`$run ./try 4`
    ;;
  esac
else
  # Defaults in case the above test program failed.
  case "$doublekind" in
  1) # IEEE 754 32-bit LE
    doubleinfbytes='0x00, 0x00, 0xf0, 0x7f'
    doublenanbytes='0x00, 0x00, 0xf8, 0x7f'
    ;;
  2) # IEEE 754 32-bit BE
    doubleinfbytes='0x7f, 0xf0, 0x00, 0x00'
    doublenanbytes='0x7f, 0xf8, 0x00, 0x00'
    ;;
  3) # IEEE 754 64-bit LE
    doubleinfbytes='0x00, 0x00, 0x00, 0x00, 0x00, 0x00, 0xf0, 0x7f'
    doublenanbytes='0x00, 0x00, 0x00, 0x00, 0x00, 0x00, 0xf8, 0x7f'
    ;;
  4) # IEEE 754 64-bit BE
    doubleinfbytes='0x7f, 0xf0, 0x00, 0x00, 0x00, 0x00, 0x00, 0x00'
    doublenanbytes='0x7f,
0xf8, 0x00, 0x00, 0x00, 0x00, 0x00, 0x00'
    ;;
  5) # IEEE 754 128-bit LE
    doubleinfbytes='0x00, 0x00, 0xf0,
0x7f'
    doublenanbytes='0x00, 0x00, 0xf8,
0x7f'
    ;;
  6) # IEEE 754 128-bit BE
    doubleinfbytes='0x7f, 0xf0, 0x00, 0x00,
0x00'
    doublenanbytes='0x7f, 0xf8, 0x00, 0x00,
0x00'
    ;;
  7) # IEEE 754 64-bit mixed: 32-bit LEs in BE
    doubleinfbytes='0x00, 0x00, 0xf0, 0x7f, 0x00, 0x00, 0x00, 0x00'
    doublenanbytes='0x00, 0x00, 0xf8, 0x7f, 0x00, 0x00, 0x00, 0x00'
    ;;
  8) # IEEE 754 64-bit mixed: 32-bit BEs in LE
    doubleinfbytes='0x00, 0x00, 0x00, 0x00, 0x7f, 0xf0, 0x00, 0x00'
    doublenanbytes='0x00, 0x00, 0x00, 0x00, 0x7f, 0xf8,

```



```

case "$doubleinbytes" in
") doubleinbytes=$undef ;;
esac
case "$doublenanbytes" in
") doublenanbytes=$undef ;;
esac
case "$longdblinbytes" in
") longdblinbytes=$undef ;;
esac
case "$longdblmanbytes"
in
") longdblmanbytes=$undef ;;
esac
$rm_try

```

Found in path(s):

```

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/perl/infnan.U

```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: dlsrc.U,v\$

?RCS:

?RCS: Copyright (c) 1996-1998, Andy Dougherty

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?RCS: \$Log: dlsrc.U,v \$

?RCS:

?X: hpux support thanks to Jeff Okamoto <okamoto@hpcc101.corp.hp.com>

?X:

?X: To create a shared library, you must compile ALL source files in the

?X: library with +z (or possibly +Z if the library is whopping huge),

?X: then link the library with -b. Example:

?X: cc -c +z module_a.c

?X: cc -c +z module_b.c

?X: ld -b module_a.o module_b.o -o module.sl

?X:

?MAKE:usedl ld dlsrc ccdlflags lddlflags ccdlflags bin_ELF ld_can_script: \

rm_try Getfile Myread test osname sed d_dlopen Findhdr Setvar \

src run cc ccflags ldflags optimize ls gccversion cat rsrc i_stdlib \

i_unistd osvers sysroot

?MAKE: -pick add \$@ %<

?Y:BOTTOM

?S:usedl:

?S: This variable

indicates if the system supports dynamic

?S: loading of some sort. See also dlsrc and dlobj.

?S:.

?S:ld:

?S: This variable indicates the program to be used to link
 ?S: libraries for dynamic loading. On some systems, it is 'ld'.
 ?S: On ELF systems, it should be \$cc. Mostly, we'll try to respect
 ?S: the hint file setting.

?S:.

?S:dlsrc:

?S: This variable contains the name of the dynamic loading file that
 ?S: will be used with the package.

?S:.

?S:cccdlflags:

?S: This variable contains any special flags that might need to be
 ?S: passed with 'cc -c' to compile modules to be used to create a shared
 ?S: library that will be used for dynamic loading. For hpux, this
 ?S: should be +z. It is up to the makefile to use it.

?S:.

?S:lddlflags:

?S: This variable contains any special flags that might need to be
 ?S: passed to \$ld to create a shared library suitable for dynamic
 ?S: loading. It is up to the makefile to use it. For hpux, it
 ?S: should be '-b'. For sunos 4.1, it is empty.

?S:.

?S:ccdlflags:

?S: This
 variable contains any special flags that might need to be
 ?S: passed to cc to link with a shared library for dynamic loading.
 ?S: It is up to the makefile to use it. For sunos 4.1, it should
 ?S: be empty.

?S:.

?S:bin_ELF:

?S: This variable saves the result from configure if generated binaries
 ?S: are in ELF format. Only set to defined when the test has actually
 ?S: been performed, and the result was positive.

?S:.

?S:ld_can_script:

?S: This variable shows if the loader accepts scripts in the form of
 ?S: -Wl,--version-script=ld.script. This is currently only supported
 ?S: for GNU ld on ELF in dynamic loading builds.

?S:.

?C:USE_DYNAMIC_LOADING ~ %<:

?C: This symbol, if defined, indicates that dynamic loading of
 ?C: some sort is available.

?C:.

?H:?%<:#\$usedl USE_DYNAMIC_LOADING /**/
 ?H:.

?W:%<:dlopen

?T:dldir thisflag tdir

```

?F:!a.out
: determine which dynamic loading, if any, to compile in
echo " "
dldir="ext/DynaLoader"
case "$usedl" in
  $define|y|true)
    dflt='y'
    usedl="$define"
  ;;
  $undef|n|false)
    dflt='n'
    usedl="$undef"
  ;;
  *)
    dflt='n'
case "$d_dlopen" in
  $define) dflt='y' ;;
esac
: Does a dl_xxx.xs file exist for this operating system
$test -f $src/$dldir/dl_${osname}.xs && dflt='y'
;;
esac
rp="Do you wish to use dynamic loading?"
./myread
usedl="$ans"
bin_ELF="$undef"
case "$ans" in
  y*) usedl="$define"
case "$dsrc" in
  ") if $test -f $src/$dldir/dl_${osname}.xs ; then
    dflt="$dldir/dl_${osname}.xs"
  elif $test "$d_dlopen" = "$define" ; then
    dflt="$dldir/dl_dlopen.xs"
  else
    dflt="
  fi
  ;;
  *) dflt="$dldir/$dsrc"
  ;;
esac
echo "The following dynamic loading files are available:"
: Can not go over to $dldir because getfile has path hard-coded in.
tdir=`pwd`; cd "$src"; $ls -C $dldir/dl*.xs; cd "$tdir"
rp="Source file to use for dynamic loading"
fn="fne"
gfpth="$src"
./getfile
usedl="$define"

```

```
: emulate basename
dlsrc=`echo $ans | $sed -e 's%.*\([^/]*\)%\1%`
```

```
$cat
<< EOM
```

Some systems may require passing special flags to \$cc -c to compile modules that will be used to create a shared library. To use no flags, say "none".

EOM

```
case "$cccdlflags" in
  *) case "$gccversion" in
    *) case "$osname" in
      hpux) dflt='+z' ;;
      irix*) dflt='-KPIC' ;;
      svr4*|esix*|solaris|nonstopux) dflt='-KPIC' ;;
      sunos) dflt='-pic' ;;
      *) dflt='none' ;;
    esac
    ;;
  *) case "$osname" in
      darwin) dflt='none' ;;
      *linux*|svr4*|esix*|solaris|nonstopux) dflt='-fPIC' ;;
      *) dflt='-fpic' ;;
    esac ;;
  esac ;;
  ' ') dflt='none' ;;
  *) dflt="$cccdlflags" ;;
esac
```

```
case "$dflt" in
  none) dflt="" ;;
esac
```

If -Dsysroot was specified, now's the time to add it

to cccdflags

```
if test "X$sysroot" != X; then
```

```
  case "$gccversion" in
  *) ;;
  *) case "$dflt" in
    *sysroot*) ;;
    'undef'|*)
      dflt="$dflt --sysroot=$sysroot" ;;
    esac
    ;;
  esac
```

```
fi
```

```

case "$dflt" in
  *) dflt='none';;
esac

```

```

rp="Any
special flags to pass to $cc -c to compile shared library modules?"
. ./myread
case "$ans" in
?X: Use ' ' so that a subsequent Configure run preserves the old state.
  none) cccdlflags=' ' ;;
  *) cccdlflags="$ans" ;;
esac

```

```

cat << EOM

```

Some systems use ld to create libraries that can be dynamically loaded, while other systems (such as those using ELF) use \$cc.

EOM

```

: Determine if this is ELF
$cat >try.c <<EOM
/* Test for whether ELF binaries are produced */
#include <fcntl.h>
#ifdef I_STDLIB
#include <stdlib.h>
#endif
#ifdef I_UNISTD
#include <unistd.h>
#endif
int main() {
  char b[4];
  int i = open("a.out",O_RDONLY);
  if(i == -1)
    exit(1); /* fail */
  if(read(i,b,4)==4 && b[0]==127 && b[1]=='E' && b[2]=='L' && b[3]=='F')
    exit(0); /* succeed (yes, it is ELF) */
  exit(1); /* fail */
}
EOM
if $cc $ccflags $ldflags -o a.out try.c >/dev/null 2>&1 && $run ./a.out; then
  bin_ELF="$define"
fi
$rm_try

```

```

case "$ld" in

    ") if $test $bin_ELF = "$define"; then
        cat <<EOM
You appear to have ELF support. I'll use $cc to build dynamic libraries.
EOM
        dflt="$cc"
    else
        echo "I'll use ld to build dynamic libraries."
        dflt='ld'
    fi
;;
*) dflt="$ld"
;;
esac

```

```

rp="What command should be used to create dynamic libraries?"
. ./myread
ld="$ans"

```

```

cat << EOM

```

Some systems may require passing special flags to `$ld` to create a library that can be dynamically loaded. If your `ld` flags include `-L/other/path` options to locate libraries outside your loader's normal search path, you may need to specify those `-L` options here as well. To use no flags, say "none".

```

EOM
case "$lddflags" in
    ") case "$osname" in
        haiku) dflt='-shared' ;;
        hpux) dflt='-b';
    case "$gccversion" in
        ") dflt="$dflt +vnocompatwarnings" ;;
    esac
;;
*linux*|irix*|gnu*) dflt="-shared $optimize" ;;
solaris) # See [perl #66604].
        # On Solaris 11, gcc -m64
on amd64
        # appears not to understand -G. gcc versions at
        # least as old as 3.4.3 support -shared, so just
        # use that with Solaris 11 and later, but keep
        # the old behavior for older Solaris versions.
        case "$gccversion" in
            ") dflt='-G' ;;
            *) case "$osvers" in

```

```

2.?)2.10) dflt='-G' ;;
*) dflt='-shared' ;;
    esac
    ;;
    esac
    ;;
    sunos) dflt='-assert nodefinitions' ;;
    svr4*|esix*|nonstopux) dflt="-G $ldflags" ;;
    *) dflt='none' ;;
esac
;;
*) dflt="$ldldflags" ;;
esac

```

: Only do this for gcc, since, for example, qcc has no concept
: of --sysroot.

```

if $test "X$sysroot" != X; then
    case "$gccversion" in
    *) ;;
    *) dflt="$dflt --sysroot $sysroot" ;;
    esac
fi

```

: Try to guess additional flags to pick up local libraries.

: Be careful not to append to a plain 'none'

```

case "$dflt" in
    none) dflt=" ;;
esac
for thisflag in $ldflags; do
    case "$thisflag" in
    -L*|-R*|-Wl,-R*)

        case " $dflt " in
        *" $thisflag "*) ;;
        *) dflt="$dflt $thisflag" ;;
        esac
        ;;
    esac
done

```

```

case "$dflt" in
    '| ') dflt='none' ;;
esac

```

```

case "$ldflags" in
    *-fstack-protector-strong*)
        case "$dflt" in
            *-fstack-protector-strong*) ;; # Don't add it again

```

```

*) dflt="$dflt -fstack-protector-strong" ;;
esac
;;
*-fstack-protector*)
case "$dflt" in
*-fstack-protector*) ;; # Don't add it again
*) dflt="$dflt -fstack-protector" ;;
esac
;;
esac

```

rp="Any special flags to pass to \$ld to create a dynamically loaded library?"

```

./myread
case "$ans" in
?X: Use ' ' so that a subsequent Configure run preserves the old state.
none) lddflags=' ' ;;
*) lddflags="$ans" ;;
esac

```

cat <<EOM

Some systems may require passing special flags to \$cc to indicate that the resulting executable will use dynamic linking. To use no flags, say "none".

EOM

```

case "$ccdlflags" in
") case "$osname" in
*linux*|hpux|gnu*)
dflt='-Wl,-E' ;;
sunos) dflt='none' ;;
*) dflt='none' ;;
esac ;;
') dflt='none' ;;
*) dflt="$ccdlflags" ;;
esac

```

rp="Any special flags to pass to \$cc to use dynamic linking?"

```

./myread
case "$ans" in
?X: Use ' ' so that a subsequent Configure run preserves the old state.
none) ccdlflags=' ' ;;
*) ccdlflags="$ans" ;;
esac

```

;;

?X: End of usedl=y section

```

*) usedl="$undef"

```

```

ld='ld'

```

```

dlsrc='dl_none.xs'
lddlflags=""
ccdlflags=""
;;
esac

ld_can_script="$undef"
case "$bin_ELF$susedl" in
  $define$define)
    # Abuse try.h and a.out names for neat cleanup
    $cat >try.c <<EOM
void foo() {}
void bar() {}
EOM
    $cat >try.h <<EOM
LIBTEST_42 {
global:
foo;
local: *;
};
EOM
    if $cc $cccdlflags $ccdlflags $ccflags \
        $ldflags $lddlflags -o a.out try.c \
        -Wl,--version-script=try.h >/dev/null 2>&1 \
        && $stest -s a.out ; then
        echo "ld supports scripting" >&4
        ld_can_script="$define"
    else

        echo "ld does not support scripting" >&4
    fi
    $rm_try
    ;;
esac

```

Found in path(s):

```

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/perl/dlsrc.U

```

No license file was found, but licenses were detected in source scan.

/*

* \$Id: dup2.C,v 3.0.1.1 1994/01/24 13:58:37 ram Exp ram \$

*

* Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

*

* You may redistribute only under the terms of the Artistic Licence,

* as specified in the README file that comes with the distribution.

* You may reuse parts of this distribution only within the terms of

* that same Artistic Licence; a copy of which may be found at the root
* of the source tree for dist 4.0.
*
* Original Author: Larry Wall <lwall@netlabs.com>
*
* \$Log: dup2.C,v \$
* Revision 3.0.1.1 1994/01/24 13:58:37 ram
* patch16: created
*
*/

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/lib/C/fake/dup2.C

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_getpwent_r.U,v ORCS:

?RCS: Copyright (c) 2002,2003 Jarkko Hietaniemi

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?RCS: Generated by the reentr.pl from the Perl 5.8 distribution.

?RCS:

?MAKE:d_getpwent_r getpwent_r_proto: Inlibc Protochk Hasproto i_systypes \
usethreads i_pwd extern_C

?MAKE: -pick add \$@ %<

?S:d_getpwent_r:

?S: This variable conditionally defines the HAS_GETPWENT_R symbol,

?S: which indicates to the C program that the getpwent_r()

?S: routine is available.

?S:.

?S:getpwent_r_proto:

?S: This variable encodes the prototype of getpwent_r.

?S: It is zero if d_getpwent_r is undef, and one of the

?S: REENTRANT_PROTO_T_ABC macros of reentr.h if d_getpwent_r

?S: is defined.

?S:.

?C:HAS_GETPWENT_R:

?C: This symbol, if defined, indicates that the getpwent_r routine

?C: is available to

getpwent re-entrantly.

?C:.

?C:GETPWENT_R_PROTO:

?C: This symbol encodes the prototype of getpwent_r.

?C: It is zero if d_getpwent_r is undef, and one of the

?C: REENTRANT_PROTO_T_ABC macros of reentr.h if d_getpwent_r

?C: is defined.

```

?C:.
?H:#$d_getpwent_r HAS_GETPWENT_R  /**/
?H:#define GETPWENT_R_PROTO $getpwent_r_proto  /**/
?H:.
?T:try hdrs d_getpwent_r_proto
: see if getpwent_r exists
set getpwent_r d_getpwent_r
eval $inlibc
case "$d_getpwent_r" in
"$define")
hdrs="$i_systypes sys/types.h define stdio.h $i_pwd pwd.h"
case "$d_getpwent_r_proto:$usetthreads" in
":define") d_getpwent_r_proto=define
set d_getpwent_r_proto getpwent_r $hdrs
eval $hasproto ;;
*) ;;
esac
case "$d_getpwent_r_proto" in
define)
case "$getpwent_r_proto" in
"|0) try='int getpwent_r(struct passwd*, char*, size_t, struct passwd**);'
./protochk "$extern_C $try" $hdrs && getpwent_r_proto=I_SBWR ;;
esac
case "$getpwent_r_proto" in
"|0) try='int getpwent_r(struct passwd*, char*, int, struct passwd**);'
./protochk
"$extern_C $try" $hdrs && getpwent_r_proto=I_SBIR ;;
esac
case "$getpwent_r_proto" in
"|0) try='struct passwd* getpwent_r(struct passwd*, char*, size_t);'
./protochk "$extern_C $try" $hdrs && getpwent_r_proto=S_SBW ;;
esac
case "$getpwent_r_proto" in
"|0) try='struct passwd* getpwent_r(struct passwd*, char*, int);'
./protochk "$extern_C $try" $hdrs && getpwent_r_proto=S_SBI ;;
esac
case "$getpwent_r_proto" in
"|0) try='int getpwent_r(struct passwd*, char*, int);'
./protochk "$extern_C $try" $hdrs && getpwent_r_proto=I_SBI ;;
esac
case "$getpwent_r_proto" in
"|0) try='int getpwent_r(struct passwd*, char*, int, FILE**);'
./protochk "$extern_C $try" $hdrs && getpwent_r_proto=I_SBIH ;;
esac
case "$getpwent_r_proto" in
"|0) d_getpwent_r=undef
getpwent_r_proto=0
echo "Disabling getpwent_r, cannot determine prototype." >&4 ;;

```

```

*) case "$getpwent_r_proto" in
REENTRANT_PROTO*) ;;
*) getpwent_r_proto="REENTRANT_PROTO_${getpwent_r_proto}"
;;
esac
echo "Prototype: $try" ;;
esac
;;
*) case "$usethreads" in
define) echo "getpwent_r has no prototype, not using it." >&4 ;;
esac
d_getpwent_r=undef
getpwent_r_proto=0
;;
esac
;;
*) getpwent_r_proto=0
;;
esac

```

Found in path(s):

```

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/threads/d_getpwent_r.U

```

No license file was found, but licenses were detected in source scan.

```

?RCS: $Id: d_strstr.U 1 2006-08-24 12:32:52Z rmanfredi $
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: $Log: d_strstr.U,v $
?RCS: Revision 3.0 1993/08/18 12:07:37 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:d_strstr: Inlibc
?MAKE: -pick add $@ %<
?S:d_strstr:
?S: This variable conditionally defines HAS_STRSTR if strstr() is
?S: available to find substrings.
?S:.
?C:HAS_STRSTR (STRSTR):
?C: This symbol, if defined, indicates that the strstr routine is
?C: available to find substrings.

```

?C:.
?H:#\$d_strstr HAS_STRSTR /**/
?H:.
?LINT:set d_strstr
:
see if strstr exists
set strstr d_strstr
eval \$inlibc

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/d_strstr.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$
?RCS:
?RCS: Copyright (c) 1999, Jarkko Hietaniemi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 3.0.
?RCS:
?MAKE:d_sched_setparam: Inlibc
?MAKE: -pick add \$@ %<
?S:d_sched_setparam:
?S: This variable conditionally defines HAS_SCHED_SETPARAM if
?S: sched_setparam() is available to set the scheduling parameters.
?S:.
?C:HAS_SCHED_SETPARAM:
?C: This symbol, if defined, indicates that the sched_setparam
?C: system call is available to set the scheduling parameters.
?C:.
?H:#\$d_sched_setparam HAS_SCHED_SETPARAM /**/
?H:.
?LINT:set d_sched_setparam
: see if sched_setparam exists
set sched_setparam d_sched_setparam
eval \$inlibc

Found

in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_sched_setparam.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: i_ulimit.U,v \$

?RCS:
?RCS: Copyright (c) 1998 Jarkko Hietaniemi
?RCS:
?RCS: You may distribute under the terms of either the GNU General Public
?RCS: License or the Artistic License, as specified in the README file.
?RCS:
?MAKE:i_ulimit: Inhdr Hasfield
?MAKE: -pick add \$@ %<
?S:i_ulimit:
?S: This variable conditionally defines the I_ULIMIT symbol, and indicates
?S: whether a C program should include <ulimit.h>.
?S:.
?C:I_ULIMIT:
?C: This symbol, if defined, indicates that <ulimit.h> exists and
?C: should be included.
?C:.
?H:#\$i_ulimit I_ULIMIT /**/
?H:.
?LINT:set i_ulimit
: see if this is a ulimit.h system
set ulimit.h i_ulimit
eval \$inhdr

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/i_ulimit.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_passwd.U 1 2006-08-24 12:32:52Z rmanfredi \$
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: Original Author: Andy Dougherty <doughera@lafcol.lafayette.edu>
?RCS:
?RCS: \$Log: d_passwd.U,v \$
?RCS: Revision 3.0.1.2 1997/02/28 15:37:21 ram
?RCS: patch61: useless unit dropped.
?RCS:
?RCS: Revision 3.0.1.1 1994/08/29 16:09:51 ram
?RCS: patch32: created by ADO
?RCS:
?X:

?X: Useless unit dropped.

?X:

?LINT:empty

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/d_passwd.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: i_ndbm.U,v 3.0.1.1 1995/05/12 12:16:53 ram Exp \$

?RCS:

?RCS: Copyright (c) 1991-1993, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 3.0.

?RCS:

?RCS: \$Log: i_ndbm.U,v \$

?RCS: Revision 3.0.1.1 1995/05/12 12:16:53 ram

?RCS: patch54: made more robust by checking both header and lib (ADO)

?RCS:

?RCS: Revision 3.0 1993/08/18 12:08:23 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?MAKE:i_ndbm i_gdbmndbm i_gdbm_ndbm d_ndbm d_ndbm_h_uses_prototypes \
d_gdbmndbm_h_uses_prototypes d_gdbm_ndbm_h_uses_prototypes: \
Inhdr Inlibc Setvar test d_cplusplus extern_C echo Protochk

?MAKE: -pick add \$@ %<

?MAKE: -pick add \$@ %<

?S:i_ndbm:

?S: This

variable conditionally defines the I_NDBM symbol, which

?S: indicates to the C program that <ndbm.h> exists and should

?S: be included.

?S:.

?C:I_NDBM:

?C: This symbol, if defined, indicates that <ndbm.h> exists and should

?C: be included.

?C:.

?S:i_gdbmndbm:

?S: This variable conditionally defines the I_GDBMNDBM symbol, which

?S: indicates to the C program that <gdbm/ndbm.h> exists and should

?S: be included. This was the location of the ndbm.h compatibility file

?S: in RedHat 7.1.

?S:.

?C:I_GDBMNDBM:

?C: This symbol, if defined, indicates that <gdbm/ndbm.h> exists and should

?C: be included. This was the location of the ndbm.h compatibility file

?C: in RedHat 7.1.

?C:.

?S:i_gdbm_ndbm:

?S: This variable conditionally defines the I_GDBM_NDBM symbol, which

?S: indicates to the C program that <gdbm-ndbm.h> exists and should

?S: be included. This is the location of the ndbm.h compatibility file

?S: in Debian 4.0.

?S:.

?C:I_GDBM_NDBM:

?C: This symbol, if defined, indicates

that <gdbm-ndbm.h> exists and should

?C: be included. This is the location of the ndbm.h compatibility file

?C: in Debian 4.0.

?C:.

?S:d_ndbm:

?S: This variable conditionally defines the HAS_NDBM symbol, which

?S: indicates that both the ndbm.h include file and an appropriate ndbm

?S: library exist. Consult the different i_*ndbm variables

?S: to find out the actual include location. Sometimes, a system has the

?S: header file but not the library. This variable will only be set if

?S: the system has both.

?S:.

?C:HAS_NDBM:

?C: This symbol, if defined, indicates that some form of ndbm.h or compatibility

?C: include exists, along with the appropriate library.

?C:.

?S:d_ndbm_h_uses_prototypes:

?S: This variable conditionally defines the NDBM_H_USES_PROTOTYPES symbol,

?S: which indicates that the ndbm.h include file uses real ANSI C

?S: prototypes instead of K&R style function declarations. K&R style

?S: declarations are unsupported in C++, so the include file requires

?S: special handling

when using a C++ compiler and this variable is

?S: undefined. Consult the different d_*ndbm_h_uses_prototypes variables

?S: to get the same information for alternative ndbm.h include files.

?S:.

?C:NDBM_H_USES_PROTOTYPES:

?C: This symbol, if defined, indicates that <ndbm.h> uses real ANSI C

?C: prototypes instead of K&R style function declarations without any

?C: parameter information. While ANSI C prototypes are supported in C++,

?C: K&R style function declarations will yield errors.

?C:.

?S:d_gdbmndbm_h_uses_prototypes:

?S: This variable conditionally defines the NDBM_H_USES_PROTOTYPES symbol,

?S: which indicates that the gdbm/ndbm.h include file uses real ANSI C

?S: prototypes instead of K&R style function declarations. K&R style

?S: declarations are unsupported in C++, so the include file requires

?S: special handling when using a C++ compiler and this variable is
 ?S: undefined. Consult the different d_*ndbm_h_uses_prototypes variables
 ?S: to get the same information for alternative
 ndbm.h include files.
 ?S:.
 ?C:GDBMNDBM_H_USES_PROTOTYPES:
 ?C: This symbol, if defined, indicates that <gdbm/ndbm.h> uses real ANSI C
 ?C: prototypes instead of K&R style function declarations without any
 ?C: parameter information. While ANSI C prototypes are supported in C++,
 ?C: K&R style function declarations will yield errors.
 ?C:.
 ?S:d_gdbm_ndbm_h_uses_prototypes:
 ?S: This variable conditionally defines the NDBM_H_USES_PROTOTYPES symbol,
 ?S: which indicates that the gdbm-ndbm.h include file uses real ANSI C
 ?S: prototypes instead of K&R style function declarations. K&R style
 ?S: declarations are unsupported in C++, so the include file requires
 ?S: special handling when using a C++ compiler and this variable is
 ?S: undefined. Consult the different d_*ndbm_h_uses_prototypes variables
 ?S: to get the same information for alternative ndbm.h include files.
 ?S:.
 ?C:GDBM_NDBM_H_USES_PROTOTYPES:
 ?C: This symbol, if defined, indicates that <gdbm-ndbm.h> uses real ANSI C
 ?C: prototypes
 instead of K&R style function declarations without any
 ?C: parameter information. While ANSI C prototypes are supported in C++,
 ?C: K&R style function declarations will yield errors.
 ?C:.
 ?H:#\$i_ndbm I_NDBM /**/
 ?H:#\$i_gdbmndbm I_GDBMNDBM /**/
 ?H:#\$i_gdbm_ndbm I_GDBM_NDBM /**/
 ?H:#\$d_ndbm HAS_NDBM /**/
 ?H:#\$d_ndbm_h_uses_prototypes NDBM_H_USES_PROTOTYPES /**/
 ?H:#\$d_gdbmndbm_h_uses_prototypes GDBMNDBM_H_USES_PROTOTYPES /**/
 ?H:#\$d_gdbm_ndbm_h_uses_prototypes GDBM_NDBM_H_USES_PROTOTYPES /**/
 ?H:.
 ?T:d_dbm_open name hdr ihdr ndbm_hdr_protochk
 ?LINT:set d_ndbm d_gdbmndbm_h_uses_prototypes d_gdbm_ndbm_h_uses_prototypes
 d_ndbm_h_uses_prototypes
 : see if ndbm.h is available
 set ndbm.h i_ndbm
 eval \$inhdr
 : Compatibility location for RedHat 7.1
 set gdbm/ndbm.h i_gdbmndbm
 eval \$inhdr
 : Compatibility location for Debian 4.0
 set gdbm-ndbm.h i_gdbm_ndbm
 eval \$inhdr

```

val="$undef"
if $test "$i_ndbm" = "$define" -o "$i_gdbmndbm" = "$define" -o "$i_gdbm_ndbm" = "$define"; then
: see if dbm_open exists
set
dbm_open d_dbm_open
eval $inlibc
case "$d_dbm_open" in
$undef)
i_ndbm="$undef"
i_gdbmndbm="$undef"
i_gdbm_ndbm="$undef"
echo "We won't be including <ndbm.h>"
val="$undef"
;;
*) val="$define"
;;
esac
fi
set d_ndbm
eval $setvar

ndbm_hdr_protochk='name=$1; hdr=$2;
eval "ihdr=\${i}_$name";
val="$undef";
if $test "$ihdr" = "$define"; then
$echo "Checking if your <$hdr> uses prototypes..." >&4;
case "$d_cplusplus" in
$define) ./protochk "$sextern_C void dbm_close(DBM *);" literal "extern \"C\" { \"$ihdr $hdr literal }" &&
val="$define" ;;
*) ./protochk "$sextern_C void dbm_close(int, int);" $ihdr $hdr || val="$define" ;;
esac;
case "$val" in
$define) $echo "Your <$hdr> seems to have prototypes";;
*) $echo "Your <$hdr> does not seem to have prototypes";;
esac;
fi;
set "d_${name}_h_uses_prototypes";
eval $setvar'

set ndbm ndbm.h
eval $ndbm_hdr_protochk
set gdbmndbm gdbm/ndbm.h
eval $ndbm_hdr_protochk
set gdbm_ndbm gdbm-ndbm.h
eval $ndbm_hdr_protochk

```

Found

in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/modified/i_ndbm.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_sighold.U 1 2006-08-24 12:32:52Z rmanfredi \$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic Licence,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic Licence; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: d_sighold.U,v \$

?RCS: Revision 3.0 1993/08/18 12:07:21 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?MAKE:d_sighold: Inlibc

?MAKE: -pick add \$@ %<

?S:d_sighold:

?S: This variable conditionally defines HAS_SIGHOLD if sighold() is

?S: available to hold signals.

?S:.

?C:HAS_SIGHOLD:

?C: This symbol, if defined, indicates that the sighold routine is

?C: available to hold signals.

?C:.

?H:#\$d_sighold HAS_SIGHOLD /**/

?H:.

?LINT:set d_sighold

:

see if sighold exists

set sighold d_sighold

eval \$inlibc

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/d_sighold.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: \$Log: i_ndbm.U,v \$
?RCS: Revision 3.0.1.1 1995/05/12 12:16:53 ram
?RCS: patch54: made more robust by checking both header and lib (ADO)
?RCS:
?RCS: Revision 3.0 1993/08/18 12:08:23 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:i_ndbm: Inhdr Inlibc Setvar
?MAKE: -pick add \$@ %<
?S:i_ndbm (d_ndbm):
?S: This variable conditionally defines the I_NDBM symbol, which
?S: indicates to the C program that <ndbm.h> exists and should
?S: be included.
?S:.
?C:I_NDBM (HAS_NDBM NDBM):
?C: This
symbol, if defined, indicates that <ndbm.h> exists and should
?C: be included.
?C:.
?H:#\$i_ndbm I_NDBM /**/
?H:.
?T:t_ndbm d_dbm_open
?LINT:set i_ndbm
: see if ndbm.h is available
?X: t_ndbm is a tentative check. We might just have the .h, not the lib -- ADO
set ndbm.h t_ndbm
eval \$inhdr
case "\$t_ndbm" in
\$define)
: see if dbm_open exists
set dbm_open d_dbm_open
eval \$inlibc
case "\$d_dbm_open" in
\$undef)
t_ndbm="\$undef"
echo "We won't be including <ndbm.h>"
;;
esac
;;
esac
val="\$t_ndbm"
set i_ndbm
eval \$setvar

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/i_ndbm.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: devtype.U,v 3.0.1.1 1994/08/29 16:31:27 ram Exp $
?RCS:
?RCS: Copyright (c) 1991-1993, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 3.0.
?RCS:
?RCS: $Log: devtype.U,v $
?RCS: Revision 3.0.1.1 1994/08/29 16:31:27 ram
?RCS: patch32: now uses new Typedef unit to compute type information
?RCS:
?RCS: Revision 3.0 1993/08/18 12:09:33 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:devtype: Myread Typedef
?MAKE: -pick add $@ %<
?S:devtype:
?S: This variable defines Dev_t to be something like dev_t, long,
?S: int, or whatever type is used to declare device numbers.
?S: This is usually the same as
?S: the type of the third argument
?S: to mknod(2).
?S:.
?C:Dev_t:
?C: This symbol holds the type used to declare device numbers.
?C: It can be int, long, dev_t, etc... This is usually the same
?C: as the type of the third argument to mknod(2).
?C: It may be necessary to include <sys/types.h> to get any
?C: typedef'ed information.
?C:.
?H:#define Dev_t $devtype /* <device> type */
?H:.
?LINT: set devtype
: see what type is used for devices
rp="What is the type used for device numbers on this system?"
set dev_t devtype long stdio.h sys/types.h
eval $typedef_ask
```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
```

debian-perl-5.26.1/U/typedefs/devtype.U

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: libdbm.U 1 2006-08-24 12:32:52Z rmanfredi $
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: $Log: libdbm.U,v $
?RCS: Revision 3.0.1.1 1997/02/28 15:56:57 ram
?RCS: patch61: replaced .a with $_a all over the place
?RCS:
?RCS: Revision 3.0 1993/08/18 12:08:58 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:libdbm: test Loc libpth _a
?MAKE: -pick add $@ %<
?S:libdbm:
?S: This variable contains the argument to pass to the loader in order
?S: to get the dbm library routines. If there is no dbm or ndbm
?S: library, it is null.
?S:.
?T:xxx
:
  see if we should include -ldbm
echo " "
if $test -r /usr/lib/libndbm$_a || $test -r /usr/local/lib/libndbm$_a ; then
  echo "-lndbm found." >&4
  libdbm='-lndbm'
elif $test -r /usr/lib/libdbm$_a || $test -r /usr/local/lib/libdbm$_a ; then
  echo "-ldb found." >&4
  libdbm='-ldb'
else
  xxx=`./loc libdbm$_a x $libpth`
  case "$xxx" in
  x)
    echo "No dbm library found." >&4
    libdbm=""
    ;;
  *)
    echo "DBM library found in $xxx." >&4
    libdbm="$xxx"
    ;;
  )
  ;;
  )
  ;;
```

esac

fi

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/libdbm.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: libpth.U 1 2006-08-24 12:32:52Z rmanfredi \$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: libpth.U,v \$

?RCS: Revision 3.0.1.6 1997/02/28 16:08:49 ram

?RCS: patch61: new loclibpth variable

?RCS:

?RCS: Revision 3.0.1.5 1995/01/11 15:31:30 ram

?RCS: patch45: call ./mips instead of just mips (WED)

?RCS:

?RCS: Revision 3.0.1.4 1994/08/29 16:29:15 ram

?RCS: patch32: added /lib/pa1.1 for HP-UX specially tuned PA-RISC libs (ADO)

?RCS: patch32: fixed information message, making it clearer (ADO)

?RCS:

?RCS: Revision 3.0.1.3 1994/06/20 07:03:54

ram

?RCS: patch30: added /usr/shlib to glibpth for shared-only libraries

?RCS:

?RCS: Revision 3.0.1.2 1994/05/13 15:26:57 ram

?RCS: patch27: fixed a typo (libpth -> glibpth)

?RCS:

?RCS: Revision 3.0.1.1 1994/05/06 15:07:53 ram

?RCS: patch23: now asks for library directories to be searched (ADO)

?RCS:

?RCS: Revision 3.0 1993/08/18 12:09:02 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?X:

?X: This unit initializes the path for C library lookup.

?X:

?MAKE:libpth glibpth xlibpth plibpth loclibpth incpth: \
usrinc incpath test cat Myread Oldconfig sysroot osname \
ccname echo cppstdin awk grep sed rm usecrosscompile

?MAKE: -pick add \$@ %<

?S:libpth:
 ?S: This variable holds the general path (space-separated) used to find
 ?S: libraries. It is intended to be used by other units.

?S:.

?S:glibpth:
 ?S: This variable holds the general path (space-separated) used to
 ?S: find libraries. It may contain directories that do not exist on
 ?S: this platform, libpth is the cleaned-up
 version.

?S:.

?S:xlibpth:
 ?S: This variable holds extra path (space-separated) used to find
 ?S: libraries on this platform, for example CPU-specific libraries
 ?S: (on multi-CPU platforms) may be listed here.

?S:.

?S:loclibpth:
 ?S: This variable holds the paths (space-separated) used to find local
 ?S: libraries. It is prepended to libpth, and is intended to be easily
 ?S: set from the command line.

?S:.

?S:plibpth:
 ?S: Holds the private path used by Configure to find out the libraries.
 ?S: Its value is prepend to libpth. This variable takes care of special
 ?S: machines, like the mips. Usually, it should be empty.

?S:.

?S:incpth:
 ?S: This variable must precede the normal include path to get the
 ?S: right one, as in "\$incpath/usr/include" or "\$incpath/usr/lib".
 ?S: Value can be "" or "/bsd43" on mips.

?S:.

?T: xxx dlist i j croak

?LINT:extern incpth

?LINT:change usrinc

?INIT:: change the next line if compiling for Xenix/286 on Xenix/386

?INIT:xlibpth='/usr/lib/386 /lib/386'

?INIT::

Possible local library directories to search.

?INIT:loclibpth="/usr/local/lib /opt/local/lib /usr/gnu/lib"

?INIT:loclibpth="\$loclibpth /opt/gnu/lib /usr/GNU/lib /opt/GNU/lib"

?INIT:

?INIT:: general looking path for locating libraries

?INIT:glibpth="/lib /usr/lib \$xlibpth"

?INIT:glibpth="\$glibpth /usr/ccs/lib /usr/ucblib /usr/local/lib"

?X: /shlib is for Digital Unix 4.0

?X: /usr/shlib is for OSF/1 systems.

?INIT:test -f /usr/shlib/libc.so && glibpth="/usr/shlib \$glibpth"

?INIT:test -f /shlib/libc.so && glibpth="/shlib \$glibpth"


```

") for i in $incpth; do
if test -f $i/errno.h -a -f $i/stdio.h -a -f $i/time.h; then
    usrinc="$i"
    break
fi
done
;;
esac

case "$usecrosscompile" in
$define|true|[yY]*)
    case "$incpth" in
") echo "Incpth not defined." >&4; croak=y ;;
*) echo "Using incpth '$incpth'." >&4 ;;
    esac
    case "$libpth" in
") echo "Libpth not defined." >&4; croak=y ;;
*) echo "Using libpth '$libpth'." >&4 ;;
    esac
    case "$usrinc" in
") echo "Usrinc not defined." >&4; croak=y ;;
*) echo "Using usrinc '$usrinc'." >&4 ;;
    esac
    case "$croak" in
y)
if test "X$sysroot" = X; then
    echo "Cannot continue, aborting." >&4; exit 1
else
    echo "Cross-compiling using sysroot $sysroot, failing to guess inc/lib paths is not fatal" >&4
fi
;;
    esac
;;
esac
;;
esac

: Default value for incpth is just usrinc
case "$incpth" in
") incpth="$usrinc";;
esac

: Set private lib path
case
"$plibpth" in
") if ./mips; then
?X: on mips, we DO NOT want /lib, and we want $incpath/usr/lib
plibpth="$incpath/usr/lib $sysroot/usr/local/lib $sysroot/usr/ccs/lib"

```

```

    fi;;
esac
case "$libpth" in
' ') dlist="";
") dlist="$loclibpth $plibpth $glibpth";
*) dlist="$libpth";;
esac

```

: Now check and see which directories actually exist, avoiding duplicates
for xxx in \$dlist

```

do
    if $test -d $xxx; then
    case " $libpth " in
*" $xxx "*) ;;
*) libpth="$libpth $xxx";;
    esac
    fi
done
$cat <<'EOM'

```

Some systems have incompatible or broken versions of libraries. Among the directories listed in the question below, please remove any you know not to be holding relevant libraries, and add any that are needed. Say "none" for none.

EOM

```

if test "X$sysroot" != X; then
    $cat <<EOM

```

You have set sysroot to \$sysroot, please supply the directories excluding sysroot

EOM

```

fi

case "$libpth" in
") dflt='none';;
*)
?X: strip leading space
set X $libpth
shift
dflt=${1+"$@"}
;;
esac
rp="Directories
to use for library searches?"
./myread
case "$ans" in
none) libpth='';;

```

```
*) libpth="$ans";;
```

```
esac
```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/modified/libpth.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: d_fchmod.U 1 2006-08-24 12:32:52Z rmanfredi $
```

```
?RCS:
```

```
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
```

```
?RCS:
```

```
?RCS: You may redistribute only under the terms of the Artistic Licence,
```

```
?RCS: as specified in the README file that comes with the distribution.
```

```
?RCS: You may reuse parts of this distribution only within the terms of
```

```
?RCS: that same Artistic Licence; a copy of which may be found at the root
```

```
?RCS: of the source tree for dist 4.0.
```

```
?RCS:
```

```
?RCS: $Log: d_fchmod.U,v $
```

```
?RCS: Revision 3.0 1993/08/18 12:05:59 ram
```

```
?RCS: Baseline for dist 3.0 netwide release.
```

```
?RCS:
```

```
?MAKE:d_fchmod: Inlibc
```

```
?MAKE: -pick add $@ %<
```

```
?S:d_fchmod:
```

```
?S: This variable conditionally defines the HAS_FCHMOD symbol, which
```

```
?S: indicates to the C program that the fchmod() routine is available
```

```
?S: to change mode of opened files.
```

```
?S:.
```

```
?C:HAS_FCHMOD (FCHMOD):
```

```
?C: This symbol, if defined, indicates that the fchmod routine is available
```

```
?C: to
```

```
change mode of opened files. If unavailable, use chmod().
```

```
?C:.
```

```
?H:#$d_fchmod HAS_FCHMOD /**/
```

```
?H:.
```

```
?LINT:set d_fchmod
```

```
: see if fchmod exists
```

```
set fchmod d_fchmod
```

```
eval $inlibc
```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/d_fchmod.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: d_gethbynm.U 1 2006-08-24 12:32:52Z rmanfredi $
```

```
?RCS:
```

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: d_gethbynm.U,v \$

?RCS: Revision 3.0 1993/08/18 12:06:08 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?MAKE:d_gethbyname: Inlibc

?MAKE: -pick add \$@ %<

?S:d_gethbyname (d_gethbynm d_gethstby):

?S: This variable conditionally defines the HAS_GETHOSTBYNAME symbol, which
?S: indicates to the C program that the gethostbyname() routine is available
?S: to look up host names in some data base or other.

?S:.

?C:HAS_GETHOSTBYNAME (GETHOSTBYNAME):

?C: This
symbol, if defined, indicates that the gethostbyname() routine is
?C: available to look up host names in some data base or other.

?C:.

?H:#\$d_gethbyname HAS_GETHOSTBYNAME /**/
?H:.

?LINT:set d_gethbyname
: see if gethostbyname exists
set gethostbyname d_gethbyname
eval \$inlibc

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/modified/d_gethbynm.U

No license file was found, but licenses were detected in source scan.

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?MAKE:d_j0 d_j0l: Inlibc

?MAKE: -pick add \$@ %<

?S:d_j0:

?S: This variable conditionally defines the HAS_J0 symbol, which

?S: indicates to the C program that the j0() routine is available.

?S:.

?S:d_j0l:

?S: This variable conditionally defines the HAS_J0L symbol, which

?S: indicates to the C program that the j0l() routine is available.

?S:
?C:HAS_J0:
?C: This symbol, if defined, indicates to the C program that the
?C: j0() function is available for Bessel functions of the first
?C: kind of the order zero, for doubles.

?C:
?C:HAS_J0L:
?C: This symbol, if defined, indicates to the C program that the
?C: j0l() function is available for Bessel functions of the first
?C: kind of the order zero, for long doubles.

?C:
?H:#\$d_j0 HAS_J0 /**/
?H:#\$d_j0l HAS_J0L /**/

?H:
?LINT:set
d_j0
?LINT:set d_j0l
: see if j0 exists
set j0 d_j0
eval \$inlibc

: see if j0l exists
set j0l d_j0l
eval \$inlibc

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_j0.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$
?RCS:
?RCS: Copyright (c) 2016 H.Merijn Brand & Todd Rinaldo
?RCS:
?RCS: You may distribute under the terms of either the GNU General Public
?RCS: License or the Artistic License, as specified in the README file.

?RCS:
?MAKE:default_inc_excludes_dot: Myread cat
?MAKE: -pick add \$@ %<
?S:default_inc_excludes_dot:
?S: When defined, remove the legacy '.' from @INC
?S:
?C:DEFAULT_INC_EXCLUDES_DOT:
?C: This symbol, if defined, removes the legacy default behavior of
?C: including '.' at the end of @INC.
?C:
?H:#\$default_inc_excludes_dot DEFAULT_INC_EXCLUDES_DOT /**/
?H:

```
: Include . in @INC
$cat <<EOM
```

Historically Perl has provided a final fallback of the current working directory '.' when searching for a library. This, however, can lead to problems when a Perl program which loads optional modules is called from a shared directory. This can lead to executing unexpected code.

EOM

```
# When changing to exclude by
default:
case "$default_inc_excludes_dot" in
  $undef|false|[nN]*) dflt="n" ;;
  *)                  dflt="y" ;;
esac
# To turn exclude off by default:
#case "$default_inc_excludes_dot" in
#  $define|true|[yY]*) dflt="y" ;;
#  *)                  dflt="n" ;;
#esac

rp='Exclude '.' from @INC by default? '
./myread
case "$ans" in
  [nN]|undef) default_inc_excludes_dot="$undef" ;;
  *)         default_inc_excludes_dot="$define" ;;
esac
```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/perl/defaultincdot.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: Rcs.U 1 2006-08-24 12:32:52Z rmanfredi $
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: $Log: Rcs.U,v $
?RCS: Revision 3.0 1993/08/18 12:05:15 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
```

?X:

?X: This is a unit that helps people who write SH scripts and keep them under

?X: RCS, but don't think to protect the \$Log and other \$Id keywords from

?X: variable substitution (or people like me who do not like to).

?X:

?MAKE:Author Date Header Id Locker Log RCSfile Revision Source State: Oldconfig

?MAKE: -pick weed \$@ %<

?LINT:describe Author

Date Header Id Locker Log RCSfile Revision Source State

: preserve RCS keywords in files with variable substitution, grrr

?Author:Author='\$Author'

?Date:Date='\$Date'

?Header:Header='\$Header'

?Id:Id='\$Id'

?\$Locker'

?Log:Log='\$Log'

?RCSfile:RCSfile='\$RCSfile'

?Revision:Revision='\$Revision'

?Source:Source='\$Source'

?State:State='\$State'

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/Rcs.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_semctl.U 1 2006-08-24 12:32:52Z rmanfredi \$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic Licence,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic Licence; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: d_semctl.U,v \$

?RCS: Revision 3.0 1993/08/18 12:07:04 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?MAKE:d_semctl: Inlibc

?MAKE: -pick add \$@ %<

?S:d_semctl:

?S: This variable conditionally defines the HAS_SEMCTL symbol, which

?S: indicates to the C program that the semctl() routine is available.

?S:.

?C:HAS_SEMCTL:

?C: This symbol, if defined, indicates that the semctl() routine is

?C: available to perform semaphore control operations.

?C:.

?H:#\$d_semctl

HAS_SEMCTL /**/

?H:.

?LINT:set d_semctl

: see if semctl exists

set semctl d_semctl

eval \$inlibc

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/d_semctl.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_getprotoent_r.U,v 0RCS:

?RCS: Copyright (c) 2002,2003 Jarkko Hietaniemi

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?RCS: Generated by the reentr.pl from the Perl 5.8 distribution.

?RCS:

?MAKE:d_getprotoent_r getprotoent_r_proto: Inlibc Protochk Hasproto \
i_systypes usethreads i_netdb extern_C

?MAKE: -pick add \$@ %<

?S:d_getprotoent_r:

?S: This variable conditionally defines the HAS_GETPROTOENT_R symbol,

?S: which indicates to the C program that the getprotoent_r()

?S: routine is available.

?S:.

?S:getprotoent_r_proto:

?S: This variable encodes the prototype of getprotoent_r.

?S: It is zero if d_getprotoent_r is undef, and one of the

?S: REENTRANT_PROTO_T_ABC macros of reentr.h if d_getprotoent_r

?S: is defined.

?S:.

?C:HAS_GETPROTOENT_R:

?C: This symbol, if defined, indicates that the getprotoent_r
routine

?C: is available to getprotoent re-entrantly.

?C:.

?C:GETPROTOENT_R_PROTO:

?C: This symbol encodes the prototype of getprotoent_r.

?C: It is zero if d_getprotoent_r is undef, and one of the

?C: REENTRANT_PROTO_T_ABC macros of reentr.h if d_getprotoent_r

?C: is defined.

?C:.

```

?H:#$d_getprotoent_r HAS_GETPROTOENT_R /**/
?H:#define GETPROTOENT_R_PROTO $getprotoent_r_proto /**/
?H:.
?T:try hdrs d_getprotoent_r_proto
: see if getprotoent_r exists
set getprotoent_r d_getprotoent_r
eval $inlibc
case "$d_getprotoent_r" in
"$define")
hdrs="$i_systypes sys/types.h define stdio.h $i_netdb netdb.h"
case "$d_getprotoent_r_proto:$usethreads" in
":define") d_getprotoent_r_proto=define
set d_getprotoent_r_proto getprotoent_r $hdrs
eval $hasproto ;;
*) ;;
esac
case "$d_getprotoent_r_proto" in
define)
case "$getprotoent_r_proto" in
"|0) try='int getprotoent_r(struct protoent*, char*, size_t, struct protoent**);'
./protochk "$extern_C $try" $hdrs && getprotoent_r_proto=I_SBWR
;;
esac
case "$getprotoent_r_proto" in
"|0) try='int getprotoent_r(struct protoent*, char*, int);'
./protochk "$extern_C $try" $hdrs && getprotoent_r_proto=I_SBI ;;
esac
case "$getprotoent_r_proto" in
"|0) try='struct protoent* getprotoent_r(struct protoent*, char*, int);'
./protochk "$extern_C $try" $hdrs && getprotoent_r_proto=S_SBI ;;
esac
case "$getprotoent_r_proto" in
"|0) try='int getprotoent_r(struct protoent*, struct protoent_data*);'
./protochk "$extern_C $try" $hdrs && getprotoent_r_proto=I_SD ;;
esac
case "$getprotoent_r_proto" in
"|0) d_getprotoent_r=undef
getprotoent_r_proto=0
echo "Disabling getprotoent_r, cannot determine prototype." >&4 ;;
* ) case "$getprotoent_r_proto" in
REENTRANT_PROTO*) ;;
*) getprotoent_r_proto="REENTRANT_PROTO_$getprotoent_r_proto" ;;
esac
echo "Prototype: $try" ;;
esac
;;
*) case "$usethreads" in
define) echo "getprotoent_r has no prototype, not using it." >&4 ;;

```

```

esac
d_getprotoent_r=undef
getprotoent_r_proto=0
;;
esac
;;
*) getprotoent_r_proto=0
;;
esac

```

Found

in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/threads/d_getprotoent_r.U
```

No license file was found, but licenses were detected in source scan.

?RCS: Copyright (c) 2016 Tony Cook

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?MAKE:dtraceobject dtracexnolib: usedtrace dtrace cc cflags optimize \

Compile cat rm_try

?MAKE: -pick add \$@ %<

?S:dtraceobject:

?S: Whether we need to build an object file with the dtrace tool.

?S:.

?S:dtracexnolib:

?S: Whether dtrace accepts -xnolib. If available we call dtrace -h

?S: and dtrace -G with -xnolib to allow dtrace to run in a jail on

?S: FreeBSD.

?S:.

?T:xnolib

: Probe whether dtrace builds an object, as newer Illumos requires an input

: object file that uses at least one of the probes defined in the .d file

case "\$usedtrace" in

\$define)

case "\$dtracexnolib" in

\$define|true|[yY]*)

dtracexnolib=\$define

\$dtrace -h -xnolib -s ../perldtrace.d -o perldtrace.h

;;

'|')

if \$dtrace

-h -xnolib -s ../perldtrace.d -o perldtrace.h 2>&1 ; then

dtracexnolib=\$define

echo "Your dtrace accepts -xnolib"

elif \$dtrace -h -s ../perldtrace.d -o perldtrace.h 2>&1 ; then

```

dtracexnolibs=$undef
echo "Your dtrace doesn't accept -xnolibs"
else
    echo "Your dtrace doesn't work at all, try building without dtrace support" >&4
    exit 1
fi
;;
*)
    dtracexnolibs=$undef
$dtrace -h -s ../perldtrace.d -o perldtrace.h
;;
esac
case $dtracexnolibs in
$define) xnolibs=-xnolibs ;;
*) xnolibs= ;;
esac

case "$dtraceobject" in
$define|true|[yY]*)
    dtraceobject=$define
    ;;
'|")
    $cat >try.c <<EOM
#include "perldtrace.h"
int main(void) {
    PERL_LOADED_FILE("dummy");
    return 0;
}
EOM
    dtraceobject=$undef
    if $cc -c -o try.o $optimize $ccflags try.c \
        && $dtrace -G $xnolibs -s ../perldtrace.d try.o >/dev/null 2>&1; then
        dtraceobject=$define
        echo "Your dtrace builds an object file"
    fi
    ;;
*) dtraceobject=$undef ;;
esac
$rm_try perldtrace.o perldtrace.h
esac

```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/perl/dtraceobject.U
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_setuid.U 1 2006-08-24 12:32:52Z rmanfredi \$

?RCS:

```

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: $Log: d_setruid.U,v $
?RCS: Revision 3.0 1993/08/18 12:07:15 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:d_setruid: Inlibc
?MAKE: -pick add $@ %<
?S:d_setruid:
?S: This variable conditionally defines the HAS_SETRUID symbol, which
?S: indicates to the C program that the setruid() routine is available
?S: to change the real uid of the current program.
?S:.
?C:HAS_SETRUID (SETRUID):
?C: This symbol, if defined, indicates that the setruid
routine is available
?C: to change the real uid of the current program.
?C:.
?H:#$d_setruid HAS_SETRUID /**/
?H:.
?LINT:set d_setruid
: see if setruid exists
set setruid d_setruid
eval $inlibc

```

Found in path(s):

```

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/d_setruid.U

```

No license file was found, but licenses were detected in source scan.

```

?RCS: $Id$
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: Original Author: Andy Dougherty <doughera@lafcol.lafayette.edu>
?RCS:

```

?RCS: \$Log: archlib.U,v \$
?RCS: Revision 3.0.1.5 1997/02/28 15:23:38 ram
?RCS: patch61: skip existence checks for archlib
?RCS:
?RCS: Revision 3.0.1.4 1995/09/25 09:15:18 ram
?RCS: patch59: unit is now forced to the top of Configure, if possible
?RCS:
?RCS: Revision 3.0.1.3 1995/02/15 14:14:14 ram
?RCS: patch51: architecture name is now computed by a separate unit
?RCS:
?RCS: Revision 3.0.1.2 1995/01/30 14:32:22 ram
?RCS:
patch49: archname is now systematically recomputed
?RCS: patch49: can now handle installation prefix changes (from WED)
?RCS:
?RCS: Revision 3.0.1.1 1994/10/29 16:02:36 ram
?RCS: patch36: created by ADO
?RCS:
?MAKE:d_archlib archlib archlibexp installarchlib: archname afs spackage \
cat Getfile Loc Oldconfig prefixexp privlib test Prefixit Prefixup
?MAKE: -pick add \$@ %<
?Y:TOP
?S:d_archlib:
?S: This variable conditionally defines ARCHLIB to hold the pathname
?S: of architecture-dependent library files for \$package. If
?S: \$archlib is the same as \$privlib, then this is set to undef.
?S:.
?S:archlib:
?S: This variable holds the name of the directory in which the user wants
?S: to put architecture-dependent public library files for \$package.
?S: It is most often a local directory such as /usr/local/lib.
?S: Programs using this variable must be prepared to deal
?S: with filename expansion.
?S:.
?S:archlibexp:
?S: This variable is the same as the archlib variable, but is
?S: filename
expanded at configuration time, for convenient use.
?S:.
?S:installarchlib:
?S: This variable is really the same as archlibexp but may differ on
?S: those systems using AFS. For extra portability, only this variable
?S: should be used in makefiles.
?S:.
?C:ARCHLIB:
?C: This variable, if defined, holds the name of the directory in
?C: which the user wants to put architecture-dependent public
?C: library files for \$package. It is most often a local directory

?C: such as /usr/local/lib. Programs using this variable must be
 ?C: prepared to deal with filename expansion. If ARCHLIB is the
 ?C: same as PRIVLIB, it is not defined, since presumably the
 ?C: program already searches PRIVLIB.
 ?C:.
 ?C:ARCHLIB_EXP:
 ?C: This symbol contains the ~name expanded version of ARCHLIB, to be used
 ?C: in programs that are not prepared to deal with ~ expansion at run-time.
 ?C:.
 ?H:#\$d_archlib ARCHLIB "\$sarchlib" /**/
 ?H:#\$d_archlib ARCHLIB_EXP "\$sarchlibexp" /**/
 ?H:.

```
: determine where public architecture
dependent libraries go
set archlib archlib
eval $prefixit
case "$sarchlib" in
")
case "$sprivlib" in
")
dflt=`./loc . ." $prefixexp/lib /usr/local/lib /usr/lib /lib`
set dflt
eval $prefixup
;;
*) dflt="$sprivlib/$sarchname";;
esac
;;
*) dflt="$sarchlib";;
esac
cat <<EOM
```

\$spackage contains architecture-dependent library files. If you are sharing libraries in a heterogeneous environment, you might store these files in a separate location. Otherwise, you can just include them with the rest of the public library files.

```
EOM
fn=d+~
rp='Where do you want to put the public architecture-dependent libraries?'
./getfile
archlib="$ans"
archlibexp="$ansexp"

if $afs; then
$cat <<EOM
```

Since you are running AFS, I need to distinguish the directory in which private files reside from the directory in which they are installed (and from

which they are presumably copied to the former directory by occult means).

EOM

```
case "$installarchlib" in
*) dflt=`echo $archlibexp | sed 's#^/afs/#/afs/#^';`
*)
dflt="$installarchlib";
esac
fn=de~
rp='Where will architecture-dependent library files be installed?'
./getfile
installarchlib="$ans"
else
installarchlib="$archlibexp"
fi
if $test X"$archlib" = X"$privlib"; then
d_archlib="$undef"
else
d_archlib="$define"
fi
```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/archlib.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: d_truncate.U 1 2006-08-24 12:32:52Z rmanfredi $
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: $Log: d_truncate.U,v $
?RCS: Revision 3.0 1993/08/18 12:07:48 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:d_truncate: Inlibc
?MAKE: -pick add $@ %<
?S:d_truncate:
?S: This variable conditionally defines HAS_TRUNCATE if truncate() is
?S: available to truncate files.
?S:.
?C:HAS_TRUNCATE (TRUNCATE):
?C: This symbol, if defined, indicates that the truncate routine is
```

?C: available to truncate files.
?C:.
?H:#\$d_truncate HAS_TRUNCATE /**/
?H:.
?LINT:set
d_truncate
: see if truncate exists
set truncate d_truncate
eval \$inlibc

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/d_truncate.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$
?RCS:
?RCS: Copyright (c) 1999 Jarkko Hietaniemi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 3.0.
?RCS:
?MAKE:d_getspnam: Inlibc
?MAKE:-pick add \$@ %<
?S:d_getspnam:
?S: This variable conditionally defines HAS_GETSPNAM if getspnam() is
?S: available to retrieve SysV shadow password entries by name.
?S:.
?C:HAS_GETSPNAM:
?C: This symbol, if defined, indicates that the getspnam system call is
?C: available to retrieve SysV shadow password entries by name.
?C:.
?H:#\$d_getspnam HAS_GETSPNAM /**/
?H:.
?LINT:set d_getspnam
: see if getspnam exists
set getspnam d_getspnam
eval \$inlibc

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_getspnam.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:
?RCS: Copyright (c) 1998, Jarkko Hietaniemi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 3.0.
?RCS:
?MAKE:i_machcthr: Inhdr usethreads
?MAKE: -pick add \$@ %<
?S:i_machcthr:
?S: This variable conditionally defines the I_MACH_CTHREADS symbol,
?S: and indicates whether a C program should include <mach/cthreads.h>.
?S:.
?C:I_MACH_CTHREADS:
?C: This symbol, if defined, indicates to the C program that it should
?C: include <mach/cthreads.h>.
?C:.
?H:#\$i_machcthr I_MACH_CTHREADS /**/
?H:.
: see if mach cthreads are available
if test "X\$usethreads" = "X\$define"; then
set mach/cthreads.h i_machcthr
eval \$inhdr
else
i_machcthr="\$undef"
fi

Found
in path(s):
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/threads/i_machcthr.U
No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$
?RCS:
?RCS: Copyright (c) 1999 Jarkko Hietaniemi
?RCS:
?RCS: You may distribute under the terms of either the GNU General Public
?RCS: License or the Artistic License, as specified in the README file.
?RCS:
?MAKE:uidformat: uidsize uidsign ivsize uvsize longsize intsize shortsize \
ivdformat uvuformat test echo
?MAKE: -pick add \$@ %<
?S:uidformat:
?S: This variable contains the format string used for printing a Uid_t.
?S:.

```

?C:Uid_t_f:
?C: This symbol defines the format string used for printing a Uid_t.
?C:.
?H:#define Uid_t_f $uidformat /**/
?H:.
: Check format string for UID
echo " "
$echo "Checking the format string to be used for uids..." >&4

case "$uidsign" in
-1) if $test X"$uidsize" = X"$ivsize"; then
    uidformat="$ivdformat"
    else
    if $test X"$uidsize" = X"$longsize"; then
        uidformat="ld"
    else
    if $test X"$uidsize" = X"$intsize"; then
        uidformat="d"
    else
    if $test X"$uidsize"
= X"$shortsize"; then
        uidformat="hd"
    fi
    fi
    fi
    fi
    ;;
*) if $test X"$uidsize" = X"$vsize"; then
    uidformat="$vuvformat"
    else
    if $test X"$uidsize" = X"$longsize"; then
        uidformat="lu"
    else
    if $test X"$uidsize" = X"$intsize"; then
        uidformat="u"
    else
    if $test X"$uidsize" = X"$shortsize"; then
        uidformat="hu"
    fi
    fi
    fi
    fi
    ;;
esac

```

Found in path(s):

```

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/typedefs/uidf.U

```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: d_setnent.U,v 3.0 1993/08/18 12:06:09 ram Exp $
?RCS:
?RCS: Copyright (c) 1991-1993, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 3.0.
?RCS:
?RCS: $Log: d_setnent.U,v $
?RCS: Revision 3.0 1993/08/18 12:06:09 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:d_setnent: Inlibc
?MAKE: -pick add $@ %<
?S:d_setnent:
?S: This variable conditionally defines HAS_SETNETENT if setnent() is
?S: available.
?S:.
?C:HAS_SETNETENT:
?C: This symbol, if defined, indicates that the setnent() routine is
?C: available.
?C:.
?H:#$d_setnent HAS_SETNETENT /**/
?H:.
?LINT:set d_setnent
: see if setnent exists
set
setnent d_setnent
eval $inlibc
```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/modified/d_setnent.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: d_statblks.U,v 3.0 1993/08/18 12:07:29 ram Exp $
?RCS:
?RCS: Copyright (c) 1991-1993, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 3.0.
```

```

?RCS:
?RCS: $Log: d_statblks.U,v $
?RCS: Revision 3.0 1993/08/18 12:07:29 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:d_statblks: Hasfield i_sysstat
?MAKE: -pick add $@ %<
?S:d_statblks:
?S: This variable conditionally defines USE_STAT_BLOCKS
?S: if this system has a stat structure declaring
?S: st_blksize and st_blocks.
?S:.
?C:USE_STAT_BLOCKS (STATBLOCKS):
?C: This symbol is defined if this system has a stat structure declaring
?C: st_blksize and st_blocks.
?C:.
?H:?%<:#ifndef
USE_STAT_BLOCKS
?H:?%<:#$d_statblks USE_STAT_BLOCKS /**/
?H:?%<:#endif
?H:.
?LINT:set d_statblks
: see if stat knows about block sizes
echo " "
echo "Checking to see if your struct stat has st_blocks field..." >&4
set d_statblks stat st_blocks $i_sysstat sys/stat.h
eval $hasfield

```

Found in path(s):

```

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/modified/d_statblks.U

```

No license file was found, but licenses were detected in source scan.

```

?RCS: $Id$
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: $Log: orderlib.U,v $
?RCS: Revision 3.0.1.4 1997/02/28 16:18:18 ram
?RCS: patch61: replaced .a with $_a all over the place
?RCS: patch61: likewise for .o replaced by $_o
?RCS: patch61: now uses the ar located by Loc.U

```

```

?RCS:
?RCS: Revision 3.0.1.3 1995/01/11 15:33:04 ram
?RCS: patch45: allows hint files to specify their own value for 'ranlib'
?RCS:
?RCS: Revision 3.0.1.2 1994/10/29 16:26:48 ram
?RCS: patch36: now performs a real small compile for accurate checks (ADO)
?RCS:
?RCS: Revision 3.0.1.1
    1994/08/29 16:31:17 ram
?RCS: patch32: use cc variable instead of hardwired 'cc' in 1st compile
?RCS:
?RCS: Revision 3.0 1993/08/18 12:09:26 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:orderlib ranlib: Loc ar cat test rm +cc +ccflags +ldflags +libs _a _o
?MAKE: -pick add $@ %<
?S:orderlib:
?S: This variable is "true" if the components of libraries must be ordered
?S: (with `lorder $* | tsort`) before placing them in an archive. Set to
?S: "false" if ranlib or ar can generate random libraries.
?S:.
?S:ranlib:
?S: This variable is set to the pathname of the ranlib program, if it is
?S: needed to generate random libraries. Set to ":" if ar can generate
?S: random libraries or if random libraries are not supported
?S:.
?F:!foobar
: see if ar generates random libraries by itself
echo " "
echo "Checking how to generate random libraries on your machine..." >&4
?X: Some systems (like MIPS) complain when running ar... Others like Ultrix
?X: need an explicit 'ar ts'
to add the table of contents.
?X: Still others like Linux run ar ts successfully, but still need ranlib.
?X: This set of tests seems the minimum necessary to check out Linux.
?X: We need to explicitly put the entries in out-of-order so that Sun's ld
?X: will fail. (Otherwise it complains, but gives an exit status of 0.)
echo 'int bar1() { return bar2(); }' > bar1.c
echo 'int bar2() { return 2; }' > bar2.c
$cat > foo.c <<'EOP'
int main() { printf("%d\n", bar1()); exit(0); }
EOP
$cc $ccflags -c bar1.c >/dev/null 2>&1
$cc $ccflags -c bar2.c >/dev/null 2>&1
$cc $ccflags -c foo.c >/dev/null 2>&1
$ar rc bar$_a bar2$_o bar1$_o >/dev/null 2>&1
if $cc $ccflags $ldflags -o foobar foo$_o bar$_a $libs >/dev/null 2>&1 &&
./foobar >/dev/null 2>&1; then

```

```

echo "ar appears to generate random libraries itself."
orderlib=false
ranlib=":"
elif $ar ts bar$_a >/dev/null 2>&1 &&
$cc $ccflags $ldflags -o foobar foo$_o bar$_a $libs >/dev/null 2>&1 &&
./foobar >/dev/null 2>&1; then
echo "a table of contents
needs to be added with 'ar ts'."
orderlib=false
ranlib="$ar ts"
else
?X: Allow hints to specify their own ranlib "script". For instance, on
?X: some NeXT machines, the timestamp put by ranlib is not correct, and this
?X: may raise tedious recompiles for nothing. Therefore, NeXT may add the
?X: ranlib='sleep 5; /bin/ranlib' line in their hints to "fix" that.
?X: (reported by Andreas Koenig <k@franz.ww.tu-berlin.de>)
case "$ranlib" in
:) ranlib="";;
")
ranlib=`./loc ranlib X /usr/bin /bin /usr/local/bin`
$test -f $ranlib || ranlib="
;;
esac
if $test -n "$ranlib"; then
echo "your system has '$ranlib'; we'll use that."
orderlib=false
else
echo "your system doesn't seem to support random libraries"
echo "so we'll use lorder and tsort to order the libraries."
orderlib=true
ranlib=":"
fi
fi
$rm -f foo* bar*

```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/orderlib.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: cpp_trad.U 1 2006-08-24 12:32:52Z rmanfredi $
```

```
?RCS:
```

```
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
```

```
?RCS:
```

```
?RCS: You may redistribute only under the terms of the Artistic Licence,
```

```
?RCS: as specified in the README file that comes with the distribution.
```

```
?RCS: You may reuse parts of this distribution only within the terms of
```

```
?RCS: that same Artistic Licence; a copy of which may be found at the root
```

```

?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: $Log: cpp_stuff.U,v $
?MAKE:cpp_trad: cpp cat contains rm
?MAKE: -pick add $@ %<
?S:cpp_trad:
?S: This variable contains the program to run to get traditional C
?S: preprocessor semantics and not ISO C semantics: we want something
?S: that knows as little about C as possible to use as a more general
?S: purpose preprocessor.
?S:.
?F:!foo.c !foo.cpp
: how do we get traditional cpp semantics?
echo " "
echo "Checking to see how to get traditional cpp semantics..."
>&4
$cat >foo.c <<'EOF'
#define A(x) x
#define B(y) y
A(a)B(b)
EOF
if $cpp foo.c >foo.cpp; $contains ab foo.cpp >/dev/null 2>&1; then
echo "Plain '$cpp' works just fine."
cpp_trad="$cpp"
elif $cpp -traditional foo.c >foo.cpp; \
$contains ab foo.cpp >/dev/null 2>&1; then
echo "We'll use '$cpp -traditional' to get proper semantics."
cpp_trad="$cpp -traditional"
else
echo "I don't know how to get traditional semantics with '$cpp'." >&4
cpp_trad="$cpp"
fi
$rm -f foo.c foo.cpp

```

Found in path(s):

```

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/cpp_trad.U

```

No license file was found, but licenses were detected in source scan.

```

?RCS: $Id$

```

```

?RCS:

```

```

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

```

```

?RCS:

```

```

?RCS: You may redistribute only under the terms of the Artistic License,

```

```

?RCS: as specified in the README file that comes with the distribution.

```

```

?RCS: You may reuse parts of this distribution only within the terms of

```

```

?RCS: that same Artistic License; a copy of which may be found at the root

```

```

?RCS: of the source tree for dist 4.0.

```

```

?RCS:
?RCS: $Log: Finish.U,v $
?RCS: Revision 3.0.1.6 1995/02/15 14:09:30 ram
?RCS: patch51: now clearer about how to edit config.sh at the prompt (WED)
?RCS:
?RCS: Revision 3.0.1.5 1994/10/29 15:53:14 ram
?RCS: patch36: added ?F: line for metalint file checking
?RCS:
?RCS: Revision 3.0.1.4 1994/05/06 14:19:37 ram
?RCS: patch23: added blank lines around 'End of Configure'
?RCS:
?RCS: Revision 3.0.1.3 1993/10/16 13:46:09 ram
?RCS: patch12: replaced Config_h by Magic_h in the dependency line
?RCS:
?RCS:
?RCS: Revision 3.0.1.2 1993/09/13 15:45:26 ram
?RCS: patch10: fixed shell evaluation w/o shell escape while in silent mode
?RCS:
?RCS: Revision 3.0.1.1 1993/08/30 08:55:59 ram
?RCS: patch8: prevents myread from blocking on empty answers, exceptionally
?RCS:
?RCS: Revision 3.0 1993/08/18 12:04:55 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?X:
?X: This unit is the very last one in the Configure script. It runs all the
?X: SH files, which among other things produce config.h and (usually) Makefile.
?X: It offers to do a make depend if the Makefile contains that target.
?X:
?MAKE:Finish: Chk_MANI Extract Myread Oldsym Magic_h cat rm contains \
test package make
?MAKE: -pick add $@ %<
?F:!config.sh
?T:pwd
: Finish up by extracting the .SH files
case "$alldone" in
exit)
?X: They supplied the -E switch
echo "Stopping at your request, leaving temporary files around."
exit 0
;;
cont)
;;
")
dflt="
nostick=true
$cat <<EOM

```

If you'd like to make any changes to the config.sh file before I begin to configure things, do it as a shell escape now (e.g. !vi config.sh).

EOM

```
rp="Press return or use a shell escape to edit config.sh:"
```

```
. UU/myread
```

```
nostick="
```

```
case "$ans" in
```

```
) ;;
```

```
*) : in case they cannot read
```

```
sh 1>&4 -c "$ans";;
```

```
esac
```

```
::
```

```
esac
```

: if this fails, just run all the .SH files by hand

```
./config.sh
```

?X:

?X: Turn silent mode off from now on (we want a verbose file extraction).

?X: This means we have to explicitly test for '\$silent' from now on to

?X: strip off any verbose messages.

?X:

```
echo " "
```

```
exec 1>&4
```

```
pwd=`pwd`
```

```
./UU/extract
```

```
cd "$pwd"
```

```
if $contains '^depend:' [Mm]akefile >/dev/null 2>&1; then
```

```
dflt=y
```

```
case "$silent" in
```

```
true) ;;
```

```
*)
```

```
$cat <<EOM
```

Now you need to generate make dependencies by running "\$make depend".

You might prefer to run it in background: "\$make depend > makedepend.out &"

It can take a while, so you might not want to run it right now.

EOM

```
::
```

```
esac
```

```
rp="Run $make depend now?"
```

```
. UU/myread
```

```
case "$ans" in
```

```
y*)
```

```

$make depend
&& echo "Now you must run '$make'."
;;
*)
echo "You must run '$make depend' then '$make'."
;;
esac
elif test -f [Mm]akefile; then
echo " "
echo "Now you must run a $make."
else
echo "Configure done."
fi

if $test -f Policy.sh; then
$cat <<EOM

```

If you compile \$package on a different machine or from a different object directory, copy the Policy.sh file from this object directory to the new one before you run Configure -- this will help you with most of the policy defaults.

```

EOM
fi
if $test -f UU/config.msg; then
echo "Hmm. I also noted the following information while running:"
echo " "
$cat UU/config.msg >&4
fi
?X:
?X: kit*isdone files are left over by shell archives built using the makedist
?X: script which comes from dist, while ark*isdone files are left over by
?X: the cshar archive maker.
?X:
$rm -f kit*isdone ark*isdone
$rm -rf UU

```

: End of Configure

Found in path(s):

```

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/Finish.U

```

No license file was found, but licenses were detected in source scan.

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?MAKE:d_logb: Inlibc

?MAKE: -pick add \$@ %<
?S:d_logb:
?S: This variable conditionally defines the HAS_LOGB symbol, which
?S: indicates to the C program that the logb() routine is available
?S: to extract the exponent of x.
?S:.
?C:HAS_LOGB:
?C: This symbol, if defined, indicates that the logb routine is
?C: available to do the logb function.
?C:.
?H:#\$d_logb HAS_LOGB /**/
?H:.
?LINT:set d_logb
: see if logb exists
set logb d_logb
eval \$inlibc

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_logb.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_fsetpos.U 1 2006-08-24 12:32:52Z rmanfredi \$
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: \$Log: d_fsetpos.U,v \$
?RCS: Revision 3.0.1.1 1994/06/20 06:57:38 ram
?RCS: patch30: created
?RCS:
?MAKE:d_fsetpos: Inlibc
?MAKE: -pick add \$@ %<
?S:d_fsetpos:
?S: This variable conditionally defines HAS_FSETPOS if fsetpos() is
?S: available to set the file position indicator.
?S:.
?C:HAS_FSETPOS:
?C: This symbol, if defined, indicates that the fsetpos routine is
?C: available to set the file position indicator, similar to fseek().
?C:.
?H:#\$d_fsetpos

HAS_FSETPOS /**/

?H:.

?LINT:set d_fsetpos

: see if fsetpos exists

set fsetpos d_fsetpos

eval \$inlibc

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/d_fsetpos.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 2000 Jarkko Hietaniemi

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?MAKE:d_strtold: Inlibc

?MAKE: -pick add \$@ %<

?S:d_strtold:

?S: This variable conditionally defines the HAS_STRTOLD symbol, which

?S: indicates to the C program that the strtold() routine is available.

?S:.

?C:HAS_STRTOLD:

?C: This symbol, if defined, indicates that the strtold routine is

?C: available to convert strings to long doubles.

?C:.

?H:#\$d_strtold HAS_STRTOLD /**/

?H:.

?LINT:set d_strtold

: see if strtold exists

set strtold d_strtold

eval \$inlibc

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_strtold.U

No license file was found, but licenses were detected in source scan.

/*

* \$Id: rename.C,v 3.0.1.1 1994/01/24 13:58:42 ram Exp ram \$

*

* Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

*

* You may redistribute only under the terms of the Artistic Licence,

* as specified in the README file that comes with the distribution.

```

* You may reuse parts of this distribution only within the terms of
* that same Artistic Licence; a copy of which may be found at the root
* of the source tree for dist 4.0.
*
* $Log: rename.C,v $
* Revision 3.0.1.1 1994/01/24 13:58:42 ram
* patch16: created
*
*/

```

Found in path(s):

```

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/lib/C/fake/rename.C

```

No license file was found, but licenses were detected in source scan.

```

?RCS: $Id: lintlib.U 1 2006-08-24 12:32:52Z rmanfredi $
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: $Log: lintlib.U,v $
?RCS: Revision 3.0 1993/08/18 12:09:05 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:lintlib lintlibexp: Getfile Loc Oldconfig
?MAKE: -pick add $@ %<
?S:lintlib:
?S: This variable holds the name of the directory in which the user wants
?S: to put public lint-library files for the package in question. It is
?S: most often a local directory such as /usr/local/lib/lint. Programs using
?S: this variable must be prepared to
?S: deal with ~name expansion.
?S:.
?S:lintlibexp:
?S: This variable is the same as the lintlib variable, but is filename
?S: expanded at configuration time, for convenient use in your makefiles.
?S:.
: determine where public lint libraries go
case "$lintlib" in
") dflt=`./loc . ." /usr/local/lib/lint /usr/lib/lint /usr/lib`;;
*) dflt="$lintlib" ;;
esac
echo " "

```

```
fn=d~
rp='Where do you want to put the public lint libraries?'
./getfile
lintlib="$ans"
lintlibexp="$ansexp"
```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/lintlib.U
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: d_safebcpy.U,v \$

?RCS: Revision 3.0.1.4 1997/02/28 15:40:58 ram

?RCS: patch61: improved overlapping copy check

?RCS: patch61: comfort them if they have memmove

?RCS: patch61: added ?F: metalint hint

?RCS:

?RCS: Revision 3.0.1.3 1995/07/25 13:58:40 ram

?RCS: patch56: re-arranged compile line to include ldflags before objects

?RCS:

?RCS: Revision 3.0.1.2 1995/01/11 15:29:23 ram

?RCS: patch45: added 'ldflags' to the test compile line (ADO)

?RCS:

?RCS: Revision 3.0.1.1 1994/05/06 14:49:03

ram

?RCS: patch23: ensure string is not optimized in read-only memory (ADO)

?RCS:

?RCS: Revision 3.0 1993/08/18 12:06:58 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?MAKE:d_safebcpy: cat d_bcopy +cc +optimize +ccflags +ldflags +libs rm \
d_memmove i_memory i_stdlib i_string i_unistd Oldconfig Setvar

?MAKE: -pick add \$@ %<

?S:d_safebcpy:

?S: This variable conditionally defines the HAS_SAFE_BCOPY symbol if

?S: the bcopy() routine can do overlapping copies.

?S:.

?C:HAS_SAFE_BCOPY (SAFE_BCOPY):

?C: This symbol, if defined, indicates that the bcopy routine is available
?C: to copy potentially overlapping memory blocks. Otherwise you should
?C: probably use memmove() or memcpy(). If neither is defined, roll your
?C: own version.

?C:.

```
?H:#$d_safebcopy HAS_SAFE_BCOPY /**/
```

?H:.

```
?F:!safebcopy
```

```
?LINT: set d_safebcopy
```

```
: can bcopy handle overlapping blocks?
```

```
?X: assume the worst
```

```
val="$undef"
```

```
case "$d_bcopy" in
```

```
"$define")
```

```
echo " "
```

```
echo "Checking to see if your bcopy() can do overlapping  
copies..." >&4
```

```
$cat >foo.c <<EOCP
```

```
#$i_memory I_MEMORY
```

```
#$i_stdlib I_STDLIB
```

```
#$i_string I_STRING
```

```
#$i_unistd I_UNISTD
```

```
EOCP
```

```
$cat >>foo.c <<'EOCP'
```

```
#include <stdio.h>
```

```
#ifdef I_MEMORY
```

```
# include <memory.h>
```

```
#endif
```

```
#ifdef I_STDLIB
```

```
# include <stdlib.h>
```

```
#endif
```

```
#ifdef I_STRING
```

```
# include <string.h>
```

```
#else
```

```
# include <strings.h>
```

```
#endif
```

```
#ifdef I_UNISTD
```

```
# include <unistd.h> /* Needed for NetBSD */
```

```
#endif
```

```
int main()
```

```
{
```

```
char buf[128], abc[128];
```

```
char *b;
```

```
int len;
```

```
int off;
```

```
int align;
```

```
?X: Copy "abcde..." string to char abc[] so that gcc doesn't
```

?X: try to store the string in read-only memory.

```
bcopy("abcdefghijklmnopqrstuvwxy0123456789", abc, 36);
```

```
for (align = 7; align >= 0; align--) {  
  for (len = 36; len; len--) {  
    b = buf+align;  
    bcopy(abc, b, len);  
    for (off = 1; off <= len; off++) {  
      bcopy(b, b+off, len);  
      bcopy(b+off, b, len);  
      if (bcmp(b, abc, len))  
        exit(1);  
    }  
  }  
}  
exit(0);  
}
```

EOCP

```
if $cc $optimize $ccflags $ldflags \  
  -o safebcpy foo.c $libs >/dev/null 2>&1; then  
  if ./safebcpy  
  2>/dev/null; then  
    echo "Yes, it can."  
    val="$define"  
  else  
    echo "It can't, sorry."  
    case "$d_memmove" in  
    "$define") echo "But that's Ok since you have memmove()." ;;  
    esac  
  fi  
  else  
    echo "(I can't compile the test program, so we'll assume not...)"  
    case "$d_memmove" in  
    "$define") echo "But that's Ok since you have memmove()." ;;  
    esac  
  fi  
  ;;  
esac  
$rm -f foo.* safebcpy core  
set d_safebcpy  
eval $setvar
```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-  
debian-perl-5.26.1/dist/U/d_safebcpy.U
```

No license file was found, but licenses were detected in source scan.

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?MAKE:d_fegetround: Inlibc

?MAKE: -pick add \$@ %<

?S:d_fegetround:

?S: This variable conditionally defines HAS_FEGETROUND if fegetround() is

?S: available to get the floating point rounding mode.

?S:.

?C:HAS_FEGETROUND:

?C: This symbol, if defined, indicates that the fegetround routine is

?C: available to return the macro corresponding to the current rounding

?C: mode.

?C:.

?H:#\$d_fegetround HAS_FEGETROUND /**/

?H:.

?LINT:set d_fegetround

: see if fegetround exists

set fegetround d_fegetround

eval \$inlibc

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_fegetround.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 2000 Jarkko Hietaniemi

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?MAKE:d_isnanl: Inlibc

?MAKE: -pick add \$@ %<

?S:d_isnanl:

?S: This variable conditionally defines the HAS_ISNANL symbol, which

?S: indicates to the C program that the isnanl() routine is available.

?S:.

?C:HAS_ISNANL:

?C: This symbol, if defined, indicates that the isnanl routine is

?C: available to check whether a long double is a NaN.

?C:.

?H:#\$d_isnanl HAS_ISNANL /**/

?H:.

?LINT:set d_isnanl

: see if isnanl exists

set isnanl d_isnanl

eval \$inlibc

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_isnanl.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1999 Jarkko Hietaniemi

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?MAKE:d_sqrtl: Inlibc

?MAKE: -pick add \$@ %<

?S:d_sqrtl:

?S: This variable conditionally defines the HAS_SQRTL symbol, which

?S: indicates to the C program that the sqrtl() routine is available.

?S:.

?C:HAS_SQRTL:

?C: This symbol, if defined, indicates that the sqrtl routine is

?C: available to do long double square roots.

?C:.

?H:#\$d_sqrtl HAS_SQRTL /**/

?H:.

?LINT:set d_sqrtl

: see if sqrtl exists

set sqrtl d_sqrtl

eval \$inlibc

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_sqrtl.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_setgrent.U,v \$

?RCS:

?RCS: Copyright (c) 1998 Andy Dougherty

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?RCS: \$Log: d_setgrent.U,v \$

?RCS:

?MAKE:d_setgrent: Inlibc

?MAKE: -pick add \$@ %<

?S:d_setgrent:

?S: This variable conditionally defines the HAS_SETGRENT symbol, which

?S: indicates to the C program that the setgrent() routine is available

?S: for initializing sequential access to the group database.

?S:.

?C:HAS_SETGRENT:

?C: This symbol, if defined, indicates that the setgrent routine is

?C: available for initializing sequential access of the group database.

?C:.

?H:#\$d_setgrent HAS_SETGRENT /**/

?H:.

?LINT:set d_setgrent

: see if setgrent exists

set setgrent d_setgrent

eval \$inlibc

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/modified/d_setgrent.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_select.U 1 2006-08-24 12:32:52Z rmanfredi \$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic Licence,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic Licence; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: d_select.U,v \$

?RCS: Revision 3.0 1993/08/18 12:07:02 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?MAKE:d_select: Inlibc

?MAKE: -pick add \$@ %<

?S:d_select:

?S: This variable conditionally defines HAS_SELECT if select() is

?S: available to select active file descriptors. A <sys/time.h>

?S: inclusion may be necessary for the timeout field.

?S:.

?C:HAS_SELECT:

?C: This symbol, if defined, indicates that the select routine is

?C: available

to select active file descriptors. If the timeout field

?C: is used, <sys/time.h> may need to be included.

?C:.

?H:#\$d_select HAS_SELECT /**/

?H:.

```
?LINT:set d_select
: see if select exists
set select d_select
eval $inlibc
```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/d_select.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: d_getgrps.U 1 2006-08-24 12:32:52Z rmanfredi $
```

```
?RCS:
```

```
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
```

```
?RCS:
```

```
?RCS: You may redistribute only under the terms of the Artistic Licence,
```

```
?RCS: as specified in the README file that comes with the distribution.
```

```
?RCS: You may reuse parts of this distribution only within the terms of
```

```
?RCS: that same Artistic Licence; a copy of which may be found at the root
```

```
?RCS: of the source tree for dist 4.0.
```

```
?RCS:
```

```
?RCS: $Log: d_getgrps.U,v $
```

```
?RCS: Revision 3.0 1993/08/18 12:06:08 ram
```

```
?RCS: Baseline for dist 3.0 netwide release.
```

```
?RCS:
```

```
?MAKE:d_getgrps: Inlibc
```

```
?MAKE: -pick add $@ %<
```

```
?S:d_getgrps:
```

```
?S: This variable conditionally defines the HAS_GETGROUPS symbol, which
```

```
?S: indicates to the C program that the getgroups() routine is available
```

```
?S: to get the list of process groups.
```

```
?S:.
```

```
?C:HAS_GETGROUPS (GETGROUPS):
```

```
?C: This symbol, if defined, indicates that the getgroups()
```

```
routine is
```

```
?C: available to get the list of process groups. If unavailable, multiple
```

```
?C: groups are probably not supported.
```

```
?C:.
```

```
?H:#$d_getgrps HAS_GETGROUPS /**/
```

```
?H:.
```

```
?LINT:set d_getgrps
```

```
: see if getgroups exists
```

```
set getgroups d_getgrps
```

```
eval $inlibc
```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/d_getgrps.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: d_pause.U 1 2006-08-24 12:32:52Z rmanfredi $
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: Original Author: Andy Dougherty <doughera@lafcol.lafayette.edu>
?RCS:
?RCS: $Log: d_pause.U,v $
?RCS: Revision 3.0.1.1 1994/08/29 16:09:54 ram
?RCS: patch32: created by ADO
?RCS:
?MAKE:d_pause: Inlibc
?MAKE: -pick add $@ %<
?S:d_pause:
?S: This variable conditionally defines the HAS_PAUSE symbol, which
?S: indicates to the C program that the pause() routine is available
?S: to suspend a process until a signal is received.
?S:.
?C:HAS_PAUSE :
?C: This symbol,
if defined, indicates that the pause routine is
?C: available to suspend a process until a signal is received.
?C:.
?H:#$d_pause HAS_PAUSE /**/
?H:.
?LINT:set d_pause
: see if pause exists
set pause d_pause
eval $inlibc
```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/d_pause.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: us rinc.U,v 1.1 2000/06/27 00:20:28 jhi Exp $
?RCS:
?RCS: Copyright (c) 1991-1993, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
```

?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 3.0.
?RCS:
?RCS: \$Log: usrinc.U,v \$
?RCS: Revision 1.1 2000/06/27 00:20:28 jhi
?RCS: Initial revision
?RCS:
?RCS: Revision 3.0.1.3 1997/02/28 16:27:12 ram
?RCS: patch61: don't ask for the include path unless they are on a MIPS
?RCS:
?RCS: Revision 3.0.1.2 1995/05/12 12:24:36 ram
?RCS: patch54: ensure that ./mips always exists (ADO)
?RCS:
?RCS: Revision 3.0.1.1 1994/05/06 15:18:31 ram
?RCS: patch23: ensure usrinc value is preserved across sessions (WED)
?RCS:
?RCS: Revision
3.0 1993/08/18 12:09:58 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:usrinc incpath mips_type: test cat echo n c Getfile Guess \
Oldconfig eunicefix contains rm sysroot cc
?MAKE: -pick add \$@ %<
?S:usrinc:
?S: This variable holds the path of the include files, which is
?S: usually /usr/include. It is mainly used by other Configure units.
?S:.
?S:incpath:
?S: This variable must precede the normal include path to get the
?S: right one, as in "\$incpath/usr/include" or "\$incpath/usr/lib".
?S: Value can be "" or "/bsd43" on mips.
?S:.
?S:mips_type:
?S: This variable holds the environment type for the mips system.
?S: Possible values are "BSD 4.3" and "System V".
?S:.
?D:usrinc='/usr/include'
?LINT:extern cppflags
?LINT:create mips
?T:xxx_prompt
?F:./mips
: What should the include directory be ?
: Use sysroot if set, so findhdr looks in the right place.
echo " "
\$echo \$n "Hmm... \$c"
dflt="\$sysroot/usr/include"
incpath="

?X: mips_type is used later, to add -DSYSTYPE_BSD43

to cppflags if needed.

mips_type=""

?X:

?X: Cannot put the following in Guess, or we get a circular dependency.

?X:

```
if $test -f /bin/mips && /bin/mips; then
```

```
  echo "Looks like a MIPS system..."
```

```
  $cat >usr.c <<'EOCP'
```

```
#ifdef SYSTYPE_BSD43
```

```
/bsd43
```

```
#endif
```

```
EOCP
```

```
if $cc $cppflags -E usr.c > usr.out && $contains /usr.out >/dev/null 2>&1; then
```

```
  dflt='/bsd43/usr/include'
```

```
  incpath='/bsd43'
```

```
  mips_type='BSD 4.3'
```

```
else
```

```
  mips_type='System V'
```

```
fi
```

```
$rm -f usr.c usr.out
```

```
echo "and you're compiling with the $mips_type compiler and libraries."
```

```
xxx_prompt=y
```

```
echo "exit 0" >mips
```

```
else
```

```
  echo "Doesn't look like a MIPS system."
```

```
  xxx_prompt=n
```

```
  echo "exit 1" >mips
```

```
fi
```

```
chmod +x mips
```

```
$unicefix mips
```

```
case "$usrinc" in
```

```
) ;;
```

```
*) dflt="$usrinc";;
```

```
esac
```

```
case "$xxx_prompt" in
```

```
y) fn=d/
```

```
  echo " "
```

```
  rp='Where are the include files you want to use?'
```

```
  ./getfile
```

```
  usrinc="$ans"
```

```
  ;;
```

```
*) usrinc="$dflt"
```

```
  ;;
```

```
esac
```

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-

debian-perl-5.26.1/U/modified/usrinc.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_htonl.U 1 2006-08-24 12:32:52Z rmanfredi \$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: d_htonl.U,v \$

?RCS: Revision 3.0.1.2 1994/08/29 16:09:25 ram

?RCS: patch32: now properly handles htonl() and friends when macros (ADO)

?RCS:

?RCS: Revision 3.0.1.1 1994/05/06 14:45:00 ram

?RCS: patch23: now also check for htonl() macro (ADO)

?RCS:

?RCS: Revision 3.0 1993/08/18 12:06:22 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?MAKE:d_htonl: Inlibc Setvar i_niin i_sysin i_arpainet cat rm contains \
cppstdin cppflags cppminus

?MAKE: -pick

add \$@ %<

?S:d_htonl:

?S: This variable conditionally defines HAS_HTONL if htonl() and its

?S: friends are available to do network order byte swapping.

?S:.

?C:HAS_HTONL (HTONL):

?C: This symbol, if defined, indicates that the htonl() routine (and

?C: friends htons() ntohl() ntohs()) are available to do network

?C: order byte swapping.

?C:.

?C:HAS_HTONS (HTONS):

?C: This symbol, if defined, indicates that the htons() routine (and

?C: friends htonl() ntohl() ntohs()) are available to do network

?C: order byte swapping.

?C:.

?C:HAS_NTOHL (NTOHL):

?C: This symbol, if defined, indicates that the ntohl() routine (and

?C: friends htonl() htons() ntohs()) are available to do network

?C: order byte swapping.

?C:.

?C:HAS_NTOHS (NTOHS):

?C: This symbol, if defined, indicates that the ntohs() routine (and

?C: friends htonl() htons() ntohl() are available to do network

?C: order byte swapping.

?C:.

?H:#\$d_htonl HAS_HTONL /**/

?H:#\$d_htonl HAS_HTONS /**/

?H:#\$d_htonl HAS_NTOHL /**/

?H:#\$d_htonl

HAS_NTOHS /**/

?H:.

?F:!htonl.c

?LINT:set d_htonl

: see if htonl --and friends-- exists

val=""

set htonl val

eval \$inlibc

: Maybe they are macros.

case "\$val" in

\$undef)

\$cat >htonl.c <<EOM

#include <stdio.h>

#include <sys/types.h>

#\$i_niin I_NETINET_IN

#\$i_sysin I_SYS_IN

#\$i_arpainet I_ARPA_INET

#ifdef I_NETINET_IN

#include <netinet/in.h>

#endif

#ifdef I_SYS_IN

#include <sys/in.h>

#endif

#ifdef I_ARPA_INET

#include <arpa/inet.h>

#endif

#ifdef htonl

printf("Defined as a macro.");

#endif

EOM

\$cppstdin \$cppflags \$cppminus < htonl.c >htonl.E 2>/dev/null

if \$contains 'Defined as a macro' htonl.E >/dev/null 2>&1; then

val="\$define"

echo "But it seems to be defined as a macro." >&4

fi

\$rm -f htonl.?

::

esac

set d_htonl

eval \$setvar

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/modified/d_htonl.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: cf_name.U 1 2006-08-24 12:32:52Z rmanfredi $
```

```
?RCS:
```

```
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
```

```
?RCS:
```

```
?RCS: You may redistribute only under the terms of the Artistic Licence,
```

```
?RCS: as specified in the README file that comes with the distribution.
```

```
?RCS: You may reuse parts of this distribution only within the terms of
```

```
?RCS: that same Artistic Licence; a copy of which may be found at the root
```

```
?RCS: of the source tree for dist 4.0.
```

```
?RCS:
```

```
?RCS: Original Author: Graham Stoney <greyham@research.canon.oz.au>
```

```
?RCS:
```

```
?RCS: $Log: cf_name.U,v $
```

```
?RCS: Revision 3.0.1.2 1994/05/06 14:29:36 ram
```

```
?RCS: patch23: fixed user name computation from /etc/passwd in bsd systems
```

```
?RCS:
```

```
?RCS: Revision 3.0.1.1 1994/01/24 14:05:11 ram
```

```
?RCS: patch16: created
```

```
?RCS:
```

```
?RCS:
```

```
?MAKE:+cf_name: cf_by passcat Filexp nametype cat test
```

```
?MAKE: -pick add $@ %<
```

```
?S:cf_name:
```

```
?S: Full name of the person who ran the Configure script and  
answered the
```

```
?S: questions. This can be used by units that require the user's full name.
```

```
?S: This variable is for internal use only.
```

```
?S:.
```

```
?T:xxx fn NAME
```

```
: figure out their full name
```

```
case "$NAME" in
```

```
) case "$nametype" in
```

```
other)
```

```
fn=`./filexp ~/.fullname`
```

```
xxx=usg
```

```
$test -f $fn && xxx=other
```

```
::
```

```
*)
```

```
xxx="$nametype"
```

```
::
```

```
esac
```

```

case "$xxx" in
bsd)
cf_name=`$passcat | grep "^$cf_by:" | \
sed -e 's/^[^:]*:[^:]*:[^:]*:[^:]*:([^:]*):.*\1/' \
-e 's/,.*//'^
;;
usg)
cf_name=`$passcat | grep "^$cf_by:" | \
sed -e 's/^[^:]*:[^:]*:[^:]*:[^:]*:([^:]*):.*\1/' \
-e 's/[^-]*-\.(\.)*\1/'^
;;
*)
cf_name=`$cat $fn`
;;
esac
;;
*)
cf_name="$NAME"
;;
esac
?X:
?X: In the original unit, Graham asked for the user name, in case the above
?X: code was unable to figure it out correctly. Since now cf_name has been
?X: made an internal variable only (i.e. it is not saved in config.sh), letting
?X: the user override the computed default each time would be a pain.
?X:
?X: Therefore, I have decided to trust the above code to get it right, and for
?X: those rare cases where it will fail, too bad :-)--RAM.
?X:
echo " "
echo "Pleased to meet you, $cf_name."

```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/cf_name.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: d_popen.U 1 2006-08-24 12:32:52Z rmanfredi $
```

```
?RCS:
```

```
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
```

```
?RCS:
```

```
?RCS: You may redistribute only under the terms of the Artistic Licence,
```

```
?RCS: as specified in the README file that comes with the distribution.
```

```
?RCS: You may reuse parts of this distribution only within the terms of
```

```
?RCS: that same Artistic Licence; a copy of which may be found at the root
```

```
?RCS: of the source tree for dist 4.0.
```

```
?RCS:
```

```
?RCS: $Log: d_popen.U,v $
```

?RCS: Revision 3.0 1993/08/18 12:06:47 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:d_popen: Inlibc
?MAKE: -pick add \$@ %<
?S:d_popen:
?S: This variable conditionally defines HAS_POPEN if popen() is
?S: available to open a pipe from a process.
?S:.
?C:HAS_POPEN (POPEN):
?C: This symbol, if defined, indicates that the popen routine is
?C: available to open a pipe from a process.
?C:.
?H:#\$d_popen HAS_POPEN /**/
?H:.
?LINT:set
d_popen
: see if popen exists
set popen d_popen
eval \$inlibc

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/d_popen.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$
?RCS:
?RCS: Copyright (c) 1998 Jarkko Hietaniemi
?RCS:
?RCS: You may distribute under the terms of either the GNU General Public
?RCS: License or the Artistic License, as specified in the README file.
?RCS:
?MAKE:d_readv: Inlibc
?MAKE: -pick add \$@ %<
?S:d_readv:
?S: This variable conditionally defines the HAS_READV symbol, which
?S: indicates to the C program that the readv() routine is available.
?S:.
?C:HAS_READV:
?C: This symbol, if defined, indicates that the readv routine is
?C: available to do gather reads. You will also need <sys/uio.h>
?C: and there I_SYSUIO.
?C:.
?H:#\$d_readv HAS_READV /**/
?H:.
?LINT:set d_readv
: see if readv exists

```
set readv d_readv
eval $inlibc
```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/perl/d_readv.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: d_internet.U 1 2006-08-24 12:32:52Z rmanfredi $
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: $Log: d_internet.U,v $
?RCS: Revision 3.0.1.1 1993/09/13 16:02:04 ram
?RCS: patch10: most mailers support Internet addresses nowadays (WAD)
?RCS:
?RCS: Revision 3.0 1993/08/18 12:06:24 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:d_internet: Myread Oldconfig Setvar
?MAKE: -pick add $@ %<
?S:d_internet:
?S: This variable conditionally defines the INTERNET symbol, which
?S: indicates to the C program that there is a mailer available
?S: which
?S: supports internet-style addresses (user@site.domain).
?S:.
?C:INTERNET:
?C: This symbol, if defined, indicates that there is a mailer available
?C: which supports internet-style addresses (user@site.domain).
?C:.
?H:#$d_internet INTERNET /**/
?H:.
?LINT:set d_internet
: check for internet mailer
dflt=y
case "$d_internet" in
"$undef") dflt=n;;
esac
cat <<EOM
```

Most mailers can deliver mail to addresses of the INTERNET persuasion,

such as user@host.edu. Some older mailers, however, require the complete path to the destination to be specified in the address.

EOM

```
rp="Does your mailer understand INTERNET addresses?"
./myread
case "$ans" in
y*) val="$define";;
*) val="$undef";;
esac
set d_internet
eval $setvar
```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/d_internet.U
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: i_bfd.U,v \$

?RCS:

?RCS: Copyright (c) 2014 H.Merijn Brand

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?MAKE:i_bfd: Inhdr Hasfield

?MAKE:-pick add \$@ %<

?S:i_bfd:

?S: This variable conditionally defines the I_BFD symbol, and

?S: indicates whether a C program can include <bfd.h>.

?S:.

?C:I_BFD:

?C: This symbol, if defined, indicates that <bfd.h> exists and

?C: can be included.

?C:.

?H:#\$i_bfd I_BFD /**/

?H:.

?LINT:set i_bfd

: see if this is a bfd.h system

set bfd.h i_bfd

eval \$inhdr

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/i_bfd.U
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:
 ?RCS: Copyright (c) 2001 Jarkko Hietaniemi
 ?RCS:
 ?RCS: You may distribute under the terms of either the GNU General Public
 ?RCS: License or the Artistic License, as specified in the README file.
 ?RCS:
 ?MAKE:d_socketmark: Inlibc
 ?MAKE: -pick add \$@ %<
 ?S:d_socketmark:
 ?S: This variable conditionally defines the HAS_SOCKETMARK symbol, which
 ?S: indicates to the C program that the socketmark() routine is available.
 ?S:.
 ?C:HAS_SOCKETMARK:
 ?C: This symbol, if defined, indicates that the socketmark routine is
 ?C: available to test whether a socket is at the out-of-band mark.
 ?C:.
 ?H:#\$d_socketmark HAS_SOCKETMARK /**/
 ?H:.
 ?LINT:set d_socketmark
 : see if socketmark exists
 set socketmark d_socketmark
 eval \$inlibc

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_socketmark.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_getprotobyname_r.U,v 0RCS:
 ?RCS: Copyright (c) 2002,2003 Jarkko Hietaniemi
 ?RCS:
 ?RCS: You may distribute under the terms of either the GNU General Public
 ?RCS: License or the Artistic License, as specified in the README file.
 ?RCS:
 ?RCS: Generated by the reentr.pl from the Perl 5.8 distribution.
 ?RCS:
 ?MAKE:d_getprotobyname_r getprotobyname_r_proto: Inlibc Protochk Hasproto \
 i_systypes usethreads i_netdb extern_C
 ?MAKE: -pick add \$@ %<
 ?S:d_getprotobyname_r:
 ?S: This variable conditionally defines the HAS_GETPROTOBYNAME_R symbol,
 ?S: which indicates to the C program that the getprotobyname_r()
 ?S: routine is available.
 ?S:.
 ?S:getprotobyname_r_proto:
 ?S: This variable encodes the prototype of getprotobyname_r.
 ?S: It is zero if d_getprotobyname_r is undef, and one of the
 ?S: REENTRANT_PROTO_T_ABC macros of reentr.h if d_getprotobyname_r

```

?S: is defined.
?S:.
?C:HAS_GETPROTOBYNAME_R:
?C: This symbol, if
    defined, indicates that the getprotobyname_r routine
?C: is available to getprotobyname re-entrantly.
?C:.
?C:GETPROTOBYNAME_R_PROTO:
?C: This symbol encodes the prototype of getprotobyname_r.
?C: It is zero if d_getprotobyname_r is undef, and one of the
?C: REENTRANT_PROTO_T_ABC macros of reentr.h if d_getprotobyname_r
?C: is defined.
?C:.
?H:#$d_getprotobyname_r HAS_GETPROTOBYNAME_R  /**/
?H:#define GETPROTOBYNAME_R_PROTO $getprotobyname_r_proto  /**/
?H:.
?T:try hdrs d_getprotobyname_r_proto
: see if getprotobyname_r exists
set getprotobyname_r d_getprotobyname_r
eval $inlibc
case "$d_getprotobyname_r" in
"$define")
    hdrs="$i_systypes sys/types.h define stdio.h $i_netdb netdb.h"
    case "$d_getprotobyname_r_proto:$usethreads" in
":define") d_getprotobyname_r_proto=define
        set d_getprotobyname_r_proto getprotobyname_r $hdrs
        eval $hasproto ;;
*) ;;
esac
case "$d_getprotobyname_r_proto" in
define)
    case "$getprotobyname_r_proto" in
"|0) try='int getprotobyname_r(const char*,
struct protoent*, char*, size_t, struct protoent**);'
./protochk "$$extern_C $try" $hdrs && getprotobyname_r_proto=I_CSBWR ;;
esac
case "$getprotobyname_r_proto" in
"|0) try='struct protoent* getprotobyname_r(const char*, struct protoent*, char*, int);'
./protochk "$$extern_C $try" $hdrs && getprotobyname_r_proto=S_CSBI ;;
esac
case "$getprotobyname_r_proto" in
"|0) try='int getprotobyname_r(const char*, struct protoent*, struct protoent_data*);'
./protochk "$$extern_C $try" $hdrs && getprotobyname_r_proto=I_CSD ;;
esac
case "$getprotobyname_r_proto" in
"|0) d_getprotobyname_r=undef
    getprotobyname_r_proto=0
    echo "Disabling getprotobyname_r, cannot determine prototype." >&4 ;;

```

```

*) case "$getprotobyname_r_proto" in
REENTRANT_PROTO*) ;;
*) getprotobyname_r_proto="REENTRANT_PROTO_${getprotobyname_r_proto}" ;;
esac
echo "Prototype: $try" ;;
esac
;;
*) case "$susetthreads" in
define) echo "getprotobyname_r has no prototype, not using it." >&4 ;;
esac
d_getprotobyname_r=undef
getprotobyname_r_proto=0
;;
esac
;;
*) getprotobyname_r_proto=0
;;
esac

```

Found

in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/threads/d_getprotobyname_r.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: Extract.U,v \$

?RCS: Revision 3.0.1.2 1997/02/28 14:58:52 ram

?RCS: patch61: added support for src.U

?RCS:

?RCS: Revision 3.0.1.1 1994/10/29 15:51:46 ram

?RCS: patch36: added ?F: line for metalint file checking

?RCS:

?RCS: Revision 3.0 1993/08/18 12:04:52 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?X:

?X: This unit produces a shell script which can be doted in order to extract

?X: .SH files with variable substitutions.

?X:

?X: When running Configure from a remote directory (\$src is not '.'),

?X: then the files will be created in that directory, so beware!

?X:

?MAKE:Extract: Mkdirp src

?MAKE: -pick add \$@ %<

?F:./extract

?T:CONFIG SRC dir file

: script used to extract .SH files with variable substitutions

cat >extract <<EOS

CONFIG=true

SRC="\$src"

EOS

cat >>extract <<'EOS'

echo "Doing variable substitutions on .SH files..."

if test -f "\$SRC/MANIFEST"; then

set x `awk '{print \$1}' <\$SRC/MANIFEST | grep '\.SH`

else

echo "(Looking for .SH files under the source directory.)"

set x `(cd "\$SRC"; find . -name "*.SH" -print)`

fi

shift

case \$# in

0) set x `(cd "\$SRC"; echo *.SH)`; shift;;

esac

if test ! -f "\$SRC/\$1"; then

shift

fi

for file in \$*; do

case "\$SRC" in

".")

case "\$file" in

/)

dir=`expr X\$file : 'X\(.*)/'`

file=`expr X\$file : 'X.*\^(.*)'`

(cd \$dir && ./\$file)

;;

*)

./\$file

;;

esac

;;

*)

?X:

?X: When running Configure remotely (\$src is not '.'), we cannot source

?X: the files directly, since that would wrongly cause

the extraction

?X: where the source lie instead of withing the current directory. Therefore,

?X: we need to 'sh <file' then, which is okay since they will source the

?X: existing config.sh file. It's not possible to use:

?X: ../src/Configure -S -O -Dsomething

?X: unfortunately since no new config.sh with the -Dsomething override

?X: will be created before running the .SH files. A minor buglet.

?X:

?X: Note that we must create the directory hierarchy ourselves if it does

?X: not exist already, and that is done through a shell emulation of the

?X: 'mkdir -p' command. We don't want to use the \$installdir metaconfig

?X: symbol here since that would require too much to be configured for

?X: this simple extraction task that may happen quickly with 'Configure -S'.

?X: -- RAM, 18/03/96

?X:

```
case "$file" in
*)
  dir=`expr X$file : 'X\(.*)/'`
  file=`expr X$file : 'X.*\^(.*)'`
  ./mkdirp $dir
  sh <"$SRC/$dir/$file"
  ;;
*)
  sh <"$SRC/$file"
  ;;
esac
;;
esac
done
if
test -f "$SRC/config_h.SH"; then
if test ! -f config.h; then
?X: oops, they left it out of MANIFEST, probably, so do it anyway.
  sh <"$SRC/config_h.SH"
fi
fi
EOS
```

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/Extract.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_fork.U 1 2006-08-24 12:32:52Z rmanfredi \$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic Licence,

?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: Original Author: Andy Dougherty <doughera@lafcol.lafayette.edu>
?RCS:
?RCS: \$Log: d_fork.U,v \$
?RCS: Revision 3.0.1.1 1994/08/29 16:07:38 ram
?RCS: patch32: created by ADO
?RCS:
?MAKE:d_fork: Inlibc
?MAKE: -pick add \$@ %<
?S:d_fork:
?S: This variable conditionally defines the HAS_FORK symbol, which
?S: indicates to the C program that the fork() routine is available.
?S:.
?C:HAS_FORK :
?C: This symbol, if defined, indicates that the fork routine is
?C: available.
?C:.
?H:#\$d_fork
HAS_FORK /**/
?H:.
?LINT:set d_fork
: see if fork exists
set fork d_fork
eval \$inlibc

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/d_fork.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$
?RCS:
?RCS: Copyright (c) 1999 Jarkko Hietaniemi
?RCS:
?RCS: You may distribute under the terms of either the GNU General Public
?RCS: License or the Artistic License, as specified in the README file.
?RCS:
?MAKE:d_dirname_r: Inlibc
?MAKE: -pick add \$@ %<
?S:d_dirname_r:
?S: This variable conditionally defines the HAS_DIRNAME_R symbol,
?S: which indicates to the C program that the dirname_r()
?S: routine is available.
?S:.

?C:HAS_DIRNAME_R:

?C: This symbol, if defined, indicates that the dirname_r routine

?C: is available to dirname re-entrantly.

?C:.

?H:#\$d_dirname_r HAS_DIRNAME_R /**/

?H:.

?LINT:set d_dirname_r

: see if dirname_r exists

set dirname_r d_dirname_r

eval \$inlibc

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/threads/d_dirname_r.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_pread.U 1 2006-08-24 12:32:52Z rmanfredi \$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic Licence,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic Licence; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: d_pread.U,v \$

?RCS:

?MAKE:d_pread: Inlibc

?MAKE: -pick add \$@ %<

?S:d_pread:

?S: This variable conditionally defines the HAS_PREAD symbol, which

?S: indicates to the C program that the pread() routine is available.

?S:.

?C:HAS_PREAD :

?C: This symbol, if defined, indicates that the pread routine is

?C: available to perform reads on a file descriptor at a given offset.

?C:.

?H:#\$d_pread HAS_PREAD /**/

?H:.

?LINT:set d_pread

: see if pread exists

set

pread d_pread

eval \$inlibc

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-

debian-perl-5.26.1/dist/U/d_pread.U

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: d_waitpid.U 1 2006-08-24 12:32:52Z rmanfredi $
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: $Log: d_waitpid.U,v $
?RCS: Revision 3.0 1993/08/18 12:08:02 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:d_waitpid: Inlibc
?MAKE: -pick add $@ %<
?S:d_waitpid:
?S: This variable conditionally defines HAS_WAITPID if waitpid() is
?S: available to wait for child process.
?S:.
?C:HAS_WAITPID (WAITPID):
?C: This symbol, if defined, indicates that the waitpid routine is
?C: available to wait for child process.
?C:.
?H:#$d_waitpid HAS_WAITPID /**/
?H:.
?LINT:set
d_waitpid
: see if waitpid exists
set waitpid d_waitpid
eval $inlibc
```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/d_waitpid.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id$
?RCS:
?RCS: Copyright (c) 1996, Andy Dougherty
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
```

?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: \$Log: d_strtoul.U,v \$
?RCS: Revision 3.0.1.1 1997/02/28 15:46:43 ram
?RCS: patch61: created
?RCS:
?RCS:
?MAKE:d_strtoul: Inlibc
?MAKE: -pick add \$@ %<
?S:d_strtoul:
?S: This variable conditionally defines the HAS_STRTOUL symbol, which
?S: indicates to the C program that the strtoul() routine is available
?S: to provide conversion of strings to unsigned long.
?S:.
?C:HAS_STRTOUL (STRTOUL):
?C: This symbol, if defined, indicates that the strtoul routine is
?C: available
to provide conversion of strings to unsigned long.
?C:.
?H:#\$d_strtoul HAS_STRTOUL /**/
?H:.
?LINT:set d_strtoul
: see if strtoul exists
set strtoul d_strtoul
eval \$inlibc

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/d_strtoul.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: baserev.U 1 2006-08-24 12:32:52Z rmanfredi \$
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: \$Log: baserev.U,v \$
?RCS: Revision 3.0 1993/08/18 12:05:24 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:baserev: Null
?MAKE: -pick wipe \$@ %<

?S:baserev:

?S: The base revision level of this package, from the .package file.

?S:.

: set the base revision

baserev=<BASEREV>

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/baserev.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: mansrc.U 1 2006-08-24 12:32:52Z rmanfredi \$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic Licence,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic Licence; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: mansrc.U,v \$

?RCS: Revision 3.0.1.9 1997/02/28 16:12:03 ram

?RCS: patch61: don't ask for AFS when they choose to not install pages

?RCS:

?RCS: Revision 3.0.1.8 1995/09/25 09:16:58 ram

?RCS: patch59: unit is now forced to the top of Configure, if possible

?RCS:

?RCS: Revision 3.0.1.7 1995/02/15 14:15:31 ram

?RCS: patch51: was mistakenly duplicating /usr/local/man/man1 (ADO)

?RCS: patch51: added /opt/man/man1 to the lookpath (ADO)

?RCS:

?RCS: Revision

3.0.1.6 1995/01/30 14:39:34 ram

?RCS: patch49: can now handle installation prefix changes (from WED)

?RCS:

?RCS: Revision 3.0.1.5 1995/01/11 15:32:25 ram

?RCS: patch45: can now use Loc variables since path stripping is deferred

?RCS:

?RCS: Revision 3.0.1.4 1994/08/29 16:30:38 ram

?RCS: patch32: now uses installation prefix for default setting

?RCS:

?RCS: Revision 3.0.1.3 1994/05/06 15:11:10 ram

?RCS: patch23: added lint hint, assuring that nroff is used

?RCS:

?RCS: Revision 3.0.1.2 1994/01/24 14:14:39 ram

?RCS: patch16: now uses _nroff in case user asked for portability

?RCS:

```

?RCS: Revision 3.0.1.1 1993/09/13 16:09:31 ram
?RCS: patch10: allows for L1 man page extension (WAD)
?RCS:
?RCS: Revision 3.0 1993/08/18 12:09:14 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:mansrc mansrcexp manext installmansrc: afs cat nroff Loc Oldconfig \
sysman spackage test Getfile Prefixit prefixexp Prefixup
?MAKE: -pick add $@ %<
?Y:TOP
?S:mansrc:
?S: This variable
contains the name of the directory in which manual
?S: source pages are to be put. It is the responsibility of the
?S: Makefile.SH to get the value of this into the proper command.
?S: You must be prepared to do the ~name expansion yourself.
?S:.
?S:mansrcexp:
?S: This variable is the same as the mansrc variable, but is filename
?S: expanded at configuration time, for convenient use in makefiles.
?S:.
?S:installmansrc:
?S: This variable is really the same as mansrcexp, unless you are using
?S: AFS in which case it points to the read/write location whereas
?S: mansrcexp only points to the read-only access location. For extra
?S: portability, you should only use this variable within your makefiles.
?S:.
?S:manext:
?S: This variable contains the extension that the manual page should
?S: have: one of 'n', 'l', or '1'. The Makefile must supply the '.'.
?S: See mansrc.
?S:.
?T:lookpath
: determine where manual pages go
set mansrc mansrc none
eval $prefixit
$cat <<EOM

$package has manual
pages available in source form.
EOM
case "$nroff" in
nroff)
echo "However, you don't have nroff, so they're probably useless to you."
case "$mansrc" in
") mansrc="none";;
esac;;
esac

```

```

echo "If you don't want the manual sources installed, answer 'none'."
case "$mansrc" in
")
lookpath="$prefixexp/share/man/man1 $prefixexp/man/man1"
lookpath="$lookpath $prefixexp/man/u_man/man1 $prefixexp/man/l_man/man1"
lookpath="$lookpath /usr/local/man/man1 /opt/man/man1 /usr/man/man1"
lookpath="$lookpath /usr/share/man/man1 /usr/local/share/man/man1"
lookpath="$lookpath /usr/man/local/man1 /usr/man/l_man/man1"
lookpath="$lookpath /usr/local/man/u_man/man1 /usr/local/man/l_man/man1"
lookpath="$lookpath /usr/man/man.L"
mansrc=`./loc . $prefixexp/man/man1 $lookpath`
if $test -d "$mansrc"; then
dflt="$mansrc"
else
dflt="$sysman"
fi
set dflt
eval $prefixup
;;
') dflt=none;;
*) dflt="$mansrc"
;;
esac
echo " "
fn=dn~
rp='Where do the manual pages (source) go?'
./getfile
if test
"$X$mansrcexp" != "$X$ansexp"; then
installmansrc="
fi
mansrc="$ans"
mansrcexp="$ansexp"
case "$mansrc" in
") mansrc=' '
installmansrc="";;
esac
if $afs && $test "$mansrc"; then
$cat <<EOM

```

Since you are running AFS, I need to distinguish the directory in which manual pages reside from the directory in which they are installed (and from which they are presumably copied to the former directory by occult means).

```

EOM
case "$installmansrc" in
") dflt=`echo $mansrcexp | sed 's#^/afs/#/afs/#'`;;
*) dflt="$installmansrc";;

```

```
esac
fn=de~
rp='Where will man pages be installed?'
./getfile
installmansrc="$sans"
else
installmansrc="$mansrcexp"
fi
```

```
case "$mansrc" in
  '') manext='0';;
  *l) manext=l;;
  *n) manext=n;;
  *o) manext=l;;
  *p) manext=n;;
  *C) manext=C;;
  *L) manext=L;;
  *L1) manext=L1;;
  *) manext=l;;
esac
```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/mansrc.U
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: i_nlist.U,v \$

?RCS:

?RCS: Copyright (c) 1998 Jarkko Hietaniemi

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?MAKE:i_nlist: Inhdr Hasfield

?MAKE: -pick add \$@ %<

?S:i_nlist:

?S: This variable conditionally defines the I_NLIST symbol, and indicates

?S: whether a C program should include <nlist.h>.

?S:.

?C:I_NLIST:

?C: This symbol, if defined, indicates that <nlist.h> exists and

?C: should be included.

?C:.

?H:#\$i_nlist I_NLIST /**/

?H:.

?LINT:set i_nlist

: see if this is a nlist.h system

set nlist.h i_nlist

eval \$inhdr

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/i_nlist.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_shmctl.U 1 2006-08-24 12:32:52Z rmanfredi \$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic Licence,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic Licence; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: d_shmctl.U,v \$

?RCS: Revision 3.0 1993/08/18 12:07:18 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?MAKE:d_shmctl: Inlibc

?MAKE: -pick add \$@ %<

?S:d_shmctl:

?S: This variable conditionally defines the HAS_SHMCTL symbol, which

?S: indicates to the C program that the shmctl() routine is available.

?S:.

?C:HAS_SHMCTL:

?C: This symbol, if defined, indicates that the shmctl() routine is

?C: available to perform shared memory control operations.

?C:.

?H:#\$d_shmctl

HAS_SHMCTL /**/

?H:.

?LINT:set d_shmctl

: see if shmctl exists

set shmctl d_shmctl

eval \$inlibc

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/d_shmctl.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_mbstowcs.U 1 2006-08-24 12:32:52Z rmanfredi \$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: \$Log: d_mbstowcs.U,v \$
?RCS: Revision 3.0 1993/08/18 12:06:29 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:d_mbstowcs: Inlibc
?MAKE: -pick add \$@ %<
?S:d_mbstowcs:
?S: This variable conditionally defines the HAS_MBSTOWCS symbol, which
?S: indicates to the C program that the mbstowcs() routine is available
?S: to convert a multibyte string into a wide character string.
?S:.
?C:HAS_MBSTOWCS (MBSTOWCS):
?C: This symbol, if defined, indicates
that the mbstowcs routine is
?C: available to convert a multibyte string into a wide character string.
?C:.
?H:#\$d_mbstowcs HAS_MBSTOWCS /**/
?H:.
?LINT:set d_mbstowcs
: see if mbstowcs exists
set mbstowcs d_mbstowcs
eval \$inlibc

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/d_mbstowcs.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_ftrncate.U 1 2006-08-24 12:32:52Z rmanfredi \$
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: \$Log: d_ftrncate.U,v \$
?RCS: Revision 3.0 1993/08/18 12:06:07 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:

?MAKE:d_ftrncate: Inlibc
?MAKE: -pick add \$@ %<
?S:d_ftrncate (d_ftrncate):
?S: This variable conditionally defines the HAS_FTRUNCATE symbol, which
?S: indicates to the C program that the ftruncate() subroutine exists.
?S:.
?C:HAS_FTRUNCATE:
?C: This symbol, if defined, indicates that the ftruncate() subroutine
?C: exists.
?C:.
?H:#\$d_ftrncate
HAS_FTRUNCATE /**/
?H:.
?LINT:set d_ftrncate
: see if ftruncate exists
set ftruncate d_ftrncate
eval \$inlibc

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/d_ftrncate.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_lockf.U 1 2006-08-24 12:32:52Z rmanfredi \$
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: Original Author: Andy Dougherty <doughera@lafcol.lafayette.edu>
?RCS:
?RCS: \$Log: d_lockf.U,v \$
?RCS: Revision 3.0.1.1 1994/08/29 16:09:36 ram
?RCS: patch32: created by ADO
?RCS:
?MAKE:d_lockf: Inlibc
?MAKE: -pick add \$@ %<
?S:d_lockf:
?S: This variable conditionally defines HAS_LOCKF if lockf() is
?S: available to do file locking.
?S:.
?C:HAS_LOCKF (LOCKF):
?C: This symbol, if defined, indicates that the lockf routine is
?C: available to do file locking.

```
?C:
?H:#$d_lockf
HAS_LOCKF /**/
?H:
?LINT:set d_lockf
: see if lockf exists
set lockf d_lockf
eval $inlibc
```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/d_lockf.U
```

No license file was found, but licenses were detected in source scan.

```
/*
* $Id: getopt.C,v 3.0.1.1 1994/01/24 13:58:40 ram Exp ram $
*
* Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
*
* You may redistribute only under the terms of the Artistic Licence,
* as specified in the README file that comes with the distribution.
* You may reuse parts of this distribution only within the terms of
* that same Artistic Licence; a copy of which may be found at the root
* of the source tree for dist 4.0.
*
* Original Author: unknown, got this off net.sources
*
* $Log: getopt.C,v $
* Revision 3.0.1.1 1994/01/24 13:58:40 ram
* patch16: created
*
*/
```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/lib/C/fake/getopt.C
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id$
?RCS:
?RCS: Copyright (c) 1999 Jarkko Hietaniemi
?RCS:
?RCS: You may distribute under the terms of either the GNU General Public
?RCS: License or the Artistic License, as specified in the README file.
?RCS:
?MAKE:d_statfs_f_flags: \
Hasfield i_sysparam i_sysmount i_systypes \
i_sysvfs i_sysstatfs Setvar d_statfs_s
```

```

?MAKE: -pick add $@ %<
?S:d_statfs_f_flags:
?S: This variable conditionally defines the HAS_STRUCT_STATFS_F_FLAGS
?S: symbol, which indicates to struct statfs from has f_flags member.
?S: This kind of struct statfs is coming from sys/mount.h (BSD),
?S: not from sys/statfs.h (SYSV).
?S:.
?C:HAS_STRUCT_STATFS_F_FLAGS:
?C: This symbol, if defined, indicates that the struct statfs
?C: does have the f_flags member containing the mount flags of
?C: the filesystem containing the file.
?C: This kind of struct statfs is coming from <sys/mount.h> (BSD 4.3),
?C: not from <sys/statfs.h> (SYSV). Older BSDs
      (like Ultrix) do not
?C: have statfs() and struct statfs, they have ustat() and getmnt()
?C: with struct ustat and struct fs_data.
?C:.
?H:#$d_statfs_f_flags HAS_STRUCT_STATFS_F_FLAGS /**/
?H:.
?LINT:set d_statfs_f_flags
: see if struct statfs knows about f_flags
case "$d_statfs_s" in
define)
  echo " "
  echo "Checking to see if your struct statfs has f_flags field..." >&4
  set d_statfs_f_flags statfs f_flags $i_systypes sys/types.h $i_sysparam sys/param.h $i_sysmount sys/mount.h
  $i_sysvfs sys/vfs.h $i_sysstatfs sys/statfs.h
  eval $hasfield
  ;;
*) val="$undef"
  set d_statfs_f_flags
  eval $setvar
  ;;
esac
case "$d_statfs_f_flags" in
"$define") echo "Yes, it does." ;;
*) echo "No, it doesn't." ;;
esac

```

Found in path(s):

```

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/perl/d_statfs_f_flags.U

```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_gethostbyaddr_r.U,v 0RCS:

?RCS: Copyright (c) 2002,2003 Jarkko Hietaniemi

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?RCS: Generated by the reentr.pl from the Perl 5.8 distribution.

?RCS:

?MAKE:d_gethostbyaddr_r gethostbyaddr_r_proto: Inlibc Protochk Hasproto \
i_systypes usethreads i_netdb extern_C

?MAKE: -pick add \$@ %<

?S:d_gethostbyaddr_r:

?S: This variable conditionally defines the HAS_GETHOSTBYADDR_R symbol,
?S: which indicates to the C program that the gethostbyaddr_r()
?S: routine is available.

?S:.

?S:gethostbyaddr_r_proto:

?S: This variable encodes the prototype of gethostbyaddr_r.
?S: It is zero if d_gethostbyaddr_r is undef, and one of the
?S: REENTRANT_PROTO_T_ABC macros of reentr.h if d_gethostbyaddr_r
?S: is defined.

?S:.

?C:HAS_GETHOSTBYADDR_R:

?C: This symbol, if defined, indicates
that the gethostbyaddr_r routine
?C: is available to gethostbyaddr re-entrantly.

?C:.

?C:GETHOSTBYADDR_R_PROTO:

?C: This symbol encodes the prototype of gethostbyaddr_r.
?C: It is zero if d_gethostbyaddr_r is undef, and one of the
?C: REENTRANT_PROTO_T_ABC macros of reentr.h if d_gethostbyaddr_r
?C: is defined.

?C:.

?H:#\$d_gethostbyaddr_r HAS_GETHOSTBYADDR_R /**/
?H:#define GETHOSTBYADDR_R_PROTO \$gethostbyaddr_r_proto /**/
?H:.

?T:try hdrs d_gethostbyaddr_r_proto
: see if gethostbyaddr_r exists
set gethostbyaddr_r d_gethostbyaddr_r
eval \$inlibc
case "\$d_gethostbyaddr_r" in
"\$define")
hdrs="\$i_systypes sys/types.h define stdio.h \$i_netdb netdb.h"
case "\$d_gethostbyaddr_r_proto:\$usethreads" in
":define") d_gethostbyaddr_r_proto=define
set d_gethostbyaddr_r_proto gethostbyaddr_r \$hdrs
eval \$hasproto ;;
*) ;;
esac
case "\$d_gethostbyaddr_r_proto" in
define)
case "\$gethostbyaddr_r_proto" in

```

"|0) try='int gethostbyaddr_r(const char*, size_t, int, struct hostent*,
char*, size_t, struct hostent**, int*);'
./protochk "$extern_C $try" $hdrs && gethostbyaddr_r_proto=I_CWISBWRE ;;
esac
case "$gethostbyaddr_r_proto" in
"|0) try='struct hostent* gethostbyaddr_r(const char*, size_t, int, struct hostent*, char*, size_t, int, int*);'
./protochk "$extern_C $try" $hdrs && gethostbyaddr_r_proto=S_CWISBWIE ;;
esac
case "$gethostbyaddr_r_proto" in
"|0) try='struct hostent* gethostbyaddr_r(const char*, size_t, int, struct hostent*, char*, int, int*);'
./protochk "$extern_C $try" $hdrs && gethostbyaddr_r_proto=S_CWISBIE ;;
esac
case "$gethostbyaddr_r_proto" in
"|0) try='struct hostent* gethostbyaddr_r(const void*, size_t, int, struct hostent*, char*, int, int*);'
./protochk "$extern_C $try" $hdrs && gethostbyaddr_r_proto=S_TWISBIE ;;
esac
case "$gethostbyaddr_r_proto" in
"|0) try='struct hostent* gethostbyaddr_r(const char*, int, int, struct hostent*, char*, int, int*);'
./protochk "$extern_C $try" $hdrs && gethostbyaddr_r_proto=S_CIISBIE ;;
esac
case
"$gethostbyaddr_r_proto" in
"|0) try='struct hostent* gethostbyaddr_r(const char*, struct hostent*, char*, int, int*);'
./protochk "$extern_C $try" $hdrs && gethostbyaddr_r_proto=S_CSBIE ;;
esac
case "$gethostbyaddr_r_proto" in
"|0) try='struct hostent* gethostbyaddr_r(const void*, struct hostent*, char*, int, int*);'
./protochk "$extern_C $try" $hdrs && gethostbyaddr_r_proto=S_TSBIE ;;
esac
case "$gethostbyaddr_r_proto" in
"|0) try='int gethostbyaddr_r(const char*, size_t, int, struct hostent*, struct hostent_data*);'
./protochk "$extern_C $try" $hdrs && gethostbyaddr_r_proto=I_CWISD ;;
esac
case "$gethostbyaddr_r_proto" in
"|0) try='int gethostbyaddr_r(const char*, int, int, struct hostent*, struct hostent_data*);'
./protochk "$extern_C $try" $hdrs && gethostbyaddr_r_proto=I_CIISD ;;
esac
case "$gethostbyaddr_r_proto" in
"|0) try='int gethostbyaddr_r(const char*, int, int);'
./protochk "$extern_C $try" $hdrs && gethostbyaddr_r_proto=I_CII ;;
esac
case
"$gethostbyaddr_r_proto" in
"|0) try='int gethostbyaddr_r(const void*, socklen_t, int, struct hostent*, char*, size_t, struct hostent**, int*);'
./protochk "$extern_C $try" $hdrs && gethostbyaddr_r_proto=I_TsISBWRE ;;
esac
case "$gethostbyaddr_r_proto" in
"|0) d_gethostbyaddr_r=undef

```

```

    gethostbyaddr_r_proto=0
    echo "Disabling gethostbyaddr_r, cannot determine prototype." >&4 ;;
*) case "$gethostbyaddr_r_proto" in
    REENTRANT_PROTO*) ;;
*) gethostbyaddr_r_proto="REENTRANT_PROTO_$gethostbyaddr_r_proto" ;;
    esac
    echo "Prototype: $try" ;;
    esac
;;
*) case "$usetthreads" in
    define) echo "gethostbyaddr_r has no prototype, not using it." >&4 ;;
    esac
    d_gethostbyaddr_r=undef
    gethostbyaddr_r_proto=0
    ;;
    esac
;;
*) gethostbyaddr_r_proto=0
    ;;
    esac

```

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/threads/d_gethostbyaddr_r.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: yacc.U,v 3.0.1.1 1994/05/13 15:28:48 ram Exp \$

?RCS:

?RCS: Copyright (c) 1991-1993, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 3.0.

?RCS:

?RCS: \$Log: yacc.U,v \$

?RCS: Revision 3.0.1.1 1994/05/13 15:28:48 ram

?RCS: patch27: added yacc as another alternative (ADO)

?RCS:

?RCS: Revision 3.0 1993/08/18 12:10:03 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?MAKE:yacc yaccflags: Guess Myread Oldconfig yacc bison cat test _exe

?MAKE: -pick add \$@ %<

?S:yacc:

?S: This variable holds the name of the compiler compiler we

?S: want to use in the Makefile. It can be yacc, byacc, or bison -y.

```

?S:.
?S:yaccflags:
?S: This
    variable contains any additional yacc flags desired by the
?S: user. It is up to the Makefile to use this.
?S:.
?T:comp
: determine compiler compiler
case "$yacc" in
")
    dflt=yacc;;
*)
    dflt="$yacc";;
esac
echo " "
comp='yacc'
if $test -f "$byacc$_exe"; then
    dflt="$byacc"
    comp="byacc or $comp"
fi
if $test -f "$bison$_exe"; then
    comp="$comp or bison -y"
fi
rp="Which compiler compiler ($comp) shall I use?"
./myread
yacc="$ans"
case "$yacc" in
*bis*)
    case "$yacc" in
*_y*) ;;
*)
    yacc="$yacc -y"
    echo "(Adding -y option to bison to get yacc-compatible behavior.)"
    ;;
esac
;;
esac
;;
esac

@if yaccflags
: see if we need extra yacc flags
dflt="$yaccflags"
case "$dflt" in
") dflt=none;;
esac
$cat <<EOH

```

Your yacc program may need extra flags to normally process the parser sources.
Do NOT specify any -d or -v flags here, since those are explicitly known

by the various Makefiles. However, if your machine has strange/undocumented options (like -Sr# on SCO to specify the maximum number of grammar rules), then please add them here. To use no flags, specify the word "none".

EOH

```
rp="Any additional yacc flags?"
```

```
./myread
```

```
case "$ans" in
```

```
none) yaccflags="";;
```

```
*) yaccflags="$ans";;
```

```
esac
```

```
@end
```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/modified/yacc.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: Config_sh.U 1 2006-08-24 12:32:52Z rmanfredi $
```

```
?RCS:
```

```
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
```

```
?RCS:
```

```
?RCS: You may redistribute only under the terms of the Artistic License,
```

```
?RCS: as specified in the README file that comes with the distribution.
```

```
?RCS: You may reuse parts of this distribution only within the terms of
```

```
?RCS: that same Artistic License; a copy of which may be found at the root
```

```
?RCS: of the source tree for dist 4.0.
```

```
?RCS:
```

```
?RCS: $Log: Config_sh.U,v $
```

```
?RCS: Revision 3.0.1.3 1997/02/28 14:57:53 ram
```

```
?RCS: patch61: added support for src.U
```

```
?RCS:
```

```
?RCS: Revision 3.0.1.2 1995/01/11 14:53:31 ram
```

```
?RCS: patch45: moved path stripping from d_portable.U to end of Configure
```

```
?RCS:
```

```
?RCS: Revision 3.0.1.1 1994/10/29 15:50:37 ram
```

```
?RCS: patch36: added ?F: line for metalint file checking
```

```
?RCS:
```

```
?RCS: Revision 3.0 1993/08/18 12:04:48 ram
```

```
?RCS: Baseline for dist 3.0 netwide release.
```

```
?RCS:
```

```
?X:
```

```
?X:
```

This unit ends up producing the config.sh script, which contains all the

```
?X: definitions figured out by Configure. The add.Config_sh command knows
```

```
?X: which variables need to be remembered. It also adds the EOT (ends the
```

```

?X: here document redirection with variable substitution).
?X:
?MAKE:Config_sh: cf_time cf_by test spitshell startsh myuname Myread \
End Obsol_sh Loc +d_portable package src cat
?MAKE: -pick add.Config_sh $@ %<
?MAKE: -pick add $@ ./Obsol_sh
?MAKE: -pick close.Config_sh $@ %<
?F:!config.over !config.arch
?T:file temp
?LINT:unclosed EOT
: back to where it started
if test -d ../UU; then
  cd ..
fi

```

```

: configuration may be unconditionally patched via a 'config.arch' file
if $test -f config.arch; then
  echo "I see a config.arch file, loading it." >&4
  . ./config.arch
fi

```

```

: configuration may be patched via a 'config.over' file
if $test -f config.over; then
  echo " "
  dflt=y
  rp='I see a config.over file. Do you wish to load it?'
  . UU/myread
  case "$ans" in
  n*) echo
"OK, I'll ignore it.";;
*) . ./config.over
  echo "Configuration override changes have been loaded."
  ;;
  esac
fi

```

```

@if d_portable
: in case they want portability, strip down executable paths
?X:
?X: Strip down paths in located executables. For each file, e.g. vi, there
?X: is a $vi variable whose value is for instance '/usr/bin/vi'. By resetting
?X: $vi to 'vi', we rely on the PATH variable to locate the executable...
?X:
case "$d_portable" in
"$define")
  echo " "
  echo "Stripping down executable paths..." >&4
?X:

```

?X: Previously, we used to do `eval $file="\$file"` but in order
?X: to handle things like `sh Configure -Dmake=gmake`, we can't do
?X: that. What we *really* want is to strip away the absolute path
?X: and rely on the end user's `$PATH` to correctly find the executable.
?X: This method assumes there is a "basename" command available. If
?X: not, replace it with the following expr-based command:

```
?X: expr $temp : '.*\(.*\)' \| $temp
```

?X: Since this preserves the actual
command name, we can now drop the
?X: OS/2 specific code.

?X: --Andy Dougherty August 1999

?X:

?X: On OS/2, a special `$ar` command not even named 'ar' is required,
?X: so we don't strip that name.

?X: Also, on DOS-ish systems, there might not be a `ln` command, but we

?X: might have `ln='cp'`.

?X: However, we can't set `d_portable=undef` on such systems since

?X: Unix-ish tools don't have standard locations there. Thus we

?X: MUST rely on the user's `$PATH`.

?X: --Andy Dougherty 4/1998

?X:

```
for file in $loclist $trylist; do
    eval temp=\${$file}
    eval $file=`basename $temp`
done
;;
esac
```

@end

: create config.sh file

echo " "

echo "Creating config.sh..." >&4

\$spitshell <<EOT >config.sh

\$startsh

#

This file was produced by running the Configure script. It holds all the

definitions figured out by Configure. Should you modify one of these values,

do not forget to propagate your changes by running "Configure -der". You may

instead choose to run each of the .SH files by yourself, or "Configure

-S".

#

Package name : \$package

Source directory : \$src

Configuration time: \$cf_time

Configured by : \$cf_by

Target system : \$myuname

EOT

?X: Command line options are saved by the Options.U unit in the

?X: temporary file UU/cmdline.opt

: Add in command line options if available

\$test -f UU/cmdline.opt && \$cat UU/cmdline.opt >> config.sh

\$spitshell <<EOT >>config.sh

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/modified/Config_sh.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: i_string.U 1 2006-08-24 12:32:52Z rmanfredi \$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic Licence,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic Licence; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: i_string.U,v \$

?RCS: Revision 3.0.1.2 1993/10/16 13:50:12 ram

?RCS: patch12: special units Loc and Guess were missing from dependencies

?RCS:

?RCS: Revision 3.0.1.1 1993/09/13 16:07:26 ram

?RCS: patch10: removed "(Actually, this looks more like...)" messages (WAD)

?RCS:

?RCS: Revision 3.0 1993/08/18 12:08:28 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?X:

?X: See if we should include <string.h> or <strings.h>

?X:

?MAKE:i_string strings:

test Setvar Findhdr Warn

?MAKE: -pick add \$@ %<

?S:i_string:

?S: This variable conditionally defines the I_STRING symbol, which

?S: indicates that <string.h> should be included rather than <strings.h>.

?S:.

?S:strings:

?S: This variable holds the full path of the string header that will be

?S: used. Typically /usr/include/string.h or /usr/include/strings.h.

?S:.

?C:I_STRING:

?C: This symbol, if defined, indicates to the C program that it should
?C: include <string.h> (USG systems) instead of <strings.h> (BSD systems).

?C:.

?H:#\$i_string I_STRING /**/

?H:.

?LINT:set i_string

: see which of string.h or strings.h is needed

echo " "

strings=`./findhdr string.h`

if \$test "\$strings" && \$test -r "\$strings"; then

echo "Using <string.h> instead of <strings.h>." >&4

val="\$define"

else

val="\$undef"

strings=`./findhdr strings.h`

if \$test "\$strings" && \$test -r "\$strings"; then

echo "Using <strings.h> instead of <string.h>." >&4

else

./warn "No string header found -- You'll surely

have problems."

fi

fi

set i_string

eval \$setvar

case "\$i_string" in

"\$undef") strings=`./findhdr strings.h`;;

*) strings=`./findhdr string.h`;;

esac

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/i_string.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: filexp.U 1 2006-08-24 12:32:52Z rmanfredi \$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic Licence,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic Licence; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: filexp.U,v \$

?RCS: Revision 3.0 1993/08/18 12:08:08 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

```

?MAKE:filexp: privlib
?MAKE: -pick add $@ %<
?S:filexp:
?S: This symbol contains the full pathname of the filexp script, in case we
?S: are saving the script for posterity.
?S:.
: must not allow self reference
case "$privlib" in
/*)
filexp=$privlib/filexp
;;
*)
filexp=`pwd`/filexp
;;
esac

```

Found in path(s):

```

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/filexp.U

```

No license file was found, but licenses were detected in source scan.

```

?RCS: $Id$
?RCS:
?RCS: Copyright (c) 2014, H.Merijn Brand
?RCS:
?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: $Log: d_backtrace.U,v $
?RCS:
?MAKE:d_backtrace: Inlibc
?MAKE: -pick add $@ %<
?S:d_backtrace:
?S: This variable conditionally defines the HAS_BACKTRACE symbol, which
?S: indicates to the C program that the backtrace() routine is available
?S: to get a stack trace.
?S:.
?C:HAS_BACKTRACE:
?C: This symbol, if defined, indicates that the backtrace() routine is
?C: available to get a stack trace. The <execinfo.h> header must be
?C: included to use this routine.
?C:.
?H:#$d_backtrace HAS_BACKTRACE /**/
?H:.
?LINT:set d_backtrace

```

```
:
see if backtrace exists
set backtrace d_backtrace
eval $inlibc
```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/modified/d_backtrace.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: Configdir.U 1 2006-08-24 12:32:52Z rmanfredi $
```

```
?RCS:
```

```
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
```

```
?RCS:
```

```
?RCS: You may redistribute only under the terms of the Artistic Licence,
```

```
?RCS: as specified in the README file that comes with the distribution.
```

```
?RCS: You may reuse parts of this distribution only within the terms of
```

```
?RCS: that same Artistic Licence; a copy of which may be found at the root
```

```
?RCS: of the source tree for dist 4.0.
```

```
?RCS:
```

```
?RCS: $Log: Configdir.U,v $
```

```
?RCS: Revision 3.0.1.1 1997/02/28 14:58:36 ram
```

```
?RCS: patch61: have README explicitly mention the package name
```

```
?RCS:
```

```
?RCS: Revision 3.0 1993/08/18 12:04:49 ram
```

```
?RCS: Baseline for dist 3.0 netwide release.
```

```
?RCS:
```

```
?MAKE:Configdir: package
```

```
?MAKE: -pick add $@ %<
```

```
: create .config dir to save info across Configure sessions
```

```
test -d ../config || mkdir ../config
```

```
cat >../config/README <<EOF
```

```
This directory created by Configure to save
```

```
information that should
```

```
persist across sessions for $package.
```

```
You may safely delete it if you wish.
```

```
EOF
```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/Configdir.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: i_dlfcn.U 1 2006-08-24 12:32:52Z rmanfredi $
```

```
?RCS:
```

```
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
```

```
?RCS:
```

?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: Original Author: Andy Dougherty <doughera@lafcol.lafayette.edu>
?RCS:
?RCS: \$Log: i_dlfcn.U,v \$
?RCS: Revision 3.0.1.1 1994/08/29 16:21:53 ram
?RCS: patch32: created by ADO
?RCS:
?MAKE:i_dlfcn: Inhdr
?MAKE: -pick add \$@ %<
?S:i_dlfcn:
?S: This variable conditionally defines the I_DLFCN symbol, which
?S: indicates to the C program that <dlfcn.h> exists and should
?S: be included.
?S:.
?C:I_DLFCN:
?C: This symbol, if defined, indicates that <dlfcn.h> exists
and should
?C: be included.
?C:.
?H:#\$i_dlfcn I_DLFCN /**/
?H:.
?LINT:set i_dlfcn
: see if dlfcn is available
set dlfcn.h i_dlfcn
eval \$inhdr

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/i_dlfcn.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$
?RCS:
?RCS: Copyright (c) 1999, Jarkko Hietaniemi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 3.0.
?RCS:
?MAKE:d_nanosleep: Inlibc
?MAKE: -pick add \$@ %<

?S:d_nanosleep:
?S: This variable conditionally defines HAS_NANOSLEEP
?S: if nanosleep() is available to sleep with 1E-9 sec accuracy.
?S:.
?C:HAS_NANOSLEEP:
?C: This symbol, if defined, indicates that the nanosleep
?C: system call is available to sleep with 1E-9 sec accuracy.
?C:.
?H:#\$d_nanosleep HAS_NANOSLEEP /**/
?H:.
?LINT:set d_nanosleep
: see if nanosleep exists
set nanosleep d_nanosleep
eval \$inlibc

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_nanosleep.U

No license file was found, but licenses were detected in source scan.

?RCS:
?RCS: Copyright (c) 2012 Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?MAKE:ilp d_ilp32 d_ilp64 d_lp64 d_can64: Assert Myread Setvar \
cat rm +cc +ccflags echo n c intsize longsize ptrsize
?MAKE: -pick add \$@ %<
?S:ilp:
?S: This variable contains the largest amount of bits that the CPU supports,
?S: from the compiler's point of view. Typically 32 or 64.
?S:.
?S:d_ilp32:
?S: This variable conditionally defines the CPU_IS_ILP32.
?S:.
?S:d_ilp64:
?S: This variable conditionally defines the CPU_IS_ILP64.
?S:.
?S:d_lp64:
?S: This variable conditionally defines the CPU_IS_LP64.
?S:.
?S:d_can64:
?S: This variable

conditionally defines CAN_HANDLE_64BITS.

?S:.

?C:CPU_ILP_MAXBITS:

?C: This symbol contains the largest amount of bits that the CPU natively

?C: supports from the compiler's point of view. Typically 32 or 64.

?C:.

?C:CPU_IS_ILP32:

?C: When defined, this indicates that the integer, long and pointer variables

?C: hold 32-bit values.

?C:.

?C:CPU_IS_ILP64:

?C: When defined, this indicates that the integer, long and pointer variables

?C: hold 64-bit values.

?C:.

?C:CPU_IS_LP64:

?C: When defined, this indicates that the long and pointer variables hold

?C: 64-bit values but integers are smaller (probably only 32-bit wide).

?C:.

?C:CAN_HANDLE_64BITS:

?C: When defined, this indicates that the compiler can handle 64-bit values

?C: despite the CPU having only 32-bit registers. These are available using

?C: the "long long" C type. It is only defined for ILP32 machines, since

?C: 64-bit support is naturally available on ILP64 and LP64 machines.

?C:.

?H:#define CPU_ILP_MAXBITS \$ilp

?H:#\$d_ilp32

CPU_IS_ILP32 /**/

?H:#\$d_ilp64 CPU_IS_ILP64 /**/

?H:#\$d_lp64 CPU_IS_LP64 /**/

?H:#\$d_can64 CAN_HANDLE_64BITS /**/

?H:.

?LINT: set d_ilp32 d_ilp64 d_lp64 d_can64

: check for architecture type

echo " "

\$echo \$n "Computing CPU architecture type...\$c" >&4

ilp=`expr \$longsize * 8`

case "\$ptrsize" in

8)

val=\$undef; set d_ilp32; eval \$setvar

case "\$intsize" in

8)

echo " ILP64." >&4

val=\$define; set d_ilp64; eval \$setvar

val=\$undef; set d_lp64; eval \$setvar

::

*)

echo " LP64." >&4

val=\$define; set d_lp64; eval \$setvar

```

    val=$undef; set d_ilp64; eval $setvar
    ;;
esac
;;
*)
echo " ILP${ilp}." >&4
case "$ilp" in
32) val=$define;;
*) val=$undef;;
esac
set d_ilp32; eval $setvar
val=$undef; set d_ilp64; eval $setvar
val=$undef; set d_lp64; eval $setvar
;;
esac

@if CAN_HANDLE_64BITS || d_can64
: see whether compiler supports 64-bit emulation
val=$undef
case "$ilp" in
64) val=$define;;
*)
$cat >try.c <<EOCP
#include "static_assert.h"
long long foo;
int main()
{
    STATIC_ASSERT(8
    == sizeof(foo));
    return 0;
}
EOCP
if $cc -c $ccflags try.c >/dev/null 2>&1; then
    echo " "
    echo "Your compiler also supports 64-bit emulation." >&4
    val=$define
fi
$rm -f try.*
;;
esac
set d_can64
eval $setvar

@end

```

Found in path(s):

```

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/ilp.U

```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: vendorscript.U,v 1.1 1999/07/08 18:32:57 doughera Exp doughera \$
?RCS:
?RCS: Copyright (c) 1999, Andy Dougherty
?RCS:
?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 3.0.
?RCS:
?RCS: \$Log: vendorscript.U,v \$
?RCS: Revision 1.1 1999/07/08 18:32:57 doughera
?RCS: Initial revision
?RCS:
?MAKE:d_vendorscript vendorscript vendorscriptexp installvendorscript: Getfile \
vendorbin cat Setprefixvar Oldconfig Prefixit test vendorprefix
?MAKE: -pick add \$@ %<
?Y:TOP
?S:vendorscript:
?S: This variable contains the eventual value of the VENDORSRIPT symbol.
?S: It may have a ~ on the front.
?S: The standard distribution will put nothing in this
directory.
?S: Vendors who distribute perl may wish to place additional
?S: executable scripts in this directory with
?S: MakeMaker Makefile.PL INSTALLDIRS=vendor
?S: or equivalent. See INSTALL for details.
?S:.
?S:vendorscriptexp:
?S: This variable is the ~name expanded version of vendorscript, so that you
?S: may use it directly in Makefiles or shell scripts.
?S:.
?D:installvendorscript="
?S:installvendorscript:
?S: This variable is really the same as vendorscriptexp but may differ on
?S: those systems using AFS. For extra portability, only this variable
?S: should be used in makefiles.
?S:.
?S:d_vendorscript:
?S: This variable conditionally defines PERL_VENDORSRIPT.
?S:.
?C:PERL_VENDORSRIPT:
?C: If defined, this symbol contains the name of a directory
?C: for holding vendor-supplied executable scripts.
?C: It may have a ~ on the front.
?C: The standard distribution will put nothing in this directory.

```

?C: Vendors who distribute perl may wish to place additional
?C: executable
scripts in this directory with
?C: MakeMaker Makefile.PL INSTALLDIRS=vendor
?C: or equivalent. See INSTALL for details.
?C:.
?C:PERL_VENDORSCRIPT_EXP:
?C: This symbol contains the ~name expanded version of VENDORSCRIPT, to be used
?C: in programs that are not prepared to deal with ~ expansion at run-time.
?C:.
?H:#$d_vendorscript PERL_VENDORSCRIPT "$vendorscript" /**/
?H:#$d_vendorscript PERL_VENDORSCRIPT_EXP "$vendorscriptexp" /**/
?H:.
?LINT:change prefixvar
?LINT:set installvendorscript
: Set the vendorscript variables
case "$vendorprefix" in
") d_vendorscript="$undef"
vendorscript="
vendorscriptexp="
;;
*) d_vendorscript="$define"
: determine where vendor-supplied scripts go.
case "$vendorscript" in
") dflt=$vendorprefix/script
$test -d $dflt || dflt=$vendorbin ;;
*) dflt="$vendorscript" ;;
esac
$cat <<EOM

```

The installation process will create a directory for vendor-supplied scripts.

```

EOM
fn=d~+
rp='Pathname for the vendor-supplied scripts directory?'
./getfile
vendorscript="$ans"
vendorscriptexp="$ansexp"
;;
esac
prefixvar=vendorscript
./installprefix

```

Found in path(s):

```

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/installdirs/vendorscript.U

```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id$
?RCS:
?RCS: Copyright (c) 2000 Jarkko Hietaniemi
?RCS:
?RCS: You may distribute under the terms of either the GNU General Public
?RCS: License or the Artistic License, as specified in the README file.
?RCS:
?MAKE:d_unordered: Inlibc
?MAKE:-pick add $@ %<
?S:d_unordered:
?S: This variable conditionally defines the HAS_UNORDERED symbol, which
?S: indicates to the C program that the unordered() routine is available.
?S:.
?C:HAS_UNORDERED:
?C: This symbol, if defined, indicates that the unordered routine is
?C: available to check whether two doubles are unordered
?C: (effectively: whether either of them is NaN)
?C:.
?H:#$d_unordered HAS_UNORDERED /**/
?H:.
?LINT:set d_unordered
: see if unordered exists
set unordered d_unordered
eval $inlibc
```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/perl/d_unordered.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: d_getsrvby.U,v $
?RCS:
?RCS: Copyright (c) 1998 Andy Dougherty
?RCS:
?RCS: You may distribute under the terms of either the GNU General Public
?RCS: License or the Artistic License, as specified in the README file.
?RCS:
?MAKE:d_getsbyname d_getsbyport: Inlibc
?MAKE:-pick add $@ %<
?S:d_getsbyname:
?S: This variable conditionally defines the HAS_GETSERVBYNAME
?S: symbol, which indicates to the C program that the
?S: getservbyname() routine is available to look up services
?S: by their name.
?S:.
?S:d_getsbyport:
```

?S: This variable conditionally defines the HAS_GETSERVBYPOR

?S: symbol, which indicates to the C program that the

?S: getservbyport() routine is available to look up services

?S: by their port.

?S:.

?C:HAS_GETSERVBYNAM

?C: This symbol, if defined, indicates that the getservbyname()

?C: routine is available to look up services by their name.

?C:.

?C:HAS_GETSERVBYPOR

?C: This symbol, if defined,

indicates that the getservbyport()

?C: routine is available to look up services by their port.

?C:.

?H:#\$d_getsbyname HAS_GETSERVBYNAM /**/

?H:#\$d_getsbyport HAS_GETSERVBYPOR /**/

?H:.

?LINT:set d_getsbyname d_getsbyport

: Optional checks for getsbyname and getsbyport

@if d_getsbyname || HAS_GETSERVBYNAM

: see if getservbyname exists

set getservbyname d_getsbyname

eval \$inlibc

@end

@if d_getsbyport || HAS_GETSERVBYPOR

: see if getservbyport exists

set getservbyport d_getsbyport

eval \$inlibc

@end

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/modified/d_getsrby.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: i_libutil.U,v \$

?RCS:

?RCS: Copyright (c) 2000 Jarkko Hietaniemi

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?MAKE:i_libutil: Inhdr Hasfield

?MAKE: -pick add \$@ %<

?S:i_libutil:

?S: This variable conditionally defines the I_LIBUTIL symbol, and indicates

?S: whether a C program should include <libutil.h>.

?S:.

?C:I_LIBUTIL:

?C: This symbol, if defined, indicates that <libutil.h> exists and

?C: should be included.

?C:.

?H:#\$i_libutil I_LIBUTIL /**/

?H:.

?LINT:set i_libutil

: see if this is a libutil.h system

set libutil.h i_libutil

eval \$inhdr

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/i_libutil.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_strtok.U 1 2006-08-24 12:32:52Z rmanfredi \$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic Licence,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic Licence; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: d_strtok.U,v \$

?RCS: Revision 3.0 1993/08/18 12:07:38 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?X:

?X: The strtok routine now appears to be a standard one, but it was

?X: missing in early BSD systems.

?X:

?MAKE:d_strtok: Inlibc

?MAKE: -pick add \$@ %<

?S:d_strtok:

?S: This variable conditionally defines HAS_STRTOK if strtok() is

?S: available to scan strings for tokens.

?S:.

?C:HAS_STRTOK (STRTOK):

?C: This symbol, if defined, indicates

that the strtok routine is

?C: available to scan strings for tokens.

?C:.

?H:#\$d_strtok HAS_STRTOK /**/

```
?H:
?LINT:set d_strtok
: see if strtok exists
set strtok d_strtok
eval $inlibc
```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/d_strtok.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id$
```

```
?RCS:
```

```
?RCS: Copyright (c) 1999, Jarkko Hietaniemi
```

```
?RCS:
```

```
?RCS: You may redistribute only under the terms of the Artistic License,
```

```
?RCS: as specified in the README file that comes with the distribution.
```

```
?RCS: You may reuse parts of this distribution only within the terms of
```

```
?RCS: that same Artistic License; a copy of which may be found at the root
```

```
?RCS: of the source tree for dist 3.0.
```

```
?RCS:
```

```
?MAKE:d_mq_getattr: Inlibc
```

```
?MAKE:-pick add $@ %<
```

```
?S:d_mq_getattr:
```

```
?S: This variable conditionally defines HAS_MQ_GETATTR if mq_getattr() is
```

```
?S: available to get the attributes and status of a POSIX message queue.
```

```
?S:.
```

```
?C:HAS_MQ_GETATTR:
```

```
?C: This symbol, if defined, indicates that the mq_getattr system call is
```

```
?C: available to get the attributes and status of a POSIX message queue.
```

```
?C:.
```

```
?H:#$d_mq_getattr HAS_MQ_GETATTR /**/
```

```
?H:
```

```
?LINT:set d_mq_getattr
```

```
: see if mq_getattr exists
```

```
set mq_getattr d_mq_getattr
```

```
eval $inlibc
```

Found

in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/perl/d_mq_getattr.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id$
```

```
?RCS:
```

```
?RCS: Copyright (c) 1999, Jarkko Hietaniemi
```

```
?RCS:
```

```

?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 3.0.
?RCS:
?MAKE:d_posix_clock: Setvar d_clock_getres d_clock_gettime d_clock_settime i_time
?MAKE: -pick add $@ %<
?S:d_posix_clock:
?S: This variable conditionally defines the HAS_POSIX_CLOCK symbol, which
?S: indicates that the entire POSIX clock_*(2) library is present.
?S:.
?C:HAS_POSIX_CLOCK:
?C: This symbol, if defined, indicates that the entire POSIX clock_*(2)
?C: library is supported.
?C:.
?H:#$d_posix_clock HAS_POSIX_CLOCK /**/
?H:.
?LINT:set d_posix_clock
: see how much of the 'POSIX clock_*(2)' library is present.
echo
" "
case "$i_time$d_clock_getres$d_clock_gettime$d_clock_settime" in
*$undef*) val="$undef" ;;
*) val="$define" ;;
esac
case "$val" in
"$define") echo "You have the full POSIX clock_*(2) library." >&4 ;;
"$undef") echo "You don't have the full POSIX clock_*(2) library." >&4 ;;
esac
set d_posix_clock
eval $setvar

```

Found in path(s):

```

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/perl/d_posix_clock.U

```

No license file was found, but licenses were detected in source scan.

```

?RCS: $Id: usethreads.U,v $
?RCS:
?RCS: Copyright (c) 1998-2000 Andy Dougherty
?RCS:
?RCS: You may distribute under the terms of either the GNU General Public
?RCS: License or the Artistic License, as specified in the README file.
?RCS:
?RCS: $Log: usethreads.U,v $
?RCS:
?MAKE:usethreads useithreads use5005threads d_oldpthreads useentrant: \

```

Myread Oldconfig Setvar test cat patchlevel
?MAKE: -pick add \$@ %<
?Y:TOP
?S:usethreads:
?S: This variable conditionally defines the USE_THREADS symbol,
?S: and indicates that Perl should be built to use threads.
?S:.
?S:useithreads:
?S: This variable conditionally defines the USE_ITHREADS symbol,
?S: and indicates that Perl should be built to use the interpreter-based
?S: threading implementation.
?S:.
?S:use5005threads:
?S: This variable conditionally defines the USE_5005THREADS symbol,
?S: and indicates that Perl should be built to use the 5.005-based
?S: threading implementation.
Only valid up to 5.8.x.
?S:.
?X: I'm putting old_pthreads in this unit because it might eventually
?X: be part of an automatic determination to see if we can use threads
?X: at all.
?S:d_oldpthreads:
?S: This variable conditionally defines the OLD_PTHREADS_API symbol,
?S: and indicates that Perl should be built to use the old
?S: draft POSIX threads API. This is only potentially meaningful if
?S: usethreads is set.
?S:.
?S:usereentrant:
?S: This variable conditionally defines the USE_REENTRANT_API symbol,
?S: which indicates that the thread code may try to use the various
?S: _r versions of library functions. This is only potentially
?S: meaningful if usethreads is set and is very experimental, it is
?S: not even prompted for.
?S:.
?C:USE_ITHREADS:
?C: This symbol, if defined, indicates that Perl should be built to
?C: use the interpreter-based threading implementation.
?C:.
?C:USE_5005THREADS:
?C: This symbol, if defined, indicates that Perl should be built to
?C: use the 5.005-based
?C: threading implementation.
?C: Only valid up to 5.8.x.
?C:.
?C:USE_THREADS:
?C: This symbol, if defined, indicates that Perl should
?C: be built to use threads. At present, it is a synonym for
?C: USE_5005THREADS for perl older than 5.8 and USE_ITHREADS

?C: for 5.8.x and newer, but eventually the source ought to be
?C: changed to use this to mean `_any_` threading implementation.
?C:.
?C:OLD_PTHREADS_API:
?C: This symbol, if defined, indicates that Perl should
?C: be built to use the old draft POSIX threads API.
?C:.
?C:USE_REENTRANT_API:
?C: This symbol, if defined, indicates that Perl should
?C: try to use the various `_r` versions of library functions.
?C: This is extremely experimental.
?C:.
?H:#\$use5005threads USE_5005THREADS /**/
?H:#\$useithreads USE_ITHREADS /**/
?H:?%<:#if defined(USE_5005THREADS) && !defined(USE_ITHREADS)
?H:?%<:#define USE_THREADS /* until src is revised*/
?H:?%<:#endif
?H:#\$d_oldpthreads OLD_PTHREADS_API /**/
?H:#\$usereentrant USE_REENTRANT_API /**/
?H:.
?X:
[hmb] Removed LINT for use5005threads, useithreads, and
?X: useereentrant, as LINT is only run on bleed
?LINT:set usethreads d_oldpthreads
?INIT:: set usethreads on the Configure command line to enable threads.
?INIT:usereentrant='undef'
?F:!usethreads.cbu
: Do we want threads support and if so, what type
?X: We should really have some explanatory text here, and some
?X: automatic setting of sensible defaults.
case "\$usethreads" in
\$define|true|[yY]*) dflt='y';;
*) # Catch case where user specified ithreads or 5005threads but
forgot -Dusethreads (A.D. 4/2002)
case "\$useithreads\$use5005threads" in
\$define) dflt='y';;
*) dflt='n';;
esac
;;
esac
cat <<EOM

Perl can be built to offer a form of threading support on some systems
To do so, Configure can be run with `-Dusethreads`.

Note that Perl built with threading support runs slightly slower
and uses slightly more memory than plain Perl.

```

If this doesn't make
any sense to you, just accept the default '$dflt'.
EOM
rp='Build a threading Perl?'
./myread
case "$ans" in
y|Y)  val="$define" ;;
*)    val="$undef" ;;
esac
set usethreads
eval $setvar

if $test $patchlevel -lt 9; then
  case "$usethreads" in
    $define)
      : Default to ithreads unless overridden on command line or with
      : old config.sh
      dflt='y'
    case "$use5005threads" in
      $define|true|[yY]*)
        echo "5.005 threads are no longer supported"
        exit 1
      ;;
    esac
    case "$useithreads" in
      $undef|false|[nN]*) dflt='n';;
    esac
    rp='Use the newer interpreter-based ithreads?'
    ./myread
    case "$ans" in
    y|Y)  val="$define" ;;
    *)    val="$undef" ;;
    esac
    set useithreads
    eval $setvar
    : Now set use5005threads to the opposite value.
    case "$useithreads" in
      $define) val="$undef" ;;
      *) val="$define" ;;
    esac
    set use5005threads
    eval $setvar
    ;;
    *)
    useithreads="$undef"
    use5005threads="$undef"
    ;;
  esac

```

?X: This is not supposed to be possible but with some trickery, maybe.

```
case "$useithreads$use5005threads" in
"$define$define")
$cat >&4 <<EOM
```

You cannot have both the itreads and the 5.005 threads enabled at the same time. Disabling the 5.005 threads since they are much less stable than the itreads.

EOM

```
use5005threads="$undef"
;;
esac
```

else

: perl-5.9.x and later

```
if test X"$usetreads" = "X$define"; then
case "$use5005threads" in
$define|true|[yY]*)
$cat >&4 <<EOM
```

5.005 threads has been removed for 5.10. Perl will be built using itreads.

EOM

```
;;
esac
fi
```

```
use5005threads="$undef"
useithreads="$usetreads"
fi
```

?X: Check out what kind of threads API we have

```
case "$d_oldpthreads" in
") : Configure tests would be welcome here. For now, assume undef.
val="$undef" ;;
*) val="$d_oldpthreads" ;;
esac
set d_oldpthreads
eval $setvar
```

?X: In general, -lptread needs to come before -lc but after other

?X: libraries such as -lgdbm and such like. We assume here that -lc

?X: is present in libswanted. If that

fails to be true, then this

?X: can be changed to add pthread to the very end of libswanted.

: Look for a hint-file generated 'call-back-unit'. If the

: user has specified that a threading perl is to be built,

: we may need to set or change some other defaults.

if \$test -f usethreads.cbu; then

 echo "Your platform has some specific hints regarding threaded builds, using them..."

 ./usethreads.cbu

else

 case "\$usethreads" in

 "\$define"|true|[yY]*)

 \$cat <<EOM

(Your platform does not have any specific hints for threaded builds.

Assuming POSIX threads, then.)

EOM

;;

 esac

fi

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/threads/usethreads.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1999 Jarkko Hietaniemi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 3.0.

?RCS:

?MAKE:siteman3dir siteman3direxp installsiteman3dir: Getfile \

Setprefixvar prefix siteprefix man3dir sed

?MAKE: -pick add \$@ %<

?Y:TOP

?D:siteman3dir="

?S:siteman3dir:

?S: This variable contains the name of the directory in which site-specific

?S: library man source pages are to be put. It is the responsibility of the

?S: Makefile.SH to get the value of this into the proper command.

?S: You must be prepared to do the ~name expansion yourself.

?S: The standard distribution will put nothing in this directory.

?S: After

perl has been installed, users may install their own local
 ?S: man3 pages in this directory with
 ?S: MakeMaker Makefile.PL
 ?S: or equivalent. See INSTALL for details.
 ?S:.
 ?D:siteman3direxp="
 ?S:siteman3direxp:
 ?S: This variable is the same as the siteman3dir variable, but is filename
 ?S: expanded at configuration time, for convenient use in makefiles.
 ?S:.
 ?D:installsiteman3dir="
 ?S:installsiteman3dir:
 ?S: This variable is really the same as siteman3direxp, unless you are using
 ?S: AFS in which case it points to the read/write location whereas
 ?S: man3direxp only points to the read-only access location. For extra
 ?S: portability, you should only use this variable within your makefiles.
 ?S:.
 ?LINT:change prefixvar
 ?LINT:set installsiteman3dir
 ?LINT:set siteman3dir
 ?LINT:set siteman3direxp
 : determine where add-on library man pages go
 case "\$siteman3dir" in
 ") dflt=`echo \$man3dir | \$sed "s#^\$prefix#\$siteprefix#"` ;;
 *) dflt=\$siteman3dir ;;
 esac
 case "\$dflt" in
 "| ") dflt=none ;;
 esac
 fn=dn+~
 rp='Pathname
 where the site-specific library manual pages should be installed?'
 ./getfile
 prefixvar=siteman3dir
 ./setprefixvar

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/installdirs/siteman3dir.U

No license file was found, but licenses were detected in source scan.

?RCS:

?RCS: Copyright (c) 1999, Jarkko Hietaniemi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 3.0.
?RCS:
?MAKE:d_memchr: Inlibc
?MAKE: -pick add \$@ %<
?S:d_memchr:
?S: This variable conditionally defines the HAS_MEMCHR symbol, which
?S: indicates to the C program that the memchr() routine is available
?S: to locate characters within a C string.
?S:.
?C:HAS_MEMCHR:
?C: This symbol, if defined, indicates that the memchr routine is available
?C: to locate characters within a C string.
?C:.
?H:#\$d_memchr HAS_MEMCHR /**/
?H:.
?LINT:set d_memchr
: see if memchr exists
set memchr d_memchr
eval \$inlibc

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/modified/d_memchr.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$
?RCS:
?RCS: Copyright (c) 1999, Jarkko Hietaniemi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 3.0.
?RCS:
?MAKE:d_sched_rr_get_interval: Inlibc
?MAKE: -pick add \$@ %<
?S:d_sched_rr_get_interval:
?S: This variable conditionally defines HAS_SCHED_RR_GET_INTERVAL if
?S: sched_rr_get_interval() is available to get the time quantum
?S: of the round robin scheduling.
?S:.
?C:HAS_SCHED_RR_GET_INTERVAL:
?C: This symbol, if defined, indicates that the sched_rr_get_interval
?C: system call is available to get the time quantum
?C: of the round robin scheduling.
?C:.
?H:#\$d_sched_rr_get_interval HAS_SCHED_RR_GET_INTERVAL /**/

?H:
?LINT:set
d_sched_rr_get_interval
: see if sched_rr_get_interval exists
set sched_rr_get_interval d_sched_rr_get_interval
eval \$inlibc

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_sched_rrgi.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: charorder.U,v \$

?RCS: Revision 3.0.1.1 1994/10/29 16:07:08 ram

?RCS: patch36: added ?F: line for metalint file checking

?RCS:

?RCS: Revision 3.0 1993/08/18 12:05:33 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?MAKE:chorder_int chorder_short chorder_long: Myread cat +cc +ccflags rm

?MAKE: -pick add \$@ %<

?S:chorder_short (d_cos d_bos):

?S: Holds the value describing the byte ordering of characters in a short.

?S: On a Big-Endian machine, that would be "c0c1".

?S:.

?S:chorder_int

(charoder):

?S: Holds the value describing the byte ordering of characters in an int.

?S: For instance, on a Big-Endian machine, this would be: "c0c1c2c3".

?S:.

?S:chorder_long (d_col d_bol):

?S: Holds the value describing the byte ordering of characters in a long.

?S: On a 64 bits Big-Endian machine, that would yield: "c0c1c2c3c4c5c6c7".

?S:.

?C:CHAR_ORDER_SHORT:

?C: Holds the byte ordering of characters in a short. It's a string

?C: value like "c0c1" on a Big-Endian machine.

?C:.

?C:CHAR_ORDER_INT:

?C: Holds the byte ordering of characters in an int. It's a string

?C: value like "c0c1c2c3" on a Big-Endian machine.

?C:.

?C:CHAR_ORDER_LONG:

?C: Holds the byte ordering of characters in a long. It's a string

?C: value like "c0c1c2c3c4c5c6c7" on a 64 bits Big-Endian machine.

?C:.

?H:#define CHAR_ORDER_SHORT "\$chorder_short" /* byte order in a short */

?H:#define CHAR_ORDER_INT "\$chorder_int" /* byte order in an int */

?H:#define CHAR_ORDER_LONG "\$chorder_long" /* byte order in a long */

?H:.

?F:!byteorder

:

check for character ordering

echo " "

echo "Checking out byte order..." >&4

\$cat >byteorder.c <<'EOCP'

#include <stdio.h>

main(argc, argv)

int argc;

char *argv[]; {

int i;

int max;

union {

short u_s;

int u_i;

long u_l;

char u_c[sizeof(long)];

} u;

switch (argv[1][0]) {

case 'l':

u.u_l = 0L;

/* HMS: ASSERT: sizeof(long) < 10. */

for(i = 0; i < sizeof(long); ++i) {

u.u_l *= 0x100L;

u.u_l += (0xc0 + i);

}

max = sizeof(long);

break;

case 's':

u.u_s = 0;

/* HMS: ASSERT: sizeof(short) < 10. */

for(i = 0; i < sizeof(short); ++i) {

u.u_s *= 0x100L;

u.u_s += (0xc0 + i);

}

```

max = sizeof(short);
break;
case 'i':
u.u_i = 0;
/* RAM: ASSERT: sizeof(int) < 10. */
for(i = 0; i < sizeof(int); ++i) {
u.u_1 *= 0x100L;
u.u_1 += (0xc0 + i);
}
max = sizeof(int);
break;
default:
max = 0;
break;
}
for(i = 0; i < max; i++) {
printf("%x", u.u_c[i] & 0x00FF);
}
printf("\n");
exit(0);
}
EOCP
if $cc $ccflags -o
byteorder byteorder.c >/dev/null 2>&1 ; then
: null statement
@if chorder_short
chorder_short=`./byteorder s`
@end
@if chorder_int
chorder_int=`./byteorder i`
@end
@if chorder_long
chorder_long=`./byteorder l`
@end
else
$cat <<EOM
(I can't seem to get my test program to work. Guessing 32 bits big-endian.)
EOM
chorder_short="c0c1"
chorder_int="c0c1c2c3"
chorder_long="c0c1c2c3"
fi
@if chorder_short
dflt=$chorder_short
rp="What is the order of characters in a short?"
./myread
chorder_short="$ans"
@end

```

```

@if chorder_int
dflt=$chorder_int
rp='What is the order of characters in an int?'
./myread
chorder_int="$ans"
@end
@if chorder_long
dflt=$chorder_long
rp='What is the order of characters in a long?'
./myread
chorder_long="$ans"
@end
$rm -f byteorder* core

```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/charorder.U
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: Original Author: Andy Dougherty <doughera@lafcol.lafayette.edu>

?RCS:

?RCS: \$Log: sizetype.U,v \$

?RCS: Revision 3.0.1.1 1994/08/29 16:32:10 ram

?RCS: patch32: created by ADO

?RCS:

?MAKE:sizetype: Myread Typedef

?MAKE: -pick add \$@ %<

?S:sizetype:

?S: This variable defines sizetype to be something like size_t,

?S: unsigned long, or whatever type is used to declare length

?S: parameters for string functions.

?S:.

?C:Size_t:

?C: This symbol holds the type used to declare length parameters

?C: for string

functions. It is usually size_t, but may be

?C: unsigned long, int, etc. It may be necessary to include

?C: <sys/types.h> to get any typedef'ed information.

```

?C:.
?H:#define Size_t $sizetype /* length paramater for string functions */
?H:.
: see what type is used for size_t
set size_t sizetype 'unsigned int' stdio.h sys/types.h
eval $stypedef
dflt="$sizetype"
echo " "
rp="What type is used for the length parameter for string functions?"
./myread
sizetype="$ans"

```

Found in path(s):

```

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/sizetype.U

```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_gethostbyname_r.U,v 0RCS:

?RCS: Copyright (c) 2002,2003 Jarkko Hietaniemi

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?RCS: Generated by the reentr.pl from the Perl 5.8 distribution.

?RCS:

?MAKE:d_gethostbyname_r gethostbyname_r_proto: Inlibc Protochk Hasproto \
i_systypes usethreads i_netdb extern_C

?MAKE: -pick add \$@ %<

?S:d_gethostbyname_r:

?S: This variable conditionally defines the HAS_GETHOSTBYNAME_R symbol,

?S: which indicates to the C program that the gethostbyname_r()

?S: routine is available.

?S:.

?S:gethostbyname_r_proto:

?S: This variable encodes the prototype of gethostbyname_r.

?S: It is zero if d_gethostbyname_r is undef, and one of the

?S: REENTRANT_PROTO_T_ABC macros of reentr.h if d_gethostbyname_r

?S: is defined.

?S:.

?C:HAS_GETHOSTBYNAME_R:

?C: This symbol, if defined, indicates

that the gethostbyname_r routine

?C: is available to gethostbyname re-entrantly.

?C:.

?C:GETHOSTBYNAME_R_PROTO:

?C: This symbol encodes the prototype of gethostbyname_r.

?C: It is zero if d_gethostbyname_r is undef, and one of the

?C: REENTRANT_PROTO_T_ABC macros of reentr.h if d_gethostbyname_r

```

?C: is defined.
?C:.
?H:#$d_gethostbyname_r HAS_GETHOSTBYNAME_R /**/
?H:#define GETHOSTBYNAME_R_PROTO $gethostbyname_r_proto /**/
?H:.
?T:try hdrs d_gethostbyname_r_proto
: see if gethostbyname_r exists
set gethostbyname_r d_gethostbyname_r
eval $inlibc
case "$d_gethostbyname_r" in
"$define")
hdrs="$i_systypes sys/types.h define stdio.h $i_netdb netdb.h"
case "$d_gethostbyname_r_proto:$susetheads" in
":define") d_gethostbyname_r_proto=define
set d_gethostbyname_r_proto gethostbyname_r $hdrs
eval $hasproto ;;
*) ;;
esac
case "$d_gethostbyname_r_proto" in
define)
case "$gethostbyname_r_proto" in
"|0) try='int gethostbyname_r(const char*, struct hostent*, char*, size_t,
struct hostent**, int*);'
./protochk "$extern_C $try" $hdrs && gethostbyname_r_proto=I_CSBWRE ;;
esac
case "$gethostbyname_r_proto" in
"|0) try='struct hostent* gethostbyname_r(const char*, struct hostent*, char*, int, int*);'
./protochk "$extern_C $try" $hdrs && gethostbyname_r_proto=S_CSBIE ;;
esac
case "$gethostbyname_r_proto" in
"|0) try='int gethostbyname_r(const char*, struct hostent*, struct hostent_data*);'
./protochk "$extern_C $try" $hdrs && gethostbyname_r_proto=I_CSD ;;
esac
case "$gethostbyname_r_proto" in
"|0) d_gethostbyname_r=undef
gethostbyname_r_proto=0
echo "Disabling gethostbyname_r, cannot determine prototype." >&4 ;;
*) case "$gethostbyname_r_proto" in
REENTRANT_PROTO*) ;;
*) gethostbyname_r_proto="REENTRANT_PROTO_$gethostbyname_r_proto" ;;
esac
echo "Prototype: $try" ;;
esac
;;
*) case "$susetheads" in
define) echo "gethostbyname_r has no prototype, not using it." >&4 ;;
esac
d_gethostbyname_r=undef

```

```
gethostbyname_r_proto=0
;;
esac
;;
*) gethostbyname_r_proto=0
;;
esac
```

Found

in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/threads/d_gethostbyname_r.U
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1996, Andy Dougherty

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: Unix.U,v \$

?RCS: Revision 3.0.1.1 1997/02/28 15:20:06 ram

?RCS: patch61: created

?RCS:

?X:

?X: The purpose of this unit is to define things that are common across all

?X: known UNIX platforms. If Configure is ported/used on a non-UNIX

?X: environment, then some of the following variables can be redefined in hint

?X: files.

?X:

?MAKE:Unix _a _o firstmakefile archobjs: Oldconfig

?MAKE: -pick add \$@ %<

?S:_a (lib_ext):

?S: This variable defines the extension

used for ordinary libraries.

?S: For unix, it is 'a'. The '.' is included. Other possible

?S: values include '.lib'.

?S:.

?S:_o (obj_ext):

?S: This variable defines the extension used for object files.

?S: For unix, it is 'o'. The '.' is included. Other possible

?S: values include '.obj'.

?S:.

?S:firstmakefile:

?S: This variable defines the first file searched by make. On unix,

?S: it is makefile (then Makefile). On case-insensitive systems,

?S: it might be something else. This is only used to deal with

?S: convoluted make depend tricks.

?S:.

?S:archobjs:

?S: This variable defines any additional objects that must be linked

?S: in with the program on this architecture. On unix, it is usually

?S: empty. It is typically used to include emulations of unix calls

?S: or other facilities. For perl on OS/2, for example, this would

?S: include os2/os2.obj.

?S:.

?INIT:: Extra object files, if any, needed on this platform.

?INIT:archobjs="

: Define several unixisms.

: Hints files

or command line option can be used to override them.

case "\$_a" in

") _a='a';;

esac

case "\$_o" in

") _o='o';;

esac

@if firstmakefile

: Which makefile gets called first. This is used by make depend.

case "\$firstmakefile" in

") firstmakefile='makefile';;

esac

@end

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/Unix.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_gethname.U 1 2006-08-24 12:32:52Z rmanfredi \$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: d_gethname.U,v \$

?RCS: Revision 3.0.1.1 1994/10/29 16:13:00 ram

?RCS: patch36: call ./xenix explicitly instead of relying on PATH

?RCS:

?RCS: Revision 3.0 1993/08/18 12:06:11 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?MAKE:d_gethname d_uname d_phostname aphostname: phostname cat \
 myhostname package d_portable Loc echo n c +i_whoami +usrinc \
 Myread Guess Oldconfig Csym

?MAKE: -pick add \$@ %<

?S:d_gethname:

?S: This variable conditionally
 defines the HAS_GETHOSTNAME symbol, which

?S: indicates to the C program that the gethostname() routine may be

?S: used to derive the host name.

?S:.

?S:d_uname:

?S: This variable conditionally defines the HAS_UNAME symbol, which

?S: indicates to the C program that the uname() routine may be

?S: used to derive the host name.

?S:.

?S:d_phostname:

?S: This variable conditionally defines the HAS_PHOSTNAME symbol, which

?S: contains the shell command which, when fed to popen(), may be

?S: used to derive the host name.

?S:.

?S:aphostname:

?S: This variable contains the command which can be used to compute the

?S: host name. The command is fully qualified by its absolute path, to make

?S: it safe when used by a process with super-user privileges.

?S:.

?C:HAS_GETHOSTNAME (GETHOSTNAME):

?C: This symbol, if defined, indicates that the C program may use the

?C: gethostname() routine to derive the host name. See also HAS_UNAME

?C: and PHOSTNAME.

?C:.

?C:HAS_UNAME (UNAME):

?C: This symbol,

if defined, indicates that the C program may use the

?C: uname() routine to derive the host name. See also HAS_GETHOSTNAME

?C: and PHOSTNAME.

?C:.

?C:PHOSTNAME:

?C: This symbol, if defined, indicates the command to feed to the

?C: popen() routine to derive the host name. See also HAS_GETHOSTNAME

?C: and HAS_UNAME. Note that the command uses a fully qualified path,

?C: so that it is safe even if used by a process with super-user

```

?C: privileges.
?C:.
?C:HAS_PHOSTNAME:
?C: This symbol, if defined, indicates that the C program may use the
?C: contents of PHOSTNAME as a command to feed to the popen() routine
?C: to derive the host name.
?C:.
?H:?%<:#$d_gethname HAS_GETHOSTNAME /**/
?H:?%<:#$d_uname HAS_UNAME /**/
?H:?%<:#$d_phostname HAS_PHOSTNAME /**/
?H:?%<:#ifdef HAS_PHOSTNAME
?H:?%<:#define PHOSTNAME "$aphostname" /* How to get the host name */
?H:?%<:#endif
?H:.
?T:file val call
?LINT:change i_whoami
: see how we will look up host name
echo " "
call="
@if HAS_GETHOSTNAME
if
set gethostname val -f d_gethname; eval $scsym; $val; then
echo 'gethostname() found.' >&4
d_gethname="$define"
call=gethostname
fi
@end
@if HAS_UNAME
if set uname val -f d_uname; eval $scsym; $val; then
if ./xenix; then
$cat <<'EOM'
uname() was found, but you're running xenix, and older versions of xenix
have a broken uname(). If you don't really know whether your xenix is old
enough to have a broken system call, use the default answer.

EOM
dflt=y
case "$d_uname" in
"$define") dflt=n;;
esac
rp='Is your uname() broken?'
./myread
case "$ans" in
n*) d_uname="$define"; call=uname;;
esac
else
echo 'uname() found.' >&4
d_uname="$define"

```

```

case "$call" in
") call=uname ;;
esac
fi
fi
@end
case "$d_gethname" in
") d_gethname="$undef";;
esac
case "$d_uname" in
") d_uname="$undef";;
esac
@if PHOSTNAME || MYHOSTNAME
case "$d_uname$d_gethname" in
*define*)
dflt=n
cat <<EOM

```

Every now and then someone has a \$call() that lies about the hostname but can't be fixed

for political or economic reasons. If you wish, I can

```
@if MYHOSTNAME && PHOSTNAME
pretend $call() isn't there and maybe compile in the hostname or
compute it from the '$phostname' command at run-time.
```

```
@elsif MYHOSTNAME
pretend $call() isn't there and maybe compile in the hostname.
```

```
@elsif PHOSTNAME
pretend $call() isn't there and maybe compute hostname at run-time
thanks to the '$phostname' command.
```

```
@elsif WHOAMI
get the hostname from whomai.h (provided you have one).
```

```
@else
simply ignore your host name and use something like "noname" instead.
```

```
@end
```

EOM

```
rp="Shall I ignore $call() from now on?"
```

```
./myread
```

```
case "$ans" in
y*) d_uname="$undef" d_gethname="$undef"; $echo $n "Okay...$c";;
esac;;
```

```
esac
```

```
@end
```

```
@if PHOSTNAME || aphostname
```

```
?X: Compute the full path name for the command
```

```
case "$phostname" in
```

```
") aphostname=";;
```

```
*) case "$aphostname" in
```

```

/*) ;;
*) set X $phostname
  shift
  file=$1
  shift
  file=`./loc $file $file $pth`
  aphostname=`echo $file $*`
  ;;
esac
;;
esac
@end
@if
PHOSTNAME && MYHOSTNAME
case "$d_uname$d_gethname" in
*define*) ;;
*)
case "$phostname" in
") ;;
*)
$cat <<EOT

```

There is no gethostname() or uname() on this system. You have two possibilities at this point:

- 1) You can have your host name (\$myhostname) compiled into \$package, which lets \$package start up faster, but makes your binaries non-portable, or
- 2) you can have \$package use a

```
popen("$aphostname","r")
```

which will start slower but be more portable.

```
@ if WHOAMI
```

Option 1 will give you the option of using whoami.h if you have one.

```
@ end
```

If you want option 2 but with a different command, you can edit config.sh at the end of this shell script.

```
EOT
```

```

case "$d_phostname" in
"$define") dflt=n;;
"$undef") dflt=y;;
")
case "$d_portable" in
"$define") dflt=n ;;
*) dflt=y ;;
esac;;

```

```

esac
rp="Do you want your host name compiled in?"
./myread
case "$ans" in
n*) d_phostname="$define" ;;
*) aphostname=""; d_phostname="$undef";;
esac;;
esac
case
"$phostname" in
")
@ if WHOAMI
case "$i_whoami" in
"$define")
dflt=y
$cat <<EOM

```

No hostname function--you can either use the whoami.h file, which has this line:

```
`grep sysname $usrinc/whoami.h`
```

or you can have the name we came up with earlier (\$myhostname) hardwired in.

EOM

```

rp="Use whoami.h to get hostname?"
./myread
case "$ans" in
n*) i_whoami="$undef";;
esac
;;
"$undef")
$cat <<EOM

```

No hostname function and no whoami.h -- hardwiring "\$myhostname".

EOM

```

;;
esac;;
@ else
echo 'No hostname function -- hardwiring "$myhostname".' >&4;;
@ end
esac;;
esac
@elsif PHOSTNAME
case "$d_undef$d_gethname" in
*define*) ;;
*)
case "$phostname" in
")
@ if WHOAMI
case "$i_whoami" in

```

```
"$define")
$cat <<EOM
```

No hostname function--we'll use the whoami.h file, which has this line:

```
`grep sysname $usrinc/whoami.h`
```

EOM

```
;;
*) echo "There will be no way for $package to get your hostname." >&4;;
esac;;
@ else
echo "There will be no way
for $package to get your hostname." >&4;;
@ end
*)
echo "I'll use 'popen('"'$aphostname"', "r")' to get your hostname." >&4
;;
esac;;
esac
@elsif MYHOSTNAME
case "$d_uname$d_gethname" in
*define*) ;;
*)
@ if WHOAMI
case "$i_whoami" in
"$define")
dflt=y
$cat <<EOM
```

No hostname function--you can either use the whoami.h file, which has this line:

```
`grep sysname $usrinc/whoami.h`
```

or you can have the name we came up with earlier (\$myhostname) hardwired in.

EOM

```
rp="Use whoami.h to get hostname?"
./myread
case "$ans" in
n*) i_whoami="$undef";;
esac
;;
"$undef")
echo 'No whoami.h--hardwiring "'$myhostname"'.' >&4;;
esac;;
@ else
echo 'Hardwiring "'$myhostname"'.' >&4;;
@ end
```

```
esac
@end
case "$d_phostname" in
") d_phostname="$undef";;
esac
```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/modified/d_gethname.U
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1999, Jarkko Hietaniemi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 3.0.

?RCS:

?MAKE:d_sigwait: Inlibc

?MAKE:-pick add \$@ %<

?S:d_sigwait:

?S: This variable conditionally defines HAS_SIGWAIT

?S: if sigwait() is available to wait a signal.

?S:.

?C:HAS_SIGWAIT:

?C: This symbol, if defined, indicates that the sigwait

?C: system call is available to wait a signal.

?C:.

?H:#\$d_sigwait HAS_SIGWAIT /**/

?H:.

?LINT:set d_sigwait

: see if sigwait exists

set sigwait d_sigwait

eval \$inlibc

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/perl/d_sigwait.U
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: fpostype.U,v \$

?RCS: Revision 3.0.1.2 1994/08/29 16:20:52 ram

?RCS: patch32: now uses new Typedef unit to compute type information

?RCS:

?RCS: Revision 3.0.1.1 1994/06/20 06:59:59 ram

?RCS: patch30: created

?RCS:

?MAKE:fpostype: Myread Typedef

?MAKE: -pick add \$@ %<

?S:fpostype:

?S: This variable defines Fpos_t to be something like fpost_t, long,

?S: uint, or whatever type is used to declare file positions in libc.

?S:.

?C:Fpos_t:

?C: This symbol holds the type used to declare file positions
in libc.

?C: It can be fpos_t, long, uint, etc... It may be necessary to include

?C: <sys/types.h> to get any typedef'ed information.

?C:.

?H:#define Fpos_t \$fpostype /* File position type */

?H:.

: see what type file positions are declared as in the library

set fpos_t fpostype long stdio.h sys/types.h

eval \$typedef

echo " "

dflt="\$fpostype"

rp="What is the type for file position used by fsetpos()?"

./myread

fpostype="\$ans"

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/fpostype.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: i_sunmath.U,v \$

?RCS:

?RCS: Copyright (c) 2000 Jarkko Hietaniemi

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?MAKE:i_sunmath: Inhdr Hasfield

?MAKE: -pick add \$@ %<
?S:i_sunmath:
?S: This variable conditionally defines the I_SUNMATH symbol, and indicates
?S: whether a C program should include <sunmath.h>.
?S:.
?C:I_SUNMATH:
?C: This symbol, if defined, indicates that <sunmath.h> exists and
?C: should be included.
?C:.
?H:#\$i_sunmath I_SUNMATH /**/
?H:.
?LINT:set i_sunmath
: see if this is a sunmath.h system
set sunmath.h i_sunmath
eval \$inhdr

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/i_sunmath.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$
?RCS:
?RCS: Copyright (c) 1999 Jarkko Hietaniemi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 3.0.
?RCS:
?MAKE:d_mprotect: Inlibc
?MAKE: -pick add \$@ %<
?S:d_mprotect:
?S: This variable conditionally defines HAS_MPROTECT if mprotect() is
?S: available to modify the access protection of a memory mapped file.
?S:.
?C:HAS_MPROTECT:
?C: This symbol, if defined, indicates that the mprotect system call is
?C: available to modify the access protection of a memory mapped file.
?C:.
?H:#\$d_mprotect HAS_MPROTECT /**/
?H:.
?LINT:set d_mprotect
: see if mprotect exists
set mprotect d_mprotect
eval \$inlibc

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_mprotect.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: Loc.U 14 2006-08-28 16:51:14Z rmanfredi \$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: Loc.U,v \$

?RCS: Revision 3.0.1.10 1997/02/28 15:04:16 ram

?RCS: patch61: allow users to specify paths on the command line

?RCS: patch61: will now substitute cp for ln if not supported

?RCS:

?RCS: Revision 3.0.1.9 1995/09/25 09:11:24 ram

?RCS: patch59: commented the purpose of the #un-def directive

?RCS: patch59: abort Configure run when mandatory command is missing

?RCS:

?RCS: Revision 3.0.1.8 1995/07/25 13:40:40 ram

?RCS: patch56: now knows about

OS/2 platforms

?RCS:

?RCS: Revision 3.0.1.7 1995/01/11 15:13:37 ram

?RCS: patch45: protected "sh -c" within backquotes for Linux and SGI

?RCS: patch45: added path lookup for the 'comm' program

?RCS:

?RCS: Revision 3.0.1.6 1994/10/29 15:56:14 ram

?RCS: patch36: added ?F: line for metalint file checking

?RCS: patch36: be careful and guard against wildcard searching (ADO)

?RCS:

?RCS: Revision 3.0.1.5 1994/06/20 06:54:55 ram

?RCS: patch30: now locates find

?RCS:

?RCS: Revision 3.0.1.4 1994/05/13 15:18:15 ram

?RCS: patch27: added byacc to the trylist (ADO)

?RCS: patch27: lint lines reformatted (ADO)

?RCS:

?RCS: Revision 3.0.1.3 1994/01/24 14:01:44 ram

?RCS: patch16: added metalint hint on changed PATH variable

?RCS:

?RCS: Revision 3.0.1.2 1993/12/15 08:16:52 ram

?RCS: patch15: now set _test variable when test is built-in

?RCS: patch15: fixed rare cases where echo is not needed

?RCS:

?RCS: Revision 3.0.1.1 1993/09/13 15:47:13 ram

?RCS: patch10: test program not always
in /bin/test (WAD)

?RCS:

?RCS: Revision 3.0 1993/08/18 12:05:05 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?X:

?X: This unit produces a shell script "loc" which can be used to find out
?X: where in a list of directories something is. It then uses loc to
?X: determine the location of commonly used programs. It leaves loc sitting
?X: around for other Configure units to use, but arranges for its demise
?X: at the end of Configure.

?X:

?X: To add a new program to find, add it both to the ?MAKE: line and to either
?X: the loclist or trylist variable.

?X:

?X: I put startsh at the end of the dependency list, in order to avoid the
?X: loading of the spitshell unit before the instructions.

?X:

?MAKE:Loc awk ar bash bison byacc cat chgrp chmod chown \
comm compress cp cpio cpp csh date echo egrep emacs expr find flex \
gmake gzip grep inews ksh less line lint ln lp lpr ls mail mailx \
make mkdir more mv nm nroff perl pg pmake pr rm rmail sed sendmail \
shar sleep smail sort
submit tail tar tbl tee test touch tr troff \
uname uniq uuname vi zcat zip: eunicefix n c startsh Instruct sysroot

?MAKE: -pick weed \$@ %<

?LINT:describe awk ar bash bison byacc cat chgrp chmod chown \
comm compress cp cpio cpp csh date echo egrep emacs expr find flex \
gmake gzip grep inews ksh less line lint ln lp lpr ls mail mailx \
make mkdir more mv nm nroff perl pg pmake pr rm rmail sed sendmail \
shar sleep smail sort submit tail tar tbl tee test touch tr troff \
uname uniq uuname vi zcat zip

?V::pth loclist trylist

?F:./loc test_h

?T:thisthing thing xxx dir file say _test DJGPP

?LINT:change PATH _egrep _ln _make _less

?LINT:extern _exe

: find out where common programs are
echo " "
echo "Locating common programs..." >&4
cat <<EOSC >loc
\$startsh
case \ \$# in
0) exit 1;;

```

esac
thing=\$1
shift
dflt=\$1
shift
for dir in \${*}; do
  case "\$thing" in
  .)
  if test -d \$dir/\$thing; then
    echo \$dir
    exit 0
  fi
  ;;
  *)
  ?X: Be careful in case thing includes wildcards that might expand
  to multiple
  ?X: files. Choose the last one. This happens when searching for shared
  ?X: libraries with version numbers. How to choose which one we want is
  ?X: probably an insoluble problem, in general.
  ?X: Some folks leave things like libc.so.orig around w/o read
  ?X: permission. A -r test would handle that, but since ./loc is
  ?X: also used to find executables (which are installed w/o read
  ?X: permission on SCO ODT 3.0, we can't include the -r test.
  ?X: If you need to use an _exe that is different from .exe
  ?X: you need to set it in Head.U.
  for thisthing in \$dir/\$thing; do
    : just loop through to pick last item
  done
  if test -f \$thisthing; then
    echo \$thisthing
    exit 0
  elif test "X$_exe" != X -a -f \$thisthing$_exe; then
    echo \$thisthing
    exit 0
  elif test -f \$dir/\$thing.exe; then
    if test -n "$DJGPP"; then
      echo \$dir/\$thing.exe
    elif test "$eunicefix" != ":"; then
      : on Eunice apparently
      echo \$dir/\$thing
    fi
    exit 0
  fi
  ;;
esac
done
echo \$dflt
exit

```

1

EOSC
chmod +x loc
\$unicefix loc
loclist="
?awk:awk
?cat:cat
?chgrp:chgrp
?chmod:chmod
?chown:chown
?comm:comm
?cp:cp
?echo:echo
?expr:expr
?find:find
?grep:grep
?ls:ls
?mkdir:mkdir
?mv:mv
?rm:rm
?sed:sed
?sleep:sleep
?sort:sort
?tail:tail
?touch:touch
?tr:tr
?uniq:uniq
"
trylist="
?Mcc:Mcc
?ar:ar
?bash:bash
?bison:bison
?byacc:byacc
?compress:compress
?cpio:cpio
?cpp:cpp
?csh:csh
?date:date
?egrep:egrep
?emacs:emacs
?flex:flex
?gmake:gmake
?gzip:gzip
?inews:inews
?ksh:ksh
?less:less
?line:line

```

?lint:lint
?ln:ln
?lp:lp
?lpr:lpr
?mail:mail
?mailx:mailx
?make:make
?more:more
?nm:nm
?nroff:nroff
?perl:perl
?pg:pg
?pmake:pmake
?pr:pr
?rmail:rmail
?sendmail:sendmail
?shar:shar
?smail:smail
?submit:submit
?tar:tar
?tbl:tbl
?tee:tee
?test:test
?troff:troff
?uname:uname
?uname:uname
?vi:vi
?zcat:zcat
?zip:zip
"
?LINT:set awk ar bash bison byacc cat chgrp chmod chown \
comm compress cp cpio cpp csh date echo emacs expr find flex \
gmake gzip grep inews ksh line lint lp lpr ls mail mailx
\
mkdir more mv nm nroff perl pg pmake pr rm rmail sed sendmail \
shar sleep smail sort submit tail tar tbl tee touch tr troff \
uname uniq uname vi zcat zip
pth=`echo $PATH | sed -e "s/$p_/ /g"`
pth="$pth $sysroot/lib $sysroot/usr/lib"
for file in $loclist; do
?X:
?X: Allow them to -Dmake=pmake on the command line for instance...
?X: If the file is not fully qualified, as in -Dmake=pmake, then we
?X: look the for the specified command (pmake here). If they say
?X: -Dmake=/sbin/make for instance, then we make sure the file
?X: exists, or we die...
?X:
eval xxx=\$$file

```

```

case "$xxx" in
/*|?:[\\]*
if test -f "$xxx"; then
: ok
else
echo "WARNING: no $xxx -- ignoring your setting for $file." >&4
xxx=`./loc $file $file $pth`
fi
;;
") xxx=`./loc $file $file $pth`;
*) xxx=`./loc $xxx $xxx $pth`;
esac
eval $file=$xxx$_exe
eval _$file=$xxx
case "$xxx" in
/*)
echo $file is in $xxx.
;;
?X: Under OS/2, we have PC-like paths
?:[\\]*)
echo $file is in $xxx.
;;
*)
echo
"I don't know where '$file' is, and my life depends on it." >&4
echo "Go find a public domain implementation or fix your PATH setting!" >&4
exit 1
;;
esac
done
echo " "
echo "Don't worry if any of the following aren't found..."
say=offhand
for file in $trylist; do
?X: Allow them to -Dmake=pmake on the command line for instance (see above)
eval xxx=\\$file
case "$xxx" in
/*|?:[\\]*)
if test -f "$xxx"; then
: ok
else
echo "WARNING: no $xxx -- ignoring your setting for $file." >&4
xxx=`./loc $file $file $pth`
fi
;;
") xxx=`./loc $file $file $pth`;
*) xxx=`./loc $xxx $xxx $pth`;
esac

```

```

eval $file=$xxx$_exe
eval _$file=$xxx
case "$xxx" in
/*)
echo $file is in $xxx.
;;
?X: Under OS/2, we have PC-like paths
?:[\\]*)
echo $file is in $xxx.
;;
*)
echo "I don't see $file out there, $say."
say=either
;;
esac
done
case "$egrep" in
egrep)
echo "Substituting grep for egrep."
egrep=$grep
_egrep=$grep
;;
esac
@if less
case "$less"
in
") ;;
*) if $less -R </dev/null >/dev/null 2>&1; then
echo "Substituting less -R for less."
less="$less -R"
_less=$less
fi
;;
esac
@end
@if ln
case "$ln" in
ln)
echo "Substituting cp for ln."
ln=$cp
_ln=$cp
;;
esac
@end
@if make || gmake
case "$make" in
make)
case "$gmake" in

```

```

gmake)
echo "I can't find make or gmake, and my life depends on it." >&4
echo "Go find a public domain implementation or fix your PATH setting!" >&4
exit 1
;;
esac
;;
esac
case "$gmake" in
gmake) ;;
*) # We can't have osname yet.
if test -f "/system/gnu_library/bin/ar.pm"; then # Stratus VOS
# Assume that gmake, if found, is definitely GNU make
# and prefer it over the system make.
echo "Substituting gmake for make."
make=$gmake
_make=$gmake
fi
;;
esac
@end
case "$test" in
test)
echo "Hopefully test is built into your sh."
;;
*)
if `sh -c "PATH= test true" >/dev/null 2>&1`; then
echo "Using the test built into your sh."
?X:
?X: We need to set both test
and _test, since Oldconfig.U will use the _test
?X: value to systematically restore computed paths, which may be wrong if
?X: we choose to load an old config.sh generated on another platform.
?X:
test=test
_test=test
fi
;;
esac
?LINT:change n c
case "$echo" in
echo)
echo "Hopefully echo is built into your sh."
;;
?X: For those rare cases where we don't need $echo...
") ;;
*)
echo " "

```

```

echo "Checking compatibility between $echo and builtin echo (if any)..." >&4
$echo $n "hi there$c" >foo1
echo $n "hi there$c" >foo2
if cmp foo1 foo2 >/dev/null 2>&1; then
echo "They are compatible. In fact, they may be identical."
else
case "$n" in
'-n') n=" c='\c';;
*) n='-n' c="";;
esac
cat <<FOO

```

They are not compatible! You are probably running ksh on a non-USG system. I'll have to use \$echo instead of the builtin, since Bourne shell doesn't have echo built in and we may have to run some Bourne shell scripts. That means I'll have to use '\$n\$c' to suppress newlines now.

Life is ridiculous.

```

FOO
$echo $n "The star should be here-->$c"
$echo "*"
fi
$rm -f foo1 foo2
;;
esac

```

?X: The next part is irrelevant to the real process
This question was auctioned at YAPC::Europe-2007 in Vienna
I never promised you could answer it. I only auctioned the question.
cat <<FOO

The following message is sponsored by

Dresden.pm<--The stars should be here.

Dear Perl user, system administrator or package maintainer, the Perl community sends greetings to you. Do you (emblematical) greet back [Y/n]? n

FOO

Found in path(s):
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/modified/Loc.U
No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_getprotobynumber_r.U,v 0RCS:
?RCS: Copyright (c) 2002,2003 Jarkko Hietaniemi
?RCS:
?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?RCS: Generated by the reentr.pl from the Perl 5.8 distribution.

?RCS:

?MAKE:d_getprotobynumber_r getprotobynumber_r_proto: Inlibc Protochk \
 Hasproto i_systypes usethreads i_netdb extern_C

?MAKE: -pick add \$@ %<

?S:d_getprotobynumber_r:

?S: This variable conditionally defines the HAS_GETPROTOBYNUMBER_R symbol,
 ?S: which indicates to the C program that the getprotobynumber_r()
 ?S: routine is available.

?S:.

?S:getprotobynumber_r_proto:

?S: This variable encodes the prototype of getprotobynumber_r.
 ?S: It is zero if d_getprotobynumber_r is undef, and one of the
 ?S: REENTRANT_PROTO_T_ABC macros of reentr.h if d_getprotobynumber_r
 ?S: is defined.

?S:.

?C:HAS_GETPROTOBYNUMBER_R:

?C: This
 symbol, if defined, indicates that the getprotobynumber_r routine
 ?C: is available to getprotobynumber re-entrantly.

?C:.

?C:GETPROTOBYNUMBER_R_PROTO:

?C: This symbol encodes the prototype of getprotobynumber_r.
 ?C: It is zero if d_getprotobynumber_r is undef, and one of the
 ?C: REENTRANT_PROTO_T_ABC macros of reentr.h if d_getprotobynumber_r
 ?C: is defined.

?C:.

?H:#\$d_getprotobynumber_r HAS_GETPROTOBYNUMBER_R /**/
 ?H:#define GETPROTOBYNUMBER_R_PROTO \$getprotobynumber_r_proto /**/
 ?H:.

?T:try hdrs d_getprotobynumber_r_proto
 : see if getprotobynumber_r exists
 set getprotobynumber_r d_getprotobynumber_r
 eval \$inlibc
 case "\$d_getprotobynumber_r" in
 "\$define")
 hdrs="\$i_systypes sys/types.h define stdio.h \$i_netdb netdb.h"
 case "\$d_getprotobynumber_r_proto:\$usethreads" in
 ":define") d_getprotobynumber_r_proto=define
 set d_getprotobynumber_r_proto getprotobynumber_r \$hdrs
 eval \$hasproto ;;
 *) ;;
 esac
 case "\$d_getprotobynumber_r_proto" in
 define)
 case "\$getprotobynumber_r_proto"

```

in
"|0) try='int getprotobynumber_r(int, struct protoent*, char*, size_t, struct protoent**);'
./protochk "$extern_C $try" $hdrs && getprotobynumber_r_proto=I_ISBWR ;;
esac
case "$getprotobynumber_r_proto" in
"|0) try='struct protoent* getprotobynumber_r(int, struct protoent*, char*, int);'
./protochk "$extern_C $try" $hdrs && getprotobynumber_r_proto=S_ISBI ;;
esac
case "$getprotobynumber_r_proto" in
"|0) try='int getprotobynumber_r(int, struct protoent*, struct protoent_data*);'
./protochk "$extern_C $try" $hdrs && getprotobynumber_r_proto=I_ISD ;;
esac
case "$getprotobynumber_r_proto" in
"|0) d_getprotobynumber_r=undef
    getprotobynumber_r_proto=0
    echo "Disabling getprotobynumber_r, cannot determine prototype." >&4 ;;
*) case "$getprotobynumber_r_proto" in
    REENTRANT_PROTO*) ;;
    *) getprotobynumber_r_proto="REENTRANT_PROTO_$getprotobynumber_r_proto" ;;
    esac
    echo "Prototype: $try" ;;
    esac
    ;;
*) case "$susethreads" in
    define) echo
    "getprotobynumber_r has no prototype, not using it." >&4 ;;
    esac
    d_getprotobynumber_r=undef
    getprotobynumber_r_proto=0
    ;;
    esac
    ;;
*) getprotobynumber_r_proto=0
    ;;
    esac

```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/threads/d_getprotobynumber_r.U
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1999, Jarkko Hietaniemi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 3.0.
?RCS:
?MAKE:d_posix_timer: Setvar d_timer_create d_timer_delete d_timer_gettime d_timer_settime
d_timer_getoverrun i_time
?MAKE: -pick add \$@ %<
?S:d_posix_timer:
?S: This variable conditionally defines the HAS_POSIX_TIMER symbol, which
?S: indicates that the entire POSIX timer_*(2) library is present.
?S:.
?C:HAS_POSIX_TIMER:
?C: This symbol, if defined, indicates that the entire POSIX timer_*(2)
?C: library is supported.
?C:.
?H:#\$d_posix_timer HAS_POSIX_TIMER /**/
?H:.
?LINT:set d_posix_timer
: see how much of the 'POSIX timer_*(2)'
library is present.
echo " "
case "\$i_time\$d_timer_create\$d_timer_delete\$d_timer_gettime\$d_timer_settime\$d_timer_getoverrun" in
"\${undef}) val="\${undef}" ;;
*) val="\$define" ;;
esac
case "\$val" in
"\$define") echo "You have the full POSIX timer_*(2) library." >&4 ;;
"\$undef") echo "You don't have the full POSIX timer_*(2) library." >&4 ;;
esac
set d_posix_timer
eval \$setvar

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/perl/d_posix_timer.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: i_fp.U,v \$
?RCS:
?RCS: Copyright (c) 1998 Jarkko Hietaniemi
?RCS:
?RCS: You may distribute under the terms of either the GNU General Public
?RCS: License or the Artistic License, as specified in the README file.
?RCS:
?MAKE:i_fp: Inhdr
?MAKE: -pick add \$@ %<
?S:i_fp:
?S: This variable conditionally defines the I_FP symbol, and indicates
?S: whether a C program should include <fp.h>.

?S:
?C:I_FP:
?C: This symbol, if defined, indicates that <fp.h> exists and
?C: should be included.
?C:.
?H:#\$i_fp I_FP /**/
?H:.
?LINT:set i_fp
: see if this is a fp.h system
set fp.h i_fp
eval \$inhdr

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/i_fp.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_setsent.U,v 3.0 1993/08/18 12:06:09 ram Exp \$
?RCS:
?RCS: Copyright (c) 1991-1993, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 3.0.
?RCS:
?RCS: \$Log: d_setsent.U,v \$
?RCS: Revision 3.0 1993/08/18 12:06:09 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:d_setsent: Inlibc
?MAKE: -pick add \$@ %<
?S:d_setsent:
?S: This variable conditionally defines HAS_SETSERVENT if setservernt() is
?S: available.
?S:.
?C:HAS_SETSERVENT:
?C: This symbol, if defined, indicates that the setservernt() routine is
?C: available.
?C:.
?H:#\$d_setsent HAS_SETSERVENT /**/
?H:.
?LINT:set d_setsent
: see if setservernt exists
set
setservernt d_setsent
eval \$inlibc

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/modified/d_setsent.U

No license file was found, but licenses were detected in source scan.

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?MAKE:d_llrintl: Inlibc

?MAKE: -pick add \$@ %<

?S:d_llrintl:

?S: This variable conditionally defines the HAS_LLRLINTL symbol, which

?S: indicates to the C program that the llrintl() routine is available

?S: to return the long long value closest to a long double (according

?S: to the current rounding mode).

?S:.

?C:HAS_LLRLINTL:

?C: This symbol, if defined, indicates that the llrintl routine is

?C: available to return the long long value closest to a long double

?C: (according to the current rounding mode).

?C:.

?H:#\$d_llrintl HAS_LLRLINTL /**/

?H:.

?LINT:set d_llrintl

: see if llrintl exists

set llrintl d_llrintl

eval \$inlibc

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_llrintl.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_getnbyname.U,v \$

?RCS:

?RCS: Copyright (c) 1998 Andy Dougherty

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?MAKE:d_getnbyname: Inlibc

?MAKE: -pick add \$@ %<

?S:d_getnbyname:

?S: This variable conditionally defines the HAS_GETNETBYNAME symbol, which

?S: indicates to the C program that the getnetbyname() routine is available

?S: to look up networks by their names.

?S:.

?C:HAS_GETNETBYNAME:

?C: This symbol, if defined, indicates that the getnetbyname() routine is

?C: available to look up networks by their names.

?C:.

?H:#\$d_getbyname HAS_GETNETBYNAME /**/

?H:.

?LINT:set d_getbyname

: see if getnetbyname exists

set getnetbyname d_getbyname

eval \$inlibc

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/modified/d_getbynm.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_sitecustomize.U,v \$

?RCS:

?RCS: Copyright (c) 2005-2006 H.Merijn Brand

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?RCS: \$Log: d_sitecustomize.U,v \$

?RCS:

?MAKE:usesitecustomize: Oldconfig Setvar

?MAKE: -pick add \$@ %<

?S:usesitecustomize:

?S: This variable is set to true when the user requires a mechanism that

?S: allows the sysadmin to add entries to @INC at runtime. This variable

?S: being set, makes perl run '\$sitelib/sitecustomize.pl' at startup.

?S:.

?C:USE_SITECUSTOMIZE:

?C: This symbol, if defined, indicates that sitecustomize should

?C: be used.

?C:.

?H:?%<:@if USE_SITECUSTOMIZE

?H:?%<:#ifndef USE_SITECUSTOMIZE

?H:?%<:#\$usesitecustomize USE_SITECUSTOMIZE /**/

?H:?%<:#endif

?H:?%<:@end

?H:.

: Check if site customization support was requested

case "\$usesitecustomize" in

 \$define|true|[Yy]*)

 usesitecustomize="\$define"

;;

```
*)
usesitecustomize="$undef"
;;
esac
```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/perl/d_sitecustomize.U
```

No license file was found, but licenses were detected in source scan.

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?MAKE:d_acosh: Inlibc

?MAKE: -pick add \$@ %<

?S:d_acosh:

?S: This variable conditionally defines the HAS_ACOSH symbol, which

?S: indicates to the C program that the acosh() routine is available.

?S:.

?C:HAS_ACOSH:

?C: This symbol, if defined, indicates that the acosh routine is

?C: available to do the inverse hyperbolic cosine function.

?C:.

?H:#\$d_acosh HAS_ACOSH /**/

?H:.

?LINT:set d_acosh

: see if acosh exists

set acosh d_acosh

eval \$inlibc

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/perl/d_acosh.U
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 2001 Jarkko Hietaniemi

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?MAKE:d_realpath: Inlibc

?MAKE: -pick add \$@ %<

?S:d_realpath:

?S: This variable conditionally defines the HAS_REALPATH symbol, which

?S: indicates to the C program that the realpath() routine is available.

?S:.

?C:HAS_REALPATH:

?C: This symbol, if defined, indicates that the realpath routine is

?C: available to do resolve paths.

?C:.

?H:#\$d_realpath HAS_REALPATH /**/

?H:.

?LINT:set d_realpath

: see if realpath exists

set realpath d_realpath

eval \$inlibc

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_realpath.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_getopt.U 1 2006-08-24 12:32:52Z rmanfredi \$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic Licence,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic Licence; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: d_getopt.U,v \$

?RCS: Revision 3.0 1993/08/18 12:06:13 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?MAKE:d_getopt: Inlibc

?MAKE: -pick add \$@ %<

?S:d_getopt:

?S: This variable conditionally defines the HAS_GETOPT symbol, which

?S: indicates that the getopt() routine exists. The getopt() routine

?S: parses command line options in a standard fashion.

?S:.

?C:HAS_GETOPT (GETOPT):

?C: This symbol, if defined, indicates that the getopt() routine exists.

?C:.

?H:#\$d_getopt HAS_GETOPT /**/

?H:.

?LINT:set d_getopt

: see if getopt exists

set getopt d_getopt

eval \$inlibc

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/d_getopt.U
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1999, Jarkko Hietaniemi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 3.0.

?RCS:

?MAKE:full_ar: ar

?MAKE: -pick add \$@ %<

?S:full_ar:

?S: This variable contains the full pathname to 'ar', whether or

?S: not the user has specified 'portability'. This is only used

?S: in the Makefile.SH.

?S:.

: Store the full pathname to the ar program for use in the C program

: Respect a hint or command line value for full_ar.

```
case "$full_ar" in
```

```
) full_ar=$ar ;;
```

```
esac
```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/Loc_ar.U
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_getpwnam_r.U,v 0RCS:

?RCS: Copyright (c) 2002,2003 Jarkko Hietaniemi

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?RCS: Generated by the reentr.pl from the Perl 5.8 distribution.

?RCS:

?MAKE:d_getpwnam_r getpwnam_r_proto: Inlibc Protochk Hasproto i_systypes \
 usethreads i_pwd extern_C

?MAKE: -pick add \$@ %<

?S:d_getpwnam_r:

?S: This variable conditionally defines the HAS_GETPWNAM_R symbol,

?S: which indicates to the C program that the getpwnam_r()

?S: routine is available.

?S:
?S:getpwnam_r_proto:
?S: This variable encodes the prototype of getpwnam_r.
?S: It is zero if d_getpwnam_r is undef, and one of the
?S: REENTRANT_PROTO_T_ABC macros of reentr.h if d_getpwnam_r
?S: is defined.
?S:
?C:HAS_GETPWNAM_R:
?C: This symbol, if defined, indicates that the getpwnam_r routine
?C: is available to
getpwnam re-entrantly.
?C:
?C:GETPWNAM_R_PROTO:
?C: This symbol encodes the prototype of getpwnam_r.
?C: It is zero if d_getpwnam_r is undef, and one of the
?C: REENTRANT_PROTO_T_ABC macros of reentr.h if d_getpwnam_r
?C: is defined.
?C:
?H:#\$d_getpwnam_r HAS_GETPWNAM_R /**/
?H:#define GETPWNAM_R_PROTO \$getpwnam_r_proto /**/
?H:
?T:try hdrs d_getpwnam_r_proto
: see if getpwnam_r exists
set getpwnam_r d_getpwnam_r
eval \$inlibc
case "\$d_getpwnam_r" in
"\$define")
hdrs="\$i_systypes sys/types.h define stdio.h \$i_pwd pwd.h"
case "\$d_getpwnam_r_proto:\$usetthreads" in
":define") d_getpwnam_r_proto=define
set d_getpwnam_r_proto getpwnam_r \$hdrs
eval \$hasproto ;;
*) ;;
esac
case "\$d_getpwnam_r_proto" in
define)
case "\$getpwnam_r_proto" in
"|0) try='int getpwnam_r(const char*, struct passwd*, char*, size_t, struct passwd**);'
./protochk "\$extern_C \$try" \$hdrs && getpwnam_r_proto=I_CSBWR ;;
esac
case "\$getpwnam_r_proto" in
"|0) try='int getpwnam_r(const char*, struct passwd*,
char*, int, struct passwd**);'
./protochk "\$extern_C \$try" \$hdrs && getpwnam_r_proto=I_CSBIR ;;
esac
case "\$getpwnam_r_proto" in
"|0) try='struct passwd* getpwnam_r(const char*, struct passwd*, char*, int);'
./protochk "\$extern_C \$try" \$hdrs && getpwnam_r_proto=S_CSBI ;;

```

esac
case "$getpwnam_r_proto" in
"|0) try='int getpwnam_r(const char*, struct passwd*, char*, int);'
./protochk "$extern_C $try" $hdrs && getpwnam_r_proto=I_CSBI ;;
esac
case "$getpwnam_r_proto" in
"|0) d_getpwnam_r=undef
    getpwnam_r_proto=0
    echo "Disabling getpwnam_r, cannot determine prototype." >&4 ;;
*) case "$getpwnam_r_proto" in
    REENTRANT_PROTO*) ;;
    *) getpwnam_r_proto="REENTRANT_PROTO_$getpwnam_r_proto" ;;
esac
echo "Prototype: $try" ;;
esac
;;
*) case "$usethreads" in
define) echo "getpwnam_r has no prototype, not using it." >&4 ;;
esac
d_getpwnam_r=undef
getpwnam_r_proto=0
;;
esac
;;
*) getpwnam_r_proto=0
;;
esac

```

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/threads/d_getpwnam_r.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: myhostname.U,v 3.0.1.3 1997/02/28 16:15:55 ram Exp \$

?RCS:

?RCS: Copyright (c) 1991-1993, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 3.0.

?RCS:

?RCS: \$Log: myhostname.U,v \$

?RCS: Revision 3.0.1.3 1997/02/28 16:15:55 ram

?RCS: patch61: improved hostname lookup by using ypmatch when NIS is used

?RCS:

?RCS: Revision 3.0.1.2 1994/10/29 16:25:43 ram

?RCS: patch36: call ./xenix explicitly instead of relying on PATH

?RCS: patch36: now uses new Tr unit to convert to/from lowercase

?RCS:

?RCS: Revision 3.0.1.1 1994/06/20 07:06:20 ram

?RCS: patch30: now a little more clever for domain name guessing

?RCS:

?RCS:

Revision 3.0 1993/08/18 12:09:18 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?MAKE:myhostname phostname mydomain: contains sed test Myread Oldconfig \
 Guess Loc awk echo sort uniq +usrinc rm hostcat Tr

?MAKE: -pick add \$@ %<

?S:myhostname (hostname):

?S: This variable contains the eventual value of the MYHOSTNAME symbol,
 ?S: which is the name of the host the program is going to run on.
 ?S: The domain is not kept with hostname, but must be gotten from mydomain.
 ?S: The dot comes with mydomain, and need not be supplied by the program.
 ?S:.

?S:mydomain:

?S: This variable contains the eventual value of the MYDOMAIN symbol,
 ?S: which is the domain of the host the program is going to run on.
 ?S: The domain must be appended to myhostname to form a complete host name.
 ?S: The dot comes with mydomain, and need not be supplied by the program.
 ?S:.

?S:phostname:

?S: This variable contains the eventual value of the PHOSTNAME symbol,
 ?S: which is a command that can be fed to popen()
 to get the host name.
 ?S: The program should probably not presume that the domain is or isn't
 ?S: there already.
 ?S:.

?C:MYHOSTNAME (HOSTNAME):

?C: This symbol contains name of the host the program is going to run on.
 ?C: The domain is not kept with hostname, but must be gotten from MYDOMAIN.
 ?C: The dot comes with MYDOMAIN, and need not be supplied by the program.
 ?C: If gethostname() or uname() exist, MYHOSTNAME may be ignored. If MYDOMAIN
 ?C: is not used, MYHOSTNAME will hold the name derived from PHOSTNAME.
 ?C:.

?C:MYDOMAIN:

?C: This symbol contains the domain of the host the program is going to
 ?C: run on. The domain must be appended to HOSTNAME to form a complete
 ?C: host name. The dot comes with MYDOMAIN, and need not be supplied by
 ?C: the program. If the host name is derived from PHOSTNAME, the domain
 ?C: may or may not already be there, and the program should check.
 ?C:.

?H:#define MYHOSTNAME "\$myhostname" /**/
 ?H:#define MYDOMAIN "\$mydomain" /**/

```

?H:
?LINT:extern osname
?T:cont
i tans tmp_re
: now get the host name
echo " "
echo "Figuring out host name..." >&4
case "$myhostname" in
") cont=true
echo 'Maybe "hostname" will work...'
if tans=`sh -c hostname 2>&1` ; then
myhostname=$tans
phostname=hostname
cont=""
fi
;;
*) cont="";;
esac
if $test "$cont"; then
if ./xenix; then
echo 'Oh, dear. Maybe "/etc/systemid" is the key...'
if tans=`cat /etc/systemid 2>&1` ; then
myhostname=$tans
phostname='cat /etc/systemid'
echo "Whadyaknow. Xenix always was a bit strange..."
cont=""
fi
elif $test -r /etc/systemid; then
echo "(What is a non-Xenix system doing with /etc/systemid?)"
fi
fi
if $test "$cont"; then
echo 'No, maybe "uname -l" will work...'
if tans=`sh -c 'uname -l' 2>&1` ; then
myhostname=$tans
phostname='uname -l'
else
echo 'Strange. Maybe "uname -n" will work...'
if tans=`sh -c 'uname -n' 2>&1` ; then
myhostname=$tans
phostname='uname -n'
else
echo 'Oh well, maybe I can mine it out of whoami.h...'
if
tans=`sh -c $contains' sysname $usrinc/whoami.h' 2>&1` ; then
myhostname=`echo "$tans" | $sed 's/^(.*)/\1/'`
phostname="sed -n -e ""'/sysname/s/^(.*)/\1/{'' -e p -e q -e }' <$usrinc/whoami.h"
else

```

```

case "$myhostname" in
") echo "Does this machine have an identity crisis or something?"
phostname="";
*)
echo "Well, you said $myhostname before..."
phostname='echo $myhostname';;
esac
fi
fi
fi
fi
case "$myhostname" in
") myhostname=noname ;;
esac
: you do not want to know about this
set $myhostname
myhostname=$1

: verify guess
if $test "$myhostname" ; then
dflt=y
rp='Your host name appears to be "$myhostname"." Right?'
./myread
case "$ans" in
y*) ;;
*) myhostname="";;
esac
fi

: bad guess or no guess
while $test "X$myhostname" = X ; do
dflt=""
rp="Please type the (one word) name of your host:"
./myread
myhostname="$ans"
done

: translate upper to lower if necessary
case "$myhostname" in
*[A-Z]*)
echo
"(Normalizing case in your host name)"
myhostname=`echo $myhostname | ./tr '[A-Z]' '[a-z]'`
;;
esac

```

?X: Do not ask for domain name if this is not used later on. In that

?X: case, the hostname may keep its domain name, but it doesn't matter.

```

@if MYDOMAIN || mydomain
case "$myhostname" in
*.*)
dflt=`expr "X$myhostname" : "X[^\.]*\(\..*\)"`
myhostname=`expr "X$myhostname" : "X\([^\.]*\)\"`
echo "(Trimming domain name from host name--host name is now $myhostname)"
;;
*) case "$mydomain" in
")
?X:
?X: There is currently no way to say we do not want hostcat if mydomain is not
?X: used. One way to achieve that would be to put that code in a mydomain.U
?X: unit. However, we want to stick the sanity checks right after the domain
?X: name computation, or if none is done, right after the hostname computation.
?X:
{
?X: If we use NIS, try ypmatch.
test "X$hostcat" = "Xypcat hosts" &&
ypmatch "$myhostname" hosts 2>/dev/null \
$sed -e 's/[ ]*#.*//; s/$/ /' > hosts
&& \
$test -s hosts
} || {
?X: Extract only the relevant hosts, reducing file size,
?X: remove comments, insert trailing space for later use.
?X: Test to be sure we *have* a hostcat command. os390 doesn't.
test "X$hostcat" != "X" &&
$hostcat | $sed -n -e "s/[ ]*#.*//; s^\$/ /
/[ ]$myhostname[ . ]/p" > hosts
}
tmp_re="[ .]"
if $test -f hosts; then
$test x`$awk "/[0-9].*[ ]$myhostname$tmp_re/ { sum++ }
END { print sum }" hosts` = x1 || tmp_re="[ ]"
dflt=`$awk "/[0-9].*[ ]$myhostname$tmp_re/ {for(i=2; i<=NF;i++) print \\$i}" \
hosts | $sort | $uniq | \
$sed -n -e "s/$myhostname\.\([-a-zA-Z0-9_]\)\^1/p"`
case `$echo X$dflt` in
X*\ *) echo "(Several hosts in the database matched hostname)"
dflt=.
;;
X.) echo "(You do not have fully-qualified names in the hosts database)"
;;
esac
else
echo "(I cannot locate a hosts database anywhere)"
dflt=.
fi

```

```

case "$dflt" in
.)
tans=`./loc resolv.conf X /etc
/usr/etc`
if $test -f "$tans"; then
echo "(Attempting domain name extraction from $tans)"
?X: Look for either a search or a domain directive.
dflt=`$sed -n -e 's// /g' \
-e 's/^search *([ ]*).*/1/p' $tans \
-e 1q 2>/dev/null`
case "$dflt" in
.) dflt=`$sed -n -e 's// /g' \
-e 's/^domain *([ ]*).*/1/p' $tans \
-e 1q 2>/dev/null`
;;
esac
fi
;;
esac
case "$dflt" in
.) echo "(No help from resolv.conf either -- attempting clever guess)"
dflt=`sh -c domainname 2>/dev/null`
case "$dflt" in
") dflt='.';
.nis.*|.yp.*|.main.*) dflt=`echo $dflt | $sed -e 's/^\.[^.]*/^/`;
esac
;;
esac
case "$dflt${osname}" in
.os390) echo "(Attempting domain name extraction from //SYS1.TCPPARMS(TCPDATA))"
dflt=`awk '/^DOMAINORIGIN/ {print $2}' "//SYS1.TCPPARMS(TCPDATA)" 2>/dev/null`
;;
esac
case "$dflt" in
.) echo "(Lost all hope -- silly guess then)"
dflt='.nonet'
;;
esac
$rm
-f hosts
;;
*) dflt="$mydomain";
esac;;
esac
echo " "
rp="What is your domain name?"
./myread
tans="$ans"

```

```

case "$sans" in
") ;;
.*) ;;
*) tans=".stans";;
esac
mydomain="$stans"

: translate upper to lower if necessary
case "$mydomain" in
*[A-Z]*)
echo "(Normalizing case in your domain name)"
mydomain=`echo $mydomain | ./tr '[A-Z]' '[a-z]'`
;;
esac

@end

: a little sanity check here
case "$phostname" in
") ;;
*)
case ` $phostname | ./tr '[A-Z]' '[a-z]^` in
$myhostname$mydomain|$myhostname) ;;
*)
case "$phostname" in
sed*)
echo "(That doesn't agree with your whoami.h file, by the way.)"
;;
*)
echo "(That doesn't agree with your $phostname command, by the way.)"
;;
esac
;;
esac
;;
esac
;;
esac

```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/modified/myhostname.U
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 2009 H.Merijn Brand

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?MAKE:d_getnameinfo: Inlibc
?MAKE: -pick add \$@ %<
?S:d_getnameinfo:
?S: This variable conditionally defines the HAS_GETNAMEINFO symbol,
?S: which indicates to the C program that the getnameinfo() function
?S: is available.
?S:.
?C:HAS_GETNAMEINFO:
?C: This symbol, if defined, indicates that the getnameinfo() function
?C: is available for use.
?C:.
?H:#\$d_getnameinfo HAS_GETNAMEINFO /**/
?H:.
?LINT:set d_getnameinfo
: see if getnameinfo exists
set getnameinfo d_getnameinfo
eval \$inlibc

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_getnameinfo.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: h_sysfile.U 1 2006-08-24 12:32:52Z rmanfredi \$
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: \$Log: h_sysfile.U,v \$
?RCS: Revision 3.0 1993/08/18 12:08:13 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:h_sysfile: Nothing
?MAKE: -pick add \$@ %<
?S:h_sysfile:
?S: This is variable gets set in various places to tell i_sys_file that
?S: <sys/file.h> should be included.
?S:.
: Initialize h_sysfile
h_sysfile=false

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-

debian-perl-5.26.1/dist/U/h_sysfile.U

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: n.U 1 2006-08-24 12:32:52Z rmanfredi $
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: $Log: n.U,v $
?RCS: Revision 3.0 1993/08/18 12:09:19 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:n c: contains
?MAKE: -pick add $@ %<
?S:n:
?S: This variable contains the -n flag if that is what causes the echo
?S: command to suppress newline. Otherwise it is null. Correct usage is
?S: $echo $n "prompt for a question: $c".
?S:.
?S:c:
?S: This variable contains the \c string if that is what causes the echo
?S: command to suppress newline.
?S: Otherwise it is null. Correct usage is
?S: $echo $n "prompt for a question: $c".
?S:.
: first determine how to suppress newline on echo command
echo " "
echo "Checking echo to see how to suppress newlines..."
(echo "hi there\c" ; echo " ") >.echotmp
if $contains c .echotmp >/dev/null 2>&1 ; then
echo "...using -n."
n='-n'
c=""
else
cat <<'EOM'
...using \c
EOM
n=""
c='\c'
fi
echo $n "The star should be here-->$c"
echo '*'
rm -f .echotmp
```

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/n.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_setpgid.U 1 2006-08-24 12:32:52Z rmanfredi \$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic Licence,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic Licence; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: d_setpgid.U,v \$

?RCS: Revision 3.0.1.2 1997/02/28 15:41:49 ram

?RCS: patch61: reworded symbol comments

?RCS:

?RCS: Revision 3.0.1.1 1994/01/24 14:06:40 ram

?RCS: patch16: created

?RCS:

?RCS: Revision 3.0 1993/08/18 12:05:56 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?MAKE:d_setpgid: Inlibc

?MAKE: -pick add \$@ %<

?S:d_setpgid:

?S: This variable conditionally defines the HAS_SETPGID symbol if the

?S: setpgid(pid, gpid) function is

available to set process group ID.

?S:.

?C:HAS_SETPGID:

?C: This symbol, if defined, indicates that the setpgid(pid, gpid)

?C: routine is available to set process group ID.

?C:.

?H:#\$d_setpgid HAS_SETPGID /**/

?H:.

?LINT:set d_setpgid

: see if setpgid exists

set setpgid d_setpgid

eval \$inlibc

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/d_setpgid.U

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: i_math.U 1 2006-08-24 12:32:52Z rmanfredi $
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: Original Author: Andy Dougherty <doughera@lafcol.lafayette.edu>
?RCS:
?RCS: $Log: i_math.U,v $
?RCS: Revision 3.0.1.1 1994/08/29 16:21:59 ram
?RCS: patch32: created by ADO
?RCS:
?MAKE:i_math: Inhdr
?MAKE: -pick add $@ %<
?X: Are there really systems that *DON'T* have math.h?
?S:i_math:
?S: This variable conditionally defines the I_MATH symbol, and indicates
?S: whether a C program may include <math.h>.
?S:.
?C:I_MATH:
?C: This symbol, if defined, indicates
?C: to the C program that it should
?C: include <math.h>.
?C:.
?H:#$i_math I_MATH /**/
?H:.
?LINT:set i_math
: see if this is a math.h system
set math.h i_math
eval $inhdr
```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/i_math.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: Csym.U,v 3.0.1.4 1995/07/25 13:36:29 ram Exp $
?RCS:
?RCS: Copyright (c) 1991-1993, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
```

?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 3.0.
?RCS:
?RCS: \$Log: Csym.U,v \$
?RCS: Revision 3.0.1.4 1995/07/25 13:36:29 ram
?RCS: patch56: re-arranged compile line to include ldflags before objects
?RCS: patch56: added quotes for OS/2 support
?RCS:
?RCS: Revision 3.0.1.3 1995/05/12 12:00:33 ram
?RCS: patch54: fixed C test program to bypass gcc builtin type checks (ADO)
?RCS:
?RCS: Revision 3.0.1.2 1994/10/31 09:34:13 ram
?RCS: patch44: added Options to the MAKE line since it's no longer in Init.U
?RCS:
?RCS: Revision
3.0.1.1 1993/08/25 14:00:05 ram
?RCS: patch6: added ldflags as a conditional dependency and to compile line
?RCS: patch6: a final double quote was missing in csym variable after eval
?RCS:
?RCS: Revision 3.0 1993/08/18 12:04:50 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:Csym mistrustnm extern_C: Options contains libc libs runnm test \
+cc +optimize +ccflags +ldflags run nm_try_exe d_cplusplus
?MAKE: -pick add \$@ %<
?LINT:define csym
?LINT:use libc
?LINT:extern mistrustnm
?LINT:set mistrustnm
?S:csym:
?S: This shell variable is used internally by Configure to check
?S: whether a given C symbol is defined or not. A typical use is:
?S: set symbol result [-fva] [previous]
?S: eval \$csym
?S: That will set result to 'true' if the function [-f], variable [-v]
?S: or array [-a] is defined, 'false' otherwise. If a previous value is
?S: given and the -r flag was provided on the command line, that value
?S: is reused without questioning.
?S:.
?S:extern_C:
?S: ANSI C
requires 'extern' where C++ requires 'extern "C"'. This
?S: variable can be used in Configure to do the right thing.
?S:.
?S:mistrustnm:
?S: This variable can be used to establish a fallthrough for the cases
?S: where nm fails to find a symbol. If usernm is false or usernm is true

?S: and mistrustnm is false, this variable has no effect. If usernm is true
?S: and mistrustnm is "compile", a test program will be compiled to try to
?S: find any symbol that can't be located via nm lookup. If mistrustnm is
?S: "run", the test program will be run as well as being compiled.
?S:.
?V:csym
?T:tval tx tlook tf tdc
?F:!try
: is a C symbol defined?
csym='tlook=\$1;
case "\$3" in
-v) tf=libc.tmp; tdc="";;
-a) tf=libc.tmp; tdc="[]";;
*) tlook="^\\$1\\$"; tf=libc.list; tdc="()";;
esac;
case "\$d_cplusplus" in
\$define) extern_C="extern \"C\"";;
*) extern_C="extern";;
esac;
tx=yes;
case "\$reuseval-\$4" in
true-) ;;
true-*) tx=no; eval "tval=\\$4"; case "\$tval" in "") tx=yes;; esac;;
esac;
case
"\$tx" in
yes)
?X:
?X: Put symbol inside a printf to fool optimizing compilers...
?X:
?X: We use 'short' instead of 'int' to try to circumvent overzealous
?X: optimizing compilers using built-in prototypes for commonly used
?X: routines to complain when seeing a different external declaration. For
?X: instance, gcc 2.6.3 fails if we use 'int' and we attempt a test against
?X: memcpy() on machines where sizeof(int) == sizeof(char *) (the usual return
?X: type), the compiler assuming it's a built-in declaration given that the
?X: returned size matches. At least with 'short' we are safe! -- RAM, for ADO
?X:
?X: Let's thank GNU cc for making our lives so easy! :-)
?X: (An alternative for the future would be to use our knowledge about gcc
?X: to force a -fno-builtin option in the compile test, in case the 'short'
?X: trick is obsoleted by future gcc releases). -- RAM
?X:
tval=false;
if \$test "\$runnm" = true; then
if \$contains \$tlook \$tf >/dev/null 2>&1; then
tval=true;
elif \$test

```

"$mistrustnm" = compile -o "$mistrustnm" = run; then
  echo "$extern_C void *$1$tdc; void *(*(p()))$tdc { return &$1; } int main(int argc, char **argv) { if(p() && p() !=
(void *)argv[0]) return(0); else return(1); }"> try.c;
  $cc -o try $optimize $ccflags $ldflags try.c >/dev/null 2>&1 $libs && tval=true;
  $stest "$mistrustnm" = run -a -x try && { $run ./try$_exe >/dev/null 2>&1 || tval=false; };
  $rm_try;
fi;
else
  echo "$extern_C void *$1$tdc; void *(*(p()))$tdc { return &$1; } int main(int argc, char **argv) { if(p() && p() !=
(void *)argv[0]) return(0); else return(1); }"> try.c;
  $cc -o try $optimize $ccflags $ldflags try.c $libs >/dev/null 2>&1 && tval=true;
  $rm_try;
fi;
;;
*)
case "$tval" in
$define) tval=true;;
*) tval=false;;
esac;
;;
esac;
eval "$2=$tval"

```

Found in path(s):

```

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/compline/Csym.U

```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 2000 Jarkko Hietaniemi

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?MAKE:d_iconv: Inlibc

?MAKE: -pick add \$@ %<

?S:d_iconv:

?S: This variable conditionally defines the HAS_ICONV symbol, which

?S: indicates to the C program that the iconv() routine is available.

?S:.

?C:HAS_ICONV:

?C: This symbol, if defined, indicates that the iconv routine is

?C: available to do character set conversions.

?C:.

?H:#\$d_iconv HAS_ICONV /**/

?H:.

?LINT:set d_iconv

```
: see if iconv exists
set iconv d_iconv
eval $inlibc
```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/perl/d_iconv.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: d_mknod.U,v 3.0.1.1 1994/10/29 16:14:17 ram Exp $
?RCS:
?RCS: Copyright (c) 1998 Andy Dougherty
?RCS:
?RCS: You may distribute under the terms of either the GNU General Public
?RCS: License or the Artistic License, as specified in the README file.
?RCS:
?RCS: Original Author: Andy Dougherty <doughera@lafayette.edu>
?RCS:
?RCS: $Log: d_mknod.U,v $
?RCS:
?MAKE:d_mknod: Inlibc
?MAKE: -pick add $@ %<
?S:d_mknod:
?S: This variable conditionally defines the HAS_MKNOD symbol, which
?S: indicates to the C program that the mknod() routine is available.
?S:.
?C:HAS_MKNOD :
?C: This symbol, if defined, indicates that the mknod routine is
?C: available. If you just want to create FIFOs, you should try
?C: to use mkfifo instead. mknod might require super-user privileges.
?C:.
?H:#$d_mknod HAS_MKNOD /**/
?H:.
?LINT:set d_mknod
: see if mknod exists
set mknod d_mknod
eval $inlibc
```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/modified/d_mknod.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: man3dir.U,v 3.1 1999/07/08 20:52:19 doughera Exp doughera $
?RCS:
?RCS: Copyright (c) 1996-1999, Andy Dougherty
?RCS: Copyright (c) 1991-1993, Raphael Manfredi
?RCS:
```

?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 3.0.
?RCS:
?RCS: \$Log: man3dir.U,v \$
?RCS: Revision 3.1 1999/07/08 20:52:19 doughera
?RCS: Updated for perl5.005_5x
?RCS:
?RCS: Revision 3.0.1.1 1997/02/28 16:10:34 ram
?RCS: patch61: created
?RCS:
?X: This was originally specific to perl5. Since perl5 has man pages that
?X: go in both man1/ and man3/ directories, we need both man1dir
?X: and man3dir. This unit is basically dist's mansrc.U with
?X: man3 used instead
of man everywhere.
?X: I then added various tests because perl5 has *lots* of man3
?X: pages with long file names. -- ADO
?X:
?MAKE:man3dir man3direxp man3ext installman3dir: cat nroff Loc Oldconfig \
sed man1dir package package Getfile Setprefixvar Prefixit Prefixup \
d_flexfnam privlib Myread test
?MAKE: -pick add \$@ %<
?Y:TOP
?D:man3dir="
?S:man3dir:
?S: This variable contains the name of the directory in which manual
?S: source pages are to be put. It is the responsibility of the
?S: Makefile.SH to get the value of this into the proper command.
?S: You must be prepared to do the ~name expansion yourself.
?S:.
?D:man3direxp="
?S:man3direxp:
?S: This variable is the same as the man3dir variable, but is filename
?S: expanded at configuration time, for convenient use in makefiles.
?S:.
?D:installman3dir="
?S:installman3dir:
?S: This variable is really the same as man3direxp, unless you are using
?S: AFS in which case it points to the read/write location whereas
?S: man3direxp only
points to the read-only access location. For extra
?S: portability, you should only use this variable within your makefiles.
?S:.
?S:man3ext:
?S: This variable contains the extension that the manual page should

?S: have: one of 'n', 'l', or '3'. The Makefile must supply the '!.

?S: See man3dir.

?S:.

?T:prog tdfit

?LINT:change prefixvar

?LINT:set man3direxp

: determine where library module manual pages go

set man3dir man3dir none

eval \$prefixit

\$cat <<EOM

\$spackage has manual pages for many of the library modules.

EOM

case "\$nroff" in

nroff)

\$cat <<'EOM'

However, you don't have nroff, so they're probably useless to you.

EOM

case "\$man3dir" in

") man3dir="none";;

esac;;

esac

case "\$d_flexfnam" in

undef)

\$cat <<'EOM'

However, your system can't handle the long file names like File::Basename.3.

EOM

case "\$man3dir" in

") man3dir="none";;

esac;;

esac

echo "If you don't want the manual sources installed, answer 'none'."

?X: In 5.005_57 and earlier, I had the following notes:

?X:

We do not use /usr/local/man/man3 because some man programs will

?X: only show the /usr/local/man/man3 contents, and not the system ones,

?X: thus man less will show the perl module less.pm, but not the system

?X: less command. We might also conflict with Tcl man pages.

?X: However, something like /opt/perl/man/man3 is fine.

?X:

?X: However, opinion seems to be shifting such that 'man POSIX' ought

?X: to just work. -- Andy Dougherty July 8, 1999

?X:

?X: remove any trailing -3.0 or other version indication from \$package

prog=`echo \$package | \$sed 's/-[0-9.]*\$//`

```

case "$man3dir" in
") dflt=`echo "$man1dir" | $sed -e 's/man1/man3/g' -e 's/man\.1/man\.3/g`
if $test -d "$privlib/man/man3"; then
cat <<EOM >&4

```

WARNING: Previous versions of perl installed man3 pages into \$privlib/man/man3. This version will suggest a new default of \$dflt.

EOM

```

tdflt=$dflt
dflt='n'
rp='Do you wish to preserve the old behavior?(y/n)'
./myread
case "$ans" in
y*) dflt="$privlib/man/man3"
;;
*) dflt=$tdflt ;;
esac
fi
;;
*) dflt="$man3dir" ;;
esac
case "$dflt" in
' ') dflt=none ;;
esac
echo " "
fn=dn+~
rp="Where do the $package library man pages (source) go?"
./getfile
prefixvar=man3dir
./setprefixvar

case "$man3dir" in
") man3dir=' '
installman3dir=";;
esac

```

: What suffix to use on installed man pages

```

case "$man3dir" in
' ')
man3ext='0'
;;
*)
rp="What suffix should be used for the $package library man pages?"
case "$man3ext" in
") case "$man3dir" in
*3) dflt=3 ;;
*3p) dflt=3p ;;

```

```

*3pm) dflt=3pm ;;
*1) dflt=1;;
*n) dflt=n;;
*o) dflt=o;;
*p) dflt=p;;
*C) dflt=C;;
*L) dflt=L;;
*L3) dflt=L3;;
*) dflt=3;;
esac
;;
*) dflt="$man3ext";;
esac
./myread
man3ext="$ans"
;;
esac

```

Found in path(s):

```

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/installdirs/man3dir.U

```

No license file was found, but licenses were detected in source scan.

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?MAKE:d_tgamma: Inlibc

?MAKE: -pick add \$@ %<

?S:d_tgamma:

?S: This variable conditionally defines the HAS_TGAMMA symbol, which

?S: indicates to the C program that the tgamma() routine is available

?S: for the gamma function. See also d_lgamma.

?S:.

?C:HAS_TGAMMA:

?C: This symbol, if defined, indicates that the tgamma routine is

?C: available to do the gamma function. See also HAS_LGAMMA.

?C:.

?H:#\$d_tgamma HAS_TGAMMA /**/

?H:.

?LINT:set d_tgamma

: see if tgamma exists

set tgamma d_tgamma

eval \$inlibc

Found in path(s):

```

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/perl/d_tgamma.U

```

No license file was found, but licenses were detected in source scan.

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?MAKE:d_rint: Inlibc

?MAKE: -pick add \$@ %<

?S:d_rint:

?S: This variable conditionally defines the HAS_RINT symbol, which

?S: indicates to the C program that the rint() routine is available.

?S:.

?C:HAS_RINT:

?C: This symbol, if defined, indicates that the rint routine is

?C: available to return the nearest integral value to x as double

?C: using the current rounding mode.

?C:.

?H:#\$d_rint HAS_RINT /**/

?H:.

?LINT:set d_rint

: see if rint exists

set rint d_rint

eval \$inlibc

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_rint.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: i_assert.U,v \$

?RCS:

?RCS: Copyright (c) 2007 H.Merijn Brand

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?MAKE:i_assert: Inhdr Hasfield

?MAKE: -pick add \$@ %<

?S:i_assert:

?S: This variable conditionally defines the I_ASSERT symbol, which

?S: indicates to the C program that <assert.h> exists and could be

?S: included.

?S:.

?C:I_ASSERT:

?C: This symbol, if defined, indicates that <assert.h> exists and

?C: could be included by the C program to get the assert() macro.

?C:.

?H:#\$i_assert I_ASSERT /**/

?H:.

```
?LINT:set i_assert
: see if this is a assert.h system
set assert.h i_assert
eval $inhdr
```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/i_assert.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: modetype.U,v 3.0.1.1 1994/10/29 16:25:07 ram Exp $
?RCS:
?RCS: Copyright (c) 1991-1993, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 3.0.
?RCS:
?RCS: Original Author: Andy Dougherty <doughera@lafcol.lafayette.edu>
?RCS:
?RCS: $Log: modetype.U,v $
?RCS: Revision 3.0.1.1 1994/10/29 16:25:07 ram
?RCS: patch36: created by ADO
?RCS:
?MAKE:modetype: Myread Typedef
?MAKE: -pick add $@ %<
?S:modetype:
?S: This variable defines modetype to be something like mode_t,
?S: int, unsigned short, or whatever type is used to declare file
?S: modes for system calls.
?S:.
?C:Mode_t:
?C: This symbol holds the type used to declare
file modes
?C: for systems calls. It is usually mode_t, but may be
?C: int or unsigned short. It may be necessary to include <sys/types.h>
?C: to get any typedef'ed information.
?C:.
?H:#define Mode_t $modetype /* file mode parameter for system calls */
?H:.
?LINT:set modetype
: see what type is used for mode_t
rp="What is the type used for file modes for system calls (e.g. fchmod())?"
set mode_t modetype int stdio.h sys/types.h
eval $typedef_ask
```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/typedefs/modetype.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: d_xdrs.U 1 2006-08-24 12:32:52Z rmanfredi $
```

```
?RCS:
```

```
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
```

```
?RCS:
```

```
?RCS: You may redistribute only under the terms of the Artistic Licence,
```

```
?RCS: as specified in the README file that comes with the distribution.
```

```
?RCS: You may reuse parts of this distribution only within the terms of
```

```
?RCS: that same Artistic Licence; a copy of which may be found at the root
```

```
?RCS: of the source tree for dist 4.0.
```

```
?RCS:
```

```
?RCS: $Log: d_xdrs.U,v $
```

```
?RCS: Revision 3.0 1993/08/18 12:08:04 ram
```

```
?RCS: Baseline for dist 3.0 netwide release.
```

```
?RCS:
```

```
?MAKE:d_xdrs: cat Csym Setvar
```

```
?MAKE: -pick add $@ %<
```

```
?S:d_xdrs:
```

```
?S: This symbol conditionally defines HAS_XDRS which indicates to the C
```

```
?S: program that XDR serialization routines are available.
```

```
?S:.
```

```
?C:HAS_XDRS (XDRS):
```

```
?C: This symbol if defined indicates to the C program that the XDR
```

```
?C: serialization routines are available to transfer data
```

```
across
```

```
?C: various architectures.
```

```
?C:.
```

```
?H:#$d_xdrs HAS_XDRS /**/
```

```
?H:.
```

```
?LINT:set d_xdrs
```

```
: see if XDR is available
```

```
echo " "
```

```
if set xdr_int val -f d_xdrs; eval $csym; $val; then
```

```
echo "Ahh! You have XDR routines for network communications." >&4
```

```
val="$define"
```

```
else
```

```
$cat >&4 <<EOM
```

```
Sigh! You do not have XDR routines -- Network communications may be hazardous.
```

```
EOM
```

```
val="$undef"
```

```
fi
```

```
set d_xdrs
```

```
eval $setvar
```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/d_xdrs.U
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 2000, Jarkko Hietaniemi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 3.0.

?RCS:

?MAKE:Devel usedevel: Myread rsrc package

?MAKE: -pick wipe \$@ %<

?T:xversion

?X: waiver of rights

?S:usedevel:

?S: This variable indicates that Perl was configured with development

?S: features enabled. This should not be done for production builds.

?S:.

?C:PERL_USE_DEVEL:

?C: This symbol, if defined, indicates that Perl was configured with

?C: -Dusedevel, to enable development features. This should not be

?C: done for production builds.

?C:.

?H:#\$usedevel PERL_USE_DEVEL /**/

?H:.

?LINT:extern versiononly

?LINT:extern

installusrbinperl

?LINT:change versiononly

?LINT:change installusrbinperl

: See if we are using a devel version and want that

```
xversion=`awk '/define[ ]+PERL_VERSION/ {print $3}' $src/patchlevel.h`
```

```
case "$usedevel" in
```

```
$define|true|[yY]*)
```

```
    usedevel="$define" ;;
```

```
*) case "$xversion" in
```

```
    *[13579])
```

```
cat >&4 <<EOH
```

```
*** WHOA THERE!!! ***
```

This is an UNSTABLE DEVELOPMENT release.

The version of this \$package distribution is \$xversion, that is, odd,

(as opposed to even) and that signifies a development release.

If you want a maintenance release, you want an even-numbered version.

Do *****NOT***** install this into production use.
Data corruption and crashes are possible.

It is most seriously suggested that you do not continue any further unless you want to help in developing and debugging Perl.

If you **still** want to build perl, you can answer 'y' now, or pass `-Dusedevel` to Configure.

EOH

```
rp='Do you really want to continue?'
dflt='n'
. ./myread
case
"$ans" in
[yY]) echo >&4 "Okay, continuing."
      usedevel="$define" ;;
*) echo >&4 "Okay, bye."
   exit 1
   ;;
esac
;;
esac
usedevel="$undef"
;;
esac
case "$usedevel" in
$define|true|[yY]*)
case "$versiononly" in
") versiononly="$define" ;;
esac
case "$installusrbinperl" in
") installusrbinperl="$undef" ;;
esac
;;
esac
```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/perl/Devel.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: Getfile.U 1 2006-08-24 12:32:52Z rmanfredi $
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
```

?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: \$Log: Getfile.U,v \$
?RCS: Revision 3.0.1.7 1997/02/28 15:01:06 ram
?RCS: patch61: getfile script now begins with "startsh"
?RCS:
?RCS: Revision 3.0.1.6 1995/02/15 14:11:00 ram
?RCS: patch51: was not working if ~'s allowed with d_portable on (WED)
?RCS:
?RCS: Revision 3.0.1.5 1995/01/11 15:11:25 ram
?RCS: patch45: added support for escaping answers to skip various checks
?RCS: patch45: modified message issued after file expansion
?RCS:
?RCS: Revision
3.0.1.4 1994/10/29 15:53:19 ram
?RCS: patch36: added ?F: line for metalint file checking
?RCS:
?RCS: Revision 3.0.1.3 1994/05/06 14:23:36 ram
?RCS: patch23: getfile could be confused by file name in "locate" requests
?RCS: patch23: new 'p' directive to assume file is in people's path (WED)
?RCS:
?RCS: Revision 3.0.1.2 1994/01/24 14:01:31 ram
?RCS: patch16: added metalint hint on changed 'ans' variable
?RCS:
?RCS: Revision 3.0.1.1 1993/09/13 15:46:27 ram
?RCS: patch10: minor format problems and misspellings fixed
?RCS: patch10: now performs from package dir and not from UU subdir
?RCS:
?RCS: Revision 3.0 1993/08/18 12:04:56 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?X:
?X: This unit produces a bit of shell code that must be dotted in in order
?X: to get a file name and make some sanity checks. Optionally, a ~name
?X: expansion is performed.
?X:
?X: To use this unit, \$rp and \$dflt must hold the question and the
?X: default answer, which will be passed as-is
to the myread script.
?X: The \$fn variable must hold the file type (f or d, for file/directory).
?X: If \$gfpth is set to a list of space-separated list of directories,
?X: those are prefixes for the filename. Unless \$gfpthkeep is set to 'y',
?X: gfpth is cleared on return from Getfile.
?X:

?X: If is is followed by a ~, then ~name substitution will occur. Upon return,
?X: \$ans is set with the filename value. If a / is specified, then only a full
?X: path name is accepted (but ~ substitution occurs before, if needed). The
?X: expanded path name is returned in that case.
?X:
?X: If a + is specified, the existence checks are skipped. This usually means
?X: the file/directory is under the full control of the program.
?X:
?X: If the 'n' (none) type is used, then the user may answer none.
?X: The 'e' (expand) switch may be used to bypass d_portable, expanding ~name.
?X:
?X: If the 'l' (locate) type is used, then it must end with a ':' and then a
?X: file name. If the answer is a directory,
the file name will be appended
?X: before testing for file existence. This is useful in locate-style
?X: questions like "where is the active file?". In that case, one should
?X: use:
?X:
?X: dflt='~news/lib'
?X: fn='l~:active'
?X: rp='Where is the active file?'
?X: ./getfile
?X: active="\$ans"
?X:
?X: If the 'p' (path) letter is specified along with 'l', then an answer
?X: without a leading / will be expected to be found in everyone's path.
?X:
?X: It is also possible to include a comma-separated list of items within
?X: parentheses to specify which items should be accepted as-is with no
?X: further checks. This is useful when for instance a full path is expected
?X: but the user may escape out via "magical" answers.
?X:
?X: If the answer to the question is 'none', then the existence checks are
?X: skipped and the empty string is returned.
?X:
?MAKE:Getfile: d_portable contains startsh Myread Filexp tr trnl
?MAKE: -pick add \$@ %<
?V:ansexp:fn gfpth gfpthkeep
?F:./getfile
?T:tilde
type what orig_rp orig_dflt fullpath already redo skip none_ok \
value exp_file nopath_ok loc_file fp pf dir direxp
?LINT:change ans
?LINT:change gfpth
: now set up to get a file name
cat <<EOS >getfile
\$startsh
EOS

```

cat <<'EOSC' >>getfile
tilde=""
fullpath=""
already=""
skip=""
none_ok=""
exp_file=""
nopath_ok=""
orig_rp="$rp"
orig_dflt="$dflt"
case "$gfpth" in
") gfpth='.' ;;
esac

```

?X: Begin by stripping out any (...) grouping.

```

case "$fn" in
*\(*)
: getfile will accept an answer from the comma-separated list
: enclosed in parentheses even if it does not meet other criteria.
expr "$fn" : '.*(\(.*\)).*' | $tr ',' $trnl >getfile.ok
fn=`echo $fn | sed 's/(.*)/`
;;
esac

```

?X: Catch up 'locate' requests early, so that we may strip the file name

?X: before looking at the one-letter commands, in case the file name contains

?X: one of them. Reported by Wayne Davison <davison@borland.com>.

```

case "$fn" in
*.*)
loc_file=`expr $fn : '.*:(.*)`
fn=`expr $fn : \"(.*)\".*`
;;
esac

```

```

case
"$fn" in
*~*) tilde=true;;
esac
case "$fn" in
*/*) fullpath=true;;
esac
case "$fn" in
*+*) skip=true;;
esac
case "$fn" in
*n*) none_ok=true;;
esac
case "$fn" in

```

```

*e*) exp_file=true;;
esac
case "$fn" in
*p*) nopath_ok=true;;
esac

case "$fn" in
*f*) type='File';;
*d*) type='Directory';;
*l*) type='Locate';;
esac

what="$type"
case "$what" in
Locate) what='File';;
esac

case "$exp_file" in
")
case "$d_portable" in
"$define") ;;
*) exp_file=true;;
esac
;;
esac

cd ..
while test "$type"; do
redo="
rp="$orig_rp"
dflt="$orig_dflt"
case "$tilde" in
true) rp="$rp (~name ok)";;
esac
. UU/myread
?X: check for allowed escape sequence which may be accepted verbatim.
if test -f UU/getfile.ok && \
$contains "^$ans$" UU/getfile.ok >/dev/null 2>&1
then
value="$ans"
ansexp="$ans"
break
fi
case "$ans" in
none)
value="
ansexp="
case "$none_ok" in

```

```

true) type="";
esac
;;
*)
case "$tilde" in
") value="$ans"
  ansexp="$ans";;
*)
value=`UU/filexp $ans`
case
$? in
0)
  if test "$ans" != "$value"; then
    echo "(That expands to $value on this system.)"
  fi
  ;;
*) value="$ans";;
esac
ansexp="$value"
case "$exp_file" in
") value="$ans";;
esac
;;
esac
case "$fullpath" in
true)
?X: Perform all the checks on ansexp and not value since when d_portable
?X: is defined, the original un-expanded answer which is stored in value
?X: would lead to "non-existent" error messages whilst ansexp has been
?X: properly expanded. -- Fixed by Jan.Djarv@sa.erisoft.se (Jan Djarv)
?X: Always expand ~user if '/' was requested
  case "$sansexp" in
  /*) value="$sansexp" ;;
?X: Allow for c:/some/path
  [a-zA-Z]/*) value="$sansexp" ;;
  *)
  redo=true
  case "$already" in
  true)
    echo "I shall only accept a full path name, as in /bin/lS." >&4
    echo "Use a ! shell escape if you wish to check pathnames." >&4
    ;;
  *)
    echo "Please give a full path name, starting with slash." >&4
    case "$tilde"
in
  true)
    echo "Note that using ~name is ok provided it expands well." >&4

```

```

    already=true
    ;;
  esac
esac
;;
esac
;;
esac
case "$redo" in
")
  case "$type" in
  File)
    for fp in $gfpth; do
      if test "X$fp" = X.; then
        pf="$ansexp"
      else
        pf="$fp/$ansexp"
      fi
      if test -f "$pf"; then
        type="
      elif test -r "$pf" || (test -h "$pf") >/dev/null 2>&1
      then
        echo "($value is not a plain file, but that's ok.)"
        type="
      fi
      if test X"$type" = X; then
        value="$pf"
        break
      fi
    done
    ;;
  Directory)
    for fp in $gfpth; do
      if test "X$fp" = X.; then
        dir="$ans"
        direxp="$ansexp"
      else
        dir="$fp/$ansexp"
        direxp="$fp/$ansexp"
      fi
      if test -d "$direxp"; then
        type="
        value="$dir"
        break
      fi
    done
    ;;
  Locate)

```

```

if test -d "$ansexp"; then
  echo "(Looking for $loc_file in directory
$value.)"
  value="$value/$loc_file"
  ansexp="$ansexp/$loc_file"
fi
if test -f "$ansexp"; then
  type="
fi
case "$nopath_ok" in
true) case "$value" in
*/*) ;;
*) echo "Assuming $value will be in people's path."
type="
;;
esac
;;
esac
;;
esac
;;
esac

case "$skip" in
true) type=";
esac

case "$type" in
") ;;
*)
if test "$fastread" = yes; then
  dflt=y
else
  dflt=n
fi
rp="$what $value doesn't exist. Use that name anyway?"
. UU/myread
dflt="
case "$ans" in
y*) type=";;
*) echo " ";;
esac
;;
esac
;;
esac
;;
esac
done
cd UU

```

```
ans="$value"  
rp="$orig_rp"  
dflt="$orig_dflt"  
rm -f getfile.ok  
test "X$gfpthkeep" != Xy && gfpth=""  
EOSC
```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-  
debian-perl-5.26.1/dist/U/Getfile.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: d_memcpy.U 1 2006-08-24 12:32:52Z rmanfredi $  
?RCS:  
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi  
?RCS:  
?RCS: You may redistribute only under the terms of the Artistic Licence,  
?RCS: as specified in the README file that comes with the distribution.  
?RCS: You may reuse parts of this distribution only within the terms of  
?RCS: that same Artistic Licence; a copy of which may be found at the root  
?RCS: of the source tree for dist 4.0.  
?RCS:  
?RCS: $Log: d_memcpy.U,v $  
?RCS: Revision 3.0.1.1 1993/09/13 16:02:58 ram  
?RCS: patch10: removed text recommending bcopy over memcpy (WAD)  
?RCS:  
?RCS: Revision 3.0 1993/08/18 12:06:34 ram  
?RCS: Baseline for dist 3.0 netwide release.  
?RCS:  
?MAKE:d_memcpy: Inlibc  
?MAKE:-pick add $@ %<  
?S:d_memcpy:  
?S: This variable conditionally defines the HAS_MEMCPY symbol, which  
?S: indicates to the C program that the memcpy() routine is available  
?S: to copy blocks of  
memory.  
?S:.  
?C:HAS_MEMCPY (MEMCPY):  
?C: This symbol, if defined, indicates that the memcpy routine is available  
?C: to copy blocks of memory.  
?C:.  
?H:#$d_memcpy HAS_MEMCPY /**/  
?H:.  
?LINT:set d_memcpy  
: see if memcpy exists  
set memcpy d_memcpy  
eval $inlibc
```

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/d_memcpy.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: sig_name.U,v \$

?RCS: Revision 3.0.1.5 1997/02/28 16:21:25 ram

?RCS: patch61: brand new algorithm for sig_name and (new!) sig_num

?RCS:

?RCS: Revision 3.0.1.4 1995/07/25 14:14:54 ram

?RCS: patch56: added <asm/signal.h> lookup for linux

?RCS:

?RCS: Revision 3.0.1.3 1995/05/12 12:24:11 ram

?RCS: patch54: now looks for <linux/signal.h> too (ADO)

?RCS:

?RCS: Revision 3.0.1.2 1994/06/20 07:06:57 ram

?RCS: patch30: final echo was missing to close awk-printed string

?RCS:

?RCS: Revision 3.0.1.1

1994/05/06 15:17:55 ram

?RCS: patch23: signal list now formatted to avoid scroll-ups (ADO)

?RCS:

?RCS: Revision 3.0 1993/08/18 12:09:47 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?MAKE:sig_name sig_name_init sig_num sig_num_init sig_count sig_size: \

awk Signal Oldconfig rm

?MAKE: -pick add \$@ %<

?S:sig_name:

?S: This variable holds the signal names, space separated. The leading

?S: SIG in signal name is removed. A ZERO is prepended to the

?S: list. This is currently not used.

?S:.

?S:sig_name_init:

?S: This variable holds the signal names, enclosed in double quotes and

?S: separated by commas, suitable for use in the SIG_NAME definition

?S: below. A "ZERO" is prepended to the list, and the list is

?S: terminated with a plain 0. The leading SIG in signal names

?S: is removed. See sig_num.

?S:.

?S:sig_num:

?S: This variable holds the signal numbers, space separated. A ZERO is

?S: prepended to the list (corresponding to the fake SIGZERO), and

?S: the list is terminated

with a 0. Those numbers correspond to

?S: the value of the signal listed in the same place within the

?S: sig_name list.

?S:.

?S:sig_num_init:

?S: This variable holds the signal numbers, enclosed in double quotes and

?S: separated by commas, suitable for use in the SIG_NUM definition

?S: below. A "ZERO" is prepended to the list, and the list is

?S: terminated with a plain 0.

?S:.

?S:sig_count (sig_name.U):

?S: This variable holds a number larger than the largest valid

?S: signal number. This is usually the same as the NSIG macro.

?S:.

?S:sig_size:

?S: This variable contains the number of elements of the sig_name

?S: and sig_num arrays, excluding the final NULL entry.

?S:.

?C:SIG_NAME:

?C: This symbol contains a list of signal names in order of

?C: signal number. This is intended

?C: to be used as a static array initialization, like this:

?C: char *sig_name[] = { SIG_NAME };

?C: The signals in the list are separated with commas, and each signal

?C: is surrounded by double

quotes. There is no leading SIG in the signal

?C: name, i.e. SIGQUIT is known as "QUIT".

?C: Gaps in the signal numbers (up to NSIG) are filled in with NUMnn,

?C: etc., where nn is the actual signal number (e.g. NUM37).

?C: The signal number for sig_name[i] is stored in sig_num[i].

?C: The last element is 0 to terminate the list with a NULL. This

?C: corresponds to the 0 at the end of the sig_num list.

?C:.

?C:SIG_NUM:

?C: This symbol contains a list of signal numbers, in the same order as the

?C: SIG_NAME list. It is suitable for static array initialization, as in:

?C: int sig_num[] = { SIG_NUM };

?C: The signals in the list are separated with commas, and the indices

?C: within that list and the SIG_NAME list match, so it's easy to compute

?C: the signal name from a number or vice versa at the price of a small

?C: dynamic linear lookup.

?C: Duplicates are allowed, but are moved to the end of the list.

?C: The signal number corresponding to sig_name[i] is sig_number[i].

?C: if (i

< NSIG) then sig_number[i] == i.

?C: The last element is 0, corresponding to the 0 at the end of

?C: the sig_name list.

?C:.

?C:SIG_COUNT:

?C: This variable contains a number larger than the largest

?C: signal number. This is usually the same as the NSIG macro.

?C:.

?C:SIG_SIZE:

?C: This variable contains the number of elements of the sig_name

?C: and sig_num arrays, excluding the final NULL entry.

?C:.

?H:#define SIG_NAME \$sig_name_init /**/

?H:#define SIG_NUM \$sig_num_init /**/

?H:#define SIG_COUNT \$sig_count /**/

?H:#define SIG_SIZE \$sig_size /**/

?H:.

?T:i doinit

?F:!= !signal_cmd

?X: signal.cmd creates a file signal.lst which has two columns:

?X: NAME number, e.g.

?X: HUP 1

?X: The list is sorted on signal number, with duplicates moved to

?X: the end..

: generate list of signal names

echo " "

case "\$sig_name_init" in

") doinit=yes ;;

*) case "\$sig_num_init" in

"|*,*) doinit=yes ;;

esac ;;

esac

case "\$doinit" in

yes)

echo "Generating a list of signal names and

numbers..." >&4

./signal_cmd

sig_count=`\$awk '/^NSIG/ { printf "%d", \$2 }' signal.lst`

sig_name=`\$awk 'BEGIN { printf "ZERO " }

!/^NSIG/ { printf "%s ", \$1 }' signal.lst`

sig_num=`\$awk 'BEGIN { printf "0 " }

!/^NSIG/ { printf "%d ", \$2 }' signal.lst`

sig_name_init=`\$awk 'BEGIN { printf "\"ZERO\", " }

!/^NSIG/ { printf "\"%s\", ", \$1 }

END { printf "0\n" }' signal.lst`

sig_num_init=`\$awk 'BEGIN { printf "0, " }

```

    !/^NSIG/ { printf "%d, ", $2}
    END { printf "0\n"}' signal.lst`
;;
esac
echo "The following $sig_count signals are available:"
echo " "
echo $sig_name | $awk \
'BEGIN { linelen = 0 }
{
for (i = 1; i <= NF; i++) {
name = "SIG" $i " "
linelen = linelen + length(name)
if (linelen > 70) {
printf "\n"
linelen = length(name)
}
printf "%s", name
}
printf "\n"
}'
sig_size=`echo $sig_name | awk '{print NF}'`
$rm -f signal.signal.c signal.awk signal.lst signal_cmd

```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/sig_name.U
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 2000 Jarkko Hietaniemi

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?MAKE:d_isinfl: Inlibc

?MAKE: -pick add \$@ %<

?S:d_isinfl:

?S: This variable conditionally defines the HAS_ISINFL symbol, which

?S: indicates to the C program that the isinfl() routine is available.

?S:.

?C:HAS_ISINFL:

?C: This symbol, if defined, indicates that the isinfl routine is

?C: available to check whether a long double is an infinity.

?C:.

?H:#\$d_isinfl HAS_ISINFL /**/

?H:.

?LINT:set d_isinfl

```
: see if isinfl exists
set isinfl d_isinfl
eval $inlibc
```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/perl/d_isinfl.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: d_endsent.U,v 3.0 1993/08/18 12:06:09 ram Exp $
```

```
?RCS:
```

```
?RCS: Copyright (c) 1991-1993, Raphael Manfredi
```

```
?RCS:
```

```
?RCS: You may redistribute only under the terms of the Artistic License,
```

```
?RCS: as specified in the README file that comes with the distribution.
```

```
?RCS: You may reuse parts of this distribution only within the terms of
```

```
?RCS: that same Artistic License; a copy of which may be found at the root
```

```
?RCS: of the source tree for dist 3.0.
```

```
?RCS:
```

```
?RCS: $Log: d_endsent.U,v $
```

```
?RCS: Revision 3.0 1993/08/18 12:06:09 ram
```

```
?RCS: Baseline for dist 3.0 netwide release.
```

```
?RCS:
```

```
?MAKE:d_endsent: Inlibc
```

```
?MAKE: -pick add $@ %<
```

```
?S:d_endsent:
```

```
?S: This variable conditionally defines HAS_ENDSERVENT if endservent() is
```

```
?S: available to close whatever was being used for service queries.
```

```
?S:.
```

```
?C:HAS_ENDSERVENT:
```

```
?C: This symbol, if defined, indicates that the endservent() routine is
```

```
?C: available to close whatever was being used for
```

```
service queries.
```

```
?C:.
```

```
?H:#$d_endsent HAS_ENDSERVENT /**/
```

```
?H:.
```

```
?LINT:set d_endsent
```

```
: see if endservent exists
```

```
set endservent d_endsent
```

```
eval $inlibc
```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/modified/d_endsent.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id$
```

```
?RCS:
```

?RCS: Copyright (c) 1999 Jarkko Hietaniemi

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?MAKE:d_msghdr_s: Hasstruct i_systypes d_socket i_sysuio Setvar

?MAKE: -pick add \$@ %<

?S:d_msghdr_s:

?S: This variable conditionally defines the HAS_STRUCTURE_MSGHDR symbol,

?S: which indicates that the struct msghdr is supported.

?S:.

?C:HAS_STRUCTURE_MSGHDR:

?C: This symbol, if defined, indicates that the struct msghdr

?C: is supported.

?C:.

?H:#\$d_msghdr_s HAS_STRUCTURE_MSGHDR /**/

?H:.

?LINT:set d_msghdr_s

: Check for msghdr_s

echo " "

echo "Checking to see if your system supports struct msghdr..." >&4

set d_msghdr_s msghdr \$i_systypes sys/types.h \$d_socket sys/socket.h \$i_sysuio sys/uio.h

eval \$hasstruct

case "\$d_msghdr_s" in

"\$define") echo "Yes, it does." ;;

*) echo "No, it doesn't."

;;

esac

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_msghdr_s.U

No license file was found, but licenses were detected in source scan.

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?MAKE:d_newlocale d_freelocale d_uselocale d_duplocale d_querylocale i_xlocale: Inlibc Inhdr

?MAKE: -pick add \$@ %<

?S:d_newlocale:

?S: This variable conditionally defines the HAS_NEWLOCALE symbol, which

?S: indicates to the C program that the newlocale() routine is available

?S: to return a new locale object or modify an existing locale object.

?S:.

?S:d_freelocale:

?S: This variable conditionally defines the HAS_FREELOCALE symbol, which

?S: indicates to the C program that the freelocale() routine is available

?S: to deallocate the resources associated with a locale object.

?S:
?S:d_uselocale:
?S: This variable conditionally defines the HAS_USELOCALE symbol, which
?S: indicates to the C program that the uselocale() routine is available
?S: to set the current locale
for the calling thread.
?S:
?S:d_duplocale:
?S: This variable conditionally defines the HAS_DUPLOCALE symbol, which
?S: indicates to the C program that the duplocale() routine is available
?S: to duplicate a locale object.
?S:
?S:d_querylocale:
?S: This variable conditionally defines the HAS_QUERYLOCALE symbol, which
?S: indicates to the C program that the querylocale() routine is available
?S: to return the name of the locale for a category mask.
?S:
?S:i_xlocale:
?S: This symbol, if defined, indicates to the C program that it should
?S: include <xlocale.h> to get uselocale() and its friends
?S:
?C:HAS_NEWLOCALE:
?C: This symbol, if defined, indicates that the newlocale routine is
?C: available to return a new locale object or modify an existing
?C: locale object.
?C:
?C:HAS_FREELOCALE:
?C: This symbol, if defined, indicates that the freelocale routine is
?C: available to deallocate the resources associated with a locale object.
?C:
?C:HAS_USELOCALE:
?C: This symbol, if defined,
indicates that the uselocale routine is
?C: available to set the current locale for the calling thread.
?C:
?C:HAS_DUPLOCALE:
?C: This symbol, if defined, indicates that the duplocale routine is
?C: available to duplicate a locale object.
?C:
?C:HAS_QUERYLOCALE:
?C: This symbol, if defined, indicates that the querylocale routine is
?C: available to return the name of the locale for a category mask.
?C:
?C:I_XLOCALE:
?C: This symbol, if defined, indicates to the C program that it should
?C: include <xlocale.h> to get uselocale() and its friends.
?C:
?H:#\$d_newlocale HAS_NEWLOCALE /**/

```
?H:#$d_freelocale HAS_FREELOCALE /**/  
?H:#$d_uselocale HAS_USELOCALE /**/  
?H:#$d_duplocale HAS_DUPLOCALE /**/  
?H:#$d_querylocale HAS_QUERYLOCALE /**/  
?H:#$i_xlocale I_XLOCALE /**/
```

?H:.

```
?LINT:set i_xlocale
```

```
?LINT:set d_newlocale
```

```
?LINT:set d_freelocale
```

```
?LINT:set d_uselocale
```

```
?LINT:set d_duplocale
```

```
?LINT:set d_querylocale
```

```
: see if this is an xlocale.h system
```

```
set xlocale.h i_xlocale
```

```
eval $inhdr
```

:

```
see if newlocale exists
```

```
set newlocale d_newlocale
```

```
eval $inlibc
```

```
: see if freelocale exists
```

```
set freelocale d_freelocale
```

```
eval $inlibc
```

```
: see if uselocale exists
```

```
set uselocale d_uselocale
```

```
eval $inlibc
```

```
: see if duplocale exists
```

```
set duplocale d_duplocale
```

```
eval $inlibc
```

```
: see if querylocale exists
```

```
set querylocale d_querylocale
```

```
eval $inlibc
```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-  
debian-perl-5.26.1/U/perl/d_newlocale.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id$
```

```
?RCS:
```

```
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
```

```
?RCS:
```

```
?RCS: You may redistribute only under the terms of the Artistic License,
```

```
?RCS: as specified in the README file that comes with the distribution.
```

?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: \$Log: i_pwd.U,v \$
?RCS: Revision 3.0.1.2 1995/07/25 14:10:57 ram
?RCS: patch56: use setvar so hint file values can override our guesses (ADO)
?RCS:
?RCS: Revision 3.0.1.1 1994/05/06 15:03:27 ram
?RCS: patch23: had forgotten cppminus in cppstd in test (ADO)
?RCS:
?RCS: Revision 3.0 1993/08/18 12:08:25 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?X:
?X: This unit checks whether there is a pwd system or not
?X:
?MAKE:i_pwd d_pwquota d_pwage d_pwchange d_pwclass d_pwexpire d_pwcomment:
\
contains rm cppstd in cppflags cppminus Inhdr Findhdr Setvar
?MAKE: -pick add \$@ %<
?S:i_pwd:
?S: This variable conditionally defines I_PWD, which indicates
?S: to the C program that it should include <pwd.h>.
?S:.
?S:d_pwquota:
?S: This variable conditionally defines PWQUOTA, which indicates
?S: that struct passwd contains pw_quota.
?S:.
?S:d_pwage:
?S: This variable conditionally defines PWAGE, which indicates
?S: that struct passwd contains pw_age.
?S:.
?S:d_pwchange:
?S: This variable conditionally defines PWCHANGE, which indicates
?S: that struct passwd contains pw_change.
?S:.
?S:d_pwclass:
?S: This variable conditionally defines PWCLASS, which indicates
?S: that struct passwd contains pw_class.
?S:.
?S:d_pwexpire:
?S: This variable conditionally defines PWEXPIRE, which indicates
?S: that struct passwd contains pw_expire.
?S:.
?S:d_pwcomment:
?S: This variable conditionally defines PWCOMMENT, which indicates
?S: that struct passwd contains pw_comment.

```

?S:.
?C:I_PWD:
?C: This symbol,
    if defined, indicates to the C program that it should
?C: include <pwd.h>.
?C:.
?C:PWQUOTA:
?C: This symbol, if defined, indicates to the C program that struct passwd
?C: contains pw_quota.
?C:.
?C:PWAGE:
?C: This symbol, if defined, indicates to the C program that struct passwd
?C: contains pw_age.
?C:.
?C:PWCHANGE:
?C: This symbol, if defined, indicates to the C program that struct passwd
?C: contains pw_change.
?C:.
?C:PWCLASS:
?C: This symbol, if defined, indicates to the C program that struct passwd
?C: contains pw_class.
?C:.
?C:PWEXPIRE:
?C: This symbol, if defined, indicates to the C program that struct passwd
?C: contains pw_expire.
?C:.
?C:PWCOMMENT:
?C: This symbol, if defined, indicates to the C program that struct passwd
?C: contains pw_comment.
?C:.
?H:#$i_pwd I_PWD /**/
?H:#$d_pwquota PWQUOTA /**/
?H:#$d_pwage PWAGE /**/
?H:#$d_pwchange PWCHANGE /**/
?H:#$d_pwclass PWCLASS /**/
?H:#$d_pwexpire PWEXPIRE /**/
?H:#$d_pwcomment PWCOMMENT /**/
?H:.
?LINT: set i_pwd d_pwquota
    d_pwage d_pwchange d_pwclass d_pwexpire d_pwcomment
?T:xxx
: see if this is a pwd.h system
set pwd.h i_pwd
eval $inhdr

case "$i_pwd" in
$define)
xxx=`./findhdr pwd.h`

```

```
$cppstdin $cppflags $cppminus < $xxx >$.h
```

```
if $contains 'pw_quota' $.h >/dev/null 2>&1; then  
  val="$define"  
else  
  val="$undef"  
fi  
set d_pwquota  
eval $setvar
```

```
if $contains 'pw_age' $.h >/dev/null 2>&1; then  
  val="$define"  
else  
  val="$undef"  
fi  
set d_pwage  
eval $setvar
```

```
if $contains 'pw_change' $.h >/dev/null 2>&1; then  
  val="$define"  
else  
  val="$undef"  
fi  
set d_pwchange  
eval $setvar
```

```
if $contains 'pw_class' $.h >/dev/null 2>&1; then  
  val="$define"  
else  
  val="$undef"  
fi  
set d_pwclass  
eval $setvar
```

```
if $contains 'pw_expire' $.h >/dev/null 2>&1; then  
  val="$define"  
else  
  val="$undef"  
fi  
set d_pwexpire  
eval $setvar
```

```
if $contains 'pw_comment' $.h >/dev/null 2>&1; then  
  val="$define"  
else  
  val="$undef"  
fi  
set d_pwcomment
```

```

eval $setvar

$rm -f $$h
;;
*)
val="$undef";
set
d_pwquota; eval $setvar
set d_pwage; eval $setvar
set d_pwchange; eval $setvar
set d_pwclass; eval $setvar
set d_pwexpire; eval $setvar
set d_pwcomment; eval $setvar
;;
esac

```

Found in path(s):

```

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/i_pwd.U

```

No license file was found, but licenses were detected in source scan.

```

?RCS: $Id: Extract.U,v 3.0.1.2 1997/02/28 14:58:52 ram Exp $
?RCS:
?RCS: Copyright (c) 1991-1993, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 3.0.
?RCS:
?RCS: $Log: Extract.U,v $
?RCS: Revision 3.0.1.2 1997/02/28 14:58:52 ram
?RCS: patch61: added support for src.U
?RCS:
?RCS: Revision 3.0.1.1 1994/10/29 15:51:46 ram
?RCS: patch36: added ?F: line for metalint file checking
?RCS:
?RCS: Revision 3.0 1993/08/18 12:04:52 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?X:
?X: This unit produces a shell script which can be doted in order to extract
?X: .SH files with variable substitutions.
?X:
?X: When running
Configure from a remote directory ($src is not '.'),
?X: then the files will be created in that directory, so beware!

```

```

?X:
?MAKE:Extract: src
?MAKE: -pick add $@ %<
?F:./extract
?T:PERL_CONFIG_SH dir file name create mkdir_p
: script used to extract .SH files with variable substitutions
cat >extract <<'EOS'
PERL_CONFIG_SH=true
echo "Doing variable substitutions on .SH files..."
if test -f MANIFEST; then
  set x `awk '{print $1}' < MANIFEST | grep \.SH$`
else
  echo "(Looking for .SH files under the source directory.)"
  set x `(cd "$src"; find . -name "*.SH" -print)`
fi
shift
case $# in
0) set x `(cd "$src"; echo *.SH)`; shift;;
esac
if test ! -f "$src/$1"; then
  shift
fi
?X: script to emulate mkdir -p
mkdir_p='
name=$1;
create="";
while test $name; do
if test ! -d "$name"; then
  create="$name $create";
  name=`echo $name | sed -e "s|^[^/]*$||"`;
  name=`echo $name | sed -e "s|(.*).*/.*|1|"`;
else
  name="";
fi;
done;
for file in $create; do
  mkdir $file;
done
'
for file in $*;
do
case "$src" in
".")
case "$file" in
*/*)
  dir=`expr X$file : 'X\(.*)/'`
  file=`expr X$file : 'X.*\^(.*)'`
  (cd "$dir" && ./$file)

```

```

;;
*)
./$file
;;
esac
;;
*)
?X:
?X: When running Configure remotely ($src is not '.'), we cannot source
?X: the files directly, since that would wrongly cause the extraction
?X: where the source lie instead of withing the current directory. Therefore,
?X: we need to 'sh <file' then, which is okay since they will source the
?X: existing config.sh file. It's not possible to use:
?X: ../src/Configure -S -O -Dsomething
?X: unfortunately since no new config.sh with the -Dsomething override
?X: will be created before running the .SH files. A minor buglet.
?X:
?X: Note that we must create the directory hierarchy ourselves if it does
?X: not exist already, and that is done through a shell emulation of the
?X: 'mkdir -p' command. We don't want to use the $installdir metaconfig
?X: symbol here since that would require too much to
?X: be configured for
?X: this simple extraction task that may happen quickly with 'Configure -S'.
?X: -- RAM, 18/03/96
?X:
case "$file" in
*/*)
dir=`expr X$file : 'X\(.*)/'`
file=`expr X$file : 'X.*\^(.*)'`
(set x $dir; shift; eval $mkdir_p)
sh <"$src/$dir/$file"
;;
*)
sh <"$src/$file"
;;
esac
;;
esac
done
if test -f "$src/config_h.SH"; then
if test ! -f config.h; then
: oops, they left it out of MANIFEST, probably, so do it anyway.
."$src/config_h.SH"
fi
fi
EOS

```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/modified/Extract.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: instubperl.U,v 1.1 1999/07/08 18:32:57 doughera Exp doughera $
```

```
?RCS:
```

```
?RCS: Copyright (c) 1999, Jarkko Hietaniemi
```

```
?RCS:
```

```
?RCS: You may redistribute only under the terms of the Artistic License,
```

```
?RCS: as specified in the README file that comes with the distribution.
```

```
?RCS: You may reuse parts of this distribution only within the terms of
```

```
?RCS: that same Artistic License; a copy of which may be found at the root
```

```
?RCS: of the source tree for dist 3.0.
```

```
?RCS:
```

```
?MAKE:installusrbinperl: installbin cat bin Myread Setvar test Devel
```

```
?MAKE: -pick add $@ %<
```

```
?LINT:set installusrbinperl
```

```
?Y:TOP
```

```
?S:installusrbinperl:
```

```
?S: This variable tells whether Perl should be installed also as
```

```
?S: /usr/bin/perl in addition to
```

```
?S: $installbin/perl
```

```
?S:.
```

```
?C:INSTALL_USR_BIN_PERL:
```

```
?C: This symbol, if defined, indicates that Perl is to be installed
```

```
?C: also as /usr/bin/perl.
```

```
?C:.
```

```
?H:#$installusrbinperl INSTALL_USR_BIN_PERL /**/
```

```
?H:.
```

```
: determine
```

```
whether to install perl also as /usr/bin/perl
```

```
echo " "
```

```
if $test -d /usr/bin -a "X$installbin" != X/usr/bin; then
```

```
$cat <<EOM
```

Many scripts expect perl to be installed as /usr/bin/perl.

If you want to, I can install the perl you are about to compile

as /usr/bin/perl (in addition to \$bin/perl).

```
EOM
```

```
if test -f /usr/bin/perl; then
```

```
$cat <<EOM
```

However, please note that because you already have a /usr/bin/perl,

overwriting that with a new Perl would very probably cause problems.

Therefore I'm assuming you don't want to do that (unless you insist).

```
EOM
```

```

case "$installusrbinperl" in
"$define"|[yY]*) dflt='y';;
*) dflt='n';;
esac
else
$cat <<EOM

```

Since you don't have a /usr/bin/perl I'm assuming creating one is okay.

EOM

```

case "$installusrbinperl" in
"$undef"|[nN]*) dflt='n';;
*) dflt='y';;
esac
fi
rp="Do you want to install perl as /usr/bin/perl?"
./myread
case "$ans" in
[yY]*) val="$define";;
*) val="$undef" ;;
esac
else
val="$undef"
fi
set
installusrbinperl
eval $setvar

```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/installdirs/instubperl.U
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 2000 Jarkko Hietaniemi

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?MAKE:d_unorderedl: Inlibc

?MAKE: -pick add \$@ %<

?S:d_unorderedl:

?S: This variable conditionally defines the HAS_UNORDEREDL symbol, which

?S: indicates to the C program that the unorderedl() routine is available.

?S:.

?C:HAS_UNORDEREDL:

?C: This symbol, if defined, indicates that the unorderedl routine is

?C: available to check whether two long doubles are unorderedl

?C: (effectively: whether either of them is NaN)

?C:.

?H:#\$d_unorderedl HAS_UNORDEREDL /**/

?H:.

?LINT:set d_unorderedl

: see if unorderedl exists

set unorderedl d_unorderedl

eval \$inlibc

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_unorderedl.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1998 Jarkko Hietaniemi

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?MAKE:d_eaccess: Inlibc

?MAKE: -pick add \$@ %<

?S:d_eaccess:

?S: This variable conditionally defines the HAS_EACCESS symbol, which

?S: indicates to the C program that the eaccess() routine is available.

?S:.

?C:HAS_EACCESS :

?C: This symbol, if defined, indicates that the eaccess routine is

?C: available to do extended access checks.

?C:.

?H:#\$d_eaccess HAS_EACCESS /**/

?H:.

?LINT:set d_eaccess

: see if eaccess exists

set eaccess d_eaccess

eval \$inlibc

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/acl/d_eaccess.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: nblock_io.U,v 3.0.1.2 1997/02/28 16:17:14 ram Exp \$

?RCS:

?RCS: Copyright (c) 1991-1993, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 3.0.
?RCS:
?RCS: \$Log: nblock_io.U,v \$
?RCS: Revision 3.0.1.2 1997/02/28 16:17:14 ram
?RCS: patch61: simplify here document for shells that can't handle them well
?RCS: patch61: force use of "startsh" at the head of the generated script
?RCS: patch61: added new files to the ?F: metalint hint
?RCS:
?RCS: Revision 3.0.1.1 1995/07/25 14:13:22 ram
?RCS: patch56: created
?RCS:
?X:
?X: Simplify here document for shells that can't handle them well.
?X: (Problem reported on FreeBSD;
it's unclear if this helps.) --AD
?X:
?MAKE:o_nonblock eagain rd_nodata d_eofnblk: cat rm_try Compile run \
d_open3 h_sysfile h_fcntl signal_t hint Oldconfig Setvar \
startsh i_unistd i_string i_fcntl i_stdlib d_fork d_pipe d_alarm
?MAKE: -pick add \$@ %<
?S:o_nonblock:
?S: This variable bears the symbol value to be used during open() or fcntl()
?S: to turn on non-blocking I/O for a file descriptor. If you wish to switch
?S: between blocking and non-blocking, you may try ioctl(FIOSNBIO) instead,
?S: but that is only supported by some devices.
?S:.
?S:eagain:
?S: This variable bears the symbolic errno code set by read() when no
?S: data is present on the file and non-blocking I/O was enabled (otherwise,
?S: read() blocks naturally).
?S:.
?S:rd_nodata:
?S: This variable holds the return code from read() when no data is
?S: present. It should be -1, but some systems return 0 when O_NDELAY is
?S: used, which is a shame because you cannot make the difference between
?S: no data and an
EOF.. Sigh!
?S:.
?S:d_eofnblk:
?S: This variable conditionally defines EOF_NONBLOCK if EOF can be seen
?S: when reading from a non-blocking I/O source.
?S:.
?C:VAL_O_NONBLOCK:
?C: This symbol is to be used during open() or fcntl(F_SETFL) to turn on

?C: non-blocking I/O for the file descriptor. Note that there is no way
?C: back, i.e. you cannot turn it blocking again this way. If you wish to
?C: alternatively switch between blocking and non-blocking, use the
?C: ioctl(FIOSNBIO) call instead, but that is not supported by all devices.

?C:.

?C:VAL_EAGAIN:

?C: This symbol holds the errno error code set by read() when no data was

?C: present on the non-blocking file descriptor.

?C:.

?C:RD_NODATA:

?C: This symbol holds the return code from read() when no data is present

?C: on the non-blocking file descriptor. Be careful! If EOF_NONBLOCK is

?C: not defined, then you can't distinguish between no data and EOF by

?C: issuing a read(). You'll have to find another way to tell for sure!

?C:.

?C:EOF_NONBLOCK:

?C: This

symbol, if defined, indicates to the C program that a read() on

?C: a non-blocking file descriptor will return 0 on EOF, and not the value

?C: held in RD_NODATA (-1 usually, in that case!).

?C:.

?H:#define VAL_O_NONBLOCK \$o_nonblock

?H:#define VAL_EAGAIN \$again

?H:#define RD_NODATA \$rd_nodata

?H:#\$d_eofnblk EOF_NONBLOCK

?H:.

?T:status

?F:!try.out !try.ret !try.err !try !mtry

?LINT:use d_open3

: check for non-blocking I/O stuff

case "\$h_sysfile" in

true) echo "#include <sys/file.h>" > head.c;;

*)

case "\$h_fcntl" in

true) echo "#include <fcntl.h>" > head.c;;

*) echo "#include <sys/fcntl.h>" > head.c;;

esac

;;

esac

echo " "

echo "Figuring out the flag used by open() for non-blocking I/O..." >&4

case "\$o_nonblock" in

")

\$cat head.c > try.c

\$cat >>try.c <<EOCP

#include <stdio.h>

#\$i_stdlib I_STDLIB

#ifdef I_STDLIB

```

#include <stdlib.h>
#endif
#ifdef I_FCNTL
#include <fcntl.h>
#endif
int main() {
#ifdef O_NONBLOCK
printf("O_NONBLOCK\n");
exit(0);
#endif
#ifdef
O_NDELAY
printf("O_NDELAY\n");
exit(0);
#endif
?X: Stevens "Advanced Programming in the UNIX Environment" page 364 mentions
?X: the FNDELAY symbol, used in 4.3BSD (source: Paul Marquess).
#ifdef FNDELAY
printf("FNDELAY\n");
exit(0);
#endif
exit(0);
}
EOCP
set try
if eval $compile_ok; then
o_nonblock=`$run ./try`
case "$o_nonblock" in
") echo "I can't figure it out, assuming O_NONBLOCK will do.";;
*) echo "Seems like we can use $o_nonblock.";;
esac
else
echo "(I can't compile the test program; pray O_NONBLOCK is right!)"
fi
;;
*) echo "Using $hint value $o_nonblock.";;
esac
$rm_try

echo " "
echo "Let's see what value errno gets from read() on a $o_nonblock file..." >&4
case "$seagain" in
")
case "$d_fork:$d_pipe:$d_alarm" in
define:define:define)
$cat head.c > try.c
$cat >>try.c <<EOCP

```

```

#include <errno.h>
#include <sys/types.h>
#include <signal.h>
#include <stdio.h>
#ifdef I_STDLIB
#include <stdlib.h>
#endif
#ifdef I_FCNTL
#include <fcntl.h>
#endif
#define MY_O_NONBLOCK $o_nonblock
#ifdef errno /* XXX need better Configure test */
extern int errno;
#endif
#ifdef I_UNISTD
#include <unistd.h>
#endif
#ifdef I_STRING
#include <string.h>
#else
#include <strings.h>
#endif
$signal_t blech(int x) { exit(3); }
EOCP
$cat >> try.c <<'EOCP'
int main()
{
int pd[2];
int pu[2];
char buf[1];
char string[100];
int ret;

ret = pipe(pd); /* Down: child -> parent */
if (ret != 0)
exit(3);
ret = pipe(pu); /* Up: parent -> child */
if (ret != 0)
exit(3);
if (0 != fork()) {
close(pd[1]); /* Parent reads from pd[0] */
close(pu[0]); /* Parent writes (blocking) to pu[1] */
#endif

```

```

if (-1 == fcntl(pd[0], F_SETFL, MY_O_NONBLOCK))
    exit(1);
#else
    exit(4);
#endif
signal(SIGALRM, blech);
alarm(5);
if ((ret = read(pd[0], buf, 1)) > 0) /* Nothing to read! */
    exit(2);
sprintf(string, "%d\n", ret);
ret =
write(2, string, strlen(string));
if (ret != strlen(string))
    exit(3);
alarm(0);
#ifdef EAGAIN
if (errno == EAGAIN) {
    printf("EAGAIN\n");
    goto ok;
}
#endif
#ifdef EWOULDBLOCK
if (errno == EWOULDBLOCK)
    printf("EWOULDBLOCK\n");
#endif
ok:
ret = write(pu[1], buf, 1); /* Unblocks child, tell it to close our pipe */
if (ret != 1)
    exit(3);
sleep(2); /* Give it time to close our pipe */
alarm(5);
ret = read(pd[0], buf, 1); /* Should read EOF */
alarm(0);
sprintf(string, "%d\n", ret);
ret = write(4, string, strlen(string));
if (ret != strlen(string))
    exit(3);
exit(0);
}

close(pd[0]); /* We write to pd[1] */
close(pu[1]); /* We read from pu[0] */
ret = read(pu[0], buf, 1); /* Wait for parent to signal us we may continue */
if (ret != 1)
    exit(3);
close(pd[1]); /* Pipe pd is now fully closed! */
exit(0); /* Bye bye, thank you for playing! */
}

```

```

EOCP
set try
if eval $compile_ok; then
?X: Use script to avoid the possible 'alarm
call' message
echo "$startsh" >mtry
echo "$run ./try >try.out 2>try.ret 4>try.err || exit 4" >>mtry
chmod +x mtry
$run ./mtry >/dev/null 2>&1
case $? in
0) eagain=`$cat try.out`;
1) echo "Could not perform non-blocking setting!";;
2) echo "I did a successful read() for something that was not there!";;
3) echo "Hmm... non-blocking I/O does not seem to be working!";;
4) echo "Could not find F_SETFL!";;
*) echo "Something terribly wrong happened during testing.";;
esac
rd_nodata=`$cat try.ret`
echo "A read() system call with no data present returns $rd_nodata."
case "$rd_nodata" in
0|-1) ;;
*)
echo "(That's peculiar, fixing that to be -1.)"
rd_nodata=-1
;;
esac
case "$eagain" in
")
echo "Forcing errno EAGAIN on read() with no data available."
eagain=EAGAIN
;;
*)
echo "Your read() sets errno to $eagain when no data is available."
;;
esac
status=`$cat try.err`
case "$status" in
0) echo "And it correctly returns 0 to
signal EOF.";;
-1) echo "But it also returns -1 to signal EOF, so be careful!";;
*) echo "However, your read() returns '$status' on EOF??";;
esac
val="$define"
if test "$status" = "$rd_nodata"; then
echo "WARNING: you can't distinguish between EOF and no data!"
val="$undef"
fi
else

```

```

echo "I can't compile the test program--assuming errno EAGAIN will do."
eagain=EAGAIN
fi
;;
*) echo "Can't figure out how to test this--assuming errno EAGAIN will do."
eagain=EAGAIN
val="$define"
;;
esac
set d_eofnblk
eval $setvar
;;
*)
echo "Using $hint value $eagain."
echo "Your read() returns $rd_nodata when no data is present."
case "$d_eofnblk" in
"$define") echo "And you can see EOF because read() returns 0.>";;
"$undef") echo "But you can't see EOF status from read() returned value.>";;
*)
?X: Should not happen, but if it does, assume the worst!
echo "(Assuming you can't see EOF status from read anyway.)"
d_eofnblk=$undef
;;
esac
;;
esac
$rm_try head.c
mtry

```

Found in path(s):

```

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/compline/nblock_io.U

```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1999, Jarkko Hietaniemi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 3.0.

?RCS:

?MAKE:d_posix_shm: Setvar d_shm_open d_shm_unlink i_sysmman

?MAKE: -pick add \$@ %<

?S:d_posix_shm:

?S: This variable conditionally defines the HAS_POSIX_SHM symbol, which

```

?S: indicates that the entire POSIX shm_*(2) library is present.
?S:.
?C:HAS_POSIX_SHM:
?C: This symbol, if defined, indicates that the entire POSIX shm_*(2)
?C: library is supported.
?C:.
?H:#$d_posix_shm HAS_POSIX_SHM /**/
?H:.
?LINT:set d_posix_shm
: see how much of the 'POSIX shm_*(2)' library is present.
echo " "
case "$i_sysmman$d_shm_open$d_shm_unlink"
in
*"$undef"*) val="$undef" ;;
*) val="$define" ;;
esac
case "$val" in
"$define") echo "You have the full POSIX shm_*(2) library." >&4 ;;
"$undef") echo "You don't have the full POSIX shm_*(2) library." >&4 ;;
esac
set d_posix_shm
eval $setvar

```

Found in path(s):

```

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/perl/d_posix_shm.U

```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 2008 H.Merijn Brand

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?MAKE:d_ctime64 d_localtime64 d_gmtime64 d_mktime64 d_diffime64 d_asctime64: Inlibc

?MAKE: -pick add \$@ %<

?S:d_ctime64:

?S: This variable conditionally defines the HAS_CTIME64 symbol, which

?S: indicates to the C program that the ctime64 () routine is available.

?S:.

?S:d_localtime64:

?S: This variable conditionally defines the HAS_LOCALTIME64 symbol, which

?S: indicates to the C program that the localtime64 () routine is available.

?S:.

?S:d_gmtime64:

?S: This variable conditionally defines the HAS_GMTIME64 symbol, which

?S: indicates to the C program that the gmtime64 () routine is available.

?S:
?S:d_mktime64:
?S: This variable conditionally defines the HAS_MKTIME64 symbol, which
?S: indicates to the
C program that the mktime64 () routine is available.
?S:
?S:d_diffime64:
?S: This variable conditionally defines the HAS_DIFFTIME64 symbol, which
?S: indicates to the C program that the diffime64 () routine is available.
?S:
?S:d_asctime64:
?S: This variable conditionally defines the HAS_ASCTIME64 symbol, which
?S: indicates to the C program that the asctime64 () routine is available.
?S:
?C:HAS_CTIME64:
?C: This symbol, if defined, indicates that the ctime64 () routine is
?C: available to do the 64bit variant of ctime ()
?C:
?C:HAS_LOCALTIME64:
?C: This symbol, if defined, indicates that the localtime64 () routine is
?C: available to do the 64bit variant of localtime ()
?C:
?C:HAS_GMTIME64:
?C: This symbol, if defined, indicates that the gmtime64 () routine is
?C: available to do the 64bit variant of gmtime ()
?C:
?C:HAS_MKTIME64:
?C: This symbol, if defined, indicates that the mktime64 () routine is
?C: available to do the 64bit variant of mktime ()
?C:
?C:HAS_DIFFTIME64:
?C: This
symbol, if defined, indicates that the diffime64 () routine is
?C: available to do the 64bit variant of diffime ()
?C:
?C:HAS_ASCTIME64:
?C: This symbol, if defined, indicates that the asctime64 () routine is
?C: available to do the 64bit variant of asctime ()
?C:
?H:#\$d_ctime64 HAS_CTIME64 /**/
?H:#\$d_localtime64 HAS_LOCALTIME64 /**/
?H:#\$d_gmtime64 HAS_GMTIME64 /**/
?H:#\$d_mktime64 HAS_MKTIME64 /**/
?H:#\$d_diffime64 HAS_DIFFTIME64 /**/
?H:#\$d_asctime64 HAS_ASCTIME64 /**/
?H:
?LINT:set d_ctime64 d_localtime64 d_gmtime64 d_mktime64 d_diffime64 d_asctime64
: see if 64bit time functions exists

```
set ctime64 d_ctime64
eval $inlibc
```

```
set localtime64 d_localtime64
eval $inlibc
```

```
set gmtime64 d_gmtime64
eval $inlibc
```

```
set mktime64 d_mkttime64
eval $inlibc
```

```
set difftime64 d_difftime64
eval $inlibc
```

```
set asctime64 d_asctime64
eval $inlibc
```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/perl/d_timefuncs64.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: d_wctomb.U 1 2006-08-24 12:32:52Z rmanfredi $
```

```
?RCS:
```

```
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
```

```
?RCS:
```

```
?RCS: You may redistribute only under the terms of the Artistic Licence,
```

```
?RCS: as specified in the README file that comes with the distribution.
```

```
?RCS: You may reuse parts of this distribution only within the terms of
```

```
?RCS: that same Artistic Licence; a copy of which may be found at the root
```

```
?RCS: of the source tree for dist 4.0.
```

```
?RCS:
```

```
?RCS: Original Author: Andy Dougherty <doughera@lafcol.lafayette.edu>
```

```
?RCS:
```

```
?RCS: $Log: d_wctomb.U,v $
```

```
?RCS: Revision 3.0.1.1 1994/08/29 16:20:43 ram
```

```
?RCS: patch32: created by ADO
```

```
?RCS:
```

```
?MAKE:d_wctomb: Inlibc
```

```
?MAKE: -pick add $@ %<
```

```
?S:d_wctomb:
```

```
?S: This variable conditionally defines the HAS_WCTOMB symbol, which
```

```
?S: indicates to the C program that the wctomb() routine is available
```

```
?S: to convert a wide character to a multibyte.
```

```
?S:.
```

```
?C:HAS_WCTOMB (WCTOMB):
```

?C: This
symbol, if defined, indicates that the wctomb routine is available
?C: to convert a wide character to a multibyte.
?C:.
?H:#\$d_wctomb HAS_WCTOMB /**/
?H:.
?LINT:set d_wctomb
: see if wctomb exists
set wctomb d_wctomb
eval \$inlibc

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/d_wctomb.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$
?RCS:
?RCS: Copyright (c) 2009 H.Merijn Brand
?RCS:
?RCS: You may distribute under the terms of either the GNU General Public
?RCS: License or the Artistic License, as specified in the README file.
?RCS:
?MAKE:d_inetpton: Inlibc
?MAKE: -pick add \$@ %<
?S:d_inetpton:
?S: This variable conditionally defines the HAS_INETPTON symbol,
?S: which indicates to the C program that the inet_pton() function
?S: is available.
?S:.
?C:HAS_INETPTON:
?C: This symbol, if defined, indicates that the inet_pton() function
?C: is available to parse IPv4 and IPv6 strings.
?C:.
?H:#\$d_inetpton HAS_INETPTON /**/
?H:.
?LINT:set d_inetpton
: see if inet_pton exists
set inet_pton d_inetpton
eval \$inlibc

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_inetpton.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: basicshell.U 1 2006-08-24 12:32:52Z rmanfredi \$
?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic Licence,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic Licence; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: basicshell.U,v \$

?RCS: Revision 3.0 1993/08/18 12:05:25 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?MAKE:basicshell: Getfile Oldconfig bash csh ksh sh

?MAKE: -pick add \$@ %<

?S:basicshell:

?S: This variable contains the eventual value of the BASICSHELL symbol,

?S: which contains the full name of the basic script shell on this

?S: system. Usual values are /bin/sh, /bin/ksh, /bin/csh.

?S:.

?C:BASICSHELL:

?C: This symbol contains the

full name of the basic script shell on this

?C: system. Usual values are /bin/sh, /bin/ksh, /bin/csh.

?C:.

?H:#define BASICSHELL "\$basicshell" /**/

?H:.

: find the most basic shell for scripts

echo " "

case "\$basicshell" in

*)

case "\$sh \$bash \$csh \$ksh" in

/sh) dflt="\$sh" ;;

/ksh) dflt="\$ksh" ;;

/csh) dflt="\$csh" ;;

/bash) dflt="\$bash" ;;

*) dflt='/bin/sh' ;;

esac

::

*)

dflt="\$basicshell";;

esac

fn=f

rp="Give the full path name of the most basic shell used on your system"

../getfile

basicshell=\$ans

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-

debian-perl-5.26.1/dist/U/basicshell.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: d_csh.U,v \$

?RCS: Revision 3.0.1.1 1997/02/28 15:32:18 ram

?RCS: patch61: added full_csh to preserve the full path even when portable

?RCS:

?RCS: Revision 3.0 1993/08/18 12:05:53 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?MAKE:d_csh full_csh: csh Setvar

?MAKE: -pick add \$@ %<

?S:d_csh:

?S: This variable conditionally defines the CSH symbol, which

?S: indicates to the C program that the C-shell exists.

?S:.

?S:full_csh:

?S: This variable contains the full pathname to 'csh', whether

or

?S: not the user has specified 'portability'. This is only used

?S: in the compiled C program, and we assume that all systems which

?S: can share this executable will have the same full pathname to

?S: 'csh.'

?S:.

?X: Yes, I know about the C symbol PORTABLE, but I think csh

?X: is unlikely to move, and I'm too lazy to add all the

?X: #ifdef PORTABLE sections to the perl source.

?X:

?C:HAS_CSH:

?C: This symbol, if defined, indicates that the C-shell exists.

?C:.

?C:CSH:

?C: This symbol, if defined, contains the full pathname of csh.

?C:.

?X: Previously, I just did \$d_csh CSH "\$full_csh", but that caused

?X: problems on VMS where the config.sh extraction program changes

?X: \$undef to a real cpp undef, and they then had #undef CSH ""

?X: which the compiler didn't like. It's easy to work around this,

```

?X: so I did. --AD 3/1998.
?X: And we don't want to define CSH if !HAS_CSH, but we don't want
?X: those lines in config.h if they don't need CSH, so protect with ?CSH
?X: and not
?%<. --RAM, 15/02/2004
?H:?%<:#$d_csh HAS_CSH /**/
?H:?CSH:#ifdef HAS_CSH
?H:?CSH:#define CSH "$full_csh" /**/
?H:?CSH:#endif
?H:.
?LINT:set d_csh
: get csh whereabouts
case "$csh" in
'csh') val="$undef" ;;
*) val="$define" ;;
esac
set d_csh
eval $setvar
: Respect a hint or command line value for full_csh.
case "$full_csh" in
") full_csh=$csh ;;
esac

```

Found in path(s):

```

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/modified/d_csh.U

```

No license file was found, but licenses were detected in source scan.

```

?RCS: $Id: d_mkfifo.U 1 2006-08-24 12:32:52Z rmanfredi $
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: Original Author: Andy Dougherty <doughera@lafcol.lafayette.edu>
?RCS:
?RCS: $Log: d_mkfifo.U,v $
?RCS: Revision 3.0.1.1 1994/10/29 16:14:17 ram
?RCS: patch36: created by ADO
?RCS:
?RCS:
?MAKE:d_mkfifo: Inlibc
?MAKE:-pick add $@ %<
?S:d_mkfifo:

```

?S: This variable conditionally defines the HAS_MKFIFO symbol, which

?S: indicates to the C program that the mkfifo() routine is available.

?S:.

?C:HAS_MKFIFO :

?C: This symbol, if defined, indicates that the mkfifo routine is

?C: available to create FIFOs. Otherwise, mknod should be able to

?C: do it for you. However, if mkfifo is there, mknod might require

?C: super-user privileges which mkfifo will not.

?C:.

?H:#\$d_mkfifo HAS_MKFIFO /**/

?H:.

?LINT:set d_mkfifo

: see if mkfifo exists

set mkfifo d_mkfifo

eval \$inlibc

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/d_mkfifo.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: i_dld.U 1 2006-08-24 12:32:52Z rmanfredi \$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic Licence,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic Licence; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: Original Author: Andy Dougherty <doughera@lafcol.lafayette.edu>

?RCS:

?RCS: \$Log: i_dld.U,v \$

?RCS: Revision 3.0.1.1 1994/10/29 16:20:07 ram

?RCS: patch36: created by ADO

?RCS:

?MAKE:i_dld: Inhdr

?MAKE: -pick add \$@ %<

?S:i_dld:

?S: This variable conditionally defines the I_DLD symbol, which

?S: indicates to the C program that <dld.h> (GNU dynamic loading)

?S: exists and should be included.

?S:.

?C:I_DLD:

?C: This symbol, if defined, indicates that <dld.h>

```
exists and should
?C: be included before using GNU dynamic loading features.
?C:.
?H:#$i_dld I_DLD /**/
?H:.
?LINT:set i_dld
: see if dld is available
set dld.h i_dld
eval $inhdr
```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/i_dld.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: d_shm.U,v 3.0 1993/08/18 12:07:17 ram Exp $
?RCS:
?RCS: Copyright (c) 1991-1993, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 3.0.
?RCS:
?RCS: $Log: d_shm.U,v $
?RCS: Revision 3.0 1993/08/18 12:07:17 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:d_shm: test d_shmctl d_shmget d_shmat d_shmdt Setvar Findhdr osname
?MAKE: -pick add $@ %<
?S:d_shm:
?S: This variable conditionally defines the HAS_SHM symbol, which
?S: indicates that the entire shm*(2) library is present.
?S:.
?C:HAS_SHM:
?C: This symbol, if defined, indicates that the entire shm*(2) library is
?C: supported.
?C:.
?H:#$d_shm HAS_SHM /**/
?H:.
?T:h_shm
?LINT:set
d_shm
: see how much of the 'shm*(2)' library is present.
h_shm=true
echo " "
case "$d_shmctl$d_shmget$d_shmat$d_shmdt" in
```

```

*$undef*) h_shm=false;;
esac
case "$osname" in
freebsd)
  case "`ipcs 2>&1`" in
  "SVID shared memory"*"not configured"*)
echo "Your $osname does not have the shm*(2) configured." >&4
  h_shm=false
val="$undef"
set shmctl d_shmctl
eval $setvar
set shmget d_shmget
eval $setvar
set shmat d_shmat
eval $setvar
set shmdt d_shmdt
eval $setvar
;;
  esac
;;
esac
: we could also check for sys/ipc.h ...
if $h_shm && $test `./findhdr sys/shm.h`; then
echo "You have the full shm*(2) library." >&4
val="$define"
else
echo "You don't have the full shm*(2) library." >&4
val="$undef"
fi
set d_shm
eval $setvar

```

Found in path(s):

```

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/modified/d_shm.U

```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: i_varhdr.U 1 2006-08-24 12:32:52Z rmanfredi \$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: i_varhdr.U,v \$

?RCS: Revision 3.0.1.3 1997/02/28 15:54:42 ram

?RCS: patch61: varargs script now starts with leading "startsh"

?RCS:

?RCS: Revision 3.0.1.2 1994/10/29 16:21:02 ram

?RCS: patch36: added ?F: line for metalint file checking

?RCS:

?RCS: Revision 3.0.1.1 1994/05/13 15:26:05 ram

?RCS: patch27: this unit now supersedes old i_stdarg.U and i_varargs.U

?RCS: patch27: modified to avoid spurious Whoa warnings (ADO)

?RCS:

?RCS: Revision 3.0
1993/08/18 12:08:49 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?MAKE:i_stdarg i_varargs i_varhdr: cat +cc +ccflags rm test Setvar \
Findhdr startsh _o

?MAKE: -pick add \$@ %<

?S:i_stdarg:

?S: This variable conditionally defines the I_STDARG symbol, which

?S: indicates to the C program that <stdarg.h> exists and should

?S: be included.

?S:.

?S:i_varargs:

?S: This variable conditionally defines I_VARARGS, which indicates

?S: to the C program that it should include <varargs.h>.

?S:.

?S:i_varhdr:

?S: Contains the name of the header to be included to get va_dcl definition.

?S: Typically one of varargs.h or stdarg.h.

?S:.

?C:I_STDARG:

?C: This symbol, if defined, indicates that <stdarg.h> exists and should

?C: be included.

?C:.

?C:I_VARARGS:

?C: This symbol, if defined, indicates to the C program that it should

?C: include <varargs.h>.

?C:.

?H:#\$i_stdarg I_STDARG /**/
?H:#\$i_varargs I_VARARGS /**/
?H:.

?W:%<:va_dcl

?F:!varargs

?T:valstd

?LINT:set i_stdarg i_varargs

?X:

?X:

Don't use setvar because the varargs test below might override these.

?X: Actually, the messages here are just informative. We don't wish to set

?X: i_varargs or i_stdarg to their final value before knowing which of the

?X: two we'll include.

?X:

: see if stdarg is available

echo " "

if \$test `./findhdr stdarg.h`; then

echo "<stdarg.h> found." >&4

valstd="\$define"

else

echo "<stdarg.h> NOT found." >&4

valstd="\$undef"

fi

: see if varargs is available

echo " "

if \$test `./findhdr varargs.h`; then

echo "<varargs.h> found." >&4

else

echo "<varargs.h> NOT found, but that's ok (I hope)." >&4

fi

?X:

?X: if you have stdarg.h, you need to support prototypes to actually use it;

?X: but if stdarg.h exists and the compiler doesn't support prototypes (for some

?X: bizarre reason), we'll fall back to varargs.h anyway so it's not so bad.

?X:

: set up the varargs testing programs

\$cat > varargs.c <<EOP

#ifdef I_STDARG

#include <stdarg.h>

#endif

#ifdef I_VARARGS

#include <varargs.h>

#endif

#ifdef

I_STDARG

int f(char *p, ...)

#else

int f(va_alist)

va_dcl

#endif

{

va_list ap;

#ifndef I_STDARG

char *p;

```

#endif
#ifdef I_STDARG
    va_start(ap,p);
#else
    va_start(ap);
    p = va_arg(ap, char *);
#endif
    va_end(ap);
    return 0;
}
EOP
$cat > varargs <<EOP
$startsh
if $cc -c $ccflags -D\ $1 varargs.c >/dev/null 2>&1; then
    echo "true"
else
    echo "false"
fi
$rm -f varargs$_o
EOP
chmod +x varargs

: now check which varargs header should be included
echo " "
i_varhdr="
val="
case "$valstd" in
"$define")
    if `./varargs I_STDARG`; then
        val='stdarg.h'
    elif `./varargs I_VARARGS`; then
        val='varargs.h'
    fi
    ;;
*)
    if `./varargs I_VARARGS`; then
        val='varargs.h'
    fi
    ;;
esac
case "$val" in
")
    echo " "
    echo "*** WHOA THERE!!! ***" >&4
    echo "  Your C compiler \"$cc\" doesn't seem to support stdarg or varargs!" >&4
    case "$knowitall" in
    ")
        echo "  I'm giving up; maybe you can try again with a different compiler?" >&4

```

```

    exit 1
    ;;
esac
echo "I could not find the definition for va_dcl...
You have problems..." >&4
val="$undef"; set i_stdarg; eval $setvar
val="$undef"; set i_varargs; eval $setvar
;;
*)
set i_varhdr
eval $setvar
case "$i_varhdr" in
stdarg.h)
    val="$define"; set i_stdarg; eval $setvar
    val="$undef"; set i_varargs; eval $setvar
    ;;
varargs.h)
    val="$undef"; set i_stdarg; eval $setvar
    val="$define"; set i_varargs; eval $setvar
    ;;
esac
echo "We'll include <$i_varhdr> to get va_dcl definition." >&4;;
esac
$rm -f varargs*

```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/modified/i_varhdr.U
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: stdchar.U,v \$

?RCS: Revision 3.0 1993/08/18 12:09:52 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?MAKE:stdchar: contains Findhdr cppstdin cppminus rm

?MAKE: -pick add \$@ %<

?S:stdchar:

?S: This variable conditionally defines STDCHAR to be the type of char

?S: used in stdio.h. It has the values "unsigned char" or "char".

?S:.

?C:STDCHAR:

?C: This symbol is defined to be the type of char used in stdio.h.

?C: It has the values "unsigned char" or "char".

?C:.

?H:#define STDCHAR \$stdchar /**/

?H:.

?F:!stdioh

:

see what type of char stdio uses.

echo " "

?X: untangle the #include nest

echo '#include <stdio.h>' | \$cppstdin \$cppminus > stdioh

if \$contains 'unsigned.*char.*_ptr;' stdioh >/dev/null 2>&1 ; then

echo "Your stdio uses unsigned chars." >&4

stdchar="unsigned char"

else

echo "Your stdio uses signed chars." >&4

stdchar="char"

fi

\$rm -f stdioh

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/stdchar.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: i_systimes.U 1 2006-08-24 12:32:52Z rmanfredi \$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic Licence,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic Licence; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: i_systimes.U,v \$

?RCS: Revision 3.0 1993/08/18 12:08:39 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?MAKE:i_systimes: Inhdr

?MAKE: -pick add \$@ %<

?S:i_systimes:

?S: This variable conditionally defines the I_SYS_TIMES symbol, and indicates

?S: whether a C program should include <sys/times.h>.

?S:.

```
?C:I_SYS_TIMES (I_SYSTIMES):
?C: This symbol, if defined, indicates to the C program that it should
?C: include <sys/times.h>.
?C:.
?H:#$i_systimes I_SYS_TIMES /**/
?H:.
?LINT:set
i_systimes
: see if this is a sys/times.h system
set sys/times.h i_systimes
eval $inhdr
```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/i_systimes.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id$
?RCS:
?RCS: Copyright (c) 1991-1993, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 3.0.
?RCS:
?MAKE:d_drand48proto: Hasproto i_stdlib i_unistd
?MAKE: -pick add $@ %<
?S:d_drand48proto:
?S: This variable conditionally defines the HAS_DRAND48_PROTO symbol,
?S: which indicates to the C program that the system provides
?S: a prototype for the drand48() function. Otherwise, it is
?S: up to the program to supply one.
?S:.
?C:HAS_DRAND48_PROTO:
?C: This symbol, if defined, indicates that the system provides
?C: a prototype for the drand48() function. Otherwise, it is up
?C: to the program to supply one. A good guess
is
?C: extern double drand48(void);
?C:.
?H:#$d_drand48proto HAS_DRAND48_PROTO /**/
?H:.
?LINT:set d_drand48proto
: see if prototype for drand48 is available
echo " "
set d_drand48proto drand48 $i_stdlib stdlib.h $i_unistd unistd.h
```

eval \$hasproto

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/protos/d_drاند48proto.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1999 Jarkko Hietaniemi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 3.0.

?RCS:

?MAKE:d_setspent: Inlibc

?MAKE: -pick add \$@ %<

?S:d_setspent:

?S: This variable conditionally defines HAS_SETSPENT if setspent() is

?S: available to initialize the scan of SysV shadow password entries.

?S:.

?C:HAS_SETSPENT:

?C: This symbol, if defined, indicates that the setspent system call is

?C: available to initialize the scan of SysV shadow password entries.

?C:.

?H:#\$d_setspent HAS_SETSPENT /**/

?H:.

?LINT:set d_setspent

: see if setspent exists

set setspent d_setspent

eval \$inlibc

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_setspent.U

No license file was found, but licenses were detected in source scan.

?RCS: You may distribute under the terms of either the GNU General Public

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/time_size.U

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_isnormal.U

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_printfed.U

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_futimes.U

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/threads/d_pthread_atfork.U

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_isinf.U

*

/opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_isless.U

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_sprintf_len.U

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/threads/d_pthratrj.U

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/modified/d_union_semun.U

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_statfs4.U

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_ptrdiff_t.U

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_statfs3.U

*

/opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_off64_t.U

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/i_stdbool.U

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/threads/d_pthread_y.U

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_signbit.U

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/threads/d_pthreadj.U

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_libm_lib_version.U

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/modified/d_longlong.U

*

/opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/ebcdic/ebcdic.U

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_cplusplus.U

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_fpos64_t.U

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_fcntl_can_lock.U

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_dlsymun.U

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-

debian-perl-5.26.1/U/perl/d_strtoll.U
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/perl/d_prctl.U
*
/opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/perl/d_strtouq.U
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/perl/d_isnan.U
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/perl/d_isfinite.U
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/perl/d_strtoull.U
No license file was found, but licenses were detected in source scan.

?RCS: \$Id: sitescriptdir.U,v \$
?RCS:
?RCS: Copyright (c) 1999 Andy Dougherty
?RCS:
?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 3.0.
?RCS:
?RCS: \$Log: sitescriptdir.U,v \$
?RCS:
?MAKE:sitescriptdir sitescriptdirexp installsitescriptdir : Getfile \
Setprefixvar Oldconfig scriptdir prefix siteprefix sed
?MAKE: -pick add \$@ %<
?Y:TOP
?D:sitescriptdir="
?S:sitescriptdir:
?S: This variable holds the name of the directory in which the user wants
?S: to put add-on publicly executable files for the package in question. It
?S: is most often a local directory such as /usr/local/bin. Programs using
?S: this variable must be prepared to deal with ~name
substitution.
?S: The standard distribution will put nothing in this directory.
?S: After perl has been installed, users may install their own local
?S: scripts in this directory with
?S: MakeMaker Makefile.PL
?S: or equivalent. See INSTALL for details.
?S:.
?D:sitescriptdirexp="
?S:sitescriptdirexp:
?S: This is the same as the sitescriptdir variable, but is filename expanded at
?S: configuration time, for use in your makefiles.
?S:.

```

?S:installsitescriptdir:
?D:installsitescriptdir="
?S: This variable is usually the same as sitescriptdirexp, unless you are on
?S: a system running AFS, in which case they may differ slightly. You
?S: should always use this variable within your makefiles for portability.
?S:.
?LINT:change prefixvar
?LINT:set installsitescriptdir
?LINT:set sitescriptdir
?LINT:set sitescriptdirexp
: determine where add-on public executables go
case "$sitescriptdir" in
") dflt=`echo $scriptdir | $sed "s#^$prefix#$siteprefix#" ` ;;
*) dflt=$sitescriptdir ;;
esac
fn=d~
rp='Pathname
  where add-on public executable scripts should be installed?'
./getfile
prefixvar=sitescriptdir
./setprefixvar

```

Found in path(s):

```

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/installdirs/sitescriptdir.U

```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1999 Jarkko Hietaniemi

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?MAKE:d_PRIId64 d_PRIi64 d_PRIu64 d_PRIO64 d_PRIx64 d_PRIXU64 \

sPRIId64 sPRIi64 sPRIu64 sPRIO64 sPRIx64 sPRIXU64: \

quadtype i_inttypes test cat rm_try Setvar Compile run

?MAKE: -pick add \$@ %<

?S:d_PRIId64:

?S: This variable conditionally defines the PERL_PRIId64 symbol, which

?S: indicates that stdio has a symbol to print 64-bit decimal numbers.

?S:.

?S:d_PRIi64:

?S: This variable conditionally defines the PERL_PRIi64 symbol, which

?S: indicates that stdio has a symbol to print 64-bit decimal numbers.

?S:.

?S:d_PRIu64:

?S: This variable conditionally defines the PERL_PRIu64 symbol, which

?S: indicates that stdio has a symbol to print 64-bit unsigned decimal
?S: numbers.
?S:.
?S:d_PRIo64:
?S: This variable
conditionally defines the PERL_PRIo64 symbol, which
?S: indicates that stdio has a symbol to print 64-bit octal numbers.
?S:.
?S:d_PRIx64:
?S: This variable conditionally defines the PERL_PRIx64 symbol, which
?S: indicates that stdio has a symbol to print 64-bit hexadecimal numbers.
?S:.
?S:d_PRIxU64:
?S: This variable conditionally defines the PERL_PRIxU64 symbol, which
?S: indicates that stdio has a symbol to print 64-bit hExADEcImAl numbers.
?S: The 'U' in the name is to separate this from d_PRIx64 so that even
?S: case-blind systems can see the difference.
?S:.
?S:sPRId64:
?S: This variable, if defined, contains the string used by stdio to
?S: format 64-bit decimal numbers (format 'd') for output.
?S:.
?S:sPRIi64:
?S: This variable, if defined, contains the string used by stdio to
?S: format 64-bit decimal numbers (format 'i') for output.
?S:.
?S:sPRIu64:
?S: This variable, if defined, contains the string used by stdio to
?S: format 64-bit unsigned decimal numbers (format 'u')
for output.
?S:.
?S:sPRIo64:
?S: This variable, if defined, contains the string used by stdio to
?S: format 64-bit octal numbers (format 'o') for output.
?S:.
?S:sPRIx64:
?S: This variable, if defined, contains the string used by stdio to
?S: format 64-bit hexadecimal numbers (format 'x') for output.
?S:.
?S:sPRIxU64:
?S: This variable, if defined, contains the string used by stdio to
?S: format 64-bit hExADEcImAl numbers (format 'X') for output.
?S: The 'U' in the name is to separate this from sPRIx64 so that even
?S: case-blind systems can see the difference.
?S:.
?C:PERL_PRId64:
?C: This symbol, if defined, contains the string used by stdio to
?C: format 64-bit decimal numbers (format 'd') for output.

```

?C:.
?C:PERL_PRIi64:
?C: This symbol, if defined, contains the string used by stdio to
?C: format 64-bit decimal numbers (format 'i') for output.
?C:.
?C:PERL_PRIu64:
?C: This symbol, if defined, contains the string used by stdio to
?C: format 64-bit unsigned decimal numbers (format 'u')
for output.
?C:.
?C:PERL_PRIo64:
?C: This symbol, if defined, contains the string used by stdio to
?C: format 64-bit octal numbers (format 'o') for output.
?C:.
?C:PERL_PRIx64:
?C: This symbol, if defined, contains the string used by stdio to
?C: format 64-bit hexadecimal numbers (format 'x') for output.
?C:.
?C:PERL_PRIXu64:
?C: This symbol, if defined, contains the string used by stdio to
?C: format 64-bit hExADECimAl numbers (format 'X') for output.
?C:.
?H:#$d_PRIi64 PERL_PRIi64 $sPRIi64 /**/
?H:#$d_PRIu64 PERL_PRIu64 $sPRIu64 /**/
?H:#$d_PRIo64 PERL_PRIo64 $sPRIo64 /**/
?H:#$d_PRIx64 PERL_PRIx64 $sPRIx64 /**/
?H:#$d_PRIXu64 PERL_PRIXu64 $sPRIXu64 /**/
?H:.
?T:yyy
?F:!try
: Check 64bit sizes
echo " "

if $test X"$quadtype" != X; then

echo "Checking how to print 64-bit integers..." >&4

if $test X"$sPRIi64" = X -a X"$quadtype" = Xint; then
$cat >try.c <<'EOCP'
#include <sys/types.h>
#include <stdio.h>
int main() {
int q = 12345678901;

printf("%ld\n", q);
}
EOCP

```

```

set try
if eval $compile; then
yyy=`$run ./try`
case "$yyy" in
12345678901)
sPRId64="d"; sPRi64="i"; sPRi64="u";
sPRIo64="o"; sPRIx64="x"; sPRIXU64="X";
echo "We will use %d."
;;
esac
fi
fi

```

```

if $test X"$sPRId64" = X -a X"$quadtype" = Xlong; then
$cat >try.c <<'EOCP'
#include <sys/types.h>
#include <stdio.h>
int main() {
long q = 12345678901;
printf("%ld\n", q);
}
EOCP

```

```

set try
if eval $compile; then
yyy=`$run ./try`
case "$yyy" in
12345678901)
sPRId64="ld"; sPRi64="li"; sPRi64="lu";
sPRIo64="lo"; sPRIx64="lx"; sPRIXU64="IX";
echo "We will use %ld."
;;
esac
fi
fi

```

```

if $test X"$sPRId64" = X -a X"$i_inttypes" = X"$define" -a X"$quadtype" = Xint64_t; then
$cat >try.c <<'EOCP'
#include <sys/types.h>
#include <inttypes.h>
#include <stdio.h>
int main() {
int64_t q = 12345678901;
printf("%" PRId64 "\n", q);
}
EOCP
set try
if eval $compile; then
yyy=`$run

```

```

./try`
case "$yyy" in
12345678901)
sPRId64=PRId64; sPRIi64=PRIi64; sPRIu64=PRIu64;
    sPRIo64=PRIo64; sPRIx64=PRIx64; sPRIXU64=PRIXU64;
echo "We will use the C9X style."
;;
esac
fi
fi

```

```

if $test X"$sPRId64" = X -a X"$quadtype" != X; then

```

```

$cat >try.c <<EOCP
#include <sys/types.h>
#include <stdio.h>
int main() {
$quadtype q = 12345678901;
printf("%Ld\n", q);
}

```

```
EOCP
```

```

set try
if eval $compile; then
yyy=`$run ./try`
case "$yyy" in
12345678901)
sPRId64=""Ld"; sPRIi64=""Li"; sPRIu64=""Lu";
    sPRIo64=""Lo"; sPRIx64=""Lx"; sPRIXU64=""LX";
echo "We will use %Ld."
;;
esac
fi
fi

```

```

if $test X"$sPRId64" = X -a X"$quadtype" = X"long long"; then

```

```

$cat >try.c <<EOCP'
#include <sys/types.h>
#include <stdio.h>
int main() {
long long q = 12345678901LL; /* AIX cc requires the LL suffix. */
printf("%lld\n", q);
}

```

```
EOCP
```

```

set try
if eval $compile; then
yyy=`$run ./try`
case "$yyy" in
12345678901)
sPRId64=""lld"; sPRIi64=""lli";

```

```

sPRIu64=""llu";
    sPRIo64=""llo"; sPRIx64=""llx"; sPRIXU64=""lIX";
    echo "We will use the %lld style."
;;
esac
fi
fi

```

```

if $test X"$sPRId64" = X -a X"$quadtype" != X; then
    $cat >try.c <<EOCP
#include <sys/types.h>
#include <stdio.h>
int main() {
    $quadtype q = 12345678901;
    printf("%qd\n", q);
}
EOCP
set try
if eval $compile; then
    yyy=`$run ./try`
    case "$yyy" in
        12345678901)
            sPRId64=""qd"; sPRIi64=""qi"; sPRIu64=""qu";
            sPRIo64=""qo"; sPRIx64=""qx"; sPRIXU64=""qX";
            echo "We will use %qd."
            ;;
        esac
    fi
fi

```

```

if $test X"$sPRId64" = X; then
    echo "Cannot figure out how to print 64-bit integers." >&4
fi
$rm_try

fi

```

```

case "$sPRId64" in
*) d_PRId64="$undef"; d_PRIi64="$undef"; d_PRIu64="$undef";
   d_PRIo64="$undef"; d_PRIx64="$undef"; d_PRIXU64="$undef";
   ;;
*) d_PRId64="$define"; d_PRIi64="$define"; d_PRIu64="$define";
   d_PRIo64="$define"; d_PRIx64="$define"; d_PRIXU64="$define";
   ;;
esac

```

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-

debian-perl-5.26.1/U/perl/quadfio.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: vendorhtml3.U,v 1.1 1999/07/08 18:32:57 doughera Exp doughera \$

?RCS:

?RCS: Copyright (c) 1999, Andy Dougherty

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 3.0.

?RCS:

?RCS: \$Log: vendorhtml3.U,v \$

?RCS: Revision 1.1 1999/07/08 18:32:57 doughera

?RCS: Initial revision

?RCS:

?MAKE:vendorhtml3 vendorhtml3exp installvendorhtml3: html3dir Getfile \

Oldconfig Setprefixvar Prefixit test vendorprefix prefix sed

?MAKE: -pick add \$@ %<

?Y:TOP

?S:vendorhtml3:

?S: This variable contains the name of the directory for html

?S: library pages. It may have a ~ on the front.

?S: The standard distribution will put nothing in this directory.

?S: Vendors

who distribute perl may wish to place their own

?S: html pages for modules and extensions in this directory with

?S: MakeMaker Makefile.PL INSTALLDIRS=vendor

?S: or equivalent. See INSTALL for details.

?S:.

?S:vendorhtml3exp:

?S: This variable is the ~name expanded version of vendorhtml3, so that you

?S: may use it directly in Makefiles or shell scripts.

?S:.

?D:installvendorhtml3="

?S:installvendorhtml3:

?S: This variable is really the same as vendorhtml3exp but may differ on

?S: those systems using AFS. For extra portability, only this variable

?S: should be used in makefiles.

?S:.

?LINT:change prefixvar

?LINT:set installvendorhtml3

: Set the vendorhtml3 variables

case "\$vendorprefix" in

") vendorhtml3="

vendorhtml3exp="

::

*) : determine where vendor-supplied module html pages go.
: There is no standard location, so try to copy the previously-selected
: directory structure for the core html pages.
: XXX Better default suggestions would be welcome.

```
case "$vendorhtml3"
in
") dflt=`echo "$html3dir" | $sed "s#^$prefix#$vendorprefix#" ` ;;
*) dflt=$vendorhtml3 ;;
esac
case "$dflt" in
"|") dflt=none ;;
esac
fn=dn+~
rp='Pathname for the vendor-supplied html pages?'
./getfile
vendorhtml3="$ans"
vendorhtml3exp="$ansexp"
;;
esac
: Use ' ' for none so value is preserved next time through Configure
$test X"$vendorhtml3" = "X" && vendorhtml3=' '
prefixvar=vendorhtml3
./installprefix
```

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/installdirs/vendorhtml3.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: prototype.U,v \$

?RCS: Revision 3.0.1.3 1994/05/06 15:11:49 ram

?RCS: patch23: ensure cc flags used when looking for prototype support

?RCS:

?RCS: Revision 3.0.1.2 1994/01/24 14:15:36 ram

?RCS: patch16: prototype handling macros now appear only when needed

?RCS:

?RCS: Revision 3.0.1.1 1993/08/25 14:03:12 ram

?RCS: patch6: defines were referring to non-existent VOID symbol

?RCS:
?RCS: Revision 3.0 1993/08/18 12:09:36 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:prototype:
Myread Oldconfig cat +cc +ccflags rm Setvar
?MAKE: -pick add \$@ %<
?S:prototype:
?S: This variable holds the eventual value of CAN_PROTOTYPE, which
?S: indicates the C compiler can handle function prototypes.
?S:.
?C:CAN_PROTOTYPE ~ %<:
?C: If defined, this macro indicates that the C compiler can handle
?C: function prototypes.
?C:.
?C:DOTS:
?C: This macro is used to specify the ... in function prototypes which
?C: have arbitrary additional arguments.
?C:.
?C:NXT_ARG:
?C: This macro is used to separate arguments in the declared argument list.
?C:.
?C:P_FUNC:
?C: This macro is used to declare "private" (static) functions.
?C: It takes three arguments: the function type and name, a parenthesized
?C: traditional (comma separated) argument list, and the declared argument
?C: list (in which arguments are separated with NXT_ARG, and additional
?C: arbitrary arguments are specified with DOTS). For example:
?C:
?C: P_FUNC(int foo, (bar, baz), int bar NXT_ARG char *baz[])
?C:.
?C:P_FUNC_VOID:
?C: This
macro is used to declare "private" (static) functions that have
?C: no arguments. The macro takes one argument: the function type and name.
?C: For example:
?C:
?C: P_FUNC_VOID(int subr)
?C:.
?C:V_FUNC:
?C: This macro is used to declare "public" (non-static) functions.
?C: It takes three arguments: the function type and name, a parenthesized
?C: traditional (comma separated) argument list, and the declared argument
?C: list (in which arguments are separated with NXT_ARG, and additional
?C: arbitrary arguments are specified with DOTS). For example:
?C:
?C: V_FUNC(int main, (argc, argv), int argc NXT_ARG char *argv[])
?C:.

```

?C:V_FUNC_VOID:
?C: This macro is used to declare "public" (non-static) functions that have
?C: no arguments. The macro takes one argument: the function type and name.
?C: For example:
?C:
?C: V_FUNC_VOID(int fork)
?C:.
?C:_ (P):
?C: This macro is used to declare function parameters for folks who want
?C: to make declarations with prototypes using a
?C: different style than
?C: the above macros. Use double parentheses. For example:
?C:
?C: int main _((int argc, char *argv[]));
?C:.
?H:%<:#$prototype CAN_PROTOTYPE /**/
?H:%<:#ifdef CAN_PROTOTYPE
?H:?NXT_ARG:#define NXT_ARG ,
?H:?DOTS:#define DOTS , ...
?H:?V_FUNC:#define V_FUNC(name, arglist, args)name(args)
?H:?P_FUNC:#define P_FUNC(name, arglist, args)static name(args)
?H:?V_FUNC_VOID:#define V_FUNC_VOID(name)name(void)
?H:?P_FUNC_VOID:#define P_FUNC_VOID(name)static name(void)
?H:?_:#define _(args) args
?H:%<:#else
?H:?NXT_ARG:#define NXT_ARG ;
?H:?DOTS:#define DOTS
?H:?V_FUNC:#define V_FUNC(name, arglist, args)name arglist args;
?H:?P_FUNC:#define P_FUNC(name, arglist, args)static name arglist args;
?H:?V_FUNC_VOID:#define V_FUNC_VOID(name)name()
?H:?P_FUNC_VOID:#define P_FUNC_VOID(name)static name()
?H:?_:#define _(args) ()
?H:%<:#endif
?H:.
?W:%<:NXT_ARG DOTS V_FUNC P_FUNC V_FUNC_VOID P_FUNC_VOID _
?LINT:set prototype
: Cruising for prototypes
echo " "
echo "Checking out
function prototypes..." >&4
$cat >prototype.c <<'EOCP'
int main(int argc, char *argv[]) {
    exit(0);}
EOCP
if $cc $ccflags -c prototype.c >prototype.out 2>&1 ; then
    echo "Your C compiler appears to support function prototypes."
    val="$define"
else

```

```
echo "Your C compiler doesn't seem to understand function prototypes."
val="$undef"
fi
set prototype
eval $setvar
$rm -f prototype*
```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/prototype.U
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_havetlib.U 1 2006-08-24 12:32:52Z rmanfredi \$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic Licence,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic Licence; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: d_havetlib.U,v \$

?RCS: Revision 3.0.1.2 1997/02/28 15:36:31 ram

?RCS: patch61: replaced .a with \$_a all over the place

?RCS: patch61: likewise for .o replaced by \$_o

?RCS:

?RCS: Revision 3.0.1.1 1994/05/06 14:44:06 ram

?RCS: patch23: added AIX support to accept shared lib stub as termlib (WED)

?RCS:

?RCS: Revision 3.0 1993/08/18 12:06:19 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?MAKE:d_havetlib termlib: cat contains Myread Loc

Filexp Oldconfig libpth \

test uname _a _o

?MAKE: -pick add \$@ %<

?S:d_havetlib:

?S: This variable conditionally defines the HAS_TERMLIB symbol, which

?S: indicates to the C program that termlib-style routines are available.

?S:.

?S:termlib:

?S: This variable contains the argument to pass to the loader to get

?S: termlib-style routines. It is up to the Makefile.SH to make sure

?S: the value gets to the right command. Note that on many systems the

?S: termlib routines are emulated by the curses or terminfo library.

?S:.

?C:HAS_TERMLIB (HAVETERMLIB):

?C: This symbol, when defined, indicates that termlib-style routines

?C: are available. There is nothing to include.

?C:.

?H:#\$d_havetlib HAS_TERMLIB /**/

?H:.

?T:xxx

: where do we get termlib routines from

echo " "

xxx=`./loc libcurses\$_a x \$libpth`

case "\$xxx" in

/*)

ar t \$xxx >grimble

if \$contains tputs\$_o grimble >/dev/null 2>&1; then

termlib='-lcurses'

d_havetlib="\$define"

echo "Terminfo library found." >&4

elif \$test "x`\$uname

2>/dev/null" = xAIX; then

Ok, do the AIX shr.o fun thing

/usr/ccs/bin/nm -en \$xxx 2>/dev/null >grimble

if \$contains '^tputs.*|extern|' grimble >/dev/null 2>&1; then

termlib='-lcurses'

d_havetlib="\$define"

echo "AIX Terminfo library found." >&4

else

xxx=x

fi

else

xxx=x

fi

rm -f grimble

::

esac

case "\$xxx" in

x)

xxx=`./loc libtermlib\$_a x \$libpth`

case "\$xxx" in

/usr/lib*/lib*)

termlib='-ltermlib'

d_havetlib="\$define"

echo "Termlib library found." >&4

::

/*)

termlib="\$xxx"

d_havetlib="\$define"

echo "Termlib library found." >&4

::

*)

```

xxx=`./loc libtermcap$_a x $libpth`
case "$xxx" in
/usr/lib*/lib*)
termlib='-ltermcap'
d_havetlib="$define"
echo "Termcap library found." >&4
;;
*)
termlib="$xxx"
d_havetlib="$define"
echo "Termcap library found." >&4
;;
*)
case "$termlib" in
")
dflt=y
rp="Your system appears to NOT have termlib-style routines. Is this true?"
./myread
case "$ans"
in
n*|f*) d_havetlib="$define"
$cat <<'EOM'
Then where are the termlib-style routines kept? Specify either -llibname
or a full pathname (~name ok).

```

EOM

```

dflt="
rp='Specify termlib path:'
./myread
termlib=`./filexp $ans`
;;
*)
d_havetlib="$undef"
termlib="
echo "You will have to play around with term.c then." >&4
;;
esac
echo " ";;
*) echo "You said termlib was $termlib before." >&4;;
esac;;
esac;;
esac

```

Found in path(s):

```

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/d_havetlib.U

```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: lex.U 1 2006-08-24 12:32:52Z rmanfredi $
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: Original Author: Graham Stoney <greyham@research.canon.oz.au>
?RCS:
?RCS: $Log: lex.U,v $
?RCS: Revision 3.0.1.3 1994/10/29 16:22:50 ram
?RCS: patch36: spurious single quote could cause Configure to crash
?RCS: patch36: (reported by Xavier Le Vouch <xavierl@eiffel.com>.)
?RCS:
?RCS: Revision 3.0.1.2 1994/08/29 16:27:09 ram
?RCS: patch32: added lexflags variable for lex flags setting
?RCS:
?RCS: Revision 3.0.1.1 1994/05/06 15:06:01 ram
?RCS: patch23: added
trailing blank line for metalint
?RCS:
?RCS: Revision 3.0 1993/08/18 12:08:55 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:lex lexflags: Guess Myread Oldconfig flex test
?MAKE: -pick add $@ %<
?S:lex:
?S: This variable holds the name of the lexical analyser generator we
?S: want to use in the Makefile. It can be lex or flex.
?S:.
?S:lexflags:
?S: This variable holds any flags that should be passed to the lexical
?S: analyzer. It is up to the Makefile to use it.
?S:.
: determine lexical analyser generator
case "$lex" in
")
dflt=lex;;
*)
dflt="$lex";;
esac
echo " "
if $test -f "$flex"; then
```

```

rp='Which lexical analyser generator (lex or flex) shall I use?'
else
rp='Which lexical analyser generator shall I use?'
fi
./myread
lex="$ans"

@if lexflags
: if using lex this will normally be useless, but flex frequently takes args
echo " "
case "$lexflags" in
") dflt='none';;
*) dflt="$lexflags";;
esac
rp="What flags should be given to $lex?"
./myread
case "$ans"
in
none) lexflags="";;
*) lexflags="$ans";;
esac

@end

```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/lex.U
```

No license file was found, but licenses were detected in source scan.

```

?RCS: $Id: inc_version_list.U,v $
?RCS:
?RCS: Copyright (c) 2000 Andy Dougherty
?RCS:
?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 3.0.
?RCS:
?RCS: $Log: inc_version_list.U,v $
?RCS:
?MAKE:inc_version_list inc_version_list_init d_inc_version_list: cat sed \
Getfile perl5 version api_versionstring rm Myread archname \
prefix sitelib_stem exe_ext
?MAKE: -pick add $@ %<
?Y:TOP
?S:inc_version_list:
?S: This variable specifies the list of subdirectories in over

```

?S: which perl.c:incpush() and lib/lib.pm will automatically
 ?S: search when adding directories to @INC. The elements in
 ?S: the list are separated by spaces. This is only useful
 ?S: if
 you have a perl library directory tree structured like the
 ?S: default one. See INSTALL for how this works. The versioned
 ?S: site_perl directory was introduced in 5.005, so that is the
 ?S: lowest possible value.
 ?S:
 ?S: This list includes architecture-dependent directories back to
 ?S: version \$api_versionstring (e.g. 5.5.640) and
 ?S: architecture-independent directories all the way back to
 ?S: 5.005.
 ?S:.
 ?S:inc_version_list_init:
 ?S: This variable holds the same list as inc_version_list, but
 ?S: each item is enclosed in double quotes and separated by commas,
 ?S: suitable for use in the PERL_INC_VERSION_LIST initialization.
 ?S:.
 ?S:d_inc_version_list:
 ?S: This variable conditionally defines PERL_INC_VERSION_LIST.
 ?S: It is set to undef when PERL_INC_VERSION_LIST is empty.
 ?S:.
 ?C:PERL_INC_VERSION_LIST:
 ?C: This variable specifies the list of subdirectories in over
 ?C: which perl.c:incpush() and lib/lib.pm will automatically
 ?C: search when adding directories to @INC, in a format
 suitable
 ?C: for a C initialization string. See the inc_version_list entry
 ?C: in Porting/Glossary for more details.
 ?C:.
 ?H:#\$d_inc_version_list PERL_INC_VERSION_LIST \$inc_version_list_init /**/
 ?H:.
 ?T:stem
 : Determine list of previous versions to include in @INC
 \$cat > getverlist <<EOPL
 #!\$perl5 -w
 use File::Basename;
 \ \$api_versionstring = "\$api_versionstring";
 \ \$version = "\$version";
 \ \$stem = "\$sitelib_stem";
 \ \$archname = "\$archname";
 EOPL
 \$cat >> getverlist <<'EOPL'
 # The list found is store twice for each entry: the original name, and
 # the binary broken down version as pack "sss", so sorting is easy and
 # unambiguous. This will work for all versions that have a maximum of
 # three digit groups, separate by '.'s or '_'s. Names are extended with

```

# ".0.0" to ensure at least three elements for the pack.
# -- H.Merijn Brand (m)'06 23-10-2006

# Can't have leading @ because metaconfig interprets it as a command!
;@inc_version_list=();
# XXX Redo to do opendir/readdir?
if (-d
$stem) {
  chdir($stem);
  ;@candidates = map {
[ $_, pack "sss", split m/[._]/, "$_.0.0" ] } glob("5.*");
  ;@candidates = sort { $a->[1] cmp $b->[1]} @candidates;
}
else {
  ;@candidates = ();
}

($pversion, $saverion, $vsn5005) = map {
  pack "sss", split m/[._]/, "$_.0.0" } $version, $api_versionstring, "5.005";
foreach $d (@candidates) {
  if ($d->[1] lt $pversion) {
  if ($d->[1] ge $saverion) {
    unshift(@inc_version_list, grep { -d } $d->[0]."/${archname}", $d->[0]);
  }
  elsif ($d->[1] ge $vsn5005) {
    unshift(@inc_version_list, grep { -d } $d->[0]);
  }
  }
  else {
# Skip newer version. I.e. don't look in
# 5.7.0 if we're installing 5.6.1.
  }
}

if (@inc_version_list) {
  print join(' ', @inc_version_list);
}
else {
  # Blank space to preserve value for next Configure run.
  print " ";
}
EOPL
chmod +x getverlist
case "$inc_version_list" in
") if test -x "$perl5$exe_ext"; then
  dflt=`$perl5 getverlist`
else
  dflt='none'

```

```

fi
;;
$undef) dflt='none'
;;
?X:  Configure -Dinc_version_list='5.6.0/$archname 5.6.0' ...
*) eval dflt=\"${inc_version_list}\" ;;
esac
case "$dflt" in
'| ') dflt=none ;;
esac
case "$dflt" in
5.005) dflt=none ;;
esac
$cat <<EOM

```

In order to ease the process of upgrading, this version of perl can be configured to use modules built and installed with earlier versions of perl that were installed under \$prefix. Specify here the list of earlier versions that this version of perl should check. If Configure detected no earlier versions of perl installed under \$prefix, then the list will be empty. Answer 'none' to tell perl to not search earlier versions.

The default should almost always be sensible, so if you're not sure, just accept the default.

EOM

```

rp='List of earlier versions to include in @INC?'
./myread
case "$ans" in
[Nn]one|'| '$undef) inc_version_list=' ' ;;
*) inc_version_list="$ans" ;;
esac
case "$inc_version_list" in
'| ')
inc_version_list_init='0'
d_inc_version_list="$undef"
;;
*) inc_version_list_init=`echo
$inc_version_list |
$sed -e 's/^/' -e 's/ /","/g' -e 's/$/',0/'
d_inc_version_list="$define"
;;
esac
$rm -f getverlist

```

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-

debian-perl-5.26.1/U/installdirs/inc_version_list.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: i_poll.U,v \$

?RCS:

?RCS: Copyright (c) 1998 Jarkko Hietaniemi

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?MAKE:i_poll: Inhdr Hasfield

?MAKE: -pick add \$@ %<

?S:i_poll:

?S: This variable conditionally defines the I_POLL symbol, and indicates

?S: whether a C program should include <poll.h>.

?S:.

?C:I_POLL:

?C: This symbol, if defined, indicates that <poll.h> exists and

?C: should be included. (see also HAS_POLL)

?C:.

?H:#\$i_poll I_POLL /**/

?H:.

?LINT:set i_poll

: see if this is a poll.h system

set poll.h i_poll

eval \$inhdr

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-

debian-perl-5.26.1/U/perl/i_poll.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_flexfnam.U 1 2006-08-24 12:32:52Z rmanfredi \$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: d_flexfnam.U,v \$

?RCS: Revision 3.0 1993/08/18 12:06:04 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?MAKE:d_flexfnam: cat rm test Setvar

?MAKE: -pick add \$@ %<

?S:d_flexfnam:

?S: This variable conditionally defines the FLEXFILENAMES symbol, which

?S: indicates that the system supports filenames longer than 14 characters.

?S:.

?C:FLEXFILENAMES:

?C: This symbol, if defined, indicates that the system supports filenames

?C: longer than 14

characters.

?C:.

?H:#\$d_flexfnam FLEXFILENAMES /**/

?H:.

?T:first

?LINT:set d_flexfnam

: see if we can have long filenames

echo " "

?X:

?X: We have to test in both /tmp and . because of NFS (remote server may allow

?X: long filenames while the local filesystem cannot support them). If at least

?X: one of those file systems cannot support long filenames, then we assume the

?X: whole system can't.

?X:

first=123456789abcdef

\$rm -f \$first

if (echo hi >\$first) 2>/dev/null; then

if \$test -f 123456789abcde; then

echo 'You cannot have filenames longer than 14 characters. Sigh.'>&4

val="\$undef"

else

echo 'You can have filenames longer than 14 characters.'>&4

val="\$define"

fi

else

\$cat <<'EOM'

You can't have filenames longer than 14 chars.

You can't even think about them!

EOM

val="\$undef"

fi

set d_flexfnam

eval \$setvar

\$rm -rf 123456789abcde*

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/modified/d_flexfnam.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: i_locale.U 1 2006-08-24 12:32:52Z rmanfredi \$

```

?RCS:
?RCS: Copyright (c) 1996, Andy Dougherty
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: $Log: i_locale.U,v $
?RCS: Revision 3.0.1.1 1997/02/28 15:48:23 ram
?RCS: patch61: created
?RCS:
?MAKE:i_locale: Inhdr
?MAKE: -pick add $@ %<
?S:i_locale:
?S: This variable conditionally defines the I_LOCALE symbol,
?S: and indicates whether a C program should include <locale.h>.
?S:.
?C:I_LOCALE:
?C: This symbol, if defined, indicates to the C program that it should
?C: include <locale.h>.
?C:.
?H:#$i_locale I_LOCALE /**/
?H:.
?LINT:set
i_locale
: see if locale.h is available
set locale.h i_locale
eval $inhdr

```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/i_locale.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: You may redistribute only under the terms of the Artistic License,
```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/compline/d_scannl.U
```

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/modified/d_getpgrp.U
```

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_gai_strerror.U
```

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/compline/d_keepsig.U
```

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_ldbl_dig.U

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/compline/sunscanf.U

*

/opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_wcscmp.U

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/typedefs/pidsign.U

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/fpu.U

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/compline/d_open3.U

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/compline/d_casti32.U

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/d_vprintf.U

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/st_ino_def.U

*

/opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/fpssize.U

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/gccvers.U

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/alignbytes.U

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/d_const.U

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/ptrsize.U

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/sockopt.U

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/d_getpagsz.U

*

/opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/floatsize.U

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/abortsig.U

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/d_attribut.U

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/compline/sbrksmart.U

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/d_strtcpy.U

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/compline/charsize.U

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-

debian-perl-5.26.1/U/typedefs/gidsign.U
*
/opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/intsize.U
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_int64_t.U
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_wcsxfrm.U
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/compline/sockopt.U
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/compline/d_sgnchr.U
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/d_open3.U
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/doublesize.U
*
/opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/d_scannl.U
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/d_volatile.U
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/typedefs/pidsize.U
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/modified/i_malloc.U
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/compline/ssizetype.U
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_dir_dd_fd.U
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/ebcdic.U
*
/opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/d_isascii.U
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/nullified/fpu.U
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/i_inttypes.U
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/typedefs/gidsize.U
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/need_va_copy.U
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/i_neterrno.U
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/compline/floatsize.U
*

/opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/compline/abortsig.U
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/d_sgndchr.U
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/compline/alignbytes.U
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/typedefs/sizesize.U
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/compline/d_eofpipe.U
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/sunscanf.U
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_builtin.U
*
/opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/Checkcc.U
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/stdio_streams.U
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/byteorder.U
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/randbits.U
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_isblank.U
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/compline/ptrsize.U
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/gccvers.U
*
/opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/modified/i_neterrno.U
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/bitpbyte.U
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/modified/d_const.U
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/ssizetype.U
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/typedefs/uidsize.U
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/d_getpgrp.U
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/selectminbits.U
*
/opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_snprintf.U
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-

debian-perl-5.26.1/dist/U/charsize.U
 * /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
 debian-perl-5.26.1/dist/U/d_access.U
 * /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
 debian-perl-5.26.1/dist/U/d_sanemcmp.U
 * /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
 debian-perl-5.26.1/dist/U/d_sigaction.U
 * /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
 debian-perl-5.26.1/U/modified/d_mmap.U
 * /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
 debian-perl-5.26.1/dist/U/d_keepsig.U
 *
 /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
 debian-perl-5.26.1/U/perl/d_c99_variadic.U
 * /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
 debian-perl-5.26.1/U/compline/doublesize.U
 * /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
 debian-perl-5.26.1/U/compline/d_isascii.U
 * /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
 debian-perl-5.26.1/U/typedefs/uidsign.U
 * /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
 debian-perl-5.26.1/U/compline/d_sigaction.U
 * /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
 debian-perl-5.26.1/U/perl/d_lc_monetary_2008.U
 * /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
 debian-perl-5.26.1/U/compline/d_sanemcmp.U
 *
 /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
 debian-perl-5.26.1/U/modified/d_volatile.U
 * /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
 debian-perl-5.26.1/dist/U/startperl.U
 * /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
 debian-perl-5.26.1/U/compline/bitpbyte.U
 * /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
 debian-perl-5.26.1/dist/U/d_eofpipe.U
 * /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
 debian-perl-5.26.1/dist/U/sbrksmart.U
 * /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
 debian-perl-5.26.1/U/typedefs/ssizesize.U
 *
 /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
 debian-perl-5.26.1/dist/U/d_casti32.U
 * /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
 debian-perl-5.26.1/U/perl/d_socklen_t.U
 * /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
 debian-perl-5.26.1/U/modified/d_strtoul.U
 * /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
 debian-perl-5.26.1/U/perl/d_dirfd.U

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/modified/d_access.U

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_u32align.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: libperl.U,v \$

?RCS:

?RCS: Copyright (c) 1996-1998, Andy Dougherty

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?MAKE:libperl useshrplib shrpenv ldlibpthname: \
Myread Oldconfig archlibexp awk cat libc \
_a osname osvers so patchlevel subversion usedl ld \
ccdlflags installarchlib userelocatableinc

?MAKE: -pick wipe \$@ %<

?S:libperl:

?S: The perl executable is obtained by linking perlmain.c with

?S: libperl, any static extensions (usually just DynaLoader),

?S: and any other libraries needed on this system. libperl

?S: is usually libperl.a, but can also be libperl.so.xxx if

?S: the user wishes to build a perl executable with a shared

?S: library.

?S:.

?S:useshrplib:

?S: This variable is set to 'true' if the user wishes

?S: to build a shared libperl, and 'false' otherwise.

?S:.

?S:shrpenv:

?S: If

the user builds a shared libperl.so, then we need to tell the

?S: 'perl' executable where it will be able to find the installed libperl.so.

?S: One way to do this on some systems is to set the environment variable

?S: LD_RUN_PATH to the directory that will be the final location of the

?S: shared libperl.so. The makefile can use this with something like

?S: \$shrpenv \$(CC) -o perl perlmain.o \$libperl \$libs

?S: Typical values are

?S: shrpenv="env LD_RUN_PATH=\$archlibexp/CORE"

?S: or

?S: shrpenv="

?S: See the main perl Makefile.SH for actual working usage.

?S: Alternatively, we might be able to use a command line option such

?S: as -R \$archlibexp/CORE (Solaris) or -Wl,-rpath

?S: \$archlibexp/CORE (Linux).

?S:.

?S:ldlibpthname:

```

?S: This variable holds the name of the shared library
?S: search path, often LD_LIBRARY_PATH. To get an empty
?S: string, the hints file must set this to 'none'.
?S:.
?T:shrpdir majonly majmin also xxx tmp_shrpenv
?X: metalint gets confused and thinks we're
    actually setting LDOPTS
?X: and LD_RUN_PATH.
?LINT:extern LDOPTS
?LINT:change LDOPTS
?LINT:extern LD_RUN_PATH
?LINT:change LD_RUN_PATH
?LINT:change ccdlflags
?LINT:extern maintloc maintname
?Y:top
: Do we want a shared libperl?
also="
case "$usedl" in
$undef)
    # No dynamic loading being used, so don't bother even to prompt.
    useshrplib='false'
    ;;
*) case "$useshrplib" in
    ") case "$osname" in
        svr4*|nonstopux|dgux|dynixptx|esix|powerux|haiku|cygwin*)
            dflt=y
            also='Building a shared libperl is required for dynamic loading to work on your system.'
            ;;
        *) dflt=n
            ;;
    esac
    ;;
$define[true][Yy]*)
    dflt=y
    ;;
*) dflt=n
    ;;
esac
$cat << EOM

```

The perl executable is normally obtained by linking perlmain.c with libperl\${_a}, any static extensions (usually just DynaLoader), and any other libraries needed on this system (such as -lm, etc.). Since your system supports dynamic loading, it is probably possible to build a shared libperl.\$so. If you will have more than one executable linked to libperl.\$so, this will significantly reduce the size of each executable, but it may have a noticeable effect on performance. The

default is probably sensible for your system.

\$also

EOM

```
rp="Build a shared libperl.$so (y/n)"
. ./myread
case "$ans" in
true|$define[[Yy]*)
  useshrplib='true' ;;
*) useshrplib='false' ;;
esac
;;
esac

case "$useshrplib" in
true)
  case "$userelocatableinc" in
true|define)
    echo "Cannot build with both -Duserelocatableinc and -Duseshrplib" >&4
    echo "See INSTALL for an explanation why that won't work." >&4
    exit 4
    ;;
esac
case "$libperl" in
")
  # Figure out a good name for libperl.so. Since it gets stored in
  # a version-specific architecture-dependent library, the version
  # number isn't really that important, except for making cc/ld happy.
  #
  # A name such as libperl.so.10.1
  majmin="libperl.$so.$patchlevel.$subversion"
  # A name such as libperl.so.100
  majonly=`echo $patchlevel $subversion |
  $awk '{printf
"%d%02d", $1, $2}`
  majonly=libperl.$so.$majonly
  # I'd prefer to keep the os-specific stuff here to a minimum, and
  # rely on figuring it out from the naming of libc.
  case "${osname}${osvers}" in
*linux*|gnu*) # ld won't link with a bare -lperl otherwise.
    dflt=libperl.$so
    ;;
cygwin*) # ld links now against the dll directly
    majmin="cygperl5_${patchlevel}_${subversion}.${so}"
    majonly=`echo $patchlevel $subversion |
    $awk '{printf "%03d%03d", $1, $2}`
    majonly=cygperl5.$majonly.$so
    dflt=$majmin
```

```

;;
*) # Try to guess based on whether libc has major.minor.
case "$libc" in
*libc.$so.[0-9]*.[0-9]*) dflt=$majmin ;;
*libc.$so.[0-9]*) dflt=$majonly ;;
*) dflt=libperl.$so ;;
esac
;;
esac
;;
*) dflt=$libperl
;;
esac
cat << EOM

```

I need to select a good name for the shared libperl. If your system uses library names with major and minor numbers, then you might want something like \$majmin. Alternatively, if your system uses a single version number for shared libraries, then you might want to use \$majonly. Or, your system might be quite happy with a simple libperl.\$so.

Since the shared libperl will get installed into a version-specific architecture-dependent directory, the version number of the shared perl library probably isn't important, so the default should be o.k.

```

EOM
rp='What name do you want to give to the shared libperl?'
./myread
libperl=$ans
echo "Ok, I'll use $libperl"
;;
*)
libperl="libperl${_a}"
;;
esac

```

```

# Detect old use of shrpdir via undocumented Configure -Dshrpdir
case "$shrpdir" in
") ;;
*) $cat >&4 <<EOM
WARNING: Use of the shrpdir variable for the installation location of
the shared $libperl is not supported. It was never documented and
will not work in this version. Let me (<$maintloc>)
know of any problems this may cause.

```

```

EOM
case "$shrpdir" in

```

```
"$archlibexp/CORE")
```

```
$cat >&4 <<EOM
```

But your current setting of \$shrpdir is the default anyway, so it's harmless.

```
EOM
```

```
::
```

```
*)
```

```
$cat >&4
```

```
<<EOM
```

Further, your current attempted setting of \$shrpdir conflicts with the value of \$archlibexp/CORE that installperl will use.

```
EOM
```

```
::
```

```
esac
```

```
::
```

```
esac
```

```
# How will the perl executable find the installed shared $libperl?
```

```
# Add $xxx to ccdlflags.
```

```
# If we can't figure out a command-line option, use $shrpdir to
```

```
# set env LD_RUN_PATH. The main perl makefile uses this.
```

```
shrpdir=$archlibexp/CORE
```

```
xxx=""
```

```
tmp_shrpdir=""
```

```
if "$useshrplib"; then
```

```
  case "$osname" in
```

```
    aix)
```

```
      # We'll set it in Makefile.SH...
```

```
      ::
```

```
    solaris)
```

```
      xxx="-R $shrpdir"
```

```
      ::
```

```
    freebsd|mirbsd|netbsd|openbsd|interix|dragonfly|bitrig)
```

```
      xxx="-Wl,-R,$shrpdir"
```

```
      ::
```

```
    bsdos|linux|irix*|dec_osf|gnu*|haiku)
```

```
      xxx="-Wl,-rpath,$shrpdir"
```

```
      ::
```

```
    hpux*)
```

```
      # hpux doesn't like the default, either.
```

```
      tmp_shrpdir="env LDOPTS=\"+s +b${shrpdir}\""
```

```
      ::
```

```
    cygwin)
```

```
      # cygwin needs only ldlibpth
```

```
      ::
```

```
  *)
```

```
    tmp_shrpdir="env LD_RUN_PATH=$shrpdir"
```

```

;;
esac
case "$xxx" in
") ;;
*)
# Only add $xxx if it isn't already in ccdlflags.
case " $ccdlflags
" in
*" $xxx "*) ;;
*) ccdlflags="$ccdlflags $xxx"
cat <<EOM >&4

```

Adding \$xxx to the flags
passed to \$ld so that the perl executable will find the
installed shared \$libperl.

```

EOM
;;
esac
;;
esac
fi
# Fix ccdlflags in AIX for building external extensions.
# (For building Perl itself bare -bE:perl.exp is needed,
# Makefile.SH takes care of this.)
case "$osname" in
aix) ccdlflags="$ccdlflags -bE:$installarchlib/CORE/perl.exp" ;;
esac
# Respect a hint or command-line value.
case "$shrpenv" in
") shrpenv="$tmp_shrpenv" ;;
esac
case "$ldlibpthname" in
") ldlibpthname=LD_LIBRARY_PATH ;;
none) ldlibpthname="" ;;
esac

```

Found in path(s):

```

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/perl/libperl.U

```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_bzero.U 1 2006-08-24 12:32:52Z rmanfredi \$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic Licence,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: \$Log: d_bzero.U,v \$
?RCS: Revision 3.0.1.2 1993/10/16 13:48:15 ram
?RCS: patch12: added magic support for bzero()
?RCS:
?RCS: Revision 3.0.1.1 1993/09/13 16:01:33 ram
?RCS: patch10: now only defines HAS_BZERO, no macro remap on memset (WAD)
?RCS:
?RCS: Revision 3.0 1993/08/18 12:05:46 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:d_bzero: Inlibc
?MAKE: -pick add \$@ %<
?S:d_bzero:
?S: This variable conditionally defines the HAS_BZERO
symbol if
?S: the bzero() routine is available to set memory to 0.
?S:.
?C:HAS_BZERO:
?C: This symbol is defined if the bzero() routine is available to
?C: set a memory block to 0.
?C:.
?H:#\$d_bzero HAS_BZERO /**/
?H:.
?M:bzero: HAS_BZERO
?M:#ifndef HAS_BZERO
?M:#ifndef bzero
?M:#define bzero(s,l) memset((s),0,(l))
?M:#endif
?M:#endif
?M:.
?LINT:set d_bzero
: see if bzero exists
set bzero d_bzero
eval \$inlibc

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/d_bzero.U

No license file was found, but licenses were detected in source scan.

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?MAKE:d_log1p: Inlibc

?MAKE: -pick add \$@ %<
?S:d_log1p:
?S: This variable conditionally defines the HAS_LOG1P symbol, which
?S: indicates to the C program that the logp1() routine is available
?S: to compute log(1 + x) for values of x close to zero.
?S:.
?C:HAS_LOG1P:
?C: This symbol, if defined, indicates that the log1p routine is
?C: available to do the logarithm of 1 plus argument function.
?C:.
?H:#\$d_log1p HAS_LOG1P /**/
?H:.
?LINT:set d_log1p
: see if log1p exists
set log1p d_log1p
eval \$inlibc

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_log1p.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$
?RCS:
?RCS: Copyright (c) 2001 Jarkko Hietaniemi
?RCS:
?RCS: You may distribute under the terms of either the GNU General Public
?RCS: License or the Artistic License, as specified in the README file.
?RCS:
?MAKE:d_nl_langinfo: Inlibc i_langinfo
?MAKE: -pick add \$@ %<
?S:d_nl_langinfo:
?S: This variable conditionally defines the HAS_NL_LANGINFO symbol, which
?S: indicates to the C program that the nl_langinfo() routine is available.
?S:.
?C:HAS_NL_LANGINFO:
?C: This symbol, if defined, indicates that the nl_langinfo routine is
?C: available to return local data. You will also need <langinfo.h>
?C: and therefore I_LANGINFO.
?C:.
?H:#\$d_nl_langinfo HAS_NL_LANGINFO /**/
?H:.
?LINT:set d_nl_langinfo
?LINT:use i_langinfo
: see if nl_langinfo exists
set nl_langinfo d_nl_langinfo
eval \$inlibc

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_nl_langinfo.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: Guess.U,v \$

?RCS: Revision 3.0.1.5 1995/07/25 13:37:14 ram

?RCS: patch56: now knows about OS/2 platforms

?RCS:

?RCS: Revision 3.0.1.4 1994/10/29 15:53:55 ram

?RCS: patch36: added ?F: line for metalint file checking

?RCS: patch36: call ./xenix explicitly instead of relying on PATH

?RCS:

?RCS: Revision 3.0.1.3 1993/12/15 08:14:35 ram

?RCS: patch15: variable d_bsd was not always set properly

?RCS:

?RCS: Revision 3.0.1.2 1993/08/30 08:57:14 ram

?RCS: patch8: fixed comment which wrongly
attributed the usrinc symbol

?RCS: patch8: no more ugly messages when no /usr/include/ctype.h

?RCS:

?RCS: Revision 3.0.1.1 1993/08/27 14:37:37 ram

?RCS: patch7: added support for OSF/1 machines

?RCS:

?RCS: Revision 3.0 1993/08/18 12:04:57 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?X:

?X: This unit hazards some guesses as to what the general nature of the system

?X: is. The information it collects here is used primarily to establish default

?X: answers to other questions.

?X:

?MAKE:Guess d_eunice d_xenix d_bsd d_linux d_dos d_os2: cat test echo n c \
contains rm tr Loc eunicefix

?MAKE: -pick add \$@ %<

?S:d_eunice:

?S: This variable conditionally defines the symbols EUNICE_SYSTEM, which

?S: alerts the C program that it must deal with ideosyncracies of VMS.

?S:.

?S:d_xenix:

?S: This variable conditionally defines the symbol XENIX_SYSTEM, which alerts

?S: the C program that it runs under Xenix.

?S:.

?S:d_dos:

?S: This symbol conditionally defines the symbol DOS_SYSTEM
when running on

?S: DOS with DJGPP or Cygwin.

?S:.

?S:d_os2:

?S: This symbol conditionally defines the symbol OS2_SYSTEM when running on

?S: an OS/2 system.

?S:.

?S:d_bsd:

?S: This symbol conditionally defines the symbol BSD_SYSTEM when running on a

?S: BSD system.

?S:.

?S:d_linux:

?S: This symbol conditionally defines the symbol LINUX_SYSTEM when running

?S: on a Linux system.

?S:.

?C:EUNICE_SYSTEM (EUNICE):

?C: This symbol, if defined, indicates that the program is being compiled

?C: under the EUNICE package under VMS. The program will need to handle

?C: things like files that don't go away the first time you unlink them,

?C: due to version numbering. It will also need to compensate for lack

?C: of a respectable link() command.

?C:.

?C:VMS_SYSTEM (VMS):

?C: This symbol, if defined, indicates that the program is running under

?C: VMS. It is currently only set in conjunction with the EUNICE symbol.

?C:.

?C:XENIX_SYSTEM (XENIX):

?C: This symbol, if defined, indicates that the program

is running under

?C: Xenix (at least 3.0 ?).

?C:.

?C:DOS_SYSTEM:

?C: This symbol, if defined, indicates that the program is running under

?C: DOS with DJGPP.

?C:.

?C:OS2_SYSTEM:

?C: This symbol, if defined, indicates that the program is running under

?C: an OS/2 system.

?C:.

?C:BSD_SYSTEM:

?C: This symbol, if defined, indicates that the program is running under

```

?C: a BSD system.
?C:.
?C:LINUX_SYSTEM:
?C: This symbol, if defined, indicates that the program is running under
?C: a Linux system.
?C:.
?H:#$d_eunice EUNICE_SYSTEM /**/
?H:#$d_eunice VMS_SYSTEM /**/
?H:#$d_xenix XENIX_SYSTEM /**/
?H:#$d_dos DOS_SYSTEM /**/
?H:#$d_os2 OS2_SYSTEM /**/
?H:#$d_bsd BSD_SYSTEM /**/
?H:#$d_linux LINUX_SYSTEM /**/
?H:.
?F:./bsd ./usg ./v7 ./osf1 ./eunice ./xenix ./venix ./dos ./os2 ./gnu ./linux
?T:xxx DJGPP MACHTYPE
: make some quick guesses about what we are up against
echo " "
$echo $n "Hmm... $c"
echo exit 1 >bsd
echo exit 1 >usg
echo exit 1 >v7
echo exit 1 >osf1
echo exit 1 >eunice
echo
  exit 1 >xenix
echo exit 1 >venix
echo exit 1 >os2
echo exit 1 >gnu
echo exit 1 >linux
echo exit 1 >dos
d_bsd="$undef"
d_linux="$undef"
d_dos="$undef"
d_os2="$undef"
?X:
?X: Do not use 'usrinc', or we get a circular dependency. because
?X: usrinc is defined in usrinc.U, which relies on us...
?X:
$cat /usr/include/signal.h /usr/include/sys/signal.h >foo 2>/dev/null
if test -f /osf_boot || $contains 'OSF/1' /usr/include/ctype.h >/dev/null 2>&1
then
  echo "Looks kind of like an OSF/1 system, but we'll see..."
  echo exit 0 >osf1
elif test `echo abc | $tr a-z A-Z` = Abc ; then
  xxx=`./loc addbib blurfl $pth`
  if $test -f $xxx; then
    echo "Looks kind of like a USG system with BSD features, but we'll see..."

```

```

echo exit 0 >bsd
echo exit 0 >usg
else
if $contains SIGTSTP foo >/dev/null 2>&1 ; then
    echo "Looks kind of like an extended USG system, but we'll see..."
else
    echo "Looks kind of like a USG system, but we'll see..."
fi
echo exit 0 >usg
fi
elif $contains SIGTSTP foo >/dev/null
2>&1 ; then
echo "Looks kind of like a BSD system, but we'll see..."
d_bsd="$define"
echo exit 0 >bsd
elif
$rm --version 2>/dev/null >foo;
$contains "Free Software Foundation" foo >/dev/null
then
xxx=`uname`
echo exit 0 >gnu
echo "Looks kind of like a GNU/$xxx system, but we'll see..."
if $test X$xxx = XLinux; then
    d_linux="$define"
    echo exit 0 >linux
fi
else
echo "Looks kind of like a Version 7 system, but we'll see..."
echo exit 0 >v7
fi
case "$eunicefix" in
*unixtovms*)
    $cat <<'EOI'
There is, however, a strange, musty smell in the air that reminds me of
something...hmm...yes...I've got it...there's a VMS nearby, or I'm a Blit.
EOI
echo exit 0 >eunice
d_eunice="$define"
: it so happens the Eunice I know will not run shell scripts in Unix format
;;
*)
echo " "
echo "Congratulations. You aren't running Eunice."
d_eunice="$undef"
;;
esac
case "$p_" in
: ) ;;

```

```

*)
$cat <<'EOI'
I have the feeling something is not exactly right, however...don't tell me...
EOI
if
test -n "$DJGPP"; then
case "X${MACHTYPE:-nonesuchmach}" in
cygwin) echo "hah!... you're running under Cygwin!";;
*) echo "got it... you're running DOS with DJGPP!";;
esac
echo exit 0 >dos
d_dos="$define"
else
$cat <<'EOI'
lemme think...does HAL ring a bell?...no, of course, you're only running OS/2!
EOI
echo exit 0 >os2
d_os2="$define"
fi
;;
esac
if test -f /xenix; then
echo "Actually, this looks more like a XENIX system..."
echo exit 0 >xenix
d_xenix="$define"
else
echo " "
echo "It's not Xenix..."
d_xenix="$undef"
fi
chmod +x xenix
$unicefix xenix
if test -f /venix; then
echo "Actually, this looks more like a VENIX system..."
echo exit 0 >venix
else
echo " "
if ./xenix; then
: null
else
echo "Nor is it Venix..."
fi
fi
chmod +x bsd usg v7 osf1 eunice xenix venix dos os2 gnu linux
$unicefix bsd usg v7 osf1 eunice xenix venix dos os2 gnu linux
$rm -f foo

```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/Guess.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: Obsol_sh.U 1 2006-08-24 12:32:52Z rmanfredi $
```

```
?RCS:
```

```
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
```

```
?RCS:
```

```
?RCS: You may redistribute only under the terms of the Artistic Licence,
```

```
?RCS: as specified in the README file that comes with the distribution.
```

```
?RCS: You may reuse parts of this distribution only within the terms of
```

```
?RCS: that same Artistic Licence; a copy of which may be found at the root
```

```
?RCS: of the source tree for dist 4.0.
```

```
?RCS:
```

```
?RCS: $Log: Obsol_sh.U,v $
```

```
?RCS: Revision 3.0 1993/08/18 12:05:11 ram
```

```
?RCS: Baseline for dist 3.0 netwide release.
```

```
?RCS:
```

```
?X:
```

```
?X: This file is prepended to .MT/Obsol_sh if that file is not empty. That file
```

```
?X: contains the necessary mappings of new symbols to obsolete ones.
```

```
?X:
```

```
?MAKE:Obsol_sh:
```

```
?MAKE: -pick prepend $@ ./Obsol_sh
```

```
?LINT:nocomment
```

```
#
```

```
# The following symbols are obsolete. They are mapped to the the new
```

```
# symbols only to ease the transition process.
```

```
The sources should be
```

```
# updated so as to use the new symbols only, since supporting of those
```

```
# obsolete symbols may end without notice.
```

```
#
```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/Obsol_sh.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id$
```

```
?RCS:
```

```
?RCS: Copyright (c) 1999 Jarkko Hietaniemi
```

```
?RCS:
```

```
?RCS: You may distribute under the terms of either the GNU General Public
```

```
?RCS: License or the Artistic License, as specified in the README file.
```

```
?RCS:
```

```
?X: This unit generates a $hasstruct string that is used internally
```

```
?X: by Configure to check if this system has a field for a
```

```
?X: particular struct (of if this system has a particular struct!)
```

?X:
?X: To use it, say something like:
?X: set d_statblocks stat i_sysstat sys/stat.h
?X: eval \$hasstruct
?X: Or, for more complicated sets of headers, do something like
?X: hdrs="\$define sys/foo.h
?X: \$i_sysbar sys/bar.h
?X: \$i_syszot sys/zot.h
?X: \$i_zappa zappa.h"
?X: set d_statblocks stat \$hdrs
?X: eval \$hasstruct
?X:

?MAKE:Hasstruct: Setvar rm_try test Compile

?MAKE: -pick add \$@ %<

?T:varname struct

?V:hasstruct

: Define hasstruct macro for Configure internal use

```
hasstruct='varname=$1; struct=$2; shift;
```

```
shift;
```

```
while $test $# -ge 2; do
```

```
case "$1" in
```

```
$define) echo "#include <$2>";;
```

```
esac ;
```

```
shift 2;
```

```
done > try.c;
```

```
echo "int main () { struct $struct foo; }" >> try.c;
```

```
set try;
```

```
if eval $compile; then
```

```
val="$define";
```

```
else
```

```
val="$undef";
```

```
fi;
```

```
set $varname;
```

```
eval $setvar;
```

```
$rm_try'
```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/protos/Hasstruct.U
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: \$Log: d_shmat.U,v \$
?RCS: Revision 3.0.1.3 1995/07/25 14:04:23 ram
?RCS: patch56: use findhdr to find <sys/shm.h>, to get the right one (ADO)
?RCS:
?RCS: Revision 3.0.1.2 1994/05/13 15:18:56 ram
?RCS: patch27: added new symbol HAS_SHMAT_PROTOTYPE (ADO)
?RCS:
?RCS: Revision 3.0.1.1 1994/05/06 14:54:18 ram
?RCS: patch23: new Shmat_t symbol to declare return type of shmat()
?RCS:
?RCS: Revision 3.0 1993/08/18 12:07:18 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:d_shmat shmattype
d_shmatprototype: Inlibc cat +cc +ccflags \
rm cppstdin cppflags cppminus Findhdr Setvar contains
?MAKE: -pick add \$@ %<
?S:d_shmat:
?S: This variable conditionally defines the HAS_SHMAT symbol, which
?S: indicates to the C program that the shmat() routine is available.
?S:.
?S:shmattype:
?S: This symbol contains the type of pointer returned by shmat().
?S: It can be 'void *' or 'char *'.
?S:.
?S:d_shmatprototype:
?S: This variable conditionally defines the HAS_SHMAT_PROTOTYPE
?S: symbol, which indicates that sys/shm.h has a prototype for
?S: shmat.
?S:.
?C:HAS_SHMAT:
?C: This symbol, if defined, indicates that the shmat() routine is
?C: available to attach a shared memory segment to the process space.
?C:.
?C:Shmat_t:
?C: This symbol holds the return type of the shmat() system call.
?C: Usually set to 'void *' or 'char *'.
?C:.
?C:HAS_SHMAT_PROTOTYPE:
?C: This symbol, if defined, indicates that the sys/shm.h includes
?C: a prototype for shmat(). Otherwise, it is up to the program
to
?C: guess one. Shmat_t shmat_((int, Shmat_t, int)) is a good guess,
?C: but not always right so it should be emitted by the program only
?C: when HAS_SHMAT_PROTOTYPE is not defined to avoid conflicting defs.

```

?C:.
?H:#$d_shmat HAS_SHMAT /**/
?H:#define Shmat_t $shmattype /**/
?H:#$d_shmatprototype HAS_SHMAT_PROTOTYPE /**/
?H:.
?LINT:set d_shmat d_shmatprototype
?T:xxx
: see if shmat exists
set shmat d_shmat
eval $inlibc
: see what shmat returns
case "$d_shmat" in
"$define")
$cat >shmat.c <<'END'
#include <sys/shm.h>
void *shmat();
END
if $cc $ccflags -c shmat.c >/dev/null 2>&1; then
shmattype='void *'
else
shmattype='char *'
fi
echo "and it returns ($shmattype)." >&4
: see if a prototype for shmat is available
xxx=`./findhdr sys/shm.h`
$cppstdin $cppflags $cppminus < $xxx > shmat.c 2>/dev/null
if $contains 'shmat.*(' shmat.c >/dev/null 2>&1; then
val="$define"
else
val="$undef"
fi
$rm -f shmat.[co]
;;
*)
val="$undef"
;;
esac
set d_shmatprototype
eval $setvar

```

Found

in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/d_shmat.U

No license file was found, but licenses were detected in source scan.

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

```
?RCS:
?MAKE:d_ilogb: Inlibc
?MAKE: -pick add $@ %<
?S:d_ilogb:
?S: This variable conditionally defines the HAS_ILOGB symbol, which
?S: indicates to the C program that the ilogb() routine is available
?S: for extracting the exponent of double x as a signed integer.
?S:.
?C:HAS_ILOGB:
?C: This symbol, if defined, indicates that the ilogb routine is
?C: available to get integer exponent of a floating-point value.
?C:.
?H:#$d_ilogb HAS_ILOGB /**/
?H:.
?LINT:set d_ilogb
: see if ilogb exists
set ilogb d_ilogb
eval $inlibc
```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/perl/d_ilogb.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id$
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: $Log: d_voidsig.U,v $
?RCS: Revision 3.0.1.3 1995/05/12 12:12:46 ram
?RCS: patch54: made cppflags dependency optional
?RCS:
?RCS: Revision 3.0.1.2 1994/08/29 16:20:35 ram
?RCS: patch32: now sets signal_t only once d_voidsig is known (WED)
?RCS:
?RCS: Revision 3.0.1.1 1994/06/20 06:59:54 ram
?RCS: patch30: now properly sets signal_t when re-using previous value
?RCS:
?RCS: Revision 3.0 1993/08/18 12:07:56 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:d_voidsig signal_t: rm contains
```

```

cppstdin cppminus +cppflags test Myread \
Oldconfig Setvar Findhdr
?MAKE: -pick add $@ %<
?S:d_voidsig:
?S: This variable conditionally defines VOIDSIG if this system
?S: declares "void (*signal(...))()" in signal.h. The old way was to
?S: declare it as "int (*signal(...))()".
?S:.
?S:signal_t:
?S: This variable holds the type of the signal handler (void or int).
?S:.
?C:VOIDSIG:
?C: This symbol is defined if this system declares "void (*signal(...))()" in
?C: signal.h. The old way was to declare it as "int (*signal(...))()". It
?C: is up to the package author to declare things correctly based on the
?C: symbol.
?C:.
?C:Signal_t (SIGNAL_T):
?C: This symbol's value is either "void" or "int", corresponding to the
?C: appropriate return type of a signal handler. Thus, you can declare
?C: a signal handler using "Signal_t (*handler())", and define the
?C: handler using "Signal_t handler(sig)".
?C:.
?H:#$d_voidsig VOIDSIG /**/
?H:#define Signal_t $signal_t /* Signal handler's return
type */
?H:.
?T:xxx
?LINT:set d_voidsig
: see if signal is declared as pointer to function returning int or void
echo " "
xxx=`./findhdr signal.h`
$test "$xxx" && $cppstdin $cppminus $cppflags < $xxx >$.tmp 2>/dev/null
if $contains 'int.*\*[ ]*signal' $.tmp >/dev/null 2>&1 ; then
echo "You have int (*signal())() instead of void." >&4
val="$undef"
elif $contains 'void.*\*[ ]*signal' $.tmp >/dev/null 2>&1 ; then
echo "You have void (*signal())() instead of int." >&4
val="$define"
elif $contains 'extern[ ]*[(\[*]signal' $.tmp >/dev/null 2>&1 ; then
echo "You have int (*signal())() instead of void." >&4
val="$undef"
else
case "$d_voidsig" in
")
echo "I can't determine whether signal handler returns void or int..." >&4
dflt=void
rp="What type does your signal handler return?"

```

```

./myread
case "$ans" in
v*) val="$define";;
*) val="$undef";;
esac;;
"$define")
echo "As you already told me, signal handler returns void." >&4;;
*)
echo "As you already told
me, signal handler returns int." >&4;;
esac
fi
set d_voidsig
eval $setvar
case "$d_voidsig" in
"$define") signal_t="void";;
*) signal_t="int";;
esac
$rm -f $$tmp

```

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/d_voidsig.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: i_regex.U 1 2006-08-24 12:32:52Z rmanfredi \$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic Licence,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic Licence; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: Original Author: Sidney C. Smith <scsmith@cbda9.apgea.army.mil>

?RCS:

?RCS: \$Log: i_regex.U,v \$

?RCS: Revision 3.0.1.1 1995/01/30 14:35:45 ram

?RCS: patch49: created

?RCS:

?RCS:

?MAKE:i_regex: Inhdr

?MAKE: -pick add \$@ %<

?S:i_regex:

?S: This variable conditionally defines the I_REGEX symbol, which

?S: indicates to the C program that <regex.h> exists and should

?S: be included.

?S:
?C:I_REGEX:
?C: This symbol, if defined, indicates that <regex.h> exists
and should
?C: be included.
?C:.
?H:#\$i_regex I_REGEX /**/
?H:.
?LINT:set i_regex
: see if regex is available
set regex.h i_regex
eval \$inhdr

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/i_regex.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: Copyright (c) 1998 Andy Dougherty
?RCS:
?RCS: Original author Jarkko Hietaniemi <jhi@iki.fi>
?RCS: Merged into dist by Andy Dougherty July 13, 1998
?RCS:
?MAKE:trnl: Nothing
?MAKE: -pick add \$@ %<
?S:trnl:
?S: This variable contains the value to be passed to the tr(1)
?S: command to transliterate a newline. Typical values are
?S: '\012' and '\n'. This is needed for EBCDIC systems where
?S: newline is not necessarily '\012'.
?S:.
?T: DJGPP
: Find the appropriate value for a newline for tr
?X: We can't
use \$tr since that would cause a circular dependency via Myread
?X: dos djgpp uses '\015\012', but reportedly is happy with '\012' in the
?X: tr command. I don't know why it passes the '\n' test but later
?X: refuses to work correctly with it. --AD 6/14/98

```

if test -n "$DJGPP"; then
    trnl='\012'
fi
if test X"$trnl" = X; then
    case "`echo foo | tr '\n' x 2>/dev/null`" in
    foox) trnl='\n' ;;
    esac
fi
if test X"$trnl" = X; then
    case "`echo foo | tr '\012' x 2>/dev/null`" in
    foox) trnl='\012' ;;
    esac
fi
if test X"$trnl" = X; then
    case "`echo foo | tr '\r\n' xy 2>/dev/null`" in
    fooxy) trnl='\n\r' ;;
    esac
fi
if test X"$trnl" = X; then
    cat <<EOM >&2

```

\$me: Fatal Error: cannot figure out how to translate newlines with 'tr'.

EOM

exit 1

fi

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/trnl.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_times.U,v 3.0.1.2 1995/07/25 14:07:50 ram Exp \$

?RCS:

?RCS: Copyright (c) 1991-1993, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 3.0.

?RCS:

?RCS: \$Log: d_times.U,v \$

?RCS: Revision 3.0.1.2 1995/07/25 14:07:50 ram

?RCS: patch56: typo fix, sytem -> system

?RCS:

?RCS: Revision 3.0.1.1 1994/08/29 16:14:00 ram

?RCS: patch32: now uses new Typedef unit to compute type information

```

?RCS:
?RCS: Revision 3.0 1993/08/18 12:07:46 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?X:
?X: What is the type returned by times() ?
?X:
?X: Force inclusion of <sys/types.h>
?X:INC: i_systypes
?MAKE:d_times clocktype:
    Csym Myread Typedef i_systimes
?MAKE: -pick add $@ %<
?S:d_times:
?S: This variable conditionally defines the HAS_TIMES symbol, which indicates
?S: that the times() routine exists. The times() routine is normally
?S: provided on UNIX systems. You may have to include <sys/times.h>.
?S:.
?S:clocktype:
?S: This variable holds the type returned by times(). It can be long,
?S: or clock_t on BSD sites (in which case <sys/types.h> should be
?S: included).
?S:.
?C:HAS_TIMES (TIMES):
?C: This symbol, if defined, indicates that the times() routine exists.
?C: Note that this became obsolete on some systems (SUNOS), which now
?C: use getrusage(). It may be necessary to include <sys/times.h>.
?C:.
?C:Clock_t (CLOCKTYPE):
?C: This symbol holds the type returned by times(). It can be long,
?C: or clock_t on BSD sites (in which case <sys/types.h> should be
?C: included).
?C:.
?H:#$d_times HAS_TIMES /**/
?H:#define Clock_t $clocktype /* Clock time */
?H:.
?T:val inc
: see if times exists
echo "
"
if set times val -f d_times; eval $csym; $val; then
echo 'times() found.' >&4
d_times="$define"
inc="
case "$i_systimes" in
"$define") inc='sys/times.h';
esac
rp="What is the type returned by times() on this system?"
set clock_t clocktype long stdio.h sys/types.h $inc

```

```

eval $typedef_ask
else
echo 'times() NOT found, hope that will do.' >&4
d_times="$undef"
?X: The following is needed for typedef (won't like an empty variable)
clocktype='int'
fi

```

Found in path(s):

```

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/typedefs/d_times.U

```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1999, Jarkko Hietaniemi

?RCS:

?RCS: This file is included with or a derivative work of a file included

?RCS: with the metaconfig program of Raphael Manfredi's "dist" distribution.

?RCS: In accordance with clause 7 of dist's modified Artistic License:

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?MAKE:multiarch: osname

?MAKE: -pick add \$@ %<

?S:multiarch:

?S: This variable conditionally defines the MULTIARCH symbol

?S: which signifies the presence of multiplatform files.

?S: This is normally set by hints files.

?S:.

?C:MULTIARCH:

?C: This symbol, if defined, signifies that the build

?C: process will produce some binary files that are going to be

?C: used in a cross-platform environment. This is the case for

?C: example with the NeXT "fat" binaries that contain executables

?C: for

several CPUs.

?C:.

?H:#\$multiarch MULTIARCH /**/

?H:.

: Check if is a multiplatform env

case "\$osname" in

darwin) multiarch="\$define" ;;

esac

case "\$multiarch" in

"|[nN]*") multiarch="\$undef" ;;

esac

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/a_dvisory/multiarch.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 2000 Jarkko Hietaniemi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 3.0.

?RCS:

?MAKE:d__fwalk: Inlibc

?MAKE: -pick add \$@ %<

?S:d__fwalk:

?S: This variable conditionally defines HAS__FWALK if _fwalk() is

?S: available to apply a function to all the file handles.

?S:.

?C:HAS__FWALK:

?C: This symbol, if defined, indicates that the _fwalk system call is

?C: available to apply a function to all the file handles.

?C:.

?H:#\$d__fwalk HAS__FWALK /**/

?H:.

?LINT:set d__fwalk

: see if _fwalk exists

set fwalk d__fwalk

eval \$inlibc

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d__fwalk.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

```

?RCS: $Log: d_getpwent.U,v $
?RCS: Revision 3.0 1993/08/18 12:06:17 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:d_getpwent: Csym Setvar
?MAKE: -pick add $@ %<
?S:d_getpwent:
?S: This variable conditionally defines the HAS_GETPWENT symbol, which
?S: indicates to the C program that it should use the getpwent()
?S: routine instead of the getpw() routine.
?S:.
?C:HAS_GETPWENT (GETPWENT):
?C: This symbol, if defined, indicates that the getpwent() routine
?C: should be used instead of the getpw()
routine.
?C:.
?H:#$d_getpwent HAS_GETPWENT /**/
?H:.
?LINT:set d_getpwent
: see if there is a getpwent
echo " "
if set getpwent val -f d_getpwent; eval $csym; $val; then
echo "getpwent() found." >&4
val="$define"
else
echo "No getpwent() found -- will use getpw() instead." >&4
val="$undef"
fi
set d_getpwent
eval $setvar

```

Found in path(s):

```

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/d_getpwent.U

```

No license file was found, but licenses were detected in source scan.

```

?RCS: $Id: i_socks.U,v $
?RCS:
?RCS: Copyright (c) 1999 Jarkko Hietaniemi
?RCS:
?RCS: You may distribute under the terms of either the GNU General Public
?RCS: License or the Artistic License, as specified in the README file.
?RCS:
?MAKE:i_socks: Inhdr Hasfield
?MAKE: -pick add $@ %<
?S:i_socks:
?S: This variable conditionally defines the I_SOCKS symbol, and indicates
?S: whether a C program should include <socks.h>.

```

?S:
?C:I_SOCKS:
?C: This symbol, if defined, indicates that <socks.h> exists and
?C: should be included.
?C:.
?H:#\$i_socks I_SOCKS /**/
?H:.
?LINT:set i_socks
: see if this is a socks.h system
set socks.h i_socks
eval \$inhdr

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/i_socks.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: \$Log: Myinit.U,v \$
?RCS: Revision 3.0.1.1 1994/10/31 09:47:29 ram
?RCS: patch44: leading comment states this unit comes before option processing
?RCS:
?RCS: Revision 3.0 1993/08/18 12:05:07 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?X:
?X: If you want to initialize any default values, copy this unit to your
?X: personal U directory and add the assignments to the end. This file
?X: is included after variables are initialized but before any old
?X: config.sh file is read in and before
?X: any Configure switch processing.
?X:
?MAKE:Myinit: Init
?MAKE:-pick add \$@ %<
?LINT: nocomment

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/Myinit.U

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: d_semget.U 1 2006-08-24 12:32:52Z rmanfredi $
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: $Log: d_semget.U,v $
?RCS: Revision 3.0 1993/08/18 12:07:05 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:d_semget: Inlibc
?MAKE: -pick add $@ %<
?S:d_semget:
?S: This variable conditionally defines the HAS_SEMGET symbol, which
?S: indicates to the C program that the semget() routine is available.
?S:.
?C:HAS_SEMGET:
?C: This symbol, if defined, indicates that the semget() routine is
?C: available to get a set of semaphores.
?C:.
?H:#$d_semget
HAS_SEMGET /**/
?H:.
?LINT:set d_semget
: see if semget exists
set semget d_semget
eval $inlibc
```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/d_semget.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id$
?RCS:
?RCS: Copyright (c) 2000 Jarkko Hietaniemi
?RCS:
?RCS: You may distribute under the terms of either the GNU General Public
?RCS: License or the Artistic License, as specified in the README file.
?RCS:
?MAKE:d_fp_class!: Inlibc
?MAKE: -pick add $@ %<
```

?S:d_fp_classl:

?S: This variable conditionally defines the HAS_FP_CLASSL symbol, which

?S: indicates to the C program that the fp_classl() routine is available.

?S:.

?C:HAS_FP_CLASSL:

?C: This symbol, if defined, indicates that the fp_classl routine is

?C: available to classify long doubles. Available for example in

?C: Digital UNIX. See for possible values HAS_FP_CLASS.

?C:.

?H:#\$d_fp_classl HAS_FP_CLASSL /**/

?H:.

?LINT:set d_fp_classl

: see if fp_classl exists

set fp_classl d_fp_classl

eval \$inlibc

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_fp_classl.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 2000 Jarkko Hietaniemi

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?MAKE:d_fpclass: Inlibc

?MAKE: -pick add \$@ %<

?S:d_fpclass:

?S: This variable conditionally defines the HAS_FPCLASS symbol, which

?S: indicates to the C program that the fpclass() routine is available.

?S:.

?C:HAS_FPCLASS:

?C: This symbol, if defined, indicates that the fpclass routine is

?C: available to classify doubles. Available for example in Solaris/SVR4.

?C: The returned values are defined in <ieeefp.h> and are:

?C:

?C: FP_SNAN signaling NaN

?C: FP_QNAN quiet NaN

?C: FP_NINF negative infinity

?C: FP_PINF positive infinity

?C: FP_NDENORM negative denormalized non-zero

?C: FP_PDENORM positive denormalized non-zero

?C: FP_NZERO negative zero

?C: FP_PZERO positive zero

?C: FP_NNORM negative normalized

```
non-zero
?C: FP_PNORM positive normalized non-zero
?C:.
?H:#$d_fpclass HAS_FPCLASS /**/
?H:.
?LINT:set d_fpclass
: see if fpclass exists
set fpclass d_fpclass
eval $inlibc
```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/perl/d_fpclass.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id$
?RCS:
?RCS: Copyright (c) 2000, Jarkko Hietaniemi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 3.0.
?RCS:
?MAKE:d_lseekproto: Hasproto i_systypes i_unistd
?MAKE: -pick add $@ %<
?S:d_lseekproto:
?S: This variable conditionally defines the HAS_LSEEK_PROTO symbol,
?S: which indicates to the C program that the system provides
?S: a prototype for the lseek() function. Otherwise, it is
?S: up to the program to supply one.
?S:.
?C:HAS_LSEEK_PROTO:
?C: This symbol, if defined, indicates that the system provides
?C: a prototype for the lseek() function. Otherwise, it is up
?C: to the program to supply one. A good guess is
?C: extern
off_t lseek(int, off_t, int);
?C:.
?H:#$d_lseekproto HAS_LSEEK_PROTO /**/
?H:.
?LINT:set d_lseekproto
: see if prototype for lseek is available
echo " "
set d_lseekproto lseek $i_systypes sys/types.h $i_unistd unistd.h
eval $hasproto
```

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/protos/d_lseekproto.U

No license file was found, but licenses were detected in source scan.

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?MAKE:d_strerror_l: Inlibc

?MAKE: -pick add \$@ %<

?S:d_strerror_l:

?S: This variable conditionally defines the HAS_STRERROR_L symbol, which

?S: indicates to the C program that the strerror_l() routine is available

?S: to return the error message for a given errno value in a particular

?S: locale (identified by a locale_t object).

?S:.

?C:HAS_STRERROR_L:

?C: This symbol, if defined, indicates that the strerror_l routine is

?C: available to return the error message for a given errno value in

?C: a particular locale (identified by a locale_t object).

?C:.

?H:#\$d_strerror_l HAS_STRERROR_L /**/

?H:.

?LINT:set d_strerror_l

: see if strerror_l exists

set strerror_l d_strerror_l

eval \$inlibc

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_strerror_l.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1999 Jarkko Hietaniemi

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?MAKE:d_fs_data_s: Hasstruct i_sysparam i_sysmount i_systypes Setvar

?MAKE: -pick add \$@ %<

?S:d_fs_data_s:

?S: This variable conditionally defines the HAS_STRUCT_FS_DATA symbol,

?S: which indicates that the struct fs_data is supported.

?S:.

?C:HAS_STRUCT_FS_DATA:

?C: This symbol, if defined, indicates that the struct fs_data

```

?C: to do statfs() is supported.
?C:.
?H:#$d_fs_data_s HAS_STRUCT_FS_DATA /**/
?H:.
?LINT:set d_fs_data_s
: Check for fs_data_s
echo " "
echo "Checking to see if your system supports struct fs_data..." >&4
set d_fs_data_s fs_data $i_systypes sys/types.h $i_sysparam sys/param.h $i_sysmount sys/mount.h
eval $hasstruct
case "$d_fs_data_s" in
"$define")    echo "Yes, it does." ;;
*)
    echo "No, it doesn't." ;;
esac

```

Found in path(s):

```

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/perl/d_fs_data_s.U

```

No license file was found, but licenses were detected in source scan.

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?MAKE:d_lgamma: Inlibc

?MAKE: -pick add \$@ %<

?S:d_lgamma:

?S: This variable conditionally defines the HAS_LGAMMA symbol, which

?S: indicates to the C program that the lgamma() routine is available

?S: for the log gamma function. See also d_tgamma and d_lgamma_r.

?S:.

?C:HAS_LGAMMA:

?C: This symbol, if defined, indicates that the lgamma routine is

?C: available to do the log gamma function. See also HAS_TGAMMA and

?C: HAS_LGAMMA_R.

?C:.

```

?H:#$d_lgamma HAS_LGAMMA /**/

```

?H:.

```

?LINT:set d_lgamma

```

```

: see if lgamma exists

```

```

set lgamma d_lgamma

```

```

eval $inlibc

```

Found in path(s):

```

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/perl/d_lgamma.U

```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: Copyright (c) 1998 Andy Dougherty

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public
?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?RCS:

?X:

?X: This unit is just a quick shorthand for the compile command
?X: to be used in all the other metaconfig units.

?X:

?MAKE:Compile: +cc +optimize +ccflags +ldflags +libs

?MAKE: -pick add \$@ %<

?LINT:define compile compile_ok

?V:compile compile_ok mc_file

?S:compile:

?S: This shell variable is used internally
by Configure to provide

?S: a convenient shorthand for the typical compile command, namely

?S: \$cc \$optimize \$ccflags \$ldflags -o \$1 \$1.c \$libs > /dev/null 2>&1

?S: Note that the output filename does not include the _exe
?S: extension. Instead we assume that the linker will be
?S: "helpful" and automatically appending the correct suffix.

?S: OS/2 users will apparently need to supply the -Zexe flag to
?S: get this behavior.

?S:

?S: To use this variable, say something like:

?S: echo 'int main() { exit(0); }' > try.c

?S: set try

?S: if eval \$compile; then

?S: echo "success" # and do whatever . . .

?S: else

?S: echo "failure" # and do whatever . . .

?S: fi

?S: To add extra flags cc flags (e.g. -DWHATEVER) just put them
?S: in \$*, e.g.

?S: set try -DTRY_THIS_FLAG

?S:.

?S:compile_ok:

?S: This shell variable is used internally by Configure to provide
 ?S: a convenient shorthand for the typical compile command that you
 ?S: expect to work ok. It is the same as \$compile,
 except we
 ?S: deliberately let the user see any error messages.
 ?S:.
 : define a shorthand compile call
 compile='
 mc_file=\$1;
 shift;
 \$cc -o \${mc_file} \$optimize \$ccflags \$ldflags \$* \${mc_file}.c \$libs > /dev/null 2>&1;
 : define a shorthand compile call for compilations that should be ok.
 compile_ok='
 mc_file=\$1;
 shift;
 \$cc -o \${mc_file} \$optimize \$ccflags \$ldflags \$* \${mc_file}.c \$libs;'

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/Compile.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: Tr.U,v 3.0.1.2 1994/10/29 18:00:54 ram Exp \$

?RCS:

?RCS: Copyright (c) 1991-1993, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 3.0.

?RCS:

?RCS: \$Log: Tr.U,v \$

?RCS: Revision 3.0.1.2 1994/10/29 18:00:54 ram

?RCS: patch43: forgot to quote \$@ to protect against "evil" characters

?RCS:

?RCS: Revision 3.0.1.1 1994/10/29 15:58:35 ram

?RCS: patch36: created

?RCS:

?X:

?X: This unit produces a bit of shell code that must be dotted in in order

?X: to do a character translation. It catches translations to uppercase or

?X: to lowercase, and then invokes the real tr to perform the job.

?X:

?X: This unit is necessary

on HP machines (HP strikes again!) with non-ascii

?X: ROMAN8-charset, where normal letters are not arranged in a row, so a-z

?X: covers not the whole alphabet but lots of special chars. This was reported

?X: by Andreas Sahlbach <a.sahlbach@tu-bs.de>.

?X:

?X: Units performing a tr '[A-Z]' '[a-z]' or the other way round should include

?X: us in their dependency and use ./tr instead.

?X:

?MAKE:Tr: startsh tr eunicefix

?MAKE: -pick add \$@ %<

?F:./tr

?T:up low

: see whether [:lower:] and [:upper:] are supported character classes

echo " "

case "`echo AbyZ | \$tr '[:lower:]' '[:upper:]' 2>/dev/null`"- "`echo AbyZ | \$tr '[:upper:]' '[:lower:]' 2>/dev/null`" in
ABYZ-abyz)

echo "Good, your tr supports [:lower:] and [:upper:] to convert case." >&4

up='[:upper:]'

low='[:lower:]'

::

*) # There is a discontinuity in EBCDIC between 'R' and 'S'

(0xd9 and 0xe2), therefore that is a nice testing point.

if test "X\$up" = X -o "X\$low" = X; then

case "`echo RS | \$tr '[R-S]' '[r-s]' 2>/dev/null`"

in

rs) up='[A-Z]'

low='[a-z]'

::

esac

fi

if test "X\$up" = X -o "X\$low" = X; then

case "`echo RS | \$tr R-S r-s 2>/dev/null`" in

rs) up='A-Z'

low='a-z'

::

esac

fi

if test "X\$up" = X -o "X\$low" = X; then

case "`echo RS | od -x 2>/dev/null`" in

D9E2|*d9e2*)

echo "Hey, this might be EBCDIC." >&4

if test "X\$up" = X -o "X\$low" = X; then

case "`echo RS | \$tr '[A-IJ-RS-Z]' '[a-ij-rs-z]' 2>/dev/null`" in

rs) up='[A-IJ-RS-Z]'

low='[a-ij-rs-z]'

::

esac

fi

if test "X\$up" = X -o "X\$low" = X; then

case "`echo RS | \$tr A-IJ-RS-Z a-ij-rs-z 2>/dev/null`" in

rs) up='A-IJ-RS-Z'

```

low='a-ij-rs-z'
;;
esac
fi
;;
esac
fi
esac
case "`echo RS | $tr \"\$up\" \"\$low\" 2>/dev/null" in
rs)
echo "Using $up and $low to convert case." >&4
;;
*)
echo "I don't know how to translate letters from upper to lower case." >&4
echo "Your tr is not acting any way I know of." >&4
exit 1
;;
esac
:
set up the translation script tr, must be called with ./tr of course
cat >tr <<EOSC
$startsh
case "\$1\$2" in
'[A-Z][a-z]') exec $tr '$up' '$low';;
'[a-z][A-Z]') exec $tr '$low' '$up';;
esac
exec $tr "\$@"
EOSC
chmod +x tr
$unicefix tr

```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/modified/Tr.U
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_shmget.U 1 2006-08-24 12:32:52Z rmanfredi \$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic Licence,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic Licence; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: d_shmget.U,v \$

?RCS: Revision 3.0 1993/08/18 12:07:20 ram

?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:d_shmget: Inlibc
?MAKE: -pick add \$@ %<
?S:d_shmget:
?S: This variable conditionally defines the HAS_SHMGET symbol, which
?S: indicates to the C program that the shmget() routine is available.
?S:.
?C:HAS_SHMGET:
?C: This symbol, if defined, indicates that the shmget() routine is
?C: available to request a shared memory segment from
the kernel.
?C:.
?H:#\$d_shmget HAS_SHMGET /**/
?H:.
?LINT:set d_shmget
: see if shmget exists
set shmget d_shmget
eval \$inlibc

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/d_shmget.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$
?RCS:
?RCS: Copyright (c) 1996, Andy Dougherty
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: You may distribute under the terms of either the GNU General Public
?RCS: License or the Artistic License, as specified in the README file.
?RCS:
?RCS: \$Log: d_sigsetjmp.U,v \$
?RCS: Revision 3.0.1.1 1997/02/28 15:44:33 ram
?RCS: patch61: created
?RCS:
?MAKE:d_sigsetjmp: Setvar cat +cc +ccflags +ldflags libs rm
?MAKE: -pick add \$@ %<
?S:d_sigsetjmp:
?S: This variable conditionally defines the HAS_SIGSETJMP symbol,
?S: which indicates that the sigsetjmp() routine

is available to

?S: call `setjmp()` and optionally save the process's signal mask.

?S:.

?C:HAS_SIGSETJMP:

?C: This variable indicates to the C program that the `sigsetjmp()`

?C: routine is available to save the calling process's registers

?C: and stack environment for later use by `siglongjmp()`, and

?C: to optionally save the process's signal mask. See

?C: `Sigjmp_buf`, `Sigsetjmp`, and `Siglongjmp`.

?C:.

?C:Sigjmp_buf:

?C: This is the buffer type to be used with `Sigsetjmp` and `Siglongjmp`.

?C:.

?C:Sigsetjmp:

?C: This macro is used in the same way as `sigsetjmp()`, but will invoke

?C: traditional `setjmp()` if `sigsetjmp` isn't available.

?C: See `HAS_SIGSETJMP`.

?C:.

?C:Siglongjmp:

?C: This macro is used in the same way as `siglongjmp()`, but will invoke

?C: traditional `longjmp()` if `siglongjmp` isn't available.

?C: See `HAS_SIGSETJMP`.

?C:.

?H:%<:#\$d_sigsetjmp HAS_SIGSETJMP /**/

?H:%<:#ifdef HAS_SIGSETJMP

?H:%<:#define Sigjmp_buf sigjmp_buf

?H:%<:#define Sigsetjmp(buf,save_mask) sigsetjmp((buf),(save_mask))

?H:%<:#define

Siglongjmp(buf,retval) siglongjmp((buf),(retval))

?H:%<:#else

?H:%<:#define Sigjmp_buf jmp_buf

?H:%<:#define Sigsetjmp(buf,save_mask) setjmp((buf))

?H:%<:#define Siglongjmp(buf,retval) longjmp((buf),(retval))

?H:%<:#endif

?H:.

?W:%<:Sigjmp_buf Sigsetjmp Siglongjmp

?F:!set

?LINT:set d_sigsetjmp

: see if `sigsetjmp` exists

?X: We can't check for these symbols with `Inlibc` because `sigsetjmp`

?X: is (sometimes? always?) a macro under `GCC`

echo " "

case "\$d_sigsetjmp" in

")

\$cat >set.c <<'EOP'

#include <setjmp.h>

sigjmp_buf env;

int set = 1;

```

int main()
{
if (sigsetjmp(env,1))
    exit(set);
set = 0;
siglongjmp(env, 1);
exit(1);
}
EOP
if $cc $ccflags $ldflags -o set set.c $libs > /dev/null 2>&1 ; then
if ./set >/dev/null 2>&1; then
    echo "POSIX sigsetjmp found." >&4
    val="$define"
else
    $cat >&4 <<EOM

```

Uh-Oh! You have POSIX sigsetjmp and siglongjmp, but they do not work properly!!

I'll ignore them.

```

EOM
    val="$undef"
fi
else
    echo "sigsetjmp not found."
>&4
    val="$undef"
fi
;;
*) val="$d_sigsetjmp"
case "$d_sigsetjmp" in
$define) echo "POSIX sigsetjmp found." >&4;;
$undef) echo "sigsetjmp not found." >&4;;
esac
;;
esac
set d_sigsetjmp
eval $setvar
$rm -f set.c set

```

Found in path(s):

```

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/d_sigsetjmp.U

```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: localarch.U,v 1.1 1999/07/08 18:32:57 doughera Exp doughera \$

?RCS:

?RCS: Copyright (c) 1999, Jarkko Hietaniemi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 3.0.
?RCS:
?RCS:
?MAKE:localarch localarchexp installlocalarch installlocalarchexp: \
afs cat Getfile \
Oldconfig Prefixit test archname uselocallib locallib sitearch
?MAKE: -pick add \$@ %<
?Y:TOP
?S:localarch:
?S: This variable contains the eventual value of the LOCALARCH symbol,
?S: which is the name of the private library for this package. It may
?S: have a ~ on the front. It is up to the makefile to eventually create
?S: this directory while performing installation
(with ~ substitution).
?S: This differs from \$sitearch in that \$sitearch is often
?S: a shared network directory while \$localarch is
?S: at a local disk, because of policy/administrative issues
?S: like for example caching (performance), licensing, or security.
?S:.
?S:localarchexp:
?S: This variable is the ~name expanded version of localarch, so that you
?S: may use it directly in Makefiles or shell scripts.
?S:.
?S:installlocalarch:
?S: This variable is really the same as localarchexp but may differ on
?S: those systems using AFS. For extra portability, only this variable
?S: should be used in makefiles.
?S:.
?S:installlocalarchexp:
?S: This variable is the ~name expanded version of installlocalarch,
?S: so that you may use it directly in Makefiles or shell scripts.
?S:.
?C:LOCALARCH:
?C: This symbol contains the name of the private library for this package.
?C: The library is private in the sense that it needn't be in anyone's
?C: execution path, but it should be accessible by the
world. The program
?C: should be prepared to do ~ expansion.
?C: The standard distribution will put nothing in this directory.
?C: Local administration may place extensions and modules in
?C: this directory.
?C: This differs from SITEARCH in that SITEARCH is often
?C: a shared network directory while LOCALARCH is
?C: at a local disk, because of policy/administrative issues
?C: like for example caching (performance), licensing, or security.
?C:.

```

?C:LOCALARCH_EXP:
?C: This symbol contains the ~name expanded version of LOCALARCH,
?C: to be used in programs that are not prepared to deal with ~
?C: expansion at run-time.
?C:.
?H:#define LOCALARCH "$localarch" /**/
?H:#define LOCALARCH_EXP "$localarchexp" /**/
?H:.
?T:tdflt
?LINT:extern sitearch
: Set the localarch variables
case "$uselocallib" in
"$define")
case "$sitearch" in
") tdflt="$tdflt/$archname"
set sitearch sitearch none
eval $prefixit
dflt="$tdflt" ;;
*) dflt="$sitearch" ;;
esac
$cat <<EOM

```

The installation process
will also create a directory for
architecture-dependent extensions and modules to be installed
alongside \$locallib.

```

EOM
fn=nd~+
rp='Pathname for local architecture-dependent library files?'
./getfile
if $test "X$localarchexp" != "X$ansexp"; then
installlocalarch="
fi
localarch="$ans"
localarchexp="$ansexp"
if $afs; then
$cat <<EOM

```

Since you are running AFS, I need to distinguish the directory in
which locally installed architecture-dependent library files reside
from the directory in which they are installed (and from which they
are presumably copied to the former directory by occult means).

```

EOM
case "$installlocalarch" in
") dflt=`echo $localarchexp | sed 's#^/afs/#/afs/.#`";;
*) dflt="$installlocalarch";;

```

```

esac
fn=de~
rp='Where will local architecture-dependent files be installed?'
./getfile
installlocalarch="$ans"
else
installlocalarch="$localarchexp"
fi
;;
*)
localarch=""
localarchexp=""
installlocalarch=""
installlocalarchexp=""
;;
esac

```

Found

in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/installdirs/localarch.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1999 Jarkko Hietaniemi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 3.0.

?RCS:

?MAKE:d_endspent: Inlibc

?MAKE: -pick add \$@ %<

?S:d_endspent:

?S: This variable conditionally defines HAS_ENDSPENT if endspent() is

?S: available to finalize the scan of SysV shadow password entries.

?S:.

?C:HAS_ENDSPENT:

?C: This symbol, if defined, indicates that the endspent system call is

?C: available to finalize the scan of SysV shadow password entries.

?C:.

?H:#\$d_endspent HAS_ENDSPENT /**/

?H:.

?LINT:set d_endspent

: see if endspent exists

set endspent d_endspent

eval \$inlibc

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_endspent.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1999 Jarkko Hietaniemi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 3.0.

?RCS:

?MAKE:siteman1dir siteman1direxp installsiteman1dir: Getfile \

Setprefixvar prefix siteprefix man1dir sed

?MAKE: -pick add \$@ %<

?Y:TOP

?D:siteman1dir="

?S:siteman1dir:

?S: This variable contains the name of the directory in which site-specific

?S: manual source pages are to be put. It is the responsibility of the

?S: Makefile.SH to get the value of this into the proper command.

?S: You must be prepared to do the ~name expansion yourself.

?S: The standard distribution will put nothing in this directory.

?S: After perl

has been installed, users may install their own local

?S: man1 pages in this directory with

?S: MakeMaker Makefile.PL

?S: or equivalent. See INSTALL for details.

?S:.

?D:siteman1direxp="

?S:siteman1direxp:

?S: This variable is the same as the siteman1dir variable, but is filename

?S: expanded at configuration time, for convenient use in makefiles.

?S:.

?D:installsiteman1dir="

?S:installsiteman1dir:

?S: This variable is really the same as siteman1direxp, unless you are using

?S: AFS in which case it points to the read/write location whereas

?S: man1direxp only points to the read-only access location. For extra

?S: portability, you should only use this variable within your makefiles.

?S:.

?LINT:change prefixvar

?LINT:set installsiteman1dir

```

?LINT:set siteman1dir
?LINT:set siteman1direxp
: determine where add-on manual pages go
case "$siteman1dir" in
") dflt=`echo $man1dir | $sed "s^#$prefix#$$siteprefix#"` ;;
*) dflt=$siteman1dir ;;
esac
case "$dflt" in
"|'') dflt=none ;;
esac
fn=dn+~
rp='Pathname
where the site-specific manual pages should be installed?'
./getfile
prefixvar=siteman1dir
./setprefixvar

```

Found in path(s):

```

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/installdirs/siteman1dir.U

```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1998, Jarkko Hietaniemi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 3.0.

?RCS:

?MAKE:i_pthread: Inhdr

?MAKE: -pick add \$@ %<

?S:i_pthread:

?S: This variable conditionally defines the I_PTHREAD symbol,

?S: and indicates whether a C program should include <pthread.h>.

?S:.

?C:I_PTHREAD:

?C: This symbol, if defined, indicates to the C program that it should

?C: include <pthread.h>.

?C:.

?H:#\$i_pthread I_PTHREAD /**/

?H:.

?LINT:set i_pthread

: see if POSIX threads are available

set pthread.h i_pthread

eval \$inhdr

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/threads/i_pthread.U

No license file was found, but licenses were detected in source scan.

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?MAKE:d_llroundl: Inlibc

?MAKE: -pick add \$@ %<

?S:d_llroundl:

?S: This variable conditionally defines the HAS_LLROUNDL symbol, which

?S: indicates to the C program that the llroundl() routine is available

?S: to return the long long value nearest to x away from zero.

?S:.

?C:HAS_LLROUNDL:

?C: This symbol, if defined, indicates that the llroundl routine is

?C: available to return the nearest long long value away from zero of

?C: the long double argument value.

?C:.

?H:#\$d_llroundl HAS_LLROUNDL /**/

?H:.

?LINT:set d_llroundl

: see if llroundl exists

set llroundl d_llroundl

eval \$inlibc

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_llroundl.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1999 Jarkko Hietaniemi

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?MAKE:d_getmntinfo_r: Inlibc

?MAKE: -pick add \$@ %<

?S:d_getmntinfo_r:

?S: This variable conditionally defines the HAS_GETMNTINFO_R symbol,

?S: which indicates to the C program that the getmntinfo_r()

?S: routine is available.

?S:.

?C:HAS_GETMNTINFO_R:

?C: This symbol, if defined, indicates that the getmntinfo_r routine

?C: is available to getmntinfo re-entrantly.

?C:.

?H:#\$d_getmntinfo_r HAS_GETMNTINFO_R /**/

?H:.

?LINT:set d_getmntinfo_r

: see if getmntinfo_r exists

set getmntinfo_r d_getmntinfo_r

eval \$inlibc

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/threads/d_getmntinfo_r.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_sysconf.U 1 2006-08-24 12:32:52Z rmanfredi \$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic Licence,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic Licence; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: Original Author: Andy Dougherty <doughera@lafcol.lafayette.edu>

?RCS:

?RCS: \$Log: d_sysconf.U,v \$

?RCS: Revision 3.0.1.1 1994/10/29 16:15:57 ram

?RCS: patch36: created by ADO

?RCS:

?MAKE:d_sysconf: Inlibc

?MAKE: -pick add \$@ %<

?S:d_sysconf:

?S: This variable conditionally defines the HAS_SYSCONF symbol, which

?S: indicates to the C program that the sysconf() routine is available

?S: to determine system related limits and options.

?S:.

?C:HAS_SYSCONF:

?C: This

symbol, if defined, indicates that sysconf() is available

?C: to determine system related limits and options.

?C:.

?H:#\$d_sysconf HAS_SYSCONF /**/

?H:.

?LINT:set d_sysconf

: see if sysconf exists

set sysconf d_sysconf

eval \$inlibc

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/d_sysconf.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1999, Jarkko Hietaniemi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 3.0.

?RCS:

?MAKE:d_sched_getparam: Inlibc

?MAKE: -pick add \$@ %<

?S:d_sched_getparam:

?S: This variable conditionally defines HAS_SCHED_GETPARAM if

?S: sched_getparam() is available to get the scheduling parameters.

?S:.

?C:HAS_SCHED_GETPARAM:

?C: This symbol, if defined, indicates that the sched_getparam

?C: system call is available to get the scheduling parameters.

?C:.

?H:#\$d_sched_getparam HAS_SCHED_GETPARAM /**/

?H:.

?LINT:set d_sched_getparam

: see if sched_getparam exists

set sched_getparam d_sched_getparam

eval \$inlibc

Found

in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_sched_getparam.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1999, Jarkko Hietaniemi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 3.0.
?RCS:
?MAKE:d_sigtimedwait: Inlibc
?MAKE: -pick add \$@ %<
?S:d_sigtimedwait:
?S: This variable conditionally defines HAS_SIGTIMEDWAIT
?S: if sigtimedwait() is available to wait a signal and additional
?S: information, with a timeout.
?S:.
?C:HAS_SIGTIMEDWAIT:
?C: This symbol, if defined, indicates that the sigtimedwait
?C: system call is available to wait a signal and additional information,
?C: with a timeout.
?C:.
?H:#\$d_sigtimedwait HAS_SIGTIMEDWAIT /**/
?H:.
?LINT:set d_sigtimedwait
: see if sigtimedwait exists
set sigtimedwait
d_sigtimedwait
eval \$inlibc

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_sigtimedwait.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$
?RCS:
?RCS: Copyright (c) 1999 Jarkko Hietaniemi
?RCS:
?RCS: You may distribute under the terms of either the GNU General Public
?RCS: License or the Artistic License, as specified in the README file.
?RCS:
?MAKE:uselargefiles \
ccflags_uselargefiles \
ldflags_uselargefiles \
libswanted_uselargefiles: \
Myread Oldconfig Setvar test lseeksize fpossize \
fpostype Compile echo n c cat lseektype rm_try run \
use64bitint use64bitall i_stdlib
?MAKE: -pick add \$@ %<
?Y:TOP
?S:uselargefiles:
?S: This variable conditionally defines the USE_LARGE_FILES symbol,
?S: and indicates that large file interfaces should be used when
?S: available.
?S:.

```

?S:ccflags_uselargefiles:
?S: This variable contains the compiler flags needed by large file builds
?S: and added to ccflags by hints files.
?S:.
?S:ldflags_uselargefiles:
?S: This variable contains the loader flags needed by large file builds
?S: and added to ldflags by
?S: hints files.
?S:.
?S:libswanted_uselargefiles:
?S: This variable contains the libraries needed by large file builds
?S: and added to ldflags by hints files. It is a space separated list
?S: of the library names without the "lib" prefix or any suffix, just
?S: like libswanted..
?S:.
?C:USE_LARGE_FILES:
?C: This symbol, if defined, indicates that large file support
?C: should be used when available.
?C:.
?H:?%<:#ifndef USE_LARGE_FILES
?H:?%<:#$uselargefiles USE_LARGE_FILES /**/
?H:?%<:#endif
?H:.
?INIT:ccflags_uselargefiles="
?INIT:ldflags_uselargefiles="
?INIT:libswanted_uselargefiles="
?T:yyy zzz
?F:!uselargefiles.cbu !try
?LINT:change lseeksize
?LINT:change fpossize
?LINT:extern usefs
?LINT:use use64bitint
?LINT:use use64bitall
: Check for large file support
# Backward compatibility (usefs is deprecated).
case "$usefs" in
"$define"|true|[yY]*)
cat <<EOM >&4

*** Configure -Dusefs is deprecated, using -Duselargefiles instead.
EOM
uselargefiles="$define"
;;
esac

case "$lseeksize:$fpossize"
in
8:8) cat <<EOM

```

You can have files larger than 2 gigabytes.

EOM

```
val="$define" ;;
*) case "$uselargefiles" in
"$undef"|false|[nN]*) dflt='n' ;;
*) dflt='y' ;;
esac
cat <<EOM
```

Perl can be built to understand large files (files larger than 2 gigabytes) on some systems. To do so, Configure can be run with `-Duselargefiles`.

If this doesn't make any sense to you, just accept the default '\$dflt'.

EOM

```
rp="Try to understand large files, if available?"
./myread
case "$ans" in
y|Y) val="$define" ;;
*) val="$undef" ;;
esac
;;
esac
set uselargefiles
eval $setvar
: Look for a hint-file generated 'call-back-unit'. If the
: user has specified that a large files perl is to be built,
: we may need to set or change some other defaults.
if $test -f uselargefiles.cbu; then
echo "Your platform has some specific hints regarding large file builds, using them..."
./uselargefiles.cbu
fi
case "$uselargefiles" in
"$define")
if $test -f uselargefiles.cbu;
then
echo " "
echo "Rechecking to see how big your file offsets are..." >&4
$cat >try.c <<EOCP
#include <sys/types.h>
#include <stdio.h>
int main()
{
printf("%d\n", (int)sizeof($lseektype));
return(0);
}
EOCP
set try
```

```

if eval $compile_ok; then
  lseeksize=`$run ./try`
  $echo "Your file offsets are now $lseeksize bytes long."
else
  dflt="$lseeksize"
  echo " "
  echo "(I can't seem to compile the test program. Guessing...)"
  rp="What is the size of your file offsets (in bytes)?"
  ./myread
  lseeksize="$ans"
fi
case "$fpostype" in
*_t) zzz="$fpostype" ;;
*) zzz="fpos_t" ;;
esac
$echo $n "Rechecking the size of $zzz...$c" >&4
$cat > try.c <<EOCP
#include <sys/types.h>
#include <stdio.h>
#ifdef I_STDLIB
#include <stdlib.h>
#endif
int main() {
  printf("%d\n", (int)sizeof($fpostype));
  return(0);
}
EOCP
set try
if eval $compile_ok; then
  yyy=`$run ./try`
  dflt="$lseeksize"
  case "$yyy" in
  ") echo
  " "
  echo "(I can't execute the test program--guessing $fpossize.)" >&4
  ;;
  *) fpossize=$yyy
  echo "$fpossize bytes." >&4
  ;;
  esac
else
  dflt="$fpossize"
  echo " "
  echo "(I can't compile the test program. Guessing...)" >&4
  rp="What is the size of your file positions (in bytes)?"
  ./myread
  fpossize="$ans"

```

```
fi
$rm_try
fi
;;
esac
```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/perl/uselfs.U
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 2000 Jarkko Hietaniemi

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?MAKE:d_fp_class: Inlibc

?MAKE: -pick add \$@ %<

?S:d_fp_class:

?S: This variable conditionally defines the HAS_FP_CLASS symbol, which

?S: indicates to the C program that the fp_class() routine is available.

?S:.

?C:HAS_FP_CLASS:

?C: This symbol, if defined, indicates that the fp_class routine is

?C: available to classify doubles. Available for example in Digital UNIX.

?C: The returned values are defined in <math.h> and are:

?C:

?C: FP_SNAN Signaling NaN (Not-a-Number)

?C: FP_QNAN Quiet NaN (Not-a-Number)

?C: FP_POS_INF +infinity

?C: FP_NEG_INF -infinity

?C: FP_POS_NORM Positive normalized

?C: FP_NEG_NORM Negative normalized

?C: FP_POS_DENORM Positive denormalized

?C: FP_NEG_DENORM

 Negative denormalized

?C: FP_POS_ZERO +0.0 (positive zero)

?C: FP_NEG_ZERO -0.0 (negative zero)

?C:.

?H:#\$d_fp_class HAS_FP_CLASS /**/

?H:.

?LINT:set d_fp_class

: see if fp_class exists

set fp_class d_fp_class

eval \$inlibc

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_fp_class.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_safebcpy.U,v 3.0.1.4 1997/02/28 15:40:58 ram Exp \$

?RCS:

?RCS: Copyright (c) 1991-1993, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 3.0.

?RCS:

?RCS: \$Log: d_safebcpy.U,v \$

?RCS: Revision 3.0.1.4 1997/02/28 15:40:58 ram

?RCS: patch61: improved overlapping copy check

?RCS: patch61: comfort them if they have memmove

?RCS: patch61: added ?F: metalint hint

?RCS:

?RCS: Revision 3.0.1.3 1995/07/25 13:58:40 ram

?RCS: patch56: re-arranged compile line to include ldflags before objects

?RCS:

?RCS: Revision 3.0.1.2 1995/01/11 15:29:23 ram

?RCS: patch45: added 'ldflags' to the test compile line (ADO)

?RCS:

?RCS:

Revision 3.0.1.1 1994/05/06 14:49:03 ram

?RCS: patch23: ensure string is not optimized in read-only memory (ADO)

?RCS:

?RCS: Revision 3.0 1993/08/18 12:06:58 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?MAKE:d_safebcpy: cat d_bcopy Compile rm_try run \

d_memmove i_memory i_stdlib i_string i_unistd Oldconfig Setvar

?MAKE: -pick add \$@ %<

?S:d_safebcpy:

?S: This variable conditionally defines the HAS_SAFE_BCOPY symbol if

?S: the bcopy() routine can do overlapping copies. Normally, you

?S: should probably use memmove().

?S:.

?C:HAS_SAFE_BCOPY (SAFE_BCOPY):

?C: This symbol, if defined, indicates that the bcopy routine is available

?C: to copy potentially overlapping memory blocks. Normally, you should

?C: probably use memmove() or memcpy(). If neither is defined, roll your

?C: own version.

?C:.

```

?H:#$d_safebcopy HAS_SAFE_BCOPY /**/
?H:.
?F:!try
?LINT: set d_safebcopy
: can bcopy handle overlapping blocks?
echo " "
?X: assume the worst.
val="$undef"
case "$d_memmove" in
"$define")
echo "I'll use memmove() instead of bcopy() for overlapping copies." ;;
*) case "$d_bcopy" in
"$define")
echo "Checking to see if bcopy() can do overlapping copies..." >&4
$cat >try.c <<EOCP
#$i_memory I_MEMORY
#$i_stdlib I_STDLIB
#$i_string I_STRING
#$i_unistd I_UNISTD
EOCP
$cat >>try.c <<'EOCP'
#include <stdio.h>
#ifdef I_MEMORY
# include <memory.h>
#endif
#ifdef I_STDLIB
# include <stdlib.h>
#endif
#ifdef I_STRING
# include <string.h>
#else
# include <strings.h>
#endif
#ifdef I_UNISTD
# include <unistd.h> /* Needed for NetBSD */
#endif
int main()
{
char buf[128], abc[128];
char *b;
int len;
int off;
int align;

/* Copy "abcde..." string to char abc[] so that gcc doesn't
try to store the string in read-only memory. */
bcopy("abcdefghijklmnopqrstuvwxy0123456789", abc, 36);

```

```

for (align = 7; align >= 0; align--) {
for (len = 36; len; len--) {
b = buf+align;
bcopy(abc, b, len);
for (off = 1; off <= len; off++) {
bcopy(b, b+off, len);
bcopy(b+off,
b, len);
if (bcmp(b, abc, len))
exit(1);
}
}
}
exit(0);
}

```

EOCP

```

set try
if eval $compile_ok; then
if $run ./try 2>/dev/null; then
echo "Yes, it can."
val="$define"
else
echo "It can't, sorry."
fi
else
echo "(I can't compile the test program, so we'll assume not...)"
fi
;;
esac
$rm_try
;;
esac
set d_safebcpy
eval $setvar

```

Found in path(s):

```

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/compline/d_safebcpy.U

```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: Cppsym.U,v 3.0.1.5 1995/05/12 11:59:11 ram Exp \$

?RCS:

?RCS: Copyright (c) 1991-1993, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 3.0.

?RCS:

?RCS: \$Log: Cppsym.U,v \$

?RCS: Revision 3.0.1.5 1995/05/12 11:59:11 ram

?RCS: patch54: split awk command onto two lines for older awk's (ADO)

?RCS:

?RCS: Revision 3.0.1.4 1995/01/11 14:55:57 ram

?RCS: patch45: new cc vs. cpp symbol checking suggested by JHI

?RCS: patch45: added more cpp symbols (JHI)

?RCS:

?RCS: Revision 3.0.1.3 1994/10/29 15:51:32 ram

?RCS: patch36: added ?F: line for metalint file checking

?RCS: patch36: new symbols ardent and titan (ADO)

?RCS:

?RCS:

Revision 3.0.1.2 1994/06/20 06:53:32 ram

?RCS: patch30: extended cpp symbol lookup list (JHI)

?RCS: patch30: renamed attrlist symbol into al for brevity

?RCS:

?RCS: Revision 3.0.1.1 1993/12/15 08:14:14 ram

?RCS: patch15: added new cpp symbols __bsdi__ and BSD_NET2

?RCS:

?RCS: Revision 3.0 1993/08/18 12:04:50 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?X: This unit produces a shell script called Cppsym, which can be used to

?X: determine whether any in a list of symbols is defined by the C compilation

?X: chain (C preprocessor symbols plus C compiler native ones).

?X: It can determine the status of any symbol, though the symbols in \$al

?X: are more easily determined. If you want to add to \$al you can do

?X: it in Myinit.U.

?MAKE:Cppsym ccsymbols cppsymbols cppccsymbols: run \
eunicefix Guess awk cat tr sed sort rm rm_try startsh osname \
+cc +gccversion test comm uniq echo Options trnl \
optimize cflags ldflags libs cpp_stuff cpp

?MAKE: -pick add \$@ %<

?T:also

symbols i postprocess_cc_v tHdrH

?X:

?X: The symbol list is in alpha order for ease of maintenance...

?X:

?X: Lots of new symbols (mostly rummaged from gcc), courtesy of

?X: Jarkko Hietaniemi <jhi@snakemail.hut.fi> -- RAM, 06/06/94

?X:

?S:ccsymbols:

?S: The variable contains the symbols defined by the C compiler alone.

?S: The symbols defined by cpp or by cc when it calls cpp are not in

?S: this list, see cppsymbols and cppccsymbols.

?S: The list is a space-separated list of symbol=value tokens.
?S:.
?S:cppsymbols:
?S: The variable contains the symbols defined by the C preprocessor
?S: alone. The symbols defined by cc or by cc when it calls cpp are
?S: not in this list, see ccsymbols and cppccsymbols.
?S: The list is a space-separated list of symbol=value tokens.
?S:.
?S:cppccsymbols:
?S: The variable contains the symbols defined by the C compiler
?S: when it calls cpp. The symbols defined by the cc alone or cpp
?S: alone are not in this list, see ccsymbols and cppsymbols.
?S: The
list is a space-separated list of symbol=value tokens.
?S:.
?F:/Cppsym
?F:/Cppsym.know
?F:!Cppsym.true
?F!:ccsym.com
?F!:ccsym.cpp
?F!:ccsym.own
?X: fake LINT hints
?LINT:change ccflags
?LINT:extern s
?LINT:extern s__
: Preprocessor symbols
echo " "
\$echo "Guessing which symbols your C compiler and preprocessor define..." >&4
?X: If your symbol is mixed case, just add it as-is.
?X: All symbols will be transformed to both all-lower and all-upper.
?X: Also drop any leading/trailing underscores, the scan will try all those.
\$cat <<'EOSH' > Cppsym.know
a29k aarch64 ABI64 aegis AES_SOURCE AIX AIX32 AIX370 AIX41 AIX42
AIX43 aixpc AIX_SOURCE alliant ALL_SOURCE alpha AM29000 am29000
AMD64 amd64 amiga AMIGAOS AMIX ansi ANSI_C_SOURCE apollo arch_ppc
arch_pwr ardent ARM ARM32 atarist att386 att3b
BeOS BIG_ENDIAN BIT_MSF BSD bsd bsd43 bsd4_2 BSD4_3 bsd4_3 bsd4_4
BSDCOMPAT bsdi BSD_4_3 BSD_4_4 BSD_NET2 BSD_TIME BSD_TYPES bull
byteorder byte_order
c cadmus clang clipper CMU COFF COMPILER_VERSION
concurrent
convex cpu CRAY cray CRAYMPP ctix CX_UX CYGWIN
DECC DGUX DGUX_SOURCE DJGPP dmert DOLPHIN DPX2 DSO Dynix DynixPTX
ELF encore EPI EXTENSIONS
FAVOR_BSD FILE_OFFSET_BITS FORTIFY_SOURCE FreeBSD
GCC_NEW_VARARGS gcos gcx gimpel GLIBC GLIBC_MINOR GNUC GNUC_MINOR
GNU_LIBRARY GNU_SOURCE GO32 gould GOULD_PN
H3050R H3050RX hbullx20 hex host_mips hp200 hp300 HP700 hp700

hp800 hp9000 hp9000s200 hp9000s300 hp9000s400 hp9000s500
hp9000s700 hp9000s800 hp9k8 hppa hpux HPUX_SOURCE hp_osf
i186 i286 i386 i486 i586 i686 i8086 i80960 i860 I960 IA32 IA64
iAPX286 ibm ibm032 ibmesa IBMR2 ibmrt ILP32 ILP64
INLINE_INTRINSICS INT64 INTEL interdata INTRINSICS is68k titanium
ksr1
LANGUAGE_C LARGEFILE64_SOURCE LARGEFILE_SOURCE LARGE_FILE_API
LFS64_LARGEFILE LFS_LARGEFILE LIBCATAMOUNT Linux LITTLE_ENDIAN
LONG64 LONGDOUBLE LONGLONG LONG_DOUBLE LONG_LONG LP64 luna
luna88k Lynx
M68000 m68k m88100 m88k M88KBCS_TARGET MACH machine MachTen
MATH_HAS_NO_SIDE_EFFECTS mc300 mc500 mc68000 mc68010 mc68020
mc68030
mc68040 mc68060 mc68k mc68k32 mc700 mc88000 mc88100
merlin mert MiNT mips MIPSEB MIPSEL MIPS_FPSET MIPS_ISA MIPS_SIM
MIPS_SZINT MIPS_SZLONG MIPS_SZPTR MODERN_C motorola mpeix MSDOS
MTXINU MULTIMAX MVS mvs M_AMD64 M_ARM M_ARMT M_COFF M_I186 M_I286
M_I386 M_I8086 M_I86 M_I86SM M_IA64 M_IX86 M_PPC M_SYS3 M_SYS5
M_SYSIII M_SYSV M_UNIX M_X86 M_XENIX
n16 ncl_el ncl_mr NetBSD news1500 news1700 news1800 news1900
news3700 news700 news800 news900 NeXT NLS nonstopux ns16000
ns32000 ns32016 ns32332 ns32k nsc32000
OCS88 OEMVS OpenBSD os OS2 OS390 osf OSF1 OSF_SOURCE
PARAGON parisc pa_risc PA_RISC1_1 PA_RISC2_0 pc532 pdp11 PGC PIC
plexus PORTAR posix POSIX1B_SOURCE POSIX2_SOURCE POSIX4_SOURCE
POSIX_C_SOURCE POSIX_SOURCE POWER powerpc ppc PROTOTYPES PWB pyr
QK_USER QNX
R3000 REENTRANT RES Rhapsody RISC6000 riscix riscos RT
S390 S390x SA110 SCO scs sequent sgi SGI_SOURCE SH SH3 sinix
SIZE_INT SIZE_LONG SIZE_PTR SOCKETS_SOURCE SOCKET_SOURCE sony
sonyrisc sony_news sparc sparclite sparcv8 sparcv9 spectrum
stardent
stdc STDC_EXT stratos sun sun3 sun386 Sun386i svr3 svr4
SVR4_2 SVR4_SOURCE svr5 SX system SYSTYPE_BSD SYSTYPE_BSD43
SYSTYPE_BSD44 SYSTYPE_SVR4 SYSTYPE_SVR5 SYSTYPE_SYSV SYSV SYSV3
SYSV4 SYSV5 sysV68 sysV88
Tek4132 Tek4300 thumb thw_370 thw_intel thw_rs6000 titan TM3200
TM5400 TM5600 tower tower32 tower32_200 tower32_600 tower32_700
tower32_800 tower32_850 tss
u370 u3b u3b2 u3b20 u3b200 u3b20d u3b5 ultrix UMAXV UnicomPBB
UnicomPBD UNICOS UNICOSMK unix UNIX95 UNIX99 unixpc unos USE_BSD
USE_FILE_OFFSET64 USE_GNU USE_ISOC9X USE_LARGEFILE
USE_LARGEFILE64 USE_MISC USE_POSIX USE_POSIX199309
USE_POSIX199506 USE_POSIX2 USE_REENTRANT USE_SVID USE_UNIX98
USE_XOPEN USE_XOPEN_EXTENDED USGr4 USGr4_2 UTek Utek UTS UWIN
uxpm uxps
vax venix VMESA vms
x86_64 xenix Xenix286 XOPEN_SOURCE XOPEN_SOURCE_EXTENDED XPG2

```

XPG2_EXTENDED XPG3 XPG3_EXTENDED XPG4 XPG4_EXTENDED
z8000 zarch
EOSH
# Maybe put other stuff here too.
?X:Some OS's will have a dash in their $osname
?X:e.g. Android is known as linux-android
?X:The
preprocessor will interpret the dash as a minus
./tr '-' '_' <<EOSH >>Cppsym.know
$osname
EOSH
./tr '[a-z]' '[A-Z]' < Cppsym.know > Cppsym.a
./tr '[A-Z]' '[a-z]' < Cppsym.know > Cppsym.b
$cat Cppsym.know > Cppsym.c
$cat Cppsym.a Cppsym.b Cppsym.c | $tr ' ' $trnl | $sort | $uniq > Cppsym.know
$rm -f Cppsym.a Cppsym.b Cppsym.c
cat <<EOSH > Cppsym
$startsh
if $test $# -gt 0; then
    echo $* | $tr " " "$trnl" | ./Cppsym.try > Cppsym.got
    if $test -s Cppsym.got; then
        $rm -f Cppsym.got
    exit 0
    fi
    $rm -f Cppsym.got
    exit 1
else
    $tr " " "$trnl" | ./Cppsym.try
    exit 0
fi
EOSH
chmod +x Cppsym
$unicefix Cppsym
?X: The below awk script will die a horrible death if
?X: some of the tested symbols are not long ints.
?X: Also, we do not make difference between just defined and defined zero.
cat <<EOSH > Cppsym.try
$startsh
cat <<'EOCP' > try.c
#include <stdio.h>
#if cpp_stuff == 1
#define STRINGIFY(a) "a"
#endif
#if cpp_stuff == 42
#define StGiFy(a) #a
#define
STRINGIFY(a) StGiFy(a)
#endif

```

```

#if $cpp_stuff != 1 && $cpp_stuff != 42
# include "Bleth: How does this C preprocessor stringify macros?"
#endif
int main() {
EOCP
?X: The length($1) command guards against possible empty entries.
?X: The awk snippet is know to give heartburn to UNICOS/mk awk.
$awk \\
EOSH
cat <<'EOSH' >> Cppsym.try
'length($1) > 0 {
    printf "#ifdef %s\nprintf(\"%s=%s\n\", STRINGIFY(%s));\n#endif\n", $1, $1, $1
    printf "#ifdef _%s\nprintf(\"_%s=%s\n\", STRINGIFY(_%s));\n#endif\n", $1, $1, $1
    printf "#ifdef __%s\nprintf(\"__%s=%s\n\", STRINGIFY(__%s));\n#endif\n", $1, $1, $1
    printf "#ifdef __%s__\nprintf(\"__%s__=%s\n\", STRINGIFY(__%s__));\n#endif\n", $1, $1, $1
}' >> try.c
echo 'return 0;}' >> try.c
EOSH
cat <<'EOSH' >> Cppsym.try
ccflags="$ccflags"
case "$osname-$gccversion" in
irix-) ccflags="\$ccflags -woff 1178" ;;
os2-*) ccflags="\$ccflags -Zlinker /PM:VIO" ;;
esac
$cc -o try -Dcpp_stuff=$cpp_stuff $optimize \$ccflags $ldflags try.c
$libs 2>/dev/null && $run ./try | $sed 's/ ^\\\\ /g'
EOSH
chmod +x Cppsym.try
$eunicefix Cppsym.try
./Cppsym < Cppsym.know | $sort | $uniq > Cppsym.true
: Add in any Linux cpp "predefined macros":
case "$osname::$gccversion" in
*linux*:*:*|*gnukfreebsd*:*:*|gnu:*:*|*)
    tHdrH=_tmpHdr
    rm -f $tHdrH.h' $tHdrH
    touch $tHdrH.h'
    # Filter out macro arguments, such as Linux's __INT8_C(c)
    if $cpp -dM $tHdrH.h' > $tHdrH'_cppsym.h' && [ -s $tHdrH'_cppsym.h' ]; then
        sed -e 's/#define[\\ ]*//;s/[\\ ]*$/ -e 's/(.*)' <$tHdrH'_cppsym.h' >$tHdrH'_cppsym.real'
        if [ -s $tHdrH'_cppsym.real' ]; then
            cat $tHdrH'_cppsym.real' Cppsym.know | sort | uniq | ./Cppsym | sort | uniq > Cppsym.true
        fi
    fi
    rm -f $tHdrH.h' $tHdrH'_cppsym.h' $tHdrH'_cppsym.real'
;;
esac
: now check the C compiler for additional symbols
?X: suggested by Jarkko Hietaniemi <jhi@snakemail.hut.fi>, thanks!

```

```

postprocess_cc_v="
case "$osname" in
aix) postprocess_cc_v="|${tr} , '
    " ;;
esac
$cat >ccsym <<EOS
$startsh
$cat >tmp.c <<EOF
extern int foo;
EOF
for i in ` $cc -v -c tmp.c 2>&1 $postprocess_cc_v `
do
case "$i" in
-D*) echo "$i" | $sed 's/^-D//';;
-A*) $test "$gccversion" && echo "$i" | $sed 's/^-A//' | $sed 's/^(.*)/(.*)/1=2/';;
esac
done
$rm_try
EOS
postprocess_cc_v="
chmod +x ccsym
$unicefix ccsym
./ccsym > ccsym1.raw
?X: AIX complains if $uniq is passed an empty file. ($sort apparently
?X: doesn't care.) --AD 14 July 1998
if $test -s ccsym1.raw; then
    $sort ccsym1.raw | $uniq >ccsym.raw
else
    mv ccsym1.raw ccsym.raw
fi

?X: canonicalize symbols for easier sort/uniq/comm usage: append =1 if no = sign
?X: the awk script must be on two lines for older awk programs, sigh! -- ADO
$awk '^=/ { print $0; next }
{ print $0"=1" }' ccsym.raw >ccsym.list
$comm -13 Cppsym.true ccsym.list >ccsym.own
$comm -12 Cppsym.true ccsym.list >ccsym.com
$comm -23 Cppsym.true ccsym.list >ccsym.cpp
also="
if $test -z ccsym.raw; then
echo "Your C compiler
doesn't seem to define any symbols!" >&4
echo " "
echo "However, your C preprocessor defines the following symbols:"
$cat Cppsym.true
ccsymbols="
cppsymbols=`$cat Cppsym.true`
cppsymbols=`echo $cppsymbols`

```

```

cppccsymbols="$ccpsymbols"
else
if $test -s ccsym.com; then
echo "Your C compiler and pre-processor define these symbols:"
$sed -e 's^(.*\)=.*\1/' ccsym.com
also='also '
symbols='ones'
cppccsymbols=`$cat ccsym.com`
cppccsymbols=`echo $cppccsymbols`
$test "$$silent" || sleep 1
fi
if $test -s ccsym.cpp; then
$test "$$also" && echo " "
echo "Your C pre-processor ${also}defines the following symbols:"
$sed -e 's^(.*\)=.*\1/' ccsym.cpp
also='further '
cppsymbols=`$cat ccsym.cpp`
cppsymbols=`echo $cppsymbols`
$test "$$silent" || sleep 1
fi
if $test -s ccsym.own; then
$test "$$also" && echo " "
echo "Your C compiler ${also}defines the following cpp symbols:"
$sed -e 's^(.*\)=1\1/' ccsym.own
$sed -e 's^(.*\)=.*\1/' ccsym.own | $uniq
>>Cppsym.true
ccsymbols=`$cat ccsym.own`
ccsymbols=`echo $ccsymbols`
$test "$$silent" || sleep 1
fi
fi

: add -D_FORTIFY_SOURCE if feasible and not already there
case "$gccversion" in
[4567].*) case "$optimize$ccflags" in
*-O*) case "$ccflags$ccpsymbols" in
*_FORTIFY_SOURCE=*) # Don't add it again.
echo "You seem to have -D_FORTIFY_SOURCE already, not adding it." >&4
;;
*) echo "Adding -D_FORTIFY_SOURCE=2 to ccflags..." >&4
ccflags="$ccflags -D_FORTIFY_SOURCE=2"
;;
esac
;;
*) echo "You have gcc 4.* or later but not optimizing, not adding -D_FORTIFY_SOURCE." >&4
;;
esac
;;

```

```
*) echo "You seem not to have gcc 4.* or later, not adding -D_FORTIFY_SOURCE." >&4
;;
esac
```

Found in path(s):

```
*/opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/modified/Cppsym.U
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: d_vfork.U,v \$

?RCS: Revision 3.0.1.6 1994/08/29 16:18:21 ram

?RCS: patch32: set default to 'y' the first time

?RCS:

?RCS: Revision 3.0.1.5 1994/06/20 06:59:14 ram

?RCS: patch30: usevfork was not always properly set

?RCS:

?RCS: Revision 3.0.1.4 1994/05/13 15:20:56 ram

?RCS: patch27: modified to avoid spurious Whoa warnings (ADO)

?RCS:

?RCS: Revision 3.0.1.3 1994/05/06 14:59:09 ram

?RCS: patch23: now explicitly ask whether vfork() should be used (ADO)

?RCS:

?RCS: Revision 3.0.1.2 1993/10/16

13:49:39 ram

?RCS: patch12: added magic for vfork()

?RCS:

?RCS: Revision 3.0.1.1 1993/09/13 16:06:57 ram

?RCS: patch10: removed automatic remapping of vfork on fork (WAD)

?RCS: patch10: added compatibility code for older config.sh (WAD)

?RCS:

?RCS: Revision 3.0 1993/08/18 12:07:55 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?MAKE:d_vfork usevfork: Inlibc Myread Oldconfig Setvar

?MAKE: -pick add \$@ %<

?S:d_vfork:

?S: This variable conditionally defines the HAS_VFORK symbol, which

?S: indicates the vfork() routine is available.

```

?S:
?S:usevfork:
?S: This variable is set to true when the user accepts to use vfork.
?S: It is set to false when no vfork is available or when the user
?S: explicitly requests not to use vfork.
?S:
?C:HAS_VFORK (VFORK):
?C: This symbol, if defined, indicates that vfork() exists.
?C:
?H:#$d_vfork HAS_VFORK /**/
?H:
?M:vfork: HAS_VFORK
?M:#ifndef HAS_VFORK
?M:#define vfork fork
?M:#endif
?M:
?LINT:set d_vfork
: see if there is a vfork
val="
set
vfork val
eval $inlibc

: Ok, but do we want to use it. vfork is reportedly unreliable in
: perl on Solaris 2.x, and probably elsewhere.
case "$val" in
$define)
echo " "
case "$usevfork" in
false) dflt='n';
*) dflt='y';;
esac
rp="Some systems have problems with vfork(). Do you want to use it?"
./myread
case "$ans" in
y|Y) ;;
*)
echo "Ok, we won't use vfork()."
val="$undef"
;;
esac
;;
esac
set d_vfork

```

```
eval $setvar
case "$d_vfork" in
$define) usevfork='true';;
*) usevfork='false';;
esac
```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/d_vfork.U
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: vendorlib.U,v 1.1 1999/07/08 18:32:57 doughera Exp doughera \$

?RCS:

?RCS: Copyright (c) 1999, Andy Dougherty

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 3.0.

?RCS:

?RCS: \$Log: vendorlib.U,v \$

?RCS: Revision 1.1 1999/07/08 18:32:57 doughera

?RCS: Initial revision

?RCS:

?MAKE:d_vendorlib vendorlib vendorlibexp installvendorlib vendorlib_stem: \

Getfile Setprefixvar Oldconfig Prefixit package vendorprefix sed \

installstyle version

?MAKE: -pick add \$@ %<

?Y:TOP

?S:vendorlib:

?S: This variable contains the eventual value of the VENDORLIB symbol,

?S: which is the name of the private library for this package.

?S: The standard

distribution will put nothing in this directory.

?S: Vendors who distribute perl may wish to place their own

?S: modules in this directory with

?S: MakeMaker Makefile.PL INSTALLDIRS=vendor

?S: or equivalent. See INSTALL for details.

?S:.

?S:vendorlibexp:

?S: This variable is the ~name expanded version of vendorlib, so that you

?S: may use it directly in Makefiles or shell scripts.

?S:.

?D:installvendorlib="

?S:installvendorlib:

?S: This variable is really the same as vendorlibexp but may differ on

?S: those systems using AFS. For extra portability, only this variable

?S: should be used in makefiles.

?S:.

?S:d_vendorlib:

?S: This variable conditionally defines PERL_VENDORLIB.

?S:.

?S:vendorlib_stem:

?S: This variable is \$vendorlibexp with any trailing version-specific component

?S: removed. The elements in inc_version_list (inc_version_list.U) can

?S: be tacked onto this variable to generate a list of directories to search.

?S:.

?C:PERL_VENDORLIB:

?C: If defined, this symbol contains

the name of a private library.

?C: The library is private in the sense that it needn't be in anyone's

?C: execution path, but it should be accessible by the world. The program

?C: should be prepared to do ~ expansion.

?C: The standard distribution will put nothing in this directory.

?C: Vendors who distribute perl may wish to place their own

?C: modules in this directory with

?C: MakeMaker Makefile.PL INSTALLDIRS=vendor

?C: or equivalent. See INSTALL for details.

?C:.

?C:PERL_VENDORLIB_EXP:

?C: This symbol contains the ~name expanded version of VENDORLIB, to be used

?C: in programs that are not prepared to deal with ~ expansion at run-time.

?C:.

?C:PERL_VENDORLIB_STEM:

?C: This define is PERL_VENDORLIB_EXP with any trailing version-specific component

?C: removed. The elements in inc_version_list (inc_version_list.U) can

?C: be tacked onto this variable to generate a list of directories to search.

?C:.

?H:#\$d_vendorlib PERL_VENDORLIB "\$vendorlib" /**/
 ?H:#\$d_vendorlib PERL_VENDORLIB_EXP
 "\$vendorlibexp" /**/
 ?H:#\$d_vendorlib PERL_VENDORLIB_STEM "\$vendorlib_stem" /**/
 ?H:.

?T:prog

?LINT:change prefixvar

?LINT:set installvendorlib

: Set the vendorlib variables

case "\$vendorprefix" in

*) d_vendorlib="\$undef"

vendorlib="

vendorlibexp="

;;

*) d_vendorlib="\$define"

: determine where vendor-supplied modules go.

: Usual default is /usr/local/lib/perl5/vendor_perl/\$version

```

case "$vendorlib" in
")
?X: remove any trailing -3.0 or other version identification
prog=`echo $package | $sed 's/-*[0-9.]*$//`
case "$installstyle" in
*lib/perl5*) dflt=$vendorprefix/lib/$package/vendor_$prog/$version ;;
*) dflt=$vendorprefix/lib/vendor_$prog/$version ;;
esac
;;
*) dflt="$vendorlib"
;;
esac
fn=d~+
rp='Pathname for the vendor-supplied library files?'
./getfile
vendorlib="$ans"
vendorlibexp="$ansexp"
;;
esac
vendorlib_stem=`echo "$vendorlibexp" | sed "s,/,$version$,,"`
prefixvar=vendorlib
./installprefix

```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/installdirs/vendorlib.U
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: Chk_MANI.U 1 2006-08-24 12:32:52Z rmanfredi \$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic Licence,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic Licence; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: Chk_MANI.U,v \$

?RCS: Revision 3.0.1.2 1997/02/28 14:57:25 ram

?RCS: patch61: added support for src.U

?RCS:

?RCS: Revision 3.0.1.1 1994/10/31 09:33:14 ram

?RCS: patch44: now lists Begin instead of Myinit in its dependencies

?RCS: patch44: leading comment now explains how this unit is included

?RCS:

?RCS: Revision 3.0 1993/08/18 12:04:45 ram

?RCS: Baseline for dist 3.0 netwide release.

```

?RCS:
?X:
?X: This unit checks the package by making sure
every file listed in MANIFEST
?X: is present. It is systematically "included" via the Finish unit (which
?X: is always present in every Configure script), although it may result in
?X: an empty inclusion when no MANIFEST is present.
?X:
?MAKE:Chk_MANI: Begin c n rsrc
?MAKE: -pick wipe $@ %<
?T:filelist ans tmppwd
?X: This check happens at metaconfig-time, so it's ok to hard-code the path.
@if {test -f ../MANIFEST}
: Now test for existence of everything in MANIFEST
echo " "
if test -f "$rsrc/MANIFEST"; then
echo "First let's make sure your kit is complete. Checking..." >&4
?X:
?X: Files spelled uppercased and beginning with PACK are produced by the
?X: shell archive builder and may be removed by the user. Usually, they are
?X: not listed in the MANIFEST file, but you never know...
?X:
?X: "split -l" is the new way of running a split, but we also try the older way
?X:
awk '$1 !~ /PACK[A-Z]+/ {print $1}' "$rsrc/MANIFEST" | \
(split -l 50 2>/dev/null || split -50)
rm -f missing
tmppwd=`pwd`
for
filelist in x??: do
(cd "$rsrc"; ls `cat "$tmppwd/$filelist"` \
>/dev/null 2>>"$tmppwd/missing")
done
if test -s missing; then
cat missing >&4
cat >&4 <<'EOM'

```

THIS PACKAGE SEEMS TO BE INCOMPLETE.

You have the option of continuing the configuration process, despite the distinct possibility that your kit is damaged, by typing 'y'es. If you do, don't blame me if something goes wrong. I advise you to type 'n'o and contact the author (<MAINTLOC>).

EOM

```

?X: Can't use $echo at this early stage
echo $n "Continue? [n] $c" >&4
read ans

```

```

case "$ans" in
y*)
  echo "Continuing..." >&4
  rm -f missing
  ;;
*)
?X:
?X: Use kill and not exit, so that the trap gets executed to clean up
?X:
  echo "ABORTING..." >&4
  kill $$
  ;;
esac
else
  echo "Looks good..."
fi
else
  echo "There is no MANIFEST file. I hope your kit is complete !"
fi
rm -f missing x??

@end

```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/Chk_MANI.U
```

No license file was found, but licenses were detected in source scan.

```

?RCS: $Id: registers.U 1 2006-08-24 12:32:52Z rmanfredi $
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: $Log: registers.U,v $
?RCS: Revision 3.0.1.2 1997/02/28 16:19:41 ram
?RCS: patch61: removed empty ?LINT lines
?RCS:
?RCS: Revision 3.0.1.1 1994/10/29 16:28:33 ram
?RCS: patch36: call ./Cpplib explicitly instead of relying on PATH
?RCS:
?RCS: Revision 3.0 1993/08/18 12:09:41 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:

```

?MAKE:registers reg1 reg2 reg3 reg4 reg5 reg6 reg7 reg8 reg9 reg10 reg11 \
reg12 reg13 reg14 reg15 reg16: awk rm Cppsym
Myread Oldconfig
?MAKE: -pick add \$@ %<
?S:registers:
?S: This variable contains the number of register declarations paid
?S: attention to by the C compiler.
?S:.
?S:reg1:
?S: This variable, along with reg2, reg3, etc. contains the eventual
?S: value for the symbols register1, register2, register3, etc. It has
?S: either the value "register" or is null.
?S:.
?C:register1:
?C: This symbol, along with register2, register3, etc. is either the word
?C: "register" or null, depending on whether the C compiler pays attention
?C: to this many register declarations. The intent is that you don't have
?C: to order your register declarations in the order of importance, so you
?C: can freely declare register variables in sub-blocks of code and as
?C: function parameters. Do not use register<n> more than once per routine.
?C:.
?LINT:describe reg2 reg3 reg4 reg5 reg6 reg7 reg8 reg9 reg10 reg11
?LINT:describe reg12 reg13 reg14 reg15 reg16
?LINT:known register2 register3 register4 register5 register6
register7
?LINT:known register8 register9 register10 register11 register12 register13
?LINT:known register14 register15 register16
?H:#define register1 \$reg1 /**/
?H:#define register2 \$reg2 /**/
?H:#define register3 \$reg3 /**/
?H:#define register4 \$reg4 /**/
?H:#define register5 \$reg5 /**/
?H:#define register6 \$reg6 /**/
?H:#define register7 \$reg7 /**/
?H:#define register8 \$reg8 /**/
?H:#define register9 \$reg9 /**/
?H:#define register10 \$reg10 /**/
?H:#define register11 \$reg11 /**/
?H:#define register12 \$reg12 /**/
?H:#define register13 \$reg13 /**/
?H:#define register14 \$reg14 /**/
?H:#define register15 \$reg15 /**/
?H:#define register16 \$reg16 /**/
?H:.
?F:!.foo
: see how many register declarations we want to use
case "\$registers" in
")

```

if ./Cppsymb vax; then
  dflt=6
elif ./Cppsymb sun mc68000 mips; then
  dflt=10
elif ./Cppsymb pyr; then
  dflt=14
elif ./Cppsymb ns32000 ns16000; then
  dflt=5
elif ./Cppsymb $smallmach; then
  dflt=3
else
  : if you have any other numbers
  for me, please send them in
  dflt=6
fi;;
*) dflt=$registers ;;
esac
?LINT:set reg2 reg3 reg4 reg5 reg6 reg7 reg8 reg9 reg10 reg11
?LINT:set reg12 reg13 reg14 reg15 reg16
cat <<EOM

```

Different C compilers on different machines pay attention to different numbers of register declarations. About how many register declarations in each routine does your C compiler pay attention to? (OK to guess)

```

EOM
rp="Maximum register declarations?"
./myread
registers=$ans
reg1="
$awk "BEGIN { for (i=1; i<=16; i++) printf \"reg%d=\\n\\\", i} \" \
</dev/null >.foo
./foo
$awk "BEGIN { for (i=1; i<=$registers; i++) printf \"reg%d=register\\n\\\", i} \" \
</dev/null >.foo
./foo
$rm -f .foo

```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/registers.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: d_scorfl.U 1 2006-08-24 12:32:52Z rmanfredi $
```

```
?RCS:
```

```
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
```

```
?RCS:
```

```
?RCS: You may redistribute only under the terms of the Artistic Licence,
```

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic Licence; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: d_scorfl.U,v \$

?RCS: Revision 3.0 1993/08/18 12:07:01 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?MAKE:d_scorfl: cat Myread Oldconfig nametype Setvar

?MAKE: -pick add \$@ %<

?S:d_scorfl:

?S: This variable conditionally defines the SCOREFULL symbol, which

?S: indicates to the C program that any scoreboard kept by the program

?S: should be kept on the basis of the user's full name as opposed to

?S: the user's login name.

?S:.

?C:SCOREFULL:

?C: This

symbol, if defined, indicates that any scoreboard kept by the

?C: program should be kept on the basis of the user's full name as opposed

?C: to the user's login name. If the user can change his full name he

?C: can enter multiple scores if this is defined.

?C:.

?H:#\$d_scorfl SCOREFULL /**/

?H:.

?LINT:set d_scorfl

: see how they want the scoreboard kept

case "\$d_scorfl" in

"\$define") dflt=y ;;

*) dflt=n ;;

esac

case "\$nametype" in

other) val="\$undef" ;;

*)

\$cat <<'EOM'

The scoreboard can be kept with one score per login name, or one score per full name. If users can change their full name, or if there is more than one person on your system with the same full name, you should keep the score by login name (the full name is still printed).

EOM

rp='Do you want the scoreboard kept by full name?'

./myread

case "\$ans" in

y*) val="\$define" ;;

*) val="\$undef" ;;

```
esac
;;
esac
set d_scorfl
eval $setvar
```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/d_scorfl.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: d_endnent.U,v 3.0 1993/08/18 12:06:09 ram Exp $
```

```
?RCS:
```

```
?RCS: Copyright (c) 1991-1993, Raphael Manfredi
```

```
?RCS:
```

```
?RCS: You may redistribute only under the terms of the Artistic License,
```

```
?RCS: as specified in the README file that comes with the distribution.
```

```
?RCS: You may reuse parts of this distribution only within the terms of
```

```
?RCS: that same Artistic License; a copy of which may be found at the root
```

```
?RCS: of the source tree for dist 3.0.
```

```
?RCS:
```

```
?RCS: $Log: d_endnent.U,v $
```

```
?RCS: Revision 3.0 1993/08/18 12:06:09 ram
```

```
?RCS: Baseline for dist 3.0 netwide release.
```

```
?RCS:
```

```
?MAKE:d_endnent: Inlibc
```

```
?MAKE: -pick add $@ %<
```

```
?S:d_endnent:
```

```
?S: This variable conditionally defines HAS_ENDNETENT if endnetent() is
```

```
?S: available to close whatever was being used for network queries.
```

```
?S:.
```

```
?C:HAS_ENDNETENT:
```

```
?C: This symbol, if defined, indicates that the endnetent() routine is
```

```
?C: available to close whatever was being used for network
```

```
queries.
```

```
?C:.
```

```
?H:#$d_endnent HAS_ENDNETENT /**/
```

```
?H:.
```

```
?LINT:set d_endnent
```

```
: see if endnetent exists
```

```
set endnetent d_endnent
```

```
eval $inlibc
```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/modified/d_endnent.U
```

No license file was found, but licenses were detected in source scan.

```

?RCS: $Id$
?RCS:
?RCS: Copyright (c) 2001 Jarkko Hietaniemi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 3.0.
?RCS:
?MAKE:d_dbminiproto: Hasproto i_dbm
?MAKE: -pick add $@ %<
?S:d_dbminiproto:
?S: This variable conditionally defines the HAS_DBMINIT_PROTO symbol,
?S: which indicates to the C program that the system provides
?S: a prototype for the dbminiproto() function. Otherwise, it is
?S: up to the program to supply one.
?S:
?C:HAS_DBMINIT_PROTO:
?C: This symbol, if defined, indicates that the system provides
?C: a prototype for the dbminiproto() function. Otherwise, it is up
?C: to the program to supply one. A good guess is
?C: extern
?C: int dbminiproto(char *);
?C:
?H:#$d_dbminiproto HAS_DBMINIT_PROTO /**/
?H:
?LINT:set d_dbminiproto
: see if prototype for dbminiproto is available
echo " "
set d_dbminiproto dbminiproto $i_dbm dbm.h
eval $hasproto

```

Found in path(s):

```

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/perl/d_dbminiproto.U

```

No license file was found, but licenses were detected in source scan.

```

?RCS: $Id: sitarch.U,v 3.1 1999/07/08 18:32:29 doughera Exp doughera $
?RCS:
?RCS: Copyright (c) 1996-1998, Andy Dougherty
?RCS: Copyright (c) 1991-1993, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 3.0.

```

?RCS:
?RCS: \$Log: sitearch.U,v \$
?RCS: Revision 3.1 1999/07/08 18:32:29 doughera
?RCS: Updated for perl5.005_5x
?RCS:
?RCS: Revision 3.0.1.1 1997/02/28 16:21:30 ram
?RCS: patch61: created
?RCS:
?MAKE:sitearch sitearchexp installsitearch d_sitearch: cat sed Getfile \
Oldconfig Setprefixvar Prefixit test archname sitelib
?MAKE: -pick add \$@ %<
?Y:TOP
?D:sitearch="
?S:sitearch:
?S: This variable contains the eventual
value of the SITEARCH symbol,
?S: which is the name of the private library for this package. It may
?S: have a ~ on the front. It is up to the makefile to eventually create
?S: this directory while performing installation (with ~ substitution).
?S: The standard distribution will put nothing in this directory.
?S: After perl has been installed, users may install their own local
?S: architecture-dependent modules in this directory with
?S: MakeMaker Makefile.PL
?S: or equivalent. See INSTALL for details.
?S:.
?D:sitearchexp="
?S:sitearchexp:
?S: This variable is the ~name expanded version of sitearch, so that you
?S: may use it directly in Makefiles or shell scripts.
?S:.
?D:installsitearch="
?S:installsitearch:
?S: This variable is really the same as sitearchexp but may differ on
?S: those systems using AFS. For extra portability, only this variable
?S: should be used in makefiles.
?S:.
?D:d_sitearch="
?S:d_sitearch:
?S: This variable conditionally defines SITEARCH to hold the
pathname
?S: of architecture-dependent library files for \$package. If
?S: \$sitearch is the same as \$archlib, then this is set to undef.
?S:.
?C:SITEARCH:
?C: This symbol contains the name of the private library for this package.
?C: The library is private in the sense that it needn't be in anyone's
?C: execution path, but it should be accessible by the world. The program
?C: should be prepared to do ~ expansion.

```

?C: The standard distribution will put nothing in this directory.
?C: After perl has been installed, users may install their own local
?C: architecture-dependent modules in this directory with
?C: MakeMaker Makefile.PL
?C: or equivalent. See INSTALL for details.
?C:.
?C:SITEARCH_EXP:
?C: This symbol contains the ~name expanded version of SITEARCH, to be used
?C: in programs that are not prepared to deal with ~ expansion at run-time.
?C:.
?H:#$d_sitearch SITEARCH "$sitearch" /**/
?H:#$d_sitearch SITEARCH_EXP "$sitearchexp" /**/
?H:.
?LINT:change prefixvar
?LINT:set installsitearch
?LINT:set
sitearch
?LINT:set sitearchexp
: determine where site specific architecture-dependent libraries go.
: sitelib default is /usr/local/lib/perl5/site_perl/$version
: sitearch default is /usr/local/lib/perl5/site_perl/$version/$archname
: sitelib may have an optional trailing /share.
case "$sitearch" in
*) dflt=`echo $sitelib | $sed 's,/share$,,'`
dflt="$dflt/$archname"
;;
*) dflt="$sitearch"
;;
esac
set sitearch sitearch none
eval $prefixit
$cat <<EOM

```

The installation process will also create a directory for architecture-dependent site-specific extensions and modules.

```

EOM
fn=d~+
rp='Pathname for the site-specific architecture-dependent library files?'
./getfile
prefixvar=sitearch
./setprefixvar
if $test X"$sitearch" = X"$sitelib"; then
d_sitearch="$undef"
else
d_sitearch="$define"
fi

```

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/installdirs/sitearch.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: Tye McQueen <tye@metronet.com> added safe setuid script checks.

?RCS:

?RCS: \$Log: d_dosuid.U,v \$

?RCS: Revision 3.0.1.2 1997/02/28 15:33:03 ram

?RCS: patch61: moved unit to TOP via a ?Y: layout directive

?RCS: patch61: tell them /dev/fd is not about floppy disks

?RCS:

?RCS: Revision 3.0.1.1 1994/10/29 16:12:08 ram

?RCS: patch36: added checks for secure setuid scripts (Tye McQueen)

?RCS:

?RCS: Revision 3.0 1993/08/18 12:05:55 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?MAKE:d_dosuid

d_suidsaf: cat contains ls rm test Myread Setvar \

Oldconfig Guess package hint

?MAKE: -pick add \$@ %<

?S:d_suidsaf:

?S: This variable conditionally defines SETUID_SCRIPTS_ARE_SECURE_NOW

?S: if setuid scripts can be secure. This test looks in /dev/fd/.

?S:.

?S:d_dosuid:

?S: This variable conditionally defines the symbol DOSUID, which

?S: tells the C program that it should insert setuid emulation code

?S: on hosts which have setuid #! scripts disabled.

?S:.

?C:SETUID_SCRIPTS_ARE_SECURE_NOW:

?C: This symbol, if defined, indicates that the bug that prevents

?C: setuid scripts from being secure is not present in this kernel.

?C:.

?C:DOSUID:

?C: This symbol, if defined, indicates that the C program should

?C: check the script that it is executing for setuid/setgid bits, and

?C: attempt to emulate setuid/setgid on systems that have disabled
 ?C: setuid #! scripts because the kernel can't do it securely.
 ?C: It is up to the package designer to make sure that this emulation
 ?C: is done securely.
 Among other things, it should do an fstat on
 ?C: the script it just opened to make sure it really is a setuid/setgid
 ?C: script, it should make sure the arguments passed correspond exactly
 ?C: to the argument on the #! line, and it should not trust any
 ?C: subprocesses to which it must pass the filename rather than the
 ?C: file descriptor of the script to be executed.
 ?C:.
 ?H:#\$d_suidsaf SETUID_SCRIPTS_ARE_SECURE_NOW /**/
 ?H:#\$d_dosuid DOSUID /**/
 ?H:.
 ?Y:TOP
 ?F:!reflect
 ?LINT: set d_suidsaf
 ?LINT: set d_dosuid
 : see if setuid scripts can be secure
 \$cat <<EOM

Some kernels have a bug that prevents setuid #! scripts from being
 secure. Some sites have disabled setuid #! scripts because of this.

First let's decide if your kernel supports secure setuid #! scripts.
 (If setuid #! scripts would be secure but have been disabled anyway,
 don't say that they are secure if asked.)

EOM

```
val="$undef"
if $test -d /dev/fd; then
  echo "#!$ls" >reflect
  chmod +x,u+s reflect
  ./reflect >flect
  2>&1
  if $contains "/dev/fd" flect >/dev/null; then
    echo "Congratulations, your kernel has secure setuid scripts!" >&4
    val="$define"
  else
    $cat <<EOM
```

If you are not sure if they are secure, I can check but I'll need a
 username and password different from the one you are using right now.
 If you don't have such a username or don't want me to test, simply
 enter 'none'.

EOM

```
rp='Other username to test security of setuid scripts with?'
```

```

dflt='none'
./myread
case "$ans" in
n|none)
case "$d_suidsafesafe" in
") echo "I'll assume setuid scripts are *not* secure." >&4
dflt=n;;
"$undef")
echo "Well, the $hint value is *not* secure." >&4
dflt=n;;
*) echo "Well, the $hint value *is* secure." >&4
dflt=y;;
esac
;;
*)
$rm -f reflect flect
echo "#!$ls" >reflect
chmod +x,u+s reflect
echo >flect
chmod a+w flect
echo "'su' will (probably) prompt you for '$ans's password.'"
su $ans -c './reflect >flect'
if $contains "/dev/fd" flect
>/dev/null; then
echo "Okay, it looks like setuid scripts are secure." >&4
dflt=y
else
echo "I don't think setuid scripts are secure." >&4
dflt=n
fi
;;
esac
rp='Does your kernel have *secure* setuid scripts?'
./myread
case "$ans" in
[yY]*) val="$define";;
*) val="$undef";;
esac
fi
else
echo "I don't think setuid scripts are secure (no /dev/fd directory)." >&4
echo "(That's for file descriptors, not floppy disks.)"
val="$undef"
fi
set d_suidsafesafe
eval $setvar

$rm -f reflect flect

```

```

: now see if they want to do setuid emulation
echo " "
val="$undef"
case "$d_suidsaf" in
"$define")
val="$undef"
echo "No need to emulate SUID scripts since they are secure here." >& 4
;;
*)
$cat <<EOM

```

Some systems have disabled setuid scripts, especially systems where setuid scripts cannot be secure. On systems where setuid scripts have been disabled, the setuid/setgid bits on scripts are currently useless. It is possible for \$package to detect those bits and emulate setuid/setgid in a secure fashion. This emulation will only work if setuid scripts have been disabled in your kernel.

```

EOM
case "$d_dosuid" in
"$define") dflt=y ;;
*) dflt=n ;;
esac
rp="Do you want to do setuid/setgid emulation?"
. ./myread
case "$ans" in
[yY]*) val="$define";;
*) val="$undef";;
esac
;;
esac
set d_dosuid
eval $setvar

```

Found in path(s):

```

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/d_dosuid.U

```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 2000 Jarkko Hietaniemi

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?MAKE:d_isfinitel: Inlibc

?MAKE: -pick add \$@ %<
?S:d_isfinitel:
?S: This variable conditionally defines the HAS_ISFINITEL symbol, which
?S: indicates to the C program that the isfinitel() routine is available.
?S:.
?C:HAS_ISFINITEL:
?C: This symbol, if defined, indicates that the isfinitel routine is
?C: available to check whether a long double is finite.
?C: (non-infinity non-NaN).
?C:.
?H:#\$d_isfinitel HAS_ISFINITEL /**/
?H:.
?LINT:set d_isfinitel
: see if isfinitel exists
set isfinitel d_isfinitel
eval \$inlibc

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_isfinitel.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: Copyright (c) 2001 Jarkko Hietaniemi
?RCS:
?MAKE:run to from targetarch usecrosscompile: src awk cat grep test rm \
echo sed mkdir cp touch chmod
?MAKE: -pick add \$@ %<
?Y:TOP
?S:usecrosscompile:
?S: This variable conditionally defines the USE_CROSS_COMPILE symbol,
?S: and indicates that our package has been cross-compiled.
?S:.
?S:run:
?S: This variable contains the command used by Configure
?S: to copy and execute a cross-compiled executable in the
?S: target host. Useful and available only during
the build.
?S: Empty string " if not cross-compiling.

?S:
?S:from:
?S: This variable contains the command used by Configure
?S: to copy files from the target host. Useful and available
?S: only during the build.
?S: The string ':' if not cross-compiling.
?S:
?S:to:
?S: This variable contains the command used by Configure
?S: to copy to from the target host. Useful and available
?S: only during the build.
?S: The string ':' if not cross-compiling.
?S:
?S:targetarch:
?S: If cross-compiling, this variable contains the target architecture.
?S: If not, this will be empty.
?S:
?C:USE_CROSS_COMPILE:
?C: This symbol, if defined, indicates that the package is being
?C: cross-compiled.
?C:
?C:CROSS_TARGET_ARCH:
?C: This symbol, if defined, indicates the target architecture
?C: the package has been cross-compiled to.
?C: Undefined if not a cross-compile.
?C:
?H:?usecrosscompile:#ifndef USE_CROSS_COMPILE
?H:?usecrosscompile:#\$usecrosscompile USE_CROSS_COMPILE /**/
?H:?usecrosscompile:#define
CROSS_TARGET_ARCH "\$targetarch" /**/
?H:?usecrosscompile:#endif
?H:
?T:croak pwd exe f q i j cwd
?LINT:extern usecrosscompile
?LINT:extern cc
?LINT:extern usrinc
?LINT:change usrinc
?LINT:change ar
?LINT:change nm
?LINT:change ranlib
?LINT:extern targethost
?LINT:extern targetdir
?LINT:change targetdir
?LINT:extern targetuser
?LINT:change targetuser
?LINT:extern targetrun
?LINT:extern targetfrom
?LINT:extern targetto

```

?LINT:extern targetmkdir
?LINT:change targetrun
?LINT:change targetfrom
?LINT:change targetto
?LINT:change targetmkdir
?LINT:extern incpth
?LINT:extern libpth
?LINT:change incpth
?LINT:change libpth
?LINT:extern locincpth
?LINT:extern loclibpth
?LINT:change locincpth
?LINT:change loclibpth
?LINT:extern TMPDIR
: setup for possible cross-compilation
run="
to=:
from=:
usecrosscompile='undef'
targetarch="
case "$usecrosscompile" in
$define|true|[yY]*)
@if { test -d ../Cross }
?X:
?X: Cross-compilation is enabled when there is a 'Cross' directory found
?X: at the root
of the package. This directory must contain the following
?X: entries for defining the cross-compilation process:
?X:
?X: FIXME FIXME
?X: WE MUST DISTINGUISH BETWEEN LOCAL cross-compiling AND REMOTE ONE
?X: ACTUALLY, REMOTE COMPILATION SHOULD BE CONFIGURED INTERACTIVELY
?X: IT WILL COPY ALL THE FILES FROM THE MANIFEST DOWN TO THE REMOTE DIR...
?X: (and copy things like 'mkdep', etc...)
?X:
$echo "Cross-compiling..."
croak="
case "$cc" in
*-*-gcc)
?X: A cross-compiling gcc, probably.
targetarch=`$echo $cc|$sed 's/-gcc$//'^
ar=$targetarch-ar
?X: leave out ld, choosing it is more complex
nm=$targetarch-nm
ranlib=$targetarch-ranlib
$echo 'extern int foo;' > try.c
set X ` $cc -v -E try.c 2>&1 | \
Sawk '/^#include </,/^End of search /'|$grep '/include`

```

```

shift
if $test $# -gt 0; then
    incpth="$incpth $*"
    incpth="$echo $incpth|sed 's/^ //' "
    echo "Guessing incpth '$incpth'." >&4
    for i in $*; do
        j="$echo $i|sed 's,/include$,/lib,\' "
        if
$test -d $j; then
            libpth="$libpth $j"
        fi
    done
    libpth="$echo $libpth|sed 's/^ //' "
    echo "Guessing libpth '$libpth'." >&4
    fi
    $rm -f try.c
    ;;
esac
case "$targetarch" in
") echo "Targetarch not defined." >&4; croak=y ;;
*) echo "Using targetarch $targetarch." >&4 ;;
esac
case "$incpth" in
") echo "Incpth not defined." >&4; croak=y ;;
*) echo "Using incpth '$incpth'." >&4 ;;
esac
case "$libpth" in
") echo "Libpth not defined." >&4; croak=y ;;
*) echo "Using libpth '$libpth'." >&4 ;;
esac
case "$usrinc" in
")
for i in $incpth; do
if $test -f $i/errno.h -a -f $i/stdio.h -a -f $i/time.h; then
    usrinc=$i
    echo "Guessing usrinc $usrinc." >&4
    break
fi
done
case "$usrinc" in
") echo "Usrinc not defined." >&4; croak=y ;;
esac
;;
*) echo "Using usrinc $usrinc." >&4 ;;
esac
case "$targethost" in
") echo "Targethost not defined." >&4; croak=y ;;
*) echo "Using targethost $targethost."

```

```

>&4
esac
locincpth=' '
loclibpth=' '
case "$croak" in
y) echo "Cannot continue, aborting." >&4; exit 1 ;;
esac
case "$src" in
/*) run=$src/Cross/run
    targetmkdir=$src/Cross/mkdir
    to=$src/Cross/to
    from=$src/Cross/from
    ;;
*) pwd=`$test -f ../Configure & cd ..; pwd`
    run=$pwd/Cross/run
    targetmkdir=$pwd/Cross/mkdir
    to=$pwd/Cross/to
    from=$pwd/Cross/from
    ;;
esac
case "$targetrun" in
") targetrun=ssh ;;
esac
case "$targetto" in
") targetto=scp ;;
esac
case "$targetfrom" in
") targetfrom=scp ;;
esac
run=$run-$targetrun
to=$to-$targetto
from=$from-$targetfrom
case "$targetdir" in
")
targetdir="{TMPDIR:-/tmp}"
echo "Guessing targetdir $targetdir." >&4
;;
esac
case "$targetuser" in
")
targetuser=root
echo "Guessing targetuser $targetuser." >&4
;;
esac
case "$targetfrom" in
scp) q=-q ;;
*) q="" ;;
esac

```

```

case "$targetrun" in
ssh|rsh)
  $cat >$run <<EOF
#!/bin/sh
case "$1" in
-cwd)
  shift
  cwd=$1
  shift
  ;;
esac
case "$cwd" in
") cwd=$targetdir ;;
esac
exe=$1
shift
if $test ! -f \${exe}.xok; then
  $to \${exe}
  $touch \${exe}.xok
fi
$targetrun -l $targetuser $targethost "cd \${cwd} && ./\${exe} \${@"
EOF
;;
*) echo "Unknown targetrun '$targetrun'" >&4
  exit 1
  ;;
esac
case "$targetmkdir" in
*/Cross/mkdir)
  $cat >$targetmkdir <<EOF
#!/bin/sh
$targetrun -l $targetuser $targethost "mkdir -p \${@"
EOF
  $chmod a+rx $targetmkdir
  ;;
*) echo "Unknown targetmkdir '$targetmkdir'" >&4
  exit 1
  ;;
esac
case "$targetto" in
scp|rcp)
  $cat >$to <<EOF
#!/bin/sh
for f in \${@"
do
  case "\${f}" in
/*)
    $targetmkdir `dirname \${f}`

```

```

    targetto $q \${f} $targetuser@$targethost:\${f}      || exit 1
    ;;
*)
    targetmkdir $targetdir/\dirname \${f}\
    targetto $q \${f} $targetuser@$targethost:$targetdir/\${f} || exit 1
    ;;
esac
done
exit 0
EOF
    ;;
cp) $cat >$to <<EOF
#!/bin/sh
for f in \${@}
do
    case "\${f}" in
    /*)
        $mkdir -p $targetdir/\dirname
        \${f}\
        $cp \${f} $targetdir/\${f} || exit 1
        ;;
    *)
        targetmkdir $targetdir/\dirname \${f}\
        $cp \${f} $targetdir/\${f} || exit 1
        ;;
    esac
done
exit 0
EOF
    ;;
*) echo "Unknown targetto '$targetto'" >&4
    exit 1
    ;;
esac
case "$targetfrom" in
scp|rcp)
    $cat >$from <<EOF
#!/bin/sh
for f in \${@}
do
    $rm -f \${f}
    targetfrom $q $targetuser@$targethost:$targetdir/\${f} . || exit 1
done
exit 0
EOF
    ;;
cp) $cat >$from <<EOF
#!/bin/sh

```

```

for f in \$@
do
$rm -f \$f
cp $targetdir/\$f . || exit 1
done
exit 0
EOF
;;
*) echo "Unknown targetfrom '$targetfrom'" >&4
exit 1
;;
esac
if $test ! -f $run; then
echo "Target 'run' script '$run' not found." >&4
else
$chmod a+rx $run
fi
if $test ! -f $to; then
echo "Target 'to' script '$to' not found." >&4
else
$chmod a+rx $to
fi
if $test ! -f $from; then
echo "Target 'from' script '$from' not found." >&4
else
$chmod a+rx $from
fi
if $test ! -f $run -o ! -f $to -o !
-f $from; then
exit 1
fi
$cat >&4 <<EOF
Using '$run' for remote execution,
and '$from' and '$to'
for remote file transfer.
EOF
@else
echo "Cross-compilation is not supported for this package." >&4
exit 1
@end
;;
esac

```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/Cross.U
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: myhostname.U,v \$

?RCS: Revision 3.0.1.3 1997/02/28 16:15:55 ram

?RCS: patch61: improved hostname lookup by using ypmatch when NIS is used

?RCS:

?RCS: Revision 3.0.1.2 1994/10/29 16:25:43 ram

?RCS: patch36: call ./xenix explicitly instead of relying on PATH

?RCS: patch36: now uses new Tr unit to convert to/from lowercase

?RCS:

?RCS: Revision 3.0.1.1 1994/06/20 07:06:20 ram

?RCS: patch30: now a little more clever for domain name guessing

?RCS:

?RCS: Revision 3.0 1993/08/18 12:09:18 ram

?RCS:

Baseline for dist 3.0 netwide release.

?RCS:

?MAKE:myhostname phostname mydomain: contains sed test Myread Oldconfig \
Guess Loc awk echo sort uniq +usrinc rm hostcat Tr osname

?MAKE: -pick add \$@ %<

?S:myhostname (hostname):

?S: This variable contains the eventual value of the MYHOSTNAME symbol,
?S: which is the name of the host the program is going to run on.

?S: The domain is not kept with hostname, but must be gotten from mydomain.

?S: The dot comes with mydomain, and need not be supplied by the program.

?S:.

?S:mydomain:

?S: This variable contains the eventual value of the MYDOMAIN symbol,
?S: which is the domain of the host the program is going to run on.

?S: The domain must be appended to myhostname to form a complete host name.

?S: The dot comes with mydomain, and need not be supplied by the program.

?S:.

?S:phostname:

?S: This variable contains the eventual value of the PHOSTNAME symbol,
?S: which is a command that can be fed to popen() to get the host name.

?S: The program
should probably not presume that the domain is or isn't
?S: there already.

?S:.

?C:MYHOSTNAME (HOSTNAME):

?C: This symbol contains name of the host the program is going to run on.
 ?C: The domain is not kept with hostname, but must be gotten from MYDOMAIN.
 ?C: The dot comes with MYDOMAIN, and need not be supplied by the program.
 ?C: If gethostname() or uname() exist, MYHOSTNAME may be ignored. If MYDOMAIN
 ?C: is not used, MYHOSTNAME will hold the name derived from PHOSTNAME.

?C:.

?C:MYDOMAIN:

?C: This symbol contains the domain of the host the program is going to
 ?C: run on. The domain must be appended to HOSTNAME to form a complete
 ?C: host name. The dot comes with MYDOMAIN, and need not be supplied by
 ?C: the program. If the host name is derived from PHOSTNAME, the domain
 ?C: may or may not already be there, and the program should check.

?C:.

?H:#define MYHOSTNAME "\$myhostname" /**/

?H:#define MYDOMAIN "\$mydomain" /**/

?H:.

?T:cont i tans tmp_re file

: now get the host name

echo

" "

echo "Figuring out host name..." >&4

case "\$myhostname" in

*) cont=true

echo 'Maybe "hostname" will work...'

if tans=`sh -c hostname 2>&1` ; then

myhostname=\$tans

phostname=hostname

cont="

fi

::

*) cont=";;

esac

if \$test "\$cont"; then

if ./xenix; then

echo 'Oh, dear. Maybe "/etc/systemid" is the key...'

if tans=`cat /etc/systemid 2>&1` ; then

myhostname=\$tans

phostname='cat /etc/systemid'

echo "Whadyaknow. Xenix always was a bit strange..."

cont="

fi

elif \$test -r /etc/systemid; then

echo "(What is a non-Xenix system doing with /etc/systemid?)"

fi

fi

if \$test "\$cont"; then

echo 'No, maybe "uname -l" will work...'

if tans=`sh -c 'uname -l' 2>&1` ; then

```

myhostname=$stans
phostname='uname -l'
else
echo 'Strange. Maybe "uname -n" will work...'
if tans=`sh -c 'uname -n' 2>&1` ; then
myhostname=$stans
phostname='uname -n'
else
echo 'Oh well, maybe I can mine it out of whoami.h...'
if tans=`sh -c $contains' sysname $usrinc/whoami.h'
2>&1` ; then
myhostname=`echo "$stans" | $sed 's/^\.*\(\.*\)^1/^
phostname="sed -n -e ""/sysname/s/^\.*\(\.*\)^1/{"" -e p -e q -e '}' <$usrinc/whoami.h"
else
case "$myhostname" in
") echo "Does this machine have an identity crisis or something?"
phostname="";
*)
echo "Well, you said $myhostname before..."
phostname='echo $myhostname';;
esac
fi
fi
fi
fi
case "$myhostname" in
") myhostname=noname ;;
esac
: you do not want to know about this
set $myhostname
myhostname=$1

: verify guess
if $test "$myhostname" ; then
dflt=y
rp='Your host name appears to be "$myhostname"." Right?'
./myread
case "$ans" in
y*) ;;
*) myhostname="";;
esac
fi

: bad guess or no guess
while $test "X$myhostname" = X ; do
dflt="
rp="Please type the (one word) name of your host:"
./myread

```

```
myhostname="$ans"
```

```
done
```

```
: translate upper to lower if necessary
```

```
case "$myhostname" in
```

```
*[A-Z]*)
```

```
echo "(Normalizing case in your host name)"
```

```
myhostname=`echo
```

```
$myhostname | ./tr '[A-Z]' '[a-z]`
```

```
::
```

```
esac
```

```
?X: Do not ask for domain name if this is not used later on. In that
```

```
?X: case, the hostname may keep its domain name, but it doesn't matter.
```

```
@if MYDOMAIN || mydomain
```

```
case "$myhostname" in
```

```
*.*)
```

```
dflt=`expr "X$myhostname" : "X[^.]*\(\..*\)`
```

```
myhostname=`expr "X$myhostname" : "X\([^.*]\)\.`
```

```
echo "(Trimming domain name from host name--host name is now $myhostname)"
```

```
::
```

```
*) case "$mydomain" in
```

```
")
```

```
?X:
```

```
?X: There is currently no way to say we do not want hostcat if mydomain is not
```

```
?X: used. One way to achieve that would be to put that code in a mydomain.U
```

```
?X: unit. However, we want to stick the sanity checks right after the domain
```

```
?X: name computation, or if none is done, right after the hostname computation.
```

```
?X:
```

```
{
```

```
?X: If we use NIS, try ypmatch.
```

```
test "X$hostcat" = "Xypcat hosts" &&
```

```
ypmatch "$myhostname" hosts 2>/dev/null \
```

```
$sed -e 's/[ ]*#.*//; s/$/ /' > hosts && \
```

```
$test -s hosts
```

```
} || {
```

```
?X: Extract only
```

```
the relevant hosts, reducing file size,
```

```
?X: remove comments, insert trailing space for later use.
```

```
$hostcat | $sed -n -e "s/[ ]*#.*//; s^$/ /
```

```
/[ ]$myhostname[ . ]/p" > hosts
```

```
}
```

```
tmp_re="[ .]"
```

```
$test x`$awk "/[0-9].*[ ]$myhostname$tmp_re/ { sum++ }
```

```
END { print sum }" hosts` = x1 || tmp_re="[ ]"
```

```
dflt=`$awk \
```

```
"/[0-9].*[ ]$myhostname$tmp_re/ {for(i=2; i<=NF;i++) print \\$i}" \
```

```
hosts | $sort | $uniq | \
```

```

$sed -n -e "s/$myhostname\\.\\([-a-zA-Z0-9_\\.])\\1/p"
case `echo X$dflt` in
X*\\ *) echo "(Several hosts in /etc/hosts matched hostname)"
dflt=.
;;
?X: There is no /etc/hosts on os390
X.)
if $test -f /etc/hosts; then
echo "(You do not have fully-qualified names in /etc/hosts)"
else
echo "(I cannot locate a hosts database anywhere)"
fi
;;
esac
case "$dflt" in
.)
tans=`./loc resolv.conf X /etc /usr/etc`
if $test -f "$tans"; then
echo "(Attempting domain name extraction from $tans)"
?X: Look for either a search
or a domain directive.
dflt=`$sed -n -e 's/ /g' \
-e 's/^search *\\([\\^ ]*)\\.*/\\1/p' $tans \
| ./tr '[A-Z]' '[a-z]' 2>/dev/null`
case "$dflt" in
.) dflt=`$sed -n -e 's/ /g' \
-e 's/^domain *\\([\\^ ]*)\\.*/\\1/p' $tans \
| ./tr '[A-Z]' '[a-z]' 2>/dev/null`
;;
esac
fi
;;
esac
case "$dflt" in
.) echo "(No help from resolv.conf either -- attempting clever guess)"
dflt=`sh -c domainname 2>/dev/null`
case "$dflt" in
") dflt='.';
.nis.*|.yp.*|.main.*) dflt=`echo $dflt | $sed -e 's/^\\.\\[\\^\\.]*/'`;
esac
;;
esac
case "$dflt$osname" in
.os390)
file="//SYS1.TCPPARMS(TCPDATA)"
echo "(Attempting domain name extraction from $file)"
dflt=`awk '/^DOMAINORIGIN/ {print $2}' "$file" 2>/dev/null`
;;

```

```

    esac
    case "$dflt" in
    .) echo "(Lost all hope -- silly guess then)"
       dflt='.nonet'
       ;;
    esac
    $rm -f hosts
    ;;
    *) dflt="$mydomain";;
    esac;;
esac
echo " "
rp="What is your domain name?"
.
./myread
tans="$ans"
case "$ans" in
") ;;
.*) ;;
*) tans=".$tans";;
esac
mydomain="$tans"

: translate upper to lower if necessary
case "$mydomain" in
*[A-Z]*)
echo "(Normalizing case in your domain name)"
mydomain=`echo $mydomain | ./tr '[A-Z]' '[a-z]'`
;;
esac

@end
: a little sanity check here
case "$phostname" in
") ;;
*)
case ` $phostname | ./tr '[A-Z]' '[a-z]^` in
$myhostname$mydomain|$myhostname) ;;
*)
case "$phostname" in
sed*)
echo "(That doesn't agree with your whoami.h file, by the way.)"
;;
*)
echo "(That doesn't agree with your $phostname command, by the way.)"
;;
esac
;;

```

```
esac
;;
esac
```

Found in path(s):

```
*/opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/myhostname.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id$
```

```
?RCS:
```

```
?RCS: Copyright (c) 1996, Cygnus Support
```

```
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
```

```
?RCS:
```

```
?RCS: You may redistribute only under the terms of the Artistic License,
```

```
?RCS: as specified in the README file that comes with the distribution.
```

```
?RCS: You may reuse parts of this distribution only within the terms of
```

```
?RCS: that same Artistic License; a copy of which may be found at the root
```

```
?RCS: of the source tree for dist 4.0.
```

```
?RCS:
```

```
?RCS: Original Author: Tom Tromeey <tromeey@cygnus.com>
```

```
?RCS:
```

```
?RCS: $Log: src.U,v $
```

```
?RCS: Revision 3.0.1.1 1997/02/28 16:23:54 ram
```

```
?RCS: patch61: created
```

```
?RCS:
```

```
?MAKE:src +rsrc: Options package contains
```

```
?MAKE: -pick add $@ %<
```

```
?Y:TOP
```

```
?S:src (srcdir):
```

```
?S: This variable holds the (possibly relative) path of the package source.
```

```
?S: It is up to the Makefile to use this variable and set VPATH accordingly
```

```
?S: to find the sources remotely. Use $pkgsrc to have an absolute path.
```

```
?S:.
```

```
?S:rsrc
```

```
(relsrcdir):
```

```
?S: This variable holds a potentially relative path to the package
```

```
?S: source. The contents are correct for the configuration environment,
```

```
?S: i.e. there might be an extra .. prepended to get out of the UU dir.
```

```
?S: Configure units should use this, not the src variable.
```

```
?S:.
```

```
: Find the path to the source tree
```

```
case "$src" in
```

```
") case "$0" in
```

```
*/*) src=`echo $0 | sed -e 's%/[^\/]*/$% %`
```

```
case "$src" in
```

```
/*) ;;
```

```
.) ;;
```

```

*) src=`cd ../$src && pwd` ;;
esac
;;
*) src='.';;
esac;;
esac
case "$src" in
") src=/
rsrc=/
;;
/*) rsrc="$src";;
*) rsrc="../$src";;
esac
?X:
?X: Now check whether we have found the right source tree (i.e. the one for the
?X: package we're about to configure). The original unit from Tom Tromeu forced
?X: the user to pick a unique file from his distribution, and we were merely
?X: checking the existence of that file. I prefer to rely on Configure (which
?X: we know *is* present since this unit is
?X: part of it!) and look for the
?X: definition of the package variable, making sure it's the same as ours.
?X: If it matches, we know we found the right source tree. -- RAM, 15/03/96
?X:
if test -f $rsrc/Configure && \
$contains "^package='$package'" $rsrc/Configure >/dev/null 2>&1
then
: found it, so we are ok.
else
?X: Otherwise try "." and up to 4 parent directories...
?X: Note that we prepend a ".." to get out of the configuration environment.
rsrc=""
for src in . .. ../.. ../../.. ../../../..; do
if test -f ../$src/Configure && \
$contains "^package=$package$" ../$src/Configure >/dev/null 2>&1
then
rsrc=../$src
break
fi
done
fi
case "$rsrc" in
")
cat <<EOM >&4

```

Sorry, I can't seem to locate the source dir for \$package. Please start Configure with an explicit path -- i.e. /some/path/Configure.

EOM

```

exit 1
;;
?X: Don't echo anything if the sources are in . -- they should know already ;-)
?X: In that case, rsrc is ../. since we lookup from within UU
../.) rsrc='.';;
*)
echo
" "
echo "Sources for $package found in \"${src}\"." >&4
;;
esac

```

Found in path(s):

```

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/src.U

```

No license file was found, but licenses were detected in source scan.

```

?RCS: $Id: d_getlogin_r.U,v 0RCS:
?RCS: Copyright (c) 2002,2003 Jarkko Hietaniemi
?RCS:
?RCS: You may distribute under the terms of either the GNU General Public
?RCS: License or the Artistic License, as specified in the README file.
?RCS:
?RCS: Generated by the reentr.pl from the Perl 5.8 distribution.
?RCS:
?MAKE:d_getlogin_r getlogin_r_proto: Inlibc Protochk Hasproto i_systypes \
  usethreads i_unistd extern_C
?MAKE: -pick add $@ %<
?S:d_getlogin_r:
?S: This variable conditionally defines the HAS_GETLOGIN_R symbol,
?S: which indicates to the C program that the getlogin_r()
?S: routine is available.
?S:.
?S:getlogin_r_proto:
?S: This variable encodes the prototype of getlogin_r.
?S: It is zero if d_getlogin_r is undef, and one of the
?S: REENTRANT_PROTO_T_ABC macros of reentr.h if d_getlogin_r
?S: is defined.
?S:.
?C:HAS_GETLOGIN_R:
?C: This symbol, if defined, indicates that the getlogin_r routine
?C: is available
?C: to getlogin re-entrantly.
?C:.
?C:GETLOGIN_R_PROTO:
?C: This symbol encodes the prototype of getlogin_r.
?C: It is zero if d_getlogin_r is undef, and one of the
?C: REENTRANT_PROTO_T_ABC macros of reentr.h if d_getlogin_r

```

```

?C: is defined.
?C:.
?H:#$d_getlogin_r HAS_GETLOGIN_R  /**/
?H:#define GETLOGIN_R_PROTO $getlogin_r_proto  /**/
?H:.
?T:try hdrs d_getlogin_r_proto
: see if getlogin_r exists
set getlogin_r d_getlogin_r
eval $inlibc
case "$d_getlogin_r" in
"$define")
hdrs="$i_systypes sys/types.h define stdio.h $i_unistd unistd.h"
case "$d_getlogin_r_proto:$usetthreads" in
":define") d_getlogin_r_proto=define
set d_getlogin_r_proto getlogin_r $hdrs
eval $hasproto ;;
*) ;;
esac
case "$d_getlogin_r_proto" in
define)
case "$getlogin_r_proto" in
"|0) try='int getlogin_r(char*, size_t);'
./protochk "$extern_C $try" $hdrs && getlogin_r_proto=I_BW ;;
esac
case "$getlogin_r_proto" in
"|0) try='int getlogin_r(char*, int);'
./protochk "$extern_C $try" $hdrs && getlogin_r_proto=I_BI
;;
esac
case "$getlogin_r_proto" in
"|0) try='char* getlogin_r(char*, size_t);'
./protochk "$extern_C $try" $hdrs && getlogin_r_proto=B_BW ;;
esac
case "$getlogin_r_proto" in
"|0) try='char* getlogin_r(char*, int);'
./protochk "$extern_C $try" $hdrs && getlogin_r_proto=B_BI ;;
esac
case "$getlogin_r_proto" in
"|0) d_getlogin_r=undef
getlogin_r_proto=0
echo "Disabling getlogin_r, cannot determine prototype." >&4 ;;
* ) case "$getlogin_r_proto" in
REENTRANT_PROTO*) ;;
*) getlogin_r_proto="REENTRANT_PROTO_$getlogin_r_proto" ;;
esac
echo "Prototype: $try" ;;
esac
;;

```

```

*) case "$usetthreads" in
define) echo "getlogin_r has no prototype, not using it." >&4 ;;
esac
d_getlogin_r=undef
getlogin_r_proto=0
;;
esac
;;
*) getlogin_r_proto=0
;;
esac

```

Found in path(s):

```

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/threads/d_getlogin_r.U

```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: Original Author: Andy Dougherty <doughera@lafcol.lafayette.edu>

?RCS:

?RCS: \$Log: lns.U,v \$

?RCS: Revision 3.0.1.1 1994/06/20 07:05:52 ram

?RCS: patch30: created by ADO

?RCS:

?X:

?X: This unit checks whether symbolic links are really supported.

?X: We can't rely on d_symlink because that may be listed in the

?X: C library but unimplemented.

?X:

?MAKE:lns: ln rm touch test

?MAKE: -pick add \$@ %<

?S:lns:

?S: This variable holds the name of the command to make

?S: symbolic links (if they are supported).

It can be used

?S: in the Makefile. It is either 'ln -s' or 'ln'

?S:.

: determine whether symbolic links are supported

echo " "

```

$rm -f blurfl sym
$touch blurfl
if $ln -s blurfl sym > /dev/null 2>&1 && $test -f sym; then
    echo "Symbolic links are supported." >&4
    ln="$ln -s"
else
    echo "Symbolic links are NOT supported." >&4
    ln="$ln"
fi
$rm -f blurfl sym

```

Found in path(s):

```

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/lns.U

```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: socksizetype.U,v \$

?RCS:

?RCS: Copyright (c) 2000 Jarkko Hietaniemi

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?MAKE:socksizetype: \

```

Protochk Oldconfig Myread cat d_socket d_socklen_t sizetype \
usesocks i_socks i_systypes extern_C

```

?MAKE: -pick add \$@ %<

?S:socksizetype:

?S: This variable holds the type used for the size argument

?S: for various socket calls like accept. Usual values include

?S: socklen_t, size_t, and int.

?S:.

?C:Sock_size_t:

?C: This symbol holds the type used for the size argument of

?C: various socket calls (just the base type, not the pointer-to).

?C:.

?H:#define Sock_size_t \$socksizetype /**/

?H:.

?T:xxx yyy try

@if Sock_size_t

: check for type of the size argument to socket calls

case "\$d_socket" in

"\$define")

```

$cat <<EOM

```

Checking to see what type is the last argument

of accept().

EOM

```

yyy="
case "$d_socklen_t" in
"$define") yyy="$yyy socklen_t"
esac
yyy="$yyy $sizetype int long unsigned"
for xxx in $yyy; do
case "$socksizetype" in
") try="$extern_C int accept(int, struct sockaddr *, $xxx *);"
case "$usesocks" in
"$define")
if ./protochk "$try" $_systypes sys/types.h $d_socket sys/socket.h literal '#define INCLUDE_PROTOTYPES'
$_socks socks.h.; then
echo "Your system accepts '$xxx *' for the last argument of accept()."
socksizetype="$xxx"
fi
;;
*) if ./protochk "$try" $_systypes sys/types.h $d_socket sys/socket.h; then
echo "Your system accepts '$xxx *' for the last argument of accept()."
socksizetype="$xxx"
fi
;;
esac
;;
esac
done
: In case none of those worked, prompt the user.
case "$socksizetype" in
") rp='What is the type for socket address structure sizes?'
dflt='int'
./myread
socksizetype=$ans
;;
esac
;;
*) : no sockets, so pick relatively harmless default
socksizetype='int'
;;
esac
@end

```

Found

in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/protos/socksizetype.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: d_wifstat.U,v \$

?RCS: Revision 3.0.1.3 1997/02/28 15:47:43 ram

?RCS: patch61: added a ?F: metalint hint

?RCS:

?RCS: Revision 3.0.1.2 1995/07/25 14:09:10 ram

?RCS: patch56: re-arranged compile line to include ldflags before objects

?RCS:

?RCS: Revision 3.0.1.1 1995/03/21 08:47:46 ram

?RCS: patch52: created

?RCS:

?MAKE:d_wifstat: d_uwait +cc +ccflags +ldflags +libs Oldconfig cat rm

?MAKE: -pick add \$@ %<

?S:d_wifstat:

?S: This symbol conditionally defines USE_WIFSTAT if the C program can
?S: safely
use the WIFxxx macros with the kind of wait() parameter

?S: declared in the program (see UNION_WAIT), or if it can't. Should
?S: only matter on HP-UX, where the macros are incorrectly written and
?S: therefore cause programs using them with an 'union wait' variable
?S: to not compile properly.

?S:.

?C:USE_WIFSTAT:

?C: This symbol, if defined, indicates to the C program that the argument
?C: for the WIFxxx set of macros such as WIFSIGNALED or WIFEXITED can
?C: be of the same kind as the one used to hold the wait() status. Should
?C: only matter on HP-UX, where the macros are incorrectly written and
?C: therefore cause programs using them with an 'union wait' variable
?C: to not compile properly. See also UNION_WAIT.

?C:.

?H:#\$d_wifstat USE_WIFSTAT /**/
?H:.

?T:type

?F:!foo

: see if we can use WIFxxx macros

echo " "

case "\$d_wifstat" in

"\$define") echo "As before, you can safely use WIFEXITED and friends!" >&4;;
"\$undef") echo "You still can't use WIFEXITED and friends!" >&4;;
*)

echo

```

"Let's see whether you can use the WIFEXITED(status) macro and its"
case "$d_uwait" in
"$define") type='union wait';;
*) type='int';;
esac
echo "friends with status declared as '$type status'..."
$cat >foo.c <<EOCP
#include <sys/types.h>
#include <sys/wait.h>

int main()
{
$type status;
int e = 0;

#ifdef WIFEXITED
if (WIFEXITED(status))
printf("\n");
exit(0);
#else
exit(2);
#endif
}
EOCP
d_wifstat="$undef"
if $cc $cflags $ldflags -o foo foo.c $libs >/dev/null 2>&1; then
if ./foo >/dev/null; then
echo "Great! Looks like we can use the WIFxxx macros." >&4
d_wifstat="$define"
else
echo "You don't seem to have WIFxxx macros, but that's ok." >&4
fi
else
echo "Apparently you can't use WIFxxx macros properly." >&4
fi
$rm -f foo.* foo core
;;
esac

```

Found in path(s):

```

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/d_wifstat.U

```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: i_sysdir.U 1 2006-08-24 12:32:52Z rmanfredi \$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: \$Log: i_sysdir.U,v \$
?RCS: Revision 3.0.1.1 1994/08/29 16:22:30 ram
?RCS: patch32: fixed typo in I_SYS_DIR symbol name
?RCS:
?RCS: Revision 3.0 1993/08/18 12:08:30 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:i_sysdir: Inhdr
?MAKE: -pick add \$@ %<
?S:i_sysdir:
?S: This variable conditionally defines the I_SYS_DIR symbol, and indicates
?S: whether a C program should include <sys/dir.h>.
?S:.
?C:I_SYS_DIR (I_SYSDIR):
?C: This symbol, if
defined, indicates to the C program that it should
?C: include <sys/dir.h>.
?C:.
?H:#\$i_sysdir I_SYS_DIR /**/
?H:.
?LINT:set i_sysdir
: see if this is an sysdir system
set sys/dir.h i_sysdir
eval \$inhdr

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/i_sysdir.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: i_sysmode.U,v \$
?RCS:
?RCS: Copyright (c) 2000 Jarkko Hietaniemi
?RCS:
?RCS: You may distribute under the terms of either the GNU General Public
?RCS: License or the Artistic License, as specified in the README file.
?RCS:
?MAKE:i_sysmode: Inhdr Hasfield
?MAKE: -pick add \$@ %<
?S:i_sysmode:
?S: This variable conditionally defines the I_SYSMODE symbol,
?S: and indicates whether a C program should include <sys/mode.h>.

?S:
?C:I_SYSMODE:
?C: This symbol, if defined, indicates that <sys/mode.h> exists and
?C: should be included.

?C:.
?H:#\$i_sysmode I_SYSMODE /**/

?H:.
?LINT:set i_sysmode
: see if this is a sys/mode.h system
set sys/mode.h i_sysmode
eval \$inhdr

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/i_sysmode.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 2003, Jarkko Hietaniemi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 3.0.

?RCS:

?MAKE:d_pthread_attr_setscope: Inlibc

?MAKE: -pick add \$@ %<

?S:d_pthread_attr_setscope:

?S: This variable conditionally defines HAS_PTHREAD_ATTR_SETSCOPE if

?S: pthread_attr_setscope() is available to set the contention scope

?S: attribute of a thread attribute object.

?S:.

?C:HAS_PTHREAD_ATTR_SETSCOPE:

?C: This symbol, if defined, indicates that the pthread_attr_setscope

?C: system call is available to set the contention scope attribute of

?C: a thread attribute object.

?C:.

?H:#\$d_pthread_attr_setscope HAS_PTHREAD_ATTR_SETSCOPE /**/

?H:.

?LINT:set

d_pthread_attr_setscope

: see if pthread_attr_setscope exists

set pthread_attr_setscope d_pthread_attr_setscope

eval \$inlibc

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_pthread_attr_ss.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_lstat.U 1 2006-08-24 12:32:52Z rmanfredi \$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic Licence,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic Licence; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: d_lstat.U,v \$

?RCS: Revision 3.0 1993/08/18 12:06:28 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?MAKE:d_lstat: Inlibc

?MAKE: -pick add \$@ %<

?S:d_lstat:

?S: This variable conditionally defines HAS_LSTAT if lstat() is

?S: available to do file stats on symbolic links.

?S:.

?C:HAS_LSTAT (LSTAT):

?C: This symbol, if defined, indicates that the lstat routine is

?C: available to do file stats on symbolic links.

?C:.

?H:#\$d_lstat HAS_LSTAT /**/

?H:.

?LINT:set

d_lstat

: see if lstat exists

set lstat d_lstat

eval \$inlibc

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/d_lstat.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: i_niin.U 1 2006-08-24 12:32:52Z rmanfredi \$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic Licence,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic Licence; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: i_niin.U,v \$

?RCS: Revision 3.0 1993/08/18 12:08:24 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?X:

?X: This unit looks wether <netinet/in.h> is available or not

?X:

?MAKE:i_niin i_sysin: Inhdr

?MAKE: -pick add \$@ %<

?S:i_niin:

?S: This variable conditionally defines I_NETINET_IN, which indicates

?S: to the C program that it should include <netinet/in.h>. Otherwise,

?S: you may try <sys/in.h>.

?S:.

?S:i_sysin:

?S: This variable conditionally

defines I_SYS_IN, which indicates

?S: to the C program that it should include <sys/in.h> instead of

?S: <netinet/in.h>.

?S:.

?C:I_NETINET_IN:

?C: This symbol, if defined, indicates to the C program that it should

?C: include <netinet/in.h>. Otherwise, you may try <sys/in.h>.

?C:.

?C:I_SYS_IN (I_SYSIN):

?C: This symbol, if defined, indicates to the C program that it should

?C: include <sys/in.h> instead of <netinet/in.h>.

?C:.

?H:#\$i_niin I_NETINET_IN /**/

?H:#\$i_sysin I_SYS_IN /**/

?H:.

?LINT:set i_niin i_sysin

: see if this is a netinet/in.h or sys/in.h system

set netinet/in.h i_niin sys/in.h i_sysin

eval \$inhdr

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/i_niin.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_semop.U 1 2006-08-24 12:32:52Z rmanfredi \$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: \$Log: d_semop.U,v \$
?RCS: Revision 3.0 1993/08/18 12:07:05 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:d_semop: Inlibc
?MAKE: -pick add \$@ %<
?S:d_semop:
?S: This variable conditionally defines the HAS_SEMOP symbol, which
?S: indicates to the C program that the semop() routine is available.
?S:.
?C:HAS_SEMOP:
?C: This symbol, if defined, indicates that the semop() routine is
?C: available to execute semaphore operations.
?C:.
?H:#\$d_semop
HAS_SEMOP /**/
?H:.
?LINT:set d_semop
: see if semop exists
set semop d_semop
eval \$inlibc

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/d_semop.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_byacc.U 1 2006-08-24 12:32:52Z rmanfredi \$
?RCS:
?RCS: Copyright (c) 1996, Andy Dougherty
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: \$Log: d_byacc.U,v \$
?RCS: Revision 3.0.1.1 1997/02/28 15:31:14 ram
?RCS: patch61: created
?RCS:

```
?MAKE:d_byacc: byacc Setvar
?MAKE: -pick add $@ %<
?S:d_byacc:
?S: This variable indicates whether byacc is available.
?S: If the user has specified 'portability', then Makefile.SH
?S: sees $byacc='byacc' whether or not the user actually has
?S: byacc. This variable allows us to determine in a makefile
?S: if we really
    have byacc.
?S:.
?LINT:set d_byacc
: Check if we really have byacc
case "$byacc" in
|"byacc") val="$undef" ;;
*) val="$define" ;;
esac
set d_byacc
eval $setvar
```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/d_byacc.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: usecbacktrace.U,v $
?RCS:
?RCS: Copyright (c) 2014 H.Merijn Brand
?RCS:
?RCS: You may distribute under the terms of either the GNU General Public
?RCS: License or the Artistic License, as specified in the README file.
?RCS:
?RCS: $Log: usecbacktrace.U,v $
?RCS:
?MAKE:usecbacktrace: Myread Oldconfig Setvar Getfile d_backtrace
?MAKE: -pick add $@ %<
?Y:TOP
?S:usecbacktrace:
?S: This variable indicates whether we are compiling with backtrace
?S: support.
?S:.
?C:USE_CBACKTRACE:
?C: This symbol, if defined, indicates that Perl should
?C: be built with support for backtrace.
?C:.
?H:#$usecbacktrace USE_CBACKTRACE /**/
?H:.
?LINT:extern ccflags
?LINT:change ccflags
```

```

: add flags if using c backtrace
case "$usebacktrace" in
"" ) usebacktrace=$undef ;;
[yY]*|true|$define)
  case "$d_backtrace" in
  [yY]*|true|$define)
    case " $ccflags " in
    *" -DUSE_C_BACKTRACE "*" ) # Already there.
    *) ccflags="$ccflags
-DUSE_C_BACKTRACE -g" ;;
    esac
    ;;
    *)
    echo "This system does not support backtrace" >&4
    usebacktrace=$undef
    ;;
    esac
    ;;
  esac

```

Found in path(s):

```

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/perl/usebacktrace.U

```

No license file was found, but licenses were detected in source scan.

```

?RCS: $Id: d_wait4.U 1 2006-08-24 12:32:52Z rmanfredi $
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: $Log: d_wait4.U,v $
?RCS: Revision 3.0 1993/08/18 12:08:01 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:d_wait4: Inlibc
?MAKE: -pick add $@ %<
?S:d_wait4:
?S: This variable conditionally defines the HAS_WAIT4 symbol, which
?S: indicates the wait4() routine is available.
?S:.
?C:HAS_WAIT4 (WAIT4):
?C: This symbol, if defined, indicates that wait4() exists.
?C:.

```

?H:#\$d_wait4 HAS_WAIT4 /**/

?H:.

?LINT:set d_wait4

: see if there is a wait4

set

wait4 d_wait4

eval \$inlibc

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/d_wait4.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 2005 H.Merijn Brand

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?MAKE:d_unsetenv: Inlibc

?MAKE: -pick add \$@ %<

?S:d_unsetenv:

?S: This variable conditionally defines the HAS_UNSETENV symbol, which

?S: indicates to the C program that the unsetenv () routine is available.

?S:.

?C:HAS_UNSETENV:

?C: This symbol, if defined, indicates that the unsetenv () routine is

?C: available for use.

?C:.

?H:#\$d_unsetenv HAS_UNSETENV /**/

?H:.

?LINT:set d_unsetenv

: see if unsetenv exists

set unsetenv d_unsetenv

eval \$inlibc

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_unsetenv.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: mailer.U 1 2006-08-24 12:32:52Z rmanfredi \$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic Licence,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: \$Log: mailer.U,v \$
?RCS: Revision 3.0.1.3 1995/01/11 15:32:11 ram
?RCS: patch45: can now use Loc variables since path stripping is deferred
?RCS:
?RCS: Revision 3.0.1.2 1994/05/06 15:10:04 ram
?RCS: patch23: ensure full path value is used for rmail also
?RCS:
?RCS: Revision 3.0.1.1 1994/01/24 14:14:18 ram
?RCS: patch16: now use _sendmail vars and friends for portability issues
?RCS:
?RCS: Revision 3.0 1993/08/18 12:09:10 ram
?RCS: Baseline for dist
3.0 netwide release.
?RCS:
?MAKE:mailer: test cat rmail mail smail sendmail Getfile Oldconfig
?MAKE: -pick add \$@ %<
?S:mailer:
?S: This variable contains the full pathname of a reasonable mailer.
?S: By reasonable, we mean some program which can understand internet
?S: addresses or at least forward them to some internet router. This
?S: mailer should be invoked as "mailer [options] recipients <mail".
?S:.
: determine the name of a reasonable mailer
case "\$mailer" in
")
if \$test -f "\$sendmail"; then
dflt="\$sendmail"
elif \$test -f "\$smail"; then
dflt="\$smail"
elif \$test -f "\$rmail"; then
dflt="\$rmail"
elif \$test -f /bin/mail; then
dflt=/bin/mail
else
dflt=\$mail
fi
;;
*) dflt="\$mailer";;
esac
\$cat <<EOM

I need the full pathname of the program used to deliver mail on your system.
A typical answer would be /usr/lib/sendmail or /bin/rmail, but you may choose
any other program, as long as it can be fed from standard input and will

honour any user-supplied headers.

EOM

fn=f

rp='Mail

transport agent to be used?'

../getfile

mailer="\$ans"

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/mailer.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: mandirs.U,v \$

?RCS:

?RCS: Copyright (c) 2000, Andy Dougherty

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 3.0.

?RCS:

?RCS: \$Log: mandirs.U,v \$

?RCS:

?MAKE: man1 man2 man3 man4 man5 man6 man7 man8 \

man2ext man4ext man5ext man6ext man7ext man8ext: \

mandirstyle man1dir man1ext man3dir prefix sed

?MAKE: -pick add \$@ %<

?Y:TOP

?X: This unit just provides convenient definitions so that

?X: MakeMaker can sensibly assume that man5 pages go in

?X: \$prefix/man/\$man5 (or \$siteprefix/man/\$man5 as appropriate)

?X: and the BSD vs. SVR4 directory naming conventions will be

?X: handled automatically, as will older System V

?X: \$prefix/man/u_man

style directories.

?X:

?S:man1:

?S: Man 1 pages will normally be installed in \$prefix/man/\$man1.

?S: This variable handles SysV/SVR4/BSD conventions appropriately.

?S: See mandirstyle.

?S:.

?S:man2:

?S: Man 2 pages will normally be installed in \$prefix/man/\$man2.

?S: This variable handles SysV/SVR4/BSD conventions appropriately.

?S: See mandirstyle.

?S:.

?S:man2ext:

?S: Extension for man2 pages, typically just '2'. See mandirstyle.

?S:.

?S:man3:

?S: Man 3 pages will normally be installed in \$prefix/man/\$man3.

?S: This variable handles SysV/SVR4/BSD conventions appropriately.

?S: See mandirstyle.

?S:.

?S:man4:

?S: Man 4 pages will normally be installed in \$prefix/man/\$man4.

?S: This variable handles SysV/SVR4/BSD conventions appropriately.

?S: See mandirstyle.

?S:.

?S:man4ext:

?S: Extension for man4 pages, typically just '4'. See mandirstyle.

?S:.

?S:man5:

?S: Man 5 pages will normally be installed in \$prefix/man/\$man5.

?S: This variable handles SysV/SVR4/BSD conventions appropriately.

?S: See

mandirstyle.

?S:.

?S:man5ext:

?S: Extension for man5 pages, typically just '5'. See mandirstyle.

?S:.

?S:man6:

?S: Man 6 pages will normally be installed in \$prefix/man/\$man6.

?S: This variable handles SysV/SVR4/BSD conventions appropriately.

?S: See mandirstyle.

?S:.

?S:man6ext:

?S: Extension for man6 pages, typically just '6'. See mandirstyle.

?S:.

?S:man7:

?S: Man 7 pages will normally be installed in \$prefix/man/\$man7.

?S: This variable handles SysV/SVR4/BSD conventions appropriately.

?S: See mandirstyle.

?S:.

?S:man7ext:

?S: Extension for man7 pages, typically just '7'. See mandirstyle.

?S:.

?S:man8:

?S: Man 8 pages will normally be installed in \$prefix/man/\$man8.

?S: This variable handles SysV/SVR4/BSD conventions appropriately.

?S: See mandirstyle.

?S:.

?S:man8ext:

```

?S: Extension for man8 pages, typically just '8'. See mandirstyle.
?S:.
?LINT: set man2 man4 man5 man6 man7 man8
?LINT: set man2ext man4ext
?LINT: set man5ext man6ext man7ext man8ext
?T: num s ts
text
?X: eval fools metalint
?T: man
: Determine locations for other man pages. For example, programs
: should place man4 pages in $prefix/man/$man4 with an extension
: of $man4ext. Use bsd naming conventions. See mandirstyle.
: man1 and man3 are handled separately above.
echo "Deducing locations for other man pages for future use."
: Deduce man1 and man3 from existing variables. Keep them for completeness.
: This approach preserves an existing SystemV-style
: /usr/local/man/l_man/man1 hierarchy.
man1=`echo $man1dir | $sed -e "s!$prefix/man/!!"`
man3=`echo $man3dir | $sed -e "s!$prefix/man/!!"`
for num in 2 4 5 6 7 8; do
s=$num
case "$mandirstyle" in
sysv|svr4)
case "$num" in
4) s='7' ;;
5) s='4' ;;
7) s='5' ;;
8) s='1M' ;;
esac
;;
esac
eval "ts=\"\$man${num}\""
eval "text=\"\$man${num}ext\""
case "$ts" in
") ts=`echo $man1 | $sed -e "s/1/$s/g"` ;;
none|$undef) ts=' ' ;;
esac
case "$text" in
") text=`echo $man1ext | $sed -e "s/1/$s/g"` ;;
none|$undef)
text=' ' ;;
esac
: Use extra quotes to preserve an empty '' value.
eval "man${num}=\"\$ts\""
eval "man${num}ext=\"\$text\""
done

```

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/mandirs.U

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: cc.U 1 2006-08-24 12:32:52Z rmanfredi $
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: $Log: cc.U,v $
?RCS: Revision 3.0.1.4 1995/05/12 12:06:47 ram
?RCS: patch54: may now abort Configure when cc does not work
?RCS:
?RCS: Revision 3.0.1.3 1995/01/11 15:20:11 ram
?RCS: patch45: changed gcc checking message to a more explicit one (WED)
?RCS:
?RCS: Revision 3.0.1.2 1994/10/29 16:04:29 ram
?RCS: patch36: detect gcc even when not called as 'gcc' (ADO)
?RCS: patch36: simplified gcc version checking (ADO)
?RCS: patch36: added ?F: line for metalint
file checking
?RCS:
?RCS: Revision 3.0.1.1 1994/05/06 14:26:06 ram
?RCS: patch23: added support for gcc version (ADO)
?RCS:
?RCS: Revision 3.0 1993/08/18 12:05:30 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:cc: Myread Oldconfig Checkcc test
?MAKE: -pick add $@ %<
?S:cc:
?S: This variable holds the name of a command to execute a C compiler which
?S: can resolve multiple global references that happen to have the same
?S: name. Usual values are 'cc' and 'gcc'.
?S: Ferrent ANSI compilers may be called 'c89'. AIX has xlc.
?S:.
?F:!cc.cbu
?D:cc='cc'
: Determine the C compiler to be used
echo " "
case "$cc" in
") dflt=cc;;
*) dflt="$cc";;
```

```

esac
rp="Use which C compiler?"
./myread
cc="$ans"

: See whether they have no cc but they do have gcc
./trygcc
?X: Look for a hint-file generated 'call-back-unit'. Now that the
?X: user has specified the compiler, we may need to set or change some
?X: other defaults.
if $test -f cc.cbu; then
    ./cc.cbu
fi
./checkcc

```

Found

in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/cc.U
```

No license file was found, but licenses were detected in source scan.

```

?RCS: $Id: d_getpgid.U 1 2006-08-24 12:32:52Z rmanfredi $
?RCS:
?RCS: Copyright (c) 1996, Andy Dougherty
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: $Log: d_getpgid.U,v $
?RCS: Revision 3.0.1.1 1997/02/28 15:33:44 ram
?RCS: patch61: created
?RCS:
?MAKE:d_getpgid: Inlibc
?MAKE: -pick add $@ %<
?S:d_getpgid:
?S: This variable conditionally defines the HAS_GETPGID symbol, which
?S: indicates to the C program that the getpgid(pid) function
?S: is available to get the process group id.
?S:.
?C:HAS_GETPGID:
?C: This symbol, if defined, indicates to the C program
    that
?C: the getpgid(pid) function is available to get the
?C: process group id.

```

```
?C:
?H:#$d_getpgid HAS_GETPGID /**/
?H:
?LINT:set d_getpgid
: see if getpgid exists
set getpgid d_getpgid
eval $inlibc
```

Found in path(s):

```
*/opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/d_getpgid.U
```

No license file was found, but licenses were detected in source scan.

Perl5 Metaconfig Units

Copyright (c) 1996-1998, Andy Dougherty

Copyright (c) 1999-2011, H.Merijn Brand

All rights reserved.

These units are the ones I used to build Configure and config_h.SH in the Perl5 distribution.

The Configure script and config_h.SH file in the Perl distribution are generated by a program called metaconfig. To run metaconfig, you will need the full dist 3.0 distribution, maintained by Raphael Manfredi.

As of this writing, the current version is dist3.0, patchlevel 70.

Dist version dist-3.0@70.tar.gz is available on CPAN (the Comprehensive Perl Archive Network) as

<<http://www.perl.com/perl/CPAN/authors/id/RAM/dist-3.0@70.tar.gz>>.

Instructions:

1. Unpack the full perl5 sources. Execute the following command

```
chmod +w Configure config_h.SH Porting/Glossary Porting/config*
```

2. Unpack the archive containing this file in the perl5 source directory. This will create a directory 'U' under the perl5 sources. That directory will contain the metaconfig units for perl5. This will also create two files in the perl5 source tree: MANIFEST.new and .package.
3. Apply any patches to perl in the perl_patches/ directory. (This may well be empty.)
4. Obtain and install dist-3.0pl70.

4. Apply any patches to dist under the dist_patches subdirectory.
5. From your main perl5 source directory, run packinit to regenerate the .package file. **IMPORTANT:** Change the name and address of the maintainer to your own name and address. I don't want bug reports intended for you coming to me.
6. From your main perl5 source directory, run

metalint (or mlint)

and repair every failure it reports.
7. From your main perl5 source directory, run

metaconfig -m (or mconfig -m)
8. Edit U/mkglossary and/or U/mkgloss.pl to point to your dist-3.0pl70 location. (See comments at the top.)
9. Run the U/mksample script to update the contents of the Porting/ subdirectory, or run all parts by hand. (see README)
10. Let me know about any changes, corrections, or enhancements.

Things to watch out for:

1. The Configure in 5.005 is a hand-patched version of that supplied with perl5.004_74 or so. Most of the patches had to do with supporting MPE/iX and EBCDIC systems. I have re-integrated most of the changes back into metaconfig, but I don't really understand why MPE/iX needed some of the patches, so I may have missed something important. I did try to flag questionable changes in the individual units.
The Configure as generated in the 5.9.x branch leading towards 5.10, is also used exactly as is without changes in the 5.8.x and 5.6.x branches, so do not remove support for features that are available in those branches, but are removed from devel (e.g. perl5005threads).
2. Future support of better random number generators should probably start with the randfunc.U unit included here. It's currently broken, but well commented and probably a good place to start.

Descriptions:

The units and other related files have been broken up into the following directories:

acl/

This is an old patch to begin to detect and use ACL (access control list) file protection schemes.

compline/

These are similar to the standard units, but I have modified them to have a more uniform compile command line, usually using the new Compile.U unit. I have submitted these for inclusion into the regular dist distribution. (The cflags.U unit is actually perl-specific since it mentions -DDEBUGGING and -DPOSIX_SOURCE, but that's the only place it is perl-specific.)

dist_patches/

These are patches to dist that must be applied before it is built and installed. I have submitted these for inclusion in the regular dist distribution.

modified/

These are modified versions of the standard units. Also included in this directory are new units that are clearly derived from existing units. I have submitted these for inclusion in the regular dist distribution.

perl/

These are specific to perl. Some are heavily derived from original dist units, and are marked as such. Others are original.

perl_patches/

These are patches to the perl source. This directory should ordinarily be empty, but there may have been drift between the standard version of perl and the one associated with these units.

protos/

These are units modified to use the new Hasproto.U or Protochk.U units to check for prototypes. I have submitted these for inclusion into the regular dist distribution.

target/

This is the very, very beginning of cross-compiler support. It doesn't work yet, and many standard units will need modification.

typedefs/

These are standard units modified to use the modified Typedef.U unit to check for typedefs. (The modified Typdef.U includes a function to avoid unnecessary prompts if the typedef being searched for exists.) I have submitted these for inclusion into the regular dist distribution.

threads/

These are specific to threading perl.

Copyright Information:

Unless otherwise indicated, the files contained in this distribution are:

Copyright (c) 1996-1998, Andy Dougherty

The following licensing terms apply to all files contained in this distribution:

You may distribute the files contained in this distribution under the terms of either

- a) the "Artistic License" which comes with Perl, or
- b) the "Artistic License" which comes with dist, or
- c) the GNU General Public License as published by the Free Software Foundation; either version 1, or (at your option) any later version (see the file "Copying" that comes with the Perl distribution).

Which one to use is your choice.

The units in the "modified" directory have been derived from units associated with the metaconfig program of Raphael Manfredi's "dist" distribution. These units list Raphael Manfredi as the Copyright holder. dist is distributed under a modified version of the Perl Artistic License. Clause 7 of this modified license as contained in dist-3.0-pl60 provides:

7. You may reuse parts of this Package in your own programs, provided that you explicitly state where you got them from, in the source code (and, left to your courtesy, in the documentation), duplicating all the associated copyright notices and disclaimers. Besides your changes, if any, must be clearly marked as such. Parts reused that way will no longer fall under this license if, and only if, the name of your program(s) have no immediate connection with the

name of the Package itself or its associated programs. You may then apply whatever restrictions you wish on the reused parts or choose to place them in the Public Domain--this will apply only within the context of your package.

In accordance with this clause, the versions of these units contained here are made available under the same terms as the rest of the units.

If you have any questions about the use of these units or about the differences between these units and the standard versions, please feel free to ask.

Andy Dougherty doughera@lafayette.edu
Dept. of Physics
Lafayette College
Easton, PA 18042-1782

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/README.dist
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: Obsol_h.U 1 2006-08-24 12:32:52Z rmanfredi $
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: $Log: Obsol_h.U,v $
?RCS: Revision 3.0 1993/08/18 12:05:11 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?X:
?X: This file is prepended to .MT/Obsol_h if that file is not empty. That file
?X: contains the necessary mappings of new symbols to obsolete ones.
?X:
?MAKE:Obsol_h:
?MAKE: -pick prepend $@ ./Obsol_h
?LINT:nocomment
/*
* The following symbols are obsolete. They are mapped to the the new
* symbols only to ease the transition process. The
```

sources should be

* updated so as to use the new symbols only, as the support for these

* obsolete symbols may end without notice.

*/

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/Obsolet_h.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: groupstyp.e.U 1 2006-08-24 12:32:52Z rmanfredi \$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic Licence,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic Licence; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: Original Author: Andy Dougherty <doughera@lafcol.lafayette.edu>

?RCS:

?RCS: \$Log: groupstyp.e.U,v \$

?RCS: Revision 3.0.1.2 1994/10/29 16:18:08 ram

?RCS: patch36: no longer uses Setvar to set 'groupstyp.e' (ADO)

?RCS: patch36: typo fix in the word 'argument' (ADO)

?RCS:

?RCS: Revision 3.0.1.1 1994/06/20 07:00:18 ram

?RCS: patch30: created by ADO

?RCS:

?MAKE:groupstyp.e: gidtype d_getgrps Myread Oldconfig Findhdr cat d_setgrps

?MAKE: -pick add \$@ %<

?INIT:groupstyp.e="

?S:groupstyp.e:

?S: This

variable defines Groups_t to be something like gid_t, int,

?S: ushort, or whatever type is used for the second argument to

?S: getgroups() and setgroups(). Usually, this is the same as

?S: gidtype (gid_t), but sometimes it isn't.

?S:.

?C:Groups_t (GROUPSTYPE):

?C: This symbol holds the type used for the second argument to

?C: getgroups() and setgroups(). Usually, this is the same as

?C: gidtype (gid_t) , but sometimes it isn't.

?C: It can be int, ushort, gid_t, etc...

?C: It may be necessary to include <sys/types.h> to get any

?C: typedef'ed information. This is only required if you have

?C: getgroups() or setgroups()..

```
?C:
?H:?%<:#if defined(HAS_GETGROUPS) || defined(HAS_SETGROUPS)
?H:?%<:#define Groups_t $groupstype /* Type for 2nd arg to [sg]etgroups() */
?H:?%<:#endif
?H:
?W:%<:getgroups HAS_GETGROUPS setgroups HAS_SETGROUPS
: Find type of 2nd arg to 'getgroups()' and 'setgroups()'
echo " "
case "$d_getgrps$d_setgrps" in
*define*)
case
"$groupstype" in
") dflt="$gidtype" ;;
*) dflt="$groupstype" ;;
esac
$cat <<EOM
What type of pointer is the second argument to getgroups() and setgroups()?
Usually this is the same as group ids, $gidtype, but not always.
```

```
EOM
rp='What type pointer is the second argument to getgroups() and setgroups()?'
./myread
groupstype="$ans"
;;
*) groupstype="$gidtype";;
esac
```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/groupstype.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id$
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: $Log: Config_h.U,v $
?RCS: Revision 3.0.1.5 1997/02/28 14:57:43 ram
?RCS: patch61: added support for src.U
?RCS:
?RCS: Revision 3.0.1.4 1995/09/25 09:10:49 ram
?RCS: patch59: commented the purpose of the #un-def directive
```

```

?RCS:
?RCS: Revision 3.0.1.3 1995/01/30 14:25:39 ram
?RCS: patch49: typo fixes in leading config.h comment (WED)
?RCS:
?RCS: Revision 3.0.1.2 1993/08/24 12:13:20 ram
?RCS: patch3: added TOP as a local shell temporary variable
?RCS:
?RCS: Revision 3.0.1.1 1993/08/19 06:42:20
    ram
?RCS: patch1: leading config.sh searching was not aborting properly
?RCS:
?RCS: Revision 3.0 1993/08/18 12:04:47 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?X:
?X: This file ends up producing the config_h.SH script, which is run to produce
?X: the config.h file. The file ./Config_h below contains all the ?H: lines
?X: extracted out of all the units. Metaconfig itself adds the !GROK!THIS!.
?X: Note that this code isn't included into Configure, but must be shipped with.
?X:
?X: For those who wish to know why the file is config_h.SH instead of the more
?X: natural config.h.SH, well... it is to support systems like MS-DOG. Only one
?X: 'dot' is allowed within the file name, as it is part of the "extension" of
?X: the file. MS-DOG will not let you have two 'dots' because that would mean
?X: two "extensions".
?X:
?MAKE:Config_h: Id End Config_sh Obsol_h myuname cf_time cf_by package src
?MAKE: -pick c_h_weed $@ %<
?MAKE: -pick c_h_weed $@ ./Config_h
?MAKE: -pick
    c_h_weed $@ ./Obsol_h
?T:CONFIG TOP
?LINT:unclosed !GROK!THIS!
?LINT:extern CONFIG_H CONFIG_SH
?LINT:change CONFIG_H CONFIG_SH
?LINT:nocomment
case "$CONFIG_SH" in
") CONFIG_SH=config.sh;;
esac
case "$CONFIG_H" in
") CONFIG_H=config.h;;
esac
case $CONFIG in
")
    if test -f $CONFIG_SH; then TOP=.;
    elif test -f ../$CONFIG_SH; then TOP=../;
    elif test -f ../../$CONFIG_SH; then TOP=../../;
    elif test -f ../../../$CONFIG_SH; then TOP=../../../;

```

```

elif test -f ../../../../$CONFIG_SH; then TOP=../../..;
else
  echo "Can't find $CONFIG_SH."; exit 1
fi
. $TOP/$CONFIG_SH
;;
esac
?X: Make sure we are in the directory where the .SH file is located.
case "$0" in
*/*) cd `expr X$0 : 'X\(.*/\)^'` ;;
esac
echo "Extracting $CONFIG_H (with variable substitutions)"
?X:
?X: Since we unconditionally translate leading #undef into /*#define, we're
?X: stuck when we really want to have a #undef in config.h. That's why there
?X: is provision here for #un-def, which is translated back into #undef after
?X:
all original #undef have been processed.
?X:
?X: Previously, we changed all
?X: #undef FOO /**/
?X: into
?X: /*#define FOO /**/
?X: The xlc compiler (available on IBM's AIX) complains that this is
?X: an illegal attempt to write a nested comment, and warns against it.
?X: There's apparently no way to shut the compiler up, either.
?X: This sed command from Hallvard B Furuseth <h.b.furuseth@usit.uio.no>
?X: changes it to
?X: /*#define FOO /**/
sed <<!GROK!THIS!>$CONFIG_H -e 's!^#undef\(.*/\)^!/*#define\1 \*!' -e 's!^#un-def!#undef!'
/*
* This file was produced by running the config_h.SH script, which
* gets its values from $CONFIG_SH, which is generally produced by
* running Configure.
*
* Feel free to modify any of this as the need arises. Note, however,
* that running config_h.SH again will wipe out any changes you've made.
* For a more permanent change edit $CONFIG_SH and rerun config_h.SH.
*
*\Id: Config_h.U 1 2006-08-24 12:32:52Z rmanfredi $
*/

/*
* Package name
  : $package
* Source directory : $src
* Configuration time: $cf_time
* Configured by   : $cf_by

```

* Target system : \$myuname

*/

#ifndef _config_h_

#define _config_h_

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/Config_h.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_gethostprotos.U,v \$

?RCS:

?RCS: Copyright (c) 1991-1993, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 3.0.

?RCS:

?MAKE:d_gethostprotos : Hasproto i_netdb

?MAKE: -pick add \$@ %<

?S:d_gethostprotos:

?S: This variable conditionally defines the HAS_GETHOST_PROTOS symbol,

?S: which indicates to the C program that <netdb.h> supplies

?S: prototypes for the various gethost*() functions.

?S: See also netdbtype.U for probing for various netdb types.

?S:.

?C:HAS_GETHOST_PROTOS:

?C: This symbol, if defined, indicates that <netdb.h> includes

?C: prototypes for gethostent(), gethostbyname(), and

?C: gethostbyaddr(). Otherwise,

it is up to the program to guess

?C: them. See netdbtype.U for probing for various Netdb_XXX_t types.

?C:.

?H:#\$d_gethostprotos HAS_GETHOST_PROTOS /**/

?H:.

?LINT:set d_gethostprotos

?X: This test actually only checks for gethostent() and assumes the

?X: others follow suit. This test fails for ChorusOS, which has

?X: gethostbyname and gethostbyaddr, but not gethostent.

: see if prototypes for various gethostxxx netdb.h functions are available

echo " "

set d_gethostprotos gethostent \$i_netdb netdb.h

eval \$hasproto

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/protos/d_gethostprotos.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: manfmt.U 1 2006-08-24 12:32:52Z rmanfredi \$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic Licence,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic Licence; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: manfmt.U,v \$

?RCS: Revision 3.0.1.5 1997/02/28 16:11:57 ram

?RCS: patch61: don't ask for AFS when they choose to not install pages

?RCS:

?RCS: Revision 3.0.1.4 1995/09/25 09:16:52 ram

?RCS: patch59: unit is now forced to the top of Configure, if possible

?RCS:

?RCS: Revision 3.0.1.3 1995/01/30 14:39:20 ram

?RCS: patch49: new installmanfmt and AFS-lookup for formatted man pages

?RCS: patch49: can now handle installation prefix changes (from WED)

?RCS:

?RCS:

Revision 3.0.1.2 1994/08/29 16:30:31 ram

?RCS: patch32: now uses installation prefix for default setting

?RCS:

?RCS: Revision 3.0.1.1 1993/09/13 16:09:22 ram

?RCS: patch10: allows for L1 man page extension (WAD)

?RCS:

?RCS: Revision 3.0 1993/08/18 12:09:13 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?MAKE:manfmt manfmtexp installmanfmt: Getfile Loc Oldconfig cat manext \

spackage Prefixit prefixexp Prefixup afs test

?MAKE: -pick add \$@ %<

?Y:TOP

?S:manfmt:

?S: This variable contains the name of the directory in which formatted

?S: manual pages are to be put. It is the responsibility of the

?S: Makefile.SH to get the value of this into the proper command. Note

?S: that you may have to do ~name substitution. Use manfmtexp otherwise.

?S:.

?S:manfmtexp:

?S: This is the same as the manfmt variable, but is filename expanded

?S: at configuration time, for programs not willing to deal with it at

?S: run-time.

?S:.

?S:installmanfmt:

?S: This variable is really

the same as manfmtexp, unless you are using

?S: AFS in which case it points to the read/write location whereas

?S: mansrcexp only points to the read-only access location. For extra

?S: portability, you should only use this variable within your makefiles.

?S:.

?LINT:change manext

?T:lookpath

: determine where manual pages go

set manfmt manfmt

eval \$prefixit

\$cat <<EOM

\$spackage has pre-formatted manual pages. If you don't want these installed, answer 'none' to the next question.

EOM

case "\$manfmt" in

")

lookpath="\$prefixexp/catman/man1 \$prefixexp/man/cat1"

lookpath="\$lookpath \$prefixexp/catman/u_man/man1"

lookpath="\$lookpath \$prefixexp/catman/l_man/man1"

lookpath="\$lookpath \$prefixexp/catman/cat1 /usr/catman/local/man1"

lookpath="\$lookpath /usr/catman/man1 /usr/man/cat1"

lookpath="\$lookpath /usr/catman/mann /usr/catman/l_man/man1"

lookpath="\$lookpath /usr/catman/u_man/man1 /usr/catman/man1"

dflt=`./loc . none \$lookpath`

set dflt

eval \$prefixup

::

*) dflt="\$manfmt"

::

esac

fn=dn~

rp='Where

do pre-formatted manual pages go?'

./getfile

if test "X\$manfmtexp" != "X\$ansexp"; then

installmanfmt="

fi

manfmt="\$ans"

manfmtexp="\$ansexp"

if \$afs && \$test "\$manfmt"; then

\$cat <<EOM

Since you are running AFS, I need to distinguish the directory in which manual pages reside from the directory in which they are installed (and from which they are presumably copied to the former directory by occult means).

EOM

```
case "$installmanfmt" in
") dflt=`echo $manfmtexp | sed 's#^/afs/#/afs/.#^';
*) dflt="$installmanfmt";
esac
fn=de~
rp='Where will pre-formatted man pages be installed?'
./getfile
installmanfmt="$ans"
else
installmanfmt="$manfmtexp"
fi
```

```
case "$manfmt" in
") manext='0';
*l) manext=l;;
*n) manext=n;;
*o) manext=l;;
*p) manext=n;;
*C) manext=C;;
*L) manext=L;;
*L1) manext=L1;;
*) manext=l;;
esac
```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/manfmt.U
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: afs.U 1 2006-08-24 12:32:52Z rmanfredi \$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic Licence,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic Licence; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: afs.U,v \$

?RCS: Revision 3.0.1.2 1997/02/28 15:23:06 ram

?RCS: patch61: can now explicitly tell Configure whether AFS is running

?RCS:

```

?RCS: Revision 3.0.1.1 1993/08/24 12:24:43 ram
?RCS: patch3: created
?RCS:
?MAKE:afs afsroot: test
?MAKE: -pick add $@ %<
?S:afs:
?S: This variable is set to 'true' if AFS (Andrew File System) is used
?S: on the system, 'false' otherwise. It is possible to override this
?S: with a hint value or command line option,
but you'd better know
?S: what you are doing.
?S:.
?S:afsroot:
?S: This variable is by default set to '/afs'. In the unlikely case
?S: this is not the correct root, it is possible to override this with
?S: a hint value or command line option. This will be used in subsequent
?S: tests for AFSness in the configure and test process.
?S:.
: allow them to override the AFS root
case "$afsroot" in
") afsroot=/afs ;;
*) afsroot=$afsroot ;;
esac

: is AFS running?
echo " "
case "$afs" in
$define|true) afs=true ;;
$undef|false) afs=false ;;
*) if $test -d $afsroot; then
afs=true
else
afs=false
fi
;;
esac
if $afs; then
echo "AFS may be running... I'll be extra cautious then..." >&4
else
echo "AFS does not seem to be running..." >&4
fi

Found in path(s):
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/afs.U
No license file was found, but licenses were detected in source scan.

?RCS: $Id: i_sysstatfs.U,v $

```

```

?RCS:
?RCS: Copyright (c) 1999 Jarkko Hietaniemi
?RCS:
?RCS: You may distribute under the terms of either the GNU General Public
?RCS: License or the Artistic License, as specified in the README file.
?RCS:
?MAKE:i_sysstatfs: Inhdr Hasfield
?MAKE: -pick add $@ %<
?S:i_sysstatfs:
?S: This variable conditionally defines the I_SYSSTATFS symbol,
?S: and indicates whether a C program should include <sys/statfs.h>.
?S:.
?C:I_SYS_STATFS:
?C: This symbol, if defined, indicates that <sys/statfs.h> exists.
?C:.
?H:#$i_sysstatfs I_SYS_STATFS /**/
?H:.
?LINT:set i_sysstatfs
: see if this is a sys/statfs.h system
set sys/statfs.h i_sysstatfs
eval $inhdr

```

Found in path(s):

```

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/perl/i_sysstatfs.U

```

No license file was found, but licenses were detected in source scan.

```

?RCS: You may distribute under the terms of either the GNU General Public
?RCS: License or the Artistic License, as specified in the README file.
?RCS:
?MAKE:d_nextafter: Inlibc
?MAKE: -pick add $@ %<
?S:d_nextafter:
?S: This variable conditionally defines HAS_NEXTAFTER if nextafter()
?S: is available to return the next machine representable double from
?S: x in direction y.
?S:.
?C:HAS_NEXTAFTER:
?C: This symbol, if defined, indicates that the nextafter routine is
?C: available to return the next machine representable double from
?C: x in direction y.
?C:.
?H:#$d_nextafter HAS_NEXTAFTER /**/
?H:.
?LINT:set d_nextafter
: see if nextafter exists
set nextafter d_nextafter
eval $inlibc

```

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_nextafter.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_socket.U,v 3.0.1.2 1997/02/28 15:46:00 ram Exp \$

?RCS:

?RCS: Copyright (c) 1991-1993, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 3.0.

?RCS:

?RCS: \$Log: d_socket.U,v \$

?RCS: Revision 3.0.1.2 1997/02/28 15:46:00 ram

?RCS: patch61: replaced .a with \$_a all over the place

?RCS:

?RCS: Revision 3.0.1.1 1994/01/24 14:08:04 ram

?RCS: patch16: can now safely declare private nm_extract in dependencies

?RCS:

?RCS: Revision 3.0 1993/08/18 12:07:26 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?MAKE:d_socket d_oldsock d_sockpair socketlib sockethdr \

d_msg_ctrunc d_msg_dontroute d_msg_oob d_msg_peek

d_msg_proxy \

d_scm_rights d_sockaddr_sa_len d_sockaddr_in6 d_sin6_scope_id \

d_ip_mreq d_ip_mreq_source d_ipv6_mreq d_ipv6_mreq_source: \

contains echo n c ar nm nm_opt nm_extract Inlibc Csym _a \

Compile cat rm_try Setvar Hasfield sysroot

?MAKE: -pick add \$@ %<

?S:d_socket:

?S: This variable conditionally defines HAS_SOCKET, which indicates

?S: that the BSD socket interface is supported.

?S:.

?S:d_sockpair:

?S: This variable conditionally defines the HAS_SOCKETPAIR symbol, which

?S: indicates that the BSD socketpair() is supported.

?S:.

?S:d_oldsock:

?S: This variable conditionally defines the OLDSOCKET symbol, which

?S: indicates that the BSD socket interface is based on 4.1c and not 4.2.

?S:.

?S:d_msg_ctrunc:

?S: This variable conditionally defines the HAS_MSG_CTRUNC symbol,

?S: which indicates that the MSG_CTRUNC is available. #ifdef is
?S: not enough because it may be an enum, glibc has been known to do this.
?S:.
?S:d_msg_dontroute:
?S: This variable conditionally defines
the HAS_MSG_DONTRROUTE symbol,
?S: which indicates that the MSG_DONTRROUTE is available. #ifdef is
?S: not enough because it may be an enum, glibc has been known to do this.
?S:.
?S:d_msg_oob:
?S: This variable conditionally defines the HAS_MSG_OOB symbol,
?S: which indicates that the MSG_OOB is available. #ifdef is
?S: not enough because it may be an enum, glibc has been known to do this.
?S:.
?S:d_msg_peek:
?S: This variable conditionally defines the HAS_MSG_PEEK symbol,
?S: which indicates that the MSG_PEEK is available. #ifdef is
?S: not enough because it may be an enum, glibc has been known to do this.
?S:.
?S:d_msg_proxy:
?S: This variable conditionally defines the HAS_MSG_PROXY symbol,
?S: which indicates that the MSG_PROXY is available. #ifdef is
?S: not enough because it may be an enum, glibc has been known to do this.
?S:.
?S:d_scm_rights:
?S: This variable conditionally defines the HAS_SCM_RIGHTS symbol,
?S: which indicates that the SCM_RIGHTS is available. #ifdef is
?S: not
enough because it may be an enum, glibc has been known to do this.
?S:.
?S:d_sockaddr_sa_len:
?S: This variable conditionally defines the HAS_SOCKADDR_SA_LEN symbol,
?S: which indicates that a struct sockaddr structure has the sa_len
?S: member.
?S:.
?S:d_sockaddr_in6:
?S: This variable conditionally defines the HAS_SOCKADDR_IN6 symbol, which
?S: indicates the availability of a struct sockaddr_in6.
?S:.
?S:d_sin6_scope_id:
?S: This variable conditionally defines the HAS_SIN6_SCOPE_ID symbol, which
?S: indicates that a struct sockaddr_in6 structure has the sin6_scope_id
?S: member.
?S:.
?S:d_ip_mreq:
?S: This variable conditionally defines the HAS_IP_MREQ symbol, which
?S: indicates the availability of a struct ip_mreq.
?S:.

?S:d_ip_mreq_source:

?S: This variable conditionally defines the HAS_IP_MREQ_SOURCE symbol,

?S: which indicates the availability of a struct ip_mreq_source.

?S:.

?S:d_ipv6_mreq:

?S: This variable conditionally defines the HAS_IPV6_MREQ symbol, which

?S: indicates

the availability of a struct ipv6_mreq.

?S:.

?S:d_ipv6_mreq_source:

?S: This variable conditionally defines the HAS_IPV6_MREQ_SOURCE symbol,

?S: which indicates the availability of a struct ipv6_mreq_source.

?S:.

?S:socketlib:

?S: This variable has the names of any libraries needed for socket support.

?S:.

?S:sockethdr:

?S: This variable has any cpp '-I' flags needed for socket support.

?S:.

?C:HAS_SOCKET (SOCKET):

?C: This symbol, if defined, indicates that the BSD socket interface is

?C: supported.

?C:.

?C:HAS_SOCKETPAIR (SOCKETPAIR):

?C: This symbol, if defined, indicates that the BSD socketpair() call is

?C: supported.

?C:.

?C:USE_OLD_SOCKET (OLDSOCKET):

?C: This symbol, if defined, indicates that the 4.1c BSD socket interface

?C: is supported instead of the 4.2/4.3 BSD socket interface. For instance,

?C: there is no setsockopt() call.

?C:.

?C:HAS_MSG_CTRUNC:

?C: This symbol, if defined, indicates that the MSG_CTRUNC is supported.

?C: Checking just with #ifdef might not be enough

because this symbol

?C: has been known to be an enum.

?C:.

?C:HAS_MSG_DONTROUTE:

?C: This symbol, if defined, indicates that the MSG_DONTROUTE is supported.

?C: Checking just with #ifdef might not be enough because this symbol

?C: has been known to be an enum.

?C:.

?C:HAS_MSG_OOB:

?C: This symbol, if defined, indicates that the MSG_OOB is supported.

?C: Checking just with #ifdef might not be enough because this symbol

?C: has been known to be an enum.

?C:.

?C:HAS_MSG_PEEK:

?C: This symbol, if defined, indicates that the MSG_PEEK is supported.

?C: Checking just with #ifdef might not be enough because this symbol

?C: has been known to be an enum.

?C:.

?C:HAS_MSG_PROXY:

?C: This symbol, if defined, indicates that the MSG_PROXY is supported.

?C: Checking just with #ifdef might not be enough because this symbol

?C: has been known to be an enum.

?C:.

?C:HAS_SCM_RIGHTS:

?C: This symbol, if defined, indicates that the SCM_RIGHTS is supported.

?C: Checking just with #ifdef might not be enough

because this symbol

?C: has been known to be an enum.

?C:.

?C:HAS_SOCKADDR_SA_LEN:

?C: This symbol, if defined, indicates that the struct sockaddr

?C: structure has a member called sa_len, indicating the length of

?C: the structure.

?C:.

?C:HAS_SOCKADDR_IN6:

?C: This symbol, if defined, indicates the availability of

?C: struct sockaddr_in6;

?C:.

?C:HAS_SIN6_SCOPE_ID:

?C: This symbol, if defined, indicates that the struct sockaddr_in6

?C: structure has a member called sin6_scope_id.

?C:.

?C:HAS_IP_MREQ:

?C: This symbol, if defined, indicates the availability of

?C: struct ip_mreq;

?C:.

?C:HAS_IP_MREQ_SOURCE:

?C: This symbol, if defined, indicates the availability of

?C: struct ip_mreq_source;

?C:.

?C:HAS_IPV6_MREQ:

?C: This symbol, if defined, indicates the availability of

?C: struct ipv6_mreq;

?C:.

?C:HAS_IPV6_MREQ_SOURCE:

?C: This symbol, if defined, indicates the availability of

?C: struct ipv6_mreq_source;

?C:.

?H:#\$d_socket HAS_SOCKET /**/

?H:#\$d_sockpair HAS_SOCKETPAIR /**/

?H:#\$d_sockaddr_sa_len HAS_SOCKADDR_SA_LEN /**/

```

?H:#$d_oldsock USE_OLD_SOCKET /**/
?H:#$d_msg_ctrunc HAS_MSG_CTRUNC /**/
?H:#$d_msg_dontroute HAS_MSG_DONTRROUTE /**/
?H:#$d_msg_oob HAS_MSG_OOB /**/
?H:#$d_msg_peek HAS_MSG_PEEK /**/
?H:#$d_msg_proxy HAS_MSG_PROXY /**/
?H:#$d_scm_rights HAS_SCM_RIGHTS /**/
?H:#$d_sockaddr_in6 HAS_SOCKADDR_IN6 /**/
?H:#$d_sin6_scope_id HAS_SIN6_SCOPE_ID /**/
?H:#$d_ip_mreq HAS_IP_MREQ /**/
?H:#$d_ip_mreq_source HAS_IP_MREQ_SOURCE /**/
?H:#$d_ipv6_mreq HAS_IPV6_MREQ /**/
?H:#$d_ipv6_mreq_source HAS_IPV6_MREQ_SOURCE /**/
?H:.
?T:val
net ENUM enum
?LINT:set d_sockpair d_sockaddr_sa_len
?LINT:set d_msg_ctrunc d_msg_dontroute d_msg_oob d_msg_peek d_msg_proxy
?LINT:set d_scm_rights d_sockaddr_in6 d_sin6_scope_id d_ip_mreq
?LINT:set d_ip_mreq_source d_ipv6_mreq d_ipv6_mreq_source
: see whether socket exists
socketlib="
sockethdr="
echo " "
$echo $n "Hmm... $c" >&4
if set socket val -f d_socket; eval $csym; $val; then
    echo "Looks like you have Berkeley networking
support." >&4
    d_socket="$define"
?X: now check for advanced features
    if set setsockopt val -f; eval $csym; $val; then
d_oldsock="$undef"
    else
echo "...but it uses the old BSD 4.1c interface, rather than 4.2." >&4
d_oldsock="$define"
    fi
else
?X: HP-UX, for one, puts all the socket stuff in socklib.o. Note that if we
?X: come here on HP-UX, then we must have used nm to get symbols, or we really
?X: don't have sockets anyway...
    if $contains socklib libc.list >/dev/null 2>&1; then
echo "Looks like you have Berkeley networking support." >&4
d_socket="$define"
: we will have to assume that it supports the 4.2 BSD interface
d_oldsock="$undef"
    else
echo "You don't have Berkeley networking in libc$a..." >&4
?X: look for optional networking libraries

```

```

if test "X$d_socket" = "X$define"; then
    echo "...but you seem to believe that you have sockets." >&4
else
    for net in net socket
    do
if test -f $sysroot/usr/lib/lib$net$_a; then
?X: space between two
 '(' needed for ksh
    ( ($nm $nm_opt $sysroot/usr/lib/lib$net$_a | eval $nm_extract) || \
    $ar t $sysroot/usr/lib/lib$net$_a 2>/dev/null >> libc.list
    if $contains socket libc.list >/dev/null 2>&1; then
d_socket="$define"
socketlib="-l$net"
case "$net" in
net)
    echo "...but the Wollongong group seems to have hacked it in." >&4
    sockethdr="-I$sysroot/usr/netinclude"
    ;;
esac
    echo "Found Berkeley sockets interface in lib$net." >&4
?X: now check for advanced features
if $contains setsockopt libc.list >/dev/null 2>&1; then
    d_oldsock="$undef"
else
    echo "...using the old BSD 4.1c interface, rather than 4.2." >&4
    d_oldsock="$define"
fi
break
    fi
fi
done
if test "X$d_socket" != "X$define"; then
    echo "or anywhere else I see." >&4
    d_socket="$undef"
    d_oldsock="$undef"
fi
fi
fi
fi

@if HAS_SOCKETPAIR || d_socketpair
: see if socketpair exists
set socketpair d_socketpair
eval
$inlibc

@end

```

```

echo " "
?X: ...
echo "Checking the availability sa_len in the sock struct ..." >&4
$cat >try.c <<EOF
#include <sys/types.h>
#include <sys/socket.h>
int main() {
struct sockaddr sa;
return (sa.sa_len);
}
EOF
val="$undef"
set try; if eval $compile; then
    val="$define"
fi
set d_sockaddr_sa_len; eval $setvar
$rm_try

echo " "
?X: ...
echo "Checking the availability struct sockaddr_in6 ..." >&4
$cat >try.c <<EOF
#include <sys/types.h>
#include <sys/socket.h>
#include <netinet/in.h>
int main() {
struct sockaddr_in6 sin6;
return (sin6.sin6_family);
}
EOF
val="$undef"
set try; if eval $compile; then
    val="$define"
fi
set d_sockaddr_in6; eval $setvar
$rm_try

echo " "
?X: ...
echo "Checking the availability sin6_scope_id in struct sockaddr_in6 ..." >&4
$cat >try.c <<EOF
#include <sys/types.h>
#include <sys/socket.h>
#include <netinet/in.h>
int main() {
struct sockaddr_in6 sin6;
return (sin6.sin6_scope_id);
}

```

```

EOF
val="$undef"
set try; if eval $compile; then
    val="$define"
fi
set
d_sin6_scope_id; eval $setvar
$rm_try

echo " "
?X: ...
echo "Checking the availability struct ip_mreq ..." >&4
$cat >try.c <<EOF
#include <sys/types.h>
#include <sys/socket.h>
#include <netinet/in.h>
int main() {
    struct ip_mreq mreq;
    return (mreq.imr_multiaddr.s_addr);
}
EOF
val="$undef"
set try; if eval $compile; then
    val="$define"
fi
set d_ip_mreq; eval $setvar
$rm_try

echo " "
?X: ...
echo "Checking the availability struct ip_mreq_source ..." >&4
$cat >try.c <<EOF
#include <sys/types.h>
#include <sys/socket.h>
#include <netinet/in.h>
int main() {
    struct ip_mreq_source mreq;
    return (mreq.imr_multiaddr.s_addr);
}
EOF
val="$undef"
set try; if eval $compile; then
    val="$define"
fi
set d_ip_mreq_source; eval $setvar
$rm_try

echo " "

```

```

?X: ...
echo "Checking the availability struct ipv6_mreq ..." >&4
$cat >try.c <<EOF
#include <sys/types.h>
#include <sys/socket.h>
#include <netinet/in.h>
int main() {
struct ipv6_mreq mreq;
return (mreq.ipv6mr_interface);
}
EOF
val="$undef"
set
try; if eval $compile; then
    val="$define"
fi
set d_ipv6_mreq; eval $setvar
$rm_try

echo " "
?X: ...
echo "Checking the availability struct ipv6_mreq_source ..." >&4
$cat >try.c <<EOF
#include <sys/types.h>
#include <sys/socket.h>
#include <netinet/in.h>
int main() {
struct ipv6_mreq_source mreq;
return (mreq.imr_multiaddr.s_addr);
}
EOF
val="$undef"
set try; if eval $compile; then
    val="$define"
fi
set d_ipv6_mreq_source; eval $setvar
$rm_try

echo " "
?X: these constants are known to be troublesomely defined as enums
?X: so that ifdef will not work for detecting their presence.
echo "Checking the availability of certain socket constants..." >&4
for ENUM in MSG_CTRUNC MSG_DONTROUTE MSG_OOB MSG_PEEK MSG_PROXY SCM_RIGHTS; do
    enum=`$echo $ENUM|./tr '[A-Z]' '[a-z]'`
    $cat >try.c <<EOF
#include <sys/types.h>
#include <sys/socket.h>
int main() {

```

```

    int i = $ENUM;
}
EOF
    val="$undef"
    set try; if eval $compile; then
val="$define"
    fi
    set d_{$enum};
eval $setvar
    $rm_try
done

```

Found in path(s):

```

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/modified/d_socket.U

```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_pathconf.U 1 2006-08-24 12:32:52Z rmanfredi \$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic Licence,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic Licence; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: Original Author: Andy Dougherty <doughera@lafcol.lafayette.edu>

?RCS:

?RCS: \$Log: d_pathconf.U,v \$

?RCS: Revision 3.0.1.1 1994/10/29 16:14:54 ram

?RCS: patch36: created by ADO

?RCS:

?MAKE:d_pathconf d_fpathconf: Inlibc

?MAKE: -pick add \$@ %<

?S:d_pathconf:

?S: This variable conditionally defines the HAS_PATHCONF symbol, which

?S: indicates to the C program that the pathconf() routine is available

?S: to determine file-system related limits and options

associated

?S: with a given filename.

?S:.

?S:d_fpathconf:

?S: This variable conditionally defines the HAS_FPATHCONF symbol, which

?S: indicates to the C program that the pathconf() routine is available

?S: to determine file-system related limits and options associated

?S: with a given open file descriptor.

?S:.

?C:HAS_PATHCONF:

?C: This symbol, if defined, indicates that pathconf() is available

?C: to determine file-system related limits and options associated

?C: with a given filename.

?C:.

?C:HAS_FPATHCONF:

?C: This symbol, if defined, indicates that pathconf() is available

?C: to determine file-system related limits and options associated

?C: with a given open file descriptor.

?C:.

?H:#\$d_pathconf HAS_PATHCONF /**/

?H:#\$d_fpathconf HAS_FPATHCONF /**/

?H:.

?LINT:set d_pathconf

?LINT:set d_fpathconf

: see if pathconf exists

set pathconf d_pathconf

eval \$inlibc

@if d_fpathconf || HAS_FPATHCONF

: see if fpathconf exists

set fpathconf d_fpathconf

eval \$inlibc

@end

Found in path(s):

*

/opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/d_pathconf.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: i_limits.U 1 2006-08-24 12:32:52Z rmanfredi \$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic Licence,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic Licence; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: i_limits.U,v \$

?RCS: Revision 3.0 1993/08/18 12:08:20 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?MAKE:i_limits: Inhdr

?MAKE: -pick add \$@ %<

?S:i_limits:

?S: This variable conditionally defines the I_LIMITS symbol, and indicates

?S: whether a C program may include <limits.h> to get symbols like WORD_BIT

?S: and friends.

?S:.

?C:I_LIMITS:

?C: This symbol, if defined, indicates to the C program that it should

?C: include <limits.h> to

get definition of symbols like WORD_BIT or

?C: LONG_MAX, i.e. machine dependant limitations.

?C:.

?H:#\$i_limits I_LIMITS /**/

?H:.

?LINT:set i_limits

: see if this is a limits.h system

set limits.h i_limits

eval \$inhdr

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/i_limits.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_rdchk.U 1 2006-08-24 12:32:52Z rmanfredi \$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic Licence,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic Licence; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: d_rdchk.U,v \$

?RCS: Revision 3.0 1993/08/18 12:06:51 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?MAKE:d_rdchk: Inlibc

?MAKE: -pick add \$@ %<

?S:d_rdchk:

?S: This variable conditionally defines the HAS_RDCHK symbol, which

?S: indicates to the C program that the rdchk() routine is available

?S: to find out if there is input pending on an IO channel.

?S:.

?C:HAS_RDCHK (RDCHK):

?C: This symbol, if defined, indicates that the rdchk routine
is available

?C: to find out if there is input pending on an IO channel. Generally

?C: the routine is used only if FIONREAD and O_NDELAY aren't available.

?C:.

?H:#\$d_rdchk HAS_RDCHK /**/

?H:.

?LINT:set d_rdchk

: see if rdchk exists

set rdchk d_rdchk

eval \$inlibc

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/d_rdchk.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 2014 Jarkko Hietaniemi & H.Merijn Brand

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?MAKE:d_copysign: Inlibc

?MAKE: -pick add \$@ %<

?S:d_copysign:

?S: This variable conditionally defines the HAS_COPYSIGN symbol, which

?S: indicates to the C program that the copysign() routine is available.

?S:.

?C:HAS_COPYSIGN:

?C: This symbol, if defined, indicates that the copysign routine is

?C: available to do the copysign function.

?C:.

?H:#\$d_copysign HAS_COPYSIGN /**/

?H:.

?LINT:set d_copysign

: see if copysign exists

set copysign d_copysign

eval \$inlibc

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_copysign.U

No license file was found, but licenses were detected in source scan.

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?MAKE:d_llrint: Inlibc

?MAKE: -pick add \$@ %<

?S:d_llrint:

?S: This variable conditionally defines the HAS_LLRLINT symbol, which

?S: indicates to the C program that the llrint() routine is available

?S: to return the long long value closest to a double (according

?S: to the current rounding mode).

?S:.

?C:HAS_LLRLINT:

?C: This symbol, if defined, indicates that the llrint routine is

?C: available to return the long long value closest to a double

?C: (according to the current rounding mode).

?C:.

?H:#\$d_llrint HAS_LLRLINT /**/

?H:.

?LINT:set d_llrint

: see if llrint exists

set llrint d_llrint

eval \$inlibc

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_llrint.U

No license file was found, but licenses were detected in source scan.

?RCS: You may redistribute only under the terms of the Artistic Licence,

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/Magic_h.U

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/d_brokstat.U

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/mkdep.U

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/d_ckeypad.U

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/nlist_pfx.U

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/d_nolnbuf.U

*

/opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/d_pidcheck.U

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/d_PORTAR.U

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/d_charsprf.U

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/d_bsdjmp.U

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-

debian-perl-5.26.1/dist/U/d_dbl_dig.U

No license file was found, but licenses were detected in source scan.

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?MAKE:d_lroundl: Inlibc

?MAKE: -pick add \$@ %<

?S:d_lroundl:

?S: This variable conditionally defines the HAS_LROUNDL symbol, which

?S: indicates to the C program that the lroundl() routine is available

?S: to return the integral value nearest to x away from zero.

?S:.

?C:HAS_LROUNDL:

?C: This symbol, if defined, indicates that the lroundl routine is

?C: available to return the nearest integral value away from zero of

?C: the long double argument value.

?C:.

?H:#\$d_lroundl HAS_LROUNDL /**/

?H:.

?LINT:set d_lroundl

: see if lroundl exists

set lroundl d_lroundl

eval \$inlibc

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_lroundl.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_endpwent_r.U,v 0RCS:

?RCS: Copyright (c) 2002,2003 Jarkko Hietaniemi

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?RCS: Generated by the reentr.pl from the Perl 5.8 distribution.

?RCS:

?MAKE:d_endpwent_r endpwent_r_proto: Inlibc Protochk Hasproto i_systypes \
usethreads i_pwd extern_C

?MAKE: -pick add \$@ %<

?S:d_endpwent_r:

?S: This variable conditionally defines the HAS_ENDPWENT_R symbol,

?S: which indicates to the C program that the endpwent_r()

?S: routine is available.

?S:.

?S:endpwent_r_proto:

?S: This variable encodes the prototype of endpwent_r.

?S: It is zero if d_endpwent_r is undef, and one of the
?S: REENTRANT_PROTO_T_ABC macros of reentr.h if d_endpwent_r
?S: is defined.
?S:.
?C:HAS_ENDPWENT_R:
?C: This symbol, if defined, indicates that the endpwent_r routine
?C: is available to
endpwent re-entrantly.
?C:.
?C:ENDPWENT_R_PROTO:
?C: This symbol encodes the prototype of endpwent_r.
?C: It is zero if d_endpwent_r is undef, and one of the
?C: REENTRANT_PROTO_T_ABC macros of reentr.h if d_endpwent_r
?C: is defined.
?C:.
?H:#\$d_endpwent_r HAS_ENDPWENT_R /**/
?H:#define ENDPWENT_R_PROTO \$endpwent_r_proto /**/
?H:.
?T:try hdrs d_endpwent_r_proto
: see if endpwent_r exists
set endpwent_r d_endpwent_r
eval \$inlibc
case "\$d_endpwent_r" in
"\$define")
hdrs="\$i_systypes sys/types.h define stdio.h \$i_pwd pwd.h"
case "\$d_endpwent_r_proto:\$setthreads" in
":define") d_endpwent_r_proto=define
set d_endpwent_r_proto endpwent_r \$hdrs
eval \$hasproto ;;
*) ;;
esac
case "\$d_endpwent_r_proto" in
define)
case "\$endpwent_r_proto" in
"|0) try='int endpwent_r(FILE**);'
./protochk "\$extern_C \$try" \$hdrs && endpwent_r_proto=I_H ;;
esac
case "\$endpwent_r_proto" in
"|0) try='void endpwent_r(FILE**);'
./protochk "\$extern_C \$try" \$hdrs && endpwent_r_proto=V_H ;;
esac
case
"\$endpwent_r_proto" in
"|0) d_endpwent_r=undef
endpwent_r_proto=0
echo "Disabling endpwent_r, cannot determine prototype." >&4 ;;
*) case "\$endpwent_r_proto" in
REENTRANT_PROTO*) ;;

```

*) endpwent_r_proto="REENTRANT_PROTO_${endpwent_r_proto}";
esac
echo "Prototype: $try" ;;
esac
;;
*) case "$susetheads" in
define) echo "endpwent_r has no prototype, not using it." >&4 ;;
esac
d_endpwent_r=undef
endpwent_r_proto=0
;;
esac
;;
*) endpwent_r_proto=0
;;
esac

```

Found in path(s):

```

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/threads/d_endpwent_r.U

```

No license file was found, but licenses were detected in source scan.

```

?RCS: $Id: d_getwd.U 1 2006-08-24 12:32:52Z rmanfredi $
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: $Log: d_getwd.U,v $
?RCS: Revision 3.0 1993/08/18 12:06:18 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:d_getwd: Csym Setvar
?MAKE: -pick add $@ %<
?S:d_getwd:
?S: This variable conditionally defines HAS_GETWD if getwd() is
?S: available to get working directory. If not, you should
?S: probably use getcwd().
?S:.
?C:HAS_GETWD (GETWD):
?C: This symbol, if defined, indicates that the getwd routine is
?C: available to get working directory.
If not, you should
?C: probably use getcwd().

```

```

?C:.
?H:#$d_getwd HAS_GETWD /**/
?H:.
?LINT:set d_getwd
: see if getwd exists
echo " "
if set getwd val -f d_getwd; eval $csym; $val; then
  echo 'getwd() found.'>&4
  val="$define"
else
  echo 'getwd() not found. Assuming getcwd() exists.'>&4
  val="$undef"
fi
set d_getwd
eval $setvar

```

Found in path(s):

```

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/d_getwd.U

```

No license file was found, but licenses were detected in source scan.

```

?RCS: $Id: libyacc.U 1 2006-08-24 12:32:52Z rmanfredi $
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: $Log: libyacc.U,v $
?RCS: Revision 3.0.1.4 1997/02/28 16:09:19 ram
?RCS: patch61: replaced .a with $_a all over the place
?RCS:
?RCS: Revision 3.0.1.3 1994/05/13 15:27:12 ram
?RCS: patch27: added yacc case (ADO)
?RCS:
?RCS: Revision 3.0.1.2 1994/05/06 15:09:01 ram
?RCS: patch23: now uses full library path instead of -l notation
?RCS:
?RCS: Revision 3.0.1.1 1994/01/24 14:13:49 ram
?RCS: patch16: un-obsolete this unit for smooth yacc compilations
?RCS:
?RCS:
Revision 3.0 1993/08/18 12:09:04 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:

```

```

?MAKE:libyacc: Loc yacc libpth _a
?MAKE: -pick add $@ %<
?S:libyacc:
?S: This variable contains the argument to pass to the loader in order
?S: to get the yacc library routines. If there is no yacc or yacc
?S: library, it is null.
?S:.
?T:xxx
: see if we should include -ly
echo " "
case "$yacc" in
*byacc*)
echo "You are using byacc, so I won't look for a yacc library." >&4
libyacc="
;;
*yacc)
xxx=`./loc liby$_a x $libpth`
case "$xxx" in
x)
echo "No yacc library found." >&4
libyacc="
;;
*)
echo "yacc library found in $xxx." >&4
libyacc="$xxx"
;;
esac
;;
*bison*)
echo "You are using bison, so I won't look for a yacc library." >&4
libyacc="
;;
*)
echo "You don't seem to have yacc, so I won't look for the yacc library." >&4
libyacc="
;;
esac

```

Found in path(s):

```

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/libyacc.U

```

No license file was found, but licenses were detected in source scan.

```

?RCS: $Id: d_setegid.U 1 2006-08-24 12:32:52Z rmanfredi $

```

```

?RCS:

```

```

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

```

```

?RCS:

```

```

?RCS: You may redistribute only under the terms of the Artistic Licence,

```

?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: d_setegid.U,v \$

?RCS: Revision 3.0 1993/08/18 12:07:07 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?MAKE:d_setegid: Inlibc

?MAKE: -pick add \$@ %<

?S:d_setegid:

?S: This variable conditionally defines the HAS_SETEGID symbol, which

?S: indicates to the C program that the setegid() routine is available

?S: to change the effective gid of the current program.

?S:.

?C:HAS_SETEGID (SETEGID):

?C: This symbol, if defined, indicates that the setegid
routine is available

?C: to change the effective gid of the current program.

?C:.

?H:#\$d_setegid HAS_SETEGID /**/

?H:.

?LINT:set d_setegid

: see if setegid exists

set setegid d_setegid

eval \$inlibc

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/d_setegid.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 2015 Jarkko Hietaniemi, H.Merijn Brand

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?MAKE:longdblmanbits doublemanbits nvmantbits: Inlibc cat Compile run \

rm_try Setvar echo i_float i_sunmath usequadmath \

d_longdbl longdblkind nvsiz doublesize longdblsize

?MAKE: -pick add \$@ %<

?S:doublemanbits:

?S: This symbol, if defined, tells how many mantissa bits

?S: there are in double precision floating point format.

?S: Note that this is usually DBL_MANT_DIG minus one, since

?S: with the standard IEEE 754 formats DBL_MANT_DIG includes
 ?S: the implicit bit which doesn't really exist.
 ?S:.
 ?S:longdblmantbits:
 ?S: This symbol, if defined, tells how many mantissa bits
 ?S: there are in long double precision floating point format.
 ?S: Note that this can be LDBL_MANT_DIG minus
 one,
 ?S: since LDBL_MANT_DIG can include the IEEE 754 implicit bit.
 ?S: The common x86-style 80-bit long double does not have
 ?S: an implicit bit.
 ?S:.
 ?S:nvmantbits:
 ?S: This variable tells how many bits the mantissa of a Perl NV has,
 ?S: not including the possible implicit bit.
 ?S:.
 ?C:DOUBLEMANTBITS:
 ?C: This symbol, if defined, tells how many mantissa bits
 ?C: there are in double precision floating point format.
 ?C: Note that this is usually DBL_MANT_DIG minus one, since
 ?C: with the standard IEEE 754 formats DBL_MANT_DIG includes
 ?C: the implicit bit, which doesn't really exist.
 ?C:.
 ?C:LONGDBLMANTBITS:
 ?C: This symbol, if defined, tells how many mantissa bits
 ?C: there are in long double precision floating point format.
 ?C: Note that this can be LDBL_MANT_DIG minus one,
 ?C: since LDBL_MANT_DIG can include the IEEE 754 implicit bit.
 ?C: The common x86-style 80-bit long double does not have
 ?C: an implicit bit.
 ?C:.
 ?C:NVMANTBITS:
 ?C: This symbol, if defined, tells how many mantissa
 bits
 ?C: (not including implicit bit) there are in a Perl NV.
 ?C: This depends on which floating point type was chosen.
 ?C:.
 ?H:#define DOUBLEMANTBITS \$doublemantbits
 ?H:#define LONGDBLMANTBITS \$longdblmantbits
 ?H:#define NVMANTBITS \$nvmantbits
 ?H:.
 ?F:!try
 : Check the length of the double mantissa
 \$echo "Checking how many mantissa bits your doubles have..." >&4
 \$cat >try.c <<EOP
 #i_float I_FLOAT
 #i_sunmath I_SUNMATH
 #ifdef I_FLOAT

```

#include <float.h>
#endif
#ifdef I_SUNMATH
#include <sunmath.h>
#endif
#ifdef DBL_MANT_DIG
#define BITS (DBL_MANT_DIG - 1) /* the implicit bit does not count */
#endif
#include <stdio.h>
int main(int argc, char *argv[]) {
#ifdef BITS
printf("%d\n", BITS);
#endif
return 0;
}
EOP
set try
if eval $compile; then
doublemantbits=`$run ./try`
else
doublemantbits="$undef"
fi
$rm_try

: Check the length of the longdouble mantissa
$echo "Checking how many mantissa bits your long doubles have..." >&4
$cat >try.c <<EOP
#$i_float I_FLOAT
#$i_sunmath
I_SUNMATH
#ifdef I_FLOAT
#include <float.h>
#endif
#ifdef I_SUNMATH
#include <sunmath.h>
#endif
#$d_longdbl HAS_LONG_DOUBLE
#if defined(HAS_LONG_DOUBLE) && defined(LDBL_MANT_DIG)
# if ($longdblkind == 3) || ($longdblkind == 4) /* 80-bit extended precision */
/* This format has no implicit bit. Beware, however, that for
* this format the bare LDBL_MANT_DIG is misleading for inf/nan:
* the top three bits are used for inf (100) / qnan (11x) / snan (101),
* and the top bit must have been one since 387, zero is plain invalid.
* For normal fp values, the LDBL_MANT_DIG is fine, though. */
# define BITS LDBL_MANT_DIG
# elif ($longdblkind == 5 || $longdblkind == 6 || $longdblkind == 7 || $longdblkind == 8) /* double double */
/* LDBL_MANT_DIG of 106 (twice 53) would be logical, but for some
* reason e.g. Irix thinks 107. But in any case, we want only

```

```

* the number of real bits, the implicit bits are of no interest. */
# define BITS 2 * (DBL_MANT_DIG - 1)
# else
# define BITS (LDBL_MANT_DIG
- 1) /* the implicit bit does not count */
# endif
#endif
#include <stdio.h>
int main(int argc, char *argv[]) {
#ifdef BITS
printf("%d\n", BITS);
#endif
return 0;
}
EOP
set try
if eval $compile; then
longdblmanbits=`$run ./try`
else
longdblmanbits="$undef"
fi
$rm_try

```

: Check the length of the NV mantissa

```
$echo "Checking how many mantissa bits your NVs have..." >&4
```

```
if test "X$susequadmath" = "X$define"; then
```

```
nvmanbits=112 # 128-1-15
```

```
else
```

```
if test "X$nvsize" = "X$doublesize"; then
```

```
nvmanbits="$doublemanbits"
```

```
else
```

```
if test "X$nvsize" = "X$longdblsize"; then
```

```
nvmanbits="$longdblmanbits"
```

```
else
```

```
nvmanbits="$undef"
```

```
fi
```

```
fi
```

```
fi
```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/perl/mantbits.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: d_getnbyad.U,v $
```

```
?RCS:
```

```
?RCS: Copyright (c) 1998 Andy Dougherty
```

```
?RCS:
```

?RCS: You may distribute under the terms of either the GNU General Public
 ?RCS: License or the Artistic License, as specified in the README file.
 ?RCS:
 ?MAKE:d_getnbyaddr: Inlibc
 ?MAKE:-pick add \$@ %<
 ?S:d_getnbyaddr:
 ?S: This variable conditionally defines the HAS_GETNETBYADDR symbol, which
 ?S: indicates to the C program that the getnetbyaddr() routine is available
 ?S: to look up networks by their IP addresses.
 ?S:.
 ?C:HAS_GETNETBYADDR:
 ?C: This symbol, if defined, indicates that the getnetbyaddr() routine is
 ?C: available to look up networks by their IP addresses.
 ?C:.
 ?H:#\$d_getnbyaddr HAS_GETNETBYADDR /**/
 ?H:.
 ?LINT:set d_getnbyaddr
 : see if getnetbyaddr exists
 set getnetbyaddr d_getnbyaddr
 eval \$inlibc

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/modified/d_getnbyad.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$
 ?RCS:
 ?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
 ?RCS:
 ?RCS: You may redistribute only under the terms of the Artistic License,
 ?RCS: as specified in the README file that comes with the distribution.
 ?RCS: You may reuse parts of this distribution only within the terms of
 ?RCS: that same Artistic License; a copy of which may be found at the root
 ?RCS: of the source tree for dist 4.0.
 ?RCS:
 ?RCS: Original Author: Andy Dougherty <doughera@lafcol.lafayette.edu>
 ?RCS:
 ?RCS: \$Log: d_closedir.U,v \$
 ?RCS: Revision 3.0.1.3 1997/02/28 15:31:26 ram
 ?RCS: patch61: added ?F: metalint hint
 ?RCS:
 ?RCS: Revision 3.0.1.2 1994/10/29 16:11:18 ram
 ?RCS: patch36: added 'ldflags' to the test compile line (ADO)
 ?RCS:
 ?RCS: Revision 3.0.1.1 1994/08/29 16:07:21 ram
 ?RCS: patch32: created by ADO
 ?RCS:

```

?MAKE:d_closedir d_void_closedir: Inlibc i_dirent i_sysdir i_sysndir \
cc ccflags ldflags libs Setvar rm
?MAKE: -pick
add $@ %<
?S:d_closedir:
?S: This variable conditionally defines HAS_CLOSEDIR if closedir() is
?S: available.
?S:.
?C:HAS_CLOSEDIR:
?C: This symbol, if defined, indicates that the closedir() routine is
?C: available.
?C:.
?H:#$d_closedir HAS_CLOSEDIR /**/
?H:.
?S:d_void_closedir:
?S: This variable conditionally defines VOID_CLOSEDIR if closedir()
?S: does not return a value.
?S:.
?C:VOID_CLOSEDIR:
?C: This symbol, if defined, indicates that the closedir() routine
?C: does not return a value.
?C:.
?H:#$d_void_closedir VOID_CLOSEDIR /**/
?H:.
?F:!closedir
?LINT:set d_closedir d_void_closedir
: see if closedir exists
set closedir d_closedir
eval $inlibc

@if VOID_CLOSEDIR || d_void_closedir
?X: The following contortions are designed so we can call closedir()
?X: and check whether it returns a value. The contortions are designed
?X: to portably pick up the correct directory header, for those
?X: systems that support various mutually incompatible directory functions.
?X: This
is from perl5's perl.h
case "$d_closedir" in
"$define")
echo " "
echo "Checking whether closedir() returns a status..." >&4
cat > closedir.c <<EOM
#$i_dirent I_DIRENT /**/
#$i_sysdir I_SYS_DIR /**/
#$i_sysndir I_SYS_NDIR /**/

#if defined(I_DIRENT)
#include <dirent.h>

```

```

#if defined(NeXT) && defined(I_SYS_DIR) /* NeXT needs dirent + sys/dir.h */
#include <sys/dir.h>
#endif
#else
#ifdef I_SYS_NDIR
#include <sys/ndir.h>
#else
#ifdef I_SYS_DIR
#ifdef hp9000s500
#include <ndir.h> /* may be wrong in the future */
#else
#include <sys/dir.h>
#endif
#endif
#endif
#endif
#endif
int main() { return closedir(opendir(".")); }
EOM
if $cc $ccflags $ldflags -o closedir closedir.c $libs > /dev/null 2>&1; then
if ./closedir > /dev/null 2>&1 ; then
echo "Yes, it does."
val="$undef"
else
echo "No, it doesn't."
val="$define"
fi
else
echo "(I can't seem to compile the test program--assuming it doesn't)"
val="$define"
fi
;;
*)
val="$undef";
;;
esac
set d_void_closedir
eval $setvar
$rm
-f closedir*
@end

```

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/d_closedir.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 2000 Jarkko Hietaniemi
?RCS:
?RCS: You may distribute under the terms of either the GNU General Public
?RCS: License or the Artistic License, as specified in the README file.
?RCS:
?MAKE:d_socks5_init: Inlibc
?MAKE: -pick add \$@ %<
?S:d_socks5_init:
?S: This variable conditionally defines the HAS_SOCKS5_INIT symbol, which
?S: indicates to the C program that the socks5_init() routine is available.
?S:.
?C:HAS_SOCKS5_INIT:
?C: This symbol, if defined, indicates that the socks5_init routine is
?C: available to initialize SOCKS 5.
?C:.
?H:#\$d_socks5_init HAS_SOCKS5_INIT /**/
?H:.
?LINT:set d_socks5_init
: see if socks5_init exists
set socks5_init d_socks5_init
eval \$inlibc

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_socks5_init.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_setlocale_r.U,v 0RCS:
?RCS: Copyright (c) 2002,2003 Jarkko Hietaniemi
?RCS:
?RCS: You may distribute under the terms of either the GNU General Public
?RCS: License or the Artistic License, as specified in the README file.
?RCS:
?RCS: Generated by the reentr.pl from the Perl 5.8 distribution.
?RCS:
?MAKE:d_setlocale_r setlocale_r_proto: Inlibc Protochk Hasproto i_systypes \
usethreads i_locale extern_C
?MAKE: -pick add \$@ %<
?S:d_setlocale_r:
?S: This variable conditionally defines the HAS_SETLOCALE_R symbol,
?S: which indicates to the C program that the setlocale_r()
?S: routine is available.
?S:.
?S:setlocale_r_proto:
?S: This variable encodes the prototype of setlocale_r.
?S: It is zero if d_setlocale_r is undef, and one of the
?S: REENTRANT_PROTO_T_ABC macros of reentr.h if d_setlocale_r
?S: is defined.

```

?S:.
?C:HAS_SETLOCALE_R:
?C: This symbol, if defined, indicates that the setlocale_r routine
?C: is
    available to setlocale re-entrantly.
?C:.
?C:SETLOCALE_R_PROTO:
?C: This symbol encodes the prototype of setlocale_r.
?C: It is zero if d_setlocale_r is undef, and one of the
?C: REENTRANT_PROTO_T_ABC macros of reentr.h if d_setlocale_r
?C: is defined.
?C:.
?H:#$d_setlocale_r HAS_SETLOCALE_R  /**/
?H:#define SETLOCALE_R_PROTO $setlocale_r_proto  /**/
?H:.
?T:try hdrs d_setlocale_r_proto
: see if setlocale_r exists
set setlocale_r d_setlocale_r
eval $inlibc
case "$d_setlocale_r" in
"$define")
hdrs="$i_systypes sys/types.h define stdio.h $i_locale locale.h"
case "$d_setlocale_r_proto:$usethreads" in
":define") d_setlocale_r_proto=define
set d_setlocale_r_proto setlocale_r $hdrs
eval $hasproto ;;
*) ;;
esac
case "$d_setlocale_r_proto" in
define)
case "$setlocale_r_proto" in
"|0) try='int setlocale_r(int, const char*, char*, int);'
./prochck "$extern_C $try" $hdrs && setlocale_r_proto=I_ICBI ;;
esac
case "$setlocale_r_proto" in
"|0) d_setlocale_r=undef
setlocale_r_proto=0
echo
"Disabling setlocale_r, cannot determine prototype." >&4 ;;
* ) case "$setlocale_r_proto" in
REENTRANT_PROTO*) ;;
*) setlocale_r_proto="REENTRANT_PROTO_$setlocale_r_proto" ;;
esac
echo "Prototype: $try" ;;
esac
;;
*) case "$usethreads" in
define) echo "setlocale_r has no prototype, not using it." >&4 ;;

```

```
esac
d_setlocale_r=undef
setlocale_r_proto=0
;;
esac
;;
*) setlocale_r_proto=0
;;
esac
```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/threads/d_setlocale_r.U
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 2009 H.Merijn Brand

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?MAKE:d_getaddrinfo: Inlibc

?MAKE: -pick add \$@ %<

?S:d_getaddrinfo:

?S: This variable conditionally defines the HAS_GETADDRINFO symbol,

?S: which indicates to the C program that the getaddrinfo() function

?S: is available.

?S:.

?C:HAS_GETADDRINFO:

?C: This symbol, if defined, indicates that the getaddrinfo() function

?C: is available for use.

?C:.

?H:#\$d_getaddrinfo HAS_GETADDRINFO /**/

?H:.

?LINT:set d_getaddrinfo

: see if getaddrinfo exists

set getaddrinfo d_getaddrinfo

eval \$inlibc

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/perl/d_getaddrinfo.U
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1999, Jarkko Hietaniemi

?RCS:
?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 3.0.
?RCS:
?MAKE:d_clock_getres: Inlibc
?MAKE: -pick add \$@ %<
?S:d_clock_getres:
?S: This variable conditionally defines HAS_CLOCK_GETRES
?S: if clock_getres() is available to get the resolution of a POSIX clock.
?S:.
?C:HAS_CLOCK_GETRES:
?C: This symbol, if defined, indicates that the clock_getres
?C: system call is available to get the resolution of a POSIX clock.
?C:.
?H:#\$d_clock_getres HAS_CLOCK_GETRES /**/
?H:.
?LINT:set d_clock_getres
: see if clock_getres exists
set clock_getres d_clock_getres
eval \$inlibc

Found in path(s):

*

/opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_clock_getres.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_memcmp.U 1 2006-08-24 12:32:52Z rmanfredi \$
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: \$Log: d_memcmp.U,v \$
?RCS: Revision 3.0.1.1 1993/09/13 16:02:35 ram
?RCS: patch10: removed text recommending bcmp over memcmp (WAD)
?RCS:
?RCS: Revision 3.0 1993/08/18 12:06:33 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:d_memcmp: Inlibc

?MAKE: -pick add \$@ %<
?S:d_memcmp:
?S: This variable conditionally defines the HAS_MEMCMP symbol, which
?S: indicates to the C program that the memcmp() routine is available
?S: to compare blocks of
memory.
?S:.
?C:HAS_MEMCMP (MEMCMP):
?C: This symbol, if defined, indicates that the memcmp routine is available
?C: to compare blocks of memory.
?C:.
?H:#\$d_memcmp HAS_MEMCMP /**/
?H:.
?LINT:set d_memcmp
: see if memcmp exists
set memcmp d_memcmp
eval \$inlibc

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/d_memcmp.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_normsig.U 1 2006-08-24 12:32:52Z rmanfredi \$
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: \$Log: d_normsig.U,v \$
?RCS: Revision 3.0.1.2 1997/02/28 15:37:03 ram
?RCS: patch61: replaced .a with \$_a all over the place
?RCS:
?RCS: Revision 3.0.1.1 1994/10/29 16:14:48 ram
?RCS: patch36: call ./bsd explicitly instead of relying on PATH
?RCS:
?RCS: Revision 3.0 1993/08/18 12:06:44 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:d_normsig joblib: test Setvar Guess _a
?MAKE: -pick add \$@ %<
?S:d_normsig:
?S: This variable conditionally

defines the NORMSIG symbol, which

?S: indicates to the C program that the normal signal handling routines

?S: should be used, as opposed to the ones in 4.1bsd (sigset, etc.).

?S:.

?S:jobslib:

?S: This variable holds the argument to be passed to the loader to include

?S: the strange signal handling routines from 4.1bsd. On systems that

?S: have NORMSIG defined this variable is null.

?S:.

?C:NORMSIG:

?C: This symbol, if defined, indicates that normal signal handling routines

?C: should be used, as opposed to the ones in 4.1bsd (sigset, etc.).

?C:.

?H:#\$d_normsig NORMSIG /**/

?H:.

?LINT:set d_normsig

: see if we need -ljobs and if we have sigset, etc.

echo " "

if \$test -r /usr/lib/libjobs\$_a || \$test -r /usr/local/lib/libjobs\$_a ; then

echo "Jobs library found." >&4

val="\$undef"

jobslib='-ljobs'

else

if ./bsd; then

echo "No jobs library found. (I suppose this is at least 4.2...)" >&4

else

echo "No jobs library found. (That's okay, we all have our faults.)" >&4

fi

val="\$define"

jobslib=""

fi

set

d_normsig

eval \$setvar

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/d_normsig.U

No license file was found, but licenses were detected in source scan.

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?MAKE:d_remainder: Inlibc

?MAKE: -pick add \$@ %<

?S:d_remainder:

?S: This variable conditionally defines the HAS_REMAINDER symbol, which

?S: indicates to the C program that the remainder() routine is available.

?S:
?C:HAS_REMAINDER:
?C: This symbol, if defined, indicates that the remainder routine is
?C: available to return the floating-point remainder.
?C:
?H:#\$d_remainder HAS_REMAINDER /**/
?H:
?LINT:set d_remainder
: see if remainder exists
set remainder d_remainder
eval \$inlibc

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_remainder.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_fcntl.U 1 2006-08-24 12:32:52Z rmanfredi \$
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: \$Log: d_fcntl.U,v \$
?RCS: Revision 3.0 1993/08/18 12:06:01 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:d_fcntl: Inlibc
?MAKE:-pick add \$@ %<
?S:d_fcntl:
?S: This variable conditionally defines the HAS_FCNTL symbol, and indicates
?S: whether the fcntl() function exists
?S:
?C:HAS_FCNTL:
?C: This symbol, if defined, indicates to the C program that
?C: the fcntl() function exists.
?C:
?H:#\$d_fcntl HAS_FCNTL /**/
?H:
?LINT:set d_fcntl
:
: see if this is an fcntl system
set fcntl d_fcntl
eval \$inlibc

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/d_fcntl.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_attribut.U 1 2006-08-24 12:32:52Z rmanfredi \$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 3.0.

?RCS:

?RCS: Original Author: Andy Dougherty <doughera@lafcol.lafayette.edu>

?RCS:

?RCS: \$Log: d_attribut.U,v \$

?RCS: Revision 3.0.1.3 1995/01/30 14:33:45 ram

?RCS: patch49: test C program now includes <stdio.h> (WED)

?RCS:

?RCS: Revision 3.0.1.2 1995/01/11 15:25:47 ram

?RCS: patch45: fixed typo in the d_attribut variable (ADO)

?RCS:

?RCS: Revision 3.0.1.1 1994/10/29 16:08:55 ram

?RCS: patch36: created by ADO

?RCS:

?MAKE:d_attribute_deprecated d_attribute_format

d_attribute_malloc \

d_attribute_nonnull d_attribute_noreturn d_attribute_pure \

d_attribute_unused d_attribute_warn_unused_result \

d_printf_format_null: \

Myread Oldconfig cat cc cflags rm Setvar contains i_stdlib run

?MAKE: -pick add \$@ %<

?S:d_attribute_format:

?S: This variable conditionally defines HASATTRIBUTE_FORMAT, which

?S: indicates the C compiler can check for printf-like formats.

?S:.

?S:d_attribute_deprecated:

?S: This variable conditionally defines HASATTRIBUTE_DEPRECATED, which

?S: indicates that GCC can handle the attribute for marking deprecated

?S: APIs

?S:.

?S:d_printf_format_null:

?S: This variable conditionally defines PRINTF_FORMAT_NULL_OK, which

?S: indicates the C compiler allows printf-like formats to be null.

?S:.

?S:d_attribute_malloc:

?S: This variable conditionally defines HASATTRIBUTE_MALLOC, which

?S: indicates the C compiler can understand functions as having

?S: malloc-like semantics.

?S:.

?S:d_attribute_nonnull:

?S: This variable conditionally

defines HASATTRIBUTE_NONNULL, which

?S: indicates that the C compiler can know that certain arguments

?S: must not be NULL, and will check accordingly at compile time.

?S:.

?S:d_attribute_noreturn:

?S: This variable conditionally defines HASATTRIBUTE_NORETURN, which

?S: indicates that the C compiler can know that certain functions

?S: are guaranteed never to return.

?S:.

?S:d_attribute_pure:

?S: This variable conditionally defines HASATTRIBUTE_PURE, which

?S: indicates that the C compiler can know that certain functions

?S: are "pure" functions, meaning that they have no side effects, and

?S: only rely on function input and/or global data for their results.

?S:.

?S:d_attribute_unused:

?S: This variable conditionally defines HASATTRIBUTE_UNUSED, which

?S: indicates that the C compiler can know that certain variables

?S: and arguments may not always be used, and to not throw warnings

?S: if they don't get used.

?S:.

?S:d_attribute_warn_unused_result:

?S: This variable conditionally

defines

?S: HASATTRIBUTE_WARN_UNUSED_RESULT, which indicates that the C

?S: compiler can know that certain functions have a return values

?S: that must not be ignored, such as malloc() or open().

?S:.

?C:HASATTRIBUTE_FORMAT ~ %< (GNU_ATTRIBUTE_CHECK):

?C: Can we handle GCC attribute for checking printf-style formats

?C:.

?C:PRINTF_FORMAT_NULL_OK:

?C: Allows __printf__ format to be null when checking printf-style

?C:.

?C:HASATTRIBUTE_MALLOC:

?C: Can we handle GCC attribute for malloc-style functions.

?C:.

?C:HASATTRIBUTE_NONNULL:

?C: Can we handle GCC attribute for nonnull function parms.

?C:.

?C:HASATTRIBUTE_NORETURN:

```

?C: Can we handle GCC attribute for functions that do not return
?C:.
?C:HASATTRIBUTE_PURE:
?C: Can we handle GCC attribute for pure functions
?C:.
?C:HASATTRIBUTE_UNUSED:
?C: Can we handle GCC attribute for unused variables and arguments
?C:.
?C:HASATTRIBUTE_DEPRECATED:
?C: Can we handle GCC attribute for marking deprecated APIs
?C:.
?C:HASATTRIBUTE_WARN_UNUSED_RESULT
~ %< (HASATTRIBUTE):
?C: Can we handle GCC attribute for warning on unused results
?C:.
?H:?%<:#$d_attribute_deprecated HASATTRIBUTE_DEPRECATED /**/
?H:?%<:#$d_attribute_format HASATTRIBUTE_FORMAT /**/
?H:?%<:#$d_printf_format_null PRINTF_FORMAT_NULL_OK /**/
?H:?%<:#$d_attribute_noreturn HASATTRIBUTE_NORETURN /**/
?H:?%<:#$d_attribute_malloc HASATTRIBUTE_MALLOC /**/
?H:?%<:#$d_attribute_nonnull HASATTRIBUTE_NONNULL /**/
?H:?%<:#$d_attribute_pure HASATTRIBUTE_PURE /**/
?H:?%<:#$d_attribute_unused HASATTRIBUTE_UNUSED /**/
?H:?%<:#$d_attribute_warn_unused_result HASATTRIBUTE_WARN_UNUSED_RESULT /**/
?H:.
?F:!attrib !attrib.out !attrib.c
?LINT:set d_attribute_deprecated
?LINT:set d_attribute_format
?LINT:set d_printf_format_null
?LINT:set d_attribute_malloc
?LINT:set d_attribute_nonnull
?LINT:set d_attribute_noreturn
?LINT:set d_attribute_pure
?LINT:set d_attribute_unused
?LINT:set d_attribute_warn_unused_result
: Look for GCC-style attribute format
case "$d_attribute_format" in
")
echo
" "
echo "Checking whether your compiler can handle __attribute__((format)) ..." >&4
$cat >attrib.c <<'EOCP'
#include <stdio.h>
void my_special_printf(char* pat,...) __attribute__((__format__(__printf__,1,2)));
EOCP
if $cc $ccflags -c attrib.c >attrib.out 2>&1 ; then
if $contains 'warning' attrib.out >/dev/null 2>&1; then
echo "Your C compiler doesn't support __attribute__((format))."

```

```

    val="$undef"
else
    echo "Your C compiler supports __attribute__((format))."
    val="$define"
fi
else
    echo "Your C compiler doesn't seem to understand __attribute__ at all."
    val="$undef"
fi
;;
*) val="$d_attribute_format" ;;
esac
set d_attribute_format
eval $setvar
$rm -f attrib*

: Look for GCC-style attribute format with null format allowed
case "$d_printf_format_null" in
") case "$d_attribute_format" in
    $define)
    echo " "
    echo "Checking whether your compiler allows __printf__ format to be null ..." >&4
$cat >attrib.c <<EOCP
#include <stdio.h>
#ifdef I_STDLIB
#include
<stdlib.h>
#endif
int null_printf (char* pat,...) __attribute__((__format__(__printf__,1,2)));
int null_printf (char* pat,...) { return (int)pat; }
int main () { exit(null_printf(NULL)); }
EOCP
if $cc $ccflags -o attrib attrib.c >attrib.out 2>&1 ; then
    : run the executable in case it produces a run-time warning
    if $run ./attrib >>attrib.out 2>&1; then
if $contains 'warning' attrib.out >/dev/null 2>&1; then
    echo "Your C compiler doesn't allow __printf__ format to be null."
    val="$undef"
else
    echo "Your C compiler allows __printf__ format to be null."
    val="$define"
fi
else
    echo "Your C compiler executable failed with __printf__ format null."
    val="$undef"
fi
else

```

```

echo "Your C compiler fails with __printf__ format null."
val="$undef"
fi
;;
*) val="$undef" ;;
esac
;;
*) val="$d_printf_format_null" ;;
esac
set d_printf_format_null
eval $setvar
$rm -f attrib*

: Look for GCC-style attribute malloc
case "$d_attribute_malloc"
in
")
echo " "
echo "Checking whether your compiler can handle __attribute__((malloc)) ..." >&4
$cat >attrib.c <<'EOCP'
#include <stdio.h>
char *go_get_some_memory( int how_many_bytes ) __attribute__((malloc));
EOCP
if $cc $ccflags -c attrib.c >attrib.out 2>&1 ; then
if $contains 'warning' attrib.out >/dev/null 2>&1; then
echo "Your C compiler doesn't support __attribute__((malloc))."
val="$undef"
else
echo "Your C compiler supports __attribute__((malloc))."
val="$define"
fi
else
echo "Your C compiler doesn't seem to understand __attribute__ at all."
val="$undef"
fi
;;
*) val="$d_attribute_malloc" ;;
esac
set d_attribute_malloc
eval $setvar
$rm -f attrib*

: Look for GCC-style attribute nonnull
case "$d_attribute_nonnull" in
")
echo " "
echo "Checking whether your compiler can handle __attribute__((nonnull(1))) ..." >&4
$cat >attrib.c <<'EOCP'

```

```

#include <stdio.h>
void do_something (char *some_pointer,...) __attribute__((nonnull(1)));
EOCP
if $cc $ccflags -c attrib.c
>attrib.out 2>&1 ; then
if $contains 'warning' attrib.out >/dev/null 2>&1; then
echo "Your C compiler doesn't support __attribute__((nonnull))."
val="$undef"
else
echo "Your C compiler supports __attribute__((nonnull))."
val="$define"
fi
else
echo "Your C compiler doesn't seem to understand __attribute__ at all."
val="$undef"
fi
;;
*) val="$d_attribute_nonnull" ;;
esac
set d_attribute_nonnull
eval $setvar
$rm -f attrib*

: Look for GCC-style attribute noreturn
case "$d_attribute_noreturn" in
")
echo " "
echo "Checking whether your compiler can handle __attribute__((noreturn)) ..." >&4
$cat >attrib.c <<'EOCP'
#include <stdio.h>
void fall_over_dead( void ) __attribute__((noreturn));
EOCP
if $cc $ccflags -c attrib.c >attrib.out 2>&1 ; then
if $contains 'warning' attrib.out >/dev/null 2>&1; then
echo "Your C compiler doesn't support __attribute__((noreturn))."
val="$undef"
else
echo "Your C compiler supports __attribute__((noreturn))."
val="$define"
fi
else
echo
"Your C compiler doesn't seem to understand __attribute__ at all."
val="$undef"
fi
;;
*) val="$d_attribute_noreturn" ;;
esac

```

```

set d_attribute_noreturn
eval $setvar
$rm -f attrib*

: Look for GCC-style attribute pure
case "$d_attribute_pure" in
")
echo " "
echo "Checking whether your compiler can handle __attribute__((pure)) ..." >&4
$cat >attrib.c <<'EOCP'
#include <stdio.h>
int square( int n ) __attribute__((pure));
EOCP
if $cc $ccflags -c attrib.c >attrib.out 2>&1 ; then
if $contains 'warning' attrib.out >/dev/null 2>&1; then
echo "Your C compiler doesn't support __attribute__((pure))."
val="$undef"
else
echo "Your C compiler supports __attribute__((pure))."
val="$define"
fi
else
echo "Your C compiler doesn't seem to understand __attribute__ at all."
val="$undef"
fi
;;
*) val="$d_attribute_pure" ;;
esac
set d_attribute_pure
eval $setvar
$rm -f attrib*

```

```

: Look for GCC-style attribute unused
case "$d_attribute_unused" in
")
echo " "
echo "Checking whether your compiler
can handle __attribute__((unused)) ..." >&4
$cat >attrib.c <<'EOCP'
#include <stdio.h>
int do_something( int dummy __attribute__((unused)), int n );
EOCP
if $cc $ccflags -c attrib.c >attrib.out 2>&1 ; then
if $contains 'warning' attrib.out >/dev/null 2>&1; then
echo "Your C compiler doesn't support __attribute__((unused))."
val="$undef"
else
echo "Your C compiler supports __attribute__((unused))."

```

```

    val="$define"
fi
else
echo "Your C compiler doesn't seem to understand __attribute__ at all."
val="$undef"
fi
;;
*) val="$d_attribute_unused" ;;
esac
set d_attribute_unused
eval $setvar
$rm -f attrib*

: Look for GCC-style attribute deprecated
case "$d_attribute_deprecated" in
")
echo " "
echo "Checking whether your compiler can handle __attribute__((deprecated)) ..." >&4
$cat >attrib.c <<'EOCP'
#include <stdio.h>
int I_am_deprecated(void) __attribute__((deprecated));
EOCP
if $cc $ccflags -c attrib.c >attrib.out 2>&1 ; then
if $contains 'warning' attrib.out >/dev/null 2>&1;
then
echo "Your C compiler doesn't support __attribute__((deprecated))."
val="$undef"
else
echo "Your C compiler supports __attribute__((deprecated))."
val="$define"
fi
else
echo "Your C compiler doesn't seem to understand __attribute__ at all."
val="$undef"
fi
;;
*) val="$d_attribute_deprecated" ;;
esac
set d_attribute_deprecated
eval $setvar
$rm -f attrib*

: Look for GCC-style attribute warn_unused_result
case "$d_attribute_warn_unused_result" in
")
echo " "
echo "Checking whether your compiler can handle __attribute__((warn_unused_result)) ..." >&4
$cat >attrib.c <<'EOCP'

```

```

#include <stdio.h>
int I_will_not_be_ignored(void) __attribute__((warn_unused_result));
EOCP
if $cc $ccflags -c attrib.c >attrib.out 2>&1 ; then
if $contains 'warning' attrib.out >/dev/null 2>&1; then
echo "Your C compiler doesn't support __attribute__((warn_unused_result))."
val="$undef"
else
echo "Your C compiler supports __attribute__((warn_unused_result))."
val="$define"
fi
else
echo
"Your C compiler doesn't seem to understand __attribute__ at all."
val="$undef"
fi
;;
*) val="$d_attribute_warn_unused_result" ;;
esac
set d_attribute_warn_unused_result
eval $setvar
$rm -f attrib*

```

Found in path(s):

```

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/modified/d_attribut.U

```

No license file was found, but licenses were detected in source scan.

```

?RCS: $Id: d_strchr.U 1 2006-08-24 12:32:52Z rmanfredi $
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: $Log: d_strchr.U,v $
?RCS: Revision 3.0.1.2 1993/10/16 13:49:20 ram
?RCS: patch12: added support for HAS_INDEX
?RCS: patch12: added magic for index() and rindex()
?RCS:
?RCS: Revision 3.0.1.1 1993/09/13 16:05:26 ram
?RCS: patch10: now only defines HAS_STRCHR, no macro remap of index (WAD)
?RCS:
?RCS: Revision 3.0 1993/08/18 12:07:32 ram
?RCS: Baseline for dist 3.0 netwide release.

```

```

?RCS:
?MAKE:d_strchr d_index: contains strings Setvar Myread Oldconfig
  Csym
?MAKE: -pick add $@ %<
?S:d_strchr:
?S: This variable conditionally defines HAS_STRCHR if strchr() and
?S: strrchr() are available for string searching.
?S:.
?S:d_index:
?S: This variable conditionally defines HAS_INDEX if index() and
?S: rindex() are available for string searching.
?S:.
?C:HAS_STRCHR:
?C: This symbol is defined to indicate that the strchr()/strrchr()
?C: functions are available for string searching. If not, try the
?C: index()/rindex() pair.
?C:.
?C:HAS_INDEX:
?C: This symbol is defined to indicate that the index()/rindex()
?C: functions are available for string searching.
?C:.
?H:#$d_strchr HAS_STRCHR /**/
?H:#$d_index HAS_INDEX /**/
?H:.
?M:index: HAS_INDEX
?M:#ifndef HAS_INDEX
?M:#ifndef index
?M:#define index strchr
?M:#endif
?M:#endif
?M:.
?M:rindex: HAS_INDEX
?M:#ifndef HAS_INDEX
?M:#ifndef rindex
?M:#define rindex strrchr
?M:#endif
?M:#endif
?M:.
?T:vali
?LINT:set d_strchr d_index
: index or strchr
echo " "
if set index val -f; eval $csym; $val; then
  if
  set strchr val -f d_strchr; eval $csym; $val; then
    if $contains strchr "$strings" >/dev/null 2>&1 ; then
?X: has index, strchr, and strchr in string header
  val="$define"

```

```

    vali="$undef"
    echo "strchr() found." >&4
else
?X: has index, strchr, and no strchr in string header
    val="$undef"
    vali="$define"
    echo "index() found." >&4
fi
else
?X: has only index, no strchr, string header is a moot point
    val="$undef"
    vali="$define"
    echo "index() found." >&4
fi
else
if set strchr val -f d_strchr; eval $csym; $val; then
    val="$define"
    vali="$undef"
    echo "strchr() found." >&4
else
    echo "No index() or strchr() found!" >&4
    val="$undef"
    vali="$undef"
fi
fi
set d_strchr; eval $setvar
val="$vali"
set d_index; eval $setvar

```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/d_strchr.U
```

No license file was found, but licenses were detected in source scan.

```

?RCS: $Id: d_psignal.U 1 2006-08-24 12:32:52Z rmanfredi $
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: $Log: d_psignal.U,v $
?RCS: Revision 3.0 1993/08/18 12:06:49 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:

```

?MAKE:d_psignal: Inlibc
?MAKE: -pick add \$@ %<
?S:d_psignal:
?S: This variable conditionally defines the HAS_PPSIGNAL symbol, which
?S: indicates that the ppsignal() routine exists. The ppsignal() routine
?S: prints a description of a signal on the standard error output.
?S:.
?C:HAS_PPSIGNAL (PPSIGNAL):
?C: This symbol, if defined, indicates
that the ppsignal() routine exists.
?C:.
?H:#\$d_psignal HAS_PPSIGNAL /**/
?H:.
?LINT:set d_psignal
: see if ppsignal exists
set ppsignal d_psignal
eval \$inlibc

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/d_psignal.U

No license file was found, but licenses were detected in source scan.

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?MAKE:d_mmemm: Inlibc

?MAKE: -pick add \$@ %<

?S:d_mmemm:

?S: This variable conditionally defines the HAS_MEMMEM symbol, which

?S: indicates to the C program that the memmem() routine is available

?S: to return a pointer to the start of the first occurrence of a

?S: substring in a memory area (or NULL if not found).

?S:.

?C:HAS_MEMMEM:

?C: This symbol, if defined, indicates that the memmem routine is

?C: available to return a pointer to the start of the first occurrence

?C: of a substring in a memory area (or NULL if not found).

?C:.

?H:#\$d_mmemm HAS_MEMMEM /**/
?H:.

?LINT:set d_mmemm

: see if memmem exists

set memmem d_mmemm

eval \$inlibc

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-

debian-perl-5.26.1/U/perl/d_memmem.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1999 Jarkko Hietaniemi

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?MAKE:d_getmntent: Inlibc

?MAKE: -pick add \$@ %<

?S:d_getmntent:

?S: This variable conditionally defines the HAS_GETMNTENT symbol, which

?S: indicates to the C program that the getmntent() routine is available

?S: to iterate through mounted files to get their mount info.

?S:.

?C:HAS_GETMNTENT:

?C: This symbol, if defined, indicates that the getmntent routine is

?C: available to iterate through mounted file systems to get their info.

?C:.

?H:#\$d_getmntent HAS_GETMNTENT /**/

?H:.

?LINT:set d_getmntent

: see if getmntent exists

set getmntent d_getmntent

eval \$inlibc

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-

debian-perl-5.26.1/U/perl/d_getmntent.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_inetd.U 1 2006-08-24 12:32:52Z rmanfredi \$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic Licence,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic Licence; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: d_inetd.U,v \$

?RCS: Revision 3.0 1993/08/18 12:06:23 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?MAKE:d_inetd: cat test package Myread Setvar

```

?MAKE: -pick add $@ %<
?S:d_inetd:
?S: This symbol conditionally defines USE_INETD which indicates to the C
?S: program that the initial socket connection will be done via inetd.
?S:.
?C:USE_INETD (INETD):
?C: This symbol if defined indicates to the C program that inetd will be
?C: in charge of the
?C: initial socket connection. The file descriptors 0 and
?C: 1 have been dup()ed from the original connected socket descriptor and
?C: are ready for send() and recv().
?C:.
?H:#$d_inetd USE_INETD /**/
?H:.
?LINT:set d_inetd
: ask whether initial socket connection is to be done via inetd
echo " "
dflt=n
case "$d_inetd" in
") if $test -f /etc/inetd.conf; then
    $cat <<EOM

```

Your system provides a so called "Internet super-server", the inetd daemon. Network services like ftp or rlogin are usually handled via ftpd and rlogind daemons. Without inetd, these daemons must always be running for the service to be on. On the contrary, inetd listens to specific ports defined in file /etc/inetd.conf and will run the appropriate daemon upon request. This scheme avoids eating up the process table and memory with useless daemons.

I can set up things so that internet connections for \$package will be done using inetd, in which case you will have to edit /etc/inetd.conf to add some specific informations.

```

EOM
    dflt=y
else
    $cat
<<EOM

```

I do not see any trace of a configuration file for inetd, hence I assume your system does not support the so called "Internet super-server". This means \$package will need to have a daemon process running on this machine to allow network connections.

```

EOM
fi;;
*) case "$d_inetd" in
"$define") dflt=y;;
esac;;
esac

```

```
rp='Do you wish to use inetd for network connections?'
```

```
./myread  
val="$undef"  
case "$ans" in  
y*|Y*) val="$define";;  
esac  
set d_inetd  
eval $setvar
```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/d_inetd.U
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1998, Jarkko Hietaniemi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 3.0.

?X:

?X: Useless unit dropped. Use randfunc instead.

?X:

?LINT:empty

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/compline/randbits.U
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1999, Jarkko Hietaniemi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 3.0.

?RCS:

?MAKE:d_timer_getoverrun: Inlibc

?MAKE: -pick add \$@ %<

?S:d_timer_getoverrun:

?S: This variable conditionally defines HAS_TIMER_GETOVERRUN

?S: if timer_getoverrun() is available to get the number of

?S: overruns of a POSIX timer.

?S:.

?C:HAS_TIMER_GETOVERRUN:

?C: This symbol, if defined, indicates that the timer_getoverrun

?C: system call is available to get the number of overruns of

?C: a POSIX timer.

?C:.

?H:#\$d_timer_getoverrun HAS_TIMER_GETOVERRUN /**/

?H:.

?LINT:set d_timer_getoverrun

: see if timer_getoverrun exists

set

timer_getoverrun d_timer_getoverrun

eval \$inlibc

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_timer_getoverrun.U

No license file was found, but licenses were detected in source scan.

Perl5 Metaconfig Units

Copyright (c) 1996-1998, Andy Dougherty

Copyright (c) 1999-2011, H.Merijn Brand

All rights reserved.

These units are the ones used to build Configure and config_h.SH in the Perl5 distribution.

metaconfig will first look in its standard locations (specified when you installed dist). It will then recurse through the 'U' subdirectory and find any additional "private" units. Private units override standard ones supplied with metaconfig.

Files in this directory:

README

This file.

Glossary.patch

The standard dist units contain some strings that make pod2man complain. This patch silences those warnings. As new units are added and Configure is regenerated, this patch may need more and more 'fuzz' to be applied. It should be freshly regenerated every once in a while. See also mkgloss.pl

In-all.pl

Re-generate the all/ folder

mkglossary

A script

to regenerate Porting/Glossary. You have to manually edit the top of the script to point the location of your metaconfig units. It is called automatically by 'mksample'. See also mkgloss.pl

mkgloss.pl

A perl script that calls U/mkglossary from the perl source tree, sorts the list of symbols, and applies the patch mentioned in Glossary.patch.

When called on its own, redirect the output to a temporary file, and compare that file to Porting/Glossary before applying.

mksample

A script to regenerate Porting/config.sh and Porting/config.H.

It also calls mkglossary, if necessary.

Subdirectories:

The units and other related files have been broken up into the following directories.

a_dvisory/

These are units that have to go first in the generated config_h.SH.

A word of explanation: Configure and config_h.SH are generated from 'Units' (the *.U files). Files indicate dependencies (using make(1)), and Configure is built to follow those dependencies.

However, config_h.SH

is simply built by putting all the units in alphabetical order and extracting the relevant lines. (This could be fixed, I suppose, but it wasn't trivial the one time I looked.)

The a_dvisory/ directory, then, is a place to put units that need to be early in config_h.SH. (Most units are self-contained and ought to be able to go anywhere. However, some things, like byteorder, need to have the #defines from multiarch available.)

acl/

This is an old patch to begin to detect and use ACL (access control list) file protection schemes.

all/

A folder that conveniently holds symbolic links to all the modules that are used to build the current Configure and config_h.SH.

compline/

These are similar to the standard units, but I have modified them to have a more uniform compile command line, usually using the new Compile.U unit. (The ccflags.U unit is perl-specific since it

mentions -DDEBUGGING and
-DPOSIX_SOURCE, but that's the only place
it is perl-specific.)

dist_patches/

These are patches to dist that must be applied before it is built and installed. I have submitted these for inclusion in the regular dist distribution. They have already been applied to the ../dist-3.0at70b directory.

ebcdic/

These are units that had to be specially modified to work under either EBCDIC or ASCII.

installdirs/

These are units to handle perl's installation directories and related issues.

modified/

These are modified versions of the standard units. Also included in this directory are new units that are clearly derived from existing units. I have submitted these for inclusion in the regular dist distribution.

nullified/

These are null units that replace units in the standard distribution. Typically they are there because some part of the perl source accidentally uses a symbol that metaconfig means we want the corresponding unit.

perl/

These are specific to perl. Some are heavily derived from original dist units, and are marked as such. Others are original.

perl_patches/

These are patches to the perl source. This directory should ordinarily be empty, but there may have been drift between the standard version of perl and the one associated with these units.

protos/

These are units modified to use the new Hasproto.U or Protochk.U units to check for prototypes.

threads/

These are specific to threading perl.

typedefs/

These are standard units modified to use the modified Typedef.U unit to check for typedefs. (The modified Typdef.U includes a function to avoid unnecessary prompts if the typedef being searched for exists.)

Where appropriate, I submitted these units for inclusion into the regular dist distribution. However, since dist is no longer actively maintained, and the alternative is for *me* to actively maintain it, the units just sit here.

Copyright

Information:

Unless otherwise indicated, the files contained in this distribution are:

Copyright (c) 1996-1998, Andy Dougherty

The following licensing terms apply to all files contained in this distribution:

You may distribute the files contained in this distribution under the terms of either

- a) the "Artistic License" which comes with Perl, or
- b) the "Artistic License" which comes with dist, or
- c) the GNU General Public License as published by the Free Software Foundation; either version 1, or (at your option) any later version (see the file "Copying" that comes with the Perl distribution).

Which one to use is your choice.

The units in the "modified" directory have been derived from units associated with the metaconfig program of Raphael Manfredi's "dist" distribution. These units list Raphael Manfredi as the Copyright holder. dist is distributed under a modified version of the Perl Artistic License. Clause 7 of this modified license as contained in dist-3.0-pl60 provides:

- 7. You may reuse parts of this Package in your own programs, provided that you explicitly state where you got them from, in the source code (and, left to your courtesy, in the documentation), duplicating all the associated copyright notices and disclaimers. Besides

your changes, if any, must be clearly marked as such. Parts reused that way will no longer fall under this license if, and only if, the name of your program(s) have no immediate connection with the name of the Package itself or its associated programs. You may then apply whatever restrictions you wish on the reused parts or choose to place them in the Public Domain--this will apply only within the context of your package.

In accordance with this clause, the versions of these units contained here are made available under the same terms as the rest of the units.

If you have any questions about the use of these units or about the differences between these units and the standard versions, please feel free to ask.

Andy Dougherty doughera@lafayette.edu
Dept. of Physics
Lafayette College
Easton, PA 18042-1782

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/README
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: d_getlogin.U 1 2006-08-24 12:32:52Z rmanfredi $
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: Original Author: Andy Dougherty <doughera@lafcol.lafayette.edu>
?RCS:
?RCS: $Log: d_getlogin.U,v $
?RCS: Revision 3.0.1.1 1994/08/29 16:07:41 ram
?RCS: patch32: created by ADO
?RCS:
?MAKE:d_getlogin: Inlibc
?MAKE: -pick add $@ %<
?S:d_getlogin:
?S: This variable conditionally defines the HAS_GETLOGIN symbol, which
?S: indicates to the C program that the getlogin() routine is available
```

?S: to get the login name.
?S:.
?C:HAS_GETLOGIN :
?C: This symbol,
if defined, indicates that the getlogin routine is
?C: available to get the login name.
?C:.
?H:#\$d_getlogin HAS_GETLOGIN /**/
?H:.
?LINT:set d_getlogin
: see if getlogin exists
set getlogin d_getlogin
eval \$inlibc

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/d_getlogin.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: i_netdb.U,v \$
?RCS:
?RCS: Copyright (c) 1998 Andy Dougherty
?RCS:
?RCS: You may distribute under the terms of either the GNU General Public
?RCS: License or the Artistic License, as specified in the README file.
?RCS:
?MAKE:i_netdb: Inhdr
?MAKE: -pick add \$@ %<
?S:i_netdb:
?S: This variable conditionally defines the I_NETDB symbol, and indicates
?S: whether a C program should include <netdb.h>.
?S:.
?C:I_NETDB:
?C: This symbol, if defined, indicates that <netdb.h> exists and
?C: should be included.
?C:.
?H:#\$i_netdb I_NETDB /**/
?H:.
?LINT:set i_netdb
: see if this is a netdb.h system
set netdb.h i_netdb
eval \$inhdr

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/modified/i_netdb.U

No license file was found, but licenses were detected in source scan.

```

?RCS: $Id: d_bcmp.U 1 2006-08-24 12:32:52Z rmanfredi $
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: $Log: d_bcmp.U,v $
?RCS: Revision 3.0.1.2 1993/10/16 13:47:52 ram
?RCS: patch12: added magic support for bcmp()
?RCS:
?RCS: Revision 3.0.1.1 1993/09/13 16:00:44 ram
?RCS: patch10: now only defines HAS_BCMP, no macro remap on memcmp (WAD)
?RCS:
?RCS: Revision 3.0 1993/08/18 12:05:42 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:d_bcmp: Inlibc
?MAKE: -pick add $@ %<
?S:d_bcmp:
?S: This variable conditionally defines the HAS_BCMP symbol
if
?S: the bcmp() routine is available to compare strings.
?S:.
?C:HAS_BCMP:
?C: This symbol is defined if the bcmp() routine is available to
?C: compare blocks of memory.
?C:.
?H:#$d_bcmp HAS_BCMP /**/
?H:.
?M:bcmp: HAS_BCMP
?M:#ifndef HAS_BCMP
?M:#ifndef bcmp
?M:#define bcmp(s,d,l) memcmp((s),(d),(l))
?M:#endif
?M:#endif
?M:.
?LINT:set d_bcmp
: see if bcmp exists
set bcmp d_bcmp
eval $inlibc

```

Found in path(s):

```

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/d_bcmp.U

```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: sizetype.U,v 3.0.1.1 1994/08/29 16:32:10 ram Exp $
?RCS:
?RCS: Copyright (c) 1991-1993, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 3.0.
?RCS:
?RCS: Original Author: Andy Dougherty <doughera@lafcol.lafayette.edu>
?RCS:
?RCS: $Log: sizetype.U,v $
?RCS: Revision 3.0.1.1 1994/08/29 16:32:10 ram
?RCS: patch32: created by ADO
?RCS:
?MAKE:sizetype: Myread Typedef
?MAKE: -pick add $@ %<
?S:sizetype:
?S: This variable defines sizetype to be something like size_t,
?S: unsigned long, or whatever type is used to declare length
?S: parameters for string functions.
?S:.
?C:Size_t:
?C: This symbol holds the type used
to declare length parameters
?C: for string functions. It is usually size_t, but may be
?C: unsigned long, int, etc. It may be necessary to include
?C: <sys/types.h> to get any typedef'ed information.
?C:.
?H:#define Size_t $sizetype /* length parameter for string functions */
?H:.
?LINT: set sizetype
: see what type is used for size_t
rp="What is the type used for the length parameter for string functions?"
set size_t sizetype 'unsigned int' stdio.h sys/types.h
eval $typedef_ask
```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/typedefs/sizetype.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id$
?RCS:
?RCS: Copyright (c) 1999 Jarkko Hietaniemi
```

```

?RCS:
?RCS: You may distribute under the terms of either the GNU General Public
?RCS: License or the Artistic License, as specified in the README file.
?RCS:
?MAKE:d_cmsg_hdr_s: Hasstruct i_systypes d_socket i_sysuio Setvar
?MAKE: -pick add $@ %<
?S:d_cmsg_hdr_s:
?S: This variable conditionally defines the HAS_STRUCT_CMSGHDR symbol,
?S: which indicates that the struct cmsghdr is supported.
?S:.
?C:HAS_STRUCT_CMSGHDR:
?C: This symbol, if defined, indicates that the struct cmsghdr
?C: is supported.
?C:.
?H:#$d_cmsg_hdr_s HAS_STRUCT_CMSGHDR /**/
?H:.
?LINT:set d_cmsg_hdr_s
: Check for cmsghdr support
echo " "
echo "Checking to see if your system supports struct cmsghdr..." >&4
set d_cmsg_hdr_s cmsghdr $i_systypes sys/types.h $d_socket sys/socket.h $i_sysuio sys/uio.h
eval $hasstruct
case "$d_cmsg_hdr_s" in
"$define") echo "Yes, it does." ;;
*) echo
"No, it doesn't." ;;
esac

```

Found in path(s):

```

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/perl/d_cmsg_hdr_s.U

```

No license file was found, but licenses were detected in source scan.

```

?RCS: $Id: i_shadow.U,v $
?RCS:
?RCS: Copyright (c) 2000 Jarkko Hietaniemi
?RCS:
?RCS: You may distribute under the terms of either the GNU General Public
?RCS: License or the Artistic License, as specified in the README file.
?RCS:
?MAKE:i_prot: Inhdr Hasfield
?MAKE: -pick add $@ %<
?S:i_prot:
?S: This variable conditionally defines the I_PROT symbol, and indicates
?S: whether a C program should include <prot.h>.
?S:.
?C:I_PROT:
?C: This symbol, if defined, indicates that <prot.h> exists and

```

?C: should be included.

?C:.

?H:#\$i_prot I_PROT /**/

?H:.

?LINT:set i_prot

: see if this is a prot.h system

set prot.h i_prot

eval \$inhdr

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/i_prot.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: etc.U 1 2006-08-24 12:32:52Z rmanfredi \$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic Licence,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic Licence; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: etc.U,v \$

?RCS: Revision 3.0 1993/08/18 12:08:07 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?MAKE:etc etcexp: Getfile Loc Oldconfig

?MAKE: -pick add \$@ %<

?S:etc:

?S: This variable holds the name of the directory in which the user wants

?S: to put "administrative" executable images for the package in question.

?S: It is most often a local directory such as /usr/local/etc. Programs

?S: relying on this variable must be prepared to deal with

~name

?S: substitutions.

?S:.

?S:etcexp:

?S: This is the same as the etc variable, but is filename expanded at

?S: configuration time, for convenient use in makefiles.

?S:.

: determine where administrative executables go

case "\$etc" in

")

dfld=`./loc ./local/etc /usr/local/etc /local/etc /usr/etc /etc`

::

*)

```
dflt="$etc"  
;;  
esac  
fn=d~  
rp='Where should the administrative executables go?'  
./getfile  
etc="$ans"  
etcexp="$ansexp"
```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/etc.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: cpp_stuff.U 1 2006-08-24 12:32:52Z rmanfredi $  
?RCS:  
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi  
?RCS:  
?RCS: You may redistribute only under the terms of the Artistic License,  
?RCS: as specified in the README file that comes with the distribution.  
?RCS: You may reuse parts of this distribution only within the terms of  
?RCS: that same Artistic License; a copy of which may be found at the root  
?RCS: of the source tree for dist 4.0.  
?RCS:  
?RCS: $Log: cpp_stuff.U,v $  
?RCS: Revision 3.0.1.1 1994/10/29 16:08:24 ram  
?RCS: patch36: now uses cppstdin instead of plain cpp for consistency (ADO)  
?RCS: patch36: remove temporary files when done  
?RCS:  
?RCS: Revision 3.0 1993/08/18 12:05:36 ram  
?RCS: Baseline for dist 3.0 netwide release.  
?RCS:  
?MAKE:cpp_stuff: cat contains cppstdin cppflags cppminus rm  
?MAKE: -pick add $@ %<  
?S:cpp_stuff:  
?S: This variable contains an identification of the concatenation  
mechanism  
?S: used by the C preprocessor.  
?S:.  
?C:CAT2:  
?C: This macro concatenates 2 tokens together.  
?C:.  
?C:CAT3:  
?C: This macro concatenates 3 tokens together.  
?C:.  
?C:CAT4:  
?C: This macro concatenates 4 tokens together.  
?C:.
```

?C:CAT5:
?C: This macro concatenates 5 tokens together.
?C:.
?C:STRINGIFY:
?C: This macro surrounds its token with double quotes.
?C:.
?C:SCAT2:
?C: This macro concatenates 2 tokens together and stringifies the result.
?C: It might not exist, so #ifdef it in your code!
?C:.
?C:SCAT3:
?C: This macro concatenates 3 tokens together and stringifies the result.
?C: It might not exist, so #ifdef it in your code!
?C:.
?C:SCAT4:
?C: This macro concatenates 4 tokens together and stringifies the result.
?C: It might not exist, so #ifdef it in your code!
?C:.
?C:SCAT5:
?C: This macro concatenates 5 tokens together and stringifies the result.
?C: It might not exist, so #ifdef it in your code!
?C:.
?X: Dist pl70 included the following, but AIX's xlc compiler
?X: (which
is ANSI-ish and has cpp_stuff == 42)) rejects
?X: The SQuoTe/EQuoTe stuff because the string literals are on
?X: separate lines. Sigh.
?X: Andy Dougherty 24 Feb 1998
?X: ?H:??<:#if \$cpp_stuff == 1
?X: ?H:?CAT2:#define CAT2(a,b)a/**/b
?X: ?H:?CAT3:#define CAT3(a,b,c)a/**/b/**/c
?X: ?H:?CAT4:#define CAT4(a,b,c,d)a/**/b/**/c/**/d
?X: ?H:?CAT5:#define CAT5(a,b,c,d,e)a/**/b/**/c/**/d/**/e
?X: ?H:?STRINGIFY:#define STRINGIFY(a)"a"
?X: ?H:??<:#define SQuoTe(a)"a"
?X: ?H:??<:#define EQuoTe(a)a"
?X: ?H:?SCAT2:#define SCAT2(a,b)EQuoTe(SQuoTe(a)b)
?X: ?H:?SCAT3:#define SCAT3(a,b,c)EQuoTe(SQuoTe(a)b/**/c)
?X: ?H:?SCAT4:#define SCAT4(a,b,c,d)EQuoTe(SQuoTe(a)b/**/c/**/d)
?X: ?H:?SCAT5:#define SCAT5(a,b,c,d,e)EQuoTe(SQuoTe(a)b/**/c/**/d/**/e)
?X: ?H:??<:#endif
?H:??<:#if \$cpp_stuff == 1
?H:?CAT2:#define CAT2(a,b) a/**/b
?H:?CAT3:#define CAT3(a,b,c) a/**/b/**/c
?H:?CAT4:#define CAT4(a,b,c,d) a/**/b/**/c/**/d
?H:?CAT5:#define CAT5(a,b,c,d,e) a/**/b/**/c/**/d/**/e
?H:?STRINGIFY:#define STRINGIFY(a) "a"
?X: If

```

you can get stringification with catify, tell me how!
?H:?%<:#endif
?H:?%<:#if $cpp_stuff == 42
?H:?%<:#define PeRl_CaTiFy(a, b) a ## b
?H:?%<:#define PeRl_StGiFy(a) #a
?X: The additional level of indirection enables these macros to be
?X: used as arguments to other macros. See K&R 2nd ed., page 231.
?H:?CAT2:#define CAT2(a,b) PeRl_CaTiFy(a,b)
?H:?CAT3:#define CAT3(a,b,c) CAT2(PeRl_CaTiFy(a,b),c)
?H:?CAT4:#define CAT4(a,b,c,d) CAT2(CAT3(a,b,c),d)
?H:?CAT5:#define CAT5(a,b,c,d,e) CAT2(CAT4(a,b,c,d),e)
?H:?%<:#define StGiFy(a) PeRl_StGiFy(a)
?H:?STRINGIFY:#define STRINGIFY(a) PeRl_StGiFy(a)
?H:?SCAT2:#define SCAT2(a,b) PeRl_StGiFy(a) PeRl_StGiFy(b)
?H:?SCAT3:#define SCAT3(a,b,c) PeRl_StGiFy(a) PeRl_StGiFy(b) PeRl_StGiFy(c)
?H:?SCAT4:#define SCAT4(a,b,c,d) PeRl_StGiFy(a) PeRl_StGiFy(b) PeRl_StGiFy(c) PeRl_StGiFy(d)
?H:?SCAT5:#define SCAT5(a,b,c,d,e) PeRl_StGiFy(a) PeRl_StGiFy(b) PeRl_StGiFy(c) PeRl_StGiFy(d)
PeRl_StGiFy(e)
?H:?%<:#endif
?H:?%<:#if $cpp_stuff != 1 && $cpp_stuff
!= 42
?H:?%<:#include "Bleth: How does this C preprocessor concatenate tokens?"
?H:?%<:#endif
?H:.
?W:?%<:CAT2 CAT3 CAT4 CAT5 STRINGIFY SCAT2 SCAT3 SCAT4 SCAT5
?F:!cpp_stuff.c
?LINT:known StGiFy
?LINT:known PeRl_CaTiFy
?LINT:known PeRl_StGiFy
: how do we concatenate cpp tokens here?
echo " "
echo "Checking to see how your cpp does stuff like concatenate tokens..." >&4
$cat >cpp_stuff.c <<'EOCP'
#define RCAT(a,b)a/**/b
#define ACAT(a,b)a ## b
RCAT(Rei,ser)
ACAT(Cir,cus)
EOCP
$cppstdin $cppflags $cppminus <cpp_stuff.c >cpp_stuff.out 2>&1
if $contains 'Circus' cpp_stuff.out >/dev/null 2>&1; then
echo "Oh! Smells like ANSI's been here." >&4
echo "We can catify or stringify, separately or together!"
cpp_stuff=42
elif $contains 'Reiser' cpp_stuff.out >/dev/null 2>&1; then
echo "Ah, yes! The good old days!" >&4
echo "However, in the good old days we don't know how to stringify and"
echo "catify at the same time."
cpp_stuff=1

```

```

else
$cat >&4 <<EOM
Hmm, I don't seem to be able to concatenate
tokens with your cpp.
You're going to have to edit the values of CAT[2-5] in config.h...
EOM
?X: It would be nice to have configure remind us at the end that some manual
?X: intervention is needed -- FIXME
cpp_stuff="/* Help! How do we handle cpp_stuff? */*/"
fi
$rm -f cpp_stuff.*

```

Found in path(s):

```

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/modified/cpp_stuff.U

```

No license file was found, but licenses were detected in source scan.

```

?RCS: $Id$
?RCS:
?RCS: Copyright (c) 2003 Jarkko Hietaniemi
?RCS:
?RCS: You may distribute under the terms of either the GNU General Public
?RCS: License or the Artistic License, as specified in the README file.
?RCS:
?MAKE:d_copysignl: Inlibc
?MAKE: -pick add $@ %<
?S:d_copysignl:
?S: This variable conditionally defines the HAS_COPYSIGNL symbol, which
?S: indicates to the C program that the copysignl() routine is available.
?S: If aintl is also present we can emulate modfl.
?S:
?C:HAS_COPYSIGNL:
?C: This symbol, if defined, indicates that the copysignl routine is
?C: available. If aintl is also present we can emulate modfl.
?C:
?H:#$d_copysignl HAS_COPYSIGNL /**/
?H:
?LINT:set d_copysignl
: see if copysignl exists
set copysignl d_copysignl
eval $inlibc

```

Found in path(s):

```

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/perl/d_copysignl.U

```

No license file was found, but licenses were detected in source scan.

```

?RCS: $Id: d_getprotby.U,v $

```

```

?RCS:
?RCS: Copyright (c) 1998 Andy Dougherty
?RCS:
?RCS: You may distribute under the terms of either the GNU General Public
?RCS: License or the Artistic License, as specified in the README file.
?RCS:
?MAKE:d_getpbyname d_getpbynumber: Inlibc
?MAKE: -pick add $@ %<
?S:d_getpbyname:
?S: This variable conditionally defines the HAS_GETPROTOBYNAME
?S: symbol, which indicates to the C program that the
?S: getprotobyname() routine is available to look up protocols
?S: by their name.
?S:.
?S:d_getpbynumber:
?S: This variable conditionally defines the HAS_GETPROTOBYNUMBER
?S: symbol, which indicates to the C program that the
?S: getprotobynumber() routine is available to look up protocols
?S: by their number.
?S:.
?C:HAS_GETPROTOBYNAME:
?C: This symbol, if defined, indicates that the getprotobyname()
?C: routine is available to look up protocols by their name.
?C:.
?C:HAS_GETPROTOBYNUMBER:
?C: This
?C: symbol, if defined, indicates that the getprotobynumber()
?C: routine is available to look up protocols by their number.
?C:.
?H:#$d_getpbyname HAS_GETPROTOBYNAME /**/
?H:#$d_getpbynumber HAS_GETPROTOBYNUMBER /**/
?H:.
?LINT:set d_getpbyname d_getpbynumber
: Optional checks for getprotobyname and getprotobynumber

@if d_getpbyname || HAS_GETPROTOBYNAME
: see if getprotobyname exists
set getprotobyname d_getpbyname
eval $inlibc
@end

@if d_getpbynumber || HAS_GETPROTOBYNUMBER
: see if getprotobynumber exists
set getprotobynumber d_getpbynumber
eval $inlibc
@end

```

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/modified/d_getprotby.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: Signal.U,v \$

?RCS: Revision 3.0.1.1 1997/02/28 15:20:01 ram

?RCS: patch61: created

?RCS:

?X:

?X: This unit produces three files:

?X:

?X: 1- A signal.c file, which, when compiled and run, produces an output like:

?X:

?X: HUP 1

?X: INT 2

?X: QUIT 3

?X: etc...

?X:

?X: 2- A signal.awk script to parse the output of signal.c, fill

?X: in gaps (up to NSIG) and move duplicates to the end.

?X:

?X: 3- A signal_cmd script to compile signal.c and run it

?X: through `sort -n -k 2 | uniq | awk -f signal.awk`.

?X:

(we try also `sort -n +1` since some old hosts don't grok `sort -k`)

?X: (This is called `signal_cmd` to avoid OS/2 confusion with

?X: `signal.cmd` vs. `signal`.)

?X: The `signal_cmd` script also falls back on checking signals one at a

?X: time in case the `signal.c` program fails. On at least one version of

?X: Linux 2.1.x, the header file `#define'd SIGRTMAX` to a symbol that

?X: is not defined by the compiler/linker. :-(. Further, on that same

?X: version of Linux, the user had a defective C-shell that gave an

?X: incorrect list for `kill -l`, so the fall-back didn't work.

?X:

?X: This unit is then used by `sig_name.U`.

?X:

?MAKE:Signal: test tr rm awk cat grep startsh eunicefix sed sort uniq \
Findhdr cppstdin +cppflags cppminus Compile trnl run

```

?MAKE: -pick add $@ %<
?X:all files declared as "public" since they're used from other units
?F:signal.c signal_cmd signal.lst signal signal.awk
?T: xx xxx xxxfiles
?LINT:use rm run
: Trace out the files included by signal.h, then look for SIGxxx
names.
?X: Remove SIGARRAYSIZE used by HPUX.
?X: Remove SIGSTKSIZE used by Linux.
?X: Remove SIGSTKSZ used by Posix.
?X: Remove SIGTYP void lines used by OS2.
?X: Some cpps, like os390, dont give the file name anywhere
if [ "$fieldn" = X ]; then
: Just make some guesses. We check them later.
xxx='/usr/include/signal.h /usr/include/sys/signal.h'
else
xxx=`echo '#include <signal.h>' |
$cpptest $cpptestminus $cpptestflags 2>/dev/null |
$grep '^ [ ]*#.*include' |
$awk '{print \\$fieldn}' | $sed 's!'!g' | \
$sed 's!\\\\\\\\\\\\\\\\!g' | $sort | $uniq`
fi
?X: Check this list of files to be sure we have parsed the cpp output ok.
?X: This will also avoid potentially non-existent files, such
?X: as ../foo/bar.h
xxxfiles=""
?X: Add /dev/null in case the $xxx list is empty.
for xx in $xxx /dev/null ; do
$test -f "$xx" && xxxfiles="$xxxfiles $xx"
done
?X: If we have found no files, at least try signal.h
case "$xxxfiles" in
") xxxfiles=`./findhdr signal.h` ;;
esac
xxx=`awk '
$1 ~ /^#define$/ &&
$2 ~ /^SIG[A-Z0-9]*$/ && $2 !~ /SIGARRAYSIZE/ && $2 !~ /SIGSTKSIZE/ && $2 !~ /SIGSTKSZ/ && $3 !~
/void/ {
print substr($2, 4, 20)
}
$1 == "#" && $2 ~ /^define$/ && $3 ~ /^SIG[A-Z0-9]*$/ && $3 !~ /SIGARRAYSIZE/ && $4 !~ /void/ {
print substr($3, 4, 20)
}' $xxxfiles`
: Append some common names just in case the awk scan failed.
xxx="$xxx ABRT ALRM BUS CANCEL CHLD CLD CONT DIL EMT FPE"
xxx="$xxx FREEZE HUP ILL INT IO IOT KILL LOST LWP PHONE"
xxx="$xxx PIPE POLL PROF PWR QUIT RTMAX RTMIN SEGV STKFLT STOP"
xxx="$xxx SYS TERM THAW TRAP TSTP TTIN TTOU URG USR1 USR2"

```

```
xxx="$xxx USR3 USR4 VTALRM WAITING WINCH WIND WINDOW XCPU XFSZ"
```

```
: generate a few handy files for later
```

```
$cat > signal.c <<'EOCP'
```

```
#include <sys/types.h>
```

```
#include <signal.h>
```

```
#include <stdio.h>
```

```
int main() {
```

```
/* Strange style to avoid deeply-nested #if/#else/#endif */
```

```
#ifndef NSIG
```

```
# ifdef _NSIG
```

```
#  define NSIG (_NSIG)
```

```
# endif
```

```
#endif
```

```
#ifndef NSIG
```

```
# ifdef SIGMAX
```

```
#  define NSIG (SIGMAX+1)
```

```
# endif
```

```
#endif
```

```
#ifndef NSIG
```

```
# ifdef SIG_MAX
```

```
#
```

```
    define NSIG (SIG_MAX+1)
```

```
# endif
```

```
#endif
```

```
#ifndef NSIG
```

```
# ifdef MAXSIG
```

```
#  define NSIG (MAXSIG+1)
```

```
# endif
```

```
#endif
```

```
#ifndef NSIG
```

```
# ifdef MAX_SIG
```

```
#  define NSIG (MAX_SIG+1)
```

```
# endif
```

```
#endif
```

```
#ifndef NSIG
```

```
# ifdef SIGARRAYSIZE
```

```
#  define NSIG (SIGARRAYSIZE+1) /* Not sure of the +1 */
```

```
# endif
```

```
#endif
```

```
#ifndef NSIG
```

```

# ifdef _sys_nsig
#  define NSIG (_sys_nsig) /* Solaris 2.5 */
# endif
#endif

/* Default to some arbitrary number that's big enough to get most
of the common signals.
*/
#ifndef NSIG
#  define NSIG 50
#endif

printf("NSIG %d\n", NSIG);

#ifndef JUST_NSIG

EOCP

echo $xxx | $tr ' ' $trnl | $sort | $uniq | $awk '
{
printf "#ifdef SIG"; printf $1; printf "\n"
printf "printf(\""; printf $1; printf " %%d\\n\",SIG";
printf $1; printf ");\n"
printf "#endif\n"
}
END {
printf "#endif /* JUST_NSIG */\n";
printf "exit(0);\n}\n";
}
' >>signal.c
$cat >signal.awk <<'EOP'
BEGIN { ndups = 0 }
$1 ~ /^NSIG$/ { nsig = $2 }
($1 !~ /^NSIG$/) && (NF == 2) {
    if ($2 >
maxsig) { maxsig = $2 }
    if (sig_name[$2]) {
dup_name[ndups] = $1
dup_num[ndups] = $2
ndups++
    }
    else {
sig_name[$2] = $1
sig_num[$2] = $2
    }
}
END {
    if (nsig == 0) {

```

```

    nsig = maxsig + 1
  }
  printf("NSIG %d\n", nsig);
  for (n = 1; n < nsig; n++) {
if (sig_name[n]) {
    printf("%s %d\n", sig_name[n], sig_num[n])
  }
else {
    printf("NUM%d %d\n", n, n)
  }
  }
  for (n = 0; n < ndups; n++) {
printf("%s %d\n", dup_name[n], dup_num[n])
  }
}

```

EOP

```
$cat >signal_cmd <<EOS
```

```
$startsh
```

```
if $test -s signal.lst; then
```

```
    echo "Using your existing signal.lst file"
```

```
    exit 0
```

```
fi
```

```
xxx="$xxx"
```

```
EOS
```

?X: Avoid variable interpolation problems, especially with

?X: xxx, which contains newlines.

```
$cat >>signal_cmd <<'EOS'
```

```
set signal
```

```
if eval $compile_ok; then
```

```
    $run ./signal$_exe | ($sort -n -k 2 2>/dev/null || $sort -n +1) |\
```

```
    $uniq | $awk -f signal.awk >signal.lst
```

```
else
```

```
    echo "(I can't seem be able to compile the whole test program)" >&4
```

```
    echo "(I'll try it in little
```

```
pieces.)" >&4
```

```
    set signal -DJUST_NSIG
```

```
    if eval $compile_ok; then
```

```
        $run ./signal$_exe > signal.nsg
```

```
        $cat signal.nsg
```

```
    else
```

```
        echo "I can't seem to figure out how many signals you have." >&4
```

```
        echo "Guessing 50." >&4
```

```
        echo 'NSIG 50' > signal.nsg
```

```
    fi
```

: Now look at all the signal names, one at a time.

```
for xx in `echo $xxx | $tr ' ' $trnl | $sort | $uniq`; do
```

```
    $cat > signal.c <<EOCP
```

```

#include <sys/types.h>
#include <signal.h>
#include <stdio.h>
int main() {
printf("$xx %d\n", SIG${xx});
return 0;
}
EOCP
set signal
if eval $compile; then
echo "SIG${xx} found."
$run ./signal$_exe >> signal.ls1
else
echo "SIG${xx} NOT found."
fi
done
if $test -s signal.ls1; then
$cat signal.nsg signal.ls1 |
$sort -n | $uniq | $awk -f signal.awk >signal.lst
fi

fi
if $test -s signal.lst; then
:
else
echo "(AAK! I can't compile the test programs -- Guessing)" >&4
echo 'kill -l' >signal
set X `csh -f <signal`
$rm -f signal
shift
case $# in
0) set HUP INT QUIT ILL TRAP ABRT
EMT FPE KILL BUS SEGV SYS PIPE ALRM TERM;;
esac
echo $@ | $tr ' ' $trnl | \
$awk '{ printf "%s %d\n", $1, ++s; }
END { printf "NSIG %d\n", ++s }' >signal.lst
fi
$rm -f signal.c signal$_exe signal$_o signal.nsg signal.ls1
EOS
chmod a+x signal_cmd
$eunicefix signal_cmd

```

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/Signal.U

No license file was found, but licenses were detected in source scan.

```

?RCS: $Id: d_memccpy.U 1 2006-08-24 12:32:52Z rmanfredi $
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: $Log: d_memccpy.U,v $
?RCS: Revision 3.0 1993/08/18 12:06:31 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:d_memccpy: Inlibc
?MAKE: -pick add $@ %<
?S:d_memccpy:
?S: This variable conditionally defines the HAS_MEMCCPY symbol, which
?S: indicates to the C program that the memccpy() routine is available
?S: to copy a character into a block of memory.
?S:.
?C:HAS_MEMCCPY (MEMCCPY):
?C: This symbol, if defined, indicates that the memccpy routine
is available
?C: to copy a character into a block of memory. Otherwise you should
?C: roll your own.
?C:.
?H:#$d_memccpy HAS_MEMCCPY /**/
?H:.
?LINT:set d_memccpy
: see if memccpy exists
set memccpy d_memccpy
eval $inlibc

```

Found in path(s):

```

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/d_memccpy.U

```

No license file was found, but licenses were detected in source scan.

```

?RCS: $Id: d_readlink.U 1 2006-08-24 12:32:52Z rmanfredi $
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.

```

```

?RCS:
?RCS: Original Author: Andy Dougherty <doughera@lafcol.lafayette.edu>
?RCS:
?RCS: $Log: d_readlink.U,v $
?RCS: Revision 3.0.1.1 1994/08/29 16:11:52 ram
?RCS: patch32: created by ADO
?RCS:
?MAKE:d_readlink: Inlibc
?MAKE: -pick add $@ %<
?S:d_readlink:
?S: This variable conditionally defines the HAS_READLINK symbol, which
?S: indicates to the C program that the readlink() routine is available
?S: to read the value of a symbolic link.
?S:.
?C:HAS_READLINK :
?C: This
symbol, if defined, indicates that the readlink routine is
?C: available to read the value of a symbolic link.
?C:.
?H:#$d_readlink HAS_READLINK /**/
?H:.
?LINT:set d_readlink
: see if readlink exists
set readlink d_readlink
eval $inlibc

```

Found in path(s):

```

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/d_readlink.U

```

No license file was found, but licenses were detected in source scan.

```

?RCS: $Id: patchlevel.U,v 3.0.1.1 1997/02/28 16:18:41 ram Exp $
?RCS:
?RCS: Copyright (c) 1991-1993, Raphael Manfredi
?RCS:
?RCS: This file is included with or a derivative work of a file included
?RCS: with the metaconfig program of Raphael Manfredi's "dist" distribution.
?RCS: In accordance with clause 7 of dist's modified Artistic License:
?RCS:
?RCS: You may distribute under the terms of either the GNU General Public
?RCS: License or the Artistic License, as specified in the README file.
?RCS:
?RCS: $Log: patchlevel.U,v $
?RCS: Revision 3.0.1.1 1997/02/28 16:18:41 ram
?RCS: patch61: added support for src.U
?RCS:
?RCS: Revision 3.0 1993/08/18 12:09:31 ram
?RCS: Baseline for dist 3.0 netwide release.

```

?RCS:

?MAKE:patchlevel revision version subversion \
 perl_patchlevel version_patchlevel_string \
 api_revision api_version api_subversion api_versionstring: \
 package test rsrc echo awk osname

?MAKE: -pick
 add \$@ %<

?S:revision:

?S: The value of revision comes from the patchlevel.h file.
 ?S: In a version number such as 5.6.1, this is the "5".
 ?S: In patchlevel.h, this is referred to as "PERL_REVISION".
 ?S:.

?S:patchlevel:

?S: The patchlevel level of this package.
 ?S: The value of patchlevel comes from the patchlevel.h file.
 ?S: In a version number such as 5.6.1, this is the "6".
 ?S: In patchlevel.h, this is referred to as "PERL_VERSION".
 ?S:.

?S:subversion:

?S: The subversion level of this package.
 ?S: The value of subversion comes from the patchlevel.h file.
 ?S: In a version number such as 5.6.1, this is the "1".
 ?S: In patchlevel.h, this is referred to as "PERL_SUBVERSION".
 ?S: This is unique to perl.
 ?S:.

?S:version:

?S: The full version number of this package, such as 5.6.1 (or 5_6_1).
 ?S: This combines revision, patchlevel, and subversion to get the
 ?S: full version number, including any possible subversions.
 ?S: This is suitable for use as a directory name, and hence is
 ?S: filesystem
 ?S: dependent.
 ?S:.

?S:api_revision:

?S: The three variables, api_revision, api_version, and
 ?S: api_subversion, specify the version of the oldest perl binary
 ?S: compatible with the present perl. In a full version string
 ?S: such as '5.6.1', api_revision is the '5'.
 ?S: Prior to 5.5.640, the format was a floating point number,
 ?S: like 5.00563.
 ?S:

?S: perl.c:incpush() and lib/lib.pm will automatically search in
 ?S: \$sitelib/.. for older directories back to the limit specified
 ?S: by these api_ variables. This is only useful if you have a
 ?S: perl library directory tree structured like the default one.
 ?S: See INSTALL for how this works. The versioned site_perl
 ?S: directory was introduced in 5.005, so that is the lowest
 ?S: possible value. The version list appropriate for the current

?S: system is determined in inc_version_list.U.
?S:
?S: XXX To do: Since compatibility can depend on compile time
?S: options (such as bincompat, longlong, etc.) it should
?S: (perhaps) be set by
Configure, but currently it isn't.
?S: Currently, we read a hard-wired value from patchlevel.h.
?S: Perhaps what we ought to do is take the hard-wired value from
?S: patchlevel.h but then modify it if the current Configure
?S: options warrant. patchlevel.h then would use an #ifdef guard.
?S:.
?S:api_version:
?S: The three variables, api_revision, api_version, and
?S: api_subversion, specify the version of the oldest perl binary
?S: compatible with the present perl. In a full version string
?S: such as '5.6.1', api_version is the '6'. See api_revision for
?S: full details. As a special case, 5.5.0 is rendered in the
?S: old-style as 5.005. (In the 5.005_0x maintenance series,
?S: this was the only versioned directory in \$sitelib.)
?S:.
?S:api_subversion:
?S: The three variables, api_revision, api_version, and
?S: api_subversion, specify the version of the oldest perl binary
?S: compatible with the present perl. In a full version string
?S: such as '5.6.1', api_subversion is the
'1'. See api_revision for
?S: full details.
?S:.
?S:api_versionstring:
?S: This variable combines api_revision, api_version, and
?S: api_subversion in a format such as 5.6.1 (or 5_6_1) suitable
?S: for use as a directory name. This is filesystem dependent.
?S:.
?S:perl_patchlevel:
?S: This is the Perl patch level, a numeric change identifier,
?S: as defined by whichever source code maintenance system
?S: is used to maintain the patches; currently Perforce.
?S: It does not correlate with the Perl version numbers or
?S: the maintenance versus development dichotomy except
?S: by also being increasing.
?S:.
?S:version_patchlevel_string:
?S: This is a string combining version, subversion and
?S: perl_patchlevel (if perl_patchlevel is non-zero).
?S: It is typically something like
?S: 'version 7 subversion 1' or
?S: 'version 7 subversion 1 patchlevel 11224'
?S: It is computed here to avoid duplication of code in myconfig.SH

```

?S: and lib/Config.pm.
?S:.
?LINT:extern LC_ALL
?LINT:extern LANGUAGE
:
  get the patchlevel
  echo " "
  echo "Getting the current patchlevel..." >&4
  if $test -r $src/patchlevel.h;then
    revision=`awk '/define[ ]+PERL_REVISION/ {print $3}' $src/patchlevel.h`
    patchlevel=`awk '/define[ ]+PERL_VERSION/ {print $3}' $src/patchlevel.h`
    subversion=`awk '/define[ ]+PERL_SUBVERSION/ {print $3}' $src/patchlevel.h`
    api_revision=`awk '/define[ ]+PERL_API_REVISION/ {print $3}' $src/patchlevel.h`
    api_version=`awk '/define[ ]+PERL_API_VERSION/ {print $3}' $src/patchlevel.h`
    api_subversion=`awk '/define[ ]+PERL_API_SUBVERSION/ {print $3}' $src/patchlevel.h`
    perl_patchlevel=`egrep ', "(MAINT|SMOKE)[0-9][0-9]*"' $src/patchlevel.h|tail -1|sed 's/[^0-9]//g`
  else
    revision=0
    patchlevel=0
    subversion=0
    api_revision=0
    api_version=0
    api_subversion=0
    perl_patchlevel=0
    $echo "(You do not have patchlevel.h. Eek.)"
  fi
: Define a handy string here to avoid duplication in myconfig.SH and configpm.
version_patchlevel_string="version $patchlevel subversion $subversion"
case
"$perl_patchlevel" in
0|") ;;
*) perl_patchlevel=`echo $perl_patchlevel | sed 's/.* //'`
  version_patchlevel_string="$version_patchlevel_string patch $perl_patchlevel"
  ;;
esac

$echo "(You have $package $version_patchlevel_string.)"

case "$osname" in
dos|vms)
: XXX Should be a Configure test for double-dots in filenames.
version=`echo $revision $patchlevel $subversion | \
  $awk '{ printf "%d_%d_%d", $1, $2, $3 }`
api_versionstring=`echo $api_revision $api_version $api_subversion | \
  $awk '{ printf "%d_%d_%d", $1, $2, $3 }`
;;
*)
version=`echo $revision $patchlevel $subversion | \

```

```

    Sawk '{ printf "%d.%d.%d", $1, $2, $3 }'`
api_versionstring=`echo $api_revision $api_version $api_subversion | \
    Sawk '{ printf "%d.%d.%d", $1, $2, $3 }'`
;;
esac
: Special case the 5.005_xx maintenance series, which used 5.005
: without any subversion label as a subdirectory in $sitelib
if test "${api_revision}${api_version}${api_subversion}" = "550"; then
    api_versionstring='5.005'
fi

```

Found

in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/perl/patchlevel.U
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 2000, Andy Dougherty

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 3.0.

?RCS:

?MAKE:versiononly: cat Myread Setvar Devel

?MAKE: -pick add \$@ %<

?LINT:set versiononly

?Y:TOP

?S:versiononly:

?S: If set, this symbol indicates that only the version-specific

?S: components of a perl installation should be installed.

?S: This may be useful for making a test installation of a new

?S: version without disturbing the existing installation.

?S: Setting versiononly is equivalent to setting installperl's -v option.

?S: In particular, the non-versioned scripts and programs such as

?S: a2p, c2ph, h2xs, pod2*, and perldoc

are not installed

?S: (see INSTALL for a more complete list). Nor are the man

?S: pages installed.

?S: Usually, this is undef.

?S:.

?LINT:extern inc_version_list

?LINT:change inc_version_list

?LINT:extern inc_version_list_init

?LINT:change inc_version_list_init

```
?LINT:extern version
: determine whether to use a version number suffix for installed binaries
echo " "
$cat <<EOM
```

Do you want to use a version number suffix for installed binaries? This will install 'perl\$version' instead of 'perl', and likewise for other binaries like 'perldoc' and 'cpan'. This allows many versions of perl to be installed side-by-side. Unless you are a developer, you probably do *not* want to do this.

```
EOM
case "$versiononly" in
"$define"[[Yy]*|true) dflt='y' ;;
*) dflt='n';
esac
rp="Do you want to use a version number suffix for installed binaries?"
./myread
case "$ans" in
[yY]*) val="$define";;
*) val="$undef" ;;
esac
set versiononly
eval $setvar
```

```
case "$versiononly" in
"$define") inc_version_list="
    inc_version_list_init=0
    ;;
esac
```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/versiononly.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: d_chsize.U 1 2006-08-24 12:32:52Z rmanfredi $
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: $Log: d_chsize.U,v $
?RCS: Revision 3.0 1993/08/18 12:05:50 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
```

?MAKE:d_chsize: Inlibc
?MAKE: -pick add \$@ %<
?S:d_chsize:
?S: This variable conditionally defines the CHSIZE symbol, which
?S: indicates to the C program that the chsize() routine is available
?S: to truncate files. You might need a -lx to get this routine.
?S:.
?C:HAS_CHSIZE (CHSIZE):
?C: This symbol, if defined, indicates that the chsize
routine is available
?C: to truncate files. You might need a -lx to get this routine.
?C:.
?H:#\$d_chsize HAS_CHSIZE /**/
?H:.
?LINT:set d_chsize
: see if chsize exists
set chsize d_chsize
eval \$inlibc

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/d_chsize.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$
?RCS:
?RCS: Copyright (c) 1999, Jarkko Hietaniemi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 3.0.
?RCS:
?MAKE:d_sched_getscheduler: Inlibc
?MAKE: -pick add \$@ %<
?S:d_sched_getscheduler:
?S: This variable conditionally defines HAS_SCHED_GETSCHEDULER if
?S: sched_getscheduler() is available to get the scheduling policy.
?S:.
?C:HAS_SCHED_GETSCHEDULER:
?C: This symbol, if defined, indicates that the sched_getscheduler
?C: system call is available to get the scheduling policy.
?C:.
?H:#\$d_sched_getscheduler HAS_SCHED_GETSCHEDULER /**/
?H:.
?LINT:set d_sched_getscheduler
: see if sched_getscheduler exists

```
set sched_getscheduler
d_sched_getscheduler
eval $inlibc
```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/perl/d_sched_getscheduler.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id$
?RCS:
?RCS: Copyright (c) 1998 Andy Dougherty
?RCS:
?RCS: You may distribute under the terms of either the GNU General Public
?RCS: License or the Artistic License, as specified in the README file.
?RCS:
?MAKE:uselongdouble: Myread Oldconfig Setvar cat test usemorebits
?MAKE: -pick add $@ %<
?Y:TOP
?S:uselongdouble:
?S: This variable conditionally defines the USE_LONG_DOUBLE symbol,
?S: and indicates that long doubles should be used when available.
?S:
?C:USE_LONG_DOUBLE:
?C: This symbol, if defined, indicates that long doubles should
?C: be used when available.
?C:
?H:%<:#ifndef USE_LONG_DOUBLE
?H:%<:#$uselongdouble USE_LONG_DOUBLE /**/
?H:%<:#endif
?H:
?LINT:extern ccflags
?LINT:use usemorebits
?F:!uselongdouble.cbu
: Check for uselongdouble support
case "$ccflags" in
*-DUSE_LONG_DOUBLE*|*-DUSE_MORE_BITS*) uselongdouble="$define" ;;
esac

case "$uselongdouble" in
$define|true|[yY]*) dflt='y';;
*)
dflt='n';;
esac
cat <<EOM
```

Perl can be built to take advantage of long doubles which
(if available) may give more accuracy and range for floating point numbers.

If this doesn't make any sense to you, just accept the default '\$dflt'.

EOM

```
rp="Try to use long doubles if available?"
```

```
./myread
```

```
case "$sans" in
```

```
y|Y) val="$define" ;;
```

```
*) val="$undef" ;;
```

```
esac
```

```
set uselongdouble
```

```
eval $setvar
```

```
case "$uselongdouble" in
```

```
true|[yY]*) uselongdouble="$define" ;;
```

```
esac
```

```
: Look for a hint-file generated 'call-back-unit'. If the
```

```
: user has specified that long doubles should be used,
```

```
: we may need to set or change some other defaults.
```

```
if $test -f uselongdouble.cbu; then
```

```
    echo "Your platform has some specific hints regarding long doubles, using them..."
```

```
    ./uselongdouble.cbu
```

```
else
```

```
    case "$uselongdouble" in
```

```
    $define)
```

```
        $cat <<EOM
```

```
(Your platform does not have any specific hints for long doubles.)
```

```
EOM
```

```
;;
```

```
    esac
```

```
fi
```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/uselongdbl.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id$
```

```
?RCS:
```

```
?RCS: Copyright (c) 2000 Jarkko Hietaniemi
```

```
?RCS:
```

```
?RCS: You may distribute under the terms of either the GNU General Public
```

```
?RCS: License or the Artistic License, as specified in the README file.
```

```
?RCS:
```

```
?MAKE:d_mkdtemp: Inlibc
```

```
?MAKE: -pick add $@ %<
```

```
?S:d_mkdtemp:
```

```
?S: This variable conditionally defines the HAS_MKDTEMP symbol, which
```

?S: indicates to the C program that the mkdtemp() routine is available
?S: to exclusively create a uniquely named temporary directory.
?S:.
?C:HAS_MKDTEMP :
?C: This symbol, if defined, indicates that the mkdtemp routine is
?C: available to exclusively create a uniquely named temporary directory.
?C:.
?H:#\$d_mkdtemp HAS_MKDTEMP /**/
?H:.
?LINT:set d_mkdtemp
: see if mkdtemp exists
set mkdtemp d_mkdtemp
eval \$inlibc

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_mkdtemp.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_cuserid.U 1 2006-08-24 12:32:52Z rmanfredi \$
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: Original Author: Andy Dougherty <doughera@lafcol.lafayette.edu>
?RCS:
?RCS: \$Log: d_cuserid.U,v \$
?RCS: Revision 3.0.1.1 1994/08/29 16:07:25 ram
?RCS: patch32: created by ADO
?RCS:
?MAKE:d_cuserid: Inlibc
?MAKE: -pick add \$@ %<
?S:d_cuserid:
?S: This variable conditionally defines the HAS_CUSERID symbol, which
?S: indicates to the C program that the cuserid() routine is available
?S: to get character login names.
?S:.
?C:HAS_CUSERID :
?C: This symbol,
if defined, indicates that the cuserid routine is
?C: available to get character login names.
?C:.
?H:#\$d_cuserid HAS_CUSERID /**/

?H:
?LINT:set d_cuserid
: see if cuserid exists
set cuserid d_cuserid
eval \$inlibc

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/d_cuserid.U

No license file was found, but licenses were detected in source scan.

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?MAKE:d_nexttoward: Inlibc

?MAKE: -pick add \$@ %<

?S:d_nexttoward:

?S: This variable conditionally defines HAS_NEXTTOWARD if nexttoward()

?S: is available to return the next machine representable long double from

?S: x in direction y.

?S:.

?C:HAS_NEXTTOWARD:

?C: This symbol, if defined, indicates that the nexttoward routine is

?C: available to return the next machine representable long double from

?C: x in direction y.

?C:.

?H:#\$d_nexttoward HAS_NEXTTOWARD /**/

?H:.

?LINT:set d_nexttoward

: see if nexttoward exists

set nexttoward d_nexttoward

eval \$inlibc

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_nexttoward.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

```

?RCS: $Log: d_portable.U,v $
?RCS: Revision 3.0.1.2 1995/01/11 15:28:52 ram
?RCS: patch45: executable path stripping moved to the end in Config_sh.U
?RCS:
?RCS: Revision 3.0.1.1 1993/12/15 08:21:17 ram
?RCS: patch15: did not strip variables properly when needed
?RCS: patch15: now also strips down variables from trylist
?RCS:
?RCS: Revision 3.0 1993/08/18 12:06:48 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?X:
?X: The Loc unit is wanted to get the definition of all the locating variables.
?X:
?MAKE:d_portable:
cat Loc Myread Oldconfig
?MAKE: -pick add $@ %<
?S:d_portable:
?S: This variable conditionally defines the PORTABLE symbol, which
?S: indicates to the C program that it should not assume that it is
?S: running on the machine it was compiled on.
?S:.
?C:PORTABLE:
?C: This symbol, if defined, indicates to the C program that it should
?C: not assume that it is running on the machine it was compiled on.
?C: The program should be prepared to look up the host name, translate
?C: generic filenames, use PATH, etc.
?C:.
?H:#$d_portable PORTABLE /**/
?H:.
?D:d_portable="
: decide how portable to be
case "$d_portable" in
"$define") dflt=y;;
*) dflt=n;;
esac
$cat <<'EOH'

```

I can set things up so that your shell scripts and binaries are more portable, at what may be a noticable cost in performance. In particular, if you ask to be portable, the following happens:

- 1) Shell scripts will rely on the PATH variable rather than using the paths derived above.
 - 2) ~username interpretations will be done at run time rather than by Configure.
- @if PHOSTNAME

3) The system name will be determined at run time, if at all possible.

@end

EOH

```
rp="Do you expect to run these scripts and binaries on multiple machines?"
./myread
case "$ans" in
y*) d_portable="$define"
?X:
?X: Paths will be stripped down (/usr/bin/vi -> vi) in Config_sh.U if needed.
?X:
;;
*) d_portable="$undef" ;;
esac
```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/d_portable.U
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_setsid.U 1 2006-08-24 12:32:52Z rmanfredi \$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic Licence,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic Licence; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: d_setsid.U,v \$

?RCS: Revision 3.0.1.1 1994/01/24 14:06:49 ram

?RCS: patch16: created

?RCS:

?RCS: Revision 3.0 1993/08/18 12:05:56 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?MAKE:d_setsid: Inlibc

?MAKE: -pick add \$@ %<

?S:d_setsid:

?S: This variable conditionally defines HAS_SETSID if setsid() is

?S: available to set the process group ID.

?S:.

?C:HAS_SETSID:

?C: This symbol, if defined, indicates that the setsid routine is

?C: available

to set the process group ID.

?C:.

?H:#\$d_setsid HAS_SETSID /**/

?H:.

?LINT:set d_setsid

: see if setsid exists

set setsid d_setsid

eval \$inlibc

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/d_setsid.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: dlsrc.U,v\$

?RCS:

?RCS: Copyright (c) 1996-1998, Andy Dougherty

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?RCS: \$Log: dlex.t.U,v \$

?RCS:

?X: hpux support thanks to Jeff Okamoto <okamoto@hpcc101.corp.hp.com>

?X:

?X: To create a shared library, you must compile ALL source files in the

?X: library with +z (or possibly +Z if the library is whopping huge),

?X: then link the library with -b. Example:

?X: cc -c +z module_a.c

?X: cc -c +z module_b.c

?X: ld -b module_a.o module_b.o -o module.sl

?X:

?MAKE:dlex.t: \

Getfile Myread cat usedl so

?MAKE: -pick add \$@ %<

?Y:BOTTOM

?S:dlex.t:

?S: This variable contains the extension that is to be used for the

?S: dynamically loaded modules that perl generates.

?S:.

: Check what extension to use for shared libs

case "\$usedl" in

\$define|y|true)

\$cat <<

EOM

On a few systems, the dynamically loaded modules that perl generates and uses will need a different extension than shared libs. The default will probably be appropriate.

```

EOM
case "$dlex" in
") dflt="$so" ;;
*) dflt="$dlex" ;;
esac
rp='What is the extension of dynamically loaded modules'
./myread
dlex="$ans"
;;
*)
dlex="none"
;;
esac

```

Found in path(s):

```

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/perl/dlex.U

```

No license file was found, but licenses were detected in source scan.

```

?RCS: $Id: d_srandom_r.U,v 0RCS:
?RCS: Copyright (c) 2002,2003 Jarkko Hietaniemi
?RCS:
?RCS: You may distribute under the terms of either the GNU General Public
?RCS: License or the Artistic License, as specified in the README file.
?RCS:
?RCS: Generated by the reentr.pl from the Perl 5.8 distribution.
?RCS:
?MAKE:d_srandom_r random_r_proto: Inlibc Protochk Hasproto i_systypes \
  usethreads i_stdlib extern_C
?MAKE: -pick add $@ %<
?S:d_srandom_r:
?S: This variable conditionally defines the HAS_SRANDOM_R symbol,
?S: which indicates to the C program that the srandom_r()
?S: routine is available.
?S:.
?S:srandom_r_proto:
?S: This variable encodes the prototype of srandom_r.
?S: It is zero if d_srandom_r is undef, and one of the
?S: REENTRANT_PROTO_T_ABC macros of reentr.h if d_srandom_r
?S: is defined.
?S:.
?C:HAS_SRANDOM_R:
?C: This symbol, if defined, indicates that the srandom_r routine
?C: is available to srandom re-entrantly.
?C:.
?C:SRANDOM_R_PROTO:
?C: This

```

```

symbol encodes the prototype of srandom_r.
?C: It is zero if d_srandom_r is undef, and one of the
?C: REENTRANT_PROTO_T_ABC macros of reentr.h if d_srandom_r
?C: is defined.
?C:.
?H:#$d_srandom_r HAS_SRANDOM_R  /**/
?H:#define SRANDOM_R_PROTO $srandom_r_proto  /**/
?H:.
?T:try hdrs d_srandom_r_proto
: see if srandom_r exists
set srandom_r d_srandom_r
eval $inlibc
case "$d_srandom_r" in
"$define")
hdrs="$i_systypes sys/types.h define stdio.h $i_stdlib stdlib.h"
case "$d_srandom_r_proto:$susetheads" in
":define") d_srandom_r_proto=define
set d_srandom_r_proto srandom_r $hdrs
eval $hasproto ;;
*) ;;
esac
case "$d_srandom_r_proto" in
define)
case "$srandom_r_proto" in
"|0) try='int srandom_r(unsigned int, struct random_data*);'
./protochk "$extern_C $try" $hdrs && srandom_r_proto=I_TS ;;
esac
case "$srandom_r_proto" in
"|0) d_srandom_r=undef
srandom_r_proto=0
echo "Disabling srandom_r, cannot determine prototype."
>&4 ;;
* ) case "$srandom_r_proto" in
REENTRANT_PROTO*) ;;
*) srandom_r_proto="REENTRANT_PROTO_ $srandom_r_proto" ;;
esac
echo "Prototype: $try" ;;
esac
;;
*) case "$susetheads" in
define) echo "srandom_r has no prototype, not using it." >&4 ;;
esac
d_srandom_r=undef
srandom_r_proto=0
;;
esac
;;
*) srandom_r_proto=0

```

```
;;
esac
```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/threads/d_srandom_r.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: Warn_v7ND.U 1 2006-08-24 12:32:52Z rmanfredi $
```

```
?RCS:
```

```
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
```

```
?RCS:
```

```
?RCS: You may redistribute only under the terms of the Artistic Licence,
```

```
?RCS: as specified in the README file that comes with the distribution.
```

```
?RCS: You may reuse parts of this distribution only within the terms of
```

```
?RCS: that same Artistic Licence; a copy of which may be found at the root
```

```
?RCS: of the source tree for dist 4.0.
```

```
?RCS:
```

```
?RCS: $Log: Warn_v7ND.U,v $
```

```
?RCS: Revision 3.0.1.1 1994/10/29 16:01:46 ram
```

```
?RCS: patch36: call ./v7 explicitly instead of relying on PATH
```

```
?RCS:
```

```
?RCS: Revision 3.0 1993/08/18 12:05:18 ram
```

```
?RCS: Baseline for dist 3.0 netwide release.
```

```
?RCS:
```

```
?X:
```

```
?X: This unit warns V7 sites that they may not have a non-blocking read.
```

```
?X: This unit needs to be mentioned in End.U to get included.
```

```
?X:
```

```
?MAKE:Warn_v7ND: package Guess
```

```
?MAKE:-pick add $@ %<
```

```
: Warnings
```

```
if ./v7; then
```

```
cat
```

```
<<EOM
```

NOTE: many V7 systems do not have a way to do a non-blocking read. If you don't have any of FIONREAD, O_NDELAY, or rdchk(), the \$package package may not work as well as it might. It might not work at all.

```
EOM
```

```
fi
```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/Warn_v7ND.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: Copyright (c) 2000,2014 Jarkko Hietaniemi
```

?RCS:
?RCS: You may distribute under the terms of either the GNU General Public
?RCS: License or the Artistic License, as specified in the README file.
?RCS:
?MAKE:d_fpclassify d_fp_classify: Inlibc cat i_math Compile rm_try Setvar
?MAKE: -pick add \$@ %<
?X:the short story is that C99 says use fpclassify. But the story is confused
?X:by systems "partially C99" (or fully "pre C99") which either user fpclassify
?X:but with different return values, or they use fp_classify (with the expected)
?X:return values, or they use some other spelling of *fp*class* (sometimes even
?X:without the *fp* part), with yet another set(s) of return values ...
?S:d_fpclassify:
?S: This variable conditionally defines the HAS_FPCLASSIFY symbol, which
?S: indicates to the C program that the fpclassify() routine is available.
?S:.
?S:d_fp_classify:
?S: This variable conditionally defines the HAS_FP_CLASSIFY
symbol, which
?S: indicates to the C program that the fp_classify() routine is available.
?S:.
?C:HAS_FPCLASSIFY:
?C: This symbol, if defined, indicates that the fpclassify routine is
?C: available to classify doubles. Available for example in HP-UX.
?C: The returned values are defined in <math.h> and are
?C:
?C: FP_NORMAL Normalized
?C: FP_ZERO Zero
?C: FP_INFINITE Infinity
?C: FP_SUBNORMAL Denormalized
?C: FP_NAN NaN
?C:
?C:.
?C:HAS_FP_CLASSIFY:
?C: This symbol, if defined, indicates that the fp_classify routine is
?C: available to classify doubles. The values are defined in <math.h>
?C:
?C: FP_NORMAL Normalized
?C: FP_ZERO Zero
?C: FP_INFINITE Infinity
?C: FP_SUBNORMAL Denormalized
?C: FP_NAN NaN
?C:
?C:.
?H:#\$d_fpclassify HAS_FPCLASSIFY /**/
?H:#\$d_fp_classify HAS_FP_CLASSIFY /**/
?H:.
?LINT:set d_fpclassify
?LINT:set d_fp_classify

```

:
check for fpclassify
?X:classified (Comment by jhi)
?X:fpclassify i_math
?X:fp_classify i_math
?X:fpclass i_math i_jeefp i_fp
?X:fp_class i_math i_fp_class
?X: No i_fp_class yet. But the systems that have
?X: this (Tru64 and IRIX) both had <fp_class.h>
?X:class i_math
echo "Checking to see if you have fpclassify..." >&4
$cat >try.c <<EOCP
#$i_math I_MATH
#ifdef I_MATH
#include <math.h>
#endif
int main() { return fpclassify(1.0) == FP_NORMAL ? 0 : 1; }
EOCP
set try
if eval $compile; then
val="$define"
echo "You have fpclassify."
else
val="$undef"
echo "You do not have fpclassify."
fi
$rm_try
set d_fpclassify
eval $setvar

```

```

: see if fp_classify exists
set fp_classify d_fp_classify
eval $inlibc

```

Found in path(s):

```

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/perl/d_fpclassify.U

```

No license file was found, but licenses were detected in source scan.

```

?RCS: $Id: d_portable.U,v 3.0.1.2 1995/01/11 15:28:52 ram Exp $
?RCS:
?RCS: Copyright (c) 1991-1993, Raphael Manfredi
?RCS:
?RCS: This file is included with or a derivative work of a file included
?RCS: with the metaconfig program of Raphael Manfredi's "dist" distribution.
?RCS: In accordance with clause 7 of dist's modified Artistic License:
?RCS:
?RCS: You may distribute under the terms of either the GNU General Public

```

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?RCS: \$Log: d_portable.U,v \$

?RCS: Revision 3.0.1.2 1995/01/11 15:28:52 ram

?RCS: patch45: executable path stripping moved to the end in Config_sh.U

?RCS:

?RCS: Revision 3.0.1.1 1993/12/15 08:21:17 ram

?RCS: patch15: did not strip variables properly when needed

?RCS: patch15: now also strips down variables from trylist

?RCS:

?RCS: Revision 3.0 1993/08/18 12:06:48 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?X:

This is the same as the dist version, except I don't bother

?X: prompting people since it makes no difference for perl5,

?X: and only confuses people.

?X:

?X: The Loc unit is wanted to get the definition of all the locating variables.

?X:

?MAKE:d_portable: Loc Oldconfig

?MAKE: -pick add \$@ %<

?S:d_portable:

?S: This variable conditionally defines the PORTABLE symbol, which

?S: indicates to the C program that it should not assume that it is

?S: running on the machine it was compiled on.

?S:.

?C:PORTABLE:

?C: This symbol, if defined, indicates to the C program that it should

?C: not assume that it is running on the machine it was compiled on.

?C: The program should be prepared to look up the host name, translate

?C: generic filenames, use PATH, etc.

?C:.

?H:#\$d_portable PORTABLE /**/

?H:.

?D:d_portable="

: decide how portable to be. Allow command line overrides.

case "\$d_portable" in

"\$undef") ;;

*) d_portable="\$define" ;;

esac

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_portable.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_setpwent.U,v \$

?RCS:
?RCS: Copyright (c) 1998 Andy Dougherty
?RCS:
?RCS: You may distribute under the terms of either the GNU General Public
?RCS: License or the Artistic License, as specified in the README file.
?RCS:
?RCS: \$Log: d_setpwent.U,v \$
?RCS:
?MAKE:d_setpwent: Inlibc
?MAKE: -pick add \$@ %<
?S:d_setpwent:
?S: This variable conditionally defines the HAS_SETPWENT symbol, which
?S: indicates to the C program that the setpwent() routine is available
?S: for initializing sequential access to the passwd database.
?S:.
?C:HAS_SETPWENT:
?C: This symbol, if defined, indicates that the setpwent routine is
?C: available for initializing sequential access of the passwd database.
?C:.
?H:#\$d_setpwent HAS_SETPWENT /**/
?H:.
?LINT:set d_setpwent
: see if setpwent exists
set setpwent d_setpwent
eval \$inlibc

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/modified/d_setpwent.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: prefshell.U 1 2006-08-24 12:32:52Z rmanfredi \$
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: \$Log: prefshell.U,v \$
?RCS: Revision 3.0.1.2 1994/10/29 16:28:13 ram
?RCS: patch36: added SHELL temporary since metalint now sees \${SHELL}
?RCS:
?RCS: Revision 3.0.1.1 1993/09/13 16:11:47 ram
?RCS: patch10: non-portable var substitution was used (WAD)
?RCS:

```

?RCS: Revision 3.0 1993/08/18 12:09:34 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:prefshell: cat package Getfile Oldconfig ksh csh bash
?MAKE: -pick add $@ %<
?S:prefshell:
?S: This
    variable contains the eventual value of the PREFSHELL symbol,
?S: which contains the full name of the preferred user shell on this
?S: system. Usual values are /bin/csh, /bin/ksh, /bin/sh.
?S:.
?C:PREFSHELL:
?C: This symbol contains the full name of the preferred user shell on this
?C: system. Usual values are /bin/csh, /bin/ksh, /bin/sh.
?C:.
?H:#define PREFSHELL "$prefshell" /**/
?H:.
?T:SHELL
: find out which shell people like to use most
case "$prefshell" in
")
    case "$ksh $bash $csh" in
*/ksh*) dflt="$ksh" ;;
*/bash*) dflt="$bash" ;;
*/csh*) dflt="$csh" ;;
*) dflt='/bin/sh' ;;
    esac
;;
*) dflt="$prefshell";;
    esac
?X: Some shells (Ultrix) do not understand ${SHELL:-/bin/sh}, sigh!
$cat <<EOM

```

Give the full path name of the shell most people like to use on your system. This will be used by \$package whenever the user wants to get a shell escape (for instance) and is not necessarily the same as the shell you are currently using (\${SHELL:-/bin/sh}).

```

EOM
fn=f/~
rp='Preferred
shell to be used?'
./getfile
prefshell=$ans

```

Found in path(s):

```

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/prefshell.U

```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: d_setservent_r.U,v 0RCS:
?RCS: Copyright (c) 2002,2003 Jarkko Hietaniemi
?RCS:
?RCS: You may distribute under the terms of either the GNU General Public
?RCS: License or the Artistic License, as specified in the README file.
?RCS:
?RCS: Generated by the reentr.pl from the Perl 5.8 distribution.
?RCS:
?MAKE:d_setservent_r setservent_r_proto: Inlibc Protochk Hasproto i_systypes \
  usethreads i_netdb extern_C
?MAKE: -pick add $@ %<
?S:d_setservent_r:
?S: This variable conditionally defines the HAS_SETSERVENT_R symbol,
?S: which indicates to the C program that the setservent_r()
?S: routine is available.
?S:.
?S:setservent_r_proto:
?S: This variable encodes the prototype of setservent_r.
?S: It is zero if d_setservent_r is undef, and one of the
?S: REENTRANT_PROTO_T_ABC macros of reentr.h if d_setservent_r
?S: is defined.
?S:.
?C:HAS_SETSERVENT_R:
?C: This symbol, if defined, indicates that the setservent_r routine
?C: is
  available to setservent re-entrantly.
?C:.
?C:SETSERVENT_R_PROTO:
?C: This symbol encodes the prototype of setservent_r.
?C: It is zero if d_setservent_r is undef, and one of the
?C: REENTRANT_PROTO_T_ABC macros of reentr.h if d_setservent_r
?C: is defined.
?C:.
?H:#$d_setservent_r HAS_SETSERVENT_R /**/
?H:#define SETSERVENT_R_PROTO $setservent_r_proto /**/
?H:.
?T:try hdrs d_setservent_r_proto
: see if setservent_r exists
set setservent_r d_setservent_r
eval $inlibc
case "$d_setservent_r" in
"$define")
  hdrs="$i_systypes sys/types.h define stdio.h $i_netdb netdb.h"
  case "$d_setservent_r_proto:$usethreads" in
":define") d_setservent_r_proto=define
  set d_setservent_r_proto setservent_r $hdrs
```

```

eval $hasproto ;;
*) ;;
esac
case "$d_setservent_r_proto" in
define)
case "$setservent_r_proto" in
"|0) try='int setservent_r(int, struct servent_data*);'
./protochk "$extern_C $try" $hdrs && setservent_r_proto=I_ID ;;
esac
case "$setservent_r_proto" in
"|0) try='void
setservent_r(int, struct servent_data*);'
./protochk "$extern_C $try" $hdrs && setservent_r_proto=V_ID ;;
esac
case "$setservent_r_proto" in
"|0) d_setservent_r=undef
setservent_r_proto=0
echo "Disabling setservent_r, cannot determine prototype." >&4 ;;
* ) case "$setservent_r_proto" in
REENTRANT_PROTO*) ;;
*) setservent_r_proto="REENTRANT_PROTO_$setservent_r_proto" ;;
esac
echo "Prototype: $try" ;;
esac
;;
*) case "$usethreads" in
define) echo "setservent_r has no prototype, not using it." >&4 ;;
esac
d_setservent_r=undef
setservent_r_proto=0
;;
esac
;;
*) setservent_r_proto=0
;;
esac

```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/threads/d_setservent_r.U
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: \$Log: Csym.U,v \$
?RCS: Revision 3.0.1.4 1995/07/25 13:36:29 ram
?RCS: patch56: re-arranged compile line to include ldflags before objects
?RCS: patch56: added quotes for OS/2 support
?RCS:
?RCS: Revision 3.0.1.3 1995/05/12 12:00:33 ram
?RCS: patch54: fixed C test program to bypass gcc builtin type checks (ADO)
?RCS:
?RCS: Revision 3.0.1.2 1994/10/31 09:34:13 ram
?RCS: patch44: added Options to the MAKE line since it's no longer in Init.U
?RCS:
?RCS: Revision 3.0.1.1 1993/08/25 14:00:05 ram
?RCS:
patch6: added ldflags as a conditional dependency and to compile line
?RCS: patch6: a final double quote was missing in csym variable after eval
?RCS:
?RCS: Revision 3.0 1993/08/18 12:04:50 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:Csym: Options contains libc libs runnm +cc +ccflags +ldflags rm
?MAKE: -pick add \$@ %<
?LINT:define csym
?LINT:use libc
?S:csym:
?S: This shell variable is used internally by Configure to check
?S: whether a given C symbol is defined or not. A typical use is:
?S: set symbol result [-fva] [previous]
?S: eval \$csym
?S: That will set result to 'true' if the function [-f], variable [-v]
?S: or array [-a] is defined, 'false' otherwise. If a previous value is
?S: given and the -r flag was provided on the command line, that value
?S: is reused without questioning.
?S:.
?V:csym
?T:tval tx tlook tf tdc tc
: is a C symbol defined?
csym='tlook=\$1;
case "\$3" in
-v) tf=libc.tmp; tc=""; tdc="";;
-a) tf=libc.tmp; tc="[0]"; tdc="[]";;
*) tlook="^\$1\\$";
tf=libc.list; tc=""; tdc="()";;
esac;
tx=yes;

```

case "$reusel-$4" in
true-) ;;
true-*) tx=no; eval "tval=\$$4"; case "$tval" in "") tx=yes;; esac;;
esac;
case "$tx" in
yes)
case "$runm" in
true)
if $contains $tlook $tf >/dev/null 2>&1;
then tval=true;
else tval=false;
fi;;
*)
?X:
?X: We use 'char' instead of 'int' to try to circumvent overzealous
?X: optimizing compilers using built-in prototypes for commonly used
?X: routines to complain when seeing a different external declaration. For
?X: instance, gcc 2.6.3 fails if we use 'int' and we attempt a test against
?X: memcpy() on machines where sizeof(int) == sizeof(char *) (the usual return
?X: type), the compiler assuming it's a built-in declaration given that the
?X: returned size matches. At least with 'char' we are safe! -- RAM, for ADO
?X:
?X: Let's thank GNU cc for making our lives so easy! :-)
?X: (An alternative for the future would be to use our knowledge about gcc
?X: to force a -fno-builtin option in the
?X: compile test, in case the 'char'
?X: trick is obsoleted by future gcc releases). -- RAM
?X:
?X: Lastly, gcc 3.4 optimizes &missing == 0 away, so we use + 2 instead now.
?X: The GNU folks like to do weird things, don't they? -- RAM, 2004-06-05
?X:
echo "extern char $1$tdc; int main() { return &$1$tc + 2; }" > t.c;
if $cc $ccflags $ldflags -o t t.c $libs >/dev/null 2>&1;
then tval=true;
else tval=false;
fi;
$rm -f t t.c;;
esac;;
*)
case "$tval" in
$define) tval=true;;
*) tval=false;;
esac;;
esac;
eval "$2=$tval"

```

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-

debian-perl-5.26.1/dist/U/Csym.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: i_sysstatvfs.U,v \$

?RCS:

?RCS: Copyright (c) 1999 Jarkko Hietaniemi

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?MAKE:i_sysstatvfs: Inhdr Hasfield

?MAKE: -pick add \$@ %<

?S:i_sysstatvfs:

?S: This variable conditionally defines the I_SYSSTATVFS symbol,

?S: and indicates whether a C program should include <sys/statvfs.h>.

?S:.

?C:I_SYS_STATVFS:

?C: This symbol, if defined, indicates that <sys/statvfs.h> exists and

?C: should be included.

?C:.

?H:#\$i_sysstatvfs I_SYS_STATVFS /**/

?H:.

?LINT:set i_sysstatvfs

: see if this is a sys/statvfs.h system

set sys/statvfs.h i_sysstatvfs

eval \$inhdr

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-

debian-perl-5.26.1/U/perl/i_sysstatvfs.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_setrgid.U 1 2006-08-24 12:32:52Z rmanfredi \$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic Licence,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic Licence; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: d_setrgid.U,v \$

?RCS: Revision 3.0 1993/08/18 12:07:14 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?MAKE:d_setrgid: Inlibc

?MAKE: -pick add \$@ %<

?S:d_setgid:

?S: This variable conditionally defines the HAS_SETRGID symbol, which

?S: indicates to the C program that the setrgid() routine is available

?S: to change the real gid of the current program.

?S:.

?C:HAS_SETRGID (SETRGID):

?C: This symbol, if defined, indicates that the setrgid
routine is available

?C: to change the real gid of the current program.

?C:.

?H:#\$d_setgid HAS_SETRGID /**/

?H:.

?LINT:set d_setgid

: see if setrgid exists

set setrgid d_setgid

eval \$inlibc

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/d_setgid.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: Setvar.U 1 2006-08-24 12:32:52Z rmanfredi \$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic Licence,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic Licence; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: Setvar.U,v \$

?RCS: Revision 3.0.1.1 1994/10/29 15:58:28 ram

?RCS: patch36: call ./whoa explicitly instead of relying on PATH

?RCS:

?RCS: Revision 3.0 1993/08/18 12:05:16 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?X:

?X: This unit produces a variable that is intended to be eval'ed in

?X: order to define/undefine a symbol. A consistency check is made

?X: regarding any previous value and a warning is issued if there

?X: is any discrepancy.

?X:

?X:

To use it, say:

?X: val=<value>

```

?X: set d_variable
?X: eval $setvar
?X:
?MAKE:Setvar: Whoa
?MAKE: -pick add $@ %<
?LINT:define setvar
?S:setvar:
?S: This shell variable is used internally by Configure to set a value
?S: to a given symbol that is defined or not. A typical use is:
?S:  val=<value computed>
?S: set d_variable
?S: eval $setvar
?S: That will print a message in case the $val value is not the same
?S: as the previous value of $d_variable.
?S:.
?V:setvar:val
?T:var was td tu
: function used to set '$1' to '$val'
setvar='var=$1; eval "was=\${$1}"; td=$define; tu=$undef;
case "$val$was" in
$define$undef) . ./whoa; eval "$var=\$td";;
$undef$define) . ./whoa; eval "$var=\$tu";;
*) eval "$var=$val";;
esac'

```

Found in path(s):

```

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/Setvar.U

```

No license file was found, but licenses were detected in source scan.

```

?RCS: $Id: d_SHM_MAC.U 1 2006-08-24 12:32:52Z rmanfredi $

```

```

?RCS:

```

```

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

```

```

?RCS:

```

```

?RCS: You may redistribute only under the terms of the Artistic Licence,

```

```

?RCS: as specified in the README file that comes with the distribution.

```

```

?RCS: You may reuse parts of this distribution only within the terms of

```

```

?RCS: that same Artistic Licence; a copy of which may be found at the root

```

```

?RCS: of the source tree for dist 4.0.

```

```

?RCS:

```

```

?RCS: $Log: d_SHM_MAC.U,v $

```

```

?RCS: Revision 3.0 1993/08/18 12:05:41 ram

```

```

?RCS: Baseline for dist 3.0 netwide release.

```

```

?RCS:

```

```

?MAKE:d_SHM_MAC d_SHM_PRM d_SHM_SEG d_SHM_IMMU: cat d_shm test rm +cc +ccflags

```

```

?MAKE: -pick add $@ %<

```

```

?S:d_SHM_MAC:

```

```

?S: Sometimes, the SHMLBA manifest needs sys/sysmacros.h, usually for

```

?S: the ctob() macro.

?S:.

?S:d_SHM_PRM:

?S: Sometimes, the SHMLBA manifest needs sys/param.h, usually for the

?S: NBPC constant.

?S:.

?S:d_SHM_SEG:

?S: Sometimes,

the SHMLBA manifest needs sys/seg.h, usually for the

?S: SNUMSHFT constant.

?S:.

?S:d_SHM_IMMU:

?S: Sometimes, the SHMLBA manifest needs sys/immu.h, usually for the

?S: stob() macro.

?S:.

?C:SHMLBA_WANTS_SYSMACROS:

?C: This value tells us to include <sys/sysmacros.h> because SHMLBA

?C: needs something from there, probably the ctob() macro.

?C:.

?C:SHMLBA_WANTS_PARAM:

?C: This value tells us to include <sys/param.h> because SHMLBA needs

?C: something from there, probably the NBPC constant.

?C:.

?C:SHMLBA_WANTS_SEG:

?C: This value tells us to include <sys/seg.h> because SHMLBA needs

?C: something from there, probably the SNUMSHFT constant.

?C:.

?C:SHMLBA_WANTS_IMMU:

?C: This value tells us to include <sys/immu.h> because SHMLBA needs

?C: something from there, probably the stob() macro. (tower_600 only?)

?C:.

?H:#\$d_SHM_MAC SHMLBA_WANTS_SYSMACROS /* SHMLBA wants ctob()? */

?H:#\$d_SHM_PRM SHMLBA_WANTS_PARAM /* SHMLBA wants NBPC? */

?H:#\$d_SHM_SEG SHMLBA_WANTS_SEG /* SHMLBA wants
SNUMSHFT? */

?H:#\$d_SHM_IMMU SHMLBA_WANTS_IMMU /* SHMLBA wants stob()? */

?H:.

?T:flags D_sys_immu D_sys_seg D_sys_sysmacros D_sys_param

: check for SHMLBA braindamage

d_SHM_MAC="\$undef"

d_SHM_PRM="\$undef"

d_SHM_SEG="\$undef"

d_SHM_IMMU="\$undef"

if \$test "\$d_shm" = "\$define" ; then

echo " "

\$cat >&4 <<EOM

Checking to see if SHMLBA needs additional headers.

The headers I'll be checking are:

sys/macros.h (for the ctob() macro)
sys/param.h (for NBPC)
sys/seg.h (for SNUMSHFT)
sys/immu.h (for the stob() macro)

EOM

```
$cat >shm_mac.c <<'EOCP'  
#include <sys/types.h>  
#include <sys/ipc.h>  
#include <sys/shm.h>  
#ifdef I_SYS_IMMU  
#include <sys/immu.h>  
#endif  
#ifdef I_SYS_SYSMACROS  
#include <sys/sysmacros.h>  
#endif  
#ifdef I_SYS_PARAM  
#include <sys/param.h>  
#endif  
#ifdef I_SYS_SEG  
#include <sys/seg.h>  
#endif  
  
int main() {  
    int foo = SHMLBA ;  
}  
EOCP  
flags='xxx'  
for D_sys_immu in "-DI_SYS_IMMU"; do  
for D_sys_seg in "-DI_SYS_SEG"; do  
for D_sys_sysmacros in "-DI_SYS_SYSMACROS";  
do  
for D_sys_param in "-DI_SYS_PARAM"; do  
case "$flags" in  
'xxx')  
case "$D_sys_immu$D_sys_param$D_sys_sysmacros$D_sys_seg" in  
")  
echo "Trying it normally..."  
;;  
*)  
echo "Trying $D_sys_immu $D_sys_param $D_sys_sysmacros $D_sys_seg"  
;;  
esac  
if $cc $ccflags \  
$D_sys_immu $D_sys_param $D_sys_sysmacros $D_sys_seg \  
-o shm_mac shm_mac.c >/dev/null 2>&1 ; then  
set X $D_sys_immu $D_sys_param $D_sys_sysmacros $D_sys_seg
```

```

shift
flags="$*"
echo "Succeeded with $flags"
fi
;;
esac
done
done
done
done
case "$flags" in
xxx)
echo "I don't know how to keep SHMLBA happy. Good luck!"
;;
esac
case "$flags" in
*I_SYS_PARAM*) d_SHM_PRM="$define";;
esac
case "$flags" in
*I_SYS_SYSMACROS*) d_SHM_MAC="$define";;
esac
case "$flags" in
*I_SYS_SEG*) d_SHM_SEG="$define";;
esac
case "$flags" in
*I_SYS_IMMU*) d_SHM_IMMU="$define";;
esac
fi
$rm -f shm_mac*

```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/d_SHM_MAC.U
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_gethbyad.U,v \$

?RCS:

?RCS: Copyright (c) 1998 Andy Dougherty

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?MAKE:d_gethbyaddr: Inlibc

?MAKE: -pick add \$@ %<

?S:d_gethbyaddr:

?S: This variable conditionally defines the HAS_GETHOSTBYADDR symbol, which

?S: indicates to the C program that the gethostbyaddr() routine is available

?S: to look up hosts by their IP addresses.

?S:.

?C:HAS_GETHOSTBYADDR:

?C: This symbol, if defined, indicates that the gethostbyaddr() routine is

?C: available to look up hosts by their IP addresses.

?C:.

?H:#\$d_gethbyaddr HAS_GETHOSTBYADDR /**/

?H:.

?LINT:set d_gethbyaddr

: see if gethostbyaddr exists

set gethostbyaddr d_gethbyaddr

eval \$inlibc

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/modified/d_gethbyad.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: locdist.U 1 2006-08-24 12:32:52Z rmanfredi \$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic Licence,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic Licence; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: locdist.U,v \$

?RCS: Revision 3.0.1.1 1994/05/06 15:09:20 ram

?RCS: patch23: added support for multi-state regions (WED)

?RCS:

?RCS: Revision 3.0 1993/08/18 12:09:06 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?MAKE:locdist orgdist citydist statedist multistatedist cntrydist contdist: \
test newslibexp cat Myread Oldconfig

?MAKE: -pick add \$@ %<

?S:locdist:

?S: This variable contains the eventual value of the LOCDIST symbol,

?S: which

is the local organization's distribution name for news.

?S:.

?S:orgdist:

?S: This variable contains the eventual value of the ORGDIST symbol,

?S: which is the organization's distribution name for news.

?S:.

?S:citydist:

?S: This variable contains the eventual value of the CITYDIST symbol,

?S: which is the city's distribution name for news.
?S:.
?S:statedist:
?S: This variable contains the eventual value of the STATEDIST symbol,
?S: which is the state's or province's distribution name for news.
?S:.
?S:multistatedist:
?S: This variable contains the eventual value of the MULTISTATEDIST symbol,
?S: which is the news distribution code for multi-state region.
?S:.
?S:centrydist:
?S: This variable contains the eventual value of the CENTRYDIST symbol,
?S: which is the country's distribution name for news.
?S:.
?S:contdist:
?S: This variable contains the eventual value of the CONTDIST symbol,
?S: which is the continent's distribution name for news.
?S:.
?C:LOCDIST:
?C: This symbol contains the
distribution name for the news system that
?C: restricts article distribution to the local organization.
?C:.
?C:ORGDIST:
?C: This symbol contains the distribution name for the news system that
?C: restricts article distribution to the organization.
?C:.
?C:CITYDIST:
?C: This symbol contains the distribution name for the news system that
?C: restricts article distribution to the city.
?C:.
?C:STATEDIST:
?C: This symbol contains the distribution name for the news system that
?C: restricts article distribution to the state or province.
?C:.
?C:MULTISTATEDIST:
?C: This symbol contains the distribution name for the news system that
?C: restricts article distribution to a multi-state region.
?C:.
?C:CENTRYDIST:
?C: This symbol contains the distribution name for the news system that
?C: restricts article distribution to the country.
?C:.
?C:CONTDIST:
?C: This symbol contains the distribution name for the news system that
?C: restricts article distribution to the continent.
?C:.
?H:#define LOCDIST

```

"$locdist" /**/
?H:#define ORGDIST "$orgdist" /**/
?H:#define CITYDIST "$citydist" /**/
?H:#define MULTISTATEDIST "$multistatedist" /**/
?H:#define STATEDIST "$statedist" /**/
?H:#define CNTRYDIST "$cntrydist" /**/
?H:#define CONTDIST "$contdist" /**/
?H.:
: get the local distributions
$cat <<'EOH'

```

Distribution groups are the things you use on the Distribution line to limit where an article will go to. You are likely to be a member of several distribution groups, such as organization, city, state, province, country, continent, etc. For example, Los Angeles has the distribution code "la", New Jersey has the code "nj", and Europe has the code "eunet".

The categories you will be asked are:

```

local organization (Could be just one machine or a cluster or an office)
organization att, dec, kgb, ...
city la, ny, mosc, ...
state/province ca, nj, bc, ...
multi-state region pnw, ne, ...
country usa, can, rok, whatever
continent na (North America), asia, etc.

```

```

EOH
if $test
-f $newslibexp/distributions; then
case "$silent" in
true) ;;
*) dflt='Hit return to continue'
rp="
./myread
;;
esac
echo "Here is your distributions file:" >&4
echo " " >&4
$cat >&4 $newslibexp/distributions
echo " " >&4
fi
echo "Use 'none' for any distributions you don't have."
echo " "
case "$locdist" in
") dflt="none";;
*) dflt="$locdist";;
esac

```

```

rp="What is the distribution code for your local organization?"
./myread
locdist="$ans"
case "$orgdist" in
") dflt="none";;
*) dflt="$orgdist";;
esac
rp="What is the distribution code for your organization?"
./myread
orgdist="$ans"
case "$citydist" in
") dflt="none";;
*) dflt="$citydist";;
esac
rp="What is the distribution code for your city?"
./myread
citydist="$ans"
case "$statedist" in
") dflt="none";;
*) dflt="$statedist";;
esac
rp="What is the distribution code for your state/province?"
./myread
statedist="$ans"
case "$multistatedist" in
") dflt="none";;
*) dflt="$multistatedist";;
esac
rp="What is the
distribution code for your multi-state region?"
./myread
multistatedist="$ans"
case "$cntrydist" in
") dflt="none";;
*) dflt="$cntrydist";;
esac
rp="What is the distribution code for your country?"
./myread
cntrydist="$ans"
case "$contdist" in
") dflt="none";;
*) dflt="$contdist";;
esac
rp="What is the distribution code for your continent?"
./myread
contdist="$ans"
$cat <<'EOM'

```

If you have any other distribution groups you will need to edit Pnews and newsetup to add them.

EOM

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/locdist.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: rcs_branch.U 1 2006-08-24 12:32:52Z rmanfredi $
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: $Log: rcs_branch.U,v $
?RCS: Revision 3.0 1993/08/18 12:09:40 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:rcs_branch: Myread contains Loc
?MAKE: -pick add $@ %<
?S:rcs_branch:
?S: This variable will hold "true" if rcs can take the -b<revision>
?S: option, which can make Life Easier on those folks who like to run
?S: rcsdiff manually.
?S:.
?T:xxx
: Tra la la la la
echo " "
echo "Checking to see if RCS understands the -b switch..." >&4
xxx=`./loc
rcs " $pth`
case "$xxx" in
")
rcs_branch=false
echo "Oh. You don't seem to have RCS here."
;;
*)
rcs > rcsbranch.out 2>&1
if $contains 'b\[rev\]' rcsbranch.out >/dev/null 2>&1 ; then
rcs_branch=true
echo "Nice! Your RCS is spiffy!"
else
rcs_branch=false
```

```
echo "Well, at least you have RCS. You know, a newer version is available."  
fi  
;;  
esac
```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-  
debian-perl-5.26.1/dist/U/rcs_branch.U
```

No license file was found, but licenses were detected in source scan.

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?MAKE:d_exp2: Inlibc

?MAKE: -pick add \$@ %<

?S:d_exp2:

?S: This variable conditionally defines the HAS_EXP2 symbol, which

?S: indicates to the C program that the exp2() routine is available.

?S:.

?C:HAS_EXP2:

?C: This symbol, if defined, indicates that the exp2 routine is

?C: available to do the 2**x function.

?C:.

?H:#\$d_exp2 HAS_EXP2 /**/

?H:.

?LINT:set d_exp2

: see if exp2 exists

set exp2 d_exp2

eval \$inlibc

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-  
debian-perl-5.26.1/U/perl/d_exp2.U
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: vendorman1dir.U,v 1.1 1999/07/08 18:32:57 doughera Exp doughera \$

?RCS:

?RCS: Copyright (c) 1999, Andy Dougherty

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 3.0.

?RCS:

?RCS: \$Log: vendorman1dir.U,v \$

?RCS: Revision 1.1 1999/07/08 18:32:57 doughera

?RCS: Initial revision

```

?RCS:
?MAKE:vendorman1dir vendorman1direxp installvendorman1dir: man1dir Getfile \
  Oldconfig Setprefixvar Prefixit test vendorprefix prefix sed
?MAKE: -pick add $@ %<
?Y:TOP
?S:vendorman1dir:
?S: This variable contains the name of the directory for man1
?S: pages. It may have a ~ on the front.
?S: The standard distribution will put nothing in this directory.
?S: Vendors
  who distribute perl may wish to place their own
?S: man1 pages in this directory with
?S: MakeMaker Makefile.PL INSTALLDIRS=vendor
?S: or equivalent. See INSTALL for details.
?S:.
?S:vendorman1direxp:
?S: This variable is the ~name expanded version of vendorman1dir, so that you
?S: may use it directly in Makefiles or shell scripts.
?S:.
?D:installvendorman1dir="
?S:installvendorman1dir:
?S: This variable is really the same as vendorman1direxp but may differ on
?S: those systems using AFS. For extra portability, only this variable
?S: should be used in makefiles.
?S:.
?LINT:change prefixvar
?LINT:set installvendorman1dir
: Set the vendorman1dir variables
case "$vendorprefix" in
") vendorman1dir="
  vendorman1direxp="
  ;;
*) : determine where vendor-supplied manual pages go.
  case "$vendorman1dir" in
  ") dflt=`echo "$man1dir" | $sed "s#^$prefix#$vendorprefix#"` ;;
  *) dflt=$vendorman1dir ;;
  esac
  case "$dflt" in
  "|") dflt=none ;;
  esac
  fn=nd~+
  rp='Pathname for
  the vendor-supplied manual section 1 pages?'
  ./getfile
  vendorman1dir="$ans"
  vendorman1direxp="$ansexp"
  ;;
esac

```

```
: Use '' for none so value is preserved next time through Configure
$test X"$vendorman1dir" = "X" && vendorman1dir=''
prefixvar=vendorman1dir
./installprefix
```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/installdirs/vendorman1dir.U
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 2005 H.Merijn Brand

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?MAKE:d_clearenv: Inlibc

?MAKE:-pick add \$@ %<

?S:d_clearenv:

?S: This variable conditionally defines the HAS_CLEARENV symbol, which

?S: indicates to the C program that the clearenv () routine is available.

?S:.

?C:HAS_CLEARENV:

?C: This symbol, if defined, indicates that the clearenv () routine is

?C: available for use.

?C:.

?H:#\$d_clearenv HAS_CLEARENV /**/

?H:.

?LINT:set d_clearenv

: see if clearenv exists

set clearenv d_clearenv

eval \$inlibc

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/perl/d_clearenv.U
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: Compile.U,v \$

?RCS:

?RCS: Copyright (c) 1998 Andy Dougherty

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?RCS:

?X:

?X: This unit is just a quick shorthand for the compile command

?X: to be used in all the other metaconfig units.

?X:

?MAKE:Compile: +cc +optimize +ccflags +ldflags +libs test

?MAKE: -pick add \$@ %<

?LINT:extern usedevel

?LINT:define compile compile_ok

?V:compile compile_ok mc_file

?S:compile:

?S: This shell variable is used internally by Configure to provide

?S: a convenient shorthand for the typical compile command, namely

?S: \$cc \$optimize \$ccflags \$ldflags -o \$1 \$1.c \$libs > /dev/null 2>&1

?S: Note that the output filename does not include the _exe

?S: extension. Instead we assume that the linker will be

?S: "helpful" and automatically appending the correct suffix.

?S: OS/2 users

will apparently need to supply the -Zexe flag to

?S: get this behavior.

?S:

?S: To use this variable, say something like:

?S: echo 'int main() { exit(0); }' > try.c

?S: set try

?S: if eval \$compile; then

?S: echo "success" # and do whatever . . .

?S: else

?S: echo "failure" # and do whatever . . .

?S: fi

?S: To add extra flags cc flags (e.g. -DWHATEVER) just put them

?S: in \$*, e.g.

?S: set try -DTRY_THIS_FLAG

?S:.

?S:compile_ok:

?S: This shell variable is used internally by Configure to provide

?S: a convenient shorthand for the typical compile command that you

?S: expect to work ok. It is the same as \$compile, except we

?S: deliberately let the user see any error messages.

?S:.

: define a shorthand compile call

```
compile='
mc_file=$1;
shift;
case "$usedevel" in $define|true|[yY]*) if $test ! -f "${mc_file}.c"; then
echo "Internal Configure script bug - compiler test file ${mc_file}.c is missing. Please report this to
perlbug@perl.org" >&4;
exit 1;
fi;
esac;
$cc -o ${mc_file}
```

```
$optimize $ccflags $ldflags $* ${mc_file}.c $libs > /dev/null 2>&1;
: define a shorthand compile call for compilations that should be ok.
compile_ok='
mc_file=$1;
shift;
$cc -o ${mc_file} $optimize $ccflags $ldflags $* ${mc_file}.c $libs;'
```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/compline/Compile.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: d_setprior.U 1 2006-08-24 12:32:52Z rmanfredi $
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: $Log: d_setprior.U,v $
?RCS: Revision 3.0 1993/08/18 12:07:11 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:d_setprior: Inlibc
?MAKE: -pick add $@ %<
?S:d_setprior:
?S: This variable conditionally defines HAS_SETPRIORITY if setpriority()
?S: is available to set a process's priority.
?S:.
?C:HAS_SETPRIORITY (SETPRIORITY):
?C: This symbol, if defined, indicates that the setpriority routine is
?C: available to set a process's priority.
?C:.
?H:#$d_setprior
HAS_SETPRIORITY /**/
?H:.
?LINT:set d_setprior
: see if setpriority exists
set setpriority d_setprior
eval $inlibc
```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/d_setprior.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: i_sysmount.U,v $
?RCS:
?RCS: Copyright (c) 1999 Jarkko Hietaniemi
?RCS:
?RCS: You may distribute under the terms of either the GNU General Public
?RCS: License or the Artistic License, as specified in the README file.
?RCS:
?MAKE:i_sysmount: Inhdr Hasfield
?MAKE:-pick add $@ %<
?S:i_sysmount:
?S: This variable conditionally defines the I_SYSMOUNT symbol,
?S: and indicates whether a C program should include <sys/mount.h>.
?S:.
?C:I_SYS_MOUNT:
?C: This symbol, if defined, indicates that <sys/mount.h> exists and
?C: should be included.
?C:.
?H:#$i_sysmount I_SYS_MOUNT /**/
?H:.
?LINT:set i_sysmount
: see if this is a sys/mount.h system
set sys/mount.h i_sysmount
eval $inhdr
```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/perl/i_sysmount.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: d_getppid.U 1 2006-08-24 12:32:52Z rmanfredi $
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: Original Author: Andy Dougherty <doughera@lafcol.lafayette.edu>
?RCS:
?RCS: $Log: d_getppid.U,v $
?RCS: Revision 3.0.1.1 1994/08/29 16:07:45 ram
?RCS: patch32: created by ADO
?RCS:
?MAKE:d_getppid: Inlibc
```

?MAKE: -pick add \$@ %<
?S:d_getppid:
?S: This variable conditionally defines the HAS_GETPPID symbol, which
?S: indicates to the C program that the getppid() routine is available
?S: to get the parent process ID.
?S:.
?C:HAS_GETPPID :
?C: This symbol,
if defined, indicates that the getppid routine is
?C: available to get the parent process ID.
?C:.
?H:#\$d_getppid HAS_GETPPID /**/
?H:.
?LINT:set d_getppid
: see if getppid exists
set getppid d_getppid
eval \$inlibc

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/d_getppid.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: h_fcntl.U 1 2006-08-24 12:32:52Z rmanfredi \$
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: \$Log: h_fcntl.U,v \$
?RCS: Revision 3.0 1993/08/18 12:08:12 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:h_fcntl: Nothing
?MAKE: -pick add \$@ %<
?S:h_fcntl:
?S: This is variable gets set in various places to tell i_fcntl that
?S: <fcntl.h> should be included.
?S:.
: Initialize h_fcntl
h_fcntl=false

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-

debian-perl-5.26.1/dist/U/h_fcntl.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: i_db.U,v 3.0.1.3 1995/07/25 14:10:22 ram Exp \$

?RCS:

?RCS: Copyright (c) 1991-1993, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 3.0.

?RCS:

?RCS: Original Author: Andy Dougherty <doughera@lafcol.lafayette.edu>

?RCS:

?RCS: \$Log: i_db.U,v \$

?RCS: Revision 3.0.1.3 1995/07/25 14:10:22 ram

?RCS: patch56: conditionally use const in test programs (ADO)

?RCS:

?RCS: Revision 3.0.1.2 1995/05/12 12:14:42 ram

?RCS: patch54: extended for more intimate DB probing (ADO)

?RCS:

?RCS: Revision 3.0.1.1 1994/08/29 16:21:50 ram

?RCS: patch32: created by ADO

?RCS:

?MAKE:i_db db_hashtype db_prefixtype \
db_version_major

db_version_minor db_version_patch : \
Inhdr +cc +ccflags rm_try contains cat \
Compile d_const libs sed run i_stdlib

?MAKE: -pick add \$@ %<

?S:i_db:

?S: This variable conditionally defines the I_DB symbol, and indicates

?S: whether a C program may include Berkeley's DB include file <db.h>.

?S:.

?S:db_hashtype:

?S: This variable contains the type of the hash structure element

?S: in the <db.h> header file. In older versions of DB, it was

?S: int, while in newer ones it is u_int32_t.

?S:.

?S:db_prefixtype:

?S: This variable contains the type of the prefix structure element

?S: in the <db.h> header file. In older versions of DB, it was

?S: int, while in newer ones it is size_t.

?S:.

?S:db_version_major:

?S: This variable contains the major version number of

?S: Berkeley DB found in the <db.h> header file.

?S:
?S:db_version_minor:
?S: This variable contains the minor version number of
?S: Berkeley DB found in the <db.h> header file.
?S: For DB version 1 this is always 0.
?S:.
?S:db_version_patch:
?S: This
variable contains the patch version number of
?S: Berkeley DB found in the <db.h> header file.
?S: For DB version 1 this is always 0.
?S:.
?C:I_DB:
?C: This symbol, if defined, indicates to the C program that it should
?C: include Berkeley's DB include file <db.h>.
?C:.
?C:DB_Prefix_t:
?C: This symbol contains the type of the prefix structure element
?C: in the <db.h> header file. In older versions of DB, it was
?C: int, while in newer ones it is u_int32_t.
?C:.
?C:DB_Hash_t:
?C: This symbol contains the type of the prefix structure element
?C: in the <db.h> header file. In older versions of DB, it was
?C: int, while in newer ones it is size_t.
?C:.
?C:DB_VERSION_MAJOR_CFG:
?C: This symbol, if defined, defines the major version number of
?C: Berkeley DB found in the <db.h> header when Perl was configured.
?C:.
?C:DB_VERSION_MINOR_CFG:
?C: This symbol, if defined, defines the minor version number of
?C: Berkeley DB found in the <db.h> header when Perl was configured.
?C: For
DB version 1 this is always 0.
?C:.
?C:DB_VERSION_PATCH_CFG:
?C: This symbol, if defined, defines the patch version number of
?C: Berkeley DB found in the <db.h> header when Perl was configured.
?C: For DB version 1 this is always 0.
?C:.
?H:#\$i_db I_DB /**/
?H:#define DB_Hash_t \$db_hashtype /**/
?H:#define DB_Prefix_t \$db_prefixtype /**/
?H:#define DB_VERSION_MAJOR_CFG \$db_version_major /**/
?H:#define DB_VERSION_MINOR_CFG \$db_version_minor /**/
?H:#define DB_VERSION_PATCH_CFG \$db_version_patch /**/
?H:.

```

?F:!try
?LINT:change libs
: see if this is a db.h system
set db.h i_db
eval $inhdr

case "$i_db" in
$define)
: Check db version.
echo " "
echo "Checking Berkeley DB version ..." >&4
$cat >try.c <<EOCP
#$d_const HASCONST
#ifndef HASCONST
#define const
#endif
#include <sys/types.h>
#include <stdio.h>
#$i_stdlib I_STDLIB
#ifdef I_STDLIB
#include <stdlib.h>
#endif
#include <db.h>
int main(int argc, char *argv[])
{
#ifdef DB_VERSION_MAJOR /* DB version >= 2 */

int Major, Minor, Patch ;
unsigned long Version ;
(void)db_version(&Major, &Minor, &Patch) ;
if (argc == 2) {
printf("%d %d %d %d %d %d\n",
DB_VERSION_MAJOR, DB_VERSION_MINOR, DB_VERSION_PATCH,
Major, Minor, Patch);
exit(0);
}
printf("You have Berkeley DB Version 2 or greater.\n");

printf("db.h is from Berkeley DB Version %d.%d.%d\n",
DB_VERSION_MAJOR, DB_VERSION_MINOR, DB_VERSION_PATCH);
printf("libdb is from Berkeley DB Version %d.%d.%d\n",
Major, Minor, Patch) ;

/* check that db.h & libdb are compatible */
if (DB_VERSION_MAJOR != Major || DB_VERSION_MINOR != Minor || DB_VERSION_PATCH != Patch) {
printf("db.h and libdb are incompatible.\n") ;
exit(3);
}
}

```

```

printf("db.h and libdb are compatible.\n");

Version = DB_VERSION_MAJOR * 1000000 + DB_VERSION_MINOR * 1000
+ DB_VERSION_PATCH;

/* needs to be >= 2.3.4 */
if (Version < 2003004) {
/* if (DB_VERSION_MAJOR ==
2 && DB_VERSION_MINOR == 0 && DB_VERSION_PATCH < 5) { */
printf("Perl needs Berkeley DB 2.3.4 or greater.\n");
    exit(2);
}

    exit(0);
#else
#if defined(_DB_H_) && defined(BTREEMAGIC) && defined(HASHMAGIC)
    if (argc == 2) {
        printf("1 0 0\n");
        exit(0);
    }
    printf("You have Berkeley DB Version 1.\n");
    exit(0); /* DB version < 2: the coast is clear. */
#else
    exit(1); /* <db.h> not Berkeley DB? */
#endif
#endif
}
EOCP
set try
if eval $compile_ok && $run ./try; then
    echo 'Looks OK.' >&4
    set ` $run ./try 1 `
    db_version_major=$1
    db_version_minor=$2
    db_version_patch=$3
else
    echo "I can't use Berkeley DB with your <db.h>. I'll disable Berkeley DB." >&4
    i_db=$undef
    case " $libs " in
    *"-ldb "*)
        : Remove db from list of libraries to use
        echo "Removing unusable -ldb from library list" >&4
        set `echo X $libs | $sed -e 's/-ldb //' -e 's/-ldb$//`
        shift
        libs="$*"
        echo "libs = $libs" >&4
    ;;

```

```

    esac
fi
$rm_try
;;
esac

@if
DB_Hash_t
case "$i_db" in
define)
: Check the return type needed for hash
echo " "
echo "Checking return type needed for hash for Berkeley DB ..." >&4
$cat >try.c <<EOCP
#$d_const HASCONST
#ifndef HASCONST
#define const
#endif
#include <sys/types.h>
#include <db.h>

#ifndef DB_VERSION_MAJOR
u_int32_t hash_cb (const void* ptr, size_t size)
{
}
HASHINFO info;
int main()
{
    info.hash = hash_cb;
}
#endif
EOCP
if $cc $ccflags -c try.c >try.out 2>&1 ; then
if $contains warning try.out >>/dev/null 2>&1 ; then
    db_hashtype='int'
else
    db_hashtype='u_int32_t'
fi
else
: XXX Maybe we should just give up here.
db_hashtype=u_int32_t
$cat try.out >&4
echo "Help: I can't seem to compile the db test program." >&4
echo "Something's wrong, but I'll assume you use $db_hashtype." >&4
fi
$rm_try
echo "Your version of Berkeley DB uses $db_hashtype for hash."
;;

```

```

*) db_hashtype=u_int32_t
;;
esac
@end
@if DB_Prefix_t
case "$i_db" in
define)
: Check the return type needed
for prefix
echo " "
echo "Checking return type needed for prefix for Berkeley DB ..." >&4
cat >try.c <<EOCP
#$d_const HASCONST
#ifndef HASCONST
#define const
#endif
#include <sys/types.h>
#include <db.h>

#ifndef DB_VERSION_MAJOR
size_t prefix_cb (const DBT *key1, const DBT *key2)
{
}
BTREEINFO info;
int main()
{
info.prefix = prefix_cb;
}
#endif
EOCP
if $cc $ccflags -c try.c >try.out 2>&1 ; then
if $contains warning try.out >>/dev/null 2>&1 ; then
db_prefixtype='int'
else
db_prefixtype='size_t'
fi
else
db_prefixtype='size_t'
: XXX Maybe we should just give up here.
$cat try.out >&4
echo "Help: I can't seem to compile the db test program." >&4
echo "Something's wrong, but I'll assume you use $db_prefixtype." >&4
fi
$rm_try
echo "Your version of Berkeley DB uses $db_prefixtype for prefix."
;;
*) db_prefixtype='size_t'
;;

```

esac
@end

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/i_db.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: i_syslog.U,v \$

?RCS:

?RCS: Copyright (c) 2000 Jarkko Hietaniemi

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?MAKE:i_syslog: Inhdr Hasfield

?MAKE: -pick add \$@ %<

?S:i_syslog:

?S: This variable conditionally defines the I_SYSLOG symbol,

?S: and indicates whether a C program should include <syslog.h>.

?S:.

?C:I_SYSLOG:

?C: This symbol, if defined, indicates that <syslog.h> exists and

?C: should be included.

?C:.

?H:#\$i_syslog I_SYSLOG /**/

?H:.

?LINT:set i_syslog

: see if this is a syslog.h system

set syslog.h i_syslog

eval \$inhdr

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/i_syslog.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: cf_who.U,v \$

?RCS: Revision 3.0.1.2 1997/02/28 15:28:50 ram

?RCS: patch61: new computation method avoiding use of temporary file

?RCS:

?RCS: Revision 3.0.1.1 1994/05/06 14:42:34 ram

?RCS: patch23: login name now computed the hard way

?RCS:

?RCS: Revision 3.0 1993/08/18 12:05:32 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?X:

?X: Oldconfig dependency is there to ensure computation occurs after old values

?X: from config.sh have been loaded, so that we can supersede them.

?X:

?MAKE:cf_time

cf_by: date Oldconfig

?MAKE: -pick add \$@ %<

?S:cf_time:

?S: Holds the output of the "date" command when the configuration file was

?S: produced. This is used to tag both config.sh and config_h.SH.

?S:.

?S:cf_by:

?S: Login name of the person who ran the Configure script and answered the

?S: questions. This is used to tag both config.sh and config_h.SH.

?S:.

?LINT:change LC_ALL LANGUAGE

: who configured the system

?X: Ensure English date -- Jarkko Hietaniemi

cf_time=`LC_ALL=C; LANGUAGE=C; export LC_ALL; export LANGUAGE; \$date 2>&1`

?X:

?X: Leave a white space between first two '(' for ksh. The sub-shell is needed

?X: on some machines to avoid the error message when logname is not found; e.g.

?X: on SUN-OS 3.2, (logname || whoami) would not execute whoami if logname was

?X: not found. Sigh!

?X:

?X: Convex had a broken logname executable which returned a non-zero status,

?X: and that broke the previous:

?X: cf_by=`(logname) 2>/dev/null || whoami) 2>&1`

?X: Switch to emergency

mode... -- RAM, 19/04/94

?X:

?X: Parentheses needed to avoid error message if the program does not exist.

?X: Uses case instead of \$test so it can be put before \$test is defined.

?X: Don't redirect to a file because on Ultrix (under script?) logname

?X: outputs a blank line first. This method will apparently work.

case "\$cf_by" in

"")

cf_by=`(logname) 2>/dev/null`

case "\$cf_by" in

```
""  
cf_by=`(whoami) 2>/dev/null`  
case "$cf_by" in  
"" ) cf_by=unknown ;;  
esac ;;  
esac ;;  
esac
```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/cf_who.U
```

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/modified/cf_who.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: ansi2knr.U,v 3.0.1.3 1994/05/06 15:11:49 ram Exp $
```

```
?RCS:
```

```
?RCS: Copyright (c) 1998 Andy Dougherty
```

```
?RCS:
```

```
?RCS: You may distribute under the terms of either the GNU General Public
```

```
?RCS: License or the Artistic License, as specified in the README file.
```

```
?RCS:
```

```
?MAKE:ansi2knr: prototype +cc +ccflags package
```

```
?MAKE: -pick add $@ %<
```

```
?S:ansi2knr:
```

```
?S: This variable is set if the user needs to run ansi2knr.
```

```
?S: Currently, this is not supported, so we just abort.
```

```
?S:.
```

```
?Y:TOP
```

```
: Check if ansi2knr is required
```

```
case "$prototype" in
```

```
"$define") ;;
```

```
*) ansi2knr='ansi2knr'
```

```
echo " "
```

```
cat <<EOM >&4
```

\$me: FATAL ERROR:

This version of \$package can only be compiled by a compiler that understands function prototypes. Unfortunately, your C compiler

```
$cc $ccflags
```

doesn't seem to understand them. Sorry about that.

If GNU cc is available for your system, perhaps you could try that instead.

Eventually, we hope to support building Perl

with pre-ANSI compilers.

If you would like to help in that effort, please contact <perlbug@perl.org>.

Aborting Configure now.

EOM

exit 2

::

esac

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/ansi2knr.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: d_csh.U,v \$

?RCS: Revision 3.0.1.1 1997/02/28 15:32:18 ram

?RCS: patch61: added full_csh to preserve the full path even when portable

?RCS:

?RCS: Revision 3.0 1993/08/18 12:05:53 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?MAKE:d_csh full_csh: csh Setvar

?MAKE: -pick add \$@ %<

?S:d_csh:

?S: This variable conditionally defines the CSH symbol, which

?S: indicates to the C program that the C-shell exists.

?S:.

?S:full_csh:

?S: This variable contains the full pathname to 'csh', whether

or

?S: not the user has specified 'portability'. This is only used

?S: in the compiled C program, and we assume that all systems which

?S: can share this executable will have the same full pathname to

?S: 'csh.'

?S:.

?C:HAS_CSH:

?C: This symbol, if defined, indicates that the C-shell exists.

?C:.

?C:CSH:

?C: This symbol, if defined, contains the full pathname of csh.

?C:.

?X: Previously, I just did \$d_csh CSH "\$full_csh", but that caused
?X: problems on VMS where the config.sh extraction program changes
?X: \$undef to a real cpp undef, and they then had #undef CSH ""
?X: which the compiler didn't like. It's easy to work around this,
?X: so I did. --AD 3/1998.
?X: And we don't want to define CSH if !HAS_CSH, but we don't want
?X: those lines in config.h if they don't need CSH, so protect with ?CSH
?X: and not ?%<. --RAM, 15/02/2004
?H: ?%<: # \$d_csh HAS_CSH /**/
?H: ?CSH: #ifdef HAS_CSH
?H: ?CSH: #define CSH "\$full_csh" /**/
?H: ?CSH: #endif
?H: .
?LINT: set d_csh
: get csh whereabouts
case
"\$csh" in
'csh') val="\$undef" ;;
*) val="\$define" ;;
esac
set d_csh
eval \$setvar
: Respect a hint or command line value for full_csh.
case "\$full_csh" in
") full_csh=\$csh ;;
esac

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/d_csh.U

No license file was found, but licenses were detected in source scan.

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?MAKE: d_llround: Inlibc

?MAKE: -pick add \$@ %<

?S: d_llround:

?S: This variable conditionally defines the HAS_LLROUND symbol, which

?S: indicates to the C program that the llround() routine is available

?S: to return the long long value nearest to x.

?S: .

?C: HAS_LLROUND:

?C: This symbol, if defined, indicates that the llround routine is

?C: available to return the nearest long long value.

?C: .

?H: # \$d_llround HAS_LLROUND /**/
?H: .

```
?LINT:set d_llround
: see if llround exists
set llround d_llround
eval $inlibc
```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/perl/d_llround.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: usenm.U,v 3.0.1.1 1997/02/28 16:26:40 ram Exp $
```

```
?RCS:
```

```
?RCS: Copyright (c) 1991-1993, Raphael Manfredi
```

```
?RCS:
```

```
?RCS: You may redistribute only under the terms of the Artistic License,
```

```
?RCS: as specified in the README file that comes with the distribution.
```

```
?RCS: You may reuse parts of this distribution only within the terms of
```

```
?RCS: that same Artistic License; a copy of which may be found at the root
```

```
?RCS: of the source tree for dist 3.0.
```

```
?RCS:
```

```
?RCS: $Log: usenm.U,v $
```

```
?RCS: Revision 3.0.1.1 1997/02/28 16:26:40 ram
```

```
?RCS: patch61: don't use nm with the GNU C library
```

```
?RCS: patch61: added support for Linux shared libs
```

```
?RCS:
```

```
?RCS: Revision 3.0 1993/08/18 12:09:57 ram
```

```
?RCS: Baseline for dist 3.0 netwide release.
```

```
?RCS:
```

```
?MAKE:usenm runnm nm_opt nm_so_opt: cat test Myread Oldconfig myuname grep \
```

```
nm d_gnulibc osname egrep rsrc
```

```
?MAKE: -pick add $@ %<
```

```
?S:usenm:
```

```
?S: This variable contains 'true' or 'false' depending
```

```
whether the
```

```
?S: nm extraction is wanted or not.
```

```
?S:.
```

```
?S:runnm:
```

```
?S: This variable contains 'true' or 'false' depending whether the
```

```
?S: nm extraction should be performed or not, according to the value
```

```
?S: of usenm and the flags on the Configure command line.
```

```
?S:.
```

```
?S:nm_opt:
```

```
?S: This variable holds the options that may be necessary for nm.
```

```
?S:.
```

```
?S:nm_so_opt:
```

```
?S: This variable holds the options that may be necessary for nm
```

```
?S: to work on a shared library but that can not be used on an
```

```
?S: archive library. Currently, this is only used by Linux, where
```

?S: nm --dynamic is *required* to get symbols from an ELF library which

?S: has been stripped, but nm --dynamic is *fatal* on an archive library.

?S: Maybe Linux should just always set usenm=false.

?S:.

: see if nm is to be used to determine whether a symbol is defined or not

?X: If there is enough inquiries, it might be worth to wait for the nm

?X: extraction. Otherwise, the C compilations might be a better deal.

?X:

?X: Don't bother if we're
using GNU libc -- skimo

?LINT:extern PASE

case "\$usenm" in

")

dflt="

case "\$d_gnulibc" in

"\$define")

echo " "

echo "nm probably won't work on the GNU C Library." >&4

dflt=n

::

esac

case "\$dflt" in

")

if \$test "\$osname" = aix -a "X\$PASE" != "Xdefine" -a ! -f /lib/syscalls.exp; then

echo " "

echo "Whoops! This is an AIX system without /lib/syscalls.exp!" >&4

echo "'nm' won't be sufficient on this system." >&4

dflt=n

fi

::

esac

case "\$dflt" in

") dflt=`\$egrep 'inlibc|csym' \$rsrc/Configure | wc -l 2>/dev/null`

if \$test \$dflt -gt 20; then

dflt=y

else

dflt=n

fi

::

esac

::

*)

case "\$usenm" in

true|\$define) dflt=y;;

*) dflt=n;;

esac

::

esac

\$cat <<EOM

I can use \$nm to extract the symbols from your C libraries. This is a time consuming task which may generate huge output on the disk (up to 3 megabytes) but that should make the symbols extraction faster. The alternative is to skip the 'nm' extraction part and to compile a small test program instead to determine whether each symbol is present. If you have a fast C compiler and/or if your 'nm' output cannot be parsed, this may be the best solution.

You probably shouldn't let me use 'nm' if you are using the GNU C Library.

EOM

```
rp="Shall I use $nm to extract C symbols from the libraries?"
```

```
./myread
```

```
case "$ans" in
```

```
[Nn]*) usenm=false;;
```

```
*) usenm=true;;
```

```
esac
```

```
?X: Name extraction is to be run if 'nm' usage is wanted and if no -r flag
```

```
?X: was provided to configure (in which case we simply re-use the previous
```

```
?X: values).
```

```
runnm=$usenm
```

```
case "$reuserval" in
```

```
true) runnm=false;;
```

```
esac
```

```
: nm options which may be necessary
```

```
case "$nm_opt" in
```

```
") if $test -f /mach_boot; then
```

```
nm_opt="# Mach
```

```
elif $test -d /usr/ccs/lib; then
```

```
nm_opt='-p' # Solaris (and SunOS?)
```

```
elif $test -f /dgux; then
```

```
nm_opt='-p' # DG-UX
```

```
elif $test -f /lib64/rld; then
```

```
nm_opt='-p' # 64-bit Irix
```

```
else
```

```
nm_opt=""
```

```
fi;;
```

```
esac
```

```
: nm options which may be necessary for shared libraries but illegal
```

```
: for archive
```

```
libraries. Thank you, Linux.
```

```
case "$nm_so_opt" in
```

```

") case "$myuname" in
*linux*|gnu*)
  if $nm --help | $grep 'dynamic' > /dev/null 2>&1; then
    nm_so_opt='--dynamic'
  fi
  ;;
esac
;;
esac

```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/modified/usenm.U
```

No license file was found, but licenses were detected in source scan.

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?MAKE:d_atanh: Inlibc

?MAKE: -pick add \$@ %<

?S:d_atanh:

?S: This variable conditionally defines the HAS_ATANH symbol, which

?S: indicates to the C program that the atanh() routine is available.

?S:.

?C:HAS_ATANH:

?C: This symbol, if defined, indicates that the atanh routine is

?C: available to do the inverse hyperbolic tangent function.

?C:.

?H:#\$d_atanh HAS_ATANH /**/

?H:.

?LINT:set d_atanh

: see if atanh exists

set atanh d_atanh

eval \$inlibc

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_atanh.U
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: libs.U,v \$

?RCS: Revision 3.0.1.6 1997/02/28 16:09:11 ram

?RCS: patch61: replaced .a with \$_a all over the place

?RCS:

?RCS: Revision 3.0.1.5 1995/07/25 14:12:05 ram

?RCS: patch56: now knows about OS/2 platforms

?RCS:

?RCS: Revision 3.0.1.4 1994/10/29 16:24:22 ram

?RCS: patch36: removed old broken thislib/thatlib processing (ADO)

?RCS:

?RCS: Revision 3.0.1.3 1994/06/20 07:05:44 ram

?RCS: patch30: code cleanup with if/elif by ADO and RAM

?RCS: patch30: undone patch23 for libswanted default setting

?RCS:

?RCS: Revision 3.0.1.2 1994/05/06 15:08:45 ram

?RCS: patch23: now includes ordered default libswanted variable (ADO)

?RCS: patch23: major cleanup for library lookups (ADO)

?RCS:

?RCS: Revision 3.0.1.1 1993/08/25 14:02:31 ram

?RCS: patch6: added default for libs

?RCS:

?RCS: Revision 3.0 1993/08/18 12:09:03 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?MAKE:libs libsfound libsfiles libsdirs libspath libscheck: \
test cat Myread Oldconfig Loc libpth package xlibpth so _a \
+usesocks sed +cc +ccflags +ldflags rm

?MAKE: -pick add \$@ %<

?S:libs:

?S: This variable holds the additional libraries we want to use.

?S: It is up to the Makefile to deal with it. The list can be empty.

?S:.

?S:libsfound:

?S: This variable holds the full pathnames of the libraries

?S: we found and accepted.

?S:.

?S:libsfiles:

?S: This variable holds the filenames aka basenames of the libraries

?S: we found and accepted.

?S:.

?S:libsdirs:

?S: This variable holds the directory names aka dirnames of the libraries

?S: we found and accepted, duplicates are removed.

?S:.

?S:libspath:
 ?S: This variable holds the directory names probed for libraries.
 ?S:.
 ?S:libscheck:
 ?S: This variable is intended to be set by hint files, if needed.
 ?S: It should contain shell code that will be eval'ed with \$xxx holding
 ?S: some library file. It may change \$xxx if needed.
 ?S: For instance, on an Irix platform, you may make sure the right
 ?S: library file is used depending on the cc command line, so that the
 ?S: correct library is used depending on the selected ABI (for 32 and
 ?S: 64-bit compilations).
 ?S:
 ?S: Here is an example of code that could be found in a hint file on Irix
 ?S: when the selected compiler was for 32-bit -- that code is put in the
 ?S: cc.cbu call-back unit to be invoked AFTER the C compiler and its
 ?S: flags have been chosen:
 ?S:
 ?S: libscheck='case "\$xxx" in
 ?S: *.a) /bin/ar p \$xxx `bin/ar t \$xxx | sed q` >\$\$o;
 ?S: case "`usr/bin/file \$\$o`" in
 ?S: *N32*)
 ?S: rm -f \$\$o ;;
 ?S: *) rm -f \$\$o; xxx=/no/n32\$xxx ;;
 ?S: esac ;;
 ?S: *) case "`usr/bin/file \$xxx`" in
 ?S: *N32*) ;;
 ?S: *) xxx=/no/n32\$xxx ;;
 ?S: esac ;;
 ?S: esac'
 ?S:.
 ?D:libs="
 ?LINT:extern libswanted
 ?LINT:change libswanted
 ?INIT:: default library list
 ?INIT:libswanted="
 ?X: This order is chosen so that libraries -lndir, -ldir, -lucb, -lbsd,
 ?X: -lBSD, -lPW, and -lx only get used if there are unresolved
 ?X: routines at link time. Usually, these are backwards compatability
 ?X: libraries, and may not be as reliable as the standard c library.
 ?X:
 ?X: The -lsocket -linet -lnsl order has been reported to be necessary
 ?X: for at least one SVR4 implementation.
 ?X: -lc must proceed -lucb or -lbsd for most Solaris applications.
 ?X: -lc_s proceeds -lc so we pick up the shared library version, if
 ?X: it is available.
 ?X:
 ?X: The ordering of c, posix, and cposix is a guess and almost
 ?X: certainly wrong on about half of all systems.

```

?X:
?X: Set proper libswanted in your private
  Myinit.U if needed.
?X:
?X:: default ordered library list
?X:libswanted='net socket inet bind nsl nm sdbm gdbm ndbm dbm malloc dl'
?X:libswanted="$libswanted dld sun m c_s c posix cposix ndir dir ucb"
?X:libswanted="$libswanted bsd BSD PW x"
?X:
?INIT:: should be set by hint files if needed
?INIT:libscheck="
?T:xxx yyy thislib thisdir libstyle linkmsg
?F:lt.c lt
: Looking for optional libraries
echo " "
echo "Checking for optional libraries..." >&4
case "$libs" in
'|') dflt="";;
*) dflt="$libs";;
esac
case "$libswanted" in
") libswanted='c_s';;
esac
?X: libsocks has nasty naming scheme.
?X: This does not work if somebody wants SOCKS 4.
case "$usesocks" in
"$define") libswanted="$libswanted socks5 socks5_sh" ;;
esac
?X: Used later for link checks
echo "extern char printf(); int main() { printf(); return 0; }" > lt.c
libsfound="
libsfiles="
libsdirs="
libspath="
for thisdir in $libpth $xlibpth; do
  test -d $thisdir && libspath="$libspath $thisdir"
done
for thislib in $libswanted;
do
  for thisdir in $libspath; do
    xxx="
    if $test ! -f "$xxx" ; then
      xxx=`ls $thisdir/lib$thislib.$so.[0-9]* 2>/dev/null | $sed -n '1p'`
      $test -f "$xxx" && eval $libscheck
      $test -f "$xxx" && libstyle=shared
    fi
    if test ! -f "$xxx"; then
      xxx=$thisdir/lib$thislib.$so

```

```

$test -f "$xxx" && eval $libscheck
$test -f "$xxx" && libstyle=shared
fi
if test ! -f "$xxx"; then
xxx=$thisdir/lib$thislib$_a
    $test -f "$xxx" && eval $libscheck
$test -f "$xxx" && libstyle=static
fi
if test ! -f "$xxx"; then
xxx=$thisdir/$thislib$_a
    $test -f "$xxx" && eval $libscheck
$test -f "$xxx" && libstyle=static
fi
if test ! -f "$xxx"; then
xxx=$thisdir/lib${thislib}_s$_a
    $test -f "$xxx" && eval $libscheck
$test -f "$xxx" && libstyle=static
$test -f "$xxx" && thislib=${thislib}_s
fi
if test ! -f "$xxx"; then
xxx=$thisdir/Slib$thislib$_a
    $test -f "$xxx" && eval $libscheck
$test
-f "$xxx" && libstyle=static
fi
if $test -f "$xxx"; then
?X:
?X: It is not sufficient to find a .so on the disk. We must make sure
?X: that we can indeed supply the -lfoo line on the cc line to link against
?X: that library. On Linux for instance, a versioned .so will not be
?X: implicitly linked against, whereas it will work fine on Solaris 2.6.
?X: --RAM, 10/10/2003
?X:
if $cc -o lt $ccflags $ldflags lt.c -l$thislib >/dev/null 2>&1;
then
linkmsg=""
else
linkmsg=" but I can't link against it"
fi
case "$libstyle" in
shared) echo "Found -l$thislib (shared)$linkmsg." ;;
static) echo "Found -l$thislib$linkmsg." ;;
*)    echo "Found -l$thislib ($libstyle)$linkmsg." ;;
esac
case " $dflt " in
*" -l$thislib "*) ;;
*)
case "$linkmsg" in

```

```

")
dflt="$dflt -l$thislib"
libsfound="$libsfound $xxx"
yyy=`basename $xxx`
libsfiles="$libsfiles $yyy"
yyy=`echo $xxx|sed -e "s%/$yyy\\$%"`
case " $libsdirs
" in
*" $yyy "*) ;;
*) libsdirs="$libsdirs $yyy" ;;
esac
;;
esac
;;
esac
break
fi
done
if $test ! -f "$xxx"; then
    echo "No -l$thislib."
fi
done
set X $dflt
shift
dflt="$*"
case "$libs" in
") dflt="$dflt";;
*) dflt="$libs";;
esac
case "$dflt" in
'|") dflt='none';;
esac
$rm -f lt.c lt

```

\$cat <<EOM

In order to compile \$package on your machine, a number of libraries are usually needed. Include any other special libraries here as well.

Say "none" for none. The default list is almost always right.

EOM

```

echo " "
rp="Which libraries to use?"
./myread
case "$ans" in
none) libs='';;
*) libs="$ans";;
esac

```

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/libs.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: libc.U 1 2006-08-24 12:32:52Z rmanfredi \$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: libc.U,v \$

?RCS: Revision 3.0.1.10 1997/02/28 15:56:48 ram

?RCS: patch61: replaced .a with \$_a all over the place

?RCS: patch61: added support for HPUX-10 nm output

?RCS:

?RCS: Revision 3.0.1.9 1995/07/25 14:11:56 ram

?RCS: patch56: now knows about OS/2 platforms

?RCS:

?RCS: Revision 3.0.1.8 1995/05/12 12:20:47 ram

?RCS: patch54: made sure only most recent version of shared lib is picked

?RCS: patch54: final "nm -p" check now uses xscan and xrun

like everybody

?RCS: patch54: can now grok Linux nm output with lead __IO (ADO)

?RCS: patch54: added support for Linux ELF output, using 'W' for alias (ADO)

?RCS:

?RCS: Revision 3.0.1.7 1994/10/29 16:23:40 ram

?RCS: patch36: now looks for shared libraries before anything else (ADO)

?RCS: patch36: added new nm output format (ADO)

?RCS:

?RCS: Revision 3.0.1.6 1994/08/29 16:28:10 ram

?RCS: patch32: added I-type symbols for nm output parsing on Linux

?RCS:

?RCS: Revision 3.0.1.5 1994/06/20 07:03:24 ram

?RCS: patch30: checks are now presented by succession of if/elif

?RCS: patch30: uniformized checks for shared objects with new so symbol

?RCS:

?RCS: Revision 3.0.1.4 1994/05/06 15:06:33 ram

?RCS: patch23: added shared library knowledge (ADO and WED)

?RCS:

?RCS: Revision 3.0.1.3 1994/01/24 14:12:17 ram

?RCS: patch16: can now export nm_extract as an internal-use only variable

?RCS:

```

?RCS: Revision 3.0.1.2 1993/09/13 16:09:03 ram
?RCS: patch10: added special handling for Apollo
systems (WAD)
?RCS:
?RCS: Revision 3.0.1.1 1993/08/27 14:40:03 ram
?RCS: patch7: added entry for /usr/shlib/libc.so (OSF/1 machines)
?RCS:
?RCS: Revision 3.0 1993/08/18 12:08:57 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:libc +nm_extract: echo n c rm test grep Getfile Myread Oldconfig Loc \
sed libs incpath libpth ar runnm nm nm_opt nm_so_opt contains xlibpth \
so _a _o osname trnl tr sort uniq sysroot
?MAKE: -pick add $@ %<
?S:libc:
?S: This variable contains the location of the C library.
?S:.
?S:nm_extract:
?S: This variable holds the name of the extraction command used to process
?S: the output of nm and yield the list of defined symbols. It is used
?S: internally by Configure.
?S:.
?T:thislib try libnames xxx xscan xrun thisname com tans file
?F:!libnames !libc.tmp !tmp.imp
?LINT:extern PASE
?LINT:extern libnames
?LINT:change nm_opt
?INIT:libnames=""
: Figure out where the libc is located
case "$runnm" in
true)
?X: indentation is wrong on purpose--RAM
:
get list of predefined functions in a handy place
echo " "
case "$libc" in
") libc=unknown
case "$libs" in
*-lc_s*) libc=`./loc libc_s$_a $libc $libpth`
esac
;;
esac
case "$libs" in
") ;;
*) for thislib in $libs; do
case "$thislib" in
-lc|-lc_s)
: Handle C library specially below.

```

```

;;
-l*)
thislib=`echo $thislib | $sed -e 's/^-!//'^
if try=`./loc lib$thislib.$so.*' X $libpth`; $test -f "$stry"; then
:
elif try=`./loc lib$thislib.$so X $libpth`; $test -f "$stry"; then
:
elif try=`./loc lib$thislib$_a X $libpth`; $test -f "$stry"; then
:
elif try=`./loc $thislib$_a X $libpth`; $test -f "$stry"; then
:
elif try=`./loc lib$thislib X $libpth`; $test -f "$stry"; then
:
elif try=`./loc $thislib X $libpth`; $test -f "$stry"; then
:
elif try=`./loc $lib$thislib$_a X $xlibpth`; $test -f "$stry"; then
:
else
try="
fi
libnames="$libnames $stry"
;;
*) libnames="$libnames $thislib" ;;
esac
done
;;
esac
?X:
?X: Some systems (e.g. DG/UX) use
"environmental" links, which make the test
?X: -f fail. Ditto for symbolic links. So in order to reliably check the
?X: existence of a file, we use test -r. It will still fail with DG/UX links
?X: though, but at least it will detect symbolic links. At some strategic
?X: points, we make use of (test -h), using a sub-shell in case builtin test
?X: does not implement the -h check for symbolic links. This makes it
?X: possible to preset libc in a hint file for instance and have it show up
?X: as-is in the question.
?X:
xxx=normal
case "$libc" in
unknown)
?X:
?X: The sed below transforms .so.9 .so.12 into something like .so.0009 .so.0012,
?X: then sorts on it to allow keeping .so.12 instead of .so.9 as the latest
?X: up-to-date library. The initial filename (before sed munging, saved in hold
?X: space via 'h') is appended via 'G' before sorting, then the leading munged
?X: part is removed after sorting. Nice efficient work from Tye McQueen.
?X: The initial blurfl is here to prevent the trailing

```

pipe from producing an

?X: empty string, causing Configure to output all its set variables!

?X:

```
set /lib/libc.$so
```

```
for xxx in $libpth; do
```

```
  $test -r $1 || set $xxx/libc.$so
```

```
  : The messy sed command sorts on library version numbers.
```

```
  $test -r $1 || \
```

```
  set `echo blurfl; echo $xxx/libc.$so.[0-9]* | \
```

```
  tr ' ' $trnl | egrep -v \.[A-Za-z]*$' | $sed -e '
```

```
  h
```

```
  s/[0-9][0-9]*/0000&/g
```

```
  s/0*\([0-9][0-9][0-9][0-9]\)\^1/g
```

```
  G
```

```
  s/\n/ / | \
```

```
  $sort | $sed -e 's/^\.* //'^
```

```
eval set \$$#
```

```
done
```

```
$test -r $1 || set $sysroot/usr/ccs/lib/libc.$so
```

```
$test -r $1 || set $sysroot/lib/libsys_s$_a
```

```
::
```

```
*)
```

?X: ensure the test below for the (shared) C library will fail

```
set blurfl
```

```
::
```

```
esac
```

```
if $test -r "$1"; then
```

```
  echo "Your (shared) C library seems to be in $1."
```

```
  libc="$1"
```

```
  elif $test -r /lib/libc && $test -r /lib/clib; then
```

?X:

?X: Apollo has its C library in /lib/clib AND /lib/libc

?X: not to mention its math library in /lib/syslib...

?X:

```
  echo "Your C library seems to be in both /lib/clib
```

```
  and /lib/libc."
```

```
  xxx=apollo
```

```
  libc='/lib/clib /lib/libc'
```

```
  if $test -r /lib/syslib; then
```

```
    echo "(Your math library is in /lib/syslib.)"
```

?X: Put syslib in libc -- not quite right, but won't hurt

```
    libc="$libc /lib/syslib"
```

```
  fi
```

```
  elif $test -r "$libc" || (test -h "$libc") >/dev/null 2>&1; then
```

```
    echo "Your C library seems to be in $libc, as you said before."
```

?X: For mips, and...

```
  elif $test -r $incpath/usr/lib/libc$_a; then
```

```
    libc=$incpath/usr/lib/libc$_a;
```

```

echo "Your C library seems to be in $libc. That's fine."
elif $test -r /lib/libc$_a; then
libc=/lib/libc$_a;
echo "Your C library seems to be in $libc. You're normal."
else
if tans=`./loc libc$_a blurfl/dyick $libpth`; $test -r "$stans"; then
:
elif tans=`./loc libc blurfl/dyick $libpth`; $test -r "$stans"; then
libnames="$libnames "`./loc clib blurfl/dyick $libpth`
elif tans=`./loc clib blurfl/dyick $libpth`; $test -r "$stans"; then
:
elif tans=`./loc Slibc$_a blurfl/dyick $xlibpth`; $test -r "$stans"; then
:
elif tans=`./loc
Mlibc$_a blurfl/dyick $xlibpth`; $test -r "$stans"; then
:
else
tans=`./loc Llibc$_a blurfl/dyick $xlibpth`
fi
if $test -r "$stans"; then
echo "Your C library seems to be in $stans, of all places."
libc=$stans
else
libc='blurfl'
fi
fi
if $test $xxx = apollo -o -r "$libc" || (test -h "$libc") >/dev/null 2>&1; then
dflt="$libc"
cat <<EOM

```

If the guess above is wrong (which it might be if you're using a strange compiler, or your machine supports multiple models), you can override it here.

```

EOM
else
dflt="
echo $libpth | $tr ' ' $trnl | $sort | $uniq > libpath
cat >&4 <<EOM

```

I can't seem to find your C library. I've looked in the following places:

```

EOM
$sed 's/^/' libpath
cat <<EOM

```

None of these seems to contain your C library. I need to get its name...

```

EOM
fi

```

```

fn=f
rp='Where is your C library?'
./getfile
libc="$ans"

echo " "
echo $libc $libnames | $tr ' ' $trnl | $sort | $uniq > libnames
set X `cat libnames`
shift
xxx=files
case $# in 1) xxx=file; esac
echo
"Extracting names from the following $xxx for later perusal:" >&4
echo " "
$sed 's/^/ /' libnames >&4
echo " "
$echo $n "This may take a while...$c" >&4

?X:
?X: Linux may need the special Dynamic option to nm for shared libraries.
?X: In general, this is stored in the nm_so_opt variable.
?X: Unfortunately, that option may be fatal on non-shared libraries.
?X:
for file in $*; do
case $file in
*$so*) $nm $nm_so_opt $nm_opt $file 2>/dev/null;;
*) $nm $nm_opt $file 2>/dev/null;;
esac
done >libc.tmp

$echo $n ".$c"
?X:
?X: To accelerate processing, we look at the correct 'sed' command
?X: by using a small subset of libc.tmp, i.e. fprintf function.
?X: When we know which sed command to use, do the name extraction
?X:
$grep fprintf libc.tmp > libc.ptf
?X:
?X: In order to enhance readability and save some space, we define
?X: some variables that will be "eval"ed.
?X:
xscan='eval "<libc.ptf $com >libc.list"; $echo $n ".$c" >&4'
xrun='eval "<libc.tmp $com >libc.list"; echo "done." >&4'
?X:
BSD-like output, I and W types added for Linux
?X: Some versions of Linux include a leading __IO in the symbol name.
?X: HP-UX 10 reportedly has trailing spaces, though I'm surprised it has
?X: BSD-like output. (AD).

```

```

?X: GNU extension: i is "indirect function"
xxx=[ADTSIW]i'
if com="$sed -n -e 's/___IO//' -e 's/^. * $xxx */p'";\
eval $xscan;\
$contains '^fprintf$' libc.list >/dev/null 2>&1; then
eval $xrun
?X: SYSV-like output
elif com="$sed -n -e 's/^__*/' -e 's/^\([a-zA-Z_0-9$]*\).*xtern.*\1/p'";\
eval $xscan;\
$contains '^fprintf$' libc.list >/dev/null 2>&1; then
eval $xrun
elif com="$sed -n -e '/|UNDEF/d' -e '/FUNC..GL/s/^. *|__*/p'";\
eval $xscan;\
$contains '^fprintf$' libc.list >/dev/null 2>&1; then
eval $xrun
elif com="$sed -n -e 's/^. * D __*/p' -e 's/^. * D //p'";\
eval $xscan;\
$contains '^fprintf$' libc.list >/dev/null 2>&1; then
eval $xrun
elif com="$sed -n -e 's/^_/ ' -e 's/^\([a-zA-Z_0-9$]*\).*xtern.*text.*\1/p'";\
eval $xscan;\
$contains '^fprintf$'
libc.list >/dev/null 2>&1; then
eval $xrun
elif com="$sed -n -e 's/^. *|FUNC |GLOB .*/p'";\
eval $xscan;\
$contains '^fprintf$' libc.list >/dev/null 2>&1; then
eval $xrun
elif com="$grep '| | $sed -n -e '/|COMMON/d' -e '/|DATA/d' \
-e '/file/d' -e 's/^\([ ^ ]*\).*\1/p'";\
eval $xscan;\
$contains '^fprintf$' libc.list >/dev/null 2>&1; then
eval $xrun
elif com="$sed -n -e 's/^. *|FUNC |GLOB .*/p' -e 's/^. *|FUNC |WEAK .*/p'";\
eval $xscan;\
$contains '^fprintf$' libc.list >/dev/null 2>&1; then
eval $xrun
?X: mips nm output (sysV)
elif com="$sed -n -e 's/^__/' -e '/|Undef/d' -e '/|Proc/s/ .*/p'";\
eval $xscan;\
$contains '^fprintf$' libc.list >/dev/null 2>&1; then
eval $xrun
elif com="$sed -n -e 's/^. *|Proc . *|Text *| */p'";\
eval $xscan;\
$contains '^fprintf$' libc.list >/dev/null 2>&1; then
eval $xrun
elif com="$sed -n -e '/Def. Text/s/.* \([ ^ ]*\)\$/\1/p'";\
eval $xscan;\

```

```

$contains '^fprintf$' libc.list >/dev/null 2>&1; then
    eval $xrun
?X: OS/2
    nm output
elif com="$sed -n -e 's/^[0-9a-f ]*_\(.*)=.*/\1/p';\
eval $xscan;\
$contains '^fprintf$' libc.list >/dev/null 2>&1; then
    eval $xrun
elif com="$sed -n -e 's/.*\.text n\ \ \ \.//p';\
eval $xscan;\
$contains '^fprintf$' libc.list >/dev/null 2>&1; then
    eval $xrun
?X: AIX nm output
elif com="sed -n -e 's/^\_.*//' -e 's/[ \t]*D[ \t]*[0-9]*.*//p';\
eval $xscan;\
$contains '^fprintf$' libc.list >/dev/null 2>&1; then
    eval $xrun
else
    $nm -p $* 2>/dev/null >libc.tmp
    $grep fprintf libc.tmp > libc.ptf
if com="$sed -n -e 's/^\_.* [ADTSIW] *_[_.]*/p' -e 's/^\_.* [ADTSIW] //p';\
eval $xscan; $contains '^fprintf$' libc.list >/dev/null 2>&1
then
    nm_opt='-p'
    eval $xrun
else
    echo " "
    echo "$nm didn't seem to work right. Trying $ar instead..." >&4
    com="
if $ar t $libc > libc.tmp && \
    $contains '^fprintf$' libc.tmp >/dev/null 2>&1
then
    for thisname in $libnames $libc; do
        $ar t $thisname >>libc.tmp
    done
    $sed -e "s/^\$_o\$//" < libc.tmp > libc.list
    echo
    "Ok." >&4
    elif test "X$osname" = "Xos2" && $ar tv $libc > libc.tmp; then
?X: Repeat libc to extract forwarders to DLL entries too
    for thisname in $libnames $libc; do
        $ar tv $thisname >>libc.tmp
?X: Revision 50 of EMX has bug in ar: it will not extract forwarders
?X: to DLL entries. Use emximp which will extract exactly them.
    emximp -o tmp.imp $thisname \
        2>/dev/null && \
        $sed -e 's/^\([_a-zA-Z0-9]*\) .*$/\1/p' \
        < tmp.imp >>libc.tmp

```

```

$rm -f tmp.imp
done
$sed -e "s/\$_o\$//" -e 's/^ \+/' < libc.tmp > libc.list
echo "Ok." >&4
else
echo "$ar didn't seem to work right." >&4
echo "Maybe this is a Cray...trying bld instead..." >&4
if bld t $libc | \
$sed -e 's/.*\+/' -e "s/\$_o:.*\+/" > libc.list &&
$test -s libc.list
then
for thisname in $libnames; do
bld t $libnames | \
$sed -e 's/.*\+/' -e "s/\$_o:.*\+/" >>libc.list
$ar t $thisname >>libc.tmp
done
echo "Ok." >&4
else
echo
"That didn't work either. Giving up." >&4
exit 1
fi
fi
fi
fi
nm_extract="$com"
case "$PASE" in
define)
echo " "
echo "Since you are compiling for PASE, extracting more symbols from libc.a ..." >&4
dump -Tv /lib/libc.a | awk '$7 == "/unix" {print $5 " " $8}' | grep "^SV" | awk '{print $2}' >> libc.list
;;
*) if $test -f /lib/syscalls.exp; then
echo " "
echo "Also extracting names from /lib/syscalls.exp for good ole AIX..." >&4
$sed -n 's/^\([^\ ]*\)[ \]*syscall[0-9]*[ \]*$/1/p' \
/lib/syscalls.exp >>libc.list
fi
;;
esac
;;
esac
$rm -f libnames libpath

```

Found in path(s):

```

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/modified/libc.U

```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: d_getpent.U,v 3.0 1993/08/18 12:06:09 ram Exp $
?RCS:
?RCS: Copyright (c) 1991-1993, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 3.0.
?RCS:
?RCS: $Log: d_getpent.U,v $
?RCS: Revision 3.0 1993/08/18 12:06:09 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:d_getpent: Inlibc
?MAKE: -pick add $@ %<
?S:d_getpent:
?S: This variable conditionally defines HAS_GETPROTOENT if getprotoent() is
?S: available to look up protocols in some data base or another.
?S:.
?C:HAS_GETPROTOENT:
?C: This symbol, if defined, indicates that the getprotoent() routine is
?C: available to look up protocols in some data base
?C: or another.
?C:.
?H:#$d_getpent HAS_GETPROTOENT /**/
?H:.
?LINT:set d_getpent
: see if getprotoent exists
set getprotoent d_getpent
eval $inlibc
```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/modified/d_getpent.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: d_setprotoent_r.U,v 0RCS:
?RCS: Copyright (c) 2002,2003 Jarkko Hietaniemi
?RCS:
?RCS: You may distribute under the terms of either the GNU General Public
?RCS: License or the Artistic License, as specified in the README file.
?RCS:
?RCS: Generated by the reentr.pl from the Perl 5.8 distribution.
?RCS:
?MAKE:d_setprotoent_r setprotoent_r_proto: Inlibc Protochk Hasproto \
```

```

i_systypes usethreads i_netdb extern_C
?MAKE: -pick add $@ %<
?S:d_setprotoent_r:
?S: This variable conditionally defines the HAS_SETPROTOENT_R symbol,
?S: which indicates to the C program that the setprotoent_r()
?S: routine is available.
?S:.
?S:setprotoent_r_proto:
?S: This variable encodes the prototype of setprotoent_r.
?S: It is zero if d_setprotoent_r is undef, and one of the
?S: REENTRANT_PROTO_T_ABC macros of reentr.h if d_setprotoent_r
?S: is defined.
?S:.
?C:HAS_SETPROTOENT_R:
?C: This symbol, if defined, indicates that the setprotoent_r
routine
?C: is available to setprotoent re-entrantly.
?C:.
?C:SETPROTOENT_R_PROTO:
?C: This symbol encodes the prototype of setprotoent_r.
?C: It is zero if d_setprotoent_r is undef, and one of the
?C: REENTRANT_PROTO_T_ABC macros of reentr.h if d_setprotoent_r
?C: is defined.
?C:.
?H:#$d_setprotoent_r HAS_SETPROTOENT_R /**/
?H:#define SETPROTOENT_R_PROTO $setprotoent_r_proto /**/
?H:.
?T:try hdrs d_setprotoent_r_proto
: see if setprotoent_r exists
set setprotoent_r d_setprotoent_r
eval $inlibc
case "$d_setprotoent_r" in
"$define")
hdrs="$i_systypes sys/types.h define stdio.h $i_netdb netdb.h"
case "$d_setprotoent_r_proto:$usethreads" in
":define") d_setprotoent_r_proto=define
set d_setprotoent_r_proto setprotoent_r $hdrs
eval $hasproto ;;
*) ;;
esac
case "$d_setprotoent_r_proto" in
define)
case "$setprotoent_r_proto" in
"|0) try='int setprotoent_r(int, struct protoent_data*);'
./prochck "$extern_C $try" $hdrs && setprotoent_r_proto=I_ID ;;
esac
case "$setprotoent_r_proto"

```

```

in
"|0) try='void setprotoent_r(int, struct protoent_data*);'
./protochk "$extern_C $try" $hdrs && setprotoent_r_proto=V_ID ;;
esac
case "$setprotoent_r_proto" in
"|0) d_setprotoent_r=undef
    setprotoent_r_proto=0
    echo "Disabling setprotoent_r, cannot determine prototype." >&4 ;;
*) case "$setprotoent_r_proto" in
    REENTRANT_PROTO*) ;;
*) setprotoent_r_proto="REENTRANT_PROTO_$setprotoent_r_proto" ;;
esac
echo "Prototype: $try" ;;
esac
;;
*) case "$usethreads" in
define) echo "setprotoent_r has no prototype, not using it." >&4 ;;
esac
d_setprotoent_r=undef
setprotoent_r_proto=0
;;
esac
;;
*) setprotoent_r_proto=0
;;
esac

```

Found in path(s):

```

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/threads/d_setprotoent_r.U

```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1999 Jarkko Hietaniemi

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?MAKE:d_statvfs d_fstatvfs: Inlibc

?MAKE: -pick add \$@ %<

?S:d_statvfs:

?S: This variable conditionally defines the HAS_STATVFS symbol, which

?S: indicates to the C program that the statvfs() routine is available.

?S:.

?S:d_fstatvfs:

?S: This variable conditionally defines the HAS_FSTATVFS symbol, which

?S: indicates to the C program that the fstatvfs() routine is available.

?S:.

?C:HAS_STATVFS:

?C: This symbol, if defined, indicates that the statvfs routine is

?C: available to stat filesystems by filenames.

?C:.

?C:HAS_FSTATVFS:

?C: This symbol, if defined, indicates that the fstatvfs routine is

?C: available to stat filesystems by file descriptors.

?C:.

?H:#\$d_statvfs HAS_STATVFS /**/

?H:#\$d_fstatvfs

HAS_FSTATVFS /**/

?H:.

?LINT:set d_statvfs

?LINT:set d_fstatvfs

: see if statvfs exists

set statvfs d_statvfs

eval \$inlibc

: see if fstatvfs exists

set fstatvfs d_fstatvfs

eval \$inlibc

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_statvfs.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 2000 Jarkko Hietaniemi

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?MAKE:d_fchdir: Inlibc

?MAKE: -pick add \$@ %<

?S:d_fchdir:

?S: This variable conditionally defines the HAS_FCHDIR symbol, which

?S: indicates to the C program that the fchdir() routine is available.

?S:.

?C:HAS_FCHDIR:

?C: This symbol, if defined, indicates that the fchdir routine is

?C: available to change directory using a file descriptor.

?C:.

?H:#\$d_fchdir HAS_FCHDIR /**/

?H:.

?LINT:set d_fchdir

```
: see if fchdir exists
set fchdir d_fchdir
eval $inlibc
```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/perl/d_fchdir.U
```

No license file was found, but licenses were detected in source scan.

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?MAKE:d_nearbyint: Inlibc

?MAKE: -pick add \$@ %<

?S:d_nearbyint:

?S: This variable conditionally defines HAS_NEARBYINT if nearbyint()

?S: is available to return the integral value closest to (according to

?S: the current rounding mode) to x.

?S:.

?C:HAS_NEARBYINT:

?C: This symbol, if defined, indicates that the nearbyint routine is

?C: available to return the integral value closest to (according to

?C: the current rounding mode) to x.

?C:.

?H:#\$d_nearbyint HAS_NEARBYINT /**/

?H:.

?LINT:set d_nearbyint

: see if nearbyint exists

set nearbyint d_nearbyint

eval \$inlibc

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/perl/d_nearbyint.U
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1999 Jarkko Hietaniemi

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?MAKE:d_getmntent_r: Inlibc

?MAKE: -pick add \$@ %<

?S:d_getmntent_r:

?S: This variable conditionally defines the HAS_GETMNTENT_R symbol,

?S: which indicates to the C program that the getmntent_r()

?S: routine is available.

?S:.

?C:HAS_GETMNTENT_R:

?C: This symbol, if defined, indicates that the getmntent_r routine

?C: is available to getmntent re-entrantly.

?C:.

?H:#\$d_getmntent_r HAS_GETMNTENT_R /**/

?H:.

?LINT:set d_getmntent_r

: see if getmntent_r exists

set getmntent_r d_getmntent_r

eval \$inlibc

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/threads/d_getmntent_r.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1999, Jarkko Hietaniemi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 3.0.

?RCS:

?MAKE:d_posix_sem: Setvar d_sem_open d_sem_unlink d_sem_close d_sem_destroy d_sem_getvalue d_sem_post d_sem_wait d_sem_init d_sem_trywait i_semaphore

?MAKE: -pick add \$@ %<

?S:d_posix_sem:

?S: This variable conditionally defines the HAS_POSIX_SEM symbol, which

?S: indicates that the entire sem*(2) library is present.

?S:.

?C:HAS_POSIX_SEM:

?C: This symbol, if defined, indicates that the entire POSIX sem_*(2)

?C: library is supported.

?C:.

?H:#\$d_posix_sem HAS_POSIX_SEM /**/

?H:.

?LINT:set d_posix_sem

: see how much of the

'POSIX sem_*(2)' library is present.

echo " "

case

"\$i_semaphore\$d_sem_open\$d_sem_close\$d_sem_destroy\$d_sem_getvalue\$d_sem_post\$d_sem_wait\$d_sem_trywait\$d_sem_init\$d_sem_unlink" in

```

*"$undef"*) val="$undef" ;;
*) val="$define" ;;
esac
case "$val" in
"$define") echo "You have the full POSIX sem_*(2) library." >&4 ;;
"$undef") echo "You don't have the full POSIX sem_*(2) library." >&4 ;;
esac
set d_posix_sem
eval $setvar

```

Found in path(s):

```

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/perl/d_posix_sem.U

```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 2000 Jarkko Hietaniemi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 3.0.

?RCS:

?MAKE:d_getprpwnam: Inlibc

?MAKE: -pick add \$@ %<

?S:d_getprpwnam:

?S: This variable conditionally defines HAS_GETPRPWNAM if getprpwnam() is

?S: available to retrieve protected (shadow) password entries by name.

?S:.

?C:HAS_GETPRPWNAM:

?C: This symbol, if defined, indicates that the getprpwnam system call is

?C: available to retrieve protected (shadow) password entries by name.

?C:.

?H:#\$d_getprpwnam HAS_GETPRPWNAM /**/

?H:.

?LINT:set d_getprpwnam

: see if getprpwnam exists

set getprpwnam d_getprpwnam

eval \$inlibc

Found

in path(s):

```

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/perl/d_getprpwnam.U

```

No license file was found, but licenses were detected in source scan.

```

?RCS: $Id$
?RCS:
?RCS: You may distribute under the terms of either the GNU General Public
?RCS: License or the Artistic License, as specified in the README file.
?RCS:
?MAKE:sysroot: Head
?MAKE: -pick add $@ %<
?S:sysroot:
?S: This variable is empty unless supplied by the Configure user.
?S: It can contain a path to an alternative root directory, under which
?S: headers and libraries for the compilation target can be found. This
?S: is generally used when cross-compiling using a gcc-like compiler.
?S:.
?LINT:extern cc
?LINT:extern cppflags
?LINT:change cppflags
?LINT:extern ccflags
?LINT:change ccflags
?LINT:extern ldflags
?LINT:change ldflags
?LINT:extern cccdlflags
?X: _sysroot is later used in ccflags, but we do not want it in config.sh
?T:var xxx path _sysroot
: Set 'sysroot' to change the logical root directory to your headers and libraries see man gcc
: This is primarily meant for cross-compile environments, and
may fail to be useful in other cases
if test "X$sysroot" = X; then
  sysroot=""
else
  case "$cc" in
    *gcc*|*g+*+)
      echo "Using $sysroot to find your headers and libraries, adding to ccflags"
      # _sysroot is used in places where we need --sysroot=foo
      # but using the rest of the flags could cause issues.
      _sysroot="--sysroot=$sysroot";
      case "$ccflags" in
        *sysroot*) ;;
        'undef'|*)
          ccflags="$ccflags $_sysroot"
        esac
      case "$ldflags" in
        *sysroot*) ;;
        'undef'|*)
          ldflags="$ldflags $_sysroot"
        esac
      case "$cppflags" in
        *sysroot*) ;;
        'undef'|*)

```

```

cppflags="$cppflags $_sysroot"
    esac
    # lddflags updated below in lddflags section;
    # same with cccdlflags
    ;;
esac

# Adjust some defaults to also use $sysroot
for var in xlibpth loclibpth locincpth glibpth; do
eval xxx=\$$var
eval $var=""
for path in $xxx; do
    eval $var="\$$var $sysroot$path\"
done
done

fi

```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/Sysroot.U
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1999, Jarkko Hietaniemi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 3.0.

?RCS:

?MAKE:d_mq_unlink: Inlibc

?MAKE: -pick add \$@ %<

?S:d_mq_unlink:

?S: This variable conditionally defines HAS_MQ_UNLINK if mq_unlink() is

?S: available to unlink a POSIX message queue.

?S:.

?C:HAS_MQ_UNLINK:

?C: This symbol, if defined, indicates that the mq_unlink system call is

?C: available to unlink a POSIX message queue.

?C:.

?H:#\$d_mq_unlink HAS_MQ_UNLINK /**/

?H:.

?LINT:set d_mq_unlink

: see if mq_unlink exists

set mq_unlink d_mq_unlink

eval \$inlibc

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_mq_unlink.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1998 Jarkko Hietaniemi

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the WRITEME file.

?RCS:

?MAKE:d_writev: Inlibc

?MAKE: -pick add \$@ %<

?S:d_writev:

?S: This variable conditionally defines the HAS_WRITEV symbol, which

?S: indicates to the C program that the writev() routine is available.

?S:.

?C:HAS_WRITEV:

?C: This symbol, if defined, indicates that the writev routine is

?C: available to do scatter writes.

?C:.

?H:#\$d_writev HAS_WRITEV /**/

?H:.

?LINT:set d_writev

: see if writev exists

set writev d_writev

eval \$inlibc

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_writev.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_safemcpy.U,v 3.0.1.5 1997/02/28 15:41:12 ram Exp \$

?RCS:

?RCS: Copyright (c) 1991-1993, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 3.0.

?RCS:

?RCS: \$Log: d_safemcpy.U,v \$

?RCS: Revision 3.0.1.5 1997/02/28 15:41:12 ram

?RCS: patch61: improved overlapping copy check

?RCS: patch61: comfort them if they have memmove

?RCS: patch61: added ?F: metalint hint

?RCS:

?RCS: Revision 3.0.1.4 1995/07/25 13:58:46 ram

?RCS: patch56: re-arranged compile line to include ldflags before objects

?RCS:

?RCS: Revision 3.0.1.3 1995/03/21 08:47:26 ram

?RCS: patch52: swapped two first arguments of memcpy() calls

?RCS:

?RCS:

Revision 3.0.1.2 1994/10/29 16:15:10 ram

?RCS: patch36: added 'ldflags' to the test compile line (ADO)

?RCS:

?RCS: Revision 3.0.1.1 1994/05/06 14:53:12 ram

?RCS: patch23: ensure string is not optimized in read-only memory (ADO)

?RCS:

?RCS: Revision 3.0 1993/08/18 12:06:58 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?MAKE:d_safemcpy: Compile cat d_memcpy rm_try run \
d_memmove i_memory i_stdlib i_string i_unistd Oldconfig Setvar

?MAKE:-pick add \$@ %<

?S:d_safemcpy:

?S: This variable conditionally defines the HAS_SAFE_MEMCPY symbol if
?S: the memcpy() routine can do overlapping copies.

?S: For overlapping copies, memmove() should be used, if available.

?S:.

?C:HAS_SAFE_MEMCPY (SAFE_MEMCPY):

?C: This symbol, if defined, indicates that the memcpy routine is available

?C: to copy potentially overlapping memory blocks. If you need to

?C: copy overlapping memory blocks, you should check HAS_MEMMOVE and

?C: use memmove() instead, if available.

?C:.

?H:#\$d_safemcpy HAS_SAFE_MEMCPY /**/

?H:.

?F:!try

?LINT:

set d_safemcpy

: can memcpy handle overlapping blocks?

echo " "

?X: assume the worst

val="\$undef"

case "\$d_memmove" in

"\$define") echo "I'll use memmove() instead of memcpy() for overlapping copies." ;;

*) case "\$d_memcpy" in

"\$define")

echo "Checking to see if memcpy() can do overlapping copies..." >&4

```

$cat >try.c <<EOCP
#$i_memory I_MEMORY
#$i_stdlib I_STDLIB
#$i_string I_STRING
#$i_unistd I_UNISTD
EOCP
$cat >>try.c <<'EOCP'
#include <stdio.h>
#ifdef I_MEMORY
# include <memory.h>
#endif
#ifdef I_STDLIB
# include <stdlib.h>
#endif
#ifdef I_STRING
# include <string.h>
#else
# include <strings.h>
#endif
#ifdef I_UNISTD
# include <unistd.h> /* Needed for NetBSD */
#endif
int main()
{
char buf[128], abc[128];
char *b;
int len;
int off;
int align;

/* Copy "abcde..." string to char abc[] so that gcc doesn't
try to store the string in read-only memory. */
memcpy(abc, "abcdefghijklmnopqrstuvwxy0123456789", 36);

for (align = 7; align >=
0; align--) {
for (len = 36; len; len--) {
b = buf+align;
memcpy(b, abc, len);
for (off = 1; off <= len; off++) {
memcpy(b+off, b, len);
memcpy(b, b+off, len);
if (memcmp(b, abc, len))
exit(1);
}
}
}
exit(0);

```

```

}
EOCP
set try
if eval $compile_ok; then
if $run ./try 2>/dev/null; then
echo "Yes, it can."
val="$define"
else
echo "It can't, sorry."
fi
else
echo "(I can't compile the test program, so we'll assume not...)"
fi
;;
esac
$rm_try
;;
esac
set d_safemcpy
eval $setvar

```

Found in path(s):

```

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/compline/d_safemcpy.U

```

No license file was found, but licenses were detected in source scan.

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?MAKE:d_fdclose: Inlibc

?MAKE: -pick add \$@ %<

?S:d_fdclose:

?S: This variable conditionally defines the HAS_FDCLOSE symbol, which

?S: indicates to the C program that the fdclose() routine is available.

?S:.

?C:HAS_FDCLOSE:

?C: This symbol, if defined, indicates that the fdclose routine is

?C: available to free a FILE structure without closing the underlying

?C: file descriptor. This function appeared in FreeBSD 10.2.

?C:.

?H:#\$d_fdclose HAS_FDCLOSE /**/

?H:.

?LINT:set d_fdclose

: see if fdclose exists

set fdclose d_fdclose

eval \$inlibc

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_fdclose.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: vendorman3dir.U,v 1.1 1999/07/08 18:32:57 doughera Exp doughera \$

?RCS:

?RCS: Copyright (c) 1999-2000, Andy Dougherty

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 3.0.

?RCS:

?RCS: \$Log: vendorman3dir.U,v \$

?RCS: Revision 1.1 1999/07/08 18:32:57 doughera

?RCS: Initial revision

?RCS:

?MAKE:vendorman3dir vendorman3direxp installvendorman3dir: man3dir Getfile \

Oldconfig Setprefixvar Prefixit test vendorprefix prefix sed

?MAKE: -pick add \$@ %<

?Y:TOP

?S:vendorman3dir:

?S: This variable contains the name of the directory for man3

?S: pages. It may have a ~ on the front.

?S: The standard distribution will put nothing in this directory.

?S: Vendors

who distribute perl may wish to place their own

?S: man3 pages in this directory with

?S: MakeMaker Makefile.PL INSTALLDIRS=vendor

?S: or equivalent. See INSTALL for details.

?S:.

?S:vendorman3direxp:

?S: This variable is the ~name expanded version of vendorman3dir, so that you

?S: may use it directly in Makefiles or shell scripts.

?S:.

?D:installvendorman3dir="

?S:installvendorman3dir:

?S: This variable is really the same as vendorman3direxp but may differ on

?S: those systems using AFS. For extra portability, only this variable

?S: should be used in makefiles.

?S:.

?LINT:change prefixvar

?LINT:set installvendorman3dir

: Set the vendorman3dir variables

case "\$vendorprefix" in

") vendorman3dir="

vendorman3direxp="

```

;;
*) : determine where vendor-supplied module manual pages go.
case "$vendorman3dir" in
  ") dflt=`echo "$man3dir" | $sed "s#^$prefix#$vendorprefix#" ` ;;
*) dflt=$vendorman3dir ;;
esac
case "$dflt" in
  "|' ') dflt=none ;;
esac
fn=nd~+
rp='Pathname
for the vendor-supplied manual section 3 pages?'
./getfile
vendorman3dir="$ans"
vendorman3direxp="$ansexp"
;;
esac
: Use ' ' for none so value is preserved next time through Configure
$test X"$vendorman3dir" = "X" && vendorman3dir=' '
prefixvar=vendorman3dir
./installprefix

```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/installdirs/vendorman3dir.U
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1999 Jarkko Hietaniemi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 3.0.

?RCS:

?MAKE:sitehtml3 sitehtml3exp installsitehtml3: Getfile Setprefixvar \

prefix siteprefix html3dir sed

?MAKE: -pick add \$@ %<

?Y:TOP

?D:sitehtml3="

?S:sitehtml3:

?S: This variable contains the name of the directory in which site-specific

?S: library html source pages are to be put. It is the responsibility of the

?S: Makefile.SH to get the value of this into the proper command.

?S: You must be prepared to do the ~name expansion yourself.

?S: The standard distribution will put nothing in this directory.

?S: After perl has
 been installed, users may install their own local
 ?S: library html pages in this directory with
 ?S: MakeMaker Makefile.PL
 ?S: or equivalent. See INSTALL for details.
 ?S:.
 ?D:sitehtml3exp="
 ?S:sitehtml3exp:
 ?S: This variable is the same as the sitehtml3 variable, but is filename
 ?S: expanded at configuration time, for convenient use in makefiles.
 ?S:.
 ?D:installsitehtml3="
 ?S:installsitehtml3:
 ?S: This variable is really the same as sitehtml3exp, unless you are using
 ?S: AFS in which case it points to the read/write location whereas
 ?S: html3direxp only points to the read-only access location. For extra
 ?S: portability, you should only use this variable within your makefiles.
 ?S:.
 ?LINT:change prefixvar
 ?LINT:set installsitehtml3
 ?LINT:set sitehtml3
 ?LINT:set sitehtml3exp
 : determine where add-on library html pages go
 : There is no standard location, so try to copy the previously-selected
 : directory structure for the core html pages.
 case "\$sitehtml3" in
 ") dflt=`echo "\$html3dir"
 | \$sed "s#^\$prefix#\$siteprefix#"` ;;
 *) dflt=\$sitehtml3 ;;
 esac
 case "\$dflt" in
 "| ") dflt=none ;;
 esac
 fn=dn+~
 rp='Pathname where the site-specific library html pages should be installed?'
 ./getfile
 prefixvar=sitehtml3
 ./setprefixvar

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/installdirs/sitehtml3.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_asctime_r.U,v ORCS:

?RCS: Copyright (c) 2002,2003 Jarkko Hietaniemi

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?RCS: Generated by the reentr.pl from the Perl 5.8 distribution.

?RCS:

?MAKE:d_asctime_r asctime_r_proto: Inlibc Protochk Hasproto i_systypes \
 usethreads i_time i_systime extern_C

?MAKE: -pick add \$@ %<

?S:d_asctime_r:

?S: This variable conditionally defines the HAS_ASCTIME_R symbol,
 ?S: which indicates to the C program that the asctime_r()
 ?S: routine is available.

?S:.

?S:asctime_r_proto:

?S: This variable encodes the prototype of asctime_r.
 ?S: It is zero if d_asctime_r is undef, and one of the
 ?S: REENTRANT_PROTO_T_ABC macros of reentr.h if d_asctime_r
 ?S: is defined.

?S:.

?C:HAS_ASCTIME_R:

?C: This symbol, if defined, indicates that the asctime_r routine
 ?C: is available to asctime
 re-entrantly.

?C:.

?C:ASCTIME_R_PROTO:

?C: This symbol encodes the prototype of asctime_r.
 ?C: It is zero if d_asctime_r is undef, and one of the
 ?C: REENTRANT_PROTO_T_ABC macros of reentr.h if d_asctime_r
 ?C: is defined.

?C:.

?H:#\$d_asctime_r HAS_ASCTIME_R /**/
 ?H:#define ASCTIME_R_PROTO \$asctime_r_proto /**/
 ?H:.

?T:try hdrs d_asctime_r_proto
 : see if asctime_r exists
 set asctime_r d_asctime_r
 eval \$inlibc
 case "\$d_asctime_r" in
 "\$define")
 hdrs="\$i_systypes sys/types.h define stdio.h \$i_time time.h \$i_systime sys/time.h"
 case "\$d_asctime_r_proto:\$usethreads" in
 ":define") d_asctime_r_proto=define
 set d_asctime_r_proto asctime_r \$hdrs
 eval \$hasproto ;;
 *) ;;
 esac
 case "\$d_asctime_r_proto" in
 define)
 case "\$asctime_r_proto" in

```

"|0) try='char* asctime_r(const struct tm*, char*);'
./protochk "$extern_C $try" $hdrs && asctime_r_proto=B_SB ;;
esac
case "$asctime_r_proto" in
"|0) try='char* asctime_r(const struct tm*, char*, int);'
./protochk "$extern_C $try"
$hdrs && asctime_r_proto=B_SBI ;;
esac
case "$asctime_r_proto" in
"|0) try='int asctime_r(const struct tm*, char*);'
./protochk "$extern_C $try" $hdrs && asctime_r_proto=I_SB ;;
esac
case "$asctime_r_proto" in
"|0) try='int asctime_r(const struct tm*, char*, int);'
./protochk "$extern_C $try" $hdrs && asctime_r_proto=I_SBI ;;
esac
case "$asctime_r_proto" in
"|0) d_asctime_r=undef
    asctime_r_proto=0
    echo "Disabling asctime_r, cannot determine prototype." >&4 ;;
*) case "$asctime_r_proto" in
    REENTRANT_PROTO*) ;;
    *) asctime_r_proto="REENTRANT_PROTO_$asctime_r_proto" ;;
    esac
    echo "Prototype: $try" ;;
    esac
;;
*) case "$usetthreads" in
    define) echo "asctime_r has no prototype, not using it." >&4 ;;
    esac
    d_asctime_r=undef
    asctime_r_proto=0
    ;;
    esac
;;
*) asctime_r_proto=0
    ;;
    esac

```

Found in path(s):

```

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/threads/d_asctime_r.U

```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_syscall.U 1 2006-08-24 12:32:52Z rmanfredi \$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: \$Log: d_syscall.U,v \$
?RCS: Revision 3.0 1993/08/18 12:07:42 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:d_syscall: Inlibc
?MAKE: -pick add \$@ %<
?S:d_syscall:
?S: This variable conditionally defines HAS_SYSCALL if syscall() is
?S: available call arbitrary system calls.
?S:.
?C:HAS_SYSCALL (SYSCALL):
?C: This symbol, if defined, indicates that the syscall routine is
?C: available to call arbitrary system calls. If undefined, that's tough.
?C:.
?H:#\$d_syscall
HAS_SYSCALL /**/
?H:.
?LINT:set d_syscall
: see if syscall exists
set syscall d_syscall
eval \$inlibc

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/d_syscall.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: \$Log: d_socket.U,v \$
?RCS: Revision 3.0.1.2 1997/02/28 15:46:00 ram
?RCS: patch61: replaced .a with \$_a all over the place
?RCS:
?RCS: Revision 3.0.1.1 1994/01/24 14:08:04 ram

?RCS: patch16: can now safely declare private nm_extract in dependencies

?RCS:

?RCS: Revision 3.0 1993/08/18 12:07:26 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?MAKE:d_socket d_oldsock d_socketpair socketlib sockethdr: contains libc \

echo n c nm_opt nm_extract Inlibc Csym _a

?MAKE: -pick add \$@ %<

?S:d_socket:

?S: This

variable conditionally defines HAS_SOCKET, which indicates

?S: that the BSD socket interface is supported.

?S:.

?S:d_socketpair:

?S: This variable conditionally defines the HAS_SOCKETPAIR symbol, which

?S: indicates that the BSD socketpair() is supported.

?S:.

?S:d_oldsock:

?S: This variable conditionally defines the OLDSOCKET symbol, which

?S: indicates that the BSD socket interface is based on 4.1c and not 4.2.

?S:.

?S:socketlib:

?S: This variable has the names of any libraries needed for socket support.

?S:.

?S:sockethdr:

?S: This variable has any cpp -I flags needed for socket support.

?S:.

?C:HAS_SOCKET (SOCKET):

?C: This symbol, if defined, indicates that the BSD socket interface is

?C: supported.

?C:.

?C:HAS_SOCKETPAIR (SOCKETPAIR):

?C: This symbol, if defined, indicates that the BSD socketpair() call is

?C: supported.

?C:.

?C:USE_OLDSOCKET (OLDSOCKET):

?C: This symbol, if defined, indicates that the 4.1c BSD socket interface

?C: is supported instead of the 4.2/4.3 BSD

socket interface. For instance,

?C: there is no setsockopt() call.

?C:.

?H:#\$d_socket HAS_SOCKET /**/

?H:#\$d_socketpair HAS_SOCKETPAIR /**/

?H:#\$d_oldsock USE_OLDSOCKET /**/

?H:.

?T:val

?LINT:use libc

?LINT:set d_socketpair

```

: see whether socket exists
socketlib=""
sockethdr=""
echo " "
$echo $n "Hmm... $c" >&4
if set socket val -f d_socket; eval $csym; $val; then
echo "Looks like you have Berkeley networking support." >&4
d_socket="$define"
?X: now check for advanced features
if set setsockopt val -f; eval $csym; $val; then
d_oldsock="$undef"
else
echo "...but it uses the old 4.1c interface, rather than 4.2" >&4
d_oldsock="$define"
fi
else
?X: HP-UX, for one, puts all the socket stuff in socklib.o. Note that if we
?X: come here on HP-UX, then we must have used nm to get symbols, or we really
?X: don't have sockets anyway...
if $contains socklib libc.list >/dev/null 2>&1; then
echo "Looks like you have Berkeley networking support." >&4
d_socket="$define"
: we will have
to assume that it supports the 4.2 BSD interface
d_oldsock="$undef"
else
echo "You don't have Berkeley networking in libc$_a..." >&4
?X: look for an optional networking library
if test -f /usr/lib/libnet$_a; then
?X: space between two '(' needed for ksh
( (nm $nm_opt /usr/lib/libnet$_a | eval $nm_extract) || \
ar t /usr/lib/libnet$_a) 2>/dev/null >> libc.list
if $contains socket libc.list >/dev/null 2>&1; then
echo "...but the Wollongong group seems to have hacked it in." >&4
socketlib="-lnet"
sockethdr="-I/usr/netinclude"
d_socket="$define"
?X: now check for advanced features
if $contains setsockopt libc.list >/dev/null 2>&1; then
d_oldsock="$undef"
else
echo "...using the old 4.1c interface, rather than 4.2" >&4
d_oldsock="$define"
fi
else
echo "or even in libnet$_a, which is peculiar." >&4
d_socket="$undef"
d_oldsock="$undef"

```

```
fi
else
echo "or anywhere else I see." >&4
d_socket="$undef"
d_oldsock="$undef"
fi
fi
fi
```

```
@if
HAS_SOCKETPAIR || d_socketpair
: see if socketpair exists
set socketpair d_socketpair
eval $inlibc
```

```
@end
```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/d_socket.U
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 2009 H.Merijn Brand

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?MAKE:d_inetntop: Inlibc

?MAKE: -pick add \$@ %<

?S:d_inetntop:

?S: This variable conditionally defines the HAS_INETNTOP symbol,

?S: which indicates to the C program that the inet_ntop() function

?S: is available.

?S:.

?C:HAS_INETNTOP:

?C: This symbol, if defined, indicates that the inet_ntop() function

?C: is available to parse IPv4 and IPv6 strings.

?C:.

?H:#\$d_inetntop HAS_INETNTOP /**/

?H:.

?LINT:set d_inetntop

: see if inet_ntop exists

set inet_ntop d_inetntop

eval \$inlibc

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_inetntop.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1999, Jarkko Hietaniemi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 3.0.

?RCS:

?MAKE:d_clock_gettime: Inlibc

?MAKE: -pick add \$@ %<

?S:d_clock_gettime:

?S: This variable conditionally defines HAS_CLOCK_GETTIME

?S: if clock_gettime() is available to get the time of a POSIX clock.

?S:.

?C:HAS_CLOCK_GETTIME:

?C: This symbol, if defined, indicates that the clock_gettime

?C: system call is available to get the time of a POSIX clock.

?C:.

?H:#\$d_clock_gettime HAS_CLOCK_GETTIME /**/

?H:.

?LINT:set d_clock_gettime

: see if clock_gettime exists

set clock_gettime d_clock_gettime

eval \$inlibc

Found in path(s):

*

/opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_clock_gettime.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1999, Jarkko Hietaniemi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 3.0.

?RCS:

?MAKE:d_posix_sched: Setvar d_sched_getparam d_sched_setparam d_sched_getscheduler d_sched_setscheduler

```

d_sched_rr_get_interval d_sched_get_priority_min d_sched_get_priority_max i_sched
?MAKE: -pick add $@ %<
?S:d_posix_sched:
?S: This variable conditionally defines the HAS_POSIX_SCHED symbol, which
?S: indicates that the entire POSIX sched_*(2) library is present.
?S:.
?C:HAS_POSIX_SCHED:
?C: This symbol, if defined, indicates that the entire POSIX sched_*(2)
?C: library is supported.
?C:.
?H:#$d_posix_sched HAS_POSIX_SCHED /**/
?H:.
?LINT:set
d_posix_sched
: see how much of the 'POSIX sched_*(2)' library is present.
echo " "
case
"$i_sched$d_sched_getparam$d_sched_getscheduler$d_sched_setscheduler$d_sched_rr_get_interval$d_sched_get_
priority_min$d_sched_get_priority_max$d_sched_setparam" in
*"${undef}*" ) val="${undef}" ;;
*) val="${define}" ;;
esac
case "$val" in
"${define}") echo "You have the full POSIX sched_*(2) library." >&4 ;;
"${undef}") echo "You don't have the full POSIX sched_*(2) library." >&4 ;;
esac
set d_posix_sched
eval $setvar

```

Found in path(s):

```

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/perl/d_posix_sched.U

```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 2001 Jarkko Hietaniemi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 3.0.

?RCS:

?MAKE:d_sresuproto: Hasproto i_unistd

?MAKE: -pick add \$@ %<

?S:d_sresuproto:

?S: This variable conditionally defines the HAS_SETRESUID_PROTO symbol,

?S: which indicates to the C program that the system provides

?S: a prototype for the setresuid() function. Otherwise, it is

?S: up to the program to supply one.

?S:.

?C:HAS_SETRESUID_PROTO:

?C: This symbol, if defined, indicates that the system provides

?C: a prototype for the setresuid() function. Otherwise, it is up

?C: to the program to supply one. Good guesses are

?C: extern

int setresuid(uid_t ruid, uid_t euid, uid_t suid);

?C:.

?H:#\$d_sresuproto HAS_SETRESUID_PROTO /**/

?H:.

?LINT:set d_sresuproto

: see if prototype for setresuid is available

echo " "

set d_sresuproto setresuid \$i_unistd unistd.h

eval \$hasproto

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_sresuproto.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 2001 Jarkko Hietaniemi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 3.0.

?RCS:

?MAKE:d_flockproto: Hasproto i_sysfile

?MAKE: -pick add \$@ %<

?S:d_flockproto:

?S: This variable conditionally defines the HAS_FLOCK_PROTO symbol,

?S: which indicates to the C program that the system provides

?S: a prototype for the flock() function. Otherwise, it is

?S: up to the program to supply one.

?S:.

?C:HAS_FLOCK_PROTO:

?C: This symbol, if defined, indicates that the system provides

?C: a prototype for the flock() function. Otherwise, it is up

?C: to the program to supply one. A good guess is

?C: extern int flock(int,

```
int);
?C:.
?H:#$d_flockproto HAS_FLOCK_PROTO /**/
?H:.
?LINT:set d_flockproto
: see if prototype for flock is available
echo " "
set d_flockproto flock $i_sysfile sys/file.h
eval $hasproto
```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/perl/d_flockproto.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: d_killpg.U 1 2006-08-24 12:32:52Z rmanfredi $
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: $Log: d_killpg.U,v $
?RCS: Revision 3.0 1993/08/18 12:06:27 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?MAKE:d_killpg: Inlibc
?MAKE: -pick add $@ %<
?S:d_killpg:
?S: This variable conditionally defines the HAS_KILLPG symbol, which
?S: indicates to the C program that the killpg() routine is available
?S: to kill process groups.
?S:.
?C:HAS_KILLPG (KILLPG):
?C: This symbol, if defined, indicates that the killpg routine is available
?C: to kill
process groups. If unavailable, you probably should use kill
?C: with a negative process number.
?C:.
?H:#$d_killpg HAS_KILLPG /**/
?H:.
?LINT:set d_killpg
: see if killpg exists
set killpg d_killpg
eval $inlibc
```

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/d_killpg.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 2008 H.Merijn Brand

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?MAKE:d_timegm: Inlibc

?MAKE: -pick add \$@ %<

?S:d_timegm:

?S: This variable conditionally defines the HAS_TIMEGM symbol, which

?S: indicates to the C program that the timegm () routine is available.

?S:.

?C:HAS_TIMEGM:

?C: This symbol, if defined, indicates that the timegm routine is

?C: available to do the opposite of gmtime ()

?C:.

?H:#\$d_timegm HAS_TIMEGM /**/

?H:.

?LINT:set d_timegm

: see if timegm exists

set timegm d_timegm

eval \$inlibc

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_timegm.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: Loc.U,v \$

?RCS: Revision 3.0.1.10 1997/02/28 15:04:16 ram

?RCS: patch61: allow users to specify paths on the command line

?RCS: patch61: will now substitute cp for ln if not supported
?RCS:
?RCS: Revision 3.0.1.9 1995/09/25 09:11:24 ram
?RCS: patch59: commented the purpose of the #un-def directive
?RCS: patch59: abort Configure run when mandatory command is missing
?RCS:
?RCS: Revision 3.0.1.8 1995/07/25 13:40:40 ram
?RCS: patch56: now knows about OS/2 platforms
?RCS:
?RCS: Revision 3.0.1.7
1995/01/11 15:13:37 ram
?RCS: patch45: protected "sh -c" within backquotes for Linux and SGI
?RCS: patch45: added path lookup for the 'comm' program
?RCS:
?RCS: Revision 3.0.1.6 1994/10/29 15:56:14 ram
?RCS: patch36: added ?F: line for metalint file checking
?RCS: patch36: be careful and guard against wildcard searching (ADO)
?RCS:
?RCS: Revision 3.0.1.5 1994/06/20 06:54:55 ram
?RCS: patch30: now locates find
?RCS:
?RCS: Revision 3.0.1.4 1994/05/13 15:18:15 ram
?RCS: patch27: added yacc to the trylist (ADO)
?RCS: patch27: lint lines reformatted (ADO)
?RCS:
?RCS: Revision 3.0.1.3 1994/01/24 14:01:44 ram
?RCS: patch16: added metalint hint on changed PATH variable
?RCS:
?RCS: Revision 3.0.1.2 1993/12/15 08:16:52 ram
?RCS: patch15: now set _test variable when test is built-in
?RCS: patch15: fixed rare cases where echo is not needed
?RCS:
?RCS: Revision 3.0.1.1 1993/09/13 15:47:13 ram
?RCS: patch10: test program not always in /bin/test (WAD)
?RCS:
?RCS: Revision
3.0 1993/08/18 12:05:05 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?X:
?X: This unit produces a shell script "loc" which can be used to find out
?X: where in a list of directories something is. It then uses loc to
?X: determine the location of commonly used programs. It leaves loc sitting
?X: around for other Configure units to use, but arranges for its demise
?X: at the end of Configure.
?X:
?X: To add a new program to find, add it both to the ?MAKE: line and to either
?X: the loclist or trylist variable.

?X:

?X: I put startsh at the end of the dependency list, in order to avoid the

?X: loading of the spitshell unit before the instructions.

?X:

```
?MAKE:Loc awk ar bash bison byacc cat chgrp chmod chown \  
comm compress cp cpio cpp csh date echo egrep emacs expr find flex \  
gmake gzip grep inews ksh less line lint ln lp lpr ls mail mailx \  
make mkdir more mv nm nroff perl pg pmake pr rm rmail sed sendmail \  
shar sleep smail sort submit tail tar tbl tee test touch tr troff
```

\

```
uname uniq uuname vi zcat zip: eunicefix n c startsh Instruct Warn
```

?MAKE: -pick weed \$@ %<

```
?LINT:describe awk ar bash bison byacc cat chgrp chmod chown \  
comm compress cp cpio cpp csh date echo egrep emacs expr find flex \  
gmake gzip grep inews ksh less line lint ln lp lpr ls mail mailx \  
make mkdir more mv nm nroff perl pg pmake pr rm rmail sed sendmail \  
shar sleep smail sort submit tail tar tbl tee test touch tr troff \  
uname uniq uuname vi zcat zip
```

?V::pth loclist trylist

?F:./loc

?T:thisthing thing xxx dir file say DJGPP

?T:_test _grep _cp _gmake _egrep _ln _make dflt

?LINT: change PATH

: find out where common programs are

echo " "

echo " "

echo "Locating common programs..." >&4

cat <<EOOSC >loc

\$startsh

case \$# in

0) exit 1;;

esac

thing=\\$1

shift

dflt=\\$1

shift

for dir in \\$*; do

case "\\$thing" in

.)

if test -d \\$dir/\\$thing; then

echo \\$dir

exit 0

fi

::

*)

?X: Be careful in case thing includes wildcards that might expand to multiple

?X: files. Choose the last one.

This happens when searching for shared

?X: libraries with version numbers. How to choose which one we want is

```

?X: probably an insoluble problem, in general.
?X: Some folks leave things like libc.so.orig around w/o read
?X: permission. A -r test would handle that, but since ./loc is
?X: also used to find executables (which are installed w/o read
?X: permission on SCO ODT 3.0, we can't include the -r test.
for this thing in \${dir}/${thing}; do
: just loop through to pick last item
done
if test -f \${thing}; then
echo \${thing}
exit 0
elif test -f \${thing}_exe; then
echo \${thing}
exit 0
elif test -f \${dir}/${thing}.exe; then
if test -n "$DJGPP"; then
echo \${dir}/${thing}.exe
else
: on Eunice apparently
echo \${dir}/${thing}
fi
fi
exit 0
fi
;;
esac
done
echo \${dflt}
exit 1
EOSC
chmod +x loc
$eunicefix loc
loclist=""
?awk:awk
?cat:cat
?chgrp:chgrp
?chmod:chmod
?chown:chown
?comm:comm
?cp:cp
?echo:echo
?expr:expr
?find:find
?grep:grep
?ls:ls
?mkdir:mkdir
?mv:mv
?rm:rm
?sed:sed

```

?sleep:sleep
?sort:sort
?tail:tail
?touch:touch
?tr:tr
?uniq:uniq
"
trylist="
?Mcc:Mcc
?ar:ar
?bash:bash
?bison:bison
?byacc:byacc
?compress:compress
?cpio:cpio
?cpp:cpp
?csh:csh
?date:date
?egrep:egrep
?emacs:emacs
?flex:flex
?gmake:gmake
?gzip:gzip
?inews:inews
?ksh:ksh
?less:less
?line:line
?lint:lint
?ln:ln
?lp:lp
?lpr:lpr
?mail:mail
?mailx:mailx
?make:make
?more:more
?nm:nm
?nroff:nroff
?perl:perl
?pg:pg
?pmake:pmake
?pr:pr
?rmail:rmail
?sendmail:sendmail
?shar:shar
?smail:smail
?submit:submit
?tar:tar
?tbl:tbl

```

?tee:tee
?test:test
?troff:troff
?uname:uname
?uuname:uuname
?vi:vi
?zcat:zcat
?zip:zip
"
?LINT:set
awk ar bash bison byacc cat chgrp chmod chown \
comm compress cp cpio cpp csh date echo emacs expr find flex \
gmake gzip grep inews ksh less line lint lp lpr ls mail mailx \
mkdir more mv nm nroff perl pg pmake pr rm rmail sed sendmail \
shar sleep smail sort submit tail tar tbl tee touch tr troff \
uname uniq uuname vi zcat zip
pth=`echo $PATH | sed
-e "s/$p_/ /g"`
pth="$pth /lib /usr/lib"
for file in $loclist; do
?X:
?X: Allow them to -Dmake=pmake on the command line for instance...
?X: If the file is not fully qualified, as in -Dmake=pmake, then we
?X: look the for the specified command (pmake here). If they say
?X: -Dmake=/sbin/make for instance, then we make sure the file
?X: exists, or we die...
?X:
eval xxx=\$$file
case "$xxx" in
/*|?:[\\/]*)
if test -f "$xxx"; then
: ok
else
./warn "no $xxx -- ignoring your setting for $file."
xxx=`./loc $file $file $pth`
fi
;;
*) xxx=`./loc $file $file $pth`;
*) xxx=`./loc $xxx $xxx $pth`;
esac
eval $file=$xxx$_exe
eval _$file=$xxx
case "$xxx" in
/*)
echo $file is in $xxx.
;;
?X: Under OS/2, we have PC-like paths
?:[\\/]*)

```

```

echo $file is in $xxx.
;;
*)
echo "I don't know where '$file' is, and my life depends on it." >&4
echo "Go find a public domain implementation or fix your PATH setting!" >&4
exit 1
;;
esac
done
echo " "
echo "Don't worry
if any of the following aren't found..."
say=offhand
for file in $trylist; do
?X: Allow them to -Dmake=pmake on the command line for instance (see above)
eval xxx=\$$file
case "$xxx" in
/*|?:[\\|/]*)
if test -f "$xxx"; then
: ok
else
./warn "no $xxx -- ignoring your setting for $file."
xxx=`./loc $file $file $pth`
fi
;;
") xxx=`./loc $file $file $pth`;
*) xxx=`./loc $xxx $xxx $pth`;
esac
eval $file=$xxx$_exe
eval _$file=$xxx
case "$xxx" in
/*)
echo $file is in $xxx.
;;
?X: Under OS/2, we have PC-like paths
?:[\\|/]*)
echo $file is in $xxx.
;;
*)
echo "I don't see $file out there, $say."
say=either
;;
esac
done
case "$egrep" in
egrep)
echo "Substituting grep for egrep."
egrep=$grep

```

```

_egrep=$_grep
;;
esac
@if ln
case "$ln" in
ln)
echo "Substituting cp for ln."
ln=$cp
_ln=$_cp
;;
esac
@end
@if make || gmake
case "$make" in
make)
case "$gmake" in
gmake)
echo "I can't find make or gmake, and my life depends on it." >&4
echo "Go find a
public domain implementation or fix your PATH setting!" >&4
exit 1
;;
esac
;;
esac
case "$gmake" in
gmake) ;;
*) # We can't have osname yet.
if test -f "/system/gnu_library/bin/ar.pm"; then # Stratus VOS
# Assume that gmake, if found, is definitely GNU make
# and prefer it over the system make.
echo "Substituting gmake for make."
make=$gmake
_make=$_gmake
fi
;;
esac
@end
case "$test" in
test)
echo "Hopefully test is built into your sh."
;;
*)
if `sh -c "PATH= test true" >/dev/null 2>&1`; then
echo "Using the test built into your sh."
?X:
?X: We need to set both test and _test, since Oldconfig.U will use the _test
?X: value to systematically restore computed paths, which may be wrong if

```

?X: we choose to load an old config.sh generated on another platform.

?X:

```
test=test
_test=test
fi
;;
esac
?LINT:change n c
case "$echo" in
echo)
echo "Hopefully echo is built into your sh."
;;
?X: For those rare cases where we don't need $echo...
") ;;
*)
echo " "
echo "Checking
compatibility between $echo and builtin echo (if any)..." >&4
$echo $n "hi there$c" >foo1
echo $n "hi there$c" >foo2
if cmp foo1 foo2 >/dev/null 2>&1; then
echo "They are compatible. In fact, they may be identical."
else
case "$n" in
'-n') n=" c='\c';;
*) n='-n' c="";;
esac
cat <<FOO
```

They are not compatible! You are probably running ksh on a non-USG system.

I'll have to use \$echo instead of the builtin, since Bourne shell doesn't have echo built in and we may have to run some Bourne shell scripts. That means I'll have to use '\$n\$c' to suppress newlines now. Life is ridiculous.

FOO

```
$echo $n "The star should be here-->$c"
$echo "*"
fi
$rm -f foo1 foo2
;;
esac
```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/Loc.U
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 2001 Jarkko Hietaniemi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 3.0.
?RCS:
?MAKE:d_socketmarkproto: Hasproto d_socket
?MAKE: -pick add \$@ %<
?S:d_socketmarkproto:
?S: This variable conditionally defines the HAS_SOCKETMARK_PROTO symbol,
?S: which indicates to the C program that the system provides
?S: a prototype for the socketmark() function. Otherwise, it is
?S: up to the program to supply one.
?S:.
?C:HAS_SOCKETMARK_PROTO:
?C: This symbol, if defined, indicates that the system provides
?C: a prototype for the socketmark() function. Otherwise, it is up
?C: to the program to supply one. A good
guess is
?C: extern int socketmark(int);
?C:.
?H:#\$d_socketmarkproto HAS_SOCKETMARK_PROTO /**/
?H:.
?LINT:set d_socketmarkproto
: see if prototype for socketmark is available
echo " "
set d_socketmarkproto socketmark \$d_socket sys/socket.h
eval \$hasproto

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_socketmarkproto.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_ctime_r.U,v 0RCS:
?RCS: Copyright (c) 2002,2003 Jarkko Hietaniemi
?RCS:
?RCS: You may distribute under the terms of either the GNU General Public
?RCS: License or the Artistic License, as specified in the README file.
?RCS:
?RCS: Generated by the reentr.pl from the Perl 5.8 distribution.
?RCS:
?MAKE:d_ctime_r ctime_r_proto: Inlibc Protochk Hasproto i_systypes \
usethreads i_time i_systime extern_C
?MAKE: -pick add \$@ %<
?S:d_ctime_r:

?S: This variable conditionally defines the HAS_CTIME_R symbol,
?S: which indicates to the C program that the ctime_r()
?S: routine is available.
?S:.
?S:ctime_r_proto:
?S: This variable encodes the prototype of ctime_r.
?S: It is zero if d_ctime_r is undef, and one of the
?S: REENTRANT_PROTO_T_ABC macros of reentr.h if d_ctime_r
?S: is defined.
?S:.
?C:HAS_CTIME_R:
?C: This symbol, if defined, indicates that the ctime_r routine
?C: is available to ctime re-entrantly.
?C:.
?C:CTIME_R_PROTO:
?C: This
symbol encodes the prototype of ctime_r.
?C: It is zero if d_ctime_r is undef, and one of the
?C: REENTRANT_PROTO_T_ABC macros of reentr.h if d_ctime_r
?C: is defined.
?C:.
?H:#\$d_ctime_r HAS_CTIME_R /**/
?H:#define CTIME_R_PROTO \$ctime_r_proto /**/
?H:.
?T:try hdrs d_ctime_r_proto
: see if ctime_r exists
set ctime_r d_ctime_r
eval \$inlibc
case "\$d_ctime_r" in
"\$define")
hdrs="\$i_systypes sys/types.h define stdio.h \$i_time time.h \$i_systime sys/time.h"
case "\$d_ctime_r_proto:\$usethreads" in
":define") d_ctime_r_proto=define
set d_ctime_r_proto ctime_r \$hdrs
eval \$hasproto ;;
*) ;;
esac
case "\$d_ctime_r_proto" in
define)
case "\$ctime_r_proto" in
"|0) try='char* ctime_r(const time_t*, char*);'
./protochk "\$extern_C \$try" \$hdrs && ctime_r_proto=B_SB ;;
esac
case "\$ctime_r_proto" in
"|0) try='char* ctime_r(const time_t*, char*, int);'
./protochk "\$extern_C \$try" \$hdrs && ctime_r_proto=B_SBI ;;
esac
case "\$ctime_r_proto" in

```

"|0) try='int
ctime_r(const time_t*, char*);'
./protochk "$extern_C $try" $hdrs && ctime_r_proto=I_SB ;;
esac
case "$ctime_r_proto" in
"|0) try='int ctime_r(const time_t*, char*, int);'
./protochk "$extern_C $try" $hdrs && ctime_r_proto=I_SBI ;;
esac
case "$ctime_r_proto" in
"|0) d_ctime_r=undef
    ctime_r_proto=0
    echo "Disabling ctime_r, cannot determine prototype." >&4 ;;
*) case "$ctime_r_proto" in
    REENTRANT_PROTO*) ;;
*) ctime_r_proto="REENTRANT_PROTO_$ctime_r_proto" ;;
esac
echo "Prototype: $try" ;;
esac
;;
*) case "$susetthreads" in
define) echo "ctime_r has no prototype, not using it." >&4 ;;
esac
d_ctime_r=undef
ctime_r_proto=0
;;
esac
;;
*) ctime_r_proto=0
;;
esac

```

Found in path(s):

```

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/threads/d_ctime_r.U

```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: inc.U 1 2006-08-24 12:32:52Z rmanfredi \$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic Licence,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic Licence; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: \$Log: inc.U,v \$

?RCS: Revision 3.0 1993/08/18 12:08:51 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?MAKE:inc incexp: Loc Oldconfig Getfile us rinc

?MAKE: -pick add \$@ %<

?S:inc:

?S: This variable holds the name of the directory in which the user wants

?S: to put public header files for the package in question. It is most

?S: often a local directory such as /usr/local/include.

?S:.

?S:incexp:

?S: This is the same as the inc variable, but is filename

expanded

?S: at configuration time for convenient use in your makefiles.

?S:.

: determine where public header files go

case "\$inc" in

")

dflt=`./loc . ." /usr/local/include /usr/include/local \$usrinc`

;;

*) dflt="\$inc"

;;

esac

fn=d~

rp="Where do you want to put the public header files?"

./getfile

inc="\$ans"

incexp="\$ansexp"

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/inc.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: usedtrace.U,v \$

?RCS:

?RCS: Copyright (c) 2008 H.Merijn Brand

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?RCS: \$Log: usedtrace.U,v \$

?RCS:

?MAKE:usedtrace dtrace: Myread Oldconfig Setvar Getfile test

?MAKE: -pick add \$@ %<

?Y:TOP

?S:usedtrace:

?S: This variable indicates whether we are compiling with dtrace

?S: support. See also dtrace.

```

?S:
?S:dtrace:
?S: This variable holds the location of the dtrace executable.
?S:
?C:USE_DTRACE:
?C: This symbol, if defined, indicates that Perl should
?C: be built with support for DTrace.
?C:
?H:#$usedtrace USE_DTRACE /**/
?H:
?T:dflt_dtrace
?LINT:set usedtrace
?LINT:set dtrace
: DTrace support
dflt_dtrace='/usr/sbin/dtrace'
$test -x /usr/bin/dtrace && dflt_dtrace='/usr/bin/dtrace'

cat <<EOM

```

Perl can be built to support DTrace on platforms that support it.
DTrace is a diagnosis and performance analysis tool from Sun.

If this doesn't make any sense to you, just accept the default.
EOM

```

while $test 1 ; do
case "$usedtrace" in
$define|true|[yY]*)
dflt='y'
;;
?*)
dflt='y'
dflt_dtrace=$usedtrace
;;
*)
dflt='n'
;;
esac

rp='Support DTrace if available?'
./myread
case "$ans" in
y|Y) val="$define" ;;
*) val="$undef" ;;
esac
set usedtrace
eval $setvar

```

```

test "X$usedtrace" != "X$define" && break

echo " "
rp='Where is the dtrace executable?'
dflt=$dflt_dtrace
./getfile
val="$ans"
set dtrace
eval $setvar

if $test -f $dtrace
then
if $dtrace -h -s ../perldtrace.d \
-o perldtrace.tmp >/dev/null 2>&1 \
&& rm -f perldtrace.tmp
then
echo " "
echo "Good: your $dtrace knows about the -h flag."
else
cat >&2 <<EOM

*** $me: Fatal Error: $dtrace doesn't support -h flag
***
*** Your installed dtrace doesn't support the -h switch to compile a D
*** program into a C header. Can't continue.

EOM
exit
1
fi
break;
fi

case "$fastread" in
yes)
cat >&2 <<EOM

*** $me: Fatal Error: $dtrace not found.
*** Can't continue.

EOM
exit 1
;;
*)
echo "*** $dtrace was not found."
echo " "
;;

```

esac
done

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/usedtrace.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: perl.v.U,v 1.1 2000/08/31 17:53:56 jhi Exp jhi \$

?RCS:

?RCS: Copyright (c) 1999 Jarkko Hietaniemi

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?MAKE:ivtype uvtype nvtype ivsize uvsize nvsize \
i8type u8type i16type u16type i32type u32type i64type u64type \
i8size u8size i16size u16size i32size u32size i64size u64size \
d_nv_preserves_uv nv_preserves_uv_bits nv_overflows_integers_at \
d_nv_zero_is_allbits_zero: \
echo rm_try use64bitint d_quad quadtype uquadtype usequadmath \
d_longdbl uselongdouble longdblsize doublesize i_quadmath \
shortsize intsize longsize i_stdlib i_string libs gccversion \
cat Compile i_inttypes test d_volatile signal_t run

?MAKE: -pick add \$@ %<
?S:ivtype:
?S: This variable contains the C type used for Perl's IV.
?S:.
?S:uvtype:
?S: This variable
contains the C type used for Perl's UV.
?S:.
?S:nvtype:
?S: This variable contains the C type used for Perl's NV.
?S:.
?S:i8type:
?S: This variable contains the C type used for Perl's I8.
?S:.
?S:u8type:
?S: This variable contains the C type used for Perl's U8.
?S:.
?S:i16type:
?S: This variable contains the C type used for Perl's I16.
?S:.
?S:u16type:
?S: This variable contains the C type used for Perl's U16.
?S:.
?S:i32type:

?S: This variable contains the C type used for Perl's I32.
?S:.
?S:u32type:
?S: This variable contains the C type used for Perl's U32.
?S:.
?S:i64type:
?S: This variable contains the C type used for Perl's I64.
?S:.
?S:u64type:
?S: This variable contains the C type used for Perl's U64.
?S:.
?S:ivsize:
?S: This variable is the size of an IV in bytes.
?S:.
?S:uvsize:
?S: This variable is the size of a UV in bytes.
?S:.
?S:i8size:
?S: This variable is the size of an I8 in bytes.
?S:.
?S:u8size:
?S: This variable is the size of an U8 in bytes.
?S:.
?S:i16size:
?S: This
variable is the size of an I16 in bytes.
?S:.
?S:u16size:
?S: This variable is the size of an U16 in bytes.
?S:.
?S:i32size:
?S: This variable is the size of an I32 in bytes.
?S:.
?S:u32size:
?S: This variable is the size of an U32 in bytes.
?S:.
?S:i64size:
?S: This variable is the size of an I64 in bytes.
?S:.
?S:u64size:
?S: This variable is the size of an U64 in bytes.
?S:.
?S:nvsize:
?S: This variable is the size of a Perl NV in bytes.
?S: Note that some floating point formats have unused bytes.
?S:.
?S:d_nv_preserves_uv:
?S: This variable indicates whether a variable of type nvtype

?S: can preserve all the bits a variable of type uvtype.
?S:.
?S:nv_preserves_uv_bits:
?S: This variable indicates how many of bits type uvtype
?S: a variable nvtype can preserve.
?S:.
?S:nv_overflows_integers_at:
?S: This variable gives the largest integer value that NVs can hold
?S: as a constant floating point expression.
?S: If it could not be determined, it holds the value 0.
?S:.
?S:d_nv_zero_is_allbits_zero:
?S: This
variable indicates whether a variable of type nvtype
?S: stores 0.0 in memory as all bits zero.
?S:.
?C:IVTYPE:
?C: This symbol defines the C type used for Perl's IV.
?C:.
?C:UVTYPE:
?C: This symbol defines the C type used for Perl's UV.
?C:.
?C:I8TYPE:
?C: This symbol defines the C type used for Perl's I8.
?C:.
?C:U8TYPE:
?C: This symbol defines the C type used for Perl's U8.
?C:.
?C:I16TYPE:
?C: This symbol defines the C type used for Perl's I16.
?C:.
?C:U16TYPE:
?C: This symbol defines the C type used for Perl's U16.
?C:.
?C:I32TYPE:
?C: This symbol defines the C type used for Perl's I32.
?C:.
?C:U32TYPE:
?C: This symbol defines the C type used for Perl's U32.
?C:.
?C:I64TYPE:
?C: This symbol defines the C type used for Perl's I64.
?C:.
?C:U64TYPE:
?C: This symbol defines the C type used for Perl's U64.
?C:.
?C:NVTYPE:
?C: This symbol defines the C type used for Perl's NV.

?C:.

?C:IVSIZE:

?C: This symbol contains the sizeof(IV).

?C:.

?C:UVSIZE:

?C: This

symbol contains the sizeof(UV).

?C:.

?C:I8SIZE:

?C: This symbol contains the sizeof(I8).

?C:.

?C:U8SIZE:

?C: This symbol contains the sizeof(U8).

?C:.

?C:I16SIZE:

?C: This symbol contains the sizeof(I16).

?C:.

?C:U16SIZE:

?C: This symbol contains the sizeof(U16).

?C:.

?C:I32SIZE:

?C: This symbol contains the sizeof(I32).

?C:.

?C:U32SIZE:

?C: This symbol contains the sizeof(U32).

?C:.

?C:I64SIZE:

?C: This symbol contains the sizeof(I64).

?C:.

?C:U64SIZE:

?C: This symbol contains the sizeof(U64).

?C:.

?C:NVSIZE:

?C: This symbol contains the sizeof(NV).

?C: Note that some floating point formats have unused bytes.

?C: The most notable example is the x86* 80-bit extended precision

?C: which comes in byte sizes of 12 and 16 (for 32 and 64 bit

?C: platforms, respectively), but which only uses 10 bytes.

?C: Perl compiled with -Duselongsdouble on x86* is like this.

?C:.

?C:NV_PRESERVES_UV:

?C: This symbol, if defined, indicates that a variable of type NVTYPE

?C: can preserve all the bits of a variable

of type UVTYPE.

?C:.

?C:NV_PRESERVES_UV_BITS:

?C: This symbol contains the number of bits a variable of type NVTYPE

?C: can preserve of a variable of type UVTYPE.

```

?C:.
?C:NV_OVERFLOWES_INTEGERS_AT:
?C: This symbol gives the largest integer value that NVs can hold. This
?C: value + 1.0 cannot be stored accurately. It is expressed as constant
?C: floating point expression to reduce the chance of decimal/binary
?C: conversion issues. If it can not be determined, the value 0 is given.
?C:.
?C:NV_ZERO_IS_ALLBITS_ZERO:
?C: This symbol, if defined, indicates that a variable of type NVTYPE
?C: stores 0.0 in memory as all bits zero.
?C:.
?H:#define IVTYPE $ivtype /**/
?H:#define UVTYPE $uvtype /**/
?H:#define I8TYPE $i8type /**/
?H:#define U8TYPE $u8type /**/
?H:#define I16TYPE $i16type /**/
?H:#define U16TYPE $u16type /**/
?H:#define I32TYPE $i32type /**/
?H:#define U32TYPE $u32type /**/
?H:??<:#ifdef HAS_QUAD
?H:??<:#define I64TYPE $i64type /**/
?H:??<:#define U64TYPE $u64type /**/
?H:??<:#endif
?H:#define NVTYPE $nvtype /**/
?H:#define IVSIZE $ivsize /**/
?H:#define UVSIZE $uvsize /**/
?H:#define I8SIZE $i8size /**/
?H:#define U8SIZE $u8size /**/
?H:#define I16SIZE $i16size /**/
?H:#define U16SIZE $u16size /**/
?H:#define I32SIZE $i32size /**/
?H:#define U32SIZE $u32size /**/
?H:??<:#ifdef
HAS_QUAD
?H:??<:#define I64SIZE $i64size /**/
?H:??<:#define U64SIZE $u64size /**/
?H:??<:#endif
?H:#define NVSIZE $nvsize /**/
?H:$d_nv_preserves_uv NV_PRESERVES_UV
?H:#define NV_PRESERVES_UV_BITS $nv_preserves_uv_bits
?H:#define NV_OVERFLOWES_INTEGERS_AT $nv_overflows_integers_at
?H:$d_nv_zero_is_allbits_zero NV_ZERO_IS_ALLBITS_ZERO
?H:??<:#if UVSIZE == 8
?H:??<:# ifdef BYTEORDER
?H:??<:# if BYTEORDER == 0x1234
?H:??<:# undef BYTEORDER
?H:??<:# define BYTEORDER 0x12345678
?H:??<:# else

```

```

?H:?%<:#      if BYTEORDER == 0x4321
?H:?%<:#      undef BYTEORDER
?H:?%<:#      define BYTEORDER 0x87654321
?H:?%<:#
        endif
?H:?%<:#      endif
?H:?%<:#      endif
?H:?%<:#endif
?H:
?T:volatile
?T:xxx
?T:d
?F:!try
: Check basic sizes
echo " "
$echo "Choosing the C types to be used for Perl's internal types..." >&4

```

```

case "$use64bitint:$d_quad:$quadtype" in
define:define:?)
ivtype="$quadtype"
uvtype="$quatype"
ivsize=8
uvsize=8
;;
*) ivtype="long"
uvtype="unsigned long"
ivsize=$longsize
uvsize=$longsize
;;
esac

```

```

case "$uselongdouble:$d_longdbl" in
define:define)
nvtype="long double"
nvsize=$longdblsize
;;
*) nvtype=double
nvsize=$doublesize
;;
esac

```

```

case "$usequadmath:$i_quadmath" in
define:define)
nvtype="__float128"
nvsize=16
case "$libs" in
*quadmath*) ;;
*) $cat <<EOM >&4

```

```
*** You requested the use of the quadmath library, but you
*** do not seem to have the quadmath library installed.
*** Cannot continue, aborting.
```

```
EOM
```

```
    exit 1
;;
esac
;;
define:*) $cat <<EOM >&4
```

```
*** You requested the use of the quadmath library, but you
*** do not seem to
have the required header, <quadmath.h>.
```

```
EOM
```

```
case "$gccversion" in
[23].*[4.[0-5]*)
    $cat <<EOM >&4
*** Your gcc looks a bit old:
*** $gccversion
```

```
EOM
```

```
;;
")
    $cat <<EOM >&4
*** You are not running a gcc.
```

```
EOM
```

```
;;
esac
$cat <<EOM >&4
*** For the quadmath library you need at least gcc 4.6.
*** Cannot continue, aborting.
```

```
EOM
```

```
exit 1
;;
esac
```

```
$echo "(IV will be "$ivtype", $ivsize bytes)"
$echo "(UV will be "$uvtype", $uvsize bytes)"
$echo "(NV will be "$nvtype", $nvsize bytes)"
```

```
$cat >try.c <<EOCP
#i_inttypes I_INTTYPES
#ifdef I_INTTYPES
#include <inttypes.h>
#endif
#include <stdio.h>
int main() {
#ifdef INT8
```

```

int8_t i = INT8_MAX;
uint8_t u = UINT8_MAX;
printf("int8_t\n");
#endif
#ifdef INT16
int16_t i = INT16_MAX;
uint16_t u = UINT16_MAX;
printf("int16_t\n");
#endif
#ifdef INT32
int32_t i = INT32_MAX;
uint32_t u = UINT32_MAX;
printf("int32_t\n");
#endif
}
EOCP

```

```

i8type="signed char"
u8type="unsigned char"
i8size=1
u8size=1

```

```

case "$i16type" in
") case
"$shortsize" in
2) i16type=short
u16type="unsigned short"
i16size=$shortsize
u16size=$shortsize
;;
esac
;;
esac

```

```

case "$i16type" in
") set try -DINT16
if eval $compile; then
case "$run ./try`" in
int16_t)
i16type=int16_t
u16type=uint16_t
i16size=2
u16size=2
;;
esac
fi
;;
esac
case "$i16type" in

```

```
) if $test $shortsize -ge 2; then
  i16type=short
  u16type="unsigned short"
  i16size=$shortsize
  u16size=$shortsize
fi
;;
esac
```

```
case "$i32type" in
  *) case "$longsize" in
    4) i32type=long
       u32type="unsigned long"
       i32size=$longsize
       u32size=$longsize
      ;;
    *) case "$intsize" in
      4) i32type=int
         u32type="unsigned int"
         i32size=$intsize
         u32size=$intsize
        ;;
      esac
    ;;
  esac
```

```
;;
esac
;;
esac
```

```
case "$i32type" in
  *) set try -DINT32
     if eval $compile; then
       case "$run ./try`" in
         int32_t)
           i32type=int32_t
           u32type=uint32_t
           i32size=4
           u32size=4
           ;;
         esac
       fi
     ;;
  esac
```

```
;;
esac
case "$i32type" in
  *) if $test $intsize -ge 4; then
     i32type=int
     u32type="unsigned
int"
     i32size=$intsize
     u32size=$intsize
```

```
fi
;;
esac
```

```
case "$i64type" in
") case "$d_quad:$quadtype" in
define:?)
i64type="$quadtype"
u64type="$uquadtype"
i64size=8
u64size=8
;;
esac
;;
esac
```

```
$echo "Checking how many bits of your UVs your NVs can preserve..." >&4
```

```
: volatile so that the compiler has to store it out to memory.
```

```
if test X"$d_volatile" = X"$define"; then
```

```
volatile=volatile
```

```
fi
```

```
$cat <<EOP >try.c
```

```
#include <stdio.h>
```

```
#$i_stdlib I_STDLIB
```

```
#ifdef I_STDLIB
```

```
#include <stdlib.h>
```

```
#endif
```

```
#include <sys/types.h>
```

```
#include <signal.h>
```

```
#ifdef SIGFPE
```

```
$volatile int bleched = 0;
```

```
$signal_t blech(int s) { bleched = 1; }
```

```
#endif
```

```
int main() {
```

```
    $svtype u = 0;
```

```
    $nvtype d;
```

```
    int n = 8 * $svsize;
```

```
    int i;
```

```
#ifdef SIGFPE
```

```
    signal(SIGFPE, blech);
```

```
#endif
```

```
for (i = 0; i < n; i++) {
```

```
    u = u << 1 | ($svtype)1;
```

```
    d = ($nvtype)u;
```

```
    if (($svtype)d != u)
```

```
        break;
```

```
    if (d <= 0)
```

```

break;
    d = ($nvtype)(u - 1);
    if (($svtype)d
!= (u - 1))
        break;
#ifdef SIGFPE
    if (bletched)
break;
#endif
    }
    printf("%d\n", ((i == n) ? -n : i));
    exit(0);
}
EOP
set try

d_nv_preserves_uv="$undef"
if eval $compile; then
    nv_preserves_uv_bits="$run ./try`"
fi
case "$nv_preserves_uv_bits" in
\[1-9]*)
    nv_preserves_uv_bits=`expr 0 - $nv_preserves_uv_bits`
    $echo "Your NVs can preserve all $nv_preserves_uv_bits bits of your UVs." 2>&1
    d_nv_preserves_uv="$define"
    ;;
[1-9]*) $echo "Your NVs can preserve only $nv_preserves_uv_bits bits of your UVs." 2>&1
    d_nv_preserves_uv="$undef" ;;
*) $echo "Can't figure out how many bits your NVs preserve." 2>&1
    nv_preserves_uv_bits="0" ;;
esac
$rm_try

$echo "Checking to find the largest integer value your NVs can hold..." >&4
: volatile so that the compiler has to store it out to memory.
if test X"$d_volatile" = X"$define"; then
    volatile=volatile
fi
$cat <<EOP >try.c
#include <stdio.h>

typedef $nvtype NV;

int
main() {
    NV value = 2;
    int count = 1;

```

```

while(count
< 256) {
    $volatile NV up = value + 1.0;
    $volatile NV negated = -value;
    $volatile NV down = negated - 1.0;
    $volatile NV got_up = up - value;
    int up_good = got_up == 1.0;
    int got_down = down - negated;
    int down_good = got_down == -1.0;

    if (down_good != up_good) {
        fprintf(stderr,
            "Inconsistency - up %d %f; down %d %f; for 2**%d (%.20f)\n",
            up_good, (double) got_up, down_good, (double) got_down,
            count, (double) value);
        return 1;
    }
    if (!up_good) {
        while (1) {
if (count > 8) {
            count -= 8;
            fputs("256.0", stdout);
        } else {
            count--;
            fputs("2.0", stdout);
        }
    }
    if (!count) {
        puts("");
        return 0;
    }
    fputs("2.0", stdout);
    }
    }
    value *= 2;
    ++count;
}
fprintf(stderr, "Cannot overflow integer range, even at 2**%d (%.20f)\n",
    count, (double) value);
return 1;
}
EOP
set try

nv_overflows_integers_at='0'
if eval $compile; then
    xxx="$run ./try`"
    case "$?" in
    0)

```

```
case "$xxx" in
2*) cat >&4 <<EOM
The largest integer your NVs can preserve is equal to $xxx
EOM
```

```
nv_overflows_integers_at="$xxx"
```

```
::
```

```
*) cat >&4 <<EOM
```

Cannot determine the largest integer value your NVs can hold, unexpected output

```
'$xxx'
```

```
EOM
```

```
::
```

```
esac
```

```
::
```

```
*) cat >&4 <<EOM
```

Cannot determine the largest integer value your NVs can hold

```
EOM
```

```
::
```

```
esac
```

```
fi
```

```
$rm_try
```

```
$echo "Checking whether NV 0.0 is all bits zero in memory..." >&4
```

```
: volatile so that the compiler has to store it out to memory.
```

```
if test X"$d_volatile" = X"$define"; then
```

```
volatile=volatile
```

```
fi
```

```
$cat <<EOP >try.c
```

```
#include <stdio.h>
```

```
#$i_stdlib I_STDLIB
```

```
#ifdef I_STDLIB
```

```
#include <stdlib.h>
```

```
#endif
```

```
#$i_string I_STRING
```

```
#ifdef I_STRING
```

```
# include <string.h>
```

```
#else
```

```
# include <strings.h>
```

```
#endif
```

```
#include <sys/types.h>
```

```
#include <signal.h>
```

```
#ifdef SIGFPE
```

```
$volatile int bletched = 0;
```

```
$signal_t blech(int s) { bletched = 1; }
```

```
#endif
```

```
int checkit($nvtype d, const char *where) {
```

```
void *v = &d;
```

```

    unsigned char *p
= (unsigned char *)v;
    unsigned char *end = p + sizeof(d);
    int fail = 0;

    while (p < end)
fail += *p++;

    if (!fail)
return 0;

    p = (unsigned char *)v;
    printf("No - %s: 0x", where);
    while (p < end)
printf ("%02X", *p++);
    printf("\n");
    return 1;
}

int main(int argc, char **argv) {
    $nctype d = 0.0;
    int fail = 0;
    fail += checkit(d, "0.0");

    /* The compiler shouldn't be assuming that bletched is 0 */
    d = bletched;

    fail += checkit(d, "bleched");

#ifdef SIGFPE
    signal(SIGFPE, blech);
#endif

    /* Paranoia - the compiler should have no way of knowing that ANSI says
    that argv[argc] will always be NULL. Actually, if it did assume this it
    would be buggy, as this is C and main() can be called from elsewhere in
    the program. */
    d = argv[argc] ? 1 : 0;

    if (d) {
printf("Odd argv[argc]=%p, d=%g\n", argv[argc], d);
    }

    fail += checkit(d, "ternary");

    memset(&d, sizeof(d), argv[argc] ? 1 :
0);

```

```

    if (d != 0.0) {
printf("No - memset doesn't give 0.0\n");
/* This might just blow up: */
printf("(gives %g)\n", d);
return 1;
    }

#ifdef SIGFPE
    if (bletched) {
printf("No - something bleched\n");
return 1;
    }
#endif
    if (fail) {
printf("No - %d fail(s)\n", fail);
return 1;
    }
printf("Yes\n");
return 0;
}
EOP
set try

d_nv_zero_is_allbits_zero="$undef"
if eval $compile; then
    xxx="$run ./try`"
    case "$?" in
0)
        case "$xxx" in
Yes) cat >&4 <<EOM
0.0 is represented as all bits zero in memory
EOM
            d_nv_zero_is_allbits_zero="$define"
            ;;
*) cat >&4 <<EOM
0.0 is not represented as all bits zero in memory
EOM
            d_nv_zero_is_allbits_zero="$undef"
            ;;
esac
            ;;
*) cat >&4 <<EOM
0.0 is not represented as all bits zero in memory
EOM
            d_nv_zero_is_allbits_zero="$undef"
            ;;
esac
fi

```

\$rm_try

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/perlrv.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 2000 Jarkko Hietaniemi

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?MAKE:d_lchmod: Inlibc

?MAKE: -pick add \$@ %<

?S:d_lchmod:

?S: This variable conditionally defines the HAS_LCHMOD symbol, which

?S: indicates to the C program that the lchmod() routine is available.

?S:.

?C:HAS_LCHMOD:

?C: This symbol, if defined, indicates that the lchmod routine is

?C: available to change symbolic link modes.

?C:.

?H:#\$d_lchmod HAS_LCHMOD /**/

?H:.

?LINT:set d_lchmod

: see if lchmod exists

set lchmod d_lchmod

eval \$inlibc

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_lchmod.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_tcstpgrp.U 1 2006-08-24 12:32:52Z rmanfredi \$

?RCS:

?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic Licence,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic Licence; a copy of which may be found at the root

?RCS: of the source tree for dist 4.0.

?RCS:

?RCS: Original Author: Andy Dougherty <doughera@lafcol.lafayette.edu>

?RCS:

```

?RCS: $Log: d_tcsetpgrp.U,v $
?RCS: Revision 3.0.1.1 1994/08/29 16:12:11 ram
?RCS: patch32: created by ADO
?RCS:
?MAKE:d_tcsetpgrp: Inlibc
?MAKE: -pick add $@ %<
?S:d_tcsetpgrp:
?S: This variable conditionally defines the HAS_TCSETPGRP symbol, which
?S: indicates to the C program that the tcsetpgrp() routine is available
?S: to set foreground process group ID.
?S:.
?C:HAS_TCSETPGRP
:
?C: This symbol, if defined, indicates that the tcsetpgrp routine is
?C: available to set foreground process group ID.
?C:.
?H:#$d_tcsetpgrp HAS_TCSETPGRP /**/
?H:.
?LINT:set d_tcsetpgrp
: see if tcsetpgrp exists
set tcsetpgrp d_tcsetpgrp
eval $inlibc

```

Found in path(s):

```

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/d_tcsetpgrp.U

```

No license file was found, but licenses were detected in source scan.

```

?RCS: $Id: Warn_v7EXT.U 1 2006-08-24 12:32:52Z rmanfredi $
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: $Log: Warn_v7EXT.U,v $
?RCS: Revision 3.0.1.1 1994/10/29 16:01:42 ram
?RCS: patch36: call ./v7 explicitly instead of relying on PATH
?RCS:
?RCS: Revision 3.0 1993/08/18 12:05:17 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?X:
?X: This unit issues warnings to V7 sites that they are living dangerously.
?X: This unit needs to get mentioned in End.U to get included.

```

```
?X:
?MAKE:Warn_v7EXT: package Guess
?MAKE: -pick add $@ %<
: Warnings
if ./v7;
then
cat <<EOM
```

NOTE: the V7 compiler may ignore some #undefs that \$package uses. If so, you may get messages about redefining EXT. Some V7 compilers also have difficulties with #defines near buffer boundaries, so beware. You may have to play with the spacing in some .h files, believe it or not.

```
EOM
fi
```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/Warn_v7EXT.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: MailAuthor.U 1 2006-08-24 12:32:52Z rmanfredi $
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic Licence,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic Licence; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: Original Author: Graham Stoney <greyham@research.canon.oz.au>
?RCS:
?RCS: $Log: MailAuthor.U,v $
?RCS: Revision 3.0.1.5 1997/02/28 15:04:41 ram
?RCS: patch61: added support for src.U
?RCS:
?RCS: Revision 3.0.1.4 1994/08/29 16:05:09 ram
?RCS: patch32: avoid message sending if they said no previously
?RCS:
?RCS: Revision 3.0.1.3 1993/10/16 13:47:30 ram
?RCS: patch12: now makes sure user-specified address is in Internet format
?RCS:
?RCS: Revision
3.0.1.2 1993/09/13 15:48:49 ram
?RCS: patch10: reverted to original intent by the Author himself
?RCS:
?RCS: Revision 3.0.1.1 1993/08/27 14:38:38 ram
?RCS: patch7: now prompts user for its e-mail address
```

?RCS: patch7: no longer silent when mail has been sent

?RCS:

?RCS: Revision 3.0 1993/08/18 12:05:06 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?RCS:

?X:

?X: This unit asks the user to please send a message to the author.

?X: To force inclusion of this unit, you must add it's name to the

?X: dependancies on the MAKE line in your private copy of End.U.

?X: This allows a smart mailagent program to automatically let users know

?X: when their package is out of date, and to allow users to be notified of

?X: any future patches.

?X:

?MAKE:MailAuthor mailpatches notifypatches usermail: test cat mailer \
package Myread patchlevel baserev rm rsrc Oldconfig Configdir

?MAKE: -pick wipe \$@ %<

?S:mailpatches:

?S: Indicates whether the user would like future patches to be mailed

?S: directly

to them.

?S:.

?S:notifypatches:

?S: Indicates whether the user would like notification of future patches

?S: mailed to them.

?S:.

?S:usermail:

?S: This variable is used internally by Configure to keep track of the

?S: user e-mail address, where notifications or patches should be sent.

?S: A '-' value means the return address will be extracted by parsing

?S: the mail headers.

?S:.

?T:opt mailpatches notifypatches atsh status

: notify author that his package is used

if \$test -f ../config/mailauthor &&

cmp \$rsrc/patchlevel.h ../config/mailauthor >/dev/null 2>&1

then

status="say that you're using \$package";

case "\$mailpatches" in

true) status='have patches mailed to you as they are issued';

esac

case "\$notifypatches" in

true) status='be notified when new patches are issued';

esac

\$cat <<EOM

You have already sent the author of \$package (<MAINTLOC>) mail to \$status. If you wish, you may modify

your previous request by sending a new mail with different options.

EOM

```
rp='Should
I send a status update to <MAINTLOC>?'
dflt=n
else
$cat <<EOM
```

If you are able to send mail to the Internet, the author of \$package would really appreciate you letting me send off a quick note, just to say that you've tried it. The author is more likely to spend time maintaining \$package if it's known that many people are using it, and you can even ask to get sent new patches automagically this way if you wish. To protect your privacy, all I'll say in the mail is the version of \$package that you're using.

EOM

```
rp='Should I send mail to <MAINTLOC>?'
dflt=y
?X: Ensure default is 'n' if question has been asked already, in case they
?X: run Configure -d next time and answered 'n' the first time. Therefore,
?X: an empty nomail will be created later on even if no mail is sent.
$test -f ../config/nomail && dflt=n
fi
./myread
case "$ans" in
[yY]*)
echo " "
echo "Great! Your cooperation is really appreciated."
$cat <<EOM
```

Some braindead sites do not set a proper return address in the From: header of their outgoing mail, making it impossible to reply to mail they generate. If your site is broken in this way, write to your system administrator and get it fixed!!! In the mean time, you can manually specify the Internet e-mail address by which the author can get back to you, should there be a need to do so. If manually specified, it should be something like "user@domain.top". If your mail system generates addresses correctly, specify "none".

EOM

```
case "$usermail" in
'|') dflt=none;;
*) dflt="$usermail";;
esac
rp='Manually specify a return address to use:'
./myread
case "$ans" in
```

```

none|*@*.*)
case "$ans" in
none) usermail='-';;
*) usermail="$ans";;
esac
;;
*)
echo "(Address does not look like an Internet one -- ignoring it.)"
?X:
?X: If we can't trust their mailer or their return address, it's highly
?X: suggested that they only register and don't ask to get anything from
?X: the author, since it's likely to bounce in null-land --
RAM.
?X:
usermail='- '
mailpatches=false
notifypatches=false
;;
esac
echo " "
opt="
rp='Would you like to have new patches automatically mailed to you?'
case "$mailpatches" in
true) dflt=y;;
*) dflt=n;;
esac
./myread
case "$ans" in
[yY]*) opt=' mailpatches'; mailpatches=true;;
*)
mailpatches=false
echo " "
rp='Ok, would you like to simply be notified of new patches?'
case "$notifypatches" in
false) dflt=n;;
*) dflt=y;;
esac
./myread
echo " "
case "$ans" in
[yY]*) opt=' notifypatches'; notifypatches=true;;
*)
echo "Fine, I'll simply say that you've tried it then."
notifypatches=false
;;
esac
;;
esac

```

```
echo "Sending mail to <MAINTLOC>..." >&4
?X: Bizarre hack here. We can't just put @SH in the hereis lines below, because
?X: metaconfig will interpret it as a command, and there's no quoting mechanism.
?X: Do it via a variable instead.
atsh='@SH'
$mailler <MAINTLOC> <<EOM >/dev/null 2>&1
Subject: Command
Precedence: junk
To: <MAINTLOC>
```

```
$atsh
package $usermail $package $baserev $patchlevel$opt
EOM
$rm -f ../config/mailauthor ../config/nomail
cp $src/patchlevel.h ../config/mailauthor
;;
*)
case "$dfit" in
"y")
echo "Oh well, maybe next time."
cp /dev/null ../config/nomail
;;
esac
;;
esac
```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/dist/U/MailAuthor.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id$
?RCS:
?RCS: Copyright (c) 1999 Jarkko Hietaniemi
?RCS:
?RCS: You may distribute under the terms of either the GNU General Public
?RCS: License or the Artistic License, as specified in the README file.
?RCS:
?MAKE:d_iovec_s: i_sysuio Hasfield
?MAKE: -pick add $@ %<
?S:d_iovec_s:
?S: This variable conditionally defines the HAS_STRUCT_IOVEC symbol,
?S: which indicates that the struct iovec is supported.
?S:.
?C:HAS_STRUCT_IOVEC:
?C: This symbol, if defined, indicates that the struct iovec
?C: to do scatter writes/gather reads is supported.
?C:.
```

```
?H:#$d_iovec_s HAS_STRUCT_IOVEC /**/
?H:.
?LINT:set d_iovec_s
: Check for iovec_s
echo "Checking to see if your system supports struct iovec..." >&4
set d_iovec_s iovec iov_base $i_sysuio sys/uio.h
eval $hasfield
case "$d_iovec_s" in
"$define") echo "Yup, it does." ;;
*) echo "Nope, it doesn't." ;;
esac
```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/perl/d_iovec_s.U
```

No license file was found, but licenses were detected in source scan.

```
?RCS: $Id: d_gnulibc.U,v 3.0.1.1 1997/02/28 15:34:33 ram Exp $
?RCS:
?RCS: Copyright (c) 1996,1998 Andy Dougherty
?RCS: Copyright (c) 1996, Sven Verdoolaege
?RCS: Copyright (c) 1991-1993, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 3.0.
?RCS:
?RCS: $Log: d_gnulibc.U,v $
?RCS: Revision 3.0.1.1 1997/02/28 15:34:33 ram
?RCS: patch61: created
?RCS:
?MAKE:d_gnulibc gnulibc_version: Myread Oldconfig Setvar rm_try \
cat Compile run
?MAKE: -pick add $@ %<
?S:d_gnulibc:
?S: Defined if we're dealing with the GNU C Library.
?S:.
?S:gnulibc_version:
?S: This variable contains the version number of the GNU C library.
?S: It is
usually something like '2.2.5'. It is a plain " if this
?S: is not the GNU C library, or if the version is unknown.
?S:.
?C:HAS_GNULIBC:
?C: This symbol, if defined, indicates to the C program that
?C: the GNU C library is being used. A better check is to use
```

```

?C: the __GLIBC__ and __GLIBC_MINOR__ symbols supplied with glibc.
?C:.
?H:#$d_gnulibc HAS_GNULIBC /**/
?H:%<:#if defined(HAS_GNULIBC) && !defined(_GNU_SOURCE)
?H:%<:# define _GNU_SOURCE
?H:%<:#endif
?H:.
?F:!glibc.ver !try
?LINT: set d_gnulibc
?X: gnulibc can be executed by calling __libc_main().
?X: Ulrich Drepper doesn't think any other libc does that,
?X: but we check if it says 'GNU C Library' to be sure.
?X:
?X: Alas, as of 3/1998 glibc 2.0.7 reportedly isn't going to
?X: have __libc_main() anymore. :-(. Fortunately, all released
?X: versions of glibc 2.x.x _do_ have CPP variables. For 2.0.6,
?X: they are:
?X: #define __GLIBC__ 2
?X: #define __GLIBC_MINOR__ 0.
?X: (The '6' isn't available :-(.
?X: glibc2.1 will
also have
?X: extern const char * __gnu_get_libc_release(void);
?X: extern const char * __gnu_get_libc_version(void);
?X: functions. --thanks to Andreas Jaeger. --AD 6/1998.
?X: Although the exact format isn't documented, __gnu_get_libc_version()
?X: returns a simple string '2.1.3' in glibc 2.1.3.
?X:
: Check if we are using the GNU C library
echo " "
echo "Checking for GNU C Library..." >&4
cat >try.c <<'EOCP'
/* Find out version of GNU C library. __GLIBC__ and __GLIBC_MINOR__
alone are insufficient to distinguish different versions, such as
2.0.6 and 2.0.7. The function gnu_get_libc_version() appeared in
libc version 2.1.0. A. Dougherty, June 3, 2002.
*/
#include <stdio.h>
int main(void)
{
#ifdef __GLIBC__
# ifdef __GLIBC_MINOR__
# if __GLIBC__ >= 2 && __GLIBC_MINOR__ >= 1 && !defined(__cplusplus)
# include <gnu/libc-version.h>
printf("%s\n", gnu_get_libc_version());
# else
printf("%d.%d\n", __GLIBC__, __GLIBC_MINOR__);
#

```

```

endif
# else
printf("%d\n", __GLIBC__);
# endif
return 0;
#else
return 1;
#endif
}
EOCP
set try
if eval $compile_ok && $run ./try > glibc.ver; then
val="$define"
gnulibc_version=`$cat glibc.ver`
echo "You are using the GNU C Library version $gnulibc_version"
else
val="$undef"
gnulibc_version=""
echo "You are not using the GNU C Library"
fi
$rm_try glibc.ver
set d_gnulibc
eval $setvar

```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/compline/d_gnulibc.U
```

No license file was found, but licenses were detected in source scan.

?RCS: \$Id: d_getnetent.U,v 3.0 1993/08/18 12:06:09 ram Exp \$

?RCS:

?RCS: Copyright (c) 1991-1993, Raphael Manfredi

?RCS:

?RCS: You may redistribute only under the terms of the Artistic License,

?RCS: as specified in the README file that comes with the distribution.

?RCS: You may reuse parts of this distribution only within the terms of

?RCS: that same Artistic License; a copy of which may be found at the root

?RCS: of the source tree for dist 3.0.

?RCS:

?RCS: \$Log: d_getnetent.U,v \$

?RCS: Revision 3.0 1993/08/18 12:06:09 ram

?RCS: Baseline for dist 3.0 netwide release.

?RCS:

?MAKE:d_getnetent: Inlibc

?MAKE: -pick add \$@ %<

?S:d_getnetent:

?S: This variable conditionally defines HAS_GETNETENT if getnetent() is

?S: available to look up network names in some data base or another.

?S:
?C:HAS_GETNETENT:
?C: This symbol, if defined, indicates that the getnetent() routine is
?C: available to look up network names in some data base
or another.

?C:.
?H:#\$d_getnent HAS_GETNETENT /**/
?H:.
?LINT:set d_getnent
: see if getnetent exists
set getnetent d_getnent
eval \$inlibc

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/modified/d_getnent.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$
?RCS:
?RCS: Copyright (c) 1991-1997, 2004-2006, Raphael Manfredi
?RCS:
?RCS: You may redistribute only under the terms of the Artistic License,
?RCS: as specified in the README file that comes with the distribution.
?RCS: You may reuse parts of this distribution only within the terms of
?RCS: that same Artistic License; a copy of which may be found at the root
?RCS: of the source tree for dist 4.0.
?RCS:
?RCS: \$Log: d_time.U,v \$
?RCS: Revision 3.0.1.2 1995/07/25 14:07:43 ram
?RCS: patch56: typo fix, sytem -> system
?RCS:
?RCS: Revision 3.0.1.1 1994/10/29 16:16:38 ram
?RCS: patch36: now uses new Typedef unit to compute type information (ADO)
?RCS:
?RCS: Revision 3.0 1993/08/18 12:07:45 ram
?RCS: Baseline for dist 3.0 netwide release.
?RCS:
?X: Maybe <sys/types.h> should be included?
?X:INC: i_systypes
?MAKE:d_time timetype: Csym Setvar Findhdr Myread Typedef
?MAKE: -pick add \$@ %<
?S:d_time:
?S: This
variable conditionally defines the HAS_TIME symbol, which indicates
?S: that the time() routine exists. The time() routine is normally
?S: provided on UNIX systems.
?S:.

?S:timetype:

?S: This variable holds the type returned by time(). It can be long,
?S: or time_t on BSD sites (in which case <sys/types.h> should be
?S: included). Anyway, the type Time_t should be used.

?S:.

?C:HAS_TIME (TIMER):

?C: This symbol, if defined, indicates that the time() routine exists.

?C:.

?C:Time_t (TIMETYPE):

?C: This symbol holds the type returned by time(). It can be long,
?C: or time_t on BSD sites (in which case <sys/types.h> should be
?C: included).

?C:.

?H:#\$d_time HAS_TIME /**/

?H:#define Time_t \$timetype /* Time type */

?H:.

?LINT:set d_time

: see if time exists

echo " "

if set time val -f d_time; eval \$csym; \$val; then

echo 'time() found.' >&4

val="\$define"

set time_t timetype long stdio.h sys/types.h

eval \$typedef

dflt="\$timetype"

echo " "

rp="What type is returned by time() on this
system?"

. ./myread

timetype="\$ans"

else

echo 'time() not found, hope that will do.' >&4

val="\$undef"

timetype='int';

fi

set d_time

eval \$setvar

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/U/d_time.U

No license file was found, but licenses were detected in source scan.

* You may redistribute only under the terms of the Artistic Licence,

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/dist/files/Jmake.tmpl

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$

?RCS:

?RCS: Copyright (c) 1998 Andy Dougherty

?RCS:

?RCS: You may distribute under the terms of either the GNU General Public

?RCS: License or the Artistic License, as specified in the README file.

?RCS:

?MAKE:use64bitint use64bitall archname64: Myread Oldconfig Setvar test \
usemorebits longsize ccflags d_quad uquadtype Compile rm_try run

?MAKE: -pick add \$@ %<

?Y:TOP

?S:use64bitint:

?S: This variable conditionally defines the USE_64_BIT_INT symbol,

?S: and indicates that 64-bit integer types should be used

?S: when available. The minimal possible 64-bitness

?S: is employed, just enough to get 64-bit integers into Perl.

?S: This may mean using for example "long longs", while your memory

?S: may still be limited to 2 gigabytes.

?S:.

?S:use64bitall:

?S: This variable conditionally defines the USE_64_BIT_ALL symbol,

?S: and indicates that 64-bit integer types should be used

?S: when available. The maximal

possible

?S: 64-bitness is employed: LP64 or ILP64, meaning that you will

?S: be able to use more than 2 gigabytes of memory. This mode is

?S: even more binary incompatible than USE_64_BIT_INT. You may not

?S: be able to run the resulting executable in a 32-bit CPU at all or

?S: you may need at least to reboot your OS to 64-bit mode.

?S:.

?S:archname64:

?S: This variable is used for the 64-bitness part of \$archname.

?S:.

?C:USE_64_BIT_INT:

?C: This symbol, if defined, indicates that 64-bit integers should

?C: be used when available. If not defined, the native integers

?C: will be employed (be they 32 or 64 bits). The minimal possible

?C: 64-bitness is used, just enough to get 64-bit integers into Perl.

?C: This may mean using for example "long longs", while your memory

?C: may still be limited to 2 gigabytes.

?C:.

?C:USE_64_BIT_ALL:

?C: This symbol, if defined, indicates that 64-bit integers should

?C: be used when available. If not defined, the native integers

?C: will be used (be

```

they 32 or 64 bits). The maximal possible
?C: 64-bitness is employed: LP64 or ILP64, meaning that you will
?C: be able to use more than 2 gigabytes of memory. This mode is
?C: even more binary incompatible than USE_64_BIT_INT. You may not
?C: be able to run the resulting executable in a 32-bit CPU at all or
?C: you may need at least to reboot your OS to 64-bit mode.
?C:.
?H:%<:#ifndef USE_64_BIT_INT
?H:%<:#$use64bitint USE_64_BIT_INT /**/
?H:%<:#endif
?H:%<:#ifndef USE_64_BIT_ALL
?H:%<:#$use64bitall USE_64_BIT_ALL /**/
?H:%<:#endif
?H:.
?INIT:archname64="
?LINT:extern cflags
?LINT:use usemorebits
?LINT:extern use64bits
?LINT:extern uselonglong
?LINT:extern uselonglongs
?LINT:extern use64bitints
?LINT:extern use64bitsint
?LINT:extern use64bitsall
?T:libcquad
?F:!try
?F:!use64bitint.cbu
?F:!use64bitall.cbu
: Do we want 64bit support
case "$uselonglong" in
"$define"|true|[yY]*)
cat <<EOM >&4

```

*** Configure -Duselonglong is deprecated, using -Duse64bitint instead.

```

EOM
use64bitint="$define"
;;
esac
case
"$use64bits" in
"$define"|true|[yY]*)
cat <<EOM >&4

```

*** Configure -Duse64bits is deprecated, using -Duse64bitint instead.

```

EOM
use64bitint="$define"
;;
esac
case "$use64bitints" in

```

```
"$define"|true|[yY]*)  
cat <<EOM >&4
```

*** There is no Configure -Duse64bitints, using -Duse64bitint instead.

```
EOM  
use64bitint="$define"  
;;  
esac  
case "$use64bitsint" in  
"$define"|true|[yY]*)  
cat <<EOM >&4
```

*** There is no Configure -Duse64bitsint, using -Duse64bitint instead.

```
EOM  
use64bitint="$define"  
;;  
esac  
case "$uselonglongs" in  
"$define"|true|[yY]*)  
cat <<EOM >&4
```

*** There is no Configure -Duselonglongs, using -Duse64bitint instead.

```
EOM  
use64bitint="$define"  
;;  
esac  
case "$use64bitsall" in  
"$define"|true|[yY]*)  
cat <<EOM >&4
```

*** There is no Configure -Duse64bitsall, using -Duse64bitall instead.

```
EOM  
use64bitall="$define"  
;;  
esac
```

```
case "$ccflags" in  
*-DUSE_LONG_LONG*|-DUSE_64_BIT_INT*|-DUSE_64_BIT_ALL*) use64bitint="$define";;  
esac  
case "$use64bitall" in  
"$define"|true|[yY]*)  
use64bitint="$define" ;;  
esac
```

```
case "$longsize" in  
8) cat <<EOM
```

You have natively 64-bit long integers.

```

EOM
val="$define"
;;
*) case "$use64bitint" in
"$define"|true|[yY]*) dflt='y';;
*) dflt='n';;
esac
case "$d_quad" in
"$define") ;;
*) dflt='n' ;;
esac
cat <<EOM

```

Perl can be built to take advantage of 64-bit integer types on some systems. To do so, Configure can be run with `-Duse64bitint`. Choosing this option will most probably introduce binary incompatibilities.

If this doesn't make any sense to you, just accept the default '\$dflt'. (The default has been chosen based on your configuration.)

```

EOM
rp="Try to use 64-bit integers, if available?"
./myread
case "$ans" in
[yY]*) val="$define" ;;
*) val="$undef" ;;
esac
;;
esac
set use64bitint
eval $setvar

```

```

case "$use64bitall" in
"$define"|true|[yY]*) dflt='y' ;;
*) case "$longsize" in
8) dflt='y' ;;
*) dflt='n' ;;
esac
;;
esac
cat <<EOM

```

You may also choose to try maximal 64-bitness. It means using as much 64-bitness as possible on the platform. This in turn means even more binary incompatibilities. On the other hand, your platform may not have any more 64-bitness available than what you already have chosen.

If this doesn't make any sense to you, just accept the default '\$dflt'.

(The default has been chosen based on your configuration.)

EOM

```
rp="Try to use maximal 64-bit support, if available?"
. ./myread
case "$ans" in
[yY]*) val="$define" ;;
*)    val="$undef" ;;
esac
set use64bitall
eval $setvar
case "$use64bitall" in
"$define")
case "$use64bitint" in
"$undef")
cat <<EOM
```

Since you have chosen a maximally 64-bit build, I'm also turning on the use of 64-bit integers.

EOM

```
use64bitint="$define" ;;
esac
;;
esac
```

```
: Look for a hint-file generated 'call-back-unit'. If the
: user has specified that a 64-bit perl is to be built,
: we may need to set or change some other defaults.
if $test -f use64bitint.cbu; then
echo "Your
platform has some specific hints regarding 64-bit integers, using them..."
. ./use64bitint.cbu
fi
case "$use64bitint" in
"$define"|true|[yY]*)
: This test was common to all the OpenBSD forks, and seems harmless for
: other platforms:
echo " "
echo "Checking if your C library has broken 64-bit functions..." >&4
cat >try.c <<EOCP
#include <stdio.h>
typedef $uquadtype myULL;
int main (void)
{
struct {
double d;
myULL u;
} *p, test[] = {
{4294967303.15, 4294967303ULL},
```

```

{4294967294.2, 4294967294ULL},
{4294967295.7, 4294967295ULL},
{0.0, 0ULL}
};
for (p = test; p->u; p++) {
myULL x = (myULL)p->d;
if (x != p->u) {
    printf("buggy\n");
    return 0;
}
}
printf("ok\n");
return 0;
}
EOCP
set try
if eval $compile_ok; then
    libcquad=`$run ./try`
    echo "Your C library's 64-bit functions are $libcquad."
else
    echo "(I can't seem to compile the test program.)"
    echo "Assuming that your C library's 64-bit functions are ok."
    libcquad="ok"
fi
$rm_try

case
"$libcquad" in
    buggy*)
        cat >&4 <<EOM

*** You have a C library with broken 64-bit functions.
*** 64-bit support does not work reliably in this configuration.
*** Please rerun Configure without -Duse64bitint and/or -Dusemorebits.
*** Cannot continue, aborting.

EOM
    exit 1
    ;;
esac
case "$longsize" in
4) case "$archname64" in
    ") archname64=64int ;;
    esac
    ;;
esac
;;
esac

```

```

: Look for a hint-file generated 'call-back-unit'. If the
: user has specified that a maximally 64-bit perl is to be built,
: we may need to set or change some other defaults.
if $test -f use64bitall.cbu; then
  echo "Your platform has some specific hints regarding 64-bit builds, using them..."
  . /use64bitall.cbu
fi
case "$use64bitall" in
"$define"|true|[yY]*)
  case "$longsize" in
4) case "$archname64" in
  "|64int) archname64=64all ;;
  esac
  ;;
  esac
  ;;
  esac

case "$d_quad:$use64bitint" in
$undef:$define)
  cat >&4 <<EOF

*** You have chosen to use 64-bit
integers,
*** but none can be found.
*** Please rerun Configure without -Duse64bitint and/or -Dusemorebits.
*** Cannot continue, aborting.

EOF
  exit 1
  ;;
  esac

Found in path(s):
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/perl/use64bits.U
No license file was found, but licenses were detected in source scan.

?RCS: $Id: d_getgrent_r.U,v 0RCS:
?RCS: Copyright (c) 2002,2003 Jarkko Hietaniemi
?RCS:
?RCS: You may distribute under the terms of either the GNU General Public
?RCS: License or the Artistic License, as specified in the README file.
?RCS:
?RCS: Generated by the reentr.pl from the Perl 5.8 distribution.
?RCS:
?MAKE:d_getgrent_r_getgrent_r_proto: Inlibc Protochk Hasproto i_systypes \

```

```

usethreads i_grp extern_C
?MAKE: -pick add $@ %<
?S:d_getgrent_r:
?S: This variable conditionally defines the HAS_GETGRENT_R symbol,
?S: which indicates to the C program that the getgrent_r()
?S: routine is available.
?S:.
?S:getgrent_r_proto:
?S: This variable encodes the prototype of getgrent_r.
?S: It is zero if d_getgrent_r is undef, and one of the
?S: REENTRANT_PROTO_T_ABC macros of reentr.h if d_getgrent_r
?S: is defined.
?S:.
?C:HAS_GETGRENT_R:
?C: This symbol, if defined, indicates that the getgrent_r routine
?C: is available to
getgrent re-entrantly.
?C:.
?C:GETGRENT_R_PROTO:
?C: This symbol encodes the prototype of getgrent_r.
?C: It is zero if d_getgrent_r is undef, and one of the
?C: REENTRANT_PROTO_T_ABC macros of reentr.h if d_getgrent_r
?C: is defined.
?C:.
?H:#$d_getgrent_r HAS_GETGRENT_R /**/
?H:#define GETGRENT_R_PROTO $getgrent_r_proto /**/
?H:.
?T:try hdrs d_getgrent_r_proto
: see if getgrent_r exists
set getgrent_r d_getgrent_r
eval $inlibc
case "$d_getgrent_r" in
"$define")
hdrs="$i_systypes sys/types.h define stdio.h $i_grp grp.h"
case "$d_getgrent_r_proto:$usethreads" in
":define") d_getgrent_r_proto=define
set d_getgrent_r_proto getgrent_r $hdrs
eval $hasproto ;;
*) ;;
esac
case "$d_getgrent_r_proto" in
define)
case "$getgrent_r_proto" in
"|0) try='int getgrent_r(struct group*, char*, size_t, struct group**);'
./protochk "$extern_C $try" $hdrs && getgrent_r_proto=I_SBWR ;;
esac
case "$getgrent_r_proto" in
"|0) try='int getgrent_r(struct group*, char*, int, struct group**);'

```

```

./protochk
"$extern_C $try" $hdrs && getgrent_r_proto=I_SBIR ;;
esac
case "$getgrent_r_proto" in
"|0) try='struct group* getgrent_r(struct group*, char*, size_t);'
./protochk "$extern_C $try" $hdrs && getgrent_r_proto=S_SBW ;;
esac
case "$getgrent_r_proto" in
"|0) try='struct group* getgrent_r(struct group*, char*, int);'
./protochk "$extern_C $try" $hdrs && getgrent_r_proto=S_SBI ;;
esac
case "$getgrent_r_proto" in
"|0) try='int getgrent_r(struct group*, char*, int);'
./protochk "$extern_C $try" $hdrs && getgrent_r_proto=I_SBI ;;
esac
case "$getgrent_r_proto" in
"|0) try='int getgrent_r(struct group*, char*, int, FILE**);'
./protochk "$extern_C $try" $hdrs && getgrent_r_proto=I_SBIH ;;
esac
case "$getgrent_r_proto" in
"|0) d_getgrent_r=undef
    getgrent_r_proto=0
    echo "Disabling getgrent_r, cannot determine prototype." >&4 ;;
*) case "$getgrent_r_proto" in
REENTRANT_PROTO*) ;;
*) getgrent_r_proto="REENTRANT_PROTO_$getgrent_r_proto" ;;
esac
echo
"Prototype: $try" ;;
esac
;;
*) case "$susethreads" in
define) echo "getgrent_r has no prototype, not using it." >&4 ;;
esac
d_getgrent_r=undef
getgrent_r_proto=0
;;
esac
;;
*) getgrent_r_proto=0
;;
esac

```

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/threads/d_getgrent_r.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$
?RCS:
?RCS: Copyright (c) 2000 Jarkko Hietaniemi
?RCS:
?RCS: You may distribute under the terms of either the GNU General Public
?RCS: License or the Artistic License, as specified in the README file.
?RCS:
?MAKE:d_finite: Inlibc
?MAKE: -pick add \$@ %<
?S:d_finite:
?S: This variable conditionally defines the HAS_FINITE symbol, which
?S: indicates to the C program that the finite() routine is available.
?S:.
?C:HAS_FINITE:
?C: This symbol, if defined, indicates that the finite routine is
?C: available to check whether a double is finite (non-infinity non-NaN).
?C:.
?H:#\$d_finite HAS_FINITE /**/
?H:.
?LINT:set d_finite
: see if finite exists
set finite d_finite
eval \$inlibc

Found in path(s):

* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-debian-perl-5.26.1/U/perl/d_finite.U

No license file was found, but licenses were detected in source scan.

?RCS: \$Id\$
?RCS:
?RCS: Copyright (c) 2000 Jarkko Hietaniemi
?RCS:
?RCS: You may distribute under the terms of either the GNU General Public
?RCS: License or the Artistic License, as specified in the README file.
?RCS:
?MAKE:d_getrlimit: Inlibc
?MAKE: -pick add \$@ %<
?S:d_getrlimit:
?S: This variable conditionally defines the HAS_GETRLIMIT symbol, which
?S: indicates to the C program that the getrlimit() routine is available.
?S:.
?C:HAS_GETRLIMIT:
?C: This symbol, if defined, indicates that the getrlimit routine is
?C: available to get process resource limits.
?C:.
?H:#\$d_getrlimit HAS_GETRLIMIT /**/
?H:.

```
?LINT:set d_getrlimit
: see if getrlimit exists
set getrlimit d_getrlimit
eval $inlibc
```

Found in path(s):

```
* /opt/cola/permits/1448963027_1666404849.0733607/0/perl-5-26-1-orig-regen-configure-1-tar-gz/metaconfig-
debian-perl-5.26.1/U/perl/d_getrlimit.U
```

1.95 gmp 2:6.1.2+dfsg-2ubuntu0.1

1.95.1 Available under license :

GNU GENERAL PUBLIC LICENSE

Version 2, June 1991

Copyright (C) 1989, 1991 Free Software Foundation, Inc.,
51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA
Everyone is permitted to copy and distribute verbatim copies
of this license document, but changing it is not allowed.

Preamble

The licenses for most software are designed to take away your freedom to share and change it. By contrast, the GNU General Public License is intended to guarantee your freedom to share and change free software--to make sure the software is free for all its users. This General Public License applies to most of the Free Software Foundation's software and to any other program whose authors commit to using it. (Some other Free Software Foundation software is covered by the GNU Lesser General Public License instead.) You can apply it to your programs, too.

When we speak of free software, we are referring to freedom, not price.

Our General Public Licenses are designed to make sure that you have the freedom to distribute copies of free software (and charge for this service if you wish), that you receive source code or can get it if you want it, that you can change the software or use pieces of it in new free programs; and that you know you can do these things.

To protect your rights, we need to make restrictions that forbid anyone to deny you these rights or to ask you to surrender the rights. These restrictions translate to certain responsibilities for you if you distribute copies of the software, or if you modify it.

For example, if you distribute copies of such a program, whether gratis or for a fee, you must give the recipients all the rights that

you have. You must make sure that they, too, receive or can get the source code. And you must show them these terms so they know their rights.

We protect your rights with two steps: (1) copyright the software, and (2) offer you this license which gives you legal permission to copy, distribute and/or modify the software.

Also, for each author's protection and ours, we want to make certain that everyone understands that there is no warranty for this free software. If the software is modified by someone else and passed on, we want its recipients to know that what they have is not the original, so that any problems introduced by others will not reflect on the original authors' reputations.

Finally, any free program is threatened constantly by software patents. We wish to avoid the danger that redistributors of a free program will individually obtain patent licenses, in effect making the program proprietary. To prevent this, we have made it clear that any patent must be licensed for everyone's free use or not licensed at all.

The precise terms and conditions for copying, distribution and modification follow.

GNU GENERAL PUBLIC LICENSE TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

0. This License applies to any program or other work which contains a notice placed by the copyright holder saying it may be distributed under the terms of this General Public License. The "Program", below, refers to any such program or work, and a "work based on the Program" means either the Program or any derivative work under copyright law: that is to say, a work containing the Program or a portion of it, either verbatim or with modifications and/or translated into another language. (Hereinafter, translation is included without limitation in the term "modification".) Each licensee is addressed as "you".

Activities other than copying, distribution and modification are not covered by this License; they are outside its scope. The act of running the Program is not restricted, and the output from the Program is covered only if its contents constitute a work based on the Program (independent of having been made by running the Program). Whether that is true depends on what the Program does.

1. You may copy and distribute verbatim copies of the Program's source code as you receive it, in any medium, provided that you

conspicuously and appropriately publish on each copy an appropriate copyright notice and disclaimer of warranty; keep intact all the notices that refer to this License and to the absence of any warranty; and give any other recipients of the Program a copy of this License along with the Program.

You may charge a fee for the physical act of transferring a copy, and you may at your option offer warranty protection in exchange for a fee.

2. You may modify your copy or copies of the Program or any portion of it, thus forming a work based on the Program, and copy and distribute such modifications or work under the terms of Section 1 above, provided that you also meet all of these conditions:

a) You must cause the modified files to carry prominent notices stating that you changed the files and the date of any change.

b) You must cause any work that you distribute or publish, that in whole or in part contains or is derived from the Program or any part thereof, to be licensed as a whole at no charge to all third parties under the terms of this License.

c) If the modified program normally reads commands interactively when run, you must cause it, when started running for such interactive use in the most ordinary way, to print or display an announcement including an appropriate copyright notice and a notice that there is no warranty (or else, saying that you provide a warranty) and that users may redistribute the program under these conditions, and telling the user how to view a copy of this License. (Exception: if the Program itself is interactive but does not normally print such an announcement, your work based on the Program is not required to print an announcement.)

These requirements apply to the modified work as a whole. If identifiable sections of that work are not derived from the Program, and can be reasonably considered independent and separate works in themselves, then this License, and its terms, do not apply to those sections when you distribute them as separate works. But when you distribute the same sections as part of a whole which is a work based on the Program, the distribution of the whole must be on the terms of this License, whose permissions for other licensees extend to the entire whole, and thus to each and every part regardless of who wrote it.

Thus, it is not the intent of this section to claim rights or contest your rights to work written entirely by you; rather, the intent is to exercise the right to control the distribution of derivative or

collective works based on the Program.

In addition, mere aggregation of another work not based on the Program with the Program (or with a work based on the Program) on a volume of a storage or distribution medium does not bring the other work under the scope of this License.

3. You may copy and distribute the Program (or a work based on it, under Section 2) in object code or executable form under the terms of Sections 1 and 2 above provided that you also do one of the following:

- a) Accompany it with the complete corresponding machine-readable source code, which must be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange; or,
- b) Accompany it with a written offer, valid for at least three years, to give any third party, for a charge no more than your cost of physically performing source distribution, a complete machine-readable copy of the corresponding source code, to be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange; or,
- c) Accompany it with the information you received as to the offer to distribute corresponding source code. (This alternative is allowed only for noncommercial distribution and only if you received the program in object code or executable form with such an offer, in accord with Subsection b above.)

The source code for a work means the preferred form of the work for making modifications to it. For an executable work, complete source code means all the source code for all modules it contains, plus any associated interface definition files, plus the scripts used to control compilation and installation of the executable. However, as a special exception, the source code distributed need not include anything that is normally distributed (in either source or binary form) with the major components (compiler, kernel, and so on) of the operating system on which the executable runs, unless that component itself accompanies the executable.

If distribution of executable or object code is made by offering access to copy from a designated place, then offering equivalent access to copy the source code from the same place counts as distribution of the source code, even though third parties are not compelled to copy the source along with the object code.

4. You may not copy, modify, sublicense, or distribute the Program

except as expressly provided under this License. Any attempt otherwise to copy, modify, sublicense or distribute the Program is void, and will automatically terminate your rights under this License. However, parties who have received copies, or rights, from you under this License will not have their licenses terminated so long as such parties remain in full compliance.

5. You are not required to accept this License, since you have not signed it. However, nothing else grants you permission to modify or distribute the Program or its derivative works. These actions are prohibited by law if you do not accept this License. Therefore, by modifying or distributing the Program (or any work based on the Program), you indicate your acceptance of this License to do so, and all its terms and conditions for copying, distributing or modifying the Program or works based on it.

6. Each time you redistribute the Program (or any work based on the Program), the recipient automatically receives a license from the original licensor to copy, distribute or modify the Program subject to these terms and conditions. You may not impose any further restrictions on the recipients' exercise of the rights granted herein. You are not responsible for enforcing compliance by third parties to this License.

7. If, as a consequence of a court judgment or allegation of patent infringement or for any other reason (not limited to patent issues), conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot distribute so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not distribute the Program at all. For example, if a patent license would not permit royalty-free redistribution of the Program by all those who receive copies directly or indirectly through you, then the only way you could satisfy both it and this License would be to refrain entirely from distribution of the Program.

If any portion of this section is held invalid or unenforceable under any particular circumstance, the balance of the section is intended to apply and the section as a whole is intended to apply in other circumstances.

It is not the purpose of this section to induce you to infringe any patents or other property right claims or to contest validity of any such claims; this section has the sole purpose of protecting the integrity of the free software distribution system, which is

implemented by public license practices. Many people have made generous contributions to the wide range of software distributed through that system in reliance on consistent application of that system; it is up to the author/donor to decide if he or she is willing to distribute software through any other system and a licensee cannot impose that choice.

This section is intended to make thoroughly clear what is believed to be a consequence of the rest of this License.

8. If the distribution and/or use of the Program is restricted in certain countries either by patents or by copyrighted interfaces, the original copyright holder who places the Program under this License may add an explicit geographical distribution limitation excluding those countries, so that distribution is permitted only in or among countries not thus excluded. In such case, this License incorporates the limitation as if written in the body of this License.

9. The Free Software Foundation may publish revised and/or new versions of the General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Program specifies a version number of this License which applies to it and "any later version", you have the option of following the terms and conditions either of that version or of any later version published by the Free Software Foundation. If the Program does not specify a version number of this License, you may choose any version ever published by the Free Software Foundation.

10. If you wish to incorporate parts of the Program into other free programs whose distribution conditions are different, write to the author to ask for permission. For software which is copyrighted by the Free Software Foundation, write to the Free Software Foundation; we sometimes make exceptions for this. Our decision will be guided by the two goals of preserving the free status of all derivatives of our free software and of promoting the sharing and reuse of software generally.

NO WARRANTY

11. BECAUSE THE PROGRAM IS LICENSED FREE OF CHARGE, THERE IS NO WARRANTY FOR THE PROGRAM, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE PROGRAM "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED

OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE PROGRAM IS WITH YOU. SHOULD THE PROGRAM PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

12. IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY AND/OR REDISTRIBUTE THE PROGRAM AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE PROGRAM (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR

THIRD PARTIES OR A FAILURE OF THE PROGRAM TO OPERATE WITH ANY OTHER PROGRAMS), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Programs

If you develop a new program, and you want it to be of the greatest possible use to the public, the best way to achieve this is to make it free software which everyone can redistribute and change under these terms.

To do so, attach the following notices to the program. It is safest to attach them to the start of each source file to most effectively convey the exclusion of warranty; and each file should have at least the "copyright" line and a pointer to where the full notice is found.

<one line to give the program's name and a brief idea of what it does.>

Copyright (C) <year> <name of author>

This program is free software; you can redistribute it and/or modify it under the terms of the GNU

General Public License as published by the Free Software Foundation; either version 2 of the License, or (at your option) any later version.

This program is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details.

You should have received a copy of the GNU General Public License along with this program; if not, write to the Free Software Foundation, Inc., 51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA.

Also add information on how to contact you by electronic and paper mail.

If the program is interactive, make it output a short notice like this when it starts in an interactive mode:

```
Gnomovision version 69, Copyright (C) year name of author
Gnomovision comes with ABSOLUTELY NO WARRANTY; for details type `show w'.
This is free software, and you are welcome to redistribute
it
under certain conditions; type `show c' for details.
```

The hypothetical commands `show w' and `show c' should show the appropriate parts of the General Public License. Of course, the commands you use may be called something other than `show w' and `show c'; they could even be mouse-clicks or menu items--whatever suits your program.

You should also get your employer (if you work as a programmer) or your school, if any, to sign a "copyright disclaimer" for the program, if necessary. Here is a sample; alter the names:

```
Yoyodyne, Inc., hereby disclaims all copyright interest in the program
`Gnomovision' (which makes passes at compilers) written by James Hacker.
```

```
<signature of Ty Coon>, 1 April 1989
Ty Coon, President of Vice
```

This General Public License does not permit incorporating your program into proprietary programs. If your program is a subroutine library, you may consider it more useful to permit linking proprietary applications with the library. If this is what you want to do, use the GNU Lesser General Public License instead of this License.

GNU GENERAL PUBLIC LICENSE
Version 3, 29 June 2007

Copyright (C) 2007 Free Software Foundation, Inc. <<http://fsf.org/>>
Everyone is permitted to copy and distribute verbatim copies of this license document, but changing it is not allowed.

Preamble

The GNU General Public License is a free, copyleft license for software and other kinds of works.

The licenses for most software and other practical works are designed to take away your freedom to share and change the works. By contrast, the GNU General Public License is intended to guarantee your freedom to share and change all versions of a program--to make sure it remains free

software for all its users. We, the Free Software Foundation, use the GNU General Public License for most of our software; it applies also to any other work released this way by its authors. You can apply it to your programs, too.

When we speak of free software, we are referring to freedom, not price. Our General Public Licenses are designed to make sure that you have the freedom to distribute copies of free software (and charge for them if you wish), that you receive source code or can get it if you want it, that you can change the software or use pieces of it in new free programs, and that you know you can do these things.

To protect your rights, we need to prevent others from denying you these rights or asking you to surrender the rights. Therefore, you have certain responsibilities if you distribute copies of the software, or if you modify it: responsibilities to respect the freedom of others.

For example, if you distribute copies of such a program, whether gratis or for a fee, you must pass on to the recipients the same freedoms that you received. You must make sure that they, too, receive or can get the source code. And you must show them these terms so they know their rights.

Developers that use the GNU GPL protect your rights with two steps:

- (1) assert copyright on the software, and (2) offer you this License giving you legal permission to copy, distribute and/or modify it.

For the developers' and authors' protection, the GPL clearly explains that there is no warranty for this free software. For both users' and authors' sake, the GPL requires that modified versions be marked as changed, so that their problems will not be attributed erroneously to authors of previous versions.

Some devices are designed to deny users access to install or run modified versions of the software inside them, although the manufacturer can do so. This is fundamentally incompatible with the aim of protecting users' freedom to change the software. The systematic pattern of such abuse occurs in the area of products for individuals to use, which is precisely where it is most unacceptable. Therefore, we have designed this version of the GPL to prohibit the practice for those products. If such problems arise substantially in other domains, we stand ready to extend this provision to those domains in future versions of the GPL, as needed to protect the freedom of users.

Finally, every program is threatened constantly by software patents.

States should not allow patents to restrict development and use of software on general-purpose computers, but in those that do, we wish to avoid the special danger that patents applied to a free program could make it effectively proprietary. To prevent this, the GPL assures that patents cannot be used to render the program non-free.

The precise terms and conditions for copying, distribution and modification follow.

TERMS AND CONDITIONS

0. Definitions.

"This License" refers to version 3 of the GNU General Public License.

"Copyright" also means copyright-like laws that apply to other kinds of works, such as semiconductor masks.

"The Program" refers to any copyrightable work licensed under this License. Each licensee is addressed as "you". "Licensees" and "recipients" may be individuals or organizations.

To "modify" a work means to copy from or adapt all or part of the work in a fashion requiring copyright permission, other than the making of an exact copy. The resulting work is called a "modified version" of the earlier work or a work "based on" the earlier work.

A "covered work" means either the unmodified Program or a work based on the Program.

To "propagate" a work means to do anything with it that, without permission, would make you directly or secondarily liable for infringement under applicable copyright law, except executing it on a computer or modifying a private copy. Propagation includes copying, distribution (with or without modification), making available to the public, and in some countries other activities as well.

To "convey" a work means any kind of propagation that enables other parties to make or receive copies. Mere interaction with a user through a computer network, with no transfer of a copy, is not conveying.

An interactive user interface displays "Appropriate Legal Notices" to the extent that it includes a convenient and prominently visible feature that (1) displays an appropriate copyright notice, and (2) tells the user that there is no warranty for the work (except to the extent that warranties are provided), that licensees may convey the

work under this License, and how to view a copy of this License. If the interface presents a list of user commands or options, such as a menu, a prominent item in the list meets this criterion.

1. Source Code.

The "source code" for a work means the preferred form of the work for making modifications to it. "Object code" means any non-source form of a work.

A "Standard Interface" means an interface that either is an official standard defined by a recognized standards body, or, in the case of interfaces specified for a particular programming language, one that is widely used among developers working in that language.

The

"System Libraries" of an executable work include anything, other than the work as a whole, that (a) is included in the normal form of packaging a Major Component, but which is not part of that Major Component, and (b) serves only to enable use of the work with that Major Component, or to implement a Standard Interface for which an implementation is available to the public in source code form. A "Major Component", in this context, means a major essential component (kernel, window system, and so on) of the specific operating system (if any) on which the executable work runs, or a compiler used to produce the work, or an object code interpreter used to run it.

The "Corresponding Source" for a work in object code form means all the source code needed to generate, install, and (for an executable work) run the object code and to modify the work, including scripts to control those activities. However, it does not include the work's System Libraries, or general-purpose tools or generally available free programs which are used unmodified in performing those activities but which are not part of the work. For example, Corresponding Source includes interface definition files associated with source files for the work, and the source code for shared libraries and dynamically linked subprograms that the work is specifically designed to require, such as by intimate data communication or control flow between those subprograms and other parts of the work.

The Corresponding Source need not include anything that users can regenerate automatically from other parts of the Corresponding Source.

The Corresponding Source for a work in source code form is that same work.

2. Basic Permissions.

All rights granted under this License are granted for the term of copyright on the Program, and are irrevocable provided the stated conditions are met. This License explicitly affirms your unlimited permission to run the unmodified Program. The output from running a covered work is covered

by this License only if the output, given its content, constitutes a covered work. This License acknowledges your rights of fair use or other equivalent, as provided by copyright law.

You may make, run and propagate covered works that you do not convey, without conditions so long as your license otherwise remains in force. You may convey covered works to others for the sole purpose of having them make modifications exclusively for you, or provide you with facilities for running those works, provided that you comply with the terms of this License in conveying all material for which you do not control copyright. Those thus making or running the covered works for you must do so exclusively on your behalf, under your direction and control, on terms that prohibit them from making any copies of your copyrighted material outside their relationship with you.

Conveying under any other circumstances is permitted solely under the conditions stated below. Sublicensing is not allowed; section 10 makes it unnecessary.

3. Protecting Users' Legal Rights From Anti-Circumvention Law.

No covered work shall be deemed part of an effective technological measure under any applicable law fulfilling obligations under article 11 of the WIPO copyright treaty adopted on 20 December 1996, or similar laws prohibiting or restricting circumvention of such measures.

When you convey a covered work, you waive any legal power to forbid circumvention of technological measures to the extent such circumvention is effected by exercising rights under this License with respect to the covered work, and you disclaim any intention to limit operation or modification of the work as a means of enforcing, against the work's users, your or third parties' legal rights to forbid circumvention of technological measures.

4. Conveying Verbatim Copies.

You may convey verbatim copies of the Program's source code as you receive it, in any medium, provided that you conspicuously and appropriately

publish on each copy an appropriate copyright notice;
keep intact all notices stating that this License and any
non-permissive terms added in accord with section 7 apply to the code;
keep intact all notices of the absence of any warranty; and give all
recipients a copy of this License along with the Program.

You may charge any price or no price for each copy that you convey,
and you may offer support or warranty protection for a fee.

5. Conveying Modified Source Versions.

You may convey a work based on the Program, or the modifications to
produce it from the Program, in the form of source code under the
terms of section 4, provided that you also meet all of these conditions:

- a) The work must carry prominent notices stating that you modified
it, and giving a relevant date.

- b) The work must carry prominent notices stating that it is
released under this License and any conditions added under section
7. This requirement modifies the requirement in section
4 to
"keep intact all notices".

- c) You must license the entire work, as a whole, under this
License to anyone who comes into possession of a copy. This
License will therefore apply, along with any applicable section 7
additional terms, to the whole of the work, and all its parts,
regardless of how they are packaged. This License gives no
permission to license the work in any other way, but it does not
invalidate such permission if you have separately received it.

- d) If the work has interactive user interfaces, each must display
Appropriate Legal Notices; however, if the Program has interactive
interfaces that do not display Appropriate Legal Notices, your
work need not make them do so.

A compilation of a covered work with other separate and independent
works, which are not by their nature extensions of the covered work,
and which are not combined with it such as to form a larger program,
in or on a volume of a storage or distribution
medium, is called an
"aggregate" if the compilation and its resulting copyright are not
used to limit the access or legal rights of the compilation's users
beyond what the individual works permit. Inclusion of a covered work
in an aggregate does not cause this License to apply to the other
parts of the aggregate.

6. Conveying Non-Source Forms.

You may convey a covered work in object code form under the terms of sections 4 and 5, provided that you also convey the machine-readable Corresponding Source under the terms of this License, in one of these ways:

- a) Convey the object code in, or embodied in, a physical product (including a physical distribution medium), accompanied by the Corresponding Source fixed on a durable physical medium customarily used for software interchange.
- b) Convey the object code in, or embodied in, a physical product (including a physical distribution medium), accompanied by a written offer, valid for at least three years and valid for as long as you offer spare parts or customer support for that product model, to give anyone who possesses the object code either (1) a copy of the Corresponding Source for all the software in the product that is covered by this License, on a durable physical medium customarily used for software interchange, for a price no more than your reasonable cost of physically performing this conveying of source, or (2) access to copy the Corresponding Source from a network server at no charge.
- c) Convey individual copies of the object code with a copy of the written offer to provide the Corresponding Source. This alternative is allowed only occasionally and noncommercially, and only if you received the object code with such an offer, in accord with subsection 6b.
- d) Convey the object code by offering access from a designated place (gratis or for a charge), and offer equivalent access to the Corresponding Source in the same way through the same place at no further charge. You need not require recipients to copy the Corresponding Source along with the object code. If the place to copy the object code is a network server, the Corresponding Source may be on a different server (operated by you or a third party) that supports equivalent copying facilities, provided you maintain clear directions next to the object code saying where to find the Corresponding Source. Regardless of what server hosts the Corresponding Source, you remain obligated to ensure that it is available for as long as needed to satisfy these requirements.
- e) Convey the object code using peer-to-peer transmission, provided you inform other peers where the object code and Corresponding Source of the work are being offered to the general public at no

charge under subsection 6d.

A separable portion of the object code, whose source code is excluded from the Corresponding Source as a System Library, need not be included in conveying the object code work.

A "User Product" is either (1) a "consumer product", which means any tangible personal property which is normally used for personal, family, or household purposes, or (2) anything designed or sold for incorporation into a dwelling. In determining whether a product is a consumer product, doubtful cases shall be resolved in favor of coverage. For a particular product received by a particular user, "normally used" refers to a typical or common use of that class of product, regardless of the status of the particular user or of the way in which the particular user actually uses, or expects or is expected to use, the product. A product is a consumer product regardless of whether the product has substantial commercial, industrial or non-consumer uses, unless such uses represent the only significant mode of use of the product.

"Installation Information" for a User Product means any methods, procedures, authorization keys, or other information required to install and execute modified versions of a covered work in that User Product from a modified version of its Corresponding Source. The information must suffice to ensure that the continued functioning of the modified object code is in no case prevented or interfered with solely because modification has been made.

If you convey an object code work under this section in, or with, or specifically for use in, a User Product, and the conveying occurs as part of a transaction in which the right of possession and use of the User Product is transferred to the recipient in perpetuity or for a fixed term (regardless of how the transaction is characterized), the Corresponding Source conveyed under this section must be accompanied by the Installation Information. But this requirement does not apply if neither you nor any third party retains the ability to install modified object code on the User Product (for example, the work has been installed in ROM).

The requirement to provide Installation Information does not include a requirement to continue to provide support service, warranty, or updates for a work that has been modified or installed by the recipient, or for the User Product in which it has been modified or installed. Access to a network may be denied when the modification itself materially and adversely affects the operation of the network or violates the rules and protocols for communication across the network.

Corresponding Source conveyed, and Installation Information provided, in accord with this section must be in a format that is publicly documented (and with an implementation available to the public in source code form), and must require no special password or key for unpacking, reading or copying.

7. Additional Terms.

"Additional permissions" are terms that supplement the terms of this License by making exceptions from one or more of its conditions. Additional permissions that are applicable to the entire Program shall be treated as though they were included in this License, to the extent that they are valid under applicable law. If additional permissions apply only to part of the Program, that part may be used separately under those permissions, but the entire Program remains governed by this License without regard to the additional permissions.

When you convey a copy of a covered work, you may at your option remove any additional permissions from that copy, or from any part of it. (Additional permissions may be written to require their own removal in certain cases when you modify the work.) You may place additional permissions on material, added by you to a covered work, for which you have or can give appropriate copyright permission.

Notwithstanding any other provision of this License, for material you add to a covered work, you may (if authorized by the copyright holders of that material) supplement the terms of this License with terms:

- a) Disclaiming warranty or limiting liability differently from the terms of sections 15 and 16 of this License; or
- b) Requiring preservation of specified reasonable legal notices or author attributions in that material or in the Appropriate Legal Notices displayed by works containing it; or
- c) Prohibiting misrepresentation of the origin of that material, or requiring that modified versions of such material be marked in reasonable ways as different from the original version; or
- d) Limiting the use for publicity purposes of names of licensors or authors of the material; or
- e) Declining to grant rights under trademark law for use of some trade names, trademarks, or service marks; or

f) Requiring indemnification of licensors and authors of that material by anyone who conveys the material (or modified versions of it) with contractual assumptions of liability to the recipient, for any liability that these contractual assumptions directly impose on

those licensors and authors.

All other non-permissive additional terms are considered "further restrictions" within the meaning of section 10. If the Program as you received it, or any part of it, contains a notice stating that it is governed by this License along with a term that is a further restriction, you may remove that term. If a license document contains a further restriction but permits relicensing or conveying under this License, you may add to a covered work material governed by the terms of that license document, provided that the further restriction does not survive such relicensing or conveying.

If you add terms to a covered work in accord with this section, you must place, in the relevant source files, a statement of the additional terms that apply to those files, or a notice indicating where to find the applicable terms.

Additional terms, permissive or non-permissive, may be stated in the form of a separately written license, or stated as exceptions; the above requirements apply either way.

8. Termination.

You may not propagate or modify a covered work except as expressly provided under this License. Any attempt otherwise to propagate or modify it is void, and will automatically terminate your rights under this License (including any patent licenses granted under the third paragraph of section 11).

However, if you cease all violation of this License, then your license from a particular copyright holder is reinstated (a) provisionally, unless and until the copyright holder explicitly and finally terminates your license, and (b) permanently, if the copyright holder fails to notify you of the violation by some reasonable means prior to 60 days after the cessation.

Moreover, your license from a particular copyright holder is reinstated permanently if the copyright holder notifies you of the violation by some reasonable means, this is the first time you have received notice of violation of this License (for any work) from that copyright

holder, and you cure the violation prior to 30 days after your receipt of the notice.

Termination of your rights under this section does not terminate the licenses of parties who have received copies or rights from you under this License. If your rights have been terminated and not permanently reinstated, you do not qualify to receive new licenses for the same material under section 10.

9. Acceptance Not Required for Having Copies.

You are not required to accept this License in order to receive or run a copy of the Program. Ancillary propagation of a covered work occurring solely as a consequence of using peer-to-peer transmission to receive a copy likewise does not require acceptance. However, nothing other than this License grants you permission to propagate or modify any covered work. These actions infringe copyright if you do not accept this License. Therefore, by modifying or propagating a covered work, you indicate your acceptance of this License to do so.

10. Automatic Licensing of Downstream Recipients.

Each time you convey a covered work, the recipient automatically receives a license from the original licensors, to run, modify and propagate that work, subject to this License. You are not responsible for enforcing compliance by third parties with this License.

An "entity transaction" is a transaction transferring control of an organization, or substantially all assets of one, or subdividing an organization, or merging organizations. If propagation of a covered work results from an entity transaction, each party to that transaction who receives a copy of the work also receives whatever licenses to the work the party's predecessor in interest had or could give under the previous paragraph, plus a right to possession of the Corresponding Source of the work from the predecessor in interest, if the predecessor has it or can get it with reasonable efforts.

You may not impose any further restrictions on the exercise of the rights granted or affirmed under this License. For example, you may not impose a license fee, royalty, or other charge for exercise of rights granted under this License, and you may not initiate litigation (including a cross-claim or counterclaim in a lawsuit) alleging that any patent claim is infringed by making, using, selling, offering for sale, or importing the Program or any portion of it.

11. Patents.

A "contributor" is a copyright holder who authorizes use under this License of the Program or a work on which the Program is based. The work thus licensed is called the contributor's "contributor version".

A contributor's "essential patent claims" are all patent claims owned or controlled by the contributor, whether already acquired or hereafter acquired, that would be infringed by some manner, permitted by this License, of making, using, or selling its contributor version, but do not include claims that would be infringed only as a consequence of further modification of the contributor version. For purposes of this definition, "control" includes the right to grant patent sublicenses in a manner consistent with the requirements of this License.

Each contributor grants you a non-exclusive, worldwide, royalty-free patent license under the contributor's essential patent claims, to make, use, sell, offer for sale, import and otherwise run, modify and propagate the contents of its contributor version.

In the following three paragraphs, a "patent license" is any express agreement or commitment, however denominated, not to enforce a patent (such as an express permission to practice a patent or covenant not to sue for patent infringement). To "grant" such a patent license to a party means to make such an agreement or commitment not to enforce a patent against the party.

If you convey a covered work, knowingly relying on a patent license, and the Corresponding Source of the work is not available for anyone to copy, free of charge and under the terms of this License, through a publicly available network server or other readily accessible means, then you must either (1) cause the Corresponding Source to be so available, or (2) arrange to deprive yourself of the benefit of the patent license for this particular work, or (3) arrange, in a manner consistent with the requirements of this License, to extend the patent license to downstream recipients. "Knowingly relying" means you have actual knowledge that, but for the patent license, your conveying the covered work in a country, or your recipient's use of the covered work in a country, would infringe one or more identifiable patents in that country that you have reason to believe are valid.

If, pursuant to or in connection with a single transaction or arrangement, you convey, or propagate by procuring conveyance of, a covered work, and grant a patent license to some of the parties receiving the covered work authorizing them to use, propagate, modify or convey a specific copy of the covered

work, then the patent license you grant is automatically extended to all recipients of the covered work and works based on it.

A patent license is "discriminatory" if it does not include within the scope of its coverage, prohibits the exercise of, or is conditioned on the non-exercise of one or more of the rights that are specifically granted under this License. You may not convey a covered work if you are a party to an arrangement with a third party that is in the business of distributing software, under which you make payment to the third party based on the extent of your activity of conveying the work, and under which the third party grants, to any of the parties who would receive the covered work from you, a discriminatory patent license (a) in connection with copies of the covered work conveyed by you (or copies made from those copies), or (b) primarily for and in connection with specific products or compilations that contain the covered work, unless you entered into that arrangement, or that patent license was granted, prior to 28 March 2007.

Nothing in this License shall be construed as excluding or limiting any implied license or other defenses to infringement that may otherwise be available to you under applicable patent law.

12. No Surrender of Others' Freedom.

If conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot convey a covered work so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not convey it at all. For example, if you agree to terms that obligate you to collect a royalty for further conveying from those to whom you convey the Program, the only way you could satisfy both those terms and this License would be to refrain entirely from conveying the Program.

13. Use with the GNU Affero General Public License.

Notwithstanding any other provision of this License, you have permission to link or combine any covered work with a work licensed under version 3 of the GNU Affero General Public License into a single combined work, and to convey the resulting work. The terms of this License will continue to apply to the part which is the covered work, but the special requirements of the GNU Affero General Public License, section 13, concerning interaction through a network will apply to the combination as such.

14. Revised Versions of this License.

The Free Software Foundation may publish revised and/or new versions of the GNU General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Program specifies that a certain numbered version of the GNU General Public License "or any later version" applies to it, you have the option of following the terms and conditions either of that numbered version or of any later version published by the Free Software Foundation. If the Program does not specify a version number of the GNU General Public License, you may choose any version ever published by the Free Software Foundation.

If the Program specifies that a proxy can decide which future versions of the GNU General Public License can be used, that proxy's public statement of acceptance of a version permanently authorizes you to choose that version for the Program.

Later license versions may give you additional or different permissions. However, no additional obligations are imposed on any author or copyright holder as a result of your choosing to follow a later version.

15. Disclaimer of Warranty.

THERE IS NO WARRANTY FOR THE PROGRAM, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE PROGRAM "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE PROGRAM IS WITH YOU. SHOULD THE PROGRAM PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

16. Limitation of Liability.

IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MODIFIES AND/OR CONVEYS THE PROGRAM AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE PROGRAM (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE PROGRAM TO OPERATE WITH ANY OTHER PROGRAMS), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF

SUCH DAMAGES.

17.

Interpretation of Sections 15 and 16.

If the disclaimer of warranty and limitation of liability provided above cannot be given local legal effect according to their terms, reviewing courts shall apply local law that most closely approximates an absolute waiver of all civil liability in connection with the Program, unless a warranty or assumption of liability accompanies a copy of the Program in return for a fee.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Programs

If you develop a new program, and you want it to be of the greatest possible use to the public, the best way to achieve this is to make it free software which everyone can redistribute and change under these terms.

To do so, attach the following notices to the program. It is safest to attach them to the start of each source file to most effectively state the exclusion of warranty; and each file should have at least the "copyright" line and a pointer to where the full notice is found.

```
<one line to give the program's name and a brief idea of what it does.>  
Copyright (C) <year> <name of author>
```

```
This program is free software: you can redistribute it and/or modify  
it under the terms of the GNU General Public License as published by  
the Free Software Foundation, either version 3 of the License, or  
(at your option) any later version.
```

```
This program is distributed in the hope that it will be useful,  
but WITHOUT ANY WARRANTY; without even the implied warranty of  
MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the  
GNU General Public License for more details.
```

```
You should have received a copy of the GNU General Public License  
along with this program. If not, see <http://www.gnu.org/licenses/>.
```

Also add information on how to contact you by electronic and paper mail.

If the program does terminal interaction, make it output a short notice like this when it starts in an interactive mode:

<program> Copyright (C) <year> <name of author>

This program comes with ABSOLUTELY NO WARRANTY; for details type `show w'.

This is free software, and you are welcome to redistribute it under certain conditions; type `show c' for details.

The hypothetical commands `show w' and `show c' should show the appropriate parts of the General Public License. Of course, your program's commands might be different; for a GUI interface, you would use an "about box".

You should also get your employer (if you work as a programmer) or school, if any, to sign a "copyright disclaimer" for the program, if necessary.

For more information on this, and how to apply and follow the GNU GPL, see <<http://www.gnu.org/licenses/>>.

The GNU General Public License does not permit incorporating your program into proprietary programs. If your program is a subroutine library, you may consider it more useful to permit linking proprietary applications with the library. If this is what you want to

do, use the GNU Lesser General

Public License instead of this License. But first, please read

<<http://www.gnu.org/philosophy/why-not-lgpl.html>>.

GNU LESSER GENERAL PUBLIC LICENSE

Version 3, 29 June 2007

Copyright (C) 2007 Free Software Foundation, Inc. <<http://fsf.org/>>

Everyone is permitted to copy and distribute verbatim copies of this license document, but changing it is not allowed.

This version of the GNU Lesser General Public License incorporates the terms and conditions of version 3 of the GNU General Public License, supplemented by the additional permissions listed below.

0. Additional Definitions.

As used herein, "this License" refers to version 3 of the GNU Lesser General Public License, and the "GNU GPL" refers to version 3 of the GNU General Public License.

"The Library" refers to a covered work governed by this License, other than an Application or a Combined Work as defined below.

An "Application" is any work that makes use of an interface provided by the Library, but which is not otherwise based on the Library.

Defining a subclass of a class defined by the Library is deemed a mode

of using an interface provided by the Library.

A "Combined Work" is a work produced by combining or linking an Application with the Library. The particular version of the Library with which the Combined Work was made is also called the "Linked Version".

The "Minimal Corresponding Source" for a Combined Work means the Corresponding Source for the Combined Work, excluding any source code for portions of the Combined Work that, considered in isolation, are based on the Application, and not on the Linked Version.

The "Corresponding Application Code" for a Combined Work means the object code and/or source code for the Application, including any data and utility programs needed for reproducing the Combined Work from the Application, but excluding the System Libraries of the Combined Work.

1. Exception to Section 3 of the GNU GPL.

You may convey a covered work under sections 3 and 4 of this License without being bound by section 3 of the GNU GPL.

2. Conveying

Modified Versions.

If you modify a copy of the Library, and, in your modifications, a facility refers to a function or data to be supplied by an Application that uses the facility (other than as an argument passed when the facility is invoked), then you may convey a copy of the modified version:

- a) under this License, provided that you make a good faith effort to ensure that, in the event an Application does not supply the function or data, the facility still operates, and performs whatever part of its purpose remains meaningful, or
- b) under the GNU GPL, with none of the additional permissions of this License applicable to that copy.

3. Object Code Incorporating Material from Library Header Files.

The object code form of an Application may incorporate material from a header file that is part of the Library. You may convey such object code under terms of your choice, provided that, if the incorporated material is not limited to numerical parameters, data structure layouts and accessors, or small macros, inline functions and templates (ten or fewer lines in length), you do both of the following:

- a) Give prominent notice with each copy of the object code that the

Library is used in it and that the Library and its use are covered by this License.

b) Accompany the object code with a copy of the GNU GPL and this license document.

4. Combined Works.

You may convey a Combined Work under terms of your choice that, taken together, effectively do not restrict modification of the portions of the Library contained in the Combined Work and reverse engineering for debugging such modifications, if you also do each of the following:

a) Give prominent notice with each copy of the Combined Work that the Library is used in it and that the Library and its use are covered by this License.

b) Accompany the Combined Work with a copy of the GNU GPL and this license document.

c) For a Combined Work that displays copyright notices during execution, include the copyright notice for the Library among these notices, as well as a reference directing the user to the copies of the GNU GPL and this license document.

d) Do one of the following:

0) Convey the Minimal Corresponding Source under the terms of this License, and the Corresponding Application Code in a form suitable for, and under terms that permit, the user to recombine or relink the Application with a modified version of the Linked Version to produce a modified Combined Work, in the manner specified by section 6 of the GNU GPL for conveying Corresponding Source.

1) Use a suitable shared library mechanism for linking with the Library. A suitable mechanism is one that (a) uses at run time a copy of the Library already present on the user's computer system, and (b) will operate properly with a modified version of the Library that is interface-compatible with the Linked Version.

e) Provide Installation Information, but only if you would otherwise be required to provide such information under section 6 of the GNU GPL, and only to the extent that such information is

necessary to install and execute a modified version of the Combined Work produced by recombining or relinking the Application with a modified version of the Linked Version. (If you use option 4d0, the Installation Information must accompany the Minimal Corresponding Source and Corresponding Application Code. If you use option 4d1, you must provide the Installation Information in the manner specified by section 6 of the GNU GPL for conveying Corresponding Source.)

5. Combined Libraries.

You may place library facilities that are a work based on the Library side by side in a single library together with other library facilities that are not Applications and are not covered by this License, and convey such a combined library under terms of your choice, if you do both of the following:

a) Accompany the combined library with a copy of the same work based on the Library, uncombined with any other library facilities, conveyed under the terms of this License.

b) Give prominent notice with the combined library that part of it is a work based on the Library, and explaining where to find the accompanying uncombined form of the same work.

6. Revised Versions of the GNU Lesser General Public License.

The Free Software Foundation may publish revised and/or new versions of the GNU Lesser General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Library as you received it specifies that a certain numbered version of the GNU Lesser General Public License "or any later version" applies to it, you have the option of following the terms and conditions either of that published version or of any later version published by the Free Software Foundation. If the Library as you received it does not specify a version number of the GNU Lesser General Public License, you may choose any version of the GNU Lesser General Public License ever published by the Free Software Foundation.

If the Library as you received it specifies that a proxy can decide whether future versions of the GNU Lesser General Public License shall apply, that proxy's public statement of acceptance of any version is permanent authorization for you to choose that version for the

Library.

GNU GENERAL PUBLIC LICENSE

Version 3, 29 June 2007

Copyright (C) 2007 Free Software Foundation, Inc. <<http://fsf.org/>>

Everyone is permitted to copy and distribute verbatim copies of this license document, but changing it is not allowed.

Preamble

The GNU General Public License is a free, copyleft license for software and other kinds of works.

The licenses for most software and other practical works are designed to take away your freedom to share and change the works. By contrast, the GNU General Public License is intended to guarantee your freedom to share and change all versions of a program--to make sure it remains free software for all its users. We, the Free Software Foundation, use the GNU General Public License for most of our software; it applies also to any other work released this way by its authors. You can apply it to your programs, too.

When we speak of free software, we are referring to freedom, not price. Our General Public Licenses are designed to make sure that you have the freedom to distribute copies of free software (and charge for them if you wish), that you receive source code or can get it if you want it, that you can change the software or use pieces of it in new free programs, and that you know you can do these things.

To protect your rights, we need to prevent others from denying you these rights or asking you to surrender the rights. Therefore, you have certain responsibilities if you distribute copies of the software, or if you modify it: responsibilities to respect the freedom of others.

For example, if you distribute copies of such a program, whether gratis or for a fee, you must pass on to the recipients the same freedoms that you received. You must make sure that they, too, receive or can get the source code. And you must show them these terms so they know their rights.

Developers that use the GNU GPL protect your rights with two steps:

- (1) assert copyright on the software, and
- (2) offer you this License giving you legal permission to copy, distribute and/or modify it.

For the developers' and authors' protection, the GPL clearly explains that there is no warranty for this free software. For both users' and

authors' sake, the GPL requires that modified versions be marked as changed, so that their problems will not be attributed erroneously to authors of previous versions.

Some devices are designed to deny users access to install or run modified versions of the software inside them, although the manufacturer can do so. This is fundamentally incompatible with the aim of protecting users' freedom to change the software. The systematic pattern of such abuse occurs in the area of products for individuals to use, which is precisely where it is most unacceptable. Therefore, we have designed this version of the GPL to prohibit the practice for those products. If such problems arise substantially in other domains, we stand

ready to extend this provision to those domains in future versions of the GPL, as needed to protect the freedom of users.

Finally, every program is threatened constantly by software patents. States should not allow patents to restrict development and use of software on general-purpose computers, but in those that do, we wish to avoid the special danger that patents applied to a free program could make it effectively proprietary. To prevent this, the GPL assures that patents cannot be used to render the program non-free.

The precise terms and conditions for copying, distribution and modification follow.

TERMS AND CONDITIONS

0. Definitions.

"This License" refers to version 3 of the GNU General Public License.

"Copyright" also means copyright-like laws that apply to other kinds of works, such as semiconductor masks.

"The Program" refers to any copyrightable work licensed under this License. Each licensee is addressed as "you". "Licensees" and "recipients" may be individuals or organizations.

To "modify" a work means to copy from or adapt all or part of the work in a fashion requiring copyright permission, other than the making of an exact copy. The resulting work is called a "modified version" of the earlier work or a work "based on" the earlier work.

A "covered work" means either the unmodified Program or a work based on the Program.

To "propagate" a work means to do anything with it that, without permission, would make you directly or secondarily liable for infringement under applicable copyright law, except executing it on a computer or modifying a private copy. Propagation includes copying, distribution (with or without modification), making available to the public, and in some countries other activities as well.

To "convey" a work means any kind of propagation that enables other parties to make or receive copies. Mere interaction with a user through a computer network, with no transfer of a copy, is not conveying.

An interactive user interface displays "Appropriate Legal Notices" to the extent that it includes a convenient and prominently visible feature that (1) displays an appropriate copyright notice, and (2) tells the user that there is no warranty for the work (except to the extent that warranties are provided), that licensees may convey the work under this License, and how to view a copy of this License. If the interface presents a list of user commands or options, such as a menu, a prominent item in the list meets this criterion.

1. Source Code.

The "source code" for a work means the preferred form of the work for making modifications to it. "Object code" means any non-source form of a work.

A "Standard Interface" means an interface that either is an official standard defined by a recognized standards body, or, in the case of interfaces specified for a particular programming language, one that is widely used among developers working in that language.

The "System Libraries" of an executable work include anything, other than the work as a whole, that (a) is included in the normal form of packaging a Major Component, but which is not part of that Major Component, and (b) serves only to enable use of the work with that Major Component, or to implement a Standard Interface for which an implementation is available to the public in source code form. A "Major Component", in this context, means a major essential component (kernel, window system, and so on) of the specific operating system (if any) on which the executable work runs, or a compiler used to produce the work, or an object code interpreter used to run it.

The "Corresponding Source" for a work in object code form means all the source code needed to generate, install, and (for an executable work) run the object code and to modify the work, including scripts to control those activities. However, it does not include the work's

System Libraries, or general-purpose tools or generally available free programs which are used unmodified in performing those activities but which are not part of the work. For example, Corresponding Source includes interface definition files associated with source files for the work, and the source code for shared libraries and dynamically linked subprograms that the work is specifically designed to require, such as by intimate data communication or control flow between those subprograms and other parts of the work.

The Corresponding Source need not include anything that users can regenerate automatically from other parts of the Corresponding Source.

The Corresponding Source for a work in source code form is that same work.

2. Basic Permissions.

All rights granted under this License are granted for the term of copyright on the Program, and are irrevocable provided the stated conditions are met. This License explicitly affirms your unlimited permission to run the unmodified Program. The output from running a covered work is covered by this License only if the output, given its content, constitutes a covered work. This License acknowledges your rights of fair use or other equivalent, as provided by copyright law.

You may make, run and propagate covered works that you do not convey, without conditions so long as your license otherwise remains in force. You may convey covered works to others for the sole purpose of having them make modifications exclusively for you, or provide you with facilities for running those works, provided that you comply with the terms of this License in conveying all material for which you do not control copyright. Those thus making or running the covered works for you must do so exclusively on your behalf, under your direction and control, on terms that prohibit them from making any copies of your copyrighted material outside their relationship with you.

Conveying under any other circumstances is permitted solely under the conditions stated below. Sublicensing is not allowed; section 10 makes it unnecessary.

3. Protecting Users' Legal Rights From Anti-Circumvention Law.

No covered work shall be deemed part of an effective technological measure under any applicable law fulfilling obligations under article

11 of the WIPO copyright treaty adopted on 20 December 1996, or similar laws prohibiting or restricting circumvention of such measures.

When you convey a covered work, you waive any legal power to forbid circumvention of technological measures to the extent such circumvention is effected by exercising rights under this License with respect to the covered work, and you disclaim any intention to limit operation or modification of the work as a means of enforcing, against the work's users, your or third parties' legal rights to forbid circumvention of technological measures.

4. Conveying Verbatim Copies.

You may convey verbatim copies of the Program's source code as you receive it, in any medium, provided that you conspicuously and appropriately publish on each copy an appropriate copyright notice; keep intact all notices stating that this License and any non-permissive terms added in accord with section 7 apply to the code; keep intact all notices of the absence of any warranty; and give all recipients a copy of this License along with the Program.

You may charge any price or no price for each copy that you convey, and you may offer support or warranty protection for a fee.

5. Conveying Modified Source Versions.

You may convey a work based on the Program, or the modifications to produce it from the Program, in the form of source code under the terms of section 4, provided that you also meet all of these conditions:

- a) The work must carry prominent notices stating that you modified it, and giving a relevant date.
- b) The work must carry prominent notices stating that it is released under this License and any conditions added under section 7. This requirement modifies the requirement in section 4 to "keep intact all notices".
- c) You must license the entire work, as a whole, under this License to anyone who comes into possession of a copy. This License will therefore apply, along with any applicable section 7 additional terms, to the whole of the work, and all its parts, regardless of how they are packaged. This License gives no permission to license the work in any other way, but it does not invalidate such permission if you have separately received it.

d) If the work has interactive user interfaces, each must display Appropriate Legal Notices; however, if the Program has interactive interfaces that do not display Appropriate Legal Notices, your work need not make them do so.

A compilation of a covered work with other separate and independent works, which are not by their nature extensions of the covered work, and which are not combined with it such as to form a larger program, in or on a volume of a storage or distribution medium, is called an "aggregate" if the compilation and its resulting copyright are not used to limit the access or legal rights of the compilation's users beyond what the individual works permit. Inclusion of a covered work in an aggregate does not cause this License to apply to the other parts of the aggregate.

6. Conveying Non-Source Forms.

You may convey a covered work in object code form under the terms of sections 4 and 5, provided that you also convey the machine-readable Corresponding Source under the terms of this License, in one of these ways:

a) Convey the object code in, or embodied in, a physical product (including a physical distribution medium), accompanied by the Corresponding Source fixed on a durable physical medium customarily used for software interchange.

b) Convey the object code in, or embodied in, a physical product (including a physical distribution medium), accompanied by a written offer, valid for at least three years and valid for as long as you offer spare parts or customer support for that product model, to give anyone who possesses the object code either (1) a copy of the Corresponding Source for all the software in the product that is covered by this License, on a durable physical medium customarily used for software interchange, for a price no more than your reasonable cost of physically performing this conveying of source, or (2) access to copy the Corresponding Source from a network server at no charge.

c) Convey individual copies of the object code with a copy of the written offer to provide the Corresponding Source. This alternative is allowed only occasionally and noncommercially, and only if you received the object code with such an offer, in accord with subsection 6b.

d) Convey the object code by offering access from a designated place (gratis or for a charge), and offer equivalent access to the Corresponding Source in the same way through the same place at no further charge. You need not require recipients to copy the Corresponding Source along with the object code. If the place to copy the object code is a network server, the Corresponding Source may be on a different server (operated by you or a third party) that supports equivalent copying facilities, provided you maintain clear directions next to the object code saying where to find the Corresponding Source. Regardless of what server hosts the Corresponding Source, you remain obligated to ensure that it is available for as long as needed to satisfy these requirements.

e) Convey the object code using peer-to-peer transmission, provided you inform other peers where the object code and Corresponding Source of the work are being offered to the general public at no charge under subsection 6d.

A separable portion of the object code, whose source code is excluded from the Corresponding Source as a System Library, need not be included in conveying the object code work.

A "User Product" is either (1) a "consumer product", which means any tangible personal property which is normally used for personal, family, or household purposes, or (2) anything designed or sold for incorporation into a dwelling. In determining whether a product is a consumer product, doubtful cases shall be resolved in favor of coverage. For a particular product received by a particular user, "normally used" refers to a typical or common use of that class of product, regardless of the status of the particular user or of the way in which the particular user actually uses, or expects or is expected to use, the product. A product is a consumer product regardless of whether the product has substantial commercial, industrial or non-consumer uses, unless such uses represent the only significant mode of use of the product.

"Installation Information" for a User Product means any methods, procedures, authorization keys, or other information required to install and execute modified versions of a covered work in that User Product from a modified version of its Corresponding Source. The information must suffice to ensure that the continued functioning of the modified object code is in no case prevented or interfered with solely because modification has been made.

If you convey an object code work under this section in, or with, or specifically for use in, a User Product, and the conveying occurs as

part of a transaction in which the right of possession and use of the User Product is transferred to the recipient in perpetuity or for a fixed term (regardless of how the transaction is characterized), the Corresponding Source conveyed under this section must be accompanied by the Installation Information. But this requirement does not apply if neither you nor any third party retains the ability to install modified object code on the User Product (for example, the work has been installed in ROM).

The requirement to provide Installation Information does not include a requirement to continue to provide support service, warranty, or updates for a work that has been modified or installed by the recipient, or for the User Product in which it has been modified or installed. Access to a network may be denied when the modification itself materially and adversely affects the operation of the network or violates the rules and protocols for communication across the network.

Corresponding Source conveyed, and Installation Information provided, in accord with this section must be in a format that is publicly documented (and with an implementation available to the public in source code form), and must require no special password or key for unpacking, reading or copying.

7. Additional Terms.

"Additional permissions" are terms that supplement the terms of this License by making exceptions from one or more of its conditions. Additional permissions that are applicable to the entire Program shall be treated as though they were included in this License, to the extent that they are valid under applicable law. If additional permissions apply only to part of the Program, that part may be used separately under those permissions, but the entire Program remains governed by this License without regard to the additional permissions.

When you convey a copy of a covered work, you may at your option remove any additional permissions from that copy, or from any part of it. (Additional permissions may be written to require their own removal in certain cases when you modify the work.) You may place additional permissions on material, added by you to a covered work, for which you have or can give appropriate copyright permission.

Notwithstanding any other provision of this License, for material you add to a covered work, you may (if authorized by the copyright holders of that material) supplement the terms of this License with terms:

- a) Disclaiming warranty or

limiting liability differently from the terms of sections 15 and 16 of this License; or

b) Requiring preservation of specified reasonable legal notices or author attributions in that material or in the Appropriate Legal Notices displayed by works containing it; or

c) Prohibiting misrepresentation of the origin of that material, or requiring that modified versions of such material be marked in reasonable ways as different from the original version; or

d) Limiting the use for publicity purposes of names of licensors or authors of the material; or

e) Declining to grant rights under trademark law for use of some trade names, trademarks, or service marks; or

f) Requiring indemnification of licensors and authors of that material by anyone who conveys the material (or modified versions of it) with contractual assumptions of liability to the recipient, for any liability that these contractual assumptions directly impose on

those licensors and authors.

All other non-permissive additional terms are considered "further restrictions" within the meaning of section 10. If the Program as you received it, or any part of it, contains a notice stating that it is governed by this License along with a term that is a further restriction, you may remove that term. If a license document contains a further restriction but permits relicensing or conveying under this License, you may add to a covered work material governed by the terms of that license document, provided that the further restriction does not survive such relicensing or conveying.

If you add terms to a covered work in accord with this section, you must place, in the relevant source files, a statement of the additional terms that apply to those files, or a notice indicating where to find the applicable terms.

Additional terms, permissive or non-permissive, may be stated in the form of a separately written license, or stated as exceptions; the above requirements apply either way.

8. Termination.

You may not propagate or modify a covered work except as expressly provided under this License. Any attempt otherwise to propagate or

modify it is void, and will automatically terminate your rights under this License (including any patent licenses granted under the third paragraph of section 11).

However, if you cease all violation of this License, then your license from a particular copyright holder is reinstated (a) provisionally, unless and until the copyright holder explicitly and finally terminates your license, and (b) permanently, if the copyright holder fails to notify you of the violation by some reasonable means prior to 60 days after the cessation.

Moreover, your license from a particular copyright holder is reinstated permanently if the copyright holder notifies you of the violation by some reasonable means, this is the first time you have received notice of violation of this License (for any work) from that copyright holder, and you cure the violation prior to 30 days after your receipt of the notice.

Termination of your rights under this section does not terminate the licenses of parties who have received copies or rights from you under this License. If your rights have been terminated and not permanently reinstated, you do not qualify to receive new licenses for the same material under section 10.

9. Acceptance Not Required for Having Copies.

You are not required to accept this License in order to receive or run a copy of the Program. Ancillary propagation of a covered work occurring solely as a consequence of using peer-to-peer transmission to receive a copy likewise does not require acceptance. However, nothing other than this License grants you permission to propagate or modify any covered work. These actions infringe copyright if you do not accept this License. Therefore, by modifying or propagating a covered work, you indicate your acceptance of this License to do so.

10. Automatic Licensing of Downstream Recipients.

Each time you convey a covered work, the recipient automatically receives a license from the original licensors, to run, modify and propagate that work, subject to this License. You are not responsible for enforcing compliance by third parties with this License.

An "entity transaction" is a transaction transferring control of an organization, or substantially all assets of one, or subdividing an organization, or merging organizations. If propagation of a covered work results from an entity transaction, each party to that

transaction who receives a copy of the work also receives whatever licenses to the work the party's predecessor in interest had or could give under the previous paragraph, plus a right to possession of the Corresponding Source of the work from the predecessor in interest, if the predecessor has it or can get it with reasonable efforts.

You may not impose any further restrictions on the exercise of the rights

granted or affirmed under this License. For example, you may not impose a license fee, royalty, or other charge for exercise of rights granted under this License, and you may not initiate litigation (including a cross-claim or counterclaim in a lawsuit) alleging that any patent claim is infringed by making, using, selling, offering for sale, or importing the Program or any portion of it.

11. Patents.

A "contributor" is a copyright holder who authorizes use under this License of the Program or a work on which the Program is based. The work thus licensed is called the contributor's "contributor version".

A contributor's "essential patent claims" are all patent claims owned or controlled by the contributor, whether already acquired or hereafter acquired, that would be infringed by some manner, permitted by this License, of making, using, or selling its contributor version, but do not include claims that would be infringed only as a consequence of further modification of the contributor version. For purposes of this definition, "control" includes the right to grant patent sublicenses in a manner consistent with the requirements of this License.

Each contributor grants you a non-exclusive, worldwide, royalty-free patent license under the contributor's essential patent claims, to make, use, sell, offer for sale, import and otherwise run, modify and propagate the contents of its contributor version.

In the following three paragraphs, a "patent license" is any express agreement or commitment, however denominated, not to enforce a patent (such as an express permission to practice a patent or covenant not to sue for patent infringement). To "grant" such a patent license to a party means to make such an agreement or commitment not to enforce a patent against the party.

If you convey a covered work, knowingly relying on a patent license, and the Corresponding Source of the work is not available for anyone to copy, free of charge and under the terms of this

License, through a publicly available network server or other readily accessible means, then you must either (1) cause the Corresponding Source to be so available, or (2) arrange to deprive yourself of the benefit of the patent license for this particular work, or (3) arrange, in a manner consistent with the requirements of this License, to extend the patent license to downstream recipients. "Knowingly relying" means you have actual knowledge that, but for the patent license, your conveying the covered work in a country, or your recipient's use of the covered work in a country, would infringe one or more identifiable patents in that country that you have reason to believe are valid.

If, pursuant to or in connection with a single transaction or arrangement, you convey, or propagate by procuring conveyance of, a covered work, and grant a patent license to some of the parties receiving the covered work authorizing them to use, propagate, modify or convey a specific copy of the covered work, then the patent license you grant is automatically extended to all recipients of the covered work and works based on it.

A patent license is "discriminatory" if it does not include within the scope of its coverage, prohibits the exercise of, or is conditioned on the non-exercise of one or more of the rights that are specifically granted under this License. You may not convey a covered work if you are a party to an arrangement with a third party that is in the business of distributing software, under which you make payment to the third party based on the extent of your activity of conveying the work, and under which the third party grants, to any of the parties who would receive the covered work from you, a discriminatory patent license (a) in connection with copies of the covered work conveyed by you (or copies made from those copies), or (b) primarily for and in connection with specific products or compilations that contain the covered work, unless you entered into that arrangement, or that patent license was granted, prior to 28 March 2007.

Nothing in this License shall be construed as excluding or limiting any implied license or other defenses to infringement that may otherwise be available to you under applicable patent law.

12. No Surrender of Others' Freedom.

If conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot convey a covered work so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may

not convey it at all. For example, if you agree to terms that obligate you to collect a royalty for further conveying from those to whom you convey the Program, the only way you could satisfy both those terms and this License would be to refrain entirely from conveying the Program.

13. Use with the GNU Affero General Public License.

Notwithstanding any other provision of this License, you have permission to link or combine any covered work with a work licensed under version 3 of the GNU Affero General Public License into a single combined work, and to convey the resulting work. The terms of this License will continue to apply to the part which is the covered work, but the special requirements of the GNU Affero General Public License, section 13, concerning interaction through a network will apply to the combination as such.

14. Revised Versions of this License.

The Free Software Foundation may publish revised and/or new versions of the GNU General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Program specifies that a certain numbered version of the GNU General Public License "or any later version" applies to it, you have the option of following the terms and conditions either of that numbered version or of any later version published by the Free Software Foundation. If the Program does not specify a version number of the GNU General Public License, you may choose any version ever published by the Free Software Foundation.

If the Program specifies that a proxy can decide which future versions of the GNU General Public License can be used, that proxy's public statement of acceptance of a version permanently authorizes you to choose that version for the Program.

Later license versions may give you additional or different permissions. However, no additional obligations are imposed on any author or copyright holder as a result of your choosing to follow a later version.

15. Disclaimer of Warranty.

THERE IS NO WARRANTY FOR THE PROGRAM, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE PROGRAM "AS IS"

WITHOUT WARRANTY

OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE PROGRAM IS WITH YOU. SHOULD THE PROGRAM PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

16. Limitation of Liability.

IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MODIFIES AND/OR CONVEYS THE PROGRAM AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE PROGRAM (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE PROGRAM TO OPERATE WITH ANY OTHER PROGRAMS), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

17.

Interpretation of Sections 15 and 16.

If the disclaimer of warranty and limitation of liability provided above cannot be given local legal effect according to their terms, reviewing courts shall apply local law that most closely approximates an absolute waiver of all civil liability in connection with the Program, unless a warranty or assumption of liability accompanies a copy of the Program in return for a fee.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Programs

If you develop a new program, and you want it to be of the greatest possible use to the public, the best way to achieve this is to make it free software which everyone can redistribute and change under these terms.

To do so, attach the following notices to the program. It is safest to attach them to the start of each source file to most effectively state the exclusion of warranty; and each file should have at least the "copyright" line and a pointer to where the full notice is found.

```
<one line to give the program's name and a brief idea of what it does.>  
Copyright (C) <year> <name of author>
```

This program is free software: you can redistribute it and/or modify it under the terms of the GNU General Public License as published by

the Free Software Foundation, either version 3 of the License, or
(at your option) any later version.

This program is distributed in the hope that it will be useful,
but WITHOUT ANY WARRANTY; without even the implied warranty of
MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
GNU General Public License for more details.

You should have received a copy of the GNU General Public License
along with this program. If not, see <<https://www.gnu.org/licenses/>>.

Also add information on how to contact you by electronic and paper mail.

If the program does terminal interaction, make it output a short
notice like this when it starts in an interactive mode:

```
<program> Copyright (C) <year> <name of author>  
This program comes with ABSOLUTELY NO WARRANTY; for details type `show w'.  
This is free software, and you are welcome to redistribute it  
under certain conditions; type `show c' for details.
```

The hypothetical commands `show w' and `show c' should show the appropriate
parts of the General Public License. Of course, your program's commands
might be different; for a GUI interface, you would use an "about box".

You should also get your employer (if you work as a programmer) or school,
if any, to sign a "copyright disclaimer" for the program, if necessary.
For more information on this, and how to apply and follow the GNU GPL, see
<<https://www.gnu.org/licenses/>>.

The GNU General Public License does not permit incorporating your program
into proprietary programs. If your program is a subroutine library, you
may consider it more useful to permit linking proprietary applications with
the library. If this is what you want to
do, use the GNU Lesser General
Public License instead of this License. But first, please read
<<https://www.gnu.org/philosophy/why-not-lgpl.html>>.

GMP Debian Package

This gmp package was built for Debian by

Steve M. Robbins <smr@debian.org>
Philipp Matthias Hahn <pmhahn@debian.org>

from sources obtained at <http://gmplib.org/> .

GMP Source Code

Copyright 1991, 1996, 1999, 2000, 2007 Free Software Foundation, Inc.

This file is part of the GNU MP Library.

The GNU MP Library is free software; you can redistribute it and/or modify it under the terms of either:

* the GNU Lesser General Public License as published by the Free Software Foundation; either version 3 of the License, or (at your option) any later version.

or

* the GNU General Public License as published by the Free Software Foundation; either version 2 of the License, or (at your option) any later version.

or both in parallel, as here.

The GNU MP Library is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details.

You should have received copies of the GNU General Public License and the GNU Lesser General Public License along with the GNU MP Library. If not, see <https://www.gnu.org/licenses/>.

The GNU Lesser General Public License v3 text is contained in `/usr/share/common-licenses/LGPL-3`.
The GNU General Public License v2 text is contained in `/usr/share/common-licenses/GPL-2`.
The GNU General Public License v3 text is contained in `/usr/share/common-licenses/GPL-3`.

GMP Documentation

The documentation is released under the GNU Free Documentation License (GFDL) and it has cover texts. As such, it has been determined not to meet the Debian Free Software Guidelines, and is not shipped in the debian packages.

The demo code in the `-doc` package is covered either by the LGPL, or under the GNU General Public License `/usr/share/common-licenses/GPL`.

See the individual source files to determine the license under which it falls.

1.96 shadow 4.5-1ubuntu2.5

1.96.1 Available under license :

NOTE:

This license has been obsoleted by the change to the BSD-style copyright. You may continue to use this license if you wish, but you are under no obligation to do so.

(*

This document is freely plagiarised from the 'Artistic Licence', distributed as part of the Perl v4.0 kit by Larry Wall, which is available from most major archive sites. I stole it from CrackLib.

\$Id\$

*)

This documents purpose is to state the conditions under which this Package (See definition below) viz: "Shadow", the Shadow Password Suite which is held by Julianne Frances Haugh, may be copied, such that the copyright holder maintains some semblance of artistic control over the development of the package, while giving the users of the package the right to use and distribute the Package in a more-or-less customary fashion, plus the right to make reasonable modifications.

So there.

Definitions:

A "Package" refers to the collection of files distributed by the Copyright Holder, and derivatives of that collection of files created through textual modification, or segments thereof.

"Standard Version" refers to such a Package if it has not been modified, or has been modified in accordance with the wishes of the Copyright Holder.

"Copyright Holder" is whoever is named in the copyright or copyrights for the package.

"You" is you, if you're thinking about copying or distributing this Package.

"Reasonable copying fee" is whatever you can justify on the basis of media cost, duplication charges, time of people involved, and so on. (You will not be required to justify it to the Copyright Holder, but only to the computing community at large as a market that must bear the fee.)

"Freely Available" means that no fee is charged for the item itself, though there may be fees involved in handling the item. It also means that recipients of the item may redistribute it under the same conditions they received it.

1. You

may make and give away verbatim copies of the source form of the Standard Version of this Package without restriction, provided that you duplicate all of the original copyright notices and associated disclaimers.

2. You may apply bug fixes, portability fixes and other modifications derived from the Public Domain or from the Copyright Holder. A Package modified in such a way shall still be considered the Standard Version.

3. You may otherwise modify your copy of this Package in any way, provided that you insert a prominent notice in each changed file stating how and when AND WHY you changed that file, and provided that you do at least ONE of the following:

a) place your modifications in the Public Domain or otherwise make them Freely Available, such as by posting said modifications to Usenet or an equivalent medium, or placing the modifications on a major archive site such as uunet.uu.net, or by allowing the Copyright Holder to include your modifications in the Standard Version of the Package.

b) use the modified Package only within your corporation or organization.

c) rename any non-standard executables so the names do not conflict with standard executables, which must also be provided, and provide separate documentation for each non-standard executable that clearly documents how it differs from the Standard Version.

d) make other distribution arrangements with the Copyright Holder.

4. You may distribute the programs of this Package in object code or executable form, provided that you do at least ONE of the following:

a) distribute a Standard Version of the executables and library files, together with instructions (in the manual page or equivalent) on where to get the Standard Version.

b) accompany the distribution with the machine-readable source of the Package with your modifications.

c) accompany any non-standard executables with their corresponding Standard Version executables, giving the non-standard executables non-standard names, and clearly documenting the differences in manual pages (or equivalent), together with instructions on where to get the Standard Version.

d) make other distribution arrangements with the Copyright Holder.

5. You may charge a reasonable copying fee for any distribution of this Package. You may charge any fee you choose for support of this Package. **YOU MAY NOT CHARGE A FEE FOR THIS PACKAGE ITSELF.** However, you may distribute this Package in aggregate with other (possibly commercial) programs as part of a larger (possibly commercial) software distribution provided that **YOU DO NOT ADVERTISE** this package as a product of your own.

6. The name of the Copyright Holder may not be used to endorse or promote products derived from this software without specific prior written permission.

7. **THIS PACKAGE IS PROVIDED "AS IS" AND WITHOUT ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, WITHOUT LIMITATION, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE.**

The End

GNU GENERAL PUBLIC LICENSE

Version 2, June 1991

Copyright (C) 1989, 1991 Free Software Foundation, Inc.

675 Mass Ave, Cambridge, MA 02139, USA

Everyone is permitted to copy and distribute verbatim copies of this license document, but changing it is not allowed.

Preamble

The licenses for most software are designed to take away your freedom to share and change it. By contrast, the GNU General Public License is intended to guarantee your freedom to share and change free software--to make sure the software is free for all its users. This

General Public License applies to most of the Free Software Foundation's software and to any other program whose authors commit to using it. (Some other Free Software Foundation software is covered by the GNU Library General Public License instead.) You can apply it to your programs, too.

When we speak of free software, we are referring to freedom, not price. Our General Public Licenses are designed to make sure that you have the freedom to distribute copies of free software (and charge for this service if you wish), that you receive source code or can get it if you want it, that you can change the software or use pieces of it in new free programs; and that you know you can do these things.

To protect your rights, we need to make restrictions that forbid anyone to deny you these rights or to ask you to surrender the rights. These restrictions translate to certain responsibilities for you if you distribute copies of the software, or if you modify it.

For example, if you distribute copies of such a program, whether gratis or for a fee, you must give the recipients all the rights that you have. You must make sure that they, too, receive or can get the source code. And you must show them these terms so they know their rights.

We protect your rights with two steps: (1) copyright the software, and (2) offer you this license which gives you legal permission to copy, distribute and/or modify the software.

Also, for each author's protection and ours, we want to make certain that everyone understands that there is no warranty for this free software. If the software is modified by someone else and passed on, we want its recipients to know that what they have is not the original, so that any problems introduced by others will not reflect on the original authors' reputations.

Finally, any free program is threatened constantly by software patents. We wish to avoid the danger that redistributors of a free program will individually obtain patent licenses, in effect making the program proprietary. To prevent this, we have made it clear that any patent must be licensed for everyone's free use or not licensed at all.

The precise terms and conditions for copying, distribution and modification follow.

GNU GENERAL PUBLIC LICENSE
TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

0. This License applies to any program or other work which contains a notice placed by the copyright holder saying it may be distributed under the terms of this General Public License. The "Program", below, refers to any such program or work, and a "work based on the Program" means either the Program or any derivative work under copyright law: that is to say, a work containing the Program or a portion of it, either verbatim or with modifications and/or translated into another language. (Hereinafter, translation is included without limitation in the term "modification".) Each licensee is addressed as "you".

Activities other than copying, distribution and modification are not covered by this License; they are outside its scope. The act of running the Program is not restricted, and the output from the Program is covered only if its contents constitute a work based on the Program (independent of having been made by running the Program). Whether that is true depends on what the Program does.

1. You may copy and distribute verbatim copies of the Program's source code as you receive it, in any medium, provided that you conspicuously and appropriately publish on each copy an appropriate copyright notice and disclaimer of warranty; keep intact all the notices that refer to this License and to the absence of any warranty; and give any other recipients of the Program a copy of this License along with the Program.

You may charge a fee for the physical act of transferring a copy, and you may at your option offer warranty protection in exchange for a fee.

2. You may modify your copy or copies of the Program or any portion of it, thus forming a work based on the Program, and copy and distribute such modifications or work under the terms of Section 1 above, provided that you also meet all of these conditions:

a) You must cause the modified files to carry prominent notices stating that you changed the files and the date of any change.

b) You must cause any work that you distribute or publish, that in whole or in part contains or is derived from the Program or any part thereof, to be licensed as a whole at no charge to all third parties under the terms of this License.

c) If the modified program normally reads commands interactively when run, you must cause it, when started running for such interactive use in the most ordinary way, to print or display an

announcement including an appropriate copyright notice and a notice that there is no warranty (or else, saying that you provide a warranty) and that users may redistribute the program under these conditions, and telling the user how to view a copy of this License. (Exception: if the Program itself is interactive but does not normally print such an announcement, your work based on the Program is not required to print an announcement.)

These requirements apply to the modified work as a whole. If identifiable sections of that work are not derived from the Program, and can be reasonably considered independent and separate works in themselves, then this License, and its terms, do not apply to those sections when you distribute them as separate works. But when you distribute the same sections as part of a whole which is a work based on the Program, the distribution of the whole must be on the terms of this License, whose permissions for other licensees extend to the entire whole, and thus to each and every part regardless of who wrote it.

Thus, it is not the intent of this section to claim rights or contest your rights to work written entirely by you; rather, the intent is to exercise the right to control the distribution of derivative or collective works based on the Program.

In addition, mere aggregation of another work not based on the Program with the Program (or with a work based on the Program) on a volume of a storage or distribution medium does not bring the other work under the scope of this License.

3. You may copy and distribute the Program (or a work based on it, under Section 2) in object code or executable form under the terms of Sections 1 and 2 above provided that you also do one of the following:

a) Accompany it with the complete corresponding machine-readable source code, which must be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange; or,

b) Accompany it with a written offer, valid for at least three years, to give any third party, for a charge no more than your cost of physically performing source distribution, a complete machine-readable copy of the corresponding source code, to be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange; or,

c) Accompany it with the information you received as to the offer to distribute corresponding source code. (This alternative is allowed only for noncommercial distribution and only if you

received the program in object code
or executable form with such
an offer, in accord with Subsection b above.)

The source code for a work means the preferred form of the work for making modifications to it. For an executable work, complete source code means all the source code for all modules it contains, plus any associated interface definition files, plus the scripts used to control compilation and installation of the executable. However, as a special exception, the source code distributed need not include anything that is normally distributed (in either source or binary form) with the major components (compiler, kernel, and so on) of the operating system on which the executable runs, unless that component itself accompanies the executable.

If distribution of executable or object code is made by offering access to copy from a designated place, then offering equivalent access to copy the source code from the same place counts as distribution of the source code, even though third parties are not compelled to copy
the source along with the object code.

4. You may not copy, modify, sublicense, or distribute the Program except as expressly provided under this License. Any attempt otherwise to copy, modify, sublicense or distribute the Program is void, and will automatically terminate your rights under this License. However, parties who have received copies, or rights, from you under this License will not have their licenses terminated so long as such parties remain in full compliance.

5. You are not required to accept this License, since you have not signed it. However, nothing else grants you permission to modify or distribute the Program or its derivative works. These actions are prohibited by law if you do not accept this License. Therefore, by modifying or distributing the Program (or any work based on the Program), you indicate your acceptance of this License to do so, and all its terms and conditions for copying, distributing or modifying the Program or works based on it.

6.

Each time you redistribute the Program (or any work based on the Program), the recipient automatically receives a license from the original licensor to copy, distribute or modify the Program subject to these terms and conditions. You may not impose any further restrictions on the recipients' exercise of the rights granted herein. You are not responsible for enforcing compliance by third parties to this License.

7. If, as a consequence of a court judgment or allegation of patent infringement or for any other reason (not limited to patent issues), conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot distribute so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not distribute the Program at all. For example, if a patent license would not permit royalty-free redistribution of the Program by all those who receive copies directly or indirectly through you, then the only way you could satisfy both it and this License would be to refrain entirely from distribution of the Program.

If any portion of this section is held invalid or unenforceable under any particular circumstance, the balance of the section is intended to apply and the section as a whole is intended to apply in other circumstances.

It is not the purpose of this section to induce you to infringe any patents or other property right claims or to contest validity of any such claims; this section has the sole purpose of protecting the integrity of the free software distribution system, which is implemented by public license practices. Many people have made generous contributions to the wide range of software distributed through that system in reliance on consistent application of that system; it is up to the author/donor to decide if he or she is willing to distribute software through any other system and a licensee cannot impose that choice.

This section is intended to make thoroughly clear what is believed to be a consequence of the rest of this License.

8. If the distribution and/or use of the Program is restricted in certain countries either by patents or by copyrighted interfaces, the original copyright holder who places the Program under this License may add an explicit geographical distribution limitation excluding those countries, so that distribution is permitted only in or among countries not thus excluded. In such case, this License incorporates the limitation as if written in the body of this License.

9. The Free Software Foundation may publish revised and/or new versions of the General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Program

specifies a version number of this License which applies to it and "any later version", you have the option of following the terms and conditions either of that version or of any later version published by the Free Software Foundation. If the Program does not specify a version number of this License, you may choose any version ever published by the Free Software Foundation.

10. If you wish to incorporate parts of the Program into other free programs whose distribution conditions are different, write to the author to ask for permission. For software which is copyrighted by the Free Software Foundation, write to the Free Software Foundation; we sometimes make exceptions for this. Our decision will be guided by the two goals of preserving the free status of all derivatives of our free software and of promoting the sharing and reuse of software generally.

NO WARRANTY

11. BECAUSE THE PROGRAM IS LICENSED FREE OF CHARGE, THERE IS NO WARRANTY FOR THE PROGRAM, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE PROGRAM "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE PROGRAM IS WITH YOU. SHOULD THE PROGRAM PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

12. IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY AND/OR REDISTRIBUTE THE PROGRAM AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE PROGRAM (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE PROGRAM TO OPERATE WITH ANY OTHER PROGRAMS), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

END OF TERMS AND CONDITIONS

1.97 login 1:4.5-1ubuntu2.5

1.97.1 Available under license :

NOTE:

This license has been obsoleted by the change to the BSD-style copyright. You may continue to use this license if you wish, but you are under no obligation to do so.

(*

This document is freely plagiarised from the 'Artistic Licence', distributed as part of the Perl v4.0 kit by Larry Wall, which is available from most major archive sites. I stole it from CrackLib.

\$Id\$

*)

This documents purpose is to state the conditions under which this Package (See definition below) viz: "Shadow", the Shadow Password Suite which is held by Julianne Frances Haugh, may be copied, such that the copyright holder maintains some semblance of artistic control over the development of the package, while giving the users of the package the right to use and distribute the Package in a more-or-less customary fashion, plus the right to make reasonable modifications.

So there.

Definitions:

A "Package" refers to the collection of files distributed by the Copyright Holder, and derivatives of that collection of files created through textual modification, or segments thereof.

"Standard Version" refers to such a Package if it has not been modified, or has been modified in accordance with the wishes of the Copyright Holder.

"Copyright Holder" is whoever is named in the copyright or copyrights for the package.

"You" is you, if you're thinking about copying or distributing this Package.

"Reasonable copying fee" is whatever you can justify on the basis of media cost, duplication charges, time of people involved, and so on. (You will not be required to justify it to the Copyright Holder, but only to the computing community at large as a market that must bear the

fee.)

"Freely Available" means that no fee is charged for the item itself, though there may be fees involved in handling the item. It also means that recipients of the item may redistribute it under the same conditions they received it.

1. You

may make and give away verbatim copies of the source form of the Standard Version of this Package without restriction, provided that you duplicate all of the original copyright notices and associated disclaimers.

2. You may apply bug fixes, portability fixes and other modifications derived from the Public Domain or from the Copyright Holder. A Package modified in such a way shall still be considered the Standard Version.

3. You may otherwise modify your copy of this Package in any way, provided that you insert a prominent notice in each changed file stating how and when AND WHY you changed that file, and provided that you do at least ONE of the following:

a) place your modifications in the Public Domain or otherwise make them Freely Available, such as by posting said modifications to Usenet or an equivalent medium, or placing the modifications on a major archive site such as uunet.uu.net, or by allowing the Copyright Holder to include your modifications in the Standard Version of the Package.

b) use the modified Package only within your corporation or organization.

c) rename any non-standard executables so the names do not conflict with standard executables, which must also be provided, and provide separate documentation for each non-standard executable that clearly documents how it differs from the Standard Version.

d) make other distribution arrangements with the Copyright Holder.

4. You may distribute the programs of this Package in object code or executable form, provided that you do at least ONE of the following:

a) distribute a Standard Version of the executables and library files, together with instructions (in the manual page or equivalent) on where to get the Standard Version.

b) accompany the distribution with the machine-readable source of the Package with your modifications.

c) accompany any non-standard executables with their corresponding Standard Version executables, giving the non-standard executables non-standard names, and clearly documenting the differences in manual pages (or equivalent), together with instructions on where to get the Standard Version.

d) make other distribution arrangements with the Copyright Holder.

5. You may charge a reasonable copying fee for any distribution of this Package. You may charge any fee you choose for support of this Package. YOU MAY NOT CHARGE A FEE FOR THIS PACKAGE ITSELF. However, you may distribute this Package in aggregate with other (possibly commercial) programs as part of a larger (possibly commercial) software distribution provided that YOU DO NOT ADVERTISE this package as a product of your own.

6. The name of the Copyright Holder may not be used to endorse or promote products derived from this software without specific prior written permission.

7. THIS PACKAGE IS PROVIDED "AS IS" AND WITHOUT ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, WITHOUT LIMITATION, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE.

The End

GNU GENERAL PUBLIC LICENSE

Version 2, June 1991

Copyright (C) 1989, 1991 Free Software Foundation, Inc.

675 Mass Ave, Cambridge, MA 02139, USA

Everyone is permitted to copy and distribute verbatim copies of this license document, but changing it is not allowed.

Preamble

The licenses for most software are designed to take away your freedom to share and change it. By contrast, the GNU General Public License is intended to guarantee your freedom to share and change free software--to make sure the software is free for all its users. This General Public License applies to most of the Free Software Foundation's software and to any other program whose authors commit to using it. (Some other Free Software Foundation software is covered by the GNU Library General Public License instead.) You can apply it to your programs, too.

When we speak of free software, we are referring to freedom, not

price. Our General Public Licenses are designed to make sure that you have the freedom to distribute copies of free software (and charge for this service if you wish), that you receive source code or can get it if you want it, that you can change the software or use pieces of it in new free programs; and that you know you can do these things.

To protect your rights, we need to make restrictions that forbid anyone to deny you these rights or to ask you to surrender the rights. These restrictions translate to certain responsibilities for you if you distribute copies of the software, or if you modify it.

For example, if you distribute copies of such a program, whether gratis or for a fee, you must give the recipients all the rights that you have. You must make sure that they, too, receive or can get the source code. And you must show them these terms so they know their rights.

We protect your rights with two steps: (1) copyright the software, and (2) offer you this license which gives you legal permission to copy, distribute and/or modify the software.

Also, for each author's protection and ours, we want to make certain that everyone understands that there is no warranty for this free software. If the software is modified by someone else and passed on, we want its recipients to know that what they have is not the original, so that any problems introduced by others will not reflect on the original authors' reputations.

Finally, any free program is threatened constantly by software patents. We wish to avoid the danger that redistributors of a free program will individually obtain patent licenses, in effect making the program proprietary. To prevent this, we have made it clear that any patent must be licensed for everyone's free use or not licensed at all.

The precise terms and conditions for copying, distribution and modification follow.

GNU GENERAL PUBLIC LICENSE TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

0. This License applies to any program or other work which contains a notice placed by the copyright holder saying it may be distributed under the terms of this General Public License. The "Program", below, refers to any such program or work, and a "work based on the Program" means either the Program or any derivative work under copyright law:

that is to say, a work containing the Program or a portion of it, either verbatim or with modifications and/or translated into another language. (Hereinafter, translation is included without limitation in the term "modification".) Each licensee is addressed as "you".

Activities other than copying, distribution and modification are not covered by this License; they are outside its scope. The act of running the Program is not restricted, and the output from the Program is covered only if its contents constitute a work based on the Program (independent of having been made by running the Program). Whether that is true depends on what the Program does.

1. You may copy and distribute verbatim copies of the Program's source code as you receive it, in any medium, provided that you conspicuously and appropriately publish on each copy an appropriate copyright notice and disclaimer of warranty; keep intact all the notices that refer to this License and to the absence of any warranty; and give any other recipients of the Program a copy of this License along with the Program.

You may charge a fee for the physical act of transferring a copy, and you may at your option offer warranty protection in exchange for a fee.

2. You may modify your copy or copies of the Program or any portion of it, thus forming a work based on the Program, and copy and distribute such modifications or work under the terms of Section 1 above, provided that you also meet all of these conditions:

a) You must cause the modified files to carry prominent notices stating that you changed the files and the date of any change.

b) You must cause any work that you distribute or publish, that in whole or in part contains or is derived from the Program or any part thereof, to be licensed as a whole at no charge to all third parties under the terms of this License.

c) If the modified program normally reads commands interactively when run, you must cause it, when started running for such interactive use in the most ordinary way, to print or display an announcement including an appropriate copyright notice and a notice that there is no warranty (or else, saying that you provide a warranty) and that users may redistribute the program under these conditions, and telling the user how to view a copy of this License. (Exception: if the Program itself is interactive but does not normally print such an announcement, your work based on the Program is not required to print an announcement.)

These requirements apply to the modified work as a whole. If identifiable sections of that work are not derived from the Program, and can be reasonably considered independent and separate works in themselves, then this License, and its terms, do not apply to those sections when you distribute them as separate works. But when you distribute the same sections as part of a whole which is a work based on the Program, the distribution of the whole must be on the terms of this License, whose permissions for other licensees extend to the entire whole, and thus to each and every part regardless of who wrote it.

Thus, it is not the intent of this section to claim rights or contest your rights to work written entirely by you; rather, the intent is to exercise the right to control the distribution of derivative or collective works based on the Program.

In addition, mere aggregation of another work not based on the Program with the Program (or with a work based on the Program) on a volume of a storage or distribution medium does not bring the other work under the scope of this License.

3. You may copy and distribute the Program (or a work based on it, under Section 2) in object code or executable form under the terms of Sections 1 and 2 above provided that you also do one of the following:

- a) Accompany it with the complete corresponding machine-readable source code, which must be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange; or,
- b) Accompany it with a written offer, valid for at least three years, to give any third party, for a charge no more than your cost of physically performing source distribution, a complete machine-readable copy of the corresponding source code, to be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange; or,
- c) Accompany it with the information you received as to the offer to distribute corresponding source code. (This alternative is allowed only for noncommercial distribution and only if you received the program in object code or executable form with such an offer, in accord with Subsection b above.)

The source code for a work means the preferred form of the work for making modifications to it. For an executable work, complete source code means all the source code for all modules it contains, plus any

associated interface definition files, plus the scripts used to control compilation and installation of the executable. However, as a special exception, the source code distributed need not include anything that is normally distributed (in either source or binary form) with the major components (compiler, kernel, and so on) of the operating system on which the executable runs, unless that component itself accompanies the executable.

If distribution of executable or object code is made by offering access to copy from a designated place, then offering equivalent access to copy the source code from the same place counts as distribution of the source code, even though third parties are not compelled to copy the source along with the object code.

4. You may not copy, modify, sublicense, or distribute the Program except as expressly provided under this License. Any attempt otherwise to copy, modify, sublicense or distribute the Program is void, and will automatically terminate your rights under this License. However, parties who have received copies, or rights, from you under this License will not have their licenses terminated so long as such parties remain in full compliance.

5. You are not required to accept this License, since you have not signed it. However, nothing else grants you permission to modify or distribute the Program or its derivative works. These actions are prohibited by law if you do not accept this License. Therefore, by modifying or distributing the Program (or any work based on the Program), you indicate your acceptance of this License to do so, and all its terms and conditions for copying, distributing or modifying the Program or works based on it.

6.

Each time you redistribute the Program (or any work based on the Program), the recipient automatically receives a license from the original licensor to copy, distribute or modify the Program subject to these terms and conditions. You may not impose any further restrictions on the recipients' exercise of the rights granted herein. You are not responsible for enforcing compliance by third parties to this License.

7. If, as a consequence of a court judgment or allegation of patent infringement or for any other reason (not limited to patent issues), conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot distribute so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you

may not distribute the Program at all. For example, if a patent license would not permit royalty-free redistribution of the Program by all those who receive copies directly or indirectly through you, then the only way you could satisfy both it and this License would be to refrain entirely from distribution of the Program.

If any portion of this section is held invalid or unenforceable under any particular circumstance, the balance of the section is intended to apply and the section as a whole is intended to apply in other circumstances.

It is not the purpose of this section to induce you to infringe any patents or other property right claims or to contest validity of any such claims; this section has the sole purpose of protecting the integrity of the free software distribution system, which is implemented by public license practices. Many people have made generous contributions to the wide range of software distributed through that system in reliance on consistent application of that system; it is up to the author/donor to decide if he or she is willing to distribute software through any other system and a licensee cannot impose that choice.

This section is intended to make thoroughly clear what is believed to be a consequence of the rest of this License.

8. If the distribution and/or use of the Program is restricted in certain countries either by patents or by copyrighted interfaces, the original copyright holder who places the Program under this License may add an explicit geographical distribution limitation excluding those countries, so that distribution is permitted only in or among countries not thus excluded. In such case, this License incorporates the limitation as if written in the body of this License.

9. The Free Software Foundation may publish revised and/or new versions of the General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Program specifies a version number of this License which applies to it and "any later version", you have the option of following the terms and conditions either of that version or of any later version published by the Free Software Foundation. If the Program does not specify a version number of this License, you may choose any version ever published by the Free Software Foundation.

10. If you wish to incorporate parts of the Program into other free programs whose distribution conditions are different, write to the author to ask for permission. For software which is copyrighted by the Free Software Foundation, write to the Free Software Foundation; we sometimes make exceptions for this. Our decision will be guided by the two goals of preserving the free status of all derivatives of our free software and of promoting the sharing and reuse of software generally.

NO WARRANTY

11. BECAUSE THE PROGRAM IS LICENSED FREE OF CHARGE, THERE IS NO WARRANTY FOR THE PROGRAM, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE PROGRAM "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE PROGRAM IS WITH YOU. SHOULD THE PROGRAM PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

12. IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY AND/OR REDISTRIBUTE THE PROGRAM AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE PROGRAM (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE PROGRAM TO OPERATE WITH ANY OTHER PROGRAMS), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

END OF TERMS AND CONDITIONS

1.98 passwd 1:4.5-1ubuntu2.5

1.98.1 Available under license :

NOTE:

This license has been obsoleted by the change to the BSD-style copyright. You may continue to use this license if you wish, but you are under no obligation to do so.

(*

This document is freely plagiarised from the 'Artistic Licence', distributed as part of the Perl v4.0 kit by Larry Wall, which is available from most major archive sites. I stole it from CrackLib.

\$Id\$

*)

This documents purpose is to state the conditions under which this Package (See definition below) viz: "Shadow", the Shadow Password Suite which is held by Julianne Frances Haugh, may be copied, such that the copyright holder maintains some semblance of artistic control over the development of the package, while giving the users of the package the right to use and distribute the Package in a more-or-less customary fashion, plus the right to make reasonable modifications.

So there.

Definitions:

A "Package" refers to the collection of files distributed by the Copyright Holder, and derivatives of that collection of files created through textual modification, or segments thereof.

"Standard Version" refers to such a Package if it has not been modified, or has been modified in accordance with the wishes of the Copyright Holder.

"Copyright Holder" is whoever is named in the copyright or copyrights for the package.

"You" is you, if you're thinking about copying or distributing this Package.

"Reasonable copying fee" is whatever you can justify on the basis of media cost, duplication charges, time of people involved, and so on. (You will not be required to justify it to the Copyright Holder, but only to the computing community at large as a market that must bear the fee.)

"Freely Available" means that no fee is charged for the item itself, though there may be fees involved in handling the item. It also means that recipients of the item may redistribute it under the same conditions they received it.

1. You

may make and give away verbatim copies of the source form of the Standard Version of this Package without restriction, provided that you duplicate all of the original copyright notices and associated disclaimers.

2. You may apply bug fixes, portability fixes and other modifications derived from the Public Domain or from the Copyright Holder. A Package modified in such a way shall still be considered the Standard Version.

3. You may otherwise modify your copy of this Package in any way, provided that you insert a prominent notice in each changed file stating how and when AND WHY you changed that file, and provided that you do at least ONE of the following:

a) place your modifications in the Public Domain or otherwise make them Freely Available, such as by posting said modifications to Usenet or an equivalent medium, or placing the modifications on a major archive site such as uunet.uu.net, or by allowing the Copyright Holder to include your modifications in the Standard Version of the Package.

b) use the modified Package only within your corporation or organization.

c) rename any non-standard executables so the names do not conflict with standard executables, which must also be provided, and provide separate documentation for each non-standard executable that clearly documents how it differs from the Standard Version.

d) make other distribution arrangements with the Copyright Holder.

4. You may distribute the programs of this Package in object code or executable form, provided that you do at least ONE of the following:

a) distribute a Standard Version of the executables and library files, together with instructions (in the manual page or equivalent) on where to get the Standard Version.

b) accompany the distribution with the machine-readable source of the Package with your modifications.

c) accompany any non-standard executables with their corresponding Standard Version executables, giving the non-standard executables non-standard names, and clearly documenting the differences in manual pages (or equivalent), together with instructions on where to get the Standard Version.

d) make other distribution arrangements with the Copyright Holder.

5. You may charge a reasonable copying fee for any distribution of this Package. You may charge any fee you choose for support of this Package. **YOU MAY NOT CHARGE A FEE FOR THIS PACKAGE ITSELF.** However, you may distribute this Package in aggregate with other (possibly commercial) programs as part of a larger (possibly commercial) software distribution provided that **YOU DO NOT ADVERTISE** this package as a product of your own.
6. The name of the Copyright Holder may not be used to endorse or promote products derived from this software without specific prior written permission.
7. **THIS PACKAGE IS PROVIDED "AS IS" AND WITHOUT ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, WITHOUT LIMITATION, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE.**

The End

GNU GENERAL PUBLIC LICENSE

Version 2, June 1991

Copyright (C) 1989, 1991 Free Software Foundation, Inc.

675 Mass Ave, Cambridge, MA 02139, USA

Everyone is permitted to copy and distribute verbatim copies of this license document, but changing it is not allowed.

Preamble

The licenses for most software are designed to take away your freedom to share and change it. By contrast, the GNU General Public License is intended to guarantee your freedom to share and change free software--to make sure the software is free for all its users. This General Public License applies to most of the Free Software Foundation's software and to any other program whose authors commit to using it. (Some other Free Software Foundation software is covered by the GNU Library General Public License instead.) You can apply it to your programs, too.

When we speak of free software, we are referring to freedom, not price. Our General Public Licenses are designed to make sure that you have the freedom to distribute copies of free software (and charge for this service if you wish), that you receive source code or can get it if you want it, that you can change the software or use pieces of it in new free programs; and that you know you can do these things.

To protect your rights, we need to make restrictions that forbid anyone to deny you these rights or to ask you to surrender the rights.

These restrictions translate to certain responsibilities for you if you distribute copies of the software, or if you modify it.

For example, if you distribute copies of such a program, whether gratis or for a fee, you must give the recipients all the rights that you have. You must make sure that they, too, receive or can get the source code. And you must show them these terms so they know their rights.

We protect your rights with two steps: (1) copyright the software, and (2) offer you this license which gives you legal permission to copy, distribute and/or modify the software.

Also, for each author's protection and ours, we want to make certain that everyone understands that there is no warranty for this free software. If the software is modified by someone else and passed on, we want its recipients to know that what they have is not the original, so that any problems introduced by others will not reflect on the original authors' reputations.

Finally, any free program is threatened constantly by software patents. We wish to avoid the danger that redistributors of a free program will individually obtain patent licenses, in effect making the program proprietary. To prevent this, we have made it clear that any patent must be licensed for everyone's free use or not licensed at all.

The precise terms and conditions for copying, distribution and modification follow.

GNU GENERAL PUBLIC LICENSE TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

0. This License applies to any program or other work which contains a notice placed by the copyright holder saying it may be distributed under the terms of this General Public License. The "Program", below, refers to any such program or work, and a "work based on the Program" means either the Program or any derivative work under copyright law: that is to say, a work containing the Program or a portion of it, either verbatim or with modifications and/or translated into another language. (Hereinafter, translation is included without limitation in the term "modification".) Each licensee is addressed as "you".

Activities other than copying, distribution and modification are not covered by this License; they are outside its scope. The act of running the Program is not restricted, and the output from the Program is covered only if its contents constitute a work based on the

Program (independent of having been made by running the Program). Whether that is true depends on what the Program does.

1. You may copy and distribute verbatim copies of the Program's source code as you receive it, in any medium, provided that you conspicuously and appropriately publish on each copy an appropriate copyright notice and disclaimer of warranty; keep intact all the notices that refer to this License and to the absence of any warranty; and give any other recipients of the Program a copy of this License along with the Program.

You may charge a fee for the physical act of transferring a copy, and you may at your option offer warranty protection in exchange for a fee.

2. You may modify your copy or copies of the Program or any portion of it, thus forming a work based on the Program, and copy and distribute such modifications or work under the terms of Section 1 above, provided that you also meet all of these conditions:

a) You must cause the modified files to carry prominent notices stating that you changed the files and the date of any change.

b) You must cause any work that you distribute or publish, that in whole or in part contains or is derived from the Program or any part thereof, to be licensed as a whole at no charge to all third parties under the terms of this License.

c) If the modified program normally reads commands interactively when run, you must cause it, when started running for such interactive use in the most ordinary way, to print or display an announcement including an appropriate copyright notice and a notice that there is no warranty (or else, saying that you provide a warranty) and that users may redistribute the program under these conditions, and telling the user how to view a copy of this License. (Exception: if the Program itself is interactive but does not normally print such an announcement, your work based on the Program is not required to print an announcement.)

These requirements apply to the modified work as a whole. If identifiable sections of that work are not derived from the Program, and can be reasonably considered independent and separate works in themselves, then this License, and its terms, do not apply to those sections when you distribute them as separate works. But when you distribute the same sections as part of a whole which is a work based on the Program, the distribution of the whole must be on the terms of

this License, whose permissions for other licensees extend to the entire whole, and thus to each and every part regardless of who wrote it.

Thus, it is not the intent of this section to claim rights or contest your rights to work written entirely by you; rather, the intent is to exercise the right to control the distribution of derivative or collective works based on the Program.

In addition, mere aggregation of another work not based on the Program with the Program (or with a work based on the Program) on a volume of a storage or distribution medium does not bring the other work under the scope of this License.

3. You may copy and distribute the Program (or a work based on it, under Section 2) in object code or executable form under the terms of Sections 1 and 2 above provided that you also do one of the following:

a) Accompany it with the complete corresponding machine-readable source code, which must be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange; or,

b) Accompany it with a written offer, valid for at least three years, to give any third party, for a charge no more than your cost of physically performing source distribution, a complete machine-readable copy of the corresponding source code, to be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange; or,

c) Accompany it with the information you received as to the offer to distribute corresponding source code. (This alternative is allowed only for noncommercial distribution and only if you received the program in object code or executable form with such an offer, in accord with Subsection b above.)

The source code for a work means the preferred form of the work for making modifications to it. For an executable work, complete source code means all the source code for all modules it contains, plus any associated interface definition files, plus the scripts used to control compilation and installation of the executable. However, as a special exception, the source code distributed need not include anything that is normally distributed (in either source or binary form) with the major components (compiler, kernel, and so on) of the operating system on which the executable runs, unless that component itself accompanies the executable.

If distribution of executable or object code is made by offering

access to copy from a designated place, then offering equivalent access to copy the source code from the same place counts as distribution of the source code, even though third parties are not compelled to copy the source along with the object code.

4. You may not copy, modify, sublicense, or distribute the Program except as expressly provided under this License. Any attempt otherwise to copy, modify, sublicense or distribute the Program is void, and will automatically terminate your rights under this License. However, parties who have received copies, or rights, from you under this License will not have their licenses terminated so long as such parties remain in full compliance.

5. You are not required to accept this License, since you have not signed it. However, nothing else grants you permission to modify or distribute the Program or its derivative works. These actions are prohibited by law if you do not accept this License. Therefore, by modifying or distributing the Program (or any work based on the Program), you indicate your acceptance of this License to do so, and all its terms and conditions for copying, distributing or modifying the Program or works based on it.

6.

Each time you redistribute the Program (or any work based on the Program), the recipient automatically receives a license from the original licensor to copy, distribute or modify the Program subject to these terms and conditions. You may not impose any further restrictions on the recipients' exercise of the rights granted herein. You are not responsible for enforcing compliance by third parties to this License.

7. If, as a consequence of a court judgment or allegation of patent infringement or for any other reason (not limited to patent issues), conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot distribute so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not distribute the Program at all. For example, if a patent license would not permit royalty-free redistribution of the Program by all those who receive copies directly or indirectly through you, then the only way you could satisfy both it and this License would be to refrain entirely from distribution of the Program.

If any portion of this section is held invalid or unenforceable under any particular circumstance, the balance of the section is intended to

apply and the section as a whole is intended to apply in other circumstances.

It is not the purpose of this section to induce you to infringe any patents or other property right claims or to contest validity of any such claims; this section has the sole purpose of protecting the integrity of the free software distribution system, which is implemented by public license practices. Many people have made generous contributions to the wide range of software distributed through that system in reliance on consistent application of that system; it is up to the author/donor to decide if he or she is willing to distribute software through any other system and a licensee cannot impose that choice.

This section is intended to make thoroughly clear what is believed to be a consequence of the rest of this License.

8. If the distribution and/or use of the Program is restricted in certain countries either by patents or by copyrighted interfaces, the original copyright holder who places the Program under this License may add an explicit geographical distribution limitation excluding those countries, so that distribution is permitted only in or among countries not thus excluded. In such case, this License incorporates the limitation as if written in the body of this License.

9. The Free Software Foundation may publish revised and/or new versions of the General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Program specifies a version number of this License which applies to it and "any later version", you have the option of following the terms and conditions either of that version or of any later version published by the Free Software Foundation. If the Program does not specify a version number of this License, you may choose any version ever published by the Free Software Foundation.

10. If you wish to incorporate parts of the Program into other free programs whose distribution conditions are different, write to the author to ask for permission. For software which is copyrighted by the Free Software Foundation, write to the Free Software Foundation; we sometimes make exceptions for this. Our decision will be guided by the two goals of preserving the free status of all derivatives of our free software and of promoting the sharing and reuse of software generally.

NO WARRANTY

11. BECAUSE THE PROGRAM IS LICENSED FREE OF CHARGE, THERE IS NO WARRANTY FOR THE PROGRAM, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE PROGRAM "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE PROGRAM IS WITH YOU. SHOULD THE PROGRAM PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

12. IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY AND/OR REDISTRIBUTE THE PROGRAM AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE PROGRAM (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE PROGRAM TO OPERATE WITH ANY OTHER PROGRAMS), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

END OF TERMS AND CONDITIONS

1.99 ca-certificates 20211016ubuntu0.18.04.1

1.99.1 Available under license :

Format: <http://www.debian.org/doc/packaging-manuals/copyright-format/1.0/>

Files: *

Copyright: 2013 System Administrator <root@localhost.localdomain>

License: ...

Format: <https://www.debian.org/doc/packaging-manuals/copyright-format/1.0/>

Source: <http://ftp.debian.org/debian/pool/main/c/ca-certificates/>

Files: debian/*

examples/*

Makefile

mozilla/*

sbin/*

Copyright: 2003 Fumitoshi UKAI <ukai@debian.or.jp>

2009 Philipp Kern <pkern@debian.org>

2011 Michael Shuler <michael@pbandjelly.org>

Various Debian Contributors

License: GPL-2+

This program is free software; you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation; either version 2 of the License, or (at your option) any later version.

This program is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details.

You should have received a copy of the GNU General Public License along with this program; if not, write to the Free Software Foundation, Inc., 51 Franklin St, Fifth Floor, Boston, MA 02110-1301, USA.

On Debian GNU/Linux systems, the complete text of the GNU General Public License can be found in '/usr/share/common-licenses/GPL-2'.

Files: mozilla/certdata.txt
mozilla/nssckbi.h

Copyright: Mozilla Contributors

Comment: Original Copyright: 1994-2000 Netscape Communications Corporation
(certdata.txt <= CVS Revision: 1.82)

NSS no longer contains explicit copyright. Upstream indicates that "Mozilla Contributors" is an appropriate attribution for the required Copyright: field in Debian's machine-readable format.
https://bugzilla.mozilla.org/show_bug.cgi?id=850003

License: MPL-2.0

Mozilla Public License Version 2.0

=====

1. Definitions

1.1. "Contributor"

means each individual or legal entity that creates, contributes to the creation of, or owns Covered Software.

1.2. "Contributor Version"

means the combination of the Contributions of others (if any) used by a Contributor and that particular Contributor's Contribution.

1.3. "Contribution"

means Covered Software of a particular Contributor.

1.4. "Covered Software"

means Source Code Form to which the initial Contributor has attached the notice in Exhibit A, the Executable Form of such Source Code Form, and Modifications of such Source Code Form, in each case including portions thereof.

1.5. "Incompatible With Secondary Licenses"

means

(a) that the initial Contributor has attached the notice described in Exhibit B to the Covered Software; or

(b) that the Covered Software was made available under the terms of version 1.1 or earlier of the License, but not also under the terms of a Secondary License.

1.6. "Executable Form"

means any form of the work other than Source Code Form.

1.7. "Larger Work"

means a work that combines Covered Software with other material, in a separate file or files, that is not Covered Software.

1.8. "License"

means this document.

1.9. "Licensable"

means having the right to grant, to the maximum extent possible, whether at the time of the initial grant or subsequently, any and all of the rights conveyed by this License.

1.10. "Modifications"

means any of the following:

(a) any file in Source Code Form that results from an addition to, deletion from, or modification of the contents of Covered Software; or

(b) any new file in Source Code Form that contains any Covered Software.

1.11. "Patent Claims" of a Contributor

means any patent claim(s), including without limitation, method, process, and apparatus claims, in any patent Licensable by such Contributor that would be infringed, but for the grant of the License, by the making, using, selling, offering for sale, having made, import, or transfer of either its Contributions or its Contributor Version.

.
1.12. "Secondary License"

means either the GNU General Public License, Version 2.0, the GNU Lesser General Public License, Version 2.1, the GNU Affero General Public License, Version 3.0, or any later versions of those licenses.

.
1.13. "Source Code Form"

means the form of the work preferred for making modifications.

.
1.14. "You" (or "Your")

means an individual or a legal entity exercising rights under this License. For legal entities, "You" includes any entity that controls, is controlled by, or is under common control with You. For purposes of this definition, "control" means (a) the power, direct or indirect, to cause the direction or management of such entity, whether by contract or otherwise, or (b) ownership of more than fifty percent (50%) of the outstanding shares or beneficial ownership of such entity.

.
2. License Grants and Conditions

.
2.1. Grants

.
Each Contributor hereby grants You a world-wide, royalty-free, non-exclusive license:

- .
(a) under intellectual property rights (other than patent or trademark) Licensable by such Contributor to use, reproduce, make available, modify, display, perform, distribute, and otherwise exploit its Contributions, either on an unmodified basis, with Modifications, or as part of a Larger Work; and
. (b) under Patent Claims of such Contributor to make, use, sell, offer for sale, have made, import, and otherwise transfer either its Contributions or its Contributor Version.

.
2.2. Effective Date

.
The licenses granted in Section 2.1 with respect to any Contribution become effective for each Contribution on the date the Contributor first distributes such Contribution.

.
2.3. Limitations on Grant Scope

.
The licenses granted in this Section 2 are the only

rights granted under this License. No additional rights or licenses will be implied from the distribution or licensing of Covered Software under this License. Notwithstanding Section 2.1(b) above, no patent license is granted by a Contributor:

- .
(a) for any code that a Contributor has removed from Covered Software;
or
- .
(b) for infringements caused by: (i) Your and any other third party's modifications of Covered Software, or (ii) the combination of its Contributions with other software (except as part of its Contributor Version); or
- .
(c) under Patent Claims infringed by Covered Software in the absence of its Contributions.

.
This License does not grant any rights in the trademarks, service marks, or logos of any Contributor (except as may be necessary to comply with the notice requirements in Section 3.4).

. 2.4. Subsequent Licenses

.
No Contributor makes additional grants as a result of Your choice to distribute the Covered Software under a subsequent version of this License (see Section 10.2) or under the terms of a Secondary License (if permitted under the terms of Section 3.3).

. 2.5. Representation

.
Each Contributor represents that the Contributor believes its Contributions are its original creation(s) or it has sufficient rights to grant the rights to its Contributions conveyed by this License.

. 2.6. Fair Use

.
This License is not intended to limit any rights You have under applicable copyright doctrines of fair use, fair dealing, or other equivalents.

. 2.7. Conditions

.
Sections 3.1, 3.2, 3.3, and 3.4 are conditions of the licenses granted in Section 2.1.

. 3. Responsibilities

.

3.1. Distribution of Source Form

.

All distribution of Covered Software in Source Code Form, including any Modifications that You create or to which You contribute, must be under the terms of this License. You must inform recipients that the Source Code Form of the Covered Software is governed by the terms of this License, and how they can obtain a copy of this License. You may not attempt to alter or restrict the recipients' rights in the Source Code Form.

.

3.2. Distribution of Executable Form

.

If You distribute Covered Software in Executable Form then:

- .
- (a) such Covered Software must also be made available in Source Code Form, as described in Section 3.1, and You must inform recipients of the Executable Form how they can obtain a copy of such Source Code Form by reasonable means in a timely manner, at a charge no more than the cost of distribution to the recipient; and
 - (b) You may distribute such Executable Form under the terms of this License, or sublicense it under different terms, provided that the license for the Executable Form does not attempt to limit or alter the recipients' rights in the Source Code Form under this License.

.

3.3. Distribution of a Larger Work

.

You may create and distribute a Larger Work under terms of Your choice, provided that You also comply with the requirements of this License for the Covered Software. If the Larger Work is a combination of Covered Software with a work governed by one or more Secondary Licenses, and the Covered Software is not Incompatible With Secondary Licenses, this License permits You to additionally distribute such Covered Software under the terms of such Secondary License(s), so that the recipient of the Larger Work may, at their option, further distribute the Covered Software under the terms of either this License or such Secondary License(s).

.

3.4. Notices

.

You may not remove or alter the substance of any license notices (including copyright notices, patent notices, disclaimers of warranty, or limitations of liability) contained within the Source Code Form of the Covered Software, except that You may alter any license notices to the extent required to remedy known factual inaccuracies.

.
3.5. Application of Additional
Terms

.
You may choose to offer, and to charge a fee for, warranty, support, indemnity or liability obligations to one or more recipients of Covered Software. However, You may do so only on Your own behalf, and not on behalf of any Contributor. You must make it absolutely clear that any such warranty, support, indemnity, or liability obligation is offered by You alone, and You hereby agree to indemnify every Contributor for any liability incurred by such Contributor as a result of warranty, support, indemnity or liability terms You offer. You may include additional disclaimers of warranty and limitations of liability specific to any jurisdiction.

.
4. Inability to Comply Due to Statute or Regulation

.
If it is impossible for You to comply with any of the terms of this License with respect to some or all of the Covered Software due to statute, judicial order, or regulation then You must: (a) comply with the terms of this License to the maximum extent possible; and (b) describe the limitations and the code they affect. Such description must be placed in a text file included with all distributions of the Covered Software under this License. Except to the extent prohibited by statute or regulation, such description must be sufficiently detailed for a recipient of ordinary skill to be able to understand it.

.
5. Termination

.
5.1. The rights granted under this License will terminate automatically if You fail to comply with any of its terms. However, if You become compliant, then the rights granted under this License from a particular Contributor are reinstated (a) provisionally, unless and until such Contributor explicitly and finally terminates Your grants, and (b) on an ongoing basis, if such Contributor fails to notify You of the non-compliance by some reasonable means prior to 60 days after You have come back into compliance. Moreover, Your grants from a particular Contributor are reinstated on an ongoing basis if such Contributor notifies You of the non-compliance by some reasonable means, this is the first time You have received notice of non-compliance with this License from such Contributor, and You become compliant prior to 30 days after Your receipt of the notice.

.
5.2. If You initiate litigation against any entity by asserting a patent infringement claim (excluding declaratory judgment actions,

counter-claims, and cross-claims) alleging that a Contributor Version directly or indirectly infringes any patent, then the rights granted to You by any and all Contributors for the Covered Software under Section 2.1 of this License shall terminate.

5.3. In the event of termination under Sections 5.1 or 5.2 above, all end user license agreements (excluding distributors and resellers) which have been validly granted by You or Your distributors under this License prior to termination shall survive termination.

* *
* 6. Disclaimer of Warranty *
* ----- *
* *
* Covered Software is provided under this License on an "as is" *
* basis, without warranty of any kind, either expressed, implied, or *
* statutory, including, without limitation, warranties that the *
* Covered Software is free of defects, merchantable, fit for a *
* particular purpose or non-infringing. The entire risk as to the *
* quality and performance of the Covered Software is with You. *
* Should any Covered Software prove defective in any respect, You *
* (not any Contributor) assume the cost of any necessary servicing, *
* repair, or correction. This disclaimer of warranty *
constitutes an *
* essential part of this License. No use of any Covered Software is *
* authorized under this License except under this disclaimer. *

* *
* 7. Limitation of Liability *
* ----- *
* *
* Under no circumstances and under no legal theory, whether tort *
* (including negligence), contract, or otherwise, shall any *
* Contributor, or anyone who distributes Covered Software as *
* permitted above, be liable to You for any direct, indirect, *
* special, incidental, *
or consequential damages of any character *
* including, without limitation, damages for lost profits, loss of *
* goodwill, work stoppage, computer failure or malfunction, or any *
* and all other commercial damages or losses, even if such party *
* shall have been informed of the possibility of such damages. This *
* limitation of liability shall not apply to liability for death or *
* personal injury resulting from such party's negligence to the *
* extent applicable law prohibits such limitation. Some *

* jurisdictions do not allow the exclusion or limitation of *
* incidental or consequential damages, so this exclusion and *
* limitation may not apply to You. *
* *

.
8. Litigation

.
Any litigation relating to this License may be brought only in the courts of a jurisdiction where the defendant maintains its principal place of business and such litigation shall be governed by laws of that jurisdiction, without reference to its conflict-of-law provisions. Nothing in this Section shall prevent a party's ability to bring cross-claims or counter-claims.

.
9. Miscellaneous

.
This License represents the complete agreement concerning the subject matter hereof. If any provision of this License is held to be unenforceable, such provision shall be reformed only to the extent necessary to make it enforceable. Any law or regulation which provides that the language of a contract shall be construed against the drafter shall not be used to construe this License against a Contributor.

.
10. Versions of the License

.
10.1. New Versions
.

Mozilla Foundation is the license steward. Except as provided in Section 10.3, no one other than the license steward has the right to modify or publish new versions of this License. Each version will be given a distinguishing version number.

.
10.2. Effect of New Versions
.

You may distribute the Covered Software under the terms of the version of the License under which You originally received the Covered Software, or under the terms of any subsequent version published by the license steward.

.
10.3. Modified Versions
.

If you create software not governed by this License, and you want to

create a new license for such software, you may create and use a modified version of this License if you rename the license and remove any references to the name of the license steward (except to note that such modified license differs from this License).

10.4. Distributing Source Code Form that is Incompatible With Secondary Licenses

If You choose to distribute Source Code Form that is Incompatible With Secondary Licenses under the terms of this version of the License, the notice described in Exhibit B of this License must be attached.

Exhibit A - Source Code Form License Notice

This Source Code Form is subject to the terms of the Mozilla Public License, v. 2.0. If a copy of the MPL was not distributed with this file, You can obtain one at <http://mozilla.org/MPL/2.0/>.

If it is not possible or desirable to put the notice in a particular file, then You may include the notice in a location (such as a LICENSE file in a relevant directory) where a recipient would be likely to look for such a notice.

You may add additional accurate notices of copyright ownership.

Exhibit B - "Incompatible With Secondary Licenses" Notice

This Source Code Form is "Incompatible With Secondary Licenses", as defined by the Mozilla Public License, v. 2.0.

1.100 sudo 1.8.21p2-3ubuntu1.5

1.100.1 Available under license :

Sudo is distributed under the following license:

Copyright (c) 1994-1996, 1998-2017

Todd C. Miller <Todd.Miller@courtesan.com>

Permission to use, copy, modify, and distribute this software for any purpose with or without fee is hereby granted, provided that the above copyright notice and this permission notice appear in all copies.

THE SOFTWARE IS PROVIDED "AS IS" AND THE AUTHOR DISCLAIMS ALL WARRANTIES WITH REGARD TO THIS SOFTWARE INCLUDING ALL IMPLIED WARRANTIES OF

MERCHANTABILITY AND FITNESS. IN NO EVENT SHALL THE AUTHOR BE LIABLE FOR ANY SPECIAL, DIRECT, INDIRECT, OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES WHATSOEVER RESULTING FROM LOSS OF USE, DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE OR OTHER TORTIOUS ACTION, ARISING OUT OF OR IN CONNECTION WITH THE USE OR PERFORMANCE OF THIS SOFTWARE.

Sponsored in part by the Defense Advanced Research Projects Agency (DARPA) and Air Force Research Laboratory, Air Force Materiel Command, USAF, under agreement number F39502-99-1-0512.

The file redblack.c bears the following license:

Copyright (c) 2001 Emin Martinian

Redistribution and use in source and binary forms, with or without modification, are permitted provided that neither the name of Emin Martinian nor the names of any contributors are be used to endorse or promote products derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

The file reallocarray.c bears the following license:

Copyright (c) 2008 Otto Moerbeek <otto@drijf.net>

Permission to use, copy, modify, and distribute this software for any purpose with or without fee is hereby granted, provided that the above copyright notice and this permission notice appear in all copies.

THE SOFTWARE IS PROVIDED "AS IS" AND THE AUTHOR DISCLAIMS ALL WARRANTIES WITH REGARD TO THIS SOFTWARE INCLUDING ALL IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS. IN NO EVENT SHALL THE AUTHOR BE LIABLE FOR ANY SPECIAL, DIRECT, INDIRECT, OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES WHATSOEVER RESULTING FROM LOSS OF USE, DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE OR OTHER TORTIOUS ACTION,

ARISING OUT OF
OR IN CONNECTION WITH THE USE OR PERFORMANCE OF THIS SOFTWARE.

The files getcwd.c, glob.c, glob.h, snprintf.c and sudo_queue.h bear the following license:

Copyright (c) 1989, 1990, 1991, 1993

The Regents of the University of California. All rights reserved.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

1. Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.
2. Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.
3. Neither the name of the University nor the names of its contributors may be used to endorse or promote products derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE REGENTS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE REGENTS OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

The file fnmatch.c bears the following license:

Copyright (c) 2011, VMware, Inc.

All rights reserved.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

- * Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.
- * Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.
- * Neither the name of the VMware, Inc. nor the names of its contributors may be used to endorse or promote products derived from this software

without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL VMWARE, INC. OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

The file `getopt_long.c` bears the following license:

```
/*-
 * Copyright (c) 2000 The NetBSD Foundation, Inc.
 * All rights reserved.
 *
 * This code is derived from software contributed to The NetBSD Foundation
 * by Dieter Baron and Thomas Klausner.
 *
 * Redistribution and use in source and binary forms, with or without
 * modification, are permitted provided that the following conditions
 * are met:
 * 1. Redistributions of source code must retain the above copyright
 *    notice, this list of conditions and the following disclaimer.
 * 2. Redistributions in binary form must reproduce
 *    the above copyright
 *    notice, this list of conditions and the following disclaimer in the
 *    documentation and/or other materials provided with the distribution.
 *
 * THIS SOFTWARE IS PROVIDED BY THE NETBSD FOUNDATION, INC. AND CONTRIBUTORS
 * ``AS IS'' AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED
 * TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR
 * PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE FOUNDATION OR CONTRIBUTORS
 * BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR
 * CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF
 * SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS
 * INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN
 * CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE)
 * ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE
 * POSSIBILITY OF SUCH DAMAGE.
 */
```

The file `inet_pton.c` bears the

following license:

```
/* Copyright (c) 1996 by Internet Software Consortium.
*
* Permission to use, copy, modify, and distribute this software for any
* purpose with or without fee is hereby granted, provided that the above
* copyright notice and this permission notice appear in all copies.
*
* THE SOFTWARE IS PROVIDED "AS IS" AND INTERNET SOFTWARE CONSORTIUM DISCLAIMS
* ALL WARRANTIES WITH REGARD TO THIS SOFTWARE INCLUDING ALL IMPLIED WARRANTIES
* OF MERCHANTABILITY AND FITNESS. IN NO EVENT SHALL INTERNET SOFTWARE
* CONSORTIUM BE LIABLE FOR ANY SPECIAL, DIRECT, INDIRECT, OR CONSEQUENTIAL
* DAMAGES OR ANY DAMAGES WHATSOEVER RESULTING FROM LOSS OF USE, DATA OR
* PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE OR OTHER TORTIOUS
* ACTION, ARISING OUT OF OR IN CONNECTION WITH THE USE OR PERFORMANCE OF THIS
* SOFTWARE.
*/
```

The embedded copy of zlib bears the following license:

Copyright (C) 1995-2017 Jean-loup Gailly and Mark Adler

This software is provided 'as-is',
without any express or implied
warranty. In no event will the authors be held liable for any damages
arising from the use of this software.

Permission is granted to anyone to use this software for any purpose,
including commercial applications, and to alter it and redistribute it
freely, subject to the following restrictions:

1. The origin of this software must not be misrepresented; you must not claim that you wrote the original software. If you use this software in a product, an acknowledgment in the product documentation would be appreciated but is not required.
2. Altered source versions must be plainly marked as such, and must not be misrepresented as being the original software.
3. This notice may not be removed or altered from any source distribution.

Jean-loup Gailly Mark Adler
jloup@gzip.org madler@alumni.caltech.edu

The following list of people, sorted by last name, have contributed code or patches to this implementation of sudo since I began maintaining it in 1993. This list is known to be incomplete--if you believe you should be listed, please send a note to sudo@sudo.ws.

Ackeret, Matt
Adler, Mark

Allbery, Russ
Anderson, Jamie
Andrew, Nick
Andric, Dimitry
Barron, Danny
Bates, Tom
Behan, Zdenk
Bellis, Ray
Benali, Elias
Beverly, Jamie
Boardman, Spider
Bostley, P.J.
Bowes, Keith
Boyce, Keith Garry
Brantley, Michael
Braun, Rob
Bezina, Pavel
Brooks, Piete
Brown, Jerry
Burr, Michael E
Burton, Ross
Bussjaeger, Andreas
Calvin, Gary
Campbell, Aaron
Chazelas, Stephane
ek, Vtzslav
Coleman, Chris
Corzine, Deven T.
Cusack, Frank
Dai, Wei
Dill, David
Earickson, Jeff
Eckhardt, Drew
Edgington, Ben
Esipovich, Marc
Espie, Marc
Faigon, Ariel
Farrell, Brian
Fobes, Steve
Frysinger, Mike
G., Daniel Richard
Gailly, Jean-loup
Gelman, Stephen
Gerraty, Simon J.
Graber, Stephane
Guillory, B.
Hayman, Randy M.
Henke, Joachim

Hideaki, YOSHIFUJI
Hieb, Dave
Holloway, Nick
Hoover, Adam
Hunter, Michael T.
Hutchings, Ben
Irrgang, Eric
Jackson, Brian
Jackson, John R.
Jackson, Richard L., Jr.
Janssen, Mark
Jepeway, Chris
Jorge, Joel Pele
Pele Jorge, Joel
Juhani, Timo
KIKUCHI, Ayamura
Kadow, Kevin
Kasal, Stepan
Kienenberger, Mike
King, Dale
King, Michael
Klyachkin, Andrey
Knoble, Jim
Knox, Tim
Komarnitsky, Alek O.
Kondrashov, Nikolai
Kopeek, Daniel
Kranenburg, Paul
Krause, David
Lakin, Eric
Larsen, Case
Levin, Dmitry V.
Libby, Kendall
Lobbess, Phillip E.
McIntyre, Jason
MacKenzie, David J.
McLaughlin, Tom
Makey, Jeff
Marchionna, Michael D.
Markham, Paul
Martinian,
Emin
Meskes, Michael
Michael, David
Miller, Todd C.
Minier, Loc
Moffat, Darren
Moldung, Jan Thomas

Morris, Charles
Mueller, Andreas
Mller, Dworkin
Nieusma, Jeff
Nikitser, Peter A.
Nussel, Ludwig
Ouellet, Jean-Philippe
Paquet, Eric
Paradis, Chantal
Percival, Ted
Perera, Andres
Peron, Christian S.J.
Peschel, Aaron
Peslyak, Alexander
Peterson, Toby
Petten, Diego Elio
Pickett, Joel
Plotnick, Alex
de Raadt, Theo
Rasch, Gudleik
Reid, Steve
Richards, Matt
Rossum, Guido van
Rouillard, John P.
Rowe, William A., Jr.
Roy, Alain
Ruusame, Elan
Ryabinkin, Eygene
SATO, Yuichi
Snchez, Wilfredo
Saucier, Jean-Francois
Schoenfeld, Patrick
Schuring, Arno
Schwarze, Ingo
Scott, Dougal
Sieger, Nick
Simon, Thor Lancelot
Slemko, Marc
Smith, Andy
Sobrado, Igor
Soulen, Steven
Spangler, Aaron
Spradling, Cloyce D.
Stier, Matthew
Stoeckmann, Tobias
Street, Russell
Stritzky, Tilo
Stroucken, Michael

Tarrall, Robert
Thomas, Matthew
Todd, Giles
Toft, Martin
Torek, Chris
Tucker, Darren
Uhl, Robert
Uzel, Petr
Valery, Reznic
Van Dinter, Theo
Venckus, Martynas
de Vries, Maarten
Wagner, Klaus
Walsh, Dan
Warburton, John
Webb, Kirk
Wetzel, Timm
Wieringen, Marco van
Wilk, Jakub
Winiger, Gary
Wood, David
Zacarias, Gustavo
Zolnowsky, John

The following people have worked to translate sudo into other languages:

Blttermann, Mario
Bogusz, Jakub
Casagrande, Milo
Castro, Felipe
Cho, Seong-ho
Chornoivan, Yuri
Diguez, Francisco
Ferreira, Rafael
Garca-Fontes, Walter
Gezer, Volkan
Hamasaki, Takeshi
Hamming, Peter
Hansen, Joe
Hantrais, Frdric
Hein, Jochen
Hufthammer, Karl Ove
Jerovek, Damir
Karvonen, Jorma
Kazik, Duan
Kelemen,

Gbor
Koir, Klemen
Kozlov, Yuri
Kramer, Jakob
Krznar, Tomislav
Marchal, Frdric
Margeviius, Algimantas
Maryanov, Pavel
Nikoli, Miroslav
Nylander, Daniel
Psa, Petr
Qun, Trn Ngc
Regueiro, Leandro
Sarer, zgr
Sendn, Abel
Sikrom, ka
Spingos, Dimitris
Taniguchi, Yasuaki
Tomat, Fbio
Uranga, Mikel Olasagasti
Vorotnikov, Artem
Wang, Wylmer

1.101 pam 1.1.8-3.6ubuntu2.18.04.6

1.101.1 Available under license :

Unless otherwise *explicitly* stated the following text describes the licensed conditions under which the contents of this Linux-PAM release may be distributed:

Redistribution and use in source and binary forms of Linux-PAM, with or without modification, are permitted provided that the following conditions are met:

1. Redistributions of source code must retain any existing copyright notice, and this entire permission notice in its entirety, including the disclaimer of warranties.
2. Redistributions in binary form must reproduce all prior and current copyright notices, this list of conditions, and the following disclaimer in the documentation and/or other materials provided with the distribution.
3. The name of any author may not be used to endorse or promote products derived from this software without their specific prior written permission.

ALTERNATIVELY, this product may be distributed under the terms of the GNU General Public License, in which case the provisions of the GNU GPL are required INSTEAD OF the above restrictions. (This clause is necessary due to a potential conflict between the GNU GPL and the restrictions contained in a BSD-style copyright.)

THIS SOFTWARE IS PROVIDED ``AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE AUTHOR(S) BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

Unless otherwise *explicitly* stated the following text describes the licensed conditions under which the contents of this libpamc release may be distributed:

Redistribution and use in source and binary forms of libpamc, with or without modification, are permitted provided that the following conditions are met:

1. Redistributions of source code must retain any existing copyright notice, and this entire permission notice in its entirety, including the disclaimer of warranties.
2. Redistributions in binary form must reproduce all prior and current copyright notices, this list of conditions, and the following disclaimer in the documentation and/or other materials provided with the distribution.
3. The name of any author may not be used to endorse or promote products derived from this software without their specific prior written permission.

ALTERNATIVELY, this product may be distributed under the terms of the GNU Library General Public License (LGPL), in which case the provisions of the GNU LGPL are required INSTEAD OF the above restrictions. (This clause is necessary due to a potential conflict between the GNU LGPL and the restrictions contained in a BSD-style


```

    /* Get the password entry */
+   pwd = pam_modutil_getpwnam (pamh, user);
+   if (pwd != NULL)
+   {
+       if (pam_modutil_drop_priv(pamh, &privs, pwd)) {
+           pam_syslog(pamh, LOG_ERR,
+               "Unable to change UID to %d temporarily\n",
+               pwd->pw_uid);
+           retval = PAM_SESSION_ERR;
+           goto finished;
+       }
+
+       if (asprintf(&dir, "%s/.cache", pwd->pw_dir) == -1 || !dir)
+           goto finished;
+       if (asprintf(&flag, "%s/motd.legal-displayed", dir) == -1 || !flag)
+           goto finished;
+
+       if (stat(flag, &s) != 0)
+       {
+           display_file(pamh, "/etc/legal");
+           mkdir(dir, 0700);
+           f = open(flag, O_WRONLY|O_CREAT|O_EXCL,
+               S_IRUSR|S_IWUSR|S_IRGRP|S_IROTH);
+           if (f>=0) close(f);
+       }
+
+finished:
+   if (pam_modutil_regain_priv(pamh,
+   &privs)) {
+       pam_syslog(pamh, LOG_ERR,
+           "Unable to change UID back to %d\n", privs.old_uid);
+       retval = PAM_SESSION_ERR;
+   }
+
+   _pam_drop(flag);
+   _pam_drop(dir);
+ }
+ }
+ return retval;
+ }
+
PAM_EXTERN
int pam_sm_open_session(pam_handle_t *pamh, int flags,
    int argc, const char **argv)
@@ -116,6 +171,9 @@
    /* Display the updated motd */
    display_file(pamh, motd_path);

```

```
+ /* Display the legal disclaimer only if necessary */
+ retval = display_legal(pamh);
+
+     return retval;
+ }
```

This package was debianized by J.H.M. Dassen (Ray) jdassen@debian.org on
Wed, 23 Sep 1998 20:29:32 +0200.

It was downloaded from <ftp://ftp.kernel.org/pub/linux/libs/pam/pre/>

Copyright (C) 1994, 1995, 1996 Olaf Kirch, <okir@monad.swb.de>
Copyright (C) 1995 Wietse Venema
Copyright (C) 1995, 2001-2008 Red Hat, Inc.
Copyright (C) 1996-1999, 2000-2003, 2005 Andrew G. Morgan <morgan@kernel.org>
Copyright (C) 1996, 1997, 1999 Cristian Gafton <gafton@redhat.com>
Copyright (C) 1996, 1999 Theodore Ts'o
Copyright (C) 1996 Alexander O. Yuriev
Copyright (C) 1996 Elliot Lee
Copyright (C) 1997 Philip W. Dalrymple <pwd@mdtsoft.com>
Copyright (C) 1999 Jan Rkorajski
Copyright (C) 1999 Ben Collins <bcollins@debian.org>
Copyright (C) 2000-2001, 2003, 2005, 2007 Steve Langasek
Copyright (C) 2003, 2005 IBM Corporation
Copyright (C) 2003, 2006 SuSE Linux AG.
Copyright (C) 2003 Nalin Dahyabhai <nalin@redhat.com>
Copyright (C) 2005-2008 Thorsten Kukuk <kukuk@thkukuk.de>
Copyright (C) 2005 Darren Tucker

Unless
otherwise *explicitly* stated the following text describes the
licensed conditions under which the contents of this Linux-PAM release
may be distributed:

Redistribution and use in source and binary forms of Linux-PAM, with
or without modification, are permitted provided that the following
conditions are met:

1. Redistributions of source code must retain any existing copyright
notice, and this entire permission notice in its entirety,
including the disclaimer of warranties.
2. Redistributions in binary form must reproduce all prior and current
copyright notices, this list of conditions, and the following
disclaimer in the documentation and/or other materials provided
with the distribution.

3. The name of any author may not be used to endorse or promote products derived from this software without their specific prior written permission.

ALTERNATIVELY, this product may be distributed under the terms of the GNU General Public License, in which case the provisions of the GNU GPL are required INSTEAD OF the above restrictions. (This clause is necessary due to a potential conflict between the GNU GPL and the restrictions contained in a BSD-style copyright.)

THIS SOFTWARE IS PROVIDED ``AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE AUTHOR(S) BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

On Debian GNU/Linux systems, the complete text of the GNU General Public License can be found in `~/usr/share/common-licenses/GPL`.

1.102 openssl 1.1.1-1ubuntu2.1~18.04.21

1.102.1 Available under license :

LICENSE ISSUES

=====

The OpenSSL toolkit stays under a double license, i.e. both the conditions of the OpenSSL License and the original SSLeay license apply to the toolkit. See below for the actual license texts.

OpenSSL License

/* =====

* Copyright (c) 1998-2018 The OpenSSL Project. All rights reserved.

*

* Redistribution and use in source and binary forms, with or without

* modification, are permitted provided that the following conditions

- * are met:
- *
- * 1. Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.
- *
- * 2. Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.
- *
- * 3. All advertising materials mentioning features or use of this software must display the following acknowledgment:
- * "This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit. (<http://www.openssl.org/>)"
- *
- * 4. The names "OpenSSL Toolkit" and "OpenSSL Project" must not be used to endorse or promote products derived from this software without prior written permission. For written permission, please contact openssl-core@openssl.org.
- *
- * 5. Products derived from this software may not be called "OpenSSL" nor may "OpenSSL" appear in their names without prior written permission of the OpenSSL Project.
- *
- * 6. Redistributions of any form whatsoever must retain the following acknowledgment:
- * "This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit (<http://www.openssl.org/>)"
- *
- * THIS SOFTWARE IS PROVIDED BY THE OpenSSL PROJECT ``AS IS'' AND ANY EXPRESSED OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE OpenSSL PROJECT OR ITS CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
- * =====
- *
- * This product includes cryptographic software written by Eric Young (ey@cryptsoft.com). This product includes software written by Tim Hudson (tjh@cryptsoft.com).

*
*/

Original SSLeay License

```
/* Copyright (C) 1995-1998 Eric Young (eay@cryptsoft.com)
 * All rights reserved.
 *
 * This package is an SSL implementation written
 * by Eric Young (eay@cryptsoft.com).
 * The implementation was written so as to conform with Netscapes SSL.
 *
 * This library is free for commercial and non-commercial use as long as
 * the following conditions are aheared to. The following conditions
 * apply to all code found in this distribution, be it the RC4, RSA,
 * lhash, DES, etc., code; not just the SSL code. The SSL documentation
 * included with this distribution is covered by the same copyright terms
 * except that the holder is Tim Hudson (tjh@cryptsoft.com).
 *
 * Copyright remains Eric Young's, and as such any Copyright notices in
 * the code are not to be removed.
 * If this package is used in a product, Eric Young should be given attribution
 * as the author of the parts of the library used.
 * This can be in the form of a textual message at program startup or
 * in documentation (online or textual) provided with the package.
 *
 * Redistribution and use in source and binary forms, with or without
 * modification, are permitted provided that the following conditions
 * are met:
 * 1. Redistributions of source code must retain the copyright
 * notice, this list of conditions and the following disclaimer.
 * 2. Redistributions in binary form must reproduce the above copyright
 * notice, this list of conditions and the following disclaimer in the
 * documentation and/or other materials provided with the distribution.
 * 3. All advertising materials mentioning features or use of this software
 * must display the following acknowledgement:
 * "This product includes cryptographic software written by
 * Eric Young (eay@cryptsoft.com)"
 * The word 'cryptographic' can be left out if the rouines from the library
 * being used are not cryptographic related :-).
 * 4. If you include any Windows specific code (or a derivative thereof) from
 * the apps directory (application code) you must
 * include an acknowledgement:
 * "This product includes software written by Tim Hudson (tjh@cryptsoft.com)"
 *
 * THIS SOFTWARE IS PROVIDED BY ERIC YOUNG ``AS IS" AND
 * ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE
```

* IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE
* ARE DISCLAIMED. IN NO EVENT SHALL THE AUTHOR OR CONTRIBUTORS BE LIABLE
* FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL
* DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS
* OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION)
* HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT
* LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY
* OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF
* SUCH DAMAGE.

*

* The licence and distribution terms for any publically available version or
* derivative of this code cannot be changed. i.e.

this code cannot simply be

* copied and put under another distribution licence

* [including the GNU Public Licence.]

*/

GNU GENERAL PUBLIC LICENSE

Version 2, June 1991

Copyright (C) 1989, 1991 Free Software Foundation, Inc.

59 Temple Place - Suite 330, Boston, MA

02111-1307, USA.

Everyone is permitted to copy and distribute verbatim copies
of this license document, but changing it is not allowed.

Preamble

The licenses for most software are designed to take away your freedom to share and change it. By contrast, the GNU General Public License is intended to guarantee your freedom to share and change free software--to make sure the software is free for all its users. This General Public License applies to most of the Free Software Foundation's software and to any other program whose authors commit to using it. (Some other Free Software Foundation software is covered by the GNU Library General Public License instead.) You can apply it to your programs, too.

When we speak of free software, we are referring to freedom, not price.

Our General Public Licenses are designed to make sure that you have the freedom to distribute copies of free software (and charge for this service if you wish), that you receive source code or can get it if you want it, that you can change the software or use pieces of it in new free programs; and that you know you can do these things.

To protect your rights, we need to make restrictions that forbid anyone to deny you these rights or to ask you to surrender the rights.

These restrictions translate to certain responsibilities for you if you

distribute copies of the software, or if you modify it.

For example, if you distribute copies of such a program, whether gratis or for a fee, you must give the recipients all the rights that you have. You must make sure that they, too, receive or can get the source code. And you must show them these terms so they know their rights.

We protect your rights with two steps: (1) copyright the software, and (2) offer you this license which gives you legal permission to copy, distribute and/or modify the software.

Also, for each author's protection and ours, we want to make certain that everyone understands that there is no warranty for this free software. If the software is modified by someone else and passed on, we want its recipients to know that what they have is not the original, so that any problems introduced by others will not reflect on the original authors' reputations.

Finally, any free program is threatened constantly by software patents. We wish to avoid the danger that redistributors of a free program will individually obtain patent licenses, in effect making the program proprietary. To prevent this, we have made it clear that any patent must be licensed for everyone's free use or not licensed at all.

The precise terms and conditions for copying, distribution and modification follow.

GNU GENERAL PUBLIC LICENSE

TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

0. This

License applies to any program or other work which contains a notice placed by the copyright holder saying it may be distributed under the terms of this General Public License. The "Program", below, refers to any such program or work, and a "work based on the Program" means either the Program or any derivative work under copyright law: that is to say, a work containing the Program or a portion of it, either verbatim or with modifications and/or translated into another language. (Hereinafter, translation is included without limitation in the term "modification".) Each licensee is addressed as "you".

Activities other than copying, distribution and modification are not covered by this License; they are outside its scope. The act of running the Program is not restricted, and the output from the Program is covered only if its contents constitute a work based on the Program (independent of having been made by running the Program).

Whether that is true depends on what the Program does.

1. You may copy and distribute verbatim copies of the Program's source code as you receive it, in any medium, provided that you conspicuously and appropriately publish on each copy an appropriate copyright notice and disclaimer of warranty; keep intact all the notices that refer to this License and to the absence of any warranty; and give any other recipients of the Program a copy of this License along with the Program.

You may charge a fee for the physical act of transferring a copy, and you may at your option offer warranty protection in exchange for a fee.

2. You may modify your copy or copies of the Program or any portion of it, thus forming a work based on the Program, and copy and distribute such modifications or work under the terms of Section 1 above, provided that you also meet all of these conditions:

a) You must cause the modified files to carry prominent notices stating that you changed the files and the date of any change.

b) You must cause any work that you distribute or publish, that in whole or in part contains or is derived from the Program or any part thereof, to be licensed as a whole at no charge to all third parties under the terms of this License.

c) If the modified program normally reads commands interactively when run, you must cause it, when started running for such interactive use in the most ordinary way, to print or display an announcement including an appropriate copyright notice and a notice that there is no warranty (or else, saying that you provide a warranty) and that users may redistribute the program under these conditions, and telling the user how to view a copy of this License. (Exception: if the Program itself is interactive but does not normally print such an announcement, your work based on the Program is not required to print an announcement.)

These requirements apply to the modified work as a whole. If identifiable sections of that work are not derived from the Program, and can be reasonably considered independent and separate works in themselves, then this License, and its terms, do not apply to those sections when you distribute them as separate works. But when you distribute the same sections as part of a whole which is a work based on the Program, the distribution of the whole must be on the terms of this License, whose permissions for other licensees extend to the entire whole, and thus to each and every part regardless of who wrote it.

Thus, it is not the intent of this section to claim rights or contest your rights to work written entirely by you; rather, the intent is to exercise the right to control the distribution of derivative or collective works based on the Program.

In addition, mere aggregation of another work not based on the Program with the Program (or with a work based on the Program) on a volume of a storage or distribution medium does not bring the other work under the scope of this License.

3. You may

copy and distribute the Program (or a work based on it, under Section 2) in object code or executable form under the terms of Sections 1 and 2 above provided that you also do one of the following:

a) Accompany it with the complete corresponding machine-readable source code, which must be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange; or,

b) Accompany it with a written offer, valid for at least three years, to give any third party, for a charge no more than your cost of physically performing source distribution, a complete machine-readable copy of the corresponding source code, to be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange; or,

c) Accompany it with the information you received as to the offer to distribute corresponding source code. (This alternative is allowed only for noncommercial distribution and only if you received the program in object code or executable form with such an offer, in accord with Subsection b above.)

The source code for a work means the preferred form of the work for making modifications to it. For an executable work, complete source code means all the source code for all modules it contains, plus any associated interface definition files, plus the scripts used to control compilation and installation of the executable. However, as a special exception, the source code distributed need not include anything that is normally distributed (in either source or binary form) with the major components (compiler, kernel, and so on) of the operating system on which the executable runs, unless that component itself accompanies the executable.

If distribution of executable or object code is made by offering access to copy from a designated place, then offering equivalent access to copy the source code from the same place counts as

distribution of the source code, even though third parties are not compelled to copy the source along with the object code.

4. You may not copy, modify, sublicense, or distribute the Program except as expressly provided under this License. Any attempt otherwise to copy, modify, sublicense or distribute the Program is void, and will automatically terminate your rights under this License. However, parties who have received copies, or rights, from you under this License will not have their licenses terminated so long as such parties remain in full compliance.

5. You are not required to accept this License, since you have not signed it. However, nothing else grants you permission to modify or distribute the Program or its derivative works. These actions are prohibited by law if you do not accept this License. Therefore, by modifying or distributing the Program (or any work based on the Program), you indicate your acceptance of this License to do so, and all its terms and conditions for copying, distributing or modifying the Program or works based on it.

6. Each time you redistribute the Program (or any work based on the Program), the recipient automatically receives a license from the original licensor to copy, distribute or modify the Program subject to these terms and conditions. You may not impose any further restrictions on the recipients' exercise of the rights granted herein. You are not responsible for enforcing compliance by third parties to this License.

7. If, as a consequence of a court judgment or allegation of patent infringement or for any other reason (not limited to patent issues), conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot distribute so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not distribute the Program at all. For example, if a patent license would not permit royalty-free redistribution of the Program by all those who receive copies directly or indirectly through you, then the only way you could satisfy both it and this License would be to refrain entirely from distribution of the Program.

If any portion of this section is held invalid or unenforceable under any particular circumstance, the balance of the section is intended to apply and the section as a whole is intended to apply in other circumstances.

It is not the purpose of this section to induce you to infringe any patents or other property right claims or to contest validity of any such claims; this section has the sole purpose of protecting the integrity of the free software distribution system, which is implemented by public license practices. Many people have made generous contributions to the wide range of software distributed through that system in reliance on consistent application of that system; it is up to the author/donor to decide if he or she is willing to distribute software through any other system and a licensee cannot impose that choice.

This section is intended to make thoroughly clear what is believed to be a consequence of the rest of this License.

8. If the distribution and/or use of the Program is restricted in certain countries either by patents or by copyrighted interfaces, the original copyright holder who places the Program under this License may add an explicit geographical distribution limitation excluding those countries, so that distribution is permitted only in or among countries not thus excluded. In such case, this License incorporates the limitation as if written in the body of this License.

9. The Free Software Foundation may publish revised and/or new versions of the General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number.

If the Program specifies a version number of this License which applies to it and "any later version", you have the option of following the terms and conditions either of that version or of any later version published by the Free Software Foundation. If the Program does not specify a version number of this License, you may choose any version ever published by the Free Software Foundation.

10. If you wish to incorporate parts of the Program into other free programs whose distribution conditions are different, write to the author to ask for permission. For software which is copyrighted by the Free Software Foundation, write to the Free Software Foundation; we sometimes make exceptions for this. Our decision will be guided by the two goals of preserving the free status of all derivatives of our free software and of promoting the sharing and reuse of software generally.

NO WARRANTY

11. BECAUSE THE PROGRAM IS LICENSED FREE OF CHARGE, THERE IS NO WARRANTY FOR THE PROGRAM,
TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE PROGRAM "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE PROGRAM IS WITH YOU. SHOULD THE PROGRAM PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

12. IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY AND/OR REDISTRIBUTE THE PROGRAM AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE PROGRAM (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE PROGRAM TO OPERATE WITH ANY OTHER PROGRAMS), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

END OF TERMS AND CONDITIONS

Appendix: How to Apply These Terms to Your New Programs

If you develop a new program, and you want it to be of the greatest possible use to the public, the best way to achieve this is to make it free software which everyone can redistribute and change under these terms.

To do so, attach the following notices to the program. It is safest to attach them to the start of each source file to most effectively convey the exclusion of warranty; and each file should have at least the "copyright" line and a pointer to where the full notice is found.

<one line to give the program's name and a brief idea of what it does.>

Copyright (C) 19yy <name of author>

This program is free software; you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free

Software Foundation; either version 2 of the License, or (at your option) any later version.

This program is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details.

You should have received a copy of the GNU General Public License along with this program; if not, write to the Free Software Foundation, Inc., 59 Temple Place - Suite 330, Boston, MA 02111-1307, USA.

Also add information on how to contact you by electronic and paper mail.

If the program is interactive, make it output a short notice like this when it starts in an interactive mode:

```
Gnomovision version 69, Copyright (C) 19yy name of author
Gnomovision comes with ABSOLUTELY NO WARRANTY; for details type `show w'.
This is free software, and you are welcome to redistribute it
under certain conditions; type `show c'
for details.
```

The hypothetical commands ``show w'` and ``show c'` should show the appropriate parts of the General Public License. Of course, the commands you use may be called something other than ``show w'` and ``show c'`; they could even be mouse-clicks or menu items--whatever suits your program.

You should also get your employer (if you work as a programmer) or your school, if any, to sign a "copyright disclaimer" for the program, if necessary. Here is a sample; alter the names:

```
Yoyodyne, Inc., hereby disclaims all copyright interest in the program
`Gnomovision' (which makes passes at compilers) written by James Hacker.
```

```
<signature of Ty Coon>, 1 April 1989
Ty Coon, President of Vice
```

This General Public License does not permit incorporating your program into proprietary programs. If your program is a subroutine library, you may consider it more useful to permit linking proprietary applications with the library. If this is what you want to do, use the GNU Library General Public License instead of this License.

The "Artistic License"

Preamble

The intent of this document is to state the conditions under which a Package may be copied, such that the Copyright Holder maintains some semblance of artistic control over the development of the package,

while giving the users of the package the right to use and distribute the Package in a more-or-less customary fashion, plus the right to make reasonable modifications.

Definitions:

"Package" refers to the collection of files distributed by the Copyright Holder, and derivatives of that collection of files created through textual modification.

"Standard Version" refers to such a Package if it has not been modified, or has been modified in accordance with the wishes of the Copyright Holder as specified below.

"Copyright Holder" is whoever is named in the copyright or copyrights for the package.

"You" is you, if you're thinking about copying or distributing this Package.

"Reasonable copying fee" is whatever you can justify on the basis of media cost, duplication charges, time of people involved, and so on. (You will not be required to justify it to the Copyright Holder, but only to the computing community at large as a market that must bear the fee.)

"Freely Available" means that no fee is charged for the item itself, though there may be fees involved in handling the item. It also means that recipients of the item may redistribute it under the same conditions they received it.

1. You may make and give away verbatim copies of the source form of the Standard Version of this Package without restriction, provided that you duplicate all of the original copyright notices and associated disclaimers.
2. You may apply bug fixes, portability fixes and other modifications derived from the Public Domain or from the Copyright Holder. A Package modified in such a way shall still be considered the Standard Version.
3. You may otherwise modify your copy of this Package in any way, provided that you insert a prominent notice in each changed file stating how and when you changed that file, and provided that you do at least ONE of the following:
 - a) place your modifications in the Public Domain or otherwise make them Freely Available, such as by posting said modifications to Usenet or

an equivalent medium, or placing the modifications on a major archive site such as uunet.uu.net, or by allowing the Copyright Holder to include your modifications in the Standard Version of the Package.

b) use the modified Package only within your corporation or organization.

c) rename any non-standard executables so the names do not conflict with standard executables, which must also be provided, and provide a separate manual page for each non-standard executable that clearly documents how it differs from the Standard Version.

d) make other distribution arrangements with the Copyright Holder.

4. You may distribute the programs of this Package in object code or executable form, provided that you do at least ONE of the following:

a) distribute a Standard Version of the executables and library files, together with instructions (in the manual page or equivalent) on where to get the Standard Version.

b) accompany the distribution with the machine-readable source of the Package with your modifications.

c) give non-standard executables non-standard names, and clearly document the differences in manual pages (or equivalent), together with instructions on where to get the Standard Version.

d) make other distribution arrangements with the Copyright Holder.

5. You may charge a reasonable copying fee for any distribution of this Package. You may charge any fee you choose for support of this Package. You may not charge a fee for this Package itself. However, you may distribute this Package in aggregate with other (possibly commercial) programs as part of a larger (possibly commercial) software distribution provided

that you do not advertise this Package as a product of your own. You may embed this Package's interpreter within an executable of yours (by linking); this shall be construed as a mere form of aggregation, provided that the complete Standard Version of the interpreter is so embedded.

6. The scripts and library files supplied as input to or produced as output from the programs of this Package do not automatically fall under the copyright of this Package, but belong to whoever generated them, and may be sold commercially, and may be aggregated with this Package. If such scripts or library files are aggregated with this Package via the so-called "undump" or "unexec" methods of producing a

binary executable image, then distribution of such an image shall neither be construed as a distribution of this Package nor shall it fall under the restrictions of Paragraphs 3 and 4, provided that you do not represent such an executable image as a Standard Version of this Package.

7. C subroutines

(or comparably compiled subroutines in other languages) supplied by you and linked into this Package in order to emulate subroutines and variables of the language defined by this Package shall not be considered part of this Package, but are the equivalent of input as in Paragraph 6, provided these subroutines do not change the language in any way that would cause it to fail the regression tests for the language.

8. Aggregation of this Package with a commercial distribution is always permitted provided that the use of this Package is embedded; that is, when no overt attempt is made to make this Package's interfaces visible to the end user of the commercial distribution. Such use shall not be construed as a distribution of this Package.

9. The name of the Copyright Holder may not be used to endorse or promote products derived from this software without specific prior written permission.

10. THIS PACKAGE IS PROVIDED "AS IS" AND WITHOUT ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, WITHOUT LIMITATION, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE.

The End

1.103 libssl 1.1.1-1ubuntu2.1~18.04.21

1.103.1 Available under license :

LICENSE ISSUES

=====

The OpenSSL toolkit stays under a double license, i.e. both the conditions of the OpenSSL License and the original SSLeay license apply to the toolkit. See below for the actual license texts.

OpenSSL License

/* =====

* Copyright (c) 1998-2018 The OpenSSL Project. All rights reserved.

*
* Redistribution and use in source and binary forms, with or without
* modification, are permitted provided that the following conditions
* are met:
*
* 1. Redistributions of source code must retain the above copyright
* notice, this list of conditions and the following disclaimer.
*
* 2. Redistributions in binary form must reproduce the above copyright
* notice, this list of conditions and the following disclaimer in
* the documentation and/or other materials provided with the
* distribution.
*
* 3. All advertising materials mentioning features or use
of this
* software must display the following acknowledgment:
* "This product includes software developed by the OpenSSL Project
* for use in the OpenSSL Toolkit. (<http://www.openssl.org/>)"
*
* 4. The names "OpenSSL Toolkit" and "OpenSSL Project" must not be used to
* endorse or promote products derived from this software without
* prior written permission. For written permission, please contact
* openssl-core@openssl.org.
*
* 5. Products derived from this software may not be called "OpenSSL"
* nor may "OpenSSL" appear in their names without prior written
* permission of the OpenSSL Project.
*
* 6. Redistributions of any form whatsoever must retain the following
* acknowledgment:
* "This product includes software developed by the OpenSSL Project
* for use in the OpenSSL Toolkit (<http://www.openssl.org/>)"
*
* THIS SOFTWARE IS PROVIDED BY THE OpenSSL PROJECT ``AS IS" AND ANY
* EXPRESSED OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED
TO, THE
* IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR
* PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE OpenSSL PROJECT OR
* ITS CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL,
* SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT
* NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES;
* LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION)
* HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT,
* STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE)
* ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED
* OF THE POSSIBILITY OF SUCH DAMAGE.
* =====
*

* This product includes cryptographic software written by Eric Young
* (eay@cryptsoft.com). This product includes software written by Tim
* Hudson (tjh@cryptsoft.com).
*
*/

Original SSLeay License

/* Copyright (C) 1995-1998 Eric Young (eay@cryptsoft.com)
* All rights reserved.
*
* This package is an SSL implementation written
* by Eric Young (eay@cryptsoft.com).
* The implementation was written so as to conform with Netscapes SSL.
*
* This library is free for commercial and non-commercial use as long as
* the following conditions are aheared to. The following conditions
* apply to all code found in this distribution, be it the RC4, RSA,
* lhash, DES, etc., code; not just the SSL code. The SSL documentation
* included with this distribution is covered by the same copyright terms
* except that the holder is Tim Hudson (tjh@cryptsoft.com).
*
* Copyright remains Eric Young's, and as such any Copyright notices in
* the code are not to be removed.
* If this package is used in a product, Eric Young should be given attribution
* as the author of the parts of the library used.
* This can be in the form of a textual message at program startup or
* in documentation (online or textual) provided with the package.
*
* Redistribution and use in source and binary forms, with or without
* modification, are permitted provided that the following conditions
* are met:
* 1. Redistributions of source code must retain the copyright
* notice, this list of conditions and the following disclaimer.
* 2. Redistributions in binary form must reproduce the above copyright
* notice, this list of conditions and the following disclaimer in the
* documentation and/or other materials provided with the distribution.
* 3. All advertising materials mentioning features or use of this software
* must display the following acknowledgement:
* "This product includes cryptographic software written by
* Eric Young (eay@cryptsoft.com)"
* The word 'cryptographic' can be left out if the rouines from the library
* being used are not cryptographic related :-).
* 4. If you include any Windows specific code (or a derivative thereof) from
* the apps directory (application code) you must
include an acknowledgement:
* "This product includes software written by Tim Hudson (tjh@cryptsoft.com)"

*
* THIS SOFTWARE IS PROVIDED BY ERIC YOUNG ``AS IS" AND
* ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE
* IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE
* ARE DISCLAIMED. IN NO EVENT SHALL THE AUTHOR OR CONTRIBUTORS BE LIABLE
* FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL
* DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS
* OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION)
* HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT
* LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY
* OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF
* SUCH DAMAGE.

*
* The licence and distribution terms for any publically available version or
* derivative of this code cannot be changed. i.e.
this code cannot simply be
* copied and put under another distribution licence
* [including the GNU Public Licence.]
*/

GNU GENERAL PUBLIC LICENSE
Version 2, June 1991

Copyright (C) 1989, 1991 Free Software Foundation, Inc.
59 Temple Place - Suite 330, Boston, MA
02111-1307, USA.

Everyone is permitted to copy and distribute verbatim copies
of this license document, but changing it is not allowed.

Preamble

The licenses for most software are designed to take away your
freedom to share and change it. By contrast, the GNU General Public
License is intended to guarantee your freedom to share and change free
software--to make sure the software is free for all its users. This
General Public License applies to most of the Free Software
Foundation's software and to any other program whose authors commit to
using it. (Some other Free Software Foundation software is covered by
the GNU Library General Public License instead.) You can apply it to
your programs, too.

When we speak of free software, we are referring to freedom, not
price.

Our General Public Licenses are designed to make sure that you
have the freedom to distribute copies of free software (and charge for
this service if you wish), that you receive source code or can get it
if you want it, that you can change the software or use pieces of it
in new free programs; and that you know you can do these things.

To protect your rights, we need to make restrictions that forbid anyone to deny you these rights or to ask you to surrender the rights. These restrictions translate to certain responsibilities for you if you distribute copies of the software, or if you modify it.

For example, if you distribute copies of such a program, whether gratis or for a fee, you must give the recipients all the rights that you have. You must make sure that they, too, receive or can get the source code. And you must show them these terms so they know their rights.

We protect your rights with two steps: (1) copyright the software, and (2) offer you this license which gives you legal permission to copy, distribute and/or modify the software.

Also, for each author's protection and ours, we want to make certain that everyone understands that there is no warranty for this free software. If the software is modified by someone else and passed on, we want its recipients to know that what they have is not the original, so that any problems introduced by others will not reflect on the original authors' reputations.

Finally, any free program is threatened constantly by software patents. We wish to avoid the danger that redistributors of a free program will individually obtain patent licenses, in effect making the program proprietary. To prevent this, we have made it clear that any patent must be licensed for everyone's free use or not licensed at all.

The precise terms and conditions for copying, distribution and modification follow.

GNU GENERAL PUBLIC LICENSE TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

0. This

License applies to any program or other work which contains a notice placed by the copyright holder saying it may be distributed under the terms of this General Public License. The "Program", below, refers to any such program or work, and a "work based on the Program" means either the Program or any derivative work under copyright law: that is to say, a work containing the Program or a portion of it, either verbatim or with modifications and/or translated into another language. (Hereinafter, translation is included without limitation in the term "modification".) Each licensee is addressed as "you".

Activities other than copying, distribution and modification are not covered by this License; they are outside its scope. The act of

running the Program is not restricted, and the output from the Program is covered only if its contents constitute a work based on the Program (independent of having been made by running the Program). Whether that is true depends on what the Program does.

1. You may copy and distribute verbatim copies of the Program's source code as you receive it, in any medium, provided that you conspicuously and appropriately publish on each copy an appropriate copyright notice and disclaimer of warranty; keep intact all the notices that refer to this License and to the absence of any warranty; and give any other recipients of the Program a copy of this License along with the Program.

You may charge a fee for the physical act of transferring a copy, and you may at your option offer warranty protection in exchange for a fee.

2. You may modify your copy or copies of the Program or any portion of it, thus forming a work based on the Program, and copy and distribute such modifications or work under the terms of Section 1 above, provided that you also meet all of these conditions:

a) You must cause the modified files to carry prominent notices stating that you changed the files and the date of any change.

b) You must cause any work that you distribute or publish, that in whole or in part contains or is derived from the Program or any part thereof, to be licensed as a whole at no charge to all third parties under the terms of this License.

c) If the modified program normally reads commands interactively when run, you must cause it, when started running for such interactive use in the most ordinary way, to print or display an announcement including an appropriate copyright notice and a notice that there is no warranty (or else, saying that you provide a warranty) and that users may redistribute the program under these conditions, and telling the user how to view a copy of this License. (Exception: if the Program itself is interactive but does not normally print such an announcement, your work based on the Program is not required to print an announcement.)

These requirements apply to the modified work as a whole. If identifiable sections of that work are not derived from the Program, and can be reasonably considered independent and separate works in themselves, then this License, and its terms, do not apply to those sections when you distribute them as separate works. But when you distribute the same sections as part of a whole which is a work based

on the Program, the distribution of the whole must be on the terms of this License, whose permissions for other licensees extend to the entire whole, and thus to each and every part regardless of who wrote it.

Thus, it is not the intent of this section to claim rights or contest your rights to work written entirely by you; rather, the intent is to exercise the right to control the distribution of derivative or collective works based on the Program.

In addition, mere aggregation of another work not based on the Program with the Program (or with a work based on the Program) on a volume of a storage or distribution medium does not bring the other work under the scope of this License.

3. You may

copy and distribute the Program (or a work based on it, under Section 2) in object code or executable form under the terms of Sections 1 and 2 above provided that you also do one of the following:

a) Accompany it with the complete corresponding machine-readable source code, which must be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange; or,

b) Accompany it with a written offer, valid for at least three years, to give any third party, for a charge no more than your cost of physically performing source distribution, a complete machine-readable copy of the corresponding source code, to be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange; or,

c) Accompany it with the information you received as to the offer to distribute corresponding source code. (This alternative is allowed only for noncommercial distribution and only if you received the program in object code or executable form with such an offer, in accord with Subsection b above.)

The source code for a work means the preferred form of the work for making modifications to it. For an executable work, complete source code means all the source code for all modules it contains, plus any associated interface definition files, plus the scripts used to control compilation and installation of the executable. However, as a special exception, the source code distributed need not include anything that is normally distributed (in either source or binary form) with the major components (compiler, kernel, and so on) of the operating system on which the executable runs, unless that component itself accompanies the executable.

If distribution of executable or object code is made by offering access to copy from a designated place, then offering equivalent access to copy the source code from the same place counts as distribution of the source code, even though third parties are not compelled to copy the source along with the object code.

4. You may not copy, modify, sublicense, or distribute the Program except as expressly provided under this License. Any attempt otherwise to copy, modify, sublicense or distribute the Program is void, and will automatically terminate your rights under this License. However, parties who have received copies, or rights, from you under this License will not have their licenses terminated so long as such parties remain in full compliance.

5. You are not required to accept this License, since you have not signed it. However, nothing else grants you permission to modify or distribute the Program or its derivative works. These actions are prohibited by law if you do not accept this License. Therefore, by modifying or distributing the Program (or any work based on the Program), you indicate your acceptance of this License to do so, and all its terms and conditions for copying, distributing or modifying the Program or works based on it.

6. Each time you redistribute the Program (or any work based on the Program), the recipient automatically receives a license from the original licensor to copy, distribute or modify the Program subject to these terms and conditions. You may not impose any further restrictions on the recipients' exercise of the rights granted herein. You are not responsible for enforcing compliance by third parties to this License.

7. If, as a consequence of a court judgment or allegation of patent infringement or for any other reason (not limited to patent issues), conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot distribute so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not distribute the Program at all. For example, if a patent license would not permit royalty-free redistribution of the Program by all those who receive copies directly or indirectly through you, then the only way you could satisfy both it and this License would be to refrain entirely from distribution of the Program.

If any portion of this section is held invalid or unenforceable under

any particular circumstance, the balance of the section is intended to apply and the section as a whole is intended to apply in other circumstances.

It is not the purpose of this section to induce you to infringe any patents or other property right claims or to contest validity of any such claims; this section has the sole purpose of protecting the integrity of the free software distribution system, which is implemented by public license practices. Many people have made generous contributions to the wide range of software distributed through that system in reliance on consistent application of that system; it is up to the author/donor to decide if he or she is willing to distribute software through any other system and a licensee cannot impose that choice.

This section is intended to make thoroughly clear what is believed to be a consequence of the rest of this License.

8. If the distribution and/or use of the Program is restricted in certain countries either by patents or by copyrighted interfaces, the original copyright holder who places the Program under this License may add an explicit geographical distribution limitation excluding those countries, so that distribution is permitted only in or among countries not thus excluded. In such case, this License incorporates the limitation as if written in the body of this License.

9. The Free Software Foundation may publish revised and/or new versions of the General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number.

If the Program specifies a version number of this License which applies to it and "any later version", you have the option of following the terms and conditions either of that version or of any later version published by the Free Software Foundation. If the Program does not specify a version number of this License, you may choose any version ever published by the Free Software Foundation.

10. If you wish to incorporate parts of the Program into other free programs whose distribution conditions are different, write to the author to ask for permission. For software which is copyrighted by the Free Software Foundation, write to the Free Software Foundation; we sometimes make exceptions for this. Our decision will be guided by the two goals of preserving the free status of all derivatives of our free software and of promoting the sharing and reuse of software generally.

NO WARRANTY

11. BECAUSE THE PROGRAM IS LICENSED FREE OF CHARGE, THERE IS NO WARRANTY FOR THE PROGRAM, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE PROGRAM "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE PROGRAM IS WITH YOU. SHOULD THE PROGRAM PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

12. IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY AND/OR REDISTRIBUTE THE PROGRAM AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE PROGRAM (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE PROGRAM TO OPERATE WITH ANY OTHER PROGRAMS), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

END OF TERMS AND CONDITIONS

Appendix: How to Apply These Terms to Your New Programs

If you develop a new program, and you want it to be of the greatest possible use to the public, the best way to achieve this is to make it free software which everyone can redistribute and change under these terms.

To do so, attach the following notices to the program. It is safest to attach them to the start of each source file to most effectively convey the exclusion of warranty; and each file should have at least the "copyright" line and a pointer to where the full notice is found.

```
<one line to give the program's name and a brief idea of what it does.>  
Copyright (C) 19yy <name of author>
```

```
This program is free software; you can redistribute it and/or modify  
it under the terms of the GNU General Public License as published by  
the Free  
Software Foundation; either version 2 of the License, or  
(at your option) any later version.
```

This program is distributed in the hope that it will be useful,

but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details.

You should have received a copy of the GNU General Public License along with this program; if not, write to the Free Software Foundation, Inc., 59 Temple Place - Suite 330, Boston, MA 02111-1307, USA.

Also add information on how to contact you by electronic and paper mail.

If the program is interactive, make it output a short notice like this when it starts in an interactive mode:

```
Gnomovision version 69, Copyright (C) 19yy name of author
Gnomovision comes with ABSOLUTELY NO WARRANTY; for details type `show w'.
This is free software, and you are welcome to redistribute it
under certain conditions; type `show c'
for details.
```

The hypothetical commands `show w' and `show c' should show the appropriate parts of the General Public License. Of course, the commands you use may be called something other than `show w' and `show c'; they could even be mouse-clicks or menu items--whatever suits your program.

You should also get your employer (if you work as a programmer) or your school, if any, to sign a "copyright disclaimer" for the program, if necessary. Here is a sample; alter the names:

```
Yoyodyne, Inc., hereby disclaims all copyright interest in the program
`Gnomovision' (which makes passes at compilers) written by James Hacker.
```

```
<signature of Ty Coon>, 1 April 1989
Ty Coon, President of Vice
```

This General Public License does not permit incorporating your program into proprietary programs. If your program is a subroutine library, you may consider it more useful to permit linking proprietary applications with the library. If this is what you want to do, use the GNU Library General Public License instead of this License.

The "Artistic License"

Preamble

The intent of this document is to state the conditions under which a Package may be copied, such that the Copyright Holder maintains some semblance of artistic control over the development of the package, while giving the users of the package the right to use and distribute the Package in a more-or-less customary fashion, plus the right to make reasonable modifications.

Definitions:

"Package" refers to the collection of files distributed by the Copyright Holder, and derivatives of that collection of files created through textual modification.

"Standard Version" refers to such a Package if it has not been modified, or has been modified in accordance with the wishes of the Copyright Holder as specified below.

"Copyright Holder" is whoever is named in the copyright or copyrights for the package.

"You" is you, if you're thinking about copying or distributing this Package.

"Reasonable copying fee" is whatever you can justify on the basis of media cost, duplication charges, time of people involved, and so on. (You will not be required to justify it to the Copyright Holder, but only to the computing community at large as a market that must bear the fee.)

"Freely Available" means that no fee is charged for the item itself, though there may be fees involved in handling the item. It also means that recipients of the item may redistribute it under the same conditions they received it.

1. You may make and give away verbatim copies of the source form of the Standard Version of this Package without restriction, provided that you duplicate all of the original copyright notices and associated disclaimers.
2. You may apply bug fixes, portability fixes and other modifications derived from the Public Domain or from the Copyright Holder. A Package modified in such a way shall still be considered the Standard Version.
3. You may otherwise modify your copy of this Package in any way, provided that you insert a prominent notice in each changed file stating how and when you changed that file, and provided that you do at least ONE of the following:

a) place your modifications in the Public Domain or otherwise make them Freely Available, such as by posting said modifications to Usenet or an equivalent medium, or placing the modifications on a major archive site such as uunet.uu.net, or by allowing the Copyright Holder to include your modifications in the Standard Version of the Package.

b) use the modified Package only within your corporation or organization.

c) rename any non-standard executables so the names do not conflict with standard executables, which must also be provided, and provide a separate manual page for each non-standard executable that clearly documents how it differs from the Standard Version.

d) make other distribution arrangements with the Copyright Holder.

4. You may distribute the programs of this Package in object code or executable

form, provided that you do at least ONE of the following:

a) distribute a Standard Version of the executables and library files, together with instructions (in the manual page or equivalent) on where to get the Standard Version.

b) accompany the distribution with the machine-readable source of the Package with your modifications.

c) give non-standard executables non-standard names, and clearly document the differences in manual pages (or equivalent), together with instructions on where to get the Standard Version.

d) make other distribution arrangements with the Copyright Holder.

5. You may charge a reasonable copying fee for any distribution of this Package. You may charge any fee you choose for support of this Package. You may not charge a fee for this Package itself. However, you may distribute this Package in aggregate with other (possibly commercial) programs as part of a larger (possibly commercial) software distribution provided

that you do not advertise this Package as a product of your own. You may embed this Package's interpreter within an executable of yours (by linking); this shall be construed as a mere form of aggregation, provided that the complete Standard Version of the interpreter is so embedded.

6. The scripts and library files supplied as input to or produced as output from the programs of this Package do not automatically fall under the copyright of this Package, but belong to whoever generated

them, and may be sold commercially, and may be aggregated with this Package. If such scripts or library files are aggregated with this Package via the so-called "undump" or "unexec" methods of producing a binary executable image, then distribution of such an image shall neither be construed as a distribution of this Package nor shall it fall under the restrictions of Paragraphs 3 and 4, provided that you do not represent such an executable image as a Standard Version of this Package.

7. C subroutines

(or comparably compiled subroutines in other languages) supplied by you and linked into this Package in order to emulate subroutines and variables of the language defined by this Package shall not be considered part of this Package, but are the equivalent of input as in Paragraph 6, provided these subroutines do not change the language in any way that would cause it to fail the regression tests for the language.

8. Aggregation of this Package with a commercial distribution is always permitted provided that the use of this Package is embedded; that is, when no overt attempt is made to make this Package's interfaces visible to the end user of the commercial distribution. Such use shall not be construed as a distribution of this Package.

9. The name of the Copyright Holder may not be used to endorse or promote products derived from this software without specific prior written permission.

10. THIS PACKAGE IS PROVIDED "AS IS" AND WITHOUT ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, WITHOUT LIMITATION, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE.

The End

1.104 libpamg 1.1.8-3.6ubuntu2.18.04.6

1.104.1 Available under license :

Unless otherwise *explicitly* stated the following text describes the licensed conditions under which the contents of this Linux-PAM release may be distributed:

Redistribution and use in source and binary forms of Linux-PAM, with or without modification, are permitted provided that the following conditions are met:

1. Redistributions of source code must retain any existing copyright

notice, and this entire permission notice in its entirety,
including the disclaimer of warranties.

2. Redistributions in binary form must reproduce all prior and current copyright notices, this list of conditions, and the following disclaimer in the documentation and/or other materials provided with the distribution.
3. The name of any author may not be used to endorse or promote products derived from this software without their specific prior written permission.

ALTERNATIVELY, this product may be distributed under the terms of the GNU General Public License, in which case the provisions of the GNU GPL are required INSTEAD OF the above restrictions. (This clause is necessary due to a potential conflict between the GNU GPL and the restrictions contained in a BSD-style copyright.)

THIS SOFTWARE IS PROVIDED ``AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE AUTHOR(S) BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

Unless otherwise *explicitly* stated the following text describes the licensed conditions under which the contents of this libpamc release may be distributed:

Redistribution and use in source and binary forms of libpamc, with or without modification, are permitted provided that the following conditions are met:

1. Redistributions of source code must retain any existing copyright notice, and this entire permission notice in its entirety, including the disclaimer of warranties.
2. Redistributions in binary form must reproduce all prior and current copyright notices, this list of conditions, and the following disclaimer in the documentation and/or other materials provided with the distribution.

3. The name of any author may not be used to endorse or promote products derived from this software without their specific prior written permission.

ALTERNATIVELY, this product may be distributed under the terms of the GNU Library General Public License (LGPL), in which case the provisions of the GNU LGPL are required INSTEAD OF the above restrictions. (This clause is necessary due to a potential conflict between the GNU LGPL and the restrictions contained in a BSD-style copyright.)

THIS SOFTWARE IS PROVIDED ``AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE AUTHOR(S) BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

Patch for Ubuntu bug #399071

Display the contents of /etc/legal as part of the MOTD, the first time the user logs in, and set a flag in the user's homedir if possible to prevent repeat displays.

Authors: Dustin Kirkland <kirkland@canonical.com>

Upstream status: Ubuntu-specific, maybe submit to Debian

Index: pam.ubuntu/modules/pam_motd/pam_motd.c

--- pam.ubuntu.orig/modules/pam_motd/pam_motd.c

+++ pam.ubuntu/modules/pam_motd/pam_motd.c

@@ -73,6 +73,61 @@

close(fd);

}

+int display_legal(pam_handle_t *pamh)

+{

+ int retval = PAM_IGNORE, rc;

+ char *user = NULL;

+ char *dir = NULL;

```

+ char *flag = NULL;
+ struct passwd *pwd = NULL;
+ struct stat s;
+ int f;
+ /* Get the user name to determine if we need to print the disclaimer */
+ rc = pam_get_item(pamh, PAM_USER, &user);
+ if (rc == PAM_SUCCESS && user != NULL && *(const char *)user != '\0')
+ {
+     PAM_MODUTIL_DEF_PRIVS(privs);
+
+
+     /* Get the password entry */
+     pwd = pam_modutil_getpwnam (pamh, user);
+     if (pwd != NULL)
+     {
+         if (pam_modutil_drop_priv(pamh, &privs, pwd) {
+             pam_syslog(pamh, LOG_ERR,
+                 "Unable to change UID to %d temporarily\n",
+                 pwd->pw_uid);
+             retval = PAM_SESSION_ERR;
+             goto finished;
+         }
+
+         if (asprintf(&dir, "%s/.cache", pwd->pw_dir) == -1 || !dir)
+             goto finished;
+         if (asprintf(&flag, "%s/motd.legal-displayed", dir) == -1 || !flag)
+             goto finished;
+
+         if (stat(flag, &s) != 0)
+         {
+             display_file(pamh, "/etc/legal");
+             mkdir(dir, 0700);
+             f = open(flag, O_WRONLY|O_CREAT|O_EXCL,
+                 S_IRUSR|S_IWUSR|S_IRGRP|S_IROTH);
+             if (f>=0) close(f);
+         }
+
+     +finished:
+         if (pam_modutil_regain_priv(pamh,
+             &privs)) {
+             pam_syslog(pamh, LOG_ERR,
+                 "Unable to change UID back to %d\n", privs.old_uid);
+             retval = PAM_SESSION_ERR;
+         }
+
+         _pam_drop(flag);
+         _pam_drop(dir);
+     }

```

```

+ }
+ return retval;
+}
+
PAM_EXTERN
int pam_sm_open_session(pam_handle_t *pamh, int flags,
    int argc, const char **argv)
@@ -116,6 +171,9 @@
    /* Display the updated motd */
    display_file(pamh, motd_path);

+ /* Display the legal disclaimer only if necessary */
+ retval = display_legal(pamh);
+
    return retval;
}

```

This package was debianized by J.H.M. Dassen (Ray) jdassen@debian.org on Wed, 23 Sep 1998 20:29:32 +0200.

It was downloaded from <ftp://ftp.kernel.org/pub/linux/libs/pam/pre/>

Copyright (C) 1994, 1995, 1996 Olaf Kirch, <okir@monad.swb.de>
 Copyright (C) 1995 Wietse Venema
 Copyright (C) 1995, 2001-2008 Red Hat, Inc.
 Copyright (C) 1996-1999, 2000-2003, 2005 Andrew G. Morgan <morgan@kernel.org>
 Copyright (C) 1996, 1997, 1999 Cristian Gafton <gafton@redhat.com>
 Copyright (C) 1996, 1999 Theodore Ts'o
 Copyright (C) 1996 Alexander O. Yuriev
 Copyright (C) 1996 Elliot Lee
 Copyright (C) 1997 Philip W. Dalrymple <pwd@mdtsoft.com>
 Copyright (C) 1999 Jan Rkorajski
 Copyright (C) 1999 Ben Collins <bcollins@debian.org>
 Copyright (C) 2000-2001, 2003, 2005, 2007 Steve Langasek
 Copyright (C) 2003, 2005 IBM Corporation
 Copyright (C) 2003, 2006 SuSE Linux AG.
 Copyright (C) 2003 Nalin Dahyabhai <nalin@redhat.com>
 Copyright (C) 2005-2008 Thorsten Kukuk <kukuk@thkukuk.de>
 Copyright (C) 2005 Darren Tucker

Unless
 otherwise *explicitly* stated the following text describes the
 licensed conditions under which the contents of this Linux-PAM release
 may be distributed:

 Redistribution and use in source and binary forms of Linux-PAM, with
 or without modification, are permitted provided that the following

conditions are met:

1. Redistributions of source code must retain any existing copyright notice, and this entire permission notice in its entirety, including the disclaimer of warranties.
2. Redistributions in binary form must reproduce all prior and current copyright notices, this list of conditions, and the following disclaimer in the documentation and/or other materials provided with the distribution.
3. The name of any author may not be used to endorse or promote products derived from this software without their specific prior written permission.

ALTERNATIVELY, this product may be distributed under the terms of the GNU General Public License, in which case the provisions of the GNU GPL are required INSTEAD OF the above restrictions. (This clause is necessary due to a potential conflict between the GNU GPL and the restrictions contained in a BSD-style copyright.)

THIS SOFTWARE IS PROVIDED ``AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE AUTHOR(S) BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

On

Debian GNU/Linux systems, the complete text of the GNU General Public License can be found in `~/usr/share/common-licenses/GPL`.

1.105 libpammodulesbin 1.1.8-3.6ubuntu2.18.04.6

1.105.1 Available under license :

Unless otherwise **explicitly** stated the following text describes the licensed conditions under which the contents of this Linux-PAM release may be distributed:

Redistribution and use in source and binary forms of Linux-PAM, with or without modification, are permitted provided that the following conditions are met:

1. Redistributions of source code must retain any existing copyright notice, and this entire permission notice in its entirety, including the disclaimer of warranties.
2. Redistributions in binary form must reproduce all prior and current copyright notices, this list of conditions, and the following disclaimer in the documentation and/or other materials provided with the distribution.
3. The name of any author may not be used to endorse or promote products derived from this software without their specific prior written permission.

ALTERNATIVELY, this product may be distributed under the terms of the GNU General Public License, in which case the provisions of the GNU GPL are required INSTEAD OF the above restrictions. (This clause is necessary due to a potential conflict between the GNU GPL and the restrictions contained in a BSD-style copyright.)

THIS SOFTWARE IS PROVIDED ``AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE AUTHOR(S) BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

1.106 tar 1.29b-2ubuntu0.4

1.106.1 Available under license :

GNU GENERAL PUBLIC LICENSE
Version 3, 29 June 2007

Copyright (C) 2007 Free Software Foundation, Inc. <<http://fsf.org/>>
Everyone is permitted to copy and distribute verbatim copies

of this license document, but changing it is not allowed.

Preamble

The GNU General Public License is a free, copyleft license for software and other kinds of works.

The licenses for most software and other practical works are designed to take away your freedom to share and change the works. By contrast, the GNU General Public License is intended to guarantee your freedom to share and change all versions of a program--to make sure it remains free software for all its users. We, the Free Software Foundation, use the GNU General Public License for most of our software; it applies also to any other work released this way by its authors. You can apply it to your programs, too.

When we speak of free software, we are referring to freedom, not price. Our General Public Licenses are designed to make sure that you have the freedom to distribute copies of free software (and charge for them if you wish), that you receive source code or can get it if you want it, that you can change the software or use pieces of it in new free programs, and that you know you can do these things.

To protect your rights, we need to prevent others from denying you these rights or asking you to surrender the rights. Therefore, you have certain responsibilities if you distribute copies of the software, or if you modify it: responsibilities to respect the freedom of others.

For example, if you distribute copies of such a program, whether gratis or for a fee, you must pass on to the recipients the same freedoms that you received. You must make sure that they, too, receive or can get the source code. And you must show them these terms so they know their rights.

Developers that use the GNU GPL protect your rights with two steps:

(1) assert copyright on the software, and (2) offer you this License giving you legal permission to copy, distribute and/or modify it.

For the developers' and authors' protection, the GPL clearly explains that there is no warranty for this free software. For both users' and authors' sake, the GPL requires that modified versions be marked as changed, so that their problems will not be attributed erroneously to authors of previous versions.

Some devices are designed to deny users access to install or run modified versions of the software inside them, although the manufacturer

can do so. This is fundamentally incompatible with the aim of protecting users' freedom to change the software. The systematic pattern of such abuse occurs in the area of products for individuals to use, which is precisely where it is most unacceptable. Therefore, we have designed this version of the GPL to prohibit the practice for those products. If such problems arise substantially in other domains, we stand

ready to extend this provision to those domains in future versions of the GPL, as needed to protect the freedom of users.

Finally, every program is threatened constantly by software patents. States should not allow patents to restrict development and use of software on general-purpose computers, but in those that do, we wish to avoid the special danger that patents applied to a free program could make it effectively proprietary. To prevent this, the GPL assures that patents cannot be used to render the program non-free.

The precise terms and conditions for copying, distribution and modification follow.

TERMS AND CONDITIONS

0. Definitions.

"This License" refers to version 3 of the GNU General Public License.

"Copyright" also means copyright-like laws that apply to other kinds of works, such as semiconductor masks.

"The Program" refers to any copyrightable work licensed under this License. Each licensee is addressed as "you". "Licensees" and "recipients" may be individuals or organizations.

To "modify" a work means to copy from or adapt all or part of the work in a fashion requiring copyright permission, other than the making of an exact copy. The resulting work is called a "modified version" of the earlier work or a work "based on" the earlier work.

A "covered work" means either the unmodified Program or a work based on the Program.

To "propagate" a work means to do anything with it that, without permission, would make you directly or secondarily liable for infringement under applicable copyright law, except executing it on a computer or modifying a private copy. Propagation includes copying, distribution (with or without modification), making available to the public, and in some countries other activities as well.

To "convey" a work means any kind of propagation that enables other parties to make or receive copies. Mere interaction with a user through a computer network, with no transfer of a copy, is not conveying.

An interactive user interface displays "Appropriate Legal Notices" to the extent that it includes a convenient and prominently visible feature that (1) displays an appropriate copyright notice, and (2) tells the user that there is no warranty for the work (except to the extent that warranties are provided), that licensees may convey the work under this License, and how to view a copy of this License. If the interface presents a list of user commands or options, such as a menu, a prominent item in the list meets this criterion.

1. Source Code.

The "source code" for a work means the preferred form of the work for making modifications to it. "Object code" means any non-source form of a work.

A "Standard Interface" means an interface that either is an official standard defined by a recognized standards body, or, in the case of interfaces specified for a particular programming language, one that is widely used among developers working in that language.

The

"System Libraries" of an executable work include anything, other than the work as a whole, that (a) is included in the normal form of packaging a Major Component, but which is not part of that Major Component, and (b) serves only to enable use of the work with that Major Component, or to implement a Standard Interface for which an implementation is available to the public in source code form. A "Major Component", in this context, means a major essential component (kernel, window system, and so on) of the specific operating system (if any) on which the executable work runs, or a compiler used to produce the work, or an object code interpreter used to run it.

The "Corresponding Source" for a work in object code form means all the source code needed to generate, install, and (for an executable work) run the object code and to modify the work, including scripts to control those activities. However, it does not include the work's System Libraries, or general-purpose tools or generally available free programs which are used unmodified in performing those activities but which are not part of the work. For example, Corresponding Source includes interface definition files associated with source files for the work, and the source code for shared libraries and dynamically

linked subprograms that the work is specifically designed to require, such as by intimate data communication or control flow between those subprograms and other parts of the work.

The Corresponding Source need not include anything that users can regenerate automatically from other parts of the Corresponding Source.

The Corresponding Source for a work in source code form is that same work.

2. Basic Permissions.

All rights granted under this License are granted for the term of copyright on the Program, and are irrevocable provided the stated conditions are met. This License explicitly affirms your unlimited permission to run the unmodified Program. The output from running a covered work is covered

by this License only if the output, given its content, constitutes a covered work. This License acknowledges your rights of fair use or other equivalent, as provided by copyright law.

You may make, run and propagate covered works that you do not convey, without conditions so long as your license otherwise remains in force. You may convey covered works to others for the sole purpose of having them make modifications exclusively for you, or provide you with facilities for running those works, provided that you comply with the terms of this License in conveying all material for which you do not control copyright. Those thus making or running the covered works for you must do so exclusively on your behalf, under your direction and control, on terms that prohibit them from making any copies of your copyrighted material outside their relationship with you.

Conveying under any other circumstances is permitted solely under the conditions stated below. Sublicensing is not allowed; section 10 makes it unnecessary.

3. Protecting Users' Legal Rights From Anti-Circumvention Law.

No covered work shall be deemed part of an effective technological measure under any applicable law fulfilling obligations under article 11 of the WIPO copyright treaty adopted on 20 December 1996, or similar laws prohibiting or restricting circumvention of such measures.

When you convey a covered work, you waive any legal power to forbid circumvention of technological measures to the extent such circumvention

is effected by exercising rights under this License with respect to the covered work, and you disclaim any intention to limit operation or modification of the work as a means of enforcing, against the work's users, your or third parties' legal rights to forbid circumvention of technological measures.

4. Conveying Verbatim Copies.

You may convey verbatim copies of the Program's source code as you receive it, in any medium, provided that you conspicuously and appropriately publish on each copy an appropriate copyright notice; keep intact all notices stating that this License and any non-permissive terms added in accord with section 7 apply to the code; keep intact all notices of the absence of any warranty; and give all recipients a copy of this License along with the Program.

You may charge any price or no price for each copy that you convey, and you may offer support or warranty protection for a fee.

5. Conveying Modified Source Versions.

You may convey a work based on the Program, or the modifications to produce it from the Program, in the form of source code under the terms of section 4, provided that you also meet all of these conditions:

- a) The work must carry prominent notices stating that you modified it, and giving a relevant date.
- b) The work must carry prominent notices stating that it is released under this License and any conditions added under section 7. This requirement modifies the requirement in section 4 to "keep intact all notices".
- c) You must license the entire work, as a whole, under this License to anyone who comes into possession of a copy. This License will therefore apply, along with any applicable section 7 additional terms, to the whole of the work, and all its parts, regardless of how they are packaged. This License gives no permission to license the work in any other way, but it does not invalidate such permission if you have separately received it.
- d) If the work has interactive user interfaces, each must display Appropriate Legal Notices; however, if the Program has interactive interfaces that do not display Appropriate Legal Notices, your work need not make them do so.

A compilation of a covered work with other separate and independent works, which are not by their nature extensions of the covered work, and which are not combined with it such as to form a larger program, in or on a volume of a storage or distribution medium, is called an "aggregate" if the compilation and its resulting copyright are not used to limit the access or legal rights of the compilation's users beyond what the individual works permit. Inclusion of a covered work in an aggregate does not cause this License to apply to the other parts of the aggregate.

6. Conveying Non-Source Forms.

You may convey a covered work in object code form under the terms of sections 4 and 5, provided that you also convey the machine-readable Corresponding Source under the terms of this License, in one of these ways:

- a) Convey the object code in, or embodied in, a physical product (including a physical distribution medium), accompanied by the Corresponding Source fixed on a durable physical medium customarily used for software interchange.
- b) Convey the object code in, or embodied in, a physical product (including a physical distribution medium), accompanied by a written offer, valid for at least three years and valid for as long as you offer spare parts or customer support for that product model, to give anyone who possesses the object code either (1) a copy of the Corresponding Source for all the software in the product that is covered by this License, on a durable physical medium customarily used for software interchange, for a price no more than your reasonable cost of physically performing this conveying of source, or (2) access to copy the Corresponding Source from a network server at no charge.
- c) Convey individual copies of the object code with a copy of the written offer to provide the Corresponding Source. This alternative is allowed only occasionally and noncommercially, and only if you received the object code with such an offer, in accord with subsection 6b.
- d) Convey the object code by offering access from a designated place (gratis or for a charge), and offer equivalent access to the Corresponding Source in the same way through the same place at no further charge. You need not require recipients to copy the Corresponding Source along with the object code. If the place to

copy the object code is a network server, the Corresponding Source may be on a different server (operated by you or a third party) that supports equivalent copying facilities, provided you maintain clear directions next to the object code saying where to find the Corresponding Source. Regardless of what server hosts the Corresponding Source, you remain obligated to ensure that it is available for as long as needed to satisfy these requirements.

e) Convey the object code using peer-to-peer transmission, provided you inform other peers where the object code and Corresponding Source of the work are being offered to the general public at no charge under subsection 6d.

A separable portion of the object code, whose source code is excluded from the Corresponding Source as a System Library, need not be included in conveying the object code work.

A "User Product" is either (1) a "consumer product", which means any tangible personal property which is normally used for personal, family, or household purposes, or (2) anything designed or sold for incorporation into a dwelling. In determining whether a product is a consumer product, doubtful cases shall be resolved in favor of coverage. For a particular product received by a particular user, "normally used" refers to a typical or common use of that class of product, regardless of the status of the particular user or of the way in which the particular user actually uses, or expects or is expected to use, the product. A product is a consumer product regardless of whether the product has substantial commercial, industrial or non-consumer uses, unless such uses represent the only significant mode of use of the product.

"Installation Information" for a User Product means any methods, procedures, authorization keys, or other information required to install and execute modified versions of a covered work in that User Product from a modified version of its Corresponding Source. The information must suffice to ensure that the continued functioning of the modified object code is in no case prevented or interfered with solely because modification has been made.

If you convey an object code work under this section in, or with, or specifically for use in, a User Product, and the conveying occurs as part of a transaction in which the right of possession and use of the User Product is transferred to the recipient in perpetuity or for a fixed term (regardless of how the transaction is characterized), the Corresponding Source conveyed under this section must be accompanied by the Installation Information. But this requirement does not apply if neither you nor any third party retains the ability to install

modified object code on the User Product (for example, the work has been installed in ROM).

The requirement to provide Installation Information does not include a requirement to continue to provide support service, warranty, or updates for a work that has been modified or installed by the recipient, or for the User Product in which it has been modified or installed. Access to a network may be denied when the modification itself materially and adversely affects the operation of the network or violates the rules and protocols for communication across the network.

Corresponding Source conveyed, and Installation Information provided, in accord with this section must be in a format that is publicly documented (and with an implementation available to the public in source code form), and must require no special password or key for unpacking, reading or copying.

7. Additional Terms.

"Additional permissions" are terms that supplement the terms of this License by making exceptions from one or more of its conditions. Additional permissions that are applicable to the entire Program shall be treated as though they were included in this License, to the extent that they are valid under applicable law. If additional permissions apply only to part of the Program, that part may be used separately under those permissions, but the entire Program remains governed by this License without regard to the additional permissions.

When you convey a copy of a covered work, you may at your option remove any additional permissions from that copy, or from any part of it. (Additional permissions may be written to require their own removal in certain cases when you modify the work.) You may place additional permissions on material, added by you to a covered work, for which you have or can give appropriate copyright permission.

Notwithstanding any other provision of this License, for material you add to a covered work, you may (if authorized by the copyright holders of that material) supplement the terms of this License with terms:

- a) Disclaiming warranty or limiting liability differently from the terms of sections 15 and 16 of this License; or
- b) Requiring preservation of specified reasonable legal notices or author attributions in that material or in the Appropriate Legal Notices displayed by works containing it; or

- c) Prohibiting misrepresentation of the origin of that material, or requiring that modified versions of such material be marked in reasonable ways as different from the original version; or
- d) Limiting the use for publicity purposes of names of licensors or authors of the material; or
- e) Declining to grant rights under trademark law for use of some trade names, trademarks, or service marks; or
- f) Requiring indemnification of licensors and authors of that material by anyone who conveys the material (or modified versions of it) with contractual assumptions of liability to the recipient, for any liability that these contractual assumptions directly impose on those licensors and authors.

All other non-permissive additional terms are considered "further restrictions" within the meaning of section 10. If the Program as you received it, or any part of it, contains a notice stating that it is governed by this License along with a term that is a further restriction, you may remove that term. If a license document contains a further restriction but permits relicensing or conveying under this License, you may add to a covered work material governed by the terms of that license document, provided that the further restriction does not survive such relicensing or conveying.

If you add terms to a covered work in accord with this section, you must place, in the relevant source files, a statement of the additional terms that apply to those files, or a notice indicating where to find the applicable terms.

Additional terms, permissive or non-permissive, may be stated in the form of a separately written license, or stated as exceptions; the above requirements apply either way.

8. Termination.

You may not propagate or modify a covered work except as expressly provided under this License. Any attempt otherwise to propagate or modify it is void, and will automatically terminate your rights under this License (including any patent licenses granted under the third paragraph of section 11).

However, if you cease all violation of this License, then your license from a particular copyright holder is reinstated (a)

provisionally, unless and until the copyright holder explicitly and finally terminates your license, and (b) permanently, if the copyright holder fails to notify you of the violation by some reasonable means prior to 60 days after the cessation.

Moreover, your license from a particular copyright holder is reinstated permanently if the copyright holder notifies you of the violation by some reasonable means, this is the first time you have received notice of violation of this License (for any work) from that copyright holder, and you cure the violation prior to 30 days after your receipt of the notice.

Termination of your rights under this section does not terminate the licenses of parties who have received copies or rights from you under this License. If your rights have been terminated and not permanently reinstated, you do not qualify to receive new licenses for the same material under section 10.

9. Acceptance Not Required for Having Copies.

You are not required to accept this License in order to receive or run a copy of the Program. Ancillary propagation of a covered work occurring solely as a consequence of using peer-to-peer transmission to receive a copy likewise does not require acceptance. However, nothing other than this License grants you permission to propagate or modify any covered work. These actions infringe copyright if you do not accept this License. Therefore, by modifying or propagating a covered work, you indicate your acceptance of this License to do so.

10. Automatic Licensing of Downstream Recipients.

Each time you convey a covered work, the recipient automatically receives a license from the original licensors, to run, modify and propagate that work, subject to this License. You are not responsible for enforcing compliance by third parties with this License.

An "entity transaction" is a transaction transferring control of an organization, or substantially all assets of one, or subdividing an organization, or merging organizations. If propagation of a covered work results from an entity transaction, each party to that transaction who receives a copy of the work also receives whatever licenses to the work the party's predecessor in interest had or could give under the previous paragraph, plus a right to possession of the Corresponding Source of the work from the predecessor in interest, if the predecessor has it or can get it with reasonable efforts.

You may not impose any further restrictions on the exercise of the rights granted or affirmed under this License. For example, you may not impose a license fee, royalty, or other charge for exercise of rights granted under this License, and you may not initiate litigation (including a cross-claim or counterclaim in a lawsuit) alleging that any patent claim is infringed by making, using, selling, offering for sale, or importing the Program or any portion of it.

11. Patents.

A "contributor" is a copyright holder who authorizes use under this License of the Program or a work on which the Program is based. The work thus licensed is called the contributor's "contributor version".

A contributor's "essential patent claims" are all patent claims owned or controlled by the contributor, whether already acquired or hereafter acquired, that would be infringed by some manner, permitted by this License, of making, using, or selling its contributor version, but do not include claims that would be infringed only as a consequence of further modification of the contributor version. For purposes of this definition, "control" includes the right to grant patent sublicenses in a manner consistent with the requirements of this License.

Each contributor grants you a non-exclusive, worldwide, royalty-free patent license under the contributor's essential patent claims, to make, use, sell, offer for sale, import and otherwise run, modify and propagate the contents of its contributor version.

In the following three paragraphs, a "patent license" is any express agreement or commitment, however denominated, not to enforce a patent (such as an express permission to practice a patent or covenant not to sue for patent infringement). To "grant" such a patent license to a party means to make such an agreement or commitment not to enforce a patent against the party.

If you convey a covered work, knowingly relying on a patent license, and the Corresponding Source of the work is not available for anyone to copy, free of charge and under the terms of this License, through a publicly available network server or other readily accessible means, then you must either (1) cause the Corresponding Source to be so available, or (2) arrange to deprive yourself of the benefit of the patent license for this particular work, or (3) arrange, in a manner consistent with the requirements of this License, to extend the patent license to downstream recipients. "Knowingly relying" means you have

actual knowledge that, but for the patent license, your conveying the covered work in a country, or your recipient's use of the covered work in a country, would infringe one or more identifiable patents in that country that you have reason to believe are valid.

If, pursuant to or in connection with a single transaction or arrangement, you convey, or propagate by procuring conveyance of, a covered work, and grant a patent license to some of the parties receiving the covered work authorizing them to use, propagate, modify or convey a specific copy of the covered work, then the patent license you grant is automatically extended to all recipients of the covered work and works based on it.

A patent license is "discriminatory" if it does not include within the scope of its coverage, prohibits the exercise of, or is conditioned on the non-exercise of one or more of the rights that are specifically granted under this License. You may not convey a covered work if you are a party to an arrangement with a third party that is in the business of distributing software, under which you make payment to the third party based on the extent of your activity of conveying the work, and under which the third party grants, to any of the parties who would receive the covered work from you, a discriminatory patent license (a) in connection with copies of the covered work conveyed by you (or copies made from those copies), or (b) primarily for and in connection with specific products or compilations that contain the covered work, unless you entered into that arrangement, or that patent license was granted, prior to 28 March 2007.

Nothing in this License shall be construed as excluding or limiting any implied license or other defenses to infringement that may otherwise be available to you under applicable patent law.

12. No Surrender of Others' Freedom.

If conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot convey a covered work so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not convey it at all. For example, if you agree to terms that obligate you to collect a royalty for further conveying from those to whom you convey the Program, the only way you could satisfy both those terms and this License would be to refrain entirely from conveying the Program.

13. Use with the GNU Affero General Public License.

Notwithstanding any other provision of this License, you have permission to link or combine any covered work with a work licensed under version 3 of the GNU Affero General Public License into a single combined work, and to convey the resulting work. The terms of this License will continue to apply to the part which is the covered work, but the special requirements of the GNU Affero General Public License, section 13, concerning interaction through a network will apply to the combination as such.

14. Revised Versions of this License.

The Free Software Foundation may publish revised and/or new versions of the GNU General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Program specifies that a certain numbered version of the GNU General Public License "or any later version" applies to it, you have the option of following the terms and conditions either of that numbered version or of any later version published by the Free Software Foundation. If the Program does not specify a version number of the GNU General Public License, you may choose any version ever published by the Free Software Foundation.

If the Program specifies that a proxy can decide which future versions of the GNU General Public License can be used, that proxy's public statement of acceptance of a version permanently authorizes you to choose that version for the Program.

Later license versions may give you additional or different permissions. However, no additional obligations are imposed on any author or copyright holder as a result of your choosing to follow a later version.

15. Disclaimer of Warranty.

THERE IS NO WARRANTY FOR THE PROGRAM, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE PROGRAM "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE PROGRAM IS WITH YOU. SHOULD THE PROGRAM PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

16. Limitation of Liability.

IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MODIFIES AND/OR CONVEYS THE PROGRAM AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE PROGRAM (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE PROGRAM TO OPERATE WITH ANY OTHER PROGRAMS), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

17.

Interpretation of Sections 15 and 16.

If the disclaimer of warranty and limitation of liability provided above cannot be given local legal effect according to their terms, reviewing courts shall apply local law that most closely approximates an absolute waiver of all civil liability in connection with the Program, unless a warranty or assumption of liability accompanies a copy of the Program in return for a fee.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Programs

If you develop a new program, and you want it to be of the greatest possible use to the public, the best way to achieve this is to make it free software which everyone can redistribute and change under these terms.

To do so, attach the following notices to the program. It is safest to attach them to the start of each source file to most effectively state the exclusion of warranty; and each file should have at least the "copyright" line and a pointer to where the full notice is found.

```
<one line to give the program's name and a brief idea of what it does.>  
Copyright (C) <year> <name of author>
```

This program is free software: you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation, either version 3 of the License, or (at your option) any later version.

This program is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details.

You should have received a copy of the GNU General Public License along with this program. If not, see <http://www.gnu.org/licenses/>.

Also add information on how to contact you by electronic and paper mail.

If the program does terminal interaction, make it output a short notice like this when it starts in an interactive mode:

```
<program> Copyright (C) <year> <name of author>
This program comes with ABSOLUTELY NO WARRANTY; for details type `show w'.
This is free software, and you are welcome to redistribute it
under certain conditions; type `show c' for details.
```

The hypothetical commands `show w' and `show c' should show the appropriate parts of the General Public License. Of course, your program's commands might be different; for a GUI interface, you would use an "about box".

You should also get your employer (if you work as a programmer) or school, if any, to sign a "copyright disclaimer" for the program, if necessary. For more information on this, and how to apply and follow the GNU GPL, see <http://www.gnu.org/licenses/>.

The GNU General Public License does not permit incorporating your program into proprietary programs. If your program is a subroutine library, you may consider it more useful to permit linking proprietary applications with the library. If this is what you want to do, use the GNU Lesser General Public License instead of this License. But first, please read <http://www.gnu.org/philosophy/why-not-lgpl.html>.

1.107 libnettle6 3.4.1-0ubuntu0.18.04.1

1.107.1 Available under license :

Format: <https://www.debian.org/doc/packaging-manuals/copyright-format/1.0/>

Upstream-Name: Nettle

Upstream-Contact: Niels Mller <nisse@lysator.liu.se>

Source: <http://www.lysator.liu.se/~nisse/nettle/>

Copyright: 2001-2011 Niels Mller

Some parts are Copyright the Free Software Foundation and various people. See below and source code comments for details.

License: LGPL-2.1+

Comment:

Nettle is distributed under the GNU Lesser General Public License (LGPL). A few of the individual files are in the public domain. To find the current status of particular files, you have to read the

copyright notices at the top of the files.

.
A list of the supported algorithms, their origins and licenses (from the manual):

.
AES

The implementation of the AES cipher (also known as rijndael) is written by Rafael Sevilla. Assembler for x86 by Rafael Sevilla and Niels Miller, Sparc assembler by Niels Miller. Released under the LGPL.

.
ARCFOUR

The implementation of the ARCFOUR (also known as RC4) cipher is written by Niels Miller. Released under the LGPL.

.
ARCTWO

The implementation of the ARCTWO (also known as RC2) cipher is written by Nikos Mavroyanopoulos and modified by Werner Koch and Simon Josefsson. Released under the LGPL.

.
BLOWFISH

The implementation of the BLOWFISH cipher is written by Werner Koch, copyright owned by the Free Software Foundation. Also hacked by Simon Josefsson and Niels Miller. Released under the LGPL.

.
CAMELLIA

The C implementation is by Nippon Telegraph and Telephone Corporation (NTT), heavily modified by Niels Miller. Assembler for x86 and x86_64 by Niels Miller. Released under the LGPL.

.
CAST128

The implementation of the CAST128 cipher is written by Steve Reid. Released into the public domain.

.
DES

The implementation of the DES cipher is written by Dana L. How, and released under the LGPL.

.
MD2

The implementation of MD2 is written by Andrew Kuchling, and hacked some by Andreas Sigfridsson and Niels Miller. Python Cryptography Toolkit license (essentially public domain).

.
MD4

This is almost the same code as for MD5 below, with modifications by Marcus Comstedt. Released into the public domain.

.

MD5

The implementation of the MD5 message digest is written by Colin Plumb. It has been hacked some more by Andrew Kuchling and Niels Miller. Released into the public domain.

.

SERPENT

The implementation of the SERPENT is based on the code in libgcrypt, copyright owned by the Free Software Foundation. Adapted to Nettle by Simon Josefsson and heavily modified by Niels Miller. Assembly for x86_64 by Niels Miller. Released under the LGPL.

.

SHA1

The C implementation of the SHA1 message digest is written by Peter Gutmann, and hacked some more by Andrew Kuchling and Niels Miller. Released into the public domain. Assembler for x86 by Niels Miller, released under the LGPL.

.

SHA224, SHA256, SHA384, and SHA512

Written by Niels Miller, using Peter Gutmann's SHA1 code as a model. Released under the LGPL.

.

TWOFISH

The implementation of the TWOFISH cipher is written by Ruud de Rooij. Released under the LGPL.

.

RSA

Written by Niels Miller, released under the LGPL. Uses the GMP library for bignum operations.

.

DSA

Written by Niels Miller, released under the LGPL. Uses the GMP library for bignum operations.

Files: *

Copyright: 2001-2011 Niels Miller

License: LGPL-2.1+

Files: aes-set-*

Copyright: 2000, 2001, 2002 Rafael R. Sevilla, Niels Miller

License: LGPL-2.1+

Files: arctwo*

Copyright: 2003 Nikos Mavroyanopoulos

2004 Simon Josefsson

2004 Free Software Foundation, Inc.

2002, 2004 Niels Mller
License: LGPL-2.1+

Files: base64.h base64-meta.c
Copyright: 2002 Dan Egnor
2002 Niels Mller
License: LGPL-2.1+

Files: blowfish.c
Copyright: 1998, 2001, 2002,
2003 Free Software Foundation, Inc.
2010 Simon Josefsson
License: LGPL-2.1+

Files: blowfish.h
Copyright: 1998, 2001 Free Software Foundation, Inc.
1998, 2001 Ray Dassen
1998, 2001 Niels Mller
License: LGPL-2.1+

Files: camellia-table.c camellia-crypt-internal.c
Copyright: 2006, 2007 NTT (Nippon Telegraph and Telephone Corporation)
2010 Niels Mller
License: LGPL-2.1+

Files: der2dsa.c
Copyright: 2005, 2009 Niels Mller
2009 Magnus Holmgren
License: LGPL-2.1+

Files: desCode.h descode.README desdata.c desinfo.c
Copyright: 2002 Dana L. How
License: LGPL-2+

This program is free software; you can redistribute it and/or modify
it under the terms of the GNU Library General Public License as published by
the Free Software Foundation; either version 2 of the License, or
(at your option) any later version.

.

This program is distributed in the hope that it will be useful,
but WITHOUT ANY WARRANTY; without even the implied warranty
of
MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
GNU Library General Public License for more details.

.

You should have received a copy of the GNU Library General Public License
along with this program; if not, write to the Free Software
Foundation, Inc., 51 Franklin St, Fifth Floor, Boston, MA 02110-1301, USA.

.

On Debian GNU/Linux systems, the complete text of the GNU Library
General Public License, version 2, can be found in
/usr/share/common-licenses/LGPL-2.

Files: des.c des.h

Copyright: 1992 Dana L. How
1997, 2001 Niels Mller

License: LGPL-2.1+

Files: gcm.c gcm.h

Copyright: 2011 Katholieke Universiteit Leuven
2011 Niels Mller

License: LGPL-2.1+

Files: md2.c

Copyright: ? Andrew Kuchling
2003 Andreas Sigfridsson
2003 Niels Mller

License: LGPL-2.1+

Files: md4.c

Copyright: 2003 Marcus Comstedt
2003 Niels Mller

License: LGPL-2.1+

Files: md5.c md5-compress.c

Copyright: Colin Plumb, Andrew
Kuchling
2001 Niels Mller

License: LGPL-2.1+

Files: memxor.c

Copyright: 1991,1993, 1995 Free Software Foundation, Inc.
2010 Niels Mller

License: LGPL-2.1+

Files: ripemd160.c ripemd160-compress.c

Copyright: 1998, 2001, 2002, 2003 Free Software Foundation, Inc.
License: LGPL-2.1+

Files: ripemd160-meta.c ripemd160.h

Copyright: 2011 Andres Mejia
License: LGPL-2.1+

Files: serpent-encrypt.c serpent-decrypt.c serpent-set-key.c

Copyright: 1998 Ross Anderson, Eli Biham, Lars Knudsen
2003, 2004, 2005 Free Software Foundation, Inc.
2010, 2011 Simon Josefsson

2011 Niels Mller

License: LGPL-2.1+

Files: sha*

Copyright: 2001, 2004 Peter Gutmann, Andrew Kuchling, Niels Mller

License: LGPL-2.1+

Files: twofish*

Copyright: 1999 Ruud de Rooij <ruud@debian.org>

1999 J.H.M. Dassen (Ray) <jdassen@wi.LeidenUniv.nl>

2001 Niels Mller

License: LGPL-2.1+

Files: dsa2sexp.c

Copyright: 2002, 2009 Niels Mller

2009 Magnus Holmgren

License: LGPL-2.1+

Files: testsuite/des-compat-test.c

Copyright: 1995-1997 Eric Young (eay@cryptsoft.com)

License: other

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

1. Redistributions of source code must retain the copyright notice, this list of conditions and the following disclaimer.
2. Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.
3. All advertising materials mentioning features or use of this software must display the following acknowledgement:
"This product includes cryptographic software written by
Eric Young (eay@cryptsoft.com)"
The word 'cryptographic' can be left out if the routines from the library being used are not cryptographic related :-).
4. If you include
any Windows specific code (or a derivative thereof) from
the apps directory (application code) you must include an acknowledgement:
"This product includes software written by Tim Hudson (tjh@cryptsoft.com)"

THIS SOFTWARE IS PROVIDED BY ERIC YOUNG ``AS IS'' AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE AUTHOR OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION)

HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

Files: tools/pkcs1-conv.c

Copyright: 2005, 2009

Niels Mller

2009 Magnus Holmgren

License: LGPL-2.1+

Files: x86*/aes-*-internal.asm

Copyright: 2001, 2002, 2005, 2008 Rafael R. Sevilla

2001, 2002, 2005, 2008 Niels Mller

License: LGPL-2.1+

Files: tools/getopt*

Copyright: 1987-2001 Free Software Foundation, Inc.

License: GPL-2+

Files: config.guess config.sub

Copyright: 1992-2003 Free Software Foundation, Inc.

License: GPL-2+ with Autoconf exception

As a special exception to the GNU General Public License, if you distribute this file as part of a program that contains a configuration script generated by Autoconf, you may include it under the same distribution terms that you use for the rest of that program.

Files: debian/*

Copyright: none

License: public-domain

I believe that most files in debian/ hardly contains any creative expression eligible for copyright.

Files: debian/sexp-conv.1

Copyright: 2002 Timshel Knoll <timshel@debian.org>

2007 Magnus Holmgren

License: GPL-2

This program

is free software; you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation; version 2 dated June. 1991.

.

This program is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details.

.

You should have received a copy of the GNU General Public License along with this program; if not, write to the Free Software Foundation, Inc., 51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA.

.
On Debian GNU/Linux systems, the complete text of the GNU General Public License, version 2, can be found in
`/usr/share/common-licenses/GPL-2`.

Comment:

This manpage was copied from the lsh-utils package. Timshel didn't explicitly select a license for his packaging work, but I think that it can be considered released under the same license as LSH itself.

Files:

`debian/pkcs1-conv.1` `debian/nettle-lfib-stream.1`

Copyright: 2007 Magnus Holmgren

License: GAP

Copying and distribution of this file, with or without modification, are permitted in any medium without royalty provided the copyright notice and this notice are preserved.

License: LGPL-2.1+

The nettle library is free software; you can redistribute it and/or modify it under the terms of the GNU Lesser General Public License as published by the Free Software Foundation; either version 2.1 of the License, or (at your option) any later version.

.
The nettle library is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU Lesser General Public License for more details.

.
You should have received a copy of the GNU Lesser General Public License along with this library; if not, write to the Free Software Foundation, Inc., 51 Franklin St, Fifth Floor, Boston, MA 02110-1301 USA

.
On Debian GNU/Linux systems, the complete text of the newest version of the GNU Lesser General Public License can be found in
`/usr/share/common-licenses/LGPL`.

License: GPL-2+

This program is free software; you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation; either version 2 of the License, or (at your option) any later version.

.
This program is distributed in the hope that it will be useful,

but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details.

You should have received a copy of the GNU General Public License along with this program; if not, write to the Free Software Foundation, Inc., 51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA.

On Debian GNU/Linux systems, the complete text of the newest version of the GNU General Public License can be found in `/usr/share/common-licenses/GPL`.

GNU GENERAL PUBLIC LICENSE
Version 2, June 1991

Copyright (C) 1989, 1991 Free Software Foundation, Inc.,
51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA
Everyone is permitted to copy and distribute verbatim copies
of this license document, but changing it is not allowed.

Preamble

The licenses for most software are designed to take away your freedom to share and change it. By contrast, the GNU General Public License is intended to guarantee your freedom to share and change free software--to make sure the software is free for all its users. This General Public License applies to most of the Free Software Foundation's software and to any other program whose authors commit to using it. (Some other Free Software Foundation software is covered by the GNU Lesser General Public License instead.) You can apply it to your programs, too.

When we speak of free software, we are referring to freedom, not price.

Our General Public Licenses are designed to make sure that you have the freedom to distribute copies of free software (and charge for this service if you wish), that you receive source code or can get it if you want it, that you can change the software or use pieces of it in new free programs; and that you know you can do these things.

To protect your rights, we need to make restrictions that forbid anyone to deny you these rights or to ask you to surrender the rights. These restrictions translate to certain responsibilities for you if you distribute copies of the software, or if you modify it.

For example, if you distribute copies of such a program, whether gratis or for a fee, you must give the recipients all the rights that

you have. You must make sure that they, too, receive or can get the source code. And you must show them these terms so they know their rights.

We protect your rights with two steps: (1) copyright the software, and (2) offer you this license which gives you legal permission to copy, distribute and/or modify the software.

Also, for each author's protection and ours, we want to make certain that everyone understands that there is no warranty for this free software. If the software is modified by someone else and passed on, we want its recipients to know that what they have is not the original, so that any problems introduced by others will not reflect on the original authors' reputations.

Finally, any free program is threatened constantly by software patents. We wish to avoid the danger that redistributors of a free program will individually obtain patent licenses, in effect making the program proprietary. To prevent this, we have made it clear that any patent must be licensed for everyone's free use or not licensed at all.

The precise terms and conditions for copying, distribution and modification follow.

GNU GENERAL PUBLIC LICENSE TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

0. This License applies to any program or other work which contains a notice placed by the copyright holder saying it may be distributed under the terms of this General Public License. The "Program", below, refers to any such program or work, and a "work based on the Program" means either the Program or any derivative work under copyright law: that is to say, a work containing the Program or a portion of it, either verbatim or with modifications and/or translated into another language. (Hereinafter, translation is included without limitation in the term "modification".) Each licensee is addressed as "you".

Activities other than copying, distribution and modification are not covered by this License; they are outside its scope. The act of running the Program is not restricted, and the output from the Program is covered only if its contents constitute a work based on the Program (independent of having been made by running the Program). Whether that is true depends on what the Program does.

1. You may copy and distribute verbatim copies of the Program's source code as you receive it, in any medium, provided that you

conspicuously and appropriately publish on each copy an appropriate copyright notice and disclaimer of warranty; keep intact all the notices that refer to this License and to the absence of any warranty; and give any other recipients of the Program a copy of this License along with the Program.

You may charge a fee for the physical act of transferring a copy, and you may at your option offer warranty protection in exchange for a fee.

2. You may modify your copy or copies of the Program or any portion of it, thus forming a work based on the Program, and copy and distribute such modifications or work under the terms of Section 1 above, provided that you also meet all of these conditions:

a) You must cause the modified files to carry prominent notices stating that you changed the files and the date of any change.

b) You must cause any work that you distribute or publish, that in whole or in part contains or is derived from the Program or any part thereof, to be licensed as a whole at no charge to all third parties under the terms of this License.

c) If the modified program normally reads commands interactively when run, you must cause it, when started running for such interactive use in the most ordinary way, to print or display an announcement including an appropriate copyright notice and a notice that there is no warranty (or else, saying that you provide a warranty) and that users may redistribute the program under these conditions, and telling the user how to view a copy of this License. (Exception: if the Program itself is interactive but does not normally print such an announcement, your work based on the Program is not required to print an announcement.)

These requirements apply to the modified work as a whole. If identifiable sections of that work are not derived from the Program, and can be reasonably considered independent and separate works in themselves, then this License, and its terms, do not apply to those sections when you distribute them as separate works. But when you distribute the same sections as part of a whole which is a work based on the Program, the distribution of the whole must be on the terms of this License, whose permissions for other licensees extend to the entire whole, and thus to each and every part regardless of who wrote it.

Thus, it is not the intent of this section to claim rights or contest your rights to work written entirely by you; rather, the intent is to exercise the right to control the distribution of derivative or

collective works based on the Program.

In addition, mere aggregation of another work not based on the Program with the Program (or with a work based on the Program) on a volume of a storage or distribution medium does not bring the other work under the scope of this License.

3. You may copy and distribute the Program (or a work based on it, under Section 2) in object code or executable form under the terms of Sections 1 and 2 above provided that you also do one of the following:

- a) Accompany it with the complete corresponding machine-readable source code, which must be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange; or,
- b) Accompany it with a written offer, valid for at least three years, to give any third party, for a charge no more than your cost of physically performing source distribution, a complete machine-readable copy of the corresponding source code, to be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange; or,
- c) Accompany it with the information you received as to the offer to distribute corresponding source code. (This alternative is allowed only for noncommercial distribution and only if you received the program in object code or executable form with such an offer, in accord with Subsection b above.)

The source code for a work means the preferred form of the work for making modifications to it. For an executable work, complete source code means all the source code for all modules it contains, plus any associated interface definition files, plus the scripts used to control compilation and installation of the executable. However, as a special exception, the source code distributed need not include anything that is normally distributed (in either source or binary form) with the major components (compiler, kernel, and so on) of the operating system on which the executable runs, unless that component itself accompanies the executable.

If distribution of executable or object code is made by offering access to copy from a designated place, then offering equivalent access to copy the source code from the same place counts as distribution of the source code, even though third parties are not compelled to copy the source along with the object code.

4. You may not copy, modify, sublicense, or distribute the Program

except as expressly provided under this License. Any attempt otherwise to copy, modify, sublicense or distribute the Program is void, and will automatically terminate your rights under this License. However, parties who have received copies, or rights, from you under this License will not have their licenses terminated so long as such parties remain in full compliance.

5. You are not required to accept this License, since you have not signed it. However, nothing else grants you permission to modify or distribute the Program or its derivative works. These actions are prohibited by law if you do not accept this License. Therefore, by modifying or distributing the Program (or any work based on the Program), you indicate your acceptance of this License to do so, and all its terms and conditions for copying, distributing or modifying the Program or works based on it.

6. Each time you redistribute the Program (or any work based on the Program), the recipient automatically receives a license from the original licensor to copy, distribute or modify the Program subject to these terms and conditions. You may not impose any further restrictions on the recipients' exercise of the rights granted herein. You are not responsible for enforcing compliance by third parties to this License.

7. If, as a consequence of a court judgment or allegation of patent infringement or for any other reason (not limited to patent issues), conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot distribute so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not distribute the Program at all. For example, if a patent license would not permit royalty-free redistribution of the Program by all those who receive copies directly or indirectly through you, then the only way you could satisfy both it and this License would be to refrain entirely from distribution of the Program.

If any portion of this section is held invalid or unenforceable under any particular circumstance, the balance of the section is intended to apply and the section as a whole is intended to apply in other circumstances.

It is not the purpose of this section to induce you to infringe any patents or other property right claims or to contest validity of any such claims; this section has the sole purpose of protecting the integrity of the free software distribution system, which is

implemented by public license practices. Many people have made generous contributions to the wide range of software distributed through that system in reliance on consistent application of that system; it is up to the author/donor to decide if he or she is willing to distribute software through any other system and a licensee cannot impose that choice.

This section is intended to make thoroughly clear what is believed to be a consequence of the rest of this License.

8. If the distribution and/or use of the Program is restricted in certain countries either by patents or by copyrighted interfaces, the original copyright holder who places the Program under this License may add an explicit geographical distribution limitation excluding those countries, so that distribution is permitted only in or among countries not thus excluded. In such case, this License incorporates the limitation as if written in the body of this License.

9. The Free Software Foundation may publish revised and/or new versions of the General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Program specifies a version number of this License which applies to it and "any later version", you have the option of following the terms and conditions either of that version or of any later version published by the Free Software Foundation. If the Program does not specify a version number of this License, you may choose any version ever published by the Free Software Foundation.

10. If you wish to incorporate parts of the Program into other free programs whose distribution conditions are different, write to the author to ask for permission. For software which is copyrighted by the Free Software Foundation, write to the Free Software Foundation; we sometimes make exceptions for this. Our decision will be guided by the two goals of preserving the free status of all derivatives of our free software and of promoting the sharing and reuse of software generally.

NO WARRANTY

11. BECAUSE THE PROGRAM IS LICENSED FREE OF CHARGE, THERE IS NO WARRANTY FOR THE PROGRAM, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE PROGRAM "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED

OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE PROGRAM IS WITH YOU. SHOULD THE PROGRAM PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

12. IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY AND/OR REDISTRIBUTE THE PROGRAM AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE PROGRAM (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE PROGRAM TO OPERATE WITH ANY OTHER PROGRAMS), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Programs

If you develop a new program, and you want it to be of the greatest possible use to the public, the best way to achieve this is to make it free software which everyone can redistribute and change under these terms.

To do so, attach the following notices to the program. It is safest to attach them to the start of each source file to most effectively convey the exclusion of warranty; and each file should have at least the "copyright" line and a pointer to where the full notice is found.

<one line to give the program's name and a brief idea of what it does.>
Copyright (C) <year> <name of author>

This program is free software; you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation; either version 2 of the License, or (at your option) any later version.

This program is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details.

You should have received a copy of the GNU General Public License along with this program; if not, write to the Free Software Foundation, Inc., 51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA.

Also add information on how to contact you by electronic and paper mail.

If the program is interactive, make it output a short notice like this when it starts in an interactive mode:

```
Gnomovision version 69, Copyright (C) year name of author
Gnomovision comes with ABSOLUTELY NO WARRANTY; for details type `show w'.
This is free software, and you are welcome to redistribute
it
under certain conditions; type `show c' for details.
```

The hypothetical commands `show w' and `show c' should show the appropriate parts of the General Public License. Of course, the commands you use may be called something other than `show w' and `show c'; they could even be mouse-clicks or menu items--whatever suits your program.

You should also get your employer (if you work as a programmer) or your school, if any, to sign a "copyright disclaimer" for the program, if necessary. Here is a sample; alter the names:

```
Yoyodyne, Inc., hereby disclaims all copyright interest in the program
`Gnomovision' (which makes passes at compilers) written by James Hacker.
```

```
<signature of Ty Coon>, 1 April 1989
Ty Coon, President of Vice
```

This General Public License does not permit incorporating your program into proprietary programs. If your program is a subroutine library, you may consider it more useful to permit linking proprietary applications with the library. If this is what you want to do, use the GNU Lesser General Public License instead of this License.

GNU LESSER GENERAL PUBLIC LICENSE
Version 3, 29 June 2007

Copyright (C) 2007 Free Software Foundation, Inc. <<http://fsf.org/>>
Everyone is permitted to copy and distribute verbatim copies of this license document, but changing it is not allowed.

This version of the GNU Lesser General Public License incorporates the terms and conditions of version 3 of the GNU General Public License, supplemented by the additional permissions listed below.

0. Additional Definitions.

As used herein, "this License" refers to version 3 of the GNU Lesser General Public License, and the "GNU GPL" refers to version 3 of the GNU

General Public License.

"The Library" refers to a covered work governed by this License, other than an Application or a Combined Work as defined below.

An "Application" is any work that makes use of an interface provided by the Library, but which is not otherwise based on the Library. Defining a subclass of a class defined by the Library is deemed a mode of using an interface provided by the Library.

A "Combined Work" is a work produced by combining or linking an Application with the Library. The particular version of the Library with which the Combined Work was made is also called the "Linked Version".

The "Minimal Corresponding Source" for a Combined Work means the Corresponding Source for the Combined Work, excluding any source code for portions of the Combined Work that, considered in isolation, are based on the Application, and not on the Linked Version.

The "Corresponding Application Code" for a Combined Work means the object code and/or source code for the Application, including any data and utility programs needed for reproducing the Combined Work from the Application, but excluding the System Libraries of the Combined Work.

1. Exception to Section 3 of the GNU GPL.

You may convey a covered work under sections 3 and 4 of this License without being bound by section 3 of the GNU GPL.

2. Conveying Modified Versions.

If you modify a copy of the Library, and, in your modifications, a facility refers to a function or data to be supplied by an Application that uses the facility (other than as an argument passed when the facility is invoked), then you may convey a copy of the modified version:

- a) under this License, provided that you make a good faith effort to ensure that, in the event an Application does not supply the function or data, the facility still operates, and performs whatever part of its purpose remains meaningful, or
- b) under the GNU GPL, with none of the additional permissions of this License applicable to that copy.

3. Object Code Incorporating Material from Library Header Files.

The object code form of an Application may incorporate material from a header file that is part of the Library. You may convey such object code under terms of your choice, provided that, if the incorporated material is not limited to numerical parameters, data structure layouts and accessors, or small macros, inline functions and templates (ten or fewer lines in length), you do both of the following:

- a) Give prominent notice with each copy of the object code that the Library is used in it and that the Library and its use are covered by this License.
- b) Accompany the object code with a copy of the GNU GPL and this license document.

4. Combined Works.

You may convey a Combined Work under terms of your choice that, taken together, effectively do not restrict modification of the portions of the Library contained in the Combined Work and reverse engineering for debugging such modifications, if you also do each of the following:

- a) Give prominent notice with each copy of the Combined Work that the Library is used in it and that the Library and its use are covered by this License.
- b) Accompany the Combined Work with a copy of the GNU GPL and this license document.
- c) For a Combined Work that displays copyright notices during execution, include the copyright notice for the Library among these notices, as well as a reference directing the user to the copies of the GNU GPL and this license document.
- d) Do one of the following:
 - 0) Convey the Minimal Corresponding Source under the terms of this License, and the Corresponding Application Code in a form suitable for, and under terms that permit, the user to recombine or relink the Application with a modified version of the Linked Version to produce a modified Combined Work, in the manner specified by section 6 of the GNU GPL for conveying Corresponding Source.

1) Use a suitable shared library mechanism for linking with the Library. A suitable mechanism is one that (a) uses at run time a copy of the Library already present on the user's computer system, and (b) will operate properly with a modified version of the Library that is interface-compatible with the Linked Version.

e) Provide Installation Information, but only if you would otherwise be required to provide such information under section 6 of the GNU GPL, and only to the extent that such information is necessary to install and execute a modified version of the Combined Work produced by recombining or relinking the Application with a modified version of the Linked Version. (If you use option 4d0, the Installation Information must accompany the Minimal Corresponding Source and Corresponding Application Code. If you use option 4d1, you must provide the Installation Information in the manner specified by section 6 of the GNU GPL for conveying Corresponding Source.)

5. Combined Libraries.

You may place library facilities that are a work based on the Library side by side in a single library together with other library facilities that are not Applications and are not covered by this License, and convey such a combined library under terms of your choice, if you do both of the following:

- a) Accompany the combined library with a copy of the same work based on the Library, uncombined with any other library facilities, conveyed under the terms of this License.
- b) Give prominent notice with the combined library that part of it is a work based on the Library, and explaining where to find the accompanying uncombined form of the same work.

6. Revised Versions of the GNU Lesser General Public License.

The Free Software Foundation may publish revised and/or new versions of the GNU Lesser General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Library as you received it specifies that a certain numbered version of the GNU Lesser General Public License "or any later version" applies to it, you have the option of following

the terms and conditions either of that published version or of any later version published by the Free Software Foundation. If the Library as you received it does not specify a version number of the GNU Lesser General Public License, you may choose any version of the GNU Lesser General Public License ever published by the Free Software Foundation.

If the Library as you received it specifies that a proxy can decide whether future versions of the GNU Lesser General Public License shall apply, that proxy's public statement of acceptance of any version is permanent authorization for you to choose that version for the Library.

GNU GENERAL PUBLIC LICENSE

Version 3, 29 June 2007

Copyright (C) 2007 Free Software Foundation, Inc. <<http://fsf.org/>>
Everyone is permitted to copy and distribute verbatim copies of this license document, but changing it is not allowed.

Preamble

The GNU General Public License is a free, copyleft license for software and other kinds of works.

The licenses for most software and other practical works are designed to take away your freedom to share and change the works. By contrast, the GNU General Public License is intended to guarantee your freedom to share and change all versions of a program--to make sure it remains free software for all its users. We, the Free Software Foundation, use the GNU General Public License for most of our software; it applies also to any other work released this way by its authors. You can apply it to your programs, too.

When we speak of free software, we are referring to freedom, not price. Our General Public Licenses are designed to make sure that you have the freedom to distribute copies of free software (and charge for them if you wish), that you receive source code or can get it if you want it, that you can change the software or use pieces of it in new free programs, and that you know you can do these things.

To protect your rights, we need to prevent others from denying you these rights or asking you to surrender the rights. Therefore, you have certain responsibilities if you distribute copies of the software, or if you modify it: responsibilities to respect the freedom of others.

For example, if you distribute copies of such a program, whether gratis or for a fee, you must pass on to the recipients the same

freedoms that you received. You must make sure that they, too, receive or can get the source code. And you must show them these terms so they know their rights.

Developers that use the GNU GPL protect your rights with two steps:

(1)

assert copyright on the software, and (2) offer you this License giving you legal permission to copy, distribute and/or modify it.

For the developers' and authors' protection, the GPL clearly explains that there is no warranty for this free software. For both users' and authors' sake, the GPL requires that modified versions be marked as changed, so that their problems will not be attributed erroneously to authors of previous versions.

Some devices are designed to deny users access to install or run modified versions of the software inside them, although the manufacturer can do so. This is fundamentally incompatible with the aim of protecting users' freedom to change the software. The systematic pattern of such abuse occurs in the area of products for individuals to use, which is precisely where it is most unacceptable. Therefore, we have designed this version of the GPL to prohibit the practice for those products. If such problems arise substantially in other domains, we stand

ready to extend this provision to those domains in future versions of the GPL, as needed to protect the freedom of users.

Finally, every program is threatened constantly by software patents. States should not allow patents to restrict development and use of software on general-purpose computers, but in those that do, we wish to avoid the special danger that patents applied to a free program could make it effectively proprietary. To prevent this, the GPL assures that patents cannot be used to render the program non-free.

The precise terms and conditions for copying, distribution and modification follow.

TERMS AND CONDITIONS

0. Definitions.

"This License" refers to version 3 of the GNU General Public License.

"Copyright" also means copyright-like laws that apply to other kinds of works, such as semiconductor masks.

"The Program" refers to any copyrightable work licensed under this License. Each licensee is addressed as "you". "Licensees"

and

"recipients" may be individuals or organizations.

To "modify" a work means to copy from or adapt all or part of the work in a fashion requiring copyright permission, other than the making of an exact copy. The resulting work is called a "modified version" of the earlier work or a work "based on" the earlier work.

A "covered work" means either the unmodified Program or a work based on the Program.

To "propagate" a work means to do anything with it that, without permission, would make you directly or secondarily liable for infringement under applicable copyright law, except executing it on a computer or modifying a private copy. Propagation includes copying, distribution (with or without modification), making available to the public, and in some countries other activities as well.

To "convey" a work means any kind of propagation that enables other parties to make or receive copies. Mere interaction with a user through a computer network, with no transfer of a copy, is not conveying.

An interactive user interface displays "Appropriate Legal Notices" to the extent that it includes a convenient and prominently visible feature that (1) displays an appropriate copyright notice, and (2) tells the user that there is no warranty for the work (except to the extent that warranties are provided), that licensees may convey the work under this License, and how to view a copy of this License. If the interface presents a list of user commands or options, such as a menu, a prominent item in the list meets this criterion.

1. Source Code.

The "source code" for a work means the preferred form of the work for making modifications to it. "Object code" means any non-source form of a work.

A "Standard Interface" means an interface that either is an official standard defined by a recognized standards body, or, in the case of interfaces specified for a particular programming language, one that is widely used among developers working in that language.

The

"System Libraries" of an executable work include anything, other than the work as a whole, that (a) is included in the normal form of packaging a Major Component, but which is not part of that Major Component, and (b) serves only to enable use of the work with that

Major Component, or to implement a Standard Interface for which an implementation is available to the public in source code form. A "Major Component", in this context, means a major essential component (kernel, window system, and so on) of the specific operating system (if any) on which the executable work runs, or a compiler used to produce the work, or an object code interpreter used to run it.

The "Corresponding Source" for a work in object code form means all the source code needed to generate, install, and (for an executable work) run the object code and to modify the work, including scripts to control those activities. However, it does not include the work's System Libraries, or general-purpose tools or generally available free programs which are used unmodified in performing those activities but which are not part of the work. For example, Corresponding Source includes interface definition files associated with source files for the work, and the source code for shared libraries and dynamically linked subprograms that the work is specifically designed to require, such as by intimate data communication or control flow between those subprograms and other parts of the work.

The Corresponding Source need not include anything that users can regenerate automatically from other parts of the Corresponding Source.

The Corresponding Source for a work in source code form is that same work.

2. Basic Permissions.

All rights granted under this License are granted for the term of copyright on the Program, and are irrevocable provided the stated conditions are met. This License explicitly affirms your unlimited permission to run the unmodified Program. The output from running a covered work is covered by this License only if the output, given its content, constitutes a covered work. This License acknowledges your rights of fair use or other equivalent, as provided by copyright law.

You may make, run and propagate covered works that you do not convey, without conditions so long as your license otherwise remains in force. You may convey covered works to others for the sole purpose of having them make modifications exclusively for you, or provide you with facilities for running those works, provided that you comply with the terms of this License in conveying all material for which you do not control copyright. Those thus making or running the covered works for you must do so exclusively on your behalf, under your direction and control, on terms that prohibit them from making any copies of

your copyrighted material outside their relationship with you.

Conveying under any other circumstances is permitted solely under the conditions stated below. Sublicensing is not allowed; section 10 makes it unnecessary.

3. Protecting Users' Legal Rights From Anti-Circumvention Law.

No covered work shall be deemed part of an effective technological measure under any applicable law fulfilling obligations under article 11 of the WIPO copyright treaty adopted on 20 December 1996, or similar laws prohibiting or restricting circumvention of such measures.

When you convey a covered work, you waive any legal power to forbid circumvention of technological measures to the extent such circumvention is effected by exercising rights under this License with respect to the covered work, and you disclaim any intention to limit operation or modification of the work as a means of enforcing, against the work's users, your or third parties' legal rights to forbid circumvention of technological measures.

4. Conveying Verbatim Copies.

You may convey verbatim copies of the Program's source code as you receive it, in any medium, provided that you conspicuously and appropriately publish on each copy an appropriate copyright notice; keep intact all notices stating that this License and any non-permissive terms added in accord with section 7 apply to the code; keep intact all notices of the absence of any warranty; and give all recipients a copy of this License along with the Program.

You may charge any price or no price for each copy that you convey, and you may offer support or warranty protection for a fee.

5. Conveying Modified Source Versions.

You may convey a work based on the Program, or the modifications to produce it from the Program, in the form of source code under the terms of section 4, provided that you also meet all of these conditions:

- a) The work must carry prominent notices stating that you modified it, and giving a relevant date.
- b) The work must carry prominent notices stating that it is released under this License and any conditions added under section

7. This requirement modifies the requirement in section 4 to

"keep intact all notices".

c) You must license the entire work, as a whole, under this License to anyone who comes into possession of a copy. This License will therefore apply, along with any applicable section 7 additional terms, to the whole of the work, and all its parts, regardless of how they are packaged. This License gives no permission to license the work in any other way, but it does not invalidate such permission if you have separately received it.

d) If the work has interactive user interfaces, each must display Appropriate Legal Notices; however, if the Program has interactive interfaces that do not display Appropriate Legal Notices, your work need not make them do so.

A compilation of a covered work with other separate and independent works, which are not by their nature extensions of the covered work, and which are not combined with it such as to form a larger program, in or on a volume of a storage or distribution medium, is called an "aggregate" if the compilation and its resulting copyright are not used to limit the access or legal rights of the compilation's users beyond what the individual works permit. Inclusion of a covered work in an aggregate does not cause this License to apply to the other parts of the aggregate.

6. Conveying Non-Source Forms.

You may convey a covered work in object code form under the terms of sections 4 and 5, provided that you also convey the machine-readable Corresponding Source under the terms of this License, in one of these ways:

a) Convey the object code in, or embodied in, a physical product (including a physical distribution medium), accompanied by the Corresponding Source fixed on a durable physical medium customarily used for software interchange.

b) Convey the object code in, or embodied in, a physical product (including a physical distribution medium), accompanied by a written offer, valid for at least three years and valid for as long as you offer spare parts or customer support for that product model, to give anyone who possesses the object code either (1) a copy of the Corresponding Source for all the software in the product that is covered by this License, on a durable physical

medium customarily used for software interchange, for a price no more than your reasonable cost of physically performing this conveying of source, or (2) access to copy the Corresponding Source from a network server at no charge.

c) Convey individual copies of the object code with a copy of the written offer to provide the Corresponding Source. This alternative is allowed only occasionally and noncommercially, and only if you received the object code with such an offer, in accord with subsection 6b.

d) Convey the object code by offering access from a designated place (gratis or for a charge), and offer equivalent access to the Corresponding Source in the same way through the same place at no further charge. You need not require recipients to copy the Corresponding Source along with the object code. If the place to copy the object code is a network server, the Corresponding Source may be on a different server (operated by you or a third party) that supports equivalent copying facilities, provided you maintain clear directions next to the object code saying where to find the Corresponding Source. Regardless of what server hosts the Corresponding Source, you remain obligated to ensure that it is available for as long as needed to satisfy these requirements.

e) Convey the object code using peer-to-peer transmission, provided you inform other peers where the object code and Corresponding Source of the work are being offered to the general public at no charge under subsection 6d.

A separable portion of the object code, whose source code is excluded from the Corresponding Source as a System Library, need not be included in conveying the object code work.

A "User Product" is either (1) a "consumer product", which means any tangible personal property which is normally used for personal, family, or household purposes, or (2) anything designed or sold for incorporation into a dwelling. In determining whether a product is a consumer product, doubtful cases shall be resolved in favor of coverage. For a particular product received by a particular user, "normally used" refers to a typical or common use of that class of product, regardless of the status of the particular user or of the way in which the particular user actually uses, or expects or is expected to use, the product. A product is a consumer product regardless of whether the product has substantial commercial, industrial or non-consumer uses, unless such uses represent the only significant mode of use of the product.

"Installation Information" for a User Product means any methods, procedures, authorization keys, or other information required to install and execute modified versions of a covered work in that User Product from a modified version of its Corresponding Source. The information must suffice to ensure that the continued functioning of the modified object code is in no case prevented or interfered with solely because modification has been made.

If you convey an object code work under this section in, or with, or specifically for use in, a User Product, and the conveying occurs as part of a transaction in which the right of possession and use of the User Product is transferred to the recipient in perpetuity or for a fixed term (regardless of how the transaction is characterized), the Corresponding Source conveyed under this section must be accompanied by the Installation Information. But this requirement does not apply if neither you nor any third party retains the ability to install modified object code on the User Product (for example, the work has been installed in ROM).

The requirement to provide Installation Information does not include a requirement to continue to provide support service, warranty, or updates for a work that has been modified or installed by the recipient, or for the User Product in which it has been modified or installed. Access to a network may be denied when the modification itself materially and adversely affects the operation of the network or violates the rules and protocols for communication across the network.

Corresponding Source conveyed, and Installation Information provided, in accord with this section must be in a format that is publicly documented (and with an implementation available to the public in source code form), and must require no special password or key for unpacking, reading or copying.

7. Additional Terms.

"Additional permissions" are terms that supplement the terms of this License by making exceptions from one or more of its conditions. Additional permissions that are applicable to the entire Program shall be treated as though they were included in this License, to the extent that they are valid under applicable law. If additional permissions apply only to part of the Program, that part may be used separately under those permissions, but the entire Program remains governed by this License without regard to the additional permissions.

When you convey a copy of a covered work, you may at your option

remove any additional permissions from that copy, or from any part of it. (Additional permissions may be written to require their own removal in certain cases when you modify the work.) You may place additional permissions on material, added by you to a covered work, for which you have or can give appropriate copyright permission.

Notwithstanding any other provision of this License, for material you add to a covered work, you may (if authorized by the copyright holders of that material) supplement the terms of this License with terms:

- a) Disclaiming warranty or limiting liability differently from the terms of sections 15 and 16 of this License; or
- b) Requiring preservation of specified reasonable legal notices or author attributions in that material or in the Appropriate Legal Notices displayed by works containing it; or
- c) Prohibiting misrepresentation of the origin of that material, or requiring that modified versions of such material be marked in reasonable ways as different from the original version; or
- d) Limiting the use for publicity purposes of names of licensors or authors of the material; or
- e) Declining to grant rights under trademark law for use of some trade names, trademarks, or service marks; or
- f) Requiring indemnification of licensors and authors of that material by anyone who conveys the material (or modified versions of it) with contractual assumptions of liability to the recipient, for any liability that these contractual assumptions directly impose on those licensors and authors.

All other non-permissive additional terms are considered "further restrictions" within the meaning of section 10. If the Program as you received it, or any part of it, contains a notice stating that it is governed by this License along with a term that is a further restriction, you may remove that term. If a license document contains a further restriction but permits relicensing or conveying under this License, you may add to a covered work material governed by the terms of that license document, provided that the further restriction does not survive such relicensing or conveying.

If you add terms to a covered work in accord with this section, you must place, in the relevant source files, a statement of the additional terms that apply to those files, or a notice indicating

where to find the applicable terms.

Additional terms, permissive or non-permissive, may be stated in the form of a separately written license, or stated as exceptions; the above requirements apply either way.

8. Termination.

You may not propagate or modify a covered work except as expressly provided under this License. Any attempt otherwise to propagate or modify it is void, and will automatically terminate your rights under this License (including any patent licenses granted under the third paragraph of section 11).

However, if you cease all violation of this License, then your license from a particular copyright holder is reinstated (a) provisionally, unless and until the copyright holder explicitly and finally terminates your license, and (b) permanently, if the copyright holder fails to notify you of the violation by some reasonable means prior to 60 days after the cessation.

Moreover, your license from a particular copyright holder is reinstated permanently if the copyright holder notifies you of the violation by some reasonable means, this is the first time you have received notice of violation of this License (for any work) from that copyright holder, and you cure the violation prior to 30 days after your receipt of the notice.

Termination of your rights under this section does not terminate the licenses of parties who have received copies or rights from you under this License. If your rights have been terminated and not permanently reinstated, you do not qualify to receive new licenses for the same material under section 10.

9. Acceptance Not Required for Having Copies.

You are not required to accept this License in order to receive or run a copy of the Program. Ancillary propagation of a covered work occurring solely as a consequence of using peer-to-peer transmission to receive a copy likewise does not require acceptance. However, nothing other than this License grants you permission to propagate or modify any covered work. These actions infringe copyright if you do not accept this License. Therefore, by modifying or propagating a covered work, you indicate your acceptance of this License to do so.

10. Automatic Licensing of Downstream Recipients.

Each time you convey a covered work, the recipient automatically receives a license from the original licensors, to run, modify and propagate that work, subject to this License. You are not responsible for enforcing compliance by third parties with this License.

An "entity transaction" is a transaction transferring control of an organization, or substantially all assets of one, or subdividing an organization, or merging organizations. If propagation of a covered work results from an entity transaction, each party to that transaction who receives a copy of the work also receives whatever licenses to the work the party's predecessor in interest had or could give under the previous paragraph, plus a right to possession of the Corresponding Source of the work from the predecessor in interest, if the predecessor has it or can get it with reasonable efforts.

You may not impose any further restrictions on the exercise of the rights

granted or affirmed under this License. For example, you may not impose a license fee, royalty, or other charge for exercise of rights granted under this License, and you may not initiate litigation (including a cross-claim or counterclaim in a lawsuit) alleging that any patent claim is infringed by making, using, selling, offering for sale, or importing the Program or any portion of it.

11. Patents.

A "contributor" is a copyright holder who authorizes use under this License of the Program or a work on which the Program is based. The work thus licensed is called the contributor's "contributor version".

A contributor's "essential patent claims" are all patent claims owned or controlled by the contributor, whether already acquired or hereafter acquired, that would be infringed by some manner, permitted by this License, of making, using, or selling its contributor version, but do not include claims that would be infringed only as a consequence of further modification of the contributor version. For purposes of this definition, "control" includes the right to grant patent sublicenses in a manner consistent with the requirements of this License.

Each contributor grants you a non-exclusive, worldwide, royalty-free patent license under the contributor's essential patent claims, to make, use, sell, offer for sale, import and otherwise run, modify and propagate the contents of its contributor version.

In the following three paragraphs, a "patent license" is any express agreement or commitment, however denominated, not to enforce a patent (such as an express permission to practice a patent or covenant not to sue for patent infringement). To "grant" such a patent license to a party means to make such an agreement or commitment not to enforce a patent against the party.

If you convey a covered work, knowingly relying on a patent license, and the Corresponding Source of the work is not available for anyone to copy, free of charge and under the terms of this

License, through a publicly available network server or other readily accessible means, then you must either (1) cause the Corresponding Source to be so available, or (2) arrange to deprive yourself of the benefit of the patent license for this particular work, or (3) arrange, in a manner consistent with the requirements of this License, to extend the patent license to downstream recipients. "Knowingly relying" means you have actual knowledge that, but for the patent license, your conveying the covered work in a country, or your recipient's use of the covered work in a country, would infringe one or more identifiable patents in that country that you have reason to believe are valid.

If, pursuant to or in connection with a single transaction or arrangement, you convey, or propagate by procuring conveyance of, a covered work, and grant a patent license to some of the parties receiving the covered work authorizing them to use, propagate, modify or convey a specific copy of the covered work, then the patent license you grant is automatically extended to all recipients of the covered work and works based on it.

A patent license is "discriminatory" if it does not include within the scope of its coverage, prohibits the exercise of, or is conditioned on the non-exercise of one or more of the rights that are specifically granted under this License. You may not convey a covered work if you are a party to an arrangement with a third party that is in the business of distributing software, under which you make payment to the third party based on the extent of your activity of conveying the work, and under which the third party grants, to any of the parties who would receive the covered work from you, a discriminatory patent license (a) in connection with copies of the covered work conveyed by you (or copies made from those copies), or (b) primarily for and in connection with specific products or compilations that contain the covered work, unless you entered into that arrangement, or that patent license was granted, prior to 28 March 2007.

Nothing in this License shall be construed as excluding or limiting

any implied license or other defenses to infringement that may otherwise be available to you under applicable patent law.

12. No Surrender of Others' Freedom.

If conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot convey a covered work so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not convey it at all. For example, if you agree to terms that obligate you to collect a royalty for further conveying from those to whom you convey the Program, the only way you could satisfy both those terms and this License would be to refrain entirely from conveying the Program.

13. Use with the GNU Affero General Public License.

Notwithstanding any other provision of this License, you have permission to link or combine any covered work with a work licensed under version 3 of the GNU Affero General Public License into a single combined work, and to convey the resulting work. The terms of this License will continue to apply to the part which is the covered work, but the special requirements of the GNU Affero General Public License, section 13, concerning interaction through a network will apply to the combination as such.

14. Revised Versions of this License.

The Free Software Foundation may publish revised and/or new versions of the GNU General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Program specifies that a certain numbered version of the GNU General Public License "or any later version" applies to it, you have the option of following the terms and conditions either of that numbered version or of any later version published by the Free Software Foundation. If the Program does not specify a version number of the GNU General Public License, you may choose any version ever published by the Free Software Foundation.

If the Program specifies that a proxy can decide which future versions of the GNU General Public License can be used, that proxy's public statement of acceptance of a version permanently authorizes you to choose that version for the Program.

Later license versions may give you additional or different permissions. However, no additional obligations are imposed on any author or copyright holder as a result of your choosing to follow a later version.

15. Disclaimer of Warranty.

THERE IS NO WARRANTY FOR THE PROGRAM, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE PROGRAM "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE PROGRAM IS WITH YOU. SHOULD THE PROGRAM PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

16. Limitation of Liability.

IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MODIFIES AND/OR CONVEYS THE PROGRAM AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE PROGRAM (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE PROGRAM TO OPERATE WITH ANY OTHER PROGRAMS), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

17.

Interpretation of Sections 15 and 16.

If the disclaimer of warranty and limitation of liability provided above cannot be given local legal effect according to their terms, reviewing courts shall apply local law that most closely approximates an absolute waiver of all civil liability in connection with the Program, unless a warranty or assumption of liability accompanies a copy of the Program in return for a fee.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Programs

If you develop a new program, and you want it to be of the greatest possible use to the public, the best way to achieve this is to make it free software which everyone can redistribute and change under these terms.

To do so, attach the following notices to the program. It is safest

to attach them to the start of each source file to most effectively state the exclusion of warranty; and each file should have at least the "copyright" line and a pointer to where the full notice is found.

```
<one line to give the program's name and a brief idea of what it does.>  
Copyright (C) <year> <name of author>
```

This program is free software: you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation, either version 3 of the License, or (at your option) any later version.

This program is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details.

You should have received a copy of the GNU General Public License along with this program. If not, see <https://www.gnu.org/licenses/>.

Also add information on how to contact you by electronic and paper mail.

If the program does terminal interaction, make it output a short notice like this when it starts in an interactive mode:

```
<program> Copyright (C) <year> <name of author>  
This program comes with ABSOLUTELY NO WARRANTY; for details type `show w'.  
This is free software, and you are welcome to redistribute it  
under certain conditions; type `show c' for details.
```

The hypothetical commands `show w' and `show c' should show the appropriate parts of the General Public License. Of course, your program's commands might be different; for a GUI interface, you would use an "about box".

You should also get your employer (if you work as a programmer) or school, if any, to sign a "copyright disclaimer" for the program, if necessary. For more information on this, and how to apply and follow the GNU GPL, see <https://www.gnu.org/licenses/>.

The GNU General Public License does not permit incorporating your program into proprietary programs. If your program is a subroutine library, you may consider it more useful to permit linking proprietary applications with the library. If this is what you want to do, use the GNU Lesser General Public License instead of this License. But first, please read <https://www.gnu.org/philosophy/why-not-lgpl.html>.

1.108 githubcompelletiergotoml v1.9.4

1.108.1 Available under license :

The bulk of github.com/pelletier/go-toml is distributed under the MIT license (see below), with the exception of [localtime.go](https://github.com/pelletier/localtime.go) and [localtime.test.go](https://github.com/pelletier/localtime.test.go).

Those two files have been copied over from Google's civil library at revision [ed46f5086358513cf8c25f8e3f022cb838a49d66](https://github.com/google/civil/commit/ed46f5086358513cf8c25f8e3f022cb838a49d66), and are distributed under the Apache 2.0 license (see below).

github.com/pelletier/go-toml:

The MIT License (MIT)

Copyright (c) 2013 - 2021 Thomas Pelletier, Eric Anderton

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE

SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

[localtime.go](https://github.com/pelletier/localtime.go), [localtime_test.go](https://github.com/pelletier/localtime_test.go):

Originals:

<https://raw.githubusercontent.com/googleapis/google-cloud-go/ed46f5086358513cf8c25f8e3f022cb838a49d66/civil/civil.go>

https://raw.githubusercontent.com/googleapis/google-cloud-go/ed46f5086358513cf8c25f8e3f022cb838a49d66/civil/civil_test.go

Changes:

* Renamed files from `civil*` to `localtime*`.

* Package changed from civil to toml.

* 'Local' prefix added to all structs.

License:

<https://raw.githubusercontent.com/googleapis/google-cloud-go/ed46f5086358513cf8c25f8e3f022cb838a49d66/LICENSE>

Apache License
Version 2.0, January 2004
<http://www.apache.org/licenses/>

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction, and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all other entities that control, are controlled by, or are under common control with that entity. For the purposes of this definition, "control" means (i) the power, direct or indirect, to cause the direction or management of such entity, whether by contract or otherwise, or (ii) ownership of fifty percent (50%) or more of the outstanding shares, or (iii) beneficial ownership of such entity.

"You" (or "Your") shall mean an individual or Legal Entity exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications, including but not limited to software source code, documentation source, and configuration files.

"Object" form shall mean any form resulting from mechanical transformation or translation of a Source form, including but not limited to compiled object code, generated documentation, and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or Object form, made available under the License, as indicated by a copyright notice that is included in or attached to the work (an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object

form, that is based on (or derived from) the Work and for which the editorial revisions, annotations, elaborations, or other modifications represent, as a whole, an original work of authorship. For the purposes of this License, Derivative Works shall not include works that remain separable from, or merely link (or bind by name) to the interfaces of, the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including the original version of the Work and any modifications or additions to that Work or Derivative Works thereof, that is intentionally submitted to Licensor for inclusion in the Work by the copyright owner or by an individual or Legal Entity authorized to submit on behalf of the copyright owner. For the purposes of this definition, "submitted" means any form of electronic, verbal, or written communication sent to the Licensor or its representatives, including but not limited to communication on electronic mailing lists, source code control systems, and issue tracking systems that are managed by, or on behalf of, the Licensor for the purpose of discussing and improving the Work, but excluding communication that is conspicuously marked or otherwise designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity on behalf of whom a Contribution has been received by Licensor and subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative Works of, publicly display, publicly perform, sublicense, and distribute the Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable (except as stated in this section) patent license to make, have made, use, offer to sell, sell, import, and otherwise transfer the Work, where such license applies only to those patent claims licensable by such Contributor that are necessarily infringed by their Contribution(s) alone or by combination of their Contribution(s) with the Work to which such Contribution(s) was submitted. If You institute patent litigation against any entity (including a cross-claim or counterclaim in a lawsuit) alleging that the Work or a Contribution incorporated within the Work constitutes direct or contributory patent infringement, then any patent licenses

granted to You under this License for that Work shall terminate as of the date such litigation is filed.

4. Redistribution.

You may reproduce and distribute copies of the

Work or Derivative Works thereof in any medium, with or without modifications, and in Source or Object form, provided that You meet the following conditions:

- (a) You must give any other recipients of the Work or Derivative Works a copy of this License; and
- (b) You must cause any modified files to carry prominent notices stating that You changed the files; and
- (c) You must retain, in the Source form of any Derivative Works that You distribute, all copyright, patent, trademark, and attribution notices from the Source form of the Work, excluding those notices that do not pertain to any part of the Derivative Works; and
- (d) If the Work includes a "NOTICE" text file as part of its distribution, then any Derivative Works that You distribute must include a readable copy of the attribution notices contained within

such NOTICE file, excluding those notices that do not pertain to any part of the Derivative Works, in at least one of the following places: within a NOTICE text file distributed as part of the Derivative Works; within the Source form or documentation, if provided along with the Derivative Works; or, within a display generated by the Derivative Works, if and wherever such third-party notices normally appear. The contents of the NOTICE file are for informational purposes only and do not modify the License. You may add Your own attribution notices within Derivative Works that You distribute, alongside or as an addendum to the NOTICE text from the Work, provided that such additional attribution notices cannot be construed as modifying the License.

You may add Your own copyright statement to Your modifications and may provide additional or different license terms and conditions

for use, reproduction, or distribution of Your modifications, or for any such Derivative Works as a whole, provided Your use, reproduction, and distribution of the Work otherwise complies with the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise,

any Contribution intentionally submitted for inclusion in the Work by You to the Licensor shall be under the terms and conditions of this License, without any additional terms or conditions.

Notwithstanding the above, nothing herein shall supersede or modify the terms of any separate license agreement you may have executed with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade names, trademarks, service marks, or product names of the Licensor, except as required for reasonable and customary use in describing the origin of the Work and reproducing the content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or agreed to in writing, Licensor provides the Work (and each Contributor provides its Contributions) on an "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied, including, without limitation, any warranties or conditions of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A PARTICULAR PURPOSE. You are solely responsible for determining the appropriateness of using or redistributing the Work and assume any risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory, whether in tort (including negligence), contract, or otherwise, unless required by applicable law (such as deliberate and grossly negligent acts) or agreed to in writing, shall any Contributor be liable to You for damages, including any direct, indirect, special, incidental, or consequential damages of any character arising as a result of this License or out of the use or inability to use the Work (including but not limited to damages for loss of goodwill, work stoppage, computer failure or malfunction, or any and all other commercial damages or losses), even if such Contributor has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing the Work or Derivative Works thereof, You may choose to offer, and charge a fee for, acceptance of support, warranty, indemnity, or other liability obligations and/or rights consistent with this License. However, in accepting such obligations, You may act only on Your own behalf and on Your sole responsibility, not on behalf of any other Contributor, and only if You agree to indemnify, defend, and hold each Contributor harmless for any liability incurred by, or claims asserted against, such Contributor by reason of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

APPENDIX: How to apply the Apache License to your work.

To apply the Apache License to your work, attach the following boilerplate notice, with the fields enclosed by brackets "[]" replaced with your own identifying information. (Don't include the brackets!) The text should be enclosed in the appropriate comment syntax for the file format. We also recommend that a file or class name and description of purpose be included on the same "printed page" as the copyright notice for easier identification within third-party archives.

Copyright [yyyy] [name of copyright owner]

Licensed under the Apache License, Version 2.0 (the "License");
you may not use this file except in compliance with the License.
You may obtain a copy of the
License at

<http://www.apache.org/licenses/LICENSE-2.0>

Unless required by applicable law or agreed to in writing, software distributed under the License is distributed on an "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the License for the specific language governing permissions and limitations under the License.

1.109 spf13-pflag v1.0.5

1.109.1 Available under license :

Copyright (c) 2012 Alex Ogier. All rights reserved.

Copyright (c) 2012 The Go Authors. All rights reserved.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

- * Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.
- * Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.
- * Neither the name of Google Inc. nor the names of its contributors may be used to endorse or promote products derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE

ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

// Copyright 2009 The Go Authors. All rights reserved.

// Use of this source code is governed by a BSD-style

// license that can be found in the LICENSE file.

1.110 go-toml 1.9.4

1.110.1 Available under license :

The bulk of github.com/pelletier/go-toml is distributed under the MIT license (see below), with the exception of [localtime.go](https://github.com/pelletier/localtime.go) and [localtime.test.go](https://github.com/pelletier/localtime.test.go).

Those two files have been copied over from Google's civil library at revision [ed46f5086358513cf8c25f8e3f022cb838a49d66](https://github.com/pelletier/localtime.go/commit/ed46f5086358513cf8c25f8e3f022cb838a49d66), and are distributed under the Apache 2.0 license (see below).

github.com/pelletier/go-toml:

The MIT License (MIT)

Copyright (c) 2013 - 2021 Thomas Pelletier, Eric Anderton

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE

SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,

FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

localtime.go, localtime_test.go:

Originals:

<https://raw.githubusercontent.com/googleapis/google-cloud-go/ed46f5086358513cf8c25f8e3f022cb838a49d66/civil/civil.go>

https://raw.githubusercontent.com/googleapis/google-cloud-go/ed46f5086358513cf8c25f8e3f022cb838a49d66/civil/civil_test.go

Changes:

- * Renamed files from civil* to localtime*.
- * Package changed from civil to toml.
- * 'Local' prefix added to all structs.

License:

<https://raw.githubusercontent.com/googleapis/google-cloud-go/ed46f5086358513cf8c25f8e3f022cb838a49d66/LICENSE>

Apache License
Version 2.0, January 2004
<http://www.apache.org/licenses/>

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction, and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all other entities that control, are controlled by, or are under common control with that entity. For the purposes of this definition, "control" means (i) the power, direct or indirect, to cause the direction or management of such entity, whether by contract or otherwise, or (ii) ownership of fifty percent (50%) or more of the outstanding shares, or (iii) beneficial ownership of such entity.

"You" (or "Your") shall mean an individual or Legal Entity exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications, including but not limited to software source code, documentation source, and configuration files.

"Object" form shall mean any form resulting from mechanical transformation or translation of a Source form, including but not limited to compiled object code, generated documentation, and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or Object form, made available under the License, as indicated by a copyright notice that is included in or attached to the work (an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object form, that is based on (or derived from) the Work and for which the editorial revisions, annotations, elaborations, or other modifications represent, as a whole, an original work of authorship. For the purposes of this License, Derivative Works shall not include works that remain separable from, or merely link (or bind by name) to the interfaces of, the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including the original version of the Work and any modifications or additions to that Work or Derivative Works thereof, that is intentionally submitted to Licensor for inclusion in the Work by the copyright owner or by an individual or Legal Entity authorized to submit on behalf of the copyright owner. For the purposes of this definition, "submitted" means any form of electronic, verbal, or written communication sent to the Licensor or its representatives, including but not limited to communication on electronic mailing lists, source code control systems, and issue tracking systems that are managed by, or on behalf of, the Licensor for the purpose of discussing and improving the Work, but excluding communication that is conspicuously marked or otherwise designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity on behalf of whom a Contribution has been received by Licensor and subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative Works of, publicly display, publicly perform, sublicense, and distribute the

Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of

this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable (except as stated in this section) patent license to make, have made, use, offer to sell, sell, import, and otherwise transfer the Work, where such license applies only to those patent claims licensable by such Contributor that are necessarily infringed by their Contribution(s) alone or by combination of their Contribution(s) with the Work to which such Contribution(s) was submitted. If You institute patent litigation against any entity (including a cross-claim or counterclaim in a lawsuit) alleging that the Work or a Contribution incorporated within the Work constitutes direct or contributory patent infringement, then any patent licenses granted to You under this License for that Work shall terminate as of the date such litigation is filed.

4. Redistribution.

You may reproduce and distribute copies of the

Work or Derivative Works thereof in any medium, with or without modifications, and in Source or Object form, provided that You meet the following conditions:

- (a) You must give any other recipients of the Work or Derivative Works a copy of this License; and
- (b) You must cause any modified files to carry prominent notices stating that You changed the files; and
- (c) You must retain, in the Source form of any Derivative Works that You distribute, all copyright, patent, trademark, and attribution notices from the Source form of the Work, excluding those notices that do not pertain to any part of the Derivative Works; and
- (d) If the Work includes a "NOTICE" text file as part of its distribution, then any Derivative Works that You distribute must include a readable copy of the attribution notices contained within

such NOTICE file, excluding those notices that do not

pertain to any part of the Derivative Works, in at least one of the following places: within a NOTICE text file distributed as part of the Derivative Works; within the Source form or documentation, if provided along with the Derivative Works; or, within a display generated by the Derivative Works, if and wherever such third-party notices normally appear. The contents

of the NOTICE file are for informational purposes only and do not modify the License. You may add Your own attribution notices within Derivative Works that You distribute, alongside or as an addendum to the NOTICE text from the Work, provided that such additional attribution notices cannot be construed as modifying the License.

You may add Your own copyright statement to Your modifications and may provide additional or different license terms and conditions

for use, reproduction, or distribution of Your modifications, or for any such Derivative Works as a whole, provided Your use, reproduction, and distribution of the Work otherwise complies with the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise, any Contribution intentionally submitted for inclusion in the Work by You to the Licensor shall be under the terms and conditions of this License, without any additional terms or conditions.

Notwithstanding the above, nothing herein shall supersede or modify the terms of any separate license agreement you may have executed with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade names, trademarks, service marks, or product names of the Licensor, except as required for reasonable and customary use in describing the origin of the Work and reproducing the content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or agreed to in writing, Licensor provides the Work (and each Contributor provides its Contributions) on an "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied, including, without limitation, any warranties or conditions of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A PARTICULAR PURPOSE. You are solely responsible for determining the appropriateness of using or redistributing the Work and assume any risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory, whether in tort (including negligence), contract, or otherwise, unless required by applicable law (such as deliberate and grossly negligent acts) or agreed to in writing, shall any Contributor be liable to You

for damages, including any direct, indirect, special, incidental, or consequential damages of any character arising as a result of this License or out of the use or inability to use the Work (including but not limited to damages for loss of goodwill,

work stoppage, computer failure or malfunction, or any and all other commercial damages or losses), even if such Contributor has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing the Work or Derivative Works thereof, You may choose to offer, and charge a fee for, acceptance of support, warranty, indemnity, or other liability obligations and/or rights consistent with this License. However, in accepting such obligations, You may act only on Your own behalf and on Your sole responsibility, not on behalf of any other Contributor, and only if You agree to indemnify, defend, and hold each Contributor harmless for any liability incurred by, or claims asserted against, such Contributor by reason of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

APPENDIX: How to apply the Apache License to your work.

To apply the Apache License to your work, attach the following boilerplate notice, with the fields enclosed by brackets "[]" replaced with your own identifying information. (Don't include the brackets!) The text should be enclosed in the appropriate comment syntax for the file format. We also recommend that a file or class name and description of purpose be included on the same "printed page" as the copyright notice for easier identification within third-party archives.

Copyright [yyyy] [name of copyright owner]

Licensed under the Apache License, Version 2.0 (the "License"); you may not use this file except in compliance with the License. You may obtain a copy of the License at

<http://www.apache.org/licenses/LICENSE-2.0>

Unless required by applicable law or agreed to in writing, software distributed under the License is distributed on an "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the License for the specific language governing permissions and limitations under the License.

1.111 pflag 1.0.5

1.111.1 Available under license :

MIT License

Copyright (c) 2021 PHPComLab

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

Cisco and the Cisco logo are trademarks or registered trademarks of Cisco and/or its affiliates in the U.S. and other countries. To view a list of Cisco trademarks, go to this URL: www.cisco.com/go/trademarks. Third-party trademarks mentioned are the property of their respective owners. The use of the word partner does not imply a partnership relationship between Cisco and any other company. (1110R)

©2024 Cisco Systems, Inc. All rights reserved.