Troubleshoot Device Insights and DUO Integration

Contents

Introduction Prerequisites Requirements Components Used Background Information Troubleshoot Review the License Level No data from Duo Connectivity test with Device Insights and DUO Verify

Introduction

This document describes the steps to configure the integration and troubleshoot Device Insights and Cisco DUO integration.

Prerequisites

Requirements

Cisco recommends that you have knowledge of these topics.

- SecureX
- DUO
- Basic knowledge of APIs
- Postman API tool

Components Used

The information in this document is based on these software and hardware versions.

• SecureX 1.103

The information in this document was created from the devices in a specific lab environment. All of the devices used in this document started with a cleared (default) configuration. If your network is live, ensure that you understand the potential impact of any command.

Background Information

SecureX Device Insights provides a unified view of the devices in your organization and

consolidates inventories from integrated data sources.

Duo secures your workforce and takes access security beyond the corporate network perimeter to protect your data at every authentication attempt, from any device, anywhere. With Duo, you can confirm your identities in a snap, monitor the health of managed and unmanaged devices, set adaptive security policies tailored for your business, secure remote access without a device agent, and provide secure, user-friendly Single Sign-On quickly and easily.

If you want to know more about the configuration, please review, this article <u>here</u> the integration module details.

Troubleshoot

In order to troubleshoot common issues with the SecureX and DUO integration, you can verify the connectivity and performance of the API.

Review the License Level

Check license in Duo Admin Panel

• Duo Licensed for Duo Access, Duo Beyond (or any newer high-end license, MFA only or Free does not apply), as shown in the image



No data from Duo

• Verify you use Duo Health Agent data in Auth Policy, as shown in the image

	Policy name NPI Policy	This section only affects applications protected by Duo's Device Health application. Learn More 🕑			
00	Users New User policy	t macOS Enforcing			
	Authentication policy	On't require users to have the app.			
	User location	Require users to have the app.			
	Devices Trusted Endpoints	Block access if frewall is off.			
		Block access if FileVault is off. Block access if surface compared is and set.			
	Operating systems	Block access if an endpoint security agent is not running.			
		Windows Reporting			

• Verify you use Trusted Endpoint in Auth Policy, as shown in the image



Connectivity test with Device Insights and DUO

You can use Postman Tool to have a more visual output while you test the connectivity.

Note: Postman is not a Cisco-developed tool. If you have a question about Postman tool functionality, please contact Postman support.

• Error code 40301 "Access Forbidden" means you do not have the right level of license, as shown in the image



- You can select No Auth as an authorization method
- You can use this API call in order to get a list of the devices (API returns the maximum supported number of entries per page), and you can find <u>documentation</u> about DUO API pagination

https://<DUO admin API FQDN>/admin/v1/endpoints

• In response to the first call, the total number of objects is returned (offset and limit parameters can be used to get the next pages), as shown in the image

https://<DUO admin API FQDN>/admin/v1/endpoints?limit=5&offset=5

```
"metadata": {
    "next_offset": 5,
    "total_objects": 64
},
```

Verify

Once DUO is added as a source to Device Insights, you can see a successful **REST API** connection status.

- You can see the REST API connection with a green status
- Press on SYNC NOW to trigger the initial full sync, as shown in the image

Paul 2 Days 🗠				Ail Mer Soriet	Add a Conton Tourse
	Status Inte	Partemana Dar Tea	lipes beautrue Term	Last Syna	
😄 no	O Spectrum				

In case the issue persists with the Device Insights and DUO integration, please see this <u>article</u> to collect HAR logs from the browser and contact TAC support in order to perform a deeper analysis.

```
"metadata": {
    "next_offset": 5,
    "total_objects": 64
},
"metadata": {
    "next_offset": 5,
    "next_offset": 5,
    "total_objects": 64
},
```