

Release Notes for Cisco Business Dashboard, Version 2.5.0

First Published: 2022-07-27

Introduction

These release notes describe the recommended practices and known issues that apply to software version 2.5.0 of Cisco Business Dashboard.

What's New in Cisco Business Dashboard Release 2.5.0

Cisco Business Dashboard release 2.5.0 introduces the following new features and changes:

- Enhanced configuration for wireless networks, including:
 - Guest access wireless networks.
 - Controlling local profiling and application inspection.
 - Wireless Radio profiles enabling RF optimization and interference detection.
 - Radio configuration for access points.
- Authentication services allowing for user-based access to wired and wireless networks.
- Device management can now be restricted by IP address.
- Unmanaged network icons can be separately filtered from the network topology diagram.
- The inventory view can be filtered based on lifecycle state.
- New notifications have been added for expired passwords and configuration mismatches.
- Let's Encrypt certificates can now be managed from the GUI.

Caveats

The following table lists the open caveats for Cisco Business Dashboard version 2.5.0.

Table 1: Open Caveats

Caveat ID Number	Headline
CSCvc04204	Getting the duplicated entry in the credentials table for switch stack after power off the master. Workaround When the stack is stable, reboot Probe.
CSCvf49309	CBD displays an outside WAN IP instead of the device IP on Network Plug and Play - Unclaimed Devices page. Workaround None
CSCvf49332	CBD responses are slow when the display is over 300 hosts on the topology page. Workaround Don't display the hosts when there are that many.
CSCvq25771	The system does not sync time from the host on VirtualBox. Workaround Install VirtualBox Guest additions in the virtual machine with the command 'sudo apt-get install -y virtualbox-guest-utils' and reboot the virtual machine. Note The presence of VirtualBox Guest Additions in the virtual machine will prevent timesyncd from running and NTP will not function.
CSCvq25807	Stack switch unit configuration is missing after master recovery from offline. Workaround Manually read and accept current config or wait for the daily schedule job.
CSCvq25817	It doesn't show real VLAN setting info on a LAG port. Workaround Review the VLAN configuration for the LAG on the device administration GUI.
CSCvv18280	CBD doesn't support "same SSID name" case for CBW. Workaround Change the SSID names on the CBW access point to keep it unique.
CSCwa46056	The Delete devices automation ticket should only allow immediate execution. Workaround None.

The following table lists the resolved caveats for version 2.5.0

Table 2: Resolved Caveats

Caveat ID Number	Headline
CSCwb03852	CBD: Switches in stack are not named correctly.
CSCwb64234	Restore the system from an old backup file will cause contuit bundle version change.

System Requirements for Cisco Dashboard and Probe

For information on updates to the System Requirements for the Dashboard and Probe refer to the Installation Guides listed below.

- [Cisco Business Dashboard Installation Guide for Amazon Web Services \(AWS\)](#)
- [Cisco Business Dashboard & Probe Installation Guide for Oracle VirtualBox](#)
- [Cisco Business Dashboard Installation Guide for Microsoft Hyper-V](#)
- [Cisco Business Dashboard & Probe Installation Guide for VMWare](#)
- [Cisco Business Dashboard & Probe Installation Guide for Linux](#)
- [Cisco Business Dashboard & Installation Guide for Microsoft Azure](#)

Cisco Supported Devices

Cisco Business Dashboard supports Cisco Business and Cisco Small Business 100 to 500 series products. For a detailed list of devices and features supported, please refer to the [Cisco Business Dashboard - Device Support List](#).

License Requirements

Cisco Business Dashboard is a licensed application. Device licenses are required for each Cisco Business and Cisco Small Business product being managed. For more information, please refer to the [Cisco Business Dashboard Datasheet](#).

Limitations and Restrictions

The Cisco Business Dashboard limitations and restrictions are described in the following sections:

- [General Limitations](#)
- [System Backup and Restore](#)

General Limitations

- The web interface on Cisco Business Dashboard takes a few minutes to become operational after the application is started.
- Depending on the size of the network, it may take the Probe several minutes to discover all devices and calculate the network topology.
- Up to 50 network devices can be managed by a single virtual machine or Raspberry Pi Probe instance. Refer to the documentation for the product in question to identify the maximum number of devices supported by an embedded probe running on a Cisco Business network device.
- Up to 2500 devices can be managed by a single Dashboard instance.
- SNMPv3 authentication keys and privacy keys must be at least 8 characters in length
- When using Safari, ensure that the certificate presented by the Cisco Business Dashboard Probe is set to **Always Trust**.
- When you deploy Cisco Business Dashboard as a Microsoft Azure virtual machine, if you select the **Availability options** to enable infrastructure redundancy, the Dashboard will not be able to automatically populate the external IP addresses in the System Variables. The external IP system variables need to be set manually.



Note Depending on the way the system has been configured, it may be necessary to regenerate the Dashboard certificate to reference the correct address.

System Backup and Restore

- When performing a system backup or restore, Cisco Business Dashboard will prevent you from doing any further configuration actions.
- Prior to beginning a system backup or restore, the idle timeout value in **Administration > Users > User Settings** should be set to at least 30 minutes (default is 60 minutes).

Where to Find Support

For current support information, visit the following URLs:

Table 3: Where to Find Support

Support	
Cisco Business Dashboard Support Forums	http://www.cisco.com/go/cbd-support
Cisco Business Phone Support	http://www.cisco.com/go/cbphone
Product Documentation	

Support	
Cisco Business Dashboard Support and Documentation Resources	https://cisco.com/go/cbd-docs
Cisco Business	
Cisco Business Home	http://www.cisco.com/go/ciscobusiness
Cisco Business Support Community	http://www.cisco.com/go/cbcommunity

