



## B Show Commands

---

- [show background](#), on page 3
- [show banner exec](#), on page 4
- [show banner motd](#), on page 5
- [show bash-shell](#), on page 6
- [show bfd clients](#), on page 7
- [show bfd neighbors](#), on page 8
- [show bgp](#), on page 10
- [show bgp](#), on page 11
- [show bgp](#), on page 13
- [show bgp](#), on page 17
- [show bgp](#), on page 19
- [show bgp](#), on page 21
- [show bgp bmp server](#), on page 22
- [show bgp community](#), on page 23
- [show bgp convergence](#), on page 25
- [show bgp dampening dampened](#), on page 26
- [show bgp dampening flap-statistics](#), on page 28
- [show bgp dampening parameters](#), on page 30
- [show bgp evi](#), on page 32
- [show bgp extcommunity](#), on page 33
- [show bgp l3vpn](#), on page 35
- [show bgp large-community](#), on page 36
- [show bgp neighbors](#), on page 38
- [show bgp neighbors](#), on page 40
- [show bgp neighbors commands](#), on page 42
- [show bgp neighbors flap-statistics](#), on page 43
- [show bgp neighbors paths](#), on page 44
- [show bgp path-attribute discard](#), on page 45
- [show bgp paths](#), on page 47
- [show bgp peer-template](#), on page 48
- [show bgp peer](#), on page 49
- [show bgp prefix-list](#), on page 50
- [show bgp private attr](#), on page 51

- [show bgp private debug history, on page 52](#)
- [show bgp process, on page 53](#)
- [show bgp received-paths, on page 54](#)
- [show bgp regexp, on page 56](#)
- [show bgp rpkicache, on page 57](#)
- [show bgp rpkisummary, on page 58](#)
- [show bgp rpkitable ipv4, on page 59](#)
- [show bgp segment-routing srv6, on page 60](#)
- [show bgp self-originated, on page 61](#)
- [show bgp sessions, on page 62](#)
- [show bgp statistics, on page 63](#)
- [show bgp summary, on page 64](#)
- [show bgp summary, on page 65](#)
- [show boot, on page 66](#)
- [show boot auto-copy, on page 67](#)
- [show boot auto-copy list, on page 68](#)
- [show boot current, on page 69](#)
- [show boot mode, on page 70](#)
- [show boot order, on page 71](#)
- [show boot timings, on page 72](#)
- [show boot variables, on page 73](#)
- [show buffer-drop detail, on page 74](#)
- [show buffer-latency detail, on page 75](#)

# show background

show background

## Syntax Description

show	Show running system information
background	show background processes (started with 'source background <file>' command)

## Command Mode

- /exec

**show banner exec**

# show banner exec

show banner exec

## Syntax Description

show	Show running system information
banner	Show current banner message
exec	Show current exec banner message

## Command Mode

- /exec

# show banner motd

show banner motd

## Syntax Description

show	Show running system information
banner	Show current banner message
motd	Show current motd banner message

## Command Mode

- /exec

**show bash-shell**

# show bash-shell

show bash-shell

## Syntax Description

show	Show running system information
bash-shell	Show bash shell status

## Command Mode

- /exec

# show bfd clients

show bfd clients

## Syntax Description

show	Show running system information
bfd	BFD commands
clients	bfd client list

## Command Mode

- /exec

**show bfd neighbors**

## show bfd neighbors

```
show bfd { [ vrf { <vrf-name> | <vrf-known-name> | all } ] } { [ <ip_type> ] } neighbors { [ multihop ] | [ srte-echo ] | [ module <module> ] | [ interface <intf_id> ] | [ application <bfd_cli_client_names> ] | [ { src-ip <src_ip> | src-ipv6 <src_ipv6> } ] | [ { dest-ip <dest_ip> | dest-ipv6 <dest_ipv6> } ] | [ vrf { <vrf-name> | <vrf-known-name> | all } ] } + [ details ]
```

### Syntax Description

show	Show running system information
bfd	BFD commands
<i>ip_type</i>	(Optional) ipv4 or ipv6
neighbors	neighbors
multihop	(Optional) Display Multihop sessions only
srte-echo	(Optional) Display SRTE echo sessions only
module	(Optional) module
<i>module</i>	(Optional) module number
interface	(Optional) interface
<i>intf_id</i>	(Optional) show bfd sessions based on interface id
application	(Optional) application
<i>bfd_cli_client_names</i>	(Optional) __nil__ Clients need to register with bfd for this list
src-ip	(Optional) Source ip
src-ipv6	(Optional) Source ip
<i>src_ip</i>	(Optional) Source ip value
dest-ip	(Optional) Destination ip
dest-ipv6	(Optional) Destination ip
<i>dest_ip</i>	(Optional) Destination ip value
vrf	(Optional) Display per-VRF information
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
all	(Optional) Display information for all VRFs
details	(Optional) details

**Command Mode**

- /exec

**show bgp**

# show bgp

```
show bgp [ vrf { <vrf-name> | <vrf-known-name> | ALL_VRFS_012345678901234 } ] { ipv4 { unicast | multicast } flap-statistics [ <ip-prefix> | <ip-addr> [ <ip-mask> ] ] | ipv6 { unicast | multicast } flap-statistics [ <ipv6-prefix> ] | all flap-statistics } [ vrf { <vrf-name> | <vrf-known-name> | ALL_VRFS_012345678901234 } ]
```

## Syntax Description

show	Show running system information
bgp	Display BGP status and configuration
vrf	(Optional) Virtual Router Context
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
flap-statistics	Display route flap statistics
<i>ip-prefix</i>	(Optional) Display flap statistics for one prefix
<i>ip-addr</i>	(Optional) Display flap statistics for one network
<i>ip-mask</i>	(Optional) Network mask
ipv4	Display BGP information for IPv4 address family
ipv6	Display BGP information for IPv6 address family
unicast	Display BGP information for unicast address family
multicast	Display BGP information for multicast address family
all	Display BGP information for all address families

## Command Mode

- /exec

# show bgp

```
show bgp [ vrf { <vrf-name> | <vrf-known-name> | ALL_VRFS_012345678901234 } ] { ipv4 { unicast | multicast } policy statistics { { redistribute [ { { eigrp | isis | ospf | rip } <tag> } | static | direct | amt | lisp | hmm | am ] } | { neighbor <neighbor-id> [ default originate | { route-map | filter-list | prefix-list } { in | out } ] } | { dampening } | { network { <ip-addr> mask <ip-mask> <ip-prefix> } } | { aggregate-address { <ip-addr> <ip-mask> <ip-prefix> } { suppress-map | advertise-map } } } | vpnv4 unicast policy statistics { neighbor <neighbor-id> [ { route-map | filter-list | prefix-list } { in | out } ] } | ipv6 { unicast | multicast } policy statistics { { redistribute [ { { eigrp | isis | ospfv3 | rip } <tag> } | static | direct | amt | lisp | hmm | am ] } | { neighbor { <neighbor-id> | <ipv6-neighbor-id> } [ default originate | { route-map | filter-list | prefix-list } { in | out } ] } | { dampening } | { network <ipv6-prefix> } | { aggregate-address <ipv6-prefix> { suppress-map | advertise-map } } } | vrf { <vrf-name> | <vrf-known-name> | ALL_VRFS_012345678901234 } ]
```

## Syntax Description

show	Show running system information
bgp	Display BGP status and configuration
vrf	(Optional) Virtual Router Context
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
ipv4	Display BGP information for IPv4 address family
ipv6	Display BGP information for IPv6 address family
vpnv4	Display BGP information for VPNv4 address family
unicast	Display BGP information for unicast address family
multicast	Display BGP information for multicast address family
policy	Display policy related information
statistics	Display Route Filter statistics
redistribute	Statistics for redistribution
isis	(Optional) ISO IS-IS
ospf	(Optional) Open Shortest Path First
ospfv3	(Optional) Open Shortest Path First v3
rip	(Optional) Routing Information Protocol
eigrp	(Optional) Enhanced Interior Gateway Protocol
static	(Optional) Static routes
direct	(Optional) Directly connected

show bgp

amt	THIS KEYWORD OR VARIABLE IS NOT SUPPORTED
lisp	(Optional) LISP EID-prefixes in the non-default VRF
hmm	(Optional) HMM prefix
am	(Optional) AM routes (learned via ARP)
tag	(Optional) Source protocol tag
neighbor	Show neighbor specific counters
<i>neighbor-id</i>	Neighbor IPv4 address
route-map	(Optional) Neighbor route-map
prefix-list	(Optional) Neighbor prefix-list
filter-list	(Optional) Neighbor filter-list
out	(Optional) Outbound policy
in	(Optional) Inbound policy
default-originate	(Optional) Default-originate policy
dampening	Show dampening info
network	Configured IP prefix to advertise
mask	Configured mask of the IP prefix advertised
aggregate-address	Configured BGP aggregate prefixes
suppress-map	Statistics of suppress policy
advertise-map	Statistics of advertise policy
<i>ip-addr</i>	IP network advertised
<i>ip-mask</i>	Dotted 4-octet mask
<i>ip-prefix</i>	IP prefix in CIDR format

**Command Mode**

- /exec

# show bgp

```
show bgp [ vrf { <vrf-name> | <vrf-known-name> | ALL_VRFS_012345678901234 } ] { { ipv4 { unicast | multicast } | vpng4 unicast [ rd { <ext-comm-rd-aa2nn4> | <ext-comm-rd-aa4nn2> } ] | ipv4 labeled-unicast } [ <ip-addr> [ <ip-mask> [ longer-prefixes ] ] [ detail ] ] | <ip-prefix> [ longer-prefixes ] [ detail ] ] | labels | exported | imported | detail ] ] | { ipv6 { unicast | multicast } | vpng6 unicast [ rd { <ext-comm-rd-aa2nm4> | <ext-comm-rd-aa4nn2> } ] | ipv6 labeled-unicast } [ <ipv6-prefix> [ longer-prefixes ] [ detail ] ] | labels | exported | imported | detail ] ] | { ipv4 mdt [ rd { <ext-comm-rd-aa2nn4> | <ext-comm-rd-aa4nn2> } ] [ <ip-addr> [ <ip-mask> ] | <ip-prefix> ] | labels | mdt-group <mdt-group> ] ] | { ipv4 | ipv6 } unicast [ injected-routes | origin-as validity-state [ valid | invalid | not-found ] ] | link-state [ route-type <rt-type> | <ip4-ls-rt> | <ip6-ls-rt> ] ] | l2vpn vpls [ rd { <ext-comm-rd-aa2nn4> | <ext-comm-rd-aa4nn2> } [ { <ip-addr> [ <ip-mask> ] | <ip-prefix> } | { ve-id <ve-id> block-offset <ve-bs> } ] ] | ipv4 mvpn [ rd { <ext-comm-rd-aa2nn4> | <ext-comm-rd-aa4nn2> } [ join <v4src-addr> <v4grp-addr> <src-asn> | rp <v4src-addr> <grp-v4prefix> <pe-addr> <rp-flags> <rp-priority> <hashlen> | sa <grp-v4prefix> | sa-ad <v4src-addr> <v4grp-addr> | route-type { 1 | 2 | 3 | 4 | 5 | 6 | 7 } [ detail ] ] | route-type { 1 | 2 | 3 | 4 | 5 | 6 | 7 } [ detail ] | join [ detail ] | sa-ad [ detail ] | i-pmsi [ detail ] ] | { <v4src-addr> [ <v4grp-addr> ] | <v4grp-addr> [ <v4src-addr> ] } [ route-type { 1 | 2 | 3 | 4 | 5 | 6 | 7 } [ detail ] ] | ipv6 mvpn [ rd { <ext-comm-rd-aa2nn4> | <ext-comm-rd-aa4nn2> } [ join <v6src-addr> <v6grp-addr> <src-asn> | rp <v6src-addr> <grp-v6prefix> <pe-addr> <rp-flags> <rp-priority> <hashlen> | sa <grp-v6prefix> | sa-ad <v6src-addr> <v6grp-addr> | route-type { 1 | 2 | 3 | 4 | 5 | 6 | 7 } [ detail ] ] | route-type { 1 | 2 | 3 | 4 | 5 | 6 | 7 } [ detail ] | join [ detail ] | sa-ad [ detail ] | i-pmsi [ detail ] ] | { <v6src-addr> [ <v6grp-addr> ] | <v6grp-addr> [ <v6src-addr> ] } [ route-type { 1 | 2 | 3 | 4 | 5 | 6 | 7 } [ detail ] ] ] | l2vpn evpn [ route-type <rtype> [ etid <et> ] | detail | rd { <ext-comm-rd-aa2nn4> | <ext-comm-rd-aa4nn2> } [ route-type <rtype> [ etid <et> ] | <ip4-evpn-rt> | <ip6-evpn-rt> | <mac-address> ] | vni-id <vni_id> [ route-type <rtype> | detail ] | es <es-id> [ route-type <rtype> [ etid <et> ] ] | <ip4-evpn-rt> | <ip6-evpn-rt> | <mac-address> ] | all [ detail ] } [ vrf { <vrf-name> | <vrf-known-name> | ALL_VRFS_012345678901234 } ] }
```

## Syntax Description

show	Show running system information
bgp	Display BGP status and configuration
vrf	(Optional) Virtual Router Context
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
<i>ip-addr</i>	(Optional) Display one particular network from the BRIB in detail
<i>ip-mask</i>	(Optional) Mask for one particular prefix in the BRIB
<i>ip-prefix</i>	(Optional) Display one particular prefix from the BRIB in detail
longer-prefixes	(Optional) Display route and more specific routes
labels	(Optional) Display BGP labels for prefixes
exported	(Optional) Display only exported prefixes
imported	(Optional) Display only imported prefixes

show bgp

injected-routes	(Optional) Display only injected prefixes
origin-as	(Optional) Display RPKI origin-as validity
validity-state	(Optional) Display validity state of origin-as for the prefix
valid	(Optional) Display only prefixes with valid origin-as
invalid	(Optional) Display only prefixes with invalid origin-as
not-found	(Optional) Display only prefixes with not-found origin-as
mdt-group	(Optional) Display prefixes with MDT group address
<i>mdt-group</i>	(Optional) MDT group address
rd	(Optional) Display information for a route distinguisher
ve-id	(Optional) VPLS VE ID
<i>ve-id</i>	(Optional) VPLS VE ID
route-type	(Optional) EVPN Route Type number
<i>rtype</i>	(Optional) EVPN route type number
1	(Optional) Inter-AS PMSI AD
2	(Optional) Intra-AS PMSI AD
3	(Optional) SPMSI AD
4	(Optional) LEAF AD
5	(Optional) Source-Active AD
6	(Optional) Shared C-Multicast
7	(Optional) Source C-Multicast
vni-id	(Optional) EVPN VNI ID number
<i>vni_id</i>	(Optional) EVPN VNI ID number
<i>rt-type</i>	(Optional) Link-State route-type
es	(Optional) Ethernet Segment
<i>es-id</i>	(Optional) ESID
etid	(Optional) Ethernet Tag-ID for L2VPN EVPN route
<i>et</i>	(Optional) Ethernet Tag-ID
<i>ipv4-evpn-rt</i>	(Optional) EVPN IPv4 address
<i>ipv4-ls-rt</i>	(Optional) Link-State NLRI with descriptor including IPv4 address

<i>mac-address</i>	(Optional) MAC address
<i>block-offset</i>	(Optional) VPLS VE Block offset
<i>ve-bs</i>	(Optional) VPLS VE Block offset
<i>ext-comm-rd-aa4nn2</i>	(Optional) VPN route distinguisher in aa4:nn or ip:nn format
<i>ext-comm-rd-aa2nn4</i>	(Optional) VPN route distinguisher in aa:nn format
<i>ipv4</i>	Display BGP information for IPv4 address family
<i>vpnv4</i>	Display BGP information for VPNV4 address family
<i>vpnv6</i>	Display BGP information for VPNV6 address family
<i>ipv6</i>	Display BGP information for IPv6 address family
<i>unicast</i>	Display BGP information for unicast address family
<i>multicast</i>	Display BGP information for multicast address family
<i>mdt</i>	Display BGP information for multicast distribution tree
<i>link-state</i>	Display BGP information for link-state address family
<i>l2vpn</i>	Display BGP information for L2VPN address family
<i>vpls</i>	Display BGP information for L2VPN VPLS address family
<i>labeled-unicast</i>	Display BGP information for labeled-unicast address family
<i>mvpn</i>	Display BGP information for MVPN address family
<i>evpn</i>	Display BGP information for L2VPN EVPN address family
<i>all</i>	Display BGP information for all address families
<i>join</i>	(Optional) Display Multicast Join route
<i>detail</i>	(Optional) Display detailed path info for routes
<i>sa</i>	(Optional) Display Multicast Source Active AD route
<i>sa-ad</i>	(Optional) Display Multicast Source Active AD route
<i>i-pmsi</i>	(Optional) Display Multicast Intra-AS I-PMSI route
<i>rp</i>	(Optional) Display Multicast Group to RP route
<i>v4src-addr</i>	(Optional) Source IP Address
<i>src-asn</i>	(Optional) Source ASN
<i>v4grp-addr</i>	(Optional) Group IP Address
<i>grp-v4prefix</i>	(Optional) Group IP prefix

**show bgp**

<i>pe-addr</i>	(Optional) PE IP Address
<i>rp-flags</i>	(Optional) Flags
<i>rp-priority</i>	(Optional) RP Priority
<i>hashlen</i>	(Optional) Hash mask length
<i>I</i>	(Optional) vrf

**Command Mode**

- /exec

# show bgp

```
show bgp [ vrf { <vrf-name> | <vrf-known-name> | ALL_VRFS_012345678901234 } ] { ipv4 { unicast | multicast } | ipv6 { unicast | multicast } | ipv4 mdt [ rd { <ext-comm-rd-aa2nn4> | <ext-comm-rd-aa4nn2> } ] | vpnv4 unicast [ rd { <ext-comm-rd-aa2nn4> | <ext-comm-rd-aa4nn2> } ] | vpnv6 unicast [ rd { <ext-comm-rd-aa2nn4> | <ext-comm-rd-aa4nn2> } ] | ipv6 labeled-unicast | link-state | l2vpn vpls [ rd { <ext-comm-rd-aa2nn4> | <ext-comm-rd-aa4nn2> } ] | ipv6 mvpn [ rd { <ext-comm-rd-aa2nn4> | <ext-comm-rd-aa4nn2> } ] | l2vpn evpn [ rd { <ext-comm-rd-aa2nn4> | <ext-comm-rd-aa4nn2> } ] | ipv4 labeled-unicast | all } { route-map { <rmap-name> | <rmap-name> } | filter-list { <fltrlist-name> | <test_pol_name> } | { community-list { <commlist-name> | <test_pol_name> } | large-community-list { <large-commlist-name> | <test_pol_name> } | extcommunity-list { <extcommlist-name> | <test_pol_name> } } [ exact-match ] } [ vrf { <vrf-name> | <vrf-known-name> | ALL_VRFS_012345678901234 } ]
```

## Syntax Description

show	Show running system information
bgp	Display BGP status and configuration
vrf	(Optional) Virtual Router Context
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
route-map	Display routes matching the route-map
<i>rmap-name</i>	Route-map name
<i>rmap-name</i>	Known route-map name
filter-list	Display routes matching the filter-list
<i>fltrlist-name</i>	Name of filter-list
community-list	Display routes matching the community-list
<i>commlist-name</i>	Name of community-list
large-community-list	Display routes matching the large-community-list
<i>large-commlist-name</i>	Name of large-community-list
extcommunity-list	Display routes matching the extcommunity-list
<i>extcommlist-name</i>	Name of extcommunity-list
<i>test_pol_name</i>	An existing test-list policy
rd	(Optional) Display information for a route distinguisher
<i>ext-comm-rd-aa4nn2</i>	(Optional) VPN route distinguisher in aa4:nn or ip:nn format

**show bgp**

<i>ext-comm-rd-aa2nn4</i>	(Optional) VPN route distinguisher in aa:nn format
ipv4	Display BGP information for IPv4 address family
vpnv4	Display BGP information for VPKNv4 address family
vpnv6	Display BGP information for VPKNv6 address family
ipv6	Display BGP information for IPv6 address family
unicast	Display BGP information for unicast address family
multicast	Display BGP information for multicast address family
mdt	Display BGP information for multicast distribution tree
labeled-unicast	Display BGP information for labeled-unicast address family
link-state	Display BGP information for link-state address family
l2vpn	Display BGP information for L2VPN address family
vpls	Display BGP information for L2VPN VPLS address family
mvpn	Display BGP information for MVPN address family
evpn	Display BGP information for L2VPN EVPN address family
all	Display BGP information for all address families
exact-match	(Optional) Exact match of the communities

**Command Mode**

- /exec

# show bgp

```
show bgp [ vrf { <vrf-name> | <vrf-known-name> | ALL_VRFS_012345678901234 } ] { { ipv4 { unicast | multicast } | ipv4 mdt [ rd { <ext-comm-rd-aa2nn4> | <ext-comm-rd-aa4nn2> } ] } | vpnv4 unicast [ rd { <ext-comm-rd-aa2nn4> | <ext-comm-rd-aa4nn2> } ] | link-state | l2vpn vpls [ rd { <ext-comm-rd-aa2nn4> | <ext-comm-rd-aa4nn2> } ] | l2vpn evpn [ rd { <ext-comm-rd-aa2nn4> | <ext-comm-rd-aa4nn2> } ] | ipv4 mvpn [ rd { <ext-comm-rd-aa2nn4> | <ext-comm-rd-aa4nn2> } ] | ipv4 labeled-unicast } nexthop <ipnexthop> | { ipv6 { unicast | multicast } | vpnv6 unicast [ rd { <ext-comm-rd-aa2nn4> | <ext-comm-rd-aa4nn2> } ] | ipv6 labeled-unicast | ipv6 mvpn [ rd { <ext-comm-rd-aa2nn4> | <ext-comm-rd-aa4nn2> } ] } nexthop <ip6nexthop> } [ vrf { <vrf-name> | <vrf-known-name> | ALL_VRFS_012345678901234 } ]
```

## Syntax Description

show	Show running system information
bgp	Display BGP status and configuration
rd	(Optional) Display information for a route distinguisher
<i>ext-comm-rd-aa4nn2</i>	(Optional) VPN route distinguisher in aa4:nn or ip:nn format
<i>ext-comm-rd-aa2nn4</i>	(Optional) VPN route distinguisher in aa:nn format
vrf	(Optional) Virtual Router Context
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
nexthop	Display routes matching the nexthop
<i>ipnexthop</i>	Nexthop address
ipv4	Display BGP information for IPv4 address family
ipv6	Display BGP information for IPv6 address family
vpnv4	Display BGP information for VPNV4 address family
vpnv6	Display BGP information for VPNV6 address family
unicast	Display BGP information for unicast address family
multicast	Display BGP information for multicast address family
mdt	Display BGP information for multicast distribution tree
link-state	Display BGP information for link-state address family
l2vpn	Display BGP information for L2VPN address family
vpls	Display BGP information for L2VPN VPLS address family
evpn	Display BGP information for L2VPN EVPN address family

**show bgp**

mvpn	Display BGP information for MVPN address family
labeled-unicast	Display BGP information for labeled-unicast address family

**Command Mode**

- /exec

# show bgp

```
show bgp [ vrf { <vrf-name> | <vrf-known-name> | ALL_VRFS_012345678901234 } ] { { { ipv4 { unicast
| multicast } | vpnv4 unicast | ipv4 mdt | link-state | l2vpn vpls | l2vpn evpn | ipv4 mvpn } nexthop-database
[ <ipnexthop> ] } | { { ipv6 { unicast | multicast } | vpnv6 unicast | ipv6 mvpn } nexthop-database [ <ipv6nexthop> ] } | { all nexthop-database } } [ vrf { <vrf-name> | <vrf-known-name> |
ALL_VRFS_012345678901234 } ]
```

## Syntax Description

show	Show running system information
bgp	Display BGP status and configuration
vrf	(Optional) Virtual Router Context
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
link-state	Display BGP information for link-state address family
l2vpn	Display BGP information for L2VPN address family
vpls	Display BGP information for L2VPN VPLS address family
nexthop-database	Display nexthop database
ipv4	Display BGP information for IPv4 address family
ipv6	Display BGP information for IPv6 address family
vpnv4	Display BGP information for VPNV4 address family
vpnv6	Display BGP information for VPNV6 address family
mdt	Display BGP information for multicast distribution tree
mvpn	Display BGP information for MVPN address family
evpn	Display BGP information for L2VPN EVPN address family
unicast	Display BGP information for unicast address family
multicast	Display BGP information for multicast address family
all	Display BGP information for all address families
<i>ipnexthop</i>	(Optional) Nexthop address

## Command Mode

- /exec

**show bgp bmp server**

# show bgp bmp server

show bgp bmp server [ <server-id> ] [ detail ]

## Syntax Description

show	Show running system information
bgp	Display BGP status and configuration
bmp	Display BMP state
server	Display BMP server information
<i>server-id</i>	(Optional) Display server specific information
detail	(Optional) Display detailed information

## Command Mode

- /exec

# show bgp community

```
show bgp [ vrf { <vrf-name> | <vrf-known-name> | ALL_VRFS_012345678901234 } ] { ipv4 { unicast |
multicast } | ipv6 { unicast | multicast } | ipv4 mdt [ rd { <ext-comm-rd-aa2nn4> | <ext-comm-rd-aa4nn2> } ]
| vpnv4 unicast [ rd { <ext-comm-rd-aa2nn4> | <ext-comm-rd-aa4nn2> } ] | vpnv6 unicast [ rd { <ext-comm-rd-aa2nn4> | <ext-comm-rd-aa4nn2> } ] | ipv6 labeled-unicast | link-state | l2vpn vpls [ rd { <ext-comm-rd-aa2nn4> | <ext-comm-rd-aa4nn2> } ] | ipv6 mvpn [ rd { <ext-comm-rd-aa2nn4> | <ext-comm-rd-aa4nn2> } ] | l2vpn evpn [ rd { <ext-comm-rd-aa2nn4> | <ext-comm-rd-aa4nn2> } ] | ipv4 labeled-unicast | all } community { <regexp-str> | { { <comm-id> | <wellknown-id> } + [ exact-match ] } } [ vrf { <vrf-name> | <vrf-known-name> | ALL_VRFS_012345678901234 } ]
```

## Syntax Description

show	Show running system information
bgp	Display BGP status and configuration
vrf	(Optional) Virtual Router Context
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
rd	(Optional) Display information for a route distinguisher
<i>ext-comm-rd-aa4nn2</i>	(Optional) VPN route distinguisher in aa4:nn or ip:nn format
<i>ext-comm-rd-aa2nn4</i>	(Optional) VPN route distinguisher in aa:nn format
ipv4	Display BGP information for IPv4 address family
ipv6	Display BGP information for IPv6 address family
vpnv4	Display BGP information for VPNV4 address family
vpnv6	Display BGP information for VPNV6 address family
unicast	Display BGP information for unicast address family
multicast	Display BGP information for multicast address family
mdt	Display BGP information for multicast distribution tree
link-state	Display BGP information for link-state address family
l2vpn	Display BGP information for L2VPN address family
vpls	Display BGP information for L2VPN VPLS address family
labeled-unicast	Display BGP information for labeled-unicast address family
mvpn	Display BGP information for MVPN address family

**show bgp community**

evpn	Display BGP information for L2VPN EVPN address family
all	Display BGP information for all address families
community	Display routes matching the BGP communities
<i>regexp-str</i>	Regular expression to match the communities
<i>comm-id</i>	BGP community value
<i>wellknown-id</i>	BGP wellknown community
exact-match	(Optional) Exact match of the communities

**Command Mode**

- /exec

# show bgp convergence

```
show bgp [ vrf { <vrf-name> | <vrf-known-name> | ALL_VRFS_012345678901234 } ] convergence [ detail ] [ vrf { <vrf-name> | <vrf-known-name> | ALL_VRFS_012345678901234 } ]
```

## Syntax Description

show	Show running system information
bgp	Display BGP status and configuration
vrf	(Optional) Virtual Router Context
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
convergence	Display information about convergence
detail	(Optional) Display detailed information about convergence

## Command Mode

- /exec

show bgp dampening dampened

## show bgp dampening dampened

```
show bgp [ vrf { <vrf-name> | <vrf-known-name> | ALL_VRFS_012345678901234 } ] { ipv4 { unicast | multicast } | ipv6 { unicast | multicast } | ipv4 mdt [ rd { <ext-comm-rd-aa2nn4> | <ext-comm-rd-aa4nn2> } ] | vpnv4 unicast [ rd { <ext-comm-rd-aa2nn4> | <ext-comm-rd-aa4nn2> } ] | vpnv6 unicast [ rd { <ext-comm-rd-aa2nn4> | <ext-comm-rd-aa4nn2> } ] | ipv6 labeled-unicast | link-state | l2vpn vpls [ rd { <ext-comm-rd-aa2nn4> | <ext-comm-rd-aa4nn2> } ] | ipv4 mvpn [ rd { <ext-comm-rd-aa2nn4> | <ext-comm-rd-aa4nn2> } ] | ipv6 mvpn [ rd { <ext-comm-rd-aa2nn4> | <ext-comm-rd-aa4nn2> } ] | l2vpn evpn [ rd { <ext-comm-rd-aa2nn4> | <ext-comm-rd-aa4nn2> } ] | ipv4 labeled-unicast | all } dampening { dampened-paths [ regexp <regexp-str> ] | history-paths [ regexp <regexp-str> ] } [ vrf { <vrf-name> | <vrf-known-name> | ALL_VRFS_012345678901234 } ]
```

### Syntax Description

show	Show running system information
bgp	Display BGP status and configuration
vrf	(Optional) Virtual Router Context
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
dampened-paths	Display all dampened paths
history-paths	Display all history paths
dampening	Display dampening info
rd	(Optional) Display information for a route distinguisher
<i>ext-comm-rd-aa4nn2</i>	(Optional) VPN route distinguisher in aa4:nn or ip:nn format
<i>ext-comm-rd-aa2nn4</i>	(Optional) VPN route distinguisher in aa:nn format
ipv4	Display BGP information for IPv4 address family
ipv6	Display BGP information for IPv6 address family
vpnv4	Display BGP information for VPNv4 address family
vpnv6	Display BGP information for VPNv6 address family
unicast	Display BGP information for unicast address family
multicast	Display BGP information for multicast address family
mdt	Display BGP information for multicast distribution tree
labeled-unicast	Display BGP information for labeled-unicast address family
link-state	Display BGP information for link-state address family

l2vpn	Display BGP information for L2VPN address family
vpls	Display BGP information for L2VPN VPLS address family
mvpn	Display BGP information for MVPN address family
evpn	Display BGP information for L2VPN EVPN address family
all	Display BGP information for all address families
regexp	(Optional) Display routes matching the AS path regular expression
<i>regexp-str</i>	(Optional) Regular expression to match the AS paths

**Command Mode**

- /exec

show bgp dampening flap-statistics

## show bgp dampening flap-statistics

```
show bgp [ vrf { <vrf-name> | <vrf-known-name> | ALL_VRFS_012345678901234 } ] { ipv4 { unicast | multicast } | ipv6 { unicast | multicast } | ipv4 mdt [ rd { <ext-comm-rd-aa2nn4> | <ext-comm-rd-aa4nn2> } ] | vpnv4 unicast [ rd { <ext-comm-rd-aa2nn4> | <ext-comm-rd-aa4nn2> } ] | vpnv6 unicast [ rd { <ext-comm-rd-aa2nn4> | <ext-comm-rd-aa4nn2> } ] | ipv6 labeled-unicast | link-state | l2vpn vpls [ rd { <ext-comm-rd-aa2nn4> | <ext-comm-rd-aa4nn2> } ] | ipv4 mvpn [ rd { <ext-comm-rd-aa2nn4> | <ext-comm-rd-aa4nn2> } ] | ipv6 mvpn [ rd { <ext-comm-rd-aa2nn4> | <ext-comm-rd-aa4nn2> } ] | l2vpn evpn [ rd { <ext-comm-rd-aa2nn4> | <ext-comm-rd-aa4nn2> } ] | ipv4 labeled-unicast | all } dampening flap-statistics [ vrf { <vrf-name> | <vrf-known-name> | ALL_VRFS_012345678901234 } ]
```

### Syntax Description

show	Show running system information
bgp	Display BGP status and configuration
vrf	(Optional) Virtual Router Context
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
dampening	Display dampening info
flap-statistics	Display flap statistics for routes
rd	(Optional) Display information for a route distinguisher
<i>ext-comm-rd-aa4nn2</i>	(Optional) VPN route distinguisher in aa4:nn or ip:nn format
<i>ext-comm-rd-aa2nn4</i>	(Optional) VPN route distinguisher in aa:nn format
ipv4	Display BGP information for IPv4 address family
ipv6	Display BGP information for IPv6 address family
vpnv4	Display BGP information for VPNv4 address family
vpnv6	Display BGP information for VPNv6 address family
unicast	Display BGP information for unicast address family
multicast	Display BGP information for multicast address family
mdt	Display BGP information for multicast distribution tree
labeled-unicast	Display BGP information for labeled-unicast address family
link-state	Display BGP information for link-state address family
l2vpn	Display BGP information for L2VPN address family
vpls	Display BGP information for L2VPN VPLS address family

mvpn	Display BGP information for MVPN address family
evpn	Display BGP information for L2VPN EVPN address family
all	Display BGP information for all address families

**Command Mode**

- /exec

show bgp dampening parameters

## show bgp dampening parameters

```
show bgp [ vrf { <vrf-name> | <vrf-known-name> | ALL_VRFS_012345678901234 } ] { ipv4 { unicast | multicast } | ipv6 { unicast | multicast } | ipv4 mdt [ rd { <ext-comm-rd-aa2nn4> | <ext-comm-rd-aa4nn2> } ] | vpnv4 unicast [ rd { <ext-comm-rd-aa2nn4> | <ext-comm-rd-aa4nn2> } ] | vpnv6 unicast [ rd { <ext-comm-rd-aa2nn4> | <ext-comm-rd-aa4nn2> } ] | ipv6 labeled-unicast | link-state | l2vpn vpls [ rd { <ext-comm-rd-aa2nn4> | <ext-comm-rd-aa4nn2> } ] | ipv4 mvpn [ rd { <ext-comm-rd-aa2nn4> | <ext-comm-rd-aa4nn2> } ] | ipv6 mvpn [ rd { <ext-comm-rd-aa2nn4> | <ext-comm-rd-aa4nn2> } ] | l2vpn evpn [ rd { <ext-comm-rd-aa2nn4> | <ext-comm-rd-aa4nn2> } ] | ipv4 labeled-unicast | all } dampening parameters [ vrf { <vrf-name> | <vrf-known-name> | ALL_VRFS_012345678901234 } ]
```

### Syntax Description

show	Show running system information
bgp	Display BGP status and configuration
vrf	(Optional) Virtual Router Context
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
dampening	Display dampening info
parameters	Display dampening parameters
rd	(Optional) Display information for a route distinguisher
<i>ext-comm-rd-aa4nn2</i>	(Optional) VPN route distinguisher in aa4:nn or ip:nn format
<i>ext-comm-rd-aa2nn4</i>	(Optional) VPN route distinguisher in aa:nn format
ipv4	Display BGP information for IPv4 address family
ipv6	Display BGP information for IPv6 address family
vpnv4	Display BGP information for VPNv4 address family
vpnv6	Display BGP information for VPNv6 address family
unicast	Display BGP information for unicast address family
multicast	Display BGP information for multicast address family
mdt	Display BGP information for multicast distribution tree
labeled-unicast	Display BGP information for labeled-unicast address family
link-state	Display BGP information for link-state address family
l2vpn	Display BGP information for L2VPN address family
vpls	Display BGP information for L2VPN VPLS address family

mvpn	Display BGP information for MVPN address family
evpn	Display BGP information for L2VPN EVPN address family
all	Display BGP information for all address families

**Command Mode**

- /exec

**show bgp evi**

## show bgp evi

show bgp evi [ <evi-id> ]

### Syntax Description

show	Show running system information
bgp	Display BGP status and configuration
evi	Display information about EVI database
<i>evi-id</i>	(Optional) EVI Id

### Command Mode

- /exec

# show bgp extcommunity

```
show bgp [ vrf { <vrf-name> | <vrf-known-name> | ALL_VRFS_012345678901234 } ] { ipv4 { unicast |
multicast } | ipv6 { unicast | multicast } | ipv4 mdt [ rd { <ext-comm-rd-aa2nn4> | <ext-comm-rd-aa4nn2> } ]
| vpnv4 unicast [ rd { <ext-comm-rd-aa2nn4> | <ext-comm-rd-aa4nn2> } ] | vpnv6 unicast [ rd { <ext-comm-rd-aa2nn4> | <ext-comm-rd-aa4nn2> } ] | ipv6 labeled-unicast | link-state | l2vpn vpls [ rd { <ext-comm-rd-aa2nn4> | <ext-comm-rd-aa4nn2> } ] | ipv4 mvpn [ rd { <ext-comm-rd-aa2nn4> | <ext-comm-rd-aa4nn2> } ] | l2vpn evpn [ rd { <ext-comm-rd-aa2nn4> | <ext-comm-rd-aa4nn2> } ] | ipv4 labeled-unicast | all } extcommunity { <regexp-str> | { 4byteas-generic { transitive <ext-comm-gen-trans> | non-transitive <ext-comm-gen-nontrans> } } + [ exact-match ] } } [ vrf { <vrf-name> | <vrf-known-name> | ALL_VRFS_012345678901234 } ]
```

## Syntax Description

show	Show running system information
bgp	Display BGP status and configuration
vrf	(Optional) Virtual Router Context
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
rd	(Optional) Display information for a route distinguisher
<i>ext-comm-rd-aa4nn2</i>	(Optional) VPN route distinguisher in aa4:nn or ip:nn format
<i>ext-comm-rd-aa2nn4</i>	(Optional) VPN route distinguisher in aa:nn format
ipv4	Display BGP information for IPv4 address family
ipv6	Display BGP information for IPv6 address family
vpnv4	Display BGP information for VPNV4 address family
vpnv6	Display BGP information for VPNV6 address family
unicast	Display BGP information for unicast address family
multicast	Display BGP information for multicast address family
mdt	Display BGP information for multicast distribution tree
link-state	Display BGP information for link-state address family
labeled-unicast	Display BGP information for labeled-unicast address family
l2vpn	Display BGP information for L2VPN address family
vpls	Display BGP information for L2VPN VPLS address family
mvpn	Display BGP information for MVPN address family

**show bgp extcommunity**

evpn	Display BGP information for L2VPN EVPN address family
all	Display BGP information for all address families
extcommunity	Display routes matching the BGP extcommunities
4byteas-generic	Generic extended community
<i>regexp-str</i>	Regular expression to match the extcommunities
transitive	Transitive extcommunity
non-transitive	Non-Transitive extcommunity
<i>ext-comm-gen-trans</i>	Extcommunity number aa4:nn format
<i>ext-comm-gen-nontrans</i>	Extcommunity number aa4:nn format
exact-match	(Optional) Exact match of the extcommunities

#### Command Mode

- /exec

# show bgp l3vpn

show bgp l3vpn [ detail ] [ vrf { <vrf-name> | <vrf-known-name> | ALL\_VRFS\_012345678901234 } ]

## Syntax Description

show	Show running system information
bgp	Display BGP status and configuration
l3vpn	BGP l3vpn information
vrf	(Optional) Virtual Router Context
detail	(Optional) Detailed information
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name

## Command Mode

- /exec

show bgp large-community

## show bgp large-community

```
show bgp [ vrf { <vrf-name> | <vrf-known-name> | ALL_VRFS_012345678901234 } ] { ipv4 { unicast | multicast } | ipv6 { unicast | multicast } | ipv4 mdt [ rd { <ext-comm-rd-aa2nn4> | <ext-comm-rd-aa4nn2> } ] | vpnv4 unicast [ rd { <ext-comm-rd-aa2nn4> | <ext-comm-rd-aa4nn2> } ] | vpnv6 unicast [ rd { <ext-comm-rd-aa2nn4> | <ext-comm-rd-aa4nn2> } ] | ipv6 labeled-unicast | link-state | l2vpn vpls [ rd { <ext-comm-rd-aa2nn4> | <ext-comm-rd-aa4nn2> } ] | ipv4 mvpn [ rd { <ext-comm-rd-aa2nn4> | <ext-comm-rd-aa4nn2> } ] | ipv6 mvpn [ rd { <ext-comm-rd-aa2nn4> | <ext-comm-rd-aa4nn2> } ] | l2vpn evpn [ rd { <ext-comm-rd-aa2nn4> | <ext-comm-rd-aa4nn2> } ] | ipv4 labeled-unicast | all } large-community { <regexp-str> | { <large-comm-xyyzz> + [ exact-match ] } } [ vrf { <vrf-name> | <vrf-known-name> | ALL_VRFS_012345678901234 } ]
```

### Syntax Description

show	Show running system information
bgp	Display BGP status and configuration
vrf	(Optional) Virtual Router Context
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
rd	(Optional) Display information for a route distinguisher
<i>ext-comm-rd-aa4nn2</i>	(Optional) VPN route distinguisher in aa4:nn or ip:nn format
<i>ext-comm-rd-aa2nn4</i>	(Optional) VPN route distinguisher in aa:nn format
ipv4	Display BGP information for IPv4 address family
ipv6	Display BGP information for IPv6 address family
vpnv4	Display BGP information for VPNV4 address family
vpnv6	Display BGP information for VPNV6 address family
unicast	Display BGP information for unicast address family
multicast	Display BGP information for multicast address family
mdt	Display BGP information for multicast distribution tree
link-state	Display BGP information for link-state address family
l2vpn	Display BGP information for L2VPN address family
vpls	Display BGP information for L2VPN VPLS address family
labeled-unicast	Display BGP information for labeled-unicast address family
mvpn	Display BGP information for MVPN address family

evpn	Display BGP information for L2VPN EVPN address family
all	Display BGP information for all address families
large-community	Display routes matching the BGP large communities
<i>regexp-str</i>	Regular expression to match the large communities
<i>large-comm-xyyzz</i>	Large Community value in xx:yy:zz format
exact-match	(Optional) Exact match of the large communities

**Command Mode**

- /exec

**show bgp neighbors**

## show bgp neighbors

```
show bgp { { [ vrf { <vrf-name> | <vrf-known-name> | ALL_VRFS_012345678901234 } ] { ipv4 { unicast | multicast } | ipv6 { unicast | multicast } | all } } | vpnv4 unicast | vpnv6 unicast | ipv6 labeled-unicast | ipv4 labeled-unicast | l2vpn evpn } neighbors { <neighbor-id> | <ipv6-neighbor-id> } { routes [ advertised | received | dampened ] | advertised-routes | received-routes } [ vrf { <vrf-name> | <vrf-known-name> | ALL_VRFS_012345678901234 } ]
```

### Syntax Description

show	Show running system information
bgp	Display BGP status and configuration
vrf	(Optional) Virtual Router Context
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
neighbors	Display all configured BGP neighbors
<i>neighbor-id</i>	Display one particular BGP neighbor
ipv4	Display BGP information for IPv4 address family
vpnv4	Display BGP information for VPNv4 address family
vpnv6	Display BGP information for VPNv6 address family
labeled-unicast	Display BGP information for labeled-unicast address family
ipv6	Display BGP information for IPv6 address family
unicast	Display BGP information for unicast address family
multicast	Display BGP information for multicast address family
all	Display BGP information for all address families
l2vpn	Display BGP information for L2VPN address family
evpn	Display BGP information for L2VPN EVPN address family
routes	Display all routes advertised/received to/from peer
advertised	(Optional) Display all routes advertised to this peer
received	(Optional) Display all routes received from this peer
advertised-routes	Display all the routes advertised to this peer
received-routes	Display all the routes received from this peer
dampened	(Optional) Display all dampened routes received from this peer

### Command Mode

- /exec

**show bgp neighbors**

# show bgp neighbors

```
show bgp { { [ vrf { <vrf-name> | <vrf-known-name> | ALL_VRFS_012345678901234 } ] { ipv4 { unicast | multicast } | ipv6 { unicast | multicast } | all } } | vpnv4 unicast | vpnv6 unicast | ipv6 labeled-unicast | link-state | l2vpn vpls | l2vpn evpn | ipv4 mvpn | ipv6 mvpn | ipv4 labeled-unicast } neighbors [ { <neighbor-id> | <ipv6-neighbor-id> | <neighbor-prefix-id> | <ipv6-neighbor-prefix-id> | <neighbor-interface> } ] [ vrf { <vrf-name> | <vrf-known-name> | ALL_VRFS_012345678901234 } ]
```

## Syntax Description

show	Show running system information
bgp	Display BGP status and configuration
vrf	(Optional) Virtual Router Context
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
neighbors	Display all configured BGP neighbors
<i>neighbor-id</i>	(Optional) Display one particular BGP neighbor
<i>neighbor-prefix-id</i>	(Optional) Display details for a prefix peering
<i>neighbor-interface</i>	(Optional) Display details for BGP interface peering
ipv4	Display BGP information for IPv4 address family
vpnv4	Display BGP information for VPNv4 address family
vpnv6	Display BGP information for VPNv6 address family
ipv6	Display BGP information for IPv6 address family
unicast	Display BGP information for unicast address family
multicast	Display BGP information for multicast address family
labeled-unicast	Display BGP information for labeled-unicast address family
link-state	Display BGP information for link-state address family
l2vpn	Display BGP information for L2VPN address family
vpls	Display BGP information for L2VPN VPLS address family
mvpn	Display BGP information for MVPN address family
evpn	Display BGP information for L2VPN EVPN address family
all	Display BGP information for all address families

## Command Mode

- /exec

**show bgp neighbors commands**

# show bgp neighbors commands

```
show bgp { { [ vrf { <vrf-name> | <vrf-known-name> | ALL_VRFS_012345678901234 } ] { ipv4 { unicast | multicast } | ipv6 { unicast | multicast } | all } } | vpnv4 unicast | vpnv6 unicast | l2vpn evpn } neighbors { <neighbor-id> | <ip6-neighbor-id> } commands [ vrf { <vrf-name> | <vrf-known-name> | ALL_VRFS_012345678901234 } ]
```

**Syntax Description**

show	Show running system information
bgp	Display BGP status and configuration
vrf	(Optional) Virtual Router Context
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
<i>neighbor-id</i>	Display one particular BGP neighbor
ipv4	Display BGP information for IPv4 address family
ipv6	Display BGP information for IPv6 address family
vpnv4	Display BGP information for VPNv4 address family
vpnv6	Display BGP information for VPNv6 address family
unicast	Display BGP information for unicast address family
multicast	Display BGP information for multicast address family
all	Display BGP information for all address families
l2vpn	Display BGP information for L2VPN address family
evpn	Display BGP information for L2VPN EVPN address family
neighbors	Display all configured BGP neighbors
commands	Display details on commands

**Command Mode**

- /exec

# show bgp neighbors flap-statistics

```
show bgp [ vrf { <vrf-name> | <vrf-known-name> | ALL_VRFS_012345678901234 } ] { ipv4 { unicast |  
multicast } | ipv6 { unicast | multicast } | all } neighbors { <neighbor-id> | <ipv6-neighbor-id> } flap-statistics  
[ vrf { <vrf-name> | <vrf-known-name> | ALL_VRFS_012345678901234 } ]
```

## Syntax Description

show	Show running system information
bgp	Display BGP status and configuration
vrf	(Optional) Virtual Router Context
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
neighbors	Display all configured BGP neighbors
<i>neighbor-id</i>	Display one particular BGP neighbor
ipv4	Display BGP information for IPv4 address family
ipv6	Display BGP information for IPv6 address family
unicast	Display BGP information for unicast address family
multicast	Display BGP information for multicast address family
all	Display BGP information for all address families
flap-statistics	Display flap statistics for routes received from this peer

## Command Mode

- /exec

**show bgp neighbors paths**

# show bgp neighbors paths

```
show bgp { { [ vrf { <vrf-name> | <vrf-known-name> | ALL_VRFS_012345678901234 } ] { ipv4 { unicast | multicast } | ipv6 { unicast | multicast } | all } } | vpnv4 unicast | vpnv6 unicast | ipv6 labeled-unicast | ipv4 labeled-unicast | link-state | l2vpn evpn } neighbors { <neighbor-id> | <ipv6-neighbor-id> } paths [ vrf { <vrf-name> | <vrf-known-name> | ALL_VRFS_012345678901234 } ]
```

## Syntax Description

show	Show running system information
bgp	Display BGP status and configuration
vrf	(Optional) Virtual Router Context
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
neighbors	Display all configured BGP neighbors
<i>neighbor-id</i>	Display one particular BGP neighbor
ipv4	Display BGP information for IPv4 address family
vpnv4	Display BGP information for VPNv4 address family
vpnv6	Display BGP information for VPNv6 address family
ipv6	Display BGP information for IPv6 address family
unicast	Display BGP information for unicast address family
multicast	Display BGP information for multicast address family
labeled-unicast	Display BGP information for labeled-unicast address family
link-state	Display BGP information for link-state address family
all	Display BGP information for all address families
l2vpn	Display BGP information for L2VPN address family
evpn	Display BGP information for L2VPN EVPN address family
paths	Display AS paths learned from this peer

## Command Mode

- /exec

# show bgp path-attribute discard

```
show bgp [ vrf { <vrf-name> | <vrf-known-name> | ALL_VRFS_012345678901234 } ] { ipv4 { unicast |
multicast } | ipv4 mdt [ rd { <ext-comm-rd-aa2nn4> | <ext-comm-rd-aa4nn2> } ] | vpnv4 unicast [ rd { <ext-comm-rd-aa2nn4> | <ext-comm-rd-aa4nn2> } ] | link-state | l2vpn vpls [ rd { <ext-comm-rd-aa2nn4> | <ext-comm-rd-aa4nn2> } ] | l2vpn evpn [ rd { <ext-comm-rd-aa2nn4> | <ext-comm-rd-aa4nn2> } ] | ipv4 labeled-unicast | ipv6 { unicast |
multicast } | vpnv6 unicast [ rd { <ext-comm-rd-aa2nn4> | <ext-comm-rd-aa4nn2> } ] | ipv6 labeled-unicast |
ipv6 mvpn [ rd { <ext-comm-rd-aa2nn4> | <ext-comm-rd-aa4nn2> } ] } path-attribute { discard | unknown } [ vrf { <vrf-name> | <vrf-known-name> | ALL_VRFS_012345678901234 } ]
```

## Syntax Description

show	Show running system information
bgp	Display BGP status and configuration
rd	(Optional) Display information for a route distinguisher
<i>ext-comm-rd-aa4nn2</i>	(Optional) VPN route distinguisher in aa4:nn or ip:nn format
<i>ext-comm-rd-aa2nn4</i>	(Optional) VPN route distinguisher in aa:nn format
vrf	(Optional) Virtual Router Context
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
ipv4	Display BGP information for IPv4 address family
ipv6	Display BGP information for IPv6 address family
vpnv4	Display BGP information for VPNv4 address family
vpnv6	Display BGP information for VPNv6 address family
unicast	Display BGP information for unicast address family
multicast	Display BGP information for multicast address family
mdt	Display BGP information for multicast distribution tree
link-state	Display BGP information for link-state address family
l2vpn	Display BGP information for L2VPN address family
vpls	Display BGP information for L2VPN VPLS address family
evpn	Display BGP information for L2VPN EVPN address family
mvpn	Display BGP information for MVPN address family
labeled-unicast	Display BGP information for labeled-unicast address family

```
show bgp path-attribute discard
```

path-attribute	path attribute on a route
discard	discard the path attribute
unknown	unknown path attribute

**Command Mode**

- /exec

# show bgp paths

show [ ip ] bgp paths

## Syntax Description

show	Show running system information
ip	(Optional) Display IP information
bgp	Display BGP status and configuration
paths	Display Path information

## Command Mode

- /exec

**show bgp peer-template**

# show bgp peer-template

```
show [ ip ] bgp peer-template [ <peer-template-name> ]
```

## Syntax Description

show	Show running system information
ip	(Optional) Display IP information
bgp	Display BGP status and configuration
peer-template	Display information about a peer-template
<i>peer-template-name</i>	(Optional) Peer-template name

## Command Mode

- /exec

# show bgp peer

show [ ip ] bgp { peer-session [ <session-template-name> ] | peer-policy [ <policy-template-name> ] }

## Syntax Description

show	Show running system information
ip	(Optional) Display IP information
bgp	Display BGP status and configuration
peer-session	Display information about a peer-session
peer-policy	Display information about a peer-policy
<i>session-template-name</i>	(Optional) Peer-session name
<i>policy-template-name</i>	(Optional) Peer-policy name

## Command Mode

- /exec

**show bgp prefix-list**

## show bgp prefix-list

```
show bgp [ vrf { <vrf-name> | <vrf-known-name> | ALL_VRFS_012345678901234 } ] { ipv4 { unicast |  
multicast } | ipv6 { unicast | multicast } } prefix-list { <prfxlist-name> | <test_pol_name> } [ vrf { <vrf-name>  
<vrf-known-name> | ALL_VRFS_012345678901234 } ]
```

### Syntax Description

show	Show running system information
bgp	Display BGP status and configuration
vrf	(Optional) Virtual Router Context
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
prefix-list	Display routes matching the prefix-list
<i>prfxlist-name</i>	Name of prefix-list
<i>test_pol_name</i>	An existing test-list policy
ipv4	Display BGP information for IPv4 address family
ipv6	Display BGP information for IPv6 address family
unicast	Display BGP information for unicast address family
multicast	Display BGP information for multicast address family

### Command Mode

- /exec

# show bgp private attr

show bgp private attr [ database | as-path | nve-peer | community | large-community | extcommunity | srte-policy | prefix-sid | srv6 | attrset ] [ brief ]

## Syntax Description

show	Show running system information
bgp	Display BGP status and configuration
private	Show BGP information intended for developer eyes only
attr	Show BGP attributes
database	(Optional) Show attribute set table
as-path	(Optional) Show AS-PATH attribute table
nve-peer	(Optional) Show NVE peer attribute table
community	(Optional) Show community attribute table
large-community	(Optional) Show large community attribute table
extcommunity	(Optional) Show extended community attribute table
srtle-policy	(Optional) Show SRTE policy attribute table
prefix-sid	(Optional) Show prefix SID attribute table
srv6	(Optional) Show SRv6 attribute table
attrset	(Optional) Show ATTRSET attribute table
brief	(Optional) Show brief info

## Command Mode

- /exec

show bgp private debug history

## show bgp private debug history

show bgp private debug history { all | ead-es | es | mac | cloudsec }

### Syntax Description

show	Show running system information
bgp	Display BGP status and configuration
private	Show BGP information intended for developer eyes only
debug	Debug
history	history
all	all
ead-es	ead-es
es	es
mac	mac
cloudsec	cloudsec

### Command Mode

- /exec

# show bgp process

```
show bgp [ vrf { <vrf-name> | <vrf-known-name> | ALL_VRFS_012345678901234 } ] process [ detail ] [ vrf { <vrf-name> | <vrf-known-name> | ALL_VRFS_012345678901234 } ]
```

## Syntax Description

show	Show running system information
bgp	Display BGP status and configuration
process	BGP global information
detail	THIS KEYWORD OR VARIABLE IS NOT SUPPORTED
vrf	(Optional) Virtual Router Context
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name

## Command Mode

- /exec

**show bgp received-paths**

## show bgp received-paths

```
show bgp [ vrf { <vrf-name> | <vrf-known-name> | ALL_VRFS_012345678901234 } ] { ipv4 { unicast | multicast } | ipv6 { unicast | multicast } | ipv4 mdt [ rd { <ext-comm-rd-aa2nn4> | <ext-comm-rd-aa4nn2> } ] | vpnv4 unicast [ rd { <ext-comm-rd-aa2nn4> | <ext-comm-rd-aa4nn2> } ] | vpnv6 unicast [ rd { <ext-comm-rd-aa2nn4> | <ext-comm-rd-aa4nn2> } ] | ipv6 labeled-unicast | link-state | l2vpn vpls [ rd { <ext-comm-rd-aa2nn4> | <ext-comm-rd-aa4nn2> } ] | ipv4 mvpn [ rd { <ext-comm-rd-aa2nn4> | <ext-comm-rd-aa4nn2> } ] | ipv6 mvpn [ rd { <ext-comm-rd-aa2nn4> | <ext-comm-rd-aa4nn2> } ] | l2vpn evpn [ rd { <ext-comm-rd-aa2nn4> | <ext-comm-rd-aa4nn2> } ] | ipv4 labeled-unicast [ all } received-paths [ private ] [ vrf { <vrf-name> | <vrf-known-name> | ALL_VRFS_012345678901234 } ]
```

### Syntax Description

show	Show running system information
bgp	Display BGP status and configuration
vrf	(Optional) Virtual Router Context
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
received-paths	Display paths stored for soft-reconfig
rd	(Optional) Display information for a route distinguisher
<i>ext-comm-rd-aa4nn2</i>	(Optional) VPN route distinguisher in aa4:nn or ip:nn format
<i>ext-comm-rd-aa2nn4</i>	(Optional) VPN route distinguisher in aa:nn format
ipv4	Display BGP information for IPv4 address family
ipv6	Display BGP information for IPv6 address family
vpnv4	Display BGP information for VPNV4 address family
vpnv6	Display BGP information for VPNV6 address family
unicast	Display BGP information for unicast address family
multicast	Display BGP information for multicast address family
mdt	Display BGP information for multicast distribution tree
labeled-unicast	Display BGP information for labeled-unicast address family
link-state	Display BGP information for link-state address family
l2vpn	Display BGP information for L2VPN address family
vpls	Display BGP information for L2VPN VPLS address family
mvpn	Display BGP information for MVPN address family

evpn	Display BGP information for L2VPN EVPN address family
all	Display BGP information for all address families
private	THIS KEYWORD OR VARIABLE IS NOT SUPPORTED

**Command Mode**

- /exec

**show bgp regexp**

## show bgp regexp

```
show bgp [ vrf { <vrf-name> | <vrf-known-name> | ALL_VRFS_012345678901234 } ] { ipv4 { unicast |  
multicast } | ipv6 { unicast | multicast } | all } regexp <regexp-str> [ vrf { <vrf-name> | <vrf-known-name>  
| ALL_VRFS_012345678901234 } ]
```

### Syntax Description

show	Show running system information
bgp	Display BGP status and configuration
vrf	(Optional) Virtual Router Context
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
ipv4	Display BGP information for IPv4 address family
ipv6	Display BGP information for IPv6 address family
unicast	Display BGP information for unicast address family
multicast	Display BGP information for multicast address family
all	Display BGP information for all address families
regexp	Display routes matching the AS path regular expression
<i>regexp-str</i>	Regular expression to match the AS paths

### Command Mode

- /exec

# show bgp rpk cache

show bgp rpk cache [ <ipv4-addr> | <ipv6-addr> ]

## Syntax Description

show	Show running system information
bgp	Display BGP status and configuration
rpk	Display RPKI information
cache	Display RPKI cache information
<i>ipv4-addr</i>	(Optional) Display one particular RPKI IPv4 cache

## Command Mode

- /exec

**show bgp rpkı summary**

# show bgp rpkı summary

show bgp rpkı summary

## Syntax Description

show	Show running system information
bgp	Display BGP status and configuration
rpkı	Display RPKI information
summary	Display RPKI summary information

## Command Mode

- /exec

# show bgp rPKI table ipv4

show bgp rPKI table { ipv4 [ <ip-prefix> ] | ipv6 [ <ipv6-prefix> ] }

## Syntax Description

show	Show running system information
bgp	Display BGP status and configuration
rPKI	Display RPKI information
table	Display RPKI table information
ipv4	Display IPv4 RPKI table information
<i>ip-prefix</i>	(Optional) Display one particular prefix from RPKI
ipv6	Display IPv6 RPKI table information

## Command Mode

- /exec

```
show bgp segment-routing srv6
```

## show bgp segment-routing srv6

show bgp segment-routing srv6

### Syntax Description

show	Show running system information
bgp	Display BGP status and configuration
segment-routing	Display segment-routing information
srv6	Display segment-routing srv6 information

### Command Mode

- /exec

# show bgp self-originated

```
show bgp [ vrf { <vrf-name> | <vrf-known-name> | ALL_VRFS_012345678901234 } ] { ipv4 { unicast |  
multicast } | ipv6 { unicast | multicast } | all } self-originated [ vrf { <vrf-name> | <vrf-known-name> |  
ALL_VRFS_012345678901234 } ]
```

## Syntax Description

show	Show running system information
bgp	Display BGP status and configuration
vrf	(Optional) Virtual Router Context
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
ipv4	Display BGP information for IPv4 address family
ipv6	Display BGP information for IPv6 address family
unicast	Display BGP information for unicast address family
multicast	Display BGP information for multicast address family
all	Display BGP information for all address families
self-originated	Self originated routes

## Command Mode

- /exec

**show bgp sessions**

## show bgp sessions

```
show bgp [ vrf { <vrf-name> | <vrf-known-name> | ALL_VRFS_012345678901234 } ] sessions [ vrf { <vrf-name> | <vrf-known-name> | ALL_VRFS_012345678901234 } ]
```

### Syntax Description

show	Show running system information
bgp	Display BGP status and configuration
vrf	(Optional) Virtual Router Context
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
sessions	Display session information for all peers

### Command Mode

- /exec

# show bgp statistics

show bgp statistics

## Syntax Description

show	Show running system information
bgp	Display BGP status and configuration
statistics	BGP global statistics

## Command Mode

- /exec

**show bgp summary**

## show bgp summary

show bgp [ vrf { <vrf-name> | <vrf-known-name> | ALL\_VRFS\_012345678901234 } ] { ipv4 { unicast | multicast } | ipv6 { unicast | multicast } | all } summary

### Syntax Description

show	Show running system information
bgp	Display BGP status and configuration
vrf	(Optional) Virtual Router Context
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
summary	Display summarized information of BGP state
ipv4	Display BGP information for IPv4 address family
ipv6	Display BGP information for IPv6 address family
unicast	Display BGP information for unicast address family
multicast	Display BGP information for multicast address family
all	Display BGP information for all address families

### Command Mode

- /exec

# show bgp summary

```
show bgp { ipv4 { unicast | multicast } | ipv6 { unicast | multicast } | ipv4 mdt | vpnv4 unicast | vpnv6 unicast
| ipv6 labeled-unicast | link-state | l2vpn vpls | ipv4 mvpn | ipv6 mvpn | l2vpn evpn | ipv4 labeled-unicast | all
} summary [ vrf { <vrf-name> | <vrf-known-name> | ALL_VRFS_012345678901234 } ]
```

## Syntax Description

show	Show running system information
bgp	Display BGP status and configuration
vrf	(Optional) Virtual Router Context
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
summary	Display summarized information of BGP state
ipv4	Display BGP information for IPv4 address family
vpnv4	Display BGP information for VPNv4 address family
vpnv6	Display BGP information for VPNv6 address family
ipv6	Display BGP information for IPv6 address family
unicast	Display BGP information for unicast address family
multicast	Display BGP information for multicast address family
labeled-unicast	Display BGP information for labeled-unicast address family
mdt	Display BGP information for multicast distribution tree
link-state	Display BGP information for link-state address family
l2vpn	Display BGP information for L2VPN address family
vpls	Display BGP information for L2VPN VPLS address family
mvpn	Display BGP information for MVPN address family
evpn	Display BGP information for L2VPN EVPN address family
all	Display BGP information for all address families

## Command Mode

- /exec

**show boot**

## show boot

show boot

### Syntax Description

show	Show running system information
boot	Show Bootvar Variables

### Command Mode

- /exec

# show boot auto-copy

show boot auto-copy

## Syntax Description

show	Show running system information
boot	Show Bootvar Variables
auto-copy	See if autocopy is turned on

## Command Mode

- /exec

**show boot auto-copy list**

## show boot auto-copy list

show boot auto-copy list

### Syntax Description

show	Show running system information
boot	Show Bootvar Variables
auto-copy	See if autocopy is turned on
list	Show the list of files to be auto-copied

### Command Mode

- /exec

# show boot current

show boot current

## Syntax Description

show	Show running system information
boot	Show Bootvar Variables
current	Show Current Bootvar Variables

## Command Mode

- /exec

**show boot mode**

# show boot mode

show boot mode

## Syntax Description

show	Show boot mode information
boot	Show boot mode
mode	See if lxc boot is turned on

## Command Mode

- /exec

# show boot order

show boot order

## Syntax Description

show	Show running system information
boot	Show Bootvar Variables
order	Show Boot Order

## Command Mode

- /exec

**show boot timings**

# show boot timings

show [ system internal ] boot timings [ detail ]

## Syntax Description

show	Show running system information
system	(Optional) System-related show commands
internal	(Optional) Commands for internal use
boot	show boot information
timings	show boot timings
detail	(Optional) show detailed time statistics

## Command Mode

- /exec

# show boot variables

show boot variables

## Syntax Description

show	Show running system information
boot	Show Bootvar Variables
variables	Display the list of boot variables

## Command Mode

- /exec

```
show buffer-drop detail
```

## show buffer-drop detail

show buffer-drop detail

### Syntax Description

show	Show running system information
buffer-drop	Show Buffer Drop information
detail	Show Session Configuration

### Command Mode

- /exec

# show buffer-latency detail

show buffer-latency detail

## Syntax Description

show	Show running system information
buffer-latency	Show Buffer Drop information
detail	Show Session Configuration

## Command Mode

- /exec

show buffer-latency detail