



stcli disk Commands

- [stcli disk Command, on page 1](#)
- [stcli disk add Command, on page 1](#)
- [stcli disk list Command, on page 2](#)

stcli disk Command

Operations on the storage cluster disks.

```
stcli disk [-h] {list | add}
```

Syntax Description	Option	Required or Optional	Description
	add	One of set required.	Adds discovered new disks and specified blacklisted disks to the storage cluster.
	list	One of set required.	Lists the storage cluster disks in the node.
Command Default	None. One option from the set is required.		
Usage Guidelines	Accompany the <code>stcli disk</code> command with one of the positional arguments enclosed in <code>{ }</code> or optional arguments enclosed in <code>[]</code> .		

stcli disk add Command

Adds discovered new disks and specified blacklisted disks to the storage cluster.

```
stcli disk add [-h] [--id ID | --name NAME] --blacklisted-disk-ids [DISKIDS [DISKIDS . . .]]
```

Syntax Description	Option	Required or Optional	Description
	--id ID	One of set required.	ID of storage cluster node.
	--name NAME	One of set required.	Name of storage cluster node.

Option	Required or Optional	Description
--blacklisted-disk-ids [DISKIDS [DISKIDS . . .]]	Required.	Blacklisted disks to add to storage cluster. Separate multiple IDs with a space.

Command Default

None. One option from the set is required.

Usage Guidelines

Accompany the `stcli disk add` command with one of the positional arguments enclosed in { } plus required `--blacklisted-disk-ids` option, or optional arguments enclosed in [].

stcli disk list Command

Lists the storage cluster disks in the node.

```
stcli disk list [-h] [--id ID | --name NAME] [--rescan]
```

Syntax Description

Option	Required or Optional	Description
--id ID	One of set required.	ID of storage cluster node. The ID is listed in the <code>stcli cluster info</code> command. <code>local</code> defaults to the local node.
--ip NAME	One of set required.	IP address of storage cluster node. The IP is listed in the <code>stcli cluster info</code> command. <code>localhost</code> defaults to the local node.
--rescan	Optional.	Rescan disks.

Command Default

None. One option from the set is required. Defaults for the options are: `local` for *ID* and `localhost` for *NAME*.

Usage Guidelines

Accompany the `stcli disk list` command with one of the positional arguments or optional arguments enclosed in [].

**Note**

Sometimes when a disk is removed, it continues to be listed in cluster summary information. To refresh this, restart the HX cluster.