



VRF-Aware DNS

Last Updated: December 15, 2011

The VRF-Aware DNS feature enables the configuration of a Virtual Private Network (VPN) routing and forwarding instance (VRF) table so that the domain name system (DNS) can forward queries to name servers using the VRF table rather than the named DNS server in the global IP address space. This feature allows DNS requests to be resolved within the appropriate Multiprotocol Label Switching (MPLS) VPN.

- [Finding Feature Information, page 1](#)
- [Information About VRF-Aware DNS, page 1](#)
- [How to Configure VRF-Aware DNS, page 2](#)
- [Configuration Examples for VRF-Aware DNS, page 7](#)
- [Additional References, page 8](#)
- [Feature Information for VRF-Aware DNS, page 9](#)

Finding Feature Information

Your software release may not support all the features documented in this module. For the latest feature information and caveats, see the release notes for your platform and software release. To find information about the features documented in this module, and to see a list of the releases in which each feature is supported, see the Feature Information Table at the end of this document.

Use Cisco Feature Navigator to find information about platform support and Cisco software image support. To access Cisco Feature Navigator, go to www.cisco.com/go/cfn. An account on Cisco.com is not required.

Information About VRF-Aware DNS

- [Domain Name System, page 1](#)
- [VRF Mapping and VRF-Aware DNS, page 2](#)

Domain Name System

Domain Name System (DNS) is a standard that defines a domain naming procedure used in TCP/IP. A domain is a hierarchical separation of the network into groups and subgroups with domain names



Americas Headquarters:
Cisco Systems, Inc., 170 West Tasman Drive, San Jose, CA 95134-1706 USA

identifying the structure. The named groups consist of named objects, usually devices like IP hosts, and the subgroups are domains. DNS has three basic functions:

- **Name space:** This function is a hierarchical space organized from a single root into domains. Each domain can contain device names or more specific information. A special syntax defines valid names and identifies the domain names.
- **Name registration:** This function is used to enter names into the DNS database. Policies are outlined to resolve conflicts and other issues.
- **Name resolution:** This function is a distributed client and server name resolution standard. The name servers are software applications that run on a server and contain the resource records (RRs) that describe the names and addresses of those entities in the DNS name space. A name resolver is the interface between the client and the server. The name resolver requests information from the server about a name. A cache can be used by the name resolver to store learned names and addresses.

A DNS server can be a dedicated device or a software process running on a device. The server stores and manages data about domains and responds to requests for name conflict resolutions. In a large DNS implementation, there can be a distributed database over many devices. A server can be a dedicated cache.

VRF Mapping and VRF-Aware DNS

To keep track of domain names, IP has defined the concept of a name server, whose job is to hold a cache (or database) of names appended to IP addresses. The cached information is important because the requesting DNS will not need to query for that information again, which is why DNS works well. If a server had to query each time for the same address because it had not saved any data, the queried servers would be flooded and would crash.

A gateway for multiple enterprise customers can be secured by mapping the remote users to a VRF domain. Mapping means obtaining the IP address of the VRF domain for the remote users. By using VRF domain mapping, a remote user can be authenticated by a VRF domain-specific AAA server so that the remote-access traffic can be forwarded within the VRF domain to the servers on the corporate network.

To support traffic for multiple VRF domains, the DNS and the servers used to resolve conflicts must be VRF aware. VRF aware means that a DNS subsystem will query the VRF name cache first, then the VRF domain, and store the returned RRs in a specific VRF name cache. Users are able to configure separate DNS name servers per VRF.

VRF-aware DNS forwards queries to name servers using the VRF table. Because the same IP address can be associated with different DNS servers in different VRF domains, a separate list of name caches for each VRF is maintained. The DNS looks up the specific VRF name cache first, if a table has been specified, before sending a query to the VRF name server. All IP addresses obtained from a VRF-specific name cache are routed using the VRF table.

How to Configure VRF-Aware DNS

- [Defining a VRF Table and Assigning a Name Server to Enable VRF-Aware DNS, page 3](#)
- [Mapping VRF-Specific Hostnames to IP Addresses, page 4](#)
- [Configuring a Static Entry in a VRF-Specific Name Cache, page 5](#)
- [Verifying the Name Cache Entries in the VRF Table, page 6](#)

Defining a VRF Table and Assigning a Name Server to Enable VRF-Aware DNS

Perform this task to define a VRF table and assign a name server.

A VRF-specific name cache is dynamically created if one does not exist whenever a VRF-specific name server is configured by using the **ip name-server vrf** command option or a permanent name entry is configured by using the **ip host vrf** command option. The VRF name cache is removed whenever all name server and permanent entries in the VRF are disabled.

It is possible that multiple name servers are configured with the same VRF name. The system will send queries to those servers in turn until any of them responds, starting with the server that sent a response the last time.

SUMMARY STEPS

1. **enable**
2. **configure terminal**
3. **ip vrf vrf-name**
4. **rd route-distinguisher**
5. **exit**
6. **ip name-server [vrf vrf-name] server-address1 [server-address2...server-address6]**
7. **ip domain lookup [source-interface interface-type interface-number]**

DETAILED STEPS

Command or Action	Purpose
Step 1 enable Example: <pre>Router> enable</pre>	Enables privileged EXEC mode. <ul style="list-style-type: none"> • Enter your password if prompted.
Step 2 configure terminal Example: <pre>Router# configure terminal</pre>	Enters global configuration mode.
Step 3 ip vrf vrf-name Example: <pre>Router(config)# ip vrf vpn1</pre>	Defines a VRF table and enters VRF configuration mode. <ul style="list-style-type: none"> • The <i>vrf-name</i> argument can be up to 32 characters.

Command or Action	Purpose
<p>Step 4 <code>rd route-distinguisher</code></p> <p>Example:</p> <pre>Router(config)# rd 100:21</pre>	Creates routing and forwarding tables for a VRF.
<p>Step 5 <code>exit</code></p> <p>Example:</p> <pre>Router(config-vrf)# exit</pre>	Exits VRF configuration mode.
<p>Step 6 <code>ip name-server [vrf vrf-name] server-address1 [server-address2...server-address6]</code></p> <p>Example:</p> <pre>Router(config)# ip name-server vrf vpn1 172.16.1.111 172.16.1.2</pre>	<p>Assigns the address of one or more name servers to a VRF table to use for name and address resolution.</p> <ul style="list-style-type: none"> The vrf keyword is optional but must be specified if the name server is used with VRF. The <i>vrf-name</i> argument assigns a name to the VRF.
<p>Step 7 <code>ip domain lookup [source-interface interface-type interface-number]</code></p> <p>Example:</p> <pre>Router(config)# ip domain lookup</pre>	<p>(Optional) Enables DNS-based address translation.</p> <ul style="list-style-type: none"> DNS is enabled by default. You only need to use this command if DNS has been disabled.

Mapping VRF-Specific Hostnames to IP Addresses

Perform this task to map VRF-specific hostnames to IP addresses.

SUMMARY STEPS

- enable**
- configure terminal**
- Do one of the following:
 - `ip domain name [vrf vrf-name] name`
 -
 - `ip domain list [vrf vrf-name] name`

DETAILED STEPS

Command or Action	Purpose
<p>Step 1 <code>enable</code></p> <p>Example:</p> <pre>Router> enable</pre>	<p>Enables privileged EXEC mode.</p> <ul style="list-style-type: none"> Enter your password if prompted.
<p>Step 2 <code>configure terminal</code></p> <p>Example:</p> <pre>Router# configure terminal</pre>	<p>Enters global configuration mode.</p>
<p>Step 3 Do one of the following:</p> <ul style="list-style-type: none"> <code>ip domain name [vrf vrf-name] name</code> <code>ip domain list [vrf vrf-name] name</code> <p>Example:</p> <pre>Router(config)# ip domain name vrf vpnl cisco.com</pre> <p>Example:</p> <pre>Router(config)# ip domain list vrf vpnl cisco.com</pre>	<p>Defines a default domain name that the Cisco IOS software will use to complete unqualified hostnames.</p> <p>or</p> <p>Defines a list of default domain names to complete unqualified hostnames.</p> <ul style="list-style-type: none"> You can specify a default domain name that the Cisco IOS software will use to complete domain name requests. You can specify either a single domain name or a list of domain names. Any hostname that does not contain a complete domain name will have the default domain name you specify appended to it before the name is looked up. The vrf keyword and <i>vrf-name</i> argument specify a default VRF domain name. The ip domain list command can be entered multiple times to specify more than one domain name to append when doing a DNS query. The system will append each in turn until it finds a match.

Configuring a Static Entry in a VRF-Specific Name Cache

Perform this task to configure a static entry in a VRF-specific name cache.

A VRF-specific name cache is dynamically created if one does not exist whenever a name server is configured for the VRF by using the **ip name-server vrf** command option or a permanent name entry is configured by using the **ip host vrf** command option. The VRF name cache is removed whenever all name server and permanent entries in the VRF are disabled.

SUMMARY STEPS

- `enable`
- `configure terminal`
- `ip host [vrf vrf-name] name [tcp-port] address1 [address2...address8]`

DETAILED STEPS

Command or Action	Purpose
<p>Step 1 <code>enable</code></p> <p>Example:</p> <pre>Router> enable</pre>	<p>Enables privileged EXEC mode.</p> <ul style="list-style-type: none"> Enter your password if prompted.
<p>Step 2 <code>configure terminal</code></p> <p>Example:</p> <pre>Router# configure terminal</pre>	<p>Enters global configuration mode.</p>
<p>Step 3 <code>ip host [vrf vrf-name] name [tcp-port] address1 [address2...address8]</code></p> <p>Example:</p> <p>Example:</p> <pre>Router(config)# ip host vrf vpn3 company1.com 172.16.2.1</pre>	<p>Defines a static hostname-to-address mapping in the host cache.</p> <ul style="list-style-type: none"> If the vrf keyword and <i>vrf-name</i> arguments are specified, then a permanent entry is created only in the VRF-specific name cache.

Verifying the Name Cache Entries in the VRF Table

Perform this task to verify the name cache entries in the VRF table.

SUMMARY STEPS

- `enable`
- `show hosts [vrf vrf-name] {all| hostname} [summary]`
- `clear host [vrf vrf-name] {all| hostname}`

DETAILED STEPS

Command or Action	Purpose
<p>Step 1 <code>enable</code></p> <p>Example:</p> <pre>Router> enable</pre>	<p>Enables privileged EXEC mode.</p> <ul style="list-style-type: none"> Enter your password if prompted.

Command or Action	Purpose
<p>Step 2 <code>show hosts [vrf vrf-name] {all hostname} [summary]</code></p> <p>Example:</p> <pre>Router# show hosts vrf vpn2</pre>	<ul style="list-style-type: none"> • Displays the default domain name, the style of name lookup service, a list of name server hosts, the cached list of hostnames and addresses, and the cached list of hostnames and addresses specific to a particular Virtual Private Network (VPN). • The vrf keyword and <i>vrf-name</i> argument only display the entries if a VRF name has been configured. • If you enter the show hosts command without specifying any VRF, only the entries in the global name cache will display.
<p>Step 3 <code>clear host [vrf vrf-name] {all hostname}</code></p> <p>Example:</p> <pre>Router# clear host vrf vpn2</pre>	<p>(Optional) Deletes entries from the hostname-to-address global address cache or VRF name cache.</p>

Configuration Examples for VRF-Aware DNS

- [VRF-Specific Name Server Configuration Example, page 7](#)
- [VRF-Specific Domain Name List Configuration Example, page 7](#)
- [VRF-Specific Domain Name Configuration Example, page 8](#)
- [VRF-Specific IP Host Configuration Example, page 8](#)

VRF-Specific Name Server Configuration Example

The following example shows how to specify a VPN named `vpn1` with the IP addresses of `172.16.1.111` and `172.16.1.2` as the name servers:

```
ip name-server vrf vpn1 172.16.1.111 172.16.1.2
```

VRF-Specific Domain Name List Configuration Example

The following example shows how to add several domain names to a list in `vpn1` and `vpn2`. The domain name is only used for name queries in the specified VRF.

```
ip domain list vrf vpn1 company.com
ip domain list vrf vpn2 school.edu
```

If there is no domain list, the domain name that you specified with the **ip domain name** global configuration command is used. If there is a domain list, the default domain name is not used. The **ip domain list** command is similar to the **ip domain name** command, except that with the **ip domain list** command you can define a list of domains, each to be tried in turn until a match is found.

VRF-Specific Domain Name Configuration Example

The following example shows how to define cisco.com as the default domain name for a VPN named vpn1. The domain name is only used for name queries in the specified VRF.

```
ip domain name vrf vpn1 cisco.com
```

Any IP hostname that does not contain a domain name (that is, any name without a dot) will have the dot and cisco.com appended to it before being looked up.

VRF-Specific IP Host Configuration Example

The following example shows how to define two static hostname-to-address mappings in the host cache for vpn2 and vpn3:

```
ip host vrf vpn2 host2 10.168.7.18
ip host vrf vpn3 host3 10.12.0.2
```

Additional References

Related Documents

Related Topic	Document Title
DNS configuration tasks	"Configuring DNS" module
IP addressing services commands: complete command syntax, command mode, command history, defaults, usage guidelines, and examples	<i>Cisco IOS IP Addressing Services Command Reference</i>

Standards

Standards	Title
No new or modified standards are supported by this feature, and support for existing standards has not been modified by this feature.	--

MIBs

MIBs	MIBs Link
No new or modified MIBs are supported by this feature, and support for existing MIBs has not been modified by this feature.	To locate and download MIBs for selected platforms, Cisco IOS releases, and feature sets, use Cisco MIB Locator found at the following URL: http://www.cisco.com/go/mibs

RFCs

RFCs	Title
No new or modified RFCs are supported by this feature, and support for existing RFCs has not been modified by this feature.	--

Technical Assistance

Description	Link
The Cisco Support and Documentation website provides online resources to download documentation, software, and tools. Use these resources to install and configure the software and to troubleshoot and resolve technical issues with Cisco products and technologies. Access to most tools on the Cisco Support and Documentation website requires a Cisco.com user ID and password.	http://www.cisco.com/cisco/web/support/index.html

Feature Information for VRF-Aware DNS

The following table provides release information about the feature or features described in this module. This table lists only the software release that introduced support for a given feature in a given software release train. Unless noted otherwise, subsequent releases of that software release train also support that feature.

Use Cisco Feature Navigator to find information about platform support and Cisco software image support. To access Cisco Feature Navigator, go to www.cisco.com/go/cfn. An account on Cisco.com is not required.

Table 1 Feature Information for VRF-Aware DNS

Feature Name	Releases	Feature Information
VRF-Aware DNS	12.4(4)T	The VRF-Aware DNS feature enables the configuration of a Virtual Private Network (VPN) routing and forwarding instance (VRF) table so that the domain name system (DNS) can forward queries to name servers using the VRF table rather than the named DNS server in the global IP address space. This feature allows DNS requests to be resolved within the appropriate Multiprotocol Label Switching (MPLS) VPN.

Cisco and the Cisco logo are trademarks or registered trademarks of Cisco and/or its affiliates in the U.S. and other countries. To view a list of Cisco trademarks, go to this URL: www.cisco.com/go/trademarks. Third-party trademarks mentioned are the property of their respective owners. The use of the word partner does not imply a partnership relationship between Cisco and any other company. (1110R)

Any Internet Protocol (IP) addresses and phone numbers used in this document are not intended to be actual addresses and phone numbers. Any examples, command display output, network topology diagrams, and other figures included in the document are shown for illustrative purposes only. Any use of actual IP addresses or phone numbers in illustrative content is unintentional and coincidental.

© 2011 Cisco Systems, Inc. All rights reserved.