



# Creating an IP Access List and Applying It to an Interface

---

**Last Updated: March 4, 2013**

IP access lists provide many benefits for securing a network and achieving nonsecurity goals, such as determining quality of service (QoS) factors or limiting **debug** command output. This module describes how to create standard, extended, named, and numbered IP access lists. An access list can be referenced by a name or a number. Standard access lists filter on only the source address in IP packets. Extended access lists can filter on source address, destination address, and other fields in an IP packet.

After you create an access list, you must apply it to something in order for it to have any effect. This module describes how to apply an access list to an interface. However, there are many other uses for an access list, which are referenced in this module and described in other modules and in other configuration guides for various technologies.

- [Finding Feature Information, page 1](#)
- [Prerequisites for Creating an IP Access List and Applying It to an Interface, page 2](#)
- [Information About Creating an IP Access List and Applying It to an Interface, page 2](#)
- [How to Create an IP Access List and Apply It to an Interface, page 3](#)
- [Configuration Examples for Creating an IP Access List and Applying It to an Interface, page 15](#)
- [Where to Go Next, page 19](#)
- [Additional References, page 19](#)
- [Feature Information for Creating an IP Access List and Applying It to an Interface, page 21](#)

## Finding Feature Information

Your software release may not support all the features documented in this module. For the latest caveats and feature information, see [Bug Search Tool](#) and the release notes for your platform and software release. To find information about the features documented in this module, and to see a list of the releases in which each feature is supported, see the feature information table at the end of this module.

Use Cisco Feature Navigator to find information about platform support and Cisco software image support. To access Cisco Feature Navigator, go to [www.cisco.com/go/cfn](http://www.cisco.com/go/cfn). An account on Cisco.com is not required.



---

**Americas Headquarters:**  
Cisco Systems, Inc., 170 West Tasman Drive, San Jose, CA 95134-1706 USA

# Prerequisites for Creating an IP Access List and Applying It to an Interface

Before you create or apply an IP access list, you should understand the concepts in the “IP Access List Overview” module. You should also have IP running in your network.

## Information About Creating an IP Access List and Applying It to an Interface

- [Helpful Hints for Creating IP Access Lists, page 2](#)
- [Access List Remarks, page 3](#)
- [Additional IP Access List Features, page 3](#)

## Helpful Hints for Creating IP Access Lists

The following tips will help you avoid unintended consequences and help you create more efficient access lists.

- Create the access list before applying it to an interface (or elsewhere), because if you apply a nonexistent access list to an interface and then proceed to configure the access list, the first statement is put into effect, and the implicit **deny** statement that follows could cause you immediate access problems.
- Another reason to configure an access list before applying it is because an interface with an empty access list applied to it permits all traffic.
- All access lists need at least one **permit** statement; otherwise, all packets are denied and no traffic passes.
- Because the software stops testing conditions after it encounters the first match (to either a **permit** or **deny** statement), you will reduce processing time and resources if you put the statements that packets are most likely to match at the beginning of the access list. Place more frequently occurring conditions before less frequent conditions.
- Organize your access list so that more specific references in a network or subnet appear before more general ones.
- Use the statement **permit any any** if you want to allow all other packets not already denied. Using the statement **permit any any** in effect avoids denying all other packets with the implicit deny statement at the end of an access list. Do not make your first access list entry **permit any any** because all traffic will get through; no packets will reach the subsequent testing. In fact, once you specify **permit any any**, all traffic not already denied will get through.
- Although all access lists end with an implicit **deny** statement, we recommend use of an explicit **deny** statement (for example, **deny ip any any**). On most platforms, you can display the count of packets denied by issuing the **show access-list** command, thus finding out more information about who your access list is disallowing. Only packets denied by explicit **deny** statements are counted, which is why the explicit **deny** statement will yield more complete data for you.
- While you are creating an access list or after it is created, you might want to delete an entry.
  - You cannot delete an entry from a numbered access list; trying to do so will delete the entire access list. If you need to delete an entry, you need to delete the entire access list and start over.

- You can delete an entry from a named access list. Use the **no permit no deny** command to delete the appropriate entry.
- In order to make the purpose of individual statements more scannable and easily understood at a glance, you can write a helpful remark before or after any statement by using the **remark** command.
- If you want to deny access to a particular host or network and find out if someone from that network or host is attempting to gain access, include the **log** keyword with the corresponding **deny** statement so that the packets denied from that source are logged for you.
- This hint applies to the placement of your access list. When trying to save resources, remember that an inbound access list applies the filter conditions before the routing table lookup. An outbound access list applies the filter conditions after the routing table lookup.

## Access List Remarks

You can include comments or remarks about entries in any IP access list. An access list remark is an optional remark before or after an access list entry that describes the entry so that you do not have to interpret the purpose of the entry. Each remark is limited to 100 characters in length.

The remark can go before or after a **permit** or **deny** statement. Be consistent about where you add remarks. Users may be confused if some remarks precede the associated **permit** or **deny** statements and some remarks follow the associated statements.

The following is an example of a remark that describes what the subsequent **deny** statement does:

```
ip access-list extended telnetting
remark Do not allow host1 subnet to telnet out
deny tcp host 172.16.2.88 any eq telnet
```

## Additional IP Access List Features

Beyond the basic steps to create a standard or extended access list, you can enhance your access lists as mentioned below. Each of these methods is described completely in the module entitled “Refining an Access List.”

- You can impose dates and times when **permit** or **deny** statements in an extended access list are in effect, making your access list more granular and specific to an absolute or periodic time period.
- After you create a named or numbered access list, you might want to add entries or change the order of the entries, known as resequencing an access list.
- You can achieve finer granularity when filtering packets by filtering on noninitial fragments of packets.

## How to Create an IP Access List and Apply It to an Interface

This section describes the general ways to create a standard or extended access list using either a name or a number. Access lists are very flexible; the tasks simply illustrate one **permit** command and one **deny** command to provide you the command syntax of each. Only you can determine how many **permit** and **deny** commands you need and their order.

**Note**

The first two tasks in this module create an access list; you must apply the access list in order for it to function. If you want to apply the access list to an interface, perform the task "Applying the Access List to an Interface". If you don't intend to apply the access list to an interface, see the "Where to Go Next" for pointers to modules that describe other ways to apply access lists.

- [Creating a Standard Access List to Filter on Source Address, page 4](#)
- [Creating an Extended Access List, page 9](#)
- [Applying the Access List to an Interface, page 14](#)

## Creating a Standard Access List to Filter on Source Address

If you want to filter on source address only, a standard access list is simple and sufficient. There are two alternative types of standard access list: named and numbered. Named access lists allow you to identify your access lists with a more intuitive name rather than a number, and they also support more features than numbered access lists.

- [Creating a Named Access List to Filter on Source Address, page 4](#)
- [What to Do Next, page 6](#)
- [Creating a Numbered Access List to Filter on Source Address, page 6](#)
- [What to Do Next, page 8](#)

## Creating a Named Access List to Filter on Source Address

Use a standard, named access list if you need to filter on source address only. This task illustrates one **permit** statement and one **deny** statement, but the actual statements you use and their order depend on what you want to filter or allow. Define your **permit** and **deny** statements in the order that achieves your filtering goals.

### SUMMARY STEPS

1. **enable**
2. **configure terminal**
3. **ip access-list standard** *name*
4. **remark** *remark*
5. **deny** {*source* [*source-wildcard*] | **any**} [**log**]
6. **remark** *remark*
7. **permit** {*source* [*source-wildcard*] | **any**} [**log**]
8. Repeat some combination of Steps 4 through 7 until you have specified the sources on which you want to base your access list.
9. **end**
10. **show ip access-list**

**DETAILED STEPS**

	<b>Command or Action</b>	<b>Purpose</b>
<b>Step 1</b>	<p><b>enable</b></p> <p><b>Example:</b></p> <pre>Router&gt; enable</pre>	<p>Enables privileged EXEC mode.</p> <ul style="list-style-type: none"> <li>Enter your password if prompted.</li> </ul>
<b>Step 2</b>	<p><b>configure terminal</b></p> <p><b>Example:</b></p> <pre>Router# configure terminal</pre>	<p>Enters global configuration mode.</p>
<b>Step 3</b>	<p><b>ip access-list standard <i>name</i></b></p> <p><b>Example:</b></p> <pre>Router(config)# ip access-list standard R&amp;D</pre>	<p>Defines a standard IP access list using a name and enters standard named access list configuration mode.</p>
<b>Step 4</b>	<p><b>remark <i>remark</i></b></p> <p><b>Example:</b></p> <pre>Router(config-std-nacl)# remark deny Sales network</pre>	<p>(Optional) Adds a user-friendly comment about an access list entry.</p> <ul style="list-style-type: none"> <li>A remark can precede or follow an access list entry.</li> <li>In this example, the remark reminds the network administrator that the subsequent entry denies the Sales network access to the interface (assuming this access list is later applied to an interface).</li> </ul>
<b>Step 5</b>	<p><b>deny {<i>source</i> [<i>source-wildcard</i>]   <b>any</b>} [<b>log</b>]</b></p> <p><b>Example:</b></p> <pre>Router(config-std-nacl)# deny 172.16.0.0 0.0.255.255 log</pre>	<p>(Optional) Denies the specified source based on a source address and wildcard mask.</p> <ul style="list-style-type: none"> <li>If the <i>source-wildcard</i> is omitted, a wildcard mask of 0.0.0.0 is assumed, meaning match on all bits of the source address.</li> <li>Optionally use the keyword <b>any</b> as a substitute for the <i>source source-wildcard</i> to specify the source and source wildcard of 0.0.0.0 255.255.255.255.</li> <li>In this example, all hosts on network 172.16.0.0 are denied passing the access list.</li> <li>Because this example explicitly denies a source address and the <b>log</b> keyword is specified, any packets from that source are logged when they are denied. This is a way to be notified that someone on a network or host is trying to gain access.</li> </ul>

Command or Action	Purpose
<p><b>Step 6</b> <code>remark remark</code></p> <p><b>Example:</b></p> <pre>Router(config-std-nacl)# remark Give access to Tester's host</pre>	<p>(Optional) Adds a user-friendly comment about an access list entry.</p> <ul style="list-style-type: none"> <li>• A remark can precede or follow an access list entry.</li> <li>• This remark reminds the network administrator that the subsequent entry allows the Tester's host access to the interface.</li> </ul>
<p><b>Step 7</b> <code>permit {source [source-wildcard]   any} [log]</code></p> <p><b>Example:</b></p> <pre>Router(config-std-nacl)# permit 172.18.5.22 0.0.0.0</pre>	<p>Permits the specified source based on a source address and wildcard mask.</p> <ul style="list-style-type: none"> <li>• Every access list needs at least one <b>permit</b> statement; it need not be the first entry.</li> <li>• If the <i>source-wildcard</i> is omitted, a wildcard mask of 0.0.0.0 is assumed, meaning match on all bits of the source address.</li> <li>• Optionally use the keyword <b>any</b> as a substitute for the <i>source source-wildcard</i> to specify the source and source wildcard of 0.0.0.0 255.255.255.255.</li> <li>• In this example, host 172.18.5.22 is allowed to pass the access list.</li> </ul>
<p><b>Step 8</b> Repeat some combination of Steps 4 through 7 until you have specified the sources on which you want to base your access list.</p>	<p>Remember that all sources not specifically permitted are denied by an implicit <b>deny</b> statement at the end of the access list.</p>
<p><b>Step 9</b> <code>end</code></p> <p><b>Example:</b></p> <pre>Router(config-std-nacl)# end</pre>	<p>Exits standard named access list configuration mode and enters privileged EXEC mode.</p>
<p><b>Step 10</b> <code>show ip access-list</code></p> <p><b>Example:</b></p> <pre>Router# show ip access-list</pre>	<p>(Optional) Displays the contents of all current IP access lists.</p>

## What to Do Next

The access list you created is not in effect until you apply it to an interface, a vty line, or reference it from a command that uses an access list. See "Applying the Access List to an Interface" or "Where to Go Next" for pointers to modules that describe other ways to use access lists.

## reating a Numbered Access List to Filter on Source Address

Configure a standard, numbered access list if you need to filter on source address only and you prefer not to use a named access list.

IP standard access lists are numbered 1 to 99 or 1300 to 1999. This task illustrates one **permit** statement and one **deny** statement, but the actual statements you use and their order depend on what you want to filter or allow. Define your **permit** and **deny** statements in the order that achieves your filtering goals.

**SUMMARY STEPS**

1. **enable**
2. **configure terminal**
3. **access-list** *access-list-number* **remark** *remark*
4. **access-list** *access-list-number* **permit** { *source* [*source-wildcard*] | **any** } [**log**]
5. **access-list** *access-list-number* **remark** *remark*
6. **access-list** *access-list-number* **deny** { *source* [*source-wildcard*] | **any** } [**log**]
7. Repeat some combination of Steps 3 through 6 until you have specified the sources on which you want to base your access list.
8. **end**
9. **show ip access-list**

**DETAILED STEPS**

Command or Action	Purpose
<p><b>Step 1</b> <b>enable</b></p> <p><b>Example:</b></p> <pre>Router&gt; enable</pre>	<p>Enables privileged EXEC mode.</p> <ul style="list-style-type: none"> <li>• Enter your password if prompted.</li> </ul>
<p><b>Step 2</b> <b>configure terminal</b></p> <p><b>Example:</b></p> <pre>Router# configure terminal</pre>	<p>Enters global configuration mode.</p>
<p><b>Step 3</b> <b>access-list</b> <i>access-list-number</i> <b>remark</b> <i>remark</i></p> <p><b>Example:</b></p> <pre>Router(config)# access-list 1 remark Give access to user1</pre>	<p>(Optional) Adds a user-friendly comment about an access list entry.</p> <ul style="list-style-type: none"> <li>• A remark of up to 100 characters can precede or follow an access list entry.</li> </ul>

Command or Action	Purpose
<p><b>Step 4</b> <code>access-list access-list-number permit {source [source-wildcard]   any} [log]</code></p> <p><b>Example:</b></p> <pre>Router(config)# access-list 1 permit 172.16.5.22 0.0.0.0</pre>	<p>Permits the specified source based on a source address and wildcard mask.</p> <ul style="list-style-type: none"> <li>• Every access list needs at least one permit statement; it need not be the first entry.</li> <li>• Standard IP access lists are numbered 1 to 99 or 1300 to 1999.</li> <li>• If the source-wildcard is omitted, a wildcard mask of 0.0.0.0 is assumed, meaning match on all bits of the source address.</li> <li>• Optionally use the keyword <b>any</b> as a substitute for the source source-wildcard to specify the source and source wildcard of 0.0.0.0 255.255.255.255.</li> <li>• In this example, host 172.16.5.22 is allowed to pass the access list.</li> </ul>
<p><b>Step 5</b> <code>access-list access-list-number remark remark</code></p> <p><b>Example:</b></p> <pre>Router(config)# access-list 1 remark Don't give access to user2 and log any attempts</pre>	<p>(Optional) Adds a user-friendly comment about an access list entry.</p> <ul style="list-style-type: none"> <li>• A remark of up to 100 characters can precede or follow an access list entry.</li> </ul>
<p><b>Step 6</b> <code>access-list access-list-number deny {source [source-wildcard]   any} [log]</code></p> <p><b>Example:</b></p> <pre>Router(config)# access-list 1 deny 172.16.7.34 0.0.0.0</pre>	<p>Denies the specified source based on a source address and wildcard mask.</p> <ul style="list-style-type: none"> <li>• If the <i>source-wildcard</i> is omitted, a wildcard mask of 0.0.0.0 is assumed, meaning match on all bits of the source address.</li> <li>• Optionally use the abbreviation <b>any</b> as a substitute for the <i>source source-wildcard</i> to specify the source and source wildcard of 0.0.0.0 255.255.255.255.</li> <li>• In this example, host 172.16.7.34 is denied passing the access list.</li> </ul>
<p><b>Step 7</b> Repeat some combination of Steps 3 through 6 until you have specified the sources on which you want to base your access list.</p>	<p>Remember that all sources not specifically permitted are denied by an implicit <b>deny</b> statement at the end of the access list.</p>
<p><b>Step 8</b> <code>end</code></p> <p><b>Example:</b></p> <pre>Router(config)# end</pre>	<p>Exits global configuration mode and enters privileged EXEC mode.</p>
<p><b>Step 9</b> <code>show ip access-list</code></p> <p><b>Example:</b></p> <pre>Router# show ip access-list</pre>	<p>(Optional) Displays the contents of all current IP access lists.</p>

## What to Do Next



The access list you created is not in effect until you apply it to an interface, a vty line, or reference it from a command that uses an access list. See "Applying the Access List to an Interface" or "Where to Go Next" for pointers to modules that describe other ways to use access lists.

## Creating an Extended Access List

If you want to filter on anything other than source address, you need to create an extended access list. There are two alternative types of extended access list: named and numbered. Named access lists allow you to identify your access lists with a more intuitive name rather than a number, and they also support more features.

For details on how to filter something other than source or destination address, see the syntax descriptions in the command reference documentation.

- [Creating a Named Extended Access List, page 9](#)
- [What to Do Next, page 12](#)
- [Creating a Numbered Extended Access List, page 12](#)

### Creating a Named Extended Access List

Create a named extended access list if you want to filter on source and destination address, or a combination of addresses and other IP fields.

#### SUMMARY STEPS

1. **enable**
2. **configure terminal**
3. **ip access-list extended** *name*
4. **remark** *remark*
5. **deny** *protocol source* [*source-wildcard*] *destination* [*destination-wildcard*] [**option** *option-name*] [**precedence** *precedence*] [**tos** *tos*] [**established**] [**log** | **log-input**] [**time-range** *time-range-name*] [**fragments**]
6. **remark** *remark*
7. **permit** *protocol source* [*source-wildcard*] *destination* [*destination-wildcard*] [**option** *option-name*] [**precedence** *precedence*] [**tos** *tos*] [**established**] [**log** | **log-input**] [**time-range** *time-range-name*] [**fragments**]
8. Repeat some combination of Steps 4 through 7 until you have specified the fields and values on which you want to base your access list.
9. **end**
10. **show ip access-list**

## DETAILED STEPS

	Command or Action	Purpose
Step 1	<p><b>enable</b></p> <p><b>Example:</b></p> <pre>Router&gt; enable</pre>	<p>Enables privileged EXEC mode.</p> <ul style="list-style-type: none"> <li>Enter your password if prompted.</li> </ul>
Step 2	<p><b>configure terminal</b></p> <p><b>Example:</b></p> <pre>Router# configure terminal</pre>	<p>Enters global configuration mode.</p>
Step 3	<p><b>ip access-list extended <i>name</i></b></p> <p><b>Example:</b></p> <pre>Router(config)# ip access-list extended nomarketing</pre>	<p>Defines an extended IP access list using a name and enters extended named access list configuration mode.</p>
Step 4	<p><b>remark <i>remark</i></b></p> <p><b>Example:</b></p> <pre>Router(config-ext-nacl)# remark protect server by denying access from the Marketing network</pre>	<p>(Optional) Adds a user-friendly comment about an access list entry.</p> <ul style="list-style-type: none"> <li>A remark can precede or follow an access list entry.</li> <li>In this example, the remark reminds the network administrator that the subsequent entry denies the Sales network access to the interface.</li> </ul>

Command or Action	Purpose
<p><b>Step 5</b> <code>deny protocol source [source-wildcard] destination [destination-wildcard] [option option-name] [precedence precedence] [tos tos] [established] [log   log-input] [time-range time-range-name] [fragments]</code></p> <p><b>Example:</b></p> <pre>Router(config-ext-nacl)# deny ip 172.18.0.0 0.0.255.255 host 172.16.40.10 log</pre>	<p>(Optional) Denies any packet that matches all of the conditions specified in the statement.</p> <ul style="list-style-type: none"> <li>• If the <i>source-wildcard</i> or <i>destination-wildcard</i> is omitted, a wildcard mask of 0.0.0.0 is assumed, meaning match on all bits of the source or destination address, respectively.</li> <li>• Optionally use the keyword <b>any</b> as a substitute for the <i>source source-wildcard</i> or <i>destination destination-wildcard</i> to specify the address and wildcard of 0.0.0.0 255.255.255.255.</li> <li>• Optionally use the keyword <b>host source</b> to indicate a source and source wildcard of <i>source</i> 0.0.0.0 or the abbreviation <b>host destination</b> to indicate a destination and destination wildcard of <i>destination</i> 0.0.0.0.</li> <li>• In this example, packets from the source network 172.18.0.0 are denied access to host 172.16.40.10. Logging messages about packets permitted or denied by the access list are sent to the facility configured by the <b>logging facility</b> command (for example, console, terminal, or syslog). That is, any packet that matches the access list will cause an informational logging message about the packet to be sent to the configured facility. The level of messages logged to the console is controlled by the <b>logging console</b> command.</li> </ul>
<p><b>Step 6</b> <code>remark remark</code></p> <p><b>Example:</b></p> <pre>Router(config-ext-nacl)# remark allow TCP from any source to any destination</pre>	<p>(Optional) Adds a user-friendly comment about an access list entry.</p> <ul style="list-style-type: none"> <li>• A remark can precede or follow an access list entry.</li> </ul>
<p><b>Step 7</b> <code>permit protocol source [source-wildcard] destination [destination-wildcard] [option option-name] [precedence precedence] [tos tos] [established] [log   log-input] [time-range time-range-name] [fragments]</code></p> <p><b>Example:</b></p> <pre>Router(config-ext-nacl)# permit tcp any any</pre>	<p>Permits any packet that matches all of the conditions specified in the statement.</p> <ul style="list-style-type: none"> <li>• Every access list needs at least one permit statement.</li> <li>• If the <i>source-wildcard</i> or <i>destination-wildcard</i> is omitted, a wildcard mask of 0.0.0.0 is assumed, meaning match on all bits of the source or destination address, respectively.</li> <li>• Optionally use the keyword <b>any</b> as a substitute for the <i>source source-wildcard</i> or <i>destination destination-wildcard</i> to specify the address and wildcard of 0.0.0.0 255.255.255.255.</li> <li>• In this example, TCP packets are allowed from any source to any destination.</li> <li>• Use the <b>log-input</b> keyword to include input interface, source MAC address, or virtual circuit in the logging output.</li> </ul>
<p><b>Step 8</b> Repeat some combination of Steps 4 through 7 until you have specified the fields and values on which you want to base your access list.</p>	<p>Remember that all sources not specifically permitted are denied by an implicit <b>deny</b> statement at the end of the access list.</p>

	Command or Action	Purpose
Step 9	<b>end</b>  <b>Example:</b> Router(config-ext-nacl)# end	Ends configuration mode and brings the system to privileged EXEC mode.
Step 10	<b>show ip access-list</b>  <b>Example:</b> Router# show ip access-list	(Optional) Displays the contents of all current IP access lists.

## What to Do Next

The access list you created is not in effect until you apply it to an interface, a vty line, or reference it from a command that uses an access list. See "Applying the Access List to an Interface" or the "Where to Go Next" for pointers to modules that describe other ways to use access lists.

## Creating a Numbered Extended Access List

Create a numbered extended access list if you want to filter on source and destination address, or a combination of addresses and other IP fields, and you prefer not to use a name. Extended IP access lists are numbered 100 to 199 or 2000 to 2699.

### SUMMARY STEPS

1. **enable**
2. **configure terminal**
3. **access-list** *access-list-number* **remark** *remark*
4. **access-list** *access-list-number* **permit** *protocol* { *source* [*source-wildcard*] | **any** } { *destination* [*destination-wildcard*] | **any** } [**precedence** *precedence*] [**tos** *tos*] [**established**] [**log** | **log-input**] [**time-range** *time-range-name*] [**fragments**]
5. **access-list** *access-list-number* **remark** *remark*
6. **access-list** *access-list-number* **deny** *protocol* { *source* [*source-wildcard*] | **any** } { *destination* [*destination-wildcard*] | **any** } [**precedence** *precedence*] [**tos** *tos*] [**established**] [**log** | **log-input**] [**time-range** *time-range-name*] [**fragments**]
7. Repeat some combination of Steps 3 through 6 until you have specified the fields and values on which you want to base your access list.
8. **end**
9. **show ip access-list**

## DETAILED STEPS

Command or Action	Purpose
<p><b>Step 1</b> <code>enable</code></p> <p><b>Example:</b></p> <pre>Router&gt; enable</pre>	<p>Enables privileged EXEC mode.</p> <ul style="list-style-type: none"> <li>• Enter your password if prompted.</li> </ul>
<p><b>Step 2</b> <code>configure terminal</code></p> <p><b>Example:</b></p> <pre>Router# configure terminal</pre>	<p>Enters global configuration mode.</p>
<p><b>Step 3</b> <code>access-list <i>access-list-number</i> remark <i>remark</i></code></p> <p><b>Example:</b></p> <pre>Router(config)# access-list 107 remark allow Telnet packets from any source to network 172.69.0.0 (headquarters)</pre>	<p>(Optional) Adds a user-friendly comment about an access list entry.</p> <ul style="list-style-type: none"> <li>• A remark of up to 100 characters can precede or follow an access list entry.</li> </ul>
<p><b>Step 4</b> <code>access-list <i>access-list-number</i> permit <i>protocol</i> [<i>source</i> [<i>source-wildcard</i>]   <b>any</b>] [<i>destination</i> [<i>destination-wildcard</i>]   <b>any</b>] [<b>precedence</b> [<i>precedence</i>] [<i>tos tos</i>] [<b>established</b>] [<b>log</b>   <b>log-input</b>] [<i>time-range time-range-name</i>] [<b>fragments</b>]</code></p> <p><b>Example:</b></p> <pre>Router(config)# access-list 107 permit tcp any 172.69.0.0 0.0.255.255 eq telnet</pre>	<p>Permits any packet that matches all of the conditions specified in the statement.</p> <ul style="list-style-type: none"> <li>• Every access list needs at least one <b>permit</b> statement; it need not be the first entry.</li> <li>• Extended IP access lists are numbered 100 to 199 or 2000 to 2699.</li> <li>• If the <i>source-wildcard</i> or <i>destination-wildcard</i> is omitted, a wildcard mask of 0.0.0.0 is assumed, meaning match on all bits of the source or destination address, respectively.</li> <li>• Optionally use the keyword <b>any</b> as a substitute for the <i>source source-wildcard</i> or <i>destination destination-wildcard</i> to specify the address and wildcard of 0.0.0.0 255.255.255.255.</li> <li>• TCP and other protocols have additional syntax available. See the <b>access-list</b> command in the command reference for complete syntax.</li> </ul>
<p><b>Step 5</b> <code>access-list <i>access-list-number</i> remark <i>remark</i></code></p> <p><b>Example:</b></p> <pre>Router(config)# access-list 107 remark deny all other TCP packets</pre>	<p>(Optional) Adds a user-friendly comment about an access list entry.</p> <ul style="list-style-type: none"> <li>• A remark of up to 100 characters can precede or follow an access list entry.</li> </ul>

Command or Action	Purpose
<p><b>Step 6</b> <code>access-list access-list-number deny protocol {source [source-wildcard]   any} {destination [destination-wildcard]   any} [precedence precedence] [tos tos] [established] [log   log-input] [time-range time-range-name] [fragments]</code></p> <p><b>Example:</b></p> <pre>Router(config)# access-list 107 deny tcp any any</pre>	<p>Denies any packet that matches all of the conditions specified in the statement.</p> <ul style="list-style-type: none"> <li>If the <i>source-wildcard</i> or <i>destination-wildcard</i> is omitted, a wildcard mask of 0.0.0.0 is assumed, meaning match on all bits of the source or destination address, respectively.</li> <li>Optionally use the keyword <b>any</b> as a substitute for the <i>source source-wildcard</i> or <i>destination destination-wildcard</i> to specify the address and wildcard of 0.0.0.0 255.255.255.255.</li> </ul>
<p><b>Step 7</b> Repeat some combination of Steps 3 through 6 until you have specified the fields and values on which you want to base your access list.</p>	<p>Remember that all sources not specifically permitted are denied by an implicit <b>deny</b> statement at the end of the access list.</p>
<p><b>Step 8</b> <code>end</code></p> <p><b>Example:</b></p> <pre>Router(config)# end</pre>	<p>Ends configuration mode and brings the system to privileged EXEC mode.</p>
<p><b>Step 9</b> <code>show ip access-list</code></p> <p><b>Example:</b></p> <pre>Router# show ip access-list</pre>	<p>(Optional) Displays the contents of all current IP access lists.</p>

## Applying the Access List to an Interface

Perform this task to apply an access list to an interface.

### SUMMARY STEPS

1. `enable`
2. `configure terminal`
3. `interface type number`
4. `ip access-group {access-list-number | access-list-name} {in | out}`

## DETAILED STEPS

Command or Action	Purpose
<p><b>Step 1</b> <code>enable</code></p> <p><b>Example:</b></p> <pre>Router&gt; enable</pre>	<p>Enables privileged EXEC mode.</p> <ul style="list-style-type: none"> <li>• Enter your password if prompted.</li> </ul>
<p><b>Step 2</b> <code>configure terminal</code></p> <p><b>Example:</b></p> <pre>Router# configure terminal</pre>	<p>Enters global configuration mode.</p>
<p><b>Step 3</b> <code>interface type number</code></p> <p><b>Example:</b></p> <pre>Router(config)# interface ethernet 0</pre>	<p>Specifies an interface and enters interface configuration mode.</p>
<p><b>Step 4</b> <code>ip access-group {access-list-number   access-list-name} {in   out}</code></p> <p><b>Example:</b></p> <pre>Router(config-if)# ip access-group noncorp in</pre>	<p>Applies the specified access list to the incoming or outgoing interface.</p> <ul style="list-style-type: none"> <li>• When you are filtering on source addresses, you typically apply the access list to an incoming interface.</li> <li>• Filtering on source addresses is most efficient when applied near the destination.</li> </ul>

- [What to Do Next, page 15](#)

## What to Do Next

The access list you created is not in effect until you apply it to an interface, a vty line, or reference it from a command that uses an access list. See "Applying the Access List to an Interface" or "Where to Go Next" for pointers to modules that describe other ways to use access lists.

# Configuration Examples for Creating an IP Access List and Applying It to an Interface

- [Example Filtering on Source Address \(Hosts\), page 16](#)
- [Example Filtering on Source Address \(Subnet\), page 16](#)
- [Example Filtering on Source Address Destination Address and IP Protocols, page 16](#)
- [Example Filtering on Source Address \(Host and Subnets\) Using a Numbered Access List, page 17](#)
- [Example Preventing Telnet Access to a Subnet, page 17](#)

- [Example Filtering on TCP and ICMP Using Port Numbers, page 17](#)
- [Example Allowing SMTP \(E-mail\) and Established TCP Connections, page 17](#)
- [Example Preventing Access to the Web By Filtering on Port Name, page 18](#)
- [Example Filtering on Source Address and Logging the Packets Permitted and Denied, page 18](#)
- [Example: Limiting Debug Output, page 18](#)

## Example Filtering on Source Address (Hosts)

In the following example, the workstation belonging to Jones is allowed access to Ethernet interface 0 and the workstation belonging to Smith is not allowed access:

```
interface ethernet 0
 ip access-group workstations in
 !
 ip access-list standard workstations
 remark Permit only Jones workstation through
 permit 172.16.2.88
 remark Do not allow Smith workstation through
 deny 172.16.3.13
```

## Example Filtering on Source Address (Subnet)

In the following example, the Jones subnet is not allowed access to Ethernet interface 0, but the Main subnet is allowed access:

```
interface ethernet 0
 ip access-group prevention in
 !
 ip access-list standard prevention
 remark Do not allow Jones subnet through
 deny 172.22.0.0 0.0.255.255
 remark Allow Main subnet
 permit 172.25.0.0 0.0.255.255
```

## Example Filtering on Source Address Destination Address and IP Protocols

The following configuration example shows an interface with two access lists, one applied to outgoing packets and one applied to incoming packets. The standard access list named `Internet_filter` filters outgoing packets on source address. The only packets allowed out the interface must be from source 172.16.3.4.

The extended access list named `marketing_group` filters incoming packets. The access list permits Telnet packets from any source to network 172.26.0.0 and denies all other TCP packets. It permits any ICMP packets. It denies UDP packets from any source to network 172.26.0.0 on port numbers less than 1024. Finally, the access list denies all other IP packets and performs logging of packets passed or denied by that entry.

```
interface Ethernet0/5
 ip address 172.20.5.1 255.255.255.0
 ip access-group Internet_filter out
 ip access-group marketing_group in
 !
 ip access-list standard Internet_filter
 permit 172.16.3.4
 ip access-list extended marketing_group
 permit tcp any 172.26.0.0 0.0.255.255 eq telnet
 deny tcp any any
 permit icmp any any
 deny udp any 172.26.0.0 0.0.255.255 lt 1024
 deny ip any any
```



## Example Filtering on Source Address (Host and Subnets) Using a Numbered Access List

In the following example, network 10.0.0.0 is a Class A network whose second octet specifies a subnet; that is, its subnet mask is 255.255.0.0. The third and fourth octets of a network 10.0.0.0 address specify a particular host. Using access list 2, the Cisco IOS software would accept one address on subnet 48 and reject all others on that subnet. The last line of the list shows that the software would accept addresses on all other network 10.0.0.0 subnets.

```
interface ethernet 0
  ip access-group 2 in
!
access-list 2 permit 10.48.0.3
access-list 2 deny 10.48.0.0 0.0.255.255
access-list 2 permit 10.0.0.0 0.255.255.255
```

## Example Preventing Telnet Access to a Subnet

In the following example, the Jones subnet is not allowed to Telnet out Ethernet interface 0:

```
interface ethernet 0
  ip access-group telnetting out
!
ip access-list extended telnetting
  remark Do not allow Jones subnet to telnet out
  deny tcp 172.20.0.0 0.0.255.255 any eq telnet
  remark Allow Top subnet to telnet out
  permit tcp 172.33.0.0 0.0.255.255 any eq telnet
```

## Example Filtering on TCP and ICMP Using Port Numbers

In the following example, the first line of the extended access list named goodports permits any incoming TCP connections with destination ports greater than 1023. The second line permits incoming TCP connections to the Simple Mail Transfer Protocol (SMTP) port of host 172.28.1.2. The last line permits incoming ICMP messages for error feedback.

```
interface ethernet 0
  ip access-group goodports in
!
ip access-list extended goodports
  permit tcp any 172.28.0.0 0.0.255.255 gt 1023
  permit tcp any host 172.28.1.2 eq 25
  permit icmp any 172.28.0.0 255.255.255.255
```

## Example Allowing SMTP (E-mail) and Established TCP Connections

Suppose you have a network connected to the Internet, and you want any host on an Ethernet to be able to form TCP connections to any host on the Internet. However, you do not want IP hosts to be able to form TCP connections to hosts on the Ethernet except to the mail (SMTP) port of a dedicated mail host.

SMTP uses TCP port 25 on one end of the connection and a random port number on the other end. The same two port numbers are used throughout the life of the connection. Mail packets coming in from the Internet will have a destination port of 25. Outbound packets will have the port numbers reversed. The fact that the secure system behind the router always will accept mail connections on port 25 is what makes possible separate control of incoming and outgoing services. The access list can be configured on either the outbound or inbound interface.

In the following example, the Ethernet network is a Class B network with the address 172.18.0.0, and the address of the mail host is 172.18.1.2. The **established** keyword is used only for the TCP protocol to indicate an established connection. A match occurs if the TCP datagram has the ACK or RST bits set, which indicate that the packet belongs to an existing connection.

```
interface ethernet 0
 ip access-group 102 in
 !
access-list 102 permit tcp any 172.18.0.0 0.0.255.255 established
access-list 102 permit tcp any host 172.18.1.2 eq 25
```

## Example Preventing Access to the Web By Filtering on Port Name

In the following example, the Winter and Smith workstations are not allowed web access; other hosts on network 172.20.0.0 are allowed web access:

```
interface ethernet 0
 ip access-group no_web out
 !
ip access-list extended no_web
 remark Do not allow Winter to browse the web
 deny host 172.20.3.85 any eq http
 remark Do not allow Smith to browse the web
 deny host 172.20.3.13 any eq http
 remark Allow others on our network to browse the web
 permit 172.20.0.0 0.0.255.255 any eq http
```

## Example Filtering on Source Address and Logging the Packets Permitted and Denied

The following example defines access lists 1 and 2, both of which have logging enabled:

```
interface ethernet 0
 ip address 172.16.1.1 255.0.0.0
 ip access-group 1 in
 ip access-group 2 out
 !
access-list 1 permit 172.25.0.0 0.0.255.255 log
access-list 1 deny 172.30.0.0 0.0.255.255 log
 !
access-list 2 permit 172.27.3.4 log
access-list 2 deny 172.17.0.0 0.0.255.255 log
```

If the interface receives 10 packets from 172.25.7.7 and 14 packets from 172.17.23.21, the first log will look like the following:

```
list 1 permit 172.25.7.7 1 packet
list 2 deny 172.17.23.21 1 packet
```

Five minutes later, the console will receive the following log:

```
list 1 permit 172.25.7.7 9 packets
list 2 deny 172.17.23.21 13 packets
```

## Example: Limiting Debug Output

The following sample configuration uses an access list to limit the **debug** command output. Limiting the **debug** output restricts the volume of data to what you are interested in, saving you time and resources.

```
Device(config)# ip access-list acl1
```

```
Device(config-std-nacl)# remark Displays only advertisements for LDP peer in acl1
Device(config-std-nacl)# permit host 10.0.0.44
```

```
Device# debug mpls ldp advertisements peer-acl acl1
```

```
tagcon: peer 10.0.0.44:0 (pp 0x60E105BC): advertise 172.17.0.33
tagcon: peer 10.0.0.44:0 (pp 0x60E105BC): advertise 172.16.0.31
tagcon: peer 10.0.0.44:0 (pp 0x60E105BC): advertise 172.22.0.33
tagcon: peer 10.0.0.44:0 (pp 0x60E105BC): advertise 192.168.0.1
tagcon: peer 10.0.0.44:0 (pp 0x60E105BC): advertise 192.168.0.3
tagcon: peer 10.0.0.44:0 (pp 0x60E105BC): advertise 192.168.1.33
```

## Where to Go Next

This module describes how to create an access list that permits or denies packets based on source or destination address or protocol. However, there are other fields you could filter on, and other ways to use access lists. If you want to create an access list that filters on other fields or if you want to apply an access list to something other than an interface, you should decide what you want to restrict in your network and determine the type of access list that achieves your goal.

See the following table for references to other fields to filter and other ways to use an IP access list.

If you want to...	See
Filter based on IP Options, TCP flags, noncontiguous ports, or TTL value	“Creating an IP Access List to Filter IP Options, TCP Flags, Noncontiguous Ports, or TTL Values” module
Reorder your access list entries	“Refining an IP Access List” module
Limit access list entries to a time of day or week	“Refining an IP Access List” module
Restrict packets with noninitial fragments	“Refining an IP Access List” module
Restrict access to virtual terminal lines	“Controlling Access to a Virtual Terminal Line”
Control routing updates	“Configuring Routing Protocol-Independent Features” module in the <i>Cisco IOS IP Routing Protocols Configuration Guide</i>
Identify or classify traffic for features such as congestion avoidance, congestion management, and priority queuing	“Regulating Packet Flow on a Per-Interface Basis-- Using Generic Traffic Shaping” module in the <i>Quality of Service Solutions Configuration Guide</i>

## Additional References

### Related Documents

Related Topic	Document Title
Cisco IOS commands	<a href="#">Cisco IOS Master Commands List, All Releases</a>
Security Commands	<i>Cisco IOS Security Command Reference</i>

Related Topic	Document Title
Order of access list entries	"Refining an IP Access List"
Access list entries based on time of day or week	"Refining an IP Access List"
Packets with noninitial fragments	"Refining an IP Access List"
Filtering on IP Options, TCP flags, noncontiguous ports, or TTL values	"Creating an IP Access List to Filter IP Options, TCP Flags, Noncontiguous Ports, or TTL Values"
Access to virtual terminal lines	"Controlling Access to a Virtual Terminal Line"
Routing updates and policy routing	"Configuring Routing Protocol-Independent Features" modules in the <i>Cisco IOS IP Routing Protocols Configuration Guide</i>
Traffic identification or classification for features such as congestion avoidance, congestion management, and priority queuing	"Regulating Packet Flow on a Per-Interface Basis-- Using Generic Traffic Shaping" module in the <i>Quality of Service Solutions Configuration Guide</i>

#### Standards

Standard	Title
None	--

#### MIBs

MIB	MIBs Link
None	To locate and download MIBs for selected platforms, Cisco IOS releases, and feature sets, use Cisco MIB Locator found at the following URL: <a href="http://www.cisco.com/go/mibs">http://www.cisco.com/go/mibs</a>

#### RFCs

RFC	Title
None	--

**Technical Assistance**

Description	Link
The Cisco Support and Documentation website provides online resources to download documentation, software, and tools. Use these resources to install and configure the software and to troubleshoot and resolve technical issues with Cisco products and technologies. Access to most tools on the Cisco Support and Documentation website requires a Cisco.com user ID and password.	<a href="http://www.cisco.com/cisco/web/support/index.html">http://www.cisco.com/cisco/web/support/index.html</a>

## Feature Information for Creating an IP Access List and Applying It to an Interface

The following table provides release information about the feature or features described in this module. This table lists only the software release that introduced support for a given feature in a given software release train. Unless noted otherwise, subsequent releases of that software release train also support that feature.

Use Cisco Feature Navigator to find information about platform support and Cisco software image support. To access Cisco Feature Navigator, go to [www.cisco.com/go/cfn](http://www.cisco.com/go/cfn). An account on Cisco.com is not required.

**Table 1** Feature Information for Creating an IP Access List and Applying It to an Interface

Feature Name	Releases	Feature Configuration Information
Creating an IP Access List and Applying It to an Interface	12.0(32)S4	IP access lists provide many benefits for securing a network and achieving nonsecurity goals, such as determining quality of service (QoS) factors or limiting debug command output. This module describes how to create standard, extended, named, and numbered IP access lists. An access list can be referenced by a name or a number. Standard access lists filter on only the source address in IP packets. Extended access lists can filter on source address, destination address, and other fields in an IP packet.

Cisco and the Cisco logo are trademarks or registered trademarks of Cisco and/or its affiliates in the U.S. and other countries. To view a list of Cisco trademarks, go to this URL: [www.cisco.com/go/trademarks](http://www.cisco.com/go/trademarks). Third-party trademarks mentioned are the property of their respective owners. The use of the word partner does not imply a partnership relationship between Cisco and any other company. (1110R)

Any Internet Protocol (IP) addresses and phone numbers used in this document are not intended to be actual addresses and phone numbers. Any examples, command display output, network topology diagrams, and other figures included in the document are shown for illustrative purposes only. Any use of actual IP addresses or phone numbers in illustrative content is unintentional and coincidental.

© 2013 Cisco Systems, Inc. All rights reserved.