

Secure Copy

The Secure Copy (SCP) feature provides a secure and authenticated method for copying device configurations or device image files. SCP relies on Secure Shell (SSH), an application and protocol that provide a secure replacement for the Berkeley r-tools suite (Berkeley university's own set of networking applications). This document provides the procedure to configure a Cisco device for SCP server-side functionality.

- Finding Feature Information, page 1
- Prerequisites for Secure Copy, page 1
- Information About Secure Copy, page 2
- How to Configure Secure Copy, page 2
- Configuration Examples for Secure Copy, page 4
- Additional References, page 5
- Feature Information for Secure Copy, page 5
- Glossary, page 6

Finding Feature Information

Your software release may not support all the features documented in this module. For the latest caveats and feature information, see Bug Search Tool and the release notes for your platform and software release. To find information about the features documented in this module, and to see a list of the releases in which each feature is supported, see the feature information table at the end of this module.

Use Cisco Feature Navigator to find information about platform support and Cisco software image support. To access Cisco Feature Navigator, go to www.cisco.com/go/cfn. An account on Cisco.com is not required.

Prerequisites for Secure Copy

- Before enabling Secure Copy (SCP), you must correctly configure Secure Shell (SSH), authentication, and authorization on the device.
- Because SCP relies on SSH for its secure transport, the device must have a Rivest, Shamir, and Adelman (RSA) key pair.

Information About Secure Copy

How Secure Copy Works

The behavior of Secure Copy (SCP) is similar to that of remote copy (RCP), which comes from the Berkeley r-tools suite (Berkeley university's own set of networking applications), except that SCP relies on Secure Shell (SSH) for security. In addition, SCP requires that authentication, authorization, and accounting (AAA) authorization be configured so that the device can determine whether the user has the correct privilege level.

SCP allows a user with appropriate authorization to copy any file that exists in the Cisco IOS File System (IFS) to and from a device by using the **copy** command. An authorized administrator may also perform this action from a workstation.



Enable the SCP option while using the pscp.exe file with the Cisco software.

How to Configure Secure Copy

Configuring Secure Copy

To configure a Cisco device for Secure Copy (SCP) server-side functionality, perform the following steps.

SUMMARY STEPS

- 1. enable
- 2. configure terminal
- 3. aaa new-model
- **4.** aaa authentication login {default | list-name} method1 [method2...]
- **5.** aaa authorization {network | exec | commands level | reverse-access | configuration} {default | list-name} [method1 [method2...]]
- **6. username** name [**privilege** level] **password** encryption-type encrypted-password
- 7. ip scp server enable
- 8. exit
- 9. show running-config
- 10. debug ip scp

DETAILED STEPS

	Command or Action	Purpose
Step 1	enable	Enables privileged EXEC mode.

	Command or Action	Purpose
		Enter your password if prompted.
	Example:	
	Device> enable	
Step 2	configure terminal	Enters global configuration mode.
	Example:	
	Device# configure terminal	
Step 3	aaa new-model	Sets AAA authentication at login.
	Example:	
	Device(config)# aaa new-model	
Step 4	aaa authentication login {default list-name} method1 [method2]	Enables the AAA access control system.
	Example:	
	Device(config)# aaa authentication login default group tacacs+	
Step 5	aaa authorization {network exec commands level	Sets parameters that restrict user access to a network.
	reverse-access configuration { default list-name } [method1 [method2]]	Note The exec keyword runs authorization to determine if the user is allowed to run an EXEC
	Example:	shell; therefore, you must use the exec keyword when you configure SCP.
	Device(config)# aaa authorization exec default group tacacs+	
Step 6	username name [privilege level] password	Establishes a username-based authentication system.
	encryption-type encrypted-password	Note You may omit this step if a network-based
	Example:	authentication mechanism, such as TACACS+ or RADIUS, has been configured.
	Device(config)# username superuser privilege 2 password 0 superpassword	
Step 7	ip scp server enable	Enables SCP server-side functionality.
	Example:	
	Device(config)# ip scp server enable	
Step 8	exit	Exits global configuration mode and returns to privileged EXEC mode.
	Example:	LALC HOUE.
	Device(config)# exit	

	Command or Action	Purpose
Step 9	show running-config	(Optional) Displays the SCP server-side functionality.
	Example:	
	Device# show running-config	
Step 10	debug ip scp	(Optional) Troubleshoots SCP authentication problems.
	Example:	
	Device# debug ip scp	

Configuration Examples for Secure Copy

Example: Secure Copy Configuration Using Local Authentication

The following example shows how to configure the server-side functionality of Secure Copy (SCP). This example uses a locally defined username and password.

```
! AAA authentication and authorization must be configured properly in order for SCP to work. aaa new-model aaa authentication login default local aaa authorization exec default local username user1 privilege 15 password 0 lab ! SSH must be configured and functioning properly. ip scp server enable
```

Example: Secure Copy Configuration Using Network-Based Authentication

The following example shows how to configure the server-side functionality of Secure Copy (SCP) using a network-based authentication mechanism:

```
! AAA authentication and authorization must be configured properly in order for SCP to work.

aaa new-model

aaa authentication login default group tacacs+

aaa authorization exec default group tacacs+

! SSH must be configured and functioning properly.

ip scp server enable
```

Additional References

Related Documents

Related Topic	Document Title	
Cisco IOS commands	Cisco IOS Master Command List, All Releases	
Secure Shell Version 1 and 2 support	Secure Shell Configuration Guide	
Authentication and authorization commands	Cisco IOS Security Command Reference: Commands A to C	
Configuring authentication and authorization	Authentication, Authorization, and Accounting Configuration Guide	

Technical Assistance

Description	Link
The Cisco Support and Documentation website provides online resources to download documentation, software, and tools. Use these resources to install and configure the software and to troubleshoot and resolve technical issues with Cisco products and technologies. Access to most tools on the Cisco Support and Documentation website requires a Cisco.com user ID and password.	http://www.cisco.com/cisco/web/support/index.html

Feature Information for Secure Copy

The following table provides release information about the feature or features described in this module. This table lists only the software release that introduced support for a given feature in a given software release train. Unless noted otherwise, subsequent releases of that software release train also support that feature.

Use Cisco Feature Navigator to find information about platform support and Cisco software image support. To access Cisco Feature Navigator, go to www.cisco.com/go/cfn. An account on Cisco.com is not required.

Table 1: Feature Information for Secure Copy

Feature Name	Releases	Feature Information
Secure Copy	Cisco IOS 12.0(21)S Cisco IOS 12.2(2)T Cisco IOS 12.2(25)S	The Secure Copy (SCP) feature provides a secure and authenticated method for copying device configurations or device image files. SCP relies on Secure Shell (SSH), an application and protocol that provide a secure replacement for the Berkeley r-tools suite. The following commands were introduced or modified: debug ip scp, ip scp server enable.

Glossary

AAA—authentication, authorization, and accounting. A framework of security services that provide the method for identifying users (authentication), for remote access control (authorization), and for collecting and sending security server information used for billing, auditing, and reporting (accounting).

RCP—remote copy. Relies on Remote Shell (Berkeley r-tools suite) for security; RCP copies files such as device images and startup configurations to and from devices.

SCP—secure copy. Relies on SSH for security; SCP support allows secure and authenticated copying of anything that exists in the Cisco IOS File System (IFS). SCP is derived from RCP.

SSH—Secure Shell. An application and protocol that provide a secure replacement for the Berkeley r-tools suite. The protocol secures the sessions using standard cryptographic mechanisms, and the application can be used similar to the Berkeley rexec and rsh tools. SSH Version 1 is implemented in the Cisco software.