

Cisco Unified Border Element Configuration Guide Roadmap

Last Updated: December 19, 2011

This roadmap lists the features documented in the *Cisco Unified Border Element Configuration Guide* and maps them to the chapters in which they appear.



Before you can configure the software features described in this guide, you will need a Product Authorization Key (PAK). Before you start the configuration process, please register your products and activate your PAK at the following URL http://www.cisco.com/go/license.

For the latest feature information and caveats, see the release notes for your platform and software release. To find information about the features documented in this module, and to see a list of the releases in which each feature is supported, see the "Cisco Unified Border Element Configuration Guide Feature support" section.

Use Cisco Feature Navigator to find information about platform support and Cisco IOS software image support. To access Cisco Feature Navigator, go to http://www.cisco.com/go/cfn. An account on Cisco.com is not required.

For more information about Cisco IOS voice features, see the entire Cisco IOS Voice Configuration Library--including feature documents, and troubleshooting information--at http://www.cisco.com/univered/cc/td/doc/product/software/ios124/124tcg/vcl.htm .

The table below lists only the Cisco IOS software release that introduced support for a given feature in a given Cisco IOS software release train. Unless noted otherwise, subsequent releases of that Cisco IOS software release train also support that feature.

Table 1 Cisco Unified Border Element Configuration Guide Feature Support

Feature Name	Where Documented	Cisco IOS Release	Cisco UBE Version
Ability to Send a SIP Registration Message on a Border Element	"SIPAbility to Send a SIP Registration Message on a Border Element"	12.4(24)T	1.3



Feature Name	Where Documented	Cisco IOS Release	Cisco UBE Version
Cisco UBE MIB support	Supports CISCO-VOICE-DIAL-CONTROL-MIB objects to obtain call volume and call rate information and CISCO-DSP-MGMT-MIB objects to report transcoding sessions availability information on the Cisco Unified Border Element	15.0(1)XA	1.4
	See the Additional References section		
Clearable SIP-UA Statistics	The Clearable SIP-US Statistics feature adds MIB support. See the Additional References section	12.3(2)T	1.0
	No commands or configurations were introduced or modified in this release.		
Configurable Hostname in Locally Generated SIP Header	"SIPConfigurable Hostname in Locally Generated SIP Headers"	12.4(2)T	1.0
Configurable Pass-through of SIP INVITE Parameters	"Cisco Unified Border Element Support for Configurable Pass-through of SIP INVITE Parameters"	15.0(1)M	1.3
Core SIP Technology Enhancements	"SIPCore SIP Technology Enhancements"	12.2(13)T	1.0
DTMF Events Through SIP Signaling	"DTMF Events through SIP Signaling"	12.2(11)T	1.0
Dynamic Payload Type Interworking for DTMF and Codec Packets for SIP-to-SIP Calls	"Support for Dynamic Payload Type Interworking for DTMF and Codec Packets for SIP-to- SIP Calls"	15.0(1)XA	1.4
Error Response Code upon an Out-of-Dialog OPTIONS Ping Failure	"Configuring an Error Response Code upon an Out- of-Dialog OPTIONS Ping Failure"	15.1(1)T	1.4
Expire Timer Reset on Receiving or Sending SIP 183 Message	"Support for Expires Timer Reset on Receiving or Sending SIP 183 Message"	15.0(1)XA	1.4

Feature Name	Where Documented	Cisco IOS Release	Cisco UBE Version
iLBC Support for SIP and H. 323	"iLBC Support for SIP and H. 323"	12.2(11)T	1.0
INFO Method for DTMF Tone Generation	"SIPINFO Method for DTMF Tone Generation"	12.2(11)T	1.0
Interworking Between RSVP Capable and RSVP Incapable Networks	"Support for Interworking Between RSVP Capable and RSVP Incapable Networks"	15.0(1)XA	1.4
Interworking of Secure RTP calls for SIP and H.323	"Interworking of Secure RTP calls for SIP and H.323"	12.2(20)T	1.0
IP-to-IP Gateway: SIP-to-SIP Basic Functionality	IP-to-IP Gateway: SIP-to-SIP Basic Functionality	12.2(13)T3	1.0
Multiple Registrars on SIP Trunks	"Support for Multiple Registrars on SIP Trunks" section .	15.0(1)XA	1.4
Negotiation of an Audio Codec from a List of Codecs on Each Leg of a SIP-to-SIP Call on the Cisco Unified Border Element	"Support for Negotiation of an Audio Codec from a List of Codecs on Each Leg of a SIP- to-SIP Call on the Cisco Unified Border Element"	15.1(2)T	8.5
Out-of-dialog OPTIONS Ping for Specified SIP Servers or Endpoints	"Configuring Cisco UBE Out- of-dialog OPTIONS Ping for Specified SIP Servers or Endpoints"	12.4(22)YB	1.3
PAID, PPID, Privacy, PCPID, and PAURI Headers on the Cisco Unified Border Element	"Support for PAID, PPID, Privacy, PCPID, and PAURI Headers on the Cisco Unified Border Element"	12.4(22)YB	1.3
RFC 2782 Compliance with DNS SRV Queries	"SIPRFC 2782 Compliance with DNS SRV Queries"	12.2(8)T	1.0
RTP Media Loopback for SIP Calls	"Configuring RTP Media Loopback for SIP Calls"	15.1(4)M	8.7
Session Timer Support	"SIPSession Timer Support"	12.2(8)T	1.0
SIP - Enhanced 180 Provisional Response Handling	"SIPEnhanced 180 Provisional Response Handling"	12.2(8)T	1.0
SIP-to-SIP Basic Feature Functionality for Session Border Controller (SBC)	"SIP-to-SIP Extended Feature Functionality for Session Border Controller (SBC)"	12.4(4)T	1.0

Feature Name	Where Documented	Cisco IOS Release	Cisco UBE Version
SIP 181 Call is Being Forwarded Message	"Configuring Support for SIP 181 Call is Being Forwarded Message"	15.0(1)XA	1.4
SIP Diversion Header Enhancements	"SIP Diversion Header Enhancements"	12.4(22)T	1.3
SIP Parameter Modification	"SIP Parameter Modification"	12.4(15)XZ	1.2
SIP SRTP Fallback to Nonsecure RTP	"SIP SRTP Fallback to Nonsecure RTP"	12.4(22)T	1.3
SIP Video Calls with Flow Around Media	"SIP Video Calls with Flow Around Media"	12.4(15)XZ	1.2
SIPGateway Support for the Bind Command	"SIPGateway Support for the bind Command"	12.2(8)T	1.0
SIP-to-SIP Extended Feature Functionality for Session Border Controllers	"SIP-to-SIP Extended Feature Functionality for Session Border Controllers"	12.4(6)T	1.0
SIP-to-SIP Supplementary Services for Session Border Controller	"SIP-to-SIP Supplementary Services for Session Border Controller"	12.4(9)T	1.0
The official marketing name of Cisco Multiservice IP-to-IP Gateway was changed to Cisco Unified Border Element (Cisco UBE).	No configuration is required.	12.4(15)XY	1.1
Transparent Tunneling of QSIG and Q.931 over SIP TDM Gateway and SIP-SIP Cisco Unified Border Element	"Transparent Tunneling of QSIG and Q.931 over SIP TDM Gateway and SIP-SIP Cisco Unified Border Element"	12.4(15)XZ	1.2
Cisco Unified Border Element and Cisco Unified Communications Manager Express Support for Universal Packaging	Cisco Unified Border Element and Cisco Unified Communications Manager Express Support for Universal Packaging	15.0(1)M	1.3
Support inbound dial-peer match based on remote IP address on SIP trunks	Configuring an Inbound Dialpeer to Match the URI on SIP Calls	15.1(2)T	8.5

Cisco and the Cisco logo are trademarks or registered trademarks of Cisco and/or its affiliates in the U.S. and other countries. To view a list of Cisco trademarks, go to this URL: www.cisco.com/go/trademarks. Third-party trademarks mentioned are the property of their respective owners. The use of the word partner does not imply a partnership relationship between Cisco and any other company. (1110R)

Any Internet Protocol (IP) addresses and phone numbers used in this document are not intended to be actual addresses and phone numbers. Any examples, command display output, network topology diagrams, and other figures included in the document are shown for illustrative purposes only. Any use of actual IP addresses or phone numbers in illustrative content is unintentional and coincidental.

© 2011 Cisco Systems, Inc. All rights reserved.