



# Integrated IS-IS Nonstop Forwarding (NSF) Awareness

---

The Integrated IS-IS Nonstop Forwarding (NSF) Awareness feature allows customer premises equipment (CPE) routers that are NSF-aware to help NSF-capable routers perform nonstop forwarding of packets. This feature is part of the software code and requires no configuration.

## Feature Specifications for the Integrated IS-IS NSF Awareness Feature

---

### Feature History

Release	Modification
12.2(15)T	This feature was introduced.

---

### Supported Platforms

For information about platforms supported, refer to Cisco Feature Navigator.

---

## Finding Support Information for Platforms and Cisco IOS and Catalyst OS Software Images

Use Cisco Feature Navigator to find information about platform support and Cisco IOS and Catalyst OS software image support. To access Cisco Feature Navigator, go to <http://www.cisco.com/go/cfn>. An account on Cisco.com is not required.

## Contents

- [Information About IS-IS NSF Awareness, page 2](#)
- [Additional References, page 2](#)



---

**Americas Headquarters:**  
Cisco Systems, Inc., 170 West Tasman Drive, San Jose, CA 95134-1706 USA

© 2003–2008 Cisco Systems, Inc. All rights reserved.

# Information About IS-IS NSF Awareness

## Benefits of IS-IS NSF Awareness

The Integrated IS-IS Nonstop Forwarding Awareness feature allows CPE routers that are NSF-aware to help NSF-capable routers perform nonstop forwarding of packets. The awareness feature is part of the software code; it need not be configured.

The local router is not necessarily performing NSF; its awareness of NSF allows the integrity and accuracy of the RIB and link-state database occurring on the neighboring NSF-capable router to be maintained during the switchover process. Customers would want the IS-IS NSF Awareness feature when their routers are neighbors to NSF-capable routers.

## Additional References

### Related Documents

Related Topic	Document Title
Nonstop forwarding (NSF)	<i>Cisco Nonstop Forwarding with Stateful Switchover Deployment Guide</i>
Integrated IS-IS commands	<i>Cisco IOS IP Routing: ISIS Command Reference</i>

### Standards

Standards	Title
No new or modified standards are supported by this feature, and support for existing standards has not been modified by this feature.	—

### MIBs

MIBs	MIBs Link
No new or modified MIBs are supported by this feature, and support for existing MIBs has not been modified by this feature.	To locate and download MIBs for selected platforms, Cisco IOS releases, and feature sets, use Cisco MIB Locator found at the following URL: <a href="http://www.cisco.com/go/mibs">http://www.cisco.com/go/mibs</a>

## RFCs

RFCs	Title
No new or modified RFCs are supported by this feature, and support for existing RFCs has not been modified by this feature.	—

## Technical Assistance

Description	Link
<p>The Cisco Support website provides extensive online resources, including documentation and tools for troubleshooting and resolving technical issues with Cisco products and technologies.</p> <p>To receive security and technical information about your products, you can subscribe to various services, such as the Product Alert Tool (accessed from Field Notices), the Cisco Technical Services Newsletter, and Really Simple Syndication (RSS) Feeds.</p> <p>Access to most tools on the Cisco Support website requires a Cisco.com user ID and password.</p>	<p><a href="http://www.cisco.com/techsupport">http://www.cisco.com/techsupport</a></p>

Cisco and the Cisco Logo are trademarks of Cisco Systems, Inc. and/or its affiliates in the U.S. and other countries. A listing of Cisco's trademarks can be found at [www.cisco.com/go/trademarks](http://www.cisco.com/go/trademarks). Third party trademarks mentioned are the property of their respective owners. The use of the word partner does not imply a partnership relationship between Cisco and any other company. (1005R)

Any Internet Protocol (IP) addresses and phone numbers used in this document are not intended to be actual addresses and phone numbers. Any examples, command display output, network topology diagrams, and other figures included in the document are shown for illustrative purposes only. Any use of actual IP addresses or phone numbers in illustrative content is unintentional and coincidental.

© 2011 Cisco Systems, Inc. All rights reserved.

■ Additional References