



## INDEX

---

### A

A6 records [A-2](#)

AAAA records [A-2](#)

    DNS update [29-2](#)

About EDNS0 [14-7](#)

absolute domain names

*See* FQDN

access control lists (ACLs)

    creating [29-8](#)

acl command (CLI)

    create [29-9](#)

ACLs

*See* access control lists (ACLs)

addrblock-admin role [5-3](#)

    core functionality [5-3](#)

    ipv6-management subrole [5-3](#)

    ric-management subrole [5-3](#)

address allocation

    attributes [21-14](#)

    in scopes [21-15](#)

    priority [21-12](#)

    round-robin [21-11](#)

address-block-policy command (CLI)

    delete [24-23](#)

    get [24-23](#)

    getOption [24-23](#)

    listOptions [24-23](#)

    listVendorOptions [24-23](#)

    setVendorOption [24-23](#)

    show [24-23](#)

    unset [24-23](#)

    unsetOption [24-23](#)

    unsetVendorOption [24-23](#)

address blocks [9-3](#)

    adding [9-5](#)

    administrator role [9-1](#)

    children [9-9](#)

    delegating [9-6](#)

    embedded policies [24-23](#)

    viewing [9-4](#)

    when to add [9-5](#)

address blocks, DHCP [20-5](#)

    creating [24-22](#)

    default subnet size [24-23](#)

    orphaned leases [24-23](#)

    policies, associating [24-22](#)

addresses

    dynamic [9-1](#)

    IP format [1-4](#)

    IPv6 [27-2](#)

    provisional [25-11](#)

    static [9-1](#)

    usage, displaying [7-19](#)

address infrastructure, creating [5-30](#)

address pools, on-demand

*See* subnet allocation, DHCP

address ranges

    adding [5-30](#)

    scopes [21-11](#)

    subnets [9-10](#)

Address records

*See* A records

address restrictions, zones [5-33](#)

address space

    delegated [9-4](#)

- local, pulling from [5-40](#)
  - managing [9-1](#)
  - unified [9-3](#)
- address usage reports
  - displaying [7-19](#)
  - running [23-22](#)
- addr-trap command (CLI)
  - create [1-10, 21-22](#)
  - set
    - high-threshold [21-22](#)
    - low-threshold [21-22](#)
- admin command (CLI)
  - enterPassword [5-6](#)
  - set password [5-6](#)
- administrators [5-1, 1-1](#)
  - adding [5-6](#)
  - centrally managing [5-20](#)
  - local cluster [5-29](#)
  - passwords
    - adding [5-6](#)
    - changing [5-7](#)
    - managing [5-6](#)
  - pulling replica [5-22](#)
  - pushing to local [5-21](#)
  - regional [5-36](#)
  - relationship to groups [5-2](#)
  - types [5-2](#)
- admin role [1-1](#)
- AFSDB records [A-2](#)
- agent\_server\_log file [7-6](#)
- allocation priority, scopes [21-12](#)
  - algorithm [21-12](#)
  - limitation-id and [21-13](#)
- all-subnets-local, DHCP option [B-4](#)
- and, DHCP expression [26-7](#)
- A records [A-1, 1-1](#)
  - adding [16-3](#)
- arithmetic functions, DHCP expressions [26-7](#)
- arp-cache-timeout, DHCP option [B-5](#)
- as-blob, DHCP expression [26-7](#)
- ash, DHCP expression [26-8](#)
- as-sint, DHCP expression [26-7](#)
- associated-ip, DHCP option [B-18](#)
- as-string, DHCP expression [26-8](#)
- as-uint, DHCP expression [26-8](#)
- Asynchronous Transfer Mode (ATM) [26-25, 1-1](#)
- AT\_BLOB option validation [B-26](#)
- AT\_BOOL option validation [B-26](#)
- AT\_DATE option validation [B-26](#)
- AT\_DNSNAME option validation [B-26](#)
- AT\_INT8 option validation [B-26, B-27](#)
- AT\_INTI option validation [B-26](#)
- AT\_INT option validation [B-26](#)
- AT\_IP6ADDR option validation [B-26](#)
- AT\_IPADDR option validation [B-26](#)
- AT\_MACADDR option validation [B-26](#)
- AT\_MESSAGE option validation [B-26](#)
- AT\_NOLEN option validation [B-26](#)
- AT\_NSTRING option validation [B-26](#)
- AT\_OVERLOAD option validation [B-26](#)
- AT\_RANGEBYTE option validation [B-27](#)
- AT\_RANGESHORT option validation [B-27](#)
- AT\_RDNSNAME option validation [B-27](#)
- AT\_SHORT option validation [B-27](#)
- AT\_SHRTI option validation [B-27](#)
- AT\_SINTI option validation [B-27](#)
- AT\_SINT option validation [B-27](#)
- AT\_SSHORT option validation [B-27](#)
- AT\_SSHRTI option validation [B-27](#)
- AT\_STIME option validation [B-27](#)
- AT\_STRING option validation [B-27](#)
- AT\_TIME option validation [B-27](#)
- AT\_TYPECNT option validation [B-27](#)
- AT\_VENDOR\_CLASS option validation [B-27](#)
- AT\_VENDOR\_OPTS option validation [B-27](#)
- AT\_ZEROSIZE option validation [B-27](#)
- attributes
  - displaying [2-5](#)

- Help window 2-6
- modifying 2-5
- visibility 2-5
- auth, DHCPv6 option B-12
- authentication, DHCP option B-18
- authentication subrole (ccm-admin) 5-4
- authentication subrole (regional-admin) 5-5
- authoritative name servers 14-4, 1-1
  - adding 15-6
- authorization subrole (ccm-admin) 5-4
- authorization subrole (regional-admin) 5-5
- auto-configure, DHCP option B-19

---

## B

- base roles 5-1
- bcms-server-a, DHCPv6 option B-13
- bcms-server-d, DHCPv6 option B-13
- bcms-servers-a, DHCP option B-10
- bcms-servers-d, DHCP option B-10
- BIND files
  - format 15-9
  - importing 15-9
- bit-and, DHCP expression 26-8
- bit-andc1, DHCP expression 26-8
- bit-andc2, DHCP expression 26-8
- bit-eqv, DHCP expression 26-8
- bit-not, DHCP expression 26-9
- bit-or, DHCP expression 26-8
- bit-orc1, DHCP expression 26-8
- bit-orc2, DHCP expression 26-8
- bit-xor, DHCP expression 26-8
- boot-file, DHCP option B-10
- BOOTP
  - clients, moving/decommissioning 21-20
  - configuring 24-1
    - requirements 24-2
  - dynamic 28-30
    - enabling 24-3

- PARTNER-DOWN state 28-15
  - scopes, enabling for 21-20
- enabling, disabling 24-3
- failover 28-29
- file reply packet field 24-2
- relay 24-4
  - failover 28-4
  - routers 24-4
- scopes, enabling for 21-20
- siaddr reply packet field 24-2
- sname reply packet field 24-2
- static 28-29
- boot-size, DHCP option B-2
- broadcast-address, DHCP option B-4
- byte, DHCP expression 26-9

---

## C

- C/C++
  - API 30-9
  - extensions 30-4, 30-9
- cablelabs-125, DHCP option C-2
- cablelabs-17, DHCPv6 option C-7
- cablelabs-client-configuration, DHCP option B-19
- cable modem termination system (CMTS) 4-2
- cache
  - flushing DNS 18-9
- cache, refreshing session 2-4
- caching-only servers 14-5
- case-sensitivity of values 1-2
- catalina.*date*.log file 7-7
- ccm\_startup\_log file 7-6
- ccm\_upgrade\_status\_log file 7-6
- ccm-admin role 5-4
  - authentication subrole 5-4
  - authorization subrole 5-4
  - core functionality 5-4
  - database subrole 5-4
  - owner-region subrole 5-4

- server-management subrole 5-4
- ccm command (CLI)
  - polling attribute, setting 6-12
  - set 7-3
- CCM database 1-2
  - files 7-6
  - logging 7-6
- ccm-management subrole (cfg-admin) 5-4
- CCM server 1-1, 4-2
  - polling attributes 6-12
- cdns\_log file 7-6
- cdns\_startup\_log file 7-6
- cdns64 command (CLI)
  - create 18-5
  - enable 18-5
- cdns command (CLI)
  - addException 18-4
  - addRootHint 18-8
  - listExceptions 18-4
  - removeException 18-4
  - resetStats 7-12
  - set
    - cache-max-ttl 18-7
    - cache-min-ttl 18-8
    - msg-cache-size 18-9
    - rrset-cache-size 18-9
- cdns-management subrole (cfg-admin) 5-4
- cdnssec command (CLI)
  - create 18-5
  - enable 18-5
- central-cfg-admin role 5-5
  - core functionality 5-5
  - dhcp-management subrole 5-5
  - ric-management subrole 5-5
- central configuration 6-1
- Central Configuration Management (CCM) server
  - See CCM server
- central-dns-admin role 5-5
  - core functionality 5-5
  - security-management subrole 5-5
  - server-management subrole 5-5
- central-host-admin role 5-5
  - core functionality 5-5
- cfg-admin role 5-4
  - ccm-management subrole 5-4
  - core functionality 5-4
  - dhcp-management subrole 5-4
  - dns-management subrole 5-4
  - ric-management subrole 5-4
  - snmp-management subrole 5-4
  - tftp-management subrole 5-4
- chaddr, DHCP field 1-2
- change set database, DNS update 17-5
  - checkpoint interval 17-5
- check-lease-acceptable extension point, DHCP 24-12, 30-37
- checkpointing, zone
  - file
    - backing up 8-5
    - dumping 17-5
    - forcing 17-5
- checkports\_log file 7-6
- child
  - address blocks 9-9
  - subnets 9-9
- ciaddr, DHCP field 24-18, 1-2
- cisco-auto-configure, DHCP option B-20
- cisco-client-last-transaction-time, DHCP option B-20
- cisco-client-requested-host-name, DHCP option B-20
- cisco-leased-ip, DHCP option B-20
- Cisco routers 24-4
- cisco-vpn-id, DHCP option B-20
- classless-static-route, DHCP option B-19
- class of service 20-11
- CLI 1-1, 2-10
  - command syntax 2-10
- client-class command (CLI)
  - create 25-3

- delete 25-3
- list 25-3
- listnames 25-3
- set 25-3
  - add-to-environment-dictionary 23-18
  - default-vpn 24-21
  - host-name 25-4
  - limitation-id 25-15
  - limitation-key 26-1
  - over-limit-client-class-name 25-15
  - override-client-id 23-19
  - override-vpn 24-21
  - selection-criteria 25-3
- show 25-3
- client-classes
  - client entries, skipping 25-12
  - configuring 25-1
  - defining 25-2
  - DHCPv6 27-33
  - editing 25-5
  - embedded policies 25-5
  - enabling 20-13
  - failover synchronization effect 28-9
  - host-name setting 25-4
  - local, pulling 6-18
  - local, pushing 6-17
  - lookup ID 23-19
  - process 25-2
  - processing order to determine 25-6
  - quality of service 20-11
  - RADIUS pool name, mapping 25-6
  - regional 6-17
  - troubleshooting 25-7
  - user class identifier, mapping 25-6
- client-class-policy command (CLI)
  - set 25-5
  - setLeaseTime 25-5
  - setOption 25-5
  - setV6Option 25-5
  - setV6VendorOption 25-5
  - setVendorOption 25-5
  - show 25-5
- client command (CLI)
  - create 25-9
  - delete 25-9
  - list 25-9
  - listnames 25-9
  - set 25-9
    - action=one-shot 25-11
    - authenticate-until 25-12
    - client-class-name 25-9
    - client-lookup-id 26-1
    - default-vpn 24-21
    - limitation-id 25-15
    - limitation-key 26-1
    - over-limit-client-class-name 25-15
    - override-vpn 24-21
    - policy-name 25-11
    - selection-criteria 25-9
  - show 25-9
- client-data, DHCPv6 option B-14
- client-fqdn, DHCP option B-18
- client-fqdn, DHCPv6 option B-13
- client ID
  - overriding 23-19
  - reservations, using for lease 23-19
- client-identifier, DHCP option B-10
- client-identifier, DHCPv6 option B-11
- client-last-transaction-time, DHCP option B-18
- client-policy command (CLI)
  - set 25-10
  - setLeaseTime 25-10
  - setOption 25-10
  - setV6Option 25-10
  - setV6VendorOption 25-10
  - setVendorOption 25-10
  - show 25-10
- client reservations

- using 23-11
- clients
  - authentication, limiting 25-12
  - caching parameters 25-13
  - configuring 25-8
  - default 25-8
  - DHCPv6 27-7, 27-34
  - editing 25-9
  - embedded policies 25-9
  - failover synchronization effect 28-9
  - hardware address 1-2
  - IP address 24-18, 1-2
  - lease request name 20-13
  - listing 25-9
  - properties 25-9
  - provisioning 25-13
  - subscribers, set by limitation-id 25-15
  - unknown 25-11
  - Windows 2000 25-10
  - your IP address 24-18, 1-11
- clt-time, DHCPv6 option B-14
- cluster command (CLI)
  - create 6-3
  - polling attributes, setting 6-12
  - set 6-3
- clusters
  - activating 6-10
  - data, recovering 6-10
  - deactivating 6-10
  - local 4-2
  - polling attributes 6-12
  - poll-replica-interval 6-9
  - poll-replica-offset 6-9
  - poll-subnet-util-interval 9-13
  - poll-subnet-util-offset 9-13
  - poll-subnet-util-retry 9-13
  - regional 4-2
  - secure connections 6-2
  - time skew effects 6-12
- CMTS
  - See* cable modem termination system
- CNAME records A-3, 1-2
- cnr\_exim utility 8-10
- cnr\_keygen utility 29-10
- cnr\_shadow\_backup utility 8-3
  - using third party programs 8-3
- cnr\_tactool utility 7-30
- cnrdb\_checkpoint utility 8-13
- cnrdb\_recover utility 8-12
- cnrdb\_verify utility 8-13
- CNRDB database 1-2
  - backing up 8-5
  - damaged 8-6
  - files 8-5
  - log files 8-5
  - recovering 8-8
- cnrsnmp\_log file 7-6
- cnrwebui\_access\_log.date.txt file 7-7
- cnrwebui\_log file 7-6
- .com domain 14-2
- comment, DHCP expression 26-9
- COMMUNICATIONS-INTERRUPTED, failover 20-10
- concat, DHCP expression 26-9
- concepts and protocols 1-1
- config\_ccm\_log file 7-6
- configuration
  - file, lease-notification 23-30
  - guidelines 4-5, 4-6
  - special cases 4-7
- configuring client-classes
  - See* client-classes
- configuring DHCP servers
  - scopes, *See* scopes
- configuring DHCP servers, *See* DHCP
- configuring DNS servers
  - loopback zones, *See* loopback, zones
  - NOTIFY, *See* NOTIFY
  - secondary, *See* secondary, name servers

- configuring DNS update
  - See* DNS update
- configuring DNS update maps
  - See* DNS update, maps
- configuring failover
  - See* failover, DHCP
- configuring policies
  - See* policies
- configuring virtual private networks
  - See* VPNs
- consistency rules
  - adding [7-23](#)
  - listing [7-23](#)
  - viewing [7-23](#)
- constrained roles [5-3, 1-8](#)
- cookie-servers, DHCP option [B-2](#)
- create-prefix, link template expression [27-16](#)
- create-prefix-addr
  - link template expression [27-16](#)
  - prefix template expression [27-24](#)
- create-prefix-range
  - link template expression [27-17](#)
  - prefix template expression [27-24](#)
- create-v6-option
  - link template expression [27-17, 27-24](#)
- cron task (UNIX) [23-29](#)

---

## D

- dashboard [3-1](#)
  - Caching DNS general indicators chart [3-22](#)
  - DHCP address utilization chart [3-14](#)
  - DHCP buffer capacity chart [3-13](#)
  - DHCP DNS update activity chart [3-14](#)
  - DHCP failover status chart [3-15](#)
  - DHCP general indicators chart [3-16](#)
  - DHCP response latency chart [3-13](#)
  - DHCP server request activity [3-11](#)
  - DHCP server response activity [3-12](#)
- DNS caching chart [3-22](#)
- DNS general indicators chart [3-19](#)
- DNS inbound zone transfers chart [3-17](#)
- DNS incoming queries chart [3-21](#)
- DNS network errors chart [3-18](#)
- DNS outbound zone transfers chart [3-17](#)
- DNS queries responses chart [3-20](#)
- DNS queries type chart [3-20](#)
- DNS related servers errors chart [3-18](#)
- system metrics chart [3-9](#)
- databases
  - backup [8-1](#)
    - strategies [8-2](#)
    - third party programs [8-3](#)
  - binding [1-1](#)
  - CNRDB [8-2, 1-2](#)
  - DNS update change set [17-5](#)
  - exporting [8-10](#)
  - importing [8-10](#)
  - log files [7-6](#)
  - replica [6-9](#)
  - startup, loading on [7-1](#)
- database subrole (ccm-admin) [5-4](#)
- database subrole (regional-admin) [5-5](#)
- data directory, changing [8-2](#)
- Data over Cable Service Interface Specification
  - See* DOCSIS
- datatype, DHCP expression [26-9](#)
- default-ip-ttl, DHCP option [B-3](#)
- default-tcp-ttl, DHCP option [B-5](#)
- delegated address space [9-4](#)
- delegation-only zones [17-3](#)
- deployment cases
  - large enterprise network [4-4, 29-2](#)
  - small to medium size LANs [4-3](#)
- dex.h file [30-10](#)
- dex extensions [30-9](#)
- DHCID records [A-3](#)
  - DNS update [29-2](#)

## DHCP

- administration [20-2](#)
- buffers, allocating [24-5](#)
- clients
  - client lease request name [20-13](#)
  - IP addresses [24-18, 1-2](#)
  - MAC addresses [20-13, 1-2](#)
  - your IP address [24-18, 1-11](#)
- client-server model [20-1](#)
- configuration guidelines [4-5](#)
- custom options [22-10](#)
- custom options, adding [22-10](#)
- dashboard
  - address utilization chart [3-14](#)
  - buffer capacity chart [3-13](#)
  - DHCP failover status chart [3-15](#)
  - DNS update activity chart [3-14](#)
  - general indicators chart [3-16](#)
  - response latency chart [3-13](#)
  - server request activity chart [3-11](#)
  - server response activity chart [3-12](#)
- defer lease extensions option [24-6](#)
- equal-priority-most-available [21-13, 21-15](#)
- ethernet addresses [21-2](#)
- forwarding [24-24](#)
- last transaction time granularity [24-7](#)
- lease history collection [6-14](#)
- leasequery, *See* leasequery
- lease-state updates to LDAP [25-24](#)
- lease times [21-2](#)
- library path [24-10](#)
- log settings [24-15](#)
- option 82 [25-13](#)
- options [22-5](#)
  - RFC 2132 [B-1](#)
  - syntax for more complex [22-7](#)
  - validation [B-15](#)
- ping packets [24-6](#)
- policies, *See* policies
- priority-address-allocation [21-15](#)
- related servers, displaying [7-20](#)
- related servers, getting [6-9](#)
- remote WAN configuration [21-2](#)
- request
  - buffers [28-19](#)
  - processing [20-12](#)
- requests, number of [24-5](#)
- requests for other servers, ignoring [23-21](#)
- response buffers [28-19](#)
- responses, number of [24-6](#)
- reverse zones, synthesizing [29-4](#)
- sample users [20-2](#)
- scopes disabling for [21-20](#)
- servers
  - configuring [24-1](#)
  - forwarding, switching [24-24](#)
  - interface, removing address [21-2](#)
  - interface, setting [21-2](#)
  - IP address of next DHCP [1-9](#)
  - logging [7-6, 29-26](#)
  - troubleshooting [24-15](#)
- SMS network discovery records [24-10](#)
- subnet utilization collection [6-13](#)
- switching [24-24](#)
- unicast, enabling [24-6](#)
- v6, *See* DHCPv6
- dhcp\_startup\_log file [7-6](#)
- dhcp-address-block command (CLI)
  - set
    - default-subnet-size [24-23](#)
    - vpn [24-20](#)
    - vpn-id [24-20](#)
  - unset [24-22](#)
- dhcp-admin role [5-4](#)
  - core functionality [5-4](#)
  - ipv6-management subrole [5-4](#)
- dhcp-client-identifier, DHCP option [B-10](#)
- dhcp command (CLI)



- attachExtension 24-24, 30-2
- detachExtension 24-24, 30-2
- disable
  - vpn-communication 24-23
- enable
  - client-class 25-3
  - collect-sample-counters 7-12
  - defer-lease-extensions 24-6
  - delete-orphaned-leases 24-23
  - delete-orphaned-subnets 24-23
  - get-subnet-mask-from-policy 22-5
  - hardware-unicast 24-6
  - ignore-requests-for-other-servers 23-21
  - ip-history 23-23
  - return-client-fqdn-if-asked 29-20
  - save-lease-renewal-time 25-23
  - skip-client-lookup 25-12
  - update-dns-for-bootp 24-3
  - use-client-fqdn 29-19
  - use-client-fqdn-first 29-20
  - use-ldap-client-data 25-20
- get 24-8
- getPrefixCount 27-29
- getRelatedServers 6-9, 7-22
- getScopeCount 21-11
- getStats 7-16
- lease history collection attributes 6-14
- limitationList 7-2, 25-17
- resetStats 7-12
- set 24-8
  - activity-summary-interval 7-12, 24-16
  - client-cache-count 25-13
  - client-cache-ttl 25-13
  - client-class-lookup-id 23-19, 25-14, 26-1
  - default-free-address-config 1-10, 3-15
  - failover-poll-interval 28-19
  - failover-poll-timeout 28-19
  - failover-recover 28-13
  - last-transaction-time-granularity 24-7
  - ldap-mode 25-20
  - log-settings 7-6, 24-15, 29-18
  - map-radius-class 25-6
  - max-dhcp-requests 24-5, 28-19
  - max-dhcp-responses 24-6
  - max-dhcp-responses) 28-19
  - max-ping-packets 24-6
  - max-waiting-packets 24-16
  - sms-lease-interval 24-10
  - sms-library-path 24-10
  - sms-network-discovery 24-10
  - sms-site-code 24-10
  - synthesize-reverse-zone 29-6
  - traps-enabled 1-10
  - username 25-19
  - v6-default-free-address-config 1-10, 3-15
  - vpn-communication 24-22
- setPartnerDown 28-18
- show 24-8
- start 7-3
- stop 7-3
- subnet utilization collection attributes 6-13
- unset 24-8
- updateSms 24-9, 24-10, 28-20
- DHCPDISCOVER packets 25-13
- dhcp-dns-update command (CLI)
  - create 29-6
  - enable
    - update-dns-first 29-6
    - update-dns-for-bootp 29-6
  - set
    - backup-server-addr 29-6
    - backup-server-key 29-12
    - dynamic-dns 29-6
    - forward-zone-name 29-5
    - reverse-zone-name 29-6
    - reverse-zone-prefix-length 29-4
    - server-addr 29-6
    - server-key 29-12

- synthesize-name 29-5
  - synthetic-name-stem 29-5
  - v6-synthetic-name-generator 29-3
- DHCP forwarding, enabling 24-24
- dhcp-interface command (CLI) 21-2
- DHCPLEASEQUERY packets
  - See* leasequery
- dhcp-lease-time, DHCP option B-8
- dhcp-management subrole (central-cfg-admin) 5-5
- dhcp-management subrole (cfg-admin) 5-4
- dhcp-management subrole (regional-addr-admin) 5-5
- dhcp-max-message-size, DHCP option B-9
- dhcp-message, DHCP option B-9
- dhcp-message-type, DHCP option B-8
- dhcp-option-overload, DHCP option B-8
- dhcp-parameter-request-list, DHCP option B-9
- dhcp-rebinding-time, DHCP option B-9
- dhcp-renewal-time, DHCP option B-9
- DHCPRENEW packets 25-16
- dhcp-requested-address, DHCP option B-8
- DHCPREQUEST packets 21-2, B-8
- dhcp-server-identifier, DHCP option B-9
- dhcp-user-class-id, DHCP option B-18
- DHCPv6
  - AAAA records. 29-2
  - address generation 27-4
  - bindings 27-7
  - client-classes 27-33
  - client FQDN, using 29-4
  - clients 27-34
  - concepts 27-2
  - DHCID records. 29-2
  - DNS update
  - DNS update, upgrading 29-3
  - lease affinity 27-8
  - lease reservations 27-9
  - leases 27-7
  - links 27-2
  - managing 27-1
  - options 27-34
  - policies 27-32
  - policy hierarchy 27-11
  - prefixes 27-2
  - PTR records. 29-2
  - reconfigure support 27-34
  - server attributes
    - max-client-leases 27-32
    - v6-client-class-lookup-id 27-32
    - synthetic names, generating 29-3
- Digital Subscriber Line (DSL) 26-25, 1-3
- dig tool, troubleshooting DNS update 29-18
- Discriminating Rate Limiter 24-7
- distributions, zone 15-19
- DNS
  - address format 14-2
  - authoritative server, *See* authoritative name servers
  - cache, flushing 18-9
  - caching-only servers, *See* caching-only servers
  - client/server model 14-5
  - configuration guidelines 4-5
  - dashboard
    - general indicators chart 3-19
    - inbound zone transfers chart 3-17
    - network errors chart 3-18
    - outbound zone transfers chart 3-17
    - related servers errors chart 3-18
  - distributed database 15-1
  - domains, *See* domains
  - dynamic DNS update, *See* DNS update
  - exception handling 18-3
  - glue records 15-16, 1-4
    - invalid 15-16
    - removing 15-17
  - lame delegation 15-16
  - log settings 17-11
  - maximum
    - cache TTL property 18-7
    - memory cache size 18-9

- name servers [14-5](#)
- name-to-address resolution [14-5, A-1](#)
- negative cache time [1-6](#)
- options
  - flushing DNS cache [18-9](#)
  - local and external ports [17-9](#)
  - maximum memory cache size [18-9](#)
- ports [17-9](#)
- primary servers, *See* primary name servers
- reverse name servers [14-6](#)
- root name servers, defining [18-8](#)
- secondary servers, *See* secondary, name servers
- servers
  - commands [17-1, 18-1](#)
  - logging [7-6, 17-11, 29-25](#)
  - managing [17-1, 18-1](#)
  - name [17-2, 18-5](#)
  - network interfaces, configuring [17-2, 18-2](#)
  - secondary, *See* secondary, name servers
- simulating top-of-zone A records [29-25](#)
- slave servers, creating [18-2](#)
- troubleshooting [17-10](#)
- dns\_startup\_log file [7-6](#)
- dns\_upgrade\_status\_log file [7-6](#)
- DNS64
  - Managing [18-4](#)
- dns-admin role [5-4](#)
  - core functionality [5-4](#)
  - ipv6-management subrole [5-4](#)
  - security-management subrole [5-4](#)
  - server-management subrole [5-4](#)
- dns command (CLI)
  - addForwarder [18-3](#)
  - disable
    - subnet-sorting [17-4](#)
  - enable
    - ixfr-enable [17-5](#)
    - notify [17-6](#)
    - round-robin [17-4](#)
    - simulate-zone-top-dynupdate [29-25](#)
    - subnet-sorting [17-4](#)
  - findRR [16-6](#)
  - forceXfer [7-2](#)
  - get
    - round-robin [17-4](#)
  - getRRCount [16-5](#)
  - getStats [7-12](#)
    - ha [19-9](#)
  - getZoneCount [15-14](#)
  - listExceptions [18-4](#)
  - listForwarders [18-3](#)
  - removeForwarder [18-3](#)
  - resetStats [7-12](#)
  - scavenge [7-2, 29-17](#)
  - set
    - activity-summary-interval [17-11](#)
    - checkpoint-interval [17-5](#)
    - log-settings [7-6, 17-11](#)
    - mem-cache-size [17-10](#)
    - notify-min-interval [17-9](#)
    - notify-send-stagger [17-9](#)
    - notify-wait [17-9](#)
  - setPartnerDown [19-4](#)
  - show [17-3, 18-6](#)
- dns-management subrole (cfg-admin) [5-4](#)
- DNSSEC
  - Managing [18-5](#)
- dns-servers, DHCPv6 option [B-12](#)
- DNS update
  - backup-server-key [29-12](#)
  - benefits [20-6](#)
  - change set database [17-5](#)
  - checkpoint, *See* checkpointing, zone
  - configurations
    - DHCPv6 synthetic name generator [26-18, 29-3](#)
    - failover synchronization effect [28-9](#)
    - policies, setting for [22-4](#)
    - synthetic name stem [26-18, 29-3](#)

- confirming records [29-16](#)
  - creating [29-6](#)
  - DCHPv6 [29-2](#)
  - definition [29-1](#)
  - DHCPv6
    - AAAA records [29-2](#)
    - DHCPID records [29-2](#)
    - PTR records [29-2](#)
    - synthetic names [29-3](#)
  - dynamic-dns [29-6](#)
  - enabling [15-18, 29-5](#)
  - failover synchronization effect [28-8](#)
  - forcing [29-27](#)
  - large deployments [29-2](#)
  - logging [29-18](#)
  - maps
    - creating [29-7](#)
    - dhcp-named-policy [29-8](#)
    - dhcp-policy-selector [29-8](#)
  - operation [20-7](#)
  - policies
    - configuring [29-12](#)
    - creating [29-12](#)
    - deleting [29-15](#)
    - editing [29-14](#)
    - interaction with previous releases [29-12](#)
    - rules [29-13](#)
    - zones, applying to [29-15](#)
  - policies, *See* DNS update, policies
  - prerequisites [29-21](#)
  - server-key [29-12](#)
  - simulating top-of-zone A records [29-25](#)
  - troubleshooting [29-18](#)
  - TSIG security [29-9](#)
  - Windows 2000 clients [29-18](#)
- dns-update-map command (CLI)
- create [29-7](#)
  - set
    - dhcp-named-policy [29-8](#)
    - dhcp-policy-selector [29-8](#)
- DOCSIS [4-1, 1-2](#)
- TFTP and [1-2](#)
- documentation
- conventions [xxxii](#)
- domain-list, DHCPv6 option [B-12](#)
- domain-name, DHCP option [B-2](#)
- domain names
- dot-separated [14-3](#)
  - space [14-2](#)
  - tree structure [14-2](#)
- domain-name-servers, DHCP option [B-2](#)
- domains
- difference from zones [14-3](#)
  - names, *See* domain names
  - registering [14-3](#)
- domain-search, DHCP option [B-19](#)
- do-times, DHCP expression [26-10](#)
- DRL [24-7](#)
- dual zone updates [29-20](#)
- dynamic
- addresses [9-1](#)
  - BOOTP, *See* BOOTP, dynamic
  - DNS, *See* DNS update
- 
- ## E
- edit mode
- staged [1-9](#)
  - synchronous [1-10](#)
- .edu domain [14-2](#)
- elapsed-time, DHCPv6 option [B-12](#)
- end, DHCP option [B-2](#)
- enterprise users [4-1](#)
- environment-destroyer extension point, DHCP [24-12, 30-39](#)
- environmentdictionary, DHCP expression [26-10](#)
- environment dictionary, extension point [30-24](#)
- data items [30-25](#)

- initial-environment-dictionary property [30-26](#)
- equal, DHCP expression [26-11](#)
- equali, DHCP expression [26-11](#)
- error, DHCP expression [26-11](#)
- event logging [7-5](#)
- Event Viewer, Windows [7-5](#)
- exception
  - See* resolution exception
- export command (CLI)
  - addresses, VPN [24-21](#)
  - leases [23-5](#)
    - vpn [24-21](#)
  - option-set [22-17](#)
- expressions [26-1](#)
  - address range for scope templates [21-7](#)
  - creating [26-3](#)
  - debugging [26-26](#)
  - embedded policy for scope templates [21-7](#)
  - link templates [27-15](#)
  - prefix templates [27-23](#)
  - scope templates [21-4](#)
    - scope name [21-7](#)
- extension command (CLI)
  - create [30-2](#)
  - list [30-2](#)
  - set
    - init-entry [30-2](#)
- extension points, DHCP [24-10](#)
  - listing [30-2](#)
- extensions [24-10](#)
  - API [C-26](#)
  - C/C++ [30-4, 30-9](#)
  - check-lease-acceptable [30-37](#)
  - client-classes
    - modifying [30-15](#)
    - processing [30-15](#)
  - configuration errors [30-5](#)
  - creating [30-2](#)
  - deciding approaches [30-3](#)
  - decoded packet data items [C-1](#)
  - definition [30-1](#)
  - determining tasks [30-3](#)
  - DEX [30-9](#)
    - environment methods [C-38](#)
  - dex.h file [30-10](#)
  - DEX attributes
    - dictionary [C-30](#)
    - methods [C-30](#)
  - dhcp-parameter-request-list option [30-28](#)
  - DHCPv6, enabling [30-14](#)
  - dictionaries [30-5, 30-23](#)
    - entries [C-1](#)
  - DNS requests, processing [30-21](#)
  - environment-destroyer [30-39](#)
  - environment dictionary [30-5, 30-24](#)
  - failover synchronization effect [28-9](#)
  - init-entry [30-29](#)
    - C/C++ [30-12](#)
    - Tcl [30-9](#)
  - initial-environment-dictionary property [30-26](#)
  - leases
    - acceptability, determining [30-17](#)
    - finding [30-16](#)
    - requests, serializing [30-17](#)
    - state changes, tracing [30-22](#)
  - lease-state-change [30-37](#)
  - networks and links, determining [30-16](#)
  - packet data items, decoded [30-27](#)
  - packets
    - decoding [30-15](#)
    - receiving [30-14](#)
  - post-class-lookup [30-32](#)
  - post-client-lookup [30-34](#)
  - post-packet-decode [30-31](#)
  - post-packet-encode [30-38](#)
  - post-send-packet [30-39](#)
  - pre-client-lookup [30-32](#)
  - pre-packet-decode [30-30](#)

- pre-packet-encode 30-38
  - recognizing 30-6
  - request dictionary 30-5, 30-26, C-10
  - request processing 30-12
  - response containers, building 30-16
  - response dictionary 30-5, 30-26, C-16
  - response packets
    - encoding 30-21
    - gathering data 30-20
    - sending 30-21
  - routine signature 30-4
  - stable storage, updating 30-21
  - Tcl 30-4, 30-7
    - environment methods C-29
  - Tcl attributes
    - dictionary C-26
    - methods C-26
  - thread-safe 30-10
  - extensions-path, DHCP option B-3
  - external authentication servers 5-13
    - adding 5-14
    - configuring 5-13
    - deleting 5-14
    - pulling 5-23
    - pushing 5-23
  - external port 17-9
- 
- F**
- failover, DHCP
    - address ranges, ensuring 28-4
    - attributes
      - advanced 28-13
      - affected 28-9
      - related failover 6-4
      - related servers 6-4, 6-7, 6-8
    - back office scenarios 28-2
    - backup
      - allocation boundary 21-15
      - percentage 20-11
      - server, removing 28-22
    - backup percentage 28-14
    - benefits 20-8
    - BOOTP
      - clients 28-29
      - relay 28-4
    - changing roles 28-21
    - checklist 28-4
    - configuring 28-1
    - confirming 28-10
    - creating server pairs 5-42
    - dynamic BOOTP backup percentage 28-15
    - lazy updates 28-16
    - LDAP 28-4
    - lease period factor 28-16
    - lease query 28-30
    - load balancing 28-20
      - compatibility with earlier release 28-20
      - configuring 28-21
    - local server synchronization 28-5
    - logging 28-9, 28-31
    - main server, adding new 28-23
    - maximum client lead time 28-16
    - monitoring 28-31
    - multiple interfaces 28-23
    - network discovery 28-20
    - network failures 28-31
    - operation 20-8
      - halting 28-22
    - pairs
      - address matches 28-6
      - backup percentage 28-14
      - creating 28-6
      - synchronizing 28-10
    - partner down state 28-17
    - polling
      - attributes 28-19
      - priority 6-13

- polling attributes, setting [6-12](#)
- regional cluster synchronization [28-7, 28-10](#)
- regional pairs [6-19](#)
- related servers, getting [6-9](#)
- removing backup server [28-22](#)
- replacing servers with defective storage [28-22](#)
- request/response buffer settings [28-19](#)
- restrictions, communications interrupted [20-10](#)
- safe period [28-17](#)
- scenarios [28-1](#)
- server pairs, creating [28-5](#)
- simple scenarios [28-2](#)
- states [20-9](#)
- state transitions [28-11](#)
- symmetrical scenarios [28-3](#)
- synchronize function [28-7](#)
- synchronizing [28-8](#)
- synchronizing pairs [5-42](#)
- troubleshooting [28-30](#)
- types [20-8, 28-1](#)

failover-pair command (CLI)

- addMatch [28-6](#)
- create [28-6](#)
- enable
  - load-balancing [28-14](#)
  - use-safe-period [28-18](#)
- listMatches [28-6](#)
- polling attributes, setting [6-12](#)
- removeMatch [28-6](#)
- set
  - backup-pct [28-14](#)
  - dynamic-bootp-backup-pct [28-30](#)
  - load-balancing [28-21](#)
  - safe-period [28-18](#)
- sync [28-10](#)

file\_tftp\_1\_log file [7-6, 7-28](#)

file\_tftp\_1\_trace file [7-6](#)

filter, lease [23-9](#)

finger-servers, DHCP option [B-8](#)

- font-servers, DHCP option [B-7](#)
- forwarding DNS servers [18-2](#)
  - listing [18-3](#)
- forwarding servers
  - DHCP [24-24](#)
- FQDN [14-2, 16-2, 1-4](#)
  - DHCP processing [20-12](#)
  - option, DHCP [29-19](#)
- free-address-low-threshold event, SNMP [1-6](#)

---

## G

- gateway address [20-14, 24-18, 1-4](#)
- generate-lease extension point, DHCP [24-11](#)
- geo-conf, DHCP option [B-19](#)
- geoconf-civic, DHCP option [B-19](#)
- geoconf-civic, DHCPv6 option [B-13](#)
- giaddr, DHCP field [20-14, 24-18, 1-4](#)
- glue records [15-16, 1-4](#)
  - invalid [15-16](#)
  - removing [15-17](#)
- .gov domain [14-2](#)
- grace period, leases [22-4](#)
- Granular Administration [5-15](#)
- grep tool (UNIX) [7-29](#)
- groups [5-1, 5-5](#)
  - adding [5-7](#)
  - interaction with roles [5-2](#)
  - pulling [5-25](#)
  - pushing [5-24](#)

---

## H

HA DNS

- backup server, setting [19-3](#)
- configuring [19-1](#)
- enabling [19-3](#)
- main server, setting [19-3](#)

- partner down, setting [19-4](#)
- server pairs, creating [19-4](#)
- synchronizing server pairs [19-4](#)
- ha-dns-pair command (CLI)
  - create [19-4](#)
  - set
    - ha-dns-backup-server [19-3](#)
    - ha-dns-main-server [19-3](#)
  - sync [19-4](#)
- Handling Malicious DNS Clients and Unresponsive Nameservers [17-9](#)
- Help
  - attributes [2-6](#)
  - pages [2-6](#)
- HINFO records [A-3, 1-4](#)
- host-admin role [5-4](#)
  - core functionality [5-4](#)
- Host Info records
  - See* HINFO records
- hostmaster, setting for zone [15-6](#)
- host-name, DHCP option [B-2](#)
- host-regex syntax [5-33](#)
- hosts
  - adding to zones [10-1, 16-9](#)
  - BOOTP [24-1](#)
  - creating [5-32](#)
  - dynamic [15-18, 29-1](#)
  - editing [10-2](#)
  - multiple interface [28-23](#)
  - pinging [23-7](#)
  - removing [10-3](#)
  - testing address ranges [5-35](#)
  - zone restrictions [5-33](#)
- HTTPS login [2-3](#)
- ia-pd, DHCPv6 option [B-13](#)
- iaprefix, DHCPv6 option [B-13](#)
- ia-ta, DHCPv6 option [B-11](#)
- ICMP
  - echo, *See* PING
  - errors, ignoring [23-7](#)
- ieee802.3-encapsulation, DHCP option [B-5](#)
- IETF [20-1, 21-22, 1-3](#)
- if, DHCP expression [26-11](#)
- ifconfig tool (UNIX) [7-29](#)
- import command (CLI) [15-9](#)
  - keys [29-11](#)
  - leases [23-5, 24-21](#)
  - option-set [22-17](#)
- impress-servers, DHCP option [B-2](#)
- in-addr.arpa domain [14-6, 1-4](#)
- incremental zone transfers [1-5](#)
  - enabling [4-6, 17-5](#)
- info-refresh-time, DHCPv6 option [B-13](#)
- init-entry extension point
  - C/C++ [30-12](#)
  - Tcl [30-9](#)
- init-entry extension point, DHCP [24-11, 30-29](#)
- initial-url, DHCP option [B-19](#)
- INIT-REBOOT packets [20-10](#)
- install\_cnr\_log file [7-6](#)
- interface cards [21-2, 29-26](#)
- interface-id, DHCPv6 option [B-12](#)
- interface-mtu, DHCP option [B-4](#)
- Internet Control Message Protocol
  - See* ICMP
- Internet Engineering Task Force [20-1, 1-3](#)
- Internet Operating System
  - See* IOS
- Internet Service Providers [4-1](#)
- interoperability of releases [4-7](#)
- Intranet Builder [18-3](#)
- IOS, VPN support [24-17](#)
- ip6-string, DHCP expression [26-12](#)

## I

- iaaddr, DHCPv6 option [B-11](#)
- ia-na, DHCPv6 option [B-11](#)



- IP addresses
    - See* addresses, IP
  - ipconfig utility [21-23, 25-10](#)
  - ip-forwarding, DHCP option [B-3](#)
  - ip-helper [28-30](#)
    - adding to router [5-38](#)
  - IP helper address [24-4](#)
  - IP history
    - See* lease history
  - iphist utility [23-25](#)
  - ip-string, DHCP expression [26-12](#)
  - IPv6 addresses [27-1](#)
  - ipv6-management subrole (addrblock-admin) [5-3](#)
  - ipv6-management subrole (dhcp-admin) [5-4](#)
  - ipv6-management subrole (dns-admin) [5-4](#)
  - irc-servers, DHCP option [B-8](#)
  - ISDN records [A-3](#)
  - iSNS, DHCP option [B-10](#)
  - ISPs
    - See* Internet Service Providers
  - is-string, DHCP expression [26-12](#)
- 
- J**
- jsui\_log.date.txt file [7-7](#)
- 
- K**
- key command (CLI)
    - create [29-10](#)
  - keys, generating secrets [29-10](#)
- 
- L**
- lame delegation [15-16, 1-5](#)
  - LAN segments [20-12, 1-9](#)
  - large enterprise deployments [4-4](#)
  - lazy updates, failover [28-16](#)
  - LDAP [16-8](#)
    - client
      - configuration [25-18](#)
      - data use, enabling [25-20](#)
    - configuring [25-18](#)
    - connections [25-29](#)
    - DHCP
      - client queries [25-19](#)
      - mapping [25-19](#)
    - directory support [25-19](#)
    - distinguished name (dn) [25-19](#)
    - embedded policies [25-21](#)
    - entry creation [25-27](#)
      - enabling [25-28](#)
    - event service, failover synchronization effect [28-8](#)
    - failover configuration [28-4](#)
    - filtering searches [25-26](#)
    - lease-state attributes [25-22](#)
    - passwords [25-19](#)
    - protocol definition [25-18](#)
    - queries, enabling [25-19](#)
    - query-timeout [25-29](#)
    - schema checking, disabling [25-18](#)
    - state updates [25-25](#)
    - storing lease data [25-24](#)
    - threadwaittime [25-29](#)
    - timeout [25-29](#)
    - troubleshooting [25-28](#)
    - typical attribute settings [25-29](#)
    - unprovisioning client entries [25-21](#)
    - updates, enabling [25-26](#)
  - ldap command (CLI)
    - create [25-19](#)
    - delete [25-19](#)
    - enable
      - can-query [25-7, 25-20](#)
      - can-update [25-26](#)
    - getEntry [25-20](#)
    - list [25-21](#)

- listnames [25-21](#)
- set
  - create-object-classes [25-27](#)
  - dn-attribute [25-27](#)
  - dn-create-format [25-27](#)
  - dn-format [25-27](#)
  - password [25-19](#)
  - preference [25-20](#)
  - search-filter [25-20](#)
  - search-path [25-19](#)
  - search-scope [25-19](#)
  - update-search-attribute [25-26](#)
  - update-search-filter [25-26](#)
  - update-search-path [25-26](#)
  - update-search-scope [25-26](#)
  - username [25-26](#)
- setEntry [25-20](#)
  - create-dictionary givenname [25-27](#)
  - create-dictionary localityname [25-27](#)
  - create-dictionary sn [25-27](#)
  - update-dictionary carlicense [25-26](#)
  - update-dictionary uid [25-26](#)
- show [25-21](#)
- unsetEntry [25-20](#)
- ldap-url, DHCP option [B-18](#)
- lease6 command (CLI)
  - activate [27-29](#)
  - deactivate [27-29](#)
  - force-available [27-29](#)
  - list [23-11](#)
- lease command (CLI)
  - activate [23-8](#)
  - deactivate [23-8](#)
  - force-available [23-20, 24-3](#)
  - list
    - macaddr [23-11](#)
  - set
    - address [25-23](#)
    - client-dns-name [25-23](#)
    - client-domain-name [25-23](#)
    - client-flags [25-23](#)
    - client-host-name [25-23](#)
    - client-id [25-23](#)
    - client-mac-addr [25-23](#)
    - expiration [25-23](#)
    - flags [25-23](#)
    - lease-renewal-time [25-23](#)
    - start-time-of-state [25-23](#)
    - state [25-23](#)
    - vendor-class-identifier [25-23](#)
  - show [23-2](#)
- lease extensions, deferring [24-8](#)
- lease history [23-22](#)
  - automatic trimming
    - age [23-28](#)
    - interval [23-28](#)
  - collecting [23-24](#)
  - collection maximum age [6-14](#)
  - database directory [23-23](#)
  - enabling [6-14, 23-23](#)
  - failover server priority [6-13](#)
  - iphist utility [23-25](#)
  - maximum age for trimming [23-28](#)
  - polling
    - data [6-11](#)
    - interval [6-12](#)
    - offset [6-13](#)
    - retry interval [6-13](#)
  - querying [23-24](#)
  - recording [9-12, 23-23](#)
  - reports [23-22](#)
  - trimming [23-27](#)
- lease-history subrole (regional-addr-admin) [5-5](#)
- Lease Notification, Dynamic [23-37](#)
- lease-notification command (CLI) [23-29](#)
  - available [23-22](#)
  - mail-host [23-29](#)
  - recipients [23-29](#)

- scopes [23-29](#)
- specifying config file [23-30](#)
- lease period factor, failover [28-16](#)
- leasequery [23-30](#)
  - DHCPv4 pre-RFC implementation [23-31](#)
  - DHCPv4 RFC 4388 implementation [23-32](#)
  - DHCPv6 implementation [23-33](#)
  - implementations [23-31](#)
  - logging [24-16](#)
  - reservations and [23-31](#)
  - statistics [23-34](#)
- leases [20-3](#)
  - activity [7-22](#)
  - address usage reports [23-22](#)
  - affinity [27-8](#)
  - benefits [20-3](#)
  - database [7-6](#)
  - deactivating [24-3](#)
    - in scopes [23-7](#)
  - deferring extensions [24-6](#)
  - defined [20-2](#)
  - DHCPv6 [27-7](#)
  - DHCPv6 life cycle [27-8](#)
  - displaying [7-22, 23-28](#)
  - excluding addresses from ranges [23-8](#)
  - expired state [20-2](#)
  - exporting [23-5](#)
  - file [23-5](#)
    - time format [23-6](#)
  - forcing available [23-19](#)
  - grace period [22-4](#)
  - history reports [23-22](#)
  - importing [23-5](#)
  - inhibiting renewals [23-20](#)
  - LDAP attributes [25-25](#)
  - notification, receiving [23-29](#)
  - obtaining [20-7](#)
  - one-shot [25-11](#)
  - orphaned
    - by VPN [24-23](#)
  - permanent [22-3, 23-3](#)
  - pinging before allocating [23-7](#)
  - provisional [25-11](#)
  - querying, *See* leasequery
  - reacquiring [20-8](#)
  - reactivating [23-8](#)
  - recommended renewal times [4-7](#)
  - releasing [20-7](#)
  - renewal time, saving as state [25-23](#)
  - renewing [20-2](#)
  - reusing [24-3](#)
  - scopes [20-2, 23-1](#)
    - listing [23-2](#)
    - viewing [23-2](#)
  - searching, filtering [23-9](#)
  - states [23-2, 25-23](#)
  - state updates in LDAP [25-24](#)
  - timeouts for unavailable [23-21](#)
  - times
    - guidelines [23-3](#)
    - in import files [23-6](#)
    - overrides, allowing [23-4](#)
  - types [20-3](#)
  - unavailable
    - clearing [23-20](#)
    - handling [23-21](#)
  - utilization [23-28](#)
- lease-state-change extension point, DHCP [24-12, 30-37](#)
- length, DHCP expression [26-12](#)
- let, DHCP expression [26-12](#)
- license [5-19](#)
- license command (CLI)
  - create [5-19](#)
  - list [5-19](#)
  - listnames [5-19](#)
  - show [5-19](#)
- licenses [5-19](#)
  - adding [2-2, 2-3](#)

## link command (CLI)

- applyTemplate [27-19](#)
- create [27-19](#)
  - template, with [27-19](#)
  - template-root-prefix, with [27-19](#)
- listPrefixes [27-19](#)
- listPrefixNames [27-19](#)

## links

- configuring [27-13](#)
- DHCPv6 [27-2](#)

## link-template command (CLI)

- apply-to (link) [27-15](#)
- create [27-14](#)
  - clone [27-15](#)

## link templates

- expressions [27-15](#)

## Linux

- CLI location [2-10](#)

## list

- link template expression [27-16](#)
- prefix template expression [27-24](#)

local clusters [1-1, 4-2](#)

- administration [5-1](#)
- connecting to [6-9](#)
- editing [6-3](#)
- replicating data [6-9](#)
- synchronizing with [6-9](#)
- tutorial [5-28](#)
- view of tree [6-2](#)

localhost [15-4, 17-10](#)local port [17-9](#)lock files [8-3](#)log, DHCP expression [26-13](#)log.xxx files, CNRDB [8-5](#)

## logging

- NOTIFY, *See* NOTIFY

logging out [2-6](#)login, Web UI [2-2](#)log-servers, DHCP option [B-2](#)

## loopback

- addresses [1-5](#)
- zones [15-4, 1-5](#)

lpr-servers, DHCP option [B-2](#)lq-client-links, DHCPv6 option [B-14](#)lq-query, DHCPv6 option [B-13](#)lq-relay-data, DHCPv6 option [B-14](#)lshift, DHCP expression [26-8](#)

---

**M**MAC addresses, clients [20-13](#)management components [1-1](#)mask-blob, DHCP expression [26-13](#)mask-int, DHCP expression [26-13](#)mask-supplier, DHCP option [B-4](#)max-dgram-reassembly, DHCP option [B-3](#)maximum client lead time, failover [20-10, 28-16](#)MB records [A-3](#)

## MCLT

- See* maximum client lead time

mcns-security-server, DHCP option [B-19](#)merit-dump, DHCP option [B-2](#)MG records [A-4](#)Microsoft DHCP stack [21-2](#).mil domain [14-2](#)MINFO records [A-4](#)Miscellaneous Options and Settings [17-9, 18-12](#)mobile-ip-home-agents, DHCP option [B-17](#)MR records [A-4](#)MSOs [4-1](#)multinetting [20-12, 1-6](#)multiple interfaces, failover [28-23](#)

## Multiple Service Operators

- See* MSOs

multiple users [2-4](#)multithreaded server [1-2](#)MX records [A-4, 1-6](#)

---

**N**

- name\_dhcp\_1\_log file [7-6](#)
  - name\_dns\_1\_log file [7-6](#)
  - Name Server records
    - See* NS records
  - name servers
    - authoritative, *See* authoritative name servers
    - domain [14-5](#)
    - primary, *See* primary name servers
    - reverse [14-6](#)
    - secondary, *See* secondary, name servers
    - types [14-5](#)
  - name-servers, DHCP option [B-2](#)
  - name-service-search, DHCP option [B-19](#)
  - name-to-address resolution [14-5, A-1](#)
  - Naming Authority Pointer records
    - See* NAPTR records
  - NAPTR records [16-8, A-5](#)
  - navigation bar labels [xxxiii](#)
  - nds-context, DHCP option [B-18](#)
  - nds-servers, DHCP option [B-18](#)
  - nds-tree, DHCP option [B-18](#)
  - negative cache time [1-6](#)
  - netbios-dd-servers, DHCP option [B-6](#)
  - netbios-name-servers, DHCP option [B-6](#)
  - netbios-node-type, DHCP option [B-7](#)
  - netbios-scope, DHCP option [B-7](#)
  - netinfo-parent-server-addr, DHCP option [B-19](#)
  - netinfo-parent-server-tag, DHCP option [B-19](#)
  - netwareip-domain, DHCP option [B-17](#)
  - netwareip-information, DHCP option [B-17](#)
  - Network Information Service
    - See* nis entries
  - network interfaces
    - DNS server [17-2, 18-2](#)
  - Network News Transport Protocol [B-7](#)
  - network number [14-3](#)
  - networks
    - editing names [21-24](#)
    - listing [21-24](#)
    - managing [21-23](#)
  - Network Time Protocol [B-6](#)
  - network time service, use of [6-12](#)
  - nis+-domain, DHCP option [B-7](#)
  - nis+-servers, DHCP option [B-7](#)
  - nis-domain, DHCP option [B-5](#)
  - nis-domain-name, DHCPv6 option [B-13](#)
  - nisp-domain-name, DHCPv6 option [B-13](#)
  - nisp-servers, DHCPv6 option [B-13](#)
  - nis-servers, DHCP option [B-5](#)
  - nis-servers, DHCPv6 option [B-13](#)
  - nntp-servers, DHCP option [B-7](#)
  - non-local-source-routing, DHCP option [B-3](#)
  - nonsecure login [2-2](#)
  - NORMAL state, failover [20-9](#)
  - not, DHCP expression [26-13](#)
  - notification, lease [23-29](#)
  - NOTIFY [1-6](#)
    - enabling [17-6](#)
    - logging transactions [17-11](#)
  - NSAP records [A-6](#)
  - nslookup utility [17-12](#)
    - troubleshooting DNS update [29-18](#)
  - NS records [A-5](#)
  - nntp-servers, DHCP option [B-7](#)
  - null, DHCP expression [26-13](#)
- 

**O**

- on-demand address pools
  - See* subnet allocation, DHCP
- option command (CLI)
  - get [22-9](#)
  - listtypes [22-16](#)
  - show [22-9](#)
  - unset [22-9](#)
- options

- custom DHCP 22-10
- data types, listing 22-16
- DHCPv6 27-12
  - setting 27-34
- failover synchronization effect 28-9
- policy hierarchy 22-3
- option-set command (CLI)
  - show 22-9
- OptionSetJumpStart.txt file 22-17
- OptionSetPXE.txt file 22-17
- option sets
  - exporting 22-17
  - importing 22-17
  - local
    - pulling 22-18
    - pushing 22-18
- or, DHCP expression 26-13
- organization, registering 13-4
- Organizationally Unique Identifier
  - See* OUI
- oro, DHCPv6 option B-11
- OUI, for VPNs 24-19, 1-7
- owner command (CLI)
  - create 12-1
- owner-region subrole (ccm-admin) 5-4
- owner-region subrole (regional-admin) 5-5
- owners
  - configuring 12-1
  - managing 12-1
  - pulling 12-3
  - pushing 12-3
- changing 5-7
- changing 2-4
- nondisplaying 5-6
- path-mtu-aging-timeout, DHCP option B-3
- path-mtu-plateau-tables, DHCP option B-3
- PAUSED state, failover 20-11
- PDU, SNMP 1-7
- performance guidelines 4-5
- perform-mask-discovery, DHCP option B-4
- pick-first-value, DHCP expression 26-13
- pinging hosts before offering 23-7
- ping utility 23-7
- Pointer (Reverse Mapping) record
  - See* PTR record
- point of contact, registering 13-3
- policies
  - cloning 22-5
  - compared with scopes 20-3
  - configuring 22-1
  - creating regional 6-15
  - defined 20-3, 22-1, 1-7
  - DHCPv6 27-32
  - dual zone updates, allowing 29-20
  - embedded 22-2
    - editing 22-7
    - scopes 21-18
    - vendor options 21-19
  - failover synchronization effect 28-9
  - guidelines 21-2
  - hierarchy 22-3
  - lease time overrides, allowing 23-4
  - local
    - pulling 6-16
    - pushing 6-16
  - named 22-2
  - options 20-13
    - adding 22-5
  - scopes 20-13
  - scopes, *See* scopes

---

**P**

- pad, DHCP option B-2
- PARTNER-DOWN state, failover 20-10
  - enabling 28-17
- passwords 5-6
  - administrator 5-6

- suboptions
  - adding 22-7
  - system-default 22-1
- policies, DHCP
  - address block 24-22
  - pushing to local clusters 5-40
- policy command (CLI)
  - create 22-5, 24-3
    - clone 22-5
  - disable
    - allow-client-a-record-update 29-19
  - enable
    - allow-client-a-record-update 29-19, 29-20
    - allow-dual-zone-dns-update 29-20
    - allow-lease-time-override 23-4
    - permanent-leases 22-5
    - use-client-id-for-reservations 23-19
  - getOption 22-6
    - dhcp-lease-time 22-5
  - listOptions 22-5
  - set 22-5, 24-3
    - grace-period 25-11
    - limitation-count 26-2
  - setLeaseTime 22-5
  - setOption 22-6, 24-3
    - subnet-mask 22-5
  - unsetOption 22-6
- policy-filters, DHCP option B-3
- polling 1-7
  - failover server priority 6-13
  - interval 6-12
  - lease history data 6-11
  - offset 6-13
  - retry interval 6-13
  - subnet utilization data 6-11
  - time skew effects 6-12
- pop3-servers, DHCP option B-7
- post-class-lookup extension point, DHCP 24-11, 30-32
- post-client-lookup extension point, DHCP 24-11, 30-34
- Post Office Protocol B-7
- post-packet-decode extension point, DHCP 24-11, 30-31
- post-packet-encode extension point, DHCP 24-12, 30-38
- post-send-packet extension point, DHCP 24-12, 30-39
- POTENTIAL-CONFLICT state, failover 20-10
- pre-client-lookup extension point, DHCP 24-11, 30-32
- pre-dns-add-forward extension point, DHCP 24-12
- preference, DHCPv6 option B-12
- preferences, user 2-9
- prefix allocation groups 27-6
- prefix command (CLI)
  - addReservation 27-29
  - applyTemplate 27-29
  - create 27-29
    - template, with 27-29
  - createReverseZone 29-4
  - deleteReverseZone 29-4
  - listLeases 27-29
  - set
    - selection-tags 25-4
- prefixes
  - configuring 27-20
  - count on server, getting 27-29
  - DHCPv6 27-2
    - reverse zones, creating 29-4
  - interface-identifier, assigning 27-4
- prefix stability 27-5
  - CMTS 27-5
  - universal 27-6
- prefix-template command (CLI)
  - apply-to (prefix) 27-22
  - create 27-22
    - clone 27-22
  - set
    - selection-tags 25-4
- prefix templates
  - expressions 27-23
- pre-packet-decode extension point, DHCP 24-11, 30-30
- pre-packet-encode extension point, DHCP 24-12, 30-38

- primary name servers [14-4](#)
    - configuring [15-4](#)
    - defined [14-5](#)
    - SOA property [A-7](#)
    - zone, setting for [15-6](#)
  - progn, DHCP expression [26-14](#)
  - Protocol Data Unit, SNMP
    - See* PDU
  - PTR records [A-6, 1-7](#)
    - DNS update [29-2](#)
  - Pushing Administrators Automatically to Local Clusters [5-21](#)
  - pxe-client-arch, DHCP option [B-18](#)
  - pxe-client-machine-id, DHCP option [B-18](#)
  - pxe-client-network-id, DHCP option [B-18](#)
  - PXE clients [22-17](#)
  - PXE clients, importing option sets for [22-17](#)
- 
- R**
- rapid-commit, DHCPv6 option [B-12](#)
  - reconfigure-accept, DHCPv6 option [B-12](#)
  - reconfigure-message, DHCPv6 option [B-12](#)
  - reconfigure support, DHCPv6 [27-34](#)
  - RECOVER-DONE state, failover [20-10](#)
  - RECOVER state, failover [20-10](#)
  - recursive queries [1-8](#)
  - regional-addr-admin role [5-5](#)
    - core functionality [5-5](#)
    - dhcp-management subrole [5-5](#)
    - lease-history subrole [5-5](#)
    - subnet-utilization subrole [5-5](#)
  - regional-admin role [5-5](#)
    - authentication subrole [5-5](#)
    - authorization subrole [5-5](#)
    - core functionality [5-5](#)
    - database subrole [5-5](#)
    - owner-region subrole [5-5](#)
  - regional clusters [1-1, 4-2](#)
    - adding
      - local clusters [5-37, 6-2](#)
      - server clusters [6-2](#)
    - administration [5-1](#)
    - client-classes
      - pulling [6-18](#)
      - pushing [6-17](#)
    - failover pairs [6-19](#)
    - policies [6-15](#)
      - pulling [6-16](#)
      - pushing [6-16](#)
    - pushing
      - option definition sets [22-18](#)
    - reservations
      - pushing [6-20](#)
    - scope templates [6-14](#)
      - pushing [6-14](#)
    - subnets to local clusters
      - pushing [9-7](#)
    - subnets to routers
      - pushing [9-7](#)
    - tutorial [5-35](#)
    - VPNs [6-18](#)
  - region command (CLI)
    - create [12-2](#)
  - regions
    - configuring [12-1](#)
    - managing [12-2](#)
    - pulling [12-3](#)
    - pushing [12-3](#)
  - regular expressions (regex) [5-33](#)
  - related servers
    - DHCP attributes [6-4](#)
    - states [6-4](#)
  - relative domain names [16-2](#)
  - relay-agent-info, DHCP option [B-18](#)
  - relay-agent-subscriber-id, DHCPv6 option [B-13](#)
  - relay-message, DHCPv6 option [B-12](#)
  - remote-dns command (CLI)



- create 17-10
- remote-id, DHCPv6 option B-13
- replica data 6-9
- replica data, viewing 6-10
- report command (CLI) 7-20, 23-22
- reports
  - address usage 7-19, 23-22
  - allocation 13-1
  - ARIN 13-1
  - IPv4 utilization 13-5
  - lease history 23-22
  - managing 13-1
  - organization
    - creating 13-4
    - editing 13-5
  - point of contact 13-2
    - editing 13-3
  - subnet utilization 9-12
  - WHOIS/SWIP 13-6
- requestdictionary, DHCP expression 26-17
- request dictionary, extension points 30-26
- request dump, DHCP expression 26-16
- request option, DHCP expression 26-14
- request packetfield, DHCP expression 26-16
- reservation command (CLI)
  - delete 23-17
- reservations, lease
  - creating 23-14
  - LEASEQUERY and 23-31
  - pushing to local clusters 6-20
  - removing 23-17
  - using client ID 23-19
- resolution exception 18-3
- resource-location-servers, DHCP option B-2
- resource records
  - A A-1, 1-1
  - A6 A-2
  - AAAA 29-2, A-2
  - adding 16-2
    - adding in CLI 16-2
  - AFSDB A-2
  - CNAME A-3, 1-2
  - configuring 16-1
  - count on server, getting 16-5
  - DHCID 29-2, A-3
  - editing 16-1
    - subzone information 15-18
  - filtering 16-7
  - HINFO A-3, 1-4
  - ISDN A-3
  - listing 16-5
  - MB A-3
  - MG A-4
  - MINFO A-4
  - MR A-4
  - MX A-4, 1-6
  - NAPTR A-5
  - NS A-5
  - NSAP A-6
  - protecting 16-3
  - PTR A-6, 1-7
  - removing 16-4
  - RP A-6
  - RT A-6
  - SOA A-7, 1-9
  - SRV A-7
  - TXT A-7
  - types A-1
  - WKS A-8, 1-11
- responsedictionary, DHCP expression 26-17
- response dictionary, extension points 30-26
- response dump, DHCP expression 26-17
- response option, DHCP expression 26-17
- response packetfield, DHCP expression 26-17
- restricting lease dates 23-4
- return-last, DHCP expression 26-14
- reverse
  - domains 14-6

- mapping records [A-6](#)
- name servers [14-6](#)
- zones [14-6, 1-8](#)
  - configuring [15-11](#)
  - prefixes, creating from [29-4](#)
- RFCs
  - 1001, 1002 [B-6](#)
  - 1035 [15-9](#)
  - 1042 [B-5](#)
  - 1123 [1-2](#)
  - 1179 [B-2](#)
  - 1191 [B-3](#)
  - 1256 [B-4](#)
  - 1350 [1-2](#)
  - 1497 [B-1](#)
  - 1782 [1-2](#)
  - 1783 [1-2](#)
  - 1995 [4-6, 17-5](#)
  - 1996 [4-6, 17-6](#)
  - 2131 [20-8, 24-2](#)
  - 2132 [B-1](#)
  - 2136 [15-18](#)
  - 2316 [1-3](#)
  - 2685 [24-19](#)
  - 2782 [16-7, 29-22, A-7](#)
  - 2915 [A-5](#)
  - 2916 [16-8](#)
  - 3041 [27-7](#)
  - 3046 [25-13, 26-1](#)
  - 3074 [28-20](#)
  - 3263 [16-8](#)
  - 3315 [27-1, B-11, B-14](#)
  - 3319 [B-12](#)
  - 3403 [16-8](#)
  - 3633 [27-1, 27-7](#)
  - 3736 [27-1](#)
  - 3898 [B-13](#)
  - 4075 [B-13](#)
  - 4174 [B-10](#)
  - 4242 [B-13](#)
  - 4280 [B-10, B-13](#)
  - 4291 [27-4](#)
  - 4388 [23-32, B-10](#)
  - 4580 [B-13](#)
  - 4649 [B-13](#)
  - 4701 [29-2, A-3](#)
  - 4702 [29-2](#)
  - 4704 [29-2](#)
  - 4833 [B-15, C-5, C-7, C-9](#)
  - 5192 [C-5](#)
  - 865 [B-2](#)
  - 868 [B-2](#)
  - 887 [B-2](#)
  - 893 [B-4](#)
  - 894 [B-5](#)
  - 950 [B-2](#)
- ric\_server\_log file [7-6](#)
- ric-management subrole (addrblock-admin) [5-3](#)
- ric-management subrole (central-cfg-admin) [5-5](#)
- ric-management subrole (cfg-admin) [5-4](#)
- RIC server
  - See* Router Interface Configuration server
- role command (CLI)
  - create [5-8](#)
- roles [5-1](#)
  - adding [5-7](#)
  - address block administrator [9-1](#)
  - base [5-1](#)
  - constrained [5-3, 1-8](#)
    - creating [5-33](#)
  - groups [5-5](#)
  - interaction with groups [5-2](#)
  - pulling [5-26](#)
  - pushing [5-26](#)
  - subroles [5-3](#)
- root name servers [14-3, 1-8](#)
  - adding [18-8](#)
  - slave servers [1-9](#)

- root-path, DHCP option [B-3](#)
  - round-robin [1-8](#)
    - enabling [17-4](#)
    - scope selection [20-12, 21-11](#)
  - routed bridge encapsulation (RBE) [1-8](#)
  - router command (CLI)
    - create [11-2](#)
    - set [11-4](#)
  - router-discovery, DHCP option [B-4](#)
  - router-interface command (CLI)
    - set [11-5](#)
  - Router Interface Configuration (RIC) server [4-2](#)
    - logging and tracing [7-6](#)
  - router interfaces
    - adding [5-38](#)
    - editing [11-5](#)
    - editing attributes [11-5](#)
    - viewing [11-5](#)
  - routers
    - adding [5-38, 11-2](#)
    - alternative login methods [11-3](#)
    - BOOTP relay [24-4](#)
    - bundling [11-5](#)
    - Cisco [24-4](#)
    - creating [11-2](#)
    - editing [11-4](#)
    - editing attributes [11-4](#)
    - gateway addresses [20-14, 24-18, 1-4](#)
    - ip-helper [5-38](#)
    - listing [11-2](#)
    - managed [11-3](#)
    - policies for [20-3](#)
    - resynchronizing [11-4](#)
    - secure communication mode [11-3](#)
    - subnet [22-5](#)
    - subnets, pushing [9-7](#)
    - uBR7200 [5-38](#)
    - virtual [11-3](#)
  - routers, DHCP option [B-2](#)
  - router-solicitation-address, DHCP option [B-4](#)
  - RP records [A-6](#)
  - RT records [A-6](#)
- 
- ## S
- safe period, failover [20-10, 28-17](#)
  - scope command (CLI)
    - addRange [21-11](#)
    - clearUnavailable [23-20](#)
    - create [21-11](#)
      - template= [21-9](#)
    - delete [21-23](#)
    - disable [21-17](#)
      - dhcp [21-21, 24-3, 28-30](#)
      - ping-clients [23-21](#)
    - enable [21-17](#)
      - bootp [21-20](#)
      - deactivated [21-21](#)
      - dhcp [21-21](#)
      - dynamic-bootp [21-20, 24-3, 28-30](#)
      - ignore-declines [23-21](#)
      - renew-only [21-21](#)
      - update-dns-for-bootp [24-3](#)
    - get [21-17](#)
    - list [21-17](#)
    - listLeases [23-2](#)
    - listnames [21-17](#)
    - listRanges [23-9](#)
    - removeRange [23-9](#)
    - removeReservation [23-17, 24-3](#)
    - report-staged-edits [21-18](#)
    - set [21-17](#)
      - backup-pct [28-14](#)
      - free-address-config [21-22](#)
      - policy [21-11](#)
      - primary-subnet [21-20](#)
      - selection-tag-list [25-4](#)
    - show [21-17](#)

- unset
  - primary-subnet [21-20](#)
- scope-policy command (CLI)
  - disable [21-19](#)
  - enable [21-19](#)
  - listVendorOptions [21-19](#)
  - set [21-19](#)
  - setVendorOptions [21-19](#)
  - show [21-19](#)
  - unset [21-19](#)
  - unsetVendorOptions [21-19](#)
- scopes
  - address
    - allocation [21-11](#)
    - ranges [21-9](#)
  - allocate-first-available [21-12, 21-14](#)
  - allocation-priority [21-12, 21-14](#)
  - attributes
    - bootp [21-20](#)
    - disabling [21-17](#)
    - dynamic bootp [21-20](#)
    - enabling [21-17](#)
    - getting [21-17](#)
    - listing [21-17](#)
    - primary-subnet [21-19](#)
    - setting [21-17](#)
    - showing [21-17](#)
  - BOOTP, enabling [21-20](#)
  - compared to policies [20-3](#)
  - count on server, getting [21-11](#)
  - creating [21-9](#)
  - deactivating [21-21](#)
  - defined [20-3](#)
  - defining [21-2](#)
  - DHCP, disabling [21-20](#)
  - editing [21-17](#)
  - edit modes [21-18](#)
  - failover
    - backup percentage [28-14](#)
    - synchronization effect [28-9](#)
  - failover-backup-allocation-boundary [21-15, 21-16](#)
  - forcing lease availability [23-19](#)
  - free address SNMP traps [21-21](#)
  - inhibiting lease renewals [23-20](#)
  - internal address allocation [21-15](#)
  - leases, *See* leases
  - moving/decommissioning BOOTP clients [21-20](#)
  - multiple [21-11](#)
  - named policies [22-2](#)
  - names [21-9](#)
  - network addresses [21-9](#)
  - pinging clients [23-7](#)
  - policies, *See* policies
  - primary subnets [21-20](#)
  - ranges
    - adding [21-11](#)
    - listing [23-9](#)
    - removing [23-9](#)
  - removing [21-22](#)
    - if not reusing addresses [21-23](#)
    - if reusing addresses [21-23](#)
  - ranges
    - reusing addresses [21-23](#)
  - renew-only [21-21](#)
  - secondary [21-19](#)
  - staged edit mode [1-9](#)
  - staged edits, reporting [21-18](#)
  - synchronous edit mode [1-10](#)
  - traps, SNMP, free address [21-21](#)
  - unreserving leases [23-17](#)
  - VPNs [24-19](#)
- scope-template command (CLI)
  - apply-to scope [21-9](#)
  - create [21-3](#)
    - clone [21-9](#)
  - set [21-8](#)
    - options-exp [21-6](#)
    - ranges-exp [21-6](#)

- scope-name [21-6](#)
  - selection-tag-list [25-4](#)
- scope templates
  - address range expressions [21-7](#)
  - cloning [21-9](#)
  - creating [21-3](#)
  - creating on regional cluster [5-41](#)
  - editing [21-8](#)
    - attributes [21-8](#)
  - embedded policy expressions [5-41, 21-7](#)
  - expressions [21-4](#)
  - managing [21-3](#)
  - name expression [5-41](#)
  - pulling from local clusters [6-15](#)
  - pushing to local clusters [6-14](#)
  - range expressions [5-41](#)
  - regional [6-14](#)
  - scope name expressions [21-7](#)
- SCP
  - See* System Configuration Protocol
- screen displays [xxxiii](#)
- scripts
  - See* extensions
- search, DHCP expression [26-17](#)
- search, lease [23-9](#)
- secondary
  - expiration time [17-8](#)
  - master [1-9](#)
  - name servers, DNS [14-4, 1-9](#)
    - adding [15-14](#)
    - defined [14-5](#)
    - separating DHCP servers from [21-1](#)
  - refresh time [15-15, 17-7](#)
  - retry time [17-8](#)
  - scopes [21-19](#)
  - subnets [21-19, 1-9](#)
  - zones [15-14](#)
    - adding [15-14](#)
- secondary name servers [15-14](#)
- secure
  - cluster connections [6-2](#)
- security-management subrole (central-dns-admin) [5-5](#)
- security-management subrole (dns-admin) [5-4](#)
- selection tags
  - appending dhcp-user-class-id [25-7](#)
  - appending RADIUS class [25-7](#)
  - appending RADIUS pool [25-7](#)
  - mapping RADIUS class [25-7](#)
  - mapping RADIUS pool name [25-7](#)
  - mapping user class identifier [25-7](#)
- server clusters, adding [6-2](#)
- server command (CLI)
  - enable/disable start-on-reboot [7-1](#)
  - getHealth [7-11](#)
  - getStats [7-12](#)
  - reload [7-3](#)
  - serverLogs
    - set logsize [7-7](#)
    - show [7-7](#)
  - set [7-3](#)
  - start [7-3](#)
  - stop [7-3](#)
- server-identifier, DHCPv6 option [B-11](#)
- server-management subrole (ccm-admin) [5-4](#)
- server-management subrole (central-dns-admin) [5-5](#)
- server-management subrole (dns-admin) [5-4](#)
- servers
  - controlling [7-1](#)
  - events, logging [7-4](#)
  - failures, troubleshooting [7-27](#)
  - health, displaying [7-10](#)
  - IP address [1-9](#)
  - related, states [6-4](#)
  - state, displaying [7-9](#)
  - statistics, showing [7-11](#)
- server-unicast, DHCPv6 option [B-12](#)
- session command (CLI)
  - cache refresh [2-4](#)

- get
  - dhcp-edit-mode [21-18](#)
- set
  - current-vpn [21-11, 24-20](#)
  - dhcp-edit-mode [21-18](#)
  - dns-edit-mode [15-2](#)
- Session Initiation Protocol (SIP) proxies [16-8](#)
- setq, DHCP expression [26-17](#)
- setting
  - custom DHCP options [22-10](#)
  - negative cache time [1-6](#)
- shadow backups [8-1](#)
  - manual [8-3](#)
  - third party backup programs and [8-3](#)
  - time, setting [8-3](#)
- SHUTDOWN state, failover [20-11](#)
- siaddr, DHCP field [24-2, 1-9](#)
- Simple Mail Transport Protocol
  - See* SNMP
- simulating top-of-zone A records [29-25](#)
- single sign-on [2-4, 6-2](#)
- sip-servers, DHCP option [B-19](#)
- sip-servers-address, DHCPv6 option [B-12](#)
- slave servers [18-2, 1-9](#)
- slp-directory-agent, DHCP option [B-18](#)
- slp-service-scope, DHCP option [B-18](#)
- SMS
  - failover on UNIX [28-20](#)
  - integrating with DHCP server [24-9](#)
  - network discovery (dhcp command) [24-10](#)
- smtp-servers, DHCP option [B-7](#)
- SNMP
  - free-address-low-threshold [1-6](#)
  - logging and tracing [7-6](#)
  - notification [1-4](#)
  - notification events [1-7](#)
  - PDU [1-7](#)
  - traps [1-6](#)
    - failover mismatch [28-31](#)
    - free address on scopes [21-21](#)
    - PDU's [1-4](#)
    - server not responding [28-31](#)
    - v2c standard [1-4](#)
- snmp command (CLI)
  - disable server-active [1-6](#)
  - enable server-active [1-6](#)
  - set
    - cache-ttl [1-6](#)
    - community [1-6](#)
    - trap-source-addr [1-6](#)
- snmp-interface command (CLI) [1-6](#)
- snmp-management subrole (cfg-admin) [5-4](#)
- sntp-servers, DHCPv6 option [B-13](#)
- SOA records [A-7, 1-9](#)
  - defined [15-6](#)
  - secondary
    - expiration time [17-8](#)
    - refresh time [17-7](#)
    - retry time [17-8](#)
  - TTL property [17-7](#)
  - Windows 2000 [29-23](#)
- Solaris
  - CLI location [2-10](#)
  - guidelines [4-5](#)
  - mouse buttons [xxxiii](#)
- SRV records [A-7](#)
  - enabling viewing [29-24](#)
  - Windows 2000 [29-22](#)
- SSH connections, routers [11-3](#)
- SSL
  - cluster connections [6-2](#)
- SSO login [2-4](#)
- staged
  - dhcp edit mode [21-18](#)
  - dns edit mode [15-1](#)
  - edit mode [1-9](#)
- starts-with, DHCP expression [26-18](#)
- STARTUP state, failover [20-9](#)

- static
  - addresses 21-2
  - BOOTP 28-29
  - routes B-4
- static-routes, DHCP option B-16
- statistics
  - leasequery 23-34
  - server 7-11
- status-code, DHCPv6 option B-12
- streettalk-directory-assistance-servers, DHCP option B-8
- streettalk-servers, DHCP option B-8
- subnet-alloc, DHCP option B-20
- subnet allocation, DHCP 24-17, 1-10
  - configuring 24-22
- subnet-mask, DHCP option B-2
- subnets 9-3
  - adding 5-30
  - address ranges 9-10
  - child 9-9
  - client-accessible 20-13
  - creating 5-40
  - defined 20-6
  - editing 9-8
  - joining 21-19
  - local B-4
  - multiple logical 21-19
  - pushing to local clusters 9-7
  - reclaiming 9-8
  - sorting, enabling 17-4
  - viewing 9-4
- subnets, DHCP
  - address block 24-22
  - allocation request 24-22
  - increment 24-22
  - initial 24-22
- subnet-selection, DHCP option B-19
- subnet utilization
  - collect-addr-util-duration 9-12
  - collect-addr-util-interval 9-12
  - collection duration 6-13
  - data, collecting 9-13
  - enabling collection 6-13
  - failover server priority 6-13
  - polling
    - data 6-11
    - interval 6-13
    - offset 6-13
    - retry interval 6-13
  - poll-subnet-util-interval 9-13
  - poll-subnet-util-offset 9-13
  - poll-subnet-util-retry 9-13
  - querying 9-13
  - reports 9-12
  - server polling interval 6-13
  - trimming data 9-14
  - trim-subnet-util-age 9-14
  - trim-subnet-util-interval 9-14
  - viewing data 9-15
- subnet-utilization subrole (regional-addr-admin) 5-5
- subroles 5-3
  - central administration management 5-20, 12-2
- subscriber limitation, using option 82 25-13
  - troubleshooting 25-17
- subscribers, set by limitation-id 25-15
- substring, DHCP expression 26-18
- subzones 1-9
  - adding 15-15
  - delegating 15-16, 1-3, 1-10
  - editing 15-18
  - lame delegation 15-16
  - name server 15-16
  - naming 15-16
  - removing 15-17
- swap-server, DHCP option B-2
- synchronization, failover
  - Complete operation 28-7
  - Exact operation 28-7

- operations [28-8](#)
- Update operation [28-7](#)
- synchronous
  - dhcp edit mode [21-18](#)
  - dns edit mode [15-1](#)
  - edit mode [1-10](#)
- synthesize-host-name, DHCP expression [26-18](#)
- System Configuration Protocol (SCP) [4-2](#)
- System Management Server
  - See* SMS
- system metrics chart, dashboard [3-9](#)

---

## T

- TAC tool [7-30](#)
- tail command (Solaris) [7-4](#)
- tasks, scheduling [7-3](#)
- Tcl
  - API [30-8](#)
  - extensions [24-10, 24-11, 30-4, 30-7](#)
- TCP Default TTL, DHCP option [B-5](#)
- tcp-keepalive-garbage, DHCP option [B-5](#)
- tcp-keepalive-interval, DHCP option [B-5](#)
- /temp directory [8-3](#)
- templates
  - scope [21-3](#)
  - zone [15-2](#)
- tenant command (CLI)
  - create [5-9](#)
- tenant data
  - managing [5-10](#)
  - pushing and pulling [5-11](#)
  - using cnr\_exim [5-12](#)
- tenants
  - adding [5-9](#)
  - assigning cluster [5-11](#)
  - editing [5-9](#)
  - managing [5-8](#)
  - pulling from replica database [5-28](#)
  - pushing to local [5-27](#)
  - using external authentication [5-12](#)
- Text records
  - See* TXT records
- TFTP [1-2, B-10](#)
  - file caching [7-29](#)
  - logging and tracing [7-28](#)
  - packets, tracing [7-28](#)
  - troubleshooting [7-27](#)
- tftp command (CLI)
  - enable [1-3](#)
  - enable file-cache [7-29](#)
  - getStats [7-18](#)
  - getTraceLevel [1-3](#)
  - serverLogs [1-3](#)
  - set [1-3](#)
    - file-cache-directory [7-29](#)
    - file-cache-max-memory-size [7-29](#)
    - home-directory [7-29](#)
    - log-file-count [7-28](#)
    - log-level [7-28](#)
    - log-settings [7-6, 7-28](#)
  - show [1-3](#)
- tftp-interface command (CLI) [1-3](#)
- tftp-management subrole (cfg-admin) [5-4](#)
- tftp-server, DHCP option [B-10](#)
- time-offset, DHCP option [B-2](#)
- timeouts for unavailable leases [23-21](#)
- time-servers, DHCP option [B-2](#)
- time service, use of [6-12](#)
- Time to Live property
  - See* TTL property
- to-blob, DHCP expression [26-19](#)
- to-ip, DHCP expression [26-19](#)
- to-ip6, DHCP expression [26-19](#)
- to-lower, DHCP expression [26-19](#)
- Tomcat
  - database log files [7-7](#)
  - server [4-2](#)



top tool (UNIX) [7-29](#)  
 to-sint, DHCP expression [26-19](#)  
 to-string, DHCP expression [26-20](#)  
 to-uint, DHCP expression [26-20](#)  
 trailer-encapsulation, DHCP option [B-4](#)  
 translate, DHCP expression [26-20](#)  
 trap command (CLI)  
   set  
     free-address-low-threshold [1-6](#)  
 trap-recipient command (CLI)  
   create [1-6](#)  
 traps, SNMP [1-4, 28-31](#)  
   creating [21-22](#)  
   failover synchronization effect [28-9](#)  
   free-address-high [1-7](#)  
   free-address-low [1-7](#)  
   low and high address thresholds [21-22](#)  
   recipients, creating [1-6](#)  
 trimming  
   immediate subnet utilization [9-14](#)  
   subnet utilization records [9-14](#)  
 Trivial File Transfer Protocol  
   *See* TFTP  
 try, DHCP expression [26-21](#)  
 TSIG keys [29-9](#)  
   creating [29-10](#)  
   DNS update configuration attributes [29-12](#)  
   failover synchronization effect [28-9](#)  
   importing [29-11](#)  
   pulling [29-10](#)  
   pushing [29-10](#)  
   rules for secrets [29-11](#)  
   secrets, generating [29-10](#)  
 TTL property [A-1](#)  
   default [17-7, 22-2](#)  
     responses [17-7](#)  
   maximum  
     cache [18-7](#)  
     memory cache size [18-9](#)

    negative cache [1-6](#)  
     zone [17-7](#)  
 tutorial  
   local cluster [5-28](#)  
   regional cluster [5-35](#)  
 TXT records [A-7](#)  
 tz-database, DHCP option [B-19](#)  
 tz-posix, DHCP option [B-19](#)

---

## U

uBR 10000 routers [11-2](#)  
 uBR 7200 routers [5-38, 11-2](#)  
 Ultra-SCSI disk [4-3](#)  
 unicast, enabling [24-6](#)  
 unified address space [9-3](#)  
 Universal Resource Identifiers (URIs) [16-8](#)  
 UNIX, troubleshooting tools [7-29](#)  
 update-policy (CLI command)  
   create [29-13](#)  
   delete [29-15](#)  
   rules  
     add [29-14](#)  
     remove [29-15](#)  
 user-auth, DHCP option [B-18](#)  
 user-class, DHCPv6 option [B-12](#)  
 user interfaces [2-1](#)  
 user preferences, setting [2-9](#)  
 users  
   differentiated services [20-11](#)  
   event warnings [7-5](#)  
   lease availability [20-7](#)  
   types of [4-1](#)  
 utility programs  
   ipconfig [21-23](#)  
   ping [23-7](#)  
   third party backup [8-3](#)

## V

- validate-host-name, DHCP expression [26-21](#)
- vendor-class, DHCPv6 option [B-12](#)
- vendor-encapsulated-options, DHCP option [B-17](#)
- vendor-opts, DHCPv6 option [B-12](#)
- virtual channel identifier [26-25](#)
- virtual path identifier [26-25, 1-11](#)
- virtual private networks
  - See* VPNs
- virtual routing and forwarding table ID
  - See* VRFs
- virus scanning, excluding directories [8-9](#)
- visibility of attributes [2-5](#)
- v-i-vendor-class, DHCP option [B-19](#)
- v-i-vendor-info, DHCP option [B-19](#)
- vmstat tool (UNIX) [7-29](#)
- vpn command (CLI)
  - create [24-19](#)
  - set
    - vrf-name [24-19](#)
- vpn-id, DHCP option [B-20](#)
- VPNs [20-5, 24-17](#)
  - configuring [24-17](#)
  - creating [24-19](#)
  - current [24-20](#)
  - failover synchronization effect [28-9](#)
  - identifier [24-19](#)
  - IOS support [24-17](#)
  - leases in, importing [24-21](#)
  - local
    - pulling [6-19](#)
    - pushing [6-18](#)
  - orphaned leases [24-23](#)
  - regional [6-18](#)
  - scopes [24-19](#)
  - setting current [21-11](#)
  - VRFs [24-19](#)
- VRFs [24-18, 24-19](#)

## W

- Web UI [1-1](#)
  - attributes
    - displaying [2-5](#)
    - modifying [2-5](#)
    - visibility [2-5](#)
  - changes, committing [2-5](#)
  - deployment scenarios [4-3](#)
  - help
    - attributes [2-6](#)
    - topics [2-6](#)
  - logging [7-6](#)
  - logging in [2-2](#)
  - navigation [2-4](#)
- Well Known Services record
  - See* WKS records
- Windows
  - CLI location [2-10](#)
  - Event Viewer [7-5](#)
  - ipconfig utility [25-10](#)
  - logging [7-4](#)
  - mouse buttons [xxxiii](#)
- Windows 2000
  - client properties [25-10](#)
  - DNS update [29-18, 29-24](#)
  - domain controllers [29-24](#)
  - environments [29-23](#)
  - SRV records [29-22, A-7](#)
- Windows SMS
  - See* SMS
- winipcfg utility [25-10](#)
- WKS records [A-8, 1-11](#)
- www-servers, DHCP option [B-7](#)

## X

- x-display-managers, DHCP option [B-7](#)

**Y**

yiaddr, DHCP field [24-18, 1-11](#)

**Z**

## zone

edit mode, setting [15-2](#)

## templates

cloning [15-4](#)

creating using CLI [15-4](#)

## zone (CLI command)

## listRR

dns [29-16](#)

## set

update-policy-list [29-15](#)

## zone command (CLI)

addDNSRR [10-2, 16-3](#)

addHost [10-2](#)

addRR [10-2, 16-3](#)

A [15-7](#)

PTR [15-13](#)

-staged or -sync [16-2](#)

applyTemplate [15-7](#)

chkpt [17-5](#)

cleanRR [16-7](#)

## create

primary [15-7](#)

template, using [15-7](#)

dumpchkpt [17-5](#)

## enable

notify [17-6](#)

findRR [16-6](#)

forceXfer [15-15](#)

## get

serial [15-6, 15-7](#)

getScavengeStartTime [29-17](#)

listHosts [10-2, 15-7](#)

listRR [15-8, 16-5](#)

removeDNSRR [10-3, 16-4](#)

removeHost [10-3](#)

removeRR [10-3, 16-4](#)

## set

checkpoint-interval [17-5](#)

defttl [17-7](#)

dist-map [15-22](#)

expire [17-8](#)

log-settings [29-17](#)

nameservers [15-7](#)

notify-set [17-6](#)

refresh [17-8](#)

retry [17-8](#)

scvg-ignore-restart-interval [29-17](#)

scvg-interval [29-17](#)

scvg-no-refresh-interval [29-17](#)

scvg-refresh-interval [29-17](#)

show [15-7](#)

syncToDns [15-8](#)

## zone-dist command (CLI)

addSecondary [15-22](#)

create [7-22, 15-22](#)

list [7-22](#)

## set

master-servers [15-22](#)

sync [15-22](#)

## zone distributions

creating [7-22, 15-22](#)

listing [7-22](#)

managing [15-19](#)

master servers, adding [15-22](#)

secondaries, adding [15-22](#)

synchronizing [15-22](#)

zone-regexpr syntax [5-33](#)

## zones

address restrictions [5-33](#)

applying update policies [29-15](#)

authoritative name servers [15-6](#)

configuring [10-1, 11-1, 16-1, 17-1, 18-1](#)

- count on server, getting [15-14](#)
- defined [14-3](#)
- delegated subzone records, editing [15-18](#)
- delegated subzones, removing [15-17](#)
- delegation-only [17-3](#)
- difference from domains [14-3](#)
- displaying resource records [16-5](#)
- DNS update, enabling [15-18](#)
- domains, adding [16-2](#)
- dual zone updates [29-20](#)
- edits
  - staged and synchronous modes [15-1](#)
- hostmaster [15-6](#)
- hosts
  - adding [10-1, 16-9](#)
  - removing [10-3](#)
- host tables, editing [10-2](#)
- importing [15-9](#)
- infrastructure [5-31](#)
- listing [5-31](#)
- loopback, *See* loopback, zones
- names, creating [15-5](#)
- point of delegation [14-3](#)
- primary server, setting [15-6](#)
- resource records
  - adding [16-2](#)
  - filtering [16-7](#)
  - protecting [16-3](#)
  - removing [16-4](#)
- restricting hosts [5-33](#)
- reverse, *See* reverse zones
- scavenging [7-2, 29-16](#)
  - start time, getting [29-17](#)
- secondary
  - expiration time [17-8](#)
  - refresh time [17-7](#)
  - retry time [17-8](#)
- secondary name servers, adding [15-14](#)
- serial numbers [15-6](#)
- staged edit mode [1-9](#)
- subzones, delegating [1-10](#)
- synchronous edit mode [1-10](#)
- template, adding from [15-7](#)
- transfers, *See* zone transfers
- TTL property, setting [17-7](#)
- zone distributions, associating [15-22](#)
- zone transfers, enabling [15-15](#)
- zone-template command (CLI)
  - apply-to [15-4](#)
  - create [15-4](#)
    - clone [15-4](#)
  - set
    - dist-map [15-22](#)
- zone templates
  - applying to zones [15-4](#)
  - creating [15-2](#)
  - zone distributions, associating [15-22](#)
- zone transfers
  - defined [14-5](#)
  - enabling [15-15](#)
  - forcing [7-2, 15-15](#)
  - forcing all [15-15](#)
- zone tree, viewing [5-31](#)