



Access List Commands

This module describes the Cisco IOS XR software commands used to configure IP Version 4 (IPv4) and IP Version 6 (IPv6) access lists.

An access control list (ACL) consists of one or more access control entries (ACEs) that collectively define the network traffic profile. This profile can then be referenced by Cisco IOS XR Software software features such as traffic filtering, priority or custom queueing, and dynamic access control. Each ACL includes an action element (permit or deny) and a filter element based on criteria such as source address, destination address, protocol, and protocol-specific parameters.

For detailed information about ACL concepts, configuration tasks, and examples, refer to the *Cisco IOS XR IP Addresses and Services Configuration Guide for the Cisco XR 12000 Series Router*.

- [clear access-list ipv4, page 2](#)
- [clear access-list ipv6, page 4](#)
- [copy access-list ipv4, page 7](#)
- [copy access-list ipv6, page 8](#)
- [deny \(IPv4\), page 10](#)
- [deny \(IPv6\), page 21](#)
- [ipv4 access-group, page 25](#)
- [ipv4 access-list, page 28](#)
- [ipv4 access-list log-update rate, page 29](#)
- [ipv4 access-list log-update threshold, page 30](#)
- [ipv6 access-group, page 31](#)
- [ipv6 access-list, page 33](#)
- [ipv6 access-list log-update rate, page 35](#)
- [ipv6 access-list log-update threshold, page 36](#)
- [ipv6 access-list maximum ace threshold, page 37](#)
- [ipv6 access-list maximum acl threshold, page 38](#)
- [permit \(IPv4\), page 39](#)

- [permit \(IPv6\)](#), page 53
- [remark \(IPv4\)](#), page 57
- [remark \(IPv6\)](#), page 59
- [resequence access-list ipv4](#), page 61
- [resequence access-list ipv6](#), page 62
- [show access-lists afi-all](#), page 64
- [show access-lists ipv4](#), page 65
- [show access-lists ipv4 standby](#), page 70
- [show access-lists ipv6](#), page 71
- [show access-lists ipv6 standby](#), page 75

clear access-list ipv4

To clear IPv4 access list counters, use the **clear access-list ipv4** command in EXEC mode.

clear access-list ipv4 *access-list name* [*sequence-number* | hardware { ingress | egress}] [*interface type interface-path-id*][*location node-id* | *sequence number*]

Syntax Description

access-list-name	Name of a particular IPv4 access list. The name cannot contain a spaces or quotation marks, but can include numbers.
sequence-number	(Optional) Specific sequence number with which counters are cleared for an access list. Range is 1 to 2147483646.
hardware	Identifies the access list as an access group for an interface.
ingress	Specifies an inbound direction.
egress	Specifies an outbound direction.
interface	(Optional) Clears the interface statistics.
type	Interface type. For more information, use the question mark (?) online help function.
interface-path-id	Physical interface or virtual interface. Note Use the show interfaces command to see a list of all interfaces currently configured on the router. For more information about the syntax for the router, use the question mark (?) online help function.
location <i>node-id</i>	(Optional) Clears hardware resource counters from the designated node. The <i>node-id</i> argument is entered in the <i>rack/slot/module</i> notation.

sequence number (Optional) Clears counters for an access list with a specific sequence number. Range is 1 to 2147483646.

Command Default The default clears the specified IPv4 access list.

Command Modes EXEC

Release	Modification
Release 3.2	This command was introduced.
Release 3.5.0	The interface keyword was added.

Usage Guidelines To use this command, you must be in a user group associated with a task group that includes appropriate task IDs. If the user group assignment is preventing you from using a command, contact your AAA administrator for assistance.

Use the **clear access-list ipv4** command to clear counters for a specified configured access list. Use a sequence number to clear counters for an access list with a specific sequence number.

Use the **hardware** keyword to clear counters for an access list that was enabled using the **ipv4 access-group** command.

Use an asterisk (*****) in place of the *access-list-name* argument to clear all access lists.



Note

An access list can be shared among multiple interfaces. Clearing hardware counters clears all counters for all interfaces that use the specified access list in a given direction (ingress or egress).

Task ID	Operations
basic-services	read, write
acl	read, write
bgp	read, write, execute

In the following example, counters for an access list named *marketing* are cleared:

```
RP/0/0/CPU0:router# show access-lists ipv4 marketing
ipv4 access-list marketing
```

```

10 permit ip 192.168.34.0 0.0.0.255 any (51 matches)
20 permit ip 172.16.0.0 0.0.255.255 any (26 matches)
30 deny tcp host 172.16.0.0 eq bgp host 192.168.202.203 30 (5 matches)

```

```
RP/0/0/CPU0:router# clear access-list ipv4 marketing
```

```
RP/0/0/CPU0:router# show access-lists ipv4 marketing
```

```

ipv4 access-list marketing
10 permit ip 192.168.34.0 0.0.0.255 any
20 permit ip 172.16.0.0 0.0.255.255 any
30 deny tcp host 172.16.0.0 eq bgp host 192.168.202.203 30

```

In the following example, counters for an access list named `acl_hw_1` in the outbound direction are cleared:

```
RP/0/0/CPU0:router# show access-lists ipv4 acl_hw_1 hardware egress location 0/2/cp0
```

```

ipv4 access-list acl_hw_1
10 permit icmp 192.168.36.0 0.0.0.255 any (251 hw matches)
20 permit ip 172.16.3.0 0.0.255.255 any (29 hw matches)
30 deny tcp any any (58 hw matches)

```

```
RP/0/0/CPU0:router# clear access-list ipv4 acl_hw_1 hardware egress location 0/2/cp0
```

```
RP/0/0/CPU0:router# show access-lists ipv4 acl_hw_1 hardware egress location 0/2/cp0
```

```

ipv4 access-list acl_hw_1
10 permit icmp 192.168.36.0 0.0.0.255 any
20 permit ip 172.16.3.0 0.0.255.255 any
30 deny tcp any any

```

Related Commands

Command	Description
ipv4 access-group , on page 25	Filters incoming or outgoing IPv4 traffic on an interface.
ipv4 access-list , on page 28	Defines an IPv4 access list and enters IPv4 access list configuration mode.
resequence access-list ipv4 , on page 61	Renumbers an existing statement and increments subsequent statements to allow a new IPv4 access list statements.

clear access-list ipv6

To clear IPv6 access list counters, use the **clear access-list ipv6** command in EXEC mode.

```
clear access-list ipv6 access-list-name [sequence-number] hardware {ingress|egress} [interface type interface-path-id] [location node-id] sequence number
```

Syntax Description

<code>access-list-name</code>	Name of a particular IPv6 access list. The name cannot contain a space or quotation marks, but can include numbers.
-------------------------------	---

sequence-number	(Optional) Specific sequence number for a particular access control entry (ACE) with which counters are cleared for an access list. Range is 1 to 2147483644.
hardware	(Optional) Identifies the access list as an access group for an interface.
ingress	(Optional) Specifies an inbound direction.
egress	(Optional) Specifies an outbound direction.
interface	(Optional) Clears the interface statistics.
type	(Optional) Interface type. For more information, use the question mark (?) online help function.
<i>instance</i>	Physical interface or virtual interface.
<i>interface-path-id</i>	Note Use the show interfaces command to see a list of all interfaces currently configured on the router. For more information about the syntax for the router, use the question mark (?) online help function.
location <i>node-id</i>	(Optional) Clears counters for an access list enabled on a card interface. The <i>node-id</i> argument is entered in the rack/slot/module notation.
sequence <i>number</i>	(Optional) Specifies a specific sequence number that clears access list counters. Range is 1 to 2147483644.

Command Default

The default clears the specified IPv6 access list.

Command Modes

EXEC

Command History

Release	Modification
Release 3.2	This command was introduced.
Release 3.5.0	The interface keyword was added.

Usage Guidelines

To use this command, you must be in a user group associated with a task group that includes appropriate task IDs. If the user group assignment is preventing you from using a command, contact your AAA administrator for assistance.

The **clear access-list ipv6** command is similar to the **clear access-list ipv4** command, except that it is IPv6-specific.

Use the **clear access-list ipv6** command to clear counters for a specified configured access list. Use a sequence number to clear counters for an access list with a specific sequence number

Use the **hardware** keyword to clear counters for an access list that was enabled using the **ipv6 access-group** command.

Use an asterisk (*) in place of the *access-list-name* argument to clear all access lists.

**Note**

An access list can be shared among multiple interfaces. Clearing hardware counters clears all counters for all interfaces that use the specified access list in a given direction (ingress or egress).

Task ID

Task ID	Operations
basic-services	read, write
acl	read, write
network	read, write

In the following example, counters for an access list named *marketing* are cleared:

```
RP/0/0/CPU0:router# show access-lists ipv6 marketing
ipv6 access-list marketing
 10 permit ipv6 3333:1:2:3::/64 any (51 matches)
 20 permit ipv6 4444:1:2:3::/64 any (26 matches)
 30 permit ipv6 5555:1:2:3::/64 any (5 matches)
RP/0/0/CPU0:router# clear access-list ipv6 marketing
RP/0/0/CPU0:router# show access-lists ipv6 marketing
ipv6 access-list marketing
 10 permit ipv6 3333:1:2:3::/64 any
 20 permit ipv6 4444:1:2:3::/64 any
 30 permit ipv6 5555:1:2:3::/64 any
```

In the following example, counters for an access list named *acl_hw_1* in the outbound direction are cleared:

```
RP/0/0/CPU0:router# show access-lists ipv6 acl_hw_1 hardware egress location 0/2/cp0
ipv6 access-list acl_hw_1
 10 permit ipv6 3333:1:2:3::/64 any (251 hw matches)
 20 permit ipv6 4444:1:2:3::/64 any (29 hw matches)
 30 deny tcp any any (58 hw matches)
RP/0/0/CPU0:router# clear access-list ipv6 acl_hw_1 hardware egress location 0/2/cp0
RP/0/0/CPU0:router# show access-lists ipv6 acl_hw_1 hardware egress location 0/2/cp0
ipv6 access-list acl_hw_1
 10 permit ipv6 3333:1:2:3::/64 any
 20 permit ipv6 4444:1:2:3::/64 any
 30 deny tcp any any
```

Related Commands

Command	Description
ipv6 access-list , on page 33	Defines an IPv6 access list and enters IPv6 access list configuration mode.

copy access-list ipv4

To create a copy of an existing IPv4 access list, use the **copy access-list ipv4** command in EXEC mode.

copy access-list ipv4 *source-acl destination-acl*

Syntax Description

source-acl	Name of the access list to be copied.
destination-acl	Name of the destination access list where the contents of the <i>source-acl</i> argument is copied.

Command Default

No default behavior or values

Command Modes

EXEC

Command History

Release	Modification
Release 3.2	This command was introduced.

Usage Guidelines

To use this command, you must be in a user group associated with a task group that includes appropriate task IDs. If the user group assignment is preventing you from using a command, contact your AAA administrator for assistance.

Use the **copy access-list ipv4** command to copy a configured access list. Use the *source-acl* argument to specify the access list to be copied and the *destination-acl* argument to specify where to copy the contents of the source access list. The *destination-acl* argument must be a unique name; if the *destination-acl* argument name exists for an access list or prefix list, the access list is not copied. The **copy access-list ipv4** command checks that the source access list exists then checks the existing list names to prevent overwriting existing access lists or prefix lists.

Task ID

Task ID	Operations
acl	read, write
filesystem	execute

In the following example, a copy of access list list-1 is created:

```
RP/0/0/CPU0:router# show access-lists ipv4 list-1

ipv4 access-list list-1
 10 permit tcp any any log
 20 permit ip any any
RP/0/0/CPU0:router# copy access-list ipv4 list-1 list-2
RP/0/0/CPU0:router# show access-lists ipv4 list-2
ipv4 access-list list-2
 10 permit tcp any any log
 20 permit ip any any
```

In the following example, copying the access list list-1 to list-3 is denied because a list-3 access list already exists:

```
RP/0/0/CPU0:router# copy access-list ipv4 list-1 list-3

list-3 exists in access-list

RP/0/0/CPU0:router# show access-lists ipv4 list-3

ipv4 access-list list-3
 10 permit ip any any
 20 deny tcp any any log
```

Related Commands

Command	Description
ipv4 access-list , on page 28	Defines an IPv4 access list and enters IPv4 access list configuration mode.
show access-lists ipv4 , on page 65	Displays the contents of all current IPv4 access lists.

copy access-list ipv6

To create a copy of an existing IPv6 access list, use the **copy access-list ipv6** command in EXEC mode.

copy access-list ipv6 *source-acl destination-acl*

Syntax Description

source-acl	Name of the access list to be copied.
destination-acl	Destination access list where the contents of the <i>source-acl</i> argument is copied.

Command Default

No default behavior or value

Command Modes EXEC

Command History	Release	Modification
	Release 3.2	This command was introduced . The command name was changed from copy ipv6 access-list to copy access-list ipv6 .

Usage Guidelines To use this command, you must be in a user group associated with a task group that includes appropriate task IDs. If the user group assignment is preventing you from using a command, contact your AAA administrator for assistance.

Use the **copy access-list ipv6** command to copy a configured access list. Use the *source-acl* argument to specify the access list to be copied and the *destination-acl* argument to specify where to copy the contents of the source access list. The *destination-acl* argument must be a unique name; if the *destination-acl* argument name exists for an access list or prefix list, the access list is not copied. The **copy access-list ipv6** command checks that the source access list exists then checks the existing list names to prevent overwriting existing access lists or prefix lists.

Task ID	Task ID	Operations
	acl	read, write
	filesystem	execute

In the following example, a copy of access list list-1 is created:

```
RP/0/0/CPU0:router# show access-lists ipv6 list-1
ipv6 access-list list-1
 10 permit tcp any any log
 20 permit ipv6 any any
RP/0/0/CPU0:router# copy access-list ipv6 list-1 list-2
RP/0/0/CPU0:router# show access-lists ipv6 list-2
ipv6 access-list list-2
 10 permit tcp any any log
 20 permit ipv6 any any
```

In the following example, copying access list list-1 to list-3 is denied because a list-3 access list already exists:

```
RP/0/0/CPU0:router# copy access-list ipv6 list-1 list-3
list-3 exists in access-list
RP/0/0/CPU0:router# show access-lists ipv6 list-3
ipv6 access-list list-3
 10 permit ipv6 any any
```

```
20 deny tcp any any log
```

Related Commands

Command	Description
ipv6 access-list , on page 33	Defines an IPv6 access list and enters IPv6 access list configuration mode.
show access-lists ipv6 , on page 71	Displays the contents of all current IPv6 access lists.

deny (IPv4)

To set conditions for an IPv4 access list, use the **deny** command in access list configuration mode. There are two versions of the **deny** command: **deny** (source), and **deny** (protocol). To remove a condition from an access list, use the **no** form of this command.

```
[ sequence-number ] deny source [ source-wildcard ] counter counter-name [log log-input]
[sequence-number]denyprotocol source source-wildcard destination destination-wildcard
[precedenceprecedence] [dscpdscp] [fragments] [ packet-length operator packet-length value] [ log |
log-input] [ttl ttl value [value1....value2]]
no sequence-number
```

Internet Control Message Protocol (ICMP)

```
[ sequence-number ] deny icmp source source-wildcard destination destination-wildcard [ icmp-type ]
[ icmp-code ] [precedence precedence] [dscp dscp] [fragments] [log log-input][icmp-off]
```

Internet Group Management Protocol (IGMP)

```
[ sequence-number ] deny igmp source source-wildcard destination destination-wildcard [ igmp-type ]
[precedence precedence] [dscp value] [fragments] [log log-input]
```

User Datagram Protocol (UDP)

```
[ sequence-number ] deny udp source source-wildcard [operator {port| protocol-port}] destination
destination-wildcard [operator {port| protocol-port}] [precedence precedence] [dscp dscp] [fragments]
[log log-input]
```

Syntax Description

sequence-number	(Optional) Number of the deny statement in the access list. This number determines the order of the statements in the access list. The number can be from 1 to 2147483646. (By default, the first statement is number 10, and the subsequent statements are incremented by 10.) Use the resequence access-list command to change the number of the first statement and increment subsequent statements of a configured access list.
-----------------	---

source	<p>Number of the network or host from which the packet is being sent. There are three alternative ways to specify the source:</p> <ul style="list-style-type: none"> • Use a 32-bit quantity in four-part dotted-decimal format. • Use the any keyword as an abbreviation for a <i>source</i> and <i>source-wildcard</i> of 0.0.0.0 255.255.255.255. • Use the host source combination as an abbreviation for a <i>source</i> and <i>source-wildcard</i> of <i>source</i> 0.0.0.0.
source-wildcard	<p>Wildcard bits to be applied to the source. There are three alternative ways to specify the source wildcard:</p> <ul style="list-style-type: none"> • Use a 32-bit quantity in four-part dotted-decimal format. Place ones in the bit positions you want to ignore. • Use the any keyword as an abbreviation for a <i>source</i> and <i>source-wildcard</i> of 0.0.0.0 255.255.255.255. • Use the host source combination as an abbreviation for a <i>source</i> and <i>source-wildcard</i> of <i>source</i> 0.0.0.0.
protocol	<p>Name or number of an IP protocol. It can be one of the keywords ahp, esp, eigrp, gre, icmp, igmp, igrp, ip, ipinip, nos, ospf, pim, pcp, sctp, tcp, or udp, or an integer from 0 to 255 representing an IP protocol number. To match any Internet protocol (including ICMP, TCP, and UDP), use the ip keyword. ICMP, SCTP, and TCP allow further qualifiers, which are described later in this table.</p>
destination	<p>Number of the network or host to which the packet is being sent. There are three alternative ways to specify the destination:</p> <ul style="list-style-type: none"> • Use a 32-bit quantity in four-part dotted-decimal format. • Use the any keyword as an abbreviation for the <i>destination</i> and <i>destination-wildcard</i> of 0.0.0.0 255.255.255.255. • Use the host destination combination as an abbreviation for a <i>destination</i> and <i>destination-wildcard</i> of <i>destination</i> 0.0.0.0.
destination-wildcard	<p>Wildcard bits to be applied to the destination. There are three alternative ways to specify the destination wildcard:</p> <ul style="list-style-type: none"> • Use a 32-bit quantity in four-part dotted-decimal format. Place ones in the bit positions you want to ignore. • Use the any keyword as an abbreviation for a <i>destination</i> and <i>destination-wildcard</i> of 0.0.0.0 255.255.255.255. • Use the host destination combination as an abbreviation for a <i>destination</i> and <i>destination-wildcard</i> of <i>destination</i> 0.0.0.0.

precedence <i>precedence</i>	(Optional) Packets can be filtered by precedence level (as specified by a number from 0 to 7) or by the following names: <ul style="list-style-type: none">• routine –Match packets with routine precedence (0)• priority –Match packets with priority precedence (1)• immediate –Match packets with immediate precedence (2)• flash –Match packets with flash precedence (3)• flash-override –Match packets with flash override precedence (4)• critical –Match packets with critical precedence (5)• internet –Match packets with internetwork control precedence (6)• network –Match packets with network control precedence (7)
--	--

dscp <i>dscp</i>	<p>(Optional) Differentiated services code point (DSCP) provides quality of service control. The values for <i>dscp</i> are as follows:</p> <ul style="list-style-type: none"> • 0—63—Differentiated services codepoint value • af11—Match packets with AF11 dscp (001010) • af12—Match packets with AF12 dscp (001100) • af13—Match packets with AF13 dscp (001110) • af21—Match packets with AF21 dscp (010010) • af22—Match packets with AF22 dscp (010100) • af23—Match packets with AF23 dscp (010110) • af31—Match packets with AF31 dscp (011010) • af32—Match packets with AF32 dscp (011100) • af33—Match packets with AF33 dscp (011110) • af41—Match packets with AF41 dscp (100010) • af42—Match packets with AF42 dscp (100100) • af43—Match packets with AF43 dscp (100110) • cs1—Match packets with CS1(precedence 1) dscp (001000) • cs2—Match packets with CS2(precedence 2) dscp (010000) • cs3—Match packets with CS3(precedence 3) dscp (011000) • cs4—Match packets with CS4(precedence 4) dscp (100000) • cs5—Match packets with CS5(precedence 5) dscp (101000) • cs6—Match packets with CS6(precedence 6) dscp (110000) • cs7—Match packets with CS7(precedence 7) dscp (111000) • default—Default DSCP (000000) • ef—Match packets with EF dscp (101110)
fragments	<p>(Optional) Causes the software to examine fragments of IPv4 packets when applying this access list entry. When this keyword is specified, fragments are subject to the access list entry.</p>
packet-length operator	<p>(Optional) Packet length operator used for filtering.</p>
packet-length value	<p>(Optional) Packet length used to match only packets in the range of the length.</p>

log	<p>(Optional) Causes an informational logging message about the packet that matches the entry to be sent to the console. (The level of messages logged to the console is controlled by the logging console command.)</p> <p>The message includes the access list number, whether the packet was permitted or denied; the protocol, whether it was TCP, UDP, ICMP, or a number; and, if appropriate, the source and destination addresses and source and destination port numbers. The message is generated for the first packet that matches a flow, and then at 5-minute intervals, including the number of packets permitted or denied in the prior 5-minute interval.</p>
log-input	(Optional) Provides the same function as the log keyword, except that the logging message also includes the input interface.
ttl	(Optional) Turns on matching against time-to-life (TTL) value.
ttl value1 value2	<p>(Optional) TTL value used for filtering. Range is 1 to 255.</p> <p>If only <i>value1</i> is specified, the match is against this value.</p> <p>If both <i>value1</i> and <i>value2</i> are specified, the packet TTL is matched against the range of TTLs between <i>value1</i> and <i>value2</i>.</p>
icmp-off	(Optional) Turns off ICMP generation for denied packets.
icmp-type	(Optional) ICMP message type for filtering ICMP packets. Range is from 0 to 255.
icmp-code	(Optional) ICMP message code for filtering ICMP packets. Range is from 0 to 255.
igmp-type	<p>(Optional) IGMP message type (0 to 15) or message name for filtering IGMP packets, as follows:</p> <ul style="list-style-type: none"> • dvmrp • host-query • host-report • mtrace • mtrace-response • pim • precedence • trace • v2-leave • v2-report • v3-report

operator	<p>(Optional) Operator is used to compare source or destination ports. Possible operands are lt (less than), gt (greater than), eq (equal), neq (not equal), and range (inclusive range).</p> <p>If the operator is positioned after the <i>source</i> and <i>source-wildcard</i> values, it must match the source port.</p> <p>If the operator is positioned after the <i>destination</i> and <i>destination-wildcard</i> values, it must match the destination port.</p> <p>If the operator is positioned after the ttl keyword, it matches the TTL value.</p> <p>The range operator requires two port numbers. All other operators require one port number.</p>
protocol-port	<p>Name of a TCP or UDP port. TCP and UDP port names are listed in the “Usage Guidelines” section.</p> <p>TCP port names can be used only when filtering TCP. UDP port names can be used only when filtering UDP.</p>
established	(Optional) For the TCP protocol only: Indicates an established connection.
match-any	(Optional) For the TCP protocol only: Filters on any combination of TCP flags.
match-all	(Optional) For the TCP protocol only: Filters on all TCP flags.
+ -	(Required) For the TCP protocol match-any , match-all : Prefix <i>flag-name</i> with + or - . Use the + <i>flag-name</i> argument to match packets with the TCP flag set. Use the - <i>flag-name</i> argument to match packets when the TCP flag is not set.
flag-name	(Required) For the TCP protocol match-any , match-all . Flag names are: ack, fin, psh, rst, syn.

Command Default

There is no specific condition under which a packet is denied passing the IPv4 access list. ICMP message generation is enabled by default.

Command Modes

IPv4 access list configuration

Command History

Release	Modification
Release 3.2	This command was introduced.

Release	Modification
Release 3.3.0	<p>The optional keywords match-any and match-all were added for the TCP protocol. The argument <i>flag-name</i> was added for the TCP protocol.</p> <p>The match-any and match-all keywords and the <i>flag-name</i> argument are supported.</p> <p>The optional keyword icmp-off was added for the ICMP protocol.</p>
Release 3.4.0	<p>The optional keyword ttl and the associated arguments <i>ttl value1</i> and <i>value2</i> and <i>operator</i>, with range values, were added to the command.</p>

Usage Guidelines

To use this command, you must be in a user group associated with a task group that includes appropriate task IDs. If the user group assignment is preventing you from using a command, contact your AAA administrator for assistance.

Use the **deny** command following the **ipv4 access-list** command to specify conditions under which a packet cannot pass the access list.

By default, the first statement in an access list is number 10, and the subsequent statements are incremented by 10.

You can add **permit**, **deny**, or **remark** statements to an existing access list without retyping the entire list. To add a new statement anywhere other than at the end of the list, create a new statement with an appropriate entry number that falls between two existing entry numbers to indicate where it belongs.

If you want to add a statement between two consecutively numbered statements (for example, between lines 10 and 11), first use the **resequence access-list** command to renumber the first statement and increment the entry number of each subsequent statement. The *increment* argument causes new, unused line numbers between statements. Then add a new statement with the *entry-number* argument, specifying where it belongs in the access list.

The following is a list of precedence names:

- critical
- flash
- flash-override
- immediate
- internet
- network
- priority

- routine

The following is a list of ICMP message type names:

- administratively-prohibited
- alternate-address
- conversion-error
- dod-host-prohibited
- dod-net-prohibited
- echo
- echo-reply
- general-parameter-problem
- host-isolated
- host-precedence-unreachable
- host-redirect
- host-tos-redirect
- host-tos-unreachable
- host-unknown
- host-unreachable
- information-reply
- information-request
- mask-reply
- mask-request
- mobile-redirect
- net-redirect
- net-tos-redirect
- net-tos-unreachable
- net-unreachable
- network-unknown
- no-room-for-option
- option-missing
- packet-too-big
- parameter-problem
- port-unreachable
- precedence-unreachable

- protocol-unreachable
- reassembly-timeout
- redirect
- router-advertisement
- router-solicitation
- source-quench
- source-route-failed
- time-exceeded
- timestamp-reply
- timestamp-request
- traceroute
- ttl-exceeded
- unreachable

The following is a list of TCP port names that can be used instead of port numbers. Refer to the current *Assigned Numbers* RFC to find a reference to these protocols. You can find port numbers corresponding to these protocols by typing a ? in the place of a port number.

- bgp
- chargen
- cmd
- daytime
- discard
- domain
- echo
- exec
- finger
- ftp
- ftp-data
- gopher
- hostname
- ident
- irc
- klogin
- kshell
- login

- lpd
- nntp
- pim-auto-rp
- pop2
- pop3
- smtp
- sunrpc
- tacacs
- talk
- telnet
- time
- uucp
- whois
- www

The following UDP port names can be used instead of port numbers. Refer to the current *Assigned Numbers* RFC to find a reference to these protocols. You can find port numbers corresponding to these protocols by typing a ? in the place of a port number.

- biff
- bootpc
- bootps
- discard
- dnsix
- domain
- echo
- isakmp
- mobile-ip
- nameserver
- netbios-dgm
- netbios-ns
- netbios-ss
- ntp
- pim-auto-rp
- rip
- snmp

- snmptrap
- sunrpc
- syslog
- tacacs
- talk
- tftp
- time
- who
- xdmcp

Use the following flags in conjunction with the **match-any** and **match-all** keywords and the + and - signs to select the flags to display:

- ack
- fin
- psh
- rst
- syn

For example, **match-all** + *ack* + *syn* displays TCP packets with both the *ack* and *syn* flags set, or **match-any** + *ack* - *syn* displays the TCP packets with the *ack* set or the *syn* not set.

Task ID

Task ID	Operations
ipv4	read, write
acl	read, write

The following example shows how to set a deny condition for an access list named Internetfilter:

```
RP/0/0/CPU0:router(config)# ipv4 access-list Internetfilter
RP/0/0/CPU0:router(config-ipv4-acl)# 10 deny 192.168.34.0 0.0.0.255
RP/0/0/CPU0:router(config-ipv4-acl)# 20 deny 172.16.0.0 0.0.255.255
RP/0/0/CPU0:router(config-ipv4-acl)# 25 deny tcp host 172.16.0.0 eq bgp host 192.168.202.203
range 1300 1400
RP/0/0/CPU0:router(config-ipv4-acl)# permit 10.0.0.0 0.255.255.255
```

Related Commands

Command	Description
ipv4 access-group , on page 25	Filters incoming or outgoing IPv4 traffic on an interface.

Command	Description
ipv4 access-list , on page 28	Defines an IPv4 access list and enters IPv4 access list configuration mode.
permit (IPv4) , on page 39	Sets the permit conditions for an IPv4 access list
remark (IPv4) , on page 57	Inserts a helpful remark about an IPv4 access list entry.
resequence access-list ipv4 , on page 61	Changes the starting entry number of the first statement in an existing IPv4 access list, and the number by which subsequent statements are incremented.
show access-lists ipv4 , on page 65	Displays the contents of all current IPv4 access lists.

deny (IPv6)

To set deny conditions for an IPv6 access list, use the **deny** command in IPv6 access list configuration mode. To remove the deny conditions, use the **no** form of this command.

```
[sequence-number] deny protocol {source-ipv6-prefix/ prefix-length | any | host source-ipv6-address} [operator {port | protocol-port}] [dscpvalue] [routing] [authen] [destopts] [ fragments] [packet-length operator packet-length value ] [ log | log-input] [ttl operator ttl value ]
```

```
no sequence-number
```

Internet Control Message Protocol (ICMP)

```
[ sequence-number] deny icmp {source-ipv6-prefix/ prefix-length | any | host source-ipv6-address} {destination-ipv6-prefix/ prefix-length | any | host destination-ipv6-address} [icmp-type] [ icmp-code][dscp value] [ routing] [authen] [destopts] [ fragments] [ log] [log-input] [icmp-off]
```

Transmission Control Protocol (TCP)

```
[sequence-number] deny tcp {source-ipv6-prefix/ prefix-length | any | host source-ipv6-address} [operator {port | protocol-port}] {destination-ipv6-prefix/ prefix-length | any | host destination-ipv6-address} [operator {port | protocol | port}] [dscpvalue] [routing] [authen] [destopts] [fragments] [established] {match-any | match-all | + | -} [flag-name] [log] [log-input]
```

User Datagram Protocol (UDP)

```
[sequence-number] deny tcp {source-ipv6-prefix/ prefix-length | any | host source-ipv6-address} [operator {port | protocol-port}] {destination-ipv6-prefix/ prefix-length | any | host destination-ipv6-address} [operator {port | protocol | port}] [dscpvalue] [routing] [authen] [destopts] [fragments] [established] [flag-name] [log] [log-input]
```

Syntax Description

<i>sequence-number</i>	(Optional) Number of the deny statement in the access list. This number determines the order of the statements in the access list. Range is 1 to 2147483646. (By default, the first statement is number 10, and the subsequent statements are incremented by 10.) Use the resequence access-list command to change the number of the first statement and increment subsequent statements of a configured access list.
<i>protocol</i>	Name or number of an Internet protocol. It can be one of the keywords ahp , esp , icmp , ipv6 , pcp , sctp , tcp , or udp , or an integer in the range from 0 to 255 representing an IPv6 protocol number.
<i>source-ipv6-prefix / prefix-length</i>	The source IPv6 network or class of networks about which to set deny conditions. This argument must be in the form documented in RFC 2373 where the address is specified in hexadecimal using 16-bit values between colons.
any	An abbreviation for the IPv6 prefix <code>::/0</code> .
<i>operator {port protocol-port}</i>	<p>(Optional) Operand that compares the source or destination ports of the specified protocol. Operands are lt (less than), gt (greater than), eq (equal), neq (not equal), and range (inclusive range).</p> <p>If the operator is positioned after the <i>source-ipv6-prefix / prefix-length</i> argument, it must match the source port.</p> <p>If the operator is positioned after the <i>destination-ipv6-prefix / prefix-length</i> argument, it must match the destination port.</p> <p>The range operator requires two port numbers. All other operators require one port number.</p> <p>The <i>port</i> argument is the decimal number of a TCP or UDP port. Range is 0 to 65535. The <i>protocol-port</i> argument is the name of a TCP or UDP port. TCP port names can be used only when filtering TCP. UDP port names can be used only when filtering UDP.</p>
<i>destination-ipv6-prefix / prefix-length</i>	Destination IPv6 network or class of networks about which to set deny conditions. This argument must be in the form documented in RFC 2373 where the address is specified in hexadecimal using 16-bit values between colons.
host <i>destination-ipv6-address</i>	Destination IPv6 host address about which to set deny conditions. This <i>destination-ipv6-address</i> argument must be in the form documented in RFC 2373 where the address is specified in hexadecimal using 16-bit values between colons.
dscp value	(Optional) Matches a differentiated services code point DSCP value against the traffic class value in the Traffic Class field of each IPv6 packet header. Range is 0 to 63.
routing	(Optional) Matches source-routed packets against the routing extension header within each IPv6 packet header.

authen	(Optional) Matches if the IPv6 authentication header is present.
destopts	(Optional) Matches if the IPv6 destination options header is present.
fragments	(Optional) Matches non-initial fragmented packets where the fragment extension header contains a nonzero fragment offset. The fragments keyword is an option only if the <i>operator</i> [<i>port-number</i>] arguments are not specified.
packet-length operator	(Optional) Packet length operator used for filtering.
packet-length value	(Optional) Packet length used to match only packets in the range of the length.
log	<p>(Optional) Causes an informational logging message about the packet that matches the entry to be sent to the console. (The level of messages logged to the console is controlled by the logging console command.)</p> <p>The message includes the access list name and sequence number, whether the packet was denied; the protocol, whether it was TCP, UDP, ICMP, or a number; and, if appropriate, the source and destination addresses and source and destination port numbers. The message is generated for the first packet that matches, and then at 5-minute intervals, including the number of packets denied in the prior 5-minute interval.</p>
log-input	(Optional) Provides the same function as the log keyword, except that the logging message also includes the input interface.
ttl	(Optional) Turns on matching against time-to-life (TTL) value.
operator	(Optional) Operand that compares the source or destination ports of the specified protocol. Operands are lt (less than), gt (greater than), eq (equal), neq (not equal), and range (inclusive range).
ttl value1 value2	<p>(Optional) TTL value used for filtering. Range is 1 to 255.</p> <p>If only <i>value1</i> is specified, the match is against this value.</p> <p>If both <i>value1</i> and <i>value2</i> are specified, the packet TTL is matched against the range of TTLs between <i>value1</i> and <i>value2</i>.</p>
icmp-off	(Optional) Turns off ICMP generation for denied packets
icmp-type	(Optional) ICMP message type for filtering ICMP packets. ICMP packets can be filtered by ICMP message type. Range is 0 to 255.
icmp-code	(Optional) ICMP message code for filtering ICMP packets. ICMP packets that are filtered by ICMP message type can also be filtered by the ICMP message code. Range is 0 to 255.
established	(Optional) For the TCP protocol only: Indicates an established connection.
match-any	(Optional) For the TCP protocol only: Filters on any combination of TCP flags.
match-all	(Optional) For the TCP protocol only: Filters on all TCP flags.

+ -	(Required) For the TCP protocol match-any , match-all : Prefix <i>flag-name</i> with + or - . Use the + <i>flag-name</i> argument to match packets with the TCP flag set. Use the - <i>flag-name</i> argument to match packets when the TCP flag is not set.
flag-name	(Required) For the TCP protocol match-any , match-all . Flag names are: ack, fin, psh, rst, syn.

Command Default

No IPv6 access list is defined.
ICMP message generation is enabled by default.

Command Modes

IPv6 access list configuration

Command History

Release	Modification
Release 3.2	This command was introduced.
Release 3.3.0	The optional keywords match-any and match-all were added for the TCP protocol. The argument <i>flag-name</i> was added for the TCP protocol. The match-any and match-all keywords and the <i>flag-name</i> argument are supported. The optional keyword icmp-off was added for the ICMP protocol.
Release 3.4.0	The optional keyword ttl and the associated arguments <i>ttl value1</i> , <i>value2</i> and <i>operator</i> , with range values, were added to the command.

Usage Guidelines

To use this command, you must be in a user group associated with a task group that includes appropriate task IDs. If the user group assignment is preventing you from using a command, contact your AAA administrator for assistance.

The **deny** (IPv6) command is similar to the **deny** (IPv4) command, except that it is IPv6-specific.

Use the **deny** (IPv6) command following the **ipv6 access-list** command to define the conditions under which a packet passes the access list.

Specifying **ipv6** for the *protocol* argument matches against the IPv6 header of the packet.

By default, the first statement in an access list is number 10, and the subsequent statements are numbered in increments of 10.

You can add permit, deny, or remark statements to an existing access list without retyping the entire list. To add a new statement anywhere other than at the end of the list, create a new statement with an appropriate entry number that falls between two existing entry numbers to indicate where it belongs.

Both the *source-ipv6-prefix/prefix-length* and *destination-ipv6-prefix/prefix-length* arguments are used for traffic filtering (the source prefix filters traffic based upon the traffic source; the destination prefix filters traffic based upon the traffic destination).

**Note**

IPv6 prefix lists, not access lists, should be used for filtering routing protocol prefixes.

Task ID

Task ID	Operations
acl	read, write

The following example shows how to configure the IPv6 access list named toCISCO and applies the access list to outbound traffic on Packet-over-SONET (POS) interface 0/2/0/2. Specifically, the first deny entry in the list keeps all packets that have a destination TCP port number greater than 5000 from exiting out of POS interface 0/2/0/2. The second deny entry in the list keeps all packets that have a source UDPo port number less than 5000 from exiting out of POS interface 0/2/0/2. The second deny entry also logs all matches to the console. The first permit entry in the list permits all ICMP packets to exit out of POS interface 0/2/0/2. The second permit entry in the list permits all other traffic to exit out of POS interface 0/2/0/2. The second permit entry is necessary because an implicit deny all condition is at the end of each IPv6 access list.

```
RP/0/0/CPU0:router(config)# ipv6 access-list toCISCO
RP/0/0/CPU0:router(config-ipv6-acl)# deny tcp any any gt 5000
RP/0/0/CPU0:router(config-ipv6-acl)# deny ipv6 any lt 5000 any log
RP/0/0/CPU0:router(config-ipv6-acl)# permit icmp any any
RP/0/0/CPU0:router(config-ipv6-acl)# permit any any
RP/0/0/CPU0:router(config)# interface POS 0/2/0/2
RP/0/0/CPU0:router(config-if)# ipv6 access-group toCISCO out
```

Related Commands

Command	Description
ipv6 access-list , on page 33	Defines an IPv6 access list and enters IPv6 access list configuration mode.
permit (IPv6) , on page 53	Sets permit conditions for an IPv6 access list.
remark (IPv6) , on page 59	Inserts a helpful remark about an IPv6 access list entry.
resequence access-list ipv6 , on page 62	Changes the starting entry number of the first statement in an existing IPv6 access list, and the number by which subsequent statements are incremented.

ipv4 access-group

To control access to an interface, use the **ipv4 access-group** command in interface configuration mode. To remove the specified access group, use the **no** form of this command.

ipv4 access-group *access-list-name* {**ingress**|**egress**} [**hardware-count**] [**interface-statistics**]

no ipv4 access-group *access-list-name* {**ingress**|**egress**} [**hardware-count**] [**interface-statistics**]

Syntax Description

access-list-name	Name of an IPv4 access list as specified by an ipv4 access-list command.
ingress	Filters on inbound packets.
egress	Filters on outbound packets.
hardware-count	(Optional) Specifies to access a group's hardware counters.
interface-statistics	(Optional) Specifies per-interface statistics in the hardware.

Command Default

The interface does not have an IPv4 access list applied to it.

Command Modes

Interface configuration

Command History

Release	Modification
Release 3.2	This command was supported .
Release 3.4.0	The argument <i>hw-count</i> was changed to <i>hardware-count</i> .
Release 3.5.0	The interface-statistics keyword was added.

Usage Guidelines

To use this command, you must be in a user group associated with a task group that includes appropriate task IDs. If the user group assignment is preventing you from using a command, contact your AAA administrator for assistance.

Use the **ipv4 access-group** command to control access to an interface. To remove the specified access group, use the **no** form of the command. Use the *access-list-name* argument to specify a particular IPv4 access list. Use the **ingress** keyword to filter on inbound packets or the **egress** keyword to filter on outbound packets. Use the *hardware-count* argument to enable hardware counters for the access group.

Permitted packets are counted only when hardware counters are enabled using the *hardware-count* argument. Denied packets are counted whether hardware counters are enabled, or not.

Filtering of MPLS packets through common ACL and interface ACL is not supported.

**Note**

For packet filtering applications using the **ipv4 access-group** command, packet counters are maintained in hardware for each direction. If an access group is used on multiple interfaces in the same direction, then packets are counted for each interface that has the *hardware-count* argument enabled.

If the access list permits the addresses, the software continues to process the packet. If the access list denies the address, the software discards the packet and returns an Internet Control Message Protocol (ICMP) host unreachable message.

If the specified access list does not exist, all packets are passed.

By default, the unique or per-interface ACL statistics are disabled.

Task ID

Task ID	Operations
acl	read, write
network	read, write

The following example shows how to apply filters on packets inbound and outbound from interface 0/2/0/2:

```
RP/0/0/CPU0:router(config)# interface 0/2/0/2
RP/0/0/CPU0:router(config-if)# ipv4 access-group p-ingress-filter ingress
RP/0/0/CPU0:router(config-if)# ipv4 access-group p-egress-filter egress
```

The following example shows how to apply per-interface statistics in the hardware:

```
RP/0/0/CPU0:router(config)# interface 0/2/0/2
RP/0/0/CPU0:router(config-if)# ipv4 access-group p-ingress-filter ingress interface-statistics
```

Related Commands

Command	Description
clear access-list ipv4 , on page 2	Resets the IPv4 access list match counters.
deny (IPv4) , on page 10	Sets the deny conditions for an ACE of an IPv4 access list.
ipv4 access-list , on page 28	Defines an IPv4 access list and enters IPv4 access list configuration mode.
permit (IPv4) , on page 39	Sets the permit conditions for an ACE of an IPv4 access list.
show access-lists ipv4 , on page 65	Displays the contents of all current IPv4 access lists.
show ipv4 interface	Displays the usability status of interfaces configured for IPv4.

ipv4 access-list

To define an IPv4 access list by name, use the **ipv4 access-list** command in global configuration mode. To remove all entries in an IPv4 access list, use the **no** form of this command.

ipv4 access-list *name*

no ipv4 access-list *name*

Syntax Description

<i>name</i>	Name of the access list. Names cannot contain a space or quotation marks.
-------------	---

Command Default

No IPv4 access list is defined.

Command Modes

Global configuration

Command History

Release	Modification
Release 3.2	This command was introduced.

Usage Guidelines

To use this command, you must be in a user group associated with a task group that includes appropriate task IDs. If the user group assignment is preventing you from using a command, contact your AAA administrator for assistance.

Use the **ipv4 access-list** command to configure an IPv4 access list. This command places the router in access list configuration mode, in which the denied or permitted access conditions must be defined with the **deny** or **permit** command.

Use the **resequence access-list ipv4** command if you want to add a **permit**, **deny**, or **remark** statement between consecutive entries in an existing IPv4 access list. Specify the first entry number (the *base*) and the increment by which to separate the entry numbers of the statements. The software renumbers the existing statements, thereby making room to add new statements with the unused entry numbers.

Use the **ipv4 access-group** command to apply the access list to an interface.

Task ID

Task ID	Operations
acl	read, write

This example shows how to define a standard access list named Internetfilter:

```
RP/0/0/CPU0:router(config)# ipv4 access-list Internetfilter
RP/0/0/CPU0:router(config-ipv4-acl)# 10 permit 192.168.34.0 0.0.0.255
RP/0/0/CPU0:router(config-ipv4-acl)# 20 permit 172.16.0.0 0.0.255.255
RP/0/0/CPU0:router(config-ipv4-acl)# 30 permit 10.0.0.0 0.255.255.255
RP/0/0/CPU0:router(config-ipv4-acl)# 39 remark Block BGP traffic from 172.16 net.
RP/0/0/CPU0:router(config-ipv4-acl)# 40 deny tcp host 172.16.0.0 eq bgp host 192.168.202.203
range 1300 1400
```

ipv4 access-list log-update rate

To specify the rate at which IPv4 access lists are logged, use the **ipv4 access-list log-update rate** command in global configuration mode. To return the update rate to the default setting, use the **no** form of this command.

ipv4 access-list log-update rate *rate-number*

no ipv4 access-list log-update rate *rate-number*

Syntax Description

rate-number	Rate at which IPv4 access hit logs are generated per second on the router. Range is 1 to 1000.
-------------	--

Command Default

Default is 1.

Command Modes

Global configuration

Command History

Release	Modification
Release 3.4.0	This command was introduced.

Usage Guidelines

To use this command, you must be in a user group associated with a task group that includes appropriate task IDs. If the user group assignment is preventing you from using a command, contact your AAA administrator for assistance.

The *rate-number* argument applies to all the IPv4 access-lists configured on the interfaces. That is, at any given time there can be between 1 and 1000 log entries for the system.

Task ID

Task ID	Operations
ipv4	read, write
acl	read, write

The following example shows how to configure a IPv4 access hit logging rate for the system:

```
RP/0/0/CPU0:router(config)# ipv4 access-list log-update rate 10
```

ipv4 access-list log-update threshold

To specify the number of updates that are logged for IPv4 access lists, use the **ipv4 access-list log-update threshold** command in global configuration mode. To return the number of logged updates to the default setting, use the **no** form of this command.

ipv4 access-list log-update threshold *update-number*

no ipv4 access-list log-update threshold *update-number*

Syntax Description

update-number	Number of updates that are logged for every IPv4 access list configured on the router. Range is 0 to 2147483647.
---------------	--

Command Default

For IPv4 access lists, 2147483647 updates are logged.

Command Modes

Global configuration

Command History

Release	Modification
Release 3.2	This command was introduced.

Usage Guidelines

To use this command, you must be in a user group associated with a task group that includes appropriate task IDs. If the user group assignment is preventing you from using a command, contact your AAA administrator for assistance.

IPv4 access list updates are logged at 5-minute intervals, following the first logged update. Configuring a lower number of updates (a number lower than the default) is useful when more frequent update logging is desired.

Task ID

Task ID	Operations
basic-services	read, write
acl	read, write

The following example shows how to configure a log threshold of ten updates for every IPv4 access list configured on the router:

```
RP/0/0/CPU0:router(config)# ipv4 access-list log-update threshold 10
```

Related Commands

Command	Description
deny (IPv4) , on page 10	Sets the deny conditions for an IPv4 access list.
ipv4 access-list , on page 28	Defines an IPv4 access list and enters IPv4 access list configuration mode.
permit (IPv4) , on page 39	Sets the permit conditions for an IPv4 access list
show access-lists ipv4 , on page 65	Displays the contents of all current IPv4 access lists.

ipv6 access-group

To control access to an interface, use the **ipv6 access-group** command in interface configuration mode. To remove the specified access group, use the **no** form of this command.

ipv6 access-group *access-list-name* {**ingress**| **egress**} [**interface-statistics**]

no ipv6 access-group *access-list-name* {**ingress**| **egress**} [**interface-statistics**]

Syntax Description

<i>access-list-name</i>	Name of an IPv6 access list as specified by an ipv6 access-list command.
ingress	Filters on inbound packets.
egress	Filters on outbound packets.
interface-statistics	(Optional) Specifies per-interface statistics in the hardware.

Command Default

The interface does not have an IPv6 access list applied to it.

Command Modes

Interface configuration

Command History

Release	Modification
Release 3.2	This command was introduced.
Release 3.3.0	The keywords { in out } were changed to { ingress egress }.
Release 3.5.0	The interface-statistics keyword was added.

Usage Guidelines

To use this command, you must be in a user group associated with a task group that includes appropriate task IDs. If the user group assignment is preventing you from using a command, contact your AAA administrator for assistance.

The **ipv6 access-group** command is similar to the **ipv4 access-group** command, except that it is IPv6-specific.

Use the **ipv6 access-group** command to control access to an interface. To remove the specified access group, use the **no** form of the command. Use the *access-list-name* to specify a particular IPv6 access list. Use the **ingress** keyword to filter on inbound packets or the **egress** keyword to filter on outbound packets.

Filtering of MPLS packets through common ACL and interface ACL is not supported.

**Note**

For packet filtering applications using the **ipv6 access-group** command, packet counters are maintained in hardware for each direction. If an access group is used on multiple interfaces in the same direction, then packets are counted for each interface.

If the access list permits the addresses, the software continues to process the packet. If the access list denies the address, the software discards the packet and returns a rate-limited Internet Control Message Protocol (ICMP) host unreachable message.

If the specified access list does not exist, all packets are passed.

By default, the unique or per-interface ACL statistics are disabled.

Task ID

Task ID	Operations
acl	read, write
ipv6	read, write

This example shows how to apply filters on packets inbound and outbound from GigabitEthernet interface 0/2/0/2:

```
RP/0/0/CPU0:router(config)# interface gigabitethernet 0/2/0/2
RP/0/0/CPU0:router(config-if)# ipv6 access-group p-in-filter ingress
RP/0/0/CPU0:router(config-if)# ipv6 access-group p-out-filter egress
```

This example shows how to apply filters on packets inbound and outbound from GigabitEthernet interface 0/2/0/2:

```
RP/0/0/CPU0:router(config)# interface gigabitethernet 0/2/0/2
```



```
RP/0/0/CPU0:router(config-if)# ipv6 access-group p-in-filter ingress
RP/0/0/CPU0:router(config-if)# ipv6 access-group p-out-filter egress
```

This example shows how to apply per-interface statistics in the hardware:

```
RP/0/0/CPU0:router(config)# interface gigabitethernet 0/2/0/2
RP/0/0/CPU0:router(config-if)# ipv6 access-group p-in-filter ingress interface-statistics
```

ipv6 access-list

To define an IPv6 access list and to place the router in IPv6 access list configuration mode, use the **ipv6 access-list** command in interface configuration mode. To remove the access list, use the **no** form of this command.

ipv6 access-list *name*

no ipv6 access-list *name*

Syntax Description

<i>name</i>	Name of the IPv6 access list. Names cannot contain a space or quotation mark, or begin with a numeric.
-------------	--

Command Default

No IPv6 access list is defined.

Command Modes

Interface configuration

Command History

Release	Modification
Release 3.2	This command was introduced.

Usage Guidelines

To use this command, you must be in a user group associated with a task group that includes appropriate task IDs. If the user group assignment is preventing you from using a command, contact your AAA administrator for assistance.

The **ipv6 access-list** command is similar to the **ipv4 access-list** command, except that it is IPv6-specific.

The IPv6 access lists are used for traffic filtering based on source and destination addresses, IPv6 option headers, and optional, upper-layer protocol type information for finer granularity of control. IPv6 access lists are defined by using the **ipv6 access-list** command in global configuration mode and their permit and deny conditions are set by using the **deny** and **permit** commands in IPv6 access list configuration mode. Configuring the **ipv6 access-list** command places the router in IPv6 access list configuration mode—the router prompt changes to router (config-ipv6-acl)#. From IPv6 access list configuration mode, permit and deny conditions can be set for the defined IPv6 access list.

See the “Examples” section for an example of a translated IPv6 access control list (ACL) configuration.



Note Every IPv6 access list has an implicit **deny ipv6 any any** statement as its last match condition. An IPv6 access list must contain at least one entry for the implicit **deny ipv6 any any** statement to take effect.



Note IPv6 prefix lists, not access lists, should be used for filtering routing protocol prefixes.

Use the **ipv6 access-group** interface configuration command with the *access-list-name* argument to apply an IPv6 access list to an IPv6 interface.



Note An IPv6 access list applied to an interface with the **ipv6 access-group** command filters traffic that is forwarded, not originated, by the router.



Note Every IPv6 ACL has implicit **permit icmp any any nd-na**, **permit icmp any any nd-ns**, and **deny ipv6 any any** statements as its last match conditions. (The former two match conditions allow for ICMPv6 neighbor discovery.) An IPv6 ACL must contain at least one entry for the implicit **deny ipv6 any any** statement to take effect. **permit icmp any any nd-na permit icmp any any nd-ns deny ipv6 any any deny ipv6 any any**.

The IPv6 neighbor discovery process makes use of the IPv6 network layer service; therefore, by default, IPv6 ACLs implicitly allow IPv6 neighbor discovery packets to be sent and received on an interface. In IPv4, the Address Resolution Protocol (ARP), which is equivalent to the IPv6 neighbor discovery process, makes use of a separate data link layer protocol; therefore, by default, IPv4 ACLs implicitly allow ARP packets to be sent and received on an interface.

Task ID

Task ID	Operations
acl	read, write
ipv6	read, write

This example shows how to configure the IPv6 access list named list2 and applies the ACL to outbound traffic on interface GigabitEthernet 0/2/0/2. Specifically, the first ACL entry keeps all packets from the network fec0:0:0:2::/64 (packets that have the site-local prefix fec0:0:0:2 as the first 64 bits of their source IPv6 address) from exiting out of interface GigabitEthernet 0/2/0/2. The second entry in the ACL permits all other traffic to exit out of interface GigabitEthernet 0/2/0/2. The second entry is necessary because an implicit deny all condition is at the end of each IPv6 ACL.

```
RP/0/0/CPU0:router(config)# ipv6 access-list list2
RP/0/0/CPU0:router(config-ipv6-acl)# 10 deny fec0:0:0:2::/64 any
RP/0/0/CPU0:router(config-ipv6-acl)# 20 permit any any

RP/0/0/CPU0:router# show ipv6 access-lists list2

ipv6 access-list list2
 10 deny ipv6 fec0:0:0:2::/64 any
 20 permit ipv6 any any
```

```
RP/0/0/CPU0:router(config)# interface gigabitethernet 0/2/0/2
RP/0/0/CPU0:router(config-if)# ipv6 access-group list2 egress
```



Note IPv6 is automatically configured as the protocol type in **permit any any** and **deny any any** statements that are translated from global configuration mode to IPv6 access list configuration mode.



Note An IPv6 router does not forward to another network an IPv6 packet that has a link-local address as either its source or destination address (and the source interface for the packet is different from the destination interface for the packet).

ipv6 access-list log-update rate

To specify the rate at which IPv6 access lists are logged, use the **ipv6 access-list log-update rate** command in global configuration mode. To return the update rate to the default setting, use the **no** form of this command.

ipv6 access-list log-update rate *rate-number*

no ipv6 access-list log-update rate *rate-number*

Syntax Description

rate-number	Rate at which IPv6 access hit logs are generated per second on the router. Range is 1 to 1000.
-------------	--

Command Default

Default is 1.

Command Modes

Global configuration

Command History

Release	Modification
Release 3.4.0	This command was introduced.

Usage Guidelines

To use this command, you must be in a user group associated with a task group that includes appropriate task IDs. If the user group assignment is preventing you from using a command, contact your AAA administrator for assistance.

The *rate-number* argument applies to all the IPv6 access-lists configured on the interfaces. That is, at any given time there can be between 1 and 1000 log entries for the system.

Task ID	Task ID	Operations
	ipv6	read, write
	acl	read, write

The following example shows how to configure a IPv6 access hit logging rate for the system:

```
RP/0/0/CPU0:router(config)# ipv6 access-list log-update rate 10
```

ipv6 access-list log-update threshold

To specify the number of updates that are logged for IPv6 access lists (ACLs), use the **ipv6 access-list log-update threshold** command in global configuration mode. To return the number of logged updates to the default setting, use the **no** form of this command.

ipv6 access-list log-update threshold *update-number*

no ipv6 access-list log-update threshold *update-number*

Syntax Description	update-number	Number of updates that are logged for every IPv6 access list configured on the router. Range is 0 to 2147483647.

Command Default For IPv6 access lists, 350000 updates are logged.

Command Modes Global configuration

Command History	Release	Modification
	Release 3.2	This command was supported.

Usage Guidelines To use this command, you must be in a user group associated with a task group that includes appropriate task IDs. If the user group assignment is preventing you from using a command, contact your AAA administrator for assistance.

The **ipv6 access-list log-update threshold** command is similar to the **ipv4 access-list log-update threshold** command, except that it is IPv6-specific.

IPv6 access list updates are logged at 5-minute intervals, following the first logged update. Configuring a lower number of updates (a number lower than the default) is useful when more frequent update logging is desired.

Task ID	Task ID	Operations
	acl	read, write
	ipv6	read, write

The following example shows how to configure a log threshold of ten updates for every IPv6 access list configured on the router:

```
RP/0/0/CPU0:router (config) # ipv6 access-list log-update threshold 10
```

ipv6 access-list maximum ace threshold

To set the maximum number of access control entries (ACEs) for IPv6 access lists, use the **ipv6 access-list maximum ace threshold** command in global configuration mode. To reset the ACE limit for IPv6 access lists, use the **no** form of this command.

ipv6 access-list maximum ace threshold *ace-number*

no ipv6 access-list maximum ace threshold *ace-number*

Syntax Description	ace-number	Maximum number of configurable ACEs allowed. Range is 50000 to 350000.
--------------------	------------	--

Command Default 50,000 ACEs are allowed for IPv6 access lists.

Command Modes Global configuration

Command History	Release	Modification
	Release 3.2	This command was introduced.
	Release 3.3.0	Range was 50000 to 100000 changed to 50000 to 350000.

Usage Guidelines To use this command, you must be in a user group associated with a task group that includes appropriate task IDs. If the user group assignment is preventing you from using a command, contact your AAA administrator for assistance.

Use the **ipv6 access-list maximum ace threshold** command to set the maximum number of configurable ACEs for IPv6 access lists. Out of resource (OOR) limits the number of ACEs that can be configured in the system. When the maximum number of configurable ACEs is reached, configuration of new ACEs is rejected.

Task ID

Task ID	Operations
acl	read, write
ipv6	read, write

The following example shows how to set the maximum number of ACEs for IPv6 access lists to 75000:

```
RP/0/0/CPU0:router(config)# ipv6 access-list maximum ace threshold 75000
```

Related Commands

Command	Description
show access-lists ipv6, on page 71	Displays the contents of all current IPv6 access lists.

ipv6 access-list maximum acl threshold

To set the maximum number of configurable IPv4 access control lists (ACLs), use the **ipv6 access-list maximum acl threshold** command in global configuration mode. To reset the IPv6 ACL limit, use the **no** form of this command.

ipv6 access-list maximum acl threshold *acl-number*

no ipv6 access-list maximum ace threshold *acl-number*

Syntax Description

acl-number	Maximum number of configurable ACLs allowed. Range is 1000 to 16000.
------------	--

Command Default

1000 IPv6 ACLs can be configured.

Command Modes

Global configuration

Command History

Release	Modification
Release 3.2	This command was introduced.
Release 3.3.0	Maximum range was changed from 2000 to 16000.

Usage Guidelines

To use this command, you must be in a user group associated with a task group that includes appropriate task IDs. If the user group assignment is preventing you from using a command, contact your AAA administrator for assistance.

Use the **ipv6 access-list maximum acl threshold** command to set the maximum number of configurable IPv6 ACLs. Out of resource (OOR) limits the number of ACLs that can be configured in the system. When the limit is reached, configuration of new ACLs is rejected.

Task ID

Task ID	Operations
acl	read, write
ipv6	read, write

The following example shows how to set the maximum number of configurable IPv6 ACLs to 1500:

```
RP/0/0/CPU0:router(config)# ipv6 access-list maximum acl threshold 1500
```

Related Commands

Command	Description
show access-lists ipv6, on page 71	Displays the contents of all current IPv6 access lists.

permit (IPv4)

To set conditions for an IPv4 access list, use the **permit** command in access list configuration mode. There are two versions of the **permit** command: **permit** (source), and **permit** (protocol). To remove a condition from an access list, use the **no** form of this command.

```
[ sequence-number ] permit source [ source-wildcard ] [log] log-input]
```

```
[ sequence-number ] permit protocol source source-wildcard destination destination-wildcard [capture]
[precedence precedence] [default nexthop [ ipv4-address1 ] [ ipv4-address2 ] [ ipv4-address3 ]] [dscp dscp]
[fragments] [log] log-input [nexthop [track track-name] [ ipv4-address1 ] [ ipv4-address2 ] [ ipv4-address3 ]]
[ttl ttl value [value1 ... value2]]
```

```
no sequence-number
```

Internet Control Message Protocol (ICMP)

```
[ sequence-number ] permit icmp source source-wildcard destination destination-wildcard [ icmp-type ]
[ icmp-code ] [precedence precedence] [dscp dscp] [fragments] [log] log-input [icmp-off]
```

Internet Group Management Protocol (IGMP)

[*sequence-number*] **permit igmp** *source source-wildcard destination destination-wildcard* [*igmp-type*]
 [**precedence** *precedence*] [**dscp** *value*] [**fragments**] [**log** | **log-input**]

User Datagram Protocol (UDP)

[*sequence-number*] **permit udp** *source source-wildcard* [*operator* { *port* | *protocol-port* }] *destination*
destination-wildcard [*operator* { *port* | *protocol-port* }] [**precedence** *precedence*] [**dscp** *dscp*] [**fragments**]
 [**log** | **log-input**]

Syntax Description

default	(Optional) Specifies the default next hop for this entry. If the default keyword is configured, ACL-based forwarding action is taken only if the results of the PLU lookup for the destination of the packets determine a default route; that is, no specified route is determined to the destination of the packet.
capture	Captures matching traffic. When the acl command is configured on the source mirroring port, if the ACL configuration command does not use the capture keyword, no traffic gets mirrored. If the ACL configuration uses the capture keyword, but the acl command is not configured on the source port, then the whole port traffic is mirrored and the capture action does not have any affect.

ipv4-address1 ipv4-address2 ipv4-address3

(Optional) Uses one to three next-hop addresses. The IP address types are defined as follows:

- **Default IP addresses**—Specifies the next-hop router in the path toward the destination in which the packets must be forwarded, if there is no explicit route for the destination address of the packet in the routing table. The first IP address that is associated with a connected interface that is currently up is used to route the packets.
 - **Specified IP addresses**—Specifies the next-hop router in the path toward the destination in which the packets must be forwarded. The first IP address that is associated with a connected interface that is currently up is used to route the packets.
-

dscp *dscp*

(Optional) Differentiated services code point (DSCP) provides quality of service control. The values for *dscp* are as follows:

- 0–63—Differentiated services codepoint value
- af11—Match packets with AF11 dscp (001010)
- af12—Match packets with AF12 dscp (001100)
- af13—Match packets with AF13 dscp (001110)
- af21—Match packets with AF21 dscp (010010)
- af22—Match packets with AF22 dscp (010100)
- af23—Match packets with AF23 dscp (010110)
- af31—Match packets with AF31 dscp (011010)
- af32—Match packets with AF32 dscp (011100)
- af33—Match packets with AF33 dscp (011110)
- af41—Match packets with AF41 dscp (100010)
- af42—Match packets with AF42 dscp (100100)
- af43—Match packets with AF43 dscp (100110)
- cs1—Match packets with CS1 (precedence 1) dscp (001000)
- cs2—Match packets with CS2 (precedence 2) dscp (010000)
- cs3—Match packets with CS3 (precedence 3) dscp (011000)
- cs4—Match packets with CS4 (precedence 4) dscp (100000)
- cs5—Match packets with CS5 (precedence 5) dscp (101000)

	<ul style="list-style-type: none"> • cs6—Match packets with CS6 (precedence 6) dscp (110000) • cs7—Match packets with CS7 (precedence 7) dscp (111000) • default—Default DSCP (000000) • ef—Match packets with EF dscp (101110)
fragments	(Optional) Causes the software to examine noninitial fragments of IPv4 packets when applying this access list entry. When this keyword is specified, fragments are subject to the access list entry.
log	<p>(Optional) Causes an informational logging message about the packet that matches the entry to be sent to the console. (The level of messages logged to the console is controlled by the logging console command.)</p> <p>The message includes the access list number, whether the packet was permitted or denied; the protocol, whether it was TCP, UDP, ICMP, or a number; and, if appropriate, the source and destination addresses and source and destination port numbers. The message is generated for the first packet that matches a flow, and then at 5-minute intervals, including the number of packets permitted or denied in the prior 5-minute interval.</p>
log-input	(Optional) Provides the same function as the log keyword, except that the logging message also includes the input interface.
nexthop1, nexthop2, nexthop3	(Optional) Forwards the specified next hop for this entry.
track <i>track-name</i>	Specifies the TRACK Name for this nexthop.

ttl	(Optional) Turns on matching against time-to-life (TTL) value.
<i>ttl value [value1 ... value2]</i>	(Optional) TTL value used for filtering. Range is 1 to 255. If only <i>value</i> is specified, the match is against this value. If both <i>value1</i> and <i>value2</i> are specified, the packet TTL is matched against the range of TTLs between <i>value1</i> and <i>value2</i> .
icmp-off	(Optional) Turns off ICMP generation for denied packets
icmp-type	(Optional) ICMP message type for filtering ICMP packets. Range is from 0 to 255.
icmp-code	(Optional) ICMP message code for filtering ICMP packets. Range is from 0 to 255.
igmp-type	(Optional) IGMP message type (0 to 15) or message name for filtering IGMP packets, as follows: <ul style="list-style-type: none">• dvmrp• host-query• host-report• mtrace• mtrace-response• pim• precedence• trace• v2-leave• v2-report• v3-report

operator	<p>(Optional) Operator is used to compare source or destination ports. Possible operands are lt (less than), gt (greater than), eq (equal), neq (not equal), and range (inclusive range).</p> <p>If the operator is positioned after the <i>source</i> and <i>source-wildcard</i> values, it must match the source port.</p> <p>If the operator is positioned after the <i>destination</i> and <i>destination-wildcard</i> values, it must match the destination port.</p> <p>If the operator is positioned after the ttl keyword, it matches the TTL value.</p> <p>The range operator requires two port numbers. All other operators require one port number.</p>
port	<p>Decimal number a TCP or UDP port. Range is 0 to 65535.</p> <p>TCP ports can be used only when filtering TCP. UDP ports can be used only when filtering UDP.</p>
protocol-port	<p>Name of a TCP or UDP port. TCP and UDP port names are listed in the “Usage Guidelines” section.</p> <p>TCP port names can be used only when filtering TCP. UDP port names can be used only when filtering UDP.</p>
established	<p>(Optional) For the TCP protocol only: Indicates an established connection.</p>
match-any	<p>(Optional) For the TCP protocol only: Filters on any combination of TCP flags.</p>
match-all	<p>(Optional) For the TCP protocol only: Filters on all TCP flags.</p>

+ -	(Required) For the TCP protocol match-any , match-all : Prefix <i>flag-name</i> with + or - . Use the + <i>flag-name</i> argument to match packets with the TCP flag set. Use the - <i>flag-name</i> argument to match packets when the TCP flag is not set.
flag-name	(Optional) For the TCP protocol match-any , match-all . Flag names are: ack , fin , psh , rst , syn .
counter	(Optional) Enables accessing ACL counters using SNMP query. The counter <i>counter-name</i> keyword is available on Cisco ASR 9000 Enhanced Ethernet Line Cards only.
<i>counter-name</i>	Defines an ACL counter name.

Command Default

There is no specific condition under which a packet is denied passing the IPv4 access list. ICMP message generation is enabled by default.

Command Modes

IPv4 access list configuration

Command History

Release	Modification
Release 3.0	This command was introduced.
Release 3.3.0	The optional keywords match-any and match-all were added for the TCP protocol. The argument <i>flag-name</i> was added for the TCP protocol. The match-any and match-all keywords and the <i>flag-name</i> argument are supported. The optional keyword icmp-off was added for the ICMP protocol.
Release 3.4.0	The optional keyword ttl and the associated arguments <i>ttl value1</i> , <i>value2</i> , and <i>operator</i> ; with range values, were added to the command.
Release 3.4.1	Both the default nexthop and nexthop keywords were added to support ACL-based forwarding.

Usage Guidelines

To use this command, you must be in a user group associated with a task group that includes appropriate task IDs. If the user group assignment is preventing you from using a command, contact your AAA administrator for assistance.

Use the **permit** command following the **ipv4 access-list** command to specify conditions under which a packet can pass the access list.

By default, the first statement in an access list is number 10, and the subsequent statements are incremented by 10.

You can add **permit**, **deny**, or **remark** statements to an existing access list without retyping the entire list. To add a new statement anywhere other than at the end of the list, create a new statement with an appropriate entry number that falls between two existing entry numbers to indicate where it belongs.

If you want to add a statement between two consecutively numbered statements (for example, between lines 10 and 11), first use the **resequence access-list** command to renumber the first statement and increment the entry number of each subsequent statement. The *increment* argument causes new, unused line numbers between statements. Then add a new statement with the *entry-number* specifying where it belongs in the access list.

The following is a list of precedence names:

- critical
- flash
- flash-override
- immediate
- internet
- network
- priority
- routine

The following is a list of ICMP message type names:

- administratively-prohibited
- alternate-address
- conversion-error
- dod-host-prohibited
- dod-net-prohibited
- echo
- echo-reply
- general-parameter-problem
- host-isolated
- host-precedence-unreachable
- host-redirect

- host-tos-redirect
- host-tos-unreachable
- host-unknown
- host-unreachable
- information-reply
- information-request
- mask-reply
- mask-request
- mobile-redirect
- net-redirect
- net-tos-redirect
- net-tos-unreachable
- net-unreachable
- network-unknown
- no-room-for-option
- option-missing
- packet-too-big
- parameter-problem
- port-unreachable
- precedence-unreachable
- protocol-unreachable
- reassembly-timeout
- redirect
- router-advertisement
- router-solicitation
- source-quench
- source-route-failed
- time-exceeded
- timestamp-reply
- timestamp-request
- traceroute
- ttl-exceeded
- unreachable

The following is a list of TCP port names that can be used instead of port numbers. Refer to the current *Assigned Numbers* RFC to find a reference to these protocols. You can find port numbers corresponding to these protocols by typing a ? in the place of a port number.

- bgp
- chargen
- cmd
- daytime
- discard
- domain
- echo
- exec
- finger
- ftp
- ftp-data
- gopher
- hostname
- ident
- irc
- klogin
- kshell
- login
- lpd
- nntp
- pim-auto-rp
- pop2
- pop3
- smtp
- sunrpc
- tacacs
- talk
- telnet
- time
- uucp
- whois

- www

The following UDP port names can be used instead of port numbers. Refer to the current *Assigned Numbers* RFC to find a reference to these protocols. You can find port numbers corresponding to these protocols by typing a ? in the place of a port number.

- biff
- bootpc
- bootps
- discard
- dnsix
- domain
- echo
- isakmp
- mobile-ip
- nameserver
- netbios-dgm
- netbios-ns
- netbios-ss
- ntp
- pim-auto-rp
- rip
- snmp
- snmptrap
- sunrpc
- syslog
- tacacs
- talk
- tftp
- time
- who
- xdmcp

Use the following flags in conjunction with the **match-any** and **match-all** keywords and the + and - signs to select the flags to display:

- ack
- fin

- psh
- rst
- syn

For example, **match-all** *+ack +syn* displays TCP packets with both the ack *and* syn flags set, or **match-any** *+ack - syn* displays the TCP packets with the ack set *or* the syn not set.

Task ID

Task ID	Operations
ipv4	read, write
acl	read, write

The following example shows how to set a permit condition for an access list named Internetfilter:

```
RP/0/0/CPU0:router(config)# ipv4 access-list Internetfilter
RP/0/0/CPU0:router(config-ipv4-acl)# 10 permit 192.168.34.0 0.0.0.255
RP/0/0/CPU0:router(config-ipv4-acl)# 20 permit 172.16.0.0 0.0.255.255
RP/0/0/CPU0:router(config-ipv4-acl)# 25 permit tcp host 172.16.0.0 eq bgp host 192.168.202.203
range 1300 1400
RP/0/0/CPU0:router(config-ipv4-acl)# deny 10.0.0.0 0.255.255.255
```

Related Commands

Command	Description
deny (IPv4) , on page 10	Sets the conditions for an IPv4 access list.
ipv4 access-group , on page 25	Filters incoming or outgoing IPv4 traffic on an interface.
ipv4 access-list , on page 28	Defines an IPv4 access list and enters IPv4 access list configuration mode.
remark (IPv4) , on page 57	Inserts a helpful remark about an IPv4 access list entry.
resequence access-list ipv4 , on page 61	Changes the starting entry number of the first statement in an existing IPv4 access list, and the number by which subsequent statements are incremented.
show access-lists ipv4 , on page 65	Displays the contents of all current IPv4 access lists.

permit (IPv6)

To set permit conditions for an IPv6 access list, use the **permit** command in IPv6 access list configuration mode. To remove the permit conditions, use the **no** form of this command.

```
[sequence-number] permit protocol {source-ipv6-prefix/ prefix-length | any | host
source-ipv6-address} [operator {port | protocol-port} capture ] [dscp value] [routing] [authen] [destopts]
[ fragments] [packet-length operator packet-length-value ] [ log | log-input] [ttl operator ttl value ]
no sequence-number
```

Internet Control Message Protocol (ICMP)

```
[ sequence-number] permit icmp {source-ipv6-prefix/ prefix-length | any | host
source-ipv6-address} {destination-ipv6-prefix/ prefix-length | any | host destination-ipv6-address} [icmp-type]
[ icmp-code][dscp value] [ routing] [authen] [destopts] [ fragments] [ log] [log-input] [icmp-off]
```

Transmission Control Protocol (TCP)

```
[sequence-number] permit tcp {source-ipv6-prefix/ prefix-length | any | host
source-ipv6-address} [operator {port | protocol-port}] {destination-ipv6-prefix/ prefix-length | any | host
destination-ipv6-address} [operator {port | protocol | port}] [dscp value] [routing] [authen] [destopts]
[fragments] [established] {match-any | match-all | + | -} [flag-name] [log] [log-input]
```

User Datagram Protocol (UDP)

```
[sequence-number] permit tcp {source-ipv6-prefix/ prefix-length | any | host
source-ipv6-address} [operator {port | protocol-port}] {destination-ipv6-prefix/ prefix-length | any | host
destination-ipv6-address} [operator {port | protocol | port}] [dscp value] [routing] [authen] [destopts]
[fragments] [established] [flag-name] [log] [log-input]
```

Syntax Description

sequence-number	(Optional) Number of the permit statement in the access list. This number determines the order of the statements in the access list. Range is 1 to 2147483646. (By default, the first statement is number 10, and the subsequent statements are incremented by 10.) Use the resequence access-list command to change the number of the first statement and increment subsequent statements of a configured access list.
protocol	Name or number of an Internet protocol. It can be one of the keywords ahp , esp , icmp , ipv6 , pcp , sctp , tcp , or udp , or an integer in the range from 0 to 255 representing an IPv6 protocol number.
source-ipv6-prefix / prefix-length	Source IPv6 network or class of networks about which to set permit conditions. This argument must be in the form documented in RFC 2373 where the address is specified in hexadecimal using 16-bit values between colons.
any	An abbreviation for the IPv6 prefix ::/0.

host <i>source-ipv6-address</i>	Source IPv6 host address about which to set permit conditions. This <i>source-ipv6-address</i> argument must be in the form documented in RFC 2373 where the address is specified in hexadecimal using 16-bit values between colons.
<i>operator {port protocol-port}</i>	(Optional) Operand that compares the source or destination ports of the specified protocol. Operands are lt (less than), gt (greater than), eq (equal), neq (not equal), and range (inclusive range). If the operator is positioned after the <i>source-ipv6-prefix / prefix-length</i> argument, it must match the source port. If the operator is positioned after the <i>destination-ipv6-prefix / prefix-length</i> argument, it must match the destination port. The range operator requires two port numbers. All other operators require one port number. The <i>port</i> argument is the decimal number of a TCP or UDP port. A port number is a number from 0 to 65535. The <i>protocol-port</i> argument is the name of a TCP or UDP port. TCP port names can be used only when filtering TCP. UDP port names can be used only when filtering UDP.
<i>destination-ipv6-prefix / prefix-length</i>	Destination IPv6 network or class of networks about which to set permit conditions. This argument must be in the form documented in RFC 2373 where the address is specified in hexadecimal using 16-bit values between colons.
host <i>destination-ipv6-address</i>	Specifies the destination IPv6 host address about which to set permit conditions. This <i>destination-ipv6-address</i> argument must be in the form documented in RFC 2373 where the address is specified in hexadecimal using 16-bit values between colons.
dscp value	(Optional) Matches a differentiated services code point (DSCP) value against the traffic class value in the Traffic Class field of each IPv6 packet header. Range is 0 to 63.
routing	(Optional) Matches source-routed packets against the routing extension header within each IPv6 packet header.
authen	(Optional) Matches if the IPv6 authentication header is present.
destopts	(Optional) Matches if the IPv6 destination options header is present.
fragments	(Optional) Matches non-initial fragmented packets where the fragment extension header contains a nonzero fragment offset. The fragments keyword is an option only if the <i>operator [port-number]</i> arguments are not specified.
packet-length operator	(Optional) Packet length operator used for filtering.
packet-length value	(Optional) Packet length used to match only packets in the range of the length.

log	(Optional) Causes an informational logging message about the packet that matches the entry to be sent to the console. (The level of messages logged to the console is controlled by the logging console command.) The message includes the access list name and sequence number, whether the packet was permitted; the protocol, whether it was TCP, UDP, ICMP, or a number; and, if appropriate, the source and destination addresses and source and destination port numbers. The message is generated for the first packet that matches, and then at 5-minute intervals, including the number of packets permitted in the prior 5-minute interval.
log-input	(Optional) Provides the same function as the log keyword, except that the logging message also includes the input interface.
ttl	(Optional) Turns on matching against time-to-life (TTL) value.
operator	(Optional) Operand that compares the source or destination ports of the specified protocol. Operands are lt (less than), gt (greater than), eq (equal), neq (not equal), and range (inclusive range).
ttl value1 value2	(Optional) TTL value used for filtering. Range is 1 to 255. If only <i>value1</i> is specified, the match is against this value. If both <i>value1</i> and <i>value2</i> are specified, the packet TTL is matched against the range of TTLs between <i>value1</i> and <i>value2</i> .
icmp-off	(Optional) Turns off ICMP generation for denied packets
icmp-type	(Optional) ICMP message type for filtering ICMP packets. Range is from 0 to 255.
icmp-code	(Optional) ICMP message code for filtering ICMP packets. Range is from 0 to 255.
established	(Optional) For the TCP protocol only: Indicates an established connection.
match-any	(Optional) For the TCP protocol only: Filters on any combination of TCP flags.
match-all	(Optional) For the TCP protocol only: Filters on all TCP flags.
+ -	(Required) For the TCP protocol match-any , match-all : Prefix <i>flag-name</i> with + or -. Use the + <i>flag-name</i> argument to match packets with the TCP flag set. Use the - <i>flag-name</i> argument to match packets when the TCP flag is not set.
flag-name	(Required) For the TCP protocol match-any , match-all . Flag names are: ack, fin, psh, rst, syn.

Command Default

No IPv6 access list is defined.

ICMP message generation is enabled by default.

Command Modes

IPv6 access list configuration

Command History

Release	Modification
Release 3.0	This command was introduced.
Release 3.3.0	The optional keywords match-any and match-all were added for the TCP protocol. The argument <i>flag-name</i> was added for the TCP protocol. The match-any and match-all keywords and the <i>flag-name</i> argument are supported. The optional keyword icmp-off was added for the ICMP protocol.
Release 3.4.0	The optional keyword ttl and the associated arguments <i>ttl value1</i> , <i>value2</i> , and <i>operator</i> , with range values, were added to the command.

Usage Guidelines

To use this command, you must be in a user group associated with a task group that includes appropriate task IDs. If the user group assignment is preventing you from using a command, contact your AAA administrator for assistance.

The **permit** (IPv6) command is similar to the **permit** (IPv4) command, except that it is IPv6-specific.

Use the **permit** (IPv6) command following the **ipv6 access-list** command to define the conditions under which a packet passes the access list.

Specifying **ipv6** for the *protocol* argument matches against the IPv6 header of the packet.

By default, the first statement in an access list is number 10, and the subsequent statements are numbered in increments of 10.

You can add **permit**, **deny**, or **remark** statements to an existing access list without retyping the entire list. To add a new statement anywhere other than the end of the list, create a new statement with an appropriate entry number that falls between two existing entry numbers to indicate where it belongs.

Both the *source-ipv6-prefix/prefix-length* and *destination-ipv6-prefix/prefix-length* arguments are used for traffic filtering (the source prefix filters traffic based upon the traffic source; the destination prefix filters traffic based upon the traffic destination).

**Note**

IPv6 prefix lists, and not access lists, should be used for filtering routing protocol prefixes.

The **fragments** keyword is an option available only if the *operator* [*port* | *protocol-port*] arguments are not specified.

Task ID

Task ID	Operations
acl	read, write

This example shows how to configure the IPv6 access list named toCISCO and applies the access list to outbound traffic on interface 0/2/0/2. Specifically, the first deny entry in the list keeps all packets that have a destination TCP port number greater than 5000 from exiting out of interface 0/2/0/2. The second deny entry in the list keeps all packets that have a source UDP port number less than 5000 from exiting out of interface 0/2/0/2. The second deny entry also logs all matches to the console. The first permit entry in the list permits all ICMP packets to exit out of interface 0/2/0/2. The second permit entry in the list permits all other traffic to exit out of interface 0/2/0/2. The second permit entry is necessary because an implicit deny all condition is at the end of each IPv6 access list.

```
RP/0/0/CPU0:router(config)# ipv6 access-list toCISCO
RP/0/0/CPU0:router(config-ipv6-acl)# deny tcp any any gt 5000
RP/0/0/CPU0:router(config-ipv6-acl)# deny ipv6 any lt 5000 any log
RP/0/0/CPU0:router(config-ipv6-acl)# permit icmp any any
RP/0/0/CPU0:router(config-ipv6-acl)# permit any any
RP/0/0/CPU0:router(config)# interface 0/2/0/2
RP/0/0/CPU0:router(config-if)# ipv6 access-group toCISCO out
```

Related Commands

Command	Description
deny (IPv6) , on page 21	Sets deny conditions for an IPv6 access list.
ipv6 access-list , on page 33	Defines an IPv6 access list and enters IPv6 access list configuration mode.
remark (IPv6) , on page 59	Inserts a helpful remark about an IPv6 access list entry.
resequence access-list ipv6 , on page 62	Changes the starting entry number of the first statement in an existing IPv6 access list, and the number by which subsequent statements are incremented.

remark (IPv4)

To write a helpful comment (remark) for an entry in an IPv4 access list, use the **remark** command in IPv4 access list configuration mode. To remove the remark, use the **no** form of this command.

[*sequence-number*] **remark** *remark*

no *sequence-number*

Syntax Description

sequence-number	(Optional) Number of the remark statement in the access list. This number determines the order of the statements in the access list. Range is 1 to 2147483646. (By default, the first statement is number 10; subsequent statements are incremented by 10.)
-----------------	--

remark Comment that describes the entry in the access list, up to 255 characters long.

Command Default The IPv4 access list entries have no remarks.

Command Modes IPv4 access list configuration

Command History	Release	Modification
	Release 3.2	This command was introduced.

Usage Guidelines To use this command, you must be in a user group associated with a task group that includes appropriate task IDs. If the user group assignment is preventing you from using a command, contact your AAA administrator for assistance.

Use the **remark** command to write a helpful comment for an entry in an IPv4 access list. To remove the remark, use the **no** form of this command.

The remark can be up to 255 characters; anything longer is truncated.

If you know the sequence number of the remark you want to delete, you can remove it by entering the **no sequence-number** command.

Use the **resequence access-list ipv4** command if you want to add statements to an existing access list and the sequence numbers of consecutive entries do not permit additional statements.

Task ID	Task ID	Operations
	ipv4	read, write
	acl	read, write

In the following example, the user1 subnet is not allowed to use outbound Telnet:

```
RP/0/0/CPU0:router(config)# ipv4 access-list telnetting
RP/0/0/CPU0:router(config-ipv4-acl)# 10 remark Do not allow user1 to telnet out
RP/0/0/CPU0:router(config-ipv4-acl)# 20 deny tcp host 172.16.2.88 255.255.0.0 any eq telnet
RP/0/0/CPU0:router(config-ipv4-acl)# 30 permit icmp any any
RP/0/0/CPU0:router# show ipv4 access-list telnetting

ipv4 access-list telnetting
  0 remark Do not allow user1 to telnet out
  20 deny tcp 172.16.2.88 255.255.0.0 any eq telnet out
  30 permit icmp any any
```

Related Commands

Command	Description
deny (IPv4) , on page 10	Sets the deny conditions for an IPv4 access list.
ipv4 access-list , on page 28	Defines an IPv4 access list and enters IPv4 access list configuration mode.
permit (IPv4) , on page 39	Sets the permit conditions for an IPv4 access list
resequence access-list ipv4 , on page 61	Changes the starting entry number of the first statement in an existing IPv4 access list, and the number by which subsequent statements are incremented.
show access-lists ipv4 , on page 65	Displays the contents of all current IPv4 access lists.

remark (IPv6)

To write a helpful comment (remark) for an entry in an IPv6 access list, use the **remark** command in IPv6 access list configuration mode. To remove the remark, use the **no** form of this command.

```
[ sequence-number ] remark remark
no sequence-number
```

Syntax Description

sequence-number	(Optional) Number of the remark statement in the access list. This number determines the order of the statements in the access list. Range is 1 to 2147483646. (By default, the first statement is number 10, and the subsequent statements are incremented by 10.)
remark	Comment that describes the entry in the access list, up to 255 characters long.

Command Default

The IPv6 access list entries have no remarks.

Command Modes

IPv6 access list configuration

Command History

Release	Modification
Release 3.2	This command was supported.

Usage Guidelines

To use this command, you must be in a user group associated with a task group that includes appropriate task IDs. If the user group assignment is preventing you from using a command, contact your AAA administrator for assistance.

The **remark (IPv6)** command is similar to the **remark (IPv4)** command, except that it is IPv6-specific.

Use the **remark** command to write a helpful comment for an entry in an IPv6 access list. To remove the remark, use the **no** form of this command.

The remark can be up to 255 characters; anything longer is truncated.

If you know the sequence number of the remark you want to delete, you can remove it by entering the **no sequence-number** command.

Use the **resequence access-list ipv6** command if you want to add statements to an existing access list and the sequence numbers of consecutive entries do not permit additional statements.

Task ID

Task ID	Operations
acl	read, write

In the following example, a remark is added:

```
RP/0/0/CPU0:router(config)# ipv6 access-list Internetfilter
RP/0/0/CPU0:router(config-ipv6-acl)# 10 permit ipv6 3333:1:2:3::/64 any
RP/0/0/CPU0:router(config-ipv6-acl)# 20 permit ipv6 4444:1:2:3::/64 any
RP/0/0/CPU0:router(config-ipv6-acl)# 30 permit ipv6 5555:1:2:3::/64 any
RP/0/0/CPU0:router(config-ipv6-acl)# 39 remark Block BGP traffic from a given host
RP/0/0/CPU0:router(config-ipv6-acl)# 40 deny tcp host 6666:1:2:3::10 eq bgp host
7777:1:2:3::20 range 1300 1400
RP/0/0/CPU0:router# show ipv6 access-list Internetfilter

ipv6 access-list Internetfilter
 10 permit ipv6 3333:1:2:3::/64 any
 20 permit ipv6 4444:1:2:3::/64 any
 30 permit ipv6 5555:1:2:3::/64 any
 39 remark Block BGP traffic from a given host
 40 deny tcp host 6666:1:2:3::10 eq bgp host 7777:1:2:3::20 range host 6666:1:2:3::10 eq
bgp host 7777:1:2:3::20 range 1300 1400
```

Related Commands

Command	Description
deny (IPv6) , on page 21	Sets the deny conditions for an IPv6 access list.
ipv6 access-list , on page 33	Defines an IPv6 access list and enters IPv6 access list configuration mode.
permit (IPv6) , on page 53	Sets permit conditions for an IPv6 access list
resequence access-list ipv6 , on page 62	Changes the starting entry number of the first statement in an existing IPv6 access list, and the number by which subsequent statements are incremented.

resequence access-list ipv4

To renumber existing statements and increment subsequent statements to allow a new IPv4 access list statement (**permit**, **deny**, or **remark**) to be added, use the **resequence access-list ipv4** command in EXEC mode.

```
resequence access-list ipv4 name [base [ increment ]]
```

Syntax Description

name	Name of an IPv4 access list.
base	(Optional) Number of the first statement in the specified access list, which determines its order in the access list. Maximum value is 2147483644. Default is 10.
increment	(Optional) Number by which the base sequence number is incremented for subsequent statements. Maximum value is 2147483644. Default is 10.

Command Default

base: 10
increment: 10

Command Modes

EXEC

Command History

Release	Modification
Release 3.2	This command was introduced.

Usage Guidelines

To use this command, you must be in a user group associated with a task group that includes appropriate task IDs. If the user group assignment is preventing you from using a command, contact your AAA administrator for assistance.

Use the **resequence access-list ipv4** command to add a **permit**, **deny**, or **remark** statement between consecutive entries in an existing IPv4 access list. Specify the first entry number (the *base*) and the increment by which to separate the entry numbers of the statements. The software renumbers the existing statements, thereby making room to add new statements with the unused entry numbers.

Task ID

Task ID	Operations
acl	read, write

In the following example, suppose you have an existing access list:

```
ipv4 access-list marketing
 1 permit 10.1.1.1
 2 permit 10.2.0.0 0.0.255.255
 3 permit tcp host 10.2.2.2 255.255.0.0 any eq telnet
```

You want to add additional entries in the access list. First you resequence the entries, renumbering the statements starting with number 20 and an increment of 5, and then you have room for four additional statements between each of the existing statements:

```
RP/0/0/CPU0:router# resequence access-list ipv4 marketing 20 5
RP/0/0/CPU0:router# show access-lists ipv4 marketing
```

```
ipv4 access-list marketing
 20 permit 10.1.1.1
 25 permit 10.2.0.0
 30 permit tcp host 10.2.2.2 255.255.0.0 any eq telnet
```

Now you add your new entries.

```
RP/0/0/CPU0:router(config)# ipv4 access-list marketing
RP/0/0/CPU0:router(config-ipv4-acl)# 3 remark Do not allow user1 to telnet out
RP/0/0/CPU0:router(config-ipv4-acl)# 4 deny tcp host 172.16.2.88 255.255.0.0 any eq telnet
RP/0/0/CPU0:router(config-ipv4-acl)# 29 remark Allow user2 to telnet out
RP/0/0/CPU0:router# show access-lists ipv4 marketing
```

```
ipv4 access-list marketing
 3 remark Do not allow user1 to telnet out
 4 deny tcp host 171.69.2.88 255.255.0.0 any eq telnet
 20 permit 10.1.1.1
 25 permit 10.2.0.0
 29 remark Allow user2 to telnet out
 30 permit tcp host 10.2.2.2 255.255.0.0 any eq telnet
```

Related Commands

Command	Description
deny (IPv4) , on page 10	Sets the deny conditions for an IPv4 access list.
ipv4 access-list , on page 28	Defines an IPv4 access list and enters IPv4 access list configuration mode.
permit (IPv4) , on page 39	Sets the permit conditions for an IPv4 access list
remark (IPv4) , on page 57	Inserts a helpful remark about an IPv4 access list . entry
show access-lists ipv4 , on page 65	Displays the contents of all current IPv4 access lists.

resequence access-list ipv6

To renumber existing statements and increment subsequent statements to allow a new IPv6 access list statement (**permit**, **deny**, or **remark**) to be added, use the **resequence access-list ipv6** command in EXEC mode.

```
resequence access-list ipv6 name [base [ increment ]]
```

Syntax Description

name	Name of an IPv6 access list.
base	(Optional) Number of the first statement in the specified access list, which determines its order in the access list. Maximum value is 2147483646. Default is 10.
increment	(Optional) Number by which the base sequence number is incremented for subsequent statements. Maximum value is 2147483644. Default is 10.

Command Default

base: 10
increment: 10

Command Modes

EXEC

Command History

Release	Modification
Release 3.2	This command was supported. The command name was changed from resequence ipv6 access-list to resequence access-list ipv6 . The <i>increment</i> maximum value was changed from 2147483646 to 2147483644.

Usage Guidelines

To use this command, you must be in a user group associated with a task group that includes appropriate task IDs. If the user group assignment is preventing you from using a command, contact your AAA administrator for assistance.

The **resequence access-list ipv6** command is similar to the **resequence access-list ipv4** command, except that it is IPv6 specific.

Use the **resequence access-list ipv6** command to add a **permit**, **deny**, or **remark** statement between consecutive entries in an existing IPv6 access list. Specify the first entry number (the *base*) and the increment by which to separate the entry numbers of the statements. The software renumbers the existing statements, thereby making room to add new statements with the unused entry numbers.

Task ID

Task ID	Operations
acl	read, write

In the following example, suppose you have an existing access list:

```
ipv6 access-list Internetfilter
 10 permit ipv6 3333:1:2:3::/64 any
 20 permit ipv6 4444:1:2:3::/64 any
 30 permit ipv6 5555:1:2:3::/64 any
```

You want to add additional entries in the access list. First, you resequence the entries, renumbering the statements starting with number 20 and an increment of 5, and then you have room for four additional statements between each of the existing statements:

```
RP/0/0/CPU0:router# resequence access-list ipv6 Internetfilter 20 5
RP/0/0/CPU0:router# show access-lists ipv6 Internetfilter
```

```
ipv6 access-list Internetfilter
 20 permit ipv6 3333:1:2:3::/64 any
 25 permit ipv6 4444:1:2:3::/64 any
 30 permit ipv6 5555:1:2:3::/64 any
```

Now you add your new entries.

```
RP/0/0/CPU0:router(config)# ipv6 access-list Internetfilter
RP/0/0/CPU0:router(config-ipv6-acl)# 3 remark Block BGP traffic from a given host
RP/0/0/CPU0:router(config-ipv6-acl)# 4 deny tcp host 6666:1:2:3::10 eq bgp host 7777:1:2:3::20
range 1300 1400
RP/0/0/CPU0:router# show access-lists ipv6 Internetfilter
```

```
ipv6 access-list Internetfilter
 3 remark Block BGP traffic from a given host
 4 deny tcp host 6666:1:2:3::10 eq bgp host 7777:1:2:3::20 range 1300 1404 deny tcp host
171.69.2.88 255.255.0.0 any eq telnet
 20 permit ipv6 3333:1:2:3::/64 any
 25 permit ipv6 4444:1:2:3::/64 any
 30 permit ipv6 5555:1:2:3::/64 any
```

Related Commands

Command	Description
deny (IPv6) , on page 21	Sets the deny conditions for an IPv6 access list.
ipv6 access-list , on page 33	Defines an IPv6 access list and enters IPv6 access list configuration mode.
permit (IPv6) , on page 53	Set permit conditions for an IPv6 access list.
remark (IPv6) , on page 59	Inserts a helpful remark about an IPv6 access list entry.

show access-lists afi-all

To display the contents of current IPv4 and IPv6 access lists, use the **show access-lists afi-all** command in EXEC mode.

show access-lists afi-all

Syntax Description

This command has no keywords or arguments.

Command Modes

EXEC

Command History	Release	Modification
	Release 3.6.0	This command was introduced.

Usage Guidelines To use this command, you must be in a user group associated with a task group that includes appropriate task IDs. If the user group assignment is preventing you from using a command, contact your AAA administrator for assistance.

Task ID	Task ID	Operations
	acl	read

The following sample output is from the **show access-lists acli-all** command:

```
RP/0/0/CPU0:router# show access-lists acli-all
ipv4 access-list crypto-1
 10 permit ipv4 65.21.21.0 0.0.0.255 65.6.6.0 0.0.0.255
 20 permit ipv4 192.168.241.0 0.0.0.255 192.168.65.0 0.0.0.255
```

show access-lists ipv4

To display the contents of current IPv4 access lists, use the **show access-lists ipv4** command in EXEC mode.

show access-lists ipv4 [*access-list-name* **hardware** {**ingress** | **egress**}] [**interface** *type interface-path-id*] {*sequence number* | **location** *node-id*} | **summary** [*access-list-name*] | *access-list-name* [*sequence-number*] | **maximum** [**detail**] [**usage pfilter** { **location** *node-id* | **all** }]]

Syntax Description		
	access-list-name	(Optional) Name of a particular IPv4 access list. The name cannot contain spaces or quotation marks, but can include numbers.
	hardware	(Optional) Identifies the access list as an access list for an interface.
	ingress	(Optional) Specifies an inbound interface.
	egress	(Optional) Specifies an outbound interface.

interface	(Optional) Displays interface statistics.
type	(Optional) Interface type. For more information, use the question mark (?) online help function.
interface-path-id	Physical interface or virtual interface. Note Use the show interfaces command to see a list of all interfaces currently configured on the router. For more information about the syntax for the router, use the question mark (?) online help function.
sequence <i>number</i>	(Optional) Sequence number of a particular IPv4 access list. Range is 1 to 2147483644.
location <i>node-id</i>	(Optional) Location of a particular IPv4 access list. The <i>node-id</i> argument is entered in the <i>rack/slot/module</i> notation.
summary	(Optional) Displays a summary of all current IPv4 access lists.
sequence-number	(Optional) Sequence number of a particular IPv4 access list. Range is 1 to 2147483644.
maximum	(Optional) Displays the current maximum number of configurable IPv4 access control lists (ACLs) and access control entries (ACEs).
detail	(Optional) Displays complete out-of-resource (OOR) details.
usage	(Optional) Displays the usage of the access list on a given line card.
pfilter	(Optional) Displays the packet filtering usage for the specified line card.
all	(Optional) Displays the location of all the line cards.

Command Default The default displays all IPv4 access lists.

Command Modes EXEC

Release	Modification
Release 3.2	This command was introduced.
Release 3.3.0	The optional keywords usage and pfilter were added.
Release 3.5.0	The interface keyword was added.

Usage Guidelines To use this command, you must be in a user group associated with a task group that includes appropriate task IDs. If the user group assignment is preventing you from using a command, contact your AAA administrator for assistance.

Use the **show access-lists ipv4** command to display the contents of all IPv4 access lists. To display the contents of a specific IPv4 access list, use the *name* argument. Use the *sequence-number* argument to specify the sequence number of the access list.

Use the **hardware**, **ingress** or **egress**, and **location** keywords to display the access list hardware contents and counters for all interfaces that use the specified access list in a given direction (ingress or egress). To display the contents of a specific access list entry, use the **sequence number** keyword and argument. The access group for an interface must be configured using the **ipv4 access-group** command for access list hardware counters to be enabled.

Use the **show access-lists ipv4 summary** command to display a summary of all current IPv4 access lists. To display a summary of a specific IPv4 access list, use the *name* argument.

Use the **show access-lists ipv4 maximum detail** command to display the OOR details for IPv4 access lists. OOR limits the number of ACLs and ACEs that can be configured in the system. When the limit is reached, configuration of new ACLs or ACEs is rejected.

Use the **show access-list ipv4 usage** command to display a summary of all interfaces and access lists programmed on the specified line card.

Task ID	Operations
acl	read

In the following example, the contents of all IPv4 access lists are displayed:

```
RP/0/0/CPU0:router# show access-lists ipv4
ipv4 access-list 101
  10 deny udp any any eq ntp
```

```

20 permit tcp any any
30 permit udp any any eq tftp
40 permit icmp any any
50 permit udp any any eq domain
ipv4 access-list Internetfilter
10 permit tcp any 172.16.0.0 0.0.255.255 eq telnet
20 deny tcp any any
30 deny udp any 172.18.0.0 0.0.255.255 lt 1024
40 deny ipv4 any any log

```

In the following example, the contents of an access list named `acl_hw_1` are displayed:

```
RP/0/0/CPU0:router# show access-lists ipv4 acl_hw_1 hardware egress location 0/2/cp0
```

```

ipv4 access-list acl_hw_1
10 permit icmp 192.168.36.0 0.0.0.255 any (251 hw matches)
20 permit ip 172.16.3.0 0.0.255.255 any (29 hw matches)
30 deny tcp any any (58 hw matches)

```

This table describes the significant fields shown in the display.

Table 1: show access-lists ipv4 hardware Field Descriptions

Field	Description
hw matches	Number of hardware matches.
ACL name	Name of the ACL programmed in hardware.
Sequence Number	Each ACE sequence number is programmed into hardware with all the fields that are corresponding to the values set in ACE.
Grant	Depending on the ACE rule, the grant is set to deny, permit, or both.
Logging	Logging is set to on if ACE uses a log option to enable logs.
Per ace icmp	If Per ace icmp is set to on in the hardware, ICMP is unreachable, is rate-limited, and is generated. The default is set to on.
Hits	Hardware counter for that ACE.

In the following example, a summary of all IPv4 access lists are displayed:

```
RP/0/0/CPU0:router# show access-lists ipv4 summary
```

```

ACL Summary:
Total ACLs configured: 3
Total ACEs configured: 11

```

This table describes the significant fields shown in the display.

Table 2: show access-lists ipv4 summary Field Descriptions

Field	Description
Total ACLs configured	Number of configured IPv4 ACLs.
Total ACEs configured	Number of configured IPV4 ACEs.

In the following example, the OOR details of the IPv4 access lists are displayed:

```
RP/0/0/CPU0:router# show access-lists ipv4 maximum detail
```

```
Default max configurable acls :5000
Default max configurable aces :200000
Current configured acls      :1
Current configured aces     :2
Current max configurable acls :5000
Current max configurable aces :200000
Max configurable acls       :9000
Max configurable aces       :350000
```

This table describes the significant fields shown in the display.

Table 3: show access-lists ipv4 maximum detail Field Descriptions

Field	Description
Default max configurable acls	Default maximum number of configurable IPv4 ACLs allowed.
Default max configurable aces	Default maximum number of configurable IPv4 ACEs allowed.
Current configured acls	Number of configured IPv4 ACLs.
Current configured aces	Number of configured IPv4 ACEs.
Current max configurable acls	Configured maximum number of configurable IPv4 ACLs allowed.
Current max configurable aces	Configured maximum number of configurable IPv4 ACEs allowed.
Max configurable acls	Maximum number of configurable IPv4 ACLs allowed.
Max configurable aces	Maximum number of configurable IPv4 ACEs allowed.

Related Commands

Command	Description
clear access-list ipv4 , on page 2	Resets the IPv4 access list match counters.
copy access-list ipv4 , on page 7	Copies an existing IPv4 access list.
deny (IPv4) , on page 10	Sets the deny conditions for an ACE of an IPv4 access list.
ipv4 access-group , on page 25	Filters incoming or outgoing IPv4 traffic on an interface.
ipv4 access-list , on page 28	Defines an IPv4 access list and enters IPv4 access list configuration mode.
permit (IPv4) , on page 39	Sets the permit conditions for an ACE of an IPv4 access list.
remark (IPv4) , on page 57	Inserts a helpful remark about an IPv4 access list entry.
resequence access-list ipv4 , on page 61	Changes the starting entry number of the first statement in an existing IPv4 access list, and the number by which subsequent statements are incremented.

show access-lists ipv4 standby

To display the contents of current IPv4 standby access lists, use the **show access-lists ipv4 standby** command in EXEC mode.

show access-lists ipv4 standby [**access-list name**] [**summary**]

Syntax Description

access-list name	(Optional) Name of a particular IPv4 access list. The name cannot contain spaces or quotation marks, but can include numbers.
summary	(Optional) Displays a summary of all current IPv4 standby access lists.

Command Modes

EXEC

Command History

Release	Modification
Release 3.8.0	This command was introduced .

Usage Guidelines

To use this command, you must be in a user group associated with a task group that includes appropriate task IDs. If the user group assignment is preventing you from using a command, contact your AAA administrator for assistance.

Use the **show access-lists ipv4 standby** command to display the contents of current IPv4 standby access lists. To display the contents of a specific IPv4 access list, use the *name* argument.

Use the **show access-lists ipv4 standby summary** command to display a summary of all standby IPv4 access lists.

Task ID

Task ID	Operations
acl	read

In the following example, the contents of all IPv4 access lists are displayed:

```
RP/0/0/CPU0:router# show access-lists ipv4 standby summary
ACL Summary:
  Total ACLs configured: 4
  Total ACEs configured: 22
```

show access-lists ipv6

To display the contents of current IPv6 access lists, use the **show access-lists ipv6** command in EXEC mode.

```
show access-lists ipv6 [access-list-name hardware {ingress|egress} [interface type interface-path-id]
{sequence number|location node-id}| summary [access-list-name] access-list-name [sequence-number] ]
maximum [detail] [usage pfilter { location node-id | all } ]]
```

Syntax Description

<i>access-list-name</i>	Name of a particular IPv6 access list. The name cannot contain a spaces or quotation marks, but can include numbers.
hardware	Identifies the access list as an access list for an interface.
ingress	Specifies an inbound interface.
egress	Specifies an outbound interface.

sequence <i>number</i>	(Optional) Sequence number of a particular IPv6 access list. Range is 1 to 2147483646.
interface	(Optional) Displays interface statistics.
type	Interface type. For more information, use the question mark (?) online help function.
interface-path-id	Physical interface or virtual interface. Note Use the show interfaces command to see a list of all interfaces currently configured on the router. For more information about the syntax for the router, use the question mark (?) online help function.
location <i>node-id</i>	Location of a particular IPv4 access list. The <i>node-id</i> argument is entered in the <i>rack/slot/module</i> notation.
all	Displays the location of all the line cards.
summary	Displays a summary of all current IPv6 access lists.
sequence-number	(Optional) Sequence number of a particular IPv6 access list. Range is 1 to 2147483646.
maximum	Displays the current maximum number of configurable IPv6 access control lists (ACLs) and access control entries (ACEs).
detail	(Optional) Displays complete out-of-resource (OOR) details.
usage	(Optional) Displays the usage of the access list on a given line card.
pfilter	Displays the packet filtering usage for the specified line card.

Command Default Displays all IPv6 access lists.

Command Modes EXEC

Command History

Release	Modification
Release 3.2	This command was introduced.
Release 3.3.0	The optional keywords usage and pfilter were added.
Release 3.5.0	The interface keyword was added.
Release 3.6.0	The all keyword was added.

Usage Guidelines

To use this command, you must be in a user group associated with a task group that includes appropriate task IDs. If the user group assignment is preventing you from using a command, contact your AAA administrator for assistance.

The **show access-lists ipv6** command is similar to the **show access-lists ipv4** command, except that it is IPv6 specific.

Use the **show access-lists ipv6** command to display the contents of all IPv6 access lists. To display the contents of a specific IPv6 access list, use the *name* argument. Use the *sequence-number* argument to specify the sequence number of the access list.

Use the **hardware**, **ingress** or **egress**, and **location** keywords to display the access list hardware contents and counters for all interfaces that use the specified access list in a given direction (ingress or egress). To display the contents of a specific access list entry, use the **sequence number** keyword and argument. The access group for an interface must be configured using the **ipv6 access-group** command for access list hardware counters to be enabled.

Use the **show access-lists ipv6 summary** command to display a summary of all current IPv6 access lists. To display a summary of a specific IPv6 access list, use the *name* argument.

Use the **show access-lists ipv6 maximum detail** command to display the OOR details for IPv6 access lists. OOR limits the number of ACLs and ACEs that can be configured in the system. When the limit is reached, configuration of new ACLs or ACEs is rejected.

Use the **show access-list ipv6 ipv4 usage** command to display a summary of all interfaces and access lists programmed on the specified line card.

Task ID

Task ID	Operations
acl	read

In the following example, the contents of all IPv6 access lists are displayed:

```
RP/0/0/CPU0:router# show access-lists ipv6

ipv6 access-list Internetfilter
 3 remark Block BGP traffic from a given host
 4 deny tcp host 6666:1:2:3::10 eq bgp host 7777:1:2:3::20 range 1300 1404 deny tcp host
171.69.2.88 255.255.0.0 any eq telnet
20 permit ipv6 3333:1:2:3::/64 any
25 permit ipv6 4444:1:2:3::/64 any
30 permit ipv6 5555:1:2:3::/64 any
ipv6 access-list marketing
10 permit ipv6 7777:1:2:3::/64 any (51 matches)
20 permit ipv6 8888:1:2:3::/64 any (26 matches)
30 permit ipv6 9999:1:2:3::/64 any (5 matches)
```

In the following example, the contents of an access list named Internetfilter is displayed:

```
RP/0/0/CPU0:router# show access-lists ipv6 Internetfilter

ipv6 access-list Internetfilter
 3 remark Block BGP traffic from a given host
 4 deny tcp host 6666:1:2:3::10 eq bgp host 7777:1:2:3::20 range 1300 1404 deny tcp host
171.69.2.88 255.255.0.0 any eq telnet
20 permit ipv6 3333:1:2:3::/64 any
```

```

25 permit ipv6 4444:1:2:3::/64 any
30 permit ipv6 5555:1:2:3::/64 any

```

In the following example, the contents of an access list named `acl_hw_1` is displayed:

```

RP/0/0/CPU0:router# show access-lists ipv6 acl_hw_1 hardware egress location 0/2/cp0

ipv6 access-list acl_hw_1
 10 permit icmp any any (251 hw matches)
 20 permit ipv6 3333:1:2:3::/64 any (29 hw matches)
 30 deny tcp any any (58 hw matches)

```

This table describes the significant fields shown in the display.

Table 4: show access-lists ipv6 hardware Field Descriptions

Field	Description
hw matches	Number of hardware matches.

In the following example, a summary of all IPv6 access lists is displayed:

```

RP/0/0/CPU0:router# show access-lists ipv6 summary

ACL Summary:
  Total ACLs configured: 3
  Total ACEs configured: 11

```

This table describes the significant fields shown in the display.

Table 5: show access-lists ipv6 summary Field Descriptions

Field	Description
Total ACLs configured	Number of configured IPv6 ACLs.
Total ACEs configured	Number of configured IPV6 ACEs.

In the following example, the OOR details of the IPv6 access lists are displayed:

```

RP/0/0/CPU0:router# show access-lists ipv6 maximum detail

Default max configurable acls :1000
Default max configurable aces :50000
Current configured acls      :1
Current configured aces      :2
Current max configurable acls :1000
Current max configurable aces :50000
Max configurable acls        :2000
Max configurable aces        :100000

```

This table describes the significant fields shown in the display.

Table 6: show access-lists pv6 maximum detail Field Descriptions

Field	Description
Default max configurable acls	Default maximum number of configurable IPv6 ACLs allowed.

Field	Description
Default max configurable aces	Default maximum number of configurable IPv6 ACEs allowed.
Current configured acls	Number of configured IPv6 ACLs.
Current configured aces	Number of configured IPv6 ACEs.
Current max configurable acls	Configured maximum number of configurable IPv6 ACLs allowed.
Current max configurable aces	Configured maximum number of configurable IPv6 ACEs allowed.
Max configurable acls	Maximum number of configurable IPv6 ACLs allowed.
Max configurable aces	Maximum number of configurable IPv6 ACEs allowed.

Related Commands

Command	Description
copy access-list ipv6 , on page 8	Copies an existing IPv6 access list.
deny (IPv6) , on page 21	Sets the deny conditions for an IPv6 access list.
ipv6 access-list , on page 33	Defines an IPv6 access list and enters IPv6 access list configuration mode.
permit (IPv6) , on page 53	Set permit conditions for an IPv6 access list.
remark (IPv6) , on page 59	Inserts a helpful remark about an IPv6 access list entry.
resequence access-list ipv6 , on page 62	Changes the starting entry number of the first statement in an existing IPv4 access list, and the number by which subsequent statements are incremented.

show access-lists ipv6 standby

To display the contents of current IPv6 standby access lists, use the **show access-lists ipv6 standby** command in EXEC mode.

show access-lists ipv6 standby [access-list name] [summary]**Syntax Description**

access-list name	(Optional) Name of a particular IPv6 access list. The name cannot contain spaces or quotation marks, but can include numbers.
summary	(Optional) Displays a summary of all current IPv6 standby access lists.

Command Default

No default behavior or values

Command Modes

EXEC

Command History

Release	Modification
Release 3.8.0	This command was introduced.

Usage Guidelines

To use this command, you must be in a user group associated with a task group that includes appropriate task IDs. If the user group assignment is preventing you from using a command, contact your AAA administrator for assistance.

Use the **show access-lists ipv6 standby** command to display the contents of current IPv6 standby access lists. To display the contents of a specific IPv6 access list, use the *name* argument.

Use the **show access-lists ipv6 standby summary** command to display a summary of all standby IPv6 access lists.

Task ID

Task ID	Operations
acl	read

In the following example, the contents of all IPv6 standby access lists are displayed:

```
RP/0/0/CPU0:router# show access-lists ipv6 standby summary
ACL Summary:
  Total ACLs configured: 4
  Total ACEs configured: 22
```

This table describes the significant fields shown in the display.

Table 7: show access-lists ipv6 standby summary Field Descriptions

Field	Description
Total ACLs configured	Number of configured standby IPv6 ACLs.

Field	Description
Total ACEs configured	Number of configured standby IPV6 ACEs.

Related Commands

Command	Description
copy access-list ipv6, on page 8	Copies an existing IPv6 access list.
ipv6 access-list , on page 33	Defines an IPv6 access list and enters IPv6 access list configuration mode.

`show access-lists ipv6 standby`