



Accessory Kits

This appendix includes the following sections:

- [Cisco Nexus 7702 Switch Accessory Kit, on page 1](#)
- [Cisco Nexus 7702 Center-Mount Kit, on page 4](#)

Cisco Nexus 7702 Switch Accessory Kit

The following table lists and illustrates the contents for the accessory kit.

Illustration	Description	Quantity
	Rack Mount Kit <ul style="list-style-type: none"> • M3 x 8 mm Phillips screws (4) • M4 x 8 mm Phillips screws (8) 	1 kit
	RJ-45 rollover cable	1
	DB-9F/RJ-45F PC terminal	1
Ground lug kit 	Ground lug kit <ul style="list-style-type: none"> • Two-hole lug (1) • M3 x 9-mm Phillips pan-head screws (2) 	1 kit
	Cable tie (2)	1
ESD wrist strap 	ESD wrist strap (disposable)	1

Illustration	Description	Quantity
Not applicable	Hazardous substances list for customers in China	1
Not applicable	Cisco Information Packet	1
Not applicable	1-Year Limited Warranty for Hardware	1



Note If you do not receive a part listed in this document, contact Cisco Technical Support at this URL: <http://www.cisco.com/warp/public/687/Directory/DirTAC.shtml>.

If you purchased this product through a Cisco reseller, you might receive additional contents in your kit, such as documentation, hardware, and power cables.

The product shipment includes power cords for the following power supplies:

- 3-kW AC power supplies—one power cord per power supply
- 3-kW DC power supplies—no power cords supplied (you must supply a 6 AWG cable for up to 45 A)

The shipped cables depend on your specification when placing an order.

The available power cords for the 3-kW AC power supplies are as follows:

- CAB-AC-16A-AUS—power cord, 250-VAC 16A, C19, Australia
- CAB-AC-16A-CH—power cord, 16A, China
- CAB-AC-2500W-EU—power cord, 250-VAC 16A, Europe
- CAB-AC-2500W-INT—power cord, 250-VAC 16A, International
- CAB-AC-2500W-ISRL—power cord, 250-VAC 16A, Israel
- CAB-9K16A-US1—power cord, 250-VAC 16A, Src Plug NEMA 6-20, US/Japan
- CAB-AC-C6K-TWLK—power cord, 250-VAC 16A, twist lock, NEMA L6-20
- CAB-7513AC—power cord, AC 110V North America
- CAB-C19-CBN—cabinet jumper power cord, 250-VAC, 16A, C20C
- CAB-ACS-16—power cord, 16-A, Switzerland
- CAB-L520P-C19-US—NEMA L5-20 to IEC-C19 6ft US

The available AC power cords for the 3.5-kW HVAC/HVDC power supplies are as follows:

- CAB-AC-16A-SG-AR—power cord, IRSM 2073/Saf-D-Grid 250 VAC 16A, Argentina
- CAB-AC-16A-SG-AZ—power cord, AU20LS3/Saf-D-Grid, 250 VAC 16A, Australia and New Zealand
- CAB-AC-16A-SG-BR—power cord, EL224/Saf-D-Grid 250 VAC 16A, Brazil
- CAB-AC-16A-SG-CH—power cord, GB 16C/Saf-D-Grid, 250 VAC 16A, China
- CAB-AC-16A-SG-EU—power cord, CEE 7-7/Saf-D-Grid, 250 VAC 16A, Europe

- CAB-AC-16A-SG-IND—power cord, SABS 164-1/Saf-D-Grid 250 VAC 16A, India
- CAB-AC-16A-SG-IN—power cord, IEC60309/Saf-D-Grid, 250 VAC 16A, International
- CAB-AC-16A-SG-IS—power cord, SI 16S3/Saf-D-Grid, 250 VAC 16A, Israel
- CAB-AC-16A-SG-IT—power cord, CEI 23-50/Saf-D-Grid to IEC-C19 250 VAC 16A, Italy
- CAB-AC-20A-SG-US—power cord, 110 VAC 20A, Straight Blade, NEMA 5-20P/Saf-D-Grid, North America
- CAB-AC-20A-SG-US1—power cord, 125 VAC 20A, twist lock, NEMA L5-20/Saf-D-Grid, North America
- CAB-AC-20A-SG-US2—power cord, 250 VAC 20A, straight-blade, NEMA 6-20/Saf-D-Grid, North America
- CAB-AC-20A-SG-US3—power cord, 250 VAC 20A, twist lock, NEMA L6-20/Saf-D-Grid, North America
- CAB-AC-20A-SG-US4—power cord, 277 VAC 20A, NEMA L7-20P/Saf-D-Grid, North America
- CAB-AC-20A-SG-C20—cabinet jumper power cord, 250 VAC, 20A, IEC C20/Saf-D-Grid, North America
- CAB-AC-16A-SG-SA—power cord, 250 VAC 16A, EL/Saf-D-Grid, South Africa
- CAB-AC-16A-SG-SK—power cord, 250 VAC 16A, Src/Saf-D-Grid, Korea
- CAB-AC-16A-SG-SW—power cord, 250 VAC 16A, SEV 5934-2/Saf-D-Grid, Switzerland
- CAB-HV-25A-SG-IN2—power cord, 300 VAC/500 VDC 20A, Ring Terminal/Saf-D-Grid, IEC/EU
- CAB-HV-25A-SG-IN3—power cord, 300 VAC 20A, Saf-D-Grid P10/Saf-D-Grid P4, IEC/EU
- CAB-HV-25A-SG-US2—power cord, 300 VAC/500 VDC 20A, Ring Terminal/Saf-D-Grid, North America
- CAB-HV-25A-SG-US5—power cord, 300 VAC 20A, Saf-D-Grid P10/Saf-D-Grid P4, North America



Note All power cords will not be orderable at first customer shipment (FCS).

The available DC power cords for the 3.5-kW HVAC/HVDC power supplies are as follows:

- CAB-HV-25A-SG-US1—power cord, 400-VDC 20A, Saf-D-Grid/Saf-D-Grid, North America
- CAB-HV-25A-SG-US2—power cord, 300-VAC/500-VDC 20A, Ring Terminal/Saf-D-Grid, North America
- CAB-HV-25A-SG-IN1—power cord, 400-VDC 20A, IEC/EU, Saf-D-Grid/Saf-D-Grid, International
- CAB-HV-25A-SG-IN2—power cord, 300-VAC/500-VDC 20A, IEC/EU, Ring Terminal/Saf-D-Grid, International



Note All power cords will not be orderable at first customer shipment (FCS).

Cisco Nexus 7702 Center-Mount Kit

If you are installing the Cisco Nexus 7702 chassis on a two-post rack, you must order this kit (N7K-C7702-CMK) when you order the switch. The following table lists the contents for this kit.

Description	Quantity
Center-mount rack mounting brackets (right and left brackets)	2
M3 x 8-mm Phillips screws	4
M4 x 8-mm Phillips screws	8