

Send comments to nexus5k-docfeedback@cisco.com



Show Commands

This chapter describes the system management **show** commands.

[Send comments to nexus5k-docfeedback@cisco.com](mailto:nexus5k-docfeedback@cisco.com)

show diagnostic bootup level

To display the current bootup diagnostic level on the switch, use the **show diagnostic bootup level** command.

show diagnostic bootup level

Syntax Description This command has no arguments or keywords.

Command Default None

Command Modes EXEC mode

Command History	Release	Modification
	4.0(0)N1(1)	This command was introduced.

Examples This example shows how to display the current bootup diagnostic level:

```
switch# show diagnostic bootup level

Current bootup diagnostic level: complete

switch#
```

Related Commands	Command	Description
	diagnostic bootup level	Configures the bootup diagnostic level for a faster module bootup time.
	show diagnostic result	Displays the results of the diagnostics tests.

[Send comments to nexus5k-docfeedback@cisco.com](mailto:nexus5k-docfeedback@cisco.com)

show diagnostic result

To display the results of the diagnostic tests, use the **show diagnostic result** command.

```
show diagnostic result module {module-no | all}
```

Syntax Description	module	Specifies the module for which diagnostic results are displayed.
	<i>module-no</i>	Module number. Valid values are 1 to 3.
	all	Displays the diagnostic results for all modules.

Command Default None

Command Modes EXEC mode

Command History	Release	Modification
	4.0(0)N1(1)	This command was introduced.

Examples

This example shows how to display the diagnostic results for a specific module:

```
switch# show diagnostic result module 1

Current bootup diagnostic level: complete

Module 1: 48X10GE/Supervisor SerialNo : JAF1339ANGH

Overall Diagnostic Result for Module 1 : PASS
Diagnostic level at card bootup: complete

Test results: (. = Pass, F = Fail, I = Incomplete,
              U = Untested, A = Abort)

    1) TestUSBFlash -----> .
    2) TestSPROM -----> .
    3) TestPCIE -----> .
    4) TestLED -----> .
    5) TestOBFL -----> .
    6) TestNVRAM -----> .
    7) TestPowerSupply -----> F
    8) TestTemperatureSensor -----> .
    9) TestFan -----> .
   10) TestVoltage -----> .
   11) TestGPIO -----> .
   12) TestInbandPort -----> .
   13) TestManagementPort -----> .
   14) TestMemory -----> .
   15) TestFabricEngine :

Eth   1  2  3  4  5  6  7  8  9 10 11 12 13 14 15 16 17 18 19 20 21 22 23 24
Port -----
      .  .  .  .  .  .  .  .  .  .  .  .  .  .  .  .  .  .  .  .  .  .  .  .
```

Send comments to nexus5k-docfeedback@cisco.com

```
Eth  25 26 27 28 29 30 31 32 33 34 35 36 37 38 39 40 41 42 43 44 45 46 47 48
Port -----
. . . . .
```

16) TestFabricPort :

```
Eth   1  2  3  4  5  6  7  8  9 10 11 12 13 14 15 16 17 18 19 20 21 22 23 24
Port -----
. . . . .
```

```
Eth  25 26 27 28 29 30 31 32 33 34 35 36 37 38 39 40 41 42 43 44 45 46 47 48
Port -----
. . . . .
```

17) TestForwardingEngine :

```
Eth   1  2  3  4  5  6  7  8  9 10 11 12 13 14 15 16 17 18 19 20 21 22 23 24
Port -----
. . . . .
```

```
Eth  25 26 27 28 29 30 31 32 33 34 35 36 37 38 39 40 41 42 43 44 45 46 47 48
Port -----
. . . . .
```

18) TestForwardingEnginePort :

```
Eth   1  2  3  4  5  6  7  8  9 10 11 12 13 14 15 16 17 18 19 20 21 22 23 24
Port -----
. . . . .
```

```
Eth  25 26 27 28 29 30 31 32 33 34 35 36 37 38 39 40 41 42 43 44 45 46 47 48
Port -----
. . . . .
```

19) TestFrontPort :

```
Eth   1  2  3  4  5  6  7  8  9 10 11 12 13 14 15 16 17 18 19 20 21 22 23 24
Port -----
. . . . .
```

```
Eth  25 26 27 28 29 30 31 32 33 34 35 36 37 38 39 40 41 42 43 44 45 46 47 48
Port -----
. . . . .
```

switch#

Related Commands

Command	Description
diagnostic bootup level	Configures the bootup diagnostic level for a faster module bootup time.
show diagnostic bootup level	Displays the bootup diagnostics level.

[Send comments to nexus5k-docfeedback@cisco.com](mailto:nexus5k-docfeedback@cisco.com)

show hosts

To display the Domain Name Server (DNS) name servers and domain names, use the **show hosts** command.

show hosts

Syntax Description This command has no arguments or keywords.

Command Default None

Command Modes EXEC mode

Command History	Release	Modification
	5.0(3)N1(1)	This command was introduced.

Examples This example shows how to display the IP addresses of the DNS servers that are used to resolve host names:

```
switch# show hosts
DNS lookup enabled
Default domain for vrf:default is mysite.com
Name/address lookup uses domain service
Name servers are 255.255.255.255
```

Vrf	Use-vrf	Token	Config
default	management	domain	mysite.com
default	management	add. domain(s)	mysite2.com
Host	Address		
switch#			

Related Commands	Command	Description
	ip domain-list	Defines a list of domains.
	ip domain lookup	Enables DNS-based host name-to-address translation.
	ip domain-name	Configures a name server.

[Send comments to nexus5k-docfeedback@cisco.com](mailto:nexus5k-docfeedback@cisco.com)

show ip dns source-interface

To display the source interfaces configured for Domain Name Server (DNS) domain lookup, use the **show ip dns source-interface** command.

```
show ip dns source-interface [vrf {vrf-name | all | default | management}]
```

Syntax Description		
vrf	(Optional)	Displays information about the virtual routing and forwarding (VRF) instance.
<i>vrf-name</i>	(Optional)	VRF name. The name is case sensitive and can be a maximum of 32 characters.
all	(Optional)	Displays all VRF instances.
default	(Optional)	Displays the default VRF information.
management	(Optional)	Displays the management VRF information.

Command Default None

Command Modes EXEC mode

Command History	Release	Modification
	5.1(3)N1(1)	This command was introduced.

Usage Guidelines This command does not require a license.

Examples This example shows how to display the source interfaces configured for DNS domain lookup:

```
switch# show ip dns source-interface
VRF Name      Interface
default       Ethernet1/5
switch#
```

Related Commands	Command	Description
	ip domain-lookup	Enables the DNS lookup feature.
	ip dns source-interface	Configures interfaces for DNS domain lookup.

Send comments to nexus5k-docfeedback@cisco.com

show logging console

To display the console logging configuration, use the **show logging console** command.

show logging console

Syntax Description This command has no arguments or keywords.

Command Default None

Command Modes EXEC mode

Command History	Release	Modification
	4.0(0)N1(1a)	This command was introduced.

Examples This example shows how to display the console logging configuration:

```
switch# show logging console
```

Related Commands	Command	Description
	logging console	Configures logging to the console.

Send comments to nexus5k-docfeedback@cisco.com

show logging info

To display the logging configuration, use the **show logging info** command.

show logging info

Syntax Description This command has no arguments or keywords.

Command Default None

Command Modes EXEC mode

Command History	Release	Modification
	4.0(0)N1(1a)	This command was introduced.

Examples This example shows how to display the logging configuration:

```
switch# show logging info
```

Related Commands	Command	Description
	logging level	Enables logging messages from a defined facility.

[Send comments to nexus5k-docfeedback@cisco.com](mailto:nexus5k-docfeedback@cisco.com)

show logging last

To display the last number of lines of the logfile, use the **show logging last** command.

show logging last *number*

Syntax Description	<i>number</i>	Enters the number of lines to display from 1 to 9999.
---------------------------	---------------	---

Command Default	None	
------------------------	------	--

Command Modes	EXEC mode	
----------------------	-----------	--

Command History	Release	Modification
	4.0(0)N1(1a)	This command was introduced.

Examples	This example shows how to display the last 42 lines of the log file: <pre>switch# show logging last 42</pre>
-----------------	---

Related Commands	Command	Description
	logging level	Enables logging messages from a defined facility.

Send comments to nexus5k-docfeedback@cisco.com

show logging level

To display the facility logging severity level configuration, use the **show logging level** command.

```
show logging level [facility]
```

Syntax Description	<i>facility</i>	(Optional) Logging facility. The facilities are listed in Table 1-1 of Appendix 1, "System Message Logging Facilities."
---------------------------	-----------------	---

Command Default	None
------------------------	------

Command Modes	EXEC mode
----------------------	-----------

Command History	Release	Modification
	4.0(0)N1(1a)	This command was introduced.
	5.0(3)N1(1)	Support for multicast and unicast routing features was added.
	5.0(3)N2(1)	Support for Flex Links and Fibre Channel over Ethernet (FCoE) N-Port Virtualizer (NPV) was added.

Examples

This example shows how to display the EtherChannel logging severity level configuration:

```
switch# show logging level port-channel
```

This example shows how to display the Flex Links logging severity level configuration:

```
switch# show logging level flexlink
Facility           Default Severity      Current Session Severity
-----           -
Flexlink           2                      5

0 (emergencies)    1 (alerts)            2 (critical)
3 (errors)         4 (warnings)         5 (notifications)
6 (information)    7 (debugging)
```

```
switch#
```

This example shows how to display the FCoE NPV logging severity level configuration:

```
switch# show logging level fcoe_mgr
Facility           Default Severity      Current Session Severity
-----           -
fcoe_mgr           2                      3

0 (emergencies)    1 (alerts)            2 (critical)
3 (errors)         4 (warnings)         5 (notifications)
6 (information)    7 (debugging)
```

```
switch#
```

Send comments to nexus5k-docfeedback@cisco.com

Related Commands

Command	Description
logging level	Configures the facility logging level.

[Send comments to nexus5k-docfeedback@cisco.com](mailto:nexus5k-docfeedback@cisco.com)

show logging logfile

To display the messages in the log file that were timestamped within the span entered, use the **show logging logfile** command.

show logging logfile [**start-time** *yyyy mmm dd hh:mm:ss*] [**end-time** *yyyy mmm dd hh:mm:ss*]

Syntax Description

start-time <i>yyyy mmm dd hh:mm:ss</i>	(Optional) Specifies a start time in the format <i>yyyy mmm dd hh:mm:ss</i> . Use three characters for the month (<i>mmm</i>) field, digits for the year (<i>yyyy</i>) and day (<i>dd</i>) fields, and digits separated by colons for the time (<i>hh:mm:ss</i>) field.
end-time <i>yyyy mmm dd hh:mm:ss</i>	(Optional) Specifies an end time in the format <i>yyyy mmm dd hh:mm:ss</i> . Use three characters for the month (<i>mmm</i>) field, digits for the year (<i>yyyy</i>) and day (<i>dd</i>) fields, and digits separated by colons for the time (<i>hh:mm:ss</i>) field.

Command Default

None

Command Modes

EXEC mode

Command History

Release	Modification
4.0(0)N1(1a)	This command was introduced.

Usage Guidelines

If you do not enter an end time, the current time is used.

Examples

This example shows how to display the messages in the log file that were timestamped within the span shown:

```
switch# show logging logfile start-time 2008 mar 11 12:10:00
```

Related Commands

Command	Description
logging logfile	Configures logging to a log file.

Send comments to nexus5k-docfeedback@cisco.com

show logging module

To display the module logging configuration, use the **show logging module** command.

show logging module

Syntax Description This command has no arguments or keywords.

Command Default None

Command Modes EXEC mode

Command History	Release	Modification
	4.0(0)N1(1a)	This command was introduced.

Examples This example shows how to display the module logging configuration:

```
switch# show logging module
```

Related Commands	Command	Description
	logging module	Configures module logging.

Send comments to nexus5k-docfeedback@cisco.com

show logging monitor

To display the monitor logging configuration, use the **show logging monitor** command.

show logging monitor

Syntax Description This command has no arguments or keywords.

Command Default None

Command Modes EXEC mode

Command History	Release	Modification
	4.0(0)N1(1a)	This command was introduced.

Examples This example shows how to display the monitor logging configuration:

```
switch# show logging monitor
```

Related Commands	Command	Description
	logging monitor	Configures logging on the monitor.

[Send comments to nexus5k-docfeedback@cisco.com](mailto:nexus5k-docfeedback@cisco.com)

show logging nvram

To display the messages in the nonvolatile random access memory (NVRAM) log, use the **show logging nvram** command.

```
show logging nvram [last number-lines]
```

Syntax Description	last number-lines (Optional) Specifies the number of lines to display. The number of lines is from 1 to 100.				
Command Default	None				
Command Modes	EXEC mode				
Command History	<table border="1"> <thead> <tr> <th>Release</th> <th>Modification</th> </tr> </thead> <tbody> <tr> <td>4.0(0)N1(1a)</td> <td>This command was introduced.</td> </tr> </tbody> </table>	Release	Modification	4.0(0)N1(1a)	This command was introduced.
Release	Modification				
4.0(0)N1(1a)	This command was introduced.				
Examples	<p>This example shows how to display the last 20 messages in the NVRAM log:</p> <pre>switch# show logging nvram last 20</pre>				
Related Commands	<table border="1"> <thead> <tr> <th>Command</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>logging level</td> <td>Enables logging messages from a defined facility.</td> </tr> </tbody> </table>	Command	Description	logging level	Enables logging messages from a defined facility.
Command	Description				
logging level	Enables logging messages from a defined facility.				

[Send comments to nexus5k-docfeedback@cisco.com](mailto:nexus5k-docfeedback@cisco.com)

show logging onboard

To display the onboard logging information based on the error type, use the **show logging onboard** command.

```
show logging onboard { boot-uptime | device-version | endtime | environmental-history |
exception-log | kernel-trace | obfl-history | obfl-logs | stack-trace | starttime | status } [> file
| | type]
```

Syntax	Description
boot-uptime	Displays the onboard failure logging (OBFL) boot and uptime information.
device-version	Displays the OBFL device version information.
endtime	Displays the OBFL logs until the specified end time in the following format: <i>mm/dd/yy-HH:MM:SS</i>
environmental-history	Displays the OBFL environmental history.
exception-log	Displays the OBFL exception log.
kernel-trace	Displays the OBFL kernel trace information.
obfl-history	Displays the OBFL history information.
obfl-logs	Displays the OBFL technical support log information.
stack-trace	Displays the OBFL kernel stack trace information.
starttime	Displays the OBFL logs from the specified start time in the following format: <i>mm/dd/yy-HH:MM:SS</i>
status	Displays the OBFL status enable or disable.
> file	(Optional) Redirects the output to a file. See the “Usage Guidelines” section for additional information.
 type	(Optional) Filters the output. See the “Usage Guidelines” section for additional information.

Command Default None

Command Modes EXEC mode

Command History	Release	Modification
	4.0(0)N1(1a)	This command was introduced.

Usage Guidelines The date and time arguments for the **starttime** and **endtime** keywords are entered as the date month/day/year (*mm/dd/yy*), followed by a hyphen, and the time in 24-hour format in hours:minutes:seconds (*HH:MM:SS*). For example:

- **starttime** 03/17/08-15:01:57
- **endtime** 03/18/08-15:04:57

The valid values for *file* are as follows:

Send comments to nexus5k-docfeedback@cisco.com

- **bootflash:**
- **ftp:**
- **scp:**
- **sftp:**
- **tftp:**
- **volatile:**

The valid values for *type* are as follows:

- **begin [-i] [-x] [word]**—Begin with the line that matches the text.
 - **-i**—Ignores the case difference when comparing the strings.
 - **-x**—Prints only the lines where the match is a whole line.
 - *word*—Specifies for the expression.
- **count [> file | | type]**—Counts number of lines.
- **egrep | grep print-match**—Egrep or Grep. Egrep searches for lines of text that match more sophisticated regular expression syntax than grep. Grep searches for lines of text that match one or many regular expressions, and outputs only the matching lines.
 - **-A num**—Prints the specifies number of lines of context after every matching line. Range: 1 to 999.
 - **-B num**—Prints the specifies number of lines of context before every matching line. Range: 1 to 999.
 - **-c**—Prints a total count of matching lines only.
 - **-i**—Ignores the case difference when comparing the strings.
 - **-n**—Prints each match preceded by its line number.
 - **-v**—Prints only the lines that contain no matches for the *word* argument.
 - **-w**—Prints only lines where the match is a complete word.
 - **-x**—Prints only the lines where the match is a whole line.
 - *word*—Specifies for the expression.
- **exclude [-i] [-x] [word]**—Excludes the lines that match.
 - **-i**—Ignores the case difference when comparing the strings.
 - **-x**—Prints only the lines where the match is a whole line.
 - *word*—Specifies for the expression.
- **head [-n num]**—Stream Editor. The optional **-n num** keyword and argument allow you to specify the number of lines to print. Range: 0 to 2147483647.
- **include [-i] [-x] [word]**—Include the lines that match.
 - **-i**—Ignores the case difference when comparing the strings.
 - **-x**—Prints only the lines where the match is a whole line.
 - *word*—Specifies for the expression.
- **last [num]**—Displays the last lines to print. The optional *num* specifies the number of lines to print. Range: 0 to 9999.
- **less [-E | -d]**—Quits at the end of the file.

Send comments to nexus5k-docfeedback@cisco.com

- **-E**—(Optional) Quits at the end of the file.
- **-d**—(Optional) Specifies a dumb terminal.
- **no-more**—Turns-off pagination for command output.
- **sed command**—Stream Editor
- **wc**—Counts words, lines, and characters.
 - **-c**—(Optional) Specifies the output character count.
 - **-l**—(Optional) Specifies the output line count.
 - **-w**—(Optional) Specifies the output word count.
 - **>**—Redirects it to a file.
 - **|**—Pipes command output to filter.

Use this command to view OBFL data from the system hardware. The OBFL feature is enabled by default and records operating temperatures, hardware uptime, interrupts, and other important events and messages that can assist with diagnosing problems with hardware cards or modules installed in a Cisco router or switch. Data is logged to files stored in nonvolatile memory. When the onboard hardware is started up, a first record is made for each area monitored and becomes a base value for subsequent records.

The OBFL feature provides a circular updating scheme for collecting continuous records and archiving older (historical) records, ensuring accurate data about the system. Data is recorded in one of two formats: continuous information that displays a snapshot of measurements and samples in a continuous file, and summary information that provides details about the data being collected. The message “No historical data to display” is seen when historical data is not available.

Examples

This example shows how to display the OBFL boot and uptime information:

```
switch# show logging onboard boot-uptime
Sun Nov  9 06:11:59 2008:  Boot Record
-----
Boot Time.....:  Sun Nov  9 06:11:58 2008
Slot Number.....:  1
Serial Number.....:  FLC12280050
Bios Version.....:  v1.2.0(06/19/08)
Firmware Version...:  4.0(1a)N1(1) [build 4.0(1a)N1(1)]
```

[Table 1](#) describes the significant fields shown in the display.

Table 1 *show logging onboard boot-uptime Command Output*

Field	Description
Boot Time	Time boot occurred.
Slot Number	Slot number.
Serial Number	Serial number of the module.
Bios Version	Primary binary input and output system (BIOS) version.
Firmware Version	Firmware version.

Send comments to nexus5k-docfeedback@cisco.com

This example shows how to display the OBFL logging device information:

```
switch# show logging onboard device-version
-----
OBFL Data for
  Module: 1
-----

Device Version Record
-----
Timestamp                Device Name      Instance Hardware Software
                        Num   Version   Version
-----
Sun Nov  3 07:07:00 2008   GATOS           2         2         0
Sun Nov  3 07:07:00 2008   GATOS           3         2         0
Sun Nov  3 07:07:00 2008   GATOS           4         2         0
Sun Nov  3 07:07:00 2008   GATOS           5         2         0
Sun Nov  3 07:07:00 2008   GATOS           6         2         0
Sun Nov  3 07:07:00 2008   GATOS           7         2         0
Sun Nov  3 07:07:00 2008   GATOS           8         2         0
Sun Nov  3 07:07:00 2008   GATOS           9         2         0
Sun Nov  3 07:07:00 2008   GATOS          10         2         0
Sun Nov  3 07:07:00 2008   GATOS          11         2         0
Sun Nov  3 07:07:00 2008   GATOS          12         2         0
Sun Nov  3 07:07:00 2008   GATOS          13         2         0
Mon Nov  4 00:15:08 2008   ALTOS           0         2         0
Mon Nov  4 00:15:08 2008   GATOS           0         2         0
Mon Nov  4 00:15:08 2008   GATOS           1         2         0
Mon Nov  4 00:15:08 2008   GATOS           2         2         0
```

[Table 2](#) describes the significant fields shown in the display.

Table 2 *show logging onboard device-version Command Output*

Field	Description
Timestamp	Day, date, and time.
Device Name	Device name.
Instance Num	Number of instances.
Hardware Version	Hardware device version.
Software Version	Software device version.

This example shows how to display the OBFL history information:

```
switch# show logging onboard obfl-history
```

The **show logging onboard obfl-history** command displays the following information:

- Timestamp when OBFL is manually disabled.
- Timestamp when OBFL is manually enabled.
- Timestamp when OBFL data is manually cleared.

This example shows how to display the OBFL kernel stack trace information:

```
switch# show logging onboard stack-trace
```

The **show logging onboard stack-trace** command displays the following information:

- Time in seconds

Send comments to nexus5k-docfeedback@cisco.com

- Time in microseconds
- Error description string
- Current process name and identification
- Kernel jiffies
- Stack trace

Related Commands

Command	Description
clear logging onboard	Clears the OBFL entries in the persistent log.
hw-module logging onboard	Enables or disabled OBFL entries based on the error type.

Send comments to nexus5k-docfeedback@cisco.com

show logging pending

To display the pending changes to the syslog server configuration, use the **show logging pending** command.

show logging pending

Syntax Description This command has no arguments or keywords.

Command Default None

Command Modes EXEC mode

Command History	Release	Modification
	4.0(0)N1(1)	This command was introduced.

Examples This example shows how to display the pending changes to the syslog server configuration:

```
switch# show logging pending
switch#
```

Related Commands	Command	Description
	logging abort	Cancels the pending changes to the syslog server configuration.

Send comments to nexus5k-docfeedback@cisco.com

show logging pending-diff

To display the differences from the current syslog server configuration to the pending changes of the syslog server configuration, use the **show logging pending-diff** command.

show logging pending-diff

Syntax Description This command has no arguments or keywords.

Command Default None

Command Modes EXEC mode

Command History	Release	Modification
	4.0(0)N1(1)	This command was introduced.

Examples This example shows how to display the pending differences of the syslog server configuration:

```
switch# show logging pending-diff
switch#
```

Related Commands	Command	Description
	logging abort	Cancels the pending changes to the syslog server configuration.

Send comments to nexus5k-docfeedback@cisco.com

show logging session status

To display the logging session status, use the **show logging session status** command.

show logging session status

Syntax Description This command has no arguments or keywords.

Command Default None

Command Modes EXEC mode

Command History	Release	Modification
	4.0(0)N1(1a)	This command was introduced.

Examples This example shows how to display the logging session status:

```
switch# show logging session status
```

Related Commands	Command	Description
	logging level	Enables logging messages from a defined facility.

Send comments to nexus5k-docfeedback@cisco.com

show logging server

To display the syslog server configuration, use the **show logging server** command.

show logging server

Syntax Description This command has no arguments or keywords.

Command Default None

Command Modes EXEC mode

Command History	Release	Modification
	4.0(0)N1(1a)	This command was introduced.

Examples This example shows how to display the syslog server configuration:

```
switch# show logging server
```

Related Commands	Command	Description
	logging server	Configures a remote syslog server.

Send comments to nexus5k-docfeedback@cisco.com

show logging status

To display the logging status, use the **show logging status** command.

show logging status

Syntax Description This command has no arguments or keywords.

Command Default None

Command Modes EXEC mode

Release	Modification
4.0(0)N1(1a)	This command was introduced.

Examples This example shows how to display the logging status:

```
switch# show logging status
Fabric Distribute      : Enabled
Session State         : IDLE
switch#
```

Command	Description
logging distribute	Enables the distribution of the syslog server configuration to network switches using the Cisco Fabric Services (CFS) infrastructure.

Send comments to nexus5k-docfeedback@cisco.com

show logging timestamp

To display the logging time-stamp configuration, use the **show logging timestamp** command.

show logging timestamp

Syntax Description This command has no arguments or keywords.

Command Default None

Command Modes EXEC mode

Command History	Release	Modification
	4.0(0)N1(1a)	This command was introduced.

Examples This example shows how to display the logging time-stamp configuration:

```
switch# show logging timestamp
```

Related Commands	Command	Description
	logging timestamp	Configures the logging time stamp granularity.

Send comments to nexus5k-docfeedback@cisco.com

show ntp authentication-status

To display the status of the Network Time Protocol (NTP) authentication, use the **show ntp authentication-status** command.

show ntp authentication-status

Syntax Description This command has no arguments or keywords.

Command Default None

Command Modes Any command mode

Command History	Release	Modification
	5.0(3)N1(1)	This command was introduced.

Examples This example shows how to display the authentication status for NTP:

```
switch(config)# show ntp authentication-status
```

Related Commands	Command	Description
	[no] ntp authenticate	Displays information about NTP peers.

Send comments to nexus5k-docfeedback@cisco.com

show ntp peer-status

To display the status of the Network Time Protocol (NTP) peers, use the **show ntp peer-status** command.

show ntp peer-status

Syntax Description This command has no arguments or keywords.

Command Default None

Command Modes EXEC mode

Command History	Release	Modification
	4.0(0)N1(1a)	This command was introduced.

Examples This example shows how to display the peer status for NTP:

```
switch(config)# show ntp peer-status
```

Related Commands	Command	Description
	show ntp peers	Displays information about NTP peers.

[Send comments to nexus5k-docfeedback@cisco.com](mailto:nexus5k-docfeedback@cisco.com)

show ntp peers

To display information about Network Time Protocol (NTP) peers, use the **show ntp peers** command.

```
show ntp peers
```

Syntax Description This command has no arguments or keywords.

Command Default None

Command Modes EXEC mode

Command History	Release	Modification
	4.0(0)N1(1a)	This command was introduced.

Examples This example shows how to display information about NTP peers:

```
switch(config)# show ntp peers
```

Related Commands	Command	Description
	show ntp peer-status	Displays status information about NTP peers.

[Send comments to nexus5k-docfeedback@cisco.com](mailto:nexus5k-docfeedback@cisco.com)

show ntp statistics

To display Network Time Protocol (NTP) statistics, use the **show ntp statistics** command.

```
show ntp statistics {io | local | memory | peer} {ipaddr address | name name1 [..nameN]}
```

Syntax Description		
io		Displays the input-output statistics.
local		Displays the counters maintained by the local NTP.
memory		Displays the statistics counters related to the memory code.
peer		Displays the per-peer statistics counter of a peer.
ipaddr address		Displays statistics for the peer with the configured IPv4 or IPv6 address. The IPv4 address format is dotted decimal, x.x.x.x. The IPv6 address format is hexadecimal A:B::C:D.
name name1		Displays statistics for a named peer.
..nameN		(Optional) Displays statistics for one or more named peers.

Command Default	
	None

Command Modes	
	EXEC mode

Command History	Release	Modification
	4.0(0)N1(1a)	This command was introduced.

Examples	
	This example shows how to display the statistics for NTP:

```
switch(config)# show ntp statistics local
```

Related Commands	Command	Description
	clear ntp statistics	Clears NTP statistics

Send comments to nexus5k-docfeedback@cisco.com

show ntp timestamp-status

To display the Network Time Protocol (NTP) time-stamp information, use the **show ntp timestamp-status** command.

show ntp timestamp-status

Syntax Description This command has no arguments or keywords.

Command Default None

Command Modes EXEC mode

Command History	Release	Modification
	4.0(0)N1(1a)	This command was introduced.

Examples This example shows how to display the NTP time-stamp status:

```
switch(config)# show ntp timestamp-status
```

Related Commands	Command	Description
	clear ntp statistics	Clears NTP statistics
	ntp	Configures NTP peers and servers on the switch.

[Send comments to nexus5k-docfeedback@cisco.com](mailto:nexus5k-docfeedback@cisco.com)

show ptp brief

To display the PTP information, use the **show ptp brief** command.

show ptp brief

Syntax Description This command has no arguments or keywords.

Command Default None

Command Modes Global configuration mode

Command History	Release	Modification
	5.2(1)N1(1)	This command was introduced.

Examples This example shows how to display the PTP status:

```
switch(config)# show ptp brief
```

Related Commands	Command	Description
	show ptp clock	Displays the properties of the local clock.
	show ptp clocks foreign-masters-record	Displays the state of foreign masters known to the PTP process.
	show ptp corrections	Displays the last few PTP corrections.
	show ptp parent	Displays the properties of the PTP parent and grandmaster clock.
	show ptp port interface	Displays the status of the PTP port.
	show ptp time-property	Displays the PTP clock time properties.

[Send comments to nexus5k-docfeedback@cisco.com](mailto:nexus5k-docfeedback@cisco.com)

show ptp clock

To display the properties of the local PTP clock including clock identity, use the **show ptp clock** command.

show ptp clock

Syntax Description This command has no arguments or keywords.

Command Default None

Command Modes Global configuration mode

Command History	Release	Modification
	5.2(1)N1(1)	This command was introduced.

Examples This example shows how to display the properties of the local clock:

```
switch(config)# show ptp clock
```

Related Commands	Command	Description
	show ptp brief	Displays the PTP status.
	show ptp clocks foreign-masters-record	Displays the state of foreign masters known to the PTP process.
	show ptp corrections	Displays the last few PTP corrections.
	show ptp parent	Displays the properties of the PTP parent and grandmaster clock.
	show ptp port interface	Displays the status of the PTP port.
	show ptp time-property	Displays the PTP clock time properties.

[Send comments to nexus5k-docfeedback@cisco.com](mailto:nexus5k-docfeedback@cisco.com)

show ptp clocks foreign-masters-record

To display the state of the foreign masters known to the PTP process, use the **show ptp clocks foreign-masters-record** command.

```
show ptp clocks foreign-masters-record [ethernet slot/port]
```

Syntax Description

ethernet	Specifies an Ethernet interface.
<i>slot/port</i>	The slot ID and port ID for the Ethernet interface.

Command Modes

Global configuration mode

Command History

Release	Modification
5.2(1)N1(1)	This command was introduced.

Usage Guidelines

For each foreign master, the output displays the clock identity, basic clock properties, and whether the clock is being used as a grandmaster.

Examples

This example shows how to display the foreign masters known to the PTP process:

```
switch(config)# show ptp foreign-masters-record
```

Related Commands

Command	Description
show ptp brief	Displays the PTP status.
show ptp clock	Displays the properties of the local clock.
show ptp corrections	Displays the last few PTP corrections.
show ptp port interface	Displays the status of the PTP port.
show ptp parent	Displays the properties of the PTP parent and grandmaster clock.
show ptp time-property	Displays the PTP clock time properties.

Send comments to nexus5k-docfeedback@cisco.com

show ptp corrections

To display the last few PTP corrections, use the **show ptp corrections** command.

show ptp corrections

Syntax Description There are no arguments or keywords for this command.

Command Default None

Command History	Release	Modification
	5.2(1)N1(1)	This command was introduced.

Examples This example shows how to display the most recent PTP corrections on the switch:

```
switch(config)# show ptp corrections
```

Related Commands	Command	Description
	show ptp brief	Displays the PTP status.
	show ptp clock	Displays the properties of the local clock.
	show ptp clocks foreign-masters-record	Displays the state of foreign masters known to the PTP process.
	show ptp port interface	Displays the status of the PTP port.
	show ptp parent	Displays the properties of the PTP parent and grandmaster clock.
	show ptp time-property	Displays the PTP clock time properties.

Send comments to nexus5k-docfeedback@cisco.com

show ptp parent

To display the properties of the PTP parent and grandmaster clock, use the **show ptp parent** command.

show ptp parent

Syntax Description There are no arguments or keywords for this command.

Command Default None

Command History	Release	Modification
	5.2(1)N1(1)	This command was introduced.

Examples This example shows how to display the properties of the PTP parent and grandmaster clock:

```
switch(config)# show ptp parent
```

Related Commands	Command	Description
	show ptp brief	Displays the PTP status.
	show ptp clock	Displays the properties of the local clock.
	show ptp clocks foreign-masters-recor d	Displays the state of foreign masters known to the PTP process.
	show ptp corrections	Displays the last few PTP corrections.
	show ptp port interface	Displays the status of the PTP port.
	show ptp time-property	Displays the PTP clock time properties.

[Send comments to nexus5k-docfeedback@cisco.com](mailto:nexus5k-docfeedback@cisco.com)

show ptp port interface

To display the status of the PTP port, use the **show ptp port interface ethernet** command.

```
show ptp port interface [ethernet slot/port]
```

Syntax Description	ethernet	Specifies an Ethernet interface.
	slot/port	The slot ID and port ID for the Ethernet interface.

Command Default None

Command Modes Global configuration mode

Command History	Release	Modification
	5.2(1)N1(1)	This command was introduced.

Examples This example shows how to display the status of the PTP port on the switch:

```
switch(config)# show ptp port interface ethernet 5/1
```

Related Commands	Command	Description
	show ptp brief	Displays the PTP status.
	show ptp clock	Displays the properties of the local clock.
	show ptp clocks foreign-masters-record	Displays the state of foreign masters known to the PTP process.
	show ptp corrections	Displays the last few PTP corrections.
	show ptp port interface	Displays the status of the PTP port.
	show ptp parent	Displays the properties of the PTP parent and grandmaster clock.
	show ptp time-property	Displays the PTP clock time properties.

[Send comments to nexus5k-docfeedback@cisco.com](mailto:nexus5k-docfeedback@cisco.com)

show ptp time-property

To display the PTP clock time properties, use the **show ptp time-property** command.

```
show ptp time-property
```

Syntax Description There are no arguments or keywords for this command.

Command Default None

Command History	Release	Modification
	5.2(1)N1(1)	This command was introduced.

Examples This example shows how to display the PTP clock time properties:

```
switch(config)# show ptp time-property
```

Related Commands	Command	Description
	show ptp brief	Displays the PTP status.
	show ptp clock	Displays the properties of the local clock.
	show ptp clocks foreign-masters-recor d	Displays the state of foreign masters known to the PTP process.
	show ptp corrections	Displays the last few PTP corrections.
	show ptp parent	Displays the properties of the PTP parent and grandmaster clock.
	show ptp port interface	Displays the status of the PTP port.

Send comments to nexus5k-docfeedback@cisco.com

show snmp community

To display the Simple Network Management Protocol (SNMP) community strings configured on the switch, use the **show snmp community** command.

show snmp community

Syntax Description This command has no arguments or keywords.

Command Default None

Command Modes EXEC mode

Command History	Release	Modification
	4.0(0)N1(1)	This command was introduced.

Examples This example shows how to display the SNMP community strings:

```
switch# show snmp community
Community          Group / Access      context      acl_filter
-----          -
public            network-admin
switch#
```

Related Commands	Command	Description
	snmp-server community	Configures the community access string to permit access to the SNMP protocol.

Send comments to nexus5k-docfeedback@cisco.com

show snmp context

To display the Simple Network Management Protocol (SNMP) contexts configured on the switch, use the **show snmp context** command.

show snmp context

Syntax Description This command has no arguments or keywords.

Command Default None

Command Modes EXEC mode

Command History	Release	Modification
	4.0(0)N1(1)	This command was introduced.

Examples This example shows how to display the SNMP contexts:

```
switch# show snmp context
```

Related Commands	Command	Description
	snmp-server context	Configures an SNMP context.

Send comments to nexus5k-docfeedback@cisco.com

show snmp engineID

To display the identification of the local Simple Network Management Protocol (SNMP) engine, use the **show snmp engineID** command.

show snmp engineID

Syntax Description This command has no arguments or keywords.

Command Default None

Command Modes EXEC mode

Command History	Release	Modification
	4.0(0)N1(1)	This command was introduced.

Usage Guidelines An SNMP engine is a copy of SNMP that can reside on a local or remote device. SNMP passwords are localized using the SNMP engine ID of the authoritative SNMP engine.

Examples This example shows how to display the SNMP engine ID:

```
switch# show snmp engineID
Local SNMP engineID: [Hex] 8000000903000DECB230C0
                    [Dec] 128:000:000:009:003:000:013:236:178:048:192
switch#
```

Related Commands	Command	Description
	show running-config snmp	Displays the running configuration information about SNMP.

[Send comments to nexus5k-docfeedback@cisco.com](mailto:nexus5k-docfeedback@cisco.com)

show snmp group

To display the names of the Simple Network Management Protocol (SNMP) groups configured on the switch, use the **show snmp group** command.

show snmp group

Syntax Description This command has no arguments or keywords.

Command Default None

Command Modes EXEC mode

Command History	Release	Modification
	4.0(0)N1(1)	This command was introduced.

Examples This example shows how to display the SNMP groups:

```
switch# show snmp group
```

```
Role: network-admin
```

```
Description: Predefined network admin role has access to all commands on the switch
```

```
-----
Rule    Perm   Type      Scope      Entity
-----
1       permit read-write
```

```
Role: network-operator
```

```
Description: Predefined network operator role has access to all read commands on the switch
```

```
-----
Rule    Perm   Type      Scope      Entity
-----
1       permit read
```

```
Role: vdc-admin
```

```
Description: Predefined vdc admin role has access to all commands within a VDC instance
```

```
-----
Rule    Perm   Type      Scope      Entity
-----
1       permit read-write
```

```
Role: vdc-operator
```

```
Description: Predefined vdc operator role has access to all read commands within a VDC instance
```

```
-----
Rule    Perm   Type      Scope      Entity
-----
1       permit read
```

Send comments to nexus5k-docfeedback@cisco.com

```
Role: priv-3
Description: This is a system defined privilege role.
vsan policy: permit (default)
Vlan policy: permit (default)
Interface policy: permit (default)
Vrf policy: permit (default)
```

```
Role: priv-2
Description: This is a system defined privilege role.
vsan policy: permit (default)
Vlan policy: permit (default)
Interface policy: permit (default)
Vrf policy: permit (default)
```

```
Role: priv-1
Description: This is a system defined privilege role.
vsan policy: permit (default)
Vlan policy: permit (default)
Interface policy: permit (default)
Vrf policy: permit (default)
```

```
Role: priv-0
Description: This is a system defined privilege role.
vsan policy: permit (default)
Vlan policy: permit (default)
Interface policy: permit (default)
Vrf policy: permit (default)
```

```
-----
```

Rule	Perm	Type	Scope	Entity
10	permit	command		traceroute6 *
9	permit	command		traceroute *
8	permit	command		telnet6 *
7	permit	command		telnet *
6	permit	command		ping6 *
5	permit	command		ping *
4	permit	command		ssh6 *
3	permit	command		ssh *
2	permit	command		enable *
1	permit	read		

```
Role: priv-15
Description: This is a system defined privilege role.
vsan policy: permit (default)
Vlan policy: permit (default)
Interface policy: permit (default)
Vrf policy: permit (default)
```

```
-----
```

Rule	Perm	Type	Scope	Entity
1	permit	read-write		

```
switch#
```

Related Commands

Command	Description
show running-config snmp	Displays the running configuration information about SNMP.

Send comments to nexus5k-docfeedback@cisco.com

show snmp host

To display the Simple Network Management Protocol (SNMP) host information, use the **show snmp host** command.

show snmp host

Syntax Description This command has no arguments or keywords.

Command Default None

Command Modes EXEC mode

Command History	Release	Modification
	4.0(0)N1(1)	This command was introduced.

Examples This example shows how to display the SNMP host:

```
switch# show snmp host
```

Related Commands	Command	Description
	snmp-server host	Configures an SNMP host.

Send comments to nexus5k-docfeedback@cisco.com

show snmp sessions

To display the current Simple Network Management Protocol (SNMP) sessions, use the **show snmp sessions** command.

show snmp sessions

Syntax Description This command has no arguments or keywords.

Command Default None

Command Modes EXEC mode

Command History	Release	Modification
	4.0(0)N1(1)	This command was introduced.

Examples This example shows how to display the SNMP sessions:

```
switch# show snmp sessions
```

Related Commands	Command	Description
	show running-config snmp	Displays the running configuration information about SNMP.

Send comments to nexus5k-docfeedback@cisco.com

show snmp trap

To display the Simple Network Management Protocol (SNMP) link trap generation information, use the **show snmp trap** command.

show snmp trap

Syntax Description This command has no arguments or keywords.

Command Default None

Command Modes EXEC mode

Command History	Release	Modification
	4.0(0)N1(1)	This command was introduced.

Examples This example shows how to display the SNMP traps:

```
switch# show snmp trap
```

```
-----
Trap type           Description           Enabled
-----
entity              : entity_mib_change   Yes
entity              : entity_module_status_change   Yes
entity              : entity_power_status_change   Yes
entity              : entity_module_inserted   Yes
entity              : entity_module_removed   Yes
entity              : entity_unrecognised_module   Yes
entity              : entity_fan_status_change   Yes
link                : linkDown            Yes
link                : linkUp              Yes
link                : IETF-extended-linkDown   Yes
link                : IETF-extended-linkUp    Yes
link                : cisco-extended-linkDown  Yes
link                : cisco-extended-linkUp   Yes
callhome            : event-notify        No
callhome            : smtp-send-fail       No
cfs                 : state-change-notif   No
cfs                 : merge-failure        No
rf                  : redundancy_framework  Yes
aaa                 : server-state-change   No
license             : notify-license-expiry  Yes
license             : notify-no-license-for-feature  Yes
license             : notify-licensefile-missing  Yes
license             : notify-license-expiry-warning  Yes
zone                : unsupp-mem          No
upgrade             : UpgradeOpNotifyOnCompletion  Yes
upgrade             : UpgradeJobStatusNotify  Yes
feature-control     : FeatureOpStatusChange  No
sysmgr              : cseFailSwCoreNotifyExtended  No
rmon                : risingAlarm          No
-----
```

Send comments to nexus5k-docfeedback@cisco.com

```

rmon          : fallingAlarm          No
rmon          : hcRisingAlarm         No
rmon          : hcFallingAlarm        No
config        : ccmCLIRunningConfigChanged No
snmp          : authentication        No
bridge        : topologychange        No
bridge        : newroot               No
stp           : inconsistency          No
stp           : loop-inconsistency    No
stp           : root-inconsistency    No
switch#

```

Related Commands

Command	Description
snmp trap link-status	Enables SNMP link trap generation.

[Send comments to nexus5k-docfeedback@cisco.com](mailto:nexus5k-docfeedback@cisco.com)

show snmp user

To display information on each Simple Network Management Protocol (SNMP) user, use the **show snmp user** command.

show snmp user

Syntax Description This command has no arguments or keywords.

Command Default None

Command Modes EXEC mode

Command History

Release	Modification
4.1(3)N2(1)	This command was introduced.

Examples

This example shows how to display the SNMP users configured on the switch:

```
switch# show snmp user
```

```

SNMP USERS
-----
User                               Auth  Priv(enforce)  Groups
-----
admin                               md5    des(no)         network-admin

NOTIFICATION TARGET USERS (configured for sending V3 Inform)
-----
User                               Auth  Priv
-----
switch#
```

This example shows how to display information about a specific SNMP user:

```
switch# show snmp user admin
switch#
```

Related Commands

Command	Description
snmp-server user	Configures a new user to an SNMP group.

[Send comments to nexus5k-docfeedback@cisco.com](mailto:nexus5k-docfeedback@cisco.com)

show system ethernet dom polling status

To display the status of transceiver digital optical monitoring periodic polling, use the **show system ethernet dom polling status** command.

```
show system ethernet dom polling status
```

Syntax Description This command has no arguments or keywords

Command Default None

Command Modes EXEC mode

Command History	Release	Modification
	5.2(1)N1(5)	This command was introduced.

Usage Guidelines Use this command to display the status of transceiver digital optical monitoring periodic polling.

Examples This example shows how to display the status of transceiver digital optical monitoring periodic polling:

```
switch# show system ethernet dom polling status
Ethernet DOM Polling Status: enabled
```

Related Commands	Command	Description
	system ethernet dom polling	Enables transceiver digital optical monitoring periodic polling.

■ show system ethernet dom polling status

Send comments to nexus5k-docfeedback@cisco.com