

INDEX

A

Active/Active FEX Topology [1-13](#)

B

buffer

configuration guidelines [1-8](#)

buffering

switch profile configuration [1-8](#)

C

CFS/IP

configuring [1-4](#)

CFS protocol [1-4](#)

channel group

failure [1-32](#)

workaround [1-32](#)

Cisco Fabric Services over IP

about [1-4](#)

requirements [1-2](#)

Cisco Nexus 5000 Series switch

reloading [1-26](#)

synchronizing peer switches after a reload [1-27](#)

commit

about [1-8](#)

best practice [1-8](#)

command [1-8](#)

order dependency for commands [1-8](#)

process duration [1-8](#)

unreachable peer [1-26](#)

unsuccessful [1-8, 1-9, 1-31](#)

config-sync mode [1-5](#)

supported commands [1-6](#)

configuration modes

selecting [1-33](#)

configuration rollback [1-9](#)

conditional features

limitation [1-31](#)

workaround [1-31](#)

configuration synchronization [1-1](#)

benefits [1-2](#)

best practices [1-9](#)

configuration examples [1-10](#)

configuring a dual-homed FEX topology
(Active/Active FEX topology) [1-13](#)

configuring an existing deployment with an A/A
topology [1-17](#)

configuring a vPC topology using configuration
synchronization [1-10](#)

definition [1-33](#)

guidelines [1-2](#)

limitations [1-3](#)

configuration rollback [1-3](#)

FCoE [1-3](#)

feature commands [1-3](#)

new deployment in a vPC topology and
straight-through FEX topology [1-21](#)

requirements [1-2](#)

switch vPC topology and straight-through FEX
topology (host vPC) [1-19](#)

D

dual-homed A/A topology

configuring [1-14](#)

Send documentation comments to n5kdocfeedback@cisco.com

E

Etherchannel [1-1](#)

F

Fabric Extender (FEX)

pre-provisioning [1-2](#)

FEX

configuring a FEX in an A/A topology [1-14](#)

how to provision [1-29](#)

straight-through topology [1-20](#)

G

Gigabit Expansion Module (GEM)

pre-provisioning [1-2](#)

I

import

abort [1-9](#)

configuration changes during [1-9](#)

methods [1-18, 1-24](#)

importing switch profile commands

about [1-9](#)

initiator switch [1-8](#)

M

merge checks [1-8](#)

mgmt0 interface [1-4](#)

lost connectivity [1-31](#)

mutual exclusion check

about [1-7](#)

command exceptions [1-7](#)

failure [1-7](#)

P

peer keepalive

configuring [1-11](#)

peer switch

running configuration in a vPC topology [1-11](#)

running configuration of FEX in A/A topology [1-14](#)

policies

synchronizing [1-22](#)

port channel members

peer switch requirements [1-23](#)

port-profiles [1-9](#)

pre-provisioning [1-9](#)

FEX in dual-homed topology [1-17](#)

offline interfaces [1-16, 1-23](#)

R

Role Based Access Control (RBAC)

switch profile requirements [1-6](#)

S

straight-through topology

diagram [1-20](#)

switch profile

configuration modes [1-33](#)

definition [1-33](#)

switch profiles [1-1](#)

about [1-5](#)

commands

not supported [1-6](#)

supported [1-6](#)

commit

requirements [1-7](#)

copying commands to [1-9](#)

creating [1-5](#)

limit [1-6](#)

naming [1-6](#)

Send documentation comments to n5kdocfeedback@cisco.com

synchronization

configuration changes made during [1-8](#)

T

terminology [1-33](#)

U

User-Based Access Controls

about [1-6](#)

V

Verification Checks [1-7](#)

vPC

Active/Active topology [1-3](#)

and straight-through FEX topologies [1-19](#)

and straight-through FEX topology

existing deployments [1-24](#)

configurations [1-3](#)

configuring [1-3, 1-11](#)

consistency check [1-1](#)

peer-config-check-bypass best practice [1-11](#)

peer-link failure [1-28](#)

straight-through topology

running configuration example [1-21](#)

topology [1-1](#)

topology diagram [1-3](#)

vPC topologies

running different versions of Cisco NX-OS [1-7](#)

vPC topology

and straight-through FEX topology new
deployment [1-21](#)

Send documentation comments to n5kdocfeedback@cisco.com