



New and Changed Information

This chapter provides release-specific information for each new and changed feature in the *Cisco Nexus 9000 Series NX-OS FC-NPV and FCoE-NPV Configuration Guide*.

- [New and Changed Information](#), on page 1

New and Changed Information

Table 1: New and Changed Features for Release 9.3(x)

Feature	Description	Changed in Release	Where Documented
25G FCoE Support	Added 25G adapter QL41212H support.	9.3(5)	FC-NPV and FCoE-NPV Supported Hardware
FCoE host over vPC with FC Uplinks	Added support for FCoE host over vPC with FC Uplinks.	9.3(5)	Cisco Nexus 9000 Series Switch vPC Configuration Example Cisco Nexus 9000 Series Switch FCoE Configuration Example
FC-NPV and FCoE-NPV on N9K-93360YC-FX2	Added support for Cisco Nexus 93360YC-FX2 switches.	9.3(5)	FC-NPV and FCoE-NPV Supported Hardware
Standard ISSU	Added support for ISSU.	9.3(5)	FC-NPV and FCoE-NPV Supported Hardware
FC FCoE-NPV	Merged FC-NPV feature information into the new Cisco Nexus 9000 Series NX-OS FC-NPV and FCoE-NPV Configuration Guide	9.3(3)	

