

Send document comments to nexus7k-docfeedback@cisco.com.



U Commands

This chapter describes the Cisco NX-OS security commands that begin with U.

use-vrf

Send document comments to nexus7k-docfeedback@cisco.com.

use-vrf

To specify a virtual routing and forwarding instance (VRF) name for a RADIUS, TACACS+, or LDAP server group, use the **use-vrf** command. To remove the VRF name, use the **no** form of this command.

use-vrf *vrf-name*

no use-vrf *vrf-name*

Syntax Description	<i>vrf-name</i> VRF name. The name is case sensitive.						
Defaults	None						
Command Modes	RADIUS server group configuration TACACS+ server group configuration LDAP server group configuration						
SupportedUserRoles	network-admin vdc-admin						
Command History	<table border="1"> <thead> <tr> <th>Release</th> <th>Modification</th> </tr> </thead> <tbody> <tr> <td>5.0(2)</td> <td>Added support for LDAP server groups.</td> </tr> <tr> <td>4.0(1)</td> <td>This command was introduced.</td> </tr> </tbody> </table>	Release	Modification	5.0(2)	Added support for LDAP server groups.	4.0(1)	This command was introduced.
Release	Modification						
5.0(2)	Added support for LDAP server groups.						
4.0(1)	This command was introduced.						

Send document comments to nexus7k-docfeedback@cisco.com.

Usage Guidelines

You can configure only one VRF instance for a server group.

Use the **aaa group server radius** command to enter RADIUS server group configuration mode, the **aaa group server tacacs+** command to enter TACACS+ server group configuration mode, or the **aaa group server ldap** command to enter LDAP server group configuration mode.

If the server is not found, use the **radius-server host** command, the **tacacs-server host** command, or the **ldap-server host** command to configure the server.



Note You must use the **feature tacacs+** command before you configure TACACS+ or the **feature ldap** command before you configure LDAP.

This command does not require a license.

Examples

This example shows how to specify a VRF name for a RADIUS server group:

```
switch# config t
switch(config)# aaa group server radius RadServer
switch(config-radius)# use-vrf vrf1
```

This example shows how to specify a VRF name for a TACACS+ server group:

```
switch# config t
switch(config)# feature tacacs+
switch(config)# aaa group server tacacs+ TacServer
switch(config-tacacs+)# use-vrf vrf2
```

This example shows how to remove the VRF name from a TACACS+ server group:

```
switch# config t
switch(config)# feature tacacs+
switch(config)# aaa group server tacacs+ TacServer
switch(config-tacacs+)# no use-vrf vrf2
```

This example shows how to specify a VRF name for an LDAP server group:

```
switch# config t
switch(config)# feature ldap
switch(config)# aaa group server ldap LdapServer
switch(config-tacacs+)# use-vrf vrf3
```

This example shows how to remove the VRF name from an LDAP server group:

```
switch# config t
switch(config)# feature ldap
switch(config)# aaa group server ldap LdapServer
switch(config-tacacs+)# no use-vrf vrf3
```

Related Commands

Command	Description
aaa group server	Configures AAA server groups.
radius-server host	Configures a RADIUS server.
show ldap-server groups	Displays LDAP server information.
show radius-server groups	Displays RADIUS server information.
show tacacs-server groups	Displays TACACS+ server information.

use-vrf

Send document comments to nexus7k-docfeedback@cisco.com.

Command	Description
feature ldap	Enables LDAP.
feature tacacs+	Enables TACACS+.
ldap-server host	Configures an LDAP server.
tacacs-server host	Configures a TACACS+ server.
vrf	Configures a VRF instance.

Send document comments to nexus7k-docfeedback@cisco.com.

user-certdn-match

To configure the attribute name, search filter, and base-DN for the certificate DN match search operation in order to send a search query to the Lightweight Directory Access Protocol (LDAP) server, use the **user-certdn-match** command. To disable this configuration, use the **no** form of this command.

```
user-certdn-match attribute-name attribute-name search-filter filter base-DN base-DN-name
no user-certdn-match
```

Syntax Description	attribute-name <i>attribute-name</i> Specifies the attribute name of the LDAP search map. The name is alphanumeric, case sensitive, and has a maximum of 128 characters. search-filter <i>filter</i> Specifies the filter for the LDAP search map. The name is alphanumeric, case sensitive, and has a maximum of 128 characters. base-DN <i>base-DN-name</i> Specifies the base designated name for the LDAP search map. The name is alphanumeric, case sensitive, and has a maximum of 128 characters.
--------------------	---

Defaults	None				
Command Modes	LDAP search map configuration				
Supported User Roles	network-admin vdc-admin				
Command History	<table border="1"> <thead> <tr> <th>Release</th> <th>Modification</th> </tr> </thead> <tbody> <tr> <td>5.0(2)</td> <td>This command was introduced.</td> </tr> </tbody> </table>	Release	Modification	5.0(2)	This command was introduced.
Release	Modification				
5.0(2)	This command was introduced.				

Usage Guidelines	To use this command, you must enable LDAP. This command does not require a license.
------------------	--

Examples	This example shows how to configure the attribute name, search filter, and base-DN for the certificate DN match search operation in order to send a search query to the LDAP server: <pre>switch# conf t switch(config)# ldap search-map s0 switch(config-ldap-search-map)# user-certdn-match attribute-name certificateDN search-filter (&(objectClass=inetOrgPerson)(cn=\$userid)) base-DN dc=acme,dc=com switch(config-ldap-search-map)# </pre>
----------	--

user-certdn-match

Send document comments to nexus7k-docfeedback@cisco.com.

Related Commands	Command	Description
	feature ldap	Enables LDAP.
	ldap search-map	Configures an LDAP search map.
	show ldap-search-map	Displays the configured LDAP search maps.

Send document comments to nexus7k-docfeedback@cisco.com.

user-pubkey-match

To configure the attribute name, search filter, and base-DN for the public key match search operation in order to send a search query to the Lightweight Directory Access Protocol (LDAP) server, use the **user-pubkey-match** command. To disable this configuration, use the **no** form of this command.

```
user-pubkey-match attribute-name attribute-name search-filter filter base-DN base-DN-name
no user-pubkey-match
```

Syntax Description	attribute-name <i>attribute-name</i>	Specifies the attribute name of the LDAP search map. The name is alphanumeric, case sensitive, and has a maximum of 128 characters.
Defaults	None	
Command Modes	LDAP search map configuration	
Supported User Roles	network-admin vdc-admin	
Command History	Release	Modification
	5.0(2)	This command was introduced.

Usage Guidelines To use this command, you must enable LDAP.

This command does not require a license.

Examples This example shows how to configure the attribute name, search filter, and base-DN for the public key match search operation in order to send a search query to the LDAP server:

```
switch# conf t
switch(config)# ldap search-map s0
switch(config-ldap-search-map)# user-pubkey-match attribute-name sshPublicKey
search-filter (&(objectClass=inetOrgPerson)(cn=$userid)) base-DN dc=acme,dc=com
switch(config-ldap-search-map)#
switch#
```

■ user-pubkey-match

Send document comments to nexus7k-docfeedback@cisco.com.

Related Commands	Command	Description
	feature ldap	Enables LDAP.
	ldap search-map	Configures an LDAP search map.
	show ldap-search-map	Displays the configured LDAP search maps.

Send document comments to nexus7k-docfeedback@cisco.com.

user-switch-bind

To configure the attribute name, search filter, and base-DN for the user-switchgroup search operation in order to send a search query to the Lightweight Directory Access Protocol (LDAP) server, use the **user-switch-bind** command. To disable this configuration, use the **no** form of this command.

user-switch-bind attribute-name *attribute-name* search-filter *filter* base-DN *base-DN-name*
no user-switch-bind

Syntax Description	attribute-name <i>attribute-name</i> Specifies the attribute name of the LDAP search map. The name is alphanumeric, case sensitive, and has a maximum of 128 characters.
	search-filter <i>filter</i> Specifies the filter for the LDAP search map. The name is alphanumeric, case sensitive, and has a maximum of 128 characters.
	base-DN <i>base-DN-name</i> Specifies the base designated name for the LDAP search map. The name is alphanumeric, case sensitive, and has a maximum of 128 characters.

Defaults	None
----------	------

Command Modes	LDAP search map configuration
---------------	-------------------------------

Supported User Roles	network-admin vdc-admin
----------------------	----------------------------

Command History	Release	Modification
	5.0(2)	This command was introduced.

Usage Guidelines	To use this command, you must enable LDAP. This command does not require a license.
------------------	--

Examples	This example shows how to configure the attribute name, search filter, and base-DN for the user-switchgroup search operation in order to send a search query to the LDAP server:
	<pre>switch# conf t switch(config)# ldap search-map s0 switch(config-ldap-search-map)# user-switch-bind attribute-name memberuid search-filter (&(objectClass=posixGroup)(cn=dccgroup)) base-DN dc=acme,dc=com switch(config-ldap-search-map)# </pre>

user-switch-bind

Send document comments to nexus7k-docfeedback@cisco.com.

Related Commands	Command	Description
	feature ldap	Enables LDAP.
	ldap search-map	Configures an LDAP search map.
	show ldap-search-map	Displays the configured LDAP search maps.

Send document comments to nexus7k-docfeedback@cisco.com.

username

To create and configure a user account in a virtual device context (VDC), use the **username** command. To remove a user account, use the **no** form of this command.

```
username user-id [expire date] [password [0 | 5] password] [role role-name]
username user-id [sshkey {key | file filename}]
username user-id [keypair generate {rsa [bits [force]] | dsa [force]}]
username user-id [keypair {export | import} {bootflash:filename | volatile:filename} {rsa | dsa}
[force]]
username user-id [priv-lvl n] [expire date] [password [0 | 5] password]
no username user-id
```

Syntax Description	
<i>user-id</i>	User identifier for the user account. The <i>user-id</i> argument is a case-sensitive, alphanumeric character string with a maximum length of 28 characters. For more information, see the usage guidelines section below. Note The Cisco NX-OS software allows these special characters in the <i>user-id</i> argument text string: (_ . + = \ -).
expire <i>date</i>	(Optional) Specifies the expire date for the user account. The format for the <i>date</i> argument is YYYY-MM-DD.
password	(Optional) Specifies a password for the account. The default is no password.
0	(Optional) Specifies that the password is in clear text. Clear text passwords are encrypted before they are saved to the running configuration.
5	(Optional) Specifies that the password is in encrypted format. Encrypted passwords are not changed before they are saved to the running configuration.
<i>password</i>	Password string. The password is alphanumeric, case sensitive, and has a maximum of 64 characters. Note All printable ASCII characters are supported in the password string if they are enclosed in quotation marks.
role <i>role-name</i>	(Optional) Specifies the user role. The <i>role-name</i> argument is case sensitive.
sshkey	(Optional) Specifies an SSH key for the user account.
<i>key</i>	SSH key string.
file <i>filename</i>	Specifies the name of a file that contains the SSH key string.
keypair	Generates SSH user keys.
generate	Generates SSH key-pairs.
rsa	Generates Rivest, Shamir, and Adelman (RSA) keys.
bits	Number of bits used to generate the key. The range is from 1024 to 2048, and the default value is 1024.
force	Forces the generation of keys even if previous ones are present.
dsa	Generates Digital System Algorithm (DSA) keys.

username

Send document comments to nexus7k-docfeedback@cisco.com.

export	Exports key-pairs to the bootflash or volatile directory.
import	Imports key-pairs from the bootflash or volatile directory.
bootflash:filename	Specifies the bootflash filename.
volatile:filename	Specifies the remote filename.
priv-lvl n	Specifies the privilege level to which the user is assigned. The range is from 0 to 15.

Defaults

Unless specified, usernames have no expire date, password, or SSH key.

In the default VDC, the default role is network-operator if the creating user has the network-admin role, or the default role is vdc-operator if the creating user has the vdc-admin role.

In nondefault VDCs, the default user role is vdc-operator.

You cannot delete the default admin user role. Also, you cannot change the expire date or remove the network-admin role for the default admin user role.

To specify privilege levels, you must enable the cumulative privilege of roles for command authorization on TACACS+ servers using the **feature privilege** command. There is no default privilege level.

This command does not require a license.

Command Modes

Global configuration

SupportedUserRoles

network-admin
vdc-admin

Command History

Release	Modification
5.1(1)	Removed support for RSA keys less than 1024 bits.
5.0(2)	Added the keypair keyword option.
5.0(2)	Added the priv-lvl keyword option.
4.1(2)	Added the sshkey keyword option.
4.0(1)	This command was introduced.

Usage Guidelines

The Cisco NX-OS software creates two default user accounts in the VDC: admin and adminbackup. The nondefault VDCs have one default user account: admin. You cannot remove a default user account.

User accounts are local to the VDCs. You can create user accounts with the same user identifiers in different VDCs.



Caution

The Cisco NX-OS software does not support all numeric usernames, whether created with TACACS+ or RADIUS, or created locally. Local users with all numeric names cannot be created. If an all numeric user name exists on an AAA server and is entered during login, the user is not logged in.

Send document comments to nexus7k-docfeedback@cisco.com.

The Cisco NX-OS software accepts only strong passwords when you have password-strength checking enabled using the **password strength-check** command. The characteristics of a strong password include the following:

- At least eight characters long
- Does not contain many consecutive characters (such as “abcd”)
- Does not contain many repeating characters (such as “aaabbb”)
- Does not contain dictionary words
- Does not contain proper names
- Contains both uppercase and lowercase characters
- Contains numbers



If you do not specify a password for the user account, the user might not be able to log in to the account.

To use this command, you must enable the cumulative privilege of roles using the **feature privilege** command.

A passphrase is required when you export or import the key-pair. The passphrase encrypts the exported private key for the user and decrypts it during import.

This command does not require a license.

Examples

This example shows how to create a user account with a password and a user role:

```
switch# config t
switch(config)# username user1 password Ci5co321 role vdc-admin
```

This example shows how to configure the SSH key for a user account:

```
switch# config t
switch(config)# username user1 sshkey file bootflash:key_file
```

This example shows how to generate the SSH public and private keys and store them in the home directory of the Cisco NX-OS device for the user:

```
switch# config t
switch(config)# username user1 keypair generate rsa
generating rsa key(2048 bits).....
generated rsa key
```

username

Send document comments to nexus7k-docfeedback@cisco.com.

This example shows how to export the public and private keys from the home directory of the Cisco NX-OS device to the bootflash directory:

```
switch# config t
switch(config)# username user1 keypair export bootflash:key_rsa rsa
Enter Passphrase:
switch(config)# dir
.
.
.
951 Jul 09 11:13:59 2009 key_rsa
221 Jul 09 11:14:00 2009 key_rsa.pub
.
```

The private key is exported as the file that you specify, and the public key is exported with the same filename followed by a .pub extension.

This example shows how to import the exported public and private keys from the bootflash directory to the home directory of the Cisco NX-OS device:

```
switch# config t
switch(config)# username user1 keypair import bootflash:key_rsa rsa
Enter Passphrase:
switch(config)# show username user1 keypair
*****
rsa Keys generated: Thu Jul 9 11:10:29 2009
ssh-rsa
AAAAB3NzaC1yc2EAAAABIwAAAIEAxWmjJT+oQhIcvnrMbx2BmD0P8boZE1TfJ
Fx9fexWp6rOiztlw0DtehnjadWc6A+DE2DvYNvqsrU9TBypYDPQkR/+Y6cKubyFW
VxSBG/NHztQc3+QC1zdkIxGNjbEHyFoajzNEO8LLOVFIMCZ2Td7gxUGRZc+fbq
S33GZsCAX6v0=
bitcount:262144
fingerprint:
8d:44:ee:6c:ca:0b:44:95:36:d0:7d:f2:b5:78:74:7d
*****
could not retrieve dsa key information
*****
switch(config)#

```

The private key is imported as the file that you specify, and the public key is imported with the same filename followed by a .pub extension.

This example shows how to assign privilege level 15 to the user:

```
switch# config t
switch(config)# feature privilege
switch(config)# enable secret 5 def456 priv-lvl 15
switch(config)# username user2 priv-lvl 15
```

Related Commands

Command	Description
enable level	Enables a user to move to a higher privilege level.
enable secret priv-lvl	Enables a secret password for a specific privilege level.
feature privilege	Enables the cumulative privilege of roles for command authorization on TACACS+ servers.
password strength-check	Checks the password security strength.

Send document comments to nexus7k-docfeedback@cisco.com.

Command	Description
show privilege	Displays the current privilege level, username, and status of cumulative privilege support.
show user-account	Displays the user account configuration.
show username	Displays the public key for the specified user.

userprofile

Send document comments to nexus7k-docfeedback@cisco.com.

userprofile

To configure the attribute name, search filter, and base-DN for the user profile search operation in order to send a search query to the Lightweight Directory Access Protocol (LDAP) server, use the **userprofile** command. To disable this configuration, use the **no** form of this command.

userprofile attribute-name *attribute-name* search-filter *filter* base-DN *base-DN-name*

no userprofile

Syntax Description

attribute-name <i>attribute-name</i>	Specifies the attribute name of the LDAP search map. The name is alphanumeric, case sensitive, and has a maximum of 128 characters.
search-filter <i>filter</i>	Specifies the filter for the LDAP search map. The name is alphanumeric, case sensitive, and has a maximum of 128 characters.
base-DN <i>base-DN-name</i>	Specifies the base designated name for the LDAP search map. The name is alphanumeric, case sensitive, and has a maximum of 128 characters.

Defaults

None

Command Modes

LDAP search map configuration

SupportedUserRoles

network-admin
vdc-admin

Command History

Release	Modification
5.0(2)	This command was introduced.

Usage Guidelines

To use this command, you must enable LDAP.

This command does not require a license.

Examples

This example shows how to configure the attribute name, search filter, and base-DN for the user profile search operation in order to send a search query to the LDAP server:

```
switch# conf t
switch(config)# ldap search-map s0
switch(config-ldap-search-map)# userprofile attribute-name description search-filter
(&(objectClass=inetOrgPerson)(cn=$userid)) base-DN dc=acme,dc=com
switch(config-ldap-search-map)#
switch#
```

Send document comments to nexus7k-docfeedback@cisco.com.

Related Commands	Command	Description
	feature ldap	Enables LDAP.
	ldap search-map	Configures an LDAP search map.
	show ldap-search-map	Displays the configured LDAP search maps.

■ userprofile

Send document comments to nexus7k-docfeedback@cisco.com.