



Numerics

802.1D

See STP

802.1Q

and trunk ports [10-3](#)

configuration limitations [12-19](#)

encapsulation [12-16](#)

native VLAN for untagged traffic [12-23](#)

tunneling

compatibility with other features [16-6](#)

defaults [16-4](#)

described [16-1](#)

tunnel ports with other features [16-6](#)

802.1s

See MSTP

802.1w

See RSTP

802.1x

See port-based authentication

802.3ad

See EtherChannel

802.3af

See PoE

802.3z flow control [10-18](#)

A

abbreviating commands [2-3](#)

ABRs [34-24](#)

access-class command [31-20](#)

access control entries

See ACEs

access-denied response, VMPS [12-28](#)

access groups

applying ACLs to interfaces [31-21](#)

IP [31-21](#)

Layer 2 [31-21](#)

Layer 3 [31-21](#)

access lists

See ACLs

access ports

and Layer 2 protocol tunneling [16-11](#)

defined [10-3](#)

accounting

with 802.1x [9-5, 9-20](#)

with RADIUS [8-28](#)

with TACACS+ [8-11, 8-17](#)

ACEs

and QoS [32-7](#)

defined [31-2](#)

Ethernet [31-2](#)

IP [31-2](#)

ACLs

ACEs [31-2](#)

any keyword [31-13](#)

applying

on bridged packets [31-39](#)

on multicast packets [31-40](#)

on routed packets [31-39](#)

on switched packets [31-38](#)

time ranges to [31-17](#)

to an interface [31-20](#)

to QoS [32-7](#)

classifying traffic for QoS [32-43](#)

comments in [31-19](#)

ACLs (continued)

- compiling 31-22
- configuring with VLAN maps 31-37
- defined 31-1, 31-7
- examples of 31-22, 32-43
- extended IP
 - configuring for QoS classification 32-45
 - creating 31-10
 - matching criteria 31-7
- hardware and software handling 31-22
- host keyword 31-13
- IP
 - applying to interfaces 31-20
 - creating 31-7
 - fragments and QoS guidelines 32-34
 - implicit deny 31-9, 31-14, 31-16
 - implicit masks 31-9
 - matching criteria 31-7
 - named 31-15
 - terminal lines, setting on 31-20
 - undefined 31-21
 - violations, logging 31-16
- limiting actions 31-38
- logging messages 31-10
- log keyword 31-16
- MAC extended 31-27, 32-46
- matching 31-7, 31-21
- monitoring 31-41
- named 31-15
- number per QoS class map 32-34
- numbers 31-7
- port 31-2
- precedence of 31-2
- QoS 32-7, 32-43
- resequencing entries 31-15
- router 31-2

ACLs (continued)

- standard IP
 - configuring for QoS classification 32-44
 - creating 31-9
 - matching criteria 31-7
 - supported features 31-22
 - support for 1-6
 - time ranges 31-17
 - unsupported features 31-6
 - using router ACLs with VLAN maps 31-37
- VLAN maps
 - configuration guidelines 31-31
 - configuring 31-30
- active links 20-1
- active router 36-1
- address aliasing 23-2
- addresses
 - displaying the MAC address table 6-27
 - dynamic
 - accelerated aging 17-8
 - changing the aging time 6-21
 - default aging 17-8
 - defined 6-20
 - learning 6-20
 - removing 6-22
 - MAC, discovering 6-27
 - multicast
 - group address range 37-3
 - STP address management 17-8
 - static
 - adding and removing 6-24
 - defined 6-20
- address resolution 6-27, 34-8
- Address Resolution Protocol
 - See ARP
- adjacency tables, with CEF 34-60

- administrative distances
 - defined 34-71
 - OSPF 34-30
 - routing protocol defaults 34-62
- advanced IP services image 1-1, 35-1
- advertisements
 - CDP 25-1
 - RIP 34-19
 - VTP 12-19, 13-3
- aggregatable global unicast addresses 35-3
- aggregate addresses, BGP 34-54
- aggregated ports
 - See EtherChannel
- aggregate policers 32-58
- aggregate policing 1-8
- aging, accelerating 17-8
- aging time
 - accelerated
 - for MSTP 18-20
 - for STP 17-8, 17-21
 - MAC address table 6-21
 - maximum
 - for MSTP 18-21
 - for STP 17-21
- alarms, RMON 28-3
- allowed-VLAN list 12-21
- area border routers
 - See ABRs
- ARP
 - configuring 34-8
 - defined 1-4, 6-27, 34-8
 - encapsulation 34-10
 - static cache configuration 34-8
 - table
 - address resolution 6-27
 - managing 6-27
- ASBRs 34-24
- AS-path filters, BGP 34-49
- asymmetrical links, and 802.1Q tunneling 16-4
- attributes, RADIUS
 - vendor-proprietary 8-31
 - vendor-specific 8-29
- audience xxxvii
- authentication
 - EIGRP 34-37
 - HSRP 36-9
 - local mode with AAA 8-36
 - NTP associations 6-5
 - RADIUS
 - key 8-21
 - login 8-23
 - TACACS+
 - defined 8-11
 - key 8-13
 - login 8-14

See also port-based authentication
- authentication keys, and routing protocols 34-72
- authoritative time source, described 6-2
- authorization
 - with RADIUS 8-27
 - with TACACS+ 8-11, 8-16
- authorized ports with 802.1x 9-4
- autoconfiguration 3-3
- automatic QoS
 - See QoS
- autonegotiation
 - duplex mode 1-3
 - interface configuration guidelines 10-16
 - mismatches 40-11
- autonomous system boundary routers
 - See ASBRs
- autonomous systems, in BGP 34-43
- Auto-RP, described 37-5
- autosensing, port speed 1-3
- auxiliary VLAN
 - See voice VLAN
- availability, features 1-5

B

BackboneFast

- described 19-5
- disabling 19-14
- enabling 19-13
- support for 1-5

backup interfaces

- See Flex Links

backup links 20-1

banners

- configuring
 - login 6-19
 - message-of-the-day login 6-18
- default configuration 6-18
- when displayed 6-18

BGP

- aggregate addresses 34-54
- aggregate routes, configuring 34-54
- CIDR 34-54
- clear commands 34-58
- community filtering 34-51
- configuring neighbors 34-53
- default configuration 34-41
- described 34-40
- enabling 34-43
- monitoring 34-58
- multipath support 34-46
- neighbors, types of 34-43
- path selection 34-46
- peers, configuring 34-53
- prefix filtering 34-50
- resetting sessions 34-45
- route dampening 34-57
- route maps 34-48
- route reflectors 34-56
- routing domain confederation 34-55
- show commands 34-58
- supernets 34-54

BGP (continued)

- support for 1-8
- Version 4 34-40

binding cluster group and HSRP group 36-11

binding database

- address, DHCP server
 - See DHCP, Cisco IOS server database
- DHCP snooping
 - See DHCP snooping binding database

bindings

- address, Cisco IOS DHCP server 21-5
- DHCP snooping database 21-6
- IP source guard 21-14

binding table, DHCP snooping

- See DHCP snooping binding database

blocking packets 24-6

booting

- boot loader, function of 3-2
- boot process 3-2
- manually 3-13
- specific image 3-13

boot loader

- accessing 3-14
- described 3-2
- environment variables 3-14
- prompt 3-14
- trap-door mechanism 3-2

bootstrap router (BSR), described 37-5

Border Gateway Protocol

- See BGP

BPDU

- error-disabled state 19-2
- filtering 19-3
- RSTP format 18-9

BPDU filtering

- described 19-3
- disabling 19-12
- enabling 19-12
- support for 1-5

- BPDU guard
 - described 19-2
 - disabling 19-11
 - enabling 19-11
 - support for 1-5
 - bridged packets, ACLs on 31-39
 - bridge groups
 - See fallback bridging
 - bridge protocol data unit
 - See BPDU
 - broadcast flooding 34-16
 - broadcast packets
 - directed 34-13
 - flooded 34-13
 - broadcast storm-control command 24-4
 - broadcast storms 24-1, 34-13
-
- C
- cables, monitoring for unidirectional links 26-1
 - candidate switch
 - defined 5-3
 - requirements 5-3
 - See also command switch, cluster standby group, and member switch
 - CA trustpoint
 - configuring 8-44
 - defined 8-42
 - caution, described xxxviii
 - CDP
 - and trusted boundary 32-40
 - configuring 25-2
 - default configuration 25-2
 - described 25-1
 - disabling for routing device 25-3 to 25-4
 - enabling and disabling
 - on an interface 25-4
 - on a switch 25-3
 - Layer 2 protocol tunneling 16-8
 - CDP (continued)
 - monitoring 25-5
 - overview 25-1
 - power negotiation extensions 10-6
 - support for 1-4
 - transmission timer and holdtime, setting 25-2
 - updates 25-2
 - CEF
 - defined 34-59
 - enabling 34-60
 - IPv6 35-14
 - CGMP
 - as IGMP snooping learning method 23-8
 - clearing cached group entries 37-49
 - enabling server support 37-32
 - joining multicast group 23-3
 - overview 37-7
 - server support only 37-7
 - switch support of 1-3
 - CIDR 34-54
 - CipherSuites 8-43
 - Cisco 7960 IP Phone 15-1
 - Cisco Discovery Protocol
 - See CDP
 - Cisco Express Forwarding
 - See CEF
 - Cisco Group Management Protocol
 - See CGMP
 - Cisco intelligent power management 10-6
 - Cisco IOS DHCP server
 - See DHCP, Cisco IOS DHCP server
 - Cisco IOS File System
 - See IFS
 - Cisco Network Assistant
 - See Network Assistant
 - Cisco Networking Services
 - See IE2100
 - CiscoWorks 2000 1-4, 30-4

- classless interdomain routing
 - See CIDR
- classless routing [34-6](#)
- class maps for QoS
 - configuring [32-47](#)
 - described [32-7](#)
 - displaying [32-78](#)
- class of service
 - See CoS
- clearing interfaces [10-25](#)
- CLI
 - abbreviating commands [2-3](#)
 - command modes [2-1](#)
 - described [1-4](#)
 - editing features
 - enabling and disabling [2-6](#)
 - keystroke editing [2-6](#)
 - wrapped lines [2-8](#)
 - error messages [2-4](#)
 - filtering command output [2-8](#)
 - getting help [2-3](#)
 - history
 - changing the buffer size [2-5](#)
 - described [2-4](#)
 - disabling [2-5](#)
 - recalling commands [2-5](#)
 - managing clusters [5-3](#)
 - no and default forms of commands [2-4](#)
- client mode, VTP [13-3](#)
- clock
 - See system clock
- cluster requirements [xxxix](#)
- clusters, switch
 - benefits [1-2](#)
 - described [5-1](#)
 - managing
 - through CLI [5-3](#)
 - through SNMP [5-4](#)
- clusters, switch (continued)
 - planning considerations
 - CLI [5-3](#)
 - SNMP [5-4](#)
 - See also Getting Started with Cisco Network Assistant
- cluster standby group
 - and HSRP group [36-11](#)
 - requirements [5-2](#)
- Coarse Wave Division Multiplexer
 - See CWDM SFPs
- command-line interface
 - See CLI
- command modes [2-1](#)
- commands
 - abbreviating [2-3](#)
 - no and default [2-4](#)
- commands, setting privilege levels [8-8](#)
- command switch
 - configuration conflicts [40-11](#)
 - defined [5-2](#)
 - password privilege levels [5-4](#)
 - recovery
 - from command-switch failure [40-7](#)
 - from lost member connectivity [40-11](#)
 - replacing
 - with another switch [40-10](#)
 - with cluster member [40-8](#)
 - requirements [5-2](#)
 - See also candidate switch, cluster standby group, member switch, and standby command switch
- community list, BGP [34-52](#)
- community ports [14-2](#)
- community strings
 - configuring [30-8](#)
 - for cluster switches [30-4](#)
 - overview [30-4](#)
- community VLANs [14-2, 14-3](#)
- compatibility, feature [24-11](#)
- config.text [3-12](#)

- configuration, initial
 - defaults [1-10](#)
 - Express Setup [1-2](#)
 - See also getting started guide and hardware installation guide
 - configuration conflicts, recovering from lost member connectivity [40-11](#)
 - configuration examples, network [1-12](#)
 - configuration files
 - clearing the startup configuration [B-18](#)
 - creating using a text editor [B-9](#)
 - default name [3-12](#)
 - deleting a stored configuration [B-18](#)
 - described [B-8](#)
 - downloading
 - automatically [3-12](#)
 - preparing [B-10, B-12, B-15](#)
 - reasons for [B-8](#)
 - using FTP [B-13](#)
 - using RCP [B-16](#)
 - using TFTP [B-10](#)
 - guidelines for creating and using [B-8](#)
 - invalid combinations when copying [B-5](#)
 - limiting TFTP server access [30-15](#)
 - obtaining with DHCP [3-7](#)
 - password recovery disable considerations [8-5](#)
 - specifying the filename [3-12](#)
 - system contact and location information [30-14](#)
 - types and location [B-9](#)
 - uploading
 - preparing [B-10, B-12, B-15](#)
 - reasons for [B-8](#)
 - using FTP [B-14](#)
 - using RCP [B-17](#)
 - using TFTP [B-11](#)
 - configuration settings, saving [3-10](#)
 - configure terminal command [10-10](#)
 - config-vlan mode [2-2, 12-7](#)
 - conflicts, configuration [40-11](#)
 - connections, secure remote [8-38](#)
 - connectivity problems [40-13, 40-15, 40-16](#)
 - consistency checks in VTP Version 2 [13-4](#)
 - console port, connecting to [2-9](#)
 - conventions
 - command [xxxviii](#)
 - for examples [xxxviii](#)
 - publication [xxxviii](#)
 - text [xxxviii](#)
 - corrupted software, recovery steps with Xmodem [40-2](#)
 - CoS
 - in Layer 2 frames [32-2](#)
 - override priority [15-6](#)
 - trust priority [15-6](#)
 - CoS input queue threshold map for QoS [32-17](#)
 - CoS output queue threshold map for QoS [32-20](#)
 - CoS-to-DSCP map for QoS [32-60](#)
 - counters, clearing interface [10-25](#)
 - crashinfo file [40-23](#)
 - cryptographic software image
 - Kerberos [8-32](#)
 - SSH [8-37](#)
 - SSL [8-41](#)
 - CWDM SFPs [1-17](#)
-
- D**
- daylight saving time [6-13](#)
 - debugging
 - enabling all system diagnostics [40-20](#)
 - enabling for a specific feature [40-19](#)
 - redirecting error message output [40-20](#)
 - using commands [40-19](#)
 - default commands [2-4](#)
 - default configuration
 - 802.1Q tunneling [16-4](#)
 - 802.1x [9-10](#)
 - auto-QoS [32-21](#)
 - banners [6-18](#)

default configuration (continued)

- BGP [34-41](#)
- booting [3-12](#)
- CDP [25-2](#)
- DHCP [21-7](#)
- DHCP option 82 [21-7](#)
- DHCP snooping [21-7](#)
- DHCP snooping binding database [21-8](#)
- DNS [6-16](#)
- dynamic ARP inspection [22-5](#)
- EIGRP [34-34](#)
- EtherChannel [33-8](#)
- fallback bridging [39-3](#)
- Flex Links [20-2](#)
- HSRP [36-5](#)
- IGMP [37-26](#)
- IGMP filtering [23-21](#)
- IGMP snooping [23-6](#)
- IGMP throttling [23-21](#)
- initial switch information [3-3](#)
- IP addressing, IP routing [34-4](#)
- IP multicast routing [37-8](#)
- IP source guard [21-15](#)
- IPv6 [35-9](#)
- Layer 2 interfaces [10-14](#)
- Layer 2 protocol tunneling [16-11](#)
- MAC address table [6-21](#)
- MSDP [38-4](#)
- MSTP [18-12](#)
- MVR [23-16](#)
- NTP [6-4](#)
- optional spanning-tree configuration [19-9](#)
- OSPF [34-25](#)
- password and privilege level [8-2](#)
- PIM [37-8](#)
- private VLANs [14-6](#)
- RADIUS [8-20](#)
- RIP [34-20](#)
- RMON [28-3](#)

default configuration (continued)

- RSPAN [27-9](#)
- SDM template [7-3](#)
- SNMP [30-6](#)
- SPAN [27-9](#)
- SSL [8-44](#)
- standard QoS [32-32](#)
- STP [17-11](#)
- system message logging [29-3](#)
- system name and prompt [6-15](#)
- TACACS+ [8-13](#)
- UDLD [26-4](#)
- VLAN, Layer 2 Ethernet interfaces [12-19](#)
- VLANs [12-8](#)
- VMPS [12-29](#)
- voice VLAN [15-3](#)
- VTP [13-6](#)
- default gateway [3-10, 34-11](#)
- default networks [34-62](#)
- default routes [34-62](#)
- default routing [34-2](#)
- deleting VLANs [12-10](#)
- description command [10-21](#)
- designing your network, examples [1-12](#)
- destination addresses, in ACLs [31-12](#)
- destination-IP address-based forwarding, EtherChannel [33-7](#)
- destination-MAC address forwarding, EtherChannel [33-6](#)
- detecting indirect link failures, STP [19-5](#)
- device [B-18](#)
- device discovery protocol [25-1](#)
- device manager
 - benefits [1-2](#)
 - described [1-2, 1-4](#)
 - in-band management [1-5](#)
 - requirements [xxxviii](#)
 - upgrading a switch [B-18](#)

DHCP

Cisco IOS server database

- configuring 21-12

- default configuration 21-7

- described 21-5

enabling

- relay agent 21-9

- server 21-9

DHCP-based autoconfiguration

- client request message exchange 3-4

configuring

- client side 3-3

- DNS 3-6

- relay device 3-6

- server side 3-5

- server-side 21-9

- TFTP server 3-5

- example 3-8

lease options

- for IP address information 3-5

- for receiving the configuration file 3-5

- overview 3-3

- relationship to BOOTP 3-4

- relay support 1-4, 1-9

- support for 1-4

DHCP binding database

- See DHCP snooping binding database

DHCP binding table

- See DHCP snooping binding database

DHCP option 82

- circuit ID suboption 21-5

- configuration guidelines 21-8

- default configuration 21-7

- displaying 21-14

- forwarding address, specifying 21-10

- helper address 21-10

- overview 21-3

DHCP option 82 (continued)

- packet format, suboption

- circuit ID 21-5

- remote ID 21-5

- remote ID suboption 21-5

DHCP snooping

- accepting untrusted packets form edge switch 21-3, 21-11

- and private VLANs 21-12

- binding database

- See DHCP snooping binding database

- configuration guidelines 21-8

- default configuration 21-7

- displaying binding tables 21-14

- message exchange process 21-4

- option 82 data insertion 21-3

- trusted interface 21-2

- untrusted interface 21-2

- untrusted messages 21-2

DHCP snooping binding database

- adding bindings 21-13

- binding file

- format 21-6

- location 21-6

- bindings 21-6

- clearing agent statistics 21-13

- configuration guidelines 21-9

- configuring 21-13

- default configuration 21-7, 21-8

- deleting

- binding file 21-13

- bindings 21-13

- database agent 21-13

- described 21-5

- displaying 21-14

- binding entries 21-14

- status and statistics 21-14

- enabling 21-13

- entry 21-6

DHCP snooping binding database (continued)

renewing database [21-13](#)

resetting

delay value [21-13](#)timeout value [21-13](#)updating process [21-6](#)

DHCP snooping binding table

See DHCP snooping binding database

Differentiated Services architecture, QoS [32-2](#)Differentiated Services Code Point [32-2](#)Diffusing Update Algorithm (DUAL) [34-33](#)directed unicast requests [1-4](#)

directories

changing [B-3](#)creating and removing [B-4](#)displaying the working [B-3](#)

Distance Vector Multicast Routing Protocol

See DVMRP

distance-vector protocols [34-3](#)distribute-list command [34-70](#)

DNS

and DHCP-based autoconfiguration [3-6](#)default configuration [6-16](#)displaying the configuration [6-17](#)in IPv6 [35-4](#)overview [6-16](#)setting up [6-17](#)support for [1-4](#)documentation, related [xxxviii](#)document conventions [xxxviii](#)

domain names

DNS [6-16](#)VTP [13-8](#)

Domain Name System

See DNS

dot1q-tunnel switchport mode [12-18](#)

double-tagged packets

802.1Q tunneling [16-2](#)Layer 2 protocol tunneling [16-10](#)

downloading

configuration files

preparing [B-10, B-12, B-15](#)reasons for [B-8](#)using FTP [B-13](#)using RCP [B-16](#)using TFTP [B-10](#)

image files

deleting old image [B-22](#)preparing [B-21, B-24, B-28](#)reasons for [B-19](#)using CMS [1-2](#)using FTP [B-25](#)using HTTP [1-2, B-18](#)using Network Assistant [1-2](#)using RCP [B-30](#)using TFTP [B-21](#)using the device manager or Network Assistant [B-18](#)drop threshold for Layer 2 protocol packets [16-11](#)DSCP [1-7, 32-2](#)DSCP input queue threshold map for QoS [32-17](#)DSCP output queue threshold map for QoS [32-20](#)DSCP-to-CoS map for QoS [32-63](#)DSCP-to-DSCP-mutation map for QoS [32-64](#)DSCP transparency [32-40](#)DTP [1-6, 12-17](#)DUAL finite state machine, EIGRP [34-33](#)dual IPv4 and IPv6 templates [7-2, 35-7](#)

dual protocol stacks

configuring [35-12](#)IPv4 and IPv6 [35-7](#)SDM templates supporting [35-8](#)duplex mode, configuring [10-15](#)

DVMRP

autosummarization

configuring a summary address [37-46](#)disabling [37-48](#)connecting PIM domain to DVMRP router [37-38](#)enabling unicast routing [37-42](#)

- DVMRP (continued)
 - interoperability
 - with Cisco devices [37-36](#)
 - with Cisco IOS software [37-7](#)
 - mrinfo requests, responding to [37-41](#)
 - neighbors
 - advertising the default route to [37-40](#)
 - discovery with Probe messages [37-36](#)
 - displaying information [37-41](#)
 - prevent peering with nonpruning [37-44](#)
 - rejecting nonpruning [37-42](#)
 - overview [37-7](#)
 - routes
 - adding a metric offset [37-48](#)
 - advertising all [37-48](#)
 - advertising the default route to neighbors [37-40](#)
 - caching DVMRP routes learned in report messages [37-42](#)
 - changing the threshold for syslog messages [37-45](#)
 - deleting [37-49](#)
 - displaying [37-50](#)
 - favoring one over another [37-48](#)
 - limiting the number injected into MBONE [37-45](#)
 - limiting unicast route advertisements [37-36](#)
 - routing table [37-7](#)
 - source distribution tree, building [37-7](#)
 - support for [1-9](#)
 - tunnels
 - configuring [37-38](#)
 - displaying neighbor information [37-41](#)
- dynamic access ports
 - characteristics [12-3](#)
 - configuring [12-30](#)
 - defined [10-3](#)
- dynamic addresses
 - See addresses
- dynamic ARP inspection
 - ARP cache poisoning [22-1](#)
 - ARP requests, described [22-1](#)
- dynamic ARP inspection (continued)
 - ARP spoofing attack [22-1](#)
 - clearing
 - log buffer [22-15](#)
 - statistics [22-15](#)
 - configuration guidelines [22-6](#)
 - configuring
 - ACLs for non-DHCP environments [22-8](#)
 - in DHCP environments [22-7](#)
 - log buffer [22-12](#)
 - rate limit for incoming ARP packets [22-4, 22-10](#)
 - default configuration [22-5](#)
 - denial-of-service attacks, preventing [22-10](#)
 - described [22-1](#)
 - DHCP snooping binding database [22-2](#)
 - displaying
 - ARP ACLs [22-14](#)
 - configuration and operating state [22-14](#)
 - log buffer [22-15](#)
 - statistics [22-15](#)
 - trust state and rate limit [22-14](#)
 - error-disabled state for exceeding rate limit [22-4](#)
 - function of [22-2](#)
 - interface trust states [22-3](#)
 - log buffer
 - clearing [22-15](#)
 - configuring [22-12](#)
 - displaying [22-15](#)
 - logging of dropped packets, described [22-4](#)
 - man-in-the middle attack, described [22-2](#)
 - network security issues and interface trust states [22-3](#)
 - priority of ARP ACLs and DHCP snooping entries [22-4](#)
 - rate limiting of ARP packets
 - configuring [22-10](#)
 - described [22-4](#)
 - error-disabled state [22-4](#)

dynamic ARP inspection (continued)
 statistics
 clearing [22-15](#)
 displaying [22-15](#)
 validation checks, performing [22-11](#)

dynamic auto trunking mode [12-18](#)

dynamic desirable trunking mode [12-18](#)

Dynamic Host Configuration Protocol
 See DHCP-based autoconfiguration

dynamic port VLAN membership
 described [12-28](#)
 reconfirming [12-31](#)
 troubleshooting [12-33](#)
 types of connections [12-30](#)

dynamic routing [34-3](#)

Dynamic Trunking Protocol
 See DTP

E

EBGP [34-39](#)

editing features
 enabling and disabling [2-6](#)
 keystrokes used [2-6](#)
 wrapped lines [2-8](#)

EIGRP
 authentication [34-37](#)
 components [34-33](#)
 configuring [34-35](#)
 default configuration [34-34](#)
 definition [34-33](#)
 interface parameters, configuring [34-36](#)
 monitoring [34-38](#)
 support for [1-8](#)

EMI [1-1](#)

enable password [8-4](#)

enable secret password [8-4](#)

encryption, CipherSuite [8-43](#)

encryption for passwords [8-4](#)

Enhanced IGRP
 See EIGRP

enhanced multilayer image
 See EMI

environment variables, function of [3-15](#)

equal-cost routing [1-9, 34-61](#)

error messages during command entry [2-4](#)

EtherChannel
 802.3ad, described [33-5](#)
 automatic creation of [33-4, 33-5](#)
 channel groups
 binding physical and logical interfaces [33-3](#)
 numbering of [33-3](#)
 configuration guidelines [33-9](#)
 configuring
 Layer 2 interfaces [33-10](#)
 Layer 3 physical interfaces [33-13](#)
 Layer 3 port-channel logical interfaces [33-12](#)
 default configuration [33-8](#)
 described [33-2](#)
 displaying status [33-20](#)
 forwarding methods [33-6, 33-15](#)
 interaction
 with STP [33-9](#)
 with VLANs [33-9](#)

LACP
 described [33-5](#)
 displaying status [33-20](#)
 hot-standby ports [33-17](#)
 interaction with other features [33-6](#)
 modes [33-5](#)
 port priority [33-19](#)
 system priority [33-18](#)

Layer 3 interface [34-3](#)

load balancing [33-6, 33-15](#)

logical interfaces, described [33-3](#)

EtherChannel (continued)

PAgP

- aggregate-port learners [33-16](#)
- compatibility with Catalyst 1900 [33-16](#)
- described [33-4](#)
- displaying status [33-20](#)
- interaction with other features [33-5](#)
- learn method and priority configuration [33-16](#)
- modes [33-4](#)
- support for [1-3](#)

port-channel interfaces

- described [33-3](#)
- numbering of [33-3](#)
- port groups [10-5](#)
- support for [1-3](#)

EtherChannel guard

- described [19-7](#)
- disabling [19-14](#)
- enabling [19-14](#)

Ethernet VLANs

- adding [12-9](#)
- defaults and ranges [12-8](#)
- modifying [12-9](#)

EUI [35-3](#)events, RMON [28-3](#)

examples

- conventions for [xxxviii](#)
- network configuration [1-12](#)

expedite queue for QoS [32-77](#)Express Setup [1-2](#)

- See also getting started guide

extended-range VLANs

- configuration guidelines [12-13](#)
- configuring [12-12](#)
- creating [12-13](#)
- defined [12-1](#)

extended system ID

- MSTP [18-14](#)
- STP [17-4, 17-14](#)

extended universal identifier

- See EUI

Extensible Authentication Protocol over LAN [9-1](#)

external BGP

- See EBGp

external neighbors, BGP [34-43](#)

F

fallback bridging

- and protected ports [39-3](#)

bridge groups

- creating [39-3](#)
- described [39-1](#)
- displaying [39-10](#)
- function of [39-2](#)
- number supported [39-4](#)
- removing [39-4](#)

bridge table

- clearing [39-10](#)
- displaying [39-10](#)

configuration guidelines [39-3](#)connecting interfaces with [10-9](#)default configuration [39-3](#)described [39-1](#)

frame forwarding

- flooding packets [39-2](#)
- forwarding packets [39-2](#)

overview [39-1](#)protocol, unsupported [39-3](#)

STP

- disabling on an interface [39-10](#)
- forward-delay interval [39-9](#)
- hello BPDU interval [39-8](#)
- interface priority [39-6](#)
- keepalive messages [17-2](#)
- maximum-idle interval [39-9](#)
- path cost [39-7](#)

fallback bridging (continued)

STP

- VLAN-bridge spanning-tree priority [39-6](#)

- VLAN-bridge STP [39-2](#)

- support for [1-8](#)

- SVIs and routed ports [39-1](#)

- unsupported protocols [39-3](#)

- VLAN-bridge STP [17-10](#)

features, incompatible [24-11](#)FIB [34-59](#)fiber-optic, detecting unidirectional links [26-1](#)

files

- copying [B-4](#)

crashinfo

- description [40-23](#)

- displaying the contents of [40-23](#)

- location [40-23](#)

- deleting [B-5](#)

- displaying the contents of [B-7](#)

tar

- creating [B-5](#)

- displaying the contents of [B-6](#)

- extracting [B-7](#)

- image file format [B-19](#)

file system

- displaying available file systems [B-2](#)

- displaying file information [B-3](#)

- local file system names [B-1](#)

- network file system names [B-4](#)

- setting the default [B-3](#)

filtering

- in a VLAN [31-30](#)

- non-IP traffic [31-27](#)

- show and more command output [2-8](#)

filtering show and more command output [2-8](#)

filters, IP

- See ACLs, IP

flash device, number of [B-1](#)

Flex Links

- configuration guidelines [20-2](#)

- configuring [20-3](#)

- default configuration [20-2](#)

- description [20-1](#)

- monitoring [20-3](#)

flooded traffic, blocking [24-7](#)flow-based packet classification [1-7](#)

flowcharts

- QoS classification [32-6](#)

- QoS egress queueing and scheduling [32-18](#)

- QoS ingress queueing and scheduling [32-16](#)

- QoS policing and marking [32-10](#)

flow control [1-3, 10-18](#)

forward-delay time

- MSTP [18-20](#)

- STP [17-21](#)

Forwarding Information Base

- See FIB

forwarding nonroutable protocols [39-1](#)

FTP

- accessing MIB files [A-3](#)

configuration files

- downloading [B-13](#)

- overview [B-12](#)

- preparing the server [B-12](#)

- uploading [B-14](#)

image files

- deleting old image [B-27](#)

- downloading [B-25](#)

- preparing the server [B-24](#)

- uploading [B-27](#)

G

- get-bulk-request operation [30-3](#)

- get-next-request operation [30-3, 30-4](#)

- get-request operation [30-3, 30-4](#)

- get-response operation [30-3](#)

global configuration mode [2-2](#)
 guest VLAN and 802.1x [9-8](#)
 guide
 audience [xxxvii](#)
 purpose of [xxxvii](#)
 guide mode [1-2](#)
 GUIs
 See device manager and Network Assistant [1-4](#)

H

hardware limitations and Layer 3 interfaces [10-22](#)
 hello time
 MSTP [18-19](#)
 STP [17-20](#)
 help, for the command line [2-3](#)
 hierarchical policy maps [32-8](#)
 configuration guidelines [32-34](#)
 configuring [32-52](#)
 described [32-11](#)
 history
 changing the buffer size [2-5](#)
 described [2-4](#)
 disabling [2-5](#)
 recalling commands [2-5](#)
 history table, level and number of syslog messages [29-9](#)
 host ports
 configuring [14-11](#)
 kinds of [14-2](#)
 hosts, limit on dynamic ports [12-33](#)
 Hot Standby Router Protocol
 See HSRP
 HP OpenView [1-4](#)
 HSRP
 authentication string [36-9](#)
 binding to cluster group [36-11](#)
 command-switch redundancy [1-1, 1-5](#)
 configuring [36-4](#)
 default configuration [36-5](#)

HSRP (continued)
 definition [36-1](#)
 guidelines [36-5](#)
 monitoring [36-11](#)
 overview [36-1](#)
 priority [36-7](#)
 routing redundancy [1-8](#)
 support for ICMP redirect messages [36-11](#)
 timers [36-9](#)
 tracking [36-7](#)
 HTTP over SSL
 see HTTPS
 HTTPS [8-42](#)
 configuring [8-45](#)
 self-signed certificate [8-42](#)
 HTTP secure server [8-42](#)

I

IBPG [34-39](#)
 ICMP
 IPv6 [35-4](#)
 redirect messages [34-11](#)
 support for [1-9](#)
 time-exceeded messages [40-17](#)
 traceroute and [40-17](#)
 unreachable messages [31-21](#)
 unreachables and ACLs [31-22](#)
 ICMP ping
 executing [40-14](#)
 overview [40-13](#)
 ICMP Router Discovery Protocol
 See IRDP
 ICMPv6 [35-4](#)
 IDS appliances
 and ingress RSPAN [27-20](#)
 and ingress SPAN [27-13](#)

IE2100

CNS embedded agents

- described 4-5
- enabling automated configuration 4-6
- enabling configuration agent 4-9
- enabling event agent 4-8

Configuration Registrar

- configID, deviceID, hostname 4-3
- configuration service 4-2
- described 4-1
- event service 4-3

IEEE 802.1p 15-1

ifIndex values, SNMP 30-5

IFS 1-4

IGMP

configuring the switch

- as a member of a group 37-26
 - statically connected member 37-31
- controlling access to groups 37-27
- default configuration 37-26
- deleting cache entries 37-50
- displaying groups 37-50
- fast switching 37-31
- host-query interval, modifying 37-29
- joining multicast group 23-3
- join messages 23-3
- leave processing, enabling 23-10
- leaving multicast group 23-4
- multicast reachability 37-26
- overview 37-2
- queries 23-3
- report suppression
- described 23-5
 - disabling 23-12
- support for 1-3
- Version 1
- changing to Version 2 37-28
 - described 37-3

IGMP (continued)

Version 2

- changing to Version 1 37-28
- described 37-3
- maximum query response time value 37-30
- pruning groups 37-30
- query timeout value 37-30

IGMP filtering

- configuring 23-21
- default configuration 23-21
- described 23-20
- monitoring 23-25
- support for 1-3

IGMP groups

- configuring filtering 23-24
- setting the maximum number 23-23

IGMP profile

- applying 23-22
- configuration mode 23-21
- configuring 23-22

IGMP snooping

- and address aliasing 23-2
- configuring 23-6
- default configuration 23-6
- definition 23-1
- enabling and disabling 23-7
- global configuration 23-7
- Immediate Leave 23-5
- method 23-7
- monitoring 23-12
- querier

 - configuring 23-10
 - guidelines and restrictions 23-5
 - support for 1-3

- VLAN configuration 23-7

IGMP throttling

- configuring 23-24
- default configuration 23-21

- IGMP throttling (continued)
 - described [23-21](#)
 - displaying action [23-25](#)
- IGP [34-24](#)
- Immediate Leave, IGMP
 - described [23-5](#)
 - enabling [23-10](#)
- initial configuration
 - defaults [1-10](#)
 - Express Setup [1-2](#)
 - See also getting started guide and hardware installation guide
- Intelligence Engine 2100 Series CNS Agents
 - See IE2100
- interface
 - number [10-10](#)
 - range macros [10-12](#)
- interface command [10-9 to 10-10](#)
- interface configuration mode [2-2](#)
- interfaces
 - configuration guidelines
 - duplex and speed [10-16](#)
 - configuring
 - duplex mode [10-15](#)
 - procedure [10-10](#)
 - speed [10-15](#)
 - configuring for IPv4 and IPv6 [35-12](#)
 - counters, clearing [10-25](#)
 - described [10-21](#)
 - descriptive name, adding [10-21](#)
 - displaying information about [10-25](#)
 - flow control [10-18](#)
 - management [1-4](#)
 - monitoring [10-24](#)
 - naming [10-21](#)
 - physical, identifying [10-9](#)
 - range of [10-11](#)
 - restarting [10-26](#)
 - shutting down [10-26](#)
- interfaces (continued)
 - status [10-24](#)
 - supported [10-9](#)
 - types of [10-1](#)
- interfaces range macro command [10-12](#)
- interface types [10-9](#)
- Interior Gateway Protocol
 - See IGP
- internal BGP
 - See IBGP
- internal neighbors, BGP [34-43](#)
- Internet Control Message Protocol
 - See ICMP
- Internet Group Management Protocol
 - See IGMP
- Internet Protocol version 6
 - See IPv6
- Inter-Switch Link
 - See ISL
- inter-VLAN routing [1-8, 34-2](#)
- Intrusion Detection System
 - See IDS appliances
- ip access group command [31-21](#)
- IP ACLs
 - extended, creating [31-10](#)
 - for QoS classification [32-7](#)
 - implicit deny [31-9, 31-14, 31-16](#)
 - implicit masks [31-9](#)
 - logging [31-16](#)
 - named [31-15](#)
 - standard, creating [31-9](#)
 - undefined [31-21](#)
 - virtual terminal lines, setting on [31-20](#)
- IP addresses
 - 128-bit [35-2](#)
 - candidate or member [5-3](#)
 - classes of [34-5](#)
 - command switch [5-2](#)
 - default configuration [34-4](#)

IP addresses (continued)

- discovering [6-27](#)
- for IP routing [34-4](#)
- IPv6 [35-2](#)
- MAC address association [34-8](#)
- monitoring [34-17](#)
- See also IP information

IP broadcast address [34-16](#)ip cef distributed command [34-60](#)IP directed broadcasts [34-13](#)ip igmp profile command [23-21](#)

IP information

- assigned
 - manually [3-9](#)
 - through DHCP-based autoconfiguration [3-3](#)
- default configuration [3-3](#)

IP multicast routing

addresses

- all-hosts [37-3](#)
- all-multicast-routers [37-3](#)
- host group address range [37-3](#)

administratively-scoped boundaries, described [37-34](#)and IGMP snooping [23-1](#)

Auto-RP

- adding to an existing sparse-mode cloud [37-13](#)
- benefits of [37-13](#)
- clearing the cache [37-50](#)
- configuration guidelines [37-9](#)
- filtering incoming RP announcement messages [37-16](#)
- overview [37-5](#)
- preventing candidate RP spoofing [37-16](#)
- preventing join messages to false RPs [37-15](#)
- setting up in a new internetwork [37-13](#)
- using with BSR [37-21](#)

bootstrap router

- configuration guidelines [37-9](#)
- configuring candidate BSRs [37-19](#)
- configuring candidate RPs [37-20](#)
- defining the IP multicast boundary [37-18](#)

IP multicast routing (continued)

bootstrap router

- defining the PIM domain border [37-17](#)
- overview [37-5](#)
- using with Auto-RP [37-21](#)

Cisco implementation [37-2](#)

configuring

- basic multicast routing [37-10](#)
- IP multicast boundary [37-34](#)

default configuration [37-8](#)

enabling

- multicast forwarding [37-10](#)
- PIM mode [37-11](#)

group-to-RP mappings

- Auto-RP [37-5](#)
- BSR [37-5](#)

MBONE

- deleting sdr cache entries [37-50](#)
- described [37-33](#)
- displaying sdr cache [37-51](#)
- enabling sdr listener support [37-33](#)
- limiting DVMRP routes advertised [37-45](#)
- limiting sdr cache entry lifetime [37-34](#)
- SAP packets for conference session announcement [37-33](#)
- Session Directory (sdr) tool, described [37-33](#)

monitoring

- packet rate loss [37-51](#)
- peering devices [37-51](#)
- tracing a path [37-51](#)

multicast forwarding, described [37-6](#)PIMv1 and PIMv2 interoperability [37-8](#)protocol interaction [37-2](#)reverse path check (RPF) [37-6](#)

routing table

- deleting [37-50](#)
- displaying [37-50](#)

IP multicast routing (continued)

RP

- assigning manually [37-11](#)
- configuring Auto-RP [37-13](#)
- configuring PIMv2 BSR [37-17](#)
- monitoring mapping information [37-22](#)
- using Auto-RP and BSR [37-21](#)

statistics, displaying system and network [37-50](#)

See also CGMP

See also DVMRP

See also IGMP

See also PIM

IP phones

- and QoS [15-1](#)
- automatic classification and queuing [32-21](#)
- configuring [15-4](#)
- ensuring port security with QoS [32-39](#)
- trusted boundary for QoS [32-39](#)

IP precedence [32-2](#)IP-precedence-to-DSCP map for QoS [32-61](#)

IP protocols

- in ACLs [31-12](#)
- routing [1-8](#)

IP routes, monitoring [34-73](#)

IP routing

- connecting interfaces with [10-9](#)
- disabling [34-18](#)
- enabling [34-18](#)

IP source guard

- and 802.1x [21-16](#)
- and DHCP snooping [21-14](#)
- and EtherChannels [21-16](#)
- and port security [21-16](#)
- and private VLANs [21-16](#)
- and routed ports [21-16](#)
- and TCAM entries [21-16](#)
- and trunk interfaces [21-16](#)
- and VRF [21-16](#)

IP source guard (continued)

binding configuration

- automatic [21-14](#)
- manual [21-14](#)

binding table [21-14](#)configuration guidelines [21-16](#)default configuration [21-15](#)described [21-14](#)disabling [21-17](#)

displaying

- bindings [21-17](#)
- configuration [21-17](#)

enabling [21-16](#)

filtering

- source IP address [21-15](#)
- source IP and MAC address [21-15](#)
- source IP address filtering [21-15](#)
- source IP and MAC address filtering [21-15](#)

static bindings

- adding [21-16](#)
- deleting [21-17](#)

IP traceroute

- executing [40-17](#)
- overview [40-16](#)

IP unicast routing

- address resolution [34-8](#)
- administrative distances [34-62, 34-71](#)
- ARP [34-8](#)
- assigning IP addresses to Layer 3 interfaces [34-5](#)
- authentication keys [34-72](#)
- broadcast
 - address [34-16](#)
 - flooding [34-16](#)
 - packets [34-13](#)
 - storms [34-13](#)
- classless routing [34-6](#)
- configuring static routes [34-61](#)

IP unicast routing (continued)

default

- addressing configuration [34-4](#)
- gateways [34-11](#)
- networks [34-62](#)
- routes [34-62](#)
- routing [34-2](#)

directed broadcasts [34-13](#)disabling [34-18](#)dynamic routing [34-3](#)enabling [34-18](#)EtherChannel Layer 3 interface [34-3](#)IGP [34-24](#)inter-VLAN [34-2](#)

IP addressing

- classes [34-5](#)
- configuring [34-4](#)

IPv6 [35-3](#)IRDP [34-11](#)Layer 3 interfaces [34-3](#)MAC address and IP address [34-8](#)passive interfaces [34-69](#)

protocols

- distance-vector [34-3](#)
- dynamic [34-3](#)
- link-state [34-3](#)

proxy ARP [34-8](#)redistribution [34-63](#)reverse address resolution [34-8](#)routed ports [34-3](#)static routing [34-3](#)steps to configure [34-4](#)subnet mask [34-5](#)subnet zero [34-6](#)supernet [34-6](#)UDP [34-14](#)with SVIs [34-3](#)

See also BGP

See also EIGRP

IP unicast routing (continued)

See also OSPF

See also RIP

IPv4 and IPv6

- configuring on an interface [35-12](#)
- differences [35-1](#)
- dual protocol stacks [35-5](#)

IPv6

- addresses [35-2](#)
- address formats [35-2](#)
- advantages [35-1](#)
- applications [35-5](#)
- assigning address [35-9](#)
- autoconfiguration [35-4](#)
- CEFv6 [35-14](#)
- configuring static routes [35-14](#)
- default configuration [35-9](#)
- defined [35-1](#)
- enabling [35-9](#)
- feature limitations [35-7](#)
- features not supported [35-6](#)
- ICMP [35-4](#)
- ICMP rate limiting [35-13](#)
- monitoring [35-20](#)
- OSPF [35-18](#)
- path MTU discovery [35-4](#)
- reasons for [35-1](#)
- RIP [35-16](#)
- SDM templates [7-2, 35-7](#)
- supported features [35-3](#)
- switch limitations [35-6](#)

IRDP

- configuring [34-12](#)
- definition [34-11](#)
- support for [1-9](#)

ISL

- and IPv6 [35-3](#)
- and trunk ports [10-3](#)

ISL (continued)

- encapsulation [1-6, 12-16](#)
 - trunking with 802.1 tunneling [16-5](#)
- isolated port [14-2](#)
- isolated VLANs [14-2, 14-3](#)

J

- join messages, IGMP [23-3](#)

K

KDC

- described [8-32](#)
 - See also Kerberos
- keepalive messages [17-2](#)
- Kerberos
- authenticating to
 - boundary switch [8-35](#)
 - KDC [8-35](#)
 - network services [8-35](#)
 - configuration examples [8-32](#)
 - configuring [8-36](#)
 - credentials [8-32](#)
 - cryptographic software image [8-32](#)
 - described [8-32](#)
 - KDC [8-32](#)
 - operation [8-34](#)
 - realm [8-33](#)
 - server [8-33](#)
 - support for [1-7](#)
 - switch as trusted third party [8-32](#)
 - terms [8-33](#)
 - TGT [8-34](#)
 - tickets [8-32](#)
- key distribution center
- See KDC

L

- l2protocol-tunnel command [16-13](#)
- LACP
- Layer 2 protocol tunneling [16-9](#)
 - See EtherChannel
- Layer 2 frames, classification with CoS [32-2](#)
- Layer 2 interfaces, default configuration [10-14](#)
- Layer 2 protocol tunneling
- configuring [16-10](#)
 - configuring for EtherChannels [16-14](#)
 - default configuration [16-11](#)
 - defined [16-8](#)
 - guidelines [16-11](#)
- Layer 2 traceroute
- and ARP [40-16](#)
 - and CDP [40-15](#)
 - broadcast traffic [40-15](#)
 - described [40-15](#)
 - IP addresses and subnets [40-16](#)
 - MAC addresses and VLANs [40-15](#)
 - multicast traffic [40-15](#)
 - multiple devices on a port [40-16](#)
 - unicast traffic [40-15](#)
 - usage guidelines [40-15](#)
- Layer 2 trunks [12-17](#)
- Layer 3 features [1-8](#)
- Layer 3 interfaces
- assigning IP addresses to [34-5](#)
 - assigning IPv4 and IPv6 addresses to [35-12](#)
 - assigning IPv6 addresses to [35-10](#)
 - changing from Layer 2 mode [34-5](#)
 - types of [34-3](#)
- Layer 3 packets, classification methods [32-2](#)
- LDAP [4-2](#)
- LEDs, switch
- See hardware installation guide
- lightweight directory access protocol
- See LDAP

line configuration mode [2-2](#)

Link Aggregation Control Protocol

- See EtherChannel

link local unicast addresses [35-3](#)

link redundancy

- See Flex Links

links, unidirectional [26-1](#)

link state advertisements (LSAs) [34-28](#)

link-state protocols [34-3](#)

load balancing [36-3](#)

logging messages, ACL [31-10](#)

login authentication

- with RADIUS [8-23](#)
- with TACACS+ [8-14](#)

login banners [6-18](#)

log messages

- See system message logging

Long-Reach Ethernet (LRE) technology [1-14](#)

loop guard

- described [19-9](#)
- enabling [19-15](#)
- support for [1-5](#)

M

MAC addresses

- aging time [6-21](#)
- and VLAN association [6-21](#)
- building the address table [6-20](#)
- default configuration [6-21](#)
- discovering [6-27](#)
- displaying [6-27](#)
- displaying in the IP source binding table [21-17](#)
- dynamic
 - learning [6-20](#)
 - removing [6-22](#)
- in ACLs [31-27](#)
- IP address association [34-8](#)

MAC addresses (continued)

- static
 - adding [6-25](#)
 - allowing [6-26](#)
 - characteristics of [6-24](#)
 - dropping [6-26](#)
 - removing [6-25](#)
- MAC address notification, support for [1-9](#)
- MAC address-to-VLAN mapping [12-28](#)
- MAC extended access lists
 - applying to Layer 2 interfaces [31-29](#)
 - configuring for QoS [32-46](#)
 - creating [31-27](#)
 - defined [31-27](#)
 - for QoS classification [32-5](#)
- macros
 - See Smartports macros
- manageability features [1-4](#)
- management access
 - in-band
 - browser session [1-5](#)
 - CLI session [1-5](#)
 - device manager [1-5](#)
 - SNMP [1-5](#)
 - out-of-band console port connection [1-5](#)
- management options
 - CLI [2-1](#)
 - clustering [1-3](#)
 - CNS [4-1](#)
 - Network Assistant [1-2](#)
 - overview [1-4](#)
- mapping tables for QoS
 - configuring
 - CoS-to-DSCP [32-60](#)
 - DSCP [32-60](#)
 - DSCP-to-CoS [32-63](#)
 - DSCP-to-DSCP-mutation [32-64](#)

- mapping tables for QoS (continued)
 - IP-precedence-to-DSCP [32-61](#)
 - policed-DSCP [32-62](#)
 - described [32-13](#)
- marking
 - action in policy map [32-49](#)
 - action with aggregate policers [32-58](#)
 - described [32-4](#), [32-8](#)
- matching, ACLs [31-7](#)
- maximum aging time
 - MSTP [18-21](#)
 - STP [17-21](#)
- maximum hop count, MSTP [18-21](#)
- maximum-paths command [34-46](#), [34-61](#)
- membership mode, VLAN port [12-3](#)
- member switch
 - defined [5-2](#)
 - managing [5-3](#)
 - recovering from lost connectivity [40-11](#)
 - requirements [5-3](#)
 - See also candidate switch, cluster standby group, and standby command switch
- messages
 - logging ACL violations [31-16](#)
 - to users through banners [6-18](#)
- messages, to users through banners [6-18](#)
- metrics, in BGP [34-47](#)
- metric translations, between routing protocols [34-66](#)
- metro tags [16-2](#)
- MHSRP [36-3](#)
- MIBs
 - accessing files with FTP [A-3](#)
 - location of files [A-3](#)
 - overview [30-1](#)
 - SNMP interaction with [30-4](#)
 - supported [A-1](#)
- mirroring traffic for analysis [27-1](#)
- mismatches, autonegotiation [40-11](#)
- module number [10-10](#)
- monitoring
 - 802.1Q tunneling [16-18](#)
 - access groups [31-41](#)
 - ACL configuration [31-41](#)
 - BGP [34-58](#)
 - cables for unidirectional links [26-1](#)
 - CDP [25-5](#)
 - CEF [34-60](#)
 - EIGRP [34-38](#)
 - fallback bridging [39-10](#)
 - features [1-9](#)
 - Flex Links [20-3](#)
 - HSRP [36-11](#)
 - IGMP
 - filters [23-25](#)
 - snooping [23-12](#)
 - interfaces [10-24](#)
 - IP
 - address tables [34-17](#)
 - multicast routing [37-49](#)
 - routes [34-73](#)
 - IPv6 [35-20](#)
 - Layer 2 protocol tunneling [16-18](#)
 - MSDP peers [38-19](#)
 - multicast router interfaces [23-13](#)
 - MVR [23-20](#)
 - network traffic for analysis with probe [27-2](#)
 - OSPF [34-32](#)
 - port
 - blocking [24-16](#)
 - protection [24-16](#)
 - private VLANs [14-14](#)
 - RP mapping information [37-22](#)
 - SFP status [1-10](#), [10-25](#), [40-13](#)
 - source-active messages [38-19](#)
 - speed and duplex mode [10-17](#)
 - traffic flowing among switches [28-1](#)
 - traffic suppression [24-16](#)
 - tunneling [16-18](#)

monitoring (continued)

VLAN

filters [31-41](#)maps [31-41](#)VLANs [12-15](#)VMPS [12-32](#)VTP [13-16](#)benefits of [38-3](#)clearing MSDP connections and statistics [38-19](#)

controlling source information

forwarded by switch [38-12](#)originated by switch [38-9](#)received by switch [38-14](#)default configuration [38-4](#)

dense-mode regions

sending SA messages to [38-17](#)specifying the originating address [38-18](#)

filtering

incoming SA messages [38-14](#)SA messages to a peer [38-12](#)SA requests from a peer [38-11](#)join latency, defined [38-6](#)

meshed groups

configuring [38-16](#)defined [38-16](#)originating address, changing [38-18](#)overview [38-1](#)peer-RPF flooding [38-2](#)

peers

configuring a default [38-4](#)monitoring [38-19](#)peering relationship, overview [38-1](#)requesting source information from [38-8](#)shutting down [38-16](#)

source-active messages

caching [38-6](#)clearing cache entries [38-19](#)defined [38-2](#)filtering from a peer [38-11](#)

MSDP (continued)

source-active messages

filtering incoming [38-14](#)filtering to a peer [38-12](#)limiting data with TTL [38-14](#)monitoring [38-19](#)restricting advertised sources [38-9](#)support for [1-9](#)

MSTP

boundary ports

configuration guidelines [18-13](#)described [18-5](#)

BPDU filtering

described [19-3](#)enabling [19-12](#)

BPDU guard

described [19-2](#)enabling [19-11](#)CIST, described [18-3](#)configuration guidelines [18-12, 19-10](#)

configuring

forward-delay time [18-20](#)hello time [18-19](#)link type for rapid convergence [18-22](#)maximum aging time [18-21](#)maximum hop count [18-21](#)MST region [18-13](#)path cost [18-18](#)port priority [18-17](#)root switch [18-14](#)secondary root switch [18-16](#)switch priority [18-19](#)

CST

defined [18-3](#)operations between regions [18-3](#)default configuration [18-12](#)default optional feature configuration [19-9](#)displaying status [18-23](#)enabling the mode [18-13](#)

MSTP (continued)

EtherChannel guard

- described 19-7
- enabling 19-14

extended system ID

- effects on root switch 18-14
- effects on secondary root switch 18-16
- unexpected behavior 18-15

instances supported 17-9

interface state, blocking to forwarding 19-2

interoperability and compatibility among modes 17-10

interoperability with 802.1D

- described 18-5
- restarting migration process 18-22

IST

- defined 18-2
- master 18-3
- operations within a region 18-3

loop guard

- described 19-9
- enabling 19-15

mapping VLANs to MST instance 18-13

MST region

- CIST 18-3
- configuring 18-13
- described 18-2
- hop-count mechanism 18-4
- IST 18-2
- supported spanning-tree instances 18-2

optional features supported 1-5

overview 18-2

Port Fast

- described 19-2
- enabling 19-10

preventing root switch selection 19-8

root guard

- described 19-8
- enabling 19-14

MSTP (continued)

root switch

- configuring 18-15
- effects of extended system ID 18-14
- unexpected behavior 18-15
- shutdown Port Fast-enabled port 19-2
- status, displaying 18-23

multicast groups

- Immediate Leave 23-5
- joining 23-3
- leaving 23-4
- static joins 23-9

multicast packets

- ACLs on 31-40
- blocking 24-7

multicast router interfaces, monitoring 23-13

multicast router ports, adding 23-8

Multicast Source Discovery Protocol

See MSDP

multicast storm 24-1

multicast storm-control command 24-4

Multicast VLAN Registration

See MVR

Multiple HSRP

See MHSRP

MVR

- and address aliasing 23-17
- configuring interfaces 23-18
- default configuration 23-16
- described 23-13
- modes 23-17
- monitoring 23-20
- setting global parameters 23-17
- support for 1-3

N

named IP ACLs [31-15](#)

NameSpace Mapper

See NSM

native VLAN

and 802.1Q tunneling [16-4](#)

configuring [12-23](#)

default [12-13](#)

neighbor discovery/recovery, EIGRP [34-33](#)

neighbors, BGP [34-53](#)

Network Assistant

benefits [1-2](#)

described [1-4](#)

downloading image files [1-2](#)

guide mode [1-2](#)

management options [1-2](#)

requirements [xxxviii](#)

upgrading a switch [B-18](#)

wizards [1-2](#)

network configuration examples

increasing network performance [1-13](#)

large network [1-16](#)

long-distance, high-bandwidth transport [1-17](#)

providing network services [1-14](#)

small to medium-sized network [1-14](#)

network design

performance [1-13](#)

services [1-14](#)

network management

CDP [25-1](#)

RMON [28-1](#)

SNMP [30-1](#)

Network Time Protocol

See NTP

no commands [2-4](#)

nonhierarchical policy maps

configuration guidelines [32-34](#)

configuring [32-49](#)

described [32-9](#)

non-IP traffic filtering [31-27](#)

nontrunking mode [12-18](#)

normal-range VLANs

configuration modes [12-7](#)

defined [12-1](#)

no switchport command [10-4](#)

note, described [xxxviii](#)

not-so-stubby areas

See NSSA

NSM [4-3](#)

NSSA, OSPF [34-28](#)

NTP

associations

authenticating [6-5](#)

defined [6-2](#)

enabling broadcast messages [6-7](#)

peer [6-6](#)

server [6-6](#)

default configuration [6-4](#)

displaying the configuration [6-11](#)

overview [6-2](#)

restricting access

creating an access group [6-9](#)

disabling NTP services per interface [6-10](#)

source IP address, configuring [6-10](#)

stratum [6-2](#)

support for [1-4](#)

synchronizing devices [6-6](#)

time

services [6-2](#)

synchronizing [6-2](#)

O

Open Shortest Path First

See OSPF

optimizing system resources 7-1

options, management 1-4

OSPF

area parameters, configuring 34-28

configuring 34-26

default configuration

metrics 34-30

route 34-30

settings 34-25

described 34-24

for IPv6 35-18

interface parameters, configuring 34-27

LSA group pacing 34-31

monitoring 34-32

router IDs 34-31

route summarization 34-29

support for 1-8

virtual links 34-29

out-of-profile markdown 1-8

P

packet modification, with QoS 32-20

PAgP

Layer 2 protocol tunneling 16-9

See EtherChannel

parallel paths, in routing tables 34-61

passive interfaces

configuring 34-69

OSPF 34-30

passwords

default configuration 8-2

disabling recovery of 8-5

encrypting 8-4

for security 1-6

passwords (continued)

overview 8-1

recovery of 40-3

setting

enable 8-3

enable secret 8-4

Telnet 8-6

with usernames 8-7

VTP domain 13-8

path cost

MSTP 18-18

STP 17-18

path MTU discovery 35-4

PBR

defined 34-66

enabling 34-68

fast-switched policy-based routing 34-69

local policy-based routing 34-69

peers, BGP 34-53

performance, network design 1-13

performance features 1-3

persistent self-signed certificate 8-42

per-VLAN spanning-tree plus

See PVST+

physical ports 10-2

PIM

default configuration 37-8

dense mode

overview 37-4

rendezvous point (RP), described 37-4

RPF lookups 37-7

displaying neighbors 37-50

enabling a mode 37-11

overview 37-3

router-query message interval, modifying 37-25

shared tree and source tree, overview 37-22

shortest path tree, delaying the use of 37-24

PIM (continued)

sparse mode

- join messages and shared tree [37-4](#)

- overview [37-4](#)

- prune messages [37-5](#)

- RPF lookups [37-7](#)

- support for [1-9](#)

versions

- interoperability [37-8](#)

- troubleshooting interoperability problems [37-22](#)

- v2 improvements [37-4](#)

PIM-DVMRP, as snooping method [23-8](#)

ping

- character output description [40-14](#)

- executing [40-14](#)

- overview [40-13](#)

PoE

- auto mode [10-7](#)

- CDP with power consumption, described [10-6](#)

- CDP with power negotiation, described [10-6](#)

- Cisco intelligent power management [10-6](#)

- configuring [10-20](#)

- devices supported [10-5](#)

- high-power devices operating in low-power mode [10-6](#)

- IEEE power classification levels [10-7](#)

- powered-device detection and initial power allocation [10-6](#)

- power management modes [10-7](#)

- power negotiation extensions to CDP [10-6](#)

- standards supported [10-6](#)

- static mode [10-8](#)

- supported watts per port [10-6](#)

- troubleshooting [40-12](#)

policed-DSCP map for QoS [32-62](#)

policers

configuring

- for each matched traffic class [32-49](#)

- for more than one traffic class [32-58](#)

policers (continued)

- described [32-4](#)

- displaying [32-78](#)

- number of [32-34](#)

- types of [32-9](#)

policing

- described [32-4](#)

hierarchical

- See hierarchical policy maps

- token-bucket algorithm [32-9](#)

policy-based routing

- See PBR

policy maps

- hierarchical [32-8](#)

policy maps for QoS

- characteristics of [32-49](#)

- described [32-7](#)

- displaying [32-79](#)

hierarchical on SVIs

- configuration guidelines [32-34](#)

- configuring [32-52](#)

- described [32-11](#)

nonhierarchical on physical ports

- configuration guidelines [32-34](#)

- configuring [32-49](#)

- described [32-9](#)

port ACLs

- defined [31-2](#)

- types of [31-3](#)

Port Aggregation Protocol

- See EtherChannel

port-based authentication

- accounting [9-5](#)

authentication server

- defined [9-2](#)

- RADIUS server [9-2](#)

- client, defined [9-2](#)

- configuration guidelines [9-11](#)

- port-based authentication (continued)
 - configuring
 - 802.1x authentication [9-12](#)
 - guest VLAN [9-19](#)
 - host mode [9-18](#)
 - manual re-authentication of a client [9-15](#)
 - periodic re-authentication [9-15](#)
 - quiet period [9-15](#)
 - RADIUS server [9-14](#)
 - RADIUS server parameters on the switch [9-13](#)
 - switch-to-client frame-retransmission number [9-17](#)
 - switch-to-client retransmission time [9-16](#)
 - default configuration [9-10](#)
 - described [9-1](#)
 - device roles [9-2](#)
 - displaying statistics [9-21](#)
 - EAPOL-start frame [9-3](#)
 - EAP-request/identity frame [9-3](#)
 - EAP-response/identity frame [9-3](#)
 - encapsulation [9-3](#)
 - guest VLAN
 - configuration guidelines [9-9](#)
 - described [9-8](#)
 - host mode [9-5](#)
 - initiation and message exchange [9-3](#)
 - method lists [9-12](#)
 - multiple-hosts mode, described [9-5](#)
 - per-user ACLs
 - AAA authorization [9-12](#)
 - configuration tasks [9-9](#)
 - described [9-9](#)
 - RADIUS server attributes [9-9](#)
 - ports
 - authorization state and dot1x port-control command [9-4](#)
 - authorized and unauthorized [9-4](#)
 - voice VLAN [9-7](#)
- port-based authentication (continued)
 - port security
 - and voice VLAN [9-6](#)
 - described [9-6](#)
 - interactions [9-6](#)
 - multiple-hosts mode [9-5](#)
 - resetting to default values [9-20](#)
 - statistics, displaying [9-21](#)
 - switch
 - as proxy [9-2](#)
 - RADIUS client [9-2](#)
 - upgrading from a previous release [32-27](#)
 - VLAN assignment
 - AAA authorization [9-12](#)
 - characteristics [9-7](#)
 - configuration tasks [9-8](#)
 - described [9-7](#)
 - voice VLAN
 - described [9-7](#)
 - PVID [9-7](#)
 - VVID [9-7](#)
- port blocking [1-3, 24-6](#)
- port-channel
 - See EtherChannel
- Port Fast
 - described [19-2](#)
 - enabling [19-10](#)
 - mode, spanning tree [12-29](#)
 - support for [1-5](#)
- port membership modes, VLAN [12-3](#)
- port priority
 - MSTP [18-17](#)
 - STP [17-16](#)
- ports
 - 802.1Q tunnel [12-4](#)
 - access [10-3](#)
 - blocking [24-6](#)
 - dynamic access [12-3](#)
 - protected [24-5](#)

ports (continued)

- routed [10-4](#)
- secure [24-7](#)
- static-access [12-3, 12-11](#)
- switch [10-2](#)
- trunks [12-3, 12-16](#)
- VLAN assignments [12-11](#)

port security

- aging [24-15](#)
- and QoS trusted boundary [32-39](#)
- configuring [24-12](#)
- default configuration [24-10](#)
- described [24-7](#)
- displaying [24-16](#)
- on trunk ports [24-13](#)
- sticky learning [24-8](#)
- violations [24-9](#)
- with other features [24-10](#)

port-shutdown response, VMPS [12-28](#)

Power over Ethernet

See PoE

preferential treatment of traffic

See QoS

prefix lists, BGP [34-50](#)preventing unauthorized access [8-1](#)primary links [20-1](#)primary VLANs [14-1, 14-3](#)

priority

- HSRP [36-7](#)
- overriding CoS [15-6](#)
- trusting CoS [15-6](#)

private VLAN edge ports

See protected ports

private VLANs

- across multiple switches [14-4](#)
- and SDM template [14-4](#)
- and SVIs [14-5](#)
- benefits of [14-1](#)
- community ports [14-2](#)

private VLANs (continued)

- community VLANs [14-2, 14-3](#)
- configuration guidelines [14-6, 14-7, 14-8](#)
- configuration tasks [14-6](#)
- configuring [14-9](#)
- default configuration [14-6](#)
- end station access to [14-3](#)
- IP addressing [14-3](#)
- isolated port [14-2](#)
- isolated VLANs [14-2, 14-3](#)
- mapping [14-13](#)
- monitoring [14-14](#)

ports

- community [14-2](#)
- configuration guidelines [14-8](#)
- configuring host ports [14-11](#)
- configuring promiscuous ports [14-12](#)
- described [12-4](#)
- isolated [14-2](#)
- promiscuous [14-2](#)
- primary VLANs [14-1, 14-3](#)
- promiscuous ports [14-2](#)
- secondary VLANs [14-2](#)
- subdomains [14-1](#)
- traffic in [14-5](#)

privileged EXEC mode [2-2](#)

privilege levels

- changing the default for lines [8-9](#)
- command switch [5-4](#)
- exiting [8-10](#)
- logging into [8-10](#)
- mapping on member switches [5-4](#)
- overview [8-2, 8-8](#)
- setting a command with [8-8](#)

promiscuous ports

- configuring [14-12](#)
- defined [14-2](#)

protected ports [1-6, 24-5](#)protocol-dependent modules, EIGRP [34-34](#)

Protocol-Independent Multicast Protocol

See PIM

proxy ARP

configuring [34-10](#)

definition [34-8](#)

with IP routing disabled [34-11](#)

pruning, VTP

disabling

in VTP domain [13-14](#)

on a port [12-23](#)

enabling

in VTP domain [13-14](#)

on a port [12-22](#)

examples [13-5](#)

overview [13-4](#)

pruning-eligible list

changing [12-22](#)

for VTP pruning [13-4](#)

VLANs [13-14](#)

PVST+

802.1Q trunking interoperability [17-10](#)

described [17-9](#)

instances supported [17-9](#)

Q

QoS

and MQC commands [32-1](#)

auto-QoS

categorizing traffic [32-21](#)

configuration and defaults display [32-31](#)

configuration guidelines [32-26](#)

described [32-21](#)

disabling [32-28](#)

displaying generated commands [32-28](#)

displaying the initial configuration [32-31](#)

effects on running configuration [32-26](#)

egress queue defaults [32-22](#)

enabling for VoIP [32-28](#)

QoS (continued)

auto-QoS

example configuration [32-29](#)

ingress queue defaults [32-22](#)

list of generated commands [32-23](#)

basic model [32-4](#)

classification

class maps, described [32-7](#)

defined [32-4](#)

DSCP transparency, described [32-40](#)

flowchart [32-6](#)

forwarding treatment [32-3](#)

in frames and packets [32-3](#)

IP ACLs, described [32-5, 32-7](#)

MAC ACLs, described [32-5, 32-7](#)

options for IP traffic [32-5](#)

options for non-IP traffic [32-5](#)

policy maps, described [32-7](#)

trust DSCP, described [32-5](#)

trusted CoS, described [32-5](#)

trust IP precedence, described [32-5](#)

class maps

configuring [32-47](#)

displaying [32-78](#)

configuration guidelines

auto-QoS [32-26](#)

standard QoS [32-34](#)

configuring

aggregate policers [32-58](#)

auto-QoS [32-21](#)

default port CoS value [32-38](#)

DSCP maps [32-60](#)

DSCP transparency [32-40](#)

DSCP trust states bordering another domain [32-41](#)

egress queue characteristics [32-71](#)

ingress queue characteristics [32-66](#)

IP extended ACLs [32-45](#)

IP standard ACLs [32-43](#)

MAC ACLs [32-46](#)

QoS (continued)

configuring

- policy maps, hierarchical [32-52](#)
- policy maps on physical ports [32-49](#)
- port trust states within the domain [32-36](#)
- trusted boundary [32-39](#)

default auto configuration [32-21](#)default standard configuration [32-32](#)displaying statistics [32-78](#)DSCP transparency [32-40](#)

egress queues

- allocating buffer space [32-71](#)
- buffer allocation scheme, described [32-19](#)
- configuring shaped weights for SRR [32-75](#)
- configuring shared weights for SRR [32-76](#)
- described [32-4](#)
- displaying the threshold map [32-74](#)
- flowchart [32-18](#)
- mapping DSCP or CoS values [32-73](#)
- scheduling, described [32-4](#)
- setting WTD thresholds [32-71](#)
- WTD, described [32-20](#)

enabling globally [32-35](#)

flowcharts

- classification [32-6](#)
- egress queueing and scheduling [32-18](#)
- ingress queueing and scheduling [32-16](#)
- policing and marking [32-10](#)

implicit deny [32-7](#)

ingress queues

- allocating bandwidth [32-68](#)
- allocating buffer space [32-68](#)
- buffer and bandwidth allocation, described [32-17](#)
- configuring shared weights for SRR [32-68](#)
- configuring the priority queue [32-70](#)
- described [32-4](#)
- displaying the threshold map [32-67](#)
- flowchart [32-16](#)
- mapping DSCP or CoS values [32-66](#)

QoS (continued)

ingress queues

- priority queue, described [32-17](#)
- scheduling, described [32-4](#)
- setting WTD thresholds [32-66](#)
- WTD, described [32-17](#)

IP phones

- automatic classification and queuing [32-21](#)
- detection and trusted settings [32-21](#), [32-39](#)

limiting bandwidth on egress interface [32-77](#)

mapping tables

- CoS-to-DSCP [32-60](#)
- displaying [32-78](#)
- DSCP-to-CoS [32-63](#)
- DSCP-to-DSCP-mutation [32-64](#)
- IP-precedence-to-DSCP [32-61](#)
- policed-DSCP [32-62](#)
- types of [32-13](#)

marked-down actions [32-51](#), [32-55](#)marking, described [32-4](#), [32-8](#)overview [32-2](#)packet modification [32-20](#)

policers

- configuring [32-51](#), [32-55](#), [32-58](#)
- described [32-8](#)
- displaying [32-78](#)
- number of [32-34](#)
- types of [32-9](#)

policies, attaching to an interface [32-9](#)

policing

- described [32-4](#), [32-8](#)
- token bucket algorithm [32-9](#)

policy maps

- characteristics of [32-49](#)
- displaying [32-79](#)
- hierarchical [32-8](#)
- hierarchical on SVIs [32-52](#)
- nonhierarchical on physical ports [32-49](#)

QoS label, defined [32-4](#)

QoS (continued)

queues

- configuring egress characteristics [32-71](#)
- configuring ingress characteristics [32-66](#)
- high priority (expedite) [32-20, 32-77](#)
- location of [32-14](#)
- SRR, described [32-15](#)
- WTD, described [32-14](#)

rewrites [32-20](#)support for [1-7](#)

trust states

- bordering another domain [32-41](#)
- described [32-5](#)
- trusted device [32-39](#)
- within the domain [32-36](#)

quality of service

See QoS

queries, IGMP [23-3](#)

R

RADIUS

attributes

- vendor-proprietary [8-31](#)
- vendor-specific [8-29](#)

configuring

- accounting [8-28](#)
- authentication [8-23](#)
- authorization [8-27](#)
- communication, global [8-21, 8-29](#)
- communication, per-server [8-20, 8-21](#)
- multiple UDP ports [8-20](#)

default configuration [8-20](#)defining AAA server groups [8-25](#)displaying the configuration [8-31](#)identifying the server [8-20](#)limiting the services to the user [8-27](#)method list, defined [8-20](#)operation of [8-19](#)

RADIUS (continued)

- overview [8-18](#)
- suggested network environments [8-18](#)
- support for [1-7](#)
- tracking services accessed by user [8-28](#)

range

- macro [10-12](#)
- of interfaces [10-11](#)

rapid convergence [18-7](#)

rapid per-VLAN spanning-tree plus

See rapid PVST+

rapid PVST+

- 802.1Q trunking interoperability [17-10](#)
- described [17-9](#)
- instances supported [17-9](#)

Rapid Spanning Tree Protocol

See RSTP

RARP [34-8](#)rcommand command [5-3](#)

RCP

configuration files

- downloading [B-16](#)
- overview [B-15](#)
- preparing the server [B-15](#)
- uploading [B-17](#)

image files

- deleting old image [B-31](#)
- downloading [B-30](#)
- preparing the server [B-28](#)
- uploading [B-32](#)

reconfirmation interval, VMPS, changing [12-31](#)recovery procedures [40-1](#)

redundancy

EtherChannel [33-2](#)HSRP [36-1](#)

STP

- backbone [17-8](#)
- path cost [12-26](#)
- port priority [12-24](#)

- redundant links and UplinkFast [19-12](#)
- reliable transport protocol, EIGRP [34-33](#)
- reloading software [3-15](#)
- Remote Authentication Dial-In User Service
 - See RADIUS
- Remote Copy Protocol
 - See RCP
- Remote Network Monitoring
 - See RMON
- Remote SPAN
 - See RSPAN
- report suppression, IGMP
 - described [23-5](#)
 - disabling [23-12](#)
- requirements
 - cluster [xxxix](#)
 - device manager [xxxviii](#)
 - Network Assistant [xxxviii](#)
- resequencing ACL entries [31-15](#)
- resets, in BGP [34-45](#)
- resetting a UDLD-shutdown interface [26-6](#)
- restricting access
 - NTP services [6-8](#)
 - overview [8-1](#)
 - passwords and privilege levels [8-2](#)
 - RADIUS [8-17](#)
 - TACACS+ [8-10](#)
- retry count, VMPS, changing [12-32](#)
- reverse address resolution [34-8](#)
- Reverse Address Resolution Protocol
 - See RARP
- RFC
 - 1058, RIP [34-19](#)
 - 1112, IP multicast and IGMP [23-2](#)
 - 1157, SNMPv1 [30-2](#)
 - 1163, BGP [34-39](#)
 - 1166, IP addresses [34-5](#)
 - 1253, OSPF [34-24](#)
 - 1267, BGP [34-39](#)
- RFC (continued)
 - 1305, NTP [6-2](#)
 - 1587, NSSAs [34-24](#)
 - 1757, RMON [28-2](#)
 - 1771, BGP [34-39](#)
 - 1901, SNMPv2C [30-2](#)
 - 1902 to 1907, SNMPv2 [30-2](#)
 - 2236, IP multicast and IGMP [23-2](#)
 - 2273-2275, SNMPv3 [30-2](#)
- RIP
 - advertisements [34-19](#)
 - authentication [34-22](#)
 - configuring [34-20](#)
 - default configuration [34-20](#)
 - described [34-19](#)
 - for IPv6 [35-16](#)
 - hop counts [34-19](#)
 - split horizon [34-22](#)
 - summary addresses [34-22](#)
 - support for [1-8](#)
- RMON
 - default configuration [28-3](#)
 - displaying status [28-6](#)
 - enabling alarms and events [28-3](#)
 - groups supported [28-2](#)
 - overview [28-1](#)
 - statistics
 - collecting group Ethernet [28-6](#)
 - collecting group history [28-5](#)
 - support for [1-9](#)
- root guard
 - described [19-8](#)
 - enabling [19-14](#)
 - support for [1-5](#)
- root switch
 - MSTP [18-14](#)
 - STP [17-14](#)
- route calculation timers, OSPF [34-30](#)
- route dampening, BGP [34-57](#)

- routed packets, ACLs on [31-39](#)
- routed ports
 - configuring [34-3](#)
 - defined [10-4](#)
 - IP addresses on [10-22, 34-4](#)
- route-map command [34-68](#)
- route maps
 - BGP [34-48](#)
 - policy-based routing [34-67](#)
- router ACLs
 - defined [31-2](#)
 - types of [31-4](#)
- route reflectors, BGP [34-56](#)
- router ID, OSPF [34-31](#)
- route selection, BGP [34-46](#)
- route summarization, OSPF [34-29](#)
- routing
 - default [34-2](#)
 - dynamic [34-3](#)
 - redistribution of information [34-63](#)
 - static [34-3](#)
- routing domain confederation, BGP [34-55](#)
- Routing Information Protocol
 - See RIP
- routing protocol administrative distances [34-62](#)
- RSPAN
 - characteristics [27-7](#)
 - configuration guidelines [27-16](#)
 - default configuration [27-9](#)
 - destination ports [27-6](#)
 - displaying status [27-23](#)
 - interaction with other features [27-8](#)
 - monitored ports [27-5](#)
 - monitoring ports [27-6](#)
 - overview [1-9, 27-1](#)
 - received traffic [27-4](#)
 - session limits [27-10](#)
- RSPAN (continued)
 - sessions
 - creating [27-17](#)
 - defined [27-3](#)
 - limiting source traffic to specific VLANs [27-22](#)
 - specifying monitored ports [27-17](#)
 - with ingress traffic enabled [27-20](#)
 - source ports [27-5](#)
 - transmitted traffic [27-5](#)
 - VLAN-based [27-6](#)
- RSTP
 - active topology [18-6](#)
 - BPDU
 - format [18-9](#)
 - processing [18-10](#)
 - designated port, defined [18-6](#)
 - designated switch, defined [18-6](#)
 - interoperability with 802.1D
 - described [18-5](#)
 - restarting migration process [18-22](#)
 - topology changes [18-10](#)
 - overview [18-6](#)
 - port roles
 - described [18-6](#)
 - synchronized [18-8](#)
 - proposal-agreement handshake process [18-7](#)
 - rapid convergence
 - described [18-7](#)
 - edge ports and Port Fast [18-7](#)
 - point-to-point links [18-7, 18-22](#)
 - root ports [18-7](#)
 - root port, defined [18-6](#)
 - See also MSTP
- running configuration, saving [3-10](#)

S

- scheduled reloads [3-15](#)
- SDM
 - described [7-1](#)
 - templates
 - configuring [7-4](#)
 - number of [7-1](#)
- SDM template
 - configuration guidelines [7-4](#)
 - configuring [7-3](#)
 - dual IPv4 and IPv6 [7-2](#)
 - types of [7-1](#)
- secondary VLANs [14-2](#)
- secure HTTP client
 - configuring [8-47](#)
 - displaying [8-47](#)
- secure HTTP server
 - configuring [8-45](#)
 - displaying [8-47](#)
- secure MAC addresses
 - deleting [24-14](#)
 - maximum number of [24-8](#)
 - types of [24-8](#)
- secure ports, configuring [24-7](#)
- secure remote connections [8-38](#)
- Secure Shell
 - See SSH
- Secure Socket Layer
 - See SSL
- security, port [24-7](#)
- security features [1-6](#)
- sequence numbers in log messages [29-7](#)
- server mode, VTP [13-3](#)
- service-provider network, MSTP and RSTP [18-1](#)
- service-provider networks
 - and 802.1Q tunneling [16-1](#)
 - and customer VLANs [16-2](#)
- service-provider networks (continued)
 - Layer 2 protocols across [16-8](#)
 - Layer 2 protocol tunneling for EtherChannels [16-9](#)
- set-request operation [30-4](#)
- setup program
 - failed command switch replacement [40-10](#)
 - replacing failed command switch [40-8](#)
- severity levels, defining in system messages [29-8](#)
- SFPs
 - monitoring status of [1-10, 10-25, 40-13](#)
 - security and identification [40-12](#)
 - status, displaying [1-10](#)
- shaped round robin
 - See SRR
- show access-lists hw-summary command [31-22](#)
- show and more command output, filtering [2-8](#)
- show cdp traffic command [25-5](#)
- show cluster members command [5-3](#)
- show configuration command [10-21](#)
- show forward command [40-21](#)
- show interfaces command [10-17, 10-21](#)
- show l2protocol command [16-14, 16-16](#)
- show platform forward command [40-21](#)
- show running-config command
 - displaying ACLs [31-20, 31-21, 31-32, 31-34](#)
 - interface description in [10-21](#)
- shutdown command on interfaces [10-26](#)
- shutdown threshold for Layer 2 protocol packets [16-11](#)
- Simple Network Management Protocol
 - See SNMP
- Smartports macros
 - applying Cisco-default macros [11-6](#)
 - applying global parameter values [11-5, 11-6](#)
 - applying macros [11-5](#)
 - applying parameter values [11-5, 11-7](#)
 - configuration guidelines [11-3](#)
 - creating [11-4](#)
 - default configuration [11-2](#)
 - defined [11-1](#)

Smartports macros (continued)

- displaying [11-8](#)
- tracing [11-3](#)
- website [11-2](#)

SMI [1-1](#)SNAP [25-1](#)

SNMP

- accessing MIB variables with [30-4](#)
- agent
 - described [30-4](#)
 - disabling [30-8](#)
- authentication level [30-10](#)
- community strings
 - configuring [30-8](#)
 - for cluster switches [30-4](#)
 - overview [30-4](#)
- configuration examples [30-15](#)
- default configuration [30-6](#)
- engine ID [30-7](#)
- groups [30-7, 30-9](#)
- host [30-7](#)
- ifIndex values [30-5](#)
- in-band management [1-5](#)
- informs
 - and trap keyword [30-11](#)
 - described [30-5](#)
 - differences from traps [30-5](#)
 - disabling [30-14](#)
 - enabling [30-14](#)
- limiting access by TFTP servers [30-15](#)
- limiting system log messages to NMS [29-9](#)
- manager functions [1-4, 30-3](#)
- managing clusters with [5-4](#)
- MIBs
 - location of [A-3](#)
 - supported [A-1](#)
- notifications [30-5](#)
- overview [30-1, 30-4](#)
- security levels [30-3](#)

SNMP (continued)

- status, displaying [30-16](#)
- system contact and location [30-14](#)
- trap manager, configuring [30-13](#)
- traps
 - described [30-3, 30-5](#)
 - differences from informs [30-5](#)
 - disabling [30-14](#)
 - enabling [30-11](#)
 - enabling MAC address notification [6-22](#)
 - overview [30-1, 30-4](#)
 - types of [30-11](#)
 - users [30-7, 30-9](#)
 - versions supported [30-2](#)
- SNMPv1 [30-2](#)
- SNMPv2C [30-2](#)
- SNMPv3 [30-2](#)
- snooping, IGMP [23-1](#)
- software images
 - location in flash [B-19](#)
 - recovery procedures [40-2](#)
 - scheduling reloads [3-16](#)
 - tar file format, described [B-19](#)
 - See also downloading and uploading
- source addresses, in ACLs [31-12](#)
- source-and-destination-IP address based forwarding, EtherChannel [33-7](#)
- source-and-destination MAC address forwarding, EtherChannel [33-6](#)
- source-IP address based forwarding, EtherChannel [33-6](#)
- source-MAC address forwarding, EtherChannel [33-6](#)
- SPAN
 - configuration guidelines [27-10](#)
 - default configuration [27-9](#)
 - destination ports [27-6](#)
 - displaying status [27-23](#)
 - interaction with other features [27-8](#)
 - monitored ports [27-5](#)
 - monitoring ports [27-6](#)

SPAN (continued)

- overview [1-9, 27-1](#)
- ports, restrictions [24-11](#)
- received traffic [27-4](#)
- session limits [27-10](#)
- sessions
 - configuring ingress forwarding [27-14, 27-21](#)
 - creating [27-11](#)
 - defined [27-3](#)
 - limiting source traffic to specific VLANs [27-15](#)
 - removing destination (monitoring) ports [27-12](#)
 - specifying monitored ports [27-11](#)
 - with ingress traffic enabled [27-13](#)
- source ports [27-5](#)
- transmitted traffic [27-5](#)
- VLAN-based [27-6](#)

spanning tree and native VLANs [12-19](#)

Spanning Tree Protocol

See STP

SPAN traffic [27-4](#)speed, configuring on interfaces [10-15](#)split horizon, RIP [34-22](#)

SRR

- configuring
 - shaped weights on egress queues [32-75](#)
 - shared weights on egress queues [32-76](#)
 - shared weights on ingress queues [32-68](#)

described [32-15](#)

shaped mode [32-15](#)

shared mode [32-15](#)

support for [1-8](#)

SSH

- configuring [8-39](#)
- cryptographic software image [8-37](#)
- described [1-5, 8-38](#)
- encryption methods [8-38](#)
- user authentication methods, supported [8-38](#)

SSL

- configuration guidelines [8-44](#)
- configuring a secure HTTP client [8-47](#)
- configuring a secure HTTP server [8-45](#)
- cryptographic software image [8-41](#)
- described [8-41](#)
- monitoring [8-47](#)

standard multilayer image

See SMI

standby command switch, requirements [5-2](#)standby ip command [36-5](#)standby links [20-1](#)standby router [36-1](#)standby timers, HSRP [36-9](#)

startup configuration

booting

manually [3-13](#)

specific image [3-13](#)

clearing [B-18](#)

configuration file

automatically downloading [3-12](#)

specifying the filename [3-12](#)

default boot configuration [3-12](#)

stateless autoconfiguration [35-4](#)

static access ports

assigning to VLAN [12-11](#)

defined [10-3, 12-3](#)

static addresses

See addresses

static IP routing [1-9](#)static MAC addressing [1-6](#)

static routes

configuring [34-61](#)

configuring for IPv6 [35-14](#)

static routing [34-3](#)static VLAN membership [12-2](#)

- statistics
 - 802.1x [9-21](#)
 - CDP [25-5](#)
 - interface [10-25](#)
 - IP multicast routing [37-50](#)
 - OSPF [34-32](#)
 - QoS ingress and egress [32-78](#)
 - RMON group Ethernet [28-6](#)
 - RMON group history [28-5](#)
 - SNMP input and output [30-16](#)
 - VTP [13-16](#)
- sticky learning [24-8](#)
- storm control
 - configuring [24-3](#)
 - described [24-1](#)
 - disabling [24-5](#)
 - displaying [24-16](#)
 - support for [1-3](#)
 - thresholds [24-1](#)
- STP
 - 802.1D and bridge ID [17-4](#)
 - 802.1D and multicast addresses [17-8](#)
 - 802.1t and VLAN identifier [17-4](#)
 - accelerating root port selection [19-4](#)
 - BackboneFast
 - described [19-5](#)
 - disabling [19-14](#)
 - enabling [19-13](#)
 - BPDU filtering
 - described [19-3](#)
 - disabling [19-12](#)
 - enabling [19-12](#)
 - BPDU guard
 - described [19-2](#)
 - disabling [19-11](#)
 - enabling [19-11](#)
 - BPDU message exchange [17-3](#)
 - configuration guidelines [17-12, 19-10](#)
- STP (continued)
 - configuring
 - forward-delay time [17-21](#)
 - hello time [17-20](#)
 - maximum aging time [17-21](#)
 - path cost [17-18](#)
 - port priority [17-16](#)
 - root switch [17-14](#)
 - secondary root switch [17-16](#)
 - spanning-tree mode [17-13](#)
 - switch priority [17-19](#)
 - counters, clearing [17-22](#)
 - default configuration [17-11](#)
 - default optional feature configuration [19-9](#)
 - designated port, defined [17-3](#)
 - designated switch, defined [17-3](#)
 - detecting indirect link failures [19-5](#)
 - disabling [17-14](#)
 - displaying status [17-22](#)
 - EtherChannel guard
 - described [19-7](#)
 - disabling [19-14](#)
 - enabling [19-14](#)
 - extended system ID
 - effects on root switch [17-14](#)
 - effects on the secondary root switch [17-16](#)
 - overview [17-4](#)
 - unexpected behavior [17-15](#)
 - features supported [1-5](#)
 - inferior BPDU [17-3](#)
 - instances supported [17-9](#)
 - interface state, blocking to forwarding [19-2](#)
 - interface states
 - blocking [17-6](#)
 - disabled [17-7](#)
 - forwarding [17-5, 17-6](#)
 - learning [17-6](#)
 - listening [17-6](#)
 - overview [17-4](#)

STP (continued)

- interoperability and compatibility among modes [17-10](#)
- keepalive messages [17-2](#)
- Layer 2 protocol tunneling [16-8](#)
- limitations with 802.1Q trunks [17-10](#)
- load sharing
 - overview [12-24](#)
 - using path costs [12-26](#)
 - using port priorities [12-24](#)
- loop guard
 - described [19-9](#)
 - enabling [19-15](#)
- modes supported [17-9](#)
- multicast addresses, effect of [17-8](#)
- optional features supported [1-5](#)
- overview [17-2](#)
- path costs [12-26](#)
- Port Fast
 - described [19-2](#)
 - enabling [19-10](#)
- port priorities [12-25](#)
- preventing root switch selection [19-8](#)
- protocols supported [17-9](#)
- redundant connectivity [17-8](#)
- root guard
 - described [19-8](#)
 - enabling [19-14](#)
- root port, defined [17-3](#)
- root switch
 - configuring [17-14](#)
 - effects of extended system ID [17-4, 17-14](#)
 - election [17-3](#)
 - unexpected behavior [17-15](#)
- shutdown Port Fast-enabled port [19-2](#)
- status, displaying [17-22](#)
- superior BPDU [17-3](#)
- timers, described [17-20](#)

STP (continued)

- UplinkFast
 - described [19-3](#)
 - enabling [19-12](#)
 - VLAN-bridge [17-10](#)
- stratum, NTP [6-2](#)
- stub areas, OSPF [34-28](#)
- subdomains, private VLAN [14-1](#)
- subnet mask [34-5](#)
- subnet zero [34-6](#)
- success response, VMPS [12-28](#)
- summer time [6-13](#)
- SunNet Manager [1-4](#)
- supernet [34-6](#)
- SVIs
 - and IP unicast routing [34-3](#)
 - and router ACLs [31-4](#)
 - connecting VLANs [10-8](#)
 - defined [10-4](#)
 - routing between VLANs [12-2](#)
- switch clustering technology [5-1](#)
 - See also clusters, switch
- switch console port [1-5](#)
- Switch Database Management
 - See SDM
- switched packets, ACLs on [31-38](#)
- Switched Port Analyzer
 - See SPAN
- switched ports [10-2](#)
- switchport block multicast command [24-7](#)
- switchport block unicast command [24-7](#)
- switchport command [10-14](#)
- switchport mode dot1q-tunnel command [16-6](#)
- switchport protected command [24-6](#)
- switch priority
 - MSTP [18-19](#)
 - STP [17-19](#)
- switch software features [1-1](#)

- switch virtual interface
 - See SVI
- synchronization, BGP [34-43](#)
- syslog
 - See system message logging
- system clock
 - configuring
 - daylight saving time [6-13](#)
 - manually [6-11](#)
 - summer time [6-13](#)
 - time zones [6-12](#)
 - displaying the time and date [6-12](#)
 - overview [6-2](#)
 - See also NTP
- system message logging
 - default configuration [29-3](#)
 - defining error message severity levels [29-8](#)
 - disabling [29-3](#)
 - displaying the configuration [29-12](#)
 - enabling [29-4](#)
 - facility keywords, described [29-12](#)
 - level keywords, described [29-9](#)
 - limiting messages [29-9](#)
 - message format [29-2](#)
 - overview [29-1](#)
 - sequence numbers, enabling and disabling [29-7](#)
 - setting the display destination device [29-4](#)
 - synchronizing log messages [29-5](#)
 - syslog facility [1-9](#)
 - time stamps, enabling and disabling [29-7](#)
 - UNIX syslog servers
 - configuring the daemon [29-10](#)
 - configuring the logging facility [29-11](#)
 - facilities supported [29-12](#)
- system MTU and 802.1Q tunneling [16-5](#)
- system name
 - default configuration [6-15](#)
 - default setting [6-15](#)

- system name (continued)
 - manual configuration [6-15](#)
 - See also DNS
- system prompt
 - default setting [6-14 to 6-15](#)
 - manual configuration [6-15](#)
- system resources, optimizing [7-1](#)

T

- TACACS+
 - accounting, defined [8-11](#)
 - authentication, defined [8-11](#)
 - authorization, defined [8-11](#)
 - configuring
 - accounting [8-17](#)
 - authentication key [8-13](#)
 - authorization [8-16](#)
 - login authentication [8-14](#)
 - default configuration [8-13](#)
 - displaying the configuration [8-17](#)
 - identifying the server [8-13](#)
 - limiting the services to the user [8-16](#)
 - operation of [8-12](#)
 - overview [8-10](#)
 - support for [1-7](#)
 - tracking services accessed by user [8-17](#)
- tagged packets
 - 802.1Q [16-3](#)
 - Layer 2 protocol [16-8](#)
- tar files
 - creating [B-5](#)
 - displaying the contents of [B-6](#)
 - extracting [B-7](#)
 - image file format [B-19](#)
- TDR [1-10](#)

Telnet

- accessing management interfaces [2-9](#)
- number of connections [1-5](#)
- setting a password [8-6](#)

templates, SDM [7-1](#)temporary self-signed certificate [8-42](#)

Terminal Access Controller Access Control System Plus

See TACACS+

terminal lines, setting a password [8-6](#)

TFTP

- configuration files
 - downloading [B-10](#)
 - preparing the server [B-10](#)
 - uploading [B-11](#)
- configuration files in base directory [3-6](#)
- configuring for autoconfiguration [3-5](#)
- image files
 - deleting [B-22](#)
 - downloading [B-21](#)
 - preparing the server [B-21](#)
 - uploading [B-23](#)
- limiting access by servers [30-15](#)

TFTP server [1-4](#)threshold, traffic level [24-2](#)

time

See NTP and system clock

Time Domain Reflector

See TDR

time-range command [31-17](#)time ranges in ACLs [31-17](#)time stamps in log messages [29-7](#)time zones [6-12](#)

Token Ring VLANs

- support for [12-6](#)
- VTP support [13-4](#)

ToS [1-7](#)

traceroute, Layer 2

- and ARP [40-16](#)
- and CDP [40-15](#)
- broadcast traffic [40-15](#)
- described [40-15](#)
- IP addresses and subnets [40-16](#)
- MAC addresses and VLANs [40-15](#)
- multicast traffic [40-15](#)
- multiple devices on a port [40-16](#)
- unicast traffic [40-15](#)
- usage guidelines [40-15](#)

traceroute command [40-17](#)

See also IP traceroute

traffic

- blocking flooded [24-6](#)
- fragmented [31-5](#)
- unfragmented [31-5](#)

traffic policing [1-8](#)traffic suppression [24-1](#)transparent mode, VTP [13-3, 13-12](#)trap-door mechanism [3-2](#)

traps

- configuring MAC address notification [6-22](#)
- configuring managers [30-11](#)
- defined [30-3](#)
- enabling [6-22, 30-11](#)
- notification types [30-11](#)
- overview [30-1, 30-4](#)

troubleshooting

- connectivity problems [40-13, 40-15, 40-16](#)
- detecting unidirectional links [26-1](#)
- displaying crash information [40-23](#)
- PIMv1 and PIMv2 interoperability problems [37-22](#)
- setting packet forwarding [40-21](#)
- SFP security and identification [40-12](#)
- show forward command [40-21](#)
- with CiscoWorks [30-4](#)
- with debug commands [40-19](#)
- with ping [40-13](#)

- troubleshooting (continued)
 - with system message logging [29-1](#)
 - with traceroute [40-16](#)
- trunking encapsulation [1-6](#)
- trunk ports
 - configuring [12-20](#)
 - defined [10-3, 12-3](#)
 - encapsulation [12-20, 12-25, 12-26](#)
 - secure MAC addresses on [24-12](#)
- trunks
 - allowed-VLAN list [12-21](#)
 - configuring [12-20, 12-25, 12-26](#)
 - ISL [12-16](#)
 - load sharing
 - setting STP path costs [12-26](#)
 - using STP port priorities [12-24, 12-25](#)
 - native VLAN for untagged traffic [12-23](#)
 - parallel [12-26](#)
 - pruning-eligible list [12-22](#)
 - to non-DTP device [12-17](#)
 - understanding [12-17](#)
- trusted boundary for QoS [32-39](#)
- trusted port states
 - between QoS domains [32-41](#)
 - classification options [32-5](#)
 - ensuring port security for IP phones [32-39](#)
 - support for [1-8](#)
 - within a QoS domain [32-36](#)
- trustpoints, CA [8-42](#)
- tunneling
 - 802.1Q [16-1](#)
 - defined [16-1](#)
 - Layer 2 protocol [16-8](#)
- tunnel ports
 - 802.1Q, configuring [16-6](#)
 - defined [12-4](#)
 - described [10-3, 16-1](#)
 - incompatibilities with other features [16-6](#)
- twisted-pair Ethernet, detecting unidirectional links [26-1](#)

- type of service
 - See ToS

U

UDLD

- default configuration [26-4](#)
- disabling
 - fiber-optic interfaces [26-5](#)
 - globally [26-5](#)
 - per interface [26-5](#)
- echoing detection mechanism [26-3](#)
- enabling
 - globally [26-5](#)
 - per interface [26-5](#)
- Layer 2 protocol tunneling [16-10](#)
- link-detection mechanism [26-1](#)
- neighbor database [26-2](#)
- overview [26-1](#)
- resetting an interface [26-6](#)
- status, displaying [26-6](#)
- support for [1-5](#)

UDP, configuring [34-14](#)

- unauthorized ports with 802.1x [9-4](#)
- unicast MAC address filtering [1-4](#)
 - and adding static addresses [6-26](#)
 - and broadcast MAC addresses [6-25](#)
 - and CPU packets [6-25](#)
 - and multicast addresses [6-25](#)
 - and router MAC addresses [6-25](#)
 - configuration guidelines [6-25](#)
 - described [6-25](#)
- unicast storm [24-1](#)
- unicast storm control command [24-4](#)
- unicast traffic, blocking [24-7](#)

UniDirectional Link Detection protocol

- See UDLD

UNIX syslog servers

- daemon configuration [29-10](#)

- facilities supported [29-12](#)

- message logging configuration [29-11](#)

- unrecognized Type-Length-Value (TLV) support [13-4](#)

upgrading information

- See release notes

upgrading software images

- See downloading

UplinkFast

- described [19-3](#)

- disabling [19-13](#)

- enabling [19-12](#)

- support for [1-5](#)

uploading

configuration files

- preparing [B-10](#), [B-12](#), [B-15](#)

- reasons for [B-8](#)

- using FTP [B-14](#)

- using RCP [B-17](#)

- using TFTP [B-11](#)

image files

- preparing [B-21](#), [B-24](#), [B-28](#)

- reasons for [B-19](#)

- using FTP [B-27](#)

- using RCP [B-32](#)

- using TFTP [B-23](#)

User Datagram Protocol

- See UDP

- user EXEC mode [2-2](#)

- username-based authentication [8-7](#)

V

- version-dependent transparent mode [13-4](#)

- virtual router [36-1](#), [36-2](#)

- vlan.dat file [12-5](#)

- VLAN 1, disabling on a trunk port [12-22](#)

- VLAN 1 minimization [12-21](#)

VLAN ACLs

- See VLAN maps

- vlan-assignment response, VMPS [12-28](#)

VLAN configuration

- at bootup [12-8](#)

- saving [12-8](#)

- VLAN configuration mode [2-2](#), [12-7](#)

VLAN database

- and startup configuration file [12-8](#)

- and VTP [13-1](#)

- VLAN configuration saved in [12-7](#)

- VLANs saved in [12-4](#)

- vlan database command [12-7](#)

- vlan dot1q tag native command [16-5](#)

- VLAN filtering and SPAN [27-6](#)

- vlan global configuration command [12-7](#)

- VLAN ID, discovering [6-27](#)

- VLAN management domain [13-2](#)

- VLAN Management Policy Server

- See VMPS

- VLAN map entries, order of [31-31](#)

VLAN maps

- applying [31-34](#)

- common uses for [31-35](#)

- configuration example [31-35](#)

- configuration guidelines [31-31](#)

- configuring [31-30](#)

- creating [31-32](#)

- defined [31-2](#)

- denying access example [31-36](#)

- denying and permitting packets [31-32](#)

- displaying [31-41](#)

- examples [31-36](#)

- removing [31-34](#)

- support for [1-7](#)

- with router ACLs [31-41](#)

VLAN membership

- confirming [12-31](#)

- modes [12-3](#)

- VLAN Query Protocol
 - See VQP
- VLANs
 - adding [12-9](#)
 - adding to VLAN database [12-9](#)
 - aging dynamic addresses [17-9](#)
 - allowed on trunk [12-21](#)
 - and spanning-tree instances [12-3, 12-6, 12-13](#)
 - configuration guidelines, extended-range VLANs [12-13](#)
 - configuration guidelines, normal-range VLANs [12-6](#)
 - configuration options [12-7](#)
 - configuring [12-1](#)
 - configuring IDs 1006 to 4094 [12-13](#)
 - connecting through SVIs [10-8](#)
 - creating in config-vlan mode [12-9](#)
 - creating in VLAN configuration mode [12-10](#)
 - customer numbering in service-provider networks [16-3](#)
 - default configuration [12-8](#)
 - deleting [12-10](#)
 - described [10-2, 12-1](#)
 - displaying [12-15](#)
 - extended-range [12-1, 12-12](#)
 - features [1-6](#)
 - illustrated [12-2](#)
 - internal [12-13](#)
 - limiting source traffic with RSPAN [27-22](#)
 - limiting source traffic with SPAN [27-15](#)
 - modifying [12-9](#)
 - native, configuring [12-23](#)
 - normal-range [12-1, 12-4](#)
 - number supported [1-6](#)
 - parameters [12-5](#)
 - port membership modes [12-3](#)
 - static-access ports [12-11](#)
 - STP and 802.1Q trunks [17-10](#)
 - supported [12-2](#)
 - Token Ring [12-6](#)
 - traffic between [12-2](#)
- VLANs (continued)
 - VLAN-bridge STP [17-10, 39-1](#)
 - VTP modes [13-3](#)
- VLAN Trunking Protocol
 - See VTP
- VLAN trunks [12-16, 12-17](#)
- VMPS
 - administering [12-32](#)
 - configuration example [12-33](#)
 - configuration guidelines [12-29](#)
 - default configuration [12-29](#)
 - description [12-27](#)
 - dynamic port membership
 - described [12-28](#)
 - reconfirming [12-31](#)
 - troubleshooting [12-33](#)
 - entering server address [12-30](#)
 - mapping MAC addresses to VLANs [12-28](#)
 - monitoring [12-32](#)
 - reconfirmation interval, changing [12-31](#)
 - reconfirming membership [12-31](#)
 - retry count, changing [12-32](#)
- voice-over-IP [15-1](#)
- voice VLAN
 - Cisco 7960 phone, port connections [15-1](#)
 - configuration guidelines [15-3](#)
 - configuring IP phones for data traffic
 - override CoS of incoming frame [15-6](#)
 - trust CoS priority of incoming frame [15-6](#)
 - configuring ports for voice traffic in
 - 802.1p priority tagged frames [15-5](#)
 - 802.1Q frames [15-5](#)
 - connecting to an IP phone [15-4](#)
 - default configuration [15-3](#)
 - described [15-1](#)
 - displaying [15-6](#)
- VQP [1-6, 12-27](#)

VTP

- adding a client to a domain [13-14](#)
- advertisements [12-19, 13-3](#)
- and extended-range VLANs [13-1](#)
- and normal-range VLANs [13-2](#)
- client mode, configuring [13-11](#)
- configuration
 - global configuration mode [13-7](#)
 - guidelines [13-8](#)
 - privileged EXEC mode [13-7](#)
 - requirements [13-9](#)
 - saving [13-7](#)
 - VLAN configuration mode [13-7](#)
- configuration mode options [13-7](#)
- configuration requirements [13-9](#)
- configuration revision number
 - guideline [13-14](#)
 - resetting [13-15](#)
- configuring
 - client mode [13-11](#)
 - server mode [13-9](#)
 - transparent mode [13-12](#)
- consistency checks [13-4](#)
- default configuration [13-6](#)
- described [13-1](#)
- disabling [13-12](#)
- domain names [13-8](#)
- domains [13-2](#)
- Layer 2 protocol tunneling [16-8](#)
- modes
 - client [13-3, 13-11](#)
 - server [13-3, 13-9](#)
 - transitions [13-3](#)
 - transparent [13-3, 13-12](#)
- monitoring [13-16](#)
- passwords [13-8](#)

VTP (continued)

- pruning
 - disabling [13-14](#)
 - enabling [13-14](#)
 - examples [13-5](#)
 - overview [13-4](#)
 - support for [1-6](#)
- pruning-eligible list, changing [12-22](#)
- server mode, configuring [13-9](#)
- statistics [13-16](#)
- support for [1-6](#)
- Token Ring support [13-4](#)
- transparent mode, configuring [13-12](#)
- using [13-1](#)
- version, guidelines [13-8](#)
- Version 1 [13-4](#)
- Version 2
 - configuration guidelines [13-8](#)
 - disabling [13-13](#)
 - enabling [13-13](#)
 - overview [13-4](#)

 W

- weighted tail drop
 - See WTD
- wizards [1-2](#)
- WTD
 - described [32-14](#)
 - setting thresholds
 - egress queue-sets [32-71](#)
 - ingress queues [32-66](#)
 - support for [1-8](#)

 X

- Xmodem protocol [40-2](#)