



---

## A

abbreviating commands [2-4](#)

ABRs [34-24](#)

access-class command [31-19](#)

access control entries

See ACEs

access-denied response, VMPS [12-28](#)

access groups

applying IPv4 ACLs to interfaces [31-20](#)

Layer 2 [31-20](#)

Layer 3 [31-20](#)

access lists

See ACLs

access ports

and Layer 2 protocol tunneling [16-11](#)

defined [10-3](#)

accounting

with 802.1x [9-25](#)

with IEEE 802.1x [9-5](#)

with RADIUS [8-28](#)

with TACACS+ [8-11, 8-17](#)

ACEs

and QoS [32-7](#)

defined [31-2](#)

Ethernet [31-2](#)

IP [31-2](#)

ACLs

ACEs [31-2](#)

any keyword [31-12](#)

ACLs (continued)

applying

on bridged packets [31-38](#)

on multicast packets [31-39](#)

on routed packets [31-38](#)

on switched packets [31-37](#)

time ranges to [31-16](#)

to an interface [31-19](#)

to QoS [32-7](#)

classifying traffic for QoS [32-43](#)

comments in [31-18](#)

compiling [31-21](#)

defined [31-1, 31-7](#)

examples of [31-21, 32-43](#)

extended IP

configuring for QoS classification [32-44](#)

extended IPv4

creating [31-10](#)

matching criteria [31-7](#)

hardware and software handling [31-21](#)

host keyword [31-12](#)

IP

creating [31-7](#)

fragments and QoS guidelines [32-33](#)

implicit deny [31-9, 31-13, 31-15](#)

implicit masks [31-9](#)

matching criteria [31-7](#)

undefined [31-20](#)

## ACLs (continued)

- IPv4
  - applying to interfaces [31-19](#)
  - creating [31-7](#)
  - matching criteria [31-7](#)
  - named [31-14](#)
  - numbers [31-8](#)
  - terminal lines, setting on [31-18](#)
  - unsupported features [31-7](#)
- Layer 4 information in [31-37](#)
- logging messages [31-8](#)
- MAC extended [31-26, 32-45](#)
- matching [31-7, 31-20](#)
- monitoring [31-40](#)
- named, IPv4 [31-14](#)
- number per QoS class map [32-33](#)
- port [31-2](#)
- precedence of [31-2](#)
- QoS [32-7, 32-43](#)
- resequencing entries [31-14](#)
- router [31-2](#)
- router ACLs and VLAN map configuration
  - guidelines [31-36](#)
- standard IP, configuring for QoS classification [32-43](#)
- standard IPv4
  - creating [31-9](#)
  - matching criteria [31-7](#)
- support for [1-7](#)
- support in hardware [31-21](#)
- time ranges [31-16](#)
- types supported [31-2](#)
- unsupported features, IPv4 [31-7](#)
- using router ACLs with VLAN maps [31-36](#)
- VLAN maps
  - configuration guidelines [31-29](#)
  - configuring [31-29](#)
- active links [20-1](#)
- active router [36-1](#)
- address aliasing [23-2](#)

- addresses
  - displaying the MAC address table [6-26](#)
  - dynamic
    - accelerated aging [17-8](#)
    - changing the aging time [6-21](#)
    - default aging [17-8](#)
    - defined [6-19](#)
    - learning [6-20](#)
    - removing [6-21](#)
  - MAC, discovering [6-26](#)
  - multicast
    - group address range [37-3](#)
    - STP address management [17-8](#)
  - static
    - adding and removing [6-24](#)
    - defined [6-19](#)
- address resolution [6-26, 34-8](#)
- Address Resolution Protocol
  - See ARP
- adjacency tables, with CEF [34-72](#)
- administrative distances
  - defined [34-84](#)
  - OSPF [34-30](#)
  - routing protocol defaults [34-74](#)
- advanced IP services image [1-1, 35-1](#)
- advertisements
  - CDP [25-1](#)
  - RIP [34-19](#)
  - VTP [12-19, 13-3](#)
- aggregatable global unicast addresses [35-3](#)
- aggregate addresses, BGP [34-57](#)
- aggregated ports
  - See EtherChannel
- aggregate policers [32-58](#)
- aggregate policing [1-8](#)
- aging, accelerating [17-8](#)

- aging time
  - accelerated
    - for MSTP [18-23](#)
    - for STP [17-8, 17-21](#)
  - MAC address table [6-21](#)
  - maximum
    - for MSTP [18-24](#)
- aging time (continued)
  - maximum (continued)
    - for STP [17-21, 17-22](#)
- alarms, RMON [28-3](#)
- allowed-VLAN list [12-22](#)
- area border routers
  - See ABRs
- ARP
  - configuring [34-9](#)
  - defined [1-5, 6-26, 34-8](#)
  - encapsulation [34-10](#)
  - static cache configuration [34-9](#)
  - table
    - address resolution [6-26](#)
    - managing [6-26](#)
- ASBRs [34-24](#)
- AS-path filters, BGP [34-51](#)
- asymmetrical links, and IEEE 802.1Q tunneling [16-4](#)
- attributes, RADIUS
  - vendor-proprietary [8-30](#)
  - vendor-specific [8-29](#)
- audience [xxxvii](#)
- authentication
  - EIGRP [34-38](#)
  - HSRP [36-9](#)
  - local mode with AAA [8-36](#)
  - NTP associations [6-5](#)
  - RADIUS
    - key [8-21](#)
    - login [8-23](#)
- authentication (continued)
  - TACACS+
    - defined [8-11](#)
    - key [8-13](#)
    - login [8-14](#)
  - See also port-based authentication
- authentication keys, and routing protocols [34-85](#)
- authoritative time source, described [6-2](#)
- authorization
  - with RADIUS [8-27](#)
- authorization (continued)
  - with TACACS+ [8-11, 8-16](#)
- authorized ports with IEEE 802.1x [9-4](#)
- autoconfiguration [3-3](#)
- automatic QoS
  - See QoS
- Auto-MDIX
  - configuring [10-19](#)
  - described [10-19](#)
- autonegotiation
  - duplex mode [1-3](#)
  - interface configuration guidelines [10-16](#)
  - mismatches [40-11](#)
- autonomous system boundary routers
  - See ASBRs
- autonomous systems, in BGP [34-44](#)
- Auto-RP, described [37-5](#)
- autosensing, port speed [1-3](#)
- auxiliary VLAN
  - See voice VLAN
- availability, features [1-5](#)

**B**

## BackboneFast

- described 19-5
- disabling 19-14
- enabling 19-13
- support for 1-6

## backup interfaces

See Flex Links

## backup links 20-1

## banners

- configuring
  - login 6-19
  - message-of-the-day login 6-18
- default configuration 6-17
- when displayed 6-17

## BGP

- aggregate addresses 34-57
- aggregate routes, configuring 34-57
- CIDR 34-57
- clear commands 34-60
- community filtering 34-54
- configuring neighbors 34-55
- default configuration 34-42
- described 34-41
- enabling 34-44
- monitoring 34-60
- multipath support 34-48
- neighbors, types of 34-44
- path selection 34-48
- peers, configuring 34-55
- prefix filtering 34-53
- resetting sessions 34-47
- route dampening 34-59
- route maps 34-50
- route reflectors 34-58
- routing domain confederation 34-58
- routing session with multi-VRF CE 34-67
- show commands 34-60

## BGP (continued)

- supernets 34-57
- support for 1-9
- Version 4 34-41

## binding cluster group and HSRP group 36-11

## binding database

- address, DHCP server
  - See DHCP, Cisco IOS server database
- DHCP snooping
  - See DHCP snooping binding database

## bindings

- address, Cisco IOS DHCP server 21-5
- DHCP snooping database 21-5
- IP source guard 21-14

## binding table, DHCP snooping

See DHCP snooping binding database

## blocking packets 24-6

## booting

- boot loader, function of 3-2
- boot process 3-2
- manually 3-13
- specific image 3-13

## boot loader

- accessing 3-14
- described 3-2
- environment variables 3-14
- prompt 3-14
- trap-door mechanism 3-2

## bootstrap router (BSR), described 37-5

## Border Gateway Protocol

See BGP

## BPDU

- error-disabled state 19-3
- filtering 19-3
- RSTP format 18-12

- BPDU filtering
    - described [19-3](#)
    - disabling [19-12](#)
    - enabling [19-12](#)
    - support for [1-6](#)
  - BPDU guard
    - described [19-3](#)
    - disabling [19-11](#)
    - enabling [19-11](#)
    - support for [1-6](#)
  - bridged packets, ACLs on [31-38](#)
  - bridge groups
    - See fallback bridging
  - bridge protocol data unit
    - See BPDU
  - broadcast flooding [34-16](#)
  - broadcast packets
    - directed [34-13](#)
    - flooded [34-13](#)
  - broadcast storm-control command [24-4](#)
  - broadcast storms [24-1, 34-13](#)
- 
- C**
- cables, monitoring for unidirectional links [26-1](#)
  - candidate switch
    - defined [5-3](#)
    - requirements [5-3](#)
    - See also command switch, cluster standby group, and member switch
  - CA trustpoint
    - configuring [8-45](#)
    - defined [8-42](#)
  - caution, described [xxxviii](#)
  - CDP
    - and trusted boundary [32-39](#)
    - configuring [25-2](#)
    - default configuration [25-2](#)
    - described [25-1](#)
    - CDP (continued)
      - disabling for routing device [25-3 to 25-4](#)
      - enabling and disabling
        - on an interface [25-4](#)
        - on a switch [25-3](#)
      - Layer 2 protocol tunneling [16-8](#)
      - monitoring [25-5](#)
      - overview [25-1](#)
      - power negotiation extensions [10-6](#)
      - support for [1-5](#)
      - transmission timer and holdtime, setting [25-2](#)
      - updates [25-2](#)
  - CEF
    - defined [34-72](#)
    - enabling [34-73](#)
    - IPv6 [35-14](#)
  - CGMP
    - as IGMP snooping learning method [23-8](#)
    - clearing cached group entries [37-49](#)
    - enabling server support [37-32](#)
    - joining multicast group [23-3](#)
    - overview [37-8](#)
    - server support only [37-8](#)
    - switch support of [1-3](#)
  - CIDR [34-57](#)
  - CipherSuites [8-43](#)
  - Cisco 7960 IP Phone [15-1](#)
  - Cisco Discovery Protocol
    - See CDP
  - Cisco Express Forwarding
    - See CEF
  - Cisco Group Management Protocol
    - See CGMP
  - Cisco Intelligence Engine 2100 Series Configuration Registrar
    - See IE2100
  - Cisco intelligent power management [10-6](#)
  - Cisco IOS DHCP server
    - See DHCP, Cisco IOS DHCP server

- Cisco IOS File System
  - See IFS
- Cisco Network Assistant
  - See Network Assistant
- Cisco Networking Services
  - See IE2100
- CiscoWorks 2000 [1-4, 30-4](#)
- CIST regional root
  - See MSTP
- CIST root
  - See MSTP
- classless interdomain routing
  - See CIDR
- classless routing [34-6](#)
- class maps for QoS
  - configuring [32-46](#)
  - described [32-7](#)
  - displaying [32-78](#)
- class of service
  - See CoS
- clearing interfaces [10-26](#)
- CLI
  - abbreviating commands [2-4](#)
  - command modes [2-1](#)
  - configuration logging [2-5](#)
  - described [1-4](#)
  - editing features
    - enabling and disabling [2-7](#)
    - keystroke editing [2-7](#)
    - wrapped lines [2-9](#)
  - error messages [2-5](#)
  - filtering command output [2-10](#)
  - getting help [2-3](#)
  - history
    - changing the buffer size [2-6](#)
    - described [2-6](#)
    - disabling [2-7](#)
    - recalling commands [2-6](#)
- CLI (continued)
  - managing clusters [5-3](#)
  - no and default forms of commands [2-4](#)
- client mode, VTP [13-3](#)
- clock
  - See system clock
- cluster requirements [xxxix](#)
- clusters, switch
  - benefits [1-2](#)
  - described [5-1](#)
  - managing
    - through CLI [5-3](#)
    - through SNMP [5-4](#)
  - planning considerations
    - CLI [5-3](#)
    - SNMP [5-4](#)
- See also Getting Started with Cisco Network Assistant
- cluster standby group
  - and HSRP group [36-11](#)
  - requirements [5-2](#)
- Coarse Wave Division Multiplexer
  - See CWDM SFPs
- command-line interface
  - See CLI
- command modes [2-1](#)
- commands
  - abbreviating [2-4](#)
  - no and default [2-4](#)
- commands, setting privilege levels [8-8](#)
- command switch
  - configuration conflicts [40-11](#)
  - defined [5-2](#)
  - password privilege levels [5-4](#)
  - recovery
    - from command-switch failure [40-7](#)
    - from lost member connectivity [40-11](#)

- command switch (continued)
  - replacing
    - with another switch [40-10](#)
    - with cluster member [40-8](#)
  - requirements [5-2](#)
  - See also candidate switch, cluster standby group, member switch, and standby command switch
- community list, BGP [34-54](#)
- community ports [14-2](#)
- community strings
  - configuring [30-8](#)
  - for cluster switches [30-4](#)
  - overview [30-4](#)
- community VLANs [14-2, 14-3](#)
- compatibility, feature [24-11](#)
- config.text [3-12](#)
- configurable leave timer, IGMP [23-5](#)
- configuration, initial
  - defaults [1-11](#)
  - Express Setup [1-2](#)
  - See also getting started guide and hardware installation guide
- configuration conflicts, recovering from lost member connectivity [40-11](#)
- configuration examples, network [1-13](#)
- configuration files
  - clearing the startup configuration [B-19](#)
  - creating using a text editor [B-9](#)
  - default name [3-12](#)
  - deleting a stored configuration [B-19](#)
  - described [B-8](#)
  - downloading
    - automatically [3-12](#)
    - preparing [B-10, B-13, B-16](#)
    - reasons for [B-8](#)
    - using FTP [B-13](#)
    - using RCP [B-17](#)
    - using TFTP [B-10](#)
  - guidelines for creating and using [B-8](#)
  - invalid combinations when copying [B-5](#)
- configuration files (continued)
  - limiting TFTP server access [30-15](#)
  - obtaining with DHCP [3-7](#)
  - password recovery disable considerations [8-5](#)
  - specifying the filename [3-12](#)
  - system contact and location information [30-14](#)
  - types and location [B-9](#)
  - uploading
    - preparing [B-10, B-13, B-16](#)
    - reasons for [B-8](#)
    - using FTP [B-14](#)
    - using RCP [B-18](#)
    - using TFTP [B-11](#)
- configuration guidelines, multi-VRF CE [34-64](#)
- configuration logging [2-5](#)
- configuration settings, saving [3-10](#)
- configure terminal command [10-10](#)
- config-vlan mode [2-2, 12-7](#)
- conflicts, configuration [40-11](#)
- connections, secure remote [8-38](#)
- connectivity problems [40-13, 40-15, 40-16](#)
- consistency checks in VTP Version 2 [13-4](#)
- console port, connecting to [2-10](#)
- conventions
  - command [xxxviii](#)
  - for examples [xxxviii](#)
  - publication [xxxviii](#)
  - text [xxxviii](#)
- corrupted software, recovery steps with Xmodem [40-2](#)
- CoS
  - in Layer 2 frames [32-2](#)
  - override priority [15-6](#)
  - trust priority [15-6](#)
- CoS input queue threshold map for QoS [32-16](#)
- CoS output queue threshold map for QoS [32-19](#)
- CoS-to-DSCP map for QoS [32-60](#)
- counters, clearing interface [10-26](#)
- crashinfo file [40-23](#)

cryptographic software image

Kerberos [8-32](#)

SSH [8-37](#)

SSL [8-41](#)

customer edge devices [34-62](#)

CWDM SFPs [1-20](#)

## D

daylight saving time [6-13](#)

debugging

enabling all system diagnostics [40-20](#)

enabling for a specific feature [40-19](#)

redirecting error message output [40-20](#)

using commands [40-19](#)

default commands [2-4](#)

default configuration

802.1x [9-12](#)

auto-QoS [32-20](#)

banners [6-17](#)

BGP [34-42](#)

booting [3-12](#)

CDP [25-2](#)

DHCP [21-7](#)

DHCP option 82 [21-7](#)

DHCP snooping [21-7](#)

DHCP snooping binding database [21-7](#)

DNS [6-16](#)

dynamic ARP inspection [22-5](#)

EIGRP [34-35](#)

EtherChannel [33-9](#)

Ethernet interfaces [10-14](#)

fallback bridging [39-3](#)

Flex Links [20-2](#)

HSRP [36-5](#)

IEEE 802.1Q tunneling [16-4](#)

IGMP [37-26](#)

IGMP filtering [23-22](#)

IGMP snooping [23-6](#)

default configuration (continued)

IGMP throttling [23-22](#)

initial switch information [3-3](#)

IP addressing, IP routing [34-4](#)

IP multicast routing [37-8](#)

IP source guard [21-15](#)

IPv6 [35-9](#)

Layer 2 interfaces [10-14](#)

Layer 2 protocol tunneling [16-11](#)

MAC address table [6-21](#)

MSDP [38-4](#)

MSTP [18-14](#)

multi-VRF CE [34-64](#)

MVR [23-17](#)

NTP [6-4](#)

optional spanning-tree configuration [19-9](#)

OSPF [34-25](#)

password and privilege level [8-2](#)

PIM [37-8](#)

private VLANs [14-6](#)

RADIUS [8-20](#)

RIP [34-19](#)

RMON [28-3](#)

RSPAN [27-9](#)

SDM template [7-3](#)

SNMP [30-6](#)

SPAN [27-9](#)

SSL [8-44](#)

standard QoS [32-31](#)

STP [17-11](#)

system message logging [29-3](#)

system name and prompt [6-15](#)

TACACS+ [8-13](#)

UDLD [26-4](#)

VLAN, Layer 2 Ethernet interfaces [12-19](#)

VLANs [12-8](#)

VMPS [12-29](#)

voice VLAN [15-3](#)

VTP [13-6](#)



- default gateway [3-10, 34-11](#)
- default networks [34-75](#)
- default routes [34-75](#)
- default routing [34-2](#)
- deleting VLANs [12-10](#)
- denial-of-service attack [24-1](#)
- description command [10-21](#)
- designing your network, examples [1-13](#)
- destination addresses, in IPv4 ACLs [31-11](#)
- destination-IP address-based forwarding, EtherChannel [33-7](#)
- destination-MAC address forwarding, EtherChannel [33-7](#)
- detecting indirect link failures, STP [19-5](#)
- device [B-19](#)
- device discovery protocol [25-1](#)
- device manager
  - benefits [1-2](#)
  - described [1-2, 1-4](#)
  - in-band management [1-5](#)
  - requirements [xxxviii](#)
  - upgrading a switch [B-19](#)
- DHCP
  - Cisco IOS server database
    - configuring [21-12](#)
    - default configuration [21-7](#)
    - described [21-5](#)
  - enabling
    - relay agent [21-9](#)
    - server [21-9](#)
- DHCP-based autoconfiguration
  - client request message exchange [3-4](#)
  - configuring
    - client side [3-3](#)
    - DNS [3-6](#)
    - relay device [3-6](#)
    - server side [3-5](#)
    - server-side [21-9](#)
    - TFTP server [3-5](#)
  - example [3-8](#)
  - DHCP-based autoconfiguration (continued)
    - lease options
      - for IP address information [3-5](#)
      - for receiving the configuration file [3-5](#)
    - overview [3-3](#)
    - relationship to BOOTP [3-4](#)
    - relay support [1-4, 1-9](#)
    - support for [1-4](#)
  - DHCP binding database
    - See DHCP snooping binding database
  - DHCP binding table
    - See DHCP snooping binding database
  - DHCP option 82
    - circuit ID suboption [21-5](#)
    - configuration guidelines [21-8](#)
    - default configuration [21-7](#)
    - displaying [21-13](#)
    - forwarding address, specifying [21-9](#)
    - helper address [21-9](#)
    - overview [21-3](#)
    - packet format, suboption
      - circuit ID [21-5](#)
      - remote ID [21-5](#)
    - remote ID suboption [21-5](#)
  - DHCP snooping
    - accepting untrusted packets form edge switch [21-3, 21-11](#)
    - and private VLANs [21-12](#)
    - binding database
      - See DHCP snooping binding database
    - configuration guidelines [21-8](#)
    - default configuration [21-7](#)
    - displaying binding tables [21-13](#)
    - message exchange process [21-4](#)
    - option 82 data insertion [21-3](#)
    - trusted interface [21-2](#)
    - untrusted interface [21-2](#)
    - untrusted messages [21-2](#)

## DHCP snooping binding database

- adding bindings [21-12](#)
- binding file
  - format [21-6](#)
  - location [21-6](#)
- bindings [21-5](#)
- clearing agent statistics [21-13](#)
- configuration guidelines [21-8](#)
- configuring [21-12](#)
- default configuration [21-7](#)
- deleting
  - binding file [21-13](#)
  - bindings [21-13](#)
  - database agent [21-13](#)
- described [21-5](#)
- displaying [21-13](#)
  - binding entries [21-13](#)
  - status and statistics [21-13](#)
- enabling [21-12](#)
- entry [21-5](#)
- renewing database [21-13](#)
- resetting
  - delay value [21-13](#)
  - timeout value [21-13](#)

## DHCP snooping binding table

See DHCP snooping binding database

Differentiated Services architecture, QoS [32-2](#)Differentiated Services Code Point [32-2](#)Diffusing Update Algorithm (DUAL) [34-33](#)directed unicast requests [1-5](#)

## directories

- changing [B-3](#)
- creating and removing [B-4](#)
- displaying the working [B-3](#)

## Distance Vector Multicast Routing Protocol

See DVMRP

distance-vector protocols [34-3](#)distribute-list command [34-83](#)

## DNS

- and DHCP-based autoconfiguration [3-6](#)
- default configuration [6-16](#)
- displaying the configuration [6-17](#)
- in IPv6 [35-4](#)
- overview [6-15](#)
- setting up [6-16](#)
- support for [1-4](#)

documentation, related [xxxviii](#)

document conventions [xxxviii](#)

## domain names

- DNS [6-15](#)
- VTP [13-8](#)

## Domain Name System

See DNS

dot1q-tunnel switchport mode [12-18](#)

## double-tagged packets

- IEEE 802.1Q tunneling [16-2](#)
- Layer 2 protocol tunneling [16-10](#)

## downloading

## configuration files

- preparing [B-10, B-13, B-16](#)
- reasons for [B-8](#)
- using FTP [B-13](#)
- using RCP [B-17](#)
- using TFTP [B-10](#)

## image files

- deleting old image [B-23](#)
- preparing [B-21, B-25, B-29](#)
- reasons for [B-19](#)
- using CMS [1-2](#)
- using FTP [B-26](#)
- using HTTP [1-2, B-19](#)
- using RCP [B-31](#)
- using TFTP [B-22](#)
- using the device manager or Network Assistant [B-19](#)

drop threshold for Layer 2 protocol packets [16-11](#)DSCP [1-8, 32-2](#)DSCP input queue threshold map for QoS [32-16](#)

- DSCP output queue threshold map for QoS [32-19](#)
- DSCP-to-CoS map for QoS [32-63](#)
- DSCP-to-DSCP-mutation map for QoS [32-64](#)
- DSCP transparency [32-39](#)
- DTP [1-6, 12-17](#)
- DUAL finite state machine, EIGRP [34-34](#)
- dual IPv4 and IPv6 templates [7-2, 35-7](#)
- dual protocol stacks
  - configuring [35-12](#)
  - IPv4 and IPv6 [35-7](#)
  - SDM templates supporting [35-8](#)
- duplex mode, configuring [10-16](#)
- DVMRP
  - autosummarization
    - configuring a summary address [37-46](#)
    - disabling [37-48](#)
  - connecting PIM domain to DVMRP router [37-38](#)
  - enabling unicast routing [37-42](#)
  - interoperability
    - with Cisco devices [37-36](#)
    - with Cisco IOS software [37-7](#)
  - mrinfo requests, responding to [37-41](#)
  - neighbors
    - advertising the default route to [37-40](#)
    - discovery with Probe messages [37-36](#)
    - displaying information [37-41](#)
    - prevent peering with nonpruning [37-44](#)
    - rejecting nonpruning [37-42](#)
  - overview [37-7](#)
  - routes
    - adding a metric offset [37-48](#)
    - advertising all [37-48](#)
    - advertising the default route to neighbors [37-40](#)
    - caching DVMRP routes learned in report messages [37-42](#)
    - changing the threshold for syslog messages [37-45](#)
    - deleting [37-49](#)
    - displaying [37-50](#)
    - favoring one over another [37-48](#)
- DVMRP (continued)
  - routes (continued)
    - limiting the number injected into MBONE [37-45](#)
    - limiting unicast route advertisements [37-36](#)
  - routing table [37-7](#)
  - source distribution tree, building [37-7](#)
  - support for [1-9](#)
  - tunnels
    - configuring [37-38](#)
    - displaying neighbor information [37-41](#)
- dynamic access ports
  - characteristics [12-3](#)
  - configuring [12-31](#)
  - defined [10-3](#)
- dynamic addresses
  - See addresses
- dynamic ARP inspection
  - ARP cache poisoning [22-1](#)
  - ARP requests, described [22-1](#)
  - ARP spoofing attack [22-1](#)
  - clearing
    - log buffer [22-15](#)
    - statistics [22-15](#)
  - configuration guidelines [22-6](#)
  - configuring
    - ACLs for non-DHCP environments [22-8](#)
    - in DHCP environments [22-7](#)
    - log buffer [22-12](#)
    - rate limit for incoming ARP packets [22-4, 22-10](#)
  - default configuration [22-5](#)
  - denial-of-service attacks, preventing [22-10](#)
  - described [22-1](#)
  - DHCP snooping binding database [22-2](#)
  - displaying
    - ARP ACLs [22-14](#)
    - configuration and operating state [22-14](#)
    - log buffer [22-15](#)
    - statistics [22-15](#)
    - trust state and rate limit [22-14](#)

- dynamic ARP inspection (continued)
  - error-disabled state for exceeding rate limit [22-4](#)
  - function of [22-2](#)
  - interface trust states [22-3](#)
  - log buffer
    - clearing [22-15](#)
    - configuring [22-12](#)
    - displaying [22-15](#)
  - logging of dropped packets, described [22-4](#)
  - man-in-the middle attack, described [22-2](#)
  - network security issues and interface trust states [22-3](#)
  - priority of ARP ACLs and DHCP snooping entries [22-4](#)
  - rate limiting of ARP packets
    - configuring [22-10](#)
    - described [22-4](#)
    - error-disabled state [22-4](#)
  - statistics
    - clearing [22-15](#)
    - displaying [22-15](#)
  - validation checks, performing [22-11](#)
- dynamic auto trunking mode [12-18](#)
- dynamic desirable trunking mode [12-18](#)
- Dynamic Host Configuration Protocol
  - See DHCP-based autoconfiguration
- dynamic port VLAN membership
  - described [12-29](#)
  - reconfirming [12-31](#)
  - troubleshooting [12-33](#)
  - types of connections [12-31](#)
- dynamic routing [34-3](#)
- Dynamic Trunking Protocol
  - See DTP
- editing features
  - enabling and disabling [2-7](#)
  - keystrokes used [2-7](#)
  - wrapped lines [2-9](#)
- EIGRP
  - authentication [34-38](#)
  - components [34-34](#)
  - configuring [34-37](#)
  - default configuration [34-35](#)
  - definition [34-33](#)
  - interface parameters, configuring [34-37](#)
  - monitoring [34-39](#)
  - support for [1-9](#)
- enable password [8-3](#)
- enable secret password [8-3](#)
- encryption, CipherSuite [8-43](#)
- encryption for passwords [8-3](#)
- Enhanced IGRP
  - See EIGRP
- environment variables, function of [3-15](#)
- equal-cost routing [1-9, 34-73](#)
- error messages during command entry [2-5](#)
- EtherChannel
  - automatic creation of [33-4, 33-5](#)
  - channel groups
    - binding physical and logical interfaces [33-3](#)
    - numbering of [33-3](#)
  - configuration guidelines [33-9](#)
  - configuring
    - Layer 2 interfaces [33-10](#)
    - Layer 3 physical interfaces [33-14](#)
    - Layer 3 port-channel logical interfaces [33-13](#)
  - default configuration [33-9](#)
  - described [33-2](#)
  - displaying status [33-20](#)
  - forwarding methods [33-6, 33-16](#)
  - IEEE 802.3ad, described [33-5](#)

---

**E**

EBGP [34-40](#)

## EtherChannel (continued)

## interaction

with STP [33-9](#)with VLANs [33-10](#)

## LACP

described [33-5](#)displaying status [33-20](#)hot-standby ports [33-18](#)interaction with other features [33-6](#)modes [33-6](#)port priority [33-19](#)system priority [33-19](#)Layer 3 interface [34-3](#)load balancing [33-6, 33-16](#)logical interfaces, described [33-3](#)

## PAgP

aggregate-port learners [33-17](#)compatibility with Catalyst 1900 [33-17](#)described [33-4](#)displaying status [33-20](#)interaction with other features [33-5](#)learn method and priority configuration [33-17](#)modes [33-4](#)support for [1-3](#)

## port-channel interfaces

described [33-3](#)numbering of [33-3](#)port groups [10-5](#)support for [1-3](#)

## EtherChannel guard

described [19-7](#)disabling [19-14](#)enabling [19-14](#)

## Ethernet VLANs

adding [12-9](#)defaults and ranges [12-8](#)modifying [12-9](#)EUI [35-3](#)events, RMON [28-3](#)

## examples

conventions for [xxxviii](#)network configuration [1-13](#)expedite queue for QoS [32-77](#)Express Setup [1-2](#)

See also getting started guide

## extended-range VLANs

configuration guidelines [12-13](#)configuring [12-12](#)creating [12-14](#)creating with an internal VLAN ID [12-15](#)defined [12-1](#)

## extended system ID

MSTP [18-17](#)STP [17-4, 17-14](#)

## extended universal identifier

See EUI

Extensible Authentication Protocol over LAN [9-1](#)

## external BGP

See EBGp

external neighbors, BGP [34-44](#)

---

**F**

## fallback bridging

and protected ports [39-4](#)

## bridge groups

creating [39-4](#)described [39-1](#)displaying [39-10](#)function of [39-2](#)number supported [39-4](#)removing [39-4](#)

## bridge table

clearing [39-10](#)displaying [39-10](#)configuration guidelines [39-3](#)connecting interfaces with [10-9](#)default configuration [39-3](#)

- fallback bridging (continued)
  - described [39-1](#)
  - frame forwarding
    - flooding packets [39-2](#)
    - forwarding packets [39-2](#)
  - overview [39-1](#)
  - protocol, unsupported [39-3](#)
  - STP
    - disabling on an interface [39-10](#)
    - forward-delay interval [39-9](#)
    - hello BPDU interval [39-8](#)
    - interface priority [39-6](#)
    - keepalive messages [17-2](#)
    - maximum-idle interval [39-9](#)
    - path cost [39-7](#)
    - VLAN-bridge spanning-tree priority [39-6](#)
    - VLAN-bridge STP [39-2](#)
  - support for [1-9](#)
  - SVIs and routed ports [39-1](#)
  - unsupported protocols [39-3](#)
  - VLAN-bridge STP [17-10](#)
- features, incompatible [24-11](#)
- FIB [34-72](#)
- fiber-optic, detecting unidirectional links [26-1](#)
- files
  - copying [B-4](#)
  - crashinfo
    - description [40-23](#)
    - displaying the contents of [40-23](#)
    - location [40-23](#)
  - deleting [B-5](#)
  - displaying the contents of [B-7](#)
  - tar
    - creating [B-5](#)
    - displaying the contents of [B-6](#)
    - extracting [B-7](#)
    - image file format [B-20](#)
- file system
  - displaying available file systems [B-2](#)
  - displaying file information [B-3](#)
  - local file system names [B-1](#)
  - network file system names [B-4](#)
  - setting the default [B-3](#)
- filtering
  - in a VLAN [31-29](#)
  - non-IP traffic [31-26](#)
  - show and more command output [2-10](#)
- filtering show and more command output [2-10](#)
- filters, IP
  - See ACLs, IP
- flash device, number of [B-1](#)
- Flex Links
  - configuration guidelines [20-2](#)
  - configuring [20-3](#)
  - default configuration [20-2](#)
  - description [20-1](#)
  - monitoring [20-3](#)
- flooded traffic, blocking [24-7](#)
- flow-based packet classification [1-8](#)
- flowcharts
  - QoS classification [32-6](#)
  - QoS egress queueing and scheduling [32-17](#)
  - QoS ingress queueing and scheduling [32-15](#)
  - QoS policing and marking [32-10](#)
- flowcontrol
  - configuring [10-18](#)
  - described [10-18](#)
- forward-delay time
  - MSTP [18-23](#)
  - STP [17-21](#)
- Forwarding Information Base
  - See FIB
- forwarding nonroutable protocols [39-1](#)

## FTP

- accessing MIB files [A-3](#)
- configuration files
  - downloading [B-13](#)
  - overview [B-12](#)
  - preparing the server [B-13](#)
  - uploading [B-14](#)
- image files
  - deleting old image [B-28](#)
  - downloading [B-26](#)
  - preparing the server [B-25](#)
  - uploading [B-28](#)

---

## G

- get-bulk-request operation [30-3](#)
- get-next-request operation [30-3, 30-4](#)
- get-request operation [30-3, 30-4](#)
- get-response operation [30-3](#)
- global configuration mode [2-2](#)
- guest VLAN and 802.1x [9-10](#)
- guide
  - audience [xxxvii](#)
  - purpose of [xxxvii](#)
- guide mode [1-2](#)
- GUIs
  - See device manager and Network Assistant [1-4](#)

---

## H

- hardware limitations and Layer 3 interfaces [10-22](#)
- hello time
  - MSTP [18-22](#)
  - STP [17-20](#)
- help, for the command line [2-3](#)

- hierarchical policy maps [32-8](#)
  - configuration guidelines [32-33](#)
  - configuring [32-51](#)
  - described [32-11](#)
- history
  - changing the buffer size [2-6](#)
  - described [2-6](#)
  - disabling [2-7](#)
  - recalling commands [2-6](#)
- history table, level and number of syslog messages [29-9](#)
- host ports
  - configuring [14-11](#)
  - kinds of [14-2](#)
- hosts, limit on dynamic ports [12-33](#)
- Hot Standby Router Protocol
  - See HSRP
- HP OpenView [1-4](#)
- HSRP
  - authentication string [36-9](#)
  - binding to cluster group [36-11](#)
  - command-switch redundancy [1-1, 1-5](#)
  - configuring [36-4](#)
  - default configuration [36-5](#)
  - definition [36-1](#)
  - guidelines [36-5](#)
  - monitoring [36-11](#)
  - overview [36-1](#)
  - priority [36-7](#)
  - routing redundancy [1-9](#)
  - support for ICMP redirect messages [36-11](#)
  - timers [36-9](#)
  - tracking [36-7](#)
- HTTP over SSL
  - see HTTPS
- HTTPS [8-42](#)
  - configuring [8-46](#)
  - self-signed certificate [8-42](#)
- HTTP secure server [8-42](#)

## I

IBPG [34-40](#)

## ICMP

IPv6 [35-4](#)

redirect messages [34-11](#)

support for [1-9](#)

time-exceeded messages [40-17](#)

traceroute and [40-17](#)

unreachable messages [31-19](#)

unreachables and ACLs [31-21](#)

## ICMP ping

executing [40-14](#)

overview [40-13](#)

## ICMP Router Discovery Protocol

See IRDP

ICMPv6 [35-4](#)

## IDS appliances

and ingress RSPAN [27-20](#)

and ingress SPAN [27-13](#)

## IE2100

CNS embedded agents

described [4-5](#)

enabling automated configuration [4-6](#)

enabling configuration agent [4-9](#)

enabling event agent [4-8](#)

## Configuration Registrar

configID, deviceID, hostname [4-3](#)

configuration service [4-2](#)

described [4-1](#)

event service [4-3](#)

## IEEE 802.1D

See STP

IEEE 802.1p [15-1](#)

## IEEE 802.1Q

and trunk ports [10-3](#)

configuration limitations [12-19](#)

encapsulation [12-16](#)

native VLAN for untagged traffic [12-23](#)

tunneling

compatibility with other features [16-6](#)

defaults [16-4](#)

described [16-1](#)

tunnel ports with other features [16-6](#)

## IEEE 802.1s

See MSTP

## IEEE 802.1w

See RSTP

## IEEE 802.1x

See port-based authentication

## IEEE 802.3ad

See EtherChannel

## IEEE 802.3af

See PoE

IEEE 802.3z flow control [10-18](#)

ifIndex values, SNMP [30-5](#)

IFS [1-5](#)

## IGMP

configurable leave timer

described [23-5](#)

enabling [23-11](#)

configuring the switch

as a member of a group [37-26](#)

statically connected member [37-31](#)

controlling access to groups [37-27](#)

default configuration [37-26](#)

deleting cache entries [37-50](#)

displaying groups [37-50](#)

fast switching [37-31](#)

host-query interval, modifying [37-29](#)

joining multicast group [23-3](#)

join messages [23-3](#)

leave processing, enabling [23-10](#)



## IGMP (continued)

- leaving multicast group [23-4](#)
- multicast reachability [37-26](#)
- overview [37-2](#)
- queries [23-3](#)
- report suppression
  - described [23-5](#)
  - disabling [23-13](#)
- supported versions [23-2](#)
- support for [1-3](#)
- Version 1
  - changing to Version 2 [37-28](#)
  - described [37-3](#)
- Version 2
  - changing to Version 1 [37-28](#)
  - described [37-3](#)
  - maximum query response time value [37-30](#)
  - pruning groups [37-30](#)
  - query timeout value [37-30](#)

## IGMP filtering

- configuring [23-22](#)
- default configuration [23-22](#)
- described [23-21](#)
- monitoring [23-26](#)
- support for [1-4](#)

## IGMP groups

- configuring filtering [23-25](#)
- setting the maximum number [23-24](#)

## IGMP profile

- applying [23-24](#)
- configuration mode [23-22](#)
- configuring [23-23](#)

## IGMP snooping

- and address aliasing [23-2](#)
- configuring [23-6](#)
- default configuration [23-6](#)
- definition [23-1](#)
- enabling and disabling [23-6](#)
- global configuration [23-7](#)

## IGMP snooping (continued)

- Immediate Leave [23-5](#)
  - method [23-7](#)
  - monitoring [23-13](#)
  - querier
    - configuration guidelines [23-11](#)
    - configuring [23-11](#)
  - supported versions [23-2](#)
  - support for [1-3](#)
  - VLAN configuration [23-7](#)
- IGMP throttling
- configuring [23-25](#)
  - default configuration [23-22](#)
  - described [23-22](#)
  - displaying action [23-26](#)

IGP [34-24](#)

## Immediate Leave, IGMP

- configuration guidelines [23-10](#)
- described [23-5](#)
- enabling [23-10](#)

## initial configuration

- defaults [1-11](#)
- Express Setup [1-2](#)
- See also getting started guide and hardware installation guide

## Intelligence Engine 2100 Series CNS Agents

See IE2100

## interface

- number [10-10](#)
- range macros [10-12](#)
- interface command [10-10](#)
- interface configuration mode [2-3](#)

## interfaces

- Auto-MDIX, configuring [10-19](#)
  - configuration guidelines
    - duplex and speed [10-16](#)
    - duplex mode [10-16](#)
    - procedure [10-10](#)
    - speed [10-16](#)
  - configuring for IPv4 and IPv6 [35-12](#)
  - counters, clearing [10-26](#)
  - default configuration [10-14](#)
  - described [10-21](#)
  - descriptive name, adding [10-21](#)
  - displaying information about [10-25](#)
  - flow control [10-18](#)
  - management [1-4](#)
  - monitoring [10-25](#)
  - naming [10-21](#)
  - physical, identifying [10-10](#)
  - range of [10-11](#)
  - restarting [10-26](#)
  - shutting down [10-26](#)
  - speed and duplex, configuring [10-17](#)
  - status [10-25](#)
  - supported [10-10](#)
  - types of [10-1](#)
- interfaces range macro command [10-12](#)
- interface types [10-10](#)
- Interior Gateway Protocol
- See IGP
- internal BGP
- See IBGP
- internal neighbors, BGP [34-44](#)
- Internet Control Message Protocol
- See ICMP
- Internet Group Management Protocol
- See IGMP
- Internet Protocol version 6
- See IPv6

## Inter-Switch Link

See ISL

inter-VLAN routing [1-9, 34-2](#)

## Intrusion Detection System

See IDS appliances

## IP ACLs

- for QoS classification [32-7](#)
- implicit deny [31-9, 31-13](#)
- implicit masks [31-9](#)
- named [31-14](#)
- undefined [31-20](#)

## IP addresses

- 128-bit [35-2](#)
- candidate or member [5-3](#)
- classes of [34-5](#)
- command switch [5-2](#)
- default configuration [34-4](#)
- discovering [6-26](#)
- for IP routing [34-4](#)
- IPv6 [35-2](#)
- MAC address association [34-8](#)
- monitoring [34-17](#)
- See also IP information

IP base image [1-1](#)

IP broadcast address [34-15](#)

ip cef distributed command [34-72](#)

IP directed broadcasts [34-13](#)

ip igmp profile command [23-22](#)

## IP information

- assigned
  - manually [3-9](#)
  - through DHCP-based autoconfiguration [3-3](#)
- default configuration [3-3](#)

## IP multicast routing

## addresses

all-hosts [37-3](#)all-multicast-routers [37-3](#)host group address range [37-3](#)administratively-scoped boundaries, described [37-34](#)and IGMP snooping [23-1](#)

## Auto-RP

adding to an existing sparse-mode cloud [37-14](#)benefits of [37-13](#)clearing the cache [37-50](#)configuration guidelines [37-10](#)filtering incoming RP announcement messages [37-16](#)overview [37-5](#)preventing candidate RP spoofing [37-16](#)preventing join messages to false RPs [37-15](#)setting up in a new internetwork [37-14](#)using with BSR [37-21](#)

## bootstrap router

configuration guidelines [37-10](#)configuring candidate BSRs [37-19](#)configuring candidate RPs [37-20](#)defining the IP multicast boundary [37-19](#)defining the PIM domain border [37-18](#)overview [37-5](#)using with Auto-RP [37-21](#)Cisco implementation [37-2](#)

## configuring

basic multicast routing [37-10](#)IP multicast boundary [37-34](#)default configuration [37-8](#)

## enabling

multicast forwarding [37-10](#)PIM mode [37-11](#)

## group-to-RP mappings

Auto-RP [37-5](#)BSR [37-5](#)

## IP multicast routing (continued)

## MBONE

deleting sdr cache entries [37-50](#)described [37-33](#)displaying sdr cache [37-51](#)enabling sdr listener support [37-33](#)limiting DVMRP routes advertised [37-45](#)limiting sdr cache entry lifetime [37-34](#)SAP packets for conference session  
announcement [37-33](#)Session Directory (sdr) tool, described [37-33](#)

## monitoring

packet rate loss [37-51](#)peering devices [37-51](#)tracing a path [37-51](#)multicast forwarding, described [37-6](#)PIMv1 and PIMv2 interoperability [37-9](#)protocol interaction [37-2](#)reverse path check (RPF) [37-6](#)

## routing table

deleting [37-50](#)displaying [37-50](#)

## RP

assigning manually [37-12](#)configuring Auto-RP [37-13](#)configuring PIMv2 BSR [37-17](#)monitoring mapping information [37-22](#)using Auto-RP and BSR [37-21](#)statistics, displaying system and network [37-50](#)

See also CGMP

See also DVMRP

See also IGMP

See also PIM

## IP phones

and QoS [15-1](#)automatic classification and queueing [32-20](#)configuring [15-4](#)ensuring port security with QoS [32-38](#)trusted boundary for QoS [32-38](#)

- IP precedence [32-2](#)
- IP-precedence-to-DSCP map for QoS [32-61](#)
- IP protocols
  - in ACLs [31-11](#)
  - routing [1-9](#)
- IP routes, monitoring [34-86](#)
- IP routing
  - connecting interfaces with [10-9](#)
  - disabling [34-18](#)
  - enabling [34-18](#)
- IP services image [1-1](#)
- IP source guard
  - and 802.1x [21-15](#)
  - and DHCP snooping [21-14](#)
  - and EtherChannels [21-15](#)
  - and port security [21-15](#)
  - and private VLANs [21-15](#)
  - and routed ports [21-15](#)
  - and TCAM entries [21-15](#)
  - and trunk interfaces [21-15](#)
  - and VRF [21-15](#)
  - binding configuration
    - automatic [21-14](#)
    - manual [21-14](#)
  - binding table [21-14](#)
  - configuration guidelines [21-15](#)
  - default configuration [21-15](#)
  - described [21-14](#)
  - disabling [21-16](#)
  - displaying
    - bindings [21-17](#)
    - configuration [21-17](#)
  - enabling [21-16](#)
  - filtering
    - source IP address [21-14](#)
    - source IP and MAC address [21-14](#)
  - source IP address filtering [21-14](#)
  - source IP and MAC address filtering [21-14](#)
- IP source guard (continued)
  - static bindings
    - adding [21-16](#)
    - deleting [21-16](#)
- IP traceroute
  - executing [40-17](#)
  - overview [40-16](#)
- IP unicast routing
  - address resolution [34-8](#)
  - administrative distances [34-74, 34-84](#)
  - ARP [34-8](#)
  - assigning IP addresses to Layer 3 interfaces [34-5](#)
  - authentication keys [34-85](#)
  - broadcast
    - address [34-15](#)
    - flooding [34-16](#)
    - packets [34-13](#)
    - storms [34-13](#)
  - classless routing [34-6](#)
  - configuring static routes [34-74](#)
  - default
    - addressing configuration [34-4](#)
    - gateways [34-11](#)
    - networks [34-75](#)
    - routes [34-75](#)
    - routing [34-2](#)
  - directed broadcasts [34-13](#)
  - disabling [34-18](#)
  - dynamic routing [34-3](#)
  - enabling [34-18](#)
  - EtherChannel Layer 3 interface [34-3](#)
  - IGP [34-24](#)
  - inter-VLAN [34-2](#)
  - IP addressing
    - classes [34-5](#)
    - configuring [34-4](#)
  - IPv6 [35-3](#)
  - IRDP [34-12](#)
  - Layer 3 interfaces [34-3](#)

## IP unicast routing (continued)

- MAC address and IP address [34-8](#)

- passive interfaces [34-22](#)

- protocols

- distance-vector [34-3](#)

- dynamic [34-3](#)

- link-state [34-3](#)

- proxy ARP [34-8](#)

- redistribution [34-76](#)

- reverse address resolution [34-8](#)

- routed ports [34-3](#)

- static routing [34-3](#)

- steps to configure [34-4](#)

- subnet mask [34-5](#)

- subnet zero [34-6](#)

- supernet [34-6](#)

- UDP [34-15](#)

- with SVIs [34-3](#)

- See also BGP

- See also EIGRP

- See also OSPF

- See also RIP

## IPv4 ACLs

- applying to interfaces [31-19](#)

- extended, creating [31-10](#)

- named [31-14](#)

- standard, creating [31-9](#)

## IPv4 and IPv6

- configuring on an interface [35-12](#)

- differences [35-1](#)

- dual protocol stacks [35-5](#)

## IPv6

- addresses [35-2](#)

- address formats [35-2](#)

- advantages [35-2](#)

- applications [35-5](#)

- assigning address [35-10](#)

- autoconfiguration [35-4](#)

- CEFv6 [35-14](#)

## IPv6 (continued)

- configuring static routes [35-15](#)

- default configuration [35-9](#)

- defined [35-1](#)

- enabling [35-10](#)

- feature limitations [35-7](#)

- features not supported [35-6](#)

- ICMP [35-4](#)

- ICMP rate limiting [35-14](#)

- monitoring [35-21](#)

- OSPF [35-19](#)

- path MTU discovery [35-4](#)

- reasons for [35-1](#)

- RIP [35-17](#)

- SDM templates [7-2, 35-7](#)

- supported features [35-3](#)

- switch limitations [35-6](#)

## IRDP

- configuring [34-12](#)

- definition [34-12](#)

- support for [1-9](#)

## ISL

- and IPv6 [35-3](#)

- and trunk ports [10-3](#)

- encapsulation [1-6, 12-16](#)

- trunking with IEEE 802.1 tunneling [16-5](#)

- isolated port [14-2](#)

- isolated VLANs [14-2, 14-3](#)

---

**J**

- join messages, IGMP [23-3](#)

**K****KDC**

described [8-32](#)

See also Kerberos

keepalive messages [17-2](#)

**Kerberos**

authenticating to

boundary switch [8-35](#)

KDC [8-35](#)

network services [8-35](#)

configuration examples [8-32](#)

configuring [8-36](#)

credentials [8-32](#)

cryptographic software image [8-32](#)

described [8-32](#)

KDC [8-32](#)

operation [8-34](#)

realm [8-33](#)

server [8-33](#)

support for [1-8](#)

switch as trusted third party [8-32](#)

terms [8-33](#)

TGT [8-34](#)

tickets [8-32](#)

**key distribution center**

See KDC

**L**

l2protocol-tunnel command [16-13](#)

**LACP**

Layer 2 protocol tunneling [16-9](#)

See EtherChannel

Layer 2 frames, classification with CoS [32-2](#)

Layer 2 interfaces, default configuration [10-14](#)

**Layer 2 protocol tunneling**

configuring [16-10](#)

configuring for EtherChannels [16-14](#)

default configuration [16-11](#)

defined [16-8](#)

guidelines [16-11](#)

**Layer 2 traceroute**

and ARP [40-16](#)

and CDP [40-15](#)

broadcast traffic [40-15](#)

described [40-15](#)

IP addresses and subnets [40-16](#)

MAC addresses and VLANs [40-15](#)

multicast traffic [40-15](#)

multiple devices on a port [40-16](#)

unicast traffic [40-15](#)

usage guidelines [40-15](#)

**Layer 3 features** [1-9](#)**Layer 3 interfaces**

assigning IP addresses to [34-5](#)

assigning IPv4 and IPv6 addresses to [35-12](#)

assigning IPv6 addresses to [35-10](#)

changing from Layer 2 mode [34-5](#)

types of [34-3](#)

**Layer 3 packets, classification methods** [32-2](#)**LDAP** [4-2](#)**LEDs, switch**

See hardware installation guide

**lightweight directory access protocol**

See LDAP

**line configuration mode** [2-3](#)**Link Aggregation Control Protocol**

See EtherChannel

**Link Failure**

detecting unidirectional [18-8](#)

link local unicast addresses [35-3](#)

**link redundancy**

See Flex Links

links, unidirectional [26-1](#)

- link state advertisements (LSAs) [34-28](#)
  - link-state protocols [34-3](#)
  - load balancing [36-3](#)
  - local SPAN [27-2](#)
  - logging messages, ACL [31-8](#)
  - login authentication
    - with RADIUS [8-23](#)
    - with TACACS+ [8-14](#)
  - login banners [6-17](#)
  - log messages
    - See system message logging
  - Long-Reach Ethernet (LRE) technology [1-15](#)
  - loop guard
    - described [19-9](#)
    - enabling [19-15](#)
    - support for [1-6](#)
- 
- ## M
- MAC addresses
    - aging time [6-21](#)
    - and VLAN association [6-20](#)
    - building the address table [6-20](#)
    - default configuration [6-21](#)
    - discovering [6-26](#)
    - displaying [6-26](#)
    - displaying in the IP source binding table [21-17](#)
    - dynamic
      - learning [6-20](#)
      - removing [6-21](#)
    - in ACLs [31-26](#)
    - IP address association [34-8](#)
    - static
      - adding [6-24](#)
      - allowing [6-26](#)
      - characteristics of [6-24](#)
      - dropping [6-25](#)
      - removing [6-24](#)
  - MAC address notification, support for [1-10](#)
  - MAC address-to-VLAN mapping [12-28](#)
  - MAC extended access lists
    - applying to Layer 2 interfaces [31-28](#)
    - configuring for QoS [32-45](#)
    - creating [31-26](#)
    - defined [31-26](#)
    - for QoS classification [32-5](#)
  - macros
    - See Smartports macros
  - magic packet [9-10](#)
  - manageability features [1-4](#)
  - management access
    - in-band
      - browser session [1-5](#)
      - CLI session [1-5](#)
      - device manager [1-5](#)
      - SNMP [1-5](#)
    - out-of-band console port connection [1-5](#)
  - management options
    - CLI [2-1](#)
    - clustering [1-3](#)
    - CNS [4-1](#)
    - Network Assistant [1-2](#)
    - overview [1-4](#)
  - mapping tables for QoS
    - configuring
      - CoS-to-DSCP [32-60](#)
      - DSCP [32-60](#)
      - DSCP-to-CoS [32-63](#)
      - DSCP-to-DSCP-mutation [32-64](#)
      - IP-precedence-to-DSCP [32-61](#)
      - policed-DSCP [32-62](#)
    - described [32-12](#)
  - marking
    - action in policy map [32-48](#)
    - action with aggregate policers [32-58](#)
    - described [32-4, 32-8](#)
  - matching, IPv4 ACLs [31-7](#)

- maximum aging time
  - MSTP [18-24](#)
  - STP [17-21](#)
- maximum hop count, MSTP [18-24](#)
- maximum-paths command [34-48, 34-73](#)
- membership mode, VLAN port [12-3](#)
- member switch
  - defined [5-2](#)
  - managing [5-3](#)
  - recovering from lost connectivity [40-11](#)
  - requirements [5-3](#)
  - See also candidate switch, cluster standby group, and standby command switch
- messages
  - to users through banners [6-17](#)
- messages, to users through banners [6-17](#)
- metrics, in BGP [34-49](#)
- metric translations, between routing protocols [34-79](#)
- metro tags [16-2](#)
- MHSRP [36-3](#)
- MIBs
  - accessing files with FTP [A-3](#)
  - location of files [A-3](#)
  - overview [30-1](#)
  - SNMP interaction with [30-4](#)
  - supported [A-1](#)
- mirroring traffic for analysis [27-1](#)
- mismatches, autonegotiation [40-11](#)
- module number [10-10](#)
- monitoring
  - access groups [31-40](#)
  - BGP [34-60](#)
  - cables for unidirectional links [26-1](#)
  - CDP [25-5](#)
  - CEF [34-73](#)
  - EIGRP [34-39](#)
  - fallback bridging [39-10](#)
  - features [1-10](#)
  - Flex Links [20-3](#)
  - monitoring (continued)
    - HSRP [36-11](#)
    - IEEE 802.1Q tunneling [16-18](#)
    - IGMP
      - filters [23-26](#)
      - snooping [23-13](#)
    - interfaces [10-25](#)
    - IP
      - address tables [34-17](#)
      - multicast routing [37-49](#)
      - routes [34-86](#)
    - IPv4 ACL configuration [31-40](#)
    - IPv6 [35-21](#)
    - Layer 2 protocol tunneling [16-18](#)
    - MSDP peers [38-19](#)
    - multicast router interfaces [23-14](#)
    - multi-VRF CE [34-71](#)
    - MVR [23-21](#)
    - network traffic for analysis with probe [27-2](#)
    - OSPF [34-33](#)
    - port
      - blocking [24-17](#)
      - protection [24-17](#)
    - private VLANs [14-14](#)
    - RP mapping information [37-22](#)
    - SFP status [10-26, 40-13](#)
    - source-active messages [38-19](#)
    - speed and duplex mode [10-17](#)
    - traffic flowing among switches [28-1](#)
    - traffic suppression [24-16](#)
    - tunneling [16-18](#)
    - VLAN
      - filters [31-40](#)
      - maps [31-40](#)
    - VLANs [12-16](#)
    - VMPS [12-32](#)
    - VTP [13-16](#)



## MSDP

- benefits of [38-3](#)
- clearing MSDP connections and statistics [38-19](#)
- controlling source information
  - forwarded by switch [38-12](#)
  - originated by switch [38-9](#)
  - received by switch [38-14](#)
- default configuration [38-4](#)
- dense-mode regions
  - sending SA messages to [38-17](#)
  - specifying the originating address [38-18](#)
- filtering
  - incoming SA messages [38-14](#)
  - SA messages to a peer [38-12](#)
  - SA requests from a peer [38-11](#)
- join latency, defined [38-6](#)
- meshed groups
  - configuring [38-16](#)
  - defined [38-16](#)
- originating address, changing [38-18](#)
- overview [38-1](#)
- peer-RPF flooding [38-2](#)
- peers
  - configuring a default [38-4](#)
  - monitoring [38-19](#)
  - peering relationship, overview [38-1](#)
  - requesting source information from [38-8](#)
  - shutting down [38-16](#)
- source-active messages
  - caching [38-6](#)
  - clearing cache entries [38-19](#)
  - defined [38-2](#)
  - filtering from a peer [38-11](#)
  - filtering incoming [38-14](#)
  - filtering to a peer [38-12](#)
  - limiting data with TTL [38-14](#)
  - monitoring [38-19](#)
  - restricting advertised sources [38-9](#)
- support for [1-9](#)

## MSTP

- boundary ports
  - configuration guidelines [18-15](#)
  - described [18-6](#)
- BPDU filtering
  - described [19-3](#)
  - enabling [19-12](#)
- BPDU guard
  - described [19-3](#)
  - enabling [19-11](#)
- CIST, described [18-3](#)
- CIST regional root [18-3](#)
- CIST root [18-5](#)
- configuration guidelines [18-15, 19-10](#)
- configuring
  - forward-delay time [18-23](#)
  - hello time [18-22](#)
  - link type for rapid convergence [18-25](#)
  - maximum aging time [18-24](#)
  - maximum hop count [18-24](#)
  - MST region [18-16](#)
  - neighbor type [18-25](#)
  - path cost [18-21](#)
  - port priority [18-20](#)
  - root switch [18-17](#)
  - secondary root switch [18-18](#)
  - switch priority [18-22](#)
- CST
  - defined [18-3](#)
  - operations between regions [18-4](#)
- default configuration [18-14](#)
- default optional feature configuration [19-9](#)
- displaying status [18-26](#)
- enabling the mode [18-16](#)
- EtherChannel guard
  - described [19-7](#)
  - enabling [19-14](#)

## MSTP (continued)

## extended system ID

effects on root switch [18-17](#)effects on secondary root switch [18-18](#)unexpected behavior [18-17](#)

## IEEE 802.1s

implementation [18-6](#)port role naming change [18-7](#)terminology [18-5](#)instances supported [17-9](#)interface state, blocking to forwarding [19-2](#)interoperability and compatibility among modes [17-10](#)

interoperability with IEEE 802.1D

described [18-8](#)restarting migration process [18-26](#)

## IST

defined [18-3](#)master [18-3](#)operations within a region [18-3](#)

## loop guard

described [19-9](#)enabling [19-15](#)mapping VLANs to MST instance [18-16](#)

## MST region

CIST [18-3](#)configuring [18-16](#)described [18-2](#)hop-count mechanism [18-5](#)IST [18-3](#)supported spanning-tree instances [18-2](#)optional features supported [1-6](#)overview [18-2](#)

## Port Fast

described [19-2](#)enabling [19-10](#)preventing root switch selection [19-8](#)

## root guard

described [19-8](#)enabling [19-14](#)

## MSTP (continued)

## root switch

configuring [18-17](#)effects of extended system ID [18-17](#)unexpected behavior [18-17](#)shutdown Port Fast-enabled port [19-3](#)status, displaying [18-26](#)

## multicast groups

Immediate Leave [23-5](#)joining [23-3](#)leaving [23-4](#)static joins [23-9](#)

## multicast packets

ACLs on [31-39](#)blocking [24-7](#)multicast router interfaces, monitoring [23-14](#)multicast router ports, adding [23-8](#)

## Multicast Source Discovery Protocol

See MSDP

multicast storm [24-1](#)multicast storm-control command [24-4](#)multicast television application [23-15](#)multicast VLAN [23-14](#)

## Multicast VLAN Registration

See MVR

## Multiple HSRP

See MHSRP

multiple VPN routing/forwarding in customer edge devices

See multi-VRF CE

## multi-VRF CE

configuration example [34-67](#)configuration guidelines [34-64](#)configuring [34-64](#)default configuration [34-64](#)defined [34-61](#)displaying [34-71](#)monitoring [34-71](#)network components [34-64](#)

multi-VRF CE (continued)  
 packet-forwarding process [34-63](#)  
 support for [1-9](#)

## MVR

and address aliasing [23-18](#)  
 and IGMPv3 [23-18](#)  
 configuration guidelines [23-17](#)  
 configuring interfaces [23-19](#)  
 default configuration [23-17](#)  
 described [23-14](#)  
 example application [23-15](#)  
 modes [23-18](#)  
 monitoring [23-21](#)  
 multicast television application [23-15](#)  
 setting global parameters [23-18](#)  
 support for [1-4](#)

## N

named IPv4 ACLs [31-14](#)

### NameSpace Mapper

See NSM

### native VLAN

and IEEE 802.1Q tunneling [16-4](#)  
 configuring [12-23](#)  
 default [12-23](#)

neighbor discovery/recovery, EIGRP [34-34](#)

neighbors, BGP [34-55](#)

### Network Assistant

benefits [1-2](#)  
 described [1-4](#)  
 downloading image files [1-2](#)  
 guide mode [1-2](#)  
 management options [1-2](#)  
 requirements [xxxviii](#)  
 upgrading a switch [B-19](#)  
 wizards [1-2](#)

### network configuration examples

increasing network performance [1-14](#)  
 large network [1-19](#)  
 long-distance, high-bandwidth transport [1-20](#)  
 providing network services [1-14](#)  
 server aggregation and Linux server cluster [1-16](#)  
 small to medium-sized network [1-17](#)

### network design

performance [1-14](#)  
 services [1-14](#)

### network management

CDP [25-1](#)  
 RMON [28-1](#)  
 SNMP [30-1](#)

### Network Time Protocol

See NTP

no commands [2-4](#)

### nonhierarchical policy maps

configuration guidelines [32-33](#)  
 configuring [32-48](#)  
 described [32-9](#)

non-IP traffic filtering [31-26](#)

nontrunking mode [12-18](#)

normal-range VLANs [12-4](#)

configuration guidelines [12-6](#)  
 configuration modes [12-7](#)  
 configuring [12-4](#)  
 defined [12-1](#)

no switchport command [10-4](#)

note, described [xxxviii](#)

not-so-stubby areas

See NSSA

NSM [4-3](#)

NSSA, OSPF [34-28](#)

## NTP

- associations
  - authenticating [6-5](#)
  - defined [6-2](#)
  - enabling broadcast messages [6-7](#)
  - peer [6-6](#)
  - server [6-6](#)
- default configuration [6-4](#)
- displaying the configuration [6-11](#)
- overview [6-2](#)
- restricting access
  - creating an access group [6-9](#)
  - disabling NTP services per interface [6-10](#)
- source IP address, configuring [6-10](#)
- stratum [6-2](#)
- support for [1-5](#)
- synchronizing devices [6-6](#)
- time
  - services [6-2](#)
  - synchronizing [6-2](#)

## O

## Open Shortest Path First

See OSPF

- optimizing system resources [7-1](#)
- options, management [1-4](#)
- OSPF
  - area parameters, configuring [34-28](#)
  - configuring [34-26](#)
  - default configuration
    - metrics [34-30](#)
    - route [34-30](#)
    - settings [34-25](#)
  - described [34-24](#)
  - for IPv6 [35-19](#)
  - interface parameters, configuring [34-27](#)
  - LSA group pacing [34-32](#)
  - monitoring [34-33](#)

## OSPF (continued)

- router IDs [34-32](#)
- route summarization [34-30](#)
- support for [1-9](#)
- virtual links [34-30](#)
- out-of-profile markdown [1-8](#)

## P

- packet modification, with QoS [32-19](#)
- PAgP
  - Layer 2 protocol tunneling [16-9](#)
  - See EtherChannel
- parallel paths, in routing tables [34-73](#)
- passive interfaces
  - configuring [34-82](#)
  - OSPF [34-30](#)
- passwords
  - default configuration [8-2](#)
  - disabling recovery of [8-5](#)
  - encrypting [8-3](#)
  - for security [1-7](#)
  - overview [8-1](#)
  - recovery of [40-3](#)
  - setting
    - enable [8-3](#)
    - enable secret [8-3](#)
    - Telnet [8-6](#)
    - with usernames [8-6](#)
  - VTP domain [13-8](#)
- path cost
  - MSTP [18-21](#)
  - STP [17-17](#)
- path MTU discovery [35-4](#)
- PBR
  - defined [34-79](#)
  - enabling [34-81](#)
  - fast-switched policy-based routing [34-82](#)
  - local policy-based routing [34-82](#)

- peers, BGP [34-55](#)
- performance, network design [1-14](#)
- performance features [1-3](#)
- persistent self-signed certificate [8-42](#)
- per-VLAN spanning-tree plus
  - See PVST+
- PE to CE routing, configuring [34-67](#)
- physical ports [10-2](#)
- PIM
  - default configuration [37-8](#)
  - dense mode
    - overview [37-4](#)
    - rendezvous point (RP), described [37-4](#)
    - RPF lookups [37-7](#)
  - displaying neighbors [37-50](#)
  - enabling a mode [37-11](#)
  - overview [37-3](#)
  - router-query message interval, modifying [37-25](#)
  - shared tree and source tree, overview [37-23](#)
  - shortest path tree, delaying the use of [37-24](#)
  - sparse mode
    - join messages and shared tree [37-4](#)
    - overview [37-4](#)
    - prune messages [37-5](#)
    - RPF lookups [37-7](#)
  - support for [1-9](#)
  - versions
    - interoperability [37-9](#)
    - troubleshooting interoperability problems [37-22](#)
    - v2 improvements [37-4](#)
- PIM-DVMRP, as snooping method [23-7](#)
- ping
  - character output description [40-14](#)
  - executing [40-14](#)
  - overview [40-13](#)
- PoE
  - auto mode [10-8](#)
  - CDP with power consumption, described [10-6](#)
  - CDP with power negotiation, described [10-6](#)
  - Cisco intelligent power management [10-6](#)
  - configuring [10-20](#)
  - devices supported [10-6](#)
  - high-power devices operating in low-power mode [10-6](#)
  - IEEE power classification levels [10-7](#)
  - powered-device detection and initial power allocation [10-7](#)
  - power management modes [10-8](#)
  - power negotiation extensions to CDP [10-6](#)
  - standards supported [10-6](#)
  - static mode [10-8](#)
  - supported watts per port [10-6](#)
  - troubleshooting [40-12](#)
- policed-DSCP map for QoS [32-62](#)
- policers
  - configuring
    - for each matched traffic class [32-48](#)
    - for more than one traffic class [32-58](#)
  - described [32-4](#)
  - displaying [32-78](#)
  - number of [32-34](#)
  - types of [32-9](#)
- policing
  - described [32-4](#)
  - hierarchical
    - See hierarchical policy maps
    - token-bucket algorithm [32-9](#)
- policy-based routing
  - See PBR

- policy maps for QoS
  - characteristics of [32-48](#)
  - described [32-7](#)
  - displaying [32-79](#)
  - hierarchical [32-8](#)
  - hierarchical on SVIs
    - configuration guidelines [32-33](#)
    - configuring [32-51](#)
    - described [32-11](#)
  - nonhierarchical on physical ports
    - configuration guidelines [32-33](#)
    - configuring [32-48](#)
    - described [32-9](#)
- port ACLs
  - defined [31-2](#)
  - types of [31-3](#)
- Port Aggregation Protocol
  - See EtherChannel
- port-based authentication
  - accounting [9-5](#)
  - authentication server
    - defined [9-2](#)
    - RADIUS server [9-2](#)
  - client, defined [9-2](#)
  - configuration guidelines [9-14](#)
  - configuring
    - 802.1x authentication [9-15](#)
    - guest VLAN [9-23](#)
    - host mode [9-22](#)
    - manual re-authentication of a client [9-19](#)
    - periodic re-authentication [9-18](#)
    - quiet period [9-19](#)
    - RADIUS server [9-17](#)
    - RADIUS server parameters on the switch [9-16](#)
    - switch-to-client frame-retransmission number [9-21](#)
    - switch-to-client retransmission time [9-20](#)
  - default configuration [9-12](#)
  - described [9-1](#)
  - device roles [9-2](#)
  - port-based authentication (continued)
    - displaying statistics [9-26](#)
    - EAPOL-start frame [9-3](#)
    - EAP-request/identity frame [9-3](#)
    - EAP-response/identity frame [9-3](#)
    - encapsulation [9-3](#)
    - guest VLAN
      - configuration guidelines [9-10](#)
      - described [9-10](#)
    - host mode [9-6](#)
    - initiation and message exchange [9-3](#)
    - magic packet [9-10](#)
    - method lists [9-15](#)
    - multiple-hosts mode, described [9-7](#)
  - per-user ACLs
    - AAA authorization [9-15](#)
    - configuration tasks [9-12](#)
    - described [9-11](#)
    - RADIUS server attributes [9-11](#)
- ports
  - authorization state and dot1x port-control command [9-4](#)
  - authorized and unauthorized [9-4](#)
  - voice VLAN [9-8](#)
- port security
  - and voice VLAN [9-8](#)
  - described [9-7](#)
  - interactions [9-7](#)
  - multiple-hosts mode [9-7](#)
- resetting to default values [9-24](#)
- statistics, displaying [9-26](#)
- switch
  - as proxy [9-2](#)
  - RADIUS client [9-2](#)
- upgrading from a previous release [32-26](#)

- port-based authentication (continued)
  - VLAN assignment
    - AAA authorization [9-15](#)
    - characteristics [9-9](#)
    - configuration tasks [9-9](#)
    - described [9-8](#)
  - voice VLAN
    - described [9-8](#)
    - PVID [9-8](#)
    - VVID [9-8](#)
  - wake-on-LAN, described [9-10](#)
- port blocking [1-3, 24-6](#)
- port-channel
  - See EtherChannel
- Port Fast
  - described [19-2](#)
  - enabling [19-10](#)
  - mode, spanning tree [12-29](#)
  - support for [1-6](#)
- port membership modes, VLAN [12-3](#)
- port priority
  - MSTP [18-20](#)
  - STP [17-16](#)
- ports
  - access [10-3](#)
  - blocking [24-6](#)
  - dynamic access [12-3](#)
  - IEEE 802.1Q tunnel [12-4](#)
  - protected [24-5](#)
  - routed [10-4](#)
  - secure [24-7](#)
  - static-access [12-3, 12-11](#)
  - switch [10-2](#)
  - trunks [12-3, 12-16](#)
  - VLAN assignments [12-11](#)
- port security
  - aging [24-15](#)
  - and QoS trusted boundary [32-38](#)
  - configuring [24-12](#)
  - default configuration [24-10](#)
  - described [24-7](#)
  - displaying [24-17](#)
  - on trunk ports [24-13](#)
  - sticky learning [24-8](#)
  - violations [24-9](#)
  - with other features [24-10](#)
- port-shutdown response, VMPS [12-28](#)
- Power over Ethernet
  - See PoE
- preferential treatment of traffic
  - See QoS
- prefix lists, BGP [34-53](#)
- preventing unauthorized access [8-1](#)
- primary links [20-1](#)
- primary VLANs [14-1, 14-3](#)
- priority
  - HSRP [36-7](#)
  - overriding CoS [15-6](#)
  - trusting CoS [15-6](#)
- private VLAN edge ports
  - See protected ports
- private VLANs
  - across multiple switches [14-4](#)
  - and SDM template [14-4](#)
  - and SVIs [14-5](#)
  - benefits of [14-1](#)
  - community ports [14-2](#)
  - community VLANs [14-2, 14-3](#)
  - configuration guidelines [14-6, 14-8](#)
  - configuration tasks [14-6](#)
  - configuring [14-9](#)
  - default configuration [14-6](#)
  - end station access to [14-3](#)
  - IP addressing [14-3](#)

- private VLANs (continued)
    - isolated port [14-2](#)
    - isolated VLANs [14-2, 14-3](#)
    - mapping [14-13](#)
    - monitoring [14-14](#)
    - ports
      - community [14-2](#)
      - configuration guidelines [14-8](#)
      - configuring host ports [14-11](#)
      - configuring promiscuous ports [14-12](#)
      - described [12-4](#)
      - isolated [14-2](#)
      - promiscuous [14-2](#)
    - primary VLANs [14-1, 14-3](#)
    - promiscuous ports [14-2](#)
    - secondary VLANs [14-2](#)
    - subdomains [14-1](#)
    - traffic in [14-5](#)
  - privileged EXEC mode [2-2](#)
  - privilege levels
    - changing the default for lines [8-9](#)
    - command switch [5-4](#)
    - exiting [8-10](#)
    - logging into [8-10](#)
    - mapping on member switches [5-4](#)
    - overview [8-2, 8-8](#)
    - setting a command with [8-8](#)
  - promiscuous ports
    - configuring [14-12](#)
    - defined [14-2](#)
  - protected ports [1-7, 24-5](#)
  - protocol-dependent modules, EIGRP [34-34](#)
  - Protocol-Independent Multicast Protocol
    - See PIM
  - provider edge devices [34-62](#)
  - proxy ARP
    - configuring [34-10](#)
    - definition [34-8](#)
    - with IP routing disabled [34-11](#)
  - pruning, VTP
    - disabling
      - in VTP domain [13-14](#)
      - on a port [12-23](#)
    - enabling
      - in VTP domain [13-14](#)
      - on a port [12-23](#)
    - examples [13-5](#)
    - overview [13-4](#)
  - pruning-eligible list
    - changing [12-23](#)
    - for VTP pruning [13-4](#)
    - VLANs [13-14](#)
  - PVST+
    - described [17-9](#)
    - IEEE 802.1Q trunking interoperability [17-10](#)
    - instances supported [17-9](#)
- 
- ## Q
- QoS
    - and MQC commands [32-1](#)
    - auto-QoS
      - categorizing traffic [32-20](#)
      - configuration and defaults display [32-30](#)
      - configuration guidelines [32-25](#)
      - described [32-20](#)
      - disabling [32-27](#)
      - displaying generated commands [32-27](#)
      - displaying the initial configuration [32-30](#)
      - effects on running configuration [32-25](#)
      - egress queue defaults [32-21](#)
      - enabling for VoIP [32-27](#)
      - example configuration [32-28](#)
      - ingress queue defaults [32-21](#)
      - list of generated commands [32-22](#)
    - basic model [32-4](#)



## QoS (continued)

## classification

class maps, described [32-7](#)defined [32-4](#)DSCP transparency, described [32-39](#)flowchart [32-6](#)forwarding treatment [32-3](#)in frames and packets [32-3](#)IP ACLs, described [32-5, 32-7](#)MAC ACLs, described [32-5, 32-7](#)options for IP traffic [32-5](#)options for non-IP traffic [32-5](#)policy maps, described [32-7](#)trust DSCP, described [32-5](#)trusted CoS, described [32-5](#)trust IP precedence, described [32-5](#)

## class maps

configuring [32-46](#)displaying [32-78](#)

## configuration guidelines

auto-QoS [32-25](#)standard QoS [32-33](#)

## configuring

aggregate policers [32-58](#)auto-QoS [32-20](#)default port CoS value [32-37](#)DSCP maps [32-60](#)DSCP transparency [32-39](#)DSCP trust states bordering another domain [32-40](#)egress queue characteristics [32-71](#)ingress queue characteristics [32-66](#)IP extended ACLs [32-44](#)IP standard ACLs [32-43](#)MAC ACLs [32-45](#)policy maps, hierarchical [32-51](#)policy maps on physical ports [32-48](#)port trust states within the domain [32-36](#)trusted boundary [32-38](#)default auto configuration [32-20](#)

## QoS (continued)

default standard configuration [32-31](#)displaying statistics [32-78](#)DSCP transparency [32-39](#)

## egress queues

allocating buffer space [32-71](#)buffer allocation scheme, described [32-18](#)configuring shaped weights for SRR [32-75](#)configuring shared weights for SRR [32-76](#)described [32-4](#)displaying the threshold map [32-74](#)flowchart [32-17](#)mapping DSCP or CoS values [32-73](#)scheduling, described [32-4](#)setting WTD thresholds [32-71](#)WTD, described [32-19](#)enabling globally [32-35](#)

## flowcharts

classification [32-6](#)egress queueing and scheduling [32-17](#)ingress queueing and scheduling [32-15](#)policing and marking [32-10](#)implicit deny [32-7](#)

## ingress queues

allocating bandwidth [32-69](#)allocating buffer space [32-68](#)buffer and bandwidth allocation, described [32-16](#)configuring shared weights for SRR [32-69](#)configuring the priority queue [32-70](#)described [32-4](#)displaying the threshold map [32-67](#)flowchart [32-15](#)mapping DSCP or CoS values [32-67](#)priority queue, described [32-16](#)scheduling, described [32-4](#)setting WTD thresholds [32-67](#)WTD, described [32-16](#)

## QoS (continued)

## IP phones

- automatic classification and queueing [32-20](#)
- detection and trusted settings [32-20, 32-38](#)

limiting bandwidth on egress interface [32-77](#)

## mapping tables

- CoS-to-DSCP [32-60](#)
- displaying [32-78](#)
- DSCP-to-CoS [32-63](#)
- DSCP-to-DSCP-mutation [32-64](#)
- IP-precedence-to-DSCP [32-61](#)
- policed-DSCP [32-62](#)
- types of [32-12](#)

marked-down actions [32-50, 32-55](#)

marking, described [32-4, 32-8](#)

overview [32-2](#)

packet modification [32-19](#)

## policers

- configuring [32-50, 32-55, 32-58](#)
- described [32-8](#)
- displaying [32-78](#)
- number of [32-34](#)
- types of [32-9](#)

policies, attaching to an interface [32-9](#)

## policing

- described [32-4, 32-8](#)
- token bucket algorithm [32-9](#)

## policy maps

- characteristics of [32-48](#)
- displaying [32-79](#)
- hierarchical [32-8](#)
- hierarchical on SVIs [32-51](#)
- nonhierarchical on physical ports [32-48](#)

QoS label, defined [32-4](#)

## QoS (continued)

## queues

- configuring egress characteristics [32-71](#)
- configuring ingress characteristics [32-66](#)
- high priority (expedite) [32-19, 32-77](#)
- location of [32-13](#)
- SRR, described [32-14](#)
- WTD, described [32-13](#)

rewrites [32-19](#)

support for [1-8](#)

## trust states

- bordering another domain [32-40](#)
- described [32-5](#)
- trusted device [32-38](#)
- within the domain [32-36](#)

## quality of service

See QoS

queries, IGMP [23-3](#)

---

**R**

## RADIUS

## attributes

- vendor-proprietary [8-30](#)
- vendor-specific [8-29](#)

## configuring

- accounting [8-28](#)
- authentication [8-23](#)
- authorization [8-27](#)
- communication, global [8-21, 8-29](#)
- communication, per-server [8-20, 8-21](#)
- multiple UDP ports [8-20](#)

default configuration [8-20](#)

defining AAA server groups [8-25](#)

displaying the configuration [8-31](#)

identifying the server [8-20](#)

limiting the services to the user [8-27](#)

method list, defined [8-20](#)

operation of [8-19](#)

- RADIUS (continued)
  - overview [8-18](#)
  - suggested network environments [8-18](#)
  - support for [1-7](#)
  - tracking services accessed by user [8-28](#)
- range
  - macro [10-12](#)
  - of interfaces [10-11](#)
- rapid convergence [18-10](#)
- rapid per-VLAN spanning-tree plus
  - See rapid PVST+
- rapid PVST+
  - described [17-9](#)
  - IEEE 802.1Q trunking interoperability [17-10](#)
  - instances supported [17-9](#)
- Rapid Spanning Tree Protocol
  - See RSTP
- RARP [34-8](#)
- rcommand command [5-3](#)
- RCP
  - configuration files
    - downloading [B-17](#)
    - overview [B-15](#)
    - preparing the server [B-16](#)
    - uploading [B-18](#)
  - image files
    - deleting old image [B-33](#)
    - downloading [B-31](#)
    - preparing the server [B-29](#)
    - uploading [B-33](#)
- reconfirmation interval, VMPS, changing [12-31](#)
- reconfirming dynamic VLAN membership [12-31](#)
- recovery procedures [40-1](#)
- redundancy
  - EtherChannel [33-2](#)
  - HSRP [36-1](#)
  - STP
    - backbone [17-8](#)
    - path cost [12-26](#)
    - port priority [12-24](#)
- redundant links and UplinkFast [19-12](#)
- reliable transport protocol, EIGRP [34-34](#)
- reloading software [3-15](#)
- Remote Authentication Dial-In User Service
  - See RADIUS
- Remote Copy Protocol
  - See RCP
- Remote Network Monitoring
  - See RMON
- Remote SPAN
  - See RSPAN
- remote SPAN [27-2](#)
- report suppression, IGMP
  - described [23-5](#)
  - disabling [23-13](#)
- requirements
  - cluster [xxxix](#)
  - device manager [xxxviii](#)
  - Network Assistant [xxxviii](#)
- resequencing ACL entries [31-14](#)
- resets, in BGP [34-47](#)
- resetting a UDLD-shutdown interface [26-6](#)
- restricting access
  - NTP services [6-8](#)
  - overview [8-1](#)
  - passwords and privilege levels [8-2](#)
  - RADIUS [8-17](#)
  - TACACS+ [8-10](#)
- retry count, VMPS, changing [12-32](#)
- reverse address resolution [34-8](#)
- Reverse Address Resolution Protocol
  - See RARP

## RFC

- 1058, RIP [34-18](#)
- 1112, IP multicast and IGMP [23-2](#)
- 1157, SNMPv1 [30-2](#)
- 1163, BGP [34-40](#)
- 1166, IP addresses [34-5](#)
- 1253, OSPF [34-24](#)
- 1267, BGP [34-40](#)
- 1305, NTP [6-2](#)
- 1587, NSSAs [34-24](#)
- 1757, RMON [28-2](#)
- 1771, BGP [34-40](#)
- 1901, SNMPv2C [30-2](#)
- 1902 to 1907, SNMPv2 [30-2](#)
- 2236, IP multicast and IGMP [23-2](#)
- 2273-2275, SNMPv3 [30-2](#)

## RIP

- advertisements [34-19](#)
- authentication [34-21](#)
- configuring [34-20](#)
- default configuration [34-19](#)
- described [34-19](#)
- for IPv6 [35-17](#)
- hop counts [34-19](#)
- split horizon [34-22](#)
- summary addresses [34-22](#)
- support for [1-9](#)

## RMON

- default configuration [28-3](#)
- displaying status [28-6](#)
- enabling alarms and events [28-3](#)
- groups supported [28-2](#)
- overview [28-1](#)
- statistics
  - collecting group Ethernet [28-6](#)
  - collecting group history [28-5](#)
- support for [1-10](#)

## root guard

- described [19-8](#)
- enabling [19-14](#)
- support for [1-6](#)

## root switch

- MSTP [18-17](#)
- STP [17-14](#)

route calculation timers, OSPF [34-30](#)route dampening, BGP [34-59](#)routed packets, ACLs on [31-38](#)

## routed ports

- configuring [34-3](#)
- defined [10-4](#)
- IP addresses on [10-22, 34-4](#)

route-map command [34-81](#)

## route maps

- BGP [34-50](#)
- policy-based routing [34-80](#)

## router ACLs

- defined [31-2](#)
- types of [31-4](#)

route reflectors, BGP [34-58](#)router ID, OSPF [34-32](#)route selection, BGP [34-48](#)route summarization, OSPF [34-30](#)route targets, VPN [34-64](#)

## routing

- default [34-2](#)
- dynamic [34-3](#)
- redistribution of information [34-76](#)
- static [34-3](#)

routing domain confederation, BGP [34-58](#)

## Routing Information Protocol

See RIP

routing protocol administrative distances [34-74](#)

**RSPAN 27-2**

- characteristics [27-8](#)
- configuration guidelines [27-16](#)
- default configuration [27-9](#)
- destination ports [27-6](#)
- displaying status [27-23](#)
- interaction with other features [27-8](#)
- monitored ports [27-5](#)
- monitoring ports [27-6](#)
- overview [1-10, 27-1](#)
- received traffic [27-4](#)
- sessions
  - creating [27-17](#)
  - defined [27-3](#)
  - limiting source traffic to specific VLANs [27-22](#)
  - specifying monitored ports [27-17](#)
  - with ingress traffic enabled [27-20](#)
- source ports [27-5](#)
- transmitted traffic [27-5](#)
- VLAN-based [27-6](#)

**RSTP**

- active topology [18-9](#)
- BPDU
  - format [18-12](#)
  - processing [18-13](#)
- designated port, defined [18-9](#)
- designated switch, defined [18-9](#)
- interoperability with IEEE 802.1D
  - described [18-8](#)
  - restarting migration process [18-26](#)
  - topology changes [18-13](#)
- overview [18-8](#)
- port roles
  - described [18-9](#)
  - synchronized [18-11](#)
- proposal-agreement handshake process [18-10](#)

**RSTP (continued)**

- rapid convergence
  - described [18-10](#)
  - edge ports and Port Fast [18-10](#)
  - point-to-point links [18-10, 18-25](#)
  - root ports [18-10](#)
- root port, defined [18-9](#)
- See also MSTP
- running configuration, saving [3-10](#)

---

**S****scheduled reloads 3-15****SDM**

- described [7-1](#)
- templates
  - configuring [7-4](#)
  - number of [7-1](#)

**SDM template**

- configuration guidelines [7-4](#)
- configuring [7-3](#)
- dual IPv4 and IPv6 [7-2](#)
- types of [7-1](#)

**secondary VLANs 14-2****secure HTTP client**

- configuring [8-47](#)
- displaying [8-48](#)

**secure HTTP server**

- configuring [8-46](#)
- displaying [8-48](#)

**secure MAC addresses**

- deleting [24-14](#)
- maximum number of [24-9](#)
- types of [24-8](#)

**secure ports, configuring 24-7****secure remote connections 8-38****Secure Shell**

- See SSH

- Secure Socket Layer
  - See SSL
- security, port [24-7](#)
- security features [1-7](#)
- sequence numbers in log messages [29-7](#)
- server mode, VTP [13-3](#)
- service-provider network, MSTP and RSTP [18-1](#)
- service-provider networks
  - and customer VLANs [16-2](#)
  - and IEEE 802.1Q tunneling [16-1](#)
  - Layer 2 protocols across [16-8](#)
  - Layer 2 protocol tunneling for EtherChannels [16-9](#)
- set-request operation [30-4](#)
- setup program
  - failed command switch replacement [40-10](#)
  - replacing failed command switch [40-8](#)
- severity levels, defining in system messages [29-8](#)
- SFPs
  - monitoring status of [10-26, 40-13](#)
  - security and identification [40-12](#)
  - status, displaying [40-13](#)
- shaped round robin
  - See SRR
- show access-lists hw-summary command [31-21](#)
- show and more command output, filtering [2-10](#)
- show cdp traffic command [25-5](#)
- show cluster members command [5-3](#)
- show configuration command [10-21](#)
- show forward command [40-21](#)
- show interfaces command [10-17, 10-21](#)
- show l2protocol command [16-14, 16-16](#)
- show platform forward command [40-21](#)
- show running-config command
  - displaying ACLs [31-19, 31-20, 31-31, 31-33](#)
  - interface description in [10-21](#)
- shutdown command on interfaces [10-26](#)
- shutdown threshold for Layer 2 protocol packets [16-11](#)
- Simple Network Management Protocol
  - See SNMP
- Smartports macros
  - applying Cisco-default macros [11-6](#)
  - applying global parameter values [11-5, 11-6](#)
  - applying macros [11-5](#)
  - applying parameter values [11-5, 11-7](#)
  - configuration guidelines [11-3](#)
  - creating [11-4](#)
  - default configuration [11-2](#)
  - defined [11-1](#)
  - displaying [11-8](#)
  - tracing [11-3](#)
  - website [11-2](#)
- SNAP [25-1](#)
- SNMP
  - accessing MIB variables with [30-4](#)
  - agent
    - described [30-4](#)
    - disabling [30-8](#)
  - authentication level [30-10](#)
  - community strings
    - configuring [30-8](#)
    - for cluster switches [30-4](#)
    - overview [30-4](#)
  - configuration examples [30-15](#)
  - default configuration [30-6](#)
  - engine ID [30-7](#)
  - groups [30-7, 30-9](#)
  - host [30-7](#)
  - ifIndex values [30-5](#)
  - in-band management [1-5](#)
  - informs
    - and trap keyword [30-11](#)
    - described [30-5](#)
    - differences from traps [30-5](#)
    - disabling [30-14](#)
    - enabling [30-14](#)
  - limiting access by TFTP servers [30-15](#)
  - limiting system log messages to NMS [29-9](#)
  - manager functions [1-4, 30-3](#)

## SNMP (continued)

- managing clusters with [5-4](#)
- MIBs
  - location of [A-3](#)
  - supported [A-1](#)
- notifications [30-5](#)
- overview [30-1, 30-4](#)
- security levels [30-3](#)
- status, displaying [30-16](#)
- system contact and location [30-14](#)
- trap manager, configuring [30-13](#)
- traps
  - described [30-3, 30-5](#)
  - differences from informs [30-5](#)
  - disabling [30-14](#)
  - enabling [30-11](#)
  - enabling MAC address notification [6-22](#)
  - overview [30-1, 30-4](#)
  - types of [30-11](#)
- users [30-7, 30-9](#)
- versions supported [30-2](#)
- SNMPv1 [30-2](#)
- SNMPv2C [30-2](#)
- SNMPv3 [30-2](#)
- snooping, IGMP [23-1](#)
- software images
  - location in flash [B-20](#)
  - recovery procedures [40-2](#)
  - scheduling reloads [3-16](#)
  - tar file format, described [B-20](#)

See also downloading and uploading
- source addresses, in IPv4 ACLs [31-11](#)
- source-and-destination-IP address based forwarding, EtherChannel [33-7](#)
- source-and-destination MAC address forwarding, EtherChannel [33-7](#)
- source-IP address based forwarding, EtherChannel [33-7](#)
- source-MAC address forwarding, EtherChannel [33-7](#)

## SPAN

- configuration guidelines [27-10](#)
- default configuration [27-9](#)
- destination ports [27-6](#)
- displaying status [27-23](#)
- interaction with other features [27-8](#)
- monitored ports [27-5](#)
- monitoring ports [27-6](#)
- overview [1-10, 27-1](#)
- ports, restrictions [24-11](#)
- received traffic [27-4](#)
- sessions
  - configuring ingress forwarding [27-14, 27-21](#)
  - creating [27-11](#)
  - defined [27-3](#)
  - limiting source traffic to specific VLANs [27-15](#)
  - removing destination (monitoring) ports [27-12](#)
  - specifying monitored ports [27-11](#)
  - with ingress traffic enabled [27-13](#)
- source ports [27-5](#)
- transmitted traffic [27-5](#)
- VLAN-based [27-6](#)
- spanning tree and native VLANs [12-19](#)
- Spanning Tree Protocol
  - See STP
- SPAN traffic [27-4](#)
- speed, configuring on interfaces [10-16](#)
- split horizon, RIP [34-22](#)
- SRR
  - configuring
    - shaped weights on egress queues [32-75](#)
    - shared weights on egress queues [32-76](#)
    - shared weights on ingress queues [32-69](#)
  - described [32-14](#)
  - shaped mode [32-14](#)
  - shared mode [32-14](#)
  - support for [1-8, 1-9](#)

## SSH

- configuring [8-39](#)
- cryptographic software image [8-37](#)
- described [1-5, 8-38](#)
- encryption methods [8-38](#)
- user authentication methods, supported [8-38](#)

## SSL

- configuration guidelines [8-44](#)
- configuring a secure HTTP client [8-47](#)
- configuring a secure HTTP server [8-46](#)
- cryptographic software image [8-41](#)
- described [8-41](#)
- monitoring [8-48](#)

standby command switch, requirements [5-2](#)

standby ip command [36-5](#)

standby links [20-1](#)

standby router [36-1](#)

standby timers, HSRP [36-9](#)

startup configuration

booting

- manually [3-13](#)
- specific image [3-12](#)

clearing [B-19](#)

configuration file

- automatically downloading [3-12](#)
- specifying the filename [3-12](#)

default boot configuration [3-12](#)

stateless autoconfiguration [35-4](#)

static access ports

- assigning to VLAN [12-11](#)
- defined [10-3, 12-3](#)

static addresses

See addresses

static IP routing [1-9](#)

static MAC addressing [1-7](#)

static routes

- configuring [34-74](#)
- configuring for IPv6 [35-15](#)

static routing [34-3](#)

static VLAN membership [12-2](#)

statistics

- 802.1x [9-26](#)
- CDP [25-5](#)
- interface [10-25](#)
- IP multicast routing [37-50](#)
- OSPF [34-33](#)
- QoS ingress and egress [32-78](#)
- RMON group Ethernet [28-6](#)
- RMON group history [28-5](#)
- SNMP input and output [30-16](#)
- VTP [13-16](#)

sticky learning [24-8](#)

storm control

- configuring [24-3](#)
- described [24-1](#)
- disabling [24-5](#)
- displaying [24-17](#)
- support for [1-3](#)
- thresholds [24-1](#)

## STP

accelerating root port selection [19-4](#)

BackboneFast

- described [19-5](#)
- disabling [19-14](#)
- enabling [19-13](#)

BPDU filtering

- described [19-3](#)
- disabling [19-12](#)
- enabling [19-12](#)

BPDU guard

- described [19-3](#)
- disabling [19-11](#)
- enabling [19-11](#)

BPDU message exchange [17-3](#)

configuration guidelines [17-12, 19-10](#)



## STP (continued)

## configuring

- forward-delay time [17-21](#)
- hello time [17-20](#)
- maximum aging time [17-21](#)
- path cost [17-17](#)
- port priority [17-16](#)
- root switch [17-14](#)
- secondary root switch [17-16](#)
- spanning-tree mode [17-13](#)
- switch priority [17-19](#)
- transmit hold-count

counters, clearing [17-22](#)default configuration [17-11](#)default optional feature configuration [19-9](#)designated port, defined [17-3](#)designated switch, defined [17-3](#)detecting indirect link failures [19-5](#)disabling [17-14](#)displaying status [17-22](#)

## EtherChannel guard

- described [19-7](#)
- disabling [19-14](#)
- enabling [19-14](#)

## extended system ID

- effects on root switch [17-14](#)
- effects on the secondary root switch [17-16](#)
- overview [17-4](#)
- unexpected behavior [17-15](#)

features supported [1-5](#)IEEE 802.1D and bridge ID [17-4](#)IEEE 802.1D and multicast addresses [17-8](#)IEEE 802.1t and VLAN identifier [17-4](#)inferior BPDU [17-3](#)instances supported [17-9](#)interface state, blocking to forwarding [19-2](#)

## STP (continued)

## interface states

- blocking [17-6](#)
- disabled [17-7](#)
- forwarding [17-5, 17-6](#)
- learning [17-6](#)
- listening [17-6](#)
- overview [17-4](#)

interoperability and compatibility among modes [17-10](#)keepalive messages [17-2](#)Layer 2 protocol tunneling [16-8](#)limitations with IEEE 802.1Q trunks [17-10](#)

## load sharing

- overview [12-24](#)
- using path costs [12-26](#)
- using port priorities [12-25](#)

## loop guard

- described [19-9](#)
- enabling [19-15](#)

modes supported [17-9](#)multicast addresses, effect of [17-8](#)optional features supported [1-6](#)overview [17-2](#)path costs [12-26, 12-27](#)

## Port Fast

- described [19-2](#)
- enabling [19-10](#)

port priorities [12-25](#)preventing root switch selection [19-8](#)protocols supported [17-9](#)redundant connectivity [17-8](#)

## root guard

- described [19-8](#)
- enabling [19-14](#)

root port, defined [17-3](#)

- STP (continued)
  - root switch
    - configuring [17-14](#)
    - effects of extended system ID [17-4, 17-14](#)
    - election [17-3](#)
    - unexpected behavior [17-15](#)
  - shutdown Port Fast-enabled port [19-3](#)
  - status, displaying [17-22](#)
  - superior BPDU [17-3](#)
  - timers, described [17-19](#)
  - UplinkFast
    - described [19-4](#)
    - enabling [19-12](#)
  - VLAN-bridge [17-10](#)
- stratum, NTP [6-2](#)
- stub areas, OSPF [34-28](#)
- subdomains, private VLAN [14-1](#)
- subnet mask [34-5](#)
- subnet zero [34-6](#)
- success response, VMPS [12-28](#)
- summer time [6-13](#)
- SunNet Manager [1-4](#)
- supernet [34-6](#)
- SVIs
  - and IP unicast routing [34-3](#)
  - and router ACLs [31-4](#)
  - connecting VLANs [10-9](#)
  - defined [10-5](#)
  - routing between VLANs [12-2](#)
- switch clustering technology [5-1](#)
  - See also clusters, switch
- switch console port [1-5](#)
- Switch Database Management
  - See SDM
- switched packets, ACLs on [31-37](#)
- Switched Port Analyzer
  - See SPAN
- switched ports [10-2](#)
- switchport block multicast command [24-7](#)
- switchport block unicast command [24-7](#)
- switchport command [10-14](#)
- switchport mode dot1q-tunnel command [16-6](#)
- switchport protected command [24-6](#)
- switch priority
  - MSTP [18-22](#)
  - STP [17-19](#)
- switch software features [1-1](#)
- switch virtual interface
  - See SVI
- synchronization, BGP [34-44](#)
- syslog
  - See system message logging
- system clock
  - configuring
    - daylight saving time [6-13](#)
    - manually [6-11](#)
    - summer time [6-13](#)
    - time zones [6-12](#)
  - displaying the time and date [6-12](#)
  - overview [6-2](#)
  - See also NTP
- system message logging
  - default configuration [29-3](#)
  - defining error message severity levels [29-8](#)
  - disabling [29-3](#)
  - displaying the configuration [29-12](#)
  - enabling [29-4](#)
  - facility keywords, described [29-12](#)
  - level keywords, described [29-9](#)
  - limiting messages [29-9](#)
  - message format [29-2](#)
  - overview [29-1](#)
  - sequence numbers, enabling and disabling [29-7](#)
  - setting the display destination device [29-4](#)
  - synchronizing log messages [29-5](#)
  - syslog facility [1-10](#)
  - time stamps, enabling and disabling [29-7](#)

- system message logging (continued)
  - UNIX syslog servers
    - configuring the daemon [29-11](#)
    - configuring the logging facility [29-11](#)
    - facilities supported [29-12](#)
- system MTU and IEEE 802.1Q tunneling [16-5](#)
- system name
  - default configuration [6-15](#)
  - default setting [6-15](#)
  - manual configuration [6-15](#)
  - See also DNS
- system prompt, default setting [6-14](#), [6-15](#)
- system resources, optimizing [7-1](#)

---

## T

### TACACS+

- accounting, defined [8-11](#)
- authentication, defined [8-11](#)
- authorization, defined [8-11](#)
- configuring
  - accounting [8-17](#)
  - authentication key [8-13](#)
  - authorization [8-16](#)
  - login authentication [8-14](#)
- default configuration [8-13](#)
- displaying the configuration [8-17](#)
- identifying the server [8-13](#)
- limiting the services to the user [8-16](#)
- operation of [8-12](#)
- overview [8-10](#)
- support for [1-7](#)
- tracking services accessed by user [8-17](#)

tagged packets

- IEEE 802.1Q [16-3](#)
- Layer 2 protocol [16-8](#)

- tar files
  - creating [B-5](#)
  - displaying the contents of [B-6](#)
  - extracting [B-7](#)
  - image file format [B-20](#)
- TDR [1-10](#)
- Telnet
  - accessing management interfaces [2-10](#)
  - number of connections [1-5](#)
  - setting a password [8-6](#)
- templates, SDM [7-1](#)
- temporary self-signed certificate [8-42](#)
- Terminal Access Controller Access Control System Plus
  - See TACACS+
- terminal lines, setting a password [8-6](#)
- TFTP
  - configuration files
    - downloading [B-10](#)
    - preparing the server [B-10](#)
    - uploading [B-11](#)
  - configuration files in base directory [3-6](#)
  - configuring for autoconfiguration [3-5](#)
  - image files
    - deleting [B-23](#)
    - downloading [B-22](#)
    - preparing the server [B-21](#)
    - uploading [B-24](#)
  - limiting access by servers [30-15](#)
- TFTP server [1-4](#)
- threshold, traffic level [24-2](#)
- time
  - See NTP and system clock
- Time Domain Reflector
  - See TDR
- time-range command [31-16](#)
- time ranges in ACLs [31-16](#)
- time stamps in log messages [29-7](#)
- time zones [6-12](#)

- Token Ring VLANs
  - support for [12-6](#)
  - VTP support [13-4](#)
- ToS [1-8](#)
- traceroute, Layer 2
  - and ARP [40-16](#)
  - and CDP [40-15](#)
  - broadcast traffic [40-15](#)
  - described [40-15](#)
  - IP addresses and subnets [40-16](#)
  - MAC addresses and VLANs [40-15](#)
  - multicast traffic [40-15](#)
  - multiple devices on a port [40-16](#)
  - unicast traffic [40-15](#)
  - usage guidelines [40-15](#)
- traceroute command [40-17](#)
  - See also IP traceroute
- traffic
  - blocking flooded [24-7](#)
  - fragmented [31-5](#)
  - unfragmented [31-5](#)
- traffic policing [1-8](#)
- traffic suppression [24-1](#)
- transmit hold-count
  - see STP
- transparent mode, VTP [13-3, 13-12](#)
- trap-door mechanism [3-2](#)
- traps
  - configuring MAC address notification [6-22](#)
  - configuring managers [30-11](#)
  - defined [30-3](#)
  - enabling [6-22, 30-11](#)
  - notification types [30-11](#)
  - overview [30-1, 30-4](#)
- troubleshooting
  - connectivity problems [40-13, 40-15, 40-16](#)
  - detecting unidirectional links [26-1](#)
  - displaying crash information [40-23](#)
  - PIMv1 and PIMv2 interoperability problems [37-22](#)
  - troubleshooting (continued)
    - setting packet forwarding [40-21](#)
    - SFP security and identification [40-12](#)
    - show forward command [40-21](#)
    - with CiscoWorks [30-4](#)
    - with debug commands [40-19](#)
    - with ping [40-13](#)
    - with system message logging [29-1](#)
    - with traceroute [40-16](#)
- trunking encapsulation [1-6](#)
- trunk ports
  - configuring [12-21](#)
  - defined [10-3, 12-3](#)
  - encapsulation [12-21, 12-25, 12-27](#)
- trunks
  - allowed-VLAN list [12-22](#)
  - configuring [12-21, 12-25, 12-27](#)
  - ISL [12-16](#)
  - load sharing
    - setting STP path costs [12-26](#)
    - using STP port priorities [12-24, 12-25](#)
  - native VLAN for untagged traffic [12-23](#)
  - parallel [12-26](#)
  - pruning-eligible list [12-23](#)
  - to non-DTP device [12-17](#)
- trusted boundary for QoS [32-38](#)
- trusted port states
  - between QoS domains [32-40](#)
  - classification options [32-5](#)
  - ensuring port security for IP phones [32-38](#)
  - support for [1-8](#)
  - within a QoS domain [32-36](#)
- trustpoints, CA [8-42](#)
- tunneling
  - defined [16-1](#)
  - IEEE 802.1Q [16-1](#)
  - Layer 2 protocol [16-8](#)

tunnel ports

- defined [12-4](#)
- described [10-4, 16-1](#)
- IEEE 802.1Q, configuring [16-6](#)
- incompatibilities with other features [16-6](#)

twisted-pair Ethernet, detecting unidirectional links [26-1](#)

type of service

- See ToS

## U

### UDLD

- configuration guidelines [26-4](#)
- default configuration [26-4](#)
- disabling
  - globally [26-5](#)
  - on fiber-optic interfaces [26-5](#)
  - per interface [26-5](#)
- echoing detection mechanism [26-3](#)
- enabling
  - globally [26-5](#)
  - per interface [26-5](#)
- Layer 2 protocol tunneling [16-10](#)
- link-detection mechanism [26-1](#)
- neighbor database [26-2](#)
- overview [26-1](#)
- resetting an interface [26-6](#)
- status, displaying [26-6](#)
- support for [1-5](#)

UDP, configuring [34-15](#)

unauthorized ports with IEEE 802.1x [9-4](#)

unicast MAC address filtering [1-5](#)

- and adding static addresses [6-25](#)
- and broadcast MAC addresses [6-25](#)
- and CPU packets [6-25](#)
- and multicast addresses [6-25](#)
- and router MAC addresses [6-25](#)
- configuration guidelines [6-25](#)
- described [6-25](#)

- unicast storm [24-1](#)
- unicast storm control command [24-4](#)
- unicast traffic, blocking [24-7](#)
- UniDirectional Link Detection protocol
  - See UDLD
- UNIX syslog servers
  - daemon configuration [29-11](#)
  - facilities supported [29-12](#)
  - message logging configuration [29-11](#)
- unrecognized Type-Length-Value (TLV) support [13-4](#)
- upgrading information
  - See release notes
- upgrading software images
  - See downloading
- UplinkFast
  - described [19-4](#)
  - disabling [19-13](#)
  - enabling [19-12](#)
  - support for [1-6](#)
- uploading
  - configuration files
    - preparing [B-10, B-13, B-16](#)
    - reasons for [B-8](#)
    - using FTP [B-14](#)
    - using RCP [B-18](#)
    - using TFTP [B-11](#)
  - image files
    - preparing [B-21, B-25, B-29](#)
    - reasons for [B-19](#)
    - using FTP [B-28](#)
    - using RCP [B-33](#)
    - using TFTP [B-24](#)
- User Datagram Protocol
  - See UDP
- user EXEC mode [2-2](#)
- username-based authentication [8-6](#)

## V

- version-dependent transparent mode [13-4](#)
- Virtual Private Network
  - See VPN
- virtual router [36-1, 36-2](#)
- vlan.dat file [12-5](#)
- VLAN 1, disabling on a trunk port [12-22](#)
- VLAN 1 minimization [12-22](#)
- VLAN ACLs
  - See VLAN maps
- vlan-assignment response, VMPS [12-28](#)
- VLAN configuration
  - at bootup [12-8](#)
  - saving [12-8](#)
- VLAN configuration mode [2-2, 12-7](#)
- VLAN database
  - and startup configuration file [12-8](#)
  - and VTP [13-1](#)
  - VLAN configuration saved in [12-7](#)
  - VLANs saved in [12-4](#)
- vlan database command [12-7](#)
- vlan dot1q tag native command [16-5](#)
- VLAN filtering and SPAN [27-6](#)
- vlan global configuration command [12-7](#)
- VLAN ID, discovering [6-26](#)
- VLAN management domain [13-2](#)
- VLAN Management Policy Server
  - See VMPS
- VLAN map entries, order of [31-29](#)
- VLAN maps
  - applying [31-33](#)
  - common uses for [31-33](#)
  - configuration guidelines [31-29](#)
  - configuring [31-29](#)
  - creating [31-30](#)
  - defined [31-2](#)
  - denying access to a server example [31-35](#)
  - denying and permitting packets [31-31](#)
  - VLAN maps (continued)
    - displaying [31-40](#)
    - examples of ACLs and VLAN maps [31-31](#)
    - removing [31-33](#)
    - support for [1-7](#)
    - wiring closet configuration example [31-34](#)
- VLAN membership
  - confirming [12-31](#)
  - modes [12-3](#)
- VLAN Query Protocol
  - See VQP
- VLANs
  - adding [12-9](#)
  - adding to VLAN database [12-9](#)
  - aging dynamic addresses [17-9](#)
  - allowed on trunk [12-22](#)
  - and spanning-tree instances [12-3, 12-6, 12-13](#)
  - configuration guidelines, extended-range VLANs [12-13](#)
  - configuration guidelines, normal-range VLANs [12-6](#)
  - configuration options [12-7](#)
  - configuring [12-1](#)
  - configuring IDs 1006 to 4094 [12-13](#)
  - connecting through SVIs [10-9](#)
  - creating in config-vlan mode [12-9](#)
  - creating in VLAN configuration mode [12-10](#)
  - customer numbering in service-provider networks [16-3](#)
  - default configuration [12-8](#)
  - deleting [12-10](#)
  - described [10-2, 12-1](#)
  - displaying [12-16](#)
  - extended-range [12-1, 12-12](#)
  - features [1-6](#)
  - illustrated [12-2](#)
  - internal [12-13](#)
  - limiting source traffic with RSPAN [27-22](#)
  - limiting source traffic with SPAN [27-15](#)
  - modifying [12-9](#)
  - multicast [23-14](#)
  - native, configuring [12-23](#)

- VLANs (continued)
  - normal-range [12-1, 12-4](#)
  - number supported [1-6](#)
  - parameters [12-5](#)
  - port membership modes [12-3](#)
  - static-access ports [12-11](#)
  - STP and IEEE 802.1Q trunks [17-10](#)
  - supported [12-2](#)
  - Token Ring [12-6](#)
  - traffic between [12-2](#)
  - VLAN-bridge STP [17-10, 39-2](#)
  - VTP modes [13-3](#)
- VLAN Trunking Protocol
  - See VTP
- VLAN trunks [12-16](#)
- VMPS
  - administering [12-32](#)
  - configuration example [12-33](#)
  - configuration guidelines [12-29](#)
  - default configuration [12-29](#)
  - description [12-28](#)
  - dynamic port membership
    - described [12-29](#)
    - reconfirming [12-31](#)
    - troubleshooting [12-33](#)
  - entering server address [12-30](#)
  - mapping MAC addresses to VLANs [12-28](#)
  - monitoring [12-32](#)
  - reconfirmation interval, changing [12-31](#)
  - reconfirming membership [12-31](#)
  - retry count, changing [12-32](#)
- voice-over-IP [15-1](#)
- voice VLAN
  - Cisco 7960 phone, port connections [15-1](#)
  - configuration guidelines [15-3](#)
  - configuring IP phones for data traffic
    - override CoS of incoming frame [15-6](#)
    - trust CoS priority of incoming frame [15-6](#)
- voice VLAN (continued)
  - configuring ports for voice traffic in
    - 802.1p priority tagged frames [15-8](#)
    - 802.1Q frames [15-5](#)
  - connecting to an IP phone [15-4](#)
  - default configuration [15-3](#)
  - described [15-1](#)
  - displaying [15-7](#)
  - IP phone data traffic, described [15-2](#)
  - IP phone voice traffic, described [15-2](#)
- VPN
  - configuring routing in [34-66](#)
  - forwarding [34-64](#)
  - in service provider networks [34-61](#)
  - routes [34-62](#)
- VPN routing and forwarding table
  - See VRF
- VQP [1-6, 12-28](#)
- VRF
  - defining [34-64](#)
  - tables [34-61](#)
- VTP
  - adding a client to a domain [13-14](#)
  - advertisements [12-19, 13-3](#)
  - and extended-range VLANs [13-1](#)
  - and normal-range VLANs [13-1](#)
  - client mode, configuring [13-11](#)
  - configuration
    - global configuration mode [13-7](#)
    - guidelines [13-8](#)
    - privileged EXEC mode [13-7](#)
    - requirements [13-9](#)
    - saving [13-7](#)
    - VLAN configuration mode [13-7](#)
  - configuration mode options [13-7](#)
  - configuration requirements [13-9](#)
  - configuration revision number
    - guideline [13-14](#)
    - resetting [13-15](#)

## VTP (continued)

## configuring

client mode [13-11](#)server mode [13-9](#)transparent mode [13-12](#)consistency checks [13-4](#)default configuration [13-6](#)described [13-1](#)disabling [13-12](#)domain names [13-8](#)domains [13-2](#)Layer 2 protocol tunneling [16-8](#)

## modes

client [13-3, 13-11](#)server [13-3, 13-9](#)transitions [13-3](#)transparent [13-3, 13-12](#)monitoring [13-16](#)passwords [13-8](#)

## pruning

disabling [13-14](#)enabling [13-14](#)examples [13-5](#)overview [13-4](#)support for [1-6](#)pruning-eligible list, changing [12-23](#)server mode, configuring [13-9](#)statistics [13-16](#)support for [1-6](#)Token Ring support [13-4](#)transparent mode, configuring [13-12](#)using [13-1](#)version, guidelines [13-8](#)Version 1 [13-4](#)

## Version 2

configuration guidelines [13-8](#)disabling [13-13](#)enabling [13-13](#)overview [13-4](#)

---

**W**

weighted tail drop

See WTD

wizards [1-2](#)

## WTD

described [32-13](#)

setting thresholds

egress queue-sets [32-71](#)ingress queues [32-67](#)support for [1-8, 1-9](#)

---

**X**Xmodem protocol [40-2](#)