



INDEX

A

- AAA down policy, NAC Layer 2 IP validation [10](#)
- abbreviating commands [4](#)
- ABRs [24](#)
- AC (command switch) [10](#)
- access-class command [19](#)
- access control entries
 - See ACEs
- access control entry (ACE) [3](#)
- access-denied response, VMPS [28](#)
- access groups
 - applying IPv4 ACLs to interfaces [20](#)
 - Layer 2 [20](#)
 - Layer 3 [20](#)
- accessing
 - clusters, switch [13](#)
 - command switches [11](#)
 - member switches [13](#)
 - switch clusters [13](#)
- access lists
 - See ACLs
- access ports
 - and Layer 2 protocol tunneling [11](#)
 - defined [3](#)
 - in switch clusters [9](#)
- access template [1](#)
- accounting
 - with 802.1x [39](#)
 - with IEEE 802.1x [8](#)
 - with RADIUS [28](#)
 - with TACACS+ [11, 17](#)
- ACEs
 - and QoS [7](#)
 - defined [2](#)
 - Ethernet [2](#)
 - IP [2](#)
- ACLs
 - ACEs [2](#)
 - any keyword [12](#)
 - applying
 - on bridged packets [37](#)
 - on multicast packets [39](#)
 - on routed packets [38](#)
 - on switched packets [37](#)
 - time ranges to [16](#)
 - to an interface [19, 7](#)
 - to IPv6 interfaces [7](#)
 - to QoS [7](#)
 - classifying traffic for QoS [43](#)
 - comments in [18](#)
 - compiling [21](#)
 - defined [1, 7](#)
 - examples of [21, 43](#)
 - extended IP, configuring for QoS classification [44](#)
 - extended IPv4
 - creating [10](#)
 - matching criteria [7](#)
 - hardware and software handling [21](#)
 - host keyword [12](#)
- IP
 - creating [7](#)
 - fragments and QoS guidelines [33](#)
 - implicit deny [9, 13, 15](#)
 - implicit masks [9](#)

- matching criteria [7](#)
 - undefined [20](#)
- IPv4
 - applying to interfaces [19](#)
 - creating [7](#)
 - matching criteria [7](#)
 - named [14](#)
 - numbers [8](#)
 - terminal lines, setting on [18](#)
 - unsupported features [6](#)
- IPv6
 - applying to interfaces [7](#)
 - configuring [4, 5](#)
 - displaying [8](#)
 - interactions with other features [4](#)
 - limitations [3](#)
 - matching criteria [3](#)
 - named [3](#)
 - precedence of [2](#)
 - supported [2](#)
 - unsupported features [3](#)
- Layer 4 information in [36](#)
- logging messages [8](#)
- MAC extended [26, 45](#)
- matching [7, 20, 3](#)
- monitoring [39, 8](#)
- named, IPv4 [14](#)
- named, IPv6 [3](#)
- names [4](#)
- number per QoS class map [33](#)
- port [2](#)
- precedence of [2](#)
- QoS [7, 43](#)
- resequencing entries [14](#)
- router [2](#)
- router ACLs and VLAN map configuration guidelines [36](#)
- standard IP, configuring for QoS classification [43](#)
- standard IPv4
 - creating [9](#)
 - matching criteria [7](#)
 - support for [9](#)
 - support in hardware [21](#)
 - time ranges [16](#)
 - types supported [2](#)
 - unsupported features, IPv4 [6](#)
 - unsupported features, IPv6 [3](#)
 - using router ACLs with VLAN maps [35](#)
 - VLAN maps
 - configuration guidelines [29](#)
 - configuring [28](#)
- active link [4, 5, 6](#)
- active links [2](#)
- active router [1](#)
- active traffic monitoring, IP SLAs [1](#)
- address aliasing [2](#)
- addresses
 - displaying the MAC address table [27](#)
 - dynamic
 - accelerated aging [8](#)
 - changing the aging time [21](#)
 - default aging [8](#)
 - defined [19](#)
 - learning [20](#)
 - removing [22](#)
 - IPv6 [2](#)
 - MAC, discovering [27](#)
 - multicast
 - group address range [3](#)
 - STP address management [8](#)
 - static
 - adding and removing [24](#)
 - defined [19](#)
- address resolution [27, 8](#)
- Address Resolution Protocol
 - See ARP
- adjacency tables, with CEF [76](#)

- administrative distances
 - defined [89](#)
 - OSPF [30](#)
 - routing protocol defaults [79](#)
- advanced IP services image [1](#)
- advertisements
 - CDP [1](#)
 - LLDP [2](#)
 - RIP [19](#)
 - VTP [19,3](#)
- aggregatable global unicast addresses [3](#)
- aggregate addresses, BGP [57](#)
- aggregated ports
 - See EtherChannel
- aggregate policers [58](#)
- aggregate policing [11](#)
- aging, accelerating [8](#)
- aging time
 - accelerated
 - for MSTP [23](#)
 - for STP [8,21](#)
 - MAC address table [21](#)
 - maximum
 - for MSTP [23,24](#)
 - for STP [21,22](#)
- alarms, RMON [3](#)
- allowed-VLAN list [21](#)
- AP1250 (Cisco wireless access point) [7](#)
- application engines, redirecting traffic to [1](#)
- area border routers
 - See ABRs
- ARP
 - configuring [9](#)
 - defined [5,27,8](#)
 - encapsulation [9](#)
 - static cache configuration [9](#)
 - table
 - address resolution [27](#)
 - managing [27](#)
- ASBRs [24](#)
- AS-path filters, BGP [51](#)
- asymmetrical links, and IEEE 802.1Q tunneling [4](#)
- attributes, RADIUS
 - vendor-proprietary [31](#)
 - vendor-specific [29](#)
- authentication
 - EIGRP [38](#)
 - HSRP [10](#)
 - local mode with AAA [36](#)
 - NTP associations [4](#)
 - RADIUS
 - key [21](#)
 - login [23](#)
 - TACACS+
 - defined [11](#)
 - key [13](#)
 - login [14](#)

See also port-based authentication
- authentication failed VLAN
 - See restricted VLAN
- authentication keys, and routing protocols [89](#)
- authoritative time source, described [2](#)
- authorization
 - with RADIUS [27](#)
 - with TACACS+ [11,16](#)
- authorized ports with IEEE 802.1x [7](#)
- autoconfiguration [3](#)
- automatic discovery
 - considerations
 - beyond a noncandidate device [7](#)
 - brand new switches [9](#)
 - connectivity [4](#)
 - different VLANs [6](#)
 - management VLANs [7](#)
 - non-CDP-capable devices [6](#)
 - noncluster-capable devices [6](#)
 - routed ports [8](#)

in switch clusters [4](#)

See also CDP

automatic QoS

See QoS

automatic recovery, clusters [10](#)

See also HSRP

auto-MDIX

configuring [21](#)

described [21](#)

autonegotiation

duplex mode [3](#)

interface configuration guidelines [18](#)

mismatches [11](#)

autonomous system boundary routers

See ASBRs

autonomous systems, in BGP [45](#)

Auto-RP, described [6](#)

autosensing, port speed [3](#)

autostate exclude [5](#)

auxiliary VLAN

See voice VLAN

availability, features [7](#)

B

BackboneFast

described [5](#)

disabling [14](#)

enabling [13](#)

support for [7](#)

backup interfaces

See Flex Links

backup links [2](#)

backup static routing, configuring [12](#)

banners

configuring

login [18](#)

message-of-the-day login [18](#)

default configuration [17](#)

when displayed [17](#)

Berkeley r-tools replacement [48](#)

BGP

aggregate addresses [57](#)

aggregate routes, configuring [57](#)

CIDR [57](#)

clear commands [60](#)

community filtering [54](#)

configuring neighbors [55](#)

default configuration [42](#)

described [42](#)

enabling [45](#)

monitoring [60](#)

multipath support [49](#)

neighbors, types of [45](#)

path selection [49](#)

peers, configuring [55](#)

prefix filtering [53](#)

resetting sessions [48](#)

route dampening [59](#)

route maps [51](#)

route reflectors [58](#)

routing domain confederation [58](#)

routing session with multi-VRF CE [71](#)

show commands [60](#)

supernets [57](#)

support for [12](#)

Version 4 [42](#)

binding cluster group and HSRP group [12](#)

binding database

address, DHCP server

See DHCP, Cisco IOS server database

DHCP snooping

See DHCP snooping binding database

bindings

address, Cisco IOS DHCP server [6](#)

DHCP snooping database [6](#)

IP source guard [15](#)

binding table, DHCP snooping
 See DHCP snooping binding database

blocking packets [7](#)

Boolean expressions in tracked lists [4](#)

booting
 boot loader, function of [2](#)
 boot process [2](#)
 manually [17](#)
 specific image [18](#)

boot loader
 accessing [18](#)
 described [2](#)
 environment variables [18](#)
 prompt [18](#)
 trap-door mechanism [2](#)

bootstrap router (BSR), described [7](#)

Border Gateway Protocol
 See BGP

BPDU
 error-disabled state [2](#)
 filtering [3](#)
 RSTP format [12](#)

BPDU filtering
 described [3](#)
 disabling [12](#)
 enabling [12](#)
 support for [7](#)

BPDU guard
 described [2](#)
 disabling [12](#)
 enabling [11](#)
 support for [7](#)

bridged packets, ACLs on [37](#)

bridge groups
 See fallback bridging

bridge protocol data unit
 See BPDU

broadcast flooding [16](#)

broadcast packets
 directed [13](#)
 flooded [13](#)

broadcast storm-control command [4](#)

broadcast storms [1, 13](#)

C

cables, monitoring for unidirectional links [1](#)

candidate switch
 automatic discovery [4](#)
 defined [3](#)
 requirements [3](#)
 See also command switch, cluster standby group, and member switch

CA trustpoint
 configuring [44](#)
 defined [42](#)

CDP
 and trusted boundary [39](#)
 automatic discovery in switch clusters [4](#)
 configuring [2](#)
 default configuration [2](#)
 defined with LLDP [1](#)
 described [1](#)
 disabling for routing device [3 to 4](#)
 enabling and disabling
 on an interface [4](#)
 on a switch [3](#)
 Layer 2 protocol tunneling [7](#)
 monitoring [4](#)
 overview [1](#)
 power negotiation extensions [7](#)
 support for [6](#)
 transmission timer and holdtime, setting [2](#)
 updates [2](#)

- CEF
 - defined [76](#)
 - enabling [77](#)
 - IPv6 [19](#)
- CGMP
 - as IGMP snooping learning method [9](#)
 - clearing cached group entries [60](#)
 - enabling server support [43](#)
 - joining multicast group [3](#)
 - overview [9](#)
 - server support only [9](#)
 - switch support of [4](#)
- CIDR [57](#)
- CipherSuites [43](#)
- Cisco 7960 IP Phone [1](#)
- Cisco AP1250 wireless access point [7](#)
- Cisco Discovery Protocol
 - See CDP
- Cisco Express Forwarding
 - See CEF
- Cisco Group Management Protocol
 - See CGMP
- Cisco intelligent power management [7](#)
- Cisco IOS DHCP server
 - See DHCP, Cisco IOS DHCP server
- Cisco IOS File System
 - See IFS
- Cisco IOS IP SLAs [1](#)
- CiscoWorks 2000 [5, 4](#)
- CIST regional root
 - See MSTP
- CIST root
 - See MSTP
- civic location [3](#)
- classless interdomain routing
 - See CIDR
- classless routing [6](#)
- class maps for QoS
 - configuring [46](#)
 - described [7](#)
 - displaying [78](#)
- class of service
 - See CoS
- clearing interfaces [31](#)
- CLI
 - abbreviating commands [4](#)
 - command modes [1](#)
 - configuration logging [5](#)
 - described [5](#)
 - editing features
 - enabling and disabling [7](#)
 - keystroke editing [7](#)
 - wrapped lines [9](#)
 - error messages [5](#)
 - filtering command output [10](#)
 - getting help [3](#)
 - history
 - changing the buffer size [6](#)
 - described [6](#)
 - disabling [7](#)
 - recalling commands [6](#)
 - managing clusters [14](#)
 - no and default forms of commands [4](#)
- client mode, VTP [3](#)
- client processes, tracking [1](#)
- clock
 - See system clock
- clusters, switch
 - accessing [13](#)
 - automatic discovery [4](#)
 - automatic recovery [10](#)
 - benefits [2](#)
 - compatibility [4](#)
 - described [1](#)
 - LRE profile considerations [14](#)

- managing
 - through CLI [14](#)
 - through SNMP [15](#)
- planning [4](#)
- planning considerations
 - automatic discovery [4](#)
 - automatic recovery [10](#)
 - CLI [14](#)
 - host names [13](#)
 - IP addresses [13](#)
 - LRE profiles [14](#)
 - passwords [13](#)
 - RADIUS [14](#)
 - SNMP [14, 15](#)
 - TACACS+ [14](#)

See also candidate switch, command switch, cluster standby group, member switch, and standby command switch
- cluster standby group
 - and HSRP group [12](#)
 - automatic recovery [12](#)
 - considerations [11](#)
 - defined [2](#)
 - requirements [3](#)
 - virtual IP address [11](#)

See also HSRP
- CNS [5](#)
- Configuration Engine
 - configID, deviceID, hostname [3](#)
 - configuration service [2](#)
 - described [1](#)
 - event service [3](#)
- embedded agents
 - described [5](#)
 - enabling automated configuration [6](#)
 - enabling configuration agent [9](#)
 - enabling event agent [7](#)
- management functions [5](#)
- Coarse Wave Division Multiplexer
 - See CWDM SFPs
- command-line interface
 - See CLI
- command modes [1](#)
- commands
 - abbreviating [4](#)
 - no and default [4](#)
- commands, setting privilege levels [8](#)
- command switch
 - accessing [11](#)
 - active (AC) [10](#)
 - configuration conflicts [11](#)
 - defined [2](#)
 - passive (PC) [10](#)
 - password privilege levels [15](#)
 - priority [10](#)
 - recovery
 - from command-switch failure [10, 7](#)
 - from lost member connectivity [11](#)
 - redundant [10](#)
 - replacing
 - with another switch [9](#)
 - with cluster member [8](#)
 - requirements [3](#)
 - standby (SC) [10](#)

See also candidate switch, cluster standby group, member switch, and standby command switch
- community list, BGP [54](#)
- community ports [2](#)
- community strings
 - configuring [14, 8](#)
 - for cluster switches [4](#)
 - in clusters [14](#)
 - overview [4](#)
 - SNMP [14](#)
- community VLANs [2, 3](#)
- compatibility, feature [12](#)
- config.text [16](#)

- configurable leave timer, IGMP **6**
- configuration, initial
 - defaults **14**
 - Express Setup **2**
- configuration changes, logging **10**
- configuration conflicts, recovering from lost member connectivity **11**
- configuration examples, network **17**
- configuration files
 - archiving **18**
 - clearing the startup configuration **18**
 - creating using a text editor **9**
 - default name **16**
 - deleting a stored configuration **18**
 - described **7**
 - downloading
 - automatically **16**
 - preparing **9, 12, 15**
 - reasons for **7**
 - using FTP **12**
 - using RCP **16**
 - using TFTP **10**
 - guidelines for creating and using **8**
 - guidelines for replacing and rolling back **20**
 - invalid combinations when copying **4**
 - limiting TFTP server access **15**
 - obtaining with DHCP **8**
 - password recovery disable considerations **5**
 - replacing a running configuration **18, 19**
 - rolling back a running configuration **18, 19**
 - specifying the filename **16**
 - system contact and location information **15**
 - types and location **8**
 - uploading
 - preparing **9, 12, 15**
 - reasons for **7**
 - using FTP **13**
 - using RCP **17**
 - using TFTP **10**
- configuration guidelines, multi-VRF CE **64**
- configuration logger **10**
- configuration logging **5**
- configuration replacement **18**
- configuration rollback **18**
- configuration settings, saving **15**
- configure terminal command **11**
- configuring port-based authentication violation modes **31**
- configuring small-frame arrival rate **5**
- config-vlan mode **2, 7**
- conflicts, configuration **11**
- connections, secure remote **37**
- connectivity problems **13, 14, 16**
- consistency checks in VTP Version 2 **4**
- console port, connecting to **10**
- content-routing technology
 - See WCCP
- control protocol, IP SLAs **4**
- corrupted software, recovery steps with Xmodem **2**
- CoS
 - in Layer 2 frames **2**
 - override priority **6**
 - trust priority **6**
- CoS input queue threshold map for QoS **16**
- CoS output queue threshold map for QoS **18**
- CoS-to-DSCP map for QoS **60**
- counters, clearing interface **31**
- CPU utilization, troubleshooting **24**
- crashinfo file **23**
- critical authentication, IEEE 802.1x **43**
- cryptographic software image
 - Kerberos **32**
 - SSH **37**
 - SSL **41**
- customer edge devices **62**
- CWDM SFPs **22**

Ddaylight saving time [13](#)

debugging

 enabling all system diagnostics [20](#) enabling for a specific feature [19](#) redirecting error message output [20](#) using commands [19](#)default commands [4](#)

default configuration

 802.1x [25](#) auto-QoS [20](#) banners [17](#) BGP [42](#) booting [16](#) CDP [2](#) DHCP [8](#) DHCP option 82 [8](#) DHCP snooping [8](#) DHCP snooping binding database [8](#) DNS [16](#) dynamic ARP inspection [5](#) EIGRP [35](#) EtherChannel [9](#) Ethernet interfaces [15](#) fallback bridging [3](#) Flex Links [7, 8](#) HSRP [5](#) IEEE 802.1Q tunneling [4](#) IGMP [37](#) IGMP filtering [25](#) IGMP snooping [7, 5, 6](#) IGMP throttling [25](#) initial switch information [3](#) IP addressing, IP routing [4](#) IP multicast routing [10](#) IP SLAs [6](#) IP source guard [16](#) IPv6 [10](#)Layer 2 interfaces [15](#)Layer 2 protocol tunneling [11](#)LLDP [3](#)MAC address table [21](#)MAC address-table move update [8](#)MSDP [4](#)MSTP [14](#)multi-VRF CE [64](#)MVR [20](#)NTP [4](#)optional spanning-tree configuration [9](#)OSPF [25](#)password and privilege level [2](#)PIM [10](#)private VLANs [6](#)RADIUS [20](#)RIP [19](#)RMON [3](#)RSPAN [9](#)SDM template [3](#)SNMP [6](#)SPAN [9](#)SSL [44](#)standard QoS [30](#)STP [11](#)system message logging [3](#)system name and prompt [15](#)TACACS+ [13](#)UDLD [4](#)VLAN, Layer 2 Ethernet interfaces [19](#)VLANs [8](#)VMPS [29](#)voice VLAN [3](#)VTP [6](#)WCCP [5](#)default gateway [14, 11](#)default networks [79](#)

default router preference

See DRP

- default routes [79](#)
- default routing [2](#)
- deleting VLANs [10](#)
- denial-of-service attack [1](#)
- description command [25](#)
- designing your network, examples [17](#)
- destination addresses
 - in IPv4 ACLs [11](#)
 - in IPv6 ACLs [5](#)
- destination-IP address-based forwarding, EtherChannel [7](#)
- destination-MAC address forwarding, EtherChannel [7](#)
- detecting indirect link failures, STP [5](#)
- device [22](#)
- device discovery protocol [1](#)
- device manager
 - benefits [2](#)
 - described [2,5](#)
 - in-band management [6](#)
 - upgrading a switch [22](#)
- DHCP
 - Cisco IOS server database
 - configuring [14](#)
 - default configuration [8](#)
 - described [6](#)
 - DHCP for IPv6
 - See DHCPv6
 - enabling
 - relay agent [10](#)
 - server [10](#)
- DHCP-based autoconfiguration
 - client request message exchange [4](#)
 - configuring
 - client side [3](#)
 - DNS [7](#)
 - relay device [8](#)
 - server side [6](#)
 - server-side [10](#)
 - TFTP server [7](#)
 - example [9](#)
 - lease options
 - for IP address information [6](#)
 - for receiving the configuration file [6](#)
 - overview [3](#)
 - relationship to BOOTP [4](#)
 - relay support [5,13](#)
 - support for [5](#)
- DHCP-based autoconfiguration and image update
 - configuring [11 to 13](#)
 - understanding [5](#)
- DHCP binding database
 - See DHCP snooping binding database
- DHCP binding table
 - See DHCP snooping binding database
- DHCP object tracking, configuring primary interface [11](#)
- DHCP option 82
 - circuit ID suboption [5](#)
 - configuration guidelines [9](#)
 - default configuration [8](#)
 - displaying [15](#)
 - forwarding address, specifying [10](#)
 - helper address [10](#)
 - overview [3](#)
 - packet format, suboption
 - circuit ID [5](#)
 - remote ID [5](#)
 - remote ID suboption [5](#)
- DHCP server port-based address allocation
 - configuration guidelines [20](#)
 - default configuration [19](#)
 - described [19](#)
 - displaying [22](#)
 - enabling [20](#)
- DHCP server port-based address assignment
 - support for [5](#)
- DHCP snooping
 - accepting untrusted packets form edge switch [3,12](#)
 - and private VLANs [13](#)

- binding database
 - See DHCP snooping binding database
 - configuration guidelines [9](#)
 - default configuration [8](#)
 - displaying binding tables [15](#)
 - message exchange process [4](#)
 - option 82 data insertion [3](#)
 - trusted interface [2](#)
 - untrusted interface [2](#)
 - untrusted messages [2](#)
- DHCP snooping binding database
- adding bindings [14](#)
 - binding file
 - format [7](#)
 - location [6](#)
 - bindings [6](#)
 - clearing agent statistics [15](#)
 - configuration guidelines [9](#)
 - configuring [14](#)
 - default configuration [8](#)
 - deleting
 - binding file [14](#)
 - bindings [15](#)
 - database agent [14](#)
 - described [6](#)
 - displaying [15](#)
 - binding entries [15](#)
 - status and statistics [15](#)
 - enabling [14](#)
 - entry [6](#)
 - renewing database [15](#)
 - resetting
 - delay value [14](#)
 - timeout value [14](#)
- DHCP snooping binding table
- See DHCP snooping binding database
- DHCPv6
- configuration guidelines [14](#)
 - default configuration [14](#)
 - described [6](#)
 - enabling client function [17](#)
 - enabling DHCPv6 server function [15](#)
 - support for [13](#)
- Differentiated Services architecture, QoS [2](#)
- Differentiated Services Code Point [2](#)
- Diffusing Update Algorithm (DUAL) [33](#)
- directed unicast requests [5](#)
- directories
 - changing [3](#)
 - creating and removing [3](#)
 - displaying the working [3](#)
- discovery, clusters
- See automatic discovery
- Distance Vector Multicast Routing Protocol
- See DVMRP
- distance-vector protocols [3](#)
- distribute-list command [88](#)
- DNS
 - and DHCP-based autoconfiguration [7](#)
 - default configuration [16](#)
 - displaying the configuration [17](#)
 - in IPv6 [4](#)
 - overview [15](#)
 - setting up [16](#)
 - support for [5](#)
- DNS-based SSM mapping [18, 20](#)
- domain names
 - DNS [15](#)
 - VTP [8](#)
- Domain Name System
- See DNS
- dot1q-tunnel switchport mode [18](#)
- double-tagged packets
 - IEEE 802.1Q tunneling [2](#)
 - Layer 2 protocol tunneling [10](#)

- downloading
 - configuration files
 - preparing [9, 12, 15](#)
 - reasons for [7](#)
 - using FTP [12](#)
 - using RCP [16](#)
 - using TFTP [10](#)
 - image files
 - deleting old image [26](#)
 - preparing [24, 28, 32](#)
 - reasons for [22](#)
 - using CMS [3](#)
 - using FTP [29](#)
 - using HTTP [3, 22](#)
 - using RCP [33](#)
 - using TFTP [25](#)
 - using the device manager or Network Assistant [22](#)
- drop threshold for Layer 2 protocol packets [11](#)
- DRP
 - configuring [12](#)
 - described [4](#)
 - IPv6 [4](#)
 - support for [13](#)
- DSCP [11, 2](#)
- DSCP input queue threshold map for QoS [16](#)
- DSCP output queue threshold map for QoS [18](#)
- DSCP-to-CoS map for QoS [63](#)
- DSCP-to-DSCP-mutation map for QoS [64](#)
- DSCP transparency [40](#)
- DTP [8, 17](#)
- dual-action detection [5](#)
- DUAL finite state machine, EIGRP [34](#)
- dual IPv4 and IPv6 templates [2, 5, 6](#)
- dual protocol stacks
 - IPv4 and IPv6 [6](#)
 - SDM templates supporting [6](#)
- dual-purpose uplinks
 - defined [6](#)
 - LEDs [6](#)
 - link selection [6, 16](#)
 - setting the type [16](#)
- DVMRP
 - autosummarization
 - configuring a summary address [57](#)
 - disabling [59](#)
 - connecting PIM domain to DVMRP router [50](#)
 - enabling unicast routing [53](#)
 - interoperability
 - with Cisco devices [48](#)
 - with Cisco IOS software [9](#)
 - mrinfo requests, responding to [52](#)
 - neighbors
 - advertising the default route to [51](#)
 - discovery with Probe messages [48](#)
 - displaying information [52](#)
 - prevent peering with nonpruning [55](#)
 - rejecting nonpruning [54](#)
 - overview [8](#)
 - routes
 - adding a metric offset [59](#)
 - advertising all [59](#)
 - advertising the default route to neighbors [51](#)
 - caching DVMRP routes learned in report messages [53](#)
 - changing the threshold for syslog messages [56](#)
 - deleting [60](#)
 - displaying [61](#)
 - favoring one over another [59](#)
 - limiting the number injected into MBONE [56](#)
 - limiting unicast route advertisements [48](#)
 - routing table [9](#)
 - source distribution tree, building [9](#)
 - support for [13](#)

- tunnels
 - configuring [50](#)
 - displaying neighbor information [52](#)
- dynamic access ports
 - characteristics [3](#)
 - configuring [30](#)
 - defined [3](#)
- dynamic addresses
 - See addresses
- dynamic ARP inspection
 - ARP cache poisoning [1](#)
 - ARP requests, described [1](#)
 - ARP spoofing attack [1](#)
 - clearing
 - log buffer [14](#)
 - statistics [14](#)
 - configuration guidelines [6](#)
 - configuring
 - ACLs for non-DHCP environments [8](#)
 - in DHCP environments [7](#)
 - log buffer [12](#)
 - rate limit for incoming ARP packets [4, 10](#)
 - default configuration [5](#)
 - denial-of-service attacks, preventing [10](#)
 - described [1](#)
 - DHCP snooping binding database [2](#)
 - displaying
 - ARP ACLs [14](#)
 - configuration and operating state [14](#)
 - log buffer [14](#)
 - statistics [14](#)
 - trust state and rate limit [14](#)
 - error-disabled state for exceeding rate limit [4](#)
 - function of [2](#)
 - interface trust states [3](#)
 - log buffer
 - clearing [14](#)
 - configuring [12](#)
 - displaying [14](#)
 - logging of dropped packets, described [4](#)
 - man-in-the middle attack, described [2](#)
 - network security issues and interface trust states [3](#)
 - priority of ARP ACLs and DHCP snooping entries [4](#)
 - rate limiting of ARP packets
 - configuring [10](#)
 - described [4](#)
 - error-disabled state [4](#)
 - statistics
 - clearing [14](#)
 - displaying [14](#)
 - validation checks, performing [11](#)
 - dynamic auto trunking mode [18](#)
 - dynamic desirable trunking mode [18](#)
 - Dynamic Host Configuration Protocol
 - See DHCP-based autoconfiguration
 - dynamic port VLAN membership
 - described [28](#)
 - reconfirming [31](#)
 - troubleshooting [33](#)
 - types of connections [30](#)
 - dynamic routing [3](#)
 - Dynamic Trunking Protocol
 - See DTP

E

 - EBGP [41](#)
 - editing features
 - enabling and disabling [7](#)
 - keystrokes used [7](#)
 - wrapped lines [9](#)
 - EIGRP
 - authentication [38](#)
 - components [34](#)
 - configuring [36](#)
 - default configuration [35](#)
 - definition [33](#)
 - interface parameters, configuring [37](#)

- monitoring [40](#)
- stub routing [39](#)
- ELIN location [3](#)
- embedded event manager
 - actions [3](#)
 - configuring [1, 5](#)
 - displaying information [7](#)
 - environmental variables [4](#)
 - event detectors [2](#)
 - policies [4](#)
 - registering and defining an applet [5](#)
 - registering and defining a TCL script [6](#)
 - understanding [1](#)
- enable password [3](#)
- enable secret password [3](#)
- encryption, CipherSuite [43](#)
- encryption for passwords [3](#)
- Enhanced IGRP
 - See EIGRP
- enhanced object tracking
 - backup static routing [12](#)
 - commands [1](#)
 - defined [1](#)
 - DHCP primary interface [11](#)
 - HSRP [7](#)
 - IP routing state [2](#)
 - IP SLAs [9](#)
 - line-protocol state [2](#)
 - network monitoring with IP SLAs [11](#)
 - routing policy, configuring [12](#)
 - static route primary interface [10](#)
 - tracked lists [3](#)
- enhanced object tracking static routing [10](#)
- enhanced PoE [7](#)
- environmental variables, embedded event manager [4](#)
- environment variables, function of [19](#)
- equal-cost routing [12, 78](#)
- error-disabled state, BPDU [2](#)
- error messages during command entry [5](#)
- EtherChannel
 - automatic creation of [4, 5](#)
 - channel groups
 - binding physical and logical interfaces [3](#)
 - numbering of [3](#)
 - configuration guidelines [9](#)
 - configuring
 - Layer 2 interfaces [10](#)
 - Layer 3 physical interfaces [14](#)
 - Layer 3 port-channel logical interfaces [13](#)
 - default configuration [9](#)
 - described [2](#)
 - displaying status [20](#)
 - forwarding methods [7, 16](#)
 - IEEE 802.3ad, described [5](#)
 - interaction
 - with STP [10](#)
 - with VLANs [10](#)
- LACP
 - described [5](#)
 - displaying status [20](#)
 - hot-standby ports [18](#)
 - interaction with other features [6](#)
 - modes [6](#)
 - port priority [19](#)
 - system priority [19](#)
- Layer 3 interface [3](#)
- load balancing [7, 16](#)
- logical interfaces, described [3](#)
- PAgP
 - aggregate-port learners [16](#)
 - compatibility with Catalyst 1900 [17](#)
 - described [4](#)
 - displaying status [20](#)
 - interaction with other features [5](#)
 - interaction with virtual switches [5](#)
 - learn method and priority configuration [16](#)
 - modes [4](#)

- support for [3](#)
 - with dual-action detection [5](#)
- port-channel interfaces
 - described [3](#)
 - numbering of [3](#)
- port groups [6](#)
- support for [3](#)
- EtherChannel guard
 - described [7](#)
 - disabling [14](#)
 - enabling [14](#)
- Ethernet VLANs
 - adding [9](#)
 - defaults and ranges [8](#)
 - modifying [9](#)
- EUI [3](#)
- event detectors, embedded event manager [2](#)
- events, RMON [3](#)
- examples
 - network configuration [17](#)
- expedite queue for QoS [76](#)
- Express Setup [2](#)
 - See also getting started guide
- extended crashinfo file [23](#)
- extended-range VLANs
 - configuration guidelines [13](#)
 - configuring [12](#)
 - creating [13](#)
 - creating with an internal VLAN ID [15](#)
 - defined [1](#)
- extended system ID
 - MSTP [17](#)
 - STP [4, 14](#)
- extended universal identifier
 - See EUI
- Extensible Authentication Protocol over LAN [1](#)
- external BGP
 - See EBGp
- external neighbors, BGP [45](#)

F

- fa0 interface [6](#)
- fallback bridging
 - and protected ports [3](#)
- bridge groups
 - creating [3](#)
 - described [1](#)
 - displaying [10](#)
 - function of [2](#)
 - number supported [4](#)
 - removing [4](#)
- bridge table
 - clearing [10](#)
 - displaying [10](#)
- configuration guidelines [3](#)
- connecting interfaces with [10](#)
- default configuration [3](#)
- described [1](#)
- frame forwarding
 - flooding packets [2](#)
 - forwarding packets [2](#)
- overview [1](#)
- protocol, unsupported [3](#)
- STP
 - disabling on an interface [9](#)
 - forward-delay interval [8](#)
 - hello BPDU interval [8](#)
 - interface priority [6](#)
 - keepalive messages [2](#)
 - maximum-idle interval [9](#)
 - path cost [6](#)
 - VLAN-bridge spanning-tree priority [5](#)
 - VLAN-bridge STP [2](#)
- support for [12](#)
- SVIs and routed ports [1](#)
- unsupported protocols [3](#)
- VLAN-bridge STP [10](#)
- Fast Convergence [3](#)

- features, incompatible 12
 - FIB 76
 - fiber-optic, detecting unidirectional links 1
 - files
 - basic crashinfo
 - description 23
 - location 23
 - copying 4
 - crashinfo, description 23
 - deleting 4
 - displaying the contents of 7
 - extended crashinfo
 - description 23
 - location 23
 - tar
 - creating 5
 - displaying the contents of 5
 - extracting 6
 - image file format 23
 - file system
 - displaying available file systems 2
 - displaying file information 2
 - local file system names 1
 - network file system names 4
 - setting the default 2
 - filtering
 - in a VLAN 28
 - IPv6 traffic 4, 7
 - non-IP traffic 26
 - show and more command output 10
 - filtering show and more command output 10
 - filters, IP
 - See ACLs, IP
 - flash device, number of 1
 - Flex Link Multicast Fast Convergence 3
 - Flex Links
 - configuration guidelines 8
 - configuring 8, 9
 - configuring preferred VLAN 11
 - configuring VLAN load balancing 10
 - default configuration 7
 - description 1
 - link load balancing 2
 - monitoring 14
 - VLANs 2
 - flooded traffic, blocking 8
 - flow-based packet classification 11
 - flowcharts
 - QoS classification 6
 - QoS egress queueing and scheduling 17
 - QoS ingress queueing and scheduling 15
 - QoS policing and marking 10
 - flowcontrol
 - configuring 20
 - described 20
 - forward-delay time
 - MSTP 23
 - STP 21
 - Forwarding Information Base
 - See FIB
 - forwarding nonroutable protocols 1
 - FTP
 - accessing MIB files 3
 - configuration files
 - downloading 12
 - overview 11
 - preparing the server 12
 - uploading 13
 - image files
 - deleting old image 30
 - downloading 29
 - preparing the server 28
 - uploading 30
-
- G**
 - general query 5
 - Generating IGMP Reports 3

get-bulk-request operation [3](#)
 get-next-request operation [3, 4](#)
 get-request operation [3, 4](#)
 get-response operation [3](#)
 global configuration mode [2](#)
 global leave, IGMP [13](#)
 guest VLAN and 802.1x [12](#)
 guide mode [3](#)
 GUIs
 See device manager and Network Assistant

H

hardware limitations and Layer 3 interfaces [27](#)
 hello time
 MSTP [22](#)
 STP [20](#)
 help, for the command line [3](#)
 hierarchical policy maps [8](#)
 configuration guidelines [33](#)
 configuring [52](#)
 described [11](#)
 history
 changing the buffer size [6](#)
 described [6](#)
 disabling [7](#)
 recalling commands [6](#)
 history table, level and number of syslog messages [10](#)
 host names, in clusters [13](#)
 host ports
 configuring [11](#)
 kinds of [2](#)
 hosts, limit on dynamic ports [33](#)
 Hot Standby Router Protocol
 See HSRP
 HP OpenView [5](#)

HSRP
 authentication string [10](#)
 automatic cluster recovery [12](#)
 binding to cluster group [12](#)
 cluster standby group considerations [11](#)
 command-switch redundancy [1, 7](#)
 configuring [4](#)
 default configuration [5](#)
 definition [1](#)
 guidelines [5](#)
 monitoring [13](#)
 object tracking [7](#)
 overview [1](#)
 priority [7](#)
 routing redundancy [12](#)
 support for ICMP redirect messages [12](#)
 timers [10](#)
 tracking [8](#)
 See also clusters, cluster standby group, and standby command switch
 HSRP for IPv6
 configuring [25](#)
 guidelines [24](#)
 HTTP over SSL
 see HTTPS
 HTTPS [42](#)
 configuring [45](#)
 self-signed certificate [42](#)
 HTTP secure server [42](#)

I

IBPG [41](#)
 ICMP
 IPv6 [4](#)
 redirect messages [11](#)
 support for [12](#)
 time-exceeded messages [16](#)
 traceroute and [16](#)

- unreachable messages [19](#)
- unreachable messages and IPv6 [4](#)
- unreachables and ACLs [21](#)
- ICMP Echo operation
 - configuring [12](#)
 - IP SLAs [11](#)
- ICMP ping
 - executing [13](#)
 - overview [13](#)
- ICMP Router Discovery Protocol
 - See IRDP
- ICMPv6 [4](#)
- IDS appliances
 - and ingress RSPAN [20](#)
 - and ingress SPAN [13](#)
- IEEE 802.1D
 - See STP
- IEEE 802.1p [1](#)
- IEEE 802.1Q
 - and trunk ports [3](#)
 - configuration limitations [19](#)
 - encapsulation [16](#)
 - native VLAN for untagged traffic [23](#)
 - tunneling
 - compatibility with other features [6](#)
 - defaults [4](#)
 - described [1](#)
 - tunnel ports with other features [6](#)
- IEEE 802.1s
 - See MSTP
- IEEE 802.1w
 - See RSTP
- IEEE 802.1x
 - See port-based authentication
- IEEE 802.3ad
 - See EtherChannel
- IEEE 802.3af
 - See PoE
- IEEE 802.3x flow control [20](#)
- ifIndex values, SNMP [5](#)
- IFS [6](#)
- IGMP
 - configurable leave timer
 - described [6](#)
 - enabling [11](#)
 - configuring the switch
 - as a member of a group [38](#)
 - statically connected member [42](#)
 - controlling access to groups [39](#)
 - default configuration [37](#)
 - deleting cache entries [61](#)
 - displaying groups [61](#)
 - fast switching [42](#)
 - flooded multicast traffic
 - controlling the length of time [12](#)
 - disabling on an interface [13](#)
 - global leave [13](#)
 - query solicitation [13](#)
 - recovering from flood mode [13](#)
 - host-query interval, modifying [40](#)
 - joining multicast group [3](#)
 - join messages [3](#)
 - leave processing, enabling [11, 8](#)
 - leaving multicast group [5](#)
 - multicast reachability [38](#)
 - overview [3](#)
 - queries [4](#)
 - report suppression
 - described [6](#)
 - disabling [16, 11](#)
 - supported versions [3](#)
 - support for [4](#)
 - Version 1
 - changing to Version 2 [40](#)
 - described [3](#)
 - Version 2
 - changing to Version 1 [40](#)
 - described [3](#)

- maximum query response time value [42](#)
 - pruning groups [42](#)
 - query timeout value [41](#)
- IGMP filtering
 - configuring [25](#)
 - default configuration [25](#)
 - described [24](#)
 - monitoring [29](#)
 - support for [4](#)
- IGMP groups
 - configuring filtering [28](#)
 - setting the maximum number [27](#)
- IGMP helper [4, 6](#)
- IGMP Immediate Leave
 - configuration guidelines [11](#)
 - described [5](#)
 - enabling [11](#)
- IGMP profile
 - applying [27](#)
 - configuration mode [25](#)
 - configuring [26](#)
- IGMP snooping
 - and address aliasing [2](#)
 - configuring [7](#)
 - default configuration [7, 5, 6](#)
 - definition [2](#)
 - enabling and disabling [7, 6](#)
 - global configuration [7](#)
 - Immediate Leave [5](#)
 - method [8](#)
 - monitoring [16, 11](#)
 - querier
 - configuration guidelines [14](#)
 - configuring [14](#)
 - supported versions [3](#)
 - support for [4](#)
 - VLAN configuration [8](#)
- IGMP throttling
 - configuring [28](#)
 - default configuration [25](#)
 - described [25](#)
 - displaying action [29](#)
- IGP [24](#)
- Immediate Leave, IGMP [5](#)
 - enabling [8](#)
- inaccessible authentication bypass [14](#)
- initial configuration
 - defaults [14](#)
 - Express Setup [2](#)
- interface
 - number [11](#)
 - range macros [13](#)
- interface command [11](#)
- interface configuration mode [3](#)
- interfaces
 - auto-MDIX, configuring [21](#)
 - configuration guidelines
 - duplex and speed [18](#)
 - configuring
 - procedure [11](#)
 - counters, clearing [31](#)
 - default configuration [15](#)
 - described [25](#)
 - descriptive name, adding [25](#)
 - displaying information about [30](#)
 - flow control [20](#)
 - management [5](#)
 - monitoring [30](#)
 - naming [25](#)
 - physical, identifying [10, 11](#)
 - range of [12](#)
 - restarting [32](#)
 - shutting down [32](#)
 - speed and duplex, configuring [18](#)
 - status [30](#)

- supported **10**
- types of **1**
- interfaces range macro command **13**
- interface types **11**
- Interior Gateway Protocol
 - See IGP
- internal BGP
 - See IBGP
- internal neighbors, BGP **45**
- Internet Control Message Protocol
 - See ICMP
- Internet Group Management Protocol
 - See IGMP
- Internet Protocol version 6
 - See IPv6
- Inter-Switch Link
 - See ISL
- inter-VLAN routing **12, 2**
- Intrusion Detection System
 - See IDS appliances
- inventory management TLV **2, 6**
- IP ACLs
 - for QoS classification **7**
 - implicit deny **9, 13**
 - implicit masks **9**
 - named **14**
 - undefined **20**
- IP addresses
 - 128-bit **2**
 - candidate or member **3, 13**
 - classes of **5**
 - cluster access **2**
 - command switch **3, 11, 13**
 - default configuration **4**
 - discovering **27**
 - for IP routing **4**
 - IPv6 **2**
 - MAC address association **8**
 - monitoring **17**
 - redundant clusters **11**
 - standby command switch **11, 13**
 - See also IP information
- IP base image **1**
- IP broadcast address **15**
- ip cef distributed command **77**
- IP directed broadcasts **13**
- ip igmp profile command **25**
- IP information
 - assigned
 - manually **14**
 - through DHCP-based autoconfiguration **3**
 - default configuration **3**
- IP multicast routing
 - addresses
 - all-hosts **3**
 - all-multicast-routers **3**
 - host group address range **3**
 - administratively-scoped boundaries, described **45**
 - and IGMP snooping **2**
 - Auto-RP
 - adding to an existing sparse-mode cloud **25**
 - benefits of **25**
 - clearing the cache **61**
 - configuration guidelines **11**
 - filtering incoming RP announcement messages **28**
 - overview **6**
 - preventing candidate RP spoofing **28**
 - preventing join messages to false RPs **27**
 - setting up in a new internetwork **25**
 - using with BSR **33**
 - bootstrap router
 - configuration guidelines **11**
 - configuring candidate BSRs **31**
 - configuring candidate RPs **32**
 - defining the IP multicast boundary **30**
 - defining the PIM domain border **29**

- overview [7](#)
- using with Auto-RP [33](#)
- Cisco implementation [2](#)
- configuring
 - basic multicast routing [11](#)
 - IP multicast boundary [45](#)
- default configuration [10](#)
- enabling
 - multicast forwarding [12](#)
 - PIM mode [13](#)
- group-to-RP mappings
 - Auto-RP [6](#)
 - BSR [7](#)
- MBONE
 - deleting sdr cache entries [61](#)
 - described [44](#)
 - displaying sdr cache [62](#)
 - enabling sdr listener support [45](#)
 - limiting DVMRP routes advertised [56](#)
 - limiting sdr cache entry lifetime [45](#)
 - SAP packets for conference session announcement [44](#)
 - Session Directory (sdr) tool, described [44](#)
- monitoring
 - packet rate loss [62](#)
 - peering devices [62](#)
 - tracing a path [62](#)
- multicast forwarding, described [7](#)
- PIMv1 and PIMv2 interoperability [10](#)
- protocol interaction [2](#)
- reverse path check (RPF) [7](#)
- routing table
 - deleting [61](#)
 - displaying [61](#)
- RP
 - assigning manually [23](#)
 - configuring Auto-RP [25](#)
 - configuring PIMv2 BSR [29](#)
 - monitoring mapping information [33](#)
 - using Auto-RP and BSR [33](#)
 - statistics, displaying system and network [61](#)
 - See also CGMP
 - See also DVMRP
 - See also IGMP
 - See also PIM
- IP phones
 - and QoS [1](#)
 - automatic classification and queueing [20](#)
 - configuring [4](#)
 - ensuring port security with QoS [38](#)
 - trusted boundary for QoS [38](#)
- IP precedence [2](#)
- IP-precedence-to-DSCP map for QoS [61](#)
- IP protocols
 - in ACLs [11](#)
 - routing [12](#)
- IP routes, monitoring [90](#)
- IP routing
 - connecting interfaces with [10](#)
 - disabling [18](#)
 - enabling [18](#)
- IP Service Level Agreements
 - See IP SLAs
- IP service levels, analyzing [1](#)
- IP services image [1](#)
- IP SLAs
 - benefits [2](#)
 - configuration guidelines [6](#)
 - configuring object tracking [9](#)
 - Control Protocol [4](#)
 - default configuration [6](#)
 - definition [1](#)
 - ICMP echo operation [11](#)
 - measuring network performance [3](#)
 - monitoring [13](#)
 - multioperations scheduling [5](#)
 - object tracking [9](#)

- operation [3](#)
- reachability tracking [9](#)
- responder
 - described [4](#)
 - enabling [8](#)
- response time [4](#)
- scheduling [5](#)
- SNMP support [2](#)
- supported metrics [2](#)
- threshold monitoring [6](#)
- track object monitoring agent, configuring [11](#)
- track state [9](#)
- UDP jitter operation [8](#)
- IP source guard
 - and 802.1x [17](#)
 - and DHCP snooping [15](#)
 - and EtherChannels [17](#)
 - and port security [17](#)
 - and private VLANs [17](#)
 - and routed ports [17](#)
 - and TCAM entries [17](#)
 - and trunk interfaces [17](#)
 - and VRF [17](#)
 - binding configuration
 - automatic [15](#)
 - manual [15](#)
 - binding table [15](#)
 - configuration guidelines [17](#)
 - default configuration [16](#)
 - described [15](#)
 - disabling [18](#)
 - displaying
 - bindings [19](#)
 - configuration [19](#)
 - enabling [17](#)
 - filtering
 - source IP address [16](#)
 - source IP and MAC address [16](#)
 - source IP address filtering [16](#)
 - source IP and MAC address filtering [16](#)
 - static bindings
 - adding [17](#)
 - deleting [18](#)
- IP traceroute
 - executing [17](#)
 - overview [16](#)
- IP unicast routing
 - address resolution [8](#)
 - administrative distances [79, 89](#)
 - ARP [8](#)
 - assigning IP addresses to Layer 3 interfaces [5](#)
 - authentication keys [89](#)
 - broadcast
 - address [15](#)
 - flooding [16](#)
 - packets [13](#)
 - storms [13](#)
 - classless routing [6](#)
 - configuring static routes [78](#)
 - default
 - addressing configuration [4](#)
 - gateways [11](#)
 - networks [79](#)
 - routes [79](#)
 - routing [2](#)
 - directed broadcasts [13](#)
 - disabling [18](#)
 - dynamic routing [3](#)
 - enabling [18](#)
 - EtherChannel Layer 3 interface [3](#)
 - IGP [24](#)
 - inter-VLAN [2](#)
 - IP addressing
 - classes [5](#)
 - configuring [4](#)
 - IPv6 [3](#)
 - IRDP [11](#)
 - Layer 3 interfaces [3](#)

- MAC address and IP address [8](#)
- passive interfaces [87](#)
- protocols
 - distance-vector [3](#)
 - dynamic [3](#)
 - link-state [3](#)
- proxy ARP [8](#)
- redistribution [80](#)
- reverse address resolution [8](#)
- routed ports [3](#)
- static routing [3](#)
- steps to configure [4](#)
- subnet mask [5](#)
- subnet zero [6](#)
- supernet [6](#)
- UDP [14](#)
- with SVIs [3](#)
- See also BGP
- See also EIGRP
- See also OSPF
- See also RIP
- IPv4 ACLs
 - applying to interfaces [19](#)
 - extended, creating [10](#)
 - named [14](#)
 - standard, creating [9](#)
- IPv4 and IPv6
 - dual protocol stacks [5](#)
- IPv6
 - ACLs
 - displaying [8](#)
 - limitations [3](#)
 - matching criteria [3](#)
 - port [2](#)
 - precedence [2](#)
 - router [2](#)
 - supported [2](#)
 - addresses [2](#)
 - address formats [2](#)
 - applications [5](#)
 - assigning address [10](#)
 - autoconfiguration [5](#)
 - CEFv6 [19](#)
 - configuring static routes [20](#)
 - default configuration [10](#)
 - default router preference (DRP) [4](#)
 - defined [1](#)
 - Enhanced Interior Gateway Routing Protocol (EIGRP) IPv6 [7](#)
 - EIGRP IPv6 Commands [7](#)
 - Router ID [7](#)
 - feature limitations [8](#)
 - features not supported [8](#)
 - forwarding [10](#)
 - ICMP [4](#)
 - monitoring [27](#)
 - neighbor discovery [4](#)
 - OSPF [6](#)
 - path MTU discovery [4](#)
 - SDM templates [2,1](#)
 - Stateless Autoconfiguration [5](#)
 - supported features [2](#)
 - switch limitations [8](#)
 - understanding static routes [6](#)
- IPv6 traffic, filtering [4](#)
- IRDP
 - configuring [12](#)
 - definition [11](#)
 - support for [12](#)
- ISL
 - and IPv6 [3](#)
 - and trunk ports [3](#)
 - encapsulation [8,16](#)
 - trunking with IEEE 802.1 tunneling [5](#)
- isolated port [2](#)
- isolated VLANs [2,3](#)

J

join messages, IGMP [3](#)

K**KDC**

described [32](#)

See also Kerberos

keepalive messages [2](#)

Kerberos

authenticating to

boundary switch [34](#)

KDC [34](#)

network services [35](#)

configuration examples [32](#)

configuring [35](#)

credentials [32](#)

cryptographic software image [32](#)

described [32](#)

KDC [32](#)

operation [34](#)

realm [33](#)

server [33](#)

support for [10](#)

switch as trusted third party [32](#)

terms [33](#)

TGT [34](#)

tickets [32](#)

key distribution center

See KDC

L

l2protocol-tunnel command [13](#)

LACP

Layer 2 protocol tunneling [9](#)

See EtherChannel

LAN base image [1](#)

Layer 2 frames, classification with CoS [2](#)

Layer 2 interfaces, default configuration [15](#)

Layer 2 protocol tunneling

configuring [10](#)

configuring for EtherChannels [14](#)

default configuration [11](#)

defined [8](#)

guidelines [11](#)

Layer 2 traceroute

and ARP [15](#)

and CDP [15](#)

broadcast traffic [15](#)

described [15](#)

IP addresses and subnets [15](#)

MAC addresses and VLANs [15](#)

multicast traffic [15](#)

multiple devices on a port [16](#)

unicast traffic [15](#)

usage guidelines [15](#)

Layer 3 features [12](#)

Layer 3 interfaces

assigning IP addresses to [5](#)

assigning IPv4 and IPv6 addresses to [13](#)

assigning IPv6 addresses to [11](#)

changing from Layer 2 mode [5, 68, 69](#)

types of [3](#)

Layer 3 packets, classification methods [2](#)

LDAP [2](#)

Leaking IGMP Reports [4](#)

LEDs, switch

See hardware installation guide

lightweight directory access protocol

See LDAP

line configuration mode [3](#)

Link Aggregation Control Protocol

See EtherChannel

link failure, detecting unidirectional [7](#)

Link Layer Discovery Protocol

See CDP

- link local unicast addresses [3](#)
 - link redundancy
 - See Flex Links
 - links, unidirectional [1](#)
 - link state advertisements (LSAs) [28](#)
 - link-state protocols [3](#)
 - link-state tracking
 - configuring [23](#)
 - described [21](#)
 - LLDP
 - configuring [3](#)
 - characteristics [4](#)
 - default configuration [3](#)
 - disabling and enabling
 - globally [4](#)
 - on an interface [5](#)
 - monitoring and maintaining [7](#)
 - overview [1](#)
 - supported TLVs [2](#)
 - switch stack considerations [2](#)
 - transmission timer and holdtime, setting [4](#)
 - LLDP-MED
 - configuring
 - procedures [3](#)
 - TLVs [6](#)
 - monitoring and maintaining [7](#)
 - overview [1,2](#)
 - supported TLVs [2](#)
 - LLDP Media Endpoint Discovery
 - See LLDP-MED
 - load balancing [4](#)
 - local SPAN [2](#)
 - location TLV [3,6](#)
 - logging messages, ACL [8](#)
 - login authentication
 - with RADIUS [23](#)
 - with TACACS+ [14](#)
 - login banners [17](#)
 - log messages
 - See system message logging
 - Long-Reach Ethernet (LRE) technology [18](#)
 - loop guard
 - described [9](#)
 - enabling [15](#)
 - support for [7](#)
 - LRE profiles, considerations in switch clusters [14](#)
-
- ## M
- MAB aging timer [8](#)
 - MAB inactivity timer
 - default setting [25](#)
 - range [28](#)
 - MAC/PHY configuration status TLV [2](#)
 - MAC addresses
 - aging time [21](#)
 - and VLAN association [20](#)
 - building the address table [20](#)
 - default configuration [21](#)
 - disabling learning on a VLAN [26](#)
 - discovering [27](#)
 - displaying [27](#)
 - displaying in the IP source binding table [19](#)
 - dynamic
 - learning [20](#)
 - removing [22](#)
 - in ACLs [26](#)
 - IP address association [8](#)
 - static
 - adding [24](#)
 - allowing [26,27](#)
 - characteristics of [24](#)
 - dropping [25](#)
 - removing [24](#)
 - MAC address learning [6](#)
 - MAC address learning, disabling on a VLAN [26](#)
 - MAC address notification, support for [13](#)

- MAC address-table move update
 - configuration guidelines [8](#)
 - configuring [12](#)
 - default configuration [8](#)
 - description [6](#)
 - monitoring [14](#)
- MAC address-to-VLAN mapping [28](#)
- MAC authentication bypass [10](#)
 - See MAB
- MAC extended access lists
 - applying to Layer 2 interfaces [27](#)
 - configuring for QoS [45](#)
 - creating [26](#)
 - defined [26](#)
 - for QoS classification [5](#)
- macros
 - See Smartports macros
- magic packet [17](#)
- manageability features [5](#)
- management access
 - in-band
 - browser session [6](#)
 - CLI session [6](#)
 - device manager [6](#)
 - SNMP [6](#)
 - out-of-band console port connection [6](#)
- management address TLV [2](#)
- management options
 - CLI [1](#)
 - clustering [3](#)
 - CNS [1](#)
 - Network Assistant [2](#)
 - overview [5](#)
- management VLAN
 - considerations in switch clusters [7](#)
 - discovery through different management VLANs [7](#)
- mapping tables for QoS
 - configuring
 - CoS-to-DSCP [60](#)
 - DSCP [60](#)
 - DSCP-to-CoS [63](#)
 - DSCP-to-DSCP-mutation [64](#)
 - IP-precedence-to-DSCP [61](#)
 - policed-DSCP [62](#)
 - described [12](#)
- marking
 - action with aggregate policers [58](#)
 - described [4, 8](#)
- matching
 - IPv6 ACLs [3](#)
- matching, IPv4 ACLs [7](#)
- maximum aging time
 - MSTP [23](#)
 - STP [21](#)
- maximum hop count, MSTP [24](#)
- maximum number of allowed devices, port-based authentication [28](#)
- maximum-paths command [49, 78](#)
- MDA
 - configuration guidelines [19 to 20](#)
 - described [9, 19](#)
 - exceptions with authentication process [4](#)
- membership mode, VLAN port [3](#)
- member switch
 - automatic discovery [4](#)
 - defined [2](#)
 - managing [14](#)
 - passwords [13](#)
 - recovering from lost connectivity [11](#)
 - requirements [3](#)
 - See also candidate switch, cluster standby group, and standby command switch
- messages, to users through banners [17](#)
- metrics, in BGP [49](#)
- metric translations, between routing protocols [83](#)

- metro tags [2](#)
- MHSRP [4](#)
- MIBs
 - accessing files with FTP [3](#)
 - location of files [3](#)
 - overview [1](#)
 - SNMP interaction with [4](#)
 - supported [1](#)
- mirroring traffic for analysis [1](#)
- mismatches, autonegotiation [11](#)
- module number [11](#)
- monitoring
 - access groups [39](#)
 - BGP [60](#)
 - cables for unidirectional links [1](#)
 - CDP [4](#)
 - CEF [77](#)
 - EIGRP [40](#)
 - fallback bridging [10](#)
 - features [13](#)
 - Flex Links [14](#)
 - HSRP [13](#)
 - IEEE 802.1Q tunneling [17](#)
 - IGMP
 - filters [29](#)
 - snooping [16, 11](#)
 - interfaces [30](#)
 - IP
 - address tables [17](#)
 - multicast routing [60](#)
 - routes [90](#)
 - IP SLAs operations [13](#)
 - IPv4 ACL configuration [39](#)
 - IPv6 [27](#)
 - IPv6 ACL configuration [8](#)
 - Layer 2 protocol tunneling [17](#)
 - MAC address-table move update [14](#)
 - MSDP peers [18](#)
 - multicast router interfaces [17, 11](#)
 - multi-VRF CE [75](#)
 - MVR [24](#)
 - network traffic for analysis with probe [2](#)
 - object tracking [12](#)
 - OSPF [32](#)
 - port
 - blocking [19](#)
 - protection [19](#)
 - private VLANs [14](#)
 - RP mapping information [33](#)
 - SFP status [31, 13](#)
 - source-active messages [18](#)
 - speed and duplex mode [19](#)
 - SSM mapping [21](#)
 - traffic flowing among switches [1](#)
 - traffic suppression [19](#)
 - tunneling [17](#)
 - VLAN
 - filters [40](#)
 - maps [40](#)
 - VLANs [16](#)
 - VMPS [32](#)
 - VTP [16](#)
 - mrouter Port [3](#)
 - mrouter port [5](#)
 - MSDP
 - benefits of [3](#)
 - clearing MSDP connections and statistics [18](#)
 - controlling source information
 - forwarded by switch [11](#)
 - originated by switch [8](#)
 - received by switch [13](#)
 - default configuration [4](#)
 - dense-mode regions
 - sending SA messages to [16](#)
 - specifying the originating address [17](#)

- filtering
 - incoming SA messages [14](#)
 - SA messages to a peer [12](#)
 - SA requests from a peer [10](#)
- join latency, defined [6](#)
- meshed groups
 - configuring [15](#)
 - defined [15](#)
- originating address, changing [17](#)
- overview [1](#)
- peer-RPF flooding [2](#)
- peers
 - configuring a default [4](#)
 - monitoring [18](#)
 - peering relationship, overview [1](#)
 - requesting source information from [8](#)
 - shutting down [15](#)
- source-active messages
 - caching [6](#)
 - clearing cache entries [18](#)
 - defined [2](#)
 - filtering from a peer [10](#)
 - filtering incoming [14](#)
 - filtering to a peer [12](#)
 - limiting data with TTL [13](#)
 - monitoring [18](#)
 - restricting advertised sources [9](#)
- support for [12](#)
- MSTP
 - boundary ports
 - configuration guidelines [15](#)
 - described [6](#)
 - BPDU filtering
 - described [3](#)
 - enabling [12](#)
 - BPDU guard
 - described [2](#)
 - enabling [11](#)
 - CIST, described [3](#)
 - CIST regional root [3](#)
 - CIST root [5](#)
 - configuration guidelines [14, 10](#)
 - configuring
 - forward-delay time [23](#)
 - hello time [22](#)
 - link type for rapid convergence [24](#)
 - maximum aging time [23](#)
 - maximum hop count [24](#)
 - MST region [15](#)
 - neighbor type [25](#)
 - path cost [20](#)
 - port priority [19](#)
 - root switch [17](#)
 - secondary root switch [18](#)
 - switch priority [21](#)
 - CST
 - defined [3](#)
 - operations between regions [3](#)
 - default configuration [14](#)
 - default optional feature configuration [9](#)
 - displaying status [26](#)
 - enabling the mode [15](#)
 - EtherChannel guard
 - described [7](#)
 - enabling [14](#)
 - extended system ID
 - effects on root switch [17](#)
 - effects on secondary root switch [18](#)
 - unexpected behavior [17](#)
 - IEEE 802.1s
 - implementation [6](#)
 - port role naming change [6](#)
 - terminology [5](#)
 - instances supported [9](#)
 - interface state, blocking to forwarding [2](#)
 - interoperability and compatibility among modes [10](#)

- interoperability with IEEE 802.1D
 - described [8](#)
 - restarting migration process [25](#)
- IST
 - defined [2](#)
 - master [3](#)
 - operations within a region [3](#)
- loop guard
 - described [9](#)
 - enabling [15](#)
- mapping VLANs to MST instance [16](#)
- MST region
 - CIST [3](#)
 - configuring [15](#)
 - described [2](#)
 - hop-count mechanism [5](#)
 - IST [2](#)
 - supported spanning-tree instances [2](#)
- optional features supported [7](#)
- overview [2](#)
- Port Fast
 - described [2](#)
 - enabling [10](#)
- preventing root switch selection [8](#)
- root guard
 - described [8](#)
 - enabling [15](#)
- root switch
 - configuring [17](#)
 - effects of extended system ID [17](#)
 - unexpected behavior [17](#)
- shutdown Port Fast-enabled port [2](#)
- status, displaying [26](#)
- multicast groups
 - Immediate Leave [5](#)
 - joining [3](#)
 - leaving [5](#)
 - static joins [10, 7](#)
- multicast packets
 - ACLs on [39](#)
 - blocking [8](#)
- multicast router interfaces, monitoring [17, 11](#)
- multicast router ports, adding [9, 8](#)
- Multicast Source Discovery Protocol
 - See MSDP
- multicast storm [1](#)
- multicast storm-control command [4](#)
- multicast television application [18](#)
- multicast VLAN [17](#)
- Multicast VLAN Registration
 - See MVR
- multidomain authentication
 - See MDA
- multioperations scheduling, IP SLAs [5](#)
- Multiple HSRP
 - See MHSRP
- multiple VPN routing/forwarding in customer edge devices
 - See multi-VRF CE
- multi-VRF CE
 - configuration example [72](#)
 - configuration guidelines [64](#)
 - configuring [64](#)
 - default configuration [64](#)
 - defined [61](#)
 - displaying [75](#)
 - monitoring [75](#)
 - network components [64](#)
 - packet-forwarding process [63](#)
 - support for [12](#)
- MVR
 - and address aliasing [21](#)
 - and IGMPv3 [21](#)
 - configuration guidelines [20](#)
 - configuring interfaces [22](#)
 - default configuration [20](#)
 - described [17](#)

- example application [18](#)
- modes [21](#)
- monitoring [24](#)
- multicast television application [18](#)
- setting global parameters [21](#)
- support for [4](#)

N

NAC

- AAA down policy [10](#)
- critical authentication [14, 43](#)
- IEEE 802.1x authentication using a RADIUS server [47](#)
- IEEE 802.1x validation using RADIUS server [47](#)
- inaccessible authentication bypass [10, 43](#)
- Layer 2 IEEE 802.1x validation [10, 19, 47](#)
- Layer 2 IP validation [10](#)

named IPv4 ACLs [14](#)

NameSpace Mapper

See NSM

native VLAN

- and IEEE 802.1Q tunneling [4](#)
- configuring [23](#)
- default [23](#)

neighbor discovery, IPv6 [4](#)

neighbor discovery/recovery, EIGRP [34](#)

neighbors, BGP [55](#)

Network Admission Control

NAC

Network Admission Control Software Configuration Guide [49, 50](#)

Network Assistant

- benefits [2](#)
- described [5](#)
- downloading image files [3](#)
- guide mode [3](#)
- management options [2](#)

upgrading a switch [22](#)

wizards [3](#)

network configuration examples

- increasing network performance [17](#)
- large network [21](#)
- long-distance, high-bandwidth transport [22](#)
- providing network services [17](#)
- server aggregation and Linux server cluster [19](#)
- small to medium-sized network [20](#)

network design

- performance [17](#)
- services [17](#)

network management

- CDP [1](#)
- RMON [1](#)
- SNMP [1](#)

network performance, measuring with IP SLAs [3](#)

network policy TLV [2, 6](#)

Network Time Protocol

See NTP

no commands [4](#)

nonhierarchical policy maps

- configuration guidelines [33](#)
- described [9](#)

non-IP traffic filtering [26](#)

nontrunking mode [18](#)

normal-range VLANs [4](#)

- configuration guidelines [6](#)
- configuration modes [7](#)
- configuring [4](#)
- defined [1](#)

no switchport command [4](#)

not-so-stubby areas

See NSSA

NSM [3](#)

NSSA, OSPF [28](#)

NTP

- associations
 - authenticating [4](#)
 - defined [2](#)
 - enabling broadcast messages [6](#)
 - peer [5](#)
 - server [5](#)
- default configuration [4](#)
- displaying the configuration [11](#)
- overview [2](#)
- restricting access
 - creating an access group [8](#)
 - disabling NTP services per interface [10](#)
- source IP address, configuring [10](#)
- stratum [2](#)
- support for [6](#)
- synchronizing devices [5](#)
- time
 - services [2](#)
 - synchronizing [2](#)

O

- object tracking
 - HSRP [7](#)
 - IP SLAs [9](#)
 - IP SLAs, configuring [9](#)
 - monitoring [12](#)
- online diagnostics
 - overview [1](#)
 - running tests [3](#)
 - understanding [1](#)
- Open Shortest Path First
 - See OSPF
- optimizing system resources [1](#)
- options, management [5](#)

OSPF

- area parameters, configuring [28](#)
- configuring [26](#)
- default configuration
 - metrics [30](#)
 - route [30](#)
 - settings [25](#)
- described [24](#)
- for IPv6 [6](#)
- interface parameters, configuring [27](#)
- LSA group pacing [31](#)
- monitoring [32](#)
- router IDs [32](#)
- route summarization [30](#)
- support for [12](#)
- virtual links [30](#)
- out-of-profile markdown [11](#)

P

- packet modification, with QoS [19](#)
- PAgP
 - Layer 2 protocol tunneling [9](#)
 - See EtherChannel
- parallel paths, in routing tables [78](#)
- passive interfaces
 - configuring [87](#)
 - OSPF [30](#)
- passwords
 - default configuration [2](#)
 - disabling recovery of [5](#)
 - encrypting [3](#)
 - for security [8](#)
 - in clusters [13](#)
 - overview [1](#)
 - recovery of [3](#)
 - setting
 - enable [3](#)
 - enable secret [3](#)

- Telnet [6](#)
 - with usernames [6](#)
- VTP domain [8](#)
- path cost
 - MSTP [20](#)
 - STP [18](#)
- path MTU discovery [4](#)
- PBR
 - defined [84](#)
 - enabling [85](#)
 - fast-switched policy-based routing [87](#)
 - local policy-based routing [87](#)
- PC (passive command switch) [10](#)
- peers, BGP [55](#)
- percentage thresholds in tracked lists [6](#)
- performance, network design [17](#)
- performance features [3](#)
- persistent self-signed certificate [42](#)
- per-VLAN spanning-tree plus
 - See PVST+
- PE to CE routing, configuring [71](#)
- physical ports [2](#)
- PIM
 - default configuration [10](#)
 - dense mode
 - overview [4](#)
 - rendezvous point (RP), described [5](#)
 - RPF lookups [8](#)
 - displaying neighbors [61](#)
 - enabling a mode [13](#)
 - overview [4](#)
 - router-query message interval, modifying [36](#)
 - shared tree and source tree, overview [34](#)
 - shortest path tree, delaying the use of [35](#)
 - sparse mode
 - join messages and shared tree [5](#)
 - overview [5](#)
 - prune messages [5](#)
 - RPF lookups [8](#)
 - stub routing
 - configuration guidelines [22](#)
 - displaying [61](#)
 - enabling [22](#)
 - overview [5](#)
 - support for [12](#)
 - versions
 - interoperability [10](#)
 - troubleshooting interoperability problems [34](#)
 - v2 improvements [4](#)
- PIM-DVMRP, as snooping method [8](#)
- ping
 - character output description [14](#)
 - executing [13](#)
 - overview [13](#)
- PoE
 - auto mode [8](#)
 - CDP with power consumption, described [7](#)
 - CDP with power negotiation, described [7](#)
 - Cisco intelligent power management [7](#)
 - configuring [22](#)
 - devices supported [6](#)
 - enhanced [7](#)
 - supported watts per port [7](#)
 - high-power devices operating in low-power mode [7](#)
 - IEEE power classification levels [8](#)
 - monitoring power [24](#)
 - policing power consumption [24](#)
 - power budgeting [23](#)
 - power consumption [23](#)
 - powered-device detection and initial power allocation [7](#)
 - power management modes [8](#)
 - power negotiation extensions to CDP [7](#)
 - standards supported [7](#)
 - static mode [9](#)
 - supported watts per port [7](#)
 - troubleshooting [11](#)
- policed-DSCP map for QoS [62](#)

- configuring
 - for each matched traffic class [48](#)
 - for more than one traffic class [58](#)
 - described [4](#)
 - displaying [78](#)
 - number of [34](#)
 - types of [9](#)
 - policing
 - described [4](#)
 - hierarchical
 - See hierarchical policy maps
 - token-bucket algorithm [9](#)
 - policy-based routing
 - See PBR
 - policy maps for QoS
 - characteristics of [48](#)
 - described [7](#)
 - displaying [78](#)
 - hierarchical [8](#)
 - hierarchical on SVIs
 - configuration guidelines [33](#)
 - configuring [52](#)
 - described [11](#)
 - nonhierarchical on physical ports
 - configuration guidelines [33](#)
 - described [9](#)
 - port ACLs
 - defined [2](#)
 - types of [3](#)
 - Port Aggregation Protocol
 - See EtherChannel
 - port-based authentication
 - accounting [8](#)
 - authentication server
 - defined [3](#)
 - RADIUS server [3](#)
 - client, defined [2](#)
 - configuration guidelines [26](#)
 - configuring
 - 802.1x authentication [32](#)
 - guest VLAN [40](#)
 - host mode [34](#)
 - inaccessible authentication bypass [43](#)
 - manual re-authentication of a client [36](#)
 - periodic re-authentication [35](#)
 - quiet period [37](#)
 - RADIUS server [34](#)
 - RADIUS server parameters on the switch [33](#)
 - restricted VLAN [41](#)
 - switch-to-client frame-retransmission number [38](#)
 - switch-to-client retransmission time [37](#)
 - violation mode [17](#)
 - violation modes [31](#)
 - default configuration [25](#)
 - described [1](#)
 - device roles [2](#)
 - displaying statistics [52](#)
 - EAPOL-start frame [5](#)
 - EAP-request/identity frame [5](#)
 - EAP-response/identity frame [5](#)
 - encapsulation [3](#)
 - guest VLAN
 - configuration guidelines [13, 14](#)
 - described [12](#)
 - host mode [7](#)
 - inaccessible authentication bypass
 - configuring [43](#)
 - described [14](#)
 - guidelines [27](#)
 - initiation and message exchange [5](#)
 - magic packet [17](#)
 - maximum number of allowed devices per port [28](#)
 - method lists [32](#)
 - multiple-hosts mode, described [8](#)

- per-user ACLs
 - AAA authorization [32](#)
 - configuration tasks [12](#)
 - described [11](#)
 - RADIUS server attributes [12](#)
- ports
 - authorization state and dot1x port-control command [7](#)
 - authorized and unauthorized [7](#)
 - critical [14](#)
 - voice VLAN [15](#)
- port security
 - and voice VLAN [17](#)
 - described [16](#)
 - interactions [16](#)
 - multiple-hosts mode [8](#)
- readiness check
 - configuring [29](#)
 - described [10,29](#)
- resetting to default values [51](#)
- statistics, displaying [52](#)
- switch
 - as proxy [3](#)
 - RADIUS client [3](#)
- upgrading from a previous release [28,26](#)
- VLAN assignment
 - AAA authorization [32](#)
 - characteristics [10](#)
 - configuration tasks [11](#)
 - described [10](#)
- voice aware 802.1x security
 - configuring [30](#)
 - described [20,30](#)
- voice VLAN
 - described [15](#)
 - PVID [15](#)
 - VVID [15](#)
- wake-on-LAN, described [17](#)
- port blocking [4,7](#)
- port-channel
 - See EtherChannel
- port description TLV [2](#)
- Port Fast
 - described [2](#)
 - enabling [10](#)
 - mode, spanning tree [29](#)
 - support for [7](#)
- port membership modes, VLAN [3](#)
- port priority
 - MSTP [19](#)
 - STP [17](#)
- ports
 - access [3](#)
 - blocking [7](#)
 - dual-purpose uplink [6](#)
 - dynamic access [3](#)
 - IEEE 802.1Q tunnel [4](#)
 - protected [6](#)
 - routed [4](#)
 - secure [8](#)
 - static-access [3,11](#)
 - switch [2](#)
 - trunks [3,16](#)
 - VLAN assignments [11](#)
- port security
 - aging [17](#)
 - and private VLANs [18](#)
 - and QoS trusted boundary [38](#)
 - configuring [12](#)
 - default configuration [11](#)
 - described [8](#)
 - displaying [19](#)
 - enabling [18](#)
 - on trunk ports [14](#)
 - sticky learning [9](#)
 - violations [10](#)
 - with other features [11](#)
- port-shutdown response, VMPS [28](#)

- port VLAN ID TLV [2](#)
- power management TLV [2, 6](#)
- Power over Ethernet
 - See PoE
- preemption, default configuration [7](#)
- preemption delay, default configuration [8](#)
- preferential treatment of traffic
 - See QoS
- prefix lists, BGP [53](#)
- preventing unauthorized access [1](#)
- primary interface for object tracking, DHCP, configuring [11](#)
- primary interface for static routing, configuring [10](#)
- primary links [2](#)
- primary VLANs [1, 3](#)
- priority
 - HSRP [7](#)
 - overriding CoS [6](#)
 - trusting CoS [6](#)
- private VLAN edge ports
 - See protected ports
- private VLANs
 - across multiple switches [4](#)
 - and SDM template [4](#)
 - and SVIs [5](#)
 - benefits of [1](#)
 - community ports [2](#)
 - community VLANs [2, 3](#)
 - configuration guidelines [6, 8](#)
 - configuration tasks [6](#)
 - configuring [9](#)
 - default configuration [6](#)
 - end station access to [3](#)
 - IP addressing [3](#)
 - isolated port [2](#)
 - isolated VLANs [2, 3](#)
 - mapping [13](#)
 - monitoring [14](#)
- ports
 - community [2](#)
 - configuration guidelines [8](#)
 - configuring host ports [11](#)
 - configuring promiscuous ports [12](#)
 - described [4](#)
 - isolated [2](#)
 - promiscuous [2](#)
- primary VLANs [1, 3](#)
- promiscuous ports [2](#)
- secondary VLANs [2](#)
- subdomains [1](#)
- traffic in [5](#)
- privileged EXEC mode [2](#)
- privilege levels
 - changing the default for lines [9](#)
 - command switch [15](#)
 - exiting [9](#)
 - logging into [9](#)
 - mapping on member switches [15](#)
 - overview [2, 7](#)
 - setting a command with [8](#)
- promiscuous ports
 - configuring [12](#)
 - defined [2](#)
- protected ports [9, 6](#)
- protocol-dependent modules, EIGRP [34](#)
- Protocol-Independent Multicast Protocol
 - See PIM
- provider edge devices [62](#)
- proxy ARP
 - configuring [10](#)
 - definition [8](#)
 - with IP routing disabled [11](#)
- proxy reports [3](#)

pruning, VTP

- disabling
 - in VTP domain [14](#)
 - on a port [23](#)
- enabling
 - in VTP domain [14](#)
 - on a port [22](#)
- examples [5](#)
- overview [4](#)

pruning-eligible list

- changing [22](#)
- for VTP pruning [4](#)
- VLANs [14](#)

PVST+

- described [9](#)
- IEEE 802.1Q trunking interoperability [10](#)
- instances supported [9](#)

Q

QoS

- and MQC commands [1](#)
- auto-QoS
 - categorizing traffic [20](#)
 - configuration and defaults display [29](#)
 - configuration guidelines [25](#)
 - described [20](#)
 - disabling [27](#)
 - displaying generated commands [27](#)
 - displaying the initial configuration [29](#)
 - effects on running configuration [25](#)
 - egress queue defaults [21](#)
 - enabling for VoIP [27](#)
 - example configuration [28](#)
 - ingress queue defaults [21](#)
 - list of generated commands [22](#)
- basic model [4](#)

classification

- class maps, described [7](#)
- defined [4](#)
- DSCP transparency, described [40](#)
- flowchart [6](#)
- forwarding treatment [3](#)
- in frames and packets [3](#)
- IP ACLs, described [5,7](#)
- MAC ACLs, described [5,7](#)
- options for IP traffic [5](#)
- options for non-IP traffic [5](#)
- policy maps, described [7](#)
- trust DSCP, described [5](#)
- trusted CoS, described [5](#)
- trust IP precedence, described [5](#)

class maps

- configuring [46](#)
- displaying [78](#)

configuration guidelines

- auto-QoS [25](#)
- standard QoS [33](#)

configuring

- aggregate policers [58](#)
- auto-QoS [20](#)
- default port CoS value [38](#)
- DSCP maps [60](#)
- DSCP transparency [40](#)
- DSCP trust states bordering another domain [40](#)
- egress queue characteristics [70](#)
- ingress queue characteristics [66](#)
- IP extended ACLs [44](#)
- IP standard ACLs [43](#)
- MAC ACLs [45](#)
- policy maps, hierarchical [52](#)
- port trust states within the domain [36](#)
- trusted boundary [38](#)

default auto configuration [20](#)default standard configuration [30](#)displaying statistics [78](#)

- DSCP transparency [40](#)
- egress queues
 - allocating buffer space [71](#)
 - buffer allocation scheme, described [17](#)
 - configuring shaped weights for SRR [74](#)
 - configuring shared weights for SRR [75](#)
 - described [4](#)
 - displaying the threshold map [74](#)
 - flowchart [17](#)
 - mapping DSCP or CoS values [73](#)
 - scheduling, described [4](#)
 - setting WTD thresholds [71](#)
 - WTD, described [18](#)
- enabling globally [35](#)
- flowcharts
 - classification [6](#)
 - egress queueing and scheduling [17](#)
 - ingress queueing and scheduling [15](#)
 - policing and marking [10](#)
- implicit deny [7](#)
- ingress queues
 - allocating bandwidth [68](#)
 - allocating buffer space [68](#)
 - buffer and bandwidth allocation, described [16](#)
 - configuring shared weights for SRR [68](#)
 - configuring the priority queue [69](#)
 - described [4](#)
 - displaying the threshold map [67](#)
 - flowchart [15](#)
 - mapping DSCP or CoS values [66](#)
 - priority queue, described [16](#)
 - scheduling, described [4](#)
 - setting WTD thresholds [66](#)
 - WTD, described [16](#)
- IP phones
 - automatic classification and queueing [20](#)
 - detection and trusted settings [20, 38](#)
 - limiting bandwidth on egress interface [77](#)
- mapping tables
 - CoS-to-DSCP [60](#)
 - displaying [78](#)
 - DSCP-to-CoS [63](#)
 - DSCP-to-DSCP-mutation [64](#)
 - IP-precedence-to-DSCP [61](#)
 - policed-DSCP [62](#)
 - types of [12](#)
- marked-down actions [50, 55](#)
- marking, described [4, 8](#)
- overview [2](#)
- packet modification [19](#)
- policers
 - configuring [50, 55, 58](#)
 - described [8](#)
 - displaying [78](#)
 - number of [34](#)
 - types of [9](#)
- policies, attaching to an interface [8](#)
- policing
 - described [4, 8](#)
 - token bucket algorithm [9](#)
- policy maps
 - characteristics of [48](#)
 - displaying [78](#)
 - hierarchical [8](#)
 - hierarchical on SVIs [52](#)
 - nonhierarchical on physical ports [48](#)
- QoS label, defined [4](#)
- queues
 - configuring egress characteristics [70](#)
 - configuring ingress characteristics [66](#)
 - high priority (expedite) [19, 76](#)
 - location of [13](#)
 - SRR, described [14](#)
 - WTD, described [13](#)
- rewrites [19](#)
- support for [11](#)

- trust states
 - bordering another domain [40](#)
 - described [5](#)
 - trusted device [38](#)
 - within the domain [36](#)
- quality of service
 - See QoS
- queries, IGMP [4](#)
- query solicitation, IGMP [13](#)

R

RADIUS

- attributes
 - vendor-proprietary [31](#)
 - vendor-specific [29](#)
- configuring
 - accounting [28](#)
 - authentication [23](#)
 - authorization [27](#)
 - communication, global [21, 29](#)
 - communication, per-server [20, 21](#)
 - multiple UDP ports [20](#)
- default configuration [20](#)
- defining AAA server groups [25](#)
- displaying the configuration [31](#)
- identifying the server [20](#)
- in clusters [14](#)
- limiting the services to the user [27](#)
- method list, defined [19](#)
- operation of [19](#)
- overview [18](#)
- suggested network environments [18](#)
- support for [10](#)
- tracking services accessed by user [28](#)

range

- macro [13](#)
- of interfaces [12](#)

rapid convergence [9](#)

rapid per-VLAN spanning-tree plus

- See rapid PVST+

rapid PVST+

- described [9](#)
- IEEE 802.1Q trunking interoperability [10](#)
- instances supported [9](#)

Rapid Spanning Tree Protocol

- See RSTP

RARP [8](#)

rcommand command [14](#)

RCP

- configuration files
 - downloading [16](#)
 - overview [14](#)
 - preparing the server [15](#)
 - uploading [17](#)
- image files
 - deleting old image [35](#)
 - downloading [33](#)
 - preparing the server [32](#)
 - uploading [35](#)

reachability, tracking IP SLAs IP host [9](#)

readiness check

- port-based authentication
 - configuring [29](#)
 - described [10, 29](#)

reconfirmation interval, VMPS, changing [31](#)

reconfirming dynamic VLAN membership [31](#)

recovery procedures [1](#)

redundancy

- EtherChannel [3](#)
- HSRP [1](#)
- STP
 - backbone [8](#)
 - path cost [26](#)
 - port priority [24](#)

redundant links and UplinkFast [13](#)

reliable transport protocol, EIGRP [34](#)

reloading software [20](#)

- Remote Authentication Dial-In User Service
 - See RADIUS
- Remote Copy Protocol
 - See RCP
- Remote Network Monitoring
 - See RMON
- Remote SPAN
 - See RSPAN
- remote SPAN [2](#)
- report suppression, IGMP
 - described [6](#)
 - disabling [16, 11](#)
- resequencing ACL entries [14](#)
- resets, in BGP [48](#)
- resetting a UDLD-shutdown interface [6](#)
- responder, IP SLAs
 - described [4](#)
 - enabling [8](#)
- response time, measuring with IP SLAs [4](#)
- restricted VLAN
 - configuring [41](#)
 - described [13](#)
 - using with IEEE 802.1x [13](#)
- restricting access
 - NTP services [8](#)
 - overview [1](#)
 - passwords and privilege levels [2](#)
 - RADIUS [17](#)
 - TACACS+ [10](#)
- retry count, VMPS, changing [32](#)
- reverse address resolution [8](#)
- Reverse Address Resolution Protocol
 - See RARP
- RFC
 - 1058, RIP [18](#)
 - 1112, IP multicast and IGMP [2](#)
 - 1157, SNMPv1 [2](#)
 - 1163, BGP [40](#)
 - 1166, IP addresses [5](#)
 - 1253, OSPF [24](#)
 - 1267, BGP [40](#)
 - 1305, NTP [2](#)
 - 1587, NSSAs [24](#)
 - 1757, RMON [2](#)
 - 1771, BGP [40](#)
 - 1901, SNMPv2C [2](#)
 - 1902 to 1907, SNMPv2 [2](#)
 - 2236, IP multicast and IGMP [2](#)
 - 2273-2275, SNMPv3 [2](#)
- RIP
 - advertisements [19](#)
 - authentication [21](#)
 - configuring [20](#)
 - default configuration [19](#)
 - described [19](#)
 - for IPv6 [6](#)
 - hop counts [19](#)
 - split horizon [22](#)
 - summary addresses [22](#)
 - support for [12](#)
- RMON
 - default configuration [3](#)
 - displaying status [6](#)
 - enabling alarms and events [3](#)
 - groups supported [2](#)
 - overview [1](#)
 - statistics
 - collecting group Ethernet [5](#)
 - collecting group history [5](#)
 - support for [14](#)
- root guard
 - described [8](#)
 - enabling [15](#)
 - support for [7](#)
- root switch
 - MSTP [17](#)
 - STP [14](#)
- route calculation timers, OSPF [30](#)

- route dampening, BGP [59](#)
- routed packets, ACLs on [38](#)
- routed ports
 - configuring [3](#)
 - defined [4](#)
 - in switch clusters [8](#)
 - IP addresses on [27, 4](#)
- route-map command [86](#)
- route maps
 - BGP [51](#)
 - policy-based routing [84](#)
- router ACLs
 - defined [2](#)
 - types of [4](#)
- route reflectors, BGP [58](#)
- router ID, OSPF [32](#)
- route selection, BGP [49](#)
- route summarization, OSPF [30](#)
- route targets, VPN [64](#)
- routing
 - default [2](#)
 - dynamic [3](#)
 - redistribution of information [80](#)
 - static [3](#)
- routing domain confederation, BGP [58](#)
- Routing Information Protocol
 - See RIP
- routing protocol administrative distances [79](#)
- RSPAN
 - characteristics [8](#)
 - configuration guidelines [15](#)
 - default configuration [9](#)
 - defined [2](#)
 - destination ports [7](#)
 - displaying status [23](#)
 - interaction with other features [8](#)
 - monitored ports [5](#)
 - monitoring ports [7](#)
 - overview [13, 1](#)
- received traffic [4](#)
- sessions
 - creating [16](#)
 - defined [3](#)
 - limiting source traffic to specific VLANs [22](#)
 - specifying monitored ports [16](#)
 - with ingress traffic enabled [20](#)
- source ports [5](#)
- transmitted traffic [5](#)
- VLAN-based [6](#)
- RSTP
 - active topology [9](#)
 - BPDU
 - format [12](#)
 - processing [12](#)
 - designated port, defined [9](#)
 - designated switch, defined [9](#)
 - interoperability with IEEE 802.1D
 - described [8](#)
 - restarting migration process [25](#)
 - topology changes [13](#)
 - overview [8](#)
 - port roles
 - described [9](#)
 - synchronized [11](#)
 - proposal-agreement handshake process [10](#)
 - rapid convergence
 - described [9](#)
 - edge ports and Port Fast [9](#)
 - point-to-point links [10, 24](#)
 - root ports [10](#)
 - root port, defined [9](#)
 - See also MSTP
- running configuration
 - replacing [18, 19](#)
 - rolling back [18, 19](#)
- running configuration, saving [15](#)

S

- SC (standby command switch) [10](#)
- scheduled reloads [20](#)
- scheduling, IP SLAs operations [5](#)
- SCP
 - and SSH [48](#)
 - configuring [48](#)
- SDM
 - described [1](#)
 - templates
 - configuring [4](#)
 - number of [1](#)
- SDM template [4](#)
 - configuration guidelines [4](#)
 - configuring [3](#)
 - dual IPv4 and IPv6 [2](#)
 - types of [1](#)
- secondary VLANs [2](#)
- Secure Copy Protocol
- secure HTTP client
 - configuring [47](#)
 - displaying [48](#)
- secure HTTP server
 - configuring [46](#)
 - displaying [48](#)
- secure MAC addresses
 - deleting [16](#)
 - maximum number of [10](#)
 - types of [9](#)
- secure ports, configuring [8](#)
- secure remote connections [37](#)
- Secure Shell
 - See SSH
- Secure Socket Layer
 - See SSL
- security, port [8](#)
- security features [8](#)
- See SCP
- sequence numbers in log messages [8](#)
- server mode, VTP [3](#)
- service-provider network, MSTP and RSTP [1](#)
- service-provider networks
 - and customer VLANs [2](#)
 - and IEEE 802.1Q tunneling [1](#)
 - Layer 2 protocols across [8](#)
 - Layer 2 protocol tunneling for EtherChannels [9](#)
- set-request operation [4](#)
- setup program
 - failed command switch replacement [9](#)
 - replacing failed command switch [8](#)
- severity levels, defining in system messages [8](#)
- SFPs
 - monitoring status of [31, 13](#)
 - security and identification [12](#)
 - status, displaying [13](#)
- shaped round robin
 - See SRR
- show access-lists hw-summary command [21](#)
- show and more command output, filtering [10](#)
- show cdp traffic command [5](#)
- show cluster members command [14](#)
- show configuration command [25](#)
- show forward command [20](#)
- show interfaces command [19, 25](#)
- show interfaces switchport [4](#)
- show l2protocol command [13, 15, 16](#)
- show lldp traffic command [7](#)
- show platform forward command [20](#)
- show running-config command
 - displaying ACLs [19, 20, 30, 33](#)
 - interface description in [25](#)
- shutdown command on interfaces [32](#)
- shutdown threshold for Layer 2 protocol packets [11](#)
- Simple Network Management Protocol
 - See SNMP
- small-frame arrival rate, configuring [5](#)

Smartports macros

- applying Cisco-default macros [6](#)
- applying global parameter values [5, 6](#)
- applying macros [5](#)
- applying parameter values [5, 7](#)
- configuration guidelines [2](#)
- creating [4](#)
- default configuration [2](#)
- defined [1](#)
- displaying [8](#)
- tracing [3](#)

SNAP [1](#)

SNMP

- accessing MIB variables with [4](#)
- agent
 - described [3](#)
 - disabling [7](#)
- and IP SLAs [2](#)
- authentication level [10](#)
- community strings
 - configuring [8](#)
 - for cluster switches [4](#)
 - overview [4](#)
- configuration examples [16](#)
- default configuration [6](#)
- engine ID [7](#)
- groups [6, 9](#)
- host [6](#)
- ifIndex values [5](#)
- in-band management [6](#)
- in clusters [14](#)
- informs
 - and trap keyword [11](#)
 - described [5](#)
 - differences from traps [5](#)
 - disabling [15](#)
 - enabling [15](#)
- limiting access by TFTP servers [15](#)
- limiting system log messages to NMS [10](#)

- manager functions [5, 3](#)

- managing clusters with [15](#)

MIBs

- location of [3](#)

- supported [1](#)

- notifications [5](#)

- overview [1, 4](#)

- security levels [3](#)

- status, displaying [17](#)

- system contact and location [15](#)

- trap manager, configuring [13](#)

traps

- described [3, 5](#)

- differences from informs [5](#)

- disabling [15](#)

- enabling [11](#)

- enabling MAC address notification [22](#)

- overview [1, 4](#)

- types of [11](#)

- users [6, 9](#)

- versions supported [2](#)

- SNMP and Syslog Over IPv6 [7](#)

- SNMPv1 [2](#)

- SNMPv2C [2](#)

- SNMPv3 [2](#)

- snooping, IGMP [2](#)

software images

- location in flash [23](#)

- recovery procedures [2](#)

- scheduling reloads [20](#)

- tar file format, described [23](#)

- See also downloading and uploading

source addresses

- in IPv4 ACLs [11](#)

- in IPv6 ACLs [5](#)

- source-and-destination-IP address based forwarding, EtherChannel [7](#)

- source-and-destination MAC address forwarding, EtherChannel [7](#)

- source-IP address based forwarding, EtherChannel [7](#)
- source-MAC address forwarding, EtherChannel [7](#)
- Source-specific multicast
 - See SSM
- SPAN
 - configuration guidelines [10](#)
 - default configuration [9](#)
 - destination ports [7](#)
 - displaying status [23](#)
 - interaction with other features [8](#)
 - monitored ports [5](#)
 - monitoring ports [7](#)
 - overview [13, 1](#)
 - ports, restrictions [12](#)
 - received traffic [4](#)
 - sessions
 - configuring ingress forwarding [14, 21](#)
 - creating [11](#)
 - defined [3](#)
 - limiting source traffic to specific VLANs [14](#)
 - removing destination (monitoring) ports [12](#)
 - specifying monitored ports [11](#)
 - with ingress traffic enabled [13](#)
 - source ports [5](#)
 - transmitted traffic [5](#)
 - VLAN-based [6](#)
- spanning tree and native VLANs [19](#)
- Spanning Tree Protocol
 - See STP
- SPAN traffic [4](#)
- split horizon, RIP [22](#)
- SRR
 - configuring
 - shaped weights on egress queues [74](#)
 - shared weights on egress queues [75](#)
 - shared weights on ingress queues [68](#)
 - described [14](#)
 - shaped mode [14](#)
 - shared mode [14](#)
 - support for [11, 12](#)
- SSH
 - configuring [38](#)
 - cryptographic software image [37](#)
 - described [6, 37](#)
 - encryption methods [38](#)
 - user authentication methods, supported [38](#)
- SSL
 - configuration guidelines [44](#)
 - configuring a secure HTTP client [47](#)
 - configuring a secure HTTP server [45](#)
 - cryptographic software image [41](#)
 - described [41](#)
 - monitoring [48](#)
- SSM
 - address management restrictions [15](#)
 - CGMP limitations [15](#)
 - components [13](#)
 - configuration guidelines [15](#)
 - configuring [13, 16](#)
 - differs from Internet standard multicast [14](#)
 - IGMP snooping [15](#)
 - IGMPv3 [13](#)
 - IGMPv3 Host Signalling [15](#)
 - IP address range [14](#)
 - monitoring [16](#)
 - operations [14](#)
 - PIM [13](#)
 - state maintenance limitations [16](#)
- SSM mapping [16](#)
 - configuration guidelines [17](#)
 - configuring [16, 19](#)
 - DNS-based [18, 20](#)
 - monitoring [21](#)
 - overview [17](#)
 - restrictions [17](#)
 - static [18, 19](#)
 - static traffic forwarding [20](#)

- standby command switch
 - configuring
 - considerations [11](#)
 - defined [2](#)
 - priority [10](#)
 - requirements [3](#)
 - virtual IP address [11](#)
 - See also cluster standby group and HSRP
- standby group, cluster
 - See cluster standby group and HSRP
- standby ip command [6](#)
- standby links [2](#)
- standby router [1](#)
- standby timers, HSRP [10](#)
- startup configuration
 - booting
 - manually [17](#)
 - specific image [18](#)
 - clearing [18](#)
 - configuration file
 - automatically downloading [16](#)
 - specifying the filename [16](#)
 - default boot configuration [16](#)
- static access ports
 - assigning to VLAN [11](#)
 - defined [3](#)
- static addresses
 - See addresses
- static IP routing [12](#)
- static MAC addressing [9](#)
- static route primary interface,configuring [10](#)
- static routes
 - configuring [78](#)
 - configuring for IPv6 [20](#)
 - understanding [6](#)
- static routing [3](#)
- static routing support, enhanced object tracking [10](#)
- static SSM mapping [18,19](#)
- static traffic forwarding [20](#)
- static VLAN membership [2](#)
- statistics
 - 802.1x [52](#)
 - CDP [4](#)
 - interface [30](#)
 - IP multicast routing [61](#)
 - LLDP [7](#)
 - LLDP-MED [7](#)
 - OSPF [32](#)
 - QoS ingress and egress [78](#)
 - RMON group Ethernet [5](#)
 - RMON group history [5](#)
 - SNMP input and output [17](#)
 - VTP [16](#)
- sticky learning [9](#)
- storm control
 - configuring [3](#)
 - described [1](#)
 - disabling [5](#)
 - displaying [19](#)
 - support for [4](#)
 - thresholds [1](#)
- STP
 - accelerating root port selection [4](#)
 - BackboneFast
 - described [5](#)
 - disabling [14](#)
 - enabling [13](#)
 - BPDU filtering
 - described [3](#)
 - disabling [12](#)
 - enabling [12](#)
 - BPDU guard
 - described [2](#)
 - disabling [12](#)
 - enabling [11](#)
 - BPDU message exchange [3](#)
 - configuration guidelines [12,10](#)

- configuring
 - forward-delay time [21](#)
 - hello time [20](#)
 - maximum aging time [21](#)
 - path cost [18](#)
 - port priority [17](#)
 - root switch [14](#)
 - secondary root switch [16](#)
 - spanning-tree mode [13](#)
 - switch priority [19](#)
 - transmit hold-count [22](#)
- counters, clearing [22](#)
- default configuration [11](#)
- default optional feature configuration [9](#)
- designated port, defined [3](#)
- designated switch, defined [3](#)
- detecting indirect link failures [5](#)
- disabling [14](#)
- displaying status [22](#)
- EtherChannel guard
 - described [7](#)
 - disabling [14](#)
 - enabling [14](#)
- extended system ID
 - effects on root switch [14](#)
 - effects on the secondary root switch [16](#)
 - overview [4](#)
 - unexpected behavior [15](#)
- features supported [7](#)
- IEEE 802.1D and bridge ID [4](#)
- IEEE 802.1D and multicast addresses [8](#)
- IEEE 802.1t and VLAN identifier [4](#)
- inferior BPDU [3](#)
- instances supported [9](#)
- interface state, blocking to forwarding [2](#)
- interface states
 - blocking [5](#)
 - disabled [7](#)
 - forwarding [5, 6](#)
 - learning [6](#)
 - listening [6](#)
 - overview [4](#)
- interoperability and compatibility among modes [10](#)
- keepalive messages [2](#)
- Layer 2 protocol tunneling [7](#)
- limitations with IEEE 802.1Q trunks [10](#)
- load sharing
 - overview [24](#)
 - using path costs [26](#)
 - using port priorities [24](#)
- loop guard
 - described [9](#)
 - enabling [15](#)
- modes supported [9](#)
- multicast addresses, effect of [8](#)
- optional features supported [7](#)
- overview [2](#)
- path costs [26](#)
- Port Fast
 - described [2](#)
 - enabling [10](#)
- port priorities [25](#)
- preventing root switch selection [8](#)
- protocols supported [9](#)
- redundant connectivity [8](#)
- root guard
 - described [8](#)
 - enabling [15](#)
- root port, defined [3](#)
- root switch
 - configuring [15](#)
 - effects of extended system ID [4, 14](#)
 - election [3](#)
 - unexpected behavior [15](#)
- shutdown Port Fast-enabled port [2](#)
- status, displaying [22](#)
- superior BPDU [3](#)
- timers, described [20](#)
- shutdown Port Fast-enabled port [2](#)
- status, displaying [22](#)
- superior BPDU [3](#)
- timers, described [20](#)

- UplinkFast
 - described [3](#)
 - enabling [13](#)
 - VLAN-bridge [10](#)
- stratum, NTP [2](#)
- stub areas, OSPF [28](#)
- stub routing, EIGRP [39](#)
- subdomains, private VLAN [1](#)
- subnet mask [5](#)
- subnet zero [6](#)
- success response, VMPS [28](#)
- summer time [13](#)
- SunNet Manager [5](#)
- supernet [6](#)
- supported watts per port [7](#)
- SVI autostate exclude
 - configuring [28](#)
 - defined [5](#)
- SVI link state [5](#)
- SVIs
 - and IP unicast routing [3](#)
 - and router ACLs [4](#)
 - connecting VLANs [9](#)
 - defined [4](#)
 - routing between VLANs [2](#)
- switch [2](#)
- switch clustering technology [1](#)
 - See also clusters, switch
- switch console port [6](#)
- Switch Database Management
 - See SDM
- switched packets, ACLs on [37](#)
- Switched Port Analyzer
 - See SPAN
- switched ports [2](#)
- switchport backup interface [4, 5](#)
- switchport block multicast command [8](#)
- switchport block unicast command [8](#)
- switchport command [15](#)
- switchport mode dot1q-tunnel command [6](#)
- switchport protected command [7](#)
- switch priority
 - MSTP [21](#)
 - STP [19](#)
- switch software features [1](#)
- switch virtual interface
 - See SVI
- synchronization, BGP [45](#)
- syslog
 - See system message logging
- system capabilities TLV [2](#)
- system clock
 - configuring
 - daylight saving time [13](#)
 - manually [11](#)
 - summer time [13](#)
 - time zones [12](#)
 - displaying the time and date [12](#)
 - overview [1](#)
 - See also NTP
- system description TLV [2](#)
- system message logging
 - default configuration [3](#)
 - defining error message severity levels [8](#)
 - disabling [4](#)
 - displaying the configuration [13](#)
 - enabling [4](#)
 - facility keywords, described [13](#)
 - level keywords, described [9](#)
 - limiting messages [10](#)
 - message format [2](#)
 - overview [1](#)
 - sequence numbers, enabling and disabling [8](#)
 - setting the display destination device [5](#)
 - synchronizing log messages [6](#)
 - syslog facility [14](#)
 - time stamps, enabling and disabling [7](#)

- UNIX syslog servers
 - configuring the daemon [12](#)
 - configuring the logging facility [12](#)
 - facilities supported [13](#)
- system MTU and IEEE 802.1Q tunneling [5](#)
- system name
 - default configuration [15](#)
 - default setting [15](#)
 - manual configuration [15](#)
 - See also DNS
- system name TLV [2](#)
- system prompt, default setting [14, 15](#)
- system resources, optimizing [1](#)

T

- TACACS+
 - accounting, defined [11](#)
 - authentication, defined [11](#)
 - authorization, defined [11](#)
 - configuring
 - accounting [17](#)
 - authentication key [13](#)
 - authorization [16](#)
 - login authentication [14](#)
 - default configuration [13](#)
 - displaying the configuration [17](#)
 - identifying the server [13](#)
 - in clusters [14](#)
 - limiting the services to the user [16](#)
 - operation of [12](#)
 - overview [10](#)
 - support for [10](#)
 - tracking services accessed by user [17](#)
- tagged packets
 - IEEE 802.1Q [3](#)
 - Layer 2 protocol [7](#)
- tar files
 - creating [5](#)
 - displaying the contents of [5](#)
 - extracting [6](#)
 - image file format [23](#)
- TCL script, registering and defining with embedded event manager [6](#)
- TDR [14](#)
- Telnet
 - accessing management interfaces [10](#)
 - number of connections [6](#)
 - setting a password [6](#)
- templates, SDM [1](#)
- temporary self-signed certificate [42](#)
- Terminal Access Controller Access Control System Plus
 - See TACACS+
- terminal lines, setting a password [6](#)
- TFTP
 - configuration files
 - downloading [10](#)
 - preparing the server [9](#)
 - uploading [10](#)
 - configuration files in base directory [7](#)
 - configuring for autoconfiguration [7](#)
 - image files
 - deleting [26](#)
 - downloading [25](#)
 - preparing the server [24](#)
 - uploading [27](#)
 - limiting access by servers [15](#)
- TFTP server [5](#)
- threshold, traffic level [2](#)
- threshold monitoring, IP SLAs [6](#)
- time
 - See NTP and system clock
- Time Domain Reflector
 - See TDR
- time-range command [16](#)
- time ranges in ACLs [16](#)

- time stamps in log messages [7](#)
- time zones [12](#)
- TLVs
 - defined [2](#)
 - LLDP [2](#)
 - LLDP-MED [2](#)
- Token Ring VLANs
 - support for [6](#)
 - VTP support [4](#)
- ToS [11](#)
- traceroute, Layer 2
 - and ARP [15](#)
 - and CDP [15](#)
 - broadcast traffic [15](#)
 - described [15](#)
 - IP addresses and subnets [15](#)
 - MAC addresses and VLANs [15](#)
 - multicast traffic [15](#)
 - multiple devices on a port [16](#)
 - unicast traffic [15](#)
 - usage guidelines [15](#)
- traceroute command [17](#)
 - See also IP traceroute
- tracked lists
 - configuring [3](#)
 - types [3](#)
- tracked objects
 - by Boolean expression [4](#)
 - by threshold percentage [6](#)
 - by threshold weight [5](#)
- tracking interface line-protocol state [2](#)
- tracking IP routing state [2](#)
- tracking objects [1](#)
- tracking process [1](#)
- track state, tracking IP SLAs [9](#)
- traffic
 - blocking flooded [8](#)
 - fragmented [5](#)
 - fragmented IPv6 [2](#)
 - unfragmented [5](#)
- traffic policing [11](#)
- traffic suppression [1](#)
- transmit hold-count
 - see STP
- transparent mode, VTP [3, 12](#)
- trap-door mechanism [2](#)
- traps
 - configuring MAC address notification [22](#)
 - configuring managers [11](#)
 - defined [3](#)
 - enabling [22, 11](#)
 - notification types [11](#)
 - overview [1, 4](#)
- troubleshooting
 - connectivity problems [13, 14, 16](#)
 - CPU utilization [24](#)
 - detecting unidirectional links [1](#)
 - displaying crash information [23](#)
 - PIMv1 and PIMv2 interoperability problems [34](#)
 - setting packet forwarding [20](#)
 - SFP security and identification [12](#)
 - show forward command [20](#)
 - with CiscoWorks [4](#)
 - with debug commands [19](#)
 - with ping [13](#)
 - with system message logging [1](#)
 - with traceroute [16](#)
- trunk failover
 - See link-state tracking
- trunking encapsulation [8](#)
- trunk ports
 - configuring [20](#)
 - defined [3](#)
 - encapsulation [20, 25, 26](#)

- trunks
 - allowed-VLAN list [21](#)
 - configuring [20, 25, 26](#)
 - ISL [16](#)
 - load sharing
 - setting STP path costs [26](#)
 - using STP port priorities [24, 25](#)
 - native VLAN for untagged traffic [23](#)
 - parallel [26](#)
 - pruning-eligible list [22](#)
 - to non-DTP device [17](#)
- trusted boundary for QoS [38](#)
- trusted port states
 - between QoS domains [40](#)
 - classification options [5](#)
 - ensuring port security for IP phones [38](#)
 - support for [11](#)
 - within a QoS domain [36](#)
- trustpoints, CA [42](#)
- tunneling
 - defined [1](#)
 - IEEE 802.1Q [1](#)
 - Layer 2 protocol [8](#)
- tunnel ports
 - defined [4](#)
 - described [3, 1](#)
 - IEEE 802.1Q, configuring [6](#)
 - incompatibilities with other features [6](#)
- twisted-pair Ethernet, detecting unidirectional links [1](#)
- type of service
 - See ToS
- disabling
 - globally [5](#)
 - on fiber-optic interfaces [5](#)
 - per interface [5](#)
- echoing detection mechanism [2](#)
- enabling
 - globally [5](#)
 - per interface [5](#)
- Layer 2 protocol tunneling [10](#)
- link-detection mechanism [1](#)
- neighbor database [2](#)
- overview [1](#)
- resetting an interface [6](#)
- status, displaying [6](#)
- support for [7](#)
- UDP, configuring [14](#)
- UDP jitter, configuring [9](#)
- UDP jitter operation, IP SLAs [8](#)
- unauthorized ports with IEEE 802.1x [7](#)
- unicast MAC address filtering [5](#)
 - and adding static addresses [25](#)
 - and broadcast MAC addresses [25](#)
 - and CPU packets [25](#)
 - and multicast addresses [25](#)
 - and router MAC addresses [25](#)
 - configuration guidelines [25](#)
 - described [25](#)
- unicast storm [1](#)
- unicast storm control command [4](#)
- unicast traffic, blocking [8](#)
- UniDirectional Link Detection protocol
 - See UDLD
- UNIX syslog servers
 - daemon configuration [12](#)
 - facilities supported [13](#)
 - message logging configuration [12](#)
- unrecognized Type-Length-Value (TLV) support [4](#)
- upgrading software images
 - See downloading

U

UDLD

- configuration guidelines [4](#)
- default configuration [4](#)

UplinkFast

- described [3](#)
- disabling [13](#)
- enabling [13](#)
- support for [7](#)

uploading

- configuration files
 - preparing [9, 12, 15](#)
 - reasons for [7](#)
 - using FTP [13](#)
 - using RCP [17](#)
 - using TFTP [10](#)
- image files
 - preparing [24, 28, 32](#)
 - reasons for [22](#)
 - using FTP [30](#)
 - using RCP [35](#)
 - using TFTP [27](#)

User Datagram Protocol

See UDP

- user EXEC mode [2](#)
- username-based authentication [6](#)

Vversion-dependent transparent mode [4](#)

virtual IP address

- cluster standby group [11](#)
- command switch [11](#)

Virtual Private Network

See VPN

virtual router [1, 2](#)virtual switches and PAgP [5](#)vlan.dat file [5](#)VLAN 1, disabling on a trunk port [22](#)VLAN 1 minimization [21](#)

VLAN ACLs

See VLAN maps

vlan-assignment response, VMPS [28](#)

VLAN configuration

- at bootup [8](#)
- saving [8](#)

VLAN configuration mode [2, 7](#)

VLAN database

- and startup configuration file [8](#)
- and VTP [1](#)
- VLAN configuration saved in [7](#)
- VLANs saved in [4](#)

vlan database command [7](#)vlan dot1q tag native command [5](#)VLAN filtering and SPAN [6](#)vlan global configuration command [7](#)VLAN ID, discovering [27](#)VLAN link state [5](#)VLAN load balancing on flex links [2](#)

- configuration guidelines [8](#)

VLAN management domain [2](#)

VLAN Management Policy Server

See VMPS

VLAN map entries, order of [29](#)

VLAN maps

- applying [33](#)
- common uses for [33](#)
- configuration guidelines [29](#)
- configuring [28](#)
- creating [30](#)
- defined [2](#)
- denying access to a server example [34](#)
- denying and permitting packets [30](#)
- displaying [40](#)
- examples of ACLs and VLAN maps [31](#)
- removing [33](#)
- support for [9](#)
- wiring closet configuration example [34](#)

VLAN membership

- confirming [31](#)
- modes [3](#)

VLAN Query Protocol

See VQP

VLANs

- adding 9
- adding to VLAN database 9
- aging dynamic addresses 9
- allowed on trunk 21
- and spanning-tree instances 3, 6, 13
- configuration guidelines, extended-range VLANs 13
- configuration guidelines, normal-range VLANs 6
- configuration options 7
- configuring 1
- configuring IDs 1006 to 4094 13
- connecting through SVIs 9
- creating in config-vlan mode 9
- creating in VLAN configuration mode 10
- customer numbering in service-provider networks 3
- default configuration 8
- deleting 10
- described 2, 1
- displaying 16
- extended-range 1, 12
- features 8
- illustrated 2
- internal 13
- limiting source traffic with RSPAN 22
- limiting source traffic with SPAN 14
- modifying 9
- multicast 17
- native, configuring 23
- normal-range 1, 4
- number supported 8
- parameters 5
- port membership modes 3
- static-access ports 11
- STP and IEEE 802.1Q trunks 10
- supported 2
- Token Ring 6
- traffic between 2

VLAN-bridge STP 10, 2

VTP modes 3

VLAN Trunking Protocol

See VTP

VLAN trunks 16

VMPS

- administering 32
- configuration example 33
- configuration guidelines 29
- default configuration 29
- description 27
- dynamic port membership
 - described 28
 - reconfirming 31
 - troubleshooting 33
- entering server address 30
- mapping MAC addresses to VLANs 28
- monitoring 32
- reconfirmation interval, changing 31
- reconfirming membership 31
- retry count, changing 32
- voice aware 802.1x security
 - port-based authentication
 - configuring 30
 - described 20, 30

voice-over-IP 1

voice VLAN

- Cisco 7960 phone, port connections 1
- configuration guidelines 3
- configuring IP phones for data traffic
 - override CoS of incoming frame 6
 - trust CoS priority of incoming frame 6
- configuring ports for voice traffic in
 - 802.1p priority tagged frames 5
 - 802.1Q frames 5
- connecting to an IP phone 4
- default configuration 3
- described 1
- displaying 7

- IP phone data traffic, described [2](#)
- IP phone voice traffic, described [2](#)
- VPN
 - configuring routing in [70](#)
 - forwarding [64](#)
 - in service provider networks [61](#)
 - routes [62](#)
- VPN routing and forwarding table
 - See VRF
- VQP [8,27](#)
- VRF
 - defining [64](#)
 - tables [61](#)
- VRF-aware services
 - ARP [67](#)
 - configuring [67](#)
 - ftp [70](#)
 - HSRP [68](#)
 - ping [68](#)
 - SNMP [68](#)
 - syslog [69](#)
 - tftp [70](#)
 - traceroute [70](#)
 - uRPF [69](#)
- VTP
 - adding a client to a domain [14](#)
 - advertisements [19,3](#)
 - and extended-range VLANs [1](#)
 - and normal-range VLANs [1](#)
 - client mode, configuring [11](#)
 - configuration
 - global configuration mode [7](#)
 - guidelines [8](#)
 - privileged EXEC mode [7](#)
 - requirements [9](#)
 - saving [7](#)
 - VLAN configuration mode [7](#)
 - configuration mode options [7](#)
 - configuration requirements [9](#)
 - configuration revision number
 - guideline [14](#)
 - resetting [15](#)
 - configuring
 - client mode [11](#)
 - server mode [9](#)
 - transparent mode [12](#)
 - consistency checks [4](#)
 - default configuration [6](#)
 - described [1](#)
 - disabling [12](#)
 - domain names [8](#)
 - domains [2](#)
 - Layer 2 protocol tunneling [8](#)
 - modes
 - client [3,11](#)
 - server [3,9](#)
 - transitions [3](#)
 - transparent [3,12](#)
 - monitoring [16](#)
 - passwords [8](#)
 - pruning
 - disabling [14](#)
 - enabling [14](#)
 - examples [5](#)
 - overview [4](#)
 - support for [8](#)
 - pruning-eligible list, changing [22](#)
 - server mode, configuring [9](#)
 - statistics [16](#)
 - support for [8](#)
 - Token Ring support [4](#)
 - transparent mode, configuring [12](#)
 - using [1](#)
 - version, guidelines [8](#)
 - Version 1 [4](#)

Version 2

- configuration guidelines [8](#)
- disabling [13](#)
- enabling [13](#)
- overview [4](#)

W

WCCP

- authentication [3](#)
- configuration guidelines [5](#)
- default configuration [5](#)
- described [1](#)
- displaying [9](#)
- dynamic service groups [3](#)
- enabling [6](#)
- features unsupported [4](#)
- forwarding method [3](#)
- Layer-2 header rewrite [3](#)
- MD5 security [3](#)
- message exchange [2](#)
- monitoring and maintaining [9](#)
- negotiation [3](#)
- packet redirection [3](#)
- packet-return method [3](#)
- redirecting traffic received from a client [6](#)
- setting the password [6](#)
- unsupported WCCPv2 features [4](#)

web authentication [10](#)

- configuring [47 to 50, 50 to ??](#)
- described [8, 21](#)
- fallback for IEEE 802.1x [49](#)

Web Cache Communication Protocol

See WCCP

weighted tail drop

See WTD

weight thresholds in tracked lists [5](#)wireless access point, Cisco AP1250 [7](#)wizards [3](#)

WTD

- described [13](#)
- setting thresholds
 - egress queue-sets [71](#)
 - ingress queues [66](#)
- support for [11, 12](#)

XXmodem protocol [2](#)

